



Enterprise PeopleTools 8.45 PeopleBook: SQR Language Reference for PeopleSoft

June 2004

Enterprise PeopleTools 8.45 PeopleBook: SQR Language Reference for PeopleSoft SKU PT845SQL-B 0604

Copyright © 1988-2004 PeopleSoft, Inc. All rights reserved.

All material contained in this documentation is proprietary and confidential to PeopleSoft, Inc. ("PeopleSoft"), protected by copyright laws and subject to the nondisclosure provisions of the applicable PeopleSoft agreement. No part of this documentation may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, including, but not limited to, electronic, graphic, mechanical, photocopying, recording, or otherwise without the prior written permission of PeopleSoft.

This documentation is subject to change without notice, and PeopleSoft does not warrant that the material contained in this documentation is free of errors. Any errors found in this document should be reported to PeopleSoft in writing.

The copyrighted software that accompanies this document is licensed for use only in strict accordance with the applicable license agreement which should be read carefully as it governs the terms of use of the software and this document, including the disclosure thereof.

PeopleSoft, PeopleTools, PS/nVision, PeopleCode, PeopleBooks, PeopleTalk, and Vantive are registered trademarks, and Pure Internet Architecture, Intelligent Context Manager, and The Real-Time Enterprise are trademarks of PeopleSoft, Inc. All other company and product names may be trademarks of their respective owners. The information contained herein is subject to change without notice.

Open Source Disclosure

PeopleSoft takes no responsibility for its use or distribution of any open source or shareware software or documentation and disclaims any and all liability or damages resulting from use of said software or documentation. The following open source software may be used in PeopleSoft products and the following disclaimers are provided.

Apache Software Foundation

This product includes software developed by the Apache Software Foundation (<http://www.apache.org/>). Copyright (c) 1999-2000 The Apache Software Foundation. All rights reserved.

THIS SOFTWARE IS PROVIDED "AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE APACHE SOFTWARE FOUNDATION OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

OpenSSL

Copyright (c) 1998-2003 The OpenSSL Project. All rights reserved.

THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT "AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE OpenSSL PROJECT OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

SSLey

Copyright (c) 1995-1998 Eric Young. All rights reserved.

THIS SOFTWARE IS PROVIDED BY ERIC YOUNG "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Loki Library

Copyright (c) 2001 by Andrei Alexandrescu. This code accompanies the book:

Alexandrescu, Andrei. "Modern C++ Design: Generic Programming and Design Patterns Applied". Copyright (c) 2001. Addison-Wesley. Permission to use, copy, modify, distribute and sell this software for any purpose is hereby granted without fee, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation.

Contents

General Preface

About This PeopleBook	.xi
PeopleSoft Application Prerequisites.....	.xi
PeopleSoft Application Fundamentals.....	.xi
Related Documentation.....	.xii
Obtaining Documentation Updates.....	.xii
Ordering Printed Documentation.....	.xii
Typographical Conventions and Visual Cues.....	.xiii
Typographical Conventions.....	.xiii
Visual Cues.....	.xiv
Country, Region, and Industry Identifiers.....	.xiv
Currency Codes.....	.xv
Comments and Suggestions.....	.xv
Common Elements in These PeopleBooks	.xv

Preface

SQR Language Reference for PeopleSoft Preface.....	.xvii
SQR Language Reference for PeopleSoft.....	.xvii

Chapter 1

Understanding SQR for PeopleSoft.....	1
SQR for PeopleSoft Tools.....	1
The SQR Language.....	1
Understanding the SQR Language.....	2
SQR Program Structure.....	2
SQR Syntax Conventions.....	3
Rules for Entering SQR Commands.....	4
SQR Command Line.....	4
SQR Command-Line Arguments.....	4
SQR Command-Line Flags.....	5
SQR Data Elements.....	15
Columns.....	15
Variables.....	15

Literals.....	19
Sample Reports.....	20

Chapter 2

SQR Command Reference.....	21
SQR Command Overview.....	21
SQR Commands.....	22
ADD.....	22
ALTER-COLOR-MAP.....	23
ALTER-LOCALE.....	25
ALTER-PRINTER.....	32
ALTER-REPORT.....	33
ARRAY-ADD, ARRAY-DIVIDE, ARRAY-MULTIPLY, ARRAY-SUBTRACT.....	34
ASK.....	36
BEGIN-DOCUMENT.....	37
BEGIN-EXECUTE.....	38
BEGIN-FOOTING.....	40
BEGIN-HEADING.....	42
BEGIN-PROCEDURE.....	43
BEGIN-PROGRAM.....	45
BEGIN-SELECT.....	46
BEGIN-SETUP.....	48
BEGIN-SQL.....	49
BREAK.....	52
CALL, CALL SYSTEM.....	52
CLEAR-ARRAY.....	56
CLOSE.....	57
COLUMNS.....	57
COMMIT.....	58
CONCAT.....	59
CONNECT.....	60
CREATE-ARRAY.....	61
CREATE-COLOR-PALETTE.....	62
#DEBUG.....	63
DECLARE-CHART.....	64
DECLARE-COLOR-MAP.....	73
DECLARE-CONNECTION.....	74
DECLARE-IMAGE.....	75
DECLARE-LAYOUT.....	76

DECLARE-PRINTER.....	84
DECLARE-PROCEDURE.....	93
DECLARE-REPORT.....	94
DECLARE-TOC.....	96
DECLARE-VARIABLE.....	98
#DEFINE.....	100
DISPLAY.....	102
DIVIDE.....	105
DO.....	106
#ELSE.....	107
ELSE.....	107
ENCODE.....	107
END-DECLARE, END-DOCUMENT, END-EVALUATE, END-FOOTING, END-HEADING.....	108
#END-IF, #ENDIF.....	108
END-IF.....	109
END-PROCEDURE, END-PROGRAM, END-SELECT, END-SETUP, END-SQL, END-WHILE.....	109
EVALUATE.....	110
EXECUTE (Sybase and Microsoft SQL Server).....	112
EXIT-SELECT.....	114
EXTRACT.....	114
FIND.....	116
GET.....	117
GET-COLOR.....	117
GOTO.....	119
GRAPHIC BOX, GRAPHIC HORZ-LINE, GRAPHIC VERT-LINE.....	120
#IF.....	122
IF.....	123
#IFDEF.....	125
#IFNDEF.....	125
#INCLUDE.....	126
INPUT.....	126
LAST-PAGE.....	129
LET.....	130
LOAD-LOOKUP.....	159
LOOKUP.....	163
LOWERCASE.....	163
MBTOSBS.....	164
MOVE.....	164
MULTIPLY.....	168
NEW-PAGE.....	169

NEW-REPORT.....	169
NEXT-COLUMN.....	170
NEXT-LISTING.....	171
OPEN.....	172
PAGE-NUMBER.....	174
POSITION.....	175
PRINT.....	175
PRINT-BAR-CODE.....	194
PRINT-CHART.....	197
PRINT-DIRECT.....	201
PRINT-IMAGE.....	202
PUT.....	203
READ.....	204
ROLLBACK.....	206
SBTOMBS.....	206
SECURITY.....	207
SET-COLOR.....	208
SET-GENERATIONS.....	210
SET-LEVELS.....	210
SET-MEMBERS.....	211
SHOW.....	211
STOP.....	215
STRING.....	215
SUBTRACT.....	216
TOC-ENTRY.....	217
UNSTRING.....	217
UPPERCASE.....	218
USE.....	219
USE-COLUMN.....	219
USE-PRINTER-TYPE.....	220
USE-PROCEDURE.....	220
USE-REPORT.....	222
WHILE.....	223
WRITE.....	224

Chapter 3

Generating HTML Output.....	227
HTML General Purpose Procedures.....	227
HTML Heading Procedures.....	231

HTML Highlighting Procedures.....	234
HTML Hypertext Link Procedures.....	238
HTML List Procedures.....	239
HTML Table Procedures.....	243

Chapter 4

Invoking SQR Execute.....	247
Running SQR Execute.....	247
Using SQR Execute Flags.....	247

Chapter 5

Using SQR Print.....	255
Understanding SQR Print.....	255
Generating Output from the Command Line.....	255
Using SQR Print Command-Line Flags.....	256
Generating Output in Microsoft Windows.....	260

Chapter 6

Avoiding Older SQR Commands.....	261
Understanding Older SQR Commands.....	261
Using Older SQR Commands.....	262
BEGIN-REPORT.....	262
DATE-TIME.....	262
DECLARE PRINTER.....	264
DECLARE PROCEDURE.....	269
DOLLAR-SYMBOL.....	270
GRAPHIC FONT.....	271
MONEY-SYMBOL.....	272
NO-FORMFEED.....	273
PAGE-SIZE.....	274
PRINT ... CODE.....	275
PRINTER-DEINIT.....	275
PRINTER-INIT.....	276

Chapter 7

Using the PSSQR.INI File and the PSSQR Command Line.....	277
Installing PSSQR.INI.....	277
Default Settings Section.....	278
Processing-Limits Section.....	284
Environment Sections.....	286
Locale Section.....	287
Fonts Section.....	290
Adding Fonts Entries.....	290
Specifying Character Sets in Windows.....	291
HTML-Images Section.....	291
PDF Fonts Section.....	292
PDF Fonts: Exclusion Ranges Section.....	294
TrueType Fonts Section.....	294
Enhanced-HTML Section.....	295
Colors Section.....	296
Using PSSQR.EXE Command-Line Options.....	296

Chapter 8

Understanding SQR Messages.....	301
Unnumbered Messages.....	301
Numbered Messages.....	304

Appendix A

Using SQR Sample Programs.....	409
Understanding SQR Samples.....	409
SQR Sample Programs.....	409

Appendix B

ISO Country and Currency Codes.....	415
ISO Country Codes.....	415
ISO Currency Codes.....	424

Glossary of PeopleSoft Terms.....435

Index 451

About This PeopleBook

PeopleBooks provide you with the information that you need to implement and use PeopleSoft applications.

This preface discusses:

- PeopleSoft application prerequisites.
- PeopleSoft application fundamentals.
- Related documentation.
- Typographical conventions and visual cues.
- Comments and suggestions.
- Common elements in PeopleBooks.

Note. PeopleBooks document only page elements that require additional explanation. If a page element is not documented with the process or task in which it is used, then either it requires no additional explanation or it is documented with common elements for the section, chapter, PeopleBook, or product line. Elements that are common to all PeopleSoft applications are defined in this preface.

PeopleSoft Application Prerequisites

To benefit fully from the information that is covered in these books, you should have a basic understanding of how to use PeopleSoft applications.

See *Enterprise PeopleTools 8.45 PeopleBook: Using PeopleSoft Applications*.

You might also want to complete at least one PeopleSoft introductory training course.

You should be familiar with navigating the system and adding, updating, and deleting information by using PeopleSoft windows, menus, and pages. You should also be comfortable using the World Wide Web and the Microsoft Windows or Windows NT graphical user interface.

These books do not review navigation and other basics. They present the information that you need to use the system and implement your PeopleSoft applications most effectively.

PeopleSoft Application Fundamentals

Each application PeopleBook provides implementation and processing information for your PeopleSoft database. However, additional, essential information describing the setup and design of your system appears in a companion volume of documentation called the application fundamentals PeopleBook. Each PeopleSoft product line has its own version of this documentation.

The application fundamentals PeopleBook consists of important topics that apply to many or all PeopleSoft applications across a product line. Whether you are implementing a single application, some combination of applications within the product line, or the entire product line, you should be familiar with the contents of this central PeopleBook. It is the starting point for fundamentals, such as setting up control tables and administering security.

Related Documentation

This section discusses how to:

- Obtain documentation updates.
- Order printed documentation.

Obtaining Documentation Updates

You can find updates and additional documentation for this release, as well as previous releases, on the PeopleSoft Customer Connection website. Through the Documentation section of PeopleSoft Customer Connection, you can download files to add to your PeopleBook Library. You'll find a variety of useful and timely materials, including updates to the full PeopleSoft documentation that is delivered on your PeopleBooks CD-ROM.

Important! Before you upgrade, you must check PeopleSoft Customer Connection for updates to the upgrade instructions. PeopleSoft continually posts updates as the upgrade process is refined.

See Also

PeopleSoft Customer Connection, <https://www.peoplesoft.com/corp/en/login.jsp>

Ordering Printed Documentation

You can order printed, bound volumes of the complete PeopleSoft documentation that is delivered on your PeopleBooks CD-ROM. PeopleSoft makes printed documentation available for each major release shortly after the software is shipped. Customers and partners can order printed PeopleSoft documentation by using any of these methods:

- Web
- Telephone
- Email

Web

From the Documentation section of the PeopleSoft Customer Connection website, access the PeopleBooks Press website under the Ordering PeopleBooks topic. The PeopleBooks Press website is a joint venture between PeopleSoft and MMA Partners, the book print vendor. Use a credit card, money order, cashier's check, or purchase order to place your order.

Telephone

Contact MMA Partners at 877 588 2525.

Email

Send email to MMA Partners at peoplesoftpress@mmapartner.com.

See Also

PeopleSoft Customer Connection, <https://www.peoplesoft.com/corp/en/login.jsp>

Typographical Conventions and Visual Cues

This section discusses:

- Typographical conventions.
- Visual cues.
- Country, region, and industry identifiers.
- Currency codes.

Typographical Conventions

This table contains the typographical conventions that are used in PeopleBooks:

Typographical Convention or Visual Cue	Description
Bold	Indicates PeopleCode function names, method names, language constructs, and PeopleCode reserved words that must be included literally in the function call.
<i>Italics</i>	Indicates field values, emphasis, and PeopleSoft or other book-length publication titles. In PeopleCode syntax, italic items are placeholders for arguments that your program must supply. We also use italics when we refer to words as words or letters as letters, as in the following: Enter the letter <i>O</i> .
KEY+KEY	Indicates a key combination action. For example, a plus sign (+) between keys means that you must hold down the first key while you press the second key. For ALT+W, hold down the ALT key while you press the W key.
Monospace font	Indicates a PeopleCode program or other code example.
“ ” (quotation marks)	Indicate chapter titles in cross-references and words that are used differently from their intended meanings.
. . . (ellipses)	Indicate that the preceding item or series can be repeated any number of times in PeopleCode syntax.
{ } (curly braces)	Indicate a choice between two options in PeopleCode syntax. Options are separated by a pipe ().

Typographical Convention or Visual Cue	Description
[] (square brackets)	Indicate optional items in PeopleCode syntax.
& (ampersand)	When placed before a parameter in PeopleCode syntax, an ampersand indicates that the parameter is an already instantiated object. Ampersands also precede all PeopleCode variables.

Visual Cues

PeopleBooks contain the following visual cues.

Notes

Notes indicate information that you should pay particular attention to as you work with the PeopleSoft system.

Note. Example of a note.

If the note is preceded by *Important!*, the note is crucial and includes information that concerns what you must do for the system to function properly.

Important! Example of an important note.

Warnings

Warnings indicate crucial configuration considerations. Pay close attention to warning messages.

Warning! Example of a warning.

Cross-References

PeopleBooks provide cross-references either under the heading “See Also” or on a separate line preceded by the word *See*. Cross-references lead to other documentation that is pertinent to the immediately preceding documentation.

Country, Region, and Industry Identifiers

Information that applies only to a specific country, region, or industry is preceded by a standard identifier in parentheses. This identifier typically appears at the beginning of a section heading, but it may also appear at the beginning of a note or other text.

Example of a country-specific heading: “(FRA) Hiring an Employee”

Example of a region-specific heading: “(Latin America) Setting Up Depreciation”

Country Identifiers

Countries are identified with the International Organization for Standardization (ISO) country code.

See Appendix B, “ISO Country and Currency Codes,” ISO Country Codes.

Region Identifiers

Regions are identified by the region name. The following region identifiers may appear in PeopleBooks:

- Asia Pacific
- Europe
- Latin America
- North America

Industry Identifiers

Industries are identified by the industry name or by an abbreviation for that industry. The following industry identifiers may appear in PeopleBooks:

- USF (U.S. Federal)
- E&G (Education and Government)

Currency Codes

Monetary amounts are identified by the ISO currency code.

See Appendix B, “ISO Country and Currency Codes,” ISO Currency Codes.

Comments and Suggestions

Your comments are important to us. We encourage you to tell us what you like, or what you would like to see changed about PeopleBooks and other PeopleSoft reference and training materials. Please send your suggestions to:

PeopleSoft Product Documentation Manager PeopleSoft, Inc. 4460 Hacienda Drive Pleasanton, CA 94588

Or send email comments to doc@peoplesoft.com.

While we cannot guarantee to answer every email message, we will pay careful attention to your comments and suggestions.

Common Elements in These PeopleBooks

As of Date	The last date for which a report or process includes data.
Business Unit	An ID that represents a high-level organization of business information. You can use a business unit to define regional or departmental units within a larger organization.
Description	Enter up to 30 characters of text.
Effective Date	The date on which a table row becomes effective; the date that an action begins. For example, to close out a ledger on June 30, the effective date for the ledger closing would be July 1. This date also determines when

you can view and change the information. Pages or panels and batch processes that use the information use the current row.

Once, Always, and Don't Run

Select Once to run the request the next time the batch process runs. After the batch process runs, the process frequency is automatically set to Don't Run.

Select Always to run the request every time the batch process runs.

Select Don't Run to ignore the request when the batch process runs.

Report Manager

Click to access the Report List page, where you can view report content, check the status of a report, and see content detail messages (which show you a description of the report and the distribution list).

Process Monitor

Click to access the Process List page, where you can view the status of submitted process requests.

Run

Click to access the Process Scheduler request page, where you can specify the location where a process or job runs and the process output format.

Request ID

An ID that represents a set of selection criteria for a report or process.

User ID

An ID that represents the person who generates a transaction.

SetID

An ID that represents a set of control table information, or TableSets. TableSets enable you to share control table information and processing options among business units. The goal is to minimize redundant data and system maintenance tasks. When you assign a setID to a record group in a business unit, you indicate that all of the tables in the record group are shared between that business unit and any other business unit that also assigns that setID to that record group. For example, you can define a group of common job codes that are shared between several business units. Each business unit that shares the job codes is assigned the same setID for that record group.

Short Description

Enter up to 15 characters of text.

See Also

Enterprise PeopleTools 8.45 PeopleBook: PeopleSoft Process Scheduler

Enterprise PeopleTools 8.45 PeopleBook: Using PeopleSoft Applications

SQR Language Reference for PeopleSoft Preface

This book is a language reference for Structured Query Reports (SQR) for PeopleSoft.

SQR Language Reference for PeopleSoft

This reference describes and demonstrates the structure, command set, and syntax of the SQR language. It also provides a list of the sample SQR programs, an overview of the SQR initialization file, and a detailed list of SQR messages.

This reference is intended for SQR and SQL developers who must report on data from a wide range of enterprise data sources. Before using this reference, familiarize yourself with the data sources from which you are reporting and the connectivity between those data sources and your operating system.

CHAPTER 1

Understanding SQR for PeopleSoft

This chapter discusses:

- SQR for PeopleSoft tools.
- The Structured Query Report (SQR) language.
- SQR command line.
- SQR data elements.
- Sample reports.

SQR for PeopleSoft Tools

SQR for PeopleSoft is a powerful enterprise reporting system that provides direct access to multiple data sources. The SQR for PeopleSoft tools make it possible to create clear, professional reports from complex arrays of information systems.

This reference describes the following SQR for PeopleSoft tools:

- The SQR language, which is a flexible, fourth generation reporting language with a lexicon of over 110 commands.
SQR's procedural design makes it easy to develop, implement, and distribute complex reports.
- SQR Execute, which enables you to run previously compiled SQR programs.
- SQR Print, which enables you to configure reports for most printers.
- SQR Samples, a library of SQR programs and output that provides a framework for creating configured reports.

The SQR Language

This section provides an overview of the SQR language and discusses:

- SQR program structure.
- SQR syntax conventions.
- Rules for entering SQR commands.

Understanding the SQR Language

SQR is a specialized programming language for accessing, manipulating, and reporting enterprise data. With SQR, you build complex procedures that perform multiple calls to multiple data sources and implement nested, hierarchical, or object-oriented program logic.

SQR has several important benefits:

- Flexibility and scalability.
- Comprehensive facilities for combined report and data processing.
- Multiple platform availability.
- Multiple data source compatibility.

With SQR, you design reports by defining the page size, headers, footers, and layout. SQR enables you to generate a variety of output types, such as complex tabular reports, multiple page reports, and form letters. You can display data in columns; produce special formats, such as mailing labels; and create HTML, PDF, or configured output for laser printers and phototypesetters.

SQR's high-level programming capabilities enable you to add procedural logic and control to data source calls. You can use SQR to write other types of applications, such as those for database manipulation and maintenance, table loading and unloading, and interactive querying and displaying.

SQR Program Structure

SQR for PeopleSoft processes source code from a standard text file and generates a report. The text file containing source code comprises a set of sections that you delimit with BEGIN-section and END-section commands. The following examples show the general structure of SQR:

- The SETUP section describes overall characteristics of the report.

```
BEGIN-SETUP
  {setup commands}...
END-SETUP
```

- The HEADING and FOOTING sections specify what is printed in the header and footer on each page of the report.

```
BEGIN-HEADING {heading_lines}
  {heading commands}...
END-HEADING
BEGIN-FOOTING {footing_lines}
  {footing commands}...
END-FOOTING
```

- The PROGRAM section runs the procedures in the report.

```
BEGIN-PROGRAM
  {commands}...
END-PROGRAM
```

- The PROCEDURE section performs the tasks to produce the report.

```
BEGIN-PROCEDURE {procedure_name}
  {procedure commands}...
END-PROCEDURE
```

SQR Syntax Conventions

The following table describes the SQR syntax conventions:

Syntax Convention	Description
{ }	Braces enclose required items.
[]	Square brackets enclose optional items.
...	Ellipses indicate that the preceding parameter can be repeated.
	A vertical bar separates alternatives inside brackets, braces, or parentheses.
!	An exclamation point begins a single-line comment that extends to the end of the line. Each comment line must begin with an exclamation point.
'	A single quote starts and ends a literal text constant or any argument with more than one word. Important! If you are copying code directly from the sample programs, change the slanted quotes to regular quotes; otherwise, you will receive an error message.
,	A comma separates multiple arguments.
()	Parentheses must enclose an argument or element.
UPPERCASE	SQR commands and arguments are uppercase within the text, but lowercase in the sample programs. (Note that these commands are case insensitive.)
<i>Variable</i>	Information and values that you must supply appear in <i>variable</i> style.
hyphen versus underscore	Many SQR commands, such as BEGIN-PROGRAM, use a hyphen, whereas procedure and variable names use an underscore. Procedure and variable names can contain either hyphens or underscores, but it is best to use underscores in procedure and variable names to distinguish them from SQR commands. It also prevents confusion when you mix variable names and numbers in an expression, where hyphens could be mistaken for minus signs.

Rules for Entering SQR Commands

Use these command rules as you develop SQR programs:

- You can enter SQR commands in any case; they are *not* case sensitive.
Many SQR programmers use uppercase for SQR commands, but SQR ignores case as it compiles source code.
- You must separate command names and arguments by at least one space or tab character.
- You must begin each command on a new line; however, you can develop commands that extend beyond one line.
- You can break a line in any position between words *except* inside a quoted string.
- You can use a hyphen (-) at the end of a line to indicate that it continues on the next line; however, SQR ignores hyphens and carriage returns in commands.
- You must begin each comment line with an exclamation point (!).

Note. To display the exclamation point (!) or single quote (') symbols in a report, type the symbol twice to indicate that it is text. For example, DON'T is typed DON''T. This rule does not apply in the document paragraph of form-letter reports.

SQR Command Line

SQR for PeopleSoft comprises SQR, SQR Execute, and SQR Print. Each has a command-line interface.

To begin running SQR, enter the following command:

```
SQR [program][connectivity][flags...][args...][@file...]
```

Note. The executable name for SQR is SQR (SQRW for Windows). The executable name for SQR Execute is SQRT (SQRWT for Windows). The executable for SQR Print is SQRP (SQRWP for Windows).

See [Chapter 4, “Invoking SQR Execute,” page 247](#) and [Chapter 5, “Using SQR Print,” page 255](#).

SQR Command-Line Arguments

The following table describes the SQR command-line arguments:

Argument	Description
<i>program</i>	Name of the text file containing the source code. The default file type or extension is .sqr. If you enter this value as a question mark (?) or omit it, SQR for PeopleSoft prompts you for the report program name. On UNIX/Linux-based systems, if your shell uses the question mark as a wildcard character, you must precede it with a backslash (\).

Argument	Description
<i>connectivity</i>	Information that SQR for PeopleSoft needs to connect to the database. If you enter this value as a question mark (?) or omit it, SQR for PeopleSoft prompts you for the information. IBM DB2: Subsystem name and Structured Query Language (SQL) authorization ID. <i>Ssname/SQLid</i> Microsoft Windows or IBM DB2: Name of the database, your username, and the password for the database. [Database] / [Username] / [Password] Informix: Name of the database. Database[/username/password] Open Database Connectivity (ODBC): Name that you give to the ODBC driver when you set up the driver, and your username and password for the database. This port has been certified against IBM DB2 and Microsoft SQL Server. Data_Source_Name/[Username]/[Password] Oracle: Your username and password for the database, and an optional connection string for the database (for example, @sales.2cme.com). [Username]/[Password[@Database]] Sybase: Your username and password for the database. Username/[Password]
<i>flags</i>	See the following section, “SQR Command-Line Flags.”
<i>args...</i>	Arguments that SQR for PeopleSoft uses while the program is running. The ASK and INPUT commands use these arguments rather than prompting the user. You must enter arguments on the command line in the sequence that the program expects—first all ASK arguments, in order, followed by INPUT arguments.
<i>@file...</i>	File containing program arguments—one argument per line. Arguments that are listed in the file are processed one at a time: first all ASK arguments, in order, followed by INPUT arguments. You can specify the command-line arguments (<i>program</i> , <i>connectivity</i> , and <i>args</i>) in this file for non-Microsoft Windows platforms.

SQR Command-Line Flags

SQR supports a number of command-line flags. Each flag begins with a hyphen (-). When a flag takes an argument, the argument must follow the flag with no intervening space.

The following table describes the SQR command-line flags:

Flag	Description
-A	Appends the output to an existing output file carrying the same name as the source of the output. If the file does not exist, a new one is created. This flag is useful when you want to run the same report more than once but want only a single output file.
-Bnn	(ODBC, Oracle, and Sybase CT-Lib) Indicates the number of rows to buffer each time SQR for PeopleSoft retrieves data from the database. The default is 10 rows. Regardless of the setting, all rows are retrieved. When used on the command line, -B controls the setting for all BEGIN-SELECT commands. Inside a program, each BEGIN-SELECT command can also have its own -B flag for further optimization.
-BURST:{xx}	-BURST:T generates the table of contents file only. -BURST:S generates the report output according to the symbolic table of contents entries that are set in the program with the <i>level</i> argument of the TOC-ENTRY command. In -BURST:S[{1}], {1} is the level on which to burst. The -BURST:S setting is equivalent to -BURST:S1. See <i>Enterprise PeopleTools 8.45 PeopleBook: SQR for PeopleSoft Developers</i>, “Generating and Publishing HTML from an SQR Program,” Bursting Reports. Note. -BURST:P and -BURST:S require -PRINTER:EH or -PRINTER:HT. The page range selection feature of -BURST:P requires -PRINTER:HT. -BURST:T requires -PRINTER:HT.
-C	(Microsoft Windows) Specifies that the Cancel dialog box appears while the program runs so that you can easily stop the program.
-CB	(Microsoft Windows, Callable SQR) Forces the communication box to use.

Flag	Description
-Dnn	(Non-Microsoft Windows) Displays the report output on the terminal while it is being written to the output file. The value for <i>nn</i> is the maximum number of lines to display before pausing. If no number is entered after -D, the display scrolls continuously. Note. The printer type must be LP; otherwise, the display is ignored. If the program is producing more than one report, the display is for the first report only.
-DBdatabase	(Sybase) Makes the SQR program use the specified database, which overrides any USE command in the SQR program.
-DEBUG [xxx]	See Chapter 2, “SQR Command Reference,” #DEBUG, page 63.
-DNT: {xx}	See Chapter 2, “SQR Command Reference,” DECLARE-VARIABLE, page 98.
-E[file]	Directs error messages to the named file or to the default file program.err. If no errors occur, no file is created.
-EH_APPLETS:dir	Specifies the directory location of the enhanced HTML applets. If you include an applet, SQR for PeopleSoft must know where it resides. SQR for PeopleSoft usually checks for the applet in a default directory; the default directory for these applets is IMAGES. Note. This flag is applicable only when you specify the -PRINTER:EH or -PRINTER:EP flag.
-EH_BQD	Generates a {report}.bqd file from the report data. Also associates a query format file (BQD) icon with {report}.bqd in the navigation bar. Note. This flag is applicable only when you specify the -PRINTER:EH or -PRINTER:EP flag.
-EH_BQD:file	Associates the BQD icon with the specified file. Note. This flag is applicable only when you specify the -PRINTER:EH or -PRINTER:EP flag.

Flag	Description
-EH_BROWSER:xx	Generates HTML, determines the browser, and displays HTML. When this flag is set to ALL, SQR for PeopleSoft generates frame.html, which contains JavaScript to determine the browser on the user's machine (that is, the person reading the report, not the person writing it). When this flag is set to BASIC, SQR for PeopleSoft generates HTML that is suitable for all browsers. When this flag is set to IE, SQR for PeopleSoft generates HTML that is designed for Microsoft Internet Explorer. When this flag is set to NETSCAPE, SQR for PeopleSoft generates HTML that is designed for Netscape. Note. This flag is applicable only when you specify the -PRINTER:EH or -PRINTER:EP flag.
-EH_CSV	Generates a {report}.csv file from the report data. Note. This flag is applicable only when you specify the -PRINTER:EH or -PRINTER:EP flag.
-EH_CSV:file	Associates the CSV icon with the specified file. Note. This flag is applicable only when you specify the -PRINTER:EH or -PRINTER:EP flag.
-EH_CSVONLY	Creates a CSV file, but does not create an HTML file. Note. This flag is applicable only when you specify the -PRINTER:EH or -PRINTER:EP flag.
-EH_FULLHTML:xx	Specifies the level of the generated enhanced HTML code. This can be 30, 32, or 40. Note. For upward compatibility, a value of TRUE is equivalent to 40 and FALSE is 30.
-EH_Icons:dir	Specifies the directory in which the HTML should find the referenced icons. Note. This flag is applicable only when you specify the -PRINTER:EH or -PRINTER:EP flag.
-EH_IMAGES:dir	Specifies the directory path for the .gif files that are used by the navigation bar. Note. This flag is applicable only when you specify the -PRINTER:EH or -PRINTER:EP flag.

Flag	Description
-EH_KEEP	Copies (does not move) the files when used in conjunction with -EH_ZIP. Note. This flag is applicable only when you specify the -PRINTER:EH or -PRINTER:EP flag.
-EH_LANGUAGE:xx	Sets the language that is used for the HTML navigation bar. You can specify English, French, German, Portuguese, Spanish, Japanese, Simplified Chinese, or Korean. Note. This flag is applicable only when you specify the -PRINTER:EH or -PRINTER:EP flag.
-EH_PDF	Associates a PDF icon with {report}.pdf in the navigation bar. Note. This flag is applicable only when you specify the -PRINTER:EH or -PRINTER:EP flag.
-EH_Scale:{nn}	Sets the scaling factor from 50 to 200. Note. This flag is applicable only when you specify the -PRINTER:EH or -PRINTER:EP flag.
-EH_XML:file	Associates the XML icon with the specified file. Note. This flag is applicable only when you specify the -PRINTER:EH or -PRINTER:EP flag.
-EH_ZIP[:file]	Moves the generated files to the specified file or {report}.zip if {file} is not specified. Note. This flag is applicable only when you specify the -PRINTER:EH or the -PRINTER:EP flag.

Flag	Description
-F[file directory]	Overrides the default output file name, program.lis. The default action places the program.lis in the same directory as the program.sqr file. To use the current directory, specify -F without an argument. To change the name of the output file, specify -F with the new name. If the new name does not specify a directory, the file is created in the current directory. The output file is not created until data is actually printed on the page. If no data is printed, no output file is created. Specify these file names and directories for different operating systems: UNIX/Linux Directory character is / -F\$HOME/reports/ IBM MVS Directory character is (-FDSN:SQR.REPORTS(
-GPRINT=YES NO	(IBM MVS) -GPRINT=YES causes the SQR report output file to have control characters written to the first column of each record of the file. -GPRINT=NO omits the control characters.
-Idir_list	Specifies the list of directories that SQR for PeopleSoft searches when processing the #INCLUDE directive if the include file does not exist in the current directory and no path was specified for the file. The directory names must be separated by commas (,) or semicolons (;). For UNIX/Linux-based systems, if your shell uses semicolons as command delimiters, you must precede each semicolon with a backslash (\). Always append the directory character to the end of each directory name. See the -F flag for a list of directory characters, sorted by operating system.
-ID	(Non-Microsoft Windows) Displays the copyright banner on the console.
-KEEP	See <i>Enterprise PeopleTools 8.45 PeopleBook: SQR for PeopleSoft Developers</i> , “Printing with SQR for PeopleSoft”.

Flag	Description
-LL{s d}{c i}	LOAD-LOOKUP: • s: SQR • d: DB • c: Case sensitive • i: Case insensitive See Chapter 2, “SQR Command Reference,” LOAD-LOOKUP, page 159 .
-Mfile	Defines a startup file containing sizes to assign to internal parameters—extremely small, large, or complex reports. <i>Mfiles</i> are text files that have individual switches in the INI files that are unique to a run.
-NOLIS	Prevents the creation of .lis files, creating .spfs instead.
-O[file]	Directs log messages to the specified file or to program.log if no file is specified. By default, the sqr.log file is used in the current working directory.
-olim	Displays the SQR resources that are used by the SQR report.
-P	(IBM MVS) Suppresses printer control characters from column 1.
-PB	(Informix) Causes column data to preserve trailing blanks.

Flag	Description
-PRINTER:xx	Uses printer type xx when creating output files. The xx represents: EH: Enhanced HTML -PRINTER:EH EP: Enhanced HTML or PDF -PRINTER:EP HP: HP LaserJet -PRINTER:HP HT: HTML 2.0 -PRINTER:HT LP: Line printer -PRINTER:LP PD: PDF -PRINTER:PD PS: PostScript -PRINTER:PS WP: Microsoft Windows -PRINTER:WP LP, HP, and PS produce files with the .lis extension. Types EH and HT produce .htm file output. Type HT produces version 2.0 HTML files with the report content inside <PRE></PRE> tags. Type EH produces reports in which content is fully formatted with version 3.0 or 3.2 HTML tags. On Microsoft Windows systems, the WP extension sends the output to the default Microsoft Windows printer. To specify a Microsoft Windows printer that is not the default, enter -PRINTER:WP:{Printer Name}, where {Printer Name} is the name that is assigned to your printer. For example, to send output to a Microsoft Windows printer named New Printer, use -PRINTER:WP:NewPrinter. If the printer name has spaces, enclose the entire argument in quotes. To also create an .spf file, use -KEEP.
-RS	Saves the program in a runtime file. The program is scanned, compiled, and checked for correct syntax. Queries are validated and compiled. Then, the executable version is saved in a file with the name program.sqt. Note. SQR for PeopleSoft does not prompt ASK variables after compilation.

Flag	Description
-RT	Uses the runtime file that is saved with the -RS flag. This skips all syntax and query checking, and processing begins immediately. Note. SQR for PeopleSoft does not prompt ASK variables after compilation.
-S	Requests that the status of all cursors be displayed at the end of the report run. Status includes the text of each SQL statement, the number of times each was compiled and run and the total number of rows that were selected. The output appears directly on the screen. This information can be used for debugging SQL statements and enhancing performance and tuning.
-Tnn	Specifies that you want to test your report for <i>nn</i> pages. To save time during testing, SQR for PeopleSoft ignores all ORDER BY clauses in SELECT statements. If the program is producing more than one report, SQR for PeopleSoft stops after producing the specified number of pages defined for the first report.
-T{B}	(Windows/DB2, Sybase CT-Lib, and ODBC) Trims trailing blanks from database character columns. (IBM MVS and DB2) Prevents SQR for PeopleSoft from removing trailing blanks from database character columns.
-T{Z}	(IBM MVS and DB2) Prevents SQR for PeopleSoft from removing trailing zeros from the decimal portion of numeric columns.
-Vserver	(Sybase) Uses the named server.
-XB	(Non-Microsoft Windows) Suppresses the SQR banner and the SQR.... <i>End of Run</i> message.
-XC	(Callable SQR) Suppresses the database commit when the report has finished running.
-XCB	(Microsoft Windows) Does not use the communication box. Requests for input are made in Microsoft Windows dialog boxes.

Flag	Description
-XI	Prevents user interaction during a program run. If an ASK or INPUT command requires user input, an error is produced and the program ends.
-XL	Prevents SQR for PeopleSoft from signing in to the database. Programs that you run in this mode cannot contain SQL statements. -XL enables you to run SQR for PeopleSoft without accessing the database. You still must supply at least an empty slash on the command line as a placeholder for the connectivity information. For example: <code>sqr myprog / -xl</code>
-XLFF	Prevents a trailing form feed.
-XMB	(Microsoft Windows) Disables the error message display so that you can run a program without interruption from error message boxes. Error messages are sent to an .err file. See the -E flag.
-XNAV	Prevents SQR for PeopleSoft from creating the navigation bar in .htm files that are generated with -PRINTER:HT. This occurs when only a single .htm file is produced. Multiple .htm files that are generated from a single report always contain the navigation bar.
-XP	(Sybase) Prevents SQR for PeopleSoft from creating temporary stored procedures. See Chapter 2, “SQR Command Reference,” BEGIN-SELECT, page 46.
-XTB	Preserves the trailing blanks in a .lis file at the end of a line.
-XTOC	Prevents SQR for PeopleSoft from generating the table of contents for the report. This flag is ignored when you also specify either -PRINTER:EH or -PRINTER:HT.
-ZIF{file}	Sets the full path and name of the SQR initialization file, sqr.ini.

Flag	Description
-ZIV	Invokes the SPF Viewer after generating the program.spf file. This flag implicitly invokes the -KEEP flag to create program.spf. In the case of multiple output files, only the first report file is passed to the viewer.
-ZMF{file}	Specifies the full path and name of the SQR error message file, sqrrr.dat.

SQR Data Elements

Each SQR data element begins with a special character that denotes the type of data element.

This section discusses:

- Columns
- Variables
- Literals

Columns

Columns are fields that are defined in the database.

The ampersand character (&) begins a database column or expression name. It can be any type of column, such as character, number, or date. Columns that are defined in a query are declared automatically, except for dynamic columns and database or aggregate functions.

Variables

Variables are storage places for text or numbers that you define and manipulate.

- \$ begins a text or date variable.
- # begins a numeric variable.
- % begins a list variable.
- @ begins a variable name for a marker location.

Marker locations identify positions to begin printing in a BEGIN-DOCUMENT paragraph.

Variable Rules

The following rules govern the use of variables in SQR:

- Variables can be almost any name of almost any length—for example, \$state_name or #total_cost.
- Do not use an underscore (_) or colon (:) as the first character of a two-variable name.

See *Enterprise PeopleTools 8.45 PeopleBook: SQR for PeopleSoft Developers*, “Using Break Logic,” Using Hyphens and Underscores.

- Variable names are *not* case sensitive.

That is, you can use a name in uppercase on one line and lowercase on the next; both refer to the same variable.

- SQR for PeopleSoft initializes variables to null (text and date) or zero (numeric).
- A command can grow to whatever length the memory of your computer can accommodate.
- Numeric variables can be one of three types: float, integer, or decimal.

See [Chapter 2, “SQR Command Reference,” DECLARE-VARIABLE, page 98.](#)

- Variables and columns are known globally throughout a report, except when used in a local procedure (one with arguments or declared with the LOCAL argument), in which case they are known in that procedure only.

See [Chapter 2, “SQR Command Reference,” BEGIN-PROCEDURE, page 43.](#)

SQR Reserved Variables

When you create multiple reports, the variables apply to the current report. SQR for PeopleSoft reserves a library of predefined variables for general use.

The following table describes the SQR reserved variables:

Variable	Description
<i>#current-column</i>	Current column on the page.
<i>\$current-date</i>	Current date and time on the local machine when SQR for PeopleSoft starts running the process.
<i>#current-line</i>	Current line on the page. This value is the physical line on the page, not the line in the report body. Line numbers are referenced in PRINT and other SQR commands that are used for positioning the data on the page. Optional page headers and footers, which are defined with BEGIN-HEADING and BEGIN-FOOTING commands, have their own line sequences. Line 2 of the heading is different from line 2 of the report body or footing.
<i>#end-file</i>	See Chapter 2, “SQR Command Reference,” READ, page 204.
<i>#page-count</i>	Current page number.
<i>#return-status</i>	Value to return to the operating system when SQR for PeopleSoft exits. This can be set in the report. <i>#return-status</i> is initialized to the “success” return value for the operating system.

Variable	Description
<i>#sql-count</i>	Count of the rows that are affected by a SELECT paragraph (INSERT, UPDATE, or DELETE). This is equivalent to ROWCOUNT in Oracle and Sybase.
<i>\$sql-error</i>	Text message from the database explaining an error. This variable is rewritten when a new error is encountered.
<i>#sql-status</i>	The value of <i>#sql-status</i> is set whenever a BEGIN-SELECT command is run. Normally this variable is checked from inside an ON-ERROR procedure, so its value describes the error condition (whereas the <i>\$sql-error</i> variable contains the error message). The actual meaning of <i>#sql-status</i> is database dependent. Therefore, consult the proper database manual to fully interpret its meaning.
<i>\$sqr-encoding-console</i> {sqr-encoding- console}	Name of encoding for character data that is written to the log file or console.
<i>\$sqr-encoding- database</i> {sqr-encoding- database}	Character data that is retrieved from and inserted into the database.
<i>\$sqr-encoding- file-input</i> {sqr-encoding- file-input}	Name of encoding for character data that is read from files that are used with the OPEN command.
<i>\$sqr-encoding- file-output</i> {sqr-encoding- file-output}	Name of encoding for character data that is written to files that are used with the OPEN command.
<i>\$sqr-encoding- report-output</i> {sqr-encoding- report-output}	Report that is generated by SQR for PeopleSoft (for example, an .lis file or a PostScript file).
<i>\$sqr-encoding- source</i> {sqr-encoding- source}	Name of encoding for SQR source files and include files.
<i>\$sqr-database</i> , {sqr-database}	Database type for which SQR was compiled. Values are DB2, ODBC, SYBASE, INFORMIX, and ORACLE.

Variable	Description
<i>\$sqr-dbcs,</i> <i>{sqr-dbcs}</i>	Specifies whether SQR for PeopleSoft recognizes double-byte character strings. Values are YES and NO.
<i>sqr-encoding,</i> <i>{sqr-encoding}</i>	Name of the default encoding as defined by the ENCODING environment variable when SQR for PeopleSoft is invoked.
<i>sqr-hostname,</i> <i>{sqr-hostname}</i>	Name of the computer on which SQR for PeopleSoft is currently running.
<i>\$sqr-locale</i>	Name of the current locale that is being used. A plus symbol (+) at the end of the name indicates that an argument that is used in the locale has changed.
<i>#sqr-max-lines</i>	Maximum number of lines, as determined by the layout. When a new report is selected, this variable is automatically updated to reflect the new layout.
<i>#sqr-max-columns</i>	Maximum number of columns, as determined by the layout. When a new report is selected, this variable is automatically updated to reflect the new layout.
<i>#sqr-pid</i>	Process ID of the current SQR process. <i>#sqr-pid</i> is unique for each run of SQR. This variable is useful in creating unique, temporary names.
<i>\$sqr-platform,</i> <i>{sqr-platform}</i>	The hardware or operating system type for which SQR was compiled. Values are MVS, Windows, and UNIX/Linux.
<i>\$sqr-program</i>	Name of the SQR process file.
<i>\$sqr-ver</i>	Text string that is shown with the -ID flag. SQR version.
<i>\$username</i>	Database username that is specified on the command line.
<i>\$sqr-report</i>	Name of the report output file. <i>\$sqr-report</i> reflects the actual name of the file to use, as specified by the -F flag or NEW-REPORT command.

List Variables

List variables contain an ordered collection of SQR variables and are nonrecursive—that is, you cannot nest lists inside lists.

Indicate list variables with the percent symbol (%). Create list variables with the LET command and a list of variables. For example:

```
let %list1 = list (num_var1|str_var1, num_var2|str_var2,...)
```

Working with list variables includes the following tasks:

- Defining a list variable:

You can use a list variable to hold multiple rows of information. Before you assign a list variable, define it by using the following syntax:

```
let %listname=list(col_var|num_var|str_var|str_lit|num_lit[,...])
or
let %listname[num_lit]=list(NUMBER|DATE|TEXT$colname
|'.colname'[,...])
```

- Assigning a list variable:

Assign a list variable by using the following syntax:

```
let %listname|%listname[num_var|num_lit]=list(col_var|str_var
|num_var|str_lit|num_lit[,...])
```

- Accessing a list variable:

Access a list variable by using the following syntax:

```
let str_var|num_var=%listname[num_var|num_lit].#colname
```

List Variable Arguments

The value between the brackets indicates either the number of rows in the list for the definition case or the row in the list to modify or assign.

If there are no brackets, there is no need to predefine; assign the types based on the given variable types. For multirow lists, the assignment must be compatible with the types that are given in the definition.

A NUMBER field has the same characteristics as an undeclared #var. The underlying storage depends on the contents, and the DEFAULT-NUMERIC setting applies.

The usual SQR rules for variable assignment apply to list access. Assignment is prohibited only between date and numeric types. Assignment of a numeric column to a string variable returns the string representation of the numeric value; assignment of a date variable to a string variable returns the default-edit-mask representation of the date.

Literals

Literals are text or numeric constants.

- A single quote begins and ends a text literal. For example:

```
'Hello'
```

- Numerals 0–9 begin numeric literals.

Numerals that include digits with an optional decimal point and leading sign are acceptable numeric literals. For example, -543.21. Numeric literals can also be expressed in scientific form. For example, 1.2E5.

Sample Reports

To see a quick overview of how an SQR report looks, view the sample reports that are stored in the SQR for PeopleSoft directory <PS_HOME>\bin\sqr\<database_platform>\SAMPLE (or SAMPLEW, for Windows). You can modify these reports to meet your needs.

CHAPTER 2

SQR Command Reference

This chapter describes and demonstrates each command in the SQR lexicon.

SQR Command Overview

The commands in this section follow the conventions listed in the section “SQR Syntax Conventions” in the previous chapter, and use the abbreviations described in the following table.

Warning! If you are copying code directly from the examples in the PDF file, make sure you change the slanted quotes to regular quotes or you will receive an error message.

Abbreviation	Description	Example
txt_col	Text column retrievable from a database.	&address
num_col	Numeric column retrievable from a database.	&price
date_col	Date or datetime column retrievable from a database.	&date1
txt_var	String variable defined in a program.	\$your_name
num_var	Numeric variable defined in a program.	#total_cost
date_var	A variable explicitly defined as a date variable.	\$date1
any_lit	A literal of any type.	'abc' 12
any_var	A variable of any type.	\$string #number \$date
any_col	A column of any type.	&string &number &date

Abbreviation	Description	Example
txt_lit	Text literal defined in a program.	'Company Confidential'
num_lit	Numeric literal defined in a program.	12345.67
int_lit	Integer literal defined in a program.	12345
nn	Integer literal used as an argument to a command.	123
position	The position qualifier, which consists of the line, column, and length specification. The minimum position, (), means to use the current line and column position on the page for the length of the field being printed.	(5,10,30)

SQR Commands

The following sections discuss the SQR commands in alphabetical order.

ADD

Syntax

```
ADD{src_num_lit | _var |
_col} TO dst_num_var
[ROUND=nn]
```

Description

Adds one number to another.

The source value is added to the destination variable and the result is placed in the destination. The source is always first and the destination is always second.

When dealing with money-related values (dollars and cents), use decimal variables rather than float variables. Float variables are stored as double precision floating point numbers, and small inaccuracies can appear when adding many numbers in succession. These inaccuracies can appear due to the way floating point numbers are represented by different hardware and software implementations and also due to inaccuracies that can be introduced when converting between floating point and decimal.

Parameters

Parameter	Description
<i>src_num_lit</i> <i>_var</i> <i>_col</i>	Source number literal, variable or column.
<i>dst_num_var</i>	A numeric destination variable that contains the result after execution.
ROUND	Rounds the result to the specified number of digits to the right of the decimal point. For float variables, this value can be from 0 to 15. For decimal variables, this value can be from 0 to the precision of the variable. For integer variables, this argument is not appropriate.

Example

To add 10 to #counter

```
add #counter to #new_count
add &price to #total round=2
```

See Also

The LET command for information about complex arithmetic expressions.

ALTER-COLOR-MAP

Syntax

ALTER-COLOR-MAP

NAME = {*color_name_lit* | *_var* | *_col*}

VALUE = ({*color_name_lit* | *_var* | *_col*} | {*rgb*})

Description

Dynamically alters a defined color.

The ALTER-COLOR-MAP command is allowed wherever the PRINT command is allowed. This command enables you to dynamically alter a defined color. You cannot use this command to define a new color.

Parameters

Parameter	Description
NAME	Defines the name of the color you want to alter. For example, <i>light blue</i> .
VALUE	Defines the RGB value of the color you want to alter. For example, (193, 233, 230).
{ <i>color_name_lit</i> <i>_var</i> <i>_col</i> }	A <i>color_name</i> is composed of the alphanumeric characters (A-Z, 0-9), the underscore (_) character, and the hyphen (-) character. It must start with an alpha (A-Z) character. It is case insensitive. The name 'none' is reserved and cannot be assigned a value. A name in the format (RGBredgreenblue) cannot be assigned a value. The name 'default' is reserved and may be assigned a value. 'Default' is used during execution when a referenced color is not defined in the runtime environment.
{ <i>rgb</i> }	<i>red_lit</i> <i>_var</i> <i>_col</i> , <i>green_lit</i> <i>_var</i> <i>_col</i> , <i>blue_lit</i> <i>_var</i> <i>_col</i> where each component is a value in the range of 000 to 255. In the BEGIN-SETUP section, only literal values are allowed.

The default colors implicitly installed with SQR include:

- black=(0,0,0)
- white=(255,255,255)
- gray=(128,128,128)
- silver=(192,192,192)
- red=(255,0,0)
- green=(0,255,0)
- blue=(0,0,255)
- yellow=(255,255,0)
- purple=(128,0,128)
- olive=(128,128,0)
- navy=(0,0,128)
- aqua=(0,255,255)
- lime=(0,128,0)
- maroon=(128,0,0)
- teal=(0,128,128)
- fuchsia=(255,0,255)

Example

```
begin-setup
  declare-color-map
    light_blue = (193, 222, 229)
  end-declare
end-setup

begin-program
  alter-color-map name = 'light_blue' value = (193, 233, 230)

  print 'Yellow Submarine' ()
    foreground = ('yellow')
    background = ('light_blue')

  get-color print-text-foreground = ($print-foreground)
  set-color print-text-foreground = ('purple')
  print 'Barney' (+1,1)
  set-color print-text-foreground = ($print-foreground)
end-program
```

See Also

The DECLARE-COLOR-MAP, SET-COLOR and GET-COLOR commands in this section.

ALTER-LOCALE

Syntax

```
ALTER-LOCALE
[LOCALE={txt_lit _var|DEFAULT|SYSTEM}]
[NUMBER-EDIT-MASK={txt_lit|_var|DEFAULT|SYSTEM}]
[MONEY-EDIT-MASK={txt_lit|_var|DEFAULT|SYSTEM}]
[DATE-EDIT-MASK={txt_lit|_var|DEFAULT|SYSTEM}]
[INPUT-DATE-EDIT-MASK={txt_lit|_var|DEFAULT|SYSTEM}]
[MONEY-SIGN={txt_lit|_var|DEFAULT|SYSTEM}]
[MONEY-SIGN-LOCATION={txt_var|DEFAULT|SYSTEM|LEFT
|RIGHT}]
[THOUSAND-SEPARATOR={txt_lit|_var|DEFAULT|SYSTEM}]
[DECIMAL-SEPARATOR={txt_lit|_var|DEFAULT|SYSTEM}]
[DATE-SEPARATOR={txt_lit|_var|DEFAULT|SYSTEM}]
[TIME-SEPARATOR={txt_lit|_var|DEFAULT|SYSTEM}]
[EDIT-OPTION-NA={txt_lit|_var|DEFAULT|SYSTEM}]
[EDIT-OPTION-AM={txt_lit|_var|DEFAULT|SYSTEM}]
[EDIT-OPTION-PM={txt_lit|_var|DEFAULT|SYSTEM}]
[EDIT-OPTION-BC={txt_lit|_var|DEFAULT|SYSTEM}]
[EDIT-OPTION-AD={txt_lit|_var|DEFAULT|SYSTEM}]
[DAY-OF-WEEK-CASE={txt_var|DEFAULT|SYSTEM|UPPER|LOWER
|EDIT|NO-CHANGE}]
[DAY-OF-WEEK-FULL=( {txt_lit1|_var1}...{txt_lit7
|_var7})]
[DAY-OF-WEEK-SHORT=( {txt_lit1|_var1}...{txt_lit7
|_var7})]
[MONTHS-CASE={txt_var|DEFAULT|SYSTEM|UPPER|LOWER|EDIT
|NO-CHANGE}]
[MONTHS-FULL=( {txt_lit1|_var1}...{txt_lit12|
_var12})]
[MONTHS-SHORT=( {txt_lit1|_var1}...{txt_lit12|_var12})]
```

Description

Selects a locale or changes locale parameters used for printing date, numeric, and money data and for data accepted by the INPUT command. A locale is a set of preferences for language, currency, and the presentation of charts and numbers.

The SYSTEM locale represents the behavior of older versions of SQR prior to Version 4.0. When you install SQR for PeopleSoft Version 4.0 or later, the default locale is set to SYSTEM. This provides upwards compatibility for older SQR programs. The SYSTEM locale settings are described in the following table.

Keyword	Value
NUMBER-EDIT-MASK	The PRINT command prints two digits to the right of the decimal point and left justifies the number in the field. The MOVE, SHOW, and DISPLAY commands format the number with six digits to the right of the decimal point and left justifies the number.
MONEY-EDIT-MASK	SQR uses the same default as the NUMBER-EDIT-MASK keyword.
DATE-EDIT-MASK	SQR uses the default database date format. See the Date Time section for more details.
INPUT-DATE-EDIT-MASK	SQR uses a default date edit mask with the INPUT command. See the Sample Date Edit Masks table for a listing of the date edit mask.
MONEY-SIGN	'\$'
MONEY-SIGN-LOCATION	LEFT
THOUSAND-SEPARATOR	','
DECIMAL-SEPARATOR	'.'
DATE-SEPARATOR	'/'
TIME-SEPARATOR	':'
EDIT-OPTION-NA	'n/a'
EDIT-OPTION-AM	'am'
EDIT-OPTION-PM	'pm'
EDIT-OPTION-BC	'bc'
EDIT-OPTION-AD	'ad'
DAY-OF-WEEK-CASE	EDIT

Keyword	Value
DAY-OF-WEEK-FULL	('Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday', 'Saturday')
DAY-OF-WEEK-SHORT	('Sun', 'Mon', 'Tue', 'Wed', 'Thu', 'Fri', 'Sat')
MONTHS-CASE	EDIT
MONTHS-FULL	('January', 'February', 'March', 'April', 'May', 'June', 'July', 'August', 'September', 'October', 'November', 'December')
MONTHS-SHORT	('Jan', 'Feb', 'Mar', 'Apr', 'May', 'Jun', 'Jul', 'Aug', 'Sep', 'Oct', 'Nov', 'Dec')

Parameters

The following are the parameters.

Note. Many of the settings can have a value of DEFAULT or SYSTEM. For a given setting, specifying DEFAULT retrieves the value from the corresponding setting of the *default* locale as identified in the Default-Settings section of the *sqr.ini* file. Similarly, specifying the keyword SYSTEM retrieves the value from the corresponding setting of the *system* locale. You can alter the *system* locale using the ALTER-LOCALE command; however, you cannot define it in the *sqr.ini* file.

Parameter	Description
LOCALE	Specifies the name of the locale to use. This name must be defined in the <i>sqr.ini</i> file. If this field is omitted, then the current locale is used. The locale name is case-insensitive and is limited to the following character set: A-Z, 0-9, underscore, or hyphen. The current locale can be determined by printing the reserved variable <i>\$sqr-locale</i> .
NUMBER-EDIT-MASK	Specifies the numeric edit mask to use with the keyword NUMBER in a PRINT, MOVE, SHOW, or DISPLAY command.
MONEY-EDIT-MASK	Specifies the numeric edit mask to use with the keyword MONEY in a PRINT, MOVE, SHOW, or DISPLAY command.
DATE-EDIT-MASK	The default date edit mask to used with the keyword DATE in the PRINT, MOVE, SHOW, or DISPLAY command, or the LET functions <i>datetostr()</i> or <i>strtodate()</i> .
INPUT-DATE-EDIT-MASK	The default date format to use with the INPUT command when TYPE=DATE is specified with the command or the input variable is a date variable. For information about Edit Masks, see <i>PRINT</i> .
MONEY-SIGN	Specifies the characters that replace the \$ or other currency symbol used in edit masks.
MONEY-SIGN-LOCATION	Specifies where to place the MONEY-SIGN characters. Valid values are LEFT and RIGHT.
THOUSAND-SEPARATOR	Specifies the character to replace the ',' edit character.

Parameter	Description
DECIMAL-SEPARATOR	Specifies the character to replace the '.' edit character.
DATE-SEPARATOR	Specifies the character to replace the '/' character.
TIME-SEPARATOR	Specifies the character to replace the ':' character.
EDIT-OPTION-NA	Specifies the characters to use with the 'na' option.
EDIT-OPTION-AM	Specifies the characters to replace 'AM'.
EDIT-OPTION-PM	Specifies the characters to replace 'PM'.
EDIT-OPTION-BC	Specifies the characters to replace 'BC'.
EDIT-OPTION-AD	Specifies the characters to replace 'AD'.
DAY-OF-WEEK-CASE	Specifies how the case for the DAY-OF-WEEK-FULL or DAY-OF-WEEK-SHORT entries are affected when used with the format codes 'DAY' or 'DY'. Valid values are UPPER, LOWER, EDIT, and NO-CHANGE. UPPER and LOWER force the output to either all uppercase or lowercase, ignoring the case of the format code in the edit mask. Use EDIT to follow the case specified with the format code in the edit mask. Use NO-CHANGE to ignore the case of the format code and output the day of week explicitly listed in the DAY-OF-WEEK-FULL or DAY-OF-WEEK-SHORT entries.
DAY-OF-WEEK-FULL	Specifies the full names for the days of the week. SQR considers the first day of the week to be Sunday. You must specify all seven days.
DAY-OF-WEEK-SHORT	Specifies the abbreviated names for the days of the week. SQR considers the first day of the week to be Sunday. You must specify all seven abbreviations.
MONTHS-CASE	Specifies how the case for the MONTHS-FULL or MONTHS-SHORT entries are affected when used with the format codes 'MONTH' or 'MON'. Valid values are UPPER, LOWER, EDIT, and NO-CHANGE. UPPER and LOWER force the output to either all uppercase or lowercase, ignoring the case of the format code in the edit mask. Use EDIT to follow the case specified with the format code in the edit mask. Use NO-CHANGE to ignore the case of the format code and output the month explicitly listed in the MONTHS-FULL or MONTHS-SHORT entries.
MONTHS-FULL	Specifies the full names for the months of the year. SQR for PeopleSoft considers the first month of the year to be January. All 12 months must be specified.
MONTHS-SHORT	Specifies the abbreviated names for the months of the year. SQR for PeopleSoft considers the first month of the year to be January. All 12 abbreviations must be specified.

Example

```

!
! The following program segments will illustrate the various
! ALTER-LOCALE features.
!
begin-setup
  declare-variable
    date $date $date1 $date2 $date3
  end-declare
end-setup

```

```

!
! Set default masks
!
alter-locale
  number-edit-mask = '9,999,999.99'
  money-edit-mask  = '$999,999,999.99'
  date-edit-mask   = 'Mon DD, YYYY'

let #value = 123456
let $edit = 'Mon DD YYYY HH:MI:SS'
let $date = strtodate('Jan 01 2004 11:22:33', $edit)
show 'With NUMBER option    #Value = ' #value number
show 'With MONEY option    #Value = ' #value money
show 'Without NUMBER option #Value = ' #value
show 'With DATE option     $Date  = ' $date date
show 'Without DATE option  $Date  = ' $date

```

Produces the following output:

```

With NUMBER option    #Value =   123,456.00
With MONEY option    #Value = $   123,456.00
Without NUMBER option #Value = 123456.000000
With DATE option     $Date  = Jan 01, 2004
Without DATE option  $Date  = 01-JAN-04

```

```

!
! Reset locale to SQR defaults and assign a multi-character
! money-sign.
!
alter-Locale
  locale = 'System'
  money-sign = 'AU$'           ! Australian dollars

let #value = 123456
show #value edit '$999,999,999,999.99'
show #value edit '$$$$,$$$$999,999.99'

```

Produces the following output:

```

AU$      123,456.00
AU$123,456.00

```

```

!
! Move the money-sign to the right side of the value. Note
! the leading space.
!
alter-locale
  money-sign = ' AU$'           ! Australian dollars
  money-sign-location = right

let #value = 123456
show #value edit '$999,999,999,999.99'

```

```
show #value edit '$$$$,$$$$999,999.99'
```

Produces the following output:

```
123,456.00 AU$
123,456.00 AU$
```

```
!
! Reset locale to SQR defaults and flip the thousand and
! decimal separator characters.
!
alter-locale
  locale = 'System'
  thousand-separator = '.'
  decimal-separator = ','
```

```
let #value = 123456
show #value edit '999,999,999,999.99'
```

Produces the following output:

```
123.456,00
```

```
!
! Reset locale to SQR defaults and change the date and time
! separators
!
alter-locale
  locale = 'System'
  date-separator = '-'
  time-separator = '.'
```

```
let $edit = 'Mon/DD/YYYY HH:MI:SS'
let $date = strtodate('Jan/01/2004 11:22:33', $edit)
show $date edit :$edit
```

Produces the following output:

```
Jan-01-2004 11.22.33
```

```
!
! Reset locale to SQR defaults and change the text used with
! the edit options 'na', 'am', 'pm', 'bc', 'ad'
!
alter-locale
  locale = 'System'
  edit-option-na = 'not/applicable'
  edit-option-am = 'a.m.'
  edit-option-pm = 'p.m.'
  edit-option-bc = 'b.c.'
  edit-option-ad = 'a.d.'
```

```
let $value = ''
let $edit = 'Mon DD YYYY HH:MI'
```



```

let $date1 = strtodate('Jan 01 2004 11:59', $edit)
let $date2 = strtodate('Feb 28 2004 12:01', $edit)
show $value edit '999,999,999,999.99Na'
show $date1 edit 'Mon DD YYYY HH:MI:SS PM'
show $date2 edit 'Mon DD YYYY HH:MI:SS pm'

```

Produces the following output:

```

      Not/Applicable
Jan 01 2004 11:59:00 A.M.
Feb 28 2004 12:01:00 p.m.

```

```

!
! Input some dates using the 'system' locale and
! output using other locales from the SQR.INI file.
!
alter-locale
  locale = 'System'
let $date1 = strtodate('Jan 01 2004', 'Mon DD YYYY')
let $date2 = strtodate('Feb 28 2004', 'Mon DD YYYY')
let $date3 = strtodate('Mar 15 2004', 'Mon DD YYYY')
show 'System:'
show
show $date1 edit 'Month DD YYYY' ' is ' $date1 edit 'Day'
show $date2 edit 'Month DD YYYY' ' is ' $date2 edit 'Day'
show $date3 edit 'Month DD YYYY' ' is ' $date3 edit 'Day'
alter-locale
  locale = 'German'
show
show 'German:'
show
show $date1 edit 'DD Month YYYY' ' ist ' $date1 edit 'Day'
show $date2 edit 'DD Month YYYY' ' ist ' $date2 edit 'Day'
show $date3 edit 'DD Month YYYY' ' ist ' $date3 edit 'Day'
alter-locale
  locale = 'Spanish'
show
show 'Spanish:'
show
show $date1 edit 'DD Month YYYY' ' es ' $date1 edit 'Day'
show $date2 edit 'DD Month YYYY' ' es ' $date2 edit 'Day'
show $date3 edit 'DD Month YYYY' ' es ' $date3 edit 'Day'

```

Produces the following output:

```

System:

January 01 2004 is Thursday
February 28 2004 is Saturday
March 15 2004 is Monday

```

```

German:

```

```
01 Januar 2004 ist Donnerstag
28 Februar 2004 ist Samstag
15 März 2004 ist Montag
```

Spanish:

```
01 enero 2004 es jueves
28 febrero 2004 es sábado
15 marzo 2004 es lunes
```

See Also

The DISPLAY, LET, MOVE, PRINT, AND SHOW commands in this section.

[Chapter 7, “Using the PSSQR.INI File and the PSSQR Command Line,” page 277](#)

ALTER-PRINTER

Syntax

ALTER-PRINTER

[POINT-SIZE={*point_size_num_lit*|_var}]

[FONT-TYPE={*font_type*|*txt_var*}]

[SYMBOL-SET={*symbol_set_id*|*txt_var*}]

[FONT={*font_int_lit*|_var}]

[PITCH={*pitch_num_lit*|_var}]

Description

Alters printer parameters at runtime.

You can place the ALTER-PRINTER command in any part of an SQR program except the SETUP section.

ALTER-PRINTER attempts to change the attributes of the *current* printer for the *current* report. If an attribute does not apply to the *current* printer, it is ignored. For example, ALTER-PRINTER is ignored if it specifies proportional fonts for a report printed on a line printer. When your program is creating multiple reports and the printer is shared by another report, the attributes are changed for that report as well.

Parameters

Parameter	Description
POINT-SIZE	Specifies the new font point size.
FONT-TYPE	Specifies the new font type. Enter PROPORTIONAL or FIXED.
SYMBOL-SET	Specifies the new symbol set identifier.
FONT	Specifies the new font as a number. (For example, 3 = Courier and 4 = Helvetica.)
PITCH	Specifies the new pitch in characters per inch. See the DECLARE-PRINTER arguments table for information about these arguments.

Example

Change the font and symbol set for the current printer.

```

alter-printer

font=4    ! Helvetica

symbol-set=12U    ! PC-850 Multilingual

```

If the output prints to a PostScript printer, the SYMBOL-SET argument is ignored; however, if the .spf file is kept (-KEEP) and later printed on an HP LaserJet, the symbol set 12U can be used.

See Also

The DECLARE-PRINTER command and the -KEEP command line flag.

ALTER-REPORT

Syntax

```

ALTER-REPORT
[HEADING={heading_name_txt_lit|_var|_col}]
[HEADING-SIZE={heading_size_int_lit|_var|_col}]
[FOOTING={footing_name_txt_lit|_var|_col}]
[FOOTING-SIZE={heading_size_int_lit|_var|_col}]

```

Description

Alters some of the report-specific functionality.

This command gives you the ability to dynamically change those heading and/or footing sections that are active for the current report. You can also change how much space the heading and/or footing sections occupy.

If the HEADING or FOOTING value is set to NONE then that section is disabled for the current report.

If the HEADING or FOOTING value is set to DEFAULT then that section reverts to whatever was in effect when the report was initiated.

If no HEADING or FOOTING value is set then the HEADING-SIZE and/or FOOTING-SIZE values affect the HEADING/FOOTING currently being used.

If the ALTER-REPORT command was not invoked from within a BEGIN-HEADING and/or BEGIN-FOOTING section and the page has not been written to, then the assignment takes effect immediately; otherwise it takes effect for the next page.

Parameters

Parameter	Description
HEADING	Specifies the name of the BEGIN-HEADING section to use.
HEADING-SIZE	Specifies the amount of space the BEGIN-HEADING section will occupies in the page.
FOOTING	Specifies the name of the BEGIN-FOOTING section to use.
FOOTING-SIZE	Specifies the amount of space the BEGIN-FOOTING section will occupies in the page

Example

```

begin-footing 2 name=confidential

```

```

    print 'Company Confidential' (1,1,0) center
    page-number (2,37,0)
end-footing

begin-footing 2          name=proprietary
    print 'Company Proprietary' (1,1,0) center
    page-number (2,37,0)
end-footing

begin-report
alter-report
    footing = 'Proprietary'
    footing-size = 6                ! Increase depth
.
.
.
end-report

```

See Also

The BEGIN-FOOTING and the BEGIN-HEADING commands in this section.

ARRAY-ADD, ARRAY-DIVIDE, ARRAY-MULTIPLY, ARRAY-SUBTRACT

Syntax

```

ARRAY-ADD{src_num_lit|_var|_col}...TO
dst_array_name (element_lit|_var|_col)[field
[(occurs_lit|_var|_col)]]...
ARRAY-DIVIDE{src_num_lit|_var|_col}...INTO
dst_array_name (element_int_lit|_var|_col)[field
[(occurs_lit|_var|_col)]]...
ARRAY-MULTIPLY{src_num_lit|_var|_col}...TIMES
dst_array_name (element_int_lit|_var|_col)[field
[(occurs_lit|_var|_col)]]...
ARRAY-SUBTRACT{src_num_lit|_var|_col}...FROM
dst_array_name (element_int_lit|_var|_col)[field
[(occurs_lit|_var|_col)]]...

```

Description

These four commands perform arithmetic on one or more elements in an array.

The following information applies to the array arithmetic commands:

- The array must first be created using the CREATE-ARRAY command.
- The four array arithmetic commands perform on one or more source numbers, placing the result into the corresponding field in the array.
- Array element and field occurrence numbers can be numeric literals (123) or numeric variables (#j) and can be from zero (0) to one less than the size of the array.

- If fields are not listed, the results are placed into consecutively defined fields in the array. If fields are listed, results are placed into those fields, at the specified occurrence of the field. If an occurrence is not specified, the zeroth (0) occurrence is used.
- All fields must be of the type number, decimal, float, or integer. They cannot be of type date, char, or text.
- If division by zero is attempted, a warning message appears, the result field is unchanged, and SQR continues executing.

Parameters

Parameter	Description
src_num_lit _var _col	Source values are added to, divided into, multiplied times, or subtracted from the respective destination array fields. All variables must be numeric in type.
dst_array_name (element_int_lit _var _col) [field [(occurs_lit _var _col)]]	Destination array fields contain the results after the operation. All variables must be numeric in type.

Example

The following example adds &salary and #comm to the first two fields defined in the emps array. The #j'th element of the array is used.

```
array-add &salary #comm to emps(#j)
```

The following example subtracts #lost, #count, and 1 from the fields loses, tot and sequence of the #j2'th element of the stats array.

```
array-subtract #lost #count 1 from stats(#j2) loses tot sequence
```

The following example multiplies occurrences 0 through 2 of the field p in the #i'th element of the percentages array by 2.

```
array-multiply 2 2 2 times percentages(#i) p(0) p(1) p(2)
```

The following example divides the #i2'th occurrence of the salesman field of the #j'th element of the commissions array by 100.

```
array-divide 100 into commissions(#j) salesman(#i2)
```

The following example uses the ARRAY-ADD command in an SQR program.

```
begin-setup
! declare arrays
create-array name=emps size=1                ! one row needed for this example
    field=Salary:number=35000                ! initialize to 35,000
    field=Comm:number=5000                   ! initialize to 5,000
end-setup

begin-program
do Main
end-program

begin-procedure Main local
! Show original contents of the arrays, then the modified arrays
! array-add
! retrieve values from the only row of array "emps"
```

```

get #sal #com FROM emps(0) Salary Comm
print 'Array-Add'          (+1, 1)

print 'Add 1000 to each column' (+1, 1)
print 'Salary' (+1, 3) bold underline
print 'Comm' (,25) bold underline

print #sal (+1, 1) money
print #com (,22) money

let #salary = 1000
let #commission = 1000
let #j = 0 ! address the array row with variable "#j"
! Add 1000 (in variables) to each column of row 0 (the 1st and only row)
array-add #salary #commission TO emps(#j)
! retrieved the new "added" values
get #sal #com FROM emps(0) Salary Comm
print #sal (+1,1) money
print #com (,22) money
end-procedure

```

See Also

The CREATE-ARRAY command for information about creating an array.

The CLEAR-ARRAY command for information about clearing or initializing an array.

The GET, PUT, and LET commands for information about using arrays.

ASK

Syntax

ASK *substitution_variable* [*prompt*]

Description

Retrieves values for a compile-time substitution variable. The retrieval can be by user input, command-line arguments, or as entries in the @file on the command line.

The value of the substitution variable replaces the reference variable in the program. Variables are referenced by enclosing the variable name in braces, for example, '{state_name}'. If the substitution variable is text or date, surround the brackets by single quotes. Substitutions are made as the program is compiled and are saved in the .sqt file. Each variable can be referenced multiple times.

ASK is used only in the SETUP section and must appear prior to any substitution variable references.

You cannot break the ASK command across program lines.

Parameters

Parameter	Description
Substitution_variable	The variable to be used as the substitution variable.
Prompt	An optional literal text string to be displayed as a prompt if the value for the substitution variable is not entered on the command line or in an argument file.

Example

In the following example, state takes the value entered by the user in response to the prompt *Enter state for this report*.

```
begin-setup
  ask state 'Enter state for this report'
end-setup
...
begin-select
  name, city, state, zip
from customers where state = '{state}'
end-select
```

See Also

The INPUT command for information about input at runtime.

Enterprise PeopleTools 8.45 PeopleBook: SQR for PeopleSoft Developers, “Compiling Programs and Using SQR Execute”

BEGIN-DOCUMENT

Syntax

BEGIN-DOCUMENT *position*

END-DOCUMENT

Description

Begins a document paragraph. A document paragraph enables you to write free-form text to create form letters, invoices, and so on.

Database columns, SQR variables, and document markers can be referenced within a document. Their location in the document determines where they are printed on the page. You should not use tabs inside a document paragraph. To indent text or field use the spacebar. Note also that if the variables being printed inside a document paragraph are variable in length, you might want to manipulate the variable outside the document paragraph.

Note. A document must be executed before you can reference its document markers. Because documents can be printed at relative positions on the page, the actual location of a document marker may not be known by SQR until the document itself has been executed.

Parameters

Parameter	Description
position	The location on the page where the document begins. The position can be fixed or relative to the current position.

Example

```
begin-document (1,1)
.b
Dear $firstname
...
end-document
```

See Also

The END-DOCUMENT command.

Enterprise PeopleTools 8.45 PeopleBook: SQR for PeopleSoft Developers, “Creating Form Letters”

BEGIN-EXECUTE

Syntax

```
BEGIN-EXECUTE
[CONNECTION=uq_txt_lit]
[ON-ERROR=procedure[(arg1[,argi]...)]]
[RSV=num_var]
[STATUS=list_var|num_var|txt_var]
[SCHEMA=txt_lit|txt_var]
[PROCEDURE=txt_lit|txt_var]
[PARAMETERS=(arg1[IN|INOUT|NULL[,argi[IN|INOUT]]...]]]
|COMMAND=txt_lit|txt_var]
|GETDATA=txt_lit|txt_var]
[BEGIN-SELECT[BEFORE=sqr_procedure[(arg1[,argi]...)]]]
[AFTER=sqr_procedure[(arg1[,argi]...)]]]
col-name type=char|text|number|date[edit-mask]
[on-break]...
FROM ROWSETS=({m,-n,n-m,m-all})
|FROM PARAMETER=txt_lit|txt_var
END-SELECT]
END-EXECUTE
```

Description

Begins a new construct. In a BEGIN-EXECUTE paragraph, the syntax of BEGIN-SELECT varies as shown in the following syntax:

Parameters

Parameter	Description
CONNECTION	Identifies a name previously specified using the DECLARE-CONNECTION construct. If you do not specify a name, SQR Server uses the default connection. The default connection is defined by the command-line entries for datasource (DSN), username (USER), and password (PASSWORD). Name is not case sensitive.
ON-ERROR	Declares a procedure to execute if an error occurs.
RSV	Row Set Variable. A global SQR variable containing the row set being retrieved.
STATUS	Identifies a list or scalar variable that receives the status of the stored procedure.
SCHEMA	Identifies the location in the datasource of the object being queried.
PROCEDURE	The name of the datasource-stored procedure to be executed. If the datasource is SAP R/3, this procedure is a BAPI. The name may include spaces.
PARAMETER_LIST	Scalar and/or list variables of the form list_var num_lit txt_lit txt_var num_var any_col. If you do not specify the keywords IN or INOUT, IN is the default. Specify all parameters in order; leaving any parameters unnamed causes a syntax error. To ignore a parameter, fill its position with the keyword NULL. This results in a null value for that parameter position.
COMMAND	A text string you pass to the datasource without modification by SQR. This string can include embedded SQR variables.
BEFORE/AFTER	Names an SQR procedure to be executed before or after the row set. The procedure is not performed unless at least one row is returned from the specified rowsets.
FROM ROWSET	Special case addition to the BEGIN-SELECT syntax. Available for use with all datasource types, including SAP R/3 and JDBC. Names the rowsets from which to retrieve the column variables. If you specify more than one row set, use identical column name/type signatures. Row set numbers must be sequential from left-to-right within the parentheses, and they must not overlap as in this example: (1-3, 2-4). Numeric literals or #variables are allowed.
FROM PARAMETER	Special case addition to the BEGIN-SELECT syntax. Available only for SAP R/3 datasources. Use only in conjunction with PROCEDURE keyword. This argument names an output parameter containing one or more rows from which the column variables are to be retrieved.
PROPERTIES = (txt_var strlit = txt_var strlit num_var num_lit any_col, ...)	Specifies a (set of) keyword/value pairs that represent modifications to be made to the Properties of the datasource (specified by the CONNECTION = statement). An arbitrary number of such pairs can be specified.

Note. This is a similar concept to the PARAMETERS = statement in DECLARE-CONNECTION, with the minor difference being that the properties specified here alter the flow of returned information, as opposed to just setting login properties. Can be used in conjunction with any data-access model (Procedure, Command, Getdata). An application of this statement would be in the MDB setting, where it might be used to specify such things as Level, Generation, or Include-Column. For example, PROPERTIES = ('SetColumn' = 5)

Example

```
begin-setup
  declare-variable
```

```

        date $when_ordered
        text $ship_method
        integer #theRow
        integer #theStatus
        integer #howMany
    end-declare
end-setup

input #howMany type=integer
input $pword
let %parm1 = list($when_ordered, $ship_method, #howMany)

declare-connection SAPR3
user=scott
parameters=clientno=5;node=starfish;
end-declare

alter-connection
    name=SAPR3
    password=$pword

Begin-Execute
    connection=SAPR3
    rsv=#theRow
    status=#theStatus
        on-error=it_failed(#theStatus)
        procedure='CreditHistory version 5'
        parameters=(%parm1,'recalculate')

    print 'proc ran OK, status is ' (+1,1)
    print #theStatus (,+5) edit 999

Begin-Select before=do_eject after=cleanup
city &col=char (1,1) on-break level=1 after=city-tot
keyval type=number (1,+1)
rcvd type=date (0,+2)
from Rowsets=(1)
End-Select

End-Execute

```

See Also

The EXECUTE command.

BEGIN-FOOTING**Syntax**

```

BEGIN-FOOTING footing_lines_int_lit
[FOR-REPORTS=(report_name1[,report_namei]...)]
[FOR-TOCS=(toc_name1[,toc_namei]...)]

```

```
[NAME={footing_name}]
END-FOOTING
```

Description

Begins the FOOTING section.

The FOOTING section defines and controls information to be printed at the bottom of each page.

You must define the *report_name* in a DECLARE-REPORT paragraph. If you do not use DECLARE-REPORT, the footing is applied to all reports. You can also specify FOR-REPORTS=(ALL). Note that the parentheses are required.

You can specify more than one BEGIN-FOOTING section; however, there can be only one for each report. A BEGIN-FOOTING section with FOR-REPORTS=(ALL) can be followed by other BEGIN-FOOTING sections for specific reports, which override the ALL setting.

You must define the *toc_name* in a DECLARE-TOC paragraph. You can also specify FOR-TOCS=(ALL). Note that the parentheses are required.

You can specify more than one BEGIN-FOOTING section; however, there can be only one section for each table of contents. A BEGIN-FOOTING section with FOR-TOCS=(ALL) can be followed by other BEGIN-FOOTING sections for a specific table of contents, which override the ALL setting.

The BEGIN-FOOTING section can be shared between reports and tables of contents.

You can print outside the footing area of the report, that is, in the body area, from the footing, but you cannot print in the footing area from the body.

Parameters

Parameter	Description
footing_lines_int_lit	The number of lines to be reserved at the bottom of each page.
FOR-REPORTS	Specifies the reports to which this footing applies. This argument is required only for a program with multiple reports. If you are writing a program that produces a single report, you can ignore this argument.
FOR-TOCS	Specifies the table of contents to which this heading applies.
NAME	Specifies the name to be associated with this footing section. This is used in conjunction with the ALTER-REPORT command. The name cannot be NONE or DEFAULT.

Example

```
begin-footing 2 for-reports=(customer, summary)
  print 'Company Confidential' (1,1,0) center
  page-number (2,37,0)
end-footing
begin-footing 2 ! For all reports
  print 'Division Report' (1,1,0) center
  page-number (2,37,0)
end-footing
begin-footing 2 for-tocs=(all)
  print 'Table of Contents' (2,1)
```

```
    let $page = roman(#page-count)      ! ROMAN numerals
    print $page (,64)
end-footing
```

See Also

The ALTER-REPORT command for information about dynamic headings and footings.

The DECLARE-LAYOUT command for information about page layout.

The DECLARE-REPORT command for information about programs with multiple reports.

The DECLARE-TOC command for information about the table of contents.

The END-FOOTING command.

BEGIN-HEADING

Syntax

```
BEGIN-HEADING heading_lines_int_lit
[FOR-REPORTS=(report_name1[, report_namei]...)]
[FOR-TOCS=(toc_name1[, toc_namei]...)]
[NAME={footing_name}]
END-HEADING
```

Description

Begins a HEADING section.

The HEADING section defines and controls information to be printed at the top of each page.

You must define the *report_name* in a DECLARE-REPORT paragraph. If you do not use DECLARE-REPORT, the heading is applied to all reports. You can also specify FOR-REPORTS=(ALL). Note that the parentheses are required.

You can specify more than one BEGIN-HEADING section; however, there can be only one for each report. A BEGIN-HEADING section with FOR-REPORTS=(ALL) can be specified followed by other BEGIN-HEADING sections for specific reports, which override the ALL setting.

You must define the *toc_name* in a DECLARE-TOC paragraph. You can also specify FOR-TOCS=(ALL). Note that the parentheses are required.

You can specify more than one BEGIN-HEADING section; however, there can be only one section for each table of contents. A BEGIN-HEADING section with FOR-TOCS=(ALL) can be specified, followed by other BEGIN-HEADING sections for specific tables of contents, which override the ALL setting.

The BEGIN-HEADING section can be shared between reports and a table of contents.

You can print outside the heading area of the report—that is, in the body area—from the heading, but you cannot print in the heading area from the body.

Parameters

Parameter	Description
heading_lines_int_lit	The number of lines to be reserved at the top of each page.
FOR-REPORTS	Specifies the reports to which this heading applies. This is required only for a program with multiple reports. If you are writing a program that produces a single report, you can ignore this argument.
FOR-TOCS	Specifies the table of contents to which this heading applies.
NAME	Specifies the name to be associated with this heading section. This option cannot be used if FOR-REPORTS or FOR-TOCS is also specified. This is used in conjunction with the ALTER-REPORT command. The name cannot be NONE or DEFAULT.

Example

```

begin-heading 2                                ! Use 2 lines for
print $current-date (1,1) edit MM/DD/YY        ! heading,
  print 'Sales for the Month of ' (1,30)        ! 2nd is blank.
  print $month ( )
end-heading
begin-heading 2 for-tocs=(all)
  print 'Table of Contents' (1,1) bold center
end-heading

```

See Also

The ALTER-REPORT command for information about dynamic headings/footings.
 The DECLARE-LAYOUT command for information about page layout.
 The DECLARE-REPORT command for information about programs with multiple reports.
 The DECLARE-TOC command for information about Table of Contents.
 The END-HEADING command.

BEGIN-PROCEDURE

Syntax

```

BEGIN-PROCEDURE procedure_name [LOCAL](arg1
[, argi]...)
END-PROCEDURE

```

Description

Begins a procedure. A procedure is one of the most powerful parts of the SQR language. It modularizes functions and provides standard execution control.

The procedure name must be unique. The name is referenced in DO commands. Procedures contain other commands and paragraphs (for example, SELECT, SQL, DOCUMENT).

By default, procedures are global. That is, variables or columns defined within a procedure are known and can be referenced outside of the procedure.

A procedure is local when the word **LOCAL** appears after the procedure name or when the procedure is declared with arguments. That is, variables declared within the procedure are available only within the procedure, even when the same variable name is used elsewhere in the program. In addition, any query defined in a local procedure will have local database column variable names assigned that do not conflict with similarly named columns defined in queries in other procedures.

SQR procedures can be called recursively. However, unlike C or Pascal, SQR maintains only one copy of the local variables and they are persistent.

Arguments passed by a **DO** command to a procedure must match in number:

- Database text or date columns, string variables, and literals can be passed to procedure string arguments. If passing a date string to a date argument, the date string must be in the format specified by the **SQR_DB_DATE_FORMAT** setting, or a database dependent format, or the database-independent format **SYYYMMDD[HH24[MI[SS[NNNNNN]]]]**.

See the Default Database Formats table in the **PRINT** command description.

- Database numeric columns, numeric variables, and numeric literals can be passed to procedure numeric arguments.
- Numeric variables (**DECIMAL**, **INTEGER**, **FLOAT**) can be passed to procedure numeric arguments without regard to the argument type of the procedure. SQR automatically converts the numeric values upon entering and leaving the procedure as required.
- Date variables or columns can be passed to procedure date or string arguments. When a date variable or column is passed to a string argument, the date is converted to a string according to the following rules:
 - For **DATETIME** columns and SQR **DATE** variables SQR uses the format specified by the **SQR_DB_DATE_FORMAT** setting. If this has not been set, the first database-dependent format as listed in the Default Database Formats table.
 - For **DATE** columns the format specified by the **SQR_DB_DATE_ONLY_FORMAT** setting is used. If this has not been set, the format listed in the Default Database Formats table is used.
 - For **TIME** columns the format specified by the **SQR_DB_TIME_ONLY_FORMAT** setting is used. If this has not been set, the format listed in the TIME Column Formats table is used.

To reference or declare global variables from a local procedure, add a leading underscore to the variable name, after the initial **\$**, **#**, or **&**. (Example: **#_amount**)

Note. All the SQR reserved variables, such as **#sql-status** and **\$sql-error**, are global variables. Within a local procedure, they must be referenced using the leading underscore: **#_sql-status** or **\$_sql-error**.

Parameters

Parameter	Description
procedure_name	Specifies a unique name for this procedure. Procedure names are not case sensitive.
LOCAL	Specifies that this is a local procedure.
arg1 [, argi]...	Specifies arguments to be passed to or returned from the procedure. Arguments can be either string variables (\$arg), numeric variables (#arg), or date variables (\$arg). If you want to return a value passed back to the calling DO command, place a colon (:) before the variable name. The arguments of the BEGIN-PROCEDURE and DO commands must match in number, order, and type.

Example

The following example shows a procedure, **main**, that also executes the procedure **print_list**, for each row returned from the Select statement. No parameters are passed to **print_list**.

```
begin-procedure main
begin-select
name
address
phone
  do print_list
from custlist order by name
end-select
end-procedure          ! main
```

In the following example, five arguments are passed to the **Calc** procedure:

```
do Calc (&tax, 'OH', &county_name, 12, #amount)

begin-procedure Calc(#rate, $state, $county, #months, :#answer)
.
.
.
let #answer = ...
end-procedure
```

In the preceding example the value for *:#answer* is returned to *#amount* in the calling DO command.

The following example references global variables:

```
begin-procedure print-it ($a, $b)
print  $_deptname (+2,5,20)          ! $deptname is
print  $a           (+1)             ! declared outside
print  $b           (+1)             ! this procedure
end-procedure
```

See Also

The DO and END-PROCEDURE commands.

The Default Database Formats table in the [Chapter 2, “SQR Command Reference,” PRINT, page 175](#) command description.

BEGIN-PROGRAM

Syntax

```
BEGIN-PROGRAM
END-PROGRAM
```

Description

Begins the PROGRAM section of an SQR program.

After processing the commands in the SETUP section, if any, SQR starts program execution at the BEGIN-PROGRAM section. The PROGRAM section typically contains a list of DO commands, though other commands can be used. This is the only required section in an SQR program.

Example

```
begin-program
  do startup
  do main
  do finish
end-program
```

See Also

The BEGIN-REPORT, BEGIN-SETUP, and END-PROGRAM command.

BEGIN-SELECT

Syntax

```
BEGIN-SELECT [DISTINCT] [-Cnn] [-Bnn] [-XP] [-NR] [-SORTnn]
[-LOCK{RR|CS|RO|RL|XX}] [-DBdatabase]
[-DBconnectionstring]
[LOOPS=nn] [ON-ERROR=procedure[(arg1[,argi]...)]]
{column} [&synonym]
{expression &synonym}
[[$columnname] &synonym = (char | number | date)]
[SQR commands]
FROM {table,...|[table:$tablename]}
      [additional SQL]
      [$variable]
END-SELECT
```

Description

Begins a SELECT paragraph. A SELECT paragraph is the principal means of retrieving data from the database and printing it in a report. A SELECT paragraph must be inside a PROCEDURE or BEGIN-PROGRAM section.

Note that SELECT * FROM is not a valid SQR SQL statement. BEGIN-SELECT can be placed inside a BEGIN-PROGRAM section.

Parameters

The following are the parameters.

Note. The arguments can span multiple lines; however, do not use the first character position unless the continuation character terminated the previous line. Otherwise, the argument will be misconstrued as a Select column.

Parameter	Description
DISTINCT	Specifies that you want to eliminate duplicate rows from your query.
-Cnn	(Oracle) Sets the context area size (buffer size for query) to larger or smaller than the default; this option is rarely needed.
-Bnn	(ODBC, Oracle, Sybase CT-Lib) Sets the number of rows to retrieve at one time. This is for performance purposes only. Regardless of this setting, all rows are selected. The default, without using -B, is 10 rows. An overall setting for a program can be indicated on the SQR command line with -B, which can be overridden by a separate -B flag on each BEGIN-SELECT command.
-XP	(Sybase) Prevents the creation of a stored procedure for the SELECT paragraph. When -XP is specified, SQR generates a new SQL statement using the current value of any bind variables each time the BEGIN-SELECT is executed. This disables the potential performance optimization created by stored procedures. If you change the variables frequently during execution and you do not want SQR to automatically create stored procedure, use this flag. You can also use -XP if the username/password to your program does not have permission to create stored procedures. However, if you do not change variables frequently during execution, the use of stored procedures may optimize your program's performance. In that case, do not use this argument. Note also that -XP is available as a command-line flag. -XP improves performance when you use bind variables and dynamic query variables in the same query. Each time the dynamic query variable changes in value, a new stored procedure is created. If the dynamic query variable changes often and the query contains bind variables, you create many stored procedures if you do not use -XP.
-DBconnectionstring	(ODBC) Specifies the ODBC connection string for this SELECT paragraph only. A connection string has the following syntax: DSN=data_source_name[:keyword=value[:keyword=value[:...]]] This option enables you to combine data from multiple databases in one program. For example, a connection string for an Oracle database named "ora8" might look like the following: 'DSN=ora8;UID=scott;PWD=tiger' where DSN, UID, and PWD are keywords common to all drivers (representing: name, user ID, and password, respectively). Connection string options are always separated by a semicolon (;). Other driver-specific options may be added to the connection string using driver-defined keywords. See your ODBC driver documentation for available options.
LOOPS	Specifies the number of rows to retrieve. After the specified number has been processed, the SELECT loop exits.
ON-ERROR	Declares a procedure to execute if an error occurs due to incorrect SQL syntax. Error trapping should be used in conjunction with dynamic query variables. SELECT paragraphs without dynamic variables are checked for errors before the program is processed and therefore do not require a special error procedure. You can optionally specify arguments to be passed to the ON-ERROR procedure. Arguments can be any variable, column, or literal.

Example

In this example, duplicate rows are not selected for the city, state, and zip columns because of the **distinct** keyword. The numbers within parentheses accompanying City, State, and Zip define the column positions of these rows. Column names can not have spaces in front of them.

See *Enterprise PeopleTools 8.45 PeopleBook: SQR for PeopleSoft Developers*, "Using Column Variables".

```

begin-select distinct
city      (1,1,30)
state     (0,+2,2)
zip       (1,+3,6)
from custlist order by city
end-select

```

In this example, the first two columns may, or may not, be present when the statement is compiled. The column `cust_id` is declared to be a number. A runtime error is produced if the database table, as identified by the variable `$table_name`, declares it to be something other than a number.

```

begin-select          loops=100
[$col_var_char]      &col1=char
[$col_var_num]       &col2=number
cust_id              &id=number
from [$table_name]
[$where clause]
[$order_by_clause]
end-select

```

See Also

Enterprise PeopleTools 8.45 PeopleBook: SQR for PeopleSoft Developers, “Selecting Data From the Database” and *Enterprise PeopleTools 8.45 PeopleBook: SQR for PeopleSoft Developers*, “Using Dynamic SQL and Error Checking”.

The END-SELECT and EXIT-SELECT commands.

BEGIN-SETUP

Syntax

```

BEGIN-SETUP
END-SETUP

```

Description

Begins a SETUP section. This section is optional, but if included, it is processed prior to the BEGIN-PROGRAM, BEGIN-HEADING, and BEGIN-FOOTING sections.

The SETUP section should be the first section in the program.

The SETUP section contains commands that determine the overall characteristics of the program. The commands used in the SETUP section cannot be used elsewhere unless specified. The SETUP section can include the following commands:

```

ASK
BEGIN-SQL

```

(The BEGIN-SQL command can also be used in BEGIN-PROCEDURE paragraphs.)

```

CREATE-ARRAY

```

(The CREATE-ARRAY command can also be used in the other sections of an SQR program.)

```

DECLARE-CHART
DECLARE-IMAGE
DECLARE-LAYOUT
DECLARE-PRINTER

```

DECLARE-PROCEDURE
 DECLARE-REPORT
 DECLARE-VARIABLE

(The DECLARE-VARIABLE command can also be used in LOCAL procedures.)

DECLARE-TOC
 LOAD-LOOKUP

(The LOAD-LOOKUP command can also be used in the other sections of an SQR program.)

USE

(Sybase and Microsoft SQL Server only.)

Example

```
begin-setup
  declare-layout customer_list
    paper-size=(8.5, 11)
    left-margin=1.0
    right-margin=1.0
  end-declare
end-setup
```

See Also

The ASK, BEGIN-SQL, CREATE-ARRAY, LOAD-LOOKUP, and USE commands.

BEGIN-SQL

Syntax

```
BEGIN-SQL [-Cnn] [-XP] [-NR] [-SORTnn]
  [-LOCK{RR|CS|RO|RL|XX}]
  [-DBdatabase] [-DBconnectionstring]
  [ON-ERROR=procedure[(arg1[,argi]...)](non-setup)
  | [ON-ERROR={STOP|WARN|SKIP}](insetup)
END-SQL
```

Description

Begins an SQL paragraph. This paragraph can reside in a BEGIN-PROCEDURE, BEGIN-SETUP, or BEGIN-PROGRAM section.

BEGIN-SQL starts all SQL statements except SELECT, which has its own BEGIN-SELECT paragraph. If a single paragraph contains more than one SQL statement, each statement except the last must be terminated by a semicolon (;).

If a single paragraph contains more than one SQL statement, and the -C flag is used, all are assigned the same context area size or logical connection number.

Only non-SELECT statements can be used (except SELECT INTO for Sybase and Microsoft SQL Server). Columns and variables can be referenced in the SQL statements.

Stored Procedures

For Sybase and Microsoft SQL Server, SQR supports stored procedures with the EXECUTE command. For Oracle, stored procedures are implemented using PL/SQL in the BEGIN-SQL paragraph.

For some databases such as Oracle, using DDL statements within a BEGIN-SQL paragraph causes a commit of outstanding inserts, updates, and deletes and releases cursors. For this reason, ensure that these are done in the proper order or unpredictable results may occur.

Oracle PL/SQL

For Oracle, PL/SQL is supported in a BEGIN-SQL paragraph. This requires an additional semicolon at the end of each PL/SQL statement. See the following Oracle example.

For Oracle PL/SQL:

```
begin-sql
declare
    varpl varchar2 (25);;
    var2 number (8,2);;
begin
    varpl := 'abcdefg';;
    $v1 := varpl;;
    $v2 := '1230894asd';;
    var2 := 1234.56;;
    #v := var2;;
end;;
end-sql
```

For Oracle stored procedures:

```
begin-sql
begin
    #dept_number := get_dept_no($dept_name);;
end;;
end-sql
```

Parameters

Parameter	Description
-Cnn	(Oracle) Sets the context area size (buffer size for query) to larger or smaller than the default; this option is rarely needed.
-XP	(Sybase) Prevents the creation of a stored procedure for the SQL paragraph. When -XP is specified, SQR generates a new SQL statement using the current value of the bind variables each time the BEGIN-SQL is executed. This disables the performance optimization created by stored procedures. If you change the variables frequently during execution and you do not want SQR to automatically create stored procedures, use this flag. You may also use it if your program does not have permission to create stored procedures. However, if you do not change variables frequently during execution, the use of stored procedures optimizes the performance of the program. In that case, do not use this argument. -XP improves performance when you use bind variables and dynamic query variables in the same query. Each time the dynamic query variable changes in value, a new stored procedure is created. If the dynamic query variable changes often and the query contains bind variables, you create many stored procedures if you do not use -XP.
-DBconnectionstring	(ODBC) Specifies the ODBC connection string for this SQL paragraph only. A connection string has the following syntax: DSN=data_source_name[;keyword=value[;keyword=value[...]]] This option enables you to combine data from multiple databases in one program. For example, a connection string for an Oracle named "ora8" might look like the following: 'DSN=ora8;UID=scott;PWD=tiger' where DSN, UID, and PWD are keywords common to all drivers (representing name, user ID, and password, respectively). Connection string options are always separated by a semicolon (;). Other driver-specific options may be added to the connection string using driver-defined keywords. See your ODBC driver documentation for available options.
ON-ERROR	Declares a procedure to execute if an error occurs due to incorrect SQL syntax except when executed in a BEGIN-SETUP section. By default, SQR reports any error and then halts; if an error procedure is declared, you can trap errors, report or log them, and continue processing. The procedure is invoked when an error occurs in any SQL statement in the paragraph. After the error procedure ends, control returns to the next SQL statement, if any. You can optionally specify arguments to be passed to the ON-ERROR procedure. Arguments can be any variable, column, or literal. If ON-ERROR is used in the SETUP section, it is a condition flag supporting the following conditions: STOP: Do not run the program. WARN: Run the program but with a warning message. SKIP: Ignore any errors and run the program.

Example

```
begin-sql
update orders set invoice_num = #next_invoice_num

where order_num = &order_num
```

```

end-sql

begin sql
delete orders

where order_num = &order_num;
insert into orders values ($customer_name, #order_num,...)
end-sql

```

See Also

Enterprise PeopleTools 8.45 PeopleBook: SQR for PeopleSoft Developers, “Using Dynamic SQL and Error Checking” and *Enterprise PeopleTools 8.45 PeopleBook: SQR for PeopleSoft Developers*, “Using Additional SQL Statements with SQR”.
 The END-SQL, BEGIN-PROCEDURE, and EXECUTE commands.
 The -S command-line flag.

BREAK

Syntax

```
BREAK
```

Description

Causes an exit from within an EVALUATE or WHILE command. Execution then continues to the command immediately following the END-WHILE or END-EVALUATE.

This command is used inside a WHILE ... END-WHILE loop or within an EVALUATE command.

See Also

The WHILE and EVALUATE commands.

CALL, CALL SYSTEM

Syntax

```
CALL subroutine USING {src_txt_lit|_var|_col}|{ src_num_lit|_var|_col}
{dst_txt_var|_num_var} [param]
```

To issue operating system commands from within an SQR program, use the following syntax:

```
CALL SYSTEM USING command status [ WAIT | NOWAIT ]
```

Description

Issues an operating system command or calls a subroutine that you have written in another language such as C or COBOL and passes the specified parameters.

You can write your own subroutines to perform tasks that are awkward in SQR.
 Subroutines can be written in any language.

Warning! PeopleSoft recommends that the UCALL function not use any database calls as it may cause erroneous results.

Used in an SQR program, CALL has the following format:

```
CALL your_sub USING source destination [param_literal]
CALL SYSTEM USING command status [WAIT|NOWAIT]
```

The CALL SYSTEM is a special subroutine that is provided as part of SQR to enable the program to issue operating system commands. Its arguments, *command*, *status*, and WAIT|NOWAIT are described in a moment.

The values of the source and destination variables and the parameter's literal value are passed to your subroutine. Upon return from the subroutine, a value is placed in the destination variable.

You must write the subroutine and call it in one of the supplied UCALL routines. (Optionally, you could rewrite UCALL in another language instead).

The source file UCALL.C contains sample subroutines written in C. The UCALL function takes the following arguments:

Argument	Description	How Passed
<i>callname</i>	Name of the subroutine.	By reference with a maximum of 31 characters, null terminated.
<i>strsrc</i>	Source string.	By reference with a maximum of 255 characters, null terminated.
<i>strdes</i>	Destination string.	By reference with a maximum of 255 characters.
<i>dblsrc</i>	Source double floating point.	By reference.
<i>dbldes</i>	Destination double floating point.	By reference.
<i>param</i>	Subroutine parameter string. It must be a literal.	By reference with a maximum of 80 characters, null terminated.

When you use the CALL command, your arguments are processed as follows:

- Calling arguments are copied into the variables depending on the type of argument. Strings are placed into *strsrc*, and numerics are placed into *dblsrc*.
- Return values are placed into *strdes* or *dbldes* depending on whether your destination argument for CALL is a string or numeric variable.

The destination arguments can also be used to pass values to your subroutine.

To access your subroutine, add a reference to it in UCALL, passing along the arguments you need.

You must relink SQR to CALL after compiling a user-defined function that becomes another SQR function.

If you have created a new object file, you must add your subroutine to the link command file: in UNIX/Linux it is called SQRMAKE; in Windows it is called SQREXT.MAK. (Alternatively, you could add your routine to the bottom of the UCALL source module that is already included in the link).

Your subroutine and calling SQR program are responsible for passing the correct string or numeric variables and optional parameter string to the subroutine. No checking is performed.

Parameters

Parameter	Description
subroutine	Specifies the name of your subroutine.
src_txt_lit _var _col	Specifies a text column, variable, or literal which is to be input to the called subroutine.
src_num_lit _var _col	Specifies a numeric column, variable (decimal, float, or integer), or literal that is to be input to the called subroutine.
dst_txt_var _num_var	Specifies a text or numeric variable (decimal, float, or integer) into which the called subroutine is to place the return result.
param	Specifies an optional alphanumeric string of characters to be passed as a parameter to the subroutine.
SYSTEM	Specifies that this CALL command issues an operating system command.
command	Specifies the operating system command to execute. The command can be a quoted string, string variable, or column.
status	Contains the status returned by the operating system. The status must be a numeric variable. The value returned in status is system-dependent as follows: UNIX/Linux: Zero (0) indicates success. Any other value is the system error code. PC/Windows: A value less than 32 indicates an error.
WAIT NOWAIT	(Windows only): WAIT specifies that SQR suspend its execution until the CALL SYSTEM command has finished processing. NOWAIT specifies that SQR start the CALL SYSTEM command but continue its own processing while that command is in progress. For Windows, the default is NOWAIT. On UNIX/Linux operating systems the behavior is always WAIT.

Example

See these sample subroutines included in the UCALL source file:

- TODASH shows how strings can be manipulated.
- SQROOT demonstrates how to access numerics.
- SYSTEM invokes a secondary command processor.

The following code calls these subroutines:

```

call todash using $addr $newaddr '//.',           ! Convert these to
                                                    ! dashes
call sqroot using #n #n2                         ! Put square root of
                                                    ! #n into #n2
call sqroot using &hnvr #j                       ! Hnvr is numeric
                                                    ! database column
call system using 'dir' #s                       ! Get directory listing

```


The following example uses the SYSTEM argument to issue an operating system command. Some operating systems let you invoke a secondary command processor to enter one or more commands and then return to SQR.

```
! Unix (Type 'exit' to return to SQR)
!
let $shell = getenv('SHELL')
if isblank($shell)
    let $shell = '/bin/sh'
end-if
call system using $shell #unix_status

!Windows (Type 'exit' to return to SQR)
!
let $comspec = getenv('COMSPEC')
let $cmd = comspec || '/c' || $comspec || ' /k'
call system using $cmd #win_status wait
```

The following step-by-step example shows how to add a user-defined subroutine to SQR so that it can be invoked from SQR using the CALL command. For this example, the C function initcap, which makes the first letter of a string uppercase, is added. The function accepts two parameters. The first parameter is the string to which the initcap function is applied. The second is the resultant string.

To add initcap function to SQR, the following modifications are needed to the UCALL.C file, which was provided with SQR:

1. Add the prototype for the initcap function:

```
static void initcap CC_ARGS((char *, char *));
```

2. Modify the UCALL routine in the UCALL.C file. Specifically, add an else if statement at the end of the if statement to check for the initcap function:

```
void ucall CC_ARGL((callname, strsrc, strdes, dblsrc, dbldes, params))
...

/* If other subroutines, add "else if..." statement for each */
else if (strcmp(callname,"initcap") == 0)
    initcap(strsrc, strdes);
else
    sq999("Unknown CALLED subroutine: %s\n", callname);
return;
}
```

3. At the end of the UCALL.C file, add the initcap routine listed in the following example. The routine name must be lowercase; however, in your SQR program it can be referenced either uppercase or lowercase.

```
static void initcap CC_ARGL((strsrc, strdes))
CC_ARG(char *, strsrc)          /* Pointer to source string */
CC_LARG(char *, strdes)         /* Pointer to destination string */
{
    int nIndex;
    int nToUpCase;
    char cChar;
```

```

nToUpCase = 1;
for (nIndex = 0; cChar = strsrc[nIndex]; nIndex++)
{
    if (isalnum(cChar))
    {
        if (nToUpCase)
            strdes[nIndex] = islower(cChar) ? toupper(cChar) : cChar;
        else
            strdes[nIndex] = isupper(cChar) ? tolower(cChar) : cChar;
        nToUpCase = 0;
    }
    else
    {
        nToUpCase = 1;
        strdes[nIndex] = cChar;
    }
}
strdes[nIndex] = '\0';
}

```

Note. The CC_ARG macros are defined in the UCALL.C source module. The macros give the programmer the ability to define a fully prototyped function without having to worry if the C compiler supports the feature.

After these modifications, recompile UCALL.C and relink SQR. See the programming manual for your particular machine for details.

Finally, the following is an example of a simple SQR program which uses the initcap function:

```

begin-program
    input $name 'Enter the first name ' ! Get the first name from the user
    lowercase $name                      ! Set the first name to all lowercase
    call initcap using $name $capname    ! Now set the first character to uppercase
    input $last 'Enter the last name ' ! Get the last name from the user
    lowercase $last                     ! Set the last name to all lowercase
    call initcap using $last $caplast    ! Now set the first character to uppercase
    .
    .
    .

```

See Also

The LET command for information about user-defined functions using UFUNC.C that can be used in the context of an expression and that can pass and/or return any number of arguments.

CLEAR-ARRAY

Syntax

CLEAR-ARRAY NAME=*array_name*

Description

Resets each field of an array to its initial value.

The CLEAR-ARRAY command resets each field of the named array to the initial value specified for that field in the CREATE-ARRAY command. If no initial value was specified, numeric fields are reset to zero, text fields are reset to null, and date fields are reset to null. CLEAR-ARRAY also releases all memory used by the specified array and returns it to its pristine state.

Parameters

Parameter	Description
NAME	Specifies the name of the array to be cleared.

Example

```
clear-array name=custs
```

See Also

The CREATE-ARRAY command.

CLOSE

Syntax

```
CLOSE {filenum_lit|_var_col}
```

Description

Closes a file, specified by its file number.

Closes a flat file that has been previously opened using the OPEN command.

Parameters

Parameter	Description
filenum_lit _var_col	Specifies the number assigned to the file in the OPEN command.

Example

```
close 5
close #j
```

See Also

The OPEN, READ, and WRITE commands.

COLUMNS

Syntax

```
COLUMNS {int_lit|_var|_col}[int_lit|_var|_col]...
```

Description

Defines logical columns to be used for PRINT commands.

COLUMNS defines the leftmost position of one or more columns within the current page layout. It sets the first column as current.

COLUMNS can be used for printing data either down the page or across the page, depending on how you use the NEXT-COLUMN and USE-COLUMN commands.

The COLUMNS command applies only to the current report. If you want to print columns in more than one report, you must specify the COLUMNS command for each report.

The USE-COLUMN 0 turns off columns. See USE-COLUMN.

Parameters

Parameter	Description
int_lit _var _col	Specifies the left margin position of each column.

See Also

The NEXT-COLUMN, NEXT-LISTING, NEW-PAGE, USE-COLUMN, and USE-REPORT commands.

COMMIT

Syntax

COMMIT

Description

Causes a database commit.

COMMIT is useful when you are doing many inserts, updates, or deletes in an SQL paragraph. A database commit releases the locks on the records that have been inserted, updated, or deleted. Used with some databases, it also has other effects. For this reason, it should not be used within the scope of an active SELECT paragraph or unpredictable results may occur.

When the application completes, a commit is performed automatically unless a ROLLBACK was done or, for callable SQR, the -XC flag was set.

Other commands or options, such as the CONNECT command and the use of DDL statements for some databases with a BEGIN-SQL paragraph, can also cause the database to do a commit.

COMMIT is an SQR command and *should not* be used within an SQL paragraph. If used in an SQL paragraph, unpredictable errors can occur.

Note. The COMMIT command can be used with SQR servers for DB2, Informix, ODBC, and Oracle. For Sybase and Microsoft SQL Server, use BEGIN TRANSACTION and COMMIT TRANSACTION within SQL paragraphs as in the following code segment.

Example

```
add 1 to #updates_done
if #updates_done > 50
    commit
    move 0 to #updates_done
end-if
```

For Sybase:

```
...      ! Begin Transaction occurred previously
```

```

begin-sql
    insert into custlog values (&cust_num, &update_date)
end-sql
add 1 to #inserts
if #inserts >= 50
    begin-sql
        commit transaction;           ! Commit every 50 rows
        begin transaction             ! Begin next transaction
    end-sql
    move 0 to #inserts
end-if

...           ! One more Commit Transaction is needed

```

Warning! Any data being changed by a current transaction is locked by the database and cannot be retrieved in a SELECT paragraph until the transaction is completed by a COMMIT or ROLLBACK statement (or COMMIT TRANSACTION or ROLLBACK TRANSACTION statement for Sybase or Microsoft SQL Server).

CONCAT

Syntax

```

CONCAT {src_any_lit|_var|_col} WITH
dst_txt_var[:$]edit_mask

```

Description

Concatenates a variable, column, or literal with a string variable.

The contents of the source field are appended to the end of the destination field.

CONCAT can optionally edit the source field before appending it. Edit masks can be changed dynamically by placing them in a string variable and referencing the variable name preceded by a colon (:).

Also, the source can be a date variable or column. If an edit mask is not specified, the date is converted to a string according to the following rules:

- For DATETIME columns and SQR DATE variables, the format specified by the SQR_DB_DATE_FORMAT setting. If this has not been set, the first database-dependent format as listed in the Default Database Formats table is used.
- For DATE columns, the format specified by the SQR_DB_DATE_ONLY_FORMAT setting is used. If this has not been set, the format listed in the Default Database Formats table is used.
- For TIME columns, the format specified by the SQR_DB_TIME_ONLY_FORMAT setting is used. If this has not been set, the format as listed in the Time Column Formats table is used.

Parameters

Parameter	Description
src_any_lit _var _col	Specifies the source field to be concatenated with the dst_txt_var field.
dst_txt_var	Contains the result after execution
edit_mask	Specifies an optional edit mask.

Example

```
concat &zip_plus_4 with $zip '-xxxx'      ! Edit zip plus 4.
concat &descrip with $rec :$desc_edit      ! Edit mask in variable.
concat $date1 with $string                 ! Concatenate a date.
```

See Also

The PRINT command for information about the Default Database Formats table, the Time Column Formats table, and edit masks.
 The LET command for string functions.
 The STRING and UNSTRING commands.

CONNECT

Syntax

```
CONNECT {txt_lit|_var|_col}[ON-ERROR=procedure[(arg1
[, argi]...)]]
```

Description

Logs off the database and logs on under a new username and password.

The new username and password can be stored in a string variable, column, or literal.

Warning! The username/password is not encrypted, so beware of security issues.

After each CONNECT, the reserved variable *\$username* is set to the new username.

All database cursors or logons are closed before the CONNECT occurs. You should not issue a CONNECT within a SELECT or an SQL paragraph while a query is actively fetching or manipulating data from the database.

Parameters

Parameter	Description
txt_lit _var _col	Specifies a username and password for the logon.
ON-ERROR	Specifies a procedure to be executed if the logon fails. If no ON-ERROR procedure is specified and the logon fails, SQR halts with an error message.

Note. You can optionally specify arguments to be passed to the ON-ERROR procedure. Arguments can be any variable, column, or literal.

Example

```
connect $new-user on-error=bad-logon($new_user)
connect 'sqr/test'
```

CREATE-ARRAY**Syntax**

```
CREATE-ARRAY NAME=array_name SIZE=nn
{FIELD=name:type[:occurs]
[={init_value_txt_lit|_num_lit}]]...
```

Description

Creates an array of fields to store and process data.

You can define arrays to store intermediate results or data retrieved from the database. For example, a SELECT paragraph can retrieve data, store it in an array, and gather statistics at the same time. When the query finishes, a summary could be printed followed by the data previously stored in the array.

SQR creates arrays before a program starts to execute. The CREATE-ARRAY command can be used in any section of a program.

Commands to process arrays include the following:

```
CREATE-ARRAY
CLEAR-ARRAY
GET
PUT
ARRAY-ADD
ARRAY-SUBTRACT
ARRAY-MULTIPLY
ARRAY-DIVIDE
LET
```

The maximum number of arrays in a program is 128; the maximum number of fields per array is 200.

The following code is a representation of an array *emps* with three fields where the CREATE-ARRAY command defines the array:

```
create-array name=emps size=10
field=name:char='Unknown'
field=rate:number:2=10.50
field=phone:char='None'
```

The *name* is a simple field (one occurrence), *rate* has two occurrences, and *phone* is a simple field. Both array elements and field occurrences are referenced beginning with zero (0). The *rate* is referenced by *rate*(0) or *rate*(1). The *emps* array will contain 10 elements, 0 through 9. All *name* fields are initialized to Unknown, all *phone* fields are initialized to None, and all *rate* fields are initialized to 10.50.

Parameters

Parameter	Description
NAME	Names the array. The name is referenced in other array commands.
SIZE	Defines the number of elements in the array.
FIELD	Defines each field or column in the array. Each field must be defined as type: DECIMAL[(p)]: Decimal numbers with an optional precision (p). FLOAT: Double precision floating point numbers. INTEGER: Whole numbers. NUMBER: Uses the DEFAULT-NUMERIC type. See the DECLARE-VARIABLE command. CHAR (or TEXT): Character string. DATE: Same as date variable. You can specify an initialization value for each field. Each field is set to this value when the array is created and when the CLEAR-ARRAY command is executed. If no initialization value is specified, numeric fields (DECIMAL, FLOAT, INTEGER) are set to zero, character fields are set to null, and date fields are set to null. All occurrences of a multiply occurring field are set to the same value. For dates, the initialization string must be formatted as 'SYYYYMMDD[HH24[MI[SS[NNNNNN]]]]'.
OCCURS	Fields can optionally have a number of occurrences (occurs), that is, they can be repeated any number of times.

Example

```
create-array name=custs size=100
  field=name:char
  field=no:number
  field=state:char
  field=zip:char
  field=contacts:char:5
  field=last-contacted:date
```

See Also

The sample report CUSTOMR4.SQR included with SQR.

The DECLARE-VARIABLE, ARRAY-ADD, ARRAY-DIVIDE, ARRAY-MULTIPLY, ARRAY-SUBTRACT, GET, PUT, LET, and CLEAR-ARRAY commands.

The LOAD-LOOKUP command for an alternative way to store database tables in memory.

CREATE-COLOR-PALETTE

Syntax

```
CREATE-COLOR-PALETTE
NAME = {palette_name_txt_lit}
COLOR_1 = {rgb_value}
COLOR_2 = {rgb_value}
[COLOR_n] = {rgb_value}
```


Description

Create a color palette.

This command enables you to create a palette of colors. There is no limit to the number of palettes that can be defined in a program. No gaps are permitted in the palette.

Parameters

Parameter	Description
NAME	Specifies the name of the color palette.
COLOR_1	Specifies the first color in the palette.
COLOR_2	Specifies the second color in the palette.
COLOR_n	Specifies the n'th color in the palette. You can specify up to 64 colors in the palette.
{rgb}	Designates a color reference. This can be expressed as (r,g,b) where r, g, and b are either a numeric literal (0 to 255), a numeric variable, or a numeric column. It can also be expressed as a (c) where c is a string literal, column, or variable that is the name of a color.

Example

```
begin-report
  create-color-palette
    name = 'funky'
    color_1 = ('blue')
    color_2 = ('red')
    color_3 = ('orange')

    Print-Chart Groovy
    Color-Palette = 'Funky'
end-report
```

See Also

The DECLARE-CHART command.

The PRINT-CHART command.

#DEBUG

Syntax

```
#DEBUG[x...]SQR_Command
```

Description

Causes the current command to be processed during a debugging session.

A -DEBUG[xx] flag in the SQR command line enables conditional compilation of SQR commands. When this flag is used, any command (including other compiler directives) preceded by the word #DEBUG is processed; other commands are ignored.

This is useful for placing DISPLAY, SHOW, PRINT or other commands in your program for testing and for deactivating them when the report goes into production.

The -DEBUG flag can contain a suffix up to 10 letters or digits. These characters are used to match any letters or digits appended to the #DEBUG preprocess command inside the program. #DEBUG commands with one or more matching suffix characters are processed; other commands are ignored. Commands without any suffix always match.

In addition, for each -DEBUGxx letter, a substitution variable is defined. For example, if the flag -DEBUGab is used on the command line, three substitution variables are defined: *debug*, *debuga*, and *debugb*. These variables can be referenced in #IFDEF commands to turn whole sections of code on or off for debugging.

Parameters

Parameter	Description
x	Represents any letter or digit.

Example

The following SQR command line contains the -DEBUG flag with no suffixes:

```
sqr myprog sammy/baker -debug
```

The following SHOW command in the program executes if invoked with the previous command line because the -DEBUG flag was used:

```
#debug show 'The total is ' #grand-tot 999,999,999
```

In the following code example, the command line contains the -DEBUG flag with the suffixes a, b, and c:

```
sqr myprog sammy/baker -debugabc
```

In the following code example, the first three #DEBUG commands are compiled, but the fourth, beginning *#debuga*, is not because its suffix does not match any of the suffixes on the -DEBUG flag:

```
#debuga show 'Now selecting rows...'
#debug show 'Finished query.'
#debugb show 'Inserting new row.'
#debuga show 'Deleting row.'
```

The following code example shows the use of an #IF with a #DEBUG:

```
#debuga #if {platform}='unix'
#debuga show 'Platform is UNIX'
#debuga #endif
```

See Also

The #IF, #IFDEF, and #IFNDEF commands.

DECLARE-CHART

Syntax

```
DECLARE-CHART chart_name
[DATA-LABELS=data_labels_lit]
[COLOR-PALETTE=color_palette_lit]
[ITEM-COLOR=(chart_item_keyword_lit, color_value_lit |(r,g,b))]
```

```

[CHART-SIZE=(chart_width_int_lit,chart_depth_int_lit)]
[TITLE=title_txt_lit]
[SUB-TITLE=subtitle_txt_lit]
[FILL=fill_lit]
[3D-EFFECTS=3d_effects_lit]
[BORDER=border_lit]
[POINT-MARKERS=point_markers_lit]
[TYPE=chart_type_lit]
[LEGEND=legend_lit]
[LEGEND-TITLE=legend_title_txt_lit]
[LEGEND-PLACEMENT=legend_placement_lit]
[LEGEND-PRESENTATION=legend_presentation_lit]
[PIE-SEGMENT-QUANTITY-DISPLAY=
pie_segement_quantity_display_lit]
[PIE-SEGMENT-PERCENT-DISPLAY=
pie_segement_percent_display_lit]
[PIE-SEGMENT-EXPLODE=pie_segement_explode_lit]
[X-AXIS-LABEL=x_axis_label_txt_lit]
[X-AXIS-MIN-VALUE={x_axis_min_value_lit|_num_lit}]
[X-AXIS-MAX-VALUE={x_axis_max_value_lit|_num_lit}]
[X-AXIS-SCALE=x_axis_scale_lit]
[X-AXIS-MAJOR-TICK-MARKS=x_axis_major_tick_marks_lit]
[X-AXIS-MINOR-TICK-MARKS=x_axis_minor_tick_marks_lit]
[X-AXIS-MAJOR-INCREMENT=
{x_axis_major_increment_lit|_num_lit}]
[X-AXIS-MINOR-INCREMENT=
x_axis_minor_increment_num_lit]
[X-AXIS-TICK-MARK-PLACEMENT=
x_axis_tick_mark_placement_lit]
[X-AXIS-GRID=x_axis_grid_lit]
[Y-AXIS-LABEL=y_axis_label_lit]
[Y-AXIS-MIN-VALUE={y_axis_min_value_lit|_num_lit}]
[Y-AXIS-MAX-VALUE={y_axis_max_value_lit|_num_lit}]
[Y-AXIS-SCALE=y_axis_scale_lit]
[Y-AXIS-MAJOR-TICK-MARKS=y_axis_major_tick_marks_lit]
[Y-AXIS-MINOR-TICK-MARKS=y_axis_minor_tick_marks_lit]
[Y-AXIS-MAJOR-INCREMENT=
{y_axis_major_increment_lit|_num_lit}]
[Y-AXIS-MINOR-INCREMENT=
y_axis_minor_increment_num_lit]
[Y-AXIS-TICK-MARK-PLACEMENT=
y_axis_tick_mark_placement_lit]
[Y-AXIS-GRID=y_axis_grid_lit]
END-DECLARE

```

Note. If CHART-SIZE is not defined, it must be defined in PRINT-CHART.

Description

Defines the attributes of a chart that can later be displayed using PRINT-CHART.

The DECLARE-CHART command can define the attributes of a chart to be printed as part of a report.

This command may only appear in the SETUP section.

A chart defined using DECLARE-CHART is printed by referencing its name in the PRINT-CHART command. Some or all of the chart attributes may be overridden at runtime with the PRINT-CHART command. As such, DECLARE-CHART is useful when the basic properties of a chart are common to many PRINT-CHART commands.

Note. All DECLARE-CHART attributes can be overridden as part of the PRINT-CHART command. Columns are not supported within the DECLARE-CHART command or the PRINT-CHART command. Attributes that are specified more than once produce a warning, and the first instance is regarded as the actual value. Attributes can be used in any order, with the exception of *chart-name*, which must follow the DECLARE-CHART keyword.

Also, the FILL specification in the DECLARE-PRINTER command can influence the appearance of the chart. The following table lists the final appearance of the chart with a combination of values for PRINTER.COLOR and CHART.FILL options.

CHART.FILL=	PRINTER.COLOR=Y	PRINTER.COLOR=N
GRAYSCALE	GRAYSCALE	GRAYSCALE
COLOR	COLOR	GRAYSCALE
CROSSHATCH	COLOR-CROSSHATCH	CROSSHATCH
NONE	NONE	NONE

Specifying Chart Data Series Colors

Color palettes are used in the new graphics to set the colors of each data point in a data series. You specify the color palette to be used in a business chart by creating an SQR COLOR-PALETTE using the CREATE-COLOR-PALETTE command. The following code demonstrates how to create the color palette:

```
Create-Color-Palette
  Name = 'Test-Palette'
  Color_1 = (100,133,238)
  Color_2 = (0, 0, 255)
  Color_3 = (0,255,0)
  Color_4 = (0,0,255)
  Color_5 = (0,0,0)
```

Users can specify any number of palettes, with up to 64 colors defined in each palette. If there are more data points in the data sets than defined colors in the palette, the palette resets and continues to set the data point colors from Color_1 to Color_n.

After a color palette has been defined, it can be used within the DECLARE-CHART and PRINT-CHART commands to specify the color palette to be used. The following code example demonstrates the use of a color palette:

```
Print-Chart test_Chart
```

COLOR-PALETTE = 'Test-Palette'

Specifying Chart Item Colors

Users can specify the foreground and background colors of the individual areas within a business chart using ITEM-COLOR = (*rgb-value*) within the DECLARE-CHART and PRINT-CHART commands. The following is a list of chart item keywords that are valid for ITEM-COLOR:

- ChartBackground - Background color of entire chart area
- ChartForeground - Text and Line color of chart area
- HeaderBackground - Area within the text box specified for the Title and Subtitle
- HeaderForeground - Text color of the Title and Subtitle
- FooterBackground - Area within the text box specified for the X Axis label
- FooterForeground - Text color of the X Axis label
- LegendBackground - Area within the box defining the legend
- LegendForeground - Text and outline color of the legend
- ChartAreaBackground - Area that includes the body of the chart
- ChartAreaForeground - Text and line colors of the chart area
- PlotAreaBackground - Area within the X and Y Axis of a chart
- PlotAreaForeground - Text and line colors of the plot area

Parameters

Parameter	Description
chart_name	A unique name to be used for referencing a chart.
CHART-SIZE	The size of the chart frame in standard SQR coordinate units.

The following DECLARE-CHART Command Arguments table describes other arguments for the DECLARE-CHART command.

Note. PeopleSoft does not currently support setting NewGraphics to Yes. This means that you should not use the DATA-LABELS, COLOR-PALETTE, and ITEM-COLOR attributes listed below as they are only valid when NewGraphics=Yes.

Argument	Choices	Description
DATA-LABELS	Yes No	NewGraphics—If YES, SQR prints the numeric value above the individual data points. If NO, no numeric values are displayed.

Argument	Choices	Description
COLOR-PALETTE	palette_name	NewGraphics—Sets the color palette to be used to color the individual data points in each chart (example: Bar, slice, point). A valid SQR color-palette must be defined to use COLOR-PALETTE.
ITEM-COLOR	ChartBackground ChartForeground HeaderBackground HeaderForeground FooterBackground FooterForeground LegendBackground LegendForeground ChartAreaBackground ChartAreaForeground PlotAreaBackground	NewGraphics—Set to color an individual item in a chart. Specify a chart item and a valid (r,g,b) color to set the color of the chart item.
TITLE	NONE text	Specifies a title for the chart. That text is placed at the top of the chart.
SUB-TITLE	NONE text	Specifies a subtitle for the chart. That text is placed below the title regardless of whether TITLE is specified.
FILL	GRAYSCALE COLOR CROSSHATCH NONE	Specifies the type of filling that is applied to the shapes (bars, pie-segments, and so on.) that represent the data loaded in the chart. GRAYSCALE varies the density of black dots. COLOR sends color instructions to the current printer. If the current printer does not support color, then it could appear in a GRAYSCALE fashion. CROSSHATCH uses patterns to fill the shapes representing each data set. With NONE, all graph shapes are filled with white.
3D-EFFECTS	YES NO	3D-EFFECTS gives your chart depth if set to YES. If set to NO, the chart is displayed in the default 2D mode.
BORDER	YES NO	If YES, then a border is drawn around the chart. If NO, then no border is displayed around the chart.
POINT-MARKERS	YES NO	If YES, then point markers are displayed for line charts. If NO, then point markers are not displayed.

Argument	Choices	Description
TYPE	LINE PIE BAR, STACKED-BAR 100%-BAR OVERLAPPED-BAR FLOATING-BAR HISTOGRAM AREA STACKED-AREA 100%-AREA XY-SCATTER-PLOT HIGH-LOW-CLOSE	Specifies the type of chart. <i>See Enterprise PeopleTools 8.45 PeopleBook: SQR for PeopleSoft Developers, “Using Business Charts”.</i>
LEGEND	YES NO	YES, displays a legend. NO does not display a legend.
LEGEND-TITLE	NONE text	Specifies the title for the legend. If NONE, then no title is displayed in the legend box.
LEGEND-PLACEMENT	CENTER-RIGHT CENTER-LEFT UPPER-RIGHT UPPER-LEFT UPPER-CENTER LOWER-RIGHT LOWER-LEFT LOWER-CENTER	Places the legend in the specified location on the chart. The first portion of the placement parameter (CENTER, UPPER, or LOWER) is the vertical position, and the second portion is the horizontal.
LEGEND-PRESENTATION	INSIDE OUTSIDE	If INSIDE, then the legend is presented inside the area defined by the two axes. If OUTSIDE, then the legend is presented within the chart border, but outside of the region represented by the two axes.
PIE-SEGMENT-QUANTITY-DISPLAY	YES NO	If YES, then the quantity is presented for each pie segment.
PIE-SEGMENT-PERCENT-DISPLAY	YES NO	If YES, then percent-of-total figures is presented for each pie segment.
PIE-SEGMENT-EXPLODE	NONE MAX MIN USE-3RD-DATA-COLUMN	Controls what pie segments are exploded (selected) within the pie chart. MAX selects the largest segment. MIN selects the smallest segment. If USE-3RD-DATA-COLUMN, then the third field in the DATA-ARRAY is used to determine which pie segments are exploded. This third field should be a CHAR and values of 'YES' or 'Y' indicate that the segment should be exploded.
X-AXIS-LABEL or Y-AXIS-LABEL	NONE text	Specifies a line of text to be displayed below (or alongside) the tick-mark labels on the axis.

Argument	Choices	Description
X-AXIS-MIN-VALUE	AUTOSCALE number	The minimum value on the axis. If there are data values that are less than X-AXIS-MIN-VALUE, then they are not displayed. AUTOSCALE directs SQR to calculate an appropriate minimum value.
Y-AXIS-MIN-VALUE	AUTOSCALE number	The minimum value on the axis. If there are data values that are less than Y-AXIS-MIN-VALUE, then they are not displayed. AUTOSCALE directs SQR to calculate an appropriate minimum value.
X-AXIS-MAX-VALUE	AUTOSCALE number	The maximum value on the axis. If there are data values that are greater than X-AXIS-MAX-VALUE, then they are not displayed. AUTOSCALE directs SQR to calculate an appropriate maximum value.
Y-AXIS-MAX-VALUE	AUTOSCALE number	The maximum value on the axis. If there are data values that are greater than Y-AXIS-MAX-VALUE, then they are not displayed. AUTOSCALE directs SQR to calculate an appropriate maximum value.
X-AXIS-SCALE or Y-AXIS-SCALE	LOG LINEAR	LOG specifies a logarithmic scale for the axis. Otherwise, the scale is LINEAR.
X-AXIS-MAJOR-TICK- MARKS	YES NO	YES specifies the display tick-marks along the axis between X-AXIS-MIN-VALUE and X-AXIS-MAX-VALUE, according to the X-AXIS-SCALE setting spaced by X-AXIS-MAJOR-INCREMENT.
Y-AXIS-MAJOR-TICK- MARKS	YES NO	YES displays the tick-marks along the axis between Y-AXIS-MIN-VALUE and Y-AXIS-MAX-VALUE, according to the Y-AXIS-SCALE setting spaced by Y-AXIS-MAJOR-INCREMENT.
X-AXIS-MINOR-TICK- MARKS	YES NO	YES displays the tick-marks along the axis between X-AXIS-MIN-VALUE and X-AXIS-MAX-VALUE, according to the X-AXIS-SCALE setting spaced by X-AXIS-MINOR-INCREMENT.

Argument	Choices	Description
Y-AXIS-MINOR-TICK-MARKS	YES NO	YES displays the tick-marks along the axis between Y-AXIS-MIN-VALUE and Y-AXIS-MAX-VALUE, according to the Y-AXIS-SCALE setting spaced by Y-AXIS-MINOR-INCREMENT.
X-AXIS-MAJOR-INCREMENT or Y-AXIS-MAJOR-INCREMENT	AUTOSCALE number	Specifies for SQR the increment used for spacing the major tick-marks on the axis. AUTOSCALE directs SQR to determine an appropriate increment.
X-AXIS-MINOR-INCREMENT or Y-AXIS-MINOR-INCREMENT	number	Specifies for SQR the increment used for spacing the minor tick-marks on the axis. These must be set for the X-AXIS-MINOR-TICK-MARKS and the Y-AXIS-MINOR-TICK-MARKS to be displayed.
X-AXIS-TICK-MARK-PLACEMENT or Y-AXIS-TICK-MARK-PLACEMENT	INSIDE OUTSIDE BOTH	INSIDE (or OUTSIDE) directs SQR to place the tick-marks on the inside (or outside) of the axis only. BOTH directs SQR to draw the tick-marks such that they appear on both sides of the axis.
X-AXIS-GRID or Y-AXIS-GRID	YES NO	If YES, then a dashed grid line is drawn for each major tick-mark on the axis. If NO, the no grid line is drawn on this axis.

Example

This code example declares a basic sales chart using DECLARE-CHART. Then, for each region, the SUB-TITLE, DATA-ARRAY, and other elements are overridden to provide the chart with the specific features desired.

```
begin-setup
```

```
declare-chart base_sales_chart
chart-size      = (30, 20 )
title           = 'Quarterly Sales'
sub-title       = none
fill            = color
3d-effects      = yes
type            = stacked-bar
legend-title    = 'Product'
x-axis-grid     = yes
end-declare
```

```
end-setup
```

```
begin-program
```

```
print-chart base_sales_chart
sub-title           = 'Region I'
data-array          = reg1_sales
data-array-row-count = #rows_reg1
data-array-column-count = 2
y-axis-max-value    = #max_of_all_regions
y-axis-min-value    = #min_of_all_regions
legend              = no
```

```
print-chart base_sales_chart
sub-title           = 'Region II'
data-array          = reg2_sales
data-array-row-count = #rows_reg2
data-array-column-count = 2
y-axis-max-value    = #max_of_all_regions
y-axis-min-value    = #min_of_all_regions
legend              = no
```

```
end-program
```

```
begin-procedure chart_region_sales ($sub, $ary,
                                     #rows, #cols,
                                     #max_of_all_regions,
                                     #min_of_all_regions)
```

```
print-chart base_sales_chart (20, 15 )
sub-title           = $sub
data-array          = all sales
data-array-row-count = #rows
data-array-column-count = #cols
data-array-column-labels = ('Q1', 'Q2', 'Q3', 'Q4' )
y-axis-max-value    = #max_of_all_regions
y-axis-min-value    = #min_of_all_regions
chart-size          = (50, 30)
```

```
end-procedure
```

See Also

The PRINT-CHART command.

DECLARE-COLOR-MAP

Syntax

In the SETUP section:

```
DECLARE-COLOR-MAP
    color_name = ({rgb})
color_name = ({rgb})
.
.
.
END-DECLARE
```

Description

Defines colors in an SQR report.

The DECLARE-COLOR-MAP command in the BEGIN-SETUP section defines or redefines colors in an SQR report. You can define an endless number of entries.

Parameters

Parameter	Description
color_name	A <i>color_name</i> is composed of the alphanumeric characters (A-Z, 0-9), the underscore (_) character, and the hyphen (-) character. It must start with an alphabetical (A-Z) character. It is case insensitive. The name none is reserved and cannot be assigned a value. A name in the format (RGBredgreenblue) cannot be assigned a value. The name default is reserved and cannot be assigned a value. Default is used during execution when a referenced color is not defined in the runtime environment.
{rgb}	<i>red_lit _var _col, green_lit _var _col, blue_lit _var _col</i> where each component is a value in the range of 000 to 255. In the BEGIN-SETUP section, only literal values are allowed. The default colors implicitly installed with SQR include: black=(0,0,0) white=(255,255,255) gray=(128,128,128) silver=(192,192,192) red=(255,0,0) green=(0,255,0) blue=(0,0,255) yellow=(255,255,0) purple=(128,0,128) olive=(128,128,0) navy=(0,0,128) aqua=(0,255,255) lime=(0,128,0) maroon=(128,0,0) teal=(0,128,128) fuchsia=(255,0,255)

Example

```
begin-setup
  declare-color-map
    light_blue = (193, 222, 229)
  end-declare
end-setup
```

See Also

The ALTER-COLOR-MAP, SET-COLOR, and GET-COLOR commands in this section.

DECLARE-CONNECTION

Syntax

In the SETUP section:

```
DECLARE-CONNECTION connection_name_txt_lit
DSN={uq_txt_lit}
[USER={uq_txt_lit}]
[PASSWORD={uq_txt_lit}]
[PARAMETERS=keyword_str=attr_str [, keyword_str=attr_str ; ...]]
END-DECLARE
```

In the body of the report:

```
DECLARE-CONNECTION connection_name
DSN={uq_txt_lit | var}
[USER={uq_txt_lit | var}]
[PASSWORD={uq_txt_lit | var}]
[PARAMETERS=keyword_str=attr_str [, keyword_str=attr_str ; ...]]
END-DECLARE
```

Description

Defines the datasource logon parameters prior to logon. Can be used to override the default connection logon parameters.

Parameters

Parameter	Description
<i>connection_name</i>	A user-defined name for describing a datasource connection.
USER, PASSWORD	Traditional logon semantics.
PARAMETERS = <i>keyword_str=attr_str</i> ;	Defines a list of keyword-attribute pairs required by a datasource driver for logon. There is no syntax restriction on these entries apart from the delimiting semicolons (;) and equal signs (=). The keywords must match the logon property names listed for a datasource.
NO-DUPLICATE= TRUE FALSE (default is FALSE)	This optional keyword prevents SQR from automatically creating additional logins to datasources that are busy handling a previous query. Creating a new login in such cases is the default behavior for SQR, which allows a single CONNECTION declaration to be used in a subquery. This behavior, while allowing dynamic logins as-needed, causes problems when doing both DDL (BEGIN-SQL) and DML (BEGIN-SELECT) against temporary tables in certain vendors datasources. In such cases, you must fetch from the temporary table using the same login in which it was created. Here, you should code the CONNECTION as NO-DUPLICATE=TRUE, and then use that connection in both the table creation logic of BEGIN-SQL and the row fetching logic of BEGIN-SELECT.

Example

```

declare-connection SAPR3-1
  dsn=SAPR3
  username=guest
  password=guest
end-declare

```

DECLARE-IMAGE

Syntax

```

DECLARE-IMAGE image_name
[TYPE=image_type_lit]
[IMAGE-SIZE=(width_num_lit,height_num_lit)]
[SOURCE=file_name_lit]
END-DECLARE

```

Note. If TYPE, IMAGE-SIZE, and SOURCE are not defined in DECLARE-IMAGE, they must be defined in PRINT-IMAGE.

Description

Declares the type, size, and source of an image to be printed.

The DECLARE-IMAGE command defines and names an image. This image can then be placed in a report at the position specified in the PRINT-IMAGE command.

Note. If the image file is unrecognizable, or has incomplete header information, then a box (either shaded, for HP printers, or having a diagonal line through it in the case of postscript) appears where the image is expected.

Parameters

Parameter	Description
image_name	Specifies a unique name for referencing the image declaration.
TYPE	Specifies the image type. Types can be EPS-FILE, HPGL-FILE, GIF-FILE, JPEG-FILE, or BMP-FILE (for Windows).
IMAGE-SIZE	Specifies the width and height of the image in SQR coordinates.
SOURCE	Specifies the name of a file containing the image. The file must be in the SQRDIR directory or you must specify the full path. Note. If the file is not in the SQRDIR directory, the full path or no path should be given. A relative path will not do, because you must know where you execute the file from.

Example

```

declare-image officer-signature
  type          = eps-file
  source        = 'off_sherman.eps'
  image-size    = (40, 5)
end-declare

```

See Also

The PRINT-IMAGE command.

DECLARE-LAYOUT

Syntax

```

DECLARE-LAYOUT layout_name
[PAPER-SIZE={paper_width_num_lit[uom],
paper_depth_num_lit[uom]}|{paper_name}]]
[FORMFEED=form_feed_lit]
[ORIENTATION=orientation_lit]
[LEFT-MARGIN=left_margin_num_lit[uom]]
[TOP-MARGIN=top_margin_num_lit[uom]]
[RIGHT-MARGIN=right_margin_num_lit[uom]]
|LINE-WIDTH=line_width_num_lit[uom]
|MAX-COLUMNS=columns_int_lit]
[BOTTOM-MARGIN=bottom_margin_num_lit[uom]]
|PAGE-DEPTH=page_depth_num_lit[uom]
|MAX-LINES=lines_int_lit]
[CHAR-WIDTH=char_width_num_lit[uom]]
[LINE-HEIGHT=line_height_num_lit[uom]]
END-DECLARE

```

Description

Defines the attributes for the layout of an output file.

The DECLARE-LAYOUT command describes the characteristics of a layout to be used for an output file. A layout can be shared by more than one report. If no DECLARE-LAYOUT is defined or if a DECLARE-REPORT does not reference a defined layout, a layout named DEFAULT is created with the default attribute values shown in the DECLARE-LAYOUT Command Arguments table. For an example of how DECLARE-LAYOUT relates to DECLARE-REPORT, see the DECLARE-REPORT examples in this document.

You can define as many layouts as are necessary for the requirements of the application. You can override the DEFAULT layout attributes by defining a layout called DEFAULT in your program. Each layout name must be unique.

SQR maps its line and column positions on the page by using a grid determined by the LINE-HEIGHT and CHAR-WIDTH arguments. That is, SQR calculates the number of columns per row by dividing the LINE-WIDTH by the CHAR-WIDTH and calculates the number of lines by dividing the PAGE-DEPTH by the LINE-HEIGHT. Each printed segment of text is placed on the page using this grid. Because the characters in proportional fonts vary in width, it is possible that a word or string is wider than the horizontal space you have allotted, especially in words containing uppercase letters or boldfaced characters. To account for this behavior, you can either move the column position in the PRINT or POSITION statements or indicate a larger CHAR-WIDTH in the DECLARE-LAYOUT command.

The selects the proper fonts. In addition, the parameter interacts with PAPER-SIZE as follows:

- When you do not specify ORIENTATION=LANDSCAPE or the PAPER-SIZE dimensions, then SQR creates a page with the dimensions set to 11 inch by 8.5 inch. This results in a page of 100 columns by 45 lines with 0.5 inch margins.
- When you specify PAPER-SIZE=(*paper_name*) the page orientation is set according to the *paper_name* specified. If you also specify ORIENTATION and the value differs from the PAPER-SIZE value, then the ORIENTATION value overrides the PAPER-SIZE value.
- When you specify PAPER-SIZE=(*page_width, page_depth*) is specified then SQR *does not* swap the page width and page depth if ORIENTATION=LANDSCAPE.

Parameters

Parameter	Description
layout_name	A unique layout name to be used for referencing the layout and its attributes.
uom (unit of measure)	An optional suffix which denotes the unit of measure to apply to the preceding value.
paper_name	An option of PAPER-SIZE. This name is associated with predefined dimensions. The following table lists valid unit of measure suffixes.

Suffix	Meaning	Definition
dp	decipoint	0.001388 inch
pt	point	0.01388 inch
mm	millimeter	0.03937 inch

Suffix	Meaning	Definition
cm	centimeter	0.3937 inch
in	inch	1.0000 inch

The following table lists valid paper names for the *paper_name* parameter.

Name	Width	Depth	Orientation
Letter	8.5 in	11 in	Portrait
Legal	8.5 in	14 in	Portrait
A4	8.27 in	11.69 in	Portrait
Executive	7.25 in	10.5 in	Portrait
B5	7.17 in	10.12 in	Portrait
Com-10	4.125 in	9.5 in	Landscape
Monarch	3.875 in	7.5 in	Landscape
DL	4.33 in	8.66 in	Landscape
C5	6.378 in	9.016 in	Landscape

The following table describes the arguments of the DECLARE-LAYOUT command:

Argument	Choice or Default UOM	Default Value	Description
PAPER-SIZE	inches	8.5 in, 11 in	Physical size of the page. The first parameter is the width of the page. The second parameter is the depth or length. It may also be a predefined name. (See the Valid Paper Names table.) Note that when ORIENTATION=LANDSCAPE the default values are 11 in, 8.5 in.
FORMFEED	YES, NO	YES	Specifies whether formfeeds are to be written at the end of each page.
ORIENTATION	PORTRAIT, LANDSCAPE	PORTRAIT	Portrait pages are printed vertically. Landscape pages are printed horizontally. Printing in landscape for the printer type HPLASERJET requires landscape fonts.
LEFT-MARGIN	inches	0.5 in	Amount of blank space to leave at the left side of the page.
TOP-MARGIN	inches	0.5 in	Amount of blank space to leave at the top of the page.
RIGHT-MARGIN	inches	0.5 in	Amount of blank space to leave at the right side of the page. If you specify LINE-WIDTH or MAX-COLUMNS, you cannot use this parameter.
LINE-WIDTH	inches	7.5 in	Length of the line. If you specify RIGHT-MARGIN or MAX-COLUMNS, you cannot use this parameter.

Argument	Choice or Default UOM	Default Value	Description
MAX-COLUMNS		75	Maximum number of columns in a line. If you specify RIGHT-MARGIN or LINE-WIDTH, you cannot use this parameter.
BOTTOM-MARGIN	inches	0.5 in	Amount of blank space to leave at the bottom of the page. If you specify PAGE-DEPTH or MAX-LINES, you cannot use this parameter.
PAGE-DEPTH	inches	10 in	Depth of the page. If you specify BOTTOM-MARGIN or MAX-LINES, you cannot use this parameter.
MAX-LINES		60	Maximum number of lines printed on the page. If you specify PAGE-DEPTH or BOTTOM-MARGIN, you cannot use this parameter.

Argument	Choice or Default UOM	Default Value	Description
LINE-HEIGHT	points	12 pt	Size of each SQR line on the page. There are 72 points per inch. If LINE-HEIGHT is not specified, it follows the value for POINT-SIZE, if specified. The default value of 12 points yields 6 lines per inch. For the printer type LINEPRINTER, this value is used only to calculate the TOP-MARGIN and BOTTOM-MARGIN (for example, not in computing the position on the page).
CHAR-WIDTH	points	7.2 pt	Size of each SQR horizontal character column on the page (for example, the distance between the locations (1, 12) and (1, 13)). For the printer type LINEPRINTER, this value is used only to calculate the TOP-MARGIN and BOTTOM-MARGIN (not in computing the position on the page).

Example

The following example illustrates the ability to specify the parameters using a different measurement system (that is, metric).

```

!
declare-layout my-layout      ! Results in:

paper-size=(a4)              !   paper-size=(210mm, 297mm)

left-margin=12.7 mm          !   top-margin=12.7mm

right-margin=25.4 mm         !   left-margin=12.7mm
end-declare                  !   right-margin=25.4mm

                             !   bottom-margin=12.7mm

```

```

! orientation=portrait
! columns=67
! lines=64

```

The following code example changes the page dimensions and also changes the left and right margins to be 1 inch.

```

!
declare-layout large-paper    ! Results in:

paper-size=(14, 11)          ! paper-size=(14in, 11in)

left-margin=1                ! top-margin=0.5in

right-margin=1               ! left-margin=1.0in
end-declare                  ! right-margin=1.0in

! bottom-margin=0.5in

! orientation=portrait

! columns=120

! lines=60

```

The following example retains the default page dimensions and changes the left and right margins to be 1 inch.

```

declare-layout default       ! Results in:

left-margin=1                ! paper-size=(8.5in, 11in)

right-margin=1               ! top-margin=0.5in
end-declare                  ! left-margin=1.0in

! right-margin=1.0in

! bottom-margin=0.5in

! orientation=portrait

! columns=65

! lines=60

```

The following example changes the orientation to landscape. The default page dimensions of (8.5in and 11in) are swapped. The columns and rows are recalculated. All other values remain the same.

```

declare-layout default       ! Results in:

orientation=landscape        ! paper-size=(11in, 8.5in)

```

```

end-declare          !   top-margin=0.5in

                     !   left-margin=0.5in

                     !   right-margin=0.5in

                     !   bottom-margin=0.5in

                     !   orientation=landscape

                     !   columns=100

                     !   lines=45

```

The following example changes the orientation to landscape. The default page dimensions of (8.5in and 11in) are swapped. In addition the top margin is set to 1 inch.

```

declare-layout my_landscape    ! Results in:

orientation=landscape          !   paper-size=(11in, 8.5in)

top-margin=1                   !   top-margin=1.0in
end-declare                    !   left-margin=0.5in

                               !   right-margin=0.5in

                               !   bottom-margin=0.5in

                               !   orientation=landscape

                               !   columns=100

                               !   lines=43

```

The following example illustrates how to specify the page dimensions using one of the predefined names. Note that the orientation has also changed because this example is an envelope.

```

declare-layout envelope        ! Results in:

paper-size=(com-10)            !   paper-size=(4.125in, 9.5in)
end-declare                    !   top-margin=0.5in

                               !   left-margin=0.5in

                               !   right-margin=0.5in

                               !   bottom-margin=0.5in

                               !   orientation=landscape

```

```
!    columns=85

!    lines=18
```

See Also

The DECLARE-REPORT command.

DECLARE-PRINTER

Syntax

```
DECLARE-PRINTER printer_name
[FOR-REPORTS=(report_name1[,report_namei]...)]
[TYPE=printer_type_lit]
[INIT-STRING=initialization_string_txt_lit]
[RESET-STRING=reset_string_txt_lit]
[COLOR=color_lit]
[POINT-SIZE=point_size_num_lit]
[FONT-TYPE=font_type_int_lit]
[SYMBOL-SET=symbol_set_id_lit]
[STARTUP-FILE=file_name_txt_lit]
[PITCH=pitch_num_lit]
[FONT=font_int_lit]
[BEFORE-BOLD=before_bold_string_txt_lit]
[AFTER-BOLD=after_bold_string_txt_lit]
END-DECLARE
```

Description

Overrides the printer defaults for the specified printer type.

Each printer has a set of defaults as listed in the DECLARE-PRINTER Command Arguments table. The DECLARE-PRINTER command overrides these defaults.

Use the DECLARE-PRINTER command in the SETUP section to define the characteristics of the printer or printers to be used. If you need to change some of the arguments depending on the runtime environment, you can use the ALTER-PRINTER command in any part of the program except the PROGRAM and SETUP sections.

A program can contain no more than one DECLARE-PRINTER command for each printer type for each report. If you do not provide a printer declaration, the default specifications are used. The default printer attributes can be overridden by providing a DECLARE-PRINTER specification for each printer. Their names are: DEFAULT-LP for line printer, DEFAULT-HP for HP LaserJet, DEFAULT-HT for HTML, and DEFAULT-PS for PostScript.

The following table describes each of the arguments, the possible choices, and the default values.

Argument	Choice or Measure	Default	Description
FOR-REPORTS		ALL	The name of the reports that use this printer definition. The default is ALL reports. This argument is required only for a program with multiple reports. If you are writing a program that produces only a single report, you can ignore this argument.
TYPE	LINEPRINTER, POSTSCRIPT, HPLASERJET, HTML, LP, PS, HP, HT	LP	SQR creates output specific to each printer. LINEPRINTER (LP) files can be viewed by a text editor. POSTSCRIPT (PS) files require you to know PostScript to understand what will be shown on the printer. HPLASERJET (HP) files are binary files and cannot be edited or viewed. HTML (HT) files can be viewed by a browser.
INIT-STRING		(none)	Sends control or other characters to the printer at the beginning of the report. This parameter is designed primarily for the LINEPRINTER and has limited use with other printer types. Specify nondisplay characters by placing their decimal values inside angle brackets. For example, <27> is the ESC or escape character.

Argument	Choice or Measure	Default	Description
RESET-STRING		(none)	Sends control or other characters to the printer at the end of the report. This parameter is designed primarily for the LINEPRINTER and has limited use with other printer types. Specify nondisplay characters by placing their decimal values inside angle brackets. For example, <27> is the ESC or escape character.
COLOR	Yes, No	No	Specifies whether this printer can print in color.
POINT-SIZE	points	12	This argument does not apply to LINEPRINTER printers. This is the beginning size of the selected font.
FONT-TYPE	PROPORTIONAL, FIXED	Depends on the font	This argument applies only to HPLASERJET printers and needs to be specified only for font types not defined in the Fonts Available for HP LaserJet Printers in SQR table.
SYMBOL-SET	HP defined sets	0U	This argument applies only to HPLASERJET printers. The default value of 0U is for the USASCII symbol set. For a complete list of the symbol sets, see the <i>HP LaserJet Technical Reference Manual</i> .

Argument	Choice or Measure	Default	Description
STARTUP-FILE	filename	POSTSCRI.STR	This argument applies only to POSTSCRIPT printers. This argument is used to specify an alternate startup file. Unless otherwise specified, the default startup file is located in the directory pointed to by the environment variable SQRDIR.
PITCH	characters/inch	10	This argument is for HPLASERJET printers only. If you specify a fixed pitch font, you should also indicate the pitch.

Argument	Choice or Measure	Default	Description
FONT	font_number	3	This is the font number of the typeface to use. For HPLASERJET printers, this is the typeface value as defined by Hewlett-Packard. For a complete list of the typeface numbers, see the <i>HP LaserJet Technical Reference Manual</i>. For POSTSCRIPT printers, SQR supplies a list of fonts and arbitrary font number assignments in the file POSTSCRI.STR. The font numbers are the same as those for HP LaserJet printers, wherever possible, so that you can use the same font number for reports to be printed on both types of printers. You can modify the font list in POSTSCRI.STR to add or delete fonts. Read the POSTSCRI.STR file for instructions. The Fonts Available for HP LaserJet Printers in SQR table lists the fonts available in SQR internally. The Fonts Available for PostScript Printers table lists the fonts available in the SQR POSTSCRI.STR file.

Argument	Choice or Measure	Default	Description
BEFORE-BOLD	any string	(none)	The BEFORE-BOLD and AFTER-BOLD arguments are for LINEPRINTER printers only. They specify the character string to turn boldfacing on and off. If the string contains blank characters, enclose it in single quote marks ('...'). To specify nonprintable characters, such as ESC, enclose the decimal value inside angle brackets as follows: BEFORE - BOLD=<27>[r ! Turn on bold AFTER - BOLD=<27>[u ! Turn it off These arguments work in conjunction with the BOLD argument of the PRINT command.
AFTER-BOLD	any string	(none)	See BEFORE-BOLD.

The following table lists the fonts available in SQR for use with the FONT argument for HPLASERJET printer types.

Value	Typeface	Style
0	Line printer	Fixed
1	Pica	Fixed
2	Elite	Fixed
3	Courier	Fixed
4	Helvetica	Proportional
5	Times Roman	Proportional
6	Letter Gothic	Fixed
8	Prestige	Fixed

Value	Typeface	Style
11	Presentations	Fixed
17	Optima	Proportional
18	Garamondi	Proportional
19	Cooper Black	Proportional
20	Coronet Bold	Proportional
21	Broadway	Proportional
22	Bauer Bodini Black Condensed	Proportional
23	Century Schoolbook	Proportional
24	University Roman	Proportional

The font you choose—in orientation, typeface, and point size—must be an internal font, available in a font cartridge, or downloaded to the printer.

For fonts not listed in the Fonts Available for HP LaserJet Printers in SQR table, you must indicate the font style using the FONT-TYPE argument, or the correct typeface cannot be selected by the printer.

The following table lists the fonts available in SQR for use with the FONT argument for PostScript printer types. Those for which boldface types are available are indicated by a *Y* in the *Bold* column.

Value	Typeface	Bold
3	Courier	Y
4	Helvetica	Y
5	Times Roman	Y
6	Avant Garde Book	N/A
8	Palatino Roman	Y
11	Symbol	N/A

Value	Typeface	Bold
12	Zapf Dingbats	N/A
17	Zapf Chancery Medium Italic	N/A
18	Bookman Light	N/A
23	New Century Schoolbook Roman	Y
30	Courier Oblique	Y
31	Helvetica Oblique	Y
32	Times Italic	Y
33	Avant Garde Demi	N/A
34	Avant Garde Book Oblique	N/A
35	Avant Garde Demi Oblique	N/A
36	Palatino Oblique	Y
37	New Century Schoolbook Italic	Y
38	Helvetica Narrow	Y
39	Helvetica Narrow Oblique	Y
40	Bookman Demi	N/A
41	Bookman Light Italic	N/A
42	Bookman Demi Italic	N/A

Other type faces can be added to the POSTSCRI.STR file.

The following table lists the fonts available in SQR for Windows when printing on Windows printer drivers (using the -PRINTER:WP command-line flag). When you use the -PRINTER:WP flag, your report is sent directly to the default Windows printer. To specify a nondefault Windows printer, enter -PRINTER:WP:{Printer Name}. The {Printer Name} is the name assigned to your printer. For example, to send output to a Windows printer named *NewPrinter*, you would use -PRINTER:WP:NewPrinter. If your printer name has spaces, enclose the entire argument in quotes.

Fonts are specified in the FONT qualifier of the ALTER-PRINTER command by their number.

Value	Windows Font/Name	Style
3	Courier New	Fixed
300	Courier New	Bold
4	Arial	Proportional
400	Arial	Bold
5	Times New Roman	Proportional
500	Times New Roman	Bold
6	AvantGarde	Proportional
8	Palatino	Proportional
800	Palatino	Bold
11	Symbol	Proportional

Note. Fonts 6, 8, and 800 are not supplied with Windows. You can get these fonts by purchasing the ADOBE Type Manager (ATM). The advantage of using ATM fonts is the compatibility for PostScript printer fonts. The Symbol font uses the SYMBOL_CHARSET instead of the usual ANSI_CHARSET character set. You can add more fonts by editing the appropriate Fonts section in the sqr.ini file.

See [Chapter 7, “Using the PSSQR.INI File and the PSSQR Command Line,” page 277](#).

Parameters

Parameter	Description
printer_name	A unique name to be used for referencing a printer definition and its attributes.

Note. The DECLARE-PRINTER Command Arguments table describes the other arguments of the DECLARE-PRINTER command. The table lists the options, default values, and description of each of the arguments.

Example

```

declare-printer HP-definition      ! Default HP definition

type=HP                          ! for all reports

font=4                           ! Helvetica

symbol-set=12U                   ! PC-850 Multilingual
end-declare
declare-printer PS-Sales          ! PS definition

for-reports=(sales)              ! for the Sales report

type=PS

font=5                           ! Times-Roman
end-declare

```

See Also

The ALTER-PRINTER and DECLARE-REPORT commands.

DECLARE-PROCEDURE

Syntax

```

DECLARE-PROCEDURE
[FOR-REPORTS=(report_name1[,report_name1]...)]
[BEFORE-REPORT=procedure_name[(arg1[,argi]...)]]
[AFTER-REPORT=procedure_name[(arg1[,argi]...)]]
[BEFORE-PAGE=procedure_name[(arg1[,argi]...)]]
[AFTER-PAGE=procedure_name[(arg1[,argi]...)]]
END-DECLARE

```

Description

Declares procedures that are triggered when a specified event occurs.

The DECLARE-PROCEDURE command can be used to define SQR procedures that are to be invoked before or after a report is printed or before the beginning or end of each page.

Issue the DECLARE-PROCEDURE in the SETUP section. For multiple reports, you can use the command as often as required to declare procedures required by all the reports. If you issue multiple DECLARE-PROCEDURE commands, the last one takes precedence. In this way, you can use one command to declare common procedures for ALL reports and others to declare unique procedures for individual reports. The referenced procedures can accept arguments.

If no FOR-REPORTS is specified, ALL is assumed. Initially, the default for each of the four procedure types is NONE. If a procedure is defined in one DECLARE-PROCEDURE for a report, that procedure is used unless NONE is specified.

Use the USE-PROCEDURE command to change the procedures to be used at runtime. To turn a procedure off, specify NONE in the USE-PROCEDURE statement.

Parameters

Parameter	Description
FOR-REPORTS	Specifies one or more reports that use the given procedures. This argument is required only for a program with multiple reports. If you are writing a program that produces only a single report, you can ignore this argument.
BEFORE-REPORT	Specifies a procedure to be executed at the time of the execution of the first command which causes output to be generated (PRINT). It can be used, for example, to create a report heading.
AFTER-REPORT	Specifies a procedure to be executed just before the report file is closed at the end of the report. It can be used to print totals or other closing summary information. If no report was generated, the procedure does not execute.
BEFORE-PAGE	Specifies a procedure to be executed at the beginning of every page, just before the first output command for the page. It can be used, for example, to set up page totals.
AFTER-PAGE	Specifies a procedure to be executed just before each page is written to the file. It can be used, for example, to display page totals. You can optionally specify arguments to be passed to any of the procedures. Arguments can be any variable, column, or literal.

Example

```

declare-procedure           ! These procedures will

before-report=report_heading ! be used by all reports

after-report=report_footing
end-declare
declare-procedure           ! These procedures will

for-reports=(customer)     ! be used by the customer

before-page=page_setup      ! report

after-page=page_totals
end-declare

```

See Also

The USE-PROCEDURE command.

DECLARE-REPORT

Syntax

```

DECLARE-REPORT report_name
[TOC=toc_name]
[LAYOUT=layout_name]
[PRINTER-TYPE=printer_type]
END-DECLARE

```


Description

Defines reports and their attributes.

Issue the DECLARE-REPORT in the SETUP section.

You can use the DECLARE-REPORT command to declare one or more reports to be produced in the application.

You must use this command when developing applications to produce more than one report.

Multiple reports can share the same layout and the same printer declarations or each report can use its own layout or printer definitions if the report has unique characteristics.

When you are printing multiple reports, unless report names are specified using the -F command-line flag, the first report declared is generated with the name of program.lis, where *program* is the application name.

Additional reports are generated with names conforming to the rules dictated by the `sqr.ini OUTPUT-FILE-MODE` setting.

When the -KEEP or -NOLIS flags are used, the first intermediate print file (SPF file) is generated with a name of program.spf and additional reports are generated with names conforming to the rules dictated by the `sqr.ini OUTPUT-FILE-MODE` setting.

Parameters

Parameter	Description
report_name	Specifies the name of the report.
TOC	Specifies the name of the Table of Contents for this report.
LAYOUT	Specifies the name of the layout for this report. If none is specified, the default layout is used.
PRINTER-TYPE	Specifies the type of printer to be used for this report. If none is specified, the default is the LINEPRINTER for this report. If no DECLARE-PRINTER is specified, DEFAULT-LP is used. Valid values for PRINTER-TYPE are HT, HP, PS, LP, HTML, HPLASERJET, POSTSCRIPT, and LINEPRINTER.

Example

```
declare-layout customer_layout
  left-margin
  right-margin
end-declare

declare-layout summary_layout
  orientation=landscape
end-declare

declare-report customer_detail

toc=detailed

layout=customer_layout
```

```

printer-type=postscript
end-declare
declare-report customer_summary

layout=summary_layout

printer-type=postscript
end-declare
.
.
.
use-report customer_detail

...print customer detail...
use-report customer_summary

...print customer summary...

```

See Also

The USE-REPORT, DECLARE-LAYOUT, DECLARE-PRINTER, and DECLARE-TOC commands.

DECLARE-TOC**Syntax**

```

DECLARE-TOC toc_name
[FOR-REPORTS=(report_name1 [, report_namei] ...)]
[DOT-LEADER=YES|NO]
[INDENTATION=position_count_num_lit]
[BEFORE-TOC=procedure_name [(arg1 [, argi] ...)]]
[AFTER-TOC=procedure_name [(arg1 [, argi] ...)]]
[BEFORE-PAGE=procedure_name [(arg1 [, argi] ...)]]
[AFTER-PAGE=procedure_name [(arg1 [, argi] ...)]]
[ENTRY=procedure_name [(argi [, argi] ...)]]
END-DECLARE

```

Description

Defines the table of contents and its attributes.

Use DECLARE-TOC in the SETUP section.

You can use DECLARE-TOC command to declare one or more table of contents for the application.

A table of contents can be shared between reports.

Parameters

Parameter	Description
toc_name	Specifies the name of the table of contents.
FOR-REPORTS	Specifies one or more reports that uses this table of contents.
DOT-LEADER	Specifies whether a dot leader precedes the page number. The default setting is NO.
INDENTATION	Specifies the number of spaces by which each level is indented. The default setting is 4.
BEFORE-TOC	Specifies a procedure to be executed before generating the table of contents. If no table of contents is generated, the procedure does not execute.
AFTER-TOC	Specifies a procedure to be executed after generating the table of contents. If no table of contents is generated, the procedure does not execute.
BEFORE-PAGE	Specifies a procedure to be executed at the start of every page.
AFTER-PAGE	Specifies a procedure to be executed at the end of each page.
ENTRY	Specifies a procedure that is executed to process each table of contents entry (instead of SQR doing it for you). When this procedure is invoked, the following SQR-reserved variables are populated with data about the TOC entry: #SQR-TOC-LEVEL: Contains the level #SQR-TOC-TEXT: Contains the text #SQR-TOC-PAGE: Contains the page number. These are global variables. If the procedure is local, you must precede it with an underscore (for example, #_sqr-toc-page). These three SQR-reserved variables are only valid within the scope of the ENTRY procedure. They can be referenced outside the scope, but their contents are undefined.

Example

```

begin-setup
  declare-toc common
    for-reports=(all)
    dot-leader=yes
    indentation=2
end-declare
end-setup
.
.
.
toc-entry level=1 text=$Chapter
toc-entry level=2 text=$Heading
.
.

```

See Also

The BEGIN-FOOTING, BEGIN-HEADING, DECLARE-REPORT, and TOC-ENTRY commands.

DECLARE-VARIABLE

Syntax

```
DECLARE-VARIABLE
[DEFAULT-NUMERIC={DECIMAL[(prec_lit)]|FLOAT|INTEGER}]
[DECIMAL[(prec_lit)]num_var[(prec_lit)][num_var
[(prec_lit)]]...]
[FLOAT num_var[num_var]...]
[DATE date_var[date_var]...]
[INTEGER num_var[num_var]...]
[TEXT string_var[string_var]...]
END-DECLARE
```

Description

Enables the user to explicitly declare a variable type.

You can set the default numeric type externally, using the -DNT command-line flag or the DEFAULT-NUMERIC setting in the Default-Settings section of the sqr.ini file. However, the setting in the DECLARE-VARIABLE command takes precedence over all other settings. If the command has not been used, then the -DNT command-line flag takes precedence over the setting in the sqr.ini file.

Besides FLOAT, INTEGER, or DECIMAL, the DEFAULT-NUMERIC setting in the sqr.ini file and -DNT command-line flag can be set to V30. With V30, the program acts in the same manner as in pre-version 4.0 releases; that is, all variables are FLOAT. Incidentally, V30 is not a valid setting for the DEFAULT-NUMERIC setting in the DECLARE-VARIABLE command.

The DECLARE-VARIABLE command enables the user to determine the type of variables to use. This command can only appear in the SETUP section or as the first statement of a local procedure. The placement of the command affects its scope. When used in the SETUP section, it affects all variables in the entire program. Alternately, when it is placed in a local procedure, its effect is limited to the scope of the procedure. If the command is in both places, the local declaration takes precedence over the SETUP declaration.

In addition to declaring variables, the command enables the default numeric type to be specified using the DEFAULT-NUMERIC setting as FLOAT, INTEGER, or DECIMAL. When dealing with money or where more precision is required, you can use the DECIMAL qualifier.

The DECLARE-VARIABLE command, the -DNT command-line flag, and the DEFAULT-NUMERIC setting in the sqr.ini file affects the way numeric literals are typed. If V30 is specified, then all numeric literals are FLOAT (just as in pre-version 4.0 releases); otherwise, the use or lack of a decimal point determines the type of the literal as either FLOAT or INTEGER, respectively. Finally, not specifying DECLARE-VARIABLE command, the -DNT command-line flag, and the DEFAULT-NUMERIC setting in the sqr.ini file is the same as specifying V30.

Parameters

Parameter	Description
DEFAULT-NUMERIC	Specifies the default type for numeric variables. Unless explicitly declared otherwise, a numeric variable assumes the variable type. This qualifier overrides any setting from the command-line flag -DNT or the DEFAULT- NUMERIC entry in the [Default-Settings] section of the sqr.ini file. If -DNT was not specified on the command line and the sqr.ini file entry has no DEFAULT-NUMERIC entry, then the default numeric type is FLOAT.
DECIMAL	Specifies that the numeric variables that follow are decimal variables with a precision specified with prec_lit. The precision can be assigned to the group of variables or to each individual variable. The precision is the total number of digits used to represent the number. This precision can range from 1 to 38. The default value is 16. The range of decimal numbers is from -9.999999999999999999999999999999E±4096 to +9.999999999999999999999999999999E±4096
FLOAT	Specifies that the numeric variables that follow are used as double precision floating point. The range and precision of these numbers are machine-dependent.
DATE	Specifies that the date variables that follow can contain a date in the range of January1, 4713 BC to December 31, 9999 AD.
INTEGER	Specifies that the numeric variables that follow are used as integers with a range of -2147483648 to +2147483647.
TEXT	Specifies that the string variables that follow are text variables.

Example

```
begin-setup
  declare-variable
    default-numeric=float
    decimal #decimal(10)
    integer #counter
    date $date
  end-declare
end-setup

.
.

let $date = strtodate('Jan 01 2004', 'Mon DD YYYY')
print $date (1,1)
position (+2,1)

let #counter = 0
while #counter < 10
  let #decimal = sqrt(#counter)
  add 1 to counter
  print #decimal (+1,1) 9.999999999
end-while

do sub1($date, 'day', 10)
```

```

do sub2

.
.
begin-procedure sub1(:$dvar, $units, #uval)
declare-variable
  date $dvar
  integer #uval
end-declare
let $dvar = dateadd($dvar, $units, #uval)
print $dvar (+1,1)
position (+2,1)
end-procedure
.
.
begin-procedure sub2 LOCAL
declare-variable
  date $mydate
end-declare
let $mydate = dateadd($_date, 'year', 5)
print $mydate (+1,1)
position (+2,1)
end-procedure
.
.

```

#DEFINE

Syntax

```
#DEFINE substitution_variable value
```

Description

Declares a value for a substitution variable within the body of the report (rather than using the ASK command).

#DEFINE is useful for specifying constants such as column locations, printer fonts, or any number or string that is used in several locations in the program. When the value of the number or string must be changed, you need only change your #DEFINE command. All references to that variable change automatically, which makes modifying programs much simpler.

If the ASK command is used to obtain the value of a substitution variable that has already been defined, ASK uses the previous value and the user is not prompted. This enables you to predefine some variables and not others. When the report runs, ASK requests values for only those variables that have not had a value assigned.

You can use #DEFINE commands inside an include file. This is a method of gathering commonly used declarations into one place, and reusing them for more than one report.

The value in the #DEFINE command can have embedded spaces, and doesn't need to be enclosed within quotes. The entire string is used as is.

The #DEFINE command cannot be broken across program lines.

Parameters

Parameter	Description
substitution_variable	The variable to be used as the substitution variable. The substitution variable is used to substitute any command, argument, or part of a SQL statement at compile time.
Value	The value to be substituted.

Example

The following code defines several constants:

```
#define page_width 8.5
#define page_depth 11
#define light LS^10027
#define bold LS^03112
#define col1 1
#define col2 27
#define col3 54
#define order_by state, county, city, co_name
```

The following code example from a report uses the preceding definitions:

```
begin-setup

declare-printer contacts

    type=hp

    paper-size=({page_width}, {page_depth})

end-declare
end-setup
begin-heading 5
    print 'Company Contacts'      (1,1) center
    print 'Sort: {order_by}'      (2,1) center
    print 'Company'               (4,{col1})
    print 'Contact'               (4,{col2})
    print 'Phone'                 (4,{col3})
end-heading
begin-procedure main
begin-select
company      (1,{col1})
    print '{bold}'      (0,{col2})      ! Print contact in boldface.
contact      ()
    print '{light}'      ()            ! Back to lightface.
phone        (0,{col3})                ! Note: There must be enough
    next-listing                ! space between col2
from customers                ! and col3 for both
order by {order_by}            ! font changes and the
end-select                    ! contact field.
```

end-procedure

See Also

The ASK command.

DISPLAY

Syntax

```
DISPLAY {any_lit|_var|_col}  
[[ :$]edit_mask|NUMBER|MONEY|DATE][NOLINE]
```

Description

Displays the specified column, variable, or literal.

The DISPLAY command can display data to a terminal. The data is displayed to the current location on the screen. If you want to display more than one field on the same line, use NOLINE on each display except the last.

Dates can be contained in a date variable or column, or a string literal, column, or variable. When a date variable or column is displayed without an edit mask, the date appears in the following manner:

- For DATETIME columns and SQR DATE variables, the format specified by the SQR_DB_DATE_FORMAT setting is used. If this has not been set, SQR uses the first database-dependent format as listed in the Default Database Formats table.
- For DATE columns, the format specified by the SQR_DB_DATE_ONLY_FORMAT setting is used. If this has not been set, the format listed in the DATE Column Formats table is used.
- For TIME columns, the format specified by the SQR_DB_TIME_ONLY_FORMAT setting is used. If this has not been set, the format listed in the TIME Column Formats table is used.

When displaying a date in a string literal, column, or variable using EDIT or DATE, the string uses the format specified by the SQR_DB_DATE_FORMAT setting, one of the database-dependent formats as listed in the Default Database Formats table, or the database-independent format SYYYYMMDD[HH24[MI[SS[NNNNNN]]]].

If you require more control over the display, use the SHOW command.

Parameters

Parameter	Description
any_lit_var_col	The text, number, or date to be displayed.
edit_mask	Causes the field to be edited before being displayed. For additional information regarding edit masks, see the PRINT command.
NUMBER	Indicates that any_lit_var_col is to be formatted using the NUMBER-EDIT-MASK of the current locale. This option is not legal with date variables.
MONEY	Indicates that any_lit_var_col is to be formatted using the MONEY-EDIT-MASK of the current locale. This option is not legal with date variables.
DATE	Indicates that any_lit_var_col is to be formatted using the DATE-EDIT-MASK of the current locale. This option is not legal with numeric variables. If DATE-EDIT-MASK has not been specified, then the date is displayed using the default format for that database (see the Default Database Formats table).
NOLINE	Suppresses the carriage return after the field is displayed.

Example

The following segments illustrate the various features of the DISPLAY command:

```
!
! Display a string using an edit mask
!
display '123456789' xxx-xx-xxxx
```

Produces the following output:

```
123-45-6789
```

```
!
! Display a number using an edit mask
!
display 1234567.89 999,999,999.99
```

Produces the following output:

```
1,234,567.89
```

```
!
! Display a number using the default edit mask (specified in SQR.INI)
!
display 123.78
```

Produces the following output:

```
123.780000
```

```
!
! Display a number using the locale default numeric edit mask
```

```
!
alter-locale number-edit-mask = '99,999,999.99'
display 123456.78 number
```

Produces the following output:

```
123,456.78
```

```
!
! Display a number using the locale default money edit mask
!
alter-locale money-edit-mask = '$$, $$$, $$$9.99'
display 123456.78 money
```

Produces the following output:

```
$123,456.78
```

```
!
! Display a date column using the locale default date edit mask
!
begin-select
dcol
  from tables
end-select
alter-locale date-edit-mask = 'DD-Mon-YYYY'
display &dcol date
```

Produces the following output:

```
01-Jan-2004
```

```
!
! Display two values on the same line
!
display 'Hello' noline
display ' World'
```

Produces the following output:

```
Hello World
```

```
!
! Display two values on the same line with editing of the values
!
alter-locale money-edit-mask = '$$, $$$, $$$9.99'
let #taxes = 123456.78
display 'You owe ' noline
display #taxes money noline
display ' in back taxes.'
```

Produces the following output:

```
You owe $123,456.78 in back taxes.
```

See Also

The SHOW command for information about screen control.

The LET command for information about copying, editing, or converting fields.

The EDIT parameter of the PRINT command for a description of the edit masks.

The ALTER-LOCALE command for a description of the arguments NUMBER-EDIT-MASK, MONEY-EDIT-MASK, and DATE-EDIT-MASK.

DIVIDE

Syntax

```
DIVIDE {src_num_lit|_var|_col} INTO dst_num_var
[ON-ERROR={HIGH|ZERO}][ROUND=nn]
```

Description

Divides one number into another.

The source field is divided into the destination field and the result is placed in the destination.

The source is always first, the destination always second.

When dealing with money-related values (dollars and cents), use decimal variables rather than float variables. Float variables are stored as double precision floating point numbers, and small inaccuracies can appear when dividing many numbers in succession. These inaccuracies can appear due to the way different hardware and software implementations represent floating point numbers.

Parameters

Parameter	Description
src_num_lit _var _col	Divided into the contents of dst_num_var.
dst_num_var	Contains the result after execution.
ON-ERROR	Sets the result to the specified number when a division by zero is attempted. If ON-ERROR is omitted and a division by zero is attempted, SQR halts with an error message.
ROUND	Rounds the result to the specified number of digits to the right of the decimal point. For float variables, this value can be from 0 to 15. For decimal variables, this value can be from 0 to the precision of the variable. For integer variables, this argument is not appropriate.

Example

```
divide 37.5 into #price ! #price / 37.5
divide &rate into #tot on-error=high
divide #j into #subtot on-error=zero
```

Note. High in the preceding example is the maximum value, while zero is the lowest value.

See Also

The ADD command.

The LET command for a discussion of complex arithmetic expressions.

DO

Syntax

```
DO procedure_name[(arg1[, arg]...)]
```

Description

Invokes the specified procedure.

When the procedure ends, processing continues with the command following the DO command. You can use arguments to send values to or receive values from a procedure.

Arguments passed by a DO command to a procedure must match in number:

- Database text columns, string variables, and literals can be passed to procedure string or date arguments.
- Database numeric columns, numeric variables, and numeric literals can be passed to procedure numeric arguments.
- Numeric variables (DECIMAL, INTEGER, FLOAT) can be passed to procedure numeric arguments without regard to the argument type of the procedure. SQR automatically converts the numeric values upon entering and leaving the procedure as required.
- Date variables can be passed to procedure date or string arguments.

When a field in a DO command receives a value back from a procedure (a colon indicates it is a back value, that is, a value that's being returned), it must be a string, numeric, or date variable, depending on the procedure argument; however, a date can be returned to a string variable and vice versa.

When a date is passed to a string, the date is converted to a string according to the following rules:

- For DATETIME columns and SQR DATE variables, the format specified by the SQR_DB_DATE_FORMAT setting is used. If this has not been set, the first database-dependent format as listed in the Default Database Formats table is used.
- For DATE columns, the format specified by the SQR_DB_DATE_ONLY_FORMAT setting is used. If this has not been set, the format listed in the DATE Column Formats table is used.
- For TIME columns the format specified by the SQR_DB_TIME_ONLY_FORMAT setting is used. If this has not been set, the format as listed in the TIME Column Formats table is used.

Parameters

Parameter	Description
procedure_name	Specifies the name of the procedure to be executed.
arg1 [, argi]	Specifies the arguments to be passed to the procedure. Arguments can be any type of variable or constant value.

Example

```
do get_names
do add_to_list ($name)
do print_list ('A', #total, &co_name, $name)
```

See Also

The BEGIN-PROCEDURE command for information about passing arguments.
The PRINT command for information about date and time formats.

#ELSE

Syntax

#ELSE

Description

Compiles the code following the #ELSE command when a preceding #IF, #IFDEF, or #IFNDEF command is FALSE. (#ELSE is a compiler directive that works with the #IF, #IFDEF, and #IFNDEF compiler directives.)

See Also

The #IF, #IFDEF, and #IFNDEF commands for a description of each compiler directive.

ELSE

Syntax

ELSE

Description

ELSE is an optional command in an IF command.

See Also

The IF command for a description and example.

ENCODE

Syntax

ENCODE *src_code_string_lit* INTO *dst_txt_var*

Description

Assigns a nondisplay or display character to a string variable.

The ENCODE command can define nondisplay characters or escape sequences sent to an output device. These characters or sequences can perform complex output device manipulations. The ENCODE command also displays characters not in the keyboard. If your keyboard does not have the Euro symbol, use the ENCODE feature to create a string variable for it.

The encode characters can be included in a report at the appropriate location using a PRINT or PRINT-DIRECT command.

Unicode (UCS-2) code points from <1> to <65535> can be defined in ENCODE command.

Parameters

Parameter	Description
<i>src_code_string_lit</i>	Specifies a string of characters to be encoded and placed in <i>dst_txt_var</i> .
<i>dst_txt_var</i>	Contains the result after execution.

Example

```
encode '<27>L11233' into $bold           ! Code sequence to turn bold on.
```

```
print $bold ( ) code-printer=lp
```

See Also

The chr function described in the Miscellaneous Functions table under the LET command.
The PRINT and PRINT-DIRECT commands.

END-DECLARE, END-DOCUMENT, END-EVALUATE, END-FOOTING, END-HEADING

Syntax

```
END-DECLARE  
END-DOCUMENT  
END-EVALUATE  
END-FOOTING  
END-HEADING
```

Description

Completes a section or paragraph.

The END-DECLARE command completes a paragraph started with:

```
DECLARE-CHART  
DECLARE-IMAGE  
DECLARE-LAYOUT  
DECLARE-PRINTER  
DECLARE-PROCEDURE  
DECLARE-REPORT  
DECLARE-VARIABLE
```

Other END- commands complete the corresponding BEGIN- command:

```
BEGIN-DOCUMENT  
EVALUATE  
BEGIN-FOOTING  
BEGIN-HEADING
```

Each command must begin on its own line.

Example

```
begin-footing 2  
  print 'Company Confidential' (1) center  
end-footing
```

See Also

The DECLARE-paragraph command.
The BEGIN-section command.

#END-IF, #ENDIF

Syntax

```
#END-IF
```

Description

Ends an #IF, #IFDEF, or #IFNDEF command. (#END-IF is a compiler directive.)

#ENDIF (without the dash) is a synonym for #END-IF.

Example

```
#ifdef debuga
  show 'DebugA: #j = ' #j edit 9999.99
  show 'Cust_num = ' &cust_num
#end-if
```

See Also

The #IF, #IFDEF, and #IFNDEF commands for a description of each compiler directive.

END-IF

Syntax

END-IF

Ends an IF command.

See Also

The IF command for a description and example.

END-PROCEDURE, END-PROGRAM, END-SELECT, END-SETUP, END-SQL, END-WHILE

Syntax

END-PROCEDURE
END-PROGRAM
END-SELECT
END-SETUP
END-SQL
END-WHILE

Description

Completes the corresponding section or paragraph.

Each END- command completes the corresponding BEGIN- command:

```
BEGIN-PROCEDURE
BEGIN-PROGRAM
BEGIN-SELECT
BEGIN-SETUP
BEGIN-SQL
WHILE
```

Each command must begin on its own line.

Example

```
begin-program
  do main
end-program
```

See Also

The BEGIN-section command.

The WHILE command.

EVALUATE

Syntax

```
EVALUATE {any_lit|_var|_col}
```

This command is equivalent to case/switch in C or Java. The general format of an EVALUATE command is the following:

```
EVALUATE {any_lit|_var|_col}
WHEN comparison_operator {any_lit|_var|_col}
  SQR_Commands...
  [BREAK]
[WHEN comparison_operator {any_lit|_var|_col}
  SQR_Commands...
  [BREAK]]
[WHEN-OTHER
  SQR_Commands...
  [BREAK]]
END-EVALUATE
```

Description

Determines the value of a column, literal, or variable and takes action based on that value.

The EVALUATE command is useful for branching to different commands depending on the value of a specified variable or column.

EVALUATE commands can be nested.

Evaluating a date variable or column with a string results in a date comparison (chronological, not a byte by byte comparison as is done for strings). The string must be in the proper format as follows:

- For DATETIME columns and SQR DATE variables the format specified by the SQR_DB_DATE_FORMAT setting, SQR uses one of the database-dependent formats (see the Default Database Formats table), or the database-independent format 'YYYYMMDD[HH24[MI[SS[NNNNNN]]]]'.
- For DATE columns, SQR uses the format specified by the SQR_DB_DATE_ONLY_FORMAT setting, or the format listed in the DATE Column Formats table.
- For TIME columns, SQR uses the format specified by the SQR_DB_TIME_ONLY_FORMAT setting, or the format as listed in the TIME Column Formats table.

Parameters

Parameter	Description
any_lit _var _col	Specifies a text or numeric column; a text, numeric, or date variable; or a text or numeric literal to be used in the evaluation. In short, an evaluation argument.
comparison_operator	Any valid comparison operator. See the list of operators in the #IF command. . See Chapter 2, “SQR Command Reference,” #IF, page 122 .
WHEN	Specifies the evaluation expression. The evaluation argument is compared with the argument, beginning from the first WHEN. If the expression is TRUE, SQR processes the commands after the WHEN. If the expression is FALSE, SQR processes the next WHEN expression. Each WHEN must be on its own line. If more than one WHEN expression appears directly before a set of commands, any one of them, if TRUE, causes the commands to execute.
BREAK	Causes an immediate exit of the EVALUATE command. Use BREAK at the end of a set of commands.
WHEN-OTHER	Signifies the start of default commands to be processed if all other WHEN expressions are FALSE. WHEN-OTHER must appear after all other WHEN expressions.

Example

```

evaluate &code
  when = 'A'
    move 1 to #j
    break
  when = 'B'
  when = 'C'
    move 2 to #j      ! Will happen if &code is B or C.
    break
  when > 'D'
    move 3 to #j      ! Move 3 to #j and continue checking.
  when > 'H'
    add 1 to #j       ! Add 1 to #j and continue checking.
  when > 'W'
    add 2 to #j
    break
  when-other
    if isnull (&code)
      do null_code
    else
      move 0 to #j    ! Unknown code.
    end-if
  break
end-evaluate

```

See Also

The commands IF and LET for comparison operators.

EXECUTE (Sybase and Microsoft SQL Server)

Syntax

```
EXECUTE [-XC][ON-ERROR=procedure[(arg1[,argi]...)]]  
[DO=procedure[(arg1[,argi]...)]]  
[@#status_var=]stored_procedure_name  
[@param={any_col|_var|_lit}[,...]]  
[INTO any_coldata_type[(length_int_lit)]  
[,...]][WITH RECOMPILE]
```

The syntax of this command generally follows that of the Sybase Transact-SQL EXECUTE command, with the exception of optional arguments and the INTO argument.

Description

Executes a stored procedure in Sybase or Microsoft SQL Server database.

If the stored procedure specified in **stored_procedure_name** contains a SELECT query, the EXECUTE command must specify an INTO argument to process the values from the query. If no INTO argument is specified, then the values from the query are ignored.

EXECUTE retrieves just the first row when the following instances are true:

- The DO procedure is not specified.
- The stored procedure, **stored_procedure_name** selects one or more rows.
- An INTO argument is specified.

This is useful for queries returning a single row.

Parameters

Parameter	Description
-XC (Sybase only)	Specifies that the EXECUTE command shares the same connection as the DO=procedure it can invoke. This argument is required to share Sybase temporary tables.
ON-ERROR	Declares an SQR procedure to execute if an error occurs. If ON-ERROR is omitted and an error occurs, SQR halts with an error message. For severe errors (for example, passing too few arguments) SQR halts, even if an error procedure is specified. You can specify arguments to be passed to the ON-ERROR procedure. Arguments can be any variable, column, or literal.
DO	Specifies an SQR procedure to execute for each row selected in the query. Processing continues until all rows have been retrieved. You can specify arguments to be passed to the procedure. Arguments can be any variable, column, or literal.
@#status_variable	Returns the procedure status in the specified numeric variable. The status is returned only after selected rows are retrieved.
stored_procedure_name	Names the stored procedure to execute.
@param	Names the parameter to pass to the stored procedure. Parameters can be passed with or without names. If used without names, they must be listed in the same sequence as defined in the stored procedure.
any_lit _var _col	Specifies the value passed to the stored procedure. It can be a string, numeric, or date variable, a previously selected column, a numeric literal, or a string literal.
OUT[PUT]	Indicates that the parameter receives a value from the stored procedure. The parameter must be a string, numeric, or date SQR variable. Output parameters receive their values only after rows selected have been retrieved. If you specify multiple output parameters, they must be in the same sequence as defined in the stored procedure.
INTO	Indicates where to store rows that are retrieved from the stored procedure's SELECT statement. The INTO argument contains the names of the columns with data types and lengths (if needed). You must specify the columns in the same sequence and match the data type used in the stored procedure's SELECT statement. If the stored procedure contains more than one SELECT query, only the first query is described with the INTO argument. Rows from subsequent queries are ignored. WITH RECOMPILE Causes the query to recompile each time it is executed rather than using the plan stored with the procedure. Normally, this is not required or recommended.

Example

The following code example invokes the stored procedure **get_total** with two parameters: a string literal and a string variable. The result from the stored procedure is stored in the variable *#total*.

```
execute get_total 'S. Q. Reporter' $State #Total Output
```

The following code example invokes the stored procedure **get_products** with two parameters. The stored procedure selects data into five column variables. The SQR procedure **print_products** is called for each row retrieved. The return status from the stored procedure is placed in the variable *#proc_return_status*.

```
execute do=print_products
    @#proc_return_status=
    get_products
```

```

        @prodcode=&code,          @max=#maximum
        INTO &prod_code          int,
        &description            char (45),
        &discount                float,
        &restock                 char,
        &expire_date             datetime

begin-procedure print_products
print &prod_code                (+1,1)
print &description              (+5,45)
print &discount                 (+5) edit 99.99
print &restock                  (+5) match Y 0 5 Yes N 0 5 No
print &expire_date              (+5,) edit 'Month dd, yyyy'
end-procedure

```

EXIT-SELECT

Syntax

EXIT-SELECT

Description

Exits a SELECT paragraph immediately.

EXIT-SELECT causes SQR to jump to the command immediately following the END-SELECT command.

Use EXIT-SELECT when you need to end a query before all rows have been retrieved.

Example

```

begin-select
cust_num, co_name, contact, city, state, zip, employees
add &employees to #tot_emps
if #tot_emps >= 5000
    exit-select          ! Have reached required total emps.
end-if
do print_company
from customers order by employees desc
end-select

```

See Also

The BEGIN-SELECT command.

EXTRACT

Syntax

```

EXTRACT {dst_txt_var|date_var} FROM
{{src_txt_lit|_var|_col}|{src_date_var|_col}}
{start_num_lit|_var}{length_num_lit|_var}

```

Description

Copies a portion of a string into a string variable.

You must specify the starting location of the string as an offset from the beginning of the string and its length. An offset of zero (0) begins at the leftmost character; an offset of 1 begins one character beyond that, and so on.

If the source is a date variable or column, it is converted to a string before the extraction according to the following rules:

- For DATETIME columns and SQR DATE variables SQR specifies the SQR_DB_DATE_FORMAT setting. If this has not been set, the first database-dependent format as listed in the Default Database Formats table is used.
- For DATE columns SQR uses the format specified by the SQR_DB_DATE_ONLY_FORMAT setting. If this has not been set, the format listed in the DATE Column Formats table is used.
- For TIME columns the format specified by the SQR_DB_TIME_ONLY_FORMAT setting is used. If this has not been set, the format as listed in the TIME Column Formats table is used.

If the destination is a date variable, the string extracted from the source must be in one of the following formats:

- The format specified by the SQR_DB_DATE_FORMAT setting
- One of the database-dependent formats (see the Default Database Formats table)
- The database-independent format 'SYYYYMMDD[HH24[MI[SS[NNNNNN]]]]'.

Parameters

Parameter	Description
dst_txt_var date_var	Specifies a text or date variable into which the extracted string is placed.
{src_txt_lit _var _col} {src_date_var _col}	Specifies a text or date variable, column, or literal from which the string is to be extracted.
start_num_lit _var	Specifies starting location of the string to be extracted.
length_num_lit _var	Specifies length of the string to be extracted.

Example

```
extract $state from $record 45 2
extract $foo from "SQR Rocks" 0 4 ! $foo='SQR'

code from &phone 0 3
extract $zip_four from &zip 5 4
extract $rec from $tape_block #loc #rec_len
```

Note. PeopleSoft recommends that you do not use the EXTRACT command when processing strings.

See Also

The substr function described in Miscellaneous Functions table under the LET command.

The FIND command.

The PRINT command for information about default date and time formats

FIND

Syntax

```
FIND {{obj_txt_lit|_var|_col}}|{date_var|_col}} IN
{{src_txt_var|_col}}|{date_var|_col}}
{start_int_lit|_var} dst_location_int_var
```

Description

Determines the location of a character sequence within a string.

FIND searches the specified string for a character sequence and, if the string is found, returns its location as an offset from the beginning of the specified string. If the sequence is not found, FIND returns -1 in *dst_location_int_var*.

You must specify an offset from which to begin the search and supply a numeric variable for the return of the location.

If the source or search object is a date variable or column, it is converted to a string before the search according to the following rules:

- For DATETIME columns and SQR DATE variables, the format specified by the SQR_DB_DATE_FORMAT setting is used. If this has not been set, the first database-dependent format as listed in the Default Database Formats table is used.
- For DATE columns, the format specified by the SQR_DB_DATE_ONLY_FORMAT setting is used. If this has not been set, the format listed in the DATE Column Formats table is used.
- For TIME columns, the format specified by the SQR_DB_TIME_ONLY_FORMAT setting is used. If this has not been set, the format as listed in the TIME Column Formats table is used.

Parameters

Parameter	Description
{{obj_txt_lit _var _col}} {date_var _col}}	Specifies a text variable, column, or literal that is to be sought in <i>src_txt_var _col</i> .
{src_txt_var _col} {date_var _col}	Specifies a text variable or column to be searched.
start_int_lit_var	Specifies the starting location of the search.
dst_location_int_var	Specifies the returned starting location of the leftmost character of the matching text in <i>{src_txt_var _col date_var _col }</i> .

Example

```
find 'aw.2' in &code5 0 #loc
find ',' in &name 0 #comma_loc
if #comma_loc = -1
...comma not found...
```

See Also

The instr function described in the Miscellaneous Functions table under the LET command.

The EXTRACT command.

The PRINT command for information about default date and time formats.

GET

Syntax

```
GET dst_any_var...FROM src_array_name(element)
[field[(occurs)]]...
```

Description

Retrieves data from an array and places it into a date, string, or numeric variable.

Parameters

Parameter	Description
<i>dst_any_var</i>	Date, string, or numeric variables (not database columns) can be destination variables. Numeric variables (decimal, float, integer) are copied from number fields. String variables are copied from char, text, or date fields. Date variables are copied from char, text, or date fields. When a date field is copied to a string variable, SQR converts the date to a string in the format specified by the SQR_DB_DATE_FORMAT setting. If this has not been set, SQR uses the first database-dependent format listed in the Default Database Formats table. If the destination is a date variable, the string extracted from the source must be in the format specified by the SQR_DB_DATE_FORMAT setting, or one of the database-dependent formats (see the Default Database Formats table), or the database-independent format 'YYYYMMDD[HH24[MI[SS[NNNNNN]]]]'.
<i>src_array_name</i> (<i>element</i>)	If the array's field names are listed, SQR takes the values from the fields and occurrences specified. If the array's field names are not listed, the values are taken from consecutively defined fields in the array.
<i>field</i> [(<i>occurs</i>)]	Array element and field occurrence numbers can be numeric literals (such as 123) or numeric variables (such as #j). If no field occurrence is stated, occurrence zero is used.

Example

The following code example copies *\$name*, *\$start_date*, and *#salary* from the first three fields in the #j'th element of the *emps* array.

```
get $name $start_date #salary from emps(#j)
```

The following code example copies *#city_tot* and *#county_tot* from the fields *cities* and *counties* in the #j'th element of the *states* array.

```
get #city_tot #county_tot from states(#j) cities counties
```

The following code example copies *\$code* from the #j'th occurrence of the *code* field in the #n'th element of the *codes* array.

```
get $code from codes(#n) code(#j)
```

See Also

The PUT command for information about moving data into an array.

GET-COLOR

Syntax

```
GET-COLOR
```

```
[PRINT-TEXT-FOREGROUND=({color_name_var | {rgb}})]
[PRINT-TEXT-BACKGROUND=({color_name_var | {rgb}})]
```

Description

Retrieves the current colors.

The GET-COLOR command is allowed wherever the PRINT command is allowed. If the requested color settings do not map to a defined name, then the name is returned as *RGBredgreenblue*, where each component is a three digit number—for example, *RGB127133033*. You can use this format wherever you use a color name. The color name *none* is returned if no color is associated with the specified area.

Parameters

Parameter	Description
PRINT-TEXT-FOREGROUND	Defines the color in which the text prints.
PRINT-TEXT-BACKGROUND	Defines the color to print as a background behind the text.
{color_name_var}	A color_name is composed of the alphanumeric characters (A-Z, 0-9), the underscore (_) character, and the hyphen (-) character. The name must start with an alphabetical (A-Z) character and is case insensitive. The name 'none' is reserved and cannot be assigned a value. A name in the format (RGBredgreenblue) cannot be assigned a value. The name 'default' is reserved and can be assigned a value. 'Default' is used during execution when a referenced color is not defined in the runtime environment.
{rgb}	<i>red_lit _var _col, green_lit _var _col, blue_lit _var _col</i> where each component is a value in the range of 000 to 255. In the BEGIN-SETUP section, only literal values are allowed. The default colors implicitly installed with SQR include: black=(0,0,0) white=(255,255,255) gray=(128,128,128) silver=(192,192,192) red=(255,0,0) green=(0,255,0) blue=(0,0,255) yellow=(255,255,0) purple=(128,0,128) olive=(128,128,0) navy=(0,0,128) aqua=(0,255,255) lime=(0,128,0) maroon=(128,0,0) teal=(0,128,128) fuchsia=(255,0,255)

Example

```
begin-setup
  declare-color-map
    light_blue = (193, 222, 229)
  end-declare
end-setup
```



```

begin-program
  alter-color-map name = 'light_blue' value = (193, 233, 230)

  print 'Yellow Submarine' ()
    foreground = ('yellow')
    background = ('light_blue')

  get-color print-text-foreground = ($print-foreground)
  set-color print-text-foreground = ('purple')
  print 'Barney' (+1,1)
  set-color print-text-foreground = ($print-foreground)
end-program

```

See Also

The DECLARE-COLOR-MAP, ALTER-COLOR-MAP, and SET-COLOR commands.

GOTO

Syntax

`GOTO label`

Description

Skips to the specified label.

Labels must end with a colon (:) and can appear anywhere within the same section or paragraph as the GOTO command.

Parameters

Parameter	Description
label	Specifies a label within the same section or paragraph.

Example

```

begin-select
price
  if &price < #old_price
    goto next
  end-if
  print &price (2,13,0) edit 999,999.99
  ...
next:
  add 1 to #count
from products
end-select

```

GRAPHIC BOX, GRAPHIC HORZ-LINE, GRAPHIC VERT-LINE

Syntax

The GRAPHIC commands have the following syntax:

```
GRAPHIC ({line_int_lit|_var},{column_int_lit|_var},  
{width_int_lit|_var})
```

```
BOX {depth_int_lit|_var}  
[rule_width_int_lit|_var[shading_int_lit|_var]]
```

```
GRAPHIC ({line_int_lit|_var},{column_int_lit|_var},  
{length_int_lit|_var})
```

```
HORZ-LINE [rule_width_int_lit|_var]
```

```
GRAPHIC ({line_int_lit|_var},{column_int_lit|_var},  
{length_int_lit|_var})
```

```
VERT-LINE [rule_width_int_lit|_var]
```

Description

Draws a box or line.

After GRAPHIC commands execute, SQR changes the current print location to the starting location of the graphic. (This is different from the way the PRINT command works.)

The GRAPHIC command has the following variations:

- BOX
- HORZ-LINE
- VERT-LINE

The following sections describe the individual GRAPHIC commands:

Parameters

Parameter	Description
BOX	BOX draws a box of any size at any location on the page. Boxes can be drawn with any size rule and can be shaded or left empty.
<i>width and depth</i>	The width is the horizontal size in character columns; depth is the vertical size in lines. The top left corner of the box is drawn at the line and column specified. The bottom right corner is calculated using the width and depth. You can specify relative placement with (+), (-), or numeric variables, as with regular print positions.
<i>rule_width</i>	The default rule width is 2 decipoints (there are 720 decipoints per inch). The top horizontal line is drawn just below the base of the line above the starting point. The bottom horizontal line is drawn just below the base of the ending line. Therefore, a one-line deep box surrounds a single line.
<i>shading</i>	A number between 1 and 100, specifying the percentage of shading to apply. 1 is very light, and 100 is black. If no shading is specified, the box is blank. Specify a rule-width of zero, if a border is not desired.
HORZ-LINE	HORZ-LINE draws a horizontal line from the location specified, for the length specified. Horizontal lines are drawn just below the base.
<i>rule_width</i>	The default rule width is 2 decipoints.
VERT-LINE	VERT-LINE draws a vertical line from the location specified for the length (in lines) specified. Vertical lines are drawn just below the base line of the line position specified to just below the base line of the line reached by the length specified. To draw a vertical line next to a word printed on line 27, position the vertical line to begin on line 26, for a length of 1 line.
<i>rule_width</i>	The default rule width is 2 decipoints.

Example

The following code example shows the GRAPHIC BOX command:

```

graphic (1,1,66) box 58 20      ! Draw box around page
graphic (30,25,10) box 10      ! Draw a 10-characters-wide-by-10- characters-long box
graphic (1,1,66) box 5 0 8     ! Draw 5 line shaded box (without border)
graphic (50,8,30) box 1        ! Draw box around 1 line

```

The following code example shows the GRAPHIC HORZ-LINE command:

```

graphic (4,1,66) horz-line 10  ! Put line under page heading
graphic (+1,62,12) horz-line   ! Put line under final total

```

The following code example shows the GRAPHIC VERT-LINE command:

```

graphic (1,27,54) vert-line     ! Draw lines between columns
graphic (1,52,54) vert-line
graphic (3,+2,4) vert-line 6    ! Red line the paragraph

```

See Also

The ALTER-PRINTER and DECLARE-PRINTER commands for information about setting and changing the FONT, FONT-TYPE, POINT-SIZE, and PITCH.

#IF

Syntax

```
#IF {txt_lit|num_lit}comparison_operator
{txt_lit|num_lit}
```

Description

Indicates that the commands following are to be compiled when the expression is TRUE. (#IF is a compiler directive.)

SQR has five compiler directives that enable different pieces of SQR code to be compiled, depending on the existence or value of substitution variables (not program variables, such as, string, numeric, or date).

Substitution variables defined automatically for each -DEBUGxxx letter can also be used with the #IF, #IFDEF, and #IFDEF directives. They can turn entire sections of an SQR program on or off from the command line, depending on the -DEBUGxxx flag.

You can nest #IF, #IFDEF, or #IFDEF directives to a maximum of 10 levels.

The #IF, #IFDEF, or #IFDEF directives cannot be broken across program lines.

The following table lists the compiler directives.

Directive	Example	Description
#IF	#IF {option}='A'	Compiles the commands following the #IF directive if the substitution variable option is equal to 'A'. The test is case-insensitive. Only one simple expression is allowed per #IF command.
#ELSE	#ELSE	Compiles the commands following the #ELSE directive when the #IF expression is FALSE.
#ENDIF	#ENDIF	Ends the #IF directive. #ENDIF can also be typed #END-IF (with a hyphen).
#IFDEF	#IFDEF option	Compiles the commands following the #IFDEF directive if the substitution variable option is defined.
#IFNDEF	#IFNDEF option	Compiles the command following the #IFNDEF directive if the substitution variable option is not defined.

Parameters

Parameter	Description
txt_lit num_lit	Any text or numeric literal.
comparison_operator	Any of the comparison operators as follows: =Equal !=Not Equal <>Not Equal <Less than >Greater than <=Less than or equal >=Greater than or equal

Example

```

begin-setup
  ask type 'Use Male, Female or Both (M,F,B)'
end-setup
begin-procedure Main
  #if {type} = 'M'
    ...code for M here
  #else
    #if {type} = 'F'
      ...code for F here
    #else
      #if {type} = 'B'
        ...code for B here
      #else
        show 'M, F or B not selected.   Report not created.'
        stop
      #endif    ! for B
    #endif    ! for F
  #endif    ! for M

  #ifdef  debug
    show 'DEBUG:  Cust_num = '  &cust_num  edit  099999
  #endif

  #ifndef debugB                ! DebugB turned on with -DEBUGB on
    do test_procedure           ! SQR command line.
  #endif

```

See Also

The #DEBUG command for information about the -DEBUG command-line flag.

IF

Syntax

IF *logical_expression*

IF commands have the following structure:

```
IF logical_expression
SQR Commands...
[ELSE
SQR Commands...]
END-IF
```

Description

Executes commands depending on the value of a condition.

The expression is evaluated as a logical TRUE or FALSE. A value or expression that evaluates to nonzero is TRUE.

Each IF command must have a matching END-IF command.

IF commands can be nested.

Comparing a date variable or column with a string, results in a date comparison (chronological, not a byte by byte comparison as is done for strings). The string must be in the proper format as follows:

- For DATETIME columns and SQR DATE variables, the format specified by the SQR_DB_DATE_FORMAT setting, one of the database-dependent formats (see the Default Database Formats table), or the database-independent format 'SYYYMMDD[HH24[MI[SS[NNNNNN]]]]' is used.
- For DATE columns, the format specified by the SQR_DB_DATE_ONLY_FORMAT setting, or the format listed in the Date Column Formats table is used.
- For TIME columns, the format specified by the SQR_DB_TIME_ONLY_FORMAT setting, or the format as listed in Time Column Formats table is used.

Parameters

Parameter	Description
logical_expression	Any valid logical expression. See the LET command for a description of logical expressions.

Example

```
if &price > &old_price and instr(&code, 'M', 1) > 0
  add 1 to #price_count
  if #price_count > 50
    show 'More than 50 prices found.' noline
    input $x 'Continue? (Y/N)'
    if upper($x) = 'N'
      stop
    end-if
  end-if
else
  add 1 to #old_price_count
end-if
if #rows ! Will be TRUE if #rows is non-zero.
  do print-it
end-if
```

```

if $date1 > 'Apr 21 2004 23:59'
do past_due
end-if

```

See Also

The LET command for a description of logical expressions.
The EVALUATE command.

#IFDEF

Syntax

`#IFDEF substitution_variable`

Description

Indicates that the following commands are to be compiled when the substitution variable has been declared by an ASK or #DEFINE command, or by the -DEBUG flag on the SQR command line. (#IFDEF is a compiler directive.)

Parameters

Parameter	Description
substitution_variable	Is the variable to be used as the substitution variable.

See Also

The #IF command for a description of each compiler directive.

#IFNDEF

Syntax

`#IFNDEF substitution_variable`

Description

Indicates that the following commands are to be compiled when the substitution variable has not been declared by an ASK or #DEFINE command, or by the -DEBUG flag on the SQR command line. (#IFNDEF is a compiler directive.)

Parameters

Parameter	Description
substitution_variable	Is the variable to be used as the substitution variable.

See Also

The #IF command for a description of each compiler directive.

#INCLUDE

Syntax

```
#INCLUDE filename_lit
```

Description

Includes an external source file into the SQR report specification.

You may want to keep commonly used routines in a single file and reference or *include* that file in programs that use the routine. For example, you might have a set of #DEFINE commands for different printers to control initialization, font changes, and page size declarations. You can reference the appropriate include file depending on which printer you want to use.

Include files can be nested up to four levels. Variable substitution scanning takes place before the #INCLUDE command is processed. This enables you to substitute all or part of the include file name at runtime, adding flexibility to controlling which file is included for the run.

Parameters

Parameter	Description
filename_lit	A file name that is valid for the platform on which this application is to be compiled.

Example

```
#include 'gethours.dat'      ! Common procedure.
#include 'XYZheader.dat'     ! Common report heading for XYZ Company.
#include 'printer{num}.dat'  ! Include printer definitions for
                           ! printer {num}, which is passed
                           ! on the command line:
                           ! SQR REP1A SAM/JOE 18
                           ! where 18 is the arbitrary number
                           ! assigned your printer
                           ! definition file, 'printer18.dat'.
                           ! The report would contain the
                           ! command: ASK num
                           ! in the SETUP section, preceding
                           ! this #include statement.
```

INPUT

Syntax

```
INPUT input_var[MAXLEN=nn][prompt]
[TYPE={CHAR|TEXT|NUMBER|INTEGER|DATE}]
[STATUS=num_var][NOPROMPT][BATCH-MODE]
[FORMAT={txt_lit|_var|_col}]
```

Description

Accepts data entered by the user at a terminal.

Use MAXLEN to prevent the user from entering data that is too long. If an INSERT or UPDATE command references a variable whose length is greater than that defined in the database, the SQL is rejected and SQR halts. If the maximum length is exceeded, the terminal beeps (on some systems, this may cause the screen to flash instead).

If *prompt* is omitted, SQR uses the default prompt, Enter [\$/#]var:. In any case, a colon (:) and two spaces are added to the prompt.

Specifying TYPE causes data type checking to occur. If the string entered is not the type specified, the terminal beeps and an error message is displayed. The INPUT command is then re-executed. If TYPE=DATE is specified, then *input_var* can be a date or text variable; however, TYPE=DATE is optional if *input_var* is a date variable. If a numeric variable is used, it is validated as a numeric variable. The types CHAR, TEXT, and DATE are invalid types. The data types supported are described in the following table:

Data Type	Description
CHAR, TEXT	Any character. This is the default datatype.
NUMBER	A floating point number in the format [+ -]9999.999[E [+ -]99]
INTEGER	An integer in the format [+ -]99999
DATE	A date in one of the following formats: - MM/DD/YYYY [BC AD] [HH:MI[:SS[.NNNNNN]] [AM PM]] - MM-DD-YYYY [BC AD] [HH:MI[:SS[.NNNNNN]] [AM PM]] - MM.DD.YYYY [BC AD] [HH:MI[:SS[.NNNNNN]] [AM PM]] - SYYYMMDD[HH24[MI[SS[NNNNNN]]]]

Specifying STATUS causes the INPUT command to complete regardless of what the user enters. No error message is displayed. A nonzero error code is stored in the indicated numeric variable if the length or datatype entered is incorrect.

The following table lists the values of the INPUT command's STATUS argument:

Status Value	Indicates
0	Successful.
1	Bad type (did not match the datatype of TYPE).

Status Value	Indicates
2	Too long (longer than MAXLEN or the input for an INTEGER variable is < -2147483648 or > +2147483647).
3	No arguments remain on the command line. The command was ignored.

By using NOPROMPT and STATUS with the SHOW command, you can write a sophisticated data entry routine.

FORMAT can only be used with dates. It can be a date edit mask or the keyword DATE. Use the keyword DATE if the date must be in the format as specified with INPUT-DATE-EDIT-MASK setting for the current locale. If FORMAT has not been set, use a database-independent format for the data as listed in the datatypes table.

Parameters

Parameter	Description
input_var	Specifies a text, numeric, or date variable for the input data.
MAXLEN	Specifies the maximum length for the data.
prompt	Specifies the prompt displayed to the user.
TYPE	Specifies the datatype required for the input.
STATUS	Specifies a numeric variable for a return status code.
NOPROMPT	Prevents the prompt from being displayed before the INPUT command is processed.
BATCH-MODE	If BATCH-MODE is specified and no more arguments are in the command line, a value of 3 is returned in the STATUS variable and the user is not prompted for input.
FORMAT	Specifies the format for entering a date. The Date Edit Format Codes table lists date edit format codes.

Example

The following example shows several INPUT commands:

```
input $state maxlen=2 'Please enter state abbreviation'
input #age 'Enter lower age boundary' type=integer
input $start_date 'Enter starting date for report' type=date
input $date_in format='Mon dd yyyy'
input $date format=date
```

The following example shows another INPUT command:

```
show clear-screen (5,32) reverse 'CUSTOMER SUMMARY' normal
Try_again:
show (12,20) 'Enter Start Date: ' clear-line
input $start-date noprompt status=#istat type=date
if #istat != 0
```

```

        show (24,1) 'Please enter date in format DD-MON-YY' beep
        goto try_again
    end-if
    show (24,1) clear-line           ! Clear error message line.

```

The following example illustrates the use of the BATCH-MODE option:

```

begin-program
while (1)
    input $A status=#stat batch-mode
    if #stat = 3
        break
    else
        do procedure ($a)
    end-if
end-while
end-program

```

See Also

The ALTER-LOCALE command.

The INPUT-DATE-EDIT-MASK setting in the chapter “Using the PSSQR.INI File and the PSSQR Command Line.”

LAST-PAGE

Syntax

LAST-PAGE *position* [*pre_txt_lit* [*post_txt_lit*]]

Description

Places the last page number on each page, as in *page n of m*.

The text strings specified in *pre_txt_lit* and *post_txt_lit* are printed immediately before and after the number.

Using LAST-PAGE causes SQR and SQRT to delay printing until the last page has been processed so that the number of the last page is known.

Parameters

Parameter	Description
position	Specifies the position for printing the last page number.
pre_txt_lit	Specifies a text string to be printed before the last page number.
post_txt_lit	Specifies a text string to be printed after the last page number.

Example

```

begin-footing 1
    page-number      (1,37) 'Page '      ! Will appear as
    last-page        ( ) ' of ' '. '      ! "Page 12 of 25."
end-footing

```

See Also

The PAGE-NUMBER, BEGIN-HEADING, and BEGIN-FOOTING commands.

LET

Syntax

```
LET dst_var=expression
```

Description

Assigns the value of an expression to a string, numeric, or date variable.

Valid expressions are formed as a combination of operands, operators, and functions. String, numeric, date, and array field operands can be used in an expression and embedded functions. SQR supports a standardized set of mathematical operators and logical comparison operators working within a carefully defined set of precedence rules. SQR also provides a rich set of mathematical, string, date, and file manipulation functions along with a number of special purpose utility functions. All combined, the SQR expression provides a powerful tool that can be tailored to suit any information processing need. The following detail outlines the specific behavior of each expression component: (1) the operand, (2) the operator, and (3) the function.

Parameters

Parameter	Description
<i>dst_var</i>	A string, numeric, or date variable or array field to which the result of the expression is assigned.
<i>expression</i>	The expression to evaluate.

Operands

Operands form the backbone of an SQR expression. Operands do not have to be the same type. You can combine string, numeric and array field operands to form a valid expression. SQR performs a sequence of automatic operand conversions as it evaluates expressions that contain dissimilar operand types. As the expression is evaluated, operands of lower precision are converted to match the operand of higher precision. Consider the following code example:

```
let #answer = #float * #decimal / #integer
```

Because the *multiply* and *divide* operators are equal in precedence, the expression is evaluated as $(\text{\#float} * \text{\#decimal}) / \text{\#integer}$. Working from the inside out, the *#float* variable is converted to a decimal type where a multiply is performed yielding the simplified expression, $(\text{\#decimal})/\text{\#integer}$. SQR now converts the *#integer* operand to a decimal type before performing the final divide. When finished with the expression evaluation, SQR converts the result to match the type of the *#answer* variable.

Converting operands of lower precision to operands of higher precision preserves the number of significant digits. The number of significant digits is not lost when an integer is converted to float or decimal. In a similar manner, the number of significant digits is preserved when floating point operands are converted to the decimal type. The number of significant digits is only sacrificed when the final result is converted to match the type of the *#answer* variable and this variable is less precise than the highest of the operands being evaluated. In the example, precision is not lost if the *#answer* is declared as a decimal type. SQR considers integer variables as the lowest in the precision hierarchy, followed by float and then decimal.

Here are a few simple expression examples:

```
let #discount = round (&price * #rate / 100, 2)
```

```

let $name = $first_name || ' ' || $last_name
let customer.total (#customer_id) =

    customer.total (#customer_id) + #invoice_total
if not range(upper($code), 'A', 'G')
    ...processing when out of range...
let store.total (#store_id, #qtr) =

    store.total (#store_id, #qtr) + #invoice_total
let $date1 = strtodate ('Apr 10 2004', 'MON DD YYYY')

```

The following sections list operators and functions supported in expressions.

Operators

The following table lists operators in descending order of precedence. Operators listed in the same row within the table have the same precedence (the operators *, /, % are equal in precedence).

Operators of the same precedence are processed in the sequence in which they appear in the expression, from left to right. Use parentheses to override the normal precedence rules. All numeric types (decimal, float, integer) are supported for all operators.

Operator	Explanation
	Concatenate two strings or dates
+, -	Sign prefix (positive or negative)
^	Exponent
*, /, %	Multiply, divide, remainder: a % b = mod(a,b) for integers
+, -	Plus, minus Note. SQR distinguishes between a sign prefix and arithmetic operation by the context of the expression.
>, <, >=, <=, <>, !=, =	Comparison operators: greater than, less than, greater or equal to, less than or equal to, not equal (!= or <>), equal
not	Logical NOT
and	Logical AND
or, xor	Logical OR, XOR (exclusive OR)

Functions

This section lists numeric, file-related, and miscellaneous functions. The functions are listed in alphabetical order.

Function arguments are enclosed in parentheses and can be nested. Arguments referenced as x, y, or z indicate the first, second, or third argument of a function. Otherwise, functions take a single argument or no arguments. All arguments are evaluated before a function is evaluated.

Not all functions support all numeric types (decimal, float, integer). Certain functions do not support the decimal type directly, but convert input decimal operands to the float type before the function is evaluated. The following table annotates the functions that directly support the decimal type and the ones that do not.

Use parentheses to override the normal precedence rules.

The following table lists numeric functions:

Function	Description
abs	Returns the absolute value of <i>num_value</i>. This function returns a value of the same type as <i>num_value</i>. Syntax: <pre>dst_var = abs(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #dabsvar = abs(#dvar)</pre>
acos	Returns the arccosine of <i>num_value</i>. In the range of 0 to π radians. The value of <i>num_value</i> must be between -1 and 1. This function returns a float value. Syntax: <pre>dst_var = acos(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #facosvar = acos(#fvar)</pre>

Function	Description
asin	Returns the arcsine of <i>num_value</i> in the range of -p/2 to p/2 radians. The value of <i>num_value</i> must be between -1 and 1. This function returns a float value. Syntax: <pre>dst_var = asin(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #fasinvar = asin(#fvar)</pre>
atan	Returns the arctangent of <i>num_value</i> in the range of -p/2 to p/2 radians. The value of <i>num_value</i> must be between -1 and 1. This function returns a float value. Syntax: <pre>dst_var = atan(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #fatanvar = atan(#fvar)</pre>
ceil	Returns a value representing the smallest integer that is greater than or equal to <i>num_value</i>. This function returns a value of the same type as <i>num_value</i>. Syntax: <pre>dst_var = ceil(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #fceilvar = ceil(#fvar)</pre>

Function	Description
cos	Returns the cosine of <i>num_value</i>. This function returns a float value. Syntax: <pre>dst_var = cos(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #fcosvar = cos(#fvar)</pre>
cosh	Returns the hyperbolic cosine of <i>num_value</i>. This function returns a float value. Syntax: <pre>dst_var = cosh(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #fcoshvar = cosh(#fvar)</pre>
deg	Returns a value expressed in degrees of <i>num_value</i> which is expressed in radians. This function returns a float value. Syntax: <pre>dst_var = deg(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #fdegvar = deg(#fvar)</pre>

Function	Description
e10	Returns the value of 10 raised to <i>num_value</i>. This function returns a float value. Syntax: <pre>dst_var = e10(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #fe10var = e10(#fvar)</pre>
exp	Returns the value of e raised to <i>num_value</i>. This function returns a float value. Syntax: <pre>dst_var = exp(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #fexpvar = exp(#fvar)</pre>
floor	Returns a value representing the largest integer that is less than or equal to <i>num_value</i>. This function returns a value of the same type as <i>num_value</i>. Syntax: <pre>dst_var = floor(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #ffloorvar = floor(#fvar)</pre>

Function	Description
log	Returns the natural logarithm of <i>num_value</i>. This function returns a float value. Syntax: <pre>dst_var = log(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #flogvar = log(#fvar)</pre>
log10	Returns the base-10 logarithm of <i>num_value</i>. This function returns a float value. Syntax: <pre>dst_var = log10(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #flog10var = log10(#fvar)</pre>
mod	Returns the fractional remainder, <i>f</i>, of <i>x_value</i>/<i>y_value</i> such that $x\_value = i * y\_value + f$, where <i>i</i> is an integer, <i>f</i> has the same sign as <i>x_value</i>, and the absolute value of <i>f</i> is less than the absolute value of <i>y_value</i>. The arguments are promoted to the type of the greatest precision and the function returns a value of that type. Syntax: <pre>dst_var = mod(x_value, y_value)</pre> <i>x_value</i> = decimal, float, or integer literal, column, variable, or expression. <i>y_value</i> = decimal, float, or integer literal, column, variable, or expression. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #fmodvar = mod(#fxvar, #fyvar)</pre>

Function	Description
power	Returns the value of <i>x_value</i> raised to the power of <i>y_value</i>. This function returns a float value. Syntax: <pre>dst_var = power(x_value, y_value)</pre> <i>x_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>y_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #fpowervar = power(#fxvar, #fyvar)</pre>
rad	Returns a value expressed in radians of <i>num_value</i> which is expressed in degrees. This function returns a float value. Syntax: <pre>dst_var = rad(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>place_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #fradvar = rad(#fvar)</pre>

Function	Description
round	Returns a value that is <i>num_value</i> rounded to <i>place_value</i> digits after the decimal separator. This function returns a value of the same type as <i>num_value</i>. Syntax: <pre>dst_var = round(num_value, place_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. <i>place_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #frndvar = round(#fvar, #fplace) (#x, #y)</pre>
sign	Returns a -1, 0, or +1 depending on the sign of <i>num_value</i>. This function returns a float value. Syntax: <pre>dst_var = sign(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #fsignvar = sign(#fvar)</pre>
sin	Returns the sine of <i>num_value</i>. This function returns a float value. Syntax: <pre>dst_var = sin(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #fsinvar = sin(#fvar)</pre>

Function	Description
sinh	Returns the hyperbolic sine of <i>num_value</i>. This function returns a float value. Syntax: <pre>dst_var = sinh(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #fsinhvar = sinh(#fvar)</pre>
sqrt	Returns the square root of <i>num_value</i>. This function returns a float value. Syntax: <pre>dst_var = sqrt(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #fsqrtvar = sqrt(#fvar)</pre>
tan	Returns the tangent of <i>num_value</i>. This function returns a float value. Syntax: <pre>dst_var = tan(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #ftanvar = tan(#fvar)</pre>

Function	Description
tanh	Returns the hyperbolic tangent of <i>num_value</i>. This function returns a float value. Syntax: <pre>dst_var = tanh(num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #ftanhvar = tanh(#fvar)</pre>
trunc	Returns a value that is <i>num_value</i> truncated to <i>place_value</i> digits after the decimal separator. This function returns a value of the same type as <i>num_value</i>. Syntax: <pre>dst_var = trunc(num_value, place_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. <i>place_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let #ftruncvar = trunc(#fvar, #fplace)</pre>

The transcendental functions sin, cos, tan, sinh, cosh, and tanh take their arguments in radians. The functions asin, acos, and atan return radian values. To convert from radians to degrees or degrees to radians, use the rad or deg functions as follows:

```
let #x = sin(rad(45))           ! Sine of 45 degrees.
let #y = deg(asin(#x))         ! Convert back to degrees.
```

If arguments or intermediate results passed to a numeric function are invalid for that function, SQR halts with an error message.

For example, passing a negative number to the sqrt function causes an error. Use the cond function described in the Miscellaneous Functions table to prevent division by zero or other invalid function or operator argument values.

The following table lists file-related functions. These functions return zero (0) if successful; otherwise, they return the system error code.

Function	Description
delete	Deletes the file <i>filename</i>. The function returns either a zero (0) to indicate success or the value returned from the operating system to indicate an error. Syntax: <pre>stat_var = delete(filename)</pre> <i>filename</i> = text literal, column, variable, or expression. <i>stat_var</i> = decimal, float, or integer variable. Example: <pre>let #fstatus = delete(\$filename)</pre>
exists	Determines if the file, <i>filename</i>, exists. The function returns either a zero (0) to indicate success or the value returned from the operating system to indicate an error. Syntax: <pre>stat_var = exists(filename)</pre> <i>filename</i> = text literal, column, variable, or expression. <i>stat_var</i> = decimal, float, or integer variable. Example: <pre>let #fstatus = exists(\$filename)</pre>
rename	Renames <i>old_filename</i> to <i>new_filename</i>. The function returns either a zero (0) to indicate success or the value returned from the operating system to indicate an error. Syntax: <pre>stat_var = rename(old_filename, new_filename)</pre> <i>old_filename</i> = text literal, column, variable, or expression. <i>new_filename</i> = text literal, column, variable, or expression. <i>stat_var</i> = decimal, float, or integer variable. Example: <pre>let #fstatus = rename(\$old_filename, \$new_filename)</pre>

The following table lists miscellaneous functions. These functions return a string value unless otherwise indicated.

In these functions where a string argument is expected and a date variable, column, or expression is entered, SQR converts the date to a string according to the following rules:

- For DATETIME columns and SQR DATE variables, the format specified by the SQR_DB_DATE_FORMAT setting is used. If this has not been set, the first database-dependent format as listed in the Default Database Formats table is used.

- For DATE columns, the format specified by the SQR_DB_DATE_ONLY_FORMAT setting is used. If this has not been set, the format listed in the DATE Column Formats table is used.
- For TIME columns, the format specified by the SQR_DB_TIME_ONLY_FORMAT setting is used. If this has not been set, the format as listed in the TIME Column Formats table is used.

On the other hand, except where noted in an individual function, if a string variable, column, or expression is entered where a date argument is expected, then the string must be in the format specified by the SQR_DB_DATE_FORMAT setting, one of the database-dependent formats listed in the Default Database Formats table, or the database-independent format 'YYYYMMDD[HH24[MI[SS[NNNNNN]]]]'

Function	Explanation
array	Returns a pointer to the starting address of the specified array field. The value returned from this function can only be used by a user-defined function. See the routine printarray in the file UFUNC.C for complete instructions on how to use this function. Syntax: <pre>array_var = array(array_name, field_name)</pre> <i>array_name</i> = text literal, column, variable, or expression <i>field_name</i> = text literal, column, variable, or expression <i>array_var</i> = text variable Example: <pre>let #fstatus = printarray(array('products', 'name'), 10, 2, 'c')</pre>
ascii	Returns the numeric value for the first character in <i>str_value</i>. This function returns a float value. Syntax: <pre>ascii_var = ascii(str_value)</pre> <i>str_value</i> = date or text literal, column, variable, or expression <i>ascii_var</i> = decimal, float, or integer variable Example: <pre>let #fascii = ascii(\$filename)</pre>
asciic	Returns the numeric value for the first character (rather than byte) of the specified string. Syntax: <pre>ascii_var = asciic(str_value)</pre> <i>str_value</i> = date or text literal, column, variable, or expression <i>ascii_var</i> = decimal, float, or integer variable Example: <pre>let #fascii = asciic(\$filename)</pre>

Function	Explanation
chr	Returns a string that is composed of a character with the numeric value of <i>num_value</i>. Syntax: <pre>dst_var = chr (num_value)</pre> <i>num_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>dst_var</i> = text variable. Example: <pre>let \$svar = chr (#num)</pre>
cond	Returns <i>y_value</i> if the <i>x_value</i> is nonzero (0); otherwise returns <i>z_value</i>. If <i>y_value</i> is numeric, the <i>z_value</i> must also be numeric; otherwise, date and textual arguments are compatible. If either the <i>y_value</i> or <i>z_value</i> is a date variable, column, or expression, a date is returned. The return value of the function depends on which value is returned. Syntax: <pre>dst_var = cond(x_value, y_value, z_value)</pre> <i>x_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>y_value</i> = Any literal, column, variable, or expression <i>z_value</i> = Any literal, column, variable, or expression <i>dst_var</i> = Any variable Example: <pre>let #avg = #total / cond(&rate != 0, &rate, 1)</pre>
dateadd	Returns a date after adding (or subtracting) the specified units to the <i>date_value</i>. Syntax: <pre>date_var = dateadd(date_value, units_value, quantity_value)</pre> <i>date_value</i> = date variable or expression <i>units_value</i> = text literal, column, variable, or expression. Valid units are 'year', 'quarter', 'week', 'month', 'day', 'hour', 'minute', and 'second' <i>quantity_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to float. <i>date_var</i> = date variable Example: <pre>let \$date = dateadd(\$startdate, 'day', 7.5)</pre>

Function	Explanation
datediff	Returns the difference between the specified dates expressed in <i>units_value</i>. The function returns a float value. The result can be negative if the first date is earlier than the second date. Syntax: <pre>dst_var = datediff(date1_value, date2_value, units_value)</pre> <i>date1_value</i> = date variable or expression <i>date2_value</i> = date variable or expression <i>units_value</i> = text literal, column, variable, or expression. Valid units are 'year', 'quarter', 'week', 'month', 'day', 'hour', 'minute', and 'second' <i>dst_var</i> = decimal, float, or integer variable Example: <pre>let #diff = datediff(\$date1, \$date2, 'hour')</pre>
datenow	Returns the current local date and time from the client machine. Syntax: <pre>dst_var = datenow()</pre> <i>dst_var</i> = date variable Example: <pre>let \$date = datenow()</pre>
datetostr	Converts the date <i>date_value</i> to a string in the format <i>format_mask</i>. Syntax: <pre>dst_var = datetostr(date_value [, format_mask])</pre> <i>date_value</i> = date variable or expression <i>format_mask</i> = text literal, column, variable, or expression. The keyword DATE can be used to specify the DATE-EDIT-MASK setting from the current locale. If this argument is not specified, then the format specified by the SQR_DB_DATE_FORMAT setting is used. If this has not been set, then the first database-dependent format listed in the Default Database Formats table is used. <i>dst_var</i> = text variable Example: let \$formdate = datetostr(\$date, 'Day Mon DD, YYYY') let \$localedate = datetostr(\$date, DATE)

Function	Explanation
edit	Formats <i>source_value</i> according to <i>edit_mask</i> and returns a string containing the result. Syntax: <pre>dst_var = edit(source_value, edit_mask)</pre> <i>source_value</i> = Any literal, column, variable, or expression <i>edit_mask</i> = text literal, column, variable, or expression <i>dst_var</i> = text variable Example:) <pre>let \$phone = edit(&phone, '(xxx) xxx-xxxx') let \$price = edit(#price,</pre>
getenv	Returns the value of the specified environment variable. If the environment variable does not exist, an empty string is returned. Syntax: <pre>dst_var = getenv(env_value)</pre> <i>env_value</i> = text literal, column, variable, or expression <i>dst_var</i> = text variable Example: <pre>let \$myuser = getenv('USER')</pre>
instr	Returns the numeric position of <i>sub_value</i> in <i>source_value</i> or zero (0) if not found. The search begins at offset <i>offset_value</i>. This function returns a float value. Syntax: <pre>dst_var = instr(source_value, sub_value, offset_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression <i>sub_value</i> = text literal, column, variable, or expression <i>offset_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to integer. <i>dst_var</i> = decimal, float, or integer variable Example: <pre>let #offset = instr(&description, 'auto', 10)</pre>

Function	Explanation
instrb	Performs the same functionality as the instr function except that the starting point and returned value are expressed in bytes rather than in characters. Syntax: <pre>dst_var = instrb(source_value, sub_value, offset_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression <i>sub_value</i> = text literal, column, variable, or expression <i>offset_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to integer. <i>dst_var</i> = decimal, float, or integer variable Example: <pre>let #offset = instrb(&description, 'auto', 10)</pre>
isblank	Returns a value of one (1) if <i>source_val</i> is an empty string, null string, or composed entirely of whitespace characters; otherwise, returns a value of zero (0). Syntax: <pre>dst_var = isblank(source_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression <i>dst_var</i> = decimal, float, or integer variable Example: <pre>let #blank = isblank(&description)</pre>
isnull	Returns a value of one (1) if <i>source_val</i> is null; otherwise, returns a value of zero (0). Syntax: <pre>dst_var = isnull(source_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression <i>dst_var</i> = decimal, float, or integer variable Example: <pre>let #null = isnull(\$date)</pre>

Function	Explanation
length	Returns the number of characters in <i>source_value</i>. Syntax: <pre>dst_var = length(source_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression <i>dst_var</i> = decimal, float, or integer variable Example: <pre>let #length = length(&description)</pre> Note. PeopleSoft recommends that you use either the lengthp or lengtht function instead of the length function.
lengthb	(Multibyte versions of SQR only.) Has the same functionality as the length function except that the return value is expressed in bytes, rather than in characters. Syntax: <pre>dst_var = lengthb(source_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression <i>dst_var</i> = decimal, float, or integer variable Example: <pre>let #length = lengthb(&description)</pre> Note. PeopleSoft recommends that you use either the lengthp or lengtht function instead of the lengthb function.
lengthp	Returns the length of a given string in print positions. Syntax: <pre>dst_var = lengthp(source_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression <i>dst_var</i> = decimal, float, or integer variable Example: <pre>let #printlen = lengthp(&string)</pre>

Function	Explanation
lengtht	Returns the length of a given string in bytes when converted (transformed) to a specified encoding. Syntax: <pre>dst_var = lengtht(source_value, encoding_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression <i>encoding_value</i> = text literal, column, variable, or expression. <i>dst_var</i> = decimal, float, or integer variable Example: <pre>let #sjislen = lengtht(\$string, 'Shift-JIS')</pre>
lower	Converts the contents of <i>source_value</i> to lowercase and returns the result. Syntax: <pre>dst_var = lower(source_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression <i>dst_var</i> = text variable Example: <pre>let \$lower = lower(&description)</pre>
lpad	Pads the <i>source_value</i> on the left to a length of <i>length_value</i> using <i>pad_value</i> and returns the result. Syntax: <pre>dst_var = lpad(source_value, length_value, pad_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression <i>length_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to integer. <i>pad_value</i> = text literal, column, variable, or expression <i>dst_var</i> = text variable Example: <pre>let \$lpad = lpad(\$notice, 25, '.'</pre>

Function	Explanation
ltrim	Trims characters in <i>source_value</i> from the left until a character is not in <i>set_value</i> and returns the result. Syntax: <pre>dst_var = ltrim(source_value, set_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression <i>set_value</i> = text literal, column, variable, or expression <i>dst_var</i> = text variable Example: <pre>let \$ltrim = ltrim(&description, '.')</pre>
nvl	Returns <i>y_value</i> if the <i>x_value</i> is null; otherwise, returns <i>x_value</i>. If <i>x_value</i> is numeric, <i>y_value</i> must also be numeric; otherwise, date and textual arguments are compatible. In any case, the <i>x_value</i> determines the type of expression returned. The return value of the function depends on which value is returned. Syntax: <pre>dst_var = nvl(x_value, y_value)</pre> <i>x_value</i> = Any literal, column, variable, or expression <i>y_value</i> = Any literal, column, variable, or expression <i>dst_var</i> = Any variable Example: <pre>let \$city = nvl(&city, '-- not city --')</pre> If <i>x_value</i> is a date and <i>y_value</i> is textual, then <i>y_value</i> is validated according to the following rules: For DATETIME columns and SQR DATE variables, the format specified by the SQR_DB_DATE_FORMAT setting, one of the database-dependent formats (see the Default Database Formats table), or the database-independent format 'SYYYMDD[HH24[MI[SS[NNNNN]]]]' is used. For DATE columns, the format specified by the SQR_DB_DATE_ONLY_FORMAT setting, or the format listed in the DATE Column Formats table is used. For TIME columns, the format specified by the SQR_DB_TIME_ONLY_FORMAT setting, or the format as listed in the TIME Column Formats table is used.

Function	Explanation
range	Returns a value of one (1) if <i>x_value</i> is between <i>y_value</i> and <i>z_value</i>; otherwise, returns a value of zero (0). If the first argument is text or numeric, the other arguments must be of the same type. If the first argument is a date, the remaining arguments can be dates and/or text. It is also possible to perform a date comparison on a mix of date and text arguments, for example, where <i>x_value</i> is a date and <i>y_value</i> and <i>z_value</i> are text arguments. In a comparison of this sort, <i>y_value</i> must represent a date that is earlier than that of <i>z_value</i>. Syntax: <pre>dst_var = range(x_value, y_value, z_value)</pre> <i>x_value</i> = Any literal, column, variable, or expression <i>y_value</i> = Any literal, column, variable, or expression <i>z_value</i> = Any literal, column, variable, or expression <i>dst_var</i> = decimal, float, or integer variable Example: <pre>let #inrange = range(&grade, 'A', 'D') let #inrange = range(\$date, \$startdat</pre> If <i>x_value</i> is a date and <i>y_value</i> and/or <i>z_value</i> is textual, then <i>y_value</i> and/or <i>z_value</i> is validated according to the following rules: For DATETIME columns and SQR DATE variables, the format specified by the SQR_DB_DATE_FORMAT setting, one of the database-dependent formats (see the Default Database Formats table), or the database-independent format 'SYYYMM-MDD[HH24[MI[SS[NNNNNN]]]]' is used. For DATE columns, the format specified by the SQR_DB_DATE_ONLY_FORMAT setting, or the format listed in the table DATE Column Formats is used. For TIME columns, the format specified by the SQR_DB_TIME_ONLY_FORMAT setting, or the format as listed in table TIME Column Formats is used.
replace	Inspects the contents of <i>source_value</i> and replaces all occurrences of <i>from_string</i> with <i>to_string</i> and returns the modified string. Syntax: <pre>dst_var = replace(source_value, from_string, to_string)</pre> <i>source_value</i> = date or text literal, column, variable, or expression <i>from_string</i> = text literal, column, variable, or expression <i>to_string</i> = text literal, column, variable, or expression <i>dst_var</i> = text variable Example: <pre>let \$replaced = replace(\$paragraph, 'good', 'excellent')</pre>

Function	Explanation
roman	Returns a string that is the character representation of <i>source_value</i> expressed in lowercase roman numerals. Syntax: <pre>dst_var = roman(source_value)</pre> <i>source_value</i> = text literal, column, variable, or expression. <i>dst_var</i> = text variable Example: <pre>let \$roman = roman(#page-count)</pre>
rpadd	Pads the <i>source_value</i> on the right to a length of <i>length_value</i> using <i>pad_value</i> and returns the result. Syntax: <pre>dst_var = rpadd(source_value, length_value, pad_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression <i>length_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to integer. <i>pad_value</i> = text literal, column, variable, or expression <i>dst_var</i> = text variable Example: <pre>let \$rpadd = rpadd(\$notice, 25, '.')</pre>
rtrim	Trims characters in <i>source_value</i> from the right until a character is not in <i>set_value</i> and returns the result. Syntax: <pre>dst_var = rtrim(source_value, set_value)</pre> <i>source_value</i> = date, or text literal, column, variable, or expression <i>set_value</i> = text literal, column, variable, or expression <i>dst_var</i> = text variable Example: <pre>let \$rtrim = rtrim(&description, '.')</pre>

Function	Explanation
strtodate	Converts the string <i>source_value</i> in the format <i>format_mask</i> to a date type. Syntax: <pre>dst_var = strtodate(source_value [, format_mask])</pre> <i>source_value</i> = text literal, column, variable, or expression <i>format_mask</i> = text literal, column, variable, or expression that describes the exact format of the <i>source_value</i>. The keyword DATE can be used to specify the DATE-EDIT-MASK setting from the current locale. If this argument is not specified, then <i>source_value</i> must be in the format specified by the SQR_DB_DATE_FORMAT setting, one of the database-dependent formats (see the Default Database Formats table), or the database-independent format 'SYYYMDD[HH24[MI[SS[NNNNNN]]]]'. Valid format codes are specified in the Date Edit Format Codes table. <i>dst_var</i> = date variable Example: let \$date = strtodate(\$str_date, 'Mon DD, YYYY') let \$date = strtodate(\$str_date, DATE)
substr	Extracts the specified portion <i>source_value</i>. The extraction begins at <i>offset_value</i> (origin is 1) for a length of <i>length_value</i> characters. Syntax: <pre>dst_var = substr(source_value, offset_value, length_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression. <i>offset_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to integer. <i>length_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to integer. <i>dst_var</i> = text variable. Example: <pre>let \$piece = substr(&record, 10, #len)</pre> Note. PeopleSoft recommends that you use either the substrp or substrt function instead of the substr function.

Function	Explanation
substrb	Has the same functionality as the substr function except that the starting point and length are expressed in bytes, rather than in characters. Syntax: <pre>dst_var = substrb(source_value, offset_value, length_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression. <i>offset_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to integer. <i>length_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to integer. <i>dst_var</i> = text variable. Example: <pre>let \$piece = substrb(&record, 10, #len)</pre> Note. PeopleSoft recommends that you use either the substr or substr function instead of the substrb function.
substrp	Returns a substring of a given string starting at a specified print position into the string and of a specified print length. Syntax: <pre>dst_var = substrp(source_value, offset_value, length_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression. <i>offset_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to integer. <i>length_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to integer. <i>dst_var</i> = decimal, float, or integer variable. Example: <pre>let \$sub = substrp(&string, #printpos, #printlen)</pre>

Function	Explanation
substrt	Returns a substring of a given string starting at a specified byte and byte length in a given encoding. Syntax: <pre>dst_var = substrt(source_value, offset_value, length_value, encoding_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression. <i>offset_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to integer. <i>length_value</i> = decimal, float, or integer literal, column, variable, or expression. The value is always converted to integer. <i>encoding_value</i> = text literal, column, variable, or expression. <i>dst_var</i> = text variable. Example: <pre>let \$sjisPrep = substrt(&string, 1, 10, 'Shift-JIS')</pre>
to_char	Converts <i>source_value</i> to a string, using maximum precision. Syntax: <pre>dst_var = to_char(source_value)</pre> <i>source_value</i> = decimal, float, or integer literal, column, variable, or expression <i>dst_var</i> = text variable Example: <pre>let \$string = to_char(#number)</pre>
to_multi_byte	Converts the specified string as follows: Any occurrence of a double-byte character that also has a single-byte representation (numerals, punctuation, roman characters, and katakana) is converted. Syntax: <pre>dst_var = to_multi_byte(source_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression Example: <pre>let \$multi = to_multi_byte(&text)</pre>

Function	Explanation
to_number	Converts <i>source_value</i> to a number. This function returns a float value. Syntax: <pre>dst_var = to_number(source_value)</pre> <i>source_value</i> = decimal, float, or integer literal, column, variable, or expression <i>dst_var</i> = decimal, float, or integer variable Example: <pre>let #value = to_number(\$number)</pre>
to_single_byte	Converts the specified string as follows: For SJIS, EBCDIC290, and EBCDIC1027, any occurrence of a single-byte character that also has a multi-byte representation (numerals, punctuation, roman characters, and katakana) is converted. This function also converts a sequence of kana characters followed by certain grammatical marks into a single-byte character that combines the two elements. For all other encodings, the string is not modified. Syntax: <pre>dst_var = to_single_byte(source_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression Example: <pre>let \$single = to_single_byte (&text)</pre>
translate	Inspects the contents of <i>source_value</i> and converts characters that match those in <i>from_set</i> to the corresponding character in <i>to_set</i> and returns the translated string. Syntax: <pre>dst_var = translate(source_value, from_set, to_set)</pre> <i>source_value</i> = date or text literal, column, variable, or expression <i>from_set</i> = text literal, column, variable, or expression <i>to_set</i> = text literal, column, variable, or expression <i>dst_var</i> = text variable Example: <pre>let \$translated = translate(edit(&price, '999,999.99'), ',','.',',','')</pre>

Function	Explanation
transform	Returns a Unicode string which is a specified transform of a given string. Syntax: <pre><i>dst_var</i> = transform(<i>source_value</i>, transform_value)</pre> <i>source_value</i> = date or text literal, column, variable or expression <i>transform_value</i> = text literal, column, variable, or expression <i>dst_var</i> = text variable Example: <pre>let \$hiragana = transform(\$string, 'ToHiragana')</pre>
unicode	Returns a Unicode string from the string of hexadecimal values provided. Syntax: <pre><i>dst_var</i> = unicode(<i>source_value</i>)</pre> <i>source_value</i> = text literal, column, variable or expression <i>dst_var</i> = text variable Example: <pre>let \$uniStr = unicode('u+5e73 u+2294')</pre>

Function	Explanation
upper	Converts the contents of <i>source_value</i> to uppercase and returns the result. Syntax: <pre>dst_var = upper(source_value)</pre> <i>source_value</i> = date or text literal, column, variable, or expression <i>dst_var</i> = text variable Example: <pre>let \$upper = upper(&description)</pre>
wrapdepth	Returns the number of print lines required by <i>source_value</i>. See the PRINTWRAP command for detailed descriptions of the parameters to this function. This function returns a float value. Syntax: <pre>dst_var = wrapdepth(source_value, wrap_width, line_height, on, strip)</pre> <i>source_value</i> = text literal, column, variable, or expression <i>wrap_width</i> = decimal, float, or integer literal, column, variable, or expression <i>line_height</i> = decimal, float, or integer literal, column, variable, or expression <i>on</i> = text literal, column, variable, or expression. <i>strip</i> = text literal, column, variable, or expression <i>dst_var</i> = decimal, float, or integer variable Example: <pre>let #depth = wrapdepth(&description, 40, 1, '<13>', '')</pre>

Writing Custom Functions

In addition to using the preceding built-in functions, you can write your own functions in C, using the supplied source file UFUNC.C.

You can pass any number of arguments to your function and values can be returned by the function or passed back in variables.

After editing and recompiling UFUNC.C, you must relink SQR.

The following is a step-by-step example of how to add a user-defined function to SQR so that it can be invoked using the LET, IF, or WHILE command.

The example adds the C function random, which returns a random number. The function accepts a parameter that is used as the seed to start a new sequence of numbers. If the seed is zero, then the same sequence is used.

When adding functions to UFUNC, keep in mind the following considerations:

- String functions require the following arguments:

- (int) Number of arguments.
- (char *) or (double *) Array of argument pointers, to either char[] or double.
- (char *) Address for result string. If unchanged, function returns a NULL string.
- (int) Maximum length of result string, in bytes.
- Numeric functions require the following arguments:
 - (int) Number of arguments.
 - (char *) or (double *) Array of argument pointers, to either char[] or double.
 - (double *) Address for result numeric value. If unchanged, function returns zero.

To add the random function to SQR, add the following modifications to the UFUNC.C file that was provided with SQR:

- Add the prototype for the random function: static void random CC_ARGS((char *, char *));
- Add the function name to the declaration list. The name of the function called from SQR is random. The return type is *n* for numeric. The number of arguments passed is 1, and the argument type is *n* for numeric. The function name in UFUNC.C is random. The characters PVR must be entered before the function name.

Name	Return_type	Number of Arguments	Arg_Types	Function
"max",	'n',	0,	"n",	PVR max,
"max",	'n',	0,	"n",	PVR max,
"split",	'n',	0,	"C",	PVR split,
"printarray",	'n',	4,	"cnnc",	PVR printarray,
"random",	'n',	1,	"n",	PVR random,

```
/* Last entry must be NULL -- do not change */
"", '\0', 0, "", 0
};
```

At the end the of UFUNC.C file, add the following random routine. The routine name must be lowercase; however, in your SQR program it can be referenced in either uppercase or lowercase.

```
static void random CC_ARGL((argc, argv, result))
CC_ARG(int, argc)          /* The number arguments passed */
CC_ARG(double *, argv[])   /* The argument list */
CC_LARG(double *, result)  /* Where to store result */
{
  if (*argv[0] != 0)
    srand(*argv[0]);
  *result = rand();
}
```



```

return;
}

```

After these modifications, recompile UFUNC.C and relink SQR. See the programmer's reference manual for details about your particular machine.

Here is a simple SQR program that uses the random function:

```

begin-program
  do get-random-number
  do process-calculations
end-program

begin-procedure
  let #seed = 44
  let #ran = random(#seed)
end-procedure

begin-procedure process-calculations
.
.
.

```

Example

The following examples show some complex expressions:

```

let #j = ((#a + #b) * #c) ^ 2
if #j > 2 and sqrt(#j) < 20 or #i + 2 > 17.4
while upper(substr(&descrip,1,#j+2)) != 'XXXX'

and not isnull(&price)
let #len = length(&fname || &initial || &lname) + 2
let $s = edit(&price * &rate, '99999.99')
let summary.total(#j) = summary.total(#j) + (&price * &rate)
if summary.total(#j) > 1000000
let store.total (#store_id, #dept)

    = store.total (#store_id, #dept) + #total
let #diff = datediff(datenow(), strtodate('1995','YYYY'),'day')
let $newdate = dateadd(datenow(),'month',50)
let $date1 = datetostr(strtodate(&sale_date), 'Day Month DD, YYYY')

```

SQR analyzes LET, IF, and WHILE expressions when it compiles your code and saves the result in an internal format so that repetitive execution is at maximum speed.

LOAD-LOOKUP

Syntax

In the SETUP section:

```

LOAD-LOOKUP
NAME=lookup_table_name
TABLE=database_table_name
KEY=key_column_name
RETURN_VALUE=return_column_name
[ROWS=initial_row_estimate_int_lit]
[EXTENT=size_to_grow_by_int_lit]
[WHERE=where_clause_txt_lit]
[SORT=sort_mode]
[QUIET]
[SCHEMA=schema_name]
[PROCEDURE=procedure_name]
[COMMAND=command_string]
[GETDATA=getdata_string]
[PARAMETERS=(...)]
[FROM-ROWSET=(m,n,-n,m-,all)]
[FROM-PARAMETER=rowset_name]

```

In the body of the report:

```

LOAD-LOOKUP
NAME=lookup_table_name
TABLE=database_table_name
KEY=key_column_name
RETURN_VALUE=return_column_name
[ROWS=initial_row_estimate_lit|_var|_col]
[EXTENT=size_to_grow_by_lit|_var|_col]
[WHERE=where_clause_txt_lit|_var|_col]
[SORT=sort_mode]
[QUIET]
[SCHEMA=schema_name]
[PROCEDURE=procedure_name]
[COMMAND=command_string]
[GETDATA=getdata_string]
[PARAMETERS=(...)]
[FROM-ROWSET=(m,n,-n,m-,all)]
[FROM-PARAMETER=rowset_name]

```

Description

Loads an internal table with columns from the database. Enables a quick search using the LOOKUP command.

Use the LOAD-LOOKUP command in conjunction with one or more LOOKUP commands.

LOAD-LOOKUP retrieves two columns from the database, the KEY field and the RETURN_VALUE field. Rows are ordered by KEY and stored in an array.

LOAD-LOOKUP commands specified in the SETUP section are always loaded and cannot reference variables for the ROWS, EXTENT, and WHERE arguments.

When you use the LOOKUP command SQR searches the array (with a binary search) to find the RETURN_VALUE corresponding to the KEY referenced in the lookup.

Usually this type of lookup can be done with a database join, but joins take substantially longer. However, if your report is small and the number of rows to be joined is small, a lookup table cannot be warranted, and in fact can be slower, because the entire table has to be loaded and sorted for each report run.

By default, SQR lets the database sort the data. This works fine if the database and SQR both use the same character set and collating sequence. The SORT argument enables you to specify the sorting method if this is not true. Additionally, if the machine that SQR is running on is faster than the machine the database is running on, letting SQR perform the sort could decrease the execution time of the report.

The only limit to the size of a lookup table is the amount of memory your computer has available. You could conceivably load an array with many thousands of rows. The binary search is performed quickly regardless of how many rows are loaded.

Except for the amount of available memory, there is no limit to the number of lookup tables that can be defined.

Parameters

Parameter	Description
NAME	The name of the lookup table. The array name is referenced in the LOOKUP command.
TABLE	The name of the table in the database, where the KEY and RETURN_VALUE columns or expressions are stored.
KEY	The name of the column that is used as the key in the array that is used for looking up the information. Keys can be character, date, or numeric data types. If numeric, SQR permits only integers 12 digits or less for the KEY column. Keys can be any database-supported expression. See the RETURN_VALUE argument, next.
RETURN_VALUE	The name of the column (expression) that is returned for each corresponding key. The following example is for ORACLE. See your database manual for the correct syntax. RETURN_VALUE='name '"-' country '"-' population'
ROWS	The initial size of the lookup table. This argument is optional, and if not specified, a value of 100 is used.
EXTENT	The amount to increase the array when it becomes full. This argument is optional, and if not specified, a value of 25% of the ROWS value is used.
WHERE	A WHERE clause used to select a subset of all the rows in the table. If specified, the selection begins after the word WHERE. The WHERE clause is limited to 255 characters.
SORT	The sorting method to be used. The following values are permitted: DC—Database sorts data, case-sensitive sort DI—Database sorts data, case-insensitive sort SC—SQR sorts data, case-sensitive sort SI—SQR sorts data, case-insensitive sort The default is SC or the method specified by the -LL command-line flag. The DI method is applicable only to databases that provide this feature and have been installed in that manner.
QUIET	Suppresses the message Loading lookup array... when the command executes. The warning message stating the number of duplicate keys found is also suppressed.

Example

The following command loads the array, states, with the columns abbr and name from the database table stateabbrs, where country is USA.

```
load-lookup

name=states

rows=50

table=stateabbrs

key=abbr

return_value=name

where=country='USA'
```

The preceding array is used in the example for the LOOKUP command to retrieve the full text of a state name from the abbreviation.

The following example uses the LOOKUP command to validate data entered by a user using an INPUT command:

```
get_state:
input $state 'Enter state abbreviation'
uppercase $state
lookup states $state $name
if $name = ''           ! Lookup didn't find a match
  show 'No such state.'
  goto get_state
end-if
```

Surround any command argument with embedded spaces by single quotes, as shown in the following example:

```
where='country=''USA'' and region = ''NE'''
```

The entire WHERE clause is surrounded by quotes. The two single quotes around USA and NE are translated to one single quote in the SQL statement.

The following example uses joins in a LOAD-LOOKUP command by including two tables in TABLE and the join in WHERE:

```
load-lookup

name=states

rows=50

sort=sc

table='stateabbrs s, regions r'
```

```

key=abbr

return_value=name

where='s.abbr = r.abbr and r.location = ''ne'''

```

LOOKUP

Syntax

```

LOOKUP lookup_table_name{key_any_lit|_var|_col}
{ret_txt_var|_date_var}

```

Description

Searches a lookup table (an array) for a key value and returns the corresponding text string.

Speeds up processing for long reports. For example, if you want to print the entire state name rather than the abbreviation, you could use LOAD-LOOKUP and then LOOKUP to do this.

Parameters

Parameter	Description
lookup_table_name	Specifies the lookup table. This table must be previously loaded with a LOAD-LOOKUP command.
key_any_lit _var _col	The key used for the lookup.
ret_txt_var _date_var	A string variable into which the corresponding value is returned.

Example

The following example works in conjunction with the example for the LOAD-LOOKUP command:

```
lookup states &state_abbr $state_name
```

This example searches the states lookup table for a matching *&state_abbr* value; if found, it returns the corresponding state name in *\$state_name*. If not found, a null is placed in *\$state_name*.

See Also

The LOAD-LOOKUP command.

LOWERCASE

Syntax

```

LOWERCASE txt_var

```

Description

Converts the contents of a text variable to lowercase.

Parameters

Parameter	Description
txt_var	Specifies a text variable to be converted to lowercase.

Example

```
input $answer 'Type EXIT to stop'
lowercase $answer      ! Allows user to enter
                        ! upper or lowercase.

if $answer = 'exit'
...etc...
```

See Also

The lower function listed in the Miscellaneous Functions table.

MBTOSBS

Syntax

MBTOSBS {*txt_var*}

Description

Converts a double-byte string to its single-byte equivalent.

This command converts the specified string as follows: Any occurrence of a double-byte character that also has a single-byte representation (numerals, punctuation, roman characters, and katakana) is converted.

Parameters

Parameter	Description
txt_var	Specifies the string to be converted.

See Also

The TO_SINGLE_BYTE function of the LET command.

MOVE

Syntax

```
MOVE {src_any_lit|_var|_col} TO dst_any_var
[[:$]format_mask|NUMBER|MONEY|DATE]
```

Description

Moves the source field to the destination field. Optionally, you can reformat the field using the *format_mask* argument. Source and destination fields can be different types, numeric, text, or date. MOVE is also useful for converting from one type to another; however, date and numeric variables are incompatible.

When a date variable or column is moved to a string variable, the date is converted according to the following rules:

- For DATETIME columns and SQR DATE variables, the format specified by the SQR_DB_DATE_FORMAT setting is used. If this has not been set, the first database-dependent format as listed in the Default Database Formats table is used.
- For DATE columns, the format specified by the SQR_DB_DATE_ONLY_FORMAT setting is used. If this has not been set, the format listed in the DATE Column Formats table is used.
- For TIME columns, the format specified by the SQR_DB_TIME_ONLY_FORMAT setting is used. If this has not been set, the format as listed in the TIME Column Formats table is used.

Finally, as this example shows, the edit mask can be contained in a string variable.

Parameters

Parameter	Description
src_any_lit _var _col	Specifies any source column, variable, or literal. Note that a date can be stored in a date variable or column, or a string literal, column, or variable. When using a date format_mask or the keyword DATE with the MOVE command, the source, if a string literal, column, or variable, must be in the format specified by the SQR_DB_DATE_FORMAT setting, one of the database-dependent formats as listed in the Default Database Formats table, or the database-independent format 'SYYYYMMDD[HH24[MI[SS[NNNNNN]]]]'.
dst_any_var	Specifies a destination variable.
format_mask	Specifies an optional format mask. For additional information regarding edit masks, see the command, PRINT.
NUMBER	Indicates that src_any_lit _var _col is to be formatted using the NUMBER-EDIT-MASK from the current locale. This option is not legal with date variables. (See the command ALTER_LOCALE.)
MONEY	Indicates that src_any_lit _var _col is to be formatted using the MONEY-EDIT-MASK from the current locale. This option is not legal with date variables. (See the command, ALTER_LOCALE.)
DATE	Indicates that src_any_lit _var _col is to be formatted using the DATE-EDIT-MASK from the current locale. This option is not legal with numeric variables. (See the command, ALTER_LOCALE.)

Example

The following example illustrates the various features of the MOVE command:

```
!
! Convert a string in place
!
move '123456789' to $ssn
move $ssn to $ssn xxx-xx-xxxx
show '$SSN = ' $ssn
```

Produces the following output:

```
$SSN = 123-45-6789
```

```
!
```

```

! Convert a number to a string using an edit mask
!
move 1234567.89 to #value
move #value to $value 999,999,999.99
show '$Value = ' $value

```

Produces the following output:

```
$Value = 1,234,567.89
```

```

!
! Convert a number to a string using a variable edit mask
!
move 123 to #counter
move '099999' to $mask
move #counter to $counter :$mask
show '$Counter = ' $counter

```

Produces the following output:

```
$Counter = 000123
```

```

!
! Convert a number to a string using the default edit mask
!
! SQR, by default, outputs six digits of precision.
! If you require more or less precision, specify an edit mask.
!
move 123.78 to #defvar
move #defvar to $defvar
show '$DefVar = ' $defvar

```

Produces the following output:

```
$DefVar = 123.780000
```

```

!
! Convert the number to a string using the locale default
! numeric edit mask
!
alter-locale number-edit-mask = '99,999,999.99'
move 123456.78 to #nvar
move #nvar to $nvar number
show '$NVar = ' $nvar

```

Produces the following output:

```
$NVar = 123,456.78
```

```

!
! Convert the money value to a string using the locale default

```



```

! money edit mask
!
alter-locale money-edit-mask = '$9,999,999.99'
move 123456.78 to #mvar
move #mvar to $mvar money
show '$MVar = ' $mvar

```

Produces the following output:

```
$MVar = $ 123,456.78
```

```

!
! Convert the date column to a string using the locale default
! date edit mask
!
begin-select
dcol
  from tables
end-select
alter-locale date-edit-mask = 'Mon-DD-YYYY'
move &dcol to $dvar date
show '$DVar = ' $dvar

```

Produces the following output:

```
$DVar = Jan-01-2004
```

```

!
! Reset date to first day of the month
! ($date1 and $date2 have been defined as date variables)
!
let $date1 = datenow()
move $date1 to $date2 'MMYYYY'
show '$Date2 = ' $date2 edit 'MM/DD/YY HH:MI'

```

Produces the following output if the report was run in October of 2004.

```
$Date2 = 10/01/04 00:00
```

```

!
! Convert date to a string
! ($date1 has been defined as a date variable)
!
move $date1 to $str_date 'DD-MON-YYYY'
show '$Str_Date = ' $str_date

```

Produces the following output.

```
$Str_Date = 01-DEC-2004
```

```
!
```

```

! Convert string (in partial format of SYYYYMMDDHHMISSNNN) to a
! date
!
move '20041129' to $date1
show '$Date1 = ' $date1 edit 'Mon DD YYYY HH:MI'

```

Produces the following output.

```
$Date1 = Nov 29 2004 00:00
```

See Also

The LET command for information about copying, editing, or converting fields.

The EDIT parameter of the PRINT command for a description of the edit masks.

The ALTER-LOCALE command for a description of the arguments NUMBER-EDIT-MASK, MONEY-EDIT-MASK, and DATE-EDIT-MASK.

The PRINT command regarding the default date-time components as a result of moving an incomplete date to a date variable.

MULTIPLY

Syntax

```
MULTIPLY {src_num_lit|_var|_col} TIMES dst_num_var
[ROUND=nn]
```

Description

Multiplies the first field by the second and places the result into the second field.

When dealing with money-related values (dollars and cents), use decimal variables rather than float variables. Float variables are stored as double precision floating point numbers, and small inaccuracies can appear when multiplying many numbers in succession. These inaccuracies can appear due to the way different hardware and software implementations represent floating point numbers.

Parameters

Parameter	Description
src_num_lit _var _col	Specifies a numeric source column, variable, or literal.
dst_num_var	Specifies a destination numeric variable.
ROUND	Rounds the result to the specified number of digits to the right of the decimal point. For float variables, this value can be from 0 to 15. For decimal variables, this value can be from 0 to the precision of the variable. For integer variables, this argument is not appropriate.

Example

```

multiply &quantity times #cost
multiply 1.5 times #result

```

See Also

The ADD command for more information.

The LET command for a discussion of complex arithmetic expressions.

NEW-PAGE

Syntax

```
NEW-PAGE [erase_from_line_num_lit|_var|_col]
```

Description

Writes the current page and begins a new one.

For line printers, this command can optionally erase the old page starting at a specified line. After this action is performed, the location on the page is unchanged—that is, the value of #current-line is the same. The default action is to erase the entire page and reset #current-line to its initial value for the page.

In reports where an overflow page is needed, sometimes it is useful to retain information from the first page on succeeding pages.

Each NEW-PAGE occurrence adds a form feed character to the output file unless you specify FORMFEED=NO in the DECLARE-LAYOUT for this program in the SETUP section.

Note. A NEW-PAGE automatically occurs if page overflow is detected. Tabular reports do not require explicit NEW-PAGE commands; use NEXT-LISTING instead.

Parameters

Parameter	Description
erase_from_line_num_lit _var _col	Specifies a numeric column, variable, or literal for line printers.

Example

```
! Write current page, then erase it
! beginning at line 5.
new-page 5
```

NEW-REPORT

Syntax

```
NEW-REPORT {report_filename_txt_lit|_var|_col}
```

Description

Closes the current report output file and opens a new one with the specified file name.

This command is normally used with single reports only. When used with multiple report declarations, this command affects the *current* report only.

The internal page counter is reset to 1 when NEW-REPORT is executed.

Note. SQR does not create a report output file until the first page is completed. It is possible that NEW-REPORT will not create a new file, for example, if no data is selected and nothing is printed on the page.

Parameters

Parameter	Description
{report_filename_txt_lit _var _col}	Specifies a new file name.

Example

The following example shows the NEW-REPORT command:

```
new-report 'rep2a.lis'
new-report $next-file
```

Assign the report file name within an SQR report by issuing the NEW-REPORT command before printing. You might even prompt for the file name to use, as shown in the following example:

```
begin-report
  input $file 'Enter report file name'
  new-report $file
  ...
```

After execution of this command, the reserved variable *\$sqr-report* is updated to reflect the new report name.

See Also

The DECLARE-REPORT and USE-REPORT commands.
The -F command-line flag.

NEXT-COLUMN

Syntax

```
NEXT-COLUMN [AT-END={NEWLINE|NEWPAGE}]
[GOTO-TOP={num_lit|_var|_col}]
[ERASE-PAGE={num_lit|_var|_col}]
```

Description

Sets the current position on the page to the next column defined with the COLUMNS command.

Parameters

Parameter	Description
AT-END	Takes effect if the current column is the last one defined when NEXT-COLUMN is invoked.
GOTO-TOP	Causes the current line in the next column to be num_lit _var _col. This argument is useful when printing columns down the page.
ERASE-PAGE	Specifies where to begin erasing the page when an AT-END=NEWPAGE occurs.

Example

The following example prints columns across the page:

```

columns 10 50                                ! Define two columns
begin-select
name    (0,1,20)
phone   (0,+3,0) edit (xxx)bx-xxx
    next-column at-end=newline                ! Print names
                                              ! across the page
from phonelist                               ! within two columns.
order by name
end-select

```

The following example prints columns down the page:

```

columns 10 50
move 55 to #bottom_line
begin-select
name    (0,1,20)
phone   (0,+3,0) edit (xxx)bx-xxx
    if #current-line >= #bottom_line
        next-column goto-top=1 at-end=newpage
    else
        position (+1,1)
    end-if
from phonelist
order by name
end-select

```

See Also

The COLUMNS and USE-COLUMN commands.

NEXT-LISTING

Syntax

```

NEXT-LISTING[NO-ADVANCE]
[SKIPLINES={num_lit|_var|_col}]
[NEED={num_lit|_var|_col}]

```

Description

Ends the current set of detail lines and begins another.

NEXT-LISTING is used in tabular reports. This command causes a new vertical offset in the page to begin.

After NEXT-LISTING is executed, line 1 is reset one line below the deepest line previously printed in the page body. That is, if you then write PRINT (1, 5), the string is printed on the next available line starting in column 5. Note that the SQR reserved variable #current-line still reflects the actual line number within the page body.

The value of SKIPLINES must be a nonnegative integer. If it is less than 0, then 0 is assumed.

The value of NEED must be an integer greater than 0. If it is less than or equal to 0, then 1 is assumed.

Parameters

Parameter	Description
NO-ADVANCE	Suppresses any line movement when no printing has occurred since the previous NEXT-LISTING or NEW-PAGE. The default increments the line position even when nothing was printed.
SKIPLINES	Causes the specified number of lines to be skipped before setting up the new offset.
NEED	Specifies the minimum number of lines needed to begin a new listing or set of detail lines. If this number of lines does not exist, a new page is started. You can use NEED to prevent a group of detail lines from being broken across two pages.

Example

```

begin-select
cust_num  (1,1)      edit 099999      ! Each detail group prints
city      (,+3)      ! starting on line 1 since
name      (2,10,30)   ! NEXT-LISTING keeps
address   (,+2)      ! moving line 1 down the
    next-listing  skiplines=1  need=2  ! page. NEED=2 keeps 2
from customers order by cust_num      ! line detail groups from
end-select            ! breaking across pages.
```

Note. The NEXT-LISTING command automatically issues a Use-Column 1 command if columns are active.

OPEN

Syntax

```

OPEN {filename_lit|_var|_col} AS
{filenum_num_lit|_var|_col}
{FOR-READING|FOR-WRITING|FOR-APPEND}
{RECORD=length_num_lit[:FIXED|:FIXED_NOLF|:VARY]}
[STATUS=num_var]
```

Description

Opens an operating system file for reading or writing. After a file is opened, it remains open until explicitly closed by the CLOSE command. A maximum of 256 files can be opened at one time.

Parameters

Parameter	Description
{filename_lit _var _col}	Specifies the file name. The file name can be literal, variable, or column. This makes it easy to prompt for a file name at runtime.
{filenum_num_lit _var _col}	Specifies a number that identifies the file in the application. All file commands use the file number to reference the file. File numbers can be numeric variables and literals. The number can be any positive integer less than 64,000.
FOR-READING	When a file is opened for reading, SQR procures all data sequentially. SQR does not allow for random access of information.
FOR-WRITING	When a file is opened for writing, a new file is created. If a file of the same name already exists, it can be overwritten (this depends on the operating system).
FOR-APPEND	When a file is opened in append mode, the current file contents are preserved. All data written is placed at the end of the file. SQR creates the file if one does not already exist. For existing files, make sure the attributes used are the same as those used when the file was created. Failure to do this can produce unpredictable results.
RECORD	For the VARY file type, this is the maximum size for a record. For the FIXED file type, this is the size of each record without the line terminator. For the FIXED_NOLF file type, this is the size of each record.
FIXED	This file type assumes that all records contained within the file are the same length. Terminate each record by a line terminator (system dependent). You can use this file type when writing or reading binary data.
FIXED_NOLF	This file type specifies that all records contained within the file are the same length with no line terminators. When writing records, SQR pads short records with blank characters to ensure each record is the same length. This file type can be used when writing or reading binary data.
VARY	This file type specifies that the records can be of varying length. Each record is terminated by a line terminator (system-dependent). Only records containing display characters (no binary data) can be used safely. When reading records, any data beyond the maximum length specified is ignored. This is the default file type.
STATUS	Sets the numeric variable to zero if the OPEN succeeds and to -1 if it fails. Without the STATUS argument, a failure on OPEN causes SQR to halt. By using a STATUS variable, you can control what processing should occur when a file cannot be opened.

Example

This section contains two examples: a regular open command, and an expanded command.

```
open 'stocks.dat' as 1 for-reading record=100
open 'log.dat'    as 5 for-writing record=70
open $filename   as #j for-append  record=80:fixed
open $filename   as 2 for-reading record=80:fixed_nolf

open $filename   as 6 for-reading record=132:vary status=#filestat
if #filestat != 0
  ... error processing ...
end-if
```

An encoding directive added to the OPEN command allows differently encoded files to be managed in a single run of SQR. When no ENCODING is specified on the OPEN command, SQR uses the file input or output encoding specified in the INI file unless the file is UCS-2 encoded and auto-detection of UCS-2 files is enabled. The complete syntax of the OPEN command is:

```
OPEN {filename_lit | _var | _col} AS {filenum_num_lit |
_var | _col}
{ FOR-READING | FOR-WRITING | FOR-APPEND }
{ RECORD = length_num_lit[:FIXED | :FIXED_NOLF |
:VARY]}
[ STATUS = num_var ]
[ ENCODING = { _var | _col | ASCII | ANSI | SJIS | JEUC
| EBCDIC |
EBCDIK290 | EBCDIK1027 | UCS-2 | UTF-8 | others... }

```

The ENCODING directive is only allowed when converting to Unicode internally.

See Also

The READ, WRITE, and CLOSE commands for information about using files.

PAGE-NUMBER

Syntax

```
PAGE-NUMBER position[pre_txt_lit[post_txt_lit]]
```

Description

Places the current page number on the page.

The text specified in *pre_txt_lit* and *post_txt_lit* are printed immediately before and after the number.

Parameters

Parameter	Description
<i>position</i>	Specifies the position of the page number.
<i>pre_txt_lit</i>	Specifies a text string to be printed before the page number.
<i>post_txt_lit</i>	Specifies a text string to be printed after the page number.

Example

```
begin-footing 1
  page-number      (1,37) 'Page '      ! Will appear as
  last-page        () ' of ' ' .'      ! "Page 12 of 25."
end-footing
```

See Also

The LAST-PAGE command.

POSITION

Syntax

```
POSITION position
[@document_marker[COLUMNS{num_lit|_var|_col}
[num_lit|_var|_col]...]]
```

Description

Sets the current position on a page.

Parameters

Parameter	Description
@document_markerg	References a location defined in a document paragraph. In this case, the position used is the location of that marker in the text of the document.
COLUMNS	Defines columns beginning at the location of the document marker. The columns defined are relative to the position of the document marker. When COLUMNS is used, the entire command cannot be broken across more than one program line.

Example

```
position (12,5)           ! Set current position to line 12, column 5.
position (+2,25)          ! Set position 2 lines down, at 25th column.
position () @total_location ! Set position to document
print #total () edit 999,999,999 ! marker @total_location.
position () @name_loc columns 1 30
print name ()             ! Columns are defined at @name_loc and
next-column               ! 29 characters to the right of @name_loc
print title ()
```

See Also

The COLUMNS command for more information.

Enterprise PeopleTools 8.45 PeopleBook: SQR for PeopleSoft Developers, “Creating Form Letters”

PRINT

Syntax

```
PRINT {any_lit|_var|_col} position[format_command[format_cmd_params]...]....
```

Description

Puts data on the page at a specified position.

See *Enterprise PeopleTools 8.45 PeopleBook: SQR for PeopleSoft Developers*, “Changing Fonts”.

Parameters

Parameter	Description
{any_lit _var _col}	Specifies the data to be printed. Dates can be contained in a date column or variable or, in a string literal, column, or variable. When using <i>EDIT</i> or <i>DATE</i> with the <i>PRINT</i> command, a date in a string literal, column, or variable must be in an acceptable format. See the description of <i>EDIT</i> for further details.
position	Specifies the position where the data is to be printed.
format_command [format_cmd_params]	Specifies optional formatting commands and parameters.

Format Commands

The *PRINT* command has the following format commands:

- BACKGROUND
- BOLD
- BOX
- CENTER
- CODE-PRINTER
- DATE
- EDIT
- FILL
- FOREGROUND
- MONEY
- NOP
- NUMBER
- ON-BREAK
- SHADE
- UNDERLINE
- WRAP

Some of these format commands can be used in combination with others and some are mutually exclusive. The following tables shows which can be used together. An X indicates that they can be used together.

	BOLD	BOX	CENTER	CODE- PRINTER	EDIT NUMBER MONEY DATE	FILL
BOLD		X	X		X	X
BOX	X		X		X	X
CENTER	X	X			X	X
CODE- PRINTER						
EDIT NUMBER MONEY DATE	X	X	X			
FILL	X	X	X			
F/B	X		X		X	X
MATCH	X	X	X			
NOP	X	X	X	X	X	X
ON-BREAK	X	X	X		X	X
SHADE	X	X	X		X	X
UNDERLINE	X		X		X	X
WRAP	X	X				X

Table, Part 1

	F / B	MATCH	NOP	ON-BREAK	SHADE	UNDERLINE	WRAP
BOLD	X	X	X	X	X	X	X
BOX	X	X	X	X	X		X
CENTER	X	X	X	X	X	X	
CODE- PRINTER			X				
EDIT NUMBER MONEY DATE	X		X	X	X	X	
FILL	X		X	X	X	X	X
F/B		X	X	X	X		X
MATCH	X		X	X	X	X	
NOP	X	X		X	X	X	X
ON-BREAK	X	X	X		X	X	X
SHADE	X	X	X	X		X	X
UNDERLINE	X	X	X	X	X		X
WRAP	X		X	X	X	X	

Table, Part 2

Note. In the previous tables, F/B stands for FOREGROUND/BACKGROUND.

The following sections describe the PRINT format commands.

BOLD

BOLD causes the string or number to print in **bold** type.

For HP LaserJet printers, the appropriate boldface font must be loaded in the printer.

For PostScript printers, the appropriate boldface must be defined in the PostScript startup file, `postscri.str`.

See the DECLARE-PRINTER Command Arguments table for information about which font can be boldfaced.

For line printers, when the BEFORE-BOLD and AFTER-BOLD arguments on the DECLARE-PRINTER command are used, the specified strings are added before and after the data to be boldfaced. If BEFORE-BOLD and AFTER-BOLD are not specified, then BOLD has no effect.

For example:

```
print &name (+1, 20) bold
print 'Your account is in arrears' (1,1) bold
```

BOX

BOX draws a one-line deep graphical box around the printed data. This option has no effect for line printers.

For example:

```
print &grand_total (+5, 20) box
print 'Happy Birthday !!' (1,1) box
```

Note. For HP LaserJet printers using proportional fonts, BOX and SHADE are not able to determine the correct length of the box because it varies with the width of the characters printed. BOX and SHADE work well with fixed-pitch fonts and with all PostScript fonts.

CENTER

CENTER centers the field on a line. The position qualifier for column is ignored. For example:

```
print 'Quarterly Sales' (1) center
```

CODE-PRINTER

CODE-PRINTER has the following syntax:

```
CODE-PRINTER = printer_type
```

Valid values for *printer_type* are HT, HP, PS, LP, HTML, HPLASERJET, POSTSCRIPT, and LINEPRINTER.

CODE-PRINTER

Adds nondisplay characters to the program for the purpose of sending a sequence to the printer. CODE-PRINTER causes the string to be placed *behind* the page buffer, rather than within it, so alignment of printed data is not affected by the white space consumed by the nondisplay characters. Only strings can be printed using CODE-PRINTER.

Because the report might be printed on different types of printers, you should specify for which type this data is to be used. The report is ignored if printed to a different type. If necessary, you can send a different sequence to another type with a second PRINT statement.

For example:

```
encode '<27>[5U' into $big_font
encode '<27>[6U' into $normal_font
...
print $big_font (0, +2) code-printer=lp
print &phone () edit '(xxx) xxx-xxxx'
```

```
print $normal_font ( ) code-printer=lp
```

In the previous example, the two CODE-PRINTER arguments put the *\$big_font* and *\$normal_font* sequences into the output, without overwriting any data in the page buffer. Sequences printed with the CODE- PRINTER argument are positioned using the regular line and column positioning. However, unlike the PRINT command, the current print location after execution is the beginning location where the CODE-PRINTER string was placed. Multiple coded strings printed using the same line and column location appear in the output in the same sequence in which they were printed.

DATE

You cannot use DATE with numeric columns or variables. DATE indicates that the field is to be formatted using the DATE-EDIT-MASK from the current locale. (See the ALTER_LOCALE command.) If this entry is not set, then the date is printed according to the following rules shown in the Date table.

Column Type	Default Mask	If not set
DATETIME	SQR_DB_DATE_FORMAT	See the Default Database Formats table for the format that is used.
DATE	SQR_DB_DATE_ONLY_FORMAT	See the DATE Column Formats table for the format that is used.
TIME	SQR_DB_TIME_ONLY_FORMAT	See the TIME Column Formats table for the format that is used.

EDIT

EDIT has the following syntax:

```
EDIT edit_format
```

EDIT causes each field to be edited before it is printed. The three types of edits are:

- Text edit
- Numeric edit
- Date edit

The following table lists the text edit format characters.

Character	Description
X	Use character in field.
B	Insert blank.

Character	Description
~ (tilde)	Skip character in field.
R[n]	Reverse sequence of string, for languages such as Hebrew. The optional number indicates right justification within length indicated.

Any other character (for example, punctuation) in a text edit mask is treated as a constant and is included in the edited field.

The characters 8, 9, 0, V, and \$ are illegal in a text edit mask because they are used to indicate that the mask is for a numeric edit.

The following table lists the numeric edit format characters.

Character	Description
8	Digit, zero fill to the right of the decimal point, trim leading blanks (left justify the number).
9	Digit, zero fill to the right of the decimal point, space fill to the left.
0	Digit, zero fill to the left.
\$	Dollar sign, optionally floats to the right.
B	Treated as a 9, but if a value is zero, the field is converted to blanks.
C	Entered at the end of the mask, causes the comma and period characters to be transposed when the edit occurs. This is to support monetary values where periods delimit thousands and commas delimit decimals. (Example: 1.234,56).
E	Scientific format. The number of 9s after the decimal point determines the number of significant digits displayed. The E can be uppercase or lowercase; the display follows the case of the mask.
V	Implied decimal point.
MI	Entered at the end of the mask, causes a minus to display at the right of the number.

Character	Description
PR	Entered at the end of the mask, causes angle brackets (<>) to display around the number if the number is negative.
PS	Entered at the end of the mask, causes parentheses to display around the number if the number is negative.
PF	Entered at the end of the mask, causes floating parentheses to display around the number if the number is negative.
NA	Entered at the end of the mask, causes N/A to display if the numeric column variable is null. The case of N/A follows that of the mask.
NU	Entered at the end of the mask, causes blanks to display if the numeric column variable is null.
.	Decimal point.
,	Comma.

Characters other than those listed in the Numeric Edit Format Characters table are illegal for numeric edit masks and cause errors during processing.

The following table shows sample edit masks and resulting fields.

Mask	Value	Display
999.99	34.568	34.57
9,999,999V9999	123,456.7890	123,4567890
8,888,888.888	123,456.789	123,456.789
9,999	1234	1,234
9,999	123	123
09999	1234	01234
9999	-123	-123

Mask	Value	Display
9999	-1234	****
9999	12345	****
9999mi	-123	123-
9999pr	-123	< 123>
999999ps	-123	(123)
999999pf	-123	(123)
9999na	(null)	n/a
9999nu	(null)	(blank)
\$\$9,999.99c	1234.56	\$1.234,56
\$\$9,999.99	1234.56	\$1,234.56
\$\$9,999.99	12.34	\$ 12.34
\$\$\$,\$\$9.99	12.34	\$12.34
9.999e	123456	1.235e+05
B9,999	0	(blank)
B9,999	12345	12,345
(xxx)bxxx-xxxx	2169910551	(216) 991-0551
xxx-xx-xxxx	123456789	123-45-6789
~~xx~xx	ABCDEFGHJIJ	CDFG
r10	ABCDEFGF	GFEDCBA

The following example shows some uses of edit masks:

```

print #total (7,55,0) edit $999,999.99          ! $ 12,345.67
print #total (7,55,0) edit $$$9,999.99          ! $12,345.67
print #total (7,55,0) edit 999,999.99pr          ! < 12,345.67>(if neg)
print #comm (7,55,0) edit b99,999.99            ! Blank if zero
print &cnum (16,1,0) edit 099999                 ! 001234
print #cat (5,10,0) edit 9.999E                  ! 1.235E+04
print #phone (16,60,0) edit (xxx)bxxx-xxxx      ! (216) 397-0551
print #total (7,55,0) edit £££9,999.99          ! Dollar-Symbol £

```

The following table lists the date edit format codes.

Character	Description
YYY YY Y	Last 3, 2, or 1 digits of the year. On input, for calculating the 4-digit year, the current century and/or decade are used. For example, a 9 using the Y mask would result in 1999 as the year if the current year is in the 1990s.
YYYY SYYY	4 digit year, S prefixes BC dates with "-".
RR	Last 2 digits of year; for years in other centuries. See the Date Edit Format Code-RR table.
CC or SCC	Century; S prefixes BC dates with "-".
BC AD	BC/AD indicator.
Q	Quarter of year (1,2,3,4; JAN-MAR=1).
RM	Roman numeral month (I-XII; JAN=I).
WW	Week of year (1-53) where week 1 starts on the first day of the year and continues to the seventh day of the year.
W	Week of the month (1-5) where week 1 starts on the first day of the month and ends on the seventh.
DDD	Day of year (1-366).
DD	Day of month (1 - 31).
D	Day of week (1-7). Sunday is first day of week.
DAY	Name of day.

Character	Description
DY	Abbreviated name of day.
ER	Japanese Imperial Era. Returns the name of the of the Japanese Imperial Era in the appropriate kanji ('Heisei' is the current era).
EY	Year of the Japanese Imperial Era. Returns the current year within the Japanese Imperial Era. Note. The common Japanese date format is: 'YYYY<nen>MM<gatsu>DD<nichi>' where <nen>, <gatsu>, and <nichi> are the kanji strings for year, month, and day respectively.
J	Julian day; the number of days since Jan 1, 4713 BC. Numbers specified with 'J' must be integers.
AM PM	Meridian indicator.
HH	Assumes 24 hour clock unless meridian indicator specified.
HH12	Hour of day (1-12).
HH24	Hour of day (0-23).
SSSSS	Seconds past midnight (0-86399).
N NN NNN NNNN NNNNN NNNNNN	Fractions of a second. Precise to microseconds; however, for most hardware and databases, this much accuracy will not be attainable.
MONTH	Name of month.
MON	Abbreviated name of month.
MM	Month (01-12; JAN=01).
MI	Minute (0-59).

Character	Description
SS	Second (0-59).
	Used to concatenate different masks.

Note. If the last two digits of the year are between 00 and 49, the return date is in the current century. If the last two digits of the year are between 50 and 99, the return date is in the century after the current one.

Last 2 Digits of Current Year	2-Digit Year is 00–49	2-Digit Year is 50–99
00–49	The return date is in the current century.	The return date is in the century before the current one.
50–99	The return date is in the century after the current one.	The return date is in the current century.

All masks can be used by the strtodate function except for CC, SCC, Q, W, and WW.

A backslash forces the next character into the output from the mask. For example, a mask of *The cu\rre\nt \mo\nth is Month* results in the output string of *The current month is January*. Without the backslashes the output string would be *The cu04e7t january is January*.

A vertical bar can be used as a delimiter between format codes; however, in most cases the bar is not necessary. For example, the mask 'YYYY|MM|DD' is the same as 'YYYYMMDD'.

Any other character (for example, punctuation) in a date edit mask is treated as a constant and is included in the edited field. If the edit mask contains spaces, it must be enclosed in single quotes (').

The masks MON, MONTH, DAY, DY, AM, PM, BC, AD, and RM are case-sensitive and follow the case of the mask entered. For example, if the month is January, the mask Mon yields "Jan" and MON yields "JAN".

All other masks are case-insensitive and can be entered in either uppercase or lowercase. In addition, National Language Support is provided for the following masks: MON, MONTH, DAY, DY, AM, PM, BC, and AD.

See the command ALTER-LOCALE in the SQR Samples section for additional information.

If the value of the date field being edited is "Mar 14 2004 9:35", the edit masks produce the results in the following table.

Edit Mask	Result
dd/mm/yy	14/03/04
DD-MON- YYYY	14-MAR-2004
'Month dd, YYYY'	March 14, 2004
MONTH-YYYY	MARCH-2004

Edit Mask	Result
HH:MI	09:35
'HH:MI PM'	09:35 AM
YYYYMMDD	20040314
MM.DD.YYYY	03.14.2004
Mon	Mar
DD D DDD	143073

In addition to being used with the EDIT argument, edit masks can be used with the MOVE, CONCAT, DISPLAY, and SHOW commands, and with the edit function of the LET command. You edit the field using the supplied mask before storing or displaying it.

When a date with missing date and/or time components is displayed or printed, the defaults are as follows:

- The default year is the current year.
- The default month is the current month.
- The default day is one.
- The default time is zero (00:00:00.000000).

For example, assuming today is September 7, 2004, the following assignment would produce an equivalent date-time of September 1, 2004 13:21:00.000000:

```
let $date1 = strtodate('13:21','HH:MI')
```

Edit masks can be changed dynamically by storing them in a string variable and referencing the variable name preceded by a colon (:). For example:

```
move '$999,999.99' to $mask
print #total (5,10) edit :$mask
show #total edit :$mask
```

When a date that is stored in a string literal, column, or variable is printed with an edit mask, it must be in one of the following formats:

- The format specified by the environment variable SQR_DB_DATE_FORMAT, or the corresponding setting in the sqr.ini file.
- One of the database-dependent formats, as listed in the Default Database Formats table.
- The database-independent format, 'SYYYYMMDD[HH24[MI[SS[NNNNNN]]]]'.

When a date column or variable is printed without an edit mask, the date is printed in the format specified by the environment variable SQR_DB_DATE_FORMAT or the corresponding setting in the sqr.ini file. If this has not been set, then the date is printed in the primary database format (the first entry) listed in the Default Database Formats table.

This applies to DISPLAY, MOVE, and SHOW commands as well as PRINT.

The following table lists default date formats for each database.

Database	Default Database Formats
DB2	YYYY-MM-DD- HH:MI:SS.NNNNNN YYYY-MM-DD
Informix	YYYY-MM-DD HH:MI:SS.NNN MM/DD/YYYY MM-DD-YYYY MM.DD.YYYY
ODBC	MM-DD-YYYY
Oracle	DD-MON-YY
Sybase	MON DD YYYY HH:MIPM MON DD YYYY [HH:MI[:SS[:NNN]]][PM] MON DD YYYY [HH:MI[:SS[:NNN]]][PM] YYYYMMDD [HH:MI[:SS[:NNN]]][PM] YYYYMMDD [HH:MI[:SS[:NNN]]][PM]

Database	DATE Column Formats
DB2	YYYY-MM-DD
Informix	MM/DD/YYYY
ODBC	DD-MON-YYYY

Database	TIME Column Formats
DB2	HH24.MI.SS
ODBC	HH24:MI:SS

FILL

FILL fills the page with the specified character or string as indicated by the print position and length.

The following example prints a line of stars and then a line of dashes followed by stars:

```
print '*' (1,1,79) fill      ! Fill line with *'s
print '-*' (+1,20,40) fill   ! Fill with '-*' characters.
```

FOREGROUND/BACKGROUND

When you specify a color on the PRINT command its scope is that of the PRINT command. If you do not define the specified color name, then the setting for *default* is used. Use the color name *none* to turn off color for the specified area.

```
PRINT {any_lit|_var|_col}
[FOREGROUND =({color_name_lit|_var|_col}|{rgb})]
[BACKGROUND =({color_name_lit|_var|_col}|{rgb})]
```

MATCH

MATCH has the following syntax:

```
MATCH match_text { line_num_lit|_var|_col }
{ column_num_lit|_var|_col } print_text ...
```

MATCH compares a field to a list of key values and if a match is found, prints the corresponding string at the specified line and column. If the match_text contains white space, it must be enclosed in single quotes ('). Any number of match text(s) can be tested, but each must have its own line, column, and print_text. If a match is not found, the unmatched field is printed at the position specified in the parentheses. Line and column positions for each matched string are treated as fixed or relative positions depending on the type of positioning used in the position qualifier for the PRINT command. For example:

```
print &type_buyer (20,12) match
A 20 12 Casual
B 20 22 Impulsive
C 21 12 Informed
D 21 22 Choosey
```

To use relative line and fixed column positioning, for example, you could use the following example:

```
print $state (0,25) match
OH 0 25 Ohio
MI 0 37 Michigan
NY 0 25 'New York'
```

The column positions are treated as fixed locations due to the fixed 25 position declared in parentheses.

MONEY

MONEY indicates that the column or variable is to be formatted using the MONEY-EDIT-MASK from the current locale. (See the ALTER_LOCALE command.) This can only be used with a numeric column or variable.

NOP

NOP suppresses the print command, causing *no operation* to be executed. This argument is useful for temporarily preventing a field from printing. For example:

```
print &ssn (1,1) nop
Hide the social security number.
```

NUMBER

NUMBER indicates that the column or variable is to be formatted using the NUMBER-EDIT-MASK from the current locale. (See the ALTER-LOCALE command.) This argument can only be used with a numeric column or variable.

ON-BREAK

ON-BREAK has the following syntax:

```
ON-BREAK [PRINT={ALWAYS|CHANGE|CHANGE/TOP-PAGE|NEVER}]
[SKIPLINES={num_lit|_var|_col}]
[PROCEDURE=procedure_name[(arg1[ ,argi]...)]
[AFTER=procedure_name[(arg1[ ,argi]...)]
[BEFORE=procedure_name[(arg1[ ,argi]...)]
[SAVE=txt_var]
[LEVEL=nn]
[SET=nn]
```

ON-BREAK causes the specified action in a tabular report when the value of a field changes (a break occurs). The default action prints the field only when its value changes (PRINT=CHANGE). ON-BREAK has the following qualifiers:

- **PRINT**—Specifies when the break field is printed.
 - ALWAYS duplicates the break field for each detail group.
 - CHANGE prints the value only when it changes. This is the default.
 - CHANGE/TOP-PAGE prints the value both when it changes and at the top of each new page.
 - NEVER suppresses printing.
- **SKIPLINES**—Specifies how many lines to skip when the value changes.
- **PROCEDURE**—Specifies the procedure to be invoked when the value changes. This qualifier cannot be used with either the AFTER or BEFORE qualifiers.
- **AFTER and BEFORE procedures**—Specify procedures to invoke either after or before the value changes. If no rows are fetched, neither procedure is executed. AFTER and BEFORE can be used only within a SELECT paragraph.
- The sequence of events is shown here:
 - **SAVE**—Indicates a string variable where the previous value of a break field is stored.
 - **LEVEL**—Specifies the level of the break for reports containing multiple breaks. For example, a report sorted by state, county, and city might have three break levels: state is level 1 (the most major), and city is level 3 (the most minor). When a break occurs, other breaks with equal or higher level numbers are cleared. The level number also affects the sequence in which AFTER and BEFORE procedures are processed.
 - **SET**—Assigns a number to the set of leveled breaks in reports with more than one set of independent breaks.

Following is the sequence of events for a query containing ON-BREAK fields:

1. Any BEFORE procedures are processed in ascending LEVEL sequence before the first row of the query is retrieved.
2. When a break occurs in the query, the following happens:

- AFTER procedures are processed in descending sequence from the highest level to the level of the current break field.
 - SAVE variables are set with the new value.
 - BEFORE procedures are processed in ascending sequence from the current level to the highest level break.
 - Any breaks with the same or higher level numbers are cleared so they do not break on the next value.
 - If a PROCEDURE has been declared, the procedure is invoked.
 - If SKIPLINES was specified, the current line position is advanced.
 - The value is printed (unless PRINT=NEVER was specified).
3. After the query finishes (at END-SELECT) any AFTER procedures are processed in descending level sequence.

For example:

```
begin-select
state (+1,1,2) on-break level=1 after=state-tot skiplines=2
county (+2,14) on-break level=2 after=cnty-tot skiplines=1
city (+2,14) on-break level=3 after=city-tot
...
end-select
```

The breaks are processed as follows:

- When city breaks, the city-tot procedure is executed.
- When county breaks, first the city-tot procedure is executed, then the cnty-tot procedure is executed.
- When state breaks, the city-tot, cnty-tot, and state-tot procedures are processed in that sequence.

If any BEFORE breaks were indicated, they would also be processed automatically, after all of the AFTER breaks and in sequence from lower to higher level numbers. For example:

```
begin-select
state (+1,1,2) on-break level=1 before=bef-state after=state-tot
county (+2,14) on-break level=2 before=bef-cnty after=cnty-tot
city (+2,14) on-break level=3 before=bef-city after=city-tot
...
end-select
```

Now when state breaks, the sequence of procedures executed is as follows:

- City-tot
- Cnty-tot
- State-tot
- Bef-state
- Bef-cnty
- Bef-city

Upon entering the query at BEGIN-SELECT, the three BEFORE procedures are executed in sequence:

- Bef-state
- Bef-cnty
- Bef-city

After the last row is retrieved, at END-SELECT, the three AFTER procedures are executed in sequence:

- City-tot
- Cnty-tot
- State-tot

The SAVE qualifier saves the previous break value in the specified string variable for use in an AFTER procedure. You may want to print the previous break field with a summary line:

```
print &state (+1,1) on-break after=state-tot save=$old-state
```

The SET qualifier enables you to have sub-reports with leveled breaks. By separating the ON-BREAKs into sets, the associated leveled breaks in each set do not interfere with each other.

```
begin-select
state (+1,1,2) on-break set=1 after=state-tot level=1
```

SET=1 associates this leveled break with other breaks having the same set number.

SHADE

Draws a one-line deep, shaded graphical box around the printed data. For line printers this argument has no effect.

```
print 'Company Confidential' (1,1) shade
print &state (+2, 40) shade
```

Note. For HP LaserJet printers using proportional fonts, BOX and SHADE are not able to determine the correct length of the box because it varies with the width of the characters printed. BOX and SHADE work well with fixed pitch fonts and with all PostScript fonts.

UNDERLINE

UNDERLINE prints the specified data with underlined characters. For line printers, UNDERLINE causes backspace and underscore characters to be output, which emulates underlining. For example:

```
print &name (+1, 45) underline
print 'Your account is in arrears' (1,1) underline
```

WRAP

WRAP wraps text at word spaces. Additional text is moved to a new line. WRAP has the following syntax:

```
WRAP {line_length_lit|_var|_col}
{max_lines_lit|_var|_col}[KEEP-TOP]
[STRIP=strip_chars][ON=break_chars][R]
[LINE-HEIGHT={line_height_lit|_var|_col}]

line_length_lit|_var|_col
```

Specifies the maximum paragraph width in characters.

Note. After a string wraps, the current position is one character to the right of the last character in the column. When a string ends on the last position of a line, an implicit line feed causes the new current position to be the first character of the following line. In the SETUP section, use the DECLARE-LAYOUT command to make the page width one character wider than the right edge of the wrapped text to avoid generating an implicit line feed.

For example:

```
print &comment (48,20,0) wrap 50 3 ! Paragraph is 50
                                   ! characters wide,
                                   ! with a maximum
                                   ! depth of 3 lines.

print &note1    (1,20,30) wrap 30 4
print &note2    (1,+2,30) wrap 30 4
print &note3    (1,+2,30) wrap 30 4
```

In this example, the line position is 1 for each of the three wrapped fields: note1, note2, and note3. The current print position after a wrap occurs at the bottom right edge of the wrapped paragraph. To continue printing on the same line, you must use a fixed line number for the next field.

```
max_lines_lit|_var|_col
```

Specifies the maximum paragraph depth in lines. Usually, the line length and maximum lines are indicated with numeric literals. However, WRAP can also reference numeric variables or columns. This is useful when you want to change the width or depth of a wrapped paragraph during report processing. The numeric variable can optionally be preceded by a colon (:). For example:

```
print $comments (1,30) wrap #wrap_width 6
print $message (5,45) wrap #msg_wid #msg_lines
```

KEEP-TOP retains the current line position except if a page break occurs, in which case, line 1 is used as the current line position. The default action is to set the next print position at the bottom of the wrapped data.

In the following example, the column &resolution prints on the same line as the first line of the column &instructions:

```
print &phone (+1,10) edit '(xxx) xxx-xxxx'
print &instructions (+1,10,30) wrap 6 30 keep-top
print &resolution (0,+3,25)
```

The STRIP and ON arguments affect which characters are to be converted before wrapping, and which characters force a wrap to occur.

- Characters in the STRIP string argument are converted to spaces before the wrap occurs.
- Characters in the ON string argument cause a wrap at each ON character found.
The ON character is not printed.

Both arguments accept regular characters and nondisplay characters whose decimal values are surrounded by angled brackets, <nn>, where nn is a decimal number between 1 and 255, representing the character in the current character set of the operating system. For example, to print a long data type that contains embedded carriage returns, the setup would be:

```
print &long_field (5,20) wrap 42 30 on=<13>
```

The paragraph wraps at each carriage return, rather than at the usual word boundaries. If the ON character is not found within the width specified for the paragraph, the wrap occurs at a word space. The following example converts the STRIP characters to spaces before wrapping on either a line feed <10> or a space (the default):

```
print &description (20,10) wrap 50 22 strip=/\^@<13> on=<10>
```

WRAP can also be used to print reversed characters, for support of languages such as Hebrew. An R after the length and max_lines arguments causes the field to be reversed before the wrap takes place. In addition, the entire paragraph is right-justified within the length indicated.

```
! Reverse wrap, in 30 character field.
```

```
print &comment (2,35) wrap 30 5 r
```

```
print $notes (1,50) wrap 50 7 r
```

LINE-HEIGHT specifies the number of lines to skip between each line of the wrapped data. By default a value of 1 (single space) is assumed. The following example prints the comment column with one blank line between each printed line for a maximum of four printed lines:

```
print &comment (1,1) wrap 40 4 line-height = 2 ! Double space text
```

See Also

The LET command for information about copying, editing, or converting fields.

The ALTER-LOCALE command for a description of the arguments NUMBER-EDIT-MASK, MONEY-EDIT-MASK, and DATE-EDIT-MASK.

The DISPLAY and SHOW commands.

PRINT-BAR-CODE

Syntax

```
PRINT-BAR-CODE position
```

```
{TYPE={bar_code_type_num_lit|_var|_col}}
```

```
{HEIGHT={bar_code_height_num_lit|_var|_col}}
```

```
{TEXT={bar_code_txt_lit|_var|_col}}
```

```
[CAPTION={bar_code_caption_txt_lit|_var|_col}]
```

```
[CHECKSUM={checksum_lit}]
```

Description

PRINT-BAR-CODE prints industry standard bar codes. SQR supports the bar code types listed in the following table.

Type	Description	Text Length	Text Type	CHECKSUM RECOGNIZED
1	UPC-A	11, 13, or 16	9	
2	UPC-E	11, 13, or 16	9	
3	EAN/JAN-13	12, 14, or 17	9	

Type	Description	Text Length	Text Type	CHECKSUM RECOGNIZED
4	EAN/JAN-8	7, 9, or 12	9	
5	3 of 9 (Code 39)	1 to 30	9, X, p	y
6	Extended 3 of 9	1 to 30	9, X, x, p, c	y
7	Interleaved 2 of 5	2 to 30	9	y
8	Code 128	1 to 30	9, X, x, p, c	
9	Codabar	1 to 30	9	y
10	Zip+4 Postnet	5, 9, or 11	9	
11	MSI Plessey	1 to 30	9	y
12	Code 93	1 to 30	9, X, p	y
13	Extended 93	1 to 30	9, X, x, p	y
14	UCC-128	19	9	
15	HIBC	1 to 30	9	y

Parameters

Parameter	Description
position	Specifies the position of the upper left corner. Position parameters can be relative. See the POSITION command for examples of relative positioning. Document markers are not allowed. After execution, the current position is returned to this location; however, the next listing line is the next line below the bottom of the bar code. (This is different than the way the PRINT command works.)
TYPE	Specifies the type of bar code to be printed. Types are shown in the Bar Code Types table.
HEIGHT	Specifies the height of the bar code in inches. The height must be between 0.1 and 2 inches. The code prints to the nearest one-tenth of an inch. For Zip+4 Postnet, the height of the bar code is fixed. The height should be between 0.2 and 2.0 for Zip+4 Postnet. If it is less than 0.2, the bar code extends above the position specified.
TEXT	Specifies the text to be encoded and printed. The number and type of text characters permitted or required depends on the bar code type. See the Bar Code Types table for specifications.
CAPTION	Specifies optional text to be printed under the bar code in the current font. SQR attempts to center the caption under the bar code; however, for proportional fonts this may vary slightly. CAPTION is not valid for Zip+4 Postnet. If specified, it is ignored.
CHECKSUM	Specifies an optional check sum to be computed and printed within the bar code. Valid values are YES and NO, where NO is the default. Note. Some barcode types ignore the CHECKSUM qualifier. See the Bar Code Types table for those barcode types for which CHECKSUM is relevant.

Example

This example shows how to use the PRINT-BAR-CODE command to create a UPC-A bar code.

```
begin-program
  print 'Sample UPC-A Barcode' (1,1)
  print-bar-code (3,1)
    type=1                ! UPC-A
    height=0.3
    text='01234567890'
    caption='0 12345 67890'
end-program
```

This example shows how to use the PRINT-BAR-CODE command to create a ZIP+4 Postnet code.

```
begin-program
  print 'Sample Zip+4 Postnet'      (1,1)
  print 'John Q. Public'           (3,1)
  print '1234 Main Street'         (4,1)
  print 'AnyTown, USA 12345-6789'  (5,1)
  print-bar-code                   (7,1)
    type=10
    height=0.2
    text='12345678934'
```

end-program

Note. SQR does not check bar code syntax. See your bar code documentation for the proper formatting of certain bar codes.

PRINT-CHART

Syntax

```
PRINT-CHART[chart_name]position
DATA-ARRAY-ROW-COUNT={x_num_lit|_var|_col}
DATA-ARRAY-COLUMN-COUNT={x_num_lit|_var|_col}
DATA-ARRAY=array_name
[DATA-LABELS=data_labels_lit | _var | _col]
[COLOR-PALETTE=color_palette_lit | _var | _col]]
[ITEM-COLOR=(Chart_item_keyword, txt_lit |var | (r,g,b))]
[DATA-ARRAY-COLUMN-LABELS={NONE|array_name|
{({txt_lit|_var}[,txt_lit|_var])...}}}]
[CHART-SIZE=(chart_width_num_lit|_var,
chart_depth_num_lit|_var)]
[TITLE={title_txt_lit|_var|_col}]
[SUB-TITLE={subtitle_txt_lit|_var|_col}]
[FILL={fill_lit|txt_var|_col}]
[3D-EFFECTS={3d_effects_lit|txt_var|_col}]
[BORDER={border_lit|txt_var|_col}]
[POINT-MARKERS={point_markers_lit|txt_var|_col}]
[TYPE={chart_type_lit|txt_var|_col}]
[LEGEND={legend_lit|txt_var|_col}]
[LEGEND-TITLE={legend_title_txt_lit|_var|_col}]
[LEGEND-PLACEMENT={legend_placement_lit|txt_var|_col}]
[LEGEND- PRESENTATION={legend_presentation_lit|txt_var|_col}]
[PIE-SEGMENT-QUANTITY-DISPLAY=      {pie_segment_quantity_display_lit|txt_var|_col}]
[PIE-SEGMENT-PERCENT- DISPLAY={pie_segment_percent_display_lit
|txt_var|_col}]
[PIE-SEGMENT-EXPLODE={pie_segment_explode_lit
|txt_var|_col}]
[X-AXIS-LABEL={x_axis_label_txt_lit|_var|_col}]
[X-AXIS-MIN-VALUE={x_axis_min_value_lit|_num_lit|_var
|_col}]
[X-AXIS-MAX-VALUE={x_axis_max_value_lit|_num_lit|_var
|_col}]
[X-AXIS-SCALE={x_axis_scale_lit|txt_var|_col}]
[X-AXIS-MAJOR-TICK-MARKS={x_axis_major_tick_marks_lit
|txt_var|_col}]
[X-AXIS-MINOR-TICK-MARKS={x_axis_minor_tick_marks_lit
|txt_var|_col}]
[X-AXIS-MAJOR-INCREMENT={x_axis_major_increment_lit
|_num_lit|_var|_col}]
[X-AXIS-MINOR-INCREMENT={x_axis_minor_increment_lit
|_num_lit|_var|_col}]
```

```

X-AXIS-TICK-MARK-PLACEMENT=
{x_axis_tick_mark_placement_lit|txt_var|_col}}
[X-AXIS-GRID={x_axis_grid_lit|txt_var|_col}}
[Y-AXIS-LABEL={y_axis_label_lit|txt_var|_col}}
[Y-AXIS-MIN-VALUE={y_axis_min_value_lit|_num_lit
|_var|_col}}]
[Y-AXIS-MAX-VALUE={y_axis_max_value_lit|_num_lit
|_var|_col}}]
[Y-AXIS-SCALE={y_axis_scale_lit|txt_var|_col}}]
[Y-AXIS-MAJOR-TICK-MARKS={y_axis_major_tick_marks_lit
|txt_var|_col}}]
[Y-AXIS-MINOR-TICK-MARKS={y_axis_minor_tick_marks_lit
|txt_var|_col}}]
[Y-AXIS-MAJOR-INCREMENT={y_axis_major_increment_lit
|_num_lit|_var|_col}}]
[Y-AXIS-MINOR-INCREMENT={y_axis_minor_increment_lit
|_num_lit|_var|_col}}]
[Y-AXIS-TICK-MARK-PLACEMENT=
    {y_axis_tick_mark_placement_lit|txt_var|_col}}]
[Y-AXIS-GRID={y_axis_grid_lit|txt_var|_col}}]

```

Note. If you do not define CHART-SIZE with this command, you must define it with DECLARE-CHART.

Description

Prints a chart. Only PostScript printers or HP printers that support HPGL (generally, this is HPLaserJet 3 and higher) render chart output.

The PRINT-CHART command directs SQR to output a chart according to the named chart, if any, and the overridden attributes, if any.

Note. PRINT-CHART can be used without referencing a named chart if all required attributes for the DECLARE-CHART are supplied in addition to all its required parameters. The PRINT-CHART command directs SQR to display the chart on the current page using the attribute values at the moment the command is executed. Manipulation of chart attribute values has no effect on the appearance of the chart after the PRINT-CHART command has been executed. For example, if you execute a PRINT-CHART with TITLE=\$ttl and \$ttl='Encouraging Results', and then change the value of \$ttl to 'Discouraging Results' immediately afterward, then the chart is printed with first value, 'Encouraging Results'. PRINT-CHART expects the DATA-ARRAY to be organized in a particular way. See the Chart Array Field Types (fewer than four fields) table for details. PRINT-CHART fills the area defined by CHART-SIZE as much as possible while maintaining an aesthetically pleasing ratio of height to width. In cases where the display area is not well suited to the chart display, the chart is centered within the specified region, and the dimensions are scaled to accommodate the region. Therefore, do not be alarmed if the chart does not fit exactly inside the box you have specified. It means that SQR has accommodated the shape of the region to provide the best looking chart possible. Chart commands used to send output to a line printer are ignored. Only PostScript printers or HP printers that support Hewlett Packard's HPGL (generally, this is HP LaserJet model 3 and higher) render chart output. If you attempt to print a chart to a LaserJet printer that does not support HPGL, the HPGL command output will likely become part of your output, leaving one or more lines of meaningless data across your report.

All the attributes defined for DECLARE-CHART are valid for the PRINT-CHART command. PRINT-CHART has five additional parameters. The position of the chart is described using the first parameter. The data that supports the chart is defined in the additional attributes: DATA-ARRAY, DATA-ARRAY-ROW-COUNT, DATA-ARRAY-COLUMN-COUNT, and DATA-ARRAY-COLUMN-LABELS.

As mentioned, each chart type meets a specific organizational requirement. The Chart Array Field Types (fewer than four fields) table describes these requirements.

Note. If the first field in the array designated by DATA-ARRAY is of type CHAR, then the value on the x-axis is the contents of that column. If the first field is not of type CHAR, then the value of the x-axis is the row number of the array designated by DATA-ARRAY, beginning with 1. Pie charts show the character value in the legend area. Histograms show the character value on the y-axis. XY-Scatter charts do not use the character value and none is needed in the array.

Note. If a PIE chart contains many small slices, the user must set the PIE-SEGMENT-QUANTITY-DISPLAY and/or PIE-SEGMENT-PERCENT-DISPLAY arguments to NO to prevent the values from one slice overwriting the values of another slice.

Chart Type	Field 0	Field 1	Field 2	Field 3
PIE	Type=char Pie segment labels, the names associated with each segment	Type=num The value associated with each pie segment	(Optional) Type=char Pie segment explode flag setting, 'Y' or 'N'	
LINE BAR STACKED-BAR 100%-BAR OVERLAPPED-BAR HISTOGRAM AREA STACKED-AREA 100%-AREA	Type=char X-Axis values	Type=num Series 1 Y-Axis values	(Optional) Type=num Series 2 Y-Axis values	(Optional) Type=num Series 3... Y-Axis values
XY-SCATTER-PLOT	Type=num Series 1 X-Axis values	Type=num Series 1 Y-Axis values	(Optional) Type=num Series 2 X-Axis values	(Optional) Type=num Series 2 ... Y-Axis values
FLOATING-BAR	Type=char X-Axis values	Type=num Series 1 Y-Axis offset	Type=num Series 1 Y-Axis duration	(Optional) Type=Num Series 2 ... Y-Axis offset

Chart Type	Field 0	Field 1	Field 2	Field 3	Field 4
HIGH-LOW-CLOSE	Type=char X-Axis values	Type=num High value	Type=num Low value	Type=num Closing value	(Optional) Type=num Opening value

Parameters

Parameter	Description
chart_name	Specifies the name of the chart from the DECLARE-CHART command. This name is not necessary if you specify the CHART-SIZE and all other pertinent attributes in the PRINT-CHART command.
Position	(row, column) Specifies the position of the upper left corner. Position parameters can be relative. See the POSITION command for examples of relative positioning. Document markers are not allowed. After execution, the current position is returned to this location; however, the next listing line is the next line below the bottom of the chart area. (This is different than the way the PRINT command works.)
DATA-ARRAY	Specifies the name of the array containing the data to be plotted. This must be the name of an array defined with CREATE-ARRAY.
DATA-ARRAY-ROW-COUNT	Specifies the number of rows or sets of data to be used from the DATA-ARRAY. If the DATA-ARRAY has a greater number of rows, only DATA-ARRAY-ROW-COUNT is included in the chart.
DATA-ARRAY-COLUMN-COUNT	Specifies the number of columns to be used from the DATA-ARRAY. If the DATA-ARRAY has a greater number of columns, only DATA-ARRAY-COLUMN-COUNT is included in the chart.
DATA-ARRAY-COLUMN-LABEL	Specifies labels for each Y-Axis value of the data set (fields) in DATA-ARRAY. These labels are displayed in the legend box. Column labels are ignored for pie charts. See the Chart Array Field Types (fewer than four fields) table for applicable fields for each type of chart. For definitions of the other arguments, see the DECLARE-CHART Command Arguments table.

Example

In this example, a pie chart is printed without explicit reference to a chart declared with DECLARE-CHART. All necessary arguments must be supplied in PRINT-CHART.

```
.
.
create-array
  name=unit_sales
  size=12
  field=product:char
  field=units:number
  field=explode:char
.
.
print-chart (15, 20)
```

```

title                = 'Green City Store Sales'
sub-title             = '(Second Quarter)'
chart-size            = (50, 28)
type                 = pie
data-array            = unit_sales
data-array-column-count = 3
data-array-row-count  = 7
3d-effects            = yes
fill                  = color

```

See Also

The DECLARE-CHART command.

PRINT-DIRECT

Syntax

PRINT-DIRECT

[NOLF]

[PRINTER={LINEPRINTER|POSTSCRIPT|HPLASERJET|HTML|LP|PS|HP|HT}]

{txt_lit|_var|_col}...

Description

Writes directly to the print output file without using the SQR page buffer.

PRINT-DIRECT can be used for special applications that cannot be accomplished directly with PRINT commands, such as initializing a page with graphics or other special sequences. Because this text is often printer-dependent and because the report can be printed on different types of printers that require different control characters, you can use the PRINTER qualifier to specify the printer type. If no PRINTER qualifier is specified, the command applies to all printer types.

When using PRINT-DIRECT in conjunction with PRINT commands, be aware that the SQR page buffer is copied to the output file only when each page is full or when a NEW-PAGE command is issued. One approach is to use PRINT-DIRECT commands inside a BEFORE-PAGE or AFTER-PAGE procedure (declared with the DECLARE-PROCEDURE command), so they are coordinated with the information coming out of the page buffer.

Parameters

Parameter	Description
NOLF	Specifies that no carriage return and line feed is to be printed. By default, printed text is followed by a carriage return and line feed character.
PRINTER	Specifies the type of printer to which this text applies.
{txt_lit _var _col}	The text to be printed.

Example

```

print-direct printer=ps '%%Page: ' $page-number
print-direct nolf printer=lp reset

```

PRINT-IMAGE

Syntax

```
PRINT-IMAGE[image_name]position
[TYPE={image_type_lit|_var|_col}]
[IMAGE-SIZE=(width_num_lit|_var|_col,height_num_lit
|_var|_col)]
[SOURCE={file_name_txt_lit|_var|_col}]
```

Note. If TYPE, IMAGE-SIZE, and SOURCE are not defined in PRINT-IMAGE, they must be defined in DECLARE-IMAGE.

Description

Prints an image.

The PRINT-IMAGE command can be placed in any section of a report with the exception of the SETUP section. The image file pointed to can be any file of the proper format.

PRINT-IMAGE may be used without referencing a named image if all required attributes for the DECLARE-IMAGE are supplied in addition to all its required parameters.

Parameters

Parameter	Description
image_name	Specifies the name of an image specified by a DECLARE-IMAGE.
position	(row, column) Specifies the position of the upper left corner. Position parameters can be relative. See the POSITION command for examples of relative positioning. Document markers are not allowed. After execution, the current position is returned to this location; however, the next listing line below the bottom of the image area. (This is different from the way the PRINT command works.)
TYPE	Specifies the image type. Types can be EPS-FILE, HPGL-FILE, GIF-FILE, JPEG-FILE, or BMP-FILE (for Windows).
IMAGE-SIZE	Specifies the width and height of the image.
SOURCE	Specifies the name of a file containing the image.

Example

For PostScript:

```
print-image office-signature (50, 20)
print-image (50, 20)
  type           = eps-file
  source         = 'sherman.eps'
  image-size = (10, 3)
```

For Windows:

```
print-image company-logo (+21, 25)
  type=bmp-file
  source='m:\logos\gustavs.bmp'
```

```
image-size=(75,50)
```

See Also

The DECLARE-IMAGE command.

PUT

Syntax

```
PUT {src_any_lit|_var|_col}...  
INTO dst_array_name(element)[field[(occurs)]]...
```

Description

Moves data into an array.

Columns retrieved from the database and SQR variables or literals can be moved into an array. The array must have been created previously using the CREATE-ARRAY command.

Considerations using PUT

When a date variable or column is moved into a text or char array field, the date is converted to a string according to the following rules:

- For DATETIME columns and SQR DATE variables, the format specified by the SQR_DB_DATE_FORMAT setting is used. If this has not been set, the first database-dependent format as listed in the Default Database Formats table is used.
- For DATE columns, the format specified by the SQR_DB_DATE_ONLY_FORMAT setting is used. If this has not been set, the format listed in the DATE Column Formats table is used.
- For TIME columns the format specified by the SQR_DB_TIME_ONLY_FORMAT setting is used. If this has not been set, the format as listed in the TIME Column Formats table is used.

When a string variable, column, or literal is moved to a date array field, the string must be in the format specified by the SQR_DB_DATE_FORMAT setting, one of the database-dependent formats as listed in the DATE Column Formats table is used, or the database-independent format 'SYYYMMDD[HH24[MI[SS[NNNNNN]]]]'.

```
dst_array_name(element)
```

If array fields are listed, data is placed into each field in the sequence it is listed, in the occurrence specified of that field.

If array fields are not listed, data is placed into consecutive fields in the order in which they were defined in the CREATE-ARRAY command; data is copied into occurrence zero of each field of the element specified in the array.

```
field [ ( occurs ) ]
```

Array element and field occurrence numbers can be numeric literals (123) or numeric variables (#j).

If no occurrence is specified, occurrence zero is used.

Parameters

Parameter	Description
src_any_var	The source variable or literal to be moved into the array. Numeric variables, literals, and database columns can be put into number (decimal, float, integer) fields. String variables, literals, and database columns can be put into char, text, or date fields. Date variables can be put into date, char, or text fields.

Example

In the following example, the four variables *&name*, *#count*, *\$date1*, and *\$code* are placed into the first four fields defined in the names array. The data is put into the *#j*'th element of the array.

```
put &name #count $date1 $code into names(#j)
```

The following command places *#j2*, *#j3*, and *#j4* into the zero through 2nd occurrences of the *tot* field in the *#j*'th element of the totals array.

```
put #j2 #j3 #j4 into totals(#j) tot(0) tot(1) tot(2)
```

The following command copies *#count* into the *#j2*'th occurrence of the count field in the *#j*'th element of the states array.

```
put #count into states(#j) count(#j2)
```

READ

Syntax

```
READ {filenum_lit|_var|_col} INTO {any_var:length_int_lit}...[STATUS=status_num_var]
```

Description

Reads the next record of a file into the specified variables.

Text and binary data is parsed according to the following criteria:

- Text data is any string of characters. The length of the variable name indicates how many characters to place into the variable. After being transferred, trailing blanks in the variable are omitted.
- If the field was written as a date variable, then it may be read into a date variable or text variable. When reading a date into a date variable, it must be in the format specified by the SQR_DB_DATE_FORMAT setting, one of the database-dependent formats as listed in the DATE Column Formats table is used, or the database-independent format 'YYYYMMDD[HH24[MI[SS[NNNNNN]]]'.
- Binary numbers, may be 1, 2, or 4 bytes in length. They must be read into numeric variables. Note that the bytes making up the binary number must be in the standard sequence expected by your operating system.
- When reading binary data the file must be opened with the FIXED or FIXED-NOLF qualifier.
- Only the integer portion of the number is represented with binary numbers. To maintain the decimal portion of the number convert the number to a string variable.
- If you use binary numbers, the file is not portable across platforms. This is because different hardware represents binary numbers differently.

The total length indicated for the variables must be less than or equal to the length of the record being read.

If there are no more records to read, the *#end-file* reserved variable is set to 1; otherwise, it is set to 0 (zero). Your program should check this variable after each READ command.

If STATUS is specified, SQR returns 0 if the read is successful; otherwise, it returns the value of *errno*, which is system-dependent.

Parameters

Parameter	Description
filenum_lit _var _col	Specifies the number assigned in the OPEN command to the file to be read.
any_var:length_int_lit	Specifies one or more variables into which data from the record read are to be put. <i>length_int_lit</i> specifies the length of each field of data.
STATUS	Specifies an optional variable into which a read status is returned.

Example

The following example shows several READ commands:

```
read 1 into $name:30 $addr:30 $city:20 $state:2 $zip:5
read 3 into $type:2 #amount:2 #rate:1 $code:5 $date:11
read #j into #sequence:2 $name:20 $title:15
```

The following example shows a READ command that reads two dates. One is loaded into a date variable; the other is loaded into a string variable, which is then converted to a date using the strtodate function.

```
.
.
.
declare-variable
  date $date1 $date2
  text $text
end-declare
.
.
.
read 4 into $date1:18 $text1:18
let $date2 = strtodate($text1,'YYYYMMDDHHMISSNNN')
      or
let $date2 = strtodate($text1)
```

The following example shows a READ command with an INSERT loop:

```
begin-sql
  begin transaction
end-sql

while 1    ! Infinite loop, exited by BREAK, below.
  read 10 into $company:40 $parent:30 $location:50
  if #end-file
    break    ! End of file reached.
  end-if
  begin-sql
    insert into comps (name, parent, location)
```

```
        values ($company, $parent, $location)
end-sql
add 1 to #inserts
if #inserts >= 100
    begin-sql
        end transaction;
        begin transaction
    end-sql
    move 0 to #inserts
end-if
end-while

begin-sql
    end transaction
end-sql
```

See Also

The OPEN, CLOSE, and WRITE commands for information about files.

ROLLBACK

Syntax

ROLLBACK

Description

An automatic rollback is performed whenever SQR ends due to program errors. ROLLBACK is useful in testing or in certain error conditions.

ROLLBACK is an SQR command and should not be used inside an SQL paragraph.

Note. The ROLLBACK command can be used with DB2, Informix, ODBC, and Oracle (Microsoft SQL Server is accessible only with SQR Server for ODBC.) For Sybase and Microsoft SQL Server, use BEGIN TRANSACTION and ROLLBACK TRANSACTION within SQL paragraphs as in the following example. See the COMMIT command for an example of ROLLBACK.

Example

```
if #error-status = 1
    rollback
    stop
end-if
```

See Also

The COMMIT command.

SBTOMBS

Syntax

SBTOMBS { *txt_var* }

Description

Converts a single-byte character into a multibyte equivalent.

This command converts the specified string as follows: Any occurrence of a single-byte character that also has a multibyte representation (numerals, punctuation, roman characters and katakana) is converted. This command also converts a sequence of a kana character followed by certain grammatical marks into a single multibyte character, which combines the two elements.

Parameters

Parameter	Description
txt_var	Specifies the string to be converted.

See Also

The TO_MULTI_BYTE function of the LET command.

SECURITY

Syntax

SECURITY

[SET=(sid [,sid]...)]

[APPEND=(sid [,sid]...)]

[REMOVE=(sid [,sid]...)]

[MODE=mode]

Description

Enables you to mark sections of a report for security purposes.

The SECURITY command can be repeated as many times as desired for the current report. After the SECURITY command is executed, all subsequent commands for the current report are constrained by the designated *sids* until the report ends or another SECURITY command executes.

You can use the SECURITY command wherever you use the PRINT command.

Parameters

Parameter	Description
SET	Sets the list of security IDs for subsequent commands. The previous list of security IDs is replaced by the specified security IDs. This argument is optional and can only be used once.
<i>sid</i>	Can be any string literal, column, or variable. The value is case-sensitive.
APPEND	Appends the specified security IDS to the current list. This argument is optional and can be used multiple times.
REMOVE	Removes the specified security IDS from the current list. This argument is optional and can be used multiple times.
MODE	Used to turn on (reactivate) or turn off (suspend) the security feature for the current report. This argument is optional and can only be used once.
<i>mode</i>	Can be any string literal, column, or variable. The value is not case-sensitive and can be either ON or OFF.

Example

```

Begin-Report
  Security Set=('Directors', 'Vice-Presidents')
  .
  .      ! Only Directors and VPS can see this
  .
  Security Remove=('Directors')
  .
  .      ! Only VPS can see this
  .
  Security Mode='Off'
  .
  .      ! Anybody can see this
  .
  Security Mode='On' Append=('Managers')
  .
  .      ! Only VPs and Managers can see this
  .
  Security Append=('Engineers')
  .
  .      ! Only VPs, Managers, and Engineers can see this
  .
End-report

```

SET-COLOR

Syntax

SET-COLOR

```

[PRINT-TEXT- FOREGROUND=({color_name_lit|_var|_col|{rgb}})]
[PRINT-TEXT- BACKGROUND=({color_name_lit|_var|_col|{rgb}})]

```

Description

Defines default colors.

The SET-COLOR command is allowed wherever the PRINT command is allowed. If the specified color name is not defined, SQR uses the settings for the color name 'default.' Use the color name 'none' to turn off color for the specified area.

Parameters

Parameter	Description
PRINT-TEXT- FOREGROUND	Defines the color in which the text is printed.
PRINT-TEXT-BACKGROUND	Defines the color to print as a background behind the text.
{color_name_lit _var _col}	A <i>color_name</i> is composed of the alphanumeric characters (A-Z, 0-9), the underscore (_) character, and the hyphen (-) character. It must start with an alphabetical (A-Z) character. It is case-insensitive. The name 'none' is reserved and cannot be assigned a value. A name in the format (RGBredgreenblue) cannot be assigned a value. The name 'default' is reserved and may be assigned a value. 'Default' is used during execution when a referenced color is not defined in the runtime environment.
{rgb}	<i>red_lit _var _col, green_lit _var _col, blue_lit _var _col</i> where each component is a value in the range of 000 to 255. In the BEGIN-SETUP section, only literal values are allowed. The default colors implicitly installed with SQR include: black=(0,0,0) white=(255,255,255) gray=(128,128,128) silver=(192,192,192) red=(255,0,0) green=(0,255,0) blue=(0,0,255) yellow=(255,255,0) purple=(128,0,128) olive=(128,128,0) navy=(0,0,128) aqua=(0,255,255) lime=(0,128,0) maroon=(128,0,0) teal=(0,128,128) fuchsia=(255,0,255)

Example

```
begin-setup
  declare-color-map
    light_blue = (193, 222, 229)
  end-declare
end-setup

begin-program
  alter-color-map name = 'light_blue' value = (193, 233, 230)

  print 'Yellow Submarine' ()
```

```

foreground = ('yellow')
background = ('light_blue')

get-color print-text-foreground = ($print-foreground)
set-color print-text-foreground = ('purple')
print 'Barney' (+1,1)
set-color print-text-foreground = ($print-foreground)
end-program

```

See Also

The DECLARE-COLOR-MAP, ALTER-COLOR-MAP, and GET-COLOR commands in this section.

SET-GENERATIONS

Syntax

SET-GENERATIONS=(*dimension, hierarchy, dimension, hierarchy, dimension, hierarchy, ..., ...*)

Description

Specifies dimension hierarchy for the previously declared dimension.

Returns the set of members in the dimension 'product' that are at the 5th generation in the dimension's hierarchy. (Returns all 'Brand Name' members (Generation Level 5) under the product hierarchy of 'all products.drink.alcoholic beverages.beer and wine.' This would increase the result set to a list of beers and wines.) Returns the set of members in the dimension 'time' that are at the 1st generation deep into the dimension. (Returns all 'Year' members (Generation Level 1) under the time hierarchy of '2004.Q1.2'. This reduces result set to '2004'.)

Example

```
set-generations=('product',5,'time',1 )
```

SET-LEVELS

Syntax

Set-levels=(*dimension, level, dimension, level, ..., ...*)

Description

Extends the dimension hierarchy for the previously declared dimension.

Set-levels used with only the previous 'set-members', returns all members under the product hierarchy and the next two generations (Product SubCategory and Brand Name) for the product hierarchy of all products.drink.alcoholic beverages.beer and wine'. Set-levels used with the previous 'set-members' and 'set-generations', returns all members for generation levels 5 through 7 under the product hierarchy of all products.drink.alcoholic beverages.beer and wine.'

Example

```
set-levels=('product',2 )
```

SET-MEMBERS

Syntax

```
set-members=(dimension, hierarchy, dimension, hierarchy,..., ...)
```

Description

Returns the set of members in a dimension, level, or hierarchy whose name is specified by a string.

Returns the set of members in the dimension 'product' at the specific hierarchy of 'all products', at a specific level of 'drink', at a specific level of 'alcoholic beverages', at a specific level of 'beer and wine'. Returns the set of members in the dimension 'time' at the specific hierarchy of '2004', at the specific level of 'Q1', at the specific level of '2'.

Example

```
set-members=('product','all products.drink.alcoholic beverages.beer and wine','time','2004.Q1.2')
```

SHOW

Syntax

```
SHOW[cursor_position]  
[CLEAR-SCREEN|CS|CLEAR-LINE|CL][any_lit|_var|_col]  
[EDITedit_mask|NUMBER|MONEY|DATE][BOLD][BLINK]  
[UNDERLINE][REVERSE][NORMAL][BEEP][NOLINE]...
```

Description

Displays one or more variables or literals on the screen. In addition, cursor control is supported for ANSI terminals.

Any number of variables and screen positions can be used in a single command. Each one is processed in sequence.

Screen locations can be indicated by either fixed or relative positions in the format (A,B), where A is the line and B is the column on the screen. A and/or B can also be numeric variables. Relative positions depend on where the previous SHOW command ended. If the line was advanced, the screen cursor is usually immediately to the right of the previously displayed value and one line down.

Fixed or relative cursor positioning can be used only within the boundaries of the terminal screen. Scrolling off the screen using relative positioning, for example (+1,1), is not supported. Instead, use a SHOW command without any cursor position when you want to scroll. Also, you cannot mix SHOW and DISPLAY commands while referencing relative cursor positions.

The SHOW command does not advance to the next line if a cursor location (...), CLEAR-SCREEN, CLEAR-LINE, or BEEP is used. (A SHOW command without any of these arguments automatically advances the line.) To add a line advance, add (+1,1) to the end of the line or use an extra empty SHOW command.

Only ANSI terminals are supported for cursor control, screen blanking, line blanking, and display characteristics.

Dates can be contained in a date variable or column, or a string literal, column, or variable. When displaying a date variable or column, without an edit mask, the date is displayed according to the following rules:

- For DATETIME columns and SQR DATE variables, the format specified by the SQR_DB_DATE_FORMAT setting is used. If this has not been set, the first database-dependent format as listed in the Default Database Formats table is used.

- For DATE columns, the format specified by the SQR_DB_DATE_ONLY_FORMAT setting is used. If this has not been set, the format listed in the Default Database Formats table is used.
- For TIME columns, the format specified by the SQR_DB_TIME_ONLY_FORMAT setting is used. If this has not been set, the format as listed in the TIME Column Formats table is used.

When displaying a date in a string literal, column, or variable using EDIT or DATE, the string must be in the format specified by the SQR_DB_DATE_FORMAT setting, one of the database-dependent formats as listed in the Default Database Formats table, or the database-independent format 'SYMMDD[HH24[MI[SS[NNNNNN]]]]'.

Parameters

Parameter	Description
cursor_position	Specifies the position on the screen to begin the display.
{CLEAR-SCREEN CS}	Clears the screen and sets the cursor position to (1,1).
{CLEAR-LINE CL}	Clears a line from the current cursor position to the end of the line.
{any_lit _var _col}	Specifies the information to be displayed.
EDIT	Shows variables under an edit mask. If the mask contains spaces, enclose it in single quotes. For additional information regarding edit masks, see the PRINT command.
NUMBER	Indicates that any_lit _var _col is to be formatted using the NUMBER-EDIT- MASK from the current locale. (See the ALTER-LOCALE command.) This option is not legal for date variables.
MONEY	Indicates that any_lit _var _col is to be formatted using the MONEY-EDIT- MASK from the current locale. (See the ALTER-LOCALE command.) This option is not legal for date variables.
DATE	Indicates that any_lit _var _col is to be formatted using the DATE-EDIT-MASK from the current locale. (See the ALTER-LOCALE command.) This option is not legal for numeric variables. If DATE-EDIT-MASK has not been specified, then the date is displayed using the default format for that database (see the Default Database Formats table).
BOLD, BLINK, UNDERLINE, and REVERSE	Changes the display of characters on terminals that support those characteristics. Some terminals support two or more characteristics at the same time for the same text. To turn all special display characteristics off, use NORMAL.
NORMAL	Turns off all special display characteristics set with BOLD, BLINK, UNDERLINE, and REVERSE.
BEEP	Causes the terminal to beep.
NOLINE	Inhibits a line advance.

Example

The following program segments illustrate the various features of the SHOW command:

```
!
! Show a string using an edit mask
!
let $ssn = '123456789'
```

```
show $ssn edit xxx-xx-xxxx
```

Produces the following output:

```
123-45-6789
```

```
!
! Show a number using an edit mask
!
show 1234567.89 edit 999,999,999.99
```

Produces the following output:

```
1,234,567.89
```

```
!
! Show a number using the default edit mask
!
show 123.78
```

Produces the following output:

```
123.780000
```

```
!
! Show a number using the locale default numeric edit mask
!
alter-locale number-edit-mask = '99,999,999.99'
show 123456.78 number
```

Produces the following output:

```
123,456.78
```

```
!
! Show a number using the locale default money edit mask
!
alter-locale money-edit-mask = '$$, $$$, $$8.99'
show 123456.78 money
```

Produces the following output:

```
$123,456.78
```

```
!
! Show a date column using the locale default date edit mask
!
begin-select
dcol
  from tables
end-select
alter-locale date-edit-mask = 'DD-Mon-YYYY'
```

```
show &dc01 date
```

Produces the following output:

```
01-Jan-2004
```

```
!
! Show two values on the same line
!
show 'Hello' ' World'
```

Produces the following output:

```
Hello World
```

```
!
! Show two values on the same line with editing of the values
!
let #taxes = 123456.78
show 'You owe ' #taxes money ' in back taxes.'
```

Produces the following output:

```
You owe $123,456.78 in back taxes.
```

The following program illustrates the usage of additional options of the SHOW command. Only terminals that support the ANSI escape characters can use the cursor control, screen blanking, line blanking and display attributes.

```
begin-program
!
! Produces a menu for the user to select from
!
show clear-screen
  (3,30) bold 'Accounting Reports for XYZ Company' normal
  (+2,10) '1. Monthly Details of Accounts'
  (+1,10) '2. Monthly Summary'
  (+1,10) '3. Quarterly Details of Accounts'
  (+1,10) '4. Quarterly Summary'

!
! Show a line of text and numerics combined
!
show (+2,1)
  'The price is ' #price edit 999.99

  '      Total = ' #total edit 99999.99

!
! Put an error message on a particular line
!
show (24,1) clear-line 'Error in SQL. Please try again.' beep
end-program
```


See Also

The LET command for information about copying, editing, or converting fields.

The EDIT parameter of the PRINT command for a description of the edit masks.

The ALTER-LOCALE command for a description of the arguments NUMBER-EDIT-MASK, MONEY-EDIT-MASK, and DATE-EDIT-MASK.

The DISPLAY command.

STOP**Syntax**

STOP [QUIET]

Description

The STOP command halts SQR and executes a ROLLBACK command (not in Sybase, Microsoft SQL Server, or Informix). All report page buffers are flushed, if they contain data; however, no headers or footers are printed and the AFTER-PAGE and AFTER-REPORT procedures are not executed.

STOP is useful in testing.

Parameters

Parameter	Description
QUIET	Causes the report to complete with the "SQR: End Of Run" message, instead of ending with an error message.

Example

```

if #error-status = 1
    rollback
    stop
else
    commit
    stop quiet
end-if

```

STRING**Syntax**

STRING {*src_any_lit|_var|_col*}...BY {*delim_txt_lit|_var|_col*}
 INTO *dst_txt_var*

Description

Concatenates a list of variables, columns, or literals into a single text variable. Each member of the list separated by the specified delimiter string.

The destination string must not be included in the list of source strings.

Parameters

Parameter	Description
{src_any_lit _var _col}	Specifies one or more fields to be concatenated, separated by the <i>delim_txt_lit _var _col</i> character or characters, and placed into the <i>dst_txt_var</i> variable. If the source is a date variable or column, it is converted to a string according to the following rules: For DATETIME columns and SQR DATE variables, the format specified by the SQR_DB_DATE_FORMAT setting is used. If this has not been set, the first database-dependent format as listed in the Default Database Formats table is used. For DATE columns, the format specified by the SQR_DB_DATE_ONLY_FORMAT setting is used. If this has not been set, the format listed in the Default Database Formats table is used. For TIME columns the format specified by the SQR_DB_TIME_ONLY_FORMAT setting is used. If this has not been set, the format as listed in the TIME Column Formats table is used.
{delim_txt_lit _var _col}	Specifies one or more characters to be used as separator characters between the source fields.
dst_txt_var	Specifies the destination field for the concatenated result.

Example

```

string &name &city &state &zip by ' - ' into $show-info
! Result: Sam Mann - New York - NY - 11287
string &cust_num &entry-date &total by ',' into $cust-data
! Result: 100014,12-MAR-04,127
! Use null delimiter.
string &code1 &code2 &code3 by '' into $codes123
! Result: AGL

```

See Also

The UNSTRING command for additional information.

The "||" concatenation operator in the Operators table under the LET command.

SUBTRACT

Syntax

```
SUBTRACT {src_num_lit|_var|_col} FROM dst_num_var[ROUND=nn]
```

Description

SUBTRACT subtracts the first value from the second and moves the result into the second field.

When dealing with money-related values (dollars and cents), use decimal variables rather than float variables. Float variables are stored as double precision floating point numbers, and small inaccuracies can appear when subtracting many numbers in succession. These inaccuracies can appear due to the way floating point numbers are represented by different hardware and software implementations.

Parameters

Parameter	Description
{src_num_lit _var _col}	Is subtracted from the contents of <i>dst_num_var</i> .
dst_num_var	Contains the result after execution.
ROUND	Rounds the result to the specified number of digits to the right of the decimal point. For float variables this value can be from 0 to 15. For decimal variables, this value can be from 0 to the precision of the variable. For integer variables, this argument is not appropriate.

Example

```
subtract 1 from #total      ! #total - 1
subtract &discount from #price ! #price - &discount
```

See Also

The ADD command for more information.

The LET command for information about complex arithmetic expressions.

TOC-ENTRY

Syntax

TOC-ENTRY

TEXT={src_txt_lit|_var|_col}

[LEVEL={level_num_lit|_var|_col}]

Description

Enter the text in the table of contents at the desired level.

Parameters

Parameter	Description
TEXT	Specifies the text to be placed in the table of contents.
LEVEL	Specifies the level at which to place the text. If this argument is not specified, the value of the previous level is used.

Example

```
toc-entry text = &heading
toc-entry text = &caption level=2
```

See Also

The DECLARE-TOC command.

UNSTRING

Syntax

UNSTRING {{src_txt_lit|_var|_col}}|{{src_date_var|_col}}

```
BY {delim_txt_lit|_var|_col}
INTO dst_txt_var...
```

Description

Copies portions of a string into one or more text variables.

Each substring is located using the specified delimiter. The source string must not be included in the list of destination strings.

If more destination strings than substrings are found in the source strings, the extra destination strings are each set to an empty string.

If more substrings are found in the source string than in the destination strings, the extra substrings are not processed. It is up to the programmer to ensure that enough destination strings are specified.

If the source is a date variable or column, it is converted to a string according to the following rules:

- For DATETIME columns and SQR DATE variables, the format specified by the SQR_DB_DATE_FORMAT setting is used. If this has not been set, the first database-dependent format as listed in the Default Database Formats table is used.
- For DATE columns, the format specified by the SQR_DB_DATE_ONLY_FORMAT setting is used. If this has not been set, the format listed in the Default Database Formats table is used.
- For TIME columns, the format specified by the SQR_DB_TIME_ONLY_FORMAT setting is used. If this has not been set, the format as listed in the TIME Column Formats table is used.

Parameters

Parameter	Description
{src_txt_lit _var _col} {src_date_var _col}	Specifies the source field to be parsed.
delim_txt_lit _var _col	Specifies one or more characters to be used to delimit the fields within {src_txt_lit _var _col} {src_date_var _col}
dst_txt_var	Specifies one or more destination fields to receive the results.

Example

```
unstring $show-info by ' - ' into $name $city $state $zip
unstring $cust-data by ', ' into $cust_num $entry-date $total
```

See Also

The STRING and EXTRACT commands.

The substr and instr functions in the Miscellaneous Functions table under the LET command.

UPPERCASE

Syntax

```
UPPERCASE txt_var
```

Description

Converts a string variable to uppercase.

Parameters

Parameter	Description
txt_var	Specifies the field to be converted to uppercase.

Example

```
input $state 'Enter state abbreviation'
uppercase $state ! Force uppercase.
```

See Also

The upper function in the Miscellaneous Functions table under the LET command.

USE

Syntax

USE *database*

Description

Uses the named database, rather than the default database associated with your username. (Sybase and Microsoft SQL Server only)

Use USE in the SETUP section only. When used, it must appear at the top of your report, before any queries are defined.

To reference more than one database in a program, specify secondary databases explicitly. For example:

```
from sqdb.sqr.customers
```

You cannot issue the Sybase or Microsoft SQL Server USE command from within an SQL paragraph.

Parameters

Parameter	Description
database	Specifies the name of the database to use.

Example

```
begin-setup
  use pubs
end-setup
```

USE-COLUMN

Syntax

USE-COLUMN {*column_number_int_lit|_var|_col*}

Description

Sets the current column.

The column must be previously defined with the COLUMNS command.

To stop printing within columns, use a column number of 0 (zero). Printing returns to normal; however, the columns remain defined for subsequent NEXT-COLUMN or USE-COLUMN commands.

Parameters

Parameter	Description
{column_number_int_lit _var _col}	Specifies the number of the defined column (not the location on the page). For example, if five columns are defined, the <i>column_number_int_lit _var _col</i> can be 1 to 5.

Example

```
use-column 3      ! Print total in 3rd column.
print #total  ( ) 999,999
use-column 0      ! End of column printing.
```

USE-PRINTER-TYPE

Syntax

USE-PRINTER-TYPE *printer-type*

Description

Sets the printer type to be used for the current report.

The USE-PRINTER-TYPE command sets or alters the printer type to be used for the current report. The USE-PRINTER-TYPE command must appear before the first output is written to that report. If output has already been written to the report file, the USE-PRINTER-TYPE command is ignored.

Parameters

Parameter	Description
printer-type	Specifies the printer type to be used for the current report. See DECLARE-PRINTER for valid types.

Example

```
use-report customer_orders
use-printer-type PostScript
print (1, 1) 'Customer Name: '
print ( ) $customer_name
```

See Also

The DECLARE-PRINTER, DECLARE-REPORT, and USE-REPORT commands.

USE-PROCEDURE

Syntax

USE-PROCEDURE

```
[FOR-REPORTS=(report_name1[,report_namei]...)]
[BEFORE-REPORT=procedure_name[(arg1[,argi]...)]]
[AFTER-REPORT=procedure_name[(arg1[,argi]...)]]
[BEFORE-PAGE=procedure_name[(arg1[,argi]...)]]
[AFTER-PAGE=procedure_name[(arg1[,argi]...)]]
```

Description

Changes the procedure usage.

The USE-PROCEDURE must be issued in the PROGRAM or PROCEDURE sections of an SQR program. USE-PROCEDURE is a runtime command; its compile-time equivalent is DECLARE-PROCEDURE. You can use the command as often as required to change to the necessary procedures required by the reports. If you issue multiple USE-PROCEDURE commands, each remains in effect for that report until altered by another USE-PROCEDURE command for that report. In this way, you can use one to change common procedures for ALL reports and others to change unique procedures for individual reports. The referenced procedures can accept arguments.

If no FOR-REPORTS is specified, ALL is assumed. Initially, the default for each of the four procedure types is NONE. If a procedure is defined in one DECLARE-PROCEDURE for a report, that procedure is used unless NONE is specified.

You can change the BEFORE-REPORT only before the first output is written to that report, because that causes the BEFORE-REPORT procedure to be executed.

Parameters

Parameter	Description
FOR-REPORTS	Specifies the reports that are to use these procedures. This argument is required only for a program with multiple reports. If you are writing a program that produces a single report, you can ignore this argument.
BEFORE-REPORT	Specifies a procedure to execute at the time of execution of the first command, which causes output to be generated. You can use the command, for example, to create a report heading.
AFTER-REPORT	Specifies a procedure to execute just before the report file is closed at the end of the report. This argument can be used to print totals or other closing summary information. If no report was generated, the procedure does not execute.
BEFORE-PAGE	Specifies a procedure to execute at the beginning of every page, just before the first output command for the page. It can be used, for example, to set up page totals.
AFTER-PAGE	Specifies a procedure to execute just before each page is written to the file. This argument can be used, for example, to display page totals. You can also specify arguments to be passed to the procedure. Arguments can be any variable, column, or literal.

Example

```
use-procedure           ! These procedures will
                        ! be used by all reports
for-reports=(all)
before-report=report_heading
```

```

after-report=report_footing
use-procedure           ! These procedures will

for-reports=(customer)  ! be used by the customer

before-page=page_setup  ! report

after-page=page_totals
use-procedure           ! The after-report

for-reports=(summary)   ! procedure will be

after-report=none       ! disabled for the

                        ! summary report

```

See Also

The DECLARE-PROCEDURE command.

USE-REPORT

Syntax

```
USE-REPORT {report_name_lit|_var|_col}
```

Description

For programs with multiple reports, enables the user to switch between reports.

The USE-REPORT command specifies to which report files the subsequent report output is to be written. An application can contain several USE-REPORT statements to control several reports.

You must specify the report name and report characteristics in a DECLARE-REPORT paragraph and in the associated DECLARE-LAYOUT and DECLARE- PRINTER paragraphs.

Parameters

Parameter	Description
{report_name_lit _var _col}	Specifies the report to become the current report. All subsequent PRINT and PRINT-DIRECT statements are written to this report until the next USE- REPORT is encountered.

Example

```

use-report customer_orders
use-printer-type PostScript
print (1, 1) 'Customer Name: '
print () $customer_name

```


See Also

The DECLARE-REPORT, DECLARE-LAYOUT, DECLARE-PRINTER, and USE-PRINTER-TYPE commands.

WHILE**Syntax**

```
WHILE logical_expression
```

The general format of a WHILE command is as follows:

```
WHILE logical_expression
SQR_commands...
[BREAK]
SQR_commands...
END-WHILE
```

Description

Begins a **WHILE ... END-WHILE** loop.

The WHILE loop continues until the condition being tested is FALSE.

An expression returning 0 (zero) is considered FALSE; an expression returning nonzero is TRUE.

BREAK causes an immediate exit of the WHILE loop; SQR continues with the command immediately following END-WHILE.

WHILE commands can be nested to any level and can include or be included within IF and EVALUATE commands.

Parameters

Parameter	Description
logical_expression	A valid logical expression. See the LET command for a description of logical expressions.

Example

The following example shows an IF nested within a WHILE:

```
while #count < 50
  do get_statistics
  if #stat_count = 100
    break      ! Exit WHILE loop.
  end-if
  add 1 to #count
end-while
```

You can use single numeric variables in your expression to make your program more readable, for example when using flags:

```
move 1 to #have_data
...
while #have_data
```

```

    ...processing...
end-while

```

The following example sets up an infinite loop:

```

while 1
    ...processing...
    if ...
        break      ! Exit loop
    end-if
end-while

```

Any complex expression can be used in the WHILE command, as shown in the following example:

```

while #count < 100 and (not #end-file or isnull(&state))
    ...
end-while

```

See Also

The LET command for a description of expressions.

WRITE

Syntax

```

WRITE {filenum_lit|_var|_col} FROM
{{{txt_lit|_var|_col}|{date_var|_col}|num_col}
[:len_int_lit]}|{num_lit|_var:len_int_lit}}...
[STATUS=status_num_var]

```

Description

Writes a record to a file from data stored in variables, columns, or literals.

The file must already be opened for writing.

If length is specified, the variable is either truncated at that length or padded with spaces to that length. If length is not specified (for string variables or database columns), the current length of the variable is used.

When writing numeric variables, the length argument is required. Only 1, 2, or 4 byte binary integers are written. Floating point values are not supported directly in the WRITE command. However, you can first convert floating point numbers to strings and then write the string.

When writing binary data the file must be open using the FIXED or FIXED-NOLF qualifiers. The file is not portable across platforms because binary numbers are represented differently.

When writing a date variable or column, the date is converted to a string according to the following rules:

- For DATETIME columns and SQR DATE variables, the format specified by the SQR_DB_DATE_FORMAT setting is used. If this has not been set, the first database-dependent format as listed in the Default Database Formats table is used.
- For DATE columns, the format specified by the SQR_DB_DATE_ONLY_FORMAT setting is used. If this has not been set, the format listed in the DATE Column Formats table is used.
- For TIME columns, the format specified by the SQR_DB_TIME_ONLY_FORMAT setting is used. If this has not been set, the format as listed in the TIME Column Formats table is used.

Text literals take the length of the literal.

Files opened for writing are treated as having variable-length records. If you need a fixed-length record, specify a length for each variable written to the file.

The total length of the variables and literals being written must not be greater (but can be less) than the record length specified when the file was opened. Records are not padded, but are written with the total length of all variables in the WRITE command.

If STATUS is specified, SQR returns 0 if the write is successful; otherwise, it returns the value of *errno*, which is system-dependent.

Parameters

Parameter	Description
filenum_lit _var _col	Specifies the number assigned in the OPEN command to the file to be written.
{{txt_lit _var _col} {date_var _col} num_col} [:len_int_lit]} {num_lit _var:len_int_lit}	Specifies one or more variables to be written. <i>len_int_lit</i> specifies the length of each field of data.
STATUS	Specifies an optional variable into which a write status is returned.

Example

```

write 5 from $name:20 $city:15 $state:2
write 17 from $company ' - ' $city ' - ' $state ' ' $zip
write #j2 from #rate:2 #amount:4 #quantity:1
move #total to $tot 99999.99          ! Convert floating point to string.
write 1 from $tot
let $date1 = datenow()                ! Put the current date and time
                                       ! into DATE variable

write 3 from $date1:20

```

See Also

The OPEN, CLOSE, and READ commands.

CHAPTER 3

Generating HTML Output

This chapter describes the procedures that enable SQR for PeopleSoft to generate HTML output. You can publish the output on an internet, intranet, or extranet website. An SQR program without HTML procedures has limited HTML capabilities. Adding HTML procedures to the SQR program enhances the appearance of the HTML output.

This chapter discusses:

- HTML general-purpose procedures
- HTML heading procedures
- HTML highlighting procedures
- HTML hypertext link procedures
- HTML list procedures
- HTML table procedures

See Also

Enterprise PeopleTools 8.45 PeopleBook: SQR for PeopleSoft Developers, “Generating and Publishing HTML from an SQR Program”

HTML General Purpose Procedures

The following table lists the HTML general-purpose procedures:

Procedure	Description
html_br	Produces the specified number of line breaks in a paragraph by using the HTML
 tag. The paragraph continues onto the next line. Syntax: <pre>html_br(number count, string attributes)</pre> count: The number of HTML
 tags that are inserted. attributes: The HTML attributes that are incorporated inside the HTML
 tag. Example: <pre>print 'Here is some text' () do html_br(3, '') print 'Here is some text three lines down' ()</pre>
html_center	Marks the start of text to be centered on the HTML document by using the HTML <CENTER> tag. You can also accomplish this by using the SQR print statement with CENTER specified in the code. Syntax: <pre>html_center()</pre> attributes: The HTML attributes that are incorporated inside the HTML <CENTER> tag. Example: <pre>do html_center('') print 'Here is some centered text' () do html_center_end</pre>
html_center_end	Marks the end of text that was previously specified as centered. Syntax: <pre>html_center_end</pre>
html_hr	Produces a horizontal divider between sections of text by using the HTML <HR> tag. Syntax: <pre>html_hr(string attributes)</pre> attributes: The HTML attributes that are incorporated inside the HTML <HR> tag. Example: <pre>print 'Here is some text' () do html_hr('') print 'Text after a horizontal divider' ()</pre>

Procedure	Description
html_img	Inserts an image by using the HTML tag. You can also do this by using the PRINT-IMAGE command; however, the html_img procedure enables you to specify the full set of available HTML attributes. Syntax: <pre>html_img(string attributes)</pre> attributes: The HTML attributes that are incorporated inside the HTML tag. Some common attributes include: • src: The URL of the image to be inserted. Example: src=/images/abc.gif • height: The height of the image in pixels. Example: height=200 • width: The width of the image in pixels. Example: width=400 Example: <pre>do html_img('src="/images/stop.gif"')</pre>
html_nobr	Marks the start of text that cannot be wrapped by using the HTML <NOBR> tag. Syntax: <pre>html_nobr</pre> Example: <pre>do html_nobr('') print 'Long line of text that should't wrap' () do html_nobr_end</pre>
html_nobr_end	Marks the end of text that cannot be wrapped by using the HTML </NOBR> tag. Syntax: <pre>html_nobr_end</pre>
html_on	Activates the HTML procedures. Call this procedure at the start of an SQR program; otherwise, the HTML procedures are not activated. After the HTML procedures are activated, format the appearance of the web page by using the various HTML procedures. Syntax: <pre>html_on</pre> Example: <pre>do html_on</pre>

Procedure	Description
html_p	Marks the start of a new paragraph by using the HTML <P> tag. Syntax: <pre>html_p(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <P> tag. A common attribute is align = left right center, which specifies the alignment of the paragraph. Example: <pre>do html_p('ALIGN=RIGHT') print 'Right aligned text' (1,1) do html_p_end print 'Normally aligned text' (+1,1)</pre>
html_p_end	Marks the end of a paragraph by using the HTML </P> tag. The end of a paragraph is typically implied and the procedure is technically not needed; however, it's good practice to specify it for completeness. Syntax: <pre>html_p_end</pre>

Procedure	Description
html_set_body_attributes	Specifies the attributes that are incorporated into the HTML <BODY> tag. Call this procedure at the start of the SQR program. Syntax: <pre>html_set_body_attributes(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <BODY> tag. Some common attributes include: - background: Specifies the image to display in the background of the web page. Example: background=/images/logo.gif - bgcolor=#rrggbb: Specifies the background color of the web page. Example: bgcolor=#80FFF Example: <pre>do html_set_body_attributes('BACKGROUND="/images/x.gif"')</pre>
html_set_head_tags	Specifies the tags that are incorporated between the HTML <HEAD> and </HEAD> tags. These are empty by default. One common tag to set is the HTML <TITLE> tag, which specifies the title to display for the web page. Call this procedure at the start of the SQR program. Syntax: <pre>html_set_head_tags(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated between the HTML <HEAD> and </HEAD> tags. Example: <pre>do html_set_head_tags('<TITLE>My Report</TITLE>')</pre>

HTML Heading Procedures

The following table lists the HTML heading procedures:

Procedure	Description
html_h1	Marks the start of text for heading level one by using the HTML <H1> tag. This heading text appears more prominently than heading level two. Syntax: <pre>html_h1(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <H1> tag. Example: <pre>do html_h1('') print 'This is a heading' () do html_h1_end</pre>
html_h1_end	Marks the end of text for heading level one by using the HTML </H1> tag. Syntax: <pre>html_h1_end</pre>
html_h2	Marks the start of text for heading level two by using the HTML <H2> tag. This heading text appears less prominently than heading level one and more prominently than heading level three. Syntax: <pre>html_h2(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <H2> tag. Example: <pre>do html_h2('') print 'This is a heading' () do html_h2_end</pre>
html_h2_end	Marks the end of text for heading level two by using the HTML </H2> tag. Syntax: <pre>html_h2_end</pre>

Procedure	Description
html_h3	Marks the start of text for heading level three by using the HTML <H3> tag. This heading text appears less prominently than heading level two and more prominently than heading level four. Note. This heading level is the default value. Syntax: <pre>html_h3(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <H3> tag.
html_h3_end	Marks the end of text for heading level three by using the HTML </H3> tag. Syntax: <pre>html_h3_end</pre>
html_h4	Marks the start of text for heading level four by using the HTML <H4> tag. This heading text appears less prominently than heading level three and more prominently than heading level five. Syntax: <pre>html_h4(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <H4> tag.
html_h4_end	Marks the end of text for heading level four by using the HTML </H4> tag. Syntax: <pre>html_h4_end</pre>
html_h5	Marks the start of text for heading level five by using the HTML <H5> tag. This heading text appears less prominently than heading level four and more prominently than heading level six. Syntax: <pre>html_h5(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <H5> tag.

Procedure	Description
html_h5_end	Marks the end of text for heading level five by using the HTML </H5> tag. Syntax: <pre>html_h5_end</pre>
html_h6	Marks the start of text for heading level six by using the HTML <H6> tag. This heading text appears less prominently than heading level five. Syntax: <pre>html_h6(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <H6> tag.
html_h6_end	Marks the end of text for heading level six by using the HTML </H6> tag. Syntax: <pre>html_h6_end</pre>

HTML Highlighting Procedures

The following table lists the HTML highlighting procedures:

Procedure	Description
html_blink	Marks the start of blinking style text by using the HTML <BLINK> tag. Syntax: <pre>html_blink(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <BLINK> tag. Example: <pre>do html_blink('') print 'This is blinking text' () do html_blink_end</pre>
html_blink_end	Marks the end of blinking style by using the HTML </BLINK> tag. Syntax: <pre>html_blink_end</pre>

Procedure	Description
html_cite	Marks the start of text in citation style by using the HTML <CITE> tag. Syntax: <pre>html_cite(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <CITE> tag. Example: <pre>do html_cite('') print 'This is a citation' () do html_cite_end</pre>
html_cite_end	Marks the end of text in citation style by using the HTML </CITE> tag. Syntax: <pre>html_cite_end</pre>
html_code	Marks the start of text in code style by using the HTML <CODE> tag. Syntax: <pre>html_code(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <CODE> tag. Example: <pre>do html_code('') print 'Here is code style text' () do html_code_end</pre>
html_code_end	Marks the end of text in code style by using the HTML </CODE> tag. Syntax: <pre>html_code_end</pre>

Procedure	Description
html_kbd	Marks the start of text in keyboard input style by using the HTML <KBD> tag. Syntax: <pre>html_kbd(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <KBD> tag. Example: <pre>do html_kbd('') print 'Here is keyboard style text' () do html_kbd_end</pre>
html_kbd_end	Marks the end of text in keyboard style by using the HTML </KBD> tag. Syntax: <pre>html_kbd_end</pre>
html_samp	Marks the start of text in sample style by using the HTML <SAMP> tag. Syntax: <pre>html_samp(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <SAMP> tag. Example: <pre>do html_samp('') print 'Here is sample style text' () do html_samp_end</pre>
html_samp_end	Marks the end of text in sample style by using the HTML </SAMP> tag. Syntax: <pre>html_samp_end</pre>

Procedure	Description
html_strike	Marks the start of text in strikethrough style by using the HTML <STRIKE> tag. Syntax: <pre>html_strike(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <STRIKE> tag. Example: <pre>do html_strike('') print 'Here is strikethrough text' () do html_strike_end</pre>
html_strike_end	Marks the end of text in strikethrough style by using the HTML </STRIKE> tag. Syntax: <pre>html_strike_end</pre>
html_sub	Marks the start of text in subscript style by using the HTML <SUB> tag. Syntax: <pre>html_sub(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <SUB> tag. Example: <pre>print 'Here is' () do html_sub('') print 'subscript text' () do html_sub_end</pre>
html_sub_end	Marks the end of text in subscript style by using the HTML </SUB> tag. Syntax: <pre>html_sub_end</pre>

Procedure	Description
html_sup	Marks the start of text in superscript style by using the HTML <SUP> tag. Syntax: <pre>html_sup(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <SUP> tag. Example: <pre>print 'Here is' () do html_sup('') print 'superscript text' () do html_sup_end</pre>
html_sup_end	Marks the end of text in superscript style by using the HTML </SUP> tag. Syntax: <pre>html_sup_end</pre>

HTML Hypertext Link Procedures

The following table lists the HTML hypertext link procedures:

Procedure	Description
html_a	Marks the start of a hypertext link by using the HTML <A> tag. When the user clicks the area with the hypertext link, the web browser switches to the specified HTML document. Syntax: <pre>html_a(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <A> tag. At a minimum, you should define the href attribute, which specifies the URL of an HTML document. Some common attributes include: • href: Indicates where the hypertext link points. Example: href=home.html • name: Indicates an anchor to which a hypertext link can point. Example: name=marker1 Example: The anchor is positioned at the top of the document. The first hypertext link points to the HTML document named otherdoc.html. The second hypertext link points to the anchor named TOP. <pre>do html_a('NAME=TOP') do html_a_end print 'At the top of document' () do html_br(20, '') do html_a('HREF=otherdoc.html') print 'Go to other document' () do html_a_end do html_p('') do html_a('HREF=#TOP') print 'Go to top of document' () do html_a_end</pre>
html_a_end	Marks the end of a hypertext link by using the HTML tag. Syntax: <pre>html_a_end</pre>

HTML List Procedures

The following table lists the HTML list procedures:

Procedure	Description
html_dd	Marks the start of a definition in a definition list by using the HTML <code><DD></code> tag. Syntax: <pre>html_dd(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <code><DD></code> tag.
html_dd_end	Marks the end of a definition in a definition list by using the HTML <code></DD></code> tag. The end of a definition in a definition list is typically implied and not needed; however, it's good form to specify it for completeness. Syntax: <pre>html_dd_end</pre>
html_dir	Marks the start of a directory list by using the HTML <code><DIR></code> tag. Syntax: <pre>html_dir(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <code><DIR></code> tag. Example: <pre>do html_dir('') do html_li('') print 'First item' () do html_li('') print 'Second item' () do html_li('') print 'Last item' () do html_dir_end</pre>
html_dir_end	Marks the end of a directory list by using the HTML <code></DIR></code> tag. Syntax: <pre>html_dir_end</pre>

Procedure	Description
html_dl	Marks the start of a definition list by using the HTML <DL> tag. A definition list displays a list of terms and definitions. The term displays above and to the left of the definition. Use the html_dt procedure to display a term. Use the html_dd procedure to display a definition. Syntax: <pre>html_dl(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <DL> tag. Example: <pre>do html_dl('') do html_dt('') print 'A Daisy' () do html_dd('') print 'A sweet and innocent flower.' () do html_dt('') print 'A Rose' () do html_dd('') print 'A very passionate flower.' () do html_dl_end</pre>
html_dl_end	Marks the end of a definition list by using the HTML </DL> tag. Syntax: <pre>html_dl_end</pre>
html_dt	Marks the start of a term in a definition list by using the HTML <DT> tag. Syntax: <pre>html_dt(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <DT> tag.
html_dt_end	Marks the end of a term in a definition list by using the HTML </DT> tag. Syntax: <pre>html_dt_end</pre>
html_li	Marks the start of a list item by using the HTML tag. Syntax: <pre>html_li(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML tag.

Procedure	Description
html_li_end	Marks the end of a list item by using the HTML tag. The end of a list item is typically implied and not needed; however, you should specify it for completeness. Syntax: <pre>html_li_end</pre>
html_menu	Marks the start of a menu by using the HTML <MENU> tag. Use the html_li procedure to identify each item in the list. Syntax: <pre>html_menu(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <MENU> tag. Example: <pre>do html_menu('') do html_li('') print 'First item' () do html_li('') print 'Second item' () do html_li('') print 'Last item' () do html_menu_end</pre>
html_menu_end	Marks the end of a menu by using the HTML </MENU> tag. Syntax: <pre>html_menu_end</pre>
html_ol	Marks the start of an ordered list by using the HTML tag. Each item in the list typically appears indented to the right with a number to the left. Use the html_li procedure to identify each item in the list. Syntax: <pre>html_ol(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML tag. Example: <pre>do html_ol('') do html_li('') print 'First item' () do html_li('') print 'Second item' () do html_li('') print 'Last item' () do html_ol_end</pre>

Procedure	Description
html_ol_end	Marks the end of an ordered list by using the HTML tag. Syntax: html_ol_end
html_ul	Marks the start of an unordered list by using the HTML tag. Each item in the list typically appears indented to the right with a bullet to the left. Use the html_li procedure to identify each item in the list. Syntax: html_ul(string attributes) attributes: defines the HTML attributes that are incorporated inside the HTML tag. Example: do html_ul('') do html_li('') print 'First item' () do html_li('') print 'Second item' () do html_li('') print 'Last item' () do html_ul_end
html_ul_end	Marks the end of an unordered list by using the HTML tag. Syntax: html_ul_end

HTML Table Procedures

The following table lists the HTML table procedures:

Procedure	Description
html_caption	Marks the start of a table caption by using the HTML <CAPTION> tag. Syntax: html_caption(string attributes) attributes: Defines the HTML attributes that are incorporated inside the HTML <CAPTION> tag.
html_caption_end	Marks the end of a table caption by using the HTML </CAPTION> tag. The end of a table caption is typically implied and not needed; however, you should specify it for completeness. Syntax: html_caption_end

Procedure	Description
html_table	Marks the start of a table by using the HTML <TABLE> tag. Syntax: <pre>html_table(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <TABLE> tag. Some common attributes include: • border: Specifies that a border appears around each cell of the table. • width: Specifies the width of the entire table in pixels. • cols: Specifies the number of columns in the table. Example: COLS=4 Example: Displaying database records in a tabular format. The html_caption_end, html_tr_end, html_td_end, and html_th_end procedures are used for completeness; however, they are typically implied and not needed. <pre>! start the table & display the column headings do html_table('border') do html_caption('') print 'Customer Records' (1,1) do html_caption_end do html_tr('') do html_th('') print 'Cust No' (+1,1) do html_th_end do html_th('') print 'Name" (,10) do html_th_end do html_tr_end ! display each record begin-select do html_tr('') do html_td('') cust_num (1,1,6) edit 099999 do html_td_end do html_td('') name (1,10,25) do html_td_end do html_tr_end next-listing skiplines=1 need=1 from customers end-select ! end the table do html_table_end</pre>
html_table_end	Marks the end of a table by using the HTML </TABLE> tag. Syntax: <pre>html_table_end</pre>

Procedure	Description
html_td	Marks the start of a new column in a table row by using the HTML <code><TD></code> tag. This specifies that the text that follows is displayed in the column. Syntax: <pre>html_td(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <code><TD></code> tag.
html_td_end	Marks the end of a column in a table by using the HTML <code></TD></code> tag. The end of a column is typically implied and not needed; however, you should specify it for completeness. Syntax: <pre>html_td_end</pre>
html_th	Marks the start of a new column header in a table row by using the HTML <code><TH></code> tag. This specifies that the text that follows is displayed as the header of the column. Syntax: <pre>html_th(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <code><TH></code> tag.
html_th_end	Marks the end of a column header in a table by using the HTML <code></TH></code> tag. The end of a column header is typically implied and not needed; however, you should specify it for completeness. Syntax: <pre>html_th_end</pre>
html_tr	Marks the start of a new row in a table by using the HTML <code><TR></code> tag. Syntax: <pre>html_tr(string attributes)</pre> attributes: Defines the HTML attributes that are incorporated inside the HTML <code><TR></code> tag.
html_tr_end	Marks the end of a row by using the HTML <code></TR></code> tag. The end of a row in a table is typically implied and not needed; however, you should specify it for completeness. Syntax: <pre>html_tr_end</pre>

CHAPTER 4

Invoking SQR Execute

SQR Execute is a runtime program that enables you to run a previously compiled SQR program.

This chapter discusses how to:

- Run SQR Execute
- Use SQR Execute flags

Running SQR Execute

To run SQR Execute, enter the following command. (If you are using Microsoft Windows, invoke SQRWT rather than SQR.)

```
SQR [program][connectivity][flags...][args...][@file...]
```

Using SQR Execute Flags

The following table describes the SQR Execute command-line flags. See the SQR command-line arguments section for information about program, connectivity, args, and @file.

See [Chapter 1, “Understanding SQR for PeopleSoft,” SQR Command-Line Arguments, page 4](#).

Flag	Description
-A	Appends the output to an existing output file of the same name. If the file does not exist, it creates a new one. This flag is useful when you want to run the same report more than once, but you want to create only one output file.
-C	(Microsoft Windows) Specifies that the Cancel dialog box appears while the program is running so that you can easily terminate the program.

Flag	Description
-BURST:{xx}	Specifies the type of bursting to be performed. -BURST:T generates the table of contents file only. -BURST:S generates the report output according to the symbolic table of contents entries that are set in the program with the TOC- ENTRY command's LEVEL argument. In -BURST:S[{l}], <i>l</i> is the level at which to burst. The -BURST:S setting is equivalent to -BURST:S1. -BURST:P generates the report output by report page numbers. In -BURST:P[{l} , {s} [, {s}] ...], <i>l</i> is the number of logical report pages that each .htm file contains and <i>s</i> is the page selection: <i>n</i>, <i>n</i>-, <i>m</i>, -<i>m</i>, or <i>n</i>-. The -BURST:P setting is equivalent to -BURST:P0,1- when using -PRINTER:HT or -BURST:P1 when using -PRINTER:EH. Note. -BURST:P and -BURST:S require -PRINTER:EH or -PRINTER:HT. The page range selection feature of -BURST:P requires -PRINTER:HT. -BURST:T requires -PRINTER:HT.
-CB	(Microsoft Windows) Forces the communication box.
-Dnn	(Non-Microsoft Windows) Causes SQR to display the report output on the terminal at the same time that it is being written to the output file. The <i>nn</i> is the maximum number of lines to display before pausing. If you don't enter a number after -D, the display scrolls continuously. The printer type must be LP; otherwise, SQR does not display any output. If the program is producing more than one report, the display is for the first report only.
-DBdatabase	(Sybase) Causes the SQR program to use the specified database, overriding any USE command in the SQR program.
-E[file]	Directs error messages to the named file or to the default file, program.err. If no errors occur, no file is created.
-EH_APPLETS:dir	Specifies the directory location of the enhanced HTML applets. The default directory for these applets is IMAGES. Note. The -EH flags in this table are applicable only when either the -PRINTER:EH or -PRINTER:EP flag is specified.

Flag	Description
-EH_BQD	Generates a {report}.bqd file from the report data. Also associates a BQD icon with {report}.bqd in the navigation bar.
-EH_BQD:file	Associates the BQD icon with the specified file.
-EH_BROWSER:xx	Specifies the target browser. When set to ALL, SQR automatically determines which browser is being used, invokes a browser-specific file, and generates HTML that is designed for that browser. When set to BASIC, SQR generates HTML that is suitable for all browsers. When set to IE, SQR generates HTML that is designed for Microsoft Internet Explorer. When set to NETSCAPE, SQR generates HTML that is designed for Netscape.
-EH_CSV	Generates a {report}.csv file from the report data.
-EH_CSV:file	Associates the CSV icon with the specified file.
-EH_CSVONLY	Creates a CSV file, but does not create an HTML file.
-EH_FULLHTML:xx	Switches between HTML 3.0 and HTML 3.2. When set to TRUE, SQR generates HTML 3.2. When set to FALSE, SQR generates HTML 3.0
-EH_Icons:dir	Specifies the directory in which the HTML should find the referenced icons.
-EH_LANGUAGE:xx	Sets the language that is used for the HTML navigation bar. You can specify English, French, German, Portuguese, Spanish, Japanese, Simplified Chinese, Korean.
-EH_PDF	Associates a PDF icon with {report}.pdf in the navigation bar.
-EH_Scale:{nn}	Sets the scaling factor from 50 to 200.

Flag	Description
-F[file directory]	Overrides the default output file name, program.lis. The default action places the program.lis in the same directory as the program.sqr file. To use the current directory, specify -F without an argument. To change the name of the output file, specify -F with the new name. If the new name does not specify a directory, the file is created in the current directory. The output file is not created until data is actually printed on the page. If no data is printed, no output file is created. Specify the file name and directory for different operating systems: • UNIX/Linux • MVS
-GPRINT=YES NO	(MVS) -GPRINT=YES causes ANSI control characters written to the first column of each record of the SQR output file.
-ID	Displays the copyright banner on the console.
-KEEP	In addition to lis files, creates an spf file for each report that the program generates.
-NOLIS	Prevents the creation of lis files. Instead, spf files are created.
-O[file]	Directs log messages to the specified file or to programt.log, if no file is specified. By default, the sqr.log file is used in the current working directory.
-P	(MVS) Suppresses printer control characters from column 1.
-PB	(Informix) Causes column data to retain trailing blanks.

Flag	Description
-PRINTER:xx	Causes printer type <i>xx</i> to be used when creating output files: • EH • EP • HP • HT • LP • PD • PS • WP Types LP, HP, and PS produce files with the .lis extension. Types EH and HT produce .htm file output. Type HT produces files in HTML version 2.0 with the report content inside the <PRE></PRE> tags. Type EH produces reports in which content is fully formatted with HTML version 3.0 or 3.2 tags. On Microsoft Windows systems, the WP extension sends the output to the default Microsoft Windows printer. To specify a nondefault Microsoft Windows printer, enter -PRINTER:WP:{Printer Name}. The {Printer Name} is the name that is assigned to the printer. For example, to send output to a Microsoft Windows printer named NewPrinter, use -PRINTER:WP:NewPrinter. If the printer name has spaces, enclose the entire argument in quotes. If you also want to create an .spf file, use -KEEP.
-S	Requests that the status of all cursors be displayed at the end of the report run. Status includes the text of each SQL statement, the number of times that each was compiled and run, and the total number of rows selected.
-Tnn	Specifies that you want to test the report for <i>nn</i> pages. SQR ignores all Order By clauses in Select statements to save time during testing. If the program is producing more than one report, SQR stops after the specified number of pages that are defined for the first report have been printed.

Flag	Description
-T{B Z BZ ZB}	(IBM MVS and DB2): • -TB prevents SQR from removing trailing blanks from database character columns. • -TZ prevents SQR from removing trailing zeros from the decimal portion of numeric columns. • -TBZ or -TZB prevents both. (Windows/DB2, Sybase CT-Lib, and ODBC): -TB trims trailing blanks from database character columns.
-Vserver	(Sybase) Uses the named server.
-XB	(Non-Microsoft Windows) Suppresses the SQR banner and the <i>SQR.... End of Run</i> message.
-XCB	(Microsoft Windows) Does not use the communication box.
-XL	Prevents SQR from signing in to the database. Programs that are run in this mode cannot contain any SQL statements. -XL enables you to run SQR without accessing the database. You still must supply at least an empty slash (/) on the command line as a placeholder for the connectivity information. For example: <code>sqr myprog / -xl</code> Some database files must be available for SQR to run whether SQR signs in to the database or not. See information about your particular operating system and database to determine which files you need.
-XMB	(Microsoft Windows) Disables the error message display so that a program can be run without interruption by error message boxes. Error messages are sent only to an .err file. See the -E flag for more information.
-XNAV	Prevents SQR from creating the navigation bar in .htm files that are generated with -PRINTER:HT. This occurs when only a single .htm file is produced. Multiple .htm files that are generated from a single report always contain the navigation bar.
-XP	(Sybase DBLib) Prevents SQR from creating temporary stored procedures. See BEGIN-SELECT for more information.

Flag	Description
-XTB	Preserves the trailing blanks in an .lis file at the end of a line.
-XTOC	Prevents SQR from generating the table of contents for the report. SQR ignores this flag when -PRINTER:EH or - PRINTER:HT is also specified.
-ZIF{file}	Sets the full path and name of the SQR initialization file, sqr.ini.
-ZIV	Invokes the SPF Viewer after generating the program.spf file. This flag implicitly invokes the -KEEP flag to create program.spf. In the case of multiple output files, only the first report file is passed to the viewer.
-ZMF{file}	Specifies the full path and name of the SQR error message file, sqrrr.dat.

See Also

Chapter 1, “Understanding SQR for PeopleSoft,” SQR Command-Line Arguments, page 4

CHAPTER 5

Using SQR Print

This chapter provides an overview of SQR Print and discusses how to:

- Generate output from the command line.
- Use SQR Print command-line flags.
- Generate output in Microsoft Windows.

Understanding SQR Print

SQR Print enables you to create printer-specific reports for any of the file types that are supported by SQR. SQR Print converts portable printer-independent files (spfs) into printer-specific files. SQR and SQRT (or SQRWT, for Windows) create spf files when you use the -KEEP and -NOLIS command-line flags.

Generating Output from the Command Line

To begin running SQR Print, enter the following command. (If you are in Microsoft Windows, invoke SQRWP rather than SQRP.)

```
SQRP [spf-file] [flags...]
```

The following table describes *spf-file* and *flags*.

SQR Print writes an lis file with the same name as the spf file, but with the lis extension. You can override this name with the -F command-line flag.

The -PRINTER command-line flag specifies the printer type. SQR offers several options:

- Line printer
- HP LaserJet
- PostScript
- HTML
- Enhanced HTML
- Adobe PDF
- Enhanced HTML and Adobe PDF

If the report contains graphics and you select a line printer, SQR Print ignores graphic elements (such as lines, boxes, and charts) and prints only text.

Using SQR Print Command-Line Flags

The following table describes the SQR Print command-line flags:

Flag	Description
-A	Appends the output to an existing output file of the same name. If the file does not exist, it creates a new one. This flag is useful when you want to run the same report more than once, but you want to create only one output file.
-BURST:{xx}	Specifies the type of bursting to be performed. -BURST:T generates the table of contents file only. -BURST:S generates the report output according to the symbolic table of contents entries that are set in the program with the TOC-ENTRY command's LEVEL argument. In -BURST:S[{l}], <i>l</i> is the level at which to burst. The -BURST:S setting is equivalent to -BURST:S1. -BURST:P generates the report output by report page numbers. In -BURST:P[{l} , {s} [, {s}] ...] , <i>l</i> is the number of logical report pages that each .htm file contains and <i>s</i> is the page selection: {<i>n</i>}, {<i>n</i>}-{<i>m</i>}, -{<i>m</i>}, or <i>n</i>-. The -BURST:P setting is equivalent to -BURST:P0,1- when using -PRINTER:HT or -BURST:P1 when using -PRINTER:EH. Note. -BURST:P and -BURST:S require -PRINTER:EH or -PRINTER:HT. The page range selection feature of -BURST:P requires -PRINTER:HT. BURST:T requires -PRINTER:HT.
-Dnn	(Non-Microsoft Windows) Displays the report output on the terminal at the same time that it is being written to the output file. The <i>nn</i> is the maximum number of lines to display before pausing. If you don't enter a number after -D, the display scrolls continuously. The printer type must be LP or the display is ignored. If the program is producing more than one report, the display is for the first report only.
-E[file]	Directs error messages to the named file or to the default file, program.err. If no errors occur, no file is created. Note. The following -EH flags are applicable only when either the -PRINTER:EH or -PRINTER:EP flag is specified.

Flag	Description
-EH_APPLETS:dir	Specifies the directory location of the enhanced HTML applets. The default directory for these applets is IMAGES.
-EH_BQD	Generates a {report}.bqd file from the report data. Also associates a BQD icon with {report}.bqd in the navigation bar.
-EH_BQD:file	Associates the BQD icon with the specified file.
-EH_BROWSER:xx	Specifies the target browser. When set to ALL, SQR automatically determines which browser is being used, invokes a browser-specific file, and generates HTML that is designed for that browser. When set to BASIC, SQR generates HTML that is suitable for all browsers. When set to IE, SQR generates HTML that is designed for Microsoft Internet Explorer. When set to NETSCAPE, SQR generates HTML that is designed for Netscape.
-EH_CSV	Generates a {report}.csv file from the report data.
-EH_CSV:file	Associates the CSV icon with the specified file.
-EH_CSVONLY	Creates a CSV file, but does not create an HTML file.
-EH_FULLHTML:xx	Switches between HTML 3.0 and HTML 3.2. When set to TRUE, SQR generates HTML 3.2. When set to FALSE, SQR generates HTML 3.0
-EH_Icons:dir	Specifies the directory in which the HTML should find the referenced icons.
-EH_LANGUAGE:xx	Sets the language that is used for the HTML navigation bar. You can specify English, French, German, Portuguese, Spanish, Japanese, Simplified Chinese, or Korean.
-EH_PDF	Associates a PDF icon with {report}.pdf in the navigation bar.

Flag	Description
-EH_Scale:{nn}	Sets the scaling factor from 50 to 200.
-F[file directory]	Overrides the default output file name, program.lis. The default action places program.lis in the same directory as the program.sqr file. To use the current directory, specify -F without an argument. To change the name of the output file, specify -F with the new name. If the new name does not specify a directory, the file is created in the current directory. The output file is not created until data is actually printed on the page. If no data is printed, no output file is created. Specify these file names and directories for different operating systems: • UNIX\Linux • MVS
-ID	Displays the copyright banner on the console.
-O[file]	Directs log messages to the specified file or to programt.log if no file is specified. By default, the sqr.log file is used in the current working directory.
-P	(IBM MVS) Suppresses printer control characters from column 1.

Flag	Description
-PRINTER:xx	Causes SQR to use printer type xx when creating output files: • EH • EP • HP • HT • LP • PD Types LP, HP, and PS produce files with the .lis extension. Types EH and HT produce .htm file output. On Microsoft Windows systems, the WP extension sends the output to the default Microsoft Windows printer. To specify a nondefault Microsoft Windows printer, enter -PRINTER:WP:{Printer Name}. The {Printer Name} is the name that is assigned to the printer. For example, to send output to a Microsoft Windows printer named NewPrinter, use -PRINTER:WP:NewPrinter. If your printer name has spaces, enclose the entire argument in quotes. If you also want to create an .spf file, use -KEEP.
-XB	(Non-Microsoft Windows) Suppresses the SQR banner and the <i>SQR.... End of Run</i> message.
-XNAV	Prevents SQR from creating the navigation bar in .htm files that are generated with -PRINTER:HT. This occurs when only a single .htm file is produced. Multiple .htm files that are generated from a single report always contain the navigation bar.
-XTB	Preserves the trailing blanks in a .lis file at the end of a line.
-XTOC	Prevents SQR from generating the table of contents for the report. This flag is ignored when -PRINTER:EH or -PRINTER:HT is also specified.
-ZIF{file}	Sets the full path and name of the SQR initialization file, sqr.ini.
-ZMF{file}	Specifies the full path and name of the SQR error message file, sqrrr.dat.

Generating Output in Microsoft Windows

In Microsoft Windows, SQR Print's graphical user interface enables you to generate output from the Print dialog box. In addition to the previously mentioned SQR Print output options, you can also select a Microsoft Windows printer. This spools the SQR output to your default Microsoft Windows printer or print server.

To generate output in Microsoft Windows:

1. Select File, Print.

The Print dialog box appears.

2. Under Generate output for, select the option next to the type of output that you want.
3. Specify a file path.
4. Select the Print to file check box.
5. Click OK.

CHAPTER 6

Avoiding Older SQR Commands

This chapter provides an overview of older SQR commands and discusses how to use them.

Understanding Older SQR Commands

Avoid incorporating the commands covered in this chapter in your SQR code. Even though they are technically supported in this release, they do not interact well with the current SQR lexicon and may cause unpredictable results. SQR may not support these commands in future releases, so you should remove these commands from your code as soon as it is feasible.

If your code still contains older SQR commands, refer to this table as you replace them with their updated alternatives:

Old Commands	Alternative to Use Instead
BEGIN-REPORT (END-REPORT)	BEGIN-PROGRAM (END-PROGRAM)
DATE-TIME	datetime function
DECLARE PRINTER	DECLARE-PRINTER
DECLARE PROCEDURE	DECLARE-PROCEDURE
DOLLAR-SYMBOL	ALTER-LOCALE
GRAPHIC FONT	ALTER-PRINTER
MONEY-SYMBOL	ALTER-LOCALE
NO-FORMFEED	DECLARE-LAYOUT
PAGE-SIZE	DECLARE-LAYOUT
PRINTER-DEINIT	DECLARE-PRINTER

Old Commands	Alternative to Use Instead
PRINTER-INIT	DECLARE-PRINTER
PRINT ... CODE	PRINT ... CODE-PRINTER

Note. Two older commands, DECLARE PRINTER and DECLARE PROCEDURE, do not contain hyphens. The new commands, DECLARE-PRINTER and DECLARE-PROCEDURE, contain hyphens.

Using Older SQR Commands

This section discusses each of the older SQR commands.

BEGIN-REPORT

You should no longer use this command because it may be discontinued in a future release. To use the newer SQR functionality, use BEGIN-PROGRAM.

Syntax

Use this syntax:

```
BEGIN-REPORT
```

Description

Begins a report.

After processing the commands in the SETUP section, SQR starts running the program at the BEGIN-REPORT section. The PROGRAM section typically contains a list of DO commands, though you can also use other commands. This is the only required section in an SQR program.

Example

For example:

```
begin-report
  do startup
  do main
  do finish
end-report
```

DATE-TIME

You should no longer use this command because it may be discontinued in a future release. To use the newer SQR functionality, use the datenow function in the LET command.

Syntax

Use this syntax:

```
DATE-TIME position [date_format[col_var]]
```


Description

Retrieves the current date and time from the local machine (or from the database for Oracle and some IBM DB2 platforms) and places it in the output file at the specified position or into a column variable.

If *col_var* is specified, *date_format* must be supplied and the current date and time is retrieved each time this command is run. Otherwise, the date is retrieved only at the program start, and the same date and time is printed each time.

If *date_format* is not specified, then the date is returned in the default format for that database. The following table provides the default date-time formats for SQR-supported databases:

Database	Default Date-Time Format
IBM DB2	YYYY-MM-DD-HH:MI YYYY-MM-DD-HH:MI:SS.NNNNNN
Informix	YYYY-MM-DD HH:MI YYYY-MM-DD HH:MI:SS.NNN
Oracle	DD-Mon-YYYY HH:MI PM
Sybase	DD-MON-YYYY HH:MI

For some databases, there are two default formats. The first format prints the date-time, as in the following example:

```
date-time (+1,1)
```

The second format retrieves the date-time into a column variable, as follows:

```
date-time () '' &date1
```

For those databases with only one default format, that format is always used in either of these cases.

See the table showing miscellaneous functions under the LET command for information about the valid edit mask format codes.

Parameters

position	Specifies the position for printing the date.
date_format	Represents a string literal containing the date format mask.
col_var	Places the retrieved date-time into a column variable rather than in the output file.

Example

For example:

```
date-time (1,50) MM/DD/YY
```

```

date-time (1,1) 'Day Mon DD, YYYY'
date-time ( ) HH:MI &time
date-time (+1,70) 'MON DD YYYY HH24:MI' &datetime
date-time (#i, #j) 'YYYY-MM-DD' &date1

```

See the \$current-date reserved and datenow functions that are described in the table showing miscellaneous functions under the LET command.

See The ALTER-LOCALE command

DECLARE PRINTER

You should no longer use this command because it may be discontinued in a future release. To use the newer SQR functionality, use DECLARE-LAYOUT and DECLARE-PRINTER.

Syntax

Use this syntax:

```

DECLARE PRINTER
[TYPE=printer_type_lit]
[ORIENTATION=orientation_lit]
[LEFT-MARGIN=left_margin_num_lit]
[TOP-MARGIN=top_margin_num_lit]
[LINE-SIZE=line_size_num_lit]
[CHAR-SIZE=char_size_num_lit]
[LINES-INCH=lines_inch_int_lit]
[CHARS-INCH=chars_inch_num_lit]
[POINT-SIZE=point_size_num_lit]
[FONT-TYPE=font_type_txt_lit]
[SYMBOL-SET=symbol_set_id_lit]
[STARTUP-FILE=file_name_txt_lit]
[FONT=font_int_lit]
[BEFORE-BOLD=before_bold_string_txt_lit]
[AFTER-BOLD=after_bold_string_txt_lit]

```

Description

Specifies the printer type and sets printer characteristics.

Use the DECLARE PRINTER command either in the SETUP section or in the body of the report. Generally, you should use it in the SETUP section. However, if you do not know what type of printer you will be using until the report is run, or if you need to change some of the arguments depending on user selection, you can put several DECLARE PRINTER commands in the body of the report and run the one that you need.

The following arguments take effect only once, upon execution of the first PRINT command, and thereafter have no effect even if changed:

```

LINE-SIZE
CHAR-SIZE
LINES-INCH
CHARS-INCH
ORIENTATION

```

SQR maps its line and column positions on the page by using a grid that is determined by the LINE-SIZE and CHAR-SIZE (or LINES-INCH and CHARS-INCH) arguments. Each printed piece of text is placed on the page by means of this grid. Because the characters in proportional fonts vary in width, a word or string may be wider than the horizontal space that you have allotted, especially in words containing uppercase letters. To account for this behavior, you can either move the column position in the PRINT statement or indicate a larger CHAR-SIZE value in the DECLARE PRINTER command.

Arguments

The following table describes the arguments for the DECLARE PRINTER command:

Argument	Choice or Measure	Default Value	Description
TYPE	LINEPRINTER, POSTSCRIPT, HPLASERJET	LINEPRINTER	SQR creates output that is specific to each printer. Line printer files generally contain ASCII characters and can be viewed by a text editor. PostScript files contain ASCII characters, but you need to know PostScript to understand what will appear on the printer. HP LaserJet files are binary files and cannot be edited or viewed.
ORIENTATION	PORTRAIT, LANDSCAPE	PORTRAIT	Portrait pages are printed vertically. Landscape pages are printed horizontally. Printing in landscape mode on HP LaserJet printers requires landscape fonts.
LEFT-MARGIN	inches	0.5	This argument does not apply to line printers. This is the amount of blank space to leave at the left side of the page.
TOP-MARGIN	inches	0.5	This argument does not apply to line printers. This is the amount of blank space to leave at the top of the page.

Argument	Choice or Measure	Default Value	Description
LINE-SIZE	points	12	This argument does not apply to line printers. This is the size of each SQR line on the page. There are 72 points per inch. If LINE-SIZE is not specified, it follows the value for POINT-SIZE, if specified. The default value of 12 points yields 6 lines per inch.
CHAR-SIZE	points	7.2	This argument does not apply to line printers. This is the size of each SQR horizontal character column on the page (for example, the distance between the locations [1,12] and [1,13]). If CHAR-SIZE is not specified and the point size is less than 8.6, CHAR-SIZE is set to 4.32, which yields 16.6 characters per inch. The default value of 7.2 yields 10 characters per inch.
LINES-INCH	lines	6	This argument does not apply to line printers. This is an alternate way of indicating the line size— in lines per inch, rather than in points (as in LINE-SIZE).
CHARS-INCH	characters	10	This argument does not apply to line printers. This is an alternate way of indicating the width of each SQR character column, in characters per inch, rather than in points (as in CHAR-SIZE).

Argument	Choice or Measure	Default Value	Description
POINT-SIZE	points	12	This argument does not apply to line printers. This is the beginning size of the selected font.
FONT-TYPE	PROPORTIONAL, FIXED	Depends on the font	This argument applies only to HP LaserJet printers and must be specified only for font types that are not listed as being available for HP LaserJet printers in SQR in the previous DECLARE-PRINTER section.
SYMBOL-SET	HP defined sets	0U	This argument applies only to HP LaserJet printers. The default value, 0U, is for the ASCII symbol set. Additional symbol sets exist. See <i>HP LaserJet Technical Reference Manual</i>.
STARTUP-FILE	filename	POSTSCRI.STR	This argument applies only to PostScript printers. Use this to specify an alternate startup file. Unless otherwise specified, the default startup file is located in the directory that is specified by the environment variable SQDIR.

Argument	Choice or Measure	Default Value	Description
FONT	font_number	3	This is the font number of the typeface to use. For HP LaserJet printers, this is the typeface value as defined by Hewlett-Packard. See <i>HP LaserJet Technical Reference Manual</i>. For PostScript printers, SQR supplies a list of fonts and arbitrary font number assignments in the postscri.str file. The font numbers are the same as those for HP LaserJet printers, wherever possible, so that you can use the same font number for reports to be printed on both types of printers. You can modify the font list in postscri.str to add or delete fonts. Read the postscri.str file for instructions. See the fonts that are listed as being available for HP LaserJet printers in SQR in the previous DECLARE-PRINTER section. See also the table that lists the fonts that are available in the SQR postscri.str file, also in the DECLARE-PRINTER section.

Argument	Choice or Measure	Default Value	Description
BEFORE-BOLD	any string	None	The BEFORE-BOLD and AFTER-BOLD arguments are for line printers only. They specify the character string to turn bold on and off. If the string contains blank characters, enclose it in single quotation marks ('). To specify nonprintable characters, such as ESC, enclose the decimal value within angle brackets as follows: BEFORE-BOLD=<27>[r ! Turn on bold AFTER-BOLD=<27>[u ! Turn it off These arguments work with the BOLD argument of the PRINT command.
AFTER-BOLD	any string	None	See BEFORE-BOLD.

The font that you choose—in orientation, typeface, and point size—must be an internal font (available in a font cartridge) or downloaded to the printer.

For fonts that are not listed as being available for HP LaserJet printers in SQR in the “DECLARE-PRINTER” section in the “SQR Command Reference” chapter, you must indicate the font style by using the FONT-TYPE argument; otherwise, the correct typeface cannot be selected by the printer.

DECLARE PROCEDURE

You should no longer use this command because it may be discontinued in a future release. To use the newer SQR functionality, use DECLARE-PROCEDURE.

Syntax

Use this syntax:

```
DECLARE PROCEDURE
[BEFORE-REPORT=procedure_name]
[AFTER-REPORT=procedure_name]
[BEFORE-PAGE=procedure_name]
[AFTER-PAGE=procedure_name]
```

Description

Defines specific event procedures.

Use the `DECLARE PROCEDURE` command either in the `SETUP` section or in the body of the report. You can use the command as often as you like.

If you issue multiple `DECLARE PROCEDURE` commands, the last one takes precedence. In this way, you can turn procedures on and off while the report is running. The referenced procedures do not take any arguments; however, they may be local. In addition, they can print only into the body of the report; that is, they cannot print into the header and footer areas.

Parameters

BEFORE-REPORT	Specifies a procedure to run at the time of the first <code>PRINT</code> command. Use this to create a report heading, for example.
AFTER-REPORT	Specifies a procedure to run just before the report file is closed at the end of the report. Use this to print totals or other closing summary information. If no report was generated, the procedure does not run.
BEFORE-PAGE	Specifies a procedure to run at the beginning of every page, just before the first <code>PRINT</code> command for the page. Use this to set up page totals, for example.
AFTER-PAGE	Specifies a procedure to run just before each page is written to the file. Use this to display page totals, for example.

Example

For example:

```
declare procedure
  before-page=page_setup
  after-page=page_totals
```

DOLLAR-SYMBOL

You should no longer use this command because it may be discontinued in a future release. To use the newer SQR functionality, use `ALTER-LOCALE`.

Syntax

Use this syntax:

```
DOLLAR-SYMBOL  new_symbol
```

Description

Redefines the currency symbol within numeric edit masks.

The dollar sign (\$) is the default currency symbol for coding edit masks in the program that prints on report listings. `DOLLAR-SYMBOL` provides a way to change that symbol for both the edit mask and for printing.

To change the symbol that prints on the report, use `MONEY-SYMBOL` in the `PROCEDURE` section. Use `DOLLAR-SYMBOL` and `MONEY-SYMBOL` together to configure SQR programs and the reports that they produce.

Use this command only in the `SETUP` section.

Note. The MONEY-SYMBOL command has the same effect as these options of the ALTER-LOCALE command: MONEY-SIGN and MONEY-SIGN-LOCATION=LEFT.

The following table lists the characters that DOLLAR-SYMBOL cannot take:

Type	Character
Numbers	0 8 9
Alphabetical	b e n r v B E N R V
Symbols	., - + ! * _ ' < > ()

Parameters

new_symbol Specifies a new, single character to be used in edit masks instead of the dollar sign (\$).

Example

For example:

```
begin-setup
  dollar-symbol £      ! Define £ as the currency symbol
end-setup
begin-procedure
...
print #amount ( ) edit £££,999.99
...
end-procedure
```

In the previous example, if you used the dollar sign in the edit mask after defining the dollar symbol as £, the following error message appears:

```
Bad numeric 'edit' format: $$$,999.99
```

See the ALTER-LOCALE command for a description of other locale-specific parameters.

GRAPHIC FONT

You should no longer use this command because it may be discontinued in a future release. To use the newer SQR functionality, use ALTER-PRINTER and DECLARE-PRINTER to set the FONT, FONT-TYPE, POINT-SIZE, and PITCH.

Syntax

Use this syntax:

```
GRAPHIC ( )
FONT { font_number_int_lit|_var }
```

```
[point_size_int_lit|_var[{1|0}
[pitch_int_lit|_var]]]
```

Description

Changes a font.

Parameters

font_number	For HP LaserJet printers, the specified font must be installed in the printer. For PostScript printers, the font must be defined in the postscri.str file.
point_size	If <i>point_size</i> is omitted, the size from the most recent DECLARE-PRINTER or GRAPHIC FONT command is used.
{1 0}	This argument is for HP LaserJet printers only. It is needed only if you are using a font that SQR does recognize. (See the fonts that are listed as being available for HP LaserJet printers in SQR in the DECLARE-PRINTER section in the chapter “SQR Command Reference.”) A 1 indicates a proportional font, and a 0 indicates a fixed-pitch font. The default is proportional.
pitch	If the specified font is fixed pitch, also indicate the pitch in characters per inch.

Example

For example:

```
graphic () font 23 8.5      ! Century Schoolbook, 8.5 points
graphic () font 6 12 0 10 ! Letter Gothic, 12 points,
                        ! fixed, 10 characters per inch
graphic () font :#font_number :#point_size
```

See ALTER-PRINTER and DECLARE-PRINTER for information about setting and changing the FONT, FONT-TYPE, POINT-SIZE, and PITCH.

MONEY-SYMBOL

You should no longer use this command because it may be discontinued in a future release. To use the newer SQR functionality, use the ALTER-LOCALE command.

Syntax

Use this syntax:

```
MONEY-SYMBOL new_symbol
```

Description

Redefines the currency symbol to be printed.

To change the symbol that prints on the report, use the MONEY-SYMBOL in the PROCEDURE section. When the MONEY-SYMBOL is set, that value is used until the next MONEY-SYMBOL command runs.

Use DOLLAR-SYMBOL and MONEY-SYMBOL together to configure SQR programs and the reports that they produce.

To indicate a nonedit character, surround its decimal value with angle brackets (<>). See the table under the DOLLAR-SYMBOL command for characters that cannot be used with MONEY-SYMBOL.

Note. The MONEY-SYMBOL command has the same effect as the MONEY-SIGN and MONEY-SIGN-LOCATION=LEFT options of the ALTER- LOCALE command.

Parameters

new_symbol Specifies a new, single character to replace the dollar sign (\$) or DOLLAR-SYMBOL character on the printed report.

Example

For example:

```
begin-setup
  dollar-symbol £! Define £ as the

      ! currency symbol
end-setup
begin-procedure! If #Amount=1234.56
...
money-symbol £
print #Amount ( ) Edit £££,999.99    ! Prints as: £1,234.56
...
money-symbol $
print #Amount ( ) Edit £££,999.99    ! Prints as: $1,234.56
...
money-symbol
print #Amount ( ) Edit £££,999.99    ! Prints as:  1,234.56
...
end-procedure
```

See the DOLLAR-SYMBOL and ALTER-LOCALE commands.

NO-FORMFEED

You should no longer use this command because it may be discontinued in a future release. To use the newer SQR functionality, use the FORMFEED parameter of the DECLARE-LAYOUT command.

Syntax

Use this syntax:

```
NO-FORMFEED
```

Description

Prevents form-feed characters from being written to the output file.

NO-FORMFEED is useful for certain types of reports; for example, flat file output. It is used only in the SETUP section.

Do not write form-feed control characters directly into the output file between pages.

Example

For example:

```
begin-setup
  no-formfeed
end-setup
```

See Also

See the FORMFEED qualifier in DECLARE-LAYOUT.

PAGE-SIZE

You should no longer use this command because it may be discontinued in a future release. To use the newer SQR functionality, use the MAX-LINES and MAX-COLUMNS parameters of the DECLARE-LAYOUT command.

Syntax

Use this syntax:

```
PAGE-SIZE  page_depth_num_lit  page_width_num_lit
```

Description

Sets the page size.

If you are printing multiple reports, you must use the PAPER-SIZE parameter of the DECLARE-LAYOUT command.

This command is used in the SETUP section only.

Specify the page depth in lines and the page width in columns. An average report that is printed on 8 1/2 by 11 inch paper might have a page size of 60 lines by 80 columns. A 3-inch by 5-inch sales lead card might have a size of 18 by 50.

If the page size is not specified, the default of 62 lines by 132 columns is used.

For line printers, SQR stores one complete page in a buffer before writing the page to the output file when you issue a NEW-PAGE command or when a page overflow occurs.

You can define a page to be 1 line deep and 4,000 characters wide, which you can use for writing large flat files, perhaps for copying to magnetic tape. Each time a NEW-PAGE occurs, one record is written. Use the NO-FORMFEED command in the SETUP section to suppress form-feed characters between pages.

Use a page width that is at least one character larger than the rightmost position that will be written. This prevents unwanted wrapping when printing. When the last column position on a line is printed, the current position becomes the first position of the next line. This can cause confusion when using relative line positioning with the NEXT-LISTING command. Having a wider page than necessary does not waste any file space because SQR trims trailing blanks on each line before writing the report file.

Determine the size of the internal page buffer that stores a complete page in memory by multiplying the page depth by the width in the PAGE-SIZE command. For personal computers, the page buffer is limited to 64K bytes. On other computers, the page buffer is limited only by the amount of memory that is available.

Example

For example:

```
begin-setup
  page-size 57 132! 57 lines long by 132 columns wide
end-setup
```

See Also

See the PAPER-SIZE parameter of the DECLARE-LAYOUT command.

PRINT ... CODE

You should no longer use this command because it may be discontinued in a future release. To use the newer SQR functionality, use PRINT ... CODE-PRINTER.

If you use CODE, the sequence is assumed to be for the printer type that is specified in the DECLARE-REPORT or for the default printer, if none is specified.

Syntax

Use this syntax:

```
PRINT . . . CODE
```

Parameters

CODE	CODE is a qualifier that may be discontinued in a future release. Use CODE-PRINTER instead.

PRINTER-DEINIT

You should no longer use this command because it may be discontinued in a future release. To use the newer SQR functionality, use the RESET-STRING parameter of the DECLARE-PRINTER command.

Syntax

Use this syntax:

```
PRINTER-DEINIT initialization_string
```

Description

Sends control or other characters to the printer at the end of a report.

Specify nondisplay characters by placing their decimal values inside angle brackets. For example, <27> is the ESC or escape character.

The PRINTER-DEINIT command is used only in the SETUP section and is designed for use with line printers. It has limited functionality with HP LaserJet and PostScript printers.

Example

For example:

```
begin-setup
  printer-deinit<27>[7J ! Reset the printer
end-setup
```

See Also

See the ENCODE command for another method of printing nondisplay characters. See the chr function in the table listing miscellaneous functions under the LET command in the chapter “SQR Command Reference.”

PRINTER-INIT

You should no longer use this command because it may be discontinued in a future release. To use the newer SQR functionality, use the INIT-STRING parameter of the DECLARE-PRINTER command.

Syntax

Use this syntax:

```
PRINTER-INIT initialization_string
```

Description

Sends control or other characters to the printer at the beginning of a report.

Specify nondisplay characters by placing their decimal values inside angle brackets. For example, <27> is the ESC or escape character.

The PRINTER-INIT command is used only in the SETUP section and is designed for use with line printers. It has limited functionality with HP LaserJet and PostScript printers.

Example

For example:

```
begin-setup
  printer-init<27>[7J ! Set the printer
end-setup
```

See Also

See the ENCODE command for another method of printing nondisplay characters. See the chr function in the table listing miscellaneous functions under the LET command in the chapter “SQR Command Reference.”

CHAPTER 7

Using the PSSQR.INI File and the PSSQR Command Line

This chapter provides an overview of the pssqr.ini file and discusses the following topics:

- pssqr.ini installation process.
- Default settings section.
- Processing-limits section.
- Environment sections.
- Locale section.
- Fonts section.
- HTML-Images section.
- PDF Fonts section.
- PDF Fonts: Exclusion Ranges Section
- TrueType Fonts Section
- Enhanced-HTML section.
- Colors section.
- pssqr.exe command-line options.

Installing PSSQR.INI

The pssqr.inI file is the initialization file for SQR for PeopleSoft. This file contains settings and parameters that SQR uses during the compile and execution phases.

The installation process installs a default initialization file called pssqr.in. This file is located in the SQR directory under the <PS_HOME> directory. The installation process also installs files named pssqr<language_cd>.ini. These files are used to by PeopleSoft to create different configurations needed to support specific languages.

For Microsoft Windows Platforms

SQR looks for the initialization file in the following locations, in order:

1. The file name specified by the -ZIF{file} command-line flag.
2. The directory in which the executable image resides.
3. The Windows system directory.

For z/OS

SQRINI is a required file during initialization. The dataset member &PSHLQ..SQRSRC(PSSQRINI) must be specified in the JCL to start the SQR process.

For All Other Platforms

SQR looks for the initialization file in the following locations, in order:

1. The file name specified by the -ZIF{file} command-line flag.
2. The current working directory.
3. The directory specified using the SQRDIR environment variable.

SQR automatically sets up SQRDIR.

You can make changes or additions to the pssqr.ini file.

The format of the file is as follows:

```

; Comments are lines that start with a semicolon. The semicolon
; must be the first character of the line and therefore cannot be
; part of another line.
;
; Leading and trailing space characters are ignored. To preserve
; the space characters you must surround the value with either
; single (') or double (") quote characters. SQR will remove
; them when the entry is processed.
;
[Section_Name]
Entry = Value
.
.

[Another_Section_Name]
Entry = Value
.
.
```

Default Settings Section

This section defines the various SQR default actions.

Entry	Value	Description
ForceSpaceAfterComma={TRUE FALSE}	TRUE FALSE	The default setting is FALSE. DB2 ONLY: Forces a space after every comma not in a literal value. This is to support DECIMAL=COMMA setting on the OS390.
ShowDBWarnings={TRUE FALSE}	TRUE FALSE	The default setting is FALSE. DB2 ONLY: If ShowDBWarnings is set to TRUE then SQR will display database warnings in the sqr output file.

Entry	Value	Description
AllowDateAsChar={TRUE FALSE}	TRUE FALSE	The default setting is FALSE. By default, SQR produces an error when a dynamic column specification does not match the database definition of the column. That is, character equals character, date equals date, and numeric equals numeric. When this value is set to TRUE, SQR allows character to equal either character or date columns. When a date column is type cast to be a character, SQR creates the string according to the following rules: For DATETIME columns, SQR uses the format specified by the SQR_DB_DATE_FORMAT setting. If this has not been set, the first database-dependent format as listed in the table showing default database formats in the Edit section under the PRINT command. For DATE columns, SQR uses the format specified by the SQR_DB_DATE_ONLY_FORMAT setting. If this has not been set, the format listed in the table showing default database formats in the Edit section under the PRINT command. For TIME columns, SQR uses the format specified by the SQR_DB_TIME_ONLY_FORMAT setting. If this has not been set, the format as listed the table showing the TIME column formats in the Edit section under the PRINT command. In the following example, AllowDateAsChar= True. This allows \$Col1 to be either date or text. <pre> Begin-Select [\$Col1] &col1=Text [\$Col2] &col2=Date [\$Col3] &col3=Number from MyTable End-Select </pre>

Entry	Value	Description
OUTPUT-FILE-MODE	LONG SHORT	Specifies the filename convention used for HTML output. SHORT specifies DOS style (8.3) and LONG specifies UNIX/Linux style (non 8.3). The default is LONG. (Ignored on 16-bit platforms). The DECLARE-TOC and -BURST commands force Output-File-Mode = LONG. The following represents the file formats for UNIX/Linux, DOS, and Windows. <i>SQR and SQRT:</i> {Program} is the name of the SQR/SQT file without the extension.
OUTPUT-FILE-MODE (continued)	LONG SHORT	(Continued) For Output-File-Mode = SHORT, SQR-generated filenames are limited to a DOS 8.3 format. • Output file = {Program}.LIS for first, and {Program}.Lnn for multi-reports • SFP file = {Program}.SFP for first, and {Program}.Snn for multi-reports • PDF file = {Program}.PDF for first; and {Program}.Pnn for multi-reports • HTM file = {Program}.HTM for “frame, and {Program}.Hbb for report bodies • GIF file={Program}.Gxx for all reports bb ranges from 00 to 99 and represents the report number. nn ranges from 01 to 99 and represents the report number. xx ranges from 00 to ZZ and represents the graphic number.

Entry	Value	Description
OUTPUT-FILE-MODE (continued)	LONG SHORT	(Continued) For Output-File-Mode = LONG, SQR-generated filenames are not constrained to a DOS 8.3 format. {Output}={Program} of first report and {Program}_nn for multi-reports. • Output file = {Output}.LIS • SPF file = {Output}.SPF • PDF file = {Output}.PDF • GIF file = {Output}_zz.SPF • HTM files = {Output}.HTM, {Output}_bb.HTM, {Output}_frm.HTM, {Output}_toc.HTM, {Output}_nav.htm bb ranges from 01 to ZHJOZI and represents the bursted page group number. nn ranges from 01 to 99 and represents the report number. zz ranges from 00 to ZHJOZI and represent the graphic number.
OUTPUT-FILE-MODE (continued)	LONG SHORT	(Continued) SQRP: {Filename} is the name of the SPF file without the extension For Output-File-Mode = SHORT, SQR-generated filenames are limited to a DOS 8.3 format. • Output file = {Filename}.LIS • GIF file = {Filename}.Gxx • PDF file = {Filename}.PDF • HTM file = .HTM and {Filename}.H00 xx ranges from 00 to ZZ and represents the graphic number.

Entry	Value	Description
OUTPUT-FILE-MODE (continued)	LONG SHORT	(Continued) For Output-File-Mode = LONG, SQR-generated filenames are not limited to a DOS 8.3 format. • Output file = {Filename}.LIS • PDF file = {Filename}.PDF • GIF file = {Filename}_zz.SPF • HTM files = {Filename}.HTM, {Filename}_bb.HTM, {Filename}_frm.HTM, {Filename}_toc.HTM, {Filename}_nav.htm bb ranges from 01 to ZHJOZI and represents the bursted page group number. zz ranges from 00 to ZHJOZI and represents the graphic number.
LOCALE	Name of a locale defined in the sqr.ini file or the name SYSTEM.	Specifies the initial locale that SQR loads when the program starts to execute. The value of SYSTEM is used to reference the default locale. See the ALTER-LOCALE command section for a complete description. See Chapter 2, “SQR Command Reference,” ALTER-LOCALE, page 25.
DEFAULT-NUMERIC	INTEGER FLOAT DECIMAL[(p)] V30	Specifies the default numeric type for variables. The command line flag -DNT overrides this setting. Similarly, the DECLARE-VARIABLE command overrides this setting. See the DECLARE-VARIABLE command for complete details on the meaning of the values. See Chapter 2, “SQR Command Reference,” DECLARE-VARIABLE, page 98.
OutputFormFeedWithDashD={TRUE FALSE}	TRUE FALSE	The default value is FALSE. When set to TRUE, the -Dnn command line flag outputs the Form-Feed character that denotes a page break.

Entry	Value	Description
OutputTwoDigitYearWarningMsg={TRUE FALSE}	TRUE FALSE	The default value is TRUE. When set to TRUE, SQR generates a warning message (sent to the warning file) when a YY or RR date edit mask is encountered during a program run. This affects only SQR code that is processed.
UseY2kCenturyAlgorithm={TRUE FALSE}	TRUE FALSE	The default value is FALSE. When set to TRUE, SQR treats the YY date edit mask as though it is an RR edit mask. See the RR edit mask.

Note. Use the setting V30 to process numbers in the same manner as in prior releases (before V4.0). Specifically, all numeric variables and literals are declared as FLOAT, including integer literals.

Processing-Limits Section

The Processing-Limits section is used to define the sizes and limitations of some of the internal structures used by SQR, which has a direct impact on memory requirements. The entries are the same as those used in the file specified with the -MFILE command line flag. If the -MFILE command line flag is used, the Processing-Limits section of the file is not processed.

Entry	Default Value	Maximum Value	Entry Size	Description
BREAKS	100	64K-1	4	Number of BREAK arguments allowed per EVALUATE or IF command.
DYNAMICARGS	70	32K-1	14	Maximum number of dynamic SQL arguments.
EXPRESSIONSPACE	8192	64K-1	1	Maximum length, in bytes, of temporary string storage used during LET operations.
FORWARDREFS	200	32K-1	8	Maximum number of column forward references.

Entry	Default Value	Maximum Value	Entry Size	Description
LONGSPACE	32K-2	32K-2	1	Maximum buffer size to transfer text and image data in bytes.
ONBREAKS	30	64K-1	8	Maximum number of ON-BREAK LEVEL=values per SET.
POSITIONS	1800	64K-1	14	Maximum number of placement parameters, for example, (10,5,30).
PROGLINEPARS	18000	64K-1	2	Maximum number of arguments for all program lines. This value is generally 3 or 4 times the value set for PROGLINES.
PROGLINES	5000	32K-1	8	Maximum number of program lines (SQR commands).
QUERIES	60	32K-1	60	Maximum number of BEGIN-SQL and BEGIN-SELECT paragraphs. This is database dependent and can vary. This size is used as a close approximation.
QUERYARGS	240	64K-1	6	Maximum number of arguments (bind variables) for all SQL or SELECT statements. The number of arguments required is one more than the number used in your report file.

Entry	Default Value	Maximum Value	Entry Size	Description
SQLSIZE	4000	64K-1	1	Maximum length of a SQL statement in characters.
STRINGSPACE	15000	64K-1	1	Maximum size of string space for program line arguments, in bytes.
SUBVARS	100	32K-1	8	Maximum number of runtime substitution variables.
VARIABLES	1500	64K-1	18	Maximum number of variables (<i>string</i> , <i>float</i> , <i>integer</i> , <i>decimal</i>), literal values, and database columns. Add 4 to the entry size for Informix.
WHENS	70	64K-1	4	Maximum number of WHEN arguments allowed per EVALUATE command.

The maximum value refers to the number of entries allowed as shown in the previous table; however, limits are lower for 32-bit machines. In any case, SQR indicates the limit if you exceed it.

In addition to increasing the sizes, you may also lower them to decrease the amount of memory used. This might be advantageous, for example, for certain applications running in the PC environment, where memory is limited.

Environment Sections

The Environment sections { Common | DB2 | Informix | ODBC | Oracle | RDB | Sybase } define the environment variables used by SQR. An environment variable can be defined in multiple environment sections; however, a definition in a database-specific environment section takes precedence over an assignment in the Environment:Common section.

The environment variables that can be set are *SQRDIR*, *SQRFLAGS*, and *DSQUERY*. On Microsoft Windows systems, *SQRDIR* is required and is automatically defined in the appropriate database-specific environment section during the SQR installation. The other environment variables are optional. *SQRFLAGS* specifies the default command-line flags for all invocations of SQR. *DSQUERY* (Sybase only) identifies the default Sybase server to use.

On Microsoft Windows systems only, the SQR Extension section defines DLLs containing new user functions (UFUNC) and user calls (UCALL). UFUNC and UCALL reside inside SQREXT.DLL and/or other DLLs.

When SQRW.DLL and SQRWT.DLL are being loaded, they look for SQREXT.DLL in the same directory, and for any DLLs specified in the SQR Extension section in sqr.ini such as:

```
[SQR Extension]
c:\sqrexts\sqrext1.dll=
c:\sqrexts\sqrext2.dll=
c:\sqrexts\sqrext3.dll=
```

Any new extension DLLs containing new user functions must be listed in the SQR Extension section in sqr.ini.

See *Enterprise PeopleTools 8.45 PeopleBook: SQR for PeopleSoft Developers*, “Using Interoperability Features”.

For Windows/Oracle, SQR uses dynamic binding of Oracle routines. When SQR attempts to access an Oracle database, it searches for the Oracle DLL as follows:

- The file described by the value of ORACLE_DLL entry in the Environment:Oracle section of the sqr.ini file.
- OCIW32.DLL (Oracle supplied).
- ORANT71.DLL (Oracle supplied).

Entry	Value	Description
SQRParseSQLEnable= {TRUE FALSE}	TRUE FALSE	The default setting is FALSE. If SQRParseSQLEnable=TRUE is added to the PSSQR.INI file (in the common or Oracle stanza) then we will perform SQL parsing. Note. The function required to perform this parsing is not a supported function on Oracle 8.X but does appear to function. If a customer wishes to assume the risk of using a feature that Oracle will not fix if a problem is found then they can turn on this parameter. Oracle 9.X customers can use this feature without any problem, although there is a performance hit of between 2-10%.

Locale Section

The Locale: locale-name section specifies the default settings for the locale identified by locale-name (which can consist of A-Z, 0-9, hyphen, or underscore). A number of locales are predefined in the sqr.ini file. Depending on your application, the settings for these locales may have to be altered or new locales may have to be added. A locale can be referenced or altered at runtime using the ALTER-LOCALE command. The entries for a locale section are described in the following table.

Note. The SYSTEM locale is provided for your reference, but is commented out. The settings for the SYSTEM locale, if set, are ignored. Use the ALTER-LOCALE command to change the SYSTEM locale settings at runtime.

See [Chapter 6, “Avoiding Older SQR Commands,” page 261](#).

Entry	Description
NUMBER-EDIT-MASK	The default numeric edit mask format when the keyword NUMBER accompanies the DISPLAY, MOVE, PRINT, or SHOW command.
MONEY-EDIT-MASK	The default numeric edit mask format when the keyword MONEY accompanies the DISPLAY, MOVE, PRINT, or SHOW command.
DATE-EDIT-MASK	The default date edit mask format when the keyword DATE accompanies the DISPLAY, MOVE, PRINT, or SHOW command, or the LET datetostr() or strtodate() functions.
INPUT-DATE-EDIT-MASK	The default date format to use with the INPUT command when TYPE=DATE is specified with the command or the input variable is a DATE variable.
MONEY-SIGN	Specifies the characters to replace the (\$) edit character.
MONEY-SIGN-LOCATION	Specifies the location of the MONEY-SIGN character. Valid values are LEFT and RIGHT.
THOUSAND-SEPARATOR	Specifies the character to replace the comma (,) edit character.
DECIMAL-SEPARATOR	Specifies the character to replace the period (.) edit character.
DATE-SEPARATOR	Specifies the character to replace the slash (/) character.
TIME-SEPARATOR	Specifies the character to replace the colon (:) character.
EDIT-OPTION-NA	Specifies the characters to replace the na option.
EDIT-OPTION-AM	Specifies the characters to replace AM

Entry	Description
EDIT - OPTION - PM	Specifies the characters to replace PM.
EDIT - OPTION - AD	Specifies the characters to replace AD.
EDIT - OPTION - BC	Specifies the characters to replace BC.
DAY - OF - WEEK - CASE	Specifies how the case for the DAY-OF-WEEK-FULL or DAY-OF- WEEK-SHORT entries are affected when used with the format codes <i>DAY</i> or <i>DY</i>. Valid values are UPPER, LOWER, EDIT, and NO-CHANGE. UPPER and LOWER forces the output to either all uppercase or lowercase, ignoring the case of the format code in the edit mask. Use EDIT to follow the case as specified with the format code in the edit mask. Use NO-CHANGE to ignore the case of the format code and output the day of week as explicitly listed in the DAY-OF-WEEK-FULL or DAY-OF-WEEK-SHORT entries.
DAY - OF - WEEK - FULL	Specifies the full names for the days of the week. SQR considers the first day of the week to be Sunday. All seven days must be specified.
DAY - OF - WEEK - SHORT	Specifies the abbreviated names for the days of the week. SQR considers the first day of the week to be Sunday. All seven abbreviations must be specified.
MONTHS - CASE	Specifies how the case for the MONTHS-FULL or MONTHS-SHORT entries is affected when used with the format codes <i>MONTH</i> or <i>MON</i>. Valid values are UPPER, LOWER, EDIT, and NO-CHANGE. UPPER and LOWER force the output to either all uppercase or lowercase, ignoring the case of the format code in the edit mask. Use EDIT to follow the case as specified with the format code in the edit mask. Use NO-CHANGE to ignore the case of the format code and output the month as explicitly listed in the MONTHS-FULL or MONTHS-SHORT entries.

Entry	Description
MONTHS - FULL	Specifies the full names for the months of the year. SQR considers the first month of the year to be January. All 12 months must be specified.
MONTHS - SHORT	Specifies the abbreviated names for the months of the year. SQR considers the first month of the year to be January. All 12 abbreviations must be specified.

Database	Date Column Formats
DB2	YYYY-MM-DD
INFORMIX	MM/DD/YYYY
ODBC	DD-MON-YYYY

Database	Time Column Formats
DB2	HH24.MI.SS
ODBC	HH24:MI:SS

Note. Refer to your database vendor for date and time defaults.

Fonts Section

The Fonts section lists the fonts available to SQR when printing on Microsoft Windows printer devices (using the -PRINTER:WP command-line flag), viewing SPF output using SPF Viewer on Microsoft Windows (SQRWV), and creating style sheet for Enhanced HTML output. This section does not apply to PostScript or HP LaserJet printer types. See the DECLARE-PRINTER command for a listing of available fonts for these alternate printer types.

See [Chapter 2, “SQR Command Reference,” DECLARE-PRINTER, page 84](#) and [Chapter 6, “Avoiding Older SQR Commands,” page 261](#).

Adding Fonts Entries

Within the Fonts section, there are a number of predefined font entries. You can add entries by using the font numbers 900 through 999. Each entry consists of a font name, a font style (fixed or proportional), and a bold indicator, all of which are associated with a font number.

For example:

```
4=Arial,proportional
```

or
 300=Courier New,fixed,bold

Note. Proportional is assumed if the second parameter starts with a *P*. Also, bold is assumed if a third parameter is supplied.

Using the font number, commands such as ALTER-PRINTER and DECLARE-PRINTER can reference a particular font style.

Specifying Character Sets in Windows

If you are a Microsoft Windows user, you can use the CharacterSet entry either to determine the Microsoft Windows default character set or to specify a character set. This enables you to print any standard character set to a Windows printer (-PRINTER:WP) or to view an SPF file that displays the appropriate character set.

The syntax is:

```
CharacterSet=DEFAULT|AUTO|character_set
```

The arguments are:

- DEFAULT reflects current SQR functionality.
- AUTO automatically determines the default character set of the Microsoft Windows installation and uses the default set when generating reports.

CharacterSet specifies one of these keywords: ANSI, ARABIC, BALTIC, CHINESEBIG5, EASTEUROPE, GB2312, GREEK, HANGUL, HEBREW, JOHAB, MAC, OEM, RUSSIAN, SHIFTJIS, SYMBOL, THAI, TURKISH, VIETNAMESE.

HTML-Images Section

The HTML-Images section defines the parameters that SQR uses when generating HTML report output files.

Entry	Value	DefaultValue	Description
FIRST-PAGE	HEIGHT, WIDTH, NAME	60,60,firstpg.gif	Specifies the NAME of the graphic image file that accesses the first page of the report. The HEIGHT and WIDTH are values specified in pixels.
PREV-PAGE	HEIGHT, WIDTH, NAME	60,60,prevpg.gif	Specifies the NAME of the graphic image file that accesses the previous page of the report. The HEIGHT and WIDTH are values specified in pixels.

Entry	Value	DefaultValue	Description
NEXT-PAGE	HEIGHT, WIDTH, NAME	60,60,nextpg.gif	Specifies the NAME of the graphic image file that accesses the next page of the report. The HEIGHT and WIDTH are values specified in pixels
LAST-PAGE	HEIGHT, WIDTH, NAME	60,60,lastpg.gif	Specifies the NAME of the graphic image file that accesses the last page of the report. The HEIGHT and WIDTH are values specified in pixels.
WALLPAPER	NAME		Specifies the NAME of the graphic image file used as the background image for the report.
Navbar Background	NAME		Background image of navigation bar.

Note. SQR does not perform any validation of the graphic image filenames provided. The user is responsible for ensuring that the graphic image files are in a location that the browser can access.

PDF Fonts Section

The PDF Fonts section lists the available fonts for SQR when printing using the -PRINTER:PD command-line flag. Fonts specified are case sensitive.

Unlike the Fonts section, the PDF Fonts section takes a list of fonts mapped to a single font number. You can specify up to 10 fonts for a single font number. Depending on the character to print, SQR determines the font to use from the list. The following is the syntax of this font list:

```
Font Number=Font1, Font2, Font3 ...
```

The list is ordered by priority from the left. If Font1 has a glyph (an image of a character) for the character you want to print, it is used, but if Font1 does not have a glyph, Font2 is checked and used if it has a glyph for that character.

Font Number is a decimal number that is used to specify fonts in the SQR program using statements like DEFINE-PRINTER or ALTER-PRINTER.

Font numbers that are multiples of 100 (300, 3200, and so on) are recognized as a bold version of the base font. For example, font 300 is the bold version of Font3.

Font numbers 30 to 39 are recognized as italic fonts, and multiples of 30 to 39 (3000, 3100, and so on) are bold italic versions of the font. If you assign nonbold fonts for a font number recognized as bold, (such as 600), the text printed with that font will be printed in bold.

Font1, Font2, and Font3 represent the font name. You can use Adobe Reader core fonts, Adobe Reader Asian Font Pack fonts, or TrueType fonts.

Adobe Reader core fonts are the fonts that Adobe Reader natively supports. The following is a list of the core fonts:

- Courier
- Courier-Bold
- Courier-Oblique
- Courier-BoldOblique
- Helvetica
- Helvetica-Bold
- Helvetica-Oblique
- Helvetica-BoldOblique
- Times-Roman
- Times-Bold
- Times-Italic
- Times-BoldItalic
- Symbol
- ZapfDingbats

Adobe Reader Asian Font Pack fonts are the font packages Adobe provides as add-on to Adobe Reader for the purpose of viewing Asian text. You can download these fonts from the Adobe website, or if you use Adobe Reader 6, the Asian Font Pack will automatically download if you open a PDF file that contains a font from the Asian Font Pack. Alternatively, you can use the Adobe Reader localized to any of the Japanese, Chinese, or Korean languages. These localized versions come with the same fonts that are included in the Adobe Asian Font Pack. The following is a list of the Asian Font Pack fonts used with SQR:

- HeiseiKakuGo-W5 (Japanese)
- HeiseiMin-W3 (Japanese)
- MHei-Medium (Traditional Chinese)
- MSung-Light (Traditional Chinese)
- STSong-Light (Simplified Chinese)
- HYGoThic-Medium (Korean)
- HYSMyeongJo-Medium (Korean)

In addition, you can use TrueType/OpenType fonts that exist on the machine where you run SQR. If you use TrueType fonts for PDF output, they will be always embedded as subset of the original font. To use TrueType fonts for PDF output, you need to specify the mapping between the font name and the font file path in the [TrueType Fonts] section, and then include the font name in the font list under the [PDF Fonts] section. See below more information about the [TrueType Fonts] section.

See [Chapter 7, “Using the PSSQR.INI File and the PSSQR Command Line,” TrueType Fonts Section, page 294.](#)

PDF Fonts: Exclusion Ranges Section

The PDF Fonts: Exclusion Ranges section defines character ranges you want to exclude from the range a font covers. Without an exclusion range, SQR uses all of the character ranges a font covers, and then checks the font listed in the next priority only when it does not cover a character. By specifying an exclusion range, you can use a font in a lower priority for a specific character or a range of characters. This mechanism allows users to control which font to use down to a single character level.

The syntax in this section is as follows:

```
Font Number=Font1 Exclusion Range, Font2 Exclusion Range, ...
```

Exclusion ranges apply to the list of fonts defined in the PDF Fonts section. For example, if you have a PDF Fonts section like the following:

```
3=Courier,Cumberland,HeiseiKakuGo-W5,...
```

In addition, if you define the PDF Fonts: Exclusion Ranges section like this

```
3=0x20AC,0x3070-0x30FF,,
```

then you are defining that Euro currency symbol (0x20AC in Unicode) is rendered using the Cumberland font, even though Courier has it. In addition, Greek characters (from 0x3070 to 0x30FF in Unicode) are rendered using HeiseiKakuGo-W5 font, even though Cumberland has them.

Each Exclusion range is specified using Unicode (UCS-2) codepoint, in decimal or in hexadecimal, in the following ways:

0x20AC (single character)

160-255 (range)

0x20AC|0x00A0-0x00FF (multiple characters and ranges)

Hexadecimal numbers need to be preceded by 0x. Otherwise, numbers are recognized as decimal.

TrueType Fonts Section

The TrueType Font section defines the mapping of font name, which is an alias SQR uses internally to look up the font, and physical font file name. You need to specify the font in the full path, unless you have placed fonts in a directory specified in the Font Path parameter, or in a Windows font folder if you are running SQR on Windows.

The syntax is:

```
font name=fontfile path
```

For example, if you have the font courier.ttf in the c:\user\fonts directory, you set the following in this section:

```
CourierNew=c:\user\fonts\courier.ttf
```

Font name can be any string that is convenient for you to identify the font, and does not need correspond to a name the font has internally. PeopleSoft recommends that you not use the same font name that is used for Adobe core fonts or for Asian Font Pack fonts. If you set the same name for any of Adobe core fonts or Asian Font Pack fonts, then the TrueType font will be used.

Note. TrueType font embedding is now supported by SQR running on z/OS. However, the Font Path parameter under the TrueType Font section is not supported for z/OS. If you're on z/OS, you need to specify the full path to each entry.

If you have a TrueType Collection (TTC) file, you will also need to specify the font number to access the specific font included in the collection. For example, if MS P Mincho is included in the TrueType collection file mmincho.ttc, then you will need to specify:

```
MSPMincho=c:\winnt\fonts\mmincho.ttc,1
```

The font number within the TrueType collection starts at 0. mmincho.ttc contains MS Mincho and MS P Mincho in this order; thus the number 0 represents MS Mincho and 1 represents MS P Mincho. If you do not specify font number, SQR uses font with font number 0 from the TrueType collection file.

Note. You can use only Microsoft type of Unicode based TrueType/OpenType fonts with SQR. SQR requires TrueType/OpenType font to have CMAP table with Platform ID 3 (Microsoft), Encoding ID 0 (Symbol), 4 (UCS-2), or 10 (UCS-4) and table format 4 or 12. SQR does not support OpenType fonts with CFF (Postscript) outline. You can use OpenType fonts with TrueType outlines, but SQR does not make use of advanced layout features provided with OpenType font.

Enhanced-HTML Section

The Enhanced-HTML section is used to define various default actions that SQR takes when generating HTML output using the -EH command-line flag.

Entry	Value	Description
Browser={ALL IE NETS CAPE}	ALL IE NETSCAPE	When set to ALL, the generated HTML auto-determines which browser is being used and invokes the proper browser-specific file. When set to IE, the generated HTML is designed for Internet Explorer. When set to NETSCAPE, the generated HTML is designed for Netscape. The default action is to generate HTML suitable for ALL browsers.
Language={English French German Portuguese Spanish Japanese Simplified Chinese Korean}	English French German Portuguese Spanish Japanese Simplified Chinese Korean	The default setting is English. Sets the language used for the HTML navigation bar.
FullHTML={TRUE FALSE}	TRUE FALSE	When set to TRUE, HTML 3.2 is generated. When set to FALSE, HTML 3.0 is generated. The default setting is FALSE.

Colors Section

The Colors section defines the default colors that you can use in your SQRs. Enter the default colors in the format of:

```
[Colors]
color_name = ({rgb})
color_name = ({rgb})
...
color_name = ({rgb})
```

The default colors implicitly installed are:

- black=(0,0,0)
- white=(255,255,255)
- gray=(128,128,128)
- silver=(192,192,192)
- red=(255,0,0)
- green=(0,255,0)
- blue=(0,0,255)
- yellow=(255,255,0)
- purple=(128,0,128)
- olive=(128,128,0)
- navy=(0,0,128)
- aqua=(0,255,255)
- lime=(0,128,0)
- maroon=(128,0,0)
- teal=(0,128,128)
- fuchsia=(255,0,255)

Using PSSQR.EXE Command-Line Options

PeopleSoft provides a shell called pssqr.exe that extends SQR to handle the submission of SQR programs under Windows and UNIX/Linux operating systems. Pssqr.exe implements a process that ensures that output is sent to the appropriate destination in a way that is consistent across platforms.

Note. PeopleSoft does not support running pssqr.exe directly from a DOS or Unix/Linux command line. Pssqr.exe is a wrapper program used by PeopleSoft Process Scheduler to run SQR reports; it is not designed to run manually outside of Process Scheduler.

Pssqr.exe does not run on OS/390, however, all output formats are supported on all platforms.

Pssqr.exe provides the following features:

- Expanded output formats: SQR Viewer, HTML, PDF, CSV (Spreadsheet Standard), HP, Postscript, Line Printer.
- Expanded printer format: Windows Default Printer (Win32 only), HP, Postscript, Line Printer.
- Enhanced delivery of reports to printers: PSSQR sends reports to the printer instead of SQR, which resolves issues that can be encountered on non-Microsoft networks.
- File output and logs have unique names. If the process instance is sent, the file names will be <SQR Program>_<Instance>.xxx. If not, then the log names will be <SQR Program>_<timestamp>.xxx.
- Common command line interface for both Windows and UNIX/Linux.
- Reads Configuration Manager settings to determine the flags (SQRFLAGS) to use.
- Support for multiple report output. Default values come from Configuration Manager if run from the command line.

Command-Line Parameter	Description
-CT	Database type. Valid values are DB2, DB2390, INFORMIX, MICROSOFT, ORACLE, SYBASE.
-CS	Server name.
-COWN	Database owner. This applies to OS/390 only.
-CD	Database name.
-CA	Access ID.
-CAP	Access password.
-RP	Program name.
-I	Process instance.
-R	Run control ID.
-CO	User ID.
-OT	Output type: • 2 (File) • 3 (Printer) • 4 (Window)

Command-Line Parameter	Description
-OF	Output format. Column headings refer to the -OT parameter. • 2 (Acrobat) • 3 (Comma delimited) • 4 (HP format) • 5 (HTML documents) • 6 (Line printer) • 10 (Postscript) • 13 (SQRiBE portable) • 14 (Text files) • 15 (Windows default printer)
-OP	Output destination.
-MR	Multiple report output. Values: # (maximum 99)
-AF	Additional flags.
-AP	Additional information.
-TR	Enable trace.
-DL	Display log file.
-FILE	Enter the name of a parameter file containing the parameters you want to pass to PSSQR. The system deletes the file immediately after use.
-LG	Language Code. Takes a three-letter language code used across PeopleSoft systems. This flag is used to determine which language version of the PSSQR.INI file to use. If you specify LG JPN, then pssqr.exe picks up the Japanese configuration file (PSSQRJPN.INI) instead of PSSQR.INI. This parameter takes effect only when the %LANGUAGE_CD% variable is used for specifying the PSSQR.INI file in PSSQRFLAGS entry of the Process Scheduler configuration or Configuration Manager.

Command-Line Parameter	Description
-LPFLAGS "<flags>"	UNIX/Linux only : Overrides the flags passed to the lp command.
-DEBUGLP ON	Displays command used to print the SQR report.

CHAPTER 8

Understanding SQR Messages

This chapter provides all the messages produced by SQR for PeopleSoft. It contains two tables listing all:

- Unnumbered messages
- Numbered messages

Note. Two digits ('nn) appear as replacement markers in the messages. Descriptions of these replacement markers are listed in the message itself. The messages contain the proper value when they appear on the screen.

Unnumbered Messages

This table lists all unnumbered SQR for PeopleSoft messages:

Error	Description
Out of memory.	This occurs when a call to the C routine 'malloc()' fails. (32-bit machines) Use the -Mfile command line flag to reduce some of the different memory requirements. Remove unneeded TSRs. (UNIX/Linux) Increase the size of the system swap file.
No cursors defined.	From the -S command line flag. The SQR program did not contain any commands that required a database cursor.
Not processed due to report errors.	From the -S command line flag. SQR cannot provide information about the cursor due to errors in the program.
Enter '01'02	Type the value to be assigned to the specified variable. '01 = First character of the variable name '02 = Rest of the variable name
NOPROMPT used - Enter value below	(Windows) This message appears when an INPUT command is defined with the NOPROMPT argument.

Error	Description
Enter '01	Enter the value to be assigned to the specified substitution variable. '01 = Name of the substitution variable
Enter this run's parameters:	Enter the values for the parameters defined in the program.
Error on line '01: '02	SQR detected an error while processing the report file. Correct the error and rerun. '01 = Source line number '02 = Source line
Error in include file "'01" on line '02: '03	SQR detected an error while processing the report file. Correct the error and rerun. '01 = Name of the include file '02 = Source line number '03 = Source line
Warning on line '01: '02	SQR detected a nonfatal error while processing the report file. '01 = Source line number '02 = Source line
Warning in include file "'01" on line '02: '03	SQR detected a nonfatal error while processing the report file. '01 = Name of the include file '02 = Source line number '03 = Source line
Type RETURN for more, C to continue w/o display, X to exit run:	Informational message that is used in conjunction with the -D command line flag.
Error at: '01 Loading Oracle DLL Failed!!!	(Oracle) Title for the dialog box that informs the user that SQR could not load the Oracle DLL.
Errors were found in the program file.	Correct the errors and rerun.
Errors were found during the program run.	Correct the errors and rerun.

Error	Description
'01: End of Run.	Informational message. '01 = Image name (for example, SQR)
Enter report name:	Enter the name of the report (.sqr or .sqt) to run.
Enter database name:	Enter the name of the database.
Enter database[/username]: Enter Username:	Enter the user name to log onto the database.
Enter Password:	Enter the password. For security reasons, the password is not be echoed.
Customer ID:	Text message
Press Enter to close...	Text message
'01: Program Aborting.	Informational message. '01 = Image name (for example, SQR)
*** Internal Coding Error ***	Informational message.
SQL DataServer Message	(Windows) A title for the error message dialog box.
Operating-System error	(Windows) A title for the error message dialog box.
DB-Library error	(Windows) A title for the error message dialog box.
'01 is running. Click the Cancel button to interrupt it.	(Windows) This is the body of the -C cancel dialog box. This lets the user quit the program run by clicking the Cancel button.
Table of Contents	Text for HTML driver
Previous	Text for HTML driver
Next	Text for HTML driver
First Page	Text for HTML driver

Error	Description
Last Page	Text for HTML driver
PAGE	Text for HTML driver

Numbered Messages

This table lists numbered messages:

Error Number	Error Message	Suggestion/Interpretation
000001	Error while opening the message file: '01' ('02): '03	Try reloading the sqrrr.dat file from the release media. If the error persists, contact technical support. '01 = Name of the error message file '02 = System error code '03 = System error message
000002	Error while reading the message file. ('01): '02	Try reloading the sqrrr.dat file from the release media. If the error persists, contact technical support. '01 = Name of the error message file '02 = System error code '03 = System error message
000003	Error while closing the message file. ('01): '02	Try reloading the sqrrr.dat file from the release media. If the error persists, contact technical support. '01 = Name of the error message file '02 = System error code '03 = System error message
000004	Error while seeking the message file. ('01): '02	Try reloading the sqrrr.dat file from the release media. If the error persists, contact technical support. '01 = Name of the error message file '02 = System error code '03 = System error message
000005	Corrupt message file: Invalid header information.	Try reloading the sqrrr.dat file from the release media. If the error persists, contact technical support.

Error Number	Error Message	Suggestion/Interpretation
000006	Corrupt message file: Invalid count (Got '01, Should be '02).	The header contains an invalid entry count. (1) Make sure SQRDIR points to the correct directory. (2) Try reloading the sqrrr.dat file from the release media. If the error persists, then contact technical support. '01 = The value read from the header '02 = What the value should be
000007	Cannot handle message file version '01.	This release of SQR does not support the header version. (1) Make sure SQRDIR points to the correct directory. (2) Try reloading the sqrrr.dat file from the release media. If the error persists, then contact technical support. '01 = Unsupported version read from the header
000010	Invalid SEMCode encountered: '01.	An invalid code was passed to the error message handler. Try reloading the files from the release media. If the error persists, then contact technical support. '01 = Invalid code
000011	Unknown conversion type ('01) for code '02.	Try reloading the sqrrr.dat file from the release media. If the error persists, then contact technical support. '01 = Invalid type '02 = Internal error code
000012	Message '01 must be either Preload or BuiltIn.	The type error code is not correct. Try reloading the sqrrr.dat file from the release media. If the error persists, then contact technical support. '01 = Error code
000013	Cannot point to message '01.	The error handler cannot position to the desired error code. Try reloading the sqrrr.dat file from the release media. If the error persists, then contact technical support. '01 = Error code
000014	The required environment variable '01 has not been defined.	Define the named environment variable and restart SQR. '01 = Environment variable name

Error Number	Error Message	Suggestion/Interpretation
000015	The Meta ESC characters do not match (Got '01', Should be '02').	The meta escape character defined in the header does not match what the error message handler expects. Try reloading the sqrrr.dat file from the release media. If the error persists, then contact technical support. '01 = What was found in the header '02 = What was expected to be found
000016	'01() called to process ('02) and the message file is not open.	The specified error routine was called but the error message file was not open. Try reloading the files from the release media. If the error persists, then contact technical support. '01 = Name of the routine '02 = Error code
000017	Message '01 must be ReportParameters or CopyrightNotice.	Try reloading the sqrrr.dat file from the release media. If the error persists, then contact technical support. '01 = Error code
000018	Allocation header does not point to a valid heap.	(Windows) This is the result of a memory overwrite. Record the steps leading up to the error and contact technical support.
000019	Allocation header has an invalid size.	(Windows) This is the result of a memory overwrite. Record the steps leading up to the error and contact technical support.
000020	GLOBAL header has an invalid size.	(Windows) This is the result of a memory overwrite. Record the steps leading up to the error, and contact technical support.
000021	Cannot free GLOBAL allocation.	(Windows) This is the result of a memory overwrite. Record the steps leading up to the error and contact technical support.
000028	Cannot access the initialization file: '01 ('02): '03	The initialization file specified by the -ZIF command line flag cannot be accessed. '01 = Name of the file '02 = System error code '03 = System error message

Error Number	Error Message	Suggestion/Interpretation
000202	DPUT: Bad field number.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000203	DARRAY: Unknown command number.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000204	'01: Cannot find '02 command.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Name of the routine '02 = Name of the command
000205	DDO: DO arguments do not match procedure's.	<obsolete>
000206	SDO: Bad params for DO command.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000207	SDO: Bad params for BEGIN-PROCEDURE command.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000208	SGOTO: Bad command numbers.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000209	SGOTO: Bad goto function parameters.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.

Error Number	Error Message	Suggestion/Interpretation
000210	SGOTO: Could not find beginning of section or paragraph.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000211	SGOTO: Bad label: from parameters.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000212	COMPAR: Unknown relational (numeric) operator.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000213	COMPAR: Unknown relational (string) operator.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000214	DONBRK: Unknown case for putlin.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000215	'01: Bad length case for numeric '02.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Name of the routine '02 = name of the variable
000216	GARRAY: Unknown command number.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000217	GCMDS: No Gfunc found.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.

Error Number	Error Message	Suggestion/Interpretation
000218	GDOC: Unknown document type.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000219	GLET: Bad operator.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000220	GLET: Stack incorrect for expression - arg '01.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Number of the argument
000221	GLET: Unknown operator type.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000222	GLET: Unknown operator in expression.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000223	GPARS: Column not SCOL, TCOL or NCOL type.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000224	GPARS: Bad parameter format: '01 = '02=	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Internal command format string '02 = Bad format field found

Error Number	Error Message	Suggestion/Interpretation
000225	GPARS: No end of required word in parfmt: '01	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Internal command format string
000226	GPARS: Bad parfmt entry: '01	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Internal command format string
000227	GPARS: Bad parameter string.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000228	GPARS: Repeat count bad: '01	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Internal command format string
000229	GPARS: Only a,b,8,9 allowed for repeats: '01	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Internal command format string
000230	GPARS: Missing required x: '01	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Internal command format string
000231	GPARS: Bad type in 'ckvrpr()'.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.

Error Number	Error Message	Suggestion/Interpretation
000232	GPROC: No Gfunc found.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000233	GRDWRT: Unknown command number.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000234	GSHOW: Unknown SHOW option.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000235	PGMPARS: 'addvar()' passed maxlen but not column.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000238	PGMPARS: '01' passed invalid parameter number: '02.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Routine name '02 = Invalid parameter number
000239	PGMPARS: 'fxclrf()' encountered bad column reference type: '01.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Internal variable type code
000240	PLCMNT: 'getplc()' passed invalid element number: '01.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Invalid element number

Error Number	Error Message	Suggestion/Interpretation
000241	RDPGM: Command array size exceeded (change COMDMAX to at least '01).	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Maximum internal command number supported.
000242	RDPGM: Bad match adding internal variable: '01	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Internal variable name
000243	RDPGM: No cmdget function found for BEGIN_S.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000244	Function '01 not included in run-time package.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Name of the SQR routine
000245	SETSQL: Could not find variable ''01', in Run Time.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Variable name
000248	SIFWHL: Command number incorrect.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000249	SPINIT: Bad parameters.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.

Error Number	Error Message	Suggestion/Interpretation
000251	DBFFIX: DBDATLEN returned out of range status.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000252	DPRPST: Error converting Sybase type for EXECUTE.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000254	SETSQL: Could not find variable entry in list.	(Oracle) This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000255	DBDESC: SQLD not = number of select columns.	(DB2, Informix) This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
000256	DBFETCH: Unknown variable dbtype encountered: '01 ('02)	(DB2, Informix) This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Variable name '02 = Unknown database type
000257	WRITE_SPF: Unknown code encountered: '01	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Unknown SPF code
000258	'01: Cannot find LOAD-LOOKUP table: '02	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Name of the routine '02 = Name of the table

Error Number	Error Message	Suggestion/Interpretation
000259	PGMPARS: '01' called with wrong variable '02'	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Name of the routine '02 = Name of the variable
000260	SQTMGT: Could not find 'vars' entry with 'nvars' index of '01'.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Index into nvars table
000261	MODIFYVAR: Attempt to change variable which is not xVAR ('01).	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = name of the variable
000262	MODIFYVAR: Incompatible variable types ('01) and ('02).	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Variable type (from) '02 = Variable type (to)
001100	Out of query arguments; use -Mfile to increase QUERYARGS.	This is the total number of variable references (\$Var, #Var, &Col) allowed in the context of a BEGIN-SQL or BEGIN- SELECT command. Use the -Mfile flag on the command line to specify a file containing an entry that increases the currently defined value.
001201	Cannot open the argument file: '01'. ('02): '03	Depends on the system error message. '01 = Name of the file '02 = System error code '03 = System error message
001202	Cannot close the argument file. ('01): '02	Depends on the system error message. '01 = System error code '02 = System error message
001203	Cannot open the - Mfile: '01'. ('02): '03	Depends on the system error message. '01 = Name of the file '02 = System error code '03 = System error message

Error Number	Error Message	Suggestion/Interpretation
001204	Minimum value for '01' in the -Mfile is '02.	Correct the -Mfile entry. '01 = Keyword in question '02 = Minimum value allowed
001205	Maximum value for '01' in the -Mfile is '02.	Correct the -Mfile entry. '01 = Keyword in question '02 = Maximum value allowed
001206	Invalid -Mfile entry: '01'.	Correct the -Mfile entry. '01 = The line from the -Mfile
001207	Cannot close the - Mfile. ('01): '02	Depends on the system error message. '01 = System error code '02 = System error message
001209	The minimum value for '01' ('02) is '03.	Value out of range. '01 = Entry name '02 = Specified value '03 = Minimum value
001210	The maximum value for '01' ('02) is '03.	Value out of range. '01 = Entry name '02 = Specified value '03 = Maximum value
001211	The value for '01' ('02) is not an integer number.	Value must be a integer value. '01 = Entry name '02 = Specified value
001300	Bind list does not match query (do not use '@__p' string).	SQR reserves the variable names that start with "@__p" for internal use. Edit the source code and use different variable names.
001301	Forward references not permitted in select list bind variables.	Within the body of BEGIN-SQL paragraphs, forward references to &column names are not permitted. Move the BEGIN-SQL paragraph after the &column definition.
001302	SQL buffer too small; use -Mfile to increase SQLSIZE.	The SQL statement exceeds the size of the internal SQL buffer. Use the -Mfile flag on the command line to specify a file containing an entry that increases the currently defined value.

Error Number	Error Message	Suggestion/Interpretation
001303	Error in SQL (perhaps missing &name after expression):	The database server has determined that the SQL statement is in error. The actual error text from the server follows this message. Correct the SQL statement.
001304	Check SELECT columns, expressions and 'where' clause for syntax.	The database server has determined that the SQL statement is in error. The actual error text from the server follows this message. Correct the SQL statement.
001305	CMPSQL: Unknown data type in database: '01.	Contact technical support with the version of the database you are connected to. '01 = Datatype in question
001306	Bind value too large (IMAGE, TEXT not allowed).	IMAGE and TEXT data types cannot be used as bind variables. Modify your SQL statement to use other columns to perform the same selection logic.
001307	CMPSQL: DBDEFN failed.	(ODBC, Oracle, Informix) This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
001308	'01: Could not bind column '02.	(ODBC, Oracle, Informix) This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Name of the SQR routine '02 = Name of the column
001309	The type for '&'01' ('02) does not match the type from the database ('03).	Correct the source code. '01 = Name of the column/expression pseudonym '02 = User specified type '03 = Database type
001400	Only numerics allowed for arithmetic.	Only #numeric variables, &columns, and literals are permitted in the arithmetic commands. Correct the source code.

Error Number	Error Message	Suggestion/Interpretation
001401	Optional qualifier is ROUND=n (0-'01).	Correct the syntax. '01 = Maximum value for ROUND=
001402	Optional qualifiers for DIVIDE are ON- ERROR={HIGH ZER O} and ROUND=n.	Correct the syntax.
001403	Attempting division by zero.	Use the ON-ERROR = HIGH ZERO option to prevent this error from halting the program.
001404	Bad number of digits to ROUND or TRUNC (0-15).	Correct the syntax.
001405	WARNING: The ROUND or TRUNC qualifier is greater than the number's precision.	Correct the syntax.
001500	Array element out of range ('01) for array ''02' on line '03.	Correct the source logic. '01 = Element number passed '02 = Name of the array '03 = Program line number
001501	Field element out of range ('01) for array ''02', field ''03', on line '04.	Correct the source logic. '01 = Element number passed '02 = Name of the array '03 = Name of the field '04 = Program line number
001502	WARNING: Attempting division by zero on line '01. Array field ''02' unchanged. Run continuing...	The ARRAY-DIVIDE command has attempted division by zero. The division has been ignored; the result field is unchanged. Add logic to account for this possibility. '01 = Program line number '02 = Name of field
001601	'FILL' not appropriate for numeric data.	The FILL argument to the PRINT command may be used only for text fields. Move the #numeric variable to a \$string variable, and then print the string variable.
001700	Report ''01': Columns must be between 1 and the page width ('02).	The specified value is wider than the width of the page. Correct the source line. '01 = Name of the current report '02 = Page width

Error Number	Error Message	Suggestion/Interpretation
001702	Report ''01': GOTO- TOP='02 must be between 0 and the page depth ('03).	The value specified on the GOTO-TOP argument of the NEXT-COLUMN command was either less than 1 or greater than the page depth. Correct the source line. '01 = Name of the current report '02 = Goto-Top value '03 = Page width
001703	Report ''01': ERASE- PAGE='02 must be between 0 and the page depth ('03).	The line number specified on the ERASE- PAGE argument of the NEXT-COLUMN command is greater than the page depth. Correct the source line. '01 = Name of the current report '02 = Erase-Page value '03 = Page width
001704	Report ''01': The NEXT-COLUMN command is not legal in the '02 section with the qualifier AT-END=NEWPAGE.	Correct the source line. '01 = Name of the current report '02 = Name of the section
001705	Report ''01': Column number '02 is not defined.	The column number specified with the USE- COLUMN command is greater than the highest column defined in the COLUMNS command. Correct the source line. '01 = Name of the current report '02 = Column number
001800	Format for CONNECT: username/password [ON-ERROR= procedure[(arg1[,argi]...)]]	Correct the syntax.
001801	Cannot use CONNECT while SQL statements are active.	Correct the program logic to ensure that all BEGIN-SELECT paragraphs have completed before executing the CONNECT command.
001802	Logoff failed prior to CONNECT.	The database server returned an error while trying to log off from the database. SQR ends the program run since it cannot continue.

Error Number	Error Message	Suggestion/Interpretation
001803	CONNECT failed. Perhaps user name/password incorrect.	The specified connectivity information is incorrect or there might have been a network failure. Use the ON-ERROR flag to trap any errors during the program run; otherwise SQR ends the program run.
001804	Sybase extensions SET and SETUSER not permitted in SQR.	Remove SET and SETUSER from the source.
001805	USE allowed once in SETUP section only, not in BEGIN-SQL. Elsewhere, specify db.[user].table...	Correct the source.
001806	Out of query space. Use -Mfile to increase QUERIES.	The number of SQL statements has been exceeded. Use the -Mfile flag on the command line specify a file that contains an entry that increases a greater value than is currently defined.
001807	The requested database connection ('01) is already active.	The -Cnn value specified is being used by another BEGIN-SELECT paragraph that is currently selecting data. Use another connection number. '01 = Connection number
001808	Cannot find inactive database cursor. Program too large.	Too many BEGIN-SELECT and BEGIN- SQL paragraphs are active at the same time. Reduce the complexity of the program.
001809	Database commit failed.	(DB2, ODBC, Oracle) This is an error that should never occur during normal operations. Record the steps leading up to the error and contact your system administrator.
001810	Database rollback failed.	(DB2, ODBC, Oracle) This is an error that should never occur during normal operations. Record the steps leading up to the error and contact your system administrator.

Error Number	Error Message	Suggestion/Interpretation
001811	Cannot open database cursor.	(ODBC, Oracle) This is an error that should never occur during normal operations. Record the steps leading up to the error and contact your system administrator.
001901	Variable for date-time must begin with '&'.	Correct the syntax.
001913	Format code must be SYYYY when specifying signed year.	Correct the edit mask.
001914	Bad input data ('01) for edit mask: ''02'.	Correct the input. '01 = Data being converted '02 = Edit mask
001915	Year cannot be zero.	Correct the date.
001916	Year must be between -4713 and 9999 inclusive.	Correct the date.
001917	Ambiguous date-time.	Correct the date.
001918	''01' is not a valid date part.	Correct the date part. '01 = Date part.
001919	Invalid day of week.	Correct the date.
001920	Format code cannot appear in date input format: ''01'.	Correct the edit mask. '01 = Improper format characters.
001921	Bad date mask starting at: ''01'.	Correct the edit mask. '01 = Improper format characters.
001922	Seconds past midnight must be between 0 and 86399.	Correct the date.
001923	Seconds must be between 0 and 59.	Correct the date.
001924	Minutes must be between 0 and 59.	Correct the date.
001925	Month must be between 1 and 12.	Correct the date.

Error Number	Error Message	Suggestion/Interpretation
001926	Day must be between 1 and '01.	Correct the date.
001927	Hour must be between 1 and 12.	Correct the date.
001928	Hour must be between 0 to 23.	Correct the date.
001929	HH24 precludes the use of meridian indicator.	Correct the edit mask.
001930	HH12 requires meridian indicator.	Correct the edit mask.
001931	Day of year must be between 1 and 365 (366 for leap year).	Correct the date.
001932	Date string too long.	Correct the date.
001933	The month ('01) is not valid for the current locale or database.	Correct the date. '01 = Name of the month.
001934	The format mask must be a literal when the date-time is not loaded into a variable.	Correct the format mask. The format mask must be a literal when the date-time is not loaded into a variable.
001935	Date-time format too long.	Correct the format mask.
001936	Bad date-time format.	Correct the format mask.
001937	Bad SQL for default date-time. (Table DUAL required for syntax.)	(Oracle) Possibly the format mask needs to be corrected; otherwise, there is a problem with the database server.
001937	Bad SQL for default date-time. (Table DUAL required for syntax.)	(DB2) Possibly the format mask needs to be corrected; otherwise, there is a problem with the database server.
001938	Cannot recompile sql.	A fatal error relating to the SQL statement used to retrieve the date-time was encountered. Record the steps leading up to the error and contact your system administrator.

Error Number	Error Message	Suggestion/Interpretation
001939	Problem executing cursor.	A fatal error relating to the SQL statement used to retrieve the date-time was encountered. Record the steps leading up to the error and contact your system administrator.
001940	Error fetching row.	A fatal error relating to the SQL statement used to retrieve the date-time was encountered. Record the steps leading up to the error and contact your system administrator.
001941	Cannot redefine variable addresses.	A fatal error relating to the SQL statement used to retrieve the date-time was encountered. Record the steps leading up to the error and contact your system administrator.
001942	The date '01' is not in the format SYYYYMMDD[HH24[MI[SS[N NNNNN]]]].	When specifying an SQR date, at a minimum, the date must be specified; the time is optional. '01 = The invalid date.
001943	The date '01' is not in one of the accepted formats listed below: MM/DD/YYYY [BC AD] [HH:MI[:SS[.NNNNN N]] [AM PM]] MM-DD-YYYY [BC AD] [HH:MI[:SS[.NNNNN N]] [AM PM]] MM.DD.YYYY [BC AD] [HH:MI[:SS[.NNNNN N]] [AM PM]] SYYYYMMDD[HH24[MI[SS[N NNNNN]]]]	The date specified with the INPUT command was not in one the default formats. Please reenter the date in a valid format. '01 = The invalid date.
001944	The date '01' is not in the format specified by SQR_DB_DATE_FORMAT or in one of the accepted formats listed below: DD-MON-YY SYYYYMMDD [HH24[MI[SS[N NNNNN]]]]	(Oracle) The date was not in one of the expected formats for this database. '01 = The invalid date.

Error Number	Error Message	Suggestion/Interpretation
001944	The date '01' is not in the format specified by SQR_DB_DATE_FORMAT or in one of the accepted formats listed below: Mon DD YYYY [HH:MI[:SS [.NNN]]] [AM PM]] Mon DD YYYY [HH:MI[:SS[:NNN]]] [AM PM]] YYYYMMDD [HH:MI[:SS [.NNN]]] [AM PM]] YYYYMMDD [HH:MI[:SS[:NNN]]] [AM PM]] SYYYYYMMDD[HH24[MI[SS[N NNNNN]]]]	(Sybase) The date was not in one of the expected formats for this database. '01 = The invalid date.
001944	The date '01' is not in the format specified by SQR_DB_DATE_FORMAT or in one of the accepted formats listed below: Mon DD YYYY [HH:MI[:SS [.NNN]]] [AM PM]] Mon DD YYYY [HH:MI[:SS[:NNN]]] [AM PM]] YYYYMMDD [HH:MI[:SS [.NNN]]] [AM PM]] YYYYMMDD [HH:MI[:SS[:NNN]]] [AM PM]] SYYYYYMMDD[HH24[MI[SS[N NNNNN]]]]	(ODBC) The date was not in one of the expected formats for this database. '01 = The invalid date.
001944	The date '01' is not in the format specified by SQR_DB_DATE_FORMAT or in one of the accepted formats listed below: YYYY-MM-DD HH:MI:SS.NNN SYYYYYMMDD[HH24[MI[SS[N NNNNN]]]]	(Informix) The date was not in one of the expected formats for this database. '01 = The invalid date.

Error Number	Error Message	Suggestion/Interpretation
001944	The date ''01' is not in the format specified by SQR_DB_DATE_FORMAT or in one of the accepted formats listed below: YYYY-MM-DD[-HH.MI.SS[.NNNNNN]] MM/DD/YYYY DD.MM.YYYY SYYYMMDD[HH24[MI[SS[N NNNN]]]]	(DB2) The date was not in one of the expected formats for this database. '01 = The invalid date.
001945	SQR does not support dates before ''01'.	SQR does not support dates before the one specified in the message. '01 = Smallest date
001946	The date variables are incompatible with each other.	The SQR function references two date variables which cannot logically be used together (for example, DateDiff of 'date- only' and 'time-only' dates).
002000	Procedure name used more than once: ''01'.	Give the procedure a unique name. '01 = Procedure name
002001	Could not find procedure: ''01'.	Check for a misspelled procedure name. '01 = Procedure name
002002	DO arguments do not match procedure's.	The argument lists for the DO and BEGIN- PROCEDURE commands must match in both type and count. Correct the source line.
002003	DO argument must be \$string or #number to accept returned value.	Correct the syntax.
002100	Edit string too long.	The edit mask must be less than 255 characters. Reduce the length of the edit mask.
002101	Bad numeric 'edit' format: '01	The numeric edit mask contains an invalid character. See the PRINT command for the valid numeric edit mask characters. '01 = Invalid character

Error Number	Error Message	Suggestion/Interpretation
002103	DOLLAR-SYMBOL must be a single alphanumeric character or its decimal value enclosed in brackets: <nnn>.	Correct the syntax.
002104	DOLLAR-SYMBOL cannot be any of the following characters: '01	Correct the syntax. '01 = List of invalid characters
002106	MONEY-SYMBOL must be a single alphanumeric character or its decimal value enclosed in brackets: <nnn>.	Correct the syntax.
002107	MONEY-SYMBOL cannot be any of the following characters: '01	Correct the syntax.
002200	ENCODE string too large; maximum is '01.	Break up the ENCODE command. '01 = Maximum length of an ENCODE string supported by this version of SQR
002300	EXIT-SELECT failed.	The database command to cancel the query returned an error. Try running the SQR program again. The error could be related to a network or server problem. If the error persists, contact your system administrator.
002301	EXIT-SELECT valid only within SELECT paragraph.	Remove the EXIT-SELECT command.
002400	Duplicate label's - do not know which one to GOTO.	Labels must be unique within the section or paragraph where they are defined. Give each label a unique name.
002401	(Labels must be in same section or paragraph as GOTO.) Cannot find a matching label for GOTO command.	Check the source code.
002500	Error getting INPUT.	The C routine "fgets()" returned an error and SQR ends the program run.
002501	Unknown INPUT datatype: type={ char number integer date}	Correct the syntax.

Error Number	Error Message	Suggestion/Interpretation
002502	INPUT STATUS= must reference #variable.	Correct the syntax.
002503	Unknown qualifier for INPUT.	Correct the syntax.
002506	Too long. Maximum '01 characters.	The response to the INPUT statement was too long. Re-enter the data. '01 = Maximum characters allowed
002507	Incorrect. Format for floating point number: [+]-]99.99[E99]	Invalid number was entered for an INPUT request. Re-enter the data.
002508	Incorrect. Format for integer: [+]-]999999	Invalid integer was entered for an INPUT request. Re-enter the data.
002510	A format mask can only be specified when TYPE=DATE is used.	Correct the syntax.
002511	The format mask cannot be stored in a date variable.	Correct the syntax.
002512	The input variable type does not match the TYPE qualifier.	Correct the syntax.
002513	Number too large for INTEGER. Valid range is -2147483648 to 2147483647.	The number was too large to be stored as an integer. Values are from -2147483648 to 2147483647. Re-enter the data.
002514	Enter a date in one of the following formats: MM/DD/YYYY [HH:MI[:SS [.NNNNN N]] [AM PM]] MM-DD-YYYY [HH:MI[:SS [.NNNNN N]] [AM PM]] MM.DD.YYYY [HH:MI[:SS [.NNNNN N]] [AM PM]] SYMMDD[HH24[MI[SS[N NNNNN]]]]	The date cannot be blank. Enter a date in one of the specified formats.

Error Number	Error Message	Suggestion/Interpretation
002515	'01 required user interaction but user interaction was disabled by the -XI command line flag.	The specified command required user interaction, but user interaction was disabled by the -XI command line flag. '01 = Name of the command
002600	LOAD-LOOKUP table ''01' has not been defined.	Add a LOAD-LOOKUP command. '01 = Load lookup table name
002601	Missing value for '01= in LOAD-LOOKUP.	Correct the syntax. '01 = Name of missing required parameter
002602	Bad value for '01= in LOAD-LOOKUP.	Correct the syntax. '01 = Name of the parameter
002603	LOAD-LOOKUP '01= cannot reference a variable in the Setup section.	Either move the LOAD-LOOKUP command from the Setup section or remove the variable reference. '01 = Name of the parameter
002604	LOAD-LOOKUP names must be unique.	Give each LOAD-LOOKUP array a unique name.
002605	Cannot compile SQL for LOAD-LOOKUP table ''01'.	The database server returned an error while trying to compile the SQL statement needed to process the LOAD-LOOKUP command. Check the column and table names. Also check the WHERE= clause for errors. '01 = Load lookup table name
002606	Could not set up cursor for LOAD-LOOKUP table ''01'.	The database server returned an error while trying to compile the SQL statement needed to set up the LOAD-LOOKUP command. Check the column and table names. Also check the WHERE= clause for errors. '01 = Load lookup table name
002607	Problem executing the cursor for LOAD- LOOKUP table ''01'.	The database server returned an error while trying to execute the SQL statement needed to process the LOAD-LOOKUP command. '01 = Load lookup table name

Error Number	Error Message	Suggestion/Interpretation
002609	Integers only allowed in numeric lookup keys.	Correct the source line.
002610	Numeric lookup keys must be <= '01 digits.	Correct the source line. '01 = maximum length supported
002611	Bad return fetching row from database in LOAD-LOOKUP table '01'.	The database server returned an error while fetching the data. '01 = Load lookup table name
002613	Loading '01' lookup table ...	This message can be inhibited by using the QUIET argument on the LOAD-LOOKUP command. '01 = Name of the load lookup table '02 = Number of rows loaded
002615	Warning: '01 duplicate keys found in '02' lookup table.	This message can be inhibited by using the QUIET argument on the LOAD-LOOKUP command. '01 = Number of duplicate keys '02 = Name of the load lookup table
002616	LOAD-LOOKUP '01= must reference a numeric variable or literal.	Correct the source line. '01 = Name of the parameter
002617	LOAD-LOOKUP '01= must reference a string variable or literal.	Correct the source line. '01 = Name of the parameter
002618	LOAD-LOOKUP '01= variable '02' has not been defined.	Correct the source line. '01 = Name of the parameter '02 = Name of the undefined variable
002619	LOAD-LOOKUP cannot support '01 rows; maximum is '02.	Reduce the ROWS= value. '01 = ROWS= value '02 = Maximum value allowed
002620	'01 command not allowed with -XL option in effect.	Either use the #IF command to conditionally compile the program when -XL is being used or do not execute this SQR report with the -XL option. '01 = SQR command
002700	Line to stop erasing for 'NEW-PAGE' is larger than the page depth.	Correct the source line.

Error Number	Error Message	Suggestion/Interpretation
002800	'ON-BREAK' not appropriate for numeric data.	The ON-BREAK argument to the PRINT command may be used only for text fields. Move the #numeric variable to a \$string variable, and then print the \$string variable.
002801	SET= and LEVEL= must be >= zero when indicated.	Correct the source line.
002802	Cannot use old style PROCEDURE= with BEFORE= or AFTER=.	Correct the syntax.
002803	Out of ON-BREAKS; use -Mfile to increase ONBREAKS.	Use the -Mfile flag on the command line to specify a file containing an entry that increases the currently defined value.
002804	SET= must be same for all ON-BREAKs in Select.	All the ON-BREAKS in a query must belong to the same SET. Use SET= to differentiate between ON-BREAKs in different queries. Correct the source line.
002805	ON-BREAK with BEFORE or AFTER must be inside Select.	Correct the source line.
002806	SAVE= must be a \$string variable.	Correct the syntax.
002900	Record :types are FIXED, VARY or FIXED_NOLF (default is VARY).	Correct the syntax.
002901	STATUS variable for '01 must be #Numeric.	Correct the syntax. '01 = SQR command affected
002902	OPEN missing required qualifiers: RECORD={rec_len} FOR-READING FOR-WRITING FOR- APPEND	Correct the syntax.
002903	Too many external files opened; maximum is '01.	Reduce the number of open external files needed by the program. '01 = Maximum number of open external files supported by this version of SQR

Error Number	Error Message	Suggestion/Interpretation
002904	File number already opened.	Check your program logic.
002905	Cannot open file '01' AS '02.('03): '04	SQR quits. '01 = Filename '02 = File number '03 = System error code '04 = System error message
002906	Cannot close file '01. ('02): '03	SQR quits. '01 = File number '02 = System error code '03 = System error message
002907	Problem closing user file(s) at the end of run.	This message may indicate system problems.
002908	Warning: Cannot CLOSE file '01 -- file not opened.	While not an error, this message indicates a problem with your SQR code. '01 = File number
003000	PAGE-NUMBER strings too long.	The pre-and post-PAGE-NUMBER strings must be less than 74 characters. Correct the source line.
003100	Cannot find document marker referenced in POSITION command.	Defines the specified @ marker in a BEGIN- DOCUMENT paragraph. Check for a misspelled @ marker name.
003101	Only 'COLUMNS nn...' allowed after document marker in POSITION command.	Correct the syntax.
003200	Specified file number not opened for reading.	Files must be opened for reading in order to use the READ command with them. Correct the program logic.
003201	Line '01: Error reading the file. ('02): '03	'01 = Program line number '02 = System error code '03 = System error message
003202	Specified file number not opened for writing.	Files must be opened for writing in order to use the WRITE command with them. Correct the program logic.

Error Number	Error Message	Suggestion/Interpretation
003203	Line '01: Error writing the file. ('02): '03	'01 = Program line number '02 = System error code '03 = System error message
003204	Length of variables exceeds record length.	The total of the lengths indicated in the command must be less than the RECORD= argument used on the OPEN command. Check for a typographical error or recalculate the RECORD= value.
003205	Numeric binary transfer allowed with FIXED or FIXED_NOLF records only.	By default, all files are opened in VARY (variable length) mode, thus prohibiting the transfer of numeric binary data. Add the:FIXED or FIXED_NOLF option to the RECORD= argument on the appropriate OPEN command.
003206	Command not complete.	Correct the syntax.
003207	File number must be a numeric literal, variable, or column.	Correct the syntax.
003208	Missing required length in READ command.	Correct the syntax.
003209	Bad length for READ or WRITE command.	Correct the syntax.
003210	\$String or #numeric variables required for READ.	Correct the syntax.
003211	#Numeric variables and literals must have :length of 1, 2 or 4 bytes.	Correct the syntax.
003212	#Numeric variables and literals on CDC may only have :length of 1 or 3 bytes.	Correct the syntax.
003213	:Length not allowed for \$date variables, length of 18 is assumed.	Correct the syntax.
003300	Unknown qualifier for STOP.	Correct the syntax.

Error Number	Error Message	Suggestion/Interpretation
003301	Program stopped by user request.	Informational message.
003400	Wrap not appropriate for numeric data.	The WRAP argument to the PRINT command may be used only for text fields. Move the #numeric variable to a \$string variable first, and then print the \$string variable.
003401	Max '01 chars/line for reverse WRAP.	Reduce the number of characters specified. '01 = Maximum number of characters supported by this version of SQR.
003402	Max '01 chars/line for WRAP with ON= or STRIP=	Reduce the number of characters specified. '01 = Maximum number of characters supported by this version of SQR
003403	Bad <number> in WRAP qualifier.	The number inside the angled brackets must be a valid number (1 - 255). Correct the source line.
003404	Missing '>' in WRAP qualifier.	A leading "<" in the ON= or STRIP= qualifier indicates that a numeric value is following, which must be ended by a closing ">". Correct the source line.
003405	The value for '01' ('02) must be '03 0.	The value specified for the specified qualifier is invalid. Correct the program logic. '01 = Qualifier name '02 = Value encountered '03 = Relation to zero (<,<=,=,>=,>)
003500	PUT, GET or ARRAY- xxxx command incomplete. Required word missing.	Correct the syntax.
003501	Did not find end of literal.	The ending quote character (') was not found at the end of the literal. Add the ending quote character.
003502	Literal too long.	Literal strings can be up to 256 characters long. Break up the literal into smaller pieces and combine using the LET command.

Error Number	Error Message	Suggestion/Interpretation
003503	Unknown variable type.	Variable names must begin with \$, #, or &. Correct the source line.
003504	Cannot find 'array_name (#element)'.	The element number was not specified. Correct the source line.
003505	'(#Element)' variable not found for array.	Each GET or PUT command must indicate the element or row number to access in the array. Correct the source line.
003506	Array specified not defined with CREATE-ARRAY.	Use the CREATE-ARRAY command to define each array before referencing that array in other commands. Check for a misspelled array name.
003507	Bad element reference for array (#variable 123).	The element number is larger than the number of rows defined in the CREATE-ARRAY command. Check program logic to make sure that the element number was not inadvertently changed.
003508	Did not find ending ')' for field.	The "occurs" number for an array field is missing a right parenthesis. Correct the source line.
003509	Field not defined in array: '01	Check for a misspelled field name against the CREATE-ARRAY command. '01 = Undefined field name
003510	More variables than fields specified in array command.	The ARRAY command must not have more variables listed to the left of the array name than there are matching fields defined for the array. Check against the CREATE-ARRAY command.
003511	More variables in command than fields in array.	The ARRAY command must not have more variables listed to the left of the array name than there are matching fields defined for the array. Check against the CREATE-ARRAY command.

Error Number	Error Message	Suggestion/Interpretation
003512	Only numeric variables and fields allowed with array arithmetic commands.	The ARRAY-ADD, ARRAY-SUBTRACT, ARRAY-MULTIPLY, and ARRAY-DIVIDE commands may have only numeric variables or literals as the source fields. Move the string data into a #numeric variable and then reference the #numeric variable.
003513	GET can only be used with \$string or #numeric variables.	You can move array fields only into \$string variables or #numeric variables. Correct the source line.
003514	PUT and GET variables must match array field types.	When moving data into or out of arrays, the source or destination variables must match the array fields in type. CHAR fields can be stored into/from strings, NUMBER fields into/from numeric variables. Check the CREATE-ARRAY command.
003515	More fields than variables found in array command.	The ARRAY command must not have more variables listed to the left of the array name than there are matching fields defined for the array. Check against the CREATE-ARRAY command.
003516	Too many arrays defined; maximum is '01.	Reduce the number of arrays needed by the program. '01 = Maximum number of arrays supported by this version of SQR
003517	Missing '=specifier' in qualifier: '01	Correct the syntax. 01 = Name of missing required parameter
003518	Duplicate array name: '01	Change the name of the array. '01 = Array name in question
003519	Too many fields defined; maximum is '01.	Reduce the number of fields. '01 = Maximum number of fields allowed per array
003520	Missing ':type' in CREATE-ARRAY FIELD= '01	Correct the syntax. '01 = The name of the field

Error Number	Error Message	Suggestion/Interpretation
003521	Duplicate FIELD name: '01	Change the name of one of the fields. '01 = The name of the field
003522	Optional :nn for FIELD must be between 1 and 64K.	Correct the source line.
003523	CREATE-ARRAY FIELDS :type must be one of the following: '01	Correct the syntax.
003525	Missing NAME= in CREATE-ARRAY.	Correct the syntax.
003526	Missing or incorrect SIZE= in CREATE-ARRAY.	Correct the syntax.
003527	Missing FIELD= statements in CREATE-ARRAY.	Correct the syntax.
003528	Array dimensioned too large for PC in CREATE-ARRAY.	On 32-bit systems, the maximum allocation that can be made is 65520 characters. The array as specified would exceed this limit. Reduce the number of entries.
003529	Missing or invalid initialization value for field '01.	Correct the syntax. 01 = Name of the field
003600	Missing 'ask' variable name.	Correct the syntax.
003601	Out of substitution or #DEFINE variables; use -Mfile to increase SUBVARS.	Use the -Mfile flag on the command line to specify a file containing an entry that increases the currently defined value.
003603	WARNING: Substitution variables do not vary when saved with run-time.	Informational message.
003605	No substitution variable entered.	The C routine "fgets()" returned an error and SQR ends the program run.

Error Number	Error Message	Suggestion/Interpretation
003700	Did not find end of paragraph: '01	Missing the END-paragraph command to match the specified paragraph. Correct the source file. '01 = BEGIN-paragraph in question
003701	Invalid command.	Check for a misspelled command.
003702	Command not allowed in this section: '01	Correct the syntax. '01 = Offending command name
003703	Paragraph not allowed inside procedure.	The BEGIN-paragraph command is not allowed here. Check your SQR code for a misplaced paragraph.
003704	Missing procedure name.	Correct the syntax.
003705	Extra argument found.	Correct the syntax.
003706	Missing Comma.	Correct the syntax.
003707	Bad Argument List.	The DO or BEGIN-PROCEDURE command has an error in its argument list, possibly extra characters after the final right parentheses. Correct the source line.
003708	Empty Argument.	The DO or BEGIN-PROCEDURE command has an error in its argument list, possibly two commas in a row inside the parentheses. Correct the source line.
003709	Only \$string and #number variables allowed for BEGIN-PROCEDURE parameters.	Correct the syntax.
003710	Unknown argument type.	An argument in a DO or BEGIN-PROCEDURE command is incorrect. Check for a misspelled variable type.
003711	Indicate :\$string or :#number returned values in BEGIN-PROCEDURE only.	Correct the syntax.

Error Number	Error Message	Suggestion/Interpretation
003712	Missing).	Correct the syntax.
003713	'01 paragraph not allowed with -XL option in effect.	Either use the #IF command to conditionally compile the program when -XL is being used or do not execute this SQR report with the -XL option. '01 = Name of the BEGIN-paragraph
003714	Bad database connection number.	The -Cnn value must be a non-zero value. Correct the source line.
003715	Did not find end of paragraph: '01 (No 'from...' clause found.)	Correct the source code. '01 = BEGIN-command in question
003716	Error in SQL statement.	The database server has determined that the SQL statement is in error. The actual error text from the server follows this message. Correct the SQL statement.
003717	Extra characters after expression continuation.	Remove the extra characters after the dash.
003718	Did not find end of expression.	An expression in a SELECT list must end with either a &column variable or a position parameter "(Row,Col,Len)". Correct the source line.
003719	Columns names and expressions must be unique or be given unique pseudonyms (&name).	Columns retrieved from the database are assigned names by prepending an "&" to the beginning of the name. You are trying to select the same &column name more than once. Change the assigned &column name by using an alias after the name.
003720	Bad number specified for 'LOOPS=' on 'BEGIN-SELECT; Maximum is 32767'.	If your program logic requires that you stop processing after more than 32767 rows have been retrieved, you could count the rows manually and use the EXIT-SELECT command to break out of the SELECT loop.

Error Number	Error Message	Suggestion/Interpretation
003721	Bad param found on 'BEGIN-SELECT' line; Format is: BEGIN-SELECT [DISTINCT] [-Cnn] [- Bnn] [LOOPS=nn] [ON- ERROR=procedure[(arg1[,argi...]...)]	(DB2) Correct the syntax.
003721	Bad param found on 'BEGIN-SELECT' line; Format is: BEGIN-SELECT [DISTINCT] [-Cnn] [LOOPS=nn] [ON-ERROR= procedure[(arg1[,argi...]...)]	(Informix) Correct the syntax.
003721	Bad param found on 'BEGIN-SELECT' line; Format is: BEGIN-SELECT [DISTINCT] [-Cnn] [LOOPS=nn] [ON-ERROR= procedure[(arg1[,argi...]...)] [-DB=database]	(ODBC) Correct the syntax.
003721	Bad param found on 'BEGIN-SELECT' line; Format is: BEGIN-SELECT [DISTINCT] [-Cnn] [- Bnn] [LOOPS=nn] [ON- ERROR=procedure[(arg1[,argi...]...)]	(Oracle) Correct the syntax.
003721	Bad param found on 'BEGIN-SELECT' line; Format is: BEGIN-SELECT [DISTINCT] [-Cnn] [- XP] [LOOPS=nnn] [ON- ERROR=procedure[(arg1[,argi...]...)]	(Sybase) Correct the syntax.
003722	Could not set up cursor.	An error occurred while trying to compile the SQL statement. Look closely at any \$string variable references. Correct the SQL statement or use the ON-ERROR= option to trap the error during the program run.
003723	Problem executing cursor.	An error occurred while trying to execute the SQL statement. Look closely at any \$string variable references. Correct the SQL statement or use the ON-ERROR= option to trap the error during the program run.

Error Number	Error Message	Suggestion/Interpretation
003724	Could not exit query loop.	The database command to cancel the query returned an error. Try running the SQR program again. The error could be related to a network or server problem. If the error persists, contact your system administrator.
003725	Bad return fetching row from database.	The database returned an error status for the last row that was fetched, commonly due to the buffer not being large enough. If selecting expressions, make sure that the length of the first expression will be adequate for all rows selected.
003726	Literal in SQL expression missing closing quote.	Literals must be surrounded by single quotes (''). To embed a quote within a literal use two single quotes in sequence (''). Correct the source line.
003727	SQL expression not ended, perhaps parentheses not balanced.	An expression in a SELECT list must end with either a &column variable or a position parameter "(Row,Col,Len)". Correct the source line.
003728	SQL expression not ended, perhaps missing &name.	An expression in a SELECT list must end with either a &column variable or a position parameter "(Row,Col,Len)". Correct the source line.
003729	SQL expression is missing &name or has unbalanced parentheses.	An expression in a SELECT list must end with either a &column variable or a position parameter "(Row,Col,Len)". Correct the source line.
003730	Incorrect arguments for BEGIN-SQL: [-Cnn] [ON-ERROR=procedure[(arg1[,argi]...)]]	(DB2) Correct the syntax.
003730	Incorrect arguments for BEGIN-SQL: [-Cnn] [ON-ERROR=procedure[(arg1[,argi]...)]]	(Informix) Correct the syntax.

Error Number	Error Message	Suggestion/Interpretation
003730	Incorrect arguments for BEGIN-SQL: [-Cnn] [-NR] [ON- ERROR=procedure(arg1[,argi]...)] [-DB=]	(ODBC) Correct the syntax.
003730	Incorrect arguments for BEGIN-SQL: [-Cnn] [ON- ERROR=procedure[(arg1[,argi]...)]]	(Oracle) Correct the syntax.
003730	Incorrect arguments for BEGIN-SQL: [-Cnn] [-XP] [ON- ERROR=procedure[(arg1[,argi]...)]]	(Sybase) Correct the syntax.
003731	Did not find 'END- SQL' after 'BEGIN- SQL'.	Correct the source file.
003732	ON-ERROR= for 'BEGIN-SQL' in SETUP section must be STOP, WARN or SKIP.	03732 Correct the syntax.
003733	Could not create procedure for SQL.	(Sybase) SQR could not create a stored procedure for the SQL statement. The most likely cause for failure is that the user name you are using to run the report under does not have the proper privileges. Either grant the user CREATE PROCEDURE privilege or use the -XP command line option to inhibit SQR from creating temporary stored procedures for SQL statements.
003734	Could not compile SQL.	Correct the SQL statement or use the ON-ERROR= option to trap the error during the program run.
003735	Could not execute SQL.	An error occurred while trying to compile the SQL statement. Correct the SQL statement or use the ON-ERROR= option to trap the error during the program run.
003736	Please use BEGIN-SELECT - END-SELECT section for SELECT statements.	(Informix, ODBC, Oracle) Correct the source code.

Error Number	Error Message	Suggestion/Interpretation
003737	Bad fetch buffer count.	(Oracle, Sybase) The -B flag specifies an illegal value. Correct the source code.
003738	Report interrupted by request.	Informational message.
003741	Dynamic column must be \$string variable.	Correct the syntax.
003742	Dynamic column missing '01'.	Correct the syntax. '01 = Missing character
003743	Dynamic columns must have a &pseudonym.	Correct the syntax.
003744	&pseudonym =type must be 'char', 'number', or 'date'.	Correct the syntax.
003745	Only a variable name may be between the '01' and '02' characters.	Correct the syntax. '01 = Leading character '02 = Trailing character
003746	When dynamic columns are used all non-dynamic columns and expressions must be defined with &name=type.	Add &name=type to all expressions and non-dynamic columns.
003747	When the table name is dynamic each column and expression must be defined with &name=type.	Add &name=type to all expressions and non-dynamic columns.
003800	Too many document paragraphs; maximum is '01.	There are too many BEGIN-DOCUMENT paragraphs. Reduce the number of DOCUMENT paragraphs needed by the program. '01 = Maximum number supported by this version of SQR
003801	Too many document markers; maximum is '01.	There are too many BEGIN-DOCUMENT paragraphs. Reduce the number of DOCUMENT paragraphs needed by the program. '01 = Maximum number supported by this version of SQR

Error Number	Error Message	Suggestion/Interpretation
003802	Duplicate document marker.	Give the document marker a unique name.
003803	Did not find 'END- DOCUMENT' after 'BEGIN-DOCUMENT'.	The BEGIN-DOCUMENT paragraph must end with END-DOCUMENT. Correct the source code.
003900	EXECUTE command is incomplete.	Correct the syntax.
003901	Bad -Cnn connection number for EXECUTE.	The -Cnn value must be a nonzero value. Correct the source line.
003902	@#Return_status must be #numeric (missing #).	Correct the source line.
003903	Missing '=' after '01.	Correct the source line. '01 = The parameter in question
003904	Unknown variable type.	Variable names must begin with \$, #, or &. Correct the source line.
003905	OUT[PUT] variables for EXECUTE may only be \$variable or #variable.	Correct the syntax.
003906	The only EXECUTE option is WITH RECOMPILE.	Correct the syntax.
003907	You must EXECUTE ... INTO &columns.	Correct the syntax.
003908	Unknown datatype for EXECUTE...INTO &columns.	Check for a misspelled data type. If the data type is correct, then contact customer technical support so SQR can be updated.
003909	EXECUTE...INTO &columns must be unique.	The &column name assigned to the column must be unique throughout the report. Give the column a unique name.
003910	Missing (length) for datatype in EXECUTE.	Correct the source line.

Error Number	Error Message	Suggestion/Interpretation
003911	Datatype should not have (length) in EXECUTE.	Correct the source line.
003912	DO= in EXECUTE requires INTO... variables.	Correct the syntax.
003913	Could not EXECUTE stored procedure.	Record the database error message displayed with this message. If needed, contact your system administrator.
003914	Bad return fetching row from database.	Record the database error message displayed with this message. If needed, contact your system administrator.
003915	Could not set up EXECUTE cursor.	The database server returned an error while trying to compile the SQL statement needed to set up the EXECUTE command.
004000	Result #variable or \$variable or '=' missing in expression.	The LET command is not properly formatted. Correct the source line.
004001	Expression too complex.	The expression is either too long or is too deeply nested. Break the expression into smaller expressions.
004002	Parentheses unbalanced in expression.	A left or right parenthesis is missing. Correct the source line.
004003	Too many variables; maximum is '01.	Break the expression into smaller expressions. '01 = Maximum number supported by this version of SQR
004004	Empty expression.	The expression is invalid. Correct the source line.
004005	Extra comma in expression.	An argument is missing after a comma in the expression. Correct the source line.
004006	Unknown operator ''01'. Do you mean '02 ?	The concatenation operator is . Correct the source line.

Error Number	Error Message	Suggestion/Interpretation
004007	Too many &column forward references in expression; maximum is '01.	The expression contains too many forward references. Break the expression into smaller expressions. '01 = Maximum number supported by this version of SQR
004008	Unknown function or variable in expression: '01	The specified function is not an SQR built-in function nor does it exist in the user-modifiable file UFUNC.C. Check for a misspelled function name. '01 = Function name
004009	Function '01' missing parentheses.	All functions in an expression must be followed by their arguments enclosed in parentheses. Correct the source line.
004010	Empty parentheses or expression.	A pair of parentheses were found with nothing inside them. Remove the () in question from the source line.
004011	User function '01' has incorrect number of arguments.	Look at the file UFUNC.C to determine the correct number and type of arguments required for the specified function. '01 = User function name
004012	Function '01' has incorrect number of arguments.	Correct the syntax of the function. Functions are described under the LET command. '01 = SQR function name
004013	Missing operator in expression.	Correct the source line.
004014	Operator '01' missing argument.	Correct the syntax of the function. Functions are described under the LET command. '01 = Operator
004015	Function '01' missing argument.	Correct the syntax of the function. Functions are described under the LET command. '01 = SQR function name

Error Number	Error Message	Suggestion/Interpretation
004016	Function or operator '01' missing arguments.	Correct the syntax of the function. Functions are described under the LET command. '01 = SQR function name
004017	User function '01' requires character argument.	Look at the file UFUNC.C to determine the correct number and type of arguments required for the specified function. '01 = User function name
004018	User function '01' requires numeric argument.	Look at the file UFUNC.C to determine the correct number and type of arguments required for the specified function. '01 = User function name
004019	User function '01' requires \$string variable.	Look at the file UFUNC.C to determine the correct number and type of arguments required for the specified function. '01 = User function name
004020	User function '01' requires #numeric variable.	Look at the file UFUNC.C to determine the correct number and type of arguments required for the specified function. '01 = User function name
004021	User function '01' has incorrect argument type list. Must be of: c,n,C,N	The UFUNC.C file has a bad definition for the specified function. Correct the UFUNC.C program file; recompile UFUNC.C; and recreate the SQR executable. '01 = User function name
004022	User function '01' missing arguments.	Look at the file UFUNC.C to determine the correct number and type of arguments required for the specified function. '01 = User function name
004023	User function '01' has incorrect return type. Must be c or n.	The UFUNC.C file has a bad definition for the specified function. Correct the UFUNC.C program file; recompile UFUNC.C; and recreate the SQR executable. '01 = User function name

Error Number	Error Message	Suggestion/Interpretation
004024	'isnull' requires a &column, \$string or \$date argument.	#numeric variables cannot be NULL. Correct the source line.
004025	'nvl' requires a &column, \$string or \$date as its first argument.	#numeric variables cannot be NULL. Correct the source line.
004026	Function or operator ''01' requires character argument.	Correct the source line. '01 = Function or operator
004027	Function or operator ''01' requires numeric argument.	Correct the source line. '01 = Function or operator
004028	IF or WHILE expression must return logical result.	The expression used must evaluate a statement that will be TRUE or FALSE. Correct the source line.
004029	Attempting division by zero in expression.	The expression tried to divide a number by zero. Use the COND() function to check if the divisor is zero; then divide by something else (for example, 1).
004030	Attempting division by zero with '%'	An attempt was made to divide a number using the "%" operator. Use the COND() function to check if the divisor is zero; then divide by something else (for example, 1).
004031	The number used with '%' ('01) is out of range.	The "%" operator works with integers only. Correct the program logic. '01 = Maximum value allowed
004032	User function has unknown return type -- expecting n or c -- need to recompile Run-Time file?	SQR detected an error while processing a user defined function. If you are running an .sqr file, it probably needs to be recompiled because the user function has changed its definition. If you are running an .sqr file, then you need to correct the UFUNC.C program file; recompile UFUNC.C, and recreate the SQR executable.

Error Number	Error Message	Suggestion/Interpretation
004033	In user function use C type with allocated string to change \$variable.	SQR detected an error while processing a user defined function. Correct the UFUNC.C program file recompile UFUNC.C and recreate the SQR executable.
004034	Could not find array '01' in ARRAY function.	Check for a misspelled array name. '01 = Array name
004035	Could not find array field '01' in ARRAY function.	Check for a misspelled array field name. '01 = Array field name
004036	Math error in expression (usually over- or under-flow).	Most of the SQR mathematical built-in functions have a corresponding C library routine. One returned an error. Break the expression into discrete expressions in order to identify the function that caused the error.
004037	Error executing expression.	Record the steps leading up to the error and contact technical support.
004038	Out of space while processing expression; Use -Mfile to increase EXPRESSIONSPACE.	The expression requires more temporary string storage than is currently allocated. Use the -Mfile flag on the command line to specify a file that contains an entry that increases by a greater value than is currently defined.
004039	'01' assumed to be a variable name, not an expression.	Warning message. '01 = Expression in question
004040	The array '01' has not been defined.	Define the array using the CREATE-ARRAY command. '01 = Array name
004041	The field '01' is not valid for array '02'.	Correct the source code. '01 = Field name '02 = Array name
004042	The array reference '01' has an incorrect number of parameters specified.	Correct the source code. '01 = Array name

Error Number	Error Message	Suggestion/Interpretation
004043	The array reference '01' requires numeric parameters for the element and occurs arguments.	Correct the source code. '01 = Array name.
004045	Function or operator '01' requires date argument.	Correct the source code. '01 = Array name
004046	Incompatible types between expression and variable.	Correct the source code.
004047	The field '01' is must be 'char' or 'float'.	Correct the source code. '01 = Field name
004048	Function or operator '01' must be a string or date argument.	Correct the source line. '01 = Function or operator
004100	Use 'print' command to format data outside SELECT query.	You must precede PRINT command arguments (WRAP, ON-BREAK.) with an explicit PRINT command when outside of a BEGIN-SELECT paragraph. Correct the source line.
004101	Cannot find required parameter.	Correct the syntax.
004102	Bad number found.	A command expecting a numeric literal or :#numeric variable reference found an illegal number definition or a reference to a string variable or column. Correct the source line.
004103	Cannot find required numeric parameter.	Correct the syntax.
004104	Cannot find placement parameters.	The position qualifier "(Row,Col,Len)" was not found. Check for a missing parentheses.
004105	Placement parameter incorrect.	The "Row", "Column" or "Length" fields are invalid or ill-formed. Correct the source line.

Error Number	Error Message	Suggestion/Interpretation
004106	Invalid second function on line.	An SQR command used as a qualifier for a primary command (for example, PRINT) is incorrect. Correct the source line.
004107	Second function must be FORMAT type.	The PRINT command may have format command qualifiers such as WRAP, CENTER, or FILL. Other qualifier commands are not permitted.
004108	Missing operator =, <, >, ...	Correct the source line.
004109	Invalid operator.	Correct the source line.
004110	Missing variable.	Correct the syntax.
004111	Please give this expression a &pseudonym.	Expressions selected in a BEGIN-SELECT paragraph should be given an &Name or be followed by a print position "(Row,Col,Len)". Correct the source line.
004112	Wrong variable type.	Correct the syntax.
004113	Command incomplete, expected '01'.	Correct the syntax. '01 = What was expected
004114	Expecting '01', found '02'.	Correct the syntax. '01 = What was expected '02 = What was encountered
004115	Unknown command or extra parameters found (missing quotes?).	Correct the syntax.
004116	Duplicate references to parameter '01'.	Correct the syntax. '01 = Duplicated parameter
004117	Unexpected equal sign found with '01'.	Correct the syntax. '01 = Parameter name
004118	Qualifier '01' cannot be used with the following qualifiers:	Correct the syntax. '01 = Qualifier name

Error Number	Error Message	Suggestion/Interpretation
004119	Expecting numeric column, found string column.	Correct the syntax.
004120	Date variables ('01) cannot be used with this command.	Correct the syntax. '01 = Parameter name
004200	Page width and depth must be > 0 and < 32767.	The values specified with the PAGE-SIZE command are out of specified range. Specify legal values.
004201	Page buffer must be < 65536 on PC SQR.	The maximum allocation on a PC is 65536. The Page-Depth * Page-Width cannot exceed this value. Reduce the Page-Depth or Page-Width.
004202	Cannot generate line printer output for this report because position qualifier(s) may be out of range. If you are running this report, specify PRINTER:{HP,EH,HT,PS,WP} for graphical printer output.	The report output cannot be generated for a Line Printer. If your report was designed for a graphics printer, specify - PRINTER:{HP,EH,HT,PS,WP} for graphical printer output.
004300	Missing end of placement (...) in SHOW.	The placement parameter is ill-formed. Correct the source line.
004301	Bad (...) location in SHOW.	Screen positions must be valid numbers. Correct the source line.
004302	Missing literal or variable name to EDIT in SHOW.	The literal or variable name must immediately precede the EDIT, NUMBER, MONEY, or DATE keywords.
004303	Missing edit mask in SHOW.	The word EDIT must be followed by a valid edit mask. Correct the source line.
004304	Only string variable allowed for dynamic edit mask.	Dynamic edit masks may only be stored in \$Variables. Correct the line.
004305	Unknown option for SHOW.	Correct the syntax.

Error Number	Error Message	Suggestion/Interpretation
004400	Program too large; use -Mfile to increase PROGLINES.	The SQR program contains too many SQR command lines. Use the -Mfile flag on the command line to specify a file containing an entry that increases the currently defined value.
004401	Out of param storage; use -Mfile to increase PROGLINEPARS.	The SQR program contains too many SQR command line parameters. Use the -Mfile flag on the command line to specify a file containing an entry that increases the currently defined value.
004402	Out of string storage; use -Mfile to increase STRINGSPACE.	The space allocated to hold the static string variables ('...') has been used. Use the -Mfile flag on the command line to specify a file containing an entry that increases the currently defined value.
004403	Out of variables; use -Mfile to increase VARIABLES.	There are too many variables (string, numeric), literals and database columns. Use the -Mfile flag on the command line to specify a file containing an entry that increases the currently defined value.
004405	Out of forward &column or \$variable references; use -Mfile to increase FORWARDREFS.	A forward referenced variable is a variable that is referenced before it is defined. Use the -Mfile flag on the command line to specify a file containing an entry that increases the currently defined value.
004406	Number '01 not allowed.	Use a different value. '01 = Internal number
004407	Referenced variables not defined:	References were made to column variables (&var) that were not defined in the program. The list of variable names follows this message.

Error Number	Error Message	Suggestion/Interpretation
004500	Out of Print positions; use -Mfile to increase POSITIONS.	A print position is the "(Row,Col,Len)" parameter. Use the -Mfile flag on the command line to specify a file containing an entry that increases the currently defined value.
004501	Use '+' and negate variable for reverse relative placement.	The use of "-#Variable" is not legal here. Negate the #Variable value and use "+#Variable".
004503	Fixed line placement #variable must be > 0. Use relative positioning, (+#line,10,0).	Correct the source line as indicated.
004504	Fixed column placement #variable must be > 0. Use relative positioning, (5,+#col,0).	Correct the source line as indicated.
004505	Length placement #variable must be >= 0.	The length field cannot be a negative value. Correct the source line.
004600	CODE not appropriate for numeric data.	The CODE qualifier to the PRINT command may only be used for text fields. Move the "#Variable" to a "\$Variable" first and then print the "\$Variable".
004601	Unknown option for GRAPHIC command: BOX, HORZ-LINE, VERT-LINE or FONT	Correct the syntax.
004602	GRAPHIC BOX out of bounds. Row: '01, Column: '02, Width: '03, Depth: '04	SQR ends the program run. '01 = Row '02 = Column '03 = Width '04 = Depth
004603	GRAPHIC VERT- LINE out of bounds. Row: '01, Column: '02, Length: '03	SQR ends the program run. '01 = Row '02 = Column '03 = Length
004604	GRAPHIC HORZ- LINE out of bounds. Row: '01, Column: '02, Length: '03	SQR ends the program run. '01 = Row '02 = Column '03 = Length

Error Number	Error Message	Suggestion/Interpretation
004700	Cannot open the program file: '01' ('02): '03	Depends on the system error message. '01 = Name of the program file '02 = System error code '03 = System error message
004701	Cannot logon to the database.	The connectivity information is either incorrect or the database server is unavailable. Check the connectivity information and the server availability.
004702	Line found outside paragraph.	All commands must be within BEGIN-... END-statements. Correct the source code.
004703	Cannot close the program file. ('01): '02	Depends on the system error message. '01 = System error code '02 = System error message
004704	#ENDIF not found for #IF.	Missing an #ENDIF to complete conditional compilation. Correct the source code.
004705	Program line too long; maximum is '01.	Break the program line into smaller lines. '01 = Maximum line length supported by this version of SQR
004706	Substitution variable {'01} would cause this line to exceed the maximum line length of '02 characters.	The substitution variable value would cause this line to exceed the maximum line size. Break the program line into smaller lines. '01 = Name of the substitution variable '02 = Maximum line length supported by this version of SQR
004707	No value found for substitution variable: {'01}	An empty value was found for the substitution variable. Check for a misspelled name. '01 = Name of the substitution variable
004708	#ELSE without preceding #IF.	Missing an #IF or #IFDEF or #IFNDEF to begin conditional compilation. Correct the source code.

Error Number	Error Message	Suggestion/Interpretation
004709	#ENDIF without preceding #IF.	Missing an #IF or #IFDEF or #IFDEF to begin conditional compilation. Correct the source code.
004710	#IF's nested too deeply; maximum is '01.	Reduce the number of nested #IF directives. '01 = The maximum depth supported by this version of SQR
004711	#INCLUDE files nested too deeply; maximum is '01.	Reduce the number of nested #INCLUDE directives. '01 = The maximum depth supported by this version of SQR
004712	Include file name too long; Modify -I flag.	The combined -I directory name with the #INCLUDE file name exceeds the maximum length permitted for a complete pathname. Check the spelling of both the -I command flag and the #INCLUDE filename.
004713	Cannot open the #INCLUDE file: '01' ('02); '03	'01 = Include file name '02 = System error code '03 = System error message
004714	Cannot close the #INCLUDE file: '01' ('02); '03	'01 = Include file name '02 = System error code '03 = System error message
004716	'BEGIN-REPORT' command not found in program.	This section is required for all reports. Correct the source code.
004717	Cannot open the report output file: '01' ('02); '03	'01 = Output file name '02 = System error code '03 = System error message
004719	Cannot logoff the database.	The database server returned an error while trying to log off from the database. SQR ends the program run.
004720	Cannot open the run-time file: '01'. ('02); '03	SQR ends the program run. '01 = Run-Time file name '02 = System error code '03 = System error message

Error Number	Error Message	Suggestion/Interpretation
004721	Cannot close the run-time file. ('01): '02	SQR ends the program run. '01 = System error code '02 = System error message
004722	Error reading the run-time file. ('01): '02	SQR ends the program run. '01 = System error code '02 = System error message
004723	Run time file must be recreated for this version of SQR.	The runtime file was created by a earlier version of SQR and is incompatible with the current version. Recreate the .sqt (runtime) file.
004724	The -XL option cannot be specified with this run-time file because access to the database is required.	Do not use the -XL option.
004725	Cannot open cursor.	The database server returned an error indicating that a new database cursor or logon could not be completed. See the error message from the database server.
004726	Cannot create procedure for SQL statement.	(Sybase) SQR could not create a stored procedure for the SQL statement. The most likely cause for failure is that the user name you are running the report under does not have the proper privileges. Either grant the user CREATE PROCEDURE privilege or use the -XP command line option to inhibit SQR from creating temporary stored procedures for SQL statements.
004727	Error writing the runtime file. ('01): '02	'01 = System error code '02 = System error message
004728	You must specify a Partitioned Data Set name and member to build a .sqt(member) run-time file. Could not create the run-time file.	(MVS) Use the proper format to specify the name of the .sqt file.
004729	Cannot find inactive database cursor. Program too large.	(DB2, Oracle) The program has too many concurrent database cursors. Reduce the complexity of the program.

Error Number	Error Message	Suggestion/Interpretation
004730	Run-time saved in file: '01	Informational message. '01 = Name of the .sqt file created
004735	Unknown variable type encountered in run-time file: '01	SQR ends loading the runtime file. '01 = Variable type
004736	Unexpected End-Of- File while processing the run-time file.	SQR ends loading the runtime file.
004737	Cannot load the run- time file because it was built for the '01 database and '02 is built for the '03 database.	SQR ends loading the runtime file. '01 = Database name from runtime file '02 = SQR image name '03 = Database that SQR is built for
004738	'END-REPORT' not paired with 'BEGIN- REPORT'.	Correct the source code.
004739	'END-PROGRAM' not paired with 'BEGIN- PROGRAM'.	Correct the source code.
004743	#INCLUDE filename must be enclosed in quotation marks.	Correct the syntax.
004744	#INCLUDE command format is: #Include 'filename'.	Correct the syntax.
004745	Array field ('01.'02) specification exceeds the PC 64K limit.	Reduce the size of the field requirements. '01 = Array name '02 = Field name
004746	Layout ''01' specifications exceeds the PC 64K limit.	The layout is too large for the 32-bit version of SQR to handle. '01 = Layout name
004747	The SQT file is corrupted and cannot be processed.	SQR ends loading the runtime file.
004748	The user function ''01' needs to be defined as entry '02 in the user function table. It requires a definition of: Return Type = ''03' Arg Count = '04 Arg Types = ""05"	The SQT file requires that the specified user function be defined. '01 = User function name '02 = Entry in the user function table '03 = Return type '04 = Argument count '05 = Argument types

Error Number	Error Message	Suggestion/Interpretation
004749	An attempt was made to move '01 characters into ''02'. The maximum allowed is '03 characters.	An attempt was made to move too much data into an SQR string variable. '01 = Number of characters to be moved '02 = Variable name '03 = Maximum characters allowed
004802	PRINTER TYPE must be HTML, HPLASERJET, POSTSCRIPT, or LINEPRINTER.	Correct the syntax.
004805	Both BEFORE-BOLD and AFTER-BOLD must be specified.	Correct the syntax.
004807	Unknown DECLARE qualifier.	Correct the syntax.
004900	Out of dynamic SQL arguments [...]; use -Mfile to increase DYNAMICARGS.	Use the -Mfile flag on the command line to specify a file containing an entry that increases the currently defined value.
004901	Date variables ('01) cannot be used in BEGIN-SQL or BEGIN-SELECT paragraphs.	Correct the source code. '01 = Variable name
005000	Report ''01' heading section size exceeds the page depth.	Reduce the size of the heading or increase the page depth.
005001	Report ''01' footing location must be less than the page depth.	Reduce the size of the footing or increase the page depth.
005002	Check 'BEGIN- HEADING' commands: Discovered 2nd page-initialization while heading in progress.	The BEGIN-HEADING procedure either caused an overflow of the current page or it issued a command that caused a page eject to occur. Check any procedure invoked by the BEGIN-HEADING section to ensure that the commands do not overflow the page or cause a page eject.

Error Number	Error Message	Suggestion/Interpretation
005003	Check 'BEGIN-FOOTING' commands; perhaps number of footing lines is too small. Discovered 2nd page- write while footing in progress.	The BEGIN-FOOTING procedure either caused an overflow of the current page or it issued a command that caused a page eject to occur. Check any procedure invoked by the BEGIN-FOOTING section to ensure that the commands do not overflow the page or cause a page eject.
005004	Attempt to execute the '01 command while processing the '02 section.	Change the SQR program logic to prevent the command from executing while the specified section is active. '01 = Command name '02 = Section name
005005	Report ''01' already has been assigned a '02 section.	Correct the source code. '01 = Report name '02 = Duplicated section name
005006	You cannot define more than one default ''01' section.	Correct the source code. '01 = Duplicated section name
005007	Report ''01' has overlapping heading and footing sections.	Correct the source code. '01 = Report name
005008	TOC ''01' already has been assigned a '02 section.	Correct the source code. '01 = Table of Contents name '02 = Duplicated section name
005100	'IF', 'WHILE', 'EVALUATE' commands nested too deeply; maximum is '01.	Reduce the nested commands. '01 = Maximum depth allowed by this version of SQR
005101	'BREAK' found outside 'WHILE' or 'EVALUATE' statement.	The BREAK command is valid only in the context of a WHILE or EVALUATE statement. Correct the source code.
005102	Out of Break commands; Use -Mfile to increase BREAKS.	This is the number of BREAK commands allowed per EVALUATE command. Use the -Mfile flag on the command line to specify a file containing an entry that increases the currently defined value.
005103	END-WHILE found without matching 'WHILE'.	Correct the source code.

Error Number	Error Message	Suggestion/Interpretation
005104	'IF' or 'EVALUATE' command not completed before 'END-WHILE'.	Correct the syntax.
005105	'ELSE' found without matching 'IF'.	ELSE can be used only within the context of an IF command. Correct the source code.
005106	Single 'ELSE' found inside 'WHILE' or 'EVALUATE' statement.	ELSE can be used only within the context of an IF command. Correct the source code.
005107	Only one 'ELSE' allowed per 'IF'.	Rewrite the source code to use nested IF statements.
005108	Found 'END-IF' without matching 'IF'.	Each IF command must have a matching END-IF command. Correct the source code.
005109	'WHILE' or 'EVALUATE' command not completed before 'END-IF'.	You are missing a closing END-WHILE or END-EVALUATE command before END- IF. IF, WHILE, and EVALUATE statements can be nested, but they cannot cross each other's boundaries. Each inner statement must be complete before a closing statement is ended. Correct the source code.
005110	EVALUATE statements nested too deep; maximum is '01.	Reduce the number of nested statements. '01 = Maximum depth supported by this version of SQR
005111	'WHEN' found outside 'EVALUATE' clause.	WHEN may be used only in the context of an EVALUATE clause. Correct the source code.
005112	'IF' or 'WHILE' not completed before 'WHEN' statement.	Correct the syntax.
005113	Out of When commands; Use -Mfile to increase WHENS.	Use the -Mfile flag on the command line to specify a file containing an entry that increases the currently defined value.

Error Number	Error Message	Suggestion/Interpretation
005114	Incorrect types for comparison. Both must be of the same type (string, numeric or date).	Correct the source line.
005115	'When-other' found outside 'Evaluate' statement.	WHEN can be used only in the context of an EVALUATE statement. Correct the source code.
005116	'IF' or 'WHILE' not ended before 'WHEN- OTHER' command.	Correct the syntax.
005117	Only one 'WHEN- OTHER' allowed per 'EVALUATE'.	Correct the syntax.
005118	Found 'END-EVALUATE' without matching 'EVALUATE'.	Each EVALUATE command must have a matching END-EVALUATE command. Correct the source code.
005119	'IF' or 'WHILE' command not completed before 'END-EVALUATE'.	Correct the syntax.
005120	'WHEN-OTHER' must be after all 'WHEN's.	Correct the syntax.
005121	No 'WHEN's found inside 'EVALUATE' statement.	Correct the syntax.
005122	'IF', 'EVALUATE' and 'WHILE' statements cannot cross sections or paragraphs.	These commands must be contained within a single section or paragraph. Correct the source code.
005200	Did not find '>' after <....	A leading left angled bracket "<" indicates that you are beginning an decimal value representing a character, which must be ended by a right angled bracket ">". Correct the source line.
005201	Bad character in <...>.	Numbers in angled brackets <> must be between 1 and 255. Correct the source line.

Error Number	Error Message	Suggestion/Interpretation
005202	Bad number in <...>.	Numbers in angled brackets <> must be between 1 and 255. Correct the source line.
005203	<...> string is too long; maximum is '01 characters.	Reduce the length of the string. If this is not possible, use a PRINT-DIRECT command in a BEGIN-REPORT or END-REPORT procedure. '01 = Maximum number of characters supported by this version of SQR
005300	Did not find '=' after qualifier: '01	Correct the syntax. '01 = Qualifier name
005301	Qualifier '01' requires a numeric value.	Correct the syntax. '01 = Qualifier name
005302	Incorrect value for qualifier '01'. Valid values are:	Correct the source line. '01 = Qualifier name
005303	Invalid qualifier '01'. Valid qualifiers are:	Correct the source line. '01 = Qualifier name
005304	Qualifier '01' requires a numeric literal, variable, or column.	Correct the source line. '01 = Qualifier name
005305	Qualifier '01' references a numeric variable that has not been defined.	Correct the source line. '01 = Qualifier name
005306	Qualifier '01' requires a string literal, variable, or column.	Correct the source line. '01 = Qualifier name
005307	List not terminated.	Correct the syntax.
005308	Missing comma in list.	Correct the syntax.
005309	Required argument '01' was not specified.	Correct the source line. '01 = Qualifier name
005310	Qualifier '01' has already been specified.	Correct the source line. '01 = Qualifier name

Error Number	Error Message	Suggestion/Interpretation
005311	Qualifier '01' requires a string literal.	Correct the source line. '01 = Qualifier name
005312	Qualifier '01' requires a list of values: (val [,val]...).	Correct the source line. '01 = Qualifier name
005313	Qualifier '01' requires a integer value.	Correct the source line. '01 = Qualifier name
005314	Invalid character in variable name '01'.	Correct the source line. '01 = Invalid character
005315	Qualifier '01' references a string variable that has not been defined.	Correct the source line. '01 = Qualifier name
005316	Qualifier '01' uses an invalid Unit-Of-Measure suffix. Valid suffixes are: dp pt mm cm in	Correct the source line. '01 = Qualifier name
005400	Second page write attempted while writing current page. Check BEFORE- PAGE, AFTER-PAGE procedures.	Check any procedure invoked by the BEFORE-PAGE or AFTER-PAGE procedures to ensure that the commands do not overflow the page or cause a page eject.
005402	String cannot be placed on page: '01 -- placement specified is out of range. ('02,'03,'04)	Ensure the values are within the page limits. '01 = Text value '02 = Row '03 = Column '04 = Length
005403	Error writing the output file. ('01): '02	'01 = System error code '02 = System error message
005404	Cannot open the Postscript startup file: '01 ('02): '03	'01 = Name of the file '02 = System error code '03 = System error message
005405	SQR trial copy exiting after '01 pages.	'01 = Number of pages.
005406	Exiting after requested number of test pages ('01).	'01 = Number of pages
005408	Program stopped by user request.	Informational message.

Error Number	Error Message	Suggestion/Interpretation
005500	Cannot set parse_only option.	(Sybase) The DB-Library routine dbsetopt() returned an error. This should never happen. Contact technical support.
005501	Cannot reset parse_only option.	(Sybase) The DB-Library routine dbclropt() returned an error. This should never happen. Contact technical support.
005502	Cannot drop SQR generated stored procedure: '01.	(Sybase) See the database server error message that was also output. This should never happen. Contact technical support. '01 = Stored procedure name
005503	Cannot use '01 datatype as bind variable.	(Sybase) Use another database column. '01 = The database datatype.
005504	Unknown datatype for bind variable: '01 Cannot create stored procedure.	(Sybase) Please contact technical support. '01 = Unknown database datatype
005505	SQL too large to create stored procedure.	(Sybase) The size of the SQL text needed to create the stored procedure is too large for SQR to process. Add the -XP option to the BEGIN-SQL or BEGIN-SELECT command.
005506	SQR's EXECUTE command not available for this version of Sybase.	(Sybase) Some early versions of Sybase SQL Server or Microsoft SQL Server do not support Remote Procedure Calls (RPCs). Update your database server.
005507	Could not add param to remote procedure call.	(Sybase) A DB-Library routine returned an unexpected error. See the error message from the database.
005508	The number of EXECUTE...INTO &columns does not match the procedure.	(Sybase) Check the definition for the stored procedure you are referencing.

Error Number	Error Message	Suggestion/Interpretation
005509	Incorrect number of INTO &columns defined in EXECUTE.	(Sybase) Check the definition for the stored procedure you are referencing.
005510	Error converting OUTPUT Sybase type for EXECUTE.	(Sybase) The DB-Library routine dbconvert() failed to convert the data from the stored procedure. Contact technical support.
005511	Number of OUTPUT parameters from EXECUTE is incorrect.	(Sybase) Check the definition for the stored procedure you are referencing.
005512	Missing default database name for USE.	(Sybase) Correct the syntax.
005512	Missing default database name for USE.	(ODBC) Could not connect to the specified datasource.
005513	You may only specify 'USE db' once, before any SQL statements are executed.	(Sybase) Only one USE command is allowed in a report. Place the SETUP section at the beginning of the SQR report.
005515	Undefined variable referenced in -DB flag: '01	(ODBC) Check for a misspelling. '01 = Variable name
005523	Database commit failed.	The database command to perform a commit returned an error. Try running the SQR program again. The error could be related to a network or server problem. If the error persists, contact your system administrator.
005524	Cannot close database cursor.	The database command to close the database cursor returned an error. Try running the SQR program again. The error could be related to a network or server problem. If the error persists, contact your system administrator.
005528	DB2 SQL '01 error '02 in cursor '03:	(DB2) '01 = Routine name '02 = Error code '03 = SQR cursor number

Error Number	Error Message	Suggestion/Interpretation
005528	INFORMIX SQL '01 error '02 (ISAM: '03) in cursor '04: '05	(Informix) '01 = Routine name '02 = Error code '03 = ISAM code '04 = SQR cursor number '05 = Error message from database
005528	ODBC SQL '01 error '02 in cursor '03: '04	(ODBC) '01 = Routine name '02 = Error code '03 = SQR cursor number '04 = Error message from database
005528	ORACLE '01 error '02 in cursor '03: '04	(Oracle) '01 = Routine name '02 = Error code '03 = SQR cursor number '04 = Error message from database
005528	Sybase '01 error in cursor '02: '03	(Sybase) '01 = Routine name '02 = SQR cursor number '03 = Error message from database
005532	System 10 files are missing.	(Sybase) Contact your system administrator.
005533	Not a System 10 SQL Server.	(Sybase) The CT-Library version of SQR can only connect to a System 10 server. Use the DB-Library version of SQR to connect to a pre-System 10 server.
005534	SQL too long for PREPARE /DECLARE; maximum '01 characters.	(DB2) The SQL statement is too large. '01 = Maximum number of characters supported by this version of SQR
005536	Unknown error message number: '01.	(DB2) '01 = Error message number
005537	Empty error message returned from system for error number: '01.	(DB2) '01 = Error message number
005538	Invalid SELECT statement; COMPUTE clauses are not supported.	(Sybase) The select statement contains a COMPUTE clause that is not supported.
005539	Could not connect to datasource specified in -db variable: ''01'.	(ODBC) Could not connect to the specified datasource.

Error Number	Error Message	Suggestion/Interpretation
005540	Not connected to a database, database access is not allowed.	The SQR program is no longer connected to a database. Commands that access the database can no longer be used. This situation can occur if the CONNECT fails and the ON-ERROR option was used.
005543	Specify the Oracle DLL name in the sqr.ini file in [Environment:Oracle] section for ORACLE_DLL entry, such as ORACLE_DLL=orant 71.dll	(Oracle) SQR was unable to load the Oracle DLL. By default, SQR looks first for "ociw32.dll" or the DLL specified by the ORACLE_DLL entry in the [Environment:Oracle] section of the sqr.ini file. If that DLL could not be loaded, then SQR attempts to load 'orant71.dll'.
005600	GETWRD: Word too long; maximum is '01.	Reduce the length of the "word". '01 = Maximum size of a "word" supported by this version of SQR
005700	Cannot call SQR recursively.	SQR cannot be called recursively. This error can only occur if a User Function from either UFUNC.C or UCALL.C calls the sqr() routine. Do not call sqr() from a UFUNC.C or UCALL.C routine.
005701	Too many SQR command line arguments; maximum is '01	To pass more than this number of arguments, use a @file argument file containing one argument per line. '01 = Maximum number supported by this version of SQR.
005702	Log file name specified is too long.	Reduce the length of the log file name.
005703	Error opening the SQR log file: '01' ('02): '03	'01 = Name of the file '02 = System error code '03 = System error message
005704	Missing program name.	The name of the program file was not found on the command line. The program name must be the first parameter on the command line.
005705	Program file name specified is too long.	Reduce the length of the program file name.

Error Number	Error Message	Suggestion/Interpretation
005707	Error opening the -E error file: '01' ('02): '03	'01 = Name of the file '02 = System error code '03 = System error message
005708	Cannot find '01 in SQRDIR, PATH or \SQR.	The specified file cannot be located in any of the directories pointed to by the mentioned environment variables or default directories. Make sure the "file" is present in one of the locations searched. '01 = File name
005709	'01 environment variable is not defined.	As of version 2.5, the environment variable SQRDIR must be defined. '01 = Name of the environment variable
005710	'01 path too long.	The length of the directory path plus the length of the file name to be opened is too long for SQR to handle. Reduce the length of the directory path. '01 = Environment variable name
005711	Bad number in -T test flag.	The number specified must be > zero. Correct the value.
005716	Unknown flag on command line: '01	Correct the syntax. '01 = Unknown command line flag
005720	Error opening tty. ('01): '02	(Tru64, UNIX/Linux) This is an error that should never occur during normal operations. Record the steps leading up to the error and contact your system administrator. '01 = System error code '02 = System error message
005721	Error with 'ioctl()'. ('01): '02	(Tru64, UNIX/Linux) This is an error that should never occur during normal operations. Record the steps leading up to the error and contact your system administrator. '01 = System error code '02 = System error message

Error Number	Error Message	Suggestion/Interpretation
005722	Error reading tty. ('01): '02	(Tru64, UNIX/Linux) This is an error that should never occur during normal operations. Record the steps leading up to the error and contact your system administrator. '01 = System error code '02 = System error message
005723	Error closing tty. ('01): '02	(Tru64, UNIX/Linux) This is an error that should never occur during normal operations. Record the steps leading up to the error and contact your system administrator. '01 = System error code '02 = System error message
005724	Bad number in -B flag.	(Oracle, Sybase) The number specified must be > zero. Correct the value.
005734	No program name given.	The report name must be the first command line argument.
005737	Unknown printer type specified with - PRINTER: switch.	The printer type can be EH, HT, LP, HP, PS, or WP. WP is valid only with PC/Windows.
005738	Database name needs to be included with - DB switch.	(ODBC) Could not connect to the specified datasource.
005738	Database name needs to be included with - DB switch.	(Sybase) Supply the database name.
005739	Too many -F switches; maximum is '01.	Reduce the number of -F switches. '01 = Maximum number allowed
005740	-F and outfile name are required with DDN or DD style SQR {program} name.	(MVS) Correct the JCL stream.
005741	Attempting to use SQR {program} file for outfile.	(MVS) Correct the JCL stream.
005742	Attempt to invoke viewer (using WinExec) failed; error code = '01.	(Windows) '01 = System error code

Error Number	Error Message	Suggestion/Interpretation
005743	Unknown numeric type specified with - DNT: switch.	Correct the command line.
005744	-DNT:Decimal precision ('01) is out of range ('02 - '03).	Correct the command line. '01 = Specified precision '02 = Minimum allowed '03 = Maximum allowed
005745	The specified default numeric type ''01 = '02' is invalid.	Correct the sqr.ini file entry. '01 = Entry '02 = Value
005746	The decimal precision ''01 = '02' is out of range ('03 - '04).	Correct the sqr.ini file entry. '01 = Entry '02 = Value '03 = Minimum allowed '04 = Maximum allowed
005747	The following error(s) occurred while processing the ['01] section from the sqr.ini file.	See the error message(s) that follow. '01 = Name of the section
005750	The -Burst switch is not properly formatted.	The "Burst" command line flag is not properly formatted.
005751	The -Burst switch cannot be used with the -NOLIS switch.	The "Burst" command line flag cannot be specified when the -NOLIS command line flag is also specified.
005752	The -Burst switch requires either the - Printer:HT or - Printer:EH switch to be specified.	The "Burst" command line flag is applicable only when HTML code is produced. You must specify either the -PRINTER:HT or - PRINTER:EH switch.
005753	The -Burst:S and - Burst:T switches can only be used against an SPF file which was generated with SQR v4.1 and above.	The "Burst" command line flag can only be specified when processing a SPF file that was generated by SQR v4.1 and above. Older SPF files do not contain the proper information that permits bursting.
005754	The -Burst switch caused no output to be generated.	The "Burst" command line flag was specified with a set of page ranges that prevented any output to be created. Change the page ranges.
005900	Bad number in - '01	(Windows) Specify a valid number. '01 = Command line option

Error Number	Error Message	Suggestion/Interpretation
005901	Bad filename in -'01	(Windows) Specify a valid file name. '01 = Command line option
005902	Bad directory in -'01	(Windows) Specify a valid directory path. '01 = Command line option
005903	Cannot access the @ parameter file ('01): '02	(Windows) Depends on the system error message. '01 = System error code '02 = System error message
005904	The argument list is too long; maximum is '01.	(Windows) To pass more than this number of arguments, use a @file argument file containing one argument per line. '01 = Maximum number supported by this version of SQR.
005905	Cannot open the report file ('01): '02	(Windows) Depends on the system error message. '01 = System error code '02 = System error message
005906	Invalid filename entered.	(Windows) Re-enter with a valid file name.
006000	Error writing the printer file. ('01): '02	This is an error that can occur during normal operations due to the system environment (for example, file locking, permissions). Record the steps leading up to the error and contact your system administrator. '01 = System error code '02 = System error message
006001	Error reading the printer file. ('01): '02	This is an error that can occur during normal operations due to the system environment (for example, file locking, permissions). Record the steps leading up to the error and contact your system administrator. '01 = System error code '02 = System error message

Error Number	Error Message	Suggestion/Interpretation
006002	Cannot open the printer file: '01 ('02): '03	This is an error that can occur during normal operations due to the system environment (for example, file locking, permissions). Record the steps leading up to the error and contact your system administrator. '01 = Name of the file '02 = System error code '03 = System error message
006003	Unexpected End-Of- File while processing the printer file.	Possibly the file is corrupted. Try to recreate the .spf file. If the error persists, contact technical support.
006004	Encountered unknown SPF code ('01) while reading the printer file.	Possibly the file is corrupted. Try to recreate the .spf file. If the error persists, contact technical support. '01 = Unknown SPF code
006100	Duplicate chart ('01).	Each chart must be given a unique name. '01 = Chart name
006101	Unknown chart ('01).	Chart could not be found. '01 = Chart name
006102	Number of chart data- array columns specified ('01) exceeds the number of array columns ('02).	Correct the source code. '01 = Number of data-array columns '02 = Number of array columns
006103	Number of chart data- array rows specified ('01) exceeds the number of array rows ('02).	Correct the source code. '01 = Number of data-array rows '02 = Number of array rows
006104	Too many pie segments ('01). Max is '02.	Correct the source code. '01 = Number of segments '02 = Maximum allowed segments
006105	Chart module is not initialized.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006106	XY charts may have only numeric columns.	Correct the syntax.

Error Number	Error Message	Suggestion/Interpretation
006107	The 3rd column in the data array must be a character column to specify USE-3RD-DATA-COLUMN.	Correct the syntax.
006108	Invalid chart size or placement.	Correct the source code.
006120	INTERNAL: Bad chart index from stack ('01).	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Chart index
006121	INTERNAL: Unknown SQR BG Interface message ('01).	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Message code
006122	INTERNAL: Unsupported Graftsman chart type ('01).	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Chart type
006123	INTERNAL: Unsupported pie-explode setting ('01).	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Setting value
006124	INTERNAL: Unsupported tick-mark placement ('01).	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Placement value
006125	Graftsman interface message ('01) not supported.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Message code

Error Number	Error Message	Suggestion/Interpretation
006126	Unrecognized return code ('01) from Grafsman command message ('02).	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Return code '02 = Message code
006127	Cannot fit Chart/Image into the current page. Position: ('01, '02) Size: ('03, '04)	Correct the source code. SQR ends the program run. '01 = Row '02 = Column '03 = Width '04 = Depth
006128	Check coordinate values.	Correct the syntax.
006140	Duplicate image ('01).	Images must be given unique names. '01 = Image name
006141	Unknown image ('01).	Image name could not be found. '01 = Image name
006142	Cannot open image file ('01). ('02): '03	'01 = Name of the file '02 = System error code '03 = System error message
006150	INTERNAL: Bad image index from stack ('01).	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Image name
006200	This report has already been defined.	Each report must be given a unique name.
006201	This layout has already been defined.	Each layout must be given a unique name.
006202	This printer has already been defined.	Each printer must be given a unique name.
006203	The values for '01' must be > 0.	Correct the syntax. '01 = Qualifier name
006204	Qualifiers '01' and '02' are mutually exclusive.	Correct the syntax. '01 = Qualifier name '02 = Qualifier name

Error Number	Error Message	Suggestion/Interpretation
006205	Qualifier '01' is not applicable with a 'default' printer.	Correct the syntax. '01 = Qualifier name
006206	The list must contain report names or ALL.	Correct the syntax.
006207	'ALL' must be specified by itself.	Correct the syntax.
006208	No report name was specified.	Correct the syntax.
006209	No layout name was specified.	Correct the syntax.
006210	No printer name was specified.	Correct the syntax.
006211	The name cannot be 'ALL'.	Correct the syntax.
006212	The name can only contain characters [0-9 A-Z _ -].	Correct the syntax.
006213	Report '01' is referenced by multiple '02' printers.	Correct the syntax. '01 = Report name '02 = Printer type
006214	Qualifier '01' is not allowed with a '02' printer.	Correct the syntax. '01 = Qualifier name '02 = Printer type
006215	The value for '01' must be '02 0.	Correct the syntax. '01 = Qualifier name '02 = Relation to zero (<,<=,=,>=,>)
006216	Report '01' does not exist.	Correct the syntax. '01 = Report name
006217	The report name can be a string literal, variable, or column.	Correct the syntax. '01 = Report name
006218	Referenced layouts not defined:	A list of undefined layouts follows this message.
006219	Referenced reports not defined:	A list of undefined reports follows this message.

Error Number	Error Message	Suggestion/Interpretation
006220	Referenced printers not defined:	A list of undefined printers follows this message.
006221	The following SQR commands (listed below) cannot be used when any of the following NEW SQR commands are also used in the same report:	Correct the syntax.
006224	No printer type was specified.	Correct the syntax.
006225	Incorrect value for printer type. Valid values are:	Correct the syntax. A list of valid printer types follows this message.
006226	Attempt to execute the '01 command while processing the '02 procedure.	SQR ends the program run. '01 = SQR command '02 = Procedure name
006227	Incorrect value for 'paper-size'. Specify the actual dimensions or one of the following names:	Correct the syntax. A list of valid predefined paper-size names follows this message.
006228	Referenced TOC (Table Of Contents) not defined:	A list of undefined Table of Contents follows this message.
006229	This TOC (Table Of Contents) has already been defined.	Each Table of Contents must be given a unique name.
006230	The list must contain TOC (Table of Contents) names or ALL.	Correct the syntax.
006231	The TOC (Table Of Contents) entry cannot be positioned given the LEVEL ('01) and INDENTATION ('02) values.	The Table of Contents entry will not fit given the specified level and current indentation values. '01 = Specified LEVEL= value '02 = Current INDENTATION= value
006232	'01 command not allowed while generating the Table of Contents.	The specified command cannot be used while the Table of Contents is being generated. '01 = SQR command

Error Number	Error Message	Suggestion/Interpretation
006233	The TOC (Table of Contents) entry "A" cannot be processed because the existing entry "B" is positioned below it. A: Line = '01, Level = '02, Text = '03' B: Line = '04, Level = '05, Text = '06'	Correct the program logic to eliminate the conflict between the two TOC (Table of Contents) entries. '01 = A: Line number '02 = A: Level value '03 = A: Text value '04 = B: Line number '05 = B: Level value '06 = B: Text value
006300	Unknown parameter ('01).	Correct the syntax. '01 = Parameter name
006301	Value not valid for parameter ('01).	Correct the syntax. '01 = Parameter name
006302	Invalid option ('02) for parameter ('01).	Correct the syntax. '01 = Parameter name '02 = Option
006303	Parameter ('01) is required, but has not been specified.	Correct the syntax. '01 = Parameter name
006304	Parameter ('01) already specified.	Correct the syntax. '01 = Parameter name
006305	Parameter ('01) does not support &columns.	Correct the syntax. '01 = Parameter name
006306	Parameter ('01) requires equal sign.	Correct the syntax. '01 = Parameter name
006307	Parameter ('01) has an unquoted string.	Correct the syntax. '01 = Parameter name
006308	Missing part of specification for parameter ('01).	Correct the syntax. '01 = Parameter name
006309	Parameter ('01) requires literal.	Correct the syntax. '01 = Parameter name
006310	Parameter ('01) requires valid numeric value.	Correct the syntax. '01 = Parameter name

Error Number	Error Message	Suggestion/Interpretation
006311	Parameter ('01) requires integer value.	Correct the syntax. '01 = Parameter name
006312	Parameter ('01) does not support type supplied.	Correct the syntax. '01 = Parameter name
006313	Parameter ('01) requires valid string. Perhaps quote or \$ is missing.	Correct the syntax. '01 = Parameter name
006314	Parameter ('01) does not accept 'NONE' in this context.	Correct the syntax. '01 = Parameter name
006315	Parameter ('01) requires proper object name.	Correct the syntax. '01 = Parameter name
006316	Parameter ('01) requires array name.	Correct the syntax. '01 = Parameter name
006317	Parameter ('01) does not accept 'AUTOSCALE' in this context.	Correct the syntax. '01 = Parameter name
006318	Parameter ('01) has improper value list.	Correct the syntax. '01 = Parameter name
006320	Parameter ('01) does not support relative values.	Correct the syntax. '01 = Parameter name
006350	Conversion [('01) to ('02)] is not supported.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = From type '02 = To type
006352	INTERNAL: Unsupported option/request ('01) in ('02).	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Option/request code '02 = Function name

Error Number	Error Message	Suggestion/Interpretation
006354	INTERNAL: Unknown data type, ('01).	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Data type
006355	INTERNAL: Unable to retrieve parameter value, ('01).	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Parameter name
006356	INTERNAL: Data type ('02) not valid for parameter ('01).	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Parameter name '02 = Data type
006357	INTERNAL: Data location ('02) not valid for data type ('01).	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Data location '02 = Data type
006358	INTERNAL: Cannot decode string ('01) to index.	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = String to decode
006359	INTERNAL: Cannot set bit value ('02) for parameter ('01).	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = Parameter name '02 = Value
006360	INTERNAL: Unknown program state ('01).	This is an internal error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = State

Error Number	Error Message	Suggestion/Interpretation
006400	Unsupported background color.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006401	Unsupported border color.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006402	Border width out of range.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006403	X position out of range.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006404	Y position out of range.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006405	X size out of range.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006406	Y size out of range.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006407	Unsupported font.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006408	Unsupported font style.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.

Error Number	Error Message	Suggestion/Interpretation
006409	Unsupported font color.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006410	Unsupported horizontal text justification value.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006411	Unsupported vertical text justification value.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006412	Unsupported font path.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006413	Unsupported font rotation.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006414	Font size out of range.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006415	Text line id# out of range.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006416	Unsupported chart type.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006417	Unsupported chart sub-type.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.

Error Number	Error Message	Suggestion/Interpretation
006418	Unsupported chart orientation (not H or V).	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006419	Unsupported perspective (not 2D or 3D).	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006420	Unsupported axis (not X or Y).	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006421	Unsupported axis label data type.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006422	Dataset id# out of range.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006423	Unsupported dataset type.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006424	Unsupported dataset color.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006425	Unsupported dataset line style.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006426	Unsupported dataset fill pattern.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.

Error Number	Error Message	Suggestion/Interpretation
006427	Unsupported dataset marker.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006428	Chart type does not support Y-axis datasets.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006429	Pie-chart segment id# is out of range.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006430	Unsupported pie-segment color.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006431	Unsupported pie-segment border color.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006432	Unsupported pie-segment pattern.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006433	Unsupported pie- segment explode setting.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006434	Command only valid for charts of type 'pie'.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006435	Pie-chart radius out of range.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.

Error Number	Error Message	Suggestion/Interpretation
006436	Pie-chart starting angle out of range.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006437	Unsupported pie-chart fill direction. Must be clockwise or counter-clockwise.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006438	Unsupported pie- segment label position.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006439	Unsupported pie- segment quantity display position.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006440	Unsupported pie- segment per-cent display position.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006441	Unsupported legend style.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006442	Unsupported legend horizontal position.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006443	Unsupported legend vertical position.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006444	Text charts do not support legend.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.

Error Number	Error Message	Suggestion/Interpretation
006445	Number of datasets specified does not match data.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006446	Unsupported axis label position.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006447	Unsupported axis type (not LINEAR or LOG).	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006448	Pie and text charts do not support axis control.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006449, 006450	Unsupported axis min scaling.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006451	Unsupported axis max scaling.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006452	Beginning of tickmarks is after end.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006453	Unsupported tickmark type.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006454	Unsupported grid type.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.

Error Number	Error Message	Suggestion/Interpretation
006455	Unsupported grid color.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006456	Grid line width out of range.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006457	Unable to open grafcap file.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006458	Unsupported grafcap device.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006459	Error in grafcap entry specification.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006460	Unable to open chart output destination.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006461	Internal error during ggDraw.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006462	Improper parameters passed to gscale.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006463	The shared library specified in the grafcap file could not be found.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.

Error Number	Error Message	Suggestion/Interpretation
006464	A function called from the shared library specified in the grafcap file could not be found.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006500	The bar code could not be positioned on the page. Row: '01, Column: '02, Height: '03	Correct the source code. '01 = Row '02 = Column '03 = Height
006501	Unknown BCL error ('01) encountered.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support. '01 = BCL error code
006502	Invalid bar code type ('01): Valid values are from 1 to 15.	Correct the source code. '01 = Bar code type.
006503	The length of the bar code text '01' must be between 1 and 30 characters.	Correct the source code. '01 = Bar code text
006504	The length of the caption text '01' must be between 1 and 30 characters.	Correct the source code. '01 = Caption text
006505	Invalid printer type ('01): Valid values are from 0 to 13.	Correct the source code. '01 = Printer type
006506	Invalid offset: Valid values are from 0 to 250.	Correct the source code.
006507	Invalid height ('01): Valid values are from 0.1 to 2.0 inches.	Correct the source code. '01 = Height
006508	Invalid checksum: Valid values are from 0 to 2.	Correct the source code.
006509	Invalid pass: Valid values are from 1 to 6.	Correct the source code.
006510	The bar code text '01' is not valid for the type of bar code ('02) selected.	Correct the source code. '01 = Bar code text '02 = Bar code type

Error Number	Error Message	Suggestion/Interpretation
006511	Internal error: Could not generate the bar code.	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006512	Internal error: Bar code buffer required too large (>32K).	This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006601	Cannot allocate the device context for the default printer.	(Windows) This is an error that can occur due to lack of system resources. Record the steps leading up to the error and contact your system administrator.
006602	Failed to start printing the document.	(Windows) This is an error that can occur due to lack of system resources or a problem with the printer. Record the steps leading up to the error and contact your system administrator.
006603	New-page (start) failed on page '01.	(Windows) This is an error that can occur due to lack of system resources or a problem with the printer. Record the steps leading up to the error and contact your system administrator. '01 = Page number
006604	New-page (end) failed on page '01.	(Windows) This is an error that can occur due to lack of system resources or a problem with the printer. Record the steps leading up to the error and contact your system administrator. '01 = Page number
006605	End document failed.	(Windows) This is an error that can occur due to lack of system resources or a problem with the printer. Record the steps leading up to the error and contact your system administrator.
006606	Error reading font information from the [Fonts] section in sqr.ini. Using the default font.	(Windows) Correct the [Fonts] section in the sqr.ini file.

Error Number	Error Message	Suggestion/Interpretation
006607	Failed to create a brush for shading.	(Windows) This is an error that can occur due to lack of system resources. Record the steps leading up to the error and contact your system administrator.
006608	Failed to select font '01.	(Windows) This is an error that can occur due to lack of system resources. Record the steps leading up to the error and contact your system administrator. '01 = Font name
006609	Failed to modify font '01.	(Windows) This is an error that can occur due to lack of system resources. Record the steps leading up to the error and contact your system administrator. '01 = Font name
006610	Failed to create a pen that was required to draw a box.	(Windows) This is an error that can occur due to lack of system resources. Record the steps leading up to the error and contact your system administrator.
006611	Failed to create a pen that was required to draw a horizontal line.	(Windows) This is an error that can occur due to lack of system resources. Record the steps leading up to the error and contact your system administrator.
006612	Failed to create a pen that was required to draw a vertical line.	(Windows) This is an error that can occur due to lack of system resources. Record the steps leading up to the error and contact your system administrator.
006613	Failed to open the image bitmap file ('01). ('02): '03	(Windows) This is an error that can occur during normal operations due to the system environment (file locking, permissions). Record the steps leading up to the error and contact your system administrator. '01 = Name of the file '02 = System error code '03 = System error message

Error Number	Error Message	Suggestion/Interpretation
006614	The file ('01) does not contain a valid bitmap.	(Windows) Specify a valid bitmap file. '01 = Name of the file
006615	Failed to create the palette for image ('01).	(Windows) This is an error that can occur due to lack of system resources or an invalid bitmap. Record the steps leading up to the error and contact your system administrator. '01 = Name of the file
006616	Failed to load RLE into memory for image ('01).	(Windows) This is an error that can occur due to lack of system resources. Record the steps leading up to the error and contact your system administrator. '01 = Name of the file
006617	Failed to convert DIB to DDB for image ('01).	(Windows) This is an error that can occur due to lack of system resources. Record the steps leading up to the error and contact your system administrator. '01 = Name of the file
006618	Failed to draw the bitmap image ('01).	(Windows) This is an error that can occur due to lack of system resources. Record the steps leading up to the error and contact your system administrator. '01 = Name of the file
006619	Cannot access the default printer's driver.	(Windows) This is an error that can occur due to lack of system resources or a problem with the printer. Record the steps leading up to the error and contact your system administrator.
006620	Cannot select the charting clip area onto the printers DC.	(Windows) This is an error that can occur due to lack of system resources or a problem with the printer. Record the steps leading up to the error and contact your system administrator.

Error Number	Error Message	Suggestion/Interpretation
006621	Cannot select create a metafile required for business graphics.	(Windows) This is an error that can occur due to lack of system resources. Record the steps leading up to the error and contact your system administrator.
006622	Cannot create a region required for business graphics.	(Windows) This is an error that can occur due to lack of system resources. Record the steps leading up to the error and contact your system administrator.
006623	Cannot create a DC required for business graphics.	(Windows) This is an error that can occur due to lack of system resources. Record the steps leading up to the error and contact your system administrator.
006624	Cannot create a bitmap required for business graphics.	(Windows) This is an error that can occur due to lack of system resources. Record the steps leading up to the error and contact your system administrator.
006625	Business graphics failed while setting up the device (ggWinDevice).	(Windows) This is an error that can occur due to lack of system resources. Record the steps leading up to the error and contact your system administrator.
006626	Cannot draw business graphics.	(Windows) This is an error that can occur due to lack of system resources or it can be due to a damaged LIBSTI.INI file. The LIBSTI.INI file resides in the Windows main directory. Make sure that the GPATH= and IPT= entries point to a valid SQR BINW directory. Record the steps leading up to the error and contact your system administrator.
006700	SQRDIR is not defined.	(Windows) The variable SQRDIR must be defined in the sqr.ini file.

Error Number	Error Message	Suggestion/Interpretation
006701	Could not allocate memory while attempting to register the .spf filename extension.	(Windows) This is an error that can occur due to lack of system resources. Record the steps leading up to the error and contact your system administrator.
006702	Could not allocate memory for the page cache.	(Windows) This is an error that should never occur during normal operations. Record the steps leading up to the error and contact technical support.
006704	Cannot open or read file ('01) ('02): '03	(Windows) This is an error that can occur during normal operations due to the system environment (for example, file locking, permissions, and so on.). Record the steps leading up to the error and contact your system administrator. '01 = Name of the file '02 = System error code '03 = System error message
006705	File ('01) is not in SPF packet format.	(Windows) The file was not produced by SQR or it has been corrupted. '01 = Name of the file
006706	Failed to identify the start of the report ('01).	(Windows) The file was not produced by SQR or it has been corrupted. '01 = Name of the file
006707	An invalid seek was made for page '01.	(Windows) This is an internal error which should not occur under normal operations. Please contact technical support. '01 = Page number
006708	Too many errors were encountered while processing the file. Processing has been stopped.	(Windows) This is an error that can occur due to lack of system resources. Record the steps leading up to the error and contact your system administrator.

Error Number	Error Message	Suggestion/Interpretation
006709	Failed to open the image bitmap file ('01). ('02): '03 This message is displayed only once per SPF file.	(Windows) This is an error that can occur during normal operations due to the system environment (for example, file locking, permissions, and so on.). Record the steps leading up to the error and contact your system administrator. '01 = Name of the file '02 = System error code '03 = System error message
006800	'01: Detected internal program error.	This is an internal error that should never occur during normal operation. Record the steps leading up to the error and contact technical support. '01 = Name of the routine
006801	'01: Null Operand Passed as input.	This is an internal error that should never occur during normal operation. Record the steps leading up to the error and contact technical support. '01 = Name of the routine
006802	'01: Decimal Exponent Under/Overflow.	Exponent Under/Overflow: Exponent of decimal number has exceeded the valid boundaries established for the decimal type. Check the documentation for the current upper and lower bounds of a decimal object. '01 = Name of the routine
006803	'01: Decimal to Integer Conversion Under/Overflow.	Integer Under/Overflow: Cannot convert input decimal object into a valid integer number. Decimal object exceeds the established integer boundaries for this machine architecture. Check the magnitude and sign of the decimal object to ensure that it falls within the upper and lower bounds of an integer number. '01 = Name of the routine

Error Number	Error Message	Suggestion/Interpretation
006804	'01: Decimal to Float Conversion Under/Overflow.	Floating Point Under/Overflow: Cannot convert input decimal object into a valid floating point number. Decimal object exceeds the established floating point boundaries for this machine architecture. Check the magnitude and sign of the decimal object to ensure that it falls within the upper and lower bounds of a floating point number. '01 = Name of the routine
006805	'01: Decimal Precision Under/Overflow.	Decimal Precision Under/Overflow: Attempt made to initialize decimal object with an invalid precision. Check the input precision value against the documented upper and lower boundaries for a decimal object. '01 = Name of the routine
006806	'01: String to Decimal Object Conversion Error.	String To Decimal Conversion Error: Length of input string is greater than precision of underlying decimal object. Either increase the precision of the decimal object or reduce the size of the input mantissa to match the decimal object precision. '01 = Name of the routine
006807	'01: Truncation/Rounding Error - Outside Valid Range for Decimal Object.	Truncation/Rounding Error: Input truncation or round value is outside the valid range for this decimal object. Please ensure that the truncation/round value is greater than or equal to zero and less than the precision of the underlying decimal object. '01 = Name of the routine
006808	'01: Decimal Error: Cannot Divide by Zero.	Decimal Math Divide by Zero Error: Attempt made to divide a decimal object by zero. Please check divisor to ensure that it does not equal zero before attempting to divide. '01 = Name of the routine
006900	There is no default printer set up on your system. Use the Control Panel "Printers" applet to define it.	(Windows) SQR Print requires that a default printer be defined. Use the "Printers" applet in the Control Panel to define one.

Error Number	Error Message	Suggestion/Interpretation
007000	The locale '01' is not defined in the sqr.ini file.	Check for a misspelled locale name and/or the sqr.ini file. '01 = Locale name
007001	At least one qualifier must be specified.	Correct the source code.
007002	The value for '01' must be a list of 02 string literals, variables or columns.	Correct the source code. '01 = Qualifier '02 = Number of entities in list
007003	The values for '01' and '02' cannot be the same.	Correct the source code. '01 = Qualifier '02 = Qualifier
007004	The value for '01' ('02) must be a single character which is not in the list: "03".	Correct the source code. '01 = Qualifier '02 = Value '03 = List of invalid characters
007005	The value for '01' ('02) is invalid. Valid values are:	Correct the source code. '01 = Qualifier '02 = Value
007006	The last character of the '01' value ('02) cannot be a digit or the minus sign or the same as either of the separators.	Correct the source code. '01 = Qualifier '02 = Invalid character
007007	The first character of the '01' value ('02) cannot be a digit or the minus sign or the same as either of the separators.	Correct the source code. '01 = Qualifier '02 = Invalid character
00700	The following errors occurred while processing the ('01) locale from the sqr.ini file.	This message precedes error messages encountered while processing the sqr.ini file. '01 = Locale name
007009	The value for '01' cannot be 'DEFAULT' or 'SYSTEM'.	Correct the syntax. '01 = Qualifier
007010	The value for '01' ('02) is not properly formatted: Did not find the '>' for the '<nnn>' construct.	Correct the syntax. '01 = Qualifier '02 = Value

Error Number	Error Message	Suggestion/Interpretation
007011	The value for '01' ('02) is not properly formatted: The value of an '<nnn>' construct must be from 1 to 255.	Correct the syntax. '01 = Qualifier '02 = Value
007012	The default locale ('01) specified in the ['02] section of the sqr.ini file has not been defined.	Correct the syntax. '01 = Locale name '02 = Section name
007013	The value for '01' ('02) must be a list of '03 quoted string literals.	Correct the syntax. '01 = Qualifier '02 = Value '03 = Number of entities in list
007014	The entry ('01 = '02) is not valid.	Correct the sqr.ini entry. '01 = Qualifier from the sqr.ini file '02 = Qualifier's value
007100	The use of an edit mask or the keywords NUMBER, MONEY or DATE is not legal when storing numeric variables.	Correct the source code.
007101	The last keyword is not '01'.	Correct the source code. '01 = Keyword
007102	Incompatible source and destination variable types.	Correct the source code.
007103	The keyword ('01) is not compatible with the variable ('02).	Correct the source code. '01 = Keyword '02 = Variable name
007104	The use of an edit mask or the keyword DATE is not legal if both variables are date variables.	Correct the source code.
007200	The specified precision ('01) is out of range ('02 - '03).	Correct the source code. '01 = Specified precision '02 = Minimum precision '03 = Maximum precision
007201	The precision is specified by a value from '01 to '02 surrounded by parentheses.	Correct the source code. '01 = Minimum precision '02 = Maximum precision

Error Number	Error Message	Suggestion/Interpretation
007202	Variable ('01) is not a decimal variable and cannot have a precision associated with it.	Correct the source code. '01 = Variable name
007203	A string variable name is required here.	Correct the source code.
007204	A numeric variable name is required here.	Correct the source code.
007205	The variable ('01) has already been defined as ''02' and may not be redefined.	Correct the source code. '01 = Variable name '02 = Variable type
007206	The variable type has not been specified.	Correct the source code.
007207	This command is only allowed within local procedures.	Correct the source code.
007208	This command must be before all other commands in the procedure.	Correct the source code.
007209	Only string (\$) and numeric (#) variables may be declared.	Correct the source code.
007210	Invalid variable name specified.	Correct the source code.
007211	You cannot declare a global variable from within a procedure.	Correct the source code.
007400	The specified character is invalid in the current character set.	Correct the program logic.
007401	''01' is not a valid value for the ENCODING environment variable.	The specified encoding scheme is not known by SQR. '01 = ENCODING environment variable setting.
007402	The Double-Byte LET function ''01' is not supported in this version of SQR.	The SQT file contains a reference to a LET function, which is not supported by this version of SQR. '01 = LET function name

Error Number	Error Message	Suggestion/Interpretation
007403	The Double-Byte SQR command '01' is not supported in this version of SQR.	The SQT file contains a reference to an SQR command, which is not supported by this version of SQR. '01 = SQR command name
007404	Double-Byte .sqt files are not supported by this version of SQR.	The runtime file was created by the Double- Byte version of SQR and is incompatible with the current version.
007405	The barcode text '01' cannot contain double- byte characters.	Correct the source code. '01 = Bar code text
007501	Using '01 edit mask from ('02) against ('03)	A date edit mask element was detected which could cause date data to be incorrectly interpreted. This warning message can be turned off by setting the "OutputTwoDigitYearWarningMsg" entry int the [Default- Settings] section of the sqr.ini file to FALSE. '01 = Edit mask element '02 = Edit mask being used '03 = Value being applied to the edit mask
007601	Cannot access the Java file ('01) ('02): '03	SQR cannot access the required file. '01 = Name of the file '02 = System error code '03 = System error message
007602	-EH_Scale: value ('01) is out of range ('02 - '03).	Correct the command line. '01 = Specified scale '02 = Minimum allowed '03 = Maximum allowed
007603	-Printer:EH functionality is not available on this platform.	Enhanced HTML functionality is not available on this platform.
007604	-Printer:PD functionality is not available on this platform.	PDF functionality is not available on this platform.
007701	Did not find end of paragraph: '01 (No 'end-execute' clause found.)	Correct the source code. '01 = BEGIN-command in question.
007702	Invalid entry for keyword, '01='02'	Correct the source code.

Error Number	Error Message	Suggestion/Interpretation
007703	May only specify either PROCEDURE=, or COMMAND=, or GETDATA=, exclusive.	Correct the source code.
007704	Must specify a SCHEMA.	Correct the source code.
007705	Must specify either a PROCEDURE, COMMAND, or GETDATA.	Correct the source code.
007706	CONNECTION '01' not found. No such connection.	Correct the source code.
007707	The returned set of Procedure parameters (INOUT and OUT) (length = '01 items) did not include one or more of the specified items.	Stored procedure error.
007708	Encountered a parameter of type '01'. Valid types are either IN, OUT, or INOUT. If no type is entered, the type defaults to IN.	Stored procedure error.
007709	The datasource failed to provide the expected return status value. Verify the query metadata.	Datasource error.
007710	The datasource failed to provide the expected number of elements in the return status list.	Datasource error.
007711	Failed to login to the requested datasource (Connection='01', username='02'). DETAILS: '03	Logon failed.
007712	The requested rowset ('01) was not available. Verify the query metadata.	Not enough rowsets.
007713	Missing or invalid Registry.properties file. Verify that the CLASSPATH includes SQRDIR, that SQRDIR contains the folder with the Registry.properties file, and that the Registry.properties file is valid.	Incorrect environment setup.

Error Number	Error Message	Suggestion/Interpretation
007714	The datasource ('01') does not support the requested capability ('02'). Check the capabilities list for the datasource, located in the Properties folder.	Invalid query for datasource.
007715	Failed to start the Java Virtual Machine (JVM). Possible causes are: missing or invalid jdk files, incorrect CLASSPATH, or insufficient resources.	Incorrect environment setup.
007716	The current rowset ('01) contained no rows. Check the return status and/or metadata for the requested service to determine the cause.	No data.
007717	The query failed. DETAILS: '01	Query failed.
007718	Failure setting property '01'. DETAILS: '02	Property-set failed.
007719	The value for keyword '01' exceeds the maximum length of '02 characters.	Keyword value too long.
007720	A fatal error occurred while fetching against the current rowset: DETAILS: '01	A failure occurred during row fetch.
007721	Parameter '01 ('02) was passed to the PROCEDURE as data type '03; expected ('04) type '05. Verify the query metadata.	A failure occurred during row fetch.
007722	Invalid query parameter: Reason: '01	Bad procedure parameter.
007723	Too many parameters (= '01) were supplied to the query. Verify the query metadata.	Bad procedure parameter.
007724	Parameter '01 ('02) was passed to the PROCEDURE as type '03; expected type '04. Verify the query metadata.	Bad procedure parameter.

Error Number	Error Message	Suggestion/Interpretation
007725	Parameter '01 ('02', JDO-type '03), specified 'NULL', is a required-parameter. Specify a value or variable name.	Bad procedure parameter.
007726	The list-variable parameter to the query is too long. Maximum number of elements is 30.	List too long.
007727	Unable to retrieve metadata for Procedure='01, Schema='02. DETAILS: '03	Metadata check failed.
007728	Parameter list type mismatch (#'01, SQR type = '02). The datasource expected a parameter of type '03. Verify the query metadata.	Parameter list mismatch.
007729	List size mismatch detected while fetching data of type ROW, '01 items, into SQR list- variable, '02 items. Fetching will proceed to the smaller size.	List size mismatch.
007730	Incorrect syntax for BEGIN-SELECT ... FROM. Options are: FROM ROWSETS=... FROM PARAMETER= \$strvar strlit	Bad begin-select syntax.
007731	Attempted to pass as INOUT or OUT a parameter which was of type ROWSET ('01). Use of such parameters is supported as IN only, after which they may be used in a BEGIN- SELECT construct.	Bad parameter keyword.
007732	Attempt to use a scalar SQR variable ('01') to reference a ROWSET procedure parameter ('02'). Use either the keyword 'NULL', or an SQR LIST variable (%var). Verify the query metadata.	Bad proc parameter.
007733	The list of keywords entered to the PARAMETERS keyword must be terminated with a semicolon.	Bad proc parameter. Correct the source code.

Error Number	Error Message	Suggestion/Interpretation
007734	Datasource '01' not found. The Connection being used by this query specifies a datasource which is not listed in the DDO Registry ('02'). DETAILS: '03.	<obsolete>
007735	Missing one or more DDO {fname}.jar files. Verify the location of the original- installation files, and that they are accessible. Error code: '01. Classpath: '02.	<obsolete>
007736	Unable to open Connection ('01') to datasource ('02'). Possible causes: (a) the Declare-Connection specification is invalid, or (b) the datasource is no longer available. DETAILS: '03.	Bad environment.
007737	Unable to locate one or more entry points in an SQR {fname}.jar file. Verify that the original-installation files have not become corrupted.	Bad environment.
007738	At least one JNI method pointer was lost. This should never occur: record the steps leading up to this failure, and contact Technical Support. DETAILS: Schema='01', Proc='02'.	Bad environment.
007739	Unable to locate query object '01' in the specified schema ('02'). DETAILS: '03.	Bad environment.
007740	Invalid &pseudonym or 'TYPE=' data-type specified for a begin-select column-variable. Valid types are: CHAR, TEXT, DATE, NUMBER.	Correct the syntax.
007741	Illegal attempt to fetch a non-scalar field into a column variable. Correct the query.	Correct the syntax.

Error Number	Error Message	Suggestion/Interpretation
007742	The output parameter specified in 'Begin- Select ... From Parameter = '01' is not available. Available parameters: '02.	Bad command.
007743	The output parameter specified in 'Begin- Select ... From Parameter = '01' is not of type ROWSET. Verify the query metadata.	Bad command.
007744	Illegal attempt to assign an SQR variable ('01') of type '02' the value from a DDO object ('03') of type '04'. Verify the query metadata.	<obsolete>
007745	Illegal attempt to assign an SQR column variable ('01') of type '02' the value from a DDO object of type '03'. Verify the query metadata.	<obsolete>
007746	Failed to locate the requested Rowset ('01) while processing the query. The last available Rowset number is '02. Verify the query metadata.	Not enough RowSets.
007747	The query raised a DDO exception. DETAILS: '01.	<obsolete>
007748	A BEGIN-SELECT paragraph was coded, but the query returned no Rows.	No data warning.
007749	Invalid syntax for PARAMETERS= (...) statement. Use: PARAMETERS=(%v \$v #v &v NULL SKIP numlit datelit textlit [IN INOUT], ...) All parameters must be specified. Optional parameters which are to be ignored may be specified by the keyword 'NULL' or 'SKIP'. Correct the syntax.	Incorrect syntax.
007750	FATAL: Failure creating Java object.	General failure.

Error Number	Error Message	Suggestion/Interpretation
007751	Attempt to create a List variable of size greater than the maximum size of '01 items.	General failure.
007752	Parameter-list item ''01' is not a member of the parameter list for this Query. Verify the query metadata.	No such input/inout parameter.
007753	Attempt to access List- row ('01) beyond the List size ('02 rows).	Bad list assignment/setup.
007754	Attempt to assign/modify a List row is not compatible with the List definition.	Bad list assignment/setup.
007755	Attempt to assign a row to a non-existent List variable. Define the List first, using the syntax: let %lname[size] = list(NUMBER DATE TEXT #var \$var [, ...])	Bad list assignment/setup.
007756	Incorrect syntax for List-variable reference. Use: let [\$ #]var = %listname[nlit #var].colname	Bad list assignment/setup.
007757	Alter-connection statement missing 'DSN=... '.	Improper alter-conn.
007758	List-definition size specifier must be literal.	Improper alter-conn.
007759	Attempt to access a non-existent List- column ('01').	No such list column name.
007760	Must specify one of the keywords, FROM- ROWSETS or FROM_PARAMETER .	Incorrect syntax for Load-lookup.
007761	Incorrect syntax to Load-lookup 'PARAMETERS=' keyword. Use: PARAMETERS=(slit nlit \$var #var %var &var, ...) No line wrapping is allowed for this usage.	Incorrect syntax for Load-lookup.

Error Number	Error Message	Suggestion/Interpretation
007762	Too many parameters ('02) entered to Load- Lookup command. Max parameters is '01.	Incorrect syntax for Load-lookup.
007763	Problem executing the cursor for LOAD- LOOKUP table ''01'. DETAILS: '02.	The database server returned an error while trying to execute the SQL statement needed to process the LOAD-LOOKUP command. '01 = Load lookup table name
007764	Bad return fetching row from database in LOAD-LOOKUP table ''01'. DETAILS: '02	The database server returned an error while fetching the data. '01 = Load lookup table name
007765	DC, DI sort options not supported with this SQR version. To sort, use SORT=SC or SORT=SI.	Database sort not supported for Load- Lookup with DDO. <obsolete>
007766	Must specify a query keyword; PROCEDURE=, COMMAND= or GETDATA=.	Incorrect syntax for Load-lookup. Specify a keyword representing the query.
007767	Unknown column variable type.	Unknown data type returned by the server.
007768	The property '01' was not found in the property sheet for the specified datasource ('02). Available property names are: '03.The datasource property sheet does not include the named property.	Verify the metadata and correct the syntax.
007769	The specified CONNECTION ('01') references a datasource whose property sheet does not show support for the Get-Data query method.The datasource property sheet does not show support for Get-Data.	Verify the metadata and property sheet and correct the syntax.
007770	Attempt to create a Selector (or MDSelector) object failed. This event should not occur. Contact your system administrator.	Failed to create the requested object. Contact your system administrator.

Error Number	Error Message	Suggestion/Interpretation
009000	Error reading the font information from the ['01] section in sqr.ini. Font name '02 is too long. The maximum length allowed for a font name is '03.	Try using a shorter font name in sqr.ini. '01 = Printing device specific font configuration section '02 = Font name '03 = Internal limit for font name
009001	Error reading the font information from the ['01] section in sqr.ini. Font file path '02 is too long. The maximum length allowed for a font file path is '03.	Try using a shorter font file path in sqr.ini. Relocate font file if necessary. '01 = Font configuration section name '02 = Font file path '03 = Internal limit for file path
009002	Font '01 is not valid for '02 output. Please correct the font configuration in the ['02 Fonts] section of the sqr.ini file.	Try using a valid font. Refer to the documentation for supported fonts. If you intend to use disk based fonts like TrueType, also check that the font type specific configuration section (like [TrueType Fonts]) is correctly configured. '01 = Font name '02 = Selected output type
009003	File name for '01 font '02 is not specified correctly. Please correct the configuration in the ['01 Fonts] section of sqr.ini file.	The font file path is not specified correctly. Please correct the sqr.ini file. '01 = Font type '02 = Font name
009004	'01 font file '02 cannot be opened. Please check if the file exists, or correct the font configuration in the ['01 Fonts] section of the sqr.ini file.	Either the font file does not exist in the location specified in sqr.ini file, or the path specified in sqr.ini file is not correct. Please correct the error and try again. '01 = Font type '02 = Font file path

Error Number	Error Message	Suggestion/Interpretation
009005	The directory ID specified for '01 in the [TrueType Fonts] section of the sqr.ini file exceeds the actual number of fonts included in the TrueType collection font file. '02 includes '03 fonts. Please specify a valid directory ID.	Correct the configuration in sqr.ini so that the directory ID is set correctly for the font. Note that the directory ID starts from 0. '01 = Font name '02 = Font file path '03 = Actual number of fonts included in TrueType collection
009006	Font '01 is not a supported type of TrueType/OpenType font.	Currently, SQR does not support CFF based OpenType font. Please remove the font from the configuration and try again.
009007	Font '01 is not a supported type of TrueType/OpenType font. The '02' table is missing from the font file.	This TrueType/OpenType font does not have the table SQR needs for processing. Please remove the font from the configuration and try again. '01 = Font name '02 = Table name
009008	Font '01 is not a supported type of TrueType/OpenType font. This font does not allow embedding in a document.	SQR requires TrueType/OpenType font with embedding feature allowed to include the subset of the font in the print output. This TrueType/OpenType font does not allow embedding. Please remove the font from the configuration and try again.

Error Number	Error Message	Suggestion/Interpretation
009009	Font '01 is not a supported type of TrueType/OpenType font. This font does not have a supported type of character to glyph mapping (CMAP) table.	SQR requires a TrueType/OpenType font with CMAP table with Platform ID 3 (Microsoft), Encoding ID 0 (Symbol), 4 (UCS-2), or 10 (UCS-4) and table format 4 or 12. Other CMAP table types and encodings are currently not supported. Please remove the font from the configuration and try again. '01 = Font name
009010	Error in the ['01:Exclusion Ranges] section in theINI file. Start character code must be greater than the end character code.	In the exclusion range section, the start character code must be smaller than the end character code. Check the section in INI file and correct error. You can specify the range in a decimal or hexadecimal number. If you use a hexadecimal number, you must prefix the number with '0x'. Otherwise, the number is recognized as a decimal.

APPENDIX A

Using SQR Sample Programs

This appendix discusses SQR samples.

Understanding SQR Samples

SQR Samples is a library of SQR programs that you can use to adapt and experiment with programs. These programs are stored in the <PS_HOME>\bin\sqr\<database_platform>\SAMPLE (SAMPLEW for Windows) directory. You can modify these programs to create configured SQRs.

SQR Sample Programs

The following table lists the sample SQR programs and provides a brief description of each. Each program comprises a report specification and a sample of the output.

Name	Description
_____.DAT	Data files that are used by the loadall.sqr programs.
_____.MEM	SQR startup files to run small, medium, and large SQR programs.
APPEND.SQR	Demonstrates the APPEND and FIXED-NOLF (no line feed) commands.
APTDIARY.SQR	Demonstrates columns and text wrapping.
AREA100.SQR	Demonstrates a 100% area chart.
BAR100.SQR	Demonstrates a 100% bar chart.
BARCODE.SQR	Demonstrates printing a bar code.
CALENDAR.SQR	Demonstrates nondatabase formatting.

Name	Description
COMP_FOR.SQR	Prints a graph of the forecasted and actual sales for a given employee.
COMP_F_G.SQR	Prints a graph of the forecasted and actual sales for a month or quarter.
COMP_PLN.SQR	Prints a graph of the planned and actual sales for a given employee.
COMP_P_G.SQR	Prints a graph of the planned and actual sales for month or quarter.
COVLET02.SQR	Uses SQR to input data from a user, enter the data in the database, and write a form letter by using a DOCUMENT paragraph.
CUST.SQR	Prints a list of all of the customers, bursted by page.
CUSTLBLS.SQR	Demonstrates printing mailing labels within columns.
CUSTOMER.SQR	Demonstrates multiple detail lines and the NEXT-LISTING command.
CUSTOMR2.SQR	Demonstrates the use of the ON-BREAK argument to the PRINT command.
CUSTOMR3.SQR	Demonstrates the use of the INPUT command to change the report output.
CUSTOMR4.SQR	Demonstrates the use of arrays.
CUSTOMR5.SQR	Demonstrates dynamic queries to enable the user to qualify a report as it runs.
CUST_SUM.SQR	Prints a group of information about each customer in the customer table.
CUSTTAPE.SQR	Demonstrates the flat file output for magnetic tape or other postprocessing.
DATAA.DAT	Needed for append.sqr.

Name	Description
DATAB.DAT	Needed for append.sqr.
DROPALL.SQR	Drops all of the SQR sample tables that are created by the LOADALL program.
DROPPROC.SQR	(Sybase) Deletes leftover, temporary, stored procedures belonging to the user.
DYNAMCOL.SQR	Demonstrates the use of dynamic columns, dynamic tables, and variables that are passed to the ON-ERROR procedure.
EMP.SQR	Prints a list of all of the employees, bursted by page.
EMP_COMM.SQR	Calculates each employee's commission, based on sales.
EMP_M_Q.SQR	Lists all employee quotas for a given month or quarter.
ENVELOPE.SQR	Demonstrates the use of printing envelope with proper bar codes.
EXPORT.SQR	Creates two SQR reports: one to export a database table and one to import that table. Data from the table is stored in an external operating system file in compressed format, with trailing blanks removed.
FLATFILE.SQR	Creates an SQR report to extract a database table and place it in a flat file.
FLOATBAR.SQR	Demonstrates a floating bar chart.
FOR_CUST.SQR	Creates a sales forecast for a given customer, grouped by month or quarter.
FOR_EMP.SQR	Creates a sales forecast for a given employee, grouped by month or quarter.
FOR_PROD.SQR	Creates a sales forecast for a given product, grouped by month or quarter.
FOR_REG.SQR	Creates a sales forecast for a given region, grouped by month or quarter.

Name	Description
FOR_SUM.SQR	Creates a table of projected product sales with links to more information.
FORMLETR.SQR	Demonstrates form letters by using a document paragraph.
HILO.SQR	Demonstrates a high-low-close chart.
HISTGRAM.SQR	Demonstrates a histogram chart.
INQUIRY.SQR	Creates an SQR program to display rows at your terminal that are selected from a database table that you specify. The resulting SQR program prompts you to qualify the rows to be selected, display those rows, then repeat.
INVOICE.SQR	Demonstrates creating multiple reports, printing invoices, and printing envelopes.
LOADALL.SQR	Creates and loads the sample tables that are used in the preceding SQR programs.
MAKEDATA.SQR	Creates a data file with a fixed length and NOLF attributes.
MAKEREPT.SQR	Helps you create SQR reports more quickly.
MULTIPLE.SQR	Demonstrates creating multiple reports.
NESTREPT.SQR	Demonstrates nesting procedures.
ORDERS.SQR	Lists all of the orders and the order lines that are associated with them.
ORD_MONG.SQR	Lists all orders for a given month and groups them by employee number.
ORD_M_Q.SQR	Lists all orders for a given month or quarter.
ORD_PROD.SQR	Lists all orders for a given product.
ORD_REGG.SQR	Creates a report of all orders from a given region, grouped by month or quarter.

Name	Description
ORD_SUM.SQR	Displays an orders summary, grouped by month.
ORD_S_Q.SQR	Prints a graph of the percent of orders for each region (in a year) and four graphs of the percent of orders for each region (one for each quarter of that year).
OVERBAR.SQR	Demonstrates an overlapped bar chart.
PHONELST.SQR	Demonstrates printing within columns, page headings, and page footings.
PLN_EMP.SQR	Creates a sales plan for a given employee, grouped by month or quarter.
PLN_GEN.SQR	Creates a sales plan, grouped by month or quarter.
PLN_REG.SQR	Creates a sales plan for given region, grouped by month or quarter.
PRODUCT.SQR	Lists products and their prices and graphs orders of products.
SALELEAD.SQR	Demonstrates DOCUMENT paragraphs.
SALES.SQR	Demonstrates charting from stored data and printing several charts on one page.
SCATTER.SQR	Demonstrates a scatter chart.
SHOWPROC.SQR	(Sybase) Shows any leftover, temporary, stored procedures belonging to the user.
STCKAREA.SQR	Demonstrates a stacked area chart.
SQR3DBAR.SQR	Demonstrates a 3D bar chart.
SQRLASER.SQR	Demonstrates graphic and file input/output commands.
SQRLINE.SQR	Demonstrates a line chart.
SQRLOGO.SQR	Demonstrates printing images.

Name	Description
SQRPIE.SQR	Demonstrates a pie chart.
TABREP.SQR	Creates a tabular SQR report for a table that you select.
UPDATE.SQR	Generates an SQR program that enables you to query and update database tables. The created program uses the SHOW command to simulate a menu interface.

APPENDIX B

ISO Country and Currency Codes

PeopleBooks use International Organization for Standardization (ISO) country and currency codes to identify country-specific information and monetary amounts.

This appendix discusses:

- ISO country codes.
- ISO currency codes.

See Also

“About This PeopleBook,” Typographical Conventions and Visual Cues

ISO Country Codes

This table lists the ISO country codes that may appear as country identifiers in PeopleBooks:

ISO Country Code	Country Name
ABW	Aruba
AFG	Afghanistan
AGO	Angola
AIA	Anguilla
ALB	Albania
AND	Andorra
ANT	Netherlands Antilles
ARE	United Arab Emirates
ARG	Argentina
ARM	Armenia
ASM	American Samoa
ATA	Antarctica

ISO Country Code	Country Name
ATF	French Southern Territories
ATG	Antigua and Barbuda
AUS	Australia
AUT	Austria
AZE	Azerbaijan
BDI	Burundi
BEL	Belgium
BEN	Benin
BFA	Burkina Faso
BGD	Bangladesh
BGR	Bulgaria
BHR	Bahrain
BHS	Bahamas
BIH	Bosnia and Herzegovina
BLR	Belarus
BLZ	Belize
BMU	Bermuda
BOL	Bolivia
BRA	Brazil
BRB	Barbados
BRN	Brunei Darussalam
BTN	Bhutan
BVT	Bouvet Island
BWA	Botswana
CAF	Central African Republic
CAN	Canada
CCK	Cocos (Keeling) Islands

ISO Country Code	Country Name
CHE	Switzerland
CHL	Chile
CHN	China
CIV	Cote D'Ivoire
CMR	Cameroon
COD	Congo, The Democratic Republic
COG	Congo
COK	Cook Islands
COL	Colombia
COM	Comoros
CPV	Cape Verde
CRI	Costa Rica
CUB	Cuba
CXR	Christmas Island
CYM	Cayman Islands
CYP	Cyprus
CZE	Czech Republic
DEU	Germany
DJI	Djibouti
DMA	Dominica
DNK	Denmark
DOM	Dominican Republic
DZA	Algeria
ECU	Ecuador
EGY	Egypt
ERI	Eritrea
ESH	Western Sahara

ISO Country Code	Country Name
ESP	Spain
EST	Estonia
ETH	Ethiopia
FIN	Finland
FJI	Fiji
FLK	Falkland Islands (Malvinas)
FRA	France
FRO	Faroe Islands
FSM	Micronesia, Federated States
GAB	Gabon
GBR	United Kingdom
GEO	Georgia
GHA	Ghana
GIB	Gibraltar
GIN	Guinea
GLP	Guadeloupe
GMB	Gambia
GNB	Guinea-Bissau
GNQ	Equatorial Guinea
GRC	Greece
GRD	Grenada
GRL	Greenland
GTM	Guatemala
GUF	French Guiana
GUM	Guam
GUY	Guyana
GXA	GXA - GP Core Country

ISO Country Code	Country Name
GXB	GXB - GP Core Country
GXC	GXC - GP Core Country
GXD	GXD - GP Core Country
HKG	Hong Kong
HMD	Heard and McDonald Islands
HND	Honduras
HRV	Croatia
HTI	Haiti
HUN	Hungary
IDN	Indonesia
IND	India
IOT	British Indian Ocean Territory
IRL	Ireland
IRN	Iran (Islamic Republic Of)
IRQ	Iraq
ISL	Iceland
ISR	Israel
ITA	Italy
JAM	Jamaica
JOR	Jordan
JPN	Japan
KAZ	Kazakstan
KEN	Kenya
KGZ	Kyrgyzstan
KHM	Cambodia
KIR	Kiribati
KNA	Saint Kitts and Nevis

ISO Country Code	Country Name
KOR	Korea, Republic of
KWT	Kuwait
LAO	Lao People's Democratic Rep
LBN	Lebanon
LBR	Liberia
LBY	Libyan Arab Jamahiriya
LCA	Saint Lucia
LIE	Liechtenstein
LKA	Sri Lanka
LSO	Lesotho
LTU	Lithuania
LUX	Luxembourg
LVA	Latvia
MAC	Macao
MAR	Morocco
MCO	Monaco
MDA	Moldova, Republic of
MDG	Madagascar
MDV	Maldives
MEX	Mexico
MHL	Marshall Islands
MKD	Fmr Yugoslav Rep of Macedonia
MLI	Mali
MLT	Malta
MMR	Myanmar
MNG	Mongolia
MNP	Northern Mariana Islands

ISO Country Code	Country Name
MOZ	Mozambique
MRT	Mauritania
MSR	Montserrat
MTQ	Martinique
MUS	Mauritius
MWI	Malawi
MYS	Malaysia
MYT	Mayotte
NAM	Namibia
NCL	New Caledonia
NER	Niger
NFK	Norfolk Island
NGA	Nigeria
NIC	Nicaragua
NIU	Niue
NLD	Netherlands
NOR	Norway
NPL	Nepal
NRU	Nauru
NZL	New Zealand
OMN	Oman
PAK	Pakistan
PAN	Panama
PCN	Pitcairn
PER	Peru
PHL	Philippines
PLW	Palau

ISO Country Code	Country Name
PNG	Papua New Guinea
POL	Poland
PRI	Puerto Rico
PRK	Korea, Democratic People's Rep
PRT	Portugal
PRY	Paraguay
PSE	Palestinian Territory, Occupie
PYF	French Polynesia
QAT	Qatar
REU	Reunion
ROU	Romania
RUS	Russian Federation
RWA	Rwanda
SAU	Saudi Arabia
SDN	Sudan
SEN	Senegal
SGP	Singapore
SGS	Sth Georgia & Sth Sandwich Is
SHN	Saint Helena
SJM	Svalbard and Jan Mayen
SLB	Solomon Islands
SLE	Sierra Leone
SLV	El Salvador
SMR	San Marino
SOM	Somalia
SPM	Saint Pierre and Miquelon
STP	Sao Tome and Principe

ISO Country Code	Country Name
SUR	Suriname
SVK	Slovakia
SVN	Slovenia
SWE	Sweden
SWZ	Swaziland
SYC	Seychelles
SYR	Syrian Arab Republic
TCA	Turks and Caicos Islands
TCD	Chad
TGO	Togo
THA	Thailand
TJK	Tajikistan
TKL	Tokelau
TKM	Turkmenistan
TLS	East Timor
TON	Tonga
TTO	Trinidad and Tobago
TUN	Tunisia
TUR	Turkey
TUV	Tuvalu
TWN	Taiwan, Province of China
TZA	Tanzania, United Republic of
UGA	Uganda
UKR	Ukraine
UMI	US Minor Outlying Islands
URY	Uruguay
USA	United States

ISO Country Code	Country Name
UZB	Uzbekistan
VAT	Holy See (Vatican City State)
VCT	St Vincent and the Grenadines
VEN	Venezuela
VGB	Virgin Islands (British)
VIR	Virgin Islands (U.S.)
VNM	Viet Nam
VUT	Vanuatu
WLF	Wallis and Futuna Islands
WSM	Samoa
YEM	Yemen
YUG	Yugoslavia
ZAF	South Africa
ZMB	Zambia
ZWE	Zimbabwe

ISO Currency Codes

This table lists the ISO country codes that may appear as currency identifiers in PeopleBooks:

ISO Currency Code	Description
ADP	Andorran Peseta
AED	United Arab Emirates Dirham
AFA	Afghani
AFN	Afghani
ALK	Old Lek
ALL	Lek
AMD	Armenian Dram

ISO Currency Code	Description
ANG	Netherlands Antilles Guilder
AOA	Kwanza
AOK	Kwanza
AON	New Kwanza
AOR	Kwanza Reajustado
ARA	Austral
ARP	Peso Argentino
ARS	Argentine Peso
ARY	Peso
ATS	Schilling
AUD	Australian Dollar
AWG	Aruban Guilder
AZM	Azerbaijani Manat
BAD	Dinar
BAM	Convertible Marks
BBD	Barbados Dollar
BDT	Taka
BEC	Convertible Franc
BEF	Belgian Franc
BEL	Financial Belgian Franc
BGJ	Lev A/52
BGK	Lev A/62
BGL	Lev
BGN	Bulgarian LEV
BHD	Bahraini Dinar
BIF	Burundi Franc
BMD	Bermudian Dollar

ISO Currency Code	Description
BND	Brunei Dollar
BOB	Boliviano
BOP	Peso
BOV	Mvdol
BRB	Cruzeiro
BRC	Cruzado
BRE	Cruzeiro
BRL	Brazilian Real
BRN	New Cruzado
BRR	Brazilian Real Dollar
BSD	Bahamian Dollar
BTN	Ngultrum
BUK	N/A
BWP	Pula
BYB	Belarussian Ruble
BYR	Belarussian Ruble
BZD	Belize Dollar
CAD	Canadian Dollar
CDF	Franc Congolais
CHF	Swiss Franc
CLF	Unidades de fomento
CLP	Chilean Peso
CNX	Peoples Bank Dollar
CNY	Yuan Renminbi
COP	Colombian Peso
CRC	Costa Rican Colon
CSD	Serbia Dinar

ISO Currency Code	Description
CSJ	Krona A/53
CSK	Koruna
CUP	Cuban Peso
CVE	Cape Verde Escudo
CYP	Cyprus Pound
CZK	Czech Koruna
DEM	Deutsche Mark
DJF	Djibouti Franc
DKK	Danish Krone
DOP	Dominican Peso
DZD	Algerian Dinar
ECS	Sucre
ECV	Unidad de Valor
EEK	Kroon
EGP	Egyptian Pound
EQE	Ekwele
ERN	Nakfa
ESA	Spanish Peseta
ESB	Convertible Peseta
ESP	Spanish Peseta
ETB	Ethiopian Birr
EUR	euro
FIM	Markka
FJD	Fiji Dollar
FKP	Falklands Isl. Pound
FRF	French Franc
GBP	Pound Sterling

ISO Currency Code	Description
GEK	Georgian Coupon
GEL	Lari
GHC	Cedi
GIP	Gibraltar Pound
GMD	Dalasi
GNE	Syli
GNF	Guinea Franc
GNS	Syli
GQE	Ekwele
GRD	Drachma
GTQ	Quetzal
GWE	Guinea Escudo
GWP	Guinea-Bissau Peso
GYD	Guyana Dollar
HKD	Hong Kong Dollar
HNL	Lempira
HRD	Dinar
HRK	Kuna
HTG	Gourde
HUF	Forint
IDR	Rupiah
IEP	Irish Pound
ILP	Pound
ILR	Old Shekel
ILS	New Israeli Sheqel
INR	Indian Rupee
IQD	Iraqi Dinar

ISO Currency Code	Description
IRR	Iranian Rial
ISJ	Old Krona
ISK	Iceland Krona
ITL	Italian Lira
JMD	Jamaican Dollar
JOD	Jordanian Dinar
JPY	Yen
KES	Kenyan Shilling
KGS	Som
KHR	Riel
KMF	Comoro Franc
KPW	North Korean Won
KRW	Won
KWD	Kuwaiti Dinar
KYD	Cayman Islands dollar
KZT	Tenge
LAJ	Kip Pot Pol
LAK	Kip
LBP	Lebanese Pound
LKR	Sri Lanka Rupee
LRD	Liberian Dollar
LSL	Loti
LSM	Maloti
LTL	Lithuanian Litas
LTT	Talonas
LUC	Convertib Franc
LUF	Luxembourg Franc

ISO Currency Code	Description
LUL	Financial Franc
LVL	Latvian Lats
LVR	Latvian Ruble
LYD	Libyan Dinar
MAD	Moroccan Dirham
MAF	Mali Franc
MDL	Moldovan Leu
MGF	Malagasy Franc
MKD	Denar
MLF	Mali Franc
MMK	Kyat
MNT	Tugrik
MOP	Pataca
MRO	Ouguiya
MTL	Maltese Lira
MTP	Maltese Pound
MUR	Mauritius Rupee
MVQ	Maldiva Rupee
MVR	Rufiyaa
MWK	Malawian Kwacha
MXN	Mexican Peso
MXP	Mexican Peso
MXV	Mexican UDI
MYR	Malaysian Ringgit
MZE	Mozambique Escudo
MZM	Metical
NAD	Namibia Dollar

ISO Currency Code	Description
NGN	Naira
NIC	Cordoba
NIO	Cordoba Oro
NLG	Netherlands Guilder
NOK	Norwegian Krone
NPR	Nepalese Rupee
NZD	New Zealand Dollar
OMR	Rial Omani
PAB	Balboa
PEI	Inti
PEN	Nuevo Sol
PES	Sol
PGK	Kina
PHP	Philippine Peso
PKR	Pakistan Rupee
PLN	Zloty
PLZ	Zloty
PTE	Portuguese Escudo
PYG	Guarani
QAR	Qatari Rial
ROK	Leu A/52
ROL	Leu
RUB	Russian Ruble
RUR	Russian Federation Rouble
RWF	Rwanda Franc
SAR	Saudi Riyal
SBD	Solomon Islands

ISO Currency Code	Description
SCR	Seychelles Rupee
SDD	Sudanese Dinar
SDP	Sudanese Pound
SEK	Swedish Krona
SGD	Singapore Dollar
SHP	St Helena Pound
SIT	Tolar
SKK	Slovak Koruna
SLL	Leone
SOS	Somali Shilling
SRG	Surinam Guilder
STD	Dobra
SUR	Rouble
SVC	El Salvador Colon
SYP	Syrian Pound
SZL	Lilangeni
THB	Baht
TJR	Tajik Ruble
TJS	Somoni
TMM	Manat
TND	Tunisian Dinar
TOP	Pa'anga
TPE	Timor Escudo
TRL	Turkish Lira
TTD	Trinidad Dollar
TWD	New Taiwan Dollar
TZS	Tanzanian Shilling

ISO Currency Code	Description
UAH	Hryvnia
UAK	Karbovanet
UGS	Uganda Shilling
UGW	Old Shilling
UGX	Uganda Shilling
USD	US Dollar
USN	US Dollar (Next day)
USS	US Dollar (Same day)
UYN	Old Uruguay Peso
UYP	Uruguayan Peso
UYU	Peso Uruguayo
UZS	Uzbekistan Sum
VEB	Bolivar
VNC	Old Dong
VND	Dong
VUV	Vatu
WST	Tala
XAF	CFA Franc BEAC
XAG	Silver
XAU	GOLD
XBA	European Composite Unit
XBB	European Monetary Unit
XBC	European Unit of Account 9
XBD	European Unit of Account 17
XCD	East Caribbean Dollar
XDR	SDR
XEU	EU Currency (E.C.U)

ISO Currency Code	Description
XFO	Gold-Franc
XFU	UIC-Franc
XOF	CFA Franc BCEAO
XPD	Palladium
XPF	CFP Franc
XPT	Platinum
XTS	For Testing Purposes
XXX	Non Currency Transaction
YDD	Yemeni Din
YER	Yemeni Rial
YUD	New Yugoslavian Dinar
YUM	New Dinar
YUN	Yugoslavian Dinar
ZAL	Financial Rand
ZAR	Rand
ZMK	Zambian Kwacha
ZRN	New Zaire
ZRZ	Zaire
ZWC	Rhodesian Dollar
ZWD	Zimbabwe Dollar

Glossary of PeopleSoft Terms

absence entitlement	This element defines rules for granting paid time off for valid absences, such as sick time, vacation, and maternity leave. An absence entitlement element defines the entitlement amount, frequency, and entitlement period.
absence take	This element defines the conditions that must be met before a payee is entitled to take paid time off.
accounting class	In PeopleSoft Enterprise Performance Management, the accounting class defines how a resource is treated for generally accepted accounting practices. The Inventory class indicates whether a resource becomes part of a balance sheet account, such as inventory or fixed assets, while the Non-inventory class indicates that the resource is treated as an expense of the period during which it occurs.
accounting date	The accounting date indicates when a transaction is recognized, as opposed to the date the transaction actually occurred. The accounting date and transaction date can be the same. The accounting date determines the period in the general ledger to which the transaction is to be posted. You can only select an accounting date that falls within an open period in the ledger to which you are posting. The accounting date for an item is normally the invoice date.
accounting split	The accounting split method indicates how expenses are allocated or divided among one or more sets of accounting ChartFields.
accumulator	You use an accumulator to store cumulative values of defined items as they are processed. You can accumulate a single value over time or multiple values over time. For example, an accumulator could consist of all voluntary deductions, or all company deductions, enabling you to accumulate amounts. It allows total flexibility for time periods and values accumulated.
action reason	The reason an employee's job or employment information is updated. The action reason is entered in two parts: a personnel action, such as a promotion, termination, or change from one pay group to another—and a reason for that action. Action reasons are used by PeopleSoft Human Resources, PeopleSoft Benefits Administration, PeopleSoft Stock Administration, and the COBRA Administration feature of the Base Benefits business process.
action template	In PeopleSoft Receivables, outlines a set of escalating actions that the system or user performs based on the period of time that a customer or item has been in an action plan for a specific condition.
activity	In PeopleSoft Enterprise Learning Management, an instance of a catalog item (sometimes called a class) that is available for enrollment. The activity defines such things as the costs that are associated with the offering, enrollment limits and deadlines, and waitlisting capacities. In PeopleSoft Enterprise Performance Management, the work of an organization and the aggregation of actions that are used for activity-based costing. In PeopleSoft Project Costing, the unit of work that provides a further breakdown of projects—usually into specific tasks. In PeopleSoft Workflow, a specific transaction that you might need to perform in a business process. Because it consists of the steps that are used to perform a transaction, it is also known as a step map.

agreement	In PeopleSoft eSettlements, provides a way to group and specify processing options, such as payment terms, pay from a bank, and notifications by a buyer and supplier location combination.
allocation rule	In PeopleSoft Enterprise Incentive Management, an expression within compensation plans that enables the system to assign transactions to nodes and participants. During transaction allocation, the allocation engine traverses the compensation structure from the current node to the root node, checking each node for plans that contain allocation rules.
alternate account	A feature in PeopleSoft General Ledger that enables you to create a statutory chart of accounts and enter statutory account transactions at the detail transaction level, as required for recording and reporting by some national governments.
AR specialist	Abbreviation for <i>receivables specialist</i> . In PeopleSoft Receivables, an individual in who tracks and resolves deductions and disputed items.
arbitration plan	In PeopleSoft Enterprise Pricer, defines how price rules are to be applied to the base price when the transaction is priced.
assessment rule	In PeopleSoft Receivables, a user-defined rule that the system uses to evaluate the condition of a customer's account or of individual items to determine whether to generate a follow-up action.
asset class	An asset group used for reporting purposes. It can be used in conjunction with the asset category to refine asset classification.
attribute/value pair	In PeopleSoft Directory Interface, relates the data that makes up an entry in the directory information tree.
authentication server	A server that is set up to verify users of the system.
base time period	In PeopleSoft Business Planning, the lowest level time period in a calendar.
benchmark job	In PeopleSoft Workforce Analytics, a benchmark job is a job code for which there is corresponding salary survey data from published, third-party sources.
book	In PeopleSoft Asset Management, used for storing financial and tax information, such as costs, depreciation attributes, and retirement information on assets.
branch	A tree node that rolls up to nodes above it in the hierarchy, as defined in PeopleSoft Tree Manager.
budgetary account only	An account used by the system only and not by users; this type of account does not accept transactions. You can only budget with this account. Formerly called "system-maintained account."
budget check	In commitment control, the processing of source transactions against control budget ledgers, to see if they pass, fail, or pass with a warning.
budget control	In commitment control, budget control ensures that commitments and expenditures don't exceed budgets. It enables you to track transactions against corresponding budgets and terminate a document's cycle if the defined budget conditions are not met. For example, you can prevent a purchase order from being dispatched to a vendor if there are insufficient funds in the related budget to support it.
budget period	The interval of time (such as 12 months or 4 quarters) into which a period is divided for budgetary and reporting purposes. The ChartField allows maximum flexibility to define operational accounting time periods without restriction to only one calendar.
business event	In PeopleSoft Receivables, defines the processing characteristics for the Receivable Update process for a draft activity.

	In PeopleSoft Sales Incentive Management, an original business transaction or activity that may justify the creation of a PeopleSoft Enterprise Incentive Management event (a sale, for example).
business unit	A corporation or a subset of a corporation that is independent with regard to one or more operational or accounting functions.
buyer	In PeopleSoft eSettlements, an organization (or business unit, as opposed to an individual) that transacts with suppliers (vendors) within the system. A buyer creates payments for purchases that are made in the system.
catalog item	In PeopleSoft Enterprise Learning Management, a specific topic that a learner can study and have tracked. For example, "Introduction to Microsoft Word." A catalog item contains general information about the topic and includes a course code, description, categorization, keywords, and delivery methods. A catalog item can have one or more learning activities.
catalog map	In PeopleSoft Catalog Management, translates values from the catalog source data to the format of the company's catalog.
catalog partner	In PeopleSoft Catalog Management, shares responsibility with the enterprise catalog manager for maintaining catalog content.
categorization	Associates partner offerings with catalog offerings and groups them into enterprise catalog categories.
channel	In PeopleSoft MultiChannel Framework, email, chat, voice (computer telephone integration [CTI]), or a generic event.
ChartField	A field that stores a chart of accounts, resources, and so on, depending on the PeopleSoft application. ChartField values represent individual account numbers, department codes, and so forth.
ChartField balancing	You can require specific ChartFields to match up (balance) on the debit and the credit side of a transaction.
ChartField combination edit	The process of editing journal lines for valid ChartField combinations based on user-defined rules.
ChartKey	One or more fields that uniquely identify each row in a table. Some tables contain only one field as the key, while others require a combination.
checkbook	In PeopleSoft Promotions Management, enables you to view financial data (such as planned, incurred, and actual amounts) that is related to funds and trade promotions.
Class ChartField	A ChartField value that identifies a unique appropriation budget key when you combine it with a fund, department ID, and program code, as well as a budget period. Formerly called <i>sub-classification</i> .
clone	In PeopleCode, to make a unique copy. In contrast, to <i>copy</i> may mean making a new reference to an object, so if the underlying object is changed, both the copy and the original change.
collection	To make a set of documents available for searching in Verity, you must first create at least one collection. A collection is set of directories and files that allow search application users to use the Verity search engine to quickly find and display source documents that match search criteria. A collection is a set of statistics and pointers to the source documents, stored in a proprietary format on a file server. Because a collection can only store information for a single location, PeopleSoft maintains a set of collections (one per language code) for each search index object.

collection rule	In PeopleSoft Receivables, a user-defined rule that defines actions to take for a customer based on both the amount and the number of days past due for outstanding balances.
compensation object	In PeopleSoft Enterprise Incentive Management, a node within a compensation structure. Compensation objects are the building blocks that make up a compensation structure's hierarchical representation.
compensation structure	In PeopleSoft Enterprise Incentive Management, a hierarchical relationship of compensation objects that represents the compensation-related relationship between the objects.
condition	In PeopleSoft Receivables, occurs when there is a change of status for a customer's account, such as reaching a credit limit or exceeding a user-defined balance due.
configuration parameter catalog	Used to configure an external system with PeopleSoft. For example, a configuration parameter catalog might set up configuration and communication parameters for an external server.
configuration plan	In PeopleSoft Enterprise Incentive Management, configuration plans hold allocation information for common variables (not incentive rules) and are attached to a node without a participant. Configuration plans are not processed by transactions.
content reference	Content references are pointers to content registered in the portal registry. These are typically either URLs or iScripts. Content references fall into three categories: target content, templates, and template pagelets.
context	In PeopleCode, determines which buffer fields can be contextually referenced and which is the current row of data on each scroll level when a PeopleCode program is running. In PeopleSoft Enterprise Incentive Management, a mechanism that is used to determine the scope of a processing run. PeopleSoft Enterprise Incentive Management uses three types of context: plan, period, and run-level.
control table	Stores information that controls the processing of an application. This type of processing might be consistent throughout an organization, or it might be used only by portions of the organization for more limited sharing of data.
cost profile	A combination of a receipt cost method, a cost flow, and a deplete cost method. A profile is associated with a cost book and determines how items in that book are valued, as well as how the material movement of the item is valued for the book.
cost row	A cost transaction and amount for a set of ChartFields.
current learning	In PeopleSoft Enterprise Learning Management, a self-service repository for all of a learner's in-progress learning activities and programs.
data acquisition	In PeopleSoft Enterprise Incentive Management, the process during which raw business transactions are acquired from external source systems and fed into the operational data store (ODS).
data elements	Data elements, at their simplest level, define a subset of data and the rules by which to group them. For Workforce Analytics, data elements are rules that tell the system what measures to retrieve about your workforce groups.
dataset	A data grouping that enables role-based filtering and distribution of data. You can limit the range and quantity of data that is displayed for a user by associating dataset rules with user roles. The result of dataset rules is a set of data that is appropriate for the user's roles.

delivery method	In PeopleSoft Enterprise Learning Management, identifies the primary type of delivery method in which a particular learning activity is offered. Also provides default values for the learning activity, such as cost and language. This is primarily used to help learners search the catalog for the type of delivery from which they learn best. Because PeopleSoft Enterprise Learning Management is a blended learning system, it does not enforce the delivery method. In PeopleSoft Supply Chain Management, identifies the method by which goods are shipped to their destinations (such as truck, air, rail, and so on). The delivery method is specified when creating shipment schedules.
delivery method type	In PeopleSoft Enterprise Learning Management, identifies how learning activities can be delivered—for example, through online learning, classroom instruction, seminars, books, and so forth—in an organization. The type determines whether the delivery method includes scheduled components.
directory information tree	In PeopleSoft Directory Interface, the representation of a directory's hierarchical structure.
document sequencing	A flexible method that sequentially numbers the financial transactions (for example, bills, purchase orders, invoices, and payments) in the system for statutory reporting and for tracking commercial transaction activity.
dynamic detail tree	A tree that takes its detail values—dynamic details—directly from a table in the database, rather than from a range of values that are entered by the user.
edit table	A table in the database that has its own record definition, such as the Department table. As fields are entered into a PeopleSoft application, they can be validated against an edit table to ensure data integrity throughout the system.
effective date	A method of dating information in PeopleSoft applications. You can predate information to add historical data to your system, or postdate information in order to enter it before it actually goes into effect. By using effective dates, you don't delete values; you enter a new value with a current effective date.
EIM ledger	Abbreviation for <i>Enterprise Incentive Management ledger</i> . In PeopleSoft Enterprise Incentive Management, an object to handle incremental result gathering within the scope of a participant. The ledger captures a result set with all of the appropriate traces to the data origin and to the processing steps of which it is a result.
elimination set	In PeopleSoft General Ledger, a related group of intercompany accounts that is processed during consolidations.
entry event	In PeopleSoft General Ledger, Receivables, Payables, Purchasing, and Billing, a business process that generates multiple debits and credits resulting from single transactions to produce standard, supplemental accounting entries.
equitization	In PeopleSoft General Ledger, a business process that enables parent companies to calculate the net income of subsidiaries on a monthly basis and adjust that amount to increase the investment amount and equity income amount before performing consolidations.
event	A predefined point either in the Component Processor flow or in the program flow. As each point is encountered, the event activates each component, triggering any PeopleCode program that is associated with that component and that event. Examples of events are FieldChange, SavePreChange, and RowDelete. In PeopleSoft Human Resources, also refers to an incident that affects benefits eligibility.
event propagation process	In PeopleSoft Sales Incentive Management, a process that determines, through logic, the propagation of an original PeopleSoft Enterprise Incentive Management event and creates a derivative (duplicate) of the original event to be processed by other objects.

	Sales Incentive Management uses this mechanism to implement splits, roll-ups, and so on. Event propagation determines who receives the credit.
exception	In PeopleSoft Receivables, an item that either is a deduction or is in dispute.
exclusive pricing	In PeopleSoft Order Management, a type of arbitration plan that is associated with a price rule. Exclusive pricing is used to price sales order transactions.
fact	In PeopleSoft applications, facts are numeric data values from fields from a source database as well as an analytic application. A fact can be anything you want to measure your business by, for example, revenue, actual, budget data, or sales numbers. A fact is stored on a fact table.
forecast item	A logical entity with a unique set of descriptive demand and forecast data that is used as the basis to forecast demand. You create forecast items for a wide range of uses, but they ultimately represent things that you buy, sell, or use in your organization and for which you require a predictable usage.
fund	In PeopleSoft Promotions Management, a budget that can be used to fund promotional activity. There are four funding methods: top down, fixed accrual, rolling accrual, and zero-based accrual.
generic process type	In PeopleSoft Process Scheduler, process types are identified by a generic process type. For example, the generic process type SQR includes all SQR process types, such as SQR process and SQR report.
group	In PeopleSoft Billing and Receivables, a posting entity that comprises one or more transactions (items, deposits, payments, transfers, matches, or write-offs). In PeopleSoft Human Resources Management and Supply Chain Management, any set of records that are associated under a single name or variable to run calculations in PeopleSoft business processes. In PeopleSoft Time and Labor, for example, employees are placed in groups for time reporting purposes.
incentive object	In PeopleSoft Enterprise Incentive Management, the incentive-related objects that define and support the PeopleSoft Enterprise Incentive Management calculation process and results, such as plan templates, plans, results data, user interaction objects, and so on.
incentive rule	In PeopleSoft Sales Incentive Management, the commands that act on transactions and turn them into compensation. A rule is one part in the process of turning a transaction into compensation.
incur	In PeopleSoft Promotions Management, to become liable for a promotional payment. In other words, you owe that amount to a customer for promotional activities.
item	In PeopleSoft Inventory, a tangible commodity that is stored in a business unit (shipped from a warehouse). In PeopleSoft Demand Planning, Inventory Policy Planning, and Supply Planning, a noninventory item that is designated as being used for planning purposes only. It can represent a family or group of inventory items. It can have a planning bill of material (BOM) or planning routing, and it can exist as a component on a planning BOM. A planning item cannot be specified on a production or engineering BOM or routing, and it cannot be used as a component in a production. The quantity on hand will never be maintained.
KPI	In PeopleSoft Receivables, an individual receivable. An item can be an invoice, a credit memo, a debit memo, a write-off, or an adjustment. An abbreviation for <i>key performance indicator</i> . A high-level measurement of how well an organization is doing in achieving critical success factors. This defines the data value or calculation upon which an assessment is determined.

LDIF file	Abbreviation for <i>Lightweight Directory Access Protocol (LDAP) Data Interchange Format file</i> . Contains discrepancies between PeopleSoft data and directory data.
learner group	In PeopleSoft Enterprise Learning Management, a group of learners who are linked to the same learning environment. Members of the learner group can share the same attributes, such as the same department or job code. Learner groups are used to control access to and enrollment in learning activities and programs. They are also used to perform group enrollments and mass enrollments in the back office.
learning components	In PeopleSoft Enterprise Learning Management, the foundational building blocks of learning activities. PeopleSoft Enterprise Learning Management supports six basic types of learning components: web-based, session, webcast, test, survey, and assignment. One or more of these learning component types compose a single learning activity.
learning environment	In PeopleSoft Enterprise Learning Management, identifies a set of categories and catalog items that can be made available to learner groups. Also defines the default values that are assigned to the learning activities and programs that are created within a particular learning environment. Learning environments provide a way to partition the catalog so that learners see only those items that are relevant to them.
learning history	In PeopleSoft Enterprise Learning Management, a self-service repository for all of a learner's completed learning activities and programs.
ledger mapping	You use ledger mapping to relate expense data from general ledger accounts to resource objects. Multiple ledger line items can be mapped to one or more resource IDs. You can also use ledger mapping to map dollar amounts (referred to as <i>rates</i>) to business units. You can map the amounts in two different ways: an actual amount that represents actual costs of the accounting period, or a budgeted amount that can be used to calculate the capacity rates as well as budgeted model results. In PeopleSoft Enterprise Warehouse, you can map general ledger accounts to the EW Ledger table.
library section	In PeopleSoft Enterprise Incentive Management, a section that is defined in a plan (or template) and that is available for other plans to share. Changes to a library section are reflected in all plans that use it.
linked section	In PeopleSoft Enterprise Incentive Management, a section that is defined in a plan template but appears in a plan. Changes to linked sections propagate to plans using that section.
linked variable	In PeopleSoft Enterprise Incentive Management, a variable that is defined and maintained in a plan template and that also appears in a plan. Changes to linked variables propagate to plans using that variable.
load	In PeopleSoft Inventory, identifies a group of goods that are shipped together. Load management is a feature of PeopleSoft Inventory that is used to track the weight, the volume, and the destination of a shipment.
local functionality	In PeopleSoft HRMS, the set of information that is available for a specific country. You can access this information when you click the appropriate country flag in the global window, or when you access it by a local country menu.
location	Locations enable you to indicate the different types of addresses—for a company, for example, one address to receive bills, another for shipping, a third for postal deliveries, and a separate street address. Each address has a different location number. The primary location—indicated by a <i>1</i> —is the address you use most often and may be different from the main address.
logistical task	In PeopleSoft Services Procurement, an administrative task that is related to hiring a service provider. Logistical tasks are linked to the service type on the work order so that different types of services can have different logistical tasks. Logistical tasks include both preapproval tasks (such as assigning a new badge or ordering a new

laptop) and postapproval tasks (such as scheduling orientation or setting up the service provider email). The logistical tasks can be mandatory or optional. Mandatory preapproval tasks must be completed before the work order is approved. Mandatory postapproval tasks, on the other hand, must be completed before a work order is released to a service provider.

market template	In PeopleSoft Enterprise Incentive Management, additional functionality that is specific to a given market or industry and is built on top of a product category.
match group	In PeopleSoft Receivables, a group of receivables items and matching offset items. The system creates match groups by using user-defined matching criteria for selected field values.
MCF server	Abbreviation for <i>PeopleSoft MultiChannel Framework server</i> . Comprises the universal queue server and the MCF log server. Both processes are started when <i>MCF Servers</i> is selected in an application server domain configuration.
merchandising activity	In PeopleSoft Promotions Management, a specific discount type that is associated with a trade promotion (such as off-invoice, billback or rebate, or lump-sum payment) that defines the performance that is required to receive the discount. In the industry, you may know this as an offer, a discount, a merchandising event, an event, or a tactic.
meta-SQL	Meta-SQL constructs expand into platform-specific Structured Query Language (SQL) substrings. They are used in functions that pass SQL strings, such as in SQL objects, the SQLExec function, and PeopleSoft Application Engine programs.
metastring	Metastings are special expressions included in SQL string literals. The metastings, prefixed with a percent (%) symbol, are included directly in the string literals. They expand at run time into an appropriate substring for the current database platform.
multibook	In PeopleSoft General Ledger, multiple ledgers having multiple-base currencies that are defined for a business unit, with the option to post a single transaction to all base currencies (all ledgers) or to only one of those base currencies (ledgers).
multicurrency	The ability to process transactions in a currency other than the business unit's base currency.
national allowance	In PeopleSoft Promotions Management, a promotion at the corporate level that is funded by nondiscretionary dollars. In the industry, you may know this as a national promotion, a corporate promotion, or a corporate discount.
node-oriented tree	A tree that is based on a detail structure, but the detail values are not used.
pagelet	Each block of content on the home page is called a pagelet. These pagelets display summary information within a small rectangular area on the page. The pagelet provide users with a snapshot of their most relevant PeopleSoft and non-PeopleSoft content.
participant	In PeopleSoft Enterprise Incentive Management, participants are recipients of the incentive compensation calculation process.
participant object	Each participant object may be related to one or more compensation objects. See also <i>compensation object</i> .
partner	A company that supplies products or services that are resold or purchased by the enterprise.
pay cycle	In PeopleSoft Payables, a set of rules that define the criteria by which it should select scheduled payments for payment creation.
pending item	In PeopleSoft Receivables, an individual receivable (such as an invoice, a credit memo, or a write-off) that has been entered in or created by the system, but hasn't been posted.

PeopleCode	PeopleCode is a proprietary language, executed by the PeopleSoft application processor. PeopleCode generates results based upon existing data or user actions. By using business interlink objects, external services are available to all PeopleSoft applications wherever PeopleCode can be executed.
PeopleCode event	An action that a user takes upon an object, usually a record field, that is referenced within a PeopleSoft page.
PeopleSoft Internet Architecture	The fundamental architecture on which PeopleSoft 8 applications are constructed, consisting of a relational database management system (RDBMS), an application server, a web server, and a browser.
performance measurement	In PeopleSoft Enterprise Incentive Management, a variable used to store data (similar to an aggregator, but without a predefined formula) within the scope of an incentive plan. Performance measures are associated with a plan calendar, territory, and participant. Performance measurements are used for quota calculation and reporting.
period context	In PeopleSoft Enterprise Incentive Management, because a participant typically uses the same compensation plan for multiple periods, the period context associates a plan context with a specific calendar period and fiscal year. The period context references the associated plan context, thus forming a chain. Each plan context has a corresponding set of period contexts.
plan	In PeopleSoft Sales Incentive Management, a collection of allocation rules, variables, steps, sections, and incentive rules that instruct the PeopleSoft Enterprise Incentive Management engine in how to process transactions.
plan context	In PeopleSoft Enterprise Incentive Management, correlates a participant with the compensation plan and node to which the participant is assigned, enabling the PeopleSoft Enterprise Incentive Management system to find anything that is associated with the node and that is required to perform compensation processing. Each participant, node, and plan combination represents a unique plan context—if three participants are on a compensation structure, each has a different plan context. Configuration plans are identified by plan contexts and are associated with the participants that refer to them.
plan template	In PeopleSoft Enterprise Incentive Management, the base from which a plan is created. A plan template contains common sections and variables that are inherited by all plans that are created from the template. A template may contain steps and sections that are not visible in the plan definition.
planned learning	In PeopleSoft Enterprise Learning Management, a self-service repository for all of a learner's planned learning activities and programs.
planning instance	In PeopleSoft Supply Planning, a set of data (business units, items, supplies, and demands) constituting the inputs and outputs of a supply plan.
portal registry	In PeopleSoft applications, the portal registry is a tree-like structure in which content references are organized, classified, and registered. It is a central repository that defines both the structure and content of a portal through a hierarchical, tree-like structure of folders useful for organizing and securing content references.
price list	In PeopleSoft Enterprise Pricer, enables you to select products and conditions for which the price list applies to a transaction. During a transaction, the system either determines the product price based on the predefined search hierarchy for the transaction or uses the product's lowest price on any associated, active price lists. This price is used as the basis for any further discounts and surcharges.
price rule	In PeopleSoft Enterprise Pricer, defines the conditions that must be met for adjustments to be applied to the base price. Multiple rules can apply when conditions of each rule are met.

price rule condition	In PeopleSoft Enterprise Pricer, selects the price-by fields, the values for the price-by fields, and the operator that determines how the price-by fields are related to the transaction.
price rule key	In PeopleSoft Enterprise Pricer, defines the fields that are available to define price rule conditions (which are used to match a transaction) on the price rule.
process category	In PeopleSoft Process Scheduler, processes that are grouped for server load balancing and prioritization.
process group	In PeopleSoft Financials, a group of application processes (performed in a defined order) that users can initiate in real time, directly from a transaction entry page.
process definition	Process definitions define each run request.
process instance	A unique number that identifies each process request. This value is automatically incremented and assigned to each requested process when the process is submitted to run.
process job	You can link process definitions into a job request and process each request serially or in parallel. You can also initiate subsequent processes based on the return code from each prior request.
process request	A single run request, such as a Structured Query Report (SQR), a COBOL or Application Engine program, or a Crystal report that you run through PeopleSoft Process Scheduler.
process run control	A PeopleTools variable used to retain PeopleSoft Process Scheduler values needed at runtime for all requests that reference a run control ID. Do not confuse these with application run controls, which may be defined with the same run control ID, but only contain information specific to a given application process request.
product category	In PeopleSoft Enterprise Incentive Management, indicates an application in the Enterprise Incentive Management suite of products. Each transaction in the PeopleSoft Enterprise Incentive Management system is associated with a product category.
programs	In PeopleSoft Enterprise Learning Management, a high-level grouping that guides the learner along a specific learning path through sections of catalog items. PeopleSoft Enterprise Learning Systems provides two types of programs—curricula and certifications.
progress log	In PeopleSoft Services Procurement, tracks deliverable-based projects. This is similar to the time sheet in function and process. The service provider contact uses the progress log to record and submit progress on deliverables. The progress can be logged by the activity that is performed, by the percentage of work that is completed, or by the completion of milestone activities that are defined for the project.
project transaction	In PeopleSoft Project Costing, an individual transaction line that represents a cost, time, budget, or other transaction row.
promotion	In PeopleSoft Promotions Management, a trade promotion, which is typically funded from trade dollars and used by consumer products manufacturers to increase sales volume.
publishing	In PeopleSoft Enterprise Incentive Management, a stage in processing that makes incentive-related results available to participants.
record group	A set of logically and functionally related control tables and views. Record groups help enable TableSet sharing, which eliminates redundant data entry. Record groups ensure that TableSet sharing is applied consistently across all related tables and views.
record input VAT flag	Abbreviation for <i>record input value-added tax flag</i> . Within PeopleSoft Purchasing, Payables, and General Ledger, this flag indicates that you are recording input VAT

	on the transaction. This flag, in conjunction with the record output VAT flag, is used to determine the accounting entries created for a transaction and to determine how a transaction is reported on the VAT return. For all cases within Purchasing and Payables where VAT information is tracked on a transaction, this flag is set to Yes. This flag is not used in PeopleSoft Order Management, Billing, or Receivables, where it is assumed that you are always recording only output VAT, or in PeopleSoft Expenses, where it is assumed that you are always recording only input VAT.
record output VAT flag	Abbreviation for <i>record output value-added tax flag</i> . See <i>record input VAT flag</i> .
reference data	In PeopleSoft Sales Incentive Management, system objects that represent the sales organization, such as territories, participants, products, customers, channels, and so on.
reference object	In PeopleSoft Enterprise Incentive Management, this dimension-type object further defines the business. Reference objects can have their own hierarchy (for example, product tree, customer tree, industry tree, and geography tree).
reference transaction	In commitment control, a reference transaction is a source transaction that is referenced by a higher-level (and usually later) source transaction, in order to automatically reverse all or part of the referenced transaction's budget-checked amount. This avoids duplicate postings during the sequential entry of the transaction at different commitment levels. For example, the amount of an encumbrance transaction (such as a purchase order) will, when checked and recorded against a budget, cause the system to concurrently reference and relieve all or part of the amount of a corresponding pre-encumbrance transaction, such as a purchase requisition.
regional sourcing	In PeopleSoft Purchasing, provides the infrastructure to maintain, display, and select an appropriate vendor and vendor pricing structure that is based on a regional sourcing model where the multiple ship to locations are grouped. Sourcing may occur at a level higher than the ship to location.
relationship object	In PeopleSoft Enterprise Incentive Management, these objects further define a compensation structure to resolve transactions by establishing associations between compensation objects and business objects.
remote data source data	Data that is extracted from a separate database and migrated into the local database.
REN server	Abbreviation for <i>real-time event notification server</i> in PeopleSoft MultiChannel Framework.
requester	In PeopleSoft eSettlements, an individual who requests goods or services and whose ID appears on the various procurement pages that reference purchase orders.
role	Describes how people fit into PeopleSoft Workflow. A role is a class of users who perform the same type of work, such as clerks or managers. Your business rules typically specify what user role needs to do an activity.
role user	A PeopleSoft Workflow user. A person's role user ID serves much the same purpose as a user ID does in other parts of the system. PeopleSoft Workflow uses role user IDs to determine how to route worklist items to users (through an email address, for example) and to track the roles that users play in the workflow. Role users do not need PeopleSoft user IDs.
roll up	In a tree, to roll up is to total sums based on the information hierarchy.
run control	A run control is a type of online page that is used to begin a process, such as the batch processing of a payroll run. Run control pages generally start a program that manipulates data.
run control ID	A unique ID to associate each user with his or her own run control table entries.

run-level context	In PeopleSoft Enterprise Incentive Management, associates a particular run (and batch ID) with a period context and plan context. Every plan context that participates in a run has a separate run-level context. Because a run cannot span periods, only one run-level context is associated with each plan context.
search query	You use this set of objects to pass a query string and operators to the search engine. The search index returns a set of matching results with keys to the source documents.
section	In PeopleSoft Enterprise Incentive Management, a collection of incentive rules that operate on transactions of a specific type. Sections enable plans to be segmented to process logical events in different sections.
security event	In commitment control, security events trigger security authorization checking, such as budget entries, transfers, and adjustments; exception overrides and notifications; and inquiries.
serial genealogy	In PeopleSoft Manufacturing, the ability to track the composition of a specific, serial-controlled item.
serial in production	In PeopleSoft Manufacturing, enables the tracing of serial information for manufactured items. This is maintained in the Item Master record.
session	In PeopleSoft Enterprise Learning Management, a single meeting day of an activity (that is, the period of time between start and finish times within a day). The session stores the specific date, location, meeting time, and instructor. Sessions are used for scheduled training.
session template	In PeopleSoft Enterprise Learning Management, enables you to set up common activity characteristics that may be reused while scheduling a PeopleSoft Enterprise Learning Management activity—characteristics such as days of the week, start and end times, facility and room assignments, instructors, and equipment. A session pattern template can be attached to an activity that is being scheduled. Attaching a template to an activity causes all of the default template information to populate the activity session pattern.
setup relationship	In PeopleSoft Enterprise Incentive Management, a relationship object type that associates a configuration plan with any structure node.
share driver expression	In PeopleSoft Business Planning, a named planning method similar to a driver expression, but which you can set up globally for shared use within a single planning application or to be shared between multiple planning applications through PeopleSoft Enterprise Warehouse.
single signon	With single signon, users can, after being authenticated by a PeopleSoft application server, access a second PeopleSoft application server without entering a user ID or password.
source transaction	In commitment control, any transaction generated in a PeopleSoft or third-party application that is integrated with commitment control and which can be checked against commitment control budgets. For example, a pre-encumbrance, encumbrance, expenditure, recognized revenue, or collected revenue transaction.
SpeedChart	A user-defined shorthand key that designates several ChartKeys to be used for voucher entry. Percentages can optionally be related to each ChartKey in a SpeedChart definition.
SpeedType	A code representing a combination of ChartField values. SpeedTypes simplify the entry of ChartFields commonly used together.
staging	A method of consolidating selected partner offerings with the offerings from the enterprise's other partners.

statutory account	Account required by a regulatory authority for recording and reporting financial results. In PeopleSoft, this is equivalent to the Alternate Account (ALTACCT) ChartField.
step	In PeopleSoft Sales Incentive Management, a collection of sections in a plan. Each step corresponds to a step in the job run.
storage level	In PeopleSoft Inventory, identifies the level of a material storage location. Material storage locations are made up of a business unit, a storage area, and a storage level. You can set up to four storage levels.
subcustomer qualifier	A value that groups customers into a division for which you can generate detailed history, aging, events, and profiles.
Summary ChartField	You use summary ChartFields to create summary ledgers that roll up detail amounts based on specific detail values or on selected tree nodes. When detail values are summarized using tree nodes, summary ChartFields must be used in the summary ledger data record to accommodate the maximum length of a node name (20 characters).
summary ledger	An accounting feature used primarily in allocations, inquiries, and PS/nVision reporting to store combined account balances from detail ledgers. Summary ledgers increase speed and efficiency of reporting by eliminating the need to summarize detail ledger balances each time a report is requested. Instead, detail balances are summarized in a background process according to user-specified criteria and stored on summary ledgers. The summary ledgers are then accessed directly for reporting.
summary time period	In PeopleSoft Business Planning, any time period (other than a base time period) that is an aggregate of other time periods, including other summary time periods and base time periods, such as quarter and year total.
summary tree	A tree used to roll up accounts for each type of report in summary ledgers. Summary trees enable you to define trees on trees. In a summary tree, the detail values are really nodes on a detail tree or another summary tree (known as the <i>basis</i> tree). A summary tree structure specifies the details on which the summary trees are to be built.
syndicate	To distribute a production version of the enterprise catalog to partners.
system function	In PeopleSoft Receivables, an activity that defines how the system generates accounting entries for the general ledger.
TableSet	A means of sharing similar sets of values in control tables, where the actual data values are different but the structure of the tables is the same.
TableSet sharing	Shared data that is stored in many tables that are based on the same TableSets. Tables that use TableSet sharing contain the SETID field as an additional key or unique identifier.
target currency	The value of the entry currency or currencies converted to a single currency for budget viewing and inquiry purposes.
template	A template is HTML code associated with a web page. It defines the layout of the page and also where to get HTML for each part of the page. In PeopleSoft, you use templates to build a page by combining HTML from a number of sources. For a PeopleSoft portal, all templates must be registered in the portal registry, and each content reference must be assigned a template.
territory	In PeopleSoft Sales Incentive Management, hierarchical relationships of business objects, including regions, products, customers, industries, and participants.
TimeSpan	A relative period, such as year-to-date or current period, that can be used in various PeopleSoft General Ledger functions and reports when a rolling time frame, rather

	than a specific date, is required. TimeSpans can also be used with flexible formulas in PeopleSoft Projects.
trace usage	In PeopleSoft Manufacturing, enables the control of which components will be traced during the manufacturing process. Serial- and lot-controlled components can be traced. This is maintained in the Item Master record.
transaction allocation	In PeopleSoft Enterprise Incentive Management, the process of identifying the owner of a transaction. When a raw transaction from a batch is allocated to a plan context, the transaction is duplicated in the PeopleSoft Enterprise Incentive Management transaction tables.
transaction state	In PeopleSoft Enterprise Incentive Management, a value assigned by an incentive rule to a transaction. Transaction states enable sections to process only transactions that are at a specific stage in system processing. After being successfully processed, transactions may be promoted to the next transaction state and “picked up” by a different section for further processing.
Translate table	A system edit table that stores codes and translate values for the miscellaneous fields in the database that do not warrant individual edit tables of their own.
tree	The graphical hierarchy in PeopleSoft systems that displays the relationship between all accounting units (for example, corporate divisions, projects, reporting groups, account numbers) and determines roll-up hierarchies.
unclaimed transaction	In PeopleSoft Enterprise Incentive Management, a transaction that is not claimed by a node or participant after the allocation process has completed, usually due to missing or incomplete data. Unclaimed transactions may be manually assigned to the appropriate node or participant by a compensation administrator.
universal navigation header	Every PeopleSoft portal includes the universal navigation header, intended to appear at the top of every page as long as the user is signed on to the portal. In addition to providing access to the standard navigation buttons (like Home, Favorites, and signoff) the universal navigation header can also display a welcome message for each user.
user interaction object	In PeopleSoft Sales Incentive Management, used to define the reporting components and reports that a participant can access in his or her context. All Sales Incentive Management user interface objects and reports are registered as user interaction objects. User interaction objects can be linked to a compensation structure node through a compensation relationship object (individually or as groups).
variable	In PeopleSoft Sales Incentive Management, the intermediate results of calculations. Variables hold the calculation results and are then inputs to other calculations. Variables can be plan variables that persist beyond the run of an engine or local variables that exist only during the processing of a section.
VAT exception	Abbreviation for <i>value-added tax exception</i> . A temporary or permanent exemption from paying VAT that is granted to an organization. This terms refers to both VAT exoneration and VAT suspension.
VAT exempt	Abbreviation for <i>value-added tax exempt</i> . Describes goods and services that are not subject to VAT. Organizations that supply exempt goods or services are unable to recover the related input VAT. This is also referred to as exempt without recovery.
VAT exoneration	Abbreviation for <i>value-added tax exoneration</i> . An organization that has been granted a permanent exemption from paying VAT due to the nature of that organization.
VAT suspension	Abbreviation for <i>value-added tax suspension</i> . An organization that has been granted a temporary exemption from paying VAT.
warehouse	A PeopleSoft data warehouse that consists of predefined ETL maps, data warehouse tools, and DataMart definitions.

work order	In PeopleSoft Services Procurement, enables an enterprise to create resource-based and deliverable-based transactions that specify the basic terms and conditions for hiring a specific service provider. When a service provider is hired, the service provider logs time or progress against the work order.
worksheet	A way of presenting data through a PeopleSoft Business Analysis Modeler interface that enables users to do in-depth analysis using pivoting tables, charts, notes, and history information.
worklist	The automated to-do list that PeopleSoft Workflow creates. From the worklist, you can directly access the pages you need to perform the next action, and then return to the worklist for another item.
XML schema	An XML definition that standardizes the representation of application messages, component interfaces, or business interlinks.
yield by operation	In PeopleSoft Manufacturing, the ability to plan the loss of a manufactured item on an operation-by-operation basis.
zero-rated VAT	Abbreviation for <i>zero-rated value-added tax</i> . A VAT transaction with a VAT code that has a tax percent of zero. Used to track taxable VAT activity where no actual VAT amount is charged. Organizations that supply zero-rated goods and services can still recover the related input VAT. This is also referred to as exempt with recovery.

Index

Numerics/Symbols

- # character 15
- \$ character 15
- % character 15
- & character 15
- @ character 15
- : character, in variable names 15
- _ character, in variable names 15
- ! characters
 - displaying 4
 - for comment lines 4
- ' characters, displaying 4
- 3D-EFFECTS argument, DECLARE-CHART command 68

A

- A flag 6, 247, 256
- absolute value (abs) function 132
- acos function 132
- ADD command 22
- additional documentation xii
- AF command-line parameter 298
- AFTER argument, BEGIN-EXECUTE command 39
- AFTER-BOLD argument
 - DECLARE PRINTER command 269
 - DECLARE-PRINTER command 89
 - PRINT command 179
- AFTER-PAGE argument
 - DECLARE PROCEDURE command 270
 - DECLARE-PROCEDURE command 94
 - DECLARE-TOC command 97
 - USE-PROCEDURE command 221
- AFTER-REPORT argument
 - DECLARE PROCEDURE command 270
 - DECLARE-PROCEDURE command 94
 - USE-PROCEDURE command 221
- AFTER-TOC argument, DECLARE-TOC command 97
- ALTER-COLOR-MAP command 23

- ALTER-LOCALE command 25, 261, 270, 272, 287
- ALTER-PRINTER command 32, 84, 92, 261, 271
- ALTER-REPORT command 33
- AP command-line parameter 298
- APPEND argument, SECURITY command 208
- applets, HTML 7
- application fundamentals xi
- arccosine (acos) function 132
- arcsine (asin) function 133
- arctangent (atan) function 133
- args... command-line argument 5
- arguments
 - separating from commands 4
 - using with procedures 106
- array field operands 130
- array function 142
- ARRAY-ADD command 34
- ARRAY-DIVIDE command 34
- ARRAY-MULTIPLY command 34
- ARRAY-SUBTRACT command 34
- arrays
 - arithmetic 34
 - ARRAY-ADD command 34
 - ARRAY-DIVIDE command 34
 - ARRAY-MULTIPLY command 34
 - ARRAY-SUBTRACT command 34
 - CLEAR-ARRAY command 56
 - CREATE-ARRAY command 61
 - elements 61
 - maximums 61
 - moving data into 203
 - resetting fields 56
 - retrieving data from 117
 - searching 163
- ascii function 142
- asciic function 142
- asin function 133
- ASK command 48, 100, 125
 - preventing user input 14
 - understanding 36
- AT-END argument, NEXT-COLUMN command 170

atan function 133

B

bar codes

printing 194

types 194

UPC-A 196

BATCH-MODE argument, INPUT

command 128, 129

BEEP argument, SHOW command 212

BEFORE argument, BEGIN-EXECUTE

command 39

BEFORE-BOLD argument

DECLARE PRINTER command 269

DECLARE-PRINTER command 89

PRINT command 179

BEFORE-PAGE argument

DECLARE PROCEDURE

command 270

DECLARE-PROCEDURE

command 94

DECLARE-TOC command 97

USE-PROCEDURE command 221

BEFORE-REPORT argument

DECLARE PROCEDURE

command 270

DECLARE-PROCEDURE

command 94

USE-PROCEDURE command 221

BEFORE-TOC argument, DECLARE-TOC

command 97

BEGIN TRANSACTION command,

Sybase and Microsoft SQL Server 206

BEGIN-DOCUMENT command 37, 108

BEGIN-EXECUTE command 38

BEGIN-FOOTING command 40, 108

BEGIN-HEADING command 42, 108

BEGIN-PROCEDURE command 43,

109

BEGIN-PROGRAM command 45, 109,

261, 262

BEGIN-REPORT command 261, 262

BEGIN-SELECT command 38, 46, 109

BEGIN-SETUP command 2, 48, 109

BEGIN-SQL command 48, 49, 109

bind variables 47

blanks, trailing 11, 13, 14

BLINK argument, SHOW command 212

-Bnn argument, BEGIN-SELECT

command 47

-Bnn flag 6

BOLD argument

PRINT command 178

SHOW command 212

BORDER argument, DECLARE-CHART

command 68

BOTTOM-MARGIN argument,

DECLARE-LAYOUT command 80

BOX argument

GRAPHIC command 121

PRINT command 179

boxes, drawing 120

branching, EVALUATE command 110

BREAK argument, EVALUATE

command 111

BREAK command 52

browser, determining 8

buffer 6

-BURST:{xx} flag 6, 248, 256

buttons, HTML 291

C

-C flag 6, 247

C, writing functions in 157

-CA command-line parameter 297

CALL command 52

CALL SYSTEM command 52

Cancel dialog box 6

-CAP command-line parameter 297

CAPTION argument, PRINT-BAR-CODE

command 196

case/switch 110

-CB flag 6, 248

-CD command-line parameter 297

ceil function 133

CENTER argument, PRINT command

179

CHAR, TEXT data type 127

CHAR-SIZE argument, DECLARE

PRINTER command 266

CHAR-WIDTH argument

DECLARE-LAYOUT command 77,

81

character columns 15

character sequences, finding 116

character sets, specifying in Windows 291

characters

control 10, 275, 276

converting single-byte to multibyte 207

display 107

- multibyte 207
- nondisplay 107, 275, 276
- printer control 11
- single-byte 207
- CHARS-INCH argument, DECLARE PRINTER command 266
- CHART.FILL option 66
- CHART-SIZE argument, DECLARE-CHART command 67
- charts 197
 - business 67
 - colors 67
 - defining attributes 65
 - printing 198
 - types 199
- CHECKSUM argument, PRINT-BAR-CODE command 196
- chr function 143
- CLEAR-ARRAY command 56, 62
- CLEAR-LINE argument, SHOW command 212
- CLEAR-SCREEN argument, SHOW command 212
- CLOSE command 57, 172
- Cnn argument
 - BEGIN-SELECT command 47
 - BEGIN-SQL command 51
- CO command-line parameter 297
- CODE-PRINTER argument, PRINT command 179
- COLOR argument, DECLARE-PRINTER command 86
- color palettes 66
- COLOR_1 argument, CREATE-COLOR-PALETTE command 63
- COLOR_2 argument, CREATE-COLOR-PALETTE command 63
- COLOR_n argument, CREATE-COLOR-PALETTE command 63
- COLOR-PALETTE argument, DECLARE-CHART command 68
- colors
 - altering defined 23
 - defaults 24, 73, 118, 209
 - defining in SQR reports 73
 - naming 23, 118
 - palettes 63, 66
 - references 63
 - retrieving 118
- Colors section, pssqr.ini 296
- columns 15
 - character 15
 - date 15
 - determining value 110
 - displaying 102
 - dynamic 15
 - global 16
 - local 16
 - not supported in DECLARE-CHART or PRINT-CHART command 66
 - number 15
 - reserved variable for current 16
 - reserved variable for maximum 18
 - setting current 219
- COLUMNS argument, POSITION command 175
- COLUMNS command 57, 170, 220
- COMMAND argument, BEGIN-EXECUTE command 39
- command line, SQR 4
- command-line arguments 4
 - args... 5
 - connectivity 5
 - @file... 5
 - flags 5
 - program 4
- command-line flags 5
 - SQR Print 256
- commands
 - abbreviations in 21
 - avoiding older 261
 - breaking 4
 - case insensitivity 4
 - hyphens in 4
 - listed alphabetically 21
 - overview 21
 - rules for entering 4
 - separating from arguments 4
- comments 4
- comments, submitting xv
- COMMIT command
 - suppressing 13
 - understanding 58
- COMMIT TRANSACTION command 59
- common elements xv
- comparison operators 123, 130
- compiler directives 107, 109, 125
 - nesting 122
 - table of 122

- CONCAT command
 - edit masks 187
 - understanding 59
- concatenation, with STRING
 - command 215
- cond function 143
- conditional processing 110, 124, 223
- Configuration Manager 297
- CONNECT command 58, 60
- CONNECTION argument,
 - BEGIN-EXECUTE command 39
- connection_name argument 74
- connectivity command-line argument 5
- constants
 - specifying 100
 - understanding 19
- contact information xv
- control characters 10, 275, 276
- copyright banner 10
- cos function 134
- cosh function 134
- cosine (cos) function 134
- COWN command-line parameter 297
- CREATE-ARRAY command 34, 48, 61, 203
- CREATE-COLOR-PALETTE
 - command 62
- cross-references xiv
- CS command-line parameter 297
- CT command-line parameter 297
- currency symbols
 - redefining 272
 - specifying 27, 270
- #current-column reserved variable 16
- \$current-date reserved variable 16
- #current-line reserved variable 16, 169
- cursors
 - controlling 211
 - database 60
 - displaying 13
- Customer Connection website xii

D

- data
 - elements 15
 - input 126
 - retrieving from array 117
 - types supported by INPUT
 - command 127
- data elements

- columns 15
- defining 15
- literals 19
- variables 15
- DATA-ARRAY argument, PRINT-CHART
 - command 197, 200
- DATA-ARRAY-COLUMN-COUNT
 - argument, PRINT-CHART command 197, 200
- DATA-ARRAY-COLUMN-LABELS
 - argument, PRINT-CHART
 - command 197, 200
- DATA-ARRAY-ROW-COUNT argument,
 - PRINT-CHART command 197, 200
- DATA-LABELS argument,
 - DECLARE-CHART command 67
- database
 - commit 58
 - cursors 60
 - joins 161
 - preventing signin 14
 - suppressing commit 13
 - types 17
 - username 18
 - using designated 219
- datasource, logon parameters 74
- date
 - columns 15
 - default formats 27, 188
 - displaying 102
 - edit format characters 184
 - edit masks 27
 - reserved variable for current 16
 - variables 15
- DATE argument
 - DECLARE-VARIABLE command 99
 - DISPLAY command 103
 - MOVE command 165
 - PRINT command 180
 - SHOW command 212
- DATE column type 180
- DATE data type 127
- date functions
 - dateadd 143
 - datediff 144
 - datenow 144
 - datetostr 144
 - strtodate 152

- DATE-EDIT-MASK keyword,
 - ALTER-LOCALE command 26, 27
- DATE-SEPARATOR keyword,
 - ALTER-LOCALE command 26, 28
- DATE-TIME command 261, 262
- dateadd function 143
- datediff function 144
- datenow function 144, 261, 262
- DATETIME column type 180
- datetostr function 144
- DAY-OF-WEEK-CASE keyword,
 - ALTER-LOCALE command 26, 28
- DAY-OF-WEEK-FULL keyword,
 - ALTER-LOCALE command 27, 28
- DAY-OF-WEEK-SHORT keyword,
 - ALTER-LOCALE command 27, 28
- DB2 206
 - COMMIT command 58
 - ROLLBACK command 206
- DBconnectionstring argument,
 - BEGIN-SELECT command 47, 51
- DBdatabase flag 7, 248
- #DEBUG command 63
- DEBUG flag 7, 63, 122, 125
- DEBUGLP ON command-line parameter 299
- DECIMAL argument, DECLARE-VARIABLE command 99
- decimal variables 16, 22
- DECIMAL-SEPARATOR keyword,
 - ALTER-LOCALE command 26, 28
- DECLARE LAYOUT command 264
- DECLARE PRINTER command 261, 264
- DECLARE PROCEDURE
 - command 261, 269
- DECLARE-CHART command 48, 64, 108, 197
- DECLARE-COLOR-MAP command 73
- DECLARE-CONNECTION
 - command 74
- DECLARE-IMAGE command 48, 75, 108
- DECLARE-LAYOUT command 48, 76, 108, 169, 261
 - arguments of 78
 - FORMFEED argument 273
 - MAX-COLUMNS argument 274
 - MAX-LINES argument 274
 - PAPER-SIZE argument 274
- DECLARE-PRINTER command 48, 84, 108, 179, 261, 262, 264, 271
 - FILL specification 66
 - INIT-STRING argument 276
 - RESET-STRING argument 275
- DECLARE-PROCEDURE command 49, 93, 108, 201, 221, 261, 269
- DECLARE-REPORT command 49, 77, 94, 108
- DECLARE-TOC command 49, 96
- DECLARE-VARIABLE command 49, 98, 108
- default colors 209
- DEFAULT layout 77
- default settings section
 - pssqr.ini 278
- DEFAULT-NUMERIC argument,
 - DECLARE-VARIABLE command 99
- #DEFINE command 100, 125
- deg function 134
- degrees 134
- delete function 141
- destination field 164
- dimension hierarchy
 - extending 210
 - specifying 210
- display characters 107
- DISPLAY command
 - edit masks 187
 - understanding 102
- DISTINCT argument, BEGIN-SELECT command 47
- DIVIDE command 105
- DL command-line parameter 298
- Dnn flag 7, 248, 256
- DNT flag 7, 98
- DO argument, EXECUTE command 113
- DO command 44, 46, 106
- document marker 37, 175
- document paragraphs 4, 37, 175, 412
- documentation
 - printed xii
 - related xii
 - updates xii
- DOLLAR-SYMBOL command 261, 270, 272

DOT-LEADER argument,
 DECLARE-TOC command 97
 double precision floating point
 numbers 22
 double-byte character strings 18
 double-byte strings 164
 DSN 23
 dst_any_var argument, MOVE
 command 165
 dynamic columns 15
 dynamic query variables 47

E

-E[file] flag 7, 248, 256
 e10 function 135
 EDIT argument
 PRINT command 180
 SHOW command 212
 edit function 145
 edit masks 60
 case sensitivity 186
 changing dynamically 187
 currency symbols 27, 270
 date 27
 date samples 186
 numeric 27
 numeric samples 182
 uses 183
 edit types 180
 EDIT-OPTION-AD keyword,
 ALTER-LOCALE command 26,
 28
 EDIT-OPTION-AM keyword,
 ALTER-LOCALE command 26,
 27, 28
 EDIT-OPTION-BC keyword,
 ALTER-LOCALE command 26,
 28
 EDIT-OPTION-NA keyword,
 ALTER-LOCALE command 26,
 28
 EDIT-OPTION-PM keyword,
 ALTER-LOCALE command 26,
 28
 -EH_APPLETS:dir flag 7, 248, 257
 -EH_BQD flag 7, 249, 257
 -EH_BQD:file flag 7, 249, 257
 -EH_BROWSER:xx flag 8, 249, 257
 -EH_CSV flag 8, 249, 257
 -EH_CSV:file flag 8, 249, 257
 -EH_CSVONLY flag 8, 249, 257
 -EH_FULLHTML:xx flag 8, 249, 257
 -EH_Icons:dir flag 8, 249, 257
 -EH_IMAGES:dir flag 8
 -EH_KEEP flag 9
 -EH_LANGUAGE:xx flag 9, 249
 -EH_PDF flag 9, 249, 257
 -EH_Scale:{nn} flag 9, 249, 258
 -EH_XML:file flag 9
 -EH_ZIP[:file] flag 9
 ELSE command 107
 #ELSE compiler directive 107, 122
 ENCODE command 107
 ENCODING environment variable 18
 END-DECLARE command 108
 END-DOCUMENT command 37, 108
 END-EVALUATE command 108
 END-EXECUTE command 38
 #end-file reserved variable 16, 204
 END-FOOTING command 40, 108
 END-HEADING command 42, 108
 END-IF command 109, 124
 #END-IF compiler directive 108
 END-PROCEDURE command 43, 109
 END-PROGRAM command 45, 109, 261
 END-REPORT command 261
 END-SELECT command 46, 109
 END-SETUP command 2, 48, 109
 END-SQL command 49, 109
 END-WHILE command 109, 223
 #ENDIF compiler directive 108, 122
 ending a query 114
 Enhanced-HTML section, pssqr.ini 295
 Environment sections, pssqr.ini 286
 ERASE-PAGE argument,
 NEXT-COLUMN command 170
 error messages, *See* messages
 errors
 testing conditions 206
 trapping 47
 escape sequences 107
 EVALUATE command 108, 110, 223
 branching 110
 exiting from with BREAK 52
 nesting 110
 exclusion ranges 294
 execute
 begin 38
 end 38

EXECUTE command (Sybase and Microsoft SQL Server) 112
 exists function 141
 EXIT-SELECT command 114
 exp function 135
 exponents 135
 expressions 130
 operands 130
 operators 131
 EXTENT argument, LOAD-LOOKUP command 161
 EXTRACT command 114

F

-F[file|directory] flag 10, 250, 258
 FIELD argument, CREATE-ARRAY command 62
 -FILE command-line parameter 298
 file number 173
 file types
 FIXED 173
 FIXED_NOLF 173
 VARY 173
 @file... command-line argument 5
 file-related functions 140
 delete 141
 exists 141
 rename 141
 files
 closing 57
 include 126
 including external source 126
 reading 204
 FILL argument
 DECLARE-CHART command 68
 PRINT command 188
 FIND command 116
 FIXED argument, OPEN command 173
 FIXED file type 173
 FIXED_NOLF argument, OPEN command 173
 FIXED_NOLF file types 173
 flagging SQR 5
 flags command-line argument 5
 FLOAT argument, DECLARE-VARIABLE command 99
 float variables 16, 22
 floating point numbers 22
 floor function 135
 FONT argument
 ALTER-PRINTER command 32
 DECLARE PRINTER command 268
 DECLARE-PRINTER command 88
 FONT-TYPE argument
 ALTER-PRINTER command 32
 DECLARE PRINTER command 267
 DECLARE-PRINTER command 86
 fonts
 adding entries 290
 changing 272
 HP LaserJet 89
 PostScript 90
 Windows 92
 Fonts section, pssqr.ini 92, 290
 specifying character sets 291
 FOOTING argument
 ALTER-REPORT command 33
 FOOTING argument, ALTER-REPORT command 33
 FOOTING section 2, 40
 FOOTING-SIZE argument,
 ALTER-REPORT command 33
 footings 33
 FOR-APPEND argument, OPEN command 173
 FOR-READING argument, OPEN command 173
 FOR-REPORTS argument
 BEGIN-FOOTING command 41
 BEGIN-HEADING command 43
 DECLARE-PRINTER command 85
 DECLARE-PROCEDURE command 94
 DECLARE-TOC command 97
 USE-PROCEDURE command 221
 FOR-TOCS argument
 BEGIN-FOOTING command 41
 BEGIN-HEADING command 43
 FOR-WRITING argument, OPEN command 173
 FOREGROUND/BACKGROUND argument, PRINT command 189
 form feeds, trailing 14
 form letters 4
 FORMAT argument, INPUT command 128
 format_mask argument, MOVE command 165
 FORMFEED argument, DECLARE-LAYOUT command 79, 273

FROM PARAMETER, BEGIN-EXECUTE
 command 39
 FROM ROWSET argument,
 BEGIN-EXECUTE command 39
 functions
 custom 157
 file-related 132, 140
 miscellaneous 132, 141
 numeric 132, 158
 random 158
 string 157
 transcendental 140
 functions, miscellaneous
 array 142
 ascii 142
 asciic 142
 chr (character) 143
 cond 143
 edit 145
 getenv (get environment variable) 145
 isblank 146
 isnull 146
 to_char 154
 to_multi_byte 154
 to_number 155
 to_single_byte 155
 wrapdepth 157

G

GET command 117
 GET-COLOR command 117
 getenv function 145
 glossary 435
 GOTO command 119
 GOTO-TOP argument, NEXT-COLUMN
 command 170
 -GPRINT=YES | NO flag 10, 250
 GRAPHIC BOX command 120, 121
 GRAPHIC command 120
 GRAPHIC FONT command 261, 271
 GRAPHIC HORZ-LINE command 120,
 121
 GRAPHIC VERT-LINE command 120,
 121
 grid, SQR 77

H

HEADING argument, ALTER-REPORT
 command 33

HEADING section 2, 42
 HEADING-SIZE argument,
 ALTER-REPORT command 33
 headings 33, 42
 HEIGHT argument, PRINT-BAR CODE
 command 196
 HORZ-LINE argument, GRAPHIC
 command 121
 hostname, reserved variable for current 18
 HPLASERJET 85
 HTML
 activating procedures 229
 adding horizontal divider 228
 applets 7
 blinking text 234
 <BODY> tags 231
 centering 228
 citations 235
 code listings 235
 column headers 246
 columns in tables 246
 definition lists 241
 definitions in definition lists 240
 directory lists 240
 displaying 8
 ending paragraphs 230
 enhanced code 8
 general-purpose procedures 227
 generating 8
 generating output 227
 <HEAD> tags 231
 heading procedures 231
 highlighting procedures 234
 hypertext link procedures 238
 hypertext links 239
 inserting images 229
 keyboard input 236
 line breaks 228
 list items 241
 list procedures 239
 marking text that cannot wrap 229
 menus 242
 ordered lists 242
 preventing wrapping 229
 publishing 227
 rows in tables 246
 sample style text 236
 starting new paragraph 230
 strikethrough text 237
 subscript text 237

- superscript text 238
 - table captions 244
 - table procedures 243
 - tables 245
 - terms in definition lists 241
 - unordered lists 243
 - HTML buttons 291
 - html_a procedure 239
 - html_a_end procedure 239
 - html_blink procedure 234
 - html_blink_end procedure 234
 - html_br procedure 228
 - html_caption procedure 244
 - html_caption_end procedure 244
 - html_center procedure 228
 - html_center_end procedure 228
 - html_cite procedure 235
 - html_cite_end procedure 235
 - html_code procedure 235
 - html_code_end procedure 235
 - html_dd procedure 240
 - html_dd_end procedure 240
 - html_dir procedure 240
 - html_dir_end procedure 240
 - html_dl procedure 241
 - html_dl_end procedure 241
 - html_dt procedure 241
 - html_dt_end procedure 241
 - html_h1 procedure 232
 - html_h1_end procedure 232
 - html_h2 procedure 232
 - html_h2_end procedure 232
 - html_h3 procedure 233
 - html_h3_end procedure 233
 - html_h4 procedure 233
 - html_h4_end procedure 233
 - html_h5 procedure 233
 - html_h5_end procedure 234
 - html_h6 procedure 234
 - html_h6_end procedure 234
 - html_hr procedure 228
 - HTML-Images section, pssqr.ini 291
 - html_img procedure 229
 - html_kbd procedure 236
 - html_kbd_end procedure 236
 - html_li procedure 241
 - html_li_end procedure 242
 - html_menu procedure 242
 - html_menu_end procedure 242
 - html_nobr procedure 229
 - html_nobr_end procedure 229
 - html_ol procedure 242
 - html_ol_end procedure 243
 - html_on procedure 229
 - html_p procedure 230
 - html_p_end procedure 230
 - html_samp procedure 236
 - html_samp_end procedure 236
 - html_set_body_attributes procedure 231
 - html_set_head_tags procedure 231
 - html_strike procedure 237
 - html_strike_end procedure 237
 - html_sub procedure 237
 - html_sub_end procedure 237
 - html_sup procedure 238
 - html_sup_end procedure 238
 - html_table procedure 245
 - html_table_end procedure 245
 - html_td procedure 246
 - html_td_end procedure 246
 - html_th procedure 246
 - html_th_end procedure 246
 - html_tr procedure 246
 - html_tr_end procedure 246
 - html_ul procedure 243
 - html_ul_end procedure 243
 - hyperbolic cosine (cosh) function 134
 - hyperbolic sine 139
 - hyphens
 - in command names 3
 - in command-line flags 5
 - in commands 4
- I**
- I command-line parameter 297
 - ID flag 10, 250, 258
 - Idir_list flag 10
 - IF command 109, 123
 - and WHILE commands 223
 - nested within a WHILE loop 223
 - nesting 124
 - #IF compiler directive 109, 122
 - #IFDEF compiler directive 109, 122, 125
 - #IFNDEF compiler directive 109, 122, 125
 - IMAGE-SIZE argument
 - DECLARE-IMAGE command 76
 - PRINT-IMAGE command 202
 - images 75
 - declaring 75

- printing 202
- #INCLUDE command 10, 126
- include files
 - nesting 126
 - understanding 126
- INDENTATION argument,
 - DECLARE-TOC command 97
- indenting text 37
- Informix
 - COMMIT command 58
 - ROLLBACK command 206
 - STOP command 215
- INIT-STRING argument,
 - DECLARE-PRINTER command 85, 276
- initcap function 55
- initialization file 277
- INPUT command
 - preventing user input 14
 - prompts 127
 - understanding 126
- INPUT-DATE-EDIT-MASK keyword,
 - ALTER-LOCALE command 26
- INSERT command 127
- instr function 145
- instrb function 146
- INTEGER argument, DECLARE-VARIABLE command 99
- INTEGER data type 127
- integer variables 16
- INTO argument, EXECUTE command 113
- isblank function 146
- isnull function 146
- ITEM-COLOR argument,
 - DECLARE-CHART command 67, 68

J

- joins 161

K

- KEEP flag 10, 12, 95, 250
- KEY argument, LOAD-LOOKUP command 161

L

- labels 119
- LAST-PAGE command 129
- layout

- DEFAULT 77
- reports 76
- LAYOUT argument, DECLARE-REPORT command 95
- LEFT-MARGIN argument
 - DECLARE PRINTER command 265
 - DECLARE-LAYOUT command 79
- LEGEND argument, DECLARE-CHART command 69
- LEGEND-PLACEMENT argument,
 - DECLARE-CHART command 69
- LEGEND-PRESENTATION argument,
 - DECLARE-CHART command 69
- LEGEND-TITLE argument,
 - DECLARE-CHART command 69
- length function 147
- lengthb function 147
- lengthp function 147
- lengtht function 148
- LET command 130
 - datenow function 262
 - edit masks 187
- LEVEL argument, TOC-ENTRY command 217
- LG command-line parameter 298
- LINE-HEIGHT argument,
 - DECLARE-LAYOUT command 77, 81
- LINE-SIZE argument, DECLARE PRINTER command 266
- LINE-WIDTH argument,
 - DECLARE-LAYOUT command 79
- LINEPRINTER 85
- lines
 - breaking in HTML 228
 - drawing 120
 - horizontal 121
 - reserved variable for current 16
 - reserved variable for maximum 18
 - vertical 121
- LINES-INCH argument, DECLARE PRINTER command 266
- lis files 11
- list variables 15, 19
 - accessing 19
 - arguments 19
 - assigning 19
 - defining 19
- literals 19
 - determining value 110
 - displaying 102, 211

- numeric 19
- text 19
- LL{s | d}{c | i} flag 11
- LOAD-LOOKUP command 11, 49, 159, 163
- loading an internal table 160
- LOCAL argument, BEGIN-PROCEDURE command 44
- local procedures 44
- LOCALE keyword, ALTER-LOCALE command 27
- Locale section, pssqr.ini 287
- locales
 - changing parameters 25
 - reserved variable for current 18
 - selecting 25
 - SYSTEM 25
- log base 10 136
- log base e 136
- log function 136
- log messages 11
- log10 function 136
- logical comparison operators 130
- logical expressions 124
- logon, defining parameters 74
- LOOKUP command 160, 163
- lookup tables, searching 163
- LOOPS argument, BEGIN-SELECT command 47
- lower function 148
- LOWERCASE command 163
- lpad function 148
- LPFLAGS "<flags>" command-line parameter 299
- ltrim function 149

M

- marker locations 15
- MATCH argument, PRINT command 189
- mathematical operators 130
- MAX-COLUMNS argument, DECLARE-LAYOUT command 80
- MAX-LINES argument, DECLARE-LAYOUT command 80
- MAXLEN argument, INPUT command 127, 128
- MBTOSBS command 164
- members, returning set 211
- messages
 - database errors 17
 - directing to a file 7
 - disabling display 14
 - numbered 304
 - setting path and name of error message file 15
 - unnumbered 301
- Mfile flag 11
- Microsoft SQL Server
 - BEGIN TRANSACTION command 206
 - ROLLBACK TRANSACTION command 206
 - STOP command 215
- miscellaneous functions
 - ltrim 149
 - range 150
 - replace 150
 - roman 151
 - rpadd 151
 - rtrim 151
- MMA Partners xii
- mod function 136
- MODE argument, SECURITY command 208
- MONEY argument
 - DISPLAY command 103
 - MOVE command 165
 - PRINT command 189
 - SHOW command 212
- MONEY-EDIT-MASK keyword, ALTER-LOCALE command 26, 27
- MONEY-SIGN keyword, ALTER-LOCALE command 26, 27
- MONEY-SIGN-LOCATION keyword, ALTER-LOCALE command 26, 27
- MONEY-SYMBOL command 261, 270, 272
- MONTHS-CASE keyword, ALTER-LOCALE command 27, 28
- MONTHS-FULL keyword, ALTER-LOCALE command 27, 28
- MONTHS-SHORT keyword, ALTER-LOCALE command 27, 28
- MOVE command
 - edit masks 187
 - understanding 164

- MR command-line parameter 298
- multibyte characters 207
- multiple reports 32, 41
- MULTIPLY command 168

N

- NAME argument
 - ALTER-COLOR-MAP command 23
 - BEGIN-FOOTING command 41
 - BEGIN-HEADING command 43
 - CLEAR-ARRAY command 57
 - CREATE-ARRAY command 62
 - CREATE-COLOR-PALETTE command 63
 - LOAD-LOOKUP command 161
- natural log base e raised to x power 135
- navigation bar 14
- NEED argument, NEXT-LISTING command 172
- nesting
 - arguments 132
 - IF command 124
- NEW-PAGE command 169
- NEW-REPORT command 169
- NEXT-COLUMN command 58, 170
- NEXT-LISTING command 171
- NO-ADVANCE argument, NEXT-LISTING command 172
- NO-DUPLICATE argument, DECLARE-CONNECTION command 74
- NO-FORMFEED command 261, 273
- NOLF argument, PRINT-DIRECT command 201
- NOLINE argument
 - DISPLAY command 102, 103
 - SHOW command 212
- NOLIS flag 11, 95, 250
- nondisplay characters 107, 275, 276
- NOP argument, PRINT command 189
- NOPROMPT argument, INPUT command 128
- NORMAL argument, SHOW command 212
- notes xiv
- NOWAIT argument, CALL command 54
- NUMBER argument
 - DISPLAY command 103
 - MOVE command 165
 - PRINT command 190

- SHOW command 212
- number columns 15
- NUMBER data type 127
- NUMBER-EDIT-MASK keyword, ALTER-LOCALE command 26, 27
- numeric edit format characters 181
- numeric edit masks 27
- numeric functions 132, 158
 - absolute value 132
 - arccosine (acos) 132
 - arcsine (asin) 133
 - arctangent (atan) 133
 - ceil 133
 - cosine (cos) 134
 - degrees (deg) 134
 - e10 (10 raised to x power) 135
 - exp (natural log base e raised to x power) 135
 - floor (largest integer) 135
 - hyperbolic cosine (cosh) 134
 - hyperbolic sine (sinh) 139
 - hyperbolic tangent (tanh) 140
 - log base e 136
 - log10 (log base 10) 136
 - mod 136
 - power 137
 - radians (rad) 137
 - round 138
 - sign 138
 - sin 138
 - sine 138
 - square root (sqrt) 139
 - tangent (tan) 139
 - truncate (trunc) 140
- numeric literals 19
- numeric operands 130
- numeric variables 15, 16
- nvl function 149

O

- O[file] flag 11, 250, 258
- ODBC
 - COMMIT command 58
 - ROLLBACK command 206
- OF command-line parameter 298
- olim flag 11
- ON-BREAK argument, PRINT command 190
- ON-ERROR argument
 - BEGIN-EXECUTE command 39

- BEGIN-SELECT command 47
- BEGIN-SQL command 51
- CONNECT command 60
- DIVIDE command 105
- EXECUTE command 113
- OP command-line parameter 298
- OPEN command 172
- operands
 - converting 130
 - understanding 130
- operating system
 - issuing commands 52
 - opening files 172
 - reserved variable for returning 18
- operators, precedence 131
- Oracle 47
 - BEGIN-SQL command, -Cnn 51
 - COMMIT command 58
 - PL/SQL 50
 - ROLLBACK command 206
- ORIENTATION argument
 - DECLARE PRINTER command 265
 - DECLARE-LAYOUT command 77, 79
- OT command-line parameter 297
- output
 - available types 2
 - choosing printer type 12
 - HTML 227
 - layout of files 76
 - overriding default file 10
 - reserved variable for returning file name 18
 - SQR Print 255, 260
 - using the command line 255
 - writing directly to files 201
- OUTPUT argument, EXECUTE command 113

P

- P flag 11, 250, 258
- page buffer 201
- page numbers
 - last 129
 - reserved variable for current 16
- page overflow 169
- #page-count reserved variable 16
- PAGE-DEPTH argument,
 - DECLARE-LAYOUT command 77, 80
- PAGE-NUMBER command 174
- PAGE-SIZE command 261, 274
- pages
 - adding numbers 174
 - new 169
 - setting position 175
 - writing 169
 - writing data at specified position 175
- palettes 66
- PAPER-SIZE argument, DECLARE-LAYOUT command 77, 79, 274
- paragraphs
 - completing 108, 109
 - document 4, 37, 175, 412
 - SELECT 46, 114
 - SQL 49
- PARAMETER_LIST argument,
 - BEGIN-EXECUTE command 39
- PARAMETERS argument,
 - DECLARE-CONNECTION command 74
- PASSWORD argument, DECLARE-CONNECTION command 74
- PB flag 11, 250
- PDF Fonts section, pssqr.ini 292
- PDF Fonts: Exclusion Ranges section,
 - pssqr.ini 294
- PeopleBooks
 - ordering xii
- PeopleCode, typographical
 - conventions xiii
- PeopleSoft application fundamentals xi
- pie chart, printing 200
- PIE-SEGMENT-EXPLODE argument,
 - DECLARE-CHART command 69
- PIE-SEGMENT-PERCENT-DISPLAY argument,
 - DECLARE-CHART command 69
- PIE-SEGMENT-QUANTITY-DISPLAY argument,
 - DECLARE-CHART command 69
- PITCH argument
 - ALTER-PRINTER command 32
 - DECLARE-PRINTER command 87
- PL/SQL 50
- POINT-MARKERS argument,
 - DECLARE-CHART command 68
- POINT-SIZE argument
 - ALTER-PRINTER command 32
 - DECLARE PRINTER command 267
 - DECLARE-PRINTER command 86

- position argument, PRINT-IMAGE
 - command 202
- POSITION command 175
- postscri.str file 179
- POSTSCRIPT 85
- power function 137
- precedence, operators 131
- precision 130
- prerequisites xi
- PRINT ... CODE command 262
- PRINT ... CODE command 275
- PRINT ... CODE-PRINTER
 - command 275
- PRINT command 118, 175
 - encode characters 107
 - format commands 176
- Print dialog box, Windows 260
- PRINT-BAR-CODE command 194
- PRINT-CHART command 65, 197
- PRINT-DIRECT command
 - encode characters 107
 - understanding 201
- PRINT-IMAGE command
 - and DECLARE-IMAGE 75
 - understanding 202
- PRINT-TEXT-BACKGROUND argument
 - GET-COLOR command 117
 - SET-COLOR command 209
- PRINT-TEXT-FOREGROUND argument
 - GET-COLOR command 117
 - SET-COLOR command 209
- printed documentation xii
- PRINTER ... CODE-PRINTER
 - command 262
- PRINTER argument, PRINT-DIRECT
 - command 201
- printer control characters 11
- printer type
 - choosing 12
 - setting 220
- PRINTER.COLOR option 66
- PRINTER-DEINIT command 261, 275
 - PRINTER:EH flag 12
 - PRINTER:EP flag 12
 - PRINTER:HP flag 12
 - PRINTER:HT flag 12
- PRINTER-INIT command 262, 276
 - PRINTER:LP flag 12
 - PRINTER:PD flag 12
 - PRINTER:PS flag 12
- PRINTER-TYPE argument,
 - DECLARE-REPORT command 95
- PRINTER:WP flag 12, 92
- PRINTER:xx flag 12, 251, 259
- printers
 - altering parameters at runtime 32
 - overriding defaults 84
- printing
 - Hebrew 181
 - on Windows 92
- PROCEDURE argument,
 - BEGIN-EXECUTE command 39
- PROCEDURE section 2
- procedures
 - beginning 43
 - calling recursively 44
 - declaring 93
 - global 43
 - invoking 106
 - local 44
 - passing date arguments to 44
 - passing numeric variables to 44
 - passing string arguments to 44
 - running 106
 - stored 49
 - USE-PROCEDURE command 221
- process file, reserved variable for
 - returning 18
- process ID, reserved variable for
 - returning 18
- Processing-Limits section, pssqr.ini 284
- program command-line argument 4
- PROGRAM section 2, 45
- program structure 2
- program.lis file 10
- program.log file 11
- program.spf file 15
- program.sqr file 10
- program.sqt file 12
- programs, samples 409
- prompts, INPUT command 127
- PROPERTIES argument,
 - BEGIN-EXECUTE command 39
- pssqr.exe, command-line options 296
- pssqr.ini
 - for other platforms 277
 - for Windows 277
- pssqr.ini sections
 - Colors 296
 - default settings 278

- Enhanced-HTML 295
- Environment 286
- Fonts 290
- HTML-Images 291
- Locale 287
- PDF Fonts 292
- PDF Fonts: Exclusion Ranges 294
- Processing-Limits 284
- TrueType font 294
- publishing HTML 227
- PUT command
 - rules 203
 - understanding 203

Q

- queries, ending 114
- QUIET argument
 - LOAD-LOOKUP command 161
 - STOP command 215

R

- R command-line parameter 297
- radians (rad) function 137
- random function 158
- range function 150
- READ command 204
- RECORD argument, OPEN command 173
- records
 - reading 204
 - writing to a file 224
- related documentation xii
- relinking SQR 157
- REMOVE argument, SECURITY command 208
- rename function 141
- replace function 150
- reports
 - BEGIN-HEADING command 42
 - closing 169
 - defining 95
 - designing 2
 - displaying output on screen 7
 - layout 76
 - marking sections for security 207
 - multiple 32, 41, 169
 - opening 169
 - output types 2
 - referencing external source files 126

- reserved variable for returning name of output file 18
- samples 20
- switching between 222
- testing 13
- reserved variables 16
 - global versus local 44
 - \$username 60
- RESET-STRING argument, DECLARE-PRINTER command 86
- #return-status reserved variable 16
- RETURN_VALUE argument, LOAD-LOOKUP command 161
- REVERSE argument, SHOW command 212
- rgb argument
 - CREATE-COLOR-PALETTE command 63
 - DECLARE-COLOR-MAP command 73
- RIGHT-MARGIN argument, DECLARE-LAYOUT command 79
- ROLLBACK command 206, 215
 - and COMMIT command 58
- ROLLBACK TRANSACTION command 59
- ROLLBACK TRANSACTION command, Sybase and Microsoft SQL Server 206
- roman function 151
- ROUND argument
 - ADD command 23, 105
 - MULTIPLY command 168
 - SUBTRACT command 217
- round function 138
- ROWCOUNT command, Oracle and Sybase 17
- rows
 - affected by SELECT paragraph 17
 - buffering 6
 - eliminating duplicates from query 47
 - reserved variable for counting 17
 - specifying number to retrieve 47
 - specifying number to retrieve simultaneously 47
- ROWS argument, LOAD-LOOKUP command 161
- RP command-line parameter 297
- rpadd function 151
- RS flag 12, 13

RSV argument, BEGIN-EXECUTE
 command 39
 rtrim function 151
 runtime file
 saving 12
 using 13

S

-S flag 13, 251
 sample programs 409
 sample reports 20
 SBTOMBS command 206
 scaling factor 9
 SCHEMA argument, BEGIN-EXECUTE
 command 39
 screen I/O 211
 searches, using LOAD-LOOKUP 160
 sections, completing 108, 109
 SECURITY command 207
 security IDs 208
 SELECT paragraphs
 beginning 46
 exiting 114
 sequential processing, FOR-
 READING 173
 SET argument, SECURITY
 command 208
 SET-COLOR command 208
 SET-GENERATIONS command 210
 SET-LEVELS command 210
 SET-MEMBERS command 211
 SETUP section 2, 48
 SHADE argument, PRINT
 command 179, 192
 SHOW command
 edit masks 187
 understanding 211
 versus DISPLAY command 102
 sid argument, SECURITY command 208
 sign function 138
 sin function 138
 sine function 138
 single-byte characters 207
 single-byte strings 164
 sinh function 139
 SIZE argument, CREATE-ARRAY
 command 62
 SKIPLINES argument, NEXT-LISTING
 command 172

SORT argument, LOAD-LOOKUP
 command 161
 SOURCE argument
 DECLARE-IMAGE command 76
 PRINT-IMAGE command 202
 source code 2
 source field 164
 source files, including external 126
 spf files 11, 12
 SPF Viewer, invoking 15
 SQL paragraphs 49
 SQL, syntax errors 47
 #sql-count reserved variable 17
 \$sql-error reserved variable 17
 #sql-status reserved variable 17
 SQR
 avoiding older commands 261
 banner 13
 command-line arguments 4
 command-line interface 4
 compiling 122
 data elements 15
 executables 4
 flags 5
 grid 77
 high-level programming capabilities 2
 initialization file 14, 277
 language 1, 2
 page buffer 201
 preventing database sign-in 14
 process file 18
 process ID 18
 program structure 2
 relinking 157
 relinking to CALL 53
 reserved variable for returning process
 file 18
 reserved variable for returning process
 ID 18
 reserved variables 16
 rules for entering commands 4
 sample programs 409
 stopping 215
 syntax conventions 3
 tools 1
 understanding 1, 2
 SQR executable 4
 SQR Execute 1, 4
 flags 247
 running 247

- SQR Print 1, 4, 255
 - command-line flags 256
 - generating output 260
 - Windows Print dialog box 260
- SQR Samples 1
- \$sqr-database reserved variable 17
- {sqr-database} reserved variable 17
- SQR_DB_DATE_FORMAT setting 44, 59
- SQR_DB_DATE_ONLY_FORMAT setting 44, 59
- SQR_DB_TIME_ONLY_FORMAT setting 44, 59
- \$sqr-dbc reserved variable 18
- {sqr-dbc} reserved variable 18
- sqr-encoding reserved variable 18
- {sqr-encoding- console} reserved variable 17
- \$sqr-encoding- database reserved variable 17
- {sqr-encoding- database} reserved variable 17
- \$sqr-encoding- file-input reserved variable 17
- {sqr-encoding- file-input} reserved variable 17
- \$sqr-encoding- file-output reserved variable 17
- {sqr-encoding- file-output} reserved variable 17
- \$sqr-encoding- report-output reserved variable 17
- {sqr-encoding- report-output} reserved variable 17
- {sqr-encoding} reserved variable 18
- \$sqr-encoding- source reserved variable 17
- {sqr-encoding- source} reserved variable 17
- \$sqr-encoding-console reserved variable 17
- sqr-hostname, reserved variable 18
- {sqr-hostname} reserved variable 18
- sqr.ini file 14
 - Default-Settings section of 27
- \$sqr-locale reserved variable 18
- sqr.log file 11
- #sqr-max-columns reserved variable 18
- #sqr-max-lines reserved variable 18
- #sqr-pid reserved variable 18
- \$sqr-platform reserved variable 18
- {sqr-platform} reserved variable 18
- \$sqr-program reserved variable 18
- \$sqr-report reserved variable 18
- \$sqr-ver reserved variable 18
- sqrerr.dat file 15
- SQREXT.MAK 53
- SQRMAKE 53
- SQRP executable 4, 255
- SQRT executable 4, 247
- sqrt function 139
- SQRW executable 4
- SQRWP executable 4, 255
- SQRWT executable 4, 247
- square root 139
- STARTUP-FILE argument
 - DECLARE PRINTER command 267
 - DECLARE-PRINTER command 87
- STATUS argument
 - BEGIN-EXECUTE command 39
 - INPUT command 127, 128
 - INPUT command, values for 127
 - OPEN command 173
 - READ command 205
 - WRITE command 225
- STOP command 215
- stored procedures
 - executing 112
 - preventing creation 14, 47, 51
 - understanding 49
- STRING command 215
- string functions 157
 - extract 114
 - instr 145
 - instrb 146
 - length 147
 - lengthb 147
 - lengthp 147
 - lengtht 148
 - lower 148
 - lowercase 163
 - lpad 148
 - ltrim 149
 - substr (substring) 152
 - substrb (substring) 153
 - substrp 153
 - substrt 154
 - transform 156
 - translate 155
 - unicode 156

- UNSTRING 218
- upper 157
- UPPERCASE 218
- string operands 130
- string values 141
- string variables, converting to
 - uppercase 218
- strings
 - converting double-byte to
 - single-byte 164
 - copying 115
 - copying into text variables 218
 - double-byte 164
 - finding character sequences within 116
 - single-byte 164
- strtodate function 152, 186
- Structured Query Report, *See* SQR
- structuring a program 2
- SUB-TITLE argument, DECLARE-CHART command 68
- subroutines
 - calling 52, 54
 - writing 52
- substitution variables
 - ASK command 36
 - #DEFINE command 100
 - #IF compiler directive 122
 - #IFDEF compiler directive 125
 - #IFNDEF compiler directive 125
- substr (substring) function 152
- substrb function 153
- substrings 114, 218
- substrp function 153
- substrt function 154
- SUBTRACT command 216
- suggestions, submitting xv
- Sybase
 - BEGIN TRANSACTION
 - command 206
 - ROLLBACK TRANSACTION
 - command 206
 - STOP command 215
 - USE command 219
- SYBASE CT-Lib 47
- SYMBOL-SET argument
 - ALTER-PRINTER command 32
 - DECLARE PRINTER command 267
 - DECLARE-PRINTER command 86
- syntax conventions 3
- SYSTEM argument

- CALL command 55
- SYSTEM argument, CALL command 54
- SYSTEM locale 25

T

- T{B} flag 13
- T{B|Z|BZ|ZB} flag 252
- T{Z} flag 13
- TABLE argument, LOAD-LOOKUP command 161
- table of contents 96
 - See Also* DECLARE-TOC command
 - creating entries 217
 - defining 96
 - footing for 41
 - heading for 43
 - sharing 96
 - suppressing 14
- tables
 - loading internal 160
- tabular reports, NEXT-LISTING command 171
- tan (tangent) function 139
- tanh function 140
- temporary stored procedures 14
- terms 435
- testing
 - error conditions 206
 - STOP command 215
- TEXT argument
 - DECLARE-VARIABLE command 99
 - PRINT-BAR-CODE command 196
 - TOC-ENTRY command 217
- text edit format characters 180
- text literals 19
- text variables 15
 - concatenating 215
 - copying strings into 218
- THOUSAND-SEPARATOR keyword, ALTER-LOCALE command 26, 27
- TIME column type 180
- TIME-SEPARATOR keyword, ALTER-LOCALE command 26, 28
- times
 - displaying 102
 - reserved variable for current 16
- TITLE argument, DECLARE-CHART command 68
- Tnn flag 13, 251

- to_char function 154
- to_multi_byte function 154
- to_number function 155
- to_single_byte function 155
- TOC argument, DECLARE-REPORT command 95
- TOC-ENTRY command 217
- TOP-MARGIN argument
 - DECLARE PRINTER command 265
 - DECLARE-LAYOUT command 79
- TR command-line parameter 298
- trailing blanks
 - preserving 11, 14
 - trimming 13
- trailing form feeds 14
- trailing zeros 13
- transcendental functions 140
- transform function 156
- translate function 155
- TrueType Font section, pssqr.ini 294
- trunc (truncate) function 140
- TYPE argument
 - DECLARE PRINTER command 265
 - DECLARE-CHART command 69
 - DECLARE-IMAGE command 76
 - DECLARE-PRINTER command 85
 - INPUT command 127, 128
 - PRINT-BAR-CODE command 196
 - PRINT-IMAGE command 202
- typographical conventions xiii

U

- UCALL function
 - arguments 53
 - avoiding database calls 52
- UCALL.C source file 53
- UFUNC.C 157
- UNDERLINE argument
 - PRINT command 192
 - SHOW command 212
- underscores
 - in procedure names 3
 - in variable names 3
- unicode function 156
- UNSTRING command 217
- UPC-A bar code 196
- UPDATE command 127
- upper function 157
- UPPERCASE command 218

- USE command 49, 219
- USE-COLUMN command 58, 219
- USE-PRINTER-TYPE command 220
- USE-PROCEDURE command 220
- USE-REPORT command 222
- USER argument, DECLARE-CONNECTION command 74
- user input
 - INPUT command 126
 - preventing 14
- \$username reserved variable 18, 60
- username, database 18

V

- VALUE argument, ALTER-COLOR-MAP command 23
- value determination 110
- variables 15
 - assigning values of expressions to 130
 - bind 47
 - converting to uppercase 218
 - date 15
 - decimal 16, 22
 - declaring 98
 - determining value 110
 - displaying 102, 211
 - dynamic query 47
 - float 16, 22
 - global 16
 - initialization 16
 - integer 16
 - list 15, 19
 - list variable arguments 19
 - local 16
 - naming 15
 - numeric 15, 16
 - reference 36
 - reserved 16
 - rules 15
 - string 115
 - substitution 36, 100, 125
 - text 15
- VARY argument, OPEN command 173
- VARY file type 173
- VERT-LINE argument, GRAPHIC command 121
- visual cues xiv
- Vserver flag 13, 252

W

WAIT argument, CALL command 54
 warnings xiv
 WHEN argument, EVALUATE command 111
 WHEN-OTHER argument, EVALUATE command 111
 WHERE argument, LOAD-LOOKUP command 161
 WHILE ... END-WHILE loop 52
 WHILE command 109
 exiting from with BREAK 52
 understanding 223
 WHILE loop 223
 Windows
 generating output 260
 selecting a printer 260
 WITH RECOMPILE argument, EXECUTE command 113
 WRAP argument, PRINT command 192
 wrapdepth function 157
 WRITE command 224

X

X-AXIS-GRID or Y-AXIS-GRID
 argument, DECLARE-CHART command 71
 X-AXIS-LABEL or Y-AXIS-LABEL
 argument, DECLARE-CHART command 69
 X-AXIS-MAJOR INCREMENT or Y-AXIS-MAJOR INCREMENT
 argument, DECLARE-CHART command 71
 X-AXIS-MAJOR-TICK- MARKS
 argument, DECLARE-CHART command 70
 X-AXIS-MAX-VALUE argument,
 DECLARE-CHART command 70
 X-AXIS-MIN-VALUE argument,
 DECLARE-CHART command 70
 X-AXIS-MINOR INCREMENT or Y-AXIS-MINOR INCREMENT
 argument, DECLARE-CHART command 71
 X-AXIS-MINOR-TICK- MARKS
 argument, DECLARE-CHART command 70

X-AXIS-SCALE or Y-AXIS-SCALE
 argument, DECLARE-CHART command 70
 X-AXIS-TICK-MARK- PLACEMENT or Y-AXIS-TICK-MARK- PLACEMENT
 argument, DECLARE-CHART command 71
 -XB flag 13, 252, 259
 -XC argument, EXECUTE command 113
 -XC flag 13
 -XCB flag 13, 252
 -XI flag 14
 -XL flag 14, 252
 -XLFF flag 14
 -XMB flag 14, 252
 -XNAV flag 14, 252, 259
 -XP argument
 BEGIN-SELECT command 47
 BEGIN-SQL command 51
 -XP flag 14, 252
 -XTB flag 14, 253, 259
 -XTOC flag 14, 253, 259

Y

Y-AXIS-MAJOR-TICK- MARKS
 argument, DECLARE-CHART command 70
 Y-AXIS-MAX-VALUE argument,
 DECLARE-CHART command 70
 Y-AXIS-MIN-VALUE argument,
 DECLARE-CHART command 70
 Y-AXIS-MINOR-TICK- MARKS
 argument, DECLARE-CHART command 71

Z

zeros, trailing 13
 -ZIF{file} flag 14, 253, 259
 ZIP+4 Postnet 196
 -ZIV flag 15, 253
 -ZMF{file} flag 15, 253, 259