

Oracle® Retail Merchandising System
Installation Guide
Release 12.0.10

April 2009

Copyright © 2009, Oracle. All rights reserved.

Primary Author: Paul Kehler

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Value-Added Reseller (VAR) Language

Oracle Retail VAR Applications

The following restrictions and provisions only apply to the programs referred to in this section and licensed to you. You acknowledge that the programs may contain third party software (VAR applications) licensed to Oracle. Depending upon your product and its version number, the VAR applications may include:

- (i) the software component known as **ACUMATE** developed and licensed by Lucent Technologies Inc. of Murray Hill, New Jersey, to Oracle and imbedded in the Oracle Retail Predictive Application Server – Enterprise Engine, Oracle Retail Category Management, Oracle Retail Item Planning, Oracle Retail Merchandise Financial Planning, Oracle Retail Advanced Inventory Planning, Oracle Retail Demand Forecasting, Oracle Retail Regular Price Optimization, Oracle Retail Size Profile Optimization, Oracle Retail Replenishment Optimization applications.
- (ii) the **MicroStrategy** Components developed and licensed by MicroStrategy Services Corporation (MicroStrategy) of McLean, Virginia to Oracle and imbedded in the MicroStrategy for Oracle Retail Data Warehouse and MicroStrategy for Oracle Retail Planning & Optimization applications.
- (iii) the **SeeBeyond** component developed and licensed by Sun Microsystems, Inc. (Sun) of Santa Clara, California, to Oracle and imbedded in the Oracle Retail Integration Bus application.
- (iv) the **Wavelink** component developed and licensed by Wavelink Corporation (Wavelink) of Kirkland, Washington, to Oracle and imbedded in Oracle Retail Mobile Store Inventory Management.
- (v) the software component known as **Crystal Enterprise Professional and/or Crystal Reports Professional** licensed by SAP and imbedded in Oracle Retail Store Inventory Management.
- (vi) the software component known as **Access Via™** licensed by Access Via of Seattle, Washington, and imbedded in Oracle Retail Signs and Oracle Retail Labels and Tags.
- (vii) the software component known as **Adobe Flex™** licensed by Adobe Systems Incorporated of San Jose, California, and imbedded in Oracle Retail Promotion Planning & Optimization application.
- (viii) the software component known as **Style Report™** developed and licensed by InetSoft Technology Corp. of Piscataway, New Jersey, to Oracle and imbedded in the Oracle Retail Value Chain Collaboration application.
- (ix) the software component known as **DataBeacon™** developed and licensed by Cognos Incorporated of Ottawa, Ontario, Canada, to Oracle and imbedded in the Oracle Retail Value Chain Collaboration application.

You acknowledge and confirm that Oracle grants you use of only the object code of the VAR Applications. Oracle will not deliver source code to the VAR Applications to you. Notwithstanding any other term or condition of the agreement and this ordering document, you shall not cause or permit alteration of any VAR Applications. For purposes of this section, “alteration” refers to all alterations, translations, upgrades, enhancements, customizations or modifications of all or any portion of the VAR Applications including all reconfigurations, reassembly or reverse assembly, re-engineering or reverse engineering and recompilations or reverse compilations of the VAR Applications or any derivatives of the VAR Applications. You acknowledge that it shall be a breach of the agreement to utilize the relationship, and/or confidential information of the VAR Applications for purposes of competitive discovery.

The VAR Applications contain trade secrets of Oracle and Oracle’s licensors and Customer shall not attempt, cause, or permit the alteration, decompilation, reverse engineering, disassembly or other reduction of the VAR Applications to a human perceivable form. Oracle reserves the right to replace, with functional equivalent software, any of the VAR Applications in future releases of the applicable program.

Contents

Preface	vii
Audience	vii
Related Documents.....	vii
Customer Support.....	Error! Bookmark not defined.
Review Patch Documentation.....	Error! Bookmark not defined.
Oracle Retail Documentation on the Oracle Technology Network.....	Error! Bookmark not defined.
Conventions.....	Error! Bookmark not defined.
1 Preinstallation Tasks.....	1
Check Database Server Requirements	1
Check Application Server Requirements.....	2
RMS on Oracle Enterprise Linux Specific Requirements	2
Check Web Browser and Client Requirements.....	3
Supported Oracle Retail Products	3
Supported Oracle Retail Integration Technologies	3
Supported Oracle Applications.....	3
2 RAC and Clustering.....	5
3 Database Installation Tasks.....	7
Mount CD-ROM on the Database Server	7
Alter Pricing Objects.....	7
Alter Pricing types	7
Alter Pricing DDL.....	7
Alter Pricing Objects.....	8
Alter RIB Objects.....	8
Alter RIB Objects.....	8
Alter RMS Objects.....	8
Alter RMS Tables	8
Alter RMS Database Objects.....	8
Validate all Invalid Objects.....	8
Update Data for RMS	9
Insert Secondary Language Data.....	9
Insert Primary Language Data.....	Error! Bookmark not defined.
Update RETL for RDW	9
Update RETL for RPAS.....	Error! Bookmark not defined.
Compile RMS Batch Libraries and Programs.....	10
Set Environment Variables	10
Compile Batch Libraries.....	11
Compile Batch Source Code	11
4 Application Server Installation Tasks.....	13
Mount CD-ROM on the Database Server	13

Set Environment Variables	13
RMS Toolset Installation	14
RMS Forms Installation.....	15
Verify and Update Helpfile Installation	Error! Bookmark not defined.

Preface

Oracle Retail Installation Guides contain the requirements and procedures that are necessary for the retailer to install Oracle Retail products.

Audience

This Installation Guide is written for the following audiences:

- Database administrators (DBA)
- System analysts and designers
- Integrators and implementation staff

Related Documents

For more information, see the following documents in the Oracle Retail Merchandising System Release 12.0.10 documentation set:

- *Oracle Retail Merchandising System Release Notes*
- *Oracle Retail Merchandising System Operations Guide – Volume 1*
- *Oracle Retail Merchandising System Operations Guide – Volume 2*
- *Oracle Retail Merchandising System Data Model*
- *Oracle Retail Merchandising Batch Schedule*

Customer Support

To contact Oracle Customer Support, access My Oracle Support at the following URL:
<https://metalink.oracle.com>

When contacting Customer Support, please provide the following:

- Product version and program/module name
- Functional and technical description of the problem (include business impact)
- Detailed step-by-step instructions to re-create
- Exact error message received
- Screen shots of each step you take

Review Patch Documentation

If you are installing the application for the first time, you install either a base release (for example, 13.0) or a later patch release (for example, 13.0.2). If you are installing a software version other than the base release, be sure to read the documentation for each patch release (since the base release) before you begin installation. Patch documentation can contain critical information related to the base release and code changes that have been made since the base release.

Oracle Retail Documentation on the Oracle Technology Network

In addition to being packaged with each product release (on the base or patch level), all Oracle Retail documentation is available on the following Web site (with the exception of the Data Model which is only available with the release packaged code):

http://www.oracle.com/technology/documentation/oracle_retail.html

Documentation should be available on this Web site within a month after a product release. Note that documentation is always available with the packaged code on the release date.

Conventions

Navigate: This is a navigate statement. It tells you how to get to the start of the procedure and ends with a screen shot of the starting point and the statement “the Window Name window opens.”

Note: This is a note. It is used to call out information that is important, but not necessarily part of the procedure.

This is a code sample
It is used to display examples of code

A hyperlink appears like this.

Preinstallation Tasks

Check Database Server Requirements

General Requirements for a database server running RMS include:

Supported on:	Versions Supported:
Database Server OS	<p>OS certified with Oracle Database 10g Enterprise Edition. Options are:</p> <ul style="list-style-type: none"> ▪ AIX5.3 ▪ Solaris 10 (SPARC) ▪ HP-UX 11.23 (PA-RISC) ▪ Oracle Enterprise Linux 4 Update 4 (OEL 4.4) for x86-64 (see the RMS on Oracle Enterprise Linux Specific Requirements table below)
Database Server	<p>Oracle Database 10g Release 2 Enterprise Edition (minimum 10.2.0.4.0 patchset required) with the following patches and components:</p> <p>Patches:</p> <ul style="list-style-type: none"> ▪ AIX Only 6154596 - When trying to compile Proc*C program it fails on AIX5 <p>Components:</p> <ul style="list-style-type: none"> ▪ Oracle Database 10g ▪ Oracle Partitioning ▪ Oracle Net Services ▪ Oracle Call Interface (OCI) ▪ Oracle Programmer ▪ Oracle XML Development Kit <p>ANSI compliant C compiler (certified with OS and database version)</p> <p>Perl compiler 5.0 or later</p> <p>x-Windows interface</p>

Check Application Server Requirements

General requirements for an application server capable of running RMS include:

Supported on:	Versions Supported:
Application Server OS	OS certified with Oracle Application Server 10g version 10.1.2.2. Options are: <ul style="list-style-type: none"> ▪ AIX5.3 ▪ Solaris 10 (SPARC) ▪ HP-UX 11.23 (PA-RISC) ▪ Oracle Enterprise Linux 4 Update 4 (OEL 4.4) for x86-64 (see the RMS on Oracle Enterprise Linux Specific Requirements table below)
Application Server	Oracle Application Server Forms and Reports 10g version 10.1.2.2 Patches: <ul style="list-style-type: none"> ▪ 5123798 ERROR WHEN PASSING COMPOSITE PARAMETERS TO SP FROM 64BIT CLIENT (HP-UX PA-RISC 11.23)

RMS on Oracle Enterprise Linux Specific Requirements

Supported on:	Versions Supported:
Database Server OS	Oracle Enterprise Linux 4 Update 4 (OEL 4.4) for x86-64 Minimum kernel version kernel-smp-2.6.9-42.0.0.1.EL.x86_64
Database Server	Oracle Database 10g Release 2 Enterprise Edition for Linux x86-64 Minimum 10.2.0.3 patchset and the following patches: <ul style="list-style-type: none"> ▪ 5397953 (ORA-07445: [KKPAPITGETALL()+2152] [SIGSEGV] [ADDRESS NOT MAPPED TO OBJECT])
Oracle Application Server Application Server OS	Oracle Application Server 10g Release 2 (10.1.2.2) for Linux x86 Oracle Enterprise Linux 4 Update 4 (OEL 4.4) for x86-64 Minimum kernel version kernel-smp-2.6.9-42.0.0.1.EL.x86_64
Configuration requirement	Database server and application server should be configured with the "No RIB" option.

Check Web Browser and Client Requirements

General requirements for client running RMS include:

Product	Version
JRE Plug-in	Sun JRE Plug-in 1.4.1+
Operating System	Windows 2000 or XP
Processor	Pentium processor
Display resolution	1024x768 resolution
PC Configuration	minimum 256 MB RAM, 450 MHz
Internet Explorer	5.5, 6.0 and higher

Supported Oracle Retail Products

Product	Version
Oracle Retail Price Management (RPM)	12.0.10
Oracle Retail Allocation	12.0.10
Oracle Retail Invoice Matching (ReIM)	12.0.10
Oracle Retail Store Inventory Management (SIM)	12.0.10
Oracle Retail Warehouse Management System (RWMS)	12.0.10
Oracle Retail Data Warehouse (RDW)	12.0.10
Oracle Retail Strategic Store Solutions (ORSSS)	12.0.9
Oracle Retail Demand Forecasting (RDF)	12.1.3
Oracle Retail Grade	12.1.3
Oracle Retail Predictive Applications Server (RPAS)	12.1.3

Supported Oracle Retail Integration Technologies

Integration Technology	Version
Oracle Retail Extract, Transform and Load (RETL)	12.0.9
Oracle Retail Integration Bus (RIB)	12.0.9
Oracle Retail Service Layer (RSL)	12.0.9

Supported Oracle Applications

Requirement	Version
Oracle E-Business Suite	11.5.10 or 12.0.2

RAC and Clustering

Real Application Cluster RDBMS and Oracle Application Server Clustering for Oracle Retail Merchandising System has been validated to run only on Linux:

The Oracle Retail products have been validated against a 10.2.0.3 RAC database. When using a RAC database, all JDBC connections should be configured to use OCI connections rather than THIN connections. It is suggested that when using OCI connections, the Oracle Retail products database be configured in the tnsnames.ora file used by the Oracle Application Server installations.

Clustering for Oracle Application Server 10.1.3 is managed as an Active-Active cluster accessed through a hardware Load Balancer. It is suggested that a VirtualHost be added to the OAS 10.1.3 reflecting the Virtual Server Name configured in the load balancer. It is also suggested that the OC4J select method be configured to prefer the use of local OC4J instances. The Oracle Retail products are currently not validated to be distributable at the application level in an OAS 10.1.3 cluster.

Clustering for Oracle Application Server 10.1.2.2 is managed as an Active-Active cluster accessed through a hardware Load Balancer. It is suggested that the Web Cache installation included with OAS 10.1.2.2 be configured to reflect all application server Mid-Tier installations. Validation has been completed utilizing a RAC 10.2.0.3 Oracle Internet Directory database with the OAS 10.1.2.2 cluster.

References for Configuration:

- Oracle® Application Server High Availability Guide 10g Release 3 (10.1.3) Part Number B15977-02
- Oracle® Application Server High Availability Guide 10g Release 2 (10.1.2) Part Number B14003-05
- Oracle® Database Oracle Clusterware and Oracle Real Application Clusters Administration and Deployment Guide 10g Release 2 (10.2) Part Number B14197-03

Database Installation Tasks

Before you apply the RMS 12.0.10 patch:

- Make a backup of all your objects and database schema.
- Check that RMS 12.0.9 is installed.
- Review the enclosed RMS 12.0.10 Patch Release Notes (rms-12010-rn.pdf).
- Review each of the enclosed defect documents.

Before copying over any files:

- Note whether customizations have been made to the module. If so, then the customizations must be reapplied over the new version of the module (or the fix may need to be applied to the custom version of the code).
- Copy the original files to a different directory before copying over them in case they need to be referred to at a later date.

Note: These instructions refer to RMS12DEV as the Oracle owning schema.

Mount CD-ROM on the Database Server

1. Copy the rms12010dbpatch.zip file from the CD /dbserverunix directory to a newly created staging directory on your UNIX server.
2. Unzip the file by entering:

```
unzip rms12010dbpatch.zip
```

Alter Pricing Objects

Alter Pricing types

1. Change directories to STAGING_AREA/pricing/types.
2. Log in to SQL*Plus as RMS12DEV and run the following command:

```
SQL> @pricing12010types.sql
```
3. Check the log file pricing12010types.log for any errors.

Alter Pricing DDL

1. Change directories to STAGING_AREA/pricing/dbcs.
2. Log in to SQL*Plus as RMS12DEV and run the following command:

```
SQL> @pricing12010dbcs.sql
```
3. Check the log file pricing12010dbcs.log for any errors.

Alter Pricing Objects

1. Change directories to STAGING_AREA/pricing/db_objects.
2. Log in to SQL*Plus as RMS12DEV and run the following command:
SQL> @pricing12010rms.sql
3. Check the log file pricing12010rms.log for any errors noting that ORA-04043 errors are to be ignored.

Alter RIB Objects

Alter RIB Objects

1. Change directories to STAGING_AREA/rib_objects/db_objects.
2. Log in to SQL*Plus as RMS12DEV and run the following command:
SQL> @patch12010rib.sql
3. Check the log file patch12010rib.log for any errors.

Alter RMS Objects

Alter RMS Types

1. Change directories to STAGING_AREA/types.
2. Log in to SQL*Plus as RMS12DEV and run the following command:
SQL> @patch12010types.sql
3. Check the log file patch12010types.log for any errors.

Alter RMS Tables

1. Change directories to STAGING_AREA/dbcs.
2. Log in to SQL*Plus as RMS12DEV and run the following command:
SQL> @patch12010dbcs.sql
3. Check the log file patch12010dbcs.log for any errors.

Alter RMS Database Objects

1. Change directories to STAGING_AREA/db_objects.
2. Log in to SQL*Plus as RMS12DEV and run the following command:
SQL> @patch12010rms.sql
3. Check the log file patch12010rms.log for any errors.

Validate all Invalid Objects

Note: Deadlocked objects may appear when running this script. This is expected. Run the script until no invalid objects remain.

1. Change directories to STAGING_AREA/utility.
2. Log in to SQL*Plus as RMS12DEV and run the following command:
SQL> @inv_obj_comp.sql
3. This script may need to be run more than once.

Update Data for RMS

Note: Ensure that you have your NLS_LANG set to UTF-8.
For example AMERICAN_AMERICA.UTF8

1. Change directories to STAGING_AREA/data.
2. Log in to SQL*Plus as RMS12DEV and run the following command:
SQL> @patch12010ctl.sql
3. Check the log file patch12010ctl.log for any errors.

Insert Language Data

Note: These scripts are only for customers who wish to have a primary language of English and a secondary language of any combination of the following: German, Spanish, French, Italian, Korean, Russian, Brazilian Portuguese, Japanese, Simplified Chinese or Traditional Chinese. The scripts are UTF-8 encoded. We recommend installing them into a database that has been set to UTF-8.

1. Change directories to INSTALL_DIR/data/<lang>.
<lang> is the country code for the language you wish to install.
2. Set the SQL*Plus session so that the encoding component of the NLS_LANG is UTF8.
For example, AMERICAN_AMERICA.UTF8
3. Log in to SQL*Plus as RMS12DEV and run the following command:
SQL> @ patch12010ctl_<lang>.sql
4. Check the log file patch12010ctl_<lang>.log for any errors.
 - <lang> is the country code for the language you wish to install.
 - de – German
 - es – Spanish
 - fr – French
 - it - Italian
 - ja – Japanese
 - ko – Korean
 - ptb – Brazilian Portuguese
 - ru - Russian
 - zhs – Simplified Chinese
 - zht – Traditional Chinese

Update RETL for RDW

Note: These steps only need to be done if you are using RDW.

1. Change directories to STAGING_AREA/repl4RDW/rfx/src.
2. Copy all the files from this directory to INSTALL_DIR/repl/rfx/src.
cp -R * INSTALL_DIR/repl/rfx/src

Compile RMS Batch Libraries and Programs

Note: Warning messages may appear during the compilation of the batch. These warnings can be ignored if the batch executables are successfully generated.

Set Environment Variables

1. Make sure the following variables are set:

Note: INSTALL_DIR is the location where RMS 12 was installed.

Make sure the path for make, makedepend, and the compiler are in \$PATH environment variable.

- MMHOME=INSTALL_DIR/rms
- MMUSER=RMS Schema Owner
- PASSWORD=RMS Schema Owner Password
- ORACLE_HOME=Location of Oracle install
- ORACLE_SID=The Oracle Sid for the RMS database

AIX:

- LIBPATH=\$ORACLE_HOME/lib:\$MMHOME/oracle/lib/bin:\$LDPATH
- OBJECT_MODE=64
- LINK_CNTRL=L_PTHREADS_D7

HP:

- SHLIB_PATH=\$ORACLE_HOME/lib:\$MMHOME/oracle/lib/bin:
- \$SH_LIBPATH

Solaris:

- LD_LIBRARY_PATH=\$ORACLE_HOME/lib:
\$MMHOME/oracle/lib/bin:\$LD_LIBRARY_PATH

Oracle Enterprise Linux:

- LD_LIBRARY_PATH=\$ORACLE_HOME/lib:
\$MMHOME/oracle/lib/bin:\$LD_LIBRARY_PATH

Compile Batch Libraries

1. Change directories to `INSTALL_DIR/rms/oracle/lib/src`.
2. Create library dependencies.
 - a. For UNIX, run the following command:


```
make -f retek.mk depend 2>&1 | tee libdpnd.log
```
 - b. For Oracle Enterprise Linux run the following command:


```
make -f retek.mk -r depend 2>&1 | tee libdpnd.log
```
 - c. Check the `libdpnd.log` file for errors.
3. Create the batch libraries.
 - a. For UNIX, run the following command:


```
make -f retek.mk retek rms resa 2>&1 | tee libretek.log
```
 - b. For Oracle Enterprise Linux run the following command:


```
make -f retek.mk -r retek rms resa 2>&1 | tee libretek.log
```
 - c. Check the `libretek.log` file for errors.
4. Install the batch libraries.


```
make -f retek.mk install
```

The batch libraries should now be in `INSTALL_DIR/rms/oracle/lib/bin`.

Compile Batch Source Code

1. Copy the files from `STAGING_AREA/batch/proc/src` to `INSTALL_DIR/rms/oracle/proc/src`.
2. Copy the files from `STAGING_AREA/batch/proc/bin` to `INSTALL_DIR/rms/oracle/proc/bin`.
 - Make sure all ksh and sql files from `INSTALL_DIR/rms/oracle/proc/src` are in `INSTALL_DIR/rms/oracle/proc/bin`
3. Change directories to `INSTALL_DIR/rms/oracle/proc/src`.
4. Create dependencies.
 - a. For UNIX, run the following command:


```
make -f mts.mk rms-depend recs-depend rtm-depend resa-depend 2>&1 | tee srcdpnd.log
```
 - b. For Oracle Enterprise Linux run the following command:


```
make -f mts.mk -r rms-depend recs-depend rtm-depend resa-depend 2>&1 | tee srcdpnd.log
```
 - c. Check the `srcdpnd.log` file for errors.
5. Create batch programs.
 - a. For UNIX, run the following commands in the order stated.


```
make -f rms.mk PRODUCT_PROCFLAGS=dynamic=ansi ditinsrt
make -f mts.mk rms-ALL recs-ALL resa-ALL rtm-ALL 2>&1 | tee srcall.log
```
 - b. For Oracle Enterprise Linux run the following commands:


```
make -f rms.mk -r PRODUCT_PROCFLAGS=dynamic=ansi ditinsrt
make -f mts.mk -r rms-ALL recs-ALL resa-ALL rtm-ALL 2>&1 | tee srcall.log
```
 - c. Check the `srcall.log` file for errors.
6. Install the batch programs.


```
make -f mts.mk rms-install recs-install resa-install rtm-install
```

The batch programs should now be in `INSTALL_DIR/rms/oracle/proc/bin`.

Application Server Installation Tasks

Mount CD-ROM on the Database Server

1. Copy the rms12010appatch.zip file from the CD /appserverunix directory to a newly created staging directory on your UNIX server.
2. Unzip the file by entering:

```
unzip rms12010appatch.zip
```

Set Environment Variables

Note: ORACLE_HOME is the location where Oracle Application Server 10g (10.1.2.0.2) has been installed

1. Set the DISPLAY variable to the IP address plus ":0.0" (ie: 10.1.1.1:0.0) of the application server.
2. Set the following variables:

Note: ORACLE_HOME is the location where Oracle Application Server 10g (10.1.2.0.2) has been installed

- **All OS Platforms**

- PATH=\$ORACLE_HOME/bin:\$ORACLE_HOME/opmn/bin:\$ORACLE_HOME/dcm/bin:INSTALL_DIR/forms10gr2_scripts:\$PATH
- CLASSPATH=\$ORACLE_HOME/jlib/importer:\$ORACLE_HOME/jlib/debugger.jar:\$ORACLE_HOME/jlib/utj.jar:\$ORACLE_HOME/jlib/ewt3.jar:\$ORACLE_HOME/jlib/share.jar:\$ORACLE_HOME/jlib/dfc.jar:\$ORACLE_HOME/jlib/help4.jar:\$ORACLE_HOME/jlib/oracle_ice.jar:\$ORACLE_HOME/jlib/jewt4.jar
- FORMS_BUILDER_CLASSPATH=\$CLASSPATH
- FORMS_PATH=INSTALL_DIR/toolset/bin:INSTALL_DIR/rms/forms/bin:\$ORACLE_HOME/forms
- REPORTS_PATH=INSTALL_DIR/rms/reports/bin:\$ORACLE_HOME/forms
- TK_UNKNOWN==\$ORACLE_HOME/guicommon/tk/admin
- UP=<RMS schema owner>/<RMS schema password>@<RMS database>

Note: Verify that TNS is set up correctly by using the UP variable to successfully log in to the RMS 12 schema.

Example: /u00/oracle> sqlplus \$UP

- **Solaris**
 - LD_LIBRARY_PATH=\$ORACLE_HOME/lib:\$ORACLE_HOME/jdk/jre/lib/sparc:\$ORACLE_HOME/jdk/jre/lib/sparc/native_threads
- **HP-UX**
 - SHLIB_PATH=\$ORACLE_HOME/lib32:\$ORACLE_HOME/lib:\$ORACLE_HOME/jdk/jre/lib/PA_RISC:\$ORACLE_HOME/jdk/jre/lib/PA_RISC/server
- **AIX**
 - LD_LIBRARY_PATH=\$ORACLE_HOME/lib:\$ORACLE_HOME/lib32:\$ORACLE_HOME/jdk/jre/lib
 - LIBPATH=\$LD_LIBRARY_PATH
- **Oracle Enterprise Linux**
 - LD_LIBRARY_PATH=\$ORACLE_HOME/lib:\$ORACLE_HOME/lib32:\$ORACLE_HOME/jdk/jre/lib

RMS Toolset Installation

1. Copy all libraries (.pll files) in the INSTALL_DIR/toolset/src directory to the INSTALL_DIR/toolset/bin directory.
2. Change directories to INSTALL_DIR/toolset/bin.
3. Run pll2plx10gr2_toolset to compile all Toolset .pll's.

Note: If the pll2plx10gr2_toolset script is not used and the libraries are compiled individually, then they must be compiled in the following order (which is noted in the pll2plx10gr2_toolset script):

- message45.pll
- ariiflib.pll
- stand45.pll
- calend45.pll
- find45.pll
- item45.pll
- tools45.pll
- mblock45.pll
- mview45.pll
- nav45.pll
- work45.pll
- itnumtype.pll
- hierfilter.pll
- rmslib.pll

4. Check to make sure that each .pll file has a corresponding .plx (to ensure that all .pll's compiled successfully).
5. Remove all newly created .plx files.
6. Copy all forms (*.fmb files) in the INSTALL_DIR/toolset/src directory to the INSTALL_DIR/toolset/bin directory.
7. Run fmb2fmx10gr2_fm (in INSTALL_DIR/toolset/bin) to compile the Toolset reference forms.
8. Remove all newly created fm_*.fmx files (reference forms should not have executable files).
9. Run fmb2fmx10gr2 (in INSTALL_DIR/toolset/bin) to generate Toolset runtime forms – .fmx's.
10. Check to make sure that each non-reference form (.fmb file) has a corresponding .fmx file.

Note: Disregard fm_*.fmx files should they be created. These files should be removed. They should NOT exist in the INSTALL_DIR/toolset/bin directory.

11. Remove all non-reference forms from INSTALL_DIR/toolset/bin; the following syntax leaves all reference forms (fm_*.fmb) in the bin directory, while removing all other forms:

```
> for PROG in `ls *.fmb | grep -v fm_`
> do PROGNAME=`echo $PROG`
> rm $PROGNAME
> done
```

12. Copy all menus (*.mmb files) in the INSTALL_DIR/toolset/src directory to the INSTALL_DIR/toolset/bin directory.
13. Run mmb2mmx10gr2 (in INSTALL_DIR/toolset/bin) to generate Toolset runtime menus – .mmx's.
14. Check to make sure that each .mmb file has a corresponding .mmx file.

Note: .err files may be created by the compilation scripts above. These files are logs of the compilation process and can be removed.

15. Remove all .mmb files from INSTALL_DIR/toolset/bin.

RMS Forms Installation

1. Copy all the files from STAGING_AREA/forms/src to INSTALL_DIR/rms/forms/src.
2. Copy all libraries (.pll files) in the INSTALL_DIR/rms/forms/src directory to the directories to the INSTALL_DIR/rms/forms/bin directory.
3. Change directories to INSTALL_DIR/rms/forms/bin.
4. Run pll2plx10gr2_forms to compile all RMS .pll's.
5. Check to make sure that each .pll file has a corresponding .plx (to ensure that all .pll's compiled successfully). Remove all newly created .plx files.
6. Copy all forms (*.fmb files) in the INSTALL_DIR/rms/forms/src directory to the INSTALL_DIR/rms/forms/bin directory.
7. Run fmb2fmx10gr2_fm (in INSTALL_DIR/rms/forms/bin) to compile the RMS reference forms.

8. Remove all newly created fm_*.fmx files (reference forms should not have executable files).
9. Run fmb2fmx10gr2 (in INSTALL_DIR/rms/forms/bin) to generate RMS runtime forms – .fmx’s.
10. Check to make sure that each non-reference form .fmb file has a corresponding .fmx file.

Note: Disregard fm_*.fmx files should they be created. These files should be removed. They should NOT exist in the INSTALL_DIR/rms/forms/bin directory.

11. Remove all non-reference form forms from INSTALL_DIR/rms/forms/bin. The following syntax leaves all reference forms (fm_*.fmb) in the bin directory, while removing all other forms:

```
> for PROG in `ls *.fmb | grep -v fm_`
> do PROGNAME=`echo $PROG`
> rm $PROGNAME
> done
```
12. Copy all menus (*.mmb files) in the INSTALL_DIR/rms/forms/src directory to the INSTALL_DIR/rms/forms/bin directory.
13. Run mmb2mmx10gr2 (in INSTALL_DIR/rms/forms/bin) to generate RMS runtime menus – .mmx’s.
14. Check to make sure that each .mmb file has a corresponding .mmx file.
15. Remove all .mmb files from INSTALL_DIR/rms/forms/bin.

Note: .err files may be created by the compilation scripts above. These files are logs of the compilation process and can be removed.



RMS Reports Installation

1. Copy all reports (*.rdf files) in the STAGING_AREA/reports/src directory to the INSTALL_DIR/rms/reports/bin directory.
2. Run rdf2rep10gr2 (in INSTALL_DIR/rms/reports/bin) to generate Reports runtime reports – .rep’s.

Note: The following error messages may appear when running rdf2rep10gr2; these errors can be ignored if report (.rep) generation was successful:

REP-0759: One or more PL/SQL libraries have been modified since the reports was saved. The PL/SQL will be recompiled.

REP-0202: Attempt to free a null pointer

REP-0759 is generated by the r25conv program. The error appears any time a report is converted.

REP-0202 is due to an Oracle bug with rwconverter and can be ignored

3. Check to make sure that each .rdf file has a corresponding .rep file.
4. Remove all .rdf files from INSTALL_DIR/rms/reports/bin.

Note: .err files may be created by the compilation scripts above. These files are logs of the compilation process and can be removed.
