

Oracle® Retail Merchandising

Batch Schedule

Release 12.0.10.2

November 2009

Copyright © 2009, Oracle. All rights reserved.

Primary Author: Nathan Young

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Value-Added Reseller (VAR) Language

Oracle Retail VAR Applications

The following restrictions and provisions only apply to the programs referred to in this section and licensed to you. You acknowledge that the programs may contain third party software (VAR applications) licensed to Oracle. Depending upon your product and its version number, the VAR applications may include:

- (i) the software component known as **ACUMATE** developed and licensed by Lucent Technologies Inc. of Murray Hill, New Jersey, to Oracle and imbedded in the Oracle Retail Predictive Application Server – Enterprise Engine, Oracle Retail Category Management, Oracle Retail Item Planning, Oracle Retail Merchandise Financial Planning, Oracle Retail Advanced Inventory Planning, Oracle Retail Demand Forecasting, Oracle Retail Regular Price Optimization, Oracle Retail Size Profile Optimization, Oracle Retail Replenishment Optimization applications.
- (ii) the **MicroStrategy** Components developed and licensed by MicroStrategy Services Corporation (MicroStrategy) of McLean, Virginia to Oracle and imbedded in the MicroStrategy for Oracle Retail Data Warehouse and MicroStrategy for Oracle Retail Planning & Optimization applications.
- (iii) the **SeeBeyond** component developed and licensed by Sun Microsystems, Inc. (Sun) of Santa Clara, California, to Oracle and imbedded in the Oracle Retail Integration Bus application.
- (iv) the **Wavelink** component developed and licensed by Wavelink Corporation (Wavelink) of Kirkland, Washington, to Oracle and imbedded in Oracle Retail Mobile Store Inventory Management.
- (v) the software component known as **Crystal Enterprise Professional and/or Crystal Reports Professional** licensed by SAP and imbedded in Oracle Retail Store Inventory Management.
- (vi) the software component known as **Access Via™** licensed by Access Via of Seattle, Washington, and imbedded in Oracle Retail Signs and Oracle Retail Labels and Tags.
- (vii) the software component known as **Adobe Flex™** licensed by Adobe Systems Incorporated of San Jose, California, and imbedded in Oracle Retail Promotion Planning & Optimization application.
- (viii) the software component known as **Style Report™** developed and licensed by InetSoft Technology Corp. of Piscataway, New Jersey, to Oracle and imbedded in the Oracle Retail Value Chain Collaboration application.
- (ix) the software component known as **DataBeacon™** developed and licensed by Cognos Incorporated of Ottawa, Ontario, Canada, to Oracle and imbedded in the Oracle Retail Value Chain Collaboration application.

You acknowledge and confirm that Oracle grants you use of only the object code of the VAR Applications. Oracle will not deliver source code to the VAR Applications to you. Notwithstanding any other term or condition of the agreement and this ordering document, you shall not cause or permit alteration of any VAR Applications. For purposes of this section, “alteration” refers to all alterations, translations, upgrades, enhancements, customizations or modifications of all or any portion of the VAR Applications including all reconfigurations, reassembly or reverse assembly, re-engineering or reverse engineering and recompilations or reverse compilations of the VAR Applications or any derivatives of the VAR Applications. You acknowledge that it shall be a breach of the agreement to utilize the relationship, and/or confidential information of the VAR Applications for purposes of competitive discovery.

The VAR Applications contain trade secrets of Oracle and Oracle’s licensors and Customer shall not attempt, cause, or permit the alteration, decompilation, reverse engineering, disassembly or other reduction of the VAR Applications to a human perceivable form. Oracle reserves the right to replace, with functional equivalent software, any of the VAR Applications in future releases of the applicable program.

Contents

Preface	vii
Audience	vii
Related Documents.....	vii
Customer Support.....	viii
Review Patch Documentation.....	viii
Oracle Retail Documentation on the Oracle Technology Network.....	viii
Conventions.....	viii
1 Introduction to Merchandising Batch Processing	1
Batch Processing.....	1
Types of Batch Programs	1
Batch Window	2
Batch Schedule and Phases.....	2
Merchandising Batch Schedule.....	3
Program List	3
Batch Schedule Diagram	5
RMS, ReIM, RTM Section	5
ReSA Section.....	6
RPM Section.....	6
Notations in the Batch Schedule Diagram.....	7
prepost Program	8
Modifications to the Batch Schedule	9
2 Program List.....	11
3 Batch Schedule Diagram	17
4 Interface Diagrams for RMS and RPAS	19
RMS Pre/Post Extract Diagrams	20
RMS Foundation Data Extract Diagrams	21
RMS Fact Data Extract Diagrams.....	23
RPAS-RMS Fact Load Diagram	24
5 Interface Diagrams for RMS and RDW.....	25
6 Interface Diagram for RPM and RDW.....	37
7 Interface Diagram for ReIM and RDW	39

Preface

This batch schedule document details the integrated cyclical processing schedules for the Oracle Retail Merchandising applications:

- Oracle Retail Merchandising System (RMS)
- Oracle Retail Invoice Matching (ReIM)
- Oracle Retail Price Management (RPM)
- Oracle Retail Sales Audit (ReSA)
- Oracle Retail Trade Management (RTM)
- Oracle Retail Allocation

Note: Although Oracle Retail Allocation is a Merchandising application, it is not represented in this batch schedule because it does not have any batch programs to run. All Allocation processing is online processing.

This guide describes the periodic and ad hoc phases of batch processing, as well as pre- and post-processing dependencies.

Audience

The audiences for this guide are as follows:

- Systems analysts and system operations personnel who need information about Merchandising processes, internally or in relation to systems across the enterprise
- Integrators and implementation staff who have the overall responsibility for implementing the Merchandising applications in their enterprise

Related Documents

For more information, see the following documents for the Oracle Retail Merchandising products:

- *Oracle Retail Merchandising System Operations Guide*
- *Oracle Retail Price Management Operations Guide*
- *Oracle Retail Invoice Matching Operations Guide*
- *Oracle Retail Data Warehouse Operations Guide*
- *Oracle Retail Predictive Application Server documentation*
- *Oracle Retail Demand Forecasting documentation*

Customer Support

To contact Oracle Customer Support, access My Oracle Support at the following URL:
<https://metalink.oracle.com>

When contacting Customer Support, please provide the following:

- Product version and program/module name
- Functional and technical description of the problem (include business impact)
- Detailed step-by-step instructions to re-create
- Exact error message received
- Screen shots of each step you take

Review Patch Documentation

If you are installing the application for the first time, you install either a base release (for example, 13.0) or a later patch release (for example, 13.0.2). If you are installing a software version other than the base release, be sure to read the documentation for each patch release (since the base release) before you begin installation. Patch documentation can contain critical information related to the base release and code changes that have been made since the base release.

Oracle Retail Documentation on the Oracle Technology Network

In addition to being packaged with each product release (on the base or patch level), all Oracle Retail documentation is available on the following Web site (with the exception of the Data Model which is only available with the release packaged code):

http://www.oracle.com/technology/documentation/oracle_retail.html

Documentation should be available on this Web site within a month after a product release. Note that documentation is always available with the packaged code on the release date.

Conventions

Navigate: This is a navigate statement. It tells you how to get to the start of the procedure and ends with a screen shot of the starting point and the statement “the Window Name window opens.”

Note: This is a note. It is used to call out information that is important, but not necessarily part of the procedure.

This is a code sample
It is used to display examples of code

A hyperlink appears like this.

Introduction to Merchandising Batch Processing

This chapter is a brief introduction to Oracle Retail batch processing. It defines basic terms and concepts, describes batch processing phases, and explains how to interpret the batch schedule diagram and program list.

Batch Processing

Batch processing is the execution of a group of batch programs (jobs). The results are returned without user intervention. Batch programs are commonly used for the following reasons:

- To process large volumes of transaction data
- To interface with external systems
- To perform internal maintenance

Batch programs can process very large quantities of data quickly and efficiently. Batch programs can perform some updates that could be performed through online transactions, but much more quickly and with less impact on system performance. Batch processing is usually scheduled for times when systems are idle or least busy.

Batch programs can be run automatically using batch scheduler software. The batch scheduler allows batch jobs to be set up in a specific order, with restrictions attached to any program as needed. If an error occurs with a batch program, an administrator must correct the error and manually rerun the batch program that failed.

Types of Batch Programs

Oracle Retail batch programs are of several types:

- Upload programs bring data from external systems into the Oracle Retail database. For example, the `posupld` program uploads daily transactions that occur at the point of sale (POS) for processing by the Oracle Retail Management System (RMS).
- Download programs extract data from RMS and format it so it can be used by external systems. For example, the `posdnld` program extracts new and changed information about an item/location for downloading to the point of sale.
- System maintenance programs perform tasks such as updating the system date. For example, the `dtesys` program increments the system date at the end of each batch cycle.
- Functional maintenance programs process data specific to a functional area. For example, the `storeadd` program updates a number of tables to create entries for a new store.

Batch Window

Because of the impact on production systems, it is not always possible to run batch programs during business hours; however, there is a window of opportunity during each day or night when online systems are not being used. This time frame is the *batch window*. For example, a retailer with stores throughout the continental U.S. might require its online systems to be available from 8 AM Eastern Standard Time, when its East Coast offices open, until 9 PM Pacific Standard Time, when its West Coast stores close. This allows an eight-hour batch window for processing all batch jobs.

Batch Schedule and Phases

Order is critical when running batch programs. Some tasks need to be performed before others. A batch schedule ensures that every time batch processing is performed, the correct tasks are performed in the proper order.

The batch schedule is a diagram that represents all batch programs and how they are sequenced. For each individual user, the schedule is a suggested starting point for the installation. Some programs are specific to products that may not be installed, so these programs may not be used at all.

The total batch schedule is divided into phases. Each phase must be completed before the next phase can begin. Within a phase, there may also be programs that depend on the completion of another program within that phase, so programs within each phase may need to be run in a particular order.

Merchandising Batch Schedule

The integrated Merchandising batch schedule combines the batch schedules of all Merchandising applications into a single schedule diagram. The diagram (later in this document) shows the batch dependencies among the Merchandising applications.

The integrated Merchandising batch schedule combines the batch modules for the following applications:

- Oracle Retail Merchandising System (RMS)
- Oracle Retail Trade Management (RTM)
- Oracle Retail Sales Audit (ReSA)
- Oracle Retail Invoice Matching (ReIM)
- Oracle Retail Price Management (RPM)

Note: Although Oracle Retail Allocation is a Merchandising application, it is not represented in this batch schedule because it does not have any batch programs to run. All Allocation processing is online processing.

Program List

The columns of the program list provide details about each batch program, as follows:

Column	Description
Program name	Name of the program or script
Functional area	Functional area of the application for which the batch program is run
Threaded	Whether the program is threaded (Y/N)
Driver	Program driver
Phase	Phase during which the program is run (see the batch schedule diagram)
Pre-dependency	Programs that must be completed before the program can be run
Post-dependency	Programs that must be run after the program completes successfully
Timing	How often the program is run (for example, daily, weekly, monthly, ad hoc)
Restart/Recovery	Whether the program uses restart/recovery (R=Yes, N=No)
Run Parameters for Program	Command syntax to run the program

For example, the following shows the information in the program list about an RMS phase 3 program named dealday:

Program Name	dealday
Functional Area	Deals
Threaded	Y
Driver	Location
Phase	3
Pre-dependency	dealinc, dealfinc, prepost dealday pre
Post-dependency	prepost dealday post, salmnth
Timing	Monthly
Restart/Recovery	R
Usage	dealday userid/passwd

The program list is grouped in the following order:

- RMS, RTM, and ReSA programs
- RPM programs
- ReIM programs
- RMS extracts for Retail Predictive Application Server (RPAS)
- RMS extracts for Retail Data Warehouse (RDW)

The extracts for RPAS and RDW are programs that are part of the RMS application.

Batch Schedule Diagram

The batch schedule diagram illustrates the program list pre- and post-dependency details. The layout and notations of the diagram also illustrate required sequences and other processing details. Executing the Merchandising batch processing in the manner diagrammed ensures that all critical dependencies are met.

For ease of setting up a schedule at client site, and also based on logical application dependencies, the diagram is divided into three main sections:

- RMS, RTM, ReIM
- ReSA
- RPM

Later chapters of this document show data flow diagrams for other batch processes:

- Chapter 4 shows the Retail Extract, Transform, and Load (RETL) data flows for the extracts from RMS to RPAS.
- Chapter 5 shows the RETL dimension and fact data flows for the extracts from RMS to Retail Data Warehouse (RDW).
- Chapter 6 shows the RETL data flow for the Promotion dimension extract from RPM to RDW.
- Chapter 7 shows the RETL data flow for the Supplier Invoice Cost dimension extract from ReIM to RDW.

RMS, ReIM, RTM Section

The first section diagrams the RMS, ReIM, and RTM programs and their dependencies. This section is further divided into phases 0 through 7, ad hoc, and date set batch.

Each phase must be completed before the next phase can begin. Also, a phase may contain programs that depend on other programs within the phase. Programs within each phase may need to run in a particular sequence.


The following are brief descriptions of the Merchandising batch processing phases. Depending on your implementation, some programs and phases may not apply.

Phase	Description
Phase 0	The first phase performs essential table maintenance including: <ul style="list-style-type: none"> ▪ Daily purges ▪ Updates to currency exchange rates ▪ Updates to value-added tax (VAT) data
Phase 1	This phase prepares the tables for interfacing with external systems in Phase 2. Among other programs, the stock variance (stkvar) batch program is run to update stock counts.
Phase 2	During this phase, information is uploaded from external interfaces, including point of sale (POS) data (posupld batch program).
Phase 3	In this phase, the main RMS processing programs are run for purchasing, ordering, stock ledger, deals, and replenishment.
Phase 4	This phase pushes data to external sources. Changed system information is rebuilt. Open to buy (OTB) data is updated. Information is sent to the forecasting system.

Phase	Description
Phase 5	This phase consists of ReIM process upload programs.
Phase 6	This phase consists of ReIM process roll-up programs.
Phase 7	This phase consists of ReIM process download programs.
Ad Hoc	Ad hoc batch programs can be run at any time. The ad hoc programs have no phase dependencies.
Date Set	The Date Set phase increments the system date and updates other calendar dates. Note: The date set phase should be the very last phase to run. Even the ad hoc programs should be run before the date set program.

Read the batch schedule diagram from left to right. In the following example, any of the programs (ediupavl, ediupack, stkvar, ditinsrt, lifstkup, ReceiverAdjustment, DiscrepancyPurge) can start at the same time; however, the stkupld program cannot start until the lifstkup program is successfully completed.

Sequence -----▶



ReSA Section

This section diagrams the ReSA programs and their dependencies.

RPM Section

This section diagrams the RPM programs and their dependencies.

Notations in the Batch Schedule Diagram

Pipes

Pipes are vertical bars (|) that represent the dependencies within a phase. Reading left to right, a pipe indicates that one or more programs to the right depend upon completion of one or more programs to the left.

In the following example, the `stkupld` module depends on the `lifstkup` module; that is, the `stkupld` module can be run only after successful completion of the `lifstkup` module.

<code>lifstkup</code>		<code>stkupld</code>
-----------------------	--	----------------------

In the following example, both of the modules `cntrordb` and `reqext` are dependent on `ociroq`. Neither `cntrordb` nor `reqext` can be run until the `ociroq` module has completed successfully.

<code>ociroq</code>		<code>cntrordb</code>
		<code>reqext</code>

In the following example, the `ibcalc` module is dependent on both `ibexpl` and `cntrprss`. The `ibcalc` module cannot be run until both `ibexpl` and `cntrprss` have completed successfully.

<code>ibexpl</code>		<code>ibcalc</code>
<code>cntrprss</code>		

Abbreviations

In the diagram, abbreviations in parentheses that follow program names have the following meanings:

Abbreviation	Meaning
(perl)	The module is a Perl script.
(FIF)	The module is related to the Financials application.
(sqlldr)	There is a sqlloader process to load/ftp the output files.
(rebuild all)	There is a rebuild process inside the application.
(IM)	The module is related to Invoice Matching but owned by RMS.
(RMS)	The module belongs to RMS.
(RMS)	(Bold type) The RMS module is executed externally to that phase.
(ReSA)	The module belongs to ReSA.
(ReSA)	(Bold type) The ReSA module is executed externally to that phase.
(ReIM)	The module belongs to ReIM.
(RTM)	The module belongs to RTM.
(Weekly)	The module is executed weekly.
(Monthly)	The module is executed monthly.
(Forms Auditing)	This is an online forms auditing process related to ReSA.

Footnotes

Footnote symbols (*, **, †, ‡) refer to footnotes that appear below that phase or section of the diagram.

prepost Program

The prepost program facilitates multi-threading by allowing general system administration functions (such as table deletions or mass updates) to be completed after all threads of a particular program have been processed. The prepost program must be run before, after, or both before and after, programs that require specific processing to run or complete successfully.

In the batch schedule diagram, the prepost program is indicated by “pre” and “post” entries, as in the following examples.

In the following example, pre-processing is required before running the ociroq program.

pre	ociroq
------------	---------------

In the following example, pre-processing is required before running the stkupd program. Also, post-processing is required after successful completion of the stkupd program.

pre	stkupd	post
------------	---------------	-------------

In the following example, post-processing is required after successful completion of the sccext program.

sccext	post
---------------	-------------

Modifications to the Batch Schedule

The integrated Merchandising batch schedule shows the dependencies for all the programs that *could* be run by a retailer. Based on many factors, there will always be some programs that a retailer does not run. Determining which programs, or groups of programs, are not required is a job that should be performed at implementation time.

One major factor involves the applications that the retailer has purchased and wants to install:

- For example, a retailer may have purchased RMS, but not ReIM; in this case, the ReIM programs would not be run.
- Another example is that a retailer may not want to use some functionality within an application. Perhaps a retailer purchased RMS but did not purchase the RDW application. In this case, the retailer may not want to run the programs that extract RMS data to be used later by the RDW application.

These major configuration choices also affect whether some programs are used:

- Whether the Retail Integration Bus (RIB) is used
For more information about configuring the RIB for Merchandising applications, see “Configuring RPM without the RIB” in the “Backend System Administration and Configuration” chapter of the Oracle Retail Price Management Operations Guide.
- Whether full-featured or simplified Retail Price Management (RPM) is used
For more information about configuring simplified RPM, see the “Backend System Administration and Configuration” chapter in the Retail Price Management Operations Guide.
- Whether full-featured or simplified RTM is used
For more information about configuring simplified RTM, see the “Oracle Retail Trade Management Batch” chapter in Volume 1 of the Oracle Retail Merchandising System Operations Guide.

RMS,RTM,ReSA Program Dependency and Scheduling Details

Program Name	Functional Area	Threaded	Driver	Phase	Pre-dependency	Post-dependency	Timing	Uses Restart/Recovery	Run Parameters for Programs
audprg	Audit	N	N/A	ad hoc	N/A	N/A	daily	N	audprg userid/passwd
audtsys	Audit	N	N/A	ad hoc	N/A	N/A	daily	N	audtsys userid/passwd
batch_orpos_extract.ksh	Point of Sale Interface	Y	Store	4	prepost batch_orpos_extract	N/A	daily	N	batch_orpos_extract.ksh userid/passwd [-p <no. of threads>] [DIR - location where extracts are to be generated]
czprg	Costing	N	N/A	ad hoc	N/A	N/A	monthly	N	czprg userid/passwd
cednid	Trade Management	Y	Broker	2	N/A	N/A	daily	R	cednid userid/passwd broker_file_name
cmpprg	Pricing	N	N/A	ad hoc	N/A	N/A	daily	N	cmpprg userid/passwd
cmpupld	Pricing	N	N/A	ad hoc	N/A	All RPM batch modules	ad hoc	R	cmpupld userid/passwd input_file reject_file
cntrmain	Contracting	N	N/A	0	N/A	All Replenishment modules	daily	R	cntrmain userid/passwd
cntrordb	Contracting	Y	Contract	3	rpladj	prepost cntrordb.post	daily	R	cntrordb userid/passwd
cntrprss	Contracting	Y	Dept	3	rplex	prepost rplbid.post	daily	R	cntrprss userid/passwd
costcalc	Deals	Y	Supplier	2	dfinrst	prepost costcalc	daily	R	costcalc userid/passwd supplier (May use the batch_costcalc.ksh for launching this program as it is created based on performance considerations)
cremhierdy	Reclassification	N	N/A	4	N/A	prepost recsldy	daily	R	cremhierdy userid/passwd
deallact	Deals	Y	Deal Id	3	prepost deallact_nor.pre	N/A	daily	R	deallact userid/passwd
dealcls	Deals	N	N/A	3	prepost dealcls_sales.pre	N/A	daily	R	dealcls userid/passwd
dealday	Deals	Y	Location	3	dealinc	prepost dealday.post	monthly	R	dealday userid/passwd
dealex	Deals	Y	Deal Id	3	prepost costcalc	recsldy	daily	N	dealex userid/passwd
deallct	Deals	Y	Deal Id	3	prepost dealinc	salrmth	daily	R	deallct userid/passwd [Y/N - EOM processing ind]
deallnc	Deals	Y	Deal Id	3	deallact	deallct	weekly/ad hoc	R	deallnc userid/passwd
dealinc	Deals	Y	Deal Id	3	prepost dealinc.pre	salrmth (if monthly)	monthly	R	dealinc userid/passwd [Y/N - EOM processing ind]
deallprg	Deals	Y	N/A	ad hoc	N/A	N/A	monthly	R	deallprg userid/passwd
dealupld	Deals	Y	File-based	0	(This program is the first one in Deals batch (This program will likely be run after sales information is uploaded into Oracle Retail))	(All other deals programs)	daily	R	dealupld userid/passwd input_file reject_file
dftrbid	Item Maintenance	Y	Dept	3	ordcost	(SQL*Load the output file)	daily	R	dftrbid userid/passwd outfile
discobapply	OTB	Y	Dept	4	ordcost	N/A	daily	R	discobapply userid/passwd
distrocpub	Pricing/Transfers/Allocation Publish	Y	Store	3	PriceEventExecutionBatch(RPM)	N/A	daily	R	distrocpub userid/passwd
dfinrst	Deals	N	N/A	1	prepost	costcalc	daily	R	dfinrst userid/passwd (P or S) (supplier/partner). Partner or Supplier.
dyprg	Maintenance	N	N/A	0	N/A	costcalc	daily	N	dyprg userid/passwd (P or S) (supplier/partner). Partner or Supplier.
dcclose	Receiving	N	N/A	ad hoc	N/A	(All other batch programs)	daily	R	dcclose userid/passwd
dtesys	Calendar	N	N/A	date_set	(This program should run at the end of the batch cycle)	prepost dtesys.post	daily	N	dtesys userid/passwd [indate--YYYYMMDD format]
dummyctn	Receiving	N	N/A	ad hoc	N/A	N/A	daily	N	dummyctn userid/passwd
ediadd	Maintenance	N	N/A	ad hoc	N/A	N/A	ad hoc	N	ediadd userid/passwd ediadd_output.ediadd_catalo
edidcon	Contracting	N	N/A	ad hoc	N/A	N/A	ad hoc	N	edidcon userid/passwd edidcon_outfil
edidlinv	Invoice Matching	Y	Location	4	N/A	N/A	daily	R	edidlinv userid/passwd output_filename
edidord	Ordering	N	N/A	4	(and after replenishment batch)	N/A	ad hoc	R	edidord userid/passwd filename
edidprd	EDI Interface - Sales and Inventory	N	N/A	4	prepost edidprd.pre	prepost edidprd.post	daily	R	edidprd userid/passwd filename
ediprg	EDI Interface - Purge	N	N/A	ad hoc	(Towards the end of the batch cycle)	N/A	monthly	R	ediprg userid/passwd
ediupadd	Maintenance	N	File-based	2	N/A	N/A	daily	N	ediupadd userid/passwd input_file reject_file
ediupack	EDI Interface - ordering	N	N/A	1	N/A	N/A	ad hoc	R	ediupack userid/passwd data_file reject_file
ediupavl	EDI Interface - Contracts	N	File-based	1	N/A	N/A	daily	R	ediupavl userid/passwd input_file reject_file
ediupcat	EDI Interface - Suppliers	N	File-based	ad hoc	N/A	N/A	daily	R	ediupcat userid/passwd edi_data_file error_file
fcstrprg	Forecasting	Y	Domain Id	ad hoc	prepost fcstrprg.pre	prepost fcstrprg.post	daily	N	fcstrprg userid/passwd domain
fcstrbid	Forecasting	Y	Domain Id	3	N/A	prepost fcstrbid.post	weekly	R	fcstrbid userid/passwd
fcstrbid_sbc	Forecasting	Y	Domain Id	3	prepost fcstrbid.post	prepost fcstrbid.post	weekly	R	fcstrbid_sbc userid/passwd
fflgdn1	Financial Interface	Y	Dept	3	salstage	prepost fflgdn1.post	daily	R	fflgdn1 userid/passwd
fflgdn2	Financial Interface	Y	Dept	3	salstage	salstage	daily	R	fflgdn2 userid/passwd
fflgdn3	Financial Interface	Y	Store/Wh	3	salrmth	N/A	monthly	R	fflgdn3 userid/passwd
ftmednid	Planning System Interface	N	N/A	ad hoc	N/A	N/A	ad hoc	R	ftmednid userid/passwd
gcpuld	Misc Interface - Taxgeocode	N	N/A	ad hoc	N/A	N/A	ad hoc	R	gcpuld -username/passwd@environment -<infile> -<outfile>
gprnpris	Ordering	Y	Supplier	ad hoc	N/A	N/A	ad hoc	R	gprnpris userid/passwd
gradupld	Forecasting	N	File-based	ad hoc	N/A	N/A	ad hoc	R	gradupld userid/passwd input_file rej_fil
hstbid	Sales	Y	Location	3	prepost hstbid.pre (for rebuild all)	prepost hstbid.post	weekly	R	hstbid userid/passwd level(weekly/rebuild)
hstbid_diff	Sales	N	N/A	ad hoc	hstbid	N/A	ad hoc	N	hstbid_diff userid/passwd
hstbidmth	Sales	Y	Dept	3	prepost hstbidmth.pre	prepost hstbidmth.post	monthly	R	hstbidmth userid/passwd level(monthly/rebuild)
hstbidmth_diff	Sales	N	N/A	ad hoc	prepost hstbid.post	prepost hstbid.post	ad hoc	N	hstbidmth_diff userid/passwd
hstmthupd	Sales	Y	Location	3	(The program should be run on the last day of the month).	HSTMTHUPD.PC for non-existent records on ITEM_LOC_HIST_MTH	monthly	R	hstmthupd userid/passwd (out_file)
hstrprg	Sales	N	N/A	ad hoc	N/A	N/A	monthly	N	hstrprg userid/passwd
hstrprg_diff	Sales	N	N/A	ad hoc	N/A	N/A	weekly	N	hstrprg_diff userid/passwd
hstwkupd	Sales	Y	Store/Wh	3	N/A	Run SQL*Loader using the control file hstwkupd.ctl to load data from the output file written by HSTWKUPD.PC for non-existent records on ITEM_LOC_HIST	weekly	R	hstwkupd userid/passwd (out_file)
hstupid	Trade Management	Y	File-based	ad hoc	Ushs2rms (perl script)	N/A	ad hoc	R	hstupid userid/passwd input_file reject_file country_id ; perl ushs_240_to_2400.inputfile.outputfile ; perl ushs2rms.inputfile.rejectfile
ibcalc	Investment Buy	Y	Dept	3	replex	rplbid	daily	R	ibcalc userid/passwd
ibexpl	Investment Buy	N	N/A	3	replex	prepost rplbid.post	daily	N	ibexpl userid/passwd
invaprg	Inventory Adjustments	N	N/A	ad hoc	N/A	ibcalc	monthly	N	invaprg userid/passwd
invclshp	Invoice Matching	N	N/A	2	N/A	N/A	daily	N	invclshp userid/passwd

invprg	Invoice Matching	N	N/A	ad hoc	ordprg	N/A	monthly	R	invprg user/passwd
lcardnd	Letter of Credit	N	N/A	4	N/A	lcm700 (perl script)	daily	R	lcardnd user/passwd output_file
lcardnd	Maintenance - Location	N	N/A	ad hoc	storeadc	N/A	monthly	R	lcardnd user/passwd
lcmdnd	Letter of Credit	N	N/A	4	N/A	lcm707 (perl script)	daily	R	lcmdnd user/passwd output_file
lcup798	Letter of Credit	N	N/A	2	lcm798 (perl script)	N/A	daily	R	lcup798 user/passwd input_file rej_file
lcupld	Letter of Credit	N	N/A	2	lcm730 (perl script)	N/A	daily	R	lcupld user/passwd input_file rej_file
lftskup	Stock Ledger	N	File-based		inv_bal_upload.sh (warehouse mgmt program)	stakupld	daily	N	lftskup user/passwd input_file output_file
likestore	Maintenance - Location	Y	Dept	ad hoc	storeadc	prepost likestore pos	daily	R	likestore user/passwd
mrt	Mass Return Transfers	Y	Warehouse	2	N/A	mrttrv	daily	R	mrt user/passwd
mntprg	Mass Return Transfers	Y	Warehouse	ad hoc	N/A	mrtupd	ad hoc	R	mntprg user/passwd
mrttrv	Mass Return Transfers	Y	Warehouse	2	mrt	mrtupd	daily	R	mrttrv user/passwd
mrtupd	Mass Return Transfers	Y	Warehouse	2	mrttrv	N/A	daily	R	mrtupd user/passwd
nwppurge	Stock Ledger	N	N/A	ad hoc	N/A	N/A	ad hoc	N	nwppurge user/passwd
nwpyearend	Stock Count	Y	Location	4	run on last day of yea	N/A	yearly	R	nwpyearend user/passwd
ociroq	Replenishment	N	N/A	3	repladj	N/A	daily	R	ociroq user/passwd
onordext	Planning System Interface	Y	Transfer	4	onordext	onordnd	weekly	R	onordext user/passwd datefil
onordnd	Planning System Interface	Y	Store/Wh	4	onordext	N/A	daily	R	onordnd user/passwd
onordext	Planning System Interface	Y	Order	4	prepost onordext prt	onordext	daily	R	onordext user/passwd datefil
ordautcl	Ordering	N	N/A	ad hoc	N/A	N/A	daily	N	ordautcl user/passwd
ordscnt	Deals	Y	Supplier	4	discotbapply	dealcals	daily	R	ordscnt user/passwd
ordprg	Ordering	N	N/A	ad hoc	reclsdly	invprg	monthly	N	ordprg user/passwd
ordrev	Ordering	N	N/A	4	ordscnt	edidlord	daily	R	ordrev user/passwd
ordupd	Ordering	N	N/A	4	(After RPM pricing change extraction batch)	otbdlord	daily	N	ordupd user/passwd
otbdlord	OTB	N	N/A	4	ordupd	otbdlord	daily	R	otbdlord user/passwd output_file
otbdisal	OTB	N	N/A	4	ordupd	N/A	daily	R	otbdisal user/passwd output_file
otbdnd	OTB	N	N/A	4	ordupd	N/A	daily	R	otbdnd user/passwd output_file
otbprg	OTB	N	N/A	ad hoc	N/A	N/A	monthly	N	otbprg user/passwd
otbupfwd	OTB	Y	File-based	ad hoc	N/A	N/A	daily	R	otbupfwd user/passwd input_file reject_fik
otbupkd	OTB	Y	File-based	ad hoc	N/A	N/A	daily	R	otbupkd user/passwd input_file reject_fik
poscndid	Point of Sale Interface	N	N/A	4	poscndid	prepost poscndid post	daily	R	poscndid user/passwd outputfil
poscndid	Point of Sale Interface	N	Store	ad hoc	N/A	prepost poscndid post	daily	R	poscndid user/passwd output_filename
posgpdid	Point of Sale Interface	Y	N/A	4	reclsdly	N/A	daily	R	posgpdid user/passwd output_file
posupld	Sales	Y	File-based	2	saexprms(ReSA)	prepost posupld post	daily	R	posupld user/passwd infile rejfile varfile itemfile lockfile
precostcalc	Deals	Y	Supplier	2	prepost precostcalc pre	costcalc	daily	R	precostcalc user/passwd supplier (May use the batch_precostcalc.ksh for launching this program as it is created based on performance considerations)
prepost	Pre/post functionality	N	N/A	all phases	N/A	N/A	daily	N	prepost user/passwd program_pre_or_pos
reclsdly	Item Maintenance	Y	Reclass no	4	cremhierdly	prepost reclsdly post	daily	R	reclsdly user/passwd process_modt
repladj	Replenishment	Y	Dept	3	rplatusd	reqlt	daily	R	repladj user/passwd
					posupld	rplxt			
					rplatusd				
					repladj				
					prepost ociroq pre				
reqlt	Replenishment	Y	Partition (Item)	3	prepost reqlt pre	prepost reqlt post	daily	R	reqlt user/passwd partition_position (May use the batch_reqlt.ksh for launching this program as it is created based on performance considerations)
rlmaint	Replenishment	Y	Location	3	storeadc	prepost rlmaint post	daily	R	rlmaint username/passwd
					rplatusd	repladj			
					rplplit				
					supcnstr				
rplapprv	Replenishment	N	N/A	3	prepost rplapprv pre	N/A	daily	R	rplapprv user/passwd
					prepost rplatusd post				
					repladj				
rplatusd	Replenishment	Y	Location	3	prepost rplatusd pre	reqlt	daily	R	rplatusd user/passwd
					ibcalc				
					rplxt				
					critprss				
					vrplbid				
rplbid	Replenishment	Y	Supplier	3	ibexpl	prepost rplbid post	daily	R	rplbid username/passwd
					prepost rplxt post				
					critprss(If contracting is used, otherwise run ...				
					rplatusd				
					rlmaint				
					repladj				
					reqlt				
rplxt	Replenishment	Y	Dept	3	prepost rplxt post	rplbid	daily	R	rplxt user/passwd dept (May use the batch_rplxt.ksh for launching this program as it is created based on performance considerations)
rplrg	Replenishment	N	N/A	ad hoc	critprss	N/A	daily	N	rplrg user/passwd
rplrg_month	Replenishment	N	N/A	ad hoc	N/A	N/A	monthly	N	rplrg_month user/passwd
rplsplit	Replenishment	Y	Supplier	3	supcnstr	rplapprv	daily	R	rplsplit user/passwd
rvmovavg	Pricing	Y	Store	3	saestage	N/A	daily	R	rvmovavg user/passwd business_date(YYYYMMDD) store/options
rvprg	RTV	N	N/A	ad hoc	N/A	N/A	monthly	N	rvprg user/passwd
sacrypt	Sales Audit	Y	Store/Day	SA	sagetref	N/A	daily	N	sacrypt user/passwd infile outfile key_e/d (Encryption/Decryption indicated)
saescheat	Sales Audit	N	N/A	SA	satotals	saexpm	monthly	R	saescheat user/passwd
					saescheat	sapurge			
saexpach	Sales Audit	N	N/A	SA	saescheat	N/A	daily	R	saexpach user/passwd
					satotals				
saexpgl	Sales Audit	N	N/A	SA	saescheat	N/A	daily	R	saexpgl user/passwd
saexpm	Sales Audit	N	N/A	SA	saescheat	N/A	daily	R	saexpm user/passwd
saexpdrw	Sales Audit	Y	Store	SA	sapreexp	res2rdw(perl script)	daily	R	saexpdrw user/passwd ; perl res2rdw inputfile outputfil
					satotals				
saexprms	Sales Audit	Y	Store	SA	saescheat	saprepost saexprms post	daily	R	saexprms user/passwd
					satotals				
saexpuar	Sales Audit	N	N/A	SA	saescheat	N/A	daily	R	saexpuar user/passwd
					saescheat				
sagetref	Sales Audit	N	N/A	SA	sastdyr	saemptlog	daily	R	sagetref user/passwd itemfile wastefile ref_itemfile prim_varianfile varupdfile storedayfile codesfile errorfile ccvaf storeposfile tendertypefile merchcodefile partnerfile supplierfile employeefile bannerfile (To prevent a file from being written, place a '-' in its place. Note: Item files must all be written together).

saimpadj	Sales Audit	N	N/A	SA	saimplogfn	satotals	daily	R	saimpadj user/passwd input_file rej_file
saimplog	Sales Audit	Y	Store/Day	SA	sagetref saproset saimplog pre	saiprepost saimplog post (Use sqj Loader to load data into ReSA tables)	daily	N	saimplog user/pw infile badfile itemfile wactefile reftemfile primvariantfile varupfile storedayfile promfile codesfile errorfile cvalfile storeposfile tendertypefile merchcodefile partnerfile supplierfile employeefile bannerfile
saimplogfn	Sales Audit	N	N/A	SA	saivouch	satotals	daily	R	saimplogfn user/passwd store_day_file
saimplogdup_upd	Sales Audit	N	Store/Day	SA	salstage fifgldn1	N/A	after store day delete	R	saimplogdup_upd user/passwd storedayfile storeposfil
salapnd	Stock Ledger	N	N/A	3	fifgldn2	N/A	daily	R	salapnd user/passwd
saldly	Stock Ledger	Y	Store/Wh	3	salstage	salweek	daily	R	saldly user/passwd
saltech	Stock Ledger	Y	Dept	3	salmth	N/A	half yearly	N	saltech user/passwd
salins	Sales	N	N/A	0	N/A	N/A	daily	R	salins user/passwd
salmaint	Stock Ledger	N	N/A	ad hoc	N/A	N/A	half yearly	N	salmaint user/passwd pre_or_post
salmth	Stock Ledger	Y	Dept	3	pre_owj_extract.ksh(RMS to RDW RETL Extract)	prepost salmth post	monthly	R	salmth user/passwd
salprg	Stock Ledger	N	N/A	ad hoc	N/A	N/A	daily	N	salprg user/passwd
salstage	Stock Ledger	N	N/A	3	posupld saldly stkdy salapnd prepost salweek pre dealfct dealinc vendinvc	salstage	daily	N	salstage user/passwd
salweek	Stock Ledger	Y	Dept	3	vendinvf	salmth	weekly	R	salweek user/passwd
sapreexp	Sales Audit	N	N/A	SA	SA audit process	prepost salweek post (Before any SA export process)	daily	R	sapreexp user/passwd
saproset	Sales Audit	N	N/A	SA	N/A	N/A	daily	N	saproset user/passwd program pre_or_pos
sapurge	Sales Audit	Y	Store	SA	saproset sapurge pre (This program should be run as the last program in the ReSA batch schedule)	saproset sapurge post sapreexp	daily	R	sapurge user/passwd deleted_items_file [optional list of store days to be deleted]
sarules	Sales Audit	N	N/A	SA	satotals	saescheat	daily	R	sarules user/passwd store_no
sastdycr	Sales Audit	N	N/A	date_set	dtesys	dtesys	daily	R	sastdycr user/passwd [YYYYMMDD]
satotals	Sales Audit	N	N/A	SA	saimplogfn	sarules	daily	R	satotals user/passwd store_nx
saivouch	Sales Audit	N	N/A	SA	saimplog (and its SQL Load process)	saimplogfn	daily	R	saivouch user/passwd infile rejfile tendertype_fil
scocext	Costing	Y	Cost change	3	costidex.ksh (RMS to RDW RETL extract)	prepost scocext post	daily	R	scocext user/passwd
schedprg	Organizational Hierarchy	N	N/A	ad hoc	N/A	N/A	monthly	R	schedprg user/passwd
stmain	Item Maintenance	N	N/A	ad hoc	icrblid	N/A	ad hoc	R	stmain user/passwd
southnd	Forecasting	Y	Domain Id	4	N/A	N/A	daily	R	southnd user/passwd
stkdy	Stock Ledger	Y	Dept	3	stklar	salweek	daily	R	stkdy user/passwd
stklprg	Stock Ledger	N	N/A	ad hoc	N/A	prepost stklprg post	monthly	N	stklprg user/passwd
stkschedxpdl	Stock Ledger	Y	Location	0	prepost stklprg pre	stklprg	daily	R	stkschedxpdl user/passwd
stklupd	Stock Ledger	Y	Location	3	stklupd	prepost stklupd post	daily	R	stklupd user/passwd
stklupld	Stock Ledger	Y	Dept	1	ilfstklp	N/A	daily	R	stklupld user/passwd input_file reject_fil
stklar	Stock Ledger	Y	Dept	1	stkschedxpdl	N/A	daily	R	stklar user/passwd report_file_name
stklxpld	Stock Ledger	Y	Dept	3	wasteadj	stklupd	daily	R	stklxpld user/passwd
stlgnld	Stock Ledger	Y	Dept	4	N/A	N/A	weekly	R	stlgnld user/passwd input_file
storeadd	Maintenance - Location	N	N/A	ad hoc	likestore	likestore	daily	R	storeadd user/passwd
supcnstr	Replenishment	N	N/A	3	rpblid	rpblid	daily	R	supcnstr user/passwd
supmth	Stock Ledger	Y	Dept	3	prepost rpblid post	prepost supmth post	monthly	R	supmth user/passwd
tamperctn	Receiving	N	N/A	ad hoc	N/A	N/A	ad hoc	N	tamperctn user/passwd
tcktdnid	Maintenance	N	N/A	ad hoc	N/A	N/A	daily	R	tcktdnid user/passwd filename print_online_ind_days_in_advance [locator
tfposdn	Sales Tax	N	N/A	4	trposdn	prepost tfposdn post	daily	R	tfposdn user/passwd output_file
trnupld	Trades Management	Y	File-based	ad hoc	N/A	N/A	daily	R	trnupld user/passwd infile
tsfrpg	Transfers	N	N/A	ad hoc	prepost tsfrpg pre	N/A	monthly	R	tsfrpg user/passwd
trxposdn	Point of Sale Interface	N	N/A	4	N/A	trposdn	daily	R	trxposdn user/passwd
trrupld	Sales Tax	N	N/A	4	N/A	N/A	ad hoc	R	trrupld username/password input_file reject_fil
vadtxpl	Maintenance - VAT	Y	Vat Region	0	prepost vadtxpl pos	prepost vadtxpl pos	daily	R	vadtxpl user/passwd
vendinvc	Deals	Y	Deal Id	3	prepost vendinvc pre	salstage(if daily) salweek(if weekly)	daily	R	vendinvc user/passwd
vendinvf	Deals	Y	Deal Id	3	prepost vendinvf pre	salstage(if daily) salweek(if weekly)	daily	R	vendinvf user/passwd
vrpblid	Replenishment	Y	Supplier	2	edupack	prepost vrpblid post	daily	R	vrpblid user/passwd
wasteadj	Stock Ledger	Y	Store	3	N/A	stklupd	daily	R	wasteadj user/passwd
whadd	Maintenance - Location	N	N/A	ad hoc	N/A	N/A	daily	R	whadd user/passwd
whstrag	Maintenance - Location	N	N/A	3	(Must be run after all replenishment batch programs).	prepost whstrag post	daily	R	whstrag user/passwd

RPM Dependency and Scheduling Details

Program Name	Functional Area	Threaded	Driver	Phase	Pre-dependency	Post-dependency	Timing	Uses Restart/Recovery	Run Parameters for Programs
FutureReclassBatch	Future Retail	N	N/A	N/A	recldy(RMS)	NewItemLocBatch	daily/ad hoc	N	itemReclassBatch.sh rpm-app-userid password
NewItemLocBatch	Future Retail	N	N/A	N/A	storeadd(RMS), ItemReclassBatch	LocationMoveBatch PriceEventExecutionBatch	daily/ad hoc	N	NewItemLocBatch.sh rpm-app-userid password [status [error-commit-count]
LocationMoveBatch	Zone Structure/Future Retail	Y	Location move	N/A	NewItemLocBatch LocationMoveBatch	PriceEventExecutionBatch	daily	N	locationMoveBatch.sh rpm-app-userid password
PriceEventExecutionBatch	Price Change/Clearance/Promotion	Y	Pricing event	N/A	salstage (RMS) PriceEventExecutionBatch	PriceEventExecutionRMSBatch	daily	N	priceEventExecutionBatch.sh rpm-app-userid password
PriceEventExecutionRMSBatch	Price Change/Clearance/Promotion	Y	Pricing event	N/A	N/A	PriceEventExecutionDealsBatch	daily	N	priceEventExecutionRMSBatch.sh rpm-app-userid password
PriceEventExecutionDealsBatch	Price Change/Clearance/Promotion	Y	Pricing event	N/A	PriceEventExecutionRMSBatch	MerchExtractKickOffBatch	daily	N	priceEventExecutionDealsBatch.sh rpm-app-userid password
PriceStrategyCalendarBatch	Price Strategy	N	N/A	N/A	N/A	MerchExtractKickOffBatch	daily	N	priceStrategyCalendarBatch.sh rpm-app-userid password
WorksheetAutoApproveBatch	Pricing Worksheet	Y	Price strategy	N/A	N/A	MerchExtractKickOffBatch	daily	N	worksheetAutoApproveBatch.sh rpm-app-userid password

						PriceEventExecutionBatch storeadd (RMS)						
MerchExtractKickOffBatch	Pricing Worksheet	Y	Price strategy	N/A	N/A	WorksheetAutoApproveBatch PriceStrategyCalendarBatch MerchExtractKickOffBatch WorksheetAutoApproveBatch	N/A	daily	N		merchExtractKickOffBatch.sh rpm-app-userid password	
RPMTtoORPOSPublishBatch.sh	Price Change/Clearance/Promotion	N	N/A	N/A	N/A	WorksheetAutoApproveBatch	N/A	daily	N		ksh RPMTtoORPOSPublishBatch.sh <userid/passwd@sid > <log path> <error path>	
RPMTtoORPOSPublishExport.sh	Price Change/Clearance/Promotion	Y	Location	N/A	N/A	RPMTtoORPOSPublishBatch.sh	N/A	daily	N		ksh RPMTtoORPOSPublishExport.sh <userid/passwd@sid > <Number of slots> <log path> <Export path>	
RegularPriceChangePublishBatch	Regular Price Changes	Y	Price event (item/loc)	N/A	N/A	WorksheetAutoApproveBatch	RegularPriceChangePublishExport	daily/ad hoc	N		regularPriceChangePublishBatch.sh rpm-app-userid password	
RegularPriceChangePublishExport	Regular Price Changes	N	Price event (item/loc)	N/A	N/A	WorksheetAutoApproveBatch	RegularPriceChangePublishExport	daily/ad hoc	N		regularPriceChangePublishExport.sh rpm-db-userid/pwd@database [export-path]	
ClearancePriceChangePublishBatch	Clearances	Y	Price event (item/loc)	N/A	N/A	WorksheetAutoApproveBatch	ClearancePriceChangePublishExport	daily/ad hoc	N		clearancePriceChangePublishBatch.sh rpm-app-userid password	
ClearancePriceChangePublishExport	Clearances	N	Price event (item/loc)	N/A	N/A	ClearancePriceChangePublishBatch	ClearancePriceChangePublishExport	daily/ad hoc	N		clearancePriceChangePublishExport.sh rpm-db-userid/pwd@database [export-path]	
PromotionPriceChangePublishBatch	Promotions	Y	Price event (item/loc)	N/A	N/A	WorksheetAutoApproveBatch	PromotionPriceChangePublishExport	daily/ad hoc	N		promotionPriceChangePublishBatch.sh rpm-app-userid password	
PromotionPriceChangePublishExport	Promotions	N	Price event (item/loc)	N/A	N/A	PromotionPriceChangePublishBatch	PromotionPriceChangePublishExport	daily/ad hoc	N		promotionPriceChangePublishExport.sh rpm-db-userid/pwd@database [export-path]	
PriceChangeAutoApproveResultsPurgeBatch	Purge	N	N/A	N/A	N/A	N/A	N/A	daily/ad hoc	N		priceChangeAutoApproveResultsPurgeBatch.sh rpm-app-userid password	
PriceChangePurgeBatch	Purge	N	N/A	N/A	N/A	N/A	N/A	daily/ad hoc	N		priceChangePurgeBatch.sh rpm-app-userid password	
PriceChangePurgeWorkspaceBatch	Purge	N	N/A	N/A	N/A	N/A	N/A	daily/ad hoc	N		priceChangePurgeWorkspaceBatch.sh rpm-app-userid password	
PromotionPurgeBatch	Purge	N	N/A	N/A	N/A	N/A	N/A	daily/ad hoc	N		promotionPurgeBatch.sh rpm-app-userid password	
PurgeExpiredExecutedOrApprovedClearancesBatch	Purge	N	N/A	N/A	N/A	N/A	N/A	daily/ad hoc	N		purgeExpiredExecutedOrApprovedClearancesBatch.sh rpm-app-userid password	
PurgeUnusedAndAbandonedClearancesBatch	Purge	N	N/A	N/A	N/A	N/A	N/A	daily/ad hoc	N		purgeUnusedAndAbandonedClearancesBatch.sh rpm-app-userid password	
PurgeLocationMovesBatch	Purge	N	N/A	N/A	N/A	N/A	N/A	daily/ad hoc	N		purgeLocationMovesBatch.sh rpm-app-userid password	
ZoneFutureRetailPurgeBatch	Purge	N	N/A	N/A	N/A	N/A	N/A	ad hoc	N		zoneFutureRetailPurgeBatch.sh rpm-app-userid password	
ItemLocDeleteBatch	Purge	N	N/A	N/A	N/A	N/A	N/A	ad hoc	N		itemLocDeleteBatch.sh rpm-app-userid password	
priceChangeAreaDifferentialBatch	Price Change	Y	N/A	N/A	N/A	N/A	N/A	ad hoc	N		priceChangeAreaDifferentialBatch rpm-app-userid password	

ReIM Dependency and Scheduling Details

Program Name	Functional Area	Threaded	Driver	Phase	Pre-dependency	Post-dependency	Timing	Uses Restart/Recovery	Run Parameters for Programs
reimautomatch	Invoice Matching (ReIM)	Y	N/A	6	NA	reimrollup	daily	R	Userid/passwd
reimpurge	Invoice Matching (ReIM)	N	N/A	0	N/A	reimposting	daily	R	Userid/passwd
reimcomplexdealupload	Invoice Matching (ReIM)	Y	N/A	5	vendirvc(RMS), vendirv(RMS)	reimautomatch	daily	R	Userid/passwd BlockSize PartitionNo
reimdiscrepancyurge	Invoice Matching (ReIM)	N	N/A	1	N/A	reimrollup	daily	R	Userid/passwd
reimediinupload	Invoice Matching (ReIM)	Y	N/A	5	edidlinv(RMS)	reimautomatch	daily	R	Userid/passwd "EDI input file with path" "EDI reject file with path"
reimediindownload	Invoice Matching (ReIM)	N	N/A	7	reimposting	N/A	daily	R	Userid/passwd
reimfedxdealupload	Invoice Matching (ReIM)	Y	N/A	5	vendirvc(RMS), vendirv(RMS)	reimautomatch	daily	R	Userid/passwd BlockSize PartitionNo
reimrollup	Invoice Matching (ReIM)	N	N/A	6	reimautomatch	reimrollup	daily	R	Userid/passwd
reimreceiptwriteoff	Invoice Matching (ReIM)	N	N/A	6	reimautomatch	N/A	daily	R	Userid/passwd
reimposting	Invoice Matching (ReIM)	N	N/A	1	reimrollup	N/A	daily	R	Userid/passwd

RMS to RPAS RETL Extracts Dependency and Scheduling Details (EXTRACTS_FOR_RPAS)

Program Name	Functional Area	Threaded	Driver	Phase	Pre-dependency	Post-dependency	Timing	Uses Restart/Recovery	Run Parameters for Programs
pre_rmse_rpas.ksh	Planning/Forecast System Interface	N	N/A	N/A	N/A. This is a pre setup script	N/A	daily	N	N/A
rmse_rpas.ksh	Planning/Forecast System Interface	N	N/A	N/A	pre_rmse_rpas.ksh. (This is the launch script to run the extracts)	Refer to RPAS Operations guide	daily	N	N/A
rmse_rpas_attributes.ksh	Planning/Forecast System Interface	N	N/A	N/A	pre_rmse_rpas.ksh skdly	Refer to RPAS Operations guide	daily	N	N/A
rmse_rpas_daily_sales.ksh	Planning/Forecast System Interface	N	N/A	N/A	pre_rmse_rpas.ksh	Refer to RPAS Operations guide	daily	N	N/A
rmse_rpas_domain.ksh	Planning/Forecast System Interface	N	N/A	N/A	pre_rmse_rpas.ksh sitmain recltdly dlyprg	Refer to RPAS Operations guide	daily	N	N/A
rmse_rpas_item_master.ksh	Planning/Forecast System Interface	N	N/A	N/A	pre_rmse_rpas.ksh recltdly dlyprg	Refer to RPAS Operations guide	daily	N	N/A
rmse_rpas_merchhier.ksh	Planning/Forecast System Interface	N	N/A	N/A	pre_rmse_rpas.ksh dlyprg	Refer to RPAS Operations guide	daily	N	N/A
rmse_rpas_orghier.ksh	Planning/Forecast System Interface	N	N/A	N/A	pre_rmse_rpas.ksh skdly	Refer to RPAS Operations guide	daily	N	N/A
rmse_rpas_stock_on_hand.ksh	Planning/Forecast System Interface	N	N/A	N/A	pre_rmse_rpas.ksh storeadd dlyprg	Refer to RPAS Operations guide	daily	N	N/A
rmse_rpas_store.ksh	Planning/Forecast System Interface	N	N/A	N/A	pre_rmse_rpas.ksh	Refer to RPAS Operations guide	daily	N	N/A
rmse_rpas_suppliers.ksh	Planning/Forecast System Interface	N	N/A	N/A	pre_rmse_rpas.ksh hstkwkupd salweek	Refer to RPAS Operations guide	daily	N	N/A
rmse_rpas_weekly_sales.ksh	Planning/Forecast System Interface	N	N/A	N/A	pre_rmse_rpas.ksh whadd dlyprg	Refer to RPAS Operations guide	daily	N	N/A
rmse_rpas_wh.ksh	Planning/Forecast System Interface	N	N/A	N/A	pre_rmse_rpas.ksh	Refer to RPAS Operations guide	daily	N	N/A
rmsl_rpas_forecast.ksh	Planning/Forecast System Interface	N	N/A	N/A	pre_rmse_rpas.ksh	Refer to RPAS Operations guide	daily	N	rmsl_rpas_forecast.ksh daily or weekly
rmsl_rpas_update_retl_date.ksh	Planning/Forecast System Interface	N	N/A	N/A	After all RMS/Planning System Integration RETL scripts are run	Refer to RPAS Operations guide	daily	N	rmsl_rpas_update_retl_date.ksh CLOSED_ORDER or RECEIVED_QTY

RMS to RDW RETL Extracts Dependency and Scheduling Details (EXTRACTS_FOR_RDW)

Dimension source: Program Name	Functional Area	Threaded	Driver	Phase	Pre-dependency	Post-dependency	Timing	Uses Restart/Recovery	Run Parameters for Programs
cdedtlx.ksh	RDW interface	N	N/A	N/A	A, B	Refer to RDW operations guide	daily	N	N/A
cmptrex.ksh	RDW interface	N	N/A	N/A	A, B	Refer to RDW operations guide	daily	N	N/A
cmprtmex.ksh	RDW interface	N	N/A	N/A	A, B	Refer to RDW operations guide	daily	N	N/A
cmprtrcox.ksh	RDW interface	N	N/A	N/A	A, B	Refer to RDW operations guide	daily	N	N/A
cmrcydcx.ksh	RDW interface	N	N/A	N/A	A, B	Refer to RDW operations guide	daily	N	N/A
emplyex.ksh	RDW interface	N	N/A	N/A	A, B	Refer to RDW operations guide	daily	N	N/A
orgarex.ksh	RDW interface	N	N/A	N/A	A, B, storeadd (RMS), dlyprg (RMS), lcltbl (RMS)	Refer to RDW operations guide	daily	N	N/A
orgchanex.ksh	RDW interface	N	N/A	N/A	A, B, storeadd (RMS), dlyprg (RMS), lcltbl (RMS)	Refer to RDW operations guide	daily	N	N/A
orgchnex.ksh	RDW interface	N	N/A	N/A	A, B, storeadd (RMS), dlyprg (RMS), lcltbl (RMS)	Refer to RDW operations guide	daily	N	N/A
orgdisex.ksh	RDW interface	N	N/A	N/A	A, B, storeadd (RMS), dlyprg (RMS), lcltbl (RMS)	Refer to RDW operations guide	daily	N	N/A
orglimex.ksh	RDW interface	N	N/A	N/A	A, B, storeadd (RMS), dlyprg (RMS), lcltbl (RMS)	Refer to RDW operations guide	daily	N	N/A

orglocex.ksh	RDW interface	N	N/A	N/A	A, B, storeadd (RMS), dlyprg (RMS), lctblid (RMS)	Refer to RDW operations guide	daily	N	N/A
orglolex.ksh	RDW interface	N	N/A	N/A	A, B, storeadd (RMS), dlyprg (RMS), lctblid (RMS)	Refer to RDW operations guide	daily	N	N/A
orgltmex.ksh	RDW interface	N	N/A	N/A	A, B, storeadd (RMS), dlyprg (RMS), lctblid (RMS)	Refer to RDW operations guide	daily	N	N/A
orgltrex.ksh	RDW interface	N	N/A	N/A	A, B, storeadd (RMS), dlyprg (RMS), lctblid (RMS)	Refer to RDW operations guide	daily	N	N/A
orgrgnex.ksh	RDW interface	N	N/A	N/A	A, B, storeadd (RMS), dlyprg (RMS), lctblid (RMS)	Refer to RDW operations guide	daily	N	N/A
phasex.ksh	RDW interface	N	N/A	N/A	A, B	Refer to RDW operations guide	daily	N	N/A
prdclex.ksh	RDW interface	N	N/A	N/A	A, B, crenhierdly (RMS), reclsdly (RMS), dlyprg (RMS)	Refer to RDW operations guide	daily	N	N/A
prdcmpex.ksh	RDW interface	N	N/A	N/A	A, B	Refer to RDW operations guide	daily	N	N/A
prddex.ksh	RDW interface	N	N/A	N/A	A, B, crenhierdly (RMS), reclsdly (RMS), dlyprg (RMS)	Refer to RDW operations guide	daily	N	N/A
prddifex.ksh	RDW interface	N	N/A	N/A	A, B, crenhierdly (RMS), reclsdly (RMS), dlyprg (RMS)	Refer to RDW operations guide	daily	N	N/A
prddivex.ksh	RDW interface	N	N/A	N/A	A, B, crenhierdly (RMS), reclsdly (RMS), dlyprg (RMS)	Refer to RDW operations guide	daily	N	N/A
prddtypex.ksh	RDW interface	N	N/A	N/A	A, B, crenhierdly (RMS), reclsdly (RMS), dlyprg (RMS)	Refer to RDW operations guide	daily	N	N/A
prdgrpex.ksh	RDW interface	N	N/A	N/A	A, B, crenhierdly (RMS), reclsdly (RMS), dlyprg (RMS)	Refer to RDW operations guide	daily	N	N/A
prdslex.ksh	RDW interface	N	N/A	N/A	A, B	Refer to RDW operations guide	daily	N	N/A
prdtmex.ksh	RDW interface	N	N/A	N/A	A, B, crenhierdly (RMS), reclsdly (RMS), dlyprg (RMS)	Refer to RDW operations guide	daily	N	N/A
prdtmlex.ksh	RDW interface	N	N/A	N/A	A, B, crenhierdly (RMS), reclsdly (RMS), dlyprg (RMS)	Refer to RDW operations guide	daily	N	N/A
prdtmimex.ksh	RDW interface	N	N/A	N/A	A, B, crenhierdly (RMS), reclsdly (RMS), dlyprg (RMS)	Refer to RDW operations guide	daily	N	N/A
prdtmimlex.ksh	RDW interface	N	N/A	N/A	A, B	Refer to RDW operations guide	daily	N	N/A
prdtmsmex.ksh	RDW interface	N	N/A	N/A	A, B	Refer to RDW operations guide	daily	N	N/A
prdpimex.ksh	RDW interface	N	N/A	N/A	A, B, crenhierdly (RMS), reclsdly (RMS), dlyprg (RMS)	Refer to RDW operations guide	daily	N	N/A
prdsbcex.ksh	RDW interface	N	N/A	N/A	A, B, crenhierdly (RMS), reclsdly (RMS), dlyprg (RMS)	Refer to RDW operations guide	daily	N	N/A
prdsdaex.ksh	RDW interface	N	N/A	N/A	A, B, crenhierdly (RMS), reclsdly (RMS), dlyprg (RMS)	Refer to RDW operations guide	daily	N	N/A
regngrpex.ksh	RDW interface	N	N/A	N/A	A, B	Refer to RDW operations guide	daily	N	N/A
regnmtbex.ksh	RDW interface	N	N/A	N/A	A, B	Refer to RDW operations guide	daily	N	N/A
rsnex.ksh	RDW interface	N	N/A	N/A	A, B	Refer to RDW operations guide	daily	N	N/A
seasnex.ksh	RDW interface	N	N/A	N/A	A, B	Refer to RDW operations guide	daily	N	N/A
substratypex.ksh	RDW interface	N	N/A	N/A	A, B	Refer to RDW operations guide	daily	N	N/A
supctrex.ksh	RDW interface	N	N/A	N/A	A, B, cntnmain (RMS)	Refer to RDW operations guide	daily	N	N/A
supsupex.ksh	RDW interface	N	N/A	N/A	A, B, cntnmain (RMS)	Refer to RDW operations guide	daily	N	N/A
suptrmex.ksh	RDW interface	N	N/A	N/A	A, B, cntnmain (RMS)	Refer to RDW operations guide	daily	N	N/A
suprtex.ksh	RDW interface	N	N/A	N/A	A, B, cntnmain (RMS)	Refer to RDW operations guide	daily	N	N/A
indrtypex.ksh	RDW interface	N	N/A	N/A	A, B	Refer to RDW operations guide	daily	N	N/A
tlitypex.ksh	RDW interface	N	N/A	N/A	A, B	Refer to RDW operations guide	daily	N	N/A

Program Name	Functional Area	Threaded	Driver	Phase	Pre-dependency	Post-dependency	Timing	Uses Restart/Recovery	Run Parameters for Programs
cmprtrpcoldex.ksh	RDW interface	N	N/A	N/A	B	Refer to RDW operations guide	daily	N	cmprtrpcoldex.ksh output_file_path/output_file_name
csstidex.ksh	RDW interface	N	N/A	N/A	C	Refer to RDW operations guide	daily	N	csstidex.ksh output_file_path/output_file_name
exchngratex.ksh	RDW interface	N	N/A	N/A	B	Refer to RDW operations guide	daily	N	exchngratex.ksh output_file_path/output_file_name
invldex.ksh	RDW interface	N	N/A	N/A	C, salstage (RMS), mrt (RMS), ordrev (RMS)	Refer to RDW operations guide	daily	Y	invldex.ksh output_file_path/output_file_name
ivaldex.ksh	RDW interface	N	N/A	N/A	C, salstage (RMS), mrt (RMS)	Refer to RDW operations guide	daily	N	ivaldex.ksh output_file_path/output_file_name
ivrcpldex.ksh	RDW interface	N	N/A	N/A	C, salstage (RMS), mrt (RMS)	Refer to RDW operations guide	daily	N	ivrcpldex.ksh output_file_path/output_file_name
ivridex.ksh	RDW interface	N	N/A	N/A	C	Refer to RDW operations guide	daily	N	ivridex.ksh output_file_path/output_file_name
ivrlidex.ksh	RDW interface	N	N/A	N/A	C, salstage (RMS), mrt (RMS)	Refer to RDW operations guide	daily	N	ivrlidex.ksh output_file_path/output_file_name
ivuldex.ksh	RDW interface	N	N/A	N/A	C, salstage (RMS), mrt (RMS)	Refer to RDW operations guide	daily	N	ivuldex.ksh output_file_path/output_file_name
lptotdex.ksh	RDW interface	N	N/A	N/A	C, saexpdrw (ReSA), resa2rdw	Refer to RDW operations guide	daily	N	lptotdex.ksh output_file_path/output_file_name
lptotldex.ksh	RDW interface	N	N/A	N/A	C, saexpdrw (ReSA), resa2rdw	Refer to RDW operations guide	daily	N	lptotldex.ksh output_file_path/output_file_name
ncstulidex.ksh	RDW interface	N	N/A	N/A	C, costcalc (RMS)	Refer to RDW operations guide	daily	N	ncstulidex.ksh output_file_path/output_file_name
post_dwi_temp.ksh	RDW interface	N	N/A	N/A	All extract batches	Refer to RDW operations guide	daily	N	N/A
prcidex.ksh	RDW interface	N	N/A	N/A	N/A	Refer to RDW operations guide	daily	N	prcidex.ksh output_file_path/output_file_name
pre_dwi_extract.ksh	RDW interface	N	N/A	N/A	A	operations guide	daily	N	N/A
pre_dwi_temp.ksh	RDW interface	N	N/A	N/A	C, salstage (RMS)	Refer to RDW operations guide	daily	N	N/A
rplicidex.ksh	RDW interface	N	N/A	N/A	C, cntnprss (RMS), edliupavl (RMS)	Refer to RDW operations guide	daily	N	rplicidex.ksh output_file_path/output_file_name
savidex.ksh	RDW interface	N	N/A	N/A	rlapprv (RMS)	Refer to RDW operations guide	daily	N	savidex.ksh output_file_path/output_file_name
scmalidex.ksh	RDW interface	N	N/A	N/A	C, salstage (RMS)	Refer to RDW operations guide	daily	N	scmalidex.ksh output_file_path/output_file_name
scmolldex.ksh	RDW interface	N	N/A	N/A	C, salstage (RMS)	Refer to RDW operations guide	daily	N	scmolldex.ksh output_file_path/output_file_name
scridex.ksh	RDW interface	N	N/A	N/A	C, salstage (RMS)	Refer to RDW operations guide	daily	Y	scridex.ksh output_file_path/output_file_name
scrtldex.ksh	RDW interface	N	N/A	N/A	C, salstage (RMS)	Refer to RDW operations guide	daily	Y	scrtldex.ksh output_file_path/output_file_name
scridex.ksh	RDW interface	N	N/A	N/A	C, rlapprv (RMS), cntnprss (RMS), rpblid (RMS), cntnmain (RMS)	Refer to RDW operations guide	daily	N	scridex.ksh output_file_path/output_file_name
scfilwex.ksh	RDW interface	N	N/A	N/A	B, msl_rpas_forecast.ksh (RMS) to RPAS extract	Refer to RDW operations guide	daily	N	scfilwex.ksh output_file_path/output_file_name
slsldmex.ksh	RDW interface	N	N/A	N/A	C, saexpdrw (ReSA), resa2rdw	Refer to RDW operations guide	daily	Y	slsldmex.ksh output_file_path/output_file_name
slsmknilidex.ksh	RDW interface	N	N/A	N/A	C, salstage (RMS)	Refer to RDW operations guide	daily	N	slsmknilidex.ksh output_file_path/output_file_name
sltblmthex.ksh	RDW interface	N	N/A	N/A	C, salmth (RMS)	Refer to RDW operations guide	daily	N	sltblmthex.ksh output_file_path/output_file_name
sltblwex.ksh	RDW interface	N	N/A	N/A	C, salweek (RMS)	Refer to RDW operations guide	daily	N	sltblwex.ksh output_file_path/output_file_name
tlidmex.ksh	RDW interface	N	N/A	N/A	C, saexpdrw (ReSA), resa2rdw	Refer to RDW operations guide	daily	N	tlidmex.ksh output_file_path/output_file_name
vhreschdex.ksh	RDW interface	N	N/A	N/A	B, savouch (ReSA)	Refer to RDW operations guide	daily	N	vhreschdex.ksh output_file_path/output_file_name
vchrmoveldsgex.ksh	RDW interface	N	N/A	N/A	B, savouch (ReSA)	Refer to RDW operations guide	daily	N	vchrmoveldsgex.ksh output_file_path/output_file_name
vchroutwex.ksh	RDW interface	N	N/A	N/A	B, savouch (ReSA)	Refer to RDW operations guide	daily	N	vchroutwex.ksh output_file_path/output_file_name

Notes:
A is a set of batch processes on the RDW system.
A consists of the following RDW batch modules
factpandm.ksh
medfactpandm.ksh
factclosedm.ksh
mt_prime.ksh
B is pre_dwi_extract.ksh DWI batch process.

Interface Diagrams for RMS and RPAS


Because RMS is the retailer's central merchandising transactional processing system, it is the principle source of the foundation data needed in some of the Oracle Retail suite of products. RMS provides foundation data to RPAS, and RPAS provides planning data to RMS.

This chapter presents flow diagrams for data processing from sources. The source system's program or output file is illustrated, along with the program or process that interfaces with the source. After initial interface processing of the source, the diagrams illustrate the flow of the data.

Before setting up a program schedule, familiarize yourself with the functional and technical constraints associated with each program. Refer to the Retail Merchandising System Operations Guide for more information about these interface programs.

RMS Pre/Post Extract Diagrams


RMS Pre RETL Extract Maintenance




*** Note:** The `pre_rmse_rpas.ksh` program checks for existing `.txt` output files. Because of this validation, retailers running the program for the first time should include an optional `-c` parameter. This parameter allows the program to run successfully without pre-existing `.txt` output files.

RMS Foundation Data Extract Diagrams


Merchandise Hierarchy for RPAS



Organization Hierarchy for RPAS



RMS Fact Data Extract Diagrams




*** Note:**

If issues are active, the following two files result from the rmse_rpas_stock_on_hand.ksh flow:
 rmse_rpas_stock_on_hand_issues.dat
 rmse_rpas_stock_on_hand_sales.dat

If issues are **not** active, the following file results from the rmse_rpas_stock_on_hand.ksh flow:
 rmse_rpas_stock_on_hand_sales.dat


Sales Extracts For RPAS



**** Note:**

Depending upon the configuration of rmse_rpas_daily_sales.ksh, the data can be pulled from TRAN_DATA_HISTORY or TRAN_DATA.

RPAS-RMS Fact Load Diagram



***Note:**

? can represent the following:

- i (for issues)
- s (for stores)

?? represents domain 01-99.

Interface Diagrams for RMS and RDW


RMS works in conjunction with the Oracle Retail Extract Transform and Load (RETL) framework. RETL provides high-performance processing to extract data from Oracle Retail applications for use in data warehouses. The architecture allows database batch processes to take advantage of parallel processing capabilities.

This chapter presents flow diagrams for the RETL extraction RMS programs. The source system's program or output file is illustrated, along with the program or process that interfaces with the source. Note that the data flows are organized according to the logic (dimension data and table data) of Oracle Retail Data Warehouse (RDW), but you can use the data to suit your business needs.

For detailed information about dimensions and facts, see the Oracle Retail Data Warehouse Operations Guide.

For summary information about the configuration, architecture, and features of RETL programs utilized in RMS/ReSA extractions, see the Oracle Retail Merchandising System Operations Guide Volume 3—Backend Configuration and Operations. For more information about the RETL tool, see the current RETL Programmer's Guide.


Legend




Note:

The modules in this flow are RDW RETL scripts. If the retailer uses RDW, this flow must be completed before starting the pre-batch maintenance flow. If the retailer does not use RDW, these jobs are not required.

RDW Maintenance




Pre-Batch Maintenance




Note:

salmth.pc resets the last eom_date. Thus, it must be run after the system indicator is extracted by pre_dwi_extract.ksh.


Post-Batch Maintenance




Dimension Dataflows




Dimension Dataflows




Supplier Dimension



Item-Supplier-Location Matrix Dimension




Dimension Dataflows




Dimension Dataflows


Product Season Dimension




Tender Type Dimension





Reason Dimension




Regionality Dimension




Fact Dataflows



Fact Dataflows





Stock Ledger




Note:
Run stock ledger fact loads once weekly.


Fact Dataflows



Return to Vendor




Net Cost




Fact Dataflows

Exchange Rates




Sales Forecasts




Note:
Run sales forecast fact loads
once weekly.


Fact Dataflows



Replacement




Fact Dataflows



Fact Dataflows

Supplier Compliance




Interface Diagram for RPM and RDW

This following program flow diagram shows the RETL extraction program that extracts the Promotion dimension from RPM through the Data Warehouse Interface (DWI). The diagram shows the output files and the scripts that interface with the source. Note that the outputs are based on the logic (dimension data and table data) of Oracle Retail Data Warehouse (RDW), but you can use the data to suit your business needs.


For detailed information about dimensions and facts, see the Oracle Retail Data Warehouse Operations Guide.


See the Oracle Retail Merchandising System Operations Guide Volume 1—Batch Overviews and Designs for more information about the modules shown in the following diagram.

Legend



Program Flow Diagram






Interface Diagram for ReIM and RDW

This following program flow diagram shows the RETL extraction program that extracts the Promotion dimension from ReIM through the Data Warehouse Interface (DWI). The diagram shows the output files and the scripts that interface with the source. Note that the outputs are based on the logic (dimension data and table data) of Oracle Retail Data Warehouse (RDW), but you can use the data to suit your business needs.


For detailed information about dimensions and facts, see the Retail Data Warehouse Operations Guide.

See the Oracle Retail Merchandising System Operations Guide Volume 1—Batch Overviews and Designs for more information about the modules shown in the following diagram.

Legend




Program Flow Diagram




Note:
The modules in this flow are RDW RETL scripts. If the retailer uses RDW, this flow must be completed before starting the pre-batch maintenance flow. If the retailer does not use RDW, these jobs are not required.

RDW Maintenance



Pre-Batch Maintenance



Note:
salmth.pc resets the last eom_date. Thus, it must be run after the system indicator is extracted by pre_dwi_extract.ksh.

Post-Batch Maintenance

