

Oracle® Retail Price Management
Installation Guide
Release 12.0.4

June 2007

Copyright © 2007, Oracle. All rights reserved.

Primary Author: Paul Kehler

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software – Restricted Rights (June 1987). Oracle Corporation, 500 Oracle Parkway, Redwood City, CA 94065

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

Oracle, JD Edwards, PeopleSoft, and Siebel are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

Value-Added Reseller (VAR) Language

- (i) the software component known as **ACUMATE** developed and licensed by Lucent Technologies Inc. of Murray Hill, New Jersey, to Oracle and imbedded in the Oracle Retail Predictive Application Server – Enterprise Engine, Oracle Retail Category Management, Oracle Retail Item Planning, Oracle Retail Merchandise Financial Planning, Oracle Retail Advanced Inventory Planning and Oracle Retail Demand Forecasting applications.
- (ii) the **MicroStrategy** Components developed and licensed by MicroStrategy Services Corporation (MicroStrategy) of McLean, Virginia to Oracle and imbedded in the MicroStrategy for Oracle Retail Data Warehouse and MicroStrategy for Oracle Retail Planning & Optimization applications.
- (iii) the **SeeBeyond** component developed and licensed by Sun Microsystems, Inc. (Sun) of Santa Clara, California, to Oracle and imbedded in the Oracle Retail Integration Bus application.
- (iv) the **Wavelink** component developed and licensed by Wavelink Corporation (Wavelink) of Kirkland, Washington, to Oracle and imbedded in Oracle Retail Store Inventory Management.
- (v) the software component known as **Crystal Enterprise Professional and/or Crystal Reports Professional** licensed by Business Objects Software Limited (“Business Objects”) and imbedded in Oracle Retail Store Inventory Management.
- (vi) the software component known as **Access Via™** licensed by Access Via of Seattle, Washington, and imbedded in Oracle Retail Signs and Oracle Retail Labels and Tags.
- (vii) the software component known as **Adobe Flex™** licensed by Adobe Systems Incorporated of San Jose, California, and imbedded in Oracle Retail Promotion Planning & Optimization application.
- (viii) the software component known as **Style Report™** developed and licensed by InetSoft Technology Corp. of Piscataway, New Jersey, to Oracle and imbedded in the Oracle Retail Value Chain Collaboration application.
- (ix) the software component known as **i-net Crystal-Clear™** developed and licensed by I-NET Software Inc. of Berlin, Germany, to Oracle and imbedded in the Oracle Retail Central Office and Oracle Retail Back Office applications.
- (x) the software component known as **WebLogic™** developed and licensed by BEA Systems, Inc. of San Jose, California, to Oracle and imbedded in the Oracle Retail Value Chain Collaboration application.
- (xi) the software component known as **DataBeacon™** developed and licensed by Cognos Incorporated of Ottawa, Ontario, Canada, to Oracle and imbedded in the Oracle Retail Value Chain Collaboration application.

Contents

Preface	vii
Audience	vii
Related Documents	vii
Customer Support	vii
Review Patch Documentation	vii
Oracle Retail Documentation on the Oracle Technology Network	viii
Conventions	viii
1 Pre-Installation Tasks.....	1
Check Application Server Requirements	1
Check Oracle Retail Software Dependencies.....	2
Supported Oracle Retail Products.....	2
Supported Oracle Retail Integration Technologies	2
Check Third-Party Software Dependencies	2
Check Client PC and Web Browser Requirements	3
Client PC Requirements.....	3
Browser Requirements.....	3
2 RAC and Clustering	5
3 Database Installation Tasks.....	7
RPM Schema	7
RSM Schema	7
4 Application Installation UNIX (Sun Solaris/AIX/HP-UX)	9
Create a New OC4J Instance for RPM	9
Configure Apache for JNLP Files.....	10
Expand the RPM Application Distribution	11
Provide the Hibernate Jar File.....	11
Clustered Installations – Pre-Install Steps.....	11
Run the RPM Application Installer.....	12
Resolving Errors Encountered During Application Installation	12
Clustered Installations – Post-Install Steps	13
Manual Deployment Option	14
Sign the RPM Client Configuration Jar File	15
Backups Created by Installer	15
Test the RPM Application	16
RPM Batch Scripts.....	16
Web Help Files	16
Re-Generating JMS Bindings with BinDEGateJMSQueue.jar.....	16

A	Appendix: RPM Application Installer Screens.....	17
B	Appendix: Installer Silent Mode	35
	Repeating an Installation Attempt.....	35
C	Appendix: Common Installation Errors.....	37
	SeeBeyond JMS Unavailable.....	37
	Keystore Errors When Signing rpm_client_config.jar.....	37
	Unreadable Buttons in the Installer.....	37
	“Unable to get a deployment manager” Message	38
	Left-Side Menu Buttons Missing in RPM Client.....	38
	“Could not create system preferences directory” Warning.....	38
D	Appendix: URL Reference	39
	JDBC URL for a Database.....	39
	HTTP URL for a WebStart Client	39
	JNDI Provider URL for an Application	39
	Deployer URI.....	40

Preface

Oracle Retail Installation Guides contain the requirements and procedures that are necessary for the retailer to install Oracle Retail products.

Audience

This Installation Guide is written for the following audiences:

- Database administrators (DBA)
- System analysts and designers
- Integrators and implementation staff

Related Documents

For more information, see the following documents in the Oracle Retail Price Management Release 12.0.4 documentation set:

- Oracle Retail Price Management Operations Guide
- Oracle Retail Price Management Release Notes
- Oracle Retail Price Management User Guide
- Oracle Retail Price Management Online Help
- Oracle Retail Price Management Data Model

Customer Support

- <https://metalink.oracle.com>

When contacting Customer Support, please provide:

- Product version and program/module name.
- Functional and technical description of the problem (include business impact).
- Detailed step-by-step instructions to recreate.
- Exact error message received.
- Screen shots of each step you take.

Review Patch Documentation

For a base release ("0" release, such as 12.0), Oracle Retail strongly recommends that you read all patch documentation before you begin installation procedures. Patch documentation can contain critical information related to the base release, based on new information and code changes that have been made since the base release.

Oracle Retail Documentation on the Oracle Technology Network

In addition to being packaged with each product release (on the base or patch level), all Oracle Retail documentation is available on the following Web site:

http://www.oracle.com/technology/documentation/oracle_retail.html

Documentation should be available on this Web site within a month after a product release. Note that documentation is always available with the packaged code on the release date.

Conventions

Navigate: This is a navigate statement. It tells you how to get to the start of the procedure and ends with a screen shot of the starting point and the statement “the Window Name window opens.”

Note: This is a note. It is used to call out information that is important, but not necessarily part of the procedure.

This is a code sample
It is used to display examples of code

A hyperlink appears like this.

Pre-Installation Tasks

RPM is a client-server-server application. Its client side code runs in a WebStart Java Virtual machine instance, while its server side code runs in the Oracle Application Server and accesses an Oracle Database server.

Check Application Server Requirements

General requirements for an application server capable of running the RPM application include:

- UNIX based OS (Solaris 9 (SPARC), HP-UX 11.23 (PARISC), AIX 5.2, or AIX 5.3) certified with Oracle Application Server 10g 10.1.3..
- Oracle Application Server 10g 10.1.3 with the following patches:
 - 4992357 (ILLEGALACCESSERROR WHEN ATTEMPTING TO LOAD ORACLE.SQL.CHARACTERSET CLASS)
 - 4959854 (CANNOT RESTART MDB THROUGH OC4J ASCONSOLE)
 - 4645524 (RETEK : RMIINITIALCONTEXTFACTORY DOES NOT WORK PROPERLY WITH GLOBAL JNDI)
 - 4619599 (ABILITY TO CONTROL MDBS INITIAL STATE)

Note: This release of RPM is only supported in a managed OC4J instance as part of OracleAS 10g. It is not supported on OC4J standalone

- Oracle Enterprise Linux requirements

Operating System Version:

- Oracle Enterprise Linux 4 Update 4 for x86-64
- Minimum kernel version kernel-smp-2.6.9-42.0.0.0.1.EL.x86_64

Oracle RDBMS

- Oracle RDBMS 10g Release 2 Enterprise Edition for Linux x86-64
- Minimum 10.2.0.3 patchset
- Patches:
 - 5397953 (ORA-07445: [KKPAPITGETALL()+2152] [SIGSEGV] [ADDRESS NOT MAPPED TO OBJECT])
 - 5921386 WRONG RESULT WITH MERGE JOINT OUTER IN THE EXECUTION PLAN

Oracle Application Server

- Oracle Application Server 10g Release 2 (10.1.2.0.2) for Linux x86
- Oracle Application Server 10g Release 3 (10.1.3.0) for Linux x86

Oracle Retail Price Matching

- Configured with “No RIB” option

Check Oracle Retail Software Dependencies

- RMS 12.0.4 must be installed prior to installing RPM.
- Security Manager (RSM) 12.0.2 must be installed prior to installing RPM. There is a set of RPM-specific data scripts that must be run in the RSM schema. These scripts are included with the RMS 12.0.4 product distribution.
- An eGate JMS server for the RPM task queue. The eGate JMS used by the RIB or a separate eGate JMS can be used for this. The JMS server must be running at the time of the RPM application installation. RPM application deployment will fail if JMS is down.

Supported Oracle Retail Products

Requirement	Version
Oracle Retail Merchandising System (RMS)/Oracle Retail Trade Management (RTM)/Oracle Retail Sales Audit (ReSA)	12.0.4
Oracle Retail Allocation	12.0.4
Oracle Retail Data Warehouse (RDW)	12.0.0.1
Oracle Retail Store Inventory Management (SIM)	11.1.1 (at a minimum)
Oracle Retail Security Manager (RSM)	12.0.2

Supported Oracle Retail Integration Technologies

Requirement	Version
Oracle Retail Extract, Transform and Load (RETL)	12.0.1
Oracle Retail Integration Bus (RIB)	12.0.1
Oracle Retail Service Layer (RSL)	12.0.1

Check Third-Party Software Dependencies

- Hibernate 2.1.8 must be downloaded and the hibernate2.jar file just be extracted. The RPM application installation procedure specifies how to install this file.

Check Client PC and Web Browser Requirements

Client PC Requirements

- Operating system is Windows 2000 or XP
- Display resolution is 1024x768 or higher
- Processor is 1GHz or higher
- Memory is 512MBytes or higher;
- Networking is intranet with at least 10Mbps data rate
- Sun J2RE Runtime 1.4.2 or higher

Browser Requirements

- Microsoft Internet Explorer 5.5 or higher

RAC and Clustering

Real Application Cluster RDBMS & Oracle Application Server Clustering for Oracle Retail Price Matching has been validated to run only on Linux:

The Oracle Retail products have been validated against a 10.2.0.3 RAC database. When using a RAC database, all JDBC connections should be configured to use OCI connections rather than THIN connections. It is suggested that when using OCI connections, the Oracle Retail products database be configured in the tnsnames.ora file used by the Oracle Application Server installations.

Clustering for Oracle Application Server 10.1.3 is managed as an Active-Active cluster accessed through a hardware Load Balancer. It is suggested that a VirtualHost be added to the OAS 10.1.3 reflecting the Virtual Server Name configured in the load balancer. It is also suggested that the OC4J select method be configured to prefer the use of local OC4J instances. The Oracle Retail products are currently not validated to be distributable at the application level in an OAS 10.1.3 cluster.

Clustering for Oracle Application Server 10.1.2.0.2 is managed as an Active-Active cluster accessed through a hardware Load Balancer. It is suggested that the Web Cache installation included with OAS 10.1.2.0.2 be configured to reflect all application server Mid-Tier installations. Validation has been completed utilizing a RAC 10.2.0.3 Oracle Internet Directory database with the OAS 10.1.2.0.2 cluster.

References for Configuration:

- Oracle® Application Server High Availability Guide 10g Release 3 (10.1.3) Part Number B15977-02
- Oracle® Application Server High Availability Guide 10g Release 2 (10.1.2) Part Number B14003-05
- Oracle® Database Oracle Clusterware and Oracle Real Application Clusters Administration and Deployment Guide 10g Release 2 (10.2) Part Number B14197-03

Database Installation Tasks

RPM Schema

The RPM database tables are installed with the RMS database schema. RMS 12.0.4 is a prerequisite of the RPM 12.0.4 installation.

RSM Schema

The RSM 12.0.2 application is a prerequisite of RPM 12.0.4. There are database scripts that are included in the RMS distribution which need to be run in the RSM schema to load RPM-specific permissions data. You must run these scripts in the RSM schema before installing the RPM application.

Application Installation UNIX (Sun Solaris/AIX/HP-UX)

These instructions apply to new installations and upgrades. If you are upgrading a previous 12.0.x installation, the application installer will upgrade the application and back up certain files from the previous installation (See *Backups Created by the Installer* from this section). To ensure that the previous installation is properly undeployed, you must provide the same application deployment name as the previous installation.

Before proceeding you must install Oracle Application Server 10g 10.1.3 plus the patches listed in Chapter 1 of this document. The RPM application will be deployed to an OC4J instance within the OracleAS10g installation. You must also have the Java 1.4.2 SDK installed on your system.

It is assumed Oracle RDBMS has already been configured and loaded with the appropriate RMS schema for your installation.

Create a New OC4J Instance for RPM

You can skip this section if you are redeploying to an existing OC4J instance.

The RPM application must be deployed to its own dedicated OC4J instance. For instructions on how to create a new OC4J instance, see *Adding and Deleting OC4J Instances* in the *Reconfiguring Application Server Instances* chapter of the *Oracle Application Server Administrator's Guide*.

1. Log into the server which is running your OracleAS10g installation. Set your ORACLE_HOME environment variable to point to this installation.
2. Choose a name for the new OC4J instance.

Example: rpm-oc4j-instance

Create this OC4J instance as documented in the Oracle Application Server Administrator's Guide.

Example:

```
$ORACLE_HOME/bin/createinstance  
-instanceName rpm-oc4j-instance
```

When prompted for the oc4jadmin password, provide the same administrative password you gave for the OracleAS installation. All OC4J instances running Oracle Retail applications must have the same oc4jadmin password.

3. Configure the JDK for this OC4J instance. By default, new OC4J instances use the Java 1.5 JDK that is shipped with the application server. This release of RPM requires Java 1.4.2.

For instructions on how to change the JDK for an OC4J instance, see the *Specifying the JDK in a Managed Configuration* section of the OC4J Runtime Configuration chapter of the Oracle Containers for J2EE Configuration and Administration Guide.

4. (AIX only) If the OracleAS installation is on AIX, you must set the **ibm.cl.eagerresolution** property in \$ORACLE_HOME/opmn/conf/opmn.xml. Add the definition of this property to the startup **java-options** for the OC4J instance.

Example:

```
<process-type id="rpm-oc4j-instance" module-id="OC4J" status="enabled">
  <module-data>
    <category id="start-parameters">
      <data id="java-bin" value="/usr/java14/bin/java"/>
      <data id="java-options" value="-Dibm.cl.eagerresolution
-Djava.security.policy=$ORACLE_HOME/j2ee/rpm-oc4j-
instance/config/java2.policy -Dhttp.webdir.enable=false"/>
    </category>
  </module-data>
</process-type>
```

Force OPMN to reload the configuration file.

Example: \$ORACLE_HOME/opmn/bin/opmnctl reload

5. Start the OC4J instance. You can do this through the Enterprise Manager web interface, or on the command line using the opmnctl utility:

Example: \$ORACLE_HOME/opmn/bin/opmnctl
startproc process-type=rpm-oc4j-instance

6. Verify that the OC4J instance was fully started. If you are using the Enterprise Manager web interface, the instance should have a green arrow indicating that it is running. On the command line, verify that the instance has a status of "Alive".

Example: \$ORACLE_HOME/opmn/bin/opmnctl status

If you are unable to start the OC4J instance after several attempts, try increasing the startup timeouts in ORACLE_HOME/opmn/conf/opmn.xml. If that does not help, consult the Oracle Application Server documentation for further assistance.

Configure Apache for JNLP Files

If this is the first WebStart application that is being installed in the HTTP server, you need to configure the **mime.types** file with the jnlp file type. If you are using the Apache distribution that is included with OracleAS, this file can be found under ORACLE_HOME/Apache/Apache/conf. Add the following line to the file:

```
application/x-java-jnlp-file      jnlp
```

Restart the Apache server for this change to take effect. If you do not add this line then jnlp files will be served as plain text and you will not be able to launch the application.

Example: \$ORACLE_HOME/opmn/bin/opmnctl
restartproc process-type=HTTP_Server

Expand the RPM Application Distribution

1. Log into the UNIX server as the user who owns the OracleAS 10g installation. Create a new staging directory for the RPM application distribution (rpm12application.zip). There should be a minimum of 160 MB disk space available for the application installation files.

Example: \$ORACLE_HOME/j2ee/rpm-oc4j-instance/rpm-staging

This location is referred to as `INSTALL_DIR` for the remainder of this chapter.

2. Copy rpm12application.zip to `INSTALL_DIR` and extract its contents.

Provide the Hibernate Jar File

The RPM application requires the hibernate2.jar file to be installed. This file should be downloaded from <http://www.hibernate.org> and placed in the `INSTALL_DIR/rpm/application/hibernate` folder before the installer is launched. For RPM 12, Hibernate 2.1.8 should be used. You need to download the Hibernate distribution and extract the hibernate2.jar file from it.

The RPM application installer verifies that hibernate2.jar has been provided and that it is the correct version. If hibernate2.jar is missing or incorrect, the installer will not proceed.

The installer applies hibernate2.jar to the RPM application by placing it under the `ORACLE_HOME/j2ee/<oc4j-instance-name>/applications/<app-name>/lib` directory.

Clustered Installations – Pre-Install Steps

Skip this section if you are not clustering the application server.

All OC4J instances in the group must have the same instance name. The group must also be named identically to these OC4J instances. For example, you might have a group named “rpm-oc4j-instance” whose members are all OC4J instances named “rpm-oc4j-instance” on different `ORACLE_HOME`’s.

If you are installing the RPM application to a clustered Oracle Application Server environment, there are some extra steps you need to take before running the RPM application installer. In these instructions, the application server node whose `ORACLE_HOME` you used for the RPM installer is referred to as the *master node*. All other nodes are referred to as the *remote nodes*.

1. On each node, create the RPM task queue in the OC4J JMS server by modifying the `$ORACLE_HOME/j2ee/<rpmoc4jinstance>/config/jms.xml` file. At the bottom of this file, before the closing `</jms-server>` tag, add the definition for the RPM task queue. Prefix the queue name with **jms/** as shown in the example below.

Example with rpmTaskQueue as the queue name:

```
<queue name="jms/rpmTaskQueue" location="jms/rpmTaskQueue">
  <description/>
</queue>
</jms-server>
```

The RPM application installer asks you for this queue name. You must provide the same queue name that you used in `jms.xml`, without the `jms/` prefix.

Example: rpmTaskQueue

2. All of the OC4J instances in the group should be restarted for the `jms.xml` changes to be picked up. Deployment of the RPM ear file will fail if the JMS queue cannot be found by OC4J.

Example: `$ORACLE_HOME/opmn/bin/opmnctl @cluster
restartproc process-type=rpm-oc4j-instance`

Run the RPM Application Installer

Once you have an OC4J instance that is configured and started, you can run the RPM application installer. This installer configures and deploys the RPM application and Java WebStart client files.

Note: Appendix A contains details on every screen and field in the application installer.

1. Make sure that the eGate JMS server is running. This server is needed for the task queue used by the RPM application. The application server verifies the JMS connection during deployment of the RPM ear file, and the deployment will fail if it cannot connect.
2. Change directories to `INSTALL_DIR/rpm/application`.
3. Set the `ORACLE_HOME` and `JAVA_HOME` environment variables. `ORACLE_HOME` should point to your OracleAS installation. `JAVA_HOME` should point to a Java 1.4.2 JDK. The installer is not compatible with earlier versions of Java.
4. If you are using an X server such as Exceed, set the `DISPLAY` environment variable so that you can run the installer in GUI mode (recommended). If you are not using an X server, or the GUI is too slow over your network, unset `DISPLAY` for text mode.
5. Run the `install.sh` script. This launches the installer. After installation is complete, a detailed installation log file is created: `rpm12install.<timestamp>.log`.

Resolving Errors Encountered During Application Installation

If the application installer encounters any errors, it halts execution immediately. You can run the installer in silent mode so that you don't have to retype the settings for your environment. See Appendix B of this document for instructions on silent mode.

See Appendix C of this document for some common installation errors.

Since the application installation is a full reinstall every time, any previous partial installs will be overwritten by the successful installation.

Clustered Installations – Post-Install Steps

If you are installing the RPM application to a clustered Oracle Application Server environment, there are some extra steps you need to take to complete the installation. In these instructions, the application server node whose ORACLE_HOME you used for the RPM installer is referred to as the *master node*. All other nodes are referred to as the *remote nodes*.

1. The RPM client files should be copied from the master node to each of the remote nodes under the same path as on the master node. For example, you should take the files under \$ORACLE_HOME/Apache/Apache/rpm and copy them onto the remote nodes under the same path.
2. All jnlp files in the RPM client needs to be modified so that the correct host name is used on each node.
3. The RPM batch files should be copied from the master node to each of the remote nodes under the same path as on the master node. You should take the \$ORACLE_HOME/j2ee/<rpminstance>/rpm-batch directory and copy it onto the remote nodes under the same path.
4. The launchRpmBatch.sh script should be modified on each remote node to point to the local RPM instance. The RPM URL is set in the PROVIDER_URL variable. This script is located at \$ORACLE_HOME/j2ee/<rpminstance>/rpm-batch/scripts/launchRpmBatch.sh.
5. By default, after installation all remote RPM instances are pointing to the RSM install on the master node. Update the RSM URL in the jndi_providers.xml file on each remote node so that each RPM instance uses its own local RSM instance. This file is located at \$ORACLE_HOME/j2ee/<oc4jinstance>/applications/<rpmappname>/conf/retek/jndi_providers.xml.
6. All of the OC4J instances in the group should be restarted for the jndi_providers.xml changes to be picked up.

Example: \$ORACLE_HOME/opmn/bin/opmnctl @cluster
restartproc process-type=rpm-oc4j-instance

Manual Deployment Option

Skip this section if you chose the default option of allowing the installer to complete installation to the application server.

The installer includes the option to configure the application locally and skip deployment to the application server. If this option is chosen, the installer makes the configured application files available under `<INSTALL_DIR>/rpm/application/rpm12/configured-output/`.

If you chose this installer option, you can complete the installation by following these steps:

1. Make sure there have not been any application server configuration changes since the installer was run. You can do this by comparing the backup files created by the installer in the staging area to the same files in the application server.

Example:

```
diff <INSTALL_DIR>/rpm/application/rpm12
/configured-
output/appserver/ORACLE_HOME/j2ee/myinstance/conf
ig/jms.xml.200610300919
$ORACLE_HOME/j2ee/myinstance/conf/jms.xml
```

If there are changes to the application server's configuration file, they should be merged into the local copy under configured-output before proceeding to the next step.

2. Inspect the contents of the `<INSTALL_DIR>/rpm/application/rpm12/configured-output/appserver/ORACLE_HOME` directory, and then overlay the files in the application server's `ORACLE_HOME`, using the same directory structure. This installs library files required by the application and required application server configuration changes.
3. Restart the OC4J instance where RPM will be deployed.

Example:

```
$ORACLE_HOME/opmn/bin/opmnctl
restartproc process-type=rpm-oc4j-instance
```

4. Deploy the RPM ear file using the Enterprise Manager web interface. The configured ear file is located at `<INSTALL_DIR>/rpm/application/rpm12/configured-output/rpm12.ear`. When deploying the ear file, you should provide the same application name you gave to the installer. These values were stored in the `<INSTALL_DIR>/rpm/application/ant.install.properties` file by the installer for later reference.

Sign the RPM Client Configuration Jar File

There is some client-side configuration that the installer performs which results in a modified `rpm_client_config.jar` file after installation. Because of this, the jar file cannot be pre-signed by Oracle. The user must sign this jar file after the installer has completed.

To create an example key called "foo", the following command can be run:

```
$JAVA_HOME/bin/keytool -genkey -alias foo
```

This command prompts you for a keystore password along with organizational info.

Once complete, the keystore alias resides in the default location in the user's home directory (ie `~/.keystore`). If you get an error message saying that the keystore has been tampered with, try renaming or deleting the `~/.keystore` file and running the `keytool` command again.

If during execution of the installer you chose to manually copy the client files to the HTTP server, you should do so before signing the `rpm_client_config.jar` file.

The `rpm_client_config.jar` is located on the HTTP server under the 'lib' subdirectory of the RPM client destination directory. To sign the `rpm_client_config.jar` file using your alias and keystore, run the `jarsigner` utility.

Example: `$JAVA_HOME/bin/jarsigner`
`rpm_client_config.jar foo`

Consult the "jarsigner" documentation from Sun for further information on the JAR signing process.

Backups Created by Installer

The RPM application installer backs up previous batch, JMS bindings, and WebStart client installations by renaming them with `<timestamp>` suffixes. This is done to prevent the removal of any custom changes you might have. These backup directories can be safely removed without affecting the current installation.

Examples: `rpm-batch.200605011726`,
`sbynjndi.200605011726`, `rpm.200605011726`

Test the RPM Application

After the application installer completes you should have a working RPM application installation. To launch the application client, open a web browser and go to the rpm.jnlp file under the HTTP url you provided during the installation.

Example: <http://myhost:7777/rpm/rpm.jnlp>

RPM also includes a status page application which can be used to verify the installation. For details see the RPM Operations Guide, under the *Price Management Status Page* section.

RPM Batch Scripts

The RPM application installer configures and installs the batch scripts under ORACLE_HOME/j2ee/<instance>/rpm-batch.

Web Help Files

The application installer automatically copies the web help files to the proper location. They are accessible from the help links within the application.

Re-Generating JMS Bindings with BindEGateJMSQueue.jar

The RPM application installer creates the ORACLE_HOME/j2ee/<oc4jinstance>/sbynjndi directory and runs the **BindEGateJMSQueue.jar** utility to bind its JMS queue. This file is located in the RPM application distribution under the rpm12/sbynjndi directory. Below are instructions on how to run this utility by itself at a later time to update the JMS host, port, and queue.

1. Set the JAVA_HOME environment variable so that it points to a 1.4.2 JDK.
2. Change directories to ORACLE_HOME/j2ee/<oc4j instance>/sbynjndi and run BindEGateJMSQueue.jar:

Usage: BindEGateJMSQueue -q <jms queue> -h <jms host> -p <jms port> -d
<output directory>

jms queue: Name of the JMS queue to use. This is not the full JNDI name of the queue. The JNDI name of the queue will become jms/Generic/Queue/<jms queue>.

jms host: eGate JMS server

jms port: eGate JMS port

output directory: directory where the .bindings files will be created.

Example: java -jar BindEGateJMSQueue.jar -q
rpmTaskQueue -h jmshost -p 27053 -d
\$ORACLE_HOME/j2ee/rpm-oc4j-instance/sbynjndi

The RPM application uses these .bindings files to locate and communicate with the e*Gate JMS server.

Appendix: RPM Application Installer Screens

You need the following details about your environment for the installer to successfully deploy the RPM application. Depending on the options you select, you may not see some screens or fields.

Screen: Data Source Details

The screenshot shows a window titled "Price Management 12 Installer - Oracle Retail". Inside the window, there is an "ORACLE" logo and the word "RETAIL" below it. The main section is titled "Data Source Details" and contains the instruction "Provide the details for the RPM data source". There are four input fields: "RMS 12 JDBC URL" with a placeholder "jdbc:oracle:thin:@[host]:[port]:[dbname]", "RMS 12 schema", "RMS 12 schema password", and "RMS 12 schema owner". A note states: "Enter the RMS schema owner. This is usually the same as the RMS schema entered above". At the bottom, there are four buttons: "Cancel", "<< Back", "Next >>", and "Install".

Data Source Details	
Provide the details for the RPM data source	
RMS 12 JDBC URL	jdbc:oracle:thin:@[host]:[port]:[dbname]
RMS 12 schema	
RMS 12 schema password	
Enter the RMS schema owner. This is usually the same as the RMS schema entered above	
RMS 12 schema owner	
Cancel << Back Next >> Install	

Fields on this screen:

Field Title	RMS 12 JDBC URL
Field Description	URL used by the RPM application to access the RMS database schema. See Appendix D: URL Reference for expected syntax. Note: The RPM database tables are a part of the RMS schema.
Destination	data-sources.xml
Example	jdbc:oracle:thin:@myhost:1525:mydatabase
Notes	

Field Title	RMS 12 schema
Field Description	Database user where the RMS database schema was installed.
Destination	data-sources.xml
Example	RMS12
Notes	

Field Title	RMS 12 schema password
Field Description	Password for the RMS schema user.
Destination	data-sources.xml
Notes	

Field Title	RMS 12 schema owner
Field Description	Database user which owns the RMS tables. This is usually the same as the RMS 12 schema above.
Destination	rpm.properties
Example	RMS12
Notes	

Screen: JMS Provider

Price Management 12 Installer - Oracle Retail

ORACLE

RETAIL

JMS Provider

RPM uses a JMS queue. This queue can be created in the built-in JMS for OC4J, or it can be created in an external SeeBeyond e*Gate JMS server

JMS Provider ☒ OracleAS JMS (built into OC4J)

☐ SeeBeyond e*Gate JMS

Enter the name for the queue used by this RPM application. This is not a fully qualified JNDI name. The JNDI name will be constructed using this queue name The default value is given as an example.

Task Queue Name

Cancel

<< Back

Next >>

Install

Fields on this screen:

Field Title	JMS Provider
Field Description	RPM is compatible with two different JMS vendors: SeeBeyond e*Gate and the OC4J JMS. If you are running a SeeBeyond e*Gate JMS server for the RIB, you can use that same JMS server for RPM's JMS functionality. Alternatively, you can also use OracleAS JMS, which is the JMS server provided within OC4J.
Destination	
Example	OracleAS JMS
Notes	

Field Title	Task Queue Name
Field Description	Name by which the task queue will be identified. If this is a new RPM environment, choose a queue name that is not already in use in the JMS server. If you have already created the queue in the JMS server as part of the Clustering Pre-Install steps, you must provide the same name in this field (without the jms/ prefix). Note: This is not a complete JNDI name. The value provided will be appended to jms/Generic/Queue/ (eGate) or jms/ (OC4J) to form the full JNDI name for the queue.
Destination	system.properties, oc4j-connectors.xml, orion-ejb-jar.xml (platform-mdb.jar), input to BindEGateJMSQueue.jar (eGate) , jms.xml (OC4J)
Example	rpmTaskQueue
Notes	

Screen: eGate JMS Settings


The screenshot shows a window titled "Price Management 12 Installer - Oracle Retail". Inside the window, there is a section titled "eGate JMS Settings". Below this title, there is a text prompt: "Enter the JMS server details. The JMS server MUST be running during this RPM installation". There are two input fields: "JMS host" and "JMS port". At the bottom of the window, there are four buttons: "Cancel", "<< Back", "Next >>", and "Install".

Fields on this screen:

Field Title	JMS host
Field Description	hostname of the SeeBeyond e*Gate JMS server
Destination	input to BindEGateJMSQueue
Example	myhost
Notes	

Field Title	JMS port
Field Description	JMS port of the SeeBeyond e*Gate JMS server
Destination	input to BindEGateJMSQueue
Example	24053
Notes	


Screen: Manual Deployment Option



Fields on this screen:

Field Title	Install files to app server?
Field Description	If you do not have write access under ORACLE_HOME, you can still use the installer to gather your settings and configure the RPM files locally in the staging area. Then, at a later time, an administrator can manually copy over the RPM files and deploy the ear file. If you select this option, instructions are printed to the console and the installer log file for the steps needed to complete the installation.
Destination	
Example	
Notes	

Screen: Client files on the HTTP server



Fields on this screen:

Field Title	Do you want the installer to copy the client files to the HTTP server?
Field Description	If the HTTP server that is serving the rpm.jnlp file is on the same host as the application server, then answer yes to this question so that the installer copies the client files to the HTTP server directories. The answer is usually yes since the RPM client files are usually installed to the Oracle Http Server that is a part of the same ORACLE_HOME as the OC4J instance running the RPM application. If the HTTP server is on a separate host, then you will have to manually copy the client files over. Copy the contents of INSTALL_DIR/rpm/application/rpm12/webstart under a new folder on the HTTP server.
Notes	

Screen: Client Destination Directory

Price Management 12 Installer - Oracle Retail

ORACLE
RETAIL

Client Destination Directory

Enter the fully-qualified path to the destination directory for the client files. This will be the parent directory of the rpm.jnlp file.

Directory path for RPM client

Enter the HTTP URL that will be used to access the above destination directory.

HTTP base URL for RPM client


Cancel << Back Next >> Install

Fields on this screen:

Field Title	Directory path for RPM client
Field Description	This is the fully-qualified path to the location in the HTTP server where the RPM client files are to be installed. The directory provided will be the parent directory of rpm.jnlp. By default, this path will point to an 'rpm' subdirectory of the document root of the Oracle Http Server that is a part of the OracleAS installation (ORACLE_HOME/Apache/Apache/htdocs). This field is only shown if you selected "yes" to the previous question (Do you want the installer to copy the client files to the HTTP server?)
Example	/path/to/oracle/home/Apache/Apache/htdocs/rsm

Field Title	HTTP base URL for RPM client
Field Description	URL which you can use to locate the RPM client files using a web browser. This URL should lead to the same directory that was given for the Directory path for RPM client field above. If you chose not to have the installer copy the client files over, this URL should point to the location where you will manually copy them after the installer has completed.. See Appendix D: URL Reference for expected syntax. This parameter can be changed later by modifying the *.jnlp files on the client side.
Destination	rpm.jnlp, rpmconfig.jnlp
Example	http://myhost:7777/rpm
Notes	

Screen: OC4J Server Type: Managed or Standalone?



Fields on this screen:

Field Title	Which type of OC4J server are you deploying to?
Field Description	A managed OC4J server is part of a larger Oracle App Server enterprise environment and is managed by OPMN. A standalone OC4J server is a single instance installed by itself and is not controlled by OPMN. This Oracle Retail application release is only supported on managed OC4J.
Example	managed
Notes	

Screen: Application Server Details - OracleAS Enterprise

Price Management 12 Installer - Oracle Retail

ORACLE
RETAIL

Application Server Details - OracleAS Enterprise

Hostname

The OPMN request port is found in ORACLE_HOME/opmn/conf/opmn.xml

OPMN request port

Cancel << Back Next >> Install

Fields on this screen:

Field Title	Hostname
Field Description	Hostname of the application server
Example	myhost
Notes	
Field Title	OPMN request port
Field Description	Port on which OPMN listens for requests to forward on to OC4J instances. This port can be found in the ORACLE_HOME/opmn/conf/opmn.xml file: <code><port local="6100" remote="6200" request="6003"/></code>
Example	6003
Notes	

Screen: Application Server Details - OC4J Standalone

Price Management 12 Installer - Oracle Retail

ORACLE
RETAIL

Application Server Details - OC4J Standalone

Hostname

Enter the RMI port for the OC4J standalone server. The RMI port can be found in the ORACLE_HOME/j2ee/home/config/rmi.xml file.

OC4J RMI port

Cancel << Back Next >> Install

Fields on this screen:

Field Title	Hostname
Field Description	Hostname of the application server
Example	myhost
Notes	

Field Title	OC4J RMI port
Field Description	Port on which the standalone OC4J server listens for connections. This setting can be found in the ORACLE_HOME/j2ee/home/config/rmi.xml file. <pre><rmi-server xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:noNamespaceSchemaLocation="http://xmlns.oracle.com/oracleas/schema/rmi-server-10_0.xsd" port="23791"</pre>
Example	23791
Notes	

Screen: Application Deployment Details

Price Management 12 Installer - Oracle Retail

ORACLE
RETAIL

Application Deployment Details

Provide the following details for the RPM application being installed.
The default values shown below are examples.

RPM 12 OC4J instance

RPM 12 app deployment name

Cancel << Back Next >> Install

Fields on this screen:

Field Title	RPM 12 OC4J instance
Field Description	Name of the OC4J instance that was created for this RPM application.
Example	rpm-oc4j-instance
Notes	
Field Title	RPM 12 app deployment name
Field Description	Name by which this RPM application will be identified in the application server
Example	rpm12
Notes	

Screen: Other Oracle Retail Applications - OracleAS Enterprise

Price Management 12 Installer - Oracle Retail

ORACLE
RETAIL

Other Oracle Retail Applications - OracleAS Enterprise

The default values shown below are examples

Provide the following details for the other apps that will integrate with RPM.

RSM 12 OC4J instance: rsm-oc4j-instance

RSM 12 app deployment name: rsm12

RIBforRPM 12 OC4J instance: rib-rpm-oc4j-instance

RIBforRPM 12 deployment name: rib-rpm

Buttons: Cancel, << Back, Next >>, Install

Fields on this screen:

Field Title	RSM 12 OC4J instance
Field Description	Name of the OC4J instance running the Security Manager (RSM) application. RSM is a requirement of RPM.
Example	rsm-oc4j-instance
Notes	
Field Title	RSM 12 app deployment name
Field Description	Application deployment name of the Security Manager (RSM) application.
Example	rsm12
Notes	

Field Title	RIBforRPM 12 OC4J instance
Field Description	Name of the OC4J instance running the RIBforRPM application. RIBforRPM provides the connection between RPM and the RIB (Retail Integration Bus), and is optional. See the RPM 12.0 Operations Guide for details on how to configure RPM without the RIB.
Example	rib-rpm-oc4j-instance
Notes	

Field Title	RIBforRPM 12 deployment name
Field Description	Application deployment name of the RIBforRPM application. See the above note about RIBforRPM under RIBforRPM 12 OC4J Instance.
Example	rib-rpm
Notes	

Screen: OC4J Administrative User

Price Management 12 Installer - Oracle Retail

ORACLE
RETAIL

OC4J Administrative User

Enter the administrative user and password for the OC4J instance to which the RPM application will be deployed.

OC4J admin user: oc4jadmin

OC4J admin password:

Buttons: Cancel, << Back, Next >>, Install

Fields on this screen:

Field Title	OC4J admin user
Field Description	Username of the admin user for OC4J instance to which the RPM application is being deployed.
Example	oc4jadmin
Notes	

Field Title	OC4J admin password
Field Description	Password for the OC4J admin user. You chose this password when you created the OC4J instance (managed OC4J) or when you started the instance for the first time (standalone OC4J).
Notes	

Screen: Oracle Retail Application URLs

Price Management 12 Installer - Oracle Retail

ORACLE
RETAIL

Oracle Retail Application URLs

Provide or modify the URLs for other Oracle Retail applications below

RPM 12 JNDI provider URL: :ormi://mspdev34:6003:rpm-oc4j-instance/rpm12

RSM 12 JNDI provider URL: :ormi://mspdev34:6003:rsm-oc4j-instance/rsm12

RIBforRPM 12 JNDI provider URL: //mspdev34:6003:rib-rpm-oc4j-instance/rib-rpm

Cancel << Back Next >> Install

Fields on this screen:

Field Title	RPM 12 JNDI provider URL
Field Description	URL which the RPM client uses to find the RPM application. See Appendix D: URL Reference for expected syntax.
Destination	rpm.jnlp, launchRpmBatch.sh
Example	opmn:ormi://myhost:6003:rpm-oc4j-instance/rpm12
Notes	

Field Title	RSM 12 JNDI provider URL
Field Description	URL which the RPM application uses to find the RSM application. See Appendix D: URL Reference for expected syntax.
Destination	jndi_providers.xml
Example	opmn:ormi://myhost:6003:rsm-oc4j-instance/rsm12
Notes	

Field Title	RIBforRPM 12 JNDI provider URL
Field Description	URL which the RPM application uses to find the RIBforRPM application. See Appendix D: URL Reference for expected syntax. RIBforRPM provides the connection between RPM and the RIB (Retail Integration Bus), and is optional. See the RPM 12.0 Operations Guide for details on how to configure RPM without the RIB.
Destination	jndi_providers.xml
Example	opmn:ormi://myhost:6003:rib-rpm-oc4j-instance/rib-rpm
Notes	

Appendix: Installer Silent Mode

Repeating an Installation Attempt

In addition to the GUI and text interfaces of the RPM installer, there is a silent mode that can be run. This mode is useful if you wish to run a repeat installation without retyping the settings you provided in the previous installation. It is also useful if you encounter errors in the middle of an installation and wish to continue.

The installer runs in two distinct phases. The first phase involves gathering settings from the user. At the end of the first phase, a properties file named `ant.install.properties` is created with the settings that were provided. Then the second phase begins, where this properties file is used to provide your settings for the installation.

To skip the first phase and re-use the `ant.install.properties` file from a previous run, follow these instructions:

1. Edit the `ant.install.properties` file and correct any invalid settings that may have caused the installer to fail in its previous run.
2. Run the installer again with the **silent** argument.

Example: `install.sh silent`

Appendix: Common Installation Errors

This section provides some common errors encountered during installation of RPM.

SeeBeyond JMS Unavailable

Error message:

```
[1013AS_1.mspdev27] 06/04/29 23:23:46 Notification ==>application: rpm12 is in failed state
```

```
[1013AS_1.mspdev27] 06/04/29 23:23:46 Notification ==>Operation failed with error:
```

```
Could not connect to host: mspdev33, port: 27053
```

```
[Summary] There are total 1 instances in the operation.
```

```
[Summary] Operation failed on 1013AS_1.mspdev27
```

```
[Summary] Operation on cluster FAILED since 1 instanced failed!
```

Solution:

Make sure the SeeBeyond e*Gate JMS server is running and that you provide the correct JMS host and port values when you install RPM. Pay special attention to the `input.taskqueue.jmshost` and `input.taskqueue.jmsport` properties in `ant.install.properties`. If you need to make a correction, you can run the installer again with this file as input by running silent mode (see Appendix B of this document).

Keystore Errors When Signing `rpm_client_config.jar`

Error message:

```
keytool error: java.io.IOException: Keystore was tampered with, or password was incorrect
```

This message may be encountered when you use the **keytool** utility to create an alias for signing the `rpm_client_config.jar` file. This usually happens when the alias for which you are generating a key already exists in the keystore file.

Solution:

Delete or rename the `~/.keystore` file and run the `keytool` command again. This creates a fresh keystore file.

Unreadable Buttons in the Installer

If you are unable to read the text within the installer buttons, it probably means that your `JAVA_HOME` is pointed to a pre-1.4.2 JDK. Set `JAVA_HOME` to a Java development kit of version 1.4.2 or later and run the installer again.

"Unable to get a deployment manager" Message

Symptom:

The application installer quits with the following error message:

```
[oracle:deploy] Unable to get a deployment manager.  
[oracle:deploy]  
[oracle:deploy] This is typically the result of an invalid deployer URI  
format being supplied, the target server not being in a started state or  
incorrect authentication details being supplied.  
[oracle:deploy]  
[oracle:deploy] More information is available by enabling logging --  
please see the Oracle Containers for J2EE Configuration and  
Administration Guide for details.
```

Solution:

This error can be caused by any of the following conditions:

- OC4J instance provided is not running.
- Incorrect OC4J instance name provided
- Incorrect OC4J administrative username and/or password
- Incorrect OPMN request port provided.

Make sure that the OC4J instance is running, and then check the **ant.install.properties** file for entry mistakes. Pay close attention to the `input.deployer.uri` (see Appendix D: *URL Reference*), `input.oc4j.instance`, `input.admin.user`, and `input.admin.password` properties. If you need to make a correction, you can run the installer again with this file as input by running silent mode (see Appendix B of this document).

Left-Side Menu Buttons Missing in RPM Client

Symptom:

You can log into the RPM application but the left-side menus do not show up on the screen.

Solution:

The RSM (Security Manager) schema has not been loaded with RPM security data. There is a set of RPM data scripts that is shipped with RMS 12.0 (See Chapter 2 of this document). Run these scripts in the RSM schema and try logging into RPM again.

"Could not create system preferences directory" Warning

Symptom:

The following text appears in the installer Errors tab:

```
May 22, 2006 11:16:39 AM java.util.prefs.FileSystemPreferences$3 run  
WARNING: Could not create system preferences directory. System preferences are  
unusable.  
May 22, 2006 11:17:09 AM java.util.prefs.FileSystemPreferences  
checkLockFile0ErrorCode  
WARNING: Could not lock System prefs. Unix error code -264946424.
```

Solution:

This is related to Java bug 4838770. The `/etc/.java/.systemPrefs` directory may not have been created on your system. See <http://bugs.sun.com> for details.

This is an issue with your installation of Java and does not affect the Oracle Retail product installation.

Appendix: URL Reference

The application installers for the Price Management product will ask for several different URLs. These include the following.

JDBC URL for a Database

Used by the Java application and by the installer to connect to the database.

Syntax: jdbc:oracle:thin:@<host>:<port>:<sid>

- <host>: hostname of the database server
- <port>: database listener port
- <sid>: system identifier for the database

Example: jdbc:oracle:thin:@myhost:1521:mysid

HTTP URL for a WebStart Client

Used within a web browser to access the application client.

Syntax: http://<host>:<port>/<path>

- <host>: hostname of the OracleAS environment
- <port>: HTTP port for the Oracle Http Server (OHS). This can be found in the Listen parameter in the ORACLE_HOME/Apache/Apache/conf/httpd.conf file, or in the output of opmnctl status -l.
- <path>: Path to the JNLP file, relative to the document root of the HTTP server. The document root for the Oracle Http Server is located at <ORACLE_HOME>/Apache/Apache/htdocs.

Example:
 <ORACLE_HOME>/Apache/Apache/htdocs/rpm/rpm.jnlp

http://myhost:7777/rpm/rpm.jnlp

JNDI Provider URL for an Application

Used by the application client to access the application running in the server. Also used by other applications for server-to-server calls.

Syntax: opmn:ormi://<host>:<port>:<instance>/<app>

- <host>: hostname of the OracleAS environment
- <port>: OPMN request port of the OracleAS environment. This can be found in the <ORACLE_HOME>/opmn/conf/opmn.xml file.
- <instance>: Name of the OC4J instance running the application
- <app>: Deployment name for the application.

Example: opmn:ormi://myhost:6003:rpm-oc4j-instance/rpm12

Note: The JNDI provider URL can have a different format depending on your cluster topology. Consult the Oracle Application Server documentation for further details.

Deployer URI

Used by the Oracle ANT tasks to deploy an application to an OC4J instance. The application installer does not ask the user for this value; it is constructed based on other inputs and written to the `ant.install.properties` file for input to the installation script. For repeat installations using silent mode, you may need to correct mistakes in the deployer URI in `ant.install.properties`.

Note: There are several different formats for the deployer URI depending on your cluster topology. Consult the Deploying with the OC4J Ant Tasks chapter of the OC4J Deployment Guide for further details.

Syntax (managed OC4J): `deployer:cluster:opmn://<host>:<port>/<instance>`

- `<host>`: hostname of the OracleAS environment
- `<port>`: OPMN request port of the OracleAS environment. This can be found in the `<ORACLE_HOME>/opmn/conf/opmn.xml` file.
- `<instance>`: Name of the OC4J instance where the application will be deployed.

Example: `deployer:cluster:opmn://myhost:6003/rpm-oc4j-instance`

Syntax (standalone OC4J): `deployer:oc4j:<host>:<port>`

- `<host>`: hostname of the OracleAS environment
- `<port>`: RMI port of the OC4J server. This can be found in the `ORACLE_HOME/j2ee/home/config/rmi.xml` file.

Example: `deployer:oc4j:myhost:23791`
