

Oracle® Application Server

Release Notes

10g Release 2 (10.1.2) for IBM zSeries Based Linux

B25837-02

September 2006

Copyright © 2006, Oracle. All rights reserved.

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software--Restricted Rights (June 1987). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

Oracle, JD Edwards, PeopleSoft, and Siebel are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

Contents

Preface	xxi
Audience	xxi
Documentation Accessibility	xxi
Related Documents	xxii
Conventions	xxii
What's New	xxiii
Chapter 9, "Oracle Application Server Portal"	xxiii
Chapter 17, "Oracle Business Intelligence"	xxiii
1 Introduction	
1.1 Latest Release Information	1-1
1.2 Purpose of this Document	1-1
1.3 Operating System Requirements	1-1
1.4 Certification Information	1-1
1.5 Licensing Information	1-2
2 Installation and Upgrade Issues	
2.1 Installation Issues	2-1
2.1.1 Locales zh_TW.EUC and zh_TW in Traditional Chinese Environments Not Supported in the OracleAS Portal Component	2-2
2.1.2 Characters Dropped or Truncated	2-2
2.1.3 Failure of File-Based Farm Repository Configuration Assistant	2-2
2.1.4 Non-English Welcome Pages URL Link Pages Incorrectly Coded	2-2
2.1.5 Distributed OracleAS Metadata Repository and Oracle Internet Directory on Separate Computers Throws Error	2-3
2.1.6 Welcome Link Coded Incorrectly	2-3
2.1.7 OracleAS Metadata Repository Creation Assistant Should Not Allow Loading into Oracle 10.1.0.4 Database	2-3
2.1.8 Installing 10.1.2.0.2 Middle Tiers Against an Existing Infrastructure	2-3
2.1.9 IBM WebSphere Required Patch Version 6.0.2	2-3
2.1.10 Disk Space Needed on a Database that Uses Automatic Storage Management	2-4
2.1.11 Oracle Ultra Search Required (Oracle Database 10g Release 2 (10.2.x) only)	2-4
2.1.12 Patch Required Prior to Running the Metadata Repository Creation Assistant on a 10.2 Real Application Cluster Database	2-4

2.1.13	Populate DB_DOMAIN Before Running Oracle Metadata Repository Creation Assistant on an Oracle 10.2 Database	2-4
2.1.14	Installer Displays Incorrect Version Number	2-5
2.1.15	JAccelerator (Ncomp) Is Not Installed with OracleAS Metadata Repository 10.1.2.x	2-5
2.1.16	Error While Setting Kernel Parameters for Oracle AS Web Cache and Setting Shell Limits	2-5
2.1.17	Do Not Use the Underscore Character in Host Name	2-5
2.1.18	Installing Oracle Application Server Middle Tier against a Real Application Clusters Database when Some of the Nodes are Down	2-5
2.1.19	Additional Step Required When Installing OracleAS Web Cache on Multihomed (Multi-IP) Computers	2-6
2.1.20	Configuring OracleAS Web Cache to Work Within an OracleAS Cold Failover Cluster.	2-6
2.1.21	Turkish Locale Does Not Display Correctly	2-7
2.2	Oracle Application Server Companion CD 10g (10.1.2.0.2).....	2-7
2.2.1	System Requirements for Oracle Application Server Companion CD 10g.....	2-7
2.2.2	Oracle Sensor Edge Server Administrator's Guide.....	2-8
2.2.3	Install Button on Companion CD Summary Screen Is Disabled	2-8
2.3	Documentation Errata	2-8
2.3.1	Additional Steps for OracleAS Single Sign-On HA Configuration.....	2-8
2.3.2	Incorrect File Extensions in Installed Documentation.....	2-8
2.3.3	Incorrect Path for OracleAS Upgrade Assistant Log File	2-9
2.3.4	Incorrect Version Number on Forms and Reports CD-ROM.....	2-9
2.3.5	Incorrect Copyright Information	2-9
2.3.6	Incorrect Media Reference in Oracle Application Server Installation Guide	2-9
2.3.7	Invalid Instruction to Apply Database Patch	2-9
2.3.8	Incorrect OID Port for Silent Installations.....	2-10
2.3.9	Incorrect Environmental Variable Recommendation.....	2-10
2.3.10	Invalid Limitation on Installing Oracle Application Server in an OracleAS Disaster Recovery Environment	2-10
2.3.11	Error While Setting Kernel Parameters for Oracle AS Web Cache and Setting Shell Limits	2-10
2.3.12	Incorrect Symbolic Link Creation Command.....	2-11

3 General Management and Security Issues

3.1	General Issues and Workarounds	3-1
3.1.1	Error Message When Executing opmnctl Commands	3-1
3.2	Starting and Stopping Release 10.1.2.0.0	3-1
3.2.1	Starting OracleAS Infrastructure	3-2
3.2.2	Stopping OracleAS Infrastructure	3-2
3.2.3	Starting a Middle-Tier Instance	3-3
3.2.4	Stopping a Middle-Tier Instance	3-4
3.3	Port Change Issues.....	3-4
3.3.1	Additional Step Needed After Changing Oracle HTTP Server Listen Port.....	3-4
3.4	Cloning Issues	3-4
3.4.1	Considerations for Cloning Oracle Ultra Search.....	3-4
3.4.2	Considerations for Cloning OracleBI Discoverer.....	3-5

3.4.3	Considerations for Cloning OracleAS Forms and Reports Services	3-5
3.5	Deployment Issues.....	3-6
3.5.1	Use Trusted Certificates When Enabling SSL Between mod_oc4j and OC4J	3-6
3.5.2	Benign Decoding Errors When Running ldapaddmt	3-6
3.5.3	Missing Files During restore_config Operation	3-6
3.5.4	Performance Improvement on Multiple Processors Systems	3-6
3.6	Documentation Errata	3-7
3.6.1	Errors in the Distributed Configuration Management Administrator's Guide	3-7
3.6.2	Errors in Oracle Process Manager and Notification Server Administrator's Guide .	3-8
3.6.3	Incorrect Reference in Oracle Application Server Concepts Guide	3-8
3.6.4	Incorrect Default Value for start-mode Element in Oracle HTTP Server opmn.xml file ..	3-8

4 High Availability

4.1	OracleAS Disaster Recovery: Discover Topology Command	4-1
4.2	OracleAS Disaster Recovery: Real Application Clusters Database Supported	4-2

5 Oracle Forms

5.1	General Issues and Workarounds	5-1
5.1.1	Unix Issues and Workarounds	5-1
5.1.2	Incorrect Memory Usage Is Reported for Forms on SLES9	5-1
5.2	Configuration Issues and Workarounds	5-1
5.2.1	Non-Internet Explorer Browser Proxy Settings when Using One-Button-Run.....	5-2
5.2.2	Change to Default Setting for FORMS_RESTRICT_ENTER_QUERY Environment Variable	5-2
5.2.3	PJC Wizard Now Part of Oracle Forms	5-2
5.2.4	Exception When Clicking Other Items While Inputting Multibyte Characters	5-2
5.2.5	JDK 1.4.2_06 Plug-in Not Installed When Running a Form on the Web for the First Time	5-2
5.2.6	CLOB Data Cannot be Retrieved When Query Data More Than Max Width.....	5-3
5.2.7	FRM-92102 Existing Sessions Disconnect When User Added To JAZN	5-3
5.2.8	Monitoring CPU Usage and Response Time	5-3
5.3	Documentation Errata	5-3
5.3.1	Incorrect Key Mapping	5-4
5.3.2	Incomplete JVM Pooling Example	5-4
5.3.3	Incorrect Script Tag Names	5-4
5.3.4	Incorrect Default Threshold Setting Description	5-4
5.3.5	Incorrect Parameter Names in URL	5-4

6 Oracle Application Server Containers for J2EE

6.1	OC4J Bugs Fixed in 10.1.2.0.2	6-1
6.2	Configuration Issues and Workarounds	6-1
6.2.1	Oracle JDBC-OCI Driver Upgrade in the Oracle Application Server	6-1
6.2.2	OC4J Out of Memory Errors	6-2
6.2.3	JDK 1.3 With OC4J 10.1.2.0.2	6-3
6.2.4	Configuring Maximum Connections with Oracle HTTP Server	6-3

6.3	Enterprise Java Beans	6-4
6.3.1	Deprecated orion-ejb-jar.xml Attributes	6-4
6.3.2	Big EAR File Deployment Runs Out of Memory	6-5
6.3.3	EJB Wrapper Code Compilation Fails When Running in zh_CN.GB18030 Locale ...	6-5
6.3.4	Disregard Previous Release Note: Package Name for RMIIInitialContextFactory Has Changed	6-5
6.3.5	How To Disable EJB Instance Pooling	6-5
6.3.6	How To Compile in Non-Batch Mode	6-5
6.4	OC4J Services.....	6-6
6.4.1	Data Sources	6-6
6.4.1.1	Data Sources Creates the Correct Number of Connection Pools in 10.1.2.....	6-6
6.4.1.2	Fatal Error Code Enhancement	6-6
6.4.1.3	Fixed Connection Pool Problems	6-7
6.4.2	ORMI	6-7
6.4.2.1	ORMI - OC4J Only Creates IPv4 Sockets	6-7
6.4.2.2	ORMI Protocol Is Not Secure	6-7
6.5	Oracle Application Server Java Authentication and Authorization Service (JAAS) Provider	6-8
6.5.1	Using the 9.0.4 Oracle Internet Directory Server with 10.1.2.0.2 OracleAS JAAS Provider	6-8
6.5.2	Support for auth-method="DIGEST" in <jazn-web-app>	6-8
6.6	Documentation Errata	6-9
6.6.1	Oracle Application Server Containers for J2EE User's Guide Documentation Errata	6-9
6.6.1.1	An OC4J Process Is Not Contained in an OC4J Instance	6-9
6.6.1.2	Correct Cross Reference for Metric-Based Load Balancing Information	6-10
6.6.1.3	JDK 1.4.2 Supported and Installed with OC4J	6-10
6.6.1.4	Primers Content Removed from OC4J User's Guide	6-10
6.6.1.5	Additional OC4J Deployment Notes	6-10
6.6.1.6	Corrected Default Log File Name	6-11
6.6.1.7	Manual Build and Deploy Methods Apply To Standalone Environment Only	6-11
6.6.1.8	High Availability Guide Has No Information on "Hot Deploying" an Application in a Clustered Environment	6-12
6.6.1.9	For State Replication, Confirm That the <cluster-config/> Tag Is in the orion-web.xml File	6-12
6.6.2	Oracle Application Server Containers for J2EE Standalone User's Guide Documentation Errata	6-12
6.6.2.1	Correction: http-web-site.....	6-13
6.6.3	Oracle XML API Reference Documentation Errata	6-13
6.6.3.1	Add Information for formDocument() Method	6-13
6.6.4	Oracle Application Server Containers for J2EE Services Guide Documentation Errata	6-13
6.6.4.1	Corrected SQLServer Data Source Example	6-14
6.6.4.2	Corrected JDBC Connect String for Third-Party Databases	6-14
6.6.4.3	Corrected Java Object Cache Code Example for Implementing a CacheEventListener	6-16
6.6.4.4	Also Add the ojdk.jar File to the Classpath to Access EJBs.....	6-16

6.6.5	Oracle Application Server Containers for J2EE Security Guide	6-17
6.6.5.1	Incorrect Example in Deployment Roles and Users	6-17
6.6.5.2	Incorrect internal-settings.xml Information	6-17
6.6.5.3	Incorrect RMIPermission and AdministrationPermission Class Information .	6-17
6.6.6	OC4J Release Notes for 10.1.2.0.2	6-17
6.6.6.1	Disregard Previous Release Note: Package Name for RMIIInitialContextFactory Has Changed	6-18

7 Oracle HTTP Server

7.1	General Issues and Workarounds	7-1
7.1.1	Oracle HTTP Server (1.0.2.2.x) Cannot Be Used with Oracle Internet Directory 10g Release (10.1.2)	7-1
7.1.2	Log Error Message	7-1
7.1.3	Apache 2.0 Startup Fails	7-2
7.2	Configuration Issues and Workarounds	7-2
7.2.1	FastCGI Sockets Path Length Error.....	7-2
7.2.2	Oracle HTTP Server Does Not Start After Enabling Port Tunneling or SSL in mod_oc4j	7-2
7.2.3	Redirects Break If OracleAS Web Cache is Turned Off or is Disabled	7-2

8 Oracle Application Server TopLink

8.1	General Issues and Workarounds	8-1
8.1.1	Installing Oracle Application Server TopLink Mapping Workbench from the Companion CD	8-1

9 Oracle Application Server Portal

9.1	OracleAS Portal 10g Release 2 (10.1.4) Issues and Workarounds.....	9-1
9.1.1	General Issues and Workarounds	9-1
9.1.1.1	Editing a Database Link Requires Password.....	9-2
9.1.1.2	Moving Content When Approval Is Enabled Does Not Require Approval	9-2
9.1.1.3	Download Fails for Files with .tgz, .gz, and .Z Extensions	9-2
9.1.1.4	Logout Link Does Not Work When Accessing OracleAS Portal Using a Mobile Device	9-2
9.1.1.5	Pushing Oracle Reports 10.1.2.0.2 Output to OracleAS Portal 10.1.4 Does Not Work	9-3
9.1.1.6	Internal Error Uploading Files or Images	9-3
9.1.1.7	OracleAS Portal Login Fails After OracleAS Cold Failover Cluster (Middle Tier) Configuration	9-3
9.1.1.8	Action Buttons Minimized to Dots on Portal Pages on IBM zSeries Based Linux	9-4
9.1.1.9	Oracle Text Support	9-4
9.1.2	Upgrade Issues and Workarounds	9-4
9.1.2.1	Relative Hypertext Links to Images and Documents May Break After Upgrade	9-4
9.1.3	User Interface Issues and Workarounds	9-4
9.1.3.1	Template Caching Option Displays Incorrectly in a Non-English Portal	9-4
9.1.4	Portlet and Provider Issues and Workarounds	9-5

9.1.4.1	Using OmniPortlet Web Page Data Source After Cloning	9-5
9.1.4.2	Truncated Data in Page Portlets.....	9-5
9.1.4.3	Download Latest Portlet Container for WSRP	9-6
9.1.4.4	Using WSRP Portlets that Display User Profile Attributes within OracleAS Portal..	9-6
9.1.4.5	Registering WSRP Producers in Enterprise Configurations	9-6
9.1.4.6	Issue Adding or Deleting Portlets on Page Portlets	9-7
9.1.4.7	Issue When Accessing Page Portlet Using Federated Portal Adapter.....	9-7
9.1.4.8	Error in JPS Portlet After Redeployment	9-7
9.1.4.9	Error in Registering the WSRP Provider On IBM zSeries Based Linux	9-7
9.1.4.10	Error While Adding Portlets.....	9-8
9.1.5	Globalization Support Issues and Workarounds.....	9-8
9.1.5.1	Text Entry Always Right to Left in BiDi Languages	9-8
9.1.5.2	Browser Limitation in BiDi Languages	9-8
9.1.5.3	Non-ASCII Character Limitations in OracleAS Portal.....	9-9
9.1.5.4	Non-ASCII Character Limitations in Oracle Instant Portal.....	9-9
9.1.5.5	Errors Displayed When the OracleAS Portal Language Is Traditional Chinese.	9-9
9.1.6	Documentation Errors.....	9-9
9.1.6.1	Help for Page and Template Caching Options Is Incorrect	9-9
9.2	OracleAS Portal 10g Release 2 (10.1.2) Issues and Workarounds.....	9-9
9.2.1	General Issues and Workarounds	9-10
9.2.1.1	Error in portal.log File After Installing OracleAS Metadata Repository.....	9-10
9.2.1.2	OracleAS Portal Login Fails After OracleAS Cold Failover Cluster (Middle Tier) Configuration	9-10
9.2.1.3	Action Buttons Minimized to Dots on Portal Pages on IBM zSeries Based Linux	9-11
9.2.2	Upgrade Issues and Workarounds	9-11
9.2.2.1	Configuring OracleAS Portal After Upgrade.....	9-11
9.2.2.2	OracleAS Portal Users Cannot Log on to Oracle Ultra Search	9-13
9.2.2.3	Apply Portal Patch After Upgrading Database from Release 9i to 10g.....	9-14
9.2.2.4	Additional Step Required When Upgrading OracleAS Metadata Repository Release 9.0.4.3 to 10.1.4.0.1	9-14
9.2.3	User Interface Issues and Workarounds	9-15
9.2.3.1	Issue Adding Regions to Pages Displayed in the Generic Page Portlets	9-16
9.2.3.2	Portlets on Subpages Not Displayed	9-16
9.2.3.3	Cannot Set Privileges Using List View on Pages Inheriting Privileges from Parent or Template	9-16
9.2.4	Export and Import Issues and Workarounds.....	9-16
9.2.4.1	Export and Import Does Not Support Reports Server Components	9-16
9.2.5	Portlet and Provider Issues and Workarounds.....	9-16
9.2.5.1	Using OmniPortlet Web Page Data Source After Cloning	9-17
9.2.5.2	Error Exporting and Importing OmniPortlet and Web Clipping Customizations	9-17
9.2.5.3	Issue Adding or Deleting Portlets on Page Portlets	9-17
9.2.6	PDK Issues and Workarounds.....	9-17
9.2.6.1	Support for WSRP and JSR 168.....	9-18
9.2.6.2	Restrictions on Struts Text Tag Lifted	9-18
9.2.7	Globalization Support Issues and Workarounds.....	9-18

9.2.7.1	Oracle Text Searching Limitation (Text Files and HTML Files)	9-18
9.2.7.2	Text Entry Always Right to Left in BiDi Languages	9-19
9.2.7.3	Non-ASCII Character Limitations in OracleAS Portal.....	9-19
9.2.7.4	Non-ASCII Character Limitations in Oracle Instant Portal.....	9-19
9.2.7.5	Shared Type Objects Cannot Be Exposed in Non-English Page Group	9-19
9.2.7.6	Translations Lost When Item Versioning Is Enabled	9-20
9.2.8	Documentation Errata	9-20
9.2.8.1	Documentation Errors	9-20
9.2.8.1.1	Editing Item/Portlet Properties	9-20
9.2.8.1.2	Editing Pending Items	9-20
9.2.8.1.3	Referencing the Current Version of Images	9-21
9.2.8.1.4	Working in List View	9-21
9.2.8.1.5	Unpublished Items Section Documented Incorrectly	9-22
9.2.8.1.6	Item Level Security and Page Caching.....	9-22
9.2.8.1.7	User Profile Help Incorrect	9-22
9.2.8.1.8	Defining a Display Style for Results from a Custom Search.....	9-22
9.2.8.1.9	Applying Background Color or Image to Page Portlets	9-22
9.2.8.1.10	Registering JSR Portlets	9-22
9.2.8.1.11	Corporate Page Groups No Longer Installed	9-22
9.2.8.1.12	Exposing Your Application as a Web Service	9-22
9.2.8.1.13	Changes Required in the Steps to Configure Security in OracleAS Portal	9-24
9.2.8.1.14	Portal Upgrade Error and Warning Messages Should Be Prefixed with WWU-	9-25
9.2.8.2	Additional Documentation	9-25
9.2.8.2.1	Inaccurate Data in Log Registry Records.....	9-25
9.2.8.2.2	Expired Items Remain Visible in WebDAV Clients	9-25
9.2.8.2.3	Enhanced Rich Text Editor	9-25
9.2.8.2.4	Using Oracle Drive with OracleAS Portal	9-25
9.2.8.2.5	Unable to Delete Tabs on Templates	9-26
9.2.8.2.6	Error Removing Subscriber from Virtual Private Portal	9-26
9.2.8.2.7	Unable to Monitor WSRP Providers in This Release	9-26
9.2.8.2.8	Location of the ptlwsrp_data.sql Script	9-26

10 Oracle Ultra Search

10.1	Upgrade Issues and Workarounds.....	10-1
10.1.1	Upgrade Fails When Upgrading to 10.1.2.....	10-1
10.2	General Issues and Workarounds	10-2
10.2.1	Creating or Editing Oracle Ultra Search ACLs Fails in Non-OracleAS Single Sign-On Mode	10-2
10.3	Documentation Errata	10-2
10.3.1	Adding and Deleting Subscribers	10-2

11 Oracle Application Server Wireless

11.1	General Issues.....	11-1
11.1.1	Unable to Test Locally Deployed JSPs.....	11-1
11.1.2	EDGE_CREATE Script Errors.....	11-2

11.1.3	Database Lock Hangs STREAMS Dispatcher	11-2
11.1.4	OracleAS Wireless Patch Required after XDK Patch is Applied	11-3
11.1.5	Broken Icons in Wireless Device Portal Homepage	11-3
11.1.6	HDML Error When Using Expense Demo Application.....	11-3
11.2	Configuration Issues and Workarounds	11-3
11.2.1	Migrate Account Numbers and PINs after Upgrade	11-4
11.2.2	SDO_INDEX_METADATA NULL FETCH Error.....	11-4
11.2.3	Updated Transformer Stylesheets Patch Required after Upgrade.....	11-4
11.2.4	OracleAS Metadata Repository Creation Assistant 9.2.0.6 Error with Wireless 10.1.2	11-4
11.2.5	Configuration Assistant Error Message	11-5
11.2.6	IBM WebSphere Required Patch Version 6.0.2	11-5

12 Oracle BPEL Process Manager

12.1	Installation Issues and Workarounds	12-2
12.1.1	Message to Ignore During Oracle BPEL Process Manager for OracleAS Middle Tier Installation	12-2
12.1.2	Migrating from Previous Releases of Oracle BPEL Process Manager	12-2
12.1.3	Adding Oracle BPEL Process Manager for OracleAS Middle Tier Memory Settings.....	12-2
12.1.4	Installing Oracle Java Virtual Machine on IBM zSeries Based Linux	12-3
12.2	General Issues and Workarounds	12-3
12.2.1	Error with opmnctl stopall to Ignore	12-3
12.2.2	Undeploying and Redeploying the OC4J_BPEL System Component Through Oracle Enterprise Manager Is Not Supported.....	12-4
12.2.3	JDeveloper BPEL Designer Limitations on Linux.....	12-4
12.2.4	JDeveloper BPEL Designer Limitations on Solaris	12-4
12.2.5	WSDL Exception Error When Trying to Create a Stub to Use a Web Service	12-4
12.2.6	Deploying Oracle JDeveloper-Created Web Services to Oracle BPEL Process Manager OC4J	12-4
12.3	Modeling and Design Time Issues and Workarounds.....	12-5
12.3.1	No Deployment Time Validation Logic with obant.....	12-5
12.3.2	Do Not Include Blank Spaces in Directory Paths of JDeveloper BPEL Designer Workspaces	12-6
12.3.3	Using Annotations in JDeveloper BPEL Designer	12-6
12.3.4	Internal Compilation Error When Using the CTRL and F9 Keys.....	12-6
12.3.5	Inline Dialogs Can Result in Data Loss in Some Cases.....	12-6
12.3.6	Do Not Add or Import XSD Files in a ZIP File.....	12-6
12.3.7	Cannot Select Property Aliases in project_name.wsdl File	12-7
12.3.8	Correlation Set Property Aliases Defined in Process WSDL Cause Problems	12-7
12.3.9	BPEL Processes Initiated by Partner Links Referring to Adapters.....	12-7
12.3.10	Changes Made In BPEL Designer Do Not Update Automatically	12-7
12.3.11	Extra Carriage Return Added When Using XML Literals	12-7
12.3.12	readFile Function Displays Only One Argument in XPath Expression Builder Window	12-8
12.3.13	Error When Selecting Message Part Elements Using Inline Schemas of a Project..	12-8
12.4	Workflow and Worklist Issues and Workarounds	12-8

12.4.1	Manually Configuring Oracle BPEL Process Manager on Oracle Application Server to Support Identity Management	12-9
12.4.2	Default Account Does Not Initially Display in Notification Service Page of Oracle Enterprise Manager	12-10
12.4.3	Always Deploy BPEL Projects with Workflow from JDeveloper BPEL Designer	12-10
12.4.4	Workflow Names Must Not Include Periods.....	12-10
12.4.5	Compilation Warning Messages That Can Be Ignored.....	12-10
12.4.6	Deleting an Entire User Task Activity	12-10
12.4.7	Deleting a Scope of a User Task Activity	12-10
12.4.8	Using the Category List in Oracle BPEL Worklist Application	12-11
12.4.9	Sequential Workflow with Automatic Escalation Error with Workflow Wizard	12-11
12.4.10	Getting Task Details with the getWorklistTaskDetails API	12-11
12.4.11	Adding Delays to Task Operations.....	12-11
12.4.12	Using the Custom Identity Service Provider Plug-in Sample on the Middle Tier	12-12
12.4.13	Configuring the TaskActionHandler and TaskManager Services to Support SSL	12-12
12.5	Transformation Issues and Workarounds.....	12-12
12.5.1	SetText Introduces a Newline Character After Transformation.....	12-13
12.5.2	Inconsistent Behavior for Functions in JDeveloper BPEL Designer.....	12-13
12.5.3	get-content-as-string Function Introduces a New Line Character After the Output	12-14
12.5.4	Target XSD with Choice May Create Invalid Target Instance at Run Time	12-14
12.5.5	Database Functions with JNDI Names Do Not Work Within a MapTest Window.....	12-15
12.6	XPath Expression Builder Issues and Workarounds	12-15
12.7	Oracle Application Server Adapter for Files/FTP Issues and Workarounds.....	12-15
12.7.1	Negative Values are Not Permitted for the PublishSize Parameter.....	12-16
12.7.2	Multiple Batching Invokes from the Same BPEL Process.....	12-16
12.7.3	Editing the Existing Logical Name Removes the Mapping in the bpel.xml File...	12-16
12.7.4	Purging Files.....	12-16
12.8	Oracle Application Server Adapter for AQ Issues and Workarounds	12-16
12.8.1	Timestamp with Local Timezone and Timestamp with Timezone are Not Supported in ADT	12-17
12.9	Oracle Application Server Adapter for Databases Issues and Workarounds.....	12-17
12.9.1	Use OC4J Connection Pooling in High Availability Environments.....	12-17
12.9.2	Database Adapter Throws an Exception for SYS.XMLTYPE	12-17
12.9.3	NCLOB Data Read by the Outbound Database Adapter Contains Invalid Characters....	12-17
12.9.4	Date/Time Format Values Not Displayed as Expected.....	12-18
12.9.5	SELECT Query Does Not Work for Multiple AND Conditions for DEPT:EMP Table.....	12-18
12.9.6	XML WSDL XSD Files Remain After the Partner Link Is Deleted	12-18
12.9.7	XML File Stored as a CLOB Is Returned as a String, Not as an XML Node	12-19
12.9.8	Cannot Query on Multiple Views	12-19
12.9.9	Using Function Calls Inside a SQL Query	12-19
12.10	Oracle Application Server Adapter for JMS Issues and Workarounds	12-19
12.10.1	Outbound Retry Functionality for AQJMS on Solaris Is Not Supported	12-19
12.10.2	Connection Retry Functionality for MQ Provider is Not Supported by the JMS Adapter	12-20

12.10.3	Removing Durable Subscriptions.....	12-20
12.11	Oracle Application Server Adapter for Oracle Applications Issues and Workarounds	12-20
12.11.1	Correlation ID Defaults to BPEL for XML Gateway Transactions Outbound From Oracle Applications	12-20
12.11.2	Wildcard Search Capabilities are Based on the E-Business Suite Instance	12-21
12.11.3	Objects Displaying for Selection are Based on E-Business Suite Instance.....	12-21
12.11.4	Workaround for Stored Procedures with Complex Types and Using the DEFAULT Clause	12-21
12.11.5	One-time Workaround for Concurrent Programs and E-Commerce Gateway Interfaces	12-21
12.11.6	Cannot Create a Partner Link If the Underlying API Has Been Re-created	12-22
12.12	General Adapter and Adapter Partner Link Issues and Workarounds.....	12-22
12.12.1	Case of Property Names in ra.xml and oc4j-ra.xml Files Must Match.....	12-23
12.12.2	Deleting Header Variables	12-23
12.12.3	Moving to the Next Window in the Adapter Configuration Wizard for Oracle Applications Adapter	12-23
12.12.4	Configuring Multiple Adapters in the Inbound Direction Using Correlation Sets	12-23
12.13	Sensor Issues and Workarounds.....	12-24
12.13.1	Sensor Integration with Oracle Application Server Integration Business Activity Monitoring	12-24
12.14	Oracle BPEL Console and Oracle BPEL Server Issues and Workarounds	12-24
12.14.1	Configuring Mozilla Firefox for Oracle BPEL Console Support	12-24
12.14.2	Oracle BPEL Console Reports	12-24
12.14.3	Unable to Delete a Domain or Re-create a Domain with the Same Name.....	12-25
12.14.4	Large Binary Attachments in SOAP Messages Can Fail with Oracle Database Lite	12-25
12.14.5	SOAP Attachment DIME Service Callback Does Not Include the Attachment Key	12-26
12.15	Oracle BPEL Portlets Issues and Workarounds	12-26
12.15.1	Oracle BPEL Console Report Portlets	12-26
12.15.2	Oracle BPEL Worklist Application Portlets	12-27
12.16	High Availability Issues and Workarounds	12-27
12.16.1	Oracle BPEL Process Manager and Real Application Clusters Databases.....	12-28
12.16.2	Disaster Recovery of Oracle BPEL Process Manager	12-28
12.16.3	Oracle BPEL Process Manager Backup and Recovery with Oracle Enterprise Manager .	12-28
12.17	Globalization/Multibyte Character Issues and Workarounds	12-28
12.17.1	Encoding Restrictions in E-Mail Subject Field.....	12-29
12.17.2	UTF-8 Encoding Always Used in XSLT Mapper	12-29
12.17.3	XML Mapper Must Use the Encoding Specified in the XSL When Reading a File.....	12-29
12.17.4	Multibyte Project Name Causes WSDL File to Be Invalid.....	12-29
12.17.5	Ruler Scale Is Not Multibyte-compliant in the Native Format Builder Wizard	12-29
12.17.6	Encoding Issue for ora:readFile	12-29
12.17.7	Data Consumed as a Text Message May Have Problems.....	12-29
12.18	Oracle BPEL Process Manager Samples Issues and Workarounds	12-30

12.19	JBoss Issues and Workarounds	12-30
12.19.1	Error To Ignore when Installing Oracle BPEL Process Manager on Solaris	12-30
12.19.2	Cannot Migrate From Oracle BPEL Process Manager 10.1.2.0.0 to 10.1.2.0.2 with JBoss Application Server	12-30
12.19.3	Increasing Connection Pool Settings for Oracle BPEL Process Manager	12-31
12.19.4	OracleAS Integration B2B and OracleAS Integration InterConnect Interoperability with Oracle BPEL Process Manager is Not Supported	12-31
12.19.5	Oracle Workflow Bridge is Not Supported	12-31
12.19.6	Identity Service Plug-in for Database Providers Sample is Not Supported	12-31
12.20	BEA WebLogic Issues and Workarounds	12-31
12.20.1	Unsupported Upgrade and Migration Scenarios.....	12-32
12.20.2	owf.ear File Not Included with Installation Software.....	12-32
12.20.3	Identity Service Plug-in for Database Providers Sample is Not Supported	12-32
12.20.4	OracleAS Integration B2B and OracleAS Integration InterConnect Interoperability with Oracle BPEL Process Manager is Not Supported	12-32
12.21	Microsoft SQL Server Issues and Workarounds	12-32
12.21.1	Oracle BPEL Process Manager for OracleAS Middle Tier Installations and Sensors	12-33
12.21.2	SOAP with Binary Attachments Not Supported	12-33
12.21.3	Reports Feature of Oracle BPEL Console and BPEL Reports Portlets Not Currently Working	12-33
12.21.4	Identity Service Plug-in for Database Providers Sample Not Currently Working	12-33
12.22	Documentation Errata	12-33
12.22.1	Oracle Application Server Administrator's Guide	12-33
12.22.2	Oracle Application Server Adapters for Files, FTP, Databases, and Enterprise Messaging User's Guide	12-34

13 Oracle BPEL Process Analytics

13.1	General Issues and Workarounds	13-1
13.1.1	Unset the ORACLE_HOME Variable Before Installing	13-2
13.1.2	Workaround for Inability to Connect to Database After Installation	13-2
13.1.3	Restart Oracle BPEL Process Analytics To Fire Alerts In Some Specific Cases	13-3
13.1.4	Array Support in Oracle BPEL Process Analytics is Limited to First Level.....	13-3
13.1.5	Non-Working Alert Delivery Channels - FAX, Instant Message, Pager	13-3
13.1.6	To Use BAMServiceWrapper, Apply Patch 1 on BPEL.....	13-3
13.1.7	Old Target Values Shown When Adding New Dimensions to a Composite Event	13-3
13.1.8	Focus Button on Update Composite Event Confirmation Page Returns Error	13-3
13.1.9	Alerts for <= KPI Value Condition Fire at 12 O'clock With Value Zero	13-4
13.1.10	Cannot Create Sensors for Primitive and Element Types.....	13-4
13.1.11	Some Error Messages Contain "BAM" Instead of "BPA"	13-4
13.1.12	Oracle BPEL Process Analytics Dashboard Shows Strange Character	13-4
13.1.13	Cannot Create Two Composite Events of the Same Name	13-4
13.1.14	Best Practice for Time Zone Settings.....	13-4
13.1.15	Dashboard KPI Table Shows Exclamation Marks	13-5
13.1.16	Do Not Use SQL Keywords for Naming the KPIs	13-5
13.1.17	New Default Units for Duration and Currency Type KPIs	13-5
13.1.18	Exception Returned In UI.LOG While Logged in as Administrator.....	13-5

13.1.19	No Oracle BPEL Process Analytics Logs Are Available From Oracle Enterprise Manager	13-5
13.1.20	Workaround for Errors Such As "Failed to Add to Metadata"	13-5
13.1.21	Parentheses Needed In KPI Creation Wizard	13-6
13.2	Known Problems.....	13-6
13.2.1	Count Aggregation Cannot Be Applied on Duration, Currency, and Percent.....	13-6
13.2.2	Alerts Not Filtered Out According to the User-Selected Time Frame	13-6
13.2.3	KPI Constructed On Dimensionsless Composite Event Is Improperly Displayed.	13-7
13.2.4	Option To See The Dashboard Pages Based on the Time Zone Not Available	13-7
13.2.5	Delete Event Icon Does Not Work in Update Composite Event	13-7
13.2.6	Sensor Cannot Handle Multiple Variables	13-7
13.2.7	Cannot Reinstall Oracle BPEL Process Analytics After Grid Control Agent Is Installed and Configured	13-7
13.3	Documentation Errata	13-8

14 Oracle Application Server Integration B2B

14.1	General Issues and Workarounds	14-1
14.1.1	Redeployment Issue	14-1
14.1.2	Purging Removes Instance Data.....	14-1
14.1.3	Self-service API for Creating Trading Partners and Agreements	14-2
14.1.4	Oracle Application Server Clustering and Integration B2B	14-2
14.1.5	B2B User Login Must Have a Role	14-2
14.1.6	Cannot Update the admin User Password	14-2
14.1.7	OracleAS Integration B2B Pages in Oracle Enterprise Manager	14-2
14.1.8	Configuring OracleAS Integration B2B in Enterprise Environments	14-2
14.2	Installation Issues and Workarounds	14-3
14.2.1	Enable Secure Socket Layer When the Midtier Instance is Registered to Oracle Internet Directory	14-3
14.2.2	Installing OracleAS Integration B2B on a Red Hat Enterprise Linux 2.1 Update5 System	14-3
14.3	Documentation Errata	14-4
14.3.1	User's Guide Documentation.....	14-4
14.3.2	Installation Documentation.....	14-5

15 Oracle Application Server Integration InterConnect

15.1	General Issues and Workarounds	15-1
15.1.1	Adapters Duplicate the Messages During Failover on Real Application Cluster (RAC) or Cold Failover Cluster (CFC) Environment	15-1
15.1.2	JCA adapter Does Not Support High Availability	15-1
15.2	Installation Issues and Workarounds	15-2
15.2.1	Make Utility at /bin/make is Required for Hub Installation on Linux	15-2
15.3	Documentation Errata	15-2
15.3.1	Documentation Errors.....	15-2
15.3.1.1	Incorrect Release Number	15-2
15.3.2	Additional Documentation	15-2
15.3.2.1	Configuring the InterConnect JCA adapter for use with DB2 and Sybase Database.	15-2

15.3.2.2	Application Name value in the oc4j-ra.xml File	15-5
16	Oracle Application Server Web Cache	
16.1	Configuration Issues and Workarounds	16-1
16.1.1	Patch Available for Configuring OracleAS Web Cache Solely as a Software Load Balancer or Reverse Proxy	16-1
16.1.2	Reloading Issue with Cache Operations Success Message in OracleAS Web Cache Manager with Internet Explorer Browser	16-1
17	Oracle Business Intelligence	
17.1	General Issues and Workarounds	17-1
17.1.1	Certification Information	17-2
17.1.2	Availability of HWOOnline Files	17-2
17.1.3	Obtaining Patch Set for GUID-Generation Issue	17-2
17.1.4	Issues with Metadata Repository and Oracle Database 10g Release 1	17-2
17.1.5	Clarification of Version Numbers	17-3
17.1.6	Compatibility Issues with Required Support Files.....	17-3
17.1.7	Resizing Issue with Mozilla and Firefox Browsers.....	17-4
17.1.8	Serif Font Issue in Worksheets.....	17-4
17.1.9	Additional Fonts Required for Non-ASCII Data When Exporting to PDF	17-4
17.1.10	Query Prediction Requires the Majority of the Query Time	17-5
17.1.11	Issue When Drilling to Detail on Page Item Set to <ALL>	17-5
17.1.12	Date Format in OracleBI Discoverer Plus and OracleBI Discoverer Viewer	17-5
17.1.13	Word Wrapping Behavior with OracleBI Discoverer Plus and OracleBI Discoverer Viewer	17-5
17.1.14	Applet Appears Behind Browser Window	17-6
17.1.15	Issues with Mac OS X Browser and OracleBI Discoverer Plus	17-6
17.1.16	Welcome Page Displays Only in English	17-7
17.1.17	Issues with Turkish Regional Settings	17-7
17.1.18	Help Files in Non-English Languages	17-7
17.1.19	New User Preferences Added.....	17-7
17.1.20	Correction to Oracle Business Intelligence Installation Guide	17-8
17.1.21	Corrections to the OracleBI Discoverer Connections Help	17-9
17.1.21.1	Account Details: Enter Password page Help topic.....	17-9
17.1.21.2	Account Details: Select Responsibility page Help topic	17-9
17.1.21.3	Connect to OracleBI Discoverer page Help topic	17-10
17.1.21.4	Account Details: Username and Password page Help topic	17-10
17.1.21.5	Account Details: Select Username page Help topic	17-10
17.1.21.6	Enter connection details page Help topic	17-10
17.1.22	Corrections to the Oracle Business Intelligence Discoverer Configuration Guide	17-10
17.1.23	Corrections to Oracle Enterprise Manager 10g Application Server Control Discoverer Help	17-11
17.1.23.1	Discoverer Administration page Help topic	17-12
17.1.23.2	Discoverer Configuration page Help topic.....	17-12
17.1.23.3	Install Catalog page Help topic	17-12
17.1.23.4	Log in to Manage Catalog page Help topic	17-12
17.1.23.5	Uninstall Catalog page Help topic	17-12

17.1.23.6	Discoverer Plus Configuration page Help topic	17-12
17.1.23.7	Discoverer Portlet Provider Configuration page Help topic	17-13
17.1.23.8	Discoverer Administration page Help topic	17-13
17.1.24	Discoverer Communication Protocol Does Not Get Upgraded Correctly from 9.0.4 to 10.1.2.0.2	17-13
17.1.25	Corrections to <i>Oracle Business Intelligence Discoverer Publishing Workbooks in OracleAS Portal</i>	17-13
17.1.25.1	Corrections and additions to section 'How to copy Discoverer connections from one Oracle Business Intelligence installation to another'	17-13
17.2	Oracle Business Intelligence Discoverer Plus Relational	17-14
17.2.1	Text Appearing Truncated or Clipped	17-15
17.2.2	Non-ASCII Characters Not Saved Correctly in Title or Text Area.....	17-15
17.2.3	Resizing in Mac OS X Browser	17-15
17.2.4	Corrections to the OracleBI Discoverer Plus Relational Help	17-15
17.2.4.1	References to the Connect to Discoverer Plus page Help topic.....	17-15
17.2.4.2	Task steps in the How do I create and save login information in a Discoverer connection Help topic	17-16
17.2.4.3	Task steps in the How to remove sorting from a worksheet Help topic.....	17-16
17.2.5	Important Bug Fixes in this Release	17-16
17.2.6	Migrating OracleBI Discoverer Plus Relational Worksheets from OracleBI Discoverer Desktop	17-16
17.2.7	Issue When Canceling Running Query	17-16
17.2.8	Scheduled Workbooks and Aggregation in OracleBI Discoverer Plus Relational	17-16
17.3	Oracle Business Intelligence Discoverer Plus OLAP	17-17
17.3.1	Issues with Applet Download	17-17
17.3.2	Disabled Netscape and Mozilla Browsers.....	17-17
17.3.3	Tabbing Fails to Synchronize Menus.....	17-17
17.3.4	ESC Key Fails to Close Certain Dialogs.....	17-17
17.3.5	Link Tool Works Incorrectly in Some Locales.....	17-18
17.3.6	Memory Issues when Exporting Extremely Large Graphs	17-18
17.3.7	Page Setup Dialog Appearing Blank	17-18
17.3.8	Printing Worksheets with Large Data Values	17-18
17.3.9	Issues with Titles and Text Areas.....	17-18
17.3.10	Issue Moving Worksheets While Opening the First Workbook.....	17-18
17.3.11	Errors with JAWS and Format Dialogs	17-18
17.3.12	Issue Exporting Discoverer Catalog with Non-ASCII Data	17-18
17.3.13	Corrections to the OracleBI Discoverer Plus OLAP Help.....	17-19
17.4	Oracle Business Intelligence Discoverer Portlet Provider	17-19
17.4.1	Inability to Turn Off Display of Range Min and Max as Labels.....	17-19
17.4.2	Using OracleBI Discoverer Portlet Provider with OracleAS Single Sign-On and Secure Sockets Layer (SSL) Modes	17-19
17.4.3	Documentation Corrections	17-20
17.4.3.1	Refresh Options page Help topic	17-20
17.4.3.2	Review Portlet Defaults page Help topic.....	17-20
17.4.3.3	Select Database Connections page (Customize mode) Help topic.....	17-21
17.4.3.4	Database Connections page Help topic.....	17-21
17.5	Oracle Business Intelligence Discoverer Viewer	17-21
17.5.1	Drill Icons Cannot Be Hidden in OracleBI Discoverer Viewer	17-22

17.5.2	Error Sending E-mail in OracleBI Discoverer Viewer	17-22
17.5.3	Error Displaying Page for Multiple SSO Users	17-22
17.5.4	Inability to Disable the Display of Row Numbers	17-22
17.5.5	Issues with OracleBI Discoverer Viewer Embedded in Frames	17-22
17.5.6	Issue Exporting to PDF Under Certain Circumstances.....	17-23
17.5.7	Known Bug with JAWS Prevents Drilling using Enter Key.....	17-23
17.5.8	JAWS Does Not Read Asterisks that Precede Fields	17-23
17.5.9	Corrections to the OracleBI Discoverer Viewer Help.....	17-24
17.5.9.1	References to the Connect to Discoverer Viewer page	17-24
17.5.9.2	List of Worksheets page Help topic	17-24
17.5.9.3	Printable Page Options page: Content Tab Help topic	17-24
17.5.9.4	Preferences page Help topic	17-24
17.5.9.5	Task steps in the "How do I create and save login information in a Discoverer connection?" Help topic	17-24
17.5.10	Discoverer Catalog Items Not Visible From UNIX Servers.....	17-25
17.5.11	OracleBI Discoverer Viewer Pages are not Cached by OracleAS Web Cache.....	17-25
17.6	Oracle Business Intelligence Discoverer EUL Command Line for Java	17-26
17.6.1	Issue with Exported Non-ASCII Data	17-26
17.7	Known Issues with Oracle OLAP Option	17-26

18 Oracle Reports

18.1	General Issues and Workarounds	18-1
18.1.1	Using the New Auto Save Feature in Reports Builder	18-2
18.1.2	OracleAS Reports Services Demos Will Not Work If JServ Is Configured	18-3
18.1.3	JSP Report Does Not Run in Oracle JDeveloper on UNIX	18-3
18.1.4	Error While Editing Batch Registered Report in OracleAS Portal.....	18-3
18.1.5	Limitation on Linked Queries for DelimitedData Output.....	18-3
18.1.6	Summary Column Not Aligned for JSP-Based Web Reports with Group Above and Matrix Style	18-4
18.1.7	Images in HTML Output of Oracle Reports Not Displayed When Viewed from Oracle Enterprise Manager 10g	18-4
18.1.8	Misalignment in Large Multibyte Reports When Using the Enhanced Font Subsetting Feature with Acrobat Reader 7.0	18-4
18.1.9	PL/SQL Compilation Failure When Using SQL Constructs.....	18-5
18.1.10	PL/SQLPackage Specification and/or Body Lost When Saving Report As XML..	18-5
18.1.11	Incorrect Color for Multiline Text in Paper Design View When Inline HTML Tags Are Used	18-6
18.1.12	Running Oracle Reports	18-6
18.2	Vendor-Specific Issues and Workarounds	18-7
18.2.1	Underlines Do Not Display in HTMLCSS Output in Browser	18-7
18.2.2	JSP-Based Web Report with Large Number of Columns Generates JSP Compilation Error	18-7
18.2.3	Java AWT Windows Hangs with Specific Graphics Cards	18-7
18.3	Globalization Support Issues and Workarounds	18-8
18.3.1	Images Do Not Display Correctly in Turkish Environment	18-8
18.3.2	MS Mincho Font in PostScript Font Mapping Does Not Work When NLS_LANG is Specified As JA16EUC	18-8
18.3.3	Multibyte Reports Containing Oracle Object Types Hang Report Builder.....	18-8

18.3.4	Reports Server's Job Status Messages in Application Server Control Contain Invalid Characters	18-8
18.3.5	ENVID Ignored While Detecting Duplicate Job.....	18-9

19 Oracle Internet Directory

19.1	Configuration Issues and Workarounds	19-1
19.1.1	Configuring Oracle Internet Directory Fan-out Replication	19-1
19.2	Administration Issues and Workarounds	19-1
19.2.1	Recommended Password Policy Values	19-1
19.3	Documentation Errata	19-2
19.3.1	Parameters in init\$ORACLE_SID.ora are Not Loaded Automatically at Database Startup	19-2
19.3.2	ODM Online Help Might Have Extra Pages in Non-English Locales	19-2

20 Oracle Delegated Administration Services

20.1	General Issues and Workarounds	20-1
20.1.1	Roles with No Members Are not Displayed in Role Assignment Section in Create/edit User	20-1
20.1.2	Resetting Oracle Application Server Single Sign-On Passwords Redirects Users to Oracle Delegated Administration Services Home Page	20-2
20.1.3	Exception Thrown in One-Level Realm Scenarios.....	20-2
20.1.4	Upgrading Oracle Application Server to 10g Release 2 (10.1.2) May Overwrite Custom Ordering of User Attribute Categories in Oracle Delegated Administration Services	20-2
20.2	Administration Issues and Workarounds	20-3
20.2.1	Enforcing Assignment and Revocation of Privileges Requires Starting a New Self-Service Console Session	20-3
20.2.2	Unified Messaging Voicemail PIN Field Mislabeled in Oracle Internet Directory Self-Service Console	20-3
20.2.3	Unlocking Privileged User Accounts	20-3
20.2.4	Create/Edit User Windows in Oracle Internet Directory Self-Service Console Display Two Time Zone Fields	20-4

21 Oracle Directory Integration and Provisioning

21.1	Configuration Issues and Workarounds	21-1
21.1.1	Two Oracle Internet Directory Plug-in Features Are not Supported after Upgrade to Oracle Internet Directory 10g Release 2 (10.1.2)	21-1
21.2	Administration Issues and Workarounds	21-1
21.2.1	Default Mapping Rule Can Be Simplified in Single-Domain Microsoft Active Directory Deployments	21-2
21.2.2	Directory Integration and Provisioning Assistant Does not Support SSL Mode 2.	21-2
21.2.3	Shell Script-based Profile Configuration Tools Are Being Deprecated	21-2
21.2.4	In a High Availability Environment Using Multimaster Replication, Provisioning Events May not Be Propagated or May Be Duplicated	21-2
21.2.5	The Oracle Directory Integration and Provisioning Server May not Shut Down if It Is Stopped and Immediately Restarted	21-2
21.2.6	Oracle Directory Integration and Provisioning Server Not Sending Provisioning Events Due to Purged Change Log Entries	21-3

22 Oracle Application Server Single Sign-On

22.1	Configuration Issues and Workarounds	22-1
22.1.1	Additional High Availability Configuration Instructions	22-1
22.1.1.1	Update the mod_rewrite Entry for SSO	22-1
22.1.1.2	Update targets.xml	22-2
22.2	Issues and Workarounds Related to Oracle Database.....	22-3
22.2.1	Issues With Upgrading the Oracle Database	22-3

23 Oracle Application Server Certificate Authority

23.1	General Issues and Workarounds	23-1
23.1.1	Adding "\" to RDN Causes Misprocessing	23-1
23.1.2	Third Party Wallet Import Fails Due To localID Value	23-1
23.1.3	DN Validation Does Not Correctly Check "=" Character	23-2
23.2	Configuration Issues and Workarounds	23-2
23.2.1	Unexpected Behavior After Revoking Web Administrator or CA Certificate	23-2
23.2.2	Allowable Values of Predicate Usage	23-2

24 Oracle Enterprise Manager

24.1	General Issues and Workarounds	24-1
24.1.1	Problems with the Oracle Enterprise Manager 10g Application Server Control Console After Deinstalling Oracle Application Server 9.0.2 or 9.0.3	24-2
24.1.2	Setting NLS and Operating System Locale Environment Variables Before Starting Management Processes	24-3
24.1.2.1	Checking the Operating System Locale	24-3
24.1.2.2	Setting the Operating System Locale	24-3
24.1.2.3	Checking the NLS_LANG Environment Variable.....	24-3
24.1.2.4	Setting the NLS_LANG Environment Variable	24-4
24.1.3	Misleading Error Message When Applying Properties to an OC4J Instance within an Oracle Application Server Cluster	24-4
24.1.4	Errors When Configuring Components or Adding or Removing OC4J Instances.	24-4
24.1.5	Problem Viewing Performance Charts and Configuring Identity Management Using a Macintosh Browser	24-4
24.1.6	Problems with the Progress Page When Using a Macintosh Browser.....	24-5
24.1.7	Topology Viewer Applet Fails in OracleAS Cold Failover Cluster Configuration.	24-6
24.1.8	Error When Clicking Topology Link from Host Page.....	24-6
24.1.9	Error When Using the ADF BUSINESS COMPONENT Link on the Host Page....	24-6
24.1.10	Farm Locator Link Lost.....	24-6
24.1.11	Incorrect Status Reported for Oracle Business Intelligence Discoverer	24-6
24.1.12	Changing From JAZN LDAP User Manager Requires OC4J Restart	24-7
24.1.13	Posting Data From the Logging Pages	24-7
24.1.14	Additional Step When Removing an Application Server Target From the Grid Control Console	24-7
24.1.15	Security Considerations When Changing Schema Passwords with the Application Server Control Console	24-7
24.1.16	Problems Viewing Some Metrics When OracleAS Portal is Configured for Secure Sockets Layer (SSL)	24-8
24.1.17	Cannot Recover Database Control Files from the Application Server Control Console...	

	24-10
24.1.18	Problem Using the Topology Viewer to Perform Operations on an OracleAS Farm When in French or French-Canadian Language Environment	24-10
24.1.19	Configuring Security When Oracle Application Server Is Managed by Grid Control.....	24-10
24.1.20	Blank Screen When Attempting to Display Application Server Control Console in Internet Explorer	24-11
24.1.21	Incorrect Memory Usage Is Reported for Forms on SLES9	24-11
24.1.22	Harmless Errors in Log Files	24-12
24.1.23	Enterprise Manager Agent Restarts Periodically When JVM Size Is Full	24-13
24.2	Documentation Errata	24-14
24.2.1	Online Help for the Application Server Control All Metrics Page	24-14
24.2.2	Error in Online Help Topic About Regular Expressions	24-14

Preface

This preface includes the following topics:

- [Audience](#)
- [Documentation Accessibility](#)
- [Related Documents](#)
- [Conventions](#)

Audience

This document is intended for users of Oracle Application Server 10g.

Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at

<http://www.oracle.com/accessibility/>

Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

TTY Access to Oracle Support Services

Oracle provides dedicated Text Telephone (TTY) access to Oracle Support Services within the United States of America 24 hours a day, seven days a week. For TTY support, call 800.446.2398.

Related Documents

For more information, see these Oracle resources:

- Oracle Application Server Documentation on Oracle Application Server Disk 1
- Oracle Application Server Documentation Library 10g Release 2 (10.1.2)

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
<code>monospace</code>	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

What's New

This chapter provides a listing of new topics introduced with this version of *Oracle Application Server Release Notes*. The new topics are in the following chapters:

- [Chapter 9, "Oracle Application Server Portal"](#)
- [Chapter 17, "Oracle Business Intelligence"](#)

Chapter 9, "Oracle Application Server Portal"

- [Section 9.1.1.9, "Oracle Text Support"](#)
- [Section 9.1.4.10, "Error While Adding Portlets"](#)

Chapter 17, "Oracle Business Intelligence"

- [Section 17.1.15, "Issues with Mac OS X Browser and OracleBI Discoverer Plus"](#)
- [Section 17.2.7, "Issue When Canceling Running Query"](#)
- [Section 17.2.8, "Scheduled Workbooks and Aggregation in OracleBI Discoverer Plus Relational"](#)
- [Section 17.5.11, "OracleBI Discoverer Viewer Pages are not Cached by OracleAS Web Cache"](#)

Introduction

This chapter introduces Oracle Application Server Release Notes, 10g Release 2 (10.1.2). It includes the following topics:

- [Section 1.1, "Latest Release Information"](#)
- [Section 1.2, "Purpose of this Document"](#)
- [Section 1.3, "Operating System Requirements"](#)
- [Section 1.4, "Certification Information"](#)
- [Section 1.5, "Licensing Information"](#)

1.1 Latest Release Information

This document is accurate at the time of publication. Oracle will update the release notes periodically after the software release. You can access the latest information and additions to these release notes on the Oracle Technology Network at

<http://www.oracle.com/technology/documentation/>

1.2 Purpose of this Document

This document contains the release information for Oracle Application Server 10g Release 2 (10.1.2). It describes differences between Oracle Application Server 10g Release 2 (10.1.2) and its documented functionality.

Oracle recommends you review its contents before installing, or working with the product.

1.3 Operating System Requirements

Oracle Application Server installation and configuration will not complete successfully unless users meet the hardware and software pre-requisite requirements before installation. Refer to *Oracle Application Server Installation Guide* for a complete list of operating system requirements.

1.4 Certification Information

The latest certification information for Oracle Application Server 10g Release 2 (10.1.2) is available at:

<http://metalink.oracle.com>

1.5 Licensing Information

Licensing information for Oracle Application Server 10g Release 2 (10.1.2) is available at:

<http://oraclestore.oracle.com>

Detailed information regarding license compliance for Oracle Application Server 10g Release 2 (10.1.2) is available at:

<http://www.oracle.com/technology/products/ias/index.html>

Installation and Upgrade Issues

This chapter describes installation and upgrade issues and their workarounds associated with Oracle Application Server. It includes the following topics:

- [Section 2.1, "Installation Issues"](#)
- [Section 2.2, "Oracle Application Server Companion CD 10g \(10.1.2.0.2\)"](#)
- [Section 2.3, "Documentation Errata"](#)

2.1 Installation Issues

This section describes issues with installation of Oracle Application Server. It includes the following topics:

- [Section 2.1.1, "Locales zh_TW.EUC and zh_TW in Traditional Chinese Environments Not Supported in the OracleAS Portal Component"](#)
- [Section 2.1.2, "Characters Dropped or Truncated"](#)
- [Section 2.1.3, "Failure of File-Based Farm Repository Configuration Assistant"](#)
- [Section 2.1.4, "Non-English Welcome Pages URL Link Pages Incorrectly Coded"](#)
- [Section 2.1.5, "Distributed OracleAS Metadata Repository and Oracle Internet Directory on Separate Computers Throws Error"](#)
- [Section 2.1.6, "Welcome Link Coded Incorrectly"](#)
- [Section 2.1.7, "OracleAS Metadata Repository Creation Assistant Should Not Allow Loading into Oracle 10.1.0.4 Database"](#)
- [Section 2.1.8, "Installing 10.1.2.0.2 Middle Tiers Against an Existing Infrastructure"](#)
- [Section 2.1.9, "IBM WebSphere Required Patch Version 6.0.2"](#)
- [Section 2.1.10, "Disk Space Needed on a Database that Uses Automatic Storage Management"](#)
- [Section 2.1.11, "Oracle Ultra Search Required \(Oracle Database 10g Release 2 \(10.2.x\) only\)"](#)
- [Section 2.1.12, "Patch Required Prior to Running the Metadata Repository Creation Assistant on a 10.2 Real Application Cluster Database"](#)
- [Section 2.1.13, "Populate DB_DOMAIN Before Running Oracle Metadata Repository Creation Assistant on an Oracle 10.2 Database"](#)
- [Section 2.1.14, "Installer Displays Incorrect Version Number"](#)

- [Section 2.1.15, "JAccelerator \(Ncomp\) Is Not Installed with OracleAS Metadata Repository 10.1.2.x"](#)
- [Section 2.1.16, "Error While Setting Kernel Parameters for Oracle AS Web Cache and Setting Shell Limits"](#)
- [Section 2.1.17, "Do Not Use the Underscore Character in Host Name"](#)
- [Section 2.1.18, "Installing Oracle Application Server Middle Tier against a Real Application Clusters Database when Some of the Nodes are Down"](#)
- [Section 2.1.19, "Additional Step Required When Installing OracleAS Web Cache on Multihomed \(Multi-IP\) Computers"](#)
- [Section 2.1.20, "Configuring OracleAS Web Cache to Work Within an OracleAS Cold Failover Cluster"](#)
- [Section 2.1.21, "Turkish Locale Does Not Display Correctly"](#)

2.1.1 Locales zh_TW.EUC and zh_TW in Traditional Chinese Environments Not Supported in the OracleAS Portal Component

If you try to install the OracleAS Portal component on a computer where the locale is set to zh_TW.EUC or zh_TW in Traditional Chinese environments, the installer will pause indefinitely because of the Java encoder behavior for these locales.

The workaround is to use the zh_TW.BIG5 locale in these environments. This requirement applies during installation only. After installation, you can reset the locale to the original locale.

2.1.2 Characters Dropped or Truncated

In locales where the zh_CN.GB18030 character set is used, input and output operations cause some characters to be dropped or truncated due to a problem in the `sun.io.CharToByteGB18030` converter of the Java Developer Kit (JDK).

To avoid this problem, do not use zh_CN.GB18030 as the character set for Oracle Internet Directory in your locale. Oracle recommends using the zh_CN.GBK or zh_CN.GB2312 character sets.

2.1.3 Failure of File-Based Farm Repository Configuration Assistant

If you select **Stop**, and then select **Retry** during operation of the File-Based Farm Repository Configuration Assistant in the Oracle Universal Installer, the configuration assistant fails and displays the following message:

```
This instance is already a member of a farm. An Oracle Application Server instance
cannot be moved directly from one farm to another.
```

There is presently no workaround for this issue.

2.1.4 Non-English Welcome Pages URL Link Pages Incorrectly Coded

Non-English Oracle Internet Directory Welcome pages files have some of the URL links coded incorrectly. The incorrectly coded Welcome pages point to `.html` URL destinations instead of `.htm` URL destinations. You will receive a `Page Not Found` error message if you encounter this issue.

If you encounter this issue, change the URL extension in the address bar of your Web browser to `.htm` instead of `.html`.

2.1.5 Distributed OracleAS Metadata Repository and Oracle Internet Directory on Separate Computers Throws Error

If you have distributed infrastructure environment with an OracleAS Metadata Repository on computer 1, and an Oracle Internet Directory installation on computer 2, the Oracle Internet Directory will not allow registration of the OracleAS Metadata Repository and will throw an error message similar to the following:

```
MR Already registered.
The service name is already registered with the specified Oracle Internet
Directory by the database containing OracleAS Metadata Repository on computer 2.
To continue with the registration, please remove existing registration in the
Oracle Internet Directory.
```

This problem occurs if both database SIDs are the same.

2.1.6 Welcome Link Coded Incorrectly

In the Forms and Reports Services Welcome pages, the Welcome link at the bottom of the pages is coded incorrectly. Users should use the Welcome tab at the top of the pages for navigation.

2.1.7 OracleAS Metadata Repository Creation Assistant Should Not Allow Loading into Oracle 10.1.0.4 Database

OracleAS Metadata Repository Creation Assistant allows loading into the Oracle 10.1.0.4 database; unfortunately, this should not be allowed by the program. The OracleAS Metadata Repository Creation Assistant program should perform a prerequisite check for this but it does not.

2.1.8 Installing 10.1.2.0.2 Middle Tiers Against an Existing Infrastructure

You can install 10g Release 2 (10.1.2.0.2) middle tiers against an existing Infrastructure. Specifically, during the 10.1.2.0.2 middle-tier installation procedure, specify the connection details for the existing 10g Release 2 (10.1.2.0.0) Identity Management, and 10.1.2.0.0 or 10g (9.0.4) OracleAS Metadata Repository as described in the *Oracle Application Server Installation Guide*.

The following are supported configurations with the 10.1.2.0.2 middle tier:

- 10.1.2.0.0 Identity Management and 10g (9.0.4) OracleAS Metadata Repository
- 10.1.2.0.0 Identity Management and 10.1.2.0.0 OracleAS Metadata Repository
- 10.1.2.0.2 Identity Management and 10.1.2.0.0 OracleAS Metadata Repository

For more information about compatibility issues between 10g Release 2 (10.1.2.0.2) and 10g Release 2 (10.1.2.0.0), see "Understanding Version Compatibility" in *Oracle Application Server Upgrade and Compatibility Guide*.

2.1.9 IBM WebSphere Required Patch Version 6.0.2

If you are using IBM WebSphere Application Server, install the following patch:
<http://www-1.ibm.com/support/docview.wss?rs=180&uid=swg24009813>

Doing so will help you avoid problems when using Oracle Industrial Telnet Server and (potentially) other products.

2.1.10 Disk Space Needed on a Database that Uses Automatic Storage Management

If you are installing OracleAS Metadata Repository on a database that uses Automatic Storage Management (ASM), make sure the disk group has at least 2 GB of disk space for the OracleAS Metadata Repository tablespaces. This is in addition to the space needed for the SYSTEM and UNDO tablespaces.

2.1.11 Oracle Ultra Search Required (Oracle Database 10g Release 2 (10.2.x) only)

If you plan to install the OracleAS Metadata Repository on Oracle Database 10g Release 2 (10.2.x), then you must install Oracle Ultra Search on the database.

OracleAS Metadata Repository Creation Assistant checks if your database contains the WKSYS and WKPROXY schema. If your database does not contain them, OracleAS Metadata Repository Creation Assistant displays the following warning:

"The Database does not contain Ultra Search Schemas WKSYS and/or WKPROXY. Please install them and try again. Refer to the *Database Install Guide and Ultra Search User Guide* for more information."

If your database does not have Oracle Ultra Search installed, you can install it from the Oracle Database 10g Companion CD-ROM. See the *Oracle Database Companion CD Installation Guide* for details.

After installing Oracle Ultra Search, you need to load the schemas onto the database using the Database Configuration Assistant (DBCA). Refer to Oracle *MetaLink* (<http://www.metalink.oracle.com>) Note 337992.1 for loading Ultra Search schemas.

2.1.12 Patch Required Prior to Running the Metadata Repository Creation Assistant on a 10.2 Real Application Cluster Database

You must install ARU patch 7993184 before running the Metadata Repository Creation Assistant on a 10.2 Real Application Cluster Database. If you do not apply the patch, you will receive an error message during Oracle Ultra Search configuration.

To apply the patch:

1. Install the 10.2 Real Application Cluster database.
2. Create the database using the DBCA or during the installation.
3. Stop all Oracle Processes.
4. Install Oracle Ultra Search in the same Oracle home from the companion CD.
5. Apply ARU patch 7993184. Go to Oracle *MetaLink* (<http://www.metalink.oracle.com>) to obtain the ARU patch.
6. Invoke the DBCA to configure Oracle Ultra Search.
7. Run the Metadata Repository Creation Assistant.

2.1.13 Populate DB_DOMAIN Before Running Oracle Metadata Repository Creation Assistant on an Oracle 10.2 Database

The default installation option for Oracle Database 10g (Release 2) 10.2 does not populate the DB_DOMAIN. The OracleAS Metadata Repository Creation Assistant uses the value of DB_DOMAIN to construct the Oracle Application Server farm name as \$SID.\$DB_DOMAIN. You should ensure that the DB_DOMAIN is populated in the database with a valid value prior to running OracleAS Metadata Repository Creation

Assistant. Failure to do will result in the default farm name of
REGRESS . RDBMS . DEV . US . ORACLE . COM.

2.1.14 Installer Displays Incorrect Version Number

The installer for the OracleAS Metadata Repository Creation Assistant displays the incorrect version number for the OracleAS Metadata Repository. The installer displays (10.1.2.0.2); the version number displayed should be (10.1.2.0.3).

This issue can be ignored during installation.

2.1.15 JAccelerator (Ncomp) Is Not Installed with OracleAS Metadata Repository 10.1.2.x

You will receive the following error message when you run the `catpatch.sql` script after Oracle Database 10.1.0.5 Patch Set application on OracleAS Metadata Repository 10.1.2.x:

```
"select dbms_java.full_ncomp_enabled from dual
ERROR at line 1: ORA-29558: JAccelerator (NCOMP) not installed. Refer to Install
Guide for instructions. ORA-6512: at "SYS.DBMS_JAVA", line 236."
```

You can ignore this error message. JAccelerator (Ncomp) is not installed with OracleAS Metadata Repository 10.1.2.x.

2.1.16 Error While Setting Kernel Parameters for Oracle AS Web Cache and Setting Shell Limits

After setting kernel parameters for Oracle AS Web Cache and Setting Shell limits, when you run `ulimit -hn` command, the value does not change. It remains 1024. Also, when you use the `su` command to change to the oracle user, the following error is displayed:

```
ksh /etc/profile[291]: ulimit: exceeds allowable limit
```

To workaround these issues, add the following parameter to the `/etc/pam.d/xdm` file:

```
session    required    /lib/security/pam_limits.so
```

2.1.17 Do Not Use the Underscore Character in Host Name

Do not use the underscore character (`_`) as part of the host name for your Oracle Application Server installation. For example, `yourbusiness_name`

2.1.18 Installing Oracle Application Server Middle Tier against a Real Application Clusters Database when Some of the Nodes are Down

If you are installing an Oracle Application Server middle tier against a Metadata Repository located on a Real Application Clusters database and some of the nodes of the database are down, you must remove the nodes that are down from the database. Following installation of Oracle Application Server middle tier, these nodes can be added back to the database.

2.1.19 Additional Step Required When Installing OracleAS Web Cache on Multihomed (Multi-IP) Computers

If you specify the secondary hostname using the OUI_HOSTNAME parameter to start up the installer as outlined in the *Oracle Application Server Installation Guide*, and you are installing OracleAS Web Cache, the OPMN configuration assistant gives the following error:

The OPMN config assistant fails.

The log files located at `ORACLE_HOME/opmn/logs/WebCache~WebCacheAdmin~1` and `ORACLE_HOME/opmn/logs/WebCache~WebCache~1` contain the following error:

```
No matching CACHE element found in webcache.xml for current hostname
(primary_hostname) and ORACLE_HOME (/u00/product/as1012secondary)
webcache/webcache.xml contains:
```

```
<CACHE NAME="secondary_hostname-WebCache" [...]
      HOSTNAME="secondary_hostname" [...]
```

To correct this error, perform the following steps:

1. Locate the `webcache.xml` file and open the file for editing.
2. Locate the following lines in the `webcache.xml` file:

```
<CACHE NAME="secondary_hostname-WebCache" [...]
      HOSTNAME="secondary_hostname" [...]
```

3. Replace the HOSTNAME of the CACHE element with the primary hostname:

```
<CACHE NAME="secondary_hostname-WebCache" [...]
      HOSTNAME="primary_hostname" [...]
```

2.1.20 Configuring OracleAS Web Cache to Work Within an OracleAS Cold Failover Cluster

Additional configuration steps are required to configure OracleAS Web Cache to work with a OracleAS Cold Failover Cluster.

Perform the following steps to configure OracleAS Web Cache. In these steps, `host1` is the virtual hostname of the active node and `host2` is the virtual hostname of the passive node.

1. Locate and open the `webcache.xml` file.
2. Locate the CACHE element:

```
<CACHE NAME="host1-WebCache" ORACLEHOME="/myoraclehome/oracle"
      HOSTNAME="host1" VOTES="1" CAPACITY="30" >
...
...
</CACHE>
```

3. Add a second CACHE element below the CACHE element you located. Copy and paste the first CACHE element below the first one:

```
<CACHE NAME="host1-WebCache" ORACLEHOME="/myoraclehome/oracle"
      HOSTNAME="host1" VOTES="1" CAPACITY="30" >
...
...
</CACHE>
<CACHE NAME="host1-WebCache" ORACLEHOME="/myoraclehome/oracle"
```



```

        HOSTNAME="host1" VOTES="1" CAPACITY="30" >
...
</CACHE>

```

4. Replace the hostname of the second CACHE element with the hostname of the passive node of your cluster:

```

<CACHE NAME="host1-WebCache" ORACLEHOME="/myoraclehome/oracle"
        HOSTNAME="host1" VOTES="1" CAPACITY="30" >
...
...
</CACHE>
<CACHE NAME="host1-WebCache" ORACLEHOME="/myoraclehome/oracle"
        HOSTNAME="host2" VOTES="1" CAPACITY="30" >
...
</CACHE>

```

5. Save the file.
6. Restart OracleAS Web Cache.

2.1.21 Turkish Locale Does Not Display Correctly

When running the Oracle Universal Installer to install Oracle Application Server using the Turkish locale, the Configuration Assistant page will not display properly.

2.2 Oracle Application Server Companion CD 10g (10.1.2.0.2)

This section describes information pertaining to the Oracle Application Server Companion CD 10g (10.1.2.0.2). It includes the following topics:

- [Section 2.2.1, "System Requirements for Oracle Application Server Companion CD 10g"](#)
- [Section 2.2.2, "Oracle Sensor Edge Server Administrator's Guide"](#)
- [Section 2.2.3, "Install Button on Companion CD Summary Screen Is Disabled"](#)

2.2.1 System Requirements for Oracle Application Server Companion CD 10g

[Table 2–1](#) lists the system requirements for the products on the Oracle Application Server Companion CD 10g (10.1.2.0.2):

Table 2–1 System Requirements

Product	Required Disk Space	Required Memory
Oracle Application Server Containers for J2EE	56 MB	512 MB
Oracle Application Server TopLink	220 MB	192 MB
Oracle Sensor Edge Server	180 MB	512 MB
Oracle HTTP Server with Apache 1.3	550 MB	512 MB
Oracle HTTP Server with Apache 2.0	450 MB	512 MB
OracleAS Web Cache	400 MB	512 MB

For operating system and hardware requirements, go to:

<http://metalink.oracle.com>.

2.2.2 Oracle Sensor Edge Server Administrator's Guide

The *Oracle Sensor Edge Server Administrator's Guide* (Part No. B14455-02) in the Oracle Application Server 10g Release 2 (10.1.2) documentation library is available on OTN (<http://www.oracle.com/technology/products>).

2.2.3 Install Button on Companion CD Summary Screen Is Disabled

If Oracle Universal Installer prerequisite check fails with warnings, and you proceed to the Install Products screen from Oracle AS 10g Companion CD, then the Install button is disabled on the Summary page.

2.3 Documentation Errata

The section describes documentation errata in installation and upgrade documentation. It includes the following topics:

- [Section 2.3.1, "Additional Steps for OracleAS Single Sign-On HA Configuration"](#)
- [Section 2.3.2, "Incorrect File Extensions in Installed Documentation"](#)
- [Section 2.3.3, "Incorrect Path for OracleAS Upgrade Assistant Log File"](#)
- [Section 2.3.4, "Incorrect Version Number on Forms and Reports CD-ROM"](#)
- [Section 2.3.5, "Incorrect Copyright Information"](#)
- [Section 2.3.6, "Incorrect Media Reference in Oracle Application Server Installation Guide"](#)
- [Section 2.3.7, "Invalid Instruction to Apply Database Patch"](#)
- [Section 2.3.8, "Incorrect OID Port for Silent Installations"](#)
- [Section 2.3.9, "Incorrect Environmental Variable Recommendation"](#)
- [Section 2.3.10, "Invalid Limitation on Installing Oracle Application Server in an OracleAS Disaster Recovery Environment"](#)
- [Section 2.3.11, "Error While Setting Kernel Parameters for Oracle AS Web Cache and Setting Shell Limits"](#)
- [Section 2.3.12, "Incorrect Symbolic Link Creation Command"](#)

2.3.1 Additional Steps for OracleAS Single Sign-On HA Configuration

Additional steps are required after OracleAS Infrastructure is installed with the OracleAS Cluster (Identity Management) option for OracleAS Single Sign-On. For more information refer to [Section 22.1.1, "Additional High Availability Configuration Instructions"](#).

2.3.2 Incorrect File Extensions in Installed Documentation

Documentation that is installed with Oracle Application Server 10g does not use standard file extensions to indicate the applicable language. For example, Chinese files (along with any other file that has an underscore in the extension) are not picked up.

To workaround this issue, change the following file extensions in the `ORACLE_HOME/ohs/htdocs` directory and all `ORACLE_HOME/ohs/htdocs` subdirectories:

- `zh_CN -> zh-CN`
- `pt_BR -> pt-BR`

- es_ES -> es-ES
- fr_CA -> fr-CA
- zh_TW -> zh-TW

2.3.3 Incorrect Path for OracleAS Upgrade Assistant Log File

Due to a typographical error, the *Oracle Application Server Quick Upgrade Guide* incorrectly identifies the path to the OracleAS Upgrade Assistant log file. The error occurs in the section on troubleshooting the middle-tier upgrade procedure.

The actual location of the OracleAS Upgrade Assistant log file is:

`DESTINATION_ORACLE_HOME/upgrade/log/iasua.log`

2.3.4 Incorrect Version Number on Forms and Reports CD-ROM

The upgrade.txt file on the Forms and Reports Services installation CD-ROM summarizes how you can upgrade to the Oracle Application Server 10g Release 2 (10.1.2.0.2) Forms and Reports Services installation type.

However, the version number included in that file is incorrect. All references to version 10.1.2.0.1 in that file should in fact be references to version 10.1.2.0.2.

2.3.5 Incorrect Copyright Information

The copyright date in the **Copyright Information** help topic incorrectly shows the copyright date range. The date range should be: **Copyright © 1996-2005, Oracle. All rights reserved.**

The link at the bottom of most of the help topics does indicate the proper trademark date range; it's only the copyright information topic itself that contains the incorrect copyright date range.

2.3.6 Incorrect Media Reference in Oracle Application Server Installation Guide

In the *Oracle Application Server Installation Guide* there are two incorrect references to installation media.

- OracleAS Guard can be installed as a standalone install kit located on OracleAS Utility media #2.

should be:

OracleAS Guard can be installed as a standalone install kit located on OracleAS Companion CD #2.

- OracleAS 10g (10.1.2.0.2) standalone install of OracleAS Guard is located on Utilities Disk 2.

should be:

OracleAS 10g (10.1.2.0.2) standalone install of OracleAS Guard is located on Companion CD Disk 2.

2.3.7 Invalid Instruction to Apply Database Patch

In Section 1.5.2.2, "Oracle9i Release 2 (9.2.0.6) Real Application Clusters Databases" in *Oracle Application Server Metadata Repository Creation Assistant User's Guide 10g Release 2 (10.1.2) for UNIX*, the following information is displayed:

"If you are running a Release 2 (9.2.0.6) database in a Real Application Clusters environment, you need to apply patch 3047933 (ARU 6662789) before you can load the OracleAS Metadata Repository on your database."

This information is incorrect. There is no patch application required.

2.3.8 Incorrect OID Port for Silent Installations

In *Oracle Application Server Installation Guide*, the OID port used during a silent installation is mentioned as port 389. However, port 389 is a privileged port and requires root access. In a silent installation, root access is not granted until the installation is over. Therefore, if you use port 389, then the following occurs:

```
OID not able to startup
```

To avoid this error, do not use the OID port number mentioned in the silent installation example of the installation guide. A commonly used default non-SSL port selected by OUI for OID is 3060. For SSL, this port is 3131. However, in the response file, you only need to specify the non-SSL port.

2.3.9 Incorrect Environmental Variable Recommendation

Section 4.8.3, "Installing on Computers with Multiple Aliases" of the *Oracle Application Server Installation Guide* incorrectly recommends to use the `ORACLE_HOSTNAME` variable. If you use the environment variable `ORACLE_HOSTNAME` as indicated in the Oracle Application Server Installation Guide, Oracle Universal Installer will exit while copying files. Attempts to use other measures during installation, (for example, loopback adapter) will also fail. Before installing Oracle Application Server on the referenced configuration, set the `OUI_HOSTNAME` environment variable to the computer whose hostname you want to use.

2.3.10 Invalid Limitation on Installing Oracle Application Server in an OracleAS Disaster Recovery Environment

Section 13.3.1, "Installing the OracleAS Infrastructure" in the Oracle Application Server Installation Guide reads:

"You must install the Oracle Identity Management and the OracleAS Metadata Repository components of OracleAS Infrastructure on the same node. You cannot distribute the components over multiple nodes."

This limitation is not true.

2.3.11 Error While Setting Kernel Parameters for Oracle AS Web Cache and Setting Shell Limits

Section 4.4.1, "Kernel Parameter Settings for OracleAS Web Cache" and section 4.5, "Set Shell Limits for the oracle User" of *Oracle Application Server Installation Guide* (B19310-03), states the kernel parameter commands and values.

When you run `ulimit -hn` command after performing the steps listed in the guide, the value does not change. It remains 1024. Also, when you use the `su` command to change to the oracle user, the following error is displayed:

```
ksh /etc/profile[291]: ulimit: exceeds allowable limit
```

To workaroud these issues, add the following parameter to the `/etc/pam.d/xdm` file:

```
session    required    /lib/security/pam_limits.so
```

2.3.12 Incorrect Symbolic Link Creation Command

In the section 5.6, "Can I use symbolic links?" the commands for creating the symbolic link is incorrect. The correct command is:

```
mkdir /home/basedir  
ln -s /home/basedir /home/linkdir
```

General Management and Security Issues

This chapter describes management and security issues associated with Oracle Application Server. It includes the following topics:

- [Section 3.1, "General Issues and Workarounds"](#)
- [Section 3.2, "Starting and Stopping Release 10.1.2.0.0"](#)
- [Section 3.3, "Port Change Issues"](#)
- [Section 3.4, "Cloning Issues"](#)
- [Section 3.5, "Deployment Issues"](#)
- [Section 3.6, "Documentation Errata"](#)

3.1 General Issues and Workarounds

This section describes general management and security issues. It includes the following topics:

- [Section 3.1.1, "Error Message When Executing opmnctl Commands"](#)

3.1.1 Error Message When Executing opmnctl Commands

When you execute either an `opmnctl stopall` or `opmnctl startall` command, the `oidctl` log file contains the following error message:

```
*** Instance Number already in use. ***  
*** Please try a different Instance number. ***
```

This error message can be safely ignored.

This error message occurs in Oracle Application Server Infrastructure installations with Oracle Internet Directory.

3.2 Starting and Stopping Release 10.1.2.0.0

The *Oracle Application Server Administrator's Guide* Release 10.1.2 describes how to start and stop instances using the `runstartupconsole` command. However, this command is not available in releases earlier than Release 10.1.2.0.2. The following sections describe how to start and stop with Release 10.1.2.0.0:

- [Section 3.2.1, "Starting OracleAS Infrastructure"](#)
- [Section 3.2.2, "Stopping OracleAS Infrastructure"](#)
- [Section 3.2.3, "Starting a Middle-Tier Instance"](#)

- [Section 3.2.4, "Stopping a Middle-Tier Instance"](#)

3.2.1 Starting OracleAS Infrastructure

To start all processes in a Release 10.1.2.0.0 OracleAS Infrastructure, follow the procedure in this section. This procedure applies to all OracleAS Infrastructure types:

- Oracle Identity Management and OracleAS Metadata Repository: Follow both steps to start Oracle Identity Management and OracleAS Metadata Repository.
- OracleAS Metadata Repository only: Follow only Step 1 to start OracleAS Metadata Repository. You do not need to perform the second step of starting Oracle Identity Management because you do not need OPMN or the Application Server Control Console in a OracleAS Metadata Repository-only installation.
- Oracle Identity Management only: Follow only Step 2 to start Oracle Identity Management. Make sure the OracleAS Metadata Repository that supports Oracle Identity Management (residing in another Oracle home) is already started.

To start OracleAS Infrastructure:

1. If your OracleAS Infrastructure contains OracleAS Metadata Repository, start it as follows:

- a. Set the `ORACLE_HOME` environment variable to the OracleAS Infrastructure Oracle home.
- b. Set the `ORACLE_SID` environment variable to the OracleAS Metadata Repository SID (default is `orcl`).
- c. Start the Net Listener:

```
ORACLE_HOME/bin/lsnrctl start
```

- d. Start the OracleAS Metadata Repository instance:

```
ORACLE_HOME/bin/sqlplus /nolog
SQL> connect SYS as SYSDBA
SQL> startup
SQL> quit
```

- e. Start the Oracle Enterprise Manager 10g Database Control:

```
ORACLE_HOME/bin/emctl start dbconsole
```

2. If your OracleAS Infrastructure contains Oracle Identity Management, start it as follows:

- a. Start components:

```
ORACLE_HOME/opmn/bin/opmnctl startall
```

This command starts OPMN and all OPMN-managed processes such as DCM, Oracle HTTP Server, OC4J instances, and Oracle Internet Directory.

- b. Start the Application Server Control Console:

```
ORACLE_HOME/bin/emctl start iasconsole
```

3.2.2 Stopping OracleAS Infrastructure

To stop all processes in a Release 10.1.2.0.0 OracleAS Infrastructure, follow the procedure in this section. This procedure applies to all OracleAS Infrastructure types:

- Oracle Identity Management and OracleAS Metadata Repository: Follow both steps to stop Oracle Identity Management and OracleAS Metadata Repository.
- OracleAS Metadata Repository only: Follow only step 2 to stop OracleAS Metadata Repository.
- Oracle Identity Management only: Follow only step 1 to stop Oracle Identity Management.

To stop OracleAS Infrastructure:

1. If your OracleAS Infrastructure contains Oracle Identity Management, stop it as follows:

- a. Stop the Application Server Control Console:

```
ORACLE_HOME/bin/emctl stop iasconsole
```

- b. Stop components:

```
ORACLE_HOME/opmn/bin/opmnctl stopall
```

This command stops OPMN and all OPMN-managed processes such as DCM, Oracle HTTP Server, OC4J instances, and Oracle Internet Directory.

2. If your OracleAS Infrastructure contains OracleAS Metadata Repository, stop it as follows:

- a. Set the ORACLE_HOME environment variable to the OracleAS Infrastructure Oracle home.

- b. Set the ORACLE_SID environment variable is set to the OracleAS Metadata Repository SID (default is orcl).

- c. Stop the OracleAS Metadata Repository instance:

```
ORACLE_HOME/bin/sqlplus /nolog
SQL> connect SYS as SYSDBA
SQL> shutdown
SQL> quit
```

- d. Stop the Net Listener:

```
ORACLE_HOME/bin/lsnrctl stop
```

- e. Stop the Oracle Enterprise Manager 10g Database Control:

```
ORACLE_HOME/bin/emctl stop dbconsole
```

3.2.3 Starting a Middle-Tier Instance

To start all processes in a Release 10.1.2.0.0 middle-tier instance, follow the procedure in this section. This procedure applies to all middle-tier instance types.

To start a middle-tier instance:

1. If the middle-tier instance uses OracleAS Infrastructure services, such as Oracle Identity Management or OracleAS Metadata Repository, make sure they are started.

2. Start components:

```
ORACLE_HOME/opmn/bin/opmnctl startall
```

This command starts OPMN and all OPMN-managed processes such as DCM, Oracle HTTP Server, OC4J instances, and OracleAS Web Cache, Forms, and Reports.

3. Start the Application Server Control Console:

```
ORACLE_HOME/bin/emctl start iasconsole
```

3.2.4 Stopping a Middle-Tier Instance

To start all processes in a Release 10.1.2.0.0 middle-tier instance, follow the procedure in this section. This procedure applies to all middle-tier instance types.

To stop a middle-tier instance:

1. Stop the Application Server Control Console:

```
ORACLE_HOME/bin/emctl stop iasconsole
```

2. Stop components:

```
ORACLE_HOME/opmn/bin/opmnctl stopall
```

This command stops OPMN and all OPMN-managed processes such as DCM, Oracle HTTP Server, OC4J instances, and OracleAS Web Cache, Forms, and Reports.

3.3 Port Change Issues

This section describes issues related to port changes. It includes the following topic:

- [Section 3.3.1, "Additional Step Needed After Changing Oracle HTTP Server Listen Port"](#)

3.3.1 Additional Step Needed After Changing Oracle HTTP Server Listen Port

After you change the Oracle HTTP Server Listen Port, you should update `portlist.ini` with the new port number. This will avoid potential problems if you later associate the middle tier with an OracleAS Infrastructure or change the OracleAS Infrastructure associated with the middle tier. The `portlist.ini` file is located in the following directory:

```
ORACLE_HOME/install
```

3.4 Cloning Issues

This section describes issues related to cloning Oracle Application Server instances. It includes the following topics:

- [Section 3.4.1, "Considerations for Cloning Oracle Ultra Search"](#)
- [Section 3.4.2, "Considerations for Cloning OracleBI Discoverer"](#)
- [Section 3.4.3, "Considerations for Cloning OracleAS Forms and Reports Services"](#)

3.4.1 Considerations for Cloning Oracle Ultra Search

When you clone an OracleAS Portal instance that has SSL enabled, the Ultra Search Administration link on the Services portlet and Application Server Control Console page point to the URLs for the source instance, not the cloned instance.

To work around this problem, edit the following file and update the `PortalListeningHostPort` property with the correct port number:

`Oracle_Home/sysman/emd/targets.xml`

The port number can be found in the following file:

`Oracle_Home/install/portlist.ini`

3.4.2 Considerations for Cloning OracleBI Discoverer

The following describes important information about cloning OracleBI Discoverer:

- Values set by users after installation in `configuration.xml` are not preserved in the cloned Oracle home. The file is located at:

`Oracle_Home/discoverer/config/configuration.xml`

To work around this problem, reset the overwritten values by copying them from the `configuration.xml` file in the source Oracle home to the `configuration.xml` file in the cloned Oracle home.

- After you clone a OracleBI Discoverer instance, when you click the Exit link on the Discoverer Viewer page, it results in a corrupted page because the port number in the `oc4j.properties` file has not been properly updated. To work around this problem, edit the following file and update the `oracle.discoverer.applications.port` property with the correct port number:

`Oracle_Home/j2ee/OC4J_BI_Forms/config/oc4j.properties`

The port number can be found in the following file:

`Oracle_Home/install/portlist.ini`

3.4.3 Considerations for Cloning OracleAS Forms and Reports Services

The following describes important information about cloning OracleAS Forms and Reports Services (installed from a separate CD):

- Before you run the `prepare_clone.pl` script, you must update the `ias.properties` file in the source Oracle home, changing the value of `DatabaseManagedClusterSupport` from `false` to `true`, as shown in the following example:

`DatabaseManagedClusterSupport=true`

- If you clone OracleAS Forms and Reports Services and then associate it with an OracleAS Infrastructure, the cloned instance is not part of a farm. To make the instance part of a farm, use the following command in the cloned Oracle home:

`dcmctl joinfarm`

Information about cloning OracleAS Forms and Reports Services in the *Oracle Application Server Administrator's Guide* is not entirely correct. The section "Considerations for Cloning OracleAS Forms and Reports Services" states:

"Before you run the `prepare_clone.pl` script, you must update the `ias.properties` file in the source Oracle home, changing the value of `DatabaseManagedClusterSupport` from `false` to `true`, as shown in the following example:

```
DatabaseManagedClusterSupport=true
```

This information is correct only if OracleAS Forms and Reports Services is associated with a Metadata Repository.

If OracleAS Forms and Reports Services is not associated with a Metadata Repository, the value of DatabaseManagedClusterSupport should be false.

3.5 Deployment Issues

This section describes other management issues. It includes the following topics:

- [Section 3.5.1, "Use Trusted Certificates When Enabling SSL Between mod_oc4j and OC4J"](#)
- [Section 3.5.2, "Benign Decoding Errors When Running ldapaddmt"](#)
- [Section 3.5.3, "Missing Files During restore_config Operation"](#)
- [Section 3.5.4, "Performance Improvement on Multiple Processors Systems"](#)

3.5.1 Use Trusted Certificates When Enabling SSL Between mod_oc4j and OC4J

You must use trusted certificates on both ends when enabling SSL between mod_oc4j and OC4J.

Otherwise, you will get the following error when accessing the HTTPS port:

```
500 Internal Server Error
```

3.5.2 Benign Decoding Errors When Running ldapaddmt

Chapter 11, "Changing from a Test to a Production Environment," in *Oracle Application Server Administrator's Guide* contains steps for migrating Oracle Internet Directory data to a production environment.

These steps include running the ldapaddmt command, and examining the add.log file. The add.log file may contain a "Decoding Error" message. This is benign and can be ignored.

3.5.3 Missing Files During restore_config Operation

Running restore_config may result in missing files messages such as:

```
Could not copy file /OracleAS/Devkit_1129/testdir/ to  
/OracleAS/Devkit_1129/backup_restore/cfg_bkp/2004-12-01_03-26-22.
```

During a restore_config operation, a temporary configuration backup is taken so that, if the restore fails, the temporary backup can be restored returning the instance to the same state as before the restore. If some files are deleted (including files/directories specified in config_misc_files.inp) before a restore operation, then, during the temporary backup, messages are displayed indicating that certain files are missing. These error/warning messages should be ignored since the missing files are restored as part of the restore_config operation.

3.5.4 Performance Improvement on Multiple Processors Systems

If you have installed Oracle Application Server on a system with multiple processors, you may see a performance benefit from enabling parallel garbage collection by

adding `-XX:+UseParallelGC` to the `jvm` options. Refer to the following Web site for more information:

<http://java.sun.com/developer/technicalArticles/Programming/turbo/index.html>

3.6 Documentation Errata

This section describes documentation errata in management documentation. It includes the following topics:

- [Section 3.6.1, "Errors in the Distributed Configuration Management Administrator's Guide"](#)
- [Section 3.6.2, "Errors in Oracle Process Manager and Notification Server Administrator's Guide"](#)
- [Section 3.6.3, "Incorrect Reference in Oracle Application Server Concepts Guide"](#)
- [Section 3.6.4, "Incorrect Default Value for start-mode Element in Oracle HTTP Server `opmn.xml` file"](#)

3.6.1 Errors in the Distributed Configuration Management Administrator's Guide

The *Distributed Configuration Management Administrator's Guide* contains the following documentation errors:

- In the "Tips:" listing in Section 2.2.6, "Removing an Oracle Application Server Instance From a DCM-Managed OracleAS Cluster":

"See `leaveCluster` for instructions on removing a DCM-Managed OracleAS Cluster from an Oracle Application Server Instance ..."

should be:

"See `leaveCluster` for instructions on removing an Oracle Application Server Instance from a DCM-Managed OracleAS Cluster..."
- In the "Important:" listing and the paragraph before step1 in section 2.2.11.3, "Setting Up Keystore Information File on Each Instance in the OracleAS File-based Farm":

"repository host instance OracleAS File-Based Farm"

should be:

"repository host instance for OracleAS File-Based Farm (or repository host instance of OracleAS File-Based Farm) "
- In the paragraph before the "Tip:" listing in section 2.3.2, "Deleting an OC4J Instance":

"`nameOfOC4JInstance` is the identifier for the new OC4J instance"

should be:

"`nameOfOC4JInstance` is the identifier for the OC4J instance you want to delete"
- In the paragraph before the "Note:" listing in Section 2.4.1, "Log File Location and Naming":

"the `log.xml` file is renamed to `log1-N.xml`, and a new `log.xml` file is created."

should be:

"the `log.xml` file is renamed to `logN+1.xml`, and a new `log.xml` file is created."

- In the first paragraph in section 2.2.7, "Exporting and Importing Configurations From a File-based Repository":

"This section explains how to save and restore a repository and move an Oracle Application Server Instance from one repository to another."

should be:

"This section explains how to save and restore a repository."

3.6.2 Errors in Oracle Process Manager and Notification Server Administrator's Guide

The *Oracle Process Manager and Notification Server Administrator's Guide* contains the following documentation errors:

- In Section 1.12, "Security", the following sentence is incomplete:

"This is expected OPMN behavior Oracle Application Server;"

should be:

"This is expected OPMN behavior;"

- In the `<dependencies>` list in Section 3.2, "opmn.xml Element and Attribute Descriptions" the following sentence is incorrectly shown twice:

"OPMN will create an aggregate dependency list at the process-set level that contains all dependencies defined at or above it. If duplicate dependencies are defined at different levels, then duplicate checks on the dependency will be made before starting a process."

- In Section 4.4, "Oracle HTTP Server Attribute Descriptions", the following paragraph is shown twice: "The number of Oracle HTTP Server Instances to start. Only valid value is 1".

3.6.3 Incorrect Reference in Oracle Application Server Concepts Guide

Section 7.2, "Oracle Application Server Infrastructure Architecture" in the Oracle Application Server Concepts guide contains the following reference:

"Some of the most frequently used deployment topologies for both Oracle Application Server Infrastructure itself and for applications which use Oracle Application Server Infrastructure are discussed in Chapter 12, "Recommended Topologies".

The reference should be to Chapter 12, "Enterprise Deployments".

3.6.4 Incorrect Default Value for start-mode Element in Oracle HTTP Server opmn.xml file

The `id="start-mode"` default value for the `opmn.xml` file listed in the Oracle HTTP Server chapter of the Oracle Process Manager and Notification Server Administrator's Guide is incorrectly listed as `ssl-enabled`. The default value for `id="start-mode"` is `ssl-disabled`.

High Availability

This chapter describes issues related to highly available topologies. This chapter contains the following issues:

- [Section 4.1, "OracleAS Disaster Recovery: Discover Topology Command"](#)
- [Section 4.2, "OracleAS Disaster Recovery: Real Application Clusters Database Supported"](#)

4.1 OracleAS Disaster Recovery: Discover Topology Command

If you run the "discover topology" command on a node that contains more than one Oracle home, and one of the Oracle homes is invalid for some reason (that is, the Oracle home does not appear in the Oracle Universal Installer), the "discover topology" command generates a warning:

```
ASGCTL> discover topology oidpass=welcome1
Discovering topology on host "hasun1" with IP address "123.45.67.89"

hasun1:7890
Connecting to the OID server on host "hasun12vip1.mydomain.com"
  using SSL port "636" and username "orcladmin"
Getting the list of databases from OID
Gathering database information for SID "orcl" from host
                                          "hasun12vip1.mydomain.com"

Getting the list of instances from OID
Gathering instance information for "immr.hasun12vip1.mydomain.com" from host
                                          "hasun12vip1.mydomain.com"

Gathering instance information for "asmid.haqadr01.mydomain.com" from host
                                          "haqadr01.mydomain.com"

***** WARNING *****
hasun1: -->ASG_IAS-15779: Error getting instance information for instance
  "asmid.haqadr01.mydomain.com" from host "haqadr01.mydomain.com". This instance
  will be excluded from the topology.xml file
drmt: -->ASG_IAS-15632: The home that contains instance
  "asmid.haqadr01.mydomain.com" could not be found
drmt: -->ASG_DUF-4950: An error occurred on host "drmt" with IP "130.35.45.23" and
  port "7890"
***** END WARNING *****

The topology has been discovered. A topology.xml file has been written to each
home in the topology.
```

To work around this issue, delete the entry for the invalid Oracle home from the `Inventory.xml` file in the `oraInventory` directory, then rerun the "discover topology" command.

4.2 OracleAS Disaster Recovery: Real Application Clusters Database Supported

Table 1-3 in the *Oracle Application Server High Availability Guide* incorrectly stated that OracleAS Disaster Recovery does not support OracleAS Infrastructure in active-active topologies. OracleAS Disaster Recovery does support OracleAS Infrastructure in active-active topologies, as well as active-passive topologies. In OracleAS Infrastructure active-active topologies, the OracleAS Metadata Repository runs on a Real Application Clusters database.

The following table shows the updated Table 1-3 (bold text shows the updates):

Table 4–1 Service level requirements and architecture choices

Business Requirements			Architecture Choices	
Local High Availability	Scalability	Disaster Recovery	Instance Redundancy	Disaster Recovery
N	N	N	Base	N
Y	N	N	Active-passive	N
N	Y	N	Active-active	N
N	N	Y	Base	Y
Y	Y	N	Active-active	N
Y	N	Y	Active-passive	Y
N	Y	Y	Active-active (middle tier) Base (Infrastructure)	Y
Y	Y	Y	Active-active (middle tier) Active-passive and active-active (Infrastructure)	Y

Note: OracleAS Disaster Recovery supports the base, active-passive, and active-active Infrastructure architectures. For additional scalability in a base, active-passive, or active-active architecture, extra computing power can be added to the infrastructure hardware (for example, high capacity CPUs, more memory)

This chapter describes issues associated with Oracle Forms. It includes the following topics:

- [Section 5.1, "General Issues and Workarounds"](#)
- [Section 5.2, "Configuration Issues and Workarounds"](#)
- [Section 5.3, "Documentation Errata"](#)

5.1 General Issues and Workarounds

This section describes general issues and workarounds. It includes the following topics:

- [Section 5.1.1, "Unix Issues and Workarounds"](#)
- [Section 5.1.2, "Incorrect Memory Usage Is Reported for Forms on SLES9"](#)

5.1.1 Unix Issues and Workarounds

On Unix platforms, if you relink Forms executables after installation (for example, because you are applying a one-off patch) the permissions on newly created executables will not necessarily be the same as the originals. Use `chmod` to change them manually.

5.1.2 Incorrect Memory Usage Is Reported for Forms on SLES9

On SLES9, when you click the Forms link on the Enterprise Manager main page, the Forms Overview page is displayed. On this page, the Pie Chart showing the Memory Usage is broken and shows an unhandled exception error. When you click the User Sessions tab, it shows the Total Memory Usage, in percentage. Due to the way SLES9 operating system reports the memory of a process, the private and shared memory sections display very high values. To resolve this issue, apply the following patch:

<http://www.kernel.org/pub/linux/kernel/v2.6/testing/patch-2.6.9-rc4.bz2>

5.2 Configuration Issues and Workarounds

This section describes configuration issues and their workarounds. It includes the following topics:

- [Section 5.2.1, "Non-Internet Explorer Browser Proxy Settings when Using One-Button-Run"](#)

- [Section 5.2.2, "Change to Default Setting for FORMS_RESTRICT_ENTER_QUERY Environment Variable"](#)
- [Section 5.2.3, "PJC Wizard Now Part of Oracle Forms"](#)
- [Section 5.2.4, "Exception When Clicking Other Items While Inputting Multibyte Characters"](#)
- [Section 5.2.5, "JDK 1.4.2_06 Plug-in Not Installed When Running a Form on the Web for the First Time"](#)
- [Section 5.2.6, "CLOB Data Cannot be Retrieved When Query Data More Than Max Width"](#)
- [Section 5.2.7, "FRM-92102 Existing Sessions Disconnect When User Added To JAZN"](#)
- [Section 5.2.8, "Monitoring CPU Usage and Response Time"](#)

5.2.1 Non-Internet Explorer Browser Proxy Settings when Using One-Button-Run

If you encounter a FORBIDDEN error when using One-Button-Run with any of the supported Browsers other than Internet Explorer, verify if 127.0.0.1 (localhost) is in the proxy settings for your browser. If 127.0.0.1 is not in the exceptions list, then add it. This ensures that the browser will bypass the proxy server.

5.2.2 Change to Default Setting for FORMS_RESTRICT_ENTER_QUERY Environment Variable

The environment setting FORMS_RESTRICT_ENTER_QUERY has a default value of TRUE. This setting disallows users from using QUERY-WHERE functionality until it is set to FALSE.

5.2.3 PJC Wizard Now Part of Oracle Forms

With Oracle Forms 10.1.2 and higher, the Forms PJC Wizard is part of the standard Forms installation. The PJC Wizard works with JDeveloper 10g (10.1.2) that is part of Oracle Developer Suite 10g. For versions of JDeveloper that are obtained from OTN, the PJC wizard is available as a separate Jar file to download and place into your JDeveloper installation.

5.2.4 Exception When Clicking Other Items While Inputting Multibyte Characters

In CJK languages, the Forms client may stop responding when clicking another item while inputting text through inline IME. As a workaround, disable the inline IME. See section 4.10.2, "Inline IME Support" in *Oracle Application Server Forms Services Deployment Guide*. This issue will be fixed in a future patch set.

5.2.5 JDK 1.4.2_06 Plug-in Not Installed When Running a Form on the Web for the First Time

The **Install JDK 1.4.2** dialog appears when running a Form on the Web for the first time. When you click **Install**, the JDK 1.4.2 Plug-in is installed instead of the JDK 1.4.2_06 Plug-in. If you are attempting to use the JDK 1.4.2 plugin from Internet Explorer, and it is not currently installed on your machine, it will download the wrong version. The workarounds are:

- Modify `formsweb.cfg` by finding:

```
jpi_codebase=http://java.sun.com/products/plugin/autodl/jinstall-1_4_2-windows-i586.cab#Version=1,4,2,06
```

and change it to:

```
jpi_codebase=http://java.sun.com/products/plugin/autodl/jinstall-1_4_2_06-windows-i586.cab#Version=1,4,2,06.
```

- Run the Form (for the first time) from Netscape, which will go to the correct location for the download.
- Go to the correct location and manually install the JDK 1.4.2_06 Plug-in.

5.2.6 CLOB Data Cannot be Retrieved When Query Data More Than Max Width

When using Japanese NLS_LANG (JA16SJIS, JA16EUC etc.) if the queried CLOB data is longer than the maximum length (240 bytes by default) of the Text Item corresponding to this CLOB data, the query fails at runtime. The issue is that the CLOB data is correctly truncated with the maximum length of the Text Item (240 bytes by default) in English NLS_LANG, but not in Japanese NLS_LANG.

On IBM zSeries Based Linux, error FRM-92101 occurs when encountering this issue.

As a workaround, extend the maximum length of the Text Item to fit the length of the CLOB data.

5.2.7 FRM-92102 Existing Sessions Disconnect When User Added To JAZN

The FRM-92102 error appears and existing Forms sessions disconnect after adding a new user to JAZN (**OC4J_BI_FORMS | Applications | formsapp | Security**). Thus, if you're adding new JAZN users to the OC4J_BI_Forms instance, you should do this while no Forms session is running.

5.2.8 Monitoring CPU Usage and Response Time

On the System Component Tables in Enterprise Manager, the CPU and Memory statistics are collected every minute, by default. Note that this potentially can mean that any CPU spikes will not be displayed. In addition, if Forms server processes are dormant, awaiting client activity or requests, it is perfectly normal for the CPU usage to report 0.0%.

On the Forms Overview page, the CPU and Memory statistics are gathered each time the page is rendered when you click the Overview Tab or when you click the refresh icon next to the timestamp. However, due to an operating system restriction, if the Response Time from the Forms Servlet is less than 16ms, it will display as 0.00ms.

5.3 Documentation Errata

This section describes documentation errata. It includes the following topics:

- [Section 5.3.1, "Incorrect Key Mapping"](#)
- [Section 5.3.2, "Incomplete JVM Pooling Example"](#)
- [Section 5.3.3, "Incorrect Script Tag Names"](#)
- [Section 5.3.4, "Incorrect Default Threshold Setting Description"](#)
- [Section 5.3.5, "Incorrect Parameter Names in URL"](#)

5.3.1 Incorrect Key Mapping

In Section 4.11.1.2.1 of *Oracle Application Server Forms Services Deployment Guide*, the description for Mapping F2 is written as:

To map F2, change the default entry for F2, "List Tab Pages", to another key. Here is an example of the default entry:

```
113: 0 : "F2" : 95 : "List Tab Pages"
```

This must be explicitly changed to another key mapping such as the following:

```
113: 8 : "F2" : 95 : "List Tab Pages"
```

The last line should read as:

```
113: 8 : "Alt+F2" : 95 : "List Tab Pages"
```

5.3.2 Incomplete JVM Pooling Example

In section 7.5.12 of *Oracle Application Server Forms Services Deployment Guide*, there is a sample formsweb.cfg configuration. The last named section is written as:

```
[salesApp]
form=sales.fmx
userid=sales/salespw@orcl
```

However, this example should read as:

```
[salesApp]
form=sales.fmx
userid=sales/salespw@orcl
jvmcontroller=
```

5.3.3 Incorrect Script Tag Names

In section 9.2.2 of *Oracle Application Server Forms Services Deployment Guide*, the script tag is written as:

```
<SCRIPT SRC="/oracle_smp_EndUserMonitoring/oracle_smp_
EndUserMonitoring.js"></SCRIPT>
```

It should read as:

```
<SCRIPT SRC="/oracle_smp_chronos/oracle_smp_chronos.js"></SCRIPT>
```

5.3.4 Incorrect Default Threshold Setting Description

In section 9.2.5 of *Oracle Application Server Forms Services Deployment Guide*, the default threshold description is written as:

The default unreasonable threshold is set to 60,000 milliseconds, which may be too small for Oracle Forms Applications. You may want to change this default to 1 minute.

The correct description should read:

The default unreasonable threshold is set to 60,000 milliseconds, which may be too small for Oracle Forms Applications. You may want to change this default to 1 hour.

5.3.5 Incorrect Parameter Names in URL

In section 9.3.1 of *Oracle Application Server Forms Services Deployment Guide*, the EndUserMonitoringURL parameter is written as:

Set EndUserMonitoringURL=http://computername:7777/oracle_smp_
EndUserMonitoring/oracle_smp_EndUserMonitoring_sdk.gif

It should read as:

EndUserMonitoringURL=http://<hostname>:<webcache port number>/oracle_smp_
chronos/oracle_smp_chronos_sdk.gif

Without the correct EndUserMonitoringURL parameters, End User Monitoring will not work.

Oracle Application Server Containers for J2EE

This chapter describes issues with Oracle Application Server Containers for J2EE (OC4J). It includes the following topics:

- [Section 6.1, "OC4J Bugs Fixed in 10.1.2.0.2"](#)
- [Section 6.2, "Configuration Issues and Workarounds"](#)
- [Section 6.3, "Enterprise Java Beans"](#)
- [Section 6.4, "OC4J Services"](#)
- [Section 6.5, "Oracle Application Server Java Authentication and Authorization Service \(JAAS\) Provider"](#)
- [Section 6.6, "Documentation Errata"](#)

6.1 OC4J Bugs Fixed in 10.1.2.0.2

The following OC4J-related bugs have been resolved in 10.1.2.0.2:

- BUG 4373794 - OC4J 10.1.2 - FATAL ERROR CODE ENHANCEMENT - This fix is described in this document at ["Fatal Error Code Enhancement"](#) on page 6-6.
- BUG 4226465 - MULTIPLE CONNECTION POOLS EXIST FOR SAME DATA SOURCE - This resolves code bug 4226465 and documentation bug 4373802. This fix is described in this document at ["Fixed Connection Pool Problems"](#) on page 6-7.

6.2 Configuration Issues and Workarounds

This section describes configuration issues and their workarounds for Oracle Application Server Containers for J2EE (OC4J).

It includes the following topics:

- [Section 6.2.1, "Oracle JDBC-OCI Driver Upgrade in the Oracle Application Server"](#)
- [Section 6.2.2, "OC4J Out of Memory Errors"](#)
- [Section 6.2.3, "JDK 1.3 With OC4J 10.1.2.0.2"](#)
- [Section 6.2.4, "Configuring Maximum Connections with Oracle HTTP Server"](#)

6.2.1 Oracle JDBC-OCI Driver Upgrade in the Oracle Application Server

It is not possible to upgrade to an arbitrary Oracle JDBC-OCI driver version due to client library compatibility constraints. Upgrading to OCI driver versions with

matching Oracle Client libraries that are installed within the Oracle Application Server 10g (10.1.2) is supported. For example, Oracle JDBC 10.1.x drivers are supported, but the Oracle JDBC 9.2.x drivers are not.

Where the use of JDBC-OCI within the Oracle Application Server is supported, it is also necessary for the `opmn.xml` entry for each OC4J instance to propagate appropriate `ORACLE_HOME` and library path values to its startup environment.

The environment variable `ORACLE_HOME` is common to all platforms, but the name of the environment variable that specifies the library path is different depending on the operating system. It is `LD_LIBRARY_PATH` for this platform.

The generic syntax for specifying the library paths in `opmn.xml` looks like this:

```
<variable_id="LIB_PATH_VARIABLE" value="LIB_PATH_VARIABLE_VALUE" />
```

where `LIB_PATH_VARIABLE` should be replaced with the appropriate platform-specific variable name that specifies the library path, and

`LIB_PATH_VARIABLE_VALUE`

should be replaced with that variable's value.

Here is an example:

```
<process-type id="OC4J_SECURITY" module-id="OC4J">
  <environment>
    <variable id="ORACLE_HOME"
value="/u01/app/oracle/product/inf10120" />
    <variable
      id="LD_LIBRARY_PATH"
      value="/u01/app/oracle/product/inf10120/lib"
    />
  </environment>
  ...
```

6.2.2 OC4J Out of Memory Errors

If the OC4J default JVM heap size is too small for applications that you deploy, then you may see Out Of Memory errors from your OC4J processes. If you review the log files for the OC4J Instance in the directory `$ORACLE_HOME/opmn/logs`, you may find errors similar to the following:

```
java.lang.OutOfMemoryError
```

To work around this problem, increase the specified heap memory by changing the Java command line options for the OC4J Instance.

Using Application Server Control Console, go to the OC4J instance homepage and perform the following steps:

1. Stop the OC4J Instance.
2. Drill down to the Server Properties page.
3. In the Command Line Options area of the Server Properties page, under the heading Multiple VM Configuration, set the Java Options.

For example, enter the following to set the JVM heap sizes to 512 Megabytes:

```
-Xmx512m
```

4. Use the Apply button to apply the changes.

5. Start the OC4J instance.

For more information, see the *Oracle Application Server Performance Guide*.

6.2.3 JDK 1.3 With OC4J 10.1.2.0.2

In order to use JDK 1.3, which is not shipped with OC4J 10.1.2, modify JDK 1.3 as follows:

1. Download and install JAAS1.0_01 from <http://java.sun.com/products/jaas>
2. Drop `jaas.jar` from the JAAS1.0_01 distribution into `jre/lib/ext`
3. Add the following lines into `jre/lib/security/java.security`.

```
#These two lines are Oracle-specific definitions

auth.policy.provider=oracle.security.jazn.spi.PolicyProvider
@ login.configuration.provider=oracle.security.jazn.spi.LoginConfigProvider
```

6.2.4 Configuring Maximum Connections with Oracle HTTP Server

In standalone OC4J, you can configure the maximum number of connections by using the `<max-http-connections>` subelement of `<application-server>` in the `server.xml` file. (This is documented in the *Oracle Application Server Containers for J2EE User's Guide*.)

Now there is also a `<max-ajp-connections>` subelement of `<application-server>` to configure a maximum number of connections for use with Oracle HTTP Server. For example:

```
<application-server>
...
  <max-ajp-connections value="10000" max-connections-queue-timeout="10"
                        close-idle-connection="allow">
    http://optional.redirect.url/page.jsp
  </max-ajp-connections>
...
</application-server>
```

The (optional) value of the element indicates a `redirect-URL`, the usage of which is described as follows.

Attributes of `<max-ajp-connections>`:

- `value`: The maximum number of connections allowed. The default value is -1, for no limit. (0 is a reserved value.)
- `max-connections-queue-timeout`: How many seconds to wait for the number of connections to drop below the maximum number. If a connection is attempted when the maximum number of connections has been reached, and there are still no available connections after the timeout expires, then appropriate action is taken depending on other settings. The default is 0 seconds.
- `close-idle-connection`: A setting of `allow` (the default) makes a new connection possible by allowing the least-recently used (LRU) idle connection to be closed if the maximum number of connections has been reached and the queue timeout has expired. Use `deny` to disallow the LRU idle connection to be closed.

- `socket-backlog`: The number of connections to queue up before denying connections at the socket level. The default is 30. This is inherited from `<max-http-connections>` functionality, but has no particular use in addition to other `<max-ajp-connections>` attribute settings; there should be no reason to use a value other than the default.

There are three possible responses when a connection is being attempted after the maximum number of connections has been reached and the timeout has expired:

- If `close-idle-connection="allow"`, the connection listener will close the oldest open idle connection by closing the client socket (but the working thread is allowed to finish its work). This allows the attempted connection to be accepted.
- If `close-idle-connection="deny"` and a `redirect-URL` is specified in the `<max-ajp-connections>` element value (as shown in the preceding example), then the connection listener will reject the attempted connection with a `302 Moved Temporarily` HTTP response. (The client system is expected to immediately retry the alternate URL.) The client socket of the attempted connection is then closed.
- If `close-idle-connection="deny"` and no `redirect-URL` is specified, then the connection listener will reject the attempted connection and send a `503 Service Unavailable` HTTP response. The client socket of the attempted connection is then closed.

6.3 Enterprise Java Beans

This section describes issues with Enterprise Java Beans (EJB). It includes the following topics:

- [Section 6.3.1, "Deprecated orion-ejb-jar.xml Attributes"](#)
- [Section 6.3.2, "Big EAR File Deployment Runs Out of Memory"](#)
- [Section 6.3.3, "EJB Wrapper Code Compilation Fails When Running in zh_CN.GB18030 Locale"](#)
- [Section 6.3.4, "Disregard Previous Release Note: Package Name for RMIIInitialContextFactory Has Changed"](#)
- [Section 6.3.5, "How To Disable EJB Instance Pooling"](#)
- [Section 6.3.6, "How To Compile in Non-Batch Mode"](#)

6.3.1 Deprecated orion-ejb-jar.xml Attributes

The following `orion-ejb-jar.xml` attributes are deprecated in releases 9.0.4.1 and 10.1.2 and will be removed in release 10.1.3:

- `max-instances-per-pk`
- `min-instances-per-pk`
- `disable-wrapper-cache`
- `disable-wrapper-cache`

In addition, the following `locking-mode` attribute setting is deprecated:

- `locking-mode="old_pessimistic"`

6.3.2 Big EAR File Deployment Runs Out of Memory

`OutOfMemory` exceptions occur when deploying EAR files with a large number of EJBs.

As part of the deployment process, wrapper code classes are generated for each EJB. The size of these classes is proportional to the number of business methods on the bean. As a performance optimization, OC4J compiles all wrapper code classes in one compiler invocation. An error can occur if the amount of generated wrapper code is too much for available memory.

A workaround is to direct the deployment process to compile each EJB module's wrapper code individually. You can do this by starting OC4J with the `ejbdeploy.batch` system property and setting it to `false`, as in the following example:

```
-Dejbdeploy.batch=false
```

Note: This workaround should only be used when this specific exception occurs.

This workaround may result in an increased deployment time for the application.

6.3.3 EJB Wrapper Code Compilation Fails When Running in zh_CN.GB18030 Locale

EJB wrapper code compilation fails when running in `zh_CN.GB18030` locale. When running in `zh_CN.GB18030` locale, parts of the EJB wrapper source code may be generated with missing characters. This causes compilation errors. The missing characters in the generated source code are due to a Sun bug documented at:

http://bugs.sun.com/bugdatabase/view_bug.do?bug_id=4954023

The workaround is to use a different locale. See the Sun bug for details.

6.3.4 Disregard Previous Release Note: Package Name for `RMIInitialContextFactory` Has Changed

Disregard the following release note from the initial 10.1.2 release notes. The information does not apply to the 10.1.2 release.

"The package name for `RMIInitialContextFactory` has changed from `oracle.j2ee.rmi.server` to `oracle.j2ee.rmi`."

6.3.5 How To Disable EJB Instance Pooling

To disable instance pooling, use the new `<max-instances>` setting with any negative number in the `orion-ejb-jar.xml` file. This creates a new instance at the start of the EJB call and releases it at the end of the call.

6.3.6 How To Compile in Non-Batch Mode

To compile in non-batch mode (for example, if OC4J throws `java.lang.OutOfMemory` exceptions while compiling in batch mode), use the `-Dejbdeploy.batch=false` option. Although non-batch mode requires less memory allocation, this mode results in a longer deployment time.

6.4 OC4J Services

This section describes release notes for OC4J services. OC4J Services include: Java Naming and Directory Interface (JNDI), Java Message Service (JMS), Data Sources, Oracle Remote Method Invocation (ORMI), J2EE Interoperability (IIOP), Java Transaction API (JTA), J2EE Connector Architecture (J2CA), and Java Object Cache.

The section contains the following release note(s):

- [Section 6.4.1, "Data Sources"](#)
- [Section 6.4.2, "ORMI"](#)

6.4.1 Data Sources

This section describes issues with Data Sources. It includes the following topics:

- [Section 6.4.1.1, "Data Sources Creates the Correct Number of Connection Pools in 10.1.2"](#)
- [Section 6.4.1.2, "Fatal Error Code Enhancement"](#)
- [Section 6.4.1.3, "Fixed Connection Pool Problems"](#)

6.4.1.1 Data Sources Creates the Correct Number of Connection Pools in 10.1.2

In the 9.0.4 release, Data Sources incorrectly created multiple connection pools for the same data source: One pool for transactional connections and one pool for non-transactional connections.

This behavior is corrected for release 10.1.2.

6.4.1.2 Fatal Error Code Enhancement

For each data source defined in `data-sources.xml`, you can define fatal error codes that indicate that the back-end database with which the data source communicates is no longer accessible. When OC4J detects one of these error codes (stated when a `SQLException` is thrown by the JDBC driver), OC4J will clean its connection pool. That is, it closes all connections in the connection pool. For Oracle, the predefined fatal error codes are: 3113, 3114, 1033, 1034, 1089, and 1090.

Use the following procedure to add additional fatal error codes for Oracle.

Use the `<fatal-error-codes>` element, which is a subtag of the `<data-source>` element. The `<fatal-error-codes>` element uses the child element `<error-code>` to define one fatal error code. You can define 0 - n `<error-code>` elements for each `<fatal-error-codes>` element. For example, for fatal error codes 10, 20, and 30, the data source definition would look like this:

```
<data-source
class="com.evermind.sql.DriverManagerDataSource"
name="ds"
location="jdbc/ds"
xa-location="jdbc/xa/ds"
ejb-location="jdbc/ejb/ds"
@ connection-driver="oracle.jdbc.driver.OracleDriver"
username="scott"
@ password="tiger"

@ url="jdbc:oracle:thin:@//localhost:1521/oracle.regress.rdbms.dev.us.oracle.com">

    <fatal-error-codes>
        <error-code code='10' />
```

```

        <error-code code='20' />
        <error-code code='30' />
    </fatal-error-codes>

</data-source>

```

6.4.1.3 Fixed Connection Pool Problems

The following connection pool problems are fixed in 10.1.2.0.2.

In pre-10.1.2.0.2 versions of OC4J, the data sources subsystem would create multiple connection pools for the same data source for the following cases:

- When a connection was used inside a global transaction and outside a global transaction during the same thread of execution (during the execution of a servlet for example.) In this case one connection pool was created for connections used inside global transactions and one connection pool was created for connections used outside of the global transaction.
- When a connection was retrieved from the data source using the non-default user or password. For example, the use of `getConnection()` caused one connection pool to be created and `getConnection("user", "password")` caused another connection pool to be created. This is especially bad because each user or password combination created another, separate connection pool.
- Indicating via configuration that a data source's connections are to be shared caused an additional data source to be created under the covers which would then duplicate all of the connection pool issues described previously.

This resolves code bug 4226465 and documentation bug 4373802.

6.4.2 ORMI

This section describes issues with ORMI. It includes the following topics:

- [Section 6.4.2.1, "ORMI - OC4J Only Creates IPv4 Sockets"](#)
- [Section 6.4.2.2, "ORMI Protocol Is Not Secure"](#)

6.4.2.1 ORMI - OC4J Only Creates IPv4 Sockets

OC4J only creates IPv4 sockets. Even on dual network stack machines (with both IPv4 and IPv6 stacks available) OC4J creates only IPv4 sockets. This may cause a problem if client-issued requests are from a IPv6 system. This is indicated by connection-refused messages from the server to the IPv6 client. To avoid this problem, start the client process with the system property `java.net.preferIPv4Stack=true`. This forces the client to only issue IPv4 requests, allowing it to communicate with the server.

6.4.2.2 ORMI Protocol Is Not Secure

It should be noted that the ORMI protocol is not secure. Any and all communication over ORMI is not encrypted including security credentials. Customers that want to encrypt ORMI traffic are advised to use ORMI over HTTPS, which will encrypt all communication between the client and the server.

6.5 Oracle Application Server Java Authentication and Authorization Service (JAAS) Provider

Be aware of the following notes when using the Oracle Application Server Java Authentication and Authorization Service (JAAS) Provider (OracleAS JAAS Provider) in release 10.1.2.0.2:

- [Section 6.5.1, "Using the 9.0.4 Oracle Internet Directory Server with 10.1.2.0.2 OracleAS JAAS Provider"](#)
- [Section 6.5.2, "Support for auth-method="DIGEST" in <jazn-web-app>"](#)

6.5.1 Using the 9.0.4 Oracle Internet Directory Server with 10.1.2.0.2 OracleAS JAAS Provider

Prior to the 10.1.2 Oracle Internet Directory implementation, Access Control List (ACL) features are not set up properly for JAZNAdminGroup. To use the 9.0.4 Oracle Internet Directory implementation with the 10.1.2 OracleAS JAAS Provider implementation, place the following contents into a file, replacing %s_MgmtRealmDN% with the appropriate ID management realm (for example, dc=us, dc=oracle, dc=com), then execute the steps that follow.

```
dn: cn=JAZNContext,cn=Products,cn=OracleContext,%s_MgmtRealmDN%
changetype: modify
replace: orclaci
orclaci: access to entry
    by group=
"cn=JAZNAdminGroup,cn=Groups,cn=JAZNContext,cn=Products,cn=OracleContext"
(browse, add, delete)
    by group= "cn=IASAdmins,cn=Groups,cn=OracleContext,%s_MgmtRealmDN%"
added_object_constraint=(objectclass=orclApplicationEntity) (add, delete, browse)
    by * (none)
orclaci: access to attr=(*)
    by group=
"cn=JAZNAdminGroup,cn=Groups,cn=JAZNContext,cn=Products,cn=OracleContext"
(search, read, write, compare)
    by group= "cn=IASAdmins,cn=Groups,cn=OracleContext,%s_MgmtRealmDN%"
(read, search, write, compare)
    by * (none)
```

1. Name the file with the .ldif extension, such as jaznacl.ldif.
2. Run the ldapmodify utility with the newly created file as input, specifying oidport, oidhost, adminuser_dn, password, and filename as appropriate:

```
ldapmodify -c -a -p oidport -h oidhost -D adminuser_dn -w password \
-f filename.ldif
```

6.5.2 Support for auth-method="DIGEST" in <jazn-web-app>

The 10.1.2.0.2 OracleAS JAAS Provider implementation now supports the setting auth-method="DIGEST" in the <jazn-web-app> element, in either the orion-web.xml file or orion-application.xml file. This is in addition to the already supported setting auth-method="SSO". Support for DIGEST is already noted in the 10.1.2.0.2 *Oracle Application Server Containers for J2EE Servlet Developer's Guide* (which includes reference documentation for orion-web.xml), but is not indicated in the 10.1.2.0.2 *Oracle Application Server Containers for J2EE User's Guide* (which includes reference documentation for orion-application.xml). "SSO" is to use Oracle Application Server Single Sign-On for HTTP client authentication. DIGEST

is to use the digest authentication mechanism. See the 10.1.2.0.2 *Oracle Application Server Containers for J2EE Security Guide* for complete information.

6.6 Documentation Errata

This section describes known errors in the OC4J documentation in Oracle Application Server 10g Release 2 (10.1.2). It covers the following books:

- [Section 6.6.1, "Oracle Application Server Containers for J2EE User's Guide Documentation Errata"](#)
- [Section 6.6.2, "Oracle Application Server Containers for J2EE Standalone User's Guide Documentation Errata"](#)
- [Section 6.6.3, "Oracle XML API Reference Documentation Errata"](#)
- [Section 6.6.4, "Oracle Application Server Containers for J2EE Services Guide Documentation Errata"](#)
- [Section 6.6.5, "Oracle Application Server Containers for J2EE Security Guide"](#)
- [Section 6.6.6, "OC4J Release Notes for 10.1.2.0.2"](#)

6.6.1 Oracle Application Server Containers for J2EE User's Guide Documentation Errata

This section describes known errors in the *Oracle Application Server Containers for J2EE User's Guide*. It includes the following topic(s):

- [Section 6.6.1.1, "An OC4J Process Is Not Contained in an OC4J Instance"](#)
- [Section 6.6.1.2, "Correct Cross Reference for Metric-Based Load Balancing Information"](#)
- [Section 6.6.1.3, "JDK 1.4.2 Supported and Installed with OC4J"](#)
- [Section 6.6.1.4, "Primers Content Removed from OC4J User's Guide"](#)
- [Section 6.6.1.5, "Additional OC4J Deployment Notes"](#)
- [Section 6.6.1.6, "Corrected Default Log File Name"](#)
- [Section 6.6.1.7, "Manual Build and Deploy Methods Apply To Standalone Environment Only"](#)
- [Section 6.6.1.8, "High Availability Guide Has No Information on "Hot Deploying" an Application in a Clustered Environment"](#)
- [Section 6.6.1.9, "For State Replication, Confirm That the <cluster-config/> Tag Is in the orion-web.xml File"](#)

6.6.1.1 An OC4J Process Is Not Contained in an OC4J Instance

The following incorrect statement appears in the *Oracle Application Server Containers for J2EE User's Guide* Chapter 8, OC4J Clustering:

"Each OC4J process is contained in an OC4J instance and inherits its configuration from the OC4J instance. All applications deployed to an OC4J instance are deployed to all OC4J processes in the OC4J instance."

The statement is incorrect because an OC4J process can only be *contained* in other processes, an OC4J instance is not a process.

The correct statement in this case is:

"Each OC4J process is associated to an OC4J instance and inherits its configuration from that OC4J instance. All applications deployed to an OC4J instance are started in all the OC4J processes associated to that OC4J instance."

6.6.1.2 Correct Cross Reference for Metric-Based Load Balancing Information

In the description of the `<metric-collector>` element of the `server.xml` file in Appendix B - Additional Information of the *Oracle Application Server Containers for J2EE User's Guide*, the following incorrect cross reference is given:

"For details on using the `<metric-collector>` element and using metric-based load balancing with `mod_oc4j`, see the *Oracle Application Server 10g Performance Guide*."

Replace the incorrect cross reference with the following correct cross reference:

For details on using metric-based load balancing with `mod_oc4j`, see the *Oracle HTTP Server Administrator's Guide*.

6.6.1.3 JDK 1.4.2 Supported and Installed with OC4J

Chapter 1: "OC4J Overview" of the *Oracle Application Server Containers for J2EE User's Guide* contains incorrect references to the Java Development Kit (JDK) used with *Oracle Application Server Containers for J2EE 10g Release 2 (10.1.2)*.

The "Using JDK With OC4J" section lists JDK 1.3.1 and 1.4.1 as the supported versions. This list should also include JDK 1.4.2.

The "Requirements" section incorrectly states that JDK 1.3.x is installed with OC4J. The correct version is JDK 1.4.2.

6.6.1.4 Primers Content Removed from OC4J User's Guide

Chapter 1: "OC4J Overview" of the *Oracle Application Server Containers for J2EE User's Guide* contains a reference to *primers*, which are no longer included in the User's Guide.

6.6.1.5 Additional OC4J Deployment Notes

The following notes on undeployment and redeployment are intended to supplement the deployment discussion in the *Oracle Application Server Containers for J2EE User's Guide*.

General undeployment/redeployment notes:

- Once an application is undeployed from OC4J, it is no longer accessible to clients. In an Oracle Application Server environment, Oracle HTTP Server will be restarted to remove the OC4J mount point. This will result in the loss of existing HTTP sessions.
- During a redeployment, OC4J removes the existing application (EAR/WAR) before redeploying the new EAR. This means, for example, that attempts to access an HTML file that was included in the previous application, but not the new one, will result in "File Not Found" errors.
- Also note that a redeployed WAR file overlays the previously expanded WAR, meaning that some older files may persist in the new deployment and will need to be deleted. For example, static HTML files from the previous deployment that are not included in the new WAR may continue to reside in the expanded WAR directory structure, and would have to be manually deleted.

Hot redeployment notes:

Note: A hot deployment is deploying an application without restarting OC4J.

- When an EAR is redeployed or *hot redeployed* on a running OC4J instance, the status of the classes loaded in the JVM from the previous application may vary. In some cases a classloader may recognize that a class or JAR file in the file system has changed, and reload the class or library. In other cases, whether a new class definition is loaded, may depend on whether the JVM tuning allows the garbage collector to flush the existing class definition.
- Issues may also exist with respect to serialized objects containing session data. If the class related to a session object changes, it may not be possible to cast the generic session object back to the class, since the class has changed and its variables may occupy a different memory footprint. This may result in lost session data.
- In an Oracle Application Server environment, a *hot deployment* adds Oc4jMount directives to `mod_oc4j.conf`, which in turn forces a restart of Oracle HTTP Server. This will result in the loss of existing HTTP sessions.

6.6.1.6 Corrected Default Log File Name

Table 3-3 of the *Oracle Application Server Containers for J2EE User's Guide 10g Release 2 (10.1.2)* states incorrectly that the default log file name for the OC4J is `web-access.log`. The correct default log file name is `default-web-access.log`.

The corrected table with the corrected default log file name for OC4J is as follows:

Table 6–1 List of Log Files Generated for OC4J

Default Log File Name	Description	Scope	Configuration File
<code>application.log</code>	All events, errors, and exceptions for a deployed application	One log file for each application deployed	<code>orion-application.xml</code>
<code>global-application.log</code>	All common events, errors, and exceptions related to applications	All applications, including the default application	<code>application.xml</code>
<code>jms.log</code>	All JMS events and errors.	JMS sub-system	<code>jms.xml</code>
<code>rmi.log</code>	All RMI events and errors	RMI sub-system	<code>rmi.xml</code>
<code>server.log</code>	All events not associated with a particular sub-system or an application. This logs history of server startup, shutdown internal server errors.	Server-wide	<code>server.xml</code>
<code>default-web-access.log</code>	All accesses to the Web site	Each Web site	<code>default-web-site.xml</code>

6.6.1.7 Manual Build and Deploy Methods Apply To Standalone Environment Only

The "Building and Deploying Within a Directory" section of Chapter 3, "Advanced Configuration and Development" of the *Oracle Application Server Containers for J2EE User's Guide 10g Release 2 (10.1.2)* should include the following note:

Note:

The manual build and deploy methods described in this section can be used in the standalone OC4J environment only, not in the enterprise environment.

In the enterprise environment, use the Oracle Enterprise Manager 10g to build and deploy applications.

6.6.1.8 High Availability Guide Has No Information on "Hot Deploying" an Application in a Clustered Environment

According to the *Oracle Application Server Containers for J2EE User's Guide* 10g Release 2 (10.1.2), deploying a new Web module to an active OC4J instance causes loss of the HTTP sessions for every Web application running within the server instance.

In a non-clustered environment, this issue can be avoided by using the `persistence-path` attribute in the root `<orion-web-app>` element within each `orion-web.xml` file. This workaround does **not** apply to a clustered environment.

The User's Guide indicates **incorrectly** that the *Oracle Application Server High Availability Guide* provides "guidelines on addressing this issue in a clustered environment". In fact, the *Oracle Application Server High Availability Guide* provides no information about this topic.

6.6.1.9 For State Replication, Confirm That the `<cluster-config/>` Tag Is in the `orion-web.xml` File

The "Configuring Web Application State Replication" section in Chapter 4, "OC4J Cluster Configuration" of the *Oracle Application Server Containers for J2EE User's Guide* 10g Release 2 (10.1.2), provides a six-step procedure for configuring state replication for Web applications.

In addition to the six steps, confirm that the `<cluster-config/>` tag has been added to the `global-web-application.xml` file. If this tag has not been added to the `global-web-application.xml` file, then add the tag to the `orion-web.xml` file. The `orion-web.xml` file is in the following location:

```
ORACLE_HOME/j2ee/<instance_name>/applications/<app_name>/<app_name>/WEB-INF/orion-web.xml
```

The `<cluster-config/>` tag is a subelement of the `<orion-web-app>` tag. For more information about the `orion-web.xml` file and the `<cluster-config/>` tag, see Chapter 6, "Configuration File Descriptions", of the *Oracle Application Server Containers for J2EE Servlet Developer's Guide*.

6.6.2 Oracle Application Server Containers for J2EE Standalone User's Guide Documentation Errata

This section describes known errors in the *Oracle Application Server Containers for J2EE Standalone User's Guide*. It includes the following topic(s):

- [Section 6.6.2.1, "Correction: http-web-site"](#)

6.6.2.1 Correction: http-web-site

The following error appears in the "Deploy Using the Admin.JAR Tool in All Environments" section of Chapter 1, "Configuration and Deployment" of the *Oracle Application Server Containers for J2EE Stand Alone User's Guide* :

In the `-bindWebApp` example, the Web site name `http_web_site` is incorrect.

The correct Web site name in this case is: `http-web-site`.

The corrected example is as follows:

```
java -jar admin.jar
ormi://oc4j_host:oc4j_ormi_port
admin welcome -bindWebApp
FAQApp FAQAppWeb http-web-site /FAQApp
```

6.6.3 Oracle XML API Reference Documentation Errata

This section describes known errors in the *Oracle XML API Reference*. It includes the following topic:

- [Section 6.6.3.1, "Add Information for formDocument\(\) Method"](#)

6.6.3.1 Add Information for formDocument() Method

In the Oracle XML API Reference, Chapter 15, "Package Dom APIs for C++", add the following entries:

- On page 15-22, in Table 15-7 "Summary of DOMImplRef Methods; Dom Package", add an entry for `formDocument()` method, description: "Forms a document reference given a pointer to the document."
- On page 15-24, add the following method description:

```
formDocument()
```

Description

Forms a document reference given a pointer to the document.

Syntax

```
DocumentRef< Node>* formDocument( Node* node);
```

Parameter	Description
node	Pointer to the document node.

Returns

`DocumentRef< Node>* pointer to the document reference.`

6.6.4 Oracle Application Server Containers for J2EE Services Guide Documentation Errata

This section describes known errors in the *OC4J Services Guide*. It includes the following topics:

- [Section 6.6.4.1, "Corrected SQLServer Data Source Example"](#)
- [Section 6.6.4.2, "Corrected JDBC Connect String for Third-Party Databases"](#)
- [Section 6.6.4.3, "Corrected Java Object Cache Code Example for Implementing a CacheEventListener"](#)
- [Section 6.6.4.4, "Also Add the ojdk.jar File to the Classpath to Access EJBs"](#)

6.6.4.1 Corrected SQLServer Data Source Example

On page 4-24 in "Example DataDirect Data Source Entries", the *Oracle Application Server Containers for J2EE Services Guide* shows the following example as a data source entry for SQLServer. However, the example is incorrect, a colon is missing.

```
@ url="jdbc:sqlserver//hostname:port;User=test;Password=secret"
```

The correct example is as follows:

```
@ url="jdbc:sqlserver://hostname:port;User=test;Password=secret"
```

6.6.4.2 Corrected JDBC Connect String for Third-Party Databases

In the "Example DataDirect Data Source Entries" section of the "Data Sources" chapter of the *Oracle Application Server Containers for J2EE Services Guide* for 9.0.4 and 10.1.2.x, the URLs in the examples are incorrect.

The INCORRECT part of the URL is as follows:

```
url="jdbc:databasevendor://...
```

The CORRECT URL fragment is as follows:

```
url="jdbc:oracle:databasevendor://...
```

The corrected example DataDirect Data Source Entries are as follows:

SQLServer

Here is a data source configuration sample for a SQLServer database.

```
<data-source
    class="com.evermind.sql.DriverManagerDataSource"
    name="OracleDS"
    location="jdbc/OracleCoreDS"
    xa-location="jdbc/xa/OracleXADS"
    ejb-location="jdbc/OracleDS"
    schema="database-schemas/ms-sql.xml"

    connection-driver="com.oracle.ias.jdbc.sqlserver.SQLServerDriver"
    username="mssql"
    password="mssql"

    url="jdbc:oracle:sqlserver://PZWU-PC\WUPZIAS;User=mssql;Password=mssql"
    inactivity-timeout="30"
/>
```

DB2

Here is a data source configuration sample for a DB2 database:

```
<data-source
```

```

        class="com.evermind.sql.DriverManagerDataSource"
        connection-driver="com.oracle.ias.jdbc.db2.DB2Driver"
        name="OracleDS"
        location="jdbc/OracleCoreDS"
        xa-location="jdbc/xa/OracleXADS"
        ejb-location="jdbc/OracleDS"
        schema="database-schemas/db2.xml"
        username="db2admin"
        password="db2admin"

        url="jdbc:oracle:db2://ying.us.oracle.com:50000;DatabaseName=sample;CreateDefaultPackage=TRUE"
        inactivity-timeout="30"
    />

```

Sybase

Here is a data source configuration sample for a Sybase database:

```

<data-source
    class="com.evermind.sql.DriverManagerDataSource"
    name="OracleDS"
    location="jdbc/OracleCoreDS"
    xa-location="jdbc/xa/OracleXADS"
    ejb-location="jdbc/OracleDS"
    schema="database-schemas/sybase.xml"
    connection-driver="com.oracle.ias.jdbc.sybase.SybaseDriver"
    username="JDBC_TEST"
    password="JDBC_TEST"
    url="jdbc:oracle:sybase://dlsun150:4101"
    inactivity-timeout="30"
/>

```

Informix

Here is a data source configuration sample for an Informix database:

```

<data-source
    class="com.evermind.sql.DriverManagerDataSource"
    name="OracleDS"
    location="jdbc/OracleCoreDS"
    xa-location="jdbc/xa/OracleXADS"
    ejb-location="jdbc/OracleDS"
    schema="database-schemas/informix.xml"

    connection-driver="com.oracle.ias.jdbc.informix.InformixDriver"
    username="tg4odbc"
    password="tg4odbc"

    url="jdbc:oracle:informix://dlsun150:3900;informixServer=gtw93;DatabaseName=gatewaydb"
    inactivity-timeout="30"
/>

```

6.6.4.3 Corrected Java Object Cache Code Example for Implementing a CacheEventListener

In the "Implementing a Cache Event Listener" section of the "Java Object Cache" chapter of the *Oracle Application Server Containers for J2EE Services Guide* for 10.1.2.0.2, Example 9-14 has mismatched braces and misleading indentation.

The corrected example for Implementing a CacheEventListener is as follows:

```
import oracle.ias.cache.*;

// A CacheEventListener for a cache object
class MyEventListener implements CacheEventListener
{
    public void handleEvent(CacheEvent ev) throws CacheException
    {
        MyObject obj = (MyObject)ev.getSource();
        obj.cleanup();
    }
}

class MyObject
{
    public void cleanup()
    {
        // do something
    }
}

import oracle.ias.cache.*;

// A CacheEventListener for a group object
class MyGroupEventListener implements CacheEventListener
{
    public void handleEvent(CacheEvent ev) throws CacheException
    {
        String groupName = (String)ev.getSource();
        notify("group " + groupName + " has been invalidated");
    }
    void notify(String str)
    {
        // do something
    }
}
```

6.6.4.4 Also Add the ojd1.jar File to the Classpath to Access EJBs

In the 10.1.2 *Oracle Application Server Containers for J2EE Services Guide*, add the following item to the "Client-Side Requirements" section of Chapter 5, "Oracle Remote Method Invocation" and again to the "Client-Side Requirements" section in Chapter 6, "J2EE Interoperability":

"Also add the ojd1.jar file to the classpath. The ojd1.jar file is located within the Application Server installation and is not part of the OC4J client package. The ojd1.jar can be downloaded from the following URL

http://www.oracle.com/technology/obe/obe_as_1012/j2ee/lookup/files/ojd1.jar

A tutorial related to this topic is available at the following URL:

http://www.oracle.com/technology/obe/obe_as_1012/j2ee/lookup/lookup.htm#install

6.6.5 Oracle Application Server Containers for J2EE Security Guide

This section describes issues with the Oracle Application Server Containers for J2EE Security Guide. It includes the following topics:

- [Section 6.6.5.1, "Incorrect Example in Deployment Roles and Users"](#)
- [Section 6.6.5.2, "Incorrect internal-settings.xml Information"](#)
- [Section 6.6.5.3, "Incorrect RMIPermission and AdministrationPermission Class Information"](#)

6.6.5.1 Incorrect Example in Deployment Roles and Users

On page 3-8 of the Oracle Application Server Containers for J2EE Security Guide, under "Deployment Roles and Users", there is an example that does not properly close the `<type>` and `<name>` subelements of a `<member>` element. Here is the corrected example:

```
<role>
  <name>developer</name>
  <members>
    <member>
      <type>user</type>
      <name>john</name>
    </member>
  </members>
</role>
```

6.6.5.2 Incorrect internal-settings.xml Information

The Oracle Application Server Containers for J2EE Security Guide incorrectly states that the `internal-settings.xml` file supports password indirection for `keystore-password` and `truststore-password` (page 14-2). This is incorrect; the `internal-settings.xml` file does not support password indirection.

6.6.5.3 Incorrect RMIPermission and AdministrationPermission Class Information

In several places in the *Oracle Application Server Containers for J2EE Security Guide* for release 10.1.0.2, the package for `RMIPermission` and for `AdministrationPermission` is **incorrectly** identified as `oracle.j2ee.server`.

The **correct** package for `RMIPermission` in 10.1.0.2 is `com.evermind.server.rmi`.

The **correct** package for `AdministrationPermission` in 10.1.0.2 is `com.evermind.server`.

6.6.6 OC4J Release Notes for 10.1.2.0.2

This section describes issues with the OC4J Release Notes for 10.1.2.0.2. It includes the following topic:

- [Section 6.6.6.1, "Disregard Previous Release Note: Package Name for RMIIInitialContextFactory Has Changed"](#)

6.6.6.1 Disregard Previous Release Note: Package Name for RMIIInitialContextFactory Has Changed

Disregard the following release note from the initial 10.1.2 OC4J Release Notes. The information does not apply to the 10.1.2 release.

"The package name for `RMIIInitialContextFactory` has changed from `oracle.j2ee.rmi.server` to `oracle.j2ee.rmi`."

Oracle HTTP Server

This chapter describes issues associated with Oracle HTTP Server. It includes the following topics:

- [Section 7.1, "General Issues and Workarounds"](#)
- [Section 7.2, "Configuration Issues and Workarounds"](#)

7.1 General Issues and Workarounds

This section describes general issues and workarounds. It includes the following topics:

- [Section 7.1.1, "Oracle HTTP Server \(1.0.2.2.x\) Cannot Be Used with Oracle Internet Directory 10g Release \(10.1.2\)"](#)
- [Section 7.1.2, "Log Error Message"](#)
- [Section 7.1.3, "Apache 2.0 Startup Fails"](#)

7.1.1 Oracle HTTP Server (1.0.2.2.x) Cannot Be Used with Oracle Internet Directory 10g Release (10.1.2)

Oracle does not support using the version of Oracle HTTP Server that is supplied with Oracle9iAS Release 1 (1.0.2.2.x) as a front end to OC4J supplied with Oracle Application Server 10g Release 2 (10.1.2). You must not use `mod_proxy` to route data between these two components.

Always use `mod_oc4j` to route data to and from OC4J supplied with Oracle Application Server 10g (10.1.2). Use `mod_proxy` to route data between Oracle HTTP Server component supplied with Oracle9iAS Release 1 (1.0.2.2.x) and OC4J supplied with Oracle9iAS Release 1 (1.0.2.2.x).

7.1.2 Log Error Message

During operations where `mod_oc4j` calls `mod_ossso` (such as login and logout), the following error message is printed to the Oracle HTTP server log:

```
[Mon Jun 27 23:57:07 2005] [error] [client 139.185.173.23] [ecid:
90258476571,1] MOD_OC4J_0376: Request initial processing failed in ac worker with
HTTP status code 1. This status will be passed back to the listener for error
handling.
```

This error message is harmless and can be ignored. It will be removed in a future release.

7.1.3 Apache 2.0 Startup Fails

For Apache 2.0 startup to succeed, link the current `libdb.so` version to `/usr/lib/libdb-3.3.so`.

For example, if the current shared library is in `/usr/lib` is `libdb-4.1.so`, then run the following command:

```
cd /usr/lib
ln -s /usr/lib/libdb-4.1.so libdb-3.3.so
```

7.2 Configuration Issues and Workarounds

This section describes configuration issues and their workarounds. It includes the following topics:

- [Section 7.2.1, "FastCGI Sockets Path Length Error"](#)
- [Section 7.2.2, "Oracle HTTP Server Does Not Start After Enabling Port Tunneling or SSL in `mod_oc4j`"](#)
- [Section 7.2.3, "Redirects Break If OracleAS Web Cache is Turned Off or is Disabled"](#)

7.2.1 FastCGI Sockets Path Length Error

On most platforms, the path for sockets used by FastCGI is limited to 108 characters. If an error such as the following is encountered, use the `FastCgiIpcDir` directive to specify a path name that is significantly shorter than 108 characters, such as `/tmp`:

```
Thu Oct 16 12:55:06 2003] [error] [client 148.87.9.44] [ecid: 82608810576,1]
FastCGI: failed to connect to (dynamic) server
"/opt/oracle/inst/Apache/Apache/fcgi-bin/echo": path
"/opt/oracle/inst/Apache/Apache/logs/fastcgi/dymanic/aac1cec5416b961cf002c5526b415
9"
is too long for a Domain socket
```

Note: The FastCGI limit of 108 characters is applicable to Apache 2.0 also.

7.2.2 Oracle HTTP Server Does Not Start After Enabling Port Tunneling or SSL in `mod_oc4j`

Oracle HTTP Server might not start if you modify its configuration to enable port tunneling (iASPT), or SSL in `mod_oc4j`. Following are the possible solutions for this issue:

- Recommended solution: if `mod_perl` is not needed, disable it by commenting out the `LoadModule perl_module libexec/libperl.so` line from `httpd.conf`.
- If `mod_perl` is needed, ensure that you are running the latest patch set from Sun, and move the `LoadModule` line for `mod_perl` until after the include of `mod_oc4j.conf` in `httpd.conf`.

7.2.3 Redirects Break If OracleAS Web Cache is Turned Off or is Disabled

By default, Oracle HTTP Server sends redirects to the OracleAS Web Cache listening port. If OracleAS Web Cache is not running or is disabled, then redirects from Oracle

HTTP Server (and any OC4J application behind Oracle HTTP Server) will not work. If you are not planning to run OracleAS Web Cache, then edit `httpd.conf` and `ssl.conf`, changing the `Port` directive so that it matches the `Listen` directive instead of the OracleAS Web Cache listening port.

Oracle Application Server TopLink

This chapter describes issues associated with Oracle Application Server TopLink (OracleAS TopLink). It includes the following topic:

- [Section 8.1, "General Issues and Workarounds"](#)

8.1 General Issues and Workarounds

This section describes general issue and workaround. It includes the following topic:

- [Section 8.1.1, "Installing Oracle Application Server TopLink Mapping Workbench from the Companion CD"](#)

8.1.1 Installing Oracle Application Server TopLink Mapping Workbench from the Companion CD

After installing the OracleAS TopLink Mapping Workbench from the Companion CD , you may encounter the following message in the console window when starting the OracleAS TopLink Mapping Workbench:

```
Unable to locate tools.jar.
```

This message can be safely ignored.

Oracle Application Server Portal

This chapter describes issues and workarounds related to Oracle Application Server Portal. It includes the following topics:

- [Section 9.1, "OracleAS Portal 10g Release 2 \(10.1.4\) Issues and Workarounds"](#)
- [Section 9.2, "OracleAS Portal 10g Release 2 \(10.1.2\) Issues and Workarounds"](#)

9.1 OracleAS Portal 10g Release 2 (10.1.4) Issues and Workarounds

This section describes issues and workarounds related to OracleAS Portal 10g Release 2 (10.1.4). It includes the following topics:

- [Section 9.1.1, "General Issues and Workarounds"](#)
- [Section 9.1.2, "Upgrade Issues and Workarounds"](#)
- [Section 9.1.3, "User Interface Issues and Workarounds"](#)
- [Section 9.1.4, "Portlet and Provider Issues and Workarounds"](#)
- [Section 9.1.5, "Globalization Support Issues and Workarounds"](#)
- [Section 9.1.6, "Documentation Errors"](#)

9.1.1 General Issues and Workarounds

This section describes general issues and their workarounds in OracleAS Portal. It includes the following topics:

- [Section 9.1.1.1, "Editing a Database Link Requires Password"](#)
- [Section 9.1.1.2, "Moving Content When Approval Is Enabled Does Not Require Approval"](#)
- [Section 9.1.1.3, "Download Fails for Files with .tgz, .gz, and .Z Extensions"](#)
- [Section 9.1.1.4, "Logout Link Does Not Work When Accessing OracleAS Portal Using a Mobile Device"](#)
- [Section 9.1.1.5, "Pushing Oracle Reports 10.1.2.0.2 Output to OracleAS Portal 10.1.4 Does Not Work"](#)
- [Section 9.1.1.6, "Internal Error Uploading Files or Images"](#)
- [Section 9.1.1.7, "OracleAS Portal Login Fails After OracleAS Cold Failover Cluster \(Middle Tier\) Configuration"](#)
- [Section 9.1.1.8, "Action Buttons Minimized to Dots on Portal Pages on IBM zSeries Based Linux"](#)

- [Section 9.1.1.9, "Oracle Text Support"](#)

9.1.1.1 Editing a Database Link Requires Password

If the database where the portal schema is installed is version 10.2 or later, then users must reenter the remote user's password when they rename or edit a database link from the Portal Navigator's Database Objects tab. This is applicable only for those database links that are created with the **Specific User** option.

9.1.1.2 Moving Content When Approval Is Enabled Does Not Require Approval

Moving content between pages or between regions of the same page does not trigger approvals. For example, when a target page is configured with an approval process and a contributor moves content from a source page to the target page, the moved content does not trigger the approval process on the target page, even when approval is required for all users.

9.1.1.3 Download Fails for Files with .tgz, .gz, and .Z Extensions

When you download documents with extensions .gz, .tgz, and .Z from OracleAS Portal, the download will fail.

As a workaround, perform the following steps:

1. Open the file, `ORACLE_HOME/Apache/Apache/conf/httpd.conf`.
2. Locate the Oracle HTTP Server `AddEncoding` directive.
3. Comment out the directives for the extensions with Z, gz, and tgz as shown in the following example:

```
# AddEncoding x-compress Z
# AddEncoding x-gzip gz tgz
```

4. Run the following command to synchronize the manual configuration changes done on the Oracle Application Server middle tier:

```
ORACLE_HOME/dcm/bin/dcmctl updateConfig -ct ohs
```

5. Restart Oracle HTTP Server by running the following command:

```
ORACLE_HOME/opmn/bin/opmnctl restartproc process-type=HTTP_Server
```

6. Restart OracleAS Web Cache by running the following command:

```
ORACLE_HOME/opmn/bin/opmnctl restartproc process-type=WebCache
```

This issue will be fixed in a future patch release.

9.1.1.4 Logout Link Does Not Work When Accessing OracleAS Portal Using a Mobile Device

When you access OracleAS Portal using a mobile device and the default home page is public, logging out does not end the session immediately. Consequently, nonpublic content accessed within the session continues to be accessible in the browser. It remains accessible until you close the browser or the wireless session times out.

You can fix this issue by applying patch 4568672 for Wireless server. This patch is available at:

<http://metalink.oracle.com>

9.1.1.5 Pushing Oracle Reports 10.1.2.0.2 Output to OracleAS Portal 10.1.4 Does Not Work

When OracleAS Portal 10g Release 2 (10.1.4) is used with Oracle Reports 10g Release 2 (10.1.2.0.2), you cannot push Oracle Reports output to OracleAS Portal.

For example, the following example does not work as expected:

```
http://mywebserver.com:7779/reports/rwservlet?server=myrep+report=test.rdf+
userid=scott/tiger@mydb+destype=oracleportal+desformat=PDF+pagegroup=mypaggrp+
outputpage=reports_output+itemtitle=pushtportal+statuspage=result
```

To resolve this issue, apply the Oracle Reports patch ARU 7769689.

9.1.1.6 Internal Error Uploading Files or Images

If your portal manages content with multiple translations and you are logged in with the default language, then you may see the following error when you try to upload a file or image item:

```
Internal error (WWC-00006)
Unexpected error - User-Defined Exception (WWC-35000)
Unexpected error - ORA-00001: unique constraint PORTAL.WWDAV$PKPATH) violated
(WWC-35000)
```

This error is displayed because another file or image item on the page has the same file name. As a workaround, perform any one of the following tasks:

- Use a different file name for the new file or image item.
- Run the DAV Loader utility (`wwdav_loader`), as described in the *Oracle Application Server Portal Configuration Guide*. Running DAV Loader can be very time consuming, however, this will enable you to upload the new file or image item without changing its file name.

9.1.1.7 OracleAS Portal Login Fails After OracleAS Cold Failover Cluster (Middle Tier) Configuration

If you configure an OracleAS Cold Failover Cluster (Middle Tier) that resides on the same node as the infrastructure associated with the middle tier from which the portal is running, then you may see the following error when you log in to OracleAS Portal:

```
Internal error (WWC-00006)
Unexpected error encountered in wwsec_app_priv.process_signon (User-Defined
Exception) (WWC-41417)
```

The Oracle Internet Directory host name in the Portal Dependency Settings file, `iasconfig.xml`, may incorrectly specify the host name of the new middle tier. As a workaround, perform the following steps:

1. Update the `IASInstance` element in the `iasconfig.xml` file so that the Host (of the `IASInstance` element associated with the Oracle Internet Directory component) is that of the Oracle Internet Directory host.
2. Run the `ptlconfig` tool to update the Oracle Internet Directory settings, as follows:

```
ptlconfig -dad <dad> -pw <portal schema password or Oracle Internet Directory
password> -oid
```

For more information about updating the `iasconfig.xml` file and running `ptlconfig`, refer to Appendix A "Using the Portal Dependency Settings Tool and File" in the *Oracle Application Server Portal Configuration Guide*.

9.1.1.8 Action Buttons Minimized to Dots on Portal Pages on IBM zSeries Based Linux

If the action buttons on the portal pages appear as dots, then increase the stack size shell limit to unlimited and restart the `OC4J_Portal` instance. Run the following command to set the stack size shell limit to unlimited:

```
prompt> ulimit -s unlimited
```

9.1.1.9 Oracle Text Support

OracleAS Portal uses Oracle Text functionality to extend its search capabilities. Oracle Text uses Verity filters to convert documents in proprietary and binary formats, such as Microsoft Word and PDF documents, into a common format that is suitable for indexing. Verity KeyView Filter SDK, which is embedded in Oracle Text, provides the ability to filter documents on a wide variety of platforms. However, Verity filters in Oracle Text are not supported on IBM zSeries Based Linux.

9.1.2 Upgrade Issues and Workarounds

This section describes upgrade-related issues and their workarounds in OracleAS Portal. It includes the following topic:

- [Section 9.1.2.1, "Relative Hypertext Links to Images and Documents May Break After Upgrade"](#)

9.1.2.1 Relative Hypertext Links to Images and Documents May Break After Upgrade

When upgrading to OracleAS Portal 10g Release 2 (10.1.4), relative hypertext links to images and documents may be broken. This can occur when the relative hypertext link uses a different case than the file name. For example, if a pre-upgrade image was uploaded to your portal with the name `PROCESS1.GIF`, and a hypertext link is referring to `process1.gif`, after the upgrade, the relative hypertext link to the image will be broken. You are most likely to encounter this in HTML templates or in documents that refer to images or other documents.

To address this issue, edit image and document names, making their case agree with the case used for the file names.

9.1.3 User Interface Issues and Workarounds

This section describes issues and workarounds related to the OracleAS Portal user interface. It includes the following topic:

- [Section 9.1.3.1, "Template Caching Option Displays Incorrectly in a Non-English Portal"](#)

9.1.3.1 Template Caching Option Displays Incorrectly in a Non-English Portal

In a non-English portal, the following template caching option label is incorrect (Template Properties: Main tab):

Cache Template Definition at User Level and Content at System Level for [] Minutes

The correct label for this template caching option is:

Cache Template Definition and Content at System Level for [] Minutes

See Also: [Section 9.1.6.1, "Help for Page and Template Caching Options Is Incorrect"](#)

9.1.4 Portlet and Provider Issues and Workarounds

This section describes issues and workarounds related to OmniPortlet, Web Clipping, Simple Parameter Form, Page portlet, and WSRP providers. This section includes the following topics:

- [Section 9.1.4.1, "Using OmniPortlet Web Page Data Source After Cloning"](#)
- [Section 9.1.4.2, "Truncated Data in Page Portlets"](#)
- [Section 9.1.4.3, "Download Latest Portlet Container for WSRP"](#)
- [Section 9.1.4.4, "Using WSRP Portlets that Display User Profile Attributes within OracleAS Portal"](#)
- [Section 9.1.4.5, "Registering WSRP Producers in Enterprise Configurations"](#)
- [Section 9.1.4.6, "Issue Adding or Deleting Portlets on Page Portlets"](#)
- [Section 9.1.4.7, "Issue When Accessing Page Portlet Using Federated Portal Adapter"](#)
- [Section 9.1.4.8, "Error in JPS Portlet After Redeployment"](#)
- [Section 9.1.4.9, "Error in Registering the WSRP Provider On IBM zSeries Based Linux"](#)
- [Section 9.1.4.10, "Error While Adding Portlets"](#)

9.1.4.1 Using OmniPortlet Web Page Data Source After Cloning

If you clone a middle-tier instance, then you must perform the following steps before you can use OmniPortlet Web Page Data Source:

1. Open the `web.xml` file.

```
ORACLE_HOME/j2ee/OC4J_Portal/applications/portalTools/omniPortlet/WEB-INF/web.xml
```

2. If the `usePort` context parameter is present, then set it to the Oracle HTTP Server port of the cloned target instance. This port number is specified in `ORACLE_HOME/install/portlist.ini`.
3. Restart the OC4J_Portal instance.

```
ORACLE_HOME/opmn/bin/opmnctl stopproc process-type=OC4J_Portal
ORACLE_HOME/opmn/bin/opmnctl startproc process-type=OC4J_Portal
```

9.1.4.2 Truncated Data in Page Portlets

In an OracleAS Portal installation that has Secure Sockets Layer (SSL) throughout (see the *Oracle Application Server Portal Configuration Guide*, Section 6.3.2.1.4 "SSL Throughout OracleAS Portal"), the page portlet output is truncated and the portlet displays some junk characters in the following scenarios:

- A page portlet that contains a tab is placed on a page whose definition is cached at the system-level

- The definition of a page portlet that contains a tab specifies system-level caching
- An instance of a page portlet that contains a tab specifies system-level caching

To avoid truncation and junk characters in a page portlet, specify user-level caching for the container page definition, the page portlet definition, and the page portlet instance.

This issue will be addressed in a future patch release. The patch will enable the use of system level caching in the presence of page portlets with tabs, without such errors.

9.1.4.3 Download Latest Portlet Container for WSRP

After the release of OracleAS Portal 10.1.2.0.2, the portlet container for WSRP was updated and continues to be updated. Review the PDK software download page for information on new versions of the container as well as any required patches that need to be applied before using it:

<http://www.oracle.com/technology/products/ias/portal/pdk.html>

9.1.4.4 Using WSRP Portlets that Display User Profile Attributes within OracleAS Portal

When a user that has not yet been authenticated visits a publicly accessible page in OracleAS Portal, a temporary session is created using an internal system user called "PUBLIC". Because PUBLIC is an internal system user that represents an unauthenticated user session, it does not expose the typical user profile attributes associated with a normal authenticated user session (for example, First name, Last name, etc.). Therefore, it is recommended that portlets that explicitly leverage user profile information only be added to non-public (that is, authenticated) pages. This will ensure that the user profile data exists for the portlet to leverage.

9.1.4.5 Registering WSRP Producers in Enterprise Configurations

When you register a WSRP producer in an Enterprise configuration, you must create a Web Services Definition Language (WSDL) document manually, then register the WSRP producer using that WSDL. This is because the dynamically generated WSDL creates URLs using the HTTPS protocol and the HTTPS port while WSRP producers use HTTP.

Note: A *producer* for WSRP portlets is analogous to a *provider* for PDK-Java portlets.

To create a WSDL document manually, perform the following tasks:

1. View the dynamically generated WSDL through your browser (preferably Internet Explorer).

To view the WSDL for our WSRP samples, go to:

`http://<host>:<external http port>/portletapp/portlets?WSDL`

2. Save the file from the browser to any externally available location.

For our WSRP Samples, save the file from the browser into the following directory:

`ORACLE_HOME/j2ee/home/applications/portletapp/wsrp-samples`

Save the file as `wsrpsamples.wsdl`.

3. Edit the file, replacing `https` with `http` and correcting the ports to be the external `http` ports.

4. View the file through a browser.

For example, for our WSRP Samples use the following URL:

```
http://<host>:<external http
port>/portletapp/wsrpsamples.wsdl
```

5. Use the URL to your *.wsdl file (such as the URL under Step 4) when you register the WSRP producer.

For more information about Enterprise configurations, see the *Oracle Application Server Enterprise Deployment Guide*

(<http://www.oracle.com/technology/documentation/appserver1012.html>)

9.1.4.6 Issue Adding or Deleting Portlets on Page Portlets

If you have the Personalize Portlets (Full) privilege on two pages, Page A and Page B, then you cannot add or delete portlets on Page B when Page B is displayed as a page portlet on Page A. However, you can add or delete portlets when pages A and B are displayed as individual pages. This is a known issue.

9.1.4.7 Issue When Accessing Page Portlet Using Federated Portal Adapter

The Federated Portal Adapter enables you to display remote portal pages in your portal. However, if both portal instances do not share the same OracleAS Single Sign-On server, then you cannot display a remote portal page as a page portlet, even if the remote page is public. A message is displayed instead of the page portlet, as shown in the following example:

```
Portlet 257,75057 responded with content-type text/plain when the client was
requesting content-type text/html
```

As a workaround, configure both portal instances to use the same OracleAS Single Sign-On server.

9.1.4.8 Error in JPS Portlet After Redeployment

When you redeploy your portlets to the portlet container, all existing sessions between the producer and all of its consumers are lost. If a consumer tries to reuse an existing producer session, then it may receive an error message the first time it tries to contact the producer after redeployment, as shown in the following example:

```
Error: Could not get markup. The cookie or session is invalid or there is a
runtime exception.
```

To reestablish the producer's session, refresh the portal page. You will not see this error message if you are reaccessing the portlet from a new browser session because it automatically establishes a new producer session.

9.1.4.9 Error in Registering the WSRP Provider On IBM zSeries Based Linux

When you register the WSRP provider on IBM zSeries Based Linux, the following error occurs:

```
An error occurred during the call to the WSRP Provider: Java stack trace from root
exception:
```

```
java.rmi.ServerException: Internal Server Error
    (java.nio.charset.IllegalCharsetNameException: "utf-8")
    at com.sun.xml.rpc.client.StreamingSender._raiseFault(StreamingSender.java:384)
    at com.sun.xml.rpc.client.StreamingSender._send(StreamingSender.java:245)
```

```
at
oracle.webdb.wsrp.WSRP_v1_ServiceDescription_PortType_Stub.getServiceDescripti
on(WSRP_v1_ServiceDescription_PortType_Stub.java:63)
at
oracle.webdb.wsrp.client.design.v1.OraWSRP_v1_ServiceDescription_PortType.getS
erviceDescription(Unknown Source)
(WWC-43273)
```

To workaround this issue, apply ARU 8464396 patch as mentioned in bug number 4741897.

9.1.4.10 Error While Adding Portlets

When you add portlet to a page, the following memory error is displayed along with JspCompileException:

```
[ **Out of memory, aborting** ]
[ ]
[ *** panic: JVMST018: Cannot allocate memory for
initializeMarkAndAllocBits(allocbits1)
```

To workaround to this issue, lower the maximum heap size by adding -Dbuild.compiler.options=-J-Xmx750M option to the OC4J_Portal java-options in the opmn.xml file. For example,

```
<process-type id="OC4J_Portal" module-id="OC4J">
<data id="java-options"
value="-Dbuild.compiler.options=-J-Xmx750M
-Djava.security.policy=$ORACLE_HOME/j2ee/OC4J_Portal/config/java2.policy
-Djava.awt.headless=true -Xmx256m "/>
```

9.1.5 Globalization Support Issues and Workarounds

This section describes issues and workarounds related to Globalization Support in OracleAS Portal. It includes the following topics:

- [Section 9.1.5.1, "Text Entry Always Right to Left in BiDi Languages"](#)
- [Section 9.1.5.2, "Browser Limitation in BiDi Languages"](#)
- [Section 9.1.5.3, "Non-ASCII Character Limitations in OracleAS Portal"](#)
- [Section 9.1.5.4, "Non-ASCII Character Limitations in Oracle Instant Portal"](#)
- [Section 9.1.5.5, "Errors Displayed When the OracleAS Portal Language Is Traditional Chinese"](#)

9.1.5.1 Text Entry Always Right to Left in BiDi Languages

The direction of all text areas and fields is right to left (RTL). However, you may want some text areas to work left to right (LTR). Internet Explorer users can change this by pressing the left hand side Ctrl and Shift keys.

9.1.5.2 Browser Limitation in BiDi Languages

To display Oracle Instant Portal correctly in bi-directional languages such as Arabic and Hebrew, use Internet Explorer.

9.1.5.3 Non-ASCII Character Limitations in OracleAS Portal

This section discusses non-ASCII character limitations when working with OracleAS Portal:

- In Web Folders, if you change the name of a portal page to use non-ASCII characters, then an error message displays.
- In some non-ASCII character set environments, you cannot use the **Browse Users** or **Browse Groups** list of values to select a user or group name. As a workaround, you can enter the user or group name manually.
- When you copy and paste an item URL containing non-ASCII characters from one browser Location or Address field into another, you may not be able to access the item if your login credentials have not been authenticated through OracleAS Single Sign-On.

As a workaround, log in to the portal before you access the item and copy the item URL.

9.1.5.4 Non-ASCII Character Limitations in Oracle Instant Portal

To use Oracle Instant Portal in an environment that supports non-ASCII character sets, you must use the UTF8 or AL32UTF8 database character set.

9.1.5.5 Errors Displayed When the OracleAS Portal Language Is Traditional Chinese

When the portal language is set to Traditional Chinese you may see errors while working with portlets, such as the Custom Search portlet, or when using the Navigator. Such errors can occur if the value of the `shared_pool_size` parameter of the OracleAS Metadata Repository database is set too low.

As a workaround, increase the value of the `shared_pool_size` parameter of the OracleAS Metadata Repository database. The recommended minimum size is 144MB, but this is too low for the Traditional Chinese language. Increase the value of the `shared_pool_size` parameter to 216MB, or higher.

9.1.6 Documentation Errors

This section describes known errors in OracleAS Portal documentation. It includes the following topic:

- [Section 9.1.6.1, "Help for Page and Template Caching Options Is Incorrect"](#)

9.1.6.1 Help for Page and Template Caching Options Is Incorrect

Page and template caching options described in the online Help are incorrect. Refer to Chapter 22, "Improving Page Performance" in the *Oracle Application Server Portal User's Guide* for correct information on page and template caching.

9.2 OracleAS Portal 10g Release 2 (10.1.2) Issues and Workarounds

This section describes issues and workarounds related to OracleAS Portal 10g Release 2 (10.1.2). It includes the following topics:

- [Section 9.2.1, "General Issues and Workarounds"](#)
- [Section 9.2.2, "Upgrade Issues and Workarounds"](#)
- [Section 9.2.3, "User Interface Issues and Workarounds"](#)

- [Section 9.2.4, "Export and Import Issues and Workarounds"](#)
- [Section 9.2.5, "Portlet and Provider Issues and Workarounds"](#)
- [Section 9.2.6, "PDK Issues and Workarounds"](#)
- [Section 9.2.7, "Globalization Support Issues and Workarounds"](#)
- [Section 9.2.8, "Documentation Errata"](#)

9.2.1 General Issues and Workarounds

This section describes general issues and their workarounds in OracleAS Portal. It includes the following topics:

- [Section 9.2.1.1, "Error in portal.log File After Installing OracleAS Metadata Repository"](#)
- [Section 9.2.1.2, "OracleAS Portal Login Fails After OracleAS Cold Failover Cluster \(Middle Tier\) Configuration"](#)
- [Section 9.2.1.3, "Action Buttons Minimized to Dots on Portal Pages on IBM zSeries Based Linux"](#)

9.2.1.1 Error in portal.log File After Installing OracleAS Metadata Repository

After installing OracleAS Metadata Repository using OracleAS Metadata Repository Creation Assistant, the following error is recorded in the `portal.log` file:

```
Error while opening file:
/private1/iasinst/Repca_050712/portal/admin/plsql/lib/sitedb.jar
```

```
Exception java.io.FileNotFoundException:
/private1/iasinst/Repca_050712/portal/admin/plsql/lib/sitedb.jar
```

This error does not affect the installation process and can be ignored.

9.2.1.2 OracleAS Portal Login Fails After OracleAS Cold Failover Cluster (Middle Tier) Configuration

If you configure an OracleAS Cold Failover Cluster (Middle Tier) that resides on the same node as the infrastructure associated with the middle tier from which the portal is running, then you may see the following error when you log in to OracleAS Portal:

```
Internal error (WWC-00006)
Unexpected error encountered in wwsec_app_priv.process_signon
(User-Defined Exception) (WWC-41417)
```

The Oracle Internet Directory host name in the Portal Dependency Settings file, `iasconfig.xml`, may incorrectly specify the host name of the new middle tier. As a workaround, perform the following steps:

1. Update the `IASInstance` element in the `iasconfig.xml` file so that the `Host` (of the `IASInstance` element associated with the Oracle Internet Directory component) is that of the Oracle Internet Directory host.
2. Run the `ptlconfig` tool to update the Oracle Internet Directory settings, as shown in the following example:

```
ptlconfig -dad <dad> -pw <portal schema password or Oracle Internet Directory
password> -oid
```


For more information about updating the `iasconfig.xml` file and running `ptlconfig`, refer to Appendix A "Using the Portal Dependency Settings Tool and File" in *Oracle Application Server Portal Configuration Guide*.

9.2.1.3 Action Buttons Minimized to Dots on Portal Pages on IBM zSeries Based Linux

If the action buttons on the portal pages appear as dots, then increase the stack size shell limit to unlimited and restart the `OC4J_Portal` instance. Run the following command to set the stack size shell limit to unlimited:

```
prompt> ulimit -s unlimited
```

9.2.2 Upgrade Issues and Workarounds

This section describes upgrade-related issues and their workarounds in OracleAS Portal. It includes the following topic:

- [Section 9.2.2.1, "Configuring OracleAS Portal After Upgrade"](#)
- [Section 9.2.2.2, "OracleAS Portal Users Cannot Log on to Oracle Ultra Search"](#)
- [Section 9.2.2.3, "Apply Portal Patch After Upgrading Database from Release 9i to 10g"](#)
- [Section 9.2.2.4, "Additional Step Required When Upgrading OracleAS Metadata Repository Release 9.0.4.3 to 10.1.4.0.1"](#)

9.2.2.1 Configuring OracleAS Portal After Upgrade

If OracleAS Portal is not configured in the source Oracle home before you upgrade, then it will remain unconfigured even after the upgrade. You can configure OracleAS Portal after upgrading the middle tier or after upgrading the OracleAS Metadata Repository, by performing the following steps:

1. Modify the port entries in the `ptlem` script:

```
DESTINATION_ORACLE_HOME/assistants/opca/ptlem.sh
```

```
%ORACLE_HOME%\assistants\opca\ptlem.bat
```

You need to update the following port values:

- `http_port` - Oracle HTTP Server port
(Get this value from `DESTINATION_ORACLE_HOME/Apache/Apache/conf/httpd.conf` or `%ORACLE_HOME%\Apache\Apache\conf\httpd.conf`)
- `wc_invalid` - OracleAS Web Cache invalidation port
- `wc_admin` - OracleAS Web Cache administration port
- `em_port` - Application Server Control port

Use Oracle Enterprise Manager 10g to obtain port values for `wc_invalid`, `wc_admin`, and `em_port` as follows:

- a. In your browser, enter the URL for the Application Server Control Console.
- b. Enter the `ias_admin` login credentials that you used for the destination Oracle home.
- c. In the Standalone Instances section, click the name of the destination middle-tier instance.

- d. Click the **Ports** tab.

The Ports page displays the port values you require.

2. Use Oracle Enterprise Manager 10g Application Server Control Console to configure OracleAS Portal.

See Also: Section 7.2.2 "Using Application Server Control Console to Configure OracleAS Portal" in the *Oracle Application Server Portal Configuration Guide*.

3. Run `ptlconfig` to configure the portal schema in the OracleAS Metadata Repository with the upgraded middle-tier instance as follows:

```
DESTINATION_ORACLE_HOME/portal/conf/ptlconfig -dad <portal_dad>  
DESTINATION_ORACLE_HOME\portal\conf\ptlconfig -dad <portal_dad>
```

Note: If you configure OracleAS Portal using Application Server Control, without updating the ports (in `ptlem.sh`), then the `iasconfig.xml` and `targets.xml` files will contain incorrect port entries; therefore, the portal will not be accessible. To reconfigure OracleAS Portal with correct port values and make it accessible, you must first enter correct port values in `iasconfig.xml` and `targets.xml`, and then configure OracleAS Portal.

Updating the targets.xml File

To update `DESTINATION_ORACLE_HOME/sysman/emd/targets.xml` \sysman\emd\targets.xml:

1. Modify the port entries in `DESTINATION_ORACLE_HOME/assistants/opca/ptlem.sh` \assistants\opca\ptlem.bat as mentioned earlier.
2. Back up `DESTINATION_ORACLE_HOME/sysman/emd/targets.xml` \sysman\emd\targets.xml.
3. Remove the target entry for the portal you are reconfiguring. You must remove the complete target entry for `<Target TYPE = "oracle_portal">`. For example,

```
<Target TYPE="oracle_portal"  
....  
</Target>
```

Before removing the target entry for this portal, ensure that this target contains the property `<Property NAME="portal_DAD" VALUE="portal"/>` and its OracleHome property maps to the destination middle tier.

4. Save the file.
5. Set the value of the `ORACLE_HOME` environment variable to `DESTINATION_ORACLE_HOME`.
6. Run the script `DESTINATION_ORACLE_HOME/assistant/opca/ptlem.sh` \assistant\opca\ptlem.bat.
7. Check the log file, `DESTINATION_ORACLE_HOME/assistant/opca/install.log` \assistant\opca\install.log, for errors.

Updating the iasconfig.xml File

To update `DESTINATION_ORACLE_`

`HOME/portal/conf/iasconfig.xml\portal\conf\iasconfig.xml`:

1. Update the port values for the `WebCacheComponent` and `EMComponent` elements that the portal instance you are reconfiguring refers to. You can obtain the upgraded port values for all the following ports from Oracle Enterprise Manager 10g, as described earlier.
 - Update `ListenPort`, `InvalidationPort`, and `AdminPort` in `WebCacheComponent` with `WebCache Listen Port`, `Web Cache Invalidation`, and `WebCache Admin Port` respectively.
 - Update `ConsoleHTTPPort` in `EMComponent` with `Application Server Control Port`.
2. Run `ptlconfig` to configure the portal schema in the OracleAS Metadata Repository with the upgraded middle-tier instance as follows:

```
DESTINATION_ORACLE_HOME/portal/conf/ptlconfig -dad <portal_dad> [-pw <portal
schema password>]
DESTINATION_ORACLE_HOME\portal\conf\ptlconfig -dad <portal_dad> [-pw <portal
schema password>]
```

For more information on `iasconfig.xml` and `ptlconfig`, refer to *Oracle Application Server Portal Configuration Guide*.

After you have updated both the `targets.xml` and `iasconfig.xml` files, bounce back the Oracle HTTP Server and OC4J_Portal from the Application Server Control Console.

9.2.2.2 OracleAS Portal Users Cannot Log on to Oracle Ultra Search

OracleAS Portal users cannot log on to manage Oracle Ultra Search if the OracleAS Metadata Repository is prepared by a 9.2.0.x database with OracleAS Metadata Repository Creation Assistant installed.

The workaround is to log on as a database user to manage Oracle Ultra Search, or invoke the following PL/SQL API to grant `orcladmin` super-user privileges.

Log on as `WKSYS`.

```
BEGIN
  WK_ADM.GRANT_SYSADMIN(
    <orcladmin dn>,
    1,
    null,
    <subscriber dn>
  )
EXCEPTION WHEN OTHERS THEN WK_ERR.RAISE;
END;
```

Here is an example:

```
BEGIN
WK_ADM.GRANT_SYSADMIN('orcladmin',1,null,'dc=oracle,dc=com');
EXCEPTION WHEN OTHERS THEN WK_ERR.RAISE;
END;
/
```

Note: The `wk_adm_code` from 9.2 does not support the fully qualified name and, therefore, generates an ORA-6502 error if you use the following string:

```
cn=orcladmin,cn=users,dc=oracle,dc=com
```

To avoid this error, specify only `orcladmin` as the user ID rather than the complete string.

9.2.2.3 Apply Portal Patch After Upgrading Database from Release 9i to 10g

After you upgrade the database where the Portal schema resides, from release 9i to release 10g, apply patch 4543413. This is relevant to OracleAS Portal releases 10.1.2.0.0, 10.1.2.0.1, 10.1.2.0.2, and 10.1.4.

9.2.2.4 Additional Step Required When Upgrading OracleAS Metadata Repository Release 9.0.4.3 to 10.1.4.0.1

If you have applied Oracle Application Server 10g (9.0.4) Patchset 3 (9.0.4.3) to your release 9.0.4 instance, and now want to upgrade the OracleAS Metadata Repository to release 10.1.4.0.1 by running 10.1.4.0.1 MRUA, you must first apply patch 5365207 to your 10.1.4.0.1 MRUA. For this, you must copy the contents of the 10.1.4.0.1 MRUA and Utilities CD-ROM to a location where you have write permission. Then apply patch 5365207 on your 10.1.4.0.1 MRUA staged directory. You can find this patch on Oracle *Metalink* at

<http://metalink.oracle.com>

Use the patched version of 10.1.4.0.1 MRUA to upgrade a release 9.0.4.3 instance to release 10.1.4.0.1. For details about running MRUA, refer to *Oracle Application Server Upgrade and Compatibility Guide*.

If you do not apply patch 5365207, then the portal component upgrade will fail with the following error when running 10.1.4.0.1 MRUA:

```
Calling upgrade plugin for PORTAL
Error: Component upgrade failed PORTAL
Error: PORTAL component version is: 9.0.4.3.0 INVALID
```

This error message is displayed on screen and is also recorded in the MRUA log file, `ORACLE_HOME\upgrade\logs\mrua.log`. For the detailed error message, review the portal upgrade precheck log file, `ORACLE_HOME\upgrade\temp\portal\precheck.log`. Refer to *Oracle Application Server Upgrade and Compatibility Guide* for further information on reviewing the upgrade log files.

The detailed error message from the `precheck.log` file reads as follows:

```
### Install Schema Validation Utility
>>> Running upg/common/prechk/svuver.sql .
Portal SQL script started at Thu Jun  1 08:55:22 2006
Connected.
# Beginning outer script: common/prechk/svuver
# Portal Schema Version = 9.0.4.3.0
# Version of schema validation utility being installed =
Connected.
###
### ERROR: Exception Executing upg/common/prechk/svuver.sql
###
```

```

### Check Failed at Thu Jun  1 08:55:24 2006 Continuing as PreCheck mode is
specified

### Invoke Schema Validation Utility in Report Mode
>>> Running upg/common/prechk/./svurun.sql .
Portal SQL script started at Thu Jun  1 08:55:24 2006
Connected.
# Beginning outer script: common/prechk/svurun
#-- Beginning inner script: common/common/svurun

l_mode := wwutl_schema_validation.MODE_REPORT;

*

ERROR at line 5:
ORA-06550: line 5, column 19:
PLS-00201: identifier 'WWUTL_SCHEMA_VALIDATION.MODE_REPORT' must be declared
ORA-06550: line 5, column 9:
PL/SQL: Statement ignored
ORA-06550: line 8, column 19:
PLS-0020: identifier 'WWUTL_SCHEMA_VALIDATION.MODE_CLEANUP' must be declared

ORA-06550: line 8, column 9:
PL/SQL: Statement ignored
ORA-06550: line 15, column 5:
PLS-00201: identifier 'WWUTL_SCHEMA_VALIDATION.VALIDATE_ALL' must be declared

ORA-06550: line 15, column 5:
PL/SQL: Statement ignored
Connected.
###
### ERROR: Exception Executing upg/common/prechk/./svurun.sql REPORT
###
### Check Failed at Thu Jun  1 08:55:25 2006 Continuing as PreCheck mode is
specified

```

Note: In the case where you have already encountered this error, apply patch 5365207 and rerun the upgrade. There is no need to restore the OracleAS Metadata Repository from backup before rerunning the upgrade. This is because the upgrade failed during the precheck phase and the portal schema in the OracleAS Metadata Repository has not been altered in the precheck phase.

If the portal upgrade fails in the precheck phase even after applying patch 5365207, then review the precheck log file for details about the new error. Based on the description of the error, resolve the problem and perform the upgrade again, or contact Oracle Support Services for help.

9.2.3 User Interface Issues and Workarounds

This section describes User Interface-related issues and their workarounds in OracleAS Portal. It includes the following topics:

- [Section 9.2.3.1, "Issue Adding Regions to Pages Displayed in the Generic Page Portlets"](#)
- [Section 9.2.3.2, "Portlets on Subpages Not Displayed"](#)

- [Section 9.2.3.3, "Cannot Set Privileges Using List View on Pages Inheriting Privileges from Parent or Template"](#)

9.2.3.1 Issue Adding Regions to Pages Displayed in the Generic Page Portlets

When you add a region to a page displayed in a generic page portlet, the new region is not displayed immediately as expected. As a workaround, manually invalidate the cache by clicking the **Clear Cache** link (Access tab) for the page containing the generic page portlet.

9.2.3.2 Portlets on Subpages Not Displayed

If a page displays a page portlet (Portlet A) with a subpage link to a page with tabs and portlets (Portlet B), the portlets under tabs in Portlet B are not displayed if you use the subpage link to navigate to Portlet B, from Portlet A. This is a known issue.

9.2.3.3 Cannot Set Privileges Using List View on Pages Inheriting Privileges from Parent or Template

If you use the List View to set access privileges for one or more pages, then privileges will *not* be set on pages inheriting privileges from a parent page or template. As a workaround, change the privileges for such pages individually, that is, using the Access tab for the subpage.

9.2.4 Export and Import Issues and Workarounds

This section describes export and import issues and their workarounds in OracleAS Portal. It includes the following topic:

- [Section 9.2.4.1, "Export and Import Does Not Support Reports Server Components"](#)

9.2.4.1 Export and Import Does Not Support Reports Server Components

If you include Reports Server Components within a transport set, then they are deleted on export and import. In addition, do not configure the Oracle Reports item type in any page groups intended for export and import. If you do, then the following error is displayed when you try to configure item types in the imported page group (by clicking the Content Type and Classifications **Edit** link on the Configure tab for the page group):

```
Internal error (WWC-00006)
Unexpected error - User-Defined Exception (WWC-35000)
Unexpected error - ORA-01403: no data found (WWC-35000)
```

9.2.5 Portlet and Provider Issues and Workarounds

This section describes issues and workarounds related to OmniPortlet, Web Clipping, Simple Parameter Form, and Page portlet. This section includes the following topics:

- [Section 9.2.5.1, "Using OmniPortlet Web Page Data Source After Cloning"](#)
- [Section 9.2.5.2, "Error Exporting and Importing OmniPortlet and Web Clipping Customizations"](#)
- [Section 9.2.5.3, "Issue Adding or Deleting Portlets on Page Portlets"](#)

9.2.5.1 Using OmniPortlet Web Page Data Source After Cloning

If you clone a middle-tier instance, then you must perform the following steps before you can use OmniPortlet Web Page Data Source:

1. Open the `web.xml` file.

```
ORACLE_HOME/j2ee/OC4J_Portal/applications/portalTools/omniPortlet/WEB-INF/web.xml
```

2. If the `usePort` context parameter is present, then set it to the Oracle HTTP Server port of the cloned target instance. This port number is specified in `ORACLE_HOME/install/portlist.ini`.

3. Restart the OC4J_Portal instance.

```
ORACLE_HOME/opmn/bin/opmnctl stopproc process-type=OC4J_Portal
ORACLE_HOME/opmn/bin/opmnctl startproc process-type=OC4J_Portal
```

9.2.5.2 Error Exporting and Importing OmniPortlet and Web Clipping Customizations

During the import or export of OmniPortlet or Web Clipping provider customizations, an error message similar to the following may be displayed:

```
[Warning: (WWU-74505)] context = Import of one of the web provider customization
failed user = PORTAL An error occurred importing data to the web provider
OMNIPORTLET.
```

As a workaround, refresh the OmniPortlet and Web Clipping providers in the portlet repository on both the source and target portals before performing an import or export.

This issue is valid only for release 10.1.2.0.0. It has been fixed in release 10.1.2.0.2.

9.2.5.3 Issue Adding or Deleting Portlets on Page Portlets

If you have the Customize Portlets (Full) privilege on two pages, Page A and Page B, then you cannot add or delete portlets on Page B when Page B is displayed as a page portlet on Page A. However, you can add or delete portlets when pages A and B are displayed as individual pages. This is a known issue.

9.2.6 PDK Issues and Workarounds

Oracle Application Server Portal Developer Kit (PDK) version 10.1.2 is included with the Portal and Wireless installation. Release notes for the PDK-Java and PDK-PL/SQL can be found at the following middle-tier `ORACLE_HOME` locations:

- **PDK-Java:** `ORACLE_HOME/portal/pdkjava/v2/pdkjava.v2.releasenotes.html`
- **PDK-PL/SQL:** `ORACLE_HOME/portal/pdkjava/v2/pdkplsql.release.notes.html`

Latest Version of OracleAS PDK

New versions of the OracleAS PDK are released periodically providing new features, new APIs, and additional documentation. To take advantage of all the latest features, download the latest PDK from the PDK downloads page on the Oracle Technology Network (OTN) at

<http://www.oracle.com/technology/products/ias/portal/pdk.html>.

Release notes for the latest OracleAS PDK version are available on Oracle Application Server Portal on OTN and also in these PDK download locations:

- `pd\p\sql\pdk\sql.release.notes.html`
- `pd\j\pdk\v2\pdkjava.v2.release.notes.html`

This section includes the following PDK-related issues and workarounds in OracleAS Portal:

- [Section 9.2.6.1, "Support for WSRP and JSR 168"](#)
- [Section 9.2.6.2, "Restrictions on Struts Text Tag Lifted"](#)

See Also: [Section 9.2.8.1.12, "Exposing Your Application as a Web Service"](#) for issues related to adding a custom JPS provider.

9.2.6.1 Support for WSRP and JSR 168

OracleAS Portal supports the building of Java Specification Request (JSR) 168 portlets starting in Oracle Application Server 10g *Release 1 (9.0.4)*. OracleAS Portal does not yet support consumption of Web Services for Remote Portlets (WSRP)-enabled portlets. Currently, you can only test your JSR 168 portlets against the hosted OracleAS Portal Verification Service at <http://portalstandards.oracle.com/> or the Developers Preview for OracleAS Portal available for download. Note that both the Developers Preview and the hosted OracleAS Portal Verification Service are provided for development purposes only and, should not be used for production systems.

See Also: [Section 9.2.8.1.10, "Registering JSR Portlets"](#)

9.2.6.2 Restrictions on Struts Text Tag Lifted

In previous releases of the Oracle Application Server Portal Developer Kit, in order to use the Struts text tag for entering form values, the provider `passAllUrlParams` flag had to be set to `true`, which affected the performance of OracleAS Web Cache, and the field name had to be unqualified. There are no such restrictions from OracleAS Portal 10g Release 2 (10.1.2) onwards.

9.2.7 Globalization Support Issues and Workarounds

This section describes issues and workarounds related to Globalization Support in OracleAS Portal. It includes the following topics:

- [Section 9.2.7.1, "Oracle Text Searching Limitation \(Text Files and HTML Files\)"](#)
- [Section 9.2.7.2, "Text Entry Always Right to Left in BiDi Languages"](#)
- [Section 9.2.7.3, "Non-ASCII Character Limitations in OracleAS Portal"](#)
- [Section 9.2.7.4, "Non-ASCII Character Limitations in Oracle Instant Portal"](#)
- [Section 9.2.7.5, "Shared Type Objects Cannot Be Exposed in Non-English Page Group"](#)
- [Section 9.2.7.6, "Translations Lost When Item Versioning Is Enabled"](#)

9.2.7.1 Oracle Text Searching Limitation (Text Files and HTML Files)

In some non-ASCII character set environments, you are unable to search non-ASCII character content of plain text files and HTML files.

You can search plain text and HTML files if the document character set is the same as the database character set.

9.2.7.2 Text Entry Always Right to Left in BiDi Languages

The direction of all text areas and fields is right to left (RTL). However, you may want some text areas to work left to right (LTR). Internet Explorer users can change this by pressing the left hand side Ctrl and Shift keys.

9.2.7.3 Non-ASCII Character Limitations in OracleAS Portal

This section discusses non-ASCII character limitations when working with OracleAS Portal:

- Non-ASCII XML data is not displayed correctly in the XML Portlet. To display non-ASCII XML data, use OmniPortlet, which has this functionality.
- If you use non-ASCII characters in Web Provider Display Names, then they are not displayed correctly. Similarly non-ASCII characters used in Provider Group Display Names cannot be displayed.
- In Web Folders, if you change the name of a portal page to use non-ASCII characters, then an error message displays.
- In some non-ASCII character set environments, you cannot use the **Browse Users** or **Browse Groups** list of values to select a user or group name. As a workaround, you can enter the user or group name manually.
- When you copy and paste an item URL containing non-ASCII characters from one browser Location or Address field into another, you may not be able to access the item if your login credentials have not been authenticated through OracleAS Single Sign-On.

As a workaround, log in to the portal before you access the item and copy the item URL.

9.2.7.4 Non-ASCII Character Limitations in Oracle Instant Portal

To use Oracle Instant Portal in an environment that supports non-ASCII character sets, you must use the UTF8 or AL32UTF8 database character set.

9.2.7.5 Shared Type Objects Cannot Be Exposed in Non-English Page Group

Shared type objects (page types and item types) always have English as the default language. If you create a page group in a language other than English, then a shared type cannot be made available to the page group unless a translation exists for the shared type in the default language of the page group.

To create the translation, follow these steps:

1. Enable the language for the Shared Objects page group.

For details, see *Oracle Application Server Portal User's Guide - Section 4.6.1 Creating a Translation*.

2. Switch to the language in the **Set Language** portlet.
3. Edit the page type or item type while the session language is set to the non-English language.

This automatically creates a translation of the type in that language.

You can now make the shared type available to the non-English page group.

9.2.7.6 Translations Lost When Item Versioning Is Enabled

If versioning is enabled and the page group has two or more translations (for example, the default language is English and translations are enabled for German and French), then adding a translation as a new version does not display the other translation. For example, if you add or edit a French translation as a new version, then the German translation is no longer visible to the page viewers. As a workaround, when multiple translations are required, disable item versioning, or use the "overwrite" mode when adding or updating translations.

9.2.8 Documentation Errata

This section describes known errors and omissions in OracleAS Portal documentation:

- [Section 9.2.8.1, "Documentation Errors"](#)
- [Section 9.2.8.2, "Additional Documentation"](#)

9.2.8.1 Documentation Errors

This section describes known errors in OracleAS Portal documentation. It includes the following topics:

- [Section 9.2.8.1.1, "Editing Item/Portlet Properties"](#)
- [Section 9.2.8.1.2, "Editing Pending Items"](#)
- [Section 9.2.8.1.3, "Referencing the Current Version of Images"](#)
- [Section 9.2.8.1.4, "Working in List View"](#)
- [Section 9.2.8.1.5, "Unpublished Items Section Documented Incorrectly"](#)
- [Section 9.2.8.1.6, "Item Level Security and Page Caching"](#)
- [Section 9.2.8.1.7, "User Profile Help Incorrect"](#)
- [Section 9.2.8.1.8, "Defining a Display Style for Results from a Custom Search"](#)
- [Section 9.2.8.1.9, "Applying Background Color or Image to Page Portlets"](#)
- [Section 9.2.8.1.10, "Registering JSR Portlets"](#)
- [Section 9.2.8.1.11, "Corporate Page Groups No Longer Installed"](#)
- [Section 9.2.8.1.12, "Exposing Your Application as a Web Service"](#)
- [Section 9.2.8.1.13, "Changes Required in the Steps to Configure Security in OracleAS Portal"](#)
- [Section 9.2.8.1.14, "Portal Upgrade Error and Warning Messages Should Be Prefixed with WWU-"](#)

9.2.8.1.1 Editing Item/Portlet Properties The online help states that clicking the **Edit** icon enables you to edit the properties of the item or portlet. While this is true for items, clicking this icon next to a portlet takes you to the **Edit Defaults** page. To edit the portlet instance attributes (such as display name), click the **Actions** icon, then click the **Edit Portlet Instance** link.

9.2.8.1.2 Editing Pending Items Online help for **Pending Items: Preview** ([cawkpend.htm](#)) incorrectly states that the submitter can continue to edit a pending item if it has not yet been approved by the first approver in the approval process.

9.2.8.1.3 Referencing the Current Version of Images Image attributes can reference an uploaded source image. The documentation currently states:

To reuse an image that has been uploaded to OracleAS Portal, enter its internal name (not file name) without a path in this field, for example, enter 1645.GIF.

If you are versioning the referenced image item, and you use the internal file name in the reference (for example, 1645.gif), then the reference does not use a new, current version of the image if one is created. The image reference continues to show the original version. For example:

1. In an image attribute, reference an image item by its internal file name, for example, 1645.gif.
2. Update the image item and create a new version. The new version is given a new internal file name (for example, 1705.gif).
3. The image attribute still refers to 1645.gif, it has not been updated to refer to the new version of the image.

Therefore, only use the internal file name if you are *not* using versioning, or if you want the reference to always point to the original version, even if it is no longer the current version.

If you are using versioning and you always want to show the current version, then use the durable link to the image item instead of the internal file name. The durable link always picks up the latest version of the image. So, instead of entering 1645.gif, enter:

```
/pls/<DAD>/url/item/<GUID>
```

This is the relative URL format of a durable link. For example:

```
/pls/portal/url/ITEM/A47D41ECA23648A9E030007F0100118A
```

Relative URLs should always be used in case the host or domain name changes, or the content is exported to another site. For more information on durable URLs, refer to section "Understanding Page and Item URLs" in *Oracle Application Server Portal User's Guide*.

9.2.8.1.4 Working in List View List View functionality is documented in the online help topic **Page Edit Mode: List View** (pobpglst.htm). Some information in this topic is incorrect:

Button: Actions List - Options *Enable ILS* and *Disable ILS* are not available.

Button: Find - The search is *not* case-sensitive.

Subitems - The online help states that the List View does not display sub-items. This is correct, however, sub-items will be listed in search results if they meet the search criteria.

Also, note that in List View, pages based on templates do not show any tabs or items belonging to the template. You must click the **Edit Template** link to see tabs and items on a template. Therefore, when editing the page in List View, you cannot add items to tabs that are inherited from the template. Likewise, if items are added to these tabs when editing the page using another edit view (for example, Graphical View), you do not see these items in List View.

If you are using Netscape 4.8, then you may notice that version information is incorrectly displayed under the **Description** column. This is not a problem in Internet Explorer.

9.2.8.1.5 Unpublished Items Section Documented Incorrectly Online help for the Edit Page Group Items tab (`sbrsmit.htm`) incorrectly refers to the **Expired and Deleted Items** section and the **Display Expired and Deleted Items** and **Retain Expired and Deleted Items** check boxes. These should be, respectively, the **Unpublished Items** section and the **Display Unpublished Items In Edit Mode** and **Retain Deleted Items** check boxes. Refer to the text on the page itself for details on how to use these check boxes.

9.2.8.1.6 Item Level Security and Page Caching The online help incorrectly states that when item-level security (ILS) is enabled, page caching is automatically disabled. Page caching is not disabled when ILS is enabled.

9.2.8.1.7 User Profile Help Incorrect Online help for the **Edit Portal User Profile** tabs, **Preferences** (`secumed1.htm`) and **Privileges** (`secgmed3.htm`), incorrectly states that there are **Reset to Defaults** buttons on these pages. This option is not available.

9.2.8.1.8 Defining a Display Style for Results from a Custom Search Online help for **Edit Defaults: Custom Search - Results Display** page (`sbrsres.htm`) incorrectly states that style and attribute settings apply only to *items* returned in search results. The **Style** and **Attribute** settings (section **Which style and attributes should be used to render the search results?**) apply to both items and pages.

9.2.8.1.9 Applying Background Color or Image to Page Portlets If you want page portlets (including navigation pages) to display a background color or background image, then follow these steps:

1. Ensure that the navigation page uses its own style when published as a portlet, that is, do not select **Use Style Of Page On Which Portlet Is Placed** in the page properties.
2. In the style for the container page (the page containing the portlet), set **Portlet Body Color** to null (no value). This step is missing from the documentation.

9.2.8.1.10 Registering JSR Portlets The *Oracle Application Server Portal Configuration Guide* provides instructions on how to register a JSR 168 portlet in a local instance of OracleAS Portal, in section "Registering and Viewing Your Portlet". These instructions do not apply to the current production release of the product, but can be used for the Developer's Preview release until the production WSRP-enabled OracleAS Portal is released. Note that the Developer's Preview is provided for development purposes only, and should not be used for production systems.

9.2.8.1.11 Corporate Page Groups No Longer Installed In some sections of the documentation, you may find reference to the Corporate Pages page group. This page group is no longer installed with OracleAS Portal and you may disregard any mention of it in the documentation. However, if you are upgrading an existing OracleAS Portal instance which contained the Corporate Pages page group, then it will not be removed by the upgrade.

9.2.8.1.12 Exposing Your Application as a Web Service Section "Exposing Your Application as a Web Service" in the *Oracle Application Server Portal Developer's Guide* has an inaccurate step and a missing step. The section should read as follows:

Before you deploy your WAR file to the Oracle Application Server, you must perform the following steps:

1. Update your `web.xml` file. These entries are required to expose your application as a Web Service as soon as it is deployed.

```
<web-app>
```

```

<description>Empty web.xml file for Web Application</description>
<session-config>
  <session-timeout>35</session-timeout>
</session-config>
<mime-mapping>
  <extension>html</extension>
  <mime-type>text/html</mime-type>
</mime-mapping>
<mime-mapping>
  <extension>txt</extension>
  <mime-type>text/plain</mime-type>
</mime-mapping>
<filter>
  <filter-name>portletfilter</filter-name>
  <filter-class>oracle.webdb.wsrp.server.ContextFilter</filter-class>
</filter>
<filter-mapping>
  <filter-name>portletfilter</filter-name>
  <servlet-name>portletjaxrpc</servlet-name>
</filter-mapping>
<filter-mapping>
  <filter-name>portletfilter</filter-name>
  <servlet-name>portletresource</servlet-name>
</filter-mapping>
<servlet>
  <servlet-name>portletdeploy</servlet-name>
<servlet-class>oracle.webdb.wsrp.server.deploy.PortletDeployServlet</servlet-cl
ass>
  <load-on-startup>1</load-on-startup>
</servlet>
<servlet>
  <servlet-name>portletjaxrpc</servlet-name>
  <servlet-class>com.sun.xml.rpc.server.http.JAXRPCServlet</servlet-class>
  <init-param>
    <param-name>configuration.file</param-name>
    <param-value>/WEB-INF/WSRPService_Config.properties</param-value>
  </init-param>
</servlet>
<servlet>
  <servlet-name>portletresource</servlet-name>
  <servlet-class>oracle.webdb.wsrp.server.ResourceServlet</servlet-class>
</servlet>
<servlet-mapping>
  <servlet-name>portletjaxrpc</servlet-name>
  <url-pattern>/portlets*</url-pattern>
</servlet-mapping>
<servlet-mapping>
  <servlet-name>portletresource</servlet-name>
  <url-pattern>/portletresource*</url-pattern>
</servlet-mapping>
</web-app>

```

2. When adding a custom JPS producer to the Oracle Application Server OC4J instance, you also must add the following library paths in your application.xml file:

```

<library path="$ORACLE_HOME/portal/jlib/commons-logging.jar"/>
<library path="$ORACLE_HOME/portal/jlib/dom4j.jar"/>
<library path="$ORACLE_HOME/portal/jlib/jaxrpc-api.jar"/>
<library path="$ORACLE_HOME/portal/jlib/jaxrpc-ri-patched.jar"/>

```

```
<library path="$ORACLE_HOME/portal/jlib/namespace.jar"/>
<library path="$ORACLE_HOME/portal/jlib/relaxngDatatype.jar"/>
<library path="$ORACLE_HOME/portal/jlib/ptlshare.jar"/>
<library path="$ORACLE_HOME/portal/jlib/saa-j-api.jar"/>
<library path="$ORACLE_HOME/portal/jlib/saa-j-ri.jar"/>
<library path="$ORACLE_HOME/portal/jlib/wsrp-common.jar"/>
<library path="$ORACLE_HOME/portal/jlib/wsrp-container.jar"/>
<library path="$ORACLE_HOME/portal/jlib/oracle-portlet-tags.jar"/>
<library path="$ORACLE_HOME/lib/xml.jar"/>
<library path="$ORACLE_HOME/lib/xmlmsg.jar"/>
<library path="$ORACLE_HOME/lib/xmlparserv2.jar"/>
<library path="$ORACLE_HOME/portal/jlib/xsdl.jar"/>
```

9.2.8.1.13 Changes Required in the Steps to Configure Security in OracleAS Portal The chapter titled, "Securing OracleAS Portal" in the *Oracle Application Server Portal Configuration Guide* has the following known errors:

- Step 1 in subsection "Configuring SSL to OracleAS Single Sign-On Using SSLConfigTool" under Section 6.3.2.1.2, "SSL to OracleAS Single Sign-On", currently states the following:
Enter n when prompted by the script to configure your site to accept browser requests using the SSL protocol.

This task must not be performed in step 1, as you will not be prompted for any input when you use the `-config_w_default` option. This task must be performed in step 3 in the same procedure where you run `SSLConfigTool` in the middle-tier Oracle home.

- Step 2 in subsection "Configuring SSL to OracleAS Web Cache Using SSLConfigTool" under Section 6.3.2.1.3, "SSL to OracleAS Web Cache", currently states the command to run `SSLConfigTool` as shown:

```
SSLConfigTool.bat -config_w_default -opwd <orcladmin_pwd>
```

However, the command must be used as follows:

```
SSLConfigTool.bat -config_w_prompt -ptl_inv_pwd <ptl_inv_pwd> -opwd <orcladmin_pwd>
```

- Step 2 in subsection "Configuring SSL Throughout OracleAS Portal Using SSLConfigTool" under Section 6.3.2.1.4, "SSL Throughout OracleAS Portal" currently states the following:

Enter the following values when prompted by the script:

- *y, when prompted to configure your site to accept browser requests using the SSL protocol.*
- *y, when asked if your Oracle HTTP Server accepts requests in SSL protocol.*

This task must not be performed in step 2, as you will not be prompted for any input when you use the `-config_w_default` option. This task must be performed in step 3 where you run `SSLConfigTool` in the middle-tier Oracle home.

- The following step is missing in subsection "Configuring SSL to OracleAS Web Cache Using SSLConfigTool" under Section 6.3.2.1.3, "SSL to OracleAS Web Cache":

Enable SSL on the OracleAS Infrastructure that has Identity Management installed and then run `SSLConfigTool` in the infrastructure Oracle home, as shown in the following example, for Windows:

```
SSLConfigTool.bat -config_w_default -opwd <orcladmin_pwd>
```

Where:

- `config_w_default` is used to run the tool in silent mode using the values specified in the `portlist.ini` and `ias.properties` files.
- `opwd` is the Oracle administrator password. If no password is specified, then you will be prompted to enter the password.

Perform this step after step 1.

9.2.8.1.14 Portal Upgrade Error and Warning Messages Should Be Prefixed with WWU- The Portal upgrade error and warning messages described in Chapter 6, "UPG-00001 to UPG-26001" of the *Oracle Application Server Portal Error Messages Guide 10g Release 2 (10.1.2)* are incorrectly prefixed with UPG-. These error and warning messages should be prefixed with WWU-.

9.2.8.2 Additional Documentation

This section describes known omissions and additions to the OracleAS Portal documentation. It includes the following topics:

- [Section 9.2.8.2.1, "Inaccurate Data in Log Registry Records"](#)
- [Section 9.2.8.2.2, "Expired Items Remain Visible in WebDAV Clients"](#)
- [Section 9.2.8.2.3, "Enhanced Rich Text Editor"](#)
- [Section 9.2.8.2.4, "Using Oracle Drive with OracleAS Portal"](#)
- [Section 9.2.8.2.5, "Unable to Delete Tabs on Templates"](#)
- [Section 9.2.8.2.6, "Error Removing Subscriber from Virtual Private Portal"](#)
- [Section 9.2.8.2.7, "Unable to Monitor WSRP Providers in This Release"](#)
- [Section 9.2.8.2.8, "Location of the ptlwsrp_data.sql Script"](#)

9.2.8.2.1 Inaccurate Data in Log Registry Records Online help describing Log Registry records ([wvlogadm.htm](#)) lists the set of actions that are logged. Since the introduction of OracleAS Web Cache, some of the actions logged in OracleAS Portal Activity Log tables have become inaccurate. Specifically, these actions are *View*, *Execute*, *Show*, and *Perform*. However, since all other actions logged are still accurate, the Activity Log tables and views still remain in the OracleAS Metadata Repository.

9.2.8.2.2 Expired Items Remain Visible in WebDAV Clients Expired items continue to be visible in WebDAV clients until they are permanently removed from the database during a system purge.

9.2.8.2.3 Enhanced Rich Text Editor The Rich Text Editor (WYSIWIG editor) that is used in OracleAS Portal to apply formatting to text items is described in a Technical Note *OracleAS Portal 9.0.4.1 – Enhanced Rich Text Editor* on OTN at:

http://www.oracle.com/technology/products/ias/portal/content_management.html

9.2.8.2.4 Using Oracle Drive with OracleAS Portal OracleAS Portal leverages the features of Oracle Drive to manage and publish portal content directly from the Windows desktop.

Oracle Drive is a powerful WebDAV client. It maps the Oracle Portal Repository as a drive and enables you to perform desktop authoring and publishing, as well as portal-specific metadata attribution, from the Windows desktop. For further information, refer to the technical note, *How to Install and Configure the Oracle Drive on OTN* at:

http://www.oracle.com/technology/products/ias/portal/content_management_10gr2.html

9.2.8.2.5 Unable to Delete Tabs on Templates You cannot delete a tab on a template (even with Manage Template privileges), if other users have placed content on the tab, in pages that are based on this template.

9.2.8.2.6 Error Removing Subscriber from Virtual Private Portal The following error can display when you use the `rmsub.csh` script to remove a subscriber from a Virtual Private Portal (VPP):

```
ERROR: Interface Version Specified does not match Profile Interface Version - 1.1
Could not delete Provisioning Profile.
```

This error does not impact the use of VPP.

9.2.8.2.7 Unable to Monitor WSRP Providers in This Release Oracle Enterprise Manager 10g Help describes how to monitor Web providers, database providers, and WSRP producers registered with OracleAS Portal. Support for WSRP providers will be provided in a future release. It is not possible to monitor WSRP providers in 10g Release 2 (10.1.2).

9.2.8.2.8 Location of the `ptlwsrp_data.sql` Script Section "Using the `ptlwsrp_data.sql` Script to Create the WSRP Portlet Preference Store" in Appendix C of the *Oracle Application Server Portal Configuration Guide* mentions the use of the script `ptlwsrp_data.sql`. It does not mention that this script first needs to be downloaded from Portal Center:

<http://portalcenter.oracle.com>

Oracle Ultra Search

This chapter describes issues associated with Oracle Ultra Search. It includes the following topics:

- [Section 10.1, "Upgrade Issues and Workarounds"](#)
- [Section 10.2, "General Issues and Workarounds"](#)
- [Section 10.3, "Documentation Errata"](#)

10.1 Upgrade Issues and Workarounds

This section describes upgrade issues and their workarounds for Oracle Ultra Search. It includes the following topics:

- [Section 10.1.1, "Upgrade Fails When Upgrading to 10.1.2"](#)

10.1.1 Upgrade Fails When Upgrading to 10.1.2

When upgrading Oracle Ultra Search to Oracle Application Server 10g 10.1.2, the upgrade status for Oracle Ultra Search may show `Failed`. This is because the validation package (`wkvalid.sql`) is not installed in the Oracle Application Server 10g 10.1.2 seed database. This will be fixed for 10.1.0.4 database.

The workaround is to first check whether the Oracle Ultra Search status is indeed invalid.

Login as SYS (for example, `sqlplus "sys/<SYS PASSWORD> as sysdba"`)

```
SQL> SELECT comp_id, status FROM sys.db_registry WHERE comp_id = 'WK'
/
```

You should see something like the following:

COMP_ID	STATUS
WK	INVALID

If the Oracle Ultra Search status is invalid, then do the following to verify if the upgrade was indeed successful.

Download `wkvalid.sql` from the following site

<http://www.oracle.com/technology/products/ultrasearch/index.html>

Connect to database as SYS and install `wkvalid.sql`.

```
> sqlplus "sys/<SYS PASSWORD> as sysdba"
```

```
@wkvalid.sql
```

Connect to the database as *SYS*, and run the Oracle Ultra Search validation package. This package checks the Oracle Ultra Search status and updates it accordingly.

```
> sqlplus "sys/<SYS PASSWORD> as sysdba"
SQL> exec sys.validate_wk
```

PL/SQL procedure successfully completed.

Check the Oracle Ultra Search status.

```
> sqlplus "sys/<SYS PASSWORD> as sysdba"
SQL> SELECT comp_id, status FROM sys.dba_registry WHERE comp_id = 'WK'
2 /
```

You should see the status as *VALID*, if the upgrade was successful.

COMP_ID	STATUS
-----	-----
WK	VALID

10.2 General Issues and Workarounds

This section describes general issues and their workarounds for Oracle Ultra Search. It includes the following topics:

- [Section 10.2.1, "Creating or Editing Oracle Ultra Search ACLs Fails in Non-OracleAS Single Sign-On Mode"](#)

10.2.1 Creating or Editing Oracle Ultra Search ACLs Fails in Non-OracleAS Single Sign-On Mode

An Oracle Ultra Search Administrator can log in as a database administrator or an OracleAS Single Sign-On user who has been granted administrative privileges. In this release, when logging in as a database administrator, under certain circumstances, the administrator will not be able to create or edit administrator-specified ACLs for a data source. An "Access Denied" error is encountered when attempting to create or modify ACLs.

The workaround is to always log in as an OracleAS Single Sign-On user in order to create/modify ACLs for a data source.

10.3 Documentation Errata

This section describes documentation errata for the *Oracle Ultra Search Administrator's Guide*. It includes the following topic:

- [Section 10.3.1, "Adding and Deleting Subscribers"](#)

10.3.1 Adding and Deleting Subscribers

The "Configuring Oracle Ultra Search in a Hosted Environment" section says to use the `usca.sh` and `usca.bat` scripts to add and delete subscribers.

Instead, use the following command to add subscribers:

```
java -jar ORACLE_HOME/ultrasearch/lib/usca.jar action=add_subscriber
oh=ORACLE_HOME oid_user_dn="cn=orcladmin" oid_passwd=<oid_user_dn's password>
oid_subscriber_dn=<subscriber's DN> (e.g., "dc=uk,dc=oracle,dc=com")>
```

```
logfile=<log file path> db_sn=<database service name
```

Use the following command to delete subscribers:

```
java -jar $ORACLE_HOME/ultrasearch/lib/usca.jar action=delete_subscriber  
oh=ORACLE_HOME oid_user_dn="cn=orcladmin" oid_passwd=<oid_user_dn's password>  
oid_subscriber_dn=<subscriber's DN (e.g., "dc=uk,dc=oracle,dc=com")>  
logfile=<log file path> db_sn=<database service name
```

Oracle Application Server Wireless

This chapter describes issues with Oracle Application Server Wireless (OracleAS Wireless). It includes the following topics:

- [Section 11.1, "General Issues"](#)
- [Section 11.2, "Configuration Issues and Workarounds"](#)

11.1 General Issues

This section describes general issues encountered in OracleAS Wireless. It includes the following topics:

- [Section 11.1.1, "Unable to Test Locally Deployed JSPs"](#)
- [Section 11.1.2, "EDGE_CREATE Script Errors"](#)
- [Section 11.1.3, "Database Lock Hangs STREAMS Dispatcher"](#)
- [Section 11.1.4, "OracleAS Wireless Patch Required after XDK Patch is Applied"](#)
- [Section 11.1.5, "Broken Icons in Wireless Device Portal Homepage"](#)
- [Section 11.1.6, "HDML Error When Using Expense Demo Application"](#)

11.1.1 Unable to Test Locally Deployed JSPs

Users reported being unable to test local JSPs using the 10.1.2.1 version of the WDK. In order to test locally deployed JSPs, follow these steps:

1. Modify the `ORACLE_HOME\j2ee\OC4J_Wireless\applications\wdk\wdk-web\WEB-INF\web.xml` file by removing the xml comments (in lines 6 and 31 in this example):

```

1.    <!-- For Transcoder -->
2.    <filter-mapping>
3.        <filter-name>SdkTranscoder</filter-name>
4.        <servlet-name>SdkContentRetriever</servlet-name>
5.    </filter-mapping>
6.    <!--
7.    <filter-mapping>
8.        <filter-name>SdkTranscoder</filter-name>
9.        <url-pattern>*.jsp</url-pattern>
10.    </filter-mapping>
11.    <filter-mapping>
12.        <filter-name>SdkTranscoder</filter-name>
13.        <url-pattern>*.mxml</url-pattern>

```

```
14.     </filter-mapping>
15.     <filter-mapping>
16.         <filter-name>SdkTranscoder</filter-name>
17.         <url-pattern>*.xhtml</url-pattern>
18.     </filter-mapping>
19.     <filter-mapping>
20.         <filter-name>SdkTranscoder</filter-name>
21.         <url-pattern>*.html</url-pattern>
22.     </filter-mapping>
23.     <filter-mapping>
24.         <filter-name>SdkTranscoder</filter-name>
25.         <url-pattern>*.htm</url-pattern>
26.     </filter-mapping>
27.     <filter-mapping>
28.         <filter-name>SdkTranscoder</filter-name>
29.         <url-pattern>*.xml</url-pattern>
30.     </filter-mapping>
31. -->
```

2. Restart the OC4J_Wireless process.

11.1.2 EDGE_CREATE Script Errors

Some users have reported receiving an error when trying to create the edge schema on an Oracle Application Server 10g installation. This is because the `dbms_aq` package is often locked by other sessions when one tries to create the edge user (using the `create_edge_user.sql` script). When trying to create the edge schema (after connecting as `edge/<password>@<db name>` and running `edg_create_streams.sql`), table and queue creation fails.

To fix this problem:

1. Unlock the package. This is a database administrator function. The session locking the package must relinquish the lock. This may require restarting the entire database instance. It ensures that no session is holding a lock on the `dbms_aq` package.
2. Explicitly give execute privilege to the edge user on the `dbms_aq` package:
 - a. Log in as *system*.
 - b. Execute `SQL> grant execute on dbms_aq to edge;`
3. Connect as `edge/<password>@<db name>` and run `edg_create_streams.sql`, again.

11.1.3 Database Lock Hangs STREAMS Dispatcher

The STREAMS dispatcher runs as a database job. If your PL/SQL development activities require you to constantly recompile packages, a database lock can hang the STREAMS dispatcher. Generally, you can restart the dispatcher by executing:

```
exec edg_util.deschedule_job;
```

To check whether or not the job exits gracefully, check the `edg_jobs` table. Run the following query:

```
select component_name, status from edg_jobs;
```

If the job has exited gracefully, this query will return no rows. If this job is in the process of exiting, the status will be *Stopping*. It may take up to 30-40 seconds for the

job to finish completely. If this query continues to return a status of *Stopping*, the dispatch job has frozen. To correct this, first clear this row from the table. Execute:

```
delete from edg_jobs where component_name = 'EdgeDispatchJob';
```

Next, restart the database. Once the database is restarted, restart (or reschedule) the job. Do this by executing:

```
exec edg_util.schedule_job;
```

The job will restart. To verify, use this query:

```
select component_name, status from edg_jobs;
```

This should return a status of *Started*.

11.1.4 OracleAS Wireless Patch Required after XDK Patch is Applied

If you are using Apache Axis and the wireless feature in Oracle Application Server 10.1.2, and you have already applied a Release 10.1.2 XDK patch, you must download an OracleAS Wireless one-off patch from Metalink.

The OracleAS Wireless one-off patch fixes a problem introduced by the XDK fix. If you do not apply the OracleAS Wireless patch, logging in from the voice channel will fail.

11.1.5 Broken Icons in Wireless Device Portal Homepage

Icons on the OracleAS Wireless Device Portal Home page for an upgraded instance in SSL mode are broken. This is because `Mod_rewrite` of the icons in an SSL configuration does not work.

To fix the problem, you must enable *rewrite* in SSL mode by adding the following entries to the SSL Virtual Host configuration:

```
RewriteEngine on
RewriteOptions inherit
```

Here is a sample entry:

```
<VirtualHost _default_:4444>
# General setup for the virtual host
DocumentRoot "/Portal1012/Apache/Apache\htdocs"
@ ServerName iwinrea05.us.oracle.com
ServerAdmin you@your.address
ErrorLog "|/Portal1012/Apache/Apache/bin/rotatelog logs/error_log 43200"
TransferLog "|/Portal1012/Apache/Apache/bin/rotatelog logs/access_log 43200"
Port 443
```

11.1.6 HDML Error When Using Expense Demo Application

A problem has been reported by users running the Expense Demo application on HDML-enabled devices. An error may appear when one attempts to click the **Approve** or **Reject** button using an HDML-enabled device to access the built-in Expense Demo application in Device Portal. Users should avoid using the Approve/Reject functionality for this demo when using HDML-enabled devices.

11.2 Configuration Issues and Workarounds

This section describes OracleAS Wireless configuration issues and workarounds. It includes the following topic:

- [Section 11.2.1, "Migrate Account Numbers and PINs after Upgrade"](#)
- [Section 11.2.2, "SDO_INDEX_METADATA NULL FETCH Error"](#)
- [Section 11.2.3, "Updated Transformer Stylesheets Patch Required after Upgrade"](#)
- [Section 11.2.4, "OracleAS Metadata Repository Creation Assistant 9.2.0.6 Error with Wireless 10.1.2"](#)
- [Section 11.2.5, "Configuration Assistant Error Message"](#)
- [Section 11.2.6, "IBM WebSphere Required Patch Version 6.0.2"](#)

11.2.1 Migrate Account Numbers and PINs after Upgrade

If you upgrade Oracle Application Server Wireless from a previous release (9.0.2.x or 9.0.4.x), you must migrate your user account numbers and PINs to OID. Failure to do so breaks the voice login.

11.2.2 SDO_INDEX_METADATA NULL FETCH Error

If you upgrade Oracle Application Server Wireless from a previous release (9.0.2.x or 9.0.4.x), you must complete the following workaround to avoid the SDO_INDEX_METADATA NULL FETCH error:

1. Connect as SYS.
2. Run the following SQL statement:

```
alter session set current_schema=MDSYS;
update sdo_index_metadata_table set SDO_INDEX_STATUS =
'VALID' where SDO_INDEX_STATUS is NULL;

update sdo_index_metadata_table set SDO_INDEX_DIMS = 2
where SDO_INDEX_GEODETIC = 'TRUE' and SDO_RTREE_DIMENSIONALITY=3;
```

11.2.3 Updated Transformer Stylesheets Patch Required after Upgrade

If you are upgrading from Release 9.0.2 to Release 10g (9.0.4), and then to Release 10.1.2, you must download the updated transformer stylesheets from the Oracle Mobile Tech Center (<http://www.oracle.com/technology/products/iaswe/devices/index.html>) and apply the stylesheets to the instance. Detailed instructions are included as part of the transformer stylesheets bundle. If you do not apply this update, service names rendered on the devices will be prefixed with a colon and an underscore (:_).

11.2.4 OracleAS Metadata Repository Creation Assistant 9.2.0.6 Error with Wireless 10.1.2

The OracleAS Metadata Repository Creation Assistant tool may fail to load OracleAS Wireless schemas into 9.0.2.6 databases. To avoid this problem, ensure that you increase the max_enabled_roles parameter to 100 before attempting a RepCA installation with a 9.2.0.6 RAC database.

First, check the current max_enabled_roles parameter value:

1. Connect to the database as sysdba.
2. Issue the command:

```
SQL> select name,value from $parameter where name='max_enabled_roles';
```


3. If the value is lower than 100, connect to the RAC database as sysdba and issue the following command:

```
SQL> alter system set max_enabled_roles=100 scope=spfile;
```

4. Restart the database to use the new value.

11.2.5 Configuration Assistant Error Message

You may see Configuration Assistant error messages in *ORACLE_HOME/wireless/logs/upgrade_CA.out\wireless\logs\upgrade_CA.out* similar to this:

```
SQL Exception: java.sql.BatchUpdateException: error occurred during batching:  
ORA-01430: column being added already exists in table
```

This message can be safely ignored if your 10.1.2 instance is a fresh instance, that is, it has not been upgraded from 9.0.2, 9.0.4, or any other previous release of Oracle Application Server.

11.2.6 IBM WebSphere Required Patch Version 6.0.2

If you are using IBM WebSphere Application Server, install the following patch:

<http://www-1.ibm.com/support/docview.wss?rs=180&uid=swg24009813>

Doing so will help you avoid problems when using Oracle Industrial Telnet Server and (potentially) other products.

Oracle BPEL Process Manager

This chapter describes issues associated with Oracle BPEL Process Manager. It includes the following topics:

- [Section 12.1, "Installation Issues and Workarounds"](#)
- [Section 12.2, "General Issues and Workarounds"](#)
- [Section 12.3, "Modeling and Design Time Issues and Workarounds"](#)
- [Section 12.4, "Workflow and Worklist Issues and Workarounds"](#)
- [Section 12.5, "Transformation Issues and Workarounds"](#)
- [Section 12.6, "XPath Expression Builder Issues and Workarounds"](#)
- [Section 12.7, "Oracle Application Server Adapter for Files/FTP Issues and Workarounds"](#)
- [Section 12.8, "Oracle Application Server Adapter for AQ Issues and Workarounds"](#)
- [Section 12.9, "Oracle Application Server Adapter for Databases Issues and Workarounds"](#)
- [Section 12.10, "Oracle Application Server Adapter for JMS Issues and Workarounds"](#)
- [Section 12.11, "Oracle Application Server Adapter for Oracle Applications Issues and Workarounds"](#)
- [Section 12.12, "General Adapter and Adapter Partner Link Issues and Workarounds"](#)
- [Section 12.13, "Sensor Issues and Workarounds"](#)
- [Section 12.14, "Oracle BPEL Console and Oracle BPEL Server Issues and Workarounds"](#)
- [Section 12.15, "Oracle BPEL Portlets Issues and Workarounds"](#)
- [Section 12.16, "High Availability Issues and Workarounds"](#)
- [Section 12.17, "Globalization/Multibyte Character Issues and Workarounds"](#)
- [Section 12.18, "Oracle BPEL Process Manager Samples Issues and Workarounds"](#)
- [Section 12.19, "JBoss Issues and Workarounds"](#)
- [Section 12.20, "BEA WebLogic Issues and Workarounds"](#)
- [Section 12.21, "Microsoft SQL Server Issues and Workarounds"](#)
- [Section 12.22, "Documentation Errata"](#)

Note: JDeveloper BPEL Designer is not supported on IBM zSeries Based Linux. You can ignore sections pertaining to JDeveloper BPEL Designer because they are not applicable to the IBM zSeries Based Linux platform.

12.1 Installation Issues and Workarounds

This section describes the following issues and workarounds:

- [Section 12.1.1, "Message to Ignore During Oracle BPEL Process Manager for OracleAS Middle Tier Installation"](#)
- [Section 12.1.2, "Migrating from Previous Releases of Oracle BPEL Process Manager"](#)
- [Section 12.1.3, "Adding Oracle BPEL Process Manager for OracleAS Middle Tier Memory Settings"](#)
- [Section 12.1.4, "Installing Oracle Java Virtual Machine on IBM zSeries Based Linux"](#)

12.1.1 Message to Ignore During Oracle BPEL Process Manager for OracleAS Middle Tier Installation

You can safely ignore the following message that appears during both Oracle BPEL Process Manager for OracleAS Middle Tier installation and also in the postinstallation log files:

```
Patch 4869010 not found ...  
WARNING: Patch 4869010 is MANDATORY and must be applied ...
```

12.1.2 Migrating from Previous Releases of Oracle BPEL Process Manager

To migrate from Oracle BPEL Process Manager release 10.1.2.0.0 to release 10.1.2.0.2, download Patch 5041642 from *OracleMetaLink*:

<http://metalink.oracle.com>

This patch includes documentation and a SQL*Plus migration script that enables you to migrate data from release 10.1.2.0.0 to 10.1.2.0.2.

12.1.3 Adding Oracle BPEL Process Manager for OracleAS Middle Tier Memory Settings

After installing Oracle BPEL Process Manager for OracleAS Middle Tier, ensure that you include the following memory settings in the OC4J_BPEL process type section of the *Oracle_Home\opmn\conf\opmn.xml* file:

```
<process-type id="OC4J_BPEL" module-id="OC4J"  
  <module-data><<category id="start-parameters">  
    <data id="java-options" value="...  
      . . .  
      . . .  
      -Xms512m -Xmx512m -Xmn300m  
      -XX:MaxPermSize=80m .../>
```

12.1.4 Installing Oracle Java Virtual Machine on IBM zSeries Based Linux

If you want to use Oracle JDeveloper's CodeCoach and Profiling features, you must install Oracle Client Java Virtual Machine (OJVM).

The `InstallOJVM` script installs OJVM in the specified JDK directory. Once installed, OJVM is the default virtual machine for every new project created in JDeveloper BPEL Designer for the specified JDK.

1. Go to `$ORACLE_HOME/integration/jdev/ojvm_linux_x86`.
2. Run `installOJVM`, and specify the JDK root directory. For example:

```
InstallOJVM $/OraBPELPM/integration/jdev/jdk
```

12.2 General Issues and Workarounds

This section describes the following issues and workarounds:

- [Section 12.2.1, "Error with opmnctl stopall to Ignore"](#)
- [Section 12.2.2, "Undeploying and Redeploying the OC4J_BPEL System Component Through Oracle Enterprise Manager Is Not Supported"](#)
- [Section 12.2.3, "JDeveloper BPEL Designer Limitations on Linux"](#)
- [Section 12.2.4, "JDeveloper BPEL Designer Limitations on Solaris"](#)
- [Section 12.2.5, "WSDL Exception Error When Trying to Create a Stub to Use a Web Service"](#)
- [Section 12.2.6, "Deploying Oracle JDeveloper-Created Web Services to Oracle BPEL Process Manager OC4J"](#)

12.2.1 Error with opmnctl stopall to Ignore

The `OPMNCTL STOPALL` command intermittently fails to perform a graceful shutdown. When this occurs, the process is stopped, but an error similar to the following appears.

```
/opmn/bin/opmnctl stopall
opmnctl: stopping opmn and all managed processes...
=====
opmn id=isunbox28:6200
      2 of 3 processes stopped.
@ ias-instance id=iasmid.isunbox28.us.oracle.com
+++++
-----
ias-component/process-type/process-set:
      OraBPEL/OC4J_BPEL/default_island
Error
--> Process (pid=9121)
      time out while waiting for a managed process to stop
      Log:

/private/jsmith/midtier/opmn/logs/OraBPEL-OC4J_BPEL~default_island~1
opmnctl: graceful stop of processes failed, trying
forceful shutdown...
```

12.2.2 Undeploying and Redeploying the OC4J_BPEL System Component Through Oracle Enterprise Manager Is Not Supported

If you undeploy the OC4J_BPEL system component through Oracle Enterprise Manager, redeploy it, and then restart OC4J_BPEL, the application cannot be accessed.

Caution: Oracle recommends that you do not undeploy and redeploy the OC4J_BPEL system component of Oracle BPEL Process Manager.

12.2.3 JDeveloper BPEL Designer Limitations on Linux

Right-clicking the mouse button in the **Diagram View** window and **Structure** window of JDeveloper BPEL Designer does not display the menu on Linux.

See Also: *Oracle BPEL Process Manager Installation Guide* for a list of supported operating systems

12.2.4 JDeveloper BPEL Designer Limitations on Solaris

Right-clicking the mouse button in the **Diagram View** window and **Structure** window of JDeveloper BPEL Designer does not display the menu on Solaris. JDeveloper BPEL Designer is not officially supported on Solaris.

See Also: *Oracle BPEL Process Manager Installation Guide* for a list of supported operating systems

12.2.5 WSDL Exception Error When Trying to Create a Stub to Use a Web Service

JDeveloper BPEL Designer enables you to automatically create a stub to use a Web service. Once you have generated the stub using the Web Service Stub/Skeleton wizard, you can call the methods (proxies to the web service) in your application. When you attempt to validate/parse the WSDL file, you receive a validation error similar to the following:

```
WSDL Validation failed with the following exceptions
@ Schema type not found. QNAME (http://schema.xmlsoap.org/soap/encoding/,
base64)
```

Similar problems occur with the WSDL for an asynchronous BPEL process generated by JDeveloper BPEL Designer.

As a workaround, use the RMI client interface for BPEL.

See Also: *Oracle_*
Home\integration\orabpel\samples\tutorials\102.Invoke
ingProcesses for an example of the RMI client interface

12.2.6 Deploying Oracle JDeveloper-Created Web Services to Oracle BPEL Process Manager OC4J

When Oracle BPEL Server attempts to invoke the OC4J service, the OC4J servlet dispatcher invokes the Oracle BPEL Console WAR file instead of the Web service EAR file. This causes the following error during run time:

```
BPEL Fault
http://schemas.oracle.com/bpel/extension}bindingFault{summary=Cannot lookup
BPEL domain.
```

The BPEL domain "MyWebService1" cannot be found; the domain may not have initialized properly.
Please verify that the BPEL domain loader has a valid set of initialization properties in the application properties file.

There are two possible workarounds to this error:

- If the *Oracle_*
Home\integration\orabpel\system\config\collaxa-config.xml file includes the following settings:

```
- <property id="soap-server-url">
  <name>BPEL soap server URL</name>
  @ <value>http://servername.localdomain:9700</value>
```

Replace `http://servername.localdomain:9700` with
`http://servername:9700`.

- Change the endpoint in the Oracle JDeveloper-created Web service to point to localhost instead of servername.

12.3 Modeling and Design Time Issues and Workarounds

This section describes the following issues and workarounds:

- [Section 12.3.1, "No Deployment Time Validation Logic with obant"](#)
- [Section 12.3.2, "Do Not Include Blank Spaces in Directory Paths of JDeveloper BPEL Designer Workspaces"](#)
- [Section 12.3.3, "Using Annotations in JDeveloper BPEL Designer"](#)
- [Section 12.3.4, "Internal Compilation Error When Using the CTRL and F9 Keys"](#)
- [Section 12.3.5, "Inline Dialogs Can Result in Data Loss in Some Cases"](#)
- [Section 12.3.6, "Do Not Add or Import XSD Files in a ZIP File"](#)
- [Section 12.3.7, "Cannot Select Property Aliases in project_name.wsdl File"](#)
- [Section 12.3.8, "Correlation Set Property Aliases Defined in Process WSDL Cause Problems"](#)
- [Section 12.3.9, "BPEL Processes Initiated by Partner Links Referring to Adapters"](#)
- [Section 12.3.10, "Changes Made In BPEL Designer Do Not Update Automatically"](#)
- [Section 12.3.11, "Extra Carriage Return Added When Using XML Literals"](#)
- [Section 12.3.12, "readFile Function Displays Only One Argument in XPath Expression Builder Window"](#)
- [Section 12.3.13, "Error When Selecting Message Part Elements Using Inline Schemas of a Project"](#)

12.3.1 No Deployment Time Validation Logic with obant

The `obant` utility does not validate your BPEL process during deployment. If you want to validate your process during deployment, use JDeveloper BPEL Designer to deploy your process.

12.3.2 Do Not Include Blank Spaces in Directory Paths of JDeveloper BPEL Designer Workspaces

Ensure that the directory path of a workspace does *not* include any blank spaces. For example, the following is not permitted:

```
C:\Program Files\projects\myWorkspace\Loanflow
```

Opening a project from a workspace whose directory path contains blank spaces causes problems. For example, the WSDL files do not display in the WSDL Chooser window when creating a partner link.

12.3.3 Using Annotations in JDeveloper BPEL Designer

Note the following issues when using annotations in JDeveloper BPEL Designer:

- The **Annotations** tab in activities of JDeveloper BPEL Designer does not provide a method for changing the order of annotations.

As a workaround, change the order of annotations in the **Source** view of the project's BPEL file in JDeveloper BPEL Designer.

- The otherwise branch in a switch activity does not allow you to create annotations. However, the case branch in a switch activity does provide this functionality.

12.3.4 Internal Compilation Error When Using the CTRL and F9 Keys

If you highlight a partner link in JDeveloper BPEL Designer, and press the **Ctrl** and **F9** keys, you receive the following compilation error in the **Log Window**:

```
Internal compilation error, terminated with a fatal exception
```

As a workaround, select the partner link *and* the project in the **Applications Navigator**, then press the **Ctrl** and **F9** keys. You receive no compilation errors in the **Log Window**.

12.3.5 Inline Dialogs Can Result in Data Loss in Some Cases

The **Log Window** at the bottom of JDeveloper BPEL Designer displays compilation errors. Assume that you double-click an **assign** activity error in the **Log Window**. The **assign** activity opens, and you correct the error and add additional assign copy rules. If you then right-click the error in the **Log Window** and select **Go to Source**, the **Source** view for your process displays without the **assign** activity or any of the copy rules you added.

If you perform one of the following tasks, this problem does not display so easily:

- For all new projects going forward, select **Preferences > BPEL Editor** from the **Tools** main menu and uncheck **Use inline editors**.
- For the current project only, right-click in JDeveloper BPEL Designer, select **Diagram Properties**, and uncheck **Use inline editors**.

12.3.6 Do Not Add or Import XSD Files in a ZIP File

Do not add or import XSD files in a ZIP file into a BPEL project. While JDeveloper BPEL Designer enables you to do this, and opens the XSD in read-only mode, you cannot use it within the BPEL process. JDeveloper BPEL Designer cannot parse the file because the file cannot be physically located. Always extract the XSDs from ZIP files before adding or importing them.

12.3.7 Cannot Select Property Aliases in `project_name.wsdl` File

You cannot select property aliases in the `project_name.wsdl` file. To use the property aliases in, for example, `adapters.wsdl`, manually add them.

12.3.8 Correlation Set Property Aliases Defined in Process WSDL Cause Problems

If you create correlation set property aliases in JDeveloper BPEL Designer, the entries are created in the WSDL file of the BPEL process. However, if the process does not use the default client partner link that refers to this WSDL file (for example, the receive activity is invoked by a partner link of an adapter), the correlation set is not validated at compilation time. This is because Oracle BPEL Server cannot find the WSDL file references in the `bpel.xml` file.

As a workaround, create the property aliases in a neutral WSDL file and reference this file in the `bpel.xml` file. The BPEL process uses this file at compilation time (the way properties are defined in separate WSDL files).

12.3.9 BPEL Processes Initiated by Partner Links Referring to Adapters

If the BPEL process is initiated by a partner link that refers to an adapter, you may need to import the `process_name.wsdl` file inside the partner link's WSDL file. This is so that any references to the message types inside `process_name.wsdl` can be handled during compilation.

This may be required in the following cases:

- When using correlation sets (the property alias is stored in `process_name.wsdl`)
- If any message type defined in `process_name.wsdl` is referred to in the `process_name.bpel` file

12.3.10 Changes Made In BPEL Designer Do Not Update Automatically

Updates that you make in the BPEL Validation Browser window may not be automatically reflected in the BPEL process. For example, if you perform the following steps:

1. Create a partner link, do not specify a WSDL file, and click **Apply** and **OK**. This error causes an **exclamation point** icon to display in the upper left corner of the **partnerLink** icon.
2. Click the exclamation point to display the BPEL Validation Browser window.
3. Double-click the partner link in the **BPEL Structure** section of this window, correctly complete all fields in the Edit Partner Link window that displays, and apply and save your changes.
4. Right-click the **BPEL Structure** window and select **Refresh Partner Links**. Note that the partner link still displays an error.

As a workaround, close the BPEL Validation Browser window, double-click the **partnerLink** icon in the **Diagram View** of JDeveloper BPEL Designer, and click **Apply** and **OK**. This action causes the error to disappear.

12.3.11 Extra Carriage Return Added When Using XML Literals

When you assign XML fragments in JDeveloper BPEL Designer, an extra carriage return is added for messages. For example:

```
<Name>QE_ORDER_NBR
```

</Name>

As a workaround, you must manually remove any unwanted carriage returns.

12.3.12 readFile Function Displays Only One Argument in XPath Expression Builder Window

The function `readFile` displays only one argument (`fileName`) in the XPath Expression Builder window (both in its description in the functions list and when you hold the cursor over this function in the Expression Body window). This function can take three arguments:

```
ora:readFile('fileName','nxsdTemplate'?, 'nxsdRoot'?)
```

See the XPath Extension Functions appendix of the *Oracle BPEL Process Manager Developer's Guide* for additional details on this function.

12.3.13 Error When Selecting Message Part Elements Using Inline Schemas of a Project

If you add or update a message type to use a message part element that uses the inline schema of the project (for example, by selecting **Project WSDL Files** > *process_name.wsdl* > **Inline Schemas** > **schema** > *process_nameProcessRequest* on the Type Chooser window), your process fails during deployment with a null error.

As a workaround, remove the `<import>` line from the WSDL file of the process:

```
<import namespace="http://xmlns.oracle.com/testing" location="testing.wsdl"/>
```

Save your changes and redeploy the process. Deployment succeeds with no null error.

12.4 Workflow and Worklist Issues and Workarounds

This section describes the following issues and workarounds:

- [Section 12.4.1, "Manually Configuring Oracle BPEL Process Manager on Oracle Application Server to Support Identity Management"](#)
- [Section 12.4.2, "Default Account Does Not Initially Display in Notification Service Page of Oracle Enterprise Manager"](#)
- [Section 12.4.3, "Always Deploy BPEL Projects with Workflow from JDeveloper BPEL Designer"](#)
- [Section 12.4.4, "Workflow Names Must Not Include Periods"](#)
- [Section 12.4.5, "Compilation Warning Messages That Can Be Ignored"](#)
- [Section 12.4.6, "Deleting an Entire User Task Activity"](#)
- [Section 12.4.7, "Deleting a Scope of a User Task Activity"](#)
- [Section 12.4.8, "Using the Category List in Oracle BPEL Worklist Application"](#)
- [Section 12.4.9, "Sequential Workflow with Automatic Escalation Error with Workflow Wizard"](#)
- [Section 12.4.10, "Getting Task Details with the getWorklistTaskDetails API"](#)
- [Section 12.4.11, "Adding Delays to Task Operations"](#)

- [Section 12.4.12, "Using the Custom Identity Service Provider Plug-in Sample on the Middle Tier"](#)
- [Section 12.4.13, "Configuring the TaskActionHandler and TaskManager Services to Support SSL"](#)

12.4.1 Manually Configuring Oracle BPEL Process Manager on Oracle Application Server to Support Identity Management

If you want to install Oracle BPEL Process Manager on an Oracle Application Server to use an Identity Management and Metadata repository, you must manually configure Oracle Internet Directory as a postinstallation step if the underlying Oracle Application Server is not configured with Identity Management.

If you are using an Oracle Application Server middle tier already configured with Identity Management, do *not* perform this postinstallation step; configuration is automatically performed during installation.

For example, since the Portal and Wireless middle-tier installation type requires Oracle Internet Directory, configuration is automatically performed during installation of Oracle BPEL Process Manager on this type of middle tier.

Replace the values shown in *italics* below with ones appropriate to your environment.

1. Ensure that *Oracle_Home\j2ee\OC4J_BPEL\config\jazzn.xml* contains the following `jazzn provider` element entries:

```
<jazzn provider="LDAP" location="ldap://host:port" default-realm="us">
  <property name="ldap.user" value="cn=orcladmin"/>
  <property name="ldap.password" value="!welcome1"/>
</jazzn>
```

2. Ensure that *Oracle_Home\integration\orabpel\system\services\config\is_config.xml* contains the following `provider` element entries:

```
<provider providerType="JAZN" name="oid">
  <connection url="ldap://host:port" binddn="cn=orcladmin" password="welcome1"
    encrypted="false"/>
</provider>
```

3. Ensure that *Oracle_Home\j2ee\OC4J_BPEL\application-deployments\hw_services\orion-application.xml* contains the following `jazzn provider` element entries:

```
<jazzn provider="LDAP" location="ldap://host:port" default-realm="us" >
  <jazzn-web-app auth-method="SSO"/>
</jazzn>
```

4. If the `bpelportlet.ear` Web provider is to be deployed through Oracle Enterprise Manager, manually configure *Oracle_Home\j2ee\OC4J_BPEL\application-deployments\bpelPortlet\orion-application.xml* as follows:

```
<jazzn provider="LDAP" location="ldap://host:port" default-realm="us" >
  <jazzn-web-app auth-method="SSO"/>
</jazzn>
```

12.4.2 Default Account Does Not Initially Display in Notification Service Page of Oracle Enterprise Manager

The Notification Service page in Oracle Enterprise Manager 10g Application Server Control Console does not display the default account after you initially install BPEL Process Manager for OracleAS Middle Tier. As a workaround, create a new e-mail account. This causes the default account to appear. If you then delete the new e-mail account, the default account continues to appear.

12.4.3 Always Deploy BPEL Projects with Workflow from JDeveloper BPEL Designer

BPEL projects with workflow must always be deployed from JDeveloper BPEL Designer. Do not use a command line tool such as `obant`. Command line deployment causes JSP features such as the payload display to not work.

12.4.4 Workflow Names Must Not Include Periods

Do *not* enter a name that includes periods in the **Workflow Name** field of the Workflow Pattern window of the Workflow wizard.

12.4.5 Compilation Warning Messages That Can Be Ignored

When you compile a BPEL process with a user task activity, warnings similar to the following appear in the **Log Window** of JDeveloper BPEL Designer:

```
Warning(443):  
[Error ORABPEL-10041]: Trying to assign incompatible types  
[Description]: in line 443 of  
"C:\apr20\integration\jdev\jdev\mywork\Application1\BPELProcess4\BPELProcess4.  
@ bpe1", <from> value type "{http://www.w3.org/2001/XMLSchema}anyType" is not  
@ compatible with <to> value type "{http://www.example.org}book anonymous  
type".
```

This indicates that an `anyType` is being assigned to an anonymous type. These warnings can be ignored. Ensure that the return value of the `from-spec` query is compatible with the `to-spec` query.

12.4.6 Deleting an Entire User Task Activity

If you want to delete and re-create a user task activity, perform the following steps:

1. Go into the **Diagram View** of the BPEL project.
2. Delete the scope activity and switch activity of the user task activity. These activities were created in the project when you ran the Workflow wizard of the user task activity.
3. Delete the partner links.
4. Delete the WSDL/XSD files from the project (recommended, but not required).
5. Create a new user task activity in which to design the workflow.

See Also: [Section 12.4.7, "Deleting a Scope of a User Task Activity"](#)

12.4.7 Deleting a Scope of a User Task Activity

A workflow scope activity is automatically created when you use the Workflow wizard of the user task activity. If you delete this scope activity, the related `config.xml`, `_form.jsp`, and `_fields.xml` files are not removed. You must

manually remove these files. If you do not remove these files, they do not cause any subsequent compilation or deployment errors.

12.4.8 Using the Category List in Oracle BPEL Worklist Application

The **Category** list of Oracle BPEL Worklist Application enables you to select the category of users, groups, or titles to search (**Group**, **Reportees**, and others). Note that the values of previous search results are also displayed. For example, assume that you first search on the **Group** category and that the results are displayed. If you next search on **Reportees**, then both the initial search results and the next search results are displayed. This is the expected behavior. Use **Check All** and **Uncheck All** to do a bulk select or unselect of the selections. Note that both these buttons only appear when there are two or more users in the selected list.

12.4.9 Sequential Workflow with Automatic Escalation Error with Workflow Wizard

You receive an error if you use the Workflow wizard to create the following type of workflow:

1. Make the following selections:
 - **Sequential Workflow with Automatic Escalation** workflow pattern on the Workflow Pattern window
 - **List of users** on the Assignment policy window
2. Expand the **RoutingWithEscalation** scope created by the Workflow wizard.
3. Double-click the **setRoutingPolicy assign** activity.
4. Select the second copy rule and click **Edit**.

orcl:create-delimited is underlined in blue, indicating an error.

12.4.10 Getting Task Details with the getWorklistTaskDetails API

When you get a task listing, each task object contains only summary information, and not detailed information such as payload, attachments, history, and so on. To get the details of a task, explicitly call the `getWorklistTaskDetails()` API inside a loop.

Note that looping while getting task details is a resource intensive action. You typically view details one task at a time. Call this method only for the task in which you are interested. Modify your `for` loop code as follows (adding one extra line to get the task details):

```
for (int i=0; i<tasks.size(); i++)
{
    IWorklistTask thisTask = (IWorklistTask)tasks.get(i);
    if ( <condition> ) { // task matches some condition
        thisTask = wlSrv.getWorklistTaskDetails(ctx, thisTask.getTaskId());
        ....
        Form form = null;
        form = PayloadFormGenerator.getMappingForm(thisTask);
        ....
    }
}
```

12.4.11 Adding Delays to Task Operations

In some cases, automated clients can perform task operations faster than Oracle BPEL Server. This can potentially result in messages being lost. While this issue is being

addressed, the workaround is to add a small delay (about five seconds) between the task operations, as shown in the following example:

```
client.updateTask(ctx, task);
Thread.sleep(5000); // sleep for 5000 milliseconds
client.customTaskOperation(ctx, taskId, "DONE");
```

12.4.12 Using the Custom Identity Service Provider Plug-in Sample on the Middle Tier

To use the custom identity service provider plug-in sample on the Oracle Application Server middle tier, you must make the following edits to the `build.xml` file:

1. Open the `Oracle_Home\integration\orabpel\samples\hw\isplugin\db\build.xml` file.

2. Change line 15 from:

```
<pathelement location="${classpath}" />
```

to:

```
<pathelement location="${client.classpath}" />
```

3. Change line 67 from:

```
<sysproperty key="java.naming.provider.url" value="ormi://${hostname}"/>
```

to:

```
<sysproperty key="java.naming.provider.url" value="${jndi.url}"/>
```

12.4.13 Configuring the TaskActionHandler and TaskManager Services to Support SSL

If you configure Oracle BPEL Process Manager for OracleAS Middle Tier with Secure Socket Layer (SSL) support, you must make the following changes to ensure that the TaskActionHandler and TaskManager services load correctly for BPEL processes.

1. Delete the `.bpel_TaskManager_1.0.jar` and `.bpel_TaskActionHandler_1.0.jar` directories under `Oracle_Home\integration\orabpel\domains\domain_name\tmp`.
2. Restart Oracle BPEL Server.

These steps re-create the correct service bindings and WSDL files for TaskManager and TaskActionHandler processes and make them available from HTTP/S-based endpoints.

Note: If your Oracle BPEL Process Manager installation exists as part of a BPEL cluster, you must perform these steps on each BPEL cluster node after you create a BPEL cluster.

12.5 Transformation Issues and Workarounds

This section describes the following issues and workarounds:

- [Section 12.5.1, "SetText Introduces a Newline Character After Transformation"](#)
- [Section 12.5.2, "Inconsistent Behavior for Functions in JDeveloper BPEL Designer"](#)
- [Section 12.5.3, "get-content-as-string Function Introduces a New Line Character After the Output"](#)

- [Section 12.5.4, "Target XSD with Choice May Create Invalid Target Instance at Run Time"](#)
- [Section 12.5.5, "Database Functions with JNDI Names Do Not Work Within a MapTest Window"](#)

12.5.1 SetText Introduces a Newline Character After Transformation

When you use `setText` on an element or attribute, the value contains a newline character after a transformation. The output is valid XML; however, the newline character has an undesired effect when translating the XML to a native format using Native Format Builder wizard translation or when doing a database `INSERT` operation.

Use one of the following methods as a workaround (assuming that **Oracle** is the static or constant value you want to assign to an element):

- Use the **xpath expression** advanced function:
 1. Select **Advanced Functions > xpath expression** from the **Component Palette**.
 2. Enter **Oracle** in the **XPath Expression** field.

The mapper generates `<xsl:value-of select="Oracle"/>` and the output does not have any spaces.
- Use the **normalize-space** string function:
 1. Select **String Functions > normalize-space** from the **Component Palette**.
 2. Enter `(" Oracle ")`.

This removes both leading and trailing spaces from the argument.

12.5.2 Inconsistent Behavior for Functions in JDeveloper BPEL Designer

The following `concat` function:

```
concat(bpws:getVariableData('variablename', 'partname', '/PO/ShipTo/First'),
       bpws:getVariableData('variablename', 'partname', '/PO/ShipTo/Last'))
```

works as expected. However, a `left-trim` function such as the following:

```
orl:left-trim(bpws:getVariableData('variablename', 'partname', '/PO/ShipTo/First'))
```

does not work.

However, `left-trim` works correctly in the following scenario:

```
orl:left-trim(string(bpws:getVariableData('variablename', 'partname', '/PO/ShipTo/First')))
```

Both the `concat` function and `left-trim` function expect a string value as an argument, but `left-trim` fails if `bpws:getVariableData` is passed as an argument. This is because `bpws:getVariableData` returns a node set and `left-trim` is unable to handle it. `concat` can handle a node set and it works.

As a workaround, explicitly chain a `string()` function to `getVariableData` before using it with any functions that come from the namespace prefixes `xp20` and `orcl` expecting a string parameter. For functions expecting numbers, you *must* convert them using the `number()` function.

12.5.3 get-content-as-string Function Introduces a New Line Character After the Output

The function `get-content-as-string` incorrectly introduces a newline character in the output. As an example, assume that the source element is:

```
<ID xmlns="">Mapper1000</ID>
```

The following XSL code results from using the function `get-content-as-string`:

```
<inv:Invoice>
  <ID>
    <xsl:value-of
      select="orcl:get-content-as-string(/po:PurchaseOrder/ID)"/>
    </ID>
  </inv:Invoice>
```

The output is as follows (when using Xalan as the XSL processor):

```
<ID>&lt;ID&gt;Mapper1000&lt;/ID&gt;&#13;
</ID>
```

Ideally, it should display without a newline character:

```
<ID>&lt;ID&gt;Mapper1000&lt;/ID&gt;&#13;</ID>
```

To achieve this, chain a `right-trim` function after `get-content-as-string`.

12.5.4 Target XSD with Choice May Create Invalid Target Instance at Run Time

Note the following source and target XSDs:

Source XSD:

```
<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns="http://www.example.org"
  targetNamespace="http://www.example.org"
  elementFormDefault="qualified" >

  <xsd:element name="choiceSrc">
    <xsd:complexType>
      <xsd:choice>
        <xsd:element name="Street" type="xsd:string"/>
        <xsd:element name="Street1" type="xsd:string"/>
      </xsd:choice>
    </xsd:complexType>
  </xsd:element>
</xsd:schema>
```

Target XSD:

```
<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns="http://www.example.org"
  targetNamespace="http://www.example.org"
  elementFormDefault="qualified" >

  <xsd:element name="choiceTgt">
    <xsd:complexType>
      <xsd:choice>
        <xsd:element name="Street" type="xsd:string"/>
        <xsd:element name="Street1" type="xsd:string"/>
      </xsd:choice>
    </xsd:complexType>
  </xsd:element>
```



```
</xsd:schema>
```

If you do not automatically map the root or manually map source `Street` to target `Street` and source `Street1` to target `Street1`, the generated XSL creates an invalid XML instance at run time.

While mapping manually, you must know the schema. If there is a choice, then you must manually use an `xsl:if`.

12.5.5 Database Functions with JNDI Names Do Not Work Within a MapTest Window

When you use JNDI names for database functions such as `query-database()`, `lookup-table()`, or `sequence-next-val()`, and try to test the map using the MapTest utility, no output is returned. The workaround is to use a JDBC string, instead of a JNDI name.

12.6 XPath Expression Builder Issues and Workarounds

If you use the XPath Building Assistant to create an XPath expression with hyphens (for example, on the Create Copy Rule window of an assign activity), a blue line displays under the hyphenated element and an error message similar to the following appears:

```
(34) Message part of name xyz-pqr- xyz not found
```

If the hyphenated elements are nested, the XPath Building Assistant does not allow you to proceed with `bpws:getVariableData()`. For example:

```
bpws:getVariableData('ug_in_var','users-and-groups','')
```

This error is most likely encountered when using the Native Format Builder wizard with the file adapter, where the element name defaults to the hyphenated name of `Root-Element`.

In addition, if elements have long names that wrap such as `root = "publicKeyInfrastructureCertificateAuthorities"` and `element = "publicKeyInfrastructureCertificateAuthority"`, XPath expression building also fails. You receive the following error message:

```
"publicKeyInfrastructureCertificateAuthorities" not found
```

Instead, click the **Expression Builder** icon on the Create Copy Rule window to display the XPath Expression Builder window. This window enables you to create an expression that includes hyphens in elements and enables long names to wrap. For example, for hyphens:

```
bpws:getVariableData('ug_in_var','users-and-groups','/ns2:users-and-groups/ns2:user-or-group/ns2:name')
```

12.7 Oracle Application Server Adapter for Files/FTP Issues and Workarounds

The section describes the following issues and workarounds:

- [Section 12.7.1, "Negative Values are Not Permitted for the PublishSize Parameter"](#)
- [Section 12.7.2, "Multiple Batching Invokes from the Same BPEL Process"](#)

- [Section 12.7.3, "Editing the Existing Logical Name Removes the Mapping in the bpel.xml File"](#)
- [Section 12.7.4, "Purging Files"](#)

12.7.1 Negative Values are Not Permitted for the PublishSize Parameter

Do *not* enter a negative value for the number of batches in which to publish messages in the adapter service WSDL file (for example, `PublishSize="-1"`). This causes a validation error when you attempt to deploy your process from JDeveloper BPEL Designer. Note that the Adapter Configuration wizard does not allow you to enter negative values for this parameter.

See Also: ["No Deployment Time Validation Logic with obant"](#) on page 12-5

12.7.2 Multiple Batching Invokes from the Same BPEL Process

If you do multiple batching file adapter invokes from the same BPEL process, your data is not correctly batched.

If you must have multiple batching file adapter invokes from the same BPEL process, perform the second (and subsequent) invoke through another shell BPEL process. This invokes the file adapter. That is, change your second partner link in the original BPEL process to point to a small BPEL process instead of the file adapter service.

This BPEL process can perform the file adapter invoke for you without issues.

12.7.3 Editing the Existing Logical Name Removes the Mapping in the bpel.xml File

The File Directories window of the Adapter Configuration wizard enables you to specify logical names instead of physical directory paths for both the incoming files directory and archive directory when using the FTP or file adapter. You must also provide corresponding property settings in the `bpel.xml` file (either manually or through the **Property** tab of the **partner link** activity).

If you later rerun the Adapter Configuration wizard and change the logical name of either the physical directory path or the archive directory, both properties are removed from the `bpel.xml` file. You must update *both* of these properties in the `bpel.xml` file.

12.7.4 Purging Files

You cannot purge control files specific to a BPEL process. For example, you cannot start anew with sequence number 1 for outbound files or reprocess a (debatching) file with errors from the beginning instead of from the last published message.

12.8 Oracle Application Server Adapter for AQ Issues and Workarounds

This section describes the following issue and workaround:

- [Section 12.8.1, "Timestamp with Local Timezone and Timestamp with Timezone are Not Supported in ADT"](#)

12.8.1 Timestamp with Local Timezone and Timestamp with Timezone are Not Supported in ADT

The AQ Adapter does not currently support the following data types for ADT columns:

- `TIMESTAMP WITH LOCAL TIMEZONE`
- `TIMESTAMP WITH TIMEZONE`

Only the `TIMESTAMP` data type is currently supported.

12.9 Oracle Application Server Adapter for Databases Issues and Workarounds

This section describes the following issues and workarounds:

- [Section 12.9.1, "Use OC4J Connection Pooling in High Availability Environments"](#)
- [Section 12.9.2, "Database Adapter Throws an Exception for SYS.XMLTYPE"](#)
- [Section 12.9.3, "NCLOB Data Read by the Outbound Database Adapter Contains Invalid Characters"](#)
- [Section 12.9.4, "Date/Time Format Values Not Displayed as Expected"](#)
- [Section 12.9.5, "SELECT Query Does Not Work for Multiple AND Conditions for DEPT:EMP Table"](#)
- [Section 12.9.6, "XML WSDL XSD Files Remain After the Partner Link Is Deleted"](#)
- [Section 12.9.7, "XML File Stored as a CLOB Is Returned as a String, Not as an XML Node"](#)
- [Section 12.9.8, "Cannot Query on Multiple Views"](#)
- [Section 12.9.9, "Using Function Calls Inside a SQL Query"](#)

See Also: The following issue that also impacts the database adapter:

- [Section 12.11.6, "Cannot Create a Partner Link If the Underlying API Has Been Re-created"](#) on page 12-22

12.9.1 Use OC4J Connection Pooling in High Availability Environments

You must use OC4J connection pooling with the database adapter. Do not use OracleAS TopLink connection pooling.

See Also: *Oracle Adapters for Files, FTP, Databases, and Enterprise Messaging User's Guide* for details about database adapter connection pooling

12.9.2 Database Adapter Throws an Exception for SYS.XMLTYPE

OracleAS TopLink does not support `SYS.XMLTYPE`.

12.9.3 NCLOB Data Read by the Outbound Database Adapter Contains Invalid Characters

When you configure two processes to perform the following tasks, invalid characters appear when the data is read from the inbound database adapter:

- A file adapter reads a Word document (in opaque format) and sends it in the database outbound direction. The data is inserted into the table.
- The database inbound direction reads the same data and sends it to the outbound file adapter, which writes to a document.

The workaround is to use a CLOB instead of NCLOB.

12.9.4 Date/Time Format Values Not Displayed as Expected

When you use datatypes such as DATE, TIMESTAMP, TIMESTAMP WITH TIME ZONE, and TIMESTAMP WITH LOCAL TIMEZONE, for which they are providing specific values, you do not see the expected formats. This is because the database adapter maps these database types to the XML type `dateTime`. For both incoming values in the instance XML and for outgoing values in the generated XML, `dateTime` is used. This is consistent with the ISO 8601 standard.

12.9.5 SELECT Query Does Not Work for Multiple AND Conditions for DEPT:EMP Table

Consider the following SELECT query:

```
select dept.*,emp.* from departments dept,employees emp where
dept.department_id='50' and emp.manager_id=dept.MANAGER_ID;
```

which can be worded as follows:

Find department 50 where any employee in that department has the same `manager_id` as the department itself.

Note that the above SQL command *returns* only those departments *and* employees that match the query. To get this same result with the adapter, you must choose `Employee` as the root table. If you chose `Department` as the root table, the adapter logically reads the employees in a separate relationship query:

```
select dept.* from departments dept,employees emp where
dept.department_id='50' and emp.manager_id=dept.MANAGER_ID;
```

```
select emp2.* from departments dept, employees emp, employees emp2 where
dept.department_id='50' and emp.manager_id=dept.MANAGER_ID and emp2.department_id
= dept.department_id;
```

The adapter returns the matching departments, plus all the employees for each matching department, even those whose `manager_id != dept.MANAGER_ID`.

Remember this simple rule: The SQL syntax only determines which rows from the root table get returned. The detail rows that are returned depend only on which root and master rows were returned. The above SQL syntax was difficult to express in the adapter because it returned columns from two tables that were both part of the `WHERE` clause. Selecting `Employees` as the root table instead of `Department` worked, but not vice versa.

12.9.6 XML WSDL XSD Files Remain After the Partner Link Is Deleted

After deleting a database adapter partner link from the **Diagram View** of JDeveloper BPEL Designer, the `toplink_mappings.xml`, the XSD, and the WSDL file remain in the **Applications Navigator**, even after refreshing. This is a known issue.

12.9.7 XML File Stored as a CLOB Is Returned as a String, Not as an XML Node

When an XML file (stored as a CLOB) is read and assigned to a variable whose type conforms to the schema, then the database adapter returns the contents of the CLOB as a string and not as an XML document/node. This is the expected behavior because `XMLType` is not supported.

12.9.8 Cannot Query on Multiple Views

Querying on multiple views when using the database adapter is not supported because you cannot create relationships between views. No option for doing so is provided in JDeveloper BPEL Designer. In addition, you cannot query on views and tables within a single query.

12.9.9 Using Function Calls Inside a SQL Query

Entering the following type of SQL query:

```
sqlquery : 'select count(*) from user_objects'
rowset : false()
row : false()
datasource : 'jdbc:oracle:thin:system/welcome1@localhost:1521:ORCL'
```

Results in the following exception error:

```
oracle.xml.sql.OracleXMLSQLException: Character ')' is not allowed in an
XML tag name.
```

If you use function calls inside a SQL query string such as `count(*)`, `sum(price)`, or `avr(price)`, include a pseudo-alias name. For example:

```
sqlquery : 'select count(*) as pseudo_alias_name_XXX from user_objects'
```

or

```
sqlquery : 'select sum(price) as total_price from user_objects'
```

12.10 Oracle Application Server Adapter for JMS Issues and Workarounds

This section describes the following issue and workaround:

- [Section 12.10.1, "Outbound Retry Functionality for AQJMS on Solaris Is Not Supported"](#)
- [Section 12.10.2, "Connection Retry Functionality for MQ Provider is Not Supported by the JMS Adapter"](#)
- [Section 12.10.3, "Removing Durable Subscriptions"](#)

12.10.1 Outbound Retry Functionality for AQJMS on Solaris Is Not Supported

When you use the JMS adapter to connect to an AQJMS provider, and if the database that hosts the AQ destination is 10.1.0.4, then the adapter retry mechanism on the outbound direction fails to reconnect to the database server if the database server goes down. This is because of a client JDBC issue with `ojdbc14.jar`. The resolution to this issue involves downloading the 10.1.0.4 JDBC drivers and using them in the mid tier by replacing the libraries, specifically `ojdbc14.jar` in `$MIDTIER_ORACLE_`

HOME/jdbc. To resolve this issue, refer to Metalink Note 317385.1 for a detailed explanation.

12.10.2 Connection Retry Functionality for MQ Provider is Not Supported by the JMS Adapter

Connection retry functionality for the MQ provider is currently not supported by the JMS adapter.

12.10.3 Removing Durable Subscriptions

The JMS adapter does not remove durable subscriptions after the BPEL partner link, which had been using a particular durable subscription, has stopped using it. You need to remove the durable subscribers manually.

12.11 Oracle Application Server Adapter for Oracle Applications Issues and Workarounds

This section describes the following issues and workarounds:

- [Section 12.11.1, "Correlation ID Defaults to BPEL for XML Gateway Transactions Outbound From Oracle Applications"](#)
- [Section 12.11.2, "Wildcard Search Capabilities are Based on the E-Business Suite Instance"](#)
- [Section 12.11.3, "Objects Displaying for Selection are Based on E-Business Suite Instance"](#)
- [Section 12.11.4, "Workaround for Stored Procedures with Complex Types and Using the DEFAULT Clause"](#)
- [Section 12.11.5, "One-time Workaround for Concurrent Programs and E-Commerce Gateway Interfaces"](#)
- [Section 12.11.6, "Cannot Create a Partner Link If the Underlying API Has Been Re-created"](#)

12.11.1 Correlation ID Defaults to BPEL for XML Gateway Transactions Outbound From Oracle Applications

The Oracle Applications adapter of the Adapter Configuration wizard does not let you specify a correlation ID for XML Gateway transactions that are outbound from Oracle Applications. Instead, a correlation ID named BPEL is automatically created in the WSDL file. If you need to do either of the following:

- Configure Oracle Applications to set this correlation ID for the corresponding XML Gateway transactions
- Want the adapter to use a different correlation ID from that configured on the Oracle Applications side

Then edit the following line contained in the <jca:operation> section of the adapter service WSDL and replace BPEL with any string of your choice:

```
Correlation="BPEL"
```

12.11.2 Wildcard Search Capabilities are Based on the E-Business Suite Instance

The E-Business Suite instance version to which you are connected determines how to use wildcards when searching for objects on the Oracle Applications Module Browser window of the Adapter Configuration wizard.

- For version 11.5.9, you search for objects using SQL wildcards (for example, enter `OE_HEADERS_IFACE%`)
- For version 11.5.10, you search for objects without specifying any characters as wildcards (for example, an equivalent of the above search string is `OE_HEADERS_IFACE`)

12.11.3 Objects Displaying for Selection are Based on E-Business Suite Instance

The E-Business Suite instance version to which you are connected determines which objects (for example, tables, views, PL/SQL procedures, and concurrent programs) display for selection on the Oracle Applications Module Browser window of the Adapter Configuration wizard.

- For version 11.5.9, everything available in the database (APPS schema) is available (for example, the `FNDWFLOAD` and `FNDWFRESGEN` concurrent programs appear)
- For version 11.5.10, only those objects available in the Integration Repository are shown (for example, `FNDWFLOAD` and `FNDWFRESGEN` do *not* appear).

12.11.4 Workaround for Stored Procedures with Complex Types and Using the DEFAULT Clause

When working with stored procedures for which the Adapter Configuration wizard must generate wrapper SQL stored procedures, there is a current limitation on `DEFAULT` clauses not being carried over to the generated wrapper stored procedures.

As a workaround, perform the following steps one time only for a given stored procedure:

1. Open the generated wrapper SQL script.
2. Copy all default clauses from the base-stored procedure into the corresponding wrapper.
3. Use SQL*Plus to reload the wrapper SQL script into the database.
4. Edit the generated XSD. If a parameter has a default clause, then its corresponding element in the XSD must have an extra attribute (`db:default="true"`). For example:

```
FINANCE$INVOICE(isTrue INTEGER DEFAULT 1, value NUMBER DEFAULT 0)
```

The elements in the XSD for `isTrue` and `value` must have the new attribute:

```
<element name="ISTRUE" ... db:default="true" .../>
<element name="VALUE" ... db:default="true" .../>
```

12.11.5 One-time Workaround for Concurrent Programs and E-Commerce Gateway Interfaces

When working with Concurrent Programs and E-Commerce Gateway interfaces, you must perform the following workaround exactly once for a given e-Business Suite instance.

Load the following SQL file:

```
%ORACLE_HOME%\integration\orabpel\system\database\scripts\apps_cp_ecx_wrapper_
oracle.sql
```

into the apps schema (using SQL*Plus) before launching the Oracle Applications adapter of the Adapter Configuration wizard to create services for either Concurrent Programs or E-Commerce Gateway Interfaces.

This is to work around the known issue with the Adapter Configuration wizard being unable to preserve `DEFAULT` clauses for PL/SQL wrappers that it generates underneath the covers.

12.11.6 Cannot Create a Partner Link If the Underlying API Has Been Re-created

The generation of a wrapper for an API that was re-created with the same name, but with a different set of parameters, fails.

This happens for both packaged procedures and top-level or root procedures that require generated wrappers. The following example illustrates the problem:

1. Create the initial API that, in this case, is defined at the top level.

```
SQL> create procedure test (a number, b varchar2, c BOOLEAN)
```

The `BOOLEAN` parameter indicates that a wrapper is necessary.

2. Use the database adapter for stored procedures in the Adapter Configuration wizard to generate and load the wrapper for this API.
3. Drop and re-create the API with a different set of parameters:

```
SQL> drop procedure test
SQL> create procedure test (
           a number, b varchar2, c number, d BOOLEAN)
```

An attempt to generate a partner link for this API using the Adapter Configuration wizard fails with the following message:

```
the wrapper procedure, TOPLEVEL$TEST, could not be found
```

As a workaround, exit JDeveloper BPEL Designer and restart it after recreating the stored procedure, but before attempting to create the second partner link.

12.12 General Adapter and Adapter Partner Link Issues and Workarounds

This section describes the following issues and workarounds:

- [Section 12.12.1, "Case of Property Names in ra.xml and oc4j-ra.xml Files Must Match"](#)
- [Section 12.12.2, "Deleting Header Variables"](#)
- [Section 12.12.3, "Moving to the Next Window in the Adapter Configuration Wizard for Oracle Applications Adapter"](#)
- [Section 12.12.4, "Configuring Multiple Adapters in the Inbound Direction Using Correlation Sets"](#)

12.12.1 Case of Property Names in ra.xml and oc4j-ra.xml Files Must Match

The case for all property names must exactly match in the `ra.xml` and `oc4j-ra.xml` files. Otherwise, you receive an error message similar to the following during run time in the `domain.log` file:

```
Type=Dequeue_ptt, operation=Dequeue
<2005-03-14 15:20:43,484> <ERROR> <default.collaxa.cube.activation>
<AdapterFramework::Inbound> Error while performing endpoint Activation: ORABPEL-12510<br>
Unable to locate the JCA Resource Adapter via WSDL port element jca:address.
The Adapter Framework is unable to startup the Resource Adapter specified in
the WSDL jca:address element:
@ {http://xmlns.oracle.com/pcbpel/wsdl/jca/}address:
location='eis/aqSample'
```

For example, if the `userName` property in the *Oracle_Home\integration\orabpel\system\appserver\oc4j\j2ee\home\application-deployments\default\AqAdapter\oc4j-ra.xml* file for the AQ adapter uses the following upper and lower case convention:

```
<config-property name="userName" value="scott"/>
```

Then this case must match the `userName` property in the corresponding *Oracle_Home\integration\orabpel\system\appserver\oc4j\j2ee\home\connectors\default\AqAdapter\AqAdapter\META-INF\ra.xml* file for the AQ adapter.

```
<config-property-name>userName</config-property-name>
```

12.12.2 Deleting Header Variables

Assuming that you have created a header variable for an adapter as follows, you cannot subsequently delete that variable through the same receive window. The workaround is to delete the header variable in the BPEL source code.

1. Create a BPEL project.
2. Double-click the **receive** activity.
3. Click the **Adapters** tab and define a header variable for the adapter.

12.12.3 Moving to the Next Window in the Adapter Configuration Wizard for Oracle Applications Adapter

If you select the Oracle Applications adapter in the Adapter Configuration wizard and click **Next** on the Database Objects window, moving to the next window can take some time. This is because a connection is being made to the database. The amount of time that it takes is based on your network connection to the database.

12.12.4 Configuring Multiple Adapters in the Inbound Direction Using Correlation Sets

When multiple adapter-based receive activities in the inbound direction use correlation sets in a process, the wrong property alias query is evaluated and the process fails at run time with the error:

```
Failed to evaluate correlation query
```

As a workaround, ensure that the port type and operation values are unique between the two adapter WSDL files. For example, ensure that each adapter WSDL file has a unique operation name.

12.13 Sensor Issues and Workarounds

This section describes the following issue and workaround:

- [Section 12.13.1, "Sensor Integration with Oracle Application Server Integration Business Activity Monitoring"](#)

12.13.1 Sensor Integration with Oracle Application Server Integration Business Activity Monitoring

You can create sensor actions in Oracle BPEL Process Manager to publish sensor data as data objects on an Oracle BAM Server. To use this functionality, you must install Oracle BAM 10.1.2.1.0 (also known as Oracle BAM 10.1.2 Patch 1). For details about obtaining Oracle BAM 10.1.2.1.0, see the **10.1.2 Patches** section at the following URL:

http://www.oracle.com/technology/products/integration/bam/htdocs/1012_support.html#patches

12.14 Oracle BPEL Console and Oracle BPEL Server Issues and Workarounds

This section describes the following issues and workarounds:

- [Section 12.14.1, "Configuring Mozilla Firefox for Oracle BPEL Console Support"](#)
- [Section 12.14.2, "Oracle BPEL Console Reports"](#)
- [Section 12.14.3, "Unable to Delete a Domain or Re-create a Domain with the Same Name"](#)
- [Section 12.14.4, "Large Binary Attachments in SOAP Messages Can Fail with Oracle Database Lite"](#)
- [Section 12.14.5, "SOAP Attachment DIME Service Callback Does Not Include the Attachment Key"](#)

12.14.1 Configuring Mozilla Firefox for Oracle BPEL Console Support

1. Select **New > Navigator Tab** from the **File** main menu in your Mozilla Web browser.
2. Enter `about:config` in the URL address field.
3. Highlight the new address and press **Ctrl** and then **Enter**.
4. Find the **signed.applets.codebase_principal_support** preference parameter in the **Preference Name** list.
5. Double-click this parameter to display the Enter boolean value window.
6. Enter **true** in the field and click **OK**.

12.14.2 Oracle BPEL Console Reports

Note the following issues when using Oracle BPEL Console reports:

- The **End Date** field format in the **Query** section is **mm/dd/yy** for *all* languages.

- Activity sensor reports show only variables of type number (for example, integer, double, decimal, and float). Nonnumeric types are not supported for this release. In addition, data is only shown for activity sensors with **Evaluation Time** set to **All** in the Create Activity Sensor window of JDeveloper BPEL Designer.
- If Albany fonts are not installed, fonts may not display properly for Asian languages in graphs (appear as squares). Albany fonts are automatically installed if you select the proper Asian language during installation.
- Validation does not work in the Mozilla Firefox browser. For example, if you enter **-1** in the **Number of Time Intervals** field, it is not validated. In addition, process time distribution report bars appear as lines in Mozilla Firefox.
- When clicking a bar in the performance report graph, the Instances page that appears sometimes does not display the correct list of instances. This is because the service level agreement (SLA) value in decimals is rounded off to the nearest integer. For example, assume there are two instances: one completes in three seconds and the other completes in two seconds. The SLA value is 2.6 seconds. The graph displays one instance in the green portion (indicating that the SLA value was satisfied) and the other in the red portion (indicating that the SLA value was not satisfied). Clicking the red portion does not show any instances. This is because the SLA value is rounded off to three seconds and therefore becomes equal to the completion time of the first instance.
- The default SLA value is shown in performance reports only when at least one instance of the business process is created.
- Reports exported to CSV format do not display Japanese or Asian characters. Fault sensor reports exported to CSV format with the fault message having multiple lines are unreadable in Microsoft Excel.
- When instances are purged, sensor data is not purged. Therefore, activity and fault sensor reports show data even if corresponding instances are not found.
- The **End Hour** field is used only for hourly reports, and *not* daily or weekly reports. For example, if you enter **07/29/05** as the end date, **22:00** as the end hour, **Weekly** as the time interval, and **3** as the time interval, the report is generated between **07/08/05** and **07/29/05**. Instances in any hour (even at 23:00 or 0:00) are also considered even though the end hour is 22:00. The same case exists for daily reports. Only with hourly intervals is report generation stopped at 22:00 hours.

12.14.3 Unable to Delete a Domain or Re-create a Domain with the Same Name

If you are unable to delete a domain or re-create a deleted domain with the same name in Oracle BPEL Admin Console (a message indicates the domain already exists), perform the following steps:

1. Go to Oracle BPEL Console.
2. Select the **BPEL Processes** tab, then select **Clear WSDL Cache**.

12.14.4 Large Binary Attachments in SOAP Messages Can Fail with Oracle Database Lite

If you use large binary attachment files in SOAP messages with Oracle Database Lite, your BPEL process may not complete processing, which can cause you to run out of system memory. Note that Oracle Database Lite is largely for testing purposes. To use large binary attachment files in SOAP messages, use an Oracle Database or the Oracle Application Server Metadata Repository as your dehydration store.

See Also: *Oracle BPEL Process Manager Installation Guide* for information about supported Oracle Databases and Oracle Application Server Metadata Repository

12.14.5 SOAP Attachment DIME Service Callback Does Not Include the Attachment Key

The **optSoapShortcut** parameter value defaults to **true** in Oracle BPEL Console. This setting causes BPEL processes with SOAP message binary attachments that use the Direct Internet Message Encapsulation (DIME) protocol to *not* display their attachment key in the Oracle BPEL Console audit trail for the process instance. This is because the binary attachment file is not saved to the dehydration database. Instead, an HTML file displays in the audit trail. For example:

```
<PutCompanyInfo>
. . .
. . .
<report href="C:\orabpel\domains\default\tmp\.bpel_DIMERequester_
1.0.jar\report.html"
/>
</PutCompanyInfo>
```

As a workaround, set **optSoapShortcut** to **false** in Oracle BPEL Console. This enables the file to be saved to the dehydration store and the attachment key to display in the audit trail for the instance (instead of the HTML file). Copy and paste the attachment key into the **Attachment Key** field at the bottom of the audit trail window and click **download** to save it as a file for viewing. If you do this, note that the File Download message initially prompts you to save the attachment key as a JSP file type. Instead, save the file as an HTML file type.

12.15 Oracle BPEL Portlets Issues and Workarounds

This section describes the following issues and workarounds:

- [Section 12.15.1, "Oracle BPEL Console Report Portlets"](#)
- [Section 12.15.2, "Oracle BPEL Worklist Application Portlets"](#)

12.15.1 Oracle BPEL Console Report Portlets

Note the following issues when using Oracle BPEL Console report portlets:

- To use Oracle BPEL Console report portlets, move the `uix2.jar` file from `ORACLE_HOME\integration\orabpel\lib` to a different directory (for example, `C:\OraMidTier\integration\orabpel\temp-lib`) and include this library path in the `ORACLE_HOME\j2ee\OC4J_BPEL\config\application.xml` file:

```
<library path="C:\OraMidTier\integration\orabpel\temp-lib"/>
```
- If you want to map portlet parameters with page parameters in Oracle Application Server Portal, the default value for the Oracle BPEL Console report portlet page parameter **Time Interval** parameter must always be in capital letters (for example, **DAILY**, **WEEKLY**, or **HOURLY**). Mapping portlet parameters with page parameters is described in section "Step 5: Mapping Portlet Parameters with Page Parameters" of the chapter "Oracle BPEL Portlets" of the *Oracle BPEL Process Manager Developer's Guide*.

12.15.2 Oracle BPEL Worklist Application Portlets

Note the following issues when using Oracle BPEL Worklist Application portlets:

- After deploying the Oracle BPEL Portlets with `dcmctl`, you must configure the Web provider with Oracle Internet Directory by ensuring that `Oracle_Home\j2ee\OC4J_BPEL\application-deployments\provider\orion-application.xml` includes the following settings:

```
<jazn provider="LDAP" default-realm="idc"><jazn-web-app
auth-method="SSO"/></jazn>
```

See the *Oracle BPEL Process Manager Developer's Guide* for instructions on deploying the Oracle BPEL Portlets with `dcmctl`.

- To use the Oracle BPEL Worklist Application portlets, move the `uix2.jar` file from `ORACLE_HOME\integration\orabpel\lib` to a different directory (for example, `C:\OraMidTier\integration\orabpel\temp-lib`) and include this library path in the `ORACLE_HOME\j2ee\OC4J_BPEL\config\application.xml` file:

```
<library path="C:\OraMidTier\integration\orabpel\temp-lib"/>
```

- Long strings of more than 360 characters in portlet titles are not handled properly
When specifying parameter values in the BPEL Worklist Portlet and BPEL Worklist Analysis Portlet, do not use long titles such as URL addresses in the **Title** field of the **Display Customization** sections. Long titles can disturb the portlet layout and cause the **Personalize** link in the upper right corner to not work.
- Worklist portlet title bar does not display the first time
When you initially install Oracle Application Server Portal, register the Web provider, create an initial page group, and add the Oracle BPEL Worklist Application portlets to the page group, the title bar does not appear. This means you cannot access the Personalize link that appears in the upper right corner of the title bar. As a workaround, create a second page group and add the Oracle BPEL Worklist Application portlets to the group. This group, and all subsequent groups you create, display the title bar and the Personalize link.
- All task states display in BPEL Worklist Portlet
When you select **All** or **Previous** in the **Category** list and **Assigned** in the **Status** list of the **Task Customization** sections of the BPEL Worklist Portlet, you see the state of *all* tasks, not just those identified as **Assigned**.

12.16 High Availability Issues and Workarounds

This section describes the following issues and workarounds:

- [Section 12.16.1, "Oracle BPEL Process Manager and Real Application Clusters Databases"](#)
- [Section 12.16.2, "Disaster Recovery of Oracle BPEL Process Manager"](#)
- [Section 12.16.3, "Oracle BPEL Process Manager Backup and Recovery with Oracle Enterprise Manager"](#)

12.16.1 Oracle BPEL Process Manager and Real Application Clusters Databases

You can use a Real Application Clusters (RAC) database as a dehydration store or as a data source for the database adapter with Oracle BPEL Process Manager. However, RAC setup requires manual steps and some patches. Contact Oracle Support Services for assistance.

12.16.2 Disaster Recovery of Oracle BPEL Process Manager

Disaster recovery (DR) functionality is not supported for the 10.1.2.0.2 phase 2 release of Oracle BPEL Process Manager.

12.16.3 Oracle BPEL Process Manager Backup and Recovery with Oracle Enterprise Manager

You must perform the following procedures to correctly back up and recover Oracle BPEL Process Manager through Oracle Enterprise Manager:

1. Open the *Oracle_Home\backup_restore\config\config_IPbpm_files.inp* file of your BPEL Process Manager for OracleAS Middle Tier installation.
2. Substitute the following directory path lines in place of the current lines in this file:

```
# Orabpel
#
${OH}/integration/orabpel/system/config/collaxa-config.xml
${OH}/integration/orabpel/system/config/*
${OH}/integration/orabpel/system/logs/*
${OH}/integration/orabpel/system/xmllib/*
${OH}/integration/orabpel/domains/*/archive/*
${OH}/integration/orabpel/domains/*/config/*
${OH}/integration/orabpel/domains/*/deploy/*
${OH}/integration/orabpel/domains/*/logs/*
```

3. Modify the *Oracle_Home\backup_restore\config\config.inp* file by appending *config_IPbpm_files.inp* to the end of the *config_files_list* parameter. For example:

```
config_files_list=config_ohs_files_nt.inp,...,config_iaspt_files.inp,config_
IPbpm_files.inp
```

12.17 Globalization/Multibyte Character Issues and Workarounds

This section describes the following issues and workarounds:

- [Section 12.17.1, "Encoding Restrictions in E-Mail Subject Field"](#)
- [Section 12.17.2, "UTF-8 Encoding Always Used in XSLT Mapper"](#)
- [Section 12.17.3, "XML Mapper Must Use the Encoding Specified in the XSL When Reading a File"](#)
- [Section 12.17.4, "Multibyte Project Name Causes WSDL File to Be Invalid"](#)
- [Section 12.17.5, "Ruler Scale Is Not Multibyte-compliant in the Native Format Builder Wizard"](#)
- [Section 12.17.6, "Encoding Issue for ora:readFile"](#)
- [Section 12.17.7, "Data Consumed as a Text Message May Have Problems"](#)

12.17.1 Encoding Restrictions in E-Mail Subject Field

The encoding for the `SUBJECT` field in an e-mail message is always set to the language of Oracle BPEL Server, and cannot be changed. If the subject of an e-mail notification is in a different language than that of Oracle BPEL Server, unreadable characters appear in the `SUBJECT` field of the e-mail client. However, the actual body content of the e-mail message is readable.

12.17.2 UTF-8 Encoding Always Used in XSLT Mapper

In the Test XSL Map window, the source and target XML files are always saved in UTF-8 encoding even if you specify a different encoding in the XML header. This eliminates the risk of incorrectly editing the encoding value in the header.

12.17.3 XML Mapper Must Use the Encoding Specified in the XSL When Reading a File

The XML mapper uses UTF-8 encoding for your operating system to read XSL content from files. Therefore, parsing errors can occur if encoding of XSL content is different from UTF-8.

The workaround is to perform one of the following:

1. Save the old map file as a different map file in UTF-8 encoding and open it in the mapper.
2. Open the old map file, and change the encoding to UTF-8 in the source view. After that, you can switch to the **Design** view.

12.17.4 Multibyte Project Name Causes WSDL File to Be Invalid

If you create a BPEL project with a multibyte name, the automatically generated WSDL file name and its referenced namespace URL do not correctly process, which causes the BPEL process to be invalid.

As a workaround, use the ASCII character set for process file names and namespaces.

12.17.5 Ruler Scale Is Not Multibyte-compliant in the Native Format Builder Wizard

If you select the fixed length file type in the Native Format Builder wizard, the ruler on the Field Lengths window that enables you to specify field length for each record is not multibyte-compliant.

12.17.6 Encoding Issue for `ora:readFile`

The extended XPath function `ora:readFile` requires a file directory path as the first parameter. These functions read the specified file by using OS-default encoding. This is not an issue if the specified file is in the local file system. However, if the specified path is a URL, the target file is not always encoded in OS-default encoding.

12.17.7 Data Consumed as a Text Message May Have Problems

When you configure the JMS adapter in the inbound direction to consume text messages, the data received may be unusable. To avoid this issue, you can use the XSD schema created by the Native Format Builder wizard and select UTF-8 as the character set when prompted.

If you use standard XSD, you expect that the text message in the JMS queue/topic is an XML string. It can contain an XML header string with the encoding attribute, but to

avoid the above-mentioned problem, keep enqueueing it without the XML header or with "encoding=UTF-8".

If the JMS message is a bytes message, this problem does not occur.

12.18 Oracle BPEL Process Manager Samples Issues and Workarounds

The `Oracle_Home\integration\orabpel\samples\demos\OWFBridge` sample includes an Oracle Workflow process named WFDemo. This process is part of the Oracle Workflow sample and must be loaded into Oracle Workflow *before* you run this sample. Otherwise, you receive Oracle BPEL Console errors if you try to build the sample.

See Also: *Oracle BPEL Process Manager Developer's Guide* for additional Oracle Workflow Bridge details, including information on adding a data source definition

12.19 JBoss Issues and Workarounds

This section describes the following issues and workarounds:

- [Section 12.19.1, "Error To Ignore when Installing Oracle BPEL Process Manager on Solaris"](#)
- [Section 12.19.2, "Cannot Migrate From Oracle BPEL Process Manager 10.1.2.0.0 to 10.1.2.0.2 with JBoss Application Server"](#)
- [Section 12.19.3, "Increasing Connection Pool Settings for Oracle BPEL Process Manager"](#)
- [Section 12.19.4, "OracleAS Integration B2B and OracleAS Integration InterConnect Interoperability with Oracle BPEL Process Manager is Not Supported"](#)
- [Section 12.19.5, "Oracle Workflow Bridge is Not Supported"](#)
- [Section 12.19.6, "Identity Service Plug-in for Database Providers Sample is Not Supported"](#)

12.19.1 Error To Ignore when Installing Oracle BPEL Process Manager on Solaris

You can receive a `cursor properties permission denied` message similar to the following during installation on Solaris. Ignore this message. Installation completes successfully.

```
Error while converting end-of-line marker in directory
"/private/myhome/JBOSS/install/jre/lib/images/cursors/cursors.prope
rties (Permission denied)".
java.io.FileNotFoundException:
/private/myhome/JBOSS/install/jre/lib/images/cursors/cursors.proper
ties (Permission denied)
```

12.19.2 Cannot Migrate From Oracle BPEL Process Manager 10.1.2.0.0 to 10.1.2.0.2 with JBoss Application Server

You cannot currently migrate from the 10.1.2.0.0 release of Oracle BPEL Process Manager with the JBoss Application Server to this 10.1.2.0.2 release. Instead, install a completely new version of Oracle BPEL Process Manager release 10.1.2.0.2 with the JBoss Application Server.

See Also: *Oracle BPEL Process Manager Installation Guide* for Oracle BPEL Process Manager release 10.1.2.0.2 installation instructions with the JBoss Application Server

12.19.3 Increasing Connection Pool Settings for Oracle BPEL Process Manager

If Oracle BPEL Server displays a "cannot fetch datasource" error, increase the maximum number of connections value in the database connection pool. For example:

```
<max-pool-size>30</max-pool-size>
```

Increase this parameter value in the following locations:

- The <local-tx-datasource> and <no-tx-datasource> sections of `oracle-ds.xml`
- The <local-tx-datasource> section of `oracle-sample-bpel-ds.xml`

These files are located in the *Oracle_Home\system\appserver\jboss\server\default\deploy* directory.

If you are using Oracle Database Lite, do not set the `max-pool-size` parameter value higher than 25. This is a limitation of Oracle Database Lite. If you need a higher value, use an Oracle Database.

See Also: *Oracle BPEL Process Manager Installation Guide* for details about using an Oracle Database

12.19.4 OracleAS Integration B2B and OracleAS Integration InterConnect Interoperability with Oracle BPEL Process Manager is Not Supported

You cannot configure the following components on the JBoss Application Server to communicate with Oracle BPEL Process Manager release 10.1.2.0.2:

- OracleAS Integration B2B
- OracleAS Integration InterConnect

12.19.5 Oracle Workflow Bridge is Not Supported

Oracle Workflow Bridge cannot be used with Oracle BPEL Process Manager and the JBoss Application Server.

12.19.6 Identity Service Plug-in for Database Providers Sample is Not Supported

The identity service plug-in for database providers sample available in *Oracle_Home\integration\orabpel\samples\hw\isplugin\db* does not currently work with the JBoss Application Server.

12.20 BEA WebLogic Issues and Workarounds

This section describes the following issues and workarounds:

- [Section 12.20.1, "Unsupported Upgrade and Migration Scenarios"](#)
- [Section 12.20.2, "owf.ear File Not Included with Installation Software"](#)
- [Section 12.20.3, "Identity Service Plug-in for Database Providers Sample is Not Supported"](#)

- [Section 12.20.4, "OracleAS Integration B2B and OracleAS Integration InterConnect Interoperability with Oracle BPEL Process Manager is Not Supported"](#)

12.20.1 Unsupported Upgrade and Migration Scenarios

The following upgrade and migration scenarios are not supported. Instead, install a completely new version of Oracle BPEL Process Manager release 10.1.2.0.2 with the BEA WebLogic Application Server.

- Oracle BPEL Process Manager 10.1.2.0.2 is only certified on BEA WebLogic Application Server 8.1.5. Therefore, you cannot currently upgrade from the 10.1.2.0.0 release of Oracle BPEL Process Manager on BEA WebLogic Application Server release 8.1.4 to the 10.1.2.0.2 release of Oracle BPEL Process Manager on BEA WebLogic Application Server release 8.1.5.
- You cannot currently migrate from the 10.1.2.0.0 release of Oracle BPEL Process Manager with the BEA WebLogic Application Server to this 10.1.2.0.2 release.

See Also: *Oracle BPEL Process Manager Installation Guide* for Oracle BPEL Process Manager release 10.1.2.0.2 installation instructions with the BEA WebLogic Application Server

12.20.2 owf.ear File Not Included with Installation Software

The `owf.ear` file that is used to install Oracle Workflow Bridge on the host on which Oracle BPEL Process Manager is installed is not included with the BEA WebLogic Application Server and Oracle BPEL Process Manager installation software.

12.20.3 Identity Service Plug-in for Database Providers Sample is Not Supported

The identity service plug-in for database providers sample available in *Oracle_Home\integration\orabpel\samples\hw\isplugin\db* does not currently work with the BEA WebLogic Application Server.

12.20.4 OracleAS Integration B2B and OracleAS Integration InterConnect Interoperability with Oracle BPEL Process Manager is Not Supported

You cannot configure the following components on the BEA WebLogic Application Server to communicate with Oracle BPEL Process Manager release 10.1.2.0.2:

- OracleAS Integration B2B
- OracleAS Integration InterConnect

12.21 Microsoft SQL Server Issues and Workarounds

This section describes the following issues and workarounds:

- [Section 12.21.1, "Oracle BPEL Process Manager for OracleAS Middle Tier Installations and Sensors"](#)
- [Section 12.21.2, "SOAP with Binary Attachments Not Supported"](#)
- [Section 12.21.3, "Reports Feature of Oracle BPEL Console and BPEL Reports Portlets Not Currently Working"](#)
- [Section 12.21.4, "Identity Service Plug-in for Database Providers Sample Not Currently Working"](#)

12.21.1 Oracle BPEL Process Manager for OracleAS Middle Tier Installations and Sensors

If you install Oracle BPEL Process Manager for OracleAS Middle Tier, ensure that you manually add the `bc4jdomgnrc.jar` line above the `BC4J/lib` line in the `Oracle_Home\j2ee\OC4J_BPEL\config\application.xml` file:

```
<library path="../../../BC4J/jlib/bc4jdomgnrc.jar"/>
<library path="../../../BC4J/lib"/>
```

This action ensures that any sensors in your process correctly load when you deploy the process to Oracle BPEL Server.

12.21.2 SOAP with Binary Attachments Not Supported

Using SOAP with binary attachments is not supported on Microsoft SQL Server. For example, the DIME samples under `Oracle_Home\integration\orabpel\samples\demos\Attachment` cannot complete successfully. This is because binary large objects (BLOB) are not supported in Microsoft SQL Server.

12.21.3 Reports Feature of Oracle BPEL Console and BPEL Reports Portlets Not Currently Working

The **Reports** link for a deployed BPEL process in the **BPEL Processes** tab of Oracle BPEL Console is not currently enabled with Microsoft SQL Server. In addition, the BPEL Reports Portlets accessible from Oracle Application Server Portal cannot be used with Microsoft SQL Server.

12.21.4 Identity Service Plug-in for Database Providers Sample Not Currently Working

The identity service plug-in for database providers sample available in `Oracle_Home\integration\orabpel\samples\hw\isplugin\db` does not currently work with Microsoft SQL Server.

12.22 Documentation Errata

This section describes known errors in the documentation. It includes the following topics:

- [Section 12.22.1, "Oracle Application Server Administrator's Guide"](#)
- [Section 12.22.2, "Oracle Application Server Adapters for Files, FTP, Databases, and Enterprise Messaging User's Guide"](#)

12.22.1 Oracle Application Server Administrator's Guide

Chapter: 19, "Introduction to Backup and Recovery"

Header: "Oracle Application Server Component Backup Input Files"

Pages: 19-5 and 19-6

Table 19-1 on page 19-5 lists the Oracle BPEL Process Manager backup input file name as `config_ip_files.inp`. The correct name is `config_IPbpm_files.inp`.

In addition, the following line on page 19-6 can be ignored:

Component Name column: Business Integration Process Manager

Backup Input File column: config_IPbpm_files.inp

12.22.2 Oracle Application Server Adapters for Files, FTP, Databases, and Enterprise Messaging User's Guide

This section describes following known errors and omissions in Oracle Application Server Adapters for Files, FTP, Databases, and *Enterprise Messaging User's Guide*:

- [Using the Native Format Translator for removing or adding namespaces to XML with no namespace](#)
- [File and FTP Adapter Features](#)
- [Archiving Successfully Processed Files](#)
- [Troubleshooting the Oracle Application Server Adapter for Java Message Service \(JMS\)](#)
- [JMS Provider Error](#)

Using the Native Format Translator for removing or adding namespaces to XML with no namespace

Chapter: 6, Native Format Builder Wizard

Header: "Using the Native Format Translator for removing or adding namespaces to XML with no namespace"

Page: 6-13

The section "Using the Native Format Translator for removing or adding namespaces to XML with no namespace" on page 6-13 has incorrect information. The section should read as follows:

When the native data is XML and that XML has no namespace, then the Native Format Translator can be used to add a namespace to an inbound XML document and remove the namespace from an outbound XML document.

The XML has no namespace when either of the following is true:

- The XML has a corresponding XML schema and there is no target namespace specified in that XML schema.
- The XML has a corresponding DTD which was converted to the XML schema.

In both cases, we need to create a wrapper schema with `targetNamespace` specified, and the wrapper schema should include the actual schema. In addition, the wrapper schema should also have the `nxsd:version` attribute set to DTD. For example:

```
--wrapper.xsd
<?xml version="1.0" encoding="UTF-8"?>
<schema xmlns="http://www.w3.org/2001/XMLSchema"
  targetNamespace="myNamespace"
  xmlns:nxsd="http://xmlns.oracle.com/pcbpel/nxsd"
  nxsd:version="DTD">
  <include schemaLocation="actual.xsd"/>
</schema>
```

Note: Ensure that `elementFormDefault="qualified"` is specified in the actual schema.

Using this wrapper .xsd in place of actual .xsd would add myNamespace namespace to the inbound xml and would remove myNamespace namespace from the outbound xml.

File and FTP Adapter Features

Chapter: 2, Oracle Application Server Adapter for Files/FTP

Header: "File and FTP Adapter Features"

Page: 2-2

The following information about supported FTP servers is missing in this section:

The FTP adapter supports Solaris and Windows FTP servers.

Archiving Successfully Processed Files

Chapter: 2, Oracle Application Server Adapter for Files/FTP

Header: "Archiving Successfully Processed Files"

Page: 2-6

First note in the section "Archiving Successfully Processed Files" on page 2-6 has incomplete information. The note should read as follows:

Note: Files greater than or equal to 7 MB cannot be delivered. As an alternative, you can debatch large files (if they have multiple messages), and publish these files in messages of sizes less than 7 MB. This alternative option is applicable only to structured files (comma-delimited or fixed position), which contain more than one message. It is not applicable to binary or XML files.

Troubleshooting the Oracle Application Server Adapter for Java Message Service (JMS)

Appendix: A, Troubleshooting and Workarounds

Header: "Troubleshooting the Oracle Application Server Adapter for Java Message Service (JMS)"

Page: A-30

Section "Troubleshooting the Oracle Application Server Adapter for Java Message Service (JMS)" is missing in appendix A "Troubleshooting and Workarounds". The section should read as follows:

JMS Provider Error

```
<JMSAdapter::Outbound>
ORABPEL-12165
ERRJMS_PROVIDER_ERR.
Could not produce message due to JMS provider error. Please examine the log
file to determine the problem.
.....
.....
.....
Caused by: javax.jms.JMSEException: MQJMS1013: operation invalid whilst
session is using asynchronous delivery.
```

Solution:

This exception occurs when the inbound JMS adapter and the outbound JMS adapter for MQ provider use the same JNDI name. To avoid this exception, specify different JNDI names in WSDL files for the inbound and outbound JMS adapter for MQ provider.

Another workaround is to specify the `UseMessageListener` property as `false` in the inbound WSDL file. For example:

```
UseMessageListener="false"
```

Oracle BPEL Process Analytics

This chapter describes issues associated with Oracle BPEL Process Analytics. It includes the following topics:

- [Section 13.1, "General Issues and Workarounds"](#)
- [Section 13.2, "Known Problems"](#)
- [Section 13.3, "Documentation Errata"](#)

Note: For Oracle BPEL Process Manager release notes, see the Oracle BPEL Process Manager site of the Oracle Technology Network at <http://www.oracle.com/technology/bpel>.

13.1 General Issues and Workarounds

This section includes the following issues:

- [Section 13.1.1, "Unset the ORACLE_HOME Variable Before Installing"](#)
- [Section 13.1.2, "Workaround for Inability to Connect to Database After Installation"](#)
- [Section 13.1.3, "Restart Oracle BPEL Process Analytics To Fire Alerts In Some Specific Cases"](#)
- [Section 13.1.4, "Array Support in Oracle BPEL Process Analytics is Limited to First Level"](#)
- [Section 13.1.5, "Non-Working Alert Delivery Channels - FAX, Instant Message, Pager"](#)
- [Section 13.1.6, "To Use BAMServiceWrapper, Apply Patch 1 on BPEL"](#)
- [Section 13.1.7, "Old Target Values Shown When Adding New Dimensions to a Composite Event"](#)
- [Section 13.1.8, "Focus Button on Update Composite Event Confirmation Page Returns Error"](#)
- [Section 13.1.9, "Alerts for <= KPI Value Condition Fire at 12 O'clock With Value Zero"](#)
- [Section 13.1.10, "Cannot Create Sensors for Primitive and Element Types"](#)
- [Section 13.1.11, "Some Error Messages Contain "BAM" Instead of "BPA"'"](#)
- [Section 13.1.12, "Oracle BPEL Process Analytics Dashboard Shows Strange Character"](#)
- [Section 13.1.13, "Cannot Create Two Composite Events of the Same Name"](#)

- [Section 13.1.14, "Best Practice for Time Zone Settings"](#)
- [Section 13.1.15, "Dashboard KPI Table Shows Exclamation Marks"](#)
- [Section 13.1.16, "Do Not Use SQL Keywords for Naming the KPIs"](#)
- [Section 13.1.17, "New Default Units for Duration and Currency Type KPIs"](#)
- [Section 13.1.18, "Exception Returned In UI.LOG While Logged in as Administrator"](#)
- [Section 13.1.19, "No Oracle BPEL Process Analytics Logs Are Available From Oracle Enterprise Manager"](#)
- [Section 13.1.20, "Workaround for Errors Such As "Failed to Add to Metadata""](#)
- [Section 13.1.21, "Parentheses Needed In KPI Creation Wizard"](#)

13.1.1 Unset the ORACLE_HOME Variable Before Installing

When installing Oracle BPEL Process Analytics, the ORACLE_HOME variable must not be set; otherwise, the installation may fail with the error, "configuration assistant 'Oracle BPA Configuration Assistant' was cancelled."

Do the following to check and clear the setting of the ORACLE_HOME variable:

1. Enter the following command:

```
echo $ORACLE_HOME
```

2. Unset the variable if it is defined using the following command:

```
unsetenv ORACLE_HOME
```

If you have already received the error, copy the TNS entry that the Oracle BPEL Process Analytics installation created in the *BPA_midtier_home/network/admin/tnsnames.ora* file as the database service you entered in the file *Default_Oracle_Home/network/admin/tnsnames.ora*, and then click the **Retry** button on the installer.

1. Enter the following command:

```
echo $ORACLE_HOME
```

2. Unset the variable if it is defined using the following command:

```
unsetenv ORACLE_HOME
```

If you have already received the error, copy the TNS entry that the Oracle BPEL Process Analytics installation created in the *BPA_midtier_home/network/admin/tnsnames.ora* file as the database service you entered in the file *Default_Oracle_Home/network/admin/tnsnames.ora*, and then click the **Retry** button on the installer.

13.1.2 Workaround for Inability to Connect to Database After Installation

Installing other Oracle products into the Oracle Application Server middle tier where Oracle BPEL Process Analytics is installed may modify the *tnsnames.ora* file such that the following error message is returned when you attempt to connect to the database:

```
ORA-12154: TNS:could not resolve the connect identifier specified
```


To resolve this problem, make sure that there is a net service name entry in the `Oracle_BPA_Home/network/admin/tnsnames.ora` file which matches the SID specified by the `oracle.tip.bam.connection.sid` parameter in the `Oracle_BPA_Home/integration/bam/config/bam.properties` file (where `Oracle_BPA_Home` is the Oracle Application middle tier home where Oracle BPEL Process Analytics is installed).

In addition, make sure that this net service name correctly resolves to the Oracle BPEL Process Analytics Repository database.

13.1.3 Restart Oracle BPEL Process Analytics To Fire Alerts In Some Specific Cases

If you configure Oracle BPEL Process Analytics (event source, composite events, KPIs, metrics, panes, and so on), start using it, and then, after several days configure alerts, the alert may not fire even if the alert condition is met. The workaround to this problem is to restart Oracle BPEL Process Analytics.

13.1.4 Array Support in Oracle BPEL Process Analytics is Limited to First Level

There is limited array support for this release. Oracle BPEL Process Analytics flattens out array attributes. Thus only first level arrays are supported.

13.1.5 Non-Working Alert Delivery Channels - FAX, Instant Message, Pager

The *Oracle BPEL Process Analytics User's Guide*, states that "An administrator can set up notifications, called explicit alerts, that are sent to the business analyst if a KPI or metric exceeds a predetermined threshold value. An explicit alert can be sent as an e-mail message, a phone message, a FAX, a Short Message Service (SMS) message, a pager message, or as an Internet instant message."

However, FAX, instant message, and pager do not work.

13.1.6 To Use BAMServiceWrapper, Apply Patch 1 on BPEL

A sample BPEL process, `BAMServiceWrapper`, is provided which enables you to invoke the Oracle BPEL Process Analytics Web Service from Oracle BPEL Process Manager.

Because of a bug in Oracle BPEL Process Manager, the sample requires Patch 1 of Oracle BPEL Process Manager to be installed for this sample to work properly.

13.1.7 Old Target Values Shown When Adding New Dimensions to a Composite Event

Updating a composite event by adding new dimensions to an existing composite event causes the old target values to be displayed in the Dashboard.

13.1.8 Focus Button on Update Composite Event Confirmation Page Returns Error

If you remove a hierarchical dimension from a composite event using the Update Composite Event Wizard, then Oracle BPEL Process Analytics displays the Focus column with a circular symbol on the confirmation page.

If you click the circular symbol, Oracle BPEL Process Analytics returns the error:

```
500 Internal server Error
```

13.1.9 Alerts for <= KPI Value Condition Fire at 12 O'clock With Value Zero

Because all KPIs are initialized to 0 at 12 o'clock by the Oracle BPEL Process Analytics engine, any alert of type (<=KPI value) will always return 'true'.

Possible workarounds to handle these with metric alerts, are to have a condition for > 0 and for < KPI value.

13.1.10 Cannot Create Sensors for Primitive and Element Types

If the Oracle BPEL Process Manager variable for which an Oracle BPEL Process Analytics sensor is defined is of primitive (`string`, `int`, and so on) or element type (no part associated), then Oracle BPEL Process Analytics sensors can be created but will not work at run time (and no errors are returned).

13.1.11 Some Error Messages Contain "BAM" Instead of "BPA"

Some error messages contain the tokens "BAM" instead of "BPA" when referring to Oracle BPEL Process Analytics. These tokens refer to Oracle BPEL Process Analytics.

13.1.12 Oracle BPEL Process Analytics Dashboard Shows Strange Character

The symbol of a circle with four spokes coming out at diagonals is a generic symbol for currency. To correct, manually modify the `opmn.xml` file to set the `LANG` environment variable to 'en_US' (United States English); the currency is then formatted correctly.

13.1.13 Cannot Create Two Composite Events of the Same Name

Creating two composite events of the same name on different event sources returns a server error.

This error occurs, for example, if you do the following:

1. Create a generic event source.
2. Create a composite event (for example 'LoanFlow') on a generic event source.
3. Create an Oracle BPEL Process Manager event source.
4. Create a composite event (for example 'LoanFlow') on Oracle BPEL Process Manager. An exception is then returned.

13.1.14 Best Practice for Time Zone Settings

If the Oracle BPEL Process Manager event source and the Oracle BPEL Process Analytics server are on the same time zone, ensure that the machine time (on which Oracle BPEL Process Manager is running) is the same as that on the Oracle BPEL Process Analytics server. Even if the machine time is slightly ahead in terms of minutes or seconds, Oracle BPEL Process Analytics will not be able to run the KPI and alerts until the Oracle BPEL Process Analytics engine reaches the same time as the event in the source machine.

However, the real time viewer in Oracle BPEL Process Analytics will capture the event. Oracle BPEL Process Analytics does not capture metrics, alerts, or KPI calculations and spends a lot of time debugging. It is now known that the time difference (between the time zones of the server and of the BPEL source machine) causes this.

13.1.15 Dashboard KPI Table Shows Exclamation Marks

If there are icons of an exclamation mark within a yellow triangle that appear against the values shown in the KPI table view in the Dashboard, it indicates that target data is loaded for the KPI value that is being presented on the screen. This icon is used to signify when a KPI is 'at risk'. A KPI is 'at risk' if there is target data and the KPI performance is 'Weak' or 'Under'.

13.1.16 Do Not Use SQL Keywords for Naming the KPIs

Do not use SQL keywords (such as COUNT, ORDER, and so on) when naming KPIs. SQL keywords can cause a syntax error at the time of target data loading.

13.1.17 New Default Units for Duration and Currency Type KPIs

The default unit of for a time KPI is now seconds. The default unit of currency is now dollars.

13.1.18 Exception Returned In UI.LOG While Logged in as Administrator

The following error is sometimes returned in the `ui.log` file while logged in as Administrator, but this has no effect on the Oracle BPEL Process Analytics user interface:

```
Exception setting DB Password java.net.ConnectException: Connection refused:
connect...
```

13.1.19 No Oracle BPEL Process Analytics Logs Are Available From Oracle Enterprise Manager

There are no logs available for Oracle BPEL Process Analytics using Logviewer from Oracle Enterprise Manager. For example, if you select BPEL Process Analytics from Available Components, and then search, the results show no logs found. However the search results should list logs related to Oracle BPEL Process Analytics.

13.1.20 Workaround for Errors Such As "Failed to Add to Metadata"

Errors may be returned during modeling when Oracle BPEL Process Analytics is attempting to get information or write to the Oracle BPEL Process Analytics repository. Examples of such errors are the following:

```
500 Internal Server Error
oracle.tip.bam.common.BAMException: Error -: BAM-60111: Failed to add Star
LoanFlowTut to Tian Metadata
```

```
500 Internal Server Error
oracle.tip.bam.common.BAMException: Informational -: BAM-60153: Failed to get
a add a new dimension: CarModel
```

To work around this problem, open the `sqlnet.ora` file in the `BPA_HOME/NETWORK/ADMIN` directory (where `BPA_Home` is the directory specification for the Oracle home where Oracle BPEL Process Analytics is installed) and change the authentication services from NTS to NONE, as follows:

To work around this problem, open the `sqlnet.ora` file in the `BPA_HOME/network/admin` directory (where `BPA_Home` is the directory specification for the Oracle home where Oracle BPEL Process Analytics is installed) and change the authentication services from NTS to NONE, as follows:

```
SQLNET.AUTHENTICATION_SERVICES=(NONE)
```

You must restart the server after modifying the `sqlnet.ora` file.

13.1.21 Parentheses Needed In KPI Creation Wizard

The Create KPI Wizard enables you to create dimensional constraints with multiple logical operators (OR and AND). However, using multiple logical operators is meaningless unless the priority of these operators can be specified also. For example, to apply a dimensional constraint that specifies "either Nissan and Star Loan or Ford and United Loan", you can specify a dimensional constraint such as the following:

```
CarModel.CarModelID = 'Nissan' AND LoanProvider.LoanProviderID = 'Star loan'  
OR CarModel.CarModelID = 'Ford' AND LoanProvider.LoanProviderID = 'United loan'
```

Because the Oracle BPEL Process Analytics parser does not know the priority of the AND and OR operators, it might start parsing from either the right or left and therefore return meaningless results. Therefore, for this release, you should not specify multiple logical operators in a dimensional constraint.

To work around this problem, use parentheses `'()'` in the KPI creation wizard. For example, you can specify the previous example as follows:

```
(CarModel.CarModelID = 'Nissan' AND LoanProvider.LoanProviderID = 'Star loan' )  
OR (CarModel.CarModelID = 'Ford' AND LoanProvider.LoanProviderID = 'United loan' )
```

13.2 Known Problems

This section describes known problems. It includes the following topics:

- [Section 13.2.1, "Count Aggregation Cannot Be Applied on Duration, Currency, and Percent"](#)
- [Section 13.2.2, "Alerts Not Filtered Out According to the User-Selected Time Frame"](#)
- [Section 13.2.3, "KPI Constructed On Dimensionsless Composite Event Is Improperly Displayed"](#)
- [Section 13.2.4, "Option To See The Dashboard Pages Based on the Time Zone Not Available"](#)
- [Section 13.2.5, "Delete Event Icon Does Not Work in Update Composite Event"](#)
- [Section 13.2.6, "Sensor Cannot Handle Multiple Variables"](#)
- [Section 13.2.7, "Cannot Reinstall Oracle BPEL Process Analytics After Grid Control Agent Is Installed and Configured"](#)

13.2.1 Count Aggregation Cannot Be Applied on Duration, Currency, and Percent

In the Create KPI Wizard, an aggregation type of Count cannot be applied to Duration, Currency, or Percent KPI value types because no meaningful KPIs can be formed with this combination of aggregation type and value types. However, the interface currently does not disable the Duration, Currency, or Percent KPI value types when the Count aggregation type is selected.

13.2.2 Alerts Not Filtered Out According to the User-Selected Time Frame

An Alert View panel in the Dashboard currently shows all alerts, regardless of the time window (Year, Quarter, Month, or Day) you have selected for the Dashboard page. For

example, suppose you select a time window of Day for a Dashboard page that contains an Alert view panel. You might expect the Alert View panel to display only alerts that occurred during the current day. However, this is currently not the case. If 1000 alerts have occurred (and have not been deleted), then 1000 alerts will be displayed in the Alert view panel, regardless of when they occurred.

13.2.3 KPI Constructed On Dimensionsless Composite Event Is Improperly Displayed

When you construct a KPI on a composite event that has no dimensions defined, those KPIs should be disabled when you are constructing a Dashboard chart with dimensions. However, you can create such a Dashboard chart, which may result in the Dashboard presenting the wrong data at run time.

For example, if you perform the following steps, the Admin Console will allow you to construct a KPI view pane that displays KPI data based on a dimensional constraint even if the KPI is based on a composite event for which no dimension has been defined:

1. Create two Composite Events, one with dimension and the other without a dimension defined.
2. Create a KPI on each composite event.
3. Assign both KPIs to a user.
4. Create a KPI view pane with a snapshot bar chart that includes both KPIs.
5. In the last page of the Create KPI View Pane wizard, specify a dimensional constraint.

13.2.4 Option To See The Dashboard Pages Based on the Time Zone Not Available

KPI aggregation is performed on a daily basis, meaning for a 24 hour time slot. Events arriving within this 24 hour time slot are aggregated to determine the KPI value. This 24 hour time slot is, by default, based on the server time zone. However the exact 24 hour time slots for different countries may be different.

For example, suppose there is a KPI named "CountLoanOffer" and on 20th April 2005 India standard time (IST) this KPI has a value of 36. If you consider the United States time window for 20th April 2005, however, the KPI may have a different value.

13.2.5 Delete Event Icon Does Not Work in Update Composite Event

If you create a composite event and then try to update the same composite event to delete an existing event, you will find that although an icon is provided to do so, it is disabled.

13.2.6 Sensor Cannot Handle Multiple Variables

Currently, Oracle BPEL Process Analytics requires that, at most, one activity variable sensor be defined for each Oracle BPEL Process Manager activity sensor.

13.2.7 Cannot Reinstall Oracle BPEL Process Analytics After Grid Control Agent Is Installed and Configured

If you install Oracle BPEL Process Analytics in an Oracle Application Server middle tier home and then install and configure Oracle Enterprise Manager Grid control agent, you cannot reinstall Oracle BPEL Process Analytics into the same middle tier home (even if you first deinstall Oracle Enterprise Manager Grid control agent.)

If you attempt to do so, an ADMN-705021 error is returned.

The only workaround to this problem is to reinstall Oracle BPEL Process Analytics in a new Oracle Application Server middle tier home.

13.3 Documentation Errata

The *Oracle BPEL Process Analytics Installation Guide*, which has not been updated for this release, directs you to run the integration repository creation assistant (IRCA) as one of the preinstallation tasks. For this release, this step is no longer required. Instead, you should do one of the following, depending on the type of database you plan to use with Oracle BPEL Process Analytics as follows:

- If you plan to use the Oracle Database that is installed with Oracle Application Server, then you should install the Oracle Application Server Infrastructure. See *Oracle Application Server Installation Guide* for the operating system you are using for details.
- If you plan to use a standalone database, then you should use Oracle Application Server Metadata Repository Creation Assistant (RepCA) to install the Oracle Application Server Metadata Repository into that database. See *Oracle Application Server Metadata Repository Creation Assistant User's Guide* for details.

Oracle Application Server Integration B2B

This chapter describes issues associated with Oracle Application Server Integration B2B (OracleAS Integration B2B). It includes the following topics:

- [Section 14.1, "General Issues and Workarounds"](#)
- [Section 14.2, "Installation Issues and Workarounds"](#)
- [Section 14.3, "Documentation Errata"](#)

14.1 General Issues and Workarounds

This section describes general issues and workarounds. It includes the following topics:

- [Section 14.1.1, "Redeployment Issue"](#)
- [Section 14.1.2, "Purging Removes Instance Data"](#)
- [Section 14.1.3, "Self-service API for Creating Trading Partners and Agreements"](#)
- [Section 14.1.4, "Oracle Application Server Clustering and Integration B2B"](#)
- [Section 14.1.5, "B2B User Login Must Have a Role"](#)
- [Section 14.1.6, "Cannot Update the admin User Password"](#)
- [Section 14.1.7, "OracleAS Integration B2B Pages in Oracle Enterprise Manager"](#)
- [Section 14.1.8, "Configuring OracleAS Integration B2B in Enterprise Environments"](#)

14.1.1 Redeployment Issue

If you see that redeployment does not reflect your design-time data changes (for example, a change in the XPath expression is not recognized), restart the B2B server as follows:

```
opmnctl restartproc process-type=B2BServer
```

14.1.2 Purging Removes Instance Data

Purging a retired configuration removes the associated run-time data. Oracle recommends that you do a database archive of run-time data before purging.

14.1.3 Self-service API for Creating Trading Partners and Agreements

Only *creating* trading partners and agreements is supported, not updating or deleting. Also, RosettaNet collaborations are not supported in this API.

14.1.4 Oracle Application Server Clustering and Integration B2B

Oracle Application Server Integration B2B cannot be installed on a clustered application server middle-tier environment. Also, after you install Oracle Application Server Integration B2B on a middle tier, you cannot add it as a node on a cluster.

14.1.5 B2B User Login Must Have a Role

Logging in as the b2b user, without first assigning a role to the b2b user, produces a blank page. You must first log in as `admin` and assign a role to the b2b user. Then the b2b user can log in, with functionality based on the assigned role.

14.1.6 Cannot Update the admin User Password

You cannot update the password for the predefined `admin` user. Instead, create a new user and assign it the `Administrator` role. You can update the password for this new user.

14.1.7 OracleAS Integration B2B Pages in Oracle Enterprise Manager

If you are using OracleAS Integration B2B in a non-English language, note that parts of some OracleAS Integration B2B pages in Oracle Enterprise Manager 10g Application Server Control appear only in English.

14.1.8 Configuring OracleAS Integration B2B in Enterprise Environments

In a typical Oracle Application Server environment, the Oracle Application Server middle tier with its installations of J2EE and Web Cache and OracleAS Integration B2B communicates with the OracleAS Infrastructure tier and its installation of the OracleAS Metadata Repository.

You can also configure OracleAS Integration B2B to run in enterprise environments. Enterprise environments are slightly different than the typical Oracle Application Server environment in that they include an additional middle tier known as a web tier that is installed and configured outside your corporate network. The web tier includes the J2EE and Web Cache install type. However, there is no installation of OracleAS Integration B2B and no applications are deployed on the web tier. The web tier is used only to exchange HTTP requests (through the Oracle HTTP Server) with the Oracle Application Server middle tier (and its installations of J2EE and Web Cache and OracleAS Integration B2B). The Oracle Application Server middle tier, in turn, communicates with the OracleAS Infrastructure tier and its installation of the OracleAS Metadata Repository.

To use OracleAS Integration B2B in enterprise environments with a web tier, you must perform the following configuration tasks:

On the Oracle Application Server middle tier (with its installations of J2EE and Web Cache and OracleAS Integration B2B):

1. Go to the `ORACLE_HOME/opmn/conf` directory.
2. Use a text editor to open `opmn.xml`.
3. Find the entry for `OC4J_B2B`.

4. Change the range of AJP Ports from 3301-3400 to 3301-3301.

This enables OC4J_B2B to run on just one AJP port.

5. Save your changes.

On the web tier (with its installation of only J2EE and Web Cache):

1. Go to the `ORACLE_HOME/Apache/Apache/conf` directory.
2. Use a text editor to open `mod_oc4j.conf`.
3. Add the following entries near the end of the file, but before the `</IfModule>` line. These entries enable AJP routing to communicate with the configured OC4J_B2B:

```
oc4jMount /b2b ajp13://hostname:ajpport
oc4jMount /b2b/* ajp13://hostname:ajpport
```

where:

- `hostname` is the name of the host on which the Oracle Application Server middle tier is installed
 - `ajpport` is the AJP port range that you configured on the Oracle Application Server middle tier
4. Save your changes.

See Also: *Oracle Application Server Integration B2B Installation Guide* for additional instructions on configuring a web tier (and its Oracle HTTP Server) outside your corporate network

14.2 Installation Issues and Workarounds

This section describes installation issues and workarounds. It includes the following topics:

- [Section 14.2.1, "Enable Secure Socket Layer When the Midtier Instance is Registered to Oracle Internet Directory"](#)
- [Section 14.2.2, "Installing OracleAS Integration B2B on a Red Hat Enterprise Linux 2.1 Update5 System"](#)

14.2.1 Enable Secure Socket Layer When the Midtier Instance is Registered to Oracle Internet Directory

If secure socket layer (SSL) is not enabled on Oracle Internet Directory (OID) but the J2EE midtier instance is registered to OID (through manual configuration), then OracleAS Integration B2B installation fails.

14.2.2 Installing OracleAS Integration B2B on a Red Hat Enterprise Linux 2.1 Update5 System

If you are installing OracleAS Integration B2B on a Red Hat Enterprise Linux 2.1 Update5 system, the OPMN Configuration Assistant may fail because it cannot start up HTTP_Server. This is due to an issue in Update5 that will be fixed in Update6 (within the e.57 kernel). The workaround to get around this failure in Update5 is the following:

1. Check if orphaned httpd processes are left behind by executing the following command:

```
$ ps -efw | grep your_j2ee_oracle_home/Apache
```

This should return processes where the parent process id is 1, similar to the following:

```
oracle 4973 1 0 Jan05 ? 0:00:00
/project1/j2ee/ohome/Apache/Apache/bin/httpd
```

2. If there are orphaned httpd processes, get the pid of those processes and kill them using the following command:

```
$ kill -9 pid
```

Go back to the Oracle Universal Installer (OUI) installation session and click **Retry** to retry the OPMN Configuration Assistant.

14.3 Documentation Errata

This section describes known errors in the documentation. It includes the following topics:

- [Section 14.3.1, "User's Guide Documentation"](#)
- [Section 14.3.2, "Installation Documentation"](#)

14.3.1 User's Guide Documentation

This section describes corrections and clarifications to *Oracle Application Server Integration B2B User's Guide*, 10g Release 2 (10.1.2.0.2), part number B19370-01.

Chapter: 3, "Supported Protocols" (supp_protos.htm)

Heading: "Document Protocols"

Page: online version

The first paragraph in this section should read as follows:

The document protocol defines the document type of the message payload. Business protocols can have multiple document protocols. Document protocols follow the hierarchy shown in *Figure 3-1*.

Chapter: 11, "Managing Callouts" (callouts.htm)

Heading: "Tutorial: Adding Callout Usages to the RosettaNet over the Internet Transaction"

Page: 11-16 and online version

The first paragraph in this section should read as follows:

This tutorial assumes you have completed *the tutorial* described in "Tutorial 1: Setting Up a RosettaNet over the Internet Transaction."

Chapter: 11, "Managing Callouts" (callouts.htm)

Heading: "Tutorial: Adding Callout Usages to the RosettaNet over the Internet Transaction"

Page: 11-17 and online version

This procedure has a missing step without which the tutorial does not work.

For the sending party server (Acme in the example), the remote trading partner (GlobalChips in the example) must have a Trading Partner Identifier - EDI Location Code set as PARTY_SITE_ID (3101 - as in the example) in the enqueued message on the ECXMSG queue. This does not have to be selected in the agreement; however, it must be set for the remote trading partner. Without the preceding Trading Partner Identifier, the enqueued OAG PO message cannot find the to-party information.

14.3.2 Installation Documentation

This section describes corrections and clarifications to *Oracle Application Server Integration B2B Installation Guide*.

None.

Oracle Application Server Integration InterConnect

This chapter describes the issues related to Oracle Application Server Integration InterConnect (OracleAS Integration InterConnect). This chapter contains the following topics:

- [Section 15.1, "General Issues and Workarounds"](#)
- [Section 15.2, "Installation Issues and Workarounds"](#)
- [Section 15.3, "Documentation Errata"](#)

15.1 General Issues and Workarounds

This section describes the following general issues:

- [Section 15.1.1, "Adapters Duplicate the Messages During Failover on Real Application Cluster \(RAC\) or Cold Failover Cluster \(CFC\) Environment"](#)
- [Section 15.1.2, "JCA adapter Does Not Support High Availability"](#)

15.1.1 Adapters Duplicate the Messages During Failover on Real Application Cluster (RAC) or Cold Failover Cluster (CFC) Environment

If your AQ adapter and the database adapter are configured to use the RAC database or the CFC database for high availability, then during the failover of the adapters from primary instance to the secondary instance, the message which is being processed at the time of failover will get duplicated.

Example: You send 100 messages from the AQ adapter. The Database adapter is subscribing to these messages. If the primary instance of the database fails while processing the thirtieth message, then the adapters successfully fail over to the secondary instance, but in the process, duplicate the thirtieth message. As a result, the subscribing adapter ends up subscribing to the thirtieth message twice and the total number of messages would be 101.

15.1.2 JCA adapter Does Not Support High Availability

In Oracle Application Server Integration InterConnect release 10.1.2.0.2, the JCA adapter does not support high availability functionality.

15.2 Installation Issues and Workarounds

This section describes the installation issues and workarounds for OracleAS Integration InterConnect. It contains the following topics:

- [Section 15.2.1, "Make Utility at /bin/make is Required for Hub Installation on Linux"](#)

15.2.1 Make Utility at /bin/make is Required for Hub Installation on Linux

Problem

Usually, on Linux, the path of make is not `/bin/make` but `/usr/bin/make`. However, Oracle Universal Installer (OUI) looks for make in the `/bin` directory. This causes an error during installation.

Workaround

Before installing OracleAS Integration InterConnect on Linux, ensure that `/bin/make` exists. If it does not exist, then make a soft link from `/usr/bin/make`. Run the `ln -s /bin/make /usr/bin/make` command as root.

15.3 Documentation Errata

This section describes known errors and omissions in Oracle Application Server Integration InterConnect documentation.

15.3.1 Documentation Errors

This section describes the following known errors in the Oracle Application Server Integration InterConnect documentation.

- [Section 15.3.1.1, "Incorrect Release Number"](#)

15.3.1.1 Incorrect Release Number

Appendix A "Upgrading Oracle Application Server Integration InterConnect" of *Oracle Application Server Integration InterConnect Installation Guide* contains incorrect release number. The release number 10.1.2.0.1 in the appendix should read as 10.1.2.0.0.

15.3.2 Additional Documentation

This section describes following known additions to the Oracle Application Server Integration InterConnect documentation.

- [Section 15.3.2.1, "Configuring the InterConnect JCA adapter for use with DB2 and Sybase Database"](#)
- [Section 15.3.2.2, "Application Name value in the oc4j-ra.xml File"](#)

15.3.2.1 Configuring the InterConnect JCA adapter for use with DB2 and Sybase Database

The section 2.3 "Configuring the JCA Adapter" of the *Oracle Application Server Integration InterConnect Adapter for JCA Installation and User's Guide* is missing the subsection "Configuring the InterConnect JCA adapter for use with DB2 and Sybase Database." This subsection should be read as follows:

You can connect to an external database in the following ways:

- By using the DataDirect drivers (provided by Oracle)
- By using the drivers provided by specific vendors

DB2 Configuration

This section explains how to configure the JCA adapter, for use with the DB2 database, by using the following drivers:

- [DataDirect Driver](#)
- [Net Driver](#)

DataDirect Driver If using the DataDirect driver, then perform the following steps:

1. In the `classpath` variable of the `Start` file, specify the path of the following files:

- `YMbase.jar`
- `YMoc4j.jar`
- `YMutil.jar`
- `YMdb2.jar`

For example:

```
java -server -Dadapter=dbapp -DORBDisableLocator=true -ms${INITIAL_MEMORY}m
-mx${MAX_MEMORY}m -classpath
:/private1/hsrirama/Ora1012/integration/interconnect/lib/YMbase.jar:/private1/h
srirama/Ora1012/lib/YMoc4j.jar:/private1/hsrirama/Ora1012/lib/YMutil.jar:/priva
te1/hsrirama/Ora1012/lib/YMdb2.jar
```

2. Specify the driver class name in the `Start` file of the JCA adapter.

```
DriverClassName=com.oracle.ias.jdbc.db2.DB2Driver
```

3. Specify the database URL in the `Start` file of the JCA adapter:

```
ConnectionString=jdbc:oracle:db2://144.23.214.118:50001;DatabaseName=TOPLINK;Pa
ckageName=JDBCPKG; CreateDefaultPackage=TRUE;ReplacePackage=TRUE
```

For example:

```
connection1_name=eis/DB/DB2Connection
connection1_mcf_class=oracle.tip.adapter.db.DBManagedConnectionFactory
connection1_mcf_
params={ConnectionString=jdbc:oracle:db2://144.23.214.118:50001;DatabaseName=TOPLI
NK;PackageName=JDBCPKG; CreateDefaultPackage=TRUE;ReplacePackage=TRUE,
DriverClassName=com.oracle.ias.jdbc.db2.DB2Driver, Username=testuser,
Password=testpassword,
platformClassName=oracle.toplink.internal.databaseaccess.DB2Platform}
```

Net Driver If using the Net driver, then perform the following steps:

1. In the `classpath` variable of the `Start` file, specify the path of the following files:

- `db2java_81.zip`
- `db2jcc_81.jar`

For example:

```
java -server -Dadapter=dbapp -DORBDisableLocator=true -ms${INITIAL_MEMORY}m  
-mx${MAX_MEMORY}m -classpath  
:/private1/hsrirama/Ora1012/integration/interconnect/lib/db2java_  
81.zip:/private1/hsrirama/Ora1012/lib/db2jcc_81.jar
```

2. Specify the driver class name in the Start file of the JCA adapter.

```
DriverClassName=COM.ibm.db2.jdbc.net.DB2Driver
```

3. Specify the database URL in the Start file of the JCA adapter:

```
ConnectionString=jdbc:db2:144.23.214.118:TOPLINK,  
DriverClassName=COM.ibm.db2.jdbc.net.DB2Driver, Username=testuser,  
Password=testpassword,  
platformClassName=oracle.toplink.internal.databaseaccess.DB2Platform
```

For example:

```
connection1_name=eis/DB/DB2Connection  
connection1_mcf_class=oracle.tip.adapter.db.DBManagedConnectionFactory  
connection1_mcf_params={ConnectionString=jdbc:db2:144.23.214.118:TOPLINK,  
DriverClassName=COM.ibm.db2.jdbc.net.DB2Driver, Username=testuser,  
Password=testpassword,  
platformClassName=oracle.toplink.internal.databaseaccess.DB2Platform}
```

Sybase Configuration

This section explains how to configure the JCA adapter, for use with the Sybase database, by using the following drivers:

- [DataDirect Driver](#)
- [Jconn Driver](#)

DataDirect Driver If using the DataDirect driver, then perform the following steps:

1. In the classpath variable of the Start file, specify the path of the following files:
 - YMbase.jar
 - YMoc4j.jar
 - YMutil.jar
 - YMsybase.jar

For example:

```
java -server -Dadapter=dbapp -DORBDisableLocator=true -ms${INITIAL_MEMORY}m  
-mx${MAX_MEMORY}m -classpath  
:/private1/hsrirama/Ora1012/integration/interconnect/lib/YMbase.jar:/private1/h  
srirama/Ora1012/lib/YMoc4j.jar:/private1/hsrirama/Ora1012/lib/YMutil.jar:/priva  
te1/hsrirama/Ora1012/lib/YMsybase.jar
```

2. Specify the driver class name in the Start file of the JCA adapter.

```
DriverClassName=com.oracle.ias.jdbc.sybase.SybaseDriver
```

3. Specify the database URL in the Start file of the JCA adapter:

```
ConnectionString=jdbc:oracle:sybase://144.23.214.104:5001;DriverClassName=com.o  
racle.ias.jdbc.sybase.SybaseDriver, Username=testuser, Password=testpassword,  
platformClassName=oracle.toplink.internal.databaseaccess.DatabasePlatform
```


For example:

```
connection1_name=eis/DB/SybaseConnection
connection1_mcf_class=oracle.tip.adapter.db.DBManagedConnectionFactory
connection1_mcf_params={ConnectionString=jdbc:oracle:sybase://144.23.214.104:5001,
DriverClassName=com.oracle.ias.jdbc.sybase.SybaseDriver, Username=testuser,
Password=testpassword,
platformClassName=oracle.toplink.internal.databaseaccess.DatabasePlatform}
```

Jconn Driver If using the Jconn driver, then perform the following steps:

1. In the classpath variable of the Start file, specify the path of the jconn2.jar file.

For example:

```
java -server -Dadapter=dbapp -DORBDisableLocator=true -ms${INITIAL_MEMORY}m
-mx${MAX_MEMORY}m -classpath
:/private1/hsrirama/Ora1012/integration/interconnect/lib/jconn2.jar
```

2. Specify the driver class name in the Start file of the JCA adapter.

```
DriverClassName=com.sybase.jdbc2.jdbc.SybDriver
```

3. Specify the database URL in the Start file of the JCA adapter:

```
ConnectionString=jdbc:sybase:Tds:144.23.214.104:5001/TestUser;DriverClassName=c
om.sybase.jdbc2.jdbc.SybDriver, Username=testuser, Password=testpassword,
platformClassName=oracle.toplink.internal.databaseaccess.DatabasePlatform
```

For example:

```
connection1_name=eis/DB/DB2Connection
connection1_mcf_class=oracle.tip.adapter.db.DBManagedConnectionFactory
connection1_mcf_
params={ConnectionString=jdbc:sybase:Tds:144.23.214.104:5001/TestUser,
DriverClassName=com.sybase.jdbc2.jdbc.SybDriver, Username=testuser,
Password=testpassword,
platformClassName=oracle.toplink.internal.databaseaccess.DatabasePlatform}
```

15.3.2.2 Application Name value in the oc4j-ra.xml File

The section A.3 "Configuration" of the *Oracle Application Server Integration InterConnect User's Guide* has incomplete information in "The name of the application" step. This step should read as follows:

- The name of the application.

```
<config-property name="applicationName" value="BPEServer"/>
```

Note: Application name in the oc4j-ra.xml file should be similar to the application name in iStudio.

Oracle Application Server Web Cache

This chapter describes the issues associated with Oracle Application Server Web Cache (OracleAS Web Cache). It includes the following topic:

- [Section 16.1, "Configuration Issues and Workarounds"](#)

16.1 Configuration Issues and Workarounds

This section describes configuration issues and their workarounds for OracleAS Web Cache. It includes the following topic:

- [Section 16.1.1, "Patch Available for Configuring OracleAS Web Cache Solely as a Software Load Balancer or Reverse Proxy"](#)
- [Section 16.1.2, "Reloading Issue with Cache Operations Success Message in OracleAS Web Cache Manager with Internet Explorer Browser"](#)

16.1.1 Patch Available for Configuring OracleAS Web Cache Solely as a Software Load Balancer or Reverse Proxy

In previous releases, you could configure OracleAS Web Cache solely as a software load balancer or reverse proxy in place of hardware load balancers.

By applying a patch to this release, you can now configure OracleAS Web Cache as software load balancer or reverse proxy even in front of an application using Edge Side Includes (ESI) or in front of another OracleAS Web Cache forming a cache hierarchy. A typical OracleAS Portal deployment, for example, has a built-in OracleAS Web Cache used for ESI assembly.

To use OracleAS Web Cache in this mode, download an Automated Release Update (ARU) for bug 4569559 from *OracleMetalink*:

<http://metalink.oracle.com>

See Also: Section "OracleAS Web Cache Solely as a Software Load Balancer or Reverse Proxy" in Chapter 8, "Setup and Configuration," of the *Oracle Application Server Web Cache Administrator's Guide*

16.1.2 Reloading Issue with Cache Operations Success Message in OracleAS Web Cache Manager with Internet Explorer Browser

When you submit a successful operation in the Cache Operations page (**Operations** and then **Cache Operations**) in OracleAS Web Cache Manager, a Success message box appears. When you click **OK** to acknowledge the message, on versions of Internet

Explorer running on Macintosh, the Success dialog box reloads the OracleAS Web Cache Manager interface into the message box itself.

Oracle Business Intelligence

This chapter describes issues associated with Oracle Business Intelligence. It includes the following topics:

- [Section 17.1, "General Issues and Workarounds"](#)
- [Section 17.2, "Oracle Business Intelligence Discoverer Plus Relational"](#)
- [Section 17.3, "Oracle Business Intelligence Discoverer Plus OLAP"](#)
- [Section 17.4, "Oracle Business Intelligence Discoverer Portlet Provider"](#)
- [Section 17.5, "Oracle Business Intelligence Discoverer Viewer"](#)
- [Section 17.6, "Oracle Business Intelligence Discoverer EUL Command Line for Java"](#)
- [Section 17.7, "Known Issues with Oracle OLAP Option"](#)

17.1 General Issues and Workarounds

This section describes general issues and workarounds for Oracle Business Intelligence products. It contains the following topics:

- [Section 17.1.1, "Certification Information"](#)
- [Section 17.1.2, "Availability of HWOnline Files"](#)
- [Section 17.1.3, "Obtaining Patch Set for GUID-Generation Issue"](#)
- [Section 17.1.4, "Issues with Metadata Repository and Oracle Database 10g Release 1"](#)
- [Section 17.1.5, "Clarification of Version Numbers"](#)
- [Section 17.1.6, "Compatibility Issues with Required Support Files"](#)
- [Section 17.1.7, "Resizing Issue with Mozilla and Firefox Browsers"](#)
- [Section 17.1.8, "Serif Font Issue in Worksheets"](#)
- [Section 17.1.9, "Additional Fonts Required for Non-ASCII Data When Exporting to PDF"](#)
- [Section 17.1.10, "Query Prediction Requires the Majority of the Query Time"](#)
- [Section 17.1.11, "Issue When Drilling to Detail on Page Item Set to <ALL>"](#)
- [Section 17.1.12, "Date Format in OracleBI Discoverer Plus and OracleBI Discoverer Viewer"](#)

- [Section 17.1.13, "Word Wrapping Behavior with OracleBI Discoverer Plus and OracleBI Discoverer Viewer"](#)
- [Section 17.1.14, "Applet Appears Behind Browser Window"](#)
- [Section 17.1.15, "Issues with Mac OS X Browser and OracleBI Discoverer Plus"](#)
- [Section 17.1.16, "Welcome Page Displays Only in English"](#)
- [Section 17.1.17, "Issues with Turkish Regional Settings"](#)
- [Section 17.1.18, "Help Files in Non-English Languages"](#)
- [Section 17.1.19, "New User Preferences Added"](#)
- [Section 17.1.20, "Correction to Oracle Business Intelligence Installation Guide"](#)
- [Section 17.1.21, "Corrections to the OracleBI Discoverer Connections Help"](#)
- [Section 17.1.22, "Corrections to the Oracle Business Intelligence Discoverer Configuration Guide"](#)
- [Section 17.1.23, "Corrections to Oracle Enterprise Manager 10g Application Server Control Discoverer Help"](#)
- [Section 17.1.24, "Discoverer Communication Protocol Does Not Get Upgraded Correctly from 9.0.4 to 10.1.2.0.2"](#)
- [Section 17.1.25, "Corrections to Oracle Business Intelligence Discoverer Publishing Workbooks in OracleAS Portal"](#)

17.1.1 Certification Information

For the latest certification information, which supersedes that in the Oracle Business Intelligence documentation, refer to Oracle*Metalink* at the following location:

<http://metalink.oracle.com>

17.1.2 Availability of HWOOnline Files

Previous versions of Oracle Business Intelligence Discoverer shipped with the files `HWOonline.htm` and `Memo.doc`, which were used to demonstrate *drill out* functionality. To reduce disk space requirements and installation time, these files and instructions for their use will be made available from Oracle Technology Network:

http://www.oracle.com/technology/sample_code/products/discoverer/index.html

17.1.3 Obtaining Patch Set for GUID-Generation Issue

In addition to performing the steps that are described in the installation guide, you must install patch set 4628714 to resolve a Globally Unique ID (GUID) generation issue with the Discoverer Catalog. Patch set 4628714 is available from Oracle*Metalink* at the following location:

<http://metalink.oracle.com>

17.1.4 Issues with Metadata Repository and Oracle Database 10g Release 1

When using Oracle Database 10g Release 1 (10.1.x) for the Metadata Repository or after upgrading the Metadata Repository to Oracle Database 10g Release 1, you might see the following error on the OracleBI Discoverer Plus Connection pages, the OracleBI

Discoverer Viewer Connection pages, and the Public Connection definition page in Application Server Control:

```
The connection list is currently unavailable.
ORA-06510: PL/SQL: unhandled user-defined exception
ORA-06512: at "ORASSO.WWSSO_API_PRIVATE," line 258
ORA-06510: PL/SQL: unhandled user-defined exception
ORA-06512: at "ORASSO.WWSSO_UTL" line 728
ORA-28231: no data passed to obfuscation toolkit
ORA-06512: at line 1 Unable to retrieve connection list
```

You will see the same problem with external applications on the server that hosts Oracle Application Server Single Sign-On.

To resolve this issue, make the following changes in the Metadata Repository database:

1. Edit the `init%ORACLE_SID%.ora` file in the following location:
`DB_install_home/dbs`
2. Add the following line to this file:
`event="10946 trace name context forever, level 36"`
3. If an `spfile%ORACLE_SID%.ora` exists in either the `dbs` folder or the database folder, rename the file to `spfile%ORACLE_SID%.bak`. Changes to `init%ORACLE_SID%.ora` are not loaded if the database server finds an `spfile`.
4. Log in as a sysadmin.
5. At the SQL prompt, shut down then start up the database server.
6. Restart the OracleBI Discoverer server using the command `opmnctl restartall`.

17.1.5 Clarification of Version Numbers

Oracle Business Intelligence documentation (for example, *Oracle Business Intelligence Discoverer Plus User's Guide*) has the version number 10.1.2.1, which covers the following installations:

- Oracle Application Server 10g Release 2 (10.1.2.0.2) Business Intelligence and Forms install type.
- Oracle Business Intelligence 10g Release 2 (10.1.2.0.2).

Oracle Business Intelligence version 10.1.2.0.2 ships with Oracle Application Server version 10.1.2.0.2. The Oracle Business Intelligence components (e.g. OracleBI Discoverer Plus) and their documentation (for example, *Oracle Business Intelligence Discoverer Plus User's Guide*) that are part of Oracle Business Intelligence 10.1.2.0.2 have a version number of 10.1.2.1 to indicate that they are changed from 10.1.2.0.0.

17.1.6 Compatibility Issues with Required Support Files

The Oracle Database and other Oracle database client software (for example, SQL*Plus, the database export utility) use Oracle Required Support Files (RSF).

Oracle Business Intelligence also uses Oracle Required Support Files (RSF), specifically RSF version 10.1.0.4. This version of the Oracle Required Support Files is installed during Oracle Business Intelligence installation.

Note that the Required Support Files version 10.1.0.4 is incompatible with earlier versions of Oracle Database 10g. So if the machine on which you install Oracle Business Intelligence already has a version of Oracle Database 10g or database client

software that is earlier than 10.1.0.4, there will be compatibility issues. For example, if you install Oracle Business Intelligence and attempt to run a version of SQL*Plus earlier than 10.1.0.4, then the following error is displayed:

```
ORA-12557 TNS: protocol adapter not loadable
```

To avoid the compatibility issues, upgrade Oracle Database 10g or database client software on the machine to the same version (that is, 10.1.0.4) as the version of the Required Support Files that were installed with Oracle Business Intelligence.

This issue does not exist for Oracle9i Database Server.

17.1.7 Resizing Issue with Mozilla and Firefox Browsers

When you use Oracle Business Intelligence Discoverer Plus Relational or Oracle Business Intelligence Discoverer Plus OLAP with Mozilla and Firefox browsers (version 1.5 and later) and you resize the browser window, the browser can freeze and might crash the applet intermittently. This issue is caused by the following bugs in the Sun Java Runtime Engine: 4836462 and 5076485.

To work around this issue, do not resize the applet window or use a different browser, such as Internet Explorer.

17.1.8 Serif Font Issue in Worksheets

You might notice unsightly font issues when using a non-English locale such as Czech. For example, when a worksheet uses a serif font, text in that worksheet might be displayed incorrectly on the screen and in printouts.

To work around this issue, update the file that maps the serif fonts. The name of this file differs depending on the locale in use. When you use OracleBI Discoverer Plus Relational or Plus OLAP in English, the file is named `file.properties`. If you use Oracle Business Intelligence Discoverer Plus in a non-English locale, then the file name includes the code for the locale, such as `file.properties.cs` for Czech.

Update the mapping file with the following information:

```
serif.0=Times New Roman,EASTEUROPE_CHARSET  
serif.1=WingDings,SYMBOL_CHARSET,NEED_CONVERTED  
serif.2=Symbol,SYMBOL_CHARSET,NEED_CONVERTED
```

Refer to the following Sun Web site for additional information about fonts:

<http://java.sun.com/j2se/1.3/docs/guide/intl/addingfonts.html>

17.1.9 Additional Fonts Required for Non-ASCII Data When Exporting to PDF

If you are running OracleBI Discoverer Plus Relational or Plus OLAP on a Macintosh or Linux client machine, you must add the appropriate font files to your client machine to allow exported PDF files to display non-ASCII data correctly.

These font files include Albany fonts with names such as `ALBANWTJ.TTF` and `ALBANWTK.TTF`. The files are stored in the `/utilities/fonts` directory on the CD-ROM or DVD for the Oracle Application Server Metadata Repository Upgrade Assistant.

To install the additional required fonts:

1. Navigate to the `/utilities/fonts` directory on the CD-ROM or DVD for the OracleAS Metadata Repository Upgrade Assistant.

2. Copy the appropriate Albany TTF file from the `/utilities/fonts` directory to the plug-in directory in the `$jdk/jre/lib/fonts` directory on the Macintosh or Linux client machine.

17.1.10 Query Prediction Requires the Majority of the Query Time

When using Oracle Business Intelligence Discoverer with a relational data source, you can predict the time that is required to retrieve information by setting the value of the `QPPEnable` preference to 1. However, in some circumstances, the majority of the time taken to retrieve information will be consumed by the prediction activity itself.

To work around this issue, set the value of the `QPPObtainCostMethod` preference to 0 (use the `EXPLAIN PLAN` statement to predict query times), rather than to 1 (use dynamic views to predict query times).

For more information about setting preferences, refer to the *Oracle Business Intelligence Discoverer Configuration Guide*.

17.1.11 Issue When Drilling to Detail on Page Item Set to <ALL>

In OracleBI Discoverer Plus Relational and OracleBI Discoverer Viewer when displaying a relational worksheet, you might encounter a known issue when drilling to detail on a page item that has been set to `<ALL>`. In this case, no data is retrieved.

17.1.12 Date Format in OracleBI Discoverer Plus and OracleBI Discoverer Viewer

Due to a known bug, OracleBI Discoverer displays a date value incorrectly in a worksheet if the URL parameter `NLS_DATE_FORMAT=` is used to display that worksheet.

For example, the database might contain a `sale_date` value of 01-NOV-2005 03:53:12. You create a worksheet in OracleBI Discoverer Plus with a date column for the `sale_date` item, which is displayed correctly. If you then display that worksheet using the `NLS_DATE_FORMAT=` parameter set to a value such as the following one:

```
http://<hostname>:<port>/discoverer/plus?@cn=us_a103&NLS_DATE_FORMAT=YYYY-MM-DD%20HH24:MI:SS)
```

then OracleBI Discoverer displays the incorrect value 2005-11-01 00:00:00, instead of the correct value 2005-11-01 03:53:12.

This issue will be addressed in an upcoming Oracle Business Intelligence patch release.

17.1.13 Word Wrapping Behavior with OracleBI Discoverer Plus and OracleBI Discoverer Viewer

To use word wrap settings correctly, you must understand how they are designed for Oracle Business Intelligence Discoverer:

- For OracleBI Discoverer Plus: Word wrap settings that you make in OracleBI Discoverer Plus are saved in the worksheet and affect the display of worksheets in OracleBI Discoverer Plus and when printing to PDF.
- For OracleBI Discoverer Viewer: Word wrap settings that you see in the Print Settings dialog work as follows:
 - The word wrap settings do not affect the display of worksheets in OracleBI Discoverer Viewer.

- For relational data:
 - * The word wrap settings do affect the printing of worksheets to PDF.
 - * If the **Always wrap text when size exceeds column width** box is checked, then the print settings in OracleBI Discoverer Viewer do override the settings made in a worksheet in OracleBI Discoverer Plus Relational for printing to PDF.
 - * If the **Always wrap text when size exceeds column width** box is not checked, then the print settings in OracleBI Discoverer Viewer do not override the settings made in a worksheet in OracleBI Discoverer Plus Relational for printing to PDF.
- For OLAP data:
 - * The word wrap settings do not affect the printing of worksheets to PDF.
 - * Regardless of whether the **Always wrap text when size exceeds column width** box is checked or unchecked, the print settings in OracleBI Discoverer Viewer never override the settings made in a worksheet in OracleBI Discoverer Plus OLAP for printing to PDF.

17.1.14 Applet Appears Behind Browser Window

When you use Microsoft Internet Explorer, the OracleBI Discoverer Plus Relational or Plus OLAP applet initialization and download dialog appears behind the browser window from which it was launched. After the OracleBI Discoverer Plus applet is downloaded and initialized, it will appear in front of the browser window from which it was launched.

To work around this issue:

- Use a browser other than Internet Explorer, such as Netscape Navigator or Mozilla Firefox.
- Use the OracleBI Discoverer Plus URL parameter `_plus_popup=false` that is documented in the *Oracle Business Intelligence Discoverer Configuration Guide*.

17.1.15 Issues with Mac OS X Browser and OracleBI Discoverer Plus

The following list describes issues when you use the Safari browser on Mac OS X with the OracleBI Discoverer Plus Relational or Plus OLAP applet:

- If you resize the browser window in the applet, then some parts of the content might be clipped. To work around this problem, always maximize the browser window for the applet when working with Mac OS X.
- Keyboard combinations (also known as mnemonics) do not work in OracleBI Discoverer Plus Relational and Plus OLAP. For example, you cannot press Alt+F to access the File menu.
- In the Share Workbooks dialog of OracleBI Discoverer Plus Relational, the leading characters of the "Shared:" list are clipped. In other words, the left edge of the list is truncated. For example, if you shared a workbook with "DISCODEV", then you will only see "SCODEV" in the list. The title for the list is also truncated such that you see only the vertical line of the "d" in "Shared" and the colon (e.g. "l:").

The dialog continues to work as expected, but you might have difficulty reading the names in the "Shared:" list. This issue has no workaround.

17.1.16 Welcome Page Displays Only in English

The Welcome page is not displayed in the correct locale as specified in the browser. You will see the Welcome page displayed in English regardless of the language setting in the browser.

To work around this issue:

1. Navigate to the `Apache/Apache/htdocs` directory on the Oracle Business Intelligence middle tier machine.
 - a. Rename the `index.html.html` file to `index.html.html-old`.
 - b. Rename the `index.html` file to `index.html.html`.
2. In the Web browser, clear the browser cache and refresh the Welcome page.

17.1.17 Issues with Turkish Regional Settings

Because of Sun JRE 1.4 bug 4688797, you might encounter issues when connecting to a database schema while your computer has Turkish regional settings. You will encounter the issue when you attempt to connect to a database schema with a user name that contains certain letters, such as the letter 'T' or 'i', for example, in "bibdemo". See the Sun JRE bug for information on the letters that are affected.

To work around this issue, either do not use Turkish regional settings or use a user name that does not contain the affected letters.

17.1.18 Help Files in Non-English Languages

Section 4.7.1 of the *Oracle Business Intelligence Installation Guide* describes how to install translated Help files for OracleBI Discoverer Plus Relational or Plus OLAP after installation. That section explains that the OracleBI Discoverer Plus Help files are available as JAR files in the `/extras` directory on the CD-ROM and DVD for Oracle Business Intelligence.

The `/extras` directory does not exist on the CD-ROM or DVD for this release. You can locate a ZIP file that contains all translated JAR files from the following location on Oracle Technology Network (<http://www.oracle.com/technology/documentation/discoverer.html>)

Once you obtain the JAR files from Oracle Technology Network, you can use the instructions in the *Oracle Business Intelligence Installation Guide* for installing the translated Help.

17.1.19 New User Preferences Added

New user preferences have been included, as described in the following table. These preferences should appear in Section 10.6, "List of Discoverer preferences" in the *Oracle Business Intelligence Discoverer Configuration Guide*.

Table 17–1 New User Preferences

Name	Category	Description	Default Value	Valid Values
CSVIgnoreCarriageReturn	Application	Specifies whether OracleBI Discoverer Plus includes carriage return characters (i.e. /r) at the end of lines when a worksheet is exported to CSV format. When this preference is set to 0, OracleBI Discoverer Plus includes only a line feed (LF) character. When this preference is set to 1, OracleBI Discoverer Plus includes a carriage return (CR) character followed by a line feed (LF) character.	0	0 = Include only a LF code. 1 = Include a CR code followed by a LF code.
RewriteCostComparison	Database	Specifies whether OracleBI Discoverer compares the execution cost of using plain SQL and summary SQL, and automatically uses the most efficient SQL type. For example, you might turn off RewriteCostComparison (i.e. set it to 0) if you want users to always query against summary data (e.g. created yesterday) even though this might be slower than querying the latest data.	1	0 = Always use summary SQL. 1 = Use the most efficient SQL type.
OptimizeComplexFolders	Database	Specifies whether OracleBI Discoverer uses optimized SQL for complex folders, to improve performance. For example, you might turn on OptimizeComplexFolders (i.e. set it to 1) if you have complex folders that affect OracleBI Discoverer performance by making the Worksheet Wizard slow to use.	0	0 = Do not use optimized SQL for complex folders. 1 = Do use optimized SQL for complex folders.
UseNoRewriteHint	Database	Specifies whether OracleBI Discoverer adds the NOREWRITE hint to the SQL. For example, you might turn on UseNoRewriteHint (i.e. set it to 1) if you want users to always query against the latest data (e.g. created today), even though this might be slower than querying the summary data (e.g. created yesterday). The NO_REWRITE hint instructs the optimizer to disable query rewrite for the query block, which overrides the setting of the parameter QUERY_REWRITE_ENABLED.	0	0 = Do not add the NOREWRITE hint. 1 = Do add the NOREWRITE hint.

17.1.20 Correction to Oracle Business Intelligence Installation Guide

This section identifies changes to *Oracle Business Intelligence Installation Guide*.

- Section 2.3 of the *Oracle Business Intelligence Installation Guide* describes the database requirements for Oracle Business Intelligence. The section should read as follows:

Oracle Business Intelligence 10.1.2.1 supports the following versions for the database that contains the data on which you want to report:

- Oracle9i Release 2 Database (9.2.0.6 and higher)
- Oracle Database 10g Release 1 (10.1.0.4 and higher)
- Oracle Database 10g Release 2 (10.2.0.1 and higher); certification is planned

Note:

- When performing relational analysis, you can use Oracle Database Standard Edition or Oracle Database Enterprise Edition. You must use Oracle Database Enterprise Edition if you want to take advantage of materialized views, analytic functions, and the Advanced Security Option (ASO) and Transparent Application Failover (TAF) database features.
 - When performing multidimensional analysis, you must use Oracle Database Enterprise Edition with the OLAP Option.
-

The latest information on supported versions is on the Certify application on <http://metalink.oracle.com>.

- In Section 4.7 "What to do next" of the *Oracle Business Intelligence Installation Guide*, ignore the bulleted item that begins with the following text: "type the following URL in a Web browser:

`http://<host.domain>:<port>/quicktour/index.htm"`

17.1.21 Corrections to the OracleBI Discoverer Connections Help

This section provides information about corrections to the OracleBI Discoverer Connections Help. It contains the following topics:

- [Section 17.1.21.1, "Account Details: Enter Password page Help topic"](#)
- [Section 17.1.21.2, "Account Details: Select Responsibility page Help topic"](#)
- [Section 17.1.21.3, "Connect to OracleBI Discoverer page Help topic"](#)
- [Section 17.1.21.4, "Account Details: Username and Password page Help topic"](#)
- [Section 17.1.21.5, "Account Details: Select Username page Help topic"](#)
- [Section 17.1.21.6, "Enter connection details page Help topic"](#)

17.1.21.1 Account Details: Enter Password page Help topic

This Help topic is incorrectly called the Create Connection: Enter Password page, when it should be called the Account Details: Enter Password page.

17.1.21.2 Account Details: Select Responsibility page Help topic

This Help topic is incorrectly called the Select Applications Responsibility for Discoverer connection page, when it should be called the Account Details: Select Responsibility page.

17.1.21.3 Connect to OracleBI Discoverer page Help topic

- The Create Connection button should have the following additional text as a note:
"The Create Connection button will be disabled if the OracleBI Discoverer manager specifies (in Application Server Control) that end users cannot create private connections."
- Disregard the note and the bullet points underneath the Password field.

17.1.21.4 Account Details: Username and Password page Help topic

Disregard this Help topic.

17.1.21.5 Account Details: Select Username page Help topic

Disregard this Help topic.

17.1.21.6 Enter connection details page Help topic

Disregard the note and the bullet points underneath the **Password** field.

17.1.22 Corrections to the Oracle Business Intelligence Discoverer Configuration Guide

This section provides information about corrections to the *Oracle Business Intelligence Discoverer Configuration Guide*. The following list summarizes the corrections required:

- Section 6.7 "URL parameters for the Discoverer Plus OLAP Servlet" contains Table 6-1. The table requires the following corrections:
 - password= is not a valid URL parameter. For security reasons, OracleBI Discoverer end users are always prompted for a password. A password can only be supplied in a HTTP Post method.
 - workbookname= should be qualified with the directory path in the Discoverer Catalog. You must prefix folder names, workbook names, and worksheet names with a forward slash character / (or the URL encoded forward slash character value %2F). For example, to specify Workbook A stored in the Users/Jchan/ area in the Discoverer Catalog, enter &workbookname=Users/JChan/Workbook+A.

If you are deploying OracleBI Discoverer in a non-Single Sign-On environment, then you must specify lm=OLAP in the URL.

- Section 6.8 "URL parameters for an OLAP worksheet in Discoverer Viewer" contains Table 6-2. In that table, note that the URL parameter worksheetname= is case-sensitive and should be worksheetName=.

If you are deploying OracleBI Discoverer in a non-Single Sign-On environment, then you must specify lm=OLAP in the URL.

- Section 8.4 incorrectly states that the caching rules that OracleBI Discoverer requires are automatically configured when you install Oracle Business Intelligence.

After installing Oracle Business Intelligence, you must manually specify caching rules, as described in section 8.5.1 "How to create Discoverer caching rules".

- Section 8.5.1 describes how to create Discoverer caching rules. Add the following steps after the current Step 8 in that section:
 - a. Display the Advanced Caching Instructions tab.

- b. Add the User-Agent header to the list of selected headers.
 - c. Click **Apply**.
- Section 15.1 "About Discoverer connections and Oracle e-Business Suite", disregard the last bullet point in the notes section that begins 'If you have already connected to the database using SSO...'
- Disregard the whole of Section 15.2 "About Discoverer private connections, OracleAS Single Sign-On and Oracle e-Business Suite users".
- In Appendix A.1 "List of Discoverer file locations", disregard the entry for `migratediscoconnection.sh` script.
- In Appendix A.2 "List of configuration settings in configuration.xml", disregard the `enableAppsSSO` setting.
- Section D.1.9 describes an issue displaying the OracleBI Discoverer Plus Relational Help when using the Sun Java Plug-in. The solution for changing the proxy settings for the Sun Java Plug-in should be written as follows:
 - a. On the client browser machine, display the dialog in which you specify proxy settings.

For example, in Microsoft Internet Explorer, from the Tools menu, choose Internet Options, Connections, LAN Settings, then Advanced to display the Proxy Settings dialog.
 - b. Ensure that the **Exceptions** field contains the following string:

`*.oraclecorp.com`
 - c. Click **OK** to save the changes.
 - d. Start a new client browser session and start OracleBI Discoverer Plus.
- Section 7.6.4 "How to disable the Preferences component on a machine" contains text in Step 3 that describes how to change the `Disco_PreferenceServer` entry from enabled to disabled. Append the following text to the instructions in Step 3:

After the `<process-type id="SessionServer" module-id="Disco_SessionServer" status="enabled">` tag, include the following tags:


```
<process-set id="SessionServer" minprocs="0" maxprocs="50"
restart-on-death="false" parallel-requests="true">
<module-data> <category id="start-parameters">

<data id="dis51ws-extra-options" value="-preferenceHost
<hostname of remote preference>" />
```


For example, to use the Preference Server on machine 138.2.150.44, enter the following information in the data tag:


```
<data id="dis51ws-extra-options" value="-preferenceHost
138.2.150.44" />
```

17.1.23 Corrections to Oracle Enterprise Manager 10g Application Server Control Discoverer Help

This section provides information about corrections to Oracle Enterprise Manager 10g Application Server Control (Application Server Control) Discoverer Help. It contains the following topics:

- [Section 17.1.23.1, "Discoverer Administration page Help topic"](#)

- [Section 17.1.23.2, "Discoverer Configuration page Help topic"](#)
- [Section 17.1.23.3, "Install Catalog page Help topic"](#)
- [Section 17.1.23.4, "Log in to Manage Catalog page Help topic"](#)
- [Section 17.1.23.5, "Uninstall Catalog page Help topic"](#)
- [Section 17.1.23.6, "Discoverer Plus Configuration page Help topic"](#)
- [Section 17.1.23.7, "Discoverer Portlet Provider Configuration page Help topic"](#)
- [Section 17.1.23.8, "Discoverer Administration page Help topic"](#)

17.1.23.1 Discoverer Administration page Help topic

The Discoverer Administration page Help topic should be amended as follows:

"Links to Install Catalog, Uninstall Catalog, and Manage Catalog on the OracleBI Discoverer Administration page Help topic should be called Install, Uninstall, and Manage, respectively."

17.1.23.2 Discoverer Configuration page Help topic

The Discoverer Configuration page Help topic should be amended as follows:

- The Viewer Delay Times area has the following two new fields:
 - **Query Request Timeout** (seconds)
The time to wait before OracleBI Discoverer displays the Query Progress page.
 - **Long Request Timeout** (seconds)
The time to wait before OracleBI Discoverer displays the Query Progress page for long queries.

17.1.23.3 Install Catalog page Help topic

This Help topic is incorrectly called the Discoverer Install Catalog page, when it should be called the Install Catalog page.

17.1.23.4 Log in to Manage Catalog page Help topic

This Help topic is incorrectly called the Discoverer Log in to Manage Catalog page, when it should be called the Log in to Manage Catalog page.

17.1.23.5 Uninstall Catalog page Help topic

This Help topic is incorrectly called the Discoverer Uninstall Catalog page, when it should be called the Uninstall Catalog page.

17.1.23.6 Discoverer Plus Configuration page Help topic

The Discoverer Plus Configuration page Help topic should be amended as follows:

- The **Default (Oracle Logo)** radio button should be changed to say **None** and its description should be as follows:
Use this radio button to avoid displaying a logo in OracleBI Discoverer Plus Relational and OracleBI Discoverer Plus OLAP.

17.1.23.7 Discoverer Portlet Provider Configuration page Help topic

The Discoverer Portlet Provider Configuration page Help topic should be amended as follows:

- The Discoverer Session Pool heading should be changed to Discoverer Session.
- The **Portlet Generic Parameters** field should be changed to the **Maximum Generic parameters** field.
- The **Maximum Sessions** field description should include the following text as note:

This value must be equal to or less than the value of the maxprocs setting in opmn.xml (for more information, see the *Oracle Business Intelligence Discoverer Configuration Guide* section entitled "List of configuration settings in opmn.xml").

17.1.23.8 Discoverer Administration page Help topic

The Discoverer Administration Help topic should be amended as follows:

- Disregard the section "Connect to SSO-enabled Oracle Applications database" that contains the **Allow authenticated OracleAS Single Sign-On (SSO) users to create and use private connections to SSO-enabled Oracle Applications databases, without entering a password** check box.

17.1.24 Discoverer Communication Protocol Does Not Get Upgraded Correctly from 9.0.4 to 10.1.2.0.2

If you set the Discoverer communication setting to Secure Tunnelling in a Business Intelligence 9.0.4 installation, then the same setting is not imported when you upgrade to Business Intelligence 10.1.2..0.2. The setting is set as Default. To resolve this issue, you need to explicitly set the communication protocol from Default to Secure Tunnelling using the Enterprise Manager main page.

17.1.25 Corrections to Oracle Business Intelligence Discoverer Publishing Workbooks in OracleAS Portal

This section provides information about corrections and additions to *Oracle Business Intelligence Discoverer Publishing Workbooks in OracleAS Portal*.

17.1.25.1 Corrections and additions to section 'How to copy Discoverer connections from one Oracle Business Intelligence installation to another'

This section contains corrections and additions to the section 'How to copy Discoverer connections from one Oracle Business Intelligence installation to another', in Chapter 2 (page 2-18 in a printed or PDF copy).

When you copy OracleBI Discoverer connections from one Oracle Business Intelligence installation to another, note the following:

- OracleAS Single Sign-On user accounts that are deployed on the source installation must be re-created on the target installation. You create OracleAS Single Sign-On users in the Administration tab - User area in OracleAS Portal (for more information, see OracleAS Portal Help).
- You must copy the tnsnames.ora file from the source installation to the target installation. For example, you can copy the <ORACLE_HOME>/network/admin/tnsnames.ora file on the source installation to the

<ORACLE_HOME>/network/admin/tnsnames.ora file on the target installation.

- If you need to obtain the ORASSO login password for the source installation (for example, to export the ORASSO schema using the ssomig command), run the ldapsearch command on the source installation. If you export the ORASSO schema using the ssomig command with the ORASSO login password for the target installation, then the export will fail.
- If you need to obtain the ORASSO login password for the target installation (for example, to import the ORASSO schema using the ssomig command), run the ldapsearch command on the target installation. If you import the ORASSO schema using the ssomig command with the ORASSO login password for the source installation, then the import will fail.
- When you use the ldapsearch command to obtain the ORASSO login password for an installation (for example, to use in the ssomig command), use the following command syntax:

```
ldapsearch -D cn=orcladmin -w <superuser password> -p <port number> -h  
<Infrastructure hostname> -b "cn=IAS,cn=Products,cn=OracleContext" -s sub -v  
OrclresourceName=ORASSO | grep orclpasswordattribute
```

Where:

- <superuser password> is the password of the orcladmin user in Oracle Internet Directory (OID). By default, this is the same password as the ias_admin user password after a new Infrastructure installation.
- <port number> is the OID port number.

For example:

```
ldapsearch -D cn=orcladmin -w manager1 -p 389 -h  
hostname1.nl.oracle.com -b  
"cn=IAS,cn=Products,cn=OracleContext" -s sub -v  
OrclresourceName=ORASSO | grep orclpasswordattribute
```

The command returns a list of OID variables and values. To obtain the ORASSO login password, look for the value of the orclpasswordattribute variable.

- After you have exported the ORASSO schema (using the ssomig command), you must copy the ssomig.dmp file and the ssoconf.log file to the target installation. For example, you can copy the files from the <source installation directory name>/inf/sso/log directory on the source installation to the <target installation directory name>/inf/sso/log directory in the target installation.

17.2 Oracle Business Intelligence Discoverer Plus Relational

This section provides release notes for Oracle Business Intelligence Discoverer Plus Relational (OracleBI Discoverer Plus Relational). It contains the following topics:

- [Section 17.2.1, "Text Appearing Truncated or Clipped"](#)
- [Section 17.2.2, "Non-ASCII Characters Not Saved Correctly in Title or Text Area"](#)
- [Section 17.2.3, "Resizing in Mac OS X Browser"](#)
- [Section 17.2.4, "Corrections to the OracleBI Discoverer Plus Relational Help"](#)
- [Section 17.2.5, "Important Bug Fixes in this Release"](#)

- [Section 17.2.6, "Migrating OracleBI Discoverer Plus Relational Worksheets from OracleBI Discoverer Desktop"](#)
- [Section 17.2.7, "Issue When Canceling Running Query"](#)
- [Section 17.2.8, "Scheduled Workbooks and Aggregation in OracleBI Discoverer Plus Relational"](#)

17.2.1 Text Appearing Truncated or Clipped

When you run OracleBI Discoverer Plus Relational with Sun Java Plug-in 1.4.2_06, the Browser Look and Feel, and an Asian language (such as Japanese, Korean, or Chinese), you might notice that static text and text in buttons in the user interface appears truncated or clipped. To work around this issue, do one of the following:

- Change the Look and Feel to either Plastic or System.
- Use JInitiator 1.3.1.17 instead of the Sun Java Plug-in.
- Install Sun Java Plug-in 1.4.2_10, when it becomes available from Sun Microsystems.

17.2.2 Non-ASCII Characters Not Saved Correctly in Title or Text Area

When you save a new workbook in OracleBI Discoverer Plus, any text characters beyond the standard ASCII characters are not saved correctly when all the conditions that are described in the following list are met:

- You are logged in as an Oracle E-Business suite user.
- The language for the computer is not English.
- OracleBI Discoverer Plus is running against an Oracle E-Business database that does not have that non-English language installed.

This issue has no workaround.

17.2.3 Resizing in Mac OS X Browser

With Mac OS X, if you resize the browser window in the OracleBI Discoverer Plus applet, then some parts of the content might be clipped. This issue is specific to Mac OS X. To work around this problem, always maximize the browser window for the OracleBI Discoverer Plus applet when working with Mac OS X.

17.2.4 Corrections to the OracleBI Discoverer Plus Relational Help

This section provides information about corrections to OracleBI Discoverer Plus Relational Help. It contains the following topics:

- [Section 17.2.4.1, "References to the Connect to Discoverer Plus page Help topic"](#)
- [Section 17.2.4.2, "Task steps in the How do I create and save login information in a Discoverer connection Help topic"](#)
- [Section 17.2.4.3, "Task steps in the How to remove sorting from a worksheet Help topic"](#)

17.2.4.1 References to the Connect to Discoverer Plus page Help topic

The OracleBI Discoverer Plus Help topics contain a number of references to the Connect to Discoverer Plus page. Each reference to the Connect to Discoverer Plus page should instead refer to the Connect to OracleBI Discoverer page.

17.2.4.2 Task steps in the How do I create and save login information in a Discoverer connection Help topic

This Discoverer Plus Help topic should be amended as follows:

- Disregard the note in Step 7.
- Disregard the note in Step 8.
- Disregard Step 9 entirely.

17.2.4.3 Task steps in the How to remove sorting from a worksheet Help topic

Step 2 in this OracleBI Discoverer Plus Relational Help topic should be reworded as follows:

2. Choose Tools | Sort to display the "Edit Worksheet dialog: Sort tab" or "Sort Crosstab dialog" (depending on the type of worksheet displayed).

17.2.5 Important Bug Fixes in this Release

The following important bugs were fixed in this release:

- In previous releases, you could not automatically open exported files with non-ASCII file names; that is, file names that used Asian characters (for example, Japanese language characters).
- In previous releases, you could not specify and save the paper size for printing in the Page Setup dialog of OracleBI Discoverer Plus.

17.2.6 Migrating OracleBI Discoverer Plus Relational Worksheets from OracleBI Discoverer Desktop

If you use OracleBI Discoverer Plus Relational to open a worksheet that was created using OracleBI Discoverer Desktop Version 9.0.4 (or earlier), the size of the title area for that worksheet defaults to two lines in height. A title height of two lines might be a problem if a worksheet title requires more than or less than two lines. If you want to change the size of the title area, then you must manually resize the title area and save the worksheet.

To resize the title area for a worksheet, open the worksheet and drag the bar at the bottom of the title area pane up or down.

17.2.7 Issue When Canceling Running Query

If you cancel a query that is running in OracleBI Discoverer Plus Relational, then you are prompted to either choose YES to undo the changes or NO to show a blank sheet. If you choose YES, then OracleBI Discoverer Plus Relational hangs and you must close the window and restart. To work around this issue, choose NO to show a blank worksheet. You can then refresh the sheet and continue working.

17.2.8 Scheduled Workbooks and Aggregation in OracleBI Discoverer Plus Relational

OracleBI Discoverer Plus Relational does not display non-aggregable values for scheduled workbooks. In other words, OracleBI Discoverer Plus Relational processes scheduled workbooks as if you selected the "Show values that cannot be aggregated as: <Non-aggregable label>" option on the "Worksheet Properties dialog: Aggregation tab".

Non-aggregable values include those based on the following SQL functions:

- A CASE SQL statement
- A DECODE SQL statement
- A PL/SQL function
- A DISTINCT SQL statement
- An analytic function

17.3 Oracle Business Intelligence Discoverer Plus OLAP

This section provides release notes for Oracle Business Intelligence Discoverer Plus OLAP (OracleBI Discoverer Plus OLAP). It contains the following topics:

- [Section 17.3.1, "Issues with Applet Download"](#)
- [Section 17.3.2, "Disabled Netscape and Mozilla Browsers"](#)
- [Section 17.3.3, "Tabbing Fails to Synchronize Menus"](#)
- [Section 17.3.4, "ESC Key Fails to Close Certain Dialogs"](#)
- [Section 17.3.5, "Link Tool Works Incorrectly in Some Locales"](#)
- [Section 17.3.6, "Memory Issues when Exporting Extremely Large Graphs"](#)
- [Section 17.3.7, "Page Setup Dialog Appearing Blank"](#)
- [Section 17.3.8, "Printing Worksheets with Large Data Values"](#)
- [Section 17.3.9, "Issues with Titles and Text Areas"](#)
- [Section 17.3.10, "Issue Moving Worksheets While Opening the First Workbook"](#)
- [Section 17.3.11, "Errors with JAWS and Format Dialogs"](#)
- [Section 17.3.12, "Issue Exporting Discoverer Catalog with Non-ASCII Data"](#)
- [Section 17.3.13, "Corrections to the OracleBI Discoverer Plus OLAP Help"](#)

17.3.1 Issues with Applet Download

There may be Oracle Business Intelligence Discoverer Plus applet download issues when caching has been enabled in the Sun Java Plug-In. Disable caching in the plug-in to avoid this issue.

17.3.2 Disabled Netscape and Mozilla Browsers

When you are running Netscape 7.x or Mozilla browsers, the Netscape and Mozilla Mail clients and Web browser may become disabled when OracleBI Discoverer Plus OLAP modal dialogs are displayed. Dismissing the OracleBI Discoverer Plus OLAP dialog resumes normal operation for the Netscape and Mozilla tools.

17.3.3 Tabbing Fails to Synchronize Menus

When you use the tab key to select items in a worksheet, the menus do not always synchronize to reflect the currently selected item. This issue has no workaround.

17.3.4 ESC Key Fails to Close Certain Dialogs

The ESC key does not close the following dialogs: Totals, New Total, Parameter, and Manage Catalog. Instead of using the ESC key, click the Close or OK button.

17.3.5 Link Tool Works Incorrectly in Some Locales

The Link tool, which enables users to drill out to external URLs from a crosstab cell, may not work correctly in all locales due to URL encoding issues. This issue has no workaround.

17.3.6 Memory Issues when Exporting Extremely Large Graphs

Exporting extremely large graphs can cause memory issues, requiring a restart of the OracleBI Discoverer Plus OLAP session. This issue has no workaround.

17.3.7 Page Setup Dialog Appearing Blank

Reinvoking the Page Setup dialog from the Print dialog may cause the Page Setup dialog to be blank. This issue has no workaround.

17.3.8 Printing Worksheets with Large Data Values

When printing a worksheet that contains large numbers in the data cells, the string ##### may be printed instead of the actual numbers. This issue has no workaround.

17.3.9 Issues with Titles and Text Areas

The following issues exist with titles and text areas:

- Non-empty titles and text areas will be printed even if they are hidden in the worksheet. This issue has no workaround.
- When you set the title or text area background to green and export the worksheet to an HTML file, the background is incorrectly set to red in the exported file. This issue has no workaround.

17.3.10 Issue Moving Worksheets While Opening the First Workbook

If you open a workbook that contains multiple sheets and you move the visible sheet within the workbook, then the newly active worksheet displays with an empty or blank sheet. If you try to refresh the sheet to solve this problem, then the newly active sheet is not displayed and you see an error message about a NullPointerException.

To work around this issue, you can display the original sheet or any other sheet, then return to the sheet that displayed as blank. Alternatively, if you open or display all sheets before starting the move operation, then you can see the target sheet right after the move operation.

17.3.11 Errors with JAWS and Format Dialogs

When you use JAWS, you will notice errors when you attempt to format graphs and crosstabs using the Format dialogs. This issue has no workaround.

17.3.12 Issue Exporting Discoverer Catalog with Non-ASCII Data

The exported file may be incomplete or corrupt when exporting a Discoverer Catalog in which the name, contents, or data in a workbook contain non-ASCII characters.

To work around this issue, perform the export operation from the command line on the middle-tier server. Set parameters to force the export to use the UTF-8 character set as shown in the following command line syntax:

```
java -Dfile.encoding=UTF-8 -classpath d4o.jar
oracle.dss.d4o.administration.D4OCommand export -h <hostname>
-po <portnumber> -sid <sid> -p <D4OSYS password> -f <export xml
filename>
```

The D4OSYS password is D4OSYS by default.

17.3.13 Corrections to the OracleBI Discoverer Plus OLAP Help

This section provides information about corrections to the OracleBI Discoverer Plus OLAP Help. The following list summarizes the corrections required:

- In the "Variance calculation" topic, the formula for the calculation is incorrect. The correct formula is "Base-Target".
- In the "Percent variance calculation" topic, the formula for the calculation is incorrect. The correct formula is "(Base-Target)/Target".
- In the "Percent markup calculation" topic, the formula for the calculation is incorrect. The correct formula is "(From - Markup)/Markup".

17.4 Oracle Business Intelligence Discoverer Portlet Provider

This section provides release notes for OracleBI Discoverer Portlet Provider. It contains the following topics:

- [Section 17.4.1, "Inability to Turn Off Display of Range Min and Max as Labels"](#)
- [Section 17.4.2, "Using OracleBI Discoverer Portlet Provider with OracleAS Single Sign-On and Secure Sockets Layer \(SSL\) Modes"](#)
- [Section 17.4.3, "Documentation Corrections"](#)

17.4.1 Inability to Turn Off Display of Range Min and Max as Labels

In the Display Options of a gauge portlet, the **Minimum Value** and **Maximum Value** range labels are checked but are also disabled so that you cannot deselect the display of those values. The values for the minimum and the maximum will appear at the ends of every gauge in the set except for those gauges where the value to be gauged is out of the range of the minimum and the maximum values. For those gauges where the value to be displayed exceeds the range of the minimum and the maximum values, the gauge will automatically adjust to accommodate the value.

This issue has no workaround.

17.4.2 Using OracleBI Discoverer Portlet Provider with OracleAS Single Sign-On and Secure Sockets Layer (SSL) Modes

If you configure OracleBI Discoverer Portlet Provider to work with OracleAS Single Sign-On and SSL, then UIX images might not display correctly in OracleBI Discoverer. For example, on the Connect to OracleBI Discoverer page, the expand icon (i.e. the blue + symbol) in the Details column of the Discoverer connections list might not display correctly.

To address this issue, you need to manually update the `oc4j-properties` file on the Oracle Business Intelligence middle tier.

To manually update the `oc4j-properties` file for OracleBI Discoverer:

1. On the Oracle Business Intelligence middle tier machine, open the `oc4j-properties` file in a text editor.
For example, open `$ORACLE_HOME/j2ee/OC4J_BI_Forms/config/oc4j-properties`
2. Locate the line `'oracle.discoverer.applications.port='` and set the port number to the SSL (i.e. HTTPS) port number that you want to use. For example, change the line to `'oracle.discoverer.applications.port=4443'`.

Note: If the file does not contain a `'oracle.discoverer.applications.port='` line, append this line (including the appropriate SSL (i.e. HTTPS) port number) to the end of the file

3. Ensure the following line exists in the `oc4j-properties` file:
`oracle.discoverer.applications.protocol=https`

Note: If the file does not contain a `'oracle.discoverer.applications.protocol=https'` line, append this line to the end of the file.

4. Save the `oc4j-properties` file.
5. Restart the Oracle Application Server infrastructure and middle tier services.

17.4.3 Documentation Corrections

This section provides information about corrections to Help topics in OracleBI Discoverer Portlet Provider. It contains the following topics:

- [Section 17.4.3.1, "Refresh Options page Help topic"](#)
- [Section 17.4.3.2, "Review Portlet Defaults page Help topic"](#)
- [Section 17.4.3.3, "Select Database Connections page \(Customize mode\) Help topic"](#)
- [Section 17.4.3.4, "Database Connections page Help topic"](#)

17.4.3.1 Refresh Options page Help topic

In the Refresh Options page Help topic, the description of the First Refresh Date field reads as follows

Use this field to specify the date that the data in the portlet is first updated (DD-MON-YYYY). For example, enter 25-JAN-2005 to update the data on January 25th, 2005. Click the adjacent calendar icon to select a date using a graphical calendar.

The correct text is as follows:

Use this field to specify the date that the data in the portlet is first updated (DD-MM-YY). For example, enter 25/01/05 to update the data on January 25th, 2005. Click the adjacent calendar icon to select a date using a graphical calendar.

17.4.3.2 Review Portlet Defaults page Help topic

In the Review Portlet Defaults page Help topic, the description reads as follows:

When you are ready to save the portlet settings, click Apply.

The correct text reads is as follows:

When you are ready to save the portlet settings, click Finish. When you edit an existing portlet, you click Apply in the Review Portlet Defaults page.

17.4.3.3 Select Database Connections page (Customize mode) Help topic

In the description for the **User's Connection** field, append the following text:

As a user of Oracle Application Server Portal, you can only change the connection to one of the following:

- (for OLAP) a connection with the same database
- (for relational) a connection with the same database and End User Layer (EUL) combination

Note that changing the connection does not enable you to display a different worksheet in the portlet. However, changing the connection might result in different data being returned to the worksheet.

17.4.3.4 Database Connections page Help topic

Replace the text in the description for the **Display different data by allowing users to customize database connection** radio button with the following text:

Use this radio button when you want to enable authenticated users to go to the Customize page and change the connection. The ability to change the connection enables users to use the portlet by connecting with different login details. That is, the same worksheet will be displayed, but the data that is contained in the worksheet might be different because the underlying login details are different.

17.5 Oracle Business Intelligence Discoverer Viewer

This section provides release notes for Oracle Business Intelligence Discoverer Viewer (OracleBI Discoverer Viewer). It contains the following topics:

- [Section 17.5.1, "Drill Icons Cannot Be Hidden in OracleBI Discoverer Viewer"](#)
- [Section 17.5.2, "Error Sending E-mail in OracleBI Discoverer Viewer"](#)
- [Section 17.5.3, "Error Displaying Page for Multiple SSO Users"](#)
- [Section 17.5.4, "Inability to Disable the Display of Row Numbers"](#)
- [Section 17.5.5, "Issues with OracleBI Discoverer Viewer Embedded in Frames"](#)
- [Section 17.5.6, "Issue Exporting to PDF Under Certain Circumstances"](#)
- [Section 17.5.7, "Known Bug with JAWS Prevents Drilling using Enter Key"](#)
- [Section 17.5.8, "JAWS Does Not Read Asterisks that Precede Fields"](#)
- [Section 17.5.9, "Corrections to the OracleBI Discoverer Viewer Help"](#)
- [Section 17.5.10, "Discoverer Catalog Items Not Visible From UNIX Servers"](#)
- [Section 17.5.11, "OracleBI Discoverer Viewer Pages are not Cached by OracleAS Web Cache"](#)

17.5.1 Drill Icons Cannot Be Hidden in OracleBI Discoverer Viewer

The `pref.txt` file contains a setting called `ShowDrillIcon`, which is not functioning properly. If you set `ShowDrillIcon` to `False`, then drill icons are still displayed in OracleBI Discoverer Viewer. The issue has no workaround.

17.5.2 Error Sending E-mail in OracleBI Discoverer Viewer

After you configure an SMTP server that has a hyphen in the name (for example, `my-smtpserver.mycompany.com`) for OracleBI Discoverer Viewer in Application Server Control, users will see the following error message when they try to send e-mail from OracleBI Discoverer Viewer:

OracleBI Discoverer was unable to read the configuration file.
A value is required for the following expression
`my-smtpserver.mycompany.com`

The application log contains the following text:

ERROR: Invalid SMTP Server

To work around this issue, use the IP address of the server instead of the server name when configuring the SMTP server. This problem will be fixed in a future patch release.

17.5.3 Error Displaying Page for Multiple SSO Users

When an OracleAS Single Sign-On (SSO) user tries to view a worksheet from a List of Worksheets Portlet using the same browser window that is already being used by an SSO user to view that worksheet, the second user will see the following error message:

The page cannot be displayed.

To work around this issue, start a new browser session and view the worksheet.

17.5.4 Inability to Disable the Display of Row Numbers

OracleBI Discoverer Viewer no longer offers the ability to disable the display of row numbers in a tabular worksheet.

17.5.5 Issues with OracleBI Discoverer Viewer Embedded in Frames

Users might see JavaScript errors such as *Access Denied* or other unexpected behavior when both of the following conditions are met:

- When OracleBI Discoverer Viewer is embedded in an IFRAME tag.
- When the domain of the server that hosts the HTML page with the IFRAME tag is different from the domain of the OracleBI Discoverer server that is running OracleBI Discoverer Viewer.

Use one of the following workarounds for this issue:

- Run the OracleBI Discoverer server and the server that hosts the HTML page with the IFRAME tag in the same domain.
- Alter the `Common2_2_20.js` file on the OracleBI Discoverer server using the following steps:
 1. Use Application Server Control to stop all services on the middle tier for Oracle Business Intelligence.

2. Make a backup copy of the `Common2_2_20.js` file from the following directory:
`ORACLE_HOME/j2ee/OC4J_BI_Forms/applications/
discoverer/discoverer/cabo/jsLibs`
3. Edit the `Common2_2_20.js` file and replace all occurrences of `parent._pprSomeAction` with `window._pprSomeAction`.
4. Use Application Server Control to start all services on the middle tier for Oracle Business Intelligence.
5. Clear the browser cache on the client machine so that the new `Common2_2_20.js` file will be used.

17.5.6 Issue Exporting to PDF Under Certain Circumstances

If you are using OracleBI Discoverer Viewer with Microsoft Internet Explorer, you might encounter an error message when you try to export to PDF a worksheet that is named with non-ASCII characters, a space, and a number. The export fails and you will see a message similar to the following one:

No %PDF- in a file header

Use one of the following methods to work around this issue:

- Use a browser other than Internet Explorer, such as one from Netscape or Mozilla.
- Remove the space between the non-ASCII characters and the number, or remove the number altogether.
- Continue to use Internet Explorer and leave the space in the worksheet name, but follow these steps:
 1. Start the Adobe Reader.
 2. From the Edit menu, choose **Preferences**, then click **Internet**.
 3. Clear the **Display PDF in browser** box.

17.5.7 Known Bug with JAWS Prevents Drilling using Enter Key

OracleBI Discoverer can be used in conjunction with assistive technologies such as the JAWS screen reader. However, a bug in JAWS prevents drilling from working correctly in OracleBI Discoverer Viewer when querying a relational datasource, described as follows.

Assume you use the keyboard to navigate to the drill icon beside an item in the worksheet header. When you press the Enter key to drill on that header item, the Drill page should be displayed (as described in the "Worksheet Display page: (Page level tools and controls)" topic in the Help system and *Oracle Business Intelligence Discoverer Viewer User's Guide*).

However, when JAWS is running, the Drill page is not displayed. Instead, the Drill popup menu is displayed. It is not possible to select items from this popup menu using the keyboard, and JAWS does not read the items on the popup menu. This issue has no workaround.

17.5.8 JAWS Does Not Read Asterisks that Precede Fields

In OracleBI Discoverer Viewer, an asterisk that precedes a text field indicates that the user is required to enter a value into that text field. The JAWS screen reader does not

read an asterisk that precedes a required text field and does not otherwise indicate that the field is required. This issue has no workaround.

17.5.9 Corrections to the OracleBI Discoverer Viewer Help

This section provides information about corrections to OracleBI Discoverer Viewer Help. It contains the following topics:

- [Section 17.5.9.1, "References to the Connect to Discoverer Viewer page"](#)
- [Section 17.5.9.2, "List of Worksheets page Help topic"](#)
- [Section 17.5.9.3, "Printable Page Options page: Content Tab Help topic"](#)
- [Section 17.5.9.4, "Preferences page Help topic"](#)
- [Section 17.5.9.5, "Task steps in the "How do I create and save login information in a Discoverer connection?" Help topic"](#)

17.5.9.1 References to the Connect to Discoverer Viewer page

The OracleBI Discoverer Viewer Help contains a number of references to the Connect to Discoverer Viewer page. Each reference to the Connect to Discoverer Viewer page should instead refer to the Connect to OracleBI Discoverer page.

17.5.9.2 List of Worksheets page Help topic

The List of Worksheets page Help topic should display the following note:

When using a private connection or connecting directly, if you use the Web browser controls (refresh, back, and forward) to refresh or navigate to or from the Worksheet List page, then you might be disconnected. If this happens, then OracleBI Discoverer Viewer prompts you to re-connect. Use controls within the page for navigation and refreshing.

17.5.9.3 Printable Page Options page: Content Tab Help topic

This Help topic is incorrectly called the Printable Page Options page: Page Content tab, when it should be called the Printable Page Options page: Content tab.

17.5.9.4 Preferences page Help topic

The following changes should be made to this Help topic:

- The **Always, when available** field, and its description are duplicated and one should be removed.
- The **When summary data is more recent than nn days** field and its description should be removed.

17.5.9.5 Task steps in the "How do I create and save login information in a Discoverer connection?" Help topic

This Discoverer Viewer Help topic should be amended as follows:

- Disregard the note in Step 7.
- Disregard the note in Step 8.
- Disregard Step 9 entirely.

17.5.10 Discoverer Catalog Items Not Visible From UNIX Servers

You might encounter issues when trying to see items in the Discoverer Catalog when using OracleBI Discoverer Viewer with OLAP data on UNIX servers. You can resolve this issue on the middle tier machine where OracleBI Discoverer runs by performing the following steps.

To check whether the time zone variable is set:

1. Open a shell prompt.
2. Type `echo $TZ` to display the time zone setting.

If no value is displayed, then the time zone has not been set.

To set the time zone variable:

1. Open a shell prompt.

Note: The UNIX user that sets the TZ variable must be the same UNIX user that installed Oracle Business Intelligence.

2. If you do not know which shell you are using, type `$echo $SHELL` to display the name of the current shell.
3. Set the time zone as appropriate.

For example, to set the time zone variable for US/Pacific time:

- For the Bourne, Bash, or Korn shell, type `export TZ=US/Pacific`
- For the C shell, type `setenv TZ US/Pacific`

Note: Consult the shell documentation for the appropriate values.

17.5.11 OracleBI Discoverer Viewer Pages are not Cached by OracleAS Web Cache

When using OracleBI Discoverer with OracleAS Web Cache, note the following:

- When OracleAS Single Sign-On is enabled, OracleAS Web Cache does not cache OracleBI Discoverer Viewer pages, regardless of whether they are accessed using a public connection or a private connection.
- If an OracleBI Discoverer Viewer page is accessed directly via a URL and the URL contains URL parameters that specify login details (e.g. user name, database name), then OracleAS Web Cache will not cache the page. For example, OracleAS Web Cache will not cache worksheet Sheet 1 in workbook Workbook 2 that is displayed using the following URL:

```
http://<host.domain>:<port>/discoverer/viewer?us=video5&db=db
1&eul=VIDEO5&wbk=Workbook+2&ws=Sheet+1
```

Note: In the example above, `us=` specifies the database user name, and `db=` specifies the database name.

However, OracleAS Web Cache will cache worksheet Sheet 1 in workbook Workbook 2 if a user logs in manually to OracleBI Discoverer Viewer using the same login details, and navigates to this worksheet.

- You must increase the delays for OracleBI Discoverer Viewer by at least 60 seconds for OracleBI Discoverer Viewer to properly cache workbooks with OracleAS Web Cache. To set the delay time, perform the following steps:
 1. Display the Application Server Control Discoverer Home page.
 2. Select the Components link to display the Components area.
 3. In the Components area, in the Name column, select the OracleBI Discoverer Viewer link.
 4. Enter a value of 60 or greater in the Viewer Delay Times field.
 5. Choose OK to save the changes that you have made.

17.6 Oracle Business Intelligence Discoverer EUL Command Line for Java

This section provides release notes for Oracle Business Intelligence Discoverer EUL Command Line for Java (OracleBI Discoverer EUL Command Line for Java). It contains the following topics:

- [Section 17.6.1, "Issue with Exported Non-ASCII Data"](#)

17.6.1 Issue with Exported Non-ASCII Data

When you export multibyte or Eastern European data (such as the names of items and business areas in Japanese or Russian characters) from OracleBI Discoverer EUL Command Line for Java on a platform other than Windows, the exported data is corrupted.

To work around this issue, edit the `discwb.sh` file that is located in the `ORACLE_HOME/discoverer` directory before exporting. Change the character set value in the `NLS_LANG` variable to UTF8.

For example, if the original setting of the variable is:

```
NLS_LANG="GERMAN_GERMANY.WE8ISO8859P1"
```

then change the setting to read like so:

```
NLS_LANG="GERMAN_GERMANY.UTF8"
```

17.7 Known Issues with Oracle OLAP Option

This section describes some of the known issues with the Oracle OLAP option. These issues affect all products that access OLAP data, including OracleBI Discoverer Plus OLAP and OracleBI Discoverer Viewer.

- At times, database resources are not properly released in the Oracle9i (Release 2) OLAP option. This may result in excessive memory consumption. To release the resources, close OracleBI Discoverer Plus OLAP or OracleBI Discoverer Viewer.
- There are potential performance issues running against analytic workspaces in Oracle OLAP 10g Release 1 version 10.1.0.4. To work around these issues, always check *OracleMetalink* for the appropriate Oracle OLAP patches at the following location:.

<http://metalink.oracle.com>

Oracle Reports

This chapter describes issues with Oracle Reports. It includes the following topics:

- [Section 18.1, "General Issues and Workarounds"](#)
- [Section 18.2, "Vendor-Specific Issues and Workarounds"](#)
- [Section 18.3, "Globalization Support Issues and Workarounds"](#)

Note:

- Refer to the Oracle Reports 10g page on OTN, (<http://www.oracle.com/technology/products/reports/index.html>) for information about Oracle Reports, including a link to download the latest version of the *Oracle Reports online Help*
 - Your Oracle Application Server software ships with a standalone installation of Oracle Application Server Forms and Reports Services. Use this CD if you do not need all the functionality of the full Oracle Application Server installation. For more information, refer to the *Oracle Application Server Forms and Reports Services Installation Guide*, available on your Documentation CD. Refer also to the Oracle Reports Technical FAQ on OTN (http://www.oracle.com/technology/products/reports/htdocs/faq/faq_fr_services.htm) for frequently asked questions about OracleAS Forms and Reports Services installation.
-

18.1 General Issues and Workarounds

This section describes general issues and their workarounds for Oracle Reports. It includes the following topics:

- [Section 18.1.1, "Using the New Auto Save Feature in Reports Builder"](#)
- [Section 18.1.2, "OracleAS Reports Services Demos Will Not Work If JServ Is Configured"](#)
- [Section 18.1.3, "JSP Report Does Not Run in Oracle JDeveloper on UNIX"](#)
- [Section 18.1.4, "Error While Editing Batch Registered Report in OracleAS Portal"](#)
- [Section 18.1.5, "Limitation on Linked Queries for DelimitedData Output"](#)
- [Section 18.1.6, "Summary Column Not Aligned for JSP-Based Web Reports with Group Above and Matrix Style"](#)

- [Section 18.1.7, "Images in HTML Output of Oracle Reports Not Displayed When Viewed from Oracle Enterprise Manager 10g"](#)
- [Section 18.1.8, "Misalignment in Large Multibyte Reports When Using the Enhanced Font Subsetting Feature with Acrobat Reader 7.0"](#)
- [Section 18.1.9, "PL/SQL Compilation Failure When Using SQL Constructs"](#)
- [Section 18.1.10, "PL/SQL Package Specification and/or Body Lost When Saving Report As XML"](#)
- [Section 18.1.11, "Incorrect Color for Multiline Text in Paper Design View When Inline HTML Tags Are Used"](#)
- [Section 18.1.12, "Running Oracle Reports"](#)

18.1.1 Using the New Auto Save Feature in Reports Builder

Oracle Reports 10g Release 2 (10.1.2) introduces the Auto Save feature, which recovers unsaved changes in the case of an unexpected event of Reports Builder or system fail. When Auto Save is enabled, Reports Builder can automatically recover unsaved changes in open reports.

To enable the Auto Save functionality, you must perform the following steps:

1. In Reports Builder, select **Edit**, and then select **Preferences** to display the Preferences dialog box.
2. In the Preferences dialog box, on the **General** tab, select **Auto Save**.

Alternatively, you can enable the Auto Save functionality by modifying the `Reports.auto_save` property in the preferences file, `cauprefs.ora` for Windows `prefs.ora` for UNIX platforms. Modify the file as follows:

```
Reports.auto_save = [YES|NO]
DEFAULT: NO
```

Usage Notes

- When Auto Save is enabled, any modifications done in the reports that are open are saved automatically in temporary recovery files at various events originating from menu, toolbar, tool palette, object navigator, property inspector, and other editor windows in Reports Builder.
- For a new report definition, Auto Save is enabled only after the report is saved the first time.
- After you save your report, Reports Builder deletes the current recovery file. Even if you just recovered unsaved changes, Reports Builder deletes the recovery file when you save the report.
- The temporary recovery file is created and saved in `.rdf` format in the same location as that of the original definition file. The format of recovery files is `reportname_extension.rdf`. For example, the recovery file of an original definition file, `emp.jsp`, would be `emp_jsp.rdf`. The `emp_jsp.rdf` file is saved in the same location as the `emp.jsp` file.
- If you reopen a previously unsaved report definition file for which a recovery file exists, then Reports Builder prompts you to save the changes. The recovery file contains the changes made until the last Auto Save event. After the changes are recovered, you must select the **Save** or **Revert** option. The **Save** option writes the unsaved previous changes to the original report definition file. The **Revert** option

does not save the recovered changes. Reports Builder deletes the recovery file when you close the report.

- If an error occurs when autosaving the recovery file, then Reports Builder prompts you to disable Auto Save or continue with the error.

Note: When Auto Save is enabled, Reports Builder assumes that the recovery file contains changes made since the last save of the report definition file. Before you choose to save the recovery file, you must ensure that the recovery file contains your latest changes. If the original report definition file is a later version than the recovery file, then you can choose to revert to the original report definition, so that you do not overwrite it with the changes read from the recovery file.

18.1.2 OracleAS Reports Services Demos Will Not Work If JServ Is Configured

To run OracleAS Reports Services demos successfully, do not configure Apache JServ on the computer where OracleAS Reports Services is installed.

18.1.3 JSP Report Does Not Run in Oracle JDeveloper on UNIX

To run a JSP-based Web report in Oracle JDeveloper on UNIX, perform either of the following steps:

- For the in-process Reports Server, edit `ORACLE_HOME/jdev/bin/jdev` to include the path to `lib32`. Append the path of `lib32` to `LD_LIBRARY_PATH=ORACLE_HOME/lib`, as shown in the following example:

```
LD_LIBRARY_PATH=ORACLE_HOME/lib:ORACLE_HOME/lib32
```

Save and invoke Oracle JDeveloper.

- Use the standalone Reports Server to run JSP-based Web report in Oracle JDeveloper.

18.1.4 Error While Editing Batch Registered Report in OracleAS Portal

If you batch register a report in OracleAS Portal, then subsequently manually edit the report's registration in OracleAS Portal, you may encounter an unexpected Save As dialog box during the manual editing process.

To work around this issue, specify the Display Name property while editing the report's registration in OracleAS Portal.

Refer to the *Oracle Application Server Reports Services Publishing Reports to the Web* manual for information on how to register a report with OracleAS Portal.

18.1.5 Limitation on Linked Queries for DelimitedData Output

DelimitedData output does not allow multiple queries to be linked to the main query, because sibling groups are not supported.

For example:

Case 1: You have a link between Q1 and Q2, a link between Q2 and Q3, and a standalone Q4 query.

```
Q1<--->Q2<--->Q3          Q4
```

In this case, DelimitedData output is generated correctly.

Case 2: You have a link between Q1 and Q2, a link between Q2 and Q3, and a link between Q4 and Q1.

Q1<-->Q2<-->Q3 Q1<-->Q4

In this case, DelimitedData output is not generated correctly. Alternatively, you can use XML output.

18.1.6 Summary Column Not Aligned for JSP-Based Web Reports with Group Above and Matrix Style

If any summary column values are not correctly left-aligned in the output of JSP-based Web reports with a Group Above or Matrix style, you can implement the following workaround to get proper alignment:

- Open the JSP report in Reports Builder.
- Select the **Web Source** view.
- In the Web Source view, locate the section where the summary column is defined, and delete the following line to remove the extra space:

```
<th class="summary_column_name"> </th>
```

18.1.7 Images in HTML Output of Oracle Reports Not Displayed When Viewed from Oracle Enterprise Manager 10g

If OracleAS Web Cache is configured as SSL-enabled and Oracle HTTP Server is not, then the images in the HTML output of Oracle Reports is not displayed when viewed from Oracle Enterprise Manager 10g. This is because the image URLs mentioned in the HTML output points to OracleAS Web Cache ports, which are SSL-enabled, whereas the request for past job outputs of Oracle Reports from Oracle Enterprise Manager 10g is non-SSL.

To work around this issue, edit the Servlet property of the URL in the `targets.xml` file for Reports Server type such that it points to the OracleAS Web Cache port instead of the Oracle HTTP Server port. The `targets.xml` file is available at `ORACLE_HOME/sysman/emd` directory.

For example, if your OracleAS Web Cache is SSL-enabled and the listening port number is 443, then the Servlet property of the URL for the Reports Server target in the `targets.xml` file should be as shown in the following example:

```
<Target TYPE="oracle_repserv" ....>
.....
<Property NAME="Servlet" VALUE="https://xyz.mycompany.com:443/reports/rwservlet"/>
.....
</Target>
```

18.1.8 Misalignment in Large Multibyte Reports When Using the Enhanced Font Subsetting Feature with Acrobat Reader 7.0

If you use Acrobat Reader 7.0 to view multibyte and unicode PDF reports that use enhanced font subsetting feature (default) and the report size is very large, then some of the characters displayed will not be aligned properly.

To work around this issue, you can do either of the following:

- Set the environment variable `REPORTS_ENHANCED_SUBSET` to `NO` to revert to the Type 3 font subsetting implementation used in releases prior to Oracle Reports 10g Release 2 (10.1.2).
- Use Acrobat Reader 6.0 or earlier.

18.1.9 PL/SQL Compilation Failure When Using SQL Constructs

PL/SQL compilation may fail if you use SQL constructs in your reports and if the following conditions are present:

- The SQL constructs were introduced in Oracle Database versions after 9.0.1, for example, `ROW_NUMBER()`.
- The SQL constructs are used in client side PL/SQL procedures.

To work around this issue, you can do any of the following:

- Use Oracle Database Release 10.1.0.4 or later.
- Move those SQL constructs to the server-side stored procedures.
- Use the SQL constructs within SQL queries directly instead of procedures.

18.1.10 PL/SQL Package Specification and/or Body Lost When Saving Report As XML

For a report developed in a release prior to Oracle Reports 10g Release 2 (10.1.2) patch 2, you may encounter the following issue when saving the report in XML format: if the report defines a PL/SQL package, the package specification, and sometimes the body, is not saved in the XML report. To resolve this issue, perform either of the following steps:

- If the RDF exists, regenerate the XML output file using Oracle Reports 10g Release 2 (10.1.2) patch 2 or later.
- If the RDF does not exist, edit the XML manually to add `type="packageSpec"` and/or `type="packageBody"` to the function element, as shown in the following example:

```
<programUnits>
  <function name="a" type="packageSpec">
    <textSource>
      <![CDATA[
        PACKAGE a IS
          function lire return date ;
        END a;
      ]]>
    </textSource>
  </function>
  <function name="a" type="packageBody">
    <textSource>
      <![CDATA[
        PACKAGE BODY a IS
          function lire return date is
            c2 date;
          begin
            c2 :=sysdate;
            return c2;
          end;
        END;
      ]]>
    </textSource>
```

```
</function>
<function name="cf_1formula" returnType="date">
  <textSource>
    <![CDATA[
      function CF_1Formula return Date is
        aa date;
        begin
          --aa :=a.lire;
        end;
      ]]>
    </textSource>
  </function>
</programUnits>
```

18.1.11 Incorrect Color for Multiline Text in Paper Design View When Inline HTML Tags Are Used

If any of the following conditions are present, then the text in the Paper Design view of Reports Builder may display in an incorrect color:

- A text object includes multiline text, which wraps beyond the first line.
- The text object's Contains HTML Tags property is set to Yes.
- More than one color is applied to different parts of the multiline text.

Note: This issue is shown in the Paper Design view only. The report output in all other output formats show correct colors.

18.1.12 Running Oracle Reports

To run Oracle Reports, you must set the following environment variables in the `reports.sh` file, which is located in the `$ORACLE_HOME/bin` directory:

```
REPORTS_DEFAULT_DISPLAY=NO; export REPORTS_DEFAULT_DISPLAY
DISPLAY=myserver:0.0; export DISPLAY
```

Where `myserver:0` is the host computer running a valid X server.

If you try to run the demos (`test.rdf`), the out of the box reports in the process server will not work and the following error message is displayed:

```
REP-3000: Internal error starting Oracle Toolkit.
```

If you are using an in-process server, ensure that the `DISPLAY` environment variable is set correctly in the following configuration file:

```
$ORACLE_HOME/opmn/conf/opmn.xml
```

For the `OC4J_BI_Forms` process-type, the default `DISPLAY` entry is as follows:

```
<variable id="DISPLAY" value="localhost:0"/>
```

You must change the default `DISPLAY` entry to a computer with a valid X server. For example, to use the X server running on `myserver:0.0`, you must use the following setting:

```
<variable id="DISPLAY" value="myserver:0.0"/>
```

After you make this change, run the `opmnctl` command to reload and restart OC4J_BI_Forms.

18.2 Vendor-Specific Issues and Workarounds

This section describes vendor-specific issues and their workarounds for Oracle Reports. It includes the following topics:

- [Section 18.2.1, "Underlines Do Not Display in HTMLCSS Output in Browser"](#)
- [Section 18.2.2, "JSP-Based Web Report with Large Number of Columns Generates JSP Compilation Error"](#)
- [Section 18.2.3, "Java AWT Windows Hangs with Specific Graphics Cards"](#)

18.2.1 Underlines Do Not Display in HTMLCSS Output in Browser

In HTMLCSS output, underlines may not display in the browser if you use a custom style for a field object and apply both background color and underline as part of the style, as shown in the following example:

```
.ReportLevel {text-decoration:underline;color:blue; background-color:yellow}
```

This is a browser limitation. The browser cannot display underlines, with absolute positioning, for the fields that have both underline and background color applied to them.

18.2.2 JSP-Based Web Report with Large Number of Columns Generates JSP Compilation Error

When you run a JSP-based Web report with more than 149 columns, you may encounter the `oracle.jsp.provider.JspCompileException` error, as shown in the following example:

```
500 Internal Server Error
OracleJSP: oracle.jsp.provider.JspCompileException:
Errors
...
6764 code too large for try statement catch( Throwable e)
{18 code too large public void _jspService(HttpServletRequest request,
HttpServletRequest response) throws java.io.IOException, ServletException}
```

This occurs due to a limitation in the Java language that does not enable compilation of Java files with large methods.

18.2.3 Java AWT Windows Hangs with Specific Graphics Cards

When you start Reports Server with `rwserver.exe`, the UI may not display and Reports Server may hang on computers with specific graphics cards (for example, ATI Rage XL PCI card). This occurs due to a problem with the UI mechanism used in Java.

As a workaround, start Reports Server with the `JVMOPTIONS` command line keyword set as shown in the following example:

```
rwserver SERVER=test JVMOPTIONS="-Dsun.java2d.noddraw=true"
```

Note: It is recommended that you start Reports Server from OPMN.

18.3 Globalization Support Issues and Workarounds

This section describes Globalization Support issues and their workarounds for Oracle Reports. It includes the following topics:

- [Section 18.3.1, "Images Do Not Display Correctly in Turkish Environment"](#)
- [Section 18.3.2, "MS Mincho Font in PostScript Font Mapping Does Not Work When NLS_LANG is Specified As JA16EUC"](#)
- [Section 18.3.3, "Multibyte Reports Containing Oracle Object Types Hang Report Builder"](#)
- [Section 18.3.4, "Reports Server's Job Status Messages in Application Server Control Contain Invalid Characters"](#)
- [Section 18.3.5, "ENVID Ignored While Detecting Duplicate Job"](#)

18.3.1 Images Do Not Display Correctly in Turkish Environment

If you are running reports that include images and use advanced imaging in Turkish environments (when NLS_LANG is set to `TURKISH_TURKEY.TR8MSWIN125` or `TURKISH_TURKEY.WE8ISO8859P9`), then set the environment variable `REPORTS_OUTPUTIMAGEFORMAT= [PNG | GIF]`.

Alternatively, you can control the value in the reports request using the command-line keyword, `OUTPUTIMAGEFORMAT= [PNG | GIF]`.

18.3.2 MS Mincho Font in PostScript Font Mapping Does Not Work When NLS_LANG is Specified As JA16EUC

When you deploy reports created with Reports Builder on Windows to a Solaris or Linux Reports Server that has NLS_LANG set to JA16EUC, the PDF font mappings will not work. This happens if any one of the following fonts is used in the PostScript font mapping entry:

```
"<MS Mincho in JP>".....  
"<MS PMincho in JP>".....
```

To work around this issue, you must perform one of the following tasks:

- Set NLS_LANG to JA16SJIS.
- Use MS Gothic instead of MS Mincho in PostScript font mappings when creating the reports.

18.3.3 Multibyte Reports Containing Oracle Object Types Hang Report Builder

Reports Builder may stop responding when you run a multibyte report containing an embedded Oracle Object type. This will be fixed in a future patch set.

This is a known issue.

18.3.4 Reports Server's Job Status Messages in Application Server Control Contain Invalid Characters

Oracle Reports status messages on the Job Status page in Application Server Control Console may contain invalid characters if the middle tier character set, NLS_CHARACTERSET (the third field of NLS_LANG) does not correspond to the encoding of the Reports Servlet response for the servlet locale.

Note: The middle tier's default encoding can be different from the Servlet's encoding. For example, when you set `LANG` to `ja` or `ja_JP.eucJP`, the default middle tier system encoding is `EUC`. However, in this locale, Reports Servlet messages are encoded in `Shift_JIS`. This is because default encoding for `ja_JP` is `Shift_JIS` in the servlet.

Oracle Enterprise Manager 10g converts the messages from the middle tier's `NLS_CHARACTERSET` to `UTF8` resulting in invalid characters in the status messages on the Job Status page. For example, the Reports Servlet messages are encoded in `Shift_JIS` when the middle tier runs with `LANG` set to `ja` and `NLS_LANG` set to `JAPANESE_JAPAN.JA16EUC`. However, Oracle Enterprise Manager 10g assumes that the original message is in `JA16EUC`, and converts it to `UTF8`, which results in the display of invalid characters in the status messages.

18.3.5 ENVID Ignored While Detecting Duplicate Job

When detecting a new incoming request for a duplicate job where the job request includes the `TOLERANCE` keyword, Reports Server ignores the value of the `ENVID` keyword. As a result, the job is marked duplicate of a previous job that was submitted with the same values for all keywords except `ENVID`.

The following example illustrates this issue:

Report Request	Report	ENVID	TOLERANCE	Output
1	Japanese.rdf	JA	10	As expected
2	Arabic.rdf	UTF	10	As expected
3	Arabic.rdf	AR	10	Same as request 2 (incorrect)
4	Japanese.rdf	JA	10	Same as request 1 (correct)

In this example, request 4 is correctly marked as a duplicate of request 1 as both the requests use the same values for all keywords, including the `ENVID` keyword. However, request 3 is incorrectly marked as duplicate of request 2 because both requests use the same values for all keywords, except the `ENVID` keyword. As a result, the changed `ENVID` will not be accepted in request 3. To work around this issue, either do not specify `TOLERANCE` on the command line or specify a dummy user parameter in the job request to differentiate the job requests in duplicate job detection.

Oracle Internet Directory

This chapter describes issues associated with Oracle Internet Directory. It includes the following topics:

- [Section 19.1, "Configuration Issues and Workarounds"](#)
- [Section 19.2, "Administration Issues and Workarounds"](#)
- [Section 19.3, "Documentation Errata"](#)

19.1 Configuration Issues and Workarounds

This section describes configuration issues and their workarounds for Oracle Internet Directory. It includes the following topics:

- [Section 19.1.1, "Configuring Oracle Internet Directory Fan-out Replication"](#)

19.1.1 Configuring Oracle Internet Directory Fan-out Replication

Users will not be able to configure fan-out replication if the supplier version is 9.0.4.x.x or lower. Refer to Bug 4536862 for additional information.

19.2 Administration Issues and Workarounds

This section describes administration issues and their workarounds for Oracle Internet Directory. It includes the following topics:

- [Section 19.2.1, "Recommended Password Policy Values"](#)

19.2.1 Recommended Password Policy Values

Password policies are sets of rules that govern how passwords are used in Oracle Internet Directory. Oracle recommends that you set the following values for password policy attributes

Table 19–1 Recommended Values for Password Policy Attributes

Attribute	Meaning	Value
pwdmaxage	Password expiration in seconds	15552000 (180 days)
pwdexpirewarning	Password expiration warning in seconds	1209600 (14 days)
pwdgraceloginlimit	Password grace login limit (the number of times that user is allowed to login after the password has expired)	5

To set these values, use an LDIF file similar to this example, `pwdpolicydef.ldif`:

```
dn:cn=pwdpolicyentry, cn=common,cn=products,cn=oraclecontext
changetype:modify
replace: pwdmaxage
pwdmaxage: 15552000
-
replace: pwdexpirewarning
pwdexpirewarning: 1209600
-
add: pwdgracelogleinlimit
pwdgracelogleinlimit: 5
```

To modify the password policies of a root Oracle context using this LDIF file, you would type:

```
ldapmodify -h host -p port -D cn=orcladmin -w password -f pwdpolicydef.ldif
```

See Also: *Oracle Internet Directory Administrator's Guide* for information on using Oracle Directory Manager to modify password policies of an identity management realm.

19.3 Documentation Errata

This section describes errors in the documentation for Oracle Internet Directory. It includes these topics:

- [Section 19.3.1, "Parameters in `init\$ORACLE_SID.ora` are Not Loaded Automatically at Database Startup"](#)
- [Section 19.3.2, "ODM Online Help Might Have Extra Pages in Non-English Locales"](#)

19.3.1 Parameters in `init$ORACLE_SID.ora` are Not Loaded Automatically at Database Startup

At startup, the database reads database initialization parameters from `spfile$ORACLE_SID.ora` rather than from `init$ORACLE_SID.ora`—unless the user explicitly specifies the latter when starting the database. Thus, wherever the *Oracle Internet Directory Administrator's Guide* specifies database parameter changes, the subsequent database restart must specify explicitly the `init$ORACLE_SID.ora` file. For example:

```
<>SQL> STARTUP PFILE = /u01/oracle/dbs/initmynewdb.ora
```

For more information, see "Using SQL*Plus to Start Up a Database" in Chapter 3 of *Oracle Database Administrator's Guide*

19.3.2 ODM Online Help Might Have Extra Pages in Non-English Locales

Users in non-English locales might notice help pages in Oracle Directory Manager online help for integration profile configuration that have no corresponding support in the product.

Oracle Delegated Administration Services

This chapter describes issues for both the Oracle Delegated Administration Services (DAS) and the Oracle Internet Directory Self-Service Console. It includes the following topics:

- [Section 20.1, "General Issues and Workarounds"](#)
- [Section 20.2, "Administration Issues and Workarounds"](#)

20.1 General Issues and Workarounds

This section describes general issues and their workarounds for Oracle Delegated Administration Services. It includes the following topics:

- [Section 20.1.1, "Roles with No Members Are not Displayed in Role Assignment Section in Create/edit User"](#)
- [Section 20.1.2, "Resetting Oracle Application Server Single Sign-On Passwords Redirects Users to Oracle Delegated Administration Services Home Page"](#)
- [Section 20.1.3, "Exception Thrown in One-Level Realm Scenarios"](#)
- [Section 20.1.4, "Upgrading Oracle Application Server to 10g Release 2 \(10.1.2\) May Overwrite Custom Ordering of User Attribute Categories in Oracle Delegated Administration Services"](#)

20.1.1 Roles with No Members Are not Displayed in Role Assignment Section in Create/edit User

A role should contain at least one unique member, so that it would be displayed in the Role Assignment section in Create User page and the Edit User page.

To add a unique member to a role, the syntax of the LDIF file is:

```
dn: DN_of_role_entry
changetype: modify
add:uniquemember
uniquemember:DN of member entry
```

Issue this command to modify the file:

```
ldapmodify -p oid_port -h oid_host -D "cn=orcladmin" -w admin_password -v -f file_name.ldif
```

20.1.2 Resetting Oracle Application Server Single Sign-On Passwords Redirects Users to Oracle Delegated Administration Services Home Page

Various application, including OracleAS Portal, use Oracle Delegated Administration Services to reset Oracle Application Server Single Sign-On passwords. Users can reset their own passwords by clicking on a link in the source application, which opens the Reset My Single Sign-On Password page in Oracle Internet Directory Self-Service Console. However, when users click the OK button after resetting their passwords, or if they click the Cancel button to end the password change process, they are redirected to the Oracle Delegated Administration Services home page instead of to the referring application page.

To redirect users to a location other than the Oracle Delegated Administration Services home page, append a query string containing the correct return URLs to the link on the referring application page. Include in the query string two *name=value* pairs for the *doneURL* and the *cancelURL* attributes. The *doneURL* attribute identifies the redirect URL to call when users click the OK button and the *cancelURL* attribute identifies the redirect URL to call when users click the Cancel button. The following example demonstrates how to build a URL to the Change Application Password page that includes the *doneURL* and the *cancelURL* attributes:

```
http://host:port/oiddas/ui/oracle/ldap/DASStep1ResetPwd?  
cancelURL=http://www.domain.com&doneURL=http://www.domain.com
```

20.1.3 Exception Thrown in One-Level Realm Scenarios

You can create a one-level realm in Oracle Internet Directory where the realm DN is the root DSE (DSA-Specific Entry). With a one-level realm, the root DSE becomes the subscriber search base in Oracle Internet Directory. Oracle Application Server Single Sign-On and Oracle Delegated Administration Services function correctly in one-level realm scenarios. However, when Oracle Delegated Administration Services attempts to retrieve a user's resource access descriptor (RAD), a *NullPointerException* is thrown from `oracle.ldap.util.User.getExtendedProperties()`. This exception is also thrown for Oracle Application Server Forms and Reports Services when integrated with one-level Oracle Internet Directory realms or if you call the `oracle.ldap.util.User.getExtendedProperties()` method from a custom application.

This problem will be fixed in a future patch release.

20.1.4 Upgrading Oracle Application Server to 10g Release 2 (10.1.2) May Overwrite Custom Ordering of User Attribute Categories in Oracle Delegated Administration Services

Upgrading Oracle Application Server to 10g Release 2 (10.1.2) may overwrite any customized ordering of user attribute categories that you have configured for Oracle Delegated Administration Services. If this occurs, you must use the Configure Attribute Categories window in the Oracle Internet Directory Self-Service Console to reorder your category list following the upgrade process.

To reorder your category list with the Configure Attribute Categories window, see the "Configuring User Entries" topic in Chapter 5, "Managing Users and Groups with the Oracle Internet Directory Self-Service Console" of the *Oracle Identity Management Guide to Delegated Administration*.

20.2 Administration Issues and Workarounds

This section describes administration issues and their workarounds for Oracle Delegated Administration Services. It includes the following topic:

- [Section 20.2.1, "Enforcing Assignment and Revocation of Privileges Requires Starting a New Self-Service Console Session"](#)
- [Section 20.2.2, "Unified Messaging Voicemail PIN Field Mislabeled in Oracle Internet Directory Self-Service Console"](#)
- [Section 20.2.3, "Unlocking Privileged User Accounts"](#)
- [Section 20.2.4, "Create/Edit User Windows in Oracle Internet Directory Self-Service Console Display Two Time Zone Fields"](#)

20.2.1 Enforcing Assignment and Revocation of Privileges Requires Starting a New Self-Service Console Session

Assignment of roles to users and groups, and revocation of those roles, are enforced only when a new Self-Service Console is created. After assigning or revoking roles, log out of the Console, then log back in.

20.2.2 Unified Messaging Voicemail PIN Field Mislabeled in Oracle Internet Directory Self-Service Console

When Oracle Collaboration Suite users use the Self-Service Console to change their passwords, the field name associated with their voicemail PIN number is incorrectly displayed as 'EmailServerContainer'. To solve this problem:

1. Use Oracle Directory Manager to navigate to the entry of the following DN:
`cn=orclpwdverifierconfig,cn=EEmailServerContainer,
cn=Products,cn=OracleContext,cn=subscriber realm`
2. Select the entry.
3. Select All for **View Properties**.
4. In the displayname text box, enter `Voicemail PIN`.
5. Choose **Apply**.

20.2.3 Unlocking Privileged User Accounts

Oracle Identity Management has two distinct types of privileged user. Both privileged user accounts can be locked if certain password policies are activated.

The first type of privileged user, the super user with the DN `cn=orcladmin`, is represented as a special user entry found within the default identity management realm. It enables directory administrators to make any modifications to the DIT and any changes to the configuration of Oracle Internet Directory servers. If the super user (`orcladmin`) account is locked—for example, as a result of too many attempts to bind with an incorrect password—then an administrator with DBA privileges to the Oracle Internet Directory repository can unlock it by using the `oidpasswd` tool. To unlock the `orcladmin` account execute the command:

```
oidpasswd unlock_su_acct=TRUE
```

The second privileged user is realm-specific. This user governs capabilities such as creation and deletion of users and groups within a realm and all the functionality related to Oracle Delegated Administration Services. This account is represented by an

entry with the DN `cn=orcladmin,cn=users, realm_DN`. Note that, in contrast to the single super user account, each realm has its own realm-specific privileged user. To unlock the realm-specific privileged account, the administrator modifies the realm-specific privileged users account password by using Oracle Directory Manager.

20.2.4 Create/Edit User Windows in Oracle Internet Directory Self-Service Console Display Two Time Zone Fields

On some distributed installations of Oracle Internet Directory, the Oracle Internet Directory Self-Service Console displays two time zone fields in the Create User and Edit User windows. To remove the duplicate field:

1. Launch Oracle Directory Manager and log in as `orcladmin`.
2. In the navigator pane, expand **Oracle Internet Directory Servers**, then *directory server instance*, then **Entry Management**.
3. Expand the following DN in the subtree beneath Entry Management: `realm_DN, cn=oraclecontext, cn=Products, cn=DAS, cn=Attribute Configuration, cn= User Configuration, cn= categories, cn=Basic Info`.
4. Select **cn=Basic Info** beneath the `cn=categories` node.
5. In the **Properties** tab page, locate the **orcldasattrname** attribute and remove the `orcltimezone;;7` value.
6. Click **Apply**.
7. Restart Oracle Delegated Administration Services and log in to the Oracle Internet Directory Self-Service Console.
8. Select the Configuration tab, then select User Entry.
9. Click **Refresh Page**.

Oracle Directory Integration and Provisioning

This chapter describes the issues associated with Oracle Directory Integration and Provisioning. It includes the following topics:

- [Section 21.1, "Configuration Issues and Workarounds"](#)
- [Section 21.2, "Administration Issues and Workarounds"](#)

21.1 Configuration Issues and Workarounds

This section describes configuration issues and their workarounds for Oracle Directory Integration and Provisioning. It includes the following topics:

- [Section 21.1.1, "Two Oracle Internet Directory Plug-in Features Are not Supported after Upgrade to Oracle Internet Directory 10g Release 2 \(10.1.2\)"](#)

21.1.1 Two Oracle Internet Directory Plug-in Features Are not Supported after Upgrade to Oracle Internet Directory 10g Release 2 (10.1.2)

In Oracle Application Server 10g Release 2 (10.1.2), the following plug-in features are not supported if Oracle Internet Directory is running against *Oracle9i* Database Server Release 9.2:

- Microsoft Windows NT Domain external authentication plug-in.
- The `simple_bind_s()` function of LDAP_PLUGIN package provided as the OID PL/SQL PLUGIN API for connecting back to the directory server as part of plug-in definitions.

21.2 Administration Issues and Workarounds

This section describes administration issues and their workarounds for Oracle Directory Integration and Provisioning. It includes the following topics:

- [Section 21.2.1, "Default Mapping Rule Can Be Simplified in Single-Domain Microsoft Active Directory Deployments"](#)
- [Section 21.2.2, "Directory Integration and Provisioning Assistant Does not Support SSL Mode 2"](#)
- [Section 21.2.3, "Shell Script-based Profile Configuration Tools Are Being Deprecated"](#)
- [Section 21.2.4, "In a High Availability Environment Using Multimaster Replication, Provisioning Events May not Be Propagated or May Be Duplicated"](#)

- [Section 21.2.5, "The Oracle Directory Integration and Provisioning Server May not Shut Down if It Is Stopped and Immediately Restarted"](#)
- [Section 21.2.6, "Oracle Directory Integration and Provisioning Server Not Sending Provisioning Events Due to Purged Change Log Entries"](#)

21.2.1 Default Mapping Rule Can Be Simplified in Single-Domain Microsoft Active Directory Deployments

In deployments with only a single domain of Microsoft Active Directory, you can simplify the default mapping rule installed with Oracle Directory Integration and Provisioning.

The default mapping rule is:

```
sAMAccountName,userPrincipalName: :  
:user:orclSAMAccountName:  
:orclADUser:toupper(trunc1(userPrincipalName,'@'))+"$"+sAMAccountname
```

If your deployment has a single domain of Active Directory, then you can simplify the default mapping rule to this:

```
sAMAccountName: : :user:orclSAMAccountName::orclADUser
```

21.2.2 Directory Integration and Provisioning Assistant Does not Support SSL Mode 2

In 10g Release 2 (10.1.2), you can use the Directory Integration and Provisioning Assistant with either a non-SSL connection or an SSL connection with no authentication, namely SSL Mode 1, which provides encryption on the connection. You cannot use the Assistant with SSL mode 2 in which one-way (server only) SSL authentication is required.

21.2.3 Shell Script-based Profile Configuration Tools Are Being Deprecated

Shell script-based profile configuration tools `ldapcreateConn.sh`, `ldapdeleteConn.sh`, and `ldapUploadAgentFile.sh` are being deprecated as of 10g Release 2 (10.1.2).

Oracle recommends that you use the Java-based Oracle Directory Integration and Provisioning Server Administration tool for configuring profiles.

21.2.4 In a High Availability Environment Using Multimaster Replication, Provisioning Events May not Be Propagated or May Be Duplicated

In multimaster replication, the last change number is stored locally on an Oracle Internet Directory node. In a high availability environment, if that node fails, and the provisioning profile is moved to another Oracle Internet Directory node, then the last applied change number in the profile becomes invalid. That number in the profile must then be reset manually on the failover node. Even then, however, events may not be propagated or may be duplicated.

21.2.5 The Oracle Directory Integration and Provisioning Server May not Shut Down if It Is Stopped and Immediately Restarted

To determine whether to shut down, the Oracle Directory Integration and Provisioning server polls the registration entry stored under `cn=odisrv,cn=subregistrysubentry`. It does this every 30 seconds. If you stop, then restart, the server within 30 seconds, then the old server instance may not shut

down before the new instance starts. To alleviate this, wait for 30 seconds before restarting the server.

21.2.6 Oracle Directory Integration and Provisioning Server Not Sending Provisioning Events Due to Purged Change Log Entries

If you use time-based change log purging with version 3.0 provisioning profiles, change logs entries are purged before the Oracle directory integration and provisioning server propagates the changes to any provisioning-integrated applications. This occurs because Oracle Directory Integration and Provisioning does not create version 3.0 provisioning profile entries in the default `cn=subscriber profile,cn=changelog subscriber,cn=oracle internet directory change log subscriber` container.

To resolve this problem, create a container in the default change log subscriber container for each version 3.0 provisioning profile and assign a value of 0 to each profile's `orclLastAppliedChangeNumber` attribute. The following sample LDIF file creates a provisioning profile container in the default change log subscriber container and assigns a value of 0 to the `orclLastAppliedChangeNumber` attribute:

```
dn: cn=profile_name,cn=changelog subscriber,cn=oracle internet directory
orclsubscriberdisable: 0
orcllastappliedchangenumber: 0
objectclass: orclChangeSubscriber
```

Oracle Application Server Single Sign-On

This chapter describes issues associated with Oracle Application Server Single Sign-On (OracleAS Single Sign-On). It includes the following topic:

- [Section 22.1, "Configuration Issues and Workarounds"](#)
- [Section 22.2, "Issues and Workarounds Related to Oracle Database"](#)

22.1 Configuration Issues and Workarounds

This section describes configuration issues and their workarounds for Oracle Application Server Single Sign-On. It includes the following topic:

- [Section 22.1.1, "Additional High Availability Configuration Instructions"](#)

22.1.1 Additional High Availability Configuration Instructions

Additional configuration steps are required after OracleAS Infrastructure is installed with the "OracleAS Cluster (Identity Management)" option. There are two sets of instructions to follow:

- The first set of instructions, in [Section 22.1.1.1, "Update the mod_rewrite Entry for SSO"](#), must be followed in all cases.
- The second set of instructions, [Section 22.1.1.2, "Update targets.xml"](#), are needed in only one installation case as described in that section.

22.1.1.1 Update the mod_rewrite Entry for SSO

Take the following steps:

1. Back up the `sso_apache.conf` file:

```
cp ORACLE_HOME/sso/conf/sso_apache.conf
   ORACLE_HOME/sso/conf/sso_apache.conf.BACKUP
```

2. Edit the file. Locate the `mod_rewrite` entry that contains the following text:

```
<IfModule mod_rewrite.c>
  RewriteEngine On
  RewriteRule ^/pls/orasso/orasso.wwsso_app_admin.ls_login$ /sso/auth [PT]
</IfModule>
```

Add the following line:

```
RewriteRule ^/pls/orasso/orasso.home$ PROTOCOL:
//LBR_HOST:LBR_PORT/pls/orasso/orasso.home [R,L]
```

replacing the placeholders in *italics* with the following values:

- Replace *LBR_HOST* with the full hostname for the HTTP load balancer.
- Replace *LBR_PORT* with the SSL listening port. If SSL is enabled, enter the SSL port value. If using the default ports of 80 or 443, do not specify a port value.
- Replace *PROTOCOL* with either HTTPS (if using the SSL port) or HTTP (if using the non-SSL port).

For example, the entry might look like this when using a non-default SSL port:

```
<IfModule mod_rewrite.c>
  RewriteEngine On
  RewriteRule ^/pls/orasso/orasso.wwsso_app_admin.ls_login$
    /sso/auth [PT]
  RewriteRule ^/pls/orasso/orasso.home$ https:
    //lbr.mydomain.com:4443/pls/orasso/orasso.home [R,L]
</IfModule>
```

As another example, the entry might look like this when using a default SSL port:

```
<IfModule mod_rewrite.c>
  RewriteEngine On
  RewriteRule ^/pls/orasso/orasso.wwsso_app_admin.ls_login$
    /sso/auth [PT]
  RewriteRule ^/pls/orasso/orasso.home$ https:
    //lbr.mydomain.com/pls/orasso/orasso.home [R,L]
</IfModule>
```

3. Save and close the file.
4. Restart Oracle HTTP Server.

22.1.1.2 Update targets.xml

The following configuration steps are needed only in the installation scenario where communications between clients and the load balancer use HTTPS, and communications between the load balancer and Oracle HTTP Server also use HTTPS:

Client ---[HTTPS]---> Load Balancer ---[HTTPS]---> Oracle HTTP Server

In this case the `oracle_sso_server` entry in the `targets.xml` file, on each physical host of the cluster, must be reconfigured to monitor the local SSL port.

Note:

Keep in mind that the hostname should remain the same. Do not change the hostname.

Perform the following steps to update `targets.xml` on each node of the cluster:

1. Back up the `targets.xml` file:

```
cp ORACLE_HOME/sysman/emd/targets.xml
   ORACLE_HOME/sysman/emd/targets.xml.BACKUP
```

2. Open the file and find the `oracle_sso_server` target type. Within this target entry, locate and edit the following two attributes:

- HTTPPort - the server SSL port number
- HTTPProtocol - the server protocol, which in this case is HTTPS

For example, you could update the two attributes this way:

```
<Property NAME="HTTPPort" VALUE="4443" />
<Property NAME="HTTPProtocol" VALUE="HTTPS" />
```

3. Save and close the file.
4. Reload the OracleAS console:

```
ORACLE_HOME/bin/emctl reload
```

22.2 Issues and Workarounds Related to Oracle Database

This section describes issues and workarounds for Oracle Application Server Single Sign-On that are triggered by the Oracle Database. It includes the following topic:

- [Section 22.2.1, "Issues With Upgrading the Oracle Database"](#)

22.2.1 Issues With Upgrading the Oracle Database

After upgrading your Metadata Repository from Oracle Database 9.2.0.6 to 10.1.x, the following error is reported on the Discoverer Plus Connection pages, the Discoverer Viewer Connection pages, and the Public Connection definition page in Application Server Control:

```
The connection list is currently unavailable.
ORA-06510: PL/SQL: unhandled user-defined exception
ORA-06512: at "ORASSO.WWSSO_API_PRIVATE," line 258
ORA-06510: PL/SQL: unhandled user-defined exception
ORA-06512: at "ORASSO.WWSSO_UTL" line 728
ORA-28231: no data passed to obfuscation toolkit
ORA-06512: at line 1 Unable to retrieve connection list
```

The same problem will be encountered with external applications on the server hosting Oracle Application Server Single Sign-On.

To resolve this issue, make the following changes in your Metadata Repository Database:

1. Edit the `init%ORACLE_SID%.ora` file in the following location:

```
DB_install_home/dbs
```

Add the following line to this file:

```
event="10946 trace name context forever, level 36"
```

2. If an `spfile%ORACLE_SID%.ora` exists in either the `dbs` folder or the database folder, rename the file to `spfile%ORACLE_SID%.bak`.

Changes to `init%ORACLE_SID%.ora` are not loaded if the database server finds an `spfile`.

3. Log in as a sysadmin.
4. At the SQL prompt, shut down then start up the database server.
5. Restart the Discoverer server using the command `opmnctl restartall`.

Oracle Application Server Certificate Authority

This chapter describes issues with Oracle Application Server Certificate Authority (OracleAS Certificate Authority, OCA). It includes the following topics:

- [Section 23.1, "General Issues and Workarounds"](#)
- [Section 23.2, "Configuration Issues and Workarounds"](#)

23.1 General Issues and Workarounds

This section describes general usage issues for OracleAS Certificate Authority and their workarounds. It includes the following topics:

- [Section 23.1.1, "Adding "\" to RDN Causes Misprocessing"](#)
- [Section 23.1.2, "Third Party Wallet Import Fails Due To localID Value"](#)
- [Section 23.1.3, "DN Validation Does Not Correctly Check "=" Character"](#)

23.1.1 Adding "\" to RDN Causes Misprocessing

If the Common Name of a certificate request contains a backslash character "\", OracleAS Certificate Authority fails to process the DN. Here is an example of an incorrect request:

```
CN=a \& b,O=aime,C=US
```

Rather than escaping the & symbol, the CN value of the certificate issued by OracleAS Certificate Authority contains two backslashes ("\\").

To work around this issue, do not use special symbols which require a backslash in front when entering the common name for generating wallets. In the example cited earlier, the Common Name in the request can be rewritten as:

```
CN= a and b, O=aime, C=US
```

23.1.2 Third Party Wallet Import Fails Due To localID Value

When importing a wallet, OracleAS Certificate Authority expects the value of `localID` in the wallet to match the private key and certificate, but some third party wallets do not use `localID` for this purpose. Consequently, OracleAS Certificate Authority fails to import the third party wallet as SubCA.

23.1.3 DN Validation Does Not Correctly Check "=" Character

If a Common Name value contains the "=" character, OracleAS Certificate Authority incorrectly accepts it as a valid character. Here is an example of an incorrect request:

```
CN=abc=, O=aime,C=US
```

In this example, "abc=" is an invalid entry due to the presence of "=" which is a special character.

The workaround for this issue is to avoid using the "=" character in this way within RDN values.

23.2 Configuration Issues and Workarounds

This section describes configuration issues and their workarounds for OracleAS Certificate Authority. It includes the following topics:

- [Section 23.2.1, "Unexpected Behavior After Revoking Web Administrator or CA Certificate"](#)
- [Section 23.2.2, "Allowable Values of Predicate Usage"](#)

23.2.1 Unexpected Behavior After Revoking Web Administrator or CA Certificate

OracleAS Certificate Authority may exhibit incorrect or unexpected behavior after it is shut down to revoke the web administrator certificate or CA certificate, and is not restarted correctly. Here are some examples:

- The OracleAS Certificate Authority service is stopped, and the web administrator and CA certificates are revoked. A new CA is created, and new CA and CASSL wallets are generated. After restarting the OracleAS Certificate Authority service, the newly enrolled web administrator sees the error message:

```
Error  
Certificate of the connecting SSL user does not exist in OCA repository
```

when trying to perform administrative actions.

- With the browser interface open, the OracleAS Certificate Authority service is stopped, and the web administrator and CA certificates are revoked. Nevertheless, the open browser session can still be used to update the Certificate Revocation List (CRL).

In both situations, the problem is due to incorrect handling of the OracleAS Certificate Authority service and its supporting services following shutdown. After you revoke the web administrator certificate or CA certificate, it is necessary to restart not only OracleAS Certificate Authority, but also OHS and the certificate authority's OC4J components using the OPMN service:

```
$ORACLE_HOME/opmn/bin/opmnctl stopall  
$ORACLE_HOME/opmn/bin/opmnctl startall
```

23.2.2 Allowable Values of Predicate Usage

As documented in Table 6-9 of the *OracleAS Certificate Authority Administrator's Guide*, the usage attribute of a policy predicate, which specifies how the certificate may be used, can be assigned values 1 through 9. Currently, however, OracleAS Certificate Authority allows only usages 1,2,4,8,9 when creating predicates. Usage values 3,5,6,7 are not being allowed even though they are valid.

Oracle Enterprise Manager

This chapter describes issues with Oracle Enterprise Manager. It includes the following topics:

- [Section 24.1, "General Issues and Workarounds"](#)
- [Section 24.2, "Documentation Errata"](#)

24.1 General Issues and Workarounds

This section describes general issues and their workarounds for the Oracle Enterprise Manager 10g Application Server Control Console. It includes the following topics:

- [Section 24.1.1, "Problems with the Oracle Enterprise Manager 10g Application Server Control Console After Deinstalling Oracle Application Server 9.0.2 or 9.0.3"](#)
- [Section 24.1.2, "Setting NLS and Operating System Locale Environment Variables Before Starting Management Processes"](#)
- [Section 24.1.3, "Misleading Error Message When Applying Properties to an OC4J Instance within an Oracle Application Server Cluster"](#)
- [Section 24.1.4, "Errors When Configuring Components or Adding or Removing OC4J Instances"](#)
- [Section 24.1.5, "Problem Viewing Performance Charts and Configuring Identity Management Using a Macintosh Browser"](#)
- [Section 24.1.6, "Problems with the Progress Page When Using a Macintosh Browser"](#)
- [Section 24.1.7, "Topology Viewer Applet Fails in OracleAS Cold Failover Cluster Configuration"](#)
- [Section 24.1.8, "Error When Clicking Topology Link from Host Page"](#)
- [Section 24.1.9, "Error When Using the ADF BUSINESS COMPONENT Link on the Host Page"](#)
- [Section 24.1.10, "Farm Locator Link Lost"](#)
- [Section 24.1.11, "Incorrect Status Reported for Oracle Business Intelligence Discoverer"](#)
- [Section 24.1.12, "Changing From JAZN LDAP User Manager Requires OC4J Restart"](#)
- [Section 24.1.13, "Posting Data From the Logging Pages"](#)

- [Section 24.1.14, "Additional Step When Removing an Application Server Target From the Grid Control Console"](#)
- [Section 24.1.15, "Security Considerations When Changing Schema Passwords with the Application Server Control Console"](#)
- [Section 24.1.16, "Problems Viewing Some Metrics When OracleAS Portal is Configured for Secure Sockets Layer \(SSL\)"](#)
- [Section 24.1.17, "Cannot Recover Database Control Files from the Application Server Control Console"](#)
- [Section 24.1.18, "Problem Using the Topology Viewer to Perform Operations on an OracleAS Farm When in French or French-Canadian Language Environment"](#)
- [Section 24.1.19, "Configuring Security When Oracle Application Server Is Managed by Grid Control"](#)
- [Section 24.1.20, "Blank Screen When Attempting to Display Application Server Control Console in Internet Explorer"](#)
- [Section 24.1.21, "Incorrect Memory Usage Is Reported for Forms on SLES9"](#)
- [Section 24.1.22, "Harmless Errors in Log Files"](#)
- [Section 24.1.23, "Enterprise Manager Agent Restarts Periodically When JVM Size Is Full"](#)

24.1.1 Problems with the Oracle Enterprise Manager 10g Application Server Control Console After Deinstalling Oracle Application Server 9.0.2 or 9.0.3

In certain situations, deinstallation of Oracle Application Server 9.0.2 or 9.0.3 may, through an automatic procedure run at deinstall time, cause a number of configuration files in the Oracle Application Server 10g directories to be overwritten with incorrect information.

The Enterprise Manager control scripts in Oracle Application Server 10g have been modified to make as-needed backups of these files; as a result, you should be able to recover from this problem by replacing the files from the backup versions.

These files are:

```
ORACLE_HOME/sysman/config/iasadmin.properties
ORACLE_HOME/sysman/emd/targets.xml
ORACLE_HOME/sysman/j2ee/config/jazn-data.xml
ORACLE_HOME/sysman/webapps/emd/WEB-INF/config/consoleConfig.xml
```

There may be a number of backup files in each of these cases. The backups are named in the form `<original-file-name>.n`, where *n* is a number from 1 to 10.

The most recent backup of the file is `.1`, then next most recent `.2`, and so on. You should check the timestamps or inspect these files to determine which is the most recent correct version of the data. This is most likely the last backup version before you deinstalled Application Server 9.0.2 or 9.0.3.

To restore these files:

1. Shut down the Application Server Control Console using the `emctl` command.
2. Remove, or rename the four files listed above
3. Copy the version of the backup file which you have determined to be the correct, working version

4. Start the Application Server Control Console.

24.1.2 Setting NLS and Operating System Locale Environment Variables Before Starting Management Processes

If in a non-English environment, you launch a command line tool such as `emctl` to start a process, make sure the operating system locale and `NLS_LANG` environment variable settings are configured properly and consistently. This is applicable to the `emctl` command line utility that is available with Oracle Application Server installations as well as with the `emctl` utility available with Grid Control Console installations.

If these environment variables are not set prior to Oracle Application Server or Grid Control Console installations, then non-ASCII characters will appear incorrectly in the Application Server Control Console or Grid Control Console, respectively. To prevent this problem from occurring, set these two environment variables prior to installation. If this is not possible, then to resolve the problem set the two environment variables after installation and restart the Management Agent.

Refer to the following sections for details on how to check and set the values for these variables:

- [Section 24.1.2.1, "Checking the Operating System Locale"](#)
- [Section 24.1.2.2, "Setting the Operating System Locale"](#)
- [Section 24.1.2.3, "Checking the NLS_LANG Environment Variable"](#)
- [Section 24.1.2.4, "Setting the NLS_LANG Environment Variable"](#)

24.1.2.1 Checking the Operating System Locale

Make sure the `LC_ALL` or `LANG` environment variables are set with the appropriate value. To check the current setting, issue the following command:

```
$PROMPT> locale
```

24.1.2.2 Setting the Operating System Locale

If you are using `bash` or `zsh`, to set the operating system locale environment variable, issue the `export` command. For example:

```
export LANG=zh_CN
```

In this example, the variable is being set to Simplified Chinese. For the specific value in each operating system, refer to operating system-specific documentation.

If you are using `csh` or `tcsh`, then issue the `setenv` command:

```
setenv LANG zh_CN
```

24.1.2.3 Checking the NLS_LANG Environment Variable

Make sure the `NLS_LANG` environment variable is set with the appropriate and compatible value with the operating system locale setting (and the Grid Control Management Repository database character set if Grid Control is being used to centrally manage the Oracle Application Server). For the specific value for the language or the character set, refer to the *Globalization Support Guide* of the Oracle product you are using.

In addition, check to see if the NLS_LANG setting exists in \$ORACLE_HOME/opmn/conf/opmn.xml. For example, the following content should appear in the opmn.xml file:

```
<environment>
  <variable id="TMP" value="/tmp"/>
  <variable id="NLS_LANG" value="JAPANESE_JAPAN.JA16SJIS"/>
</environment>
```

If the NLS_LANG setting exists, make sure the NLS_LANG setting in the opmn.xml file is identical to the NLS_LANG environment variable.

24.1.2.4 Setting the NLS_LANG Environment Variable

If you are using bash or zsh, to set the NLS_LANG environment variable, issue the export command. For example:

```
export NLS_LANG="Simplified Chinese_China.ZHS16GBK"
```

In this example, the variable is being set to Simplified Chinese. For the specific value in each operating system, refer to operating system-specific documentation.

If you are using csh or tcsh, then issue the setenv command. For example:

```
setenv NLS_LANG "Simplified Chinese_China.ZHS16GBK"
```

24.1.3 Misleading Error Message When Applying Properties to an OC4J Instance within an Oracle Application Server Cluster

Changes applied on the OC4J Server Properties page to an OC4J instance within an Oracle Application Server cluster will always show the message `Server properties have been applied across the cluster`. In fact, changes to environment variables, ports, islands, and number of island processes will only be applied to the current OC4J instance currently under administration and not to other OC4J instances within the cluster. Other values on this page (for example, Java Options) will be applied across the cluster.

Information concerning which values are applied cluster wide is displayed in a tip at the top of the page; however, the confirmation message may be incorrect.

24.1.4 Errors When Configuring Components or Adding or Removing OC4J Instances

If you install Oracle Management Agent 10.1.0.2 on a computer which has one or more instances of Oracle Application Server 10g (10.1.2), then you may encounter errors in Application Server Control Console if you later modify your component configuration in the Oracle Application Server installation. For example, you may receive errors if you create or remove an OC4J instance or if you configure an Oracle Application Server component after you have installed the application server.

To workaroud this problem, install the Oracle Management Agent 10.1.0.3 or later patchsets.

24.1.5 Problem Viewing Performance Charts and Configuring Identity Management Using a Macintosh Browser

When using the Apple Safari browser on a Macintosh computer, it is not possible to use the Application Server Control Console to configure or change the Identity Management configuration for an Application Server middle-tier installation.

Specifically, the problem occurs when you click Configure in the Identity Management section of the Infrastructure page in the Application Server Control Console. You can enter the host and port for the Identity Management host, but you cannot display the next page in the wizard.

In addition, the performance charts on the Application Server Home page do not display correctly in the Macintosh browser. Instead of a chart, small question marks appear in their place.

To fix this problem, perform the following procedure:

1. Stop the Application Server Control service for this Oracle home.
2. Use a text editor to open the following configuration file in the Oracle Home of the application server instance you are attempting to modify:

```
$ORACLE_HOME/sysman/j2ee/config/emd-web-site.xml
```

3. Locate the following entry in the file:

```
<!-- The default web-app for this site, bound to the root -->
<default-web-app application="em" name="default" />
<web-app application="em" name="emd" root="/emd" load-on-startup="true" />
```

4. Add the following argument to the <web-app> tag:

```
shared="true"
```

For example:

```
<!-- The default web-app for this site, bound to the root -->
<default-web-app application="em" name="default" />
<web-app application="em" name="emd" root="/emd"
  load-on-startup="true" shared="true"/>
```

5. Save your changes and close the em-web-site.xml file.
6. Use the Services control panel to start the Application Server Control service for this Oracle home.

24.1.6 Problems with the Progress Page When Using a Macintosh Browser

Often, when you perform an operation with the Application Server Control Console, such as creating a new OC4J instance, Enterprise Manager displays a progress page, which indicates that the operation is still in progress.

When using the Apple Safari browser on a Macintosh computer, the progress page continues to display even after the operation is complete. As a result, the operation confirmation page does not display as it should.

To solve this problem, set the EM_OC4J_OPTS environment variable to the following value and restart the Application Server Control:

```
-Doracle.sysman.emSDK.eml.util.iAS.waitForCompletion=true
```

See Also: Appendix "Managing and Configuring Application Server Control" of the *Oracle Application Server Administrator's Guide* for more information about using the EM_OC4J_OPTS environment variable

24.1.7 Topology Viewer Applet Fails in OracleAS Cold Failover Cluster Configuration

The Java applet version of the Topology Viewer fails to connect to the Oracle Process Manager and Notification Server (OPMN) if you access Application Server Control with the virtual hostname in a OracleAS Cold Failover Cluster configuration.

Use one of the following workarounds:

- Use the HTML Only version of the Topology Viewer.
- Connect to the Application Server Control with the physical hostname.

24.1.8 Error When Clicking Topology Link from Host Page

In the Host page of Application Server Control, when clicking the **Topology** link, the following error appears:

Could not determine the oracle home for this component

To workaround this error, navigate to the Farm page, and click the **Topology** link from that page.

24.1.9 Error When Using the ADF BUSINESS COMPONENT Link on the Host Page

In the Host page of Application Server Control, when clicking the **ADF BUSINESS COMPONENTS** target in the **Targets** section, the following error appears:

Error: Failed to connect to OC4J null instance now, please click refresh page to try again!

To avoid this error, navigate to the OC4J Administration page, and click the **ADF Business Components** link in the **Related Links** section.

24.1.10 Farm Locator Link Lost

In some installations, the Farm locator link is lost in Application Server Control Console once you navigate to the Application Server Home page and click **Configure Component** just above the System Components table to configure a component. Locator links display at the top of pages in Application Server Control Console. They specify the location of the current page within Application Server Control Console. As the user navigates through hierarchical content, or drills down through levels of content and functions, locator links track the location, and allow the user to navigate back to higher levels in the hierarchy.

To get back to the Farm page, navigate to the Application Server Home page, and click the **Farm** link in the **General** section.

24.1.11 Incorrect Status Reported for Oracle Business Intelligence Discoverer

When managing OracleBI Discoverer with Grid Control Console release 10.1, the Grid Control Console displays inaccurate status for OracleBI Discoverer. For instance, when the component is actually up, the Grid Control Console displays the status as down. A one-off patch to the Grid Control Console Management Agent release 10.1.0.4 will soon be released to Oracle MetaLink to resolve this specific problem.

This problem does not manifest in the Application Server Control Console release 10.1.2. The status for OracleBI Discoverer is displayed correctly in the Application Server Control Console.

24.1.12 Changing From JAZN LDAP User Manager Requires OC4J Restart

If you use the OC4J Application Properties page to change the User Manager for an OC4J application, then note the following: The application will start using the JAZN LDAP User Manager immediately after you select **Use JAZN LDAP User Manager** and click **Apply**.

However, if you change from a JAZN LDAP user manager to another User Manager, such as the JAZN XML User Manager, you must restart the OC4J instance before the new User Manager is available to the application.

24.1.13 Posting Data From the Logging Pages

After you configure security for the Application Server Control, you may see intermittent issues with form data updates in the Logging pages. These issues may occur with Microsoft Internet Explorer browsers after you install the 832894 (MS04-004) security update or the 821814 hotfix. Microsoft Internet Explorer has known issues with using a form on a HTTPS Web page. Problem related to these updates have been seen in the Advanced Search feature of the Search Log Repository page.

To workaround this problem, download the Microsoft Q831167 .exe package and any other related patch recommended by Microsoft.

See Also:

<http://support.microsoft.com/default.aspx?kbid=831167>

24.1.14 Additional Step When Removing an Application Server Target From the Grid Control Console

If an Oracle Application Server 10g (9.0.4) or 10g Release 2 (10.1.2) target is removed from the Grid Control Console, the Infrastructure page in the Application Server Control Console will still show Central Management as **Configured**.

To reset the Central Management section of the page, delete the following file from the `centralagents.lst` in the application server Oracle home:

`ORACLE_HOME/sysman/emd/centralagents.lst` (UNIX)

24.1.15 Security Considerations When Changing Schema Passwords with the Application Server Control Console

You can use the Application Server Control Console to change the password for a component schema in the OracleAS Metadata Repository.

However, when you perform this task in the Application Server Control Console, the new password you enter will be saved in clear text format in the following log file:

`ORACLE_HOME/sysman/log/em-web-access.log`

In addition, if the Application Server Control Console has not been secured, the new schema password will be transmitted unencrypted from the client-side browser to the machine where the Console is running.

See Also: "Configuring Security for the Application Server Control Console" in the chapter "Enabling SSL in the Infrastructure" in the *Oracle Application Server Administrator's Guide* for more information about the benefits of configuring security for the Application Server Control Console

To avoid these potential security issues, perform the following procedure before changing a schema password in the Application Server Control Console:

1. Stop the Application Server Control.

You can stop the Application Server Control by entering the following command in the Application Server Control Oracle home:

```
ORACLE_HOME/bin/emctl stop iasconsole
```

See Also: The "Starting and Stopping" chapter of the *Oracle Application Server Administrator's Guide*

2. Secure the Application Server Control by entering the following command:

```
ORACLE_HOME/bin/emctl secure iasconsole0.
```

See Also: "Configuring Security for Enterprise Manager Application Server Control Console" in Appendix A of *Oracle Application Server Administrator's Guide*

3. Use a text editor to open the following configuration file in the application server Oracle home:

```
ORACLE_HOME/sysman/j2ee/config/emd-web-site.xml
```

4. Locate the following entry in the emd-web-site.xml file:

```
<!-- Access Log, where requests are logged to -->
<access-log path="../../log/em-web-access.log" />
```

5. Modify the access-log path entry so it describes the format of each log entry, as follows:

```
<!-- Access Log, where requests are logged to -->
<access-log path="../../log/em-web-access.log"
  format="$ip - [$time] '$path' $status $size"/>
```

6. Save and close the emd-web-site.xml file.

7. Start the Application Server Control.

You can start the Application Server Control by entering the following command in the Application Server Control Oracle home:

```
ORACLE_HOME/bin/emctl start iasconsole
```

See Also: The "Starting and Stopping" chapter of *Oracle Application Server Administrator's Guide*

24.1.16 Problems Viewing Some Metrics When OracleAS Portal is Configured for Secure Sockets Layer (SSL)

When you use Application Server Control Console to monitor targets such as OracleAS Portal that has been configured to use Secure Sockets Layer (SSL), some performance metrics for OracleAS Portal may not display.

To correct this problem you must allow the Application Server Control to recognize the Certificate Authority that was used by the Web Site to support HTTPS. You must add the Certificate of that Certificate Authority to the list of Certificate Authorities recognized by the Application Server Control.

To configure Application Server Control to recognize the Certificate Authority:

1. Obtain the Certificate of the Web Site's Certificate Authority, as follows:

- a. In Microsoft Internet Explorer, connect to the HTTPS URL of the application server you are attempting to monitor.
- b. Double-click the lock icon at the bottom of the browser screen, which indicates that you have connected to a secure Web site.

The browser displays the Certificate dialog box, which describes the Certificate used for this Web site. Other browsers offer a similar mechanism to view the Certificate detail of a Web Site.

- c. Click the **Certificate Path** tab and select the first entry in the list of certificates.
- d. Click **View Certificate** to display a second Certificate dialog box.
- e. Click the **Details** tab on the Certificate window.
- f. Click **Copy to File** to display the Certificate Manager Export wizard.
- g. In the Certificate Manager Export wizard, select **Base64 encoded X.509 (.CER)** as the format you want to export and save the certificate to a text file with an easily-identifiable name, such as `portal_certificate.cer`.
- h. Open the certificate file using your favorite text editor.

The content of the certificate file will look similar to the content shown in Example 15-1.

2. Update the list of Certificate Authorities, as follows:

- a. Locate the `b64InternetCertificate.txt` file in the following directory of the Oracle Application Server Oracle home:

```
ORACLE_HOME/sysman/config/
```

This file contains a list of Base64 Certificates.

- b. Edit the `b64InternetCertificate.txt` file and add the contents of the Certificate file you just exported to the end of the file, taking care to include all the Base64 text of the Certificate including the BEGIN and END lines.

3. Copy the text file that contains the certificate (for example, the file you named `portal_certificate.cer` earlier in this procedure) to the OracleAS Portal middle tier.

4. Use the `orapki` utility to update the `monwallet` Oracle wallet by using the following command:

```
ORACLE_HOME/bin/orapki wallet add
-wallet ORACLE_HOME/sysman/config/monwallet
-trusted_cert
-cert certificate_location
```

When you are prompted for a password, enter the password for the `monwallet` wallet. The default password is *welcome*.

In the example, replace *certificate_location* with the full path to the text file that contains the certificate you saved earlier in this procedure and that you copied to the OracleAS Portal middle tier. For example:

```
/dua0/oracle/portal_certificate.cer
```

5. Restart the Application Server Control.

After you restart the Application Server Control, Enterprise Manager detects your addition to the list of Certificate Authorities and you can successfully monitor the OracleAS Portal metrics using the secure Application Server Control Console.

Example 24–1 Example Content of an Exported Certificate

```
-----BEGIN CERTIFICATE-----  
MIIDBzCCAnCgAwIBAgIQTs4NcImNY3JAs5edi/5RkTANBgk  
... base64 certificate content ...  
-----END CERTIFICATE-----
```

24.1.17 Cannot Recover Database Control Files from the Application Server Control Console

If you back up an OracleAS Infrastructure Oracle home, you will notice that when you attempt to recover the backup, the option for recovering the OracleAS Metadata Repository database control files is not available on the Perform Recovery page of the Application Server Control Console.

As a result, you cannot recover the database control files that you backed up by using the Application Server Control Console. Instead, use the command-line OracleAS Backup and Recovery Tool to recover the database control files. Specifically, to recover the database control files, use the `-c` command-line argument to the Backup and Recovery tool.

For more information, see "Restoring and Recovering the Metadata Repository" in *Oracle Application Server Administrator's Guide*.

24.1.18 Problem Using the Topology Viewer to Perform Operations on an OracleAS Farm When in French or French-Canadian Language Environment

If the default language is set to French or French-Canadian, and you select an operation from the contextual menu next to the OracleAS Farm icon in the Application Server Control Console Topology Viewer, a JavaScript error occurs.

To workaroud this problem, use the contextual menu associated with the individual instances in the OracleAS Farm.

For more information about using the contextual menus in the Topology Viewer, see "Actions You Can Perform Using the HTML Only Topology Viewer" in the Enterprise Manager online Help.

24.1.19 Configuring Security When Oracle Application Server Is Managed by Grid Control

If you are managing Oracle Application Server with Oracle Enterprise Manager 10g Grid Control, keep in mind the following restriction if you decide to enable security for the Application Server Control after you begin managing the application server with Grid Control.

After you enable security for the Application Server Control, the **Administer** link on the Application Server Home page in the Grid Control Console will no longer work. Instead of linking to the new HTTPS URL for the secure Application Server Control, the Administer link is still configured to link to the original HTTP URL.

To remedy this problem, you must remove the application server target from the Grid Control Console and then add the target again. For information about removing and adding monitored targets, see the Grid Control Console online help.

24.1.20 Blank Screen When Attempting to Display Application Server Control Console in Internet Explorer

If you navigate to the Application Server Control Console and Microsoft Internet Explorer displays a blank screen instead of the Application Server Control Console, the problem is likely caused by the Internet Explorer **Allow META REFRESH** security option. This option must be enabled in order for you to display specific pages in the Application Server Control Console.

There are three possible workarounds for this problem:

1. Enable the **Allow META REFRESH** option for all pages you display in Internet Explorer:
 - a. Select **Internet Options** from the Internet Explorer **Tools** menu.
 - b. Click the **Security** tab.
 - c. Click **Custom Level**.
 - d. Scroll down to the **Miscellaneous** options and make sure that the **Allow META REFRESH** option is enabled.
2. Use a more specific URL when connecting to the Application Server Control Console.

For example, if you are having trouble accessing `http://host:port/`, then try entering a more specific URL, such as:

```
http://host:port/emd/console/
```

3. Add the Application Server Control Console URL to the list of Internet Explorer Trusted Sites:
 - a. Select **Internet Options** from the Internet Explorer **Tools** menu.
 - b. Click the **Security** tab.
 - c. Click the **Trusted Sites** icon, and then click **Sites** to display the Trusted Sites dialog box.
 - d. If you have not enabled Application Server Control security, clear the **Require server verification (https:) for all sites in this zone** check box.
 - e. Enter the URL for the Application Server Control Console and click **Add**.

24.1.21 Incorrect Memory Usage Is Reported for Forms on SLES9

On SLES9, when you click the Forms link on the Enterprise Manager main page, the Forms Overview page is displayed. On this page, the Pie Chart showing the Memory Usage is broken and shows an unhandled exception error. When you click the User Sessions tab, it shows the Total Memory Usage, in percentage. Due to the way SLES9 operating system reports the memory of a process, the private and shared memory sections display very high values. To resolve this issue, apply the following patch:

<http://www.kernel.org/pub/linux/kernel/v2.6/testing/patch-2.6.9-rc4.bz2>

24.1.22 Harmless Errors in Log Files

During installation of J2EE, Oracle Business Intelligence, Portal and Wireless, and Enterprise Manager Agent and Console, some of the errors that show up in the log files are harmless and can be ignored. These errors may come up in the `emias.log`, `em-application.log`, and `emagent.trc` files.

Some of these errors are listed in the following examples:

Example 24–2 Error in `emias.log` file

```
ERROR cache.CacheManager run.519 -
Exception message: sleep interrupted java.lang.InterruptedException: sleep
interrupted at java.lang.Thread.sleep(Native Method) at
oracle.sysman.emSDK.svc.cache.CacheManager$Checker.run(CacheManager.java:507) at
java.lang.Thread.run(Thread.java:534)
```

Example 24–3 Error in `emias.log` file

```
2005-07-01 16:20:23,231 [EMUI_16_20_23_/console/metrics/metricData] ERROR
metrics.AllMetricsUtil getNLSSString.126 - Can't find resource for bundle
oracle.sysman.eml.rsc.gen.hostMsg, key host_paging_activity_pgactive
java.util.MissingResourceException: Can't find resource for bundle
oracle.sysman.eml.rsc.gen.hostMsg, key host_paging_activity_pgactive
  at java.util.ResourceBundle.getObject(ResourceBundle.java:326)
  at java.util.ResourceBundle.getObject(ResourceBundle.java:323)
  at java.util.ResourceBundle.getString(ResourceBundle.java:286)
  at
oracle.sysman.ias.sta.metrics.AllMetricsUtil.getNLSSString(AllMetricsUtil.java:122)
  at oracle.sysman.ias.sta.metrics.MetricData.getMetricData(MetricData.java:389)
  at oracle.sysman.ias.sta.metrics.MetricData.getHeader(MetricData.java:194)
  at oracle.sysman.ias.sta.metrics.MetricCtrl.prepareData(MetricCtrl.java:118)
  at oracle.sysman.emSDK.svlt.PageHandler.handleRequest(PageHandler.java:419)
  at oracle.sysman.emSDK.svlt.EMServlet.myDoGet(EMServlet.java:728)
  at oracle.sysman.emSDK.svlt.EMServlet.doGet(EMServlet.java:307)
  at oracle.sysman.eml.app.Console.doGet(Console.java:271)
  at javax.servlet.http.HttpServlet.service(HttpServlet.java:740)
  at javax.servlet.http.HttpServlet.service(HttpServlet.java:853)
  at
com.evermind.server.http.ServletRequestDispatcher.invoke(ServletRequestDispatcher.
java:837)
  at
com.evermind.server.http.ServletRequestDispatcher.forwardInternal(ServletRequestDi
spatcher.java:330)
  at
com.evermind.server.http.HttpRequestHandler.processRequest(HttpRequestHandler.java
:830)
  at com.evermind.server.http.HttpRequestHandler.run(HttpRequestHandler.java:285)
  at com.evermind.server.http.HttpRequestHandler.run(HttpRequestHandler.java:126)
  at
com.evermind.util.ReleasableResourcePooledExecutor$MyWorker.run(ReleasableResource
PooledExecutor.java:186)
  at java.lang.Thread.run(Thread.java:534)
```

Example 24–4 Error in `em-application.log`

```
05/07/01 02:23:03 emd: Portal Configuration Interface failed to initialise:
java.lang.ArrayIndexOutOfBoundsException: Array index out of range: 6
```

```

at java.util.Vector.remove(Vector.java:792)
at oracle.ias.sysmgmt.context.RequestContext.removeLastEntry(Unknown Source)
at oracle.ias.sysmgmt.instrumentation.Timer.stop(Unknown Source)
at oracle.ias.sysmgmt.clientmetadata.MetadataAccessHelper.<init>(Unknown Source)
at oracle.ias.sysmgmt.clientmetadata.MetadataAccessImpl.<init>(Unknown Source)
at oracle.ias.sysmgmt.clientmetadata.MetadataAccessFactory.getInstance(Unknown
Source)
at oracle.ias.sysmgmt.smi.SMIEntryPoint.<init>(Unknown Source)
at sun.reflect.NativeConstructorAccessorImpl.newInstance0(Native Method)
at
sun.reflect.NativeConstructorAccessorImpl.newInstance(NativeConstructorAccesso
rImpl.java:39)
at
sun.reflect.DelegatingConstructorAccessorImpl.newInstance(DelegatingConstructorAcc
essorImpl.java:27)
at java.lang.reflect.Constructor.newInstance(Constructor.java:274)
at oracle.ias.sysmgmt.smiapi.SMISessionManager.loadAndCreateInstance(Unknown
Source)
at oracle.ias.sysmgmt.smiapi.SMISessionManager.createSession(Unknown Source)
at oracle.ias.sysmgmt.EntryPoint.getConfiguration(Unknown Source)
at oracle.webdb.config.smi.GeneralConfig.initialiseEnviroment(Unknown Source)
at oracle.webdb.config.smi.CacheConfig9025Imp.read(Unknown Source)
at oracle.webdb.config.smi.CacheConfigLatestImp.read(Unknown Source)
at oracle.webdb.monitoring.hawkeye.PortalIntegration$InitThread.run(Unknown
Source)

```

Example 24–5 Error in emagent.trc after securing Enterprise Manager Agent and Console

```

2005-07-01 17:27:51 Thread-1505459120 WARN  ssl: fd=20, nmehllssl_write nzos_Write
error = 28862
2005-07-01 17:29:38 Thread-965684144 WARN  ssl: fd=17, nmehllssl_write nzos_Write
error = 28862
2005-07-01 17:32:35 Thread-965684144 WARN  ssl: fd=19, nmehllssl_write nzos_Write
error = 28862
2005-07-01 17:38:35 Thread-965684144 WARN  ssl: fd=19, nmehllssl_write nzos_Write
error = 28862
2005-07-01 17:42:37 Thread-965684144 WARN  ssl: fd=19, nmehllssl_write nzos_Write
error = 28862
2005-07-01 17:48:34 Thread-1235123120 WARN  ssl: fd=18, nmehllssl_write nzos_Write
error = 28862
2005-07-01 17:53:34 Thread-965684144 WARN  ssl: fd=19, nmehllssl_write nzos_Write
error = 28862

```

24.1.23 Enterprise Manager Agent Restarts Periodically When JVM Size Is Full

If the JVM stack size is full, then the Enterprise Manager Agent on your computer will restart periodically and the following error will occur in `emconsole.nohup`:

```

JVM memory size at 2005-08-16 18:04:06 (Total=9969664, Free=0) is 1894192
(pid=23041): emagent now exiting normally

```

To resolve this issue, set the `NormalThreadStackSize` to 524288 in `$ORACLE_HOME/sysman/config/emd.properties` and run the following command:

```
emctl reload
```

This would increase the JVM stack size and stop the agent from restarting.

24.2 Documentation Errata

This section describes documentation errata. It includes the following topic:

- [Section 24.2.1, "Online Help for the Application Server Control All Metrics Page"](#)
- [Section 24.2.2, "Error in Online Help Topic About Regular Expressions"](#)

24.2.1 Online Help for the Application Server Control All Metrics Page

Most of the component home pages within the Application Server Control include an **All Metrics** link. When you click this link, Enterprise Manager displays the All Metrics page, which provides a comprehensive list of all the performance metrics you can monitor for the selected component.

In most cases, you can click a metric name on the All Metrics page to display the Metric Details page, and then click **Help** to get more information about the selected metric.

However, for some metrics, clicking **Help** will display a `Topic not found` error. This problem will be addressed in a future version of Oracle Application Server.

In other cases, the online help provided for a particular metric might refer to features available only when you are centrally managing your application server instance with the Grid Control Console. For example, the online help might refer to thresholds, alerts, or the display of historical data about a metric. In those cases, you can access these additional monitoring features by installing and configuring Grid Control Console.

See Also:

<http://www.oracle.com/technology/documentation/oem.html>

24.2.2 Error in Online Help Topic About Regular Expressions

In the Application Server Control online help topic "About Regular Expressions," the example for the asterisk (*) character shows:

OC4J*

The example should instead show the following:

OC4J.*