

Oracle® Trading Community Architecture

Reference Guide

Release 12

Part No. B25896-01

December 2006

Oracle Trading Community Architecture Reference Guide, Release 12

Part No. B25896-01

Copyright © 2003, 2006, Oracle. All rights reserved.

Primary Author: Essan Ni

Contributing Author: Charlie Ahern, Mathew Daniel, Melanie Heisler

Contributor: Alan Adams, Anupam Bordia, Carol Chow, Mani Desik, Rashmi Goyal, Sherry Jenq, Charity Kocher, Shannon Kreps, Jocelyn Lin, Maria Quinlan, Srinivasa Rangan, Indrajit Sen, Ajay Singh, Adam Stafford, Matt Stitz

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS

Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software--Restricted Rights (June 1987). Oracle Corporation, 500 Oracle Parkway, Redwood City, CA 94065.

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

Oracle, JD Edwards, PeopleSoft, and Siebel are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Contents

Send Us Your Comments

Preface

1 Bulk Import

Bulk Import Interface Tables.....	1-1
HZ_IMP_ADDRESSES_INT.....	1-2
HZ_IMP_ADDRESSUSES_INT.....	1-7
HZ_IMP_CLASSIFICS_INT.....	1-9
HZ_IMP_CONTACTPTS_INT.....	1-11
HZ_IMP_CONTACTROLES_INT.....	1-16
HZ_IMP_CONTACTS_INT.....	1-18
HZ_IMP_CREDITRTNGS_INT.....	1-21
HZ_IMP_FINNUMBERS_INT.....	1-28
HZ_IMP_FINREPORTS_INT.....	1-30
HZ_IMP_PARTIES_INT.....	1-33
HZ_IMP_RELSHIPS_INT.....	1-43

2 Customer Interface

Customer Interface and Bulk Import.....	2-1
Customer Interface Table Descriptions and Validation.....	2-1

3 D&B Data Elements

D&B Data Elements Overview.....	3-1
General Data Elements.....	3-1
Financial Data Elements.....	3-16

4 Seeded Relationship Types, Phrases, and Roles

Relationship Types.....	4-1
Relationship Phrase and Role Pairs.....	4-5
Relationship Phrase and Role Pair Codes.....	4-13

5 Seeded Word Replacement Lists

Seeded Word Replacement Lists.....	5-1
ADDRESS_DICTIONARY.....	5-2
DOMAIN_NAME_DICTIONARY.....	5-20
EXPANDED_PERSON_NAME_DICTIONARY.....	5-21
KEY MODIFIERS.....	5-153
ORGANIZATION_NAME_DICTIONARY.....	5-156
PERSON_NAME_DICTIONARY.....	5-159
US_STATE_DICTIONARY.....	5-202

6 Seeded Attributes and Transformations

Seeded Attributes.....	6-1
Party Attributes.....	6-2
Address Attributes.....	6-12
Contact Attributes.....	6-14
Contact Point Attributes.....	6-16
Seeded Transformations.....	6-18

7 Seeded Match Rules

Seeded Match Rules.....	7-2
General Match Rules.....	7-2
Feature-Specific Match Rules.....	7-4
BULK MATCH: IDENTICAL ORGANIZATIONS.....	7-5
BULK MATCH: IDENTICAL PARTIES.....	7-7
BULK MATCH: IDENTICAL PERSONS.....	7-10
CREDIT MANAGEMENT SEARCH.....	7-12
DL ADDRESS AND RELATIONSHIP SEARCH.....	7-14
DL ADDRESS DEFAULT.....	7-16
DL RELATIONSHIP DEFAULT.....	7-18
DL SMART SEARCH.....	7-21
DL SYSTEM DUPLICATE IDENTIFICATION.....	7-23
HZ_CONTACT_ADV_SEARCH_MATCH_RULE.....	7-25
HZ_CONTACT_SIMPLE_SEARCH_RULE	7-27

HZ_ORG_ADV_SEARCH_RULE.....	7-29
HZ_ORG_SIMPLE_SEARCH_RULE.....	7-31
HZ_PERSON_ADVANCED_SEARCH_MATCH_RULE.....	7-33
HZ_PERSON_SIMPLE_SEARCH_RULE.....	7-36
RM SEARCH RULE.....	7-38
SAMPLE: ADDRESS_ORGANIZATIONS.....	7-41
SAMPLE: ADDRESS_PERSONS.....	7-42
SAMPLE: ADVANCED SEARCH RULE.....	7-44
SAMPLE: BASIC SEARCH RULE.....	7-47
SAMPLE: ORGANIZATIONS_OPTIMIZED.....	7-50
SAMPLE: PERSON_OPTIMIZED.....	7-52
SAMPLE: SEARCH.....	7-53
SAMPLE: SEARCH ADDRESS ORGANIZATIONS EXACT.....	7-56
SAMPLE: SEARCH EXACT.....	7-57
SAMPLE: SEARCH SIMILAR ORGANIZATION EXACT.....	7-61
SAMPLE: SEARCH SIMILAR PERSON EXACT.....	7-63
SAMPLE: SIMILAR_ORGANIZATION.....	7-65
SAMPLE: SIMILAR_PERSON.....	7-67

8 Party and Account Merge Impact

Party and Account Merge Impact Overview.....	8-1
Party Merge Impact.....	8-2
Party Merge Impact Reference by Application.....	8-22
Account Merge Impact.....	8-36
Account Merge Impact Reference by Application.....	8-49

Glossary

Send Us Your Comments

Oracle Trading Community Architecture Reference Guide, Release 12

Part No. B25896-01

Oracle welcomes customers' comments and suggestions on the quality and usefulness of this document. Your feedback is important, and helps us to best meet your needs as a user of our products. For example:

- Are the implementation steps correct and complete?
- Did you understand the context of the procedures?
- Did you find any errors in the information?
- Does the structure of the information help you with your tasks?
- Do you need different information or graphics? If so, where, and in what format?
- Are the examples correct? Do you need more examples?

If you find any errors or have any other suggestions for improvement, then please tell us your name, the name of the company who has licensed our products, the title and part number of the documentation and the chapter, section, and page number (if available).

Note: Before sending us your comments, you might like to check that you have the latest version of the document and if any concerns are already addressed. To do this, access the new Applications Release Online Documentation CD available on Oracle MetaLink and www.oracle.com. It contains the most current Documentation Library plus all documents revised or released recently.

Send your comments to us using the electronic mail address: appsdoc_us@oracle.com

Please give your name, address, electronic mail address, and telephone number (optional).

If you need assistance with Oracle software, then please contact your support representative or Oracle Support Services.

If you require training or instruction in using Oracle software, then please contact your Oracle local office and inquire about our Oracle University offerings. A list of Oracle offices is available on our Web site at www.oracle.com.

Preface

Intended Audience

Welcome to Release 12 of the *Oracle Trading Community Architecture Reference Guide*.

This guide assumes you have a working knowledge of the following:

- The principles and customary practices of your business area.
- Computer desktop application usage and terminology.

If you have never used Oracle Applications, we suggest you attend one or more of the Oracle Applications training classes available through Oracle University.

See Related Information Sources on page x for more Oracle Applications product information.

TTY Access to Oracle Support Services

Oracle provides dedicated Text Telephone (TTY) access to Oracle Support Services within the United States of America 24 hours a day, seven days a week. For TTY support, call 800.446.2398.

Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site

at <http://www.oracle.com/accessibility/>.

Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

Structure

- 1 Bulk Import**
- 2 Customer Interface**
- 3 D&B Data Elements**
- 4 Seeded Relationship Types, Phrases, and Roles**
- 5 Seeded Word Replacement Lists**
- 6 Seeded Attributes and Transformations**
- 7 Seeded Match Rules**
- 8 Party and Account Merge Impact**
- Glossary**

Related Information Sources

This document is included on the Oracle Applications Document Library, which is supplied in the Release 12 DVD Pack. You can download soft-copy documentation as PDF files from the Oracle Technology Network at <http://otn.oracle.com/documentation>, or you can purchase hard-copy documentation from the Oracle Store at <http://oraclestore.oracle.com>. The Oracle E-Business Suite Documentation Library Release 12 contains the latest information, including any documents that have changed significantly between releases. If substantial changes to this book are necessary, a revised version will be made available on the online documentation CD on Oracle *MetaLink*.

If this guide refers you to other Oracle Applications documentation, use only the Release 12 versions of those guides.

For a full list of documentation resources for Oracle Applications Release 12, see Oracle Applications Documentation Resources, Release 12, Oracle *MetaLink* Document 394692.1.

Online Documentation

All Oracle Applications documentation is available online (HTML or PDF).

- **PDF** - PDF documentation is available for download from the Oracle Technology Network at <http://otn.oracle.com/documentation>.
- **Online Help** - Online help patches (HTML) are available on *OracleMetaLink*.
- **Oracle MetaLink Knowledge Browser** - The *OracleMetaLink* Knowledge Browser lets you browse the knowledge base, from a single product page, to find all documents for that product area. Use the Knowledge Browser to search for release-specific information, such as FAQs, recent patches, alerts, white papers, troubleshooting tips, and other archived documents.
- **Oracle eBusiness Suite Electronic Technical Reference Manuals** - Each Electronic Technical Reference Manual (eTRM) contains database diagrams and a detailed description of database tables, forms, reports, and programs for a specific Oracle Applications product. This information helps you convert data from your existing applications and integrate Oracle Applications data with non-Oracle applications, and write custom reports for Oracle Applications products. Oracle eTRM is available on *OracleMetaLink*.

Related Guides

You should have the following related books on hand. Depending on the requirements of your particular installation, you may also need additional manuals or guides.

Oracle Applications Installation Guide: Using Rapid Install:

This book is intended for use by anyone who is responsible for installing or upgrading Oracle Applications. It provides instructions for running Rapid Install either to carry out a fresh installation of Oracle Applications Release 12, or as part of an upgrade from Release 11i to Release 12. The book also describes the steps needed to install the technology stack components only, for the special situations where this is applicable.

Oracle Applications Maintenance Procedures:

This guide describes how to use AD maintenance utilities to complete tasks such as compiling invalid objects, managing parallel processing jobs, and maintaining snapshot information. Part of Maintaining Oracle Applications, a 3-book set that also includes Oracle Applications Patching Procedures and Oracle Applications Maintenance Utilities.

Oracle Applications Maintenance Utilities:

This guide describes how to run utilities, such as AD Administration and AD Controller, used to maintain the Oracle Applications file system and database. Outlines the actions performed by these utilities, such as monitoring parallel processes, generating Applications files, and maintaining Applications database entities. Part of Maintaining Oracle Applications, a 3-book set that also includes Oracle Applications Patching Procedures and Oracle Applications Maintenance Procedures.

Oracle Applications Patching Procedures:

This guide describes how to patch the Oracle Applications file system and database using AutoPatch, and how to use other patching-related tools like AD Merge Patch, OAM Patch Wizard, and OAM Registered Flagged Files. Describes patch types and structure, and outlines some of the most commonly used patching procedures. Part of Maintaining Oracle Applications, a 3-book set that also includes Oracle Applications Maintenance Utilities and Oracle Applications Maintenance Procedures.

Oracle Applications Upgrade Guide: Release 11i to Release 12:

This guide provides information for DBAs and Applications Specialists who are responsible for upgrading a Release 11i Oracle Applications system (techstack and products) to Release 12. In addition to information about applying the upgrade driver, it outlines pre-upgrade steps and post-upgrade steps, and provides descriptions of product-specific functional changes and suggestions for verifying the upgrade and reducing downtime.

Oracle Alert User's Guide:

This guide explains how to define periodic and event alerts to monitor the status of your Oracle Applications data.

Oracle Application Framework Developer's Guide:

This guide contains the coding standards followed by the Oracle Applications development staff to produce applications built with Oracle Application Framework. This guide is available in PDF format on *OracleMetaLink* and as online documentation in JDeveloper 10g with Oracle Application Extension.

Oracle Application Framework Personalization Guide:

This guide covers the design-time and run-time aspects of personalizing applications built with Oracle Application Framework.

Oracle Applications Concepts:

This book is intended for all those planning to deploy Oracle E-Business Suite Release 12, or contemplating significant changes to a configuration. After describing the Oracle Applications architecture and technology stack, it focuses on strategic topics, giving a broad outline of the actions needed to achieve a particular goal, plus the installation and configuration choices that may be available.

Oracle Applications Developer's Guide:

This guide contains the coding standards followed by the Oracle Applications development staff. It describes the Oracle Application Object Library components needed to implement the Oracle Applications user interface described in the *Oracle Applications User Interface Standards for Forms-Based Products*. It also provides information to help you build your custom Oracle Forms Developer forms so that they integrate with Oracle Applications.

Oracle Applications Flexfields Guide:

This guide provides flexfields planning, setup, and reference information for the Oracle Applications implementation team, as well as for users responsible for the ongoing

maintenance of Oracle Applications product data. This guide also provides information on creating custom reports on flexfields data.

Oracle Applications Supportability Guide:

This manual contains information on Oracle Diagnostics and the Logging Framework for system administrators and custom developers.

Oracle Applications System Administrator's Guide Documentation Set:

This documentation set provides planning and reference information for the Oracle Applications System Administrator. *Oracle Applications System Administrator's Guide - Configuration* contains information on system configuration steps, including defining concurrent programs and managers, enabling Oracle Applications Manager features, and setting up printers and online help. *Oracle Applications System Administrator's Guide - Maintenance* provides information for frequent tasks such as monitoring your system with Oracle Applications Manager, managing concurrent managers and reports, using diagnostic utilities, managing profile options, and using alerts. *Oracle Applications System Administrator's Guide - Security* describes User Management, data security, function security, auditing, and security configurations.

Oracle Applications User Interface Standards for Forms-Based Products:

This guide contains the user interface (UI) standards followed by the Oracle Applications development staff. It describes the UI for the Oracle Applications products and how to apply this UI to the design of an application built by using Oracle Forms.

Oracle Applications User's Guide:

This guide explains how to navigate, enter data, query, and run reports using the user interface (UI) of Oracle Applications. This guide also includes information on setting user profiles, as well as running and reviewing concurrent requests.

Oracle Integration Repository User's Guide:

This guide covers the employment of Oracle Integration Repository in researching and deploying business interfaces to produce integrations between applications.

Oracle Workflow Administrator's Guide:

This guide explains how to complete the setup steps necessary for any product that includes workflow-enabled processes. It also describes how to manage workflow processes and business events using Oracle Applications Manager, how to monitor the progress of runtime workflow processes, and how to administer notifications sent to workflow users.

Oracle Workflow API Reference:

This guide describes the APIs provided for developers and administrators to access Oracle Workflow.

Oracle Workflow Developer's Guide:

This guide explains how to define new workflow business processes and customize existing Oracle Applications-embedded workflow processes. It also describes how to

define and customize business events and event subscriptions.

Oracle Workflow User's Guide:

This guide describes how users can view and respond to workflow notifications and monitor the progress of their workflow processes.

Oracle Financials and Oracle Procurement Functional Upgrade Guide: Release 11i to Release 12:

This guides provides detailed information about the functional impacts of upgrading Oracle Financials and Oracle Procurement products from Release 11i to Release 12. This guide supplements the *Oracle Applications Upgrade Guide: Release 11i to Release 12*.

Oracle Financials Concepts Guide:

This guide describes the fundamental concepts of Oracle Financials. The guide is intended to introduce readers to the concepts used in the applications, and help them compare their real world business, organization, and processes to those used in the applications.

Oracle Financials Glossary:

The glossary includes definitions of common terms that are shared by all Oracle Financials products. In some cases, there may be different definitions of the same term for different Financials products. If you are unsure of the meaning of a term you see in an Oracle Financials guide, please refer to the glossary for clarification. You can find the glossary in the online help or in the *Oracle Financials Implementation Guide*.

Oracle Financials Implementation Guide:

This guide provides information on how to implement the Oracle Financials E-Business Suite. It guides you through setting up your organizations, including legal entities, and their accounting, using the Accounting Setup Manager. It covers intercompany accounting and sequencing of accounting entries, and it provides examples.

Oracle Customer Data Librarian Implementation Guide:

This guide describes how to implement Oracle Customer Data Librarian. As part of implementing Oracle Customer Data Librarian, you must also complete all the implementation steps for Oracle Customers Online.

Oracle Customer Data Librarian User Guide:

This guide describes how to use Oracle Customer Data Librarian to establish and maintain the quality of the Trading Community Architecture Registry, focusing on consolidation, cleanliness, and completeness. Oracle Customer Data Librarian has all of the features in Oracle Customers Online, and is also part of the Oracle Customer Data Management product family.

Oracle Customers Online Implementation Guide:

This guide describes how to implement Oracle Customers Online.

Oracle Customers Online User Guide:

This guide describes how to use Oracle Customers Online to view, create, and maintain your customer information. Oracle Customers Online is based on Oracle Trading Community Architecture data model and functionality, and is also part of the Oracle Customer Data Management product family.

Oracle Receivables Implementation Guide:

This guide provides you with information on how to implement Oracle Receivables. Use this guide to understand the implementation steps required for application use, including how to set up customers, transactions, receipts, accounting, tax, and collections. This guide also includes a comprehensive list of profile options that you can set to customize application behavior.

Oracle Receivables Reference Guide:

This guide provides you with detailed information about all public application programming interfaces (APIs) that you can use to extend Oracle Receivables functionality. This guide also describes the Oracle Receivables open interfaces, such as AutoLockbox which lets you create and apply receipts and AutoInvoice which you can use to import and validate transactions from other systems. Archiving and purging Receivables data is also discussed in this guide.

Oracle Receivables User Guide:

This guide provides you with information on how to use Oracle Receivables. Use this guide to learn how to create and maintain transactions and bills receivable, enter and apply receipts, enter customer information, and manage revenue. This guide also includes information about accounting in Receivables. Use the Standard Navigation Paths appendix to find out how to access each Receivables window.

Oracle Trading Community Architecture Administration Guide:

This guide describes how to administer and implement Oracle Trading Community Architecture (TCA). You set up, control, and manage functionality that affects data in the TCA Registry. It also describes how to set up and use Resource Manager to manage resources.

Oracle Trading Community Architecture Technical Implementation Guide:

This guide explains how to use the public Oracle Trading Community Architecture application programming interfaces (APIs) and develop callouts based on Oracle Workflow Business Events System (BES). For each API, this guide provides a description of the API, the PL/SQL procedure, and the Java method, as well as a table of the parameter descriptions and validations. For each BES callout, this guide provides the name of the logical entity, its description, and the ID parameter name. Also included are setup instructions and sample code.

Oracle Trading Community Architecture User Guide:

This guide describes the Oracle Trading Community Architecture (TCA) and how to use features from the Trading Community Manager responsibility to create, update, enrich, and cleanse the data in the TCA Registry. It also describes how to use Resource Manager to define and manage resources.

Integration Repository

The Oracle Integration Repository is a compilation of information about the service endpoints exposed by the Oracle E-Business Suite of applications. It provides a complete catalog of Oracle E-Business Suite's business service interfaces. The tool lets users easily discover and deploy the appropriate business service interface for integration with any system, application, or business partner.

The Oracle Integration Repository is shipped as part of the E-Business Suite. As your instance is patched, the repository is automatically updated with content appropriate for the precise revisions of interfaces in your environment.

Do Not Use Database Tools to Modify Oracle Applications Data

Oracle **STRONGLY RECOMMENDS** that you never use SQL*Plus, Oracle Data Browser, database triggers, or any other tool to modify Oracle Applications data unless otherwise instructed.

Oracle provides powerful tools you can use to create, store, change, retrieve, and maintain information in an Oracle database. But if you use Oracle tools such as SQL*Plus to modify Oracle Applications data, you risk destroying the integrity of your data and you lose the ability to audit changes to your data.

Because Oracle Applications tables are interrelated, any change you make using an Oracle Applications form can update many tables at once. But when you modify Oracle Applications data using anything other than Oracle Applications, you may change a row in one table without making corresponding changes in related tables. If your tables get out of synchronization with each other, you risk retrieving erroneous information and you risk unpredictable results throughout Oracle Applications.

When you use Oracle Applications to modify your data, Oracle Applications automatically checks that your changes are valid. Oracle Applications also keeps track of who changes information. If you enter information into database tables using database tools, you may store invalid information. You also lose the ability to track who has changed your information because SQL*Plus and other database tools do not keep a record of changes.

Bulk Import

This chapter covers the following topics:

- Bulk Import Interface Tables
- HZ_IMP_ADDRESSES_INT
- HZ_IMP_ADDRESSUSES_INT
- HZ_IMP_CLASSIFICS_INT
- HZ_IMP_CONTACTPTS_INT
- HZ_IMP_CONTACTROLES_INT
- HZ_IMP_CONTACTS_INT
- HZ_IMP_CREDITRTNGS_INT
- HZ_IMP_FINNUMBERS_INT
- HZ_IMP_FINREPORTS_INT
- HZ_IMP_PARTIES_INT
- HZ_IMP_RELSHIPS_INT

Bulk Import Interface Tables

The interface tables for TCA Bulk Import are:

- HZ_IMP_ADDRESSES_INT, page 1-2
- HZ_IMP_ADDRESSUSES_INT, page 1-7
- HZ_IMP_CLASSIFICS_INT, page 1-9
- HZ_IMP_CONTACTPTS_INT, page 1-11
- HZ_IMP_CONTACTROLES_INT, page 1-16

- HZ_IMP_CONTACTS_INT, page 1-18
- HZ_IMP_CREDITRTNGS_INT, page 1-21
- HZ_IMP_FINNUMBERS_INT, page 1-28
- HZ_IMP_FINREPORTS_INT, page 1-30
- HZ_IMP_PARTIES_INT, page 1-33
- HZ_IMP_RELSHIPS_INT, page 1-43

Aside from the validations specified for each column, you should also be familiar with general validations that apply for entering data, for example through user interfaces.

If a column is described as not updateable, the import process ignores any passed value unless specified otherwise. This rule applies only to interface table records that update existing records in the TCA Registry.

Refer to the *Oracle eBusiness Suite Electronic Technical Reference Manual* for additional information about the interface tables, including:

- Description of the column value
- Data type
- Column length
- Requirement, whether the column needs a value or can be left null

Related Topics

Loading Data into the Interface Tables, *Oracle Trading Community Architecture User Guide*

HZ_IMP_ADDRESSES_INT

The HZ_IMP_ADDRESSES_INT table contains address information to be imported into these TCA tables:

- HZ_LOCATIONS
- HZ_PARTY_SITES

This table lists the columns in the interface table, as well as the validation and destination.

Column	Validation	Destination
BATCH_ID	Mandatory	None
PARTY_ORIG_SYSTEM	- Mandatory - ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM
PARTY_ORIG_SYSTEM_REFERENCE	Mandatory	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM_REFERENCE
SITE_ORIG_SYSTEM	- Mandatory - ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM
SITE_ORIG_SYSTEM_REFERENCE	Mandatory	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM_REFERENCE
INSERT_UPDATE_FLAG	<i>I, U, or NULL</i>	None
CORRECT_MOVE_INDICATOR	<i>C, M, or NULL</i>	None
ADDRESS1	- Mandatory for records to be inserted as new - Cannot be updated to NULL	HZ_LOCATIONS.ADDRESS1
ADDRESS2	None	HZ_LOCATIONS.ADDRESS2
ADDRESS3	None	HZ_LOCATIONS.ADDRESS3
ADDRESS4	None	HZ_LOCATIONS.ADDRESS4
ADDRESS_LINES_PHONETIC	None	HZ_LOCATIONS.ADDRESS_LINES_PHONETIC
CITY	None	HZ_LOCATIONS.CITY
CLLI_CODE	None	HZ_LOCATIONS.CLLI_CODE

Column	Validation	Destination
COUNTRY	- Mandatory for records to be inserted as new - Cannot be updated to NULL - Foreign key to FND_TERRITORIES.TERRITORY_CODE	HZ_LOCATIONS.COUNTRY
COUNTY	None	HZ_LOCATIONS.COUNTY
DELIVERY_POINT_CODE	None	HZ_LOCATIONS.DELIVERY_POINT_CODE
DESCRIPTION	None	HZ_LOCATIONS.DESCRPTION
LANGUAGE	Foreign key to FND_LANGUAGES.LANGUAGE_CODE with INSTALLED_FLAG in <i>B</i> (Base Language) or <i>I</i> (Installed Language)	HZ_LOCATIONS.LANGUAGE
LOCATION_DIRECTIONS	None	HZ_LOCATIONS.LOCATION_DIRECTIONS
POSTAL_CODE	None	HZ_LOCATIONS.POSTAL_CODE
POSTAL_PLUS4_CODE	None	HZ_LOCATIONS.POSTAL_PLUS4_CODE
PROVINCE	None	HZ_LOCATIONS.PROVINCE
SALES_TAX_GEOCODE	None	HZ_LOCATIONS.SALES_TAX_GEOCODE
SALES_TAX_INSIDE_CITY_LIMITS	None	HZ_LOCATIONS.SALES_TAX_INSIDE_CITY_LIMITS
SHORT_DESCRIPTION	None	HZ_LOCATIONS.SHORT_DESCRIPTION
STATE	None	HZ_LOCATIONS.STATE

Column	Validation	Destination
TIMEZONE_CODE	Foreign key to HZ_TIMEZONES.TIMEZONE_ID	HZ_LOCATIONS.TIMEZONE_ID
ATTRIBUTE_CATEGORY	None	HZ_LOCATIONS.ATTRIBUTE_CATEGORY
ATTRIBUTE1 to ATTRIBUTE20	None	HZ_LOCATIONS.ATTRIBUTE1 to HZ_LOCATIONS.ATTRIBUTE20
ADDRESS1_STD	- Mandatory for records to be inserted as new - Cannot be updated to NULL	HZ_LOCATIONS.ADDRESS1
ADDRESS2_STD	None	HZ_LOCATIONS.ADDRESS2
ADDRESS3_STD	None	HZ_LOCATIONS.ADDRESS3
ADDRESS4_STD	None	HZ_LOCATIONS.ADDRESS4
CITY_STD	None	HZ_LOCATIONS.CITY
PROV_STATE_ADMIN_CODE_STD	None	HZ_LOCATIONS.STATE if HZ_IMP_ADDRESSES_INT.STATE is not null. Otherwise, HZ_LOCATIONS.PROVINCE if HZ_IMP_ADDRESSES_INT.PROVINCE is not null. If both HZ_IMP_ADDRESSES_INT.STATE and HZ_IMP_ADDRESSES_INT.PROVINCE are null, then HZ_LOCATIONS.STATE.
COUNTY_STD	None	HZ_LOCATIONS.COUNTY

Column	Validation	Destination
COUNTRY_STD	- Mandatory - Foreign key to FND_TERRITORIES.TERRITORY_CODE	HZ_LOCATIONS.COUNTRY
POSTAL_CODE_STD	None	HZ_LOCATIONS.POSTAL_CODE
ACCEPT_STANDARDIZED_FLAG	None	None
ADAPTER_CONTENT_SOURCE	None	None
ADDR_VALID_STATUS_CODE	Populate only if ACCEPT_STANDARDIZED_FLAG is Y	HZ_LOCATIONS.VALIDATION_STATUS_CODE
DATE_VALIDATED	- Populate only if ACCEPT_STANDARDIZED_FLAG is Y - Cannot pass for update if CONTENT_SOURCE_TYPE in HZ_LOCATIONS is USER_ENTERED	HZ_LOCATIONS.DATE_VALIDATED
PARTY_SITE_NAME	None	HZ_PARTY_SITES.PARTY_SITE_NAME
PARTY_SITE_NUMBER	- Not updateable - Cannot be updated to NULL - Must be unique - Use value if passed; otherwise, automatically generate from sequence	HZ_PARTY_SITES.PARTY_SITE_NUMBER
INTERFACE_STATUS	None	None
ACTION_FLAG	None	None

Column	Validation	Destination
ERROR_ID	None	None
CREATION_DATE	None	None
VALIDATION_BATCH_ID	None	None
CREATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_DATE	None	None
LAST_UPDATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_LOGIN	Foreign key to FND_LOGINS.LOGIN_ID	None
REQUEST_ID	Foreign key to FND_CONCURRENT_REQUESTS. REQUEST_ID	None
PROGRAM_APPLICATION_ID	Foreign key to FND_APPLICATION.APPLICATION_ID	None
PROGRAM_ID	Foreign key to FND_CONCURRENT_PROGRAM. CONCURRENT_PROGRAM_ID	None
PROGRAM_UPDATE_DATE	None	None
CREATED_BY_MODULE	Mandatory and not updateable unless current value in TCA is NULL	HZ_PARTY_SITES.CREATED_BY_ MODULE
PRIMARY_FLAG	Y, N, or NULL	HZ_PARTY_SITES.IDENTIFYING_ ADDRESS_FLAG

HZ_IMP_ADDRESSUSES_INT

The HZ_IMP_ADDRESSUSES_INT table contains address use information to be imported into the TCA table HZ_PARTY_SITE_USES.

This table lists the columns in the interface table, as well as the validation and

destination.

Column	Validation	Destination
BATCH_ID	Mandatory	None
PARTY_ORIG_SYSTEM	- Mandatory - ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM
PARTY_ORIG_SYSTEM_REFERENCE	Mandatory	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM_REFERENCE
SITE_ORIG_SYSTEM	- Mandatory - ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM
SITE_ORIG_SYSTEM_REFERENCE	Mandatory	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM_REFERENCE
INSERT_UPDATE_FLAG	<i>I, U, or NULL</i>	None
SITE_USE_TYPE	- Mandatory and not updateable - PARTY_SITE_USE_CODE lookup - Combination of SITE_USE_TYPE and PARTY_SITE_ID must be unique for active party site use records	HZ_PARTY_SITE_USES.SITE_USE_TYPE
INTERFACE_STATUS	None	None
ACTION_FLAG	None	None
ERROR_ID	None	None
CREATION_DATE	None	None
CREATED_BY	Foreign key to FND_USER.USER_ID	None

Column	Validation	Destination
LAST_UPDATE_DATE	None	None
LAST_UPDATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_LOGIN	Foreign key to FND_LOGINS.LOGIN_ID	None
REQUEST_ID	Foreign key to FND_CONCURRENT_REQUESTS. REQUEST_ID	None
PROGRAM_APPLICATION_ID	Foreign key to FND_APPLICATION.APPLICATION_ID	None
PROGRAM_ID	Foreign key to FND_CONCURRENT_PROGRAM. CONCURRENT_PROGRAM_ID	None
PROGRAM_UPDATE_DATE	None	None
CREATED_BY_MODULE	Mandatory and not updateable unless current value in TCA is NULL	HZ_PARTY_SITES.CREATED_BY_ MODULE
PRIMARY_FLAG	Y, N, or NULL	HZ_PARTY_SITE_USES.PRIMARY_ FLAG

HZ_IMP_CLASSIFICS_INT

The HZ_IMP_CLASSIFICS_INT table contains classification information to be imported into the TCA table HZ_CODE_ASSIGNMENTS.

Within the same content source type, there should be no overlapping assignments for the same party and classification, or class category and class code combination.

This table lists the columns in the interface table, as well as the validation and destination.

Column	Validation	Destination
BATCH_ID	Mandatory	None
PARTY_ORIG_SYSTEM	• Mandatory • ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM
PARTY_ORIG_SYSTEM_REFERENCE	Mandatory	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM_REFERENCE
INSERT_UPDATE_FLAG	<i>I, U, or NULL</i>	None
CLASS_CATEGORY	• Mandatory and not updateable • Cannot be updated to NULL • Foreign key to HZ_CLASS_CATEGORIES	HZ_CODE_ASSIGNMENTS.CLASS_CATEGORY
CLASS_CODE	• Mandatory and not updateable • Cannot be updated to NULL • Must be a valid lookup code from the lookup type same as class category	HZ_CODE_ASSIGNMENTS.CLASS_CODE
START_DATE_ACTIVE	• Mandatory • Cannot be updated to NULL	HZ_CODE_ASSIGNMENTS.START_DATE_ACTIVE
END_DATE_ACTIVE	Must be NULL or greater than START_DATE_ACTIVE	HZ_CODE_ASSIGNMENTS.END_DATE_ACTIVE
RANK	None	HZ_CODE_ASSIGNMENTS.RANK
INTERFACE_STATUS	None	None
ACTION_FLAG	None	None
ERROR_ID	None	None

Column	Validation	Destination
CREATION_DATE	None	None
CREATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_DATE	None	None
LAST_UPDATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_LOGIN	Foreign key to FND_LOGINS.LOGIN_ID	None
REQUEST_ID	Foreign key to FND_CONCURRENT_REQUESTS. REQUEST_ID	None
PROGRAM_APPLICATION_ID	Foreign key to FND_APPLICATION.APPLICATION ID	None
PROGRAM_ID	Foreign key to FND_CONCURRENT_PROGRAM. CONCURRENT_PROGRAM_ID	None
PROGRAM_UPDATE_DATE	None	None
CREATED_BY_MODULE	Mandatory	HZ_CODE_ASSIGNMENTS.CREATED_BY_MODULE
PRIMARY_FLAG	Y, N, or NULL	HZ_CODE_ASSIGNMENTS.PRIMARY_FLAG

HZ_IMP_CONTACTPTS_INT

The HZ_IMP_CONTACTPTS_INT table contains contact point information to be imported into the TCA table HZ_CONTACT_POINTS.

This table lists the columns in the interface table, as well as the validation and destination.

Column	Validation	Destination
BATCH_ID	Mandatory	None
CP_ORIG_SYSTEM	• Mandatory • ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM
CP_ORIG_SYSTEM_REFERENCE	Mandatory	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM_REFERENCE
PARTY_ORIG_SYSTEM	• Mandatory • ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM
PARTY_ORIG_SYSTEM_REFERENCE	Mandatory	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM_REFERENCE
SITE_ORIG_SYSTEM	ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM
SITE_ORIG_SYSTEM_REFERENCE	None	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM_REFERENCE
INSERT_UPDATE_FLAG	<i>I, U, or NULL</i>	None
CONTACT_POINT_TYPE	• Mandatory for inserts and not updateable • <i>EDI</i> value allowed only for party of type Organization • COMMUNICATION_TYPE lookup • Cannot be updated to NULL	HZ_CONTACT_POINTS.CONTACT_POINT_TYPE
CONTACT_POINT_PURPOSE	CONTACT_POINT_PURPOSE lookup. If <i>WEB</i> for CONTACT_POINT_TYPE, then CONTACT_POINT_PURPOSE_WEB lookup.	HZ_CONTACT_POINTS.CONTACT_POINT_PURPOSE

Column	Validation	Destination
EDI_ECE_TP_LOCATION_CODE	None	HZ_CONTACT_POINTS.EDI_ECE_TP_LOCATION_CODE
EDI_ID_NUMBER	Mandatory if CONTACT_POINT_TYPE is <i>EDI</i>	HZ_CONTACT_POINTS.EDI_ID_NUMBER
EDI_PAYMENT_FORMAT	None	HZ_CONTACT_POINTS.EDI_PAYMENT_FORMAT
EDI_PAYMENT_METHOD	None	HZ_CONTACT_POINTS.EDI_PAYMENT_METHOD
EDI_REMITTANCE_INSTRUCTION	None	HZ_CONTACT_POINTS.EDI_REMITTANCE_INSTRUCTION
EDI_REMITTANCE_METHOD	None	HZ_CONTACT_POINTS.EDI_REMITTANCE_METHOD
EDI_TP_HEADER_ID	None	HZ_CONTACT_POINTS.EDI_TP_HEADER_ID
EDI_TRANSACTION_HANDLING	None	HZ_CONTACT_POINTS.EDI_TRANSACTION_HANDLING
EFT_PRINTING_PROGRAM_ID	None	HZ_CONTACT_POINTS.EFT_PRINTING_PROGRAM_ID
EFT_SWIFT_CODE	None	HZ_CONTACT_POINTS.EFT_SWIFT_CODE
EFT_TRANSMISSION_PROGRAM_ID	None	HZ_CONTACT_POINTS.EFT_TRANSMISSION_PROGRAM_ID
EFT_USER_NUMBER	None	HZ_CONTACT_POINTS.EFT_USER_NUMBER
EMAIL_ADDRESS	Mandatory if CONTACT_POINT_TYPE is <i>EMAIL</i>	HZ_CONTACT_POINTS.EMAIL_ADDRESS

Column	Validation	Destination
EMAIL_FORMAT	If CONTACT_POINT_TYPE is <i>EMAIL</i> : - Cannot update to NULL - EMAIL_FORMAT lookup	HZ_CONTACT_POINTS.EMAIL_FORMAT
PHONE_AREA_CODE	None	HZ_CONTACT_POINTS.PHONE_AREA_CODE
PHONE_CALLING_CALENDAR	None	HZ_CONTACT_POINTS.PHONE_CALLING_CALENDAR
PHONE_COUNTRY_CODE	Foreign key to HZ_PHONE_COUNTRY_CODES.PHONE_COUNTRY_CODE if CONTACT_POINT_TYPE is <i>PHONE</i>	HZ_CONTACT_POINTS.PHONE_COUNTRY_CODE
PHONE_EXTENSION	None	HZ_CONTACT_POINTS.PHONE_EXTENSION
PHONE_LINE_TYPE	- Mandatory if CONTACT_POINT_TYPE is <i>PHONE</i> - PHONE_LINE_TYPE lookup	HZ_CONTACT_POINTS.PHONE_LINE_TYPE
PHONE_NUMBER	If CONTACT_POINT_TYPE is <i>PHONE</i> , either PHONE_NUMBER or RAW_PHONE_NUMBER must be passed, but not both at the same time	HZ_CONTACT_POINTS.PHONE_NUMBER
RAW_PHONE_NUMBER	If CONTACT_POINT_TYPE is <i>PHONE</i> , either PHONE_NUMBER or RAW_PHONE_NUMBER must be passed, but not both at the same time	HZ_CONTACT_POINTS.RAW_PHONE_NUMBER
TELEX_NUMBER	Mandatory if CONTACT_POINT_TYPE is <i>TLX</i>	HZ_CONTACT_POINTS.TELEX_NUMBER

Column	Validation	Destination
TIMEZONE_CODE	Foreign key to HZ_TIMEZONES.TIMEZONE_ID if CONTACT_POINT_TYPE is <i>PHONE</i>	HZ_CONTACT_POINTS.TIMEZONE_ID
URL	Mandatory if CONTACT_POINT_TYPE is <i>WEB</i>	HZ_CONTACT_POINTS.URL
WEB_TYPE	Mandatory if CONTACT_POINT_TYPE is <i>WEB</i>	HZ_CONTACT_POINTS.WEB_TYPE
ATTRIBUTE_CATEGORY	None	HZ_CONTACT_POINTS.ATTRIBUTE_CATEGORY
ATTRIBUTE1 TO ATTRIBUTE20	None	HZ_CONTACT_POINTS.ATTRIBUTE1 to HZ_CONTACT_POINTS.ATTRIBUTE20
INTERFACE_STATUS	None	None
ACTION_FLAG	None	None
ERROR_ID	None	None
CREATION_DATE	None	None
CREATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_DATE	None	None
LAST_UPDATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_LOGIN	Foreign key to FND_LOGINS.LOGIN_ID	None
REQUEST_ID	Foreign key to FND_CONCURRENT_REQUESTS.REQUEST_ID	None

Column	Validation	Destination
PROGRAM_APPLICATION_ID	Foreign key to FND_APPLICATION.APPLICATION_ID	None
PROGRAM_ID	Foreign key to FND_CONCURRENT_PROGRAM.CONCURRENT_PROGRAM_ID	None
PROGRAM_UPDATE_DATE	None	None
CREATED_BY_MODULE	Mandatory and not updateable unless current value in TCA is NULL	HZ_CONTACT_POINTS.CREATED_BY_MODULE
PRIMARY_FLAG	Y, N, or NULL	HZ_CONTACT_POINTS.PRIMARY_FLAG

HZ_IMP_CONTACTROLES_INT

The HZ_IMP_CONTACTROLES_INT table contains contact role information to be imported into the TCA table HZ_ORG_CONTACT_ROLES.

This table lists the columns in the interface table, as well as the validation and destination.

Column	Validation	Destination
BATCH_ID	Mandatory	None
CONTACT_ORIG_SYSTEM	- Mandatory - ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM
CONTACT_ORIG_SYSTEM_REFERENCE	Mandatory	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM_REFERENCE
SUB_ORIG_SYSTEM	- Mandatory - ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM

Column	Validation	Destination
SUB_ORIG_SYSTEM_REFERENCE	Mandatory	HZ_ORIG_SYS_REFERENCES.ORG_SYSTEM_REFERENCE
INSERT_UPDATE_FLAG	I, U, or NULL	None
ROLE_TYPE	• Mandatory • Cannot be updated to NULL • CONTACT_ROLE_TYPE lookup • Combination of ROLE_TYPE and ORG_CONTACT_ID must be unique	HZ_ORG_CONTACT_ROLES.ROLE_TYPE
INTERFACE_STATUS	None	None
ACTION_FLAG	None	None
ERROR_ID	None	None
CREATION_DATE	None	None
CREATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_DATE	None	None
LAST_UPDATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_LOGIN	Foreign key to FND_LOGINS.LOGIN_ID	None
REQUEST_ID	Foreign key to FND_CONCURRENT_REQUESTS.REQUEST_ID	None
PROGRAM_APPLICATION_ID	Foreign key to FND_APPLICATION.APPLICATION_ID	None

Column	Validation	Destination
PROGRAM_ID	Foreign key to FND_CONCURRENT_PROGRAM. CONCURRENT_PROGRAM_ID	None
PROGRAM_UPDATE_DATE	None	None
CREATED_BY_MODULE	Mandatory and not updateable unless current value in TCA is NULL	HZ_ORG_CONTACT_ROLES.CRE ATED_BY_MODULE

HZ_IMP_CONTACTS_INT

The HZ_IMP_CONTACTS_INT table contains contact information to be imported into these TCA tables:

- HZ_RELATIONSHIPS
- HZ_ORG_CONTACTS
- HZ_PARTIES

This table lists the columns in the interface table, as well as the validation and destination.

Column	Validation	Destination
BATCH_ID	Mandatory	None
CONTACT_ORIG_SYSTEM	• Mandatory • ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORI G_SYSTEM
CONTACT_ORIG_SYSTEM_REFER ENCE	Mandatory	HZ_ORIG_SYS_REFERENCES.ORI G_SYSTEM_REFERENCE
SUB_ORIG_SYSTEM	• Mandatory • ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORI G_SYSTEM

Column	Validation	Destination
SUB_ORIG_SYSTEM_REFERENCE	Mandatory	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM_REFERENCE
OBJ_ORIG_SYSTEM	- Mandatory - ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM
OBJ_ORIG_SYSTEM_REFERENCE	Mandatory	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM_REFERENCE
INSERT_UPDATE_FLAG	I, U, or NULL	None
CONTACT_NUMBER	Use value if passed; otherwise, automatically generate from sequence	HZ_ORG_CONTACTS.CONTACT_NUMBER
DEPARTMENT_CODE	DEPARTMENT_TYPE lookup	HZ_ORG_CONTACTS.DEPARTMENT_CODE
DEPARTMENT	None	HZ_ORG_CONTACTS.DEPARTMENT
TITLE	CONTACT_TITLE lookup	HZ_ORG_CONTACTS.TITLE
JOB_TITLE	None	HZ_ORG_CONTACTS.JOB_TITLE
JOB_TITLE_CODE	RESPONSIBILITY lookup	HZ_ORG_CONTACTS.JOB_TITLE_CODE
DECISION_MAKER_FLAG	Y, N, or NULL	HZ_ORG_CONTACTS.DECISION_MAKER_FLAG
REFERENCE_USE_FLAG	Y, N, or NULL	HZ_ORG_CONTACTS.REFERENCE_USE_FLAG
COMMENTS	None	HZ_ORG_CONTACTS.COMMENTS
RELATIONSHIP_TYPE	- Mandatory and not updateable - Cannot be updated to NULL	HZ_RELATIONSHIPS.RELATIONSHIP_TYPE

Column	Validation	Destination
RELATIONSHIP_CODE	- Mandatory and not updateable - PARTY_RELATIONS_TYPE lookup - Cannot be updated to NULL	HZ_RELATIONSHIPS.RELATIONSHIP_CODE
START_DATE	Cannot be updated to NULL	HZ_RELATIONSHIPS.START_DATE
END_DATE	None	HZ_RELATIONSHIPS.END_DATE
REL_COMMENTS	None	HZ_RELATIONSHIPS.COMMENTS
ATTRIBUTE_CATEGORY	None	HZ_RELATIONSHIPS.ATTRIBUTE_CATEGORY
ATTRIBUTE1 to ATTRIBUTE20	None	HZ_RELATIONSHIPS.ATTRIBUTE1 to HZ_RELATIONSHIPS.ATTRIBUTE20
INTERFACE_STATUS	None	None
ACTION_FLAG	None	None
ERROR_ID	None	None
CREATION_DATE	None	None
CREATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_DATE	None	None
LAST_UPDATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_LOGIN	Foreign key to FND_LOGINS.LOGIN_ID	None

Column	Validation	Destination
REQUEST_ID	Foreign key to FND_CONCURRENT_REQUESTS.REQUEST_ID	None
PROGRAM_APPLICATION_ID	Foreign key to FND_APPLICATION.APPLICATION_ID	None
PROGRAM_ID	Foreign key to FND_CONCURRENT_PROGRAM.CONCURRENT_PROGRAM_ID	None
PROGRAM_UPDATE_DATE	None	None
CREATED_BY_MODULE	Mandatory and not updateable unless current value in TCA is NULL	HZ_ORG_CONTACTS.CREATED_BY_MODULE

HZ_IMP_CREDITRTNGS_INT

The HZ_IMP_CREDITRTNGS_INT table contains credit rating information to be imported into the TCA table HZ_CREDIT_RATINGS.

This table lists the columns in the interface table, as well as the validation and destination.

Column	Validation	Destination
BATCH_ID	Mandatory	None
PARTY_ORIG_SYSTEM	- Mandatory - ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM
PARTY_ORIG_SYSTEM_REFERENCE	Mandatory	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM_REFERENCE
INSERT_UPDATE_FLAG	I, U, or NULL	None

Column	Validation	Destination
RATED_AS_OF_DATE	Not updateable	HZ_CREDIT_RATINGS.RATED_AS_OF_DATE
RATING_ORGANIZATION	Not updateable	HZ_CREDIT_RATINGS.RATING_ORGANIZATION
AVG_HIGH_CREDIT	None	HZ_CREDIT_RATINGS.AVG_HIGH_CREDIT
BANKRUPTCY_IND	Y, N, or NULL	HZ_CREDIT_RATINGS.BANKRUPTCY_IND
BUSINESS_DISCONTINUED	None	HZ_CREDIT_RATINGS.BUSINESS_DISCONTINUED
CLAIMS_IND	None	HZ_CREDIT_RATINGS.CLAIMS_IND
COMMENTS	None	HZ_CREDIT_RATINGS.COMMENTS
CR_SCR_CLAS_EXPL	None	HZ_CREDIT_RATINGS.CR_SCR_CLAS_EXPL
CREDIT_SCORE	None	HZ_CREDIT_RATINGS.CREDIT_SCORE
CREDIT_SCORE_AGE	None	HZ_CREDIT_RATINGS.CREDIT_SCORE_AGE
CREDIT_SCORE_CLASS	None	HZ_CREDIT_RATINGS.CREDIT_SCORE_CLASS
CREDIT_SCORE_COMMENTARY to CREDIT_SCORE_COMMENTARY10	CREDIT_SCORE_COMMENTARY lookup	HZ_CREDIT_RATINGS.CREDIT_SCORE_COMMENTARY to HZ_CREDIT_RATINGS.CREDIT_SCORE_COMMENTARY10
CREDIT_SCORE_DATE	None	HZ_CREDIT_RATINGS.CREDIT_SCORE_DATE

Column	Validation	Destination
CREDIT_SCORE_INCD_DEFAULT	None	HZ_CREDIT_RATINGS.CREDIT_SCORE_INCD_DEFAULT
CREDIT_SCORE_NATL_PERCENTILE	None	HZ_CREDIT_RATINGS.CREDIT_SCORE_NATL_PERCENTILE
CREDIT_SCORE_OVERRIDE_CODE	FAILURE_SCORE_OVERRIDE_CODE lookup	HZ_CREDIT_RATINGS.CREDIT_SCORE_OVERRIDE_CODE
CRIMINAL_PROCEEDING_IND	None	HZ_CREDIT_RATINGS.CRIMINAL_PROCEEDING_IND
DEBARMENT_IND	Y, N, or NULL	HZ_CREDIT_RATINGS.DEBARMENT_IND
DEBARMENTS_COUNT	None	HZ_CREDIT_RATINGS.DEBARMENTS_COUNT
DEBARMENTS_DATE	None	HZ_CREDIT_RATINGS.DEBARMENTS_DATE
DELQ_PMT_PCTG_FOR_ALL_FIRMS	None	HZ_CREDIT_RATINGS.DELQ_PMT_PCTG_FOR_ALL_FIRMS
DELQ_PMT_RNG_PRCNT	None	HZ_CREDIT_RATINGS.DELQ_PMT_RNG_PRCNT
DESCRIPTION	None	HZ_CREDIT_RATINGS.DESCRPTION
DET_HISTORY_IND	None	HZ_CREDIT_RATINGS.DET_HISTORY_IND
DISASTER_IND	None	HZ_CREDIT_RATINGS.DISASTER_IND
FAILURE_SCORE	None	HZ_CREDIT_RATINGS.FAILURE_SCORE
FAILURE_SCORE_AGE	None	HZ_CREDIT_RATINGS.FAILURE_SCORE_AGE

Column	Validation	Destination
FAILURE_SCORE_CLASS	None	HZ_CREDIT_RATINGS.FAILURE_SCORE_CLASS
FAILURE_SCORE_COMMENTARY to FAILURE_SCORE_COMMENTARY10	FAILURE_SCORE_COMMENTARY lookup	HZ_CREDIT_RATINGS.FAILURE_SCORE_COMMENTARY to HZ_CREDIT_RATINGS.FAILURE_SCORE_COMMENTARY10
FAILURE_SCORE_DATE	None	HZ_CREDIT_RATINGS.FAILURE_SCORE_DATE
FAILURE_SCORE_INCD_DEFAULT	None	HZ_CREDIT_RATINGS.FAILURE_SCORE_INCD_DEFAULT
FAILURE_SCORE_NATNL_PERCENTILE	None	HZ_CREDIT_RATINGS.FAILURE_SCORE_NATNL_PERCENTILE
FAILURE_SCORE_OVERRIDE_CODE	FAILURE_SCORE_OVERRIDE_CODE lookup	HZ_CREDIT_RATINGS.FAILURE_SCORE_OVERRIDE_CODE
FINCL_EMBT_IND	Y, N, or NULL	HZ_CREDIT_RATINGS.FINCL_EMBT_IND
FINCL_LGL_EVENT_IND	None	HZ_CREDIT_RATINGS.FINCL_LGL_EVENT_IND
GLOBAL_FAILURE_SCORE	None	HZ_CREDIT_RATINGS.GLOBAL_FAILURE_SCORE
HIGH_CREDIT	None	HZ_CREDIT_RATINGS.HIGH_CREDIT
HIGH_RNG_DELQ_SCR	None	HZ_CREDIT_RATINGS.HIGH_RNG_DELQ_SCR
JUDGEMENT_IND	Y, N, or NULL	HZ_CREDIT_RATINGS.JUDGEMENT_IND
LIEN_IND	Y, N, or NULL	HZ_CREDIT_RATINGS.LIEN_IND
LOW_RNG_DELQ_SCR	None	HZ_CREDIT_RATINGS.LOW_RNG_DELQ_SCR

Column	Validation	Destination
MAXIMUM_CREDIT_CURRENCY_CODE	Foreign key to FND_CURRENCIES.CURRENCY_CODE with Y for CURRENCY_FLAG and Y or N for ENABLED_FLAG	HZ_CREDIT_RATINGS.MAXIMUM_CREDIT_CURRENCY_CODE
MAXIMUM_CREDIT_RECOMMENDATION	None	HZ_CREDIT_RATINGS.MAXIMUM_CREDIT_RECOMMENDATION
NEGV_PMT_EXPL	None	HZ_CREDIT_RATINGS.NEGV_PMT_EXPL
NO_TRADE_IND	Y, N, or NULL	HZ_CREDIT_RATINGS.NO_TRADE_IND
NUM_PRNT_BKCY_CONVS	None	HZ_CREDIT_RATINGS.NUM_PRNT_BKCY_CONVS
NUM_PRNT_BKCY_FILING	None	HZ_CREDIT_RATINGS.NUM_PRNT_BKCY_FILING
NUM_SPCL_EVENT	None	HZ_CREDIT_RATINGS.NUM_SPCL_EVENT
NUM_TRADE_EXPERIENCES	None	HZ_CREDIT_RATINGS.NUM_TRADE_EXPERIENCES
OPRG_SPEC_EVNT_IND	None	HZ_CREDIT_RATINGS.OPRG_SPEC_EVNT_IND
OTHER_SPEC_EVNT_IND	None	HZ_CREDIT_RATINGS.OTHER_SPEC_EVNT_IND
PAYDEX_COMMENT	None	HZ_CREDIT_RATINGS.PAYDEX_COMMENT
PAYDEX_FIRM_COMMENT	None	HZ_CREDIT_RATINGS.PAYDEX_FIRM_COMMENT
PAYDEX_FIRM_DAYS	None	HZ_CREDIT_RATINGS.PAYDEX_FIRM_DAYS

Column	Validation	Destination
PAYDEX_INDUSTY_COMMENT	None	HZ_CREDIT_RATINGS.PAYDEX_I NDUSTY_COMMENT
PAYDEX_INDUSTY_DAYS	None	HZ_CREDIT_RATINGS.PAYDEX_I NDUSTY_DAYS
PAYDEX_NORM	None	HZ_CREDIT_RATINGS.PAYDEX_ NORM
PAYDEX_SCORE	None	HZ_CREDIT_RATINGS.PAYDEX_S CORE
PAYDEX_THREE_MONTHS_AGO	None	HZ_CREDIT_RATINGS.PAYDEX_T HREE_MONTHS_AGO
PRNT_BKCY_CHAPTER_CONV	None	HZ_CREDIT_RATINGS.PRNT_BKC Y_CHAPTER_CONV
PRNT_BKCY_CONV_DATE	None	HZ_CREDIT_RATINGS.PRNT_BKC Y_CONV_DATE
PRNT_BKCY_CONV_DATE	None	HZ_CREDIT_RATINGS.PRNT_BKC Y_CONV_DATE
PRNT_BKCY_FILG_CHAPTER	None	HZ_CREDIT_RATINGS.PRNT_BKC Y_FILG_CHAPTER
PRNT_BKCY_FILG_DATE	None	HZ_CREDIT_RATINGS.PRNT_BKC Y_FILG_DATE
PRNT_BKCY_FILG_TYPE	None	HZ_CREDIT_RATINGS.PRNT_BKC Y_FILG_TYPE
PRNT_HQ_BKCY_IND	PRNT_HQ_IND lookup	HZ_CREDIT_RATINGS.PRNT_HQ_ BKCY_IND
PUB_REC_EXPL	None	HZ_CREDIT_RATINGS.PUB_REC_ EXPL
RATING	None	HZ_CREDIT_RATINGS.RATING

Column	Validation	Destination
SECURED_FLNG_IND	None	HZ_CREDIT_RATINGS.SECURED_FLNG_IND
SLOW_TRADE_EXPL	None	HZ_CREDIT_RATINGS.SLOW_TRADE_EXPL
SPCL_EVENT_COMMENT	None	HZ_CREDIT_RATINGS.SPCL_EVENT_COMMENT
SPCL_EVENT_UPDATE_DATE	None	HZ_CREDIT_RATINGS.SPCL_EVENT_UPDATE_DATE
SPCL_EVNT_TXT	None	HZ_CREDIT_RATINGS.SPCL_EVNT_TXT
SUIT_IND	Y, N, or NULL	HZ_CREDIT_RATINGS.SUIT_IND
SUIT_JUDGE_IND	None	HZ_CREDIT_RATINGS.SUIT_JUDGE_IND
INTERFACE_STATUS	None	None
ACTION_FLAG	None	None
ERROR_ID	None	None
CREATION_DATE	None	None
CREATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_DATE	None	None
LAST_UPDATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_LOGIN	Foreign key to FND_LOGINS.LOGIN_ID	None
REQUEST_ID	Foreign key to FND_CONCURRENT_REQUESTS.REQUEST_ID	None

Column	Validation	Destination
PROGRAM_APPLICATION_ID	Foreign key to FND_APPLICATION.APPLICATION_ID	None
PROGRAM_ID	Foreign key to FND_CONCURRENT_PROGRAM.CONCURRENT_PROGRAM_ID	None
PROGRAM_UPDATE_DATE	None	None
CREATED_BY_MODULE	Mandatory and not updateable unless current value in TCA is NULL	HZ_CREDIT_RATINGS.CREATED_BY_MODULE

HZ_IMP_FINNUMBERS_INT

The HZ_IMP_FINNUMBERS_INT table contains financial number information to be imported into the TCA table HZ_FINANCIAL_NUMBERS.

This table lists the columns in the interface table, as well as the validation and destination.

Column	Validation	Destination
BATCH_ID	Mandatory	None
PARTY_ORIG_SYSTEM	- Mandatory - ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM
PARTY_ORIG_SYSTEM_REFERENCE	Mandatory	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM_REFERENCE
INSERT_UPDATE_FLAG	<i>I, U, or NULL</i>	None
TYPE_OF_FINANCIAL_REPORT	None	None
DOCUMENT_REFERENCE	None	None

Column	Validation	Destination
DATE_REPORT_ISSUED	None	None
ISSUED_PERIOD	None	None
REPORT_START_DATE	None	None
REPORT_END_DATE	None	None
FINANCIAL_NUMBER_NAME	• FIN_NUM_NAME lookup • Combination of FINANCIAL_NUMBER_NAME and FINANCIAL_REPORT_ID must be unique	HZ_FINANCIAL_NUMBERS.FINANCIAL_NUMBER_NAME
FINANCIAL_NUMBER	None	HZ_FINANCIAL_NUMBERS.FINANCIAL_NUMBER
FINANCIAL_NUMBER_CURRENCY	None	HZ_FINANCIAL_NUMBERS.FINANCIAL_NUMBER_CURRENCY
FINANCIAL_UNITS_APPLIED	None	HZ_FINANCIAL_NUMBERS.FINANCIAL_UNITS_APPLIED
PROJECTED_ACTUAL_FLAG	None	HZ_FINANCIAL_NUMBERS.PROJECTED_ACTUAL_FLAG
INTERFACE_STATUS	None	None
ACTION_FLAG	None	None
ERROR_ID	None	None
CREATION_DATE	None	None
CREATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_DATE	None	None
LAST_UPDATED_BY	Foreign key to FND_USER.USER_ID	None

Column	Validation	Destination
LAST_UPDATE_LOGIN	Foreign key to FND_LOGINS.LOGIN_ID	None
REQUEST_ID	Foreign key to FND_CONCURRENT_REQUESTS. REQUEST_ID	None
PROGRAM_APPLICATION_ID	Foreign key to FND_APPLICATION.APPLICATION_ID	None
PROGRAM_ID	Foreign key to FND_CONCURRENT_PROGRAM. CONCURRENT_PROGRAM_ID	None
PROGRAM_UPDATE_DATE	None	None
CREATED_BY_MODULE	Mandatory and not updateable unless current value in TCA is NULL	HZ_FINANCIAL_NUMBERS.CREATED_BY_MODULE

HZ_IMP_FINREPORTS_INT

The HZ_IMP_FINREPORTS_INT table contains financial report information to be imported into the TCA table HZ_FINANCIAL_REPORTS.

This combination of values in these columns must be unique:

- PARTY_ID
- FINANCIAL_REPORT_TYPE
- DOCUMENT_REFERENCE
- DATE_REPORT_ISSUED
- ISSUED_PERIOD or REPORT_START_DATE and REPORT_END_DATE
- ACTUAL_CONTENT_SOURCE

This table lists the columns in the interface table, as well as the validation and destination.

Column	Validation	Destination
BATCH_ID	Mandatory	None
PARTY_ORIG_SYSTEM	• Mandatory • ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM
PARTY_ORIG_SYSTEM_REFERENCE	Mandatory	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM_REFERENCE
INSERT_UPDATE_FLAG	<i>I, U, or NULL</i>	None
TYPE_OF_FINANCIAL_REPORT	None	HZ_FINANCIAL_REPORTS.TYPE_OF_FINANCIAL_REPORT
DOCUMENT_REFERENCE	None	HZ_FINANCIAL_REPORTS.DOCUMENT_REFERENCE
DATE_REPORT_ISSUED	None	HZ_FINANCIAL_REPORTS.DATE_REPORT_ISSUED
ISSUED_PERIOD	Either ISSUED_PERIOD alone or the REPORT_START_DATE and REPORT_END_DATE combination is mandatory. Cannot pass both.	HZ_FINANCIAL_REPORTS.ISSUED_PERIOD
REPORT_START_DATE	Either ISSUED_PERIOD alone or the REPORT_START_DATE and REPORT_END_DATE combination is mandatory. Cannot pass both.	HZ_FINANCIAL_REPORTS.REPORT_START_DATE
REPORT_END_DATE	• Equal to or greater than REPORT_START_DATE. • Can and must be populated only if REPORT_START_DATE has value. • Either ISSUED_PERIOD alone or the REPORT_START_DATE and REPORT_END_DATE combination is mandatory. Cannot pass both.	HZ_FINANCIAL_REPORTS.REPORT_END_DATE

Column	Validation	Destination
AUDIT_IND	Y, N, or NULL	HZ_FINANCIAL_REPORTS.AUDIT_IND
CONSOLIDATED_IND	Y, N, or NULL	HZ_FINANCIAL_REPORTS.CON OLIDATED_IND
ESTIMATED_IND	Y, N, or NULL	HZ_FINANCIAL_REPORTS.ES TIMATED_IND
FINAL_IND	Y, N, or NULL	HZ_FINANCIAL_REPORTS.FI NAL_IND
FISCAL_IND	Y, N, or NULL	HZ_FINANCIAL_REPORTS.FI SCAL_IND
FORECAST_IND	Y, N, or NULL	HZ_FINANCIAL_REPORTS.FO RECAST_IND
OPENING_IND	Y, N, or NULL	HZ_FINANCIAL_REPORTS.OW ENING_IND
PROFORMA_IND	Y, N, or NULL	HZ_FINANCIAL_REPORTS.P ROFORMA_IND
QUALIFIED_IND	Y, N, or NULL	HZ_FINANCIAL_REPORTS.Q UALIFIED_IND
REQUIRING_AUTHORITY	None	HZ_FINANCIAL_REPORTS.R EQUIRING_AUTHORITY
RESTATED_IND	Y, N, or NULL	HZ_FINANCIAL_REPORTS.RO STATED_IND
SIGNED_BY_PRINCIPALS_IND	Y, N, or NULL	HZ_FINANCIAL_REPORTS.SI GNE D_BY_PRINCIPALS_IND
TRIAL_BALANCE_IND	Y, N, or NULL	HZ_FINANCIAL_REPORTS.T RIAL _BALANCE_IND
UNBALANCED_IND	Y, N, or NULL	HZ_FINANCIAL_REPORTS.U NBA LANCED_IND

Column	Validation	Destination
INTERFACE_STATUS	None	None
ACTION_FLAG	None	None
ERROR_ID	None	None
CREATION_DATE	None	None
CREATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_DATE	None	None
LAST_UPDATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_LOGIN	Foreign key to FND_LOGINS.LOGIN_ID	None
REQUEST_ID	Foreign key to FND_CONCURRENT_REQUESTS. REQUEST_ID	None
PROGRAM_APPLICATION_ID	Foreign key to FND_APPLICATION.APPLICATION ID	None
PROGRAM_ID	Foreign key to FND_CONCURRENT_PROGRAM. CONCURRENT_PROGRAM_ID	None
PROGRAM_UPDATE_DATE	None	None
CREATED_BY_MODULE	Mandatory and not updateable unless current value in TCA is NULL	HZ_FINANCIAL_REPORTS.CREA TED_BY_MODULE

HZ_IMP_PARTIES_INT

The HZ_IMP_PARTIES_INT table contains party information to be imported into these TCA tables:

- HZ_PARTIES

- HZ_ORGANIZATION_PROFILES
- HZ_PERSON_PROFILES

This table lists the columns in the interface table, as well as the validation and destination.

Column	Validation	Destination
BATCH_ID	Mandatory	None
PARTY_ORIG_SYSTEM	• Mandatory • ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM
PARTY_ORIG_SYSTEM_REFERENCE	Mandatory	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM_REFERENCE
INSERT_UPDATE_FLAG	<i>I, U, or NULL</i>	None
PARTY_TYPE	• Mandatory and not updateable • PARTY_TYPE lookup • Value must be <i>PERSON</i> or <i>ORGANIZATION</i>	HZ_PARTIES.PARTY_TYPE
PARTY_ID	• For internal use only. Any passed value is ignored. • Cannot be updated to NULL.	None
PARTY_NUMBER	• Not updateable • Must be unique • Cannot be updated to NULL • Use value if passed; otherwise, automatically generate from sequence	HZ_PARTIES.PARTY_NUMBER
SALUTATION	None	HZ_PARTIES.SALUTATION

Column	Validation	Destination
ATTRIBUTE_CATEGORY	None	HZ_PARTIES.ATTRIBUTE_CATEGORY
ATTRIBUTE1 to ATTRIBUTE24	None	HZ_PARTIES.ATTRIBUTE1 to HZ_PARTIES.ATTRIBUTE24
JGZZ_FISCAL_CODE	None	HZ_ORGANIZATION_PROFILES.JGZZ_FISCAL_CODE or HZ_PERSON_PROFILES.JGZZ_FISCAL_CODE
TAX_REFERENCE	OWN_RENT_IND lookup	HZ_ORGANIZATION_PROFILES.TAX_REFERENCE or HZ_PERSON_PROFILES.TAX_REFERENCE
KNOWN_AS to KNOWN_AS5	None	HZ_ORGANIZATION_PROFILES.KNOWN_AS to HZ_PARTIES.KNOWN_AS5 or HZ_PERSON_PROFILES.KNOWN_AS to HZ_PARTIES.KNOWN_AS5
RENT_OWN_IND	OWN_RENT_IND lookup	HZ_ORGANIZATION_PROFILES.RENT_OWN_IND or HZ_PERSON_PROFILES.RENT_OWN_IND
ORGANIZATION_NAME	• Mandatory • Cannot be updated to NULL	HZ_ORGANIZATION_PROFILES.ORGANIZATION_NAME
ORGANIZATION_NAME_PHONE TIC	None	HZ_ORGANIZATION_PROFILES.ORGANIZATION_NAME_PHONE TIC

Column	Validation	Destination
ORGANIZATION_TYPE	None	HZ_ORGANIZATION_PROFILES.ORGANIZATION_TYPE
ANALYSIS_FY	None	HZ_ORGANIZATION_PROFILES.ANALYSIS_FY
BRANCH_FLAG	Y, N, or NULL	HZ_ORGANIZATION_PROFILES.BRANCH_FLAG
BUSINESS_SCOPE	None	HZ_ORGANIZATION_PROFILES.BUSINESS_SCOPE
CEO_NAME	None	HZ_ORGANIZATION_PROFILES.CEO_NAME
CEO_TITLE	None	HZ_ORGANIZATION_PROFILES.CEO_TITLE
CONG_DIST_CODE	None	HZ_ORGANIZATION_PROFILES.CONG_DIST_CODE
CONTROL_YR	None	HZ_ORGANIZATION_PROFILES.CONTROL_YR
CORPORATION_CLASS	None	HZ_ORGANIZATION_PROFILES.CORPORATION_CLASS
CURR_FY_POTENTIAL_REVENUE	None	HZ_ORGANIZATION_PROFILES.CURR_FY_POTENTIAL_REVENUE
NEXT_FY_POTENTIAL_REVENUE	None	HZ_ORGANIZATION_PROFILES.NEXT_FY_POTENTIAL_REVENUE
PREF_FUNCTIONAL_CURRENCY	None	HZ_ORGANIZATION_PROFILES.PREF_FUNCTIONAL_CURRENCY
DISADV_8A_IND	Y, N, or NULL	HZ_ORGANIZATION_PROFILES.DISADV_8A_IND
DO_NOT_CONFUSE_WITH	None	HZ_ORGANIZATION_PROFILES.DO_NOT_CONFUSE_WITH

Column	Validation	Destination
DUNS_NUMBER_C	None	HZ_ORGANIZATION_PROFILES.DUNS_NUMBER_C
EMP_AT_PRIMARY_ADR	None	HZ_ORGANIZATION_PROFILES.EMP_AT_PRIMARY_ADR
EMP_AT_PRIMARY_ADR_EST_IND	EMP_AT_PRIMARY_ADR_EST_IND lookup	HZ_ORGANIZATION_PROFILES.EMP_AT_PRIMARY_ADR_EST_IND
EMP_AT_PRIMARY_ADR_MIN_IND	EMP_AT_PRIMARY_ADR_MIN_IND lookup	HZ_ORGANIZATION_PROFILES.EMP_AT_PRIMARY_ADR_MIN_IND
EMP_AT_PRIMARY_ADR_TEXT	None	HZ_ORGANIZATION_PROFILES.EMP_AT_PRIMARY_ADR_TEXT
EMPLOYEES_TOTAL	None	HZ_ORGANIZATION_PROFILES.EMPLOYEES_TOTAL
DISPLAYED_DUNS	None	None
EXPORT_IND	Y, N, or NULL	HZ_ORGANIZATION_PROFILES.EXPORT_IND
FISCAL_YEAREND_MONTH	MONTH lookup	HZ_ORGANIZATION_PROFILES.FISCAL_YEAREND_MONTH
GSA_INDICATOR_FLAG	Y, N, or NULL	HZ_ORGANIZATION_PROFILES.GSA_INDICATOR_FLAG
HQ_BRANCH_IND	HQ_BRANCH_IND lookup	HZ_ORGANIZATION_PROFILES.HQ_BRANCH_IND
IMPORT_IND	Y, N, or NULL	HZ_ORGANIZATION_PROFILES.IMPORT_IND
INCORP_YEAR	None	HZ_ORGANIZATION_PROFILES.INCORP_YEAR
LABOR_SURPLUS_IND	Y, N, or NULL	HZ_ORGANIZATION_PROFILES.LABOR_SURPLUS_IND

Column	Validation	Destination
LEGAL_STATUS	LEGAL_STATUS lookup	HZ_ORGANIZATION_PROFILES.LEGAL_STATUS
LINE_OF_BUSINESS	None	HZ_ORGANIZATION_PROFILES.LINE_OF_BUSINESS
LOCAL_BUS_IDENTIFIER	None	HZ_ORGANIZATION_PROFILES.LOCAL_BUS_IDENTIFIER
LOCAL_BUS_IDEN_TYPE	LOCAL_BUS_IDEN_TYPE lookup	HZ_ORGANIZATION_PROFILES.LOCAL_BUS_IDEN_TYPE
MINORITY_OWNED_IND	Y, N, or NULL	HZ_ORGANIZATION_PROFILES.MINORITY_OWNED_IND
MINORITY_OWNED_TYPE	None	HZ_ORGANIZATION_PROFILES.MINORITY_OWNED_TYPE
MISSION_STATEMENT	None	HZ_ORGANIZATION_PROFILES.MISSION_STATEMENT
OOB_IND	Y, N, or NULL	HZ_ORGANIZATION_PROFILES.OOB_IND
PARENT_SUB_IND	Y, N, or NULL	HZ_ORGANIZATION_PROFILES.PARENT_SUB_IND
PRINCIPAL_NAME	None	HZ_ORGANIZATION_PROFILES.PRINCIPAL_NAME
PRINCIPAL_TITLE	None	HZ_ORGANIZATION_PROFILES.PRINCIPAL_TITLE
PUBLIC_PRIVATE_OWNERSHIP_FLAG	Y, N, or NULL	HZ_ORGANIZATION_PROFILES.PUBLIC_PRIVATE_OWNERSHIP_FLAG
REGISTRATION_TYPE	REGISTRATION_TYPE lookup	HZ_ORGANIZATION_PROFILES.REGISTRATION_TYPE
SMALL_BUS_IND	Y, N, or NULL	HZ_ORGANIZATION_PROFILES.SMALL_BUS_IND

Column	Validation	Destination
TOTAL_EMP_EST_IND	TOTAL_EMP_EST_IND lookup	HZ_ORGANIZATION_PROFILES.TOTAL_EMP_EST_IND
TOTAL_EMP_MIN_IND	TOTAL_EMP_MIN_IND lookup	HZ_ORGANIZATION_PROFILES.TOTAL_EMP_MIN_IND
TOTAL_EMPLOYEES_IND	TOTAL_EMPLOYEES_INDICATOR lookup	HZ_ORGANIZATION_PROFILES.TOTAL_EMPLOYEES_IND
TOTAL_EMPLOYEES_TEXT	None	HZ_ORGANIZATION_PROFILES.TOTAL_EMPLOYEES_TEXT
TOTAL_PAYMENTS	None	HZ_ORGANIZATION_PROFILES.TOTAL_PAYMENTS
WOMAN_OWNED_IND	Y, N, or NULL	HZ_ORGANIZATION_PROFILES.WOMAN_OWNED_IND
YEAR_ESTABLISHED	None	HZ_ORGANIZATION_PROFILES.YEAR_ESTABLISHED
PERSON_FIRST_NAME	- A value must be passed for either PERSON_FIRST_NAME or PERSON_LAST_NAME - Cannot be updated to NULL	HZ_PERSON_PROFILES.PERSON_FIRST_NAME
PERSON_LAST_NAME	- A value must be passed for either PERSON_FIRST_NAME or PERSON_LAST_NAME - Cannot be updated to NULL	HZ_PERSON_PROFILES.PERSON_LAST_NAME
PERSON_MIDDLE_NAME	None	HZ_PERSON_PROFILES.PERSON_MIDDLE_NAME
PERSON_INITIALS	None	HZ_PERSON_PROFILES.PERSON_INITIALS
PERSON_NAME_SUFFIX	None	HZ_PERSON_PROFILES.PERSON_NAME_SUFFIX

Column	Validation	Destination
PERSON_PRE_NAME_ADJUNCT	CONTACT_TITLE lookup	HZ_PERSON_PROFILES.PERSON_PRE_NAME_ADJUNCT
PERSON_PREVIOUS_LAST_NAME	None	HZ_PERSON_PROFILES.PERSON_PREVIOUS_LAST_NAME
PERSON_TITLE	None	HZ_PERSON_PROFILES.PERSON_TITLE
PERSON_FIRST_NAME_PHONETIC	None	HZ_PERSON_PROFILES.PERSON_FIRST_NAME_PHONETIC
PERSON_LAST_NAME_PHONETIC	None	HZ_PERSON_PROFILES.PERSON_LAST_NAME_PHONETIC
PERSON_MIDDLE_NAME_PHONETIC	None	HZ_PERSON_PROFILES.MIDDLE_NAME_PHONETIC
PERSON_NAME_PHONETIC	None	HZ_PERSON_PROFILES.PERSON_NAME_PHONETIC
PERSON_ACADEMIC_TITLE	None	HZ_PERSON_PROFILES.PERSON_ACADEMIC_TITLE
DATE_OF_BIRTH	- Cannot be later than the system date - If DATE_OF_DEATH and DATE_OF_BIRTH are both passed, then the date of death must be later than the date of birth	HZ_PERSON_PROFILES.DATE_OF_BIRTH
PLACE_OF_BIRTH	None	HZ_PERSON_PROFILES.PLACE_OF_BIRTH

Column	Validation	Destination
DATE_OF_DEATH	- Cannot be later than the system date - If DATE_OF_DEATH and DATE_OF_BIRTH are both passed, then the date of death must be later than the date of birth	HZ_PERSON_PROFILES.DATE_OF_DEATH
DECEASED_FLAG	- Y, N, or NULL - If DATE_OF_DEATH is not NULL, then DECEASED_FLAG must be Y	HZ_PERSON_PROFILES.DECEASED_FLAG
DECLARED_ETHNICITY	None	HZ_PERSON_PROFILES.DECLARED_ETHNICITY
GENDER	None	HZ_PERSON_PROFILES.GENDER
HEAD_OF_HOUSEHOLD_FLAG	Y, N, or NULL	HZ_PERSON_PROFILES.HEAD_OF_HOUSEHOLD_FLAG
HOUSEHOLD_INCOME	None	HZ_PERSON_PROFILES.HOUSEHOLD_INCOME
HOUSEHOLD_SIZE	None	HZ_PERSON_PROFILES.HOUSEHOLD_SIZE
MARITAL_STATUS	MARITAL_STATUS lookup	HZ_PERSON_PROFILES.MARITAL_STATUS
MARITAL_STATUS_EFFECTIVE_DATE	None	HZ_PERSON_PROFILES.MARITAL_STATUS_EFFECTIVE_DATE
PERSON_IDEN_TYPE	None	HZ_PERSON_PROFILES.PERSON_IDEN_TYPE
PERSON_IDENTIFIER	None	HZ_PERSON_PROFILES.PERSON_IDENTIFIER

Column	Validation	Destination
PERSONAL_INCOME	None	HZ_PERSON_PROFILES.PERSONAL_INCOME
INTERFACE_STATUS	None	None
ACTION_FLAG	None	None
ERROR_ID	None	None
CREATION_DATE	None	None
CREATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_DATE	None	None
LAST_UPDATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_LOGIN	Foreign key to FND_LOGINS.LOGIN_ID	None
REQUEST_ID	Foreign key to FND_CONCURRENT_REQUESTS.REQUEST_ID	None
PROGRAM_APPLICATION_ID	Foreign key to FND_APPLICATION.APPLICATION_ID	None
PROGRAM_ID	Foreign key to FND_CONCURRENT_PROGRAM.CONCURRENT_PROGRAM_ID	None
PROGRAM_UPDATE_DATE	None	None
CREATED_BY_MODULE	Mandatory and not updateable unless current value in TCA is NULL	HZ_ORGANIZATION_PROFILES.CREATED_BY_MODULE or HZ_PERSON_PROFILES.CREATED_BY_MODULE

HZ_IMP_RELSHIPS_INT

The HZ_IMP_RELSHIPS_INT table contains relationship information to be imported into these TCA tables:

- HZ_RELATIONSHIPS
- HZ_PARTIES
- HZ_ORG_CONTACTS (Optional)

This table lists the columns in the interface table, as well as the validation and destination.

Column	Validation	Destination
BATCH_ID	Mandatory	None
SUB_ORIG_SYSTEM	• Mandatory • ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM
SUB_ORIG_SYSTEM_REFERENCE	Mandatory	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM_REFERENCE
OBJ_ORIG_SYSTEM	• Mandatory • ORIG_SYSTEM lookup	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM
OBJ_ORIG_SYSTEM_REFERENCE	Mandatory	HZ_ORIG_SYS_REFERENCES.ORIG_SYSTEM_REFERENCE
INSERT_UPDATE_FLAG	I, U, or NULL	None
RELATIONSHIP_TYPE	• Mandatory and not updateable • Cannot be updated to NULL	HZ_RELATIONSHIPS.RELATIONSHIP_TYPE

Column	Validation	Destination
RELATIONSHIP_CODE	- Mandatory and not updateable - PARTY_RELATIONS_TYPE lookup - Cannot be updated to NULL	HZ_RELATIONSHIPS.RELATIONSHIP_CODE
START_DATE	Cannot be updated to NULL	HZ_RELATIONSHIPS.START_DATE
END_DATE	None	HZ_RELATIONSHIPS.END_DATE
COMMENTS	None	HZ_RELATIONSHIPS.COMMENTS
ATTRIBUTE_CATEGORY	None	HZ_RELATIONSHIPS.ATTRIBUTE_CATEGORY
ATTRIBUTE1 to ATTRIBUTE20	None	HZ_RELATIONSHIPS.ATTRIBUTE1 to HZ_RELATIONSHIPS.ATTRIBUTE20
INTERFACE_STATUS	None	None
ACTION_FLAG	None	None
ERROR_ID	None	None
CREATION_DATE	None	None
CREATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_DATE	None	None
LAST_UPDATED_BY	Foreign key to FND_USER.USER_ID	None
LAST_UPDATE_LOGIN	Foreign key to FND_LOGINS.LOGIN_ID	None

Column	Validation	Destination
REQUEST_ID	Foreign key to FND_CONCURRENT_REQUESTS. REQUEST_ID	None
PROGRAM_APPLICATION_ID	Foreign key to FND_APPLICATION.APPLICATION_ID	None
PROGRAM_ID	Foreign key to FND_CONCURRENT_PROGRAM. CONCURRENT_PROGRAM_ID	None
PROGRAM_UPDATE_DATE	None	None
CREATED_BY_MODULE	Mandatory and not updateable unless current value in TCA is NULL	HZ_RELATIONSHIPS.CREATED_BY_MODULE

Customer Interface

This chapter covers the following topics:

- Customer Interface and Bulk Import
- Customer Interface Table Descriptions and Validation

Customer Interface and Bulk Import

You can use Customer Interface to import both party and account information, including accounts that are associated with parties already loaded into your database. However, customer Interface runs independently and does not regard party level information already loaded into your database using Bulk Import. If you plan to use Customer Interface to import accounts that are associated with the imported parties, you must ensure that the source ID alone is unique across all source systems. See:

- Bulk Import Overview, *Oracle Trading Community Architecture User Guide*.
- Loading Data into the Interface Tables, *Oracle Trading Community Architecture User Guide*.
- Unique Source IDs for Importing Associated Accounts, *Oracle Trading Community Architecture User Guide*.

Customer Interface Table Descriptions and Validation

Below is a detailed description of the five Customer Interface tables and the validation performed on each column when you run Customer Interface.

Table Name: RA_CUSTOMERS_INTERFACE_ALL

This table stores customer, address, and business purpose information. You do not have to enter values in this table if you do not want to import customers, addresses, or business purposes.

ADDRESS1 through 4

Enter the address for your customer in these four columns. You can enter up to four lines of an address.

Validation: If you enter a value in ORIG_SYSTEM_ADDRESS_REF, you must enter a value in ADDRESS1. For multiple rows with the same address reference, insert values in address 1-4.

Destination: HZ_LOCATIONS.ADDRESS1,
HZ_LOCATIONS.ADDRESS2,
HZ_LOCATIONS.ADDRESS3, and
HZ_LOCATIONS.ADDRESS4

CITY, STATE, PROVINCE, COUNTY, POSTAL_CODE, COUNTRY

Enter the city, state, province, county, and postal code for your customer's address. You must enter values that have already been defined in AR_LOCATION_VALUES if Address Validation is set to 'Error' and you are calculating sales tax. You must do this for each address component on which your tax location flexfield structure is based.

If Address Validation is set to 'Warning' and you pass an address component value that does not exist in AR_LOCATION_VALUES, Customer Interface inserts this value into AR_LOCATION_VALUES and displays a warning message in the Customer Interface Transfer report.

If Address Validation is set to 'No Validation' and you pass a value that does not exist in AR_LOCATION_VALUES, Customer Interface inserts this value into AR_LOCATION_VALUES.

You must always enter a value for Country.

Validation: The country must exist in FND_TERRITORIES.

Destination: HZ_LOCATIONS.CITY, HZ_LOCATIONS.STATE,
HZ_LOCATIONS.PROVINCE,
HZ_LOCATIONS.COUNTY,
HZ_LOCATIONS.POSTAL_CODE, and
HZ_LOCATIONS.COUNTRY

ADDRESS_KEY

This column is not currently used by Customer Interface.

ADDRESS_LINES_PHONETIC

The phonetic or Kana (Japanese) representation of a customer address. This column is optional.

Validation:	None
Destination:	HZ_LOCATIONS.ADDRESS_LINES_PHONETIC

BILL_TO_ORIG_ADDRESS_REF

Enter the Bill-To location that you want to associate with the Ship-To address on this record.

Validation:	You can enter a value only if the SITE_USE_CODE column in this record is 'Ship-To'. Also, the Bill-To address must exist for your customer or any related customers.
--------------------	--

Destination:	HZ_CUST_SITE_USES_ALL.BILL_TO_SITE_USE_ID
---------------------	---

CUSTOMER_ATTRIBUTE_CATEGORY

Enter Descriptive Flexfield category information for your customer. This column is optional.

Validation:	None
--------------------	------

Destination:	HZ_CUST_ACCOUNTS.ATTRIBUTE_CATEGORY and HZ_PARTIES.ATTRIBUTE_CATEGORY
---------------------	--

ADDRESS_ATTRIBUTE_CATEGORY

Enter Descriptive Flexfield category information for your customer's address. This column is optional.

Validation:	None
--------------------	------

Destination:	HZ_LOCATIONS.ATTRIBUTE_CATEGORY, HZ_PARTY-SITES.ATTRIBUTE_CATEGORY, and HZ_CUST_ACCT_SITES_ALL.ATTRIBUTE_CATEGORY
---------------------	---

SITE_USE_ATTRIBUTE_CATEGORY

Enter Descriptive Flexfield category information for your customer's site use. This column is optional.

Validation:	None
--------------------	------

Destination:	HZ_CUST_SITE_USES_ALL.ATTRIBUTE_CATEGORY
---------------------	--

CUSTOMER_ATTRIBUTE_1 to 15

Enter Descriptive Flexfield information for your customer. This column is optional.

Validation:	None
Destination:	HZ_CUST_ACCOUNTS.ATTRIBUTE1 TO 15 and HZ_PARTIES.ATTRIBUTE1 TO 15

ADDRESS_ATTRIBUTE_1 to 15

Enter Descriptive Flexfield information for your customer's address. This column is optional.

Validation:	None
Destination:	HZ_LOCATIONS.ATTRIBUTE1 TO 15, HZ_PARTY_SITES.ATTRIBUTE1 TO 15, and HZ_CUST_ACCT_SITES_ALL.ATTRIBUTE1 TO 15

SITE_USE_ATTRIBUTE_1 to 15

Enter Descriptive Flexfield information for you customer's site use. This column is optional.

Validation:	None
Destination:	HZ_CUST_SITE_USES_ALL.ATTRIBUTE1 TO 15, HZ_PARTIES.ATTRIBUTE1 TO 15, and HZ_CUST_ACCOUNTS.ATTRIBUTE1 TO 15

CUSTOMER_CATEGORY_CODE

Enter a category to categorize your customer. Use customer categories that you previously defined in the Receivables Lookups window. This column is optional.

Validation:	AR_LOOKUPS.LOOKUP_CODE where LOOKUP_TYPE = 'CUSTOMER_CATEGORY'
Destination:	HZ_CUST_ACCOUNTS.CATEGORY_CODE

ADDRESS_CATEGORY_CODE

Enter the address category code for your customer's site. Use a defined code from the Oracle Receivables Lookups window. This column is optional.

Validation:	AR_LOOKUPS.LOOKUP_CODE where LOOKUP_TYPE = 'ADDRESS_CATEGORY.' The lookup code must be enabled.
Destination:	HZ_CUST_ACCT_SITES_ALL.CUSTOMER_CATEGORY_ CODE

CUSTOMER_CLASS_CODE

Enter the customer class for your customer. Use customer classes that you previously defined in the Receivables Lookups window. This column is optional.

Validation: AR_LOOKUPS.LOOKUP_CODE where LOOKUP_TYPE = 'CUSTOMER CLASS'

Destination: HZ_CUST_ACCOUNTS.CUSTOMER_CLASS_CODE

CUSTOMER_KEY

This column is not currently used by Customer Interface.

CUSTOMER_NAME

Enter the name of your customer. This column is required.

Validation: The same customer reference cannot have different customer names within this table.

Destination: HZ_PARTIES.PARTY_NAME

CUSTOMER_NAME_PHONETIC

The phonetic or Kana (Japanese) representation of your customer name. This column is optional.

Validation: None

Destination: HZ_PARTIES.PARTY_NAME_PHONETIC

CUSTOMER_NUMBER

Enter your customer's number.

Validation: Must be null if you are using Automatic Customer Numbering. Must exist if you are not using Automatic Customer Numbering. This value must be unique within HZ_PARTIES.

Destination: HZ_PARTIES.PARTY_NUMBER

CUSTOMER_STATUS

Enter the status of your customer. This column is required.

Validation: Must equal 'A' for Active or 'I' for Inactive. If you do not enter a value in this column, the status is defaulted to 'A'.

Destination: HZ_CUST_ACCOUNTS.STATUS and
HZ_PARTIES_STATUS

CUSTOMER_TYPE

Enter 'Internal' or 'External' to indicate customer type for your customer. This column is optional.

Validation: AR_LOOKUPS.LOOKUP_CODE where LOOKUP_TYPE = 'CUSTOMER_TYPE'. Multiple rows with the same customer reference must have the same customer type.

Destination: HZ_CUST_ACCOUNTS.CUSTOMER_TYPE

CUST_TAX_CODE, SITE_USE_TAX_CODE

Enter the tax code that you want to assign to your customer or business purpose, depending on the column you choose. You must use tax codes that you previously defined in the Tax Codes and Rates window. These columns are optional.

Validation: Must exist in AR_VAT_TAX.

Destination: HZ_CUST_ACCOUNTS.TAX_CODE and
HZ_CUST_SITE_USES_ALL.TAX_CODE

CUST_TAX_EXEMPT_NUM

This column is not currently used by Customer Interface and must be left blank.

Validation: None

Destination: None

CUST_TAX_REFERENCE

Enter the tax registration number for your customer. This column is optional.

Validation: None

Destination: HZ_PARTIES.TAX_REFERENCE

CUST_SHIP_VIA_CODE, SITE_SHIP_VIA_CODE

Enter the freight carrier you want to assign to your customer or the customer's business purpose, depending on the column you choose. Use freight carriers that you previously defined in the Freight Carriers window. This column is optional.

Validation: Must exist in ORG_FREIGHT.

Destination: HZ_CUST_ACCOUNTS.SHIP_VIA and
HZ_CUST_SITE_USES_ALL.SHIP_VIA

CREATED_BY

Enter the user ID that is creating this row. This column is required.

Validation: None

Destination: None

CREATION_DATE

Enter the system date. This column is required.

Validation: Must be a valid date format.

Destination: None

DEMAND_CLASS_CODE

Enter the demand class for your customer's address. Use demand classes that you previously defined in the Demand Classes window. This column is optional.

Validation: Must exist in FND_COMMON_LOOKUPS

Destination: HZ_CUST_SITE_USES_ALL.DEMAND_CLASS_CODE

GL_ID_REC

If the business purpose for your customer's address is Bill-To, enter the code combination ID for the Receivable account. This column is optional.

Validation: None

Destination: HZ_CUST_SITE_USES_ALL.GL_ID_REC

GL_ID_REV

If the business purpose for your customer's address is Bill-To, enter the code combination ID for the Revenue account. This column is optional.

Validation: None

Destination: HZ_CUST_SITE_USES_ALL.GL_ID_REV

GL_ID_TAX

If the business purpose for your customer's address is Bill-To, enter the code

combination ID for the Tax account. This column is optional.

Validation: None

Destination: HZ_CUST_SITE_USES_ALL.GL_ID_TAX

GL_ID_FREIGHT

If the business purpose for your customer's address is Bill-To, enter the code combination ID for the Freight account. This column is optional.

Validation: None

Destination: HZ_CUST_SITE_USES_ALL.GL_ID_FREIGHT

GL_ID_CLEARING

If the business purpose for your customer's address is Bill-To, enter the code combination ID for the AutoInvoice Clearing Account. This column is optional.

Validation: None

Destination: HZ_CUST_SITE_USES_ALL.GL_ID_CLEARING

GL_ID_UNBILLED

If the business purpose for your customer's address is Bill-To, enter the code combination ID for the Unbilled Receivable account. This column is optional.

Validation: None

Destination: HZ_CUST_SITE_USES_ALL.GL_ID_UNBILLED

GL_ID_UNEARNED

If the business purpose for your customer's address is Bill-To, enter the code combination ID for the Unearned Revenue account. This column is optional.

Validation: None

Destination: HZ_CUST_SITE_USES_ALL.GL_ID_UNEARNED

INSERT_UPDATE_FLAG

Specify whether you are inserting a new record or updating an existing record. This column is required.

Validation: 'T' for insert or 'U' for update.

Destination: None

INTERFACE_STATUS

This column is used by Customer Interface and should be left null. The Customer Interface program updates this column with all error messages that apply to this interface record. If an interface record has several problems, the Customer Interface program updates this column with multiple error codes.

LOCATION

Enter a shorthand name for your customer's business purpose. You use this value to quickly refer to a business purpose during data entry.

Validation: If automatic site numbering is set to No, you must enter a value in this column. If not, do not enter a value. Values for this column must be unique.

Destination: HZ_CUST_SITE_USES_ALL.LOCATION

Important: This column is not updatable.

LOCATION_CCID

This column is used by Customer Interface and should be left null. Customer Interface stores the code combination ID of valid addresses in this column.

Validation: None

Destination: None

LAST_UPDATED_BY

Enter the user ID that is updating this row. This column is required.

Validation: None

Destination: None

LAST_UPDATE_DATE

Enter the system date. This column is required.

Validation: Must be a valid date format.

Destination: None

LAST_UPDATE_LOGIN

Enter the login ID. This column is optional.

Validation: None

Destination: None

LANGUAGE

Enter the language used by your customer's site. This column is optional.

Validation: Must exist in FND_LANGUAGES.NLS_LANGUAGE

Destination: HZ_CUST_ACCT_SITES_ALL.LANGUAGE

MESSAGE_TEXT

This column is used by Customer Interface and should be left null.

Validation: None

Destination: None

ORG_ID

Enter the operating unit for which you want the Customer Interface program to validate and import customer information.

This column is optional. If you do not enter a value, the Customer Interface program validates and imports customer information for all the operating units on your access list.

Validation: Common Utility MO_GLOBAL.GET_VALID_ORG() validates that the ORG_ID is NOT NULL and is on your access list.

Destination: None

ORIG_SYSTEM_ADDRESS_REF

Enter a value you can use to uniquely identify your customer's address in your original system.

This column forms part of the primary key for RA_CUSTOMERS_INTERFACE. The primary key is a combination of ORIG_SYSTEM_CUSTOMER_REF, ORIG_SYSTEM_ADDRESS_REF, and SITE_USE_CODE.

To enter multiple addresses for a customer, enter multiple records in RA_CUSTOMERS_INTERFACE with identical customer information, but with different

address information.

This column is required if you are either inserting or updating address information.

Validation: Must not exist in HZ_LOCATIONS for insert. Must exist in HZ_CUST_ACCT_SITES_ALL for update.

Destination: HZ_LOCATIONS.Orig_System_Reference and HZ_CUST_ACCT_SITES_ALL.Orig_System_Reference

Orig_System_Customer_Ref

Enter a value that uniquely identifies your customer in your original system.

This column forms part of the primary key for RA_CUSTOMERS_INTERFACE. The primary key is a combination of Orig_System_Customer_Ref, Orig_System_Address_Ref, and Site_Use_Code.

If you are entering a new customer, you must also enter a customer level profile in RA_CUSTOMER_PROFILES_INTERFACE. This column is required.

Validation: Must not exist in HZ_PARTIES for insert. Must exist in HZ_CUST_ACCOUNTS for update. The same customer reference cannot have different customer names within this table. Inserts for this column must be unique.

Destination: HZ_CUST_ACCOUNTS.Orig_System_Reference and HZ_PARTIES.Orig_System_Reference

Orig_System_Parent_Ref

Enter the original system reference of the related customer, if one exists. If you enter a value in this column, the system checks the Create Reciprocal Customer Accounts parameter for the Customer Interface programs to determine whether the application should automatically create the reciprocal relationship.

If the parameter is set to *Yes*, the system creates an additional, opposite entry in the HZ_CUST_ACCT_RELATE_ALL table. This column is optional.

Validation: Must exist in HZ_PARTIES.Orig_System_Reference and HZ_CUST_ACCOUNTS.Orig_System_Reference. Multiple rows with the same customer reference must have the same Orig_System_Parent_Ref.

Destination: Inserts into HZ_CUST_ACCT_RELATE_ALL.Cust_Account_Id.

ORIG_SYSTEM_PARTY_REF

Enter a value you can use to unique identify a party in your original system. To create a new customer for an existing party, you must populate this column with the existing party's reference. This column is used for creating multiple customer accounts for one party through Customer Interface.

If you do not provide an original system reference, then the value from the ORIG_SYSTEM_CUSTOMER_REF column becomes the reference for the party as well as the customer.

Validation: Must exist in HZ_PARTIES for insert and update.

Destination: HZ_PARTIES.ORIG_SYSTEM_REFERENCE

PARTY_NUMBER

Enter the party number if the HZ: Generate Party Number profile option is set to *No*. If the profile option is set to *Yes*, you must leave this column blank because the party number is automatically generated.

Validation: Must exist in HZ_PARTIES for insert and update.

Destination: HZ_PARTIES.PARTY_NUMBER

PARTY_SITE_NUMBER

Enter the party site number if the HZ: Generate Party Site Number profile option is set to *No*. If the profile option is set to *Yes*, you must leave this column blank because the party site number is automatically generated.

Validation: Must exist in HZ_PARTY_SITES for insert and update.

Destination: HZ_PARTY_SITES.SITE_NUMBER

PERSON_FLAG

Enter Y if your customer is a person.

Validation: Must be 'Y,' 'N,' or null.

Destination: None

PERSON_FIRST_NAME

If your customer is a person, then enter the person's first name.

Validation: None

Destination: HZ_PARTIES.PERSON_FIRST_NAME and
HZ_PERSON_PROFILES.PERSON_FIRST_NAME

PERSON_LAST_NAME

If your customer is a person, then enter the person's last name, also known as the surname or family name.

Validation: None

Destination: HZ_PARTIES.PERSON_LAST_NAME and
HZ_PERSON_PROFILES.PERSON_LAST_NAME

PRIMARY_SITE_USE_FLAG

Enter 'Y' or 'N' to indicate whether a site use is the primary business purpose. Enter a value in this column only if the INSERT_UPDATE_FLAG is 'Y' and you enter a value in ORIG_SYSTEM_ADDRESS_REF. If you do not enter a value in this column, the first active site use is made primary.

Validation: Must have only one primary business purpose for each usage (Bill-To, Ship-To, and so on). Must be null, 'Y,' or 'N'.

Mandatory when inserting an address and must be null when the record is for updating purposes. Not updatable.

Destination: HZ_CUST_SITE_USES_ALL.PRIMARY_FLAG

REQUEST_ID

This column is used by Customer Interface and should be left null.

SITE_USE_CODE

Enter the business purpose for your customer's address. Use business purposes you previously defined in the Receivables Lookups window with a lookup type of 'Business purposes for a customer address.'

This column forms part of the primary key for RA_CUSTOMERS_INTERFACE. The primary key is a combination of ORIG_SYSTEM_CUSTOMER_REF, ORIG_SYSTEM_ADDRESS_REF, and SITE_USE_CODE.

If you enter a value in ORIG_SYSTEM_ADDRESS_REF, you must enter a value in this column. To enter multiple business purposes for an address, enter multiple records in RA_CUSTOMERS_INTERFACE with identical customer and address information, but with different site uses. You can only assign one type of business purpose to each address.

Validation: Must equal a value in AR_LOOKUPS.LOOKUP_CODE

where LOOKUP_TYPE = 'SITE_USE_CODE'. Inserts for this column must be unique.

Destination: HZ_CUST_SITE_USES_ALL.SITE_USE_CODE

SITE_USE_TAX_EXEMPT_NUM

This column is not currently used by Customer Interface and must be left blank.

Validation: None

Destination: None

SITE_USE_TAX_REFERENCE

Enter the tax registration number for your customer's site. This column is optional.

Validation: None

Destination: HZ_CUST_SITE_USES_ALL.TAX_REFERENCE

TERRITORY

Enter the territory associated with your customer record.

Validation: None

Destination: HZ_CUST_ACCT_SITES_ALL.TERRITORY

TRANSLATED_CUSTOMER_NAME

The translated customer name.

Validation: None

Destination: HZ_CUST_ACCT_SITES_ALL.TRANSLATED_CUSTOMER_NAME

VALIDATED_FLAG

This column is used by Customer Interface and should be left null.

Destination: HZ_CUST_ACCOUNTS.CUSTOMER_TYPE

WARNING_TEXT

This column is not currently used by Customer Interface.

URL

The uniform resource locator (URL) for your customer's home page on the World Wide Web. This column is optional.

Validation: None

Destination: HZ_CONTACT_POINTS.URL

Table Name: RA_CUSTOMER_PROFILES_INTERFACE

This table stores customer profile information. If you are entering a new customer in RA_CUSTOMERS_INTERFACE, you must either pass a customer profile class that already exists or customer profile values. You do not have to enter values in this table if you are not entering a new customer or assigning customer profile information to customer addresses.

The HZ_CUST_PROFILE_CLASSES table contains values from the profile class that you pass, or from the seeded profile class if you do not provide a class. During import, these values populate the HZ_CUSTOMER_PROFILES table.

The data in the RA_CUSTOMERS_PROFILES_INTERFACE table also populates the HZ_CUSTOMER_PROFILES table. Because both sources can provide values for the same column in the HZ_CUSTOMER_PROFILES table, the resulting value depends on whether the value from the RA_CUSTOMER_PROFILES_INTERFACE table is null or not.

- **Value is not null** - The value from the RA_CUSTOMER_PROFILES_INTERFACE table always overwrites any value from the HZ_CUST_PROFILE_CLASSES table.

- **Value is null**

- These fields in the HZ_CUSTOMER_PROFILES table still take the null value from the RA_CUSTOMER_PROFILES_INTERFACES table:

AUTO_REC_INCL_DISPUTED_FLAG

CREDIT_HOLD

CREDIT_RATING

PERCENT_COLLECTABLE

RISK_CODE

ATTRIBUTE_CATEGORY

ATTRIBUTE1 through ATTRIBUTE15

CLEARING_DAYS

GLOBAL_ATTRIBUTE_CATEGORY

GLOBAL_ATTRIBUTE1 through GLOBAL_ATTRIBUTE20

Note: During the update of customer profiles, the RISK_CODES and CREDIT_RATING fields in the HZ_CUSTOMER_PROFILES table retain their existing values when the values for these fields are null in the RA_CUSTOMER_PROFILES_INTERFACES table.

- These fields in the HZ_CUSTOMER_PROFILES table take instead the value from the HZ_CUST_PROFILE_CLASSES table:

COLLECTOR_ID (referenced by the COLLECTOR_NAME column in the RA_CUSTOMER_PROFILES_INTERFACE table)

CREDIT_BALANCE_STATEMENTS

CREDIT_CHECKING

DISCOUNT_TERMS

DUNNING_LETTERS

INTEREST_CHARGES

STATEMENTS

TOLERANCE

TAX_PRINTING_OPTION

AUTOCASH_HIERARCHY_ID (referenced by the AUTOCASH_HIERARCHY_NAME column in the RA_CUSTOMER_PROFILES_INTERFACE table)

DISCOUNT_GRACE_DAYS

INTEREST_PERIOD_DAYS

OVERRIDE_TERMS

PAYMENT_GRACE_DAYS

STANDARD_TERMS (referenced by the STANDARD_TERM_NAME column in the RA_CUSTOMER_PROFILES_INTERFACE table)

STATEMENT_CYCLE_ID (referenced by the STATEMENT_CYCLE_NAME column in the RA_CUSTOMER_PROFILES_INTERFACE table)

CHARGE_ON_FINANCE_CHARGE_FLAG

GROUPING_RULE_ID (referenced by the GROUPING_RULE_NAME column in the RA_CUSTOMER_PROFILES_INTERFACE table)

CONS_INV_FLAG

CONS_INV_TYPE

AUTOCASH_HIERARCHY_ID_FOR_ADR (referenced by the
AUTOCASH_HIERARCHY_NAME_ADR column in the
RA_CUSTOMER_PROFILES_INTERFACE table)

LOCKBOX_MATCHING_OPTION

CREDIT_ANALYST_ID (not exposed in the
RA_CUSTOMER_PROFILES_INTERFACE table)

REVIEW_CYCLE (not exposed in the
RA_CUSTOMER_PROFILES_INTERFACE table)

ACCOUNT_STATUS

Enter the status of your customer's account. Use account statuses you previously defined in the Receivables Lookups window with a lookup type of 'Account Status.' This column is optional.

Validation: AR_LOOKUPS.LOOKUP_CODE where LOOKUP_TYPE =
'ACCOUNT_STATUS' and ENABLED_FLAG='Y'

Destination: HZ_CUSTOMER_PROFILES.ACCOUNT_STATUS

ATTRIBUTE_CATEGORY, AMOUNT_ATTRIBUTE_CATEGORY

Enter Descriptive Flexfield category information. These columns are optional.

Validation: None

Destination: HZ_CUSTOMER_PROFILES.ATTRIBUTE_CATEGORY
and
HZ_CUST_PROFILE_AMTS.ATTRIBUTE_CATEGORY

ATTRIBUTE1-15, AMOUNT_ATTRIBUTE1-15

Enter Descriptive Flexfield information. These columns are optional.

Validation: None

Destination: HZ_CUSTOMER_PROFILES.ATTRIBUTE1-15 and
HZ_CUST_PROFILE_AMTS.ATTRIBUTE1-15

AUTO_REC_INCL_DISPUTED_FLAG

Specify whether to include debit items that have been placed in dispute when you create automatic receipts for your customers. Defaults to No if null.

Validation: Must equal 'Y' (Yes) or 'N' (No). Mandatory when profile class is null.

Destination: HZ_CUSTOMER_PROFILES.AUTO_REC_INCL_DISPUTE
D_FLAG

AUTOCASH_HIERARCHY_NAME

Enter the AutoCash Rule set to assign to your customer. Use AutoCash Rules sets that you previously defined in the AutoCash Rule Sets window.

Validation: Must exist in AR_AUTOCASH_HIERARCHIES with status 'A.' Mandatory when no profile class specified.

Destination: HZ_CUSTOMER_PROFILES.AUTOCASH_HIERARCHY_I
D

AUTO_REC_MIN_RECEIPT_AMOUNT

Enter the minimum receipt amount that must be specified for your customer when you create automatic receipts in this currency. This column is optional.

Validation: None

Destination: HZ_CUST_PROFILE_AMTS.AUTO_REC_MIN_RECEIPT_
AMOUNT

CHARGE_ON_FINANCE_CHARGE_FLAG

Specify whether you want to compound interest for your customer.

Validation: Must equal 'Y' (Yes) or 'N' (No). Required if INTEREST_CHARGES is set to 'Y.' Do not enter a value if INTEREST_CHARGES is null or set to 'N'.

Destination: HZ_CUSTOMER_PROFILES.CHARGE_ON_FINANCE_C
HARGE_FLAG

CLEARING_DAYS

Enter the number of clearing days for a customer profile.

Validation: Must be an integer greater than or equal to zero.

Destination: HZ_CUSTOMER_PROFILES.CLEARING_DAYS

COLLECTOR_NAME

Enter the collector assigned to a customer profile.

Validation: Must be unique in AR_COLLECTORS and STATUS = 'A'

(Active). Mandatory when no profile class specified.

Destination: HZ_CUSTOMER_PROFILES.COLLECTOR_ID (derived from CUSTOMER_NAME)

CONS_INV_FLAG

Enter Y if you send your customer consolidated billing invoice.

Validation: If you enter a value, you must enter either Y or N.

Destination: HZ_CUSTOMER_PROFILES.CONS_INV_FLAG

CONS_INV_TYPE

If you send your customer consolidated bills, then enter the type of consolidated billing invoice, SUMMARY or DETAIL.

Validation: None

Destination: HZ_CUSTOMER_PROFILES.CONS_INV_TYPE

CREATED_BY

Enter the user ID that is creating this row. This column is required.

Validation: None

Destination: None

CREATION_DATE

Enter the system date. This column is required.

Validation: Must be a valid date format.

Destination: None

CREDIT_BALANCE_STATEMENTS

Specify whether to send statements to customers with credit balances.

Validation: Must equal 'Y' (Yes) or 'N' (No). Must be 'N' when STATEMENTS = 'N.' Mandatory when no profile class specified. Mandatory when STATEMENTS = Yes. Must be null when STATEMENTS is null.

Destination: HZ_CUSTOMER_PROFILES.CREDIT_BALANCE_STATEMENTS

CREDIT_HOLD

Specify whether to put a hold on your customer's credit.

Validation: Must equal 'Y' (Yes) or 'N' (No)'.

Destination: HZ_CUSTOMER_PROFILES.CREDIT_HOLD

CREDIT_RATING

Enter the credit rating for your customer. Use credit ratings you previously defined in the Receivables Lookups window using the lookup Type 'Credit rating for customers.' This column is optional.

Validation: AR_LOOKUPS.LOOKUP_CODE where LOOKUP_TYPE = 'CREDIT_RATING' and ENABLED_FLAG='A'

Destination: HZ_CUSTOMER_PROFILES.CREDIT_RATING

CURRENCY_CODE

Enter a currency code to define customer profile amounts for your customer. Use currency codes previously defined in the Currencies window. Regardless of the value stored in INSERT_UPDATE_FLAG, Customer Interface always inserts and updates customer profile amount values you pass in this table. You must enter a value if any one of the following columns have values:

INTEREST_RATE

MAX_INTEREST_CHARGE

MIN_DUNNING_AMOUNT

MIN_DUNNING_INVOICE_AMOUNT

MIN_FC_BALANCE_AMOUNT

MIN_FC_INVOICE_AMOUNT

MIN_STATEMENT_AMOUNT

OVERALL_CREDIT_LIMIT

TRX_CREDIT_LIMIT

To update customer profile amounts, you provide a currency code for each row in the interface table. To update just the customer profile, you provide one row with a null CURRENCY_CODE column. To update both, you must provide a row with a null CURRENCY_CODE column to update the profile and rows with currency code to update the amounts.

Validation: Must exist in FND_CURRENCIES. Mandatory when a profile amount value is populated. (Profile amount

columns are listed above.)

Destination: HZ_CUST_PROFILE_AMTS.CURRENCY_CODE

CUSTOMER_PROFILE_CLASS_NAME

Enter the name of the customer profile class you want to assign to a customer or bill-to, dunning, or statements address. This column is required.

If this column is null, an active profile class with a profile class ID of '0' must exist in the HZ_CUST_PROFILE_CLASSES table.

Validation: Must equal HZ_CUST_PROFILE_CLASSES.NAME and STATUS = 'A' (Active)

Destination: HZ_CUSTOMER_PROFILES.CUSTOMER_PROFILE_CLASS_ID (derived from CUSTOMER_PROFILE_CLASS_NAME)

DISCOUNT_TERMS, CREDIT_CHECKING, DUNNING_LETTERS, INTEREST_CHARGES, STATEMENTS

Specify whether to allow discounts, check credit, send dunning letters, charge interest or and send statements.

Validation: Must equal 'Y' (Yes) or 'N' (No). Mandatory when no profile class specified.

Destination: HZ_CUSTOMER_PROFILES.DISCOUNT_TERMS, HZ_CUSTOMER_PROFILES.CREDIT_CHECKING, HZ_CUSTOMER_PROFILES.DUNNING_LETTERS, HZ_CUSTOMER_PROFILES.INTEREST_CHARGES, and HZ_CUSTOMER_PROFILES.STATEMENTS

DISCOUNT_GRACE_DAYS

Enter the number of days after the discount date that your customer can still take discounts.

Validation: Number must be non-negative (must be ≥ 0). Must be null when DISCOUNT_TERMS is null or 'No'.

Destination: HZ_CUSTOMER_PROFILES.DISCOUNT_GRACE_DAYS

GROUPING_RULE_NAME

Enter the grouping rule to assign to your customer. Use grouping rules you previously defined in the Grouping Rules window.

Validation:	Must exist in RA_GROUPING_RULES. Mandatory when no profile class is specified.
Destination:	HZ_CUSTOMER_PROFILES.GROUPING_RULE_ID (derived from GROUPING_RULE_NAME)

INTERFACE_STATUS

This column is used by Customer Interface and should be left null. The Customer Interface program updates this column with all error messages which apply to this interface record. If an interface record has several problems, the Customer Interface program updates this column with multiple error codes.

Validation:	None
Destination:	None

INSERT_UPDATE_FLAG

Enter a value to indicate whether you are inserting a new record or updating an existing record.

Regardless of the value you enter in this column, you cannot insert or update profile information in the following columns: CURRENCY_CODE, AUTO_REC_MIN_RECEIPT_AMOUNT, INTEREST_RATE, MAX_INTEREST_CHARGE, MIN_DUNNING_AMOUNT, MIN_DUNNING_INVOICE_AMOUNT, MIN_FC_BALANCE_AMOUNT, MIN_FC_INVOICE_AMOUNT, MIN_STATEMENT_AMOUNT, OVERALL_CREDIT_LIMIT, TRX_CREDIT_LIMIT, AMOUNT_ATTRIBUTE_CATEGORY and AMOUNT_ATTRIBUTE1 through AMOUNT_ATTRIBUTE15.

If you are trying to insert new profile amount information, Customer Interface will automatically insert this information even if this column is set to 'U.' For example, if you want to update the tax printing option value for a record that you have already inserted and at the same time enter a new currency code for this customer profile, enter 'U' in this column. Customer Interface will automatically update the tax printing option value and automatically insert the new currency code.

This column is required.

Validation:	I' for insert, 'U' for update
Destination:	None

INTEREST_PERIOD_DAYS

Enter the number of days to which the interest rate refers.

Validation:	Number must be positive. Mandatory when INTEREST_CHARGES is Yes. Must be null when INTEREST_CHARGES is No or null.
Destination:	HZ_CUSTOMER_PROFILES.INTEREST_PERIOD_DAYS

INTEREST_RATE

Enter the interest rate to charge your customer for this currency. This column is optional.

Validation:	None
Destination:	HZ_CUST_PROFILE_AMTS.INTEREST_RATE

LAST_UPDATED_BY

Enter the user ID that is updating this row. This column is required.

Validation:	None
Destination:	None

LAST_UPDATE_DATE

Enter the system date. This column is required.

Validation:	Must be a valid date format.
Destination:	None

LAST_UPDATE_LOGIN

Enter the login ID. This column is optional.

Validation:	None
Destination:	None

MAX_INTEREST_CHARGE

Enter the maximum amount of interest to charge your customer in this currency for each invoice. This column is optional.

Validation:	None
Destination:	HZ_CUST_PROFILE_AMTS.MAX_INTEREST_CHARGE

MIN_DUNNING_AMOUNT

Enter the minimum amount in this currency that must be past due for your customer before you select the customer for dunning. This column is optional.

Validation: None

Destination: HZ_CUST_PROFILE_AMTS.MIN_DUNNING_AMOUNT

MIN_DUNNING_INVOICE_AMOUNT

Enter the minimum invoice amount in this currency that must be past due for your customer before you select the customer for dunning. This column is optional.

Validation: None

Destination: HZ_CUST_PROFILE_AMTS.MIN_DUNNING_INVOICE_AMOUNT

MIN_FC_BALANCE_AMOUNT

Enter the minimum customer balance that you require before you charge your customer finance charges for past due items in this currency. This column is optional.

Validation: None

Destination: HZ_CUST_PROFILE_AMTS.MIN_FC_BALANCE_AMOUNT

MIN_FC_INVOICE_AMOUNT

Enter the minimum invoice balance that you require before you charge your customer finance charges for past due items in this currency. This column is optional.

Validation: None

Destination: HZ_CUST_PROFILE_AMTS.MIN_FC_INVOICE_AMOUNT

MIN_STATEMENT_AMOUNT

Enter the minimum outstanding balance in this currency that your customer must exceed in order for a statement to be generated. This column is optional.

Validation: None

Destination: HZ_CUST_PROFILE_AMTS.MIN_STATEMENT_AMOUNT

ORG_ID

Enter the operating unit for which you want the Customer Interface program to validate and import customer information.

This column is optional. If you do not enter a value, the Customer Interface program validates and imports customer information for all the operating units on your access list.

Validation: Common Utility MO_GLOBAL.GET_VALID_ORG() validates that the ORG_ID is NOT NULL and is on your access list.

Destination: None

ORIG_SYSTEM_CUSTOMER_REF

Enter the value that represents the customer or bill-to, dunning, or statements site for which you are inserting or updating customer profile information.

Validation: For insert, this customer reference must exist in HZ_CUST_ACCOUNTS or be successfully validated in RA_CUSTOMERS_INTERFACE. For update, this customer reference must exist in HZ_CUST_ACCOUNTS.

Destination: HZ_CUSTOMER_PROFILES.CUSTOMER_ID (Derived from ORIG_SYSTEM_CUSTOMER_REF)

ORIG_SYSTEM_ADDRESS_REF

Enter the value that represents the customer bill-to, dunning, or statements address for which you are inserting or updating customer profile information. An active bill-to, dunning, or statements business purpose must be associated with this address.

Validation: For insert, this address reference must exist in HZ_CUST_ACCT_SITES or be successfully validated in RA_CUSTOMERS_INTERFACE. For update, this address reference must exist in HZ_CUST_ACCT_SITES.

Destination: HZ_CUSTOMER_PROFILES.SITE_USE_ID (derived from ORIG_SYSTEM_ADDRESS_REF)

OVERALL_CREDIT_LIMIT

Enter the total amount of credit to give to your customer in this currency. This column is optional.

Validation: TRX_CREDIT_LIMIT and OVERALL_CREDIT_LIMIT

must both be filled in, or both be null.
TRX_CREDIT_LIMIT may not be greater than the
OVERALL_CREDIT_LIMIT.

Destination: HZ_CUST_PROFILE_AMTS.OVERALL_CREDIT_LIMIT

OVERRIDE_TERMS

Specify whether you want to be able to enter payment terms that are different from the payment term you enter in STANDARD_TERM_NAME.

Validation: Must equal 'Y' (Yes) or 'N' (No). Mandatory when no profile class is specified.

Destination: HZ_CUSTOMER_PROFILES.OVERRIDE_TERMS

PAYMENT_GRACE_DAYS

Enter the number of days you will allow your customer's receipt to be overdue before you initiate collection action.

Validation: Number must be non-negative (must be ≥ 0).

Destination: HZ_CUSTOMER_PROFILES.PAYMENT_GRACE_DAYS

PERCENT_COLLECTABLE

Enter the percentage of your customer's account balance that you expect to collect regularly. This column is optional.

Validation: Must be between 0 to 100.

Destination: HZ_CUSTOMER_PROFILES.PERCENT_COLLECTABLE

REQUEST_ID

This column is used by Customer Interface, and should be left null.

Validation: None

Destination: None

RISK_CODE

Enter the risk code for your customer. Use risk codes you previously defined in the Receivables Lookups window with a lookup type of 'Customer credit risk.' This column is optional.

Validation: AR_LOOKUPS.LOOKUP_CODE where LOOKUP_TYPE = 'RISK_CODE'

Destination: HZ_CUSTOMER_PROFILES.RISK_CODE

STANDARD_TERM_NAME

Enter the standard payment terms for your customer. Use payment terms that you previously defined in the Payment Terms window. This column is optional.

Validation: Must exist in RA_TERMS. Must have a unique value. Mandatory when no profile class is specified.

Destination: HZ_CUSTOMER_PROFILES.STANDARD_TERMS
(derived from STANDARD_TERM_NAME)

STATEMENT_CYCLE_NAME

Enter the statement cycle to associate with your customer. Use statement cycles that you previously defined in the Statement Cycles window.

Validation: Must exist in AR_STATEMENT_CYCLES. Must be null when STATEMENTS is No or null. Mandatory when STATEMENTS is Yes. Must have a unique value.

Destination: HZ_CUSTOMER_PROFILES.STATEMENT_CYCLE_ID
(derived from STATEMENT_CYCLE_NAME)

TAX_PRINTING_OPTION

Enter a tax printing option to indicate how you want to print tax information for your customer's invoices.

Validation: AR_LOOKUPS.LOOKUP_CODE where LOOKUP_TYPE = 'TAX_PRINTING_OPTION'. Mandatory when no profile class specified.

Destination: HZ_CUSTOMER_PROFILES.TAX_PRINTING_OPTION

TOLERANCE

Enter the percent over the credit limit that your customer can exceed before you will act.

Validation: Must be between -100 and 100. Mandatory when no profile class specified.

Destination: HZ_CUSTOMER_PROFILES.TOLERANCE

TRX_CREDIT_LIMIT

Enter the amount of credit for each order that you want to give to your customer in this currency.

Validation: TRX_CREDIT_LIMIT and OVERALL_CREDIT_LIMIT must both be filled in, or both be null.
TRX_CREDIT_LIMIT may not be greater than the OVERALL_CREDIT_LIMIT.

Destination: HZ_CUST_PROFILE_AMTS.TRX_CREDIT_LIMIT

VALIDATED_FLAG

This column is used by Customer Interface, and should be left null.

Validation: None

Destination: None

Table Name: RA_CONTACT_PHONES_INTERFACE

This table stores telephone numbers for customers, addresses and contacts as well as contacts for customers and addresses. You do not have to enter values in this table if you do not want to pass telephone or contact information.

CONTACT_ATTRIBUTE_CATEGORY

Enter Descriptive Flexfield category information. This column is optional.

Validation: None

Destination: HZ_ORG_CONTACTS.ATTRIBUTE_CATEGORY and
HZ_CUST_ACCT_ROLES.ATTRIBUTE_CATEGORY

PHONE_ATTRIBUTE_CATEGORY

Enter Descriptive Flexfield category information. This column is optional.

Validation: None

Destination: HZ_CONTACT_POINTS.ATTRIBUTE_CATEGORY

PHONE_ATTRIBUTE_1-15

Enter Descriptive Flexfield category information. These columns are optional.

Validation: None

Destination: HZ_CONTACT_POINTS.ATTRIBUTE1 TO 15

CONTACT_ATTRIBUTE1-24

Enter Descriptive Flexfield information. These columns are optional.

Validation: None

Destination: HZ_ORG_CONTACTS.ATTRIBUTE1 TO 24 and
HZ_CUST_ACCT_ROLES.ATTRIBUTE1 TO 24

CONTACT_FIRST_NAME

Enter the contact's first name.

Validation: None

Destination: HZ_PARTIES.PERSON_FIRST_NAME and
HZ_PERSON_PROFILES.PERSON_FIRST_NAME

CONTACT_JOB_TITLE

Enter the job title or responsibility for this contact. Use contact job titles that you previously defined in the Receivables Lookups window. This column is optional.

Validation: AR_LOOKUPS.LOOKUP_CODE where LOOKUP_TYPE =
'RESPONSIBILITY'

Destination: HZ_ORG_CONTACTS.JOB_TITLE_CODE

CONTACT_LAST_NAME

Enter the contact's last name. If ORIG_SYSTEM_CONTACT_REF is filled in, then you must enter a value in this column. Otherwise, this column is optional.

Validation: None

Destination: HZ_PARTIES.PERSON_LAST_NAME and
HZ_PERSON_PROFILES.PERSON_LAST_NAME

CONTACT_POINT_TYPE

Enter the type of the contact point, such as phone or e-mail, that you want to update.

Validation: AR_LOOKUPS.LOOKUP_CODE where LOOKUP_TYPE =
'COMMUNICATION_TYPE'. Mandatory when specifying
contact point information.

Destination: HZ_CONTACT_POINTS.CONTACT_POINT_TYPE

CONTACT_TITLE

Enter the title for this contact. This column is optional.

Validation: AR_LOOKUPS.LOOKUP_CODE where LOOKUP_TYPE = 'CONTACT_TITLE'

Destination: HZ_ORG_CONTACTS.TITLE

CREATED_BY

Enter the user ID that is creating this row. This column is required.

Validation: None

Destination: None

CREATION_DATE

Enter the system date. This column is required.

Validation: Must be a valid date format.

Destination: None

INTERFACE_STATUS

This column is used by Customer Interface and should be left null. The Customer Interface program updates this column with all error messages that apply to this interface record. If an interface record has several problems, the Customer Interface program updates this column with multiple error codes.

INSERT_UPDATE_FLAG

Enter a value to indicate whether you are inserting a new record or updating an existing record. This column is required.

Validation: 'I' for insert, 'U' for update.

Destination: None

LAST_UPDATED_BY

Enter the userid that is updating this row. This column is required.

Validation: None

Destination: None

LAST_UPDATE_DATE

Enter the system date. This column is required.

Validation: Must be a valid date format.

Destination: None

LAST_UPDATE_LOGIN

Enter the login ID. This column is optional.

Validation: None

Destination: None

ORG_ID

Enter the operating unit for which you want the Customer Interface program to validate and import customer information.

This column is optional. If you do not enter a value, the Customer Interface program validates and imports customer information for all the operating units on your access list.

Validation: Common Utility MO_GLOBAL.GET_VALID_ORG() validates that the ORG_ID is NOT NULL and is on your access list.

Destination: None

ORIG_SYSTEM_CUSTOMER_REF

Enter a value that you can use to uniquely identify your customer in your original system.

Validation: Must equal HZ_CUST_ACCOUNTS.ORIG_SYSTEM_REFERENCE for update. If you are entering either contact or telephone information, you must enter a value in this column.

Destination: None

ORIG_SYSTEM_ADDRESS_REF

Enter a value that you can use to uniquely identify this address in your original system.

If this column is null, the phone or contact that you enter refers to the customer.

Validation: Must equal
HZ_CUST_ACCT_SITES_ALL.Orig_System_Reference
for update. If you are entering information that refers to
an address, such as a contact or telephone, then you must
enter a value in this column.

Destination: None

Orig_System_Contact_Ref

Enter a value that you can use to uniquely identify this contact in your original system.

This column forms part of the primary key for HZ_CUST_ACCT_ROLES and
HZ_ORG_CONTACTS. The primary key is a combination of
Orig_System_Contact_Ref and Orig_System_Telephone_Ref.

To enter a contact for a customer, do not enter a value in
Orig_System_Address_Ref.

If you are entering a contact for a specific address, then enter values in both
Orig_System_Customer_Ref and Orig_System_Address_Ref.

Validation: Must equal
HZ_ORG_CONTACTS.Orig_System_Reference for
update. If you are entering contact information or
information that refers to a contact, such as a telephone
number assigned to a contact, you must enter a value in
this column.

Destination: HZ_ORG_CONTACTS.Orig_System_Reference and
HZ_CUST_ACCT_ROLES.Orig_System_Reference

Orig_System_Telephone_Ref

Enter a value that you can use to uniquely identify this telephone in your original
system.

This column forms part of the primary key for RA_CONTACT_PHONES_INTERFACE.
The primary key is a combination of Orig_System_Contact_Ref and
Orig_System_Telephone_Ref.

To enter a telephone for a customer, do not enter values in
Orig_System_Address_Ref or Orig_System_Contact_Ref.

To enter a telephone for a specific address, enter values in
Orig_System_Customer_Ref and Orig_System_Address_Ref.

To enter telephones for a specific contact, enter values in
Orig_System_Customer_Ref, Orig_System_Contact_Ref, and

ORIG_SYSTEM_ADDRESS_REF, if the contact is associated with an address.

Validation: Must equal
HZ_CONTACT_POINTS.ORIG_SYSTEM_REFERENCE.
Mandatory when specifying telephone information.

Destination: HZ_CONTACT_POINTS.ORIG_SYSTEM_REFERENCE

REQUEST_ID

This column is used by Customer Interface and should be left null.

TELEPHONE

Enter the telephone number for the customer, address, or contact.

Validation: Mandatory when specifying telephone information (for example, if ORIG_SYSTEM_TELEPHONE_REF is filled in).

Destination: HZ_CONTACT_POINTS.PHONE_NUMBER

TELEPHONE_AREA_CODE, TELEPHONE_EXTENSION

Enter the area code or extension for the telephone number, depending on the column you choose. These columns are optional.

Validation: None

Destination: HZ_CONTACT_POINTS.AREA_CODE and
HZ_CONTACT_POINTS.EXTENSION

TELEPHONE_TYPE

Enter the type of telephone number such as General, Fax, or Telex. Use telephone types that you previously defined in the Receivables Lookups window with a lookup type of 'Types of communication used in contacting customers.'

- If TELEPHONE_TYPE in RA_CONTACTS_PHONES_INT_ALL = 'TLX,' then CONTACT_POINT_TYPE = 'TLX' and PHONE_LINE_TYPE is null.
- If TELEPHONE_TYPE in RA_CONTACTS_PHONES_INT_ALL is a valid lookup code of PHONE_LINE_TYPE lookup and = 'Phone,' then CONTACT_POINT_TYPE = 'PHONE' and PHONE_LINE_TYPE = 'GEN.'
- If TELEPHONE_TYPE in RA_CONTACTS_PHONES_INT_ALL is a valid lookup code of PHONE_LINE_TYPE lookup and does not = 'PHONE,' then CONTACT_POINT_TYPE = 'PHONE' and PHONE_LINE_TYPE = valid lookup code 'X.'

If you want to specify that the phone line type is general, then you should populate the interface table with 'GEN.' The CONTACT_POINT_TYPE will be 'PHONE' for all telephone types except 'TLX.'

Validation: AR_LOOKUPS.LOOKUP_CODE where LOOKUP_TYPE = 'PHONE_LINE_TYPE' or 'TLX.' Mandatory when specifying telephone information (for example, if ORIG_SYSTEM_TELEPHONE_REF is filled in).

Destination: HZ_CONTACT_POINTS.CONTACT_POINT_TYPE

VALIDATED_FLAG

This column is used by Customer Interface and should be left null.

SEX_CODE

The gender of the contact person (male or female). This column is not currently used by Customer Interface.

EMAIL_ADDRESS

The electronic mail address for this contact person. This column is optional.

Validation: None

Destination: HZ_CONTACT_POINTS.EMAIL_ADDRESS

MAIL_STOP

The location used by the postal service to deliver mail to this contact person. This column is optional.

Validation: None

Destination: HZ_ORG_CONTACTS.MAIL_STOP

SALUTATION

The introductory greeting to use in official documents sent to this contact person. This column is not currently used by Customer Interface.

CONTACT_KEY

This column is populated by an Oracle Sales and Marketing Application Programming Interface (API). This column is optional.

Validation: None

Destination: HZ_ORG_CONTACTS.CONTACT_KEY

Table Name: RA_CUSTOMER_BANKS_INTERFACE

This table stores bank information for a customer or for a specific Bill-To address. You do not have to enter values in this table if you do not want to insert or assign customer bank information. If you associate an automatic payment method to a customer or a customer's Bill-To business purpose, you must enter a bank account for this customer.

ATTRIBUTE_CATEGORY

Enter Descriptive Flexfield category information. This column is optional.

Validation: None

Destination: AP_BANK_ACCOUNT_USES.ATTRIBUTE_CATEGORY

ATTRIBUTE1-15

Enter Descriptive Flexfield information. This column is optional.

Validation: None

Destination: AP_BANK_ACCOUNT_USES.ATTRIBUTE1-15

BANK_ACCOUNT_NUM, BANK_ACCOUNT_CURRENCY_CODE

Enter the account number or currency code for this bank account, depending on the column you choose. This number must be unique within a bank branch.

Validation: If the bank account already exists, do not enter a value. If the bank account does not exist, you must enter a value.

Destination: IBY_EXT_BANK_ACCOUNTS.BANK_ACCOUNT_NUM
and IBY_EXT_BANK_ACCOUNTS.CURRENCY_CODE

BANK_ACCOUNT_INACTIVE_DATE

Enter the date that this bank account becomes inactive. This column is optional.

Validation: Must be a valid date format.

Destination: IBY_EXT_BANK_ACCOUNTS.END_DATE

BANK_ACCOUNT_DESCRIPTION

Enter a description for this bank account. This column is optional.

Validation: None

Destination: IBY_EXT_BANK_ACCOUNTS.DESRIPTION

BANK_ACCOUNT_CHECK_DIGITS

Enter the number this bank account prints on checks. This column is optional.

Validation: None

Destination: IBY_EXT_BANK_ACCOUNTS.CHECK_DIGITS

BANK_ACCOUNT_NAME

Enter the bank account name to assign to a customer or Bill-To address. Use the Banks window to define banks and bank accounts for your customers. If the bank account has not already been defined, Customer Interface will try to create it in AP_BANK_ACCOUNTS. This column is required.

Validation: Must exist in AP_BANK_ACCOUNTS or, if it does not exist, values must exist for BANK_ACCOUNT_CURRENCY_CODE, BANK_ACCOUNT_NUM, BANK_NAME, and BANK_BRANCH_NAME.

Destination: IBY_EXT_BANK_ACCOUNTS.BANK_ACCOUNT_NAME

BANK_NAME, BANK_BRANCH_NAME

Enter the name of the bank or bank branch for the account you are inserting. If the bank account does not exist, you must enter a value.

Validation: BANK_NAME together with BANK_BRANCH_NAME must be unique. If the bank account already exists, do not enter a value. Bank_Branch_Name is mandatory when the bank account is not defined.

Destination: HZ_PARTIES.PARTY_NAME.

BANK_NUMBER

Enter the number of the bank associated with the bank account.

Validation: Must be unique. If the bank account already exists, do not enter a value. If the bank account does not exist, this column is optional.

Destination: HZ_ORGANIZATION_PROFILES.BANK_OR_BRANCH_

NUMBER

BANK_NUM

Enter the number of the bank branch associated with the bank account you are inserting.

Validation: Must be unique. If the bank account already exists, do not enter a value. If the bank account does not exist, this column is optional.

Destination: HZ_ORGANIZATION_PROFILES.BANK_OR_BRANCH_NUMBER

BANK_BRANCH_DESCRIPTION

Enter a description for this bank branch. This column is optional.

Validation: None

Destination: HZ_PARTIES.MISSION_STATEMENT

BANK_BRANCH_ADDRESS1-4, BANK_BRANCH_CITY, BANK_BRANCH_COUNTY, BANK_BRANCH_STATE, BANK_BRANCH_ZIP, BANK_BRANCH_PROVINCE

Enter the street address, city, county, state, postal code, or province for this bank branch. These columns are optional.

Validation: None

Destination: HZ_PARTIES.ADDRESS_LINE1-4, HZ_PARTIES.CITY,
HZ_LOCATIONS.BANK_BRANCH_COUNTY,
HZ_PARTIES.STATE, HZ_PARTIES.ZIP,
HZ_PARTIES.PROVINCE

BANK_BRANCH_COUNTRY

Enter the country for this bank branch. This column is optional.

Validation: Must exist in FND_TERRITORIES.TERRITORY_CODE.

Destination: HZ_PARTIES.COUNTRY

BANK_BRANCH_PHONE, BANK_BRANCH_AREA_CODE

Enter the telephone number or telephone area code for this bank branch. These columns are optional.

Validation:	None
Destination:	HZ_CONTACT_POINTS.PHONE_NUMBER and HZ_CONTACT_POINTS.PHONE_AREA_CODE

BANK_BRANCH_EFT_USER_NUMBER

Enter the Electronic Funds Transfer user ID. This column is optional.

Validation:	None
Destination:	HZ_CONTACT_POINTS.EFT_USER_NUMBER

BANK_ACCOUNT_ATT_CATEGORY, BANK_BRANCH_ATT_CATEGORY

Enter Descriptive Flexfield category information. These columns are optional.

Validation:	None
Destination:	AP_BANK_ACCOUNTS.ATTRIBUTE_CATEGORY and AP_BANK_BRANCHES.ATTRIBUTE_CATEGORY

BANK_ACCOUNT_ATTRIBUTE1-15, BANK_BRANCH_ATTRIBUTE1-15

Enter Descriptive Flexfield information. These columns are optional.

Validation:	None
Destination:	AP_BANK_ACCOUNTS.ATTRIBUTE1-15 and AP_BANK_BRANCHES.ATTRIBUTE1-15

BANK_HOME_COUNTRY

Enter the home country code for the bank. This column is optional.

Validation:	This column is validated against FND_TERRITORIES. Mandatory when creating a new bank.
Destination:	HZ_ORGANIZATION_PROFILES.HOME_COUNTRY

CREATED_BY

Enter the user ID that is creating this row. This column is required.

Validation:	None
Destination:	None

CREATION_DATE

Enter the system date. This column is required.

Validation: Must be a valid date format.

Destination: None

END_DATE

Enter the date that this bank account becomes inactive. This column is optional.

Validation: End Date cannot be before the start date. Customers can be assigned to multiple bank accounts as long as there is no overlapping date range. Must be a valid date format.

Destination: IBY_PMT_INSTR_USES_ALL.END_DATE

INTERFACE_STATUS

This column is used by Customer Interface and should be left null. The Customer Interface program updates this column with all error messages that apply to this interface record. If an interface record has several problems, the Customer Interface program updates this column with multiple error codes.

Validation: None

Destination: None

LAST_UPDATED_BY

Enter the user ID that is updating this row. This column is required.

Validation: None

Destination: None

LAST_UPDATE_DATE

Enter the system date. This column is required.

Validation: Must be a valid date format.

Destination: None

LAST_UPDATE_LOGIN

Enter the login ID. This column is optional.

Validation: None

Destination: None

ORG_ID

Enter the operating unit for which you want the Customer Interface program to validate and import customer information.

This column is optional. If you do not enter a value, the Customer Interface program validates and imports customer information for all the operating units on your access list.

Validation: Common Utility MO_GLOBAL.GET_VALID_ORG() validates that the ORG_ID is NOT NULL and is on your access list.

Destination: None

ORIG_SYSTEM_CUSTOMER_REF

Enter the value that represents the customer for which you are inserting bank information. This column is required.

Validation: The customer reference must exist in HZ_CUST_ACCOUNTS or be successfully validated in RA_CUSTOMERS_INTERFACE.

Destination: IBY_EXTERNAL_PAYERS_ALL.CUST_ACCOUNT_ID

ORIG_SYSTEM_ADDRESS_REF

Enter the value that represent the customer address for which you are inserting bank information. An active Bill-To business purpose must be associated with this address. This column is required only if you want to insert bank information for a specific Bill-To address.

Validation: For insert, the address reference must exist in HZ_CUST_ACCT_SITES_ALL or be successfully validated in RA_CUSTOMERS_INTERFACE (derived from ORIG_SYSTEM_CUSTOMER_REF)

Destination: IBY_EXTERNAL_PAYERS_ALL.ACCT_SITE_USE_ID

PRIMARY_FLAG

Indicates whether this is the primary bank account for this customer or Bill-To address. This column is required.

Validation: Enter 'Y' or 'N.' Only one primary bank account can exist at either the customer level or address level.

Destination: IBY_PMT_INSTR_USES_ALL.ORDER_OF_PREFERENCE

REQUEST_ID

This column is used by Customer Interface, and should be left null.

Validation: None

Destination: None

START_DATE

Enter the starting date that this bank account becomes active. This column is required.

Validation: End Date cannot be before the start date. Customers can be assigned to multiple bank accounts as long as there is no overlapping date range. Must be a valid date format.

Destination: IBY_PMT_INSTR_USES_ALL.START_DATE

VALIDATED_FLAG

This column is used by Customer Interface, and should be left null.

Validation: None

Destination: None

Table Name: RA_CUST_PAY_METHOD_INTERFACE

This table stores payment method information for a customer or for a specific Bill-To address. If you associate an automatic payment method to a customer or a customer's Bill-To address, a bank account must exist for this customer. You do not have to enter values in this table if you do not want to assign a payment method to a customer. You cannot insert payment methods using Customer Interface. You must use the Payment Methods window to create new payment methods.

ATTRIBUTE_CATEGORY

Enter Descriptive Flexfield category information. This column is optional.

Validation: None

Destination: RA_CUST_RECEIPT_METHODS.ATTRIBUTE_CATEGORY

ATTRIBUTE1-15

Enter Descriptive Flexfield information. This column is optional.

Validation: None

Destination: RA_CUST_RECEIPT_METHODS.ATTRIBUTE1-15

CREATED_BY

Enter the user ID that is creating this row. This column is required.

Validation: None

Destination: None

CREATION_DATE

Enter the system date. This column is required.

Validation: Must be a valid date format.

Destination: None

END_DATE

Enter the date that this payment method becomes inactive. This column is optional.

Validation: Customers can be assigned to multiple payment methods as long as there is no overlapping date range. Must be a valid date format.

Destination: RA_CUST_RECEIPT_METHODS.END_DATE

INTERFACE_STATUS

This column is used by Customer Interface and should be left null. The Customer Interface program updates this column with all error messages that apply to this interface record. If an interface record has several problems, the Customer Interface program updates this column with multiple error codes.

Validation: None

Destination: None

LAST_UPDATED_BY

Enter the user ID that is updating this row. This column is required.

Validation: None

Destination: None

LAST_UPDATE_DATE

Enter the system date. This column is required.

Validation: Must be a valid date format.

Destination: None

LAST_UPDATE_LOGIN

Enter the login ID. This column is optional.

Validation: None

Destination: None

ORG_ID

Enter the operating unit for which you want the Customer Interface program to validate and import customer information.

This column is optional. If you do not enter a value, the Customer Interface program validates and imports customer information for all the operating units on your access list.

Validation: Common Utility MO_GLOBAL.GET_VALID_ORG() validates that the ORG_ID is NOT NULL and is on your access list.

Destination: None

ORIG_SYSTEM_CUSTOMER_REF

Enter the value that represents the customer for which you are inserting a payment method. This column is required.

Validation: The customer reference must exist in HZ_CUST_ACCOUNTS or be successfully validated in RA_CUSTOMERS_INTERFACE.

Destination: RA_CUST_RECEIPTS_METHODS.CUSTOMER_ID (derived from ORIG_SYSTEM_CUSTOMER_REF)

ORIG_SYSTEM_ADDRESS_REF

Enter the value that represents the customer address for which you are inserting a payment method. An active Bill-To business purpose must be associated with this address. This column is required only if you are inserting a payment method for a specific Bill-To address.

Validation: This address reference must exist in HZ_PARTY_SITES or be successfully validated in RA_CUSTOMERS_INTERFACE.

Destination: RA_CUST_RECEIPT_METHODS.SITE_USE_ID (derived from ORIG_SYSTEM_ADDRESS_REF)

PAYMENT_METHOD_NAME

Enter the name of the payment method that you want to assign to a customer or Bill-To address. This column is required.

Validation: Must exist in AR_RECEIPT_METHODS.

Destination: RA_CUST_RECEIPTS_METHODS.RECEIPT_METHOD_ID (derived from PAYMENT_METHOD_NAME)

PRIMARY_FLAG

Enter 'Y' or 'N' to indicate whether this is the primary payment method for a customer or Bill-To address. This column is required.

Validation: Only one primary payment method can exist at either the customer level or Bill-To address level.

Destination: RA_CUST_RECEIPTS_METHODS.PRIMARY_FLAG

REQUEST_ID

This column is used by Customer Interface and should be left null.

Validation: None

Destination: None

START_DATE

Enter the starting date that this payment method becomes active. This column is required.

Validation: Customers can be assigned to multiple payment methods

as long as there is no overlapping date range. Must be a valid date format.

Destination: RA_CUST_RECEIPT_METHODS.START_DATE

VALIDATED_FLAG

This column is used by Customer Interface and should be left null.

Validation: None

Destination: None

Related Topics

Customer Interface, *Oracle Trading Community Architecture User Guide*

System Tables Updated by Customer Interface, *Oracle Trading Community Architecture User Guide*

Interface Data Required to Run Customer Interface, *Oracle Trading Community Architecture User Guide*

A Sample Customer Import, *Oracle Trading Community Architecture User Guide*

D&B Data Elements

This chapter covers the following topics:

- D&B Data Elements Overview
- General Data Elements
- Financial Data Elements

D&B Data Elements Overview

The D&B data products include over 150 separate data elements that are mapped to columns in the TCA Registry. The names of some of the D&B data elements are slightly different from the column names in the HZ tables.

Related Topics

Oracle eBusiness Suite Electronic Technical Reference Manual (eTRM)

General Data Elements, page 3-1

Financial Data Elements, page 3-16

General Data Elements

8(A) Firms Indicator

The 8(A) Firms Indicator identifies a small business classified by the Small Business Administration as socially or economically disadvantaged. A value of Yes means the business is classified as disadvantaged. This indicator is available only for US companies.

Average High Credit

The average high credit represents the median of the highest credit extended to the

subject business over the past 12 months. The average is calculated by taking the sum of all high credit dollar amounts from unique supplier account experiences divided by the total number of account experiences.

Capital Type

This element group describes the amount and type of capital in the business. The amount and currency code specify the value. Type Indicator describes whether the amount is Issued Capital, Paid in Capital, Nominal, or Authorized. Paid Up or Issued Capital is the amount of capital pledged by shareholders at any given time and is calculated by multiplying the number of shares issued by the par value or face of each share. Some shares confer different obligations or voting rights on their owners. The share capital is a component of the equity of any company along with reserves and accumulated profits or losses. In the event of a liquidation of the business, any shares not yet paid up must be fully paid up at that time. Nominal or Authorized Capital refers to a maximum amount of set issued or paid-up capital beyond which the subject could not issue any further capital or shares.

CEO Name

The name of the individual identified as having the chief executive function. The CEO is the highest ranking person on site: President, Owner, Branch Manager, and so on. Some data products provide the individual's title along with the name.

CEO Title

The position title of the primary executive in the company.

Claims Indicator

Indicates if open claims, liens, protested bills, warrants, Social Securities Summons, or equivalent exist in the D&B database for the case company.

Commentary

Automatically generated comments, as necessary.

Commentary Counter

Number of Commentary items.

Commercial Credit Score (USA)

The Commercial Credit Score (USA) is a statistically modeled D&B score indicating the risk of delinquent payments based on the information in D&B's files. The higher the score, the lower the probability of payment delinquency.

The Commercial Credit Score (USA) predicts the likelihood that a company will pay its bills in a severely delinquent manner (over 90 days past term) within the next twelve

months. Severely delinquent is defined as a business with at least 25% of its payments slow and at least 10% of its payments 90 days or more past due.

This score is only available to D&B customers in the United States for businesses located in the United States.

Commercial Credit Score (USA) Data Product

This data product includes the Commercial Credit Score (USA) as well as other indicators of creditworthiness such as the D&B Credit Rating, the Paydex score, and bankruptcy information.

This score is only available to D&B customers in the United States for businesses located in the United States.

Congressional District Code

The Congressional District Code is a number that represents a congressional district of the United States.

Control Year

The year that the present majority control or ownership of shares was established. Can be the same as Start Year.

Country Code

The two character ISO code for the country where the business is located.

Credit Score Class

A number between 0 and 5 that indicates the risk of delinquent payments over the next 12 months.

Credit Score Class Explanation

A descriptive explanation of the Credit Score Class. It describes the risk of delinquent payment over the next 12 months.

Credit Score Percentile

The percentile places the business in a 1 to 100 rank order with 1 indicating the highest risk and 100 indicating the lowest risk among the other businesses in D&B's US database.

Criminal Indicator

The Criminal Indicator provides an indication of whether criminal proceedings related to the case exist in D&B's database.

Currency

Default three character ISO currency code for figures in the data product.

D&B Rating

The D&B Rating gives an indication of credit worthiness. The D&B Rating is normally divided into two parts, the financial strength code and the risk indicator reflects the risk associated with the business. The Financial Strength component is an indication of the size of the subject's tangible net worth (that is, the shareholders funds less any intangible assets) based primarily on the most recent fiscal balance sheet results. The Composite Appraisal component is linked to the level of risk and is an overall evaluation of credit worthiness. It takes into account the financial condition but also several nonfinancial factors such as trade payment history, length of operation, employee numbers, legal structure, management experience, and any adverse listings.

In some countries, D&B uses other information in its databases to assign an ER code (size by employee range) to businesses within specific industries or *R* ratings for companies without current financial statements on file. The Rating Interpretation Tables contain specific rating definitions and interpretation tables for countries around the world.

Date Scored

The date on which the Commercial Credit Score was generated.

Debarments Count

A count of the debarments present in the D&B file.

Debarments Date

The date of the last current debarment filing. This element is available only from the US.

Debarments Element Group

A count of the US government debarments present in the D&B file and the date of the last current debarment filing.

Delinquency Score (calculated)

The Credit/Delinquency Score is a statistically modeled D&B score indicating the risk of delinquent payments based on the information in D&B's files. The higher the Delinquency Score, the lower the probability of payment delinquency.

The US Delinquency Score predicts the likelihood that a company will pay its bills in a severely delinquent manner (over 90 days past term), or obtain legal relief from creditors, or cease operations without paying all creditors in full over the next 12 months, based on the information in D&B's files. Severely delinquent is defined as a

business with at least 25% of its payments slow and at least 10% of its payments 90 days or more past due.

The Australian Delinquency Score measures the probability that a business will pay in a severely delinquent manner, defined as at least 10% of trade payments being more than 90 days beyond terms in the next 12 months.

The New Zealand Delinquency Score predicts the probability of severely delinquent payment within the next 12 months; however, the definition of severely delinquent is at least 20% of trade payments being more than 60 days beyond terms.

The Canadian Delinquency Score predicts the likelihood of a firm paying in a severely delinquent manner during the next twelve months where severely delinquent is defined as over 90 days past terms.

Delinquency Score Class

The Delinquency Score Class enables you to quickly segment your new and existing accounts into various risk segments to determine appropriate marketing or credit policies. The Class segments the data into five distinct risk groups where 1 represents businesses that have the lowest probability of severe delinquency, 5 represents businesses with the highest probability of severe delinquency. The Incidence of default relates the percentage probability of delinquency outcome for a score range/class.

Delinquency Score Commentary

The Credit (Delinquency) Score Commentary is a repeating field containing codes which explain the conditions driving the score assigned to the business.

Delinquency Score Industry Percentile, Delinquency Score National Percentile

The Delinquency Score Percentile illustrates where a company falls among businesses in the D&B information base, and is most effectively used to rank order portfolios from highest to lowest risk of business failure. The percentile is based on a 1 to 100 scale, where 1 represents businesses that have the highest probability of severe delinquency, and 100 which represents businesses with the lowest probability of severe delinquency.

Delinquency Score Override Code

Delinquency Score Override Code is populated for special case instances in Australia where the delinquency score is a special value (0, 893-895) or cannot be calculated.

Disaster Special Events Indicator

Indicates if special events exist in the D&B database for the subject company concerning disasters such as fire, flood, earthquake, hurricane, and so on.

Domestic Ultimate Element Group

This group of elements provides the Domestic Ultimate Name, D-U-N-S Number, and

country code in which the business is located. The Domestic Ultimate is the highest corporate family member in the same country as the subject business if you walk up the branch of the corporate family tree. A business may be its own domestic ultimate. The fields will be blank if the subject business is a single location (not linked) in the D&B database. The Domestic Ultimate Name is the legal business name. The Domestic Ultimate party can be a headquarters or a branch/division. A country can have more than one Domestic Ultimate organization. There will be a separate Domestic Ultimate party for each limb of a tree.

Do Not Confuse With

Indicates that a similarly named business should not be confused with the business undergoing review.

D-U-N-S Number

D-U-N-S, which stands for Data Universal Numbering System, is a 9-digit nonindicative identification number assigned by D&B to each separate commercial entity in the D&B database. Each record is given a different number. For businesses with multiple locations, each location is assigned its own unique D-U-N-S Number. This field is always populated and contains the D-U-N-S number of the business that all other data elements in the record describe.

Employees Statistics Group

The Employees Statistics group provides the total number of persons employed by this business and the number of persons at this physical address (excluding employees of branches or divisions who are not at this physical address). The Estimated or Actual and the Minimum, Maximum, or Average indicators qualify the data provided for the number of employees.

Enquiry D-U-N-S

Identifier of case enquired upon, will be the same as D-U-N-S unless a trade up from a branch to a headquarters location has taken place.

Export Indicator

Indicates that the D&B database contains information whether the business exports or not.

Failure Score (calculated), Failure Score Aggregate, Failure Score Industry Incidence of Default

D&B's Failure Scores predict the probability of severe financial distress or failure. The Failure Score Commentary field is available only from the US and contains explanation codes for that particular score.

In the US, the calculated failure score (values 1,001 to 1,850) provides a direct relationship between the score and the level of risk. A 1,001 represents businesses that

have the highest probability of financial stress, and 1,850 the lowest probability of financial stress. The marginal odds of being good doubles for each 40 point increase. For example, a score of 1,200, on a marginal basis, represents twice the risk of financial stress as a score of 1,240. This score enables you to use more granular cutoffs to drive your automated decision-making process. Failure scores are not calculated in the US for those businesses designated as Discontinued at This Location, Open Bankruptcy, Higher Risk, or Self Inquired D-U-N-S®. These records are automatically assigned a score of 0.

For Japan, the Failure Score (values 0 to 10) predicts the probability of closure (failure) in the next twelve months.

In Canada, where there is a Stability Score predicting the probability of business closure, instead of failure, the value in the Failure Score field is the Stability Score (values 1 to 10).

Failure Score Class

The Failure Score Class segments the data into five distinct risk groups where 1 represents businesses that have the lowest probability of financial stress, and 5 represents businesses with the highest probability of financial stress. This class enables you to quickly segment new and existing accounts into various risk segments to determine appropriate marketing or credit policies. The Incidence of default relates the percentage probability of failure outcome for a score range/class.

Failure Score Commentary

The Failure Score Commentary field is available only from the US and contains explanation codes for that particular score.

Failure Score National Percentile

The percentile score of 1 to 100 indicates where a company falls among businesses in the local D&B information base, and is most effectively used to rank order portfolios from highest to lowest risk of business failure. A percentile score of 1 represents businesses that have the highest probability of financial stress, and a 100 which represents businesses with the lowest probability of financial stress. Percentile Scores are available from Western Europe, the US and Australia.

Failure Score Override Code

In Europe, the Failure Score Override Code indicates the reason for variance between the D&B Rating and Failure Score. European values are: 1 indicates severe negative information, 2 indicates minimal data, 3 indicates new business, 4 indicates out of business, 5 indicates miscellaneous information. In the US, the code indicates the reason no score was calculated or that the score is equal to 0. The US values are 6 indicates special events, 7 indicates business discontinued at this location, 8 indicates open bankruptcy. Override codes 9 to 19 will be used to indicate special case instances for Australia where the failure score is a special value (0, 900 to 995) or cannot be

calculated.

Fax Number

The main facsimile number for the subject business.

Financial Embarrassment Indicator

Indicates whether a record exists of an open bankruptcy, receivership liquidation, discontinuance with unpaid obligations or an equivalent event related to the company in the D&B database. Other specific event categories relate to administrator appointments and orders, Meeting of Creditors, Wind Up Petitions and Statements of Insolvency.

Financial/Legal Special Events Indicator

Indicates whether special events exist in D&B's database that denote financial embarrassment or legal filings related to the business. These include Public Sales, Change of 50% of Assets, Public Filings, Letter of Liability, and Principals Antecedents – Bankruptcy.

Global Failure Score Aggregate, Global Failure Score (calculated), Global Failure Score Age, Global Failure Score Date

D&B's Global Failure Score predicts the likelihood of a firm ceasing business without paying all creditors in full, or reorganizing, or obtaining relief from creditors under state or federal law over the next 12 months. D&B's Global Failure Score is only available as a raw score with a four-digit scale starting from 1001-1850.

The Global Failure Score is a single, uniform measure predicting risk of failure in any included country. Included countries are defined as those countries that have a statistical model that predicts business failure for companies within that country. In the score's first version, these countries are Australia, Belgium, France, Germany, Italy, Netherlands, Portugal, Spain, United Kingdom, and United States.

While the Global Failure Score is defined as a single, uniform measure predicting risk of failure in any country, the definition of failure can vary from country to country. Therefore the Global Failure Score may be different for Country A and Country B at the same approval rate.

In most cases Global Failure Score will be used in combination with Local Country Failure Scores. The Global Failure Score provides a globally standardized measure of failure risk, whereas the Local Country Failure Scores provides information on how a specific company is performing relative to its peers in the same country. Both of these scores are critical for decision making and portfolio management for global customer account and vendor portfolios. Global Failure Score Age and Date are reserved for future use and are not currently populated.

Global Ultimate Element Group

This group of elements gives you the Global Ultimate Name, its D-U-N-S number, and the Country Code in which it is located. The Global Ultimate is the highest member of the corporate family worldwide. Fields will be blank if the business has a single location in the D&B database. The Global Ultimate Name is the legal business name. The Country code is the two-character ISO code for the country in which the Global Ultimate is located.

Headquarters or Branch

Indicates if the subject location is a branch or division. Branches and/or divisions are typically other locations, apart from the headquarters or principal trading office, from which the organization conducts its business. However, a division can operate from the same location as the headquarters. The distinction is that a division will utilize a separate tradestyle name and have separate and distinct operations from that of the headquarters. Branches are not separate legal entities. Indicates whether the subject business is a branch, headquarters, or single location.

Headquarters Element Group

This group of data elements gives you the Headquarters Name, its D-U-N-S number and the Country Code in which it is located. If the case inquired upon is a branch or division, the Headquarters D-U-N-S, Name, and Country Code (two-character ISO code) will appear in these fields. Fields will be blank if the record is a single location (not linked) in the D&B database.

High Range Score for Incidence of Delinquent Payment

This is the value of the high end of the range of the Commercial Credit Score for which an incidence of delinquency percentage could be linked. If range is between 240 to 280, the high range score is 280.

Highest Credit

Highest credit extended in the last 12 months.

History Indicator

Code indicating whether:

- Detrimental information exists about the company in the D&B database. For example, a current or past bankruptcy.
- Detrimental information exists about the management of the business in the D&B database. For example, a bankrupt affiliate.
- Complete details exist about the management and company, but no detrimental

information exists in the D&B database

- Incomplete details exist on management or company, but no detrimental information exists in the D&B database.

The History Indicator is not available from all of D&B's databases, including Europe, Australia, and New Zealand.

Import Indicator

Indicates whether the D&B database contains information that the business imports or not.

Incidence of Delinquent Payment Percentage for All Firms

This value is the delinquency percentage for all firms in D&B's US database.

Incidence of Delinquent Payment Percentage for Range

This value is the delinquency percentage for a specific Commercial Credit Score range.

Incorporation Year

The year the business incorporated. The Incorporation Year may or may not be the same as the year the business started.

International Dialing Code

The international telecommunications dialing code for the country in which the business is located.

Labor Surplus Area Indicator

Indicator of labor surplus area as defined by the United States Department of Labor and available only from the US.

Legal Status

A code indicating the legal structure of the business as registered with governmental authorities. Examples include LSC/102 (private limited company) or LSC/10 (general partnership).

Line of business

Narrative description of the operations or activities of the business generated from the primary SIC code under which it is classified.

Local Activity Code Element Group

Local Activity Classification Code. This field contains only NACE codes where they are available. NACE codes are a statistical classification of economic activities of the European Community. The Local Activity Code Type indicates whether the NACE code in the Local Activity Code field is a four- or five-digit NACE.

Local Business ID Element Group

The Local business ID Number field contains the primary business identification number assigned to the business by a government agency, Chamber of Commerce or association. The ID Type field contains the code representing the type of business identification number.

Location Ownership

Indicates whether premises at physical address are owned or rented.

Low Range Score for Incidence of Delinquent Payment

This value is the low end of the range of the Commercial Credit Score for which an incidence of delinquency percentage could be linked. If range is between 240 to 280, the low range score is 240.

Minority Owned Indicator

Indicates that a business is minority-owned. This indicator is available only from the US.

Name

The primary name of the business.

Negative Payment Explanation

Conditional comment generated when negative payment comments are used.

No Trade Indicator

Indicates if there are no trade experiences, or completed payment transactions, in the D&B files for this business.

Number of Trade Experiences

Number of completed transactions, usually payment experiences.

Operational Special Events Indicator

Indicates whether special events exist in the D&B database that concern changes to the

business' operations. These include categories such as name changes, management changes, changes of legal form, control, or capital; business wind up or closure; or moves.

Other Special Events Indicator

Indicates that special events not otherwise specified exist in the D&B database for the business.

Out of Business Indicator

Indicates that the company has discontinued operations.

Parent Element Group

This group of data elements gives you the Parent Name, its D-U-N-S number and the Country Code in which it is located. The Parent company has a majority interest in the subject company. The subject company is then referred to as a 'Subsidiary.'

Paydex

The D&B payment score (Paydex) is a score that assesses the payment performance of a business. Based on the trade experiences in D&B's database, the score corresponds to an average days beyond terms or within terms enabling you to predict when your existing or potential customer accounts are likely to pay. Derived from a dollar-weighted average of a company's combined individual payment experiences, it ranges from 0 to 100 with higher scores representing businesses which pay their bills more promptly. The Paydex Interpretation Tables contain interpretation tables for D&B's payment score for specific countries.

Paydex 3 Months Prior

Paydex Score from 3 months ago.

Paydex Norm

The industry median or average Paydex score for the subject's line of business.

Parent / Headquarters Bankruptcy Element Group

Indicates if the business has a relationship to a Parent or Headquarters that entered into bankruptcy.

- **Parent Name in Bankruptcy:** Name of the parent company in bankruptcy proceedings.
- **Parent D-U-N-S Number in Bankruptcy:** D-U-N-S number of the parent in bankruptcy.

- **Parent Bankruptcy Filing Counter:** Number of bankruptcy filings by a parent. Includes the Parent Bankruptcy Filing Type, Parent Bankruptcy Chapter Number, and Parent Bankruptcy Filing Date.
- **Parent Bankruptcy Filing Type:** The type of bankruptcy filed by the parent.
- **Parent Bankruptcy Chapter Number:** The chapter of bankruptcy filed by the parent.
- **Parent Bankruptcy Filing Date:** The date bankruptcy was filed by the parent (format YYYYMMDD).
- **Parent Bankruptcy Conversion Counter:** Number of the bankruptcy conversion by the parent. Includes Parent Bankruptcy Conversion Date and Parent Bankruptcy Chapter Conversion.
- **Parent Bankruptcy Conversion Date:** The date the bankruptcy was converted by the parent from one chapter type to another (format YYYYMMDD).
- **Parent Bankruptcy Chapter Conversion:** Change of bankruptcy type.

Postal Code

Part of the physical address, the code identifying the geographic subsection of the city in which the business is located. Known as the ZIP code in the United States, post or postal code elsewhere.

Postal Town

The name of the town (according to the postal service) in which the business is located.

Primary SIC Code

Standard Industrial Classification code. The four-digit SIC code is an index which describes the function (manufacturer, wholesaler, retailer or service) and the line of business in which the company is engaged.

Principal Title and Name

Names and job titles of principal executives of case subject.

Registration Type

Type of registration. Field values are RTC/1 (cooperative), RTC/2 (federally chartered), RTC/3 (professional), RTC/4 (profit), RTC/5 (state chartered), RTC/6 (nonprofit).

Secured Filings Indicator

Indicates whether open secured filings such as US UCC filings, secured charges/mortgages pledgings, or equivalent exist for the business in D&B's database.

SER Rating

The Supplier Evaluation Risk (SER) Rating predicts the likelihood of a firm ceasing business without paying all creditors in full, or reorganizing, or obtaining relief from creditors under state or federal law over the next 12 months. A rating of 1 represents the lowest risk factor while 9 represents the highest risk.

SIC Type

Version of SIC. Values are 1972 (used in Europe and Australia), 1977 (used in Canada), and 1987 (used in the US).

Slow Trade Explanation

Conditional comment generated when Paydex score is used or slow trade experiences are present.

Small Business Indicator

Indicates business is classified as a small business by the Small Business Administration (SBA). This indicator is available only from the US.

Street

Address line of physical location. Will also contain, if available, building name and neighborhood in separate lines.

Suits/Judgments Indicator

Indicates whether open suits, judgment, petitions or payment remarks exist in the D&B database for the company.

Tangible Net Worth Element Group

The Tangible Net Worth field contains equity of the business after all liabilities have been deducted from assets and any intangible assets have been disregarded. The Tangible Net Worth Indicator qualifies the amount, indicating whether it is actual or estimated. In some databases, the indicators and value may be in the alphanumeric Tangible Net Worth Text field. In Australia, there may be a code G after the value meaning that the figure is taken from a consolidated or group financial statement that will include the financial results of the subject's affiliates or sister subsidiaries as well.

Telephone Number

The main telephone number of the business. Different countries may have telephone numbers of varied lengths which may or may not include the country or city access codes. Each country does have an access code (contained in the International Dialing Code field) which must be used when dialing cross-border into that country.

Total Employees Element Group

The figure contained in the Total Employees field indicates the number of persons employed by the subject. The Total Employees Composition Table indicates if the value from a particular country will include subsidiaries, branches, or divisions. Some databases also include the indicator fields that tell you if subsidiaries are included or whether the Total Employees value is:

- Estimated or actual
- Minimum, maximum, or average

In some databases, the indicators and value may be contained in a combined alphanumeric field. This type of data will be delivered in the Total Employees Text field. For example, in Australia, if a G appears after the number, it indicates that the figure is a group figure.

Woman Owned Indicator

Indicates business is woman-owned. This indicator is available only in the US.

Total Payments

The total number of payment experiences contained in D&B's database for the subject company.

Trade Style, Alternate Name

Trade Styles are additional business names used by the company – also referred to as a DBA (doing business as) or AKA (also known as) names. In some jurisdictions, these names are shown to be registered to, and therefore owned by, a company. They are used to secure the name, advertise a particular product or to distinguish between different parts of the company's operations or divisions. These names are registered in the same way as a business or firm, with the responsible authority.

Year Started

The year that the organization actually commenced present operations. If the business was formed to acquire or continue the operations of a preexisting business, then the start date may reflect this original start date.

Financial Data Elements

Accounts Payable

Amount of merchandise purchased on credit and not paid for by the balance sheet date. Also known as Trade Creditors. In Italy, Accounts Payable include Cambiali Creditors where applicable.

Accounts Receivable

Amount of sales made and billed to customers on credit terms, but not yet paid. This is money owed by customers and not yet received. Also called Trade Debtors. The value may or may not be net of bad debts. In Italy, Accounts Receivable include Cambiali Debtors where applicable.

Audit Indicator

Indicates whether D&B has been able to determine whether the financial statement was prepared by audit. Not populated by all country databases. The Financial Statement Quality Table provides a description of the types/quality of financial statements loaded into various D&B country databases.

Cash and Liquid Assets

Amount of cash on hand and in banks and other liquid assets where available.

Consolidated indicator

Indicates whether statement is consolidated or not.

Cost of Sales

Cost of Sales (or Cost of Goods Sold where applicable) from the Profit & Loss or Income Statement.

Current Ratio

Current Assets divided by Current Liabilities. For Italy, the Current Ratio is calculated by *Total Current Assets – Stock Depreciation – Bad Debts* / *Total Current Liabilities*. For Belgium, the Current Ratio = *Total Current Assets* / (*Total Current Liabilities* + *Regularization Account*).

Dividends

Dividends paid to shareholders.

Estimated Indicator

Indicates whether the financial statement figures are estimated or actual. Not populated by all country databases.

Fiscal Indicator

Indicates whether the financial statement period is 12 months or not. Not populated by all country databases.

Final Indicator

Indicates if financial statement figures are the final closing statement for a business which has ceased trading. Not populated by all country databases.

Fixed Assets

Amount of tangible property owned by a business that has a life longer than one year such as buildings, equipment and land. Should be the net cost (original cost minus depreciation and revaluation).

Forecast Indicator

Indicates financial statement figures are future projections. Only present in Taiwan.

Gross Income

Amount left over after deducting the Cost of Goods sold from Net Sales. May be negative.

Income Statement Date

Date of Income or Profit & Loss Statement. Applies where no start or end dates are supplied.

Intangible Assets

Total of intangible assets (goodwill, patents, research and development, nonissued capital, organizational expenses). May or may not be net of depreciation or amortization.

Inventory

Includes merchandise on hand that is ready to be sold. May also include work in progress plus raw materials minus depreciation.

Long Term Debt

Long Term (Financial) Debt owed by the business. Includes categories such as minority

interest, convertible debentures (over one year), debentures, mortgages, loans, hire purchases due after one year, and pension debt due to group companies or participants. Excludes categories such as provisions and allowances.

Net Income

Amount left over after all expenses and taxes are deducted. Also called Net Profit or Loss after Taxes.

Net Worth

Total amount of Equity (Net Worth). Includes capital stock, retained earnings treasury stock, and so on – is not the Tangible Net Worth. May be negative.

Opening Indicator

Indicates figures that are the opening statement for the business. Not populated by all country databases.

P & L from Date

Starting Date of Profit and Loss Statement.

P & L to Date

Ending Date of Profit and Loss Statement.

Previous Net Worth

Previous Net Worth minus intangibles. May be negative to reflect a deficit net tangible worth position.

Previous Sales

Net sales for previous period.

Previous Statement Date

Date of previous financial statement. May be full date, month and year, or year only.

Previous Working Capital

Working Capital (*Current Assets minus Current Liabilities*) for previous period. For Italy, Working Capital is calculated as follows: *Total Current Assets – Stock Depreciation – Bad Debts – Total Current Liabilities*. For Belgium, Working Capital is calculated as follows: *Total Current Assets – (Total Current Liabilities + Regularization Account)*.

Profit Before Tax

Profit before tax, will appear as a negative if value is a pre-tax loss.

Pro forma Indicator

Indicates the financial statement figures are pro forma. Typically used to represent the state of a company as a result of a pending structural change based on actual or known performance.

Qualified Indicator

Indicates auditors have made qualifying remarks about the fairness and accuracy of the figures.

Quick Ratio

Cash plus Accounts Receivable divided by Current Liabilities. For Italy, the Quick Ratio is calculated by: $(Total\ Current\ Assets - Stock\ Depreciation - Bad\ Debts - Stocks\ \&\ Work\ in\ Process) / Total\ Current\ Liabilities$. For Belgium, the Quick Ratio is calculated by: $Total\ Current\ Assets - (Receivables\ over\ 1\ year + Total\ Net\ Stocks\ \&\ Work\ in\ Process) / (Total\ Current\ Liabilities + Regularization\ Account)$. For France, Iberia and Germany, the Quick Ratio is calculated by: $(Total\ Current\ Assets - Stocks) / Current\ Liabilities$. The Quick Ratio is not available for the United Kingdom or Ireland.

Re-Stated Indicator

Indicates figures resubmitted after corrections to original statement for period.

Retained Earnings

Retained earnings.

Sales

Net sales for the period after returns, allowances, and discounts are deducted. In Europe, this is the Sales for the period less taxes.

Signed Indicator

Indicates if figures are signed by principals.

Statement Currency

Currency code of financial statement. Some databases are populated only if the Statement Currency Code is different than the default.

Statement Date

Date of current financial statement. May be full date, month and year, or year only.

Subsidiary

Indicates whether the subject business is a subsidiary. A value of Yes indicates that it is a Subsidiary. A value of No indicates that it is not a subsidiary.

Total Assets

Total amount of current and long-term assets.

Total Current Assets

Total amount of all current (less than one year) assets.

Total Current Liabilities

Total amount of all current (less than one year) liabilities.

Total Liabilities

Total liabilities owed by business.

Total Liabilities & Equity

Total amount of Liabilities & Equity.

Total Long Term Liabilities

Total long term (greater than one year) liabilities owed by business.

Trial Balance Indicator

Indicates that financial statement figures are trial balance.

Unbalanced Indicator

Indicates submitted balance sheet figures do not balance.

Seeded Relationship Types, Phrases, and Roles

This chapter covers the following topics:

- Relationship Types
- Relationship Phrase and Role Pairs
- Relationship Phrase and Role Pair Codes

Relationship Types

This table lists the seeded relationship types and their definitions for hierarchical and circular allowed.

Relationship Type Code	Relationship Type Name	Hierarchical	Circular Allowed
AFFILIATE	Affiliation	No	Yes
AGREEMENT_SIGNER	Agreement Signing	No	Yes
APPLICANT_REFeree	Application Referee	No	Yes
APPROVING_MANAGER	Management Approval	No	Yes
ASSOCIATE	Association	No	Yes
BANKING_GROUP	Banking Group	No	Yes
BANK_ACCOUNT_CONTACT	Banking Contact	No	No

Relationship Type Code	Relationship Type Name	Hierarchical	Circular Allowed
BANK_AND_BRANCH	Bank and Branch	No	Yes
BENEFICIARY	Beneficiary	No	Yes
BOARD_MEMBER	Board Membership	No	Yes
BROKER	Broker	No	Yes
CAREGIVER	Caregiver	No	No
CLEARINGHOUSE_BANK	Bank Clearinghouse	No	Yes
COMPETITOR	Competitive	No	Yes
CONTACT	Contact	No	Yes
CTB_ENTERPRISE_HIER	Healthcare Enterprise Hierarchy	Yes	Yes
CUSTOMER/SELLER	Buying and Selling	No	Yes
CUSTOMER_PREFERED_SUPPLIER	Preferential Buying and Selling	No	Yes
DEFAULT_ADMIN	Default Administrator	No	Yes
DEPENDENT	Dependency	No	Yes
DNB_HIERARCHY	D&B Hierarchy	Yes	No
DOMESTIC_PARTNER	Domestic Partner	No	Yes
DOMESTIC_ULTIMATE	Domestic Ultimate	No	Yes
DOWNLOAD_CONTENT	Download Content	No	Yes
EMERGENCY_CONTACT	Emergency Contact	No	No
EMPLOYMENT	Employment	No	Yes
GLOBAL_ULTIMATE	Global Ultimate	No	Yes

Relationship Type Code	Relationship Type Name	Hierarchical	Circular Allowed
GUARANTOR	Guarantor	No	Yes
HEADQUARTERS/DIVISION	Corporate	No	Yes
INST_ACCREDITATION	Institutional Accreditation	No	No
INVENTORY_ORG	Inventory Organization	No	Yes
KEY_COMPANY	Key Company	No	Yes
LEGAL_CONTACT	Legal Contact	No	Yes
LE_AND_BANK	Legal Entity and Bank	No	Yes
MANAGER	Management	No	Yes
MEMBERSHIP	Membership	No	Yes
MODELED_BY	Modeling	No	Yes
NEXT_OF_KIN	Next of Kin	No	Yes
OU_AND_BANK	Operating Unit and Bank	No	Yes
PARENT/CHILD	Parent and Child	No	Yes
PARENT/SUBSIDIARY	Parent and Subsidiary	No	Yes
PARTNER	Partnership	No	Yes
PARTNER_HIERARCHY	Partner Hierarchy	Yes	No
PARTNER_MANAGED_CUSTOMER	Distributor	No	Yes
PAYTO	Paying	No	Yes
POM_DEFAULT_APPROVER	POM Default Approver	No	Yes
POM_PARTY_REFERENCE	POM Party Reference	No	Yes

Relationship Type Code	Relationship Type Name	Hierarchical	Circular Allowed
POS_ADDRESS_SITES	iSupplier Portal Address Sites	No	No
POS_EMPLOYMENT	POS Employment	No	No
POS_SUPPLIER_CONTACT	iSupplier Portal Supplier Contact	No	No
POS_VENDOR_CONTACT	iSupplier Portal Vendor Contact	No	No
POS_VENDOR_PARTY	POS Supplier	No	No
REFERENCE	Reference	No	Yes
REGISTERED_COMPANY	Registered Company	No	Yes
REG_APPROVER	Registered Approver	No	Yes
RELATIVE	Family Relation	No	Yes
REPAIR_DEPOT_PROVIDER	Depot Repair	No	Yes
SHIPTO	Shipping	No	Yes
SIBLING	Sibling	No	Yes
SPOUSE	Spousal	No	Yes
STOCK_HOLDER	Stock Holder	No	Yes
STUDENT/INSTRUCTOR	Teaching	No	Yes
STUDENTINSTITUTION	Student/Institution	No	No
STUDENT_ADVISING	Student Advising (Person)	No	No
STUDENT_ADVISING_AT	Student Advising (Organization)	No	No
STUDENT_COUNSELING	Student Counseling (Person)	No	No

Relationship Type Code	Relationship Type Name	Hierarchical	Circular Allowed
STUDENT_COUNSELING_AT	Student Counseling (Organization)	No	No
THIRD_PARTY_AUTHOR	Third Party Authorship	No	Yes
UNREGISTERED_COMPANY	Unregistered Company	No	Yes
VAD	VAD	No	Yes
VAR	VAR	No	Yes

Relationship Phrase and Role Pairs

This table lists the seeded relationship phrases and roles, as well as the subject and object types.

Relationship Type	Subject Type	Forward Role	Forward Phrase	Object Type	Backward Role	Backward Phrase
Affiliation	Organization (Parent)	Affiliate Of	Affiliates	Organization (Child)	Affiliate	Organization Affiliates
Agreement Signing	Organization (Parent)	Agreement Signer Of	Agreement Signers	Organization (Child)	Agreement Signer	Organizations with Agreement Signers
Application Referee	Person (Parent)	Referee	Referees	Person (Child)	Has Referee	People with Referee
Management Approval	Person (Parent)	Order Approving Manager Of	Exchange Approvers	Person (Child)	Approved By	Approved Exchange Users
Association	Person (Not Hierarchical)	Associate Of	Associates	Person (Not Hierarchical)	Associate Of	Associates

Relationship Type	Subject Type	Forward Role	Forward Phrase	Object Type	Backward Role	Backward Phrase
Banking Group	Group (Parent)	Includes Member	Banking Groups	Organization (Child)	Member Of	Banking Group Members
Banking Contact	Person (Parent)	Contact For	Bank Account Contacts	CE_BANK_ACCOUNT (Child)	Has Contact	Bank Accounts Contacts
Bank and Branch	Organization (Parent)	Has Branch	Banks Branches	Organization (Child)	Branch Of	Banks
Beneficiary	Person (Parent)	Beneficiary Of	Beneficiaries	Person (Child)	Benefactor Of	People Benefactors
Beneficiary	Organization (Parent)	Beneficiary Of	Organization Beneficiaries	Person (Child)	Benefactor Of	Benefactors
Board Membership	Person (Parent)	Board Member Of	Board Members	Organization (Child)	Contains Board Member	Boards
Broker	Organization (Parent)	Broker of	Brokers	Organization (Child)	Broker	Brokerages
Caregiver	Person (Parent)	Caregiver for	Caregivers	Person (Child)	Cared For By	Cared for Patients
Bank Clearinghouse	Organization (Parent)	Clearinghouse For	Clearinghouses Branches	Organization (Child)	Uses Clearinghouse	Bank Branches
Competitive	Organization (Not Hierarchical)	Competitor Of	Competitors	Organization (Not Hierarchical)	Competitor Of	Competitors
Contact	Person (Parent)	Contact For	People Contacts	Person (Child)	Has Contact	People with Contacts
Contact	Person (Parent)	Contact For	Organization Contacts	Organization (Child)	Has Contact	Organizations with Contacts

Relationship Type	Subject Type	Forward Role	Forward Phrase	Object Type	Backward Role	Backward Phrase
Healthcare Enterprise Hierarchy	Organization (Parent)	Parent Of	Healthcare Parent Organizations	Organization (Child)	Child of	Healthcare Child Organizations
Buying and Selling	Person (Parent)	Customer Of	People Customers	Organization (Child)	Seller To	Suppliers To People
Buying and Selling	Organization (Parent)	Customer Of	Organization Customers	Organization (Child)	Seller To	Suppliers for Organizations
Preferential Buying and Selling	Organization (Parent)	Preferred Supplier By	Preferred Suppliers	Organization (Child)	Preferred Supplier To	Customers with Preferred Suppliers
Default Administrator	Person (Parent)	Default Admin For	POM Default Administrators	Organization (Child)	Default Admin By	Organizations with POM Default Administrators
Dependency	Person (Parent)	Dependent Of	Guardians	Person (Child)	Guardian Of	Dependents
D&B Hierarchy	Organization (Parent)	Headquarters Of	D&B Headquarters	Organization (Child)	Division Of	D&B Divisions
D&B Hierarchy	Organization (Parent)	Domestic Ultimate Of	D&B Domestic Ultimates	Organization (Child)	Domestic Subsidiary Of	D&B Domestic Subsidiaries
D&B Hierarchy	Organization (Parent)	Parent Of	D&B Parents	Organization (Child)	Subsidiary Of	D&B Subsidiaries
D&B Hierarchy	Organization (Parent)	Global Ultimate Of	D&B Global Ultimates	Organization (Child)	Global Subsidiary Of	D&B Global Subsidiaries
Domestic Partner	Person (Not Hierarchical)	Domestic Partner Of	Domestic Partners	Person (Not Hierarchical)	Domestic Partner Of	Domestic Partners
Domestic Ultimate	Organization (Parent)	Domestic Ultimate Of	Domestic Ultimates	Organization (Child)	Domestic Subsidiary Of	Domestic Subsidiaries

Relationship Type	Subject Type	Forward Role	Forward Phrase	Object Type	Backward Role	Backward Phrase
Download Content	Organization (Parent)	Download Content To	Download Privilege Granters	Organization (Child)	Download Content From	Organizations with Privilege to Download
Emergency Contact	Person (Parent)	Emergency Contact for	Emergency Contacts	Person (Child)	Emergency Contact of	Has Emergency Contacts
Employment	Person (Parent)	Employee Of	Employees	Organization (Child)	Employer Of	Employers
Global Ultimate	Organization (Parent)	Global Ultimate Of	Global Ultimates	Organization (Child)	Global Subsidiary Of	Global Subsidiaries
Guarantor	Organization (Parent)	Guarantor For	Organization Guarantors of Organizations	Organization (Child)	Guarantor	Organizations with Organizations Guarantors
Guarantor	Organization (Parent)	Guarantor For	Institutional Guarantors	Person (Child)	Guarantor	People with Organization Guarantors
Guarantor	Person (Parent)	Guarantor For	Guarantors	Person (Child)	Guarantor	People with Guarantor
Corporate	Organization (Parent)	Headquarters Of	Headquarters	Organization (Child)	Division Of	Divisions
Institutional Accreditation	Organization (Parent)	Accredited By	Accredited Organizations	Organization (Child)	Accredits	Accrediting Organizations
Inventory Organization	Organization (Parent)	Inventory Organization Of	Inventory Organizations	Organization (Child)	Inventory Organization	Organizations with Inventory Organizations
Key Company	Organization (Parent)	Key Company Of	Key Companies	Organization (Child)	Key Company	Organizations with Key Companies

Relationship Type	Subject Type	Forward Role	Forward Phrase	Object Type	Backward Role	Backward Phrase
Legal Contact	Person (Parent)	Legal Contact For	POM Legal Contacts	Organization (Child)	Legal Contact	POM Organizations with Legal Contacts
Legal Entity and Bank	Organization (Parent)	Uses Bank	Legal Entities That Use Banks	Organization (Child)	Bank Used By	Banks Used by Legal Entities
Management	Person (Parent)	Reports To	Management Reports	Person (Child)	Manager Of	Managers
Membership	Group (Parent)	Member Of	Subgroups	Group (Child)	Includes Member	Groups with Subgroups
Membership	Organization (Parent)	Member Of	Organization Members	Group (Child)	Includes Member	Organization Groups
Membership	Person (Parent)	Member Of	Members	Group (Child)	Includes Member	Groups
Modeling	Organization (Parent)	Modeled By	Modeling Companies	Organization (Child)	Modeled Company	Modeled Companies
Next of Kin	Person (Parent)	Next of Kin for	Next of Kin	Person (Child)	Next of Kin of	Kin
Operating Unit and Bank	Organization (Parent)	Uses Bank	Operating Units That Use Bank	Organization (Child)	Bank Used By	Banks Used by Operating Units
Parent and Child	Person (Parent)	Parent Of	Parents	Person (Child)	Child of	Children
Parent and Subsidiary	Organization (Parent)	Parent Of	Parents of Subsidiaries	Organization (Child)	Subsidiary Of	Subsidiaries
Partnership	Organization (Not Hierarchical)	Partner Of	Partners	Organization (Not Hierarchical)	Partner Of	Partners

Relationship Type	Subject Type	Forward Role	Forward Phrase	Object Type	Backward Role	Backward Phrase
Partner Hierarchy	Organization (Parent)	Parent Of	Parents of Subsidiary - Partner	Organization (Child)	Subsidiary Of	Subsidiaries of - Partner
Distributor	Organization (Parent)	Customer Managed By	Customers Managed by Distributor	Organization (Child)	Manages	Distributors
Paying	Organization (Parent)	Pay To Of	Payees	Organization (Child)	Pay From Of	Payers
POM Default Approver	Person (Parent)	Default Approver For	Default Approvers for an Exchange Organization	Organization (Child)	Default Approver	Exchange Organizations with a Default Approver
POM Party Reference	Organization (Parent)	Party Referred By	Referred Exchange Entities	Organization (Child)	Referred Party	Exchange Entity Referrers
iSupplier Portal Address Sites	VENDOR_PARTY_SITE (Parent)	Address Of	Addresses	VENDOR_SITE (Child)	At Site	Supplier Sites
POS Employment	Organization (Parent)	Employer Of	Users of Procurement Application	Person (Child)	Employee Of	Organizations for Grouping Procurement Users
iSupplier Portal Supplier Contact	POS_CONTACT_PARTY (Parent)	Contact of Supplier	Supplier Contacts	VENDOR_PARTY (Child)	Supplier has Contact	Supplier with Contacts
iSupplier Portal Vendor Contact	VENDOR_PARTY_CONTACT (Parent)	Is Supplier Contact	Person Contacts	VENDOR_CONTACT (Child)	Is Contact	Supplier Person Contact

Relationship Type	Subject Type	Forward Role	Forward Phrase	Object Type	Backward Role	Backward Phrase
POS Supplier	Organization (Parent)	Party Of Vendor	Organizations for Grouping Supplier Employees	POS_VENDOR (Child)	Vendor Of Party	Suppliers with Organization for Grouping Users
Reference	Organization (Not Hierarchical)	Reference For	Organizations Providing References	Organization (Not Hierarchical)	Reference For	Organizations Providing References
Registered Company	Organization (Parent)	Registered Company Of	Registered Companies	Organization (Child)	Registered Company	Organizations with Registered Companies
Registered Approver	Person (Parent)	Registration Approver of	POM Registered Approvers	Person (Child)	Registration Approved By	Registered POM Approved People
Family Relation	Person (Not Hierarchical)	Relative Of	Relatives	Person (Not Hierarchical)	Relative Of	Relatives
Depot Repair	Organization (Parent)	Repair Depot Provider For	Repair Depot Providers	Organization (Child)	Repair Depot Provider	Organizations with Repair Depot Providers
Shipping	Organization (Parent)	Ship To Of	Shipping Sources	Organization (Child)	Ship From Of	Shipping Destinations
Sibling	Person (Not Hierarchical)	Sibling Of	Siblings	Person (Not Hierarchical)	Sibling Of	Siblings
Spousal	Person (Not Hierarchical)	Spouse Of	Spouses	Person (Not Hierarchical)	Spouse Of	Spouses
Stock Holder	Organization (Parent)	Stock Holder Of	Stockholders	Organization (Child)	Stock Held By	Organizations with Stockholders

Relationship Type	Subject Type	Forward Role	Forward Phrase	Object Type	Backward Role	Backward Phrase
Teaching	Person (Parent)	Student Of	Students	Person (Child)	Instructor Of	Instructors
Student/Institution	Person (Parent)	Attends Institution	Students Attending Institution	Organization (Child)	Has Student	Institutions Attended
Student Advising (Person)	Person (Parent)	Advisor Of	Student Advisees	Person (Child)	Advisee Of	Student Advisors
Student Advising (Organization)	Person (Parent)	Advisor At	Student Advisors at Organization	Organization (Child)	Has Advisor	Organizations with Student Advisors
Student Counseling (Person)	Person (Parent)	Counselor Of	Student Counselees	Person (Child)	Counselee Of	Student Counselors
Student Counseling (Organization)	Person (Parent)	Counselor At	Student Counselors at Organization	Organization (Child)	Has Counselor	Organizations with Student Counselors
Third Party Authorship	Organization (Parent)	Third Party Author For	Exchanges that own content managed by another Organization	Organization (Child)	Third Party Author	Exchanges that manage content owned by another Organization
Unregistered Company	Organization (Parent)	Unregistered Company Of	Unregistered Companies	Organization (Child)	Unregistered Company	Organizations with Unregistered Companies
VAD	Organization (Parent)	VAD Of	VADs	Organization (Child)	VAD Vendor Of	VAD Suppliers
VAR	Organization (Parent)	VAR Of	VARs	Organization (Child)	VAR Vendor Of	VAR Suppliers

Relationship Phrase and Role Pair Codes

This table lists the seeded relationship phrase and role pairs by code.

RELATIONSHIP_TY PE	FORWARD_REL_C ODE	FORWARD_ROLE_ CODE	BACKWARD_REL_ CODE	BACKWARD_ROLE
AFFILIATE	AFFILIATE_TO	ORGWITHAFFILIA TE	AFFILIATE	AFFILIATETOORG
AGREEMENT_SIGN ER	AGREEMENT_SIGN ER_OF	AGREEMENTSIGN ER	AGREEMENT_SIGN ER	ORGWITHAGREEM ENTSIGNER
APPLICANT_REFE REE	REFEREE	REFEREE	HAS_REFEREE	PERWITHREFEREE
APPROVING_MAN AGER	POM_APPROVING _MANAGER	POMAPPROVINGM ANAGER	POM_APPROVED_ BY	POMAPPROVEDPE R
ASSOCIATE	ASSOCIATE_OF	ASSOCIATE	ASSOCIATE_OF	ASSOCIATE
BANKING_GROUP	CONTAINS_MEMB ER	BANKINGGROUP	MEMBER_OF	BANKINGGROUP MEM
BANK_ACCOUNT_ CONTACT	CONTACT_OF	BANKACCOUNTC ONTACT	CONTACT	BANKACCOUNTW ITHCONTACT
BANK_AND_BRAN CH	HAS_BRANCH	BANKWITHBRANC H	BRANCH_OF	BANKBRANCH
BENEFICIARY	BENEFICIARY_OF	PERBENEFICIARY PER	BENEFACITOR_OF	PERBENEFACITOR PER
BENEFICIARY	BENEFICIARY_OF	ORGBENEFICIARY PER	BENEFACITOR_OF	PERBENEFACITOR ORG
BOARD_MEMBER	BOARD_MEMBER_ OF	BOARDMEMBER	CONTAINS_BOAR D_MEMBER	BOARD
BROKER	BROKER_OF	BROKER	BROKER	BROKERAGE
CAREGIVER	CAREGIVER_FOR	CAREGIVER	CARED_FOR	CAREDFORPATIEN T

RELATIONSHIP_TYPE	FORWARD_REL_CODE	FORWARD_ROLE_CODE	BACKWARD_REL_CODE	BACKWARD_ROLE_CODE
CLEARINGHOUSE_BANK	CLEARINGHOUSE_FOR	CLEARINGHOUSE	USES_CLEARINGHOUSE	BANKUSECLEARINGHOUSE
COMPETITOR	COMPETITOR_OF	COMPETITOR	COMPETITOR_OF	COMPETITOR
CONTACT	CONTACT_OF	CONTACTPER	CONTACT	PERWITHCONTACT
CONTACT	CONTACT_OF	CONTACTORG	CONTACT	ORGWITHCONTACT
CTB_ENTERPRISE_HIER	PARENT_OF	HEALTHCAREPARORG	CHILD_OF	HEALTHCARECHILDORG
CUSTOMER/SELLER	CUSTOMER_OF	PERCUSTOMER	SELLER_TO	SUPPLIERFORPER
CUSTOMER/SELLER	CUSTOMER_OF	ORGCUSTOMER	SELLER_TO	SUPPLIERFORORG
CUSTOMER_PREFERRED_SUPPLIER	PREFERRED_SUPPLIER_BY_CUSTOMER	PREFERRED_SUPPLIER	CUSTOMERS_PREFERRED_SUPPLIER	CUSTOMERWITHPREFSUPPLIER
DEFAULT_ADMIN	POM_DEFAULT_ADMIN_FOR	POMDEFAULTADMIN	POM_DEFAULT_ADMIN_BY	ORGWITHPOMDEFAULTADMIN
DEPENDENT	DEPENDENT_OF	GUARDIAN	GUARDIAN_OF	DEPENDANT
DNB_HIERARCHY	HEADQUARTERS_OF	DNB_HEADQUARTER	DIVISION_OF	DNB_DIVISION
DNB_HIERARCHY	DOMESTIC_ULTIMATE_OF	DNB_DOMESTICULTIMATE	DOMESTIC_SUBSIDIARY_OF	DNB_DOMESTICSUBSIDIARY
DNB_HIERARCHY	PARENT_OF	DNB_PARENT	SUBSIDIARY_OF	DNB_SUBSIDIARY
DNB_HIERARCHY	GLOBAL_ULTIMATE_OF	DNB_GLOBALULTIMATE	GLOBAL_SUBSIDIARY_OF	DNB_GLOBALSUBSIDIARY

RELATIONSHIP_TY PE	FORWARD_REL_C ODE	FORWARD_ROLE_ CODE	BACKWARD_REL_ CODE	BACKWARD_ROLE
DOMESTIC_PARTN ER	DOMESTIC_PARTN ER_OF	DOMESTICPARTN ER	DOMESTIC_PARTN ER_OF	DOMESTICPARTN ER
DOMESTIC_ULTIM ATE	DOMESTIC_ULTIM ATE_OF	DOMESTICULTIMA TE	DOMESTIC_SUBSID IARY_OF	DOMESTICSUBSID ARY
DOWNLOAD_CON TENT	POM_DOWNLOAD _ITEM_PRIVILEGE_ TO	ORGTHATDOWNL OAD	POM_DOWNLOAD _ITEM_FROM	ORGPROVIDEDOW NLOAD
EMERGENCY_CON TACT	EMERGENCY_CON TACT_FOR	EMERGENCY_CON TACT	EMERGENCY_CON TACT_OF	HAS_EMERGENCY _CONTACTS
EMPLOYMENT	EMPLOYEE_OF	EMPLOYEE	EMPLOYER_OF	EMPLOYER
GLOBAL_ULTIMAT E	GLOBAL_ULTIMAT E_OF	GLOBALULTIMAT E	GLOBAL_SUBSIDIA RY_OF	GLOBALSUBSIDIA RY
GUARANTOR	GUARANTOR_FOR	ORGGUARANTOR ORG	GUARANTOR	ORGWITHORGGU ARANTOR
GUARANTOR	GUARANTOR_FOR	ORGGUARANTOR	GUARANTOR	PERWITHORGGUA R
GUARANTOR	GUARANTOR_FOR	GUARANTOR	GUARANTOR	PERWITHGUARAN TOR
HEADQUARTERS/ DIVISION	HEADQUARTERS_ OF	HEADQUARTER	DIVISION_OF	DIVISION
INST_ACCREDITAT ION	ACCREDITED_BY	ACCREDITEDORG	ACCREDITS	ACCREDITINGORG
INVENTORY_ORG	INVENTORY_ORG_ OF	INVENTORYORG	INVENTORY_ORG	ORGWITHINVENT ORYORG
KEY_COMPANY	KEY_COMPANY_O F	KEYCOMPANY	KEY_COMPANY	ORGWITHKEYCO MPANY
LEGAL_CONTACT	POM_LEGAL_CON TACT_FOR	POMLEGALCONT ACT	POM_LEGAL_CON TACT	POMORGWITHLEG ALCONTACT

RELATIONSHIP_TY PE	FORWARD_REL_C ODE	FORWARD_ROLE_ CODE	BACKWARD_REL_ CODE	BACKWARD_ROLE
LE_AND_BANK	USES_BANK	LEUSEBANK	BANK_USED_BY	BANKUSEBYLE
MANAGER	REPORTS_TO	MANAGEMENTRE PORT	MANAGER_OF	MANAGER
MEMBERSHIP	MEMBER_OF	SUBGROUP	CONTAINS_MEMB ER	GROUPWITHSUBG ROUP
MEMBERSHIP	MEMBER_OF	MEMBEROFGROUP	CONTAINS_MEMB ER	ORGGROUP
MEMBERSHIP	MEMBER_OF	MEMBER	CONTAINS_MEMB ER	GROUP
MODELED_BY	MODELED_BY	MODELINGCOMP ANY	MODELED_COMP ANY	MODELEDCOMPAN Y
NEXT_OF_KIN	NEXT_OF_KIN_FO R	NEXT_OF_KIN	NEXT_OF_KIN_OF	KINFOLK
OU_AND_BANK	USES_BANK	OUUSEBANK	BANK_USED_BY	BANKUSEBYOU
PARENT/CHILD	PARENT_OF	PARENT	CHILD_OF	CHILD
PARENT/SUBSIDIA RY	PARENT_OF	PARENTOFSUB	SUBSIDIARY_OF	SUBSIDIARYOFPAR ENT
PARTNER	PARTNER_OF	PARTNER	PARTNER_OF	PARTNER
PARTNER_HIERAR CHY	PARENT_OF	PARTNER_PARENT _OF	SUBSIDIARY_OF	PARTNER_SUBSIDI ARY_OF
PARTNER_MANAG ED_CUSTOMER	CUSTOMER_INDIR ECTLY_MANAGED _BY	CUSTINDIRMANA GEDPART	INDIRECTLY_MAN AGES_CUSTOMER	PARTNERINDIREC TMANAGEDCUST
PAYTO	PAYTO_OF	PAYEE	PAYFROM_OF	PAYER
POM_DEFAULT_A PPROVER	POM_DEFAULT_A PPROVER_FOR	POMDEFAULTAPP ROVER	POM_DEFAULT_A PPROVER	POMAPPROVEDOR G

RELATIONSHIP_TY PE	FORWARD_REL_C ODE	FORWARD_ROLE_ CODE	BACKWARD_REL_ CODE	BACKWARD_ROLE
POM_PARTY_REFE RENCE	POM_PARTY_REFE RRED_BY	POMREFERRER	POM_REFERRED_P ARTY	POMREFEREE
POS_ADDRESS_SIT ES	ADDRESS_OF_SITE	ADDRESS	SITE_ADDRESS	SUPPLIER_SITE
POS_EMPLOYMEN T	EMPLOYER_OF	POSEMPLOYEE	EMPLOYEE_OF	POSEMPLOYER
POS_SUPPLIER_CO NTACT	CONTACT_OF_SUP PLIER	CONTACT_OF_SUP PLIER	SUPPLIER_CONTA CT	SUPPLIER_CONTA CT
POS_VENDOR_CO NTACT	PARTY_OF_CONTA CT	PARTY_OF_CONTA CT	CONTACT_OF_PA RTY	CONTACT_OF_PA RTY
POS_VENDOR_PAR TY	PARTY_OF_VENDO R	POSORGWITHSUP PLIER	VENDOR_OF_PART Y	POSSUPPLIER
REFERENCE	REFERENCE_FOR	REFERENCE	REFERENCE_FOR	REFERENCE
REGISTERED_COM PANY	REGISTERED_COM PANY_OF	REGISTEREDCOMP	REGISTERED_COM PANY	ORGWITHREGISTE REDCOMPANY
REG_APPROVER	POM_REG_APPRO VER_OF	POMREGAPPROVE R	POM_REG_APPRO VED_BY	REGISTEREDPOMA PPER
RELATIVE	RELATIVE_OF	RELATIVE	RELATIVE_OF	RELATIVE
REPAIR_DEPOT_PR OVIDER	REPAIR_DEPOT_PR OVIDER_FOR	REPAIRDEPOTPRO VIDER	REPAIR_DEPOT_PR OVIDER	ORGIWTHREPAIR DEPOTPROV
SHIPTO	SHIPTO_OF	SHIPPINGSOURCE	SHIPFROM_OF	SHIPPINGDEST
SIBLING	SIBLING_OF	SIBLING	SIBLING_OF	SIBLING
SPOUSE	SPOUSE_OF	SPOUSE	SPOUSE_OF	SPOUSE
STOCK_HOLDER	STOCK_HOLDER_ OF	ORGSTOCKHOLDE R	STOCK_HOLDER	ORGWITHORGSTO CKHOLDER

RELATIONSHIP_TY PE	FORWARD_REL_C ODE	FORWARD_ROLE_ CODE	BACKWARD_REL_ CODE	BACKWARD_ROLE_ CODE
STUDENT/INSTRU CTOR	STUDENT_OF	STUDENT	INSTRUCTOR_OF	INSTRUCTOR
STUDENTINSTITUT ION	ATTENDS_INSTITU TION	STUDENTATTENDI NG	HAS_STUDENT	INSTITUTIONATTE NDING
STUDENT_ADVISI NG	ADVISOR_OF	STUDENTADVISEE	ADVISEE_OF	STUDENTADVISOR
STUDENT_ADVISI NG_AT	ADVISOR_AT	STUDENTADVISOR ORG	HAS_ADVISOR	ORGWITHSTUDEN TADVISOR
STUDENT_COUNS ELING	COUNSELOR_OF	STUDENTCOUNSE LEE	COUNSELEE_OF	STUDENTCOUNSE LOR
STUDENT_COUNS ELING_AT	COUNSELOR_AT	STUDENTCOUNSE LEEORG	HAS_COUNSELOR	ORGWITHSTUDEN TCOUNSELOR
THIRD_PARTY_AU THOR	POM_THIRDPARTY _AUTHOR_FOR	POMTHIRDPARTY AUTHOR	POM_THIRDPARTY _AUTHOR	POMORGWITHTHI RDPARTYAUTHOR
UNREGISTERED_C OMPANY	UNREGISTERED_C OMPANY_OF	UNREGISTEREDCO MP	UNREGISTERED_C OMPANY	ORGWITHUNREGI STEREDCOMP
VAD	VAD_OF	VAD	VAD_VENDOR_OF	VADSUPPLIER
VAR	VAR_OF	VAR	VAR_VENDOR_OF	VARSUPPLIER

Seeded Word Replacement Lists

This chapter covers the following topics:

- Seeded Word Replacement Lists
- ADDRESS_DICTIONARY
- DOMAIN_NAME_DICTIONARY
- EXPANDED_PERSON_NAME_DICTIONARY
- KEY MODIFIERS
- ORGANIZATION_NAME_DICTIONARY
- PERSON_NAME_DICTIONARY
- US_STATE_DICTIONARY

Seeded Word Replacement Lists

These seeded word replacement lists are available for Data Quality Management.

- ADDRESS_DICTIONARY, page 5-2
- DOMAIN_NAME_DICTIONARY, page 5-20
- EXPANDED_PERSON_NAME_DICTIONARY, page 5-21
- KEY MODIFIERS, page 5-153
- ORGANIZATION_NAME_DICTIONARY, page 5-156
- PERSON_NAME_DICTIONARY, page 5-159
- US_STATE_DICTIONARY, page 5-202

All of these lists are in American English.

Related Topics

Word Replacements, *Oracle Trading Community Architecture Administration Guide*

ADDRESS_DICTIONARY

This table lists the original and replacement words of the ADDRESS_DICTIONARY word replacement list.

ORIGINAL_WORD	REPLACEMENT_WORD
ALLEE	ALY
ALLEY	ALY
ANEX	ANX
ANNEX	ANX
ANNX	ANX
ARCADE	ARC
AV	AVE
AVEN	AVE
AVENU	AVE
AVENUE	AVE
AVN	AVE
BAYOO	BYU
BAYOU	BYU
BEACH	BCH
BEND	BND
BLUF	BLF

ORIGINAL_WORD	REPLACEMENT_WORD
BLUFF	BLF
BLUFFS	BLF
BOT	BTM
BOTTM	BTM
BOTTOM	BTM
BOUL	BLVD
BOULEVARD	BLVD
BOULV	BLVD
BOX	PO
BRANCH	BR
BRDGE	BRG
BRIDGE	BRG
BROOK	BRK
BROOKS	BRK
BUILDING	BLDG
BURGS	BG
BYPA	BYP
BYPAS	BYP
BYPASS	BYP
BYPS	BYP

ORIGINAL_WORD	REPLACEMENT_WORD
CAMP	CMP
CANYN	CYN
CANYON	CYN
CAPE	CPE
CAUSEWAY	CSWY
CAUSWAY	CSWY
CENT	CTR
CENTER	CTR
CENTERS	CTR
CENTR	CTR
CIRC	CIR
CIRCL	CIR
CIRCLE	CIR
CIRCLES	CIR
CLF	CLFS
CLIFF	CLFS
CLIFFS	CLFS
CLUB	CLB
CNTER	CTR
CNTR	CTR

ORIGINAL_WORD	REPLACEMENT_WORD
CNYN	CYN
CORNER	COR
CORNERS	COR
COURSE	CRSE
COURT	CT
COURTS	CT
COVE	CV
COVES	CV
CP	CMP
CRCL	CIR
CRCLE	CIR
CRECENT	CRES
CREEK	CRK
CRESCENT	CRES
CRESENT	CRES
CROSSING	XING
CRSCNT	CRES
CRSENT	CRES
CRSNT	CRES
DALE	DL

ORIGINAL_WORD	REPLACEMENT_WORD
DRES	CRES
DRIV	DR
DRIVE	DR
DRIVES	DR
DRV	DR
EAST	EA
EIGHT	8
EIGHTH	8TH
ESTATE	EST
ESTS	EST
EXP	EXPY
EXPRESS	EXPY
EXPRESSWAY	EXPY
EXPW	EXPY
EXTENSION	EXT
EXTN	EXT
EXTNSN	EXT
EXTS	EXT
FALLS	FALL
FERRY	FRY

ORIGINAL_WORD	REPLACEMENT_WORD
FIELD	FLD
FIELDS	FLD
FIFTH	5TH
FIRST	1ST
FIVE	5
FLAT	FLT
FLATS	FLT
FLDS	FLD
FLTS	FLT
FORD	FRD
FORDS	FRD
FORESTS	FRST
FORG	FRG
FORGE	FRG
FORK	FRK
FORKS	FRK
FORT	FT
FOUR	4
FOURTH	4TH
FREEWAY	FWY

ORIGINAL_WORD	REPLACEMENT_WORD
FREEWY	FWY
FRRY	FRY
FRT	FT
FRWAY	FWY
FRWY	FWY
GARDEN	GDNS
GARDENS	GDNS
GARDN	GDNS
GATEWAY	GTWY
GATEWY	GTWY
GATWAY	GTWY
GDN	GDNS
GLEN	GLN
GLENS	GLN
GRDEN	GDNS
GRDNS	GDNS
GREEN	GRN
GREENS	GRN
GROV	GRV
GROVE	GRV

ORIGINAL_WORD	REPLACEMENT_WORD
GTWAY	GTWY
HARB	HBR
HARBOR	HBR
HARBORS	HBR
HARBR	HBR
HAVEN	HVN
HAVN	HVN
HEIGHT	HTS
HEIGHTS	HTS
HIGHWAY	HWY
HIGHWY	HWY
HILL	HL
HILLS	HL
HIWAY	HWY
HIWY	HWY
HLLW	HOLW
HOLLOW	HOLW
HOLWS	HOLW
HRBOR	HBR
HT	HTS

ORIGINAL_WORD	REPLACEMENT_WORD
HWAY	HWY
INLWT	INLT
ISLAND	ISS
ISLANDS	ISS
ISLND	ISS
ISLND	ISS
ISLND	ISS
JCTION	JCT
JCTN	JCT
JCTNS	JCT
JCTS	JCT
JUNCTION	JCT
JUNCTN	JCT
JUNCTON	JCT
KEY	KY
KEYS	KY
KNL	KNLS
KNOL	KNLS
KNOLL	KNLS
KNOLLS	KNLS
KYS	KY

ORIGINAL_WORD	REPLACEMENT_WORD
LAKE	LKS
LAKES	LKS
LANDING	LNDG
LANE	LN
LANES	LN
LCK	LCKS
LDGE	LDG
LIGHT	LGT
LNDNG	LNDG
LOAF	LF
LOCK	LCKS
LOCKS	LCKS
LODG	LDG
LODGE	LDG
LOOPS	LOOP
MANOR	MNR
MANORS	MNR
MDW	MDWS
MEADOW	MDWS
MEADOWS	MDWS

ORIGINAL_WORD	REPLACEMENT_WORD
MILLS	MLS
MISSION	MSN
MISSN	MSN
MNRS	MNR
MNTAIN	MTN
MNTN	MTN
MNTNS	MTN
MOUNT	MTN
MOUNTAIN	MTN
MOUNTIN	MTN
MSSN	MSN
MTIN	MTN
NECK	NCK
NINE	9
NINETHA	9TH
NORTH	NO
NORTHEAST	NE
NORTHWEST	NW
ONE	1
ORCHARD	ORCH

ORIGINAL_WORD	REPLACEMENT_WORD
ORCHRD	ORCH
OVL	OVAL
PARKS	PARK
PARKWAY	PKY
PARKWY	PKY
PATHS	PATH
PIKES	PIKE
PINE	PNE
PINES	PNE
PKWAY	PKY
PKWY	PKY
PKWYS	PKY
PLACE	PL
PLAIN	PLNS
PLAINES	PLNS
PLAZA	PLZ
PLN	PLNS
PLZA	PLZ
PNES	PNE
POB	PO

ORIGINAL_WORD	REPLACEMENT_WORD
POBOX	PO
POINT	PT
POINTS	PT
PORT	PRT
PORTS	PRT
PRAIRIE	PR
PRK	PARK
PRR	PR
PRTS	PRT
PTS	PT
RAD	RADL
RADIAL	RADL
RADIEL	RADL
RANCH	RNCH
RANCHES	RNCH
RAPID	RPDS
RAPIDS	PRDS
RDGE	RDG
RDGS	RDG
RDS	RD

ORIGINAL_WORD	REPLACEMENT_WORD
REST	RST
RIDGE	RDG
RIDGES	RDG
RIVER	RIV
RIVERS	RIV
RIVR	RIV
RNCHS	RNCH
ROAD	RD
ROADS	RD
RVR	RIV
SECOND	2ND
SEVEN	7
SEVENTH	7TH
SHL	SHLS
SHOAL	SHLS
SHOALS	SHLS
SHOAR	SHRS
SHOARS	SHRS
SHORE	SHRS
SHORES	SHRS

ORIGINAL_WORD	REPLACEMENT_WORD
SHR	SHRS
SIX	6
SIXTH	6TH
SOUTH	SO
SOUTHEAST	SE
SOUTHWEST	SW
SPG	SPGS
SPNG	SPGS
SPNGS	SPGS
SPURS	SPUR
SQR	SQ
SQRE	SQ
SQU	SQ
SQUARE	SQ
SQUARES	SQ
STATION	STA
STATIONS	STA
STATN	STA
STN	STA
STR	ST

ORIGINAL_WORD	REPLACEMENT_WORD
STRAV	STRA
STRAVE	STRA
STRAVEN	STRA
STRAVENUE	STRA
STRAVN	STRA
STREAM	STRM
STREET	ST
STREETS	ST
STREME	STRM
STRT	ST
STRVN	STRA
STRVNUE	STRA
SUMIT	SMT
SUMITT	SMT
SUMMIT	SMT
TEN	10
TERR	TER
TERRACE	TER
THREE	3
TPK	TPKE

ORIGINAL_WORD	REPLACEMENT_WORD
TRACE	TRCE
TRACES	TRCE
TRACK	TRAK
TRAFFICWAY	TRFY
TRAIL	TRL
TRAILER	TRLR
TRAILS	TRL
TRAKCS	TRAK
TRIRD	3RD
TRK	TRAK
TRKS	TRAK
TRLRS	TRLR
TRLS	TRL
TRNPK	TPKE
TUNEL	TUNL
TUNLS	TUNL
TUNNEL	TUNL
TUNNL	TUNL
TURNPIKE	TPKE
TURNPK	TPKE

ORIGINAL_WORD	REPLACEMENT_WORD
TWO	2
UNION	UN
UNIONS	UN
VALLEY	VLY
VALLEYS	VLY
VALLY	VLY
VIAALGE	VLG
VIADCT	VIA
VIADUCT	VIA
VIEW	VW
VIEWS	VW
VILL	VLG
VILLAG	VLG
VILLE	VL
VILLG	VLG
VILLIAGE	VLG
VIST	VIS
VISTA	VIS
VLGS	VLG
VLLY	VLY

ORIGINAL_WORD	REPLACEMENT_WORD
VLYS	VLV
VST	VLV
VSTA	VIS
VWS	VW
WALKS	WALK
WAYS	WAY
WELL	WLS
WELLS	WLS
WEST	W
WY	WAY

DOMAIN_NAME_DICTIONARY

This table lists the original and replacement words of the DOMAIN_NAME_DICTIONARY word replacement list. The list is used for e-mail addresses and URLs. The replacement words are intentionally blank so that the returned values will be more fuzzy.

Original Word	Replacement Word
AU	
CN	
CO	
COM	
EDU	

Original Word	Replacement Word
FR	
GOV	
HTM	
HTML	
IN	
JP	
NET	
ORG	
TV	
UK	
WWW	

EXPANDED_PERSON_NAME_DICTIONARY

This table lists the original and replacement words of the EXPANDED_PERSON_NAME_DICTIONARY word replacement list in alphabetical order from A to F.

ORIGINAL_WORD	REPLACEMENT_WORD
AB	ABNER
ABBEY	ABIGAIL
ABBIE	ABIGAIL
ABBOTT	ABBOT

ORIGINAL_WORD	REPLACEMENT_WORD
ABBY	ABIGAIL
ABE	ABRAHAM
ABIE	ABRAHAM
ABRAM	ABRAHAM
AD	ADAM
ADA	ADELAIDE
ADABEL	ADABELLE
ADALARD	ALBERT
ADALBERT	ALBERT
ADALIA	ADELAIDE
ADALINE	ADELAIDE
ADAMS	ADAM
ADAMSON	ADAM
ADDIE	ADELAIDE
ADDY	ADELAIDE
ADELA	ADELAIDE
ADELARD	ALBERT
ADELE	ADELAIDE
ADELIA	ADELAIDE
ADELINA	ADELAIDE

ORIGINAL_WORD	REPLACEMENT_WORD
ADELIND	ADELAIDE
ADELINE	ADELAIDE
ADELLA	ADELAIDE
ADEN	ADIN
ADENA	ADINE
ADIELL	ADIEL
ADILA	ADELAIDE
ADINA	ADINE
ADNAH	ADNA
ADOLF	ADOLPH
ADOLPHE	ADOLPH
ADOLPHUS	ADOLPH
ADRIA	ADRIENNE
ADRIANA	ADRIENNE
ADRIANNA	ADRIENNE
ADRIANNE	ADRIENNE
ADRIEN	ADRIAN
AG	AGATHA
AGATHE	AGATHA
AGATHY	AGATHA

ORIGINAL_WORD	REPLACEMENT_WORD
AGGIE	AGATHA
AGGY	AGATHA
AGNA	AGNES
AGNELLA	AGNES
AGNETA	AGNES
AIDA	ADELAIDE
AIMEE	AMY
AKSEL	AVERILL
AL	ALBERT
ALAIN	ALAN
ALAINE	ELAINE
ALARICK	ALARIC
ALASTAIR	ALEX
ALAYNE	ELAINE
ALBEN	ALBAN
ALBERTA	ALBERT
ALBERTINA	ALBERT
ALBERTINE	ALBERT
ALBIN	ALBAN
ALBION	AUBIN

ORIGINAL_WORD	REPLACEMENT_WORD
ALBRECHT	ALBERT
ALCOT	ALCOTT
ALDA	ALDIS
ALDAS	ALDIS
ALDIN	ALDEN
ALDOUS	ALDIS
ALDUS	ALDIS
ALDWIN	ALDEN
ALDYA	ALDIS
ALEC	ALEX
ALECK	ALEX
ALEDA	ALIDA
ALEECE	ALICE
ALENE	AILEEN
ALETA	ALETHEA
ALEXA	ALEX
ALEXANDER	ALEX
ALEXANDRA	ALEX
ALEXIS	ALEX
ALF	ALFRED

ORIGINAL_WORD	REPLACEMENT_WORD
ALFIE	ALFRED
ALFONSO	ALPHONSE
ALFREDA	FREDA
ALFY	ALFRED
ALGAR	ALGER
ALGIE	ALGERNON
ALICIA	ALICE
ALICK	ALEX
ALINA	ALANA
ALINE	AILEEN
ALIS	ALICE
ALISA	ALICE
ALISON	ALICE
ALISSA	ALICE
ALITTA	ALETHEA
ALIX	ALEX
ALLA	ALEX
ALLAN	ALAN
ALLANA	ALANA
ALLEN	ALAN

ORIGINAL_WORD	REPLACEMENT_WORD
ALLIE	ALICE
ALLIS	ALICE
ALLISTER	ALEX
ALLY	ALICE
ALOISIA	ALOYSIA
ALOYSE	ALOYSIA
ALOYSIUS	LEWIS
ALPHONSO	ALPHONSE
ALRISE	ALARICE
ALTHEE	ALTHEA
ALTHETA	ALTHEA
ALVA	ALBAN
ALVAN	ALVIN
ALWIN	ALVIN
ALWYN	ALVIN
ALYCE	ALICE
ALYDA	ALIDA
ALYS	ALICE
ALYSIA	ALICE
ALYSSA	ALICE

ORIGINAL_WORD	REPLACEMENT_WORD
AMALIA	AMELIA
AMARY	AMORY
AMELIE	AMELIA
AMERY	AMORY
AMI	AMY
AMIE	AMY
ANA	STACY
ANABEL	ANN
ANABELLA	ANN
ANABELLE	ANN
ANASTAS	STACY
ANASTASIA	STACY
ANASTASIUS	STACY
ANASTATIA	STACY
ANASTATIUS	STACY
ANATOL	ANATOLE
ANDEE	ANDREA
ANDERS	ANDREW
ANDERSON	ANDERSEN
ANDERSSON	ANDERSEN

ORIGINAL_WORD	REPLACEMENT_WORD
ANDI	ANDREA
ANDRE	ANDREW
ANDREANA	ANDREA
ANDREAS	ANDREW
ANDRIEN	ANDREW
ANDY	ANDREW
ANGEL	ANGELA
ANGELICA	ANGELA
ANGELINA	ANGELA
ANGELINE	ANGELA
ANGELITA	ANGELA
ANGIE	ANGELA
ANGY	ANGELA
ANITA	ANN
ANNA	ANN
ANNE	ANN
ANNETTA	ANN
ANNETTE	ANN
ANNIE	ANN
ANNORA	ANN

ORIGINAL_WORD	REPLACEMENT_WORD
ANSEL	ANSELM
ANTHIA	ANTHEA
ANTOINE	ANTHONY
ANTOINETTA	ANTONIA
ANTOINETTE	ANTONIA
ANTON	ANTHONY
ANTONI	ANTHONY
ANTONINA	ANTONIA
ANTONIO	ANTHONY
ANTONY	ANTHONY
ANYA	ANN
ARA	ARABELLA
ARABELLE	ARABELLA
ARCH	ARCHIBALD
ARCHER	ARCHIBALD
ARCHIE	ARCHIBALD
ARCHY	ARCHIBALD
ARDELIA	ARDIS
ARDELIS	ARDIS
ARDELLA	ARDIS

ORIGINAL_WORD	REPLACEMENT_WORD
ARDELLE	ARDIS
ARDENE	ARDIS
ARDINE	ARDIS
ARDRA	ARDIS
ARIANA	ARIADNE
ARIANE	ARIADNE
ARLANA	ARLENE
ARLEEN	ARLENE
ARLENA	ARLENE
ARLETTE	ARLENE
ARLEY	HARLEY
ARLIE	HARLEY
ARLINA	ARLENE
ARLINE	ARLENE
ARMAND	HERMAN
ARMIN	HERMAN
ARMINE	ARMINA
ARMOND	HERMAN
ARMYN	HERMAN
ARNE	ARNOLD

ORIGINAL_WORD	REPLACEMENT_WORD
ARNIE	ARNOLD
ARNO	ARNOLD
ARON	AARON
ART	ARTHUR
ARTIE	ARTHUR
ARTURO	ARTHUR
ARV	ARVIN
ARVIE	ARVIN
ARVY	ARVIN
ASTREA	ASTRA
ASTRED	ASTRA
ASTRID	ASTRA
ATHENE	ATHENA
AUDIE	AUDREY
AUDRIE	AUDREY
AUDRY	AUDREY
AUGIE	GUS
AUGUST	GUS
AUGUSTA	GUS
AUGUSTIN	GUS

ORIGINAL_WORD	REPLACEMENT_WORD
AUGUSTINA	GUS
AUGUSTINE	GUS
AUGUSTUS	GUS
AURA	AURELIA
AUREA	AURELIA
AUREL	AURELIA
AURELIE	AURELIA
AURICK	WARRICK
AURIE	AURELIA
AURORA	AURELIA
AUSTEN	GUS
AUSTIN	GUS
AUSTINE	GUS
AV	AVERILL
AVA	AVIS
AVERIL	AVERILL
AVI	AVIS
AVRAM	ABRAHAM
AXEL	AVERILL
AYLMER	ELMER

ORIGINAL_WORD	REPLACEMENT_WORD
AZALEA	AZALIA
AZELIA	AZALIA
BABBY	BARBARA
BABETTE	BARBARA
BABS	BARBARA
BARBETTE	BARBARA
BARBY	BARBARA
BARD	BAIRD
BARDEN	BORDEN
BARDO	BARTHOLOMEW
BARNABAS	BARNABY
BARNARD	BERNIE
BARNET	BERNIE
BARNETT	BERNIE
BARNEY	BERNIE
BARRETT	BARRET
BARRIE	BARUCH
BARRON	BARON
BARRY	BARUCH
BART	BARTHOLOMEW

ORIGINAL_WORD	REPLACEMENT_WORD
BARTH	BARTHOLOMEW
BARTHOL	BARTHOLOMEW
BARTHOLEMEW	BARTHOLOMEW
BARTHOLEMY	BARTHOLOMEW
BARTLETT	BARTHOLOMEW
BARTLEY	BARTHOLOMEW
BARTRAM	BERTRAM
BAT	BARTHOLOMEW
BAX	BAXTER
BAYNARD	BERNIE
BEA	BEATRICE
BEAUTRIX	BEATRICE
BECKY	REBECCA
BEE	BEATRICE
BEL	LINDA
BELINDA	LINDA
BELL	MIRABEL
BELLE	ISABEL
BEN	BENJAMIN
BENAY	BENA

ORIGINAL_WORD	REPLACEMENT_WORD
BENEDETTA	BENEDICTA
BENEDIC	BENEDICT
BENEDICK	BENEDICT
BENEDIX	BENEDICT
BENETTA	BENEDICTA
BENITA	BENEDICTA
BENJIE	BENJAMIN
BENJY	BENJAMIN
BENNET	BENEDICT
BENNETT	BENEDICT
BENNIE	BENJAMIN
BENNY	BENJAMIN
BENSON	BENJAMIN
BERENICE	BERNIE
BERG	BURGESS
BERGER	BURGESS
BERGESS	BURGESS
BERN	BERNIE
BERNADETTE	BERNADINE
BERNARD	BERNIE

ORIGINAL_WORD	REPLACEMENT_WORD
BERNARR	BERNIE
BERNETA	BERNADINE
BERNETTA	BERNADINE
BERNETTE	BERNADINE
BERNHARD	BERNIE
BERNI	BERNIE
BERNIA	BERNADINE
BERNICE	BERNIE
BERNY	BERNIE
BERRI	BERYL
BERRIE	BERYL
BERRY	BERYL
BERT	ALBERT
BERTA	BERTHA
BERTI	BERTHA
BERTIE	ALBERT
BERTINA	BERTHA
BERTON	BURTON
BERTRAND	BERTRAM
BERTY	OSBERT

ORIGINAL_WORD	REPLACEMENT_WORD
BERYLE	BERYL
BESS	ELIZABETH
BESSE	ELIZABETH
BESSIE	ELIZABETH
BETH	ELIZABETH
BETSY	ELIZABETH
BETTE	ELIZABETH
BETTI	ELIZABETH
BETTINA	ELIZABETH
BETTY	ELIZABETH
BEV	BEVERLY
BEVERLEY	BEVERLY
BEVERLIE	BEVERLY
BEVIN	BEVAN
BEVVY	BEVERLY
BIANCA	BLANCHE
BILL	WILLIAM
BILLE	WILLIAM
BILLIE	WILLIAM
BILLY	WILLIAM

ORIGINAL_WORD	REPLACEMENT_WORD
BINA	SABINA
BLAISE	BLAZE
BLANCA	BLANCHE
BLANCH	BLANCHE
BLANE	BLAINE
BLASE	BLAZE
BLAYNE	BLAINE
BLISS	BLYTHE
BLISSE	BLYTHE
BLUMA	ANTHEA
BOB	ROBERT
BOBBE	ROBERTA
BOBBI	ROBERTA
BOBBIE	ROBERT
BOBBY	ROBERT
BONI	BONNIE
BONNE	BONNIE
BONNI	BONNIE
BONNY	BONNIE
BRAM	ABRAHAM

ORIGINAL_WORD	REPLACEMENT_WORD
BRANCA	BLANCHE
BRANDON	BRENDAN
BREE	AUBREY
BREN	BRENDA
BRENDEN	BRENDAN
BRENDON	BRENDAN
BRENNAN	BRENDAN
BRET	BRETT
BREY	AUBREY
BRIDGID	BRIDGET
BRIE	BRIDGET
BRIETA	BRIDGET
BRIETTA	BRIDGET
BRIGETTE	BRIDGET
BRIGIDA	BRIDGET
BRIGITTE	BRIDGET
BRINA	SABRINA
BRITA	BRIDGET
BRODERICK	ROD
BROM	BROMLEY

ORIGINAL_WORD	REPLACEMENT_WORD
BROMLEA	BROMLEY
BROMLEIGH	BROMLEY
BRUNHILD	BRUNHILDE
BRUNHILDA	BRUNHILDE
BRYAN	BRIAN
BRYANT	BRIAN
BRYCE	BRICE
BUD	BUDD
BUDDY	BUDD
BURG	BURGESS
BURT	BURTON
CAL	CALVIN
CALVERT	CALVIN
CAM	CAMILLA
CAMELLA	CAMILLA
CAMELLIA	CAMILLA
CAMILLE	CAMILLA
CAMM	CAMERON
CAMPBALL	CAMPBELL
CANDICE	CANDACE

ORIGINAL_WORD	REPLACEMENT_WORD
CANDIDA	CANDACE
CANDIE	CANDACE
CANDY	CANDACE
CAREY	CAROL
CARISSA	CHARISSA
CARL	CHARLES
CARLETON	CHARLTON
CARLO	CHARLES
CARLOS	CHARLES
CARLOTTA	CHARLOTTE
CARLTON	CHARLTON
CARLY	CARLA
CARMELA	CARMEL
CARMELITA	CARMEL
CARMENA	CARMEN
CARMINA	CARMEN
CARMINE	CARMEN
CARMITA	CARMEN
CAROLA	CAROL
CAROLE	CAROL

ORIGINAL_WORD	REPLACEMENT_WORD
CAROLINA	CAROL
CAROLINE	CAROL
CAROLLE	CAROL
CAROLYN	CAROL
CARR	CAREW
CARRIE	CAROL
CARROL	CHARLES
CARRY	CHARLOTTE
CARY	CAROL
CARYL	CAROL
CASPER	JASPER
CASS	CASSANDRA
CASSANDRE	CASSANDRA
CASSIE	CASSANDRA
CASSY	CASIMIR
CATHARINE	KATHERINE
CATHERINA	KATHERINE
CATHERINE	KATHERINE
CATHLEEN	KATHERINE
CECILE	CECILIA

ORIGINAL_WORD	REPLACEMENT_WORD
CECILY	CECILIA
CELESTA	CELESTE
CELESTINE	CELESTE
CELIA	CECILIA
CEPORAH	ZIPPORAH
CHAD	CHADWICK
CHAN	CHANDLER
CHANCELLOR	CHAUNCEY
CHANCELOR	CHAUNCEY
CHAPEN	CHAPIN
CHAPLAND	CHAPIN
CHAPLIN	CHAPIN
CHARITA	CHARITY
CHARLENE	CHARLOTTE
CHARLETON	CHARLTON
CHARLEY	CHARLES
CHARLIE	CHARLES
CHARLINE	CHARLOTTE
CHARMAIN	CHARMINE
CHARRY	CHARITY

ORIGINAL_WORD	REPLACEMENT_WORD
CHAS	CHARLES
CHELTON	CHILTON
CHERRY	CHARITY
CHERYL	CHERIE
CHESTON	CHESTER
CHET	CHESTER
CHRISSIE	CHRIS
CHRISSY	CHRIS
CHRISTA	CHRIS
CHRISTABEL	CHRIS
CHRISTABELLE	CHRIS
CHRISTAL	CHRIS
CHRISTIAN	CHRIS
CHRISTIANA	CHRIS
CHRISTIE	CHRIS
CHRISTINA	CHRIS
CHRISTINE	CHRIS
CHRISTOPHER	CHRIS
CHRISTY	CHRIS
CHRYSTAL	CHRIS

ORIGINAL_WORD	REPLACEMENT_WORD
CHUCK	CHARLES
CICILY	CECILIA
CINDY	CYNTHIA
CIS	CECILIA
CISSY	CECILIA
CLAIRE	CLAIR
CLARA	CLAIR
CLARABELLE	CLAIR
CLARE	CLAIR
CLARENCE	CLAIR
CLARETA	CLAIR
CLARETTE	CLAIR
CLARI	CLAIR
CLARIBEL	CLAIR
CLARICE	CLARISSA
CLARINE	CLAIR
CLARISA	CLARISSA
CLARISE	CLARISSA
CLARKE	CLARK
CLAUDE	CLAUD

ORIGINAL_WORD	REPLACEMENT_WORD
CLAUDETTE	CLAUD
CLAUDIA	CLAUD
CLAUDIE	CLAUD
CLAUDINE	CLAUD
CLAUDIO	CLAUD
CLAUDY	CLAUD
CLAUS	NICHOLAS
CLAY	CLAYTON
CLAYBORN	CLAYTON
CLAYBORNE	CLAYTON
CLEM	CLEMENT
CLEMENCE	CLEMENT
CLEO	CLEOPATRA
CLEVE	CLIVE
CLOE	CHLOE
CLOTHILDE	CLOTILDE
CLOTILDA	CLOTILDE
CLOVIS	LEWIS
COL	COLEMAN
COLAN	COLIN

ORIGINAL_WORD	REPLACEMENT_WORD
COLBERT	CULBERT
COLE	COLEMAN
COLEEN	COLLEEN
COLENE	COLLEEN
COLLETTE	COLETTE
COLLEY	NICHOLAS
COLMAN	COLEMAN
COLVER	CULVER
CON	CONNIE
CONALL	CONAL
CONANA	CONAL
CONANT	CONAL
CONN	CONNIE
CONNEL	CONAL
CONNI	CONNIE
CONSTANCE	CONNIE
CONSTANT	CONNIE
CONSTANTIA	CONNIE
CONSTANTINA	CONNIE
CONSTANTINE	CONNIE

ORIGINAL_WORD	REPLACEMENT_WORD
CONSUELO	CONSUELA
CORALIE	CORAL
CORBY	CORBIN
CORDELLIA	CORDELLA
CORENE	CORA
CORETTA	CORA
CORETTE	CORA
CORINNA	CORA
CORINNE	CORA
CORNEL	CORNELIUS
CORNELA	CORNELIA
CORNELL	CORNELIUS
CORRENA	CORA
CORRIE	CORA
CORRY	CORA
CORT	COURTENAY
CORTIE	COURTENAY
CORTY	COURTENAY
CORWIN	CORBIN
CORY	COREY

ORIGINAL_WORD	REPLACEMENT_WORD
COURT	COURTENAY
COURTLAND	COURTENAY
COURTNEY	COURTENAY
CRISPEN	CRISPIN
CRYSTAL	CHRIS
CURT	CURTIS
CUTHBERT	CULBERT
CY	CYRUS
CYN	CYNTHIA
CYNTH	CYNTHIA
CYNTHIE	CYNTHIA
DAG	DAGMAR
DAIL	DALE
DAILE	DALE
DAISIE	DAISY
DAL	DALLAS
DALILA	DELILAH
DALTON	DALE
DAMARIS	DAMARA
DAMIAN	DAMON

ORIGINAL_WORD	REPLACEMENT_WORD
DAN	DANIEL
DANBY	DENBY
DANE	DANA
DANIELL	DANIEL
DANNY	DANIEL
DANTE	DURAND
DAPHIE	DAPHNE
DARA	DARCIE
DAREECE	DARICE
DAREES	DARICE
DARI	DARICE
DARIAN	DARIUS
DARLEEN	DARLENE
DARLINE	DARLENE
DARNELL	DANIEL
DARREN	DARRELL
DARRYL	DARRELL
DARYL	DARLENE
DAVE	DAVID
DAVETA	DAVINA

ORIGINAL_WORD	REPLACEMENT_WORD
DAVIDA	DAVINA
DAVIE	DAVID
DAVIS	DAVID
DAVITA	DAVINA
DAVY	DAVID
DEANE	DEAN
DEANNA	DIANA
DEB	DEBORAH
DEBBIE	DEBORAH
DEBBY	DEBORAH
DEBORA	DEBORAH
DEBRA	DEBORAH
DEE	AUDREY
DEEDEE	DEIDRE
DEL	CORDELIA
DELA	ADELAIDE
DELBERT	ALBERT
DELIA	CORDELLA
DELLA	CORDELLA
DELMER	DELMAR

ORIGINAL_WORD	REPLACEMENT_WORD
DELORES	DOLORES
DELORIS	DOLORES
DELPHINIA	DELPHINE
DEMITRIA	DEMETRIA
DEMMY	DEMETRIUS
DEMONA	MONA
DEMPSEY	DEMPSTER
DEMPSTOR	DEMPSTER
DEMY	DEMETRIA
DENICE	DENISE
DENIS	DENNIS
DENNIE	DENNIS
DENNISON	DENNIS
DENNY	DENNIS
DENY	DENNIS
DENYS	DENNIS
DENZIL	DENNIS
DEREK	THEODORIC
DERIAN	DARIUS
DERK	THEODORIC

ORIGINAL_WORD	REPLACEMENT_WORD
DERMOT	KERMIT
DERRICK	THEODORIC
DERWOOD	DURWARD
DESDAMONA	MONA
DESDEMONA	MONA
DESTA	MODESTA
DESTE	MODESTA
DEWEY	DAVID
DI	DIANA
DIANE	DIANA
DIANNA	DIANA
DIANNE	DIANA
DICK	RICHARD
DICKY	RICHARD
DIEGO	JAMES
DIERDRE	DEIDRE
DIM	DAPHNE
DIMITRI	DEMETRIUS
DIMITRIA	DEMETRIA
DINA	DINAH

ORIGINAL_WORD	REPLACEMENT_WORD
DION	DENNIS
DIX	DIXIE
DIXON	BENEDICT
DMITRI	DEMETRIUS
DODI	DORIS
DOLLIE	DOROTHY
DOLLY	DOROTHY
DOLORA	DOLORES
DOLPH	RUDOLPH
DOM	DOMINIC
DOMINIQUE	DOMINICA
DOMINY	DOMINIC
DON	DONALD
DONA	DONNA
DONAL	DONALD
DONALL	DONALD
DONINICK	DOMINIC
DONN	DONALD
DONNELL	DONALD
DONNIE	DONALD

ORIGINAL_WORD	REPLACEMENT_WORD
DONNY	DONALD
DORA	DOROTHY
DORE	DOROTHY
DOREEN	DORENE
DORETTA	DOROTHY
DOREY	DORIAN
DORI	THEODORA
DORIE	DORENE
DORIN	DORINDA
DORINE	DORENE
DOROTHEA	DOROTHY
DOROTHI	DOROTHY
DORRAN	DORAN
DORRIE	DOLORES
DORRY	DOLORES
DORTHEA	DOROTHY
DORTHY	DOROTHY
DORY	ISIDORE
DOT	DOROTHY
DOTTIE	DOROTHY

ORIGINAL_WORD	REPLACEMENT_WORD
DOTTY	DOROTHY
DOUG	DOUGLAS
DREW	ANDREW
DRU	DRUSILLA
DRUCILLA	DRUSILLA
DRUE	ANDREW
DRUS	DRUSILLA
DRUSIE	DRUSILLA
DUD	DEDLEY
DUKE	MARMADUKE
DULCI	DULCIE
DULCINE	DULCIE
DUNC	DUNCAN
DURANT	DURAND
DURWARE	DURWARD
DURWOOD	DURWARD
DURWYN	DURWIN
DWANE	DUANE
DWAYNE	DUANE
EADIE	EDITH

ORIGINAL_WORD	REPLACEMENT_WORD
EADITH	EDITH
EADWINA	EDWINA
EADWINE	EDWINA
EARLE	EARL
EARLY	EARL
EARTHA	HERTHA
EB	EBENEZER
EBERHART	EVERARD
EDA	EDITH
EDDIE	ED
EDDY	ED
EDE	EDITH
EDIE	EDITH
EDINA	EDITH
EDISON	ED
EDLIN	ED
EDMOND	ED
EDMUND	ED
EDNY	EDNA
EDRICH	ERIC

ORIGINAL_WORD	REPLACEMENT_WORD
EDRICK	EDRIC
EDSON	ED
EDUARD	ED
EDVIG	HEDWIG
EDWARD	ED
EDWIN	ED
EDWINE	EDWINA
EDYTHE	EDITH
EFFY	EFFIE
EFREM	EPHRAIM
EGON	EGAN
EILEEN	AILEEN
EIRENE	IRENE
EL	ELDON
ELANA	ELAINE
ELAYNE	ELAINE
ELBERT	ALBERT
ELBERTA	ALBERT
ELDEN	ELDON
ELDRED	EDDRIDGE

ORIGINAL_WORD	REPLACEMENT_WORD
ELDRID	EDDRIDGE
ELDWEN	ELDWIN
ELEANOR	HELEN
ELEANORA	HELEN
ELEANORE	HELEN
ELENA	HELEN
ELENE	HELEN
ELENORE	HELEN
ELERY	ELLERY
ELEXA	ALEX
ELFRIDA	ELFREDA
ELIA	ELI
ELIEZER	ELEAZAR
ELIHU	ELIAS
ELIJAH	ELIAS
ELINOR	HELEN
ELINORE	HELEN
ELIOT	ELIAS
ELISA	ELIZABETH
ELISABETH	ELIZABETH

ORIGINAL_WORD	REPLACEMENT_WORD
ELISABETTA	ELIZABETH
ELISE	ELIZABETH
ELISON	ELLISON
ELISSA	ALICE
ELIZA	ELIZABETH
ELLA	HELEN
ELLEN	HELEN
ELLIE	HELEN
ELLIOT	ELIAS
ELLIS	ELIAS
ELMIRA	ALMIRA
ELNORE	HELEN
ELOISE	LOUISE
ELSA	ELIZABETH
ELSBETH	ELIZABETH
ELSE	ELIZABETH
ELSIE	ELIZABETH
ELSWORTH	ELLSWORTH
ELVA	ELVIRA
ELVIE	ELVIRA

ORIGINAL_WORD	REPLACEMENT_WORD
ELVIN	ALVIN
ELWYN	ELWIN
ELY	ELI
EM	EMILY
EMERY	EMORY
EMIE	EMMA
EMILIA	EMILY
EMILIE	EMILY
EMLYN	EMIL
EMMETT	EMMET
EMMIE	EMMA
EMMY	EMILY
ENRICO	HENRY
EOLANDE	YOLANDE
EPH	EPHRAIM
ERDA	HERTHA
ERICK	ERIC
ERIK	ERIC
ERIKA	ERICA
ERIN	ERINA

ORIGINAL_WORD	REPLACEMENT_WORD
ERLE	EARL
ERMA	IRMA
ERME	IRMA
ERMIN	HERMAN
ERMINIE	ARMINA
ERN	ERNEST
ERNA	ERNESTINE
ERNESTA	ERNESTINE
ERNIE	ERNEST
ERROL	EARL
ERVIN	IRVIN
ERVINE	IRVIN
ERWIN	IRVIN
ESME	ESMERALDA
ESSIE	ESTHER
ESSY	ESTHER
ESTA	ESTHER
ESTELLA	ESTELLE
ESTER	ESTHER
ETHELBERT	ALBERT

ORIGINAL_WORD	REPLACEMENT_WORD
ETHYL	ETHEL
ETTA	HENRIETTA
ETTY	HENRIETTA
EUGENIE	EUGENIA
EUPHEMIA	EFFIE
EUPHEMIE	EFFIE
EV	EVERARD
EVA	EVE
EVAN	JOHN
EVELEEN	EVE
EVELINA	EVE
EVELINE	EVE
EVELYN	EVE
EVERETT	EVERARD
EVIE	EVE
EVITA	EVE
EVONNE	EVE
EZ	EZRA
EZMERALDA	ESMERALDA
FABE	FABIAN

ORIGINAL_WORD	REPLACEMENT_WORD
FAE	FAITH
FAIRLIE	FAIRLEY
FAN	FANNY
FANNIE	FANNY
FARANT	FARAND
FARL	FAIRLEY
FARLEY	FAIRLEY
FARRAND	FARAND
FARREL	FARRELL
FAULKNER	FALKNER
FAUSTENA	FAUSTINA
FAUSTINE	FAUSTINA
FAY	FAITH
FAYE	FAITH
FEFFRY	GEOFFREY
FELIC	FELICIA
FELISE	FELICIA
FEODOR	THEODORE
FEODORE	THEODORE
FERD	FERDINAND

ORIGINAL_WORD	REPLACEMENT_WORD
FERDE	FERDINAND
FERDIE	FERDINAND
FERNALD	FARNELL
FERNAND	FERDINAND
FERNANDO	FERDINAND
FHIONA	FIONNA
FIDELIA	FIDELA
FIDELITY	FIDELA
FIDELLA	FIDELA
FIFI	JOSEPHINE
FILBERT	PHILBERT
FILIP	PHILIP
FILMORE	FILMER
FILP	PHILIP
FINDLAY	FINLEY
FIO	FIONNA
FIONA	FIONNA
FISKE	FISK
FLAVIUS	FLAVIAN
FLEM	FLEMING

ORIGINAL_WORD	REPLACEMENT_WORD
FLETCH	FLETCHER
FLEUR	FLORENCE
FLEURETTE	FLORENCE
FLO	FLORENCE
FLORA	FLORENCE
FLORETTE	FLORENCE
FLORIA	FLORENCE
FLORIE	FLORENCE
FLORIS	FLORENCE
FLORY	FLORIAN
FLOSSIE	FLORENCE
FLOWER	FLORENCE
FLOYD	LLOYD
FOREST	FORREST
FOWLER	FALKNER
FRAN	FRANCES
FRANCE	FRANCES
FRANCESCA	FRANCES
FRANCHOT	FRANCES
FRANCINE	FRANCES

ORIGINAL_WORD	REPLACEMENT_WORD
FRANCIS	FRANCES
FRANK	FRANKLIN
FRANKIE	FRANCES
FRANNY	FRANCES
FRANZ	FRANCES
FRED	FREDERICK
FREDDIE	FREDERICK
FREDDY	FREDERICK
FREDERIC	FREDERICK
FREDERICKSEN	FREDERIKSEN
FREDERICKSON	FREDERIKSEN
FREDIE	FREDA
FREDRIC	FREDERICK
FREDRICKSEN	FREDERIKSEN
FREDRICKSON	FREDERIKSEN
FREDRIKA	FREDERICA
FREEMON	FREEMAN
FREIDA	FREDA
FRIDA	FREDA
FRIEDA	FREDA

ORIGINAL_WORD	REPLACEMENT_WORD
FRITZ	FREDERICK
FRITZI	FRITZIE
FRITZY	FRITZIE

This table lists the original and replacement words of the EXPANDED_PERSON_NAME_DICTIONARY word replacement list in alphabetical order from G to N.

ORIGINAL_WORD	REPLACEMENT_WORD
GABBY	GABRIEL
GABE	GABRIEL
GABEY	GABRIELLE
GABI	GABRIELLE
GABIE	GABRIELLE
GABRIELLA	GABRIELLE
GADMON	GADMAN
GAE	GAY
GAEL	ABIGAIL
GAIL	ABIGAIL
GALE	ABIGAIL
GAR	GARVIN
GARDA	GERDA
GARDNER	GARDINER

ORIGINAL_WORD	REPLACEMENT_WORD
GARETH	GARETT
GAREY	GARETT
GARNETT	GARNET
GAROLD	GERALD
GARRETH	GARETT
GARRETT	GARETT
GARRY	GARETT
GARTH	GARETT
GARY	GARETT
GASPAR	JASPER
GAVIN	GAWAIN
GAYE	GAY
GAYL	ABIGAIL
GEMINA	GEMINI
GEN	GUINEVERE
GENA	EUGENIA
GENE	EUGENIA
GENEVA	GENEVIEVE
GENIE	EUGENIA
GENNY	GUINEVERE

ORIGINAL_WORD	REPLACEMENT_WORD
GEOF	GEOFFREY
GEOFF	GEOFFREY
GEORGETTA	GEORGIANA
GEORGETTE	GEORGIANA
GEORGI	GEORGIANA
GEORGIA	GEORGIANA
GEORGIANNA	GEORGIANA
GEORGIE	GEORGIANA
GEORGINA	GEORGIANA
GEORGINE	GEORGIANA
GERALDA	GERALDINE
GERARD	GARETT
GERDI	GERDA
GERELD	GERALD
GERI	GERALDINE
GERRALD	GERALD
GERRY	GERALD
GERTA	GERTRUDE
GERTI	GERTRUDE
GERTIE	GERTRUDE

ORIGINAL_WORD	REPLACEMENT_WORD
GERTY	GERTRUDE
GERVAIS	GERVASE
GERY	GERALD
GIAN	JOHN
GIANNA	JANE
GIL	GILBERT
GILBERTE	GILBERTA
GILBERTINA	GILBERTA
GILBERTINE	GILBERTA
GILE	GILES
GILLES	GILES
GILLI	GILDA
GILLY	GILES
GILPIN	GILBERT
GINA	REGINA
GINE	REGINA
GINGER	VIRGINIA
GINNY	VIRGINIA
GIOVANNI	JOHN
GISELA	GISELLE

ORIGINAL_WORD	REPLACEMENT_WORD
GISELE	GISELLE
GITEL	GITTEL
GITLE	GITTEL
GITTLE	GITTEL
GLAD	GLADYS
GLADDIE	GLADYS
GLADINE	GLADYS
GLADIS	GLADYS
GLADWIN	GOODWIN
GLENDA	GLEN
GLENN	GLEN
GLENNA	GLEN
GLENNIE	GLEN
GLENNIS	GLEN
GLORIANNA	GLORIANA
GLORY	GLORIA
GLYNIS	GLEN
GLYNN	GLEN
GODDERD	GODDARD
GODDORD	GODDARD

ORIGINAL_WORD	REPLACEMENT_WORD
GODFREY	GEOFFREY
GODWIN	GOODWIN
GOLDY	GOLDIE
GRACIA	GRACE
GRACIE	GRACE
GRACYE	GRACE
GRAEME	GRAHAM
GRAY	GRAYSON
GREDEL	MARGARET
GREG	GREGORY
GREGGORY	GREGORY
GRETA	MARGARET
GRETCHEN	MARGARET
GREY	GRAYSON
GREYSON	GRAYSON
GRIFF	GRIFFITH
GRIFFIN	GRIFFITH
GRISSEL	GRISELDA
GUENEVERE	GUINEVERE
GUIDO	GUY

ORIGINAL_WORD	REPLACEMENT_WORD
GUNAR	GUNTHER
GUNTAR	GUNTHER
GUNTER	GUNTHER
GUNT HAR	GUNTHER
GUSSIE	GUS
GUSTA	GUS
GUSTAF	GUS
GUSTANE	GUS
GUSTAVE	GUS
GUSTAVO	GUS
GUSTAVUS	GUS
GUSTIN	GUS
GUYON	GUY
GWEN	GWENDOLEN
GWENDOLYN	GWENDOLEN
GWENN	GWENDOLEN
GWYN	GWENDOLEN
GWYNETH	GWENDOLEN
HADEN	HADDEN
HADRIAN	ADRIAN

ORIGINAL_WORD	REPLACEMENT_WORD
HAGGAR	HAGAR
HAL	HENRY
HALDANE	HALDEN
HALSY	HALDSEY
HAM	GRAHAM
HAMISH	JAMES
HAMLIN	HENRY
HANK	HENRY
HANLEIGH	HANLEY
HANS	JOHN
HANSON	HANSEN
HANSSON	HANSEN
HARALD	HAROLD
HARBERT	HERBERT
HARDEN	HARLEY
HARL	HARLEY
HARLEIGH	HARLEY
HARMAN	HERMAN
HARMON	HERMAN
HARRIETTA	HARRIET

ORIGINAL_WORD	REPLACEMENT_WORD
HARRIETTE	HARRIET
HARROD	HAROD
HARRY	HAROLD
HART	HARLEY
HARTLEY	HARLEY
HARV	HARVEY
HARVE	HARVEY
HARWELL	HARTWELL
HARWILL	HARTWELL
HATTI	HARRIET
HATTIE	HARRIET
HATTY	HARRIET
HAYNES	HAINES
HEATH	HEATHER
HECK	HECTOR
HEDDY	HEDDA
HEDI	HEDWIG
HEDVIG	HEDWIG
HEDY	HEDDA
HEIDI	HILDA

ORIGINAL_WORD	REPLACEMENT_WORD
HEINRICK	HENRY
HELENA	HELEN
HELENE	HELEN
HELLENE	HELEN
HELOISE	LOUISE
HEN	HENRY
HENDRICK	HENRY
HENDRIK	HENRY
HENLEIGH	HANLEY
HENLEY	HANLEY
HENNI	HENRIETTA
HENNIE	HENRIETTA
HENRI	HENRY
HENRIETTE	HENRIETTA
HENRIKA	HENRIETTA
HEPSIBA	HEPHZIBAH
HEPSIBAH	HEPHZIBAH
HEPSIBETHA	HEPHZIBAH
HERALD	HAROLD
HERB	HERBERT

ORIGINAL_WORD	REPLACEMENT_WORD
HERBIE	HERBERT
HERELD	HAROLD
HERM	HERMAN
HERMIE	HERMAN
HERMON	HERMAN
HERNANDO	FERDINAND
HEROD	HERROD
HEROLD	HAROLD
HERRICK	HAROLD
HERTA	HERTHA
HERV	HARVEY
HERVE	HARVEY
HERVEY	HARVEY
HESKETH	HEZEKIAH
HETTI	HESTER
HETTIE	HESTER
HETTY	HESTER
HEWE	HUGH
HIATT	HYATT
HILAIRE	HILARY

ORIGINAL_WORD	REPLACEMENT_WORD
HILDAGARD	HILDA
HILDAGARDE	HILDA
HILDE	HILDA
HILDEGARD	HILDA
HILDIE	HILDA
HILDY	HILDA
HILLAREY	HILARY
HILLARY	HILARY
HOBART	HUBERT
HOLLIE	HOLLY
HONEY	HONORA
HONORIA	HONORA
HORATION	HORACE
HORATIUS	HORACE
HORTENSA	HORTENSE
HOWIE	HOWARD
HOYT	HUBERT
HUBBARD	HUBERT
HUBIE	HUBERT
HUEY	HUGH

ORIGINAL_WORD	REPLACEMENT_WORD
HUGHES	HUGH
HUGHIE	HUGH
HUGO	HUGH
HUMFREY	HUMPHREY
HUNTLEY	HUNTER
HY	HYMAN
HYMEN	HYMAN
HYMIE	HYMAN
IAN	JOHN
IDALLA	IDA
IDELLE	IDA
IGGY	IGNATIUS
IGNACE	IGNATIUS
IGNATIA	IGNACIA
IGNATZ	IGNATIUS
IGNATZIA	IGNACIA
ILENE	AILEEN
ILINE	AILEEN
ILLENE	AILEEN
ILLONA	AILEEN

ORIGINAL_WORD	REPLACEMENT_WORD
IMMANUEL	EMMANUEL
IMOGEN	IMOGENE
INA	KATHERINE
INES	INEZ
INGA	INGRID
INGE	IGOR
INGEBORG	INGRID
INGMAR	IGOR
INGRAHAM	INGRAM
INGRED	INGRID
INNIS	INNESS
IONE	IONA
IONIA	IONA
IRENA	IRENE
IRINA	IRENE
IRME	IRMA
IRMINA	IRMA
IRMINE	IRMA
IRV	IRVIN
IRVING	IRVIN

ORIGINAL_WORD	REPLACEMENT_WORD
IRWIN	IRVIN
ISABELLA	ISABEL
ISABELLE	ISABEL
ISADOR	ISIDORE
ISADORE	ISIDORE
ISBEL	ISABEL
ISIDOR	ISIDORE
ISIDORA	ISDORA
ISOBEL	ISABEL
ISOLDA	ISOLDE
ISSY	ISIDORE
IVA	IVAH
IVAN	JOHN
IVAR	YVES
IVER	YVES
IVES	YVES
IVO	YVES
IVON	YVES
IVONNE	YVONNE
IVOR	YVES

ORIGINAL_WORD	REPLACEMENT_WORD
IZ	ISRAEL
IZZY	ISRAEL
JABE	JABEZ
JACABSIN	JACOBSON
JACENTA	JACINDA
JACK	JOHN
JACOB	JAMES
JACOBSEN	JACOBSON
JACOBSSON	JACOBSON
JACQUES	JAMES
JADAH	JADA
JADDA	JADA
JAKE	JAMES
JAKIE	JAMES
JAKOBSEN	JACOBSON
JAKOBSON	JACOBSON
JAMESY	JAMES
JAMIE	JAMES
JAN	JOHN
JANET	JANE

ORIGINAL_WORD	REPLACEMENT_WORD
JANETTE	JANE
JANEY	JANE
JANICE	JANE
JANNA	JANE
JARET	GARETT
JARV	GERVASE
JARVEY	GERVASE
JARVIS	GERVASE
JARY	GARETT
JASMIN	JASMINE
JASMINA	JASMINE
JEAN	JOHN
JEANETTE	JANE
JEANIE	JANE
JEANNINE	JANE
JED	JEDEDIAH
JEDDY	JEDEDIAH
JEDIDIAH	JEDEDIAH
JEFEREY	GEOFFREY
JEFF	GEOFFREY

ORIGINAL_WORD	REPLACEMENT_WORD
JEFFERS	GEOFFREY
JEFFREY	GEOFFREY
JEGGAR	JEGAR
JEGGER	JEGAR
JEM	JAMES
JEMIMA	JEMIMAH
JEMMIE	JAMES
JEMMIMA	JEMIMAH
JEMMY	JAMES
JEN	GUINEVERE
JENNI	GUINEVERE
JENNIE	GUINEVERE
JENNIFER	GUINEVERE
JENNY	GUINEVERE
JENSON	JENSEN
JENSSON	JENSEN
JER	GERALD
JERALDINE	GERALDINE
JERELO	GERALD
JEREMIAH	JEREMY

ORIGINAL_WORD	REPLACEMENT_WORD
JEREMIAS	JEREMY
JEROLD	GERALD
JERRI	GERALDINE
JERRIE	GERALDINE
JERROLD	GERALD
JERRY	GERALD
JERVIS	GERVASE
JESS	JESSICA
JESSE	JESSICA
JESSI	JESSICA
JESSIE	JESSICA
JESSY	JESSICA
JETH	JETHRO
JEVON	JOHN
JILL	JULIE
JIM	JAMES
JIMMIE	JAMES
JIMMY	JAMES
JINNY	VIRGINIA
JO	JOSEPHINE

ORIGINAL_WORD	REPLACEMENT_WORD
JOAN	JANE
JOANA	JANE
JOANIE	JANE
JOANNA	JANE
JOBYNA	JOBINA
JOCELIN	LYNN
JOCELYN	LYNN
JOCK	JOHN
JOCKO	JAMES
JODIE	JUDITH
JODY	JUDITH
JOE	JOSEPH
JOEY	JOSEPH
JOHAN	JOHN
JOHANN	JOHN
JOHANNA	JANE
JOHNNIE	JOHN
JOHNNY	JOHN
JOLIET	JULIE
JON	JOHN

ORIGINAL_WORD	REPLACEMENT_WORD
JONAH	JONAS
JONE	JONAS
JONIE	JANE
JONNIE	JOHN
JONNY	JOHN
JORGE	GEORGE
JORGENSON	JORGENSEN
JOS	JOSEPH
JOSE	JOSEPH
JOSEPHINA	JOSEPHINE
JOSH	JOSHUA
JOSIE	JOSEPHINE
JOSLYN	LYNN
JUAN	JOHN
JUANA	JANE
JUANITA	JANE
JUDITHA	JUDITH
JUDY	JUDITH
JULE	JULIE
JULES	JULIE

ORIGINAL_WORD	REPLACEMENT_WORD
JULEY	JULIE
JULIA	JULIE
JULIAN	JULIE
JULIANA	JULIE
JULIANE	JULIE
JULIET	JULIE
JULIETTA	JULIE
JULIETTE	JULIE
JULIUS	JULIE
JUN	JUNIUS
JUNIE	JUNIUS
JURGEN	GEORGE
JUST	JUSTIN
JUSTINA	JUSTINE
JUSTUS	JUSTIN
KARA	KATHERINE
KAREN	KATHERINE
KARENA	KATHERINE
KARIN	KATHERINE
KARL	CHARLES

ORIGINAL_WORD	REPLACEMENT_WORD
KARLA	CARLA
KARLY	CARLA
KAROL	CAROL
KAROLE	CAROL
KAROLINA	CAROL
KAROLINE	CAROL
KAROLYN	CAROL
KARYN	KATHERINE
KASPAR	JASPER
KATE	KATHERINE
KATHARINA	KATHERINE
KATHARINE	KATHERINE
KATHERIN	KATHERINE
KATHIE	KATHERINE
KATHLEEN	KATHERINE
KATHLENE	KATHERINE
KATHRINA	KATHERINE
KATHRYN	KATHERINE
KATHY	KATHERINE
KATIE	KATHERINE

ORIGINAL_WORD	REPLACEMENT_WORD
KAVAN	CAVAN
KAYNE	KANE
KAZIMIR	CASIMIR
KELCEY	KELSEY
KEMBLE	KIMBALL
KEN	KENNETH
KENDAL	KENDALL
KENDRICKS	KENDRICK
KENLEIGH	KENLEY
KENNET	KENNETH
KENNY	KENNETH
KENRIC	KENDRICK
KENT	KENNETH
KERBY	KIRBY
KERK	KIRK
KERR	KIRBY
KERRIE	KIRBY
KERRIN	KIRBY
KERRY	KIRBY
KERWIN	KIRBY

ORIGINAL_WORD	REPLACEMENT_WORD
KESTER	CHRIS
KETTI	KATHERINE
KEV	KEVIN
KIERAN	KIRBY
KILE	KYLE
KIM	KIMBALL
KIMBLE	KIMBALL
KIRBEE	KIRBY
KIRBIE	KIRBY
KIRWIN	KIRBY
KIT	CHRIS
KITTIE	KATHERINE
KITTY	KATHERINE
KLAUS	NICHOLAS
KONRAD	CONRAD
KORAL	CORAL
KRIS	CHRIS
KRISS	CHRIS
KRISTIAN	CHRIS
KRISTIANA	CHRIS

ORIGINAL_WORD	REPLACEMENT_WORD
KRISTIN	CHRIS
KRISTINA	CHRIS
KRISTINE	CHRIS
KURT	CURTIS
KYNAN	CONAL
LAINE	ELAINE
LAM	LAMBERT
LAMOND	LAMONT
LANA	ALANA
LANCELOT	LANCE
LANCEY	LANCE
LANE	ALANA
LANGDON	LANDON
LANGSTON	LANDON
LANI	ELAINE
LARAINÉ	LORRAINE
LARI	LAURA
LARRY	LAWRENCE
LARS	LAWRENCE
LARSEN	LARSON

ORIGINAL_WORD	REPLACEMENT_WORD
LARSSON	LARSON
LARZ	LAWRENCE
LATHROPE	LATHROP
LAUGHTON	LAWTON
LAUNCE	LANCE
LAUNCELOT	LANCE
LAUREEN	LAURA
LAUREL	LAURA
LAUREN	LAWRENCE
LAURENCE	LAWRENCE
LAURENT	LAWRENCE
LAURETTE	LAURA
LAURIE	LAWRENCE
LAVERNA	VERNA
LAVERNE	VERNA
LAVINA	LAVINIA
LAZAR	ELEAZAR
LAZARUS	ELEAZAR
LEA	LEE
LECTRA	ELECTRA

ORIGINAL_WORD	REPLACEMENT_WORD
LEDA	ALIDA
LEELA	LEILA
LEELAND	LELAND
LEICESTER	LESTER
LEIGH	LEE
LEILAH	LEILA
LELA	LILLIAN
LELAH	LILLIAN
LELIA	LILLIAN
LEM	LEMUEL
LEN	LEE
LENA	HELEN
LENNI	HELEN
LENNIE	LEE
LENNY	LEE
LENORE	HELEN
LEO	LEE
LEOLA	LEONA
LEON	LEE
LEONARD	LEE

ORIGINAL_WORD	REPLACEMENT_WORD
LEONARDO	LEE
LEONE	LEONA
LEONI	LEONA
LEONIE	LEONA
LEONORE	HELEN
LEONTYNE	LEONTINE
LEOPOLD	LEE
LEORA	HELEN
LEPP	LEE
LEROY	ELROY
LES	LESLEY
LESLI	LESLEY
LESLIE	LESLEY
LESLY	LESLEY
LETA	LETITIA
LETICIA	LETITIA
LETTA	ALETHEA
LETTIE	LETITIA
LETTY	CHARLOTTE
LEW	LEWIS

ORIGINAL_WORD	REPLACEMENT_WORD
LEWES	LEWIS
LEX	ALEX
LIANA	LEANNE
LIANNE	LEANNE
LIBBY	ELIZABETH
LIDA	ALIDA
LIL	LILLIAN
LILA	LILLIAN
LILAH	LILLIAN
LILIA	LILLIAN
LILIAN	LILLIAN
LILIS	LILLITH
LILITH	LILLITH
LILLA	LILLIAN
LILLI	LILLIAN
LILLIBEL	LILLIAN
LILLIE	LILLIAN
LILLY	LILLIAN
LILY	LILLIAN
LILYAN	LILLIAN

ORIGINAL_WORD	REPLACEMENT_WORD
LILYBELL	LILLIAN
LILYBELLE	LILLIAN
LINA	CAROL
LINC	LINCOLN
LIND	LINDA
LINDIE	LINDA
LINDON	LYNDON
LINDY	LINDA
LINK	LINCOLN
LINN	LYNN
LION	LEE
LIONEL	LEE
LIRIS	LYRIS
LISA	ELIZABETH
LISABET	ELIZABETH
LISABETH	ELIZABETH
LIBETH	ELIZABETH
LISLE	LYLE
LIVA	OLIVIA
LIVI	OLIVIA

ORIGINAL_WORD	REPLACEMENT_WORD
LIVIA	OLIVIA
LIVVI	OLIVIA
LIZ	ELIZABETH
LIZA	ELIZABETH
LIZZIE	ELIZABETH
LIZZY	ELIZABETH
LODIE	MELODY
LOIS	ALOYSIA
LOLETA	LOLA
LOLITA	LOLA
LON	ALPHONSE
LONNY	ZEBULON
LORA	LAURA
LORAIN	LORRAINE
LORALIE	LAURA
LOREDO	LORING
LOREE	LAURA
LORELIE	LAURA
LOREN	LAWRENCE
LORENZ	LAWRENCE

ORIGINAL_WORD	REPLACEMENT_WORD
LORENZO	LAWRENCE
LORETTA	LAURA
LORETTE	LAURA
LORI	LAURA
LORIE	LAURA
LORIN	LAWRENCE
LORINDA	LAURA
LORINE	HELEN
LORNA	LAURA
LORNE	LAURA
LORRIE	LAURA
LORRY	LAWRENCE
LOTHAIR	LUTHER
LOTHAR	LUTHER
LOTHARIO	LUTHER
LOTTA	CHARLOTTE
LOTTE	CHARLOTTE
LOTTIE	CHARLOTTE
LOTTY	CHARLOTTE
LOU	LOUISE

ORIGINAL_WORD	REPLACEMENT_WORD
LOUIE	LEWIS
LOUIS	LEWIS
LOUISA	LOUISE
LOVEL	LOWELL
LOVELL	LOWELL
LOYCE	LOUISE
LU	LUCY
LUCAS	LUCIUS
LUCE	LUCIUS
LUCIA	LUCY
LUCIAN	LUCIUS
LUCIE	LUCY
LUCILLA	LUCY
LUCILLE	LUCY
LUCINDA	LUCY
LUCRETIA	LUCY
LUDOVICK	LEWIS
LUDVIG	LEWIS
LUIGI	LEWIS
LUIS	LEWIS

ORIGINAL_WORD	REPLACEMENT_WORD
LUKE	LUCIUS
LUKEV	LUCIUS
LULU	LUCY
LYN	LYNN
LYND	LINDA
LYNDA	LINDA
LYNNA	LYNN
LYNNE	LYNN
LYON	LEE
MADA	MADLINE
MADDIE	MADLINE
MADDIS	MATTHEW
MADDOX	MADDOCK
MADELEINE	MADLINE
MADELENE	MADLINE
MADOLON	MADLINE
MADEN	MATTHEW
MADGE	MARGARET
MADID	MADLINE
MADOC	MADDOCK

ORIGINAL_WORD	REPLACEMENT_WORD
MAE	MAY
MAG	MARGARET
MAGDA	MADLINE
MAGDALEN	MADLINE
MAGGIE	MARGARET
MAIDY	MAIDA
MAISIE	MARGARET
MAL	MALVIN
MALAN	MELANIE
MALVINA	MELVINA
MAMIE	MARY
MANDA	AMANDA
MANDIE	AMANDA
MANDY	AMANDA
MANNY	EMMANUEL
MANON	MARY
MANUEL	EMMANUEL
MAPH	DAPHNE
MARA	MARY
MARC	MARK

ORIGINAL_WORD	REPLACEMENT_WORD
MARCEL	MARK
MARCELLA	MARCIA
MARCH	MARK
MARCIE	MARCIA
MARCO	MARK
MARCUS	MARK
MARCY	MARCIA
MAREK	MARK
MARGARITA	MARGARET
MARGE	MARGARET
MARGER	MARGARET
MARGERY	MARGARET
MARGIE	MARGARET
MARGO	MARGARET
MARGOT	MARGARET
MARI	MARY
MARIA	MARY
MARIAM	MARY
MARIAN	MARY
MARIE	MARY
MARIETTA	MARY

ORIGINAL_WORD	REPLACEMENT_WORD
MARIETTE	MARY
MARIGOLD	MARIGOLDE
MARILYN	MARY
MARION	MARY
MARISA	MARIS
MARITA	MAURITA
MARJORIE	MARGARET
MARL	MERLIN
MARLA	MARY
MARLEEN	MADELINE
MARLEN	MERLIN
MARLENE	MADELINE
MARLIN	MERLIN
MARLINE	MADELINE
MARLON	MERLIN
MARRAS	MARIS
MARRIS	MARIS
MARS	MARK
MARSH	MARSHALL
MARSHA	MARCIA

ORIGINAL_WORD	REPLACEMENT_WORD
MARSHAL	MARSHALL
MARTA	MARTHA
MARTEENA	MARTINA
MARTELLA	MARTHA
MARTHE	MARTHA
MARTI	MARTINA
MARTIE	MARTHA
MARTIN	MARK
MARTINE	MARTINA
MARTY	MARK
MARTYN	MARK
MARV	IRVIN
MARVELLA	MARVA
MARVIN	IRVIN
MARYA	MARY
MAT	MATTHEW
MATHIAS	MATTHEW
MATT	MATTHEW
MATTHIAS	MATTHEW
MATTI	MATHILDA

ORIGINAL_WORD	REPLACEMENT_WORD
MATTIE	MARTHA
MATTY	MATTHEW
MAUD	MATHILDA
MAUDE	MATHILDA
MAUREEN	MARY
MAURETTA	MAURITA
MAUREY	MURRAY
MAURI	MAURITA
MAURICE	MURRAY
MAURY	MURRAY
MAX	MAXIMILLIAN
MAXEY	MAXIMILLIAN
MAXIE	MAXIMILLIAN
MAXIM	MAXIMILLIAN
MAYBELLE	MABEL
MAYER	MEYER
MEAGAN	MEGAN
MEAGHAN	MEGAN
MEG	MARGARET
MEGHAN	MEGAN

ORIGINAL_WORD	REPLACEMENT_WORD
MEHITABEL	METHETABEL
MEL	MELISSA
MELAN	MELANIE
MELANIA	MELANIE
MELBA	MELVINA
MELICENT	MILLCENT
MELIE	AMELIA
MELINA	MELANIE
MELISA	MELISSA
MELL	AMELIA
MELLIE	MELANIE
MELLY	MELANIE
MELODIE	MELODY
MELONEY	MELANIE
MELVIN	MALVIN
MENA	PHILOMENA
MERCI	MERCEDES
MERCY	MERCEDES
MERI	MERRIE
MERIDITH	MEREDITH

ORIGINAL_WORD	REPLACEMENT_WORD
MERIEL	MURIEL
MERL	MERLIN
MERLA	MERLE
MERRI	MERRITT
MERRICK	EMORY
MERRILL	MYRON
MERT	MYRTLE
MERTA	MYRTLE
MERV	IRVIN
MERVIN	IRVIN
MERWIN	IRVIN
MERYL	MERLE
METABEL	METHETABEL
MICKEY	MICHAEL
MIKE	MICHAEL
MILICENT	MILLCENT
MILL	AMELIA
MILLI	MILDRED
MILLIE	MILDRED
MILLY	CAMILLA

ORIGINAL_WORD	REPLACEMENT_WORD
MILT	MILTON
MIMI	MARY
MIN	MINNA
MINA	WILHELMINA
MINETTE	MARY
MINI	MINNA
MINNIE	MINNA
MINNY	MINNA
MIRA	MIRABEL
MIRABELLE	MIRABEL
MIRI	MIRANDA
MIRIAM	MARY
MITCH	MICHAEL
MITCHELL	MICHAEL
MITZI	MARY
MITZIE	MARY
MODESTE	MODESTA
MOE	MOSES
MOIRA	MARY
MOLL	MARY

ORIGINAL_WORD	REPLACEMENT_WORD
MOLLIE	MARY
MOLLY	MARY
MONIQUE	MONICA
MONTAGU	MONTAGUE
MONTE	MONTAGUE
MONTY	MONTGOMERY
MOREL	MURRAY
MORENE	MARY
MORICE	MURRAY
MORRIS	MURRAY
MORRY	MURRAY
MORT	MORTIMER
MORTIE	MORTIMER
MORTY	MORTIMER
MOSE	MOSES
MOSS	MOSES
MUNRO	MONROE
MUR	MURIEL
MURDOCK	MURDOCH
MURIELLE	MURIEL

ORIGINAL_WORD	REPLACEMENT_WORD
MURREY	MURRAY
MURRY	MURRAY
MURTAGH	MURDOCH
MYRNA	MORNA
MYRT	MYRTLE
MYRTA	MYRTLE
NADA	NADINE
NADIA	NADINE
NAN	ANN
NANA	ANN
NANCY	ANN
NANETE	ANN
NANETTE	ANN
NANINE	ANN
NANON	ANN
NARA	NARDA
NAT	NATALIE
NATALA	NATALIE
NATALE	NATALIE
NATALEE	NATALIE

ORIGINAL_WORD	REPLACEMENT_WORD
NATALIA	NATALIE
NATASHA	NATALIE
NATE	NATHANIEL
NATHALIE	NATALIE
NATHAN	NATHANIEL
NATHANAEL	NATHANIEL
NATICA	NATALIE
NATIE	NATHANIEL
NATIKA	NATALIE
NATTIE	NATALIE
NATTY	NATHANIEL
NEAL	CORNELIUS
NEALE	CORNELIUS
NEALEY	CORNELIUS
NED	ED
NEDDA	NEDA
NEDDY	ED
NEDI	NEDA
NEIL	CORNELIUS
NEILSON	CORNELIUS

ORIGINAL_WORD	REPLACEMENT_WORD
NELIA	CORNELIA
NELL	CORNELIA
NELLIE	HELEN
NELLY	HELEN
NELSON	CORNELIUS
NEREEN	NERINE
NERIN	NERINE
NERINA	NERINE
NERITA	NERISSA
NERNADINA	BERNADINE
NESSA	AGNES
NESSIE	AGNES
NESSIM	NESTOR
NETTA	NATALIE
NETTIE	NATALIE
NETTY	NATALIE
NEV	NEVILLE
NEVIL	NEVILLE
NEVINS	NEVIN
NEWEL	NOEL

ORIGINAL_WORD	REPLACEMENT_WORD
NEWELL	NOEL
NEYSA	AGNES
NIC	DOMINIC
NICHOL	NICHOLAS
NICHOLL	NICHOLAS
NICK	NICHOLAS
NICKY	NICHOLAS
NICOLA	NICOLE
NICOLAS	NICHOLAS
NICOLETTA	NICOLE
NICOLETTE	NICOLE
NIKI	NICOLE
NIKKI	NICOLE
NIKOLA	NICOLE
NILES	NICHOLAS
NINA	ANN
NINETTE	ANN
NINON	ANN
NOBEL	NOBLE
NOELLA	NOEL

ORIGINAL_WORD	REPLACEMENT_WORD
NOELLE	NOEL
NOLAN	NOBLE
NOLITA	OLIVIA
NOLL	OLIVER
NOLLIE	OLIVER
NOLLY	OLIVER
NOMI	NAOMI
NONIE	NONA
NONNA	NONA
NORA	HELEN
NORAH	HONORA
NOREEN	HONORA
NORINE	HONORA
NORM	NORMAN
NORMAND	NORMAN
NORMI	NORMA
NORMIE	NORMA
NORRIE	HONORA
NORRIS	NORMAN
NORTY	NORTON

ORIGINAL_WORD	REPLACEMENT_WORD
NORWOOD	NORWARD
NORWORD	NORWARD

This table lists the original and replacement words of the EXPANDED_PERSON_NAME_DICTIONARY word replacement list in alphabetical order from O to Z.

ORIGINAL_WORD	REPLACEMENT_WORD
OBE	OBADIAH
OCTAVE	OCTAVIUS
OCTAVIAN	OCTAVIUS
OCTAVUS	OCTAVIUS
ODEL	ODELE
ODELET	ODELE
ODELL	ODELE
ODELLA	ODELIA
ODET	ODETTE
ODETTA	ODETTE
ODILE	ODELIA
ODIN	ODELE
ODO	ODELE
OLEN	OLAF
OLIVE	OLIVIA

ORIGINAL_WORD	REPLACEMENT_WORD
OLIVIER	OLIVER
OLLI	OLIVIA
OLLIE	OLIVER
ONA	UNA
ONDINE	UNDINE
OONA	UNA
ORA	AURELIA
ORABEL	ORIBEL
ORABELLE	ORIBEL
ORALIA	AURELIA
ORALIE	AURELIA
OREL	AURELIA
ORI	ORIBEL
ORIBELLE	ORIBEL
ORIEL	ORIOLE
ORIN	OREN
ORLANDO	ROLAND
ORLENE	ORLENA
ORLINA	ORLENA
ORMAN	ORMOND

ORIGINAL_WORD	REPLACEMENT_WORD
ORMAND	ORMOND
ORRIN	OREN
ORSINI	ORSON
ORSINO	ORSON
ORVIL	ORVILLE
OS	OSWALD
OSBORNE	OSBORN
OSBOURNE	OSBORN
OSMAND	OSMOND
OSMUND	OSMOND
OTILA	OTTILIE
OTTI	OTTILIE
OTTIE	OTTILIE
OTTILLIA	OTTILIE
OWAIN	OWEN
OZ	OSWALD
OZZIE	OSCAR
PACKSTON	PAXTON
PADDY	PAT
PADRAIC	PAT

ORIGINAL_WORD	REPLACEMENT_WORD
PAIGE	PAGE
PALEY	PAUL
PAM	PAMELA
PAMMY	PAMELA
PANSIE	PANSY
PARKE	PARK
PARNELL	PETER
PATRIC	PAT
PATRICE	PAT
PATRICIA	PAT
PATRICK	PAT
PATSY	PAT
PATTI	PAT
PATTY	PAT
PAULETTE	PAULA
PAULI	PAULA
PAULIE	PAULA
PAULINA	PAULA
PAULINE	PAULA
PAULITA	PAULA

ORIGINAL_WORD	REPLACEMENT_WORD
PAXON	PAXTON
PAYNE	PAINE
PEARCE	PETER
PEARLE	PEARL
PEARSON	PIERSON
PEDRO	PETER
PEERSON	PIERSON
PEG	MARGARET
PEGGY	MARGARET
PEITRO	PETER
PEN	PENELOPE
PENNIE	PENELOPE
PENNY	PENELOPE
PEONIE	PEONY
PEPI	PEPITA
PERCE	PERCIVAL
PERCEVAL	PERCIVAL
PERCY	PERCIVAL
PEREGRINE	PERRY
PERL	PEARL

ORIGINAL_WORD	REPLACEMENT_WORD
PERLIE	PEARL
PERNELL	PETER
PERNELLA	PARNELLA
PERR	PERRY
PERRIN	PETER
PET	PETRA
PETA	PETRA
PETE	PETER
PETEY	PETER
PETI	PETRA
PETIE	PETER
PETRIE	PETER
PETRINA	PETRA
PETRINE	PETRA
PETTA	PETRA
PETULAH	PETULA
PEYTON	PAT
PHEBE	PHILOMENA
PHELPS	PHILIP
PHENICA	PHENICE

ORIGINAL_WORD	REPLACEMENT_WORD
PHENICIA	PHENICE
PHIL	PHILIP
PHILINA	PHILANA
PHILINE	PHILANA
PHILIPA	PHILIPPA
PHILIPPE	PHILIPPA
PHILIS	PHYLLIS
PHILLANE	PHILANA
PHILLIS	PHYLLIS
PHOEBE	PHILOMENA
PHYL	PHYLLIS
PHYLIS	PHYLLIS
PIERCE	PETER
PIERRE	PETER
PIPPA	PHILIPPA
PIPPIN	PERRY
POL	PAULA
POLL	PAULA
POLLIE	PAULA
POLLY	PAULA

ORIGINAL_WORD	REPLACEMENT_WORD
PORCIA	PORTIA
PRENTISS	PRENTICE
PRIMROSE	ROSE
PRIS	PRISCILLA
PRISILLA	PRISCILLA
PRISSIE	PRISCILLA
PRISSY	PRISCILLA
PROCTER	PROCTOR
PRU	PRUDENCE
PRUD	PRUDENCE
PRUDI	PRUDENCE
PRUDIE	PRUDENCE
PRUDY	PRUDENCE
PRYOR	PRIOR
PURCELL	PERCIVAL
QUEENIE	REGINA
QUENT	QUENTIN
QUILL	QUILLON
QUINN	CONAL
QUINT	QUENTIN

ORIGINAL_WORD	REPLACEMENT_WORD
QUINTIN	QUENTIN
QUINTINA	QUINTA
RAB	ROBERT
RACE	HORACE
RACHELE	RACHEL
RACHELLE	RACHEL
RADBOURNE	RADBURN
RADBURNE	RADBURN
RAE	RACHEL
RAFAEL	RAPHAEL
RAFAELA	RAPHAELA
RAFF	RAPHAEL
RAFFAELLO	RAPHAEL
RALFSTON	RALSTON
RALPH	RANDOLPH
RAMA	MONA
RAMON	REGINALD
RAMONA	MONA
RAN	FARAND
RAND	RANDOLPH

ORIGINAL_WORD	REPLACEMENT_WORD
RANDAL	RANDOLPH
RANDALL	RANDOLPH
RANDIE	MIRANDA
RANDY	RANDOLPH
RANI	RANA
RANIA	RANA
RAWSON	RAWLING
RAY	REGINALD
RAYMOND	REGINALD
RAYMUND	REGINALD
REBA	REBECCA
REBAH	REBBA
REBEKAH	REBECCA
REED	READE
REG	REGINALD
REGAN	REGINA
REGGIE	REGINA
REGINE	REGINA
REID	READE
REINHOLD	REGINALD

ORIGINAL_WORD	REPLACEMENT_WORD
RENA	IRENE
RENATA	RENEE
RENE	IRENE
RENI	RENEE
RENNIE	RENEE
RENNY	IRENE
REYNOLD	REGINALD
RHODIA	ROSE
RIBA	REBECCA
RICA	ULRICA
RICARDO	RICHARD
RICH	RICHARD
RICHIE	RICHARD
RICK	ERIC
RICKY	RICHARD
RIKA	ERICA
RIKI	ERICA
RINALDO	REGINALD
RITA	MAURITA
RITCH	RICHARD

ORIGINAL_WORD	REPLACEMENT_WORD
RITCHIE	RICHARD
RIVA	REBECCA
RO	ROLANDA
ROB	ROBERT
ROBBI	ROBERTA
ROBBIE	ROBERT
ROBBY	ROBERT
ROBERTO	ROBERT
ROBI	ROBERTA
ROBIN	ROBERT
ROBINA	ROBERTA
ROCHELLE	RACHEL
RODDIE	ROD
RODDY	ROD
RODERIC	ROD
RODERICK	ROD
RODI	ROD
RODIE	RHODA
RODMAN	ROD
RODMANN	ROD

ORIGINAL_WORD	REPLACEMENT_WORD
RODNEY	ROD
RODRICK	ROD
ROLA	ROLANDA
ROLEY	ROLAND
ROLF	RANDOLPH
ROLFE	RANDOLPH
ROLISTON	RALSTON
ROLLIN	ROLAND
ROLLO	ROLAND
ROLPH	RUDOLPH
ROLSTON	RALSTON
RON	REGINALD
RONA	RONDALDA
RONALD	REGINALD
RONNIE	VERONICA
RONNY	VERONICA
RORIE	ROD
RORRY	ROD
RORY	ROD
ROS	ROSWELL

ORIGINAL_WORD	REPLACEMENT_WORD
ROSA	ROSE
ROSABEL	ROSE
ROSABELLA	ROSE
ROSALEEN	ROSE
ROSALIA	ROSE
ROSALIE	ROSE
ROSALIND	ROSE
ROSALINDE	ROSE
ROSALLE	ROSE
ROSALYN	ROSE
ROSAMOND	ROSE
ROSAMUND	ROSE
ROSANN	ROSE
ROSANNA	ROSE
ROSANNE	ROSE
ROSEL	ROSE
ROSELLA	ROSE
ROSELLE	ROSE
ROSELYN	ROSE
ROSEMARIE	ROSE

ORIGINAL_WORD	REPLACEMENT_WORD
ROSEMARY	ROSE
ROSENA	ROSE
ROSENE	ROSE
ROSETTA	ROSE
ROSETTE	ROSE
ROSIE	ROSE
ROSINA	ROSE
ROSITA	ROSE
ROSLYN	ROSE
ROWLAND	ROLAND
ROX	ROXANE
ROXANA	ROXANE
ROXANNA	ROXANE
ROXANNE	ROXANE
ROXIE	ROXANE
ROXY	ROXANE
ROY	ELROY
ROZ	ROSWELL
ROZALIE	ROSE
ROZINA	ROSE

ORIGINAL_WORD	REPLACEMENT_WORD
RUBE	REUBEN
RUBEN	REUBEN
RUBERTA	ROBERTA
RUBETTA	RUBY
RUDOLF	RUDOLPH
RUDY	RUDOLPH
RUFE	GRIFFITH
RUFUS	GRIFFITH
RUIAS	URIAH
RUPERT	ROBERT
RUPERTA	ROBERTA
RUSS	RUSSELL
RUSSEL	RUSSELL
RUTHERFURD	RUTHERFORD
RUTHIE	RUTH
RYDER	RIDER
SABINE	SABINA
SADIE	SARAH
SADYE	SARAH
SAL	SALVADOR

ORIGINAL_WORD	REPLACEMENT_WORD
SALENE	SELENA
SALLIE	SARAH
SALLY	SARAH
SAMANTHA	SAM
SAMELLA	SAM
SAMMY	SAM
SAMPSON	SAM
SAMSON	SAM
SAMUEL	SAM
SAMUELA	SAM
SAMUELIA	SAM
SANBORNE	SANBORN
SANBURN	SANBORN
SANDERS	SANDY
SANDFORD	SANFORD
SANDI	SANDY
SANDOR	SANDY
SANDRA	SANDY
SARA	SARAH
SARENA	SARAH

ORIGINAL_WORD	REPLACEMENT_WORD
SARENE	SARAH
SARETTA	SARAH
SARI	SARAH
SARITA	SARAH
SAUNDERS	SANDY
SAVINA	SABINA
SAXEN	SAXON
SCHMID	SMITH
SCHMIDT	SMITH
SCHMITS	SMITH
SCHMITT	SMITH
SCHMITZ	SMITH
SCOT	SCOTT
SCOTTIE	SCOTT
SCOTTY	SCOTT
SEAMUS	JAMES
SEAN	JOHN
SEdgeWINN	SEdgeWICK
SELDA	GRISELDA
SELIG	ZELIG

ORIGINAL_WORD	REPLACEMENT_WORD
SELMA	ANSELMA
SERA	SERAPHINE
SERAFINA	SERAPHINE
SEWEL	SEWELL
SEYMOUR	MURRAY
SHAMUS	JAMES
SHANE	JOHN
SHARA	SHARON
SHARI	SHARON
SHAWN	JOHN
SHEBA	BATHSHEBA
SHEILA	SHELLEY
SHEL	SHELDON
SHELBY	SELBY
SHELL	SHELLEY
SHELLY	SHELDON
SHELTON	SHELDON
SHEP	SHEPARD
SHEPHERD	SHEPARD
SHEPLY	SHEPLEY

ORIGINAL_WORD	REPLACEMENT_WORD
SHEPP	SHEPARD
SHEPPARD	SHEPARD
SHERI	SHIRLEY
SHERM	SHERMAN
SHERRARD	SHERARD
SHERRY	CHERIE
SHERYL	SHIRLEY
SHIRL	SHIRLEY
SHIRLEE	SHIRLEY
SHIRLIE	SHIRLEY
SI	SIMON
SIB	SYBIL
SIBBIE	SYBIL
SIBBY	SYBIL
SIBEL	SYBIL
SIBELL	SYBIL
SIBIE	SYBIL
SIBYL	SYBIL
SID	SIDNEY
SIDONIA	SIDNEY

ORIGINAL_WORD	REPLACEMENT_WORD
SIDONIE	SIDNEY
SIEGFRIED	SIFFRID
SIL	PRISCILLA
SILVA	SYLVIA
SILVAN	SILAS
SILVANA	SYLVIA
SILVANUS	SILAS
SILVESTER	SILAS
SILVIA	SYLVIA
SIM	SAM
SIMEON	SIMON
SIMONETTA	SIMONE
SIMPSON	SAM
SIMSON	SAM
SOFIA	SOPHIA
SOL	SOLOMON
SOLLY	SOLOMON
SONDRA	SANDY
SONIA	SOPHIA
SONJA	SOPHIA

ORIGINAL_WORD	REPLACEMENT_WORD
SONNY	TYSON
SONYA	SOPHIA
SOPH	SOPHIA
SOPHEY	SOPHIA
SOPHI	SOPHIA
SOPHIE	SOPHIA
SOPHY	SOPHIA
SPENCE	SPENCER
SPENSER	SPENCER
SPRAGE	SPRAGUE
STACEY	STACY
STAFFARD	STAFFORD
STAFORD	STAFFORD
STAN	STANLEY
STANLEIGH	STANLEY
STEFAN	STEPHEN
STEFANIE	STEPHANIE
STEFFEN	STEPHEN
STELLA	ESTELLE
STEPHANA	STEPHANIE

ORIGINAL_WORD	REPLACEMENT_WORD
STEPHANIA	STEPHANIE
STEPHENIE	STEPHANIE
STEVE	STEPHEN
STEVEN	STEPHEN
STEVIE	STEPHEN
STEW	STEWARD
STIRLING	STERLING
STJEPAN	STEPHEN
STU	STEWARD
STUART	STEWARD
SUE	SUSAN
SUSANA	SUSAN
SUSANNA	SUSAN
SUSANNAH	SUSAN
SUSI	SUSAN
SUSIE	SUSAN
SUSSANNE	SUSAN
SUSY	SUSAN
SUZANNA	SUSAN
SUZETTA	SUSAN

ORIGINAL_WORD	REPLACEMENT_WORD
SUZIE	SUSAN
SUZY	SUSAN
SWAIN	SWAINE
SWANE	SWAINE
SYBYL	SYBIL
SYD	SIDNEY
SYDNEY	SIDNEY
SYL	SYLVIA
SYLVAN	SILAS
SYLVESTER	SILAS
SYLVIE	SYLVIA
TABBIE	TABITHA
TAD	THADDEUS
TAIT	TATE
TAITE	TATE
TALBOT	TALBOTT
TALLBOY	TALBOTT
TALLU	TALLULAH
TALLULA	TALLULAH
TAM	THOMAS

ORIGINAL_WORD	REPLACEMENT_WORD
TAMA	TAMARA
TAMMANY	THOMAS
TAMMY	THOMAS
TANYA	TANIA
TAVEY	OCTAVIUS
TAVI	OCTAVIA
TAVIA	OCTAVIA
TED	THEODORE
TEDDI	THEODORA
TEDDIE	THEODORE
TEDDY	THEODORE
TEDRIC	THEODORIC
TEENA	MARTINA
TERRENCE	TERENCE
TERRY	TERENCE
TESS	TERESA
TESSA	TERESA
TESSIE	TERESA
THACHER	THATCHER
THACKERAY	THATCHER

ORIGINAL_WORD	REPLACEMENT_WORD
THAD	THADDEUS
THAXTER	THATCHER
THEA	THEODORA
THEDA	THEODORA
THEO	THEODORE
THEOBALD	TYBALT
THEODOSIA	THEODORA
THERESA	TERESA
THERESE	TERESA
THIA	ANTHEA
THIBAUT	TYBALT
THOM	THOMAS
THOMASA	THOMASINA
THOMASINE	THOMASINA
THORMAN	THURMAN
TILDA	MATHILDA
TILLIE	MATHILDA
TILLY	MATHILDA
TIM	TIMOTHY
TIMMIE	TIMOTHY

ORIGINAL_WORD	REPLACEMENT_WORD
TINA	MARTINA
TIPPI	ZIPPORAH
TIPPIE	ZIPPORAH
TISH	LETITIA
TOBE	TOBIAS
TOBI	TOBEY
TOBIT	TOBIAS
TOBY	TOBIAS
TOINETTE	ANTONIA
TOM	THOMAS
TOMAS	THOMAS
TOMMY	THOMAS
TONI	ANTONIA
TONY	ANTHONY
TORIN	TERENCE
TORRANCE	TERENCE
TRACEY	TERESA
TRACY	TERESA
TRAVIS	TRAVERS
TRICIA	PAT

ORIGINAL_WORD	REPLACEMENT_WORD
TRINA	KATHERINE
TRISH	PAT
TRIX	BEATRICE
TRIXIE	BEATRICE
TRUDE	GERTRUDE
TRUDY	GERTRUDE
TSIPROAH	ZIPPORAH
TUDOR	THEODORE
TY	TYSON
TYBALD	TYBALT
ULRIC	ALARIC
ULRICH	ALARIC
ULRICK	ALARIC
ULRIKA	ULRICA
URANIE	URANIA
URIA	URIAH
URIEL	URIAH
URSA	URSULA
URSEL	URSULA
URSI	URSULA

ORIGINAL_WORD	REPLACEMENT_WORD
URSULETTE	URSULA
UTA	OTILIE
UZZIEL	UZIEL
VACHIL	VACHEL
VAL	VALENTINA
VALE	VAIL
VALEDA	VELDA
VALENCIA	VALENTINA
VALENTE	VALENTINE
VALENTIA	VALENTINA
VALERIA	VALENTINA
VALERIE	VALENTINA
VALIANT	VALENTINE
VALLE	VAIL
VALLIE	VALENTINA
VALORA	VALENTINA
VAN	VANESSA
VANNI	VANESSA
VARECK	WARRICK
VARICK	WARRICK

ORIGINAL_WORD	REPLACEMENT_WORD
VASHTA	VASHTI
VASTI	VASHTI
VAUGHN	VAUGHAN
VELMA	WILHELMINA
VERDIE	VERDA
VERGIL	VIRGIL
VERN	VERNON
VERNE	VERNON
VERNICE	VERNA
VERNITA	VERNA
VI	VIVIAN
VICK	VIC
VICKI	VIC
VICKY	VIC
VICTOIR	VIC
VICTOR	VIC
VICTORIA	VIC
VICTORIE	VIC
VICTORINE	VIC
VIN	VINCENT

ORIGINAL_WORD	REPLACEMENT_WORD
VINA	ALVINA
VINCE	VINCENT
VINE	VINNA
VINIA	LAVINIA
VINNY	GALVIN
VIOLA	VIOLET
VIOLETTA	VIOLET
VIOLETTE	VIOLET
VIONA	FIONNA
VIONNA	FIONNA
VIRG	VIRGIL
VIRGIE	VIRGIL
VIRGILIA	VIRGINIA
VIRGINIE	VIRGINIA
VIRGY	VIRGINIA
VITTORIO	VIC
VIV	VIVIAN
VIVI	VIVIAN
VIVIA	VIVIAN
VIVIANE	VIVIAN

ORIGINAL_WORD	REPLACEMENT_WORD
VIVIE	VIVIAN
VIVIEN	VIVIAN
VIVIENNE	VIVIAN
VLAD	VLADIMIR
VLADAMIR	VLADIMIR
VOLNY	VOLNEY
VON	YVONNE
VONN	VAUGHAN
VONNIE	YVONNE
VONNY	VERONICA
WAIN	WAYNE
WAINE	WAYNE
WALDEMAR	VLADIMIR
WALDIMAR	VLADIMIR
WALDO	VLADIMIR
WALLI	WALLACE
WALLIE	WALLACE
WALLIS	WALLACE
WALLY	WALLACE
WALSH	WALLACE

ORIGINAL_WORD	REPLACEMENT_WORD
WALT	WALLACE
WALTER	WALLACE
WALTERS	WALLACE
WEB	WEBSTER
WEBB	WEBSTER
WELLESLEY	WESLEY
WENDA	WANDA
WENDEL	WENDELL
WENDI	GWENDOLEN
WENDY	GWENDOLEN
WENONAH	WENONA
WES	WESLEY
WIATT	GUY
WIL	WILSON
WILBERT	GILBERT
WILBUR	GILBERT
WILFREDA	FREDA
WILFRID	WILFRED
WILHELM	WILLIAM
WILL	WILLIAM

ORIGINAL_WORD	REPLACEMENT_WORD
WILLET	WILLIAM
WILLIS	WILLIAM
WILLY	WILLIAM
WILMA	WILHELMINA
WIN	WINSTON
WINA	EDWINA
WINFRED	WILIFRED
WINFRID	WILIFRED
WINN	ELWIN
WINNIE	EDWINA
WINNY	WINIFRED
WINONA	WENONA
WINTON	WINSTON
WLADIMIR	VLADIMIR
WOODIE	WOODROW
WORD	WARD
WYATT	GUY
WYNE	WYNNE
WYNN	ELWIN
XENIA	XENA

ORIGINAL_WORD	REPLACEMENT_WORD
XINA	CHRIS
YANCEY	YANCY
YASMINE	JASMINE
YOLANDA	YOLANDE
YORICK	YORK
YORKE	YORK
YVETTE	YVONNE
YVON	YVES
ZABRINE	ZABRINA
ZACH	ZACHARIAH
ZACHARIAS	ZACHARIAH
ZACHARY	ZACHARIAH
ZACK	ZACHARIAH
ZANE	JOHN
ZEB	ZEBADIAH
ZEBA	ZEBADA
ZEBE	ZEBADIAH
ZEBEDEE	ZEBADIAH
ZEENA	ZENA
ZEKE	EZEKIEL

ORIGINAL_WORD	REPLACEMENT_WORD
ZELDA	GRISELDA
ZENIA	ZENA
ZEPH	ZEPHANIAH
ZERLA	ZERLINA
ZERLINE	ZERLINA
ZINA	ZINAH
ZIPPORA	ZIPPORAH
ZITA	TERESA
ZORAH	ZORA
ZORANA	ZORA
ZORINA	ZORA

KEY MODIFIERS

This table lists the original and replacement words of the KEY MODIFIERS word replacement list. Many of the replacement words are intentionally blank so that the returned values will be more fuzzy.

Original Word	Replacement Word
a	A
b	B
c	C
d	D

Original Word	Replacement Word
e	E
f	F
g	G
h	H
i	I
j	J
k	K
l	L
m	M
n	N
o	O
p	P
q	Q
r	R
s	S
t	T
u	U
v	V
w	W
x	X

Original Word	Replacement Word
y	Y
z	Z
!	
"	
#	
\$	
%	
&	
'	
(	
)	
*	
+	
,	
-	
.	
/	
:	
;	
<	

Original Word	Replacement Word
=	
>	
?	
@	
[	
\	
]	
^	
_	
,	
{	
}	
~	

ORGANIZATION_NAME_DICTIONARY

This table lists the original and replacement words of the ORGANIZATION_NAME_DICTIONARY word replacement list.

ORIGINAL_WORD	REPLACEMENT_WORD
AND	
ASSOCIATES	ASSOC

ORIGINAL_WORD	REPLACEMENT_WORD
AT	
BY	
CALIFORNIA	CALIF
CHAPTER	CHPTR
COLLEGE	COLL
COLLEGES	COLL
COMMUNITY	COMM
COMPANY	CO
COMPUTER	COMP
COMPUTING	COMP
CONSULTANTS	CONS
CORPORATION	CORP
DEPARTMENT	DEPT
DIVISION	DIV
ENGINEERING	ENGR
ENTERPRISES	ENTR
FOR	
GROUP	GRP
IN	
INCORP	INC

ORIGINAL_WORD	REPLACEMENT_WORD
INCORPORATED	INC
INDUSTRIES	IND
INDUSTRY	IND
INFORMATION	INFO
INTERNATIONAL	INTL
INTERNL	INTL
JAYNE	JANE
LABORATORIES	LAB
LABORATORY	LAB
LIMITED	LTD
MANAGEMENT	MGMT
OF	
OR	
PARTNERS	PTR
SERVICES	SVCS
SOFTWARE	SOFT
STATE	ST
SYSTEMS	SYS
TECHNOLOGIES	TECH
TECHNOLOGY	TECH

ORIGINAL_WORD	REPLACEMENT_WORD
THE	
UNIVERSITY	UNIV

PERSON_NAME_DICTIONARY

This table lists the original and replacement words of the PERSON_NAME_DICTIONARY word replacement list

ORIGINAL_WORD	REPLACEMENT_WORD
ABBEY	ABIGAIL
ABBIE	ABIGAIL
ABBY	ABIGAIL
ABE	ABRAHAM
ABIE	ABRAHAM
ABRAM	ABRAHAM
ADAMS	ADAM
ADAMSON	ADAM
ADOLF	ADOLPH
ADOLPHE	ADOLPH
ADOLPHUS	ADOLPH
ADRIA	ADRIENNE
ADRIANA	ADRIENNE
ADRIANNA	ADRIENNE

ORIGINAL_WORD	REPLACEMENT_WORD
ADRIANNE	ADRIENNE
ADRIEN	ADRIAN
AGATHE	AGATHA
AGNA	AGNES
AIMEE	AMY
AL	ALBERT
ALAINE	ELAINE
ALARICK	ALARIC
ALAYNE	ELAINE
ALBERTA	ALBERT
ALCOT	ALCOTT
ALDIN	ALDEN
ALDWIN	ALDEN
ALEC	ALEX
ALENE	AILEEN
ALEXANDER	ALEX
ALF	ALFRED
ALFIE	ALFRED
ALFONSO	ALPHONSE
ALFREDA	FREDA

ORIGINAL_WORD	REPLACEMENT_WORD
ALFY	ALFRED
ALINA	ALANA
ALINE	AILEEN
ALIS	ALICE
ALLAN	ALAN
ALLANA	ALANA
ALLEN	ALAN
ALLIE	ALICE
ALLIS	ALICE
ALLY	ALICE
ALONZO	ALPHONSE
ALPHONSO	ALPHONSE
ALVAN	ALVIN
ALYCE	ALICE
ALYS	ALICE
AMALIA	AMELIA
AMELIE	AMELIA
AMI	AMY
AMIE	AMY
ANDERSON	ANDERSEN

ORIGINAL_WORD	REPLACEMENT_WORD
ANDERSSON	ANDERSEN
ANDRE	ANDREW
ANDREANA	ANDREA
ANDY	ANDREW
ANGIE	ANGELA
ANGY	ANGELA
ANNA	ANN
ANNE	ANN
ANNIE	ANN
ANTONIO	ANTHONY
ANTONY	ANTHONY
ARABELLE	ARABELLA
ARCH	ARCHIBALD
ARCHIE	ARCHIBALD
ARCHY	ARCHIBALD
ARIANA	ARIADNE
ARIANE	ARIADNE
ARLANA	ARLENE
ARLEEN	ARLENE
ARLENA	ARLENE

ORIGINAL_WORD	REPLACEMENT_WORD
ARLETTE	ARLENE
ARLINA	ARLENE
ARLINE	ARLENE
ARMINE	ARMINA
ARNE	ARNOLD
ARNIE	ARNOLD
ARNO	ARNOLD
ART	ARTHUR
ARTIE	ARTHUR
ARTURO	ARTHUR
AUDRIE	AUDREY
AUDRY	AUDREY
AVERIL	AVERILL
AZALEA	AZALIA
AZELIA	AZALIA
BARNARD	BERNIE
BARRETT	BARRET
BECKY	REBECCA
BELINDA	LINDA
BEN	BENJAMIN

ORIGINAL_WORD	REPLACEMENT_WORD
BENJIE	BENJAMIN
BENJY	BENJAMIN
BENNIE	BENJAMIN
BENNY	BENJAMIN
BERNARD	BERNIE
BERNHARD	BERNIE
BERNI	BERNIE
BERNY	BERNIE
BERT	ALBERT
BERTIE	ALBERT
BETH	ELIZABETH
BETSY	ELIZABETH
BETTE	ELIZABETH
BETTI	ELIZABETH
BETTY	ELIZABETH
BEV	BEVERLY
BEVERLEY	BEVERLY
BEVERLIE	BEVERLY
BILL	WILLIAM
BILLE	WILLIAM

ORIGINAL_WORD	REPLACEMENT_WORD
BILLIE	WILLIAM
BILLY	WILLIAM
BLANE	BLAINE
BLAYNE	BLAINE
BOB	ROBERT
BOBBI	ROBERTA
BOBBIE	ROBERT
BOBBY	ROBERT
BONNE	BONNIE
BONNI	BONNIE
BONNY	BONNIE
BREE	AUBREY
BREN	BRENDA
BRENDEN	BRENDAN
BRENDON	BRENDAN
BRET	BRETT
BREY	AUBREY
BRIGETTE	BRIDGET
BRYAN	BRIAN
BRYCE	BRICE

ORIGINAL_WORD	REPLACEMENT_WORD
BUD	BUDD
BUDDY	BUDD
CALVERT	CALVIN
CAMELLA	CAMILLA
CAMELLIA	CAMILLA
CAMILLE	CAMILLA
CAMPBALL	CAMPBELL
CANDICE	CANDACE
CARLOTTA	CHARLOTTE
CARLY	CARLA
CARMELA	CARMEL
CAROLE	CAROL
CAROLINE	CAROL
CAROLLE	CAROL
CAROLYN	CAROL
CARYL	CAROL
CASSANDRE	CASSANDRA
CASSIE	CASSANDRA
CATHARINE	KATHERINE
CATHERINE	KATHERINE

ORIGINAL_WORD	REPLACEMENT_WORD
CATHLEEN	KATHERINE
CECILE	CECILIA
CELESTA	CELESTE
CELESTINE	CELESTE
CHAD	CHADWICK
CHANCELLOR	CHAUNCEY
CHANCELOR	CHAUNCEY
CHARLEY	CHARLES
CHARLIE	CHARLES
CHERYL	CHERIE
CHET	CHESTER
CHRISTIAN	CHRIS
CHRISTOPHER	CHRIS
CHUCK	CHARLES
CINDY	CYNTHIA
CLAIRE	CLAIR
CLARKE	CLARK
CLAY	CLAYTON
COLE	COLEMAN
COLEEN	COLLEEN

ORIGINAL_WORD	REPLACEMENT_WORD
COLLETTE	COLETTE
COLMAN	COLEMAN
CONNI	CONNIE
CONSUELO	CONSUELA
CORY	COREY
CURT	CURTIS
CY	CYRUS
CYNTH	CYNTHIA
CYNTHIE	CYNTHIA
DAISIE	DAISY
DAMIAN	DAMON
DANIELL	DANIEL
DAPHIE	DAPHNE
DARLEEN	DARLENE
DARLINE	DARLENE
DARRYL	DARRELL
DAVE	DAVID
DAVIE	DAVID
DAVY	DAVID
DEANE	DEAN

ORIGINAL_WORD	REPLACEMENT_WORD
DEANNA	DIANA
DEB	DEBORAH
DEBBIE	DEBORAH
DEBBY	DEBORAH
DEBORA	DEBORAH
DEBRA	DEBORAH
DELORES	DOLORES
DELORIS	DOLORES
DELPHINIA	DELPHINE
DENICE	DENISE
DENIS	DENNIS
DENNIE	DENNIS
DENNISON	DENNIS
DENNY	DENNIS
DENY	DENNIS
DENYS	DENNIS
DEREK	THEODORIC
DERRICK	THEODORIC
DIANE	DIANA
DIANNA	DIANA

ORIGINAL_WORD	REPLACEMENT_WORD
DIANNE	DIANA
DICK	RICHARD
DICKY	RICHARD
DIERDRE	DEIDRE
DIMITRI	DEMETRIUS
DINA	DINAH
DIX	DIXIE
DMITRI	DEMETRIUS
DOLORA	DOLORES
DOM	DOMINIC
DOMINIQUE	DOMINICA
DON	DONALD
DONA	DONNA
DONINICK	DOMINIC
DONN	DONALD
DONNY	DONALD
DOREEN	DORENE
DORINE	DORENE
DORTHY	DOROTHY
DOUG	DOUGLAS

ORIGINAL_WORD	REPLACEMENT_WORD
DREW	ANDREW
DWANE	DUANE
DWAYNE	DUANE
EARLE	EARL
EDDIE	ED
EDDY	ED
EDISON	ED
EDMOND	ED
EDMUND	ED
EDUARD	ED
EDWARD	ED
EDWIN	ED
EDYTHE	EDITH
EFREM	EPHRAIM
EILEEN	AILEEN
ELANA	ELAINE
ELAYNE	ELAINE
ELDEN	ELDON
ELDRED	EDDRIDGE
ELDRID	EDDRIDGE

ORIGINAL_WORD	REPLACEMENT_WORD
ELDWEN	ELDWIN
ELISABETH	ELIZABETH
ELISON	ELLISON
ELMIRA	ALMIRA
ELSBETH	ELIZABETH
ELSWORTH	ELLSWORTH
EM	EMILY
EMERY	EMORY
EMIE	EMMA
EMILIA	EMILY
EMILIE	EMILY
EMMETT	EMMET
EMMIE	EMMA
EMMY	EMILY
EPH	EPHRAIM
ERICK	ERIC
ERIK	ERIC
ERIKA	ERICA
ERLE	EARL
ERMINIE	ARMINA

ORIGINAL_WORD	REPLACEMENT_WORD
ERNESTA	ERNESTINE
ERNIE	ERNEST
ESTELLA	ESTELLE
EVA	EVE
EVELEEN	EVE
EVELINA	EVE
EVELINE	EVE
EVELYN	EVE
EVIE	EVE
EVITA	EVE
EZ	EZRA
FAE	FAITH
FAY	FAITH
FAYE	FAITH
FERNAND	FERDINAND
FERNANDO	FERDINAND
FIONA	FIONNA
FLETCH	FLETCHER
FOREST	FORREST
FRAN	FRANCES

ORIGINAL_WORD	REPLACEMENT_WORD
FRANCE	FRANCES
FRANCESCA	FRANCES
FRANCINE	FRANCES
FRANCIS	FRANCES
FRANK	FRANKLIN
FRED	FREDERICK
FREDDIE	FREDERICK
FREDDY	FREDERICK
FREDERIC	FREDERICK
FREDERICKSEN	FREDERIKSEN
FREDERICKSON	FREDERIKSEN
FREDIE	FREDA
FREDRIC	FREDERICK
FREDRICKSEN	FREDERIKSEN
FREDRICKSON	FREDERIKSEN
FREDRIKA	FREDERICA
FREEMON	FREEMAN
FREIDA	FREDA
FRIDA	FREDA
FRIEDA	FREDA

ORIGINAL_WORD	REPLACEMENT_WORD
GABBY	GABRIEL
GABEY	GABRIELLE
GABI	GABRIELLE
GABIE	GABRIELLE
GABRIELLA	GABRIELLE
GAEL	ABIGAIL
GAIL	ABIGAIL
GALE	ABIGAIL
GARDNER	GARDINER
GARNETT	GARNET
GARRETT	GARETT
GAYL	ABIGAIL
GENEVA	GENEVIEVE
GEOF	GEOFFREY
GEOFF	GEOFFREY
GEORGIA	GEORGIANA
GEORGIANNA	GEORGIANA
GEORGINA	GEORGIANA
GEORGINE	GEORGIANA
GERELD	GERALD

ORIGINAL_WORD	REPLACEMENT_WORD
GERRALD	GERALD
GERRY	GERALD
GERTA	GERTRUDE
GERTI	GERTRUDE
GERTIE	GERTRUDE
GERTY	GERTRUDE
GERY	GERALD
GINA	REGINA
GINE	REGINA
GISELE	GISELLE
GLADIS	GLADYS
GLENN	GLEN
GODWIN	GOODWIN
GOLDY	GOLDIE
GRACIE	GRACE
GRACYE	GRACE
GRAEME	GRAHAM
GRAY	GRAYSON
GREG	GREGORY
GREGGORY	GREGORY

ORIGINAL_WORD	REPLACEMENT_WORD
GREY	GRAYSON
GREYSON	GRAYSON
GRIFFIN	GRIFFITH
GWEN	GWENDOLEN
GWENN	GWENDOLEN
GWYN	GWENDOLEN
GWYNETH	GWENDOLEN
HADEN	HADDEN
HADRIAN	ADRIAN
HAGGAR	HAGAR
HANK	HENRY
HANSON	HANSEN
HANSSON	HANSEN
HARALD	HAROLD
HARRY	HAROLD
HELENA	HELEN
HELENE	HELEN
HELLENE	HELEN
HENRI	HENRY
HERALD	HAROLD

ORIGINAL_WORD	REPLACEMENT_WORD
HERB	HERBERT
HERBIE	HERBERT
HERELD	HAROLD
HERM	HERMAN
HERMIE	HERMAN
HERMON	HERMAN
HEROLD	HAROLD
HILLARY	HILARY
HOLLIE	HOLLY
HOWIE	HOWARD
HUEY	HUGH
HUGHIE	HUGH
HUGO	HUGH
HUMFREY	HUMPHREY
ILENE	AILEEN
ILINE	AILEEN
ILLENE	AILEEN
IMMANUEL	EMMANUEL
ISABELLA	ISABEL
ISABELLE	ISABEL

ORIGINAL_WORD	REPLACEMENT_WORD
JACOB	JAMES
JAKE	JAMES
JAMIE	JAMES
JANET	JANE
JANETTE	JANE
JARVIS	GERVASE
JASMIN	JASMINE
JASMINA	JASMINE
JEFEREY	GEOFFREY
JEFF	GEOFFREY
JEFFREY	GEOFFREY
JEMMY	JAMES
JENSON	JENSEN
JENSSON	JENSEN
JEREMIAH	JEREMY
JEROLD	GERALD
JERRY	GERALD
JERVIS	GERVASE
JESS	JESSICA
JESSE	JESSICA

ORIGINAL_WORD	REPLACEMENT_WORD
JESSI	JESSICA
JESSIE	JESSICA
JESSY	JESSICA
JIM	JAMES
JIMMIE	JAMES
JIMMY	JAMES
JOAN	JANE
JOCELIN	LYNN
JOCELYN	LYNN
JODIE	JUDITH
JODY	JUDITH
JOE	JOSEPH
JOEY	JOSEPH
JOHNNIE	JOHN
JOHNNY	JOHN
JON	JOHN
JONAH	JONAS
JONNIE	JOHN
JONNY	JOHN
JORGE	GEORGE

ORIGINAL_WORD	REPLACEMENT_WORD
JORGENSON	JORGENSEN
JOSH	JOSHUA
JOSLYN	LYNN
JUDITHA	JUDITH
JUDY	JUDITH
JULE	JULIE
JULES	JULIE
JULEY	JULIE
JULIA	JULIE
JULIANE	JULIE
JURGEN	GEORGE
JUSTINA	JUSTINE
KARLA	CARLA
KARLY	CARLA
KAROLINA	CAROL
KAROLYN	CAROL
KATE	KATHERINE
KATHARINE	KATHERINE
KATHERIN	KATHERINE
KATHIE	KATHERINE

ORIGINAL_WORD	REPLACEMENT_WORD
KATHLEEN	KATHERINE
KATHLENE	KATHERINE
KATHRYN	KATHERINE
KATHY	KATHERINE
KATIE	KATHERINE
KEMBLE	KIMBALL
KEN	KENNETH
KENDAL	KENDALL
KENDRICKS	KENDRICK
KENNY	KENNETH
KENRIC	KENDRICK
KERBY	KIRBY
KERK	KIRK
KEV	KEVIN
KILE	KYLE
KIM	KIMBALL
KIMBLE	KIMBALL
KIRBEE	KIRBY
KIRBIE	KIRBY
KIRWIN	KERWIN

ORIGINAL_WORD	REPLACEMENT_WORD
KONRAD	CONRAD
KORAL	CORAL
KRIS	CHRIS
KRISS	CHRIS
KRISTIAN	CHRIS
KURT	CURTIS
LAMOND	LAMONT
LANA	ALANA
LANCELOT	LANCE
LARAINÉ	LORRAINE
LARRY	LAWRENCE
LARS	LAWRENCE
LARZ	LAWRENCE
LAUGHTON	LAWTON
LAUREN	LAWRENCE
LAURENCE	LAWRENCE
LAURIE	LAWRENCE
LEA	LEE
LEELA	LEILA
LEELAND	LELAND

ORIGINAL_WORD	REPLACEMENT_WORD
LEIGH	LEE
LELA	LILLIAN
LELAH	LILLIAN
LEN	LEE
LENNIE	LEE
LENNY	LEE
LEO	LEE
LEONARD	LEE
LEONARDO	LEE
LEOPOLD	LEE
LEROY	ELROY
LES	LESLEY
LESLI	LESLEY
LESLIE	LESLEY
LESLY	LESLEY
LEW	LEWIS
LEWES	LEWIS
LIANA	LEANNE
LIANNE	LEANNE
LILAH	LILLIAN

ORIGINAL_WORD	REPLACEMENT_WORD
LILIA	LILLIAN
LILIAN	LILLIAN
LILLI	LILLIAN
LILLIE	LILLIAN
LILLY	LILLIAN
LILY	LILLIAN
LILYAN	LILLIAN
LINC	LINCOLN
LINDON	LYNDON
LINK	LINCOLN
LINN	LYNN
LIZ	ELIZABETH
LOLETA	LOLA
LOLITA	LOLA
LON	ALPHONSE
LORA	LAURA
LORAIN	LORRAINE
LOREN	LAWRENCE
LORETTA	LAURA
LORETTE	LAURA

ORIGINAL_WORD	REPLACEMENT_WORD
LORI	LAURA
LORIE	LAURA
LORIN	LAWRENCE
LORRIE	LAURA
LOU	LOUISE
LOUIE	LEWIS
LOUIS	LEWIS
LUCAS	LUCIUS
LUCIA	LUCY
LUCIAN	LUCIUS
LUCIE	LUCY
LUCILLA	LUCY
LUCILLE	LUCY
LUDVIG	LEWIS
LUIS	LEWIS
LUKE	LUCIUS
LYN	LYNN
LYNDA	LINDA
LYNNE	LYNN
MADDOX	MADDOCK

ORIGINAL_WORD	REPLACEMENT_WORD
MADELEINE	MADELINE
MADELENE	MADELINE
MAE	MAY
MAGGIE	MARGARET
MANDA	AMANDA
MANDIE	AMANDA
MANDY	AMANDA
MANNY	EMMANUEL
MANUEL	EMMANUEL
MARC	MARK
MARCELLA	MARCIA
MARCIE	MARCIA
MARCUS	MARK
MARCY	MARCIA
MARGE	MARGARET
MARGERY	MARGARET
MARGIE	MARGARET
MARGO	MARGARET
MARGOT	MARGARET
MARI	MARY

ORIGINAL_WORD	REPLACEMENT_WORD
MARIA	MARY
MARIAN	MARY
MARIE	MARY
MARIGOLD	MARIGOLDE
MARITA	MAURITA
MARJORIE	MARGARET
MARL	MERLIN
MARLEN	MERLIN
MARLIN	MERLIN
MARLON	MERLIN
MARSHA	MARCIA
MARSHAL	MARSHALL
MARTA	MARTHA
MARTIE	MARTHA
MARTINE	MARTINA
MARTY	MARK
MAT	MATTHEW
MATHIAS	MATTHEW
MATT	MATTHEW
MATTHIAS	MATTHEW

ORIGINAL_WORD	REPLACEMENT_WORD
MATTY	MATTHEW
MAUD	MATHILDA
MAUDE	MATHILDA
MAURICE	MURRAY
MAX	MAXIMILLIAN
MAYBELLE	MABEL
MEAGAN	MEGAN
MEAGHAN	MEGAN
MEGHAN	MEGAN
MEL	MELISSA
MELIE	AMELIA
MELISA	MELISSA
MELODIE	MELODY
MELVIN	MALVIN
MERCI	MERCEDES
MERCY	MERCEDES
MERIDITH	MEREDITH
MERL	MERLIN
MERYL	MERLE
MIKE	MICHAEL

ORIGINAL_WORD	REPLACEMENT_WORD
MINI	MINNA
MINNIE	MINNA
MINNY	MINNA
MIRABELLE	MIRABEL
MOE	MOSES
MONIQUE	MONICA
MORICE	MURRAY
MORT	MORTIMER
MORTIE	MORTIMER
MORTY	MORTIMER
MURDOCK	MURDOCH
MURREY	MURRAY
MURRY	MURRAY
MURTAGH	MURDOCH
NATALE	NATALIE
NATALEE	NATALIE
NATALIA	NATALIE
NATE	NATHANIEL
NATHALIE	NATALIE
NATHAN	NATHANIEL

ORIGINAL_WORD	REPLACEMENT_WORD
NATHANAEL	NATHANIEL
NEVIL	NEVILLE
NICK	NICHOLAS
NICKY	NICHOLAS
NICOLAS	NICHOLAS
NICOLETTE	NICOLE
NIKI	NICOLE
NIKKI	NICOLE
NORM	NORMAN
OLLIE	OLIVER
PAIGE	PAGE
PAM	PAMELA
PATRIC	PAT
PATRICIA	PAT
PATRICK	PAT
PAYNE	PAINE
PEGGY	MARGARET
PETE	PETER
PHEBE	PHILOMENA
PHIL	PHILIP

ORIGINAL_WORD	REPLACEMENT_WORD
PHILIPPE	PHILIPPA
PHILIS	PHYLLIS
PHILLIS	PHYLLIS
PHOEBE	PHILOMENA
PHYLIS	PHYLLIS
PORCIA	PORTIA
PRISILLA	PRISCILLA
QUENT	QUENTIN
QUINT	QUENTIN
QUINTIN	QUENTIN
QUINTINA	QUINTA
RACHELE	RACHEL
RACHELLE	RACHEL
RAFAEL	RAPHAEL
RALPH	RANDOLPH
RAMON	REGINALD
RAMONA	MONA
RANDAL	RANDOLPH
RANDALL	RANDOLPH
RANDY	RANDOLPH

ORIGINAL_WORD	REPLACEMENT_WORD
RAY	REGINALD
RAYMOND	REGINALD
RAYMUND	REGINALD
REBAH	REBBA
REBEKAH	REBECCA
REED	READE
REID	READE
RENATA	RENEE
REYNOLD	REGINALD
RICARDO	RICHARD
RICH	RICHARD
RICHIE	RICHARD
RICKY	RICHARD
RITCH	RICHARD
RITCHIE	RICHARD
ROB	ROBERT
ROBBIE	ROBERT
ROBBY	ROBERT
ROBERTO	ROBERT
RODERICK	ROD

ORIGINAL_WORD	REPLACEMENT_WORD
RODMANN	ROD
RODNEY	ROD
ROSETTA	ROSE
ROSETTE	ROSE
ROSIE	ROSE
ROWLAND	ROLAND
ROX	ROXANE
ROXANA	ROXANE
ROXANNA	ROXANE
ROXANNE	ROXANE
ROXIE	ROXANE
ROXY	ROXANE
ROY	ELROY
RUBEN	REUBEN
RUBERTA	ROBERTA
RUDOLF	RUDOLPH
RUDY	RUDOLPH
RUPERT	ROBERT
RUSS	RUSSELL
RUSSEL	RUSSELL

ORIGINAL_WORD	REPLACEMENT_WORD
RUTHERFURD	RUTHERFORD
RUTHIE	RUTH
RYDER	RIDER
SADYE	SARAH
SAL	SALVADOR
SALENE	SELENA
SAMANTHA	SAM
SAMMY	SAM
SAMPSON	SAM
SAMSON	SAM
SAMUEL	SAM
SAMUELA	SAM
SANDFORD	SANFORD
SANDI	SANDY
SANDRA	SANDY
SARA	SARAH
SAXEN	SAXON
SCOT	SCOTT
SCOTTIE	SCOTT
SCOTTY	SCOTT

ORIGINAL_WORD	REPLACEMENT_WORD
SEDGEWINN	SEDGEWICK
SHARA	SHARON
SHARI	SHARON
SHELBY	SELBY
SHERRY	CHERIE
SIBEL	SYBIL
SIBELL	SYBIL
SIBYL	SYBIL
SILVA	SYLVIA
SILVANA	SYLVIA
SILVIA	SYLVIA
SIMEON	SIMON
SOFIA	SOPHIA
SOL	SOLOMON
SOLLY	SOLOMON
SONDRA	SANDY
SONYA	SOPHIA
SOPHEY	SOPHIA
SOPHI	SOPHIA
SOPHIE	SOPHIA

ORIGINAL_WORD	REPLACEMENT_WORD
SOPHY	SOPHIA
SPENCE	SPENCER
SPENSER	SPENCER
SPRAGE	SPRAGUE
STACEY	STACY
STAN	STANLEY
STANLEIGH	STANLEY
STEFAN	STEPHEN
STEFANIE	STEPHANIE
STEFFEN	STEPHEN
STELLA	ESTELLE
STEPHENIE	STEPHANIE
STEVE	STEPHEN
STEVEN	STEPHEN
STEVIE	STEPHEN
STEW	STEWARD
STU	STEWARD
STUART	STEWARD
SUE	SUSAN
SUSANA	SUSAN

ORIGINAL_WORD	REPLACEMENT_WORD
SUSANNA	SUSAN
SUSANNAH	SUSAN
SUSIE	SUSAN
SUSSANNE	SUSAN
SUSY	SUSAN
SUZANNA	SUSAN
SUZIE	SUSAN
SUZY	SUSAN
SYBYL	SYBIL
SYLVIE	SYLVIA
TED	THEODORE
TEDDIE	THEODORE
TEDDY	THEODORE
TEENA	MARTINA
TERRENCE	TERENCE
TERRY	TERENCE
TESS	TERESA
TESSA	TERESA
TESSIE	TERESA
THAD	THADDEUS

ORIGINAL_WORD	REPLACEMENT_WORD
THEO	THEODORE
THERESA	TERESA
THERESE	TERESA
THOM	THOMAS
TILDA	MATHILDA
TIM	TIMOTHY
TIMMIE	TIMOTHY
TINA	MARTINA
TOBE	TOBIAS
TOBI	TOBEY
TOBY	TOBIAS
TOM	THOMAS
TOMAS	THOMAS
TOMMY	THOMAS
TONY	ANTHONY
TORIN	TERENCE
TORRANCE	TERENCE
TY	TYSON
ULRIC	ALARIC
ULRICH	ALARIC

ORIGINAL_WORD	REPLACEMENT_WORD
ULRICK	ALARIC
URIA	URIAH
VERN	VERNON
VERNE	VERNON
VERNICE	VERNA
VICK	VIC
VICKI	VIC
VICKY	VIC
VICTOIR	VIC
VICTOR	VIC
VICTORIA	VIC
VINCE	VINCENT
VIOLA	VIOLET
VIOLETTA	VIOLET
VIOLETTE	VIOLET
VIV	VIVIAN
VIVIANE	VIVIAN
VIVIEN	VIVIAN
VIVIENNE	VIVIAN
VLAD	VLADIMIR

ORIGINAL_WORD	REPLACEMENT_WORD
VLADAMIR	VLADIMIR
WALLIE	WALLACE
WALLIS	WALLACE
WALLY	WALLACE
WALT	WALLACE
WALTER	WALLACE
WEBB	WEBSTER
WELLESLEY	WESLEY
WENDY	GWENDOLEN
WENONAH	WENONA
WES	WESLEY
WILFRID	WILFRED
WILHELM	WILLIAM
WILL	WILLIAM
WILLIS	WILLIAM
WILLY	WILLIAM
WINONA	WENONA
WLADIMIR	VLADIMIR
WOODIE	WOODROW
YASMINE	JASMINE

ORIGINAL_WORD	REPLACEMENT_WORD
ZACH	ZACHARIAH
ZACHARIAS	ZACHARIAH
ZACHARY	ZACHARIAH
ZACK	ZACHARIAH
ZEKE	EZEKIEL

US_STATE_DICTIONARY

This table lists the original and replacement words for the US_STATE_DICTIONARY word replacement list. This list is only for the states in the US.

Original Word	Replacement Word
AL	ALABAMA
AK	ALASKA
AZ	ARIZONA
AR	ARKANSAS
AS	AMERICAN SAMOA
CA	CALIFORNIA
CO	COLORADO
CT	CONNECTICUT
DE	DELAWARE
DC	DISTRICT OF COLUMBIA
FL	FLORIDA

Original Word	Replacement Word
FM	FEDERATED STATES OF MICRONESIA
GA	GEORGIA
GU	GUAM
HI	HAWAII
ID	IDAHO
IL	ILLINOIS
IN	INDIANA
IA	IOWA
KS	KANSAS
KY	KENTUCKY
LA	LOUISIANA
ME	MAINE
MH	MARSHALL ISLANDS
MD	MARYLAND
MA	MASSACHUSETTS
MI	MICHIGAN
MN	MINNESOTA
MS	MISSISSIPPI
MO	MISSOURI
MP	NORTHERN MARIANA ISLANDS

Original Word	Replacement Word
MT	MONTANA
NE	NEBRASKA
NV	NEVADA
NH	NEW HAMPSHIRE
NJ	NEW JERSEY
NM	NEW MEXICO
NY	NEW YORK
NC	NORTH CAROLINA
ND	NORTH DAKOTA
OH	OHIO
OK	OKLAHOMA
OR	OREGON
PA	PENNSYLVANIA
PR	PUERTO RICO
PW	PALAU
RI	RHODE ISLAND
SC	SOUTH CAROLINA
SD	SOUTH DAKOTA
TN	TENNESSEE
TX	TEXAS

Original Word	Replacement Word
UT	UTAH
VT	VERMONT
VA	VIRGINIA
VI	VIRGIN ISLANDS
WA	WASHINGTON
WV	WEST VIRGINIA
WI	WISCONSIN
WY	WYOMING

Seeded Attributes and Transformations

This chapter covers the following topics:

- Seeded Attributes
- Seeded Transformations

Seeded Attributes

Seeded attributes are provided for the entities used in Data Quality Management: Party, Address, Contact, and Contact Point. These attributes are used for matching in the staged schema. Most of the attributes correspond to a column in a HZ table, such as HZ_PARTIES. A table exists in the staged schema for each entity, and each of the four tables has 30 custom attribute columns that you can use to add attributes that are not seeded.

Seeded attributes are defined as lookup codes, and the lookup meaning is what appears as the attribute name in the Define Attributes and Transformations page.

The staged schema also includes special logical attributes to facilitate matching for more frequently used and ambiguously defined attributes:

- **Address:** Concatenates address information from the ADDRESS1, ADDRESS2, ADDRESS3, and ADDRESS 4 columns in the HZ_LOCATIONS table
- **All Account Names:** Concatenates all account names for a party from the ACCOUNT_NAME column in the HZ_CUST_ACCOUNTS table
- **All Account Numbers:** Concatenates all account numbers for a party from the ACCOUNT_NUMBER column in the HZ_CUST_ACCOUNTS table
- **Concatenated Party Names:** Concatenates all party names including known-as names from the PARTY_NAME, KNOWN_AS, KNOWN_AS2, KNOWN_AS3, KNOWN_AS4, and KNOWN_AS5 columns in the HZ_PARTIES table
- **Phone Number Flexible Format:** Concatenates phone numbers in the format of

phone number, raw phone number, phone country code, and raw phone number from the PHONE_NUMBER, RAW_PHONE_NUMBER, PHONE_COUNTRY_CODE, and RAW_PHONE_NUMBER columns in the HZ_CONTACT_POINTS table

You cannot apply similarity algorithms to these attributes because the attributes consist of a concatenation of columns. The similarity algorithm would apply to the entire concatenation and likely produce unusable results. See: *Assigning Scores, Transformations, and Thresholds, Oracle Trading Community Architecture Administration Guide.*

Related Topics

Attributes for DQM, *Oracle Trading Community Architecture Administration Guide*

Creating Custom Attributes, *Oracle Trading Community Architecture Administration Guide*

Party Attributes

The attributes for the party entity are stored in the HZ_STAGED_PARTIES table of the staged schema. The source tables for the attribute values include HZ_PARTIES, HZ_ORGANIZATION_PROFILES, and HZ_PERSON_PROFILES. This table shows the seeded attributes and their source table from the TCA Registry.

Attribute Name	Attribute Code	Source Table
Account Number	ALL_ACCOUNT_NUMBERS	HZ_ORGANIZATION_PROFILES
All Account Names	ALL_ACCOUNT_NAMES	HZ_ORGANIZATION_PROFILES
All Party Names	PARTY_ALL_NAMES	CUSTOM
Average High Credit	AVE_HIGH_CREDIT	HZ_ORGANIZATION_PROFILES
Best Time to Begin Contact	BEST_TIME_CONTACT_BEGIN	HZ_ORGANIZATION_PROFILES or HZ_PERSON_PROFILES
Best Time to End Contact	BEST_TIME_CONTACT_END	HZ_ORGANIZATION_PROFILES or HZ_PERSON_PROFILES

Attribute Name	Attribute Code	Source Table
Branch Flag	BRANCH_FLAG	HZ_ORGANIZATION_PROFILES
Business Scope	BUSINESS_SCOPE	HZ_ORGANIZATION_PROFILES
Category Code	CATEGORY_CODE	HZ_PARTIES
CEO Name	CEO_NAME	HZ_ORGANIZATION_PROFILES
CEO Title	CEO_TITLE	HZ_ORGANIZATION_PROFILES
Competitor Flag	COMPETITOR_FLAG	HZ_PARTIES
Concatenated Party Names	PARTY_ALL_NAMES	<Logical attribute>
Congressional District Code	CONG_DIST_CODE	HZ_ORGANIZATION_PROFILES
Content Source Number	CONTENT_SOURCE_NUMBER	HZ_ORGANIZATION_PROFILES or HZ_PERSON_PROFILES
Content Source Type	CONTENT_SOURCE_TYPE	HZ_ORGANIZATION_PROFILES or HZ_PERSON_PROFILES
Control Year	CONTROL_YR	HZ_ORGANIZATION_PROFILES
Corporation Class	CORPORATION_CLASS	HZ_ORGANIZATION_PROFILES
Credit Score	CREDIT_SCORE	HZ_ORGANIZATION_PROFILES
Credit Score Age	CREDIT_SCORE_AGE	HZ_ORGANIZATION_PROFILES

Attribute Name	Attribute Code	Source Table
Credit Score Class	CREDIT_SCORE_CLASS	HZ_ORGANIZATION_PROFILES
Credit Score Commentary	CREDIT_SCORE_COMMENTARY	HZ_ORGANIZATION_PROFILES
Credit Score Commentary 2 through Credit Score Commentary 10	CREDIT_SCORE_COMMENTARY2 through CREDIT_SCORE_COMMENTARY10	HZ_ORGANIZATION_PROFILES
Credit Score Date	CREDIT_SCORE_DATE	HZ_ORGANIZATION_PROFILES
Credit Score Incident Default	CREDIT_SCORE_INCD_DEFAULT	HZ_ORGANIZATION_PROFILES
Credit Score National Percentile	CREDIT_SCORE_NATL_PERCENTILE	HZ_ORGANIZATION_PROFILES
Customer Reference	REFERENCE_USE_FLAG	HZ_PARTIES
CUSTOM ATTRIBUTE 1 through CUSTOM ATTRIBUTE 30	CUSTOM_ATTRIBUTES1 through CUSTOM_ATTRIBUTES30	CUSTOM
Date of Birth	DATE_OF_BIRTH	HZ_PERSON_PROFILES
Date of Death	DATE_OF_DEATH	HZ_PERSON_PROFILES
Debarment Indicator	DEBARMENT_IND	HZ_ORGANIZATION_PROFILES
Debarments Count	DEBARMENTS_COUNT	HZ_ORGANIZATION_PROFILES
Debarments Date	DEBARMENTS_DATE	HZ_ORGANIZATION_PROFILES
Declared Ethnicity	DECLARED_ETHNICITY	HZ_PERSON_PROFILES

Attribute Name	Attribute Code	Source Table
Disadvantaged Under Title 8A Indicator	DISADV_8A_IND	HZ_ORGANIZATION_PROFILES
Domain	DOMAIN_NAME	HZ_EMAIL_DOMAIN
Dun & Bradstreet Credit Rating	DB_RATING	HZ_ORGANIZATION_PROFILES
D-U-N-S Number	DUNS_NUMBER_C	HZ_ORGANIZATION_PROFILES
Effective End Date	EFFECTIVE_END_DATE	HZ_ORGANIZATION_PROFILES
Effective Start Date	EFFECTIVE_START_DATE	HZ_ORGANIZATION_PROFILES
E-Mail Domain	DOMAIN_NAME	CUSTOM
Enquiry D-U-N-S	ENQUIRY_DUNS	HZ_ORGANIZATION_PROFILES
Export Indicator	EXPORT_IND	HZ_ORGANIZATION_PROFILES
Failure Score	FAILURE_SCORE	HZ_ORGANIZATION_PROFILES
Failure Score Age	FAILURE_SCORE_AGE	HZ_ORGANIZATION_PROFILES
Failure Score Class	FAILURE_SCORE_CLASS	HZ_ORGANIZATION_PROFILES
Failure Score Commentary	FAILURE_SCORE_COMMENTARY	HZ_ORGANIZATION_PROFILES
Failure Score Commentary 2 through Failure Score Commentary 10	FAILURE_SCORE_COMMENTARY2 through FAILURE_SCORE_COMMENTARY10	HZ_ORGANIZATION_PROFILES

Attribute Name	Attribute Code	Source Table
Failure Score Date	FAILURE_SCORE_DATE	HZ_ORGANIZATION_PROFILES
Failure Score Incident Default	FAILURE_SCORE_INCD_DEFAULT	HZ_ORGANIZATION_PROFILES
Failure Score Override Code	FAILURE_SCORE_OVERRIDE_CODE	HZ_ORGANIZATION_PROFILES
Fiscal Year for Financial Analysis	ANALYSIS_FY	HZ_ORGANIZATION_PROFILES
Gender	GENDER	HZ_PERSON_PROFILES
Global Failure Score	GLOBAL_FAILURE_SCORE	HZ_ORGANIZATION_PROFILES
Group Type	GROUP_TYPE	HZ_PARTIES
GSA Indicator Flag	GSA_INDICATOR_FLAG	HZ_ORGANIZATION_PROFILES
Head of Household Flag	HEAD_OF_HOUSEHOLD_FLAG	HZ_PERSON_PROFILES
Highest Credit	HIGH_CREDIT	HZ_ORGANIZATION_PROFILES
Household Income	HOUSEHOLD_INCOME	HZ_PERSON_PROFILES
Household Size	HOUSEHOLD_SIZE	HZ_PERSON_PROFILES
HQ Branch Indicator	HQ_BRANCH_IND	HZ_ORGANIZATION_PROFILES
Import Indicator	IMPORT_IND	HZ_ORGANIZATION_PROFILES
Internal Flag	INTERNAL_FLAG	HZ_ORGANIZATION_PROFILES or HZ_PERSON_PROFILES

Attribute Name	Attribute Code	Source Table
Known As 1	KNOWN_AS	HZ_ORGANIZATION_PROFILES or HZ_PERSON_PROFILES
Known As 2 through Known As 5	KNOWN_AS2 through KNOWN_AS5	HZ_ORGANIZATION_PROFILES or HZ_PERSON_PROFILES
Labor Surplus Indicator	LABOR_SURPLUS_IND	HZ_ORGANIZATION_PROFILES
Language Name	LANGUAGE_NAME	HZ_PARTIES
Last Known GPS	LAST_KNOWN_GPS	HZ_PERSON_PROFILES
Last Month of Fiscal Year	FISCAL_YEAREND_MONTH	HZ_ORGANIZATION_PROFILES
Legal Structure	LEGAL_STATUS	HZ_ORGANIZATION_PROFILES
Line of Business	LINE_OF_BUSINESS	HZ_ORGANIZATION_PROFILES
Local Activity Classification Code	LOCAL_ACTIVITY_CODE	HZ_ORGANIZATION_PROFILES
Local Activity Classification Code Type	LOCAL_ACTIVITY_CODE_TYPE	HZ_ORGANIZATION_PROFILES
Local Business Identifier	LOCAL_BUS_IDEN_TYPE	HZ_ORGANIZATION_PROFILES
Local Business Identifier Type	LOCAL_BUS_IDENTIFIER	HZ_ORGANIZATION_PROFILES
Marital Status	MARITAL_STATUS	HZ_PERSON_PROFILES
Marital Status Effective Date	MARITAL_STATUS_EFFECTIVE_DATE	HZ_PERSON_PROFILES

Attribute Name	Attribute Code	Source Table
Maximum Credit Currency Code	MAXIMUM_CREDIT_CURR ENCY_CORE	HZ_ORGANIZATION_PROF ILES
Maximum Credit Recommendation	MAXIMUM_CREDIT_RECO MMENDATION	HZ_ORGANIZATION_PROF ILES
Min/Max/Ave Number of Employees at Primary Address Indicator	EMP_AT_PRIMARY_ADR_M IN_IND	HZ_ORGANIZATION_PROF ILES
Minority Owned Indicator	MINORITY_OWNED_IND	HZ_ORGANIZATION_PROF ILES
Minority Type	MINORITY_OWNED_TYPE	HZ_ORGANIZATION_PROF ILES
Name	PARTY_ALL_NAMES	CUSTOM
Name	PARTY_NAME	HZ_PARTIES
Number of Employees	EMPLOYEES_TOTAL	HZ_ORGANIZATION_PROF ILES
Number of Employees at Primary Address	EMP_AT_PRIMARY_ADR	HZ_ORGANIZATION_PROF ILES
Number of Employees Estimation Indicator	EMP_AT_PRIMARY_ADR_E ST_IND	HZ_ORGANIZATION_PROF ILES
Organization Name	ORGANIZATION_NAME	HZ_ORGANIZATION_PROF ILES
Organization Type	ORGANIZATION_TYPE	HZ_ORGANIZATION_PROF ILES
Out of Business Indicator	OOB_IND	HZ_ORGANIZATION_PROF ILES
Parent/Subsidiary Indicator	PARENT_SUB_IND	HZ_ORGANIZATION_PROF ILES
Party Name	PARTY_NAME	HZ_PARTIES

Attribute Name	Attribute Code	Source Table
Party Source Details	PARTY_SOURCE_SYSTEM_REF	CUSTOM
Party Type	PARTY_TYPE	HZ_PARTIES
Paydex Norm	PAYDEX_NORM	HZ_ORGANIZATION_PROFILES
Paydex Score	PAYDEX_SCORE	HZ_ORGANIZATION_PROFILES
Paydex Score Three Months Ago	PAYDEX_THREE_MONTHS_AGO	HZ_ORGANIZATION_PROFILES
Person Academic Title	PERSON_ACADEMIC_TITLE	HZ_PERSON_PROFILES
Person First Name	PERSON_FIRST_NAME	HZ_PERSON_PROFILES
Person Initials	PERSON_INITIALS	HZ_PERSON_PROFILES
Person Last Name	PERSON_LAST_NAME	HZ_PERSON_PROFILES
Person Middle Name	PERSON_MIDDLE_NAME	HZ_PERSON_PROFILES
Person Middle Name Phonetic	MIDDLE_NAME_PHONETIC	HZ_PERSON_PROFILES
Person Name	PERSON_NAME	HZ_PERSON_PROFILES
Person Name Suffix	PERSON_NAME_SUFFIX	HZ_PERSON_PROFILES
Person Pre-Name Adjunct	PERSON_PRE_NAME_ADJUNCT	HZ_PERSON_PROFILES
Person Previous Last Name	PERSON_PREVIOUS_LAST_NAME	HZ_PERSON_PROFILES
Person Title	PERSON_TITLE	HZ_PERSON_PROFILES
Personal Identification	PERSON_IDENTIFIER	HZ_PERSON_PROFILES

Attribute Name	Attribute Code	Source Table
Personal Income	PERSONAL_INCOME	HZ_PERSON_PROFILES
Phonetic Representation of Organization Name	ORGANIZATION_NAME_PHONETIC	HZ_ORGANIZATION_PROFILES
Phonetic Representation of Person First Name	PERSON_FIRST_NAME_PHONETIC	HZ_PERSON_PROFILES
Phonetic Representation of Person Last Name	PERSON_LAST_NAME_PHONETIC	HZ_PERSON_PROFILES
Phonetic Representation of Person Name	PERSON_NAME_PHONETIC	HZ_PERSON_PROFILES
Place of Birth	PLACE_OF_BIRTH	HZ_PERSON_PROFILES
Potential Revenue of Current Fiscal Year	CURR_FY_POTENTIAL_REVENUE	HZ_ORGANIZATION_PROFILES
Potential Revenue of the Next Fiscal Year	NEXT_FY_POTENTIAL_REVENUE	HZ_ORGANIZATION_PROFILES
Preferred Functional Currency	PREF_FUNCTIONAL_CURRENCY	HZ_ORGANIZATION_PROFILES
Principal Title	PRINCIPAL_TITLE	HZ_ORGANIZATION_PROFILES
Principal Name	PRINCIPAL_NAME	HZ_ORGANIZATION_PROFILES
Private Ownership Flag	PUBLIC_PRIVATE_OWNERSHIP_FLAG	HZ_ORGANIZATION_PROFILES
Reference Use Flag	REFERENCE_USE_FLAG	HZ_PARTIES
Registration Type	REGISTRATION_TYPE	HZ_ORGANIZATION_PROFILES
Registry ID	PARTY_NUMBER	HZ_PARTIES

Attribute Name	Attribute Code	Source Table
Rent or Own Indicator	RENT_OWN_IND	HZ_ORGANIZATION_PROFILES or HZ_PERSON_PROFILES
Salutation	SALUTATION	HZ_PARTIES
SIC Code	SIC_CODE	HZ_ORGANIZATION_PROFILES
SIC Code Version	SIC_CODE_TYPE	HZ_ORGANIZATION_PROFILES
Small Business Indicator	SMALL_BUS_IND	HZ_ORGANIZATION_PROFILES
Status	STATUS	HZ_PARTIES
Tax Name	TAX_NAME	HZ_ORGANIZATION_PROFILES or HZ_PERSON_PROFILES
Tax Registration Num	TAX_REFERENCE	HZ_ORGANIZATION_PROFILES or HZ_PERSON_PROFILES
Taxpayer ID	JGZZ_FISCAL_CODE	HZ_ORGANIZATION_PROFILES or HZ_PERSON_PROFILES
Text Number of Employees at Primary Address	EMP_AT_PRIMARY_ADR_EXT	HZ_ORGANIZATION_PROFILES
Third Party Flag	THIRD_PARTY_FLAG	HZ_PARTIES
Total Number of Employees Estimation Indicator	TOTAL_EMP_EST_IND	HZ_ORGANIZATION_PROFILES
Total Number of Employees in Text Format	TOTAL_EMPLOYEES_TEXT	HZ_ORGANIZATION_PROFILES
Total Number of Employees Indicator	TOTAL_EMPLOYEES_IND	HZ_ORGANIZATION_PROFILES

Attribute Name	Attribute Code	Source Table
Total Number of Employees Min/Max/Ave Indicator	TOTAL_EMP_MIN_IND	HZ_ORGANIZATION_PROFILES
Total Payments	TOTAL_PAYMENTS	HZ_ORGANIZATION_PROFILES
Type of Personal Identification	PERSON_IDEN_TYPE	HZ_PERSON_PROFILES
Validated Flag	VALIDATED_FLAG	HZ_PARTIES
Woman Owned Index	WOMAN_OWNED_IND	HZ_ORGANIZATION_PROFILES
Year Established	YEAR_ESTABLISHED	HZ_ORGANIZATION_PROFILES
Year Incorporated	INCORP_YEAR	HZ_ORGANIZATION_PROFILES

Address Attributes

The attributes for the Address entity are stored in the HZ_STAGED_PARTY_SITES table of the staged schema. The source tables for the attribute values include HZ_LOCATIONS and HZ_PARTY_SITES. This table shows the seeded attributes and their source table from the TCA Registry.

Attribute Name	Attribute Code	Source Table
Address	Address	CUSTOM
Address 1 through Address 4	ADDRESS1 through ADDRESS4	HZ_LOCATIONS
Address Effective Date	ADDRESS_EFFECTIVE_DATE	HZ_LOCATIONS
Address Expiration Date	ADDRESS_EXPIRATION_DATE	HZ_LOCATIONS

Attribute Name	Attribute Code	Source Table
Address Phonetic Representation	ADDRESS_LINES_PHONETIC	HZ_LOCATIONS
Address Source Details	ADDR_SOURCE_SYSTEM_REF	CUSTOM
Address Source Status	STATUS	HZ_PARTY_SITES
City	CITY	HZ_LOCATIONS
CLLI Code	CLLI_CODE	HZ_LOCATIONS
Content Source Type	CONTENT_SOURCE_TYPE	HZ_LOCATIONS
Country Code	COUNTRY	HZ_LOCATIONS
County	COUNTY	HZ_LOCATIONS
CUSTOM ATTRIBUTE 1 through CUSTOM ATTRIBUTE 30	CUSTOM_ATTRIBUTES1 through CUSTOM_ATTRIBUTES30	<Custom attribute>
Floor	FLOOR	HZ_LOCATIONS
House Number	HOUSE_NUMBER	HZ_LOCATIONS
Identifying Address Flag	IDENTIFYING_ADDRESS_FLAG	HZ_PARTY_SITES
Language	LANGUAGE	HZ_LOCATIONS
Mailstop	MAILSTOP	HZ_PARTY_SITES
P.O. Box Number	PO_BOX_NUMBER	HZ_LOCATIONS
Position	POSITION	HZ_LOCATIONS
Postal Code	POSTAL_CODE	HZ_LOCATIONS
Postal Code Extension	POSTAL_PLUS4_CODE	HZ_LOCATIONS

Attribute Name	Attribute Code	Source Table
Province	PROVINCE	HZ_LOCATIONS
Sales Tax Geocode	SALES_TAX_GEOCODE	HZ_LOCATIONS
Sales Tax Inside City Limits	SALES_TAX_INSIDE_CITY_LIMITS	HZ_LOCATIONS
Site Name	PARTY_SITE_NAME	HZ_PARTY_SITES
Site Number	PARTY_SITE_NUMBER	HZ_PARTY_SITES
State	STATE	HZ_LOCATIONS
Status	STATUS	HZ_PARTY_SITES
Street	STREET	HZ_LOCATIONS
Street Number	STREET_NUMBER	HZ_LOCATIONS
Street Suffix	STREET_SUFFIX	HZ_LOCATIONS
Suite	SUITE	HZ_LOCATIONS
Validated Flag	VALIDATED_FLAG	HZ_LOCATIONS

Contact Attributes

The attributes for the Contact entity are stored in the HZ_STAGED_CONTACTS table of the staged schema. The source tables for the attribute values include HZ_ORG_CONTACTS, HZ_PERSON_PROFILES, and HZ_RELATIONSHIPS. This table shows the seeded attributes and their source table from the TCA registry.

Attribute Name	Attribute Code	Source Table
Best Time to Begin Contact	BEST_TIME_CONTACT_BEGIN	HZ_PERSON_PROFILES
Best Time to End Contact	BEST_TIME_CONTACT_END	HZ_PERSON_PROFILES

Attribute Name	Attribute Code	Source Table
Contact Name	CONTACT_NAME	CUSTOM
Contact Number	CONTACT_NUMBER	HZ_ORG_CONTACTS
Contact Source Details	CONTACT_SOURCE_SYSTEM_REF	CUSTOM
Content Source Type	CONTENT_SOURCE_TYPE	HZ_RELATIONSHIPS
CUSTOM ATTRIBUTE 1 through CUSTOM ATTRIBUTE 30	CUSTOM_ATTRIBUTES1 through CUSTOM_ATTRIBUTES30	<Custom attribute>
Date of Birth	DATE_OF_BIRTH	HZ_PERSON_PROFILES
Date of Death	DATE_OF_DEATH	HZ_PERSON_PROFILES
Decision Maker Flag	DECISION_MAKER_FLAG	HZ_ORG_CONTACTS
Directional Flag	DIRECTIONAL_FLAG	HZ_RELATIONSHIPS
Job Title	JOB_TITLE	HZ_ORG_CONTACTS
Known As	KNOWN_AS	HZ_PERSON_PROFILES
Person Academic Title	PERSON_ACADEMIC_TITLE	HZ_PERSON_PROFILES
Person First Name	PERSON_FIRST_NAME	HZ_PERSON_PROFILES
Person Initials	PERSON_INITIALS	HZ_PERSON_PROFILES
Person Last Name	PERSON_LAST_NAME	HZ_PERSON_PROFILES
Person Middle Name	PERSON_MIDDLE_NAME	HZ_PERSON_PROFILES
Person Name	PERSON_NAME	HZ_PERSON_PROFILES
Person Name Suffix	PERSON_NAME_SUFFIX	HZ_PERSON_PROFILES

Attribute Name	Attribute Code	Source Table
Person Previous Last Name	PERSON_PREVIOUS_LAST_NAME	HZ_PERSON_PROFILES
Person Title	PERSON_TITLE	HZ_PERSON_PROFILES
Personal Identification	PERSON_IDENTIFIER	HZ_PERSON_PROFILES
Personal Identification Type	PERSON_IDEN_TYPE	HZ_PERSON_PROFILES
Phonetic Representation of Person First Name	PERSON_FIRST_NAME_PHONETIC	HZ_PERSON_PROFILES
Phonetic Representation of Person Last Name	PERSON_LAST_NAME_PHONETIC	HZ_PERSON_PROFILES
Phonetic Representation of Person Name	PERSON_NAME_PHONETIC	HZ_PERSON_PROFILES
Place of Birth	PLACE_OF_BIRTH	HZ_PERSON_PROFILES
Rank	RANK	HZ_ORG_CONTACTS
Reference Use Flag	REFERENCE_USE_FLAG	HZ_ORG_CONTACTS
Relationship Type	RELATIONSHIP_TYPE	HZ_RELATIONSHIPS
Tax Name	TAX_NAME	HZ_PERSON_PROFILES
Tax Registration Num	TAX_REFERENCE	HZ_PERSON_PROFILES
Taxpayer ID	JGZZ_FISCAL_CODE	HZ_PERSON_PROFILES
Title	TITLE	HZ_ORG_CONTACTS

Contact Point Attributes

The attributes for the Contact Point entity are stored in the HZ_STAGED_CONTACT_POINTS table of the staged schema. The source tables for the attribute values is HZ_CONTACT_POINTS. This table shows the seeded attributes and their source table from the TCA Registry.

Attribute Name	Attribute Code	Source Table
Contact Point Purpose	CONTACT_POINT_PURPOSE	HZ_CONTACT_POINTS
Contact Point Source Details	CPT_SOURCE_SYSTEM_REF	CUSTOM
Contact Point Type	CONTACT_POINT_TYPE	HZ_CONTACT_POINTS
CUSTOM ATTRIBUTE 1 through CUSTOM ATTRIBUTE 30	CUSTOM_ATTRIBUTES1 through CUSTOM_ATTRIBUTES30	<Custom attribute>
EDI ECE TP Location Code	EDI_ECE_TP_LOCATION_CODE	HZ_CONTACT_POINTS
EDI ID Number	EDI_ID_NUMBER	HZ_CONTACT_POINTS
EDI Payment Format	EDI_PAYMENT_FORMAT	HZ_CONTACT_POINTS
EDI Payment Method	EDI_PAYMENT_METHOD	HZ_CONTACT_POINTS
EDI Remittance Instruction	EDI_REMITTANCE_INSTRUCTION	HZ_CONTACT_POINTS
EDI Remittance Method	EDI_REMITTANCE_METHOD	HZ_CONTACT_POINTS
EDI TP Header ID	EDI_TP_HEADER_ID	HZ_CONTACT_POINTS
EDI Transaction Handling	EDI_TRANSACTION_HANDLING	HZ_CONTACT_POINTS
E-Mail Address	EMAIL_ADDRESS	HZ_CONTACT_POINTS
E-Mail Format	EMAIL_FORMAT	HZ_CONTACT_POINTS
Last Contact Day and Time	LAST_CONTACT_DT_TIME	HZ_CONTACT_POINTS
Phone Area Code	PHONE_AREA_CODE	HZ_CONTACT_POINTS
Phone Calling Calendar	PHONE_CALLING_CALENDAR	HZ_CONTACT_POINTS

Attribute Name	Attribute Code	Source Table
Phone Country Code	PHONE_COUNTRY_CODE	HZ_CONTACT_POINTS
Phone Extension	PHONE_EXTENSION	HZ_CONTACT_POINTS
Phone Line Type	PHONE_LINE_TYPE	HZ_CONTACT_POINTS
Phone Number	PHONE_NUMBER	HZ_CONTACT_POINTS
Phone Number	FLEX_FORMAT_PHONE_NUMBER	CUSTOM
Primary Flag	PRIMARY_FLAG	HZ_CONTACT_POINTS
Phone Number	RAW_PHONE_NUMBER	HZ_CONTACT_POINTS
Status	STATUS	HZ_CONTACT_POINTS
Phone Type	TELEPHONE_TYPE	HZ_CONTACT_POINTS
Telex Number	TELEX_NUMBER	HZ_CONTACT_POINTS
Time Zone	TIME_ZONE	HZ_CONTACT_POINTS
URL	URL	HZ_CONTACT_POINTS
Web Site	URL	HZ_CONTACT_POINTS
Web Type	WEB_TYPE	HZ_CONTACT_POINTS

Seeded Transformations

Transformations are preconfigured for the entities of Party, Address, Contact, and Contact Point. You can also create your own transformations.

Transformations, seeded or not, can also contain word replacements. See: Word Replacements, *Oracle Trading Community Architecture Administration Guide*.

Note: The EXACT transformation, as well as other transformations that include EXACT, replaces non-English characters, for example á with a, ü and û with u, ô with o, and é with e.

This table shows the seeded transformations, the function and purpose of each, as well as examples of the transformation.

Transformation Name	PL/SQL Function Name	Operations	Purpose	Example Input	Example Output
CLEANSE	HZ_TRANS_PKG.CLEANSE	Applies EXACT. Reduces any double letters to single letters. Removes all non-leading vowels. Replaces vowels that have a prepending % with a %.	To catch incorrect vowel usage and typing errors.	D' Angello	D ANGL
CLEANSE (EMAIL) + WRDOMAIN	HZ_TRANS_PKG.CLEANSED_EMAIL	Applies EXACT. Applies the DOMAIN_NAME_DICTIONARY word replacement list. Applies CLEANSE.	To catch incorrect vowel usage and typing errors. as well as mistakes with domain names.	joe.smith@oracle.com	J SMTH ORCL
CLEANSE (URL) + WRDOMAIN	HZ_TRANS_PKG.CLEANSED_URL	Applies EXACT (URL). Applies the DOMAIN_NAME_DICTIONARY word replacement list. Applies CLEANSE. Removes leading and trailing spaces.	To catch incorrect vowel usage and typing errors. as well as mistakes with domain names.	http://ww.oracle.com	ORCL
CLEANSE + WRADDRESS	HZ_TRANS_PKG.BASIC_CLEANSE_WADDRESS	Applies EXACT. Applies the ADDRESS_DICTIONARY word replacement list. Applies CLEANSE.	Clean and replace words for addresses.	300 Oracle Pkwy.	300 ORCL PRKWY

Transformation Name	PL/SQL Function Name	Operations	Purpose	Example Input	Example Output
CLEANSE + WRNAMES	HZ_TRANS_PKG .BASIC_CLEANSE_WRNAMES	Applies EXACT. Applies the ORGANIZATION_NAME_DICTIONARY or PERSON_NAME_DICTIONARY word replacement list depending on party type. Applies CLEANSE.	Clean and replace words for organization names.	Transform Corp.	TRNSFRM CRPRTN
CLEANSE + WRNAMES + REVERSE	HZ_TRANS_PKG .REVERSE_WRNAMES_CLEANSE (for person or organization names)	Applies REVERSE. Applies the ORGANIZATION_NAME_DICTIONARY and then PERSON_NAME_DICTIONARY. Applies CLEANSE.	To catch incorrect ordering of words, as well as nicknames, abbreviations, and spelling variations for person or organization names and incorrect vowel usage and typing errors.	D' Angello Mike	MCHL D ANGL
CLEANSE + WRORGANIZATION	HZ_TRANS_PKG .WRORG_CLEANSE	Applies CLEANSE. Applies the ORGANIZATION_NAME_DICTIONARY word replacement list.	To catch nicknames, abbreviations, and spelling variations for organization names as well as incorrect vowel usage and typing errors.	Transform Corp	TRNSFRM CRPRTN
CLEANSE + WRPERSON	HZ_TRANS_PKG .BASIC_CLEANSE_WRPERS	Applies EXACT. Applies the PERSON_NAME_DICTIONARY word replacement list. Applies CLEANSE.	Clean and replace words for person names.	Bob S. Smith	RBRT S SMTH

Transformation Name	PL/SQL Function Name	Operations	Purpose	Example Input	Example Output
CLEANSE + WRPERSON + REVERSE	HZ_TRANS_PKG .REVERSE_WRP ERSON_CLEANSE	Applies REVERSE. Applies the PERSON_NAME_DICTI ONARY. Applies CLEANSE.	Clean and reverses person names.	Smith Bob	Bob Smith
CLEANSE + WRSTATE	HZ_TRANS_PKG .WRSTATE_CLE ANSE	Applies CLEANSE. Applies the US_STATE_DICTIO NARY word replacement list.	To catch spelling errors and incorrect abbreviations for state as well as incorrect vowel usage and typing errors.	CA	CLFRN
CLEANSE SPECIAL + WRADDRESS	HZ_TRANS_PKG .WRADDRESS_C LEANSE	Applies EXACT and EXACT SPECIAL, if different. Applies the ADDRESS_DICTIO NARY word replacement list. Applies CLEANSE.	To catch abbreviations for words used in the address as well as incorrect vowel usage and typing errors.	W. Main St.	WST MN STRT
CLEANSE SPECIAL + WRNAMES	HZ_TRANS_PKG .WRNAMES_CLE ANSE	Applies EXACT and EXACT SPECIAL, if different. Applies the ORGANIZATION_NAM E_DICTIO NARY or PERSON_NAME_DICTI ONARY word replacement list depending on party type. Applies CLEANSE.	To transform and clean organization names.	Poot's Coffee	PTS CF PTS

Transformation Name	PL/SQL Function Name	Operations	Purpose	Example Input	Example Output
CLEANSE SPECIAL + WRPERSON	HZ_TRANS_PKG .WRPERSON_CL EANSE	Applies EXACT and EXACT SPECIAL, if different. Applies the PERSON_NAME_DICTI ONARY word replacement list. Applies CLEANSE.	To transform and clean person names.	Bob Smith	RBRT SMTH RBRT
CLUSTER	HZ_TRANS_PKG .CLUSTER_WOR D	Applies EXACT. Removes all except the first 3 characters of the first 2 words.	To catch spelling errors at the end of the word and minor format errors.	D' Angello	D ANGE
CLUSTER + WRNAMES	HZ_TRANS_PKG .WRNAMES_CL USTER	Applies EXACT. Applies the ORGANIZATION_NAM E_DICTIONARY or PERSON_NAME_DICTI ONARY word replacement list depending on party type. Applies CLUSTER.	To catch nicknames, abbreviations, and spelling variations for person or organization names as well as spelling errors at the end of the word and minor format errors.	D' Angello Corp	D ANGE
CLUSTER + WRNAMES + REVERSE	HZ_TRANS_PKG .REVERSE_WRN AMES_CLUSTER (for person or organization names)	Applies REVERSE. Applies the ORGANIZATION_NAM E_DICTIONARY and then PERSON_NAME_DICTI ONARY. Applies CLUSTER.	To catch incorrect ordering of words, as well as nicknames, abbreviations, and spelling variations for person names and spelling errors at the end of the word and minor format errors.	Inc Mitchell	MITC INCO

Transformation Name	PL/SQL Function Name	Operations	Purpose	Example Input	Example Output
CLUSTER + WRORGANIZATION	HZ_TRANS_PKG.WRORG_CLUSTER	Applies EXACT. Applies the ORGANIZATION_NAME_DICTIONARY word replacement list. Applies CLUSTER.	To catch nicknames, abbreviations, and spelling variations for organization names as well as spelling errors at the end of the word and minor format errors.	Mitchell Inc	MITC INCO
CLUSTER + WRPERSON	HZ_TRANS_PKG.WRPERSON_CLUSTER	Applies EXACT. Applies the PERSON_NAME_DICTIONARY word replacement list. Applies CLUSTER.	To catch nicknames, abbreviations, and spelling variations for person names as well as spelling errors at the end of the word and minor format errors.	Mike D'Angello	MICH D
CLUSTER + WRPERSON + REVERSE	HZ_TRANS_PKG.REVERSE_WRPERSON_CLUSTER (for person names only)	Applies REVERSE. Applies the PERSON_NAME_DICTIONARY. Applies CLUSTER.	To catch incorrect ordering of words, as well as nicknames, abbreviations, and spelling variations for person names and spelling errors at the end of the word and minor format errors.	Inc Mitchell	MITC INCO

Transformation Name	PL/SQL Function Name	Operations	Purpose	Example Input	Example Output
CORE DOMAIN EXTRACTION	HZ_EMAIL_DOMAINS_V2PUB.CORE_DOMAIN	Extracts core domain of e-mail address.	To extract the core domain of e-mail addresses and ignore ISP e-mail domains.	Joe.smith@oracle.co.uk	ORACLE.CO.UK (if CO.UK is an E-Mail Domain Suffixes lookup code and not included in the ISP E-Mail Domains lookup type) CO.UK (if the input does not match codes in either lookup type)
EXACT	HZ_TRANS_PKG.EXACT	Capitalize all letters. Replace all non-alphanumeric characters except for a % with a space. Reduce double spaces to a single space.	To catch format errors.	D' Angello	D ANGELLO
EXACT (DATE)	HZ_TRANS_PKG.EXACT_DATE	Standardizes any date value to DD-MM-YYYY.	To enable character comparison for dates.	01-JAN-2002	01-JAN-2002
EXACT (URL)	HZ_TRANS_PKG.EXACT_URL	Capitalize all letters. Removes the <i>xyz://</i> value.	To catch case errors.	http://WWw.oracle.com	WWW.Oracle.COM

Transformation Name	PL/SQL Function Name	Operations	Purpose	Example Input	Example Output
EXACT + WRADDRESS	HZ_TRANS_PKG.BASIC_WRADDR	Applies EXACT. Applies the ADDRESS_DICTIONARY word replacement list.	To standardize address details.	300 Oracle Pkwy.	300 Oracle Parkway
EXACT + WRNAMES	HZ_TRANS_PKG.BASIC_WRNAMES	Applies EXACT. Applies the ORGANIZATION_NAME_DICTIONARY or PERSON_NAME_DICTIONARY word replacement list depending on party type.	To standardize organization names.	Transform Corp.	Transform Corporation
EXACT + WRORGANIZATION	HZ_TRANS_PKG.WRORG_EXACT	Applies EXACT. Applies the ORGANIZATION_NAME_DICTIONARY word replacement list.	To catch nicknames, abbreviations, and spelling variations for organization names.	Transform Corp	Transform CORPORATION
EXACT + WRPERS	HZ_TRANS_PKG.BASIC_WRPERS	Applies EXACT. Applies the PERSON_NAME_DICTIONARY word replacement list.	To standardize common person nicknames.	Bob Smith	Robert Smith
EXACT + WRSTATE	HZ_TRANS_PKG.WRSTATE_EXACT	Applies EXACT. Applies the US_STATE_DICTIONARY word replacement list.	To catch spelling errors and incorrect abbreviations for state.	CA	California

Transformation Name	PL/SQL Function Name	Operations	Purpose	Example Input	Example Output
EXACT SPECIAL	HZ_TRANS_PKG .RM_SPLCHAR	Capitalize all letters. Replace all non-alphanumeric characters except for a % with a space. Reduce double spaces to a single space. Remove characters .!"#&.	To catch format errors.	D.D. Angello	DD ANGELLO
EXACT SPECIAL + WRADDRESS	HZ_TRANS_PKG .WRADDRESS_EXACT	Applies EXACT and EXACT SPECIAL, if different. Applies the ADDRESS_DICTIONARY word replacement list.	To catch abbreviations for words used in the address.	W. Main St.	WEST Main STREET
EXACT SPECIAL + WRNAMES	HZ_TRANS_PKG .WRNAMES_EXACT	Applies EXACT and EXACT SPECIAL, if different. Applies the ORGANIZATION_NAME_DICTIONARY or PERSON_NAME_DICTIONARY word replacement list depending on party type.	To catch nicknames, abbreviations, and spelling variations for person or organization names.	Transform Corp	Transform CORPORATION
EXACT SPECIAL + WRPERSON	HZ_TRANS_PKG .WRPERSON_EXACT	Applies EXACT and EXACT SPECIAL, if different. Applies the PERSON_NAME_DICTIONARY word replacement list.	To catch nicknames, abbreviations, and spelling variations for person names.	Mike D' Angello	MICHAEL DANGELLO

Transformation Name	PL/SQL Function Name	Operations	Purpose	Example Input	Example Output
EXACT SPECIAL CTX	HZ_TRANS_PKG. RM_SPLCHAR_CTX	For staging context, applies EXACT SPECIAL. For search context, forces uppercase, replaces all non-alphanumeric characters with a space, removes all spaces.	To remove non-alphanumeric characters.	25-321@4	25 321 4
EXACT SPECIAL NOSPC	HZ_TRANS_PKG. RM_SPLCHAR_BLANKS	Capitalize all letters. Replace all non-alphanumeric characters except for a % with a space. Reduce double spaces to a single space. Remove characters .! "\$&, and removes all spaces.	To remove blanks before or after special characters.	joe.smith@oracle.com	joe.smith@oracle.com
EXACT STRING	HZ_TRANS_PKG. EXACT_PADDED	Does basic sanitization as per EXACT. Prepends and appends a # to the sanitized string to disable contains matching.	To capture the exact string and catch format errors.	D'Angello	#D ANGELLO #
FORCE UPPERCASE ONLY	HZ_TRANS_PKG. EXACT_EMAIL	Capitalize all letters.	To catch case errors.	Joe.smith@oracle.com	JOE.SMITH@ORACLE.COM

Transformation Name	PL/SQL Function Name	Operations	Purpose	Example Input	Example Output
FULL DOMAIN EXTRACTION	HZ_EMAIL_DOMAINS_V2PUB.FULL_DOMAIN	Extracts full domain of e-mail address.	To extract the full domain of e-mail addresses and ignore ISP e-mail domains.	Joe.smith@oracle.co.uk	ORACLE.CO.UK (if the input does not match codes in the ISP E-Mail Domains lookup type)
REVERSE	HZ_TRANS_PKG.REVERSE_NAME	Applies EXACT. Reorders the first and last words of the string.	To catch incorrect ordering of words.	Madison Mitchell	Mitchell Madison
REVERSE PHONE NUMBER	HZ_TRANS_PKG.REVERSE_PHONE_NUMBER	Applies EXACT. Reverses the string. Replaces any alphanumeric characters with their corresponding numbers as per a telephone keypad.	To reverse the phone number.	1 (650)555-2325	5432555056 1
SOUNDEX	HZ_TRANS_PKG.SOUNDX	Applies EXACT. Applies the Soundex Algorithm.	To catch spelling errors.	Smith	S260

Related Topics

Transformations Overview, *Oracle Trading Community Architecture Administration Guide*

Creating Custom Transformations, *Oracle Trading Community Architecture Administration Guide*

Seeded Match Rules

This chapter covers the following topics:

- Seeded Match Rules
- BULK MATCH: IDENTICAL ORGANIZATIONS
- BULK MATCH: IDENTICAL PARTIES
- BULK MATCH: IDENTICAL PERSONS
- CREDIT MANAGEMENT SEARCH
- DL ADDRESS AND RELATIONSHIP SEARCH
- DL ADDRESS DEFAULT
- DL RELATIONSHIP DEFAULT
- DL SMART SEARCH
- DL SYSTEM DUPLICATE IDENTIFICATION
- HZ_CONTACT_ADV_SEARCH_MATCH_RULE
- HZ_CONTACT_SIMPLE_SEARCH_RULE
- HZ_ORG_ADV_SEARCH_RULE
- HZ_ORG_SIMPLE_SEARCH_RULE
- HZ_PERSON_ADVANCED_SEARCH_MATCH_RULE
- HZ_PERSON_SIMPLE_SEARCH_RULE
- RM SEARCH RULE
- SAMPLE: ADDRESS_ORGANIZATIONS
- SAMPLE: ADDRESS_PERSONS
- SAMPLE: ADVANCED SEARCH RULE
- SAMPLE: BASIC SEARCH RULE
- SAMPLE: ORGANIZATIONS_OPTIMIZED

- SAMPLE: PERSON_OPTIMIZED
- SAMPLE: SEARCH
- SAMPLE: SEARCH ADDRESS ORGANIZATIONS EXACT
- SAMPLE: SEARCH EXACT
- SAMPLE: SEARCH SIMILAR ORGANIZATION EXACT
- SAMPLE: SEARCH SIMILAR PERSON EXACT
- SAMPLE: SIMILAR_ORGANIZATION
- SAMPLE: SIMILAR_PERSON

Seeded Match Rules

Data Quality Management provides generic seeded match rules that you can use or base your custom match rules on. Other match rules are seeded for specific applications or features, but can be used otherwise depending on your business needs. See:

- General Match Rules, page 7-2
- Feature-Specific Match Rules, page 7-4

Important: You must compile all seeded match rules before you can use them. See: *Compiling Match Rules, Oracle Trading Community Architecture Administration Guide*.

Related Topics

Match Rules Overview, *Oracle Trading Community Architecture Administration Guide*

General Match Rules

Bulk Duplicate Identification

You can use these three generic seeded match rules to identify duplicates, in bulk:

- That currently exist within your TCA Registry
- Between interface tables and the TCA Registry

For example, you can use match rules with the Bulk Duplicate Identification purpose for batch de-duplication and Registry de-duplication in TCA Bulk Import.

- BULK MATCH: IDENTICAL ORGANIZATIONS, page 7-5

- BULK MATCH: IDENTICAL PARTIES, page 7-7
- BULK MATCH: IDENTICAL PERSONS, page 7-10

Match rules with this purpose are used in the bulk duplicate identification process of DQM. See: Bulk Duplicate Identification, *Oracle Trading Community Architecture Administration Guide* and Bulk Duplicate Identification Matching Process, *Oracle Trading Community Architecture Administration Guide*.

Expanded Duplicate Identification

You can use these nine generic seeded match rules to identify duplicates that currently exist within your TCA Registry, for example, through batch duplicate identification:

- DL ADDRESS DEFAULT, page 7-16
- DL RELATIONSHIP DEFAULT, page 7-18
- DL SYSTEM DUPLICATE IDENTIFICATION, page 7-23
- SAMPLE: ADDRESS_ORGANIZATIONS, page 7-41
- SAMPLE: ADDRESS_PERSONS, page 7-42
- SAMPLE: ORGANIZATIONS_OPTIMIZED, page 7-50
- SAMPLE: PERSON_OPTIMIZED, page 7-52
- SAMPLE: SIMILAR_ORGANIZATION, page 7-65
- SAMPLE: SIMILAR_PERSON, page 7-67

Search

You can use these sixteen generic seeded match rules for search functionality:

- CREDIT MANAGEMENT SEARCH, page 7-12
- DL ADDRESS AND RELATIONSHIP SEARCH, page 7-14
- DL SMART SEARCH, page 7-21
- HZ_CONTACT_ADV_SEARCH_MATCH_RULE, page 7-25
- HZ_CONTACT_SIMPLE_SEARCH_RULE, page 7-27
- HZ_ORG_ADV_SEARCH_RULE, page 7-29
- HZ_ORG_SIMPLE_SEARCH_RULE, page 7-31

- HZ_PERSON_ADVANCED_SEARCH_MATCH_RULE, page 7-33
- HZ_PERSON_SIMPLE_SEARCH_RULE, page 7-36
- SAMPLE: ADVANCED SEARCH RULE, page 7-44
- SAMPLE: BASIC SEARCH RULE, page 7-47
- SAMPLE: SEARCH, page 7-53
- SAMPLE: SEARCH ADDRESS ORGANIZATIONS EXACT, page 7-56
- SAMPLE: SEARCH EXACT, page 7-57
- SAMPLE: SEARCH SIMILAR ORGANIZATION EXACT, page 7-61
- SAMPLE: SEARCH SIMILAR PERSON EXACT, page 7-63

Related Topics

Seeded Match Rules, page 7-2

Feature-Specific Match Rules

Relationship Manager

The RM SEARCH RULE seeded match rule is provided specifically for Relationship Manager to search for existing relationships. See:

- RM SEARCH RULE, page 7-38
- Setting Up Relationship Manager, *Oracle Trading Community Architecture Administration Guide*.

Oracle Customer Data Librarian De-Duplication

Five seeded match rules are provided specifically for de-duplication in Oracle Customer Data Librarian. You can use or base your custom match rules on any of these:

- DL ADDRESS AND RELATIONSHIP SEARCH, page 7-14
- DL ADDRESS DEFAULT, page 7-16
- DL RELATIONSHIP DEFAULT, page 7-18
- DL SMART SEARCH, page 7-21
- DL SYSTEM DUPLICATE IDENTIFICATION, page 7-23

You can use these seeded match rules for profile options used to set up de-duplication.
See: Setting Up De-Duplication, *Oracle Customer Data Librarian Implementation Guide*.

Organization and Person Search

Four seeded match rules are provided specifically for simple and advanced searches of organizations and persons. For example, you can use these match rules to set profile options for the searches in Customers Online.

- HZ_ORG_ADV_SEARCH_RULE, page 7-29
- HZ_ORG_SIMPLE_SEARCH_RULE, page 7-31
- HZ_PERSON_ADVANCED_SEARCH_MATCH_RULE, page 7-33
- HZ_PERSON_SIMPLE_SEARCH_RULE, page 7-36

Oracle Credit Management

The CREDIT MANAGEMENT SEARCH match rule is seeded specifically for features in Oracle Credit Management.

Oracle Receivables

These match rules are seeded specifically for features in Oracle Receivables.

- SAMPLE: BASIC SEARCH RULE
- SAMPLE: ADVANCED SEARCH RULE

See: Seeded Search Match Rules, *Oracle Receivables Reference Guide*.

Related Topics

Seeded Match Rules, page 7-2

BULK MATCH: IDENTICAL ORGANIZATIONS

The BULK MATCH: IDENTICAL ORGANIZATIONS match rule identifies duplicate parties of type Organization in bulk.

Purpose: Bulk Duplicate Identification

Search Operator: Match Any Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation
Address	Address	No	EXACT + WRADDRESS
Contact Name	Contact	No	EXACT + WRPERSON
D-U-N-S Number	Party	No	EXACT
Name	Party	No	EXACT + WRNAMES
Party Type	Party	Yes	EXACT
Phone Number	Contact Point	No	REVERSE PHONE NUMBER
Postal Code	Address	Yes	EXACT SPECIAL NOSPC
SIC Code	Party	Yes	EXACT
Taxpayer ID	Party	No	EXACT SPECIAL
Web Site	Contact Point	No	CLEANSE (URL) + WRDOMAIN

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	175
Override Threshold	
Automatic Merge Threshold	250

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation	Weight (%)
Address	Address	100	EXACT + WRADDRESS	100
City	Address	15	EXACT	100
Contact Name	Contact	20	EXACT STRING	100
			EXACT + WRPERSON	90
Country Code	Address	5	EXACT	100
D-U-N-S Number	Party	200	EXACT	100
Job Title	Contact	10	EXACT	100
Name	Party	80	EXACT STRING	100
			EXACT + WRNAMES	90
Phone Number	Contact Point	70	EXACT SPECIAL	100
			REVERSE PHONE NUMBER	100
State	Address	5	EXACT + WRSTATE	100
Taxpayer ID	Party	200	EXACT SPECIAL	100
Web Site	Contact point	20	CLEANSE (URL) + WRDOMAIN	0
			EXACT (URL)	100

BULK MATCH: IDENTICAL PARTIES

The BULK MATCH: IDENTICAL PARTIES match rule identifies duplicate parties in bulk.

Purpose: Bulk Duplicate Identification

Search Operator: Match Any Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation
Address	Address	No	EXACT + WRADDRESS
Contact Name	Contact	No	EXACT + WRPERSON
D-U-N-S Number	Party	No	EXACT
E-Mail Address	Contact Point	No	FORCE UPPERCASE ONLY
Name	Party	No	EXACT + WRNAMES
Party Type	Party	Yes	EXACT
Phone Number	Contact Point	No	REVERSE
Postal Code	Address	Yes	EXACT SPECIAL NOSPC
SIC Code	Party	Yes	EXACT
Taxpayer ID	Party	No	EXACT SPECIAL
Web Site	Contact Point	No	EXACT (URL)

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	175
Override Threshold	
Automatic Merge Threshold	300

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation	Weight (%)
Address	Address	100	EXACT + WRADDRESS	100
City	Address	15	EXACT	100
Contact Name	Contact	20	EXACT STRING	100
			EXACT + WRPERSONE	90
Country Code	Address	5	EXACT	100
D-U-N-S Number	Party	200	EXACT	100
E-Mail Address	Contact Point	60	FORCE UPPERCASE ONLY	100
Job Title	Contact	10	EXACT	100
Name	Party	80	EXACT STRING	100
			EXACT + WRNAMES	90
Phone Number	Contact Point	70	EXACT	100
			Reverse	100

Attribute Name	Entity	Score	Transformation	Weight (%)
State	Address	5	EXACT + WRSTATE	100
Taxpayer ID	Party	200	EXACT SPECIAL	100
Web Site	Contact point	20	EXACT (URL)	100

BULK MATCH: IDENTICAL PERSONS

The BULK MATCH: IDENTICAL PERSONS match rule identifies duplicate parties of type Person in bulk.

Purpose: Bulk Duplicate Identification

Search Operator: Match Any Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation
Address	Address	No	EXACT + WRADDRESS
E-Mail Address	Contact Point	No	FORCE UPPERCASE ONLY
Name	Party	No	EXACT + WRNAMES
Party Type	Party	Yes	EXACT
Phone Number	Contact Point	No	REVERSE PHONE NUMBER
Postal Code	Address	Yes	EXACT SPECIAL NOSPC
Taxpayer ID	Party	No	EXACT SPECIAL

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	175
Override Threshold	
Automatic Merge Threshold	250

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation	Weight (%)
Address	Address	100	EXACT + WRADDRESS	100
City	Address	5	EXACT	100
Country	Address	5	EXACT	100
E-Mail Address	Contact Point	60	FORCE UPPERCASE ONLY	100
Name	Party	80	EXACT STRING	100
			EXACT + WRNAMES	90
Phone Number	Contact Point	70	EXACT SPECIAL	100
			REVERSE PHONE NUMBER	100
State	Address	5	EXACT + WRSTATE	100
Taxpayer ID	Party	200	EXACT SPECIAL	100

CREDIT MANAGEMENT SEARCH

The CREDIT MANAGEMENT SEARCH match rule is used for credit management search.

Purpose: Search

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation
Account Number	Party	No	EXACT SPECIAL
Address	Address	No	CLEANSE SPECIAL + WRADDRESS
All Account Names	Party	No	CLEANSE SPECIAL + WRNAMES
City	Address	No	CLEANSE
Country Code	Address	No	EXACT
D-U-N-S Number	Party	No	EXACT
Name	Party	No	CLEANSE SPECIAL + WRNAMES
Postal Code	Address	No	EXACT SPECIAL NOSPC
Registry ID	Party	No	EXACT SPECIAL
State	Address	No	CLEANSE + WRSTATE

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	75
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation	Weight (%)
Account Number	Party	100	EXACT SPECIAL	100
Address	Address	40	CLEANSE SPECIAL + WRADDRESS	80
			EXACT SPECIAL + WRADDRESS	100
All Account Names	Party	50	CLEANSE SPECIAL + WRNAMES	80
			EXACT SPECIAL + WRNAMES	100
City	Address	20	CLEANSE	80
			EXACT	100
Country Code	Address	5	EXACT	100
D-U-N-S Number	Party	100	EXACT	100
Name	Party	40	CLEANSE SPECIAL + WRNAMES	80
			EXACT SPECIAL + WRNAMES	100

Attribute Name	Entity	Score	Transformation	Weight (%)
Postal Code	Address	30	EXACT SPECIAL NOSPC	100
Registry ID	Party	100	EXACT SPECIAL	100
State	Address	10	CLEANSE + WRSTATE	80
			EXACT + WRSTATE	100

DL ADDRESS AND RELATIONSHIP SEARCH

The DL ADDRESS AND RELATIONSHIP SEARCH match rule searches for addresses or relationships for merge request mapping.

Purpose: Search

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation
Address	Address	No	CLEANSE SPECIAL + WRADDRESS
City	Address	No	CLEANSE
Country Code	Address	No	EXACT
County	Address	No	CLEANSE
Name	Party	No	CLEANSE SPECIAL + WRNAMES
Party Type	Party	No	EXACT

Attribute Name	Entity	Filter	Transformation
Postal Code	Address	No	EXACT SPECIAL NOSPC
Province	Address	No	CLEANSE
Registry ID	Party	No	EXACT SPECIAL
State	Address	No	CLEANSE + WRSTATE

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	80
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation	Weight (%)
Address	Address	50	CLEANSE SPECIAL + WRADDRESS	80
			EXACT SPECIAL + WRADDRESS	100
City	Address	30	CLEANSE	80
			EXACT	100
Country Code	Address	5	EXACT	100

Attribute Name	Entity	Score	Transformation	Weight (%)
County	Address	15	CLEANSE	80
			EXACT	100
Name	Party	40	CLEANSE SPECIAL + WRNAMES	80
			EXACT SPECIAL + WRNAMES	100
Postal Code	Address	40	EXACT SPECIAL NOSPC	100
Province	Address	20	CLEANSE	80
			EXACT	100
Registry ID	Party	80	EXACT SPECIAL	100
State	Address	20	CLEANSE + WRSTATE	80
			EXACT + WRSTATE	100

Related Topics

Addresses and Relationships, Oracle Customer Data Librarian User Guide

DL ADDRESS DEFAULT

The DL ADDRESS DEFAULT match rule identifies duplicate addresses as default suggestions for mapping addresses in merge requests.

Purpose: Expanded Duplicate Identification

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation
Address	Address	No	CLEANSE SPECIAL + WRADDRESS
City	Address	No	CLEANSE
Country Code	Address	No	EXACT
County	Address	No	CLEANSE
Postal Code	Address	No	EXACT SPECIAL NOSPC
Province	Address	No	CLEANSE
State	Address	No	CLEANSE + WRSTATE

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	85
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation	Weight (%)
Address	Address	50	CLEANSE SPECIAL + WRADDRESS	80

Attribute Name	Entity	Score	Transformation	Weight (%)
City	Address	20	EXACT SPECIAL + WRADDRESS	100
			CLEANSE	80
Country Code	Address	5	EXACT	100
			EXACT	100
County	Address	15	CLEANSE	80
			EXACT	100
Postal Code	Address	25	EXACT SPECIAL NOSPC	100
			EXACT	100
Province	Address	15	CLEANSE	80
			EXACT	100
State	Address	15	CLEANSE + WRSTATE	80
			EXACT + WRSTATE	100

Related Topics

Addresses, *Oracle Customer Data Librarian User Guide*

DL RELATIONSHIP DEFAULT

The DL RELATIONSHIP DEFAULT match rule identifies duplicate relationships as default suggestions for mapping relationships in merge requests.

Purpose: Expanded Duplicate Identification

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of

the matching process.

Attribute Name	Entity	Filter	Transformation
Address	Address	No	CLEANSE SPECIAL + WRADDRESS
City	Address	No	CLEANSE
E-Mail Address	Contact Point	No	CLEANSE (EMAIL) + WRDOMAIN
Job Title	Contact	No	EXACT
Name	Party	No	CLEANSE SPECIAL + WRNAMES
Postal Code	Address	No	EXACT SPECIAL NOSPC

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	160
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation	Weight (%)
Address	Address	30	CLEANSE SPECIAL + WRADDRESS	70

Attribute Name	Entity	Score	Transformation	Weight (%)
			EXACT SPECIAL + WRADDRESS	100
City	Address	15	CLEANSE	80
			EXACT	100
Country Code	Address	5	EXACT	100
County	Address	10	CLEANSE	80
			EXACT	100
E-Mail Address	Contact Point	160	CLEANSE (EMAIL) + WRDOMAIN	80
			FORCE UPPERCASE ONLY	100
Job Title	Contact	20	EXACT	100
Name	Party	200	CLEANSE SPECIAL + WRNAMES	80
			EXACT SPECIAL + WRNAMES	100
Phone Number	Contact Point	140	EXACT SPECIAL CTX	100
Postal Code	Address	20	EXACT SPECIAL NOSPC	100
Province	Address	10	CLEANSE	80
			EXACT	100
State	Address	10	CLEANSE + WRSTATE	80
			EXACT + WRSTATE	100

Related Topics

Relationships, *Oracle Customer Data Librarian User Guide*

DL SMART SEARCH

The DL SMART SEARCH match rule can be used for Smart Search to search for potential duplicate parties from which you create merge requests.

Purpose: Search

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation
Address	Address	No	CLEANSE SPECIAL + WRADDRESS
City	Address	No	CLEANSE
Country Code	Address	No	EXACT
Name	Party	No	CLEANSE SPECIAL + WRNAMES SOUNDEX
Party Type	Party	No	EXACT
Registry ID	Party	No	EXACT SPECIAL
SIC Code	Party	No	EXACT
State	Address	No	EXACT + WRSTATE

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	70
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation	Weight (%)
Address	Address	25	CLEANSE SPECIAL + WRADDRESS	80
		100	EXACT SPECIAL + WRADDRESS	100
City	Address	10	CLEANSE	80
			EXACT	100
Country Code	Address	5	EXACT	100
Name	Party	40	CLEANSE SPECIAL + WRNAMES	80
			EXACT SPECIAL + WRNAMES	100
			SOUNDEX	60
Party Type	Party	10	EXACT	100
Registry ID	Party	100	EXACT SPECIAL	100
SIC Code	Party	20	EXACT	100
State	Address	5	EXACT + WRSTATE	100

Related Topics

Smart Search, *Oracle Customer Data Librarian User Guide*

DL SYSTEM DUPLICATE IDENTIFICATION

The DL SYSTEM DUPLICATE IDENTIFICATION match rule can be used for System Duplicate Identification to identify duplicate parties to include in SDI batches.

Purpose: Expanded Duplicate Identification

Search Operator: Match Any Attribute

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation
Address	Address	No	CLEANSE SPECIAL + WRADDRESS
City	Address	No	CLEANSE
Country Code	Address	No	EXACT
Name	Party	No	CLEANSE SPECIAL + WRNAMES SOUNDEX
Party Type	Party	No	EXACT
Registry ID	Party	No	EXACT SPECIAL
SIC Code	Party	No	EXACT
State	Address	No	EXACT + WRSTATE

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	100
Override Threshold	
Automatic Merge Threshold	100

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation	Weight (%)
Address	Address	25	CLEANSE SPECIAL + WRADDRESS	100
City	Address	10	CLEANSE	100
Country Code	Address	5	EXACT	100
Name	Party	100	CLEANSE SPECIAL + WRNAMES	80
			EXACT SPECIAL + WRNAMES	100
			SOUNDEX	70
Party Type	Party	10	EXACT	100
Registry ID	Party	100	EXACT SPECIAL	100
SIC Code	Party	20	EXACT	100
State	Address	5	EXACT + WRSTATE	100

Related Topics

Creating System Duplicate Identification Batches, *Oracle Customer Data Librarian User Guide*

HZ_CONTACT_ADV_SEARCH_MATCH_RULE

The HZ_CONTACT_ADV_SEARCH_MATCH_RULE match rule is used for advanced searches for contacts.

Purpose: Search

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation
Address	Address	No	CLEANSE SPECIAL + WRADDRESS
City	Address	No	CLEANSE
Country Code	Address	No	EXACT
E-Mail Address	Contact Point	No	CLEANSE (EMAIL) + WRDOMAIN
Job Title	Contact	No	EXACT
Name	Party	No	CLEANSE SPECIAL + WRNAMES
Phone Number	Contact Point	60	EXACT SPECIAL CTX
Postal Code	Address	No	EXACT SPECIAL NOSPC
Province	Address	No	CLEANSE
State	Address	No	CLEANSE + WRSTATE

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	270
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation	Weight (%)
Address	Address	40	CLEANSE SPECIAL + WRADDRESS	80
			EXACT SPECIAL + WRADDRESS	100
City	Address	30	CLEANSE	80
			EXACT	100
Country Code	Address	10	EXACT	100
E-Mail Address	Contact Point	60	CLEANSE (EMAIL) + WRDOMAIN	80
			FORCE UPPERCASE ONLY	100
Job Title	Contact	20	EXACT	100
Name	Party	40	CLEANSE SPECIAL + WRNAMES	80
			EXACT SPECIAL + WRNAMES	100

Attribute Name	Entity	Score	Transformation	Weight (%)
Phone Number	Contact Point	60	EXACT SPECIAL CTX	100
Postal Code	Address	40	EXACT SPECIAL NOSPC	100
Province	Address	20	CLEANSE	80
			EXACT	100
State	Address	20	CLEANSE + WRSTATE	80
			EXACT + WRSTATE	100

HZ_CONTACT_SIMPLE_SEARCH_RULE

The HZ_CONTACT_SIMPLE_SEARCH_RULE match rule is used for basic searches for contacts.

Purpose: Search

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation
E-Mail Address	Contact Point	No	CLEANSE (EMAIL) + WRDOMAIN
Job Title	Contact	No	EXACT
Name	Party	No	CLEANSE SPECIAL + WRNAMES

Attribute Name	Entity	Filter	Transformation
Phone Number	Contact Point	60	EXACT SPECIAL CTX

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	144
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation	Weight (%)
E-Mail Address	Contact Point	60	CLEANSE (EMAIL) + WRDOMAIN	80
			FORCE UPPERCASE ONLY	100
Job Title	Contact	20	EXACT	100
Name	Party	40	CLEANSE SPECIAL + WRNAMES	80
			EXACT SPECIAL + WRNAMES	100
Phone Number	Contact Point	60	EXACT SPECIAL CTX	100

HZ_ORG_ADV_SEARCH_RULE

The HZ_ORG_ADV_SEARCH_RULE match rule can be used for advanced searches of organizations, for example, the search in Customers Online.

Purpose: Search

Search Operator: Match Any Attribute

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation
Account Number	Party	No	EXACT SPECIAL
Address	Address	No	CLEANSE SPECIAL + WRADDRESS
City	Address	No	CLEANSE
Country Code	Address	No	EXACT
D-U-N-S Number	Party	No	EXACT
Name	Party	No	CLEANSE SPECIAL + WRNAMES WORD REPLACE + EXACT + REVERSE
Phone Number	Contact Point	No	EXACT SPECIAL CTX
Postal Code	Address	No	EXACT SPECIAL NOSPC
Province	Address	No	CLEANSE
Registry ID	Party	No	EXACT SPECIAL

Attribute Name	Entity	Filter	Transformation
State	Address	No	CLEANSE + WRSTATE
Taxpayer ID	Party	No	EXACT SPECIAL
Web Site	Contact Point	No	CLEANSE (URL) + WRDOMAIN

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	450
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation	Weight (%)
Account Number	Party	60	EXACT SPECIAL	100
Address	Address	40	CLEANSE SPECIAL + WRADDRESS	80
			EXACT SPECIAL + WRADDRESS	100
City	Address	30	CLEANSE	80
			EXACT	100
Country Code	Address	10	EXACT	100

Attribute Name	Entity	Score	Transformation	Weight (%)
D-U-N-S Number	Party	60	EXACT	100
Name	Party	40	CLEANSE SPECIAL + WRNAMES	80
			EXACT SPECIAL + WRNAMES	100
Phone Number	Contact Point	60	EXACT SPECIAL CTX	100
Postal Code	Address	40	EXACT SPECIAL NOSPC	100
Province	Address	20	CLEANSE	80
			EXACT	100
Registry ID	Party	60	EXACT SPECIAL	100
State	Address	20	CLEANSE + WRSTATE	80
			EXACT + WRSTATE	100
Taxpayer ID	Party	60	EXACT SPECIAL	100
Web Site	Contact Point	60	CLEANSE (URL) + WRDOMAIN	80
			EXACT (URL)	100

HZ_ORG_SIMPLE_SEARCH_RULE

The HZ_ORG_SIMPLE_SEARCH_RULE match rule can be used for simple searches of organizations, for example, the search in Customers Online.

Purpose: Search

Search Operator: Match Any Attribute

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation
Account Number	Party	No	EXACT SPECIAL
D-U-N-S Number	Party	No	EXACT
Name	Party	No	CLEANSE SPECIAL + WRNAMES
Registry ID	Party	No	EXACT SPECIAL
Taxpayer ID	Party	No	EXACT SPECIAL
Web Site	Contact Point	No	CLEANSE (URL) + WRDOMAIN

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	255
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation	Weight (%)
Account Number	Party	60	EXACT SPECIAL	100

Attribute Name	Entity	Score	Transformation	Weight (%)
D-U-N-S Number	Party	60	EXACT	100
Name	Party	40	CLEANSE SPECIAL + WRNAMES	80
			EXACT SPECIAL + WRNAMES	100
Registry ID	Party	60	EXACT SPECIAL	100
Taxpayer ID	Party	60	EXACT SPECIAL	100
Web Site	Contact Point	60	CLEANSE (URL) + WRDOMAIN	80
			EXACT (URL)	100

HZ_PERSON_ADVANCED_SEARCH_MATCH_RULE

The HZ_PERSON_ADVANCED_SEARCH_MATCH_RULE match rule can be used for advanced searches of persons, for example, the search in Customers Online.

Purpose: Search

Search Operator: Match Any Attribute

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation
Account Number	Party	No	EXACT SPECIAL
Address	Address	No	CLEANSE SPECIAL + WRADDRESS
City	Address	No	CLEANSE

Attribute Name	Entity	Filter	Transformation
Country	Address	No	EXACT
E-Mail Address	Contact Point	No	CLEANSE (EMAIL) + WRDOMAIN
Job Title	Contact	No	EXACT
Name	Party	No	CLEANSE SPECIAL + WRNAMES
Phone Number	Contact Point	No	EXACT SPECIAL CTX
Postal Code	Address	No	EXACT SPECIAL NOSPC
Province	Address	No	CLEANSE
Registry ID	Party	No	EXACT SPECIAL
State	Address	No	CLEANSE + WRSTATE EXACT + WRSTATE
Taxpayer ID	Party	No	EXACT SPECIAL

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	415
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the

matching process.

Attribute Name	Entity	Score	Transformation	Weight (%)
Account Number	Party	60	EXACT SPECIAL	100
Address	Address	40	CLEANSE SPECIAL + WRADDRESS	80
			EXACT SPECIAL + WRADDRESS	100
City	Address	30	CLEANSE	80
			EXACT	100
Country	Address	10	EXACT	100
E-Mail Address	Contact Point	60	CLEANSE (EMAIL) + WRDOMAIN	80
			FORCE UPPERCASE ONLY	100
Job Title	Contact	20	EXACT	100
Name	Party	40	CLEANSE SPECIAL + WRNAMES	80
			EXACT SPECIAL + WRNAMES	100
Phone Number	Contact Point	60	EXACT SPECIAL CTX	100
Postal Code	Address	40	EXACT SPECIAL NOSPC	100
Province	Address	20	CLEANSE	80
			EXACT	100
Registry ID	Party	60	EXACT SPECIAL	100

Attribute Name	Entity	Score	Transformation	Weight (%)
State	Address	20	CLEANSE + WRSTATE	80
			EXACT + WRSTATE	100
Taxpayer ID	Party	60	EXACT SPECIAL	100

HZ_PERSON_SIMPLE_SEARCH_RULE

The HZ_PERSON_SIMPLE_SEARCH_RULE match rule can be used for simple searches of persons, for example, the search in Customers Online.

Purpose: Search

Search Operator: Match Any Attribute

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation
Account Number	Party	No	EXACT SPECIAL
E-Mail Address	Contact Point	No	CLEANSE (EMAIL) + WRDOMAIN
Job Title	Contact	No	EXACT
Name	Party	No	CLEANSE SPECIAL + WRNAMES
Phone Number	Contact Point	No	EXACT SPECIAL CTX
Registry ID	Party	No	EXACT SPECIAL
Taxpayer ID	Party	No	EXACT SPECIAL

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	60
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation	Weight (%)
Account Number	Party	60	EXACT SPECIAL	100
E-Mail Address	Contact Point	60	CLEANSE (EMAIL) + WRDOMAIN	80
			FORCE UPPERCASE ONLY	100
Job Title	Contact	20	EXACT	100
Name	Party	40	CLEANSE SPECIAL + WRNAMES	80
			EXACT SPECIAL + WRNAMES	100
Phone Number	Contact Point	60	EXACT SPECIAL CTX	100
Registry ID	Party	60	EXACT SPECIAL	100
Taxpayer ID	Party	60	EXACT SPECIAL	100

RM SEARCH RULE

The RM SEARCH RULE match rule is used in Relationship Manager to determine the search criteria and results when you search for the party to manage relationships for.

Purpose: Search

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation
Address	Address	No	CLEANSE SPECIAL + WRADDRESS
City	Address	No	CLEANSE
Contact Name	Contact	No	CLEANSE SPECIAL + WRPERSON SOUNDEX
Country	Address	No	EXACT
E-Mail Address	Contact Point	No	CLEANSE (EMAIL) + WRDOMAIN
Name	Party	No	CLEANSE SPECIAL + WRNAMES SOUNDEX
Party Type	Party	Yes	EXACT
Phone Number	Contact Point	No	EXACT SPECIAL CTX
Postal Code	Address	No	EXACT SPECIAL NOSPC
Registry ID	Party	No	EXACT SPECIAL

Attribute Name	Entity	Filter	Transformation
SIC Code	Party	No	EXACT
SIC Code Version	Party	No	EXACT
State	Address	No	CLEANSE + WRSTATE
Taxpayer ID	Party	No	EXACT SPECIAL
Tax Registration Num	Party	No	EXACT SPECIAL

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	75
Override Threshold	
Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation	Weight (%)
Address	Address	40	EXACT SPECIAL + WRADDRESS	100
			CLEANSE SPECIAL + WRADDRESS	80
City	Address	10	CLEANSE	80
			EXACT	100

Attribute Name	Entity	Score	Transformation	Weight (%)
Contact Name	Contact	60	EXACT SPECIAL + WRPERSON	80
			CLEANSE SPECIAL + WRPERSON	70
			EXACT STRING	100
			SOUNDEX	60
Country	Address	10	EXACT	100
E-Mail Address	Contact Point	80	CLEANSE (EMAIL) + WRDOMAIN	80
			FORCE UPPERCASE ONLY	100
Name	Party	60	CLEANSE SPECIAL + WRNAMES	80
			EXACT SPECIAL + WRNAMES	100
			SOUNDEX	60
Phone Number	Contact Point	80	EXACT SPECIAL CTX	90
Postal Code	Address	15	EXACT SPECIAL NOSPC	100
Registry ID	Party	100	EXACT SPECIAL	100
SIC Code	Party	25	EXACT	100
SIC Code Version	Party	25	EXACT	100
State	Address	20	EXACT + WRSTATE	100

Attribute Name	Entity	Score	Transformation	Weight (%)
			CLEANSE + WRSTATE	80
Taxpayer ID	Party	60	EXACT SPECIAL	100
Tax Registration Num	Party	100	EXACT SPECIAL	100

Related Topics

Searching for Parties and Viewing Results, *Oracle Trading Community Architecture User Guide*

SAMPLE: ADDRESS_ORGANIZATIONS

The SAMPLE: ADDRESS_ORGANIZATIONS match rule identifies duplicate parties of type Organization based on party name and address.

Purpose: Expanded Duplicate Identification

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation Name
Name	Party	No	CLEANSE SPECIAL + WRNAMES
Party Type	Party	Yes	EXACT
Postal Code	Address	No	EXACT SPECIAL NOSPC

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	55
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation Name	Weight (%)
Address	Address	60	CLEANSE SPECIAL + WRADDRESS	70
			EXACT SPECIAL + WRADDRESS	100
D-U-N-S Number	Party	70	EXACT	100
Name	Party	50	CLEANSE SPECIAL + WRNAMES	70
			EXACT SPECIAL + WRNAMES	90
			EXACT STRING	100
Tax Registration Num	Party	70	EXACT SPECIAL	100

SAMPLE: ADDRESS_PERSONS

The SAMPLE: ADDRESS_PERSONS match rule identifies duplicate parties of type Person based on party name and address.

Purpose: Expanded Duplicate Identification

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation Name
Name	Party	No	CLEANSE SPECIAL + WRNAMES
Party Type	Party	Yes	EXACT
Postal Code	Address	No	EXACT SPECIAL NOSPC

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	65
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation Name	Weight (%)
Address	Address	60	CLEANSE SPECIAL + WRADDRESS	70

Attribute Name	Entity	Score	Transformation Name	Weight (%)
Name	Party	50	EXACT SPECIAL + WRADDRESS	100
			CLEANSE SPECIAL + WRNAMES	70
			EXACT SPECIAL + WRNAMES	90
			EXACT STRING	100

SAMPLE: ADVANCED SEARCH RULE

The SAMPLE: ADVANCED SEARCH RULE match rule is used for advanced search.

Purpose: Search

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation
Account Number	Party	No	EXACT SPECIAL
All Account Names	Party	No	CLEANSE SPECIAL + WRNAMES
Category Code	Party	No	EXACT
City	Address	No	CLEANSE
Corporation Class	Party	No	EXACT
Country	Address	No	EXACT

Attribute Name	Entity	Filter	Transformation
County	Address	No	CLEANSE
Customer Reference	Party	No	EXACT
Name	Party	No	CLEANSE SPECIAL + WRNAMES SOUNDEX
Party Type	Party	Yes	EXACT
Phone Number	Contact Point	No	EXACT SPECIAL CTX
Postal Code	Address	No	EXACT SPECIAL NOSPC
Province	Address	No	CLEANSE
Registry ID	Party	No	EXACT SPECIAL
SIC Code	Party	No	EXACT
SIC Code Version	Party	No	EXACT
State	Address	No	CLEANSE + WRSTATE
Tax Name	Party	No	CLEANSE
Tax Registration Num	Party	No	EXACT SPECIAL

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	75

Threshold	Value
Override Threshold	
Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation	Weight (%)
Account Number	Party	100	EXACT SPECIAL	100
All Account Names	Party	60	EXACT SPECIAL + WRNAMES	100
Category Code	Party	10	EXACT	100
City	Address	30	CLEANSE	80
			EXACT	100
Corporation Class	Party	30	EXACT	100
Country	Address	30	EXACT	100
County	Address	20	CLEANSE	80
			EXACT	100
Customer Reference	Party	20	EXACT	100
Name	Party	60	CLEANSE SPECIAL + WRNAMES	80
			EXACT SPECIAL + WRNAMES	100
			SOUNDEX	60
Phone Area Code	Contact Point	30	EXACT SPECIAL	100

Attribute Name	Entity	Score	Transformation	Weight (%)
Phone Country Code	Contact Point	10	EXACT SPECIAL	100
Phone Number	Contact Point	80	EXACT SPECIAL CTX	100
Postal Code	Address	35	EXACT SPECIAL NOSPC	100
Province	Address	20	CLEANSE	70
Registry ID	Party	100	EXACT SPECIAL	100
SIC Code	Party	30	EXACT	100
SIC Code Version	Party	10	EXACT	100
State	Address	20	EXACT + WRSTATE	100
			CLEANSE + WRSTATE	80
Tax Name	Party	30	CLEANSE	80
			EXACT	100
Tax Registration Num	Party	70	EXACT SPECIAL	80

SAMPLE: BASIC SEARCH RULE

The SAMPLE: BASIC SEARCH RULE match rule is used for basic search.

Purpose: Search

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation
All Account Names	Party	No	CLEANSE SPECIAL + WRNAMES
Account Number	Party	No	EXACT SPECIAL
Address	Address	No	CLEANSE SPECIAL + WRADDRESS
City	Address	No	CLEANSE
Contact Name	Contact	No	CLEANSE SPECIAL + WRPERSON SOUNDEX
Country	Address	No	EXACT
E-Mail Address	Contact Point	No	CLEANSE (EMAIL) + WRDOMAIN
Name	Party	No	CLEANSE SPECIAL + WRNAMES
Phone Number	Contact Point	No	EXACT SPECIAL CTX
Postal Code	Address	No	EXACT SPECIAL NOSPC
Registry ID	Party	No	EXACT SPECIAL
Site Number	Address	No	EXACT SPECIAL
State	Address	No	CLEANSE + WRSTATE

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	75
Override Threshold	
Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation	Weight (%)
All Account Names	Party	60	CLEANSE SPECIAL + WRNAMES	80
			EXACT SPECIAL + WRNAMES	100
Account Number	Party	100	EXACT SPECIAL	100
Address	Address	40	EXACT SPECIAL + WRADDRESS	100
			CLEANSE SPECIAL + WRADDRESS	70
City	Address	30	CLEANSE	70
			EXACT	100
Contact Name	Contact	50	CLEANSE SPECIAL + WRPERSO	80
			SOUNDEX	0
			EXACT SPECIAL + WRPERSO	100
Country	Address	10	EXACT	100

Attribute Name	Entity	Score	Transformation	Weight (%)
E-Mail Address	Contact Point	80	CLEANSE (EMAIL) + WRDOMAIN	70
			FORCE UPPERCASE ONLY	100
Name	Party	60	CLEANSE SPECIAL + WRNAMES	80
			EXACT SPECIAL + WRNAMES	100
			SOUNDEX	60
Phone Number	Contact Point	80	EXACT SPECIAL CTX	100
Postal Code	Address	20	EXACT SPECIAL NOSPC	100
Registry ID	Party	100	EXACT SPECIAL	100
Site Number	Address	50	EXACT SPECIAL	100
State	Address	20	EXACT + WRSTATE	100

SAMPLE: ORGANIZATIONS_OPTIMIZED

The SAMPLE: ORGANIZATIONS_OPTIMIZED match rule identifies duplicate parties of type Organization.

Purpose: Expanded Duplicate Identification

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation Name
Address	Address	No	EXACT SPECIAL + WRADDRESS
DUNS Number	Party	No	EXACT
Name	Party	No	EXACT SPECIAL + WRNAMES
Party Type	Party	Yes	EXACT
Tax Registration Num	Party	No	EXACT SPECIAL

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	20
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation Name	Weight (%)
Address	Address	19	EXACT SPECIAL + WRADDRESS	100
DUNS Number	Party	20	EXACT	100
Name	Party	19	EXACT SPECIAL + WRNAMES	100

Attribute Name	Entity	Score	Transformation Name	Weight (%)
Tax Registration Num	Party	20	EXACT SPECIAL	100

SAMPLE: PERSON_OPTIMIZED

The SAMPLE: PERSON_OPTIMIZED match rule identifies duplicate parties of type Person.

Purpose: Expanded Duplicate Identification

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation Name
E-Mail Address	Contact Point	No	CLEANSE (EMAIL) + WRDOMAIN
Party Type	Party	Yes	EXACT
Phone Number	Contact Point	No	EXACT SPECIAL CTX
Tax Registration Num	Party	No	EXACT SPECIAL

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	15

Threshold	Value
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation Name	Weight (%)
E-Mail Address	Contact Point	20	CLEANSE (EMAIL) + WRDOMAIN	75
			FORCE UPPERCASE ONLY	100
Phone Number	Contact Point	20	EXACT SPECIAL CTX	100
Tax Registration Num	Party	20	EXACT SPECIAL	100

SAMPLE: SEARCH

The SAMPLE: SEARCH match rule is for search interface based on commonly used attributes.

Purpose: Search

Search Operator: Match Any Attribute

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation Name
Address	Address	No	CLEANSE SPECIAL + WRADDRESS
City	Address	No	CLEANSE
Contact Name	Contact	No	CLEANSE SPECIAL + WRPERSON
D-U-N-S Number	Party	No	EXACT
E-Mail Address	Contact Point	No	CLEANSE (EMAIL) + WRDOMAIN
Name	Party	No	CLEANSE SPECIAL + WRNAMES
Postal Code	Address	No	EXACT SPECIAL NOSPC
Phone Number	Contact Point	No	EXACT SPECIAL CTX
State	Address	No	CLEANSE + WRSTATE
Web Site	Contact Point	No	CLEANSE (URL) + WRDOMAIN

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	80
Override Threshold	
Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation Name	Weight (%)
Address	Address	40	EXACT SPECIAL + WRADDRESS	100
			CLEANSE SPECIAL + WRADDRESS	80
City	Address	30	EXACT	100
			CLEANSE	80
Contact Name	Contact	40	EXACT SPECIAL + WRPERSON	100
			CLEANSE SPECIAL + WRPERSON	80
D-U-N-S Number	Party	80	EXACT	100
E-Mail Address	Contact Point	60	CLEANSE (EMAIL) + WRDOMAIN	80
			FORCE UPPERCASE ONLY	100
Name	Party	40	CLEANSE SPECIAL + WRNAMES	80
			EXACT SPECIAL + WRNAMES	100
Postal Code	Address	30	EXACT SPECIAL NOSPC	100
Phone Number	Contact Point	60	EXACT SPECIAL CTX	100
State	Address	20	CLEANSE + WRSTATE	80

Attribute Name	Entity	Score	Transformation Name	Weight (%)
Web Site	Contact Point	60	EXACT + WRSTATE	100
			CLEANSE (URL) + WRDOMAIN	90

SAMPLE: SEARCH ADDRESS ORGANIZATIONS EXACT

The SAMPLE: SEARCH ADDRESS ORGANIZATIONS EXACT match rule is for search interfaces. The match rule is for a high performance search of addresses and organizations based only on Exact and Word Replacement transformations.

Purpose: Search

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation Name
Name	Party	No	CLEANSE SPECIAL + WRNAMES
Party Type	Party	Yes	EXACT
Postal Code	Address	No	EXACT SPECIAL NOSPC

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	80
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation Name	Weight (%)
Address	Address	60	CLEANSE SPECIAL + WRADDRESS	70
			EXACT SPECIAL + WRADDRESS	100
D-U-N-S Number	Party	70	EXACT	100
Name	Party	50	CLEANSE SPECIAL + WRNAMES	80
			EXACT SPECIAL + WRNAMES	100
Tax Registration Num	Party	70	EXACT SPECIAL	100

SAMPLE: SEARCH EXACT

The SAMPLE: SEARCH EXACT match rule is for search interfaces. The match rule is for a high performance and comprehensive search based only on Exact and Word Replacement transformations.

Purpose: Search

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation Name
Address	Address	No	EXACT SPECIAL + WRADDRESS
All Account Names	Party	No	EXACT SPECIAL + WRNAMES
Account Number	Party	No	EXACT SPECIAL
Category Code	Party	No	EXACT
City	Address	No	EXACT
Contact Name	Contact	No	EXACT SPECIAL + WRPERSO
Corporation Class	Party	No	EXACT
Country Code	Address	No	EXACT
County	Address	No	EXACT
Customer Reference	Party	No	EXACT
E-Mail Address	Contact Point	No	FORCE UPPERCASE ONLY
Name	Party	No	EXACT SPECIAL + WRNAMES
Party Type	Party	Yes	EXACT
Phone Number	Contact Point	No	EXACT SPECIAL CTX

Attribute Name	Entity	Filter	Transformation Name
Postal Code	Address	No	EXACT SPECIAL NOSPC
Province	Address	No	EXACT
SIC Code	Party	No	EXACT
SIC Code Version	Party	No	EXACT
State	Address	No	EXACT + WRSTATE
Tax Name	Party	No	EXACT
Tax Registration Num	Party	No	EXACT SPECIAL
Taxpayer ID	Party	No	EXACT SPECIAL

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	525
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation Name	Weight (%)
Address	Address	60	CLEANSE SPECIAL + WRADDRESS	80

Attribute Name	Entity	Score	Transformation Name	Weight (%)
			EXACT SPECIAL + WRADDRESS	100
All Account Names	Party	50	EXACT SPECIAL + WRNAMES	100
Account Number	Party	100	EXACT SPECIAL	100
Category Code	Party	10	EXACT	100
City	Address	30	EXACT	100
Contact Name	Contact	30	EXACT SPECIAL + WRPERSON	90
			EXACT STRING	100
Corporation Class	Party	30	EXACT	100
Country Code	Address	30	EXACT	100
County	Address	20	EXACT	100
Customer Reference	Party	20	EXACT	100
E-Mail Address	Contact Point	70	FORCE UPPERCASE ONLY	100
Name	Party	50	EXACT SPECIAL + WRNAMES	100
Phone Number	Contact Point	70	EXACT SPECIAL CTX	100
Postal Code	Address	30	EXACT SPECIAL NOSPC	100
Province	Address	10	EXACT	100
SIC Code	Party	30	EXACT	100

Attribute Name	Entity	Score	Transformation Name	Weight (%)
SIC Code Version	Party	10	EXACT	100
State	Address	20	EXACT + WRSTATE	100
Tax Name	Party	30	EXACT	100
Tax Registration Num	Party	80	EXACT SPECIAL	100
Taxpayer ID	Party	100	EXACT SPECIAL	100

SAMPLE: SEARCH SIMILAR ORGANIZATION EXACT

The SAMPLE: SEARCH SIMILAR ORGANIZATION EXACT match rule is for search interfaces. The match rule is for a high performance search of similar organizations based only on Exact and Word Replacement transformations.

Purpose: Search

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation Name
Address	Address	No	CLEANSE SPECIAL + WRADDRESS
Contact Name	Contact	No	EXACT SPECIAL + WRPERSON
D-U-N-S Number	Party	No	EXACT
Name	Party	No	CLEANSE SPECIAL + WRNAMES

Attribute Name	Entity	Filter	Transformation Name
Party Type	Party	Yes	EXACT
Phone Number	Contact Point	No	EXACT SPECIAL CTX
Postal Code	Address	No	EXACT SPECIAL NOSPC
Tax Registration Num	Party	No	EXACT SPECIAL

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	80
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation Name	Weight (%)
Address	Address	60	CLEANSE SPECIAL + WRADDRESS	80
			EXACT SPECIAL + WRADDRESS	100
Contact Name	Contact	30	EXACT SPECIAL + WRPERSON	90

Attribute Name	Entity	Score	Transformation Name	Weight (%)
			EXACT STRING	100
D-U-N-S Number	Party	70	EXACT	100
Name	Party	50	CLEANSE SPECIAL + WRNAMES	90
			EXACT SPECIAL + WRNAMES	100
Phone Number	Contact Point	65	EXACT SPECIAL CTX	100
Postal Code	Address	20	EXACT SPECIAL NOSPC	100
Tax Registration Num	Party	70	EXACT SPECIAL	100

SAMPLE: SEARCH SIMILAR PERSON EXACT

The SAMPLE: SEARCH SIMILAR PERSON EXACT match rule is for search interfaces. The match rule is for a high performance search of similar persons based only on Exact and Word Replacement transformations.

Purpose: Search

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation Name
Address	Address	No	CLEANSE SPECIAL + WRADDRESS

Attribute Name	Entity	Filter	Transformation Name
E-Mail Address	Contact Point	No	CLEANSE (EMAIL) + WRDOMAIN
Name	Party	No	EXACT SPECIAL + WRNAMES
Postal Code	Address	No	EXACT SPECIAL NOSPC
Tax Registration Num	Party	No	EXACT SPECIAL

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	100
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation Name	Weight (%)
Address	Address	60	CLEANSE SPECIAL + WRADDRESS	80
			EXACT SPECIAL + WRADDRESS	100
E-Mail Address	Contact Point	65	CLEANSE (EMAIL) + WRDOMAIN	70

Attribute Name	Entity	Score	Transformation Name	Weight (%)
Name	Party	50	FORCE UPPERCASE ONLY	100
			EXACT SPECIAL + WRNAMES	100
			EXACT STRING	100
Postal Code	Address	20	EXACT SPECIAL NOSPC	100
Phone Number	Contact Point	65	EXACT SPECIAL CTX	100
Tax Registration Num	Party	100	EXACT SPECIAL	100

SAMPLE: SIMILAR_ORGANIZATION

The SAMPLE: SIMILAR_ORGANIZATION match rule identifies duplicate parties of type Organization that have similar names, addresses, contacts, or contact points.

Purpose: Expanded Duplicate Identification

Search Operator: Match Any Attribute

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of the matching process.

Attribute Name	Entity	Filter	Transformation Name
Address	Address	No	CLEANSE SPECIAL + WRADDRESS
Contact Name	Contact	No	CLEANSE SPECIAL + WRPERSON

Attribute Name	Entity	Filter	Transformation Name
D-U-N-S Number	Party	No	EXACT
Name	Party	No	CLEANSE SPECIAL + WRNAMES
Phone Number	Contact Point	No	EXACT SPECIAL CTX
Postal Code	Address	No	EXACT SPECIAL NOSPC
Tax Registration Num	Party	No	EXACT SPECIAL

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	100
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation Name	Weight (%)
Address	Address	60	CLEANSE SPECIAL + WRADDRESS	80
			EXACT SPECIAL + WRADDRESS	100

Attribute Name	Entity	Score	Transformation Name	Weight (%)
Contact Name	Contact	30	CLEANSE SPECIAL + WRPERSON	70
			EXACT SPECIAL + WRPERSON	90
			EXACT STRING	100
D-U-N-S Number	Party	100	EXACT	100
Name	Party	50	CLEANSE SPECIAL + WRNAMES	70
			EXACT SPECIAL + WRNAMES	90
			EXACT STRING	100
Phone Number	Contact Point	65	EXACT SPECIAL CTX	100
Postal Code	Address	20	EXACT SPECIAL NOSPC	100
SIC Code	Party	20	EXACT	100
Tax Registration Num	Party	100	EXACT SPECIAL	100

SAMPLE: SIMILAR_PERSON

The SAMPLE: SIMILAR_PERSON match rule identifies duplicate parties of type Person that have similar names, address, or contact points.

Purpose: Expanded Duplicate Identification

Search Operator: Match All Attributes

Acquisition

This table shows the seeded attributes and transformations for the acquisition part of

the matching process.

Attribute Name	Entity	Filter	Transformation Name
Address	Address	No	CLEANSE SPECIAL + WRADDRESS
E-Mail Address	Contact Point	No	CLEANSE (EMAIL) + WRDOMAIN
Name	Party	No	CLEANSE SPECIAL + WRNAMES
Postal Code	Address	No	EXACT SPECIAL NOSPC
Tax Registration Num	Party	No	EXACT SPECIAL

Scoring

This table shows the seeded thresholds for the scoring part of the matching process.

Threshold	Value
Match Threshold	100
Override Threshold	
Automatic Merge Threshold	

This table shows the seeded attributes and transformations for the scoring part of the matching process.

Attribute Name	Entity	Score	Transformation Name	Weight (%)
Address	Address	60	CLEANSE SPECIAL + WRADDRESS	70

Attribute Name	Entity	Score	Transformation Name	Weight (%)
E-Mail Address	Contact Point	65	EXACT SPECIAL + WRADDRESS	100
			CLEANSE (EMAIL) + WRDOMAIN	70
Name	Party	50	FORCE UPPERCASE ONLY	100
			CLEANSE SPECIAL + WRNAMES	60
			EXACT SPECIAL + WRNAMES	90
Phone Number	Contact Point	65	EXACT STRING	100
			EXACT SPECIAL CTX	100
Postal Code	Address	20	EXACT SPECIAL NOSPC	100
Tax Registration Num	Party	100	EXACT SPECIAL	100

Party and Account Merge Impact

This chapter covers the following topics:

- Party and Account Merge Impact Overview
- Party Merge Impact
- Party Merge Impact Reference by Application
- Account Merge Impact
- Account Merge Impact Reference by Application

Party and Account Merge Impact Overview

The Party Merge and Account Merge functionalities are part of the Data Quality Management (DQM) tools provided by Trading Community Architecture (TCA). You can use party and account merge to identify and resolve duplicates that exist in the Trading Community registry.

Different applications across the Oracle E-Business Suite have data associated with both parties and customer accounts. Any references to parties and accounts are updated when parties or accounts are merged. This ensures data integrity across the Oracle E-Business Suite.

This chapter describes the results of the party and account merge processes initiated in Oracle E-Business suites applications. For most applications the descriptions include what information is merged or transferred and any validations that occur before completion of the process.

Knowing how data throughout the Oracle E-Business Suite is affected when you run either the Party Merge or Account Merge processes helps you determine:

- Impact of running the merge process.
- Changes to the data for parties and customer accounts.

This information is intended for end-users who are interested in understanding the

implication of running either a party merge or an account merge process.

Assumptions

This document assumes that the reader understands the basic concepts of the various applications in the E-Business Suite. For detailed information regarding the entities affected during merge, please refer to respective application user's guide and the electronic technical reference manual (eTRM) located in *OracleMetaLink*.

Related Topics

Party Merge Impact, page 8-2

Party Merge Impact Reference by Application, page 8-22

Account Merge Impact, page 8-36

Account Merge Impact Reference by Application, page 8-49

Party Merge Impact

This section provides details regarding how party merge affects the data in different applications within the e-Business Suite.

Activity Based Management

When parties are merged, any records containing different types of balances such as profitability balance, expense balance, transaction balance and summarized (YTD) balances, for a party are transferred to the master party.

Advanced Global Intercompany System (AGIS)

Intercompany organizations are entities that reference the party record in TCA. When parties are merged, the Intercompany organization and related tables are transferred to the master party. The information that will be transferred include:

- Intercompany transaction batches
- Intercompany transaction headers
- Intercompany transaction distribution lines
- Intercompany customer associations
- Intercompany supplier associations

Validation

The merge will be vetoed if the party to be merged is an Intercompany organization with existing transactions applied, and if the party is not associated to the same legal entity as the master party.

Advanced Pricing

The following information transfers to the master party record:

Pricing Qualifiers: Parties and party sites can be used as pricing qualifiers in Advanced Pricing. Any record referring to the candidate party as the pricing qualifier is updated to look at the master party record.

Validation

The pricing qualifier information is transferred to the master party record after ensuring that a similar qualifier does not exist for the master party.

Applications Object Library

The following information is transferred to the master party:

- The Customer link on an Oracle Applications login account, such as any login pointing to the old party will now be pointing to the new party.
- Documents attached to the candidate party.

Cash Management

Bank and branch information is stored in the Cash Management application. If any of the parties that have been identified for merge are either banks or branches, the merge will be vetoed.

Collections

Information regarding delinquencies associated with a party is stored in the Collections application. When parties are merged, the delinquency information is transferred to the master party.

When two parties are merged, the following information is transferred to the master party:

- Collections scores for delinquencies, sites, accounts and parties
- Delinquencies of a party
- Collections communications sent to parties; party, account and site

- Strategies applied to parties, accounts, and sites in order to recover debt
- Promises to pay debt made by customers.

Complex Maintenance, Repair, and Overhaul

The following information merges with the master party record:

- Information about documents or manuals provided by the supplier of a product
- Additional information about the party that supplied the document or manuals
- Additional information about the party that received the documents
- Document subscription information such as subscription type, frequency, and so on that is associated with a party
- Information about the revisions to a document and details about the party that approved the revision
- Information about standard and non-standard maintenance operations associated with parties
- Current and draft routes which consist of one or more operations

The following is transferred to the master party record:

- Information required to perform the following types of transactions with a third party organization: service, exchange, loan, and borrow

Validations

The merge takes place only if the master party does not have similar dependent records

If Oracle Purchasing application has been installed, then the subscription information is associated to a supplier and not a party. Therefore, the merge operation does not take place.

If Human Resources is installed, then the revision of documents and the approver of a revision comes from the HR tables. Therefore, the merge operation does not take place.

Contracts Core

When parties are merged the following information is transferred to the master party:

- Current versions of all contracts

CRM Foundation

The following information is merged into the master party record:

- Temporary placement of fulfillment content to be previewed and then either submitted for dispatch or deleted associated with the duplicate party
- Information requests that have been processed by the Fulfillment Server for the duplicate party
- Fulfillment content history for every content corresponding to a template

CRM Foundation - Interaction History

During party merge, all interactions associated with the duplicate party are transferred to the master party record.

CRM Foundation - Resource Manager

Resource manager allows users to access and define CRM specific resource attributes for parties. Therefore, when two parties are merged, additional resource information defined for the party is transferred to the master party.

Validation

The resource is not transferred if the master party already has a resource defined in the resource manager application.

CRM Foundation - Tasks and Notes

The following information transfers to the master party record:

- Tasks that are associated with the duplicate party
- Contact information associated with the tasks
- Task audit information
- Task references associated with the duplicate party
- Notes and note context associated with the party

CRM Foundation - Territories

If the party records are identified as duplicates, then the territory definition values that are based on parties are transferred.

Validation

If the party has an associated named account, then an error is raised and party merge cannot be completed. In other words, if a party is assigned to a territory group that party cannot be merged to another party.

CRM Foundation - User Management

In User Management, you can define approvers for a given organization (customer). These approvers are responsible for processing account requests for this customer. The following changes can be seen in User Management when party merge process takes place:

- Pending requests to be approved are transferred from the duplicate party to the master party.
- All of the approvers associated with the duplicate party are inactivated.
- If no approver list is defined for master party, then the requests are assigned to the default list.

Customer Care

The Customer Care merge process transfers information to the master party about relationship plans, which allow companies to automate their customer service practices and provide a proactive and consistent way to take care of the customers needs.

Validations

If no relationship plans exist on the master party record, then the relationship plan from the duplicate party is transferred to the master party.

If the duplicate and master parties have identical relationship plans, then the relationship plan from the duplicate party is merged to the master party's relationship plan. Otherwise, the duplicate party's relationship plan transfers to the master party.

E-Business Tax

The E-Business Tax application stores transaction tax information related to the tax setup of a party or a party site, or both. The tax information stored include fiscal tax classifications, tax registrations, exemptions, tax accounts, and subscription options.

When parties are merged in TCA, the following changes will take place:

- Tax classifications will be merged if there is an equivalent record in the master party; otherwise, the information will be transferred.
- Tax accounts will be merged if there is an equivalent record in the master party;

otherwise, the information will be transferred.

- The E-Business Tax's tax registration record will be copied rather than transferred so that historic data held in the Tax Repository is retained for audit purposes.

Note: Exemptions will neither be transferred nor merged to avoid conflicting exemptions from appearing in the tax setup for the master party.

Validations

The merge will be vetoed when the parties' E-Business Tax registrations for a given Tax, Tax Jurisdiction, and Tax Regime differ in key registration attributes: registration number, set invoice values as tax inclusive, and set for self assessment or reverse.

Note: Veto will not occur for differing TCA registration numbers. The TCA registration number of the merge-to party record will be kept on the surviving party record.

Grants Proposal

The following information is transferred in case of person-party merge:

- Person information, such as graduation date, field of study, area of specialization, school name, and degrees
- A person's biosketch information
- Information pertaining to a person's role and percentage effort on a given proposal
- Information pertaining to a person's completed proposals and awards

The following information is transferred in case of organization-party merge:

- The organization along with its multiple locations

Validations

If the master party has any information associated with it in Grants Proposal product, then the merge cannot be completed.

Human Resources

The following information transfers to the master party record:

- Corresponding personal information for employees, applicants, ex-employees,

ex-applicants, contacts and other people

- Records from educational institutions that a person is attending or has attended and the dates of attendance
- Competence information or description of knowledge, skills, abilities or other characteristics of a person
- Information about interviews and other events related to a person
- Address and phone number information for the following people:
 - Current or former employees
 - Current or former applicants
 - Employee contacts
- Records of educational qualification, certificates, licenses, and so on for a person
- Previous employment information for a person

Installed Base

The following information transfers to the master party record:

- Item instance's associated parties, its locations (if the location is a party site) and contacts
- System's install location and all of the contacts
- Transactions pertaining to the line details, system, party associations and location

Validation

The information is transferred only if an equivalent record does not exist for the master party.

You cannot merge a party that is defined as the internal party in Installed Base Install parameter setup. The Installed Base application setup requires that you set up the party owning the enterprise data as an internal party in the Installed Base installation parameters table. After you define this party as an installation parameter, you cannot merge the party with any other party. This preserves the integrity of the current data in the Installed Base data.

If you attempt to merge this internal party with another party, then an exception will be raised and the merge will not take place.

iStore

The following information is affected when party merge takes place:

- Duplicate party's shopping lists will always be transferred to the master party.
- Pre-IBE.O (11.5.9) If the master party does not have express checkout setting, the duplicate party's records will be transferred. If the master party already has a record in this table, then the duplicate party's record will be deleted.
- IBE.O (11.5.9) Duplicate Party's record will always be deleted.
- If a master party does not have a minisite access restriction, the duplicate party's access restrictions (records) are transferred to the master party. If master party already has minisite party access restrictions, then the duplicate party's record will be end-dated.
- If the shared cart is shared with both the master party and the duplicate party, the shared cart record for the duplicate party will be deleted from this table. Otherwise all the shared carts will be transferred to the master.
- Duplicate party's active cart will always be deleted.

iSupplier Portal

When parties are merged, the following entities are transferred to the master party from the merge-from party:

- Payment preferences of suppliers and supplier addresses
- Business classifications used in supplier profile management
- Supplier profile change requests for prospective and approved suppliers

When parties are merged, the following entities are neither merged nor transferred to the master party from the merge-from party:

- Requests from the supplier to assign bank account to a supplier address
- Change requests from supplier on supplier addresses
- Notes for supplier addresses
- Temporary supplier address data created during Release 12 upgrade
- Change requests from supplier on contacts
- Temporary supplier contact data created during Release 12 upgrade

- Change requests from supplier on supplier address and supplier contacts
- Supplier registration data
- Temporary supplier data created during Release 12 upgrade

Validation

- Vetoed if the merged-from party is identified as the enterprise party created by iSupplier to represent the deploying company
- Vetoed if there are pending change requests in the supplier profile management tables:
 - POS_ACNT_ADDR_REQ: Stores requests from supplier to assign account to a supplier address
 - POS_ADDRESS_REQUEST: Stores change requests from supplier on supplier addresses
 - POS_CONT_ADDR_REQUESTS: Stores change requests for association between supplier address and supplier contact
 - POS_PRODUCT_SERVICE_REQUEST: Stores change requests for product service offerings
 - POS_BUS_CLASS_REQS: Stores change requests for supplier classifications

Internal Control Management

When parties are merged, the following entities are transferred to the master party from the merge-from party:

- Assessment owners
- Constraint creators
- Certification owners
- Violation creators
- Auditors of audit procedures

Lease Management

The following information transfers to the master party record:

- Lease invoice details
- External insurance provider and agent details
- Asset location detail
- Shipping instructions identified during the Asset Return process

Legal Entity

When parties are merged and the merge-from party is a legal authority, the following legal information will be transferred to the master party:

- Legal functions that a legal entity or an establishment should perform for a given registration.
- Registration information of legal entities or establishments.

When parties are merged and the merge-from party is a legal contact, the following legal information will be transferred to the master party:

- Legal associations between business and legal objects.

The merge is vetoed if the either the merge-from or merge-to parties are legal contacts, and the taxpayer ID's are not the same for both the merge-from parties and the master party.

When the merge involves any party that is a first party legal entity (FPLE) or an establishment of a first party legal entity, the merge is vetoed.

Learning Management

When parties are merged, the following are transferred from the merge-from party to the master party:

- Performance
- Event association
- Class and learning path enrollment data

Loans

The following information transfers to the master party record:

- Loan information
- Loan participants (borrower, co-borrower, and guarantor) information

Marketing

The following information transfers to the master party record:

- Partners who source the funds to run marketing campaigns, events, offers, and so on.
- Partners associated with a marketing activity such as campaigns
- Associations of parties to the marketing medium such as newspaper, radio, and so on.
- Information about the party that is registering for the event
- Information about the party attending the event
- Contact information for the registering party
- Contact information for the party attending the event
- Extra information regarding the origin and mapping details when party records are imported into the TCA registry
- Trade profile defined at party level
- Organizations that are affiliates
- Resources associated with an event
- Vendors for a marketing medium
- Venues such as conference centers, rooms, and so on, which can be used to hold an event
- Agenda information containing track and sessions
- Contact history (used by fatigue rules)
- Fatigue projections for a target group

The following information is merged into the master party:

- Information in the table containing the list bought from an external company that should be imported as part of any marketing activity
- Information in the table containing customers/contacts/target/ prospects generated for a list, to be used for mailshots, telemarketing, and so on.

- Imported records from the list import process
- Parties with products competing in the same market as the deploying company
- Parties belonging to a market segment

Offers

The following information is merged to the master party record:

- Customer contacts associated to offers
- Offer qualifier that is associated to the party

Order Capture

The following information transfers to the master party record:

- The header data for an order capture quotation
- Order line or quote information which includes the item, item organization, unit of measure, quantity ordered, and so on
- Shipping information for a quote

Order Management

In Advanced Pricing, you can use pricing qualifiers, which reference a party or party site when defining pricing modifiers. When orders are created, these price adjustment attributes are captured within the Order Management application. When the party or party site is merged, any references to the price adjustments are updated with the master party information.

Partner Management

When two parties are merged, the following actions take place:

- All partner memberships are terminated for the party being merged.
- Any pending or incomplete enrollment requests submitted by the party being merged are canceled.
- Profile information for the party being merged is not migrated.

When two parties are merged, the following information is transferred to the master party:

- Transaction level information for leads, opportunities, referrals, deal registrations, fund requests, and special pricing requests
- Lead assignment history

Validation

When two parties are merged, the channel manager assignment may not be qualified based on the territory setup for Oracle Partner Manager usages. To assign a correct channel team after the party merge, run the concurrent request program PV: Territory assignment for partners in TOTAL or INCREMENTAL mode, available under the PRM Concurrent Requests responsibility and select INCREMENT mode.

Payables

When parties are merged, the following entities are transferred to the master party from the merge-from party:

- None

When parties are merged, the following entities are merged to the master party from the merge-from party:

- Invoices
- Payments
- Suppliers
- Supplier Sites

Validation

Party merge will be vetoed in the following cases:

- The associated Supplier/Supplier Sites have not been merged.
- There are unpaid invoices associated with the merged-from Party/Party Site.

Note: Even if the user selected ALL in the Supplier Merge, that is not a guarantee that all invoices are transferred. After the merge, the user could have deleted the Inactive On date and entered new transactions, so in this case you cannot just rely on the Accounts Payables merge table to determine if all invoices have been merged.

- The user has not selected the *Transfer PO* checkbox on the Supplier Merge form.

Note: To create new purchase orders for a deactivated supplier, first activate the supplier.

- A Supplier/Supplier Site is associated with the merged-from Party/Party Site but there is not a Supplier/Supplier Site associated with the merged-to Party/Party Site.
- Payables must confirm that the merged-from Party/Party Site and merged-to Party/Party Site are correlated with the same merged-from Supplier/Supplier Site and merged-to Supplier/Supplier Site. For example, if Supplier A is merged into Supplier B and Supplier B is then merged into Supplier C, the user cannot merge Party A into Party C. In this case, the corresponding merged-from Party and merged-to Party are not the same.

Payments

When a party is merged, Oracle Payments checks to see the Taxpayer ID is the same for the parties. If it is, then any active payment instruments such as credit cards, debit cards, or bank accounts associated with any party is moved under the master party. If the Taxpayer ID is different, then the merge will be prevented and the user has to inactivate any payment instruments under the parties that will be merged into the surviving party.

In addition to the payment instruments, a party that is a payee or payer will have payment attributes. These attributes are copied over to master party if they don't already exist there. The list of payment methods associated with the master party will include all the payment methods that were associated with any of the merged parties.

Transactions for the party or parties being merged into the surviving party will be transferred to the master party.

Validation

Party Merge processes will be vetoed only when active credit cards or bank accounts exist on the merge-from party and if the taxpayer ID's are not the same.

Project Contracts

In Project Contracts, all the existing funding records from the duplicate party are merged into the master party record.

The following information transfers to the master party record:

- The total funding for a funding pool contributed by a party
- Current and historic information regarding contract funding associated with the party

Projects

The following information transfers to the master party record:

- Project set owner
- External organization playing a role on a project
- Control items (Owner, Closed By, Last Modified by, and Assigned to Action)
- Progress (Published by)

Validation

You cannot merge a party that is defined as a key member on a project.

Proposals

The following information is transferred to the master party record:

- Sales proposals created for the party
- Information about the e-mail recipients who received the email with the proposal document

Quality

The following information transfers to the master party record:

- Party data elements on collection plans

Note: If an electronic record snapshot has been made for the merge from party, it will contain the original party name, even though the Quality Result will have the name of the master party.

For improved performance, create a custom database index on QA_RESULTS.PARTY_ID before performing a party merge, if the following conditions are met:

- Oracle Quality is installed.
- One or more collection plans that include Party as a collection element have been defined.
- These collection plans contain a large amount of results.

Receivables

The following information transfers to the master party record:

- Credit request associated with the party
- Case folder associated with the party
- Phone and fax information associated with the contact points for a party

Sales

The following information merges with the master party record:

- Information about a product in which the party is interested
- Information about sales leads associated with a party
- Information about the contact associated with the sales lead
- Forecast information for opportunities associated with a party
- Information about sales opportunities associated with a party
- Sales credits assigned to partner identified by the party
- Associations between a party contact and opportunity
- Information about competitors that exist for a sales opportunity
- Employee access to a party, opportunity and lead
- Changes to the parties and lead information that has been modified by a territory definition
- Information about the current environment of a party

The following information transfers to the master party record:

- Customer account plan information

Service

The following information merges with the master party record:

- Service request information associated with parties
- Service request incident location

- Audit information for service requests
- Contact point for a service request that is associated with a party
- Any party site used on a charge line
- Any site and site use that is associated to a party for a service request

Validations

If a service request has more than one contact, these contacts are merged.

If duplicate contact points exist for the two contacts that were merged, and these duplicate contact points are then merged, it could result in duplicate records in CS_HZ_SR_CONTACT_POINTS. In this case, the duplicate records are deleted.

Service Contracts

The following information transfers to the master party record:

- Billing profiles: One or more billing profiles for a party
- Global contract defaults: Information that has to be defaulted when renewing a service contract or when creating a service contract from an order is associated with the duplicate party
- Service availability: Exceptions to services availability for the party
- Pricing Qualifiers: Parties and party sites can be used as pricing qualifiers against a service contract. Any record referring to the candidate party as the pricing qualifier is updated to look at the master party record.

Shipping Execution

Party merge cannot be completed if:

- The duplicate party is a freight carrier
- The duplicate party has sites where a load can be tendered by the shipper

Validation

Party Merge processes will be vetoed only if the organization for which the records are being merged is WMS enabled and there is a change in ship-to address for shipment lines which are staged (picked) and packed but not yet confirmed for shipment.

Site Management

From Site management a party of type *REAL ESTATE* is created whenever a internal *Site* is associated with a *Legal Entity*. Also an external site can be associated with some external party in Site Management.

If two parties are merged and if *from* party is associated with an External *Site* in Site Management , the existing association is replaced with a new association with new *To* party in Site Management after merge.

If two parties are merged and if *from* party is associated with an External *Site* in Site Management , the existing association is replaced with a new association with new *To* party in Site Management after merge.

Validation

Merge is not allowed if either the merge-from or the merge-to parties are real estate parties which are created from Site Management.

Sourcing

If a merge request includes either parties or party sites originally created for use in Oracle iSupplier Portal or Oracle Sourcing, the request will be denied.

Spares Management

The following information transfers to the master party record:

- Move-order header information associated with a party
- Pack list containing information about the parts that were shipped

Student Systems

If a merge request includes parties that have related records in Oracle Student Systems, the request will be denied.

Supply Chain Intelligence

The following information transfers to the master party record:

- Cost of goods sold (COGS) information from the order line
- Past due or backordered lines
- Order management summary from the order header and line

When parties are merged, depot repair orders are transferred from the merge-from

party to the master party.

Territory Manager

Note: Named accounts are setup on the party site rather than on the party.

When party sites are merged and both merge-from and merge-to party sites are named accounts:

- If both the named accounts belong to the same parent territory, then the merge-from named account and the associated sales team are deleted.
- If the named accounts belong to different parent territories, then the merge-to named account is added to the parent territory of the merge-from named account with the sales team of the merge-from named account. The merge-from named account is then deleted.

When party sites are merged, and the merge-from party site is setup as a named account and the merge-to party site is not a named account:

- If the merge-from named account belongs to a territory whose matching rule is either DUNS or REGISTRY ID, and if the party of the merge-to party site already exists as a named account in the territory, then the merge-from named account and the associated sales team are deleted.
- If the merge-from named account belongs to a territory whose matching rule is either DUNS or REGISTRY ID, and if the party of the merge-to party site does not exist as a named account in the territory, then the merge-to party site will replace the merge-from party site as a named account.
- If the merge-from named account belongs to a territory whose matching rule is neither DUNS nor REGISTRY ID, then the merge-to party site replaces the merge-from party site as a named account.

When party sites are merged, and the merge-from party site is not a named account while the merge-to party is:

- No transfers or deletes.

Trade Management

The following information transfers to the master party record:

- Broker and contact information for claims and claim history
- Buying group on a claim line and claim line history

- Trade profiles
- Code conversion mappings
- Partner and partner contact for a resale batch
- Billing party and contact for a resale header
- Billing, shipping and sold from party and contacts for a resale interface line
- Billing, shipping and sold from party and contacts for a resale line
- End customer, reseller and partner for a special price or soft fund request
- Party, buying group contact and autopay party for an offer
- Parent party and rollup party for customer targets
- Budget source and vendor for budgets

Trading Community Architecture

For details regarding the TCA entities affected during Party Merge, see: Party Merge Overview, *Oracle Trading Community Architecture User Guide*.

Transportation Execution

The following information transfers to the master party record:

- Facilities

XML Gateway

A party can be defined as a trading partner in the XML Gateway application. Therefore, if two parties are merged, then references to the trading partners is also merged.

When parties are merged the following information is transferred to the master party:

- Trading partner header information
- Any document logs for inbound, outbound and pass through messages
- Any outbound transactions logs

Related Topics

Party Merge Impact Reference by Application, page 8-22

Party Merge Impact Reference by Application

This table shows the results of merging parties using applications in the Oracle E-Business suite, describing the affected tables, the transfer or merge action, and the validations performed for each application prior to completion of the party merge process.

Product Name	Tables affected	Action	Validations
Activity Based Management	FEM_PARTY_PROFITABILITY	Merged	None
Advanced Global Intercompany System (AGIS)	FUN_TRX_BATCHES FUN_TRX_HEADERS FUN_DIST_LINES FUN_CUSTOMER_MAPS FUN_SUPPLIER_MAPS	Transferred	Vetoed if Intercompany org has existing transactions and does not have the same legal entity.
Advanced Pricing	QP_QUALIFIERS	Conditionally transferred	The pricing qualifier information is transferred to the master party record after ensuring that a similar qualifier does not exist for the Master Party.
Applications Object Library	FND_ATTACHED_DOCUMENTS FND_USER	Transferred	None
Cash Management	CE_BANK_MERGE_V CE_BANK_BRANCHES_MERGE_V	None	Merge is vetoed in all cases.

Product Name	Tables affected	Action	Validations
Collections	IEX_CASE_CONTACTS IEX_DELINQUENCIES_ALL IEX_DUNNINGS IEX_PROMISE_DETAILS IEX_SCORE_HISTORIES IEX_STRATEGIES	Transferred	None
Complex Maintenance, Repair, and Overhaul	AHL_DOC_REVISIONS_B AHL_DOCUMENTS_B AHL_OPERATIONS_B AHL_OSP_ORDERS_B AHL_RECIPIENT_DOCUMENTS AHL_ROUTES_B AHL_SUBSCRIPTIONS_B AHL_SUPPLIER_DOCUMENTS	Conditionally transferred	The merge takes place only if the master party does not have a similar dependent records. If Oracle Purchasing application has been installed, then the subscription information is associated to a supplier and not a party. Therefore, the merge operation does not take place. If Human Resources is installed, then the revision of documents and the approver of revision comes from HR tables. Therefore, the merge operation does not take place.
Contracts Core	OKC_K_PARTY_ROLES_B OKC_RULES_B OKC_K_ITEMS OKC_CONTACTS	Transferred Transferred	None If the contact already exists for the master party, the contact is not transferred.
CRM Foundation	JTF_FM_CONTENT_HISTORY_V JTF_FM_PREVIEWS_V JTF_FM_PROCESSED_V	Merged	None
CRM Foundation - Interaction History	JTF_IH_INTERACTIONS	Transferred	None

Product Name	Tables affected	Action	Validations
CRM Foundation - Resource Manager	JTF_RS_RESOURCE_EXTNS	Conditionally transferred	The resource is not transferred if the master party already has a resource defined in the resource manager application.
CRM Foundation - Tasks and Notes	JTF_NOTES_B JTF_NOTE_CONTEXTS JTF_PERZ_QUERY_PARAM JTF_TASK_ASSIGNMENTS JTF_TASK_AUDITS_B JTF_TASK_CONTACTS JTF_TASK_PHONES JTF_TASK_REFERENCES_B JTF_TASKS_B	Transferred	None
CRM Foundation - Territories	JTF_TTY_NAMED_ACCTS	Conditionally transferred	If the party has an associated named account an error is raised and party merge cannot be completed. In other words, if a party is assigned to a territory group that party cannot be merged to another party.
CRM Foundation - User Management	JTF_UM_APPROVERS	The records are end-dated	None
Customer Care	CSC_CUST_PLANS CSC_CUST_PLANS_AUDIT CSC_CUSTOMERS CSC_CUSTOMERS_AUDIT_HIST CSC_CUSTOMIZED_PLANS	Merged or transferred	If no relationship plans exist on the master party record, then the relationship plan from the duplicate party is transferred to the master party. If the master party has a relationship plan associated with it, then the relationship plan from the duplicate party is merged to it if the two plans are identical. Otherwise, the relationship plan from the duplicate party is transferred to the master party.

Product Name	Tables affected	Action	Validations
E-Business Tax	ZX_PARTY_TAX_PROFILE	Merged	None
	ZX_REGISTRATIONS		Veto if key fields are for same registration.
	ZX_EXEMPTIONS	None	Veto if key fields are different for same exemptions.
	HZ_CODE_ASSIGNMENTS	Transferred	None
	ZX_REPORT_CODES_ASSOC		
Grants Proposal	IGW_PERSON_BIOSKETCH	Conditionally transferred	If the master party has any information associated with it in Grants Proposal product, then the merge will not go through.
	IGW_PERSON_DEGREES		
	IGW_PROP_LOCATIONS		
	IGW_PROP_PERSON_SUPPORT		
	IGW_PROP_PERSONS		
Human Resources	PER_ADDRESSES	Transferred	The parties should be of type person.
	PER_ALL_PEOPLE_F		
	PER_COMPETENCIES		
	PER_ESTABLISHMENT_ATTENDANCES		
	PER_EVENTS PER_PHONES		
	PER_PREVIOUS_EMPLOYERS		
	PER_QUALIFICATIONS		

Product Name	Tables affected	Action	Validations
Installed Base	CSI_I_PARTIES	Conditionally transferred	The information is transferred only if an equivalent record does not exist for the master party.
	CSI_ITEM_INSTANCES		
	CSI_SYSTEMS_B		You cannot merge a party that is defined as the internal party in the Installed Base Install parameter setup. The Installed Base application setup requires that the party owing the enterprise data be setup as an internal party in the Installed Base installation parameters table. Once defined as an installation parameter in Installed Base, this party cannot be merged with any other party to preserve the integrity of data already existing in Installed Base.If you try to merge this internal party with another, an exception will be raised and the merge will not take place.
	CSI_T_PARTY_DETAILS		
	CSI_T_TXN_LINE_DETAILS		
	CSI_T_TXN_SYSTEMS		
iStore	IBE_ACTIVE_QUOTES_ALL	Transferred	If master party doesn't have minisite access restriction, the duplicate party's access restrictions (records) will be transferred to the master party. If master party already has minisite party access restrictions, then the duplicate party's record will be end-dated.
	IBE_MSITE_PRTY_ACCSS		
	IBE_ORD_ONECLICK_ALL		
	IBE_SH_QUOTE_ACCESS		If the shared cart is shared with both the master party and the duplicate party, the shared cart record for the duplicate party will be deleted from this table. Otherwise all the shared carts will be transferred to the master party.
	IBE_SH_SHP_LISTS		
iSupplier Portal	POS_ACNT_PAY_PREF	None	
	POS_ADDRESS_NOTES		
	POS_SUPPLIER_REGISTRATIONS		
	POS_BUS_CLASS_ATTR	Transferred	
	POS_SUPPLIER_MAPPINGS		

Product Name	Tables affected	Action	Validations
	POS_ADDRESS_UPGRADE	None	Not needed after upgrade to R12.
	POS_CONTACT_UPGRADE		
	POS_VENDOR_UPG_TMP		
	POS_ACCT_ADDR_REQ	None	Veto merge if there is a pending request in the table.
	POS_ADDRESS_REQUESTS		
	POS_CONT_ADDR_REQUESTS		
	POS_CONTACT_REQUESTS		
Internal Control Management	AMW_ASSESSMENTS_B	Transferred	None
	AMW_CONSTRAINTS_B		
	AMW_CERTIFICATION_B		
	AMW_VIOLATIONS		
	AMW_AP_EXECUTIONS		
Lease Management	OKL_CNSLD_AR_HDRS_B	Transferred	None
	OKL_EXT_SELL_INVS_B		
	OKL_INS_POLICIES_B		
	OKL_OPEN_INT		
	OKL_RELOCATE_ASSETS_B		
	OKL_TRX_AR_INVOICES_B		
	OKL_TXL_ITM_INSTS		
	OKL_TXL_RCPT_APPS_B		
Legal Entity Configurator	XLE_ENTITY_PROFILES	Veto Merge	Vetoed for FPLE only.
	XLE_ETB_PROFILES		Vetoed for FP Establishments only.
	XLE_ASSOCIATIONS	Transferred	Vetoed if taxpayer ID is not the same.
	XLE_REGISTRATIONS		None
	XLE_REG_FUNCTIONS		None

Product Name	Tables affected	Action	Validations
Learning Management	OTA_ATTEMPTS	Transferred	None
	OTA_SCORM_OBJ_ATTEMPTS		
	OTA_SCORM_OBJ_PERFS		
	OTA_SCORM_OBJECTIVES		
	OTA_LO_SCORM_OBJECTIVES		
	OTA_EVENT_ASSOCIATIONS		
	OTA_DELEGATE_BOOKINGS		
	OTA_LP_ENROLLMENTS		
Loans	OTA_LP_MEMBER_ENROLLMENTS		
Loans	LNS_LOAN_HEADERS_ALL	Transferred	None
	LNS_PARTICIPANTS		
Marketing	AMS_IMP_SOURCE_LINES	Merged	None
	AMS_LIST_ENTRIES		
	AMS_PARTY_SOURCES		
	AMS_PARTY_MARKET_SEGMENTS		
	AMS_COMPETITOR_PRODUCTS_B		

Product Name	Tables affected	Action	Validations
	AMS_AGENDAS_B	Transferred	None
	AMS_IBA_PL_SITES_B		
	AMS_ACT_PARTNERS		
	AMS_ACT_RESOURCES		
	AMS_CHANNELS_B		
	AMS_EVENT_REGISTRATIONS		
	AMS_TCOP_CONTACTS		
	AMS_TCOP_CHANNEL_SUMMARY		
	AMS_TCOP_CONTACT_SUMMARY		
	AMS_TCOP_PRVW_CONTACTS		
	AMS_TCOP_PRVW_FTG_DTLS		
	AMS_VENUES_B		
Offers	AMS_OFFER_PARTIES	Merged	None
Order Capture	ASO_QUOTE_HEADERS_ALL	Transferred	None
	ASO_QUOTE_LINES_ALL		
	ASO_SHIPMENTS		
Order Management	OE_PRICE_ADJ_ATTRIBS	Transferred	None

Product Name	Tables affected	Action	Validations
Partner Management	PV_ASSIGNMENT_LOGS	Transferred	The responsibilities stored in the PV_GE_PTNR_RESPS table for the party being merged are revoked. The responsibilities stored in the PV_GE_PTNR_RESPS table associated with the master party are granted to the users of the party being merged.
	PV_ENTY_ATTR_VALUES		
	PV_LEAD_ASSIGNMENTS		
	PV_LEAD_PSS_LINES		
	PV_SEARCH_ATTR_VALUES		
	PV_GE_PARTY_NOTIFICATIONS		
	PV_PARTNER_ACCESSES		
	PV_TAP_ACCESS_TERRS		
	PV_TAP_BATCH_CHG_PARTNERS		
	PV_REFERRALS_B		
	PV_GE_PTNR_RESPS		
	PV_PG_ENRL_REQUESTS	Cancelled	All incomplete or submitted Enrollment Requests for the party being merged are canceled.
	PV_PG_MEMBERSHIPS	Terminated	All memberships for the party being merged are terminated.
	PV_PARTNER_PROFILES	Merged	The status of the party being merged is set to M. The Profile is not migrated.
Payables	AP_SUPPLIERS	Transferred	If no veto.
	AP_SUPPLIER_SITES_ALL		
	AP_INVOICES_ALL		
	AP_CHECKS_ALL		
Payments	IBY_CREDITCARD	Merged	Taxpayer ID is the same.

Product Name	Tables affected	Action	Validations
	IBY_ACCOUNT_OWNERS	Merged or Transferred	Taxpayer ID is the same.
	IBY_EXTERNAL_PAYEES_ALL		
	IBY_EXTERNAL_PAYERS_ALL		
	IBY_PMT_INSTR_USES_ALL		
	IBY_DOCS_PAYABLE_ALL	Transferred	Taxpayer ID is the same.
	IBY_EXT_PARTY_PMT_METHODS		
	IBY_FNDCT_TX_EXTENSIONS		
	IBY_PAYMENTS_ALL		
	IBY_TRXN_SUMMARIES_ALL		
Project Contracts	OKE_K_FUNDING_SOURCES	Transferred	None
	OKE_K_FUNDING_SOURCES_H		
	OKE_POOL_PARTIES		
Projects	PA_CI_ACTIONS	Conditionally transferred	You cannot merge a party that is defined as a key member on a project.
	PA_CONTROL_ITEMS		
	PA_PERCENT_COMPLETES		
	PA_PROJECT_REQUESTS		
	PA_RESOURCE_TXN_ATTRIBUTES		
	PA_CI_IMPACTS		
	PA_PROJECT_SETS_B		
Proposals	PRP_EMAIL_RECIPIENTS	Transferred	None
	PRP_PROPOSALS		

Product Name	Tables affected	Action	Validations
Quality	QA_RESULTS	Transferred	None
Receivables	AR_CMGT_CASE_FOLDERS	Transferred	None
	AR_CMGT_CREDIT_REQUESTS		
	AR_CUSTOMER_CALLS_ALL		
	AR_CUSTOMER_CALLS_TO_PICS		
Sales	AS_ACCESSES_ALL	Merged	None
	AS_CHANGED_ACCOUNTS_ALL		
	AS_CURRENT_ENVIRONMENT		
	AS_INTERESTS_ALL		
	AS_LEAD_COMPETITORS		
	AS_LEAD_CONTACTS_ALL		
	AS_LEADS_ALL		
	AS_OPP_WORKSHEET_LINES		
	AS_SALES_CREDITS		
	AS_SALES_CREDITS_DENORM		
	AS_SALES_LEAD_CONTACTS		
	AS_SALES_LEADS		
	AS_ACCOUNT_PLANS	Transferred	None

Product Name	Tables affected	Action	Validations
Service	CS_ESTIMATE_DETAILS CS_HZ_SR_CONTACT_POINTS CS_INCIDENTS_ALL_B CS_INCIDENTS_AUDIT_B	Merged	If a Service Request has more than one contact, then these contacts are merged. If duplicate contact points exist for the two contacts that were merged, and these duplicate contact points are then merged, then it could result in duplicate records in CS_HZ_SR_CONTACT_POINTS. In this case, the duplicate records are deleted.
	CS_CHG_SUB_RESTRICTIONS	Transferred	None
Service Contracts	OKS_BILLING_PROFILES_B OKS_K_DEFAULTS OKS_SERV_AVAIL_EXCEPTS OKS_QUALIFIERS	Transferred	None
Shipping Execution	WSH_CARRIERS WSH_CARRIER_SITES	None	If the party has been used as a freight carrier or has carrier sites, then the merge cannot be completed.
Site Management	RRS_SITES_B	Merged	If party is not a real estate party.

Product Name	Tables affected	Action	Validations
Sourcing	PON_ATTRIBUTE_LISTS PON_AUCTION_EVENTS PON_AUCTION_HEADERS_ ALL PON_AUCTION_TEMPLATE S PON_BIDDERS_LISTS PON_BIDDING_PARTIES PON_BID_HEADERS PON_CONTRACTS PON_DISCUSSIONS PON_PARTY_PREFERENCES PON_TE_RECIPIENTS PON_TE_VIEW_AUDIT PON_THREADS PON_THREAD_ENTRIES	None	If the party has a Sourcing use, then the merge request will be denied.
Spares Management	CSP_MOVEORDER_HEADE RS CSP_PACKLIST_HEADERS	Transferred	None
Student Systems	All tables with an IGS_ prefix	None	If the party is linked to records in any Student Systems table, the merge request will be denied.
Supply Chain Intelligence	OPI_DBI_COGS_F ISC_BOOK_SUM2_PDUE_F ISC_BOOK_SUM2_PDUE2_F ISC_BOOK_SUM2_BKORD_F ISC_BOOK_SUM2_F ISC_DR_REPAIR_ORDERS_F	Transferred	None

Product Name	Tables affected	Action	Validations
Territory Manager	JTF_TERR_VALUES_ALL	Transferred	None
	JTF_TTY_NAMED_ACCTS	Transferred or Deleted	
Trade Management	OZF_CLAIMS_ALL	Transferred	None
	OZF_CLAIMS_HISTORY_ALL		
	OZF_CLAIM_LINES_ALL		
	OZF_CLAIM_LINES_HIST_ALL		
	OZF_CUST_TRD_PRFLS_ALL		
	OZF_CODE_CONVERSIONS_ALL		
	OZF_RESALE_BATCHES_ALL		
	OZF_RESALE_LINES_INT_ALL		
	OZF_RESALE_HEADERS_ALL		
	OZF_RESALE_LINES_ALL		
	OZF_REQUEST_HEADERS_ALL_B		
	OZF_OFFERS		
	OZF_ACTIVITY_CUSTOMERS		
	OZF_ACCOUNT_ALLOCATIONS		
	OZF_ACT_BUDGETS		
Trading Community Architecture	See: Party Merge Overview, <i>Oracle Trading Community Architecture User Guide</i> .		

Product Name	Tables affected	Action	Validations
Transportation Execution	FTE_LOCATION_PARAMETERS	Transferred	None
XML Gateway	ECX_DOCLOGS ECX_OUTBOUND_LOGS ECX_TP_HEADERS	Transferred	None

Related Topics

Party Merge Impact, page 8-2

Party and Account Merge Impact Overview, page 8-1

Account Merge Impact

This section provides details regarding how account merge affects the data in different applications within the Oracle E-Business Suite.

Advanced Global Intercompany System (AGIS)

When two customer accounts are merged, the master account will replace the merge-from account in any netting agreements including the merge-from account. Similarly, the master account site use will replace the merge-from account site use in any netting agreements including the merge-from account site use.

If the merge results in having duplicate entries of customers or customer site uses in a given netting agreement, the lower priority customer or customer site use entry will be removed from the netting agreement.

Advanced Pricing

The Advanced Pricing merge process transfers the following information to the master account:

- Customer accounts and account sites can be used as pricing qualifiers in the Advanced Pricing application. Any record referring to the candidate customer account or site as the pricing qualifier is updated to look at the master customer account or site record.
- Any agreements associated with the customer account or account sites.

Collections

The following information transfers to the master account record:

- The debtor's promise to pay
- Promise to pay history associated with the customer account

Contracts Core

The following information transfers to the master account record:

- Customer account in contract tables
- Customer account, customer address and customer site mentioned in rules
- References to contract line and item that has been associated with the duplicate account or account site
- If the accounts belong to different parties, then the party role record is updated with the master party information

CRM Foundation - Interaction History

During account merge, all interaction activity information associated with the duplicate account is transferred to the master account record.

CRM Foundation - Tasks

Tasks can be opened by a customer or on their behalf. The task has to be associated to the correct customer account or account site. Therefore, when customer accounts are being merged, the tasks are transferred to the master customer account.

Validations

The following logic has been incorporated to ensure that the tasks look at the correct account site information:

- If the accounts being merged belong to the same party then the party site information is not updated.
- If the accounts being merged belong to different parties and duplicate account has both party site and corresponding, account site information then the task is updated to look at the surviving party, party site and account.
- If the accounts being merged belong to different parties and duplicate account has both party site does NOT have corresponding account site information then the

merge is declined.

Customer Care

The Customer Care merge process transfers information to the master account about relationship plans, which allow companies to automate their customer service practices and provide a proactive and consistent way to take care of the customers needs.

E-Business Tax

Validations

- If the addresses are set up for tax validation in Geography Hierarchy, then the address elements defined in the tax usage must match. If one address is created with different values for these address elements, then you cannot merge these two addresses. See: *Managing Validations, Oracle Trading Community Architecture Administration Guide*.

For example, Address 1 is created in a country that is set up with City, County and State as fields that are mandatory for tax validation. Address 2 is created in the same country. To merge these two addresses, the city, county, and state for both addresses must be exactly the same.

- If the addresses are not set up for tax validation in Geography Hierarchy, then you can merge the addresses as long as the country is the same.
- If you have addresses, one who is setup for tax validation and one who is not, then you cannot merge the addresses.

Exchange

If the duplicate account belongs to an exchange user, then the exchange application does not allow the merge to go through.

Federal Financials

The following information transfers to the master account record:

- Customer finance charge information associated with the account
- AR/AP netting customer vendor reference information
- Interagency information used by the FMS Form 224 Statement of Transaction report, SF 1081 Voucher and Schedule of Withdrawals and Credit process
- Cash receipt batch information used by the Federal Cash receipt process

- Finance charges information associated with invoices entered in Receivables
- Receivables transactions created by the IPAC Transaction process
- Cash receipt batch information associated to the account site use

Global Accounting Engine

When two customer accounts are being merged, accounting events are generated. An accounting event is a note in Oracle Applications to indicate that something relevant has occurred and that accounting entries should be generated. Later, when they are translated, these accounting events generate new accounting entries against the control accounts of the candidate and the master records. This has the net effect of transferring the control account balances from the candidate record to the master record.

Global Financials

Global Financials Common Country Features

Oracle Receivables lets you charge interest against customers who have overdue or late invoices. The interest charged on a customer's overdue invoices and late payments are charged to the customer account. When two customer accounts are merged, the Interest invoices are transferred from the duplicate customer account to the master customer account's bill-to site.

Oracle Financials for Asia Pacific

The Oracle Financials for Korea has some global descriptive flexfield information associated at the account site level. This information is merged when two customer accounts are merged.

Oracle Financials for Latin America

When you merge accounts using the Receivables module in the Oracle Financials for Brazil, this transfers the following information to the master account:

- Bank return documents associated with the customer account.
- Remittance occurrences for collection documents.
- Related follow up occurrences for the remittance occurrence.
- Payment schedule information.
- Accounting entries that have been successfully transferred from the subledgers to Oracle General Ledger.

- Oracle Financials for Brazil also has some global descriptive flexfield information (Tax Payer ID) associated at the account site level. This information is merged when two customer accounts are merged.

For the Receivables module of Oracle Financials for Latin America, the following information is deleted when two accounts are merged:

- Tax profile information which determines tax for a customer account site
- Exceptions to determine tax for a customer account site
- Legal messages for tax rules defined for the customer account
- Rules for determining tax that is associated with the account or account site

Oracle Financials for Argentina has some global descriptive flexfield information (Tax Payer ID) associated at the account level. This information is merged when two customer accounts are merged.

Oracle Financials for Chile has some global descriptive flexfield information (Tax Payer ID) associated at the account level. This information is merged when two customer accounts are merged.

Oracle Financials for Colombia has some global descriptive flexfield information (Tax Payer ID) associated at the account level. This information is merged when two customer accounts are merged.

Grants Accounting

The following information transfers to the master account record:

- Award information regarding grants received from a funding agency for execution of projects
- Contact information for the awards
- The send-to information for the reports present for the award and installments being transferred

Incentive Compensation

The following information is transferred to the master customer account:

- Transactional data collected from external systems such as Receivables and stored in interface table in Sales Compensation application
- The same transactional data that is validated and loaded into the Commission headers table

Installed Base

The following information transfers to the master account record:

- Instance's owner party account, bill-to and ship-to addresses
- System's owner account, bill-to and ship-to addresses
- Transactions pertaining to system's bill-to and ship-to addresses
- Transactions pertaining to party accounts and their bill-to and ship-to addresses

Inventory

The following information merges with the master account record:

- Items demand and reservation information associated with a customer account
- Record of every material transaction of a serialized unit in the inventory that is associated with a customer account

iStore

The following information is taken care of as part of account merge:

- Duplicate account's shopping lists will always be transferred to the master account.
- Pre-IBE.O (11.5.9) If master account does not have express checkout setting, the duplicate account's records will be transferred. If master account already has a record in this table, then the duplicate account's record will be deleted.
- IBE.O (11.5.9) Duplicate account's record will always be deleted.
- If the shared cart is shared to both the master account and the duplicate account, the shared cart record for the duplicate account will be deleted from this table. Otherwise all the shared carts will be transferred to the master.
- Duplicate party's active cart will always be deleted.

Validations

iStore account merge doesn't allow merge across organizations.

Loans

The following information transfers to the master account record:

- Loan information
- Loan participants (borrower, co-borrower, and guarantor) information

Master Scheduling and Planning

The following information transfers to the master account record:

- Forecast consumption information associated with the customer account
- Material requirements forecasts associated with the customer account
- Forecast over-consumption entries associated with the customer account
- Information regarding changes to sales order that affects forecast consumption
- Sourcing information of an item in an organization

Multi -Currency Credit Checking

Information about the relationship between a credit limit and a credit usage rule set can be associated with a customer account or with a customer account site. The credit usage rule defines the set of currencies that shares a predefined credit limit during the credit checking process. When two customer accounts are merged, the credit usage information for the duplicate customer account is deleted.

Order Capture

The following information transfers to the master account record:

- The header data for an order capture quotation that is associated with a customer account
- Order line or quote information, which includes the item, item organization, unit of measure, quantity ordered, and so on
- Shipping information for a quote

Order Management

The following information transfers to the master account record:

- Order header and header history information
- Order header acknowledgment information
- Order line details and history information

- Order line acknowledgment information
- Attachment rules of an order
- Defaulting rules associated with the customer account or account sites
- Processing constraint associated with the account or site
- Holds defined to halt the processing of orders and returns
- Hip tolerances for an item that is at the account or account site level
- Sets for an order for shipping at site level

Partner Management

The following information merges with the master account record:

- Partner referrals and deal registrations

Payables

Payables stores the bank information related to the customer. When you merge customer accounts, the bank accounts are transferred to the master customer account or account site uses.

If the master customer account or account site use has more than one primary bank for the same currency, the primary flag of the most recently updated customer account or site use is cleared.

Payments

When customer accounts are merged, then any active payment instruments such as credit cards, debit cards, or bank accounts associated with any merging account are moved under the master account.

In addition to the payment instruments, an account will have payment attributes. These attributes are copied over to the master account if they don't already exist there. The list of payment methods associated with the master account will include all the payment methods that were associated with any of the merged accounts.

Transactions for the account or accounts being merged into the surviving account will be transferred to the master account.

Projects

When two customer accounts merge, the following information is updated to look at the master customer account:

- Project information
 - Project customer and customer billing contribution
 - Project customer bill-to and ship-to addresses
 - Project customer contacts
 - Customer billing retention setup
 - Work sites defined at the task level
- Agreements
- Invoice information
 - Draft invoice bill-to and ship-to addresses
 - Draft invoice lines work site
- Inter-company billing customer

Validation

If the resulting customer account has more than ninety-nine agreements, then the merge cannot be completed.

Property Manager

The following information transfers to the master account record:

- Billing terms of leases associated with the duplicate customer account
- Billing items associated with the billing terms
- Space assignments belonging to a customer account

Provisioning

In Service Fulfillment Manager, when two customer accounts are merged, the following information is affected:

- SFM Order headers are transferred to the master customer account
- The Install at site at the SFM Order Line level is set to the new customer site

Public Sector Financials (International)

The following information transfers to the master account record:

- Dialog unit, which is a collection of transactions requiring approval of Oracle Receivables and Payables sub-ledger transactions
- Transaction unit, which consists of dialog units batched together for approval
- Dunning charges linked to dunned payment schedules
- Extensions of the dunning letter set lines which holds the values for multiple currencies for each letter in the dunning letter set
- Associations between customer accounts and suppliers
- Standard charge information for generating periodical invoices
- Records for deriving transactions available for netting purposes
- Information on single third party netting transactions

Purchasing

In purchasing, the following information is impacted when two customer accounts are merged:

- For requisition lines sourced internally (Internal requisitions), the deliver to location is updated to point to the location associated with the new Customer Account

Receivables

The following information transfers to the master account record:

- Record of the calls made for a past due customer account or transaction
- Correspondence information such as account statements, dunning letters, and customer calls available for an account
- Consolidated billing invoice information associated with the duplicate customer account
- Receipt information associated with the customer account
- Information about any activity that occurs against an invoice, debit memo, chargeback, credit memo, on-account credit, or receipt

- Invoice, debit memo, commitment, bills receivable, and credit memo header information associated with the customer account
- Transaction header and line information
- Tax exemption details for either customer accounts and sites
- Transactions present in the AutoInvoice interface tables
- Receipts present in the Postbatch interim tables
- Credit request associated with the customer account
- Case folder associated with the customer account
- Transactions present in the summary tables and associated with the customer account

Release Management

The following information is transferred to the master customer account or account site:

- Cumulative accounting (CUM) key values associated with the account or site
- Header and line level schedule information associated with accounts

Service

All the service requests associated with the customer accounts are merged with the records in the merge master account.

Service Contracts

The following information transfers to the master account or site:

- The billing profile contains the customer's billing address, as well as other billing information such as summary or detailed bill and so on. The billing profile information attached to the duplicate record is transferred to the master account site.
- Accounts and account sites can be used as pricing qualifiers against a service contract. Any record referring to the candidate account or account site as the pricing qualifier is updated to look at the master account or account site record.

Shipping Execution

The following information transfers to the master account record:

- Picking rules associated with the account.
- Picking batches associated with the account.
- Delivery information associated with the account.
- Trip stop information associated with the customer account.
- Calendar information associated with the customer account.

The following information is transferred to the master record during account or site merge:

- Calendar assignments associated with accounts or account sites.
- If the delivery lines are shipped, then that information is transferred to the account or site.
- If the delivery lines are not shipped, not packed, and not assigned to a delivery, then the lines, account and locations are transferred.
- If delivery lines are not shipped, packed into a container, and not assigned to a delivery, then lines account and locations are transferred, lines are unpacked from container, and exception is logged against the immediate container.

- If delivery lines are not shipped or assigned to a delivery but not packed, then lines account and locations are transferred.

After transfer, if a delivery happens to have delivery lines with more than one location, then the transferred delivery lines are unassigned from the delivery and an exception is logged against the delivery.

- If delivery lines are not shipped, packed into a container, and assigned to a delivery, then lines account and locations are transferred.

After transfer, if a delivery happens to have delivery lines with more than one location, then the transferred delivery lines are unpacked and unassigned from the delivery and an exception is logged against the delivery.

- Open deliveries, their associated containers account, and locations are transferred. After transfer, if a stop happens to have delivery with more than one location, then the transferred delivery is unassigned from the trip stop and an exception is logged against the trip stop.
- Stop's locations associated with transferred deliveries are transferred.
- Open empty deliveries account and locations are transferred.

Validation

The locations for completed shipments are not merged.

Account Merge processes will be vetoed only if the organization for which the records are being merged is WMS enabled and there is a change in ship-to address for shipment lines which are staged (picked) and packed but not yet confirmed for shipment.

Spares Management

Resources with ship to address can be assigned to a customer account. When two customer accounts are merged, the resource is merged with the record associated with the master customer account.

Trade Management

The following information is transferred to the master account record:

- Account and product information required by Account Manager Dashboard
- Account for customer targets
- Beneficiary and account for an offer
- Billing and shipping account and account relationship information for a claim and claim history
- Buying group on a claim line and claim line history
- Code conversion mappings
- End customer, partner and reseller account for a request header
- Funds utilized
- Retail price information for products
- Trade profiles

Trading Community Architecture

In TCA the following information is transferred when two accounts are merged:

- Roles that a party performs in relation to a customer accounts
- Account relationships associated with the customer account

The following information is copied to the master customer account

- Account sites associated with the duplicate customer account
- Contact points associated with the customer account if the two customer accounts being merged belong to different parties
- Contacts are copied if a matching record cannot be found in the master record

The following information is merged during customer account merge:

- Customer profile classes
- Customer profile class amounts

Training Administration

The following information transfers to the master account record:

- Information related to customer's agreement
- Information about student enrollment
- Finance charge information associated with an account
- Information regarding the relationship between an event or a class with a customer account
- Training history associated with the customer account

Related Topics

Account Merge Impact Reference by Application, page 8-49

Party and Account Merge Impact Overview, page 8-1

Account Merge Impact Reference by Application

This table shows the results of merging customer accounts using applications in the Oracle E-Business suite, describing the affected tables, the transfer or merge action, and the validations performed for each application prior to completion of the account merge process.

Product Name	Tables affected	Action	Validations
Advanced Global Intercompany System (AGIS)	FUN_NET_CUSTOMERS_ALL	Transferred	None
Advanced Pricing	QP_QUALIFIERS OE_AGREEMENTS_B	Conditionally transferred	The pricing qualifier information is transferred to the master party record after ensuring that a similar qualifier does not exist for the Master account or account site.
Collections	IEX_PROMISE_DETAILS	Transferred	None
Contracts Core	OKC_K_ITEMS OKC_K_PARTY_ROLES_B OKC_RULES_B	Transferred	None
CRM Foundation - Interaction History	JTF_IH_ACTIVITIES	Transferred	None
CRM Foundation - Tasks	JTF_TASKS_AUDITS_B JTF_TASKS_B JTF_PERZ_QUERY_PARAM	Transferred	The following logic has been incorporated to ensure that the tasks look at the correct account site information: If the accounts being merged belong to the same party, then the party site information is not updated If the accounts being merged belong to different parties and duplicate account has both party site and corresponding account site information, then the task is updated to look at the surviving party, party site and account. If the accounts being merged belong to different parties and the duplicate account does not have corresponding account site information, then merge is declined.

Product Name	Tables affected	Action	Validations
Customer Care	CSC_CUST_PLANS CSC_CUST_PLANS_AUDIT CSC_CUSTOMERS CSC_CUSTOMERS_AUDIT_HI ST CSC_CUSTOMIZED_PLANS	Merged	None
E-Business Tax	HZ_GEO_NAME_REFERENCES	None	Vetoed in certain conditions.
Exchange		None	If the party has an Exchange use, then the request will be denied.
Federal Financials	FV_CUST_FINANCE_CHRGS_ ALL FV_CUST_VEND_XREFS FV_INTERAGENCY_FUNDS_ ALL FV_INTERIM_CASH_RECEIPT S_ALL FV_INVOICE_FINANCE_CHR GS_ALL FV_IPAC_TRX_ALL	Transferred	None
Global Accounting Engine	AX_EVENTS	Transferred	New accounting entries are created which have the effect of transferring information
Global Financial - Financials Common country	JG_ZZ_INTEREST_INVOICES_ ALL	Transferred	None

Product Name	Tables affected	Action	Validations
Global Financials Latin America - Localization	For Brazil:	Transferred	None
	JL_BR_AR_BANK_RETURNS		
	JL_BR_AR_OCCURENCE_DOCUMENTS		
	JL_BR_AR_PAY_SCH_UPD		
	JL_BR_BALANCES_ALL		
	JL_BR_JOURNALS_ALL		
	For LTE:	Transferred	None
	JL_ZZ_AR_TX_CUS_CLS_ALL		
	JL_ZZ_AR_TX_EXC_CUS_ALL		
	JL_ZZ_AR_TX_LGL_MSG_ALL		
Grants Accounting	GMS_AWARDS_ALL	Transferred	None
	GMS_AWARDS_CONTACTS		
	GMS_DEFAULT_REPORTS		
	GMS_REPORTS		
Incentive Compensation	CN_COMM_LINES_API_ALL	Transferred	None
	CN_COMMISSION_HEADERS_ALL		
Installed Base	CSI_IP_ACCOUNTS	Transferred	None
	CSI_ITEM_INSTANCES		
	CSI_SYSTEMS_B		
	CSI_T_PARTY_ACCOUNTS		
	CSI_T_TXN_SYSTEMS		
Inventory	MTL_DEMAND	Merged	None
	MTL_UNIT_TRANSACTIONS		

Product Name	Tables affected	Action	Validations
iStore	IBE_ACTIVE_QUOTES_ALL IBE_ORD_ONECLICK_ALL IBE_SH_QUOTE_ACCESS IBE_SH_SHP_LISTS		iStore account merge doesn't allow merge across organizations. If the shared cart is shared to both the master account and the duplicate account, the shared cart record for the duplicate account will be deleted from this table. Otherwise all the shared carts will be transferred to the master account.
Loans	LNS_LOAN_HEADERS_ALL LNS_PARTICIPANTS	Transferred	None
Master Schedule and Planning	MRP_FORECAST_DATES MRP_FORECAST_DESIGNATORS MRP_FORECAST_UPDATES MRP_SALES_ORDER_UPDATES MRP_SR_ASSIGNMENTS	Transferred	None
Multi-Currency Credit checking	HZ_CREDIT_USAGES	Deleted	None
Order Capture	ASO_QUOTE_HEADERS_ALL ASO_QUOTE_LINES_ALL ASO_SHIPMENTS	Transferred	None

Product Name	Tables affected	Action	Validations
Order Management	OE_ATTACHMENT_RULE_ELEMENTS	Merged	None
	OE_CUST_ITEM_SETTINGS		
	OE_SETS		
	OE_DEF_ATTR_DEF_RULES		
	OE_DEF_CONDN_ELEMS		
	OE_DROP_SHIP_SOURCES		
	OE_HEADER_ACKS		
	OE_HEADERS_IFACE_ALL		
	OE_HOLD_SOURCES		
	OE_LINE_ACKS		
	OE_LINES_IFACE_ALL		
	OE_ORDER_HEADER_HISTORY		
	OE_ORDER_HEADERS_ALL		
	OE_ORDER_LINES_ALL		
	OE_ORDER_LINES_HISTORY		
	OE_PC_VTMPLT_COLS		
Partner Management	PV_REFERRALS_B	Merged	None
Payables	AP_BANK_ACCOUNTS_ALL	Transferred	None
Payments	IBY_CREDITCARD	Merged	Taxpayer ID is the same.
	IBY_ACCOUNT_OWNERS	Merged or Transferred	Taxpayer ID is the same.
	IBY_EXTERNAL_PAYEES_ALL		
	IBY_EXTERNALPAYERS_ALL		
	IBY_PMT_INSTR_USES_ALL		

Product Name	Tables affected	Action	Validations
	IBY_DOCS_PAYABLE_ALL	Transferred	Taxpayer ID is the same.
	IBY_EXT_PARTY_PMT_METHODS		
	IBY_FNDCT_TX_EXTENSIONS		
	IBY_PAYMENTS_ALL		
	IBY_TRXN_SUMMARIES_ALL		
Projects	PA_AGREEMENTS	Transferred	If the resulting customer account has more than ninety-nine agreements, then the merge cannot be completed.
	PA_DRAFT_INVOICE_ITEMS		
	PA_PROJECT_CONTACTS		
	PA_PROJECT_CUSTOMERS		
	PA_TASKS		
Property Manager	PA_IMPLEMENTATIONS_ALL	Transferred	None
	PN_PAYMENT_TERMS_ALL		
Provisioning	PN_SPACE_ASSIGN_EMP_ALL	Transferred	None
	XDP_ORDER_HEADERS		
	XDP_ORDER_LINE_ITEMS		

Product Name	Tables affected	Action	Validations
Public Sector Financials (International)	IGI_DUN_CHARGE_ALL	Transferred	None
	IGI_DUN_CUST_LETTER_SET_LINES		
	IGI_EXP_DIAL_UNIT_DEF_ALL		
	IGI_EXP_TRAN_UNIT_DEF_ALL		
	IGI_PO_VENDORS		
	IGI_RA_CUSTOMERS		
	IGI_RPI_STANDING_CHARGES_ALL		
	IGI_STP_CANDIDATES_ALL		
	IGI_STP_PACKAGES_ALL		
Purchasing	PO_REQUISITION_LINES_ALL	Transferred	None

Product Name	Tables affected	Action	Validations
Receivables	AR_CASH_RECEIPTS	Transferred	None
	AR_CMGT_CASE_FOLDERS		
	AR_CMGT_CREDIT_REQUESTS		
	AR_CONS_INV		
	AR_CORRESPONDENCES		
	AR_CUSTOMER_CALL_TOPICS		
	AR_INTERIM_CASH_RECEIPT_LINES		
	AR_INTERIM_CASH_RECEIPTS		
	AR_PAYMENT_SCHEDULES		
	AR_TRX_BAL_SUMMARY		
	AR_TRX_SUMMARY		
	RA_CUSTOMER_TRX		
	RA_INTERFACE_LINES		
	RA_TAX_EXEMPTIONS		
	RA_TAX_EXEMPTIONS_ALL		
Release Management	RLM_CUST_ITEM_CUM_KEYS	Transferred	Vetoed under certain conditions
	RLM_INTERFACE_HEADERS		
	RLM_INTERFACE_LINES		
	RLM_SCHEDULE_HEADERS		
	RLM_SCHEDULE_LINES		
Service	CS_INCIDENTS_ALL_B	Merged	None
Service Contracts	OKS_BILLING_PROFILES_B	Transferred	None

Product Name	Tables affected	Action	Validations
Shipping Execution	WSH_CALENDAR_ASSIGNMENTS	Transferred	Vetoed under certain conditions.
	WSH_DELIVERY_DETAILS		
	WSH_NEW_DELIVERIES		
	WSH_TRIP_STOPS		
	WSH_PICKING_BATCHES		
	WSH_PICKING_RULES		
Spares Management	CSP_RS_CUST_RELATIONS	Merged	None
Trade Management	OZF_CLAIMS_ALL	Transferred	None
	OZF_CLAIMS_HISTORY_ALL		
	OZF_CLAIM_LINES_ALL		
	OZF_CLAIMS_LINES_HISTORY_ALL		
	OZF_CUST_TRD_PRFLS_ALL		
	OZF_CODE_CONVERSIONS_ALL		
	OZF_FUNDS_UTILIZED_ALL_B		
	OZF_REQUEST_HEADERS_ALL_B		
	OZF_OFFERS		
	OZF_ACTIVITY_CUSTOMERS		
	OZF_ACCOUNT_ALLOCATIONS		
	OZF_CUST_DAILY_FACTS		
	OZF_RETAIL_PRICE_POINTS		
Trading Community Architecture	HZ_CUST_ACCOUNT_ROLES	Transferred	None
	HZ_CUST_RELATE_ALL		

Product Name	Tables affected	Action	Validations
Training Administration	HZ_CONTACT_POINTS	Copied	The contact points are copied if the customer accounts being merged belong to different parties.
	HZ_CUST_ACCT_SITE_USES		
	HZ_CUST_ACCT_SITES		
	HZ_ORG_CONTACTS		
		Merged	The org contacts are copied if a matching record does not exist in the master customer account.
	HZ_CUST_PROFILE_CLASS_A MTS		
	HZ_CUST_PROFILE_CLASSES		None
		Transferred	None
	OTA_BOOKING_DEALS		
	OTA_DELEGATE_BOOKINGS		
	OTA_FINANCE_HEADERS		
	OTA_EVENT_ASSOCIATIONS		
	OTA_NOTRNG_HISTORIES		

Related Topics

Account Merge Impact, page 8-36

Party and Account Merge Impact Overview, page 8-1

Glossary

account

The business relationship that a party can enter in to with another party. The account has information about the terms and conditions of doing business with the party.

account relationship

A relationship that implies financial responsibility between the owners of the accounts. For example, a customer account relationship lets you apply payments to and create invoices for related customers, as well as apply invoices to related customers' commitments.

account role

The role that a party has in regard to controlling or using an account, for example, owner, authorized user, or contact.

account site

A party site that is used within the context of an account, for example, for billing or shipping purposes.

acquisition

The part of the DQM matching process that matches input record attributes against the attributes in the staged schema to get a smaller group of records that form the work unit. This process narrows down the records that can be scored in the scoring part of the matching process.

acquisition attribute

Attributes used for selecting the most relevant subset of records for matching, or the work unit. For example, to get records based on D-U-N-S Number, you include the D-U-N-S Number attribute for acquisition.

adapter

A device that enables different pieces of software to be compatible. In the context of address validation, adapters facilitate integration between the TCA Registry and a third party or a deploying company data source.

area code time zone

A time zone that corresponds to a specific area code, used for countries that have multiple time zones.

attribute

Corresponds to a column in a TCA Registry table, and the attribute value is the value that is stored in the column. For example, Name is an attribute and the actual values of party names are stored in a column in the HZ_PARTIES table.

attribute group

A group of closely related attributes within the same entity. Each group has a primary attribute. The values for each attribute in a group must come from the same data source.

automatic merge threshold

Value used in DQM matching to evaluate match scores. A record with a score that exceeds the automatic merge threshold is by default selected for party merge.

batch de-duplication

The process within TCA Bulk Import of identifying and resolving duplicates within an import batch. The duplicates are resolved in the interface tables, before actual import into the TCA Registry.

black box

An abstraction of a device or system in which only its externally visible behavior is considered and not its implementation or inner workings. In the context of TCA adapters for address validation, a black box is a central XML open-standards based functionality that allows integration between the TCA Registry and third party or other data sources, through adapters. The black box accepts requests from callers, sends requests to adapters, and receives the adapters' responses.

bulk duplicate identification

The Data Quality Management process of identifying duplicates for a large number of records within the TCA Registry. The process involves only match rules with the Bulk Duplicate Identification type.

Business Information Report (BIR)

A report that provides many of the data elements from the D&B database in a standard report format.

business object

An abstract grouping of Oracle Trading Community Architecture entities to form an operable, logical business unit. Business objects contain attributes specific to that object,

as well as embedded business objects, business structures, and granular entities.

See also: business structure, page Glossary-3 and entity, page Glossary-6

business purpose

Also known as site use, a business purpose describes which functions are performed at a particular customer account site. For example, the address where you ship your goods has a ship-to business purpose, and the address where you will send dunning letters has a dunning business purpose.

business structure

The same as a business object, except that you cannot perform operations and services on them individually, for example with APIs. Business structures can contain embedded business structures and granular entities, but not embedded business objects.

See also: business object, page Glossary-2 and entity, page Glossary-6

caller

A source that sends requests to black boxes for data services through integration with adapters. Examples of callers are concurrent programs and APIs.

candidate record

See: duplicate, page Glossary-6

category use

Controls which object can use a given class category. For example, the SIC code 1977 can be used only by parties of type Organization.

certification level

A level that identifies the extent to which a record is certified, according to quality standards that your organization sets. The record is manually evaluated and assigned the certification level.

circular relationship

Circular relationships participate in a circle of relationships between entities. For example, Party A is related to Party B, who is related to Party C, who is related to Party A.

class category

Consists of multiple classification codes that allow for broad grouping of entities. Categories can have rules pertaining to a set of class codes, for example, Multiple Parent, Multiple Assignment, and Leaf Node Assignment rules.

class code

Provides a specific value for a class category.

classification

A means of categorizing different objects in Oracle Applications. Classifications are not limited to parties but can include projects, tasks, orders, and so on. Classifications can be user defined or based on external standards, such as the NAICS (North American Industrial Classification System), NACE (European Union's Statistical Classification of Economic Activity), or SIC (Standard Industrial Classification).

code relationship

Relates various class codes within a category in a hierarchy. For example, IT is a parent of Software.

contact point

A means of contacting a party other than postal mail, for example, phone number, e-mail address, fax number, and so on.

contact preference

Provides information about when and how parties prefer to be contacted. You can specify the subjects on which to contact a party, the number of times to contact a party, and the reason for specifying a contact preference. You can also set preferences for a party's e-mail address or phone number.

country structure

A hierarchical definition of geography types for a country. For example, the structure for United States is: State, County, City, then Postal Code.

See also: geography type, page Glossary-6

country time zone

A time zone that applies to an entire country.

customer

A person or organization that the deploying company has a selling relationship with, regardless of whether anything has been purchased or serviced. A selling relationship can be established simply by negotiation terms that will be used if you later sell products.

customer profile class

Specific credit limits, payment terms, statement cycles, invoicing, and discount information that you use to categorize customer accounts. For each profile class, you can also define amount limits for your finance charges, dunning, and statements for

each currency in which you do business.

D&B hierarchy

Contains hierarchical corporate relationships that D&B provides through batch load and the online Enterprise Management Global Data Product (GDP). You can view this corporate structure in a relationship hierarchy.

data element

A piece of information in a data product that you can use to identify, contact, and evaluate the credit risk of parties. The complete D&B database includes over 150 key business data elements. Examples of data elements include the D-U-N-S Number, local business ID, and D&B rating.

data product

A fixed set of data elements from D&B containing country-specific information to meet your business decision-making criteria.

Data Quality Management (DQM)

A set of tools to keep the TCA Registry clean and accurate, with powerful searching, matching, duplicate identification, and merging functionality.

data sharing group

Identifies a subset of party-related data that can be secured. The data sharing group identifies both the types of entities to be protected (such as parties, their addresses, contact points, relationships, and the like) as well as specific criteria to identify which party related data to protect, which can be based on classifications, relationship types, or "created by" modules.

For example, one data sharing group might be created for patients, another for employees, and another for parties classified as both patients and employees. A security administrator may then assign privileged access to create, update, or delete information secured by this data sharing group based on the applicable business policy.

data source

The source of the records in the TCA Registry, for example user entered, third party, or other source system.

deploying company

The Oracle customer that has or will install, implement, and run all or part of the Oracle E-Business Suite.

D-U-N-S (Data Universal Numbering System) Number

The nine-digit identification number assigned by D&B to each commercial entity in its

database. For businesses with multiple locations, each location is assigned a unique D-U-N-S Number.

duplicate

A record that has been identified as a duplicate of at least one other record.

duplicate set

A group of records (such as parties, addresses or relationships) that has been identified as potential duplicates of one another in appearance and/or function.

entity

A group of related attributes in the TCA Registry, for example Organization Profile, Person Profile, Address, and Contact Point.

exact match

Matching method that requires an exact character match, as compared to a search that uses the similarity algorithm.

extensions

Extended attributes and their attribute values. These custom attributes extend the TCA Registry. TCA extensions use the extensibility framework and features from Oracle Product Lifecycle Management (PLM).

file load

Contains information about loading data from one comma-separated value (CSV) file, or file delimited by another allowed character, into the import interface tables. A file load identifies the source file to load, as well as the location, format, and content of the file, and defines how attributes from the file map to the interface table columns.

fuzzy match

Matching method that finds data with only some similarity to the search criteria and compensates for errors in data entry and phonetics.

geography

A defined instance of a geography type. For example, San Jose is a geography of the City geography type.

See also: geography type, page Glossary-6

geography type

A divisional grouping of geographies, either geopolitical, for example City, Province, and District, or physical, for example Island, Mountain, and Continent.

See also: geography, page Glossary-6

geography usage

A classification of a set of geography types to indicate the purpose and use of that data, for example for taxation. For example, the State, County, and City geography types can be used for US sales tax calculation.

See also: geography type, page Glossary-6

geography validation

A process to ensure that addresses have valid geographic information, for example, the correct combination of city, state, and postal code. Because street level data is not included, however, this validation does not ensure that addresses pass postal validation and can have postal deliveries to those locations.

Global Data Product (GDP)

A fixed set of data elements from D&B containing information to meet your business decision-making criteria. The GDP is not country specific and can be purchased globally.

granular entity

See: entity, page Glossary-6

group ID

Identifies records acquired from D&B in the HZ_PARTY_INTERFACE table. For a batch of records with the same ID, you can specify that ID to transfer those records from the interface table into the TCA tables.

hierarchical relationship

A relationship in which a party is ranked above the other. The rank is determined by the role that they are taking in a relationship

hierarchical relationship type

A relationship type that allows hierarchical relationships. A hierarchy can be defined by creating multiple hierarchical relationship type records.

hierarchy

A collection of entities associated with a particular hierarchical relationship type at a given point in time. The hierarchy is a tree structure that shows relationships by organizing entities in hierarchical levels. For a given entity, all entities displayed the level below in the hierarchy are its children, and the entity displayed a level above is its parent.

hierarchy node

An entity in a relationship hierarchy. The node at the top of the hierarchy is the top parent, or root node. Any node without children is a leaf node.

identifying address

The main address for a party, regardless of business purpose. Each party has only one identifying address.

import batch

A set of data to be imported at one time, with one batch per data source. Batches are loaded into the import interface tables and then transferred to the TCA Registry.

input record

The basis for comparison or matching. Input records can be compared to other records in the staged schema to find existing duplicates in the TCA Registry. An input record can also be search criteria or entered party information that is compared to the staged schema to find matches or potential duplicates in the registry.

interface search tables

A set of temporary staged tables with B-Tree indexes, used in Data Quality Management, to store transformed data from TCA Bulk Import interface tables. The interface search tables can be joined with themselves to find duplicates within an import batch, or joined with the staged schema to find duplicates between the interface tables and the TCA Registry.

internal indicator

An attribute that indicates if a party is internal to your organization or not.

leaf child

A record in a hierarchy that does not have any children.

location

A point in geographical space described by an address.

logical entity

See: entity, page Glossary-6

mapped D-U-N-S Number

The D-U-N-S Number associated with the party record that is actively mapped to the D&B data source, through Source System Management. When multiple parties have the same D-U-N-S Number, the party that is actively mapped has the mapped D-U-N-S

Number.

master record

The record that remains after other duplicates in a duplicate set merge or transfer into it.

Master Reference Geography Hierarchy

The geographical data considered as the single source of truth. The geography usage for the entire hierarchy is Master Reference, and defined geography types and geographies are considered master reference geography types and geographies. For example, Country is a universally recognized geography type, and United States is considered a master geography.

See also: geography, page Glossary-6, geography type, page Glossary-6, and geography usage, page Glossary-7

match percentage

A percentage that indicates how closely a search result matches the search criteria. The percentage is the record score divided by the highest possible score.

match rule

A rule that determines which records are matches for an input record. A match rule consists of acquisition attributes that are used for matching and can also include scoring attributes to score the matched records.

match rule set

A match rule of type Set that contains multiple match rules and conditions to determine which rule in the set to use. All rules in a set have the same purpose, either Search or Expanded Duplicate Identification.

match score

The score of an attribute after the original score has been multiplied by the weight percentage. The total score of a record consists of the sum of all match scores from its attributes.

match threshold

Value used in DQM matching to evaluate match scores. A record with a score that exceeds the match threshold is selected as a match for the input record.

merge

The operation that maps one detail entity to another detail entity of the same type, to resolve duplicates.

merge batch

Contains information about the duplicate parties or party sites to merge.

Merge Dictionary

A dictionary that stores the entities and procedures that must be processed to merge party entities for any Oracle application.

merge mapping

The process of evaluating the records in a duplicate set for the purposes of: a) identifying a single record which will survive as the merge master, and b) defining which specific addresses and relationships from each of the remaining duplicates will be brought forward into the merge master.

merge master

See: master record, page Glossary-9

merge request

A request is that is created when a Data Librarian, a system process, or an end user identifies a set of records as duplicates that need to be merged. The Data Librarian has a choice to accept or reject the request. After a merge request is created, accepted, merged, and submitted, the Party Merge process merges the duplicate parties or information.

Multiple merge request

A merge request that contains two or more party records to be merged. In contrast, a single merge request contains only one party record, which means that only the subordinate entities already related to that specific party, such as addresses or contacts, are to be merged.

object

The entity that the subject is related to in either direction of a relationship. For example, if Oracle is the employer of Joe, then Joe is the object. With the other direction stating that Joe is the employee of Oracle, Oracle is the object.

organization person

A person who acts on behalf of or in the context of an organization.

Organization Profile entity

An entity with attributes that describe parties of type Organization.

Other entity

An entity that is not a party profile entity. Other entities include: Address, Contact

Point, Credit Rating, Financial Report, and Relationship entities.

override threshold

Value used in matching to evaluate match scores. The input record can be prevented from entering the TCA Registry if a duplicate is found that exceeds the override threshold.

party

A person, organization, relationship, or collection of parties that can enter into business relationships with other parties.

party preference

Enables you to store a persistent state for a party that is a user of Oracle Applications. For example, in a mobile customer application, you can create and maintain the My Customers list, which is a subset of customers in the TCA Registry. Each user can create a personal list of customers by adding customers from the public database to a personalized customer list. The iReceivables application can also use the party preference feature to store a list of customer accounts frequently accessed by a user.

party profile attributes

Party profile attributes describe basic details of a party, for example name and address. Attribute values are the values that a party has for the attributes. For example, Oracle is the attribute value for the Organization Name attribute. Attribute values can be purchased, entered, or imported into the TCA Registry.

The profile attributes are categorized for parties of type Person and Organization:

- **Person:** Person Profile, Financial Details, Demographics, and Tax Details
- **Organization:** Business Profile, Business Details, Socioeconomic Details, Tax Details, and Special Events

party profile entity

Either the Person Profile or Organization Profile entity. These entities include attributes that describe parties of type Person or Organization.

party site

The association between a party and one or more locations. For example, the headquarters of a company is a party site.

party type

The type of party: Person, Organization, Group, or Relationship.

Person Profile entity

An entity with attributes that describe parties of type Person.

phone format

The format of phone numbers within a country. For example, for the US phone format, you define the phone country code as 01, the fixed area code as three numbers in length, the subscriber number as seven digits in length, and the format style as 999-999-9999.

preprocessing

A process that runs after submitting a new or changing the master of an existing merge request. Preprocessing creates or regenerates the merge request and all suggested mapping defaults.

primary

The primary address, phone, e-mail, or URL for a business purpose. For example, an organization has many addresses for the bill-to purpose. The primary bill-to address is the main one among all of the organizations's bill-to addresses.

primary attribute

The primary attribute of an attribute group.

primary business purpose

The primary business purpose for a specific address, or customer account site.

prospect

A person or organization that a party has a potential selling relationship with. A prospect might or might not become a customer.

purge request

A purge request contains one or more parties to purge from the TCA Registry. Only parties that are marked for purge in the request are actually purged.

quality adjusted match percentage

A match percentage that takes into account the custom-defined quality of the records. The quality adjusted match percentage is calculated by adding the weighted match percentage and the weighted quality percentage.

quality score

A number that represents the quality of the record, with 100 as the highest. The `get_quality_score` procedure, with custom-defined logic, determines the quality score.

quality weighting

The portion of the final quality adjusted match percentage that should be based on quality. The `get_quality_weighting` procedure, with custom-defined logic, determines the quality weighting.

Registry De-Duplication

The process within TCA Bulk Import of identifying and resolving duplicates between an import batch and the TCA Registry. The duplicates are resolved after the actual import into the TCA Registry.

Registry ID

The unique number given to each entity in the TCA Registry.

relationship

A state of connectedness between two entities, consisting of two entities and a relationship phrase pair that belongs to a relationship type. Each relationship has two directions, as determined by the phrase pair.

For example, a relationship states that Oracle is the employer of Joe, as well as that Joe is the employee of Oracle, in the other direction.

relationship group

A mechanism for grouping similar relationship roles and phrases together. As a general rule, this grouping is used to determine which relationship roles and phrases are displayed in application user interfaces but can also be used to group roles and phrases for other functional uses.

relationship hierarchy

A relationship hierarchy is all the entities associated with a particular hierarchical relationship type at a given point in time under a top node, or root. The hierarchy is a tree structure that shows relationships by organizing entities in hierarchical levels. For a given entity, all entities displayed the level below in the hierarchy are its children, and the entity displayed a level above is its parent.

relationship model

A model that allows you to get visibility into the complex relationships among the members of your trading community and to utilize the information to make better business decisions.

relationship phrase

Defines the role of the subject of a relationship. For example, if an organization is an employer of a person, the Employer Of role describes the subject.

relationship phrase and role pair

Consists of a subject relationship phrase and role, an object relationship phrase and role, a subject type, and an object type. Each relationship phrase and role pair must belong to a relationship type. Each relationship type can have one or more relationship phrase and role pairs.

For example, the pair is defined so that Organization is the subject type, Employer Of is the subject phrase, Employer is the subject role, Person is the object type, Employee Of the object phrase, and Employee the object role. When you create a relationship with this phrase and role pair, the parties that you use must match the subject and object types.

relationship role

A term that describes the role that an entity plays in a relationship. Every relationship has two entities and two relationship roles, or a relationship role pair. One role describes the subject entity of the relationship, and the other the object.

For example, if Pat is the employee of Vision, then Pat is the subject party and Vision is the object party. Pat's relationship role is employee, and Vision's role is employer. The role pair is employee/employer.

relationship type

A relationship type is a categorization of relationship phrase pairs and consists of one or more phrase pairs that can be used to create relationships. Hierarchical relationships are created with phrase pairs that belong to a hierarchical relationship type. A relationship type also determines whether circular relationships are allowed when relationships are created with its phrase pairs.

score

Assigned in integer form to attributes in the work unit. Scores are not limited to the range of 1 to 100 and are multiplied by the weight percentage to calculate the match score.

scoring

The process of assigning weighing factors to match results, and grouping and ranking the match results.

scoring attribute

Attribute used to calculate a score for each record in the work unit.

similarity algorithm

Computes the edit distance between two strings, or groups of text, and assigns a percentage value to the result.

The calculation used to determine the similarity percentage is:

1. Determine the edit distance, or the number of changes required to make the longer string match the shorter string.

For example, for Smythe and Smith, the edit distance is two.

2. Subtract the edit distance from the number of characters in the longest string.

Following the example above: $6 - 2 = 4$.

3. Divide the amount calculated in step 2 by the number of characters in the longest string.

Continuing the example: $4/6 = 0.6666$

4. Express the result as an integer.

In this example the result would be a similarity score of 67.

If two strings are identical, then the similarity percentage equals 100. If no characters in the two strings are the same, then the similarity percentage is zero.

Single merge request

A merge request that contains only one party record to be merged. Only the subordinate entities already related to that specific party, such as addresses or relationships, are to be merged. In contrast, a multiple merge request consists of a duplicate set with at least two parties to merge.

Single Source of Truth (SST) record

The record that represents a single view of the most accurate information about a party's profile. The attributes in the SST record can contain information from different data sources, depending on your setup.

site use

See: business purpose, page Glossary-3

Smart Search

A search engine powered by DQM, with results based on the entered search criteria and the match rule used for Smart Search.

source ID

The ID of the record in the legacy, third party, or other external system.

source system

A legacy, third party, or other external system that provides data for the TCA Registry.

source system overwrite rule

Determines if new source system data can overwrite existing user-entered data in the SST record. This rule applies only to user-entered data that previously overwrote source system data.

staged schema

A mirror of the TCA Registry but contains data that are transformed and standardized based on transformation functions for better matching. Data in the staged schema is extracted into an interMedia index for high performance searching.

standardize

Standardizing is a data manipulation technique that improves the quality of matching. Standardizing in Data Quality Management involves transforming words or phrases into the same format.

subject

The entity that the object relates to in either direction of a relationship. For example, if Oracle is the employer of Joe, then Oracle is the subject. With the other direction stating that Joe is the employee of Oracle, Joe is the subject.

System Duplicate Identification (SDI) batch

The output of the System Duplicate Identification (SDI) process. An SDI batch may contain multiple duplicate sets that can be used to create merge requests by the Data Librarian.

TCA Registry

The central repository of party information for all Oracle applications. The party information includes details about organizations and people, the relationships among the parties, and the places where the parties do business.

threshold

A value used to evaluate records, for example to determine if a record is a match or not.

top parent

A record in a hierarchy that does not have any parent. The top parent is a root node.

Trading Community Architecture (TCA)

A model that provides a virtual representation of the community that business is conducted in. This model includes parties and related party entities.

transfer

The operation that moves one detail entity from the duplicate candidate record to the master record, to resolve duplicates.

transformation

A seeded or user-defined rule that transforms and standardizes TCA attribute values into representations that can assist in the identification of potential matches.

transformation function

See: transformation, page Glossary-17

user create and update rule

Determines user privileges to create new records for Other entities and to update Other entity data from source systems..

User-Defined Geography Hierarchy

A classification of geographical data, created from master reference data or manually entered, for specific usage such as tax. While the Master Reference Geography Hierarchy is the source of truth for geography data, for example with all the US states defined, user-defined geography hierarchies contain entities with arbitrary boundaries, for example time zones that encompass various US states in each zone.

See also: Master Reference Geography Hierarchy, page Glossary-9

user overwrite rule

Determines if new user-entered data can overwrite existing source system data in the SST record. Each rule includes all attributes from the party profile entities, and you define the rule for each individual attribute.

validation status code

A code that describes an address's level of validation against a known and authorized source. Address validation adapters assign one of these codes to each address record that is validated. A default code must be reached or exceeded for an address to be updated with data from the authority's database.

weight

A percentage that is assigned to a transformation function and is used to factor the score of an attribute.

weighted match percentage

The original match percentage that is adjusted for the calculation of the final quality adjusted match percentage. For example, if 70% of the final percentage is from the

original percentage, then the original percentage must be adjusted to be out of 70%, not 100%. This adjustment, for the weighted match percentage, is calculated as:

$$\text{Weighted Match Percentage} = \text{Match Percentage} * (100 - \text{Quality Weighting}) / 100$$

weighted quality percentage

The quality score adjusted based on the quality weighting, for the calculation of the final quality adjusted match percentage. For example, if the quality weighting is 30, meaning 30% of the final percentage is from the quality score, then the quality score of the record must be adjusted to be out of 30%. This weighted quality percentage is calculated as:

$$\text{Weighted Quality Percentage} = \text{Quality Score} * \text{Quality Weighting} / 100$$

word replacement

A word mapping that is used to create synonyms which are treated as equivalents for searching and matching. Base words in the party, account, address, or organization contact record are replaced with a normalized word during search to provide consistency in search results.

work unit

Consists of all records from the staged schema with attribute values that match the attribute values of the input record.