

**Oracle® E-Business Tax: Vertex Q-Series and Taxware
Sales/Use Tax System**

Implementation Guide

Release 12

Part No. B25961-01

December 2006

Copyright © 2006, Oracle. All rights reserved.

Primary Author: Desh Deepak, Robert MacIsaac

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS

Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software--Restricted Rights (June 1987). Oracle Corporation, 500 Oracle Parkway, Redwood City, CA 94065.

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

Oracle, JD Edwards, PeopleSoft, and Siebel are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Contents

Send Us Your Comments

Preface

1 License and Support for the Vertex Q-Series and Taxware Sales/Use Tax System

License.....	1-1
Support.....	1-1

2 Installing and Implementing the Vertex Q-Series or Taxware Sales/Use Tax System

Installing the Tax Service Provider Product.....	2-1
Setup Checklist for PrePackaged Tax Service Provider Integration.....	2-1
Setup Checklist for Non-PrePackaged Tax Service Provider Integration.....	2-6

3 Business Processes

Transaction Options in Oracle Receivables.....	3-1
Working with Service Provider Tax Jurisdiction Codes.....	3-1
Monthly Procedures.....	3-2
Exemption Handling.....	3-2
Reconciliation and Audit Procedures.....	3-2
Support Procedures.....	3-4

4 Technical Reference

Available Parameters.....	4-1
Customizable Tax Functions.....	4-1

Storing Tax Information in Descriptive Flexfields and Other Applications.....	4-22
---	------

Send Us Your Comments

Oracle E-Business Tax: Vertex Q-Series and Taxware Sales/Use Tax System Implementation Guide, Release 12

Part No. B25961-01

Oracle welcomes customers' comments and suggestions on the quality and usefulness of this document. Your feedback is important, and helps us to best meet your needs as a user of our products. For example:

- Are the implementation steps correct and complete?
- Did you understand the context of the procedures?
- Did you find any errors in the information?
- Does the structure of the information help you with your tasks?
- Do you need different information or graphics? If so, where, and in what format?
- Are the examples correct? Do you need more examples?

If you find any errors or have any other suggestions for improvement, then please tell us your name, the name of the company who has licensed our products, the title and part number of the documentation and the chapter, section, and page number (if available).

Note: Before sending us your comments, you might like to check that you have the latest version of the document and if any concerns are already addressed. To do this, access the new Applications Release Online Documentation CD available on Oracle MetaLink and www.oracle.com. It contains the most current Documentation Library plus all documents revised or released recently.

Send your comments to us using the electronic mail address: appsdoc_us@oracle.com

Please give your name, address, electronic mail address, and telephone number (optional).

If you need assistance with Oracle software, then please contact your support representative or Oracle Support Services.

If you require training or instruction in using Oracle software, then please contact your Oracle local office and inquire about our Oracle University offerings. A list of Oracle offices is available on our Web site at www.oracle.com.

Preface

Intended Audience

Welcome to Release 12 of the *Oracle E-Business Tax: Vertex Q-Series and Taxware Sales/Use Tax System Implementation Guide*.

This guide assumes you have a working knowledge of the following:

- The principles and customary practices of your business area.
- Computer desktop application usage and terminology.

If you have never used Oracle Applications, we suggest you attend one or more of the Oracle Applications training classes available through Oracle University.

See Related Information Sources on page viii for more Oracle Applications product information.

TTY Access to Oracle Support Services

Oracle provides dedicated Text Telephone (TTY) access to Oracle Support Services within the United States of America 24 hours a day, seven days a week. For TTY support, call 800.446.2398.

Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all

of our customers. For more information, visit the Oracle Accessibility Program Web site at <http://www.oracle.com/accessibility/>.

Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

Structure

- 1 License and Support for the Vertex Q-Series and Taxware Sales/Use Tax System**
- 2 Installing and Implementing the Vertex Q-Series or Taxware Sales/Use Tax System**
- 3 Business Processes**
- 4 Technical Reference**

Related Information Sources

This document is included on the Oracle Applications Document Library, which is supplied in the Release 12 DVD Pack. You can download soft-copy documentation as PDF files from the Oracle Technology Network at <http://otn.oracle.com/documentation>, or you can purchase hard-copy documentation from the Oracle Store at <http://oraclestore.oracle.com>. The Oracle E-Business Suite Documentation Library Release 12 contains the latest information, including any documents that have changed significantly between releases. If substantial changes to this book are necessary, a revised version will be made available on the online documentation CD on Oracle *MetaLink*.

If this guide refers you to other Oracle Applications documentation, use only the Release 12 versions of those guides.

For a full list of documentation resources for Oracle Applications Release 12, see Oracle Applications Documentation Resources, Release 12, Oracle *MetaLink* Document 394692.1.

Online Documentation

All Oracle Applications documentation is available online (HTML or PDF).

- **PDF** - PDF documentation is available for download from the Oracle Technology Network at <http://otn.oracle.com/documentation>.

- **Online Help** - Online help patches (HTML) are available on *OracleMetaLink*.
- **Oracle MetaLink Knowledge Browser** - The *OracleMetaLink* Knowledge Browser lets you browse the knowledge base, from a single product page, to find all documents for that product area. Use the Knowledge Browser to search for release-specific information, such as FAQs, recent patches, alerts, white papers, troubleshooting tips, and other archived documents.
- **Oracle eBusiness Suite Electronic Technical Reference Manuals** - Each Electronic Technical Reference Manual (eTRM) contains database diagrams and a detailed description of database tables, forms, reports, and programs for a specific Oracle Applications product. This information helps you convert data from your existing applications and integrate Oracle Applications data with non-Oracle applications, and write custom reports for Oracle Applications products. Oracle eTRM is available on *OracleMetaLink*.

Related Guides

You should have the following related books on hand. Depending on the requirements of your particular installation, you may also need additional manuals or guides.

Oracle Applications Installation Guide: Using Rapid Install:

This book is intended for use by anyone who is responsible for installing or upgrading Oracle Applications. It provides instructions for running Rapid Install either to carry out a fresh installation of Oracle Applications Release 12, or as part of an upgrade from Release 11*i* to Release 12. The book also describes the steps needed to install the technology stack components only, for the special situations where this is applicable.

Oracle Applications Maintenance Procedures:

This guide describes how to use AD maintenance utilities to complete tasks such as compiling invalid objects, managing parallel processing jobs, and maintaining snapshot information. Part of Maintaining Oracle Applications, a 3-book set that also includes Oracle Applications Patching Procedures and Oracle Applications Maintenance Utilities.

Oracle Applications Maintenance Utilities:

This guide describes how to run utilities, such as AD Administration and AD Controller, used to maintain the Oracle Applications file system and database. Outlines the actions performed by these utilities, such as monitoring parallel processes, generating Applications files, and maintaining Applications database entities. Part of Maintaining Oracle Applications, a 3-book set that also includes Oracle Applications Patching Procedures and Oracle Applications Maintenance Procedures.

Oracle Applications Patching Procedures:

This guide describes how to patch the Oracle Applications file system and database using AutoPatch, and how to use other patching-related tools like AD Merge Patch, OAM Patch Wizard, and OAM Registered Flagged Files. Describes patch types and structure, and outlines some of the most commonly used patching procedures. Part of

Maintaining Oracle Applications, a 3-book set that also includes Oracle Applications Maintenance Utilities and Oracle Applications Maintenance Procedures.

Oracle Applications Upgrade Guide: Release 11i to Release 12:

This guide provides information for DBAs and Applications Specialists who are responsible for upgrading a Release 11i Oracle Applications system (techstack and products) to Release 12. In addition to information about applying the upgrade driver, it outlines pre-upgrade steps and post-upgrade steps, and provides descriptions of product-specific functional changes and suggestions for verifying the upgrade and reducing downtime.

Oracle Alert User's Guide:

This guide explains how to define periodic and event alerts to monitor the status of your Oracle Applications data.

Oracle Application Framework Developer's Guide:

This guide contains the coding standards followed by the Oracle Applications development staff to produce applications built with Oracle Application Framework. This guide is available in PDF format on *OracleMetaLink* and as online documentation in JDeveloper 10g with Oracle Application Extension.

Oracle Application Framework Personalization Guide:

This guide covers the design-time and run-time aspects of personalizing applications built with Oracle Application Framework.

Oracle Applications Concepts:

This book is intended for all those planning to deploy Oracle E-Business Suite Release 12, or contemplating significant changes to a configuration. After describing the Oracle Applications architecture and technology stack, it focuses on strategic topics, giving a broad outline of the actions needed to achieve a particular goal, plus the installation and configuration choices that may be available.

Oracle Applications Developer's Guide:

This guide contains the coding standards followed by the Oracle Applications development staff. It describes the Oracle Application Object Library components needed to implement the Oracle Applications user interface described in the *Oracle Applications User Interface Standards for Forms-Based Products*. It also provides information to help you build your custom Oracle Forms Developer forms so that they integrate with Oracle Applications.

Oracle Applications Supportability Guide:

This manual contains information on Oracle Diagnostics and the Logging Framework for system administrators and custom developers.

Oracle Applications System Administrator's Guide Documentation Set:

This documentation set provides planning and reference information for the Oracle Applications System Administrator. *Oracle Applications System Administrator's Guide* -

Configuration contains information on system configuration steps, including defining concurrent programs and managers, enabling Oracle Applications Manager features, and setting up printers and online help. *Oracle Applications System Administrator's Guide - Maintenance* provides information for frequent tasks such as monitoring your system with Oracle Applications Manager, managing concurrent managers and reports, using diagnostic utilities, managing profile options, and using alerts. *Oracle Applications System Administrator's Guide - Security* describes User Management, data security, function security, auditing, and security configurations.

Oracle Applications User's Guide:

This guide explains how to navigate, enter data, query, and run reports using the user interface (UI) of Oracle Applications. This guide also includes information on setting user profiles, as well as running and reviewing concurrent requests.

Oracle Applications Multiple Organizations Implementation Guide:

This guide describes the multiple organizations concepts in Oracle Applications. It describes in detail on setting up and working effectively with multiple organizations in Oracle Applications.

Oracle Advanced Global Intercompany System User's Guide:

This guide describes the self service application pages available for Intercompany users. It includes information on setting up intercompany, entering intercompany transactions, importing transactions from external sources and generating reports.

Oracle Customer Data Librarian Implementation Guide:

This guide describes how to implement Oracle Customer Data Librarian. As part of implementing Oracle Customer Data Librarian, you must also complete all the implementation steps for Oracle Customers Online.

Oracle Customer Data Librarian User Guide:

This guide describes how to use Oracle Customer Data Librarian to establish and maintain the quality of the Trading Community Architecture Registry, focusing on consolidation, cleanliness, and completeness. Oracle Customer Data Librarian has all of the features in Oracle Customers Online, and is also part of the Oracle Customer Data Management product family.

Oracle Customers Online Implementation Guide:

This guide describes how to implement Oracle Customers Online.

Oracle Customers Online User Guide:

This guide describes how to use Oracle Customers Online to view, create, and maintain your customer information. Oracle Customers Online is based on Oracle Trading Community Architecture data model and functionality, and is also part of the Oracle Customer Data Management product family.

Oracle E-Business Tax Implementation Guide:

This guide provides a conceptual overview of the E-Business Tax tax engine, and

describes the prerequisite implementation steps to complete in other applications in order to set up and use E-Business Tax. The guide also includes extensive examples of setting up country-specific tax requirements.

Oracle E-Business Tax Reporting Guide:

This guide explains how to run all tax reports that make use of the E-Business Tax data extract. This includes the Tax Reporting Ledger and other core tax reports, country-specific VAT reports, and Latin Tax Engine reports.

Oracle E-Business Tax User Guide:

This guide describes the entire process of setting up and maintaining tax configuration data, as well as applying tax data to the transaction line. It describes the entire regime-to-rate setup flow of tax regimes, taxes, statuses, rates, recovery rates, tax jurisdictions, and tax rules. It also describes setting up and maintaining tax reporting codes, fiscal classifications, tax profiles, tax registrations, configuration options, and third party service provider subscriptions. You also use this manual to maintain migrated tax data for use with E-Business Tax.

Oracle Financials and Oracle Procurement Functional Upgrade Guide: Release 11i to Release 12:

This guides provides detailed information about the functional impacts of upgrading Oracle Financials and Oracle Procurement products from Release 11*i* to Release 12. This guide supplements the Oracle Applications Upgrade Guide: Release 11*i* to Release 12.

Oracle Financials Concepts Guide:

This guide describes the fundamental concepts of Oracle Financials. The guide is intended to introduce readers to the concepts used in the applications, and help them compare their real world business, organization, and processes to those used in the applications.

Oracle Financials Country-Specific Installation Supplement:

This guide provides general country information, such as responsibilities and report security groups, as well as any post-install steps required by some countries.

Oracle Financials for the Americas User Guide:

This guide describes functionality developed to meet specific business practices in countries belonging to the Americas region. Consult this user guide along with your financial product user guides to effectively use Oracle Financials in your country.

Oracle Financials for Asia/Pacific User Guide:

This guide describes functionality developed to meet specific business practices in countries belonging to the Asia/Pacific region. Consult this user guide along with your financial product user guides to effectively use Oracle Financials in your country.

Oracle Financials for Europe User Guide:

This guide describes functionality developed to meet specific business practices in countries belonging to the European region. Consult this user guide along with your

financial product user guides to effectively use Oracle Financials in your country.

Oracle Financials for India User Guide:

This guide provides information on how to use Oracle Financials for India. Use this guide to learn how to create and maintain setup related to India taxes, defaulting and calculation of taxes on transactions. This guide also includes information about accounting and reporting of taxes related to India.

Oracle Financials for India Implementation Guide:

This guide provides information on how to implement Oracle Financials for India. Use this guide to understand the implementation steps required for application use, including how to set up taxes, tax defaulting hierarchies, set up different tax regimes, organization and transactions.

Oracle Financials Glossary:

The glossary includes definitions of common terms that are shared by all Oracle Financials products. In some cases, there may be different definitions of the same term for different Financials products. If you are unsure of the meaning of a term you see in an Oracle Financials guide, please refer to the glossary for clarification. You can find the glossary in the online help or in the *Oracle Financials Implementation Guide*.

Oracle Financials Implementation Guide:

This guide provides information on how to implement the Oracle Financials E-Business Suite. It guides you through setting up your organizations, including legal entities, and their accounting, using the Accounting Setup Manager. It covers intercompany accounting and sequencing of accounting entries, and it provides examples.

Oracle Financials RXi Reports Administration Tool User Guide:

This guide describes how to use the RXi reports administration tool to design the content and layout of RXi reports. RXi reports let you order, edit, and present report information to better meet your company's reporting needs.

Oracle General Ledger Implementation Guide:

This guide provides information on how to implement Oracle General Ledger. Use this guide to understand the implementation steps required for application use, including how to set up Accounting Flexfields, Accounts, and Calendars.

Oracle General Ledger Reference Guide

This guide provides detailed information about setting up General Ledger Profile Options and Applications Desktop Integrator (ADI) Profile Options.

Oracle General Ledger User's Guide:

This guide provides information on how to use Oracle General Ledger. Use this guide to learn how to create and maintain ledgers, ledger currencies, budgets, and journal entries. This guide also includes information about running financial reports.

Oracle Integration Repository User's Guide:

This guide covers the employment of Oracle Integration Repository in researching and deploying business interfaces to produce integrations between applications.

Oracle Internet Expenses Implementation and Administration Guide:

This book explains in detail how to configure Oracle Internet Expenses and describes its integration with other applications in the E-Business Suite, such as Oracle Payables and Oracle Projects. Use this guide to understand the implementation steps required for application use, including how to set up policy and rate schedules, credit card policies, audit automation, and the expenses spreadsheet. This guide also includes detailed information about the client extensions that you can use to extend Oracle Internet Expenses functionality.

Oracle Payables User Guide:

This guide describes how to use Oracle Payables to create invoices and make payments. In addition, it describes how to enter and manage suppliers, import invoices using the Payables open interface, manage purchase order and receipt matching, apply holds to invoices, and validate invoices. It contains information on managing expense reporting, procurement cards, and credit cards. This guide also explains the accounting for Payables transactions.

Oracle Payables Implementation Guide:

This guide provides you with information on how to implement Oracle Payables. Use this guide to understand the implementation steps required for how to set up suppliers, payments, accounting, and tax.

Oracle Payables Reference Guide:

This guide provides you with detailed information about the Oracle Payables open interfaces, such as the Invoice open interface, which lets you import invoices. It also includes reference information on purchase order matching and purging purchasing information.

Oracle Purchasing User's Guide:

This guide describes how to create and approve purchasing documents, including requisitions, different types of purchase orders, quotations, RFQs, and receipts. This guide also describes how to manage your supply base through agreements, sourcing rules, and approved supplier lists. In addition, this guide explains how you can automatically create purchasing documents based on business rules through integration with Oracle Workflow technology, which automates many of the key procurement processes.

Oracle Subledger Accounting Implementation Guide:

This guide provides setup information for Oracle Subledger Accounting features, including the Accounting Methods Builder. You can use the Accounting Methods Builder to create and modify the setup for subledger journal lines and application accounting definitions for Oracle subledger applications. This guide also discusses the reports available in Oracle Subledger Accounting and describes how to inquire on subledger journal entries.

Oracle Receivables Implementation Guide:

This guide provides you with information on how to implement Oracle Receivables. Use this guide to understand the implementation steps required for application use, including how to set up customers, transactions, receipts, accounting, tax, and collections. This guide also includes a comprehensive list of profile options that you can set to customize application behavior.

Oracle Receivables Reference Guide:

This guide provides you with detailed information about all public application programming interfaces (APIs) that you can use to extend Oracle Receivables functionality. This guide also describes the Oracle Receivables open interfaces, such as AutoLockbox which lets you create and apply receipts and AutoInvoice which you can use to import and validate transactions from other systems. Archiving and purging Receivables data is also discussed in this guide.

Oracle Receivables User Guide:

This guide provides you with information on how to use Oracle Receivables. Use this guide to learn how to create and maintain transactions and bills receivable, enter and apply receipts, enter customer information, and manage revenue. This guide also includes information about accounting in Receivables. Use the Standard Navigation Paths appendix to find out how to access each Receivables window.

Oracle Trading Community Architecture Administration Guide:

This guide describes how to administer and implement Oracle Trading Community Architecture (TCA). You set up, control, and manage functionality that affects data in the TCA Registry. It also describes how to set up and use Resource Manager to manage resources.

Oracle Trading Community Architecture Technical Implementation Guide:

This guide explains how to use the public Oracle Trading Community Architecture application programming interfaces (APIs) and develop callouts based on Oracle Workflow Business Events System (BES). For each API, this guide provides a description of the API, the PL/SQL procedure, and the Java method, as well as a table of the parameter descriptions and validations. For each BES callout, this guide provides the name of the logical entity, its description, and the ID parameter name. Also included are setup instructions and sample code.

Oracle Trading Community Architecture Reference Guide:

This guide contains seeded relationship types, seeded Data Quality Management data, D and B data elements, Bulk Import interface table fields and validations, and a comprehensive glossary. This guide supplements the documentation for Oracle Trading Community Architecture and all products in the Oracle Customer Data Management family.

Oracle Trading Community Architecture User Guide:

This guide describes the Oracle Trading Community Architecture (TCA) and how to

use features from the Trading Community Manager responsibility to create, update, enrich, and cleanse the data in the TCA Registry. It also describes how to use Resource Manager to define and manage resources.

Oracle Projects Documentation Set

Oracle Projects Implementation Guide:

Use this manual as a guide for implementing Oracle Projects. This manual also includes appendixes covering security functions, menus and responsibilities, and profile options.

Oracle Projects Fundamentals:

Oracle Project Fundamentals provides the common foundation shared across the Oracle Projects products (Project Costing, Project Billing, Project Resource Management, Project Management, and Project Portfolio Analysis). Use this guide to learn fundamental information about the Oracle Projects solution. This guide includes a Navigation Paths appendix. Use this appendix to find out how to access each window in the Oracle Projects solution.

Oracle Project Costing User Guide:

Use this guide to learn detailed information about Oracle Project Costing. Oracle Project Costing provides the tools for processing project expenditures, including calculating their cost to each project and determining the GL accounts to which the costs are posted.

Oracle Project Billing User Guide:

This guide shows you how to use Oracle Project Billing to define revenue and invoicing rules for your projects, generate revenue, create invoices, and integrate with other Oracle Applications to process revenue and invoices, process client invoicing, and measure the profitability of your contract projects.

Oracle Project Management User Guide:

This guide shows you how to use Oracle Project Management to manage projects through their lifecycles -- from planning, through execution, to completion.

Oracle Project Portfolio Analysis User Guide:

This guide contains the information you need to understand and use Oracle Project Portfolio Analysis. It includes information about project portfolios, planning cycles, and metrics for ranking and selecting projects for a project portfolio.

Oracle Project Resource Management User Guide:

This guide provides you with information on how to use Oracle Project Resource Management. It includes information about staffing, scheduling, and reporting on project resources.

Oracle Projects Glossary:

This glossary provides definitions of terms that are shared by all Oracle Projects applications. If you are unsure of the meaning of a term you see in an Oracle Projects guide, please refer to the glossary for clarification. You can find the glossary in the

online help for Oracle Projects, and in the Oracle Projects Fundamentals book.

Integration Repository

The Oracle Integration Repository is a compilation of information about the service endpoints exposed by the Oracle E-Business Suite of applications. It provides a complete catalog of Oracle E-Business Suite's business service interfaces. The tool lets users easily discover and deploy the appropriate business service interface for integration with any system, application, or business partner.

The Oracle Integration Repository is shipped as part of the E-Business Suite. As your instance is patched, the repository is automatically updated with content appropriate for the precise revisions of interfaces in your environment.

Do Not Use Database Tools to Modify Oracle Applications Data

Oracle **STRONGLY RECOMMENDS** that you never use SQL*Plus, Oracle Data Browser, database triggers, or any other tool to modify Oracle Applications data unless otherwise instructed.

Oracle provides powerful tools you can use to create, store, change, retrieve, and maintain information in an Oracle database. But if you use Oracle tools such as SQL*Plus to modify Oracle Applications data, you risk destroying the integrity of your data and you lose the ability to audit changes to your data.

Because Oracle Applications tables are interrelated, any change you make using an Oracle Applications form can update many tables at once. But when you modify Oracle Applications data using anything other than Oracle Applications, you may change a row in one table without making corresponding changes in related tables. If your tables get out of synchronization with each other, you risk retrieving erroneous information and you risk unpredictable results throughout Oracle Applications.

When you use Oracle Applications to modify your data, Oracle Applications automatically checks that your changes are valid. Oracle Applications also keeps track of who changes information. If you enter information into database tables using database tools, you may store invalid information. You also lose the ability to track who has changed your information because SQL*Plus and other database tools do not keep a record of changes.

License and Support for the Vertex Q-Series and Taxware Sales/Use Tax System

License

Vertex Q-Series

If you wish to implement the Vertex Q-Series with Oracle E-Business Suite, you must obtain a license from Vertex, Inc.

Visit the Vertex website at <http://www.vertexinc.com> for further information. All support for the Vertex Q-Series is provided by Vertex Inc.

Taxware Sales/Use Tax System

If you wish to implement Taxware Sales/Use Tax System with Oracle E-Business Suite, you must obtain a license from Taxware, LP - A First Data Company.

Visit the Taxware website at <http://www.taxware.com> for further information. All support for the Taxware Sales/Use Tax System is provided by Taxware.

Support

The integrations with Vertex Q-Series and Taxware Sales/Use Tax System are supported by Oracle for US state and local sales taxes only within the order-to-cash business flows. For a complete list of the order-to-cash application products supported by Oracle E-Business Tax, see: E-Business Tax and Transaction Taxes, *Oracle E-Business Tax User Guide*.

Installing and Implementing the Vertex Q-Series or Taxware Sales/Use Tax System

Installing the Tax Service Provider Product

The latest Oracle certified versions of tax service providers products are available prepackaged with Oracle E-Business Suite Release 12. The product database objects of each tax service provider reside on the Oracle installation CD as a single zip file. A one-step automated process facilitates the installation without any user intervention, which replaces the multi-step process previously required but still supported as an alternative.

Prerequisites

- Execute a license agreement with a tax service provider.
- Provide Oracle SQL*Plus access to the APPS schema.

Setup Checklist for PrePackaged Tax Service Provider Integration

Tax service provider database server-side software, residing on the Oracle CD, is manually installed after the Oracle E-Business suite Release 12 is successfully installed. To find the version of the latest prepackaged tax service provider software, review the documentation included with your software. The prepackaged installation process will automatically upgrade the existing database server-side tax service provider software, if any. The main components of prepackaged tax service provider software are:

- An installation driver script.
- A zipped tax service provider software file consisting of database server-side objects.

Where appropriate, Oracle may certify a more recent version of tax service provider

software than the version included with the Oracle CD. Users can download the prepackaged tax service provider software via Oracle *MetaLink*. Contact your Oracle support representative for more information.

Complete the following steps in the order shown to implement the prepackaged version of a tax service provider product:

1. Run the installation driver script.
2. Set profile options.
3. Set up lookup codes for tax exemption reason.
4. Set up provider-specific tax regime and taxes.
5. Set up service subscriptions.
6. Install client-side tax service provider software.
7. Load tax jurisdictions and rates.
8. Set up tax accounts.
9. Turn on address validation.
10. Set up jurisdiction codes and other optional fields (optional).
11. Verify the tax service provider implementation.

Step 1 Run the Installation Driver Script

The installation driver script (UNIX Shell script for UNIX-based systems) unzips the tax service provider software zip file, installs the database server-side software, and integrates tax service provider software with E-Business Tax. After a successful installation of Release 12, run the driver script at the command prompt as follows:

```
cd $ZX_TOP/bin
zxtxptnr.sh <parameter1> <parameter2> <parameter3> <parameter4>
<parameter5> <parameter6>
```

This table contains parameters passed to the driver script:

Parameter	Parameter Name	Required
parameter1	Provider Name	Yes
parameter2	System User (Database)	Yes

Parameter	Parameter Name	Required
parameter3	Provider Schema Name	Yes
parameter4	Tablespace Name for Provider Schema	Yes
parameter5	Temporary Tablespace Name for Provider Schema	Yes
parameter6	SQL*Loader Executable (sqlldr) for loading sample Taxware Data	Yes

The parameters in this table are required and must be passed in the order listed. An example driver script run command based on this table for Vertex is (note that Taxware has an additional parameter):

```
$ZX_TOP/bin/ztxptnr.sh vertex system vertex USER_DATA TEMP
```

Other relevant information for the driver script includes:

- Location of the driver script: \$ZX_TOP/bin.
- Location of the execution log file: \$APPLTMP.
- Name of the execution log file: ztxptnr.log.

Step 2 Set Profile Options

Set the relevant profile options for your tax service provider. See: Setting Profile Option Values, *Oracle E-Business Tax Implementation Guide*.

Step 3 Set Up Lookup Code Tax Exemption Reason

When storing tax exemptions in E-Business Tax, use the Lookups window to set up the Tax Exemption Reason lookup code. The lookup type for this lookup code is ZX_EXEMPTION_REASON. These reason codes are used by tax service providers to determine the exemption reason. The reason codes are restricted in the number of characters that are used by a provider. See: Setting Up Lookup Codes, *Oracle E-Business Tax Implementation Guide*.

Important: Vertex exemption reasons are restricted to one alphanumeric character. Define Vertex exemption reasons so that the first character of the Exemption Reason Name is unique.

Important: Taxware exemption reasons are restricted to two alphanumeric characters. Define Taxware exemption reasons so that the first two characters of the Exemption Reason Name are unique.

Step 4 Set Up Provider-Specific Tax Regime and Taxes

To implement a tax service provider, you need to create a tax regime and taxes. You typically create three taxes: state, county, and city. See: United States Sales and Use Tax, *Oracle E-Business Tax Implementation Guide*.

Step 5 Set Up Service Subscriptions

After creating a tax regime, create service subscription for your operating unit or legal entity to the tax regime you just created for your tax service provider. If your installation uses multiple organizations for United States, you may use a tax service provider only for some specific operating units or legal entities. See: Setting Up Service Subscriptions, *Oracle E-Business Tax User Guide*.

Step 6 Install Client-Side Tax Service Provider Software

Install all necessary client-side tax service provider software. Refer to the user guides of your tax service provider.

Step 7 Load Tax Jurisdictions and Rates

Obtain and load the tax jurisdictions and rates from your tax service provider. Load this data into both the tax service provider system and E-Business Tax.

See: *Oracle Integration Repository* for information about loading tax jurisdictions and rates.

Step 8 Set Up Tax Accounts

Define tax accounts in E-Business Tax. If you define separate tax liability accounts for each ship-to state, it is easier for you to reconcile total tax amounts for each state in General Ledger with tax service provider reports. See: Setting Up Tax Accounts, *Oracle E-Business Tax User Guide*.

Step 9 Turn on Address Validation

Ensure that address validation is turned on before creating customer addresses. See: Real-Time Address Validation, *Oracle Trading Community Architecture User Guide*.

Step 10 Set Up Jurisdiction Codes and Other Optional Fields

You can optionally implement descriptive flexfields and use the standard fields available in Oracle Receivables windows to extend the basic functionality of this

integration. Use the Warehouse Jurisdiction Code, Salesperson Jurisdiction Code, and Customer Addresses Jurisdiction Code to support tax calculations using Ship To, Ship From, Point of Order Origin, and Point of Order Acceptance addresses.

You can set up tax exemptions and product tax exceptions in E-Business Tax. See: *Setting Up Tax Exemptions, Oracle E-Business Tax User Guide* and *Setting Up Tax Exceptions, Oracle E-Business Tax User Guide* for more information.

You can set an option in the User Defined Receivables Activity Information descriptive flexfield to indicate whether you want to post adjustment information to the tax service provider audit table.

Step 11 Verify the Tax Service Provider Implementation

Perform these steps to verify that your tax service provider is successfully integrated:

1. Create customer addresses.

Verify that the customer addresses are validated against the loaded geography data.

2. Create a sales order.

Verify that the estimated tax is calculated using the tax service.

3. Import a sales order with AutoInvoice.

Verify that tax is calculated using the tax service provider on invoices imported from Oracle Order Management or other feeder systems.

4. Create an invoice using the Receivables Transaction Workbench.

Verify that tax is calculated using the tax service provider on manual invoices created in Oracle Receivables.

5. Update or delete an invoice line.

When you update or delete an invoice line, tax amounts should reconcile to your tax service provider tax reports.

6. Credit an invoice.

When you create credit memos, tax amounts should reconcile to your tax service provider tax reports.

7. Copy an invoice.

Verify that tax is calculated using the tax service provider on the copied invoice.

8. Create an exempt order.

Verify that Oracle Receivables exemptions are used in calculating tax with the tax service provider.

9. Adjust an invoice.

Verify that tax adjustments reconcile with your service provider tax reports. Only approved adjustments of type *Tax* are reflected in your provider tax reports, which lets you control which write-offs have recoverable sales tax from the state, county, and city.

Setup Checklist for Non-PrePackaged Tax Service Provider Integration

Complete these steps in the order shown to implement a tax service provider product:

1. Install database server-side software.
2. Provide grants to the APPS schema.
3. Recreate synonyms.
4. Set profile options.
5. Set up lookup code tax exemption reason.
6. Set up provider-specific tax regime and taxes.
7. Set up service subscriptions.
8. Create index on Vertex audit file.
9. Install client-side tax service provider software.
10. Load tax jurisdictions and rates.
11. Set up tax accounts.
12. Turn on address validation.
13. Setup jurisdiction codes and other optional fields (optional).
14. Verify the tax service provider implementation.

Step 1 Install Database Server-Side Software

Install the latest Oracle-certified version of your tax service provider product. Provider-specific database objects should all be created in a separate schema.

Step 2 Provide Grants to the APPS Schema

Once a service provider software is installed, give the following grants to the APPS schema in order to execute the service provider APIs:

Vertex

```
CONNECT <Vertex schema>/<Vertex password>
GRANT ALL ON QSU TO <APPS Schema>
WITH GRANT OPTION;
GRANT ALL ON GEO TO <APPS Schema>
WITH GRANT OPTION;
GRANT ALL ON REGPRERETURNSTBL TO <APPS Schema>
WITH GRANT OPTION;
```

Taxware

```
CONNECT <Taxware schema>/<Taxware password>
GRANT ALL ON TAXPKG_GEN TO <APPS Schema>
WITH GRANT OPTION;
GRANT ALL ON TAXPKG_10 TO <APPS Schema>
WITH GRANT OPTION;
GRANT DELETE ON TAXAUDIT_HEADER to <APPS Schema>;
GRANT DELETE ON TAXAUDIT_DETAIL to <APPS Schema>;
GRANT DELETE ON TAXAUDIT_TAX to <APPS Schema>;
GRANT DELETE ON TAXAUDIT_JURIS to <APPS Schema>;
```

Step 3 Recreate Synonyms

Once the packages are installed, you must recreate the following synonyms to point to the correct service provider packages:

Vertex

```
CONNECT <APPS Schema>/<APPS Password>
DROP SYNONYM ZX_TAX_VERTEX_QSU;
DROP SYNONYM ZX_TAX_VERTEX_GEO;
DROP SYNONYM ZX_TAX_VERTEX_AUDIT;
CREATE SYNONYM ZX_TAX_VERTEX_QSU FOR <Vertex Schema>.QSU;
CREATE SYNONYM ZX_TAX_VERTEX_GEO FOR <Vertex Schema>.GEO;
CREATE SYNONYM ZX_TAX_VERTEX_AUDIT FOR <Vertex Schema>.REGPRERETURNSTBL;
```

Taxware

```
CONNECT <apps schema>/<apps password>
DROP SYNONYM ZX_TAX_TAXWARE_010;
DROP SYNONYM ZX_TAX_TAXWARE_GEN;
DROP SYNONYM ZX_TAX_TAXWARE_AUDIT_HEADER;
DROP SYNONYM ZX_TAX_TAXWARE_AUDIT_DETAIL;
DROP SYNONYM ZX_TAX_TAXWARE_AUDIT_JURIS;
DROP SYNONYM ZX_TAX_TAXWARE_AUDIT_TAX;
CREATE SYNONYM ZX_TAX_TAXWARE_010 FOR <Taxware Schema>.TAXPKG_10;
CREATE SYNONYM ZX_TAX_TAXWARE_GEN FOR <Taxware Schema>.TAXPKG_GEN;
CREATE SYNONYM ZX_TAX_TAXWARE_AUDIT_HEADER FOR <Taxware
Schema>.TAXAUDIT_HEADER;
CREATE SYNONYM ZX_TAX_TAXWARE_AUDIT_DETAIL FOR <Taxware
Schema>.TAXAUDIT_DETAIL;
CREATE SYNONYM ZX_TAX_TAXWARE_AUDIT_JURIS FOR <Taxware
Schema>.TAXAUDIT_JURIS;
CREATE SYNONYM ZX_TAX_TAXWARE_AUDIT_TAX FOR <Taxware
Schema>.TAXAUDIT_TAX;
```

Step 4 to Step 7

See: Step 2 to Step 5 in the Setup Checklist for PrePackaged Tax Service Provider

Integration, page 2-1 for details of these setup steps.

Step 8 Create Index on Vertex Audit Table (Vertex only)

During the rollback phase of AutoInvoice, the program deletes invalid transactions from the Oracle Receivables interface tables. You need to create an index for the TRANSUSERAREA column in the REGPRERETURNSTBL Vertex table so that Vertex can identify the invoices to delete much more quickly.

To create this index:

1. Login to SQLPLUS in the Vertex Schema.
2. Enter the following SQL command:

```
CREATE INDEX <INDEX_NAME> ON  
REGPRERETURNSTBL (TRANSUSERAREA) ;
```

where <INDEX_NAME> is unique within the Vertex schema.

Step 9 to Step 14

See: Step 6 to Step 11 in the Setup Checklist for PrePackaged Tax Service Provider Integration, page 2-1 for details of these setup steps.

Business Processes

Transaction Options in Oracle Receivables

If you have integrated with a tax service provider, these actions are not required for Receivables transactions:

- Entering tax classification codes on transaction lines.
- Entering transaction line attributes in the Additional Tax Determining Factors window.

Working with Service Provider Tax Jurisdiction Codes

Service providers may use their own tax jurisdiction code to identify a taxing jurisdiction. A service provider jurisdiction code is typically needed when the zip code of an address does not uniquely identify the exact taxing jurisdiction. For example, the same city and zip code may have two or more different taxing jurisdictions in different geographical areas within the same zip code. For such zip codes, you should enter the service provider tax jurisdiction codes when you enter your customer addresses.

See: Address Formatting, *Oracle Trading Community Architecture User Guide* for information about entering customer addresses.

Vertex

Vertex uses the term *geocode* for tax jurisdiction codes. The geocode is an internal code that is understood by the Vertex integration. The geocode is a nine-digit numeric code that is composed of a two-digit state code, followed by a three-digit county code, followed by a four-digit code to identify a tax jurisdiction within a city. For example: 12-345-6789.

The Vertex integration uses the Vertex GeoCoder API to retrieve the geocode for a ship-to customer address, if a geocode is not available on the customer address and cannot be retrieved from the E-Business Tax jurisdiction setup. If the GeoCoder API

cannot find a geocode, an error is raised.

Taxware

The Taxware jurisdiction code is a nine-digit alphanumeric code. It is composed of the two-character state code, the five-digit zip code, and a unique two-digit numeric code. For example, the code CA9411401 is composed of the state code CA for California, the zip code 94114, and the Taxware jurisdiction code 01.

The Taxware integration retrieves the jurisdiction code either from the customer address or the E-Business Tax jurisdiction setup. If a jurisdiction code is not found, then 00 is passed as the jurisdiction code to the tax calculation API.

Monthly Procedures

Each month tax service providers send an updated version of their data file. You need to upload the data file into both the tax service provider system and the E-Business Tax system. This will ensure that E-Business Tax has the latest information for address validation and tax jurisdiction code/geocode retrieval during tax calculation.

Exemption Handling

You can define your customer and product exemptions using a tax service provider, E-Business Tax, or both. At transaction time, if an applicable E-Business Tax exemption or non-jurisdiction based tax exception is found, it is passed to the tax service provider API and applied to the tax calculation. The tax service provider tax repository includes the exempt tax line for complete audit and reconciliation.

If you decide to build your own logic to pass exemptions to the tax service provider, for example, by making use of E-Business Tax fiscal classifications, you can write your own code using PL/SQL. See: Customizable Tax Functions, page 4-1 for information customizing the exemption and exception values passed by E-Business Tax.

If the Tax Handling field is enabled on an Oracle Order Management or Oracle Receivables transaction line, you can override the tax service provider setup and identify a transaction as exempt, according to your tax exemption setup in E-Business Tax. See: Setting Up Tax Exemptions, *Oracle E-Business Tax User Guide* for more information.

Set the eBTax: Allow Override of Customer Exemptions profile option to control the display of the Tax Handling field. See: Setting Profile Option Values, *Oracle E-Business Tax Implementation Guide*.

Reconciliation and Audit Procedures

Tax service providers return the calculated tax lines to E-Business Tax. The tax lines for Oracle Receivables transactions returned by tax service providers are stored in

E-Business Tax similar to the way tax lines calculated by E-Business Tax itself are stored.

Due to the limitations of Vertex and Taxware APIs in accepting the transaction line update details, whenever a user updates a transaction line in Oracle Receivables, two lines are passed to Vertex or Taxware for tax calculation. For example, if the line amount is changed from \$100 to \$200, because of either quantity or price change, the tax service provider API is called for a transaction line with line amount as -\$100 and another line with line amount as \$200. The taxes for transaction line of line amount -\$100 back out the original tax amounts calculated for the original line amount of \$100.

Only approved adjustments of type *Tax* are synchronized with the tax service providers. This gives you greater control over which adjustments should reduce the sales tax liability. If you have adjustments of type *Tax* that you do not want to post to the tax service provider repository, see: Storing Tax Information in Descriptive Flexfields and Other Applications, page 4-22 for more information.

Before completing your tax returns using the tax service provider reports, you should reconcile the total tax amounts held in E-Business Tax, Oracle General Ledger, and a tax service provider repository. All Oracle Receivables transactions get stored in the tax service provider repository at the time of tax calculation. Thus, the tax details in E-Business Tax and in a tax service provider repository are always the same. The Oracle Receivables transactions are posted to General Ledger only when they are completed and posted to General Ledger from the Subledger Accounting application. Therefore, before reconciliation with General Ledger, all transactions must be completed and posted to the General Ledger.

You can reconcile the total tax amounts of Oracle Receivables transactions by state to Oracle General Ledger. The total tax amounts by state reported by the Tax Reconciliation Report should reconcile to each state tax liability account held in Oracle General Ledger.

Reconcile total tax amounts by state to the tax service provider repository by running the Vertex Sales Tax Register or Taxware Sales/Use Tax report.

The tax service providers and Oracle Receivables use different terms when referring to the tax calculation date and the accounting date for transactions. This table summarizes these terminology differences:

Value	Oracle Receivables	Vertex Q-Series	Taxware SUTS
Accounting Date	GL Date	Transaction Date	Fiscal Date
Tax Calculation Date	Transaction Date	Invoice Date	Invoice Date

Related Topics

Tax Reconciliation Report, *Oracle E-Business Tax Reporting Guide*

Support Procedures

Begin with E-Business Tax debug messages to review issues that arise with tax calculation by tax service providers. The debug log contains all the input and output parameters sent and received to and from a tax service provider. The tax service provider returned messages are printed in the debug log after this E-Business Tax introductory message:

An error has occurred in the tax service provider API. Please review the following messages and contact tax service provider support for further action.

Related Topics

System Alerts, Metrics, and Logs, *Oracle Applications System Administrator's Guide - Maintenance*

Technical Reference

Available Parameters

The tax service providers tax calculation APIs get the input from the view `ZX_O2C_CALC_TXN_INPUT_V`. For the list of available attributes refer to the view description in the *Oracle E-Business Suite Electronic Technical Reference Manual*.

Customizable Tax Functions

Tax service providers require some attributes that do not exist as standard columns in the E-Business Suite tables or can be mapped to an attribute out of two or more potential attribute in E-Business Suite. To achieve this, view `ZX_O2C_CALC_TXN_INPUT_V` has some extra columns. There are tax functions that populate the values of these extra columns in the tables `ZX_PRVDR_HDR_EXTNS_GT` and `ZX_PRVDR_LINE_EXTNS_GT` used for the view.

The packages `ARP_TAX_VIEW_TAXWARE` and `ARP_TAX_VIEW_VERTEX` contain the tax functions for Taxware and Vertex respectively. These tax functions contain default logic that can be re-written for an installation. The tax functions are called from the procedures in the packages `ZX_TAXWARE_USER_PKG` and `ZX_VERTEX_USER_PKG`, which insert records in `ZX_PRVDR_HDR_EXTNS_GT` and `ZX_PRVDR_LINE_EXTNS_GT` tables.

The table below contains the tax functions contained in `ARP_TAX_VIEW_TAXWARE` `ARP_TAX_VIEW_VERTEX` packages and the values assigned to Vertex and Taxware API parameters by the calling procedures in the packages `ZX_TAXWARE_USER_PKG` and `ZX_VERTEX_USER_PKG`.

Function/Procedure Name	Column Name in ZX_O2C_CALC_TXN_INPUT_V	Default Value	Mapped Attribute of Taxware API	Mapped Attribute of Vertex API
TRANSACTION_DATE	LINE_EXT_DATE_ATTRIBUTE1	TRX_LINE_GL_DATE of ZX_LINES_DET_FACTORS	TaxLink.FiscalDate	fTransDate
PRODUCT_CODE	LINE_EXT_VARIABLE_CHAR_ATTRIBUTE2	SEGMENT1 of MTL_SYSTEM_ITEMS	TaxLink.ProdCode	fTDMProdCd
AUDIT_FLAG	LINE_EXT_VARIABLE_CHAR_ATTRIBUTE8	ATTRIBUTE15 of AR_RECEIVABLES_TRX	TaxLink.ReptInd	Not mapped directly, but determines if the transaction should be recorded in the Vertex repository.
SHIP_TO_ADDRESS_CODE	LINE_EXT_VARIABLE_CHAR_ATTRIBUTE9	- Ship-to address jurisdiction code - TAX_JURISDICTION_CODE from ZX_JURISDICTIONS_B	TaxLink.StateCode = substr(SHIP_TO_ADDRESS_CODE,2,2) TaxLink.PriZip = substr(SHIP_TO_ADDRESS_CODE,4,5) TaxLink.PriGeo = substr(SHIP_TO_ADDRESS_CODE,9,2)	.fJurisSTGeoCd = substr(SHIP_TO_ADDRESS_CODE,2,9) .fJurisSTInCi = substr(SHIP_TO_ADDRESS_CODE,1,1)

Function/Procedure Name	Column Name in ZX_O2C_CALC_TXN_INPUT_V	Default Value	Mapped Attribute of Taxware API	Mapped Attribute of Vertex API
SHIP_FROM_ADDRESS_CODE	LINE_EXT_VAR CHAR_ATTRIB UTE10	Warehouse address jurisdiction code	JurLink.ShipFr.State = substr(SHIP_FROM_ADDRESS_CODE,2,2) JurLink.ShipFr.Zip = substr(SHIP_FROM_ADDRESS_CODE,4,5) JurLink.ShipFr.Geo = substr(SHIP_FROM_ADDRESS_CODE,9,2)	.fJurisSFGeoCd = substr(SHIP_FROM_ADDRESS_CODE,2,9) .fJurisSFInCi = substr(SHIP_FROM_ADDRESS_CODE,1,1)
POA_ADDRESS_CODE	LINE_EXT_VAR CHAR_ATTRIB UTE11	Taxware: Organization jurisdiction code Vertex: Salesperson jurisdiction code	JurLink.POA.State = substr(POA_ADDRESS_CODE,2,2) JurLink.POA.Zip = substr(POA_ADDRESS_CODE,4,5) JurLink.POA.Geo = substr(POA_ADDRESS_CODE,9,2)	.fJurisOAGeoCd = substr(POA_ADDRESS_CODE,2,9) .fJurisOAInCi = substr(POA_ADDRESS_CODE,1,1)
CUSTOMER_CODE	LINE_EXT_VAR CHAR_ATTRIB UTE12	Bill To Party Number (PARTY_NUMBER of HZ_PARTIES)	TaxLink.CustNo	.fTDMCustCd

Function/Procedure Name	Column Name in ZX_O2C_CALC_TXN_INPUT_V	Default Value	Mapped Attribute of Taxware API	Mapped Attribute of Vertex API
COMPANY_CODE	LINE_EXT_VAR CHAR_ATTRIBUT UTE14	01	TaxLink.CompanyID	.fTDMCompCd
DIVISION_CODE	LINE_EXT_VAR CHAR_ATTRIBUT UTE15	01	TaxLink.DivCode	.fTDMDivCd
SERVICE_INDICATOR	LINE_EXT_VAR CHAR_ATTRIBUT UTE1	Profile: ZX_TAXVDR_SERVICEIND	JurLink.ServInd	N/A
TAX_SEL_PARAM	LINE_EXT_NUMBER_ATTRIBUT UTE6	Profile: ZX_TAXVDR_TAXSELPARAM	TaxSelParm	N/A
CUSTOMER_NAME	LINE_EXT_VAR CHAR_ATTRIBUT UTE13	Bill To Party Name (PARTY_NAME of HZ_PARTIES)	TaxLink.CustName	N/A
VENDOR_CONTROL_EXEMPTIONS	LINE_EXT_VAR CHAR_ATTRIBUT UTE16	Job Number (ATTRIBUTE1 from RA_CUST_TRX_TYPES)	TaxLink.JobNo	N/A
USE_NEXPRO	LINE_EXT_VAR CHAR_ATTRIBUT UTE17	Profile: ZX_TAXVDR_USENEXPRO	TaxLink.UseNexproInd	N/A

Function/Procedure Name	Column Name in ZX_O2C_CALC_TXN_INPUT_V	Default Value	Mapped Attribute of Taxware API	Mapped Attribute of Vertex API
POO_ADDRESS_CODE	LINE_EXT_VAR CHAR_ATTRIB UTE20	Salesperson jurisdiction code	JurLink.POO.State = substr(POO_ADDRESS_CODE,2,2) JurLink.POO.Zip = substr(POO_ADDRESS_CODE,4,5) JurLink.POO.Geo = substr(POO_ADDRESS_CODE,9,2)	N/A
CALCULATION_FLAG	LINE_EXT_VAR CHAR_ATTRIB UTE21	00000 (Calculate tax at all jurisdiction levels)	TaxLink.NoStateTax TaxLink.StateExempt TaxLink.NoCnTax TaxLink.CnExempt TaxLink.NoLoTax TaxLink.LoExempt TaxLink.NoSecCnTax TaxLink.SecCnExempt TaxLink.NoSecLoTax TaxLink.SecLoExempt	N/A

Function/Procedure Name	Column Name in ZX_O2C_CALC_TXN_INPUT_V	Default Value	Mapped Attribute of Taxware API	Mapped Attribute of Vertex API
TRX_LINE_TYPE	LINE_EXT_VAR CHAR_ATTRIBUT UTE1	SALE	N/A	.fTransType
CUSTOMER_CLASS	LINE_EXT_VAR CHAR_ATTRIBUT UTE13	Null	N/A	.fTDMCustClass Cd
GET_EXEMPTIONS (parameter state_exempt_percent)	LINE_EXT_NUMBER_ATTRIBUT UTE1	RATE_MODIFIER of ZX_EXEMPTIONS for STATE Tax	TaxLink.StExemptAmt = TaxLink.GrossAmt * (GET_EXEMPTIONS.state_exempt_percent)	.fPriStExmtAmt = fTransExtendedAmt * (GET_EXEMPTIONS.state_exempt_percent)
GET_EXEMPTIONS (parameter county_exempt_percent)	LINE_EXT_NUMBER_ATTRIBUT UTE2	RATE_MODIFIER of ZX_EXEMPTIONS for COUNTY Tax	TaxLink.CntyExemptAmt = TaxLink.GrossAmt * (GET_EXEMPTIONS.county_exempt_percent)	.fPriCoExmtAmt = fTransExtendedAmt * (GET_EXEMPTIONS.county_exempt_percent)
GET_EXEMPTIONS (parameter city_exempt_percent)	LINE_EXT_NUMBER_ATTRIBUT UTE3	RATE_MODIFIER of ZX_EXEMPTIONS for CITY Tax	TaxLink.CityExemptAmt = TaxLink.GrossAmt * (GET_EXEMPTIONS.city_exempt_percent)	.fPriCiExmtAmt = fTransExtendedAmt * (GET_EXEMPTIONS.city_exempt_percent)
GET_EXEMPTIONS (parameter state_exempt_reason)	LINE_EXT_VAR CHAR_ATTRIBUT UTE4	NULL	TaxLink.StReasonCode	.fPriStExmtRsnCd
GET_EXEMPTIONS (parameter county_exempt_reason)	LINE_EXT_VAR CHAR_ATTRIBUT UTE5	NULL	TaxLink.CntyReasonCode	.fPriCoExmtRsnCd

Function/Procedure Name	Column Name in ZX_O2C_CALC_TXN_INPUT_V	Default Value	Mapped Attribute of Taxware API	Mapped Attribute of Vertex API
GET_EXEMPTIONS (parameter city_exempt_reason)	LINE_EXT_VAR CHAR_ATTRIB UTE6	NULL	TaxLink.CityReasonCode	.fPriCiExmtRsnCd
GET_EXEMPTIONS (parameter use_step)	LINE_EXT_VAR CHAR_ATTRIB UTE3	Taxware: 'Y'	TaxLink.UseStep	N/A
GET_EXEMPTIONS (parameter step_proc_flag)	LINE_EXT_VAR CHAR_ATTRIB UTE7	Taxware: 1	TaxLink.StepProcFlg	N/A
GET_EXEMPTIONS (parameter crit_flag)	LINE_EXT_VAR CHAR_ATTRIB UTE19	'R'	TaxLink.CritFlg	N/A
GET_EXEMPTIONS (parameter sec_county_exempt_percent)	LINE_EXT_NUMBER_ATTRIB UTE4	RATE_MODIFIER of ZX_EXEMPTIONS for SECONDARY COUNTY Tax	TaxLink.SecCntExemptAmt = TaxLink.GrossAmt * (GET_EXEMPTIONS.sec_county_exempt_percent)	N/A
GET_EXEMPTIONS (parameter sec_city_exempt_percent)	LINE_EXT_NUMBER_ATTRIB UTE5	RATE_MODIFIER of ZX_EXEMPTIONS for SECONDARY CITY Tax	TaxLink.SecLoExemptAmt = TaxLink.GrossAmt * (GET_EXEMPTIONS.sec_city_exempt_percent)	N/A
GET_EXEMPTIONS (parameter state_certificate_number)	LINE_EXT_VAR CHAR_ATTRIB UTE22	EXEMPT_CERTIFICATE_NUMBER of ZX_EXEMPTIONS for STATE Tax	TaxLink.StTaxCertificateNo	N/A

Function/Procedure Name	Column Name in ZX_O2C_CALC_TXN_INPUT_V	Default Value	Mapped Attribute of Taxware API	Mapped Attribute of Vertex API
GET_EXEMPTIONS (parameter county_certificate_number)	LINE_EXT_VAR CHAR_ATTRIB UTE23	EXEMPT_CERTIFICATE_NUMBER of ZX_EXEMPTIONS for COUNTY Tax	TaxLink.CnTaxCertificateNo	N/A
GET_EXEMPTIONS (parameter city_certificate_number)	LINE_EXT_VAR CHAR_ATTRIB UTE24	EXEMPT_CERTIFICATE_NUMBER of ZX_EXEMPTIONS for CITY Tax	TaxLink.LoTaxCertificateNo	N/A
GET_EXEMPTIONS (parameter cert_no)	LINE_EXT_VAR CHAR_ATTRIB UTE3	EXEMPT_CERTIFICATE_NUMBER of ZX_EXEMPTIONS for CITY, COUNTY or STATE Tax in the order it is found	N/A	.fPriCustExmtCertificateNum
GET_EXEMPTIONS (parameter district_exempt_reason)	LINE_EXT_VAR CHAR_ATTRIB UTE7	NULL	N/A	.fPriDiExmtReasonCd
GET_EXEMPTIONS (parameter district_exempt_percent)	LINE_EXT_NUMBER_ATTRIB UTE4	RATE_MODIFIER of ZX_EXEMPTIONS for DISTRICT Tax	N/A	.fPriDiExmtAmt = fTransExtendedAmt * (GET_EXEMPTIONS.district_exempt_percent)

The tax functions are included in the E-Business Tax files \$ZX_TOP/patch/115/sql/ztxvwab.pls and ztxvwvb.pls.

The value of the eBTax Vertex: Case Sensitive profile option is assigned to the header_ext_varchar_attribute1. This profile option is used by Vertex to indicate whether information retrieval is performed using case-sensitive searches.

All tax functions have a parameter named `p_view_name`. This parameter identifies the transaction source context for rewriting the body of a tax function. Based on the transaction source, the table below identifies the table from where you can fetch transaction line attributes and join with other E-Business Suite tables.

Transaction Source	p_view_name value for Vertex	p_view_name value for Taxware	Table Name
AutoInvoice - Invoice/Debit Memo/On Account Credit Memo	TAX_LINES_INVOIC E_IMPORT_V_V INVOICE	TAX_LINES_INVOIC E_IMPORT_V_A INVOICE	RA_CUSTOMER_TR X_LINES_ALL
AutoInvoice - Applied Credit Memo	TAX_LINES_RMA_I MPORT_V_V CREDITMEMO	TAX_LINES_RMA_I MPORT_V_A CREDITMEMO	RA_CUSTOMER_TR X_LINES_ALL
Recurring Invoice	TAX_LINES_RECUR R_INVOICE_V_V	TAX_LINES_RECUR R_INVOICE_V_A	RA_CUSTOMER_TR X_LINES_ALL
Manual Entry & Update - Invoice/Debit Memo/On Account Credit Memo	TAX_LINES_CREAT E_V_V INVOICE	TAX_LINES_CREAT E_V_A INVOICE	RA_CUSTOMER_TR X_LINES_ALL
Manual Entry & Update - Applied Credit Memo	TAX_LINES_CM_V_ V CREDITMEMO	TAX_LINES_CM_V_ A CREDITMEMO	RA_CUSTOMER_TR X_LINES_ALL
Override Tax Lines	TAX_LINES_DELETE _V_V	TAX_LINES_DELETE _V_A	RA_CUSTOMER_TR X_LINES_ALL
Delete Invoice/Debit Memo/On Account Credit Memo/ Applied Credit Memo	TAX_LINES_CREAT E_V_V	TAX_LINES_CREAT E_V_A	RA_CUSTOMER_TR X_LINES_ALL
Tax Adjustment	TAX_ADJUSTMENT S_V_V	TAX_ADJUSTMENT S_V_A	RA_ADJUSTMENTS_ ALL
Order Management	OE_TAX_LINES_SU MMARY_V_V	OE_TAX_LINES_SU MMARY_V_A	OE_ORDER_LINES_ ALL

Transaction Source	p_view_name value for Vertex	p_view_name value for Taxware	Table Name
Order Capture	ASO_TAX_LINES_S UMMARY_V_V	ASO_TAX_LINES_S UMMARY_V_A	ASO_QUOTE_LINES _ALL

FUNCTION TRANSACTION_DATE(

```
p_view_name IN VARCHAR2,  
p_header_id IN NUMBER,  
p_line_id IN NUMBER) RETURN DATE;
```

Input	Description
p_view_name	Name of view calling this function
p_header_id	ID of transaction header
p_line_id	ID of transaction line

The function returns NULL by default and the calling procedure stores the GL Date value on the transaction line in the LINE_EXT_DATE_ATTRIBUTE1 column of the ZX_PRVDR_LINE_EXTNS_GT table. This value is used for reporting purposes.

FUNCTION PRODUCT_CODE(

```
p_view_name      IN VARCHAR2,  
p_header_id      IN NUMBER,  
p_line_id        IN NUMBER,  
p_item_id        IN NUMBER,  
p_memo_line_id   IN NUMBER) RETURN VARCHAR2;
```

Input	Description
p_view_name	Name of view calling this function
p_header_id	ID of transaction header
p_line_id	ID of transaction line
p_item_id	ID of inventory item

Input	Description
p_memo_line_id	ID of memo line

The function returns NULL by default and the calling procedure stores the SEGMENT1 value from the MTL_SYSTEM_ITEMS table (System Items key flexfield) in the LINE_EXT_VARCHAR_ATTRIBUTE2 column of the ZX_PRVDR_LINE_EXTNS_GT table. If a memo line is passed instead of an inventory item, then a NULL value is stored. The part number is used to determine exemptions.

FUNCTION AUDIT_FLAG(

```
p_view_name IN VARCHAR2,
p_header_id IN NUMBER,
p_line_id IN NUMBER) RETURN VARCHAR2;
```

Input	Description
p_view_name	Name of view calling this function
p_header_id	ID of transaction header
p_line_id	ID of transaction line

The function returns NULL by default and the calling procedure stores the value Y in the LINE_EXT_VARCHAR_ATTRIBUTE8 column of the ZX_PRVDR_LINE_EXTNS_GT table.

The value is used as an indicator for the auditing of tax adjustments. If Y, the tax adjustment is posted to the tax service provider repository.

FUNCTION SHIP_TO_ADDRESS_CODE(

```
p_view_name          IN VARCHAR2,
p_header_id          IN NUMBER,
p_line_id            IN NUMBER
p_ship_to_address_id IN NUMBER,
p_ship_to_location_id IN NUMBER,
p_trx_date           IN NUMBER,
p_ship_to_state       IN VARCHAR2,
p_postal_code         IN VARCHAR2) RETURN VARCHAR2;
```

Input	Description
p_view_name	Name of view calling this function
p_header_id	ID of transaction header
p_line_id	ID of transaction line
p_ship_to_address_id	ID of Ship-to address
p_ship_to_location_id	ID of Ship-to location
p_trx_date	Transaction Date
p_ship_to_state	State of the ship-to
p_postal_code	Zip code for the ship-to

The function returns NULL by default and the calling procedure stores the value in the ZX_PRVDR_LINE_EXTNS_GT table as per the description below.

The first character represents the In/Out City Limits flag. If this value is 1, then the Ship-to address is within the city limits; if this value is 0, then it is outside the city limits. The rest of the string is the jurisdiction code for the Ship-to address.

The In/Out City Limits is derived from the SALES_TAX_INSIDE_CITY_LIMITS column of the HZ_LOCATIONS table. If the In/Out City Limits flag is not found in the SALES_TAX_INSIDE_CITY_LIMITS column of the HZ_LOCATIONS table, the default value is within the city limits (1). For Taxware, the value of the first character is always 1.

The jurisdiction code is obtained from the SALES_TAX_GEOCODE column of the HZ_LOCATIONS table. If SALES_TAX_GEOCODE is NULL, the ZX_JURISDICTION_CODE column of the ZX_JURISDICTIONS_B table is returned for the ship-to city and zip code.

FUNCTION SHIP_FROM_ADDRESS_CODE(

```

p_view_name    IN VARCHAR2,
p_header_id    IN NUMBER,
p_line_id      IN NUMBER,
p_warehouse_id IN NUMBER) RETURN VARCHAR2;
```

Input	Description
p_view_name	Name of view calling this function
p_header_id	ID of transaction header
p_line_id	ID of transaction line
p_warehouse_id	ID of warehouse of the ship-from

The function returns NULL by default and the calling procedure stores the value in the ZX_PRVDR_LINE_EXTNS_GT table as per the description below.

The first character represents the In/Out City Limits flag. If this value is 1, then the Ship-from address is within the city limits; if this value is 0, then it is outside the city limits. The rest of the string is the jurisdiction code for the Ship-from address. For Taxware, the value of the first character is always 1.

The In/Out City Limits is derived from LOC_INFORMATION14 of the Location Address descriptive flexfield. The jurisdiction code is derived from LOC_INFORMATION13 of the Location Address descriptive flexfield.

FUNCTION POA_ADDRESS_CODE(

```
p_view_name IN VARCHAR2,
p_header_id IN NUMBER,
p_line_id IN NUMBER,
p_salesrep_id IN NUMBER) RETURN VARCHAR2;
```

Input	Description
p_view_name	Name of view calling this function
p_header_id	ID of transaction header
p_line_id	ID of transaction line
p_salesrep_id	ID of the primary sales representative

The function uses all four parameters for Vertex. The function does not use the p_salesrep_id parameter for Taxware.

The function returns NULL by default and the calling procedure stores the value in the ZX_PRVDR_LINE_EXTNS_GT table as per the description below.

The first character represents the In/Out City Limits flag. If this value is 1, then the Point

of Order Acceptance is within the city limits; if this value is 0, then it is outside the city limits. For Taxware, the value of the first character is 1.

The rest of the string is the jurisdiction code for the Point of Order Acceptance.

For Vertex, the In/Out City Limits is derived from the SALES_TAX_INSIDE_CITY_LIMITS column of the RA_SALESREPS view. The jurisdiction is derived from the SALES_TAX_GEOCODE column of the RA_SALESREPS view.

For Taxware, the jurisdiction code is derived from SALES_TAX_GEOCODE of the ZX_PRODUCT_OPTIONS_ALL table.

FUNCTION CUSTOMER_CODE(

```
p_view_name IN VARCHAR2,  
p_header_id IN NUMBER,  
p_line_id IN NUMBER) RETURN VARCHAR2;
```

Input	Description
p_view_name	Name of view calling this function
p_header_id	ID of transaction header
p_line_id	ID of transaction line

The function returns NULL by default and the calling procedure stores the bill to party PARTY_NUMBER from the HZ_PARTIES table in the LINE_EXT_VARCHAR_ATTRIBUTE12 column of the ZX_PRVDR_LINE_EXTNS_GT table. This value is used to determine the taxability of the individual customer.

FUNCTION COMPANY_CODE(

```
p_view_name      IN VARCHAR2,  
p_header_id      IN NUMBER,  
p_line_id        IN NUMBER) RETURN VARCHAR2;
```

Input	Description
p_view_name	Name of view calling this function
p_header_id	ID of transaction header
p_line_id	ID of transaction line

The function returns NULL by default and the calling procedure stores 01 for both

Taxware and Vertex in the LINE_EXT_VARCHAR_ATTRIBUTE14 column of the ZX_PRVDR_LINE_EXTNS_GT table. This value is used to control the tax reporting level and identifies exemptions defined in the tax service provider system.

FUNCTION DIVISION_CODE(

```
p_view_name      IN VARCHAR2,  
p_header_id      IN NUMBER,  
p_line_id        IN NUMBER) RETURN VARCHAR2;
```

Input	Description
p_view_name	Name of view calling this function
p_header_id	ID of transaction header
p_line_id	ID of transaction line

The function returns NULL by default and the calling procedure stores 01 for both Taxware and Vertex in the LINE_EXT_VARCHAR_ATTRIBUTE15 column of the ZX_PRVDR_LINE_EXTNS_GT table. This value is used to control the tax reporting level and identifies exemptions defined in the tax service provider system.

FUNCTION SERVICE_INDICATOR(

```
p_view_name      IN VARCHAR2,  
p_header_id      IN NUMBER,  
p_line_id        IN NUMBER) RETURN NUMBER;
```

Input	Description
p_view_name	Name of view calling this function
p_header_id	ID of transaction header
p_line_id	ID of transaction line

The function returns NULL by default and the calling procedure stores 1, 2, or 3 in the LINE_EXT_VARCHAR_ATTRIBUTE1 column of the ZX_PRVDR_LINE_EXTNS_GT table. 1 indicates *service*; 2 indicates *rental*; 3 indicates *non-service*. The value is taken from the eBTax Taxware: Service Indicator profile option.

FUNCTION TAX_SEL_PARM(

```
p_view_name      IN VARCHAR2,  
p_header_id      IN NUMBER,  
p_line_id        IN NUMBER) RETURN NUMBER
```

Input	Description
p_view_name	Name of view calling this function
p_header_id	ID of transaction header
p_line_id	ID of transaction line

The function returns NULL by default and the calling procedure stores the value 2 or 3 in the LINE_EXT_NUMBER_ATTRIBUTE6 column of the ZX_PRVDR_LINE_EXTNS_GT table. 2 means use only the ship-to address in the tax calculation; 3 means use all jurisdiction information in the tax calculation. The value is taken from the eBTax Taxware: Tax Selection profile option.

FUNCTION CUSTOMER_NAME(

```
p_view_name IN VARCHAR2,  
p_header_id IN NUMBER,  
p_line_id IN NUMBER) RETURN VARCHAR2;
```

Input	Description
p_view_name	Name of view calling this function
p_header_id	ID of transaction header
p_line_id	ID of transaction line

The function returns NULL by default and the calling procedure stores the bill to party PARTY_NAME from the HZ_PARTIES table in the LINE_EXT_VARCHAR_ATTRIBUTE13 column of the ZX_PRVDR_LINE_EXTNS_GT table. This value is used on the Sales/Use Tax Report to report by customer name.

FUNCTION VENDOR_CONTROL_EXEMPTIONS(

```
p_view_name      IN VARCHAR2,  
p_header_id      IN NUMBER,  
p_line_id        IN NUMBER,  
p_trx_type_id    IN NUMBER) RETURN VARCHAR2;
```

Input	Description
p_view_name	Name of view calling this function
p_header_id	ID of transaction header
p_line_id	ID of transaction line
p_trx_type_id	ID of the transaction type

The function returns NULL by default and the calling procedure stores ATTRIBUTE1 of the RA_CUST_TRX_TYPES_ALL table in the LINE_EXT_VARCHAR_ATTRIBUTE16 column of the ZX_PRVDR_LINE_EXTNS_GT table. The value corresponds to the job number which is used to determine exemptions.

FUNCTION USE_NEXPRO(

```
p_view_name    IN VARCHAR2,
p_header_id    IN NUMBER,
p_line_id      IN NUMBER) RETURN VARCHAR2
```

Input	Description
p_view_name	Name of view calling this function
p_header_id	ID of transaction header
p_line_id	ID of transaction line

The function returns NULL by default and the calling procedure assigns the value Y or N to the LINE_EXT_VARCHAR_ATTRIBUTE17 column of the ZX_PRVDR_LINE_EXTNS_GT table.

The value indicates whether Taxware uses the Nexpro functionality: Y = Use Nexpro; N = Do not use Nexpro. The value is taken from the eBTax Taxware: Use Nexpro profile option.

FUNCTION POO_ADDRESS_CODE(

```
p_view_name    IN VARCHAR2,
p_header_id    IN NUMBER,
p_line_id      IN NUMBER,
p_salesrep_id  IN NUMBER) RETURN VARCHAR2;
```

Input	Description
p_view_name	Name of view calling this function
p_header_id	ID of transaction header
p_line_id	ID of transaction line
p_salesrep_id	ID of the primary sales representative

The function returns NULL by default and the calling procedure stores the value in the ZX_PRVDR_LINE_EXTNS_GT table as per the description below. This function is only for Taxware.

The value of the first character is always 1. The rest of the string is the jurisdiction code for the Point of Order Origin. It is derived from the SALES_TAX_GEOCODE column of the RA_SALESREPS view.

FUNCTION CALCULATION_FLAG(

```
p_view_name    IN VARCHAR2,
p_header_id    IN NUMBER,
p_line_id      IN NUMBER) RETURN VARCHAR2;
```

Input	Description
p_view_name	Name of view calling this function
p_header_id	ID of transaction header
p_line_id	ID of transaction line

The function returns NULL by default and the calling procedure stores a 5-character string, to represent the five jurisdiction level calculation flags, in the LINE_EXT_VARCHAR_ATTRIBUTE21 column of the ZX_PRVDR_LINE_EXTNS_GT table. The first character is for the state tax; the second for the county tax; the third for the city tax; the fourth for the secondary county tax; and the fifth for the secondary city tax.

Each character identifies whether tax should be calculated at a particular jurisdiction level. 1 indicates that tax should not be calculated for this level; 0 indicates that tax should be calculated.

FUNCTION TRX_LINE_TYPE(

```
p_view_name    IN VARCHAR2,  
p_header_id    IN NUMBER,  
p_line_id      IN NUMBER) RETURN VARCHAR2;
```

Input	Description
p_view_name	Name of view calling this function
p_header_id	ID of transaction header
p_line_id	ID of transaction line

The function returns NULL by default and the calling procedure stores the value SALE in the LINE_EXT_VARCHAR_ATTRIBUTE1 column of the ZX_PRVDR_LINE_EXTNS_GT table. Valid values are PURCHASE, RENTAL, SALE, and SERVICE.

FUNCTION CUSTOMER_CLASS(

```
p_view_name    IN VARCHAR2,  
p_header_id    IN NUMBER,  
p_line_id      IN NUMBER,  
p_customer_id  IN NUMBER) RETURN VARCHAR2;
```

Input	Description
p_view_name	Name of view calling this function
p_header_id	ID of transaction header
p_line_id	ID of transaction line
p_customer_id	ID of customer (ship-to, bill-to, or other)

The function returns NULL by default and the calling procedure also stores the value NULL in the LINE_EXT_VARCHAR_ATTRIBUTE13 column of the ZX_PRVDR_LINE_EXTNS_GT table. You can customize the function to return a customer class code to use to determine exemptions.

PROCEDURE GET_EXEMPTIONS(

```
p_exemption_id IN NUMBER,  
p_state_exempt_percent OUT NUMBER,  
p_state_exempt_reason OUT VARCHAR2,  
p_state_cert_no OUT VARCHAR2,  
p_county_exempt_percent OUT NUMBER,  
p_county_exempt_reason OUT VARCHAR2,  
p_county_cert_no OUT VARCHAR2,  
p_city_exempt_percent OUT NUMBER,  
p_city_exempt_reason OUT VARCHAR2,  
p_city_cert_no OUT VARCHAR2,  
p_sec_county_exempt_percent OUT NUMBER,  
p_sec_city_exempt_percent OUT NUMBER,  
p_use_step OUT VARCHAR2,  
p_step_proc_flag OUT VARCHAR2,  
p_crit_flag OUT VARCHAR2)
```

Input	Description
p_exemption_id	ID of exemption record
p_<juris>_exempt_percent	Exemption percent for jurisdiction
p_<juris>_exempt_reason	Exemption reason for jurisdiction
p_<juris>_cert_no	Exemption certificate number for jurisdiction
p_use_step	Use STEP90 flag
p_step_proc_flag	STEP processing flag
p_crit_flag	Criterion flag

The procedure returns NULL values by default for all output parameters and the calling procedure assigns the value as per the description below. This procedure is called for Taxware integration only.

E-Business Tax stores exemptions for each jurisdiction individually in the ZX_EXEMPTIONS table. Therefore, this procedure may get called five times if the exemptions are defined for each of the five jurisdiction levels. E-Business Tax assigns the values stored in the ZX_EXEMPTIONS table for each jurisdiction. Only the first two characters of the exemption reason stored in ZX_EXEMPTIONS are passed to Taxware.

If ZX_EXEMPTIONS does not have exemption records for all five jurisdictions, Taxware is passed Y for p_use_step, 1 for p_step_proc_flag, and R for p_crit_flag.

If this procedure is re-written at an installation, E-Business Tax passes the values of the flags p_use_step, p_step_proc_flag and p_crit_flag to Taxware from the last call

E-Business Tax makes to the GET_EXEMPTION procedure for a transaction line. Each call to GET_EXEMPTION should return a jurisdiction-specific exempt percentage, exempt reason, and exempt certificate number that is passed to Taxware.

PROCEDURE GET_EXEMPTIONS(

```
p_exemption_id IN NUMBER,  
p_cert_no OUT  VARCHAR2,  
p_state_exempt_percent OUT  NUMBER,  
p_state_exempt_reason OUT  VARCHAR2,  
p_county_exempt_percent OUT  NUMBER,  
p_county_exempt_reason OUT  VARCHAR2,  
p_city_exempt_percent OUT  NUMBER,  
p_city_exempt_reason OUT  VARCHAR2,  
p_district_exempt_percent OUT  NUMBER,  
p_district_exempt_reason OUT  VARCHAR2)
```

Input	Description
p_exemption_id	ID of exemption record
p_<juris>_exempt_percent	Exemption percent for jurisdiction
p_<juris>_exempt_reason	Exemption reason for jurisdiction
p_cert_no	Exemption certificate number

The procedure returns NULL values by default for all output parameters and the calling procedure assigns the value as per the description below. This procedure is called for Vertex integration only.

E-Business Tax stores exemptions for each jurisdiction individually in the ZX_EXEMPTIONS table. Therefore, this procedure may get called four times if the exemptions are defined for each of the four jurisdiction levels. E-Business Tax assigns the values stored in the ZX_EXEMPTIONS table for each jurisdiction. Only the first character of the exemption reason stored in ZX_EXEMPTIONS is passed to Vertex.

If this procedure is re-written at an installation, each call to GET_EXEMPTION should return a jurisdiction-specific exempt percentage and exempt reason that is passed to Vertex. The certificate number received from the last call to this function for a transaction line is passed to Vertex for that transaction line.

Related Topics

Tax Partner Services Plug-In, *Oracle E-Business Tax Reporting Guide*

Storing Tax Information in Descriptive Flexfields and Other Applications

Some descriptive flexfields and fields in other applications are used specifically for service provider integration. The following tables list all such fields. Note that all fields are optional.

Predefined Descriptive Flexfields for Storing Tax Information

The table below shows the predefined descriptive flexfields that you can use to enter ship-from information.

Table Name	Column	Window	Field Name	Description
HR_LOCATION S_V (Location Address descriptive flexfield)	LOC_ INFORMATION 1 3	Location Address	Sales Tax Override	Ship-From jurisdiction code.
HR_LOCATION S_V (Location Address descriptive flexfield)	LOC_ INFORMATION 1 4	Location Address	Inside City Limits	Indicates whether the address is considered inside or outside the city limits (Vertex only).

User-Defined Descriptive Flexfields Used to Store Tax Information

If you want to use any of the following descriptive flexfields to store tax information, you must register each flexfield as required.

Table Name	Field Name	Column	Description	Value Set Name
AR_ RECEIVABLES_ TRX	Receivables Activity Information	ATTRIBUTE15	Post Adjustment to Service Provider	AR_TAXVDR_Y ES_NO
RA_CUST_TRX_ TYPES_ALL	Transaction Type Information	ATTRIBUTE1	Job Number (Taxware Only)	AR_TAXVDR_C HAR10

Important: Use of user-defined descriptive flexfields is considered a customization. Functions supplied by Oracle may change in future releases to support these fields in core tables. Additionally, if these columns are in use by your customizations, you may need to either redefine the tax functions so that they look in other attribute columns, or your customizations may need to be changed.

Other Application Fields Used to Store Tax Information

The table below lists fields in other applications that you can use to enter point of order acceptance (POA), point of order origin (POO), and ship-to information.

Table Name	Column	Window	Field Name	Description
JTF_RS_SALESREPS	SALES_TAX_GEOCODE	Sales Force	Geo Override	Point of Order Origin jurisdiction code (Taxware)
				Point of Order Acceptance GeoCode (Vertex)
	SALES_TAX_IN SIDE_CITY_LIMITS	Sales Force	Inside City Limits	Indicates whether the POA address is inside the city limits (Vertex Only)
HZ_LOCATION S	SALES_TAX_GEOCODE	Customer Addresses	Geo Override	Ship-to GeoCode
	SALES_TAX_IN SIDE_CITY_LIMITS	Customer Addresses	Inside City Limits	Indicates whether the ship-to address is inside the city limits (Vertex Only)
AR_SYSTEM_PARAMETERS_ALL	SALES_TAX_GEOCODE	System Options	Geo Override	Point of Order Acceptance jurisdiction code (Taxware Only)

Related Topics

Defining Descriptive Flexfields, *Oracle Applications Flexfields Guide*