

**Oracle® Retail Fiscal Management and Brazil
Localization**
Installation Guide
Release 13.2.3
E25289-01

October 2011

Copyright © 2011, Oracle. All rights reserved.

Primary Author: Wade Schwarz

Contributors: Nathan Young

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Value-Added Reseller (VAR) Language

Oracle Retail VAR Applications

The following restrictions and provisions only apply to the programs referred to in this section and licensed to you. You acknowledge that the programs may contain third party software (VAR applications) licensed to Oracle. Depending upon your product and its version number, the VAR applications may include:

(i) the **MicroStrategy** Components developed and licensed by MicroStrategy Services Corporation (MicroStrategy) of McLean, Virginia to Oracle and imbedded in the MicroStrategy for Oracle Retail Data Warehouse and MicroStrategy for Oracle Retail Planning & Optimization applications.

(ii) the **Wavelink** component developed and licensed by Wavelink Corporation (Wavelink) of Kirkland, Washington, to Oracle and imbedded in Oracle Retail Mobile Store Inventory Management.

(iii) the software component known as **Access Via**TM licensed by Access Via of Seattle, Washington, and imbedded in Oracle Retail Signs and Oracle Retail Labels and Tags.

(iv) the software component known as **Adobe Flex**TM licensed by Adobe Systems Incorporated of San Jose, California, and imbedded in Oracle Retail Promotion Planning & Optimization application.

You acknowledge and confirm that Oracle grants you use of only the object code of the VAR Applications. Oracle will not deliver source code to the VAR Applications to you. Notwithstanding any other term or condition of the agreement and this ordering document, you shall not cause or permit alteration of any VAR Applications. For purposes of this section, "alteration" refers to all alterations, translations, upgrades, enhancements, customizations or modifications of all or any portion of the VAR Applications including all reconfigurations, reassembly or reverse assembly, re-engineering or reverse engineering and recompilations or reverse compilations of the VAR Applications or any derivatives of the VAR Applications. You acknowledge that it shall be a breach of the agreement to utilize the relationship, and/or confidential information of the VAR Applications for purposes of competitive discovery.

The VAR Applications contain trade secrets of Oracle and Oracle's licensors and Customer shall not attempt, cause, or permit the alteration, decompilation, reverse engineering, disassembly or other reduction of the VAR Applications to a human perceivable form. Oracle reserves the right to replace, with functional equivalent software, any of the VAR Applications in future releases of the applicable program.

Contents

Send Us Your Comments	ix
Preface	xi
Audience	xi
Related Documents.....	xi
Customer Support.....	xi
Review Patch Documentation.....	xii
Oracle Retail Documentation on the Oracle Technology Network.....	xii
Conventions.....	xii
1 Preinstallation Tasks	1
Patch Contents.....	1
Check for the Current Version of the Installation Guide.....	1
Implementation Capacity Planning.....	2
Check Database Server Requirements	2
Check Supported Application Server Requirements	3
Verify Single Sign-On.....	4
Check Supported Web Browser and Client Requirements	4
Supported Oracle Retail Products	4
Supported Third-Party Products	5
Supported Oracle Retail Integration Technologies	5
2 RAC and Clustering	7
3 Patch Installation	9
4 RTIL Installation Tasks—Patch	11
Install Managed Server in WebLogic	11
Install Node Manager.....	15
Start the Managed Servers.....	19
Install TaxWeb Tax Rules.....	19
Install TaxWeb Tax Rules .jar Files	20
Install Datasource Configuration File	21
Expand the RTIL Application Distribution	21
Run the RTIL Application Installer	21
Resolving Errors Encountered During Application Installation.....	25
Troubleshooting RTIL Deployment	26
5 Database Installation Tasks—Patch	27
RMS/ORFM Database Patch Sequence	27
Option 1: Patch ORFM Database using the Patch Installer.....	27
Create Staging Directory for ORFM Database Schema Files	28
Run the ORFM Database Schema Patch Installer	28

Option 2: Patch ORFM Database using Controller Scripts.....	29
Create Staging Directory for RMS Database Schema Files	29
Run the RMS Database Controller Scripts.....	30
6 Batch Installation Tasks—Patch	33
Option 1: Use RMS Batch Installer to Patch	33
Create Staging Directory for RMS and ORFM Batch Patch Files	33
Copy Batch Files.....	34
Custom Modules.....	34
Run the Installer Patching Utility	34
Run RMS Batch Installer	35
Resolving Errors Encountered During Batch Installation.....	37
RETL	37
Data Conversion Scripts.....	37
Option 2: Compile ORFM Batch Directly	38
Create Staging Directory for ORFM Batch Patch Files	38
Set Environment Variables	38
Compile Batch Libraries.....	39
Compile Batch Source Code	40
Copy Data Conversion Scripts.....	40
7 Application Installation Tasks—Patch	41
Create RMS Help Managed Server.....	41
Install Node Manager.....	45
Option 1: Use RMS Application Installer to Patch	51
Create Staging Directory for RMS and ORFM Application Patch Files	51
Copy Forms and Library Patch Files.....	52
Custom Modules.....	52
Run the Installer Patching Utility	52
Run the RMS Application Installer.....	53
Delete Obsolete Files	56
Resolving Errors Encountered During Application Installation.....	57
Clustered Installations – Post-Installation Steps	57
Oracle Configuration Manager	57
RMS Reports Copied by the Application Installer	57
Test the RMS Application.....	58
Option 2: Compile ORFM Toolset and Forms Directly	58
Create Staging Directory for ORFM Application Files	58
Set Environment Variables	58
Delete Obsolete Files	59
ORFM Forms Installation	60
Install the Online Help.....	61

8 Reports Installation Tasks—Patch	63
Manually Copy Reports to Install Directory	63
BI Server Component Installation Tasks.....	63
Installation Process Overview.....	63
Extracting the BI Server Web Archive from the Source Media	64
Creating an Exploded Directory for the Installation.....	65
Configuring the BI Publisher Repository and Installing Fonts	65
Install Managed Server in WebLogic	66
Install NodeManager.....	72
Start the Managed Servers.....	77
Additional Setup Steps Before Deploying the BI Application.....	78
Deploying the BI Application in WebLogic	80
Installing the RMS/ORFM BI Publisher Templates.....	88
Configuring the RMS JDBC connection.....	88
Configuring the BIPublisher Scheduler	89
Verify Oracle BI Publisher Set Up for RMS Reports	89
9 Data Migration	91
Create Staging Directory for RMS Data Migration Files	91
Configure ORFM Data Migration Tool.....	91
Run the ORFM Data Migration Tool.....	98
A Appendix: ORFM RTIL Installer Screens	99
B Appendix: ORFM Database Patch Installer Screens	109
C Appendix: RMS Batch Installer Screens	113
D Appendix: RMS Application Installer Screens	119
E Appendix: Installer Silent Mode	131
Repeating an Installation Attempt.....	131
F Appendix: URL Reference	133
JDBC URL for a Database	133
LDAP Server URL.....	133
JNDI Provider URL for an Application	133
G Appendix: Common Installation Errors	135
Database Installer Hangs on Startup.....	135
Unreadable Buttons in the Installer	135
Warning: Could not create system preferences directory	135
Warning: Couldn't find X Input Context.....	135
Unresponsive Country and Currency Drop-Downs.....	136
Could not exel robot child process: Permission denied.....	136
ConcurrentModificationException in Installer GUI.....	137
FRM-30064: Unable to parse statement select while compiling fm_ituda.fmb	137
ORA-04031 (unable to allocate memory) error during database schema installation	137

X Error of failed request: BadWindow (invalid Window parameter)	138
RIB Errors	138
Error Connecting to Database URL	138
Multi-Threaded OCI Client Dumps Core after Reconnecting To Database	139
Forms Installer Fails on HP-UX	139
ORFM DB Installer Fails on s11071552_extax_help_gtt_l10n_br.sql after applying hotfix 11071552	140
GUI Screens Fail to Open When Running Installer	141
H Appendix: Application Deployment Method	143
I Appendix: Single Sign-On Resource Access Descriptors	145
J Appendix: RMS RETL Instructions	147
Configuration	147
RETL	147
RETL User and Permissions	147
K Appendix: Setting Up Password Stores with Oracle Wallet.....	149
About Password Stores and Oracle Wallet.....	149
Setting Up Password Stores for Database User Accounts.....	150
Setting Up Wallets for Database User Accounts.....	151
For RMS, RPM Plsql Batch, RETL DB, RWMS batch, and ARI	151
For Java Applications (SIM, ReIM, RPM, Alloc, RIB, RSL, AIP, RETL)	153
How Does the Wallet Relate to the Application?	156
How Does the Wallet Relate to Java Batch Program Use?	156
Setting Up RETL Wallets	156
Quick Guide for Retail Wallets	158
L Appendix: Installation Order	163
Enterprise Installation Order.....	163

Send Us Your Comments

Oracle Retail Fiscal Management and Brazil Localization Installation Guide, Release 13.2.3

Oracle welcomes customers' comments and suggestions on the quality and usefulness of this document.

Your feedback is important, and helps us to best meet your needs as a user of our products. For example:

- Are the implementation steps correct and complete?
- Did you understand the context of the procedures?
- Did you find any errors in the information?
- Does the structure of the information help you with your tasks?
- Do you need different information or graphics? If so, where, and in what format?
- Are the examples correct? Do you need more examples?

If you find any errors or have any other suggestions for improvement, then please tell us your name, the name of the company who has licensed our products, the title and part number of the documentation and the chapter, section, and page number (if available).

Note: Before sending us your comments, you might like to check that you have the latest version of the document and if any concerns are already addressed. To do this, access the Online Documentation available on the Oracle Technology Network Web site. It contains the most current Documentation Library plus all documents revised or released recently.

Send your comments to us using the electronic mail address: retail-doc_us@oracle.com

Please give your name, address, electronic mail address, and telephone number (optional).

If you need assistance with Oracle software, then please contact your support representative or Oracle Support Services.

If you require training or instruction in using Oracle software, then please contact your Oracle local office and inquire about our Oracle University offerings. A list of Oracle offices is available on our Web site at www.oracle.com.

Preface

Oracle Retail Installation Guides contain the requirements and procedures that are necessary for the retailer to install Oracle Retail products.

Audience

This Installation Guide is written for the following audiences:

- Database administrators (DBA)
- System analysts and designers
- Integrators and implementation staff

Related Documents

You can find more information about this product in these resources:

- *Oracle Retail Merchandising System Release Notes*
- *Oracle Retail Merchandising System Installation Guide*
- *Oracle Retail Fiscal Management -RMS Brazil Localization Implementation Guide*
- *Oracle Retail Fiscal Management Data Model*
- *Oracle Retail Merchandising System Data Model*
- *Oracle Retail Merchandising Batch Schedule*

Also see the documentation library for Oracle Business Intelligence Enterprise Edition at this URL: http://www.oracle.com/technology/documentation/bi_ee.html

Customer Support

To contact Oracle Customer Support, access My Oracle Support at the following URL: <https://support.oracle.com>

When contacting Customer Support, please provide the following:

- Product version and program/module name
- Functional and technical description of the problem (include business impact)
- Detailed step-by-step instructions to re-create
- Exact error message received
- Screen shots of each step you take

Review Patch Documentation

When you install the application for the first time, you install either a base release (for example, 13.2) or a later patch release (for example, 13.2.3). If you are installing the base release and additional patch and bundled hot fix releases, read the documentation for all releases that have occurred since the base release before you begin installation.

Documentation for patch and bundled hot fix releases can contain critical information related to the base release, as well as information about code changes since the base release.

Oracle Retail Documentation on the Oracle Technology Network

Documentation is packaged with each Oracle Retail product release. Oracle Retail product documentation is also available on the following Web site:

http://www.oracle.com/technology/documentation/oracle_retail.html

(Data Model documents are not available through Oracle Technology Network. These documents are packaged with released code, or you can obtain them through My Oracle Support.)

Documentation should be available on this Web site within a month after a product release.

Conventions

Navigate: This is a navigate statement. It tells you how to get to the start of the procedure and ends with a screen shot of the starting point and the statement “the Window Name window opens.”

This is a code sample

It is used to display examples of code

Preinstallation Tasks

Note: The RMS installer provides the option to configure multiple application deployment methods. See Appendix H: Application Deployment Method in the *Oracle Retail Merchandising System Installation Guide* to help determine your deployment approach.

Patch Contents

Patch releases include all defect fixes that have been released through bundled hot fix releases since the last patch release. Patch releases may also include new defect fixes and enhancements that have not previously been included in any bundled hot fix release.

Check for the Current Version of the Installation Guide

Corrected versions of Oracle Retail installation guides may be published whenever critical corrections are required. For critical corrections, the rerelease of an installation guide may not be attached to a release; the document will simply be replaced on the Oracle Technology Network Web site.

Before you begin installation, check to be sure that you have the most recent version of this installation guide. Oracle Retail installation guides are available on the Oracle Technology Network at the following URL:

http://www.oracle.com/technology/documentation/oracle_retail.html

An updated version of an installation guide is indicated by part number, as well as print date (month and year). An updated version uses the same part number, with a higher-numbered suffix. For example, part number E123456-02 is an updated version of an installation guide with part number E123456-01.

If a more recent version of this installation guide is available, that version supersedes all previous versions. Only use the newest version for your installation.

Implementation Capacity Planning

There is significant complexity involved in the deployment of Oracle Retail applications, and capacity planning is site specific. Oracle Retail strongly suggests that before installation or implementation you engage your integrator (such as the Oracle Retail Consulting team) and hardware vendor to request a disk sizing and capacity planning effort.

Sizing estimates are based on a number of factors, including the following:

- Workload and peak concurrent users and batch transactions
- Hardware configuration and parameters
- Data sparsity
- Application features utilized
- Length of time history is retained

Additional considerations during this process include your high availability needs as well as your backup and recovery methods.

Check Database Server Requirements

ORFM requires that the RMS 13.2.3 database schema be installed. See the *Oracle Retail Merchandising System Installation Guide* for the supported database server requirements.

Check Supported Application Server Requirements

General requirements for an application server capable of running ORFM include the following.

Note: Files required for Oracle Configuration Manager (OCM) are removed after OPatch is used to patch a WebLogic server. This will not cause the product installers to fail, but will cause OCM installation to fail. To work around this issue back up the content of the \$ORACLE_HOME/utls/ccr/lib directory prior to applying a patch using OPatch, and recopy the content back after you apply any patches. ORACLE_HOME is the location where WebLogic has been installed.

Supported on	Versions Supported
Application Server OS	<p>OS certified with Oracle Fusion Middleware 11g Release 1 (11.1.1.3). Options are:</p> <ul style="list-style-type: none"> ▪ Oracle Linux 5 Update 5 for x86-64 (Actual hardware or Oracle virtual machine). ▪ Red Hat Enterprise Linux 5 Update 5 (RHEL 5.5) for x86-64 (Actual hardware or Oracle virtual machine). ▪ AIX 6.1 (Actual hardware or LPARs) ▪ Solaris 10 Sparc (Actual hardware or logical domains) ▪ HP-UX 11.31 Integrity (Actual hardware, HPVM, or vPars)
Application Server	<p>Oracle Fusion Middleware 11g Release 1 (11.1.1.3) with the following one off patches.</p> <ul style="list-style-type: none"> ▪ 6880880 – New Opatch version for Linux 64-bit (Required for Forms 11.1.1.3 component) ▪ 10065423 - MERGE REQUEST ON TOP OF 11.1.1.3.0 FOR BUGS 9891666 9891675 ▪ 9356983 - FORMS FAIL TO COMPILE WITH FRM-30312 WHEN NLS_LANG INCLUDES UTF8 CHARACTERSET <p>Note: These patches are for Linux 64-bit only, for other OSes these patches are not required. Patch 10065423 must be applied before patch 9356983.</p> <p>Components</p> <ul style="list-style-type: none"> ▪ Oracle WebLogic Server 11g Release 1 (10.3.3) ▪ Oracle Forms Services 11g Release 1 (11.1.1.3) <p>Other components</p> <ul style="list-style-type: none"> ▪ Oracle BI Publisher 10g (10.1.3.4) <p>Required for SSO</p> <ul style="list-style-type: none"> ▪ Oracle Internet Directory 10g (10.1.4.3)

Verify Single Sign-On

If a single sign-on is to be used, verify the Oracle Infrastructure Server 10g version 10.1.4.3 server has been installed. If applicable, verify the Oracle HTTP server hosting Oracle Forms is registered with the Infrastructure Oracle Internet Directory.

Check Supported Web Browser and Client Requirements

General requirements for client running RMS include the following.

Requirement	Version
Operating system	Windows XP
Display resolution	1024x768 or higher
Processor	2.6GHz or higher
Memory	1GByte or higher
Networking	intranet with at least 10Mbps data rate
Sun Java Runtime Environment	1.6.0_22+
Browser	Microsoft Internet Explorer version 7.0

Note: Oracle Retail does not recommend or support installations of ORFM with less than 256 kb bandwidth available between the PC client location (store and warehouse locations) and the data center at which the application server resides. Attempting to utilize less than 256 kb total available bandwidth causes unpredictable network utilization spikes, and performance of the ORFM screens degrades below requirements established for the product. The 256 kb requirement provides reasonable, predictable performance and network utilization.

Supported Oracle Retail Products

Product	Version
Oracle Retail Merchandising System (RMS)	13.2.3
Oracle Retail Store Inventory Management (SIM)	13.2.3
Oracle Retail Warehouse Management System (RWMS)	13.2.3

Supported Third-Party Products

Product	Version
Mastersaf	SPED – Mastersaf DW since V2R01 (Version 2 Release 01) NFE – Masteresaf DFe (NFe for goods, NFSe for services and CTe for transport) V1.R54
TaxWeb Tax Rules (The Tax Rules software is a product of TaxWeb Compliance Software S.A.)	2.8.7 Note: ORFM/RTIL was tested with TaxWeb v2.8.7. Please contact TaxWeb for the latest compatible release (http://www.taxweb.com.br).

Supported Oracle Retail Integration Technologies

Integration Technology	Version
Oracle Retail Integration Bus (RIB)	13.2.3

Note: The following integration points are not supported for ORFM/RMS Brazil Localization, but they are supported with non-Brazil RMS:

Oracle E-Business Suite integration using the Oracle Financial Operations Control Integration Pack for Oracle Retail Merchandising Suite and Oracle E-Business Suite Financials in Oracle Application Integration Architecture 2.5.

PeopleSoft Enterprise Financials integration using the Oracle Retail Merchandising Integration Pack for PeopleSoft Enterprise Financials: Financial Operations Control in Oracle Application Integration Architecture 2.5.

RAC and Clustering

Oracle Retail Fiscal Management has been validated to run in two configurations on Linux:

- Standalone WebLogic Server and Database installations
- Real Application Cluster Database and Oracle Application Server Clustering

The Oracle Retail products have been validated against an 11.2.0.2 RAC database. When using a RAC database, all JDBC connections should be configured to use OCI connections rather than THIN connections. It is suggested that when using OCI connections, the Oracle Retail products database be configured in the tnsnames.ora file used by the WebLogic Server installations.

Clustering for WebLogic Server 10.3.3 is managed as an Active-Active cluster accessed through a Load Balancer. Validation has been completed utilizing a RAC 11.2.0.2 Oracle Internet Directory database with the WebLogic 10.3.3 cluster. It is suggested that a Web Tier 11.1.1.3 installation be configured to reflect all application server installations if SSO will be utilized.


References for Configuration:

- Oracle Fusion Middleware High Availability Guide 11g Release 1 (11.1.1) Part Number E10106-09
- Oracle Real Application Clusters Administration and Deployment Guide 11g Release 2 (11.2) Part Number E16795-11

Patch Installation

The database portion of ORFM can be patched from release 13.2.2. This guide details the steps needed to perform a patch installation of ORFM.

To successfully complete the ORFM 13.2.3 patch, installers from the RMS 13.2, ORFM 13.2, RMS 13.2.3 and ORFM 13.2.3 releases must be run in a specific sequence.



This guide explains the steps needed to perform an installation of RMS/ORFM. These chapters should be followed in order:

- Chapter 4 - RTIL Installation Tasks—Patch
- Chapter 5 - Database Installation Tasks—Patch
- Chapter 6 - Batch Installation Tasks—Patch
- Chapter 7 - Application Installation Tasks—Patch
- Chapter 8 - Reports Installation Tasks—Patch

RTIL Installation Tasks—Patch


Before proceeding, you must install Oracle WebLogic Server 11g Release 1 (10.3.3) and patches listed in Chapter 1, [Preinstallation Tasks](#). The RTIL application is deployed to a WebLogic Managed server within the WebLogic installation.

Note: There are no RTIL updates for the 13.2.3 release. If you have already installed RTIL 13.2.2, you have the latest code and can skip to the next chapter.


Install Managed Server in WebLogic

Before running the application installer, you must install a managed server for the RTIL application in WebLogic if it was not created during the domain installation.


1. Log in to the Administration Console.




2. Click **Lock & Edit**.
3. Navigate to **Environment > Servers**. Select new tab of the servers on the right side.




4. Set the following variables:
 - **Server Name:** This value should be specific to your targeted application (for example, rtil-server).
 - **Server Listen Address:** <weblogic server> (for example, redevlv0074.us.oracle.com)
 - **Server Listen Port:** A free port. Check for availability.
A suggestion is to increment the AdminServer port by two and keep incrementing by two for each managed server (for example, 17003, 17005, 17007, and so on.)
5. Click Next.



6. Click Finish.




7. Click **Activate Changes** on the left side. Once the changes are activated, the State of the rttl-server should change to SHUTDOWN status.





Install Node Manager

Install Node Manager if it was not created during domain install. The node manager is required so that the managed servers can be started and stopped through the admin console. Only one node manager is needed per WebLogic installation.


1. Log in to the Administration Console.
2. Click **Lock & Edit**. Navigate to Environments->Machines. Click **New**.
3. The following page is displayed. Set the following variables:
 - **Name:** Logical machine name
 - **Machine OS:** UNIX




4. Click **OK** to activate the changes.
5. Click the machine created.



6. Click the Node Manager tab and update the details below.
 - **Type:** Plain
 - **Listen Address:** <weblogic server> (for example, redevlv0074.us.oracle.com)
 - **Listen Port:** Assign a port number. The default port is 5556.



7. Click **Save**.
8. Click **Activate Changes**.
9. Click **Lock & Edit**.
10. Navigate to **Environments > machines**. Click the machine name. Select the **Servers** tab. Click **Add**.



11. Add the managed servers that need to be configured with the Nodemanager. Save changes.
 - From the drop down select the managed server to be added to nodemanager
 - Server: <app-server> (for example: rttl-server)
12. Click **Next**. Click **Finish**.
13. To activate changes the server must be stopped as follows:


```
<WLS_HOME>/user_projects/domains/<domain name>/bin/stopManagedWebLogic.sh rttl-server ${server_name}:${server_port}
```
14. Go to each managed server that is being added to the machine and click the Server Start tab. In the Class Path box, add the following:


```
<full-path-to-domain>/servers/<managed-server>
```

For example:

```
/u00/webadmin/product/10.3.3/WLS/user_projects/domains/rttl_domain/servers/rttl-server
```
15. Click **Save**.
16. Click **Activate Changes**.

Start the Managed Servers

To start the managed servers, complete the following steps.


1. Start the Node Manager from the command line.

```
<WLS_HOME>/wlserver_10.3/server/bin startNodeManager.sh
```

After the Node Manager is started, the managed servers can be started through the admin console.

2. Update weblogic console->servers-><app>-server->server start tab->Classpath with the following:

```
CLASSPATH: <WLS_HOME>/modules/com.bea.core.apache.log4j_1.2.13.jar
```



3. Navigate to Environments > Servers. Select <app-server> (for example, rtil-server server managed server). Click the Control tab.
4. Click **Start** to start the managed server.

Install TaxWeb Tax Rules

Important Note: The TaxWeb installation instructions provided in this chapter are for reference only and are subject to change per TaxWeb requirements. In all cases, the installation guide provided by TaxWeb is considered the master document.

TaxWeb Tax Rules is a third party tax rules engine that is actively used within the Brazilian market. TaxWeb Tax Rules is a Java application. The binary distribution is made available as a set of Java Archive (jar) files.

Within the Oracle Retail suite, TaxWeb Tax Rules is integrated with RMS and ORFM through RTIL. To install TaxWeb Tax Rules so that it integrates with Oracle Retail applications, complete the following steps.

1. Be sure Oracle Database 11g Release 2 is installed, as TaxWeb Tax Rules requires it for its application schema installation and configuration.
2. Install the jar files in the lib folder of the WebLogic domain in which RTIL will be deployed.
3. Install the data source configuration file (taxcomponent.conf) in the config folder of the WebLogic domain in which RTIL will be deployed.
4. Configure the data source in the WebLogic domain.

For detailed information about installation and how to configure the Tax Rules application and data source, refer to the installation guide provided by TaxWeb Tax Rules.

Important Note: If there is an existing Tax Rules database user from a previously installed release, it should not be used. Drop and recreate the user with scripts from the Tax Rules release supported for 13.2.3.

Install TaxWeb Tax Rules .jar Files

Copy the list of mentioned jars from the TaxWeb Tax Rules bundle delivered by TaxWeb to the lib folder of the Weblogic domain in which RTIL will be deployed.

- commons-logging-api.jar
- taxinterfaces.jar
- commons-logging-1.1.1.jar
- commons-pool-1.5.5.jar
- commons-logging-1.3.jar
- commons-io-2.0.1.jar
- commons-beanutils-1.7.jar
- commons-beanutils-1.8.3.jar
- commons-lang-2.4.jar
- log4j.jar
- commons-collections-3.2.1.jar
- javaee-api-5.0-1.jar
- ojdbc5.jar
- taxrules.jar

Note : All the above mentioned jars are used and owned by the TaxWeb Tax Rules application. In subsequent releases, jars may be added or removed by TaxWeb. See the *Oracle Retail Fiscal Management/RMS Brazil Localization Implementation Guide* for details on redeploying your .jar files.

Install Datasource Configuration File

The prerequisite for this step is the availability of a TaxWeb Tax Rules schema which should be installed based on the TaxWeb Tax Rules installation guide. The datasource should be created in the WebLogic domain in which RTIL will be installed. Please refer to the TaxWeb Tax Rules installation guide for data source creation details.

The configured datasource name should be included in the taxcomponent.conf file supplied in the TaxWeb Tax Rules distribution and placed in the config folder of the Weblogic domain in which RTIL will be deployed.

Expand the RTIL Application Distribution

To expand the RTIL application distribution, complete the following steps.

1. Create a new staging directory for the RTIL application distribution (rtil13application.zip). There should be a minimum of 40 MB disk space available for the application installation files.

Example:

```
<WLS_HOME> /user_projects/domain/<domain_name>/
servers/<rtil-server>/rtil-staging
```

This location is referred to as STAGING_DIR for the remainder of this chapter.

2. Copy rtil13application.zip to STAGING_DIR and extract its contents.

Run the RTIL Application Installer

Once you have a WebLogic instance that is configured and started, you can run the RTIL application installer. This installer configures and deploys the RTIL application.

Note: See [Appendix: ORFM RTIL Installer Screens](#) for details on every screen and field in the RTIL application installer.

Note: It is recommended that the installer be run as the same UNIX account that owns the WebLogic application server ORACLE_HOME files. This method takes full advantage of the installer's capabilities. If the installer is run as a different user, the Manual Deployment Option must be selected.

1. Change directories to STAGING_DIR/rtil/application. This directory was created when the rtil13application.zip file was expanded under STAGING_DIR.
2. Set and export the following environment variables.

Variable	Description	Example
ORACLE_HOME	The location where Weblogic has been installed	ORACLE_HOME= /u00/webadmin/product/10.3.3/WLS export ORACLE_HOME
WEBLOGIC_DOMAIN_HOME	The location where the Weblogic domain has been installed	WEBLOGIC_DOMAIN_HOME=\$ORACLE_HOME/ user_projects/domains/adf_domain/ Export WEBLOGIC_DOMAIN_HOME

Variable	Description	Example
JAVA_HOME	Location of a Java 6.0 (1.6.0) JDK	JAVA_HOME= /u00/webadmin/java/jdk1.6.0_12 Export JAVA_HOME
DISPLAY	Address and port of X server on desktop system of user running installation. Optional for RTIL application installer.	DISPLAY=<IP address>:0 export DISPLAY

3. If you are using an X server (such as Exceed), set the DISPLAY environment variable so that you can run the installer in GUI mode (recommended). If you are not using an X server, or the GUI is too slow over your network, do not set DISPLAY for text mode.
4. Run the install.sh script. This launches the installer. After installation is complete, a detailed installation log file is created (rtil13install.<timestamp>.log).

Note: The typical usage for GUI mode is no arguments.

```
./install.sh [text | silent]
```


5. The installer leaves behind the ant.install.properties file for future reference and repeat installations. This file contains inputs you provided. As a security precaution, make sure that the file has restrictive permissions.

Example: `chmod 600 ant.install.properties`

6. Once the installer is finished, open a web browser and navigate to the URL reported at the end of the installer logs. You should see this text, which indicates RTIL was installed successfully:


```
E|invocationKey not present
```

7. Once RTIL installation is complete, set the JTA transaction timeout to 1000 seconds in the WebLogic Admin console.
 - To override the default JTA timeout, log in to the WebLogic admin console. Navigate to Services > JTA link to go to the Configuration section.
 - Replace the default timeout of 30 seconds with 1000.
 - For the changes to take effect, bounce the WebLogic Server (for the domain).




8. Once RTIL installation is complete, configure Xmx and Xms values in the WebLogic Admin console.

a. Log in to the admin console.




b. Click **Lock & Edit**.


c. Navigate to Servers -> RTIL Managed Server (for example, rtil-server).




d. Click the Server Start tab under configuration.



- e. Change the Xmx and Xms values to 3072m.
Example: `-Xmx3072m -Xms3072m -XX:MaxPermSize=256m`
- f. Save the configuration.
- g. Click **Activate Changes**.



- h. Navigate to Environment → Servers
- i. Click the Control Tab, under Summary of Servers.



- j. Restart RTIL Managed Server.

Resolving Errors Encountered During Application Installation

If the application installer encounters any errors, execution is halted immediately. You can run the installer in silent mode so that you do not have to retype the settings for your environment. See [Appendix: Installer Silent Mode](#) for silent mode instructions.

See [Appendix: Common Installation Errors](#) for common installation errors.

Because full application installation is required every time, any previous partial installations are overwritten by the successful installation.

Troubleshooting RTIL Deployment

Confirm the following details are in the RTIL database. If they are not, complete the following steps to configure the RTIL URL in the WebService Consumer.

Log in to the RMS database schema as an RMS user.

Add a record in the retail_service_report_url table with the following column values.

Column Name	Value
RS_CODE	RTIL
RS_NAME	Retail Tax Integration Layer
RS_TYPE	S
URL	<RTIL URL> (for example, http://<rtilhostname:port>/rtil-web/invokeApp
SERVER	<RTIL_SERVER_NAME>
PORT	<PORT_NUMBER> (for example, 17002)

Database Installation Tasks—Patch

There are two different methods to use for installing the ORFM 13.2.3 database schema patch. Option 1 uses the installer to apply the patch. Option 2 uses the patch controller scripts directly.

Note: If any ORFM hotfixes have been applied to the schema after 13.2, be aware that using the installer or controller scripts to apply the 13.2.3 patch can have unexpected results. You will need to decide if it is safe to run all the scripts in the patch, or if the scripts need to be selectively run.

Note: If you have manually applied the required hotfix 11071552, you will encounter errors when running the ORFM 13.2.1 database schema patch. See [Appendix G: Common Installation Errors](#) for the workaround and more details.

Note: Shutdown any applications that may be using the RMS schema (for example RIB) before applying a schema patch.

RMS/ORFM Database Patch Sequence

It is very important that the RMS and ORFM database patches are run in the correct sequence. Use the following sequence to determine the order to apply RMS and ORFM patches. Running patches out of sequence can cause installation errors.

1. RMS 13.2 DB Upgrade
2. ORFM 13.2 DB Install
3. RMS 13.2.1 DB Patch
4. ORFM 13.2.1 DB Patch
5. RMS 13.2.2 DB Patch
6. ORFM 13.2.2 DB Patch
7. RMS 13.2.3 DB Patch
8. ORFM 13.2.3 DB Patch

Option 1: Patch ORFM Database using the Patch Installer

The ORFM 13.2.3 database schema patch installer may be used to apply the ORFM 13.2.3 patch to a schema from 13.2. The installer should only be used to apply the patch if the schema being patched does not contain customizations or hotfixes. The patch may also be applied outside of the installer by calling the controller scripts directly. See [Option 2: Patch ORFM Database using Controller Scripts](#) later in this chapter for details on this method.

Before you apply the ORFM 13.2.3 patch:

- Make a backup of all your objects and database schema.
- Determine which patches and hotfix bundles have already been installed.
- Make sure the required RMS and ORFM schema patches have been applied. Refer to the section **RMS/ORFM Database Patch Sequence** for details.
- Review the enclosed 13.2.3 Release Notes (rms-1323-rn.pdf).

Create Staging Directory for ORFM Database Schema Files

To create a staging directory for ORFM database schema files, complete the following steps.

1. Log into the database server as a user that can connect to the RMS database.
2. Create a staging directory for the ORFM 13.2.3 Patch. There should be a minimum of 40 MB disk space available in this location.
3. Copy the orfm1323dbpatch.zip file from the ORFM 13.2.3 release to the staging directory. This is referred to as DB_PATCH_DIR when patching a database schema.
4. Change directories to DB_PATCH_DIR and extract the orfm1323dbpatch.zip. This creates a orfm/dbschemapatch subdirectory under DB_PATCH_DIR

Run the ORFM Database Schema Patch Installer

To run the ORFM database schema patch installer, complete the following steps.

Note: See [Appendix: ORFM Database Patch Installer Screens](#) for details about the screens and fields in the ORFM database schema patch installer.

1. Change directories to DB_PATCH_DIR/orfm/dbschemapatch.
2. Source the oraenv script to set up the Oracle environment variables (such as ORACLE_HOME, ORACLE_SID, PATH).

```
Example: prompt$ . oraenv
          ORACLE_SID = [] ? mydb
          prompt$
```

Verify the ORACLE_HOME and ORACLE_SID variables after running this script.

```
Example: prompt$ echo $ORACLE_HOME
          /u00/oracle/product/mydbversion
          prompt$ echo $ORACLE_SID
          mydb
```

3. Set and export the following environment variables. These variables are needed in addition to the environment variables set by the oraenv script above.

Variable	Description	Example
NLS_LANG	Locale setting for Oracle database client	NLS_LANG=AMERICAN_AMERICA.UTF8 export NLS_LANG
DISPLAY	Address and port of X server on desktop system of user running install. Optional for dbschema installer	DISPLAY=<IP address>:0 export DISPLAY

4. If you are going to run the installer in GUI mode using an X server, you need to have the XTEST extension enabled. This setting is not always enabled by default in your X server. See [Appendix: Common Installation Errors](#) for details.
5. If the patch installer has already been run in this location you may wish to back up the ant.install.properties file. The settings from the ORFM 13.2.3 patch install will be refreshed with the latest input every time the installer runs.
6. Run the install.sh script to start the installer.

Note: Below are the usage details for install.sh. The typical usage for GUI mode is no arguments.

```
install.sh [text | silent]
```

7. On the Apply a Patch page for each product, provide the path to the corresponding controller ksh script. This path will be DB_PATCH_DIR/rms/dbschemapatch/mom-dbpatch/<version>/orfm. This directory should contain a orfm_controller.ksh file, which the installer runs to apply the ORFM 13.2.3 Patch.
8. The installer leaves behind the ant.install.properties file for future reference and repeat installations. This file contains inputs you provided. As a security precaution, make sure that the file has restrictive permissions.

Example: `chmod 600 ant.install.properties`

Option 2: Patch ORFM Database using Controller Scripts

While the installer can be used to apply the entire ORFM database patch, there are situations in which it is better to run the patch directly with the scripts released in the patch. The installer calls start-all ksh scripts named orfm_controller.ksh which run all of the files in the patch. If there are any customizations or hotfixes in the schema then certain statements in the patch may result in errors. In this situation it is better to investigate where the conflicts are and fix the SQL scripts accordingly.

Before you apply the ORFM 13.2.3 patch:

- Make a backup of all your objects and database schema.
- Determine which patches and hotfix bundles have already been installed
- Make sure the required RMS and ORFM schema patches have been applied. Refer to the section **RMS/ORFM Database Patch Sequence** for details.
- Review the enclosed 13.2.3 Patch Release Notes (rms-1323-rn.pdf).

Create Staging Directory for RMS Database Schema Files

To create a staging directory for RMS database schema files, complete the following steps.

1. Log into the database server as a user that can connect to the RMS database.
2. Create a staging directory for the ORFM 13.2.3 Patch. There should be a minimum of 40 MB disk space available in this location.
3. Copy the orfm1323dbpatch.zip file from the ORFM 13.2.3 release to the staging directory. This is referred to as DB_PATCH_DIR when patching a database schema.
4. Change directories to DB_PATCH_DIR and extract the orfm1323dbpatch.zip. This creates a orfm/dbschemapatch subdirectory under DB_PATCH_DIR

Run the RMS Database Controller Scripts

To run the RMS database controller scripts, complete the following steps.

1. Change directories to `DB_PATCH_DIR/orfm/dbschemapatch/orfm-dbpatch/`.
2. Source the `oraenv` script to set up the Oracle environment variables (`ORACLE_HOME`, `ORACLE_SID`, `PATH`, etc)

```
Example: prompt$ . oraenv
          ORACLE_SID = [] ? mydb
          prompt$
```

3. Verify the `ORACLE_HOME` and `ORACLE_SID` variables after running this script.

```
Example: prompt$ echo $ORACLE_HOME
          /u00/oracle/product/mydbversion
          prompt$ echo $ORACLE_SID
          mydb
```

4. Set and export the `NLS_LANG` environment variable.

```
Example: NLS_LANG=AMERICAN_AMERICA.UTF8
          export NLS_LANG
```

5. For each version you want to patch, configure the individual `controller.cfg` files as follows:

- Copy `DB_PATCH_DIR/orfm/dbschemapatch/orfm-dbpatch/<version>/orfm/templates/controller.cfg` to `DB_PATCH_DIR/orfm/dbschemapatch/orfm-dbpatch/<version>/orfm/controller.cfg`
- Open the `controller.cfg` file you just created and replace the tokens for the following variables with the appropriate values:
 - i. Export `PATCH_DIR= DB_PATCH_DIR/orfm/dbschemapatch/orfm-dbpatch/<version>/orfm`
 - ii. export `SCHEMA_OWNER=<The name of the RMS schema>`
 - iii. export `MMUSER=< The name of the RMS schema >`
 - iv. export `ORACLE_SID=<SID for the database the MMUSER schema resides in>`
 - v. export `TNS_ADMIN=/path/to/wallet/files/dir/`
 - vi. export `UP=/@<Schema Owner Wallet Alias>`

```
Note: See Appendix: Setting Up Password Stores with Oracle Wallet for instructions to set up the database wallet.
```

6. For each version you wish to patch, `cd` to `DB_PATCH_DIR/orfm/dbschemapatch/orfm-dbpatch/<version>/orfm` and run the following commands:

```
$ ./orfm_controller.ksh DBO Y
```

7. If the installation fails for any of the patches before completion, look at the logs in the `DB_PATCH_DIR/orfm/dbschemapatch/orfm-dbpatch/<version>/orfm/error` and `DB_PATCH_DIR/orfm/dbschemapatch/orfm-dbpatch/<version>/orfm/log` directories to determine the source of the error. You can continue the patch by rerunning the `orfm_controller.ksh` file, but only if the files generated in the `DB_PATCH_DIR/orfm/dbschemapatch/orfm-dbpatch/<version>/orfm/processed` directory from the last patch attempt are still there. Any scripts that ran previously will be skipped. If you wish to start a new patch, delete all files in the `DB_PATCH_DIR/orfm/dbschemapatch/orfm-dbpatch/<version>/orfm/processed` directory.

Batch Installation Tasks—Patch

There are two different methods to use for installing the ORFM 13.2.3 Batch Patch. Option 1 uses the RMS installer to apply patch. Option 2 compiles the batch directly.

Option 1: Use RMS Batch Installer to Patch

Note: If using the RMS Batch Installer to apply the ORFM 13.2.3 patch, the RMS 13.2.3 and ORFM 13.2.3 Batch patches should be applied at the same time. This section provides instructions on how to do this.

As shipped, the RMS 13.2 Batch installer will install and compile the batch programs for version 13.2. Patches for ORFM batch may be applied by copying the new source files and recompiling in place in the environment using the profile scripts created by the installer. This is the method to use if there is already an environment at the previous patch level. Go to the section “Option 2: Compile ORFM Batch Directly” for these instructions.

The installer method is only intended for new environments. Do not use the installer patching utility to attempt patching of batch in existing environments with the installer. If the patch is applied to customizations, they will be overwritten.

In this section, STAGING_DIR refers to the location where the RMS 13.2 Batch installer was originally expanded. The installer files from the original RMS 13.2 installation can be re-used or a new directory can be created with a fresh copy of the RMS 13.2 application installer.

Before you apply the RMS and ORFM 13.2.3 Batch patches:

- Make a backup of all your Batch files.
- Review the enclosed 13.2.3 Patch Release Notes (rms-1323-rn.pdf).

Before copying over any files:

- Note whether customizations have been made to the module. If so, then the customizations must be reapplied over the new version of the file (or the fix may need to be applied to the custom version of the code).
- Copy the original files to a different directory before copying over them in case they need to be referred to at a later date.

Create Staging Directory for RMS and ORFM Batch Patch Files

To create a staging directory for RMS and ORFM batch patch files, complete the following steps.

1. Log into the database server as a user that can connect to the RMS database.
2. Create a staging directory for the RMS 13.2.3 Batch Patch. There should be a minimum of 25 MB disk space available in this location.
3. Copy the rms1323batchpatch.zip file from the RMS 13.2.3 release to the staging directory. This is referred to as RMS_BATCH_PATCH_DIR when patching a database schema.

4. Change directories to `RMS_BATCH_PATCH_DIR` and extract the **rms1323batchpatch.zip** file. This creates a batch-patch subdirectory under `RMS_BATCH_PATCH_DIR`.
5. Create a staging directory for the ORFM 13.2.3 Batch Patch. There should be a minimum of 5 MB disk space available in this location. This should be a different directory than `RMS_BATCH_PATCH_DIR`.
6. Copy the `orfm1323batchpatch.zip` file from the ORFM 13.2.3 release to the staging directory. This is referred to as `ORFM_BATCH_PATCH_DIR` when patching a database schema.
7. Change directories to `ORFM_BATCH_PATCH_DIR` and extract the **orfm1323batchpatch.zip** file. This creates a batch-patch subdirectory under `ORFM_BATCH_PATCH_DIR`.
8. If you do not already have one, create a staging directory for the RMS batch installation software or use the same staging directory as created in the database schema step above. There should be a minimum of 35 MB disk space available in this location.
9. Copy the **rms13batch.zip** file from the RMS 13.2 release to the staging directory. This is referred to as `STAGING_DIR` when installing the RMS batch software.
10. Change directories to `STAGING_DIR` and extract the `rms13batch.zip` file. This creates an `rms/batch` subdirectory under `STAGING_DIR`.

Copy Batch Files

For new environments, the installer can be used to install and compile the batch programs at the latest patch level using the installer patching utility included with RMS and ORFM batch patches. The utility is located under `RMS_BATCH_PATCH_DIR/batch-patch/patch-util` and `ORFM_BATCH_PATCH_DIR/batch-patch/patch-util`. This utility will accept as input the RMS and ORFM patch files and add them to the RMS 13.2 Batch installer package. After running this utility, the RMS Batch installer can be used to install the environment, and they will install the latest version of each batch module.

Custom Modules

Custom source can be provided by the user in a folder named `RMS_BATCH_PATCH_DIR/batch-patch/patch-util/custom` and `ORFM_BATCH_PATCH_DIR/batch-patch/patch-util/custom`. The source code in this folder is applied last, after all patches have been applied.

Run the Installer Patching Utility

To run the installer patching utility, complete the following steps.

1. Set the `JAVA_HOME` environment variable to point to a JDK which is being used by WebLogic install.
2. Set the `ANT_HOME` environment variable to point to an Ant installation. There is one included with the RMS installer that can be used to do this.

```
ANT_HOME=STAGING_DIR/rms/batch/ant
export ANT_HOME
```
3. Change directories to `RMS_BATCH_PATCH_DIR/batch-patch/patch-util/`
4. Modify the `patch.properties` file. Set the `staging.dir` and `patch.to.version` properties.

Property Name	Description
installer.dir	The directory where the RMS installer files are located under STAGING_DIR. Example: /opt/rms/batch
patch.to.version	The version you want to patch to Example: 13.2.3

5. Run the patch.sh script. This script will copy the RMS files from each patch from 13.2 up to the patch specified in the **patch.to.version** property. These files are copied into the RMS installer package.
6. Change directories to ORFM_BATCH_PATCH_DIR/batch-patch/patch-util/
7. Modify the patch.properties file. Set the staging.dir and patch.to.version properties.

Property Name	Description
installer.dir	The directory where the RMS installer files are located under STAGING_DIR. Example: /opt/rms/batch
patch.to.version	The version want to patch to Example: 13.2.3

8. Run the patch.sh script. This script will copy the ORFM files from each patch from 13.2.0 up to the patch specified in the **patch.to.version** property. These files are copied into the RMS installer package.

Run RMS Batch Installer

To run the RMS batch installer, complete the following steps.

Note: See [Appendix: RMS Batch Installer Screens](#) for details on every screen and field in the batch installer.

1. Change directories to STAGING_DIR/rms/batch. This directory was created when the rms13batch.zip file was expanded under STAGING_DIR.
2. Source the oraenv script to set up the Oracle environment variables (ORACLE_HOME, ORACLE_SID, PATH, etc)

```
Example: prompt$ . oraenv
          ORACLE_SID = [] ? mydb
          prompt$
```

Verify the ORACLE_HOME and ORACLE_SID variables after running this script.

```
Example: prompt$ echo $ORACLE_HOME
          /u00/oracle/product/mydbversion
          prompt$ echo $ORACLE_SID
          mydb
```

- Verify that the following executables are available from PATH: make, makedepend, cc, ar.

Example: Here are some locations where makedepend is commonly found:

Linux:	/usr/X11R6/bin
SUN:	/usr/openwin/bin
AIX:	/usr/X11R6/bin
HP-UX:	/opt/imak/bin

Note: For environments running Solaris and Oracle RDBMS 11.2.0.2, ensure Sun Studio 12 compiler is in the path.

For example,

```
export
PATH=/vol.rtk/compilers/sunstudio12.1/bin:/usr/xpg4/b
in:$PATH
```

- Set and export the following environment variables. These variables are needed in addition to the environment variables set by the oraenv script above.

Property Name	Description	Example
DISPLAY	Address and port of X server on desktop system of user running install. Optional for batch installer	DISPLAY=<IP address>:0 export DISPLAY

- If you are going to run the installer in GUI mode using an X server, you need to have the XTEST extension enabled. This setting is not always enabled by default in your X server. See Appendix G: Common Installation Errors for more details.
- Run the install.sh script to start the installer.

Note: Below are the usage details for install.sh. The typical usage for GUI mode is no arguments.

```
./install.sh [text | silent]
```

Depending on system resources, a typical RMS batch installation takes anywhere from 20 to 60 minutes.

The installer will ask for an installation directory. This is the destination directory for the RMS files. This directory is referred to as `INSTALL_DIR` for the remainder of this chapter. Do not provide an `INSTALL_DIR` that is located at or underneath `STAGING_DIR`.

- After the installer is complete, you can check its log file: `rms.batch.install.<timestamp>.log`.
- The installer leaves behind the `ant.install.properties` file for future reference and repeat installations. This file contains inputs you provided. As a security precaution, make sure that the file has restrictive permissions.

Example: `chmod 600 ant.install.properties`

Note: The object counts performed by the installer may be off due to the patch adding or removing modules. The installer warnings about this can be ignored

Resolving Errors Encountered During Batch Installation

The RMS batch installer is a full install that starts from the beginning each time it is run. If you encounter errors in your environment, after resolving the issue you can safely run the batch installer again to attempt another installation.

RETL

The RMS batch installer installs the RETL files under `INSTALL_DIR/RETLfor<product>/rfx`.

See Appendix: RMS RETL Instructions of this document for more information about RETL.

Data Conversion Scripts

The RMS batch installer installs the data conversion scripts under `INSTALL_DIR/external/scripts`. To complete the setup of these files, perform the following steps.

1. Create the following new directories:

`INSTALL_DIR/external/data`

`INSTALL_DIR/external/logs`

The RMS Batch installer should have already created `INSTALL_DIR/scripts`.

2. Log into sqlplus as SYSTEM and run the following commands:

```
SQL> create or replace directory rms13dev_ext_data as
'INSTALL_DIR/external/data' ;
```

```
SQL> create or replace directory rms13dev_ext_logs as
'INSTALL_DIR/external/logs' ;
```

Note: You need to replace `INSTALL_DIR` with your `INSTALL_DIR` and you can rename the external data and log directory.

Note: The user that creates these directories owns them.

Note: The data and logs directories should be `chmoded 777`.

3. Log into sqlplus as SYSTEM and grant access to them by running the following commands:

```
SQL> grant read on directory rms13dev_ext_data to public;
```

```
SQL> grant read, write on directory rms13dev_ext_logs to public
```

4. Grant the following privileges to any other users who will be using data conversion.

```
SQL> grant read on directory rms13dev_ext_data to RMS13DEVc;
```

```
SQL> grant read, write on directory rms13dev_ext_logs to RMS13DEV;
```

Option 2: Compile ORFM Batch Directly

Note: There is no ORFM batch added for the 13.2.3 release. If you have already installed the ORFM 13.2.2 batch, you have the latest code and can skip to the next chapter.

Note: Warning messages may appear during the compilation of the batch. These warnings can be ignored if the batch executables are successfully generated.

Create Staging Directory for ORFM Batch Patch Files

To create a staging directory for RMS batch patch files, complete the following steps.

1. Log into the database server as a user that can connect to the RMS database.
2. Create a staging directory for the ORFM 13.2.3 Batch Patch. There should be a minimum of 5 MB disk space available in this location.
3. Copy the `orfm1323batchpatch.zip` file from the ORFM 13.2.3 release to the staging directory. This is referred to as `ORFM_BATCH_PATCH_DIR` when patching a database schema.
4. Change directories to `ORFM_BATCH_PATCH_DIR` and extract the `orfm1323batchpatch.zip` file. This creates a `batch-patch` subdirectory under `ORFM_BATCH_PATCH_DIR`.

Set Environment Variables

Note: `INSTALL_DIR` is the location where RMS 13 batch was installed.

To set environment variables, make sure the following variables are set. The RMS 13.2 batch installer should have created a `batch.profile` file located at `INSTALL_DIR/batch.profile`. This profile script can be used to set all environment variables listed below.

Example: `cd <INSTALL_DIR>`
`./batch.profile`

Variables set by `batch.profile`:

- `PATH` must include `make`, `makedepend` and the C compiler
- `MMHOME=INSTALL_DIR/rms`
- `MMUSER=RMS Schema Owner`
- `ORACLE_HOME=Location of Oracle install`
- `ORACLE_SID=The Oracle Sid for the RMS database`
- `UP=/@< Schema Owner Wallet Alias >`
- `TNS_ADMIN=/path/to/wallet/files/dir/`

AIX:

- LIBPATH=\$ORACLE_HOME/lib:\$MMHOME/oracle/lib/bin:\$LDPATH
- OBJECT_MODE=64
- LINK_CNTRL=L_PTHREADS_D7

HP:

- SHLIB_PATH=\$ORACLE_HOME/lib:\$MMHOME/oracle/lib/bin:\$SHLIB_PATH

Solaris:

- LD_LIBRARY_PATH=\$ORACLE_HOME/lib:\$MMHOME/oracle/lib/bin:\$LD_LIBRARY_PATH

Note: For environments running Solaris and Oracle RDBMS 11.2.0.2, ensure Sun Studio 12 compiler is in the path.

Example: export
PATH=/vol.rtk/compilers/sunstudio12.1/bin:/usr/xpg4/bin:\$PATH

Linux:

- LD_LIBRARY_PATH=\$ORACLE_HOME/lib:\$MMHOME/oracle/lib/bin:\$LD_LIBRARY_PATH

Note: See [Appendix: Setting Up Password Stores with Oracle Wallet](#)

Compile Batch Libraries

To compile batch libraries, complete the following steps.

Note: Verify that TNS is set up correctly by using the UP variable to successfully log in to the RMS 13 schema. For example, /u00/oracle> sqlplus \$UP.

1. Copy the files from ORFM_BATCH_PATCH_DIR/batch-patch/<version>/oracle/lib/src to INSTALL_DIR/oracle/lib/src. This step should be done with each version you want to apply in order of earliest to latest patch starting at 13.2.0 and ending with the 13.2.3 deltas.
2. Change directories to INSTALL_DIR/oracle/lib/src.
3. To make library dependencies run this command.
make -f l10n_rmslib.mk depend 2>&1 | tee libdpnd.log
Check the libdpnd.log file for errors.
4. To make batch libraries:
make -f l10n_rmslib.mk 2>&1 | tee libretek.log
Check the libretek.log file for errors.
5. To install batch libraries:
make -f l10n_rmslib.mk install
The batch libraries should now be in INSTALL_DIR/oracle/lib/bin.

Compile Batch Source Code

To compile batch source code complete the following steps.

1. Copy the files from `ORFM_BATCH_PATCH_DIR/batch-patch/<version>/oracle/proc/src` to `INSTALL_DIR/oracle/proc/src`. This step should be done with each version you want to apply in order of earliest to latest patch starting at 13.2.0 and ending with the 13.2.3 deltas.
2. Change directories to `INSTALL_DIR/oracle/proc/src`.
3. Create dependencies.
 - a. Run the following command:

```
make -f l10n_rms.mk depend 2>&1 | tee srcdpnd.log
```
 - b. Check the `srcdpnd.log` file for errors.
4. Create batch programs.
 - a. Run the following command:

```
make -f l10n_rms.mk 2>&1 | tee srcall.log
```
 - b. Check the `srcall.log` file for errors.
5. Install the batch programs.

```
make -f l10n_rms.mk install
```

The ORFM batch programs should now be in `INSTALL_DIR/oracle/proc/bin`.

Copy Data Conversion Scripts

Copy the files from `ORFM_BATCH_PATCH_DIR/batch-patch/<version>/external` to `INSTALL_DIR/external`. This step should be done with each version you want to apply in order of earliest to latest patch starting at 13.2.0 and ending with the 13.2.2 deltas.

Application Installation Tasks—Patch


There are two different methods to use for installing the ORFM 13.2.3 Application patch. Option 1 uses the RMS installer to apply the patch. Option 2 compiles the ORFM toolset and forms directly.

Note: If the 13.2.3 database schema patch has been run, the entire set of toolsets and forms must be recompiled.

Create RMS Help Managed Server


Note: If rms help managed server is already installed, please skip this section.

1. Log in to the admin console.




2. Click Lock & Edit.

3. Navigate to Environment > Servers and select new tab of the servers on the right side.




4. Set the following variables:
 - **Server Name:** These should be some name specific to your application targeted (for example, rms-help-server).
 - **Server Listen Address:** <weblogic server> (for example, redevlv0065.us.oracle.com)
 - **Server Listen Port:** A free port; check for availability.
A suggestion is to increment the AdminServer port by two and keep incrementing by two for each managed server (for example, 17003, 17005, 17007, and so on).

5. Click Next.



6. Click **Finish**.




7. Click **Activate Changes** on the left side.

Install Node Manager


Install Node Manager if it was not created during domain install. Node Manager is required so that the managed servers can be started and stopped through the admin console. Only one node manager is needed per WebLogic installation.

1. Log in to the admin console.
2. Click **Lock & Edit** button and navigate to Environments > Machines.
3. Click **New**.



4. Set the following variables:
 - **Name:** Logical machine name
 - **Machine OS:** UNIX
5. Click **OK**.

6. Click on the machine created.



7. Click the Node Manager tab and update the details below.
 - **Type:** Plain
 - **Listen Address:** Machine IP (for example, redevlv0065.us.oracle.com)
 - **Listen Port:** Node manager will be assigned a default port (for example, 5556)

The screenshot shows the WLS Console interface for configuring the Node Manager for a machine named 'redevlv0065'. The browser address bar shows the URL: `http://redevlv0065.us.oracle.com:7001/console/console.portal?_nfpb=true&_pageLabel=CoreMachineMad`. The page title is 'Settings for redevlv0065 - ClassicDomain - WLS Console'. The breadcrumb navigation is: Home > Summary of Servers > Summary of Deployments > Summary of Servers > Summary of Machines > Summary of Servers > Summary of Machines > redevlv0065.

On the left side, there is a 'Domain Structure' tree showing the hierarchy: ClassicDomain > Environment > Servers > Clusters > Virtual Hosts > Migratable Targets > Machines > Work Managers > Startup & Shutdown Classes > Deployments > Services > Security Realms > Interoperability > Diagnostics. Below this are sections for 'How do I...' (with links for 'Create and configure machines', 'Monitor Node Manager status', and 'Monitor Node Manager logs') and 'System Status' (showing 'Health of Running Servers' with counts for Failed (0), Critical (0), and Overloaded (0)).


The main content area is titled 'Settings for redevlv0065' and has three tabs: 'Configuration', 'Monitoring', and 'Notes'. The 'Configuration' tab is active and has three sub-tabs: 'General', 'Node Manager', and 'Servers'. The 'Node Manager' sub-tab is selected. A 'Save' button is visible at the top left of the configuration area.

Below the 'Save' button, there is explanatory text: 'This page allows you to define the Node Manager configuration for this machine. To control a Managed Server from the console, Node Manager must be configured and running on the machine where the Managed Servers are installed. The settings defined on this page are used to configure communication between the current domain and Node Manager instances that control Managed Servers. This page does not control the configuration of the Node Manager instances.'

The configuration fields are as follows:

- Type:** A dropdown menu set to 'Plain'. Description: 'Returns the node manager type. [More Info...](#)'
- Listen Address:** A text input field containing 'redevlv0065.us.oracle.com'. Description: 'The host name or IP address where Node Manager listens for connection requests. [More Info...](#)'
- Listen Port:** A text input field containing '5556'. Description: 'The port number where Node Manager listens for connection requests. [More Info...](#)'
- Node Manager Home:** An empty text input field. Description: 'Returns the nodemanager home directory that will be used to substitute for the shell command template. [More Info...](#)'
- Shell Command:** An empty text input field. Description: 'Returns the local command line to use when invoking SSH or BSH node manager functions. [More Info...](#)'
- Debug Enabled:** An unchecked checkbox. Description: 'Specifies whether communication with this Node Manager needs to be debugged. When enabled, Node Manager provides more information about request processing. This information is sent to the log of the managed server.' (partially visible)

8. Click Save.



9. Click Activate Changes.

10. Click Lock & Edit.

11. Navigate to Environments->machines->click on the machine name and select the Servers tab.

The screenshot shows the Oracle WebLogic Server Administration Console interface. The browser address bar indicates the URL: `http://redevlv0065.us.oracle.com:7001/console/console.portal?_nfpb=true&_pageLabel=CoreMachineCont`. The page title is "Settings for redevlv0065 - ClassicDomain - WLS Console".


The main content area is titled "Settings for redevlv0065" and has tabs for "Configuration", "Monitoring", and "Notes". The "Servers" sub-tab is selected. Below the tabs, there is a message: "This page displays the servers that have been assigned to this Machine. You can select a server to configure from the list of available servers."

Below the message is a section titled "Customize this table" and "Servers (Filtered - More Columns Exist)". There are "Add" and "Remove" buttons above the table. The table shows 5 servers:

<input type="checkbox"/>	Name	Cluster	Machine	State	Health	Listen Port
<input type="checkbox"/>	AdminServer(admin)		redevlv0065	RUNNING	OK	7001
<input type="checkbox"/>	help-server		redevlv0065	RUNNING	OK	9003
<input type="checkbox"/>	publisher-ms		redevlv0065	RUNNING	OK	9004
<input type="checkbox"/>	WLS_FORMS	cluster_forms	redevlv0065	RUNNING	OK	9001
<input type="checkbox"/>	WLS_REPORTS	cluster_reports	redevlv0065	RUNNING	OK	9002

At the bottom of the table, there are "Add" and "Remove" buttons and a pagination indicator: "Showing 1 to 5 of 5 Previous | Next".

12. Click Add. Add the managed servers that need to be configured with NodeManager.



13. Set the following variables:
 - Server: name of server previously created (for example, rms-help-server)
14. Click **Next**. Click **Finish**.
15. Click **Activate Changes**.

Note: To activate changes the server must be stopped if it is running:

```
$WLS_HOME/user_projects/domains/<domain-name>/bin/stopManagedWebLogic.sh <rms-help-server>
${server_name}:${server_port}
```

Go to each managed server that is being added to the machine and click the Server Start tab. In the Class Path box, add the following:

```
<full-path-to-domain>/servers/<managed-server>
```

For example:

```
/u00/webadmin/product/10.3.3/WLS/user_projects/domains/ClassicDomain/servers/rms-help-server
```

16. After the CLASSPATH changes are finished, click **Save**.
17. Click **Activate Changes**.
18. Start the Nodemanager from the server using the startNodeManager.sh at \$WLS_HOME/wlserver_10.3/server/bin.

19. Update nodemanager.properties file at the following location and set the SecureListener variable to false.
\$WLS_HOME/wlserver_10.3/common/nodemanager/nodemanager.properties
SecureListener=false
20. The NodeManager must be restarted after making changes to the nodemanager.properties file.

Note: The nodemanager.properties file is created after NodeManager is started for the first time. It is not available before that point.

Option 1: Use RMS Application Installer to Patch

Note: If using the RMS Application Installer to apply the ORFM 13.2.3 patch, the RMS 13.2.3 and ORFM 13.2.3 Application patches should be applied at the same time. This section provides instructions on how to do this.

As shipped, the RMS 13.2 Forms installer installs and compiles the forms for version 13.2. Patches for ORFM Forms may be applied by copying the new source files and recompiling in place in the environment using the profile scripts created by the installer. This is the method to use if there is already an environment at the previous patch level. Go to the section “Option 2: Compile ORFM Toolset and Forms Directly” for these instructions.

The installer method is only intended for new environments. Do not use the installer patching utility to attempt patching of forms in existing environments with the installer. If the patch is applied to customizations, they will be overwritten.

In this section, STAGING_DIR refers to the location where the RMS 13.2 application installer was originally expanded. A new directory should be created with a fresh copy of the RMS 13.2 application installer.

Before you apply the RMS and ORFM 13.2.3 patch:

- Make a backup of all your forms and library files.
- Review the enclosed 13.2.3 Patch Release Notes (rms-1323-rn.pdf).

Before copying over any files:

- Note whether customizations have been made to the module. If so, then the customizations must be reapplied over the new version of the file (or the fix may need to be applied to the custom version of the code).
- Copy the original files to a different directory before copying over them in case they need to be referred to at a later date.

Create Staging Directory for RMS and ORFM Application Patch Files

To create a staging directory for RMS and ORFM application patch files, complete the following steps.

1. Log on to your application server as a user with read and write access to the Weblogic files.
2. Create a staging directory for the RMS Application patch. There should be a minimum of 530 MB disk space available in this location.

3. Copy the file `rms1323apppatch.zip` from the RMS 13.2.3 release to staging directory. This will be referred to as `RMS_APP_PATCH_DIR` when installing application software and reports.
4. Change directories to `RMS_APP_PATCH_DIR` and extract the file `rms1323apppatch.zip`. This creates an `app-patch` subdirectory under `RMS_APP_PATCH_DIR`.
5. Create a staging directory for the ORFM 13.2.3 Application Patch. There should be a minimum of 140 MB disk space available in this location. This should be a different directory than `RMS_APP_PATCH_DIR`.
6. Copy the `orfm1323apppatch.zip` file from the ORFM 13.2.3 release to the staging directory. This is referred to as `ORFM_APP_PATCH_DIR` when patching a database schema.
7. Change directories to `ORFM_APP_PATCH_DIR` and extract the **`orfm1323apppatch.zip`** file. This creates an `app-patch` subdirectory under `ORFM_APP_PATCH_DIR`.
8. If you do not already have one, create a staging directory for the RMS application installation software or use the same staging directory as created in the database schema step above. There should be a minimum of 600 MB disk space available in this location.
9. Copy the file `rms13appserver.zip` from the RMS 13.2 release to staging directory. This will be referred to as `STAGING_DIR` when installing application software and reports.
10. Change directories to `STAGING_DIR` and extract the file `rms13appserver.zip`. This will create an `rms/application` subdirectory under `STAGING_DIR`.

Copy Forms and Library Patch Files

For new environments, the installer can be used to install and compile the forms at the latest patch level using the installer patching utility included with RMS and ORFM Forms patches. The utility is located under `RMS_APP_PATCH_DIR/app-patch/patch-util` and `ORFM_APP_PATCH_DIR/app-patch/patch-util`. This utility will accept as input the RMS and ORFM patch files and add them to the RMS 13.2 Forms installer package. After running this utility, the RMS Forms installer can be used to install the environment, and they will install the latest version of each batch module.

Custom Modules

Custom source can be provided by the user in a folder named `RMS_APP_PATCH_DIR/app-patch/patch-util/custom` and `ORFM_APP_PATCH_DIR/app-patch/patch-util/custom`. The source code in this folder is applied last, after all patches have been applied.

Run the Installer Patching Utility

To run the installer patching utility, complete the following steps.

1. Set the `JAVA_HOME` environment variable to point to a JDK.
2. Set the `ANT_HOME` environment variable to point to an Ant installation. There is one included with the RMS installer that can be used for this.

```
ANT_HOME=<INSTALL_DIR>/rms/application/ant
export ANT_HOME
```
3. Change directories to `RMS_APP_PATCH_DIR/app-patch/patch-util/`

4. Modify the patch.properties file. Set the staging.dir and patch.to.version properties.

Property Name	Description
staging.dir	The directory where the installer files are located under STAGING_DIR. Example: /opt/rms/application
patch.to.version	The version want to patch to Example: 13.2.3

5. Run the patch.sh script. This script will copy the files from each patch from 13.2.3 up to the patch specified in the **patch.to.version** property. These files are copied into the installer package.
6. Change directories to ORFM_APP_PATCH_DIR/app-patch/patch-util/
7. Modify the patch.properties file.

Property Name	Description
installer.dir	The directory where the RMS installer files are located under STAGING_DIR. Example: /opt/rms/application
patch.to.version	The version want to patch to Example: 13.2.3

Set the staging.dir and patch.to.version properties. Run the patch.sh script. This script will copy the ORFM files from each patch from 13.2.0 up to the patch specified in the **patch.to.version** property. These files are copied into the RMS installer package.

Run the RMS Application Installer

To run the RMS application installer, complete the following steps.

Note: See [Appendix: RMS Application Installer Screens](#) for details on every screen and field in the application installer.

Note: It is necessary to have \$ORACLE_HOME/network/admin/tnsnames.ora file configured in this WLS installation. Forms will use this information for connectivity.

A copy tnsnames.ora file must be created for the \$ORACLE_INSTANCE/config location. If the file is not copied to this location, forms will not compile correctly.

Note: ORACLE_HOME is the location where Oracle Forms 11gR1 has been installed.

ORACLE_INSTANCE is the instance that is created during configuration of Oracle forms 11gR1 and contains the executables to compile

1. Log on to your application server as a user with read and write access to the Weblogic files.

2. Change directories to STAGING_DIR/rms/application. This directory was created when the rms13application.zip file was expanded under STAGING_DIR.
3. Set and export the following environment variables.

Variable	Description	Example
DOMAIN_HOME	The location where Forms 11.1.1.3 domain has been installed.	DOMAIN_HOME= /u00/webadmin/product/10.3.3/WLS_Forms/user_projects/domains/ClassicDomain/ export DOMAIN_HOME
WLS_INSTANCE	The name of the managed server that contains Oracle Forms.	WLS_INSTANCE=WLS_FORMS Export WLS_INSTANCE
ORACLE_SID	The database/SID where the RMS schema resides.	ORACLE_SID=mydb
NLS_LANG	Locale setting for Oracle database client.	NLS_LANG=AMERICAN_AMERICA.UTF8 export NLS_LANG
JAVA_HOME	Location of a Java 6.0 (1.6.0) JDK.	JAVA_HOME= /u00/webadmin/java/jdk1.6.0_12 Export JAVA_HOME
DISPLAY	Address and port of X server on desktop system of user running install. Required for forms application installer.	DISPLAY=<IP address>:0 export DISPLAY

4. To install the RMS application you need to be using an X server such as Exceed and have set the DISPLAY environment variable. The installer does not continue otherwise.
5. Run the install.sh script to start the installer.

Note: Below are the usage details for install.sh. The typical usage for GUI mode is no arguments.

```
./install.sh [text | silent]
```

6. The Installer automatically sets additional environment variables based on the values of the environment variables set in step 3. At the end of the preinstall checks it will print out a summary containing these new environment variables:

Example:

```
MW_HOME=/u00/webadmin/product/10.3.3/WLS_Forms
ORACLE_HOME=/u00/webadmin/product/10.3.3/WLS_Forms/as_1
ORACLE_INSTANCE=/u00/webadmin/product/10.3.3/WLS_Forms/asinst_1
DOMAIN_HOME=/u00/webadmin/product/10.3.3/WLS_Forms/user_projects/domains/ClassicDomain
WLS_INSTANCE=WLS_FORMS
```

```
ORACLE_SID=mydb
```

```
JAVA_HOME=/u00/webadmin/java/jdk1.6.0_12
```

Verify that these environment variables are correct. If any of them are incorrect, you need to verify that the Weblogic shell scripts that set them are configured properly. Check the following scripts:

```
$DOMAIN_HOME/bin/setDomainEnv.sh
$WEBLOGIC_HOME/wlserver_10.3/common/bin/commEnv.sh
```

Example:

```
/u00/webadmin/product/10.3.3/WLS_Forms/user_
projects/domains/ClassicDomain/bin/setDomainEnv.sh

/u00/webadmin/product/10.3.3/WLS_Forms/wlserver_
10.3/common/bin/commEnv.sh
```

Depending on system resources, a typical installation takes anywhere from 45 minutes to two hours.

The installer asks for an installation directory. This is the destination directory for the RMS files. This directory will be referred to as `INSTALL_DIR` for the remainder of this chapter. Do not provide an `INSTALL_DIR` that is located at or underneath `STAGING_DIR`.

Note: You may see the following warning repeated during installation:

```
[exec] Warning! One or more of your selected
locales are not available.
[exec] Please invoke the commands "locale" and
"locale -a" to verify your
[exec] selections and the available locales.
[exec]
[exec] Continuing processing using the "C" locale.
```

Or

```
[exec] couldn't set locale correctly
```

This warning can be ignored.

7. After the installation is complete, you can check its log file: `INSTALL_DIR/base/log/rms.app.install.<timestamp>.log`. The `INSTALL_DIR/base/error` will contain information about possible failed compilations.
8. The installer leaves behind the `ant.install.properties` file for future reference and repeat installations. This file contains inputs you provided. As a security precaution, make sure that the file has restrictive permissions.

Example: `chmod 600 ant.install.properties`

Note: The object counts performed by the installer may be off due to the patch adding or removing modules. The installer warnings about this can be ignored

9. If during the screens you chose not to have the installer automatically configure WebLogic, after the installation is complete follow the post installation tasks by making backups of the listed files and copying the required files to the specified location.

Example:

```
#####
##                      WebLogic Configuration Tasks                      ##
#####
Contact your WebLogic administrator and have them make backups of the following
files:

/u00/webadmin/product/10.3.3/WLS_Forms/user_projects/domains/ClassicDomain/config/
fmwconfig/servers/WLS_FORMS/applications/formsapp_11.1.1/config/forms/registry/ora
cle/forms/registry/Registry.dat
/u00/webadmin/product/10.3.3/WLS_Forms/user_projects/domains/ClassicDomain/config/
fmwconfig/servers/WLS_FORMS/applications/formsapp_11.1.1/config/formsweb.cfg

Have the WebLogic administrator stop WLS_FORMS and ohs1,
copy everything in /home/oretail/rms132/install/post
to /u00/webadmin/product/10.3.3/WLS_Forms to update the files
and then start WLS_FORMS and ohs1
for the changes to take effect.

example: cp -R * /u00/webadmin/product/10.3.3/WLS_Forms
```

Delete Obsolete Files

The following forms and menus are obsolete as of 13.2.2 and should be deleted from INSTALL_DIR.

```
INSTALL_DIR/base/forms/src/company.mmb
INSTALL_DIR/base/forms/src/ribapierr.fmb
INSTALL_DIR/base/forms/src/freclass.fmb
INSTALL_DIR/base/forms/src/l10ncnae.fmb
INSTALL_DIR/base/forms/src/tribsubs.fmb
INSTALL_DIR/base/forms/src/vfreclass.fmb
INSTALL_DIR/base/forms/bin/company.mmx
INSTALL_DIR/base/forms/bin/ribapierr.fmx
INSTALL_DIR/base/forms/bin/freclass.fmx
INSTALL_DIR/base/forms/bin/l10ncnae.fmx
INSTALL_DIR/base/forms/bin/tribsubs.fmx
INSTALL_DIR/base/forms/bin/vfreclass.fmx
```

Resolving Errors Encountered During Application Installation

In the event a form or menu does not compile, go to `INSTALL_DIR/base/error` and see which objects didn't compile. To try and manually recompile the object run `INSTALL_DIR/base/forms.profile` and run the following command:

```
# frmcmp.sh userid=$SUP module_type=form module=FORM_OR_MENU
```

You can also safely rerun the installer to see if the form compiles.

Note: If you rerun the installer, and choose to check the box **Configure WebLogic** in the installer screens, you may need to clean up duplicate entries in the WebLogic `formsweb.cfg` file.

Clustered Installations – Post-Installation Steps

If you are installing the RMS application to a clustered Oracle Application Server environment, there are some extra steps you need to take to complete the installation. In these instructions, the application server node with the `ORACLE_HOME` you used for the RMS application installer is referred to as *master node*. All other nodes are referred to as *remote nodes*.

To complete the RMS forms application install, the installer provided new versions of `formsweb.cfg` and the newly-created env files for the new RMS installation. The env files should be copied from the master node to the remote node(s). The entries added to `formsweb.cfg` for these new environments should be copied from the master node to the remote nodes.

Note: Do not copy the entire `formsweb.cfg` file from one node to another. Only copy the RMS entries appended to this file by the installer. There is node-specific information in this file that is different between `ORACLE_HOME` installations.

Oracle Configuration Manager

The Oracle Retail OCM Installer packaged with this release installs the latest version of OCM.

The following document is available through My Oracle Support (formerly MetaLink). Access My Oracle Support at the following URL:

<https://support.oracle.com>

Oracle Configuration Manager Installer Guide (Doc ID: 1071030.1)

This guide describes the procedures and interface of the Oracle Retail Oracle Configuration Manager Installer that a retailer runs at the beginning of the installation process.

OCM Documentation Link

<http://www.oracle.com/technology/documentation/ocm.html>

RMS Reports Copied by the Application Installer

The application installer copies RMS report files to `INSTALL_DIR/base/reports`. These files should be installed into BI Publisher as documented in the RMS Reports chapter of this document.

Test the RMS Application

Oracle Retail provides test cases that allow you to smoke test your installation. Refer to My Oracle Support document, *Oracle Retail Merchandising Installation Test Cases* (ID 1277131.1.1).

Option 2: Compile ORFM Toolset and Forms Directly

Option 2 entails compiling ORFM forms directly, as described below.

Create Staging Directory for ORFM Application Files

To create a staging directory for ORFM application files, complete the following steps.

1. Log into the application server as a user with read and write access to the WebLogic files.
2. Create a staging directory for the ORFM application installation software. There should be a minimum of 140 MB disk space available in this location.
3. Copy the file `orfm1323apppatch.zip` from the ORFM 13.2.3 release to staging directory. This is referred to as `ORFM_APP_PATCH_DIR` when installing application software and reports.
4. Change directories to `ORFM_APP_PATCH_DIR` and extract the file `orfm1323apppatch.zip`.

Set Environment Variables

To set environment variables, complete the following steps.

Note:

`INSTALL_DIR` is the location where RMS 13 forms were installed.

`ORACLE_HOME` is the location where Oracle WebLogic (10.3.3) has been installed.

`ORACLE_INSTANCE` is the location where WebLogic has been installed and contains the executables to compile forms.

Make sure the following variables are set. The RMS 13.2 forms installer should have created a `forms.profile` file located at `INSTALL_DIR/base/forms.profile`. This profile script can be used to set all environment variables listed below.

Example: `cd <INSTALL_DIR>/base`
`./forms.profile`

Variables set by `forms.profile` are as follows.

- **All OS Platforms**
 - `MMHOME=INSTALL_DIR/base`
 - `ORACLE_HOME=/path/to/WebLogic/as_1`
 - `ORACLE_INSTANCE=/path/to/WebLogic/asinst_1`
 - `ORACLE_SID= The Oracle Sid for the RMS database`
 - `UP=/@< Schema Owner Wallet Alias >`
 - `TNS_ADMIN=/path/to/wallet/files/dir/`
 - `NLS_LANG=AMERICAN_AMERICA.UTF8`
 - `DISPLAY=<IP address of X server>:0.0`

- PATH=\$ORACLE_HOME/bin:\$ORACLE_HOME/opmn/bin:\$ORACLE_HOME/dcm/bin:INSTALL_DIR/base/forms_scripts:\$PATH
- CLASSPATH=\$ORACLE_HOME/jlib/importer:\$ORACLE_HOME/jlib/debugger.jar:\$ORACLE_HOME/jlib/utj.jar:\$ORACLE_HOME/jlib/ewt3.jar:\$ORACLE_HOME/jlib/share.jar:\$ORACLE_HOME/jlib/dfc.jar:\$ORACLE_HOME/jlib/help4.jar:\$ORACLE_HOME/jlib/oracle_ice.jar:\$ORACLE_HOME/jlib/jewt4.jar
- FORMS_BUILDER_CLASSPATH=\$CLASSPATH
- FORMS_PATH=INSTALL_DIR/base/toolset/bin:INSTALL_DIR/rms/forms/bin:\$ORACLE_HOME/forms
- TK_UNKNOWN=\$ORACLE_INSTANCE/config/FRComponent/frcommon/guicommon/tk/admin
- PATH=\$ORACLE_INSTANCE/bin:\$PATH

Note: See Appendix M: Setting Up Password Stores with Oracle Wallet in this document.

Note: Verify that TNS is set up correctly by using the UP variable to successfully log in to the RMS 13 schema.

Example: /u00/oracle> sqlplus \$UP

- **AIX**
 - LD_LIBRARY_PATH=\$ORACLE_HOME/lib:\$ORACLE_HOME/lib32:\$ORACLE_HOME/jdk/jre/lib
 - LIBPATH=\$LD_LIBRARY_PATH
- **Linux**
 - LD_LIBRARY_PATH=\$ORACLE_HOME/lib:\$ORACLE_HOME/lib32:\$ORACLE_HOME/jdk/jre/lib

Delete Obsolete Files

The following forms and menus are obsolete as of 13.2.2 and should be deleted from INSTALL_DIR.

```
INSTALL_DIR/base/forms/src/company.mmb
INSTALL_DIR/base/forms/src/ribapierr.fmb
INSTALL_DIR/base/forms/src/freclass.fmb
INSTALL_DIR/base/forms/src/l10ncnae.fmb
INSTALL_DIR/base/forms/src/tribsubs.fmb
INSTALL_DIR/base/forms/src/vfreclass.fmb
INSTALL_DIR/base/forms/bin/company.mmx
INSTALL_DIR/base/forms/bin/ribapierr.fmx
INSTALL_DIR/base/forms/bin/freclass.fmx
INSTALL_DIR/base/forms/bin/l10ncnae.fmx
INSTALL_DIR/base/forms/bin/tribsubs.fmx
INSTALL_DIR/base/forms/bin/vfreclass.fmx
```

ORFM Forms Installation

Instructions for ORFM forms installation are as follows.

1. Copy the files from `ORFM_APP_PATCH_DIR/app-patch /<version>/base/forms/src` to `INSTALL_DIR/base/forms/src`. This step should be done with each version you want to apply in order of earliest to latest patch starting at 13.2.0 and ending with the 13.2.3 deltas.
2. Copy all libraries (.pll files) in the `INSTALL_DIR/base/forms/src` directory to the directories to the `INSTALL_DIR/base/forms/bin` directory.
3. Change directories to `INSTALL_DIR/base/forms/bin`.
4. Run `forms.pll.sh` to compile all RMS .pll's.
5. Copy all forms (*.fmb files) in the `INSTALL_DIR/base/forms/src` directory to the `INSTALL_DIR/base/forms/bin` directory.
6. Run `forms.fm_fmb.sh` (in `INSTALL_DIR/base/rms/forms/bin`) to compile the RMS reference forms.
7. Run `forms.fmb.sh` (in `INSTALL_DIR/base/rms/forms/bin`) to generate RMS runtime forms – .fmx's.
8. Check to make sure that each non-reference form .fmb file has a corresponding .fmx file.
9. Copy all menus (*.mmb files) in the `INSTALL_DIR/base/forms/src` directory to the `INSTALL_DIR/base/forms/bin` directory.
10. Run `menus.mmb.sh` (in `INSTALL_DIR/base/rms/forms/bin`) to generate RMS runtime menus – .mmx's.

Note: .err files may be created by the compilation scripts above. These files are logs of the compilation process and can be removed.

Install the Online Help

To install the online help, complete the following steps.

Note: You can skip this section if you have already installed the helpfile included with RMS 13.2.2.

1. Log into the WebLogic instance to which online help will be installed.
2. Create a server if necessary. In this example, rms-help-server is being used.
3. Select **Deployments**.
4. If there is an existing “rms-help” deployment, it must be stopped and deleted. Check the box next to “rms-help” and click **Stop->Force Stop Now**. Click **Yes** on the next screen. Check the box next to “rms-help” and click **Delete**. On the next screen, click **Yes**. When finished deleting, bounce the rms-help-server.
5. Select **Deployments**.
6. Click **Install**.
7. Click in the **Path:** box and enter ORFM_APP_PATCH_DIR/app-patch/13.2.3/online-help/rms-help.ear, the ear file that will be deployed.
8. Leave **Install this deployment as an application** selected. Click **Next**.
9. Select the rms-help-server created in Step 2. Click **Next**.
10. Leave rms-help for the application name. Click **Next**.
11. Verify settings. Click **Finish**.
12. Select **Deployments**.
13. Check the box next to rms-help and click **Start -> Servicing all Requests**
14. Click **Yes**
15. In the database, set the WEBHELP_SERVER column in the LANG table for the RMS schema owner to point to the RMS help server and port. For example, set it to `http://redevlv0065.us.oracle.com:17003`.

Reports Installation Tasks—Patch

ORFM Reports are included in the ORFM Application patch: orfm1322apppatch.zip in the reports directories.

Note: There are no ORFM reports added for the 13.2.3 release. If you have already installed the ORFM 13.2.2 reports, you have the latest code and can skip to the next chapter.

Manually Copy Reports to Install Directory

If you followed “[Option 1: Use RMS Application Installer to Patch](#)” in the chapter, [Application Installation Tasks—Patch](#),” you can skip to the next section (“Installing the RMS/ORFM BI Publisher Templates.”) If you followed “[Option 2: Compile ORFM Toolset and Forms Directly](#),” you must manually copy the reports to `INSTALL_DIR`. Copy the reports from the ORFM application patch `ORFM_APP_PATCH_DIR/app-patch/<version>/reports` to the reports directory created during RMS installation, `INSTALL_DIR/base/reports`. This step should be done with each version you want to apply in order of earliest to latest patch starting at 13.2.0 and ending with the 13.2.3 deltas.

Note: If BIPublisher application is already deployed to a bipublisher managed server in Weblogic, you can directly go to “Installing the RMS BIPublisher Templates” section. If not, please follow the below instructions.

BI Server Component Installation Tasks

Oracle BI Publisher is used as the main RMS and RWMS reporting engine and can be used in conjunction with external printing solutions like label printing. This section describes the installation of Oracle BI Publisher as a server application within WebLogic 10.3.3. One deployment of BI Publisher can be used for both the RMS and RWMS reports.

If you are installing BI Publisher as a part the Oracle BI EE suite, please refer to the appropriate Fusion Middleware guides for the installation of the product in a WebLogic server environment. Otherwise, you must perform the steps described in this section to deploy Oracle BI Publisher as a standalone web application into a WebLogic server environment.

Installation Process Overview

Installing the BI Publisher server as a standalone web application in a WebLogic server involves the following tasks:

1. Locate the correct and generic version of `xmlpserver.war` from the BI Publisher source media.
2. Create an exploded directory from the `xmlpserver.war` file where the BI server installation will reside on the WebLogic server.
3. Deploy BI Publisher into the WebLogic application server instance.
4. Configure the BI Publisher repository.

- Optionally, install additional fonts into the JRE of the WebLogic server's JDK if you are planning to develop reports that are directly rendered by BI Publisher.

The following post-installation tasks are involved once BI Publisher has been installed:

- Set up the RMS BI Publisher Report Templates produced for RMS.
- Create the BI Publisher scheduler schema on the database server (required to send and schedule reports).
- Set up for the RMS application specific configuration files to integrate BI Publisher.

Extracting the BI Server Web Archive from the Source Media

The BI Server components must be extracted from the source installation media. If you have downloaded the source distribution of Oracle BI EE, you must locate the BI Publisher source directory from the media.

The BI Publisher install media contains the following:

- BI Publisher server application
- BI Publisher runtime libraries
- BI Publisher fonts
- BI Publisher desktop tools
- Documentation: User's Guide, "Javadocs," demos, and samples

Individual components are located in the directory structure as follows:

Directory	Component
<BI_MEDIA>/fonts	Font files.
<BI_MEDIA>/generic	xmlpserver.war (for non-oc4j application servers) xmlpserver.ear (for non-oc4j application servers)
<BI_MEDIA>/oc4j	xmlpserver.ear (for oc4j).
<BI_MEDIA>/XMLP	XMLP repository.
<BI_MEDIA>/XMLP/DemoFiles	Data source for demo reports.
<BI_MEDIA>/XMLP/Tools	Template Builder for Word Add-in.

Complete the following steps.

- Create the <BI_DEPLOYMENT> directory on the server and change directory into this directory.

Example assuming that /u00/webadmin is the root of the installation:

```
mkdir /u00/webadmin/RMS_BIP
cd /u00/webadmin/RMS_BIP
```

- Locate the manual/generic/xmlpserver.war file from this directory structure and copy it to the <BI_DEPLOYMENT> directory on the server using a copy command with the following syntax:

- `cp <BI_MEDIA>/manual/generic/xmlpserver.war <BI_DEPLOYMENT>`

For example,

```
cp /tmp/BIPublisherSource/manual/xmlpserver.war /u00/webadmin/RMS_BIP
```

Creating an Exploded Directory for the Installation

You need to create an exploded archive directory from this `xmlpserver.war` file. This will be the directory from which WebLogic will run the BI Server.

Note: Do not deploy the `xmlpserver.war` or `xmlpserver.ear` file on the WebLogic Server by uploading it from the WebLogic console, because the console deploys the application (or Web module) in an archived file format.

This is not recommended for BI Publisher configuration, because you must update `WEB-INF/xmlp-server-config.xml` manually before the deployment. To work around this issue, use an "exploded archive" directory.

Complete this task by following these steps:

1. Change directory to `<BI_DEPLOYMENT>` on the server.

Example assuming that `/u00/webadmin` is the root of the installation:

```
cd /u00/webadmin/RMS_BIP
```

2. By running the `jar` command with `-x` for extraction with the file `xmlpserver.jar`, create an exploded directory called "xmlpserver" within `<BI_DEPLOYMENT>`. This is the location where the application will be deployed in the WebLogic server.

For example,

```
mkdir xmlpserver
cd xmlpserver
jar -xvf /u00/webadmin/RMS_BIP/xmlpserver/xmlpserver.war
```

You should now have an exploded directory structure with `<BI_DEPLOYMENT>/xmlpserver/` for the deployment.

Note: Any changes to the BI Publisher configuration files, such as to update the catalog path in the `xmlp-server-config.xml` file, must be done before deployment. For more information on catalogs, refer to the BI Publisher Documentation.

3. Delete the war file.

For example,

```
rm /u00/webadmin/RMS_BIP/xmlpserver/xmlpserver.war
```

Configuring the BI Publisher Repository and Installing Fonts

Before deploying BI Publisher in your WebLogic server, you must set up the BI Publisher repository and install the font files into the JVM used by the server.

To set up the repository, copy the `<BI_MEDIA>/XMLP` directory to `<BI_REPOSITORY>`.

For example,

```
cp -R /tmp/BIPublisherSource/XMLP /u00/webadmin/RMS_BIP/xmlpserver
```

1. Assign appropriate permissions for the WebLogic server instance user to have read, write and execute permissions to enable the deployment of this directory structure to serve as a web application.
2. Open the `xmlp-server-config.xml` file located in `BI_HOME_DIR/xmlpserver/WEB-INF` directory with a text editor.

For example,

```
<?xml version="1.0" encoding="UTF-8"?>
<xmlpConfig xmlns="http://xmlns.oracle.com/oxp/xmlp">
  <resource>
    <file path="{oracle.home}/xdo/repository"/>
  </resource>
</xmlpConfig>
```

3. Replace `{oracle.home}/xdo/repository` with file path to the location where you copied the XMLP repository directory on your server.

For example,

```
<?xml version="1.0" encoding="UTF-8"?>
<xmlpConfig xmlns="http://xmlns.oracle.com/oxp/xmlp">
  <resource>
    <file path="/u00/webadmin/RMS_BIP/xmlpserver/XMLP"/>
  </resource>
</xmlpConfig>
```

4. Save the `xmlp-server-config.xml` after updating it.
5. (Optional) Copy the font files from the `<BI_MEDIA>/fonts` in the installation media to the fonts directory of the Java Runtime Environment used by the WebLogic server being used for the deployment (represented by `WLS_JAVA_HOME` in the example below). This is an optional task for users that plan to deploy their own customized reports for RMS using BI Publisher directly.

For example,


```
cp -R /tmp/BIPublisherSource/fonts WLS_JAVA_HOME/jre/lib/fonts
```

Note: This task will require a WLS server restart.

Install Managed Server in WebLogic


Before running the deployment of BI Application, you must install a managed server for deploying the BI application in WebLogic, if it was not created during the domain installation. Follow the steps below to install bipublisher managed server.

1. Log in to the admin console.




2. Click **Lock & Edit**.

3. Navigate to Environment > Servers. Select new tab of the servers on the right side.



4. Set the following variables:
 - **Server Name:** This value should be specific to your targeted application (for example, bipublisher-server)
 - **Server Listen Address:** <weblogic server> (for example, redevlv0072.us.oracle.com)
 - **Server Listen Port:** A free port. Check for availability.
A suggestion is to increment the AdminServer port by two and keep incrementing by two for each managed server (for example, 7003, 7005, 7007 and so on.)

5. Click Next.



6. Click Finish.

The screenshot shows the Oracle WebLogic Server Administration Console interface. The main content area is titled "Summary of Servers" and includes a "Configuration" tab. Below the tab, there is a message stating "Server created successfully." and a table of servers. The table has columns for Name, Cluster, Machine, State, Health, and Listen Port. The servers listed are AdminServer (admin), bipublisher-server, WLS_FORMS, and WLS_REPORTS. The WLS_FORMS and WLS_REPORTS servers are in a RUNNING state with OK health.

Name	Cluster	Machine	State	Health	Listen Port
AdminServer (admin)		redevlv0072	RUNNING	OK	7001
bipublisher-server			Unknown		7003
WLS_FORMS	cluster_forms	redevlv0072	RUNNING	OK	9001
WLS_REPORTS	cluster_reports	redevlv0072	RUNNING	OK	9002

- Click **Activate Changes** on the left side. Once the changes are activated, the State of the bipublisher-server should change to SHUTDOWN status.

The screenshot shows the WLS Console interface in a browser window. The main content area displays the 'Summary of Servers' page. A green message at the top indicates that all changes have been activated. The 'Configuration' tab is selected, showing a table of servers. The 'bipublisher-server' is highlighted in the table, and its state is 'SHUTDOWN'. The 'Health' column shows a green checkmark and 'OK'. The 'Listen Port' is 7003. The 'Machine' is redevlv0072. The 'Cluster' is empty. The 'Name' is bipublisher-server. The 'State' is SHUTDOWN. The 'Health' is OK. The 'Listen Port' is 7003.

Name	Cluster	Machine	State	Health	Listen Port
AdminServer (admin)		redevlv0072	RUNNING	OK	7001
bipublisher-server		redevlv0072	SHUTDOWN	OK	7003
WLS_FORMS	cluster_forms	redevlv0072	RUNNING	OK	9001
WLS_REPORTS	cluster_reports	redevlv0072	RUNNING	OK	9002


Install NodeManager

Install NodeManager if it was not created during domain install. NodeManager is required so that the managed servers can be started and stopped through the admin console. Only one node manager is needed per WebLogic install.

1. Log in to the admin console.
2. Click **Lock & Edit**. Navigate to Environments->Machines. Click **New**.

The following page is displayed. Set the following variables:

- Name: Logical machine name
- Machine OS: UNIX



3. Click **OK** to activate the changes.

4. Click the machine created.

The screenshot displays the Oracle WebLogic Server Administration Console in a Windows Internet Explorer browser window. The browser's address bar shows the URL: `http://redevlv0072.us.oracle.com:7001/console/console.portal?_nfpb=true&_pageLabel=CoreMachineMachineTal`. The console interface includes a navigation menu on the left with options like "Change Center", "Domain Structure", and "How do I...". The main content area is titled "Summary of Machines" and contains a table with one machine entry.

Summary of Machines


A machine is the logical representation of the computer that hosts one or more WebLogic Server instances (servers). WebLogic Server uses configured machine names to determine the optimum server in a cluster to which certain tasks, such as HTTP session replication, are delegated. The Administration Server uses the machine definition in conjunction with Node Manager to start remote servers.

This page displays key information about each machine that has been configured in the current WebLogic Server domain.


Machines

<input type="checkbox"/>	Name ↕	Type
<input type="checkbox"/>	redevlv0072	UnixMachine

The table shows one machine with the name "redevlv0072" and type "UnixMachine". The table is controlled by "New", "Clone", and "Delete" buttons above and below it. The status "Showing 1 to 1 of 1" is displayed on the right side of the table.




5. Click the NodeManager tab and update the details below.
 - **Type:** Plain
 - **Listen Address:** <weblogic server> (for example, redevlv0072.us.oracle.com)
 - **Listen Port:** Assign a port number. Default port is 5556.



6. Click Save.
7. Click Activate Changes.
8. Click Lock & Edit.

9. Navigate to Environments > machines. Click the machine name. Select the Servers tab. Click **Add**.



10. Add the managed servers that need to be configured with the Nodemanager. Save changes.
 - From the drop down select the managed server to be added to nodemanager
 - Server: <app-server> (for example: bipublisher-server)
11. Click **Next**. Click **Finish**.
12. Click **Activate Changes**.

Note: To activate changes the server needs to be stopped:

```
<WLS_HOME>/user_projects/domains/<domain_name>/
bin/
stopManagedWebLogic.sh bipublisher-server
${server_name}:${server_port}
```

Go to the managed server that is being added to the machine and click the Server Start tab. In the Class Path box, add the following:

```
<full-path-to-domain>/servers/<managed-server>
```

```
For example: /u00/webadmin/product/10.3.3
/WLS/user_projects/domains/<Domain
_name>/servers/bipublisher-server
```

13. Click **Save**.
14. Click **Activate Changes**.
15. Update `nodemanager.properties` file at the following location and set the `SecureListener` variable to `false`.
`<WEBLOGIC_HOME>/wlserver_10.3/common/nodemanager/nodemanager.properties`
`SecureListener=false`
16. Start NodeManager from the server using the `startNodeManager.sh` at
`<WEBLOGIC_HOME>/wlserver_10.3/server/bin`

Start the Managed Servers

To start the managed servers, complete the following steps.

1. Start the Node Manager from the command line if it is not started already.

```
$WLS_HOME/wlserver_10.3/server/bin startNodeManager.sh
```

After the Node Manager is started, the managed servers can be started through the admin console.

2. Navigate to **Environments > Servers**. Select `<bipublisher-server>` managed server. Click the **Control** tab.

The screenshot shows the Oracle WebLogic Server Administration Console. The main content area displays the 'Summary of Servers' page with the 'Control' tab selected. A table lists the servers in the domain:

Server	Machine	State	Status of Last Action
AdminServer (admin)	redevlv0072	RUNNING	None
bipublisher-server		SHUTDOWN	None
WLS_FORMS	redevlv0072	RUNNING	None
WLS_REPORTS	redevlv0072	RUNNING	None

Buttons for 'Start', 'Resume', 'Suspend', 'Shutdown', and 'Restart SSL' are visible above and below the table. The 'bipublisher-server' row has a 'Start' button available.

3. Click **Start** to start the managed server.

Additional Setup Steps Before Deploying the BI Application

Following steps are the additional set up steps required before deploying the BI application in WebLogic.

1. Shutdown the bipublisher managed server created above.
2. Add the following option to the startWebLogic.sh script for the server on which the BI Publisher instance is installed.


```
JAVA_OPTIONS="${JAVA_OPTIONS} -  
Dtoplink.xml.platform=oracle.toplink.platform.xml.jaxp.JAXPPlatform"
```

3. Locate the below mentioned jar files in <BI_DEPLOYMENT>/xmlpsrver/WEB-INF/lib and add the libraries in your installation (example: copy the jars to the location <WLS_HOME/user_projects/domains/<domain_home>/servers/bipublisher-server/). Append the path of the libraries to the Java classpath for the bipublisher managed server in the weblogic admin console (Classpath in weblogic admin console is available in the path: Weblogic Administration console->Servers->BIPublisher managed server->Server Start-> Classpath)

- ojdbc14.jar
- bijdbc14.jar
- toplink.jar
- commons-dbc-1.1.jar

4. Add the following arguments to the arguments of the java launcher (Arguments in weblogic admin console is available in the path: Weblogic Administration console->Servers->BIPublisher managed server->Server Start-> Arguments)

```
-Xms512m -Xmx512m -  
Dtoplink.xml.platform=oracle.toplink.platform.xml.jaxp.JAXPPlatform -  
Djavax.xml.soap.MessageFactory=WebLogic.xml.saa.j.MessageFactoryImpl
```



- Restart the WebLogic server.

Deploying the BI Application in WebLogic


The exploded archive directory created above in “Creating an Exploded Directory for the Installation” must now be deployed into the bipublisher managed server of WebLogic. Deployment can be achieved in a number of ways but we will use the WebLogic Administration Console and the following steps.

Open the WebLogic Administration console web page by typing the appropriate URL for the WebLogic admin server.


For example,

`http://wls_srv:7001/console`


1. Log on to the console using an administrator user name and password.
2. In the Change Center of the Administration Console, click **Lock & Edit**.
3. In the left pane of the Administration Console, click **Deployments**.
4. In the right pane, click **Install**. The following screen should be displayed.




5. Select the exploded directory referenced by <BI_DEPLOYMENT>/xmlpsrver. Click Next.




6. Select the Install this deployment as an application option. Click Next.



7. Select the bipublisher managed server as the deployment target. Click **Next**.



8. Select **I will make the deployment accessible from the following location** from Source accessibility.




9. Click **Finish**.

The screenshot shows the 'Summary of Deployments' page in the WLS Console. The page is titled 'Summary of Deployments - ClassicDomain - WLS Console'. It features a navigation pane on the left with sections for 'Domain Structure', 'Deployments', 'How do I...', and 'System Status'. The main content area is titled 'Control' and contains a table of deployed applications. The table has columns for Name, State, Health, Type, and Deployment Order. The applications listed include 'ari-help', 'DMS Application (11.1.1.1.0)', 'em', 'PMW Welcome Page Application (11.1.0.0.0)', 'formsapp (11.1.1)', 'formsconfigbeans', 'NonJ2EEManagement (11.1.1)', 'reports (11.1.1.2.0)', 'rms-help', 'rvms-help', 'wsl-wls', and 'xmlpserver'. The 'Activate Changes' button is located at the top left of the console window.


Name	State	Health	Type	Deployment Order
ari-help	Active	OK	Enterprise Application	100
DMS Application (11.1.1.1.0)	Active	OK	Web Application	5
em	Active	OK	Enterprise Application	400
PMW Welcome Page Application (11.1.0.0.0)	Active	OK	Enterprise Application	5
formsapp (11.1.1)	Active	OK	Enterprise Application	100
formsconfigbeans	Active	OK	Enterprise Application	100
NonJ2EEManagement (11.1.1)	Active	OK	Enterprise Application	100
reports (11.1.1.2.0)	Active	OK	Enterprise Application	100
rms-help	Active	OK	Enterprise Application	100
rvms-help	Active	OK	Web Application	100
wsl-wls	Active	OK	Enterprise Application	5
xmlpserver	distribute Initializing		Web Application	100

10. To activate these changes, in the **Change Center** of the Administration Console, click **Activate Changes**.

- On the left side of the console, select Deployments. A list of deployments should now be showing in the table on the right.



12. Scroll down and select **xmlpserver** to start the service. The server's state should change to an active state when refreshed.



13. Launch BI Publisher using the appropriate URL for the WebLogic server appended by the web application context `"/xmlpserver"`.

For example:

http://wls_srv:7003/xmlpserver

Note: If using SSO/LDAP for BIPublisher, BIPublisher managed server should be started using the following parameter:

`-Dweblogic.http.enableRemoteUserHeader=true`

If the `<bipublisher-server>` is being started from WebLogic Admin console, the above parameter should be added here before restarting the BIPublisher managed server from the Admin console:

Adminconsole > Environment > Servers-> `<bipublisher-server>` > Server Start > Arguments.

If the server is being started from UNIX, consider the following example:

```
<WEBLOGIC_DOMAIN_HOME>/bin/startManagedWeblogic.sh <bipublisher-server> <server:port> -Dweblogic.http.enableRemoteUserHeader=true
```

Installing the RMS/ORFM BI Publisher Templates

In this section we will outline how the RMS/ORFM report templates are installed into the appropriate BI server repositories. BI_REPOSITORY refers to the BI Publisher reports repository. Example: /u00/webadmin/RMS_BIP/xmlpserver/XMLP

Report files are placed in the directory - "INSTALL_DIR/base/reports " and have to be copied into the BI repository directory.

1. Locate the RMS directory to hold the reports under <BI_REPOSITORY>/Reports/Guest.
Example <BI_REPOSITORY>Reports/Guest/RMS13
2. Change directory to the INSTALL_DIR/base/reports used for the application install. This directory contains subdirectories whose names reflect the names of report templates provided with RMS and ORFM.
3. Copy each report directory into the directory created above

For example,

```
cp -R * /u00/webadmin/RMS_BIP/xmlpserver/XMLP/Reports/Guest/RMS13/
```

Configuring the RMS JDBC connection

Follow the below steps to configure JDBC connection for RMS Data Source name. This datasource RMS will be used for RMS reports.

1. Log on with the default user ID and passwords for BI Publisher using the administrative user and password configured previously.
2. Click the **Admin** tab and select the **JDBC Connection** hyperlink in the Data Sources lists. The following screen is displayed.

The screenshot shows the Oracle BI Publisher Admin console. The browser address bar indicates the URL: http://reddevl0065.us.oracle.com:17003/xmlpserver/servelet/adm/datasource/updateconnection?mode=UPDATE&type=jdbc&name=RMS13. The page title is "ORACLE BI Publisher Enterprise" and the user is logged in as "administrator". The navigation tabs are "Reports", "Schedules", and "Admin". The current page is "Admin > JDBC > Update Data Source: RMS13". The "Update Data Source: RMS13" form is displayed with the following fields:

- General**
 - TIP Please make sure to install the required JDBC driver classes.
 - Data Source Name: RMS13
 - * Driver Type: Oracle 9i/10g/11g
 - * Database Driver Class: oracle.jdbc.OracleDriver
 - * Connection String: jdbc:oracle:thin:@reddevl0064.us.oracle.com:1521:dvols72
 - * Username: rms01app
 - Password: [masked]
 - Pre Process Function: [empty]
 - Post Process Function: [empty]
 - Use Proxy Authentication
 -
- Security**
 - Available Roles: gabrole
 - Allowed Roles: [empty]
 - Buttons: Move, Move All

3. Enter the appropriate details for the RMS data source. Once the data is entered, click Test Connection to test the connection.

Configuring the BIPublisher Scheduler

Complete the following tasks for scheduler configuration:

1. Create the database user for scheduler configuration as below:

```
create user <scheduler schema user> identified by <password> default
tablespace <table space name> temporary tablespace temp;
grant create session,create table to <scheduler schema user>;
alter user <scheduler schema user> quota unlimited on <table space name>;
```

2. Navigate to the top level Admin display and select the **Scheduler Configuration** hyperlink. This will show you the following screen. Enter the appropriate database connection details and test the connection as previously done. If this connection operates successfully, save the connection details. Click **Install Schema** to install the schema for BI publisher using the <scheduler schema user> that was created in the previous step.

Note: For information about configuring BI Publisher, use the following URL:

http://download.oracle.com/docs/cd/E12844_01/doc/bip.1013/e12690/T434820T487783.htm#5187634

Verify Oracle BI Publisher Set Up for RMS Reports

Verify that Oracle BI Publisher has been set up correctly as follows:

1. Click the **Admin** tab. Click **Report Repository** under System Maintenance. The Path variable should be set as part of the BI Publisher install, REPORTS_DIR.
2. Add the following values to the <installation name>.env file located here:


```
$WLS_HOME/user_projects/domains/<domain
name>/config/fmwconfig/servers/WLS_FORMS/applications/formsapp_11.1.1/
config/<installation name>/<installation name>.env
```

 - ORACLE_RMS_REPORTS_HOST=http://<server>:<port>/

For example,
ORACLE_RMS_REPORTS_HOST=http://redevlv0072.us.oracle.com:7003/
 - ORACLE_RMS_RWSERVER=/<location to RMS directory>/

For example, ORACLE_RMS_RWSERVER=xmlpsrver/Guest/RMS13/

Data Migration

The 13.2.3 release includes a tool for upgrading preexisting data in the RMS schema to the ORFM 13.2.3 schema, once 13.2.3 ORFM database scripts are executed. When ORFM is installed, your existing RMS data must be migrated to accommodate changes to the database caused by ORFM installation.

Note: If you already ran the Data Migration tool during or after the 13.2.2 release, you do not need to run it again.

Before running the ORFM 13.2.3 Data Migration Tool, do the following.

1. Make a backup of all your objects and database schema.
2. Ensure that ORFM 13.2.3 is installed.
3. Review the enclosed 13.2.3 Upgrade Release Notes (rms-1323-rn.pdf).
4. Review each of the enclosed defect documents.
5. Run the l10nbrfisdnl.d.pc batch program. This program must to be run after RTIL has been installed.

Create Staging Directory for RMS Data Migration Files

To create a staging directory for RMS data migration files, complete the following steps.

1. Log in to the database server as a user that can connect to the RMS database.
2. Create a staging directory for the RMS database schema installation software.
3. Copy the orfm1323datamigration.zip file from the ORFM 13.2 release to the staging directory. This is referred to as STAGING_DIR when running the data migration tool.
4. Change directories to STAGING_DIR and extract the orfm1323datamigration.zip file. This creates a “master_controller” subdirectory under STAGING_DIR.

Configure ORFM Data Migration Tool

To configure the ORFM data migration tool, complete the following steps.

1. Change directories to STAGING_DIR/master_controller/rms/br.
2. Source the oraenv script to set up the Oracle environment variables (ORACLE_HOME, ORACLE_SID, PATH, etc).

```

Example:  prompt$ . oraenv
              ORACLE_SID = [] ? mydb
              prompt$

```

3. Verify the ORACLE_HOME and ORACLE_SID variables after running this script.

```
Example: prompt$ echo $ORACLE_HOME
           /u00/oracle/product/mydbversion
prompt$ echo $ORACLE_SID
           mydb
```

4. Set and export the NLS_LANG environment variable.

```
Example: NLS_LANG=AMERICAN_AMERICA.UTF8
           export NLS_LANG
```

5. Set and export the TNS_ADMIN environment variable.

```
Example: TNS_ADMIN=/path/to/wallet/files/dir/
           export TNS_ADMIN
```

6. Open the l10nbrcontroller.cfg file and replace the values variables as follows:

- a. Export PATCH_DIR=STAGING_DIR/master_controller/rms
- b. export SCHEMA_OWNER=<The name of the RMS schema>
- c. export MMUSER=/@< Schema Owner Wallet Alias >

```
Note: See Appendix K: Setting Up Password Stores with
Oracle Wallet for how to set up database wallet.
```

```
Note: Verify that TNS is set up correctly by using the UP
variable to successfully log in to the RMS 13 schema.
```

```
Example: /u00/oracle> sqlplus $UP
```

7. Configure the following files in the STAGING_DIR/master_controller/rms/br/files directory with data from your existing RMS/ORFM schema for the migration. (Use the existing files as templates for how this data should be formatted. For descriptions of this data, see the *Oracle Retail Fiscal Management Data Model*.)

▪ competitor.dat

This file is used to update the jurisdiction code for a given competitor. Attributes are:

- Competitor
- Jurisdiction Code

▪ country_atrib.dat

This file is used to update the country attributes for Brazil. Attributes are:

- Item costing tax inclusive indicator (Y/N)
- Default cost for purchase orders, deals, cost components
- Default location
- Default location type

▪ vat_codes.dat

This file is used to load the tax codes for Brazil. Attributes are:

- Tax code
- Tax code description
- Indicator (Y/N), depending on whether the tax code is included in the calculation of the Negotiated Item Cost.

- **addr.dat**
This file is used to update the jurisdiction code for a given supplier/partner/store/warehouse. Attributes are:
 - Address key
 - Jurisdiction code
- **comphead.dat**
This file is used to update the jurisdiction code for a company. Attributes are:
 - company
 - Jurisdiction code
- **comp_store.dat**
This file is used to update the jurisdiction code for a competitor store. Attributes are:
 - Competitor store
 - Jurisdiction code
- **customer.dat**
This is used to update the jurisdiction code for a given customer. Attributes are:
 - Customer
 - Jurisdiction code
- **ordcust.dat**
This file is used to update the jurisdiction code for a customer order. Attributes are:
 - Customer
 - Customer order sequence number
 - Jurisdiction code
- **outloc.dat**
This file is used to update the jurisdiction code for a given outside location. Attributes are:
 - Outside location type
 - Outside location
 - Jurisdiction code
- **rtv_head.dat**
This file is used to update the jurisdiction code for a RTV. Attributes are:
 - RTV order number
 - Jurisdiction code
- **country_l10n_ext.dat**
This file is used to load the fiscal attributes for countries. Attributes are:
 - Country
 - Fiscal country
 - Fiscal code
- **item_country_l10n_ext.dat**
This file is used to load the fiscal attributes for items. Attributes are:
 - Item
 - Country

- Service ind
- Merchandise origin
- NCM
- NCM characteristic
- IPI
- Pauta code
- Service code
- Federal service code
- State_of_manufacture
- Pharma_list_type
- outloc_l10n_ext.dat
This file is used to load the fiscal attributes for outside locations. Attributes are:
 - Outside location type
 - Outside location
 - Taxpayer type
 - Address line 1
 - Address line 2
 - Address line 3
 - Neighborhood
 - Jurisdiction code
 - State
 - Country
 - Postal code
 - CPF
 - CNPJ
 - NIT
 - SUFRAMA
 - City inscription
 - State inscription
 - IPI contributor (Y/N)

- partner_l10n_ext.dat
This file is used to load the fiscal attributes for partners. Attributes are:
 - Partner type
 - Partner
 - Taxpayer type
 - Address line 1
 - Address line 2
 - Address line 3
 - Neighborhood
 - Jurisdiction code
 - State
 - Country
 - Postal code
 - CPF
 - CNPJ
 - NIT
 - SUFRAMA
 - City inscription
 - State inscription
 - IPI contributor (Y/N)
 - ICMS contributor (Y/N)
 - PIS contributor (Y/N)
 - COFINS contributor (Y/N)
- store_l10n_ext.dat
This file is used to load the fiscal attributes for stores. Attributes are:
 - Store
 - Taxpayer type
 - Address line 1
 - Address line 2
 - Address line 3
 - Neighborhood
 - Jurisdiction code
 - State
 - Country
 - Postal code
 - CPF
 - CNPJ
 - NIT
 - SUFRAMA
 - City inscription
 - State inscription
 - ISS contributor (Y/N)

- Rural producer (Y/N)
- IPI contributor (Y/N)
- ICMS contributor (Y/N)
- Matching operation type
- Control recovery of ST (Y/N)
- PIS contributor (Y/N)
- COFINS contributor (Y/N)
- sups_l10n_ext.dat
 - This file is used to load the fiscal attributes for suppliers.
 - Supplier
 - Taxpayer type
 - Address line 1
 - Address line 2
 - Address line 3
 - Neighborhood
 - Jurisdiction code
 - State
 - Country
 - Postal code
 - CPF
 - CNPJ
 - NIT
 - SUFRAMA
 - City inscription
 - State inscription
 - ISS contributor (Y/N)
 - SIMPLES contributor (Y/N)
 - ST contributor (Y/N)
 - Rural producer (Y/N)
 - IPI contributor (Y/N)
 - ICMS contributor (Y/N)
 - PIS contributor (Y/N)
 - COFINS contributor (Y/N)
 - is_income_range_eligible
 - is_distr_a_manufacturer
 - icms_simples_rate
- wh_l10n_ext.dat
 - This file is used to load the fiscal attributes for warehouses. Attributes are:
 - Warehouse
 - Taxpayer type
 - Address line 1
 - Address line 2

- Address line 3
- Neighborhood
- Jurisdiction code
- State
- Country
- Postal code
- CPF
- CNPJ
- NIT
- SUFRAMA
- City inscription
- State inscription
- ISS contributor (Y/N)
- Rural producer (Y/N)
- IPI contributor (Y/N)
- ICMS contributor (Y/N)
- Matching operation type
- Control recovery of ST (Y/N)
- PIS contributor (Y/N)
- COFINS contributor (Y/N)
- l10n_br_entity_trib_subs.dat
This file is used to load the state inscriptions for suppliers/warehouses and stores. Attributes are:
 - Supplier/Warehouse/Store
 - Entity Type (SUPP/S/W)
 - Country
 - State
 - State Inscription
- l10n_br_entity_cnae_codes.dat
This file is used to load the CNAE codes for supplier/store/warehouse/company/ outside location/partner. Attributes are:
 - Supplier/Store/Warehouse/Company/Outside location/ Partner
 - Partner type/Outside location type
 - Entity type
 - Country
 - CNAE code
 - Primary indicator (Y/N)
- l10n_br_sup_tax_regime.dat
This file is used to load the tax regime of the supplier. Attributes are:
 - Supplier
 - Tax_regime

Run the ORFM Data Migration Tool

To run the ORFM data migration tool, complete the following steps.

1. Change directories to STAGING_DIR/master_controller/rms/br.
2. If rerunning the data migration process, clear the contents of the “processed” directory.
3. Run prevalidation tool to ensure that the input files for the data migration tool is up to date:

```
$ ./rms132_br_upgrade.ksh PREVALIDATION
```
4. Run migration tool.


```
$ ./rms132_br_upgrade.ksh UPGRADE
```
5. Run migration cleanup tool to remove temporary data migration objects from the database.

```
$ ./rms132_br_upgrade.ksh CLEANUP
```
6. Refer to the files in the **log** and **error** directory if there are problems during migration.
7. Rebuild synonyms for any additional RMS users.


Appendix: ORFM RTIL Installer Screens

You need the following details about your environment for the installer to successfully deploy the RTIL application. Depending on the options you select, you may not see some screens or fields.

Screen: Retail Tax Integration Layer – Introduction



Screen: Manual Deployment Option



Fields on this Screen:

Field Title	Install files to app server?
Field Description	If you do not have write access under ORACLE_HOME, you can still use the installer to gather your settings and configure the RTIL files locally in the staging area. At a later time, an administrator can manually copy over the RTIL files and deploy the war file. If you select this option, instructions are printed to the console and the installer log file for the steps needed to complete the installation.

Screen: Application Deployment Details

Application Deployment Details

The default values shown below are examples

RTIL 13 app deployment name

Enter the RTIL13 weblogic managed server or cluster.

RTIL13 server/cluster

Cancel Back Next Install

Fields on this Screen:

Field Title	RTIL 13 app deployment name
Field Description	Name by which this RTIL application is identified in the application server
Example	rtil13

Field Title	RTIL 13 server/cluster
Field Description	Name of the RTIL WebLogic managed server or cluster.
Example	rtil-server

Screen: WebLogic Administrative User

Fields on this Screen:


Field Title	Hostname
Field Description	Hostname of the application server
Example	redevlv0074

Field Title	WebLogic admin port
Field Description	Port number of admin console
Example	17001

Field Title	WebLogic admin user
Field Description	User name of the admin user for the WebLogic instance to which the ORFM application is being deployed.
Example	weblogic

Field Title	WebLogic admin password
Field Description	Password for the WebLogic admin user. You chose this password when you created the WebLogic instance or when you started the instance for the first time.

Screen: Log 4j logger Details



Fields on this Screen:


Field Title	Log4j Log Level
Field Description	Specifies the level at which the logging is enabled.
Example	INFO

Field Title	Output to STDOUT
Field Description	Specifies whether the logs should be routed to the console.

Field Title	Log4j logfile MaxFileSize (MB)
Field Description	Specifies the file size threshold beyond which the log file gets rolled over.
Example	5

Field Title	Log4j logfile MaxBackupIndex
Field Description	Specifies the number of rolled over log files that will be retained.
Example	30

Screen: Data Source Details



Fields on this Screen:

Field Title	RMS JDBC URL
Field Description	URL used by the application to access the RMS Database schema.
Example	jdbc:oracle:thin@mspdv314:1521:pkols05

Field Title	RMS schema user
Field Description	Database schema user for the application. This value should match the value in the RMS database schema field for the RMS DB installer.
Example	rms01

Field Title	RMS schema password
Field Description	Password for user, RMS Schema User

Screen: Installation Summary


Summary of Installation	
App Name	rtil13
Weblogic Managed Server/Clus...	rtil-server
App Server Host	redevlv0074
Weblogic Admin Port	17001
Weblogic Admin User	weblogic
Log4j Log Level	INFO
Output to STDOUT?	true
Log4j logfile MaxFileSize (MB)	5
Log4j logfile MaxBackupIndex	30

All fields on this summary screen are read-only. In GUI mode of the installer, this screen provides the opportunity to review inputs and go back to previous screens to correct them if necessary.

Appendix: ORFM Database Patch Installer Screens

You need the following details about your environment for the installer to successfully patch the ORFM/ RMS database schema.

Screen: ORFM Database Schema Details



Fields on this screen:

Field Title	ORFM/RMS schema
Field Description	Provide the RMS database user here. The installer logs into the database as this user to patch the RMS schema. This user must already exist in the database when the ORFM database schema patch installer is run.
Example	rms01

Field Title	ORFM/RMS schema password
Field Description	Database password for the RMS schema Owner.

Field Title	ORFM/RMS Oracle SID
Field Description	Oracle system identifier for the database where the ORFM patch will be applied.
Example	pkols05

The database settings provided are validated by the installer when you advance to the next screen.


Screen: Apply an ORFM DB Patch



Fields on this Screen:

Field Title	ORFM Patch Directory
Field Description	Provide the directory path to the ORFM patch you want to install. The installer runs only the patch you provide. Note: The directory you choose must contain an orfm_controller.ksh file.
Example	/path/to/ orfm/dbschemapatch/orfm-dbpatch/13.2.3/orfm Note: The patch option is intended for patches starting with 13.2.1.

Screen: Continue ORFM DB Patch



Fields on this Screen:

Field Title	Continue ORFM DB Patch?
Field Description	<p>The patch process allows you to continue a previously run patch if it stopped before completion or failed. If Yes is selected, any scripts that were previously run for the ORFM patch will be skipped. If No is selected, the patch will start from the beginning.</p> <p>Note: To continue a patch, the content of the “processed” directories in the ORFM Patch Directory chosen on the previous screen must be the same as it was after the previous patch was stopped. If you choose No, this directory will be cleared, and you will not be able to continue this patch in the future.</p>

Appendix: RMS Batch Installer Screens

You need the following details about your environment for the installer to successfully compile and install the RMS batch programs. Depending on the options you select, you may not see some screens or fields.

Screen: Welcome



There are no fields on this screen. The Welcome screen contains information about the RMS Batch Installer and prerequisites.

Screen: DataSourceDetails

Oracle Retail Merchandising System - Batch Installer

ORACLE

Data Source Details

Please provide information for the RMS database user. It is assumed that you have already run the RMS DB schema installer with this user to create the RMS tables and objects. The RMS batch installer will authenticate as this user to create library objects and query for data to generate batch source files.

RMS Schema Owner: rms01
 RMS Schema Password: *****
 RMS Oracle SID: pkols05

Buttons: Cancel, Back, Next, Install

Fields on this Screen:

Field Title	RMS Schema Owner
Field Description	Provide the RMS database user here. The installer will log into the database as this user to create RMS library objects and query for data to generate batch source files. This user must already exist in the database and have the RMS tables installed.
Example	rms01

Field Title	RMS Schema Password
Field Description	Database password for the RMS Schema Owner.

Field Title	RMS Oracle SID
Field Description	Oracle system identifier for the database where RMS will be installed
Example	pkols05

Screen: Oracle Wallet

Oracle Wallet

An Oracle Wallet is an encrypted container used to store and retrieve sensitive information, such as user credentials. A new Wallet is created to contain passwords used by RMS. Every Wallet is itself protected by a password, and the field for this Wallet password must be filled out to move on to the next screen.

The password must have a minimum length of eight characters and contain alphabetic characters combined with numbers or special characters.

Oracle Wallet password

Please re-enter password

Fields on this Screen:

Field Title	Oracle Wallet password
Field Description	This is the password for the wallet that will store the database credentials that were supplied in the previous screen.

Screen: Batch Installation Directory

Oracle Retail Merchandising System - Batch Installer

ORACLE

Batch Installation Directory


Please enter the directory where RMS Batch will be installed.

Batch Installation Directory

Fields on this Screen:

Field Title	Batch Installation Directory
Field Description	Location where the installer will install the batch source and then compile it. This is the permanent location for the RMS batch programs.
Example	/opt/oracle/retail/rmsbatch

Screen: Summary




All of the fields on this summary screen are read-only. In GUI mode of the installer, this screen provides the opportunity to review inputs and go back to previous screens to correct them if necessary.

Once you advance forward from this screen, the installer connects to the database and validate that the RMS user exists before beginning installation.

Appendix: RMS Application Installer Screens

Screen: Welcome



There are no fields on this screen. The Welcome screen contains information about the RMS Application Installer and prerequisites.

Screen: Oracle Customer Information

For information about this screen, see the "Oracle Configuration Manager" section in the *Oracle Configuration Manager Installer Guide*.

Screen: Data Source Details

Fields on this Screen:

Field Title	RMS Schema Owner
Field Description	This is the same username that was used during the RMS Database Schema Installer.
Example	rms01

Field Title	RMS Schema Password
Field Description	This is the same password that was used during the RMS Database Schema Installer.

Field Title	RMS Oracle SID
Field Description	This is the same Oracle SID that was used during the RMS Database Schema Installer.
Example	pkols05

Field Title	Test Data Source?
Field Description	Attempt to validate the Data Source Details on this screen. This will happen when you click Next . Note: If you get any errors not related to incorrectly entered credentials, please refer to Appendix: Common Installation Errors .

Screen: Oracle Wallet

Oracle Retail Merchandising System - Forms App Installer

ORACLE

Oracle Wallet

An Oracle Wallet is an encrypted container used to store and retrieve sensitive information, such as user credentials. A new Wallet is created to contain passwords used by RMS. Every Wallet is itself protected by a password, and the field for this Wallet password must be filled out to move on to the next screen.

The password must have a minimum length of eight characters and contain alphabetic characters combined with numbers or special characters.

Oracle Wallet password

Please re-enter password

Cancel Back Next Install

Fields on this Screen:

Field Title	Oracle Wallet password
Field Description	This is the password for the wallet that will store the database credentials that were supplied in the previous screen.

Screen: Installation Name

Installation Name

Please enter the Installation Name. The Installation Name is a unique name that will be used to identify this installation of RMS. This name will be included in the RMS Application URLs and reported by the Oracle Configuration Manager.


Installation Name

Cancel Back Next Install

Fields on this Screen:

Field Title	Installation Name
Field Description	This value is used in conjunction the Oracle Configuration Manager (OCM). It gives the installation a unique name so the OCM can identify different installations of RMS in the same WebLogic instance.
Example	rms13inst


Screen: Application Installation Directory



Fields on this Screen:

Field Title	Application Installation Directory
Field Description	The location where the RMS Application (toolset, forms and reports) will be installed. The RMS \$MMHOME path will be a subdirectory of this directory, named base.
Example	/u01/oracle/retail

Screen: Application Deployment Method



Fields on this Screen:

Field Title	Which Environment Deployment Method would you like to use
Field Description	Select the Application Deployment Method you would like. See Appendix: Application Deployment Method for information.
Example	Base – 1 URL

Screen: WebLogic Configuration



Fields on this Screen:

Field Title	Configure WebLogic
Field Description	Make the necessary configurations to the WebLogic server to be able to run RMS forms. If you choose No, these configurations should be done manually. Note: If you rerun the installer, and choose to check the box in the installer screens, Configure WebLogic, you may need to clean up duplicate entries in the WebLogic formsweb.cfg file.

Screen: Weblogic Administrative Details

Oracle Retail Merchandising System - Forms App Installer

ORACLE

Weblogic Administrative Details

Enter the administrative user and password for the Weblogic Server to which the application will be deployed.

Hostname: redevlv0065

Weblogic Admin port: 7001

Weblogic Admin User: weblogic

Weblogic Admin Password: ●●●●●●●●●●


Cancel Back Next Install

Fields on this Screen:

Field Title	WebLogic Admin User
Field Description	Username of the admin user for WebLogic instance to which the RMS Webhelp application is being deployed.
Example	weblogic

Field Title	WebLogic Admin Password
Field Description	Password for the WebLogic admin user. You chose this password when you created the WebLogic instance.

Screen: Webhelp Installation Details



Fields on this Screen:

Field Title	WebLogic Help Server
Field Description	The WebLogic managed server that was created for the RMS Webhelp application.
Example	rms-help-instance

Screen: Summary

Installation Summary	
Summary of Installation.	
RMS Schema Owner:	rms01
RMS Database:	pkols05
Installation Name:	rms13inst
Installation Directory:	/u00/webadmin/rms13inst
Deployment Method:	Base
Configure Weblogic:	true
Hostname:	redevlv0065
Weblogic Admin port:	7001
Weblogic Admin User:	weblogic
RMS Help Server:	rms-help-instance

Buttons: Cancel, Back, Next, Install

All of the fields on this summary screen are read-only. In GUI mode of the installer, this screen provides the opportunity to review inputs and go back to previous screens to correct them if necessary.

Once you advance forward from this screen, the installer connects to the database and validates that the RMS user exists before beginning installation.

Appendix: Installer Silent Mode

Repeating an Installation Attempt

In addition to the GUI and text interfaces of the RMS installer, there is a silent mode that can be run. This mode is useful if you wish to run a repeat installation without retyping the settings you provided in the previous installation. It is also useful if you encounter errors in the middle of an installation and wish to continue.

The installer runs in two distinct phases. The first phase involves gathering settings from the user. At the end of the first phase, a properties file named `ant.install.properties` is created with the settings that were provided. Then the second phase begins, where this properties file is used to provide your settings for the installation.

To skip the first phase and re-use the `ant.install.properties` file from a previous run, follow these instructions:

1. Edit the `ant.install.properties` file and correct any invalid settings that may have caused the installer to fail in its previous run.
2. Look for duplicate properties in the `ant.install.properties` file. Some properties are set on multiple pages to ensure default values when a page is only displayed under certain conditions. For example, if there are two instances of `input.property.name`, remove all but the last one.
3. Run the installer again with the **silent** argument.

Example: `install.sh silent`

Appendix: URL Reference

JDBC URL for a Database

Used by the Java application and by the installer to connect to the database.

Thick Client Syntax: jdbc:oracle:oci:@<sid>

<sid>: system identifier for the database

Example: jdbc:oracle:oci:@mysid

Thin Client Syntax: jdbc:oracle:thin:@<host>:<port>:<sid>

<host>: hostname of the database server

<port>: database listener port

<sid>: system identifier for the database

Example: jdbc:oracle:thin:@myhost:1521:mysid

LDAP Server URL

Used by the Java application to connect to the LDAP directory.

Syntax: ldap://<host>:<port>

<host>: hostname of the directory server

<port>: LDAP server port

Example: ldap://myhost:389

JNDI Provider URL for an Application

Used by the application client to access the application running in the server. Also used by other applications for server-to-server calls.

OracleAS :

Syntax: opmn:ormi://<host>:<port>:<instance>/<app>

<host>: hostname of the OracleAS environment

<port>: OPMN request port of the OracleAS environment. This can be found in the <ORACLE_HOME>/opmn/conf/opmn.xml file.

<instance>: Name of the OC4J instance running the application

<app>: Deployment name for the application.

Example: opmn:ormi://myhost:6003:rsm-oc4j-instance/rsm13

Note: The JNDI provider URL can have a different format depending on your cluster topology. Consult the Oracle Application Server documentation for further details.

WebSphere:

Syntax: iiop://<host>:<port>

<host>: hostname of the WebSphere environment

<port>: BOOTSTRAP port of the WebSphere server that is running the application.

Example: iiop://myhost:2809

Appendix: Common Installation Errors

This section provides some common errors encountered during installation of RMS.

Database Installer Hangs on Startup

Symptom:

When the database schema installer is run, the following is written to the console and the installer hangs indefinitely:

```
Running pre-install checks
Running tnsping to get listener port
```

Solution:

The installer startup script is waiting for control to return from the **tnsping** command, but **tnsping** is hanging. Type Control+C to cancel the installer, and investigate and solve the problem that is causing the **tnsping <sid>** command to hang. This can be caused by duplicate database listeners running.

Unreadable Buttons in the Installer

If you are unable to read the text within the installer buttons, it probably means that your JAVA_HOME is pointed to a pre-1.4.2 JRE or JDK. Set JAVA_HOME to a Java runtime environment of version 1.5 or later and run the installer again.

Warning: Could not create system preferences directory

Symptom:

The following text appears in the installer Errors tab:

```
May 22, 2006 11:16:39 AM java.util.prefs.FileSystemPreferences$3 run
WARNING: Could not create system preferences directory. System preferences are
unusable.
May 22, 2006 11:17:09 AM java.util.prefs.FileSystemPreferences
checkLockFile0ErrorCode
WARNING: Could not lock System prefs. Unix error code -264946424.
```

Solution:

This is related to Java bug 4838770. The `/etc/.java/.systemPrefs` directory may not have been created on your system. See <http://bugs.sun.com> for details.

This is an issue with your installation of Java and does not affect the Oracle Retail product installation.

Warning: Couldn't find X Input Context

Symptom:

The following text appears in the console window during execution of the installer in GUI mode:

```
Couldn't find X Input Context
```

Solution:

This message is harmless and can be ignored.

Unresponsive Country and Currency Drop-Downs

Symptom:

In GUI mode, when you click on the drop-down list selection for the primary country or currency, the list does not appear, and this message appears in the console window:


```
XTEST extension not installed on this X server: Error 0
```

Solution:

To run the RMS installer in GUI mode you must have the XTEST extension enabled in your X server.

Enabling XTEST in Exceed:

1. Open Xconfig to edit Exceed configuration
2. Go to the X Server Protocol settings
3. Click on the Extensions tab
4. Make sure that the XTEST extension is selected:



5. Restart the X Server and re-run the RMS installer.

Could not exec robot child process: Permission denied

Symptom:

When opening a drop-down list in GUI mode of the RMS installer, the installer freezes up and displays the following message in the console:

```
Couldn't exec robot child process: Permission denied
```

Solution:

As the owner of the database ORACLE_HOME (i.e. *oracle*), grant execute permissions to the *awt_robot** files under *\$ORACLE_HOME/jdk/jre/lib*. The database schema installer uses *\$ORACLE_HOME/jdk* for its *JAVA_HOME*.

Example (using SUN Solaris):

```
chmod a+x $ORACLE_HOME/jdk/jre/lib/sparc/awt_robot
chmod a+x $ORACLE_HOME/jdk/jre/lib/sparcv9/awt_robot
```

ConcurrentModificationException in Installer GUI

Symptom:

In GUI mode, the errors tab shows the following error:

```
java.util.ConcurrentModificationException
    at
java.util.AbstractList$Itr.checkForComodification(AbstractList.java:448)
    at java.util.AbstractList$Itr.next(AbstractList.java:419)
... etc
```

Solution:

You can ignore this error. It is related to third-party Java Swing code for rendering of the installer GUI and does not affect the retail product installation.

FRM-30064: Unable to parse statement select while compiling fm_ituda.fmb

Symptom:

When running the application installer you get the following error:

```
FRM-30064: Unable to parse statement select vu.uda_desc, vu.uda_id from v_uda vu
where get_primary_lang = get_user_lang and vu.display_type = 'LV' union all
select nvl(t.translated_value, vu.uda_desc), vu.uda_id from tl_shadow t, v_uda
vu where get_primary_lang != get_user_lang and upper(vu.uda_desc) = t.key(+) and
get_user_lang = t.lang(+) and vu.display_type = 'LV' order by 1.
ORA-28112: failed to execute policy function
Record Group RG_UDA_LOV
Form: FM_ITUDALST
```

```
FRM-30085: Unable to adjust form for output.
```

```
Form not created
```

Solution:

Disable the database filter policies by running drop_filter_policy.sql, run the application installer again and then run add_filter_policy.sql. Both files can be located with the database installer.

ORA-04031 (unable to allocate memory) error during database schema installation

Symptom:

When running the database schema installer you get the following error one or more times:

```
[ora:sqlplus] alter package
[ora:sqlplus] *
[ora:sqlplus] ERROR at line 1:
[ora:sqlplus] ORA-04031: unable to allocate 92120 bytes of shared memory ("shared
[ora:sqlplus] pool", "unknown object", "PL/SQL MPCODE", "BAMIMA: Bam Buffer")
```

Solution:

There was not enough available memory in the shared pool on the database at the time of compilation. There are several choices to get past this error:

- Log into the database and attempt to recompile invalid objects in the database schema. Subsequent attempts to compile the same object(s) can be successful.
- Have a DBA increase the shared pool size on the database and re-run the installer from scratch on a new schema user.

X Error of failed request: BadWindow (invalid Window parameter)

Symptom:

When compiling forms during the application installation you receive this error one or more times:

```
X Error of failed request: BadWindow (invalid Window parameter)
Major opcode of failed request: 18 (X_ChangeProperty)
Resource id in failed request: 0x1800002
Serial number of failed request: 432
Current serial number in output stream: 437
```

Solution:

This error occurs when there are too many requests made to the X server. If this error occurs manually recompile the form.

Example:

```
frmpcmp.sh userid=$UP module_type=form module=FORM_OR_MENU
```

RIB Errors

At random times, the RIB will get certain errors such as GETNEXT(?,?,?,?,?) and/or ORA-21700 object does not exist or is marked for delete. This is very confusing because you may research and find that the object exists and is valid.

You must re-initialize the reference to reference an existing object. You do this by:

1. Bringing down the RIB OAS in question
2. Running `/RIB_INSTALL_DIR>/InstallAndCompileAllRibOracleObjects.sql`
3. Running another object validate script (ex: `inv_obj_comp.sql`) to make sure objects are valid (some may have deallocated in the end of the previous step).
4. Bringing up the RIB OAS in question

Error Connecting to Database URL

Symptom:

After entering database credentials in the installer screens and hitting next, a message pops up with an error like this:

```
Error connecting to database URL <url> as user <user>
details...
```

The message prevents you from moving on to the next screen to continue the installation.

Solution:

This error occurs when the installer fails to validate the user credentials you have entered on the screen. Make sure that you have entered the credentials properly. If you receive a message similar to this:

```
Error connecting to database URL <url> as user <user>
java.lang.Exception: UnsatisfiedLinkError encountered when using the Oracle
driver.
```

Please check that the library path is set up properly or switch to the JDBC thin client.

It may mean that the installer is using the incorrect library path variables for the platform you are installing on. Open the file

```
<STAGING_DIR>/rms/dbschema/common/preinstall.sh and toggle the variable
"use32bit" to "true" if it is set to "false" or vice versa. This setting is dependant on the
JRE that is being used.
```

Multi-Threaded OCI Client Dumps Core after Reconnecting To Database

Symptom

If a multi-threaded Oracle client process that uses OCI to connect to a remote database loses connectivity with the database, it tries to reconnect and the client program continues to run. The program then dumps the core with the following stack trace, when Automatic Diagnostic Repository (ADR) is enabled.

```
skgfgio sdbgrfbibf_io_block_file dbgrfrbf_read_block_file dbgrmflrp_read_page
dbgrmblgmp_get_many_pages dbgrmmdrrmd_read_relation_meta_data
dbgrmmdora_open_record_access_full
dbgriporc_openrel_wcreate dbgrip_open_relation_access dbgrip_start_iterator
dbgrip_relation_iterator dbgruprac_read_adrctl...
```

Solution

Oracle Retail recommended you disable ADR (`diag_adr_enabled=OFF`, a `sqlnet.ora` parameter) while using multi-threaded OCI/OCCI application. `diag_adr_enabled` was introduced in Oracle 11g as a new method of tracing ADR. This will dump additional trace details.

Disabling '`diag_adr_enabled`' does not disturb any functionality. Therefore, it can safely be unset by doing `diag_adr_enabled=off` in `sqlnet.ora`. However, if you still want tracing, you can have following parameters/variables set in `sqlnet.ora`:

```
trace_level_server=16 -- for server side NET tracing
trace_level_client=16 -- for client side NET tracing
```

For how to set traditional tracing, see the My Oracle Support document, "SQL*Net, Net8, Oracle Net Services - Tracing and Logging at a Glance" (ID 219968.1).

Forms Installer Fails on HP-UX

Symptom

Errors occur during Forms installer screens when run on HP-UX. When you click **Next** on the installer screen, "Data Source Details," the following error is issued: "No ocijdbc11 in java.library.path." The message prevents you from moving to the next screen.

Solution

This error message can be ignored. Verify that the data source details you entered are correct, and uncheck the box labeled **Test Data Source?** The installer screens will not attempt to validate the data source when you click **Next**. The installer will attempt to validate once again when installation starts, and the installer will fail if the credentials are incorrect.

ORFM DB Installer Fails on s11071552_extax_help_gtt_l10n_br.sql after applying hotfix 11071552

Symptom

When running the ORFM 13.2.1 database patch, it fails on the file s11071552_extax_help_gtt_l10n_br.sql:

```
[exec] Executing file s11071552_extax_help_gtt_l10n_br.sql
[exec] ORA Error while executing s11071552_extax_help_gtt_l10n_br.sql
[delete] Deleting directory
/home/waschwar/RFM13.2.1/orfm/dbschemapatch/dblogs/.wallet
```

BUILD FAILED

```
/home/waschwar/RFM13.2.1/orfm/dbschemapatch/build.xml:385: The following error
occurred while executing this line:
/home/waschwar/RFM13.2.1/orfm/dbschemapatch/build.xml:236: The following error
occurred while executing this line:
/home/waschwar/RFM13.2.1/orfm/dbschemapatch/build.xml:175:
/home/waschwar/RFM13.2.1/orfm/dbschemapatch/orfm-
dbpatch/13.2.1/orfm/orfm_controller.ksh has failed. Check error logs in
/home/waschwar/RFM13.2.1/orfm/dbschemapatch/orfm-dbpatch/13.2.1/orfm/error/ for
more details
```

If you look in the file s11071552_extax_help_gtt_l10n_br.err, it reports this error message:

```
Altering table EXTAX_HELP_GTT_L10N_BR
ALTER TABLE EXTAX_HELP_GTT_L10N_BR ADD PACK_NO VARCHAR2(25)
*
ERROR at line 1:
ORA-01430: column being added already exists in table
```

Solution

This error occurs when running the ORFM 13.2.1 database schema patch after applying the required hotfix 11071552. This will fail because dbc's are not rerunnable, and this hotfix contains dbcs that are called by the 13.2.1 patch. To resolve this issue, you must edit the DBC.dat file for ORFM 13.2.1 so that the dbcs contained in the hotfix 11071552 do not run during 13.2.1 installation.

1. Change directories to DB_PATCH_DIR/orfm/dbschemapatch/orfm-dbpatch/13.2.1/orfm/files.
2. Make a backup of the DBC.dat file:


```
$ cp DBC.dat DBC.dat_ORIG
```
3. Open up DBC.dat in a text editor and remove the lines beginning in **s11071552** or **s11071552a**:

```
s11071552_extax_help_gtt_l10n_br.sql
s11071552_extax_res_retail_det_l10n_br.sql
s11071552_extax_res_retail_l10n_br.sql
s11071552_extax_stg_retail_l10n_br.sql
s11071552a_extax_stg_retail_l10n_br.sql
s11071552_extax_res_cost_l10n_br.sql
s11071552_extax_res_cost_det_l10n_br.sql
s11071552_extax_stg_cost_l10n_br.sql
s11071552a_extax_stg_cost_l10n_br.sql
s11802380_fm_ap_stage_detail_hist.sql
s11802380_fm_ap_stage_head_hist.sql
s11802380_fm_fiscal_doc_complement_hist.sql
s11802380_fm_schedule_hist.sql
```

4. DBC.dat should now look like this:
s11802380_fm_ap_stage_detail_hist.sql
s11802380_fm_ap_stage_head_hist.sql
s11802380_fm_fiscal_doc_complement_hist.sql
s11802380_fm_schedule_hist.sql
5. Save and exit. The installation can be rerun after this is done. You should choose to continue the previous install when rerunning the installer.

GUI Screens Fail to Open When Running Installer

Symptom

When running the installer in GUI mode, the screens fail to open and the installer ends, returning to the console without an error message. The ant.install.log file contains this error:

```
Fatal exception: Width (0) and height (0) cannot be <= 0  
java.lang.IllegalArgumentException: Width (0) and height (0) cannot be <= 0
```

Solution


This is an error encountered when Antinstaller is used in GUI mode with certain X Servers. To work around this issue, copy ant.install.properties.sample to ant.install.properties and rerun the installer.

Appendix: Application Deployment Method

The RMS installer provides the option to configure multiple application deployment methods. This is a setup where there is still a single primary RMS installation, but there are additional levels where customization can occur. This means multiple URLs configured in formsweb.cfg with cascading FORMS_PATH values.

The installer provides three choices for cascading environment configuration:

- **Base:** A standard RMS base installation with one application installation folder, and one URL.
- **Production:** Base plus two additional forms directories for PRD and EMG and an additional URL for EMG.
- **Development:** Production plus two additional forms directories for UAT and DEV and two additional URLs for UAT and DEV.



The above diagrams show how the application deployment method environment configurations are set up in the forms installation.

The installer creates the set of URLs, and empty directories for the other environments. All forms installed by this installer are placed in the “Base” environment. We are simply laying down the structure for customizations and fixes that the user can make after installation is complete.

Appendix: Single Sign-On Resource Access Descriptors

Oracle Forms applications such as RMS use database connections for authentication and authorization purposes. Oracle Single Sign-On, however, uses the Oracle Internet Directory (OID) user ID and password for this purpose. The Forms framework maps OID user IDs to database connections via information stored in Resource Access Descriptors (RADs). A user will have one RAD for each application accessed. RADs may be created by an administrator or by an LDIF script. Depending on the Oracle Internet Directory and/or the formsweb.cfg configuration, RADs may also be created by the user.

A user is prompted for the database connection information whenever formsweb.cfg file specifies ssoMode = true and createDynamicResources = true for an application and no valid RAD exists. RADs may become invalid when passwords have expired or have been changed.

RADs may be created by administrators or users via the Delegated Administration Services application.

Note: Users can create new RADs only if one or more RADs already exist.

RADs may be created and via LDIF scripts as well. See My Oracle Support document 244526.1.

Appendix: RMS RETL Instructions

This Appendix summarizes the RETL program features utilized in the RMS Extractions (RMS ETL). More information about the RETL tool is available in the *Oracle Retail Extract, Transform, and Load Programmer's Guide*. More information about RMS ETL is available in the RMS ETL operations guide.

Configuration

The following are configuration instructions.

RETL

Before attempting to configure and run RMS ETL, install RETL version 10.3 or later which is required to run RMS ETL. Run the `verify_retl` script (included as part of the RETL installation) to ensure that RETL is working properly before proceeding.

RETL User and Permissions

RMS ETL should be installed and run as the RETL user. Additionally, the permissions should be set up as per the *Oracle Retail Extract, Transform, and Load Programmer's Guide*. RMS ETL reads data, creates, deletes and updates tables. (This is to ensure that weekly sales data is not pulled multiple times on subsequent extractions.) If these permissions are not set up properly, extractions will fail.

Environment Variables

In addition to the RETL environment variables (please see the Programmer's Guide for version of RETL), you need to set `MMHOME` to the base directory for RMS ETL. This is the top level directory that selected during the RMS Batch installation process. So in `.kshrc` you should add a line like the following:

```
export MMHOME=<base directory for RMS ETL>
```

`rmse_config.env`

There are a couple variables that will need to change depending upon local settings:

```
export DBNAME=pk01s05
export RMS_OWNER=rms01
export BA_OWNER=rms01
```

Also, you will need to set the environment variable `PASSWORD` in either the `rmse_config.env`, `.kshrc` or some other location that can be included via one of those two means. For example, adding this line to the `rmse_config.env` will cause the password "bogus" to be used to log into the database: `export PASSWORD=pass1`

Appendix: Setting Up Password Stores with Oracle Wallet

As part of an application installation, administrators must set up password stores for database user accounts using Oracle Wallet. These password stores must be installed on the application database side. While the installer handles much of this process, the administrators must perform some additional steps.

A password store for the application and application server user accounts must also be installed; however, the installer takes care of this entire process.

About Password Stores and Oracle Wallet

Oracle databases have allowed other users on the server to see passwords in case database connect strings (username/password@db) were passed to programs. In the past, users could navigate to `ps -ef | grep <username>` to see the password if the password was supplied in the command line when calling a program.

To make passwords more secure, Oracle Retail has implemented the Oracle Software Security Assurance (OSSA) program. Sensitive information such as user credentials now must be encrypted and stored in a secure location. This location is called password stores or wallets. These password stores are secure software containers that store the encrypted user credentials.

Users can retrieve the credentials using aliases that were set up when encrypting and storing the user credentials in the password store. For example, if `username/password@db` is entered in the command line argument and the alias is called `db_username`, the argument to a program is as follows:

```
sqlplus /@db_username
```

This would connect to the database as it did previously, but it would hide the password from any system user.

After this is configured, as in the example above, the application installation and the other relevant scripts are no longer needed to use embedded usernames and passwords. This reduces any security risks that may exist because usernames and passwords are no longer exposed.

When the installation starts, all the necessary user credentials are retrieved from the Oracle Wallet based on the alias name associated with the user credentials.

There are two different types of password stores or wallets. One type is for database connect strings used in program arguments (such as `sqlplus /@db_username`). The other type is for Java application installation and application use.

Setting Up Password Stores for Database User Accounts

After the database is installed and the default database user accounts are set up, administrators must set up a password store using the Oracle wallet. This involves assigning an alias for the username and associated password for each database user account. The alias is used later during the application installation. This password store must be created on the system where the application server and database client are installed.

This section describes the steps you must take to set up a wallet and the aliases for the database user accounts. For more information on configuring authentication and password stores, see the *Oracle Database Security Guide*.

Note: In this section, <wallet_location> is a placeholder text for illustration purposes. Before running the command, ensure that you specify the path to the location where you want to create and store the wallet.

To set up a password store for the database user accounts, perform the following steps:

1. Create a wallet using the following command:

```
mkstore -wrl <wallet_location> -create
```

After you run the command, a prompt appears. Enter a password for the Oracle Wallet in the prompt.

Note: The `mkstore` utility is included in the Oracle Database Client installation.

The wallet is created with the auto-login feature enabled. This feature enables the database client to access the wallet contents without using the password. For more information, refer to the *Oracle Database Advanced Security Administrator's Guide*.

2. Create the database connection credentials in the wallet using the following command:

```
mkstore -wrl <wallet_location> -createCredential <alias-name> <database-user-name>
```

After you run the command, a prompt appears. Enter the password associated with the database user account in the prompt.

3. Repeat Step 2 for all the database user accounts.
4. Update the `sqlnet.ora` file to include the following statements:

```
WALLET_LOCATION = (SOURCE = (METHOD = FILE) (METHOD_DATA = (DIRECTORY =
<wallet_location>)))
SQLNET.WALLET_OVERRIDE = TRUE
SSL_CLIENT_AUTHENTICATION = FALSE
```

5. Update the `tnsnames.ora` file to include the following entry for each alias name to be set up.

```
<alias-name> =
  (DESCRIPTION =
    (ADDRESS_LIST =
      (ADDRESS = (PROTOCOL = TCP) (HOST = <host>) (PORT = <port>))
    )
    (CONNECT_DATA =
      (SERVICE_NAME = <service>)
    )
  )
```

In the previous example, <alias-name>, <host>, <port>, and <service> are placeholder text for illustration purposes. Ensure that you replace these with the relevant values.

Setting Up Wallets for Database User Accounts

The following examples show how to set up wallets for database user accounts for the following applications:

- For RMS, RWMS, RPM Batch, RETL, RMS, RWMS, and ARI
- For Java Applications (SIM, ReIM, RPM, Alloc, RIB, RSL, AIP, RETL)

For RMS, RPM Plsql Batch, RETL DB, RWMS batch, and ARI

1. Create a new directory called wallet under your folder structure.

```
cd /projects/rms13.2/dev/
mkdir .wallet
```

Note: The default permissions of the wallet allow only the owner to use it, ensuring the connection information is protected. If you want other users to be able to use the connection, you must adjust permissions appropriately to ensure only authorized users have access to the wallet.

2. Create a sqlnet.ora in the wallet directory with the following content.

```
WALLET_LOCATION = (SOURCE = (METHOD = FILE) (METHOD_DATA =
(DIRECTORY = /projects/rms13.2/dev/.wallet)) )
SQLNET.WALLET_OVERRIDE=TRUE
SSL_CLIENT_AUTHENTICATION=FALSE
```

Note: WALLET_LOCATION must be on line 1 in the file.

3. Setup a tnsnames.ora in the wallet directory. This tnsnames.ora includes the standard tnsnames.ora file. Then, add two custom tns_alias entries that are only for use with the wallet. For example, sqlplus /@dvols29_rms01user.

```
ifile = /u00/oracle/product/11.2.0.1/network/admin/tnsnames.ora
```

```
dvols29_rms01user =
(DESCRIPTION = (ADDRESS_LIST = (ADDRESS = (PROTOCOL = tcp)
(host = mspdv311.us.oracle.com) (Port = 1521)))
(CONNECT_DATA = (SID = dvols29) (GLOBAL_NAME = dvols29)))
```

```
dvols29_rms01user.world =
(DESCRIPTION = (ADDRESS_LIST = (ADDRESS = (PROTOCOL = tcp)
(host = mspdv311.us.oracle.com) (Port = 1521)))
(CONNECT_DATA = (SID = dvols29) (GLOBAL_NAME = dvols29)))
```

Note: It is important to not just copy the tnsnames.ora file because it can quickly become out of date. The ifile clause (shown above) is key.

4. Create the wallet files. These are empty initially.
 - a. Ensure you are in the intended location.

```
$ pwd
/projects/rms13.2/dev/.wallet
```

- b. Create the wallet files.

```
$ mkstore -wrl . -create
```

- c. Enter the wallet password you want to use. It is recommended that you use the same password as the UNIX user you are creating the wallet on.

- d. Enter the password again.

Two wallet files are created from the above command:

- ewallet.p12
- cwallet.sso

5. Create the wallet entry that associates the user name and password to the custom tns alias that was setup in the wallet's tnsnames.ora file.

```
mkstore -wrl . -createCredential <tns_alias> <username> <password>
```

Example: mkstore -wrl . -createCredential
dvols29_rms01user rms01user passwd

6. Test the connectivity. The ORACLE_HOME used with the wallet must be the same version or higher than what the wallet was created with.

```
$ export TNS_ADMIN=/projects/rms13.2/dev/.wallet /* This is very import to use wallet to point at the alternate tnsnames.ora created in this example */
```

```
$ sqlplus /@dvols29_rms01user
```

```
SQL*Plus: Release 11
```

```
Connected to:  
Oracle Database 11g
```

```
SQL> show user  
USER is "rms01user"
```

Running batch programs or shell scripts would be similar:

```
Ex: dtesys /@dvols29_rms01user  
script.sh /@dvols29_rms01user
```

Set the UP unix variable to help with some compiles :

```
export UP=@dvols29_rms01user  
for use in RMS batch compiles, and RMS, RWMS, and ARI forms compiles.
```

As shown in the example above, users can ensure that passwords remain invisible.

Additional Database Wallet Commands

The following is a list of additional database wallet commands.

- Delete a credential on wallet

```
mkstore -wrl . -deleteCredential dvols29_rms01user
```

- Change the password for a credential on wallet

```
mkstore -wrl . -modifyCredential dvols29_rms01user rms01user passwd
```

- List the wallet credential entries
`mkstore -wrl . -list`
 This command returns values such as the following.
`oracle.security.client.connect_string1`
`oracle.security.client.user1`
`oracle.security.client.password1`
- View the details of a wallet entry
`mkstore -wrl . -viewEntry oracle.security.client.connect_string1`
 Returns the value of the entry:
`dvo1s29_rms01user`
`mkstore -wrl . -viewEntry oracle.security.client.user1`
 Returns value of the entry:
`rms01user`

`mkstore -wrl . -viewEntry oracle.security.client.password1`
 Returns value of the entry:
`passwd`

For Java Applications (SIM, ReIM, RPM, Alloc, RIB, RSL, AIP, RETL)

For Java application, consider the following:

- For database user accounts, ensure that you set up the same alias names between the password stores (database wallet and Java wallet). You can provide the alias name during the installer process.
- Document all aliases that you have set up. During the application installation, you must enter the alias names for the application installer to connect to the database and application server.
- Passwords are not used to update entries in Java wallets. Entries in Java wallets are stored in partitions, or application-level keys. In each retail application that has been installed, the wallet is located in
`<WEBLOGIC_DOMAIN_HOME>/retail/<appname>/config` Example:
`mspdV351:[1033_WLS] /u00/webadmin/product/10.3.3/WLS/user_projects/`
`domains/132_mck_soa_domain/retail/reim13/config`
- Application installers should create the Java wallets for you, but it is good to know how this works for future use and understanding.
- Scripts are located in `<WEBLOGIC_DOMAIN_HOME>/retail/<appname>/retail-public-security-api/bin` for administering wallet entries.
 Example:
`mspdV351:[1033_WLS] /u00/webadmin/product/10.3.3/WLS/user_projects/`
`domains/132_mck_soa_domain/retail/reim13/retail-public-security-api/bin`
- In this directory is a script to help you update each alias entry without having to remember the wallet details. For example, if you set the RPM database alias to `rms01user`, you will find a script called `update-RMS01USER.sh`.

Note: These scripts are available only with application installed by way of an installer.

- Two main scripts are related to this script in the folder for more generic wallet operations: `dump_credentials.sh` and `save_credential.sh`.

- If you have not installed the application yet, you can unzip the application zip file and view these scripts in <app>/application/retail-public-security-api/bin.

Example:

```
mspdev351:[1033_WLS] /u00/webadmin/reim/application/retail-public-security-api/bin
```

update-<ALIAS>.sh

update-<ALIAS>.sh updates the wallet entry for this alias. You can use this script to change the user name and password for this alias. Because the application refers only to the alias, no changes are needed in application properties files.

Usage:

```
update-<username>.sh <myuser>
```

Example:

```
mspdev71:[1034WLS]
/u00/webadmin/product/10.3.4/WLS/user_projects/domains/java_domain/retail/rpml
32test/retail-public-security-api/bin> ./update-RMS01USER.sh
usage: update-RMS01USER.sh <username>
```

<username>: the username to update into this alias.

Example: update-RMS01USER.sh myuser

Note: this script will ask you for the password for the username that you pass in.

```
mspdev71:[1034WLS]
/u00/webadmin/product/10.3.4/WLS/user_projects/domains/java_domain/retail/rpml
32test/retail-public-security-api/bin>
```

dump_credentials.sh

dump_credentials.sh is used to retrieve information from the wallet. For each entry found in the wallet, the wallet partition, the alias, and the user name are displayed. Note that the password is not displayed. If the value of an entry is uncertain, run save_credential.sh to resave the entry with a known password.

```
dump_credentials.sh <wallet location>
```

Example:

```
dump_credentials.sh
/u00/webadmin/product/10.3.3/WLS/user_projects/domains/132_mck_soa_domain/retail/reim13/config
```

```
Retail Public Security API Utility
```

```
=====
```

```
Below are the credentials found in the wallet at the
location:/u00/webadmin/product/10.3.3/WLS/user_projects/domains/132_mck_soa_domain/retail/reim13/config
```

```
=====
```

```
Apapplication level key partition name:reim13
User Name Alias:WLS-ALIAS User Name:weblogic
User Name Alias:RETAIL-ALIAS User Name:retail.user
User Name Alias:LDAP-ALIAS User Name:RETAIL.USER
User Name Alias:RMS-ALIAS User Name:rms132mock
User Name Alias:REIMBAT-ALIAS User Name:reimbat
```

save_credential.sh

save_credential.sh is used to update the information in wallet. If you are unsure about the information that is currently in the wallet, use dump_credentials.sh as indicated above. You can add new or update using save_credential.sh as shown below:

```
save_credential.sh -a <alias> -u <user> -p <partition name> -l <path of the
wallet file location where credentials are stored>
```

Example:

```
mospdv351:[1033_WLS]
/u00/webadmin/mock132_testing/rtil/rtil/application/retail-public-security-
api/bin> save_credential.sh -l
/u00/webadmin/product/10.3.3/WLS/user_projects/domains/132_mck_soa_domain/reta
il/reiml3/config
-a RMS-ALIAS -p reiml3 -u rms132mock
```

```
=====
Retail Public Security API Utility
=====
```

```
Enter password:
Verify password:
```

Note: -p in the above command is for partition name. You must specify the proper partition name used in application code for each Java application.

save_credential.sh and dump_credentials.sh scripts are the same for all applications. If using save_credential.sh to add a wallet entry or to update a wallet entry, bounce the application/managed server so that your changes are visible to the application. Also, save a backup copy of your cwallet.sso file in a location outside of the deployment path, because redeployment or reinstallation of the application will wipe the wallet entries you made after installation of the application. To restore your wallet entries after a redeployment/reinstallation, copy the backed up cwallet.sso file over the cwallet.sso file. Then bounce the application/managed server.

Usage

```
=====
Retail Public Security API Utility
=====
usage: save_credential.sh -au[plh]
E.g. save_credential.sh -a rms-alias -u rms_user -p rib-rms -l ./
-a,--userNameAlias <arg>          alias for which the credentials
needs to be stored
-h,--help                          usage information
-l,--locationofWalletDir <arg>    location where the wallet file is
created.If not specified, it creates the wallet under secure-credential-wallet
directory which is already present under the retail-public-security-api/
directory.
-p,--appLevelKeyPartitionName <arg> application level key partition name
-u,--userName <arg>              username to be stored in secure
credential wallet for specified alias*
```

How Does the Wallet Relate to the Application?

The ORACLE Retail Java applications have the wallet alias information you create in an <app-name>.properties file. Below is the reim.properties file. Note the database information and the user are presented as well. The property called `datasource.credential.alias=RMS-ALIAS` uses the ORACLE wallet with the argument of RMS-ALIAS at the `cs.m.wallet.path` and `cs.m.wallet.partition.name = reim13` to retrieve the password for application use.

Reim.properties code sample:

```
datasource.url=jdbc:oracle:thin:@mspdv349.us.oracle.com:1521:pkols07
datasource.schema.owner=rms132mock
datasource.credential.alias=RMS-ALIAS
# =====
# ossa related Configuration
#
# These settings are for ossa configuration to store credentials.
# =====

cs.m.wallet.path=/u00/webadmin/product/10.3.3/WLS/user_projects/domains/132_mck_soa
_domain/retail/reim13/config
cs.m.wallet.partition.name=reim13
```

How Does the Wallet Relate to Java Batch Program Use?

Some of the ORACLE Retail Java batch applications have an alias to use when running Java batch programs. For example, alias REIMBAT-ALIAS maps through the wallet to REIM app user reimbat, already on the database. To run a ReIM batch program the format would be: `reimbatchpgmname REIMBAT-ALIAS <other arguments as needed by the program in question>`.

Setting Up RETL Wallets

RETL 13.2 creates a wallet under `$RFX_HOME/etc/security`, with the following files:

- `cwallet.sso`
- `jazn-data.xml`
- `jps-config.xml`
- `README.txt`

To set up RETL wallets, perform the following steps:

1. Set the following environment variables:
 - `ORACLE_SID=<retaildb>`
 - `RFX_HOME=/u00/rfx/rfx-13.2.0`
 - `RFX_TMP=/u00/rfx/rfx-13.2.0/tmp`
 - `JAVA_HOME=/usr/jdk1.6.0_12.64bit`
 - `LD_LIBRARY_PATH=$ORACLE_HOME`
 - `PATH=$RFX_HOME/bin:$JAVA_HOME/bin:$PATH`
2. Change directory to `$RFX_HOME/bin`.
3. Run `setup-security-credential.sh`.
 - Enter 1 to add a new database credential.
 - Enter the dbuseralias. For example, `retl_java_rms01user`.
 - Enter the database user name. For example, `rms01user`.
 - Enter the database password.

- Re-enter the database password.
 - Enter D to exit the setup script.
4. Update your RETL environment variable script to reflect the names of both the Oracle Networking wallet and the Java wallet.
- For example, to configure RETLforRPAS, modify the following entries in `$MMHOME/RETLforRPAS/rfx/etc/rmse_rpas_config.env`.
- The RETL_WALLET_ALIAS should point to the Java wallet entry:
`export RETL_WALLET_ALIAS="retl_java_rms01user"`
 - The ORACLE_WALLET_ALIAS should point to the Oracle network wallet entry:
`export ORACLE_WALLET_ALIAS="dvo1s29_rms01user"`
 - The SQLPLUS_LOGON should use the ORACLE_WALLET_ALIAS:
`export SQLPLUS_LOGON="/@${ORACLE_WALLET_ALIAS}"`
5. To change a password later, run `setup-security-credential.sh`.
- Enter 2 to update a database credential.
 - Select the credential to update.
 - Enter the database user to update or change.
 - Enter the password of the database user.
 - Re-enter the password.

Quick Guide for Retail Wallets

Retail App	Wallet Type	Wallet Location	Wallet Partition	Alias Name	User Name	Use	Create By	Alias Example	Notes
RMS batch	DB	<RMS batch install dir (MMHOME)>/.wallet	n/a	<Database SID>_<Database schema owner>	<rms schema owner>	Compile, execution	Installer	n/a	Alias hard-coded by installer
RMS forms	DB	<forms install dir>/base/.wallet	n/a	<Database SID>_<Database schema owner>	<rms schema owner>	Compile	Installer	n/a	Alias hard-coded by installer
ARI forms	DB	<forms install dir>/base/.wallet	n/a	<Db_Ari01>	<ari schema owner>	Compile	Manual	ari-alias	
RMWS forms	DB	<forms install dir>/base/.wallet	n/a	<Database SID>_<Database schema owner>	<rwms schema owner>	Compile forms, execute batch	Installer	n/a	Alias hard-coded by installer
RPM app	DB	<RPM batch install dir>/.wallet	n/a	<rms schema owner alias>	<rms schema owner>	Execute batch	Manual	rms-alias	
RWMS auto-login	JAVA	<forms install dir>/base/.javawallet							
			<RWMS Installation name>	<RWMS database user alias>	<RWMS schema owner>	RWMS forms app to avoid dblogin screen	Installer	rwms13inst	
			<RWMS Installation name>	BI_ALIAS	<BI Publisher administrative user>	RWMS forms app to connect to BI Publisher	Installer	n/a	Alias hard-coded by installer
AIP app	JAVA	<weblogic domain home>/retail/<deployed aip app name>/config							Each alias must be unique
			aip13	<AIP weblogic user alias>	<AIP weblogic user name>	App use	Installer	aip-weblogic-alias	
			aip13	<AIP database schema user alias>	<AIP database schema user name>	App use	Installer	aip01user-alias	

Retail App	Wallet Type	Wallet Location	Wallet Partition	Alias Name	User Name	Use	Create By	Alias Example	Notes
			aip13	<rib-aip weblogic user alias>	<rib-aip weblogic user name>	App use	Installer	rib-aip- weblogic- alias	
RPM app	JAVA	<weblogic domain home>/retail/<deployed rpm app name>/config							Each alias must be unique
			rpm13	<rpm weblogic user alias>	<rpm weblogic user name>	App use	Installer	rpm- weblogic- alias	
			rpm13	<rms shema user alias>	<rms shema user name>	App, batch use	Installer	rms01user- alias	
			rpm13	<rpm application user one alias>	<rpm application user one name>	App use	Installer	user1-alias	
			rpm13	<rpm application user two alias>	<rpm application user two name>	App use	Installer	user2-alias	
			rpm13	<rpm batch user alias>	<rpm batch user name>	App, batch use	Installer	rpmbatch- alias	
			rpm13	<rib-rpm weblogic user alias>	<rib-rpm weblogic user name>	App use	Installer	rib-rpm- weblogic- alias	
ReIM app	JAVA	<weblogic domain home>/retail/<deployed reim app name>/config							Each alias must be unique
			<installed app name>	<reim weblogic user alias>	<reim weblogic user name>	App use	Installer	weblogic- alias	
			<installed app name>	<rms shema user alias>	<rms shema user name>	App, batch use	Installer	rms01user- alias	
			<installed app name>	<reim webservice validation user alias>	<reim webservice validation user name>	App use	Installer	reimwebser vice-alias	
			<installed app name>	<reim batch user alias>	<reim batch user name>	App, batch use	Installer	reimbatch- alias	

Retail App	Wallet Type	Wallet Location	Wallet Partition	Alias Name	User Name	Use	Create By	Alias Example	Notes
Alloc app	JAVA	<weblogic domain home>/retail/<deployed alloc app name>/config							Each alias must be unique
			<installed app name>	<alloc weblogic user alias>	<alloc weblogic user name>	App use	Installer	weblogic-alias	
			<installed app name>	<rms shema user alias>	<rms shema user name>	App use	Installer	rms01user-alias	
			<installed app name>	<rsl for rms weblogic user alias>	<rsl for rms weblogic user name>	App use	Installer	rsl-rms-weblogic-alias	
RSL app	JAVA	<RSL INSTALL DIR>/rsl-rms/security/config							Each alias must be unique
			rsl-rsm	<rsl weblogic user alias>	<rsl weblogic user name>	App use	Installer	weblogic-alias	
			rsl-rsm	<rms shema user alias>	<rms shema user name>	App use	Installer	rms01user-alias	
SIM app	JAVA	<weblogic domain home>/retail/<deployed sim app name>/config							
			rpm	<rpm weblogic user alias>	<rpm weblogic user name>	App use	Installer	rpm-weblogic-alias	
			rms	<rsl for rms weblogic user alias>	<rsl for rms weblogic user name>	App use	Installer	rsl-rms-weblogic-alias	
			rib-sim	<rib-sim weblogic user alias>	<rib-sim weblogic user name>	App use	Installer	rib-sim-weblogic-alias	
RETL	JAVA	<RETL home>/etc/security	n/a	<target application user alias>	<target application db userid>	App use	Manual	retl_java_rms01user	User may vary depending on RETL flow's target application

Retail App	Wallet Type	Wallet Location	Wallet Partition	Alias Name	User Name	Use	Create By	Alias Example	Notes
RETL	DB	<RETL home>/wallet	n/a	<target application user alias>	<target application db userid>	App use	Manual	<db>_ <user>	User may vary depending on RETL flow's target application
RIB	JAVA	<RIBHOME DIR>/deployment-home/conf/security							<app> is one of aip, rfm, rms, rpm, sim, rwms, tafr
JMS			jms<1-5>	<jms user alias> for jms<1-5>	<jms user name> for jms<1-5>	Integration use	Installer	jms-alias	
Weblogic			rib-<app>-app-server-instance	<rib-app weblogic user alias>	<rib-app weblogic user name>	Integration use	Installer	weblogic-alias	
Admin GUI			rib-<app>#web-app-user-alias	<rib-app admin gui user alias>	<rib-app admin gui user name>	Integration use	Installer	admin-gui-alias	
Application			rib-<app>#user-alias	<app weblogic user alias>	<app weblogic user name>	Integration use	Installer	app-user-alias	Valid only for aip, rpm, sim
DB			rib-<app>#app-db-user-alias	<rib-app database schema user alias>	<rib-app database schema user name>	Integration use	Installer	db-user-alias	Valid only for rfm, rms, rwms, tafr
Error Hospital			rib-<app>#hosp-user-alias	<rib-app error hospital database schema user alias>	<rib-app error hospital database schema user name>	Integration use	Installer	hosp-user-alias	

Appendix: Installation Order

This section provides a guideline as to the order in which the Oracle Retail applications should be installed. If a retailer has chosen to use only some of the applications, the order is still valid, less the applications not being installed.

Note: The installation order is not meant to imply integration between products.

Enterprise Installation Order

1. Oracle Retail Merchandising System (RMS), Oracle Retail Trade Management (RTM), Oracle Retail Sales Audit (ReSA). Optional: Oracle Retail Fiscal Management (ORFM)

Note: ORFM is an optional application for RMS if you are implementing Brazil localization.

2. Oracle Retail Service Layer (RSL)
3. Oracle Retail Extract, Transform, Load (RETL)
4. Oracle Retail Active Retail Intelligence (ARI)
5. Oracle Retail Warehouse Management System (RWMS)
6. Oracle Retail Invoice Matching (ReIM)
7. Oracle Retail Price Management (RPM)

Note: During installation of RPM, you are asked for the RIBforRPM provider URL. Because RIB is installed after RPM, make a note of the URL you enter. To change the RIBforRPM provider URL after you install RIB, edit the `remote_service_locator_info_ribserver.xml` file.

8. Oracle Retail Allocation
9. Oracle Retail Central Office (ORCO)
10. Oracle Retail Returns Management (ORRM)
11. Oracle Retail Back Office (ORBO) or Back Office with Labels and Tags (ORLAT)
12. Oracle Retail Store Inventory Management (SIM)

Note: During installation of SIM, you are asked for the RIB provider URL. Because RIB is installed after SIM, make a note of the URL you enter. To change the RIB provider URL after you install RIB, edit the `remote_service_locator_info_ribserver.xml` file.

13. Oracle Retail Predictive Application Server (RPAS)
14. Oracle Retail Demand Forecasting (RDF)
15. Oracle Retail Category Management (CM)
16. Oracle Retail Replenishment Optimization (RO)
17. Oracle Retail Analytic Parameter Calculator Replenishment Optimization (APC RO)

18. Oracle Retail Regular Price Optimization (RPO)
19. Oracle Retail Merchandise Financial Planning (MFP)
20. Oracle Retail Size Profile Optimization (SPO)
21. Oracle Retail Assortment Planning (AP)
22. Oracle Retail Item Planning (IP)
23. Oracle Retail Item Planning Configured for COE (IP COE)
24. Oracle Retail Advanced Inventory Planning (AIP)
25. Oracle Retail Integration Bus (RIB)
26. Oracle Retail Point-of-Service (ORPOS)
27. Oracle Retail Markdown Optimization (MDO)
28. Oracle Retail Clearance Optimization Engine (COE)
29. Oracle Retail Analytic Parameter Calculator for Markdown Optimization (APC-MDO)
30. Oracle Retail Analytic Parameter Calculator for Regular Price Optimization (APC-RPO)
31. Oracle Retail Promotion Intelligence and Promotion Planning and Optimization (PI-PPO)
32. Oracle Retail Analytics
33. Oracle Retail Workspace (ORW)