

# **Oracle® Retail Service Layer**

Installation Guide

Release 13.2.5

E37578-01

October 2012

Copyright © 2012, Oracle. All rights reserved.

Primary Author: Nathan Young

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

## Value-Added Reseller (VAR) Language

### Oracle Retail VAR Applications

The following restrictions and provisions only apply to the programs referred to in this section and licensed to you. You acknowledge that the programs may contain third party software (VAR applications) licensed to Oracle. Depending upon your product and its version number, the VAR applications may include:

- (i) the **MicroStrategy** Components developed and licensed by MicroStrategy Services Corporation (MicroStrategy) of McLean, Virginia to Oracle and imbedded in the MicroStrategy for Oracle Retail Data Warehouse and MicroStrategy for Oracle Retail Planning & Optimization applications.
- (ii) the **Wavelink** component developed and licensed by Wavelink Corporation (Wavelink) of Kirkland, Washington, to Oracle and imbedded in Oracle Retail Mobile Store Inventory Management.
- (iii) the software component known as **Access Via**™ licensed by Access Via of Seattle, Washington, and imbedded in Oracle Retail Signs and Oracle Retail Labels and Tags.
- (iv) the software component known as **Adobe Flex**™ licensed by Adobe Systems Incorporated of San Jose, California, and imbedded in Oracle Retail Promotion Planning & Optimization application.

You acknowledge and confirm that Oracle grants you use of only the object code of the VAR Applications. Oracle will not deliver source code to the VAR Applications to you. Notwithstanding any other term or condition of the agreement and this ordering document, you shall not cause or permit alteration of any VAR Applications. For purposes of this section, "alteration" refers to all alterations, translations, upgrades, enhancements, customizations or modifications of all or any portion of the VAR Applications including all reconfigurations, reassembly or reverse assembly, re-engineering or reverse engineering and recompilations or reverse compilations of the VAR Applications or any derivatives of the VAR Applications. You acknowledge that it shall be a breach of the agreement to utilize the relationship, and/or confidential information of the VAR Applications for purposes of competitive discovery.

The VAR Applications contain trade secrets of Oracle and Oracle's licensors and Customer shall not attempt, cause, or permit the alteration, decompilation, reverse engineering, disassembly or other reduction of the VAR Applications to a human perceivable form. Oracle reserves the right to replace, with functional equivalent software, any of the VAR Applications in future releases of the applicable program.



---

---

# Contents

|                                                                                                   |            |
|---------------------------------------------------------------------------------------------------|------------|
| <b>Send Us Your Comments .....</b>                                                                | <b>vii</b> |
| <b>Preface .....</b>                                                                              | <b>ix</b>  |
| Audience .....                                                                                    | ix         |
| Related Documents .....                                                                           | ix         |
| Customer Support .....                                                                            | ix         |
| Review Patch Documentation .....                                                                  | ix         |
| Oracle Retail Documentation on the Oracle Technology Network .....                                | x          |
| Conventions .....                                                                                 | x          |
| <b>1 Preinstallation Tasks .....</b>                                                              | <b>1</b>   |
| Check for the Current Version of the Installation Guide .....                                     | 1          |
| Check Application Server Requirements .....                                                       | 1          |
| Check Oracle Retail Software Dependencies .....                                                   | 2          |
| UNIX User Account Privileges to Install the Software .....                                        | 3          |
| Moving the RSL Packaged .jars to the Server Library .....                                         | 3          |
| Configure the rsl-rms-wls-instance .....                                                          | 3          |
| <b>2 Application Installation .....</b>                                                           | <b>7</b>   |
| Create a Managed Server for RSLforRMS .....                                                       | 7          |
| Expand the RSLforRMS Distribution .....                                                           | 8          |
| Run the RSLforRMS Installer .....                                                                 | 8          |
| Resolving Errors Encountered During Application Installation .....                                | 9          |
| Backups Created by Installer .....                                                                | 9          |
| <b>A Appendix: RSLforRMS Installer Screens .....</b>                                              | <b>11</b>  |
| <b>B Appendix: Common Installation Errors .....</b>                                               | <b>17</b>  |
| Unreadable Buttons in the Installer .....                                                         | 17         |
| Warning: Could not create system preferences directory .....                                      | 17         |
| ConcurrentModificationException in Installer GUI .....                                            | 17         |
| Warning: Could not find X Input Context .....                                                     | 18         |
| Files not available to copy at the end of installation, results in non working applications ..... | 18         |
| Installer Fails because of missing .jar in \$ORACLE_HOME/utls/ccr/lib .....                       | 18         |
| GUI screens fail to open when running Installer .....                                             | 19         |
| <b>C Appendix: URL Reference .....</b>                                                            | <b>21</b>  |
| JDBC URL for a Database .....                                                                     | 21         |
| <b>D Appendix: Setting Up Password Stores with Oracle Wallet .....</b>                            | <b>23</b>  |
| About Password Stores and Oracle Wallet .....                                                     | 23         |
| Setting Up Password Stores for Database User Accounts .....                                       | 24         |
| Setting Up Wallets for Database User Accounts .....                                               | 25         |
| For RMS, RPM Plsql Batch, RETL DB, RWMS batch, and ARI .....                                      | 25         |
| For Java Applications (SIM, ReIM, RPM, Alloc, RIB, RSL, AIP, RETL) .....                          | 27         |

|                                                             |           |
|-------------------------------------------------------------|-----------|
| How Does the Wallet Relate to the Application? .....        | 30        |
| How Does the Wallet Relate to Java Batch Program Use? ..... | 30        |
| Setting up RETL Wallets .....                               | 31        |
| Quick Guide for Retail Wallets .....                        | 33        |
| <b>E Appendix: Installation Order .....</b>                 | <b>39</b> |
| Enterprise Installation Order.....                          | 39        |

---

---

# Send Us Your Comments

Oracle Retail Service Layer Installation Guide, Release 13.2.5

Oracle welcomes customer comments and suggestions on the quality and usefulness of this document.

Your feedback is important, and helps us to best meet your needs as a user of our products. For example:

- Are the implementation steps correct and complete?
- Did you understand the context of the procedures?
- Did you find any errors in the information?
- Does the structure of the information help you with your tasks?
- Do you need different information or graphics? If so, where, and in what format?
- Are the examples correct? Do you need more examples?

If you find any errors or have any other suggestions for improvement, then please tell us your name, the name of the company who has licensed our products, the title and part number of the documentation and the chapter, section, and page number (if available).

---

**Note:** Before sending us your comments, you might like to check that you have the latest version of the document and if any concerns are already addressed. To do this, access the Online Documentation available on the Oracle Technology Network Web site. It contains the most current Documentation Library plus all documents revised or released recently.

---

Send your comments to us using the electronic mail address: [retail-doc\\_us@oracle.com](mailto:retail-doc_us@oracle.com)

Please give your name, address, electronic mail address, and telephone number (optional).

If you need assistance with Oracle software, then please contact your support representative or Oracle Support Services.

If you require training or instruction in using Oracle software, then please contact your Oracle local office and inquire about our Oracle University offerings. A list of Oracle offices is available on our Web site at [www.oracle.com](http://www.oracle.com).





---

---

# Preface

The Oracle Retail Service Layer development team delivers RSL applications only for non-Java/Java EE service providers such as RMS (Oracle Forms based). Other implementations of RSL exist but are bundled within other Oracle Retail Java EE applications and are installed as part of those applications. Currently RSL provides an implementation for integrating applications with RMS. RPM is the only Oracle Retail Java EE application that includes an integrated implementation of RSL.

An application-specific version of RSL in a Java EE environment is referred to as RSLfor<App> (for this release only RSLforRMS). This application is packaged as an EAR file that must be deployed in an application server. Currently, RSL applications have been certified to install and execute in Oracle Fusion Middleware 11g Release 1 (11.1.1.6) /Oracle WebLogic Server 11g Release 1 (10.3.6).

## Audience

This manual is designed for System Administrators, Developers, and Applications Support personnel installing the RSL for RMS implementation provided by the RSL team.

## Related Documents

For more information, see the following documents in the Oracle Retail Service Layer Release 13.2.5 documentation set:

- *Oracle Retail Service Layer Release Notes*

## Customer Support

To contact Oracle Customer Support, access My Oracle Support at the following URL:  
<https://support.oracle.com>

When contacting Customer Support, please provide the following:

- Product version and program/module name
- Functional and technical description of the problem (include business impact)
- Detailed step-by-step instructions to re-create
- Exact error message received
- Screen shots of each step you take

## Review Patch Documentation

When you install the application for the first time, you install either a base release (for example, 13.2) or a later patch release (for example, 13.2.1). If you are installing the base release and additional patch and bundled hot fix releases, read the documentation for all releases that have occurred since the base release before you begin installation.

Documentation for patch and bundled hot fix releases can contain critical information related to the base release, as well as information about code changes since the base release.

---

## Oracle Retail Documentation on the Oracle Technology Network

Documentation is packaged with each Oracle Retail product release. Oracle Retail product documentation is also available on the following Web site:

[http://www.oracle.com/technology/documentation/oracle\\_retail.html](http://www.oracle.com/technology/documentation/oracle_retail.html)

(Data Model documents are not available through Oracle Technology Network. These documents are packaged with released code, or you can obtain them through My Oracle Support.)

Documentation should be available on this Web site within a month after a product release.

## Conventions

**Navigate:** This is a navigate statement. It tells you how to get to the start of the procedure and ends with a screen shot of the starting point and the statement “the Window Name window opens.”

---

**Note:** This is a note. It is used to call out information that is important, but not necessarily part of the procedure.

---

This is a code sample

It is used to display examples of code

A hyperlink appears like this.

---

---

# Preinstallation Tasks

This chapter includes tasks to complete before installation.

## Check for the Current Version of the Installation Guide

Corrected versions of Oracle Retail installation guides may be published whenever critical corrections are required. For critical corrections, the rerelease of an installation guide may not be attached to a release; the document will simply be replaced on the Oracle Technology Network Web site.

Before you begin installation, check to be sure that you have the most recent version of this installation guide. Oracle Retail installation guides are available on the Oracle Technology Network at the following URL:

[http://www.oracle.com/technology/documentation/oracle\\_retail.html](http://www.oracle.com/technology/documentation/oracle_retail.html)

An updated version of an installation guide is indicated by part number, as well as print date (month and year). An updated version uses the same part number, with a higher-numbered suffix. For example, part number E123456-02 is an updated version of an installation guide with part number E123456-01.

If a more recent version of this installation guide is available, that version supersedes all previous versions. Only use the newest version for your installation.

## Check Application Server Requirements

General requirements for an application server capable of running the Oracle Retail Invoice Matching application include the following.

---

---

**Note:** Files required for Oracle Configuration Manager (OCM) are removed after OPatch is used to patch the WebLogic server. This will cause the product installers and OCM installation to fail. To work around this issue, back up the content of the \$ORACLE\_HOME/utls/ccr/lib directory prior to applying a patch using OPatch, and recopy the content back after you apply any patches. ORACLE\_HOME is the location where WebLogic Server has been installed.

---

---

---

---

**Note:** If using an OPatch on Linux 64-bit platforms, see [Installer Fails because of missing .jar in \\$ORACLE\\_HOME/utls/ccr/lib](#) in Appendix: Common Installation Errors.

---

---

| Supported on:         | Versions Supported:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Application Server OS | <p>OS certified with Oracle Fusion Middleware 11g Release 1 (11.1.1.6). Options are:</p> <ul style="list-style-type: none"> <li>▪ Oracle Linux 5 for x86-64 (Actual hardware or Oracle virtual machine).</li> <li>▪ Red Hat Enterprise Linux 5 for x86-64 (Actual hardware or Oracle virtual machine).</li> <li>▪ AIX 6.1, 7.1 (Actual hardware or LPARs)</li> <li>▪ Solaris 10, 11 SPARC (Actual hardware or logical domains)</li> <li>▪ HP-UX 11.31 Integrity (Actual hardware, HPVM, or vPars)</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                 |
| Application Server    | <p>Oracle Fusion Middleware 11g Release 1 (11.1.1.6)</p> <p><b>Components:</b></p> <ul style="list-style-type: none"> <li>▪ Oracle WebLogic Server 11g Release 1 (10.3.6)</li> <li>▪ Java: <ul style="list-style-type: none"> <li>JDK 1.6.0+ 64 bit</li> <li>or</li> <li>Jrockit 1.6 R28 build or later, within the 1.6 code line. 64 bit.</li> </ul> </li> </ul> <p><b>IMPORTANT:</b> If there is an existing WebLogic installation on the server, you must upgrade to WebLogic 10.3.6. All middleware components associated with WebLogic server should be upgraded to 11.1.1.6.</p> <p>Back up the weblogic.policy file (\$WLS_HOME/wlserver_10.3/server/lib) before upgrading your WebLogic server, because this file could be overwritten. Copy over the weblogic.policy backup file after the WebLogic upgrade is finished and the post patching installation steps are completed.</p> |

## Check Oracle Retail Software Dependencies

Service Providing Applications (such as RMS) must have all RSL components installed (including stored procedures, tables, and Oracle objects). Refer to the installation guide for each for details.

### Supported Oracle Retail Products

| Integrates with                                   | Version |
|---------------------------------------------------|---------|
| Oracle Retail Allocation (Client)                 | 13.2.5  |
| Oracle Retail Store Inventory Management (SIM)    | 13.2.5  |
| Oracle Retail Merchandising System (RMS) (Server) | 13.2.5  |
| Oracle Retail Price Management (RPM) (Server)     | 13.2.5  |

## UNIX User Account Privileges to Install the Software

A UNIX user account is needed to install the software. The UNIX user that is used to install the software should have write access to the WebLogic server installation files.

For example, webadmin.

---

---

**Note:** Installation steps will fail when trying to modify files under the WebLogic installation, unless the user has write access.

---

---

## Moving the RSL Packaged .jars to the Server Library

Copy the ojdbc6.jar from this location (RSL1325forRMS/rsl-rms/oracle) to this location (\$WLS\_HOME/wlserver\_10.3/server/lib).

---

---

**Note:** WebLogic must be restarted after ojdbc6.jar has been copied into WLS\_HOME.

---

---

## Configure the rsl-rms-wls-instance

To configure the rsl-rms-wls-instance, do the following.

1. Configure the startup script.
  - a. Take a backup of the script (the following uses "APPDomain" as the domain name where RSL will be installed), \$DOMAIN\_HOME/ APPDomain /bin/startWebLogic.sh.
  - b. Edit the script, \$DOMAIN\_HOME/ APPDomain /bin/startWebLogic.sh, to add the following attributes.
 

```
# Arguments for JDK 1.6.0+ 64bit:
CLASSPATH=$DOMAIN_HOME/servers/$SERVER_NAME:$CLASSPATH
JAVA_VM="-server"          USER_MEM_ARGS="-Xms1024m -Xmx2048m -XX:MaxPermSize=512m"

# Arguments for Jrockit:
CLASSPATH=$DOMAIN_HOME/servers/$SERVER_NAME:$CLASSPATH
JAVA_VM="-server"
USER_MEM_ARGS="-Xms1024m -Xmx2048m"
```

The following is a sample from startWebLogic.sh using 1.6.0+ JDK:

```
echo "."
echo "."
echo "JAVA Memory arguments: ${MEM_ARGS}"
echo "."
echo "WLS Start Mode=${WLS_DISPLAY_MODE}"
echo "."
CLASSPATH=$DOMAIN_HOME/servers/$SERVER_NAME:$CLASSPATH
JAVA_VM="-server"
USER_MEM_ARGS="-Xms1024m -Xmx2048m -XX:MaxPermSize=512m"
echo "CLASSPATH=${CLASSPATH}"
```

```
echo "."

echo "PATH=${PATH}"

echo "."

echo "*****"

echo "*" To start WebLogic Server, use a username and "*"

echo "*" password assigned to an admin-level user. For *"

echo "*" server administration, use the WebLogic Server *"

echo "*" console at http://hostname:port/console *"

echo "*****"

# CLASS CACHING

if [ "${CLASS_CACHE}" = "true" ] ; then
    echo "Class caching enabled..."
    JAVA_OPTIONS="${JAVA_OPTIONS} -Dlaunch.main.class=${SERVER_CLASS} -
Dlaunch.class.path=${CLASSPATH}" -
Dlaunch.complete=weblogic.store.internal.LockManagerImpl -cp
${WL_HOME}/server/lib/pcl2.jar"
    export JAVA_OPTIONS
    SERVER_CLASS="com.oracle.classloader.launch.Launcher"
fi

# START WEBLOGIC

echo "starting weblogic with Java version:"

${JAVA_HOME}/bin/java ${JAVA_VM} -version

if [ "${WLS_REDIRECT_LOG}" = "" ] ; then
    echo "Starting WLS with line:"
    echo "${JAVA_HOME}/bin/java ${JAVA_VM} ${MEM_ARGS} -
Dweblogic.Name=${SERVER_NAME} -
Djava.security.policy=${WL_HOME}/server/lib/weblogic.policy ${JAVA_OPTIONS}
${PROXY_SETTINGS} ${SERVER_CLASS}"
    ${JAVA_HOME}/bin/java ${JAVA_VM} ${MEM_ARGS} -Dweblogic.Name=${SERVER_NAME} -
Djava.security.policy=${WL_HOME}/server/lib/weblogic.policy ${JAVA_OPTIONS}
${PROXY_SETTINGS} ${SERVER_CLASS}
else
    echo "Redirecting output from WLS window to ${WLS_REDIRECT_LOG}"
    ${JAVA_HOME}/bin/java ${JAVA_VM} ${MEM_ARGS} -Dweblogic.Name=${SERVER_NAME} -
Djava.security.policy=${WL_HOME}/server/lib/weblogic.policy ${JAVA_OPTIONS}
${PROXY_SETTINGS} ${SERVER_CLASS} >"${WLS_REDIRECT_LOG}" 2>&1
fi

stopAll
```

---

**Note:** The statements above must be added to the startWebLogic script before the call is made to start the server.

---

---

**Note:** Weblogic must be restarted for these changes to take effect.

---

2. Edit the nodemanager.properties file at the following location with the below values:  
\$WLS\_HOME/wlserver\_10.3/common/nodemanager/nodemanager.properties
  - SecureListener=false
  - StartScriptEnabled=true
  - StartScriptName=startWebLogic.sh.

---

**Note:** The nodemanager.properties file is created after the nodemanager is started for the first time. It is not available before that.

---

---

**Note:** The nodemanager must be restarted after changes are made to the nodemanager.properties file.

---





---



---

## Application Installation

Before proceeding, you must create a WebLogic server. The RSLforRMS application is deployed to a server within the WebLogic Application installation.

---



---

**IMPORTANT:** If there is an existing WebLogic installation on the server, you must upgrade to WebLogic 10.3.6. All middleware components associated with WebLogic server should be upgraded to 11.1.1.6.

Back up the weblogic.policy file (\$WLS\_HOME/wlserver\_10.3/server/lib) before upgrading your WebLogic server, because this file could be overwritten. Copy over the weblogic.policy backup file after the WebLogic upgrade is finished and the post patching installation steps are completed.

---



---

### Create a Managed Server for RSLforRMS

The RSLforRMS application must be deployed to its own dedicated WebLogic server. Use the following steps to create a new managed server instance for RSLforRMS and configure it to RSL requirements.

---



---

**Note:** For information on using commands to create a managed server instance, see the Weblogic® Application Server Administrator's Guide 11g Release 3 (10.3.6).

---



---

Create the rsl-rms-wls-instance using WebLogic administration console GUI:

1. Log in to the WebLogic administration console GUI (<http://<host>:<port>/console>) as administrator.
2. In the right menu, navigate to Environment → Servers.
3. Click **New**.
4. Enter the Name, Port, and Listen address of the server instance to be created. For example:
  - Server Name : rsl-rms-wls-server
  - Server Listen Address: myhost82

---



---

**Note:** The RSL application server must be on the same application server of the application that will be using RSL (for example, SIM, RPM, and Allocation).

---



---

- Server Listen Port: 19007
5. Click **Next**. Click **Finish**.
  6. Make sure you see the new instance listed under Servers.
  7. Click on the server name that you just created. Navigate to Configuration → General tab.
  8. In the Machine field, select the machine name where the server will be running.

9. Start the newly created server using the Administration Console (servers → control tab).

## Expand the RSLforRMS Distribution

To expand the RSLforRMS distribution, do the following.

1. Log into the UNIX server as the user who owns the WebLogic installation and determine where the RSL 13.2 application server file (RslServerPak13.2.5forRMS\_eng\_ga.tar) will be installed. There should be a minimum of 25 MB disk space available for the application installation files.
2. Copy RslServerPak13.2.5forRMS\_eng\_ga.tar (located at CD/appserverunix) to a newly created staging directory on the UNIX server.
3. Change directory to the location of RslServerPak13.2.5forRMS\_eng\_ga.tar and extract this file. This will create directory: /RSL1325forRMS.

To extract run the following: tar xf RslServerPak13.2.5forRMS\_eng\_ga.tar

RSL\_INSTALL\_HOME refers to the directory structure including the newly created /RSL1325forRMS.

For example, /u00/webadmin/media/ RSL1325forRMS

## Run the RSLforRMS Installer

Configuration scripts are provided to deploy and configure the RSLforRMS application in the application server, including the JDBC DataSource.

1. Change directory to RSL\_INSTALL\_HOME.
2. Set the WL\_HOME, WEBLOGIC\_DOMAIN\_HOME and JAVA\_HOME environment variables.  
  
WL\_HOME should point to your Application Server installation (for example, WL\_HOME = /u00/webadmin/product/10.3.x/WLS. JAVA\_HOME should point to the Java that is installed for the WebLogic server.  
  
WEBLOGIC\_DOMAIN\_HOME should point to the application server domain (for example, WEBLOGIC\_DOMAIN\_HOME = /u00/webadmin/product/10.3.x/WLS/user\_projects/domains/APPDomain).
3. Set the PATH environment variable (for example, PATH=\$JAVA\_HOME/bin:\$PATH).
4. If you are using an X server, such as Exceed, set the DISPLAY environment variable so that you can run the installer in GUI mode (recommended). If you are not using an X server, or the GUI is too slow over your network, unset DISPLAY for text mode.
5. Run the rsl-installer.sh script. (See "[Appendix: RSLforRMS Installer Screens.](#)") This launches the installer. After installation is complete, a detailed installation log file is created (rsl13install.<timestamp>.log) in the RSL\_INSTALL\_HOME/.retail-installer directory.
6. After the script has run successfully, verify that the application is running and the Oracle DataSource was configured properly by logging into the Application Server Console.

## Resolving Errors Encountered During Application Installation

If the application installer encounters any errors, it halts execution immediately.

See “[Appendix: Common Installation Errors](#)” for common installation errors.

Because the application installation is a full reinstallation every time, any previous partial installation will be overwritten by the successful installation.

## Backups Created by Installer

The RSLforRMS application installer backs up previous installations by renaming them with <timestamp> suffixes. This is done to prevent the removal of any custom changes you might have. These backup directories can be safely removed without affecting the current installation.

For example, rsl-rms.200605011726



---

## Appendix: RSLforRMS Installer Screens

This section describes the Oracle Retail Service Layer 13.2 Installer screens.

This environment information is necessary for successful deployment of the RSLforRMS application. The screens and fields displayed depend on the options selected; some screens and fields may not be displayed.

The following are RSLforRMS installer screens.

### Screen: Data Source Details

**Retail Service Layer 13 Installer - Oracle Retail**

**ORACLE®**

**Data Source Details**

Provide the details for the RMS data source

RMS 13 JDBC URL

RMS 13 schema

RMS 13 schema password

Note: entering an alias for this user will enhance security for this application. If left blank it will default to the username.

RSL 13 schema user alias

Enter the RSL schema owner. This is usually the same as the RSL schema entered above

RSL 13 schema owner

|                   |                                                                                                                           |
|-------------------|---------------------------------------------------------------------------------------------------------------------------|
| Field Title       | RMS 13 JDBC URL                                                                                                           |
| Field Description | URL used by RSLforRMS to access the RMS database schema. See <a href="#">Appendix: URL Reference</a> for expected syntax. |
| Example           | jdbc:oracle:thin:@myhost:1525:mydatabase                                                                                  |

|                          |                                                                         |
|--------------------------|-------------------------------------------------------------------------|
| <b>Field Title</b>       | RMS 13 schema                                                           |
| <b>Field Description</b> | Database schema owner user where the RMS database schema was installed. |
| <b>Example</b>           | RMS13                                                                   |

|                          |                                   |
|--------------------------|-----------------------------------|
| <b>Field Title</b>       | RMS 13 schema password            |
| <b>Field Description</b> | Password for the RMS schema user. |

|                          |                                                                                                                                                                                                                     |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Field Title</b>       | RSL 13 schema user alias                                                                                                                                                                                            |
| <b>Field Description</b> | Alias for the RMS/RSL schema user.                                                                                                                                                                                  |
| <b>Note</b>              | This alias must be unique. Do not use the same value for any other alias fields in the installer. If the same alias is used, entries in the wallet can override each other and cause problems with the application. |

|                          |                          |
|--------------------------|--------------------------|
| <b>Field Title</b>       | RSL 13 schema owner      |
| <b>Field Description</b> | Owner of the RMS schema. |
| <b>Example</b>           | RMS13                    |

Screen: Application Server Instance Details

Retail Service Layer 13 Installer - Oracle Retail

ORACLE

Application Deployment Details

The default values shown below are examples

RSL 13 app deployment name

rsl-rms

Enter the RSL13 weblogic managed server or cluster.

RSL13 server/cluster

rsl-rms-wls-instance

Cancel

Back

Next

Install

|                   |                                          |
|-------------------|------------------------------------------|
| Field Title       | RSL 13 app deployment name               |
| Field Description | The name of the deployment/context_root. |
| Example           | rsl-rms                                  |

|                   |                                                           |
|-------------------|-----------------------------------------------------------|
| Field Title       | RSL 13 server/cluster                                     |
| Field Description | The name of the RSL13 WebLogic managed server or cluster. |
| Example           | rsl-rms-wls-instance                                      |

## Screen: WebLogic Administrative User

**Retail Service Layer 13 Installer - Oracle Retail**

**ORACLE®**

**Weblogic Administrative User**

Enter the administrative user and password for the Weblogic Server to which the application will be deployed.

Hostname: myhost82

Weblogic admin port: 7001

Weblogic admin user: weblogic

Weblogic admin password:

Note: entering an alias for this user will enhance security for this application. If left blank it will default to the username.

Weblogic admin alias: weblogic-admin-alias

Buttons: Cancel, Back, Next, Install

| Field Title       | Hostname                                                                                                                                                                      |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Field Description | Host name of the WebLogic application server where RSL would be deployed.                                                                                                     |
| Example           | Myhost82<br><b>Note:</b> The RSL application server must be on the same application server of the application that will be using RSL (for example, SIM, RPM, and Allocation). |

| Field Title       | Weblogic admin port                    |
|-------------------|----------------------------------------|
| Field Description | The port of the WebLogic admin server. |
| Example           | 7001                                   |



|                          |                                                                                      |
|--------------------------|--------------------------------------------------------------------------------------|
| <b>Field Title</b>       | <b>Weblogic admin user</b>                                                           |
| <b>Field Description</b> | The user name of the WebLogic server. The user should have administrator privileges. |
| <b>Example</b>           | Weblogic                                                                             |

|                          |                                          |
|--------------------------|------------------------------------------|
| <b>Field Title</b>       | <b>Weblogic admin password</b>           |
| <b>Field Description</b> | The password for the WebLogic user name. |
| <b>Example</b>           | welcome1                                 |

|                          |                                                                                                                                                                                                                     |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Field Title</b>       | <b>Weblogic admin alias</b>                                                                                                                                                                                         |
| <b>Field Description</b> | The alias for the admin user name.                                                                                                                                                                                  |
| <b>Example</b>           | Weblogic-admin-alias                                                                                                                                                                                                |
| <b>Notes</b>             | This alias must be unique. Do not use the same value for any other alias fields in the installer. If the same alias is used, entries in the wallet can override each other and cause problems with the application. |



---

## Appendix: Common Installation Errors

This section provides some common errors encountered during installation of RSLforRMS.

### Unreadable Buttons in the Installer

If you are unable to read the text within the installer buttons, it could mean that your JAVA\_HOME is pointed to an older version of the JDK than is supported by the installer. Set JAVA\_HOME with the appropriate JDK (the same JDK that has been used by WebLogic Server).

### Warning: Could not create system preferences directory

#### Symptom

The following text appears in the installer Errors tab:

```
May 22, 2006 11:16:39 AM java.util.prefs.FileSystemPreferences$3 run
WARNING: Could not create system preferences directory. System preferences are
unusable.
May 22, 2006 11:17:09 AM java.util.prefs.FileSystemPreferences
checkLockFile0ErrorCode
WARNING: Could not lock System prefs. Unix error code -264946424.
```

#### Solution

This is related to Java bug 4838770. The /etc/.java/.systemPrefs directory may not have been created on your system. See <http://bugs.sun.com> for details.

This is an issue with your installation of Java and does not affect the Oracle Retail product installation.

### ConcurrentModificationException in Installer GUI

#### Symptom

In GUI mode, the errors tab shows the following error:

```
java.util.ConcurrentModificationException
    at
java.util.AbstractList$Itr.checkForComodification(AbstractList.java:448)
    at java.util.AbstractList$Itr.next(AbstractList.java:419)
... etc
```

#### Solution

You can ignore this error. It is related to third-party Java Swing code for rendering of the installer GUI and does not affect the retail product installation.

## Warning: Could not find X Input Context

### Symptom

The following text appears in the console window during execution of the installer in GUI mode:

Couldn't find X Input Context

### Solution

This message is harmless and can be ignored.

## Files not available to copy at the end of installation, results in non working applications

If you choose the option, **No. Configure but do not install the application**, in the installer screen titled **Manual Deployment Option**, wallet files that are required for application run time are deleted at the end of the installation.

### Solution

Manual Deployment is not currently available in this installer. Choose **Yes. I have write access to the application server** in the installer screen, **Manual Deployment Option**.

---

**Note:** To successfully perform this option, you also need to run the installer as a user with write access to the WebLogic installation.

---

## Installer Fails because of missing .jar in \$ORACLE\_HOME/utls/ccr/lib

### Symptom

The jar file expected by the installer (emocmcInt.jar) is overwritten after the OPatch patch 6880880 is applied, and any other patch is applied afterward using that OPatch. If you try to run the installer after patching, as outlined in the installation guides, the installer fails. All applications that are installed in the same WebLogic server that hosts any of the forms applications will be affected by this issue. This is because of required Oracle patches for Linux 64-bit systems that are applied to the forms server using OPatch.

### Solution

Back up the content of the \$ORACLE\_HOME/utls/ccr/lib directory prior to applying OPatch patch 6880880, and recopy the content back after you apply any patches using that OPatch.

## GUI screens fail to open when running Installer

### Symptom

When running the installer in GUI mode, the screens fail to open and the installer ends, returning to the console without an error message. The ant.install.log file contains this error:

```
Fatal exception: Width (0) and height (0) cannot be <= 0  
java.lang.IllegalArgumentException: Width (0) and height (0) cannot be <= 0
```

### Solution

This error is encountered when Antinstaller is used in GUI mode with certain X Servers. To work around this issue, copy ant.install.properties.sample to ant.install.properties and rerun the installer.



---

## Appendix: URL Reference

The application installers for the RSLforRMS product will ask for several different URLs. These include the following.

### JDBC URL for a Database

Used by the Java application and by the installer to connect to the database.

#### Syntax

`jdbc:oracle:thin:@<host>:<port>:<sid>`

where:

- `<host>` is the hostname of the database server.
- `<port>` is the database listener port.
- `<sid>` is the system identifier for the database.

#### Example:

`jdbc:oracle:thin:@myhost:1521:mysid`





---

## Appendix: Setting Up Password Stores with Oracle Wallet

As part of an application installation, administrators must set up password stores for database user accounts using Oracle Wallet. These password stores must be installed on the application database side. While the installer handles much of this process, the administrators must perform some additional steps.

A password store for the application and application server user accounts must also be installed; however, the installer takes care of this entire process.

### About Password Stores and Oracle Wallet

Oracle databases have allowed other users on the server to see passwords in case database connect strings (username/password@db) were passed to programs. In the past, users could navigate to `ps -ef | grep <username>` to see the password if the password was supplied in the command line when calling a program.

To make passwords more secure, Oracle Retail has implemented the Oracle Software Security Assurance (OSSA) program. Sensitive information such as user credentials now must be encrypted and stored in a secure location. This location is called password stores or wallets. These password stores are secure software containers that store the encrypted user credentials.

Users can retrieve the credentials using aliases that were set up when encrypting and storing the user credentials in the password store. For example, if username/password@db is entered in the command line argument and the alias is called db\_username, the argument to a program is as follows:

```
sqlplus /@db_username
```

This would connect to the database as it did previously, but it would hide the password from any system user.

After this is configured, as in the example above, the application installation and the other relevant scripts are no longer needed to use embedded usernames and passwords. This reduces any security risks that may exist because usernames and passwords are no longer exposed.

When the installation starts, all the necessary user credentials are retrieved from the Oracle Wallet based on the alias name associated with the user credentials.

There are two different types of password stores or wallets. One type is for database connect strings used in program arguments (such as `sqlplus /@db_username`). The other type is for Java application installation and application use.

## Setting Up Password Stores for Database User Accounts

After the database is installed and the default database user accounts are set up, administrators must set up a password store using the Oracle wallet. This involves assigning an alias for the username and associated password for each database user account. The alias is used later during the application installation. This password store must be created on the system where the application server and database client are installed.

This section describes the steps you must take to set up a wallet and the aliases for the database user accounts. For more information on configuring authentication and password stores, see the *Oracle Database Security Guide*.

---

**Note:** In this section, `<wallet_location>` is a placeholder text for illustration purposes. Before running the command, ensure that you specify the path to the location where you want to create and store the wallet.

---

To set up a password store for the database user accounts, perform the following steps:

1. Create a wallet using the following command:

```
mkstore -wrl <wallet_location> -create
```

After you run the command, a prompt appears. Enter a password for the Oracle Wallet in the prompt.

---

**Note:** The `mkstore` utility is included in the Oracle Database Client installation.

---

The wallet is created with the auto-login feature enabled. This feature enables the database client to access the wallet contents without using the password. For more information, refer to the *Oracle Database Advanced Security Administrator's Guide*.

2. Create the database connection credentials in the wallet using the following command:

```
mkstore -wrl <wallet_location> -createCredential <alias-name> <database-user-name>
```

After you run the command, a prompt appears. Enter the password associated with the database user account in the prompt.

3. Repeat Step 2 for all the database user accounts.
4. Update the `sqlnet.ora` file to include the following statements:

```
WALLET_LOCATION = (SOURCE = (METHOD = FILE) (METHOD_DATA = (DIRECTORY =  
<wallet_location>)))  
SQLNET.WALLET_OVERRIDE = TRUE  
SSL_CLIENT_AUTHENTICATION = FALSE
```

- 
5. Update the tnsnames.ora file to include the following entry for each alias name to be set up.

```
<alias-name> =
  (DESCRIPTION =
    (ADDRESS_LIST =
      (ADDRESS = (PROTOCOL = TCP) (HOST = <host>) (PORT = <port>))
    )
    (CONNECT_DATA =
      (SERVICE_NAME = <service>)
    )
  )
```

In the previous example, <alias-name>, <host>, <port>, and <service> are placeholder text for illustration purposes. Ensure that you replace these with the relevant values.

## Setting Up Wallets for Database User Accounts

The following examples show how to set up wallets for database user accounts for the following applications:

- [For RMS, RWMS, RPM Batch, RETL, RMS, RWMS, and ARI](#)
- [For Java Applications \(SIM, ReIM, RPM, Alloc, RIB, RSL, AIP, RETL\)](#)

### For RMS, RPM Plsql Batch, RETL DB, RWMS batch, and ARI

1. Create a new directory called wallet under your folder structure.

```
cd /projects/rms13.2/dev/
mkdir .wallet
```

---

---

**Note:** The default permissions of the wallet allow only the owner to use it, ensuring the connection information is protected. If you want other users to be able to use the connection, you must adjust permissions appropriately to ensure only authorized users have access to the wallet.

---

---

2. Create a sqlnet.ora in the wallet directory with the following content.

```
WALLET_LOCATION = (SOURCE = (METHOD = FILE) (METHOD_DATA =
(DIRECTORY = /projects/rms13.2/dev/.wallet)) )
SQLNET.WALLET_OVERRIDE=TRUE
SSL_CLIENT_AUTHENTICATION=FALSE
```

---

---

**Note:** WALLET\_LOCATION must be on line 1 in the file.

---

---

3. Setup a tnsnames.ora in the wallet directory. This tnsnames.ora includes the standard tnsnames.ora file. Then, add two custom tns\_alias entries that are only for use with the wallet. For example, sqlplus /@dvols29\_rms01user.

```
ifile = /u00/oracle/product/11.2.0.1/network/admin/tnsnames.ora
```

```
dvols29_rms01user =
  (DESCRIPTION = (ADDRESS_LIST = (ADDRESS = (PROTOCOL = tcp)
    (host = mspdv311.us.oracle.com) (Port = 1521)))
    (CONNECT_DATA = (SID = dvols29) (GLOBAL_NAME = dvols29)))
```

```
dvols29_rms01user.world =
  (DESCRIPTION = (ADDRESS_LIST = (ADDRESS = (PROTOCOL = tcp)
    (host = mspdv311.us.oracle.com) (Port = 1521)))
    (CONNECT_DATA = (SID = dvols29) (GLOBAL_NAME = dvols29)))
```

---

---

**Note:** It is important to not just copy the tnsnames.ora file because it can quickly become out of date. The ifile clause (shown above) is key.

---

---

4. Create the wallet files. These are empty initially.
  - a. Ensure you are in the intended location.  

```
$ pwd
/projects/rms13.2/dev/.wallet
```
  - b. Create the wallet files.  

```
$ mkstore -wrl . -create
```
  - c. Enter the wallet password you want to use. It is recommended that you use the same password as the UNIX user you are creating the wallet on.
  - d. Enter the password again.  
 Two wallet files are created from the above command:
    - ewallet.p12
    - cwallet.sso
5. Create the wallet entry that associates the user name and password to the custom tns alias that was setup in the wallet's tnsnames.ora file.  

```
mkstore -wrl . -createCredential <tns_alias> <username> <password>
```

---

---

**Example:** mkstore -wrl . -createCredential  
 dvols29\_rms01user rms01user passwd

---

---

6. Test the connectivity. The ORACLE\_HOME used with the wallet must be the same version or higher than what the wallet was created with.  

```
$ export TNS_ADMIN=/projects/rms13.2/dev/.wallet /* This is very import to use wallet to point at the alternate tnsnames.ora created in this example */

$ sqlplus /@dvols29_rms01user

SQL*Plus: Release 11

Connected to:
Oracle Database 11g

SQL> show user
USER is "rms01user"
```

Running batch programs or shell scripts would be similar:

```
Ex: dtesys /@dvols29_rms01user
script.sh /@dvols29_rms01user
```

Set the UP unix variable to help with some compiles :

```
export UP=/@dvols29_rms01user
for use in RMS batch compiles, and RMS, RWMs, and ARI forms compiles.
```

As shown in the example above, users can ensure that passwords remain invisible.

---

## Additional Database Wallet Commands

The following is a list of additional database wallet commands.

- Delete a credential on wallet  
`mkstore -wrl . -deleteCredential dvols29_rms01user`
- Change the password for a credential on wallet  
`mkstore -wrl . -modifyCredential dvols29_rms01user rms01user passwd`
- List the wallet credential entries  
`mkstore -wrl . -list`  
This command returns values such as the following.  
`oracle.security.client.connect_string1`  
`oracle.security.client.user1`  
`oracle.security.client.password1`
- View the details of a wallet entry  
`mkstore -wrl . -viewEntry oracle.security.client.connect_string1`  
Returns the value of the entry:  
`dvols29_rms01user`  
`mkstore -wrl . -viewEntry oracle.security.client.user1`  
Returns value of the entry:  
`rms01user`  
  
`mkstore -wrl . -viewEntry oracle.security.client.password1`  
Returns value of the entry:  
`passwd`

## For Java Applications (SIM, ReIM, RPM, Alloc, RIB, RSL, AIP, RETL)

For Java application, consider the following:

- For database user accounts, ensure that you set up the same alias names between the password stores (database wallet and Java wallet). You can provide the alias name during the installer process.
- Document all aliases that you have set up. During the application installation, you must enter the alias names for the application installer to connect to the database and application server.
- Passwords are not used to update entries in Java wallets. Entries in Java wallets are stored in partitions, or application-level keys. In each retail application that has been installed, the wallet is located in  
`<WEBLOGIC_DOMAIN_HOME>/retail/<appname>/config` Example:  
`mspdvdv351:[103x_WLS] /u00/webadmin/product/10.3.x/WLS/user_projects/`  
`domains/132_mck_soa_domain/retail/reim13/config`
- Application installers should create the Java wallets for you, but it is good to know how this works for future use and understanding.
- Scripts are located in `<WEBLOGIC_DOMAIN_HOME>/retail/<appname>/retail-public-security-api/bin` for administering wallet entries.  
Example:  
`mspdvdv351:[103x_WLS] /u00/webadmin/product/10.3.x/WLS/user_projects/`  
`domains/132_mck_soa_domain/retail/reim13/retail-public-security-api/bin`
- In this directory is a script to help you update each alias entry without having to remember the wallet details. For example, if you set the RPM database alias to `rms01user`, you will find a script called `update-RMS01USER.sh`.

---

**Note:** These scripts are available only with application installed by way of an installer.

---

- Two main scripts are related to this script in the folder for more generic wallet operations: `dump_credentials.sh` and `save_credential.sh`.
- If you have not installed the application yet, you can unzip the application zip file and view these scripts in `<app>/application/retail-public-security-api/bin`.

Example:

```
mspdv351:[103x_WLS] /u00/webadmin/reim/application/retail-public-security-api/bin
```

#### **update-<ALIAS>.sh**

`update-<ALIAS>.sh` updates the wallet entry for this alias. You can use this script to change the user name and password for this alias. Because the application refers only to the alias, no changes are needed in application properties files.

##### **Usage:**

```
update-<username>.sh <myuser>
```

##### **Example:**

```
mspdev71:[103xWLS]
/u00/webadmin/product/10.3.x/WLS/user_projects/domains/java_domain/retail/rpm1
32test/retail-public-security-api/bin> ./update-RMS01USER.sh
```

usage: `update-RMS01USER.sh <username>`

`<username>`: the username to update into this alias.

Example: `update-RMS01USER.sh myuser`

Note: this script will ask you for the password for the username that you pass in.

```
mspdev71:[103xWLS]
/u00/webadmin/product/10.3.x/WLS/user_projects/domains/java_domain/retail/rpm1
32test/retail-public-security-api/bin>
```

#### **dump\_credentials.sh**

`dump_credentials.sh` is used to retrieve information from the wallet. For each entry found in the wallet, the wallet partition, the alias, and the user name are displayed. Note that the password is not displayed. If the value of an entry is uncertain, run `save_credential.sh` to resave the entry with a known password.

```
dump_credentials.sh <wallet location>
```

---

**Example:**

```
dump_credentials.sh
/u00/webadmin/product/10.3.x/WLS/user_projects/domains/132_mck_soa_domain/retail/reim13/config
```

**Retail Public Security API Utility**

```
=====
Below are the credentials found in the wallet at the
location:/u00/webadmin/product/10.3.x/WLS/user_projects/domains/132_mck_soa_domain/retail/reim13/config
=====
```

```
Application level key partition name:reim13
User Name Alias:WLS-ALIAS User Name:weblogic
User Name Alias:RETAIL-ALIAS User Name:retail.user
User Name Alias:LDAP-ALIAS User Name:RETAIL.USER
User Name Alias:RMS-ALIAS User Name:rms132mock
User Name Alias:REIMBAT-ALIAS User Name:reimbat
```

**save\_credential.sh**

save\_credential.sh is used to update the information in wallet. If you are unsure about the information that is currently in the wallet, use dump\_credentials.sh as indicated above. You can add new or update using save\_credential.sh as shown below:

```
save_credential.sh -a <alias> -u <user> -p <partition name> -l <path of the wallet file location where credentials are stored>
```

**Example:**

```
mshpdv351:[103x_WLS]
/u00/webadmin/mock132_testing/rttl/rttl/application/retail-public-security-api/bin> save_credential.sh -l
/u00/webadmin/product/10.3.x/WLS/user_projects/domains/132_mck_soa_domain/retail/reim13/config
-a RMS-ALIAS -p reim13 -u rms132mock
```

**Retail Public Security API Utility**

```
=====
Enter password:
Verify password:
```

---

**Note:** -p in the above command is for partition name. You must specify the proper partition name used in application code for each Java application.

---

---

save\_credential.sh and dump\_credentials.sh scripts are the same for all applications. If using save\_credential.sh to add a wallet entry or to update a wallet entry, bounce the application/managed server so that your changes are visible to the application. Also, save a backup copy of your cwallet.sso file in a location outside of the deployment path, because redeployment or reinstallation of the application will wipe the wallet entries you made after installation of the application. To restore your wallet entries after a redeployment/reinstallation, copy the backed up cwallet.sso file over the cwallet.sso file. Then bounce the application/managed server.

---

### Usage

```
=====
Retail Public Security API Utility
=====
usage: save_credential.sh -au[plh]
E.g. save_credential.sh -a rms-alias -u rms_user -p rib-rms -l ./
-a, --userNameAlias <arg>          alias for which the credentials
needs to be stored
-h, --help                          usage information
-l, --locationofWalletDir <arg>    location where the wallet file is
created. If not specified, it creates the wallet under secure-credential-wallet
directory which is already present under the retail-public-security-api/
directory.
-p, --appLevelKeyPartitionName <arg> application level key partition name
-u, --userName <arg>               username to be stored in secure
credential wallet for specified alias*
```

## How Does the Wallet Relate to the Application?

The ORACLE Retail Java applications have the wallet alias information you create in an <app-name>.properties file. Below is the reim.properties file. Note the database information and the user are presented as well. The property called datasource.credential.alias=RMS-ALIAS uses the ORACLE wallet with the argument of RMS-ALIAS at the csm.wallet.path and csm.wallet.partition.name = reim13 to retrieve the password for application use.

Reim.properties code sample:

```
datasource.url=jdbc:oracle:thin:@mspdv349.us.oracle.com:1521:pkols07
datasource.schema.owner=rms132mock
datasource.credential.alias=RMS-ALIAS
# =====
# ossa related Configuration
#
# These settings are for ossa configuration to store credentials.
# =====

csm.wallet.path=/u00/webadmin/product/10.3.x/WLS/user_projects/domains/132_mck_soa
_domain/retail/reim13/config
csm.wallet.partition.name=reim13
```

## How Does the Wallet Relate to Java Batch Program Use?

Some of the ORACLE Retail Java batch applications have an alias to use when running Java batch programs. For example, alias REIMBAT-ALIAS maps through the wallet to



---

REIM app user reimbat, already on the database. To run a ReIM batch program the format would be: `reimbatchpgmname REIMBAT-ALIAS <other arguments as needed by the program in question>`.

## Setting up RETL Wallets

RETL creates a wallet under `$RFX_HOME/etc/security`, with the following files:

- `cwallet.sso`
- `jazn-data.xml`
- `jps-config.xml`
- `README.txt`

To set up RETL wallets, perform the following steps:

1. Set the following environment variables:
  - `ORACLE_SID=<retaildb>`
  - `RFX_HOME=/u00/rfx/rfx-13.2.0`
  - `RFX_TMP=/u00/rfx/rfx-13.2.0/tmp`
  - `JAVA_HOME=/usr/jdk1.6.0_12.64bit`
  - `LD_LIBRARY_PATH=$ORACLE_HOME`
  - `PATH=$RFX_HOME/bin:$JAVA_HOME/bin:$PATH`
2. Change directory to `$RFX_HOME/bin`.
3. Run `setup-security-credential.sh`.
  - Enter 1 to add a new database credential.
  - Enter the dbuseralias. For example, `retl_java_rms01user`.
  - Enter the database user name. For example, `rms01user`.
  - Enter the database password.
  - Re-enter the database password.
  - Enter D to exit the setup script.
4. Update your RETL environment variable script to reflect the names of both the Oracle Networking wallet and the Java wallet.

For example, to configure RETLforRPAS, modify the following entries in `$MMHOME/RETLforRPAS/rfx/etc/rmse_rpas_config.env`.

  - The `RETL_WALLET_ALIAS` should point to the Java wallet entry:  
`export RETL_WALLET_ALIAS="retl_java_rms01user"`
  - The `ORACLE_WALLET_ALIAS` should point to the Oracle network wallet entry:  
`export ORACLE_WALLET_ALIAS="dvols29_rms01user"`
  - The `SQLPLUS_LOGON` should use the `ORACLE_WALLET_ALIAS`:  
`export SQLPLUS_LOGON="/@${ORACLE_WALLET_ALIAS}"`
5. To change a password later, run `setup-security-credential.sh`.
  - Enter 2 to update a database credential.
  - Select the credential to update.
  - Enter the database user to update or change.
  - Enter the password of the database user.
  - Re-enter the password.



## Quick Guide for Retail Wallets

| Retail App      | Wallet Type | Wallet Location                          | Wallet Partition         | Alias Name                             | User Name                          | Use                                       | Create By | Alias Example | Notes                         |
|-----------------|-------------|------------------------------------------|--------------------------|----------------------------------------|------------------------------------|-------------------------------------------|-----------|---------------|-------------------------------|
| RMS batch       | DB          | <RMS batch install dir (MMHOME)>/.wallet | n/a                      | <Database SID>_<Database schema owner> | <rms schema owner>                 | Compile, execution                        | Installer | n/a           | Alias hard-coded by installer |
| RMS forms       | DB          | <forms install dir>/base/.wallet         | n/a                      | <Database SID>_<Database schema owner> | <rms schema owner>                 | Compile                                   | Installer | n/a           | Alias hard-coded by installer |
| ARI forms       | DB          | <forms install dir>/base/.wallet         | n/a                      | <Db_Ari01>                             | <ari schema owner>                 | Compile                                   | Manual    | ari-alias     |                               |
| RMWS forms      | DB          | <forms install dir>/base/.wallet         | n/a                      | <Database SID>_<Database schema owner> | <rwms schema owner>                | Compile forms, execute batch              | Installer | n/a           | Alias hard-coded by installer |
| RPM app         | DB          | <RPM batch install dir>/.wallet          | n/a                      | <rms schema owner alias>               | <rms schema owner>                 | Execute batch                             | Manual    | rms-alias     |                               |
| RWMS auto-login | JAVA        | <forms install dir>/base/.javawallet     |                          |                                        |                                    |                                           |           |               |                               |
|                 |             |                                          | <RWMS Installation name> | <RWMS database user alias>             | <RWMS schema owner>                | RWMS forms app to avoid dblogin screen    | Installer | rwms13inst    |                               |
|                 |             |                                          | <RWMS Installation name> | BI_ALIAS                               | <BI Publisher administrative user> | RWMS forms app to connect to BI Publisher | Installer | n/a           | Alias hard-coded by installer |

| Retail App     | Wallet Type | Wallet Location                                              | Wallet Partition | Alias Name                       | User Name                       | Use            | Create By | Alias Example          | Notes                     |
|----------------|-------------|--------------------------------------------------------------|------------------|----------------------------------|---------------------------------|----------------|-----------|------------------------|---------------------------|
| <b>AIP app</b> | JAVA        | <weblogic domain home>/retail/<deployed aip app name>/config |                  |                                  |                                 |                |           |                        | Each alias must be unique |
|                |             |                                                              | aip13            | <AIP weblogic user alias>        | <AIP weblogic user name>        | App use        | Installer | aip-weblogic-alias     |                           |
|                |             |                                                              | aip13            | <AIP database schema user alias> | <AIP database schema user name> | App use        | Installer | aip01user-alias        |                           |
|                |             |                                                              | aip13            | <rib-aip weblogic user alias>    | <rib-aip weblogic user name>    | App use        | Installer | rib-aip-weblogic-alias |                           |
| <b>RPM app</b> | JAVA        | <weblogic domain home>/retail/<deployed rpm app name>/config |                  |                                  |                                 |                |           |                        | Each alias must be unique |
|                |             |                                                              | rpm13            | <rpm weblogic user alias>        | <rpm weblogic user name>        | App use        | Installer | rpm-weblogic-alias     |                           |
|                |             |                                                              | rpm13            | <rms shema user alias>           | <rms shema user name>           | App, batch use | Installer | rms01user-alias        |                           |
|                |             |                                                              | rpm13            | <rpm application user one alias> | <rpm application user one name> | App use        | Installer | user1-alias            |                           |

| Retail App       | Wallet Type | Wallet Location                                                | Wallet Partition     | Alias Name                              | User Name                              | Use            | Create By | Alias Example          | Notes                     |
|------------------|-------------|----------------------------------------------------------------|----------------------|-----------------------------------------|----------------------------------------|----------------|-----------|------------------------|---------------------------|
|                  |             |                                                                | rpm13                | <rpm application user two alias>        | <rpm application user two name>        | App use        | Installer | user2-alias            |                           |
|                  |             |                                                                | rpm13                | <rpm batch user alias>                  | <rpm batch user name>                  | App, batch use | Installer | rpmbatch-alias         |                           |
|                  |             |                                                                | rpm13                | <rib-rpm weblogic user alias>           | <rib-rpm weblogic user name>           | App use        | Installer | rib-rpm-weblogic-alias |                           |
| <b>ReIM app</b>  | JAVA        | <weblogic domain home>/retail/<deployed reim app name>/config  |                      |                                         |                                        |                |           |                        | Each alias must be unique |
|                  |             |                                                                | <installed app name> | <reim weblogic user alias>              | <reim weblogic user name>              | App use        | Installer | weblogic-alias         |                           |
|                  |             |                                                                | <installed app name> | <rms shema user alias>                  | <rms shema user name>                  | App, batch use | Installer | rms01user-alias        |                           |
|                  |             |                                                                | <installed app name> | <reim webservice validation user alias> | <reim webservice validation user name> | App use        | Installer | reimwebsevice-alias    |                           |
|                  |             |                                                                | <installed app name> | <reim batch user alias>                 | <reim batch user name>                 | App, batch use | Installer | reimbatch-alias        |                           |
| <b>Alloc app</b> | JAVA        | <weblogic domain home>/retail/<deployed alloc app name>/config |                      |                                         |                                        |                |           |                        | Each alias must be unique |

| Retail App     | Wallet Type | Wallet Location                                              | Wallet Partition     | Alias Name                        | User Name                        | Use     | Create By | Alias Example          | Notes                     |
|----------------|-------------|--------------------------------------------------------------|----------------------|-----------------------------------|----------------------------------|---------|-----------|------------------------|---------------------------|
|                |             |                                                              | <installed app name> | <alloc weblogic user alias>       | <alloc weblogic user name>       | App use | Installer | weblogic-alias         |                           |
|                |             |                                                              | <installed app name> | <rms shema user alias>            | <rms shema user name>            | App use | Installer | rms01user-alias        |                           |
|                |             |                                                              | <installed app name> | <rsl for rms weblogic user alias> | <rsl for rms weblogic user name> | App use | Installer | rsl-rms-weblogic-alias |                           |
| <b>RSL app</b> | JAVA        | <RSL INSTALL DIR>/rsl-rms/security/config                    |                      |                                   |                                  |         |           |                        | Each alias must be unique |
|                |             |                                                              | rsl-rsm              | <rsl weblogic user alias>         | <rsl weblogic user name>         | App use | Installer | weblogic-alias         |                           |
|                |             |                                                              | rsl-rsm              | <rms shema user alias>            | <rms shema user name>            | App use | Installer | rms01user-alias        |                           |
| <b>SIM app</b> | JAVA        | <weblogic domain home>/retail/<deployed sim app name>/config |                      |                                   |                                  |         |           |                        |                           |
|                |             |                                                              | rpm                  | <rpm weblogic user alias>         | <rpm weblogic user name>         | App use | Installer | rpm-weblogic-alias     |                           |
|                |             |                                                              | rms                  | <rsl for rms weblogic user alias> | <rsl for rms weblogic user name> | App use | Installer | rsl-rms-weblogic-alias |                           |
|                |             |                                                              | rib-sim              | <rib-sim weblogic user alias>     | <rib-sim weblogic user name>     | App use | Installer | rib-sim-weblogic-alias |                           |

| Retail App  | Wallet Type | Wallet Location                             | Wallet Partition              | Alias Name                      | User Name                      | Use             | Create By | Alias Example       | Notes                                                     |
|-------------|-------------|---------------------------------------------|-------------------------------|---------------------------------|--------------------------------|-----------------|-----------|---------------------|-----------------------------------------------------------|
| RETL        | JAVA        | <RETL home>/etc/security                    | n/a                           | <target application user alias> | <target application db userid> | App use         | Manual    | retl_java_rms01user | User may vary depending on RETL flow's target application |
| RETL        | DB          | <RETL home>/wallet                          | n/a                           | <target application user alias> | <target application db userid> | App use         | Manual    | <db>_<user>         | User may vary depending on RETL flow's target application |
| RIB         | JAVA        | <RIBHOME DIR>/deployment-home/conf/security |                               |                                 |                                |                 |           |                     | <app> is one of aip, rfm, rms, rpm, sim, rwms, tafr       |
| JMS         |             |                                             | jms<1-5>                      | <jms user alias> for jms<1-5>   | <jms user name> for jms<1-5>   | Integration use | Installer | jms-alias           |                                                           |
| WebLogic    |             |                                             | rib-<app>-app-server-instance | <rib-app weblogic user alias>   | <rib-app weblogic user name>   | Integration use | Installer | weblogic-alias      |                                                           |
| Admin GUI   |             |                                             | rib-<app>#web-app-user-alias  | <rib-app admin gui user alias>  | <rib-app admin gui user name>  | Integration use | Installer | admin-gui-alias     |                                                           |
| Application |             |                                             | rib-<app>#user-alias          | <app weblogic user alias>       | <app weblogic user name>       | Integration use | Installer | app-user-alias      | Valid only for aip, rpm, sim                              |

| Retail App        | Wallet Type | Wallet Location | Wallet Partition                        | Alias Name                                                         | User Name                                                            | Use                | Create By | Alias Example       | Notes                                        |
|-------------------|-------------|-----------------|-----------------------------------------|--------------------------------------------------------------------|----------------------------------------------------------------------|--------------------|-----------|---------------------|----------------------------------------------|
| DB                |             |                 | rib-<br><app>#app-<br>db-user-<br>alias | <rib-app<br>database<br>schema user<br>alias>                      | <rib-app<br>database<br>schema<br>user<br>name>                      | Integration<br>use | Installer | db-user-<br>alias   | Valid only<br>for rfm,<br>rms, rwms,<br>tafr |
| Error<br>Hospital |             |                 | rib-<br><app>#hosp<br>-user-alias       | <rib-app<br>error<br>hospital<br>database<br>schema user<br>alias> | <rib-app<br>error<br>hospital<br>database<br>schema<br>user<br>name> | Integration<br>use | Installer | hosp-user-<br>alias |                                              |



---



---

## Appendix: Installation Order

This section provides a guideline as to the order in which the Oracle Retail applications should be installed. If a retailer has chosen to use some, but not all, of the applications the order is still valid less the applications not being installed.

---



---

**Note:** The installation order is not meant to imply integration between products.

---



---

### Enterprise Installation Order

1. Oracle Retail Merchandising System (RMS), Oracle Retail Trade Management (RTM), Oracle Retail Sales Audit (ReSA), Optional: Oracle Retail Fiscal Management (ORFM)

---



---

**Note:** ORFM is an optional application for RMS if you are implementing Brazil localization.

---



---

2. Oracle Retail Service Layer (RSL)
3. Oracle Retail Extract, Transform, Load (RETL)
4. Oracle Retail Active Retail Intelligence (ARI)
5. Oracle Retail Warehouse Management System (RWMS)
6. Oracle Retail Invoice Matching (ReIM)
7. Oracle Retail Price Management (RPM)

---



---

**Note:** During installation of RPM, you are asked for the RIBforRPM provider URL. Since RIB is installed after RPM, make a note of the URL you enter. If you need to change the RIBforRPM provider URL after you install RIB, you can do so by editing the `remote_service_locator_info_ribserver.xml` file.

---



---

8. Oracle Retail Allocation
9. Oracle Retail Central Office (ORCO)
10. Oracle Retail Returns Management (ORRM)
11. Oracle Retail Back Office (ORBO) or Back Office with Labels and Tags (ORLAT)
12. Oracle Retail Store Inventory Management (SIM)

---



---

**Note:** During installation of SIM, you are asked for the RIB provider URL. Since RIB is installed after SIM, make a note of the URL you enter. If you need to change the RIB provider URL after you install RIB, you can do so by editing the `remote_service_locator_info_ribserver.xml` file.

---



---

13. Oracle Retail Predictive Application Server (RPAS)
14. Oracle Retail Demand Forecasting (RDF)
15. Oracle Retail Category Management (CM)
16. Oracle Retail Replenishment Optimization (RO)

17. Oracle Retail Analytic Parameter Calculator Replenishment Optimization (APC RO)
18. Oracle Retail Regular Price Optimization (RPO)
19. Oracle Retail Merchandise Financial Planning (MFP)
20. Oracle Retail Size Profile Optimization (SPO)
21. Oracle Retail Assortment Planning (AP)
22. Oracle Retail Item Planning (IP)
23. Oracle Retail Item Planning Configured for COE (IP COE)
24. Oracle Retail Advanced Inventory Planning (AIP)
25. Oracle Retail Integration Bus (RIB)
26. Oracle Retail Point-of-Service (ORPOS)
27. Oracle Retail Markdown Optimization (MDO)
28. Oracle Retail Clearance Optimization Engine (COE)
29. Oracle Retail Analytic Parameter Calculator for Markdown Optimization (APC-MDO)
30. Oracle Retail Analytic Parameter Calculator for Regular Price Optimization (APC-RPO)
31. Oracle Retail Promotion Intelligence and Promotion Planning and Optimization (PI-PPO)
32. Oracle Retail Analytics
33. Oracle Retail Workspace (ORW)