

Oracle® Configuration Manager

Collection Overview

Release 10.3.2

E12022-05

February 2010

E12022-05

Copyright © 2008, 2010, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Contents

Preface	xvii
Audience	xvii
Documentation Accessibility	xvii
Related Documents	xviii
Conventions	xviii
 1 Introduction	
 2 Collections	
2.1 Application Deployment	2-1
2.1.1 Application Configuration	2-1
2.2 Automatic Storage Management	2-1
2.2.1 ASM Instance Properties	2-1
2.3 CalDAV Application	2-1
2.3.1 General	2-1
2.4 Calendar Applications	2-1
2.4.1 Calendar Application HTTP Server Configuration	2-2
2.5 Calendar Server	2-2
2.5.1 Calendar Server Basic Configuration	2-2
2.5.2 Calendar Configuration	2-2
2.5.3 Calendar Server Configuration	2-2
2.6 Cluster Database	2-2
2.6.1 Database Configuration Version	2-2
2.6.2 Control Files	2-2
2.6.3 CPU Usage	2-2
2.6.4 Data Files	2-2
2.6.5 Instance Information	2-3
2.6.6 Feature Usage	2-3
2.6.7 High-Water Mark	2-3
2.6.8 Database License	2-4
2.6.9 Database Options	2-4
2.6.10 Redo Logs	2-4
2.6.11 Rollback Segments	2-4
2.6.12 Tablespaces	2-4
2.6.13 Database Users	2-5

2.6.14	High Availability - Database Files.....	2-5
2.6.15	High Availability - General Information.....	2-5
2.6.16	High Availability - Initialization Parameters	2-5
2.6.17	High Availability - RMAN Configuration.....	2-5
2.6.18	STATS Pack Configuration.....	2-5
2.7	Conference Application	2-5
2.7.1	General	2-5
2.8	Contract Management Server Database	2-6
2.8.1	CM Admin and group Database information	2-6
2.8.2	CM Database Information	2-6
2.8.3	CM Admin and group Database upgrade Version history	2-6
2.9	Contract Management Server	2-6
2.9.1	Contract Manager Configuration Parameters	2-6
2.10	Database Instance.....	2-7
2.10.1	ASM Disk	2-7
2.10.2	Control Files.....	2-7
2.10.3	CPU Usage.....	2-7
2.10.4	Database Components	2-7
2.10.5	Database Configuration Version	2-8
2.10.6	Database License.....	2-8
2.10.7	Database Options.....	2-8
2.10.8	Database Scheduler Jobs	2-8
2.10.9	Database Users	2-8
2.10.10	Data Files.....	2-8
2.10.11	DB Invalid Objects	2-8
2.10.12	Feature Usage	2-9
2.10.13	High Availability - Database Files.....	2-9
2.10.14	High Availability - General Information.....	2-9
2.10.15	High Availability - Initialization Parameters	2-9
2.10.16	High Availability - RMAN Configuration	2-9
2.10.17	High-Water Mark.....	2-9
2.10.18	Initialization Parameters.....	2-10
2.10.19	Instance Information	2-10
2.10.20	MGMT_DB_CPU_USAGE_ECM	2-10
2.10.21	MGMT_DB_USERS_ECM	2-10
2.10.22	Redo Logs.....	2-10
2.10.23	Rollback Segments.....	2-11
2.10.24	STATS Pack Configuration.....	2-11
2.10.25	System Global Area	2-11
2.10.26	Tablespaces	2-11
2.11	DeviceManagement Application	2-11
2.11.1	Blocked Devices	2-12
2.11.2	General	2-12
2.12	Email Application	2-12
2.12.1	CSI	2-12
2.12.2	General	2-12
2.12.3	SubjectSortingGroupingRules.....	2-12

2.12.4	IMAP.....	2-12
2.12.5	IMAP Endpoint Properties.....	2-13
2.12.6	Local Email Patterns.....	2-13
2.12.7	Non Local Email Patterns.....	2-13
2.12.8	Persistence.....	2-13
2.12.9	SubjectSortingReplacementRules.....	2-13
2.12.10	SMTP.....	2-13
2.12.11	SMTP Endpoint Properties.....	2-13
2.12.12	VMS Properties.....	2-13
2.12.13	Transport.....	2-14
2.13	E-Mail Housekeeper.....	2-14
2.13.1	E-Mail Housekeeper Instance Mailstore Configuration.....	2-14
2.14	E-Mail IMAP Server.....	2-15
2.14.1	E-Mail IMAP Instance Mailstore Configuration.....	2-15
2.15	E-Mail List Server.....	2-15
2.15.1	E-Mail List Server Instance Mailstore Configuration.....	2-15
2.16	E-Mail NNTP Inbound Server.....	2-15
2.16.1	E-Mail NNTP Inbound Instance Mailstore Configuration.....	2-15
2.17	E-Mail NNTP Outbound Server.....	2-15
2.17.1	E-Mail NNTP Outbound Instance Mailstore Configuration.....	2-15
2.18	E-Mail POP Server.....	2-15
2.18.1	E-Mail POP Instance Mailstore Configuration.....	2-16
2.19	E-Mail SMTP Inbound Server.....	2-16
2.19.1	E-Mail SMTP Inbound Instance Mailstore Configuration.....	2-16
2.20	E-Mail SMTP Outbound Server.....	2-16
2.20.1	E-Mail SMTP Outbound Instance Mailstore Configuration.....	2-16
2.21	E-Mail Virus Scrubber.....	2-16
2.21.1	E-Mail Virus Scrubber Instance Mailstore Configuration.....	2-16
2.22	FTP Application.....	2-16
2.22.1	General.....	2-16
2.23	Host.....	2-17
2.23.1	File Systems.....	2-17
2.23.2	Hardware.....	2-17
2.23.3	Hardware CPU.....	2-17
2.23.4	Host User Defined Products.....	2-18
2.23.5	I/O Devices.....	2-18
2.23.6	Network Information Configuration.....	2-18
2.23.7	Operating System.....	2-18
2.23.8	Operating System Components.....	2-18
2.23.9	Operating System Modules.....	2-18
2.23.10	Operating System Properties.....	2-19
2.23.11	Operating System Registered Software.....	2-19
2.23.12	Operating System Running Products.....	2-19
2.23.13	Operating System ULIMITs.....	2-19
2.23.14	Host User Defined Products.....	2-19
2.24	IAS Configuration.....	2-19
2.24.1	Console.....	2-19

2.24.2	DCM Auto Archive Check	2-20
2.24.3	Debug Log Level Check.....	2-20
2.24.4	Log Level Check.....	2-20
2.25	IBM Websphere Install	2-20
2.25.1	IBM Product Components.....	2-20
2.25.2	IBM Products	2-20
2.25.3	IBM Product Family	2-20
2.26	IM Application	2-21
2.26.1	General	2-21
2.27	JDEdwards Enterprise One	2-21
2.27.1	Data Sources	2-21
2.27.2	Environments	2-22
2.27.3	Data Server (F9650).....	2-22
2.27.4	Deployment Servers (F9650)	2-22
2.27.5	Crystal Enterprise CMS	2-22
2.27.6	Enterprise Servers (F9650)	2-22
2.27.7	Crystal Enterprise Web Server.....	2-23
2.27.8	Web Servers (F9650)	2-23
2.27.9	Windows Terminal Server (F9650).....	2-23
2.27.10	Path Codes	2-23
2.27.11	Updates	2-24
2.27.12	Data Indicators	2-24
2.28	JDEdwards Enterprise One Collaborative Portal.....	2-24
2.28.1	Standalone Agent Managed Instances.....	2-24
2.28.2	Standalone Agent Managed Instances Attributes.....	2-24
2.28.3	Standalone Agent Managed Instance JAS INI.....	2-24
2.28.4	Standalone Agent Managed Instances JDBJ INI	2-24
2.28.5	Standalone Agent Managed Instances JDE INI.....	2-25
2.29	JDEdwards Enterprise One Enterprise Server.....	2-25
2.29.1	Standalone Agent Managed Instances.....	2-25
2.29.2	Standalone Agent Managed Instance Attributes	2-25
2.29.3	Standalone Agent Managed Instance JDE INI	2-25
2.30	JDEdwards Enterprise One Management Console.....	2-25
2.30.1	Management Console Agent.....	2-25
2.30.2	Management Console Agent Attributes.....	2-25
2.30.3	Management Console JAS INI	2-26
2.30.4	Management Console JDBC INI.....	2-26
2.30.5	Management Console Managed Homes	2-26
2.30.6	Management Console Managed Instances.....	2-26
2.31	JDEdwards Enterprise One PIM Synch Server.....	2-26
2.31.1	Standalone Agent Managed Instances.....	2-26
2.31.2	Standalone Agent Managed Instance Attributes	2-26
2.31.3	Standalone Agent Managed Instance JAS INI.....	2-27
2.31.4	Standalone Agent Managed Instance JDBJ INI	2-27
2.32	JDEdwards Enterprise One Standalone Agent.....	2-27
2.32.1	Standalone Agent.....	2-27
2.32.2	Standalone Agent Attributes.....	2-27

2.32.3	Standalone Agent Managed Instances.....	2-27
2.33	JDEdwards Enterprise One Transaction Server	2-27
2.33.1	Standalone Agent Managed Instances.....	2-27
2.33.2	Standalone Agent Managed Instance Attributes	2-28
2.33.3	Standalone Agent Managed Instance JAS INI.....	2-28
2.33.4	Standalone Agent Managed Instance JDBJ INI.....	2-28
2.34	JDEdwards Enterprise One Web Server	2-28
2.34.1	Standalone Agent Managed Instances.....	2-28
2.34.2	Standalone Agent Managed Instance Attributes	2-28
2.34.3	Standalone Agent Managed Instance JAS INI.....	2-28
2.34.4	Standalone Agent Managed Instance JDBJ INI.....	2-29
2.35	JServ	2-29
2.35.1	Configuration Files	2-29
2.35.2	JServ Zones	2-29
2.36	OC4J	2-29
2.36.1	Applications.....	2-29
2.36.2	Configuration Files	2-29
2.36.3	Connection Pools	2-29
2.36.4	Data Sources	2-29
2.36.5	Deployed Applications	2-30
2.36.6	Global Web Module Settings	2-30
2.36.7	Log Growth Check.....	2-30
2.36.8	Managed Data Sources.....	2-30
2.36.9	Modules.....	2-30
2.36.10	Native Data Sources	2-30
2.36.11	Port Ranges	2-30
2.36.12	Resource Usage	2-30
2.36.13	Web Module Settings	2-31
2.36.14	Web Module URLs	2-31
2.37	OHS Configuration.....	2-31
2.37.1	File Permission Check.....	2-31
2.37.2	Identity Check	2-31
2.37.3	Log Growth Check.....	2-31
2.37.4	Log Level Check.....	2-32
2.37.5	Virtual Hosts.....	2-32
2.38	Oracle Agent Deployment Configuration	2-32
2.38.1	MGMT_ECM_EMD_JAVA_PARAMS	2-32
2.39	Oracle Application Server.....	2-32
2.39.1	Configuration Files	2-32
2.39.2	Console	2-32
2.39.3	DCM.....	2-33
2.39.4	Deployed Applications	2-33
2.39.5	General	2-33
2.39.6	Components.....	2-33
2.39.7	OPMN.....	2-33
2.40	Oracle Beehive Site Configuration	2-33
2.40.1	Application Server	2-33

2.40.2	HTTP Server	2-33
2.40.3	OC4J	2-33
2.40.4	Database	2-34
2.40.5	LDAP	2-34
2.40.6	Virtual Server	2-34
2.41	Oracle Business Intelligence (BI) Analytics Server	2-34
2.41.1	BI Analytics Server Configuration Parameters	2-34
2.42	Oracle Business Intelligence (BI) Cluster Controller	2-35
2.42.1	BI Cluster Controller Configuration Parameters	2-35
2.42.2	BI DAC Server Properties	2-35
2.42.3	BI DAC ETL Summary	2-36
2.43	Oracle Business Intelligence (BI) DAC	2-36
2.43.1	BI DAC Server Properties	2-36
2.43.2	BI DAC ETL Summary	2-36
2.44	Oracle Business Intelligence (BI) Presentation Server	2-37
2.44.1	BI Presentation Server Configuration Parameters	2-37
2.44.2	BI Presentation Server Alerts Configurations	2-37
2.44.3	BI Presentation Server Cache Configurations	2-38
2.44.4	BI Presentation Server Charts Configurations.....	2-38
2.44.5	BI Presentation Server Client Configurations.....	2-38
2.44.6	BI Presentation Server Display Configurations.....	2-38
2.44.7	BI Presentation Server Marketing Configurations.....	2-38
2.44.8	BI Presentation Server Other Configurations	2-38
2.44.9	BI Presentation Server Report Cache Configurations	2-38
2.44.10	BI Presentation Server State Pool Configurations.....	2-38
2.44.11	BI Presentation Server Thread Pool Configurations.....	2-39
2.44.12	BI Presentation Server XML Cache Defaults	2-39
2.45	Oracle Business Intelligence (BI) Scheduler Server.....	2-39
2.45.1	BI Scheduler.....	2-39
2.45.2	BI Schedule IBOTS.....	2-40
2.45.3	BI Scheduler Mail.....	2-40
2.46	Oracle Business Intelligence (BI) Web Plugin.....	2-40
2.46.1	BI Web Plugin.....	2-40
2.47	Oracle Cluster	2-41
2.47.1	Cluster Manager Configuration	2-41
2.47.2	High Availability Cluster Interconnect	2-41
2.47.3	Server Configuration.....	2-41
2.48	Oracle Concurrent Manager	2-41
2.48.1	Concurrent Processing Package Versions	2-41
2.48.2	Concurrent Processing Profile Options	2-41
2.48.3	ICM Settings	2-41
2.48.4	Concurrent Managers (Service Instances).....	2-42
2.48.5	Specialization Rules.....	2-42
2.48.6	Summary Configuration.....	2-42
2.48.7	Workshifts for Concurrent Managers	2-42
2.49	Oracle Configuration Manager	2-42
2.49.1	Oracle Configuration Manager Package Versions.....	2-42

2.49.2	Oracle Configuration Manager Parameter Values	2-43
2.50	Oracle E-Business Suite.....	2-43
2.50.1	Number of Active Users	2-43
2.50.2	Applied Patches (January to December) - Collected by Month.....	2-43
2.50.3	Applications Customer Forms.....	2-43
2.50.4	Applications System Summary	2-43
2.50.5	Applications Topology.....	2-43
2.50.6	Comprising Patches (January to December) - Collected by Month	2-43
2.50.7	Component Version	2-44
2.50.8	Configuration Version	2-44
2.50.9	Custom Alert Information.....	2-44
2.50.10	Custom Applications.....	2-44
2.50.11	Profile Options Registered Under Custom Application	2-44
2.50.12	Custom Audit Group Information.....	2-44
2.50.13	Custom Database Objects	2-44
2.50.14	Custom Hooks.....	2-44
2.50.15	Custom Message Count	2-45
2.50.16	Custom Objects Owned by Apps	2-45
2.50.17	Custom Request Sets	2-45
2.50.18	Responsibility Count.....	2-45
2.50.19	Custom Triggers	2-45
2.50.20	Custom Value Sets - Table Validated.....	2-45
2.50.21	Custom Value Sets (Other than Table Validated).....	2-45
2.50.22	Custom Workflows.....	2-45
2.50.23	Registered Data Groups.....	2-45
2.50.24	Database Version	2-46
2.50.25	End-Dated Users	2-46
2.50.26	Generic Service Components	2-46
2.50.27	Generic Service Component Parameters.....	2-46
2.50.28	High Priority Patches Not Applied.....	2-46
2.50.29	JTF Hooks.....	2-46
2.50.30	Localization Modules	2-46
2.50.31	NLS Language Support	2-47
2.50.32	Other Customizations	2-47
2.50.33	Patchset Information	2-47
2.50.34	Printers	2-47
2.50.35	Printer Drivers.....	2-47
2.50.36	User Profile Options	2-47
2.50.37	Technology Stack Inventory (DB)	2-47
2.51	Oracle E-Business Suite Infrastructure	2-47
2.51.1	Appsweb Configuration	2-48
2.51.2	Appsweb Configuration Metadata	2-48
2.51.3	Applications Context Files	2-48
2.51.4	Dbc File.....	2-48
2.51.5	Dbc File Meta.....	2-48
2.51.6	Custom Context Variables.....	2-48
2.51.7	Environments Context Variables.....	2-48

2.51.8	Global Context Variables.....	2-49
2.51.9	Host Context Variables	2-49
2.51.10	Install Context Variables.....	2-49
2.51.11	Processes Context Variables.....	2-49
2.51.12	System Context Variables	2-49
2.51.13	Technology Stack Inventory (File System).....	2-49
2.51.14	Workflow Mailer Configuration.....	2-50
2.51.15	Workflow Mailer Configuration Metadata.....	2-50
2.52	Oracle Enterprise Manager 10g Grid Control Management Agent.....	2-50
2.52.1	Agent Configuration Parameters	2-50
2.52.2	Java Parameters.....	2-50
2.52.3	Log Parameters	2-51
2.52.4	Perl Parameters	2-51
2.53	Oracle Enterprise Manager 10g Grid Control Management Repository	2-51
2.53.1	EM Repository Monitory Agents	2-51
2.53.2	EM Repository Monitored Beacons	2-51
2.53.3	EM Repository Configuration Parameters.....	2-51
2.53.4	OMS Name	2-51
2.54	Oracle Enterprise Manager 10g Grid Control Management Service.....	2-51
2.54.1	OMS Configuration Parameters	2-51
2.55	Oracle EPM Calc Manager.....	2-52
2.55.1	Database Connection.....	2-52
2.55.2	Instance Information	2-52
2.55.3	Web Application Deployment	2-52
2.56	Oracle EPM Architect	2-52
2.56.1	Database Connection.....	2-52
2.56.2	Instance Information	2-52
2.56.3	Web Application Deployment	2-52
2.57	Oracle EPM ERPI	2-53
2.57.1	Database Connection.....	2-53
2.57.2	Instance Information	2-53
2.57.3	Web Application Deployment	2-53
2.58	Oracle EPM Essbase Administration Service.....	2-53
2.58.1	Instance Information	2-53
2.58.2	Web Application Deployment	2-53
2.59	Oracle EPM Essbase Provider Service	2-53
2.59.1	Instance Information	2-53
2.59.2	Web Application Deployment	2-53
2.60	Oracle EPM Essbase Server	2-53
2.60.1	Instance Information	2-54
2.61	Oracle EPM Financial Management.....	2-54
2.61.1	Database Connection.....	2-54
2.61.2	Instance Information	2-54
2.62	Oracle EPM Financial Reporting	2-54
2.62.1	Instance Information	2-54
2.62.2	Web Application Deployment	2-54
2.63	Oracle EPM HSS.....	2-54

2.63.1	Database Connection.....	2-54
2.63.2	Instance Information	2-55
2.63.3	Security Options Setting	2-55
2.63.4	Security Service Providers.....	2-55
2.63.5	Web Application Deployment	2-55
2.64	Oracle EPM Performance Scorecard	2-55
2.64.1	Database Connection.....	2-55
2.64.2	Instance Information	2-55
2.64.3	Web Application Deployment	2-55
2.65	Oracle EPM Planning	2-55
2.65.1	Business Rules	2-55
2.65.2	Database Connection.....	2-56
2.65.3	Instance Information	2-56
2.65.4	Web Application Deployment	2-56
2.66	Oracle EPM Profitability	2-56
2.66.1	Database Connection.....	2-56
2.66.2	Instance Information	2-56
2.66.3	Web Application Deployment	2-56
2.67	Oracle EPM RA Framework.....	2-56
2.67.1	Database Connection.....	2-56
2.67.2	Instance Information	2-57
2.67.3	Web Application Deployment	2-57
2.68	Oracle EPM System	2-57
2.68.1	Database Connection.....	2-57
2.68.2	Instance Information	2-57
2.69	Oracle EPM Web Analysis.....	2-57
2.69.1	Instance Information	2-57
2.69.2	Web Application Deployment	2-57
2.70	Oracle EPM Workspace	2-57
2.70.1	Database Connection.....	2-57
2.70.2	Instance Information	2-57
2.70.3	Web Application Deployment	2-57
2.71	Oracle Exadata Storage Server Software	2-58
2.71.1	CELL Celldisk Configuration	2-58
2.71.2	Oracle Cell Configuration.....	2-58
2.71.3	CELL Griddisk Configuration	2-59
2.71.4	CELL IORM Configuration	2-59
2.71.5	CELL LUN Configuration	2-59
2.71.6	CELL Physical Disk Configuration	2-60
2.72	Oracle Grid Control Repository	2-60
2.72.1	Object Privileges	2-60
2.73	Oracle Home	2-61
2.73.1	Dependency Rules	2-61
2.73.2	Oracle Oneoff Patches.....	2-61
2.73.3	Oracle Oneoff Patches Bugs Fixed	2-61
2.73.4	Oracle Oneoff PatchesComponents	2-61
2.73.5	Oracle Software Components	2-61

2.73.6	Oracle Software Patchsets.....	2-61
2.73.7	Oracle Versioned Patches	2-62
2.74	Oracle HTTP Server	2-62
2.74.1	SSL Ciphers Suite Settings.....	2-62
2.74.2	Configuration Files	2-62
2.74.3	General	2-62
2.74.4	Listen Addresses	2-62
2.74.5	Performance Related	2-62
2.74.6	Virtual Hosts.....	2-63
2.75	Oracle Hyperion Enterprise Performance Management (EPM) System	2-63
2.75.1	EPM System (Root Node).....	2-63
2.75.2	Foundation Shared Services.....	2-63
2.75.3	Foundation Workspace.....	2-64
2.75.4	EPM Architect	2-64
2.75.5	Calc Manager.....	2-64
2.75.6	Essbase (Agent Port).....	2-65
2.75.7	Essbase (Web App Port)	2-65
2.75.8	Essbase (Web App Port)	2-65
2.75.9	Planning	2-66
2.75.10	Financial Management.....	2-66
2.75.11	Performance Scorecard	2-66
2.75.12	Profitability and Cost Management	2-67
2.75.13	ERP Integrator	2-67
2.75.14	Report & Analysis (Web App Port).....	2-67
2.75.15	Report & Analysis (Web App Port).....	2-68
2.75.16	Report and Analysis (Web App Port).....	2-68
2.76	Oracle iAS Farm	2-68
2.76.1	Farm Configuration.....	2-68
2.77	Oracle Internet Directory	2-68
2.77.1	Oracle Internet Directory Configuration.....	2-68
2.78	Oracle Listener.....	2-69
2.78.1	Listener Status	2-69
2.79	Oracle Retail.....	2-69
2.79.1	Oracle Retail Active Retail Intelligence Application	2-69
2.79.2	Oracle Retail Allocation Java Application	2-69
2.79.3	Oracle Retail Back Office Java Application.....	2-69
2.79.4	Oracle Retail Central Office Java Application	2-69
2.79.5	Oracle Retail Markdown Optimization.....	2-69
2.79.6	Oracle Retail Workspace.....	2-69
2.79.7	Oracle Retail Data Warehouse Database.....	2-70
2.79.8	Oracle Retail Merchandising System Application	2-70
2.79.9	Oracle Retail Returns Management Java Application.....	2-70
2.79.10	Oracle Retail Price Management Java Application.....	2-70
2.79.11	Oracle Retail Warehouse Management System Application	2-70
2.79.12	Oracle Retail Invoice Matching Java Application.....	2-70
2.79.13	Oracle RPAS Global Domain	2-70
2.79.14	Oracle Retail Predictive Application Server	2-70

2.79.15	Oracle RPAS Sub Domain	2-70
2.79.16	Oracle Retail Store Inventory Management Java Application	2-70
2.79.17	Oracle Retail Integration Bus Java Application.....	2-71
2.80	Oracle WebLogic Server.....	2-71
2.80.1	General Server Configuration	2-71
2.80.2	Virtual Host Configuration	2-71
2.80.3	Jolt Connection Pools Configuration	2-72
2.80.4	Work Manager Configuration	2-72
2.80.5	Startup and Shutdown Classes Configuration.....	2-72
2.80.6	JDBC DataSource Configuration	2-72
2.80.7	JDBC Multi-DataSource Configuration.....	2-72
2.80.8	JMS Connection Factory Configuration	2-72
2.80.9	JMS Topic Configuration	2-73
2.80.10	JMS Queue Configuration	2-73
2.80.11	Resource Configuration	2-73
2.81	Oracle WebLogic Install	2-73
2.81.1	Oracle WebLogic Product Components	2-73
2.81.2	Oracle WebLogic Product.....	2-73
2.82	PeopleSoft Application Server	2-74
2.82.1	Application Server Analytics Parameters	2-74
2.82.2	Application Server Cache Parameters	2-74
2.82.3	Application Server Configuration Parameters.....	2-74
2.82.4	Application Server Database Parameters.....	2-74
2.82.5	Application Server Domain Parameters.....	2-74
2.82.6	Application Server Integration Broker Parameters	2-74
2.82.7	Application Server Interface Driver Parameters.....	2-74
2.82.8	Application Server Jolt Listener Parameters.....	2-74
2.82.9	Application Server Jolt Relay Parameters	2-75
2.82.10	Application Server Message Broker Dispatcher Parameters.....	2-75
2.82.11	Application Server Message Broker Handler Parameters	2-75
2.82.12	Application Server Options Parameters.....	2-75
2.82.13	Application Server Optimization Engine Parameters.....	2-75
2.82.14	Application Server People Code Debugger Parameters	2-76
2.82.15	Application Server PPM Server Parameters	2-76
2.82.16	Application Server PSBRKDSP Server Parameters	2-76
2.82.17	Application Server PSBRKHND Server Parameters	2-76
2.82.18	Application Server PSPUBDSP Server Parameters.....	2-77
2.82.19	Application Server PSPUBHND Server Parameters	2-77
2.82.20	Application Server PSSUBDSP Server Parameters.....	2-78
2.82.21	Application Server PSSUBHND Server Parameters.....	2-78
2.82.22	Application Server PUB-SUB Servers Parameters	2-78
2.82.23	Application Server QCK Server Parameters.....	2-79
2.82.24	Application Server Query Server Parameters	2-79
2.82.25	Application Server Remote Call Parameters	2-79
2.82.26	Application Server REN Server Parameters	2-79
2.82.27	Application Server SAM Server Parameters.....	2-79
2.82.28	Application Server Security Parameters	2-79

2.82.29	Application Server Slave Parameters.....	2-79
2.82.30	Application Server SMTP Parameters	2-80
2.82.31	Application Server Startup Parameters.....	2-80
2.82.32	Application Server Tools Parameters	2-80
2.82.33	Application Server Trace Parameters	2-81
2.82.34	Application Server Workstation Parameters	2-81
2.83	PeopleSoft Batch Server	2-81
2.83.1	Batch Server Application Engine Parameters.....	2-81
2.83.2	Batch Server Cache Parameters	2-81
2.83.3	Batch Server Crystal Parameters	2-81
2.83.4	Batch Server Database Parameters	2-82
2.83.5	Batch Server Data Mover Parameters	2-82
2.83.6	Batch Server Distribution Agent Parameters.....	2-82
2.83.7	Batch Server Integration Broker Parameters.....	2-82
2.83.8	Batch Server Configuration Parameters	2-82
2.83.9	Batch Server Interface Driver Parameters	2-82
2.83.10	Batch Server nVision Parameters	2-82
2.83.11	Batch Server Optimization Engine Parameters	2-83
2.83.12	Batch Server Process Scheduler Parameters	2-83
2.83.13	Batch Server Remote Parameters.....	2-83
2.83.14	Batch Server SMTP Parameters	2-83
2.83.15	Batch Server SQR Parameters	2-83
2.83.16	Batch Server Startup Parameters	2-84
2.83.17	Batch Server Tools Parameters	2-84
2.83.18	Batch Server Trace Parameters	2-84
2.83.19	Batch Server Tuxedo Parameters.....	2-84
2.84	PeopleSoft Database	2-84
2.84.1	Database Parameters	2-84
2.84.2	Database Language Parameters.....	2-85
2.84.3	Database Patch Parameters	2-85
2.84.4	Database Version Parameters	2-85
2.85	PeopleSoft Web Server	2-85
2.85.1	Web Server Configuration Parameters.....	2-85
2.85.2	Web Server Information Parameters.....	2-88
2.86	Presence Application.....	2-88
2.86.1	General	2-88
2.87	PushMail Application.....	2-88
2.87.1	General	2-88
2.88	Primavera	2-89
2.88.1	APPLICATION_GENERAL.....	2-89
2.88.2	APP_LIMITS.....	2-89
2.88.3	AUTHENTICATION	2-89
2.88.4	CONNPOOL	2-89
2.88.5	DATA_LIMITS.....	2-90
2.88.6	DBSESSION	2-90
2.88.7	DB_CONNECTION.....	2-90
2.88.8	DOC_REPOSITORY	2-90

2.88.9	EARNEDVALUEPREFS	2-90
2.88.10	EMAIL_NOTIFICATIONS	2-91
2.88.11	GROUP_SERVER.....	2-91
2.88.12	JAVA_OS.....	2-91
2.88.13	JAVA_PLUGIN	2-91
2.88.14	LOGSETTINGS	2-91
2.88.15	PERFMON	2-91
2.88.16	PREFS_OTHER	2-92
2.88.17	SERVICES	2-92
2.88.18	THREADPOOL	2-93
2.88.19	TIMESHEET_CONNECTION	2-93
2.88.20	TIMESHEET_OPTS	2-93
2.88.21	TRACER.....	2-93
2.88.22	USERSECURITY	2-93
2.88.23	WORKFLOW_REPOSITORY.....	2-93
2.88.24	WORKTIME_DATE	2-94
2.89	RAC Database.....	2-94
2.89.1	ASM Disk	2-94
2.89.2	Database Components	2-94
2.89.3	Database Scheduler Jobs	2-94
2.89.4	DB Invalid Objects	2-95
2.89.5	MGMT_DB_CPU_USAGE_ECM	2-95
2.89.6	MGMT_DB_USERS_ECM	2-95
2.89.7	Redologs.....	2-95
2.89.8	Voting Disk	2-95
2.90	Real-Time Collaboration	2-96
2.90.1	Real-Time Collaboration Command-Line Control Configuration	2-96
2.91	Search Application.....	2-96
2.91.1	General	2-96
2.92	Siebel Component.....	2-96
2.92.1	Siebel Component Configuration.....	2-96
2.93	Siebel Component Group	2-97
2.93.1	Siebel Component Group Configuration	2-97
2.94	Siebel Enterprise.....	2-97
2.94.1	Siebel Enterprise Configuration	2-97
2.95	Siebel Gateway	2-98
2.95.1	Siebel Gateway Configuration.....	2-98
2.96	Siebel Server.....	2-98
2.96.1	Siebel Server System Configuration.....	2-98
2.96.2	Siebel Server General Configuration	2-98
2.97	TimeManagement Application	2-99
2.97.1	General	2-99
2.98	UserDirectory Application	2-99
2.98.1	Attribute	2-99
2.98.2	Configuration Parameters	2-99
2.98.3	Custom Attributes	2-99
2.99	VoiceMessage Application Configuration	2-99

2.99.1	General	2-99
2.99.2	Facility Properties	2-99
2.100	Web Cache	2-100
2.100.1	Cluster Information	2-100
2.100.2	Cluster Members	2-100
2.100.3	Configuration Files	2-100
2.100.4	File Permission Check	2-100
2.100.5	Identity Check	2-100
2.100.6	Listening Ports	2-100
2.100.7	Log Growth Check	2-100
2.100.8	Log Level Check	2-101
2.100.9	Operations Ports	2-101
2.100.10	Origin Servers	2-101
2.100.11	Performance Related	2-101
2.100.12	Site Aliases	2-101
2.100.13	Host Mappings	2-101
2.101	WebDAV Application	2-102
2.101.1	General	2-102
2.101.2	Default Welcome Docs	2-102
2.102	Workspaces Application	2-102
2.102.1	General	2-102
2.103	XMPP Application	2-102
2.103.1	General	2-102
2.103.2	Domain Names	2-102
2.103.3	Search Fields	2-102
2.103.4	Supported Agents	2-103

Preface

This manual lists the configuration categories and their associated items for the target types from which Oracle Configuration Manager collects data.

Audience

This document is intended for all users of Oracle Configuration Manager.

Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible to all users, including users that are disabled. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at <http://www.oracle.com/accessibility/>.

Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

Deaf/Hard of Hearing Access to Oracle Support Services

To reach Oracle Support Services, use a telecommunications relay service (TRS) to call Oracle Support at 1.800.223.1711. An Oracle Support Services engineer will handle technical issues and provide customer support according to the Oracle service request process. Information about TRS is available at <http://www.fcc.gov/cgb/consumerfacts/trs.html>, and a list of phone numbers is available at <http://www.fcc.gov/cgb/dro/trsphonebk.html>.

Related Documents

For more information, see the following documents in the Oracle Configuration Manager documentation set:

- *Oracle Configuration Manager Installation and Administration Guide*
- *Oracle Configuration Manager Quick Start Guide*

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
<code>monospace</code>	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Introduction

This document lists the configuration items collected by Oracle Configuration Manager version 10.3.2. The configuration information is grouped according to collection targets such as the host, database, Web Cache, and so on.

This chapter lists the configuration categories and their items for the target types from which Oracle Configuration Manager collects data.

2.1 Application Deployment

The configuration categories and their associated configuration items for the Application Deployment target type follow.

2.1.1 Application Configuration

Path
Deployment Order
Type

2.2 Automatic Storage Management

The configuration categories and their associated configuration items for the Automatic Storage Management target type follow.

2.2.1 ASM Instance Properties

Host
Port
SID

2.3 CalDAV Application

The configuration categories and their associated configuration items for the CalDAV Application target type follow.

2.3.1 General

Collection Browsing Enabled
Default Future Time Period In Day
Default Past Time Period In Day

2.4 Calendar Applications

The configuration categories and their associated configuration items for the Calendar Applications target type follow.

2.4.1 Calendar Application HTTP Server Configuration

Category Name
Property Name
Property Value

2.5 Calendar Server

The configuration categories and their associated configuration items for the Calendar Server target type follow.

2.5.1 Calendar Server Basic Configuration

Calendar
Server Host
Port

2.5.2 Calendar Configuration

Calendar Log Level
Calendar Maximum LDAP Connection

2.5.3 Calendar Server Configuration

Category Name
Property Name
Property Value

2.6 Cluster Database

The configuration categories and their associated configuration items for the Cluster Database target type follow.

2.6.1 Database Configuration Version

Installed Version
Collection Version

2.6.2 Control Files

File Name
Status
Creation Date

2.6.3 CPU Usage

Database ID
Version
Time at which the CPU usage changed
CPU count of the database
CPU socket count of the database

2.6.4 Data Files

File Name

Status
Autoextensible
Increment
Maximum File Size
OS Storage
Initial Size
Database Name

2.6.5 Instance Information

Database Name
Global Name
Version
Host
Instance Name
Instance Startup Time
Restricted Mode
Archive Log Mode
Read Only Mode
Default Temporary Tablespace
Database Character Set
National Character Set
Creation Date
Release
Edition
Database Version
Is 64bit
Release Status

2.6.6 Feature Usage

Name
Version
Currently Used
Ever Used
First Usage Date
Aux Count
Feature Information
Total Samples
Last Usage Date
Last Sample Date
Last Sample Period
Database ID
Detected Usages

2.6.7 High-Water Mark

Name
Version
Highwater
Last Value
Database ID

2.6.8 Database License

- Session Maximum
- Sessions Warning
- Sessions Highwater
- Users Maximum

2.6.9 Database Options

- Name
- Selected

2.6.10 Redo Logs

- Group Number
- Members
- File Name
- Log Size
- Thread Number

2.6.11 Rollback Segments

- Name
- Status
- Tablespace Name
- Extents
- Initial Size
- Next Size
- Maximum Extents
- Minimum Extents
- Percent Increase
- Optimal Size
- Average Active
- Wraps
- Shrinks
- Average Shrink
- High Water Mark Size

2.6.12 Tablespaces

- Tablespace Name
- Contents
- Status
- Extent Management
- Allocation Type
- Logging
- Initial Extent
- Next Extent
- Increment
- Maximum Extents
- Segment Space Management
- Block Size
- Minimum Extents
- Minimum Extent Size
- Big File

2.6.13 Database Users

User Name
User ID
Default Tablespace
Temporary Default Tablespace
Created
Profile
Expiry Date

2.6.14 High Availability - Database Files

Name
Total Size

2.6.15 High Availability - General Information

Dbid
Log Mode
Force Logging
Database Role
Flashback On

2.6.16 High Availability - Initialization Parameters

Name
Value

2.6.17 High Availability - RMAN Configuration

Name
Value

2.6.18 STATS Pack Configuration

Is Installed
Snapshot Frequency

2.7 Conference Application

The configuration categories and their associated configuration items for the Conference Application target type follow.

2.7.1 General

Default Dialout Call Timeout
Default Participant Codec
Default SIP Participant Codec
Default Voice Participant Mode
OWC Host Wait Session Timeout
OWC Log Flush Period
OWC Media Host Service Bus Address Prefix
OWC Media Host Service Load Balance Bus Address Suffix
OWC Roster Service Bus Address Prefix
OWC Roster Service Load Balance Bus Address Suffix
OWC Use Remote Media Sessions

SIPP STN Gateway IP Address
SIPP STN Gateway Port

2.8 Contract Management Server Database

The configuration categories and their associated configuration items for the Contract Management Server Database target type follow.

2.8.1 CM Admin and group Database information

Database Name
JNDI Name
User Name
Connect String
Project Count
User count

2.8.2 CM Database Information

DB Service Type
Schedule DB Type
Boot strap Connect String
Database version and OS

2.8.3 CM Admin and group Database upgrade Version history

Database Name
From Version
To Version
Date Converted
Remarks
Conversion Status

2.9 Contract Management Server

The configuration categories and their associated configuration items for the Contract Management Server target type follow.

2.9.1 Contract Manager Configuration Parameters

Web Version
Ear Size
EAR Date
Build ID
Word Version
Word Operational on Server
MS Word version on server
Word Scratch Location
App Server Host Name
App Server Type
Domain Home
Protocol
Web Port
SMTP Server
JDK Path

JVM Max Heap Size
 Session Time out
 XML Session Timeout
 Repository Type
 Repository URL Host
 Authentication Mode
 LDAP Host
 LDAP Port
 LDAP User
 Is Standalone
 Print Debug Level
 Report Images Location
 Contract Manager Home

2.10 Database Instance

The configuration categories and their associated configuration items for the Database Instance target type follow.

2.10.1 ASM Disk

This metric captures ASM Disks details which has status other than MEMBER.

Name	Description	Data Type	Sample Value
Instance ID	Instance ID	NUMBER	1
Group Number	Group Number	NUMBER	1
Disk Number	Disk Number	NUMBER	1
Header Status	Header Status	VARCHAR2	UNKNOWN
Path	Path	VARCHAR2	ORCL:VOL3

2.10.2 Control Files

File Name
 Status
 Creation Date

2.10.3 CPU Usage

Database ID
 Version
 Time at which the CPU usage changed
 CPU count of the database
 CPU socket count of the database

2.10.4 Database Components

Namespace
 Component ID
 Component Name
 Version
 Status
 Schema

2.10.5 Database Configuration Version

Installed Version
Collection Version

2.10.6 Database License

Session Maximum
Sessions Warning
Sessions Highwater
Users Maximum

2.10.7 Database Options

Name
Selected

2.10.8 Database Scheduler Jobs

This metric captures GATHER_STATS_JOB details from DBA_SCHEDULER_JOBS.

Name	Description	Data Type	Sample Value
Owner	Owner of the object	VARCHAR2	SYS
Job Name	Job Name	VARCHAR2	GATHER_STATS_JOB
State	State	VARCHAR2	SCHEDULED
Schedule Name	Scheduler Name	VARCHAR2	MAINTENANCE_WINDOW_GROUP
Owner	Owner of the object	VARCHAR2	SYS

2.10.9 Database Users

User Name
User ID
Default Tablespace
Temporary Default Tablespace
Created
Profile
Expiry Date

2.10.10 Data Files

File Name
Status
Autoextensible
Increment
Maximum File Size
OS Storage
Initial Size
Database Name

2.10.11 DB Invalid Objects

This metric captures owner-wise count of the invalid objects for the database.

Name	Description	Data Type	Sample Value
Owner	Owner of the object	VARCHAR2	SYSMAN
Invalid Objects Count	Count of invalid objects	NUMBER	2

2.10.12 Feature Usage

Name
 Version
 Currently Used
 Ever Used
 First Usage Date
 Aux Count
 Feature Information
 Total Samples
 Last Usage Date
 Last Sample Date
 Last Sample Period
 Database ID
 Detected Usages

2.10.13 High Availability - Database Files

Name
 Total Size

2.10.14 High Availability - General Information

Dbid
 Log Mode
 Force Logging
 Database Role
 Flashback On

2.10.15 High Availability - Initialization Parameters

Name
 Value

2.10.16 High Availability - RMAN Configuration

Name
 Value

2.10.17 High-Water Mark

Name
 Version
 Highwater
 Last Value
 Database ID

2.10.18 Initialization Parameters

Name
Value
Is Default

2.10.19 Instance Information

Database Name
Global Name
Version
Host
Instance Name
Instance Startup Time
Restricted Mode
Archive Log Mode
Read Only Mode
Default Temporary Tablespace
Database Character Set
National Character Set
Creation Date
Release
Edition
Database Version
Is 64bit
Release Status

2.10.20 MGMT_DB_CPU_USAGE_ECM

DBID
Version
Time at which the CPU usage changed
CPU count of the database
CPU core count of the database
CPU socket count of the database

2.10.21 MGMT_DB_USERS_ECM

User Name
User ID
Default Tablespace
Default Temporary Tablespace
Created
Profile
Expiry date

2.10.22 Redo Logs

Group Num
Status
Members
File Name
Archived
Log Size
Sequence Num
First Change SCN

OS Storage
Thread Num
Type - Type of Redo logs

2.10.23 Rollback Segments

Name
Status
Tablespace Name
Extents
Initial Size
Next Size
Maximum Extents
Minimum Extents
Percent Increase
Optimal Size
Average Active
Wraps
Shrinks
Average Shrink
High Water Mark Size

2.10.24 STATS Pack Configuration

Is Installed
Snapshot Frequency

2.10.25 System Global Area

Name
Size

2.10.26 Tablespaces

Tablespace Name
Contents
Status
Extent Management
Allocation Type
Logging
Initial Extent
Next Extent
Increment
Maximum Extents
Segment Space Management
Block Size
Minimum Extents
Minimum Extent Size
Big File

2.11 DeviceManagement Application

The configuration categories and their associated configuration items for the DeviceManagement Application target type follow.

2.11.1 Blocked Devices

Device ID
Description

2.11.2 General

Uncertified Device Allowed

2.12 Email Application

The configuration categories and their associated configuration items for the Email Application target type follow.

2.12.1 CSI

Stream Buffer Size
Stream Max Read Size
Stream Max Write Size
Stream PreFetch Size
Stream Timeout

2.12.2 General

Directory Cache TTL
Global Domain Name
IMAP Enabled
Max Directory Cache Entries
Max Mail Size
SMTP Enabled
Timeout Checking Interval
SaveParseErrorEmails

2.12.3 SubjectSortingGroupingRules

SubjectSortingGroupingRules

2.12.4 IMAP

Assume Single EndPoint
Folder Polling Interval
Port
Login Error Threshold
Parse Error Threshold
Session Timeout
Cache Message Size
ClientKeepAliveInterval
Folder Cache Directory
FolderOpenBatchSize
Max Folder Cache Size
Max Sessions
Message Load Batch Size
Search Support Level
Server Session Concurrency
Show Instance Name Banner
Surrogate Auth

2.12.5 IMAP Endpoint Properties

Endpoint Name
Endpoint Scheme

2.12.6 Local Email Patterns

Local Email Patterns

2.12.7 Non Local Email Patterns

Non Local Email Patterns

2.12.8 Persistence

Durable FileRoot
MaxFile Cache Size
TempFile Root
Copy Batch Size
Delete Batch Size
Max DB Connection Retry
Move Batch Size
Undelete Batch Size
Update Flags Batch Size
Pld Store Cache Linger
Pld Store Maximum Mem Cached Records
Pld Store Maximum Open FDs
Pld Store Record Cache Size
Pld Store Stream Buffer Size

2.12.9 SubjectSortingReplacementRules

SubjectSortingReplacementRules

2.12.10 SMTP

Assume Single Endpoint
Authentication
Port
DSN Enabled
Send Mail Even If No TLS
Server Session Concurrency
Use TLS

2.12.11 SMTP Endpoint Properties

Endpoint Name
Endpoint Scheme

2.12.12 VMS Properties

VMS Name
Custom Display Name
Custom Domain Name
Custom Product Version
Log All Exceptions

- Max Aborted Transitions Per Session
- Max Bad Transitions Per Session
- Max Command Line Size
- Max Recipients Per Transaction
- Max Rejected Addresses Per Session
- Max Size Before Attack Suspected
- Max Size Abort Transaction
- Max Useless Commands Per Session
- Next Command Timeout
- Next Data Chunk Timeout
- Quit Write Timeout
- Reject All
- Suppress Received From
- Suppress Response Text
- Use Default Display Name
- Use Default Domain Name
- Use Default Max Size
- Use Default Product Version
- Auth Mandatory
- Show Instance Name In Banner

2.12.13 Transport

- Accept Invalid Local Users
- Delivery Concurrency
- InMemory Queue Size
- LocalDelivery BatchSize
- Max Retry Period
- Processing Enabled
- Relay Server
- Retry Interval
- Scan On Upload
- Simple Relay Mode
- SMTP Delivery Batch Size
- SMTP Delivery Checkpoint
- Thread Pool Size
- Keep Alive Interval
- Maximum DB Message Queue Percentage
- Minimum DB Message Queue Percentage
- Queue Poll Interval

2.13 E-Mail Housekeeper

The configuration categories and their associated configuration items for the E-Mail Housekeeper target type follow.

2.13.1 E-Mail Housekeeper Instance Mailstore Configuration

- Mailstore Name
- Instance ID
- Property Name
- Property Value

2.14 E-Mail IMAP Server

The configuration categories and their associated configuration items for the E-Mail IMAP Server target type follow.

2.14.1 E-Mail IMAP Instance Mailstore Configuration

Mailstore Name
Instance ID
Property Name
Property Value

2.15 E-Mail List Server

The configuration categories and their associated configuration items for the E-Mail List Server target type follow.

2.15.1 E-Mail List Server Instance Mailstore Configuration

Mailstore Name
Instance ID
Property Name
Property Value

2.16 E-Mail NNTP Inbound Server

The configuration categories and their associated configuration items for the E-Mail NNTP Inbound Server target type follow.

2.16.1 E-Mail NNTP Inbound Instance Mailstore Configuration

Mailstore Name
Instance ID
Property Name
Property Value

2.17 E-Mail NNTP Outbound Server

The configuration categories and their associated configuration items for the E-Mail NNTP Outbound Server target type follow.

2.17.1 E-Mail NNTP Outbound Instance Mailstore Configuration

Mailstore Name
Instance ID
Property Name
Property Value

2.18 E-Mail POP Server

The configuration categories and their associated configuration items for the E-Mail POP Server target type follow.

2.18.1 E-Mail POP Instance Mailstore Configuration

Mailstore Name
Instance ID
Property Name
Property Value

2.19 E-Mail SMTP Inbound Server

The configuration categories and their associated configuration items for the E-Mail SMTP Inbound Server target type follow.

2.19.1 E-Mail SMTP Inbound Instance Mailstore Configuration

Mailstore Name
Instance ID
Property Name
Property Value

2.20 E-Mail SMTP Outbound Server

The configuration categories and their associated configuration items for the E-Mail SMTP Outbound Server target type follow.

2.20.1 E-Mail SMTP Outbound Instance Mailstore Configuration

Mailstore Name
Instance ID
Property Name
Property Value

2.21 E-Mail Virus Scrubber

The configuration categories and their associated configuration items for the E-Mail Virus Scrubber target type follow.

2.21.1 E-Mail Virus Scrubber Instance Mailstore Configuration

Mailstore Name
Instance ID
Property Name
Property Value

2.22 FTP Application

The configuration categories and their associated configuration items for the FTP Application target type follow.

2.22.1 General

Channel Security
Data Connection Port
DMS Instrumentation
FTP Server Enabled

- Max DC Port Count
- Port
- Session Timeout
- Upload BufferSize
- Default DataPort
- Listening Point
- Default Command Characterset
- Internal IP

2.23 Host

The configuration categories and their associated configuration items for the Host target type follow.

2.23.1 File Systems

- Resource Name
- Mount Location
- Type
- Mount Options
- Disk Space (GB)
- Local Drive
- Available Disk Space (GB)

2.23.2 Hardware

- Host Name
- Domain
- Vendor Name
- System Config
- Machine Architecture
- Clock Frequency (MHz)
- Memory Size (MB)
- Local Disk Space (GB)
- CPU Count
- CPU Board Count
- I/O Card Count
- Fan Count
- Power Supply Count
- Boot Disk Volume Serial Number
- System BIOS
- System Serial Number
- Available Local Disk Space (GB)
- Available Memory (MB)

2.23.3 Hardware CPU

- Vendor Name
- Frequency (MHz)
- ECache (MB)
- IMPL
- Revision
- Mask
- Siblings

2.23.4 Host User Defined Products

Product Name
Product Version
Product Vendor
Product Type

2.23.5 I/O Devices

Name
Vendor Name
Frequency (MHz)
Bus
Revision

2.23.6 Network Information Configuration

Name
Flags
Maximum Transfer Unit
INET Address
Mask
Broadcast Address
MAC Address
Hostname Aliases
Description
Default Gateway
DHCP Enabled

2.23.7 Operating System

Name
Vendor Name
Base Version
Update Level
Distributor Version
Max Swap Space (MB)
Address Length (bits)
Platform ID
Maximum Process Virtual Memory (MB)
Timezone
Timezone Region
Timezone Delta

2.23.8 Operating System Components

Name
Type
Version
Installation Date
Description

2.23.9 Operating System Modules

Name
Size (Bytes)

Referring Modules

2.23.10 Operating System Properties

Name
Source
Value

2.23.11 Operating System Registered Software

ID
Name
Vendor Name
Version
Installation Date
Installed Location
Description
Vendor Specific Information

2.23.12 Operating System Running Products

Command
Application ID
Mapper Version

2.23.13 Operating System ULIMITs

CPU Time
File Blocks
Data Blocks
Stack
Coredump
Number of Files
Virtual Memory

2.23.14 Host User Defined Products

Product Name
Product Version

2.24 IAS Configuration

The configuration categories and their associated configuration items for the IAS Configuration target type follow.

2.24.1 Console

Protocol for Agent
Host for Agent
Port for Agent
Path for Agent
Protocol for Application Server Control
Host for Application Server Control
Port for Application Server Control

2.24.2 DCM Auto Archive Check

Column	Description	Collected From
Count	Whether auto archive is enabled for DCM (enabled if the value is not zero)	Output of the <code>dcmctl set</code> command, Auto Archive Count parameter

2.24.3 Debug Log Level Check

Column	Description	Collected From
Component Codes	OPMN components to configure logging for	"Comp" attribute of the "debug" tag in <code>opmn.xml</code>
Rotation Size	Size at which to rotate the log	"Rotation-size" attribute of the "debug" tag in <code>opmn.xml</code>

2.24.4 Log Level Check

Column	Description	Collected From
Element	OPMN component ("notification-server" or "process-manager")	Name of the tag in <code>opmn.xml</code>
Level	Logging level for the component	"Level" attribute of the tag
Rotation Size	Size at which to rotate the log	"Rotation-size" attribute of the tag

2.25 IBM Websphere Install

The configuration categories and their associated configuration items for the IBM Websphere Install target type follow.

2.25.1 IBM Product Components

Name
Spec Version
Build Version
Build Date

2.25.2 IBM Products

Name
ID
Version
Build Level
Build Date

2.25.3 IBM Product Family

Name
Version

2.26 IM Application

The configuration categories and their associated configuration items for the IM Application target type follow.

2.26.1 General

- IM Buffer Stage Size
- IM Purging Period Timer
- IM EndPointDeath Detection Time
- Pending Messages Limit

2.27 JDEdwards Enterprise One

The configuration categories and their associated configuration items for the JDEdwards Enterprise One target type follow.

2.27.1 Data Sources

- Data Source Server Location
- Data Source Location
- Data Source Name
- Release
- Server
- Library Name
- OCM Data Source
- AS400 BLOB Data Source
- Decimal Shift
- Julian Date
- Use Table Owner
- Object Owner
- DLL Name
- Data Source Type
- Data Source Type Description
- Data Source Use
- Support Updates
- Platform Type
- Data Class
- Database Name
- Database Instance
- Port
- JDBNET
- Unicode
- LOB Support
- TNS_ODBC_JDBNET Data Source
- Future Use OCM3
- Future Use OCMC
- Future Use LL
- Future Use OMUI
- Future Use OMCC
- Future Use DSFC30
- Future Use DSFC10
- Future Use ENHV
- Future Use DSFF1

2.27.2 Environments

Environment
 Description
 Release
 Path Code
 JITI
 Change
 Developer
 WAN Configured
 Detached Mode
 Environment Code 3

2.27.3 Data Server (F9650)

Server
 Server Description
 Release
 Platform
 Platform Description
 Location
 Data Source Type
 Data Source Type Description

2.27.4 Deployment Servers (F9650)

Server
 Server Description
 Release
 Platform
 Platform Description
 Location
 Server Share Path
 Primary Deployment Server

2.27.5 Crystal Enterprise CMS

Server
 Server Description
 Release
 Platform
 Platform Description
 Location
 User

2.27.6 Enterprise Servers (F9650)

Server
 Port Number
 Server Description
 Release
 Platform
 Platform Description
 Location
 Logical Machine Name
 Data Source Type

Data Source Type Description
Server Map Data Source
Server Share Path
Deployment Server Name

2.27.7 Crystal Enterprise Web Server

Server
Port Number
Server Description
Release
Platform
Platform Description
Location

2.27.8 Web Servers (F9650)

Server
Port Number
Server Description
Release
Platform
Platform Description
Location
Primary JAS Server
Protocol
Server URL
Default Login
Installation Path
Deployment Server

2.27.9 Windows Terminal Server (F9650)

Server
Server Description
Release
Platform
Platform Description
Location

2.27.10 Path Codes

Path Code
Description
Machine Key
Server Share Path
Status Code
Merge Option
Release
Database Type
Data Source
UNC Flag

2.27.11 Updates

- Update Name
- Release
- From Release
- To Release
- Update Description
- Update Type
- Update Type Description
- Date

2.27.12 Data Indicators

- Usage Data Indicator Type
- Description
- Release
- Metric ID
- Description
- Value 1
- Value 2

2.28 JDEdwards Enterprise One Collaborative Portal

The configuration categories and their associated configuration items for the JDEdwards Enterprise One Collaborative Portal target type follow.

2.28.1 Standalone Agent Managed Instances

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Instance Target Type Description

2.28.2 Standalone Agent Managed Instances Attributes

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Instance Attribute
- Instance Attribute Description
- Instance Attribute Value

2.28.3 Standalone Agent Managed Instance JAS INI

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Section
- Item
- Value

2.28.4 Standalone Agent Managed Instances JDBJ INI

- Standalone Agent Install Location
- Instance Name
- Instance Target Type

Section
Item
Value

2.28.5 Standalone Agent Managed Instances JDE INI

Standalone Agent Install Location
Instance Name
Instance Target Type
Section
Item
Value

2.29 JDEdwards Enterprise One Enterprise Server

The configuration categories and their associated configuration items for the JDEdwards Enterprise One Enterprise Server target type follow.

2.29.1 Standalone Agent Managed Instances

Standalone Agent Install Location
Instance Name
Instance Target Type
Instance Target Type Description

2.29.2 Standalone Agent Managed Instance Attributes

Standalone Agent Install Location
Instance Name
Instance Target Type
Instance Attribute
Instance Attribute Description
Instance Attribute Value

2.29.3 Standalone Agent Managed Instance JDE INI

Instance Name
Instance Target Type
Section
Item
Value

2.30 JDEdwards Enterprise One Management Console

The configuration categories and their associated configuration items for the JDEdwards Enterprise One Management Console target type follow.

2.30.1 Management Console Agent

Management Console Install Location

2.30.2 Management Console Agent Attributes

Management Console Install Location
Agent Attribute

Agent Attribute Description
Agent Attribute Value

2.30.3 Management Console JAS INI

Management Console Install Location
Section
Item
Value

2.30.4 Management Console JDBC INI

Management Console Install Location
Section
Item
Value

2.30.5 Management Console Managed Homes

Management Console Install Location
Managed Home Host
Managed Home Install Location

2.30.6 Management Console Managed Instances

Management Console Install Location
Managed Home Host
Managed Home Install Location
Instance Name
Instance Target Type
Instance Target Type Description

2.31 JDEdwards Enterprise One PIM Synch Server

The configuration categories and their associated configuration items for the JDEdwards Enterprise One PIM Synch Server target type follow.

2.31.1 Standalone Agent Managed Instances

Standalone Agent Install Location
Instance Name
Instance Target Type
Instance Target Type Description

2.31.2 Standalone Agent Managed Instance Attributes

Standalone Agent Install Location
Instance Name
Instance Target Type
Instance Attribute
Instance Attribute Description
Instance Attribute Value

2.31.3 Standalone Agent Managed Instance JAS INI

Standalone Agent Install Location
Instance Name
Instance Target Type
Section
Item
Value

2.31.4 Standalone Agent Managed Instance JDBJ INI

Standalone Agent Install Location
Instance Name
Instance Target Type
Section
Item
Value

2.32 JDEdwards Enterprise One Standalone Agent

The configuration categories and their associated configuration items for the JDEdwards Enterprise One Standalone Agent target type follow.

2.32.1 Standalone Agent

Standalone Agent Install Location

2.32.2 Standalone Agent Attributes

Standalone Agent Install Location
Agent Attribute
Agent Attribute Description
Agent Attribute Value

2.32.3 Standalone Agent Managed Instances

Standalone Agent Install Location
Instance Name
Instance Target Type
Instance Target Type Description

2.33 JDEdwards Enterprise One Transaction Server

The configuration categories and their associated configuration items for the JDEdwards Enterprise One Transaction Server target type follow.

2.33.1 Standalone Agent Managed Instances

Standalone Agent Install Location
Instance Name
Instance Target Type
Instance Target Type Description

2.33.2 Standalone Agent Managed Instance Attributes

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Instance Attribute
- Instance Attribute Description
- Instance Attribute Value

2.33.3 Standalone Agent Managed Instance JAS INI

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Section
- Item
- Value

2.33.4 Standalone Agent Managed Instance JDBJ INI

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Section
- Item
- Value

2.34 JDEdwards Enterprise One Web Server

The configuration categories and their associated configuration items for the JDEdwards Enterprise One Web Server target type follow.

2.34.1 Standalone Agent Managed Instances

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Instance Target Type Description

2.34.2 Standalone Agent Managed Instance Attributes

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Instance Attribute
- Instance Attribute Description
- Instance Attribute Value

2.34.3 Standalone Agent Managed Instance JAS INI

- Standalone Agent Install Location
- Instance Name
- Instance Target Type
- Section
- Item
- Value

2.34.4 Standalone Agent Managed Instance JDBJ INI

Standalone Agent Install Location
Instance Name
Instance Target Type
Section
Item
Value

2.35 JServ

The configuration categories and their associated configuration items for the JServ target type follow.

2.35.1 Configuration Files

Name
Name
Size (Bytes)
Modification Time

2.35.2 JServ Zones

Zone Name

2.36 OC4J

The configuration categories and their associated configuration items for the OC4J target type follow.

2.36.1 Applications

Application
Parent Application

2.36.2 Configuration Files

Display File Path Name
File Path Name
File Size (Bytes)
Modification Time

2.36.3 Connection Pools

Name
Application
Class
JDBC URL

2.36.4 Data Sources

Name
Application
JNDI Location
Class

JDBC Driver
JDBC URL

2.36.5 Deployed Applications

Application Name

2.36.6 Global Web Module Settings

JSP Mode

2.36.7 Log Growth Check

Column	Description	Collected From
Java Options	Command-line Java startup options	"Java-options" module data from the "start-parameters" category of an OC4J component in opmn.xml
OC4J Options	Command-line OC4J startup options	"OC4J-options" module data from the "start-parameters" category of an OC4J component in opmn.xml

2.36.8 Managed Data Sources

Name
Application
JNDI Location
Connection Pool

2.36.9 Modules

Application
Module
Module Type

2.36.10 Native Data Sources

Name
Application
JNDI Location
Class
JDBC URL

2.36.11 Port Ranges

Service
Port Range

2.36.12 Resource Usage

Starting Heap Size (MB)
Maximum Heap Size (MB)
Number of JVMs

2.36.13 Web Module Settings

Application
Module
JSP Mode
Session Timeout (seconds)
Can Be Distributed

2.36.14 Web Module URLs

Module
Application
URL Mapping
Load on Startup

2.37 OHS Configuration

The configuration categories and their associated configuration items for the OHS Configuration target type follow.

2.37.1 File Permission Check

Column	Description
File Path	File Path
File Mode	UNIX file permissions
User ID	UNIX file owner
Group ID	UNIX file group

2.37.2 Identity Check

Column	Description	Collected From
Virtual Host	Virtual host name	Argument to a VirtualHost directive in httpd.conf
User ID	UNIX user that handles requests for this virtual host	Value of a User directive in httpd.conf
Group ID	UNIX group that handles requests for this virtual host	Value of a Group directive in httpd.conf

2.37.3 Log Growth Check

Column	Description	Collected From
Virtual Host	Virtual host name	Argument to a VirtualHost directive in httpd.conf
Log Name	Log type, either CustomLog, ErrorLog, or TransferLog	Name of the directive in httpd.conf
Value	Value of the directive (log path and information about how to append to the log)	Not Applicable

2.37.4 Log Level Check

Column	Description	Collected From
Virtual Host	Virtual host name	Argument to a VirtualHost directive in httpd.conf
Directive	Either LogLevel, SSLLogLevel, RewriteLogLevel, ScriptLog, or PlsqliLogEnable	Not Applicable
Value	Value of the directive (the logging level)	Not Applicable

2.37.5 Virtual Hosts

IP Address
Port
Host
Type

2.38 Oracle Agent Deployment Configuration

The configuration categories and their associated configuration items for the Oracle Agent Deployment Configuration target type follow.

2.38.1 MGMT_ECM_EMD_JAVA_PARAMS

Java Home
Class path and classpath.lst
Host class path
Java options
Java definitions
Java Version - Collects the Agent Java Version

2.39 Oracle Application Server

The configuration categories and their associated configuration items for the Oracle Application Server target type follow.

2.39.1 Configuration Files

Name
Name
Size (Bytes)
Modification Time

2.39.2 Console

Protocol for Agent
Host for Agent
Port for Agent
Path for Agent
Protocol for Application Server Control
Host for Application Server Control
Port for Application Server Control

2.39.3 DCM

DCM Repository Type

2.39.4 Deployed Applications

OC4J Instance
Name

2.39.5 General

Install Type
Infrastructure Database
Version

2.39.6 Components

Display Name
Type
Name

2.39.7 OPMN

Request Port
Remote Port
Local Port
Use SSL
Log Level for ONS
Log Level for Process Manager

2.40 Oracle Beehive Site Configuration

The configuration categories and their associated configuration items for the Oracle Beehive Site Configuration target type follow.

2.40.1 Application Server

Primary Host Name
Application Server Instance
Oracle Home
Timezone
OPMN Local Port
OPMN Remote Port
OPMN Request Port

2.40.2 HTTP Server

Primary Host Name
Application Server Instance
HTTP Server

2.40.3 OC4J

Primary Host Name
Application Server Instance
OC4J Name

2.40.4 Database

Type
Connect Descriptor
Schema Name

2.40.5 LDAP

Type
HostName
Port
SSL Port

2.40.6 Virtual Server

BTI Client Port
BTI Secure Client Port
FTP Port
HTTP Port
HTTP SSL Enabled
HTTP SSL Port
IMAP Port
IMAP SSL Enabled
IMAP SSL Port
Server Name
SMTP Authentication Required
SMTP Port
SMTP SSL Enabled
SMTP SSL Port
XMPP Port
XMPP SSL Enabled
XMPP SSL Port

2.41 Oracle Business Intelligence (BI) Analytics Server

The configuration categories and their associated configuration items for the Oracle BI Analytics Server target type follow.

2.41.1 BI Analytics Server Configuration Parameters

Product Version
Cache Enable
Cache Replace Algorithm
Maximum Rows Per Cache Entry
Maximum Cache Entry Size
Maximum Cache Entries
Maximum Global Cache Entries
Cache Poll Seconds
Locale
Sort Memory Size
Sort Buffer Increment Size
Sort Memory Size
SSL
RPC Service or Port Number
Maximum Session Limit

Server Thread Range
 DB Gateway Thread Stack Size
 Maximum Expanded Sub Query Predicates
 Maximum Query Plan Cache Entries
 Maximum Drill Down Info Cache Entries
 Maximum Drill Down Query Cache Entries
 Enable DB Hints
 Cluster Participant
 Disconnected
 ODBC350
 OCI7
 OCI8e
 OCI8i
 OCI10g
 DB2CLI
 DB2CLI35
 NQXML
 XMLA
 Strong Date Time Check

2.42 Oracle Business Intelligence (BI) Cluster Controller

The configuration categories and their associated configuration items for the Oracle BI Cluster Controller target type follow.

2.42.1 BI Cluster Controller Configuration Parameters

Product Version
 Enable Controller
 Primary Controller
 Servers
 Server Poll Seconds
 Controller Poll Seconds
 Client Server Port
 Client Controller Port
 Monitor Controller Port
 Monitor Server Port
 Schedulers
 SSL
 SSL Certificate File
 SSL Private-Key File
 SSL PK Pass Phrase File
 SSL PK Pass Phrase Program
 SSL Verify Peer
 SSL CA Certificate Directory
 SSL CA Certificate File
 SSL Cert Verification Depth

2.42.2 BI DAC Server Properties

Product Version
 Type
 Connect String
 Host
 Port

Database User Name
JDBC Driver
JDBC URL
EMail Host
EMail Protocol
EMail User
EMail Address

2.42.3 BI DAC ETL Summary

Step Name
SRCDB Name
Trgt DB Name
Step Type Name
Phase Name
Exec Name
RS Status
Server Name
RS Status Desc
RS Start TS
RS End TS
RS Success Rows
RS Failed Rows
RS Error Code

2.43 Oracle Business Intelligence (BI) DAC

The configuration categories and their associated configuration items for the Oracle BI DAC target type follow.

2.43.1 BI DAC Server Properties

Product Version
Type
Connect String
Host
Port
Database User Name
JDBC Driver
JDBC URL
EMail Host
EMail Protocol
EMail User
EMail Address

2.43.2 BI DAC ETL Summary

Step Name
SRCDB Name
Trgt DB Name
Step Type Name
Phase Name
Exec Name
RS Status
Server Name

RS Status Desc
RS Start TS
RS End TS
RS Success Rows
RS Failed Rows
RS Error Code

2.44 Oracle Business Intelligence (BI) Presentation Server

The configuration categories and their associated configuration items for the Oracle BI Presentation Server target type follow.

2.44.1 BI Presentation Server Configuration Parameters

Product Version
Configuration Directory
Connection Expire Minutes
Connection Maximum Concurrent Establish
Corda Lib Directory
CSV Charset
Data Directory
Debug Startup
Default Message Directory
Disconnected
Disconnected Directory
Drillability Status
DSN
Enable 508
Force Refresh
Java Home
Maintenance Mode
On Demand Answers
Persistent Storage State
System Subject Area
Use Replication
Allowed Languages
Allowed Locale

2.44.2 BI Presentation Server Alerts Configurations

Content Delivery Mode
Default Delivery Disposition
Default Delivery Format
Embed Resources Inline
Enabled
Force 7bit ASCII Attachment Names
Ignore Webcat Delivery Profiles
MHTML Mime Type
Schedule Server
Session Cleanup Frequency Seconds
Session Timeout Seconds
UpperCase Recipient Names

2.44.3 BI Presentation Server Cache Configurations

Cache Refresh Optimize

2.44.4 BI Presentation Server Charts Configurations

Default Image Type

Maximum Completion Time (Seconds)

Maximum Processing Threads

2.44.5 BI Presentation Server Client Configurations

Auto Flush Enabled

SSO Server Variable

SSO Strip Windows Domain

2.44.6 BI Presentation Server Display Configurations

Allow Remember Password

Collapsible Sections Default

Dashboard Inline Load

Disable Pivot Table Auto Preview

ShowPage Tabs Always

Show Section Headings Default

Maximum DropDown Values

Reload Inline

2.44.7 BI Presentation Server Marketing Configurations

Marketing FunctionShip Fixed Random

Marketing FunctionShip Percent Random

Marketing Use BOM

Marketing Wrap Column Headers

Marketing Cache Use Temp Table

2.44.8 BI Presentation Server Other Configurations

Admin URL

Server URL

Volume

Web URL

Catalog Path

Completely Disable

Preload DBG Help

Listener

2.44.9 BI Presentation Server Report Cache Configurations

Disk Resave Minutes

Memory Buckets

Memory Cleanup Interval Minutes

Verify Reloaded Entry Key

2.44.10 BI Presentation Server State Pool Configurations

Memory Buckets

Memory Minimum Bucket Size
Verify Reloaded Entry Key

2.44.11 BI Presentation Server Thread Pool Configurations

Idle Thread Timeout Secs
Worker Thread Size Kb
Maximum Threads
Worker Thread Size Kb

2.44.12 BI Presentation Server XML Cache Defaults

Memory Buckets
Memory Minimum Bucket Size
Verify Reloaded Entry Key

2.45 Oracle Business Intelligence (BI) Scheduler Server

The configuration categories and their associated configuration items for the Oracle BI Scheduler Server target type follow.

2.45.1 BI Scheduler

Product Version
Admin Name
Bulk Fetch Buffer Size
CLI Type
Cluster Port
DSN
Default Script Path
Log All SQL Statements
Maximum Exec Threads
Minimum Exec Threads
Number of DB Connections
Part Of Cluster
Pause On Startup
Pool Timeout
Pool Username
Port String
Purge Inst Days
Purge Interval Minutes
Scheduler Script Path
Target Type
Temp Path
Table Error Messages
Table Instances
Table Jobs
Table Parameters
Java Host Server
Certificate PrivateKey FileName
Certificate FileName
Certificate Verify Depth
Passphrase FileName
Use SSL
Verify Peer

- Script RPC Port
- Auth PWD
- Auth User
- Server
- Service
- System

2.45.2 BI Schedule IBOTS

- Debug
- Keep Error Log Files
- Log Purge Days
- Log Directory
- Maximum Delivery SleepSecs
- Maximum Global SleepSecs
- Maximum Request SleepSecs
- MaxRows Times Columns
- Minimum Delivery Sleep Secs
- Minimum Global Sleep Secs
- Minimum Request Sleep Secs
- Number Of Delivery Retries
- Number Of Global Retries
- Number Of Request Retries
- Web Server

2.45.3 BI Scheduler Mail

- From
- Max Recipients
- Password
- SMTP Port
- SMTP Server
- Sender
- SMTP CA Certificate Directory
- SMTP CA Certificate Verification Depth
- Try
- Use Bcc
- Use SSL

2.46 Oracle Business Intelligence (BI) Web Plugin

The configuration categories and their associated configuration items for the Oracle BI Web Plugin target type follow.

2.46.1 BI Web Plugin

- Product Version
- Data Directory
- Temporary Directory
- Address
- Port
- Certificate Validation Depth
- Credential Alias
- SSL Version
- SSL Enabled Dir

Key Store Path

2.47 Oracle Cluster

The configuration categories and their associated configuration items for the Oracle Cluster target type follow.

2.47.1 Cluster Manager Configuration

Property
Value
Config File

2.47.2 High Availability Cluster Interconnect

Interface Name
Node Name
Subnet
IP Address
Is Public

2.47.3 Server Configuration

Property
Value
Config File

2.48 Oracle Concurrent Manager

The configuration categories and their associated configuration items for the Oracle Concurrent Manager target type follow.

2.48.1 Concurrent Processing Package Versions

Package
Type
Version

2.48.2 Concurrent Processing Profile Options

Profile Option Name
Profile Option ID
Profile Option Value
Level ID
Application Short Name
User Profile Option Name
SQL Validation
Description

2.48.3 ICM Settings

Name
Value

2.48.4 Concurrent Managers (Service Instances)

- Application ID
- Concurrent Queue Name
- Service
- Application Short Name
- Target Node
- Target
- Primary
- Secondary
- Enabled
- Cache Size
- Resource Consumer Group
- Program Library
- Diagnostic Level
- Sleep Seconds

2.48.5 Specialization Rules

- Manager
- Action
- Type
- Object

2.48.6 Summary Configuration

- Setting
- Status

2.48.7 Workshifts for Concurrent Managers

- User Concurrent Queue Name
- Time Period Application ID
- Concurrent Time Period Name
- Time Period App Short Name
- Description
- Minimum Processes
- Maximum Processes
- Sleep Seconds
- Service Parameters

2.49 Oracle Configuration Manager

The configuration categories and their associated configuration items for the Oracle Configuration Manager target type follow.

2.49.1 Oracle Configuration Manager Package Versions

- Package Name
- Package Version
- Build Date
- Package Platform
- Package Architecture

2.49.2 Oracle Configuration Manager Parameter Values

Parameter Name
Parameter Category
Parameter Value
File Name

2.50 Oracle E-Business Suite

The configuration categories and their associated configuration items for the Oracle E-Business Suite target type follow.

2.50.1 Number of Active Users

Number of Active Users

2.50.2 Applied Patches (January to December) - Collected by Month

Applied Patch ID
Patch Number
Patch Type
Applied Date

2.50.3 Applications Customer Forms

Menu Name
Sequence
Submenu
Function Name
Type
Prompt
Description
Application Short Name
Form Name

2.50.4 Applications System Summary

Applications System Name
Release Name
Multi-Organization Flag
Multi-Lingual Flag
Multi-Currency Flag

2.50.5 Applications Topology

Node Name
Platform
Administration
Database
Concurrent Processing
Forms
Web

2.50.6 Comprising Patches (January to December) - Collected by Month

Applied Patch ID

Patch Name

2.50.7 Component Version

Component
Version

2.50.8 Configuration Version

Installed Version
Collection Version

2.50.9 Custom Alert Information

Alert Name
Alert
Application Short Name
Table Name
Description

2.50.10 Custom Applications

Application Short Name
Application Name
Basepath

2.50.11 Profile Options Registered Under Custom Application

Profile Option Name
Application Short Name
User Profile Option Name
SQL Validation
Description

2.50.12 Custom Audit Group Information

Table Name
Table Value
Enabled
Application Short Name
Group Name
Description
User Table Name

2.50.13 Custom Database Objects

Object Name
Object Type
Owner
Status

2.50.14 Custom Hooks

Module
Call Package
Call Procedure

2.50.15 Custom Message Count

Application Short Name
Number Of Custom Messages

2.50.16 Custom Objects Owned by Apps

Object Name
Object Type
Owner
Status

2.50.17 Custom Request Sets

Request Set Name
User Request Set Name
Request Set
Application Short Name

2.50.18 Responsibility Count

Application Short Name
Number of User Defined Responsibilities

2.50.19 Custom Triggers

Trigger Name
Object Type
Owner
Status

2.50.20 Custom Value Sets - Table Validated

Flex Value Set Name
Description
Meaning

2.50.21 Custom Value Sets (Other than Table Validated)

Flex Value Set Name
Description
Meaning

2.50.22 Custom Workflows

Object
Type
Description

2.50.23 Registered Data Groups

Data Group ID
Data Group Name
Default Group Flag
Creation Date

2.50.24 Database Version

Banner

2.50.25 End-Dated Users

Number of End-Dated Users

2.50.26 Generic Service Components

Component ID
Component Name
Component Type
Component Type Display Name
Concurrent Queue Name
Concurrent Queue Display Name
Container Type
Container Type Display Name
Inbound Agent Name
Inbound Agent Display Name
Outbound Agent Name
Outbound Agent Display Name
Startup Mode
Startup Mode Display Name

2.50.27 Generic Service Component Parameters

Component Parameter ID
Parameter Name
Parameter Display Name
Parameter Value
Default Parameter Value
Encrypted Flag
Allow Reload Flag

2.50.28 High Priority Patches Not Applied

Bug Number
Release
Baseline

2.50.29 JTF Hooks

Number of Custom JTF Hooks

2.50.30 Localization Modules

Application Short Name
Oracle User Name
Module Short Name
Module Version
Status
Last Update Date

2.50.31 NLS Language Support

Installed Flag
Language Code
NLS Language

2.50.32 Other Customizations

Function Name
User Function Name
Type
Application Name
HTML Call

2.50.33 Patchset Information

Application Short Name
Application Name
Patch Level
Creation Date
Product Version
Status

2.50.34 Printers

Printer Name
Printer Type

2.50.35 Printer Drivers

Printer Driver Name
Description

2.50.36 User Profile Options

Profile Option Name
Profile Option ID
Profile Option Value
Level ID
Application Short Name
User Profile Option Name
SQL Validation
Description

2.50.37 Technology Stack Inventory (DB)

Technology Components
Component Version/Value

2.51 Oracle E-Business Suite Infrastructure

The configuration categories and their associated configuration items for the Oracle E-Business Suite Infrastructure target type follow.

2.51.1 Appswweb Configuration

Section
Property Name
Property Value

2.51.2 Appswweb Configuration Metadata

Display File Path
File Path
File Size
Modification Time
File Mode
File Owner

2.51.3 Applications Context Files

Path
Node Name
Context Name
Context Type
Version

2.51.4 Dbc File

Property Name
Property Value

2.51.5 Dbc File Meta

Display File Path
File Path
File Size
Modification Time
File Mode
File Owner

2.51.6 Custom Context Variables

Path
Node Name
OA Var
Type
OA Var Value
OA Var Name
Category

2.51.7 Environments Context Variables

Path
Node Name
OA Var
Type
OA Var Value
OA Var Name
Category

2.51.8 Global Context Variables

Path
Node Name
OA Var
Type
OA Var Value
OA Var Name
Category

2.51.9 Host Context Variables

Path
Node Name
OA Var
Type
OA Var Value
OA Var Name
Category

2.51.10 Install Context Variables

Path
Node Name
OA Var
Type
OA Var Value
OA Var Name
Category

2.51.11 Processes Context Variables

Path
Node Name
OA Var
Type
OA Var Value
OA Var Name
Category

2.51.12 System Context Variables

Path
Node Name
OA Var
Type
OA Var Value
OA Var Name
Category

2.51.13 Technology Stack Inventory (File System)

Tier
Technology Components
Component Version/Value

2.51.14 Workflow Mailer Configuration

Property Name	Property Value
---------------	----------------

2.51.15 Workflow Mailer Configuration Metadata

Display File Path
File Path
File Size
Modification Time
File Mode
File Owner

2.52 Oracle Enterprise Manager 10g Grid Control Management Agent

The configuration categories and their associated configuration items for the Oracle Enterprise Manager 10g Grid Control Management Agent target type follow.

2.52.1 Agent Configuration Parameters

Agent URL
Agent Version
Repository URL
Agent Timezone
Metric Browser Enabled
Upload Interval (Mins)
Upload Backoff%
Upload Timeout (secs)
Upload File Size (kb)
Maximum Size Allowed Upload Directory (MB)
Maximum Number of Files Allowed in Upload Directory (MB)
Maximum Amount% of Disk Allowed in Upload Directory (MB)
Agent Listening on All NICS
Agent Listening on All NICS
SSL Session Cache Enabled
Timeout Primary Header (Secs)
Timeout Secondary Headers (Secs)
Timeout Body (Secs)
Dynamic Property Timeout (Secs)
Timeout for RAC Database (Secs)
Timeout for Database (Secs)
OMS Version Agent Connects to
Character Set Used by OMS
Protocol Version Used by OMS
Email Address for OOB
Email Gateway for OOB
Email from Address

2.52.2 Java Parameters

Java Home
Class Path and classpath.lst
Host Class Path
Java Definitions

2.52.3 Log Parameters

- Maximum Log Size (MB)
- Maximum Rolls for Log File
- Maximum Trace File Size (MB)
- Maximum Rolls for Trace File

2.52.4 Perl Parameters

- Perl Binary Home
- Perl Trace Level

2.53 Oracle Enterprise Manager 10g Grid Control Management Repository

The configuration categories and their associated configuration items for the Oracle Enterprise Manager 10g Grid Control Management Repository target type follow.

2.53.1 EM Repository Monitory Agents

- Agent Name

2.53.2 EM Repository Monitored Beacons

- Beacon Name

2.53.3 EM Repository Configuration Parameters

- Type of Repository
- Repository Version

2.53.4 OMS Name

- Names of OMS Connecting to Repository
- ORACLE_HOME of the OMS

2.54 Oracle Enterprise Manager 10g Grid Control Management Service

The configuration categories and their associated configuration items for the Oracle Enterprise Manager 10g Grid Control Management Service target type follow.

2.54.1 OMS Configuration Parameters

- Server Name
- Server Port
- HTTPS Port
- Server Host
- Ping Command
- OOB Shutdown
- OOB Crash
- Large Repository
- Repository User
- Repository Server
- Repository Port
- Repository SID

- Repository Connect String
- Email Address
- Email from Address
- Email from Name
- Email Gateway
- IP UI Enable
- Public Servlet Enabled
- iSqlPlus URL
- iSqlPlus WebDBA URL
- Dump Modules
- EM Keyfile Location

2.55 Oracle EPM Calc Manager

The configuration categories and their associated configuration items for the Oracle EPM Calc Manager target type follow.

2.55.1 Database Connection

- Database Type
- JDBC URL

2.55.2 Instance Information

- Version

2.55.3 Web Application Deployment

- Application Server Type
- LWA Host
- LWA Port

2.56 Oracle EPM Architect

The configuration categories and their associated configuration items for the Oracle EPM Architect target type follow.

2.56.1 Database Connection

- Database Type
- JDBC URL

2.56.2 Instance Information

- Version

2.56.3 Web Application Deployment

- Application Server Type
- LWA Host
- LWA Port

2.57 Oracle EPM ERPI

The configuration categories and their associated configuration items for the Oracle EPM ERPI target type follow.

2.57.1 Database Connection

Database Type
JDBC URL

2.57.2 Instance Information

Version

2.57.3 Web Application Deployment

Application Server Type
LWA Host
LWA Port

2.58 Oracle EPM Essbase Administration Service

The configuration categories and their associated configuration items for the Oracle EPM Essbase Administration Service target type follow.

2.58.1 Instance Information

Version

2.58.2 Web Application Deployment

Application Server Type
LWA Host
LWA Port

2.59 Oracle EPM Essbase Provider Service

The configuration categories and their associated configuration items for the Oracle EPM Essbase Provider Service target type follow.

2.59.1 Instance Information

Version

2.59.2 Web Application Deployment

Application Server Type
LWA Host
LWA Port

2.60 Oracle EPM Essbase Server

The configuration categories and their associated configuration items for the Oracle EPM Essbase Server target type follow.

2.60.1 Instance Information

- Version
- 32-64 mode
- Essbase App Location
- ESSLANG
- Agent Port
- App Start Port
- App End Port
- Server Thread
- Agent Threads
- Net Retry
- Net Delay
- Dynamic Calculator Cache
- BlockSize

2.61 Oracle EPM Financial Management

The configuration categories and their associated configuration items for the Oracle EPM Financial Management type follow.

2.61.1 Database Connection

- Database Type
- OleDb Driver

2.61.2 Instance Information

- Version
- DCOM User

2.62 Oracle EPM Financial Reporting

The configuration categories and their associated configuration items for the Oracle EPM Financial Reporting type follow.

2.62.1 Instance Information

- Version

2.62.2 Web Application Deployment

- Application Server Type
- LWA Host
- LWA Port

2.63 Oracle EPM HSS

The configuration categories and their associated configuration items for the Oracle EPM HSS target type follow.

2.63.1 Database Connection

- Database Type
- JDBC URL

2.63.2 Instance Information

Version

2.63.3 Security Options Setting

Token Timeout

Logging Level

Delegated User Management

2.63.4 Security Service Providers

Name

Type

Host

Port

SSL Enabled

Base DN

Id Attribute

Trusted

2.63.5 Web Application Deployment

Application Server Type

LWA Host

LWA Port

2.64 Oracle EPM Performance Scorecard

The configuration categories and their associated configuration items for the Oracle EPM Performance Scorecard target type follow.

2.64.1 Database Connection

Database Type

JDBC URL

2.64.2 Instance Information

Version

2.64.3 Web Application Deployment

Application Server Type

LWA Host

LWA Port

2.65 Oracle EPM Planning

The configuration categories and their associated configuration items for the Oracle EPM Planning target type follow.

2.65.1 Business Rules

MYOLAP_Enabled

Css_refresh
Launch_log_dateformat
Launch_log_Log_Calc_script
Launch_log_filename
HBR_Cache
HBR_Cache_refresh_rate
Plugin_data_refresh_rate

2.65.2 Database Connection

Database Type
JDBC URL

2.65.3 Instance Information

Version

2.65.4 Web Application Deployment

Application Server Type
LWA Host
LWA Port

2.66 Oracle EPM Profitability

The configuration categories and their associated configuration items for the Oracle EPM Profitability target type follow.

2.66.1 Database Connection

Database Type
JDBC URL

2.66.2 Instance Information

Version

2.66.3 Web Application Deployment

Application Server Type
LWA Host
LWA Port

2.67 Oracle EPM RA Framework

The configuration categories and their associated configuration items for the Oracle EPM RA Framework target type follow.

2.67.1 Database Connection

Database Type
JDBC URL

2.67.2 Instance Information

Version

2.67.3 Web Application Deployment

Application Server Type

LWA Host

LWA Port

2.68 Oracle EPM System

The configuration categories and their associated configuration items for the Oracle EPM System target type follow.

2.68.1 Database Connection

JDBC URL

2.68.2 Instance Information

Version

2.69 Oracle EPM Web Analysis

The configuration categories and their associated configuration items for the Oracle EPM Web Analysis target type follow.

2.69.1 Instance Information

Version

2.69.2 Web Application Deployment

Application Server Type

LWA Host

LWA Port

2.70 Oracle EPM Workspace

The configuration categories and their associated configuration items for the Oracle EPM Workspace target type follow.

2.70.1 Database Connection

Database Type

JDBC URL

2.70.2 Instance Information

Version

2.70.3 Web Application Deployment

Application Server Type

LWA Host
LWA Port

2.71 Oracle Exadata Storage Server Software

The configuration categories and their associated configuration items for the Oracle Exadata Storage Server Software (Exadata Cell) target type follow.

2.71.1 CELL Celldisk Configuration

Attribute	Description
Name	Unique name of the cell disk
Celldisk Comment	User comment for the cell disk
Creation Time	Time stamp when the cell disk was created
Device Name	Operating system device name of the LUN used by the cell disk
Device Partition	Operating system device name of the partition that is used by the cell disk
Error Count	Number of errors that occurred on the cell disk
Free Space (GB)	Amount of unused space available on the cell disk
ID	Global unique identifier (GUID) that is generated when the cell disk is created
LUN	ID of the LUN on which the cell disk is located
Raid Level	Value of the RAID level that is currently used on the LUN, for example, RAID 0.
Celldisk Size (GB)	Total size of the cell disk
Celldisk Status	Current status of the cell disk, such as <code>normal</code> or <code>importRequired</code>

2.71.2 Oracle Cell Configuration

Attribute	Description
Cell Name	Unique name for the cell
BMC Type	Name and version of the BMC
Cell Version	Version of the cell software
CPU Count	Number of CPUs on the cell
Fan Count	Count of working fans and total fans, displayed as working/total
ID	Global unique identifier (GUID) supplied by the hardware vendor
Interconnect Count	Number of network interconnects
IORM Boost	Ratio of the cumulative number of positions in the I/O queue that were skipped because of IORM scheduling to the number of I/Os that were scheduled. This ratio is calculated by sampling the changes each minute in the two numbers.
IP Address 1	IP address 1 for the cell
IP Address 2	IP address 2 for the cell
IP Address 3	IP address 3 for the cell

Attribute	Description
IP Address 4	IP address 4 for the cell
Kernel Version	Version of the host kernel software
Make Model	Make and mode of the cell hardware supplied by the vendor
Metric History Days	Number of days that metric history, alert history, and ADR files are retained. The default is 7 days.
Power Count	Count of power supplies, displayed as working/total. Not available on HP hardware.

2.71.3 CELL Griddisk Configuration

Attribute	Description
Griddisk Name	Unique name of the grid disk
Available To	Names of the clients that can access this grid disk
Cell Disk	Name of the cell disk that contains the grid disk
Griddisk Comment	User-supplied text string
Creation Time	Time stamp when the grid disk was created
Error Count	Count of hardware errors detected by the cell disk containing this grid disk
ID	Global unique identifier (GUID) that is generated when the grid disk is created
Lowest Offset (MB)	Lowest byte offset of the grid disk on the physical disk
Griddisk Size (MB)	Total size of the grid disk
Griddisk Status	Current status of the grid disk, such as <code>active</code> , <code>inactive</code> , <code>not present</code> , or <code>importRequired</code>

2.71.4 CELL IORM Configuration

Attribute	Description
IO Resource Plan Name	Unique name of the interdatabase plan. The name value is automatically set to <code>cellname_IORMPLAN</code> .
Category Plan	Allocation plan for the categories set up in the databases using the cell
DB Plan	Allocation plan for the databases using the cell
Status	Current status of the interdatabase plan, either <code>active</code> or <code>inactive</code> .

2.71.5 CELL LUN Configuration

Attribute	Description
LUN Name	Unique name assigned to the LUN. This might be different (or extended from) the LUN ID if the ID is not unique.
Cell Disk	Name of the cell disk associated with the LUN. This is empty if the LUN is not associated with a cell disk.
Device Name	Operating system device name for the LUN, for example, <code>/dev/cciss/c1d5</code>

Attribute	Description
ID	Identifier assigned by the system
System LUN	If value is <code>TRUE</code> , then the disk is a system disk. If the value is <code>FALSE</code> , then the disk is not a system disk, and only has data on it.
Auto Create	Indicator whether the LUN was automatically created. Values are <code>TRUE</code> or <code>FALSE</code> . Single-disk LUNs are automatically created when disks without LUNs are converted to cell disks. For example, <code>CREATE DISK ALL</code> creates single-disk LUNs for all physical disks without LUNs. These single-disk LUNs have this attribute set to <code>TRUE</code> .
LUN Size (GB)	Raw size of the LUN before being converted to a cell disk
Physical Devices	Physical disk names that form the LUN
Raid Level	Value of the RAID level that is used on the LUN, for example, <code>RAID 0</code> .
LUN Status	Status of the LUN, which can be <code>normal</code> , <code>warning</code> , or <code>critical</code> .

2.71.6 CELL Physical Disk Configuration

Attribute	Description
Physical Disk Name	Unique name of the physical disk
ID	Identifier assigned by the system
LUN	List of LUNs converted from this physical disk
Insert Time	Time that the disk was inserted
Disk Size (GB)	Size of the disk in bytes
Physical Disk Status	Status of the physical disk. Values can be <code>normal</code> , <code>warning</code> , or <code>critical</code> .

2.72 Oracle Grid Control Repository

The configuration categories and their associated configuration items for the Oracle Grid Control Repository target type follow.

2.72.1 Object Privileges

This metric captures `EXECUTE` permissions for `SYSMAN` on `UTL_FILE`, `UTL_SMTP` and `UTL_TCP` objects. If the Grid Control Repository owner `SYSMAN` is not explicitly granted `EXECUTE` on the `UTL_FILE`, `UTL_SMTP` and `UTL_TCP` packages, it will break several major functionalists of Grid or DB Control.

Name	Description	Data Type	Sample Value
Grantee	Name of Grantee	VARCHAR2	SYSMAN
Privilege	Kind of Privilege	VARCHAR2	EXECUTE
Table Name	Name of the table	VARCHAR2	UTL_FILE
Grantor	Name of Grantor	VARCHAR2	SYS
Owner	Name of Owner	VARCHAR2	SYS

2.73 Oracle Home

The configuration categories and their associated configuration items for the Oracle Home target type follow.

2.73.1 Dependency Rules

Referencer Name
Referencer Version
Dependee Name
Dependee Version

2.73.2 Oracle Oneoff Patches

ID
Is Rollbackable
XML Inventory Location
Installer Version
Timestamp

2.73.3 Oracle Oneoff Patches Bugs Fixed

Id
Bug Number

2.73.4 Oracle Oneoff PatchesComponents

Id
Component Name
Version

2.73.5 Oracle Software Components

Name
Version
Description
External Name
Languages
Installed Location
Installer Version
Minimum Deinstaller Version
Is Toplevel
Timestamp
Patch Version

2.73.6 Oracle Software Patchsets

Name
Version
Description
External Name
Installed Location
Minimum Installer Version
Timestamp

2.73.7 Oracle Versioned Patches

- Name
- Version
- Patchset Name
- Patchset Version
- Description
- External Name
- Languages
- Installed Location
- Minimum Deinstaller Version
- Timestamp

2.74 Oracle HTTP Server

The configuration categories and their associated configuration items for the Oracle HTTP Server target type follow.

2.74.1 SSL Ciphers Suite Settings

- SSL Virtual Host
- Cipher Suite

2.74.2 Configuration Files

- File Path
- File Path Name
- File Size (Bytes)
- Modification Time

2.74.3 General

- Document Root
- Default Port
- Server Name

2.74.4 Listen Addresses

- Listening IP Address
- Listening Port
- Listening Protocol

2.74.5 Performance Related

- Maximum Requests Processed Simultaneously
- Maximum Requests Handled by Each Child Process
- Maximum Spare Processes
- Minimum Spare Processes
- Processes to Create at Startup
- Allow Multiple Requests per Connection
- Maximum Requests per Connection
- Connection Timeout (seconds)
- SSL Session Timeout (seconds)
- DNS Hostname in Access Log
- Error Logging Level
- mod_oc4j Load Balancing Policy

Size of OC4J Connection Cache

2.74.6 Virtual Hosts

IP Address

Port

Host

Type

2.75 Oracle Hyperion Enterprise Performance Management (EPM) System

The configuration categories and their associated configuration items for the Oracle Hyperion Enterprise Performance Management (EPM) System target type follow.

2.75.1 EPM System (Root Node)

The metrics and metric columns for EPM System are:

- Instance Information
 - Version
- Registry Connection
 - JDBC URL

2.75.2 Foundation Shared Services

The metrics and metric columns for Foundation Shared Services are:

- Instance Information
 - Version
- Database Connection
 - Database Type
 - JDBC URL
- Web App Deployment
 - App Server Type
 - LWA Host
 - Port
- Security Service Providers
 - Name
 - Type
 - Host
 - Port
 - SSL Enabled
 - Base DN
 - ID Attribute
 - Trusted

- Security Options Setting
 - Token Timeout
 - Logging Level
 - Delegated User Management

2.75.3 Foundation Workspace

The metrics and metric columns for Foundation Workspace are:

- Instance Information
 - Version
- Database Connection
 - Database Type
 - JDBC URL
- Web App Deployment
 - App Server Type
 - LWA Host
 - Port

2.75.4 EPM Architect

The metrics and metric columns for EPM Architect are:

- Instance Information
 - Version
- Database Connection
 - Database Type
 - JDBC URL
- Web App Deployment
 - App Server Type
 - LWA Host
 - Port

2.75.5 Calc Manager

The metrics and metric columns for Calc Manager are:

- Instance Information
 - Version
- Database Connection
 - Database Type
 - JDBC URL
- Web App Deployment
 - App Server Type

- LWA Host
- Port

2.75.6 Essbase (Agent Port)

The metric and metric columns for Essbase (Agent Port) are:

- Instance Information
 - Version
 - 32-64 mode
 - Essbase App Location
 - ESSLANG
 - Agent Port
 - App Start Port
 - App End Port
 - Server Thread
 - Agent Threads
 - Net Retry
 - Net Delay
 - Dynamic Calculator Cache
 - BlockSize

2.75.7 Essbase (Web App Port)

Target type is oracle_epm_eas. The metrics and metric columns are:

- Instance Information
 - Version
- Web App Deployment
 - App Server Type
 - LWA Host
 - Port

2.75.8 Essbase (Web App Port)

Target type is oracle_epm_aps. The metrics and metric columns are:

- Instance Information
 - Version
- Web App Deployment
 - App Server Type
 - LWA Host
 - Port

2.75.9 Planning

The metrics and metric columns for Planning are:

- Instance Information
 - Version
- Database Connection
 - Database Type
 - JDBC URL
- Web App Deployment
 - App Server Type
 - LWA Host
 - Port
- Business Rules
 - MYOLAP_Enabled
 - Css_refresh
 - Launch_log_dateformat
 - Launch_log_Log_Calc_Script
 - Launch_log_filename
 - HBR_Cache
 - HBR_Cache_refresh_rate
 - Plugin_data_refresh_rate

2.75.10 Financial Management

The metrics and metric columns for Financial Management are as follows. HFM limitation limits to only one instance per machine.

- Instance Information
 - Version
 - DCOM User
- Database Connection
 - Database Type
 - OLEDB Driver

2.75.11 Performance Scorecard

The metrics and metric columns for Performance Scorecard are:

- Instance Information
 - Version
- Database Connection
 - Database Type
 - JDBC URL

- Web App Deployment
 - App Server Type
 - LWA Host
 - Port

2.75.12 Profitability and Cost Management

The metrics and metric columns for Profitability and Cost Management are:

- Instance Information
 - Version
- Database Connection
 - Database Type
 - JDBC URL
- Web App Deployment
 - App Server Type
 - LWA Host
 - Port

2.75.13 ERP Integrator

The metrics and metric columns for ERP Integrator are:

- Instance Information
 - Version
- Database Connection
 - Database Type
 - JDBC URL
- Web App Deployment
 - App Server Type
 - LWA Host
 - Port

2.75.14 Report & Analysis (Web App Port)

Target type is oracle_epm_ra_framework. The metrics and metric columns for Report & Analysis are:

- Instance Information
 - Version
- Database Connection
 - Database Type
 - JDBC URL
- Web App Deployment

- App Server Type
- LWA Host
- Port

2.75.15 Report & Analysis (Web App Port)

Target type is oracle_epm_web_analysis. The metrics and metric columns for Report & Analysis are:

- Instance Information
 - Version
- Web App Deployment
 - App Server Type
 - LWA Host
 - Port

2.75.16 Report and Analysis (Web App Port)

Target type is oracle_epm_fr. Target type is oracle_epm_web_analysis. The metrics and metric columns for Report & Analysis are:

- Instance Information
 - Version
- Web App Deployment
 - App Server Type
 - LWA Host
 - Port

2.76 Oracle iAS Farm

The configuration categories and their associated configuration items for the Oracle iAS Farm target type follow.

2.76.1 Farm Configuration

Farm Name
Version

2.77 Oracle Internet Directory

The configuration categories and their associated configuration items for the Oracle Internet Directory target type follow.

2.77.1 Oracle Internet Directory Configuration

Oracle Internet Directory Connect Descriptor
Oracle Internet Directory Host
Oracle Internet Directory Port
Oracle Internet Directory Secure Port

2.78 Oracle Listener

The configuration categories and their associated configuration items for the Oracle Listener target type follow.

2.78.1 Listener Status

- TNS Address
- Alias
- Version
- Start Date
- Trace Level
- Security
- SNMP Status
- SID List

2.79 Oracle Retail

The configuration categories and their associated configuration items for the Oracle Retail target type follow.

2.79.1 Oracle Retail Active Retail Intelligence Application

- Version
- Install Date

2.79.2 Oracle Retail Allocation Java Application

- Version
- Install Date

2.79.3 Oracle Retail Back Office Java Application

- Version
- Install Date
- Application Name
- AppServer Instance Profile
- Deployment Stack

2.79.4 Oracle Retail Central Office Java Application

- Version
- Install Date
- Application Name
- AppServer Instance Profile
- Deployment Stack

2.79.5 Oracle Retail Markdown Optimization

- Version
- Install Date

2.79.6 Oracle Retail Workspace

- Version

Install Date
Build Number

2.79.7 Oracle Retail Data Warehouse Database

Version
Install Date

2.79.8 Oracle Retail Merchandising System Application

Version
Install Date

2.79.9 Oracle Retail Returns Management Java Application

Version
Install Date
Application Name
AppServer Instance Profile
Deployment Stack

2.79.10 Oracle Retail Price Management Java Application

Version
Install Date

2.79.11 Oracle Retail Warehouse Management System Application

Version
Install Date

2.79.12 Oracle Retail Invoice Matching Java Application

Version
Install Date

2.79.13 Oracle RPAS Global Domain

Dimension

2.79.14 Oracle Retail Predictive Application Server

Module
Release
Release Date

2.79.15 Oracle RPAS Sub Domain

Position

2.79.16 Oracle Retail Store Inventory Management Java Application

Version
Install Date

2.79.17 Oracle Retail Integration Bus Java Application

- Application Name
- Application Type
- Database URL
- Database User
- JNDI URL
- JNDI Factory
- JNDI User
- JMS Server Home
- JMS URL
- JMS Port
- JMS User
- OAS Instance Name
- OC4J Instance Name
- Kernel Version
- Functional Artifact Version
- RIB PAK Version

2.80 Oracle WebLogic Server

The configuration categories and their associated configuration items for the Oracle WebLogic Server target type follow.

2.80.1 General Server Configuration

- Listen Port
- Administration Port
- Native IO Enabled
- Maximum Open Sockets
- Stuck Thread Maximum Time
- Stuck Thread Timer Interval
- Accept Backlog
- Login Timeout
- Managed Server Independence Enabled
- Low Memory GC Threshold
- Low Memory Granularity Level
- Low Memory Sample Size
- Low Memory Time Interval
- SSL Listen Port
- SSL Login Timeout
- Cluster Name
- Cluster Weight
- Machine Name

2.80.2 Virtual Host Configuration

- Name
- Deployment Order
- Front End Host
- Front End HTTP Port
- Front End HTTPS Port
- Virtual Host Names
- Network Access Point
- Log File Name

Logging Enabled
Maximum Post Size

2.80.3 Jolt Connection Pools Configuration

Name
Primary Addresses
Failover Addresses
Minimum Pool Size
Maximum Pool Size
Receive Timeout

2.80.4 Work Manager Configuration

Name
Ignore Stuck Threads
Minimum Threads
Maximum Threads
Request Class Type
Request Class Name
Capacity Constraint

2.80.5 Startup and Shutdown Classes Configuration

Name
Type
Class Name
Deployment Order

2.80.6 JDBC DataSource Configuration

Name
JNDI Name
Row Prefetch Enabled
Row Prefetch Size
Two Phase Commit Enabled
URL
Driver Name
Capacity Increment
Initial Capacity
Maximum Capacity
Connection Reserve Timeout
Inactive Connection Timeout
Statement Cache Size

2.80.7 JDBC Multi-DataSource Configuration

Name
JNDI Name
Algorithm Type
Datasource List

2.80.8 JMS Connection Factory Configuration

Name

Module Name
JNDI Name
Transaction Timeout
Acknowledge Policy
Maximum Messages
Send Timeout

2.80.9 JMS Topic Configuration

Name
Module Name
JNDI Name
Maximum Message Size
Maximum Bytes
Maximum Messages
Multicast Port

2.80.10 JMS Queue Configuration

Name
Module Name
JNDI Name
Maximum Message Size
Maximum Bytes
Maximum Messages

2.80.11 Resource Configuration

Start Heap
Maximum Heap

2.81 Oracle WebLogic Install

The configuration categories and their associated configuration items for the Oracle WebLogic Install target type follow.

2.81.1 Oracle WebLogic Product Components

Name
Version
Sub Component Names

2.81.2 Oracle WebLogic Product

Name
Version
Service Pack Level
Patch Level
Status
Install Time
Install Directory
Java Home
Java Version
Java Vendor

2.82 PeopleSoft Application Server

The configuration categories and their associated configuration items for the PeopleSoft Application Server target type follow.

2.82.1 Application Server Analytics Parameters

- Maximum Instances
- Minimum Instances

2.82.2 Application Server Cache Parameters

- Maximum Cache Memory Settings

2.82.3 Application Server Configuration Parameters

- Configuration Path
- Domain
- GUID
- Host Name
- PeopleSoft Home
- State

2.82.4 Application Server Database Parameters

- Enable Database Monitoring
- Oracle Disable First Rows Hint
- PeopleSoft Database Maximum Cursors
- Sybase Packet Size Options
- Use Local Oracle Database Options

2.82.5 Application Server Domain Parameters

- Add to Path
- Allow Dynamic Changes
- Domain ID
- Log Fence
- Restartable
- Spawn Threshold
- Trace-Log File Character Set

2.82.6 Application Server Integration Broker Parameters

- Integration Broker Profile Information
- Message View Size
- Minimum Message Size for Compression
- Thread Pool Size

2.82.7 Application Server Interface Driver Parameters

- SCP Locale

2.82.8 Application Server Jolt Listener Parameters

- Address
- Client Cleanup Timeout

Client Connection Mode
Clients per Handler
Encryption
Initialize Timeout
Jolt Compression Threshold
Maximum Handlers
Minimum Handlers
Port

2.82.9 Application Server Jolt Relay Parameters

Listener Address
Listener Port

2.82.10 Application Server Message Broker Dispatcher Parameters

Allowed Consecutive Service Failures
Dispatch List Multiplier
Dispatcher Queue Maximum Queue Size
Handler Status Check Count
Maximum Ping Interval
Memory Queue Refresh Rate
Ping Rate
Recycle Count
Restart Period
Scan Interval

2.82.11 Application Server Message Broker Handler Parameters

Allowed Consecutive Service Failures
Maximum Instances
Maximum Retries
Minimum Instances
Recycle Count
Service Timeout

2.82.12 Application Server Options Parameters

Allowed Consecutive Service Failures
Auto Select Prompts
Maximum Fetch Size
Maximum Instances
Minimum Instances
Recycle Count
Service Timeout
Tuxedo Queue Size

2.82.13 Application Server Optimization Engine Parameters

Maximum Instances
Optimized Maximum General Services
Service Timeout

2.82.14 Application Server People Code Debugger Parameters

Debugger Message Log Enable
PSDBGSRV Listener Port

2.82.15 Application Server PPM Server Parameters

Maximum Instances
Minimum Instances

2.82.16 Application Server PSBRKDSP Server Parameters

Default Allowed Consecutive Service Failures
Default Dispatch List Multiplier
Default Dispatcher Queue Maximum Queue Size
Default Memory Queue Refresh Rate
Default Recycle Count
Default Restart Period
Default Scan Interval

The metrics and their sample values are:

Name	Sample Value
dflt_allowed_consec_service_failures	0
dflt_dispatch_list_multiplier	15
dflt_dispatcher_queue_max_queue_size	1000
dflt_recycle_count	0
dflt_restart_period	120
dflt_scan_interval	0
dflt_memory_queue_refresh_rate	1000

2.82.17 Application Server PSBRKHND Server Parameters

Default Allowed Consecutive Service Failures
Default Dispatch List Multiplier
Default Dispatcher Queue Maximum Queue Size
Default Memory Queue Refresh Rate
Default Recycle Count
Default Restart Period
Default Scan Interval

The metrics and their sample values are:

Name	Sample Value
dflt_allowed_consec_service_failures	0
dflt_dispatch_list_multiplier	15
dflt_dispatcher_queue_max_queue_size	1000
dflt_memory_queue_refresh_rate	1000
dflt_recycle_count	0

Name	Sample Value
dflt_restart_period	120
dflt_scan_interval	0

2.82.18 Application Server PSPUBDSP Server Parameters

Default Allowed Consecutive Service Failures
 Default Dispatch List Multiplier
 Default Dispatcher Queue Maximum Queue Size
 Default Memory Queue Refresh Rate
 Default Recycle Count
 Default Restart Period
 Default Scan Interval

The metrics and their sample values are:

Name	Sample Value
dflt_allowed_consec_service_failures	0
dflt_dispatch_list_multiplier	15
dflt_dispatcher_queue_max_queue_size	1000
dflt_memory_queue_refresh_rate	1000
dflt_recycle_count	0
dflt_restart_period	120
dflt_scan_interval	0

2.82.19 Application Server PSPUBHND Server Parameters

Default Allowed Consecutive Service Failures
 Default Dispatch List Multiplier
 Default Dispatcher Queue Maximum Queue Size
 Default Memory Queue Refresh Rate
 Default Recycle Count
 Default Restart Period
 Default Scan Interval

The metrics and their sample values are:

Name	Sample Value
dflt_allowed_consec_service_failures	0
dflt_dispatch_list_multiplier	15
dflt_dispatcher_queue_max_queue_size	1000
dflt_memory_queue_refresh_rate	1000
dflt_recycle_count	0
dflt_restart_period	120
dflt_scan_interval	0

2.82.20 Application Server PSSUBDSP Server Parameters

Default Allowed Consecutive Service Failures
Default Dispatch List Multiplier
Default Dispatcher Queue Maximum Queue Size
Default Memory Queue Refresh Rate
Default Recycle Count
Default Restart Period
Default Scan Interval

The metrics and their sample values are:

Name	Sample Value
dflt_allowed_consec_service_failures	0
dflt_dispatch_list_multiplier	15
dflt_dispatcher_queue_max_queue_size	1000
dflt_memory_queue_refresh_rate	1000
dflt_recycle_count	0
dflt_restart_period	120
dflt_scan_interval	0

2.82.21 Application Server PSSUBHND Server Parameters

Default Allowed Consecutive Service Failures
Default Dispatch List Multiplier
Default Dispatcher Queue Maximum Queue Size
Default Memory Queue Refresh Rate
Default Recycle Count
Default Restart Period
Default Scan Interval

The metrics and their sample values are:

Name	Sample Value
dflt_allowed_consec_service_failures	0
dflt_dispatch_list_multiplier	15
dflt_dispatcher_queue_max_queue_size	1000
dflt_memory_queue_refresh_rate	1000
dflt_recycle_count	0
dflt_restart_period	120
dflt_scan_interval	0

2.82.22 Application Server PUB-SUB Servers Parameters

Domain Slave Mode
Load Balance Interval
Message Segment from Database
Persistent Cursors on DB2 OS390
Serial Recycle

2.82.23 Application Server QCK Server Parameters

Allowed Consecutive Service Failures
 Maximum Fetch Size
 Maximum Instances
 Minimum Instances
 Recycle Count
 Service Time Out

2.82.24 Application Server Query Server Parameters

Allowed Consecutive Service Failures
 Maximum Fetch Size
 Maximum Instances
 Minimum Instances
 Recycle Count
 Service Time Out
 Use Dirty-Read

2.82.25 Application Server Remote Call Parameters

RCCBL Redirect

2.82.26 Application Server REN Server Parameters

Default Authentication Token
 Default HTTP Port
 Default HTTPS Port
 IO Buffer Size
 Log Severity Level

2.82.27 Application Server SAM Server Parameters

Allowed Consecutive Service Failures
 Maximum Fetch Size
 Maximum Instances
 Minimum Instances
 Recycle Count
 Service Timeout

2.82.28 Application Server Security Parameters

Validate Signon with Database

2.82.29 Application Server Slave Parameters

This metric captures failover configuration for Integration Broker. Dynamic slaves are configured in conjunction with domain failover. If a slave domain has the highest priority within a failover group, it can dynamically change to a master during failover. Dynamic slaves can be configured in the Failover Configuration page in the Service Operations Monitor.

Column	Description	Sample Value
MACHINE	Application Server Slaves; Server Name of Application Server	PTA156

Column	Description	Sample Value
PATH	Application Server Machine; Path of Domain Configuration	C:\PT80411\PSTOOLS
FAILOVERFLAG	Application Server Failover; Flag 0 or 1 to indicate Fail Over mode is enabled	1
FAILOVERTIME	Application Server Failover Time; Time (minutes) field, specify the number of minutes that can pass without the domain registering itself before the failover should commence.	120
SLAVEMODE	Application Server Slave Mode; 0 or 1 to indicate type of Slave	0

2.82.30 Application Server SMTP Parameters

SMTP Blackberry Reply To
SMTP Character Set
SMTP Client Certification Alias
SMTP Client Certification Alias 1
SMTP Encoding DLL
SMTP Guaranteed
SMTP Port
SMTP Port 1
SMTP Send Time
SMTP Sender
SMTP Server
SMTP Server 1
SMTP Source Machine
SMTP SSL Port
SMTP SSL Port 1
SMTP Trace
SMTP Use SSL
SMTP Use SSL 1

2.82.31 Application Server Startup Parameters

Connect ID
Connect Password
Database Name
Database Type
Server Name
User ID
User Password

2.82.32 Application Server Tools Parameters

Add to Class Path
Character Set
Database Flags
Enable PPM Agent
Java Virtual Machine Options
Non-proxy Hosts
Proxy Host
Proxy Port

Suppress Application Error Box
Suppress SQL Error

2.82.33 Application Server Trace Parameters

Dump Manager Objects at Crash
Dump Memory Image at Crash
Log Error Report
Mail Error Report
Trace AE
Trace Analytic
Trace Analytic Mask
Trace PC
Trace PC Mask
Trace PIA
Trace PIA Mask
Trace PPM
Trace PPR
Trace PPR Mask
Trace SQL
Trace SQL Mask

2.82.34 Application Server Workstation Parameters

Address
Client Cleanup Timeout
Encryption
Initialization Timeout
Maximum Clients per Handler
Maximum Handlers
Minimum Handlers
Port
Tuxedo Compression Threshold

2.83 PeopleSoft Batch Server

The configuration categories and their associated configuration items for the PeopleSoft Batch Server target type follow.

2.83.1 Batch Server Application Engine Parameters

Allowed Consecutive Service Failures
Maximum Fetch Size
Maximum Instances
Recycle Count
Scheduled Query Dirty-Read

2.83.2 Batch Server Cache Parameters

Cache Base Directory
Maximum Cache Memory

2.83.3 Batch Server Crystal Parameters

Trace

Trace File

2.83.4 Batch Server Database Parameters

Enable Database Monitoring
Oracle Disable First Rows Hint
Sybase Packet Size
Use Local Oracle Database

2.83.5 Batch Server Data Mover Parameters

Input Directory
Last Scripts Directory
Log Directory
Output Directory

2.83.6 Batch Server Distribution Agent Parameters

Allowed Consecutive Service Failures
Maximum Fetch Size
Maximum Instances
Minimum Instances
Recycle Count

2.83.7 Batch Server Integration Broker Parameters

Minimum Message Size for Compression

2.83.8 Batch Server Configuration Parameters

Configuration Path
Domain
GUID
Host Name
PeopleSoft Configuration Home
State

2.83.9 Batch Server Interface Driver Parameters

SCP Locale

2.83.10 Batch Server nVision Parameters

Drill Down Directory
Enable Drill Down for File
Enable Poll Dialogs
Instance Directory
Layout Directory
Macro Directory
Poll Dialog Seconds
Save Temporary File
Style Directory
Template Directory
Trace Level

2.83.11 Batch Server Optimization Engine Parameters

- Maximum Instances
- Optimization Maximum General Services
- Service Timeout

2.83.12 Batch Server Process Scheduler Parameters

- Allow Dynamic Changes
- Authentication Timeout
- COBOL Bin
- Crystal Report Writer Report Path
- Database Bin
- Default Printer
- File Chunk Size
- Log Directory
- Log Fence
- Log Output Directory
- Log Space Threshold
- Maximum Reconnect Attempt
- Output Directory Optional Extension
- Processor Version Name
- Reconnection Interval
- Temporary
- Tool Bin
- Tool Bin Server
- Trace-Log File Character Set
- Update Table Stats on Purge
- WinWord

2.83.13 Batch Server Remote Parameters

- Remote Call COBOL Redirect
- Remote Call COBOL Timeout

2.83.14 Batch Server SMTP Parameters

- SMTP Character Set
- SMTP Encoding DLL
- SMTP Port
- SMTP Port 1
- SMTP Send Time
- SMTP Sender
- SMTP Server
- SMTP Server 1
- SMTP Source Machine
- SMTP Trace

2.83.15 Batch Server SQR Parameters

- Enhanced HTML
- PeopleSoft SQR 1
- PeopleSoft SQR 2
- PeopleSoft SQR 3
- PeopleSoft SQR 4
- PeopleSoft SQR Flags

Print Log
SQR Bin

2.83.16 Batch Server Startup Parameters

Connect ID
Connect Password
Database Name
Database Type
Server Name
User ID
User Password

2.83.17 Batch Server Tools Parameters

Add to Class Path
Character Set
Database Flags
Enable PPM Agent
Java VM Options
Non-proxy Hosts
Proxy Host
Proxy Port
Suppress Application Error Box

2.83.18 Batch Server Trace Parameters

Trace Application Engine
Trace File
Trace Option
Trace Option Mask
Trace PC
Trace PPM
Trace SQL

2.83.19 Batch Server Tuxedo Parameters

Add to Path
Grace Period
Maximum Restart Attempt
Restartable
Spawn Threshold

2.84 PeopleSoft Database

The configuration categories and their associated configuration items for the PeopleSoft Database target type follow.

2.84.1 Database Parameters

Database Name
Database Server Name
Database Server Name Microsoft SQL
Database Type
GUID

- License Code
- License Group
- Long Name
- Maintenance Log Valid
- Owner ID
- PeopleTools Patch Level
- Product Category
- Short Name
- System Type
- Unicode

2.84.2 Database Language Parameters

- Language

2.84.3 Database Patch Parameters

- Database Fix By
- Database Maintenance Log Type
- Database Update ID

2.84.4 Database Version Parameters

- PeopleTools Release
- PeopleTools Release Bin
- Version

2.85 PeopleSoft Web Server

The configuration categories and their associated configuration items for the PeopleSoft Web Server target type follow.

2.85.1 Web Server Configuration Parameters

- Allow Unregistered Content
- Application Server
- Audit Password
- Authentication Token Domain
- Authentication Token Enabled Page
- Authentication User HTTP Interval
- Browser Configuration Error HTML
- Browser ID Last in Database
- Browser URL
- Bypass Signon
- Cache Menu on Web Server
- Cache Purge All Hit Count
- Cache Purge Stale Interval
- Cache Target Content
- Change Password on Expire
- Change Password on Warn
- Chart File System
- Chart URL
- Check for Duplicate Cookies
- Compress Cache Files
- Compress Mime Types

- Compress Query
- Compress Report Output
- Compress Report Output Netscape
- Compress Response
- Configuration Path
- Connection Information
- Cookies Required Page
- CSS File System
- CSS URL
- Custom Headers
- Debug Inline Java Script
- Debug Inline Style Sheet
- Debug Overlap
- Debug Save File
- Debug Show Layout
- Default Port
- Default Password
- Default Scheme
- Default User ID
- Default XML Link Password
- Default XML Link User ID
- Description in Database
- Enable Browser Cache
- Enable Debug Dump File
- Enable New Window
- Enable No Version
- Enable PPM Agent
- Enable Processing Wait
- Enable Report Repository
- Enable Trace
- Exception Page
- Expire Page
- Expire Page Content Name
- Help URL
- Ignore Parameter Template
- Image File System
- Image URL
- Is Clustering Configured
- Java Class Path
- Java Home
- Java Vendor
- Java Version
- Java Virtual Machine Information
- Java Virtual Machine Name
- Joltpooling
- JS File System
- JS URL
- Logout Page
- Maximum Saved State
- MCF Authentication Failure Page
- New Signon Session
- No Default Signon For Workflow
- No Exit Help
- Operating System Architecture
- Operating System Name

Operating System Version
Options
Pagelet Error Page
Password Expired Page
Password Warning Page
Physical Path
Portal Accept Compressed Encodings
Portal Cache Home Page on Browser
Portal Cache Objects
Portal Cache Stale Interval
Portal Compress Response
Portal Debug Cache
Portal Detail Error Page
Portal Home Page Stale Interval
Portal HTTP Port
Portal HTTPS Port
Portal Servlet Session Cookie Name
Portal Target Error Page
Portal Use Cached Proxied Java Script
Portal Use HTTP for Same Server
PPM Console
PPM Monitor Buffer Size
PPM Trace
PeopleSoft Discovery Client Name
PeopleSoft Discovery Complete
PeopleSoft Discovery Domain Name
PeopleSoft Discovery JVM ID
PeopleSoft Discovery Listener Address
PeopleSoft Discovery Listener Host
PeopleSoft Discovery Listener Port
PeopleSoft Discovery Listener Port Enabled
PeopleSoft Discovery Maximum Inactive Interval
PeopleSoft Discovery PeopleTools Release
PeopleSoft Discovery Server Information
PeopleSoft Discovery Servlet Context Name
PeopleSoft Discovery Session Cookie Domain
PeopleSoft Discovery Session Cookie Name
PeopleSoft Discovery Site Name
PeopleSoft Discovery SSL Listener Address
PeopleSoft Discovery SSL Listener Host
PeopleSoft Discovery SSL Listener Port
PeopleSoft Discovery SSL Listener Port Enabled
PeopleSoft Server
PeopleSoft Web Server Name
PeopleTools Performance Test Page URL
Public Session Timeout
Redirect Page
Relative URL
Report Repository Path
Save Confirm Display Time
Session Time Out
Signon Error Page
Signon Page
Signon Result Document Page
Signon Trace Page

- Single Thread NS
- SSL Required
- SSL Required Page
- Start Page
- Start Page Script
- Status Block Time Out
- Testing
- Thread Delay
- Timeout Warning Script
- Trace PPM Agent
- User Directory
- User ID Cookie Age
- User Profile Page
- Use Secure Cookie with SSL
- Version
- View File Title
- Warning Time Out
- Web Password
- Web Profile
- Web Profile Name
- Web User ID
- XML Link Use HTTP for Same Server

2.85.2 Web Server Information Parameters

- Application Directory
- Cell Node Server
- Configuration Path
- Domain
- GUID
- Host Name
- Site
- State
- Type

2.86 Presence Application

The configuration categories and their associated configuration items for the Presence Application target type follow.

2.86.1 General

Maximum allowable lead time for activity start time

2.87 PushMail Application

The configuration categories and their associated configuration items for the PushMail Application target type follow.

2.87.1 General

- Days Message Available
- Heartbeat Interval
- IMAP Connection Live Time
- Max Concurrent Users

Max Inbox Messages
Max Message Size

2.88 Primavera

The configuration categories and their associated configuration items for the Primavera target type follow.

2.88.1 APPLICATION_GENERAL

AllowAutoSummarizeOption
BuildId
CompressAppletComm
CompressHtml
EnableXSSFilter
IgnoreDST

2.88.2 APP_LIMITS

ExcelImportMaxFileSize
ExcelImportMaxTrans
MaxActionCodeValues
MaxActsPerActView
MaxAppletMemory
MaxMRUListItems
MaxPortletsPerDashboard
MaxProjectActivityCodes
MaxProjectsInPortfolio
MaxProjsPerPortfView
MaxRPSpreadsheetProjs

2.88.3 AUTHENTICATION

AuthMode
ContextPathOverride
ServerAndPortOverride
UserNameHeaderKey

2.88.4 CONNPOOL

DbId
DBName
ConnectionPool_Type
PMR_FetchSize
PMR_LeaseRequestWaitTimeout
PMR_MaintenanceFrequency
PMR_MaxConnections
PMR_MaxLeaseDuration
PMR_RenewableFreeLimit
PMR_RenewableLeases
PMR_ResizeRate
PMR_TraceSQL

2.88.5 DATA_LIMITS

dbId
DBName
MaxActCodesPerProject
MAXactivityCodeTreeLevels
MaxActivityIDLength
MaxBaselinesPerProject
MaxCostAcctTreeLevels
MaxCostAccountIDLength
MAXEPSTreeLevels
MaxOBSTreeLevels
MAXProjectCodeTreeLevels
MaxProjectIDLength
MAXResourceCodeTreeLevels
MaxResourceIDLength
MaxResourceTreeLevels
MaxRoleIDLength
MaxRoleTreeLevels
MaxRSRCTreeLevels
MaxTSResourceHourFlag
MaxTimesheetResourceHours
MaxWBSCodeLength
MaxWBSTreeLevels

2.88.6 DBSESSION

DbId
DBName
SessionSettings_Setting1
SessionSettings_Setting2
SessionSettings_Setting3
SessionSettings_Setting4
SessionSettings_Setting5

2.88.7 DB_CONNECTION

DbId
DBName
Description
PublicGroupId
URL

2.88.8 DOC_REPOSITORY

DbId
DBName
EnableConnectionPooling
MaxConnections
URL

2.88.9 EARNEDVALUEPREFS

dbId
DBName
EVCalculation

EvComputeType
EvEtcComputeType
EvEtcUserValue
EvUserPct

2.88.10 EMAIL_NOTIFICATIONS

InitiationNotifications
InvitationNotifications
IssueNotifications
NotifFromEmailOverride

2.88.11 GROUP_SERVER

DbId
DBName
GroupServer_Port
GroupServer_Protocol
GroupServer_Server
GroupServer_URL

2.88.12 JAVA_OS

java_class_path
java_library_path
java_vm_name
java_vm_version
os_arch
os_name
os_version

2.88.13 JAVA_PLUGIN

JavaPluginURL_FF
JavaPluginURL_IE
JavaPluginVersionID_FF
JavaPluginVersionID_IE
JnlpJreVersion

2.88.14 LOGSETTINGS

Asynchronous
ConsoleLoggerEnabled
ConsoleLoggerSevLvl
EmailLoggerEnabled
EmailLoggerSubject
FileLoggerArchiveNum
FileLoggerEnabled
FileLoggerHTML
FileLoggerLogFileSize
FileLoggerSeverityLevel

2.88.15 PERFMON

PerfMonEnabled

PerfMonMonitorHost
PerfMonMonitorPort
PerfMonUpdateInterval

2.88.16 PREFS_OTHER

BaselineUseAtCompletionValue
BLUseBudgetValWithPlanDate
CompletedActTimeWindow
CurrencyId
DatabaseVersion
dbId
DBName
EnablePasswordPolicy
ExpeditionRootUrl
IncExpensesInEVFlag
NonlaborIsMaterial
PreferencesFromSettingsTable
ProjArchEnabledFlag
SummarizeByCalendar
SummByFinancialPeriods
TasksrcSumPeriodType
TaskSumPeriodTyp

2.88.17 SERVICES

SvcAsynchJobsGraceTime
SvcAsynchJobsPurgeInterval
SvcCollabSyncSvcSynItvl
SvcConfigMgmtColEbl
SvcConfigMgmtCollTime
SvcLicenseSvcExpCheckRate
SvcLicenseSvcUpdateRate
SvcMailSvcMaxQueueLength
SvcMailSvcSendInterval
SvcMailSvcSmtpport
SvcNextKeySvcMaxCacheKys
SvcNextKeyServiceRefRate
SvcPerfMaxSummNodeCnt
SvcPerfUseEntpSumm
SvcPrdPerfConcThreads
SvcPrdPerfEnabled
SvcPrdPerfExecutionItvl
SvcProjHchyCacheLmt
SvProjHchyCachePolicy
SvcProjHchyCacheMaintFreq
SvcRegSvePort
SvcRgeSveRefreshRate
SvcRegSveStalePeriod
SSAThisPrdCoreThreads
SSAThisPrdEnabled
SSAThisPrdExecIntvl
SvcTimestampSvcRefreshRate
SvcWebSchedActSchedMode
SvcWebSchedASAPCleanupRate

SvcWebSchedConcSched
SvcWebSchedEnabaled
SvcWebSchedSchedulingIntvl

2.88.18 THREADPOOL

MaintFreq
MaxTaskDuration
LRMaxTaskDurationLR
NumThreads

2.88.19 TIMESHEET_CONNECTION

TimesheetCodebase
TimesheetURL

2.88.20 TIMESHEET_OPTS

dbId
DBName
LogCompletedActFlag
LogFutureTSFlag
LogHrsAfter ActFinishFlag
LogHrsBeforeActStartFlag
LogNotStartedActFlag
DefaultTSApprovalMgr
Level2TSApprovalOrder
EnableTSAudit
TSHourDigits
TimesheetDailyFlag
TSApprovalLevels
ResourceUseTSFlag
RsrcSelfAddFlag
NotStartedActTimeWindow
PastTimesheetPeriods
AllowUserTimePeriodFlag

2.88.21 TRACER

TracerEnabled
TracerServerName
TracerSocketPort

2.88.22 USERSECURITY

DbId
DBName
AllowMultiSessionUser
LogLoginAttempts
LoginLockoutCount
LoginLockoutDuration

2.88.23 WORKFLOW_REPOSITORY

DbId

DBName
 WRep_ConnectionTestPeriod
 WRep_EnableConnectionPooling
 WRep_MaxConnections
 WRep_Timeout

2.88.24 WORKTIME_DATE

dbId
 DBName
 ActivityDefaultDuration
 WeekStartDay
 HoursPerDay
 HoursPerMonth
 HoursPerWeek
 HoursPerYear

2.89 RAC Database

The configuration categories and their associated configuration items for the RAC Database target type follow.

2.89.1 ASM Disk

This metric captures ASM Disks details which has status other than MEMBER.

Name	Description	Data Type	Sample Value
Instance ID	Instance ID	NUMBER	1
Group Number	Group Number	NUMBER	1
Disk Number	Disk Number	NUMBER	1
Header Status	Header Status	VARCHAR2	UNKNOWN
Path	Path	VARCHAR2	ORCL:VOL3

2.89.2 Database Components

Namespace
 Component ID
 Component Name
 Version
 Status
 Schema

2.89.3 Database Scheduler Jobs

This metric captures GATHER_STATS_JOB details from DBA_SCHEDULER_JOBS.

Name	Description	Data Type	Sample Value
Owner	Owner of the object	VARCHAR2	SYS
Job Name	Job Name	VARCHAR2	GATHER_STATS_JOB
State	State	VARCHAR2	SCHEDULED

Name	Description	Data Type	Sample Value
Schedule Name	Scheduler Name	VARCHAR2	MAINTENANCE_WINDOW_GROUP

2.89.4 DB Invalid Objects

This metric captures owner-wise count of the invalid objects for the database.

Name	Description	Data Type	Sample Value
Owner	Owner of the object	VARCHAR2	SYSMAN
Invalid Objects Count	Count of invalid objects	NUMBER	2

2.89.5 MGMT_DB_CPU_USAGE_ECM

DBID
Version
Time at which the CPU usage changed
CPU count of the database
CPU core count of the database
CPU socket count of the database

2.89.6 MGMT_DB_USERS_ECM

User Name
User ID
Default Tablespace
Default Temporary Tablespace
Created
Profile
Expiry date

2.89.7 Redologs

Group Num
Status
Members
File Name
Archived
Log Size
Sequence Num
First Change SCN
OS Storage
Thread Num
Type

2.89.8 Voting Disk

This metric captures all the clusterware voting disk locations for RAC Database.

Name	Description	Data Type	Sample Value
Voting Disk Location	Voting Disk Location on RAC Database	VARCHAR2	/oradbshare/storage/vdisk

2.90 Real-Time Collaboration

The configuration categories and their associated configuration items for the Real-Time Collaboration target type follow.

2.90.1 Real-Time Collaboration Command-Line Control Configuration

Property Name
Property Value

2.91 Search Application

The configuration categories and their associated configuration items for the Search Application target type follow.

2.91.1 General

Cached Page Max Length
Case Sensitive
Crawl Calendars Enabled
Crawl Emails Enabled
Exclude Regex
Max Results
Max Search Duration
Recovery
Sync Frequency
Two DB Mode
Wildcard Char

2.92 Siebel Component

The configuration categories and their associated configuration items for the Siebel Component target type follow.

2.92.1 Siebel Component Configuration

This metric captures details for the Siebel Component Configuration in parameter pairs of Property Name and Property Value. Not all Siebel components contain the same set of parameters so the actual output may vary from one component to another. For example, an Application Object Manager (AOM) component may have different parameters than a Transaction Router component. This generic pairing of Property Name and Property Value allows for any parameter to be captured for all Siebel components.

Following is an example of parameter pairs for the SCCObjMgr_enu component:

Property Name	Property Value
datasource	ServerDataSrc
host	sdchpi01
maxtasks	500
maxmtservers	10
SIEBEL_ENTERPRISE	sia80

Property Name	Property Value
SIEBEL_COMPNAME	SCCObjMgr_enu

2.93 Siebel Component Group

The configuration categories and their associated configuration items for the Siebel Component Group target type follow.

2.93.1 Siebel Component Group Configuration

This metric captures details for the Siebel Component Group Configuration in parameter pairs of Property Name and Property Value. This is similar in nature to the Siebel Component Configuration, however the Component Groups will have the same Property Names for all groups (though the Property Values may be different). A Component Group Configuration is not the same as a Siebel component definition, although some of the same parameter names may appear.

Following is an example of parameter pairs for the Call Center component group:

Property Name	Property Value
SIEBEL_COMPGROUP	CallCenter
SIEBEL_ENTERPRISE	sia80
SIEBEL_GATEWAY	sdcp520a001

2.94 Siebel Enterprise

The configuration categories and their associated configuration items for the Siebel Enterprise target type follow.

2.94.1 Siebel Enterprise Configuration

This metric captures details for the Siebel Enterprise Configuration in parameter pairs of Property Name and Property Value. The Property Names are parameters that are appropriate for or affect the entire Siebel Enterprise. This would include Siebel Enterprise parameters as well as Siebel Named Subsystems. Named Subsystem Property Names are in the format of:

SubSys_<datasrc><parameter>

where

<datasrc> is the Siebel data source name, and

<parameter> is the parameter name in that Siebel data source

Following is an example of parameter pairs for a Siebel Enterprise:

Property Name	Property Value
filesystem	vol1/sia80ora/siebsrvr/fs
secadptmode	DB
secadptname	DBSecAdpt
SIEBEL_GATEWAY	sdchpi01
SubSys_DBSecAdptdatasourcename	ServerDataSrc
SubSys_GatewayDataSrcdsconnectstring	sdchpi01:3220

Property Name	Property Value
SubSys_ServerDataSrcdsmaxcursorsize	-1
tableowner	usia05

2.95 Siebel Gateway

The configuration categories and their associated configuration items for the Siebel Gateway target type follow.

2.95.1 Siebel Gateway Configuration

This metric captures details for the Siebel Gateway Configuration in parameter pairs of Property Name and Property Value. The Property Names are parameters that are appropriate for or affect the Siebel Gateway.

Following is an example of parameter pairs for a Siebel Gateway:

Property Name	Property Value
host	sdchpi01
SIEBEL_GATEWAY	sdchpi01

2.96 Siebel Server

The configuration categories and their associated configuration items for the Siebel Server target type follow.

2.96.1 Siebel Server System Configuration

This metric captures details for the Siebel Server System Configuration in parameter pairs of Property Name and Property Value. The Property Names gathered for this section contains the Siebel server parameter names while the Property Values are those specific to the settings for this Siebel server.

Following is an example of parameter pairs for a Siebel Server System Configuration:

Property Name	Property Value
host	sdchpi01
logdir	/vol1/sia80ora/siebsrvr/enterprises/sia80/srvr1/log
rootdir	/vol1/sia80ora/siebsrvr
SIEBEL_ENTERPRISE	sia80
SIEBEL_SERVER	srvr1

2.96.2 Siebel Server General Configuration

This metric captures details for the Siebel Server General Configuration in parameter pairs of Property Name and Property Value. The Property Names gathered for this section are not necessarily Siebel server parameter settings, but could contain applicable details for the Siebel server which might be found in other files on the server (such as base.txt). These Property Names would be associated with their corresponding Property Values.

Following is an example of parameter pairs for a Siebel Server General Configuration:

Property Name	Property Value
Base File Contents	8.0.0.2 SIA [20412] LANG_INDEPENDENT
Enabled Languages	enu;fra;

2.97 TimeManagement Application

The configuration categories and their associated configuration items for the TimeManagement Application target type follow.

2.97.1 General

Enable Dynamic Participants
Enable Presence Integration
Enable External Participant Notification Delivery
Enable Generic Class Of BusinessEvents

2.98 UserDirectory Application

The configuration categories and their associated configuration items for the UserDirectory Application target type follow.

2.98.1 Attribute

Name
Type
Subtype

2.98.2 Configuration Parameters

Max Entity Address Count
SuperMax Entity Address Count

2.98.3 Custom Attributes

Name
Description

2.99 VoiceMessage Application Configuration

The configuration categories and their associated configuration items for the VoiceMessage Application Configuration target type follow.

2.99.1 General

VoiceMessage Property

2.99.2 Facility Properties

Facility CollabId

2.100 Web Cache

The configuration categories and their associated configuration items for the Web Cache target type follow.

2.100.1 Cluster Information

Cluster Name

2.100.2 Cluster Members

Host Name
Oracle Home
Capacity

2.100.3 Configuration Files

Display Name
Name
Size (Bytes)
Modification Time

2.100.4 File Permission Check

Column	Description
File Path	File Path
File Mode	UNIX file permissions
User ID	UNIX file owner
Group ID	UNIX file group

2.100.5 Identity Check

Column	Description	Collected From
User ID	UNIX user that Web Cache runs as	USERID attribute of the IDENTITY tag in webcache.xml
Group ID	UNIX group that Web Cache runs as	GROUPID attribute of the IDENTITY tag in webcache.xml

2.100.6 Listening Ports

IP Address
Port
Protocol

2.100.7 Log Growth Check

Column	Description	Collected From
Log Name	Event log rollover frequency	FREQUENCY attribute of the ROLLOVER tag (child of the EVENTLOG tag) in webcache.xml

Column	Description	Collected From
Value	Access log rollover frequency	ROLLOVERNAME attribute of the ACCESSLOG tag in webcache.xml

2.100.8 Log Level Check

Column	Description	Collected From
Verbosity	Event log verbosity	LEVEL attribute of the VERBOSITY tag in webcache.xml
IO Logger	Whether the IO logger is enabled	ENABLED attribute of the IOLOGGER tag in webcache.xml

2.100.9 Operations Ports

Type
IP Address
Port
Protocol

2.100.10 Origin Servers

Name
Port
Protocol
Capacity

2.100.11 Performance Related

Cache Memory Limit (MB)
Maximum Incoming Connections
Keep Alive Timeout (seconds)
Origin Server Timeout (minutes)

2.100.12 Site Aliases

Site Name
Site Port
Site URL
Alias Name
Alias Port
Alias URL

2.100.13 Host Mappings

Site Name
Site Port
Site URL
Origin Server Name
Origin Server Port

2.101 WebDAV Application

The configuration categories and their associated configuration items for the WebDAV Application target type follow.

2.101.1 General

- Authentication Scheme
- Browser Session Timeout
- DAVClient Session Timeout
- DepthLimit
- Display Last ModifiedBy
- Display Last ModifiedOn
- Display Lock Status
- Display Versioning Status
- DMS Instrumentation
- Download BufferSize
- MinimumLock Timeout
- Upload BufferSize
- User Preference Refresh Time
- WebDAV Server Enabled

2.101.2 Default Welcome Docs

- Default Welcome Docs

2.102 Workspaces Application

The configuration categories and their associated configuration items for the Workspaces Application target type follow.

2.102.1 General

- Db Download BufferSize
- Db Upload BufferSize

2.103 XMPP Application

The configuration categories and their associated configuration items for the XMPP Application target type follow.

2.103.1 General

- Language
- XMPP Port
- XMPP SSL Port
- XMPP Timer KeepAliveTime

2.103.2 Domain Names

- Domain Names

2.103.3 Search Fields

- Search Fields

2.103.4 Supported Agents

Supported Agents

