



BEA WebLogic Platform

Release Notes

Version 10.2
Document Revised: March 28, 2008

Contents

BEA WebLogic Platform Release Notes

- New and Changed Features2
- Installing WebLogic Platform2
- Upgrading Domains and Applications3
- Supported Configurations3
- Switching JDKs3
- Customer Support5

Known Limitations in WebLogic Platform

BEA WebLogic Platform Release Notes

WebLogic Platform 10.2 includes the following products:

- WebLogic Server 10.0 Maintenance Pack 1
- WebLogic Portal 10.2
- WebLogic Integration 10.2
- Workshop for WebLogic 10.2

This document provides the following information:

- [New and Changed Features](#)
- [Installing WebLogic Platform](#)
- [Upgrading Domains and Applications](#)
- [Supported Configurations](#)
- [Supported databases and database drivers: See Supported Database Configurations.](#)
- [Switching JDKs](#)
- [Customer Support](#)

For information about limitations in WebLogic Platform 10.2, see [“Known Limitations in WebLogic Platform”](#) on page 7.

New and Changed Features

The following table provides links to information about new and changed features, as well as known limitations in the products that are part of WebLogic Platform 10.2.

For Information About	See ...
WebLogic Server 10.0	<ul style="list-style-type: none"> What's new: http://e-docs.bea.com/wls/docs100/notes/index.html Known limitations: http://e-docs.bea.com/wls/docs100/issues/index.html
Workshop for WebLogic 10.2	<ul style="list-style-type: none"> What's new: http://e-docs.bea.com/wlw/docs102/guide/introduction/conWhatsNew.html Known limitations: http://e-docs.bea.com/wlw/docs102/relnotes/index.html
WebLogic Portal 10.2	http://e-docs.bea.com/wlp/docs102/relnotes/index.html
WebLogic Integration 10.2	http://e-docs.bea.com/wli/docs102/relnotes/
BEA JRockit J2SE 5.0 JDK	http://e-docs.bea.com/jrockit/releases/R27/relnotes/index.html

Installing WebLogic Platform


You can install the software by using graphical mode, console mode, or silent mode. For more information, see the [BEA Products Installation Guide](#).

You can install WebLogic Platform in the following ways:

- **Distributed installation:** You can install WebLogic Platform in separate systems such that the number of WebLogic Portal (WLP) and WebLogic Integration (WLI) CPUs installed in all the systems equals the number of WebLogic Platform products that you have bought.

For example, if you have bought two WebLogic Platform products – that is, two CPUs each of WLI and WLP, you can run two CPUs of WLI in one system and two CPUs of


WLP in the other system, and then run WebLogic Server (WLS) in both the systems as separate instances (see the following figure).



Note that, in this case, you cannot install two CPUs of WLS on a third system.

- **Integrated installation:** You can install WLI and WLP in a single system.

For example, if you have bought one WebLogic Platform product, you can run one CPU each of WLI and WLP in a single system, as shown in the following figure.



Upgrading Domains and Applications

For information about upgrading WebLogic Platform domains, see the [Domain Upgrade Guide](#).

For information about upgrading applications created in WebLogic Integration (WLI), WebLogic Portal (WLP), and Workshop, see the [WLI Upgrade Guide](#), [WLP Upgrade Guide](#), and [Workshop Upgrade Guide](#), respectively.

Supported Configurations

- Supported operating systems: See List of Supported Operating System Configurations in [Supported Configurations for BEA WebLogic Platform 10.2](#).
- Supported databases and database drivers: See [Supported Database Configurations](#).

Switching JDKs

The following instructions are provided for users who have already installed either WebLogic Portal 10.2, Workshop for WebLogic 10.2, or WebLogic Server 10.0 and want to switch from Sun Java 2 to BEA JRockit, or vice-versa:

1. Examine the WebLogic Server start script. This script is located in the `bin` subdirectory of your domain's root directory and, by default, is named `startWebLogic.cmd` (Windows) or `startWebLogic.sh` (UNIX).

2. Locate the settings for the following two variables:

- JAVA_VENDOR
- JAVA_HOME

3. If these variables are set within the script, change them as appropriate.

The following `set JAVA_VENDOR` and `set JAVA_HOME` commands specify the BEA JRockit J2SE 5.0 JDK, where `c:\bea` is the BEA home directory:

```
set JAVA_VENDOR=BEA
set JAVA_HOME=c:\bea\jrockit_150_11
```

For Sun, the equivalent commands are as follows:

```
set JAVA_VENDOR=Sun
set JAVA_HOME=c:\bea\jdk150_11
```

4. If the `JAVA_VENDOR` variable is not set in the WebLogic Server start script, then you need to set the default JDK in the `setDomainEnv.cmd` (Windows) or `setDomainEnv.sh` (UNIX) script as described in this step. The `setDomainEnv` script is also located in the `bin` subdirectory of the domain's root directory.

The following two code snippets show the switching of the default JDK from Sun Java 2 JDK 5.0 to BEA JRockit J2SE 5.0 (R27.0) JDK in `commEnv.cmd` on Windows. In these snippets, the BEA home directory is `c:\bea`.

The first code snippet shows the initial settings that establish Sun Java 2 JDK 5.0 as the default:

```
if "%JAVA_VENDOR%"=="BEA" (
    set JAVA_HOME=C:\bea\jrockit_150_11
) else (
    if "%JAVA_VENDOR%"=="Sun" (
        set JAVA_HOME=C:\bea\jdk150_11
    ) else (
        set JAVA_VENDOR=Sun
        set JAVA_HOME=C:\bea\jdk150_11 )
)
```

The second code snippet shows the changes, **in bold**, made to switch to JRockit as the default:

```
if "%JAVA_VENDOR%"=="BEA" (
    set JAVA_HOME=C:\bea\jrockit_150_11
) else (
    if "%JAVA_VENDOR%"=="Sun" (
        set JAVA_HOME=C:\bea\jdk150_11
    ) else (
```

```
set JAVA_VENDOR=BEA  
set JAVA_HOME=C:\bea\jrockit_150_11
```

For more information about BEA support for BEA JRockit and the Sun Java 2 JDK, see [Supported Configurations for WebLogic Server, WebLogic Portal, and Workshop for WebLogic Platform - Version 10.2](#).

Customer Support

If you have any questions about this version of WebLogic Platform 10.2, or if you have problems installing and running the product, contact BEA Customer Support through BEA eSupport at:

<http://support.bea.com>

You can also contact Customer Support by using the contact information provided on the BEA Customer Support card, which is included in the product package.

When contacting Customer Support, be prepared to provide the following information:

- Your name, e-mail address, phone number, and fax number
- Your company name and company address
- Your machine type and authorization codes
- The name and version of the product you are using
- A description of the problem and the content of pertinent error messages

Known Limitations in WebLogic Platform

This section lists the limitations that have been identified in the WebLogic Platform 10.2. Wherever possible, workarounds are provided.

For each problem described, a tracking number is specified. These numbers enable BEA and users to monitor the status of issues while solutions are being developed.

For information about limitations of BEA Smart Update, see [Known Limitations in Smart Update](#).

Problem ID	Description
CR365516	<p>Exception <code>com.bea.plateng.patch.PatchInstallationException</code> is thrown when you apply or remove patch using Smart Update or during an incremental installation to a <code>BEA_HOME</code> with Node Manager already running</p> <p>When Node Manager is running, the process locks the file <code>weblogic_patch.jar</code>. As a result, patch cannot be installed or removed successfully because it fails to update <code>weblogic_patch.jar</code>.</p> <p>Operating System: Windows</p> <p>Workaround: Shut down Node Manager when you perform incremental installation or invoke Smart Update from the same <code>BEA_HOME</code>.</p>

Problem ID	Description
CR364584	<p>Silent installer fails when installing Platform in an existing BEA_HOME containing WLS 10.0MP1, which was installed using WLS 10.0 MP1 installer</p> <p>Operating System: All</p> <p>Workaround: Install WebLogic Platform 10.2 by using one of the following methods:</p> <ul style="list-style-type: none">• Use the GUI mode of installation• Use the WebLogic Platform10.2 installer to install WLS 10.0 MP1; avoid using the WLS 10.0 MP1 installer.
CR361299	<p>Deployment of WebLogic Portal applications fails in a WebLogic Platform 10.2 domain that is upgraded from WebLogic Platform 8.1 SP5 domain</p> <p>Operating System: All</p> <p>Workaround: On the 8.1 domain, open the <code>domain-info.xml</code> file from the <code>_cfgwiz_donotdelete</code> directory. Search for the following text:</p> <pre>name='WebLogic Portal Extension'</pre> <p>Remove the extra space between the words Portal and Extension and then proceed with the domain upgrade.</p>
CR359464	<p>You cannot rollback WebLogic Server 10.0 MP1 to the previous version using Platform uninstaller</p> <p>All products in WebLogic Platform 10.2 are based on WLS 10.0 MP1 (10.0.1). The WebLogic Platform uninstaller allows you to rollback WLS 10.0.1 to 10.0.0 when WLP 10.2, WLI 10.2, and WLW 10.2 are installed. However, you must not rollback WLS to 10.0.0 because it is not a valid product combination.</p> <p>Operating System: All</p> <p>Workaround: Uninstall WLP 10.2, WLI 10.2, and WLW 10.2 and then rollback WLS to 10.0.0.</p>

Problem ID	Description
CR359409 CR361499	<p data-bbox="315 354 1184 383">com.bea.plateng.domain.ValidateException when extending ALSB cluster domain with WLI</p> <p data-bbox="315 397 1228 510">When you create either a WLI or an ALSB domain, the <code>wls_webservice.jar</code> template is applied to the products. When extending the WLI domain with ALSB or ALSB domain with WLI, the Configuration Wizard applies the <code>wls_webservice.jar</code> template again, resulting in <code>com.bea.plateng.domain.ValidateException</code>.</p> <p data-bbox="315 526 545 552">Operating System: All</p> <p data-bbox="315 565 1228 618">Workaround: You can either use the Configuration Wizard or use a WLST script to extend the domain.</p> <p data-bbox="315 624 579 651">Using Configuration Wizard</p> <ol data-bbox="315 666 1228 968" style="list-style-type: none"> <li data-bbox="315 666 666 692">1. Create an ALSB cluster domain. <li data-bbox="315 704 1150 730">2. Launch Configuration Wizard to extend the ALSB cluster domain using templates. For more information about extending a domain using templates, see Extending an Existing Domain. <li data-bbox="315 808 1076 861">3. In the Select Extension Source screen of Configuration Wizard, browse to <code>BEA_HOME\wli_10.2\common\templates\</code> and select <code>p13n.jar</code>. <li data-bbox="315 874 928 900">4. Close the Configuration Wizard after extending the domain. <li data-bbox="315 913 1197 965">5. Repeat steps 2 to 4 for <code>wli_worklist.jar</code> and <code>wli_jpd.jar</code> templates (in step 3, choose <code>wli_worklist.jar</code> and <code>wli_jpd.jar</code> respectively). <p data-bbox="315 991 1228 1130">Note: Every time you extend the domain with a new template, you must finish the domain extension process. Domain extension does not work if you click Previous after extending a domain with one template and without closing the Configuration Wizard. You must use the templates <code>p13n.jar</code>, <code>wli_worklist.jar</code>, and <code>wli_jpd.jar</code> in the same order.</p> <p data-bbox="315 1137 427 1163">Using WLST</p> <p data-bbox="315 1180 1228 1319">Extending the domain using WLST is easier than using the Configuration Wizard. Use the script <code>ExtendDom.py</code>, which is attached to CR359409. To support the <code>loadDB</code> operation and properties, three more scripts are attached to the CR—<code>dataSourceSetupOracle.py</code>, <code>dataSourceSetup.py</code>, and <code>propertyUtil.py</code>. Copy these scripts to the WLST path. Follow these steps:</p> <ol data-bbox="315 1336 1002 1506" style="list-style-type: none"> <li data-bbox="315 1336 942 1362">1. Edit <code>ExtendDom.py</code> as per your environment (lines 12-22). <li data-bbox="315 1374 1002 1400">2. Copy the other three scripts to the same folder as <code>ExtendDom.py</code>. <li data-bbox="315 1413 995 1439">3. Launch WLST (<code>\$WLSERVER_HOME/common/bin/WLST.cmd</code>). <li data-bbox="315 1451 814 1477">4. Run <code>execfile('\$PATH/ExtendDom.py')</code> <li data-bbox="315 1489 438 1515">5. <code>exit()</code>

Problem ID	Description
CR359317	<p>java.util.zip.ZipException when you install Weblogic Integration 10.2 in a directory other than BEA_HOME</p> <p>When you install WebLogic Platform, you can specify a non-default product Home for WebLogic Integration. However, WebLogic Integration does not work in this case.</p> <p>Operating System: All</p> <p>Workaround: Install WebLogic Server and WebLogic Integration together in the same <i>BEA_HOME</i>. The WebLogic Server directory must be <i>BEA_HOME/wlserver_10.0</i> and WebLogic Integration directory must be <i>BEA_HOME/wli_10.2</i>.</p>
CR359092	<p>FileNotFoundException when using the Previous button in the Configuration Wizard</p> <p>After creating a domain by using the Configuration Wizard, you cannot use the Previous button to go back to the Welcome screen of the wizard.</p> <p>Operating System: All</p> <p>Workaround: To create another domain, exit the Configuration Wizard and restart the wizard.</p>
CR358861	<p>*.jks files are not included when unpacking a WebLogic Portal domain template</p> <p>When you unpack a WebLogic Portal domain template, which was created by using the <code>pack</code> command or the Domain Template Builder, and unpack the template into a managed server domain, the managed server fails because *.jks files are missing.</p> <p>Operating System: All</p> <p>Workaround: Copy the *.jks files from the original domain to the new domain.</p>
CR358553	<p>WebLogic Portal domain created on Windows cannot be transferred to Solaris</p> <p>While creating portal domain template, pack (or Domain Template Builder) refers four different libraries to the same directory causing conflicting libraries references in the config.xml inside the resulting template.</p> <p>Operating System: Windows, Solaris</p> <p>Workaround: Use Domain Template Builder to create the portal domain template. In the "Add" or "Omit" Application screen, try to customize the path to differentiate the paths to those different libraries:</p> <pre>content-management-app-lib#10.2.0@10.2.0 content-management-web-lib#10.2.0@10.2.0 webdav-app-lib#10.2.0@10.2.0 webdav-web-lib#10.2.0@10.2.0.0</pre>

Problem ID	Description
CR358496	<p data-bbox="315 395 1229 453">Installation fails when the <i>BEA_HOME</i> path name is long</p> <p data-bbox="315 395 1229 453">The patch installation fails (<code>java.lang.IllegalArgumentException</code>) during the patch install process when the <i>BEA_HOME</i> path name is long.</p> <p data-bbox="315 470 1229 583">The patch system uses the <code>java.Preferences</code> class to determine the default location for the patch cache directory. It uses the absolute path for <i>BEA_HOME</i> as the basis for a node name to retrieve this data. This class has a limitation of 80 characters for node names, and therefore throws an exception when the path name is long, causing the patch installation to fail.</p> <p data-bbox="315 600 579 626">Operating System: Solaris</p> <p data-bbox="315 638 1229 661">Workaround: The absolute path for the <i>BEA_HOME</i> directory must not exceed 70 characters.</p>
CR286040	<p data-bbox="315 690 1229 748">Using WLST to run a script that uses <code>loadProperties</code> fails when a property name in the file contains improper characters.</p> <p data-bbox="315 765 1229 822">An error message is displayed when you use <code>loadProperties</code> to load a property that contains a . (period) character in the property name.</p> <p data-bbox="315 840 545 866">Operating System: All</p> <p data-bbox="315 878 1229 930">Workaround: In the <code>loadProperties</code> file, specify the property name without using the . (period) character. For example, use <code>sbm</code> instead of <code>sbm.db.default</code> as property name.</p>

Problem ID	Description
CR280837	<p>On Solaris, when multiple users run Domain Provisioning tools like the Configuration Wizard, Domain Stop Server Script or WLST Off-Line Scripting, it is possible that subsequent users of the tool might encounter error messages like:</p> <pre>*sys-package-mgr*: can't write cache file for '/home/wimbleton/load12/jdk150_04/lib/tools.jar' *sys-package-mgr*: can't write cache file for '/home/wimbleton/load12/weblogic91/server/lib/weblogic.jar' *sys-package-mgr*: can't write cache file for '/home/wimbleton/load12/weblogic91/server/lib/webservices.jar' *sys-package-mgr*: can't write cache file for '/home/wimbleton/load12/jdk150_04/jre/lib/rt.jar' *sys-package-mgr*: can't write cache file for '/home/wimbleton/load12/jdk150_04/jre/lib/jsse.jar'</pre> <p>This message appears because WLST creates a temporary directory (for example, on Solaris it is /var/tmp/wlstTemp) that gets shared by all users and it is unable to differentiate between users. As a result, access to the directory gets blocked when the user accessing the directory is not the one who originally created the directory.</p> <p>Workaround: Manually adjust directory permissions.</p>
CR271218	<p>Unknown Publisher Security Alert</p> <p>On the Windows platform, an Unknown Publisher security alert may be encountered when launching a downloaded 9.2 installer, even though BEA's digital signature is present and correctly registered.</p> <p>This is a known Microsoft Windows problem with very large digitally-signed files. BEA has already filed a support case with Microsoft, Case # SRX060608602617. Contact BEA Customer Support for more information.</p> <p>Operating System: Windows</p>

Problem ID	Description
-------------------	--------------------

CR234871	Installer hangs on Windows XP during Node Manager configuration
-----------------	--

If you choose to install Node Manager as a Windows service, which is an option available via a custom installation, the installation program may hang after you specify a listen port for Node Manager.

This problem may occur if Windows Firewall is running, and the listen port chosen for Node Manager has not been specified as a Windows Firewall exception.

Operating System: Windows XP Professional with Service Pack 2

Workaround: Before you run the installation program, do either of the following:

- Turn off Windows Firewall (recommended)
- Add the port you want to use for the Node Manager listen port as a Windows Firewall exception

If you choose to turn off Windows Firewall prior to installation, you can turn it back on after the installation procedure is complete.

Problem ID	Description
CR230483	<p data-bbox="252 348 1180 383">Configuration of application-scoped resources cannot be changed in domain template</p> <p data-bbox="252 395 1180 539">If you create a template or extension template of a domain that contains application-scoped resources, and then create or extend a clustered domain on the basis of that template or extension, the Configuration Wizard may not properly retarget the application-scoped resources. If the template on which a clustered domain is based contains application-scoped JMS or JDBC resources, the domain may fail to start.</p> <p data-bbox="252 552 481 586">Operating System: All</p> <p data-bbox="252 591 1072 626">Workaround: Note the following best practices for creating domains and templates:</p> <ul data-bbox="252 631 1180 1083" style="list-style-type: none"> <li data-bbox="252 631 1180 748">• When creating a domain or extension template, include only JMS and JDBC resources that are global to the domain and that can be customized during the domain creation process; for example, JDBC data source and JMS file store settings for the domain, or cluster configuration settings. <li data-bbox="252 753 1180 817">• Rely on the application and on the application deployment process to create the required application-scoped resources in the target environment. <li data-bbox="252 822 1180 1083">• If you are migrating an application from a non-clustered to a clustered domain, and the application includes packaged JMS resources for which you want to have scalability and load balancing, you can do the following: <ul data-bbox="292 921 1180 1083" style="list-style-type: none"> <li data-bbox="292 921 1180 986">— In place of each JMS queue in the packaged JMS module, create a uniform distributed JMS queue. <li data-bbox="292 991 938 1020">— Configure a JMS server for each Managed Server in the cluster. <li data-bbox="292 1025 1180 1083">— Include the connection factory and the uniform distributed queues in the same sub deployment group, and deploy them to the cluster. <p data-bbox="292 1095 1180 1211">When the application is deployed, each Managed Server in the cluster has a connection factory and a member for each distributed queue. For information about configuring JMS for a clustered environment, see “Configuring Clustered WebLogic JMS Resources” in <i>Configuring and Managing WebLogic JMS</i>.</p> <ul data-bbox="252 1216 1180 1367" style="list-style-type: none"> <li data-bbox="252 1216 1180 1367">• After you create or extend the domain, you may need to perform additional steps to make sure that the application and its application-scoped resources are targeted and deployed properly for a clustered environment. For more information on the targeting and deployment of application-scoped modules, see “Deploying Applications and Modules” in <i>Deploying Applications to WebLogic Server</i>.

Problem ID	Description
CR229700	<p data-bbox="315 397 1228 510">QuickStart is not displayed correctly after installation</p> <p data-bbox="315 401 1228 510">When installing AquaLogic Service Bus or WebLogic Server, if you specify a directory for either the BEA Home directory or WebLogic Server Home directory that contains a multibyte character set in the directory name, QuickStart is not displayed correctly after the installation is complete.</p> <p data-bbox="315 527 1032 553">Operating System: Any system in which the Sun Java 2 J2SE 5.0 is used.</p> <p data-bbox="315 567 1201 621">Workaround: During installation, choose directories for BEA Home and WebLogic Server Home with names that include only the ASCII character set.</p>
CR229655	<p data-bbox="315 649 1194 703">Exception java.lang.UnsupportedOperationException thrown from domain configured using WLST offline</p> <p data-bbox="315 725 1228 838">When operating in offline mode, WLST does not support the creation of security roles. If a WLST offline script includes statements that define security roles, WLST terminates abnormally when executing the script, throwing the <code>java.lang.UnsupportedOperationException</code> exception.</p> <p data-bbox="315 855 545 881">Operating System: All</p> <p data-bbox="315 895 962 921">Workaround: Use WLST in online mode to specify security roles.</p>
CR227881	<p data-bbox="315 949 973 975">Limited support in Template Builder for compatibility-mode security</p> <p data-bbox="315 991 1228 1072">When using the Domain Template Builder to create a template from a domain that contains a Compatibility security configuration, you cannot create or assign additional users, groups, and global roles.</p> <p data-bbox="315 1090 545 1116">Operating System: All</p> <p data-bbox="315 1130 1201 1211">Workaround: After you create a domain based on a template that contains a Compatibility security configuration, boot the domain and add users, groups, and roles via the WebLogic Server Administration Console.</p>

Problem ID	Description
CR224337	<p data-bbox="252 354 1163 413">Server fails to start when domain name includes a dot and the dot is preceded and followed by strings of a certain length</p> <p data-bbox="252 430 1163 482">If you create a domain and assign a name that has all the following characteristics, the domain will not start:</p> <ul data-bbox="252 499 1163 597" style="list-style-type: none"><li data-bbox="252 499 1163 522">• The name includes the period character (.).<li data-bbox="252 534 1163 557">• Two alphanumeric characters precede the period.<li data-bbox="252 569 1163 591">• Five or more alphanumeric characters follow the dot. <p data-bbox="252 614 1163 637">For example, a domain created with the name <code>zq.domain</code> will not start.</p> <p data-bbox="252 654 1163 677">Operating System: All</p> <p data-bbox="252 694 1163 716">Workaround: When choosing a domain name, do one of the following:</p> <ul data-bbox="252 734 1163 817" style="list-style-type: none"><li data-bbox="252 734 1163 756">• Do not use a name that contains a dot character.<li data-bbox="252 769 1163 817">• If you use a dot character, make sure that you provide more than two characters preceding the dot.
CR224184	<p data-bbox="252 852 1163 939">PointBase is not disabled after a domain is extended using two or more extension templates, and an extension template other than the first is used to change the database from PointBase to a production RDBMS</p> <p data-bbox="252 956 1163 1039">If you extend a domain using two or more extension templates, and switch the database from PointBase to a production RDBMS when applying the second template or a subsequent one, PointBase is not disabled for the domain.</p> <p data-bbox="252 1057 1163 1079">Operating System: All</p> <p data-bbox="252 1097 1163 1119">Workaround: Two workarounds can be used to avoid this problem, as follows:</p> <ul data-bbox="252 1137 1163 1255" style="list-style-type: none"><li data-bbox="252 1137 1163 1189">• When extending the domain using the first extension template, specify the production RDBMS. This step ensures that subsequent extension templates do not re-enable PointBase.<li data-bbox="252 1201 1163 1255">• When starting the domain, run the WebLogic Server start script specifying the <code>nopointbase</code> option. For example: <p data-bbox="290 1272 1163 1295">UNIX:</p> <pre data-bbox="290 1307 1163 1329">startWebLogic.sh nopointbase</pre> <p data-bbox="290 1347 1163 1369">Windows:</p> <pre data-bbox="290 1381 1163 1404">startWebLogic nopointbase</pre>

Problem ID	Description
CR220653	<p data-bbox="315 354 1189 413">WebLogic Server fails to start and displays the message that the server is not found in the WL_HOME directory</p> <p data-bbox="315 430 1224 574">A message similar to the following is displayed when you try to start WebLogic Server: The WebLogic Server wasn't found in directory <i>directory-name</i>. Please edit the <code>setWLSEnv.cmd</code> script so that the <code>WL_HOME</code> variable points to the WebLogic installation directory. Your environment has not been set.</p> <p data-bbox="315 591 1224 651">This problem is caused by a Windows bug that limits the length of the directory name you can use for the BEA Home directory.</p> <p data-bbox="315 668 545 690">Operating System: All</p> <p data-bbox="315 708 1150 755">Workaround: Do not choose a BEA Home directory name that contains more than 12 characters.</p>
CR214849	<p data-bbox="315 782 857 808">Thread dump occurs when Ctrl+C is used to stop server</p> <p data-bbox="315 826 1231 911">Using Ctrl+C to stop a WebLogic Server instance results in a thread dump in the command window from which the server was started. This problem occurs because the RDBMS configured for the domain halts before the WebLogic Server shutdown procedure is completed.</p> <p data-bbox="315 928 1217 1038">This problem can happen in either the WebLogic Server Examples domain or Avitek Medical Records domain when configured with the default PointBase RDBMS, but potentially can happen in any domain in which the RDBMS is configured to start and stop with WebLogic Server.</p> <p data-bbox="315 1055 606 1078">Operating System: Windows</p> <p data-bbox="315 1095 1217 1180">Workaround: The recommended way to shut down a WebLogic Server instance is via the WebLogic Server Administration Console. For details, see “Starting and Stopping Servers” in <i>Managing Server Startup and Shutdown</i>.</p>

Known Limitations in WebLogic Platform