



THE ENTERPRISE MIDDLEWARE SOLUTION

# BEA TUXEDO

# System Messages

## MAC Catalog

BEA TUXEDO Release 6.5  
Document Edition 6.5  
February 1999

# Copyright

Copyright © 1999 BEA Systems, Inc. All Rights Reserved.

## Restricted Rights Legend

This software and documentation is subject to and made available only pursuant to the terms of the BEA Systems License Agreement and may be used or copied only in accordance with the terms of that agreement. It is against the law to copy the software except as specifically allowed in the agreement. This document may not, in whole or in part, be copied photocopied, reproduced, translated, or reduced to any electronic medium or machine readable form without prior consent, in writing, from BEA Systems, Inc.

Use, duplication or disclosure by the U.S. Government is subject to restrictions set forth in the BEA Systems License Agreement and in subparagraph (c)(1) of the Commercial Computer Software-Restricted Rights Clause at FAR 52.227-19; subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.227-7013, subparagraph (d) of the Commercial Computer Software--Licensing clause at NASA FAR supplement 16-52.227-86; or their equivalent.

Information in this document is subject to change without notice and does not represent a commitment on the part of BEA Systems. THE SOFTWARE AND DOCUMENTATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND INCLUDING WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. FURTHER, BEA Systems DOES NOT WARRANT, GUARANTEE, OR MAKE ANY REPRESENTATIONS REGARDING THE USE, OR THE RESULTS OF THE USE, OF THE SOFTWARE OR WRITTEN MATERIAL IN TERMS OF CORRECTNESS, ACCURACY, RELIABILITY, OR OTHERWISE.

## Trademarks or Service Marks

BEA, ObjectBroker, TOP END, TUXEDO, and WebLogic are registered trademarks of BEA Systems, Inc. BEA Builder, BEA Connect, BEA Manager, BEA MessageQ, Jolt and M3 are trademarks of BEA Systems, Inc.

All other company names may be trademarks of the respective companies with which they are associated.

### BEA TUXEDO System Messages MAC Catalog

Document Edition	Date	Software Version
6.5	February 1999	BEA TUXEDO Release 6.5

---

# Content

1. **MAC Messages 1000-1099**
2. **MAC Messages 1100-1199**



# 1 MAC Messages

## 1000-1099

<b>1000</b>	<b>ERROR: USAGE: Set name value</b>
<b>Description</b>	You can set environment variables with TuxShell using the Set command. The syntax for the Set command is “Set <i>name value</i> ”, which will set the environment variable <i>name</i> to the value <i>value</i> .
<b>Action</b>	Ensure that the Set command in the script run by the TuxShell has the proper format.
<b>1001</b>	<b>ERROR: Could not allocate memory for environment</b>
<b>Description</b>	While creating an environment context, the system ran out of memory.
<b>Action</b>	Check the memory on the system where the TuxShell was running. Increase the amount of memory which is allotted to TuxShell using the finder.
<b>1002</b>	<b>ERROR: tuxputenv returns an error. String not added to environment</b>
<b>Description</b>	tuxputenv(3c) returned an error while TuxShell was setting an environment variable.
<b>Action</b>	Check the memory on the system where the TuxShell was running. Increase the amount of memory which is allotted to TuxShell using the finder.

<b>1003    ERROR: Environment is full</b>	
<b>Description</b>	The TuxShell process can only keep track of 255 environment variables.
<b>Action</b>	Use fewer environment variables in your TuxShell script.
<b>1004    ERROR: tuxputenv returns an error. String not added to environment</b>	
<b>Description</b>	tuxputenv(3c) returned an error while TuxShell was setting an environment variable.
<b>Action</b>	Check the memory on the system where the TuxShell was running. Increase the amount of memory which is allotted to TuxShell using the finder.
<b>1005    ERROR: USAGE: Unset name</b>	
<b>Description</b>	You can unset environment variables with TuxShell using the Unset command. The syntax for the Unset command is "Unset <i>name</i> ", which will unset the environment variable <i>name</i> .
<b>Action</b>	Ensure that the Unset command in the script run by the TuxShell has the proper format.
<b>1007    ERROR: Memory Full Error returned by AEProcessAppleEvent</b>	
<b>Description</b>	A high level event has been received by the process. The Macintosh High Level Event API AEProcessAppleEvent has been called, in order to properly parse the event. A <i>memFullErr</i> event code was returned by AEProcessAppleEvent.
<b>Action</b>	Check the memory on the system where the process was running. Increase the amount of memory which is allotted to the process using the finder.
<b>1008    ERROR: Buffer is too small returned by AEProcessAppleEvent</b>	
<b>Description</b>	A high level event has been received by the process. The Macintosh High Level Event API AEProcessAppleEvent has been called, in order to properly parse the event. A <i>bufferIsSmall</i> event code was returned by AEProcessAppleEvent.
<b>Action</b>	The high level event returned by the system is improper. Contact your BEA TUXEDO system Technical Support.

---

<b>1009</b>	<b>ERROR: Corrupt Data returned by AEProcessAppleEvent</b>
<b>Description</b>	A high level event has been received by the process. The Macintosh High Level Event API AEProcessAppleEvent has been called, in order to properly parse the event. A <i>errAECorruptData</i> event code was returned by AEProcessAppleEvent.
<b>Action</b>	The high level event returned by the system is improper. Contact your BEA TUXEDO system Technical Support.

---

<b>1010</b>	<b>ERROR: Newer Version returned by AEProcessAppleEvent</b>
<b>Description</b>	A high level event has been received by the process. The Macintosh High Level Event API AEProcessAppleEvent has been called, in order to properly parse the event. A <i>errAENewerVersion</i> event code was returned by AEProcessAppleEvent.
<b>Action</b>	The high level event returned by the system is improper. Contact your BEA TUXEDO system Technical Support.

---

<b>1011</b>	<b>ERROR: The directory {TUXDIR}lib is not present</b>
<b>Description</b>	<code>viewc(1)</code> and <code>viewc32</code> need to be able to find the {TUXDIR}lib directory on Macintosh, in order to find the Symantec Project <code>VIEWC_DNR.prj</code> .
<b>Action</b>	Make sure that TUXDIR is set using the Set command. Make sure that the {TUXDIR}lib directory exists as has the proper permissions. Make sure that the project <code>VIEWC_DNR.prj</code> can be located in the {TUXDIR}lib directory.

---

<b>1012</b>	<b>ERROR: Error creating FSSpec record</b>
<b>Description</b>	An error occurred while creating an internal structure to represent the {TUXDIR}lib directory.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.

---

<b>1013</b>	<b>ERROR: Error creating alias record</b>
<b>Description</b>	An error occurred while creating an internal structure to represent the {TUXDIR}lib directory.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.

---

<b>1014</b>	<b>ERROR: Error creating descriptor list</b>
<b>Description</b>	An error occurred while creating an internal structure to represent the {TUXDIR}lib directory.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1015</b>	<b>ERROR: The file VIEWC_DNR was removed</b>
<b>Description</b>	viewc(1) and viewc32 need to be able to find the {TUXDIR}lib directory on Macintosh, in order to find the Symantec Project VIEWC_DNR.prj.
<b>Action</b>	Make sure that TUXDIR is set using the Set command. Make sure that the {TUXDIR}lib directory exists as has the proper permissions. Make sure that the project VIEWC_DNR.prj can be located in the {TUXDIR}lib directory.
<b>1016</b>	<b>ERROR: Error creating FSSpec record</b>
<b>Description</b>	An error occurred while creating an internal structure to represent the {TUXDIR}lib:VIEWC_DNR.prj file.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1017</b>	<b>ERROR: Error creating alias record</b>
<b>Description</b>	An error occurred while creating an internal structure to represent the {TUXDIR}lib:VIEWC_DNR.prj file.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1018</b>	<b>ERROR: Error adding Alias record to list</b>
<b>Description</b>	An error occurred while updating an internal structure to represent the {TUXDIR}lib:VIEWC_DNR.prj file, inside the {TUXDIR}lib directory.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1019</b>	<b>ERROR: Error Creating Finder Address</b>
<b>Description</b>	An error occurred while creating an internal structure to represent the finder.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.



---

<b>1020</b>	<b>ERROR: Error Creating High Level Event for Compiler</b>
<b>Description</b>	An error occurred while creating a high level event for the Symantec compiler.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1021</b>	<b>ERROR: Error adding option to Apple Event</b>
<b>Description</b>	An error occurred while updating a high level event for the Symantec compiler.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1022</b>	<b>ERROR: Error adding Alias List to Apple Event</b>
<b>Description</b>	An error occurred while updating a high level event for the Symantec compiler.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1023</b>	<b>ERROR: TimeoutError Waiting for reply AppleEvent</b>
<b>Description</b>	An error occurred while sending a high level event to the Symantec compiler.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1024</b>	<b>ERROR: Error Creating Target Compiler Address</b>
<b>Description</b>	An error occurred while creating a high level event for the MPW compiler.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1025</b>	<b>ERROR: Error getting the current working directory</b>
<b>Description</b>	While attempting to find the current working directory of the process, an error occurred.
<b>Action</b>	Make sure that the directory in which the process is working still exists.

---

<b>1026</b>	<b>ERROR: Error Creating High Level Event for Compiler</b>
<b>Description</b>	An error occurred while creating a high level event for the MPW compiler.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1027</b>	<b>ERROR: Error adding buildclient command to Apple Event</b>
<b>Description</b>	viewc and viewc32 work by sending a buildclient command to ToolServer. An error occurred while updating a high level event with the buildclient command.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1028</b>	<b>ERROR: TimeoutError Waiting for reply AppleEvent</b>
<b>Description</b>	viewc and viewc32 work by sending a buildclient command to ToolServer. The MPW compiler may have taken too long to complete the compilation process.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1029</b>	<b>ERROR: An error occurred getting the MPW Error Code</b>
<b>Description</b>	viewc and viewc32 work by sending a buildclient command to ToolServer. An error occurred while attempting to retrieve the status of the compilation.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1030</b>	<b>WARN: An error has occurred compiling the file. Usually a struct &gt; 32K</b>
<b>Description</b>	viewc and viewc32 work by sending a buildclient command to ToolServer. The view compilation has failed.
<b>Action</b>	The usual cause of this error is a view structure which is greater than 32K. The MPW compiler cannot handle a structure this large, and hence this compilation will fail. Decrease the number of elements in the view, or the number of occurrences of elements in the view.

---

<b>1031</b>	<b>ERROR: Error creating Launch record for internal application</b>
<b>Description</b>	In the second phase of <code>viewc</code> and <code>viewc32</code> , an application which was generated in the first phase must be run. An error occurred while generating a launch record for this application.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1032</b>	<b>ERROR: Error launching internal application</b>
<b>Description</b>	In the second phase of <code>viewc</code> and <code>viewc32</code> , an application which was generated in the first phase must be run. An error occurred while launching this application.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1033</b>	<b>ERROR: Error waiting for launched application</b>
<b>Description</b>	In the second phase of <code>viewc</code> and <code>viewc32</code> , an application which was generated in the first phase must be run. An error occurred while waiting for this application to finish execution.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1034</b>	<b>ERROR: TUXDIR is not set</b>
<b>Description</b>	While attempting to initialize the Symantec THINK C compiler, it was found that TUXDIR was not set.
<b>Action</b>	Use the Set command in your <code>TuxShell</code> script to set the appropriate value for TUXDIR.
<b>1035</b>	<b>ERROR: Utility not handled</b>
<b>Description</b>	An unknown utility was requested in <code>TuxShell</code> .
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1036</b>	<b>ERROR: Error Creating THINK Address</b>
<b>Description</b>	While attempting to create the address of the Symantec THINK C compiler, an error occurred.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.

---

<b>1037</b>	<b>ERROR: Error Creating High Level Event for THINK Compiler</b>
<b>Description</b>	While attempting to create a high level event for the Symantec THINK C compiler, an error occurred.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1038</b>	<b>ERROR: TimeoutError Waiting for reply AppleEvent</b>
<b>Description</b>	While waiting for a high level event from the Symantec THINK C compiler, an error occurred.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1039</b>	<b>ERROR: An error occurred making compiler noninteractive</b>
<b>Description</b>	An error occurred while attempting to make the Symantec THINK C compiler noninteractive.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1040</b>	<b>ERROR: viewc created file not found</b>
<b>Description</b>	viewc or viewc32 creates a file to be compiled in its first phase. While the Symantec THINK C Compiler was being used, TuxShell could not find the file generated by viewc or viewc32.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1041</b>	<b>ERROR: Error creating FSSpec record</b>
<b>Description</b>	viewc or viewc32 creates a file to be compiled in its first phase. While the Symantec THINK C Compiler was being used, TuxShell could create an FSSpec record for this file.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1042</b>	<b>ERROR: Error Creating High Level Event for THINK Compiler</b>
<b>Description</b>	An error occurred while creating a high level event for the THINK compiler.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.

---

<b>1043</b>	<b>ERROR: Error adding file name to Apple Event</b>
<b>Description</b>	viewc or viewc32 creates a file to be compiled in its first phase. While the Symantec THINK C Compiler was being used, TuxShell could not add the file name to a high level apple event for the compiler.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.

---

<b>1044</b>	<b>ERROR: Error adding signature to Apple Event</b>
<b>Description</b>	viewc or viewc32 creates a file to be compiled in its first phase. While the Symantec THINK C Compiler was being used, TuxShell could not add the application signature to a high level apple event for the compiler.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.

---

<b>1045</b>	<b>ERROR: TimeoutError Waiting for reply AppleEvent</b>
<b>Description</b>	viewc or viewc32 creates a file to be compiled in its first phase. While the Symantec THINK C Compiler was being used, a timeout error occurred while waiting for the compiler to compile the file.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.

---

<b>1046</b>	<b>ERROR: An error occurred adding generated file to project</b>
<b>Description</b>	viewc or viewc32 creates a file to be compiled in its first phase. An error occurred while attempting to add the file to the VIEWC_DNR.prj project.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.

---

<b>1047</b>	<b>ERROR: An error occurred getting obj specifier of file</b>
<b>Description</b>	viewc or viewc32 creates a file to be compiled in its first phase. An error occurred while attempting to retrieve information about the file which has been added to the VIEWC_DNR.prj project.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.

---

<b>1048</b>	<b>ERROR: Error Creating High Level Event for THINK Compiler</b>
<b>Description</b>	viewc or viewc32 creates a file to be run in its second phase. An error occurred while attempting to create an apple event to tell the Symantec THINK C compiler to run the project.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1049</b>	<b>ERROR: Error adding update options to Apple Event</b>
<b>Description</b>	viewc or viewc32 creates a file to be run in its second phase. An error occurred while attempting to create an update an apple event to tell the Symantec THINK C compiler to run the project.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1050</b>	<b>ERROR: Error adding save options to Apple Event</b>
<b>Description</b>	viewc or viewc32 creates a file to be run in its second phase. An error occurred while attempting to create an update an apple event to tell the Symantec THINK C compiler to run the project.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1051</b>	<b>ERROR: TimeoutError Waiting for reply AppleEvent</b>
<b>Description</b>	viewc or viewc32 creates a file to be run in its second phase. An error occurred while waiting for the VIEWC_DNR.prj project to run to completion.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1052</b>	<b>ERROR: Error running internal application</b>
<b>Description</b>	viewc or viewc32 creates a file to be run in its second phase. The application did not run successfully.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1053</b>	<b>ERROR: Error Creating High Level Event for THINK Compiler</b>
<b>Description</b>	viewc or viewc32 creates a file to be run in its second phase. We are attempting to clean the VIEWC_DNR.prj project by removing the file generated in the first phase. However, an error occurred while generating a high level apple event for this purpose.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.

---

<b>1054 ERROR: Error adding file name to Apple Event</b>	
<b>Description</b>	viewc or viewc32 creates a file to be run in its second phase. We are attempting to clean the VIEWC_DNR.prj project by removing the file generated in the first phase. An error occurred while adding the file name to a high level apple event.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1055 ERROR: TimeoutError Waiting for reply AppleEvent</b>	
<b>Description</b>	viewc or viewc32 creates a file to be run in its second phase. We are attempting to clean the VIEWC_DNR.prj project by removing the file generated in the first phase. A timeout error occurred while waiting for the Symantec THINK C Compiler to remove the file.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1056 ERROR: An error occurred removing generated file from project</b>	
<b>Description</b>	viewc or viewc32 creates a file to be run in its second phase. We are attempting to clean the VIEWC_DNR.prj project by removing the file generated in the first phase. An error occurred while removing the file.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1057 WARN: The utility returned an error</b>	
<b>Description</b>	All the utilities which TuxShell runs return an error code. One of the utilities run by TuxShell returned an error. This occurs when wud or wud32 is being used.
<b>Action</b>	Consult the documentation on the utility which returned an error.
<b>1058 ERROR: Could not get utility menu Handle</b>	
<b>Description</b>	An error occurred reading the resource fork of the TuxShell.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1059 ERROR: An error occurred quitting project</b>	
<b>Description</b>	The Symantec THINK C Compiler returned an error to TuxShell while quitting the VIEWC_DNR.prj project.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.

---

<b>1060    ERROR: Error Creating THINK Address</b>	
<b>Description</b>	While attempting to generate an address for the Symantec THINK C Compiler, an error occurred.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1061    ERROR: CC is not set</b>	
<b>Description</b>	When using <code>viewc</code> or <code>viewc32</code> through <code>TuxShell</code> , the environment variable <code>CC</code> must be set.
<b>Action</b>	Set <code>CC</code> depending on the compiler which is being used. If you are using the MPW compiler, set <code>CC</code> to <code>applec</code> . If you are using the Symantec THINK C compiler, set <code>CC</code> to <code>THINK_C</code> . If you are using the MetroWerks CodeWarrior compiler, set <code>CC</code> to <code>mwerks</code> .
<b>1062    ERROR: Compiler <i>compiler</i> is not supported</b>	
<b>Description</b>	The compiler <i>compiler</i> given via the <code>CC</code> environment variable is not supported.
<b>Action</b>	Set <code>CC</code> depending on the compiler which is being used. If you are using the MPW compiler, set <code>CC</code> to <code>applec</code> . If you are using the Symantec THINK C compiler, set <code>CC</code> to <code>THINK_C</code> . If you are using the MetroWerks CodeWarrior compiler, set <code>CC</code> to <code>mwerks</code> .
<b>1063    ERROR: Error Creating High Level Event for THINK Compiler</b>	
<b>Description</b>	<code>viewc</code> or <code>viewc32</code> must run the Symantec THINK C compiler. An error occurred while creating a High Level Event.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1064    ERROR: TimeoutError Waiting for reply AppleEvent</b>	
<b>Description</b>	<code>viewc</code> or <code>viewc32</code> must run the Symantec THINK C compiler. A timeout error occurred while configuring the Symantec THINK C Compiler.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.



---

<b>1065</b>	<b>ERROR: Error Creating THINK Address</b>
<b>Description</b>	While attempting to generate an address for the Symantec THINK C Compiler, an error occurred.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1066</b>	<b>ERROR: THINK C compile call returns an error</b>
<b>Description</b>	The Symantec THINK C compiler failed.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1067</b>	<b>ERROR: MPW compile call returns an error</b>
<b>Description</b>	The MPW compiler failed.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1068</b>	<b>ERROR: Compiler not supported: <i>compiler</i></b>
<b>Description</b>	<i>compiler</i> is not supported.
<b>Action</b>	Set CC depending on the compiler which is being used. If you are using the MPW compiler, set CC to applec. If you are using the Symantec THINK C compiler, set CC to THINK_C. If you are using the MetroWerks CodeWarrior compiler, set CC to mwerks.
<b>1069</b>	<b>WARN: Utility not found: <i>utility</i></b>
<b>Description</b>	TuxShell does not run utility.
<b>Action</b>	Make sure your TuxShell script invokes only those utilities which are available to it. Utilities which are supported by TuxShell are gencat, mklanginfo, mkfldhdr, viewc, viewdis, viewc32, viewdis32, mkfldhdr32, set, and unset.
<b>1070</b>	<b>WARN: Quoting Error. Skipping line</b>
<b>Description</b>	All double quoted elements must have a terminating double quote in TuxShell scripts.
<b>Action</b>	If you are using double quotes, make sure they are properly matched in your TuxShell script.

---

<b>1071</b>	<b>WARN: Too many parameters. Skipping line</b>
<b>Description</b>	TuxShell can handle a maximum of 31 arguments per command.
<b>Action</b>	Use fewer arguments.
<b>1072</b>	<b>WARN: Could not start compiler. Skipping line</b>
<b>Description</b>	TuxShell attempted to start a compiler for viewc or viewc32 but was not successful. TuxShell will skip the line.
<b>Action</b>	Analyze the cause of the compiler failure. If you are using Symantec THINK C, be sure that the VIEWC_DNR.prj is located in TUXDIR:lib:. Be sure that if you double click on VIEWC_DNR.prj, that the compiler launches properly. Be sure that the Symantec THINK C Compiler is not already active.
<b>1073</b>	<b>WARN: An Error occurred in utility: <i>utility</i></b>
<b>Description</b>	All the utilities which TuxShell runs return an error code. One of the utilities run by TuxShell returned an error.
<b>Action</b>	Consult the documentation on the utility which returned an error.
<b>1074</b>	<b>ERROR: A fatal error has occurred. Aborting TuxShell</b>
<b>Description</b>	Some fatal error has occurred during the TuxShell processing.
<b>Action</b>	Restart TuxShell and try again.
<b>1075</b>	<b>ERROR: Could not get apple menu Handle</b>
<b>Description</b>	An error occurred reading the resource fork of the TuxShell.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1076</b>	<b>ERROR: Could not get file menu Handle</b>
<b>Description</b>	An error occurred reading the resource fork of the TuxShell.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.

---

<b>1077</b>	<b>ERROR: Memory Full Error returned by AEProcessAppleEvent</b>
<b>Description</b>	While the TuxShell was processing a high level apple event, a memFullErr occurred.
<b>Action</b>	Check the memory on the system where the TuxShell was running. Increase the amount of memory which is allotted to TuxShell using the finder.

---

<b>1078</b>	<b>ERROR: Buffer is too small returned by AEProcessAppleEvent</b>
<b>Description</b>	While the TuxShell was processing a high level apple event, a bufferIsSmall error occurred.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.

---

<b>1079</b>	<b>ERROR: Corrupt Data returned by AEProcessAppleEvent</b>
<b>Description</b>	While the TuxShell was processing a high level apple event, a errAECorruptData error occurred.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.

---

<b>1080</b>	<b>ERROR: Newer Version returned by AEProcessAppleEvent</b>
<b>Description</b>	While the TuxShell was processing a high level apple event, a errAENewerVersion error occurred.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.

---

<b>1081</b>	<b>ERROR: Unable to open TuxShell.stdout</b>
<b>Description</b>	TuxShell attempt to write all output destined for stdout into a file called TuxShell.stdout. However, TuxShell could not open the file in the working directory.
<b>Action</b>	Make sure that the working directory of the TuxShell exists and that it is writable.

---

<b>1082</b>	<b>ERROR: Unable to open TuxShell.stderr</b>
<b>Description</b>	TuxShell attempt to write all output destined for stderr into a file called TuxShell.stderr. However, TuxShell could not open the file in the working directory.
<b>Action</b>	Make sure that the working directory of the TuxShell exists and that it is writable.

---

<b>1083    ERROR: Error opening script file</b>	
<b>Description</b>	TuxShell attempted to open a script for execution. However, TuxShell could not open the file.
<b>Action</b>	Make sure that the directory in which the script resides is writable by the user of TuxShell.
<b>1084    ERROR: Error retrieving directory name</b>	
<b>Description</b>	TuxShell attempted to open a script for execution. However, TuxShell could not retrieve the name of the directory in which the file exists.
<b>Action</b>	Make sure that the directory in which the script resides is writable by the user of TuxShell.
<b>1085    ERROR: Error initializing status dialog</b>	
<b>Description</b>	An error occurred reading the resource fork of the TuxShell.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1086    ERROR: Error updating status dialog</b>	
<b>Description</b>	An error occurred reading the resource fork of the TuxShell.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1087    INFO: User killed script</b>	
<b>Description</b>	The user of TuxShell cancelled the script while in progress.
<b>Action</b>	Do not hit the CANCEL button.
<b>1088    ERROR: Unknown Error: <i>number</i> returned by RunScript</b>	
<b>Description</b>	An internal routine of TuxShell returned unknown error code <i>number</i> .
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.

---

<b>1089</b>	<b>ERROR: Memory is low. Aborting TuxShell</b>
<b>Description</b>	The memory low routine of TuxShell was invoked.
<b>Action</b>	Check the memory on the system where the TuxShell was running. Increase the amount of memory which is allotted to TuxShell using the finder.

---

<b>1090</b>	<b>ERROR: Unable to allocate Handle for emergency memory. Aborting TuxShell</b>
<b>Description</b>	The memory low routine of TuxShell was invoked.
<b>Action</b>	Check the memory on the system where the TuxShell was running. Increase the amount of memory which is allotted to TuxShell using the finder. If it seems that there should be enough memory for this operation, contact your BEA TUXEDO system Technical Support.

---

<b>1091</b>	<b>INFO: Could not add <i>variable</i> to environment</b>
<b>Description</b>	The Set command of TuxShell could not add <i>variable</i> to the environment.
<b>Action</b>	Check the memory on the system where the TuxShell was running. Increase the amount of memory which is allotted to TuxShell using the finder. If it seems that there should be enough memory for this operation, contact your BEA TUXEDO system Technical Support.

---

<b>1092</b>	<b>WARN: wud32 returns an error</b>
<b>Description</b>	The wud32 command of TuxShell returned an error.
<b>Action</b>	Check the files TuxShell.stdout and TuxShell.stderr for further information about the cause of failure.

---

<b>1093</b>	<b>WARN: wud returns an error</b>
<b>Description</b>	The wud command of TuxShell returned an error.
<b>Action</b>	Check the files TuxShell.stdout and TuxShell.stderr for further information about the cause of failure.

---

<b>1094</b>	<b>WARN: TuxShell file overflow</b>
<b>Description</b>	An internal error occurred while reading the TuxShell script file.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1095</b>	<b>ERROR: MWERKS_MPW must be set to the MPW component of Code Warrior</b>
<b>Description</b>	If the MetroWerks compiler is used, then the environment variable MWERKS_MPW must be set to point to the directory where the MPW component of the MetroWerks compiler is installed.
<b>Action</b>	If you are using the MetroWerks compiler, be sure to install the MPW portion of the compiler. Set MWERKS_MPW to point to the directory where the MPW utilities are installed. The ToolServer must also know where to find the MPW utilities.
<b>1096</b>	<b>ERROR: Error Creating Target Compiler Address</b>
<b>Description</b>	An error occurred creating the address for the MetroWerks Compiler.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1097</b>	<b>ERROR: TUXDIR is not set</b>
<b>Description</b>	While attempting to initialize the MetroWerks compiler, it was found that TUXDIR was not set.
<b>Action</b>	Use the Set command in your TuxShell script to set the appropriate value for TUXDIR.
<b>1098</b>	<b>ERROR: Error getting the current working directory</b>
<b>Description</b>	While attempting to find the current working directory of the process, an error occurred.
<b>Action</b>	Make sure that the directory in which the process is working still exists.
<b>1099</b>	<b>ERROR: Error Creating High Level Event for Compiler</b>
<b>Description</b>	An error occurred while creating a high level event for the MetroWerks compiler.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.

# 2 MAC Messages

## 1100-1199

<b>1100</b>	<b>ERROR: Error adding buildclient command to Apple Event</b>
<b>Description</b>	viewc and viewc32 work by sending a buildclient command to ToolServer. An error occurred while updating a high level event with the buildclient command.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1101</b>	<b>ERROR: TimeoutError Waiting for reply AppleEvent</b>
<b>Description</b>	An error occurred while sending a high level event to the MetroWerks compiler.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1102</b>	<b>ERROR: An error occurred getting the MPW Error Code</b>
<b>Description</b>	viewc and viewc32 work by sending a buildclient command to ToolServer. An error occurred while attempting to retrieve the status of the compilation. For the MetroWerks compiler, the MPW versions of the compiler are used.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.

<b>1103    WARN: An error has occurred compiling the view file.</b>	
<b>Description</b>	viewc and viewc32 work by sending a buildclient command to ToolServer. An error occurred during the compilation of the file. For the MetroWerks compiler, the MPW versions of the compiler are used.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.
<b>1104    ERROR: Metrowerks compile call returns an error</b>	
<b>Description</b>	viewc and viewc32 work by sending a buildclient command to ToolServer. An error occurred during the compilation of the file. For the MetroWerks compiler, the MPW versions of the compiler are used.
<b>Action</b>	Contact your BEA TUXEDO system Technical Support.