



BEA WebLogic Adapter for FIX[®]

Installation and Configuration Guide

Version 8.1.2
Document Revised: January 2004

Copyright

Copyright © 2004 BEA Systems, Inc. All Rights Reserved.

Portions Copyright © 2004 iWay Software. All Rights Reserved.

Restricted Rights Legend

This software and documentation is subject to and made available only pursuant to the terms of the BEA Systems License Agreement and may be used or copied only in accordance with the terms of that agreement. It is against the law to copy the software except as specifically allowed in the agreement. This document may not, in whole or in part, be copied, photocopied, reproduced, translated, or reduced to any electronic medium or machine readable form without prior consent, in writing, from BEA Systems, Inc.

Use, duplication or disclosure by the U.S. Government is subject to restrictions set forth in the BEA Systems License Agreement and in subparagraph (c)(1) of the Commercial Computer Software-Restricted Rights Clause at FAR 52.227-19; subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.227-7013, subparagraph (d) of the Commercial Computer Software--Licensing clause at NASA FAR supplement 16-52.227-86; or their equivalent.

Information in this document is subject to change without notice and does not represent a commitment on the part of BEA Systems. THE SOFTWARE AND DOCUMENTATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND INCLUDING WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. FURTHER, BEA Systems DOES NOT WARRANT, GUARANTEE, OR MAKE ANY REPRESENTATIONS REGARDING THE USE, OR THE RESULTS OF THE USE, OF THE SOFTWARE OR WRITTEN MATERIAL IN TERMS OF CORRECTNESS, ACCURACY, RELIABILITY, OR OTHERWISE.

Trademarks or Service Marks

BEA, Jolt, Tuxedo, and WebLogic are registered trademarks of BEA Systems, Inc. BEA Builder, BEA Campaign Manager for WebLogic, BEA eLink, BEA Liquid Data for WebLogic, BEA Manager, BEA WebLogic Commerce Server, BEA WebLogic Enterprise, BEA WebLogic Enterprise Platform, BEA WebLogic Express, BEA WebLogic Integration, BEA WebLogic Personalization Server, BEA WebLogic Platform, BEA WebLogic Portal, BEA WebLogic Server, BEA WebLogic Workshop and How Business Becomes E-Business are trademarks of BEA Systems, Inc.

All other trademarks are the property of their respective companies.

Contents

About This Document

| | |
|---|------|
| Who Should Read This Documentation | v |
| What You Need to Know | vi |
| Product Documentation on the dev2dev Web Site | vi |
| Related Information | vi |
| Contact Us! | vii |
| Documentation Conventions | viii |

Installing the BEA WebLogic Adapter for FIX

| | |
|--|---|
| Preparing to Install the Adapter | 2 |
| Review the Release Notes | 2 |
| Obtain a FIX Engine License | 2 |
| Understanding the Representation of Paths | 2 |
| Installing the Adapter | 3 |
| Step 1. Obtain the BEA WebLogic Adapter for FIX | 4 |
| Step 2. Configure the Domain | 4 |
| Step 3. Extract the Adapter Files and Change the WebLogic Script | 4 |
| Extracting Files and Adjusting the Classpath for Windows | 5 |
| Extracting Files and Adjusting the Classpath for UNIX | 5 |
| Step 4. Update the BEA License | 6 |
| Step 5. Place the FIX Engine License in Your Domain Home Directory | 7 |
| Step 6. Deploy the Adapter | 7 |

| | |
|--|----|
| Step 7. Create an Adapter Administrative User | 9 |
| Next Steps | 11 |
| Starting to Integrate Your Application With FIX. | 11 |

Index

About This Document

This document explains how to install and configure the BEA WebLogic Adapter for FIX.

Who Should Read This Documentation

This document is intended for the following members of an integration team:

- **Integration Specialists**—Lead the integration design effort. Integration specialists have expertise in defining the business and technical requirements of integration projects, and in designing integration solutions that implement specific features of WebLogic Integration. The skills of integration specialists include business and technical analysis, architecture design, project management, and WebLogic Integration product knowledge.
- **Technical Analysts**—Provide expertise in an organization's information technology infrastructure, including telecommunications, operating systems, applications, data repositories, future technologies, and IT organizations. The skills of technical analysts include technical analysis, application design, and information systems knowledge.
- **Enterprise Information System (EIS) Specialists**—Provide domain expertise in the systems that are being integrated using WebLogic Integration adapters. The skills of EIS specialists include technical analysis and application integration design.
- **System Administrators**—Provide in-depth technical and operational knowledge about databases and applications deployed in an organization. The skills of system administrators include capacity and load analysis, performance analysis and tuning, deployment topologies, and support planning.

What You Need to Know

This document assumes that you have an understanding of:

- Web technologies
- WebLogic Integration
- FIX software, system, and environment. This includes understanding of FIX tools and configuration as well as processes and data models.
- Your specific FIX business needs and applications

Product Documentation on the dev2dev Web Site

BEA product documentation, along with other information about BEA software, is available from the BEA dev2dev Web site:

<http://dev2dev.bea.com>

To view the documentation for a particular product, select that product from the list on the dev2dev page; the home page for the specified product is displayed. From the menu on the left side of the screen, select Documentation for the appropriate release. The home page for the complete documentation set for the product and release you have selected is displayed.

Related Information

Readers of this document may find the following documentation and resources especially useful:

- *BEA WebLogic Adapter for FIX Release Notes*
<http://edocs.bea.com/wladders/fix/docs812/pdf/relnotes.pdf>
- *BEA WebLogic Adapter for FIX User Guide*
<http://edocs.bea.com/wladders/fix/docs812/pdf/user.pdf>
- *Introduction to the BEA WebLogic Adapters*
<http://edocs.bea.com/wladders/docs81/pdf/intro.pdf>
- BEA WebLogic Adapters Dev2Dev Product Documentation
<http://dev2dev.bea.com/products/wladders/index.jsp>
- Application Integration documentation
<http://edocs.bea.com/wli/docs81/aiover/index.html>

<http://edocs.bea.com/wli/docs81/aiuser/index.html>

- BEA WebLogic Integration documentation

<http://edocs.bea.com/wli/docs81/index.html>

- BEA WebLogic Platform documentation

<http://edocs.bea.com/platform/docs81/index.html>

- FIX documentation

<http://www.fixprotocol.org>

Contact Us!

Your feedback on the BEA WebLogic Adapter for FIX documentation is important to us. Send us e-mail at **docsupport@bea.com** if you have questions or comments. Your comments will be reviewed directly by the BEA professionals who create and update the BEA WebLogic Adapter for FIX documentation.

In your e-mail message, please indicate that you are using the documentation for BEA WebLogic Adapter for FIX and the version of the documentation.

If you have any questions about this version of BEA WebLogic Adapter for FIX, or if you have problems using the BEA WebLogic Adapter for FIX, contact BEA Customer Support through BEA WebSUPPORT at **www.bea.com**. You can also contact Customer Support by using the contact information provided on the Customer Support Card which is included in the product package.

When contacting Customer Support, be prepared to provide the following information:

- Your name, e-mail address, phone number, and fax number
- Your company name and company address
- Your machine type
- The name and version of the product you are using
- A description of the problem and the content of pertinent error messages

Documentation Conventions

The following documentation conventions are used throughout this document.

| Convention | Item |
|--------------------------------|---|
| boldface text | Indicates terms defined in the glossary. |
| Ctrl+Tab | Indicates that you must press two or more keys simultaneously. |
| <i>italics</i> | Indicates emphasis or book titles. |
| monospace text | Indicates code samples, commands and their options, data structures and their members, data types, directories, and file names and their extensions. Monospace text also indicates text that you must enter from the keyboard. <i>Examples:</i> <pre>#include <iostream.h> void main () the pointer psz chmod u+w * \tux\data\ap .doc tux.doc BITMAP float</pre> |
| monospace boldface text | Identifies significant words in code. <i>Example:</i> <pre>void commit ()</pre> |
| <i>monospace italic text</i> | Identifies variables in code. <i>Example:</i> <pre>String <i>expr</i></pre> |
| UPPERCASE TEXT | Indicates device names, environment variables, and logical operators. <i>Examples:</i> <pre>LPT1 SIGNON OR</pre> |
| { } | Indicates a set of choices in a syntax line. The braces themselves should never be typed. |

| Convention | Item |
|------------|--|
| [] | <p>Indicates optional items in a syntax line. The brackets themselves should never be typed.</p> <p><i>Example:</i></p> <pre>buildobjclient [-v] [-o name] [-f file-list]... [-l file-list]...</pre> |
| | <p>Separates mutually exclusive choices in a syntax line. The symbol itself should never be typed.</p> |
| ... | <p>Indicates one of the following in a command line:</p> <ul style="list-style-type: none"> • That an argument can be repeated several times in a command line • That the statement omits additional optional arguments • That you can enter additional parameters, values, or other information <p>The ellipsis itself should never be typed.</p> <p><i>Example:</i></p> <pre>buildobjclient [-v] [-o name] [-f file-list]... [-l file-list]...</pre> |
| . | <p>Indicates the omission of items from a code example or from a syntax line. The vertical ellipsis itself should never be typed.</p> |

Installing the BEA WebLogic Adapter for FIX

This section explains how to install the BEA WebLogic Adapter for FIX with WebLogic Integration on both Windows and UNIX systems.

This section is organized as follows:

- [Preparing to Install the Adapter](#)
- [Installing the Adapter](#)
- [Next Steps](#)

Preparing to Install the Adapter

Before you install the BEA WebLogic Adapter for FIX, be sure to complete the following tasks:

- [Review the Release Notes](#)
- [Obtain a FIX Engine License](#)
- [Understanding the Representation of Paths](#)

Review the Release Notes

The *BEA WebLogic Adapter for FIX Release Notes* contain important information about the software you must install prior to installing the BEA WebLogic Adapter for FIX. Also, check the release notes for information about any required patches for your system. The *BEA WebLogic Adapter for FIX Release Notes* are available at the following URL:

<http://edocs.bea.com/wladapters/fix/docs812/pdf/relnotes.pdf>

Obtain a FIX Engine License

Before you use the adapter, you must obtain a license for the FIX engine. The BEA WebLogic Adapter for FIX includes a FIX engine which requires a separate license. The adapter will not function properly without this license. To obtain this license, contact your BEA representative.

Understanding the Representation of Paths

When you install WebLogic Integration, you specify the locations for files. Some of these files are required by the adapter. This document uses the following conventions to represent the locations of these files.

- *BEA_HOME* represents the BEA Home directory of your WebLogic installation. For example:
 - If you install the product in the default location on a Windows system, *BEA_HOME* represents `c:\bea`.
 - If you install the product in the default location on a UNIX system, *BEA_HOME* represents `/bea`.
- *WLI_HOME* represents the root of your WebLogic Integration installation. For example:
 - If you install WebLogic Integration in the default location on a Windows system, *WLI_HOME* represents `c:\bea\weblogic81\integration`.

- If you install WebLogic Integration in the default location on a UNIX system, *WLI_HOME* represents `/bea/weblogic81/integration`.
- *domain* is used to indicate the name of a domain.

You use the Configuration Wizard to create custom user domains. When you set up the domain configuration with the Configuration Wizard, you must specify a domain name, *domain*. You must also indicate where the directory associated with this domain is created. This directory contains files required for that domain. To learn more about the Configuration Wizard, see *Using the Configuration Wizard* which is available at the following URL:

<http://edocs.bea.com/platform/docs81/configwiz/index.html>

- *DOMAIN_HOME* represents the complete path to the root of a domain.

For example, if you use the Configuration Wizard to create a domain in the default location on a Windows system, *DOMAIN_HOME* represents

`c:\bea\weblogic81\user_projects\domains\domain`.

If you use the Configuration Wizard to create a domain in the default location on a UNIX system, *DOMAIN_HOME* represents `/bea/weblogic81/user_projects/domains/domain`.

Note: *WLI_HOME* and *BEA_HOME* (italicized) also represent the corresponding Windows and UNIX environment variables. For example, the literal interpretation of *WLI_HOME* is `%WLI_HOME%` for Windows and `$WLI_HOME` for UNIX.

Unlike *WLI_HOME* and *BEA_HOME*, *DOMAIN_HOME* is not an environment variable that is set by default in the WebLogic Integration environment.

Installing the Adapter

This section explains how to install the BEA WebLogic Adapter for FIX with WebLogic Integration. It includes the following steps:

- [Step 1. Obtain the BEA WebLogic Adapter for FIX](#)
- [Step 2. Configure the Domain](#)
- [Step 3. Extract the Adapter Files and Change the WebLogic Script](#)
- [Step 4. Update the BEA License](#)
- [Step 5. Place the FIX Engine License in Your Domain Home Directory](#)
- [Step 6. Deploy the Adapter](#)

- [Step 7. Create an Adapter Administrative User](#)

Step 1. Obtain the BEA WebLogic Adapter for FIX

To obtain the EAR file containing the BEA WebLogic Adapter for FIX software (BEA_FIX_8_1.ear), do one of the following:

- Download the file from the following URL:
http://commerce.bea.com/products/weblogicadapters/wl_adapter_home.jsp
- Obtain the software on CD.

Step 2. Configure the Domain

You must deploy the BEA WebLogic Adapter for FIX in a domain that supports application integration functionality. You can create one of your own, or use the sample integration domain. The sample integration domain is:

- On Windows: `BEA_HOME\weblogic81\samples\domains\integration`
- On UNIX: `BEA_HOME/weblogic81/samples/domains/integration`

If you have not already done so, use the Configuration Wizard to create the domain using the Integration domain template.

To learn more about the Configuration Wizard, see the *Configuration Wizard Template Reference* at the following URL:

<http://edocs.bea.com/platform/docs81/confgwiz/index.html>

Step 3. Extract the Adapter Files and Change the WebLogic Script

This section explains how to extract the BEA WebLogic Adapter for FIX files and edit your WebLogic script (`setDomainEnv`) to add jar files to the CLASSPATH, and adjust the PATH.

Set the classpath using the procedure appropriate for your system:

- [Extracting Files and Adjusting the Classpath for Windows](#)
- [Extracting Files and Adjusting the Classpath for UNIX](#)

Extracting Files and Adjusting the Classpath for Windows

To extract the BEA WebLogic Adapter for FIX files and edit the WebLogic script:

1. Use WinZip (or another similar file extraction product) to extract the following files from BEA_FIX_8_1.ear file to a directory of your choice (for example, *D:\fixextract*):

- xercesExt.jar
- xercesImpl.jar
- fixengine-1.3.1.jar

2. Go to the root directory for your domain:

```
cd DOMAIN_HOME
```

Note: You must choose a domain that supports application integration functionality.

3. Open the `setDomainEnv.cmd` file with an ASCII editor.

4. Find the following command in the `setDomainEnv.cmd` file:

```
set CLASSPATH=%ARDIR%\ant\ant.jar;%JAVA_HOME%\jre\lib\rt.jar
```

5. Immediately *after* this command line, insert the following command lines so that the CLASSPATH and PATH point to the files you extracted in Step 1:

```
rem ===== Xerces jar files and fix engine =====
set CLASSPATH=%CLASSPATH%;D:\fixextract\xercesExt.jar
set CLASSPATH=%CLASSPATH%;D:\fixextract\fixengine-1.3.1.jar
set CLASSPATH=%CLASSPATH%;D:\fixextract\xercesImpl.jar
```

Here, *D:\fixextract* is the directory to which you extracted the files from the ear file.

6. Save your changes and close the `setDomainEnv.cmd` file.

Extracting Files and Adjusting the Classpath for UNIX

To extract the BEA WebLogic Adapter for FIX files and edit the WebLogic script:

1. Use jar (or another similar file extraction product) to extract the following files from the BEA_FIX_8_1.ear file to a directory of your choice (for example, */fixextract*).

- xercesExt.jar
- xercesImpl.jar
- fixengine-1.3.1.jar

2. Go to the root directory for your domain:

```
cd DOMAIN_HOME
```

Note: You must choose a WebLogic Integration domain that supports application integration functionality.

3. Find the `setDomainEnv.sh` file.
4. Find the following command in the `setDomainEnv.sh` file:

```
set CLASSPATH="${ARDIR}/ant/ant.jar:${JAVA_HOME}/jre/lib/rt.jar"
```

5. Immediately *after* this command, insert the following command lines so that the `CLASSPATH` and `PATH` point to the files you extracted in Step 1:

```
rem ===== Xerces jar files and fix engine =====  
CLASSPATH=$CLASSPATH:/fixextract/xercesExt.jar  
CLASSPATH=$CLASSPATH:/fixextract/xercesImpl.jar  
CLASSPATH=$CLASSPATH:/fixextract/fixengine-1.3.1.jar
```

Here, `/fixextract` is the directory to which you extracted the files from the ear file.

6. Save your changes and close the `setDomainEnv.sh` file.

Step 4. Update the BEA License

To use the BEA WebLogic Adapter for FIX you must have a valid software license. If you have downloaded the adapter for evaluation, see the instructions on the adapter download page to obtain an evaluation license. If you have purchased a license for the adapter, you should receive the license file as an e-mail attachment. Once you have the license file for the adapter, you must update your `license.bea` file to include the new information for the adapter.

To update your `license.bea` file:

1. Save the adapter license file in the `BEA_HOME` directory. To avoid overwriting your `license.bea` file, use a name other than `license.bea`. For example, save the file as `fix_adapter_license.bea`. The adapter license file is the `license_update_file` referred to in step 4 of this procedure.

Warning: Do not overwrite or change the name of the existing `license.bea` file.

2. Go to the `BEA_HOME` directory:
 - On a Windows system, open an MS-DOS session and go to the `BEA_HOME` directory.

- On a UNIX system, go to the `BEA_HOME` directory.
3. Add the JDK to your `PATH` variable. If it is already included, skip to step 4.
 - On a Windows system:


```
set PATH=BEA_HOME\jdk141_05\bin;%PATH%
```
 - On a UNIX system:


```
PATH=BEA_HOME/jdk141_05/bin:$PATH
export PATH
```
 4. Merge the adapter license file into your existing license:
 - On a Windows system:


```
UpdateLicense license_update_file
```
 - On a UNIX system:


```
sh UpdateLicense.sh license_update_file
```

Here, `license_update_file` is the name of the adapter license file you saved in step 1.
 5. Save a backup copy of your updated `license.bea` file. This backup location should be a safe place that is neither the WebLogic Integration nor the application installation directories.

Step 5. Place the FIX Engine License in Your Domain Home Directory

The BEA WebLogic Adapter for FIX requires a license for the FIX engine that is included with the adapter. To learn more about obtaining a FIX engine license, see [“Obtain a FIX Engine License” on page 2](#). Once you have the license file (`license.bin`), copy it to your `DOMAIN_HOME` directory.

Step 6. Deploy the Adapter

After you have installed the BEA WebLogic Adapter for FIX, you must deploy it to your domain.

To deploy the adapter:

1. Start WebLogic Server in your domain.
2. Start the WebLogic Server Administration Console in a browser using the following URL:

```
http://host:port/console/
```

Where,

- *host* represents the machine on which WebLogic Server is running
- *port* represents the listening port.

For example, `http://localhost:7001/console/`

3. Enter the user name and password for the server.

The WebLogic Server Administration Console appears.



4. In the left pane, expand the Deployments node.
5. Under the Deployments node, right-click Applications and select Deploy a New Application.

This initiates the Deployment Assistant in the right panel.

An application is a J2EE application or Web Service contained in an Enterprise Application Archive (EAR) file or exploded EAR directory. Individual components contained in a J2EE application can be deployed to one or more target servers or clusters.

This Applications page displays key information about the EAR files or exploded EAR directories that have been configured for deployment in this WebLogic Server domain.


[Deploy a new Application](#)

Click to deploy a new application

[Customize this view...](#)

6. Click the Deploy a new Application link.

The Administration Console displays the Deploy an Application window.



7. Click the upload your files(s) link.


The Administration Console displays the Install or Upload an Application window.

Upload and Install an Application or Module

Click the Browse... button below to locate an application or module file on the machine from which you are currently browsing. When you have located the file, click the Upload button to upload and install the application or module on this Administration Server. The following types of files may be uploaded and installed.

- A **.jar** containing EJBs (Enterprise JavaBeans)
- A **.war** (Web Application Archive) containing JSPs and Servlets
- A **.rar** (Resource Adapter Archive) containing a Connector module
- An **.ear** (J2EE Enterprise Application Archive) containing any of the above

Note: If you browse for the file, you may have to adjust the file-type filter to 'All' in order to find .jar, .war, .rar and .ear files.




8. Click **Browse**, navigate to the directory in which the `BEA_FIX_8_1.ear` file resides, and then click **Upload**.

The Administration Console prompts you to confirm the uploaded application.

9. Click the radio button next to the application file and then click **Continue**.

The Administration Console uploads the file and displays the **Deploy an Application** window (specifying the default target server).



10. Click **Deploy**.

The Administration Console deploys the application and displays its deployment status.

Step 7. Create an Adapter Administrative User

If you want to manage security for the BEA WebLogic Adapter for FIX, you can create an administrative user (such as `fixAdapterAdmin`) who is authorized to log in to the Application View Console, create application views, configure services and events, deploy, and test. This adapter administrator also needs to be added to the `Administrators` group.

To learn more about the Application View Console, see Viewing and Changing Application View Details in *Managing WebLogic Application Integration Solutions* at the following URL:
<http://edocs.bea.com/wli/docs81/manage/index.html>

To create a new adapter administrative user:

1. In the left pane of the WebLogic Server Administration Console, click the Security node.
2. In the left pane, click the Realms node.
3. In the left pane, click the name of the realm for which you want to configure security.
4. In the left pane, click Users.

The Users page is displayed.



Users are entities that can be authenticated. A user can be a person or software entity, such as a Java client. Each user is given a unique identity within a security realm. BEA recommends assigning users to groups for two reasons: it makes the WebLogic Security Service perform better, and makes it more efficient for administrators who work with large numbers of users.

This Users page displays key information about each user that has been configured in this security realm.

 [Configure a new User...](#)

Click to configure a new user.

Filter By:

| User | Description | Provider | |
|--------------------------------------|----------------------|----------------------|---|
| weblogic | weblogic | DefaultAuthenticator |  |
| installadministrator | installadministrator | DefaultAuthenticator |  |

5. Under the Deployments node, right-click Applications and select Deploy a New Application. This initiates the Deployment Assistant in the right panel. Click the Configure a New User link.

The Create User page is displayed.

 [Configure a new User...](#)

General | Groups | Details

This page allows you to define a user in this security realm.

Name: MyAdapterAdmin

The login name for this user:

Description:

A short description of this user. For example, the user's full name.

Password: [Change...](#)

Enter a description for this user.

Click to change the password.

6. Click the Groups tab.

The Groups page is displayed.

[Configure a new User...](#)

Select a group for the user.

7. In the Possible Groups list, select Administrators and then click the right arrow to add the Administrators group to the list of current groups.
8. Click Apply.
9. In the left pane, right-click the Users node, select Open and confirm that the user you created appears in the list of users.

Next Steps

After you have finished installing the BEA WebLogic Adapter for FIX, you can proceed to the following tasks:

- [Starting to Integrate Your Application With FIX](#)

Starting to Integrate Your Application With FIX

After you have successfully installed and deployed the BEA WebLogic Adapter for FIX and the BEA Application Explorer, you can begin integrating your application with your FIX system using the adapter and BEA WebLogic Integration. To learn more about integrating with FIX, see the *BEA WebLogic Adapter for FIX User Guide* at the following URL:

<http://edocs.bea.com/wladders/fix/docs812/pdf/user.pdf>

Index

A

adapter software, obtaining 1-4
administrative user, creating 1-9

B

BEA_HOME variable 1-2
before you install 1-2

C

classpath, updating 1-4
customer support contact information vii

D

documentation, where to find it vi
domain name 1-2
domains, configuring 1-4

E

extracting JARs 1-4

I

installing
 before you install 1-2
 configuring the domain 1-4
 creating an adapter administrative user 1-9
 deploying the adapter 1-7
 extracting JARs 1-4
 obtaining the adapter software 1-4
 placing the FIX engine license 1-7

steps, summary of 1-3
updating the BEA license 1-6
updating the classpath 1-4

L

license, updating 1-6

P

paths, representation of 1-2
product support vii

R

related information vi
Release Notes, reviewing 1-2

S

security, configuring 1-9
support vii

T

technical support vii

U

updating the BEA license 1-6

W

WebLogic Server Administration Console 1-7
WLI_HOME variable 1-2

X

xerces files, extracting 1-5