



BEA WebLogic Personal Messaging API™

WebLogic Exchange Service Setup

Copyright

Copyright © 1995-2006 BEA Systems, Inc. All Rights Reserved.

Restricted Rights Legend

This software is protected by copyright, and may be protected by patent laws. No copying or other use of this software is permitted unless you have entered into a license agreement with BEA authorizing such use. This document is protected by copyright and may not be copied photocopied, reproduced, translated, or reduced to any electronic medium or machine readable form, in whole or in part, without prior consent, in writing, from BEA Systems, Inc.

Information in this document is subject to change without notice and does not represent a commitment on the part of BEA Systems. THE DOCUMENTATION IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND INCLUDING WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. FURTHER, BEA SYSTEMS DOES NOT WARRANT, GUARANTEE, OR MAKE ANY REPRESENTATIONS REGARDING THE USE, OR THE RESULTS OF THE USE, OF THE DOCUMENT IN TERMS OF CORRECTNESS, ACCURACY, RELIABILITY, OR OTHERWISE.

Trademarks and Service Marks

Copyright © 1995-2006 BEA Systems, Inc. All Rights Reserved. BEA, BEA JRockit, BEA WebLogic Portal, BEA WebLogic Server, BEA WebLogic Workshop, Built on BEA, Jolt, JoltBeans, SteelThread, Top End, Tuxedo, and WebLogic are registered trademarks of BEA Systems, Inc. BEA AquaLogic, BEA AquaLogic Data Services Platform, BEA AquaLogic Enterprise Security, BEA AquaLogic Service Bus, BEA AquaLogic Service Registry, BEA Builder, BEA Campaign Manager for WebLogic, BEA eLink, BEA Liquid Data for WebLogic, BEA Manager, BEA MessageQ, BEA WebLogic Commerce Server, BEA WebLogic Communications Platform, BEA WebLogic Enterprise, BEA WebLogic Enterprise Platform, BEA WebLogic Enterprise Security, BEA WebLogic Express, BEA WebLogic Integration, BEA WebLogic Java Adapter for Mainframe, BEA WebLogic JDriver, BEA WebLogic Log Central, BEA WebLogic Network Gatekeeper, BEA WebLogic Personalization Server, BEA WebLogic Personal Messaging API, BEA WebLogic Platform, BEA WebLogic Portlets for Groupware Integration, BEA WebLogic Server Process Edition, BEA WebLogic SIP Server, BEA WebLogic WorkGroup Edition, Dev2Dev, Liquid Computing, and Think Liquid are trademarks of BEA Systems, Inc. BEA Mission Critical Support, BEA Mission Critical Support Continuum, and BEA SOA Self Assessment are service marks of BEA Systems, Inc.

All other names and marks are property of their respective owners.

Table of Contents

Installation

- Installing the MAPI Subsystem 1-1
 - Using Microsoft Exchange 2000 or 2003 System Manager 1-2
 - Using the Microsoft Exchange 5.5 Administrator 1-2
- Installing the WebLogic Exchange Service 1-2
 - Installing Using Graphical-Mode Installation 1-3
 - Installing Using Console-Mode Installation 1-5
 - Verifying the Installation 1-9
- What's Included 1-10

Configuration

- Starting and Stopping the Exchange Service 2-1
 - Starting and Stopping from the Control Panel 2-1
 - Starting and Stopping from the Windows Start Menu 2-2
- Setting Process Rights 2-2
- Windows Domain Requirements 2-2
- Maintaining Application/Service Uptime 2-2
 - Reporting an Exchange Service Crash 2-3

About This Guide

This guide is intended for Microsoft Exchange administrators who need to install the WebLogic Exchange Service.

Note: Use of the WebLogic Exchange Service supports connecting to Microsoft Exchange 5.5, 2000 and 2003 and is used with the Exchange/MAPI Provider. If you are running Microsoft Exchange 2000 or 2003, you can use the Exchange/WebDAV Provider for connectivity to Exchange; therefore, the WebLogic Exchange Service is not required to be installed.

Refer to the *BEA WebLogic Personal Messaging API Administration Guide* for more information on the differences between the Exchange/MAPI Provider and Exchange/WebDAV Provider.

This chapter contains the following sections:

- [Prerequisites](#)
- [Documentation Conventions](#)

Prerequisites

Before you install the WebLogic Exchange Service, perform the following steps:

1. Install the Java Development Kit (JDK) 1.4 (or higher).
2. The MAPI subsystem must be installed on the WebLogic Exchange Service machine. For more information, see [“Installing the MAPI Subsystem” on page 1-1](#).
3. Refer to the *BEA WebLogic Personal Messaging API Supported Configurations Guide* for more information on specific platform and OS combinations.

Documentation Conventions

The Windows convention of “\” as a path separator is used wherever necessary.

Also, since system software and configurations can vary from one system to another, portions of the command syntax displayed in this document may include sample parameters or variables that represent the actual command syntax you would need to enter. These entries are indicated by parameters in uppercase placed between percent signs (%PARAMETER%), as shown in the following table.

Parameter	Definition
%BEA_HOME%	The complete directory specification for the product. For example, d:\bea\.
%BEA_EXCHANGE_SERVICE_HOME%	The complete directory specification for the WebLogic Exchange Service. For example, d:\bea\wlpmapi43\exchange_service.

Installation

This chapter describes how to install the MAPI subsystem and Exchange Service.

Note: The %BEA_HOME% directory refers to the directory where products are installed and %BEA_EXCHANGE_SERVICE_HOME% refers to the directory the Exchange Service is installed.

This chapter contains the following sections:

- [Installing the MAPI Subsystem](#)
- [Installing the WebLogic Exchange Service](#)
- [What's Included](#)

Installing the MAPI Subsystem

You can install the MAPI subsystem with the Microsoft Exchange 2000 or 2003 System Manager or the Microsoft Exchange 5.5 Administrator.

Note: Before installing the MAPI subsystem, be sure the machine satisfies the Windows Domain requirements. For more information, [“Windows Domain Requirements” on page 2-2](#).

This section contains the following topics:

- [Using Microsoft Exchange 2000 or 2003 System Manager](#)
- [Using the Microsoft Exchange 5.5 Administrator](#)

Using Microsoft Exchange 2000 or 2003 System Manager

Perform the following steps to install the WebLogic Exchange Service using the System Manager:

1. Insert the Microsoft Exchange 2000 or 2003 Server CD.
2. Assign the Install action to Microsoft Exchange System Management Tools.
Note: Do not install Microsoft Exchange 5.5 Administrator.
3. Click **Next** and choose an installation path.
4. Click **Finish** to complete the installation.
5. Recommended: Install the latest Service Pack of Microsoft Exchange.
6. Set the Process Rights. For more information see [“Setting Process Rights” on page 2-2](#).

Using the Microsoft Exchange 5.5 Administrator

Perform the following steps to install the WebLogic Exchange Service using the Administrator:

1. Insert the Microsoft Exchange 5.5 Server CD.
Note: If you are running Exchange 2000, the Exchange 5.5 CD also ships with Exchange 2000 distributions.
2. Choose **Setup Server and Components**.
3. Choose **Microsoft Exchange 5.5**.
4. Choose **Complete/Custom**.
5. Choose **Microsoft Exchange Administrator only** install (uncheck all other boxes).
6. Enter the Microsoft license key.
7. Set the Process Rights. For more information, see [“Setting Process Rights” on page 2-2](#).
8. Install the Exchange 5.5 Service Pack 4 available at <http://www.microsoft.com/exchange/downloads/55/sp4.asp>

Installing the WebLogic Exchange Service

The BEA installation program supports the following methods for installing the WebLogic Exchange Service software:

- Graphical mode

Graphical-mode installation is an interactive, GUI-based method for installing WebLogic Exchange Service. It can be run on both Windows and UNIX systems. For installation procedures, see [“Installing Using Graphical-Mode Installation” on page 1-3](#)

Note: If you want to run graphical-mode installation, the console attached to the machine on which you are installing the software must support a Java-based GUI. All consoles for Windows systems support Java-based GUIs, but not all consoles for UNIX systems do. If you attempt to start the installation program in graphical mode on a system that cannot support a graphical display, the installation program automatically starts console-mode installation.

- Console mode

Console-mode installation is an interactive, text-based method for installing WebLogic Exchange Service, from the command line, on either a UNIX system or a Windows system. For instructions for using this method, see [“Installing Using Console-Mode Installation” on page 1-5](#).

Installing Using Graphical-Mode Installation

Perform the following steps to install the WebLogic Exchange Service using the Graphical-Mode installation.

- [Start Graphical-Mode Installation](#)
- [Running the Installation Program](#)

Start Graphical-Mode Installation

Note: If you are installing WebLogic Exchange Service on a Windows system that supports more than one monitor, you must disable all but one monitor before starting the installation program.

To start the installation in graphical mode on a Windows system:

1. Log in to the Windows system.

2. Obtain the WebLogic Exchange Service installer. This installer is available from the WebLogic Personal Messaging API product bundle.
3. Go to the directory that contains the installation file and invoke the installation procedure by entering the following command:

```
java -jar wl_exchange_service_setup-XX.jar
```

Here, `wl_exchange_service_setup-XX.jar` is the name of the WebLogic Exchange Service installation file. In this filename, `XX` represents the version number of the software you are installing.

Note: To ensure that the hardware/software configuration on which you are installing the product is supported by WebLogic Exchange Service, see the [Supported Configurations Guide](#).

4. Proceed to [Running the Installation Program](#).

Running the Installation Program

The installation program prompts you to enter specific information about your system and configuration. For instructions on responding to the prompts during installation, see [Table 1-1](#).

Table 1-1 Console Installation Prompts

In this window...	Perform the following action...
Welcome	Click Next to proceed with the installation. You may cancel the installation at any time by clicking Exit .
BEA License Agreement	Read the BEA Software License Agreement and indicate your acceptance of the terms of the agreement by selecting Yes . To continue with the installation, you must accept the terms of the license agreement and then click Next .
Choose BEA Home Directory	Specify the BEA Home directory that will serve as the central support directory for all BEA products installed on the target system. If you already have a BEA Home directory on your system, you can select that directory (recommended) or create a new BEA Home directory. If you choose to create a new directory, the WebLogic Exchange Service installation program automatically creates the directory for you. The files in the BEA Home directory are essential to ensuring that BEA software operates correctly on your system such as ensuring that licensing works correctly for the installed BEA products.

Table 1-1 Console Installation Prompts

In this window...	Perform the following action...
Choose Install Type	Select the option button for the type of installation you want to perform: <ul style="list-style-type: none"> • Complete-all the software components provided with Exchange Service, including sample files, are installed on your system. • Custom-you select software components to be installed.
Choose Components	Note: This window is displayed only if you selected Custom installation in the Choose Install Type window. Specify the components to be installed by selecting or clearing the appropriate check boxes. This window displays a tree-view of all the components available for installation. In an initial installation, all components are selected.
Choose Product Directory	Specify the directory in which you want to install the WebLogic Exchange Service software and click Next. You can accept the default product directory (<code>wlpmapi43</code>) or create a new product directory. If you choose to create a new directory, the installation program automatically creates the directory for you.
Choose JDK_HOME Directory	Specify the directory in which your JDK is installed.
Choose Shortcut Location	Specify the location for the shortcuts to BEA product components.
Status	Read the information displayed about BEA products and services.
Installation Complete	Click Done to exit the installation program.

Installing Using Console-Mode Installation

Perform the following steps to install the WebLogic Exchange Service using the Console-Mode Installation. You can install on either Windows or Unix.

- [Start Console-Mode Installation on Windows](#)
- [Start Console-Mode Installation on UNIX](#)
- [Running the Console-Mode Installation](#)

Start Console-Mode Installation on Windows

1. Obtain the WebLogic Exchange Service installer. This installer is available from the WebLogic Personal Messaging API product bundle.
2. Open an MS-DOS command prompt window.
3. Go to the directory that contains the installation file and invoke the installation procedure by entering the following command:

```
java -jar wl_exchange_service_setup-XX.jar -mode=console
```

Here, `wl_exchange_service_setup-XX.jar` is the name of the WebLogic Exchange Service installation file. In this filename, `XX` represents the version number of the software you are installing.

Note: To ensure that the hardware/software configuration on which you are installing the product is supported by WebLogic Exchange Service, see the [Supported Configurations Guide](#).

4. Proceed to [Running the Console-Mode Installation](#).

Start Console-Mode Installation on UNIX

1. Obtain the WebLogic Exchange Service installer. This installer is available from the WebLogic Personal Messaging API product bundle.
2. Open a shell window.
3. Add the bin directory of the appropriate SDK to the beginning of the PATH variable definition on the target system. For example:

```
PATH=JDK_HOME/bin:$PATH
```

```
export PATH
```

JDK_HOME represents the full path to the Java SDK directory.

4. Go to the directory that contains the installation file and invoke the installation procedure by entering the following command:

```
java -jar wl_exchange_service_setup-XX.jar -mode=console
```

Here, `wl_exchange_service_setup-XX.jar` is the name of the WebLogic Exchange Service installation file. In this filename, `XX` represents the version number of the software you are installing.

Note: To ensure that the hardware/software configuration on which you are installing the product is supported by WebLogic Exchange Service, see the *Supported Configurations Guide*.

5. Proceed to [Running the Console-Mode Installation](#).

Running the Console-Mode Installation

To complete the console-mode installation process, respond to the prompts in each section by entering the number associated with your choice or by pressing `Enter` to accept the default. To exit the installation process, enter `exit` (or `x`, for short) in response to any prompt. To review or change your selection, enter `previous` (or `p`, for short) at the prompt. To proceed to the following window, enter `next` (or `n`, for short).

Note: The sample console text and directory pathnames in this section use Windows conventions (backslashes) for pathnames, for example `C:\bea\wlpmapi43`. When entering pathnames on a UNIX system, use the UNIX convention (forward slashes) in pathnames, for example, `/home1/bea/wlpmapi43`.

The following procedure steps you through the installation program. Use this procedure after you have started the installation program in console mode as described in the previous sections.

1. At the Welcome prompt, type `next` (or `n` for short) or press `Enter` to continue with the installation process.

The BEA Systems License Agreement prompt is displayed.

2. Read the Agreement and indicate your acceptance or rejection of its terms by doing one of the following at the prompt:

- Type `1` to indicate your agreement with the terms of the license and proceed with the installation. To review the entire agreement, press `Enter` or type `Down` several times.

Type `Up` to scroll back through sections previously displayed.

- Type `2` if you do not agree with the terms of the license. If you type `2`, the installation process terminates.

The Choose BEA Home directory prompt is displayed.

3. Specify the BEA Home directory that will serve as the central support directory for all BEA products installed on the target system.

The installation program displays the following prompt:

Choose BEA Home Directory:

Installation

```
-----  
*BEA home choice  
1|Create a new BEA Home [C:\bea]  
->2|Use an existing BEA Home [D:\beahome1]  
Enter index number to select OR [Exit] [Previous] [Next]>
```

Note: Instead of typing complete words when you want to enter [Exit], [Previous], and [Next], you can use the following one-letter shortcuts: x, p, and n, respectively.

4. Do one of the following:

- To use an existing BEA Home directory, type 2 or *next* (or *n* for short), or press *Enter*. If you have more than one BEA Home directory on your system, an additional prompt will display the directories. Type the number associated with the desired BEA Home directory.
- To create a new BEA Home directory, type 1, then at the prompt, enter the full path of the BEA Home directory, for example *C:\beahome2*. If you specify a directory that does not exist, the installation program creates it for you.

4. Whether you accept the existing BEA Home directory or choose to create a new BEA Home directory, you are prompted to confirm your selection, as shown in the following sample:

```
Choose BEA Home Directory:  
-----  
*BEA home choice  
->1|Yes, Use this BEA home directory [C:\bea]  
2|No, return to BEA home directory selection  
Enter index number to select OR [Exit] [Previous] [Next]>
```

5. On the command line, type 1 or press *Enter* to accept your selection. Otherwise, type 2 to return to the *Choose BEA Home Directory* panel where you can modify your entry.
6. After you have selected your BEA Home directory and confirmed your selection, the *Choose Install Type* prompt is displayed.
7. Specify the type of installation you want to perform by entering the number associated with the install type, as shown in the following text:

```
Choose Install Type:  
-----
```



```
->1|Complete
2|Custom Installation
```

8. Do one of the following:
 - Type 1 or press `Enter` to choose a complete installation.
 - Type 2 to choose a custom installation. The `Choose Components` prompt is displayed.
9. Specify the directory in which you want to install the WebLogic Exchange Service software. Select the default product directory (`BEA_HOME\wlpmpi43`) or create a new product directory.

If you specify a new directory, the installation program automatically creates it for you.

The choices displayed in this section are as follows:

```
Choose Product Directory:
```

```
-----
```

```
Product Installation Directory= [C:\bea\wlpmpi43]
```

```
Input new Product Installation Directory OR [Exit] [Previous] [Next] >
```

11. Do one of the following:
 - Press `Enter` or type `next` (or `n` for short) to accept the current selection.
 - Enter the full path to the directory in which you want to install the WebLogic Exchange software and press `Enter`.
12. You are prompted to confirm your selection as shown in the following text:

```
Choose Product Directory:
```

```
-----
```

```
->1| Yes, use this product directory [C:\bea\wlpmpi43]
```

```
2| No, select another product directory
```

```
Enter index number to select OR [Exit] [Previous] [Next] >\
```

Verify that your entry is correct, then type 1 or press `Enter` to proceed with the installation. Otherwise, type 2 to return to the `Choose Product Directory` panel where you can modify your entry.

10. Specify the `JDK_HOME` directory where your Java SDK is installed.
11. Specify the location for the shortcuts to BEA product components.
12. Press `Enter` or type `Exit` to exit the installation program.

Verifying the Installation

Perform the following steps to verify the installation:

1. Browse to **Start > Settings > Control Panel > Administrative Tools > Services**.
2. Confirm that the BEA WebLogic Exchange Service is installed.

What's Included

The WebLogic Exchange Service installation includes the following directories:

Table 1-2 Installation Directories

Directory	Description
%BEA_HOME%	The product install directory. For example, d:\bea.
%BEA_HOME%\wlpmap143	The WebLogic Personal Messaging API product install directory. For example, d:\bea\wlpmap143. This is %BEA_WLPMAPI_HOME%.
%BEA_WLPMAPI_HOME%\exchange_service	The WebLogic Exchange Service files. This is %BEA_EXCHANGE_SERVICE_HOME%.
%BEA_EXCHANGE_SERVICE_HOME%\bin	The WebLogic Exchange Service binary executable files.
%BEA_EXCHANGE_SERVICE_HOME%\lib	The core WebLogic Exchange Service Java libraries including third-party components
%BEA_EXCHANGE_SERVICE_HOME%\scripts	Scripts to facilitate starting and stopping the WebLogic Exchange Service.

Configuration

This chapter describes how to configure the WebLogic Exchange Service.

This chapter contains the following sections:

- [Starting and Stopping the WebLogic Exchange Service](#)
- [Setting Process Rights](#)
- [Windows Domain Requirements](#)
- [Maintaining Application/Service Uptime](#)

Starting and Stopping the WebLogic Exchange Service

You can start and stop the WebLogic Exchange Service from the Control Panel or from the Windows Start Menu.

This section contains the following topics:

- [Starting and Stopping from the Control Panel](#)
- [Starting and Stopping from the Windows Start Menu](#)

Starting and Stopping from the Control Panel

Perform the following steps to start or stop the WebLogic Exchange Service from the Control Panel:

1. Browse to **Start > Settings > Control Panel > Administrative Tools > Services**.

2. Locate the **BEA WebLogic Exchange Service**.
 - To start the service: Right-click on the service and select **Start**.
 - To stop the service: Right-click on the service and select **Stop**.

Starting and Stopping from the Windows Start Menu

Perform the following steps to start or stop the WebLogic Exchange Service from the Windows Start Menu:

1. Browse to **Start > Programs > BEA WebLogic > Personal Messaging API > Exchange Service**.
2. To start the service, select **Start Service**. To stop the service, select **Stop Service**.

Setting Process Rights

The machine that runs the WebLogic Exchange Service and the MAPI subsystem on behalf of users requires the “Act as Part of Operating System” privilege. This process actually logs the user accessing their Exchange mailbox into the Windows machine and the operating system calls required to do this need “Act as Part of Operating System”. If WebLogic Exchange Service runs as LocalSystem (the default), no further action is required since this privilege is granted to the LocalSystem user.

To grant “Act as Part of Operating System” privilege, browse to **Control Panel > Administrative Tools > Local Security Policy > Local Policies > User Rights Assignment**.

Windows Domain Requirements

The machine running the WebLogic Exchange Service must be in the same domain as the Exchange server, or on a domain with a bidirectional trust relationship with the Exchange domain. Additionally, each user that will access their mailbox using the machine with the WebLogic Exchange Service must have “Log on Locally” rights to that machine.

Maintaining Application/Service Uptime

The WebLogic Exchange Service runs as a Windows service. This allows you to use the Windows built-in crash recovery for services. To enable crash recovery, go to **Control Panel > Administrative Tools > Services > properties** for the service you are running. Under the **Recovery** tab, set **First Failure, Second Failure and Subsequent Failures** to **Restart the**

Service. You may want to set the **Restart Service After** time to 0 minutes, so that the service restarts immediately.

Note: In the event that the service does restart, all existing sessions will be lost.

Reporting a WebLogic Exchange Service Crash

This section includes steps to gather information to help debug an WebLogic Exchange Service crash. Provide as much of the following information when submitting your request to support:

- **The contents of your Application Log in the Event Viewer** – This can be obtained by running `eventvwr`, right clicking on the Application Log and choosing **Save File As**. Save the file in `.evt` format.
- **What operation was being performed at the time of the crash, what mailbox was being hit, and a PST file containing the contents of the mailbox against which the crash occurred** – PST files may be exported from Outlook. This can be difficult to obtain, but given the data and a series of steps to reproduce a particular problem, support will be better able to solve any crash issue.
- **The version information for `cz_mapi.dll`** – In Windows Explorer, right click the `cz_mapi.dll` file and select the **Version** tab.
- **A crash log from Java** – When a crash occurs, frame information is written to an `hs*.log` file (HotSpot Log).

Configuration