

Oracle® JRockit Real Time

Installation Guide

3.0

June 2008

ORACLE®

Copyright © 2007, 2008, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Contents

Installing Oracle JRockit Real Time

Note on Oracle JRockit Real Time Installation	1
Supported Configurations	1
Notation Used in this Guide.	2
Installing and Uninstalling JRockit Real Time	2
Installing JRockit Real Time.	2
To install JRockit Real Time	3
To start JRockit Real Time (Windows x86).	5
Adding JRockit Real Time to Your Path	5
Uninstalling JRockit Real Time	6
Uninstalling Windows Versions.	6
Uninstalling Windows Versions from the Command Line	6
Uninstalling Linux and Solaris Versions from the Command Line.	6
Installing and Uninstalling JRockit Real Time in Console Mode	7
Installing JRockit Real Time in Console Mode	7
Uninstalling JRockit Real Time in Console Mode	7
Installing and Uninstalling JRockit Real Time in Silent Mode	8
The silent.xml File	8
Installing JRockit Real Time in Silent Mode	9
Uninstalling JRockit Real Time in Silent Mode	9
Special Note About Installing on Linux or Solaris	10
Ensure the Installer is Executable.	10

Acquire Root Access for System Wide Installation	10
Identify the Default Location of System Preferences.	10

Installing Oracle JRockit Real Time

This section describes how to install Oracle JRockit Real Time as a standalone application. It includes information on the following subjects:

- [Supported Configurations](#)
- [Notation Used in this Guide](#)
- [Installing and Uninstalling JRockit Real Time](#)
- [Installing and Uninstalling JRockit Real Time in Console Mode](#)
- [Installing and Uninstalling JRockit Real Time in Silent Mode](#)
- [Special Note About Installing on Linux or Solaris](#)

Note: JRockit Real Time can be used by any application and does not interact with or create an Oracle registry.

Note on Oracle JRockit Real Time Installation

This document shows how to install Oracle JRockit Real Time only. The Oracle JRockit JVM is installed as a part of many Oracle products. Refer to the documentation for those products for installation instructions.

Supported Configurations

For a complete list of supported configurations, please visit:

http://edocs.bea.com/jrockit/jrdocs/suppPlat/supp_plat.html

Notation Used in this Guide

Throughout this document, JRockit Real Time versions are defined with the following notation:

`jrrt-<jrrt_version>-<java_version>`

For example:

`jrrt-3.0.0-1.6.0`

In this example, the product is JRockit Real Time 3.0 for Java SE 6.

Installing and Uninstalling JRockit Real Time

This section explains how to install and uninstall a standalone version of JRockit Real Time in GUI mode for the following platforms:

- Microsoft Windows 32-bit x86 and 64-bit Xeon/AMD64.
- Red Hat Linux 32-bit x86 and 64-bit Xeon/AMD64.
- Sun Solaris on 64-bit SPARC.

Note: If you are installing on Linux and Solaris, please refer to [Identify the Default Location of System Preferences](#) for information on where to find the system preferences.

Installing JRockit Real Time

In the following procedure you will run the self-installing executable (Windows) or the self-extracting binary (Solaris and Linux). The screen shots are taken from a Windows installation of JRockit Real Time. The executables for this release of JRockit Real Time are listed in [Table 1](#).

Table 1 JRockit Real Time Installers by Version and Platform

On...	For Java SE version...	Use...
Windows 32-bit x86	1.4.2	<code>jrrt-3.0.0-1.4.2-windows-ia32.exe</code>
	5.0	<code>jrrt-3.0.0-1.5.0-windows-ia32.exe</code>
	6	<code>jrrt-3.0.0-1.6.0-windows-ia32.exe</code>

Table 1 JRockit Real Time Installers by Version and Platform

On...	For Java SE version...	Use...
Windows 64-bit Xeon/AMD64	5.0	jrrt-3.0.0-1.5.0-windows-x64.exe
	6	jrrt-3.0.0-1.6.0-windows-x64.exe
Red Hat Linux 32-bit x86	1.4.2	jrrt-3.0.0-1.4.2-linux-ia32.bin
	5.0	jrrt-3.0.0-1.5.0-linux-ia32.bin
	6	jrrt-3.0.0-1.6.0-linux-ia32.bin
Red Hat Linux 64-bit Xeon/AMD64	5.0	jrrt-3.0.0-1.5.0-linux-x64.bin
	6	jrrt-3.0.0-1.6.0-linux-x64.bin
Sun Solaris on 64-bit Sparc	1.4.2	jrrt-3.0.0-1.4.2-solaris-sparcv9.bin
	5.0	jrrt-3.0.0-1.5.0-solaris-sparcv9.bin
	6	jrrt-3.0.0-1.6.0-solaris-sparcv9.bin

To install JRockit Real Time

1. Make sure you have downloaded the appropriate version of JRockit Real Time for your operating system (see [Table 1](#)).
2. On your local drive, locate the executable file for the version of JRockit Real Time you want to install.

Note: If you install JRockit Real Time on Linux or Solaris please refer to [Ensure the Installer is Executable](#).


3. Run the installer.

The install process begins and the Oracle installer window appears, followed by the **Welcome** window.

4. Click **Next**.

The **Choose Product Installation Directory** window appears (see [Figure 1-2](#)).

Figure 1-2 Choose Product Installation Directory Window




5. Click **Next** if you are satisfied with the suggested installation directory.

Note: If you want a different location for the installation you can pick one by clicking **Browse** or type a new directory into the **Product Installation Directory** field. By clicking **Reset**, you set the selection back to the default directory.

6. Click **Next** (the installation starts immediately after you click **Next**).

The **Oracle Installer** window appears and the installation process continues, as indicated on the progress meter in the lower right corner of the window (see [Figure 1-3](#)).

Figure 1-3 Oracle Installer Window with Progress Meter



When the installation is complete, the **Installation Complete** window appears.

7. Click **Done**.

JRockit Real Time is now installed.

To start JRockit Real Time (Windows x86)

If you have installed JRockit Real Time you can start Oracle JRockit Mission Control 3.0.3 from the **Start** menu.

Adding JRockit Real Time to Your Path

Once you have installed JRockit Real Time, you need to add it to your path.

Use this command for Windows platforms:

Note: This example assumes that you are using the Windows Command Prompt (DOS) or compatible command shell and have selected the default product installation directory.

```
set PATH=%ProgramFiles%\JRockit Real
Time\jrirt-<jrirt_version>-<java_version>\bin;%PATH%
```

Use this command for Linux and Solaris platforms:

Note: This example assumes that you are using the UNIX bash shell or compatible command shell and have selected the default product installation directory.

```
export PATH=$HOME/jrirt-<jrirt_version>-<java_version>/bin:$PATH
```

Uninstalling JRockit Real Time

This section describes how to uninstall the Windows, Linux, and Solaris versions of JRockit Real Time.

Uninstalling Windows Versions

To uninstall JRockit Real Time, do the following:

1. Click **Start** and open the **All Programs** menu.
2. Select Oracle JRockit Real Time [version]>**Uninstall Oracle JRockit Real Time [version]**.
The **Oracle Uninstaller** confirmation message appears.
3. Click **OK**.
 - The **Oracle Uninstaller** appears and the uninstall process commences.

4. Click **OK**.

JRockit Real Time is removed from your computer.

Uninstalling Windows Versions from the Command Line

To uninstall JRockit Real Time from the command line, run the following command from a console window:

```
%SystemRoot%\Installer\Oracle\jrirt-<jrirt_version>-<java_version>-<arch>\uninstall.exe
```

Uninstalling Linux and Solaris Versions from the Command Line

To uninstall Linux and Solaris versions of JRockit Real Time, do the following:

1. Ensure you are one step below the appropriate JRockit Real Time product directory.
2. At the command line, enter:

```
rm -rf jrirt-<jrirt_version>-<java_version>
```

JRockit Real Time is removed from your computer.

Installing and Uninstalling JRockit Real Time in Console Mode

This section describes how to install JRockit Real Time using console mode, rather than from a GUI.

Installing JRockit Real Time in Console Mode

To install JRockit Real Time in console mode, do the following:

1. Make sure you have downloaded the appropriate version of JRockit Real Time for your operating system (see [Table 1](#)).
2. On your local drive, locate the executable file for the version of JRockit Real Time you want to install:

Note: If you install JRockit Real Time on Linux or Solaris please refer to [Ensure the Installer is Executable](#).

3. Open a command window or console on your computer.
4. Change to the directory from which you want to install JRockit Real Time.
5. At the command line, enter:

```
jrirt-<jrirt_version>-<java_version>-<platform>.<ext> -mode=console
```

where *ext* is the file name extension, either *exe* on Windows and *bin* on Linux and Solaris.

The system responds:

```
Extracting 0%.....100%
```

Once the extraction process is complete, the system will prompt you through the installation, replicating the procedures described in [Installing and Uninstalling JRockit Real Time](#).

Note: If you don't specify `-mode=console` at the command line, the installer will revert to GUI mode, as described in [Installing and Uninstalling JRockit Real Time](#).

Uninstalling JRockit Real Time in Console Mode

To uninstall Windows versions, use one of the methods described in [Uninstalling Windows Versions](#) and [Uninstalling Windows Versions from the Command Line](#).

To uninstall Linux and Solaris versions, use the method described in [Uninstalling Linux and Solaris Versions from the Command Line](#).

Installing and Uninstalling JRockit Real Time in Silent Mode

The silent installation mode lets you set installation configurations only once and then use those configurations to duplicate the installation on many machines. During installation in silent mode, the installation program reads installation options from an XML file that you create prior to beginning the installation (see [The silent.xml File](#)). The installation program does not display any configuration options during the installation process. For more information on silent mode, please refer to “[What Is Silent-Mode Installation?](#)” in the Oracle WebLogic Server *Installation Guide*.

The silent.xml File

For a silent mode installation to be successful, you will need to create the file `silent.xml` and store it on your computer. This file contains the values you want included in your setup. [Listing 1](#) shows an example of a `silent.xml` file for JRockit Real Time 3.0 for Java SE 6.

Listing 1 Example of a silent.xml File

```
<?xml version="1.0" encoding="UTF-8" ?>
<domain-template-descriptor>
  <input-fields>
    <!--
      Installation directory
      This option is valid for all platforms and Oracle JRockit Real Time products
    -->
    <data-value name="USER_INSTALL_DIR" value="C:\Program Files\JRockit Real
Time\jrirt-3.0.0-1.6.0" />
    <!--
  </input-fields>
</domain-template-descriptor>
```

Installing JRockit Real Time in Silent Mode

To install JRockit Real Time in silent mode, do the following (this procedure assumes that `silent.xml` is stored in the same directory as the JRockit Real Time installer):

1. Make sure you have downloaded the appropriate version of JRockit Real Time for your operating system (see [Table 1](#)).
2. On your local drive, locate the executable file for the version of JRockit Real Time you want to install:

Note: If you install JRockit Real Time on Linux or Solaris please refer to [Ensure the Installer is Executable](#).

3. Open a command window or console on your computer.
4. Change to the directory from which you want to install JRockit Real Time.
5. At the command line, enter:

```
jrirt-<jrirt_version>-<java_version>-<platform>.<ext> -mode=silent
-silent_xml="silent.xml"
```

where `ext` is the file name extension, either `exe` on Windows and `bin` on Linux and Solaris.

You will receive a message advising that files are being extracted and no other confirmation.

If you want to confirm the installation on Windows, click **Start > Programs**. If the installation is successful, you will see Oracle JRockit Real Time in your Program menu.

Note: If you want to create an install log, add the option `-log=log.log` at the end of the command.

Uninstalling JRockit Real Time in Silent Mode

To uninstall Windows versions, use one of the methods described in [Uninstalling Windows Versions](#) and [Uninstalling Windows Versions from the Command Line](#).

To uninstall Linux and Solaris versions, use the method described in [Uninstalling Linux and Solaris Versions from the Command Line](#).

Special Note About Installing on Linux or Solaris

If you are installing JRockit Real Time on either a Linux or Solaris machine, note the following information.

Ensure the Installer is Executable

If you install JRockit Real Time on Linux or Solaris by using the `.bin` file, you need to ensure the file is executable. You can use `chmod +x <filename>` to make the file executable.

Acquire Root Access for System Wide Installation

If you choose to install JRockit Real Time on Linux or Solaris into a system-wide location such as `/usr/local`, you must first become the root user to gain the necessary permissions. If you do not have root access, simply install JRockit Real Time into a directory where you have permission to write, for example, your home directory.

Identify the Default Location of System Preferences

When installing on Linux and Solaris, the default location for system preferences will be:

```
<JAVAHOME>/systemPrefs
```

where `<JAVA_HOME>=<INSTALLDIR>/jre`.

unless the user is root, in which case it will be `/etc/.java/systemPrefs`.