

Oracle® Insurance IStream
IStream Publisher Error Messages
Release 4.2
E14879-01

January 2009

Copyright

Copyright © 2009, Oracle and/or its affiliates. All rights reserved.

Primary Authors: Andrew Brooke and Ken Weinberg

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS

Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are “commercial computer software” or “commercial technical data” pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

IStream Publisher 4.2 Error Messages

Contents	Page
Simple Requests	2
Aggregate Request	28
Distribution Request	31
System Errors	41

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S1	text="P2P.52: Could not open destination./Login failed (530 User userA cannot log in.)">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.52: Could not open destination./Login failed (530 User userA cannot log in.)/java.io.IOException	Invalid FTP destination credential. The user ID (userA) does not exist.		PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="ftp://dsdb1/Source/sourcefile.pdf"/> <destination ContentType="application/postscript" url="ftp://dsdb1/test-only/destinationfile\$ID.ps"> <credentials user="userA" password="password" /> </destination> </render-PDF-to-TIFF>
S2	Could not open destination./Malformed url D:file:///c:/DS31/Source/pdf2tiff/destination.tiff">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.52: Could not open destination./Malformed url D:file:///c:/DS31/Source/pdf2tiff/destination.tiff	Invalid destination URL. The D drive does not exist.		PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales.pdf"/> <destination ContentType="image/tiff" url="D:file:///c:/DS31/Source/pdf2tiff/destination.tiff"/> </render-PDF-to-TIFF>
S3	Could not open destination./The file c:\DS31\Source\pdf2tiff\destinationfile.tiff does not exist">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.52: Could not open destination./The file c:\DS31\Source\pdf2tiff\destinationfile.tiff does not exist	The existing file cannot be overwritten. The destination.tiff is read-only under the destination directory.	Allow 'write' permissions on file that will be overwritten. Because the file presently has only 'read-only' permissions, the system cannot overwrite the file as it cannot be opened.	PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales.pdf"/> <destination ContentType="image/tiff" url="file:///c:/DS31/Source/pdf2tiff/destinationfile.tiff"/> </render-PDF-to-TIFF>
S4	Could not open destination./The repository object does not point to an existing file or folder">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.52: Could not open destination./The repository object does not point to an existing file or folder/com.insystems.repository.ftpadapter.FtpException	FTP destination (folderA) has no write permission.	Allow 'write' permissions on the parent folder as well as the destination file that will be overwritten. Because the parent folder as well as the file presently have no write permissions, the system cannot overwrite the file as it cannot be opened.	PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="ftp://dsdb1/Source/sourcefile.pdf"/> <destination ContentType="application/postscript" url="ftp://dsdb1/folderA/destinationfile\$ID.ps"> </render-PDF-to-TIFF>
S5	Invalid source for PDF Rendering./Repository object does not exist">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.14: Invalid source for PDF Rendering./Repository object does not exist/com.insystems.repository.RepositoryException	FTP source file (sourcefile.pdf) has no read/write permission	Allow read' permissions on source file. Because the file presently has no read or write permissions, the system cannot access the file or open it to read the contents.	PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="ftp://dsdb1/Source/sourcefile.pdf"/> <destination ContentType="application/postscript" url="ftp://dsdb1/shared/destinationfile\$ID.ps"/> </render-PDF-to-TIFF>
S6	response hanging	Invalid JMS type in the render request. Should be PDF, not PDD.		PDF-2-TIFF	JMSType render-PDD-to-TIFF
S7	Invalid source for PDF Rendering./No object at: file:/c:/DS31/Source/file.pdf">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.14: Invalid source for PDF Rendering./No object at: file:/c:/DS31/Source/hello.pdf/com.insystems.repository.RepositoryException	Incorrect render element in request: file.pdf does not exist in the source directory		PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="{filesources}/file.pdf"/> <destination ContentType="image/tiff" url="{filesources}/pdf2tiff/destinationfile.pdf"/> </render-PDF-to-TIFF>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S8	P2P.64: Conversion from PDF to PS failed. Error code=1 () messageKey="P2P.64">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.64: Conversion from PDF to PS failed. Error code=1 ()	Invalid source document file type. Source file should be pdf, not ps.	Ensure that the source document is a valid PDF file with the correct PDF mime type and .pdf extension. One way to ensure this is to check that the file can be opened and displayed properly in Adobe Acrobat Reader.	PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales.ps"/> <destination ContentType="image/tiff" url="file:///c:/DS31/Source/pdf2tiff/destinationfile.pdf"/> </render-PDF-to-TIFF>
S9	The page range is out of range.">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.40: The page range is out of range.	Invalid page range. There are only 6 pages.		PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales.pdf"/> <destination ContentType="image/tiff" url="file:///c:/DS31/Source/hello.tiff"/> <output-name>Black Ice Fax</output-name> <fax-configuration pageRange="2-20"/> </render-PDF-to-TIFF>
S10	<errorDetails messageKey="P2P.14" text="P2P.14: Invalid source for PDF Rendering./Login failed (530 User test2 cannot log in.)">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.14: Invalid source for PDF Rendering./Login failed (530 User test2 cannot log in.)/java.io.IOException	Invalid credentials. The test2 user does not exist.		PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="ftp://dsdb1/shared2/sourcefile.pdf"> <credentials user="test2" password="password" /> </source> <destination ContentType="application/postscript" url="ftp://dsdb1/test-only/destinationfile.ps"> <credentials user="test" password="password" /> </destination> </render-PDF-to-TIFF>
S11	Invalid source for PDF Rendering./Malformed url ///D:/Sales.pdf">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.14: Invalid source for PDF Rendering./Malformed url ///D:/Sales.pdf	Invalid source URL wrong: The D drive does not exist.		PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="///D:/Sales.pdf"/> <destination ContentType="image/tiff" url="{filesource}/hello.tiff"/> </render-PDF-to-TIFF>
S12	Could not open destination./Malformed url #\$\$\$^file:///c:/DS31/Source/hello.tiff">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.52: Could not open destination./Malformed url #\$\$\$^file:///c:/DS31/Source/hello.tiff	There are special characters in the URL.		PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales.pdf"/> <destination ContentType="image/tiff" url="#\$\$\$^file:///c:/DS31/Source/hello.tiff"/> </render-PDF-to-TIFF>
S13	Invalid source for PDF Rendering./Repository object does not exist">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.14: Invalid source for PDF Rendering./Repository object does not exist/com.insystems.repository.RepositoryException	Invalid FTP source: the Source22 folder does not exist.		PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="ftp://dsdb1/Source22/sourcefile.pdf"/> <destination ContentType="application/postscript" url="ftp://dsdb1/shared2/destinationfile.ps"/> </render-PDF-to-TIFF>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S14	Could not open destination./Login failed (530 User test cannot log in.)>com.insystems.distributor.services.rendering.RenderingServiceException: P2P.52: Could not open destination./Login failed (530 User test cannot log in.)/java.io.IOException	Invalid destination credential password (password2)		PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="ftp://dsdb1/Source/sourcefile.pdf"/> <destination ContentType="application/postscript" url="ftp://dsdb1/test-only/destinationfile.ps"> <credentials user="test" password="password2" /> </destination> </render-PDF-to-TIFF>
S15	Invalid source for PDF Rendering./Repository object does not exist">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.14: Invalid source for PDF Rendering./Repository object does not exist/com.insystems.repository.RepositoryException	FTP source folder has no read/write permission.	Allow 'read' permissions on the parent folder containing source file. Because the folder presently has no read or write permissions, the system cannot access the file under this folder.	PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="ftp://dsdb1/Source/sourcefile.pdf"/> <destination ContentType="application/postscript" url="ftp://dsdb1/shared/destination.ps"/> </render-PDF-to-TIFF>
S16	Invalid source for PDF Rendering./The file {0} does not exist">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.14: Invalid source for PDF Rendering./The file {0} does not exist	Source file (sales.pdf) has no read/write permission.	Allow 'read' permissions on the source file. Because the file presently has no read or write permissions, the system cannot access the file or open it to read the contents.	PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales.pdf"/> <destination ContentType="image/tiff" url="file:///c:/DS31/Source/hello.tiff"/> </render-PDF-to-TIFF>
S17	P2P.40: The page range is out of range.">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.40: The page range is out of range.	Invalid page range: there are only 6 pages.		PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales2.pdf"/> <destination ContentType="image/tiff" url="file:///c:/DS31/Source/Sales10.tiff"/> <output-name>Black Ice Fax</output-name> <fax-configuration pageRange="1,2,4-8"/> </render-PDF-to-TIFF>
S18	P2P.40: The page range is out of range.">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.40: The page range is out of range.	Invalid page range: there are only 6 pages.		PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales2.pdf"/> <destination ContentType="image/tiff" url="file:///c:/DS31/Source/Sales10.tiff"/> <output-name>Black Ice Fax</output-name> <fax-configuration pageRange="2-8"/> </render-PDF-to-TIFF>
S19	Failed to create version due to: ApiError: ErrorMsg: No permission for this item. Status: Cannot Add Version (code=101603)">java.io.IOException: Failed to create version due to: ApiError: ErrorMsg: No permission for this item. Status: Cannot Add Version (code=101603)	DMS destination file has no modify permission.		PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="calligo://admin:password@Calligo;dsdb1:2099/Source/Sales20"/> > <destination ContentType="image/tiff" url="calligo://testuser:password@Calligo;dsdb1:2099/Destination/Sales20.tiff"/> </render-PDF-to-TIFF>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S20	It;nested>Failed to create object Sales20.tiff due to: ApiError: ErrorMsg: You do not have permission to create an item in 'Destination'.Status: Error Creating node com.insystems.repository.lapiadapter.CalligoDMSException: Failed to create object Sales20.tiff due to: ApiError: ErrorMsg: You do not have permission to create an item in 'Destination'.Status: Error Creating node	DMS destination folder has no add item permission.		PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="calligo://admin:password@Calligo;dsdb1:2099/Source/Sales20/"> > <destination ContentType="image/tiff" url="calligo://testuser:password@Calligo;dsdb1:2099/Destination/Sales20.tiff"/> </render-PDF-to-TIFF>
S21	P2P.52: Could not open destination./Failed to access the workspace in DMS due to: Invalid username/password specified.">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.52: Could not open destination./Failed to access the workspace in DMS due to: Invalid username/password specified./com.insystems.repository.lapiadapter.calligo.HandlerIOException	DMS destination credential is invalid: the username (admin2) is incorrect.		PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="calligo://admin:password@Calligo;dsdb1:2099/Source/Sales20/"> > <destination ContentType="image/tiff" url="calligo://Calligo;dsdb1:2099/Destination/Sales20.tiff"> <credentials user="admin2" password="password"/> </destination> </render-PDF-to-TIFF>
S22	"P2P.14: Invalid source for PDF Rendering./Failed to access the workspace in DMS due to: Invalid username/password specified.">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.14: Invalid source for PDF Rendering./Failed to access the workspace in DMS due to: Invalid username/password specified./com.insystems.repository.lapiadapter.calligo.HandlerIOException	DMS source password is invalid.	Ensure correct username/password credentials combination is provided to access the DMS, and that the credentials provided have the required permission to access the parent folder and/or source document(s) in the request.	PDF-2-TIFF	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="calligo://admin:password2@Calligo;dsdb1:2099/Source/Sales20/"> </source> <destination ContentType="image/tiff" url="calligo://Calligo;dsdb1:2099/Destination/Sales20.tiff"> <credentials user="admin" password="password"/> </destination> </render-PDF-to-TIFF>
S23	Could not open destination./The file c:\DS31\Destination\destinationfile.pcl does not exist">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.52: Could not open destination./The file c:\DS31\Destination\destinationfile.pcl does not exist	Destination folder has no write permission.	Ensure correct username/password credentials combination is provided to access the DMS, and that the credentials provided have the required permission to access the destination folder and(or) destination document(s) in the request.	PDF 2 PCL	<render-PDF-to-PCL> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales2.pdf"/> <destination ContentType="application/vnd.hp-PCL" url="file:///c:/DS31/Destination/destinationfile.pcl"/> </render-PDF-to-PCL>
S24	Invalid request data (com.insystems.distributor.services.pdf2pcl.Adobe@2dd353) ./Unable to set attribute "copies" for printer-configuration">com.insystems.distributor.ServiceException: DM.fromXml: Invalid request data (com.insystems.distributor.services.pdf2pcl.Adobe@2dd353) ./Unable to set attribute "copies" for printer-configuration/org.xml.sax.SAXException	Number of copies (2) is invalid.		PDF 2 PCL	<render-PDF-to-PCL> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales.pdf"/> <destination ContentType="application/vnd.hp-PCL" url="file:///c:/DS31/Destination/test2.pcl"/> <output-name>HPLJIII</output-name> <printer-configuration duplex="flipLongEdge" copies="-2" pageRange="1-4"> </printer-configuration> </render-PDF-to-PCL>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S25	<errorDetails messageKey="P2P.27" text="P2P.27: Could not open printer.">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.27: Could not open printer.</errorDetails>	Invalid printer driver (driver1).		PDF 2 PCL	<pre><render-PDF-to-PCL> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales.pdf"/> <destination ContentType="application/vnd.hp-PCL" url="file:///c:/DS31/Destination/test2.pcl"/> <output-name>driver1</output-name> <printer-configuration duplex="none" copies="2" pageRange="1-4" > </printer-configuration> </render-PDF-to-PCL></pre>
S26	Invalid request data (com.insystems.distributor.services.pdf2pcl.Adobe@9ff97)./Attribute "duplex" already appeared in this tag.">com.insystems.distributor.ServiceException: DM.fromXml: Invalid request data (com.insystems.distributor.services.pdf2pcl.Adobe@9ff97)./Attribute "duplex" already appeared in this tag./org.xml.sax.SAXParseException	Duplicate XML tags: duplex appears twice in the XML code.		PDF 2 PCL	<pre><render-PDF-to-PCL> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales.pdf"/> <destination ContentType="application/vnd.hp-PCL" url="file:///c:/DS31/Destination/test2.pcl"/> <output-name>HPLJIII</output-name> <printer-configuration duplex="flipLongEdge" copies="2" duplex="none" pageRange="1-4"> </printer-configuration> </render-PDF-to-PCL></pre>
S27	text="P2P.52: Could not open destination./Login failed (530 User userA cannot log in.)">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.52: Could not open destination./Login failed (530 User userA cannot log in.)/java.io.IOException	Invalid destination credential: userA does not exist.		PDF 2 PCL	<pre><render-PDF-to-PCL> <source ContentType="application/pdf" url="ftp://dsdb1/Source/sourcefile.pdf"/> <destination ContentType="application/postscript" url="ftp://dsdb1/test-only/destinationfile.ps"> <credentials user="userA" password="password" /> </destination> </render-PDF-to-PCL></pre>
S28	Could not open destination./Malformed url D:file:///c:/DS31/Source/pdf2tiff/destinationfile.pcl">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.52: Could not open destination./Malformed url D:file:///c:/DS31/Source/pdf2tiff/destinationfile.pcl	Invalid destination URL wrong: D drive does not exist.		PDF 2 PCL	<pre><render-PDF-to-PCL> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales.pdf"/> <destination ContentType="image/tiff" url="D:file:///c:/DS31/Source/pdf2tiff/destinationfile.pcl"/> </render-PDF-to-PCL></pre>
S29	P2P.64: Conversion from PDF to PS failed. Error code=1 (") messageKey="P2P.64">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.64: Conversion from PDF to PS failed. Error code=1 (")	Tried to print a corrupted source PDF file.	Ensure that the source document is a valid PDF file. One way to ensure this is to check that the file can be opened and displayed properly in Adobe Acrobat Reader.	PDF 2 PCL	<pre><render-PDF-to-PCL> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales.pdf"/> <destination ContentType="application/vnd.hp-PCL" url="file:///c:/DS31/Destination/destinationfile.pcl"/> <output-name>HPLJIII</output-name> </render-PDF-to-PCL></pre>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S30	P2P.64: Conversion from PDF to PS failed. Error code=1 (Error: May not be a PDF file (continuing anyway) Error (0): PDF file is damaged - attempting to reconstruct xref table...	The source PDF file was corrupt and therefore could not be rendered.		PDF 2 PCL	<pre><render-PDF-to-PCL> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales.pdf"/> <destination ContentType="application/vnd.hp-PCL" url="file:///c:/DS31/Destination/destinationfile\$ID.pcl"/> </render-PDF-to-PCL></pre>
S31	P2P.40: The page range is out of range.">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.40: The page range is out of range.	Invalid page range: there are only 6 pages total.		PDF 2 PCL	<pre><render-PDF-to-PCL> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales2.pdf"/> <destination ContentType="application/vnd.hp-PCL" url="file:///c:/DS31/Destination/test2.ps"/> <output-name>HPLJIII</output-name> <printer-configuration duplex="none" copies="2" pageRange="1,2,5-10" > </printer-configuration> </render-PDF-to-PCL></pre>
S32	Could not open destination./The repository object does not point to an existing file or folder">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.52: Could not open destination./The repository object does not point to an existing file or folder/com.insystems.repository.ftpadapter.FtpException	FTP destination folder has no write permission.	Allow 'write' permissions on the parent folder as well as the destination file that will be overwritten. Because the parent folder as well as the file presently have no write permissions, the system cannot overwrite the file as it cannot be opened.	PDF 2 PS	<pre><render-PDF-to-PS> <source ContentType="application/pdf" url="ftp://dsdb1/Source/sourcefile.pdf"/> <destination ContentType="application/postscript" url="ftp://dsdb1/shared2/destinationfile\$ID.ps"/> <output-name>HPPS</output-name> <printer-configuration duplex="flipLongEdge"/> </render-PDF-to-PS></pre>
S33	text="P2P.52: Could not open destination./Login failed (530 User userA cannot log in.)">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.52: Could not open destination./Login failed (530 User userA cannot log in.)/java.io.IOException	Invalid destination credential: userA does not exist.		PDF 2 PS	<pre><render-PDF-to-PS> <source ContentType="application/pdf" url="ftp://dsdb1/Source/sourcefile.pdf"/> <destination ContentType="application/postscript" url="ftp://dsdb1/test-only/destinationfile\$ID.ps"> <credentials user="userA" password="password" /> </destination> </render-PDF-to-PS></pre>
S34	Could not open destination./Malformed url D:file:///c:/DS31/Source/pdf2tiff/destinationfile\$ID.ps">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.52: Could not open destination./Malformed url D:file:///c:/DS31/Source/pdf2tiff/destinationfile\$ID.ps	Invalid destination URL: D drive does not exist		PDF 2 PS	<pre><render-PDF-to-PS> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales.pdf"/> <destination ContentType="image/tiff" url="D:file:///c:/DS31/Source/pdf2tiff/destinationfile\$ID.ps"/> </render-PDF-to-PS></pre>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S35	Could not open destination./Login failed (530 User test cannot log in.)>com.insystems.distributor.services.rendering.RenderingServiceException: P2P.52: Could not open destination./Login failed (530 User test cannot log in.)/java.io.IOException	Invalid FTP destination credential: wrong password.		PDF 2 PS	<pre><render-PDF-to-PS> <source ContentType="application/pdf" url="ftp://dsdb1/Source/sourcefile.pdf"/> <destination ContentType="application/postscript" url="ftp://dsdb1/test-only/destinationfile.ps"> <credentials user="test" password="password2" /> </destination> <output-name>HPPS</output-name> <printer-configuration duplex="flipLongEdge"/> </render-PDF-to-PS></pre>
S36	T_PCL_W.tiff2pcl_failed: TIFF to PCL conversion failed(from C:\DS31\Destination\temp\tiff2pcl45428.tiff, to C:\DS31\Destination\temp\tiff2pcl45429.pcl, with settings Printer Config: {copies=1, {PAGE_RANGE=10}})/T_PCL_W.invalid_page_range: Invalid page range (10)" messageKey="T_PCL_W.tiff2pcl_failed">com.insystems.distributor.services.rendering.RenderingServiceException: T_PCL_W.tiff2pcl_failed: TIFF to PCL conversion failed(from C:\DS31\Destination\temp\tiff2pcl45428.tiff, to C:\DS31\Destination\temp\tiff2pcl45429.pcl, with settings Printer Config: {copies=1, {PAGE_RANGE=10}})/T_PCL_W.invalid_page_range: Invalid page range (10)/com.insystems.distributor.services.snowbound.SnowboundException	Invalid page range. Document has only 8 pages.	The pageRange parameter value must have at least page number that falls within the number of pages of the source document. For example, for a document having 10 pages, any of the following is a valid value: 1-, -10, 1,3,5,7,9, 5-10. For for the following value: "1,5,1", pages 1 and 5 will be printed but because there is no page 11, that will be ignored.	TIFF 2 PCL	<pre><render-TIFF-to-PCL> <source ContentType="image/tiff" url="file:///c:/DS31/Source/Sales.tif"/> <destination ContentType="application/vnd.hp-PCL" url="file:///c:/DS31/Destination/curSales.pcl"/> <printer-configuration pageRange="10" /> </render-TIFF-to-PCL></pre>
S37	Failed to open file to copy repository document into it/No object at: file:/c:/DS31/Source/Sales.word">com.insystems.distributor.services.rendering.RenderingServiceException: RU.failed_to_open_file: Failed to open file to copy repository document into it/No object at: file:/c:/DS31/Source/Sales.word/com.insystems.repository.RepositoryException	Source file type (Word) is incorrect.		TIFF 2 PCL	<pre><render-TIFF-to-PCL> <source ContentType="image/tiff" url="file:///c:/DS31/Source/Sales.word"/> <destination ContentType="application/vnd.hp-PCL" url="file:///c:/DS31/Destination/curSales.pcl"/> </render-TIFF-to-PCL></pre>
S38	Copy file to repository failed./vm511a">com.insystems.distributor.services.rendering.RenderingServiceException: RU.CF2R: Copy file to repository failed./vm511a/java.io.IOException	FTP destination path is incorrect.		TIFF 2 PCL	<pre><render-TIFF-to-PCL> <source ContentType="image/tiff" url="file:///c:/DS31/Source/Sales.tif"/> <destination ContentType="application/vnd.hp-PCL" url="ftp://anonymous@vm511a/DS31/Destination/curSales.pcl"/> </render-TIFF-to-PCL></pre>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S39	Failed to open file to copy repository document into it/No object at: file://c:/DS31/Source/nonexist/Sales.tif">com.insystems.distributor.services.rendering.RenderingServiceException: RU.failed_to_open_file: Failed to open file to copy repository document into it/No object at: file://c:/DS31/Source/nonexist/Sales.tif/com.insystems.repository.RepositoryException	Source File URL is incorrect.		TIFF 2 PS	<render-TIFF-to-PS> <source ContentType="image/tiff" url="file:///c:/DS31/Source/nonexist/Sales.tif"/> <destination ContentType="application/vnd.hp-PS" url="file:///c:/DS31/Destination/newSales10.ps"/> </render-TIFF-to-PS>
S40	Copy file to repository failed./The file c:\DS31\Destination\newSales10.ps does not exist">com.insystems.distributor.services.rendering.RenderingServiceException: RU.CF2R: Copy file to repository failed./The file c:\DS31\Destination\newSales10.ps does not exist com.insystems.repository.fileadapter.FileException: The file c:\DS31\Destination\newSales10.ps does not exist/com.insystems.repository.fileadapter.FileException	Destination file has no write permission.	Allow 'write' permissions on file that will be overwritten. Because the file presently has only 'read-only' permissions, the system cannot overwrite the file because it cannot be opened.	TIFF 2 PS	<render-TIFF-to-PS> <source ContentType="image/tiff" url="file:///c:/DS31/Source/Sales.tif"/> <destination ContentType="application/vnd.hp-PS" url="file:///c:/DS31/Destination/newSales10.ps"/> </render-TIFF-to-PS>
S41	Failed to open file to copy repository document into it/Repository object does not exist">com.insystems.distributor.services.rendering.RenderingServiceException: RU.failed_to_open_file: Failed to open file to copy repository document into it/Repository object does not exist/com.insystems.repository.RepositoryException	FTP source folder has no read permission.	Allow read' permissions on the parent folder containing source file. Because the folder presently has no read or write permissions, the system cannot access the file under this folder.	TIFF 2 PS	<render-TIFF-to-PS> <source ContentType="image/tiff" url="ftp://dsdb1/shared2/sourcefile.tif"/> <destination ContentType="application/vnd.hp-PS" url="file:///c:/DS31/Destination/newSales10.ps"/> </render-TIFF-to-PS>
S42	Copy file to repository failed./Malformed url \$ftp://dsdb1/shared/newSales10.ps">com.insystems.distributor.services.rendering.RenderingServiceException: RU.CF2R: Copy file to repository failed./Malformed url \$ftp://dsdb1/shared/newSales10.ps	There are special characters in the FTP destination directory URL.		TIFF 2 PS	<render-TIFF-to-PS> <source ContentType="image/tiff" url="ftp://dsdb1/shared/sourcefile.tif"/> <destination ContentType="application/vnd.hp-PS" url="\$ftp://dsdb1/shared/newSales10.ps"/> </render-TIFF-to-PS>
S43	Word automation: Undocumented error (native code): 11!Could not run macro DSMacro2. (Code=0, Context=37401, Description="Unable to run the specified macro">com.insystems.distributor.services.rendering.RenderingServiceException: NW.native_unknown_key: Word automation: Undocumented error (native code): 11!Could not run macro DSMacro2. (Code=0, Context=37401, Description="Unable to run the specified macro">)	DSMacro2 macro does not exist.		WORD 2 HTML	<render-Word-to-HTML> <source ContentType="application/msword" url="file:///c:/DS31/Source/newSales.doc"/> <destination url="file:///c:/DS31/Destination/newSales.html"/> <macro name="DSMacro2" type="word"/> </render-Word-to-HTML>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S44	Word automation: Undocumented error (native code): 11!Could not run macro ##UpdateToc##;hello;DSMacro2. (Code=0, Context=37401, Description="Unable to run the specified macro")>com.insystems.distributor.services.rendering.RenderingServiceException: NW.native_unknown_key: Word automation: Undocumented error (native code): 11!Could not run macro ##UpdateToc##;test;DSMacro2. (Code=0, Context=37401, Description="Unable to run the specified macro")	The nested macro within word-options (test) does not exist.		WORD 2 HTML	<pre data-bbox="1924 185 2583 532"><render-Word-to-HTML> <source ContentType="application/msword" url="file:///c:/DS31/Source/sourcefile.doc"/> <destination url="file:///c:/DS31/Destination/destinationfile.html"/> <macro name="DSMacro2" type="word"/> <word-options updateToc="true"> <macro name="test" type="word"/> </word-options> </render-Word-to-HTML></pre>
S45	Copy file to repository failed./The file d:\ds31\source\wordTest.pcl does not exist">com.insystems.distributor.services.rendering.RenderingServiceException: RU.CF2R: Copy file to repository failed./The file d:\ds31\source\wordTest.pcl does not exist	Invalid destination URL: D drive does not exist.		WORD 2 PCL	<pre data-bbox="1924 537 2583 708"><render-Word-to-PCL> <source ContentType="application/msword" url="file:///c:/ds31/source/Sales.doc"/> <destination ContentType="application/pdf" url="file:///d:/ds31/source/wordTest.pcl"/> </render-Word-to-PCL></pre>
S46	Copy file to repository failed./Error after STOR new.pcl command (550 new.pcl: Access is denied.)">com.insystems.distributor.services.rendering.RenderingServiceException: RU.CF2R: Copy file to repository failed./Error after STOR new.pcl command (550 new.pcl: Access is denied.)	FTP destination (test-only folder) has no write permission.	Allow 'write' permissions on the parent folder as well as the destination file that will be overwritten. Because the parent folder as well as the file presently have no write permissions, the system cannot overwrite the file because it cannot be opened.	WORD 2 PCL	<pre data-bbox="1924 712 2583 943"><render-Word-to-PCL> <source ContentType="application/msword" url="file:///c:/ds31/source/Sales.doc"/> <destination ContentType="application/postscript" url="ftp://dsdb1/test-only/new.pcl"> <credentials user="test" password="password" /> </destination> </render-Word-to-PCL></pre>
S47	<destination ContentType="application/postscript" url="ftp://dsdb1/test-only/LTC_Rate_Increase_pdf\$ID.ps"> <credentials user="userA" password="password" /> </destination>	Invalid FTP destination credential: userA user does not exist.		WORD 2 PCL	<pre data-bbox="1924 948 2583 1172"><render-Word-to-PCL> <source ContentType="application/msword" url="file:///c:/ds31/source/Sales.doc"/> <destination ContentType="application/postscript" url="ftp://dsdb1/test-only/new.pcl"> <credentials user="userA" password="password" /> </destination> </render-Word-to-PCL></pre>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S48	Flag 'error' is not allowed in PDF Encryption. Allowed flags are Print, PrintLowRes, Accessibility, Assembly, Copy, Fill, ModifyContents, ModifyAnnotations, LowStrength, HighStrength.">com.insystems.distributor.services.encryption.EncryptPdfException: EPS.09: Flag 'error' is not allowed in PDF Encryption. Allowed flags are Print, PrintLowRes, Accessibility, Assembly, Copy, Fill, ModifyContents, ModifyAnnotations, LowStrength, HighStrength.	Encryption-params flags has an invalid value (error).		WORD 2 PDF	<pre data-bbox="1927 185 2583 565"><render-Word-to-PDF> <source ContentType="application/msword" url="file:///c:/DS31/Source/sourcefile.doc"/> <destination url="file:///c:/DS31/Destination/destinationfile.pdf"/> <output-name>Calligo PDF Converter</output-name> <driver-configuration extractLinks="metadata" embedFonts="true"> <encryption-params flags="error" ownerPassword="Text" userPassword="Text"/> </driver-configuration> <macro name="DSMacro" type="word"/> </render-Word-to-PDF></pre>
S49	Flag 'print:copy' is not allowed in PDF Encryption. Allowed flags are Print, PrintLowRes, Accessibility, Assembly, Copy, Fill, ModifyContents, ModifyAnnotations, LowStrength, HighStrength.">com.insystems.distributor.services.encryption.EncryptPdfException: EPS.09: Flag 'print:copy' is not allowed in PDF Encryption. Allowed flags are Print, PrintLowRes, Accessibility, Assembly, Copy, Fill, ModifyContents, ModifyAnnotations, LowStrength, HighStrength.	Encryption-params flag cannot contain a colon separator.		WORD 2 PDF	<pre data-bbox="1927 570 2583 950"><render-Word-to-PDF> <source ContentType="application/msword" url="file:///c:/DS31/Source/sourcefile.doc"/> <destination url="file:///c:/DS31/Destination/destinationfile.pdf"/> <output-name>Calligo PDF Converter</output-name> <driver-configuration extractLinks="metadata" embedFonts="true"> <encryption-params flags="print:copy" ownerPassword="Text" userPassword="Text"/> </driver-configuration> <macro name="DSMacro" type="word"/> </render-Word-to-PDF></pre>
S50	Copy file to repository failed./The file c:\ds31\source\Sales.tiff does not exist">com.insystems.distributor.services.rendering.RenderingServiceException: RU.CF2R: Copy file to repository failed./The file c:\ds31\source\Sales.tiff does not exist	The existing file cannot be overwritten: sales.tiff is read-only under the destination directory.	Allow 'write' permissions on the file that will be overwritten. Because the file presently has only 'read-only' permissions, the system cannot overwrite the file because it cannot be opened.	WORD 2 TIFF	<pre data-bbox="1927 954 2583 1122"><render-Word-to-TIFF> <source ContentType="application/msword" url="file:///c:/ds31/source/Sales.doc"/> <destination ContentType="application/pdf" url="file:///c:/ds31/source/Sales.tiff"/> </render-Word-to-TIFF></pre>
S51	Copy file to repository failed./The file c:\ds31\destination\Sales10.tiff does not exist">com.insystems.distributor.services.rendering.RenderingServiceException: RU.CF2R: Copy file to repository failed./The file c:\ds31\destination\Sales10.tiff does not exist	Destination folder is read-only and set user has no write access.	Ensure correct username/password credentials combination is provided to access the FTP destination, and that the credentials provided have the required permission to access the destination folder and(or) destination document(s) in the request.	WORD 2 TIFF	<pre data-bbox="1927 1127 2583 1344"><render-Word-to-TIFF> <source ContentType="application/msword" url="file:///c:/ds31/source/Sales.doc"/> <destination ContentType="application/pdf" url="file:///c:/ds31/destination/Sales10.tiff"/> <output-name>Black Ice Fax</output-name> <fax-configuration pageRange="2"/> </render-Word-to-TIFF></pre>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S52	Timeout in Service.run(String). ">com.insystems.distributor.ServiceException: FD.03: Timeout in Service.run(String).	Invalid DMS destination path.	Check the dms url provided in the request for syntax, credentials, port number/servername and connection. The syntax for a dms url is: "calligo://user name:password@calligo database name;server name:port number/path"	WORD 2 TIFF	<render-Word-to-TIFF> <source ContentType="application/msword" url="calligo://admin:password@Calligo;dsub1:2099/Source/sourcefile"/> <destination ContentType="image/tiff" url="calligo://admin:password@Calligo;dsub1:2099/Source/newthis.tif"/> </render-Word-to-TIFF>
S53	text="FD.03: Timeout in Service.run(String). ">com.insystems.distributor.ServiceException: FD.03: Timeout in Service.run(String).	File type mismatch: the DMS source file (Sales20) is a pdf file, but this service renders a Word file to tiff.		WORD 2 TIFF	<render-Word-to-TIFF> <source ContentType="application/msword" url="calligo://admin:password@Calligo;dsub1:2099/Source/Sales20"/> <destination ContentType="image/tiff" url="file:///c:/DS31/Destination/newthis.tif"/> <output-name>Black Ice Fax</output-name> </render-Word-to-TIFF>
S54	Unable to open printer (native code): 2!The printer name is invalid./Unable to open printer">com.insystems.distributor.services.rendering.RenderingServiceException: NW.native2: Unable to open printer (native code): 2!The printer name is invalid./Unable to open printer	Wrong printer driver name: HPPS2.		WORD 2 PS	<render-Word-to-PS> <source ContentType="application/msword" url="file:///c:/ds31/source/Sales.doc"/> <destination ContentType="application/pdf" url="file:///c:/ds31/source/Sales.ps"/> <output-name>HPPS2</output-name> </render-Word-to-PS>
S55	PROXY.ERROR.10: Document ModelsFS:''testW97feature.clg' does not exist.">	Incorrect file system path: GenDocsFS=C:/DS31/Source/pdf2tiff should be C:/DS31/Source.	Check filepath for source document. Verify that the source file exists under the directory/sub directory and path provided and has the appropriate read permissions to be opened and rendered.	CLG 2 WORD	<render-CLG-to-Word> <clg-source UISR="GenDocsFS:'testW97feature.clg'"> </clg-source> <destination url="file:///c:/DS31/Destination/clg2word/feature.doc"> </destination> </render-CLG-to-Word>
S56	PROXY.ERROR.10: Document ModelsFS:''test2W97feature.clg' does not exist.">	Wrong source subdirectory path: test2 should be test.	Check filepath for source document. Verify that the source file exists under the directory/sub directory and path provided and has the appropriate read permissions to be opened and rendered.	CLG 2 WORD	<render-CLG-to-Word> <clg-source UISR="GenDocsFS:'test2W97feature.clg'"> </clg-source> <destination url="file:///c:/DS31/Destination/clg2word/feature.doc"> </destination> </render-CLG-to-Word>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S57	JPROXY.TRANS: Failed to transfer content of temporary file (file:///c:/DS31/Destination/clg2word/feature.doc) to the destination ({1}). Please see nested exception/The file c:\DS31\Destination\clg2word\feature.doc does not exist">com.insystems.distributor.services.content.CalligoException: JPROXY.TRANS: Failed to transfer content of temporary file (file:///c:/DS31/Destination/clg2word/feature.doc) to the destination ({1}). Please see nested exception/The file c:\DS31\Destination\clg2word\feature.doc does not exist	Destination file has no write permission.	Allow 'write' permissions on file that will be overwritten. Because the file presently has only 'read-only' permissions, the system cannot overwrite the file as it cannot be opened.	CLG 2 WORD	<pre data-bbox="1927 185 2583 594"><render-CLG-to-Word> <clg-source UISR="GenDocsFS:'testW97feature.clg'"> <credentials user="test" password="password"/> </clg-source> <destination url="file:///c:/DS31/Destination/clg2word/feature.doc"> </destination> </render-CLG-to-Word></pre>
S58	JPROXY.TRANS: Failed to transfer content of temporary file (file:///c:/DS31/Destination/clg2word/feature.doc) to the destination ({1}). Please see nested exception/The file c:\DS31\Destination\clg2word\feature.doc does not exist">com.insystems.distributor.services.content.CalligoException: JPROXY.TRANS: Failed to transfer content of temporary file (file:///c:/DS31/Destination/clg2word/feature.doc) to the destination ({1}). Please see nested exception/The file c:\DS31\Destination\clg2word\feature.doc does not exist	Destination folder has no write permission.	Allow 'write' permissions on the parent folder as well as the destination file that will be overwritten. Because the parent folder as well as the file presently have no write permissions, the system cannot overwrite the file as it cannot be opened.	CLG 2 WORD	<pre data-bbox="1927 599 2583 1003"><render-CLG-to-Word> <clg-source UISR="GenDocsFS:'testW97feature.clg'"> <credentials user="test" password="password"/> </clg-source> <destination url="file:///c:/DS31/Destination/clg2word/feature.doc"> </destination> </render-CLG-to-Word></pre>
S59	JPROXY.TRANS: Failed to transfer content of temporary file (ftp://dsdb1/test-only/feature.doc) to the destination ({1}). Please see nested exception/Login failed (530 User test cannot log in.)">com.insystems.distributor.services.content.CalligoException: JPROXY.TRANS: Failed to transfer content of temporary file (ftp://dsdb1/test-only/feature.doc) to the destination ({1}). Please see nested exception/Login failed (530 User test cannot log in.)/java.io.IOException	Invalid destination credential password		CLG 2 WORD	<pre data-bbox="1927 1008 2583 1289"><render-CLG-to-Word> <clg-source UISR="GenDocsFS:'testW97feature.clg'"> </clg-source> <destination url="ftp://dsdb1/test-only/feature.doc"> <credentials user="test" password="password2" /> </destination> </render-CLG-to-Word></pre>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S60	<p>REX.05: Couldn't open source file (file:///c:/DS31/Source/this/Sales.doc)/No object at: file:///c:/DS31/Source/this/Sales.doc">com.insystems.distributor.services.delivery.repository.RepositoryServiceException: REX.05: Couldn't open source file (file:///c:/DS31/Source/this/Sales.doc)/No object at: file:///c:/DS31/Source/this/Sales.doc/com.insystems.repository.RepositoryException</p>	Incorrect file system source URL.	Check filepath for source document. Verify that the source file exists under the directory/sub directory and path provided and has the appropriate read permissions to be opened and rendered.	Deliver 2 Repository	<pre><deliver-to-repository> <source ContentType="application/msword" url="file:///c:/DS31/Source/this/Sales.doc"/> <destination ContentType="application/msword" url="file:///c:/DS31/Destination/delSales.doc"> </destination> </deliver-to-repository></pre>
S61	<p>REX.05: Couldn't open source file (\$ftp://dsdb2/Sales.doc)/Malformed url \$ftp://dsdb2/Sales.doc">com.insystems.distributor.services.delivery.repository.RepositoryServiceException: REX.05: Couldn't open source file (\$ftp://dsdb2/Sales.doc)/Malformed url \$ftp://dsdb2/Sales.doc</p>	Incorrect FTP source URL .		Deliver 2 Repository	<pre><deliver-to-repository> <source ContentType="application/msword" url="\$ftp://dsdb2/Sales.doc"/> <destination ContentType="application/msword" url="ftp://dsdb1/test-only/anotherSales.ps"> <credentials user="test" password="password" /> </destination> </deliver-to-repository></pre>
S62	<p>REX.06: Couldn't create destination object (ftp://dsdb1/test-only/anotherSales.ps)/The repository object does not point to an existing file or folder">com.insystems.distributor.services.delivery.repository.RepositoryServiceException: REX.06: Couldn't create destination object (ftp://dsdb1/test-only/anotherSales.ps)/The repository object does not point to an existing file or folder/com.insystems.repository.ftpadapter.FtpException</p>	File system destination folder has no write/modify permissions.	Allow 'write' permissions on the parent folder as well as the destination file that will be overwritten. Because the parent folder as well as the file presently have no write permissions, the system cannot overwrite the file as it cannot be opened.	Deliver 2 Repository	<pre><deliver-to-repository> <source ContentType="application/msword" url="file:///c:/DS31/Source/Sales.doc"/> <destination ContentType="application/msword" url="ftp://dsdb1/test-only/anotherSales.ps"> <credentials user="test" password="password" /> </destination> </deliver-to-repository></pre>
S63	<p>REX.06: Couldn't create destination object (ftp://dsdb1/test-only/anotherSales.ps)/Login failed (530 User test2 cannot log in.)">com.insystems.distributor.services.delivery.repository.RepositoryServiceException: REX.06: Couldn't create destination object (ftp://dsdb1/test-only/anotherSales.ps)/Login failed (530 User test2 cannot log in.)/java.io.IOException</p>	Incorrect username for FTP destination folder.		Deliver 2 Repository	<pre><deliver-to-repository> <source ContentType="application/msword" url="file:///c:/DS31/Source/Sales.doc"/> <destination ContentType="application/msword" url="ftp://dsdb1/test-only/anotherSales.ps"> <credentials user="test2" password="password" /> </destination> </deliver-to-repository></pre>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S64	REX.08: Couldn't copy data to destination (calligo://testuser:password@Calligo;dldb1:2099/Destination/sourcefile)/Failed to create version due to: ApiError: ErrorMsg: No permission for this item. Status: Cannot Add Version (code=101603)">com.insystems.distributor.services.delivery.repository.RepositoryServiceException: REX.08: Couldn't copy data to destination (calligo://testuser:password@Calligo;dldb1:2099/Destination/destinationfile)/Failed to create version due to: ApiError: ErrorMsg: No permission for this item. Status: Cannot Add Version (code=101603)/java.io.IOException	DMS destination folder has no permissions.		Deliver 2 Repository	<pre><deliver-to-repository> <source ContentType="application/msword" url="calligo://admin:password@Calligo;dldb1:2099/Source/sourcefile "/> <destination ContentType="application/msword" url="calligo://testuser:password@Calligo;dldb1:2099/Destination/destinationfile"> </destination> </deliver-to-repository></pre>
S65	Sending failed; nested exception is: javax.mail.MessagingException: IOException while sending message; nested exception is: java.io.IOException: com.insystems.repository.RepositoryException: No object at: file://c:/DS31/Source/hello22.tiff">javax.mail.SendFailedException: Sending failed; nested exception is: javax.mail.MessagingException: IOException while sending message; nested exception is: java.io.IOException: com.insystems.repository.RepositoryException: No object	Incorrect attachment source URL.		Deliver 2 Fax	<pre><deliver-to-fax> <fax-number>555-555-1234/pn=John.Smith/o=john.smith@mail.internal.companyname.com </fax-number> <fax-attachment> <source url="file:///c:/DS31/Source/hello22.tiff" ContentType="image/tiff"/> </fax-attachment> <fax-property name="fcsfile" value="fcsccl.pcl"/> <fax-property name="note" value="This should be added as a note."/> <fax-property name="atdate" value="02-10-2005"/> <fax-property name="fromfaxnum" value="555-555-9876"/> </deliver-to-fax></pre>
S66	<errorDetails messageKey="FaxService.error" text="Missing domain">javax.mail.internet.AddressException: Missing domain in string ``fax=555-555-1234/pn=John.Smith/o=john.smith@''	Incorrect email server.		Deliver 2 Fax	<pre><deliver-to-fax> <fax-number>555-555-1234/pn=John.Smith/o=john.smith@</fax-number> <fax-attachment> <source url="file:///c:/DS31/Source/hello.tiff" ContentType="image/tiff"/> </fax-attachment> <fax-property name="fcsfile" value="fcsccl.pcl"/> <fax-property name="note" value="This should be added as a note."/> <fax-property name="atdate" value="02-10-2005"/> <fax-property name="fromfaxnum" value="555-555-9876"/> </deliver-to-fax></pre>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S67	RDS.03: Exception/No object at: file://c:/DS31/Source/new2.txt">com.insystems.distributor.services.delivery.email.EmailServiceException: RDS.03: Exception/No object at: file://c:/DS31/Source/new2.txt/com.insystems.repository.RepositoryException	Invalid body source URL.		Deliver 2 Email	<pre> <deliver-to-email subject="Test Subject" priority="normal" > <body-source> <source url="file:///c:/DS31/Source/new2.txt" ContentType="text/plain"> </source> </body-source> <sender name="1st Submitter" emailAddress="jsmith@mailserve.internal.companyname.com" /> <receiver name="1st Receiver" emailAddress="brogersi@mailserve.internal.companyname.com" type="to" /> <attachment> <source url="file:///c:/DS31/Destination/test2.ps" ContentType="image/tiff" /> </attachment> </deliver-to-email> </pre>
S68	Unable to send e-mail message./Sending failed; nested exception is: javax.mail.SendFailedException: Invalid Addresses; nested exception is: javax.mail.SendFailedException: 550 Relaying is prohibited">com.insystems.distributor.services.delivery.email.EmailServiceException: MessagingException: Unable to send e-mail message./Sending failed; nested exception is: javax.mail.SendFailedException: Invalid Addresses; nested exception is: javax.mail.SendFailedException: 550 Relaying is prohibited	Invalid receiver email address (44@22).		Deliver 2 Email	<pre> <deliver-to-email subject="Test Subject" priority="normal" > <body-source> <source url="file:///c:/DS31/Source/new.txt" ContentType="text/plain"> </source> </body-source> <sender name="1st Submitter" emailAddress="jsmith@mailserve.internal.companyname.com" /> <receiver name="1st Receiver" emailAddress="44@22" type="to" /> <attachment> <source url="file:///c:/DS31/Destination/test2.ps" ContentType="image/tiff" /> </attachment> </deliver-to-email> </pre>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S69	RDS.03: Could not open file file:///c:/DS31/Destination/test222222.ps/No object at: file:/c:/DS31/Destination/test222222.ps">com.insystems.distr istributor.services.delivery.email.EmailServiceException: RDS.03: Could not open file file:///c:/DS31/Destination/test222222.ps/No object at: file:/c:/DS31/Destination/test222222.ps/com.insystems.repos itory.RepositoryException	Invalid source url for attachment.		Deliver 2 Email	<pre> <deliver-to-email subject="Test Subject" priority="normal" > <body-source> <source url="{filesouce}/new.txt" ContentType="text/plain"> </source> </body-source> <sender name="1st Submitter" emailAddress="jsmith@mailserve.internal.companyname.com" /> <receiver name="1st Receiver" emailAddress="jsmith@mailserve.internal.companyname.com" type="to" /> <attachment> <source url="{filedest}/test222222.ps" ContentType="image/tiff" /> </attachment> </deliver-to-email> </pre>
S70	RDS.02: Could not open file ftp://dsdb1/test- only/source\$ID.ps/Login failed (530 User test22 cannot log in.)">com.insystems.distributor.services.delivery.email.Email ServiceException: RDS.02: Could not open file ftp://dsdb1/test-only/sourcef\$ID.ps/Login failed (530 User test22 cannot log in.)/java.io.IOException	Invalid username for attachment.		Deliver 2 Email	<pre> <deliver-to-email subject="Test Subject" priority="normal" > <body-source> <source url="{filesouce}/new.txt" ContentType="text/plain"> </source> </body-source> <sender name="1st Submitter" emailAddress="jsmith@mailserve.internal.companyname.com" /> <receiver name="1st Receiver" emailAddress="jsmith@mailserve.internal.companyname.com" type="to" /> <attachment> <source url="ftp://dsdb1/test-only/source\$ID.ps"> <credentials user="test22" password="password" /> </source> </attachment> </deliver-to-email> </pre>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S71	PEX.UNEXPECTEDERROR: Unexpected Exception thrown from the PrinterServiceAdapter ({1})/No object at: file:/c:/DS31/Source/hello/hello.tiff">com.insystems.distributor.services.delivery.printer.PrinterServiceException: PEX.UNEXPECTEDERROR: Unexpected Exception thrown from the PrinterServiceAdapter ({1})/No object at: file:/c:/DS31/Source/hello/hello.tiff/com.insystems.repository.RepositoryException	Invalid source URL.	Check filepath for source document. Verify that the source file exists under the directory/sub directory and path provided and has the appropriate read permissions to be opened and rendered.	Deliver 2 Printer	<deliver-to-printer> <source ContentType="application/postscript" url="file:///c:/DS31/Source/hello/hello.tiff"/> <output-name>HPPS</output-name> </deliver-to-printer>
S72	PEX.UNEXPECTEDERROR: Unexpected Exception thrown from the PrinterServiceAdapter ({1})/The file {0} does not exist">com.insystems.distributor.services.delivery.printer.PrinterServiceException: PEX.UNEXPECTEDERROR: Unexpected Exception thrown from the PrinterServiceAdapter ({1})/The file {0} does not exist	No permission to read source URL.	Allow read' permissions on source file. Because the file presently has no read or write permissions, the system cannot access the file or open it to read the contents.	Deliver 2 Printer	<deliver-to-printer> <source ContentType="application/postscript" url="file:///c:/DS31/Source/hello.tiff"/> <output-name>HPPS</output-name> </deliver-to-printer>
S73	Error message popped up: There was an error found when printing the document "hello.tiff" to LPT1: the device is not connected. After you cancel the error message, here is the response: PEX.WRITE_PRINTER_ERROR: Spooling.spool error document writing ({1})">com.insystems.distributor.services.delivery.printer.PrinterServiceException: PEX.WRITE_PRINTER_ERROR: Spooling.spool error document writing ({1})	Calligo PDF Converter was used instead of a printer driver.	Check the printer driver being used in the delivery service. The printer specified in the 'output-name' parameter must have the correct printer drivers and support printing the document file type being sent to the printer. For example, a PCL printer specified for postscript file will fail to print the document correctly.	Deliver 2 Printer	<deliver-to-printer> <source ContentType="application/postscript" url="file:///c:/DS31/Source/hello.tiff"/> <output-name>Calligo PDF Converter</output-name> </deliver-to-printer>
S74	PEX.INVALID_PRINTER: Failed: Provided printer server name is not valid for current workstation ({1})">com.insystems.distributor.services.delivery.printer.PrinterServiceException: PEX.INVALID_PRINTER: Failed: Provided printer server name is not valid for current workstation ({1})	Invalid printer driver name.		Deliver 2 Printer	<deliver-to-printer> <source ContentType="application/postscript" url="file:///c:/DS31/Source/hello.tiff"/> <output-name>HPPS2</output-name> </deliver-to-printer>
S75	PCL.09: Couldn't open source file (file:/c:/DS31/Source/Sales2222.pcl)/No object at: file:/c:/DS31/Source/Sales2222.pcl">com.insystems.distributor.pcl.PCLException: PCL.09: Couldn't open source file (file:/c:/DS31/Source/Sales2222.pcl)/No object at: file:/c:/DS31/Source/Sales2222.pcl/com.insystems.repository.RepositoryException	First source file was not found.		Concatenate-pcl (streams)	<concatenate-pcl-files numberPCLsegments="2"> <pcl-source url="file:///c:/DS31/Source/Sales2222.pcl"/> <pcl-source url="file:///c:/DS31/Source/test2.pcl"/> <pcl-destination url="file:///c:/DS31/Destination/PCLConcatenate/ConcatenatedPCL.pcl"/> </concatenate-pcl-files>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S76	PCL.09: Couldn't open source file (file:/c:/DS31/Source/test22.pcl)/No object at: file:/c:/DS31/Source/test22.pcl">com.insystems.distributor.pcl.PCLException: PCL.09: Couldn't open source file (file:/c:/DS31/Source/test22.pcl)/No object at: file:/c:/DS31/Source/test22.pcl/com.insystems.repository.RepositoryException	Second source file was not found		Concatenate-pcl (streams)	<concatenate-pcl-files numberPCLsegments="2"> <pcl-source url="file:///c:/DS31/Source/Sales.pcl"/> <pcl-source url="file:///c:/DS31/Source/test22.pcl"/> <pcl-destination url="file:///c:/DS31/Destination/PCLConcatenate/ConcatenatedPCL.pcl"/> </concatenate-pcl-files>
S77	PCL.12: Invalid attribute "numberPCLsegments" specified in the request (0).>com.insystems.distributor.pcl.PCLException: PCL.12: Invalid attribute "numberPCLsegments" specified in the request (0).	Number of PCL segments is invalid: numberPCLsegments=0.		Concatenate-pcl (streams)	<concatenate-pcl-files numberPCLsegments="0"> <pcl-source url="file:///c:/DS31/Source/Sales.pcl"/> <pcl-source url="file:///c:/DS31/Source/test2.pcl"/> <pcl-destination url="file:///c:/DS31/Destination/PCLConcatenate/ConcatenatedPCL.pcl"/> </concatenate-pcl-files>
S78	PCL.07: Number of PCL segments specified in the request does not match with number of PCLsegmentIDs (1 <> 2).>com.insystems.distributor.pcl.PCLException: PCL.07: Number of PCL segments specified in the request does not match with number of PCLsegmentIDs (1 <> 2).	All the source files have the same PCLSegmentID, but the number of segments equal 2.		Concatenate-pcl (streams)	<concatenate-pcl-files numberPCLsegments="2"> <pcl-source url="file:///c:/DS31/Source/Sales.pcl" PCLsegmentID="8" /> <pcl-source url="file:///c:/DS31/Source/test2.pcl" PCLsegmentID="8" /> <pcl-destination url="file:///c:/DS31/Destination/PCLConcatenate/ConcatenatedPCL.pcl"/> </concatenate-pcl-files>
S79	PCL.07: Number of PCL segments specified in the request does not match with number of PCLsegmentIDs (2 <> 1).>com.insystems.distributor.pcl.PCLException: PCL.07: Number of PCL segments specified in the request does not match with number of PCLsegmentIDs (2 <> 1).	PCLSegmentID is greater than the number of segments.		Concatenate-pcl (streams)	<concatenate-pcl-files numberPCLsegments="1"> <pcl-source url="file:///c:/DS31/Source/Sales.pcl" PCLsegmentID="8" /> <pcl-source url="file:///c:/DS31/Source/test2.pcl" PCLsegmentID="10" /> <pcl-destination url="file:///c:/DS31/Destination/PCLConcatenate/ConcatenatedPCL.pcl"/> </concatenate-pcl-files>
S80	PCL.04: Exception in PCLConcatenation Service./The file c:\DS31\Destination\PCLConcatenate\ConcatenatedPCL.pcl 1.prn does not exist">com.insystems.distributor.pcl.PCLException: PCL.04: Exception in PCLConcatenation Service./The file c:\DS31\Destination\PCLConcatenate\ConcatenatedPCL.pcl 1.prn does not exist	The destination URL has no write permission.	Allow 'write' permissions on file that will be overwritten. Because the file presently has only 'read-only' permissions, the system cannot overwrite the file as it cannot be opened.	Concatenate-pcl (streams)	<concatenate-pcl-files numberPCLsegments="2"> <pcl-source url="file:///c:/DS31/Source/Sales.pcl" PCLsegmentID="8" /> <pcl-source url="file:///c:/DS31/Source/test2.pcl" PCLsegmentID="10" /> <pcl-destination url="file:///c:/DS31/Destination/PCLConcatenate/ConcatenatedPCL.pcl"/> </concatenate-pcl-files>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S81	PCL.10: Number of PCL segments specified in the request is greater than number of source files (4 > 2). com.insystems.distributor.pcl.PCLException: PCL.10: Number of PCL segments specified in the request is greater than number of source files (4 > 2).	Number of segments is greater than the number of source files.		Concatenate-pcl (streams)	<concatenate-pcl-files numberPCLsegments="4"> <pcl-source url="file:///c:/DS31/Source/Sales.pcl"/> <pcl-source url="file:///c:/DS31/Source/test2.pcl"/> <pcl-destination url="file:///c:/DS31/Destination/PCLConcatenate/ConcatenatedPCL.pcl"/> </concatenate-pcl-files>
S82	PSS.04: Invalid PostScript file (file:///c:/DS31/Source/Sales.pcl). No pages found. com.insystems.distributor.concatenate.ps.PSException: PSS.04: Invalid PostScript file (file:///c:/DS31/Source/Sales.pcl). No pages found.	You cannot concatenate pcl files within a concatenate-ps-files request.		Concatenate-PS (streams)	<concatenate-ps-files numberPSsegments="1"> <ps-source url="file:///c:/DS31/Source/Sales.pcl"/> <ps-source url="file:///c:/DS31/Source/test2.pcl"/> <destination url="file:///c:/DS31/Destination/PSConcatenate/ConcatenatedPS.ps"/> </concatenate-ps-files>
S83	PSS.04: Invalid PostScript file (file:///c:/DS31/Source/sourcefile.doc). No pages found. com.insystems.distributor.concatenate.ps.PSException: PSS.04: Invalid PostScript file (file:///c:/DS31/Source/sourcefile.doc). No pages found.	You cannot concatenate a Word file within a concatenate-ps-files request.		Concatenate-PS (streams)	<concatenate-ps-files numberPSsegments="1"> <ps-source url="file:///c:/DS31/Source/Sales.ps"/> <ps-source url="file:///c:/DS31/Source/sourcefile.doc"/> <destination url="file:///c:/DS31/Destination/PSConcatenate/ConcatenatedPS.ps"/> </concatenate-ps-files>
S84	PSS.04: Invalid PostScript file (file:///c:/DS31/Source/test2.ps). No pages found. com.insystems.distributor.concatenate.ps.PSException: PSS.04: Invalid PostScript file (file:///c:/DS31/Source/test2.ps). No pages found.	Source file (test2.ps) is corrupt.		Concatenate-PS (streams)	<concatenate-ps-files numberPSsegments="1"> <ps-source url="file:///c:/DS31/Source/Sales.ps"/> <ps-source url="file:///c:/DS31/Source/test2.ps"/> <destination url="file:///c:/DS31/Destination/PSConcatenate/ConcatenatedPS.ps"/> </concatenate-ps-files>
S85	<errorDetails text="PSS.04: Invalid PostScript file (calligo://admin:password@Calligo;dsdb1:2099/Source/sourcefile). No pages found." messageKey="PSS.04">com.insystems.distributor.concatenate.ps.PSException: PSS.04: Invalid PostScript file (calligo://admin:password@Calligo;dsdb1:2099/Source/sourcefile). No pages found.	One of the files you are trying to concatenate is a Word file. You can only concatenate PS files using this service.		Concatenate-PS (streams)	<concatenate-ps-files numberPSsegments="2"> <ps-source url="calligo://admin:password@Calligo;dsdb1:2099/Source/ps" /> <ps-source url="calligo://admin:password@Calligo;dsdb1:2099/Source/ps2"/> <ps-source url="calligo://admin:password@Calligo;dsdb1:2099/Source/ps4.ps"/> <ps-source url="calligo://admin:password@Calligo;dsdb1:2099/Source/sourcefile" /> <destination url="{filedest}/PSConcatenate/ConcatenatedPS\$ID.ps"/> </concatenate-ps-files>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S86	EPS.07: Could not open destination./The url c:\DS31\Destination\encrypt points to a folder">com.insystems.distributor.services.encryptedPdfException: EPS.07: Could not open destination./The url c:\DS31\Destination\encrypt points to a folder/com.insystems.repository.fileadapter.FileException	No destination file name specified.		Encrypt-pdf	<pre><encrypt-pdf> <source url="file:///c:/DS31/Source/Sales2.pdf" ContentType="application/pdf" deleteAfterExecution="none"/> <destination url="file:///c:/DS31/Destination/encrypt/" ContentType="application/pdf" copyMetadata="false"/> <encryption-params userPassword="password" ownerPassword="password"/> </encrypt-pdf></pre>
S87	EPS.09: Flag 'printcopy' is not allowed in PDF Encryption. Allowed flags are Print, PrintLowRes, Accessibility, Assembly, Copy, Fill, ModifyContents, ModifyAnnotations, LowStrength, HighStrength.">com.insystems.distributor.services.encryptedPdfException: EPS.09: Flag 'printcopy' is not allowed in PDF Encryption. Allowed flags are Print, PrintLowRes, Accessibility, Assembly, Copy, Fill, ModifyContents, ModifyAnnotations, LowStrength, HighStrength.	Incorrect value for the flag: printcopy.		Encrypt-pdf	<pre><encrypt-pdf> <source url="file:///c:/DS31/Source/Sales2.pdf" ContentType="application/pdf" deleteAfterExecution="none"/> <destination url="file:///c:/DS31/Destination/encrypt/Sales2" ContentType="application/pdf" copyMetadata="false"/> <encryption-params flags="printcopy" userPassword="password" ownerPassword="password"/> </encrypt-pdf></pre>
S88	EPS.09: Flag 'copy.fill' is not allowed in PDF Encryption. Allowed flags are Print, PrintLowRes, Accessibility, Assembly, Copy, Fill, ModifyContents, ModifyAnnotations, LowStrength, HighStrength.">com.insystems.distributor.services.encryptedPdfException: EPS.09: Flag 'copy.fill' is not allowed in PDF Encryption. Allowed flags are Print, PrintLowRes, Accessibility, Assembly, Copy, Fill, ModifyContents, ModifyAnnotations, LowStrength, HighStrength.	Period (.) incorrectly used as a flag value separator.		Encrypt-pdf	<pre><encrypt-pdf> <source url="file:///c:/DS31/Source/Sales2.pdf" ContentType="application/pdf" deleteAfterExecution="none"/> <destination url="file:///c:/DS31/Destination/encrypt/Sales2" ContentType="application/pdf" copyMetadata="false"/> <encryption-params flags="print,copy.fill" userPassword="password" ownerPassword="password"/> </encrypt-pdf></pre>
S89	CSR.03" text="file:///c:/DS31/Destination/deletefiles2: CSR.03: Couldn't delete specified folder due to repository exception/No object at: file:/c:/DS31/Destination/deletefiles2">com.insystems.distributor.services.cleanup.CleanupServiceException: CSR.03: Couldn't delete specified folder due to repository exception/No object at: file:/c:/DS31/Destination/deletefiles2/com.insystems.repository.RepositoryException	Source folder does not exist.		Delete-files	<pre><delete-file> <folder-source> <source url="file:///c:/DS31/Destination/deletefiles2"/> <filter value=""/> </folder-source> </delete-file></pre>
S90	CSR.03" text="file:///c:/DS31/Destination/deletefiles: CSR.03: Couldn't delete specified folder due to repository exception">com.insystems.distributor.services.cleanup.CleanupServiceException: CSR.03: Couldn't delete specified folder due to repository exception/java.lang.NullPointerException	Source folder has no permissions.	Allow 'read' permissions on the parent folder containing source file. Because the folder presently has no read or write permissions, the system cannot access the file under this folder.	Delete-files	<pre><delete-file> <folder-source> <source url="file:///c:/DS31/Destination/deletefiles"/> <filter value=""/> </folder-source> </delete-file></pre>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S91	CSR.01" text="file:///c:/DS31/Destination/deletefiles/test10.ps: CSR.01: Couldn't delete specified file due to repository exception/No object at: file:/c:/DS31/Destination/deletefiles/test10.ps">com.insystems.distributor.services.cleanup.CleanupServiceException: CSR.01: Couldn't delete specified file due to repository exception/No object at: file:/c:/DS31/Destination/deletefiles/test10.ps/com.insystems.repository.RepositoryException	Source file does not exist.		Delete-files	<delete-file> <folder-source> <source url="file:///c:/DS31/Destination/deletefiles"/> <filter value=""/> </folder-source> <source url="file:///c:/DS31/Destination/deletefiles/test10.ps"/> </delete-file>
S92	Check that history is not updated if changes are aborted	Source file has no permission.		Delete-files	Verify no changes are saved in history of the version if changes are aborted
S93	text="ftp://dsdb1/wrong/test-only/anotherSales2.ps: CSR.01: Couldn't delete specified file due to repository exception/Repository object does not exist">com.insystems.distributor.services.cleanup.CleanupServiceException: CSR.01: Couldn't delete specified file due to repository exception/Repository object does not exist/com.insystems.repository.RepositoryException	FTP source file under the folder has no permissions.	Allow 'read' permissions on source file. Because the file presently has no read or write permissions, the system cannot access the file or open it to read the contents.	Delete-files	<delete-file> <folder-source> <source url="file:///c:/DS31/Destination/deletefiles"/> <filter value=""/> </folder-source> <source url="ftp://dsdb1/wrong/test-only/anotherSales2.ps"/> </delete-file>
S94	file:/c:/DS31/Destination/deletefiles/newSales2_files/: CSR.02: Couldn't delete file in specified folder due to repository exception/Could not delete c:\DS31\Destination\deletefiles\newSales2_files">com.insystems.distributor.services.cleanup.CleanupServiceException: CSR.02: Couldn't delete file in specified folder due to repository exception/Could not delete c:\DS31\Destination\deletefiles\newSales2_files/com.insystems.repository.fileadapter.FileException	You cannot delete subfolders: subfolder newSales2_files is within the deletefiles folder..		Delete-files	<delete-file> <folder-source> <source url="file:///c:/DS31/Destination/deletefiles"/> <filter value=""/> </folder-source> </delete-file>
S95	PROXY.ERROR.10: Document ModelsFS:'\sourceTest2.CMS does not exist.">	Calligo-source is invalid and points to a non-existent file.		Generate-Calligo-Document	<generate-calligo-document> <calligo-source UISR="ModelsFS:'\sourceTest2.CMS" docType="cms"/> <destination url="{filesource}\test\sample.doc" /> <calligo-destination UISR="GenDocsFS:'newGen.CLG"/> <key-data name="infosource_location" value="C:\DS31\Source\test\samplexml2.xml" type="string" /> <generation-data name="infosource_location22"> <source url="file:///C:\DS31\Source\test\samplexml2.xml" /> </generation-data> </generate-calligo-document>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S96	<p>PROXY.ERROR.21: Could not add ModelsFS:'&apos;newGen.CLG&apos;' to repository (21!!InsRepFileAccess.Add() failed (80040612).).> com.insystems.distributor.services.content.CalligoException: PROXY.ERROR.21: Could not add ModelsFS:'&apos;newGen.CLG&apos;';</p>	<p>Calligo destination file is open.</p>		<p>Generate-Calligo-Document</p>	<pre><generate-calligo-document> <calligo-source UISR="ModelsFS:'test\SampleTest.CMS" docType="cms"/> <destination url="{filesource}\test\sample.doc" /> <calligo-destination UISR="GenDocsFS:'newGen.CLG"/> <key-data name="infosource_location2" value="C:\DS31\Source\test\samplxml2.xml" type="string" /> <generation-data name="infosource_location"> <source url="file:///C:\DS31\Source\test\samplxml2.xml" /> </generation-data> </generate-calligo-document></pre>
S97	<p>PROXY.ERROR.19: 19!!InsGenerateDocument.Generate() failed (4677:0x1245).. Check generation log for more details.">Start Section generate: ModelsFS:test\SampleTest.CMS Assembly Engine (Reference Context): Not all Key Data are known. Assembly Engine (Reference Context): Cannot evaluate reference: infosource_location Assembly Engine (Reference Context): Wrong type of parameter(s) in function call: plus Assembly Engine (Reference Context): QUERY Error: DataStream:539 - Assembly Engine: XMLIS was unable to process the *** UNEVALUATED EXPRESSION: &lt;&quot;FILE=&quot; + INFOSOURCE_LOCATION&gt; *** rule Section generate completed.</p>	<p>Key-data name does not match the one in the CMS.</p>		<p>Generate-Calligo-Document</p>	<pre><generate-calligo-document> <calligo-source UISR="ModelsFS:'test\SampleTest.CMS" docType="cms"/> <destination url="{filesource}\test\sample.doc" /> <calligo-destination UISR="GenDocsFS:'newGen.CLG"/> <key-data name="infosource_location2" value="C:\DS31\Source\test\samplxml2.xml" type="string" /> <generation-data name="infosource_location2"> <source url="file:///C:\DS31\Source\test\samplxml2.xml" /> </generation-data> </generate-calligo-document></pre>
S98	<p>PROXY.ERROR.19: 19!!InsGenerateDocument.Generate() failed (4677:0x1245).. Check generation log for more details.">Start Section generate: ModelsFS:test\SampleTest.CMS Assembly Engine (Reference Context): QUERY Error: DataStream:1527 - Assembly Engine: XMLIS was unable to find c:\ds31\source\test\samplxml20.xml. The infosource cannot process the QUERY &quot;FILE=C:\DS31\SOURCE\TEST\SAMPLEXML2.XML; UID=;PWD=&quot; rule(s). Section generate completed.</p>	<p>The XML file location in the key-data value is incorrect.</p>		<p>Generate-Calligo-Document</p>	<pre><generate-calligo-document> <calligo-source UISR="ModelsFS:'test\SampleTest.CMS" docType="cms"/> <destination url="{filesource}\test\sample.doc" /> <calligo-destination UISR="GenDocsFS:'newGen.CLG"/> <key-data name="infosource_location" value="C:\DS31\Source\test\samplxml20.xml" type="string" /> <generation-data name="infosource_location2"> <source url="file:///C:\DS31\Source\test\samplxml2.xml" /> </generation-data> </generate-calligo-document></pre>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S99	<p>PROXY.ERROR.19: 19!InsGenerateDocument.Generate() failed (-2147467259:0x80004005).. Check generation log for more details.">Start Section generate: ModelsFS:test\SampleTest.CMS Start compile Section. Assembly Engine (Compile Section): Unknown rule - cannot compile Section: BREAKK Assembly Engine (Compile Section): Keyword NEXT is expected to follow QUERY rule. Assembly Engine (Compile Section): Unexpected rule at the end of Section: Section compile completed.</p>	<p>Assembling errors occurred in the CMS document.</p>		<p>Generate-Calligo-Document</p>	<pre><generate-calligo-document> <calligo-source UISR="ModelsFS:'test\SampleTest.CMS" docType="cms"/> <destination url="{filesouce}\test\sample.doc" /> <calligo-destination UISR="GenDocsFS:'newGen.CLG"/> <key-data name="infosource_location22" value="C:\DS31\Source\test\samplxml2.xml" type="string" /> <generation-data name="infosource_location"> <source url="file:///C:\DS31\Source\test\samplxml2.xml" /> </generation-data> </generate-calligo-document></pre>
S100	<p>PROXY.ERROR.19: 19!InsGenerateDocument.Generate() failed (4677:0x1245).. Check generation log for more details.">Start Section generate: ModelsFS:test\SampleTest.CMS Assembly Engine (Reference Context): QUERY Error: DataStream:1722 - Assembly Engine: XMLIS was unable to process the FILE=C:\TEMP\GENDATA9964.XML;UID=;PWD= rule Section generate completed.</p>	<p>Errors in the requiried XML file.</p>		<p>Generate-Calligo-Document</p>	<pre><generate-calligo-document> <calligo-source UISR="ModelsFS:'test\SampleTest.CMS" docType="cms"/> <destination url="{filesouce}\test\sample.doc" /> <calligo-destination UISR="GenDocsFS:'newGen.CLG"/> <key-data name="infosource_location22" value="C:\DS31\Source\test\samplxml2.xml" type="string" /> <generation-data name="infosource_location"> <source url="file:///C:\DS31\Source\test\samplxml2.xml" /> </generation-data> </generate-calligo-document></pre>
S101	<p>KD.INVALID_DATE: Invalid date value found in the class setting">com.insystems.distributor.services.content.CalligoException: KD.INVALID_DATE: Invalid date value found in the class setting</p>	<p>Valid key-data type, but its incorrect type is associated with the value.</p>		<p>Generate-Calligo-Document</p>	<pre><generate-calligo-document> <calligo-source UISR="ModelsFS:'test\SampleTest.CMS" docType="cms"/> <destination url="{filesouce}\test\sample.doc" /> <calligo-destination UISR="GenDocsFS:'newGen.CLG"/> <key-data name="infosource_location" value="C:\DS31\Source\test\samplxml2.xml" type="date" /> <generation-data name="infosource_location22"> <source url="file:///C:\DS31\Source\test\samplxml2.xml" /> </generation-data> </generate-calligo-document></pre>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S102	<p>PROXY.ERROR.19: 19!InsGenerateDocument.Generate() failed (4677:0x1245).. Check generation log for more details.">Start Section generate: ModelsFS:test\SampleTest.CMS Assembly Engine (Reference Context): Not all Key Data are known. Assembly Engine (Reference Context): Cannot evaluate reference: infosource_location Assembly Engine (Reference Context): Wrong type of parameter(s) in function call: plus Assembly Engine (Reference Context): QUERY Error: DataStream:539 - Assembly Engine: XMLIS was unable to process the *** UNEVALUATED EXPRESSION: &lt;&quot;FILE=&quot; + INFOSOURCE_LOCATION&gt; *** rule Section generate completed.</p>	<p>Generation-data name does not match the one in the CMS.</p>		<p>Generate-Calligo-Document</p>	<pre><generate-calligo-document> <calligo-source UISR="ModelsFS:'test\SampleTest.CMS" docType="cms"/> <destination url="{filesouce}\test\sample.doc" /> <calligo-destination UISR="GenDocsFS:'newGen.CLG'"/> <key-data name="infosource_location22" value="C:\DS31\Source\test\samplxml2.xml" type="string" /> <generation-data name="infosource_location2"> <source url="file:///C:\DS31\Source\test\samplxml2.xml" /> </generation-data> </generate-calligo-document></pre>
S103	<p>PROXY.ERROR.19: 19!InsGenerateDocument.Generate() failed (4677:0x1245).. Check generation log for more details.">Start Section generate: ModelsFS:test\SampleTest.CMS Assembly Engine (Reference Context): QUERY Error: DataStream:1722 - Assembly Engine: XMLIS was unable to process the FILE=C:\TEMP\GENDATA9982.XML;UID=;PWD= rule Section generate completed.</p>	<p>Incorrect XML code under the job-data tag: "bad data".</p>		<p>Generate-Calligo-Document</p>	<pre><generate-calligo-document> <calligo-source UISR="ModelsFS:'test\SampleTest.CMS" docType="cms"/> <destination url="{filesouce}\test\sample.doc" /> <calligo-destination UISR="GenDocsFS:'newGen.CLG'"/> <key-data name="infosource_location22" value="C:\DS31\Source\test\samplxml2.xml" type="string" /> <generation-data name="infosource_location"> <!-- source url="file:///C:\DS31\Source\test\samplxml2.xml" / --> <job-data> bad data </job-data> </generation-data> </generate-calligo-document></pre>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S104	PROXY.ERROR.19: 19!InsGenerateDocument.Generate() failed (4615:0x1207).. Check generation log for more details.">Start Section generate: ModelsFS:test\SampleTest.CMS	The embedded XML code for the plain-data tag does not have the information required by the CMS document.		Generate-Calligo-Document	<pre> <generate-calligo-document> <calligo-source UISR="ModelsFS:'test\SampleTest.CMS" docType="cms"/> <destination url="file:///c:/DS31/Source/test/sample.doc" /> <calligo-destination UISR="GenDocsFS:'newGen.CLG'"/> <key-data name="infosource_location22" value="C:\DS31\Source\test\samplxml2.xml" type="string" /> <generation-data name="infosource_location"> <!-- source url="file:///C:\DS31\Source\test\samplxml2.xml" / --> <plain-data> <interactive> <CustomerData> <insured2 type="array"> <row type="string">Full Time Employees (2)</row> </insured2> <eff_date type="array"> <row type="date">11/11/1999</row> </eff_date> </CustomerData> </interactive> </plain-data> </generation-data> </generate-calligo-document> </pre>

ID	Error message returned	Cause	Possible Solution	Service	Sample Code
S105	PROXY.ERROR.19: 19!InsGenerateDocument.Generate() failed (4674:0x1242).. Check generation log for more details.">Assembly Engine (Section): Cannot load document. 0x80004005 ("C:\Program Files\Insystems Corporation\Calligo\temp\FSGA57.tmp")	Incorrect clg source document: a Word doc was used instead of clg doc.		Generate-Calligo-Document	<pre> <generate-calligo-document> <calligo-source UISR="ModelsFS:'test\sample.doc" docType="clg"/> <destination url="{filesouce}\test\sample.doc" /> <calligo-destination UISR="GenDocsFS:'newGen.CLG"/> <key-data name="infosource_location22" value="C:\DS31\Source\test\samplxml2.xml" type="string" /> <generation-data name="infosource_location"> <!-- source url="file:///C:\DS31\Source\test\samplxml2.xml" / --> <plain-data> <interactive> <CustomerData> <insured type="array"> <row type="string">Full Time Employees (2)</row> </insured> <eff_date type="array"> <row type="date">11/11/1999</row> </eff_date> </CustomerData> </interactive> </plain-data> </generation-data> </generate-calligo-document> </pre>

ID	Error message returned	Cause	Scenario
A1	DM.fromXml: Invalid request data (com.insystems.distributor.services.content.CalligoService@47ab39).Element "request" allows no further input; "render-Word-to-PDF" is not allowed." messageKey="BS.01">com.insystems.distributor.ServiceException: DM.fromXml: Invalid request data (com.insystems.distributor.services.content.CalligoService@47ab39).Element "request" allows no further input; "render-Word-to-PDF" is not allowed./org.xml.sax.SAXParseException	You cannot have two simple requests under one request XML tag.	<pre> ...<dependent-aggregate type="word2Pdf-service"> <request> <render-Word-to-PDF> <source ContentType="application/msword" url="{filedest}/test/sample.doc"/> <destination ContentType="application/pdf" url="{filedest}/test/sample.pdf"/> <output-name>Calligo PDF Converter</output-name> </render-Word-to-PDF> <render-Word-to-PDF> <source ContentType="application/msword" url="{filedest}/test/sample.doc"/> <destination ContentType="application/pdf" url="{filedest}/test/sample.pdf"/> <output-name>Calligo PDF Converter</output-name> </render-Word-to-PDF> </request>..... </pre>
A2	Hanging	Invalid type for dependent aggregate request: pdf-to-zip.	<pre> ...<dependent-aggregate type="render-PDF-to-ZIP"> <request> <render-PDF-to-PCL> <source ContentType="application/pdf" url="{filedest}/test/sample.pdf"/> <destination ContentType="application/vnd.hp-PCL" url="{filedest}/test/sample.pcl"/> <output-name>HPLJIII</output-name> <printer-configuration collate="OFF" copies="2" duplex="flipLongEdge" pageRange=""> </render-PDF-to-PCL> </request>.... </pre>
A3	REX.05: Couldn't open source file (file:///c:/DS31/Source/Sales2.doc)/No object at: file:/c:/DS31/Source/Sales2.doc" messageKey="REX.05">com.insystems.distributor.services.delivery.repository.Repository ServiceException: REX.05: Couldn't open source file (file:///c:/DS31/Source/Sales2.doc)/No object at: file:/c:/DS31/Source/Sales2.doc/com.insystems.repository.RepositoryException	Error occurred on root request: deliver-to-repository - source not found.	<pre> ...<request> <deliver-to-repository> <source ContentType="application/msword" url="file:///c:/DS31/Source/Sales2.doc"/> <destination ContentType="application/msword" url="file:///c:/DS31/Destination/dd.doc"> </destination> </deliver-to-repository> </request>.... </pre>
A4	NW.native2: Unable to open printer (native code): 2!The printer name is invalid./Unable to open printer" messageKey="NW.native2">com.insystems.distributor.services.rendering.RenderingServi ceException: NW.native2: Unable to open printer (native code): 2!The printer name is invalid./Unable to open printer	Error occurred on second level request: render-word-to-PDF - incorrect convert printer name.	<pre> ...<dependent-aggregate type="word2Pdf-service"> <request> <render-Word-to-PDF> <source ContentType="application/msword" url="{filedest}/test/sample.doc"/> <destination ContentType="application/pdf" url="{filedest}/test/sample.pdf"/> <output-name>Calligo PDF Converter2</output-name> </render-Word-to-PDF> </request> </pre>

ID	Error message returned	Cause	Scenario
A5	<p>P2P.61: Unable to process request, please check page range entered."</p> <p>messageKey="P2P.61">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.61: Unable to process request, please check page range entered.</p>	<p>Error occured on third level request: render-PDF-to-PCL - incorrect page range.</p>	<pre> ...<dependent-aggregate type="word2Pdf-service"> <request> <render-Word-to-PDF> <source ContentType="application/msword" url="{filedest}/test/sample.doc"/> <destination ContentType="application/pdf" url="{filedest}/test/sample.pdf"/> <output-name>Calligo PDF Converter</output-name> </render-Word-to-PDF> </request> </dependent-aggregate type="render-PDF-to-PCL"> <request> <render-PDF-to-PCL> <source ContentType="application/pdf" url="{filedest}/test/sample.pdf"/> <destination ContentType="application/vnd.hp-PCL" url="{filedest}/test/sample.pcl"/> <output-name>HPLJIII</output-name> <printer-configuration collate="OFF" copies="2" duplex="flipLongEdge" pageRange="200-2"/> </render-PDF-to-PCL> </request>.... </pre>
A6	<p>DM.fromXml: Invalid request data (com.insystems.distributor.services.delivery.repository.RepositoryService@871f8)/Element &quot;service-queue&quot; does not allow &quot;queue&quot; here." messageKey="BS.01">com.insystems.distributor.ServiceException: DM.fromXml: Invalid request data (com.insystems.distributor.services.delivery.repository.RepositoryService@871f8)/Element &quot;service-queue&quot; does not allow &quot;queue&quot; here./org.xml.sax.SAXParseException</p>	<p>Service queue missing queue-connection-factory-tag for the last dependency request: deliver-to printer.</p>	<pre> <dependent-aggregate type="deliver-to-printer"> <request> <deliver-to-printer> <source ContentType="application/vnd.hp-PCL" url="{filedest}/test/sample.pcl"/> <output-name>HPLJIII</output-name> </deliver-to-printer> </request> <service-queue> <queue name="service" type="Name"/> </service-queue> </pre>

ID	Error message returned	Cause	Scenario
A7	Hanging	Invalid reply-to-queue for delivery-to-printer: queue name="nothing". This queue does not exist.	<pre> <dependent-aggregate type="deliver-to-printer"> <request> <deliver-to-printer> <source ContentType="application/vnd.hp-PCL" url="{filedest}/test/sample.pcl"/> <output-name>HPLJIII</output-name> </deliver-to-printer> </request> <service-queue> <queue-connection-factory> <queue-factory-context-name contextName="JmsQueueConnectionFactory2"/> </queue-connection-factory> <queue name="service" type="Name"/> </service-queue> <reply-to-queue> <queue-connection-factory> <queue-factory-context-name contextName="JmsQueueConnectionFactory2"/> </queue-connection-factory> <queue name="nothing" type="Name"/> </reply-to-queue> </pre>
A8	FD.04: Unexpected exception in Service." messageKey="FD.04">com.insystems.distributor.ServiceException: FD.04: Unexpected exception in Service./java.lang.ClassCastException	Aggregate request type is delivery-to-email, but render-PDF-to-PS occurred within this request.	<pre><dependent-aggregate type="deliver-to-email"> <request> <render-PDF-to-PS> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales2.pdf"/> <destination ContentType="image/tiff" url="file:///c:/DS31/Source/pdf2tiff/CNA\$ID.ps"/> </render-PDF-to-PS> </request>.... </pre>

ID	Error message returned	Cause	Possible Solution	Segment	Scenario
D1	DR.01: Failed to parse DistributionRequest: {0}/Element "file" allows no further input; "item-destination" is not allowed." messageKey="DR.01">com.insystems.distributor.services.distribution.DistributionRequestException: DR.01: Failed to parse DistributionRequest: {0}/Element "file" allows no further input; "item-destination" is not allowed./org.xml.sax.SAXParseException	File item contains a destination URL.		Distribution Item<distribution-item id="item2"> <distribution-item-metadata/> <file> <item-source url="{filesourc}/Sales.doc" ContentType="application/msword"/> <item-destination url="{filesourc}/Sales.doc" ContentType="application/msword"/> </file> </distribution-item>....
D2	DR.01: Failed to parse DistributionRequest: {0}/Element "calligo-item" does not allow "calligo-destination" here." messageKey="DR.01">com.insystems.distributor.services.distribution.DistributionRequestException: DR.01: Failed to parse DistributionRequest: {0}/Element "calligo-item" does not allow "calligo-destination" here./org.xml.sax.SAXParseException	Calligo-item contains a destination URL.		Distribution Item<distribution-item id="item1"> <distribution-item-metadata/> <calligo-item> <calligo-source UISR="PublisherFS:'test\PublisherTest.CMS" docType="cms"/> <calligo-destination UISR="PublisherFS:'newGen.CLG"/> <key-data name="infosource_location" value="C:\DS31\Source\test\samplxml2.xml" type="string" /> </calligo-item> </distribution-item>....
D3	DR.01: Failed to parse DistributionRequest: {0}/Attribute value for "id" is #REQUIRED." messageKey="DR.01">com.insystems.distributor.services.distribution.DistributionRequestException: DR.01: Failed to parse DistributionRequest: {0}/Attribute value for "id" is #REQUIRED./org.xml.sax.SAXParseException	Distribution-item is missing an ID.		Distribution Item<distribution-item > <distribution-item-metadata/> <folder> <item-source url="{filesourc}/test2/Sales.doc" ContentType="application/msword"></item-source> <filter type="wildcard" value="*.doc"/> </folder> </distribution-item>....
D4	DR.01: Failed to parse DistributionRequest: {0}/ID values must be XML names; "" is not a name." messageKey="DR.01">com.insystems.distributor.services.distribution.DistributionRequestException: DR.01: Failed to parse DistributionRequest: {0}/ID values must be XML names; "" is not a name./org.xml.sax.SAXParseException	Distribution-item ID is empty.		Distribution Item<distribution-item id=""> <distribution-item-metadata/> <folder> <item-source url="{filesourc}/test2/Sales.doc" ContentType="application/msword"></item-source> <filter type="wildcard" value="*.doc"/> </folder> </distribution-item>....
D5	RU.failed_to_open_file: Failed to open file to copy repository document into it/No object at: file:/c:/DS31/Source/Sales.doc" messageKey="RU.failed_to_open_file">com.insystems.distributor.serv ices.rendering.RenderingServiceException: RU.failed_to_open_file: Failed to open file to copy repository document into it/No object at: file:/c:/DS31/Source/Sales.doc/com.insystems.repository.RepositoryE xception	Folder item source has no permissions.	Allow read' permissions on the parent folder containing source file. Because the folder presently has no read or write permissions, the system cannot access the file under this folder.	Distribution Item<distribution-item id="item2"> <distribution-item-metadata/> <file> <item-source url="{filesourc}/Sales.doc" ContentType="application/msword"/> </file> </distribution-item>....

ID	Error message returned	Cause	Possible Solution	Segment	Scenario
D6	<p>P2P.64: Conversion from PDF to PS failed. Error code=1 (Error: May not be a PDF file (continuing anyway) Error (0): PDF file is damaged - attempting to reconstruct xref table... Error: Couldn't find trailer dictionary Error: Couldn't read xref table)"</p> <p>messageKey="P2P.64">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.64: Conversion from PDF to PS failed. Error code=1 (Error: May not be a PDF file (continuing anyway) Error (0): PDF file is damaged - attempting to reconstruct xref table...</p>	File item is a Word file but contentType is "application/pdf".		Distribution Item	<pre> ...<distribution-item id="item2"> <distribution-item-metadata/> <file> <item-source url="{filesourc}/Sales.doc" ContentType="application/pdf"/> </file> </distribution-item>.... </pre>
D7	<p>DR.01: Failed to parse DistributionRequest: {0}/Element &quot;distribution-item&quot; does not allow &quot;calligo-item&quot; here."</p> <p>messageKey="DR.01">com.insystems.distributor.services.distribution.DistributionRequestException: DR.01: Failed to parse DistributionRequest: {0}/Element &quot;distribution-item&quot; does not allow &quot;calligo-item&quot; here./org.xml.sax.SAXParseException</p>	In the distribution item, there are two items listed: calligo-item and file. You can only have one item.		Distribution Item	<pre> ...<distribution-item id="item2"> <distribution-item-metadata/> <file> <item-source url="{filesourc}/Sales.doc" ContentType="application/msword"/> </file> <calligo-item> <calligo-source UISR="PublisherFS:test\PublisherTest.CMS" docType="cms"/> <key-data name="infosource_location" value="C:\DS31\Source\test\samplxml2.xml" type="string" /> </calligo-item> </distribution-item>.... </pre>
D8	<p>DR.01: Failed to parse DistributionRequest: {0}/Another element already has an ID attribute with value &quot;printer1&quot;."</p> <p>messageKey="DR.01">com.insystems.distributor.services.distribution.DistributionRequestException: DR.01: Failed to parse DistributionRequest: {0}/Another element already has an ID attribute with value &quot;printer1&quot;./org.xml.sax.SAXParseException</p>	Two channels have the same ID:printer id="printer1" and repository id="printer1".		Delivery Channels	<pre> <delivery-channels> <printer id="printer1" printerName="HPLJIII" outputName="HPLJIII" operatingMode="Synchronized"> <printer-metadata/> </printer> <repository id="printer1" operatingMode="Synchronized"> <repository-metadata/> </repository> <printer id="printer2" printerName="HPLJIII" outputName="HPLJIII" operatingMode="Synchronized"> <printer-metadata/> </printer> </delivery-channels> </pre>
D9	<p>DR.01: Failed to parse DistributionRequest: {0}/Attribute value for &quot;id&quot; is #REQUIRED."</p> <p>messageKey="DR.01">com.insystems.distributor.services.distribution.DistributionRequestException: DR.01: Failed to parse DistributionRequest: {0}/Attribute value for &quot;id&quot; is #REQUIRED./org.xml.sax.SAXParseException</p>	Printer channel does not have an ID attribute.		Delivery Channels	<pre> <printer printerName="HPLJIII" outputName="HPLJIII" operatingMode="Synchronized"> <printer-metadata/> </printer> </pre>

ID	Error message returned	Cause	Possible Solution	Segment	Scenario
D10	DR.01: Failed to parse DistributionRequest: {0}/ID values must be XML names; "" is not a name." messageKey="DR.01">com.insystems.distributor.services.distribution.DistributionRequestException: DR.01: Failed to parse DistributionRequest: {0}/ID values must be XML names; "" is not a name./org.xml.sax.SAXParseException	Repository channel ID is empty.		Delivery Channels	<delivery-channels> <printer id="printer1" printerName="HPLJIII" outputName="HPLJIII" operatingMode="Synchronized"> <printer-metadata/> </printer> <repository id="" operatingMode="Synchronized"> <repository-metadata/> </repository> <printer id="printer2" printerName="HPLJIII" outputName="HPLJIII" operatingMode="Synchronized"> <printer-metadata/> </printer> </delivery-channels>
D11	DR.01: Failed to parse DistributionRequest: {0}/Attribute value for "printerName" is #REQUIRED." messageKey="DR.01">com.insystems.distributor.services.distribution.DistributionRequestException: DR.01: Failed to parse DistributionRequest: {0}/Attribute value for "printerName" is #REQUIRED./org.xml.sax.SAXParseException	Printer channel is missing a printer name.		Delivery Channels<delivery-channels> <printer id="printer1" outputName="HPLJIII" operatingMode="Synchronized"> <printer-metadata/> </printer> <repository id="repository1" operatingMode="Synchronized"> <repository-metadata/> </repository> <printer id="printer2" outputName="HPLJIII" operatingMode="Synchronized"> <printer-metadata/> </printer> </delivery-channels>....
D12	RSR.02: No rendering service available to render from application/msword to error." messageKey="RSR.02">com.insystems.distributor.services.distribution.DistributionRequestException: RSR.02: No rendering service available to render from application/msword to error.	Email channel has an invalid content type: error.		Delivery Channels<email id="email" operatingMode="Synchronized" ContentType="error" outputName="Calligo PDF Converter"></email> </delivery-channels>....
D13	DR.01: Failed to parse DistributionRequest: {0}/Attribute value for "id" is #REQUIRED." messageKey="DR.01">com.insystems.distributor.services.distribution.DistributionRequestException: DR.01: Failed to parse DistributionRequest: {0}/Attribute value for "id" is #REQUIRED./org.xml.sax.SAXParseException	Missing recipient ID.		RecipientDR.01: Failed to parse DistributionRequest: {0}/Attribute value for "id" is #REQUIRED." messageKey="DR.01">com.insystems.distributor.services.distribution.DistributionRequestException: DR.01: Failed to parse DistributionRequest: {0}/Attribute value for "id" is #REQUIRED./org.xml.sax.SAXParseException....

ID	Error message returned	Cause	Possible Solution	Segment	Scenario
D14	<p>DR.01: Failed to parse DistributionRequest: {0}/ID values must be XML names; &quot;&quot; is not a name."</p> <p>messageKey="DR.01">com.insystems.distributor.services.distribution.DistributionRequestException: DR.01: Failed to parse DistributionRequest: {0}/ID values must be XML names; &quot;&quot; is not a name./org.xml.sax.SAXParseException</p>	<p>Empty recipient ID.</p>		<p>Recipient</p>	<pre> ...<recipient id=""> <delivery-preferences> <preference-printer id="prefered_printer" refID="printer1"></preference-printer> <preference-repository id="prefered_repository" refID="repository1"> <absolute-path url="{filedest}/test/"> </preference-repository> <preference-email id="preferred_email" refID="email" subject="hi there..."> <email-body> <embedded-content>hi there...</embedded-content> </email-body> <sender emailAddress="fli@cnaserve.internal.insystems.com"></sender> <receiver emailAddress="fli@cnaserve.internal.insystems.com"></receiver> </preference-email> </delivery-preferences>.... </pre>
D15	<p>DE.07: Delivery preference refers to non-existing channel: refID=printer"</p> <p>messageKey="DE.07">com.insystems.distributor.services.distribution.DistributionRequestException: DE.07: Delivery preference refers to non-existing channel: refID=printer</p>	<p>There is no delivery-channel ID that matches the printer reference ID.</p>		<p>Recipient</p>	<pre> ...<delivery-preferences> <preference-printer id="prefered_printer" refID="printer"></preference-printer> <preference-repository id="prefered_repository" refID="repository1"> <absolute-path url="{filedest}/test/"> </preference-repository> <preference-email id="preferred_email" refID="email" subject="hi there..."> <email-body> <embedded-content>hi there...</embedded-content> </email-body> <sender emailAddress="fli@cnaserve.internal.insystems.com"></sender> <receiver emailAddress="fli@cnaserve.internal.insystems.com"></receiver> </preference-email> </delivery-preferences>.... </pre>
D16	<p>REX.06: Couldn't create destination object (D:file:///c:/DS31/Destination/test2/Sales.doc)/Malformed url D:file:///c:/DS31/Destination/test2/Sales.doc"</p> <p>messageKey="REX.06">com.insystems.distributor.services.delivery.repository.RepositoryServiceException: REX.06: Couldn't create destination object (D:file:///c:/DS31/Destination/test2/Sales.doc)/Malformed url D:file:///c:/DS31/Destination/test2/Sales.doc com.insystems.repository.url.RepositoryURLException: Malformed url D:file:///c:/DS31/Destination/test2/Sales.doc/com.insystems.repository.url.RepositoryURLException</p>	<p>Preference-repository's absolute-path URL is invalid: there is no such drive.</p>		<p>Recipient</p>	<pre> ...<delivery-preferences> <preference-printer id="prefered_printer4" refID="printer2"></preference-printer> <preference-repository id="prefered_repository4" refID="repository1"> <absolute-path url="{filedest}/test2/"> </preference-repository> </delivery-preferences>.... </pre>

ID	Error message returned	Cause	Possible Solution	Segment	Scenario
D17	<p>NW.native6: Word automation: Unknown COleDispatchException (native code): 6!MS Word error (6)"</p> <p>messageKey="NW.native6">com.insystems.distributor.services.rendering.RenderingServiceException: NW.native6: Word automation: Unknown COleDispatchException (native code): 6!MS Word error (6)</p>	<p>Page out of range.</p>		<p>Recipient</p>	<pre>....<delivery-preferences> <preference-printer id="prefered_printer2" refID="printer2" ContentType="application/postscript"> <render-param outputName="HPPS"> <ps> <printer-configuration pageRange="2222" duplex="none"/> </ps> </render-param> </preference-printer>....</pre>
D18	<p>RSR.02: No rendering service available to render from application/msword to application/tiff."</p> <p>messageKey="RSR.02">com.insystems.distributor.services.distribution.DistributionRequestException: RSR.02: No rendering service available to render from application/msword to application/tiff.</p>	<p>Invalid content-type: render word to tiff.</p>		<p>Recipient</p>	<pre>....<delivery-preferences> <preference-printer id="prefered_printer2" refID="printer2" ContentType="application/postscript"> <render-param outputName="HPPS"> <ps> <printer-configuration pageRange="2" duplex="none"/> </ps> </render-param> </preference-printer> <preference-repository id="prefered_repository2" refID="repository1" ContentType="application/tiff"> <absolute-path url="{filedest}/test2"/> </preference-repository> </delivery-preferences>....</pre>
D19	<p>DE.06: DistributionItem not found: (item40). Please check references to DistributionItem (e.g. in recipient-item, email-body and alike)."</p> <p>messageKey="DE.06">com.insystems.distributor.services.distribution.DistributionRequestException: DE.06: DistributionItem not found: (item40). Please check references to DistributionItem (e.g. in recipient-item, email-body and alike). at com.insystems.distributor.services.distribution.DistributionEngine.getDistributionItem(DistributionEngine.java:739)</p>	<p>The recipient-item refID (item40) does not map to any distribution item.</p>		<p>Recipient</p>	<pre>....<recipient-package id="recipient_package5"> <recipient-item refID="item40"> <destination ContentType="application/postscript" url="file:///c:/DS31/Destination/Sales20.ps"/> <render-param outputName="HPPS"> <ps> <printer-configuration pageRange="2" duplex="none"/> </ps> </render-param> </recipient-item>....</pre>

ID	Error message returned	Cause	Possible Solution	Segment	Scenario
D20	<p>"REX.06: Couldn't create destination object (file:///c:/DS31/Destination/Sales20.ps)/The file c:\DS31\Destination\Sales20.ps does not exist"</p> <p>messageKey="REX.06">com.insystems.distributor.services.delivery.repository.RepositoryServiceException: REX.06: Couldn't create destination object (file:///c:/DS31/Destination/Sales20.ps)/The file c:\DS31\Destination\Sales20.ps does not exist</p>	<p>Recipient-item destination URL has no permissions.</p>	<p>Allow 'write' permissions on the parent folder as well as the destination file if it is to be overwritten. Because the parent folder has no write permissions, the system cannot create the destination file under it or overwrite the existing file if it already exists.</p>	<p>Recipient</p>	<pre> ...<recipient-package id="recipient_package5"> <recipient-item refID="item4"> <destination ContentType="application/postscript" url="file:///c:/DS31/Destination/Sales20.ps"/> <render-param outputName="HPPS"> <ps> <printer-configuration pageRange="2" duplex="none"/> </ps> </render-param> </recipient-item>.... </pre>
D21	<p><deliver-to-repository-response status="failure"> <errorDetails text="REX.03: Destination URL not found in the request"</p> <p>messageKey="REX.03">com.insystems.distributor.services.delivery.repository.RepositoryServiceException: REX.03: Destination URL not found in the request</p>	<p>Recipient-item and delivery-preference did not specify the destination URL for delivery to repository.</p>		<p>Recipient</p>	<pre> ...<delivery-preferences> <preference-printer id="preferred_printer2" refID="printer2" ContentType="application/postscript"> <render-param outputName="HPPS"> <ps> <printer-configuration pageRange="2" duplex="none"/> </ps> </render-param> </preference-printer> <preference-repository id="preferred_repository2" refID="repository1" ContentType="application/pdf"> </preference-repository> </delivery-preferences> <recipient-packages> <recipient-package id="recipient_package3"> <recipient-item refID="item2"> </recipient-item> <delivery-preference refID="preferred_repository2"/> <delivery-preference refID="preferred_printer2"/> </recipient-package> </recipient-packages>.... </pre>
D22	<p>RSR.02: No rendering service available to render from application/msword to application/tiff."</p> <p>messageKey="RSR.02">com.insystems.distributor.services.distribution.DistributionRequestException: RSR.02: No rendering service available to render from application/msword to application/tiff.</p>	<p>Invalid recipient-item contentType.</p>		<p>Recipient</p>	<pre> ...<recipient-packages> <recipient-package id="recipient_package3"> <recipient-item refID="item2" ContentType="application/tiff"> </recipient-item> <delivery-preference refID="preferred_repository2"/> <delivery-preference refID="preferred_printer2"/> </recipient-package> </recipient-packages>.... </pre>

ID	Error message returned	Cause	Possible Solution	Segment	Scenario
D23	<p>DR.01: Failed to parse DistributionRequest: {0}/Element &quot;recipient-package&quot; requires additional elements."</p> <p>messageKey="DR.01">com.insystems.distributor.services.distribution.DistributionRequestException: DR.01: Failed to parse DistributionRequest: {0}/Element &quot;recipient-package&quot; requires additional elements./org.xml.sax.SAXParseException</p>	<p>Recipient-package is missing delivery-preference.</p>		<p>Recipient</p>	<pre><recipient id="recipient4"> <delivery-preferences> <preference-printer id="prefered_printer4" refID="printer2"></preference-printer> <preference-repository id="prefered_repository4" refID="repository1"> <absolute-path url="file:///c:/DS31/Destination/test2"/> </preference-repository> </delivery-preferences> <recipient-packages> <recipient-package id="recipient_package5"> <recipient-item refID="item4"> <destination ContentType="application/postscript" url="file:///c:/DS31/Destination/Sales20.ps"/> <render-param outputName="HPPS"> <ps> <printer-configuration pageRange="2" duplex="none"/> </ps> </render-param> </recipient-item> </recipient-package> </recipient-packages> </recipient> </pre>
D24	<p>RP.01: Failed to resolve delivery preference: prefered_printer (delivery-preference element should refer to one of the preferences defined for the same recipient)."</p> <p>messageKey="RP.01">com.insystems.distributor.services.distribution.DistributionRequestException: RP.01: Failed to resolve delivery preference: prefered_printer (delivery-preference element should refer to one of the preferences defined for the same recipient).</p>	<p>recipient-package delivery-preference refID is invalid because the associated ID is not within the same recipient.</p>		<p>Recipient</p>	<pre><recipient id="recipient4"> <delivery-preferences> <preference-printer id="prefered_printer4" refID="printer2"></preference-printer> <preference-repository id="prefered_repository4" refID="repository1"> <absolute-path url="{filedest}/test2"/> </preference-repository> </delivery-preferences> <recipient-packages> <recipient-package id="recipient_package5"> <recipient-item refID="item4"> <destination ContentType="application/postscript" url="file:///c:/DS31/Destination/Sales20.ps"/> <render-param outputName="HPPS"> <ps> <printer-configuration pageRange="2" duplex="none"/> </ps> </render-param> </recipient-item> <delivery-preference refID="prefered_repository4"/> <delivery-preference refID="prefered_printer"/> </recipient-package> </recipient-packages> </recipient>.... </pre>

ID	Error message returned	Cause	Possible Solution	Segment	Scenario
D25	<p>JPROXY.TRANS: Failed to transfer content of temporary file (a/5/item1/PublisherTest.doc) to the destination ({1}). Please see nested exception/Malformed url a/5/item1/PublisherTest.doc"</p> <p>messageKey="JPROXY.TRANS">com.insystems.distributor.services.content.CalligoException: JPROXY.TRANS: Failed to transfer content of temporary file (a/5/item1/PublisherTest.doc) to the destination ({1}). Please see nested exception/Malformed url a/5/item1/PublisherTest.doc</p>	<p>The distribution service failed because the temp directory does not exist or is invalid.</p>		Recipient	<pre> <recipient-packages> <recipient-package id="recipient_package1"> <recipient-item refID="item1"> <destination url="file:///c:/DS31/Source/test" /> </recipient-item> <delivery-preference refID="prefered_repository"/> <delivery-preference refID="prefered_printer"/> </recipient-package> <recipient-package id="recipient_package2"> <recipient-item refID="item2"> <destination ContentType="application/postscript" url="file:///c:/DS31/Destination/Sales10.ps"/> <render-param outputName="HPPS"> <ps> <printer-configuration pageRange="2" duplex="none"/> </ps> </render-param> </recipient-item> <delivery-preference refID="prefered_repository"/> <delivery-preference refID="prefered_printer"/> </recipient-package> </recipient-packages> </pre>
D26	<p>DR.01: Failed to parse DistributionRequest: {0}/No element has an ID attribute with value &quot;recipient_package10&quot;."</p> <p>messageKey="DR.01">com.insystems.distributor.services.distribution.DistributionRequestException: DR.01: Failed to parse DistributionRequest: {0}/No element has an ID attribute with value &quot;recipient_package10&quot;;/org.xml.sax.SAXParseException</p>	<p>Invalid recipientPackageRefID. there is no corresponding ID.</p>		Event Handler	<pre><event> <recipient-package-ready recipientPackageRefID="recipient_package10"/> <event-handler serviceType="count-pages" seqNumber="1"/> <event-handler serviceType="render-Word-to-PCL" seqNumber="2"> <event-handler-metadata> <render-Word-to-PCL> <output-name>HPLJIII</output-name> </render-Word-to-PCL> </event-handler-metadata> </event-handler>.... </pre>
D27	<p>CPS.03: File file:///C:/DS31/Destination/temp/111/item1/PublisherTest.doc is not supported by CountPagesService."</p> <p>messageKey="CPS.03">com.insystems.distributor.services.countpages.CountPagesException: CPS.03: File file:///C:/DS31/Destination/temp/111/item1/PublisherTest.doc is not supported by CountPagesService...</p>	<p>Sequence number (-2) incorrect for count pages service type.</p>		Event Handler	<pre><event-handlers> <event> <recipient-package-ready recipientPackageRefID="recipient_package1"/> <event-handler serviceType="count-pages" seqNumber="-2"/> <event-handler serviceType="render-Word-to-PCL" seqNumber="2"> <event-handler-metadata> <render-Word-to-PCL> <output-name>HPLJIII</output-name> </render-Word-to-PCL> </event-handler-metadata> </event-handler>.... </pre>

ID	Error message returned	Cause	Possible Solution	Segment	Scenario
D28	<p>DR.01: Failed to parse DistributionRequest: {0}/IDREF/IDREFS values must be XML names; &quot;20&quot; is not a name."</p> <p>messageKey="DR.01">com.insystems.distributor.services.distribution.DistributionRequestException: DR.01: Failed to parse DistributionRequest: {0}/IDREF/IDREFS values must be XML names; &quot;20&quot; is not a name./org.xml.sax.SAXParseException</p>	<p>Invalid delivery-package-ready refid</p>		<p>Event Handler</p>	<pre> ...<event-handlers> <event> <delivery-package-ready deliveryChannelRefID="20"/> <event-handler serviceType="count-pages" seqNumber="1"/> <event-handler serviceType="render-Word-to-PCL" seqNumber="2"> <event-handler-metadata> <render-Word-to-PCL> <output-name>HPLJIII</output-name> </render-Word-to-PCL> </event-handler-metadata> </event-handler> <event-handler serviceType="concatenate-pcl" seqNumber="3"> <event-handler-metadata> <concatenate-pcl/> </event-handler-metadata> </event-handler> </event> </event-handlers>...</pre>
D29	<p>CPS.03: File file:///C:/DS31/Destination/temp/111/item1/PublisherTest.doc is not supported by CountPagesService."</p> <p>messageKey="CPS.03">com.insystems.distributor.services.countpages.CountPagesException: CPS.03: File file:///C:/DS31/Destination/temp/111/item1/PublisherTest.doc is not supported by CountPagesService</p>	<p>You cannot count pages of Word documents.</p>		<p>Event Handler</p>	<pre> <event-handler serviceType="count-pages" seqNumber="1"/> <event-handler serviceType="render-Word-to-PCL" seqNumber="2"> <event-handler-metadata> <render-Word-to-PCL> <output-name>HPLJIII</output-name> </render-Word-to-PCL> </event-handler-metadata> </event-handler> <event-handler serviceType="concatenate-pcl" seqNumber="3"> <event-handler-metadata> <concatenate-pcl/> </event-handler-metadata> </event-handler> </event> </event-handlers></pre>

ID	Error message returned	Cause	Possible Solution	Segment	Scenario
D30	<p>errorDetails</p> <p>text="DM.fromXml: Event handler proxy failed(in preRun): {TaskNode: , taskID=2573, serviceType=generate-calligo-document, taskType=event_handler_with_proxy, request={RequestData: request(String)=&lt;event-handler-request taskID=&quot;2565 2568&quot; distributionRequestID=&quot;1023&quot;&gt;&lt;event&gt; &lt;recipient-package-ready recipientPackageRefID=&quot;recipient_package2&quot;/&gt;&lt;event-handler critical=&quot;false&quot; seqNumber=&quot;2&quot; serviceType=&quot;generate-calligo-document&quot;&gt; &lt;event-handler-metadata&gt; &lt;calligo-source UISR=&quot;Test_FS:&amp;apos;testdata\basefunc\cover.CMS&quot; ; docType=&quot;cms&quot; rigorous=&quot;true&quot;&gt;&lt;/calligo-source&gt;&lt;key-data name=&quot;numberOfPages&quot; type=&quot;numeric&quot; value=&quot;1&quot;&gt;&lt;/key-data&gt;&lt;/event-handler-metadata&gt; &lt;/event-handler&gt; &lt;/event&gt; &lt;/event-handler-request&gt; request={EventHandlerRequest: distributionRequestID=1023, taskID(s) messageKey="EHF.01"</p>	<p>Missing <generate-calligo-document> tag within the <event-handler-metadata> tag while trying to generate a cover page.</p>		Event Handler	<pre>.....<event-handlers> <event> <recipient-package-ready recipientPackageRefID="recipient_package2" /> <event-handler serviceType="count-pages" seqNumber="1"/> <event-handler serviceType="generate-calligo-document" seqNumber="2" critical="false"> <event-handler-metadata> <calligo-source UISR="Test_FS:'testdata\basefunc\cover.CMS" docType="cms"/> <key-data name="numberOfPages" type="numeric" value="{numberOfPages}"/> </event-handler-metadata> </event-handler> <event-handler serviceType="concatenate-pcl" seqNumber="3"> <event-handler-metadata> <concatenate-pcl/> </event-handler-metadata> </event-handler> </event> </event-handlers>.....</pre>

ID	Error message returned	Cause	Scenario
E1	hanging	Worker Agent server not started.	<pre><render-PDF-to-PS> <source ContentType="application/pdf" url="{filesource}/Sales2.pdf"/> <destination ContentType="application/postscript" url="{filedest}/dd/LTC_Rate_Increase\$ID.ps"/> <output-name>HPPS</output-name> </render-PDF-to-PS></pre>
E2	com.insystems.test.console.DistributorException at com.insystems.test.console.QueueHelper.getConnectionFactory(Unknown Source) at com.insystems.test.console.QueueHelper.getConnection(Unknown Source) at com.insystems.test.console.Main.run(Unknown Source)	OpenJMS Agent not started.	<pre><render-PDF-to-PS> <source ContentType="application/pdf" url="{filesource}/Sales2.pdf"/> <destination ContentType="application/postscript" url="{filedest}/dd/LTC_Rate_Increase\$ID.ps"/> <output-name>HPPS</output-name> </render-PDF-to-PS></pre>
E3	hanging	Queue Agent not started.	<pre><render-PDF-to-PS> <source ContentType="application/pdf" url="{filesource}/Sales2.pdf"/> <destination ContentType="application/postscript" url="{filedest}/dd/LTC_Rate_Increase\$ID.ps"/> <output-name>HPPS</output-name> </render-PDF-to-PS></pre>
E4	DM.fromXml: Invalid request data (com.insystems.distributor.services.pdf2ps.Pdf2PsService@233b8d)./Element "render-PDF-to-PS" does not allow "output-name" here." messageKey="BS.01">com.insystems.distributor.ServiceException: DM.fromXml: Invalid request data (com.insystems.distributor.services.pdf2ps.Pdf2PsService@233b8d)./Element "render-PDF-to-PS" does not allow "output-name" here./org.xml.sax.SAXParseException	XML tags are in incorrect order: output-name tag placed before of source tag.	<pre><render-PDF-to-PS> <output-name>HPPS</output-name> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales2.pdf"/> <destination ContentType="application/postscript" url="file:///c:/DS31/Destination/Sales2.ps"/> </render-PDF-to-PS></pre>
E5	DM.fromXml: Invalid request data (com.insystems.distributor.services.pdf2ps.Pdf2PsService@13674f3)./Element "render-PDF-to-PS" does not allow "render-PDF-to-PS" here." messageKey="BS.01">com.insystems.distributor.ServiceException: DM.fromXml: Invalid request data (com.insystems.distributor.services.pdf2ps.Pdf2PsService@13674f3)./Element "render-PDF-to-PS" does not allow "render-PDF-to-PS" here./org.xml.sax.SAXParseException	Invalid XML tag: missing back slash in ending tag: should be: </render-PDF-to-PS>.	<pre><render-PDF-to-PS> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales2.pdf"/> <destination ContentType="application/postscript" url="file:///c:/DS31/Destination/Sales2.ps"/> <output-name>HPPS</output-name> <render-PDF-to-PS></pre>

ID	Error message returned	Cause	Scenario
E6	Hanging	Incorrect jms type: currently: PDF-to-PS; should be: render-PDF-to-PS	<pre> JMSType PDF-to-PS JMSReplyTo \${ResponseQueue} JMSDestination \${SubmissionQueue} RequestID pdf2ps4 <?xml version="1.0" encoding="UTF-8"?> <!DOCTYPE render-PDF-to-PS SYSTEM "\${dtdsource}/distributor.dtd"> <render-PDF-to-PS> <source ContentType="application/pdf" url="\${filesource}/Sales2.pdf"/> <destination ContentType="application/postscript" url="\${filedest}/Sales2.ps"/> <output-name>HPPS</output-name> </render-PDF-to-PS> </pre>
E7	hanging	Invalid JMS destination queue name: submit2 queue does not exist.	<pre> JMSType render-PDF-to-PS JMSReplyTo \${ResponseQueue} JMSDestination submit2 RequestID pdf2ps4 <?xml version="1.0" encoding="UTF-8"?> <!DOCTYPE render-PDF-to-PS SYSTEM "\${dtdsource}/distributor.dtd"> <render-PDF-to-PS> <source ContentType="application/pdf" url="\${filesource}/Sales2.pdf"/> <destination ContentType="application/postscript" url="\${filedest}/Sales2.ps"/> <output-name>HPPS</output-name> </render-PDF-to-PS> </pre>
E8	DM.fromXml: Invalid request data (com.insystems.distributor.services.pdf2ps.Pdf2PsService@17850e8)./Element "render-PDF-to-PS" does not allow "source" here." messageKey="BS.01">com.insystems.distributor.ServiceException: DM.fromXml: Invalid request data (com.insystems.distributor.services.pdf2ps.Pdf2PsService@17850e8)./Element "render-PDF-to-PS" does not allow "source" here./org.xml.sax.SAXParseException	Duplicate XML tags: source tag.	<pre> <render-PDF-to-PS> <source ContentType="application/pdf" url="\${filesource}/Sales2.pdf"/> <source ContentType="application/pdf" url="\${filesource}/Sales2.pdf"/> <destination ContentType="application/postscript" url="\${filedest}/Sales2.ps"/> <output-name>HPPS</output-name> </render-PDF-to-PS> </pre>
E9	DM.fromXml: Invalid request data (com.insystems.distributor.services.pdf2ps.Pdf2PsService@142d6c2)./Expected "</output-name>" to terminate element starting on line 7." messageKey="BS.01">com.insystems.distributor.ServiceException: DM.fromXml: Invalid request data (com.insystems.distributor.services.pdf2ps.Pdf2PsService@142d6c2)./Expected "</output-name>" to terminate element starting on line 7./org.xml.sax.SAXParseException	Missing XML ending tag: </output-name>.	<pre> <render-PDF-to-PS> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales2.pdf"/> <destination ContentType="application/postscript" url="file:///c:/DS31/Destination/Sales2.ps"/> <output-name>HPPS </render-PDF-to-PS> </pre>

ID	Error message returned	Cause	Scenario
E10	DM.fromXml: Invalid request data (com.insystems.distributor.services.pdf2tiff.Pdf2TiffService@41fdcf)./Whitespace required before attributes." messageKey="BS.01">com.insystems.distributor.ServiceException: DM.fromXml: Invalid request data (com.insystems.distributor.services.pdf2tiff.Pdf2TiffService@41fdcf)./Whitespace required before attributes./org.xml.sax.SAXParseException	Quote character (") is in the password. This is a reserved XML character.	<render-PDF-to-TIFF> <source ContentType="application/pdf" url="ftp://dsdb1/shared2/Humana.pdf"> <credentials user="test" password="password" /> </source> <destination ContentType="application/postscript" url="ftp://dsdb1/test-only/LTC_Rate_Increase_pdf\$ID.ps"> <credentials user="test" password="pass"word" /> </destination> </render-PDF-to-TIFF>
E11	P2P.14: Invalid source for PDF Rendering./No object at: file://c:/DS31/Source/Sales2.pdf" messageKey="P2P.14">com.insystems.distributor.services.rendering.RenderingServiceException: P2P.14: Invalid source for PDF Rendering./No object at: file://c:/DS31/Source/Sales2.pdf/com.insystems.repository.RepositoryException	One of the worker environments has the wrong source directory. When Publisher choose that worker to render the file, it fails.	<render-PDF-to-PS> <source ContentType="application/pdf" url="file:///c:/DS31/Source/Sales2.pdf"/> <destination ContentType="application/postscript" url="file:///c:/DS31/Destination/dd/LTC_Rate_Increase\$ID.ps"/> <output-name>HPPS</output-name> </render-PDF-to-PS>
E12	javax.jms.JMSEException: Cannot create a queue with null or empty name at org.exolab.jms.client.JmsQueueSession.createQueue(JmsQueueSession.java:99) at com.insystems.test.console.Main.run(Unknown Source)	Missing jms reply to queue name.	JMSType render-PDF-to-PS JMSReplyTo JMSDestination submit RequestID pdf2ps4 <?xml version="1.0" encoding="UTF-8"?> <!DOCTYPE render-PDF-to-PS SYSTEM "\${dtdsource}/distributor.dtd"> <render-PDF-to-PS> <source ContentType="application/pdf" url="\${filesource}/Sales2.pdf"/> <destination ContentType="application/postscript" url="\${filedest}/Sales2.ps"/> <output-name>HPPS</output-name> </render-PDF-to-PS>
E13	REX.05: Couldn't open source file (calligo://admin:password@Calligo;dsdb1:2099/Source/canlife)/Could not access server" messageKey="REX.05">com.insystems.distributor.services.delivery.repository.RepositoryServiceException: REX.05: Couldn't open source file (calligo://admin:password@Calligo;dsdb1:2099/Source/canlife)/Could not access server/com.insystems.repository.lapiadapter.calligo.Handler\$IOException	The DMS is not responding.	<deliver-to-repository> <source ContentType="application/msword" url="calligo://admin:password@Calligo;dsdb1:2099/Source/canlife"/> <destination ContentType="application/msword" url="calligo://admin:password@Calligo;dsdb1:2099/Destination/canlife"> </destination> </deliver-to-repository>

ID	Error message returned	Cause	Scenario
E14	<pre> javax.jms.JMSEException: Failed to make message persistent: org.exolab.jms.persistence.PersistenceException: Failed to get pooled connection at sun.rmi.transport.StreamRemoteCall.exceptionReceivedFromServer(Unknown Source) at sun.rmi.transport.StreamRemoteCall.executeCall(Unknown Source) at sun.rmi.server.UnicastRef.invoke(Unknown Source) at org.exolab.jms.server.rmi.RmiJmsServerSession_Stub.sendMessage(Unknown Source) at org.exolab.jms.client.rmi.RmiJmsSessionStub.sendMessage(RmiJmsSessionStub.java:174) at org.exolab.jms.client.JmsSession.sendMessage(JmsSession.java:867) at org.exolab.jms.client.JmsMessageProducer.sendMessage(JmsMessageProducer.java:285) at org.exolab.jms.client.JmsQueueSender.send(JmsQueueSender.java:145) at org.exolab.jms.client.JmsQueueSender.send(JmsQueueSender.java:100) at com.insystems.test.console.QueueHelper.send(Unknown Source) at com.insystems.test.console.Main.run(Unknown Source) </pre>	<p>The database is not responding.</p>	<pre> <deliver-to-repository> <source ContentType="application/msword" url="calligo://admin:password@Calligo;dsdb1:2099/Source/canlife"/> <destination ContentType="application/msword" url="calligo://admin:password@Calligo;dsdb1:2099/Destination/canlife"> </destination> </deliver-to-repository> </pre>