

PeopleTools 8.56 Online Help Updates, January 2018

PeopleBook	Path	Description of Change
Application Designer Developer's Guide	Specifying Character Field Attributes	In PeopleSoft name fields, while a space is a valid character, it is not allowed immediately after the comma separating the last name from the first name.
Application Designer Developer's Guide	Populating HTML Areas	<p>Respond Once Only - Select this check box to indicate that this HTML area is to be included in the AJAX response one time only, except when some other properties of the HTML area have been changed, such as its content, label, and so on. When this check box is unselected, the HTML area is always included in the AJAX response. This setting applies to HTML areas at any level (from level 0 to level 3).</p> <p>Note: This setting can be overridden by the ForceUpdateOnce property of the Field class.</p>
Application Designer Developer's Guide	Specifying Type Properties for Push Buttons or Links	For action widgets only, the combination of record and field names that specify the location of the PeopleCode must be 28 characters or less.
Application Designer Developer's Guide	Using Grids	For both non-tabbed grids and tabbed grids, indicated that up to two columns can be selected as the row header to be displayed for screen readers.
Application Designer Developer's Guide	Using Grids	<ul style="list-style-type: none"> • Added the List Grid Layout (Ordered) grid layout type. • Revised the labels for all grid layout types to match what is presented in the user interface.
<ul style="list-style-type: none"> • Application Designer Developer's Guide • Fluid User Interface Developer's Guide 	<ul style="list-style-type: none"> • Setting Component Properties • Setting Page Field Properties for Controls • Setting Component Properties for 	Spell check is not currently supported in fluid applications.

PeopleBook	Path	Description of Change
	Fluid Components	
<ul style="list-style-type: none"> • Application Designer Developer's Guide • Fluid User Interface Developer's Guide 	<ul style="list-style-type: none"> • Defining Pop-up Menus • Working with Other Page Controls 	<p>Pop-up menus are not currently supported in fluid applications. The use of pop-up menus can produce unpredictable results with other features of fluid applications.</p>
<ul style="list-style-type: none"> • Application Designer Developer's Guide • Fluid User Interface Developer's Guide 	<ul style="list-style-type: none"> • Setting Page Field Properties for Controls • Creating Display Control and Related Fields • Working with Other Page Controls 	<p>The Show Label option is not supported for page controls on fluid pages.</p>
<ul style="list-style-type: none"> • Application Designer Developer's Guide • Fluid User Interface Developer's Guide 	<ul style="list-style-type: none"> • Using Edit Boxes and Long Edit Boxes • Working with Other Page Controls 	<p>The character limit counter is not supported in fluid applications. If the Enable Long Edit Counter check box is selected for a long edit box on a fluid page, no information is displayed about characters remaining.</p>
Application Designer Developer's Guide	Setting Component Properties	<p>Across the user interface, the "Fluid like theme for Classic" label has been changed to "Classic Plus".</p>
Application User's Guide	<ul style="list-style-type: none"> • Using PeopleSoft Applications with Mobile Devices 	<p>Created new sections based on content published in the <i>Browser Compatibility Guide</i>.</p>

PeopleBook	Path	Description of Change
	<ul style="list-style-type: none"> Gestures Used with Mobile Devices 	
Application User's Guide	Using PeopleSoft Applications with Mobile Devices	<ul style="list-style-type: none"> Classic pages and page elements are not sized appropriately on small form factor devices. Fluid navigation collections operate differently on small form factor devices.
Application User's Guide	Working with Fluid Homepages and Dashboards	Added a new section: Understanding Fluid Dashboards.
Application User's Guide	Working with Fluid Pages and Controls	Added a new section: Using the Back Button.
Application User's Guide	Working with Fluid Pages and Controls	When a classic content reference is selected as the default custom homepage tab by the system administrators or through user personalization, users must add the Homepages tile to the NavBar in order to be able to navigate to any fluid homepages.
Application User's Guide	Working with Fluid Pages and Controls	Added a new section: Working with the Slide-out Left Panel.
Automated Configuration Management	Delivered Configuration Plug-ins	Added a new property (env.pttokendomaincomp) to the PTWebProfileConfig plug-in. This property enables or disables the ps-token check across domains in a cluster setup.
BI Publisher for PeopleSoft	Defining Report Definitions, Creating Report Definitions	Connected Query is available as a data source type for BI Publisher power users.
Change Assistant and PeopleSoft Update Manager	Modifying Step Properties and Parameters	Added Step types ExportTemplate and UpdateCurrentHomes.
Change Assistant and PeopleSoft Update Manager	Variables for All Step Types that Use Path	Updated the runtime order and added #ALL_PATHS_TGT_CBL which is used to determine the COBOL location.
Change Assistant and PeopleSoft Update Manager	Reviewing the Execution Comparison Report	Added a note that PTIA0008.SQR must be run after data conversion is finished.

PeopleBook	Path	Description of Change
Change Assistant and PeopleSoft Update Manager	Understanding Change Assistant For Upgrades	Each application homepage in My Oracle Support will have a tab for the Upgrade Source Images for that application.
Change Assistant and PeopleSoft Update Manager	Using Change Assistant to Apply PeopleTools Patch	Updated this topic for 8.56 patches.
Data Management	Running SYSAUDIT, Application Engine Integrity	Added a new audit query (AE-16) and resolution for Application Engine.
Fluid User Interface Developer's Guide	Implementing Master/Detail Components	Revised this section to provide detailed instructions on how to create the record, page, component, and content reference definitions plus PeopleCode program needed to load a master list into PT_MDSTARTPAGE_NUI from this separate component.
Fluid User Interface Developer's Guide	Working with Two-Panel Implementations	Added this topic with three sections: <ul style="list-style-type: none"> • AJAX Transfers. • Left Panel Collision Handling with Slide-out Left Panels. • Creating a Translator Component to Handle Search Initialization
Fluid User Interface Developer's Guide	Working with Group Boxes	Revised the section, Creating Custom Headers, to describe how to use the Custom Header Left/Middle/Right/Bottom group box types to reparent custom controls to the default header. Included a note on how to avoid having custom buttons become the first focusable field on a page.
Fluid User Interface Developer's Guide	Working with Other Page Controls	Added a section: Working with Scroll Areas
Fluid User Interface Developer's Guide	Working with Other Page Controls	Noted that the rich text editor is not supported for long edit boxes in fluid applications. In addition, added Page Controls Not Supported in Fluid Applications to note the following page controls are not supported in fluid applications: <ul style="list-style-type: none"> • Frames • Pop-up menus • Scroll bars • Trees

PeopleBook	Path	Description of Change
Fluid User Interface Developer's Guide	Considering Accessibility for Fluid Pages	By default, the focus will be set to the first interactive field found on the page. However, if this field is not visible because it is within an invisible element (for example, a group box that is set to invisible) or within collapsed accordion content, then focus will be lost.
Fluid User Interface Developer's Guide	Implementing Transfers and Modal Windows With PeopleCode	Added a new section, Transfer and Modal Functions, listing the 18 built-in PeopleCode functions that can be used to implement transfers and create modal windows. The table indicates which function is available for use in which context.
Fluid User Interface Developer's Guide	Working with the Back Button	To support navigation tracking to remote content in a clustered PeopleSoft environment, an additional HTTP request, PTGETREMOTEDATA, is issued from the local site to the remote site.
Fluid User Interface Developer's Guide	Managing Fluid User Interface Deployments	As of PeopleTools 8.55, a PeopleSoft system operates in fluid mode only; classic mode is not available as a system setting. Updated information to describe settings relevant to fluid applications, not fluid mode.
Fluid User Interface Developer's Guide	Preparing to Use MAF for PeopleSoft Applications	Updated the download and install instructions to more clearly indicate that MAF is typically a standard part of the PeopleTools bundle downloaded from OSDC. Therefore, downloading MAF is not typically required. OTN is to be used to download MAF in rare circumstances only when the supported version of MAF is not yet available on OSDC and therefore is not yet included in the PeopleTools bundle.
Fluid User Interface Developer's Guide	Using the Push Notification Window	Added a note to state that notifications are displayed in the language of the notification approver. The notification language does not depend on the user's language preference or the PIA session language.
Fluid User Interface Developer's Guide	Using the Push Notification Window	Replaced existing notification screenshot to show notifications without any reference to AWE.
Fluid User Interface Developer's Guide	Setting Up Push Notification Configurations	Updated the content to include a topic on configuring push notifications for multiple Process Scheduler domains and added content on

PeopleBook	Path	Description of Change
		troubleshooting the push notification configuration.
Fluid User Interface Developer's Guide	Configuring Push Notification to Run within Oracle Mobile Application Framework	Updated content to clearly state that HTTPS needs to be used in IB service configuration when configuring push notifications to the Google Cloud Messaging server.
Global Technology	Fine-Tuning COBOL Programs for the z/OS Unicode Environment, Understanding Character Set Conversion	Added a note to use one of those three options (NewLine LF, NewLine CR, or NewLine CRLF) at the end of the command for changing the newline characters in the <i>Understanding Character Set Conversion</i> section.
Global Technology	Translating HTML Definitions	Replaced the steps involved to translate HTML definition with a note on HTML objects.
Global Technology	Converting to Unicode on Microsoft SQL Server and DB2/UDB Databases, Importing Database Contents Using PeopleSoft Data Mover	Added a note: When importing on MSS or on ORA for any 9.0 and higher app databases, SET ENABLED_DATATYPE 9.1 is also valid and has the same effect as SET ENABLED_DATATYPE 9.0.
Integration Broker	Sending and Receiving Binary Data	Added a note to say that MTOM is currently supported for asynchronous messaging only.
Integration Broker	Integrating with BPEL Process-Based Services Developing Transforms Using Oracle XSL Mapper Developing Transform Programs Using the XSLT Transform Builder	Removed all BPEL content from the Integration Broker book including the entire chapter - Integrating with BPEL Process-Based Services In code examples, replaced all instances of BPEL with ESB.

PeopleBook	Path	Description of Change
	Understanding Providing WSDL Documents Consuming and Invoking Oracle Mediator/ESB-Based Services	
Integration Broker Administration	Working With the AS2 Connectors Understanding Nodes Using WS-Reliable Messaging	Removed all BPEL content from the Integration Broker Administration book including the section - <ul style="list-style-type: none"> • BPEL Node (included in the topic Understanding Nodes)
MultiChannel Framework	Understanding the E-mail Channel, Working with E-mails using PeopleSoft Multichannel Framework	Corrected the heading of the section, replaced the mention of 'MCF_GetMail target connector' with 'GETMAILTARGET target connector of the MCF_GetMail node', and removed step3 from the section - Transport Later Security Configurations.
MultiChannel Framework	Configuring E-mail Channel in PeopleSoft Integration Broker, Configuring GETMAILTARGET Connector Properties	Modified description content to describe the relationship between MCF_FORCE_DOWNLOAD_ATTACH and MCF_CONTENTTYPES
MultiChannel Framework	Configuring E-mail Channel in PeopleSoft Integration Broker, Configuring GETMAILTARGET Connector Properties	Replaced backslash (\) with forward slash (/) in the default value and description paths.
MultiChannel Framework	JSMCAPI Quick Reference, JSMCAPI Classes, GroupStatistics	Added a note in the numberOfAbandoned field that the field is only updated for voice tasks, and only if the CTI adapter supports this calculation.
PeopleCode API Reference	Analytic Calculation Engine Classes,	For the GetAnalyticModel method, corrected the documentation to show that the correct PeopleCode reserved word is AnalyticModel .

PeopleBook	Path	Description of Change
	AnalyticInstance Class Methods	
PeopleCode API Reference	BannerTile Class	The BannerTile class includes three new methods and two new properties: <ul style="list-style-type: none"> • Methods: <ul style="list-style-type: none"> ○ ApplyVisuals ○ DeleteContext ○ DeleteContextAndUpdate • Properties: <ul style="list-style-type: none"> ○ AnnounceText ○ IsPersistContext
PeopleCode API Reference	BI Publisher Classes, ReportDefn Class Methods	Added the setPDFConversionPageNumbering method.
PeopleCode API Reference	BPEL Classes	PeopleSoft no longer supports BPEL integration. This chapter and documentation for the following classes has been removed: <ul style="list-style-type: none"> • AsyncFFSend class • BPELUtil class • IBUtil class
PeopleCode API Reference	Life Cycle of a Component Interface	Removed COM from the note about where user-defined methods can be executed.
PeopleCode API Reference	Field Class Properties	Revised the documentation for the Style property to more clearly define its usage to set a custom override to the style class specified in Application Designer. Added restrictions on which system conditions will override this custom override.
PeopleCode API Reference	Fluid Page Utilities Classes, PanelController Class Methods	Added methods for handling left panel collisions using a slide-out left panel: IsSide1CollisionInterPage, IsSide1CollisionIntraPage, and IsSide1HasCollision.
PeopleCode API Reference	System Setup for Java Classes	For Application Engine programs, modify the “Add To CLASSPATH” parameter on the Process Scheduler machine.
PeopleCode API Reference	Mail Classes, Mail Classes Examples	Updated the examples to more fully handle response codes from the Send command.

PeopleBook	Path	Description of Change
PeopleCode API Reference	Message Classes, IntBroker Class Methods	<p>Added an optional fourth parameter to the GenLayoutDoc method:</p> <p><i>use_custom_doc</i> - Specifies an optional boolean value indicating whether to return the Document object based on the custom document instead of the parent document.</p>
PeopleCode API Reference	Mobile Application Platform (MAP) Classes	<p>Added the following new PeopleCode items:</p> <ul style="list-style-type: none"> • Map class methods: <ul style="list-style-type: none"> ○ GetCustDocument ○ GetExceptionDocument ○ GetExceptionURIDocument • Map class properties: <ul style="list-style-type: none"> ○ ExceptionLayoutName ○ IsIBBaseDomain ○ MAPException ○ NoBackButtonUpdate • MapPage class properties: <ul style="list-style-type: none"> ○ SubPage • MapElement class properties: <ul style="list-style-type: none"> ○ NoCustomContainer ○ PreSelected ○ RefLayoutHidden ○ SubContainer ○ SubPage
PeopleCode API Reference	Related Content Framework Classes	<p>Added a new chapter documenting these classes:</p> <ul style="list-style-type: none"> • PTCS_SRVDEFN:RCServiceDefinition • PTCS_SRVDEFN:RCParameter • PTCS_SERVICE:RCService • PTCS_SRVCONFIG:RCServiceConfig • PTCS_SRVCONFIG:RCMapFields • PTCS_MENULAYOUT:RCMenuLayout • PTCS_MENULAYOUT:RCMenuFolder • PTCS_MENULAYOUT:RCMenuLink
PeopleCode API Reference	<ul style="list-style-type: none"> • Row Class Methods • Rowset Class Methods 	<p>For the CopyTo method of either class to copy all of the properties of the fields from the source object, the source and target scrolls must have exactly the same shape.</p>

PeopleBook	Path	Description of Change
PeopleCode API Reference	Rowset Class Methods	Added the new FillChunk method.
PeopleCode API Reference	Rowset Class Methods	Added an example to the Flush method demonstrating how to use the IsUserSorted method with a user-sorted grid.
PeopleCode Developer's Guide	Processing Sequences, Field Change Processing	Note: In certain, limited circumstances, tabbing out of a field is not recognized as a change of focus. This occurs when the next item in the tab order does not have an "on-focus handler." For example, the embedded help icon does not have an on-focus handler. In these limited circumstances, field change processing will not occur.
PeopleCode Developer's Guide	Deferred Processing Mode	Clarified concepts regarding deferred processing mode and corrected misstatements about the default state for components, pages, and fields, which is deferred processing mode for all three.
PeopleCode Developer's Guide	Using the HTML Sanitizer	The HTML sanitizer is used to scan and sanitize HTML files uploaded with the AddAttachment and MAddAttachment functions.
PeopleCode Language Reference	PeopleCode Built-in Functions and Language Constructs	For the CreateMessage, the definition of the first parameter was changed to: Operation. <i>srcv_op_name</i> – Specify the name of the service operation you want to create a Message object for as a string value.
PeopleCode Language Reference	PeopleCode Built-in Functions and Language Constructs	Use the DoModalX and DoModalXComponent functions in classic applications only, either in a standalone classic application or when classic components are included in fluid activity guide and master/detail wrappers.
PeopleCode Language Reference	PeopleCode Built-in Functions and Language Constructs	For the InsertImage function, corrected the documentation to show that the correct constant value is %InsertImage_Cancelled.
PeopleCode Language Reference	PeopleCode Built-in Functions and Language Constructs	Added functions for managing AJAX transfers (asynchronous in-place transfers) and handling left panel collisions using a slide-out left panel: IsMDAJAXTrf, IsMDListSlideout, SetMDAJAXTrf, and SetMDListSlideout.
PeopleCode Language Reference	PeopleCode Built-in Functions and Language Constructs	The Prompt function is not supported in fluid applications. A PeopleCode error will occur if the function is used in a fluid application.

PeopleBook	Path	Description of Change
PeopleCode Language Reference	PeopleCode Built-in Functions and Language Constructs	SetComponentChanged can be used only in events that occur after the Page activate event.
PeopleCode Language Reference	PeopleCode Built-in Functions and Language Constructs	The ShouldSuppressCREF function has been deprecated and is retained for backward compatibility only.
PeopleCode Language Reference	PeopleCode Built-in Functions and Language Constructs	<p>Revised the documentation for the StripOffHTMLTags function to clarify that it both removes all HTML tags in an HTML-formatted string and then decodes six specific HTML entities into their plain text character equivalents. In addition:</p> <p>Warning! Do not use StripOffHTMLTags to prevent cross-site scripting (XSS). In fact, the string returned by StripOffHTMLTags should be re-encoded using the EscapeHTML function before sending to the browser because the decoding performed by the function can activate XSS injection.</p>
PeopleCode Language Reference	PeopleCode Built-in Functions and Language Constructs	Added two new functions for developing fluid and classic applications, and specifically those that operate in both contexts: TransferTop and ViewURLTop.
PeopleCode Language Reference	PeopleCode Built-in Functions and Language Constructs	Added two new functions for developing fluid and classic applications, and specifically those that operate in both contexts: ViewContentURLClassic and ViewContentURLFluid.
PeopleCode Language Reference	Directive PeopleCode Functions and Constructs	During compilation, the entire directive block that evaluates to False is treated as a PeopleCode comment. This PeopleCode comment has a special limit of 32,766 characters (unlike regular PeopleCode comments which are limited to 16,383 characters). If your PeopleCode program has a block that evaluates to False that is greater than 32,766 characters, you will be unable to save your program and will receive an error message.
PeopleCode Language Reference	Meta-SQL Reference	Corrected the examples for %DateDiff to ensure that the <i>date_from</i> precedes the <i>date_to</i> .

PeopleBook	Path	Description of Change
PeopleCode Language Reference	Meta-SQL Reference	Corrected the examples for %KeyEqual and %KeyEqualNoEffDt to match the correct syntax without a comma between the two parameters.
PeopleCode Language Reference	System Variables Reference	For the %DbName variable, noted that on SQL Server, the value returned is the ODBC name for the database.
PeopleCode Language Reference	Meta-HTML Reference	The proper HTML usage of the %tabindex meta-variable is to always enclose it in double quotes as follows: tabindex="%tabindex"
PeopleCode Language Reference	Meta-SQL Reference	Added the %SelectByRowNum function.
Performance Monitor	(Multiple files) Setting Up SSL Setting Up SSL Client Authentication Setting Global System Options Setting Up Monitor Clusters	Revised the content to remove SSL related configuration in PPMI URL.
Pivot Grid	Including Pivot Grid Subpages in Application Pages, Including Chart Only View and Search Options on the Application Page	Added a note to emphasize <i>ComponentLife</i> variable used as an example in the topic is only valid for custom fluid search pages – that is, it can only be used when replacing the PeopleTools delivered PTS_NUI_SEARCH page.
Portal Technology	Administering Content References	For the Display on Small Form Factor check box, clarified that: Manually select this option only if this content reference has been designed to display and perform well on small form factor devices such as smart phones. If this option is deselected, any <i>tile</i> defined for this content reference will not be available on fluid homepages or fluid dashboards when the user is signed in on a small form factor device.

PeopleBook	Path	Description of Change
Portal Technology	<ul style="list-style-type: none"> • Administering Content References, Available Content Reference Attributes • Configuring Web Profiles, Configuring Custom Properties 	<ul style="list-style-type: none"> • Added the BGLOBALVALUES content reference attribute. • Updated the parallelLoading custom attribute with the following. Pagelets with global variables should not be loaded in parallel; such pagelets must be loaded sequentially. When the parallelLoading property is set to true, you must also add the BGLOBALVALUES content reference attribute to the content reference definition for each pagelet that includes global variables; set the BGLOBALVALUES attribute to true. Then, these pagelets will be loaded sequentially while all other pagelets will be loaded in parallel.
Portal Technology	Configuring Web Profiles, Configuring Custom Properties	Added the FocusOnList property.
Portal Technology	Configuring Web Profiles, Configuring Custom Properties	Added the IDDA property.
Portal Technology	Defining Macro Sets and Macros	<ul style="list-style-type: none"> • Updated the section, "Enabling a Custom Macro Set," to reflect the new macro set and style sheet definitions delivered in PeopleTools 8.56.03. • Added a new section, "Updating a Custom Macro Set Created Prior to PeopleTools 8.56."
Portal Technology	Creating Contextual Fluid Dashboards	Updated the procedures and PeopleCode examples to reflect new PTNUI:Banner:BannerTile class methods and properties.
Portal Technology	<ul style="list-style-type: none"> • Fluid Navigation Collections • Understanding Activity Guides 	Activity guides and fluid navigation collections do not support conditional navigation.

PeopleBook	Path	Description of Change
	<ul style="list-style-type: none"> Configuring Conditional Navigation 	
Portal Technology	Configuring Conditional Navigation	As of PeopleTools 8.55, a PeopleSoft system operates in fluid mode only; classic mode is not available as a system setting. Therefore, the Conditional Navigation Decision Matrix has been updated to remove all entries for classic mode.
Portal Technology	WorkCenter-Like Functionality in Fluid Applications	WorkCenters are a classic-only feature delivered in PeopleTools. However, several PeopleTools features allow you to create WorkCenter-like functionality in fluid applications: master/detail components and fluid navigation collections.
Portal Technology	Administering WorkCenter Starting Pages	Select the Classic Plus check box to display the pagelet area of a WorkCenter with fluid-like styling (which is also referred to as "classic plus"). Only the pagelet area of the WorkCenter is affected by this setting.
Portal Technology	Enhancing Activity Guides	Indicated that the PTAI_NAV_SAVE_NEXT and PTAI_NAV_SAVE_PREV methods for custom buttons are to be used in classic activity guides only.
Portal Technology	<ul style="list-style-type: none"> PeopleTools Components Delivered as Classic Plus Configuring Branding System Options Branding Classic Components 	Across the user interface, the "Fluid like theme for Classic" label has been changed to "Classic Plus".
Portal Technology	PeopleTools Components Delivered as Classic Plus	The following Data Migration Workbench components were also delivered as enabled for "classic plus": PTADSADMINRPT, PTADSADMINRPTSRCH (Administrator Reports), PTADSDEFNSEARCH (Data Set Designer), PTADSDMW, PTADSDMWSEARCH (Data Migration

PeopleBook	Path	Description of Change
		Workbench), PTADSMMGR, PTADSPROP, PTADSSUMRPT (Run Data Set Summary Report), and PTPRJREPOSDEFN (Manage File Locations).
Portal Technology	Producing Remote Portlets (Producer), How WSRP Content Is Styled	Revised this section and included the following: In addition, while the look of PeopleSoft classic content on a PeopleSoft portal reflects the selected system branding theme type (Tangerine, Classic Plus, and so on), when the same content is produced and consumed through WSRP, the PeopleSoft branding theme setting is irrelevant and ignored.
Query	Creating New Queries, Viewing and Editing Query Properties	Appended the Query field information with maximum character length allowed and types of characters allowed.
Search Technology	Working with Global Search, Working with the Portal Registry Search	Updated content to include the following: <ul style="list-style-type: none"> • Portal registry menu search is called Navigator. • Every search result has an associated icon. The default icon is PTNAVSRCH_DEF_ICN, which can be changed. • Location of facet folder.
Security Administration	Employing LDAP Directory Services, Enabling Signon PeopleCode for LDAP Authentication	Removed the note that stated that the user ID entered, whether it is Invoke As user signing in or a default user, must be able to access the User Profiles component in a permission list as "Invoke As" user no longer needs any specific security to work.
Test Framework	Executing Tests, Executing a Test from the Command Line	Repositioning of the pstopic2 content, Executing a Test from a URL to Executing a Test from the Command Line. Also emphasizing the parameter helps in executing a text.
Test Framework	Executing a Test on Windows Remote Desktop	Added a new topic on how to prevent a test failure if the test is running on PeopleSoft Test Framework on a remote host and the customer is accessing the remote host from Windows Remote Desktop.

PeopleBook	Path	Description of Change
Workflow Technology	Creating Worklist Entries by an External System	Removed Oracle BPEL explanation from section Defining CREATE_WORKLIST_ITEM Service Operation.