

---

# MySQL Enterprise Backup 8.0 Release Notes

## Abstract

This document lists the changes to the MySQL Enterprise Backup 8.0 product, beginning with the most recent release. Each release section covers added or changed functionality, bug fixes, and known issues, if applicable. For information about changes in a different MySQL Enterprise Backup series, see the release notes for that series.

For additional MySQL Enterprise Backup 8.0 documentation, see the [MySQL Enterprise Backup User's Guide \(Version 8.0.16\)](#).

For legal information, see the [Legal Notices](#).

For help with using MySQL, please visit either the [MySQL Forums](#) or [MySQL Mailing Lists](#), where you can discuss your issues with other MySQL users.

Document generated on: 2019-04-19 (revision: 17699)

## Table of Contents

Preface and Legal Notices .....	1
Changes in MySQL Enterprise Backup 8.0.16 (Not yet released, General Availability) .....	3
Changes in MySQL Enterprise Backup 8.0.15 (2019-02-01, General Availability) .....	3
Changes in MySQL Enterprise Backup 8.0.14 (2019-01-21, General Availability) .....	3
Changes in MySQL Enterprise Backup 8.0.13 (2018-10-22, General Availability) .....	4
Changes in MySQL Enterprise Backup 8.0.12 (2018-07-27, General Availability) .....	5
Changes in MySQL Enterprise Backup 8.0.11 (2018-04-19, General Availability) .....	7
Index .....	8

## Preface and Legal Notices

This document lists the changes to the MySQL Enterprise Backup 8.0 product, beginning with the most recent release.

### Legal Notices

Copyright © 2003, 2019, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users

are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

This documentation is NOT distributed under a GPL license. Use of this documentation is subject to the following terms:

You may create a printed copy of this documentation solely for your own personal use. Conversion to other formats is allowed as long as the actual content is not altered or edited in any way. You shall not publish or distribute this documentation in any form or on any media, except if you distribute the documentation in a manner similar to how Oracle disseminates it (that is, electronically for download on a Web site with the software) or on a CD-ROM or similar medium, provided however that the documentation is disseminated together with the software on the same medium. Any other use, such as any dissemination of printed copies or use of this documentation, in whole or in part, in another publication, requires the prior written consent from an authorized representative of Oracle. Oracle and/or its affiliates reserve any and all rights to this documentation not expressly granted above.

## Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

## Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

## Changes in MySQL Enterprise Backup 8.0.16 (Not yet released, General Availability)

Version 8.0.16 has no release notes, or they have not been published because the product version has not been released.

## Changes in MySQL Enterprise Backup 8.0.15 (2019-02-01, General Availability)

MySQL Enterprise Backup 8.0.15 is the latest release for MySQL Enterprise Backup. It only supports MySQL Server 8.0.15. For earlier versions of MySQL 8.0, use the MySQL Enterprise Backup version with the same version number as the server. For MySQL server 5.7, please use MySQL Enterprise Backup 4.1, and for MySQL Server 5.6 and 5.5, please use MySQL Enterprise Backup 3.12.

This release contains no functional changes and is published to align version number with the MySQL Server 8.0.15 release.

## Changes in MySQL Enterprise Backup 8.0.14 (2019-01-21, General Availability)

MySQL Enterprise Backup 8.0.14 is the latest release for MySQL Enterprise Backup. It only supports MySQL Server 8.0.14. For earlier versions of MySQL 8.0, use the MySQL Enterprise Backup version with the same version number as the server. For MySQL server 5.7, please use MySQL Enterprise Backup 4.1, and for MySQL Server 5.6 and 5.5, please use MySQL Enterprise Backup 3.12.

- [Functionality Added or Changed](#)
- [Bugs Fixed](#)

### Functionality Added or Changed

- `mysqlbackup` now supports encrypted binary and relay log. See [descriptions for the undo log files](#) for details.
- `mysqlbackup` now supports the `--ssl-fips-mode` option, which controls whether `mysqlbackup` operates in FIPS mode. See [FIPS Support](#) for details.

### Bugs Fixed

- When working with a Group Replication cluster, `mysqlbackup` quit unexpectedly near the end of a backup operation when, in order to write to the `backup_history` table, it tried to connect with an unencrypted connection to one of the nodes on which the backup user had not logged on before. It was because, as a user created with the `caching_sha2_password` plugin (enabled by default on MySQL 8.0 servers), the backup user must log on with an encrypted connection when it connects to the server for the first time; the attempt to log on thus failed, and `mysqlbackup` could not handle the failure. With this fix, at such failures, `mysqlbackup` quits gracefully with the warning that the backup operation is finished without updates to the backup history. (Bug #28893180)
- An `apply-incremental-backup` operation failed with an error (`RDR1 ERROR: Unable to remove relaylog files from full backup`) when the incremental backup was created with the `--compress` option. (Bug #28366241)

- `mysqlbackup` quit unexpectedly during an `apply-incremental-backup` operation if the backed up server had been started using relative paths for `--datadir` and `--log-bin`. (Bug #28334521)
- Attempts to restore a backup of a MySQL 5.7 Server to a MySQL 8.0 Server resulted in a strange error message (`Server_version is not obtained`). With this fix, `mysqlbackup` now indicates that the operation is not supported. For related information, see [Restoring a Backup with a Database Upgrade or Downgrade](#). (Bug #27952379)
- After restoring an incremental folder backup and putting its binary log at a specified location different from that for the base backup, the older binary log files of the base backup were not removed by `mysqlbackup`. (Bug #27890472)
- Partial backups sometimes failed because full-text index files had their file names matched by the regular expression provided by the `--include-tables` option, and the files were then handled as ordinary tablespace files by `mysqlbackup`. With this fix, `mysqlbackup` excludes any full-text index files from backups. (Bug #25044900)

## Changes in MySQL Enterprise Backup 8.0.13 (2018-10-22, General Availability)

MySQL Enterprise Backup 8.0.13 is the latest release for MySQL Enterprise Backup. It only supports MySQL Server 8.0.13. For earlier versions of MySQL 8.0, use the MySQL Enterprise Backup version with the same version number as the server. For MySQL server 5.7, please use MySQL Enterprise Backup 4.1, and for MySQL Server 5.6 and 5.5, please use MySQL Enterprise Backup 3.12.

- [Functionality Added or Changed](#)
- [Bugs Fixed](#)

### Functionality Added or Changed

- `mysqlbackup` now supports backup compression (the use of the `--compress` and `--uncompress` options) for incremental backups (except for incremental backups created with the `--incremental-with-redo-log-only` option).
- `mysqlbackup` now supports [transparent page compression](#) for InnoDB tables. The support is enabled by setting the `mysqlbackup` option `--compress-method=punch-hole`; see description for the option for details.

### Bugs Fixed

- Restoring an incremental backup image using the `copy-back-and-apply-log` command failed with `mysqlbackup` complaining that the server repository configuration (including, e.g., value of `innodb_data_file_path`) was unknown for the target server. With this fix, `mysqlbackup` gets the required information from the `backup-my.cnf` file already restored with the base backup of the incremental backup. (Bug #28411028)

References: This issue is a regression of: Bug #27429244.

- `mysqlbackup` hung when a backup operation failed due to a full disk. With this fix, `mysqlbackup` quits gracefully in the situation by throwing an error. (Bug #28399821)
- During an `--apply-incremental-backup` operation, `mysqlbackup` attempted to delete the binary log of the backed-up, running server. (Bug #28377502)

- On FreeBSD platforms, using the `--show-progress` option did not make `mysqlbackup` print progress reports. (Bug #28350122)
- A `mysqlbackup` operation on an image stored on an OpenStack cloud storage service sometimes failed with a segmentation fault or a bad URL error. It was because of a race condition caused by an uninitialized variable, which has been eliminated by this fix. (Bug #28189239, Bug #28183729)
- Backups for databases with encrypted InnoDB tables failed when the `--compress` option was used. (Bug #28177466)
- The Windows version of MySQL Enterprise Backup did not display its build ID when invoked. (Bug #27916702)
- A `mysqlbackup` operation on an image stored on an OpenStack cloud storage service failed with a `401 Unauthorized` error when the operation took a long time and the authentication token for the cloud access expired. With this fix, a separate thread in `mysqlbackup` requests a new token from the OpenStack cloud service in that situation, so that the operation can continue. (Bug #27893174)
- When the `--show-progress=table` option was used, `mysqlbackup` gave a warning in the error log on an aborted connection to the server near the end of the operation. It was because the connection to the server for writing to the `backup_progress` table had remained open. With this fix, the connection is properly closed after the `mysqlbackup` operation is finished. (Bug #27647283)
- When an incremental backup was restored without using the `--log-bin` option, the binary log was not restored to its original location on the backed up server, but to the location specified by `--log-bin` earlier during the restore of the base backup. The same occurred for relay logs of incremental backups for slaves when the `--relay-log` option was not used. (Bug #27545745)
- If, when a backup was in progress and `mysqlbackup` was reading the binary log (or the relay log) index file and the server tried to modify the index file (because, for example, a log flush or log purge just took place), the binary logging (or relay logging) stopped; the server also quit unexpectedly on Windows platforms. It was because `mysqlbackup` did not handle well the file sharing violation. With this fix, `mysqlbackup` now reads the index file using the local file system API, which handles the file sharing violation gracefully; also, `mysqlbackup` now copies the index file into its buffer and then closes it, instead of keeping it open for long, so the server can modify or delete the index file more easily. (Bug #22914974, Bug #26047119)

## Changes in MySQL Enterprise Backup 8.0.12 (2018-07-27, General Availability)

MySQL Enterprise Backup 8.0.12 is the latest release for MySQL Enterprise Backup. It only supports MySQL Server 8.0.12. For earlier versions of MySQL 8.0, use the MySQL Enterprise Backup version with the same version number as the server. For MySQL server 5.7, please use MySQL Enterprise Backup 4.1, and for MySQL Server 5.6 and 5.5, please use MySQL Enterprise Backup 3.12.

- [Functionality Added or Changed](#)
- [Bugs Fixed](#)

### Functionality Added or Changed

- **Important Change:** Starting from release 8.0.12, the storage engine of the `mysql.backup_history` table on a backed-up server has switched from CSV to InnoDB, and a new column for server UUIDs has been added to the table. See [Backup History Table Update](#) for the new user privileges required by `mysqlbackup` due to this change.

- **Important Change:** When working with a [Group Replication](#) setup, `mysqlbackup` now makes the backup history available to all members of the server group by making sure that the `backup_history` table is updated on a primary node after each `mysqlbackup` operation. See [Using MySQL Enterprise Backup with Group Replication](#) for details.

With the implementation of this feature, the new user privilege of `SELECT` on `performance_schema.replication_group_members` is now required by `mysqlbackup` to work with any server, even when it does not belong to a Group Replication setup. See [Grant MySQL Privileges to Backup Administrator](#) for details.

- Version information for `mysqlbackup` is now printed to the `stdout` instead of the `stderr` stream when the `--version` or `--help` option is used. (Bug #27253989)
- OAuth is now supported for Oracle Cloud Storage client authentication. Two new options, `--cloud-storage-url` and `--cloud-oauth-token`, have been introduced for the purpose. See [Cloud Storage Options](#) for details.

## Bugs Fixed

- Backups for a server failed when it had `ANSI_QUOTES` in its values for `sql_mode`. (Bug #27939774)
- The maximum value that could be set for the `--safe-slave-backup-timeout` option was 2700 (seconds), which automatically replaced any larger value. With this fix, there is no longer a maximum limit, even though a high value is not recommended; see the description of `--safe-slave-backup-timeout` for details. (Bug #27883020)
- Restoring an incrementation backup on top of a data directory restored using a compressed backup failed. It was because `mysqlbackup` did not set `is_compressed=0` in the `backup_variables.txt` file inside the restored data directory. (Bug #27787988)
- When `mysqlbackup` performed sanity checks on InnoDB tablespaces and found a space ID mismatch for an FSP header and a page header, the name of the problematic tablespace was not given in the error report. (Bug #27752703)
- If an `ALTER TABLE` statement was executed on the server before an incremental backup was taken, a server restored with the backup on which the incremental backup was applied (using the `apply-incremental-backup` command) could not be started, as the `.ibd` file of the altered table was missing in the restored data. (Bug #27735134)
- After a server has been restored using an incremental backup created with the `--incremental-with-redo-log-only` option, it could not be started. (Bug #27722525)
- `mysqlbackup` issued a warning whenever the number of files specified in the system variable `innodb_data_file_path` of the server to be backed up exceeded 100. With this fix, a warning is issued only if the number of InnoDB data files to be opened exceeds the number specified by the system variable `innodb_open_files`. (Bug #27701402)
- Backups failed for a server that had been started with a value for `--innodb_log_file_size` different from the one the server was initiated with. (Bug #27571663)
- An `apply-incremental-backup` operation failed when individual tablespaces with relative file paths were involved. (Bug #27278876)
- In a [Group Replication](#) setting for MySQL servers, when changes were made to one group member and a backup was taken on another, the relay log for the replication applier was missing from the backup, so that the restored server could not be started. (Bug #25534078)

- When a compressed backup was restored with the `--innodb_data_home_dir` option pointing to a restore location outside of the data directory, `.ibd` files were still being copied into the data directory, causing an exception to be thrown at the attempt to start the restored server. (Bug #24826986)

## Changes in MySQL Enterprise Backup 8.0.11 (2018-04-19, General Availability)

MySQL Enterprise Backup 8.0.11 is the latest release for MySQL Enterprise Backup. It only supports MySQL Server 8.0.11. For MySQL server 5.7, please use MySQL Enterprise Backup 4.1, and for MySQL Server 5.6 and 5.5, please use MySQL Enterprise Backup 3.12.

- [Functionality Added or Changed](#)
- [Bugs Fixed](#)

### Functionality Added or Changed

- Offline backups are no longer supported by `mysqlbackup`. As a result, a number of options used for offline backup operations have been removed. See [What's New in MySQL Enterprise Backup 8.0?](#) for details. (Bug #27429244)
- The server option `--secure-auth`, deprecated since MySQL 5.7.5, is no longer supported by `mysqlbackup`. (Bug #27265328)
- Servers' use of the `keyring_encrypted_file` and `keyring_aws` plugins is now supported. See [Working with Encrypted InnoDB Tablespaces](#) for details. (Bug #27127898)
- Information on the executed GTIDs is now included in the `mysqlbackup` output and the backup log when the backed-up server has GTIDs enabled. (Bug #25978803)
- The binary log for a backed-up server, instead of being restored always to the data directory on the target server, is now restored by default to the same location it was found on the backed-up server. It can also be restored to a different location specified with the new `--log-bin` option. (Bug #25141738, Bug #83927)
- The relay log for a backed-up slave server, instead of being restored always to the data directory on the target slave server, is now restored by default to the same location it was found on the backed-up slave server. It can also be restored to a different location specified with the new `--relay-log` option. (Bug #25141738, Bug #83927)
- The `backup_history` table now includes a `server_uuid` column, which stores the value of the `server_uuid` of the backed up server.
- The options `--ssl` and `--ssl-verify-server-cert`, already deprecated in MySQL Enterprise Backup 4.1, have now been removed. Use the `--ssl-mode` option instead to configure the security mode of your connection to the server.
- [MySQL Enterprise Firewall](#) is now supported.
- A new option, `--tls-version`, specifies the protocols `mysqlbackup` permits for encrypted connections to MySQL servers.
- A file now tracks information of [external tablespaces](#) for a backup or restore in JSON format. See description for `tablespace_tracker` in [Types of Files in a Backup](#) for details.
- `mysqlbackup` could not restore the auto increment values in tables and the corruptions flags for indexes onto a server. The tasks are now made possible by having `mysqlbackup` copying onto the

target server blocks of redo logs that cover the duration from the latest checkpoint up to the backup end time, so that the restored server can, during the recovery phase at its first start, restore the auto increment values and the corruption flags using those blocks.

- The buffer size for cloud transfers can now be specified using the new `--cloud-buffer-size` option. See [Cloud Storage Options](#) for details.
- HTTP Basic Authentication and non-chunked transfer are now supported for backup and restore using OpenStack Swift-compatible object storage services. Two new options, `--cloud-basicauth-url` and `--cloud-chunked-transfer`, have been introduced for these purposes. See [Cloud Storage Options](#) for details.

## Bugs Fixed

- After restoring a full backup, if the following restore of an incremental backup changed the restore location of the undo log, either `mysqlbackup` hung, or the restored server failed to start. With this fix, `mysqlbackup` quits with a proper error (“Undo tablespace in the base backup not found”) in the situation.

Users should make sure the undo log location does not change between successive restores of a full and an incremental backups, or of two incremental backups. (Bug #27530916)

- When restoring an incremental backup containing encrypted InnoDB tables to a MySQL Community Server, the password provided to `mysqlbackup` with the `--encrypt-password` option was never validated, so that when the wrong password was given, the restore still succeeded, but the restored server could not be started. With this fix, `mysqlbackup` throws an error and stops the restore if the password is wrong. (Bug #27483449)
- `mysqlbackup` failed to backup to an Amazon S3 cloud storage. (Bug #27231229)
- An `apply-incremental-backup` operation corrupted the non-InnoDB files in its target backup when the sizes of those files are smaller in the incremental backup than in the target backup. (Bug #27001934)
- `mysqlbackup` could not establish a connection to the server with a Unix socket using the option `--protocol=SOCKET`. (Bug #26977679)
- A number of memory leaks were observed when running `mysqlbackup`. They have now been fixed. (Bug #26495834, Bug #26373259, Bug #26093563, Bug #26423820, Bug #26497245)
- After applying an incremental backup created with the `--incremental-with-redo-log-only` option to a full backup, the full backup's binary log became corrupted. (Bug #26403452)
- On macOS, `mysqlbackup` failed to determine the relay log file name correctly and thus could not back up the relay log for a slave server. (Bug #25574605)
- `mysqlbackup` only accepts values for `--ssl-mode` in upper case. With this fix, the option's value has become case insensitive. (Bug #25548088)

## Index

### Symbols

- `--help`, 5
- `--include-tables`, 3
- `--incremental-with-redo-log-only`, 5
- `--innodb_log_file_size`, 5

--show-progress, 4  
--ssl-fips-mode, 3  
--uncompress, 5  
--version, 5

## **A**

ALTER TABLE, 5  
Amazon S3, 7  
ANSI\_QUOTES, 5  
apply-incremental-backup, 3, 5, 7  
auto increment values, 7

## **B**

backup\_history table, 5  
binary log, 4, 7

## **C**

cloud operations, 4  
cloud-basicauth-url, 7  
cloud-buffer-size, 7  
cloud-chunked-transfer, 7  
cloud-oauth-token, 5  
cloud-storage-url, 5  
compressed backups, 5  
compressed incremental backup, 4  
compression, 4, 5  
corruption flags for indexes, 7

## **D**

disk full, 4

## **E**

encrypted InnoDB tables, 4, 7  
external tablespace, 7

## **G**

Group Replication, 3, 5  
GTID, 7

## **I**

Important Change, 5  
incremental backup, 3, 4, 5, 7  
incremental-with-redo-log-only, 7  
InnoDB cluster, 3  
innodb\_open\_files, 5  
innodb\_data\_file\_path, 4  
innodn\_data\_file\_path, 5  
innodn\_data\_home\_dir, 5

## **M**

MySQL Enterprise Firewall, 7

## O

OAuth, 5  
offline backup, 7  
OpenStack, 4

## R

relay log, 4, 7

## S

secure-auth, 7  
server upgrade, 3  
server\_uuid, 7  
sql\_mode, 5  
ssl-mode, 7

## T

tablespace ID check, 5  
tablespace\_tracker, 7  
tls-version, 7  
transparent page compression, 4

## U

undo log, 7