

Oracle Utilities Mobile Workforce Management

Database Administrator's Guide

Release 2.0.1

E17823-02

July 2010

Copyright © 2007, 2010, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS

Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle America, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third party content, products and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third party content, products or services.

Contents

Preface	i-i
Audience	i-i
Related Documents	i-i
Updates to this Documentation	i-i
Conventions	i-ii
Chapter 1	
Database Overview	1-1
Supported Database Platforms.....	1-2
Supported Platforms Summary Table.....	1-2
Support for Software Patches and Upgrades.....	1-2
Database Maintenance Rules.....	1-3
What Changes Are Permitted.....	1-3
What Changes Are Not Permitted	1-3
Chapter 2	
Database Installation	2-1
Installation Overview	2-2
Oracle Database Installation.....	2-3
Database Creation.....	2-3
Security Configuration.....	2-4
Populating Language Data.....	2-5
Initial Installation	2-5
Upgrade Install	2-8
Demo Install	2-10
Chapter 3	
Database Design	3-1
Database Object Standard.....	3-2
Categories of Data	3-2
Naming Standards.....	3-2
Column Data Type and Constraints.....	3-5
User Defined Code.....	3-5
System Assigned Identifier	3-5
Date/Time/Timestamp	3-5
Number	3-5
Fixed Length/Variable Length Character Columns.....	3-5
Null Constraints	3-5
Default Value Setting.....	3-5
Foreign Key Constraints	3-6
Standard Columns	3-6
Owner Flag	3-6
Version.....	3-6

Chapter 4

Database Implementation Guidelines	4-1
Configuration Guidelines.....	4-2
Index.....	4-2
Table Partitioning Recommendations.....	4-2
Storage Recommendations.....	4-2
Database Configuration Recommendations.....	4-2
Database Syntax.....	4-3
Database Initialization Parameters.....	4-3
Oracle Database Implementation Guidelines.....	4-4
Oracle Partitioning.....	4-4

Appendix A

Upgrades to the Oracle Utilities Application Framework V2.2.0.7 Database	A-1
Automatic Data Upgrade.....	A-2
Display/Expand Zones in Portal.....	A-2
Long Userid Support.....	A-2
Long Context Value on XAI Sender.....	A-2
Metadata For Translation.....	A-2
Online Help.....	A-2
Performance Metadata Flags.....	A-3
Precise Time for Holiday Dates.....	A-3
Portal Display Rule.....	A-3
Rownum in Explorer Zones.....	A-3
Support Child XML Storage.....	A-3
Secure Business Services and Service Scripts.....	A-4
Security On User Access.....	A-4
Timed Batch Jobs.....	A-4
Update Zone Parameter.....	A-4
Schema Change.....	A-5
New Tables.....	A-5
New Views.....	A-6
Dropped Tables.....	A-6
Unsupported Tables.....	A-6
Added Columns.....	A-6
Dropped Columns.....	A-8
Unsupported Table Columns.....	A-9
Column Format Change.....	A-9
Metadata Changes in FW for Successful Upgrade.....	A-10
New System Data.....	A-12
Algorithm Type.....	A-12
Algorithm.....	A-12
Application Service.....	A-12
Access Mode Added to Application Service.....	A-13
Batch Control.....	A-14
Business Object.....	A-14
FK Reference.....	A-14
Lookups.....	A-15
Maintenance Object.....	A-20
Script.....	A-21
To do Type.....	A-22
Portal.....	A-23
Portal Zone.....	A-23
UI Map.....	A-24
XAI Inbound Service.....	A-25

Zone Type.....	A-25
Zone.....	A-25

Appendix B

Upgrades to the Oracle Utilities Application Framework V4.0.2 Database	B-1
Automatic Data Upgrade	B-2
Display/Expand Zones in Portal	B-2
Schema Change.....	B-2
New Tables	B-2
Dropped Tables.....	B-2
Unsupported Tables	B-2
Added Columns	B-3
Dropped Columns	B-3
Unsupported Table Columns.....	B-3
Metadata Changes in FW for Successful Upgrade.....	B-3
New System Data	B-4
Algorithm Type	B-4
Algorithm	B-4
Application Service	B-4
Access Mode Added to Application Service.....	B-4
FK Reference.....	B-4
Lookups.....	B-4
Maintenance Object.....	B-5
Script	B-5
To do Type.....	B-5
Portal Zone	B-6
UI Map.....	B-6
Zone.....	B-6

Appendix C

Oracle Utilities Mobile Workforce Management System Table Guide	C-1
Development and Implementation System Tables	C-2

Appendix D

Oracle Application Framework System Table Guide.....	D-1
About the Application Framework System Tables	D-2
System Table Standards	D-2
Guidelines for System Table Updates.....	D-3
Business Configuration Tables.....	D-3
Development and Implementation System Tables.....	D-5
Oracle Utilities Application Framework Only Tables.....	D-19
System Table List	D-20

Appendix E

License and Copyright Notices	E-1
Third Party Products.....	E-1
Notice concerning usage of ANTLR.....	E-1
Notice concerning usage of Apache Software.....	E-1
Notice concerning usage of ASM.....	E-4
Notice concerning usage of CruiseControl.....	E-5
Notice concerning usage of dom4j	E-5
Notice concerning usage of Ehcache.....	E-6
Notices concerning usage of Hibernate and c3p0.....	E-7
Notice concerning usage of International Components for Unicode (ICU4J)	E-13
Notice concerning usage of fcrypt	E-13
Notice concerning usage of Jaxen	E-14
Notice concerning usage of JOSSO.....	E-15

Notice concerning usage of libjpeg.....	E-15
Notice concerning usage of libproj4.....	E-16
Notice concerning usage of libtiff.....	E-16
Notice concerning usage of MX4J.....	E-17
Notice concerning usage of PicoContainer.....	E-17
Notice concerning usage of QDox.....	E-18
Notice concerning usage of XStream.....	E-19
Notice concerning usage of Perl.....	E-19
Notice concerning usage of Mime-Base64 Perl Module.....	E-21
Notice concerning usage of Mime-Lite Perl Module.....	E-21
Notice concerning usage of DBD::DB2 Perl Module.....	E-21
Notice concerning usage of DBI Perl Module.....	E-23
Notice concerning usage of JCIP Annotations.....	E-23
Notice concerning usage of YUI Library.....	E-23

Preface

This guide provides instructions for installing and maintaining the database for Oracle Utilities Mobile Workforce Management.

This preface contains these topics:

- **Audience**
- **Related Documents**
- **Updates to this Documentation**
- **Conventions**

Audience

Oracle Utilities Mobile Workforce Management Database Administrator's Guide is intended for database administrators who will be installing and maintaining the database for Oracle Utilities Mobile Workforce Management.

Related Documents

For more information, see these Oracle documents:

- *Oracle Utilities Mobile Workforce Management Quick Install Guide*
- *Oracle Utilities Mobile Workforce Management Installation Guide*

Updates to this Documentation

This documentation is provided with the version of the product indicated. Additional and updated information about the operations and configuration of the product is available from the Knowledge Base section of My Oracle Support (<http://support.oracle.com>). Please refer to My Oracle Support for more information.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Chapter 1

Database Overview

This section provides an overview of the Oracle Utilities Mobile Workforce Management database, including:

- **Supported Database Platforms**
- **Database Maintenance Rules**

Supported Database Platforms

This section defines the platforms on which Oracle Utilities Mobile Workforce Management is verified to operate.

Supported Platforms Summary Table

Oracle Utilities Mobile Workforce Management is certified on the following platforms:

Platform	Database Version
AIX 6.1 TL4 (POWER 64-bit)	Oracle Database Server 11.2.0.1 (64-bit)
HP-UX 11.31 (Itanium 64-bit)	Oracle Database Server 11.2.0.1 (64-bit)
Oracle Enterprise Linux 5.4 (64-bit) x86_64 (64-bit)	Oracle Database Server 11.2.0.1 (64-bit)
Red Hat Enterprise Linux 5.4 (64-bit) x86_64 (64-bit)	Oracle Database Server 11.2.0.1 (64-bit)
Solaris 10 (SPARC 64-bit)	Oracle Database Server 11.2.0.1 (64-bit)
Windows Server 2008 SP2 (x86_64 64-bit)	Oracle Database Server 11.2.0.1 (64-bit)

Refer to My Oracle Support for additional details.

Support for Software Patches and Upgrades

Due to the ongoing nature of software improvement, vendors will issue patches and service packs for the operating systems, application servers and database servers on top of specific versions that Oracle Utilities Mobile Workforce Management has been tested with.

If it is necessary to apply an upgrade, please do that in a test environment prior to updating the Oracle Utilities Mobile Workforce Management production environment.

The only exception from this rule is Hibernate software. For this the exact version mentioned in this guide must be installed. Please always check with Oracle Utilities Mobile Workforce Management support prior to installing Hibernate updates.

Always contact Oracle Utilities Mobile Workforce Management support prior to applying vendor updates that do not guarantee backward compatibility.

Database Maintenance Rules

The database supplied with the product consists of the following elements:

- A set of users to administrate, execute and read the database schema provided.
- A set of database roles to implement security for each of the users provided.
- A schema containing the base database objects used by the product.

The installation of these components is outlined in the installation section of this document.

What Changes Are Permitted

During and after installation of the product the following changes may be performed by the database administrator personnel on site:

- Users supplied by product may be changed according to the site standards.
- Database objects may be added to the schema according to database naming standards outlined later in this document.
- Database views and indexes may be created against base database objects.
- Database storage attributes for base indexes and base tables may be changed according to site standards and hardware used.
- Tablespace names, attributes and locations may be changed according to site standards.
- Database topology (that is, base table/index to tablespace, tablespace to data file, datafile to location) may be altered according to tuning and/or site standards.
- Database triggers may be created against base database objects unless they attempt to contravene base data integrity rules.
- Database initialization and parameter settings may be altered to site standards unless otherwise advised by Oracle Support or outlined in this document.

What Changes Are Not Permitted

In order to maintain the operations of the product and upgradability, during and after installation of the product the following changes may *not* be performed by the database administrator personnel on site:

- Roles provided must not be altered in any way.
- Base objects must not be removed or altered in the following ways:
 - Columns in base tables must not be altered in anyway (altered, removed or added).
 - Columns in Indexes must not be altered or removed.
 - Tables must not be renamed or removed.
 - Base Views must not be renamed or removed.
 - Base indexes must not be removed.

Chapter 2

Database Installation

This section provides the steps required to install or upgrade the Oracle Utilities Mobile Workforce Management database, including:

- **Installation Overview**
- **Oracle Database Installation**

Installation Overview

Note. Refer to the *Oracle Utilities Mobile Workforce Management Installation Guide* for the hardware and software versions required for the installation on the Unix Server or Windows Server. This installation is for Oracle Utilities Mobile Workforce Management V2.0.1 and the upgrade of Oracle Utilities Mobile Workforce Management V2.0.0.0 or V2.0.0.1. to V2.0.1.

The following type of installation is available for Oracle Utilities Mobile Workforce Management:

- **Initial Install** - a database with no demo data.
- **Upgrade Install** - a database upgrade.
- **Demo Install** - a database populated with demo data.

Note: The database installation requires a supported version of the Java Development Kit to be installed on the Windows desktop where the install package is staged and run from. Refer to the Supported Platform section of the *Oracle Utilities Mobile Workforce Management Installation Guide* for the required version of Java.

For an Initial Install or Demo Install you will create an empty database on the Unix or Windows server and then populate the database with data. For a database Upgrade Install you will upgrade your current Oracle Utilities Mobile Workforce Management database.

Review the Storage.par file prior to Initial Install or Upgrade Install. Information in this file is used by CDXDBI while installing and upgrading the Oracle Utilities Mobile Workforce Management database objects.

For optimum storage allocation, DBAs should create multiple tablespaces with extents sized to store different types of tables/indexes. They can then edit this file before each upgrade and install process, to spread the tables and indexes across these tablespaces. Tables and indexes can be created in parallel by editing degree of parallelism. The default value is 1.

To provide additional information, the table names are included for each index as a comment.

Tablespace and parallel information for only the new objects is used. Therefore, for initial installs, information for each object should be reviewed. Be careful while editing this file. Make sure that the tablespace names being used exist in the database. Do not change the basic format of this file.

Note. Prior to the installation of the database schema for the product, please ensure that the Database Management System software is installed according to your site standards and the installation guide provided by the database vendor.

Also ensure that the Oracle Locator component is installed.

Oracle Database Installation

The following section outlines the instructions for installing the Oracle Database for Oracle Utilities Mobile Workforce Management.

Note: The installation tools outlined in this guide run on Windows and UNIX/Linux only. If the database server is installed on a platform not supported by the utilities then the site should use the Windows utilities to execute the installation.

Database Creation

This step is not required if you are performing a database upgrade from a previous version of the application.

Note: The Unix and Windows installs will create an empty database with the Oracle Locator component, Geocoder feature, at least one tablespace for storing the application objects before running the install. The default name of the application tablespace is CISTS_01. If you do not use the default name or want to spread the application objects across multiple tablespaces, you must edit the Storage.par file, supplied with the install package, before the installation process.

Unix

The files are located in MWM/DatabaseCreation/Unix.

1. FTP the contents of the Database Creation folder to a temporary directory on the UNIX server.
2. To create the database set the ORACLE_HOME and ORACLE_BASE variables.
3. Execute the utility cdxdba.plx by entering following command:

```
perl cdxdba.plx
```

4. The script will prompt for parameter values:
 - Enter the instance name (DEMO): DEMO
 - Enter ORACLE_BASE: the directory where the setup files for the database will be created (/orasw/app/oracle):
 - Enter ORACLE_HOME: the folder where the current version of Oracle software is installed (/orasw/app/oracle/product/):
 - Enter ORACLE_DATA: the directory where the data files for the database will be created (/db05/oradata):
 - Enter the character set for the database (UTF8):
5. Enter the values based on the settings of your database server. You can also accept the default values displayed if they match your database server settings. You will be prompted to confirm the settings and select Y or N to create the database.

```
ORACLE_SID: DEMO
ORACLE_HOME: /orasw/app/oracle/product/
ORACLE_BASE: /orasw/app/oracle
ORACLE_DATA: /db05/oradata
Character Set: UTF8
Do you want to continue (Y/N)?
```

6. Once the database has been created, you will be prompted with the questions:

```
Do you want to import a demo database dump into this database (Y/N)?
```

- Select N to exit the database utility.
- Select Y to import the Demo Install data.

For the Demo Install use the dump file exp_demo.dmp.

```
Do you want to import a demo database dump into this database (Y/N)? Y
```

- Enter the name of the dump file (exp_demo.dmp):
- Enter the name of the log file (exp_demo.log):

```
Ready to import the CISADM schema into the database, do you want to continue (Y/N)? Y
```

Note. Update the oratab, tnsnames.ora and listener.ora files for the new database and check the connectivity to this database from another server and from your desktop.

Windows

The files are located in MWM/DatabaseCreation/Windows. You should be logged in as a user who is a member of local ORA_DBA group on that server. The ORA_DBA group should have "administrator" privileges assigned to it.

1. To create a database, run the utility CDXDBA.exe located in the Windows folder.

The utility will display a list with the following options:

- E - Export a schema from the database
- R - Refresh a schema with a database dump.
- C - Create/Recreate a local database.
- H - See help for the command line options.

2. Select option C to create an empty database on your machine.

Follow the prompts to complete the install.

3. Once the database has been created you can exit the utility or select the R - Refresh a schema with a database dump file to load the Demo Install data.

Option R causes the utility to drop all the objects from the schema and import the schema from a database dump file.

For the Demo Install use the dump file exp_demo.dmp.

Note. Update the oratab, tnsnames.ora and listener.ora files for the new database and check the connectivity to this database from another server and from your desktop.

Security Configuration

The configuration utility and scripts are located in the Security folder.

Execute the OraGenSec.exe utility.

The script will prompt for parameter values:

```
Enter the application read-only user or Schema Owner in the database (e.g CISADM or CISREAD):
```

```
Enter the password for the user:
```

```
Enter the name of the Oracle Database: database name
```

Enter a comma-separated list of Oracle users in which synonyms need to be created (e.g. `cisuser,cisread`): `cisuser,cisread`

Select the following options:
 (A/a): Generate security for All objects in the Database (e.g. A or a for all objects)
 (O/o): Generate security for specific Objects inputted in this terminal (e.g. `CI_ACCT,CI_ACCT_K`)
 Generate security for specific objects generated from an input File (e.g. `Security_Objects.txt`)

The utility configures security for the CISADM schema objects.

Populating Language Data

At this point, the Oracle Utilities Mobile Workforce Management demo database is ready for use. Please note that this database contains data in the ENGLISH language only. If you use any other supported language, you must first run the NEWLANG batch program to duplicate the data entries for that language. For more information on running this batch program, refer to the User Documentation, Defining Background Processes.

You can also install the language specific demo data packages (if available) into the database. Please contact your Oracle representative to receive information on these packages

Initial Installation

This section describes the initial installation of the database.

Note: You must have a supported version of the Java Development Kit installed on the Windows desktop where you stage and run the database installation package. Refer to the *Oracle Utilities Mobile Workforce Management Installation Guide* for more information.

Database Script and Utilities Installation

Unzip the `database.zip` file to your local machine.

The database folder contains several files that will be referred to in the installation process.

Set up a Microsoft Windows desktop with the Oracle Client installed.

Create Database

The Initial installation requires the following to be installed before the installation can be started:

- A database must be created. Site standard techniques or tools may be used to create the database. The templates for creating the database are located under the relevant database version subdirectory of the "Database Creation" directory under:
 - `createdb.sql` - Create Database
 - `createdbcatalog.sql` - Build database catalog tables.
 - `createdbfiles.sql` - Create data files for tablespaces
 - `init.ora` - Sample initialization parameters for the database
 - `createcdxusers.sql` - Create users
 - `restartdb.sql` - DB restart
- The users and roles for the product. Templates for this activity are located under the relevant database version subdirectory of the "Database Creation" directory as `createcdxusers.sql`.

Note. Please alter a copy of the above files for site specific changes.

Note. The CDXDBA utility provided in the Database Creation folder may be used to automate the process. See "Database Creation" for more details.

Pre-Install Tasks

To enable the geocoder feature:

- If the Oracle database was created without using CDXDBA, make sure the Oracle Locator component is installed.
- Execute "MWM_Geocoder_install.sql" with a DBA privileged user from the SQL prompt from the Pre-Install folder under ORS.

Install

Install Oracle Utilities Application Framework V4.0.2 prior to Oracle Utilities Mobile Workforce Management 2.0.1.

The files for Oracle Utilities Application Framework installation are located in the FW folder

1. Install Base FW V4.0.2 by running the CdxDBI.exe from the Install-Upgrade folder under FW402.
2. Apply prerequisite Framework DB single fixes. See the *Oracle Utilities Mobile Workforce Management Installation Guide* for more details.

The files for the Initial Install of MWM 2.0.1 are located in the Install-Upgrade folder under ORS. To install the MWM database:

The process prompts you for the names of three database users:

- A user that will own the application schema (for example, CISADM).
- A user that has select/update/insert/delete (read-write) privileges to the objects in the application schema. The application will access the database as this user. (for example, CISUSER).
- A user with read-only privileges to the objects in the application schema. (for example, CISREAD).
- Location for jar files. (The Jar files are bundled with the database package.)
- Java Home (For example, C:\Java\jdk1.6.0_18)

Perform the following steps:

1. Run CDXDBI.exe from ORS/Install-Upgrade. The utility prompts you to enter values for the following parameters:
 - The name of the target database.
 - The password for the SYSTEM user account in the database (in silent mode).
 - The name of the owner of the Database Schema.
 - The password for the user (in silent mode).
 - The Oracle user with read-write privileges to the Database Schema.
 - The location of the Jar file.
 - Java Home.
2. If you chose to continue, CDXDBI first checks for the existence of each of the users specified and prompts for their password, default tablespace, and temporary tablespace, if they do not exist.

3. After setting up the roles and users, the utility continues upgrading schema and system data definitions. If an error occurs while executing an SQL or another utility, it logs and displays the error message and allows you to re-execute the current step.

The files for the Initial Install of MWM 2.0.1 are located in the Install-Upgrade folder under M1. To install the MWM database:

1. Run CDXDBI.exe from MWM/Install-Upgrade. The utility prompts you to enter values for the following parameters:
 - The name of the target database.
 - The password for the SYSTEM user account in the database (in silent mode).
 - The name of the owner of the Database Schema.
 - The password for the user (in silent mode).
 - The Oracle user with read-write privileges to the Database Schema.
 - The location of the Jar file.
 - Java Home.
2. If you chose to continue, CDXDBI first checks for the existence of each of the users specified and prompts for their password, default tablespace, and temporary tablespace, if they do not exist.
3. After setting up the roles and users, the utility continues upgrading the schema and system data definitions. If an error occurs while executing an SQL or another utility, it logs and displays the error message and allows you to re-execute the current step.

CDXDBI performs the following tasks:

1. Interacts with the user to collect information about the name of Oracle account that will own the application schema (for example, CISADM), password of this account, password of the SYSTEM account in the database, and the name of the Oracle account that the application user will use (for example, CISUSER), and the name of the Oracle account that will be assigned read-only privileges to the application schema (for example, CISREAD).
2. Connects to the database as SYSTEM account, checks whether the user already has the application schema installed to verify whether this is an initial installation.
3. Verifies whether the tablespace names already exist in Storage.par file (the process aborts, if not).
4. Installs the schema, installs the system data, and configures security.
5. Maintains upgrade log tables in the database.
6. Updates release id when the upgrade is completed successfully.
7. If an error occurs while executing a SQL script or another utility, it logs and displays the error message and allows you to re-execute the current step. Log files CDXDBI###.log are created in the same folder as CDXDBI and contains all the SQL commands executed against the database along with the results. The log files are incremental so that the results are never overwritten. If warning messages are generated during the upgrade, CDXDBI prompts the user at the end of the process. Users should check the log files to verify the warning messages. Warning messages are only alerts and do not necessary mean a problem exists.
8. Stores the Schema owner and password in the feature configuration table . The password is stored in encrypted format.

Post-Install Tasks:

Refer to **Populating Language Data** on page 2-5 if the application is to run in another language other than English.

The Following steps will import styles and maps in the specified database:

- Please execute ImportSDOThemes.bat with parameters
`ImportSDOThemes.bat -u CISADM -p <PASSWORD> -c <DATABASE NAME>`
- After importing themes/styles /GEOM Metadata (zz_user_sdo_themes/zz_user_sdo_styles), postImport.sql is invoked from target main schema. This will:
 - Insert new styles/themes/sdo_geom_metadata in USER_SDO_THEMES/USER_SDO_STYLES/USER_SDO_GEOM_METADATA
 - Drop ZZ_USER_SDO_THEMES, ZZ_USER_SDO_STYLES, ZZ_USER_SDO_GEOM_METADATA tables from target database.
 - Create domain key indexes

Database Statistics Generation

During an install process, new database objects may be added to the target database. Before starting to use the database, generate the statistics for these new objects.

Upgrade Install

The following section assumes an existing Oracle Utilities Mobile Workforce Management V2.0.0 installation on top of Oracle Utilities Application Framework V4.0.1 installation.

- Apply prerequisite Framework DB single fixes. See the *Oracle Utilities Mobile Workforce Management Installation Guide* for more details.

The files for the Upgrade Install of Oracle Utilities Mobile Workforce Management 2.0.1 are located in the Install-Upgrade folder.

Install

The CDXDBI process prompts for the names of three database users during this process:

- A user that will own the application schema (for example, CISSPLADM).
- A user that has read-write privileges to the objects in the application schema. The application will access the database as this user. (for example, CISSPLUSER).
- A user with read-only privileges to the objects in the application schema. (for example, CISSPLREAD).
- Location for jar files. (The Jar files are bundled with the database package.)
- Java Home (For example, C:\Java\jdk1.6.0_18)

Following are the steps involved:

1. Review and edit the Storage.par file to set the tablespace names. The instructions for editing the file are included in the file itself.
2. Run CDXDBI.exe from ORS/Install-Upgrade folder. The utility prompts you to enter values for the following parameters:
 - The name of the target database.
 - The password for the SYSTEM user account in the database (in silent mode).
 - The name of the owner of the Database Schema.
 - The password for the user (in silent mode)
 - The Oracle user with read-write privileges to the Database Schema

- The Oracle user with read-only privileges to the Database Schema
 - The location of the Jar file.
 - Java Home.
3. The utility at this point is ready to perform the upgrade install and prompts you for permission to start the process.
 4. If you chose to continue, CDXDBI first checks for the existence of each of the users specified earlier and prompts for their password, default tablespace, and temporary tablespace, if they do not exist.
 5. After setting up the roles and users, the utility continues upgrading schema and system data definitions. If an error occurs while executing an SQL or another utility, it logs and displays the error message and allows you to re-execute the current step.
 6. Run CDXDBI.exe From MWM/Install-Upgrade. The utility prompts you to enter values for the following parameters:
 - The name of the target database.
 - The password for the SYSTEM user account in the database (in silent mode).
 - The name of the owner of the Database Schema.
 - The password for the user (in silent mode)
 - The Oracle user with read-write privileges to the Database Schema
 - The Oracle user with read-only privileges to the Database Schema
 - The location of the Jar file.
 - Java Home.
 7. The utility at this point is ready to perform the upgrade install and prompts you for permission to start the process.
 8. If you chose to continue, CDXDBI first checks for the existence of each of the users specified earlier and prompts for their password, default tablespace, and temporary tablespace, if they do not exist.
 9. After setting up the roles and users, the utility continues upgrading schema and system data definitions. If an error occurs while executing an SQL or another utility, it logs and displays the error message and allows you to re-execute the current step.

CDXDBI performs the following tasks:

1. Interacts with the user to collect information about the name of Oracle account that will own the application schema (for example, CISSPLADM), password of this account, password of the SYSTEM account in the database, and the name of the Oracle account that the application user will use (for example, CISSPLUSER), and the name of the Oracle account that will be assigned read-only privileges to the application schema (for example, CISSPLREAD).
2. Connects to the database as SYSTEM account, checks whether the user already has the application schema installed to verify whether this is an upgrade installation.
3. Verifies whether the upgrade path from the current release id to the target release id is supported by the upgrade.
4. Verifies whether the tablespace names already exist in Storage.par file (the process aborts, if not).
5. Upgrades the schema, upgrades the system data, and configures security.
6. Maintains upgrade log tables in the database.

7. Updates release id when the upgrade is completed successfully.
8. If an error occurs while executing a SQL script or another utility, it logs and displays the error message and allows you to re-execute the current step. Log files CDXDBI###.log are created in the same folder as CDXDBI and contains all the SQL commands executed against the database along with the results. The log files are incremental so that the results are never overwritten. If warning messages are generated during the upgrade, CDXDBI prompts the user at the end of the process. Users should check the log files to verify the warning messages. Warning messages are only alerts and do not necessary mean a problem exists.
9. Stores the Schema owner and password in feature configuration table . The password will be stored in encrypted format.

Demo Install

Before the installation can be started:

- A database must be created. Site standard techniques or tools may be used to create the database. The templates for creating the database are located under the relevant database version subdirectory of the MWM/DatabaseCreation directory under :
 - createdb.sql - Create Database
 - createdbcatalog.sql - Build database catalog tables.
 - createdbfiles.sql - Create data files for tablespaces
 - init.ora - Sample initialization parameters for the database
 - createcdxusers.sql - Create Users
 - restartdb.sql - restart database
- The users and roles for the product. Templates for this activity are located under the relevant database version subdirectory of the "Database Creation" directory as createcdxusers.sql.

Note: Please alter a copy of the above files for site specific changes.

Note: The CDXDBA utility provided in the "Database Creation" folder may be used to automate the process.

Install

Complete the application **Database Creation** on page 2-3 to create the database and import the Demo Install data into the database.

The Database Creation contains the instructions for the import of the Demo Install data.

Chapter 3

Database Design

This section provides a standard for database objects such as tables, columns, and indexes, for products using the Oracle Utilities Application Framework. This standard helps smooth integration and upgrade processes by ensuring clean database design, promoting communications, and reducing errors. Just as Oracle Utilities Application Framework goes through innovation in every release of the software, it is also inevitable that the product will take advantage of various database vendors' new features in each release. The recommendations in the database installation section include only the ones that have been proved by vigorous QA processes, field tests and benchmarks. This section includes:

- **Database Object Standard**
- **Column Data Type and Constraints**
- **Standard Columns**

Database Object Standard

This section discusses the rules applied to naming database objects and the attributes that are associated with these objects.

Categories of Data

A table can belong to one of the three categories:

- Control (admin)
- Master
- Transaction

For purposes of physical table space design, metadata and control tables can belong to the same category.

Example of tables in each category:

- **Control:** SC_USER, CI_ADJ_TYPE, F1_BUS_OBJ
- **Master:** CI_PER, CI_PREM,
- **Transaction:** F1_FACT, CI_FT

All tables have the category information in their index name. The second letter of the index carries this information. See **Indexes** on page 3-3 for more information.

Naming Standards

The following naming standards must be applied to database objects.

Table

Table names are prefixed with the owner flag value of the product. For customer modification **CM** must prefix the table name. The length of the table names must be less than or equal to 30 characters. A language table should be named by suffixing **_L** to the main table. The key table name should be named by suffixing **_K** to the main table.

It is recommended to start a table name with the 2-3 letter acronym of the subsystem name that the table belongs to. For example, **MD** stands for metadata subsystem and all metadata table names start with **CI_MD**.

Some examples are:

- CI_ADJ_TYPE
- CI_ADJ_TYPE_L

A language table stores language sensitive columns such as a description of a code. The primary key of a language table consists of the primary key of the code table plus language code (LANGAGUE_CD).

A key table accompanies a table with a surrogate key column. A key value is stored with the environment id that the key value resides in the key table.

The tables prior to V2.0.0 are prefixed with CI_ or SC_.

Columns

The length of a column name must be less than or equal to 30 characters. The following conventions apply when you define special types of columns in the database.

- Use the suffix **FLG** to define a lookup table field. Flag columns must be CHAR(4). Choose lookup field names carefully as these column names are defined in the lookup table (CI_LOOKUP_FLD) and must be prefixed by the product owner flag value.
- Use the suffix **CD** to define user-defined codes. User-defined codes are primarily found as the key column of the admin tables.
- Use the suffix **ID** to define system assigned key columns.
- Use the suffix **SW** to define Boolean columns. The valid values of the switches are 'Y' or 'N'. The switch columns must be CHAR(1)
- Use the suffix **DT** to define Date columns.
- Use the suffix **DTTM** to define Date Time columns.
- Use the suffix **TM** to define Time columns.

Some examples are:

- ADJ_STATUS_FLG
- CAN_RSN_CD

Indexes

Index names are composed of the following parts:

[X][application specific prefix][C/M/T]NNN[P/S]n

- **X** - X is used as a leading character of all base index names prior to Version 2.0.0 of the framework. Now the first character of product owner flag value should be used instead of letter X. For client specific implementation index in Oracle, use CM.
- Application specific prefix could be C, F, T or another letter.
- **C/M/T** - The second character can be either C or M or T. C is used for control tables (Admin tables). M is for the master tables. T is reserved for the transaction tables.
- **NNN** - A three-digit number that uniquely identifies the table on which the index is defined.
- **P/S** - P indicates that this index is the primary key index. S is used for indexes other than primary keys. n is the index number, unique across all indexes on a given table (0 for primary and 1, 2, etc., for the secondary indexes).

Some examples are:

- XC001P0
- XT206S1
- CM206S2

Warning! Do not use index names in the application as the names can change due to unforeseeable reasons.

Oracle Implementations

The storage.par file that comes with the product allocates all base tables and indexes to the default tablespace CISTS_01. If you decide to allocate some tables or indexes outside of the default tablespace, then this has to be reflected in the storage.par file by changing the tablespace name from the default value to a custom value, according to the format shown below:

Format: Object Type:Object Name:Tablespace name:Parallel:Comments.

Where Parallel defines the number of threads, that Oracle DB Server will use to access a table or create an index . Default value is 1.

For instance, if a DBA decided to allocate table CI_ACCT in a tablespace MyTablespace, then they would have to change line 2 below to TABLE:CI_ACCT:MyTablespace:1

```
TABLE:CO_INSTALLATION:CISTS_01:1
TABLE:CL_ACCT:CISTS_01:1
...
etc.,
INDEX:XC001P0:CISTS_01:1  :prompt # CL_DV_TEST_TYPE_L
INDEX:XC002P0:CISTS_01:1  :prompt # CL_BANK_ACCOUNT
INDEX:XC003P0:CISTS_01:1  :prompt # CL_BANK
...
etc.
```

The cdxdbi process uses the storage.par file to place the new database objects into defined tablespaces. A tablespace referenced in the storage.par file must exist in the database.

The storage.par file has to be adjusted before each upgrade and/or new installation as required to allocate the tables and indexes across those tablespaces.

Table name is included as a comment for each of the indexes for clarity.

For initial installs, information for each object should be reviewed by a DBA. For upgrades, only tablespace information for the objects added in the new release needs to be reviewed by a DBA.

Be careful while editing this file. Make sure that the tablespace names being used exist in the database. Do not change the basic format of this file.

Sequence

The base sequence name must be prefixed with the owner flag value of the product.

Trigger

The base trigger name must be prefixed with the owner flag value of the product.

When implementers add database objects, such as tables, triggers and sequences, the name of the objects should be prefixed by CM. For example, Index names in base product are prefixed by X; the Implementer's index name must not be prefixed with X.

Column Data Type and Constraints

This section discusses the rules applied to column data type and constraints, and the attributes that are associated with these objects.

User Defined Code

User Defined Codes are defined as CHAR type. The length can vary by the business requirements but a minimum of eight characters is recommended. You will find columns defined in less than eight characters but with internationalization in mind new columns should be defined as CHAR(10) or CHAR(12). Also note that when the code is referenced in the application the descriptions are shown to users in most cases.

System Assigned Identifier

System assigned random numbers are defined as CHAR type. The length of the column varies to meet the business requirements. Number type key columns are used when a sequential key assignment is allowed or number type is required to interface with external software. For example, Notification Upload Staging ID is a Number type because most EDI software uses a sequential key assignment mechanism. For sequential key assignment implementation, the DBMS sequence generator is used in conjunction with Number Type ID columns.

Date/Time/Timestamp

Date, Time and Timestamp columns are defined physically as DATE in Oracle. Non-null constraints are implemented only for the required columns.

Number

Numeric columns are implemented as NUMBER type in Oracle. The precision of the number should always be defined. The scale of the number might be defined. Non-null constraints are implemented for all number columns.

Fixed Length/Variable Length Character Columns

When a character column is a part of the primary key of a table define the column in CHAR type. For the non-key character columns, the length should be the defining factor. If the column length should be greater than 10, use VARCHAR2 type in Oracle.

Null Constraints

The Non-null constraints are implemented for all columns except optional DATE, TIME or TIMESTAMP columns.

Default Value Setting

The rules for setting the database default values are as follows:

- When a predefined default value is not available, set the default value of Non-null CHAR or VARCHAR columns to blank except the primary key columns.
- When a predefined default value is not available, set the default value Non-null Number columns to 0 (zero) except the primary key columns.
- No database default values should be assigned to the Non Null Date, Time, and Timestamp columns.

Foreign Key Constraints

Referential integrity is enforced by the application. In the database do not define FK constraints. Indexes are created on most of Foreign Key columns to increase performance.

Standard Columns

This section discusses the rules applied to standard columns and the attributes that are associated with these objects.

Owner Flag

Owner Flag (OWNER_FLG) columns exist on the system tables that are shared by multiple products. Oracle Utilities Application Framework limits the data modification of the tables that have owner flag to the data owned by the product.

Version

The Version column is used to for optimistic concurrency control in the application code. Add the Version column to all tables that are maintained by a Row Maintenance program irrespective of the language used (COBOL or JAVA).

Chapter 4

Database Implementation Guidelines

The following section outlines the general implementation guidelines for the database components, including:

- **Configuration Guidelines**
- **Oracle Database Implementation Guidelines.**

Note: Refer to My Oracle Support for more information.

Configuration Guidelines

This section includes general recommendations for configuring various database objects and includes a brief syntax overview. It covers the general aspects of the database objects and does not cover any specific implementation requirements.

Index

Index recommendations specify points that need to be considered when creating indexes on a table.

1. Indexes on a table should be created according to the functional requirements of the table and not in order to perform SQL tuning.
2. The foreign keys on a table should be indexes.

In an Oracle Utilities Application Framework environment, always make sure that the optimization parameters are set as follows:

```
optimizer_index_cost_adj=1  
optimizer_index_caching=100
```

This will make sure that optimizer give a higher priority to index scans.

Table Partitioning Recommendations

Oracle Utilities has two recommendations for partitioning tables.

1. No partitioning for non-RAC environments.
2. Minimum of 'n' partitions for selective database objects, where 'n' is number of RAC nodes.

Storage Recommendations

This section specifies recommended options for storing the database objects.

SecureFile for Storing LOBs

Beginning with Oracle 11g, tables having fields with data type of CLOB or BLOBs should have the LOB Columns stored as SecureFiles.

- The storage options with SecureFiles should be CACHE and COMPRESS.
- The COMPRESS options make sure that LOB data is always stored in the compressed state.

See **Database Syntax** on page 4-3 for more information on SecurFiles.

Database Configuration Recommendations

This section specifies the recommended methods for configuring the database with a focus on specific functional area.

Large Redo Log File Sizes

The Redo Log files are written by the Log Writer Background process. These Log files are written in a serial manner. Once a Log File is full, a Log Switch occurs and the next Log file starts getting populated.

It is recommended that the size of the Redo Log files should be sufficiently high so that you do not see frequent Log Switches in the Alert logs of the database. Frequent Log Switches impact the IO performance and can be avoided by having a larger Redo log File size.

Database Syntax

SecureFile

```
CREATE TABLE <Table_Name>
  ( COLUMN1 ...,
    COLUMN2 (CLOB)
  )
LOB (COLUMN2) STORE AS SECUREFILE (CACHE COMPRESS);
```

Database Initialization Parameters

The recommended Initialization Parameters are given below. These parameters are a starting point for database tuning. An optimal value for a production environment may differ from one customer deployment to another.

db_block_size=8192

log_checkpoint_interval=10000

db_file_multiblock_read_count=8

transactions=3000

open_cursors=1200

optimizer_index_cost_adj=1

optimizer_index_caching=100

session_cached_cursors=50

trace_enabled=FALSE

db_files=1024

dbwr_io_slaves=10 (Only if Asynchronous IO is not Supported)

sessions=1528

sec_case_sensitive_logon=FALSE

processes=1000

dml_locks=4860

Oracle Database Implementation Guidelines

This section provides specific guidelines for implementing the Oracle database.

Oracle Partitioning

If you use a base index for the partitioning key, rename the index to CM**.

If you use the primary key index of the table as the partitioning key:

- Make the index non-unique.
- Primary constraints should still exist.

The upgrade on the partitioned table will work the best if the partitioning key is not unique. This allows the upgrade tool to drop the PK constraints if the primary key columns are modified and recreate the PK constraints without dropping the index.

Appendix A

Upgrades to the Oracle Utilities Application Framework V2.2.0.7 Database

This document describes the database upgrade process for the Oracle Utilities Application Framework database from V2.2.0.7 to V4.0.2. It highlights changes made to the administrative tables and how those changes should be applied to the data in order for a V2.2.0.7 database to work with the V4.0.2 application, and to preserve the business logic implemented in the previous version of the application. The changes that do not require data upgrade are not described in this document. The tasks that need to be performed after running the upgrade scripts are included.

The added functionality of V4.0.2 is not the scope of this documentation. The upgrade scripts do not turn on the newly added functionality by default. For new functionality, refer the V4.0.2 User Guides. In the last section of this document you will find a list of the new tables that are added in V4.0.2.

Automatic Data Upgrade

This section describes what the upgrade script will populate in new tables and columns to preserve the existing base product application functions of the previous version of Oracle Utilities Application Framework.

Display/Expand Zones in Portal

To allow the user to display or hide zones in the portal, we need to provide an extra field on the Field Maintenance Page of Portal Zone (CI_PORTAL_ZONE). The new field added to Portal Zone is called Display Switch (DISPLAY_SW). It defines a display switch value of Y or N to display or hide a zone within the portal.

Also to allow the user to expand or collapse the zones in the portal, we need to provide an extra field on the Field Maintenance Page of Portal Zone. The new field added to Portal Zone is called Zone Collapsed Switch (ZONE_COLLAPSED_SW). It defines a Zone Collapsed switch value of Y or N to collapse or display a zone within the portal.

As a part of the Upgrade Process DISPLAY_SW is set to 'Y' and ZONE_COLLAPSED_SW is set to 'N'.

Long Userid Support

To support Long Userid other than the fixed 8 Character Userid, a new column External Userid (EXT_USER_ID) is added to the User Table (SC_USER) Table. The External Userid column has unique values and it is mapped to Userid (USER_ID). Users are authenticated using External Userid and there after the Userid would be used by the Application. The External Userid (EXT_USER_ID) would be populated as Userid (USER_ID) wherever the External Userid is not populated as a part of the Upgrade Process.

Long Context Value on XAI Sender

A new field Context Value Long (F1_CTXT_VAL_LONG) is added to XAI Sender Table (CI_XAI_SNDR_CTX). This new field is a longer version of the existing field CTXT_VAL. CTXT_VAL supports only 50 characters. To accommodate the long Value for the SOAP Action URL (for making third party web service calls) and long encrypted passwords, the new column is added on the XAI Sender Table. The existing column CTXT_VAL on this table would be unsupported. For this to be possible, as a part of upgrade script, all the current data in CTXT_VAL column would be updated into F1_CTXT_VAL_LONG column. There after the column CTXT_VAL would be updated with a single Blank.

Metadata For Translation

Two new Flags Translatable Flag (F1_TRANSLATABLE_FLG) and Extract for Translation Flag (F1_EXTRACT_TRANSLATION_FLG) are added to aid in Translation, which was originally handled in a Text file. Translatable Flag is added in CI_MD_FLD and indicates whether we translate the label on this field or not and the valid values are yes (YES) and no (NO). Extract for Translation Flag is added to CI_MD_TBL and CI_MD_TBL_FLD and has a valid values of yes (YES) and no (NO). A table or a table field, which is marked for extraction, would be included in the extraction process to be sent to WPTG. As a part of upgrade process the flag F1_TRANSLATABLE_FLG is defaulted to yes (YES) and F1_EXTRACT_TRANSLATION_FLG is defaulted to no (NO).

Online Help

To follow Oracle documentation standards, TUGBU Word documentation for CCB and Framework is converted into DITA XML format. This will involve Conversion of old word files and indexes to DITA xml, Online help generation using DITA open toolkit and Integration of the

new online help with Framework. The DITA documentation architecture requires small individual topics that are built up into topic hierarchies. To support this for Help related Navigation keys in CI_MD_NAV Table, the URL (field- URL_OVRD) is updated based on the set naming strategy.

Performance Metadata Flags

Two new Flags Cache Flag (CACHE_FLG) and Key Validation Flag (KEY_VALIDATION_FLG) are added to the Metadata Table (CI_MD_TBL). The Cache Flg will enable Caching of the Table and Key Validation Flag determines if Key Uniqueness is being issued by Framework before Inserting into the database. The valid values for cache flag are not Cached (NONE) and cachedForBatch (BTCH). The valid values for key validation flag are always (ALL), never (NONE) and onlineOnly (ONLI). As a part of the upgrade process CACHE_FLG would be populated with a default value of NONE and for KEY_VALIDATION_FLG it would be populated with ALL, for product owned data as well.

Precise Time for Holiday Dates

Two new Fields named Holiday Start Date (F1_HOLIDAY_START_DTTM) Holiday End Date (F1_HOLIDAY_END_DTTM) are added to the Metadata Table (CI_CAL_HOL). This will help in defining the holiday begin and end dates with time. This is different from the existing Holiday dates where we just specify the date. As a part of the upgrade process the field F1_HOLIDAY_START_DTTM would be populated with HOLIDAY_DT with Time as 00:00:00. For F1_HOLIDAY_END_DTTM the default value would be F1_HOLIDAY_START_DTTM+24 Hours.

Portal Display Rule

A new flag Allow User Configuration (USER_CONFIG_FLG) is added to the Portal Table (CI_PORTAL). User Configuration Flag indicates if a user is allowed to have individual control of the zones on this portal. This flag is defaulted to 'Y' for all existing Portals during the upgrade process. If the Override User Configuration flag on CI_PORTAL is Blank and Allow User Configuration Flag is set to Y, then display the Portal, else if it set to 'N' then the Portal should not get displayed.

Rownum in Explorer Zones

The number of Records retrieved by the Query in Data Explorer Zone Types would be limited. This is because the entire result is neither required to be displayed and nor required for downloads. The existing Zone Parameter Values for Zone Type-Data Explorer and Zone Type Parameter-NBROFROWS and ROWSTOEXPORT would be updated. As a part of upgrade process when Zone Parameter values do not exists then limitFetch=false would be set. For existing non-blank Zone Parameter values, limitFetch=false count=ZONE_PARM_VAL would be updated.

Support Child XML Storage

The child list elements are allowed to contain XML mappings to XML storage fields. The existing implementation of Business Objects storing any XML mapped fields under groups stored the field in the physical storage field as a top-level xml element. This may result in conflict in their storage. So the new Implementation will store the fields like so in the physical CLOB field. The existing Business Object schemas that exist will remain. As a part of Upgrade Process an attribute "fwRel="2" would be added to the root "schema" to provide backward compatibility to already existing Business Object schemas.

Secure Business Services and Service Scripts

Application Services (APP_SVC_ID) is added to Business Service Table (F1_BUS_SVC). Based on the Application Service, the ability to execute a Business Service and a Service Script by different user groups would be controlled. As a part of upgrade process the APP_SVC_ID column for existing Business Services (F1_BUS_SVC) and Service scripts (CL_SCR) would be populated with a Default Application Service (F1-DFLTAPS) where there is no Application Service associated. The default Application Service would be added to all the existing User groups and the 'Execute' Access Mode on this Service would be granted to all the user groups.

Security On User Access

A new flag User Enable (USER_ENABLE_FLG) is added to user Table (SC_USER). The valid values are Enable (ENBL) and Disable (DSBL). When a user depart or is no longer associated with the system then the BO Web service after confirming the status of the user and immediately deny user access to all "authorized" application services when the user is disabled. As a part of the upgrade process the USER_ENABLE_FLG will be set to 'ENBL' for the existing users in the Users table(SC_USER).

Timed Batch Jobs

A new flag Batch Control Type (F1_BATCH_CTRL_TYPE_FLG) is added to Batch Control Table (CL_BATCH_CTRL). The valid values are Not Timed (F1NT) and Timed (F1TM). Along with this there are additional new columns added to the Batch Control Table. Based on this the batch controls will be automatically initialized on a timed basis. As a part of the upgrade process the F1_BATCH_CTRL_TYPE_FLG will be set to 'F1NT' for the existing data in the Batch Control Table.

Update Zone Parameter

A new field Zone Parameter Value override (ZONE_PARM_VAL_OVRD) is added to zone parameter Table (CL_ZONE_PRM). The users would be able to override the existing value for Zone Parameter. For this to be possible, as a part of upgrade script, all Zone Type Parameters with usage as zone, which are not found in Zone parameter, a record needs to be inserted in Zone Parameter with Zone Parameter value as blank.

Schema Change

New Tables

The following new tables are added to Oracle Utilities Application Framework V4.0.2.

Tables	Description
CI_BATCH_CTRL_ALG	Batch Control Algorithm
F1_BUS_OBJ_STATUS_RSN	Business Object Status Reason
F1_BUS_OBJ_STATUS_RSN_CHAR	Business Object Status Reason Characteristic
F1_BUS_OBJ_STATUS_RSN_L	Business Object Status Reason Language
F1_EXT_LOOKUP_VAL	Extendable Lookup
F1_EXT_LOOKUP_VAL_L	Extendable Lookup Language
F1_GEN_PROC	F1_GEN_PROC
F1_GEN_PROC_K	F1_GEN_PROC_K
F1_MANAG_CONTENT	Managed Content
F1_MANAG_CONTENT_L	Managed Content Language
F1_MST_CONFIG	Master Configuration. Added in FW 22
F1_REQ	Request
F1_REQ_K	Request Key
F1_REQ_LOG	Request Log
F1_REQ_LOG_PARM	Request Log Parameter
F1_REQ_TYPE	Request Type
F1_REQ_TYPE_L	Request Type Language
F1_REQ_TYPE_LOG	Request Type Log
F1_REQ_TYPE_LOG_PARM	Request Type Log Parameter
F1_SYNC_REQ	F1_SYNC_REQ
F1_SYNC_REQ_CHAR	F1_SYNC_REQ_CHAR
F1_SYNC_REQ_K	F1_SYNC_REQ_K
F1_SYNC_REQ_LOG	F1_SYNC_REQ_LOG
F1_SYNC_REQ_LOG_PARM	F1_SYNC_REQ_LOG_PARM

New Views

The following new Views are added to Oracle Utilities Application Framework V4.0.2.

View	Description
CI_USR_ACC_GRP_VW	Access Group by User View

Dropped Tables

The following tables are dropped in this release.

- CI_SCR_STEP_K

Unsupported Tables

The following tables would be deprecated in a future release.

- CI_XAI_SVC_VERS (L)
- CI_MODULE

Added Columns

The following Table Columns are added to Oracle Utilities Application Framework V4.0.2.

Table	Column	Required	Upgrade Note
CI_BATCH_CTRL	BATCH_LANGUAGE_CD	N	Timed Batch Jobs
CI_BATCH_CTRL	BATCH_THREAD_CNT	N	Timed Batch Jobs
CI_BATCH_CTRL	EMAILID	N	Timed Batch Jobs
CI_BATCH_CTRL	F1_BATCH_CTGY_FLG	N	Timed Batch Jobs
CI_BATCH_CTRL	F1_BATCH_CTRL_TYPE_FLG	Y	Timed Batch Jobs
CI_BATCH_CTRL	F1_TIMER_ACTIVE_FLG	N	Timed Batch Jobs
CI_BATCH_CTRL	MAX_COMMIT_RECORDS	N	Timed Batch Jobs
CI_BATCH_CTRL	TIMER_INTERVAL	N	Timed Batch Jobs
CI_BATCH_CTRL	TRC_PGM_END_SW	N	Timed Batch Jobs
CI_BATCH_CTRL	TRC_PGM_STRT_SW	N	Timed Batch Jobs
CI_BATCH_CTRL	TRC_SQL_SW	N	Timed Batch Jobs
CI_BATCH_CTRL	TRC_STD_SW	N	Timed Batch Jobs
CI_BATCH_CTRL	USER_ID	N	Timed Batch Jobs
CI_BATCH_JOB	BATCH_NBR	N	Timed Batch Jobs

Table	Column	Required	Upgrade Note
CI_CAL_HOL	F1_HOLIDAY_END_DTTM	Y	Precise Time for Holiday Dates
CI_CAL_HOL	F1_HOLIDAY_START_DTTM	Y	Precise Time for Holiday Dates
CI_FK_REF	ZONE_CD	N	
CI_INSTALL_PROD	PROD_TYPE_FLG	N	
CI_MD_FLD_L	DESCRLONG_OVRD	N	
CI_MD_FLD	F1_TRANSLATABLE_FLG	Y	Metadata for Translation
CI_MD_FLD	F1_TRANSLATION_CONTEXT	N	Metadata for Translation
CI_MD_TBL	CACHE_FLG	Y	Performance Metadata Flags
CI_MD_TBL	KEY_VALIDATION_FLG	Y	Performance Metadata Flags
CI_MD_TBL_FLD	F1_EXTRACT_TRANSLATION_FLG	Y	Metadata for Translation
CI_MD_TBL_FLD	F1_TRANSLATION_CONTEXT	N	Metadata for Translation
CI_MD_TBL	F1_EXTRACT_TRANSLATION_FLG	Y	Metadata for Translation
CI_MD_TBL	F1_TRANSLATION_CONTEXT	N	Metadata for Translation
CI_MSG	F1_TRANSLATION_CONTEXT	N	Metadata for Translation
CI_PORTAL	USER_CONFIG_FLG	Y	Portal Display Rule
CI_PORTAL_ZONE	SORT_SEQ	N	Portal Display Rule
CI_PORTAL_ZONE	SORT_SEQ_OVRD	N	Portal Display Rule
CI_PORTAL_ZONE	ZONE_REFRESH_PERIOD	N	
CI_PORTAL_ZONE	DISPLAY_SW	N	Display/Expand Zones in Portal
CI_PORTAL_ZONE	ZONE_COLLAPSED_SW	N	Display/Expand Zones in Portal
CI_TIME_ZONE	F1_TIMEZONE_NAME	Y	
CI_TIME_ZONE_L	DFLT_TIME_ZONE_LABEL	N	

Table	Column	Required	Upgrade Note
CI_TIME_ZONE_L	SHIFT_TIME_ZONE_LABEL	N	
CI_USR_ZONE	ZONE_REFRESH_PERIOD	N	
CI_XAI_SNDR_CTX	F1_CTXT_VAL_LONG	Y	Long Context Value on XAI Sender
CI_ZONE_L	DESCRLONG_OVRD	N	Update Zone Parameter
CI_ZONE_PRM	ZONE_PARM_VAL_OVRD	N	Update Zone Parameter
F1_BNDL_ENTITY	USER_ID	N	
F1_BUS_OBJ_STATUS	STATUS_REASON_FLG	N	
F1_BUS_SVC	APP_SVC_ID	Y	Secure Business Services and Service Scripts
F1_DATA_AREA	F1_EXT_DATA_AREA_CD	N	
F1_FACT	BO_STATUS_REASON_CD	N	
F1_FACT_LOG	BO_STATUS_REASON_CD	N	
SC_USER	EXT_USER_ID	Y	Long Userid Support
SC_USER	TIME_ZONE_CD	N	
SC_USER	F1_SECURITY_HASH	N	Long Userid Support
SC_USER	USER_ENABLE_FLG	N	Security on User Access

Dropped Columns

The following columns are dropped in this release.

- CI_PORTAL: USER_CONFIG_OVRD_FLG column.
- F1_MAP_L: HTML_DEFN column.
- CI_XAI_SNDR_CTX: CTXT_VAL column.
- CI_XAI_IN_SVC_L: DESCR254 column.
- CI_SCR_STEP, CI_SCR_STEP_L, CI_SCR_PRMP, CI_SCR_PRMP_L, CI_SCR_FLD_MAP: SCR_STEP_ID column.

Unsupported Table Columns

These columns will be deprecated in a future release.

- CI_XAI_IN_SVC: XAI_VERSION_ID column is not used.
- CI_XAI_JDBC_CON: DATABASE_NAME column is not used.

Column Format Change

Table Name	Column Name	From	To
CI_ALG_L	DESCR50	VARCHAR2: 50	VARCHAR2: 100
CI_ALG_TYPE_L	DESCR50	VARCHAR2: 50	VARCHAR2: 100
CI_BATCH_CTRL_P_L	DESCR50	VARCHAR2: 50	VARCHAR2: 100
CI_MD_MENU_ITEM_L	DESCR50	VARCHAR2: 50	VARCHAR2: 100
CI_MD_MENU_L	DESCR50	VARCHAR2: 50	VARCHAR2: 100
CI_MSG_L	MESSAGE_TEXT	VARCHAR2: 100	VARCHAR2: 254
CI_MSG_L	MESSAGE_TEXT_OVRD	VARCHAR2: 100	VARCHAR2: 254
CI_NT_DWN_PROF_L	DESCR50	VARCHAR2: 50	VARCHAR2: 100
CI_NT_DWN_TYPE_L	DESCR50	VARCHAR2: 50	VARCHAR2: 100
CI_NT_UP_XTYPE_L	DESCR50	VARCHAR2: 50	VARCHAR2: 100
CI_NT_XID_L	DESCR50	VARCHAR2: 50	VARCHAR2: 100
CI_SYSDATA_LOG	PK_VAL1	VARCHAR2: 50	VARCHAR2: 300
CI_SYSDATA_LOG	PK_VAL2	VARCHAR2: 50	VARCHAR2: 300
CI_SYSDATA_LOG	PK_VAL3	VARCHAR2: 50	VARCHAR2: 300
CI_SYSDATA_LOG	PK_VAL4	VARCHAR2: 50	VARCHAR2: 300
CI_SYSDATA_LOG	PK_VAL5	VARCHAR2: 50	VARCHAR2: 300
CI_XAI_JDBC_CON	DATABASE_PASS_WORD	VARCHAR2: 32	VARCHAR2: 64
CI_WF_EVT_TYPE_L	DESCR50	VARCHAR2: 50	VARCHAR2: 100
Change Done Only In Metadata	ADDRESS1	VARCHAR2: 64	VARCHAR2: 254
Change Done Only In Metadata	ADDRESS2	VARCHAR2: 64	VARCHAR2: 254
Change Done Only In Metadata	ADDRESS3	VARCHAR2: 64	VARCHAR2: 254

Table Name	Column Name	From	To
Change Done Only In Metadata	ADDRESS4	VARCHAR2: 64	VARCHAR2: 254

Metadata Changes in FW for Successful Upgrade

The Following Metdata is changed in FW40 for a successful Upgrade.

Metadata Description	Action Items for Products
ADDRESS1, ADDRESS2, ADDRESS3 and ADDRESS4 Fields are going to be set as FW owned during upgrade. The DataType would be set as VARCHAR2(254 BYTE).	Products that upgrade to FW40 need to make sure that the physical tables should have these columns of length 254.
The label of ADDRESS4 field is changed to 'Address 4	'Products that upgrade to FW40 need to make sure that there would be a new label for Address4 field.
BO_DATA_AREA, CITY, COUNTY, GEO_CODE, HOUSE_TYPE, IN_CITY_LIMIT, NUM1, NUM2 and POSTAL would be FW owned.	NONE
The Label of GEO_CODE field is changed to 'Geographical Code	'Products that upgrade to FW40 need to make sure that there would be a new label for GEO_CODE field.
XAI_ENV_HNDL_ID = 'DefaultHnd' in CI_XAI_ENV_HNDL Table would be FW owned.	NONE
Lookup Field HOUSE_TYPE would be FW owned.	NONE
Lookup Field Value- DFLT for field ENV_TYPE_FLG would be FW owned	NONE
Lookup Field Values- APTF and FPNM for field SENDER_CTXT_FLG would be FW owned.	NONE
ACCT_ID, PER_ID and PREM_ID fields are removed from FW. These fields would be now C1 owned.	Products that upgrade to FW40 need to make sure that these fields would be now C1 owned. During FW40 upgrade in BI these fields should be set as 'BI' owned. If they do not need these fields then it needs to be removed from their environment.
The label of NUM1 field is changed to 'Number 1	'Products that upgrade to FW40 need to make sure that there would be a new label for NUM1 field.
ACTION_FLG (Lookup) and EFF_DT fields are promoted to FW.	Products that upgrade to FW40 need to make sure that these fields would now be F1 owned.

Metadata Description	Action Items for Products
TST_COMP_TYP_CD is made CM owned in FW	Products that upgrade to FW40 need to make sure that if they have this field as F1 owned then it would be deleted. This field is moved to CCB and is related to BUG-6698188
Lookup Field- ACCESS_MODE and Field_Value- 'PE' would be set as F1 owned	Products that upgrade to FW40 need to make sure that the field value-'PE' would now be F1 owned for field name-'ACCESS_MODE'.
Field TRANS_BUS_OBJ_CD would be FW Owned.	Products that upgrade to FW40 need to make sure that this Field would now be F1 owned.
View CI_USR_ACC_GRP_VW would be F1 Owned	Products that upgrade to FW40 need to make sure that this view would now be F1 owned.
CI_SCRIPTS Zone is deleted from FW. Also for CI_TODO Zone the record with Zone Parameter name as CACHE_DATA is made FW owned with value as 'Y'	'ETM , CCB and BI needs to care about this. The FW 402 upgrade scripts will handle this.
INPUT_OPT_TYPE is deleted from FW	Products that upgrade to FW40 need to make sure that these fields would be now C1 owned. During FW40 upgrade in BI these fields should be set as 'BI' owned. If they do not need these fields then it needs to be removed from their environment.

New System Data

This section lists the new system data that are added for business process configuration.

Algorithm Type

The following algorithm types are new to V4.0.2.

Algorithm Type	Description
F1-MTR-EM	To Do Summary Email Monitor.
F1-ORAGEOCD	Oracle Spatial Geocoding
F1-REQ-INF	Request Information
F1-REQTY-VAL	Request Type Validation
F1-GEN-BOMNJ	Generic Business Object Status Monitor Java
F1-SMSEND	Send SMS Message Using Oracle BPEL
F1-GENPRINFO	Maintenance Object - Information
F1-TD-SM-EM	Email Users on Outstanding To Dos

Algorithm

The following Algorithms are Framework Owned system data in V4.0.2.

Algorithm	Description
F1-AT-RQ	Transition to Default Next Status
F1-AT-RQJ	Transition to Default Next Status Using Java Based Algorithm Type
F1-GENPRINFO	General Process
F1-MTR-EM	To Do Summary Email Monitor
F1-ORAGEOCD	Oracle Spatial Geocoding
F1-REQ-INF	Request Information
F1-REQTY-VAL	Request Type Validation
F1-SMSSNDBPL	Oracle Sms Send
F1-TD-SM-EM	Email Users on Outstanding To Dos

Application Service

The following Application Services are new to V4.0.2.

Application Service	Description
ALGDESCRSERVICE	Algorithm Description

Application Service	Description
F1-APAYEXPCRTYPEBOAS	Request Type - To Do Summary Email Type
F1-DFLTAPS	Default Execution Application Service
F1-EXPUSERSREQBOAS	Request - To Do Summary Email
F1-GENPROC	General Process Maintenance Object
F1ADMIN	System Admin Functions via Browser Client
F1APPSEC	Application Security Portal
F1BORFOL	Business Object Status Reason Portal
F1CONFIGLOG	Show User Config Log (Debugging Tool)
F1DEBUG	Debug Option Access via Browser Client
F1EMHLAU	Embedded Help
F1EXLKP	Extendable Lookup
F1EXLKPS	Extendable Lookup Query
F1LCAMRP	Request MO
F1LEXTLKUP	Extended Lookup Value
F1LRACTN	Request Type - Retrieve Action Details for Display
F1LTAMTP	Request Type MO
F1REQ	Request
F1REQTYP	Request Type
F1STREAS	Status Reason
F1SUBRQQ	Request Query
F1TBLEXC	Translatable Strings Exceeding Capacity
F1UIZONE	Context Sensitive Zone
FWLSTRJP	Status Reason MO
FWLTMGCT	Managed Content

Access Mode Added to Application Service

The following Access Mode is added to existing Application Services and is new to V4.0.2.

Application Service	Description	Access Mode
CILTUSEP	User	Enable/Disable (ENBL)
CILTWSDP	Feature Configuration	Super User (F1SU)

Batch Control

The following Batch Controls are new to V4.0.2.

Batch Control	Description
F1-ARQPR	Request Monitor
F1-REQTY	Request Type Monitor
F1-SUBRQ	Request Monitor (Deferred)

Business Object

The following Business Objects are Framework Owned system data in V4.0.2.

Business Object	Description
F1-BOStatusReason	Business Object Status Reason
F1-COUNTRY	Country BO
F1-ContextZonePhysicalBO	Physical BO for Context Sensitive Zone
F1-ExtLkpPhysicalBO	Physical BO for Extended Lookup
F1-Installation	Installation Options - Framework
F1-ManagedContPhysicalBO	Physical BO for Managed Content
F1-StatusReasonPhysicalBO	Physical BO for Status Reason
F1-ToDoSumEmailReq	To Do Summary Email Request
F1-ToDoSumEmailTyp	To Do Summary Email
F1-User	User
F1-XAI_Inbound_Service	XAI Inbound Service

FK Reference

The following FK References are new to V4.0.2.

FK Reference	Description
F1-ACCGP	Access Group
F1-ACTTY	Request Type
F1-BOSRC	BO with Search Zone
F1-BUS	Business Object
F1-CAL	Work Calendar
F1-CNTRY	Country
F1-CTXZN	Context Sensitive Zone
F1-CURCY	Currency
F1-DASRC	Data Area with Search Zone

FK Reference	Description
F1-DISPR	Display Profile
F1-EXLKP	Extendable Lookup value list
F1-EXLKU	Extendable Lookup
F1-GENPR	General Process
F1-MANCT	Managed Content
F1-MDSO	Meta-data Search Object
F1-PHONE	Phone Type
F1-REQTY	Request Type
F1-SCSRC	Script with Search Zone
F1-STRSN	Status Reason
F1-SUBRQ	Request
F1-TZONE	Time Zone
F1-UISRC	UI Map with Search Zone
F1-USSRC	User Id With Search Zone
F1-XAIAD	XAI Adapter
F1-XAICL	XAI Class
F1-XAIEH	XAI Envelope Handler
F1-XAIEX	XAI Executer
F1-XAIFM	XAI Format
F1-XAIRC	XAI Receiver
F1-XAISV	XAI Inbound Service
F1-ZONHD	Zone Type
F1SR-MO	MO Option - Status Reason

Lookups

The following Lookups are added to Oracle Utilities Application Framework V4.0.2.

Lookup Field Name	Field Value	Language	Description
ACCESS_MODE	ENBL	ENG	Enable/Disable
ACCESS_MODE	F1AC	ENG	Active
ACCESS_MODE	F1IN	ENG	Inactive
ACCESS_MODE	F1SU	ENG	Super User
ACCESS_MODE	PE	ENG	Pending

Lookup Field Name	Field Value	Language	Description
ALG_ENTITY_FLG	F1GS	ENG	Installation - Address Geocoding
ALG_ENTITY_FLG	F1MA	ENG	Maintenance Object - Audit
ALG_ENTITY_FLG	F1SR	ENG	Installation - SMS Receive
ALG_ENTITY_FLG	F1SS	ENG	Installation - SMS Send
BUS_OBJ_OPT_FLG	F1PD	ENG	Request Preview Service Script
BUS_OBJ_OPT_FLG	F1PV	ENG	Request Preview Map
CACHE_FLG	BTCH	ENG	Cached for Batch
CACHE_FLG	NONE	ENG	Not Cached
CHAR_ENTITY_FLG	F1AR	ENG	Request Log
CHAR_ENTITY_FLG	F1RT	ENG	Request Type Log
DEST_FLD_TYPE_FLG	GBL	ENG	Global Context
DEST_FLD_TYPE_FLG	PRTC	ENG	Portal Context
EXT_DATA_TYPE_FLG	DUR	ENG	Duration
EXT_SYS_TYP_FLG	F1CR	ENG	Application Context Root
EXT_SYS_TYP_FLG	F1DB	ENG	Database Connection Information
EXT_SYS_TYP_FLG	F1SS	ENG	SMS Send Configuration
F1-DELETEME	F1IA	ENG	Image Accessibility
F1-DELETEME	F1LG	ENG	System Data Logging Enabled
F1DB_OPT_TYP_FLG	F1DP	ENG	Schema Password
F1DB_OPT_TYP_FLG	F1DU	ENG	Schema Owner
F1SS_OPT_TYP_FLG	F1OP	ENG	Operation Name
F1SS_OPT_TYP_FLG	F1PT	ENG	Port Type
F1SS_OPT_TYP_FLG	F1PW	ENG	Password
F1SS_OPT_TYP_FLG	F1SN	ENG	Service Name
F1SS_OPT_TYP_FLG	F1SU	ENG	Server URL

Lookup Field Name	Field Value	Language	Description
F1SS_OPT_TYP_FLG	F1UN	ENG	User Name
F1_BATCH_CTGY_FLG	F1ADG	ENG	Ad Hoc
F1_BATCH_CTGY_FLG	F1CVG	ENG	Conversion
F1_BATCH_CTGY_FLG	F1EXG	ENG	Extract
F1_BATCH_CTGY_FLG	F1MNG	ENG	Monitor
F1_BATCH_CTGY_FLG	F1OVG	ENG	Object Validation
F1_BATCH_CTGY_FLG	F1PRG	ENG	Process What's Ready
F1_BATCH_CTGY_FLG	F1RIG	ENG	Referential Integrity
F1_BATCH_CTGY_FLG	F1TDG	ENG	To Do Entry
F1_BATCH_CTRL_TYPE_FLG	F1NT	ENG	Not Timed
F1_BATCH_CTRL_TYPE_FLG	F1TM	ENG	Timed
F1_DATE_MATH_OPERATION_FLG	F1AB	ENG	Add Business Days
F1_DATE_MATH_OPERATION_FLG	F1AD	ENG	Add Days
F1_DATE_MATH_OPERATION_FLG	F1AT	ENG	Add Times
F1_DATE_MATH_OPERATION_FLG	F1DD	ENG	Date Difference
F1_DATE_MATH_OPERATION_FLG	F1DT	ENG	Date Time Difference
F1_DATE_MATH_OPERATION_FLG	F1FL	ENG	Force Last Day
F1_DATE_MATH_OPERATION_FLG	F1MD	ENG	Days in Month
F1_DATE_MATH_OPERATION_FLG	F1WD	ENG	Day of Week
F1_EXTRACT_TRANSLATION_FLG	F1NO	ENG	No
F1_EXTRACT_TRANSLATION_FLG	F1YS	ENG	Yes

Lookup Field Name	Field Value	Language	Description
F1_EXT_LOOKUP_U SAGE_FLG	F1AC	ENG	Active
F1_EXT_LOOKUP_U SAGE_FLG	F1IN	ENG	Inactive
F1_INPUT_IS_IN_DS T_FLG	F1N	ENG	No
F1_INPUT_IS_IN_DS T_FLG	F1Y	ENG	Yes
F1_INPUT_IS_IN_DS T_FLG	F1AN	ENG	Assume Not in Shift
F1_INPUT_IS_IN_DS T_FLG	F1AY	ENG	Assume In Shift
F1_PROD_TYPE_FL G	F1PL	ENG	Parallel application
F1_SHOW_ALL_REQ _FLG	F1YE	ENG	Yes
F1_STATE_CONDITI ON_FLG	F1AC	ENG	Active
F1_STATE_CONDITI ON_FLG	F1IN	ENG	Inactive
F1_TIMER_ACTIVE_ FLG	F1DS	ENG	No
F1_TIMER_ACTIVE_ FLG	F1EN	ENG	Yes
F1_TRANSLATABLE_ FLG	F1NO	ENG	No
F1_TRANSLATABLE_ FLG	F1YS	ENG	Yes
GEO_MTCH_QLTY_ FLG	1	ENG	Exact match
GEO_MTCH_QLTY_ FLG	10	ENG	Postal code does not match
GEO_MTCH_QLTY_ FLG	11	ENG	City does not match
GEO_MTCH_QLTY_ FLG	2	ENG	Street type does not match
GEO_MTCH_QLTY_ FLG	3	ENG	House does not match
GEO_MTCH_QLTY_ FLG	4	ENG	Street address does not match
ICON_TYPE_FLG	LBTN	ENG	32 x 32 pixels

Lookup Field Name	Field Value	Language	Description
ICON_TYPE_FLG	MBTN	ENG	24 x 24 pixels
ICON_TYPE_FLG	SBTN	ENG	16 x 16 pixels
INS_ALG_ENTITY_FLG	F1GS	ENG	Geocoding Service
INS_ALG_ENTITY_FLG	F1SR	ENG	SMS Receive Service
INS_ALG_ENTITY_FLG	F1SS	ENG	SMS Send Service
KEY_VALIDATION_FLG	ALL	ENG	Always Check Uniqueness
KEY_VALIDATION_FLG	NONE	ENG	Never Perform Uniqueness Checking
KEY_VALIDATION_FLG	ONLI	ENG	Check Uniqueness Online Only
MAINT_OBJ_OPT_FLG	F1SR	ENG	Status Reason Field
MAINT_OBJ_OPT_FLG	F1RB	ENG	ReplaceBOOption
MAINT_OBJ_OPT_FLG	F1RM	ENG	ReplaceMOOption
MAINT_OBJ_OPT_FLG	F1RS	ENG	Replace BO Status Option
MAINT_OBJ_SEVT_FLG	F1MA	ENG	Audit
MANAG_CONTENT_TYPE_FLG	F1CS	ENG	CSS Definitions
MANAG_CONTENT_TYPE_FLG	F1JS	ENG	Javascript
MANAG_CONTENT_TYPE_FLG	F1WL	ENG	Whitelist
MANAG_CONTENT_TYPE_FLG	F1X	ENG	XSLT
MANAG_CONTENT_TYPE_FLG	F1XC	ENG	XSLTC
MSG_PARM_TYP_FLG	DUR	ENG	Duration parameter
PROD_TYPE_FLG	F1PL	ENG	Parallel Application
SENDER_CTXT_FLG	BMSG	ENG	Bytes Message
SENDER_CTXT_FLG	JMSP	ENG	JMSUserPassword

Lookup Field Name	Field Value	Language	Description
SENDER_CTXT_FLG	JMSU	ENG	JMS User Name
SRC_FLD_TYPE_FLG	GBLC	ENG	Global Context
SRC_FLD_TYPE_FLG	PRTC	ENG	Portal Context
STATUS_REASON_FLG	F1OT	ENG	Optional
STATUS_REASON_FLG	F1RD	ENG	Required
STATUS_REASON_SELECT_FLG	F1SL	ENG	Selectable
STATUS_REASON_SELECT_FLG	F1US	ENG	Not Selectable
STD_TM_SRC_FLG	F1RF	ENG	Referenced Time Zone
STEP_TYPE_FLG	NVRD	ENG	Navigate and refresh dashboard
USER_CONFIG_FLG	N	ENG	No
USER_CONFIG_FLG	Y	ENG	Yes
USER_ENABLE_FLG	DSBL	ENG	Disable
USER_ENABLE_FLG	ENBL	ENG	Enable
XAI_OPTION_FLG	TDIN	ENG	To Do Type for Inbound JMS Message Errors
XAI_OPTION_FLG	SUSR	ENG	Privileged Users
ZONE_HPRM_USG_FLG	ZOVR	ENG	Zone - Override Allowed

Maintenance Object

The following Maintenance Objects are new to V4.0.2.

MO code	Description
F1-GENPROC	General Process
F1-MAN CONT	Managed Content
F1-REQ	Request
F1-REQ-TYPE	Request Type
F1-EXT LKUP	Extendable Lookup
F1-UI ZONE	Context Sensitive Zone - Single Row
F1-STSREASON	Business Object Status Reason

Script

The following Scripts are Framework-owned system data in V4.0.2.

Script	Description
F1-AppSerDet	Get Application Service Details
F1-AppSrvNav	Navigate to User Group Application Service Page
F1-BOStatus	Status Reason Drop Down populate - Pre Processing
F1-ChkOutLst	Objects Checked Out By User
F1-CondShwZn	Zone Visibility - Should Display Zone in Portal Conditionally
F1-CreEmail	Request - Create Email
F1-DelUsrGrp	Deny Access
F1-EdtMDFld	Edit MD Field
F1-ExLkActn	Extendable Lookup Actions
F1-ExLkpActZ	Extendable Lookup - Action Map Derivation
F1-ExLkpValD	Extendable Lookup Value Derivation Script
F1-ExLkpZ	Extended Lookup - Action Map Derivation
F1-ExtDA	Visibility script for Extended Data Area
F1-GENPRINFO	General Process MO Information
F1-GetUser	Get the current User
F1-GetUsrInf	Retrieves the user information with user id appended
F1-GotoPrtl	Navigate to portal, given appropriate maintenance object code and key values
F1-MainRqTyp	Request Type - Maintain
F1-MaintStRs	Business Object Status Reason Maintenance
F1-MtrEmail	Request Type - To Do Summary Email Monitor
F1-PopMDFld	Populate MD Field
F1-ReqActn	Request - Retrieve Action Details for Display
F1-ReqAdd	Request - Add
F1-ReqCan	Request - Cancel
F1-ReqChg	Request - Change

Script	Description
F1-ReqDisp	Request - BO and Map Derivation
F1-ReqInf	Request - Information
F1-ReqTyDisp	Request Type - Retrieve Details for Display
F1-ReqTypSel	Request Type - Select Active
F1-ReqValTyp	Request - Validate Request Type
F1-ReqZ	Request - Action Map Derivation
F1-RetChrDet	Retrieve Characteristic Type Information Details
F1-RetSchDef	Retrieves schema definition
F1-RqTypActn	Request Type - Retrieve Action Details for Display
F1-RqTypZ	Request Type - Action Map Derivation
F1-RqUsrLgAd	Request - Add User Log Entry
F1-RtUsrLgAd	Request Type - Add User Log Entry
F1-STRLONG	String Too Long
F1-SecAthLvl	Security Type with Authorization Level Info
F1-SelBOLbl	Retrieve Label for Select BO
F1-StsReqRsn	BO Statuses
F1-TRANSTBL	Inhibit tables with fields not exceeding capacity
F1-TdSumText	To Do Summary Text Message
F1-TodoRqDsp	Request - Retrieve To Do Summary Email Request Details for Display
F1-TodoSmPrv	Request - Preview To Do Summary Email
F1-TodoSumEm	To Do Summary Email
F1-TodoTyDsp	Retrieve To Do Summary Email for Display
F1-UpdMDFld	Update MD Field
F1-UsrGrpCds	User Group Access Codes
F1-ValTdsTyp	To Do Summary Email Request Type Validation
F1ExtLkMaint	Extended Lookup Maintenance
CreatePerson	SS Create Person

To do Type

The following To Do type is new to V4.0.2.

To Do Type	Description
F1-ARQPR	Request Monitor Errors
F1-INJMS	JMS Inbound Message In Error
F1-REQTY	Request Type Monitor Errors
F1-SUBRQ	Request Monitor (Deferred) Errors

Portal

The following Portal is new to V4.0.2.

Portal	Description
F1APPSEC	Application Security
F1EMHLAU	Embedded Help Authoring
F1EXLKP	Extendable Lookup
F1EXLKPS	Extendable Lookup Query
F1REQ	Request
F1REQTYP	Request Type
F1STREAS	Status Reason
F1SUBRQQ	Request Query
F1TBLEXC	Translatable Strings Exceeding Capacity
F1_MAN_CON	Managed Content

Portal Zone

The following Portal Zones are added to V4.0.2

Portal	Zone
F1APPSEC	F1-APSVDTL
F1APPSEC	F1-USGRPWSR
F1APPSEC	F1-USGRPWTSR
F1EMHLAU	F1-UISRC
F1EXLKP	F1-EXLKPLST
F1EXLKP	F1-EXLKPVLD
F1EXLKP	F1-EXLKACTN
F1EXLKPS	F1-EXLKPSRCH
F1REQ	F1-SUBRACTN
F1REQ	F1-SUBRQL

Portal	Zone
F1REQ	F1-SUBRQZ
F1REQTYP	F1-REQTYL
F1REQTYP	F1-RQTACTN
F1REQTYP	F1-SUBRQD
F1REQTYP	F1-SUBRQT
F1STREAS	F1-BORFOL
F1STREAS	F1-SREBO
F1SUBRQQ	F1-SUBREQ
F1TBLEXC	F1-STRLONG
F1TBLEXC	F1-TRANSTBL
F1_MAN_CON	F1-MAN-CON
F1_MAN_CON	F1-SCHHDR-MC
F1_SCHEMA_BO	F1-SCHEMA-US
F1_SCHEMA_DA	F1-EXTDA

UI Map

The following UI Maps are Framework Owned system data in V4.0.2.

Map	Description
F1-AppSrvDetDisp	Application Service Details Display
F1-AppSrvUsGrpFilter	Application Service User Group Filter Area
F1-AppZoneHeaderMenu	Application URL Zone Header Menu Fragment
F1-CancelRequest	Request - Cancel Confirmation
F1-DAExplorerHeaderFrameAction	Explorer Header Action UI Map Fragment
F1-DisplayFavoriteScripts	Display Favorite Scripts
F1-EditMDField	Edit MD Field
F1-EditorHeader	HTML Editor Zone Header
F1-EnterRequestType	Request - Select Request Type
F1-ExplZoneHeadMenuFusion	Fusion style zone header menu for explorer zones
F1-ExtDAHeader	Default Header for Data Explorers
F1-GenericZoneHdrActions	Generic Zone Header Actions

Map	Description
F1-MQueryExpHeaderFrameActions	Multi Query Explorer Header Action UI Map
F1-MultiExplorerHeadFrameAct	Explorer Header Action UI Map Fragment
F1-RequestActions	Request - Actions
F1-RequestTypeActions	Request Type - Actions
F1-RequestTypeUserLogAdd	Request Type - Add User Log Entry
F1-RequestUserLogAdd	Request - Add User Log Entry
F1-StatusReasonInput	State Transition - Enter Reason
F1-StatusReasonMaintenance	Status Reason - Maintenance
F1-StringLongDetails	Display fields exceeding 70% capacity
F1-ToDoSumEmailDisp	To Do Summary Email Request - Display
F1-ToDoSumEmailPreview	Request - Preview To Do Summary Email
F1-ToDoSumEmailReqMaint	Request - To Do Summary Email Maintenance
F1-ToDoSumEmailTypMaint	To Do Summary Email Type - Maintenance
F1-ToDoSumEmailTypeDisp	To Do Summary Email Request Type - Display
F1-UIMapHeadMenuFusion	Fusion look zone header menu

XAI Inbound Service

The following XAI Inbound Service is new to V4.0.2.

XAI Inbound Service name	Description
F118739517	F1-SmsReceive

Zone Type

The following Zone Types are new to V4.0.2.

Zone Type code	Description
F1-APP-URL	Application URL

Zone

The following new Zones are added to V4.0.2.

Zone	Zone Type	Description
F1-APSRVSEC	F1-DE	Get Application Service Security

Zone	Zone Type	Description
F1-APSVDTL	F1-MAPEXPL	ApplicationServiceDetails
F1-BNCTXZS	F1-DE-QUERY	Context Sensitive Zone Search
F1-BNEXLKPS	F1-DE-QUERY	ExtendedLookupSearch
F1-BNMANCONS	F1-DE-QUERY	Managed Content Search
F1-BNSTSRSNS	F1-DE-QUERY	Business Object Status Reason Search
F1-BORFOL	F1-DE-SINGLE	Business Objects with Status Reason
F1-BOSRCH	F1-DE-QUERY	Business Object Search
F1-BOSTSLST	F1-DE-SINGLE	Retrieve BO Statuses Allowing Reason
F1-BSRDRS	F1-DE-SINGLE	Getrequiredstatusreasons
F1-BSSLRS	F1-DE-SINGLE	Get all selected Reasons
F1-CONDSHWZN	F1-DE-SINGLE	ApplicationServiceDetails
F1-DASRCH	F1-DE-QUERY	Data Area Search
F1-DISSTS	F1-DE-SINGLE	Zone to fetch distinct states for the BO
F1-EXLKPLST	F1-DE-SINGLE	Extendable Lookup Value List
F1-EXLKPSRCH	F1-DE-QUERY	ExtendableLookupSearch
F1-EXLKPVAlD	F1-MAPDERV	ExtendableLookupValue
F1-EXTDA	F1-DE-SINGLE	Extension Data Areas
F1-FAVSCR	F1-DE-SINGLE	Favorites Scripts
F1-GETACTTYP	F1-DE-SINGLE	Retrieve Active Request Types
F1-GETEXLKPD	F1-DE-SINGLE	Get Extended Lookup Value details
F1-GETEXTSYS	F1-DE-SINGLE	Retrieve External Systems
F1-GETRECREQ	F1-DE-SINGLE	Retrieve Latest Request for Request Type
F1-GPINFO	F1-DE-SINGLE	Retrieve General Process Information
F1-MAN-CON	F1-XMLEditor	Editor
F1-MONAVKEY	F1-DE-SINGLE	Get Tab Menu Navigation Key for MO
F1-REQTYL	F1-DE-SINGLE	Request Type Log

Zone	Zone Type	Description
F1-RQTACTN	F1-MAPDERV	Actions
F1-SCHHDR-MC	F1-FIELDVALS	General Information
F1-SCSRCH	F1-DE-QUERY	Script Search
F1-SREBO	F1-DE-SINGLE	Status Reasons
F1-STRLONG	F1-MAPEXPL	Translatable Strings Exceeding Capacity
F1-SUBRACTN	F1-MAPDERV	Actions
F1-SUBREQ	F1-DE-QUERY	Request Search
F1-SUBRQD	F1-MAPDERV	Request Type
F1-SUBRQL	F1-DE-SINGLE	Request Log
F1-SUBRQT	F1-DE-SINGLE	Request Type List
F1-SUBRQZ	F1-MAPDERV	Request
F1-TDS-ALL	F1-DE-SINGLE	To Do Summary Email All
F1-TDS-CNT	F1-DE-SINGLE	To Do Summary Email Count
F1-TDS-OPN	F1-DE-SINGLE	To Do Summary Email Get Open To Dos by Type
F1-TDS-PRV	F1-DE-SINGLE	To Do Summary Email Preview
F1-TRANSTBL	F1-DE-SINGLE	Translatable Tables
F1-TZSRCH	F1-DE-QUERY	Time Zone Search
F1-UISRC	F1-DE-QUERY	UI Map Search
F1-UISRCH	F1-DE-QUERY	UserInterfaceMapSearch
F1-USGRACML	F1-DE	Get User Group Access Modes
F1-USGRPWSR	F1-DE	UserGroups with Access
F1-USGRPWTSR	F1-DE	UserGroups without Access
F1-USGRSECL	F1-DE	Get Security Type Access for User Group
F1-USSRCH	F1-DE-QUERY	User Search
F1_USRSCR	F1-MAPEXPL	Favorite Scripts
F1-WORKCAL	F1-DE-QUERY	Work Calendar Search

Appendix B

Upgrades to the Oracle Utilities Application Framework V4.0.2 Database

This document describes the database upgrade process for the Oracle Utilities Application Framework database from V4.0.1 to V4.0.2. It highlights changes made to the administrative tables and how those changes should be applied to the data in order for a V4.0.1 database to work with the V4.0.2 application, and to preserve the business logic implemented in the previous version of the application. The changes that do not require data upgrade are not described in this document. The tasks that need to be performed after running the upgrade scripts are included.

The added functionality of V4.0.2 is not the scope of this documentation. The upgrade scripts do not turn on the newly added functionality by default. For new functionality, refer the V4.0.2 User Guides. In the last section of this document you will find a list of the new tables that are added in V4.0.2.

Automatic Data Upgrade

This section describes what the upgrade script will populate in new tables and columns to preserve the existing base product application functions of the previous version of Oracle Utilities Application Framework.

Display/Expand Zones in Portal

To allow the user to display or hide zones in the portal, we need to provide an extra field on the Field Maintenance Page of Portal Zone (CI_PORTAL_ZONE). The new field added to Portal Zone is called Display Switch (DISPLAY_SW). It defines a display switch value of Y or N to display or hide a zone within the portal.

Also to allow the user to expand or collapse the zones in the portal, we need to provide an extra field on the Field Maintenance Page of Portal Zone. The new field added to Portal Zone is called Zone Collapsed Switch (ZONE_COLLAPSED_SW). It defines a Zone Collapsed switch value of Y or N to collapse or display a zone within the portal.

As a part of the Upgrade Process DISPLAY_SW is set to 'Y' and ZONE_COLLAPSED_SW is set to 'N'.

Schema Change

New Tables

The following new tables are added to Oracle Utilities Application Framework V4.0.2.

Tables	Description
F1_DB_OBJECTS_REPO	F1_DB_OBJECTS_REPO
F1_GEN_PROC	F1_GEN_PROC
F1_GEN_PROC_K	F1_GEN_PROC_K
F1_SYNC_REQ	F1_SYNC_REQ
F1_SYNC_REQ_CHAR	F1_SYNC_REQ_CHAR
F1_SYNC_REQ_K	F1_SYNC_REQ_K
F1_SYNC_REQ_LOG	F1_SYNC_REQ_LOG
F1_SYNC_REQ_LOG_PARM	F1_SYNC_REQ_LOG_PARM

Dropped Tables

The following tables are dropped in this release.

- CI_SCR_STEP_K

Unsupported Tables

The following tables would be deprecated in a future release.

- CI_XAI_SVC_VERS (L)
- CI_MODULE

Added Columns

The following Table Columns are added to Oracle Utilities Application Framework V4.0.2.

Table	Column	Required	Upgrade Note
CI_PORTAL_ZONE	DISPLAY_SW	N	Display/Expand Zones in Portal
CI_PORTAL_ZONE	ZONE_COLLAPSED_SW	N	Display/Expand Zones in Portal

Dropped Columns

The following columns are dropped in this release.

- CI_PORTAL: USER_CONFIG_OVRD_FLG column.
- F1_MAP_L: HTML_DEFN column.
- CI_XAI_SNDR_CTX: CTXT_VAL column.
- CI_XAI_IN_SVC_L: DESCR254 column.
- CI_SCR_STEP, CI_SCR_STEP_L, CI_SCR_PRMPPT, CI_SCR_PRMPPT_L, CI_SCR_FLD_MAP: SCR_STEP_ID column.

Unsupported Table Columns

These columns will be deprecated in a future release.

- CI_XAI_IN_SVC: XAI_VERSION_ID column is not used.
- CI_XAI_JDBC_CON: DATABASE_NAME column is not used.

Metadata Changes in FW for Successful Upgrade

The Following Metadata is changed in FW402 for a successful Upgrade.

Metadata Description	Action Items for Products
CI_SCRIPTS Zone is deleted from FW. Also for CI_TODO Zone the record with Zone Parameter name as CACHE_DATA is made FW owned with value as 'Y'	'ETM , CCB and BI needs to care about this. The FW 402 upgrade scripts will handle this.

New System Data

This section lists the new system data that are added for business process configuration.

Algorithm Type

The following algorithm types are new to V4.0.2.

Algorithm Type	Description
F1-GENPRINFO	Maintenance Object - Information

Algorithm

The following Algorithms are Framework Owned system data in V4.0.2.

Algorithm	Description
F1-GENPRINFO	General Process

Application Service

The following Application Services are new to V4.0.2.

Application Service	Description
F1-GENPROC	General Process Maintenance Object

Access Mode Added to Application Service

The following Access Mode is added to existing Application Services and is new to V4.0.2.

Application Service	Description	Access Mode
F1-EXPUSERSREQBOAS	Request - To Do Summary Email	Pending (PE)

FK Reference

The following FK References are new to V4.0.2.

FK Reference	Description
F1-GENPR	General Process

Lookups

The following Lookups are added to Oracle Utilities Application Framework V4.0.2.

Lookup Field Name	Field Value	Language	Description
ALG_ENTITY_FLG	F1MA	ENG	Maintenance Object - Audit
F1_INPUT_IS_IN_DS T_FLG	F1AN	ENG	Assume Not in Shift

Lookup Field Name	Field Value	Language	Description
F1_INPUT_IS_IN_DS T_FLG	F1AY	ENG	Assume In Shift
MAINT_OBJ_OPT_FLG	F1RB	ENG	ReplaceBO Option
MAINT_OBJ_OPT_FLG	F1RM	ENG	ReplaceMO Option
MAINT_OBJ_OPT_FLG	F1RS	ENG	Replace BO Status Option
MAINT_OBJ_SEVT_FLG	F1MA	ENG	Audit
SENDER_CTXT_FLG	JMSP	ENG	JMS User Password
SENDER_CTXT_FLG	JMSU	ENG	JMS User Name
STEP_TYPE_FLG	NVRD	ENG	Navigate and refresh dashboard
XAI_OPTION_FLG	TDIN	ENG	To Do Type for Inbound JMS Message Errors
ZONE_HPRM_USG_FLG	ZOVR	ENG	Zone - Override Allowed

Maintenance Object

The following Maintenance Objects are new to V4.0.2.

MO code	Description
F1-GENPROC	General Process

Script

The following Scripts are Framework-owned system data in V4.0.2.

Script	Description
F1-ExLkActn	Extendable Lookup Actions
F1-ExLkpActZ	Extendable Lookup - Action Map Derivation
F1-ExLkpZ	ExtendedLookup-ActionMapDerivation
F1-GENPRINFO	General Process MO Information
F1-SelBOLbl	Retrieve Label for Select BO

To do Type

The following To Do type is new to V4.0.2.

To Do Type	Description
F1-INJMS	JMS Inbound Message In Error

Portal Zone

The following Portal Zones are added to V4.0.2

Portal	Zone
F1EXLKP	F1-EXLKACTN

UI Map

The following UI Maps are Framework Owned system data in V4.0.2.

Map	Description
F1-ExplZoneHeadMenuFusion	Fusion style zone header menu for explorer zones
F1-ExtendableLookupActions	Extendable Lookup - Actions
F1-UIMapHeadMenuFusion	Fusion look zone header menu

Zone

The following new Zones are added to V4.0.2.

Zone	Zone Type	Description
F1-EXLKACTN	F1-MAPDERV	Actions
F1-FAVSCR	F1-DE-SINGLE	Favorites Scripts
F1-GPINFO	F1-DE-SINGLE	Retrieve General Process Information
F1_USRSCR	F1-MAPEXPL	Favorite Scripts

Appendix C

Oracle Utilities Mobile Workforce Management System Table Guide

This chapter lists the system tables owned by Oracle Utilities Mobile Workforce Management V2.0.1 and explains the data standards of the system tables. The data standards are required for Oracle Utilities Mobile Workforce Management installation, development within Oracle Utilities Mobile Workforce Management, configuration of Oracle Utilities products, and customization of the Oracle Utilities products. Adhering to the data standards is a prerequisite for a seamless upgrade to the next release of the product. For the general discussion of System Tables, refer to the System Table Guide for the Oracle Utilities Application Framework.

This section includes:

- **Development and Implementation System Tables**

Development and Implementation System Tables

Parameter Definition

Properties	Description
Tables	M1_PARM_DEF, M1_PARM_DEF_L
Standard Data Fields	Parameter Definition (PARM_DEF_CD).
Customer Modification	None

Appendix D

Oracle Application Framework System Table Guide

This section lists the system tables owned by the Oracle Utilities Application Framework V4.0.2 and explains the data standards of the system tables. The data standards are required for the installation of Oracle Utilities Application Framework, development within the Oracle Utilities Application Framework, and the configuration and customization of Oracle Utilities products. Adhering to the data standards is a prerequisite for seamless upgrade to future releases.

This section includes:

- **About the Application Framework System Tables**
- **System Table Standards**
- **Guidelines for System Table Updates**
- **System Table List**

About the Application Framework System Tables

System tables are a subset of the tables that must be populated at the time the product is installed. They include Metadata and configuration tables. The data stored in the system tables are the information that Oracle Utilities Application Framework product operations are based on.

As the product adds more functionality, the list of system tables can grow. The complete list of the system tables can be found in the **System Table List** section.

System Table Standards

System table standards must be observed for the following reasons:

- The product installation and upgrade process and customer modification data extract processes depend on the data prefix and owner flag values to determine the system data owned by each product.
- The standards ensure that there will be no data conflict in the product being developed and the future Oracle Utilities Application Framework release.
- The standards ensure that there will be no data conflict between customer modifications and future Oracle Utilities product releases.
- The data prefix is used to prevent test data from being released to production.

Developer's Note: All test data added to the system data tables must be prefixed by ZZ (all upper case) in order for the installation and upgrade utility to recognize them as test data.

Guidelines for System Table Updates

This section describes guidelines regarding the updating of the system table properties.

Business Configuration Tables

The majority of data in the tables in this group belongs to the customer. But these tables are shipped with some initial data in order for the customer to login to the system and begin configuring the product. Unless specified otherwise, the initial data is maintained by Oracle Utilities Application Framework and subject to subsequent upgrade.

Application Security and User Profile

These tables define the access rights of a User Group to Application Services and Application Users.

Properties	Description
Tables	SC_ACCESS_CNTRL, SC_USER, SC_USR_GRP_PROF, SC_USR_GRP_USR, SC_USER_GROUP, SC_USER_GROUP_L
Initial Data	User Group All SERVICES and default system user SYSUSER. Upon installation the system default User Group All SERVICES is given unrestricted accesses to all services defined in Oracle Utilities Application Framework.

Developer's Note: When a new service is added to the system, all actions defined for the service must be made available to the User Group All SERVICES.

Currency Code

The ISO 4217 three-letter codes are taken as the standard code for the representation of each currency.

Properties	Description
Tables	CI_CURRENCY_CD, CI_CURRENCY_CD_L
Initial Data	United States Dollar (USD).

DB Process

Properties	Description
Tables	CI_DB_PROC, CI_DB_PROC_L, CI_DB_INSTR, CI_DB_INSTR_L, L, CI_DB_INSTR_OVRD
Initial Data	Copy DB Process (CL-COPDB). This DB process allows users to copy a DB process from one database to another using Config Lab utility.

Display Profile

The Display Profile Code is referenced in the User (SC_USER) table.

Properties	Description
Tables	CI_DISP_PROF, CI_DISP_PROF_L
Initial Data	North America (NORTHAM) and Europe (EURO).

Installation Options

Installation Option has only one row that is shipped with the initial installation of the Oracle Utilities Application Framework. The updatable columns in these tables are customer data and will not be overridden by the upgrade process unless a special script is written and included in the upgrade process.

Properties	Description
Tables	F1_INSTALLATION, CI_INSTALL_ALG, CI_INSTALL_MSG, CI_INSTALL_MSG_L, CI_INSTALL_PROD
Initial Data	Option 11111.

Developer's Note: The system data owner of an environment is defined in the Installation Option. This Owner Flag value is stamped on all system data that is added to this environment. The installation default value is Customer Modification (CM). This value must be changed in the base product development environments.

Language Code

Language Code must be a valid code defined in ISO 639-2 Alpha-3. Adding a new language code to the table without translating all language dependent objects in the system can cause errors when a user chooses the language.

Properties	Description
Tables	CI_LANGUAGE
Initial Data	English (ENG).

To Do Priority and Role

New To Do Types released will be linked to the default To Do Role and set to the product assigned priority value initially. These initial settings can be overridden by the implementation.

Properties	Description
Tables	CI_ROLE(L), CI_TD_VAL_ROLE
Initial Data	F1_DFLT

Development and Implementation System Tables

This section defines the standards for the system tables that contain data for application development. The data in these tables implement business logic and UI functions shared by various products and product extensions in the same database.

Standards

When adding new data, the owner flag value of the environment must prefix certain fields of these tables. For example, when a developer adds a new algorithm type to an Oracle Utilities Customer Care and Billing environment, C1 should prefix the new Algorithm Type code. The fields that are subject to this rule are listed in Standard Data Fields property.

The data that is already in these tables cannot be modified if the data owner is different than the environment owner. This prevents the developers from accidentally modifying system data that belongs to the Oracle Utilities application framework or the base products. However, some fields are exempt from this rule and can be modified by Customer Modification. These fields are listed in the Customer Modification Fields property.

Starting with version 2.2 of the framework a new system data upgrade rule was introduced - Override Owner flag. If duplicate data rows (data row with same primary key values) are found at the time of upgrade, the owner flag values will get overridden. The lower level application system data will override the upper level system data. For example, F1 overrides C1, F1&C1 override CM, and so on. This rule will be applied to the following tables: CI_CHAR_ENTITY, CI_MD_MO_ALG, F1_BUS_OBJ_ALG, F1_BUS_OBJ_STATUS_ALG, CI_MD_MO_OPT, F1_BUS_OBJ_OPT, F1_BUS_OBJ_STATUS_OPT, F1_BUS_OBJ_STATUS, F1_BUS_OBJ_STATUS_L

Algorithm Type

Properties	Description
Tables	CI_ALG_TYPE, CI_ALG_TYPE_L, CI_ALG_TYPE_PRM, CI_ALG_TYPE_PRM_L
Standard Data Fields	Algorithm Type (ALG_TYPE_CD)
Customer Modification	None

Algorithm

Properties	Description
Tables	CI_ALG, CI_ALG_L, CI_ALG_PARM, CI_ALG_VER
Standard Data Fields	Algorithm (ALG_CD)
Customer Modification	None

Application Security

Properties	Description
Tables	SC_APP_SERVICE, SC_APP_SERVICE_L, CI_APP_SVC_ACC
Standard Data Fields	Application Service ID (APP_SVC_ID). Customer care and billing products prior to version 2.0 will continue to use CI as a prefix for the application service.
Customer Modification	None

Batch Control

Properties	Description
Tables	CI_BATCH_CTRL, CI_BATCH_CTRL_L, CI_BATCH_CTRL_P, CI_BATCH_CTRL_P_L
Standard Data Fields	Batch Process (BATCH_CD), Program Name (PROGRAM_NAME)
Customer Modification	Next Batch Number (NEXT_BATCH_NBR), Last Update Instance (LAST_UPDATE_INST), Last Update Date time (LAST_UPDATE_DTM) and the batch process update these columns. Time Interval (TIMER_INTERVAL), Thread Count (BATCH_THREAD_CNT), Maximum Commit Records (MAX_COMMIT_RECS), User (USER_ID), Language (LANGUAGE_CD), Email Address (EMAILID), Start program debug tracing (TRC_PGM_STRT_SW), End Program Debug trace (TRC_PGM_END_SW), SQL debug tracing (TRC_SQL_SW) and Standard debug tracing (TRC_STD_SW) on CI_BATCH_CTRL Table. Batch Parameter Value (BATCH_PARM_VAL) on Batch Control Parameters Table (CI_BATCH_CTRL_P)

Business Object

Properties	Description
Tables	F1_BUS_OBJ, F1_BUS_OBJ_L, F1_BUS_OBJ_ALG, F1_BUS_OBJ_OPT, F1_BUS_OBJ_STATUS, F1_BUS_OBJ_STATUS_L, F1_BUS_OBJ_STATUS_ALG, F1_BUS_OBJ_STATUS_OPT, F1_BUS_OBJ_STATUS_RSN, F1_BUS_OBJ_STATUS_RSN_L, F1_BUS_OBJ_STATUS_RSN_CHAR F1_BUS_OBJ_TR_RULE, F1_BUS_OBJ_TR_RULE_L
Standard Data Fields	Business Object (BUS_OBJ_CD)
Customer Modification	Batch Control (BATCH_CD), Alert (BO_ALERT_FLG), Sequence (SORT_SEQ5), Status Reason (STATUS_REASON_FLG) fields on Business Object Status Table (F1_BUS_OBJ_STATUS). Instance Control (INSTANCE_CTRL_FLG), Application Service (APP_SVC_ID) on Business Object Table (F1_BUS_OBJ). Status Reason Selection (STATUS_REASON_SELECT_FLG) on Status Reason Table (F1_BUS_OBJ_STATUS_RSN)

Business Service

Properties	Description
Tables	F1_BUS_SVC, F1_BUS_SVC_L
Standard Data Fields	Business Service (BUS_SVC_CD)
Customer Modification	Application Service (APP_SVC_ID)

Characteristics

Properties	Description
Tables	CI_CHAR_TYPE, CI_CHAR_TYPE_L, CI_CHAR_ENTITY, CI_CHAR_VAL, CI_CHAR_VAL_L
Standard Data Fields	Characteristic Type (CHAR_TYPE_CD)

Properties	Description
Customer Modification	Adhoc Characteristic Value Validation Rule (ADHOC_VAL_ALG_CD) on Characteristic Entity Table (CI_CHAR_ENTTTY)

Data Area

Properties	Description
Tables	F1_DATA_AREA, F1_DATA_AREA_L
Standard Data Fields	Data Area Code (DATA_AREA_CD)
Customer Modification	None

Display Icon

Properties	Description
Tables	CI_DISP_ICON, CI_DISP_ICON_L
Standard Data Fields	Display Icon Code (DISP_ICON_CD)
Customer Modification	None

Foreign Key Reference

Properties	Description
Tables	CI_FK_REF, CI_FK_REF_L
Standard Data Fields	FK reference code (FK_REF_CD)
Customer Modification	Info Program Name (INFO_PRG), Zone (ZONE_CD)

Lookup

Properties	Description
Tables	CI_LOOKUP_FIELD, CI_LOOKUP_VAL, CI_LOOKUP_VAL_L, F1_EXT_LOOKUP_VAL, F1_EXT_LOOKUP_VAL_L

Properties	Description
Standard Data Fields	<p>Field Name (FIELD_NAME)</p> <ul style="list-style-type: none"> A lookup field name must have corresponding field metadata. The name of the lookup field column must be assigned to avoid conflicts among different products. If you follow the standards for database field names, a Customer Modification lookup field name will be automatically Customer Modification prefixed. <p>Field Value (FIELD_VALUE)</p> <ul style="list-style-type: none"> If a lookup field is customizable, Customer Modification can insert new lookup values. X or Y must prefix when implementers introduce a new lookup value. Product development can extend the Oracle Utilities Application Framework owned lookup field's value with caution. When it needs to be extended, prefix the first letter of the Owner Flag to the value. For example, when adding a new value to the algorithm entity flag (ALG_ENTITY_FLG), prefix with C1 if you are developing an Oracle Utilities Customer Care and Billing product. <p>Introduced in V 4.0.1: Value (F1_EXT_LOOKUP_VALUE)</p> <ul style="list-style-type: none"> This will allow storing longer value keys rather than the normal 4byte lookup values.
Customer Modification	Override Description (DESCR_OVRD) on Lookup Field Value Language Table (CI_LOOKUP_VAL_L)

A new Feature option is defined through adding a value to EXT_SYS_TYP_FLG. The field value for this look up field must be prefixed by the Owner flag value.

Map

Properties	Description
Tables	F1_MAP, F1_MAP_L
Standard Data Fields	UI Map (MAP_CD)
Customer Modification	None

Managed Content

Properties	Description
Tables	F1_MANAG_CONTENT, F1_MANAG_CONTENT_L
Standard Data Fields	Managed Content (MANAG_CONTENT_CD)
Customer Modification	None

Messages

Properties	Description
Tables	CI_MSG_CATEGORY, CI_MSG_CATEGORY_L, CI_MSG, CI_MSG_L

Properties	Description
Standard Data Fields	<p data-bbox="946 218 1406 243">Message Category (MESSAGE_CAT_NBR)</p> <ul data-bbox="946 254 1485 947" style="list-style-type: none"> <li data-bbox="946 254 1485 405">• Messages are grouped in categories and each category has message numbers between 1 and 99999. A range of message categories is assigned to a product. You must use only the assigned category for your product. <li data-bbox="946 426 1485 516">• Oracle Utilities Customer Care and Billing and Oracle Utilities Business Intelligence - 00001 thru 00100 <li data-bbox="946 537 1485 594">• Oracle Utilities Application Framework Java - 11001 thru 11100 <li data-bbox="946 615 1485 672">• Oracle Utilities Customer Care and Billing Java - 11101 thru 11200 <li data-bbox="946 693 1485 749">• Oracle Utilities Business Intelligence Java - 11201 thru 11300 <li data-bbox="946 770 1308 795">• Implementer COBOL - 90000 <li data-bbox="946 816 1263 842">• Implementer WSS - 90001 <li data-bbox="946 863 1256 888">• Implementer Java - 90002 <li data-bbox="946 909 1268 934">• Reserved for Tests - 99999 <p data-bbox="946 961 1485 1018">Message Number (MESSAGE_NBR) for COBOL message categories</p> <ul data-bbox="946 1029 1485 1119" style="list-style-type: none"> <li data-bbox="946 1029 1485 1119">• Message numbers below 1000 are reserved for common messages. Implementers must not use message numbers below 1000. <p data-bbox="946 1140 1485 1197">Message Number (MESSAGE_NBR) for Java message categories</p> <ul data-bbox="946 1207 1485 1913" style="list-style-type: none"> <li data-bbox="946 1207 1485 1264">• Subsystem Standard Messages - 00001 thru 02000 <li data-bbox="946 1285 1292 1310">• Reserved - 02001 thru 09999 <li data-bbox="946 1331 1403 1356">• Published Messages - 10001 thru 11000 <li data-bbox="946 1377 1383 1402">• Package Messages - 10001 thru 90000 <li data-bbox="946 1423 1292 1449">• Reserved - 90001 thru 99999 <li data-bbox="946 1470 1485 1526">• Each package is allocated 100 message numbers, each starting from 101. <li data-bbox="946 1547 1485 1801">• Published Messages are messages that are special-interest messages that implementations need to know about and are therefore published in the user docs. Examples of these include messages that are highly likely to be changed for an implementation, or messages that are embedded into other texts/messages and therefore the message number is never shown <li data-bbox="946 1822 1485 1913">• Reserved message number ranges are for future use and therefore must not be used by all products.

Properties	Description
Customer Modification	Override Description (DESCRLONG_OVRD), Message Text Override (MESSAGE_TEXT_OVRD)

Meta Data - Table and Field

Properties	Description
Tables	CI_MD_TBL, CI_MD_TBL_FLD, CI_MD_TBL_L, CI_MD_TBL_FLD_L, CI_MD_FLD, CI_MD_FLD_L, F1_DB_OBJECTS_REPO
Standard Data Fields	<p>Table Name (TBL_NAME)</p> <ul style="list-style-type: none"> Table names must match with the physical table name or view name in the database. Field Name (FLD_NAME)Field name must match with the physical column name in the database unless the field is a work field. Field name does not have to follow the prefixing standard unless the field is a work field or customer modification field. F1_DB_OBJECTS_REPO Table stores information about Indexes, Sequences, Triggers and other database objects excluding Tables and Fields (as they are already stored in the other Metadata tables)
Customer Modification	Audit Switches (AUDIT_INSERT_SW, AUDIT_UPDATE_SW, AUDIT_DELETE_SW), Override label (OVRD_LABEL) on MD Table Field Table (CI_MD_TBL_FLD). Audit Program Name (AUDIT_PGM_NAME), Audit Table Name (AUDIT_TBL_NAME), Audit Program Type (AUDIT_PGM_TYPE_FLG), Key Validation (KEY_VALIDATION_FLG) and Caching strategy (CACHE_FLG) on MD Table (CI_MD_TBL). Override Label (OVRD_LABEL) and Customer Specific Description (DESCRLONG_OVRD) on Field Table.

Meta Data - Constraints

Properties	Description
Tables	CI_MD_CONST, CI_MD_CONST_FLD
Standard Data Fields	Constraint Id (CONST_ID) <ul style="list-style-type: none"> Index Name for Primary Constraints <Index Name>Rnn for Foreign Key Constraints Where <ul style="list-style-type: none"> nn: integer, 01 through 99
Customer Modification	None

Meta Data - Menu

Menus can be extended to support multiple products by adding a new menu line to an existing menu. The sequence number on the menu line language table (CI_MD_MENU_LINE_L) determines the order the menu lines appear. Within the same sequence, alphabetic sorting is used.

Properties	Description
Tables	CI_MD_MENU, CI_MD_MENU_L, CI_MD_MENU_ITEM, CI_MD_MENU_ITEM_L, CI_MD_MENU_LINE, CI_MD_MENU_LINE_L
Standard Data Fields	Menu Name (MENU_NAME), Menu Item Id (MENU_ITEM_ID), Menu Line Id (MENU_LINE_ID)
Customer Modification	Override Label (OVRD_LABEL) on Menu Line Language Table (CI_MD_MENU_LINE_L)

Meta Data - Program, Location and Services

Properties	Description
Tables	CI_MD_PRG_COM, CI_MD_PRG_LOC, CI_MD_SVC, CI_MD_SVC_L, CI_MD_SVC_PRG, CI_MD_PRG_REF, CI_MD_PRG_MOD, CI_MD_PRG_EL_AT, CI_MD_PRG_ELEM, CI_MD_PRG_SEC, CI_MD_PRG_SQL, CI_MD_PRG_VAR, CI_MD_PRG_TAB

Properties	Description
Standard Data Fields	Program Component Id (PROG_COM_ID), Location Id (LOC_ID), Program Component Name (PROG_COM_NAME), Service Name (SVC_NAME), Navigation Key (NAVIGATION_KEY)
Customer Modification	User Exit Program Name (USER_EXIT_PGM_NAME) on Program Componenets Table (CI_MD_PRG_COM),

Meta Data - Maintenance Object

Properties	Description
Tables	CI_MD_MO, CI_MD_MO_L, CI_MD_MO_TBL, CI_MD_MO_OPT, CI_MD_MO_ALG
Standard Data Fields	Maintenance Object (MAINT_OBJ_CD)
Customer Modification	None

Meta Data - Work Tables

Properties	Description
Tables	CI_MD_WRK_TBL, CI_MD_WRK_TBL_L, CI_MD_WRK_TBLFLD, CI_MD_MO_WRK
Standard Data Fields	Work Table Name (WRK_TBL_NAME)
Customer Modification	None

Meta Data - Search Object

Properties	Description
Tables	CI_MD_SO, CI_MD_SO_L, CI_MD_SO_RSFLD, CI_MD_SO_RSFLDAT, CI_MD_SO CG, CI_MD_SO CG_FLD, CI_MD_SO CG_FLDAT, CI_MD_SO CG_L, CI_MD_SO CG_SORT
Standard Data Fields	Search Object (SO_CD)
Customer Modification	None

Navigation Option

Properties	Description
Tables	CI_NAV_OPT, CI_NAV_OPT_L, CI_NAV_OPT_CTXT, CI_NAV_OPT_USG, CI_MD_NAV
Standard Data Fields	Navigation Option Code (NAV_OPT_CD), Navigation Key (NAVIGATION_KEY)
Customer Modification	None

Portal and Zone

Properties	Description
Tables	CI_PORTAL, CI_PORTAL_L, CI_PORTAL_ZONE, CI_ZONE, CI_ZONE_L, CI_ZONE_PRM, CI_ZONE_HDL, CI_ZONE_HDL_L, CI_ZONE_HDL_PRM, CI_ZONE_HDL_PRM_L, CI_UI_ZONE
Standard Data Fields	Portal Code (PORTAL_CD), Zone Code (ZONE_CD), Zone Type Code (ZONE_HDL_CD) <ul style="list-style-type: none"> A new Zone can be added to the Product owned Portal Pages. The existing Zones cannot be removed from the Product owned Portal Pages.
Customer Modification	Sort Sequence (SORT_SEQ) on Context Sensitive Zone Table (CI_UI_ZONE). Show on Portal Preferences (USER_CONFIG_FLG) on Portal Table (CI_PORTAL). Override Sequence (SORT_SEQ_OVRD) on Portal Zone Table (CI_PORTAL_ZONE). Customer Specific Description (DESCRLONG_OVRD) on Zone Language Table (CI_ZONE_L). Override Parameter Value (ZONE_HDL_PARM_OVRD) on Zone Type Parameters Table (CI_ZONE_HDL_PRM). Override Parameter Value (ZONE_PARM_VAL_OVRD) on Zone Parameters Table (CI_ZONE_PRM).

Sequence

Properties	Description
Tables	CI_SEQ
Standard Data Fields	Sequence Name (SEQ_NAME)
Customer Modification	Sequence Number (SEQ_NBR) This field is updated by the application process and must be set to 1 initially.

Schema

Properties	Description
Tables	F1_SCHEMA
Standard Data Fields	Schema Name (SCHEMA_NAME)
Customer Modification	None

Script

Properties	Description
Tables	CI_SCR, CI_SCR_L, CI_SCR_CRT, CI_SCR_CRT_GRP, CI_SCR_CRT_GRP_L, CI_SCR_DA, CI_SCR_FLD_MAP, CI_SCR_PRMP,CI, CI_SCR_PRMP_L, CI_SCR_STEP, CI_SCR_STEP_L
Standard Data Fields	Script (SCR_CD)
Customer Modification	None

To Do Type

Properties	Description
Tables	CI_TD_TYPE, CI_TD_TYPE_L, CI_TD_SRTKEY_TY, CI_TD_DRLKEY_TY, CI_TD_SRTKEY_TY_L
Standard Data Fields	To Do Type Code (TD_TYPE_CD)
Customer Modification	Creation Batch Code (CRE_BATCH_CD), Route Batch Code (RTE_BATCH_CD), Priority Flag (TD_PRIORITY_FLG) on To Do Type Table (CI_TD_TYPE)

XAI configuration

Properties	Description
Tables	CI_XAI_ADAPTER, CI_XAI_ADAPTER_L, CI_XAI_CLASS, CI_XAI_CLASS_L, CI_XAI_ENV_HNDL, CI_XAI_ENV_HNDL_L, CI_XAI_FORMAT, CI_XAI_FORMAT_L, CI_XAI_RCVR, CI_XAI_RCVR_L, CI_XAI_RCVR_CTX, CI_XAI_RCVR_RSP, CI_XAI_RCVR_RGRP, CI_XAI_SENDER, CI_XAI_SERNDER_L, CI_XAI_SNDR_CTX, CI_XAI_OPTION
Standard Data Fields	Adapter Id (XAI_ADAPTER_ID), Class Id (XAI_CLASS_ID), Envelope Handler Id (XAI_ENV_HNDL_ID), XAI Format Id (XAI_FORMAT_ID), Receiver Id (XAI_RCVR_ID), Sender Id (XAI_SENDER_ID)
Customer Modification	Option Value (OPTION_VALUE on XAI Option Table (CI_XAI_OPTION))

The following XAI tables might have system data installed upon the initial installation but a subsequence system data upgrade process will not update the content of these table unless the change is documented in the database upgrade guide : CI_XAI_RCVR, CI_XAI_RCVR_L, CI_XAI_RCVR_CTX, CI_XAI_RCVR_RSP, CI_XAI_RCVR_RGRP, CI_XAI_SENDER, CI_XAI_SERNDER_L, CI_XAI_SNDR_CTX

XAI Services

Properties	Description
Tables	CI_XAI_IN_SVC, CI_XAI_IN_SVC_L, CI_XAI_SVC_PARM, CI_XAI_SVC_VERS, CI_XAI_SVC_VERS_L
Standard Data Fields	XAI Inbound Service Id (XAI_IN_SVC_ID), XAI Inbound Service Name (XAI_IN_SVC_NAME)
Customer Modification	XAI Version (XAI_VERSION_ID), Trace (TRACE_SW), Debug (DEBUG_SW), Request XSL (INPUT_XSL), Response XSL (RESPONSE_XSL), Record XSL (RECORD_XSL and Post Error (POST_ERROR_SW) on XAI Inbound Service Table (CI_XAI_IN_SVC)

Oracle Utilities Application Framework Only Tables

All data of the tables in this group belong to the Oracle Utilities Application Framework. No data modification or addition is allowed for these tables by base product development and customer modification. When an environment is upgraded to the next release of the Oracle Utilities Application Framework, the upgrade process will refresh the data in these tables.

- CI_MD_AT_DTL / CI_MD_AT_DTL_L
- CI_MD_ATT_TY
- CI_MD_CTL / CI_MD_CTL_L
- CI_MD_CTL_TMPL
- CI_MD_ELTY / CI_MD_ELTY_L
- CI_MD_ELTY_AT
- CI_MD_LOOKUP / CI_MD_LOOKUP_F
- CI_MD_PDF / CI_MD_PDF_VAL
- CI_MD_MSG / CI_MD_MSG_L
- CI_MD_SRC_TYPE / CI_MD_SRC_TYPE_L
- CI_MD_TMPL / CI_MD_TMPL_L
- CI_MD_TMPL_ELTY
- CI_MD_TMPL_VAR / CI_MD_TMPL_VAR_L
- CI_MD_VAR / CI_MD_VAR_DTL / CI_MD_VAR_DTL_L
- CI_XAI_EXECUTER / CI_XAI_EXECUTER_L

System Table List

This section contains the names of system tables, upgrade actions, and a brief description of the tables. The upgrade actions are explained below.

Keep (KP): The data of the table in the customer's database is kept untouched. No insert or delete is performed to this table by the upgrade process. The initial installation will add necessary data for the system

Merge (MG): The non-base product data of the table in the database is kept untouched. If the data belongs to the base product, any changes pertaining to the new version of the software are performed.

Refresh (RF): The existing data in the table is replaced with the data from the base product table.

Note. New product data is also inserted into tables marked as 'Merge'. If implementers add rows for a customer specific enhancement, it can cause duplication when the system data gets upgraded to the next version. We strongly recommend following the guidelines on how to use designated range of values or prefixes to segregate the implementation data from the base product data.

Table Name	Upgrade Action	Description
CI_ALG	MG	Algorithm
CI_ALG_L	MG	Algorithm Language
CI_ALG_PARM	MG	Algorithm Parameters
CI_ALG_TYPE	MG	Algorithm Type
CI_ALG_TYPE_L	MG	Algorithm Type Language
CI_ALG_TYPE_PRM	MG	Algorithm Type Parameter
CI_ALG_TYPE_PRM_L	MG	Algorithm Type Parameter Language
CI_ALG_VER	MG	Algorithm Version
CI_APP_SVC_ACC	MG	Application Service Access Mode
CI_BATCH_CTRL	MG	Batch Control
CI_BATCH_CTRL_ALG	KP	Batch Control Algorithm
CI_BATCH_CTRL_L	MG	Batch Control Language
CI_BATCH_CTRL_P	MG	Batch Control Parameters
CI_BATCH_CTRL_P_L	MG	Batch Control Parameters Language
CI_CHAR_ENTITY	MG	Characteristic Type Entity
CI_CHAR_TYPE	MG	Characteristic Type
CI_CHAR_TYPE_L	MG	Characteristic Type Language
CI_CHAR_VAL	MG	Characteristic Type Value
CI_CHAR_VAL_L	MG	Characteristic Type Value Language

Table Name	Upgrade Action	Description
CI_CURRENCY_CD	KP	Currency Code
CI_CURRENCY_CD_L	KP	Currency Code Language
CI_DB_INSTR	KP	DB Process Instruction
CI_DB_INSTR_ALG	KP	DB Process Instruction Algorithm
CI_DB_INSTR_L	KP	DB Process Instruction Language
CI_DB_INST_OVRD	KP	DB Process Instruction Override
CI_DB_PROC	KP	DB Process
CI_DB_PROC_L	KP	DB Process Language
CI_DISP_ICON	MG	Display Icon
CI_DISP_ICON_L	MG	Display Icon Language
CI_DISP_PROF	KP	Display Profile
CI_DISP_PROF_L	KP	Display Profile Language
CI_FK_REF	MG	Foreign Key Reference
CI_FK_REF_L	MG	Foreign Key Reference Language
CI_LANGUAGE	MG	Language Code
CI_LOOKUP_FIELD	MG	Lookup Field
CI_LOOKUP_VAL	MG	Lookup Field Value
CI_LOOKUP_VAL_L	MG	Lookup Field Value Language
CI_MD_ATT_TY	RF	MD Element Attribute Type
CI_MD_AT_DTL	RF	MD Element Attribute Type Detail
CI_MD_AT_DTL_L	RF	MD Element Attribute Type Detail Language
CI_MD_CONST	MG	Constraints
CI_MD_CONST_FLD	MG	Constraint Fields
CI_MD_CTL	RF	Generator Control
CI_MD_CTL_L	RF	Generator Control Language
CI_MD_CTL_TMPL	RF	Generator Control Template
CI_MD_ELTY	RF	MD Element Type
CI_MD_ELTY_AT	RF	Element Type Attributes
CI_MD_ELTY_L	RF	Element Type Language
CI_MD_FLD	MG	Field
CI_MD_FLD_L	MG	Field Language

Table Name	Upgrade Action	Description
CI_MD_LOOKUP	RF	MD Lookup Field Value
CI_MD_LOOKUP_F	RF	MD Lookup Field
CI_MD_MENU	MG	Menu Information
CI_MD_MENU_IMOD	MG	Menu Item Module Maint
CI_MD_MENU_ITEM	MG	Menu Item
CI_MD_MENU_ITEM_L	MG	Menu Item Language
CI_MD_MENU_L	MG	Menu Language
CI_MD_MENU_LINE	MG	Menu Line
CI_MD_MENU_LINE_L	MG	Menu Line Language
CI_MD_MENU_MOD	MG	Menu Product Components
CI_MD_MO	MG	Maintenance Object
CI_MD_MO_ALG	MG	Maintenance Object Algorithm
CI_MD_MO_L	MG	Maintenance Object Language
CI_MD_MO_OPT	MG	Maintenance Object Option
CI_MD_MO_TBL	MG	Maintenance Object Table
CI_MD_MO_WRK	MG	Maintenance Object Work Tables
CI_MD_MSG	RF	MD Message
CI_MD_MSG_L	RF	MD Message Language
CI_MD_NAV	MG	Navigation Key
CI_MD_PDF	RF	Predefined Fields
CI_MD_PDF_VAL	RF	Predefined Values
CI_MD_PRG_COM	MG	Program Components
CI_MD_PRG_ELEM	MG	UI Page Elements
CI_MD_PRG_EL_AT	MG	UI Page Element Attributes
CI_MD_PRG_LOC	MG	Program Location
CI_MD_PRG_MOD	MG	Program Module
CI_MD_PRG_SEC	MG	UI Page Sections
CI_MD_PRG_SQL	MG	MD SQL Meta Data
CI_MD_PRG_TAB	MG	UI Tab Meta Data
CI_MD_PRG_VAR	MG	Program Variable
CI_MD_SO	MG	Search Object
CI_MD_SO CG	MG	Search Object Criteria Group

Table Name	Upgrade Action	Description
CI_MD_SOCG_FLD	MG	Search Object Criteria Group Field
CI_MD_SOCG_FLDAT	MG	Search Criteria Group Field Attribute
CI_MD_SOCG_L	MG	Search Object Criteria Group Language
CI_MD_SOCG_SORT	MG	Search Criteria Group Result Sort Order
CI_MD_SO_L	MG	Search Object Language
CI_MD_SO_RSFLD	MG	Search Object Result Field
CI_MD_SO_RSFLDAT	MG	Search Object Result Field Attribute
CI_MD_SRC_TYPE	RF	Source Type
CI_MD_SRC_TYPE_L	RF	Source Type Language
CI_MD_SVC	MG	MD Service
CI_MD_SVC_L	MG	MD Service Language
CI_MD_SVC_PRG	MG	MD Service Program
CI_MD_TAB_MOD	MG	UI Tab Module
CI_MD_TBL	MG	MD Table
CI_MD_TBL_FLD	MG	MD Table Field
CI_MD_TBL_FLD_L	MG	MD Table Field Language
CI_MD_TBL_L	MG	MD Table Language
CI_MD_TMPL	RF	Template
CI_MD_TMPL_ELTY	RF	Template Element Types
CI_MD_TMPL_L	RF	Template Language
CI_MD_TMPL_VAR	RF	Template Variable
CI_MD_TMPL_VAR_L	RF	Template Variable Language
CI_MD_VAR	RF	Variable
CI_MD_VAR_DTL	RF	Variable Detail
CI_MD_VAR_DTL_L	RF	Variable Detail Language
CI_MD_WRK_TBL	MG	Work Table
CI_MD_WRK_TBLFLD	MG	Work Table Field
CI_MD_WRK_TBL_L	MG	Work Table Language
CI_MSG	MG	Message
CI_MSG_CATEGORY	MG	Message Category

Table Name	Upgrade Action	Description
CI_MSG_CATEGORY_L	MG	Message Category Language
CI_MSG_L	MG	Message Language
CI_NAV_OPT	MG	Navigation Option
CI_NAV_OPT_CTXT	MG	Navigation Option Context
CI_NAV_OPT_L	MG	Navigation Option Language
CI_NAV_OPT_USG	MG	Navigation Option Usage
CI_PORTAL	MG	Portal
CI_PORTAL_L	MG	Portal Language
CI_PORTAL_ZONE	MG	Portal Zone
CI_SCR	MG	Script
CI_SCR_CRT	MG	Script Criteria
CI_SCR_CRT_GRP	MG	Script Criteria Group
CI_SCR_CRT_GRP_L	MG	Script Criteria Group Language
CI_SCR_DA	MG	Script Data Area
CI_SCR_FLD_MAP	MG	Script Field Mapping
CI_SCR_L	MG	Script Language
CI_SCR_PRMPPT	MG	Script Prompt
CI_SCR_PRMPPT_L	MG	Script Prompt Language
CI_SCR_STEP	MG	Script Step
CI_SCR_STEP_L	MG	Script Step Language
CI_SEQ	MG	Sequence
CI_TD_DRLKEY_TY	MG	To Do Type Drill Key
CI_TD_SRTKEY_TY	MG	To Do Type Sort Key
CI_TD_SRTKEY_TY_L	MG	To Do Type Sort Key Language
CI_TD_TYPE	MG	To Do Type
CI_TD_TYPE_L	MG	To Do Type Language
CI_USR_NAV_LINK	MG	User Favorite Links
CI_USR_PORTAL	KP	User Portal
CI_USR_ZONE	KP	User Zone
CI_XAI_ADAPTER	MG	XAI Adapter
CI_XAI_ADAPTER_L	MG	XAI Adapter Lang
CI_XAI_CLASS	MG	XAI Class
CI_XAI_CLASS_L	MG	XAI Class Language

Table Name	Upgrade Action	Description
CI_XAI_ENV_HNDL	MG	XAI Envelope Handler
CI_XAI_ENV_HNDL_L	MG	XAI Envelope Handler Language
CI_XAI_EXECUTER	RF	XAI Executer
CI_XAI_EXECUTER_L	RF	XAI Executer Language
CI_XAI_FORMAT	RF	XAI Format
CI_XAI_FORMAT_L	RF	XAI Format Language
CI_XAI_IN_SVC	MG	XAI Inbound Service
CI_XAI_IN_SVC_L	MG	XAI Inbound Service Language
CI_XAI_JNDI_SVR	KP	XAI JNDI Server
CI_XAI_JNDI_SVR_L	KP	XAI JNDI Server Language
CI_XAI_OPTION	KP	XAI Option
CI_XAI_RCVR	KP	XAI Receiver
CI_XAI_RCVR_CTX	KP	XAI Receiver Context
CI_XAI_RCVR_L	KP	XAI Receiver Language
CI_XAI_RCVR_RGRP	KP	XAI Receiver Rule Group
CI_XAI_RCVR_RSP	KP	XAI Receiver Response
CI_XAI_SENDER	KP	XAI Sender
CI_XAI_SENDER_L	KP	XAI Sender Language
CI_XAI_SNDR_CTX	KP	XAI Sender Context
CI_XAI_SVC_PARM	MG	XAI Inbound Service Parameters
CI_XAI_SVC_VERS	MG	XAI Inbound Service Version
CI_XAI_SVC_VERS_L	MG	XAI Inbound Service Version Language
CI_ZONE	MG	Zone
CI_ZONE_HDL	MG	Zone Type
CI_ZONE_HDL_L	MG	Zone Type Language
CI_ZONE_HDL_PRM	MG	Zone Type Parameters
CI_ZONE_HDL_PRM_L	MG	Zone Type Parameters Language
CI_ZONE_L	MG	Zone Language
CI_ZONE_PRM	MG	Zone Parameters
F1_BUS_OBJ	MG	Business Object
F1_BUS_OBJ_ALG	MG	Business Object Algorithm
F1_BUS_OBJ_L	MG	Business Object Language

Table Name	Upgrade Action	Description
F1_BUS_OBJ_OPT	MG	Business Object Option
F1_BUS_OBJ_STATUS	MG	Business Object Status
F1_BUS_OBJ_STATUS_AL G	MG	Business Object Status Algorithm
F1_BUS_OBJ_STATUS_L	MG	Business Object Status Language
F1_BUS_OBJ_STATUS_OP T	MG	Business Object Status Option
F1_BUS_OBJ_STATUS_RS N	MG	Status Reason
F1_BUS_OBJ_STATUS_RS N_CHAR	KP	Status Reason Characteristic
F1_BUS_OBJ_STATUS_RS N_L	MG	Status Reason Language
F1_BUS_OBJ_TR_RULE	MG	Business Object Transition Rule
F1_BUS_OBJ_TR_RULE_L	MG	Business Object Transition Rule Language
F1_BUS_SVC	MG	Business Service
F1_BUS_SVC_L	MG	Business Service Language
F1_DATA_AREA	MG	Data Area
F1_DATA_AREA_L	MG	Data Area Language
F1_DB_OBJECTS_REPO	MG	Database Objects Repository
F1_EXT_LOOKUP_VAL	MG	Extendable Lookup
F1_EXT_LOOKUP_VAL_ L	MG	Extendable Lookup Language
F1_INSTALLATION	KP	Installation Option - Framework
F1_MANAG_CONTENT	MG	Managed Content
F1_MANAG_CONTENT_ L	MG	Managed Content Language
F1_MAP	MG	UI Map
F1_MAP_L	MG	UI Map Language
F1_SCHEMA	MG	Schema
SC_ACCESS_CNTL	MG	User Group Access Control
SC_APP_SERVICE	MG	Application Service
SC_APP_SERVICE_L	MG	Application Service Language
SC_USER	KP	User
SC_USER_GROUP	KP	User Group

Table Name	Upgrade Action	Description
SC_USER_GROUP_L	KP	User Group Language
SC_USR_GRP_PROF	MG	User Group Profile
SC_USR_GRP_USR	KP	User Group User

Appendix E

License and Copyright Notices

License and Copyright notices for associated products:

Third Party Products

Notice concerning usage of ANTLR

Oracle Corporation has used ANTLR in developing this software.

Notice concerning usage of Apache Software

The following are covered under the Apache 2.0 license.

- Apache Axis
- Cgilib
- Commons-BeanUtils
- Commons-Codec
- Commons-Collections
- Commons-HttpClient
- Commons-lang
- Commons-logging
- Commons-Fileupload
- Commons-IO
- Log4j
- Maven
- Qdox
- Tomcat
- Velocity
- Woodstox XML processor
- StAX

/*

* Copyright 1999-2004 The Apache Software Foundation.

*

```
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Apache License

Version 2.0, January 2004

<http://www.apache.org/licenses/>

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on

behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and
You must cause any modified files to carry prominent notices stating that You changed the files; and

You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

Notice concerning usage of ASM

Copyright (c) 2000-2005 INRIA, France Telecom

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the copyright holders nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Notice concerning usage of CruiseControl

CruiseControl, a Continuous Integration Toolkit

Copyright (c) 2001, ThoughtWorks, Inc.

651 W Washington Ave. Suite 600

Chicago, IL 60661 USA

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of ThoughtWorks, Inc., CruiseControl, nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Notice concerning usage of dom4j

BSD style license

Redistribution and use of this software and associated documentation ("Software"), with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain copyright statements and notices. Redistributions must also contain a copy of this document.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name "DOM4J" must not be used to endorse or promote products derived from this Software without prior written permission of MetaStuff, Ltd. For written permission, please contact dom4j-info@metastuff.com.
4. Products derived from this Software may not be called "DOM4J" nor may "DOM4J" appear in their names without prior written permission of MetaStuff, Ltd. DOM4J is a registered trademark of MetaStuff, Ltd.
5. Due credit should be given to the DOM4J Project - <http://www.dom4j.org>

THIS SOFTWARE IS PROVIDED BY METASTUFF, LTD. AND CONTRIBUTORS ``AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL METASTUFF, LTD. OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright 2001-2005 (C) MetaStuff, Ltd. All Rights Reserved.

Notice concerning usage of Ehcache

The Apache Software License, Version 1.1

Copyright (c) 2000 The Apache Software Foundation. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. The end-user documentation included with the redistribution, if any, must include the following acknowledgment:

"This product includes software developed by the Apache Software Foundation (<http://www.apache.org/>)."

Alternately, this acknowledgment may appear in the software itself, if and wherever such third-party acknowledgments normally appear.

4. The names "Apache" and "Apache Software Foundation" must not be used to endorse or promote products derived from this software without prior written permission. For written permission, please contact apache@apache.org.

5. Products derived from this software may not be called "Apache", nor may "Apache" appear in their name, without prior written permission of the Apache Software Foundation.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE APACHE SOFTWARE FOUNDATION OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

=====
=====

This software consists of voluntary contributions made by many individuals on behalf of the Apache Software Foundation. For more information on the Apache Software Foundation, please see <<http://www.apache.org/>>.

Portions of this software are based upon public domain software originally written at the National Center for Supercomputing Applications, University of Illinois, Urbana-Champaign.

Notices concerning usage of Hibernate and c3p0

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.

51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library

(independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Notice concerning usage of International Components for Unicode (ICU4J)

ICU License - ICU 1.8.1 and later

COPYRIGHT AND PERMISSION NOTICE Copyright (c) 1995-2003 International Business Machines Corporation and others All rights reserved. Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, provided that the above copyright notice(s) and this permission notice appear in all copies of the Software and that both the above copyright notice(s) and this permission notice appear in supporting documentation.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE. Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization of the copyright holder.

All trademarks and registered trademarks mentioned herein are the property of their respective owners.

Notice concerning usage of fcrypt

/ crypto/des/fcrypt.c /

/ Copyright (C) 1996 Eric Young (eay@mincom.oz.au)

All rights reserved.

This package is an SSL implementation written by Eric Young (eay@mincom.oz.au).

The implementation was written so as to conform with Netscapes SSL.

This library is free for commercial and non-commercial use as long as the following conditions are adhered to. The following conditions apply to all code found in this distribution, be it the RC4, RSA, lhash, DES, etc., code; not just the SSL code. The SSL documentation included with this distribution is covered by the same copyright terms except that the holder is Tim Hudson (tjh@mincom.oz.au).

Copyright remains Eric Young's, and as such any Copyright notices in the code are not to be removed. If this package is used in a product, Eric Young should be given attribution as the author of the parts of the library used.

This can be in the form of a textual message at program startup or in documentation (online or textual) provided with the package.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. All advertising materials mentioning features or use of this software must display the following acknowledgement: "This product includes cryptographic software written by Eric Young (eay@mincom.oz.au)"

The word 'cryptographic' can be left out if the routines from the library being used are not cryptographic related.

4. If you include any Windows specific code (or a derivative thereof) from the apps directory (application code) you must include an acknowledgement: "This product includes software written by Tim Hudson (tjh@mincom.oz.au)"

THIS SOFTWARE IS PROVIDED BY ERIC YOUNG ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.

IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The licence and distribution terms for any publically available version or derivative of this code cannot be changed. i.e. this code cannot simply be copied and put under another distribution licence [including the GNU Public Licence.]

Notice concerning usage of Jaxen

Copyright 2003 (C) The Werken Company. All Rights Reserved.

Redistribution and use of this software and associated documentation ("Software"), with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain copyright statements and notices. Redistributions must also contain a copy of this document.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name "jaxen" must not be used to endorse or promote products derived from this Software without prior written permission of The Werken Company. For written permission, please contact bob@werken.com.
4. Products derived from this Software may not be called "jaxen" or may "jaxen" appear in their names without prior written permission of The Werken Company. "jaxen" is a registered trademark of The Werken Company.
5. Due credit should be given to The Werken Company. (<http://jaxen.werken.com/>).

THIS SOFTWARE IS PROVIDED BY THE WERKEN COMPANY AND CONTRIBUTORS ``AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE WERKEN COMPANY OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,

EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Notice concerning usage of JOSSO

Copyright (c) 2004-2006, Novascope S.A. and the JOSSO team. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

* Neither the name of the JOSSO team nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Notice concerning usage of libjpeg

The authors make NO WARRANTY or representation, either express or implied, with respect to this software, its quality, accuracy, merchantability, or fitness for a particular purpose. This software is provided "AS IS", and you, its user, assume the entire risk as to its quality and accuracy.

This software is copyright (C) 1991-1998, Thomas G. Lane.

All Rights Reserved except as specified below.

Permission is hereby granted to use, copy, modify, and distribute this software (or portions thereof) for any purpose, without fee, subject to these

conditions:

(1) If any part of the source code for this software is distributed, then this README file must be included, with this copyright and no-warranty notice unaltered; and any additions, deletions, or changes to the original files must be clearly indicated in accompanying documentation.

(2) If only executable code is distributed, then the accompanying documentation must state that "this software is based in part on the work of the Independent JPEG Group".

(3) Permission for use of this software is granted only if the user accepts full responsibility for any undesirable consequences; the authors accept NO LIABILITY for damages of any kind.

These conditions apply to any software derived from or based on the IJG code, not just to the unmodified library. If you use our work, you ought to acknowledge us.

Permission is NOT granted for the use of any IJG author's name or company name in advertising or publicity relating to this software or products derived from it. This software may be referred to only as "the Independent JPEG Group's software".

We specifically permit and encourage the use of this software as the basis of commercial products, provided that all warranty or liability claims are assumed by the product vendor.

Notice concerning usage of libproj4

Copyright (c) 2000, Frank Warmerdam

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies

or substantial portions of the Software. THE SOFTWARE IS PROVIDED "AS IS", WITHOUT

WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Notice concerning usage of libtiff

Copyright (c) 1988-1997 Sam Leffler

Copyright (c) 1991-1997 Silicon Graphics, Inc.

Permission to use, copy, modify, distribute, and sell this software and its documentation for any purpose is hereby granted without fee, provided that (i) the above copyright notices and this permission notice appear in all copies of the software and related documentation, and (ii) the names of Sam Leffler and Silicon Graphics may not be used in any advertising or publicity relating to the software without the specific, prior written permission of Sam Leffler and Silicon Graphics.

THE SOFTWARE IS PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EXPRESS, IMPLIED OR OTHERWISE, INCLUDING WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL SAM LEFFLER OR SILICON GRAPHICS BE LIABLE FOR ANY SPECIAL, INCIDENTAL, INDIRECT OR CONSEQUENTIAL DAMAGES OF ANY KIND, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER OR NOT ADVISED OF THE POSSIBILITY OF DAMAGE,

AND ON ANY THEORY OF LIABILITY, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Notice concerning usage of MX4J

This product includes software developed by the MX4J project (<http://mx4j.sourceforge.net>).

The MX4J License, Version 1.0

Copyright (c) 2001-2004 by the MX4J contributors. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The end-user documentation included with the redistribution, if any, must include the following acknowledgment:

"This product includes software developed by the MX4J project (<http://mx4j.sourceforge.net>)."

Alternately, this acknowledgment may appear in the software itself, if and wherever such third-party acknowledgments normally appear.

4. The name "MX4J" must not be used to endorse or promote products derived from this software without prior written permission. For written permission, please contact biorn_steedom@users.sourceforge.net
5. Products derived from this software may not be called "MX4J", nor may "MX4J" appear in their name, without prior written permission of Simone Bordet.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE MX4J CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Notice concerning usage of PicoContainer

Copyright (c) 2003-2004, PicoContainer Organization

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of the PicoContainer Organization nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Notice concerning usage of QDox

The license used for QDox is derived from the Apache Software License.

The IronSmith Software License, Version 1.1

(This license is derived and fully compatible with the Apache Software License - see <http://www.apache.org/LICENSE.txt>)

Copyright (c) 2002 The IronSmith Project. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The end-user documentation included with the redistribution, if any, must include the following acknowledgment: "This product includes software developed by the IronSmith Project (<http://www.ironsmith.org/>).". Alternately, this acknowledgment may appear in the software itself, if and wherever such third-party acknowledgments normally appear.
4. The names "IronSmith" and "The IronSmith Project" must not be used to endorse or promote products derived from this software without prior written permission. For written permission, please contact help@ironsmith.org.
5. Products derived from this software may not be called "IronSmith" or "QDox", nor may "IronSmith" or "QDox" appear in their name, without prior written permission of the IronSmith Project.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE APACHE SOFTWARE FOUNDATION OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF

USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Notice concerning usage of XStream

XStream is an open source software, made available under a BSD license.

Copyright (c) 2003-2005, Joe Walnes

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of XStream nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Notice concerning usage of Perl

Perl Kit, Version 5

Copyright (C) 1993, 1994, 1995, 1996, 1997, 1998

1999, 2000, 2001, by Larry Wall and others

All rights reserved.

This program is free software; it is being redistributed under the terms of the "Artistic License".

The Artistic License

Preamble

The intent of this document is to state the conditions under which a Package may be copied, such that the Copyright Holder maintains some semblance of artistic control over the development of the package, while giving the users of the package the right to use and distribute the Package in a more-or-less customary fashion, plus the right to make reasonable modifications.

Definitions:

"Package" refers to the collection of files distributed by the Copyright Holder, and derivatives of that collection of files created through textual modification.

"Standard Version" refers to such a Package if it has not been modified, or has been modified in accordance with the wishes of the Copyright Holder.

"Copyright Holder" is whoever is named in the copyright or copyrights for the package.

"You" is you, if you're thinking about copying or distributing this Package.

"Reasonable copying fee" is whatever you can justify on the basis of media cost, duplication charges, time of people involved, and so on. (You will not be required to justify it to the Copyright Holder, but only to the computing community at large as a market that must bear the fee.)

"Freely Available" means that no fee is charged for the item itself, though there may be fees involved in handling the item. It also means that recipients of the item may redistribute it under the same conditions they received it.

1.You may make and give away verbatim copies of the source form of the Standard Version of this Package without restriction, provided that you duplicate all of the original copyright notices and associated disclaimers.

2.You may apply bug fixes, portability fixes and other modifications derived from the Public Domain or from the Copyright Holder. A Package modified in such a way shall still be considered the Standard Version.

3.You may otherwise modify your copy of this Package in any way, provided that you insert a prominent notice in each changed file stating how and when you changed that file, and provided that you do at least ONE of the following:

1.place your modifications in the Public Domain or otherwise make them Freely Available, such as by posting said modifications to Usenet or an equivalent medium, or placing the modifications on a major archive site such as ftp.uu.net, or by allowing the Copyright Holder to include your modifications in the Standard Version of the Package.

2.use the modified Package only within your corporation or organization.

3.rename any non-standard executables so the names do not conflict with standard executables, which must also be provided, and provide a separate manual page for each non-standard executable that clearly documents how it differs from the Standard Version.

4.make other distribution arrangements with the Copyright Holder.

4.You may distribute the programs of this Package in object code or executable form, provided that you do at least ONE of the following:

a)distribute a Standard Version of the executables and library files, together with instructions (in the manual page or equivalent) on where to get the Standard Version.

b)accompany the distribution with the machine-readable source of the Package with your modifications.

c)accompany any non-standard executables with their corresponding Standard Version executables, giving the non-standard executables non-standard names, and clearly documenting the differences in manual pages (or equivalent), together with instructions on where to get the Standard Version.

d)make other distribution arrangements with the Copyright Holder.

5.You may charge a reasonable copying fee for any distribution of this Package. You may charge any fee you choose for support of this Package. You may not charge a fee for this Package itself. However, you may distribute this Package in aggregate with other (possibly commercial) programs as part of a larger (possibly commercial) software distribution provided that you do not advertise this Package as a product of your own.

6.The scripts and library files supplied as input to or produced as output from the programs of this Package do not automatically fall under the copyright of this Package, but belong to whomever generated them, and may be sold commercially, and may be aggregated with this Package.

7.C or perl subroutines supplied by you and linked into this Package shall not be considered part of this Package.

8.The name of the Copyright Holder may not be used to endorse or promote products derived from this software without specific prior written permission.

9.THIS PACKAGE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The End

Notice concerning usage of Mime-Base64 Perl Module

Copyright 1995-1999,2001-2004 Gisle Aas <gisle@ActiveState.com>

This library is free software; you can redistribute it and/or modify it under the same terms as Perl itself.

The standard version of the package that is used can be obtained from <http://www.cpan.org>. Specifically, the software can be obtained from the following link :

<http://search.cpan.org/search%3fmodule=MIME::Base64>

Notice concerning usage of Mime-Lite Perl Module

This is MIME::Lite 3.01 Maintenance release

TERMS AND CONDITIONS

Copyright (c) 1997 by Eryq.

Copyright (c) 1998 by ZeeGee Software Inc.

Copyright (c) 2003 Yves Orton. demerphq (at) hotmail.com.

All rights reserved. This program is free software; you can redistribute it and/or modify it under the same terms as Perl itself.

This software comes with NO WARRANTY of any kind. See the COPYING file in the distribution for details.

The standard version of the package that is used can be obtained from <http://www.cpan.org>. Specifically, the software can be obtained from the following link :

<http://search.cpan.org/search%3fmodule=MIME::Lite>

Notice concerning usage of DBD::DB2 Perl Module

License Agreement for DBD::DB2

PLEASE READ THIS AGREEMENT CAREFULLY BEFORE INSTALLING OR USING THIS PROGRAM. IF YOU INSTALL OR USE THIS PROGRAM, YOU AGREE TO THESE TERMS.

1. This DBD::DB2 code "Program" is owned by International Business Machines Corporation or its subsidiaries (IBM) or IBM's suppliers, and is copyrighted and licensed, not sold. IBM retains title to the Program, and grants the user of the Program "You" an:

irrevocable, worldwide, nonexclusive, perpetual, royalty-free and fully paid-up license

(i) to use, execute, display, perform, and reproduce the Program,

-
- (ii) to prepare derivative works based on the Program,
 - (iii) to distribute copies of the Program and derivative works thereof, and
 - (iv) to authorize others to do all of the above.
 2. You must reproduce the copyright notice and any other legend of ownership on each copy or partial copy of the Program.
 3. IBM would appreciate receiving a copy of derivative works of the Program that You create. You may provide to IBM such derivative works pursuant to the terms of this Agreement and the directions in the README file contained within the Program directory. You represent and warrant to IBM that You are the sole author of, and/or have full exclusive right, title and interest to any and all derivative works You provide to IBM. You further represent that You are under no obligation to assign your rights in such derivative works to any third-party, including without limitation, any current or former employer.
 4. You agree that IBM may utilize all information, ideas, concepts, know-how or techniques furnished by You to IBM in connection with any derivative works You make or have made to the IBM Program, and that You provide to IBM and IBM may, but shall not be obligated to, include such derivative works in the IBM Program or in any IBM product without accounting to You.
 5. With respect to any derivative works of the Program You provide to IBM, You grant to IBM an:
 - irrevocable, worldwide, non-exclusive, perpetual, royalty--free and fully paid-up license
 - (i) to use, execute, display, perform, and reproduce your derivative works,
 - (ii) to prepare derivative works based upon your derivative works,
 - (iii) to distribute copies of your derivative works, and
 - (iv) to authorize others to do all of the above.
 6. YOU UNDERSTAND THAT THE PROGRAM IS BEING PROVIDED TO YOU "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF MERCHANTABILITY, QUALITY, PERFORMANCE, INTELLECTUAL PROPERTY INFRINGEMENT OR FITNESS FOR ANY PARTICULAR PURPOSE. IBM has no obligation to provide service, defect correction, or any maintenance for the Program. IBM has no obligation to supply any Program updates or enhancements to You even if such are or later become available.
 7. IBM accepts no liability for damages You may suffer as a result of your use of the Program. Under no circumstances is IBM liable for any of the following:
 1. third-party claims against You for losses or damages;
 2. loss of, or damage to, your records or data; or
 3. direct damages, lost profits, lost savings, incidental, special, or indirect damages or consequential damages, even if IBM or its authorized supplier, has been advised of the possibility of such damages.
 8. Some jurisdictions do not allow these limitations or exclusions, so they may not apply to You.
 9. You are responsible for the payment of any taxes resulting from this license.
 10. You agree not to bring a legal action more than two years after the cause of action arose.
 11. This license will be governed by and interpreted in accordance with the laws of the State of New York.
 12. This license is the only understanding and agreement IBM has for your use of the Program.

The standard version of the package that is used can be obtained from <http://www.cpan.org>. Specifically, the software can be obtained from the following link :

<http://search.cpan.org/search%3fmodule=DBD::DB2>

Notice concerning usage of DBI Perl Module

DBI by Tim Bunce. This pod text by Tim Bunce, J. Douglas Dunlop, Jonathan Leffler and others. Perl by Larry Wall and the perl5-porters.

COPYRIGHT

The DBI module is Copyright (c) 1994-2004 Tim Bunce. Ireland.

All rights reserved.

This is distributed under the terms of the Artistic License.

The standard version of the package that is used can be obtained from <http://www.cpan.org>. Specifically, the software can be obtained from the following link :

<http://search.cpan.org/search%3fmodule=DBD::DB2>

Notice concerning usage of JCIP Annotations

This software uses the JCIP Annotations library which is copyright (c) 2005 Brian Goetz and Tim Peierls and is released under the Creative Commons Attribution License (<http://creativecommons.org/licenses/by/2.5>). The official home for this software is <http://www.jcip.net>.

Notice concerning usage of YUI Library

Software License Agreement (BSD License)

Copyright (c) 2009, Yahoo! Inc.

All rights reserved.

Redistribution and use of this software in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of Yahoo! Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission of Yahoo! Inc.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT

(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.