

SeeBeyond™ eBusiness Integration Suite

e*Way Intelligent Adapter for PeopleSoft Batch User's Guide

Release 4.5.2



The information contained in this document is subject to change and is updated periodically to reflect changes to the applicable software. Although every effort has been made to ensure the accuracy of this document, SeeBeyond Technology Corporation (SeeBeyond) assumes no responsibility for any errors that may appear herein. The software described in this document is furnished under a License Agreement and may be used or copied only in accordance with the terms of such License Agreement. Printing, copying, or reproducing this document in any fashion is prohibited except in accordance with the License Agreement. The contents of this document are designated as being confidential and proprietary; are considered to be trade secrets of SeeBeyond; and may be used only in accordance with the License Agreement, as protected and enforceable by law. SeeBeyond assumes no responsibility for the use or reliability of its software on platforms that are not supported by SeeBeyond.

e*Gate, e*Insight, e*Way, e*Xchange, e*Xpressway, iBridge, Intelligent Bridge, IQ, SeeBeyond, and the SeeBeyond logo are trademarks and service marks of SeeBeyond Technology Corporation. All other brands or product names are trademarks of their respective companies.

© 1999–2002 by SeeBeyond Technology Corporation. All Rights Reserved. This work is protected as an unpublished work under the copyright laws.

This work is confidential and proprietary information of SeeBeyond and must be maintained in strict confidence.

Version 20020307214341.

Contents

Preface	8
Intended Reader	8
Organization	8
Nomenclature	9
Online Use	9
Writing Conventions	9
Additional Documentation	10
<hr/>	
Chapter 1	
Introduction	11
Overview	11
Batch e*Way	11
ODBC e*Way	11
e*Gate to PeopleSoft	12
PeopleSoft to e*Gate	13
Components	14
<hr/>	
Chapter 2	
Installation	15
System Requirements	15
Supported Operating Systems	15
External System Requirements	16
SOCKS Support	16
OS/390 Support	16
Environment Configuration	16
Installing the e*Way	17
Windows Systems	17
Installation Procedure	17
Subdirectories and Files	19
Environment Configuration	21
UNIX Systems	22

Installation Procedure	22
Subdirectories and Files	22
Environment Configuration	25
Optional Example Files	26
Installation Procedure	26
Subdirectories and Files	27

Chapter 3

System Implementation	28
Overview	28
Implementation Sequence	29
The e*Gate Enterprise Manager	30
Creating a Schema	31
Creating Event Types	32
Generating Event Type Definitions	33
Using the ETD Editor's Build Tool	33
The PeopleSoft Converter Wizard	34
Assigning ETDs to Event Types	37
Defining Collaborations	38
Creating Intelligent Queues	39
Sample Schema	39
Subscribing to an External System	39
Publishing to an External System	40

Chapter 4

Setup Procedures	42
Overview	42
Setting Up the e*Way	43
Creating the e*Way	43
Modifying e*Way Properties	44
Configuring the e*Way	45
Using the e*Way Editor	46
Section and Parameter Controls	47
Parameter Configuration Controls	47
Command-line Configuration	48
Getting Help	48
Changing the User Name	49
Setting Startup Options or Schedules	49
Activating or Modifying Logging Options	51
Activating or Modifying Monitoring Thresholds	52
Troubleshooting the e*Way	53
Configuration Problems	53
System-related Problems	54

Chapter 5

Operational Overview	55
e*Gate to PeopleSoft	55
Outbound Process Flow	56
PeopleSoft to e*Gate	58
Inbound Process Flow	58
Batch Operation	60
Message-Based Operation	60
General Information	60
Receiving Data with a <i>Receive Order</i>	61
Error Reporting	63
ODBC Operation	64
Using SQL Functions	64
Static vs. Dynamic SQL Functions	64
Benefits of Stored Procedures	64
ODBC SQL Type Support	66
e*Way Architecture	67
Event Type Definitions and Collaborations	68
Basic e*Way Processes	69
Initialization Process	70
Connect to External Process	71
Data Exchange Process	72
Disconnect from External Process	75
Shutdown Process	75

Chapter 6

Configuration Parameters	76
Overview	76
General Settings	77
Journal File Name	77
Max Resends Per Message	77
Max Failed Messages	77
Forward External Errors	78
Communication Setup	79
Exchange Data Interval	79
Zero Wait Between Successful Exchanges	79
Start Exchange Data Schedule	80
Stop Exchange Data Schedule	81
Down Timeout	81
Up Timeout	81
Resend Timeout	81
Exchange-if-in-window-on-startup	82
Monk Configuration	83
Specifying Function or File Names	83
Specifying Multiple Directories	83

Load Path	83
Additional Path	83
Auxiliary Library Directories	84
Monk Environment Initialization File	84
Startup Function	85
Process Outgoing Message Function	85
Exchange Data with External Function	86
External Connection Establishment Function	87
External Connection Verification Function	88
External Connection Shutdown Function	88
Positive Acknowledgment Function	89
Negative Acknowledgment Function	90
Shutdown Command Notification Function	91
Dynamic Configuration	92
Enable Message Configuration	92
Publish Status Record on Success	94
Publish Status Record on Error	95
Include Order Record in Error Record	95
Include Payload in Error Record	95
Action on Malformed Command	95

Chapter 7

API Functions 97

Overview 97

Batch e*Way Standard Functions 98

batch-ack	98
batch-exchange-data	99
batch-ext-connect	99
batch-ext-shutdown	100
batch-ext-verify	100
batch-init	101
batch-nak	101
batch-proc-out	102
batch-regular-proc-out	102
batch-shutdown-notify	103
batch-startup	104

ODBC e*Way Standard Functions 105

db-stdver-conn-estab	105
db-stdver-conn-shutdown	107
db-stdver-conn-ver	107
db-stdver-data-exchg	109
db-stdver-data-exchg-stub	109
db-stdver-init	110
db-stdver-neg-ack	110
db-stdver-pos-ack	111
db-stdver-proc-outgoing	112
db-stdver-proc-outgoing-stub	113
db-stdver-shutdown	114
db-stdver-startup	115

Generic e*Way Functions 117

event-commit-to-egate	117
event-rollback-to-egate	118
event-send-to-egate	118
event-send-to-egate-ignore-shutdown	119
event-send-to-egate-no-commit	119
get-logical-name	120

Contents

insert-exchange-data-event	120
send-external-up	121
send-external-down	121
shutdown-request	122
start-schedule	122
stop-schedule	123
waiting-to-shutdown	123

Appendix A

Document Type Definitions	124
Receive XML Messages	124
Error Messages	125
Data Message	126

Appendix B

ODBC Monk Scripts	128
Sample Monk Scripts	128
Initializing Monk Extensions	129
Calling Stored Procedures	130
Inserting Records with Dynamic SQL Statements	132
Updating Records with Dynamic SQL Statements	134
Selecting Records with Dynamic SQL Statements	136
Deleting Records with Dynamic SQL Statements	138
Inserting a Binary Image to a Database	139
Retrieving an Image from a Database	142
Common Supporting Routines	144

Index	147
--------------	------------

Preface

This Preface contains information regarding the User's Guide itself.

P.1 Intended Reader

The reader of this guide is presumed to be a developer or system administrator with responsibility for maintaining the SeeBeyond™ e*Gate™ Integrator system, and have a working knowledge of:

- Windows NT/2000 and/or UNIX operations and administration
- Windows-style GUI operations
- FTP and ODBC concepts and operations
- Integrating PeopleSoft Batch applications with external systems

P.2 Organization

This User's Guide is organized roughly into two parts. The first part, consisting of Chapters 1-4, introduces the e*Way and describes the procedures for installing and setting up the e*Way, and implementing a working system incorporating the e*Way. Chapter 3 also contains descriptions of the sample schemas provided with the product. These can be used to test your system following installation and, if appropriate, as templates you can modify to produce your own custom schemas. This part should be of particular interest to a System Administrator or other user charged with the task of getting the system up and running.

The second part, consisting of Chapters 5-8, describes the details of e*Way operation and configuration, including descriptions of the API functions. This part should be of particular interest to a Developer involved in customizing the e*Way for a specific purpose. Information contained in this part that is necessary for the initial setup of the e*Way is cross-referenced in the first part of the guide, at the appropriate points in the procedures.

P.3 Nomenclature

Note that for purposes of brevity, the e*Way Intelligent Adapter for PeopleSoft Batch is frequently referred to as the PeopleSoft Batch e*Way, or simply the e*Way.

P.4 Online Use

This User's Guide is provided in Adobe Acrobat's Portable Document Format (PDF). As such, it can be printed out on any printer or viewed online. When viewing online, you can take advantage of the extensive hyperlinking imbedded in the document to navigate quickly throughout the Guide.

Hyperlinking is available in:

- The Table of Contents
- The Index
- Within the chapter text, indicated by **blue print**

Existence of a hyperlink *hotspot* is indicated when the hand cursor points to the text. Note that the hotspots in the Index are the *page numbers*, not the topics themselves. Returning to the spot you hyperlinked from is accomplished by right-clicking the mouse and selecting **Go To Previous View** on the resulting menu.

P.5 Writing Conventions

The writing conventions listed in this section are observed throughout this document.

Monospaced (Courier) Font

Computer code and text to be typed at the command line are set in Courier as shown below.

```
Configuration forBOB_Promotion  
java -jar ValidationBuilder.jar
```

Variables within a command line are set in Courier italic as shown below.

```
stcregutl -rh host-name -un user-name -up password -sf
```

Bold Sans-serif Font

- User Input: Click **Apply** to save, or **OK** to save and close.
- File Names and Paths: In the **Open** field, type **D:\setup\setup.exe**.
- Parameter, Function, and Command Names: The default parameter **localhost** is normally only used for testing; the Monk function **iq-put** places an Event into an IQ.

P.6 Additional Documentation

- Many of the procedures included in this User's Guide are described in greater detail in the *e*Gate Integrator User's Guide*.
- For descriptions of the Batch e*Way, see the *Batch e*Way Intelligent Adapter User's Guide*.
- For descriptions of the ODBC e*Way, see the *e*Way Intelligent Adapter for ODBC User's Guide*.

Introduction

1.1 Overview

The PeopleSoft Batch e*Way uses features of the SeeBeyond Batch e*Way and the SeeBeyond ODBC e*Way. The following sections describe both of those e*Ways. For more detailed information, see [Chapter 5](#).

1.1.1 Batch e*Way

The Batch e*Way supports standard FTP according to RFC-959. The Batch e*Way supports the following commands:

APPE	NOOP	RNTO
CWD	PASS	SITE
DELE	QUIT	STOR
LIST	RETR	TYPE
MKD	RNFR	USER

1.1.2 ODBC e*Way

The ODBC e*Way uses a Monk extension library to issue SQL (Structured Query Language) statements. The library contains functions to access the database and generate SQL statements. SQL is the language used to communicate with the database server to access and manipulate data. By populating a database with the data flowing through an integration engine, all the information available to an integrated delivery network (IDN) is stored for evaluation. This allows the ODBC e*Way to operate independently of the underlying DBMS (database management system).


To access the database, you execute an SQL command, which is the American National Standards Institute (ANSI) standard language for operating upon relational databases. The language contains a large set of operators for defining and manipulating tables. SQL statements can be used to create, alter, and drop tables from a database.

1.1.3 e*Gate to PeopleSoft

A data file from the source application is passed to e*Gate for transformation, and then loaded directly into the PeopleSoft application tables using SQL commands from the ODBC e*Way. The main components of this PeopleSoft-inbound batch-mode interface include:

- A source-specific e*Way, to transfer a source data file.
- e*Gate Integrator, to route the data.
- An ODBC e*Way, to transform and load the data into the PeopleSoft system
- A file-handling e*Way, to process failed transactions.

Figure 1 e*Gate-to-PeopleSoft Interface Overview




1.1.4 PeopleSoft to e*Gate

A PeopleSoft-outbound batch-mode interface involves the extraction of data from the PeopleSoft application tables, the processing and manipulation of that data, and the placement of the resulting data into an interface table or file. The data in the interface table or file is then sent to e*Gate for transformation and routing. The main components of an outbound batch interface include:

- An e*Way (either ODBC or Batch), to retrieve a data table or file.
- e*Gate, to transform and route the data.

Figure 2 PeopleSoft-to-e*Gate Interface Overview



The PeopleSoft-to-e*Gate interface was designed to be as flexible as possible. Most batch interfaces run on a scheduled basis, but this design also allows for an interface to be initiated by a remote function call (RFC) within the interface program. The design can accommodate interface data written to either an interface table or an interface file.

1.1.5 Components

The PeopleSoft Batch e*Way incorporates the following components:

- Executable file (installed with e*Gate Integrator)
 - ♦ **stcewgenericmonk.exe**
- Default configuration files
 - ♦ **batch.def**
 - ♦ **dart.def**
- Monk function scripts, discussed in [Chapter 6](#)
- Monk library files, discussed in [Chapter 7](#)

For a list of installed files, see [Chapter 2](#).

Installation

This chapter describes the requirements and procedures for installing the e*Way Intelligent Adapter for PeopleSoft Batch. Following installation, you must configure it for your system (see [Chapter 6](#)) and incorporate it into a schema (see [Chapter 3](#)).

2.1 System Requirements

To use the e*Way Intelligent Adapter for PeopleSoft Batch, you need the following:

- 1 An e*Gate Participating Host, version 4.5.1 or later.
- 2 A TCP/IP network connection.
- 3 A connection to an FTP server.
- 4 Sufficient free disk space to accommodate e*Way files:
 - ♦ Approximately 1.2 MB on Windows systems
 - ♦ Approximately 5.1 MB on Solaris systems

Note: Additional disk space is required to process and queue the data that this e*Way processes; the amount necessary varies based on the type and size of the data being processed.

2.1.1 Supported Operating Systems

Note: The e*Gate Enterprise Manager GUI runs only on the Windows operating system.

The e*Way Intelligent Adapter for PeopleSoft Batch is available on the following operating systems:

- Windows 2000, Windows 2000 SP1, and Windows 2000 SP2
- Windows NT 4.0 SP 6a
- Solaris 2.6, Solaris 7, and Solaris 8

2.1.2 External System Requirements

- A *full version* of PeopleTools 7.5.3.
- PeopleSoft HRMS 7.5.
- A database client: i.e., Oracle7 Oracle8 or Oracle8i, Sybase (OpenClient), Informix (Client SDK), etc.
- An FTP server compliant with RFC-959.

Note: A user name and password granting appropriate access to the FTP server must be available for the e*Way's use.

2.1.3 SOCKS Support

SOCKS is a generic proxy protocol for TCP/IP-based networking applications. When an application client needs to connect to an application server, the client connects to a SOCKS proxy server. The proxy server connects to the application server on behalf of the client, and relays data between the client and the application server. For the application server, the proxy server is the client.

The Batch e*Way supports the SOCKS version 5 Authentication protocol. To enable SOCKS 5 support, the SOCKS server name and port number, as well as the user name and encrypted password, must be specified in the configuration file. Details of these configuration parameters are provided in the *Batch e*Way Intelligent Adapter User's Guide*.

2.1.4 OS/390 Support

The e*Gate system now supports OS/390. However, OS/390 systems use the EBCDIC character set. As a consequence, ASCII-based systems cannot directly transport data to an EBCDIC-based system. ASCII to EBCDIC data conversion is necessary when data is sent from UNIX/Windows to OS/390. This data conversion should take place within the Collaboration.

To transport any EBCDIC data to an ASCII-based system (UNIX or Windows), you must first convert the data by using the **ebcdic->ascii** Monk function. Refer to the *Monk Developer's Reference* for details about that function.

See also the *Batch e*Way Intelligent Adapter User's Guide*, which describes options for data transfer modes to an FTP server.

2.2 Environment Configuration

No changes are necessary to the Participating Host's operating environment or to the e*Gate system to support the operation of this e*Way. No configuration changes required in the external system; all necessary configuration changes can be made within e*Gate.

2.3 Installing the e*Way

2.3.1 Windows Systems


Installation Procedure

Note: *The installation utility detects and suggests the appropriate installation directory. Use this directory unless advised otherwise by SeeBeyond. You must have Administrator privileges to install this e*Way.*

To install the e*Way on a Windows NT or Windows 2000 system

- 1 Log in as an Administrator on the workstation on which you want to install the e*Way.
- 2 Exit all Windows programs and disable any anti-virus applications before running the setup program.
- 3 Insert the e*Way installation CD-ROM into the CD-ROM drive.
- 4 If the CD-ROM drive's Autorun feature is enabled, the setup application should launch automatically. Otherwise, use the Windows Explorer or the Control Panel's Add/Remove Applications feature to launch the file `setup.exe` on the CD-ROM drive.
- 5 The InstallShield setup application launches. Follow the on-screen instructions until you come to the Choose Product screen.


Figure 3 Choose Product Dialog



- 6 Check Add-ons, then click Next. Again follow the on-screen instructions.


- 7 When the Select Components dialog box appears, highlight—but do not check—eWays, and then click Change.

Figure 4 Select Components Dialog



- 8 When the Select Sub-components dialog box appears, check the PeopleSoft Batch e*Way.

Figure 5 Select e*Way Dialog



- 9 Click Continue, and the Select Components dialog box reappears.
- 10 Click Next and continue with the installation.

Subdirectories and Files

Note: *Installing the e*Way Intelligent Adapter for PeopleSoft Batch installs both the Batch e*Way and the ODBC e*Way. Both the Java and Monk versions of the Batch e*Way are installed; however, only the files used by the Monk version are used by this e*Way and, therefore, are listed in this section.*

By default, the InstallShield installer creates the following subdirectories and installs the following files within the \eGate\client tree on the Participating Host, and the \eGate\Server\registry\repository\default tree on the Registry Host.

Table 1 Participating Host & Registry Host

Subdirectories	Files
\bin\	stcodbctest.exe stcstruct.exe stc_dbapps.dll stc_dbmonkext.ctl stc_dbmonkext.dll stc_dbodbc.dll stc_ewftp.ctl stc_ewftp.dll stc_monkfilesystem.dll
\configs\FtpHeuristics\	FtpHeuristics.cfg
\configs\stcewgenericmonk\	batch.def batchFtpRule.txt dart.def dartRule.txt ScFtp3.6To4.1Rule.txt
\etd\	dbwizard.ctl
\monk_library\	dart.gui
\monk_library\batch\ (continued on next page)	batch-ack.monk batch-dynamic-init.monk batch-dynamic-proc-out.monk batch-dynamic-send-to-egate.monk batch-exchange-data.monk batch-exchange-utils.monk batch-ext-connect.monk batch-ext-shutdown.monk batch-ext-verify.monk batch-fetch-files-from-remote.monk batch-fetch-named-files.monk batch-init.monk batch-nak.monk batch-persist.monk batch-post-transfer.monk batch-proc-out.monk batch-regular-init.monk batch-regular-proc-out.monk batch-send-path-file.monk

Table 1 Participating Host & Registry Host

Subdirectories	Files
\monk_library\batch\ (continued)	batch-shutdown-notify.monk batch-startup.monk batch-utils.monk batch-validate-params.monk file-ext-connect.monk file-ext-shutdown.monk file-ext-verify.monk file-fetch-path.monk file-fetch.monk file-init.monk file-remote-path-list.monk file-remote-post-transfer.monk file-rmt-list.monk file-rmt-post-transfer.monk file-send-path-file.monk file-send.monk file-startup.monk file-validate-params.monk ftp-connect.monk ftp-disconnect.monk ftp-ext-connect.monk ftp-ext-shutdown.monk ftp-ext-verify.monk ftp-fetch-path.monk ftp-fetch.monk ftp-init.monk ftp-pre-post-commands.monk ftp-remote-path-list.monk ftp-remote-post-transfer.monk ftp-rmt-list.monk ftp-rmt-post-transfer.monk ftp-send-path-file.monk ftp-send.monk ftp-startup.monk ftp-validate-params.monk local-post-transfer.monk
\monk_library\common\ 	batch_eway_data.dtd batch_eway_data.ssc batch_eway_error.dtd batch_eway_error.ssc batch_eway_order.dtd batch_eway_order.ssc

Table 1 Participating Host & Registry Host

Subdirectories	Files
\\monk_library\dart\	db-sanitize-symbol.monk db-stdver-eway-funcs.monk db-struct-bulk-insert.monk db-struct-call.monk db-struct-execute.monk db-struct-fetch.monk db-struct-insert.monk db-struct-select.monk db-struct-update.monk db2msg-display.monk db2msg.ssc db_bind.monk odbcmsg-display.monk odbcmsg.ssc oramsg-display.monk oramsg.ssc sybmsg-display.monk sybmsg.ssc
\\stcgui\ctls\	guidart.ctl

By default, the InstallShield installer also installs the following files within the \\eGate\Server\registry\repository\default tree on the Registry Host.

Table 2 Registry Host Only

Subdirectories	Files
\	stcewbatch.ctl stcewodbc.ctl

Environment Configuration

No changes are required to the Participating Host's operating environment to support this e*Way.

2.3.2 UNIX Systems

Installation Procedure

Note: You are not required to have root privileges to install this e*Way. Log on under the user name that you wish to own the e*Way files. Be sure that this user has sufficient privilege to create files in the e*Gate directory tree.

To install the e*Way on a UNIX system

- 1 Log onto the workstation containing the CD-ROM drive and, if necessary, mount the drive.
- 2 Insert the e*Way installation CD-ROM into the CD-ROM drive.
- 3 At the shell prompt, type

```
cd /cdrom
```
- 4 Start the installation script by typing:

```
setup.sh
```
- 5 A menu appears, with several options. Select the **Install e*Way** option, and follow any additional on-screen instructions.

Note: The installation utility detects and suggests the appropriate installation directory. Use this directory unless advised otherwise by SeeBeyond. Note also that **no spaces** should appear in the installation path name.

Subdirectories and Files

Note: Installing the e*Way Intelligent Adapter for PeopleSoft Batch installs both the Batch e*Way and the ODBC e*Way. Both the Java and Monk versions of the Batch e*Way are installed; however, only the files used by the Monk version are used by this e*Way and, therefore, are listed in this section.

The preceding installation procedure installs the following files only within the /eGate/Server/registry/repository/default tree on the Registry Host.

Table 3 Registry Host Only

Subdirectories	Files
/	stcewbatch.ctl stcewodbc.ctl

The preceding installation procedure also creates the following subdirectories and installs the following files within the /eGate/client tree on the Participating Host, and the /eGate/Server/registry/repository/default tree on the Registry Host.

Table 4 Participating Host & Registry Host

Subdirectories	Files
/bin/	stcodbctest.exe stcstruct.exe stc_dbapps.dll stc_dbmonkext.ctl stc_dbmonkext.dll stc_dbodbc.dll stc_ewftp.ctl stc_ewftp.dll stc_monkfilesys.dll
/configs/FtpHeuristics/	FtpHeuristics.cfg
/configs/stcewgenericmonk/	batch.def batchFtpRule.txt dart.def dartRule.txt ScFtp3.6To4.1Rule.txt
/etd/	dbwizard.ctl
/monk_library/	dart.gui
/monk_library/batch/	batch-ack.monk batch-dynamic-init.monk batch-dynamic-proc-out.monk batch-dynamic-send-to-egate.monk batch-exchange-data.monk batch-exchange-utils.monk batch-ext-connect.monk batch-ext-shutdown.monk batch-ext-verify.monk batch-fetch-files-from-remote.monk batch-fetch-named-files.monk batch-init.monk batch-nak.monk batch-persist.monk batch-post-transfer.monk batch-proc-out.monk batch-regular-init.monk batch-regular-proc-out.monk batch-send-path-file.monk batch-shutdown-notify.monk batch-startup.monk batch-utils.monk batch-validate-params.monk file-ext-connect.monk file-ext-shutdown.monk file-ext-verify.monk file-fetch.monk file-fetch-path.monk file-init.monk file-remote-path-list.monk
(continued on next page)	

Table 4 Participating Host & Registry Host

Subdirectories	Files
/monk_library/batch/ (continued)	file-remote-post-transfer.monk file-rmt-list.monk file-rmt-post-transfer.monk file-send-path-file.monk file-send.monk file-startup.monk file-validate-params.monk ftp-connect.monk ftp-disconnect.monk ftp-ext-connect.monk ftp-ext-shutdown.monk ftp-ext-verify.monk ftp-fetch-path.monk ftp-fetch.monk ftp-init.monk ftp-pre-post-commands.monk ftp-remote-path-list.monk ftp-remote-post-transfer.monk ftp-rmt-list.monk ftp-rmt-post-transfer.monk ftp-send-path-file.monk ftp-send.monk ftp-startup.monk ftp-validate-params.monk local-post-transfer.monk
/monk_library/common/	batch_eway_data.dtd batch_eway_data.ssc batch_eway_error.dtd batch_eway_error.ssc batch_eway_order.dtd batch_eway_order.ssc
/monk_library/dart/	db-sanitize-symbol.monk db-stdver-eway-funcs.monk db-struct-bulk-insert.monk db-struct-call.monk db-struct-execute.monk db-struct-fetch.monk db-struct-insert.monk db-struct-select.monk db-struct-update.monk db2msg-display.monk db2msg.ssc db_bind.monk odbcmmsg-display.monk odbcmmsg.ssc oramsg-display.monk oramsg.ssc sybmsg-display.monk sybmsg.ssc

Table 4 Participating Host & Registry Host

Subdirectories	Files
/stcgui/ctls/	guidart.ctl

Environment Configuration

No changes are required to the Participating Host's operating environment to support this e*Way.

2.4 Optional Example Files

The installation CD contains two sample schema, **IB_psoft** and **OB_psoft**, located in the `samples\ewpsoft` directory. To use these schemas, you must load them onto your system using the following procedure. See [Sample Schema](#) on page 39 for descriptions of the sample schema and instructions regarding its use.


Note: *The PeopleSoft Batch e*Way must be properly installed on your system before you can run the sample schema.*

2.4.1 Installation Procedure

To load a sample schema


- 1 Invoke the **Open Schema** dialog box and select **New** (see Figure 6).

Figure 6 Open Schema Dialog



- 2 Type the name you want to give to the schema (for example, **IB.Sample**)
- 3 Select **Create from export** and navigate to the directory containing the sample schema by clicking the **Find** button (see Figure 7).

Figure 7 New Schema Dialog



- 4 Select the desired archive file (*.zip) and click **Open**.

Note: The schema installs with the host name **localhost** and control broker name **localhost_cb**. If you want to assign your own names, copy the file *.zip to a local directory and extract the files. Using a text editor, edit the file *.exp, replacing all instances of the name **localhost** with your desired name. Add the edited .exp file back into the .zip file.

2.4.2 Subdirectories and Files

The preceding process creates the following subdirectories and installs the following files within the \eGate\client\eGateImport tree on the Participating Host. These files also are committed to their own schemas on the Registry Host.

Table 5 Subdirectories and Files - IB_psoft

Subdirectories	Files
\	IB_psoft.ctl IB_psoft.exp
\IB_psoft\runtime\configs\stcewfile\	dartfeeder.cfg dartfeeder.sc
\IB_psoft\runtime\configs\stcewgenericmonk\	Dart.cfg Dart.sc
\IB_psoft\runtime\data\	IB_DART.dat
\IB_psoft\runtime\monk_scripts\common\	IB_ERROR_HANDLER.tsc RIDE_IB.ssc RIDE_IB_DART.dsc RIDE_IB_DART.ssc

Table 6 Subdirectories and Files - OB_psoft

Subdirectories	Files
\	OB_psoft.ctl OB_psoft.exp
\OB_psoft\runtime\configs\stcewfile\	eater.cfg eater.sc
\OB_psoft\runtime\configs\stcewgenericmonk\	dartpoll.cfg dartpoll.sc
\OB_psoft\runtime\data\	Stc_ride.dat Stc_ride.dms
\OB_psoft\runtime\monk_scripts\common\	OB_DART.dsc OB_DART.ssc

System Implementation

In this chapter we summarize the procedures required for implementing a working system incorporating the e*Way Intelligent Adapter for PeopleSoft Batch. Please see the *e*Gate Integrator User's Guide* for additional information.

3.1 Overview

This e*Way provides a specialized transport component for incorporation into an operational Schema. The schema also contains Collaborations, linking different data or Event types, and Intelligent Queues. Typically, other e*Way types also are used as components of the Schema.

Topics included in this chapter include:

[The e*Gate Enterprise Manager](#) on page 30

[Creating a Schema](#) on page 31

[Creating Event Types](#) on page 32


[Generating Event Type Definitions](#) on page 33

[Defining Collaborations](#) on page 38

[Creating Intelligent Queues](#) on page 39

[Sample Schema](#) on page 39

3.1.1 Implementation Sequence




- 1 The first step is to create a new Schema—the subsequent steps apply only to this Schema (see [Creating a Schema](#) on page 31).
- 2 The second step is to define the Event Types you are transporting and processing within the Schema (see [Creating Event Types](#) on page 32).
- 3 Third, you need to associate the Event Types created in the previous step with Event Type Definitions (ETDs) derived from the applicable Business Rules (see [Generating Event Type Definitions](#) on page 33).
- 4 The fourth step is to create and configure the required e*Ways (see [Chapter 4](#)).
- 5 Next is to define and configure the Collaborations linking the Event Types from step 2 (see [Defining Collaborations](#) on page 38).
- 6 Now you need to create Intelligent Queues to hold published Events (see [Creating Intelligent Queues](#) on page 39).
- 7 Finally, you must test your Schema. Once you have verified that it is working correctly, you may deploy it to your production environment.

3.2 The e*Gate Enterprise Manager

First, here is a brief look at the e*Gate Enterprise Manager. The general features of the e*Gate Enterprise Manager window are shown in Figure 8. See the *e*Gate Integrator User's Guide* for a detailed description of the features and use of the Enterprise Manager.

Figure 8 e*Gate Enterprise Manager Window (Components View)



Use the Navigator and Editor panes to view the e*Gate components. Note that you may only view components of a single schema at one time, and that all operations apply only to the current schema. All procedures in this chapter should be performed while displaying the Components Navigator pane.

3.3 Creating a Schema


A schema is the structure that defines e*Gate system parameters and the relationships between components within the e*Gate system. Schemas can span multiple hosts.

Because all setup and configuration operations take place within an e*Gate schema, a new schema must be created, or an existing one must be started before using the system. Schemas store all their configuration parameters in the e*Gate Registry.

To select or create a schema

- 1 Invoke the **Open Schema** dialog box and **Open** an existing schema or click **New** to create a new schema.

Figure 9 Open Schema Dialog




- 2 Enter a new schema name and click **Open**.
- 3 The e*Gate Enterprise Manager then opens under your new schema name.
- 4 From the **Options** menu, click on **Default Editor** and select **Monk**.
- 5 Select the **Components** tab, found at the bottom of the Navigator pane of the e*Gate Enterprise Manager window.
- 6 You are now ready to begin creating the necessary components for this new schema.

3.4 Creating Event Types

Within e*Gate, messages and/or packages of data are defined as Events. Each Event must be categorized into a specific Event Type within the schema.

To define the Event Types

- 1 In the e*Gate Enterprise Manager's Navigator pane, select the Event Types folder.
- 2 On the Palette, click the New Event Type button .
- 3 In the New Event Type Component box, enter the name for the input Event Type and click **Apply**. Use this method to create all required Event Types, for example:
 - ♦ InboundEvent
 - ♦ ValidEvent
 - ♦ InvalidEvent
- 4 After you have created the final Event Type, click **OK**.


3.5 Generating Event Type Definitions

3.5.1 Using the ETD Editor's Build Tool

The Event Type Definition Editor's Build tool automatically creates an Event Type Definition file based upon sample data. Use this procedure to create an Event Type Definition based upon the data your installation requires.


Note: Be sure to set the Default Editor to Monk, from the Options menu in the e*Gate Enterprise Manager.

To create an Event Type Definition using the Build tool

- 1 Launch the ETD Editor by clicking  in the e*Gate Enterprise Manager tool bar.
- 2 On the ETD Editor's tool bar, click **Build**.

The *Build an Event Type Definition* dialog box opens.

Figure 10 Build Event Type Definition Dialog




- 3 In the *File name* box, type the name of the ETD file you want to build.

Note: The Editor automatically supplies the .ssc extension.

- 4 Click Next. A new dialog box appears, as shown in Figure 11.

Figure 11 Building the ETD Dialog




- 5 Under *Build From*, select **Library Converter**.
- 6 Under *Select a Library Converter*, select **PeopleSoft Converter**.
- 7 In the *Additional Command Line Arguments* box, type any additional arguments, if desired.
- 8 Click **Finish**, and the PeopleSoft Converter Wizard appears.
- 9 Follow the Wizard's instructions to finish building the ETD file.

The PeopleSoft Converter Wizard


The PeopleSoft Converter Wizard consists of a series of two dialog boxes, which ask for specific parameters. They are the *Login Screen* and the *Select Activity Name and Message Definition* dialog boxes.

Figure 12 Converter Wizard - Login Screen Dialog



- 1 Enter the following information when the *Login Screen* dialog box opens:
 - Machine Name or IP Address**—host name or IP address of the PeopleSoft application host.
 - Port Number** —communication port number.
 - Operator ID**—your login name.
 - Operator Password**—your login password.
- 2 After entering the information, click *Next*. The *Select Activity Name and Message Definition* dialog box appears.

Figure 13 Converter Wizard - Select Activity Name and Message Definition Dialog



- 3 Enter the requested Activity Name and Message Definition.

Activity Name—the name of the PeopleSoft Activity.

Message Definition—the name of the PeopleSoft Message Definition to be used to generate the e*Gate Event Type Definition.

- 4 Click **Finish**.

The e*Gate Event Type Definition is then generated automatically and displayed in the ETD Editor.

3.5.2 Assigning ETDs to Event Types

After you have created the e*Gate system's ETD files, you can assign them to Event Types you have already created.

To assign ETDs to Event Types



- 1 In the Enterprise Manager window, select the **Event Types** folder in the Navigator/Components pane.
- 2 In the Editor pane, select one of the Event Types you created.
- 3 Right-click on the Event Type and select **Properties** (or click  in the toolbar). The Event Type Properties dialog box appears. See Figure 14.

Figure 14 Event Type Properties Dialog Box



- 4 Under Event Type Definition, click **Find**, and the Event Type Definition Selection dialog box appears (it is similar to the Windows Open dialog box).
- 5 Open the **monk_scripts** folder, then select the desired file name (.ssc). It is usually found in the **common** sub-folder, but may be in a sub-folder specific to the e*Way.
- 6 Click **Select**. The file populates the Event Type Definition field.

- 7 To save any work in the properties dialog box, click **Apply** to enter it into the system.
- 8 When finished assigning ETDs to Event Types, click **OK** to close the properties dialog box and apply all the properties.


Each Event Type is now associated with the specified Event Type Definition.

3.6 Defining Collaborations

After you have created the required Event Type Definitions, you must define a Collaboration to transform the incoming Event into the desired outgoing Event.

Collaborations are e*Way components that receive and process Event Types, then forward the output to other e*Gate components. Collaborations consist of the Subscriber, which “listens” for Events of a known type or from a given source, and the Publisher, which distributes the transformed Event to a specified recipient. The same Collaboration cannot be assigned to more than one e*Gate component.

Figure 15 Collaborations



The Collaboration is driven by a Collaboration Rule script, which defines the relationship between the incoming and outgoing ETDs. You can use an existing Collaboration Rule script, or use the Monk programming language to write a new Collaboration Rule script. Once you have written and successfully tested a script, you can then add it to the system’s run-time operation.

Collaborations are defined using the e*Gate Monk Collaboration Rules Editor. See the *e*Gate Integrator User’s Guide* for instructions on using this Editor. The file extension for Monk Collaboration Rules is **.tsc**.

3.7 Creating Intelligent Queues

The final step is to create and associate an IQ for the PeopleSoft Batch e*Way. IQs manage the exchange of information between components within the e*Gate system, providing non-volatile storage for data as it passes from one component to another. IQs use IQ Services to transport data. IQ Services provide the mechanism for moving Events between IQs, handling the low-level implementation of data exchange (such as system calls to initialize or reorganize a database). See the *e*Gate Integrator User's Guide* for complete information on queuing options and procedures for creating IQs.

3.8 Sample Schema


The e*Gate CD includes two sample schemas, located in the `samples\ewpsoft` directory, that illustrate both the inbound and outbound modes of operation. See [Optional Example Files](#) on page 26 for information on sample schema installation.

3.8.1 Subscribing to an External System

In this example, the Batch e*Way fetches two files from the remote UNIX machine **wellington** every 24 hours, using the FTP protocol. These files are stored in the home directory of user **adam**, under the subdirectory **pub/download**.

Figure 16 below shows a diagram of this setup.

Figure 16 Subscribe-to-external-system Setup



This setup has the following additional characteristics:

- The names of the two files are **file1.txt** and **file2.txt**. No other files are required.
- The two files contain multiple records delimited by a new line (`\n`) character.
- After retrieving the files from the remote system, the Batch e*Way deletes the remote copy.
- The last seven day's worth of files on the local system are kept.

The Table 7 lists the most critical parameters and the settings required to achieve the setup described previously.

Table 7 Parameters for the Input Example


Section	Parameter	Value
Communication Setup	Start Exchange Data Schedule	Repeatedly, every 24 hours
External Host Setup	Host Type	UNIX
	External Host Name	wellington
	User Name	adam
	Encrypted Password	*****
	File Transfer Method	FTP
Subscribe To External	Remote Directory Name	pub/download
	Remote File Regexp	^file[12].txt\$
	Record Type	Delimited
	Record Delimiter	\n
	Delimiter on Last Record	Yes
	Remote Command After Transfer	delete
	Local Command After Transfer	archive
	Local Rename or Archive Name	d:\archive/%a

3.8.2 Publishing to an External System

In this example, the Batch e*Way sends a file containing new line (\n) delimited messages to the remote UNIX machine **wellington**, using the FTP protocol. The file is created in the subdirectory **pub/upload**, under the user **adam**.

Figure 17 below shows a diagram of this setup.

Figure 17 Publish-to-external-system Setup



This file is sent once every hour under the name **myfile.tmp**, and is renamed **myfile.txt** after it arrives. This technique can be used if there is a process on the remote machine

watching for a file to be created, but we want to make sure that it does not see the file until it is there in its entirety.

A copy of the file on the local system is not required and is deleted.

The Table 8 below lists the most critical parameters and the settings required to achieve the setup described previously.

Table 8 Parameters for the Output Example

Section	Parameter	Value
Communication Setup	Start Exchange Data Schedule	Repeatedly, every 1 hour
External Host Setup	Host Type	UNIX
	External Host Name	wellington
	User Name	adam
	Encrypted Password	*****
	File Transfer Method	FTP
Publish To External	Remote Directory Name	pub/upload
	Remote File Name	myfile.tmp
	Append or Overwrite when Transferring Files	Overwrite
	Record Type	Delimited
	Record Delimiter	\n
	Delimiter on Last Record	Yes
	Remote Command After Transfer	rename
	Local Command After Transfer	delete
	Remote Rename or Archive Name	myfile.txt

Setup Procedures

This chapter summarizes the initial setup procedures for the PeopleSoft Batch e*Way.

4.1 Overview

After installing the PeopleSoft Batch e*Way, you must perform an initial setup for it to work with your system. A wide range of setup options allow the e*Way to conform to your system's operational characteristics and your facility's operating procedures.

The topics discussed in this chapter include the following:

Setting Up the e*Way

[Creating the e*Way](#) on page 43

[Modifying e*Way Properties](#) on page 44

[Configuring the e*Way](#) on page 45

[Changing the User Name](#) on page 49

[Setting Startup Options or Schedules](#) on page 49

[Activating or Modifying Logging Options](#) on page 51

[Activating or Modifying Monitoring Thresholds](#) on page 52

Troubleshooting the e*Way

[Configuration Problems](#) on page 53

[System-related Problems](#) on page 54

4.2 Setting Up the e*Way

Note: The e*Gate Enterprise Manager GUI runs only on the Windows operating system.


4.2.1 Creating the e*Way

The first step in implementing an e*Way is to define the e*Way component using the e*Gate Enterprise Manager.

To create an e*Way

- 1 Open the schema in which the e*Way is to operate.
- 2 Select the e*Gate Enterprise Manager Navigator's Components tab.
- 3 Open the host on which you want to create the e*Way.
- 4 Select the Control Broker you want to manage the new e*Way.

Figure 18 e*Gate Enterprise Manager Window (Components View)



- 5 On the Palette, click Create a New e*Way.
- 6 Enter the name of the new e*Way, then click OK.
- 7 All further actions are performed in the e*Gate Enterprise Manager Navigator's Components tab.


4.2.2 Modifying e*Way Properties

To modify any e*Way properties

- 1 Right-click on the desired e*Way and select **Properties** to edit the e*Way's properties. The properties dialog opens to the **General** tab (shown in Figure 19).

Note: The executable and default configuration files used by this e*Way are listed in **Components** on page 14.

Figure 19 e*Way Properties (General Tab)



- 2 Make the desired modifications, then click **OK**.

4.2.3 Configuring the e*Way


The e*Way's default configuration parameters are stored in an ASCII text file with a .def extension. The e*Way Editor provides a simple graphical interface for viewing and changing those parameters to create a working configuration (.cfg) file.

To change e*Way configuration parameters

- 1 In the e*Gate Enterprise Manager's Component editor, select the e*Way you want to configure and display its properties.

Note: The executable and default configuration files used by this e*Way are listed in [Components](#) on page 14.


Figure 20 e*Way Properties - General Tab



- 2 Under Configuration File, click New to create a new file or Find to select an existing configuration file. If you select an existing file, an Edit button appears. Click this button to edit the currently selected file.
- 3 You are now in the e*Way Configuration Editor.

4.2.4 Using the e*Way Editor

Figure 21 The e*Way Configuration Editor







The e*Way Editor controls fall into one of six categories:

- The **Menu bar** allows access to basic operations (e.g., saving the configuration file, viewing a summary of all parameter settings, and launching the Help system)
- The **Section selector** at the top of the Editor window enables you to select the category of the parameters you wish to edit
- **Section controls** enable you to restore the default settings, restore the last saved settings, display tips, or enter comments for the currently selected section
- The **Parameter selector** allows you to jump to a specific parameter within the section, rather than scrolling
- **Parameter controls** enable you to restore the default settings, restore the last saved settings, display tips, or enter comments for the currently selected parameter
- **Parameter configuration controls** enable you to set the e*Way's various operating parameters

Section and Parameter Controls

The section and parameter controls are shown in Table 9 below.

Table 9 Parameter and Section Controls

Button	Name	Function
	Restore Default	Restores default values
	Restore Value	Restores saved values
	Tips	Displays tips
	User Notes	Enters user notes



Note: The section controls affect all parameters in the selected section, whereas the parameter controls affect only the selected parameter.

Parameter Configuration Controls

Parameter configuration controls fall into one of two categories:

- Option buttons
- Selection lists, which have controls as described in Table 10

Table 10 Selection List Controls

Button	Name	Function
	Add to List	Adds the value in the text box to the list of available values.
	Delete Items	Displays a "delete items" dialog box, used to delete items from the list.

Command-line Configuration

In the **Additional Command Line Arguments** box, type any additional command line arguments that the e*Way may require, taking care to insert them *at the end* of the existing command-line string. Be careful not to change any of the default arguments unless you have a specific need to do so.

Getting Help

To launch the e*Way Editor's Help system

From the **Help** menu, select **Help** topics.

To display tips regarding the general operation of the e*Way

From the **File** menu, select **Tips**.

To display tips regarding the selected Configuration Section

In the **Section Control** group, click .

To display tips regarding the selected Configuration Parameter

In the **Parameter Control** group, click .

Note: *“Tips” are displayed and managed separately from the online Help system. You cannot search for Tips within the Help system, or view Help system topics by requesting Tips.*

For detailed descriptions and procedures for using the e*Way Configuration Editor, see the *e*Gate Integrator User's Guide*.

4.2.5 Changing the User Name

Like all e*Gate executable components, e*Ways run under an e*Gate user name. By default, all e*Ways run under the **Administrator** user name. You can change this if your site's security procedures so require.

To change the user name

- 1 Display the e*Way's properties dialog.
- 2 On the **General** tab, use the **Run as user** list to select the e*Gate user under whose name this component is to run.

See the *e*Gate Integrator System Administration and Operations Guide* for more information on the e*Gate security system.


4.2.6 Setting Startup Options or Schedules

SeeBeyond e*Ways can be started or stopped by any of the following methods:

- The Control Broker can start the e*Way automatically whenever the Control Broker starts.
- The Control Broker can start the e*Way automatically whenever it detects that the e*Way terminated execution abnormally.
- The Control Broker can start or stop the e*Way on a schedule that you specify.
- Users can start or stop the e*Way manually using an interactive monitor.

You determine how the Control Broker starts or shuts down an e*Way using options on the e*Way properties **Start Up** tab (see Figure 22). See the *e*Gate Integrator System Administration and Operations Guide* for more information about how interactive monitors can start or shut down components.

Figure 22 e*Way Properties (Start-Up Tab)



To set the e*Way's startup properties

- 1 Display the e*Way's properties dialog.
- 2 Select the Start Up tab.
- 3 To have the e*Way start automatically when the Control Broker starts, select the Start automatically check box.
- 4 To have the e*Way start manually, clear the Start automatically check box.
- 5 To have the e*Way restart automatically after an abnormal termination:
 - A Select Restart after abnormal termination.
 - B Set the desired number of retries and retry interval.
- 6 To prevent the e*Way from restarting automatically after an abnormal termination, clear the Restart after abnormal termination check box.
- 7 Click OK.


4.2.7 Activating or Modifying Logging Options

Logging options enable you to troubleshoot problems with the e*Way and other e*Gate components.

To set the e*Way debug level and flag

- 1 Display the e*Way's Properties dialog.
- 2 Select the **Advanced** tab.
- 3 Click **Log**. The dialog window appears (see Figure 23).

Figure 23 e*Way Properties (Advanced Tab - Log Option)



- 4 Select **DEBUG** for the **Logging level**.
- 5 Select either **e*Way (EWY)** or **e*Way Verbose (EWYV)** for the **Debugging flag**. Note that the latter has a significant negative impact on system performance.
- 6 Click **OK**.

The other options apply to other e*Gate components and are activated in the same manner. See the *e*Gate Integrator Alert and Log File Reference* for additional information concerning log files, logging options, logging levels, and debug flags.

4.2.8 Activating or Modifying Monitoring Thresholds

Monitoring thresholds enable you to monitor the throughput of the e*Way. When the monitoring thresholds are exceeded, the e*Way sends a Monitoring Event to the Control Broker, which is then routed to the e*Gate Monitor and any other configured destinations.

- 1 Display the e*Way's properties dialog.
- 2 Select the **Advanced** tab.
- 3 Click **Thresholds**.
- 4 Select the desired threshold options and click **OK**.

See the *e*Gate Integrator Alert and Log File Reference* for more information concerning threshold monitoring, routing specific notifications to specific recipients, or for general information about e*Gate's monitoring and notification system.

4.3 Troubleshooting the e*Way

In the initial stages of developing your e*Gate Integrator system administration system, most problems with e*Ways can be traced to configuration.

4.3.1 Configuration Problems

In the Enterprise Manager

- Does the e*Way have the correct Collaborations assigned?
- Do those Collaborations use the correct Collaboration Services?
- Is the logic correct within any Collaboration Rule script employed by this e*Way's Collaborations?
- Do those Collaborations subscribe to and publish Events appropriately?
- Are all the components that *feed* this e*Way properly configured, and are they sending the appropriate Events correctly?
- Are all the components that this e*Way *feeds* properly configured, and are they subscribing to the appropriate Events correctly?

In the e*Way Editor

- Check that all configuration options are set appropriately.
- Check that all settings you changed are set correctly.
- Check all required changes to ensure they have not been overlooked.
- Check the defaults to ensure they are acceptable for your installation.

On the e*Way's Participating Host

- Check that the Participating Host is operating properly, and that it has sufficient disk space to hold the IQ data that this e*Way's Collaborations publish.
- Check that the PATH (on Windows) or LD_LIBRARY_PATH (on UNIX) environmental variable includes a path to the PeopleSoft dynamically-loaded libraries.

In the PeopleSoft Application

- Check that the application is configured correctly, is operating properly, and is sending or receiving the correct data appropriately.

4.3.2 System-related Problems

- Check that the connection between the external application and the e*Way is functioning appropriately.
- Once the e*Way is up and running properly, operational problems can be due to:
 - ♦ External influences (network or other connectivity problems).
 - ♦ Problems in the operating environment (low disk space or system errors)
 - ♦ Problems or changes in the data the e*Way is processing.
 - ♦ Corrections required to Collaboration Rule scripts that become evident in the course of normal operations.

One of the most important tools in the troubleshooter's arsenal is the e*Way log file. See the *e*Gate Integrator Alert and Log File Reference Guide* for an extensive explanation of log files, debugging options, and using the e*Gate monitoring system to monitor operations and performance.

Operational Overview

This chapter contains an overview of the operational behavior and basic internal processes of the PeopleSoft Batch e*Way, and covers the following topics:

e*Gate to PeopleSoft on page 55

PeopleSoft to e*Gate on page 58

Batch Operation on page 60

ODBC Operation on page 64

e*Way Architecture on page 67

Basic e*Way Processes on page 69

The information on Batch and ODBC operation is excerpted from the *Batch e*Way Intelligent Adapter User's Guide* and the *e*Way Intelligent Adapter for ODBC User's Guide*, respectively.

5.1 e*Gate to PeopleSoft

An e*Gate-outbound batch-mode interface loads a collection of transactions, usually in the form of a data file, into PeopleSoft. The interface can be triggered by a user or the source application, or by a scheduling mechanism (for example, a nightly synchronization of inventory information with an external system, or a weekly load of timecard information into PeopleSoft Payroll).

A data file from the source application is passed to e*Gate for transformation, and then loaded directly into the PeopleSoft application tables using SQL commands from the ODBC e*Way. The main components of this interface include:


- A source-specific e*Way, to transfer a source data file.
- e*Gate Integrator, to route the data.
- An ODBC e*Way, to transform and load the data into the PeopleSoft system
- An error-file-handling e*Way, to process failed transactions.

5.1.1 Outbound Process Flow

The e*Gate-outbound process is as follows (see Figure 24):

- 1 A trigger Event or schedule in the source application initiates the creation of an interface file.
- 2 When the interface file is complete, the source e*Way sends the entire data file to *Gate.
- 3 For each row of data in the interface file, e*Gate routes the message to the ODBC e*Way.

Figure 24 e*Gate-to-PeopleSoft Batch Process Flow



- 4 Each message is transformed and mapped to the PeopleSoft-inbound message structure. The message structure contains one or more repeating table structures that are required to insert the transaction into the PeopleSoft application tables. For

example, an employee hire from the source system might require multiple row inserts into multiple PeopleSoft tables.

Once the message structure is loaded, the data is inserted into the application tables and a **commit** can be issued. The **commit** is configurable. After the message is processed successfully, the Batch e*Way is ready for the next message.

- 5 If the transformation fails or the data is not inserted, the original, un-transformed message from e*Gate is written to an error file.

Depending on the error handling requirements, when an error is encountered the interface may stop processing, stop processing and rollback all transactions, or bypass the error and continue processing.

- A If **stop on error** processing is desired, the Batch e*Way is suspended so that no more transactions are sent to PeopleSoft. Any unprocessed transactions from the interface file remain in the e*Gate queue.
 - B If **continue on error** processing is desired, the e*Way is not suspended and after the failed message is written to the error file, the remaining messages in the queue continue normal processing. Additional failed transactions are appended to the error file. When all of the transactions in the interface data file have been processed, the user can then correct the failed records for reprocessing.
 - C If **rollback on error** processing is desired, the Batch e*Way is suspended and the messages in the e*Gate queue are purged. Note that for rollback on error processing, only one **commit** is issued after all transactions in the interface file have been processed successfully.
- 6 At this point user intervention is required to edit the error file, using a standard file editor, and correct the offending data.
 - 7 Once the file is corrected, it is moved to the error handling directory where the error handling e*Way loads and reprocesses the messages. The corrected messages are routed to the Batch e*Way for transformation, mapping, and loading.
 - 8 For **stop on error** processing, once the failed message as been reprocessed successfully, the Batch e*Way is re-started to continue processing the remaining transactions in the e*Gate queue.

5.2 PeopleSoft to e*Gate

An e*Gate-inbound batch-mode interface extracts data from the PeopleSoft application tables, processes the data, and sends the results to an interface table or file. The data in the interface table or file is then sent to e*Gate for transformation and routing. Two different methods can be used in this mode:

- ODBC (Direct Load)
- Batch

The main components of this interface include:

- An e*Way (either ODBC or Batch), to retrieve a data table or file.
- e*Gate Integrator, to transform and route the data.
- A target-system-specific e*Way, to load the transformed data into the target system.

The design for outbound batch mode interfaces was created to be as flexible as possible. Most batch interfaces run on a scheduled basis, but the design also allows for an interface to be initiated by a remote function call (RFC) within the interface program. The design can accommodate interface data written to either an interface table or an interface file.

Outbound batch mode interfaces vary widely depending on the source and target applications, and the data to be interfaced. Because of this, the design does not attempt to generalize the extraction of data from PeopleSoft, the processing of that data, or output to a file or table. Instead, the design focuses solely on the process of sending the data from an interface table or file to the Intelligent Queue.

It begins after the interface program has loaded the data to the table or file, and ends once the data is transformed and routed to the Intelligent Queue. The design does not address a significant portion of the interfacing task, including logical units of work and target system error handling and alerting. These issues need to be addressed both as part of the interface program design and the inbound batch interface design for the target system.

5.2.1 Inbound Process Flow


The e*Gate-inbound process is as follows (see Figure 25):

- 1 A process scheduler triggers the interface program to execute and writes data to an interface table or file (see Note 1).
- 2 The Batch e*Way retrieves the interface data.
- 3 The data is received by e*Gate.
- 4 Each row of data is identified, transformed, and routed to the target e*Way.
- 5 The transformed messages are loaded into the target application.

Note: *The interface program is a separate program outside of PeopleSoft that extracts data from the PeopleSoft application tables, manipulates the data, and writes the results to an output. The batch interface programs are usually initiated on the application*

server by a scheduling tool such as the PeopleSoft Process Scheduler, Autosys, or a 'cron job'.

Figure 25 PeopleSoft-to-e*Gate Process Flow



The Batch e*Way can be triggered to fetch data on a scheduled basis or by an external function call within the interface program. The polling schedule is a configurable parameter in the e*Gate workbench. The external function call is a function developed as part of the design that a developer can use within the interface program to send the data to the e*Gate.

5.3 Batch Operation

Note: For more complete information, see the *Batch e*Way Intelligent Adapter User's Guide*.

The PeopleSoft Batch e*Way makes use of the following Batch e*Way behavior models:

Subscriber

In this case, the e*Way polls an external system based on a schedule, and searches for files based on specific criteria. It then retrieves the files that match the criteria, stores them locally, and then reads the records in the files, while simultaneously keeps track of its own progress by maintaining state information in a separate file.

Message-Based

This model requires the use of the parameter, **Enable Message Configuration**. If this parameter is enabled, then the e*Way has a subscription to an ordering transmission that determines its activity. This subscription is to an XML message, with all relevant parameters governing the transfer, including the file to be sent (if it is an outbound transfer). There are two options for the ordering transmission.

- ◆ Receive one time (from one or more sources)
- ◆ Receive multiple times, according to a schedule that remains in effect until a new order arrives

5.3.1 Message-Based Operation

General Information

The *Order* Extensible Markup Language (XML) message has the following basic format:

```

<batch_e*Way_order>
  <command>                (command)  </command>
  <order_record>
    <error_record>
      </error_record>
    </order_record>
  <order_record>
    <error_record>
      </error_record>
    </order_record>
  <payload>                (DATA)   </payload>
</Batch_e*Way_Order>

```

The main record has the following subrecords:

- **Command**, which should be set to **Receive**
- **Order**, which contains the details for retrieving from a single source
- **Error**, which contains error information published by the e*Way after attempting to execute the order. This subrecord is only sent if the **Publish Status Record on Error parameter** is set to **Yes**.
- **Payload**, which is not used in **Receive** mode

The data can be the following forms:

- In the first case, the payload node can contain base64 data, in which case it has a **payload** attribute set to **base64Insitu**
- In the second case, the payload node represents the directory for the payload, in which case it has a **payload** attribute equal to **localDir**

Receiving Data with a *Receive* Order

Receiving from a file is similar to sending, as shown in this example.

```
<batch_e*way_order>
  <command>           receive           </command>
  <external_host_setup>
    <host_type>       Unix               </host_type>
    <user_name>       Alincoln           </user_name>
    <encrypted_password> liasdfLIJB     </encrypted_password>
    <file_transfer_method> ftp         </file_transfer_method>
    <return_tag>      Factor order      </return_tag>
  </external_host_setup>
  <communication_setup>
    <down_timeout>    10                 </down_timeout>
    <up_timeout>      20                 </up_timeout>
    <resend_timeout>  20                 </resend_timeout>
  </communication_setup>
  <subscribe_to_external>
    <remote_directory_name> /usr/home/honest_abe/from
    </remote_directory_name>
    <remote_file_regexp> Y*.dat        </remote_file_regexp>
  </subscribe_to_external>
</batch_e*way_order>
```

In this case, the e*Way retrieves all of the files in the designated directory that match the given regular expression, and stores them in a temporary directory. It then reads the entire contents of each file and sends it to e*Gate as a publication (using the **event-send-to-egate** function). The message sent is similar to the XML message that initiated the transfer, except for two differences:

- There is one return message per *order* in the command, instead of one return per *command*. Thus, if a command is received with orders for three transfers, the e*Way attempts three transfers, and returns the three retrieved files as three *receive* responses.
- It contains a *payload* field that contains the data received. Please refer to the following example:

```

<batch_e*way_order>
  <command>           receive           </command>
  <external_host_setup>
    <host_type>       Unix               </host_type>
    <user_name>       Alincoln           </user_name>
    <encrypted_password> liasdfLIJB     </encrypted_password>
    <file_transfer_method> ftp         </file_transfer_method>
    <return_tag>      Factor order      </return_tag>
  </external_host_setup>
  <communication_setup>
    <down_timeout>    10                 </down_timeout>
    <up_timeout>      20                 </up_timeout>
    <resend_timeout>  20                 </resend_timeout>
  </communication_setup>
  <subscribe_to_external>
    <remote_directory_name> /usr/home/honest_abe/from
    </remote_directory_name>
    <remote_file_regexp> Y*.dat         </remote_file_regexp>
  </subscribe_to_external>
  <payload>           (DATA)            </payload>
</batch_e*way_order>

```

Only when it has sent all records does the e*Way acknowledge (ACK) the *order* command message. The **<return_tag>** field of the XML message is used to store a unique tag generated by the originator of the command. This tag helps the e*Gate system administrator to determine, as each response comes back, which system gave that response.

As a final example of the receive command, consider this example of a command to go to three different systems for three different kinds of data, Factory Orders, Builds of Materials, and Engineering Updates. First, note the command record (transfer details omitted for brevity):

```

<batch_e*way_order>
  <command>           receive           </command>
  <return_tag>       Factor order      </return_tag>
  <return_tag>       Build of Materials </return_tag>
  <return_tag>       Engineering Updates </return_tag>
</batch_e*way_order>

```

The Batch e*Way attempts each *receive* transfer, and follows its normal procedures for retrying and raising exceptions if problems occur. As each transfer succeeds, it returns an XML message with the *payload* and the corresponding return tag. If it fails, it returns an XML message with the error record.

```

<batch_e*way_order>
  <command>           receive           </command>
  <return_tag>       Factor order      </return_tag>
  <payload>          (DATA)            </payload>
</batch_e*way_order>

```

And then each of the other two, (Build of Materials, and Engineering Updates).

```

<batch_e*way_order>
  <command>           receive           </command>
  <return_tag>       Build of Materials </return_tag>
  <payload>          (DATA)            </payload>
</batch_e*way_order>

```

```

<batch_e*way_order>
  <command>          receive          </command>
    <return_tag>    Engineering Updates </return_tag>
    <payload>       (DATA)           </payload>
</batch_e*way_order>

```

Please see [Receive XML Messages](#) on page 124 for the corresponding Document Type Definition (DTD) file.

Error Reporting

If the parameter **Publish Status Record on Error** is set to **Yes**, and the e*Way encounters problems with one order, it publishes the command message containing only the orders that failed, along with the corresponding error records. This is illustrated in the following template:

```

<batch_e*way_order>
  <command>          (command)        </command>
  <order_record>
  <error_record>
    <error_code>          </error_code>
    <error_text>         </error_text>
    <last_action>        </last_action>
  </error_record>
  </order_record>
  <payload>          (DATA)          </payload>
</batch_e*way_order>

```

The *last action* record contains whatever command the e*Way can indicate. Thus, if a failure occurs on renaming a file after the transfer, then the e*Way populates this field with the *rename* command it is attempting to perform.

Please see [Error Messages](#) on page 125, for the corresponding Document Type Definition (DTD) file.

5.4 ODBC Operation

Note: For more complete information, see the *e*Way Intelligent Adapter for ODBC User's Guide*.

5.4.1 Using SQL Functions

Static vs. Dynamic SQL Functions

Dynamic SQL statements are built and executed at run time versus Static SQL statements that are embedded within the program source code. Dynamic statements do not require knowledge of the complete structure on an SQL statement before building the application. This allows for run time input to provide information about the database objects to query.

The application can be written so that it prompts the user or scans a file for information that is not available at compilation time.

In Dynamic statements the four steps of processing an SQL statement take place at run time, but they are performed only once. Execution of the plan takes place only when EXECUTE is called. [Figure 26 on page 65](#) shows the difference between Dynamic SQL with immediate execution and Dynamic SQL with prepared execution. See Static SQL Functions and Dynamic SQL Functions in the *e*Way Intelligent Adapter for ODBC User's Guide*.

Benefits of Dynamic SQL

Using dynamic SQL commands, an application can prepare a *generic* SQL statement once and execute it multiple times. Statements can also contain markers for parameter values to be supplied at execution time, so that the statement can be executed with varying inputs.


Limitations of Dynamic SQL

The use of dynamic SQL commands has some significant limitations. A dynamic SQL implementation of an application generally performs worse than an implementation where permanent stored procedures are created and the client program invokes them with RPC (remote procedure call) commands.

Benefits of Stored Procedures

When a stored procedure is created for an application, SQL statement compilation and optimization are performed once when the procedure is created. With a dynamic SQL application, compilation and optimization are performed every time the client program runs. A dynamic SQL implementation also incurs database space overhead because each instance of the client program must create separate compiled versions of the application's prepared statements. When you design an application to use stored procedures and RPC commands, all instances of the client program can share the same stored procedure. See Stored Procedure Functions in the *e*Way Intelligent Adapter for ODBC User's Guide*.

Figure 26 Example of Dynamic SQL processing



ODBC SQL Type Support

The following table shows the supported SQL data types and the corresponding native data type for the database.

Table 11 ODBC SQL Type Support

SQL Type Name	SQL Datatype	Oracle Datatype
SQL_BIT	BIT	N/A
SQL_BINARY	BINARY (n)	N/A
SQL_VARBINARY	VARBINARY (n)	RAW (n)
SQL_CHAR	CHAR (n)	CHAR (n)
SQL_VARCHAR	VARCHAR (n)	VARCHAR2 (n)
SQL_DECIMAL	DECIMAL (p, s)	NUMBER (p, s)
SQL_NUMERIC	NUMERIC (p, s)	N/A
SQL_TINYINT	TINYINT	+
SQL_BIGINT	BIGINT	+
SQL_SMALLINT	SMALLINT	+
SQL_INTEGER	INTEGER	+
SQL_REAL	REAL	*
SQL_FLOAT	FLOAT(p)	FLOAT(b)
SQL_DOUBLE	DOUBLE PRECISION	FLOAT
SQL_DATE	DATE	N/A
SQL_TIME	TIME	N/A
SQL_TIMESTAMP	TIMESTAMP	DATE
SQL_LONGVARCHAR	LONG VARCHAR	LONG
SQL_LONGVARBINARY	LONG VARBINARY	LONG RAW

*Oracle float (p) specifies a floating point number with precision range from 1 to 126.

+Oracle uses number (p) to define data types that span TINYINT, BIGINT, SMALLINT, and INTEGER. Oracle **int** type is internally mapped to NUMBER (38) which is returned as SQL_DECIMAL.


Note: All variable precision data types require precision values.

SQL_DECIMAL and SQL_NUMERIC data types require specification of scale which indicates the number of digits to the right of the decimal point.

5.5 e*Way Architecture

Conceptually, an e*Way can be viewed as a multi-layered structure, consisting of one or more layers (see Figure 27). Each layer contains Monk scripts and/or functions, and makes use of lower-level Monk functions residing in the layer beneath. You, as user, primarily use the highest-level functions, which reside in the upper layer(s).

Figure 27 Typical e*Way Architecture




The upper layers of the e*Way use Monk functions to perform Business Process modeling and ETD mapping, package data as e*Gate *Events*, send those Events to Collaborations, and manage interaction with the external system. These layers are built upon an e*Way Kernel layer that manages the basic operations of the e*Way, data processing, and communication with other e*Gate components.

The communication layers of the e*Way are single-threaded. Functions run serially, and only one function can be executed at a time. Processing layers are multi-threaded, with one executable thread for each Collaboration. Each thread maintains its own Monk environment; therefore, information such as variables, functions, path information, and so on cannot be shared between threads.

5.6 Event Type Definitions and Collaborations

Collaborations execute the business logic that enable the e*Way to do its intended work. In turn, each Collaboration executes a Collaboration Rule, containing the actual instructions to execute the business logic. Each Collaboration that publishes its processed Events internally (within e*Gate Integrator) requires one or more IQs to receive the Events, as shown in Figure 28. Any Collaboration that publishes its processed Events only to an external system does *not* require *any* IQs.

Figure 28 Collaborations and IQs



Configuration options that control the Monk environment and define the Monk functions used to perform various e*Way operations are discussed in [Chapter 6](#). You can create and modify these functions using the SeeBeyond Collaboration Rules Editor or a text editor (such as *Microsoft Word* or *Notepad*, or UNIX *vi*). The available set of e*Way API functions is described in [Chapter 7](#). Generally, e*Way Kernel Monk functions should be called directly only when there is a specific need not addressed by higher-level Monk functions, and should be used only by experienced developers.


For more information on defining Collaborations, defining IQs, assigning Collaborations to e*Ways, or configuring Collaborations to publish Events, see the *e*Gate Integrator User's Guide*.

5.7 Basic e*Way Processes

Note: This section describes the basic operation of a typical e*Way based on the Generic e*Way Kernel. Not all functionality described in this section is used routinely by this e*Way.

The most basic processes carried out by an e*Way are listed in Figure 29. In e*Ways based on the Generic Monk e*Way Kernel (using `stcewgenericmonk.exe`), these processes are controlled by the listed Monk functions. Configuration of these functions is described in the referenced sections of this User's Guide.

Figure 29 Basic e*Way Processes




A series of diagrams on the next several pages illustrate the interaction and operation of these functions during the specified processes. Configuring the parameters associated with these functions is covered in [Chapter 6](#), while the functions themselves are described in [Chapter 7](#).

Initialization Process

Figure 30 illustrates the e*Way's initialization process, using the **Monk Environment Initialization File** and **Startup Function**.


Figure 30 Initialization Process



Connect to External Process

Figure 31 illustrates how the e*Way connects to the external system, using the **External Connection Establishment Function** and **External Connection Verification Function**.

Figure 31 Connection Process



Note: The e*Way selects the connection function based on an internal **up/down** flag rather than a poll to the external system. See **Figure 33 on page 73** and **Figure 32 on page 72** for examples of how different functions use this flag.

User functions can manually set this flag using Monk functions. See **send-external-up** on page 121 and **send-external-down** on page 121 for more information.

Data Exchange Process


Event-driven

Figure 32 illustrates how the e*Way's event-driven data exchange process works, using the **Process Outgoing Message Function**.

The e*Way periodically checks the *Failed Message* counter against the value specified by the **Max Failed Messages** parameter. When the *Failed Message* counter exceeds the specified maximum value, the e*Way logs an error and shuts down.

After the function exits, the e*Way waits for the next outgoing Event.


Figure 32 Event-Driven Data Exchange Process



Schedule-driven

Figure 33 illustrates how the e*Way's schedule-driven data exchange process works for incoming data, using the **Exchange Data with External Function, Positive Acknowledgment Function**, and **Negative Acknowledgment Function**.

Figure 33 Schedule-Driven Data Exchange Process



Start can occur in any of the following ways:

- *Start Data Exchange* time occurs
- Periodically during data-exchange schedule (after *Start Data Exchange* time, but before *Stop Data Exchange* time), as set by **Exchange Data Interval**
- The **start-schedule** Monk function is called


*Send Events to e*Gate* can be implemented using any of the following Monk functions:

- **event-send-to-egate**
- **event-send-to-egate-ignore-shutdown**
- **event-send-to-egate-no-commit**

The last of these is used when confirmation of correct transmission is required from the external system. In this case, the e*Way sends information back to the external system after receiving data. Depending upon whether the acknowledgment is positive or negative, you subsequently use one of the following functions to complete the process (see Figure 34):

- **event-commit-to-egate**
- **event-rollback-to-egate**

Figure 34 Send Event to e*Gate with Confirmation




After the function exits, the e*Way waits for the next *Start* time or command.

Disconnect from External Process

Figure 35 illustrates how the e*Way disconnects from the external system, using the **External Connection Shutdown Function**.


Figure 35 Disconnect Process



Shutdown Process

Figure 36 illustrates how the e*Way shuts itself down, using the **Shutdown Command Notification Function**.

Figure 36 Shutdown Process



Configuration Parameters

This chapter describes the configuration parameters for the e*Way Intelligent Adapter for PeopleSoft Batch.

6.1 Overview

The e*Way's configuration parameters are set using the e*Way Editor; see [Configuring the e*Way](#) on page 45 for procedural information. The default configurations are provided in `batch.def` and `dart.def`.

The following configuration sections are included in this User's Guide, since they are an integral part of the operational description. For all other configuration information, please refer to the *Batch e*Way Intelligent Adapter User's Guide* or the *e*Way Intelligent Adapter for ODBC User's Guide*, as applicable.

- [General Settings](#) on page 77
- [Communication Setup](#) on page 79
- [Monk Configuration](#) on page 83
- [Dynamic Configuration](#) on page 92

6.2 General Settings

The General Settings control basic operational parameters.

Journal File Name

Description

Specifies the name of the journal file.

Required Values

A valid filename, optionally including an absolute path (for example, c:\temp\filename.txt). If an absolute path is not specified, the file is stored in the e*Gate SystemData directory. See the *e*Gate Integrator System Administration and Operations Guide* for more information about file locations.

Additional Information

An Event is Journalled for the following conditions:

- When the number of resends is exceeded (see **Max Resends Per Message** below)
 - When its receipt is due to an external error, but **Forward External Errors** is set to No
-

Max Resends Per Message

Description

Specifies the number of times the e*Way attempts to resend a message (Event) to the external system after receiving an error. When this maximum is reached, the e*Way waits for the number of seconds specified by the **Resend Timeout** parameter, and then rolls back the Event to its publishing IQ.

Required Values

An integer from 1 through 1,024. The default is 5.

Max Failed Messages

Description

Specifies the maximum number of failed messages (Events) that the e*Way allows. When the specified number of failed messages is reached, the e*Way shuts down and exits.

Required Values

An integer from 1 through 1,024. The default is 3.

Forward External Errors

Description

Selects whether error messages that begin with the string “DATAERR” that are received from the external system are queued to the e*Way’s configured queue. See [Exchange Data with External Function](#) on page 86 for more information.

Required Values

Yes or No. The default value, No, specifies that error messages are not to be forwarded. See [Data Exchange Process](#) on page 72 for more information about how the e*Way uses this function.

6.3 Communication Setup

The Communication Setup parameters control the schedule by which the e*Way obtains data from the external system.

***Note:** The schedule you set using the e*Way's properties in the e*Gate Enterprise Manager controls when the e*Way executable runs. The schedule that you set within the parameters discussed in this section (using the e*Way Editor) determines when data is exchanged. Be sure you set the "exchange data" schedule to fall within the "run the executable" schedule.*

Exchange Data Interval

Description

Specifies the number of seconds the e*Way waits between calls to the [Exchange Data with External Function](#) during scheduled data exchanges.

Required Values

An integer from 0 through 86,400. The default is 120.

Additional Information

- If [Zero Wait Between Successful Exchanges](#) is set to Yes and the [Exchange Data with External Function](#) returns data, the setting of this parameter is ignored and the e*Way invokes the [Exchange Data with External Function](#) immediately
- If it is desired to invoke the [Exchange Data with External Function](#) again as soon as possible when data is **not** queued to e*Gate via the return mechanism, the e*Way Kernel Monk function [insert-exchange-data-event](#) can be called directly (prior to leaving the exchange function) to accomplish this
- If this parameter is set to zero, no exchange data schedule is set and the [Exchange Data with External Function](#) is never called

See also

[Start Exchange Data Schedule](#) on page 80

[Stop Exchange Data Schedule](#) on page 81

Zero Wait Between Successful Exchanges

Description

Selects whether to initiate data exchange after the [Exchange Data Interval](#) or immediately after a successful previous exchange.

Required Values

Yes or No. The default is No.

Additional Information

- If this parameter is set to **Yes**, and the previous exchange function returned data, the e*Way invokes the **Exchange Data with External Function** immediately
- If it is desired to invoke the **Exchange Data with External Function** again as soon as possible when data is **not** queued to e*Gate via the return mechanism, the e*Way Kernel Monk function **insert-exchange-data-event** can be called directly (prior to leaving the exchange function) to accomplish this
- If this parameter is set to **No**, the e*Way always waits the number of seconds specified by **Exchange Data Interval** between invocations of the **Exchange Data with External Function**

Start Exchange Data Schedule

Description

Establishes the schedule to invoke the e*Way's **Exchange Data with External Function**.

Required Values

One of the following:

- One or more specific dates/times
- A single repeating, regular, interval (such as weekly, daily, or every *n* seconds)

Other Requirements

If you set a schedule using this parameter, you must also define *all* of the following parameters. If you do not, the e*Way terminates execution when the schedule attempts to start.

- **Exchange Data with External Function**
- **Positive Acknowledgment Function**
- **Negative Acknowledgment Function**

Additional Information

When the schedule starts, the e*Way determines whether or not:

- it is waiting to send an ACK or NAK to the external system (using the **Positive Acknowledgment Function** or **Negative Acknowledgment Function**)
- the connection to the external system is active

If *no* ACK/NAK is pending and the connection *is* active, the e*Way immediately executes the **Exchange Data with External Function**. Thereafter, the **Exchange Data with External Function** is called according to the **Exchange Data Interval** parameter until the **Stop Exchange Data Schedule** time is reached.

Stop Exchange Data Schedule

Description

Establishes the schedule to stop data exchange.

Required Values

One of the following:

- One or more specific dates/times
- A single repeating, regular, interval (such as weekly, daily, or every *n* seconds)

Down Timeout

Description

Specifies the number of seconds for the e*Way to wait between calls to the **External Connection Establishment Function**.

Required Values

An integer from 1 through 86,400. The default is 15.

Up Timeout

Description

Specifies the number of seconds for the e*Way to wait between calls to the **External Connection Verification Function** to verify that the connection is still up.

Required Values

An integer from 1 through 86,400. The default is 15.

Resend Timeout

Description

Specifies the number of seconds the e*Way waits between attempts to resend a message (Event) to the external system, after receiving an error message from the external system.

Required Values

An integer from 1 through 86,400. The default is 15.

Exchange-if-in-window-on-startup

Description

If this Batch e*Way parameter is set to **Yes** and e*Way starts within an *exchange data* window (see [Exchange Data Interval](#)), the e*Way will invoke the [Exchange Data with External Function](#) parameter immediately.

Required Values

Yes or No. The default is No.

6.4 Monk Configuration

The parameters in this section help you set up the information required by the e*Way to utilize Monk for communication with the external system.

Specifying Function or File Names

Parameters that require the name of a Monk function accept either a function name (implied by the absence of a period <.>) or the name of a file (optionally including path information) containing a Monk function. If a file name is specified, the function invoked is given by the base name of the file (for example, for a file named **my-startup.monk**, the e*Way would attempt to execute the function **my-startup**). If path information is specified, that path is appended to the **Load Path**.

If you specify a file name, be sure that the file has one of the following extensions:

- .monk
- .tsc
- .dsc

Specifying Multiple Directories

To specify multiple directories, manually enter the directory names rather than selecting them with the **File Selection** button. Directory names must be separated with semicolons, and you can mix absolute paths with relative e*Gate paths. For example:

```
monk_scripts\my_dir;c:\my_directory
```

The internal e*Way function that loads this path information is called only once, when the e*Way first starts up.

Load Path

The Monk *load path* is the path Monk uses to locate files and data (set internally within Monk). The default load paths are determined by the **SharedExe** and **SystemData** settings in the **.egate.store** file. See the *e*Gate Integrator System Administration and Operations Guide* for more information about this file.

Additional Path

Description

Specifies a path to be appended to the **Load Path**. A directory specified here is searched *after* searching the default load path.

Required Values

A pathname, or a series of paths separated by semicolons.

Note: *For direct-load or direct-extract operation, this parameter is optional and may be left blank; for batch-mode operation, this parameter is not used.*

Additional information

The internal e*Way function that loads this path information is called only once, when the e*Way first starts up.

Auxiliary Library Directories

Description

Specifies a path to auxiliary library directories. Any .monk files found within those directories are loaded automatically into the e*Way's Monk environment.

Required Values

A pathname, or a series of paths separated by semicolons.

- For ODBC (direct-load/direct-extract) operation, the default value is `monk_library/dart`.
- For batch-mode operation, the default value is `monk_library/batch`.

Note: This parameter is optional and may be left blank.

Monk Environment Initialization File

Description

Specifies a file that contains environment initialization functions, which is loaded after the [Auxiliary Library Directories](#) are loaded.

Required Values

A filename within the [Load Path](#), or filename plus path information (relative or absolute). If path information is specified, that path is appended to the load path.

- For ODBC (direct-load/direct-extract) operation, the default value is `db-stdver-init`.
- For batch-mode operation, the default value is `batch-init`.

Note: This parameter is optional and may be left blank.

Returns

The string "FAILURE" indicates that the function failed, and the e*Way exits; any other string, including a *null string*, indicates success.

Additional information

- Use this feature to initialize the e*Way's Monk environment (for example, to define Monk variables that are used by the e*Way's function scripts); it is good practice to initialize any global Monk variables that may be used by any other Monk Extension scripts
- The internal function that loads this file is called once when the e*Way first starts up

- The e*Way loads this file and try to invoke a function of the same base name as the file name

Startup Function

Description

Specifies a Monk function that the e*Way loads and invokes upon startup or whenever the e*Way's configuration is reloaded. It is called after the e*Way loads the specified **Monk Environment Initialization File** and any files within the specified **Auxiliary Library Directories**. This function accepts no input, and must return a string.

This function should be used to initialize the external system before data exchange starts.

Required Values

The name of a Monk function or the name of a file containing a Monk function.

- For ODBC (direct-load/direct-extract) operation, the default value is **db-stdver-startup**.
- For batch-mode operation, the default value is **batch-startup**.

Note: This parameter is optional and may be left blank.

Returns

The string "FAILURE" indicates that the function failed, and the e*Way exits; any other string (including a *null string*) indicates success.

Process Outgoing Message Function

Description

Specifies the Monk function responsible for sending outgoing messages (Events) from the e*Way to the external system. This function is event-driven, rather than schedule-driven). The function requires a non-null string as input (i.e., the outgoing Event to be sent), and must return a string.

Required Values

The name of a Monk function or the name of a file containing a Monk function.

- For ODBC (direct-load/direct-extract) operation, the default value is **db-stdver-proc-outgoing**.
- For batch-mode operation, the default value is **batch-proc-out**.

Note: This parameter is **required**, and must **not** be left blank.

Returns

- A *null string* ("") indicates that the Event was published successfully to the external system

- A string beginning with **RESEND** indicates that the Event should be resent
- A string beginning with **CONNERR** indicates that there is a problem with the connection to the external system, and causes a rollback of the Event
- A string beginning with **DATAERR** indicates that there is a problem with the message (Event) data itself, and causes a rollback of the Event
- A string beginning with **SHUTDOWN** indicates that the e*Way must exit immediately
- If any string other than one of the preceding is returned, the e*Way creates an entry in the log file indicating that an attempt has been made to access an unsupported function

Additional Information

- The e*Way invokes this function when one of its Collaborations publishes an Event to an *external* destination (as specified within the e*Gate Enterprise Manager).
- Once this function has been called with a *non-null string*, the e*Way does not process another Event until the current Event has been completely processed.

Note: *If you wish to use **event-send-to-egate** to enqueue failed Events in a separate IQ, the e*Way must have an inbound Collaboration (with appropriate IQs) configured to process those Events.*

Exchange Data with External Function

Description

Specifies a Monk function that initiates the transmission of data from the external system to the e*Gate system and forwards that data as an inbound Event to one or more e*Gate Collaborations. This function is invoked automatically by the **Start Exchange Data Schedule** or manually by the **start-schedule** Monk function, and is responsible for either sending data to or receiving data from the external system. If this function returns data, it is queued to e*Gate in an inbound Collaboration. The e*Way must have at least one Collaboration configured suitably to process the inbound Event, as well as any required IQs.

Required Values

The name of a Monk function or the name of a file containing a Monk function.

- For ODBC (direct-load/direct-extract) operation, the default value is **db-stdver-data-exchg**.
- For batch-mode operation, the default value is **batch-exchange-data**.

Note: *This parameter is **conditional** and must be supplied only if the **Exchange Data Interval** is set to a non-zero value.*

Returns

- A *null string* ("") indicates that the data exchange was completed successfully, but with no resultant data sent back to the e*Gate system

- A string beginning with **CONNERR** indicates that there is a problem with the connection to the external system
- A string beginning with **DATAERR** indicates that there is a problem with the message (Event) data itself. If the error string contains data beyond the keyword, the entire string is queued to e*Gate if an inbound Collaboration is so configured and **Forward External Errors** is set to **Yes**. Queuing, however, is performed without the subsequent sending of a **ACK** or **NAK** to the external system.
- Any other string indicates that the contents of the string are packaged as an inbound Event

Additional Information

- Data can be queued directly to e*Gate by using the **event-send-to-egate** Monk function or, if a two-phase approach is required, by using **event-send-to-egate-no-commit** and then **event-commit-to-egate** or **event-rollback-to-egate** to commit or rollback the enqueued events, as appropriate

Note: *Until an Event is committed, it is not revealed to subscribers of that Event.*

External Connection Establishment Function

Description

Specifies a Monk function that the e*Way calls (repeatedly) when it has determined that the connection to the external system is down. The function accepts no input and must return a string.

This function is executed according to the interval specified within the **Down Timeout** parameter, and is called *only* according to this schedule. Once the e*Way has determined that its connection to the external system is up, it calls the **External Connection Verification Function** (see next).

Required Values

The name of a Monk function or the name of a file containing a Monk function.

- For ODBC (direct-load/direct-extract) operation, the default value is **db-stdver-conn-estab**.
- For batch-mode operation, the default value is **batch-ext-connect**.

Note: *This parameter is **required**, and must **not** be left blank.*

Returns

- A string beginning with **SUCCESS** or **UP** indicates that the connection was established successfully
- A string beginning with **DOWN** indicates that the connection was not established successfully
- Any other string, including a *null string*, indicates that the attempt to establish the connection failed and the external state is unknown

External Connection Verification Function

Description

Specifies a Monk function that the e*Way calls when its internal variables show that the connection to the external system is up. It is executed according to the interval specified within the **Up Timeout** parameter, and is called *only* according to this schedule. The function accepts no input and must return a string.

Required Values

The name of a Monk function or the name of a file containing a Monk function.

Note: This parameter is optional and may be left blank.

- For ODBC (direct-load/direct-extract) operation, the default value is **db-stdver-conn-ver**.
- For batch-mode operation, the default value is **batch-ext-verify**.

Returns

- "SUCCESS" or "UP" indicates that the connection was established successfully
- Any other string (including the null string) indicates that the attempt to establish the connection failed

Additional Information

If this function is not specified, the e*Way executes the **External Connection Establishment Function** in its place. This latter function also is called when the e*Way has determined that its connection to the external system is down.

External Connection Shutdown Function

Description

Specifies a Monk function that the e*Way calls to shut down the connection to the external system. This function is invoked only when the e*Way receives a *suspend* command from a Control Broker.

Required Values

The name of a Monk function or the name of a file containing a Monk function.

- For ODBC (direct-load/direct-extract) operation, the default value is **db-stdver-shutdown**.
- For batch-mode operation, the default value is **db-stdver-conn-shutdown**.

Note: This parameter is **required**, and must **not** be left blank.

Input

A string indicating the purpose for shutting down the connection.

- "SUSPEND_NOTIFICATION" - the e*Way is being suspended or shut down

- “RELOAD_NOTIFICATION” - the e*Way is being reconfigured

Returns

A string, the value of which is ignored. Any return value indicates that the *suspend* command can proceed and that the connection to the external system can be broken immediately.

Note: Include in this function any required “clean up” operations that must be performed as part of the shutdown procedure, but before the e*Way exits.

Positive Acknowledgment Function

Description

This function is loaded during the initialization process and is called when all data received from the external system has been processed and enqueued successfully. The function requires a non-null string as input (the Event to be sent to e*Gate) and must return a string.

Required Values

The name of a Monk function or the name of a file containing a Monk function.

- For ODBC (direct-load/direct-extract) operation, the default value is **db-stdver-pos-ack**.
- For batch-mode operation, the default value is **batch-ack**.

Note: This parameter is *conditional* and must be supplied only if the **Exchange Data with External Function** is set to a non-zero value.

Input

A string, the inbound Event to e*Gate.

Returns

- The string beginning with CONNERR indicates a problem with the connection to the external system; when the connection is re-established, the function is called again, with the same input data
- Any other string, including a *null string*, indicates that the acknowledgement has been sent to the external system successfully

Additional Information

- After the **Exchange Data with External Function** returns a string that is transformed into an inbound Event, the Event is handed off to one or more Collaborations for further processing. The e*Way executes this function only if the Event’s processing is completed successfully by *all* the Collaborations to which it was sent; otherwise, the e*Way executes the **Negative Acknowledgment Function**.
- This function can return data to be queued, but the e*Way will *not* acknowledge the data with an ACK or NAK.

Note: *If you configure the acknowledgment function to return a non-null string, you must configure a Collaboration (with appropriate IQs) to process the returned Event.*

Negative Acknowledgment Function

Description

This function is loaded during the initialization process and is called when the e*Way fails to process or enqueue data received from the external system successfully. The function requires a non-null string as input (the Event to be sent to e*Gate) and must return a string.

Required Values

The name of a Monk function or the name of a file containing a Monk function.

- For ODBC (direct-load/direct-extract) operation, the default value is **db-stdver-neg-ack**.
- For batch-mode operation, the default value is **batch-nak**.

Note: *This parameter is **conditional** and must be supplied only if the **Exchange Data with External Function** is set to a non-zero value.*

Input

A string, the inbound Event to e*Gate.

Returns

- The string beginning with CONNERR indicates a problem with the connection to the external system; when the connection is re-established, the function is called again, using the same input data
- Any other string, including a *null string*, indicates that the acknowledgement has been sent to the external system successfully

Additional Information

- This function is called only during the processing of inbound Events. After the **Exchange Data with External Function** returns a string that is transformed into an inbound Event, the Event is handed off to one or more Collaborations for further processing. The e*Way executes this function if the Event's processing is not completed successfully by *all* the Collaborations to which it was sent; otherwise, the e*Way executes the **Positive Acknowledgment Function**.
- This function can return data to be queued, but the e*Way will *not* acknowledge the data with an ACK or NAK.

Note: *If you configure the acknowledgment function to return a non-null string, you must configure a Collaboration (with appropriate IQs) to process the returned Event.*

Shutdown Command Notification Function

Description

The e*Way calls this Monk function automatically to notify the external system that it is about to shut down. This function also can be used to shut down the connection with the external. The function accepts a string as input and must return a string.

Required Values

The name of a Monk function or the name of a file containing a Monk function.

- For ODBC (direct-load/direct-extract) operation, the default value is **db-stdver-shutdown**.
- For batch-mode operation, the default value is **batch-shutdown-notify**.

Note: This parameter is **required**, and must **not** be left blank.

Input

When the Control Broker issues a shutdown command to the e*Way, the e*Way calls this function with the string "SHUTDOWN_NOTIFICATION" passed as a parameter.

Returns

- A *null string* or "SUCCESS" indicates that the shutdown can occur immediately
- Any other string indicates that shutdown must be postponed; once postponed, shutdown does not proceed until the Monk function **shutdown-request** is executed

Additional Information

If you postpone a shutdown using this function, be sure to use the **shutdown-request** function to complete the process in a timely manner.

6.5 Dynamic Configuration

This section describes parameters used to configure a dynamic Batch e*Way:

Note: Use the following XML Document Type Definition (DTD) and e*Gate Event Type Definition (ETD) files when using dynamic configuration:

Table 12 Dynamic Configuration Files

DTD File	Corresponding ETD File
batch_eway_data.dtd	batch_eway_data.xsc
batch_eway_error.dtd	batch_eway_error.xsc
batch_eway_order.dtd	batch_eway_order.xsc

Enable Message Configuration

Description

Use this parameter to indicate that the e*Way contains an XML message which determines its activities. The XML message should contain all relevant parameters that govern the transfer. See [Appendix A](#) for details about the DTD.

Note: When the XML message sets the e*Way to receive, Batch retrieves the external file and wraps it into the XML payload (see [Data Message](#) on page 126), and transforms the data into Base64 format. To send the data back in its original format, use the **Base64-to-Raw** Monk function. Details on how to use this function are explained in the *Monk Developer's Reference*.

Required Values

Yes or No. (No is the default).

When this parameter is set to **Yes**, the Batch e*Way becomes Event-driven, so it does *not* exchange data based on scheduling, and the record type is always a single record. Additionally, certain other configuration parameters are affected, as shown in Table 13.

Note: If the fields marked as **Overridden by message** are set by the XML message, then the table below holds true. However, if the fields are *not* set by the XML message, then those fields marked as **Overridden by message** *must* be specified in the .cfg file. Only **subscriptions** fields must be set.

Table 13 Effect of Enabling Message Configuration

Section	Parameter	Effect
Communication Setup	Start Exchange Data Schedule	Ignored.
	Stop Exchange Data Schedule	Ignored.
	Exchange Data Interval	Ignored.
	Zero Wait Between Successful Exchanges	Ignored.
	Down Timeout	Ignored.
	Up Timeout	Ignored.
External Host Setup	External Host Name	Overridden by message.
	Host Type	Overridden by message.
	User Name	Overridden by message.
	Encrypted Password	Overridden by message.
	File Transfer Method	Overridden by message.
Monk Configuration	Process Outgoing Message Function	The XML event is parsed and processed.
	Exchange Data With External Function	Ignored.
	Positive Acknowledgment Function	Ignored.
	Negative Acknowledgment Function	Ignored.
	Startup Function	Normal behavior, but the value assigned to transfer method is ignored.
Publish To External	Remote Directory Name	Overridden by message.
Publish To External	Remote File Name	Overridden by message.
	Append or Overwrite when Transferring Files	Overridden by message.
	Record Type	Automatically set to Single Record . Any other value is ignored.
	Record Delimiter	Ignored.
	Delimiter on Last Record	Ignored.
	Record Size	Ignored.
	Remote Command After Transfer	Overridden by message.
	Remote Rename or Archive Name	Overridden by message.
	Local Command After Transfer	Overridden by message.
Local Archive Directory	Overridden by message.	

Table 13 Effect of Enabling Message Configuration (Continued)

Section	Parameter	Effect
Recourse Action	Action on Fetch Failure	Normal behavior, but an additional option is needed to publish the Event that contains the configuration message.
	Action on Send Failure	Normal behavior, but an additional option is needed to publish the Event that contains the configuration message.
Sequence Numbering	Starting Sequence Number	Ignored.
	Max Sequence Number	Ignored.
SOCKS	Server Host Name	Overridden by message.
	Server Port	Overridden by message.
Subscribe To External	Remote Directory Name	Overridden by message.
	Remote File Regexp	Overridden by message.
	Record Type	Ignored.
	Record Delimiter	Ignored.
	Delimiter on Last Record	Ignored.
	Record Size	Ignored.
	Remote Command After Transfer	Overridden by message.
	Remote Rename or Archive Name	Overridden by message.
	Local Command After Transfer	Overridden by message.
Local Archive Directory	Overridden by message.	
FTP	server_port	Overridden by message.
	mode	Overridden by message.
	Pretransfer_Commands	Overridden by message.
	Posttransfer_Commands	Overridden by message.

Publish Status Record on Success

Description

When this parameter is set to **Yes**, the Batch e*Way will publish a *good error* record to e*Gate, with the same format that is specified in `batch_eway_error.dtd`. (See [Error Messages](#) on page 125.) The *good error* record is published only when the payload has been successfully sent to the remote host.

Note: *This parameter is not used by the PeopleSoft Batch e*Way.*

Required Values

Yes or No. (No is the default).

Publish Status Record on Error

Description

This parameter determines whether or not the Batch e*Way publishes an error record to e*Gate. The error record is in the format of `batch_eway_error.dtd` (See [Error Messages](#) on page 125). You are required, however, to configure an inbound topic to process this Event.

Required Values

Yes or No. (No is the default).

Include Order Record in Error Record

Description

If this parameter is set to **Yes**, the Batch e*Way includes an Order Record as part of an error record when [Publish Status Record on Error](#) is enabled.

Required Values

Yes or No. (No is the default).

Include Payload in Error Record

Description

If this parameter is set to **Yes**, the Batch e*Way includes the Payload as part of an Error Record when the **Order Record Command** is **Send**.

Note: This parameter is not used by the PeopleSoft Batch e*Way.

Required Values

Yes or No. (No is the default).

Action on Malformed Command

Description

If [Enable Message Configuration](#) is set to **Yes**, the Batch e*Way requires a specific XML message structure. This parameter specifies the action that the Batch e*Way takes when the Outgoing Event doesn't match the XML message structure the e*Way requires.

Note: This parameter is not used by the PeopleSoft Batch e*Way.

Required Values

One of the following values:

- Exit (the default value)
- Ignore
- Raise Alert
- Publish Error Record

API Functions

This chapter describes the most basic Monk functions used by the PeopleSoft Batch e*Way.

7.1 Overview

Two complete sets of Monk functions are used by the PeopleSoft Batch e*Way. This chapter lists only a subset of these functions, which are closely interlinked with [Monk Configuration](#) on page 83, and [Basic e*Way Processes](#) on page 69:

[Batch e*Way Standard Functions](#) on page 98

[ODBC e*Way Standard Functions](#) on page 105

[Generic e*Way Functions](#) on page 117

For descriptions of the entire set of Batch e*Way Monk functions, please see the *Batch e*Way Intelligent Adapter User's Guide*.

For descriptions of the entire set of ODBC e*Way Monk functions, please see the *e*Way Intelligent Adapter for ODBC User's Guide*.

7.2 Batch e*Way Standard Functions

The functions in this category are those called by Batch e*Way configuration parameters (see [Monk Configuration](#) on page 83), and include:

- [batch-ack](#) on page 98
- [batch-exchange-data](#) on page 99
- [batch-ext-connect](#) on page 99
- [batch-ext-shutdown](#) on page 100
- [batch-ext-verify](#) on page 100
- [batch-init](#) on page 101
- [batch-nak](#) on page 101
- [batch-proc-out](#) on page 102
- [batch-regular-proc-out](#) on page 102
- [batch-shutdown-notify](#) on page 103
- [batch-startup](#) on page 104

batch-ack

Description

Acknowledgment function that is called automatically when the e*Way successfully processes and queues Events from the external system.

Signature

(`batch-ack` *command*)

Parameters

Name	Type	Description
command	String	Any non-null string

Returns

Returns the string "FAILURE" on all errors; otherwise, returns a *null string*.

Throws

None.

Location

batch-ack.monk

Additional Information

This function is called only during the processing of inbound Events. After the [Exchange Data with External Function](#) returns a string that is transformed into an inbound Event, the Event is handed off to a Collaboration for further processing. If the Event's processing is completed successfully, the e*Way executes the [Positive Acknowledgment Function](#); otherwise, the e*Way executes the [Negative Acknowledgment Function](#).

This function can return an Event to be queued, but the e*Way does not return a positive or negative acknowledgement to the external system.

The e*Way exits if it fails its attempt to invoke this function or this function returns a "FAILURE" string.

batch-exchange-data

Description

Initiates an exchange of Events (either inbound or outbound) with an external system.

Signature

(batch-exchange-data)

Parameters

None.

Returns

Returns a *null string* if the function processed an *outbound* Event successfully; otherwise, returns a string to be packaged as an *inbound* Event.

Throws

None.

Location

batch-exchange-data.monk

batch-ext-connect

Description

Establishes or re-establishes a connection to the external system.

Signature

(batch-ext-connect)

Parameters

None.

Returns

Returns the string "UP" if the connection was made successfully; otherwise, returns the string "DOWN".

Throws

except-method

Location

batch-ext-connect.monk

batch-ext-shutdown

Description

Shuts down the connection between the external system and the e*Way.

Signature

(batch-ext-shutdown *command*)

Parameters

Name	Type	Description
command	String	Any non-null string

Returns

Returns a *null string*.

Throws

except-method

Location

batch-ext-shutdown.monk

batch-ext-verify

Description

Confirms that the external system is operating and available.

Signature

(batch-ext-verify)

Parameters

None.

Returns

Returns the string "UP" if the connection was verified successfully; otherwise, returns the string "DOWN".

Throws

except-method

Location

batch-ext-verify.monk

batch-init

Description

Loads the library file **stc_monkfilesys.dll**, and defines exceptions and variables upon which other e*Way functions depend.

Signature

(batch-init)

Parameters

None.

Returns

Returns the string "FAILURE" on all errors; otherwise, returns a *null string*.

Throws

except-method

Location

batch-init.monk

batch-nak

Description

Called automatically when the e*Way fails to process and queue Events from the external system.

Signature

(batch-nak *command*)

Parameters

Name	Type	Description
command	String	Any non-null string

Returns

Returns the string "FAILURE" on all errors; otherwise, returns a *null string*.

Throws

None.

Location

batch-nak.monk

Additional Information

This function is only called during the processing of inbound Events. After the [Exchange Data with External Function](#) returns a string that is transformed into an inbound Event, the Event is handed off to a Collaboration for further processing. If the

Event's processing is completed unsuccessfully, the e*Way executes the **Positive Acknowledgment Function**; otherwise, the e*Way executes the **Negative Acknowledgment Function**.

This function can return an Event to be queued, but the e*Way does not return a positive or negative acknowledgement to the external system.

The e*Way exits if it fails its attempt to invoke this function or this function returns a "FAILURE" string.

batch-proc-out

Description

Sends the outbound Event from the e*Way to the external system.

Signature

(batch-proc-out *Event*)

Parameters

Name	Type	Description
Event	String	The Event to be sent

Returns

Returns one of the following strings:

- ◆ Null ("")
- ◆ "RESEND"
- ◆ "CONNERR"
- ◆ "DATAERR"

Throws

None.

Location

batch-proc-out.monk

batch-regular-proc-out

Description

Sends the outbound Event from the e*Way to the external system.

Signature

(batch-regular-proc-out *Event*)

Parameters

Name	Type	Description
Event	String	The Event to be sent

Returns

Returns one of the following strings:

- ◆ *Null* (“”)
- ◆ “RESEND”
- ◆ “CONNERR”
- ◆ “DATAERR”

Throws

None.

Location

batch-regular-proc-out.monk

batch-shutdown-notify

Description

Notifies the external system that the e*Way is shutting down.

Signature

(*batch-shutdown-notify command*)

Parameters

Name	Type	Description
command	String	Any non-null string

Returns

Returns a *null string*.

Throws

None.

Location

batch-shutdown-notify.monk

batch-startup

Description

Launches a Monk function that starts the e*Way. The function that is invoked depends on whether the e*Way uses FTP or file transfer via `copy`, as selected by the **File Transfer Method** configuration parameter.

Signature

(batch-startup)

Parameters

None.

Returns

Returns the string "FAILURE" on all errors; otherwise, returns a *null string*.

Throws

except-method

Location

batch-startup.monk

7.3 ODBC e*Way Standard Functions

The functions in this category are those called by ODBC e*Way configuration parameters (see [Monk Configuration](#) on page 83), and include:

db-stdver-conn-estab on page 105	db-stdver-neg-ack on page 110
db-stdver-conn-shutdown on page 107	db-stdver-pos-ack on page 111
db-stdver-conn-ver on page 107	db-stdver-proc-outgoing on page 112
db-stdver-data-exchg on page 109	db-stdver-proc-outgoing-stub on page 113
db-stdver-data-exchg-stub on page 109	db-stdver-shutdown on page 114
db-stdver-init on page 110	db-stdver-startup on page 115

db-stdver-conn-estab

Description

Used to establish external system connection. The following tasks are performed by this function:

- Construct a new connection handle
- Call `db-long` to connect to database
- Set up timestamp format, if required
- Set up maximum long data buffer limit, if required
- Bind a dynamic SQL statement and stored procedures

Signature

```
(db-stdver-conn-estab)
```

Parameters

None.

Returns

Returns the string "UP" or "SUCCESS" if connection established, any other string if connection not established.

Throws

None.

Additional Information

In order to use the standard database time format, the following function call has been added to this function (immediately before the call to the **db-bind** function):

```
(db-std-timestamp-format connection-handle)
```

To override the use of the standard database time format, the **db-std-timestamp-format** function call should be removed.

For *Maximum Long Data Size* the ODBC library allocates an internal buffer for each `SQL_LONGVARCHAR` and `SQL_LONGVARBINARY` data, when the SQL statement or stored procedure that contains these data types are bound. The default size of each internal data buffer is 1 MB (1048576 bytes). If the user needs to handle long data larger than this default value, add the following function call to specify the maximum data size:

```
(db-max-long-data-size connection-handle maximum-data-size)
```

Examples

```
(define db-stdver-conn-estab
  (lambda ( )
    (let ((result "DOWN") (last_dberr ""))
      (display "[++] Executing e*Way external connection establishment
        function.")
      (display "db-stdver-conn-estab: logging into the database with:\n")
      (display "DATABASE NAME = ")
      (display DATABASE_SETUP_DATABASE_NAME)
      (newline )
      (display "USER NAME = ")
      (display DATABASE_SETUP_USER_NAME)
      (newline )
      (set! connection-handle (make-connection-handle))
      (if (connection-handle? connection-handle)
        (begin
          (if (db-login connection-handle DATABASE_SETUP_DATABASE_NAME
            DATABASE_SETUP_USER_NAME DATABASE_SETUP_ENCRYPTED_PASSWORD)
            (begin
              (db-bind )
              (set! result "UP")
            )
            (begin
              (set! last_dberr (db-get-error-str connection-handle))
              (display last_dberr)
              (event-send "ALERTCAT_OPERATIONAL" "ALERTSUBCAT_CANTCONN"
                "ALERTINFO_FATAL" "0" "Cannot connect to database" (string-append
                  "Failed to connect to database: " DATABASE_SETUP_DATABASE_NAME
                  "with error" last_dberr) 0 (list))
              (newline )
              (db-logout connection-handle)
              (set! result "DOWN")
            )
          )
        )
        (begin
          (set! result "DOWN")
          (display "Failed to create connection handle.")
          (event-send "ALERTCAT_OPERATIONAL" "ALERTSUBCAT_UNUSABLE"
            "ALERTINFO_FATAL" "0" "database connection handle creation error"
            "Failed to create database connection handle" 0 (list))
          )
        )
        result
      )
    ))
```

db-stdver-conn-shutdown

Description

Called by the system to request that the interface disconnect from the external system, preparing for a suspend/reload cycle.

Signature

```
(db-stdver-conn-shutdown string)
```

Parameters

Name	Type	Description
string	string	When the e*Way calls this function, it passes the string "SUSPEND_NOTIFICATION" as the parameter.

Returns

Any return value indicates that the suspend can occur immediately, and the interface is placed in the *down* state.

Throws

None.

Examples

```
(define db-stdver-conn-shutdown
  (lambda ( message-string )
    (let ((result "SUCCESS"))
      (comment "Std e*Way connection shutdown function" "[++] Usage:
        Function called by system to request that the interface
        disconnect from the external system, preparing for a suspend/
        reload cycle. Any return value indicates that the suspend can
        occur immediately, and the interface is placed in the down state.
        [++] Input to expect: Function should not expect input. [++]
        Expected return values: anything indicates that the external is
        ready to suspend.n")
      (comment "db-stdver-conn-shutdown [++] Implementation specific
        comment" "none")
      (display "[++] Executing e*Way external connection shutdown
        function.")
      (display message-string)
      (db-logout connection-handle)
      result
    )
  ))
```

db-stdver-conn-ver

Description

Used to verify whether or not the external system connection has been established.

Signature

```
(db-stdver-conn-ver)
```

Parameters

None.

Returns

The string "UP" or "SUCCESS" if connection established, any other string if connection not established.

Throws

None.

Additional Information

To use standard database time format, add the following function call to this function: (**db-std-timestamp-format** *connection-handle*) after the (**db-bind**) call.

This SQL statement is designed for database management systems other than Oracle. The use of this function occasionally results in an error in the e*Way's log file. Despite the error, however, the function will complete successfully.

Note: *To users of earlier versions of DART: db-check-connect calls should be replaced with db-alive calls.*

Examples

```
(define db-stdver-conn-ver
  (lambda ( )
    (let ((result "DOWN") (last_dberr ""))
      (display "[++] Executing e*Way external connection verification
function.")
      (display "db-stdver-conn-ver: checking connection status...\n")
      (cond ((string=? STCDB "SYBASE") (db-sql-select connection-handle
"verify" "select getdate()")) ((string=? STCDB "ORACLE8i") (db-
sql-select connection-handle "verify" "select sysdate from
dual")) ((string=? STCDB "ORACLE8") (db-sql-select connection-
handle "verify" "select sysdate from dual")) ((string=? STCDB
"ORACLE7") (db-sql-select connection-handle "verify" "select
sysdate from dual")) (else (db-sql-select connection-handle
"verify" "select {fn NOW()}"))))
      (if (db-alive connection-handle)
        (begin
          (db-sql-fetch-cancel connection-handle "verify")
          (set! result "UP")
        )
        (begin
          (set! last_dberr (db-get-error-str connection-handle))
          (display last_dberr)
          (event-send "ALERTCAT_OPERATIONAL" "ALERTSUBCAT_LOSTCONN"
"ALERTINFO_FATAL" "0" "Lost connection to database" (string-
append "Lost connection to database: "
DATABASE_SETUP_DATABASE_NAME "with error" last_dberr) 0 (list))
          (set! result "DOWN")
        )
      )
      result
    )
  ))
```

db-stdver-data-exchg

Description

Used for sending a received Event from the external system to e*Gate. The function expects no input.

Signature

```
(db-stdver-data-exchg)
```

Parameters

None.

Returns

- A message-string indicates a successful operation, and the Event is sent to e*Gate
- An empty string indicates a successful operation, but nothing is sent to e*Gate
- The string "CONNERR" indicates loss of connection with the external

In the latter case, the client moves to a *down* state and attempts to connect; upon reconnecting, this function is re-executed using the same input message.

Throws

None.

Examples

```
(define db-stdver-data-exchg
  (lambda ( )
    (let ((result ""))
      (display "[++] Executing e*Way external data exchange function.")
      result
    )
  ))
```

db-stdver-data-exchg-stub

Description

Used as a place holder for the function entry point for sending an Event from the external system to e*Gate. The function expects no input.

Note: This function should **not** be used when the interface is configured as an outbound-only connection.

Signature

```
(db-stdver-data-exchg-stub)
```

Parameters

None.

Returns

- A message-string indicates a successful operation, and the Event is sent to e*Gate

- An empty string indicates a successful operation, but nothing is sent to e*Gate
- The string "CONNERR" indicates loss of connection with the external

In the latter case, the client moves to a *down* state and attempts to connect; upon reconnecting, this function is re-executed using the same input message.

Throws

None.

Examples

```
(define db-stdver-data-exchg-stub
  (lambda ( )
    (let ((result ""))
      (event-send "ALERTCAT_OPERATIONAL" "ALERTSUBCAT_INTEREST"
        "ALERTINFO_NONE" "0" "Possible configuration error." "Default
        away data exchange function called." 0 (list))
      result
    )
  ))
```

db-stdver-init

Description

This function begins the initialization process for the e*Way. It loads all of the Monk extension library files that the other e*Way functions access.

Signature

```
(db-stdver-init)
```

Parameters

None.

Returns

If a "FAILURE" string is returned, the e*Way shuts down; any other return indicates success.

Throws

None.

db-stdver-neg-ack

Description

Used to send a negative acknowledgement to the external system, and for post-processing after failing to send data to e*Gate.

Signature

```
(db-stdver-neg-ack message-string)
```

Parameters

Name	Description
message-string	The Event for which a negative acknowledgment is sent.

Returns

- A *null string* indicates a successful operation.
- The string "CONNERR" indicates a loss of connection with the external

In the latter case, the client moves to a *down* state and attempts to connect; upon reconnection, this function is re-executed.

Throws

None.

Examples

```
(define db-stdver-neg-ack
  (lambda ( message-string )
    (let ((result ""))
      ( (display "[++] Executing e*Way external negative acknowledgment
          function.")
        (display message-string)
        result
      )
    ))
```

db-stdver-pos-ack

Description

Used to send a positive acknowledgement to the external system, and for post-processing after successfully sending data to e*Gate.

Signature

```
(db-stdver-pos-ack message-string)
```

Parameters

Name	Description
message-string	The Event for which an acknowledgment is sent.

Returns

- A *null string* indicates a successful operation, and the e*Way is then able to proceed with the next request
- The string "CONNERR" indicates a loss of connection with the external

In the latter case, the client moves to a *down* state and attempts to connect; upon reconnection, this function is re-executed.

Throws

None.

Examples

```
(define db-stdver-pos-ack
  (lambda ( message-string )
    (let ((result ""))
      (display "[++] Executing e*Way external positive acknowledgement
        function.")
      (display message-string)
      result
    )
  ))
```

db-stdver-proc-outgoing

Description

Used for sending a received message (Event) from e*Gate to the external system.

Signature

```
(db-stdver-proc-outgoing message-string)
```

Parameters

Name	Type	Description
message-string	string	The Event to be processed.

Returns

One of the following strings (if a string other than the following is returned, the e*Way creates an entry in the log file indicating that an attempt has been made to access an unsupported function).

- A *null string* indicates a successful operation
- The string "RESEND" causes the message to be resent immediately

In this case, the e*Way compares the number of attempts it has made to send the Event to the number specified in the Max Resends per Messages parameter, and does one of the following:

- ♦ If the number of attempts does not exceed the maximum, the e*Way pauses the number of seconds specified by the **Resend Timeout** parameter, increment the *resend attempts* counter for that message, then repeat the attempt to send the message
- ♦ If the number of attempts exceeds the maximum, the function returns *false* and rolls back the message to the e*Gate IQ from which it was obtained
- The string "CONNERR" indicates that there is a problem communicating with the external system

In this case, the e*Way pauses the number of seconds specified by the **Resend Timeout** parameter, then calls the **External Connection Establishment Function**

according to the **Down Timeout** schedule, and rolls back the message (Event) to the IQ from which it was obtained.

- The string "DATAERR" indicates that there is a problem with the message (Event) data itself

In this case, the e*Way pauses the number of seconds specified by the **Resend Timeout** parameter, then increments its *failed message* counter and rolls back the message (Event) to the IQ from which it was obtained. If the e*Way's journal is enabled (see the **Journal File Name** configuration parameter) the message (Event) is saved to the journal file.

Throws

None.

Examples

```
(define db-stdver-proc-outgoing
  (lambda ( message-string )
    (let ((result ""))
      (display "[++] Executing e*Way external process outgoing message
                function.")
      (display message-string)
      result
    )
  ))
```

db-stdver-proc-outgoing-stub

Description

Used as a place holder for the function entry point for sending an Event received from e*Gate to the external system (used to catch configuration problems).

Note: *This function should **not** be used when the interface is configured as an inbound-only connection.*

Signature

(db-stdver-proc-outgoing-stub *message-string*)

Parameters

Name	Type	Description
message-string	string	The Event to be processed.

Returns

One of the following strings (if a string other than the following is returned, the e*Way creates an entry in the log file indicating that an attempt has been made to access an unsupported function).

- A *null string* indicates a successful operation
- The string "RESEND" causes the message to be resent immediately

In this case, the e*Way compares the number of attempts it has made to send the Event to the number specified in the Max Resends per Messages parameter, and does one of the following:

- ◆ If the number of attempts does not exceed the maximum, the e*Way pauses the number of seconds specified by the **Resend Timeout** parameter, increment the *resend attempts* counter for that message, then repeat the attempt to send the message
- ◆ If the number of attempts exceeds the maximum, the function returns *false* and rolls back the message to the e*Gate IQ from which it was obtained
- The string "CONNERR" indicates that there is a problem communicating with the external system

In this case, the e*Way pauses the number of seconds specified by the **Resend Timeout** parameter, then calls the **External Connection Establishment Function** according to the **Down Timeout** schedule, and rolls back the message (Event) to the IQ from which it was obtained.

- The string "DATAERR" indicates that there is a problem with the message (Event) data itself

In this case, the e*Way pauses the number of seconds specified by the **Resend Timeout** parameter, then increments its *failed message* counter and rolls back the message (Event) to the IQ from which it was obtained. If the e*Way's journal is enabled (see the **Journal File Name** configuration parameter) the message (Event) is saved to the journal file.

Throws

None.

Examples

```
(define db-stdver-proc-outgoing-stub
  (lambda ( message-string )
    (let ((result ""))
      (display "[++] Executing e*Way external process outgoing message
function stub.")
      (display message-string)
      (event-send "ALERTCAT_OPERATIONAL" "ALERTSUBCAT_INTEREST"
        "ALERTINFO_NONE" "0" "Possible configuration error." (string-
append "Default eway process outgoing msg function passed
following message: " msg) 0 (list))
      result
    )
  ))
```

db-stdver-shutdown

Description

Called by the system to request that the external shutdown, a return value of **SUCCESS** indicates that the shutdown can occur immediately, any other return value indicates that the shutdown Event must be delayed. You are then required to execute a shutdown-request call from within a monk function to allow the requested shutdown process to continue.

Signature

`(db-stdver-shutdown shutdown_notification)`

Parameters

Name	Type	Description
shutdown_notification	string	When the e*Way calls this function, it passes the string "SHUTDOWN_NOTIFICATION" as the parameter.

Returns

The string "SUCCESS" allows an immediate shutdown to occur; anything else delays shutdown until [shutdown-request](#) is executed successfully.

Throws

None.

Examples

```
(define db-stdver-shutdown
  (lambda ( message-string )
    (let ((result "SUCCESS"))
      (display "[++] Executing e*Way external shutdown command
notification function.")
      result
    )
  ))
```

db-stdver-startup

Description

Used for instance specific function loads and invokes setup.

Signature

`(db-stdver-startup)`

Parameters

None.

Returns

The string "FAILURE" causes shutdown of the e*Way; any other return indicates success.

Throws

None.

Examples

```
(define db-stdver-startup
  (lambda ( )
    (let ((result "SUCCESS"))
      (display "[++] Executing e*Way external startup function.")
      result
    )
  ))
```

7.4 Generic e*Way Functions

The functions described in this section control the e*Way's most basic operations, and can only be used by the functions defined within the e*Way's configuration file. None of these functions is available to Collaboration Rules scripts executed by the e*Way.

The current set of basic Monk functions is:

- [event-commit-to-egate](#) on page 117
- [event-rollback-to-egate](#) on page 118
- [event-send-to-egate](#) on page 118
- [event-send-to-egate-ignore-shutdown](#) on page 119
- [event-send-to-egate-no-commit](#) on page 119
- [get-logical-name](#) on page 120
- [insert-exchange-data-event](#) on page 120
- [send-external-up](#) on page 121
- [send-external-down](#) on page 121
- [shutdown-request](#) on page 122
- [start-schedule](#) on page 122
- [stop-schedule](#) on page 123
- [waiting-to-shutdown](#) on page 123

event-commit-to-egate

Description

Commits the Event sent previously to the e*Gate system using [event-send-to-egate-no-commit](#).

Signature

`(event-commit-to-egate string)`

Parameters

Name	Type	Description
string	string	The data to be sent to the e*Gate system.

Returns

Boolean true (**#t**) if the data is committed successfully; otherwise, false (**#f**).

Throws

None.

event-rollback-to-egate

Description

Rolls back the Event sent previously to the e*Gate system using **event-send-to-egate-no-commit**, following receipt of a rollback command from the external system.

Signature

`(event-rollback-to-egate string)`

Parameters

Name	Type	Description
string	string	The data to be rolled back to the e*Gate system.

Returns

Boolean true (#t) if the data is rolled back successfully; otherwise, false (#f).

Throws

None.

event-send-to-egate

Description

Sends data that the e*Way has already received from the external system into the e*Gate system as an Event.

Signature

`(event-send-to-egate string)`

Parameters

Name	Type	Description
string	string	The data to be sent to the e*Gate system

Returns

A Boolean true (#t) if the data is sent successfully; otherwise, a Boolean false (#f).

Throws

None.

Additional information

This function can be called by any e*Way function when it is necessary to send data to the e*Gate system in a blocking fashion.

See also

[event-send-to-egate-ignore-shutdown](#) on page 119

[event-send-to-egate-no-commit](#) on page 119

event-send-to-egate-ignore-shutdown

Description

Sends data that the e*Way has already received from the external system into the e*Gate system as an Event—but ignores any pending shutdown issues.

Signature

`(event-send-to-egate-ignore-shutdown string)`

Parameters

Name	Type	Description
string	string	The data to be sent to the e*Gate system.

Returns

Boolean true (**#t**) if the data is sent successfully; otherwise, false (**#f**).

Throws

None.

See also

[event-send-to-egate](#) on page 118

[event-send-to-egate-no-commit](#) on page 119

event-send-to-egate-no-commit

Description

Sends data that the e*Way has received from the external system to the e*Gate system as an Event—but without Committing, pending confirmation from the external system of correct transmission of the data.

Signature

`(event-send-to-egate-no-commit string)`

Parameters

Name	Type	Description
string	string	The data to be sent to the e*Gate system.

Returns

Boolean true (#t) if the data is sent successfully; otherwise, false (#f).

Throws

None.

See also

[event-commit-to-egate](#) on page 117

[event-rollback-to-egate](#) on page 118

[event-send-to-egate](#) on page 118

[event-send-to-egate-ignore-shutdown](#) on page 119

get-logical-name

Description

Returns the logical name of the e*Way.

Signature

(get-logical-name)

Parameters

None.

Returns

The name of the e*Way (as defined by the e*Gate Enterprise Manager).

Throws

None.

insert-exchange-data-event

Description

While the [Exchange Data with External Function](#) is still active, this function can be called to initiate a repeat call to it—whether or not data was queued to e*Gate via the function’s return mechanism following the initial call.

Signature

(insert-exchange-data-event)

Parameters

None.

Returns

None.

Throws

None.

See also

[Exchange Data Interval](#) on page 79

[Zero Wait Between Successful Exchanges](#) on page 79

send-external-up

Description

Informs the e*Way that the connection to the external system is up.

Signature

(send-external-up)

Parameters

None.

Returns

None.

Throws

None.

send-external-down

Description

Informs the e*Way that the connection to the external system is down.

Signature

(send-external-down)

Parameters

None.

Returns

None.

Throws

None.

shutdown-request

Description

Completes the e*Gate shutdown procedure that was initiated by the Control Broker but was interrupted by returning a non-null value within the [Shutdown Command Notification Function](#). Once this function is called, shutdown proceeds immediately.

Signature

(shutdown-request)

Parameters

None.

Returns

None.

Throws

None.

Additional Information

Once interrupted, the e*Way's shutdown cannot proceed until this Monk function is called. If you do interrupt an e*Way shutdown, we recommend that you complete the process in a timely fashion.

start-schedule

Description

Requests that the e*Way execute the [Exchange Data with External Function](#) specified within the e*Way's configuration file. Does not affect any defined schedules.

Signature

(start-schedule)

Parameters

None.

Returns

None.

Throws

None.

stop-schedule

Description

Requests that the e*Way halt execution of the [Exchange Data with External Function](#) specified within the e*Way's configuration file. Execution is stopped when the e*Way concludes any open transaction. Does not effect any defined schedules, and does not halt the e*Way process itself.

Signature

(stop-schedule)

Parameters

None.

Returns

None.

Throws

None.

waiting-to-shutdown

Description

Informs the external application that a shutdown command has been issued.

Signature

(waiting-to-shutdown)

Parameters

None.

Returns

Boolean true (**#t**) if successful; otherwise, false (**#f**).

Throws

None.

Document Type Definitions

This appendix provides Document Type Definitions (DTDs) for the XML Messages used in Dynamic Configuration.

A.1 Receive XML Messages

The DTD below provides details of the XML Message that can be used for Receive orders.

```
<!-- Copyright (C) 2000, SeeBeyond Technology Corporation, All rights reserved. -->
<!-- batch eWay order record format. -->
<!ELEMENT batch_eWay_order (command,
                            (order_record)+,
                            payload?) >
<!ELEMENT command (#PCDATA) >
<!ATTLIST command Enumeration (send|receive) "send" >
<!ELEMENT order_record (external_host_setup?,
                        (subscribe_to_external|publish_to_external)?,
                        FTP?,
                        SOCKS?) >
<!ELEMENT external_host_setup (host_type?,
                               external_host_name?,
                               user_name?,
                               encrypted_password?,
                               file_transfer_method?,
                               return_tag?) >
<!ELEMENT host_type (#PCDATA) >
<!ELEMENT external_host_name (#PCDATA) >
<!ELEMENT user_name (#PCDATA) >
<!ELEMENT encrypted_password (#PCDATA) >
<!ELEMENT file_transfer_method (#PCDATA) >
<!ATTLIST file_transfer_method Enumeration (ftp|copy) "ftp" >
<!ELEMENT return_tag (#PCDATA) >
<!ELEMENT subscribe_to_external (remote_directory_name?,
                                 remote_file_regexp?,
                                 remote_command_after_transfer?,
                                 remote_rename_or_archive_name?,
                                 local_command_after_transfer?,
                                 local_archive_directory?) >
<!ELEMENT remote_directory_name (#PCDATA) >
<!ELEMENT remote_file_regexp (#PCDATA) >
<!ELEMENT remote_command_after_transfer (#PCDATA) >
<!ATTLIST remote_command_after_transfer Enumeration
(archive|delete|none|rename) "delete" >
<!ELEMENT remote_rename_or_archive_name (#PCDATA) >
<!ELEMENT local_command_after_transfer (#PCDATA) >
```

```

<!ATTLIST local_command_after_transfer Enumeration (archive|delete)
"delete" >
<!ELEMENT local_archive_directory (#PCDATA) >
<!ELEMENT publish_to_external (remote_directory_name?,
remote_file_name?,
append_or_overwrite_when_transferring_files?,
remote_command_after_transfer?,
remote_rename_or_archive_name?,
local_command_after_transfer?,
local_archive_directory?) >
<!ELEMENT remote_file_name (#PCDATA) >
<!ELEMENT append_or_overwrite_when_transferring_files (#PCDATA) >
<!ATTLIST append_or_overwrite_when_transferring_files Enumeration
(append|overwrite) "append" >
<!ELEMENT FTP (server_port,
mode) >
<!ELEMENT server_port (#PCDATA) >
<!ELEMENT mode (#PCDATA) >
<!ELEMENT SOCKS
(server_host_name,server_port,method,user_name,encrypted_password) >
<!ELEMENT server_host_name (#PCDATA) >
<!ELEMENT method (#PCDATA) >
<!ELEMENT payload (#PCDATA) >

```

A.2 Error Messages

The DTD below is used for the Error Reporting XML Message.

```

<!-- Copyright (C) 2000, SeeBeyond Technology Corporation, All rights
reserved. -->
<!-- batch away error record format. -->
<!ELEMENT batch_eWay_error (command,
(return_tag|order_record)?,
error_record,
payload?) >
<!ELEMENT command (#PCDATA) >
<!ATTLIST command Enumeration (send|receive) "send" >
<!ELEMENT order_record (external_host_setup?,
(subscribe_to_external|publish_to_external)?,
FTP?,
SOCKS?) >
<!ELEMENT external_host_setup (host_type?,
external_host_name?,
user_name?,
encrypted_password?,
file_transfer_method?,
return_tag?) >
<!ELEMENT host_type (#PCDATA) >
<!ELEMENT external_host_name (#PCDATA) >
<!ELEMENT user_name (#PCDATA) >
<!ELEMENT encrypted_password (#PCDATA) >
<!ELEMENT file_transfer_method (#PCDATA) >
<!ATTLIST file_transfer_method Enumeration (ftp|copy) "ftp" >
<!ELEMENT return_tag (#PCDATA) >
<!ELEMENT subscribe_to_external (remote_directory_name?,
remote_file_regexp?,
remote_command_after_transfer?,
remote_rename_or_archive_name?,

```

```

                                local_command_after_transfer?,
                                local_archive_directory?) >
<!ELEMENT remote_directory_name (#PCDATA) >
<!ELEMENT remote_file_regexp (#PCDATA) >
<!ELEMENT remote_command_after_transfer (#PCDATA) >
<!ATTLIST remote_command_after_transfer Enumeration
(archive|delete|none|rename) "delete" >
<!ELEMENT remote_rename_or_archive_name (#PCDATA) >
<!ELEMENT local_command_after_transfer (#PCDATA) >
<!ATTLIST local_command_after_transfer Enumeration (archive|delete)
"delete" >
<!ELEMENT local_archive_directory (#PCDATA) >
<!ELEMENT publish_to_external (remote_directory_name?,
                                remote_file_name?,
                                append_or_overwrite_when_transferring_files?,
                                remote_command_after_transfer?,
                                remote_rename_or_archive_name?,
                                local_command_after_transfer?,
                                local_archive_directory?) >
<!ELEMENT remote_file_name (#PCDATA) >
<!ELEMENT append_or_overwrite_when_transferring_files (#PCDATA) >
<!ATTLIST append_or_overwrite_when_transferring_files Enumeration
(append|overwrite) "append" >
<!ELEMENT FTP (server_port,
                                mode) >
<!ELEMENT server_port (#PCDATA) >
<!ELEMENT mode (#PCDATA) >
<!ELEMENT SOCKS
(server_host_name,server_port,method,user_name,encrypted_password) >
<!ELEMENT server_host_name (#PCDATA) >
<!ELEMENT method (#PCDATA) >
<!ELEMENT payload (#PCDATA) >
<!ELEMENT error_record (error_code,
                                error_text,
                                last_action) >
<!ELEMENT error_code (#PCDATA) >
<!ELEMENT error_text (#PCDATA) >
<!ELEMENT last_action (#PCDATA) >

```

A.3 Data Message

The DTD file below provides a data structure, includes a data payload, and is used for transporting data to a Batch e*Way.

```

<!-- Copyright (C) 2000, SeeBeyond Technology Corporation, All rights
reserved. -->
<!-- batch_eway_data record format. -->
<!ELEMENT batch_eway_data (command,
                                (return_tag|order_record)?,
                                payload) >
<!ELEMENT command (#PCDATA) >
<!ATTLIST command Enumeration (send|receive) "send" >
<!ELEMENT order_record (external_host_setup?,
                                (subscribe_to_external|publish_to_external)?,
                                FTP?,
                                SOCKS?) >
<!ELEMENT external_host_setup (host_type?,
                                external_host_name?,

```

```

        user_name?,
        encrypted_password?,
        file_transfer_method?,
        return_tag?) >
<!ELEMENT host_type (#PCDATA) >
<!ELEMENT external_host_name (#PCDATA) >
<!ELEMENT user_name (#PCDATA) >
<!ELEMENT encrypted_password (#PCDATA) >
<!ELEMENT file_transfer_method (#PCDATA) >
<!ATTLIST file_transfer_method Enumeration (ftp|copy) "ftp" >
<!ELEMENT return_tag (#PCDATA) >
<!ELEMENT subscribe_to_external (remote_directory_name?,
        remote_file_regexp?,
        remote_command_after_transfer?,
        remote_rename_or_archive_name?,
        local_command_after_transfer?,
        local_archive_directory?) >
<!ELEMENT remote_directory_name (#PCDATA) >
<!ELEMENT remote_file_regexp (#PCDATA) >
<!ELEMENT remote_command_after_transfer (#PCDATA) >
<!ATTLIST remote_command_after_transfer Enumeration
(archive|delete|none|rename) "delete" >
<!ELEMENT remote_rename_or_archive_name (#PCDATA) >
<!ELEMENT local_command_after_transfer (#PCDATA) >
<!ATTLIST local_command_after_transfer Enumeration (archive|delete)
"delete" >
<!ELEMENT local_archive_directory (#PCDATA) >
<!ELEMENT publish_to_external (remote_directory_name?,
        remote_file_name?,
        append_or_overwrite_when_transferring_files?,
        remote_command_after_transfer?,
        remote_rename_or_archive_name?,
        local_command_after_transfer?,
        local_archive_directory?) >
<!ELEMENT remote_file_name (#PCDATA) >
<!ELEMENT append_or_overwrite_when_transferring_files (#PCDATA) >
<!ATTLIST append_or_overwrite_when_transferring_files Enumeration
(append|overwrite) "append" >
<!ELEMENT FTP (server_port,
        mode) >
<!ELEMENT server_port (#PCDATA) >
<!ELEMENT mode (#PCDATA) >
<!ELEMENT SOCKS
(server_host_name,server_port,method,user_name,encrypted_password) >
<!ELEMENT server_host_name (#PCDATA) >
<!ELEMENT method (#PCDATA) >
<!ELEMENT payload (#PCDATA) >

```

ODBC Monk Scripts

7.5 Sample Monk Scripts

This section includes sample Monk scripts that demonstrate how to use the ODBC e*Way's Monk functions to implement the following activities:

[Initializing Monk Extensions](#) on page 129

[Calling Stored Procedures](#) on page 130

[Inserting Records with Dynamic SQL Statements](#) on page 132

[Updating Records with Dynamic SQL Statements](#) on page 134

[Selecting Records with Dynamic SQL Statements](#) on page 136

[Deleting Records with Dynamic SQL Statements](#) on page 138

[Inserting a Binary Image to a Database](#) on page 139

[Retrieving an Image from a Database](#) on page 142

[Common Supporting Routines](#) on page 144

7.5.1 Initializing Monk Extensions

The sample script shows how to initialize the Monk extensions. This function is used by many of the other sample Monk scripts shown in this chapter.

To use this sample script in an actual implementation, modify the following values:

- **EGATE** – This designates the location of the e*Gate client.
- **dsn** – This is the name of the data source.
- **uid** – This is the user name.
- **pwd** – This is the login password.

```
;demo-init.monk

(define EGATE "/eGate/client")

; routine to load DART Monk extension
(define (load-library extension)
  (define filename (string-append EGATE "/bin/" extension))
  (if (file-exists? filename)
      (load-extension filename)
      (begin
        (display (string-append "File " filename " does not
exist.\n"))
        (abort filename)
      )
  )
)

(load-library "stc_monkext.dll")

;;
;; define STCDB variables, data source, user ID, and password
;;

(define STCDB "ORACLE8")

(load-library "stc_dbmonkext.dll")

(define dsn "database")
(define uid "Administrator")
(define pwd (encrypt-password uid "password"))
```

7.5.2 Calling Stored Procedures

This script gives an example of calling Stored Procedures (see the *e*Way Intelligent Adapter for ODBC User's Guide*) Refer to [Benefits of Stored Procedures](#) on page 64 for additional details.

```
;demo-proc-execute.monk

; load Monk database extension
(load "demo-init.monk")
(load "demo-common.monk")

; call stored procedure and display results
(define (execute-procedure hdbc hstmt)
  (let ((prm-count (db-proc-param-count hdbc hstmt)))
    (if (db-proc-execute hdbc hstmt)
        (begin
          (do ((col-count (db-proc-column-count hdbc hstmt) (db-
proc-column-count hdbc hstmt)))
              ((or (not (number? col-count)) (= col-count 0)))
              (display-proc-column-property hdbc hstmt col-count)
              (display-proc-column-value hdbc hstmt col-count)
            )
          (display-proc-parameter-output-value hdbc hstmt prm-count)
          (if (db-proc-return-exist hdbc hstmt)
              (begin
                (display "return: value = ")
                (display (db-proc-return-value hdbc hstmt))
                (newline)
              )
            )
          (display (db-get-error-str hdbc))
        )
      )
  )
)

; make new connection handle
(define hdbc (make-connection-handle))
(if (not (connection-handle? hdbc))
    (display (db-get-error-str hdbc))
  )

(if (db-login hdbc dsn uid pwd)
    (begin
      (display "\ndatabase login succeed !\n")

      ; bind the stored procedure
      (define hstmt1 (bind-procedure hdbc "PERSONNEL.GET_EMPLOYEES"))

      ; call the stored procedure if the binding is successful
      (if (statement-handle? hstmt1)
          (begin
            (display "call PERSONNEL.GET_EMPLOYEES to get all sales
...\n\n")
            (if (and
                  (db-proc-param-assign hdbc hstmt1 0 "30")
                  (db-proc-param-assign hdbc hstmt1 1 "10")
                )
                (execute-procedure hdbc hstmt1)
                (display (db-get-error-str hdbc))
            )
          )
        )
  )
)
```

```
    )  
    (if (not (db-logout hdbc))  
        (display (db-get-error-str hdbc))  
    )  
    )  
    (display (db-get-error-str hdbc))  
    )
```

7.5.3 Inserting Records with Dynamic SQL Statements

```

;demo-stmt-insert.monk

; load Monk database extension
(load "demo-init.monk")
(load "demo-common.monk")

; execute dynamic statement and display results
(define (execute-statement hdbc hstmt)
  (if (db-stmt-execute hdbc hstmt)
      (begin
        (display-stmt-row-count hdbc hstmt)
        #t
      )
      #f
  )
)

; make new connection handle
(define hdbc (make-connection-handle))
(if (not (connection-handle? hdbc))
    (display (db-get-error-str hdbc))
)

(define stmt1 "INSERT INTO SCOTT.BONUS SELECT ENAME, JOB, SAL, COMM
FROM SCOTT.EMP WHERE DEPTNO = ?")

(if (db-login hdbc dsn uid pwd)
    (begin
      (display "\ndatabase login succeed !\n")

      ; bind the dynamic statement
      (define hstmt1 (bind-statement hdbc stmt1))

      ; assign parameter and execute the dynamic statement
      (if (statement-handle? hstmt1)
          (begin
            (display "\nInsert accounting department into bonus table
... \n")
            (if (db-stmt-param-assign hdbc hstmt1 0 "10")
                (if (execute-statement hdbc hstmt1)
                    (begin
                      (display "\nCommit the insertions ... \n")
                      (if (not (db-commit hdbc))
                          (display (db-get-error-str hdbc))
                      )
                    )
                (display (db-get-error-str hdbc))
            )
            (display (db-get-error-str hdbc))
          )
          (display "\nInsert sales department into bonus table
... \n")
          (if (db-stmt-param-assign hdbc hstmt1 0 "20")
              (if (execute-statement hdbc hstmt1)
                  (begin
                    (display "\nCommit the insertions ... \n")
                    (if (not (db-commit hdbc))
                        (display (db-get-error-str hdbc))
                    )
                  )
              (display (db-get-error-str hdbc))
            )
          )
        )
      )
    )
  )

```

```
        )  
        (display (db-get-error-str hdbc))  
    )  
    )  
    (if (not (db-logout hdbc))  
        (display (db-get-error-str hdbc))  
    )  
    )  
    (display (db-get-error-str hdbc))  
)
```

7.5.4 Updating Records with Dynamic SQL Statements

```
;demo-stmt-update.monk

; load Monk database extension
(load "demo-init.monk")
(load "demo-common.monk")

; execute dynamic statement and display results
(define (execute-statement hdbc hstmt)
  (if (db-stmt-execute hdbc hstmt)
      (begin
        (display-stmt-row-count hdbc hstmt)
        #t
      )
      #f
  )
)

; make new connection handle
(define hdbc (make-connection-handle))
(if (not (connection-handle? hdbc))
    (display (db-get-error-str hdbc))
)

(define stmt1 "UPDATE SCOTT.BONUS SET COMM = ? WHERE JOB = ?")

(if (db-login hdbc dsn uid pwd)
    (begin
      (display "\ndatabase login succeed !\n")

      ; bind the dynamic statement
      (define hstmt1 (bind-statement hdbc stmt1))

      ; assign parameter and execute the dynamic statement
      (if (statement-handle? hstmt1)
          (begin
            (display "\nUpdate commission of manager ...\n")
            (if
              (and
                (db-stmt-param-assign hdbc hstmt1 0 "10")
                (db-stmt-param-assign hdbc hstmt1 1 "MANAGER")
              )
              (if (execute-statement hdbc hstmt1)
                  (begin
                    (display "\nCommit the updates ...\n")
                    (if (not (db-commit hdbc))
                        (display (db-get-error-str hdbc))
                    )
                  )
                  (display (db-get-error-str hdbc))
                )
              (display (db-get-error-str hdbc))
            )
          )
          (display "\nUpdate commission of clerk ...\n")
          (if
            (and
              (db-stmt-param-assign hdbc hstmt1 0 "20")
              (db-stmt-param-assign hdbc hstmt1 1 "CLERK")
            )
            (if (execute-statement hdbc hstmt1)
                (begin
                  (display "\nCommit the updates ...\n")
                )
            )
          )
        )
    )
)
```


7.5.5 Selecting Records with Dynamic SQL Statements

```

;demo-stmt-select.monk

; load Monk database extension
(load "demo-init.monk")
(load "demo-common.monk")

; execute dynamic statement and display results
(define (execute-statement hdbc hstmt)
  (if (db-stmt-execute hdbc hstmt)
      (begin
        (display-stmt-column-value hdbc hstmt)
        #t
      )
      #f
  )
)

; make new connection handle
(define hdbc (make-connection-handle))
(if (not (connection-handle? hdbc))
    (display (db-get-error-str hdbc))
)

(define stmt1 "SELECT EMPNO, ENAME, JOB FROM SCOTT.EMP WHERE JOB = ?")
(define stmt2 "SELECT ENAME, DNAME, JOB, HIREDATE FROM SCOTT.EMP,
SCOTT.DEPT WHERE EMP.DEPTNO = DEPT.DEPTNO AND DEPT.DNAME = ?")

(if (db-login hdbc dsn uid pwd)
    (begin
      (display "\ndatabase login succeed !\n")

      ; bind the dynamic statements
      (define hstmt1 (bind-statement hdbc stmt1))
      (define hstmt2 (bind-statement hdbc stmt2))

      ; assign parameter and execute the dynamic statement
      (if (statement-handle? hstmt1)
          (begin
            (display "\nList all salesman ...\n\n")
            (if (db-stmt-param-assign hdbc hstmt1 0 "SALESMAN")
                (if (not (execute-statement hdbc hstmt1))
                    (display (db-get-error-str hdbc))
                )
                (display (db-get-error-str hdbc))
            )
            (display "\nList all manager ...\n\n")
            (if (db-stmt-param-assign hdbc hstmt1 0 "MANAGER")
                (if (not (execute-statement hdbc hstmt1))
                    (display (db-get-error-str hdbc))
                )
                (display (db-get-error-str hdbc))
            )
          )
      )

      (if (statement-handle? hstmt2)
          (begin
            (display "\nList employee of accounting department
...\n\n")
            (if (db-stmt-param-assign hdbc hstmt2 0 "ACCOUNTING")
                (if (not (execute-statement hdbc hstmt2))
                    (display (db-get-error-str hdbc))
                )
            )
          )
      )
    )
)

```



```
        )
      (display (db-get-error-str hdbc))
    )
  )
  (display (db-get-error-str hdbc))
)
(if (not (db-logout hdbc))
  (display (db-get-error-str hdbc))
)
)
(display (db-get-error-str hdbc))
)
```

7.5.6 Deleting Records with Dynamic SQL Statements

```

;demo-stmt-delete.monk

; load Monk database extension
(load "demo-init.monk")
(load "demo-common.monk")

; execute dynamic statement and display results
(define (execute-statement hdbc hstmt)
  (if (db-stmt-execute hdbc hstmt)
      (begin
        (display-stmt-row-count hdbc hstmt)
        #t
      )
      #f
  )
)

; make new connection handle
(define hdbc (make-connection-handle))
(if (not (connection-handle? hdbc))
    (display (db-get-error-str hdbc))
)

(define stmt1 "DELETE FROM SCOTT.BONUS WHERE ENAME IS NOT NULL")

(if (db-login hdbc dsn uid pwd)
    (begin
      (display "\ndatabase login succeed !\n")

      ; bind the dynamic statement
      (define hstmt1 (bind-statement hdbc stmt1))

      ; assign parameter and execute the dynamic statement
      (if (statement-handle? hstmt1)
          (begin
            (display "\nDelete records from scott.bonus table ...\n")
            (if (execute-statement hdbc hstmt1)
                (begin
                  (display "\nCommit the deletions ...\n")
                  (if (not (db-commit hdbc))
                      (display (db-get-error-str hdbc))
                  )
                )
            )
            (display (db-get-error-str hdbc))
          )
      )
    )

    (if (not (db-logout hdbc))
        (display (db-get-error-str hdbc))
    )
  )
  (display (db-get-error-str hdbc))
)

```

7.5.7 Inserting a Binary Image to a Database

This sample shows how to insert a Binary Image into a Database. It uses both Static and Dynamic SQL functions. See the *e*Way Intelligent Adapter for ODBC User's Guide* for more details.

```

;demo-image-insert.monk

; load Monk database extension
(load "demo-init.monk")
(load "demo-common.monk")

(define (query-exist hdbc hstmt id)
  (let ((rec-count 0) (result '#()))
    (if (db-stmt-param-assign hdbc hstmt 0 id)
        (if (db-stmt-execute hdbc hstmt)
            (begin
              (set! result (vector-ref (db-stmt-fetch hdbc hstmt) 0))
              (set! rec-count (string->number result))
              (set! result (db-stmt-fetch-cancel hdbc hstmt))
              (if (> rec-count 0)
                  (begin
                    (display "image already exist\n")
                    #t
                  )
                  #f
                )
              )
            )
        (begin
          (display (db-get-error-str hdbc))
          #f
        )
      )
    (begin
      (display (db-get-error-str hdbc))
      #f
    )
  )
)

(define (execute-statement hdbc hstmt)
  (let ((col-count (db-stmt-column-count hdbc hstmt)) (row-count 0))
    (if (db-stmt-execute hdbc hstmt)
        (begin
          (if (> col-count 0)
              (if (not (display-stmt-column-value hdbc hstmt col-
count))
                  (display (db-get-error-str hdbc))
                  )
              )
          (set! row-count (db-stmt-row-count hdbc hstmt))
          (if (boolean? row-count)
              (display (db-get-error-str hdbc))
              (display (string-append "number of image insert = "
(number->string row-count) "\n"))
            )
          (newline)
          #t
        )
        #f
      )
  )
)

```

```

)

(define (bind-image-statement hdbc stmt)
  (let ((hstmt (db-stmt-bind-binary hdbc stmt)))
    (display (string-append "\nDynamic statement : " stmt "\n"))
    (if (statement-handle? hstmt)
        (begin
          ; (db-stmt-param-bind hdbc hstmt 0 "SQL_INTEGER" 4 0)
          ; (db-stmt-param-bind hdbc hstmt 1 "SQL_VARCHAR" 20 0)
          ; (db-stmt-param-bind hdbc hstmt 2 "SQL_VARCHAR" 10 0)
          ; (db-stmt-param-bind hdbc hstmt 3 "SQL_INTEGER" 38 0)
          ; (db-stmt-param-bind hdbc hstmt 4 "SQL_INTEGER" 38 0)
          ; (db-stmt-param-bind hdbc hstmt 5 "SQL_INTEGER" 10 0)
          (db-stmt-param-bind hdbc hstmt 6 "SQL_LONGVARIABLE"
2000000 0)
          (define prm-count (db-stmt-param-count hdbc hstmt))
          (display-stmt-parameter-property hdbc hstmt prm-count)

          (define col-count (db-stmt-column-count hdbc hstmt))
          (display-stmt-column-property hdbc hstmt col-count)
        )
        (display (db-get-error-str hdbc)))
    )
  hstmt
)

(define image1-id "7100")
(define image1-name "Coast")
(define image1-type "JPEG")
(define image1-width "1280")
(define image1-height "1024")
(define image1-file (string-append image1-name ".jpg"))

(define image-port (open-input-file image1-file))
(define image1-data (read image-port 1000000))
(close-port image-port)
(define image1-size (number->string (string-length image1-data)))

(define image2-id "7200")
(define image2-name "Launch")
(define image2-type "JPEG")
(define image2-width "2000")
(define image2-height "1600")
(define image2-file (string-append image2-name ".jpg"))

(define image-port (open-input-file image2-file))
(define image2-data (read image-port 2000000))
(close-port image-port)
(define image2-size (number->string (string-length image2-data)))

(define hdbc (make-connection-handle))
(display (connection-handle? hdbc)) (newline)

(define stmt0 "select count(0) from SCOTT.IMAGE where PIX_ID = ?")
(define stmt1 "insert into SCOTT.IMAGE (PIX_ID, PIX_NAME, PIX_TYPE,
BYTE_SIZE, PIX_WIDTH, PIX_HEIGHT, PIX_DATA) values (?, ?, ?, ?, ?, ?,
?)")

(if (db-login hdbc dsname uid pwd)
    (begin
      (display "\ndatabase login succeed !\n")
      (display (db-dbms hdbc)) (newline)
    )
  )

```

```

(display (db-std-timestamp-format hdbc)) (newline)
(display (db-max-long-data-size hdbc 2000000)) (newline)

; bind the query and insert statement
(define hquery (bind-statement hdbc stmt0))
(define hinsert (bind-image-statement hdbc stmt1))

(if (and
    (statement-handle? hquery)
    (statement-handle? hinsert)
)
    (begin
        (if (not (query-exist hdbc hquery image1-id))
            (begin
                (display (string-append "insert image " image1-file "\n"))
                (if (and
                    (db-stmt-param-assign hdbc hinsert 0 image1-id)
                    (db-stmt-param-assign hdbc hinsert 1 image1-name)
                    (db-stmt-param-assign hdbc hinsert 2 image1-type)
                    (db-stmt-param-assign hdbc hinsert 3 image1-size)
                    (db-stmt-param-assign hdbc hinsert 4 image1-width)
                    (db-stmt-param-assign hdbc hinsert 5 image1-height)
                    (db-stmt-param-assign hdbc hinsert 6 image1-data)
                )
                    (if (execute-statement hdbc hinsert)
                        (db-commit hdbc)
                        (display (db-get-error-str hdbc)))
                    (display (db-get-error-str hdbc)))
                )
            )
        )
    )

    (if (not (query-exist hdbc hquery image2-id))
        (begin
            (display (string-append "insert image " image2-file "\n"))
            (if (and
                (db-stmt-param-assign hdbc hinsert 0 image2-id)
                (db-stmt-param-assign hdbc hinsert 1 image2-name)
                (db-stmt-param-assign hdbc hinsert 2 image2-type)
                (db-stmt-param-assign hdbc hinsert 3 image2-size)
                (db-stmt-param-assign hdbc hinsert 4 image2-width)
                (db-stmt-param-assign hdbc hinsert 5 image2-height)
                (db-stmt-param-assign hdbc hinsert 6 image2-data)
            )
                (if (execute-statement hdbc hinsert)
                    (db-commit hdbc)
                    (display (db-get-error-str hdbc)))
                (display (db-get-error-str hdbc)))
            )
        )
    )

    (if (not (db-logout hdbc))
        (display (db-get-error-str hdbc))
    )
)
(display (db-get-error-str hdbc))
)

```

7.5.8 Retrieving an Image from a Database

This sample shows how to Retrieve an image from a Database. It uses both Static and Dynamic SQL functions. See the *e*Way Intelligent Adapter for ODBC User's Guide* for more details.

```
;demo-image-select.monk

; load Monk database extension
(load "demo-init.monk")
(load "demo-common.monk")

(define (get-image hdbc hstmt)
  (do (
    (result (db-stmt-fetch hdbc hstmt) (db-stmt-fetch hdbc
hstmt))
      (first_name "")
      (file_type "")
      (file_name "")
      (width "")
      (height "")
      (output_port '())
    )
    ((boolean? result) result)
    (set! first_name (vector-ref result 0))
    (set! file_type (strip-trailing-whitespace (vector-ref result
1)))
    (set! width (strip-trailing-whitespace (vector-ref result 2)))
    (set! height (strip-trailing-whitespace (vector-ref result 3)))
    (cond
      ((string=? file_type "JPEG") (set! file_name (string-append
first_name ".jpg")))
      ((string=? file_type "GIF") (set! file_name (string-append
first_name ".gif")))
      ((string=? file_type "BITMAP") (set! file_name (string-append
first_name ".bmp")))
      ((string=? file_type "TIFF") (set! file_name (string-append
first_name ".tif")))
      (else (set! file_name (string-append first_name ".raw")))
    )
    (if (file-exists? file_name)
      (file-delete file_name)
    )
    (display (string-append "picture name = " file_name "\n"))
    (display (string-append "picture size = " width " x " height
"\n\n"))
    (set! output_port (open-output-file file_name))
    (display (vector-ref result 4) output_port)
    (close-port output_port)
  )
)

(define (execute-statement hdbc hstmt)
  (let ((col-count (db-stmt-column-count hdbc hstmt)) (row-count 0))
    (if (db-stmt-execute hdbc hstmt)
      (begin
        (if (> col-count 0)
          (if (not (get-image hdbc hstmt))
            (display (db-get-error-str hdbc))
          )
        )
        (set! row-count (db-stmt-row-count hdbc hstmt))
        (if (boolean? row-count)

```

```

                (display (db-get-error-str hdbc))
                (display (string-append "number of image retrieved = "
(number->string row-count) "\n"))
            )
            (newline)
            #t
        )
        #f
    )
)

(define hdbc (make-connection-handle))
(display (connection-handle? hdbc)) (newline)

(define stmt "select PIX_NAME, PIX_TYPE, PIX_WIDTH, PIX_HEIGHT,
PIX_DATA from SCOTT.IMAGE where PIX_ID = ?")

(if (db-login hdbc dsn uid pwd)
    (begin
        (display "\ndatabase login succeed !\n")
        (display (db-dbms hdbc)) (newline)
        (display (db-std-timestamp-format hdbc)) (newline)
        (display (db-max-long-data-size hdbc 2000000)) (newline)

        ; bind the select statement
        (define hselect (bind-binary-statement hdbc stmt))

        ; execute the dynamic statement
        (display "select IMAGE table\n")
        (if (statement-handle? hselect)
            (begin
                (if (db-stmt-param-assign hdbc hselect 0 "7100")
                    (if (not (execute-statement hdbc hselect))
                        (display (db-get-error-str hdbc))
                    )
                    (display (db-get-error-str hdbc))
                )
                (if (db-stmt-param-assign hdbc hselect 0 "7200")
                    (if (not (execute-statement hdbc hselect))
                        (display (db-get-error-str hdbc))
                    )
                    (display (db-get-error-str hdbc))
                )
            )
        )
        (if (not (db-logout hdbc))
            (display (db-get-error-str hdbc))
        )
    )
    (display (db-get-error-str hdbc))
)

```

7.5.9 Common Supporting Routines

This sample script displays and defines values and parameters for stored procedures. The routines contained in this script are used by many of the Monk samples in this chapter. For more details about functions used in this script, see the *e*Way Intelligent Adapter for ODBC User's Guide* for more details.

```

;demo-common.monk

;;
;; stored procedure auxiliary functions
;;

; display parameter properties of the stored procedure
(define (display-proc-parameter-property hdbc hstmt prm-count)
  (display "parameter count = ") (display prm-count) (newline)
  (do ((i 0 (+ i 1))) ((= i prm-count))
    (display "parameter ")
    (display (db-proc-param-name hdbc hstmt i))
    (display ": type = ")
    (display (db-proc-param-type hdbc hstmt i))
    (display ", io = ")
    (display (db-proc-param-io hdbc hstmt i))
    (newline)
  )
)

; display value of output parameters from stored procedure
(define (display-proc-parameter-output-value hdbc hstmt prm-count)
  (do ((i 0 (+ i 1))) ((= i prm-count))
    (if (not (equal? (db-proc-param-io hdbc hstmt i) "IN"))
      (begin
        (display "output parameter ")
        (display (db-proc-param-name hdbc hstmt i))
        (display " = ")
        (display (db-proc-param-value hdbc hstmt i))
        (newline)
      )
    )
  )
)

; display column properties of the return result set
(define (display-proc-column-property hdbc hstmt col-count)
  (display "column count = ") (display col-count) (newline)
  (do ((i 0 (+ i 1))) ((= i col-count))
    (display "column ")
    (display (db-proc-column-name hdbc hstmt i))
    (display ": type = ")
    (display (db-proc-column-type hdbc hstmt i))
    (newline)
  )
  (newline)
)

; display column value of the return result set of the stored
procedure
(define (display-proc-column-value hdbc hstmt col-count)
  (define (fetch-next)
    (let ((result (db-proc-fetch hdbc hstmt)))
      (if (boolean? result)
        result
        (begin (display result) (newline) (fetch-next)))
    )
  )
)

```



```

    )
  )
  (fetch-next)
  (newline)
)

; bind stored procedure and display parameter properties
(define (bind-procedure hdbc proc)
  (let ((hstmt (db-proc-bind hdbc proc)))
    (if (statement-handle? hstmt)
        (begin
          (display (string-append "bind stored procedure : " proc
"\n"))
          (define prm-count (db-proc-param-count hdbc hstmt))
          (display-proc-parameter-property hdbc hstmt prm-count)
          (newline)
          (if (db-proc-return-exist hdbc hstmt)
              (begin
                (display "return: type = ")
                (display (db-proc-return-type hdbc hstmt))
                (newline)
              )
            )
          (newline)
        )
        (display (db-get-error-str hdbc)))
    hstmt
  )
)

;;
;; dynamic statement auxiliary functions
;;

; display parameter properties of the SQL statement
(define (display-stmt-parameter-property hdbc hstmt prm-count)
  (display "parameter count = ") (display prm-count) (newline)
  (do ((i 0 (+ i 1))) ((= i prm-count))
    (display "parameter #")
    (display i)
    (display ": type = ")
    (display (db-stmt-param-type hdbc hstmt i))
    (newline)
  )
  (newline)
)

; display column properties of the SQL statement
(define (display-stmt-column-property hdbc hstmt col-count)
  (display "column count = ") (display col-count) (newline)
  (do ((i 0 (+ i 1))) ((= i col-count))
    (display "column ")
    (display (db-stmt-column-name hdbc hstmt i))
    (display ": type = ")
    (display (db-stmt-column-type hdbc hstmt i))
    (newline)
  )
  (newline)
)

```

```

; display column value of the return result set of the SQL statement
(define (display-stmt-column-value hdbc hstmt)
  (define (fetch-next)
    (let ((result (db-stmt-fetch hdbc hstmt)))
      (if (boolean? result)
          result
          (begin (display result) (newline) (fetch-next)))
      )
    )
  (fetch-next)
  (newline)
)

; display row count affected by the execution of the SQL statement
(define (display-stmt-row-count hdbc hstmt)
  (let ((row-count (db-stmt-row-count hdbc hstmt)))
    (cond
      ((= row-count 0) (display "\n(no row affected)\n"))
      ((= row-count 1) (display "\n(1 row affected)\n"))
      (else (display (string-append "\n(" (number->string row-
count) " rows affected)\n")))
    )
  )
)

; bind dynamic statement and display paramters and column properties
(define (bind-statement hdbc stmt)
  (let ((hstmt (db-stmt-bind hdbc stmt)))
    (display (string-append "\nDynamic statement : " stmt "\n"))
    (if (statement-handle? hstmt)
        (begin
          (define prm-count (db-stmt-param-count hdbc hstmt))
          (display-stmt-parameter-property hdbc hstmt prm-count)

          (define col-count (db-stmt-column-count hdbc hstmt))
          (display-stmt-column-property hdbc hstmt col-count)
        )
        (display (db-get-error-str hdbc))
    )
    hstmt
  )
)

; bind dynamic statement to input/output raw binary data
(define (bind-binary-statement hdbc stmt)
  (let ((hstmt (db-stmt-bind-binary hdbc stmt)))
    (display (string-append "\nDynamic statement : " stmt "\n"))
    (if (statement-handle? hstmt)
        (begin
          (define prm-count (db-stmt-param-count hdbc hstmt))
          (display-stmt-parameter-property hdbc hstmt prm-count)

          (define col-count (db-stmt-column-count hdbc hstmt))
          (display-stmt-column-property hdbc hstmt col-count)
        )
        (display (db-get-error-str hdbc))
    )
    hstmt
  )
)

```

Index

A

Action on Malformed Command parameter 95
 Additional Path parameter 83
 Assigning ETDs to Event Types 37
 Autorun 17
 Auxiliary Library Directories parameter 84

B

Base64 92
 Batch e*Way Functions 98–104
 batch mode interface
 operational overview 56
 outbound from PeopleSoft 58
 batch-ack function 98
 batch-exchange-data function 99
 batch-ext-connect function 99
 batch-ext-shutdown function 100
 batch-ext-verify function 100
 batch-init function 101
 batch-nak function 101
 batch-proc-out function 102
 batch-shutdown-notify function 103
 batch-startup function 104
 Build tool 33

C

calling stored procedures, sample 130
 Changing the User Name 49
 Collaboration 38, 53, 54, 68
 Rules 38, 68
 Rules Editor 68
 common supporting routines, sample 144
 Communication Setup 79–82
 Components, e*Way 14
 configuration
 Communication Setup 79–82
 Dynamic Configuration 92–96
 General Settings 77–78
 Monk Configuration 83–91
 configuration parameters
 Action on Malformed Command 95
 Additional Path 83

Auxiliary Library Directories 84
 Down Timeout 81
 Enable Message Configuration 92
 Exchange Data Interval 79
 Exchange Data With External Function 86
 Exchange-if-in-window-on-startup 82
 External Connection Establishment Function 87
 External Connection Shutdown Function 88
 External Connection Verification Function 88
 Forward External Errors 78
 Include Order Record in Error Record 95
 Include Payload in Error Record 95
 Journal File Name 77
 Max Failed Messages 77
 Max Resends Per Message 77
 Monk Environment Initialization File 84
 Negative Acknowledgment Function 90
 Positive Acknowledgement Function 89
 Process Outgoing Message Function 85
 Publish Status Record on Error 95
 Publish Status Record on Success 94
 Resend Timeout 81
 Shutdown Command Notification Function 91
 Start Exchange Data Schedule 80
 Startup Function 85
 Stop Exchange Data Schedule 81
 Up Timeout 81
 Zero Wait Between Successful Exchanges 79
 configuration procedures 45
 continue on error 57
 conventions, writing in document 9
 Creating an e*Way 43

D

db-stdver-conn-estab function 105
 db-stdver-conn-shutdown function 107
 db-stdver-conn-ver function 107
 db-stdver-data-exchg function 109
 db-stdver-data-exchg-stub function 109
 db-stdver-init function 110
 db-stdver-neg-ack function 110
 db-stdver-pos-ack function 111
 db-stdver-proc-outgoing function 112
 db-stdver-proc-outgoing-stub function 113
 db-stdver-shutdown function 114
 db-stdver-startup function 115
 deleting records, sample 138
 Document Type Definition (DTD) 124
 Down Timeout parameter 81
 Dynamic Configuration 92–96

E

- e*Gate to PeopleSoft operation 12, 55
- e*Way
 - Components 14
 - Configuration 45
 - creating 43
 - Installation 17
 - Properties 44
 - Schedules 49
 - Startup Options 49
 - troubleshooting 53
- e*Way Operation
 - e*Gate to PeopleSoft 12, 55
 - PeopleSoft to e*Gate 13, 58
- EBCDIC 16
- Editor
 - Collaboration Rules 68
 - ETD 33
- Enable Message Configuration parameter 92
- Enterprise Manager 30
- error reporting 63
- ETD Editor 33
- Event Type 37
- Event Type Definition (ETD) 37
- event-commit-to-egate function 117
- event-rollback-to-egate function 118
- Events 67
- event-send-to-egate function 118
- event-send-to-egate-ignore-shutdown function 119
- event-send-to-egate-no-commit function 119
- Exchange Data Interval parameter 79
- Exchange Data with External Function parameter 86
- Exchange-if-in-window-on-startup parameter 82
- External Connection Establishment Function parameter 87
- External Connection Shutdown Function parameter 88
- External Connection Verification Function parameter 88

F

- Forward External Errors parameter 78
- functions (see also functions, Monk)
 - Batch e*Way 98–104
 - Generic 117–123
 - ODBC e*Way 105–116
- functions, Monk
 - batch-ack 98
 - batch-exchange-data 99
 - batch-ext-connect 99
 - batch-ext-shutdown 100
 - batch-ext-verify 100

- batch-init 101
- batch-nak 101
- batch-proc-out 102
- batch-shutdown-notify 103
- batch-startup 104
- db-stdver-conn-estab 105
- db-stdver-conn-shutdown 107
- db-stdver-conn-ver 107
- db-stdver-data-exchg 109
- db-stdver-data-exchg-stub 109
- db-stdver-init 110
- db-stdver-neg-ack 110
- db-stdver-pos-ack 111
- db-stdver-proc-outgoing 112
- db-stdver-proc-outgoing-stub 113
- db-stdver-shutdown 114
- db-stdver-startup 115
- event-commit-to-egate 117
- event-rollback-to-egate 118
- event-send-to-egate 118
- event-send-to-egate-ignore-shutdown 119
- event-send-to-egate-no-commit 119
- get-logical-name 120
- insert-exchange-data-event 120
- send-external down 121
- send-external-up 121
- shutdown-request 122
- start-schedule 122
- stop-schedule 123
- waiting-to-shutdown 123

G

- General Settings 77–78
- Generic e*Way Functions 117–123
- get-logical-name function 120

I

- Include Order Record in Error Record parameter 95
- Include Payload in Error Record parameter 95
- initializing Monk extensions, sample 129
- insert-exchange-data-event function 120
- inserting records, sample 132
- Installation procedure
 - e*Way (UNIX) 22
 - e*Way (Windows) 17
 - sample schema 26
- InstallShield 17
- Intelligent Queue (IQ) 39, 53, 58

J

Journal File Name parameter 77

L

Load Path, Monk 83
logging options 51

M

Max Failed Messages parameter 77
Max Resends Per Message parameter 77
monitoring thresholds 52
Monk Configuration 83–91
 Load Path 83
 Specifying File Names 83
 Specifying Function Names 83
 Specifying Multiple Directories 83
Monk Environment Initialization File parameter 84

N

Negative Acknowledgment Function parameter 90

O

ODBC e*Way Functions 105–116
operational overview 56, 58
OS/390 16
outbound batch mode interface 58
outbound from PeopleSoft 58

P

parameters - see configuration parameters
Participating Host 53
PeopleSoft to e*Gate operation 13, 58
Positive Acknowledgment Function parameter 89
procedures
 configuration 45
 installation 17
Process Outgoing Message Function parameter 85
processing
 continue on error 57
 rollback on error 57
 stop on error 57
Properties, e*Way 44
Publish Status Record on Error parameter 95
Publish Status Record on Success parameter 94

Q

Queues 39

R

Receiving Data with a Receive Order 61
remote function call (RFC) 14, 58
Resend Timeout parameter 81
rollback on error 57

S

sample
 calling stored procedures 130
 common routines 144
 common supporting routines 144
 deleting records with dynamic SQL statements 138
 dynamic SQL statements 132, 134, 136, 138
 initializing Monk extensions 129
 inserting binary images 139
 inserting records with dynamic SQL statements 132
 retrieving images 142
 selecting records with dynamic SQL statements 136
 stored procedures 130
 updating records with dynamic SQL statements 134
sample schema
 descriptions 39
 installation 26
Schedules 49
selecting records, sample 136
send-external-down function 121
send-external-up function 121
Setting Startup Options or Schedules 49
Shutdown Command Notification Function parameter 91
shutdown-request function 122
SOCKS
 description 16
Start Exchange Data Schedule parameter 80
start-schedule function 122
Startup Function parameter 85
Startup Options 49
Stop Exchange Data Schedule parameter 81
stop on error 57
stop-schedule function 123
stored procedures, sample 130
supported variable SQL datatypes 66

T

troubleshooting the e*Way 53

U

UNIX installation procedure 22
Up Timeout parameter 81
updating records, sample 134
User name 49
Using the e*Gate Enterprise Manager 30

W

waiting-to-shutdown function 123
Windows installation procedure 17

X

XML 60

Z

Zero Wait Between Successful Exchanges parameter
79