



Sun Cluster 3.1 Data Service for DHCP Guide

Sun Microsystems, Inc.
4150 Network Circle
Santa Clara, CA 95054
U.S.A.

Part No: 817-3328-10
October 2003, Revision A

Copyright 2003 Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, CA 95054 U.S.A. All rights reserved.

This product or document is protected by copyright and distributed under licenses restricting its use, copying, distribution, and decompilation. No part of this product or document may be reproduced in any form by any means without prior written authorization of Sun and its licensors, if any. Third-party software, including font technology, is copyrighted and licensed from Sun suppliers.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, docs.sun.com, AnswerBook, AnswerBook2, and Solaris are trademarks, registered trademarks, or service marks of Sun Microsystems, Inc. in the U.S. and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc.

The OPEN LOOK and Sun™ Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

Federal Acquisitions: Commercial Software—Government Users Subject to Standard License Terms and Conditions.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright 2003 Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, CA 95054 U.S.A. Tous droits réservés.

Ce produit ou document est protégé par un copyright et distribué avec des licences qui en restreignent l'utilisation, la copie, la distribution, et la décompilation. Aucune partie de ce produit ou document ne peut être reproduite sous aucune forme, par quelque moyen que ce soit, sans l'autorisation préalable et écrite de Sun et de ses bailleurs de licence, s'il y en a. Le logiciel détenu par des tiers, et qui comprend la technologie relative aux polices de caractères, est protégé par un copyright et licencié par des fournisseurs de Sun.

Des parties de ce produit pourront être dérivées du système Berkeley BSD licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, docs.sun.com, AnswerBook, AnswerBook2, et Solaris sont des marques de fabrique ou des marques déposées, ou marques de service, de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays. Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

L'interface d'utilisation graphique OPEN LOOK et Sun™ a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciés de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui en outre se conforment aux licences écrites de Sun.

CETTE PUBLICATION EST FOURNIE "EN L'ETAT" ET AUCUNE GARANTIE, EXPRESSE OU IMPLICITE, N'EST ACCORDEE, Y COMPRIS DES GARANTIES CONCERNANT LA VALEUR MARCHANDE, L'APTITUDE DE LA PUBLICATION A REpondre A UNE UTILISATION PARTICULIERE, OU LE FAIT QU'ELLE NE SOIT PAS CONTREFAISANTE DE PRODUIT DE TIERS. CE DENI DE GARANTIE NE S'APPLIQUERAIT PAS, DANS LA MESURE OU IL SERAIT TENU JURIDIQUEMENT NUL ET NON AVENU.



030731@5943



Contents

Installing and Configuring Sun Cluster HA for DHCP	5
Installing and Configuring Sun Cluster HA for DHCP	5
Sun Cluster HA for DHCP Overview	6
Planning the Sun Cluster HA for DHCP Installation and Configuration	6
Configuration Restrictions	6
Configuration Requirements	7
Installing and Configuring DHCP	9
How to Install and Configure DHCP	10
Verifying the Installation and Configuration of DHCP	11
▼ How to Verify the Installation and Configuration of DHCP	11
Installing the Sun Cluster HA for DHCP Packages	12
How to Install the Sun Cluster HA for DHCP Packages by Using the Web Start Program	12
▼ How to Install the Sun Cluster HA for DHCP Packages by using the <code>scinstall</code> utility	13
Registering and Configuring Sun Cluster HA for DHCP	14
▼ How to Register and Configure Sun Cluster HA for DHCP	14
Verifying the Sun Cluster HA for DHCP Installation and Configuration	16
▼ How to Verify the Sun Cluster HA for DHCP Installation and Configuration	16
Understanding Sun Cluster HA for DHCP Fault Monitor	16
Resource Properties	17
Probing Algorithm and Functionality	17
Debug Sun Cluster HA for DHCP	17
▼ How to turn debug on for Sun Cluster HA for DHCP	17

Installing and Configuring Sun Cluster HA for DHCP

Installing and Configuring Sun Cluster HA for DHCP

Table 1-1 lists the tasks for installing and configuring Sun Cluster HA for DHCP. Perform these tasks in the order that they are listed.

TABLE 1-1 Task Map: Installing and Configuring Sun Cluster HA for DHCP

Task	For Instructions, Go To
Plan the installation	"Planning the Sun Cluster HA for DHCP Installation and Configuration" on page 6
Install and configure DHCP	"How to Install and Configure DHCP" on page 10
Verify installation and configuration	"How to Verify the Installation and Configuration of DHCP" on page 11
Install Sun Cluster HA for DHCP Packages	"How to Install the Sun Cluster HA for DHCP Packages by using the <code>scinstall</code> utility" on page 13
Register and Configure Sun Cluster HA for DHCP	"How to Register and Configure Sun Cluster HA for DHCP" on page 14
Verify Sun Cluster HA for DHCP Installation and Configuration	"How to Verify the Sun Cluster HA for DHCP Installation and Configuration" on page 16
Understand Sun Cluster HA for DHCP fault monitor	"Understanding Sun Cluster HA for DHCP Fault Monitor" on page 16
Debug Sun Cluster HA for DHCP	"How to turn debug on for Sun Cluster HA for DHCP " on page 17

Sun Cluster HA for DHCP Overview

Solaris DHCP provides dynamic TCP/IP configuration to a DHCP client. The Sun Cluster HA for DHCP data service uses the DHCP software that is bundled with Solaris 8/9. For further information on DHCP refer to the `dhcp(4)` man page.

The Sun Cluster HA for DHCP data service provides a mechanism for orderly startup and shutdown, fault monitoring and automatic failover of the DHCP service. The following DHCP component is protected by the Sun Cluster HA for DHCP data service.

TABLE 1-2 Protection of Components

Component	Protected by
DHCP server	Sun Cluster HA for DHCP

Planning the Sun Cluster HA for DHCP Installation and Configuration

This section contains the information you need to plan your Sun Cluster HA for DHCP installation and configuration.

Configuration Restrictions



Caution – Your data service configuration might not be supported if you do not observe these restrictions.

Consider the restrictions in this section to plan the installation and configuration of Sun Cluster HA for DHCP. This section provides a list of software and hardware configuration restrictions that apply to Sun Cluster HA for DHCP only.

For restrictions that apply to all data services, see the *Sun Cluster Release Notes*.

- **The Sun Cluster HA for DHCP data service can only be configured as a failover service** – DHCP cannot operate as a scalable service and therefore the Sun Cluster HA for DHCP data service can only be configured to run as a failover service.

- **DHCP server** – DHCP has to operate as a DHCP server and not as a relay host.
- **DHCP single instance** – Only one DHCP resource can be configured within Sun Cluster.
- **DHCP network table** – The DHCP network table can be text or binary files and can be mounted as either a Failover File System (FFS) or a Global File System (GFS).

Note – It is considered best practice when mounting Global File Systems to mount them with the /global prefix and to mount Failover File Systems with the /local prefix. However, be aware that this is simply viewed as best practice.

Configuration Requirements



Caution – Your data service configuration might not be supported if you do not adhere to these requirements.

Use the requirements in this section to plan the installation and configuration of Sun Cluster HA for DHCP. These requirements apply to Sun Cluster HA for DHCP only. You must meet these requirements before you proceed with your Sun Cluster HA for DHCP installation and configuration.

- **DHCP component and its dependencies** —The Sun Cluster HA for DHCP data service can be configured to protect a DHCP component. This component and its dependencies are briefly described below.

TABLE 1-3 DHCP components and their dependencies (via → symbol)

Componet	Description
DHCP server (Mandatory)	→ <i>SUNW.HAStoragePlus</i> resource The <i>SUNW.HAStoragePlus</i> resource manages the DHCP File System Mount points and ensures that DHCP is not started until these are mounted.

The DHCP component has a configuration and registration file under `/opt/SUNWscdhc/util`. These files allow you to register the DHCP components with Sun Cluster.

EXAMPLE 1-1 DHCP configuration and registration file for Sun Cluster

```
# cd /opt/SUNWscdhc
#
# ls -l util/*
```

EXAMPLE 1-1 DHCP configuration and registration file for Sun Cluster (Continued)

```
total 6
-rwxr-xr-x  1 root    sys      1094 Dec 20 14:44 dhcp_config
-rwxr-xr-x  1 root    sys       514 Dec 20 14:44 dhcp_register
#
# more util/*
:::::::::::::
util/dhcp_config
:::::::::::::
#
# Copyright 2003 Sun Microsystems, Inc. All rights reserved.
# Use is subject to license terms.
#
# This file will be sourced in by dhcp_register and the parameters
# listed below will be used.
#
# These parameters can be customized in (key=value) form
#
#     RS - name of the resource for the application
#     RG - name of the resource group containing RS
#     PORT - name of any port number
#     LH - name of the LogicalHostname SC resource
#     NETWORK - name of the DHCP Network, however comprised of following
#               <network>@<nafo_or_nodename>@<node number>
#     HAS_RS - name of the DHCP HASStoragePlus SC resource
#
#     The following two examples illustrate sample parameters
#     for DHCP on a 2 node cluster (tequila/sunrise)
#
#     Sun Cluster 3.0 using nafo
#
#     NETWORK=192.168.100.0@nafo0@1/192.168.100.0@nafo0@2
#
#     Sun Cluster 3.1 using ipmp
#
#     NETWORK=192.168.100.0@tequila@1/192.168.100.0@sunrise@2
#
RS=
RG=
PORT=
LH=
NETWORK=
HAS_RS=
:::::::::::::
util/dhcp_register
:::::::::::::
#
# Copyright 2003 Sun Microsystems, Inc. All rights reserved.
# Use is subject to license terms.
#
. `dirname $0`/dhcp_config
```


EXAMPLE 1-1 DHCP configuration and registration file for Sun Cluster (Continued)

```
scrgadm -a -j $RS -g $RG -t SUNW.gds \  
-x Start_command="/opt/SUNWscdhc/bin/start_dhcp \  
-R $RS -G $RG -N $NETWORK " \  
-x Stop_command="/opt/SUNWscdhc/bin/stop_dhcp \  
-R $RS -G $RG -N $NETWORK " \  
-x Probe_command="/opt/SUNWscdhc/bin/probe_dhcp \  
-R $RS -G $RG -N $NETWORK " \  
-y Port_list=$PORT/tcp -y Network_resources_used=$LH \  
-x Stop_signal=9 \  
-y Resource_dependencies=$HAS_RS \  
#
```

- **Sun Cluster HA for DHCP data service** – requires Solaris 8 7/01 (or later) with patches 109077-07 (or later) and 111302-01 (or later) or Solaris 9.
- **/etc/inet/dhcpsvc.conf parameters** – The following `/etc/inet/dhcpsvc.conf` parameters have to be set.
 - **DAEMON_ENABLED** should always be true
 - **PATH** should point to the Cluster File System for the DHCP network table
 - **RUN_MODE** should always be `SERVER`
 - **RESOURCE** is set to either `SUNWbinfiles` or `SUNWfiles`
The following parameter in `etc/inet/dhcpsvc.conf` cannot be set
 - **INTERFACE**

Note – Ensure that `/etc/inet/dhcpsvc.conf` is consistent on all nodes within Sun Cluster that will host the DHCP service, or is linked on a directory on a Cluster File System.

Note – With respect to responses to DHCP requests, `SUNWbinfiles` should be used for the DHCP network table to achieve the best DHCP performance.

Installing and Configuring DHCP

This section contains the procedures you need to install and configure DHCP.

How to Install and Configure DHCP

Use this procedure to install and configure DHCP.

1. **Install the following packages from the Solaris CD**
 - SUNWdhcsu
 - SUNWdhcsb
 - SUNWdhcm
2. **Mount DHCP Cluster File Systems** – You must ensure that the Cluster File System for the DHCP network table is mounted.

Note – If a Failover File System is used by the DHCP network table, you must mount this manually.

3. **Install the required DHCP patches** — Refer back to the “Configuration Requirements” on page 7 for a list of patches that need to be installed.
4. **Run the following commands to configure DHCP** –

```
# /usr/sadm/admin/bin/dhcpmgr
```

- Choose Configure as DHCP Server
 - Choose Text files or Binary files
 - Enter a path for the DHCP network table
 - Choose which name services should be used to store host records
 - Choose Length of Lease and if clients can renew their leases
 - If used, supply a DNS configuration for the DHCP client of this server
 - Add which network and network mask should provide ip-addresses
 - Choose LAN as Network Type
 - If used, supply a NIS configuration for the DHCP clients of this server
 - If used, supply a NIS+ configuration for the DHCP clients of this server
 - Create your addresses and macros
5. **Check /etc/inet/dhcpsvc.conf** – has the following parameters defined.
 - **DAEMON_ENABLED** should always be true
 - **PATH** should point to a Cluster File System
 - **RUN_MODE** should always be SERVER
 - **RESOURCE** is set to either SUNWbinfiles or SUNWfiles
 6. **Make sure /etc/inet/dhcpsvc.conf is consistent** – on all nodes within Sun Cluster that will host the DHCP service
This can be done by either
 - Copying /etc/inet/dhcpsvc.conf onto each node with Sun Cluster
 - Move your edited dhcpsvc.conf to your Cluster File System and create a symbolic link from /etc/inet/dhcpsvc.conf to dhcpsvc.conf within the Cluster File System.

7. **Ensure that DHCP is stopped on all nodes**

```
# /etc/rc2.d/K21dhcp stop
```

8. **Disable DHCP startup on boot on all nodes**

```
# rm /etc/rc3.d/S34dhcp
```

Verifying the Installation and Configuration of DHCP

This section contains the procedure you need to verify the installation and configuration.

▼ How to Verify the Installation and Configuration of DHCP

Use this procedure to verify the installation and configuration. This procedure does not verify that your application is highly available because you have not installed your data service yet.

1. **Check /etc/inet/dhcpsvc.conf**

Ensure that the parameters are set accordingly to your requirements

- SERVER_MODE
- PATH
- DAEMON_ENABLED

2. **Check /etc/inet/dhcpsvc.conf is consistent on all nodes within Sun Cluster**

3. **Check that DHCP startup on boot has been disabled**

Installing the Sun Cluster HA for DHCP Packages

If you did not install the Sun Cluster HA for DHCP packages during your initial Sun Cluster installation, perform this procedure to install the packages. Perform this procedure on each cluster node where you are installing the Sun Cluster HA for DHCP packages. To complete this procedure, you need the Sun Cluster Agents CD-ROM.

If you are installing more than one data service simultaneously, perform the procedure in “Installing the Software” in *Sun Cluster 3.1 10/03 Software Installation Guide*.

Install the Sun Cluster HA for DHCP packages by using one of the following installation tools:

- The Web Start program
- The `scinstall` utility

Note – The Web Start program is *not* available in releases earlier than Sun Cluster 3.1 Data Services 10/03.

How to Install the Sun Cluster HA for DHCP Packages by Using the Web Start Program

You can run the Web Start program with a command-line interface (CLI) or with a graphical user interface (GUI). The content and sequence of instructions in the CLI and the GUI are similar. For more information about the Web Start program, see the `installer(1M)` man page.

1. **On the cluster node where you are installing the Sun Cluster HA for DHCP packages, become superuser.**
2. **(Optional) If you intend to run the Web Start program with a GUI, ensure that your `DISPLAY` environment variable is set.**
3. **Load the Sun Cluster Agents CD-ROM into the CD-ROM drive.**
If the Volume Management daemon `vold(1M)` is running and configured to manage CD-ROM devices, it automatically mounts the CD-ROM on the `/cdrom/scdataservices_3_1_vb` directory.
4. **Change to the Sun Cluster HA for DHCP component directory of the CD-ROM.**

The Web Start program for the Sun Cluster HA for DHCP data service resides in this directory.

```
# cd /cdrom/scdataservices_3_1_vb/components/SunCluster_HA_DHCP_3.1
```

5. Start the Web Start program.

```
# ./installer
```

6. When you are prompted, select the type of installation.

- To install only the C locale, select Typical.
- To install other locales, select Custom.

7. Follow instructions on the screen to install the Sun Cluster HA for DHCP packages on the node.

After the installation is finished, the Web Start program provides an installation summary. This summary enables you to view logs that the Web Start program created during the installation. These logs are located in the `/var/sadm/install/logs` directory.

8. Exit the Web Start program.

9. Unload the Sun Cluster Agents CD-ROM from the CD-ROM drive.

- a. To ensure that the CD-ROM is not being used, change to a directory that does *not* reside on the CD-ROM.
- b. Eject the CD-ROM.

```
# eject cdrom
```

▼ How to Install the Sun Cluster HA for DHCP Packages by using the `scinstall` utility

Use this procedure to install the Sun Cluster HA for DHCP packages by using the `scinstall` utility. You need the Sun Cluster Agents CD-ROM to perform this procedure. This procedure assumes that you did not install the data service packages during your initial Sun Cluster installation.

If you installed the Sun Cluster HA for DHCP packages as part of your initial Sun Cluster installation, proceed to “Registering and Configuring Sun Cluster HA for DHCP” on page 14.

Otherwise, use this procedure to install the Sun Cluster HA for DHCP packages. Perform this procedure on all nodes that can run Sun Cluster HA for DHCP.

- 1. Load the Sun Cluster Agents CD-ROM into the CD-ROM drive.**
- 2. Run the `scinstall` utility with no options.**

This step starts the `scinstall` utility in interactive mode.

3. Choose the menu option, Add Support for New Data Service to This Cluster Node.

The `scinstall` utility prompts you for additional information.

4. Provide the path to the Sun Cluster Agents CD-ROM.

The utility refers to the CD as the “data services cd.”

5. Specify the data service to install.

The `scinstall` utility lists the data service that you selected and asks you to confirm your choice.

6. Exit the `scinstall` utility.

7. Unload the CD from the drive.

Registering and Configuring Sun Cluster HA for DHCP

This section contains the procedures you need to configure Sun Cluster HA for DHCP.

▼ How to Register and Configure Sun Cluster HA for DHCP

Use this procedure to configure Sun Cluster HA for DHCP as a failover data service. This procedure assumes that you installed the data service packages during your initial Sun Cluster installation.

If you did not install the Sun Cluster HA for DHCP packages as part of your initial Sun Cluster installation, go to “How to Install the Sun Cluster HA for DHCP Packages by using the `scinstall` utility” on page 13.

Otherwise, use this procedure to configure the Sun Cluster HA for DHCP data service.

1. Become superuser on one of the nodes in the cluster that will host DHCP.

2. Register the `SUNW.gds` resource type.

```
# scrgadm -a -t SUNW.gds
```

3. Register the `SUNW.HAStoragePlus` resource type.

```
# scrgadm -a -t SUNW.HAStoragePlus
```

4. Create a failover resource group .

```
# scrgadm -a -g DHCP-failover-resource-group
```

5. Create a resource for the DHCP Disk Storage.

```
# scrgadm -a -j DHCP-has-resource \  
-g DHCP-failover-resource-group \  
-t SUNW.HAStoragePlus \  
-x FilesystemMountPoints=DHCP- instance-mount-points
```

6. Create a resource for the DHCP Logical Hostname.

```
# scrgadm -a -L -j DHCP-lh-resource \  
-g DHCP-failover-resource-group \  
-l DHCP-logical-hostname
```

7. Enable the failover resource group that now includes the DHCP Disk Storage and Logical Hostname resources.

```
# scswitch -z -g DHCP-failover-resource-group
```

8. Create and register the DHCP component.

```
# cd /opt/SUNWscdhc/util
```

Edit the dhcp_configfile and follow the comments within that file, i.e.

```
# These parameters can be customized in (key=value) form  
# RS - name of the resource for the application  
# RG - name of the resource group containing RS  
# PORT - name of any port number, as it's ignored  
# LH - name of the LogicalHostname SC resource  
# NETWORK - name of the DHCP Network, however comprised of following  
# <network>@<nafo or nodename>@<node number>  
# HAS_RS - name of the DHCP HAStoragePlus SC resource
```

The following is an example for DHCP for a 2 node (tequila/sunrise) Sun Cluster 3.1 with IPMP.

```
RS=dhcp-res  
RG=dhcp-rg  
PORT=23  
LH=dhcp-lh-res  
NETWORK=192.168.100.0@tequila@1/192.168.100.0@sunrise@2  
HAS_RS=dhcp-has-res
```

After editing dhcp_config you must now register the resource.

```
# ./dhcp_register
```

9. Enable each DHCP resource.

Repeat this step for each DHCP component as in the previous step.

```
# scstat
```

```
# scswitch -e -j DHCP-resource
```

Verifying the Sun Cluster HA for DHCP Installation and Configuration

This section contains the procedure you need to verify that you installed and configured your data service correctly.

▼ How to Verify the Sun Cluster HA for DHCP Installation and Configuration

Use this procedure to verify that you installed and configured Sun Cluster HA for DHCP correctly.

1. **Become superuser on one of the nodes in the cluster that will host DHCP.**
2. **Ensure all the DHCP resources are online with `scstat`.**

```
# scstat
```

For each DHCP resource that is not online, use the `scswitch` command as follows.

```
# scswitch -e -j DHCP-resource
```

3. **Run the `scswitch` command to switch the DHCP resource group to another cluster node, such as `node2`.**

```
# scswitch -z -g DHCP-failover-resource-group -h node2
```

Understanding Sun Cluster HA for DHCP Fault Monitor

Use the information in this section to understand Sun Cluster HA for DHCP fault monitor. This section describes the Sun Cluster HA for DHCP fault monitor's probing algorithm or functionality, states the conditions, messages, and recovery actions associated with unsuccessful probing.

For conceptual information on fault monitors, see the *Sun Cluster Concepts Guide*.

Resource Properties

Sun Cluster HA for DHCP fault monitor uses the same resource properties as resource type `SUNW.gds`. Refer to the `SUNW.gds(5)` man page for a complete list of resource properties used.

Probing Algorithm and Functionality

- **DHCP**
 - Sleeps for `Thorough_probe_interval`
 - Checks that the `in.dhcpd` daemon is still running. If this fails then the probe will restart the DHCP resource.
 - Checks if PNM (Public Network Monitoring) or IPMP (IP Multi Pathing) has changed the active interface for the network that DHCP is using. If this fails then the probe will restart the DHCP resource.

Debug Sun Cluster HA for DHCP

▼ How to turn debug on for Sun Cluster HA for DHCP

Use the information in this section to understand how to turn on debug for Sun Cluster HA for DHCP.

The DHCP component has a `DEBUG` file under `/opt/SUNWscdhc/etc`.

This file allows you to turn debug on for the DHCP resource on a particular node within Sun Cluster. If you require debug to be turned on for the DHCP resource across the whole Sun Cluster, you will need to repeat this step on all nodes within Sun Cluster.

1. Edit `/etc/syslog.conf`

Edit `/etc/syslog.conf` and change `daemon.notice` to `daemon.debug`

```
# grep daemon /etc/syslog.conf
*.err;kern.debug;daemon.notice;mail.crit      /var/adm/messages
*.alert;kern.err;daemon.err                  operator
#
```

Change the `daemon.notice` to `daemon.debug` and restart `syslogd`. Note that the output below, from the command `grep daemon /etc/syslog.conf`, shows that `daemon.debug` has now been set.

```
# grep daemon /etc/syslog.conf
*.err;kern.debug;daemon.debug;mail.crit      /var/adm/messages
*.alert;kern.err;daemon.err                  operator
#
# pkill -1 syslogd
#
```

2. Edit `/opt/SUNWscdhc/etc/config`

Edit `/opt/SUNWscdhc/etc/config` and change `DEBUG=` to `DEBUG=ALL` or `DEBUG=resource`

```
# cat /opt/SUNWscdhc/etc/config
#
# Copyright 2003 Sun Microsystems, Inc. All rights reserved.
# Use is subject to license terms.
#
# Usage:
#     DEBUG=<RESOURCE_NAME> or ALL
#
DEBUG=ALL
#
```

Note – To turn off debug, simply reverse the steps above.

Index

C

- C locale, 13
- Command
 - dhcp_register command, 15
 - dhcprm command, 10
 - scinstall, 14
 - scrgadm command, 14
 - scswitch, 16
- Configuratation, Restrictions, 6
- Configuration
 - dhcp_config file, 15
 - dhcpsvc.conf file, 9
 - Registering Sun Cluster HA for DHCP, 14
 - Requirements, 7
 - Verification, 11

D

- Debugging, How to turn debug on for Sun Cluster HA for DHCP, 17
- Dhcp, 6

F

- Fault monitoring
 - Probing Algorithm and Functionality, 17
 - Resource properties, 17
 - Understanding the faultmonitoring, 16
- files, installation logs, 13

I

- Installation
 - Install DHCP, 9
 - Sun Cluster HA for DHCP Packages on SC3.1, 13
- installing
 - Sun Cluster HA for DHCP
 - by using Web Start program, 12
 - log files created, 13

L

- locales, 13
- log files, installation, 13

R

- Resource Types
 - SUNW.gds resource type, 14
 - SUNW.StoragePlus resource type, 14

V

- /var/sadm/install/logs directory, 13

W

- Web Start program, 12

