



Sun Cluster Data Service for Agfa IMPAX Guide for Solaris OS

SPARC Platform Edition Alpha

Sun Microsystems, Inc.
4150 Network Circle
Santa Clara, CA 95054
U.S.A.

Part No: 819-1250
September 2004, Revision A

Sun Proprietary/Confidential: Need to Know

Copyright 2005 Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, CA 95054 U.S.A. All rights reserved.

This product or document is protected by copyright and distributed under licenses restricting its use, copying, distribution, and decompilation. No part of this product or document may be reproduced in any form by any means without prior written authorization of Sun and its licensors, if any. Third-party software, including font technology, is copyrighted and licensed from Sun suppliers.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, docs.sun.com, AnswerBook, AnswerBook2, and Solaris are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc.

The OPEN LOOK and Sun™ Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

U.S. Government Rights – Commercial software. Government users are subject to the Sun Microsystems, Inc. standard license agreement and applicable provisions of the FAR and its supplements.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright 2005 Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, CA 95054 U.S.A. Tous droits réservés.

Ce produit ou document est protégé par un copyright et distribué avec des licences qui en restreignent l'utilisation, la copie, la distribution, et la décompilation. Aucune partie de ce produit ou document ne peut être reproduite sous aucune forme, par quelque moyen que ce soit, sans l'autorisation préalable et écrite de Sun et de ses bailleurs de licence, s'il y en a. Le logiciel détenu par des tiers, et qui comprend la technologie relative aux polices de caractères, est protégé par un copyright et licencié par des fournisseurs de Sun.

Des parties de ce produit pourront être dérivées du système Berkeley BSD licenciés par l'Université de Californie. UNIX est une marque déposée aux États-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, docs.sun.com, AnswerBook, AnswerBook2, et Solaris sont des marques de fabrique ou des marques déposées, de Sun Microsystems, Inc. aux États-Unis et dans d'autres pays. Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux États-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

L'interface d'utilisation graphique OPEN LOOK et Sun™ a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciés de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui en outre se conforment aux licences écrites de Sun.

CETTE PUBLICATION EST FOURNIE "EN L'ETAT" ET AUCUNE GARANTIE, EXPRESSE OU IMPLICITE, N'EST ACCORDEE, Y COMPRIS DES GARANTIES CONCERNANT LA VALEUR MARCHANDE, L'APTITUDE DE LA PUBLICATION A REpondre A UNE UTILISATION PARTICULIERE, OU LE FAIT QU'ELLE NE SOIT PAS CONTREFAISANTE DE PRODUIT DE TIERS. CE DENI DE GARANTIE NE S'APPLIQUERAIT PAS, DANS LA MESURE OU IL SERAIT TENU JURIDIQUEMENT NUL ET NON AVENU.



050509@11223



Sun Proprietary/Confidential: Need to Know

Contents

Preface 5

Installing and Configuring Sun Cluster HA for Agfa IMPAX 11

Sun Cluster HA for Agfa IMPAX Overview 11

Overview of Installing and Configuring Sun Cluster HA for Agfa IMPAX 12

Planning the Sun Cluster HA for Agfa IMPAX Installation and Configuration 13

Configuration Restrictions 13

Configuration Requirements 14

Configuration Planning Questions 15

Enabling Agfa IMPAX to Run in a Cluster 15

▼ How to Enable Agfa IMPAX to Run in a Cluster 15

Installing the Sun Cluster HA for Agfa IMPAX Packages 16

▼ How to Install the Sun Cluster HA for Agfa IMPAX Packages by Using the Web Start Program 17

▼ How to Install the Sun Cluster HA for Agfa IMPAX Packages by Using the `scinstall` Utility 18

Configuring Sun Cluster HA for Oracle to Support Sun Cluster HA for Agfa IMPAX 19

Registering and Configuring Sun Cluster HA for Agfa IMPAX 20

▼ How to Register and Configure Sun Cluster HA for Agfa IMPAX as a Failover Data Service 20

Verifying the Sun Cluster HA for Agfa IMPAX Installation and Configuration 22

▼ How to Verify the Sun Cluster HA for Agfa IMPAX Installation and Configuration as a Failover Data Service 22

Index 23

Preface

Sun Cluster Data Service for Agfa IMPAX Guide for Solaris OS explains how to install and configure Sun™ Cluster HA for Agfa IMPAX.

This document is intended for system administrators with extensive knowledge of Sun software and hardware. Do not use this document as a planning or presales guide. Before reading this document, you should have already determined your system requirements and purchased the appropriate equipment and software.

The instructions in this document assume knowledge of the Solaris™ Operating System and expertise with the volume manager software that is used with Sun Cluster.

UNIX Commands

This document contains information about commands that are specific to installing and configuring Sun Cluster data services. The document does *not* contain comprehensive information about basic UNIX® commands and procedures, such as shutting down the system, booting the system, and configuring devices. Information about basic UNIX commands and procedures is available from the following sources:

- Online documentation for the Solaris Operating System
- Solaris Operating System man pages
- Other software documentation that you received with your system

Typographic Conventions

The following table describes the typographic changes that are used in this book.

TABLE P-1 Typographic Conventions

Typeface or Symbol	Meaning	Example
AaBbCc123	The names of commands, files, and directories, and onscreen computer output	Edit your <code>.login</code> file. Use <code>ls -a</code> to list all files. <code>machine_name%</code> you have mail.
AaBbCc123	What you type, contrasted with onscreen computer output	<code>machine_name%</code> su Password:
<i>AaBbCc123</i>	Command-line placeholder: replace with a real name or value	The command to remove a file is <code>rm filename</code> .
<i>AaBbCc123</i>	Book titles, new terms, and terms to be emphasized	Read Chapter 6 in the <i>User's Guide</i> . Perform a <i>patch analysis</i> . Do <i>not</i> save the file. [Note that some emphasized items appear bold online.]

Shell Prompts in Command Examples

The following table shows the default system prompt and superuser prompt for the C shell, Bourne shell, and Korn shell.

TABLE P-2 Shell Prompts

Shell	Prompt
C shell prompt	<code>machine_name%</code>
C shell superuser prompt	<code>machine_name#</code>
Bourne shell and Korn shell prompt	<code>\$</code>

TABLE P-2 Shell Prompts (Continued)

Shell	Prompt
Bourne shell and Korn shell superuser prompt	#

Related Documentation

Information about related Sun Cluster topics is available in the documentation that is listed in the following table. All Sun Cluster documentation is available at <http://docs.sun.com>.

Topic	Documentation
Data service administration	<i>Sun Cluster Data Services Planning and Administration Guide for Solaris OS</i> Individual data service guides
Concepts	<i>Sun Cluster Concepts Guide for Solaris OS</i>
Overview	<i>Sun Cluster Overview for Solaris OS</i>
Software installation	<i>Sun Cluster Software Installation Guide for Solaris OS</i>
System administration	<i>Sun Cluster System Administration Guide for Solaris OS</i>
Hardware administration	<i>Sun Cluster 3.0-3.1 Hardware Administration Manual for Solaris OS</i> Individual hardware administration guides
Data service development	<i>Sun Cluster Data Services Developer's Guide for Solaris OS</i>
Error messages	<i>Sun Cluster Error Messages Guide for Solaris OS</i>
Command and function reference	<i>Sun Cluster Reference Manual for Solaris OS</i>

For a complete list of Sun Cluster documentation, see the release notes for your release of Sun Cluster at <http://docs.sun.com>.

Related Third-Party Web Site References

Third-party URLs that are referenced in this document provide additional related information.

Note – Sun is not responsible for the availability of third-party web sites mentioned in this document. Sun does not endorse and is not responsible or liable for any content, advertising, products, or other materials that are available on or through such sites or resources. Sun will not be responsible or liable for any actual or alleged damage or loss caused or alleged to be caused by or in connection with use of or reliance on any such content, goods, or services that are available on or through such sites or resources.

Accessing Sun Documentation Online

The docs.sun.comSM Web site enables you to access Sun technical documentation online. You can browse the docs.sun.com archive or search for a specific book title or subject. The URL is <http://docs.sun.com>.

Ordering Sun Documentation

Sun Microsystems offers select product documentation in print. For a list of documents and how to order them, see “Buy printed documentation” at <http://docs.sun.com>.

Product Training

Sun Microsystems offers training in many Sun technologies through a variety of instructor-led courses and self-paced courses. For information about the training courses that Sun offers and to enroll in a class, visit Sun Microsystems Training at <http://training.sun.com/>.

Getting Help

If you have problems installing or using Sun Cluster, contact your service provider and provide the following information:

- Your name and email address (if available)
- Your company name, address, and phone number
- The model and serial numbers of your systems
- The release number of the Solaris Operating System (for example, Solaris 8)
- The release number of Sun Cluster (for example, Sun Cluster 3.0)

Use the following commands to gather information about each node on your system for your service provider.

Command	Function
<code>prtconf -v</code>	Displays the size of the system memory and reports information about peripheral devices
<code>psrinfo -v</code>	Displays information about processors
<code>showrev -p</code>	Reports which patches are installed
<code>SPARCprtdiag -v</code>	Displays system diagnostic information
<code>scinstall -pv</code>	Displays Sun Cluster release and package version information

Also have available the contents of the `/var/adm/messages` file.

Installing and Configuring Sun Cluster HA for Agfa IMPAX

This chapter explains how to install and configure Sun Cluster HA for Agfa IMPAX.

This chapter contains the following sections.

- “Sun Cluster HA for Agfa IMPAX Overview” on page 11
- “Overview of Installing and Configuring Sun Cluster HA for Agfa IMPAX” on page 12
- “Planning the Sun Cluster HA for Agfa IMPAX Installation and Configuration” on page 13
- “Enabling Agfa IMPAX to Run in a Cluster” on page 15
- “Installing the Sun Cluster HA for Agfa IMPAX Packages” on page 16
- “Configuring Sun Cluster HA for Oracle to Support Sun Cluster HA for Agfa IMPAX” on page 19
- “Registering and Configuring Sun Cluster HA for Agfa IMPAX” on page 20
- “Verifying the Sun Cluster HA for Agfa IMPAX Installation and Configuration” on page 22

Sun Cluster HA for Agfa IMPAX Overview

To eliminate single points of failure in an IMPAX system, Sun Cluster HA for Agfa IMPAX provides automatic failover for the IMPAX application. Sun Cluster HA for Agfa IMPAX is a failover data service.

For conceptual information about failover data services, see the *Sun Cluster Concepts Guide for Solaris OS*.

Sun Cluster HA for Agfa IMPAX requires an Oracle database made available by Sun Cluster HA for Oracle. Sun Cluster HA for Agfa IMPAX provides fault monitoring for the database only. Configure the database resource so that it does not attempt a local restart of the database.

Each component of the Agfa IMPAX service has a data service that protects the component when the component is configured in Sun Cluster. See the following table.

TABLE 1 Protection of Agfa IMPAX Components by Sun Cluster Data Services

Agfa IMPAX Component	Data Service
Oracle database	Sun Cluster HA for Oracle
Agfa IMPAX	Sun Cluster HA for Agfa IMPAX
NFS file system	Sun Cluster HA for NFS

Overview of Installing and Configuring Sun Cluster HA for Agfa IMPAX

The following table summarizes the tasks for installing and configuring Sun Cluster HA for Agfa IMPAX and provides cross-references to detailed instructions for performing these tasks. Perform the tasks in the order that they are listed in the table.

TABLE 2 Tasks for Installing and Configuring Sun Cluster HA for Agfa IMPAX

Task	Instructions
Plan the Agfa IMPAX installation.	Your Agfa documentation and a consultant from Agfa. <i>Sun Cluster Data Services Planning and Administration Guide for Solaris OS</i> "Planning the Sun Cluster HA for Agfa IMPAX Installation and Configuration" on page 13
Install and configure Agfa IMPAX.	A consultant from Agfa always installs the IMPAX software.
Enable Agfa IMPAX to run in a cluster.	"How to Enable Agfa IMPAX to Run in a Cluster" on page 15

TABLE 2 Tasks for Installing and Configuring Sun Cluster HA for Agfa IMPAX
(Continued)

Task	Instructions
Install the Sun Cluster HA for Agfa IMPAX packages, together with the HA for Oracle packages.	"Installing the Sun Cluster HA for Agfa IMPAX Packages" on page 16
Register the Sun Cluster HA for Oracle data service and configure the cluster for the data service.	"Configuring Sun Cluster HA for Oracle to Support Sun Cluster HA for Agfa IMPAX" on page 19
Register the Sun Cluster HA for Agfa IMPAX data service and configure the cluster for the data service.	"Registering and Configuring Sun Cluster HA for Agfa IMPAX" on page 20
Verify the Sun Cluster HA for Agfa IMPAX installation and configuration.	"Verifying the Sun Cluster HA for Agfa IMPAX Installation and Configuration" on page 22

Planning the Sun Cluster HA for Agfa IMPAX Installation and Configuration

This section contains the information that you need to plan your Sun Cluster HA for Agfa IMPAX installation and configuration.

Note – Before you begin, refer to your Agfa IMPAX documentation and consult your Agfa consultant for configuration restrictions and requirements that are not imposed by Sun Cluster software.

Configuration Restrictions

The configuration restrictions in this section apply only to Sun Cluster HA for Agfa IMPAX.



Caution – If your data service configuration does not conform to these restrictions, the data service configuration might not be supported.

For restrictions that apply to all data services, see the *Sun Cluster Data Services Planning and Administration Guide for Solaris OS*.

Connections between the database and Agfa IMPAX are not resilient. To ensure integrity, do not configure Oracle for a local failover. Instead, use Sun Cluster's capacity to fail over to another cluster node.

For performance reasons, install the database files on a highly available local file system. Do not install database files on the cluster file system. The resulting degraded performance could affect the functionality of not only the IMPAX application, but also of the connected modalities and viewing stations.

Configuration Requirements

The configuration requirements in this section apply only to Sun Cluster HA for Agfa IMPAX.



Caution – If your data service configuration does not satisfy these requirements, the data service configuration might not be supported.

For requirements that apply to all data services, see “Configuration Guidelines for Sun Cluster Data Services” in *Sun Cluster Data Services Planning and Administration Guide for Solaris OS*.

Installation Requirements

Agfa IMPAX must be installed according to the installation notes that are supplied by Agfa for your specific version of Agfa IMPAX. A consultant from Agfa always installs the Agfa IMPAX software. This is a requirement for the cluster to be supported by Agfa and by Sun.

Dependency on Sun Cluster HA for Oracle

Sun Cluster HA for Agfa IMPAX depends on the Sun Cluster HA for Oracle data service and uses an `HASStoragePlus` resource to synchronize startup of this database resource. When your Agfa engineer installs the Agfa IMPAX software, the engineer also installs the Oracle software. “[Configuring Sun Cluster HA for Oracle to Support Sun Cluster HA for Agfa IMPAX](#)” on page 19 contains details about the requirements for configuring Sun Cluster HA for Oracle.

Additional Libraries

Sun Cluster HA for Agfa IMPAX requires the libraries that are provided in the `/opt/SUNWscpax/impaxapp/util/` directory. These libraries enable the IMPAX application to be used in a cluster. Additionally, some scripts must be replaced in the installation. The Agfa documentation contains the details about these scripts.

Configuration Planning Questions

Use the questions in this section to plan the installation and configuration of Sun Cluster HA for Agfa IMPAX. Write the answers to these questions in the space that is provided on the data service worksheets in “Configuration Worksheets” in *Sun Cluster Data Services Planning and Administration Guide for Solaris OS*.

- Which resource groups will you use for the Sun Cluster HA for Agfa IMPAX application resource and the logical hostname resource?
- What is the logical hostname for the Sun Cluster HA for Agfa IMPAX resource? Clients access the data service through this logical hostname.
- Where will the system configuration files reside?

See “Configuration Guidelines for Sun Cluster Data Services” in *Sun Cluster Data Services Planning and Administration Guide for Solaris OS* for the advantages and disadvantages of using the local file system instead of the cluster file system.

Enabling Agfa IMPAX to Run in a Cluster

Before you begin, contact your Agfa consultant to install the Agfa IMPAX application. Your consultant installs and configures Oracle at the same time as installing the IMPAX software.

▼ How to Enable Agfa IMPAX to Run in a Cluster

- Steps**
1. Become superuser on one cluster node.
 2. Create a resource group for the IMPAX resource.

```
# scrgadm -a -g impax-rg
```

impax-rg The name of the resource group you are adding

Note – You add the Oracle resources to this group. See “[Configuring Sun Cluster HA for Oracle to Support Sun Cluster HA for Agfa IMPAX](#)” on page 19 for more information.

3. If necessary, add an entry to `/etc/hosts` for each node on which Agfa IMPAX can run.

```
# Echo "address host" >>/etc/hosts
```

address The IP address of the node

host The host name, which is the name of the IMPAX service

4. Add a logical host name resource to the resource group that you created in [Step 2](#).

```
# scrgadm -a -L -g impax-rg -l hostname
```

impax-rg The resource group

hostname A logical host name. use the IMPAX service name.

5. Bring online the resource group that you created in [Step 2](#).

```
# scswitch -Z -g impax-rg
```

Installing the Sun Cluster HA for Agfa IMPAX Packages

If you did not install the Sun Cluster HA for Agfa IMPAX packages during your initial Sun Cluster installation, perform this procedure to install the packages. Perform this procedure on each cluster node where you are installing the Sun Cluster HA for Agfa IMPAX packages. To complete this procedure, you need the Sun Java Enterprise System Accessory CD Volume 3.

If you are installing more than one data service simultaneously, perform the procedure in "Installing the Software" in *Sun Cluster Software Installation Guide for Solaris OS*.

Install the Sun Cluster HA for Agfa IMPAX packages by using one of the following installation tools:

- The Web Start program
- The `scinstall` utility

Note – The Web Start program is *not* available in releases earlier than Sun Cluster 3.1 Data Services 10/03.

▼ How to Install the Sun Cluster HA for Agfa IMPAX Packages by Using the Web Start Program

You can run the Web Start program with a command-line interface (CLI) or with a graphical user interface (GUI). The content and sequence of instructions in the CLI and the GUI are similar. For more information about the Web Start program, see the `installer(1M)` man page.

- Steps**
- 1. On the cluster node where you are installing the Sun Cluster HA for Agfa IMPAX packages, become superuser.**
 - 2. (Optional) If you intend to run the Web Start program with a GUI, ensure that your `DISPLAY` environment variable is set.**
 - 3. Insert the Sun Java Enterprise System Accessory CD Volume 3 into the CD-ROM drive.**

If the Volume Management daemon `vold(1M)` is running and configured to manage CD-ROM devices, it automatically mounts the CD-ROM on the `/cdrom/cdrom0` directory.
 - 4. Change to the Sun Cluster HA for Agfa IMPAX component directory of the CD-ROM.**

The Web Start program for the Sun Cluster HA for Agfa IMPAX data service resides in this directory.

```
# cd /cdrom/cdrom0/components/SunCluster_HA_AGFA_IMPAX_3.1
```
 - 5. Start the Web Start program.**

```
# ./installer
```
 - 6. When you are prompted, select the type of installation.**
 - To install only the C locale, select Typical.
 - To install other locales, select Custom.
 - 7. Follow the instructions on the screen to install the Sun Cluster HA for Agfa IMPAX packages on the node.**

After the installation is finished, the Web Start program provides an installation summary. This summary enables you to view logs that the Web Start program created during the installation. These logs are located in the `/var/sadm/install/logs` directory.
 - 8. Exit the Web Start program.**
 - 9. Remove the Sun Java Enterprise System Accessory CD Volume 3 from the CD-ROM drive.**

- a. To ensure that the CD-ROM is not being used, change to a directory that does *not* reside on the CD-ROM.
- b. Eject the CD-ROM.

```
# eject cdrom
```

Next Steps Go to “[Registering and Configuring Sun Cluster HA for Agfa IMPAX](#)” on page 20.

▼ How to Install the Sun Cluster HA for Agfa IMPAX Packages by Using the `scinstall` Utility

Perform this procedure on all of the cluster members that can master Sun Cluster HA for Agfa IMPAX.

Before You Begin Ensure that you have the Sun Java Enterprise System Accessory CD Volume 3.

- Steps**
1. Load the Sun Java Enterprise System Accessory CD Volume 3 into the CD-ROM drive.
 2. Run the `scinstall` utility with no options.
This step starts the `scinstall` utility in interactive mode.
 3. Select the menu option, Add Support for New Data Service to This Cluster Node.
The `scinstall` utility prompts you for additional information.
 4. Provide the path to the Sun Java Enterprise System Accessory CD Volume 3.
The utility refers to the CD as the “data services cd.”
 5. Specify the data service to install.
The `scinstall` utility lists the data service that you selected and asks you to confirm your choice.
 6. Exit the `scinstall` utility.
 7. Unload the CD from the drive.

Next Steps Go to “[Registering and Configuring Sun Cluster HA for Agfa IMPAX](#)” on page 20.

Configuring Sun Cluster HA for Oracle to Support Sun Cluster HA for Agfa IMPAX

Sun Cluster HA for Agfa IMPAX depends on a highly available Oracle database. When configuring Sun Cluster HA for Oracle to support Agfa IMPAX, add the Oracle server resource and the Oracle listener resource to the same resource group that you created for the IMPAX service. For details about how to install, configure, and register resources for Sun Cluster HA for Oracle, refer to *Sun Cluster Data Service for Oracle Guide for Solaris OS*.

In addition to registering the resources, add the oramon user to Oracle and allow it to probe the database.

EXAMPLE 1 Registering Sun Cluster HA for Oracle Resources

The following example assumes that you created a resource group called `impax-rg` for the IMPAX data service.

```
# scrgadm -a -j oralnsr-rs -t SUNW.oracle_listener -g impax-rg\  
-x ORACLE_HOME=/global/export/oracle -x LISTENER_NAME=LISTNRname
```

EXAMPLE 2 Adding an Oracle Server Resource to the IMPAX Resource Group

The following example assumes that you created a resource group called `impax-rg` for the IMPAX data service.

```
# scrgadm -a -j oraserver-rs -t SUNW.oracle_server -g impax-rg \  
-t SUNW.oracle_server -x CONNECT_STRING=oramon/monitor -x ORACLE_SID=oraSID \  
-x ORACLE_HOME=/global/export/oracle \  
-x ALERT_LOG_FILE=/global/export/oracle/admin/oraSID/bdump/alert_oraSID.log
```

EXAMPLE 3 Configuring the oramon User

The following example illustrates the necessary oramon configuration.

```
su - mvf  
    sqlplus "/ as sysdba"  
grant connect, resource to oramon identified by "monitor";  
alter user oramon default tablespace system quota 1m on system;  
grant select on v_$sysstat to oramon;  
grant create session to oramon;  
grant create table to oramon;  
exit;
```

Registering and Configuring Sun Cluster HA for Agfa IMPAX

To enable Sun Cluster HA for Agfa IMPAX to make Agfa IMPAX highly available, configure the Sun Cluster HA for Agfa IMPAX data service as a failover data service.

Before you perform this procedure, ensure that the Sun Cluster HA for Agfa IMPAX data service packages are installed. Perform all the steps in “How to Install the Sun Cluster HA for Agfa IMPAX Packages by Using the Web Start Program” on page 17 or “How to Install the Sun Cluster HA for Agfa IMPAX Packages by Using the `scinstall` Utility” on page 18.

▼ How to Register and Configure Sun Cluster HA for Agfa IMPAX as a Failover Data Service

Steps 1. Add an `impaxscripts` resource.

This resource allows Sun Cluster to perform certain tasks before Oracle starts and to clean up afterward if necessary.

a. Edit the registration configuration file

`/opt/SUNWscpax/impaxscripts/util/impaxscripts_config` and change the resource and resource group names according to your configuration.

The following shows the contents of the `impaxscripts_config` file. If they are appropriate to your configuration, you can use the default values for RS and RG.

```
# These parameters can be customized in (key=value) form
#
#          RS - name of the resource for the application
#          RG - name of the resource group containing RS
#          PORT - name of the port number
#          LH - name of the LogicalHostname SC resource
#          HAS_RS - name of the HAStoragePlus SC resource
#
RS=impaxscripts-rs
RG=impax-rg
PORT=
LH=
HAS_RS=
```

- b. Verify that the `/opt/SUNWscpax/impaxscripts/etc/config` configuration file contains the correct variable settings.

These variables are provided by the Agfa IMPAX installation. They should read as follows:

```
USERID=mvf
# default userid for impax installations
CLEANKILL="/usr/mvf/bin/sun_cluster_impax_kill"
ORACLEPRE="/usr/mvf/bin/sun_cluster_oracle_prestart"
```

- c. Create the resource and register it in the cluster by gaining root access and using the `impaxscripts_register` utility.

```
# /opt/SUNWscpax/impaxscripts/util/impaxscripts_register
```

If this utility fails, return to [Step b](#) and verify that the configuration file is correct.

2. Register the `SUNW.gds` resource type.

```
# scrgadm -a -t SUNW.gds
```

3. Register the `SUNW.HAStoragePlus` resource type.

```
# scrgadm -a -j ora-ds -t SUNW.HAStoragePlus -
ora-ds    The logical name for the Oracle database
```

4. Create an `HAStoragePlus` resource for the file system on which the database files reside.

```
# scrgadm -a -j ora-ds -t SUNW.HAStoragePlus -g impax-rg \
-x FileSystemMountPoints=/dbase, /cache1
```

5. To optimize the data path, manage the global file system in the same manner as you manage the disk groups.

This approach makes the system local to the base services, although the files are available on both nodes.

```
# scrgadm -a -t SUNW.HAStoragePlus -x FileSystemMountPoints=/global/export
```

6. Edit the `/opt/SUNWscpax/impaxapp/util/impax_config` file to match the following:

- your configuration
- the name of your resource group, as specified in [Step 1](#).
- your dependencies

7. Register the resource in the cluster framework by using the `impax_register` utility.

```
# /opt/SUNWscpax/impaxapp/util/impax_register
```

Verifying the Sun Cluster HA for Agfa IMPAX Installation and Configuration

Use the service tools to verify that an Agfa IMPAX instance is available on the logical IP address.

▼ How to Verify the Sun Cluster HA for Agfa IMPAX Installation and Configuration as a Failover Data Service

- Steps**
1. **Switch the IMPAX resource to another node to verify that the stop and start methods work.**
 2. **Disable the IMPAX resource, then try to start the application manually.**
This step ensures that no cluster-related interaction fails.
 3. **Disable all resources except the logical host name resource and data service resource.**
 4. **Manually start the Agfa IMPAX application.**

Index

A

Agfa IMPAX application
installing, 15-16
protection by data services, 12-13
resource group planning, 15
Agfa IMPAX data service, *See* Sun Cluster HA
for Agfa IMPAX

C

C locale, 17
commands, node information, 9
configuring
requirements, 14
restrictions, 13-14
Sun Cluster HA for Agfa IMPAX
planning, 13-15

D

database, configuration, 14
directories, `/var/sadm/install/logs`, 17

F

fault monitoring, restrictions, 12
files
installation logs, 17
system configuration, 15

H

HASStoragePlus, 14

I

IMPAX, *See* Agfa IMPAX application
installing
Agfa IMPAX application, 15-16
Oracle, 14
Sun Cluster HA for Agfa IMPAX
by using `scinstall` utility, 18
by using Web Start program, 17-18
log files created, 17

L

libraries, required, 14
locales, 17
log files, installation, 17
logical hostnames, planning the resource group
for, 15

O

Oracle
oramon user, 19
Sun Cluster HA for Agfa IMPAX dependency
on, 14
oramon Oracle user, 19

P

- planning, for installation and configuration, 13-15
- protection, Agfa IMPAX application, 12-13
- prtconf -v command, 9
- prtdiag -v command, 9
- psrinfo -v command, 9

R

- requirements
 - configuration, 14
 - libraries, 14
- resource groups
 - logical hostname planning, 15
 - Sun Cluster HA for Agfa IMPAX planning, 15
 - Sun Cluster HA for Oracle, 19
- resources, logical hostname planning, 15
- restrictions
 - configuration, 13-14
 - fault monitoring, 12

S

- scinstall -pv command, 9
- scinstall utility, 18
- showrev -p command, 9
- Sun Cluster HA for Agfa IMPAX
 - overview, 11-12
 - configuration planning, 13-15
 - installing
 - by using scinstall utility, 18
 - by using Web Start program, 17-18
 - verifying the installation, 22
- Sun Cluster HA for Oracle, configuring, 19
- system configuration files, location, 15

T

- training, 8

V

- /var/sadm/install/logs directory, 17
- verifying, Sun Cluster HA for Agfa IMPAX installation, 22

W

- Web Start program, 17-18