

Sun Ultra 1 Series Reference Manual



THE NETWORK IS THE COMPUTER™

Sun Microsystems Computer Company
A Sun Microsystems, Inc. Business
901 San Antonio Road Palo Alto, CA 94303-4900 USA
650 960-1300
fax 650 969-9131

Part No.: 801-6189
Revision A, September 1995

Send comments about this document to: docfeedback@sun.com

1997 Sun Microsystems, Inc., 901 San Antonio Road, Palo Alto, California 94303-4900 U.S.A.

All rights reserved.

This product or document is protected by copyright and distributed under licenses restricting its use, copying, distribution, and decompilation. No part of this product or document may be reproduced in any form by any means without prior written authorization of Sun and its licensors, if any.

Portions of this product may be derived from the UNIX® system, licensed from Novell, Inc., and from the Berkeley 4.3 BSD system, licensed from the University of California. UNIX is a registered trademark in the United States and in other countries and is exclusively licensed by X/Open Company Ltd. Third-party software, including font technology in this product, is protected by copyright and licensed from Sun's suppliers. RESTRICTED RIGHTS: Use, duplication, or disclosure by the U.S. Government is subject to restrictions of FAR 52.227-14(g)(2)(6/87) and FAR 52.227-19(6/87), or DFAR 252.227-7015(b)(6/95) and DFAR 227.7202-3(a).

Sun, Sun Microsystems, the Sun logo, and Solaris are trademarks or registered trademarks of Sun Microsystems, Inc. in the United States and in other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the United States and in other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc.

The OPEN LOOK® and Sun™ Graphical User Interfaces were developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox Corporation in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a nonexclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

THIS PUBLICATION IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

Copyright 1997 Sun Microsystems, Inc., 901 San Antonio Road, Palo Alto, Californie 94303-4900 U.S.A. Tous droits réservés.

Ce produit ou document est protégé par un copyright et distribué avec des licences qui en restreignent l'utilisation, la copie et la décompilation. Aucune partie de ce produit ou de sa documentation associée ne peut être reproduite sous aucune forme, par quelque moyen que ce soit, sans l'autorisation préalable et écrite de Sun et de ses bailleurs de licence, s'il y en a.

Des parties de ce produit pourront être dérivées du système UNIX® licencié par Novell, Inc. et du système Berkeley 4.3 BSD licencié par l'Université de Californie. UNIX est une marque enregistrée aux Etats-Unis et dans d'autres pays, et licenciée exclusivement par X/Open Company Ltd. Le logiciel détenu par des tiers, et qui comprend la technologie relative aux polices de caractères, est protégé par un copyright et licencié par des fournisseurs de Sun.

Sun, Sun Microsystems, le logo Sun, et Solaris sont des marques déposées ou enregistrées de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays. Toutes les marques SPARC, utilisées sous licence, sont des marques déposées ou enregistrées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

Les utilisateurs d'interfaces graphiques OPEN LOOK® et Sun™ ont été développés de Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox Corporation pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique, cette licence couvrant aussi les licenciés de Sun qui mettent en place les utilisateurs d'interfaces graphiques OPEN LOOK et qui en outre se conforment aux licences écrites de Sun.

CETTE PUBLICATION EST FOURNIE "EN L'ETAT" SANS GARANTIE D'AUCUNE SORTE, NI EXPRESSE NI IMPLICITE, Y COMPRIS, ET SANS QUE CETTE LISTE NE SOIT LIMITATIVE, DES GARANTIES CONCERNANT LA VALEUR MARCHANDE, L'APTITUDE DES PRODUITS A REpondre A UNE UTILISATION PARTICULIERE OU LE FAIT QU'ILS NE SOIENT PAS CONTREFAISANTS DE PRODUITS DE TIERS.



Adobe PostScript

Contents

Preface vii

How This Book Is Organized vii

Related Books vii

Typographic Conventions viii

- 1. Back Panel Connectors 1-1**
 - 1.1 Connector Layout 1-1
 - 1.2 Serial Connectors 1-2
 - 1.3 Parallel Connector 1-3
 - 1.4 Keyboard/Mouse Connector 1-4
 - 1.5 Attachment Unit Interface (AUI) Connector 1-5
 - 1.6 Twisted-Pair Ethernet (TPE) Connector 1-6
 - 1.7 SCSI Connector 1-6
 - 1.7.1 SCSI Implementation 1-7
 - 1.8 Audio Ports 1-8
 - 1.9 Audio Specifications 1-9
 - 1.10 SBus Card 13W3 Video Connector 1-10

- 2. Twisted-Pair Ethernet Link Test 2-1**
 - 2.1 Overview 2-1
 - 2.2 Technical Discussion 2-4

- 2.3 Troubleshooting 2-4
- 2.4 Moves and Changes 2-5
- 2.5 Checking or Disabling the Link Test 2-5
- 2.6 Enabling the Link Test 2-6

- 3. Modem Setup Specifications 3-1**
 - 3.1 Setting Up the Modem 3-1
 - 3.2 Serial Port Speed Change 3-2
 - 3.3 Recommendations 3-3
 - 3.3.1 Cable 3-3
 - 3.3.2 Modem Switch Settings (AT Commands) 3-3

- 4. Main Logic Board Jumpers 4-1**
 - 4.1 Identifying Jumpers 4-2
 - 4.2 Flash PROM Jumpers 4-3
 - 4.3 Serial Port Jumpers 4-4

- 5. System Specifications 5-1**
 - 5.1 Power 5-1
 - 5.2 Environment 5-1
 - 5.3 Physical Specifications 5-3
 - 5.4 Memory Mapping 5-3

Figures

- FIGURE 1-1 Back Panel Switches and Connectors 1-1
- FIGURE 1-2 DB-25 Serial Connectors 1-2
- FIGURE 1-3 DB-25 Parallel Connector 1-3
- FIGURE 1-4 DIN-8 Keyboard/Mouse Connector 1-4
- FIGURE 1-5 DB-15 AUI Connector 1-5
- FIGURE 1-6 RJ-45 TPE Connector 1-6
- FIGURE 1-7 50-Pin SCSI Connector 1-6
- FIGURE 1-8 Audio Port Locations 1-8
- FIGURE 1-9 13W3 Video Connector 1-10
- FIGURE 2-1 Hosts and Hub in a Local Area Network 2-2
- FIGURE 2-2 Ensuring Host-Hub Communication 2-3
- FIGURE 4-1 Jumper Locations on the Main Logic Board 4-2
- FIGURE 4-2 Identifying Jumper Pins 4-3
- FIGURE 4-3 Ultra 1 Series, Jumper J2104 Pin Numberin 4-4

Preface

The *Sun Ultra 1 Series Reference Manual* contains useful information about the use and maintenance of a Sun™ Ultra™ 1 Series system.

How This Book Is Organized

Chapter 1, “Back Panel Connectors,” shows the location of each back panel connector and gives the pinouts for each connector.

Chapter 2, “Twisted-Pair Ethernet Link Test,” presents a full tutorial about connecting the system to a twisted-pair Ethernet local area network.

Chapter 3, “Modem Setup Specifications,” gives modem settings for Ultra 1 Series systems used in specific network telecommunication applications.

Chapter 4, “Main-Logic Board Jumpers,” gives the locations and pin definitions of user-configurable main-logic board jumpers.

Chapter 5, “Physical Specifications,” gives system requirements about power and environment, and also gives system dimension, weight, and memory mapping specifications.

Related Books

- *Sun Ultra 1 Series Hardware Setup Instructions*
- *Sun Ultra 1 Series Installation Guide*
- *Sun Ultra 1 Series Product Notes*

- *Sun Ultra 1 Series Service Manual*
- *Solaris Handbook for SMCC Peripherals*

Typographic Conventions

The following table describes the typographic changes used in this book.

TABLE P-1 Typographic Conventions

Typeface or Symbol	Meaning	Example
AaBbCc123	The names of commands, files, and directories; on-screen computer output	Edit your <code>.login</code> file. Use <code>ls -a</code> to list all files. machine_name% You have mail.
AaBbCc123	What you type, contrasted with on-screen computer output	machine_name% su Password:
<i>AaBbCc123</i>	Command-line placeholder: replace with a real name or value	To delete a file, type <code>rm filename</code> .
<i>AaBbCc123</i>	Book titles, new words or terms, or words to be emphasized	Read Chapter 6 in <i>User's Guide</i> . These are called <i>class</i> options. You <i>must</i> be root to do this.

Back Panel Connectors

1.1 Connector Layout




FIGURE 1-1 Back Panel Switches and Connectors

1.2 Serial Connectors




FIGURE 1-2 DB-25 Serial Connectors

TABLE 1-1 Serial Connector Pinouts, RS-423/RS-232

Pin	Function	I/O	Signal Description
1	none	none	Not connected
2	TxD	O	Transmit Data
3	RxD	I	Receive Data
4	RTS	O	Ready To Send
5	CTS	I	Clear To Send
6	DSR	I	Data Set Ready
7	Gnd		Signal Ground
8	DCD	I	Data Carrier Detect
9-14	none	none	Not connected
15	TRxC	I	Transmit Clock
16	none	none	Not connected
17	RTxC	I	Receive Clock
18-19	none	none	Not connected
20	DTR	O	Data Terminal Ready
21-23	none	none	Not connected
24	TxC	O	Transmit Clock
25	none	none	Not connected

1.3 Parallel Connector




FIGURE 1-3 DB-25 Parallel Connector

TABLE 1-2 Parallel Connector Pinouts

Pin	Description	Pin	Description
1	nStrobe	14	nAutoFd
2	Data[1]	15	nFault
3	Data[2]	16	nInit
4	Data[3]	17	nSelectIn
5	Data[4]	18	Signal Ground
6	Data[5]	19	Signal Ground
7	Data[6]	20	Signal Ground
8	Data[7]	21	Signal Ground
9	Data[8]	22	Signal Ground
10	nAck	23	Signal Ground
11	Busy	24	Signal Ground
12	PError	25	Signal Ground
13	Select		

1.4 Keyboard/Mouse Connector




FIGURE 1-4 DIN-8 Keyboard/Mouse Connector

TABLE 1-3 Keyboard/Mouse Connector Pinouts

Pin	Description	Pin	Description
1	Ground	5	Keyboard Out
2	Ground	6	Keyboard In
3	+5 Vdc	7	Power Key In
4	Mouse In	8	+5 Vdc

Note – All signals are standard TTL levels. The +5V supply is fuse-protected.

1.5 Attachment Unit Interface (AUI) Connector




FIGURE 1-5 DB-15 AUI Connector

TABLE 1-4 AUI Connector Pinouts

Pin	Function
1	Gnd
2	AUI_CI+
3	AUI_DO+
4	Gnd
5	AUI_DI+
6	Gnd
7	NC
8	Gnd
9	AUI_CI-
10	AUI_DO-
11	Gnd
12	AUI_DI-
13	+12 VDC
14	Gnd
15	NC

1.6 Twisted-Pair Ethernet (TPE) Connector



FIGURE 1-6 RJ-45 TPE Connector

TABLE 1-5 TPE Connector Pinouts

Pin	Description	Pin	Description
1	Transmit Data +	5	N.C.
2	Transmit Data -	6	Receive Data -
3	Receive Data +	7	N.C.
4	N.C.	8	N.C.

1.7 SCSI Connector




FIGURE 1-7 50-Pin SCSI Connector

Note – All signals shown in Table 1-6 are active low.

TABLE 1-6 SCSI Connector Pinouts

Pin	Level	Function	I/O	Description
1-25	GND	Ground		
26	TTL	sd0	I&O	SCSI Data Bit 0
27	TTL	sd1	I&O	SCSI Data Bit 1
28	TTL	sd2	I&O	SCSI Data Bit 2
29	TTL	sd3	I&O	SCSI Data Bit 3
30	TTL	sd4	I&O	SCSI Data Bit 4
31	TTL	sd5	I&O	SCSI Data Bit 5
32	TTL	sd6	I&O	SCSI Data Bit 6
33	TTL	sd7	I&O	SCSI Data Bit 7
34	TTL	sdp	I&O	SCSI Data Parity
35-37	GND	Ground		
38	TTL	Termpower	I&O	Termination Voltage
39-40	GND			
41	TTL	atn	O	Attention
42	GND	Ground		
43	TTL	bsy	O	Busy
44	TTL	ack	O	Acknowledge
45	TTL	rst	O	Reset
46	TTL	msg	O	Message
47	TTL	sel	O	Select
48	TTL	cd	O	Control/Data
49	TTL	req	O	Request
50	TTL	io	O	Input/Output

1.7.1 SCSI Implementation

- Single-ended

- 8-bit (narrow SCSI) with parity
- 10 MBytes/sec Fast SCSI
- Supports 8 SCSI addresses:
 - Target 0-6 for devices
 - Target 7 reserved for SCSI host adapter on main-logic board
- Supports up to 3 internal SCSI drives:
 - SCSI disk drive target 0 (lower drive slot)
 - SCSI disk drive target 1 (upper drive slot)
 - SCSI CD-ROM drive target 6
- External 8-bit SCSI devices supported via 50-pin SCSI connector

1.8 Audio Ports




FIGURE 1-8 Audio Port Locations

All audio ports use EIA standard 3.5-mm/0.125-inch jacks.

TABLE 1-7 Audio Port Signals

	Headphones	Line Out	Line In	Microphone
Tip	Left Channel	Left Channel	Left Channel	Left Channel
Ring (Center)	Right Channel	Right Channel	Right Channel	Right Channel
Shield	Ground	Ground	Ground	Ground

TABLE 1-8 Audio Port Functions

Port	Function
Headphones	Connects stereophonic headphones for private listening of audio output.
Line Out	Connects the system audio output to an external stereophonic amplifier and loudspeakers.
Line In	Connects external stereophonic audio sources such as a compact disc player or cassette tape player to the system.
Microphone	Connects the SunMicrophone™ II (or other suitable microphone*) to the system. *The Ultra 1 microphone port accepts stereophonic input; however, the Sun Microphone II is a monophonic device. Note also that the older SunMicrophone is not compatible with the Ultra 1 system.

1.9 Audio Specifications

The specifications in Table 1-9 assume use of the Audio Tool format setting “CD-ROM or DAT” selected.

The microphone input specifications are for the SunMicrophone II.

TABLE 1-9 Audio Inputs and Output

Stereo I/Os	Specifications
Line In	2V typical, 4V max.; 5-50 ohms impedance
Frequency Response	20 Hz-17 kHz +/- 0.5 dB
Internal CD Input	


TABLE 1-9 Audio Inputs and Output

Stereo I/Os	Specifications
Input Level	0.1 Vrms typical at 10 kOhms; 2Vpp max.
Distortion	0.01%, typical at 1 kHz
S/N Ratio	84 dB, typical IEC 179 A-weighted
Frequency Response	20 Hz-17 kHz +/- 0.5 dB
Microphone Input	15 mV typical, 0.6-1.0 kOhms impedance; +5 VDC input bias via a 2.2kOhms resistor
Headphones Output	1V typical, 2.4V max.; 16 Ohms -1kOhms impedance
Line Out	1V typical, 2.4V max.; 5-50 kOhms impedance

TABLE 1-10 Internal Monaural Speaker Specifications

Speaker	Specifications
Power Output	1.5W ave., 3W peak
Distortion	0.02%, typical at 1 kHz
Impedance	16 Ohms +/- 20%
Frequency Response	150 Hz-17 kHz +/- 0.5 dB

1.10 SBus Card 13W3 Video Connector

**FIGURE 1-9** 13W3 Video Connector

The SBus frame buffer card for your system provides the 13W3 video connector for transmitting video output signals from the system unit to the monitor.

See Table 1-11 for 13W3 video connector pinouts.

TABLE 1-11 13W3 Video Connector Pinouts

Pin	Function	I/O	Level
A1	Red	O	Analog
A2	Green	O	Analog
A3	Blue	O	Analog
1	Serial Read		TTL
2	Vert Sync	O	TTL
3	Sense <0>	I	TTL
4	Ground		GND
5	Comp Sync	O	TTL
6	Horiz Sync	O	TTL
7	Serial Write		TTL
8	Sense <1>	I	TTL
9	Sense <2>	I	TTL
10	Ground		GND

Twisted-Pair Ethernet Link Test

Read this chapter if you are connecting your Ultra 1 Series system to a twisted-pair Ethernet (TPE) network. This chapter contains important information for getting your system to communicate correctly over a TPE network. If you have no experience with TPE networks, ask your system or network administrator to perform the procedures in this chapter.

2.1 Overview

- The twisted-pair Ethernet link integrity test is a function defined by the IEEE 802.3 10BASE-T specification.
- For a networked workstation (host) to communicate with a network hub, the link test state (enabled or disabled) must be the same on the host and hub.
- If either the host or hub does not share the link test enabled/disabled state of the other, then the host cannot communicate effectively with the hub, and the hub cannot communicate effectively with the host.

FIGURE 2-1 gives an example of a star configuration local area network (LAN), showing the relationship of hosts to a hub.

FIGURE 2-2 shows the importance of ensuring that the host and hub link test settings match.




FIGURE 2-1 Hosts and Hub in a Local Area Network




FIGURE 2-2 Ensuring Host-Hub Communication

2.2 Technical Discussion

The twisted-pair Ethernet link integrity test determines the state of the twisted-pair cable link between the host and the hub in a network. Both the host and hub regularly transmit a link test pulse. When either the host or hub has not received a link test pulse within a certain amount of time (50-150 ms), it makes the transition from the link-pass state to the link-fail state and remains in the link-fail state until it once again receives regular link test pulses.

The link integrity test is specific to twisted-pair Ethernet and is not applicable to the other physical layer implementations of IEEE 802.3 such as 10BASE5 ("thicknet") or 10BASE2 ("thinnet").

The link test function at the host or hub is either enabled (link test enabled or 1) or disabled (link test disabled or 0). The IEEE 802.3 10BASE-T specification requires that the link test be enabled at both the host and the hub.

Although link test disabled does not conform to the specification, it is often encountered in real-world installations. Hubs from various vendors can exhibit any of the following:

- Link test is "hardwired" enabled—link test is always enabled.
- Link test is "hardwired" disabled—link test is always disabled.
- Link test is configurable—the network administrator may enable or disable link test.

2.3 Troubleshooting

If you have connected an Ultra 1 Series host to a hub using twisted-pair Ethernet cable and observe either "no carrier" messages or fail to communicate effectively with another host in the same network, look first at the hub. If it supports configurable link test, then make sure "link test enabled" is configured. This is usually done by setting a hardware switch.

If the hub does not support configurable link test, then refer to the hub manufacturer's documentation. Check to see if your hub is hardwired for link test disabled. If it is, you must follow the "Checking or Disabling the Link Test" procedure elsewhere in this chapter to disable the link test at your Ultra 1 Series host.

2.4 Moves and Changes

If the Ultra 1 Series host is physically moved to another network location or if the hub is reconfigured, remember to refer back to Figure 2-2. Unless the new network relationship between the host and the hub is functional (that is, 1-1 link test enabled-link test enabled or 0-0 link test disabled-link test disabled), there will be no full, regular two-way communication between the host and the hub.

2.5 Checking or Disabling the Link Test

To check the link test state of an Ultra 1 Series host:

1. If you do not see the `ok` prompt, press the **Stop (L1)-a** keys.
2. At the `ok` prompt, type:

```
ok printenv tpe-link-test?
tpe-link-test?      true           true
ok
```

The above screen shows the current link test state (true, or enabled), followed by the default state (true, or enabled).

To disable the host's link test function:

- **Type the following command:**

```
ok setenv tpe-link-test? false
tpe-link-test? =    false
ok
```

- **Boot the host and verify that the transceiver cable problem messages do not appear. Type either `boot net` or `boot disk` and press Return.**

2.6 Enabling the Link Test

1. If you do not see the `ok` prompt, press the Stop (L1)-a keys.
2. At the `ok` prompt, type:

```
ok printenv tpe-link-test?
tpe-link-test?      false           true
ok
```

The above screen shows the current link test state (false, or disabled), followed by the default state (true, or enabled).

- To enable the host's link test function, type:

```
ok setenv tpe-link-test? true
tpe-link-test? =    true
ok
```

- Boot the host and verify that the transceiver cable problem messages do not appear. Type either `boot net` or `boot disk` and press Return.

Modem Setup Specifications

3.1 Setting Up the Modem

Any modem compatible with U.S. Robotics[®] or CCITT V.24 can be connected to the Ultra 1 Series serial ports. Modems can be set up to function in one of three ways:

- Dial out only
- Dial in only
- Bidirectional Calls

To set up your modem:

- **Become root (superuser).** Type `admintool`.

```
% su
Password:
# admintool
```

1. **Highlight** `Browse`.
2. **Select** `Serial Port`.
3. **Select Port A or Port B for your modem connection.**
4. **Select** `Edit`.
5. **Select** `Expert`.
6. **Open the Use Template menu, and choose one of the following:**
 - Select Modem - Dial-Out Only

- Select Modem - Dial-In Only
- Select Modem - Bidirectional

7. **Select** `Apply`.

8. **Set your modem auto-answer switch to one of the following:**

- For Dial-Out Only, set the switch to Off
- For Dial-In Only, set the switch to On
- For Bidirectional, set the switch to On

3.2 Serial Port Speed Change

You must edit the `/etc/remote` file to change the speed of a serial port.

- **Become root (superuser), and type** `cd /etc`.

```
% su
Password:
# cd /etc
```

1. **Type** `vi remote`.

2. **Type** `tip speed device-name .`

Typical speeds are 9600, 19200 to 38400 bps.

The device name is the serial port name — for example,
`/dev/tty[a,b]` or `/dev/term/[a,b]`.

3. **Press Esc and type** `:wq` to save your file change(s) and to exit from the `vi` text editor.

3.3 Recommendations

3.3.1 Cable

For a modem-to-host (system) connection, use an RS-423/RS-232 straight-through cable with DB-25 male connectors at both ends.

3.3.2 Modem Switch Settings (AT Commands)

- Enable transmit flow control (AT&H1) [suggested setting]
(Required for sending binary/8-bit data)
- Set link rate to fixed
(Will not track modem data rate, AT&Bn; n = menu choice in modem manual.)
- Set display result codes (ATQ0)
- Set verbal result codes (ATV1)
- Set result code subset (ATXn; n = option choice)
- Save settings in NVRAM (AT&W)

Note – The above settings are guidelines to help you get started quickly. Changes to these guidelines should be expected depending on your site requirements and the modem you are using.

For additional information about modem switch settings, see the manual that came with your modem.

Main Logic Board Jumpers

Jumper settings given in this chapter refer to etchings on the main logic board. Jumpers are labeled with the letter “J” followed by a four-digit number. See Figure 4-1.




FIGURE 4-1 Jumper Locations on the Main Logic Board

4.1 Identifying Jumpers

Jumpers are marked on the main logic board with part numbers. For example, the serial port jumpers are marked J2104 and J2105. Jumper pins are located immediately adjacent to the part number. Pin 1 is marked with an asterisk in any of the positions shown. See Figure 4-2.




FIGURE 4-2 Identifying Jumper Pins

4.2 Flash PROM Jumpers

The Ultra 1 Series system uses flash PROMs. Flash PROMs permit the following:

- Reprogramming of specific code blocks
- Remote reprogramming of the PROM chip by a system administrator over a local area network

TABLE 4-1 Flash PROM Jumper Settings

Jumper	Pins 1 + 2 Select	Pins 2 + 3 Select	Default Jumper on Pins	Signal Controlled
J2002	Flash PROM	Not To Be Used	1 + 2	FLASH PROM SEL
J2003	Write Protect	Write Enable	1 + 2	FLASH PROM PROG ENABLE
J2204	High Half Booting	Normal Booting	2 + 3	XOR LOGIC SET

Note – If you are reprogramming your system flash PROM, after successful reprogramming be sure to return the flash PROM Write Protect/Enable jumper (J2003) to the Write Protect position to ensure system security.

For flash PROM reprogramming information and the function of J2204, see the *SMCC System Flash PROM Programming Guide*.

4.3 Serial Port Jumpers

The serial port jumpers on the main logic board permit configuring the two DB-25 serial ports on the system unit back panel for either RS-423 or RS-232 signal levels. RS-423 levels are the default standard for North American users. RS-232 levels are required for digital telecommunication in nations of the European Community.

TABLE 4-2 Serial Port Jumper Settings

Jumper	Pins 1 + 2 Select	Pins 2 + 3 Select	Default Shunt on Pins	Signal Controlled
J2104	RS-232	RS-423	2 + 3	RS232/RS423 SEL
J2105	RS-232	RS-423	2 + 3	RS232/RS423 SEL

Note – In an Ultra 1 Series system, jumper J2104 is not marked with an asterisk to indicate pin 1. The pins are numbered in the way shown in Figure 4-3 in relation to the J2104 marking on the main logic board.




FIGURE 4-3 Ultra 1 Series, Jumper J2104 Pin Numberin

System Specifications

5.1 Power

TABLE 5-1 Power Specifications

Input/Output	Specifications
AC Power Input	100-240 VAC nominal, 47-63 Hz.
DC Power Output	180 W maximum

5.2 Environment

The following specifications comply with the *International Electrotechnical Commission (IEC) Standards*, 5th ed., 1990-1994.

See TABLE 5-2..

TABLE 5-2 Environmental Specifications

Operating	
Altitude	0 to 3000 meters (0 to 9840 feet), 5°C to 35°C (41°F to 95°F) —IEC 68-2-40, 68-2-41
Humidity	20% to 80% Relative Humidity (RH), noncondensing —IEC 68-2-2, 68-2-3
Shock	5 gravity (g) peak, 11 milliseconds half-sine pulse —IEC 68-2-27
Vibration	0.1 g peak, 5 to 500 Hz, 3 perpendicular axes —IEC 68-2-26
Temperature	5°C to 40°C (41°F to 104°F) at 20%-70% RH noncondensing —IEC 68-2-1, 68-2-2
Nonoperating	
Altitude	0 to 12,000 meters (0 to 39,360 feet), 0°C to 10°C (32°F to 50°F) —IEC 68-2-40, 68-2-41
Humidity	95% RH, noncondensing —IEC 68-2-2, 68-2-3
Shock	30 g peak, 11 milliseconds half-sine pulse —IEC 68-2-27
Vibration	1 g peak, 5 to 500 Hz, 3 perpendicular axes —IEC 68-2-6
Temperature	-40°C to 65°C (-40°F to 149°F) at 20%-70% RH, noncondensing —IEC 68-2-1, 68-2-2

5.3 Physical Specifications

TABLE 5-3 Dimensions and Weight

Height	Width	Depth	Weight*
10.15 cm (4.00 in.)	41.7 cm (16.44 in.)	44.3 cm (17.44 in.)	12.25 kg (27.0 lb)

Note – *These weight figures are approximations for a system equipped with 2 hard disk drives, 1 CD-ROM drive, and 3 SBus cards.

TABLE 5-4 Physical Clearances

Clearance	Specification
Compact Disc/ Diskette	16.51 cm (6.5 in.)
System Unit Parallel Placement	7.6 cm (3.0 in.)*

*Physical space between two system units side by side

5.4 Memory Mapping

Single Inline Memory Modules (SIMMs) are grouped on the main logic board in banks of two slots each. SIMMs are installed in identical pairs per bank.

TABLE 5-5 Main Logic Board Memory Mapping

Bank	Slots
0	U0701 + U0601
1	U0702 + U0602
2	U0703 + U0603
3	U0704 + U0604

