

Oracle® iPlanet Web Server 7.0.9 Release Notes

Copyright © 2010, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related software documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle America, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. UNIX is a registered trademark licensed through X/Open Company, Ltd.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Contents

Oracle iPlanet Web Server 7.0.9 Release Notes	5
Features and Enhancements in Web Server 7.0.9	5
Resolution of SSL/TLS Vulnerability CVE-2009-3555	6
Support for JDT Java Compiler	6
Support for Oracle JRockit JDK	6
Ability to Change Session ID on Authentication	6
For Large Applications, <code>--directory</code> Option of <code>add-webapp</code> Command Deprecated in Favor of <code>--file-on-server</code> Option	6
Issues Resolved in Web Server 7.0.9	7
Hardware and Software Requirements	8
Supported Platforms	8
System Virtualization Support	8
Operating System Patches	8
Supported Browsers	11
Deprecation Notices	11
Installation, Migration, and Upgrade Notes	12
Installation	12
Migration	12
Upgrade	13
Known Issues	14
Administration	14
Core	22
FastCGI	23
Installation	24
Migration and Upgrade	25
Sample Applications	28
Search	29
Security	29
Session Replication	30

Web Container	30
Localization	31
Sun Java Enterprise System	33
Web Server Documentation	35
Web Server Documentation Set	35
Documentation, Support, and Training	37
Searching Oracle Product Documentation	37
Third-Party Web Site References	37
Features and Enhancements in Previous Web Server Releases	37
Features and Enhancements in 7.0 Update 8	38
Features and Enhancements in 7.0 Update 7	38
Features and Enhancements in 7.0 Update 6	41
Features and Enhancements in 7.0 Update 5	42
Features and Enhancements in 7.0 Update 4	42
Features and Enhancements in 7.0 Update 3	43
Features and Enhancements in 7.0 Update 2	44
Features and Enhancements in 7.0 Update 1	46
Features and Enhancements in 7.0	48
Issues Resolved in Previous Web Server Releases	55
Issues Resolved in 7.0 Update 8	55
Issues Resolved in 7.0 Update 7	56
Issues Resolved in 7.0 Update 6	57
Issues Resolved in 7.0 Update 5	58
Issues Resolved in 7.0 Update 4	60
Issues Resolved in 7.0 Update 3	63
Issues Resolved in 7.0 Update 2	69
Issues Resolved in 7.0 Update 1	71

Oracle iPlanet Web Server 7.0.9 Release Notes

This *Release Notes* document contains important information about the 7.0.9 release of Oracle iPlanet Web Server (Web Server). This document addresses new features and enhancements, installation notes, known problems, and other late-breaking issues. Read this document before you begin using Web Server 7.0.9.

This document contains the following sections:

- “Features and Enhancements in Web Server 7.0.9” on page 5
- “Issues Resolved in Web Server 7.0.9” on page 7
- “Hardware and Software Requirements” on page 8
- “Installation, Migration, and Upgrade Notes” on page 12
- “Known Issues” on page 14
- “Web Server Documentation” on page 35
- “Features and Enhancements in Previous Web Server Releases” on page 37
- “Issues Resolved in Previous Web Server Releases” on page 55

Features and Enhancements in Web Server 7.0.9

Oracle iPlanet Web Server 7.0.9 is an update release to Sun Java System Web Server 7.0. In addition to the features and enhancements in Web Server 7.0 and Updates 1 through 8, Web Server 7.0.9 brings the following additional features and enhancements to the product.

- “Resolution of SSL/TLS Vulnerability CVE-2009-3555” on page 6
- “Support for JDT Java Compiler” on page 6
- “Support for Oracle JRockit JDK” on page 6
- “Ability to Change Session ID on Authentication” on page 6
- “For Large Applications, - -directory Option of add-webapp Command Deprecated in Favor of - -file-on-server Option” on page 6

Resolution of SSL/TLS Vulnerability CVE-2009-3555

Web Server 7.0 Update 7 included NSS 3.12.5, which provided relief, but not resolution, for the SSL/TLS renegotiation vulnerability [CVE-2009-3555](#). Additionally, Web Server 7.0 Update 7 disabled all use of SSL/TLS renegotiation in order to protect Web Server from attack. If either the client or Web Server attempted to trigger renegotiation on an existing SSL/TLS session, the connection would fail.

Web Server 7.0.9 includes NSS 3.12.6, which provides safe SSL/TLS renegotiation and so provides resolution of CVE-2009-3555. As a result, Web Server 7.0.9 re-enables use of SSL/TLS renegotiation.

Support for JDT Java Compiler

You can now configure Web Server to use the Eclipse JDT Java compiler instead of Ant and another Java compiler. For more information, see [“Using the Eclipse JDT Java Compiler” in Oracle iPlanet Web Server 7.0.9 Developer’s Guide to Java Web Applications](#).

Support for Oracle JRockit JDK

Web Server now supports the Oracle JRockit JDK on the 32-bit platforms it supports. For the 7.0.9 release, the minimum required JRockit JDK version is R27.6.5, which is certified to be compatible with Java SE 6 Update 14 (1.6.0_14).

Ability to Change Session ID on Authentication

Web Server 7.0.9 adds the `changeSessionIdOnAuthentication` property to the `sun-web-app` element of the `sun-web.xml` file. This property enables web applications to change session IDs upon authentication in order to avoid *session fixation* attacks. For more information, see [“sun-web-app Element” in Oracle iPlanet Web Server 7.0.9 Developer’s Guide to Java Web Applications](#).

For Large Applications, `--directory` Option of `add-webapp` Command Deprecated in Favor of `--file-on-server` Option

For large applications, you should use the `--file-on-server` option of the `add-webapp` command to provide a path to an exploded war file outside the Web Server root directory. Note, however, that the Administration server does not manage web applications deployed outside the Web Server root directory. For more information, see `add-webapp(1)` and [“Deploying a Web Application Directory” in Oracle iPlanet Web Server 7.0.9 Administrator’s Guide](#).

Issues Resolved in Web Server 7.0.9

This section lists the important issues resolved in Web Server 7.0.9.

Problem ID	Description
6837680	range header in reverse proxy does not take multiple values
6885216	WS7.0u6:wadm doesn't print error when password file is not correct
6896709	Web server 7.0 does not handled web apps deployed outside the installation path correctly
6899047	conn->elapsed doesn't get refreshed for new ka request in low latency mode (request header timeout).
6901051	unable to install a cert if o or ou contains comma
6911225	PAM auth : Passwd aging causes webservd to dump core in free_resp function
6911277	Server return 404 for /j_security_check -ending URLs
6913746	unable to startup the server if the first character is a digit in the hostname
6914493	regression: wadm reset-admin-password command fails on web server 7.0 U6 and U7
6917800	doc bug for web server 7 auto tuning which may cause a large memory usage
6920807	Admin GUI "Certificate Authorities tab" and wadm "list-certs" showed error in Japanese Windows OS
6927134	web 7u8 - Admin GUI will add additional IF/ELSEIF in the <virtual-server>-obj.conf
6928578	htaccess config causes webserver to crash on RHEL & SUSE Linux installation
6928808	ClassCast exception for HEAD requests on Java resources that do request dispatching
6931166	LIBPATH needs to be fixed for AIX 5.3/6.1 JDK6SR7 certification
6933187	Interval in check offline server of loadbalancer should be configurable.
6940796	net_read can set EAGAIN in errno when it times out.
6944895	web 7 RPP missing jsessionid
6947057	web7 RPP docs - to add retries parameter in docs
6955691	WS7: webdav crash when max-xml-request-body-size set to unlimited
6958053	web 7: file with comma in its filename inside a war file cause Admin GUI "Deployment Pending"
6960564	Installation of WS7U8 on IBM AIX 6.1 generates an error message but is successful.

Hardware and Software Requirements

This section provides information about the hardware and software requirements of Web Server 7.0.9, including the following topics:

- “Supported Platforms” on page 8
- “System Virtualization Support” on page 8
- “Operating System Patches” on page 8
- “Supported Browsers” on page 11
- “Deprecation Notices” on page 11

Supported Platforms

Complete information about supported operating environments and hardware for Web Server 7.0.9 is available in the *Oracle iPlanet Web Server 7.0.9 Certification Matrix*, which is accessible at the [Oracle Fusion Middleware Supported System Configurations](#) page.

System Virtualization Support

System virtualization is a technology that enables multiple operating system (OS) instances to execute independently on shared hardware. Functionally, software deployed to an OS hosted in a virtualized environment is generally unaware that the underlying platform has been virtualized. Oracle performs testing of its products on select system virtualization and OS combinations to help validate that Oracle products continue to function on properly sized and configured virtualized environments as they do on non-virtualized systems.

For information about Oracle support for Oracle products in virtualized environments, see [Supported Virtualization Technologies with Oracle Fusion Middleware](#).

Operating System Patches

Update your operating system with the latest applicable patches. Required patches are listed in the following sections.

Solaris Patches

x86 or SPARC users of Solaris 9 or 10 Operating System should have the latest patch cluster installed. This patch cluster is available under “Recommended and Security Patches” on the <http://sunsolve.sun.com/pub-cgi/show.pl?target=patchpage> web site.

Note – On a 32-bit Solaris (SPARC) platform, install `SUNWlibC` and `SUNWlibCx` packages, in addition to the patches listed in the sections below.

Web Server 7.0 installer determines if the required patches are installed on your machine, without them the installation fails. The following patches are required for successful installation and functioning of Web Server 7.0 on a supported platform.

Note – If the patches available at <http://sunsolve.sun.com> are *obsolete*, download the most recent version of these patches as they include the latest bug fixes and product enhancements.

Note – To know the Solaris Operation System version installed on your machine, see the `/etc/release` file.

The `/etc/release` file contains Solaris Operation System version information in the following format:

```
Solaris 10 6/06 s10x_u2wos_08 X86
Copyright 2006 Sun Microsystems, Inc. All Rights Reserved.
Use is subject to license terms.
Assembled 02 May 2006
```

Solaris 9 Platform (SPARC)

- Solaris 9 9/05
- 112970-12
- 111711-26 — Shared library patch for C++ (for the 32-bit version of Web Server)
- 111712-26 — Shared library patch for C++ (for the 64-bit version of Web Server)
- 112963-34
- 111722-05
- 112233-12

Solaris 9 Platform (x86)

- Solaris 9 9/05
- 114354-11
- 111712-17 — Kernel patch
- 111713-23 — Shared library patch for C++
- 113986-28
- 111728-04
- 111712-17

Solaris 10 Platform (SPARC and x86)

Note – For the 64-bit version of Web Server, you must check if the SUNWlxml package is installed on the server by running the command `# pkginfo SUNWlxml` which produces the following output:

```
system      SUNWlxml The XML library
```

This package is always installed with Solaris 10 standard installation, even if you choose the lowest level of installation `METACLUSTER=SUNWCmreq, NAME=Minimal Core System Support`.

If you do not want this package, you can either remove it by using the `pkgrm` command or use a `jumpstart` image which lacks this package.

- SPARC
 - 119963-20 — Shared library patch for C++
- x86
 - 119964-20 — Shared library patch for C++

Incompatible Patches

Some incompatible patches can affect Web Server startup and cause the server not to respond to requests. The following table lists such patches. If you have an incompatible patch installed on your machine, upgrade the patch to a recommended compatible patch.

TABLE 1 List of Incompatible Patches

Operating System	Incompatible Patch	Recommended Compatible Patch
Solaris 9 SPARC	112963-22 (linker patch)	112963-25 (linker patch)
	112963-23 (linker patch)	
	112963-24 (linker patch)	
Solaris 9 x86	113986-18 (linker patch)	113986-21 (linker patch)
	113986-19 (linker patch)	
	113986-20 (linker patch)	

AIX Patches

AIX 5.3

- 5300-08-01-0819 or above

AIX 6.1

- 6100-00-04-0815 or above

Supported Browsers

Complete information about supported web browsers for Web Server 7.0.9 is available in the *Oracle iPlanet Web Server 7.0.9 Certification Matrix*, which is accessible at the [Oracle Fusion Middleware Supported System Configurations](#) page.

Deprecation Notices

Deprecated Operating System Versions. As of the release of iPlanet Web Server 7.0.9, the following operating system versions are deprecated:

Microsoft Window Server 2003 Enterprise Edition, Service Pack 2
Solaris 9 Update 8 x86 (32-bit)
Solaris 9 Update 9 SPARC (32- and 64-bit)

These operation system versions will not be certified in a future release of iPlanet Web Server.

Uncertified Operating System Versions. As of the release of iPlanet Web Server 7.0.9, the following operating system versions are no longer certified:

HP-UX 11.11
Microsoft Windows 2000 Server and Windows 2000 Advanced Server
Microsoft Windows XP
Novell SUSE Linux Enterprise Server 9
OpenSolaris
Red Hat Enterprise Linux Advanced Server 3
Solaris 8

Deprecated Web Browser Versions. As of the release of iPlanet Web Server 7.0.9, the following web browser versions are deprecated:

Firefox 2
Microsoft Internet Explorer 6
Mozilla (all versions)

These web browser versions will become unsupported in a future release of iPlanet Web Server.

Installation, Migration, and Upgrade Notes

This section includes notes about installing, migrating and upgrading Web Server. For detailed information about these topics, review the information in the *Oracle iPlanet Web Server 7.0.9 Installation and Migration Guide*. For known issues in this release of Web Server, see “Known Issues” on page 14 in these release notes.

Installation

You cannot install Web Server to a directory that contains an earlier version of Web Server. You can, however, migrate the existing installation after installing Web Server to a new directory.

Web Server can be installed as part of Java Enterprise System or as a standalone version.

Standalone Installation

In a standalone installation, all the necessary shared components such as NSS, NSPR are co-packaged with the Web Server installation files.

Java ES Installation

If you are installing Web Server as part of the Java ES suite, the Java ES installer installs all the shared components such as NSS and NSPR as separate packages and Web Server specific binaries as separate operating system dependent packages. Hence you need to download and install all the shared components patches and Web Server patches.

Visit Sun Solve (<http://sunsolve.sun.com/show.do?target=patches/patch-access>). Download and install the latest Java ES Component Patches for the respective operating system.

Note – Web Server 7.0 Update 5 will not start successfully without installing the latest NSS / NSPR patches on your system. Therefore, before installing Web Server 7.0 Update 5, you can check for the appropriate NSS patch available for your system in Web Server 7.0 Update 5 patch README bundled within our Update 5 patch.

Migration

Web Server 6.0 and 6.1 configurations can be migrated. Direct migration from a Web Server version lower than 6.0 is not supported. Earlier versions such as Web Server 4.0 or later must first be migrated to Web Server 6.1, then to Web Server 7.0. For information about migrating from Web Server 4.0 or later to Web Server 6.1, see the latest *Sun Java System Web Server 6.1 Installation and Migration Guide* and the *Sun Java System Web Server 6.1 Release Notes* at [http://docs.sun.com/app/docs/prod/sjs.websrv61?l=en\[amp\]a=view](http://docs.sun.com/app/docs/prod/sjs.websrv61?l=en[amp]a=view).

For detailed information on migrating from Web Server 4.1 to Web Server 7.0, and from all versions of Web Server 6.0 to Web Server 7.0, see the *Oracle iPlanet Web Server 7.0.9 Installation and Migration Guide*.

Upgrade

When you install Sun Java System Web Server 7.0.9 over an existing installation of Sun Java System Web Server 7.0, the installer automatically carries out the upgrade.

If you have Sun Java System Web Server 7.0 installed, point the Sun Java System Web Server 7.0 Update 7 installer to the location of the Web Server 7.0 installation and then upgrade.

If you have installed Sun Java System Web Server 7.0 as part of Java ES 5, you are encouraged to install the following patches from the <http://sunsolve.sun.com/show.do?target=patchpage> web site to upgrade to Web Server 7.0 Update 7:

- 125437 for Solaris SPARC/SPARCv9
- 125438 for Solaris x86/x64
- 125439 for Linux
- 125440 for HP-UX
- 125441 for Windows

If you are using a localized version of Web Server, install the following patches before installing the base patches for successful upgrade from Web Server 7.0 to Web Server 7.0 Update 7:

- 126331-07 for Solaris SPARC (8/9/10) (Solaris SPARC Localization patch id)
- 126332-07 for Solaris x86 (8/9/10) (Solaris x86 Localization patch id)

In Web Server 7.0 Update 5, the multilingual files are integrated into the base patch. Hence, if Web Server 7.0 multilingual packages are installed on your system, you must first install the 110n patch 126331-05 (Sparc)/126332-05 (x86) and then install the base patch 125437-15 (Sparc)/125438-15 (x86) or higher.

For detailed information about upgrading from Web Server 7.0 to Web Server 7.0 Update 5, see *Oracle iPlanet Web Server 7.0.9 Installation and Migration Guide*.

Compatibility Issues

1. Web Server 7.0 supports JavaServer Faces 1.2 technology. Most JavaServer Faces 1.1 applications are expected to work with Web Server 7.0 without any modifications. However, there are some compatibility issues that might be encountered when migrating applications to JavaServer Faces 1.2 applications and such applications require modifications. The changes are documented in the JavaServer Faces release notes at https://javaserverfaces.dev.java.net/rlnotes/1.2_04/issues.html.

2. Sun Java System Portal Server 7.1, provided with Java ES 5 is not compatible with Sun Java System Web Server 7.0 Update 1. If you have deployed Sun Java System Portal Server 7.1 along with Web Server 7.0, you need to upgrade both servers rather than only Sun Java System Web Server 7.0. The required Sun Java System Portal Server 7.1 upgrade is available with Java Enterprise System 5 Update 1 or with the following patches available on <http://sunsolve.sun.com/show.do?target=patchpage> web site.
 - 124301 (SPARC)
 - 124302 (x86)
 - 124303 (Linux)

If you are using a localized version of Web Server, install the following Portal Server localization patches:

- 125301 (Solaris SPARC, Solaris x86 localization)
- 125302 (Linux localization)

Known Issues

This section lists the important known issues and limitations at the time of the Web Server 7.0.9 release.

- “Administration” on page 14
- “Core” on page 22
- “FastCGI” on page 23
- “Installation” on page 24
- “Migration and Upgrade” on page 25
- “Sample Applications” on page 28
- “Search” on page 29
- “Security” on page 29
- “Session Replication” on page 30
- “Web Container” on page 30
- “Localization” on page 31
- “Sun Java Enterprise System” on page 33

Administration

The following table lists the known issues in the administration of Web Server.

TABLE 2 Known Issues in Administration

Problem ID	Description
6944873	<p>On AIX with IBM JDK 6, user authentication fails if the uid contains a double quote and Web Server is configured to use LDAP realm</p> <p>This issue arises due to a bug in the IBM JDK.</p>
6364924	<p>A node can be registered to multiple administration servers which may cause a configuration conflict.</p> <p>It is possible to register a node to a second Administration Server without canceling the registration with the first Administration Server. However, this leads to the nodes becoming inaccessible to both the Administration Servers.</p> <p>Workaround:</p> <p>On each registration, restart the administration node. The administration node will be available to the most recent Administration Server it has registered to.</p>
6379125	<p>wadm command allows connecting to a node, shows a certificate and then throws a 'HTTP 400 Error'.</p> <p>When an administration node receives a connection, the administration node does not check the connection is from the Administration Server before proceeding. It not only prints an inappropriate error message, but also prompts the user to enter the password.</p>
6327352	<p>Session replication enabled instances does not come up normally, if other instances in the cluster are not started.</p>
6393534	<p>After migrating the Java keystore keycerts using the migrate-jks-keycert command, trying to list the migrated jks keycerts using the list-certs command, displays the CN, org and other information instead of the certificate nickname.</p>
6407486	<p>While setting the SSL property using the wadm set-ssl-prop command, the server-cert-nickname property accepts any certificate nickname, instead of accepting only the server certificate nickname.</p>
6443742	<p>The set-session-replication-prop CLI command does not work if the 'node' option is provided with a qualified domain name.</p> <p>Workaround</p> <p>Use the output of the list-nodes command for the valid names of the nodes in the set-session-replication-prop command.</p>
6468570	<p>Specifying "yes" at the wadm prompt crashes the CLI.</p>
6469676	<p>When you try to connect to the Administration Server after the administration certificates have expired, an incorrect error message is displayed.</p>
6480600	<p>The register-node command gives an incorrect error message when the Administration server runs out of disk space.</p>

TABLE 2 Known Issues in Administration (Continued)

Problem ID	Description
6495446	If no disk space is available on the device, wadm throws an incorrect error message "Unable to communicate with the administration server".
6502800	Executing the migrate-server command with both "--all" and "--instance" options does not result in an error. A warning or an error message should be displayed indicating that the user is attempting the set mutually exclusive options.
6416328	The Start Instances. button in the Admin Console is enabled for instance which is already running. The buttons should be enabled or disabled based on the status of the instance.
6418312	wadm allows you to define duplicate user properties. Adding duplicate user properties does not show an error message; however, a new user property is not created.
6421740	There is no provision to create new Access Control List (ACL) file using the Admin Console or the CLI.
6423432	On Windows, using an existing configuration, repeating the process of adding and removing the registered nodes causes validation failure.
6430417	MIME Types allows MIME value with multibyte characters.
6442081	Text in Access Control List page is not formatted.
6442172	User can be switched between 'available' and 'selected' lists in ACE even though the user is deleted from the authentication database.
6446162	No warning is issued before the deletion of key or the digestfile authentication database.
6448421	Administration Interface allows you to create a new user with multi-byte User ID in the keyfile authentication database.
6455827	User and Group table in the Admin Console displays the entire result in a single page.
6461101	Labeling of the Request Certificate and Install buttons in the Admin Console Create Self-Signed Certificate page needs to be revised.
6462057	Add and Remove buttons are enabled in new ACE window even if no items are present in the 'Available' list.
6464891	Admin Console truncates the display of server logs at 50 lines or 2 pages.
6465382	No validation exist to check the entry of wrong country code in the certificate request wizard.
6465421	In the Admin Console, no text field description is provided for virtual-server, authdb, dav collection, and event fields .

TABLE 2 Known Issues in Administration (Continued)

Problem ID	Description
6466336	Admin Console shows wrong JDK version while creating a new configuration. The JDK version displayed in the Admin Console is 5.0 u6 instead of 5.0 u7.
6471171	Style formatting is lost after restarting the Administration Server from Nodes -> Administration Server General tab.
6471367	Attempting to access the Admin Console in another tab of the same browser does not work.
6471792	View Log displays result in a single page. Although the search criteria selected for record size is 25 log entries, the log displays the results in one single page even if there are more than 50 log entries.
6472932	Token mismatch error is displayed when you remove the token password and then reset it in the Common tasks -> Select configuration -> Edit configuration -> Certificates -> PKCS11 Tokens page.
6486037	The Virtual Server Management->Content Handling->Document Directories->Add should have a browse option to choose the path of a additional document directory.
6492906	Message displayed about WebDAV collection locks in the Admin Console is misleading. If you specify the time-out value for the WebDAV collection as <code>infinite</code> , the Common Tasks->Select Configuration ->Select Virtual Server->Edit Virtual Sever ->WebDAV->Select collection page displays the message DOES NOT EXPIRE. What it actually means is that the lock does not expire automatically after a specified time or the time-out is infinite.
6498484	Incorrect error message is displayed on setting empty token password using the 'Set passwords' button.
6500157	Instance fails to restart if you try to edit a token password and deploy a configuration on an instance which is already running.
6502287	The Admin Console displays an exception when you delete a configuration and click on the Migrate button.
6502374	The Admin Console Review screen in wizards should only show fields that have values.
6502793	During migration, the log-dir path permission is not validated.
6266358	Cannot log in through the Administration CLI if the administration password has extended ASCII characters.
6361329	The error-response file name should be validated.
6367282	Administration server starts with expired certificate; wadm should warn about expired certificates.
6375505	The unregister-node command should also clean up certificates on the administration node.
6408169	WebDAV lock CLIs do not work in a cluster environment.

TABLE 2 Known Issues in Administration (Continued)

Problem ID	Description
6408186	Multiple installations of the administration nodes on the same node that is registered to the same administration server should be not be allowed.
6416369	Accessing the administration node URL results in Page Not Found error. As the administration node does not have a GUI, accessing the administration node URL results in Page Not Found error.
6422936	No validation for class path prefix and suffix, and native library path in JVM Path Settings in Java.
6423310	The server.xml elements should be grouped based on functionality.
6441773	On Windows, Administration Server moves the Web application files physically before stopping the Web application.
6462515	The Admin Console misleads user with "Instance modified" message when runtime files gets created in the config directory.
6462579	Trust store does not deleted on uninstalling the administration node after unregistering it with the administration server.
6468330	Changes made to the JavaHome property does not get saved after restarting the instance.
6491749	Need better validation in certain text fields to prevent obj.conf file corruption. Most of the functional validation of the data in a form is done in the back end. The GUI has only minimal checks such as empty fields, integer values, and ASCII values. Hence, the GUI stores the data in the obj . conf when parsed gets corrupted .
6497213	Executing the restart-admin command followed by the stop-admin command throws exception in administration error logs.
6587832	On Windows, the Admin Console intermittently fails to come up. Workaround: <ol style="list-style-type: none"> 1. This problem is seen on Windows 2003 if you have "Internet Explorer Enhanced Security Configuration" enabled. 2. To access the Admin Console without disabling Enhanced Security feature, include the site in the list of trusted sites explicitly on the browser. 3. To disable Internet Explorer enhanced security configuration, go to Control Panel > Add/Remove Programs > Add/Remove Windows Components. 4. Deselect the check box next to Internet Explorer Enhanced Security Configuration. 5. Restart the browser.

TABLE 2 Known Issues in Administration (Continued)

Problem ID	Description
6746045	<p data-bbox="489 239 1282 265">Once config changes are made it is found that file ownership changes in docs directory</p> <p data-bbox="489 282 1332 335">When a user creates a directory, adds some files and deploys them under the docs directory, the ownership of all files under this directory, changes to the owner who installed Web Server.</p> <p data-bbox="489 352 618 378">Workaround:</p> <p data-bbox="489 395 1053 421">The user directories should not be created under docs directory.</p>
6750708	<p data-bbox="489 447 1239 473">Web Server 7.0 Administration CLI does not accept multibyte characters as input.</p> <p data-bbox="489 491 1296 569">Admin CLI does not accept input strings which has multibyte or non-ascii characters. For example, if you are entering an input value containing a non-ascii character (Felhasználók) along with the command, the input value will be garbled as below:</p> <pre data-bbox="489 586 1310 638">wadm> set-authdb-prop --config=test --authdb=sajit url=ldap://test.example.com:389/ou=Felhaszn??l??k,dc=india,dc=example,dc=com</pre> <p data-bbox="489 656 618 682">Workaround:</p> <p data-bbox="489 699 1303 786">While modifying the server.xml file manually, to enter base DN value, you have to type the URL encoded sequence as input instead of multibyte characters. For example, type:: "Felhaszn%C3%A1l%C3%B3k" instead of "Felhasználók"</p>

TABLE 2 Known Issues in Administration (Continued)

Problem ID	Description
6722375	<p>The Admin server throws an error as the postpatch script for patches 125437-14 and 125438-14 are not Alternate Root compliant.</p> <p>Workaround:</p> <ol style="list-style-type: none"> 1. Boot the alternate boot OS after adding the patch to the alternate boot environment. 2. Start the admin server. The admin server fails to start and throws the below error message: <pre>java.lang.NoClassDefFoundError: com/sun/scn/client/comm/SvcTagException</pre> 3. Edit the web server postpatch script to define the ROOTDIR value as / or /space, where JES base path is given. <pre>bash-3.00# cat postpatch #!/bin/ksh # Copyright (c) 2007 by Sun Microsystems, Inc. # All rights reserved # PATH="/bin:/usr/bin:/sbin:/usr/sbin:\$PATH" export PATH ROOTDIR=/ BASEDIR="`pkgparam -R \$ROOTDIR SUNWwbsvr7 BASEDIR 2>/dev/null`" if [-n "\$BASEDIR"] then INSTALL_DIR="\$ROOTDIR\$BASEDIR/SUNWwbsvr7"; PERLDIR="\$INSTALL_DIR/lib/perl" if [-f "\$INSTALL_DIR/lib/wsenv"] then . "\$INSTALL_DIR/lib/wsenv"; WS_IS_JES=1; export WS_IS_JES bash-3.00#</pre> 4. Run the script to complete the upgrade. <pre>bash-3.00# ksh /tmp/postpatch "/opt/SUNWwbsvr7/lib/perl/perl" -I "/opt/SUNWwbsvr7/lib/perl" -I "/opt/SUNWwbsvr7/lib/perl/lib" -I "/opt/SUNWwbsvr7/lib/perl/lib/site_perl" "/opt/SUNWwbsvr7/lib/upgradeServer.pl" bash-3.00#</pre>The admin server starts without any error.

TABLE 2 Known Issues in Administration (Continued)

Problem ID	Description
6784450	<p>Unable to login to Admin server using Mozilla Firefox 3.0</p> <p>Workaround:</p> <ol style="list-style-type: none"> 1. On the Solaris 10 platform, Mozilla Firefox 3.0.4 browser, go to Edit-> Preferences-> Advanced-> Encryption-> Server tab. 2. Click Add Exceptions... 3. Enter the address of the website you want to access in the text area and click Allow
6820164	<p>An OpenSolaris 2008.11 Bug 4788 causes a serious impact on Web Server.</p> <p>Web Server's certificates are affected during deployment of Web Server on OpenSolaris 2008.11, with the below warning:</p> <pre>root# /opt/webserver7/admin-server/bin/startserv Oracle iPlanet Web Server 7.0U4 B12/02/2008 02:49 warning: CORE1235: SSL server certificate Admin-Server-Cert is not yet valid. ...</pre> <p>An OpenSolaris Bug 4788, with time, causes this problem. For more information about this, see Bug 4788.</p> <p>Workaround:</p> <p>Reboot your server after deploying OpenSolaris 2008.11 and correct the server time.</p>
6842383	<p>FastCGI suid environment for Red Hat Enterprise Linux</p> <p>To get the FastCGI suid environment to work on Red Hat Enterprise Linux, perform the following steps:</p> <ol style="list-style-type: none"> 1. <code>cd <webserver_install>/plugins</code> 2. <code>chown webservd fastcgi</code> 3. <code>cd fastcgi</code> 4. <code>chmod 4755 Fastcgistub</code> 5. Add the following lines in <code>/etc/ld.so.conf</code> <pre><webserver_install>/lib <webserver_install>/jdk/jre/lib/i365/server</pre> 6. Run <code>ldconfig</code> 7. Restart the Web Server <p>Note – The file system where the Web Server is installed and the <code>/tmp</code> directory should have permission to run the suid program, The file system should not be mounted with the <code>nosuid</code> option.</p>
6893239	<p>JDK 1.6.0 and JDK 1.5.0 logger are not working properly.</p>

Core

The following table lists the known issues in the core of Web Server.

TABLE 3 Known Issues in Core

Problem ID	Description
6944895	<p>jsessionid is missing when ntrans-j2ee NameTrans precedes reverse-proxy-/ NameTrans</p> <p>If the <code>obj.conf</code> contains <code>NameTrans</code> directives such that <code>nt rans - j2ee</code> precedes <code>reverse-proxy- /</code>, the <code>jsessionid</code> is lost.</p> <p>Workaround</p> <p>Reorder the <code>NameTrans</code> directives such that <code>reverse-proxy- /</code> precedes <code>nt rans - j2ee</code>; for example:</p> <pre>NameTrans fn="map" from="/" name="reverse-proxy-/" to="http:/" NameTrans fn="nt rans - j2ee" name="j2ee"</pre>
6948770	<p>On 64-bit Linux, can't distinguish between 32-bit and 64-bit Web Server</p> <p>The <code>wadm -version</code> command does not indicate whether Web Server is 32-bit or 64-bit.</p> <p>Workaround</p> <p>Enter the following command in a terminal window:</p> <pre>file <i>install-dir</i>/lib/webservd</pre>
6955106	<p>On Linux, exception at startup due to a non-existent jhall.jar link</p> <p>During startup, Java throws a <code>FileNotFoundException</code> exception that specifies <code>jhall.jar</code> as the missing file. This situation arises after <code>sun-javahelp-2.0-fcs</code> has been uninstalled, because the uninstallation leaves a link to <code>jhall.jar</code> in <code>/usr/java/packages</code>.</p> <p>Workaround</p> <p>Remove the link to <code>jhall.jar</code>; for example:</p> <pre>rm -f /usr/java/packages/jhall.jar</pre>

TABLE 3 Known Issues in Core (Continued)

Problem ID	Description
6785490	<p>Any URI that does not end with the "real" file name fails to execute properly, resulting in a "No input file specified" error.</p> <p>For PHP users:</p> <p>Web Server 7.0 Update 4 populates the environment variables REQUEST_URI and SCRIPT_FILENAME for FastCGI and CGI applications. The introduction of the SCRIPT_FILENAME variable causes PHP to display a No input file specified PHP error for scripts that are mapped to virtual URIs, that is, URLs ending with / instead of /index.html or URLs making use of Web Server 7.0's URI rewriting feature. The affected PHP versions are 5.2.5 through 5.2.9. For more information, see http://bugs.php.net/bug.php?id=47042.</p> <p>Workaround:</p> <p>If a PHP application is mapped to a virtual URI, then cgi.fix_pathinfo should be set to 0 in the php.ini file. This setting is required for many popular PHP applications like Drupal, Wordpress, Joomla, etc.</p> <p>However, this setting will cause PHP applications that rely on path-info like /foobar.php/baz/ to return a No input file specified PHP error. If a PHP application relies on path-info, then cgi.fix_pathinfo should not be disabled.</p>
6296993	When there is an error executing an obj.conf directive, the filename and line number where the offending directive was found are not logged.
6365160	When server.xml schema validation fails due to a data type constraint violation, it displays an error message that does not describe the set of valid values for the element.
6378940	All HTTP header parsing error are not logged with the client IP and a description of the error.
6470552	set-variable SAF could not set predefined variable.
6489220	<p>Server treats non-interpolated strings that contain \$\$ character constants as interpolated.</p> <p>When a parameter value contains a \$\$ escape, the server constructs a PblockModel for the parameter block. This is unnecessary because \$\$ is a constant.</p>

FastCGI

The following table lists the known issues in the FastCGI.

TABLE 4 Known Issues in FastCGI

Problem ID	Description
6485248	<p>The fastcgi stub does not properly close all the processes when reuse-connection is set to true.</p> <p>Configure Web Server 7.0 to work with PHP as a FastCGI plug-in and set <code>reuse-connection=true</code>. When you shutting down the server or reconfiguring the server, the <code>fastcgi()</code> process and its child processes are left behind and not killed properly.</p>

Installation

The following table lists the known issues in the installation of Web Server.

TABLE 5 Known Issues in Installation

Problem ID	Description
6948019	<p>On Unix, if any directory in the installation path lacks the appropriate execute privilege, server startup fails</p> <p>If any of the directories in the installation path does not provide execute privilege to the <code>websrvd</code> user, the Web Server instance fails to start.</p> <p>Workaround</p> <p>Use the <code>chmod o+x directory</code> as needed to change execute permissions to the directories in the installation path.</p>
6414539	<p>Uninstalling the administration node does not delete itself from the administration server node.</p> <p>After installing the administration node and registering it with the administration server in the Node tab, the administration node is listed in the Node tab. When the administration node is uninstalled, the administration node entry remains in the Node tab.</p>
6287206	<p>Cannot install if the setup is started from a shared folder on the network.</p> <p>On the Windows platform, unable to install the product when the installer <code>setup.exe</code> is started from a shared network folder on another machine.</p>
6311607	<p>On Windows, installer crashes in CLI mode, if the administration password is >= 8 characters.</p> <p>If the administration user password is greater than eight characters, then any invalid input to the administration port, web server port, or the administration user ID crashes the installer.</p> <p>Workaround:</p> <p>When installing Web Server 7.0 on the Windows platform using the command-line interface (CLI), the administration password must be set to less than (<) eight characters.</p>

TABLE 5 Known Issues in Installation (Continued)

Problem ID	Description
6408072	<p>On Windows, need icons for objects in Programs folder.</p> <p>The objects in the Web Server 7.0 folder on Windows are created with default Windows program icons and do not have specific icons that denote Sun programs.</p>
6492144	<p>The CLI installer does not handle ctrl+c while entering the password.</p> <p>The installer does not accept <code>ctrl+c</code> and hence the terminal becomes unusable.</p>
6710925	<p>RH5.1 user cannot install Web Server 7.0 Update 3 using GUI mode</p> <p>Workaround</p> <p>To overcome this failure:</p> <ol style="list-style-type: none"> 1. Use the CLI based installer. 2. Create a symbolic link to the <code>xdpyinfo</code> command. For example, <pre>[root@server bin]# ln -s /usr/bin/xdpyinfo /usr/X11R6/bin/xdpyinfo</pre>
6717123	<p>Registration Options panel UI sometimes doesn't show up properly</p> <p>The 'Registration Options' GUI in the installer does not show up properly sometimes.</p> <p>Workaround:</p> <p>Resizing the installer window will fix this issue.</p>

Migration and Upgrade

The following table lists the known issues in the migration and upgrade areas of Web Server.

TABLE 6 Known Issues in Migration and Upgrade

Problem ID	Description
6914893	<p>Not all properties from 6.0 jvm12.conf file are migrated to 7.0 server.xml file</p> <p>When migrating from Sun iPlanet Web Server 6.0 to Oracle iPlanet Web Server 7.0, properties in the 6.0 jvm12.conf file of the form</p> <p><i>name = value</i></p> <p>are not migrated as JVM options to the 7.0 server.xml file. Only the properties listed in “jvm12.conf Parameter Reference” in <i>iPlanet Web Server 6.0, Enterprise Edition Programmer’s Guide to Servlets</i> (http://docs.sun.com/source/816-5689-10/xjvm.htm#22633) are migrated.</p> <p>Workaround</p> <p>Migrate these properties’ values manually. To do so, use Chapter 3, “Elements in server.xml,” in <i>Oracle iPlanet Web Server 7.0.9 Administrator’s Configuration File Reference</i> to locate the server.xml element or subelement that corresponds to the jvm12.conf property you are migrating, and transfer the value to the server.xml file.</p>
6407877	<p>Incorrect migration occurs while migrating from Web Server 6.0 to 7.0 if the installed.pkg file is not found.</p> <p>In Web Server 6.0 to 7.0 migration, if the installed.pkg file is missing, Web Server incorrectly migrates the NSServlet entries in the magnus.conf file.</p>
6490124	<p>6.x->7.0: Migrated scheduled events still points to 6.x paths in the server.xml file.</p>
6502529	<p>6.1->7.0: Migration does not handle relative path set for search-collection-dir correctly.</p> <p>During instance migration, specifying a relative path for the target path into which the search collections should be copied, results in the search collection directory being created with respect to the config-store. When the instance is instantiated, the indexes are created without properly migrating the search collections.</p>
6502769	<p>6.x->7.0: Migration ignores any "document-root" NameTrans specified in the obj.conf file.</p>
6498806	<p>On Windows, Web Server Admin Console does not appropriately warn users during migration.</p> <p>Administration Server does not detect if the selected new configuration or the service name already exists on Windows and hence does not appropriately warn the users to select a different configuration name or suggest a different configuration name as default.</p>
6500509	<p>Web Server 7.0 migration tool is unable to successfully migrate from Web Server 6.1 if it has Root Certs installed in it.</p>

TABLE 6 Known Issues in Migration and Upgrade (Continued)

Problem ID	Description
6747123	<p>The request processing behavior has changed in Web Server 7.0 Update 2 release.</p> <p>This change does not manifest while using Web Server 7.0 Update 2 RPP.</p> <p>A modification in the Web Server's request processing engine to fix a significant error in Web Server, has changed the order in which the web server processes objects and directives in the server's <code>obj . conf</code> file. This correction now guarantees that the below rules are applied while processing a request:</p> <ul style="list-style-type: none"> ■ All <code>ppath</code> objects that apply to a request are evaluated ■ If there is a named object that applies to a request, it will take precedence over any <code>ppath</code> objects in cases where the two conflict. <p>If your <code>obj . conf</code> file contain <code>ppath</code> objects, evaluate them to determine if your <code>obj . conf</code> file requires any modification. As a consequence of the above change in the request processing behavior, when you upgrade previous Web Server versions to the Web Server 7.0 Update 2, or later, you may have to make minor changes to the <code>obj . conf</code> files, as described after this table.</p>

Handling the request processing behavior change in Web Server 7.0 Update 2

As a consequence of the change to the request processing behavior, when you upgrade previous Web Server versions to the Web Server 7.0 Update 2 or later, you may have to make minor changes to the `obj . conf` files, as listed below:

1. Using IF directive

In the following example, directives contained in the `ppath` objects will not be invoked when an explicit JSP extension is found in the request URI, as the `nt rans - j 2ee NameTrans SAF` will apply to a JSP extension and cause the object named `j 2ee` to be evaluated next. The WebLogic proxy service used here to forward requests to the WebLogic server is no longer invoked, although there are no modifications made to the `obj . conf` file. As a result, the web server sends the request to its own web container, instead of the WebLogic proxy, resulting in failure of the request.

In the `obj . conf` file, default object, add a conditional statement to the `nt rans - j 2ee` service with the problem URIs, as shown below:

```
<Object name="default">
AuthTrans fn="match-browser" browser="*MSIE*" ssl-unclean-shutdown="true"
#
#Adding <IF...> and </IF> bracketing to compensate
for change in ppath processing
#
<IF $uri !~ ".*WebApp/.*" >
NameTrans fn="nt rans - j 2ee" name="j 2ee"
PathCheck fn="find-index-j 2ee"
ObjectType fn="type-j 2ee"
Error fn="error-j 2ee"
</IF>
....
```

```

....
<Object name="j2ee">
Service fn="service-j2ee" method="*"
</Object>

<Object ppath="*/examplesWebApp/*" >
Service fn=wl_proxy WebLogicHost=jwsse10.red.iplanet.com WebLogicPort=7001
</Object>

<Object ppath="*/ejemploWebApp/*">
Service fn=wl_proxy WebLogicHost=jwsse10.red.iplanet.com
WebLogicPort=7002
</Object>
</Object>

```

This allows the ntrans - j2ee to be executed only when the URI's do not match.

2. Using assign-name NameTrans

In simple scenarios, you can change ppath objects to name objects by using assign-name in the default object. This allows the assign-name to be executed ahead of ntrans - j2ee.

```

<Object name="default">
NameTrans fn="assign-name" from="/examplesWebApp/*" name="examples_proxy"
NameTrans fn="assign-name" from="/ejemploWebApp/*" name="ejemplo_proxy"
NameTrans fn="ntrans-j2ee" name="j2ee"
....
....
</Object>

<Object name="j2ee">
Service fn="service-j2ee" method="*"
</Object>

<Object name="examples proxy" >
Service fn=wl_proxy WebLogicHost=jwsse10.red.iplanet.com WebLogicPort=7001
</Object>

<Object name="ejemplo proxy">
Service fn=wl_proxy WebLogicHost=jwsse10.red.iplanet.com WebLogicPort=7002
</Object>

```

3. Disabling

Turning off Java Web container support on web server will ensure that the JSPs will be handled by WebLogic proxy function. However, this is only suggested when you do not intend to host Java content in the proxying tier.

Sample Applications

The following table lists the known issues in Sample Applications of Web Server.

TABLE 7 Known Issues in Sample Applications

Problem ID	Description
6472796	<p>sendmail.jsp shows incorrect file to be edited to specify resource.host for javamail sample application.</p> <p>Workaround</p> <p>To set <code>javamail.resource.host</code>, edit the <code>javamail.build.properties</code> and not the <code>build.xml</code> as specified in <code>install-dir/samples/java/webapps/javamail/src/docroot/sendmail.jsp</code>.</p>

Search

The following table lists the know issues in the search functionality of Web Server.

TABLE 8 Known Issues in Search

Problem ID	Description
6943388	<p>Building a search collection hangs when the number of documents is large</p> <p>When building a search collection for a large number of documents, the process hangs.</p> <p>This situation arises because the processing of each document is handled by a new thread, each consuming heap space.</p> <p>Workaround</p> <p>Increase the Java heap size using the <code>-Xmx</code> option. For example, you might increase the heap size from 128 MB (<code>-Xmx128m</code>) to 512 MB (<code>-Xmx512m</code>).</p>
6701532	<p>Search engine fails to index password protected PDF document</p> <p>If a PDF document is password protected and encrypted, the search engine fails to index the document's metadata. As a result, the requested search fails.</p>

Security

The following table lists the known issues in the security area of Web Server.

TABLE 9 Known Issues in Security

Problem ID	Description
6376901	<p>Limitation supporting basic and digest-based ACLs for resources in the same directory.</p> <p>If the server uses digest and basic-based ACLs in different parts of their doc tree, attempting to use both simultaneously on different files or resources in the same directory is not possible.</p>

TABLE 9 Known Issues in Security (Continued)

Problem ID	Description
6431287	<p>TLS_ECDH_RSA_* require the server cert signed with RSA keys.</p> <p>Cipher suites of the form TLS_ECDH_RSA_* requires server to have an ECC keypair with a cert signed using RSA keys. Note that this precludes using these cipher suites with self-signed certificates. This requirement is inherent to these cipher suites and is not a bug. The server should detect and warn about wrong configurations related to these cipher suites but currently it does not do so.</p>

Session Replication

The following table lists the known issues in the session replication functionality of Web Server 7.0.

TABLE 10 Known Issues in Session Replication

Problem ID	Description
6324321	<p>Descriptive error message is not displayed when an error occurs remotely.</p> <p>When an exception occurs remotely, error messages are logged in the error log of the remote instance. However, the local instance currently displays a generic remote exception which does not clearly indicate which error log that the user must view.</p>
6396820	<p>Session replication does not failover correctly when cookies are disabled on the client.</p>
6406176	<p>When enabled, session replication should be the default session manager.</p> <p>After enabling session replication by using the Admin Console or the CLI, or by editing the <code>server.xml</code> file, session replication is not really enabled. Instead, <code>sun-web.xml</code> needs to be manually edited.</p>
6800993	<p>A minor data loss occurs, as async cluster is not available.</p> <p>It is observed that a small amount of http session data loss can occur in few cases. Asynchronous implementation, by using <code>async</code> parameter, in session failover might resolve this issue.</p>

Web Container

The following table lists the known issues in the web container of Web Server.

TABLE 11 Known Issues in Web Container

Problem ID	Description
4858178	<p>Web container writes to stderr.</p>

TABLE 11 Known Issues in Web Container (Continued)

Problem ID	Description
6349517	<p>Incorrect web application session statistics for MaxProcs > 1 mode.</p> <p>Web Server runs in multi-process mode. The <code>MaxProcs</code> configuration variable in the <code>magnus.conf</code> is used to set the maximum number of processes. If the value for <code>MaxProcs</code> is set to greater than 1, the Web Server uses <code>mmap</code>-based session manager so that the session could be shared among different JVMs. While collecting statistics from multiple processes, web application MBeans provide session for individual MBeans. There is no way to find the true number of sessions by seeing individual MBean's web application session statistics.</p>
6394715	<p>Web container deletes the disabled web application MBeans object.</p> <p>When the web application is disabled by setting the <code><enabled></code> element to false in the <code>server.xml</code> file, the web container deletes the web application's MBeans and hence treats it as a closed or deleted web application. Since disabled objects are deleted, statistics are also lost.</p>
6419070	<p>No information is logged in error logs at the finest log level on successful JNDI resource creation.</p>
6422200	<p>com.sun.org.apache.xerces.internal.jaxp.DocumentBuilderImpl.parse does 1 byte reads.</p> <p>When reading the <code>server.xml</code> file, the first line containing the XML version number and the encoding is read 1 byte at a time.</p>
6440064	<p>Servlet container creates a thread per virtual server.</p>
6501184	<p>REQ_EXIT causes javax.servlet.ServletException.</p>

Localization

The following table lists the known issues in the localized version of Web Server.

TABLE 12 Known Issues in Localization

Problem ID	Description
6543814	<p>Search filter “*” does not work correctly for multi-byte strings.</p>

TABLE 12 Known Issues in Localization (Continued)

Problem ID	Description
5046634	<p>There is no functionality equivalent to use-responseCT-for-headers in Web Server 7.0.</p> <p>Response header encoding is enabled at the web-app level by setting the value of the configuration parameter use-responseCT-for-headers to any of the values; yes, true, or on in the web-app/sun-web.xml file.</p> <p>For example, set Response header encoding as follows:</p> <pre data-bbox="415 427 1043 644"><sun-web-app> <parameter-encoding form-hint-field="j_encoding"/> <property name="use-responseCT-for-headers" value="true" /> <session-config> <session-manager/> </session-config> <jsp-config/> </sun-web-app></pre>
6716537	<p>Creating socket error message is not localized.</p>
6775946	<p>patchrm 125437-15 fails if they are installed in Japanese locale.</p> <p>Installing patchrm 125437-15 in Japanese locale fails and throws the below error:</p> <pre data-bbox="415 805 729 826">WARNING: patchrm returned <7></pre> <p>The log file output is as below:</p> <pre data-bbox="415 892 1029 999">/var/tmp/dstreAAAW0a4wU/SUNWwbsvr7x/install/checkinstall: XXXXXXXXXXXXXXXXXXXX 4: '(' unexpected pkgadd: ERROR: checkinstall script did not complete successfully Installation of <SUNWwbsvr7x> partially failed.</pre> <p>This issue is observed in the following platforms:</p> <ul style="list-style-type: none"> ■ SPARC Platform - Solaris 10 with patch 119254-40 through 119254-47 and without 119254-48 ■ x86 - Solaris 10 with patch 119255-40 through 119255-47 and without 119255-48 <p>Workaround:</p> <ol style="list-style-type: none"> 1. Avoid installing the above listed affected patches. If these patches are already installed, you can remove them by using the patchrm(1M) command to return to a safe patch level. 2. Avoid installing patches with Japanese locale. For more information, see http://sunsolve.sun.com/search/document.do?assetkey=1-26-103104-1. 3. Apply patch 119254-48 or higher on Solaris 10 SPARC platform and patch 119255-48 or higher on Solaris 10 x86 platform.

Sun Java Enterprise System

The following table lists the known issues in the Sun Java Enterprise System (Java ES).

TABLE 13 Known Issues in Java ES

Problem ID	Description
6432106	<p>Sun Java System Portal Server search throws exception after Web Server upgrade.</p> <p>Portal Server search functionality throws exception when upgrading Web Server from Java ES 4 to Java ES 5.</p> <p>Workaround</p> <p>Note – Move the existing <code>libdb-3.3.so</code> and <code>libdb_java-3.3.so</code> library files to an appropriate location, somewhere outside the Web Server's private directories. Once the Portal Server libraries are in a suitable location, that path must be specified for the <code><libdb-3.3.so path>:<libdb_java-3.3.so path></code> in the following commands.</p> <p>On Solaris platform, perform the following steps:</p> <ol style="list-style-type: none"> Copy the <code>libdb-3.3.so</code> and <code>libdb_java-3.3.so</code> files from Web Server 6.1 <code>lib</code> directory to an appropriate location. <p>Note – For HP-UX, the files are <code>libdb-3.3.sl</code> and <code>libdb_java-3.3.sl</code>. For windows, the files are <code>libdb-3.3.dll</code> and <code>libdb_java-3.3.dll</code>.</p> <p>Caution – Do not copy the library files to Web Server 7.0 private directories (For example, <code>lib</code> directory).</p> Create a directory (<code>mkdir</code>) by name <code>/portal_libraries</code>. Copy the library files <code>libdb-3.3.so</code> and <code>libdb_java-3.3.so</code> to <code>/portal_libraries</code>. Use the <code>wadm</code> command to inform the Web Server about the location of the library files. Get the current native library path setting by typing the following administration CLI command: <pre>get-jvm-prop -user=admin --config=hostname native-library-path-prefix</pre> Save the output. Append the copied <code>libdb-3.3.so</code> and <code>libdb_java-3.3.so</code> path to the existing native library path by typing the following administration CLI command. <pre>set-jvm-prop --config=hostname native-library-path-prefix=<existing native library-path>:</portal-libraries-path></pre> where, <code>portal-libraries-path</code> is the location of where you copied the <code>libdb-3.3.so</code> and <code>libdb_java-3.3.so</code> files in Step 1. If you do not get any results or output for the <code>get-jvm-prop</code> command, at the command prompt, set the <code>native-library-path-prefix</code>: <pre>native-library-path-prefix=</portal-libraries-path></pre> Note – For Windows platform, use <code>';</code> as the separator for <code>native-library-path-prefix</code> parameter as follows: <pre>native-library-path-prefix=<existing native library path>;<portal-libraries-path></pre> For non-Windows platform, use the <code>'</code> as the separator for <code>native-library-path-prefix</code> parameter as follows: <pre>native-library-path-prefix=<existing native library path>:<portal-libraries-path></pre> Deploy the modified configuration by typing the following command: <pre>deploy-config [--user=admin-user] config-name</pre>

TABLE 13 Known Issues in Java ES (Continued)

Problem ID	Description
6504178	Migration logs reports a bogus "root is not a valid user" message on Java ES 5. While migrating from Java ES 4 to Java ES 5 on UNIX platforms, the migration log file reports WARNING: "root is not a valid user". This is incorrect as the "root" user is valid on that host.
6453037	A lot of warnings/info messages displayed at Web Server startup on the standard output instead of routing these messages to the log file.

Web Server Documentation

Web Server Documentation Set

The Web Server documentation set describes how to install and administer the Web Server. The URL for Web Server documentation is <http://docs.sun.com/coll/1653.9>.

For an introduction to Web Server, refer to the books in the order in which they are listed in the following table.

TABLE 14 Web Server Documentation

Document Title	Contents
<i>Documentation Center</i>	Web Server documentation topics organized by tasks and subject
<i>Release Notes</i>	<ul style="list-style-type: none"> ■ Late-breaking information about the software and documentation ■ Supported platforms and patch requirements for installing Web Server
<i>Installation and Migration Guide</i>	Performing installation and migration tasks: <ul style="list-style-type: none"> ■ Installing Web Server and its various components ■ Migrating data from Sun ONE Web Server 6.0 or Sun Java System Web Server 6.1 to Oracle iPlanet Web Server 7.0

TABLE 14 Web Server Documentation (Continued)

Document Title	Contents
<i>Administrator's Guide</i>	Performing the following administration tasks: <ul style="list-style-type: none"> ■ Using the Administration and command-line interfaces ■ Configuring server preferences ■ Using server instances ■ Monitoring and logging server activity ■ Using certificates and public key cryptography to secure the server ■ Configuring access control to secure the server ■ Using Java Platform, Enterprise Edition (Java EE) security features ■ Deploying applications ■ Managing virtual servers ■ Defining server workload and sizing the system to meet performance needs ■ Searching the contents and attributes of server documents, and creating a text search interface ■ Configuring the server for content compression ■ Configuring the server for web publishing and content authoring using WebDAV
<i>Developer's Guide</i>	Using programming technologies and APIs to do the following: <ul style="list-style-type: none"> ■ Extend and modify Web Server ■ Dynamically generate content in response to client requests and modify the content of the server
<i>NSAPI Developer's Guide</i>	Creating custom Netscape Server Application Programmer's Interface (NSAPI) plug-ins
<i>Developer's Guide to Java Web Applications</i>	Implementing Java Servlets and JavaServer Pages (JSP) technology in Web Server
<i>Administrator's Configuration File Reference</i>	Editing configuration files
<i>Performance Tuning, Sizing, and Scaling Guide</i>	Tuning Web Server to optimize performance
<i>Troubleshooting Guide</i>	Troubleshooting Web Server
<i>CLI Reference Manual</i>	Administration commands that allow you to administer the Web Server through the CLI

Documentation, Support, and Training

The Oracle web site provides information about the following additional resources:

- Documentation (<http://docs.sun.com/>)
- Support (<http://www.sun.com/support/>)
- Training (http://education.oracle.com/pls/web_prod-plq-dad/db_pages.getpage?page_id=315)

Searching Oracle Product Documentation

Besides searching Oracle product documentation from the docs.sun.com web site, you can use a search engine by typing the following syntax in the search field:

```
search-term site:docs.sun.com
```

For example, to search for “proxy,” type the following:

```
proxy site:docs.sun.com
```

To include other Oracle web sites in your search (for example, java.sun.com, www.sun.com, and developers.sun.com), use sun.com in place of docs.sun.com in the search field.

Third-Party Web Site References

Third-party URLs are referenced in this document and provide additional, related information.

Note – Oracle is not responsible for the availability of third-party web sites mentioned in this document. Oracle does not endorse and is not responsible or liable for any content, advertising, products, or other materials that are available on or through such sites or resources. Oracle will not be responsible or liable for any actual or alleged damage or loss caused or alleged to be caused by or in connection with use of or reliance on any such content, goods, or services that are available on or through such sites or resources.

Features and Enhancements in Previous Web Server Releases

This section lists the features and enhancements in the following releases:

- “Features and Enhancements in 7.0 Update 8” on page 38
- “Features and Enhancements in 7.0 Update 7” on page 38
- “Features and Enhancements in 7.0 Update 6” on page 41
- “Features and Enhancements in 7.0 Update 5” on page 42

- “Features and Enhancements in 7.0 Update 4” on page 42
- “Features and Enhancements in 7.0 Update 3” on page 43
- “Features and Enhancements in 7.0 Update 2” on page 44
- “Features and Enhancements in 7.0 Update 1” on page 46
- “Features and Enhancements in 7.0” on page 48

Features and Enhancements in 7.0 Update 8

Web Server 7.0 Update 8 contains the following fixes for security vulnerabilities:

Bug 6916389 describes the buffer overflow vulnerabilities in the WebDAV extensions to Sun Java System Web Server. These issues may allow remote clients to trigger a Web Server crash, thus resulting in a Denial of Service (DoS) condition. These issues may also allow remote unauthorized users to gain elevated privileges, enabling them to access and modify sensitive files.

Bug 6916390 describes the format string vulnerabilities in the WebDAV extensions to Sun Java System Web Server. These issues may allow remote clients to trigger a Web Server crash, thus resulting in a Denial of Service (DoS) condition. These issues may also allow remote unauthorized users to gain elevated privileges, enabling them to access and modify sensitive files.

Bug 6916391 describes the buffer overflow issues in the Digest Authentication methods in Sun Java System Web Server, which may allow remote unprivileged users to crash the Web Server, thus leading to a Denial of Service (DoS) condition. These issues may also lead to execution of arbitrary code with elevated privileges.

Bug 6916392 describes the heap overflow issues in the HTTP TRACE functionality in Sun Java System Web Server, which may allow remote unprivileged users to crash the Web Server, thus leading to a Denial of Service (DoS) condition. These issues may also be exploited to gain unauthorized access to sensitive information.

Features and Enhancements in 7.0 Update 7

Web Server 7.0 Update 7 introduces Kerberos/SPNEGO support. This release introduces a new ACL authentication method called `gssapi`. The `gssapi` authentication method works with a Kerberos user repository. This release also introduces a suitable `auth-db` of type `kerberos` for use with the `gssapi` authentication method.

For more information on configuring a Kerberos authentication, see “[Working With the Authentication Database](#)” in *Oracle iPlanet Web Server 7.0.9 Administrator’s Guide*

Note – Kerberos enabled Web Server on Solaris are tested with clients such as IE on Windows 2003 and Firefox on RHEL 5.3.

Web Server 7.0 Update 7 supports Windows 2008 SP2 32 bit (x86) Enterprise Edition.

Web Server 7.0 Update 7 is bundled with JDK 6. There is an improvement in the performance in admin server.

Web Server 7.0 Update 7 is integrated with new Xerces C++ patch which fixes the vulnerability. For more information, see <http://www.cert.fi/en/reports/2009/vulnerability2009085.html>.

Note – Web Server 7.0 Update 7 resolves a regression in LDAP authentication (6888100) accidentally introduced in Update 6. All customers using LDAP authentication are encouraged to upgrade to Update 7.

Deprecated Platforms

Note – Platforms, Solaris 8 and Windows 2000 are deprecated. They will not be supported from Web Server 7.0 Update 9 onwards.

SSL/TLS Vulnerability Fix (CVE-2009-3555)

Web Server 7.0 Update 7 is upgraded to include NSS 3.12.5 which provides relief for the SSL/TLS renegotiation vulnerability: <http://web.nvd.nist.gov/view/vuln/detail?vulnId=CVE-2009-3555>

This vulnerability is a flaw in the current SSL/TLS renegotiation protocol definition. It is not a bug in the Web Server implementation. Due to this reason, there is no implementation-level fix for this vulnerability. The only workaround is to disable renegotiation entirely in order to protect the Web Server from attack.

Therefore, Web Server 7.0 Update 7 disables all use of SSL/TLS renegotiation. If either the client or the Web Server attempt to trigger renegotiation on an existing SSL/TLS session, the connection will fail.

Typically renegotiation was used to obtain a client certificate sometime after the SSL/TLS connection was first established. Web applications which attempt to obtain a client certificate in this fashion will now fail.

Obtaining a client certificate during the initial connection handshake will continue to work correctly. This mode can be configured by setting the `client-auth` element to 'required' in `server.xml`:

```
<http-listener>
  <ssl>
    <client-auth>required</client-auth>
  </ssl>
</http-listener>
```

A future update of Web Server 7 will implement a safe renegotiation protocol as soon as the IETF finalizes the design of the new protocol enhancement. It is possible to re-enable the vulnerable SSL/TLS renegotiation capability by setting the environment variable: `NSS_SSL_ENABLE_RENEGOTIATION=1`. This mode is known to be vulnerable to attack as described in CVE-2009-3555.

Java SE 5.0 and 6.0 Support

Web Server supports the 32-bit version of the Java Platform, Standard Edition (Java SE) 5.0 and Java Platform, Standard Edition (Java SE) 6. For the 64-bit version of Web Server, the 64-bit version of Java Development Kit (JDK) software support is available.

JDK 6.0 Update 17 is delivered on Solaris, Linux and Windows as part of Web Server 7.0 Update 8 release.

The following table lists the JDK versions supported on various platforms:

TABLE 15 Supported JDK Versions

Operating System	Supported Java SE Version	Whether Co-packaged With Web Server	64-bit Support (Yes/No)
Solaris SPARC	1.5.0_22 1.6.0_17	No Yes	Yes
Solaris x86/AMD,AMD64	1.5.0_22 1.6.0_17	No Yes	Yes
Linux (32-bit)	1.5.0_22	No	No
Linux (64-bit)	1.6.0_17	Yes	Yes
Windows	1.5.0_22 1.6.0_17	No Yes	No
HP-UX	1.5.0.16 (1.5.0.12--_21_mar_2008_11_52) 1.6.0.04	No	No
AIX	1.5.0 pap32dev-20080315 (SR7) 1.6.0 pap3260sr1-20080416_01(SR2)	No	No

At the time of installation, you must specify a valid path for the JDK. To use the JDK version that is not co-packaged with the product, download the software from the following location:

JDK version 1.6.0: <http://java.sun.com/javase/downloads/index.jsp>

JDK version 1.5.0: http://www.hp.com/products1/unix/java/java2/jdkjre5_0/index.html

When you use JDK 1.5.0 on AIX platform, Administration server may fail to start and displays an error message “Unable to find/open the administration server's certificate database”. This is due to the restricted security policy on the installed JDK and limiting key size.

For more information about security information on SDKs, see: <http://www.ibm.com/developerworks/java/jdk/security/50/>

You can overcome this problem by downloading unrestricted security policy by clicking on “IBM SDK Policy files”. The downloaded zip file is unpacked and the two JAR files are placed in the JRE directory (`jre/lib/security/`).

Features and Enhancements in 7.0 Update 6

Web Server 7.0 Update 6 is an update release to Web Server 7.0. In addition to the features and enhancements in Web Server 7.0 and Web Server 7.0 Update 1, Update 2, Update 3, Update 4 and Update 5 releases, Web Server 7.0 Update 6 release brings the following value-additional features and enhancements to the product.

New features and enhancements are described in the sections below.

For more information about Binary Logging in Web Server, see *Oracle iPlanet Web Server 7.0.9 Performance Tuning, Sizing, and Scaling Guide*.

Sun Java System Web Server 7.0 Update 6 is integrated with the new NSS (Network Security Services) 3.12.3. This version of the NSS fixes the security alert for [CVE-2009-2404](#).

For more information, see the [NSS 3.12.3 Release Notes \(http://www.mozilla.org/projects/security/pki/nss/nss-3.12.3/nss-3.12.3-release-notes.html\)](http://www.mozilla.org/projects/security/pki/nss/nss-3.12.3/nss-3.12.3-release-notes.html). From the previously mentioned document, you can find more information on the additional environmental variables added in this version.

Sun Java System Web Server 7.0 Update 6 contains both the NSS 3.12.3 and the NSPR 4.7.4 version.

Sun Java System Web Server 7.0 Update 6 has support for the Solaris 8 Branded Zones.

See also — “Features and Enhancements in 7.0 Update 5” on page 42.

Features and Enhancements in 7.0 Update 5

Web Server 7.0 Update 5 is an update release to Web Server 7.0. In addition to the features and enhancements in Web Server 7.0 and Web Server 7.0 Update 1, Update 2, Update 3, and Update 4 releases, Web Server 7.0 Update 5 release brings the following value-additional features and enhancements to the product.

New features and enhancements are described in the sections below.

[“Binary Logging” on page 42](#)

Binary Logging

Binary logging is a functionality introduced in Sun Java System Web Server 7.0 Update 5. This feature allows server information to be stored in a single log file that contains binary, unformatted log data of all the web sites hosted on a server. It thus minimizes the usage of system resources used for logging, may improve performance and scalability, and at the same time records detailed log information.

Features and Enhancements in 7.0 Update 4

Web Server 7.0 Update 4 is an update release to Web Server 7.0. In addition to the features and enhancements in Web Server 7.0 and Web Server 7.0 Update 1, Update 2, and Update 3 releases, Web Server 7.0 Update 4 release brings the following value-additional features and enhancements to the product.

New features and enhancements are described in the sections below.

[“REQUEST_URI and SCRIPT_FILENAME Support” on page 42](#)

[“default-sun-web.xml Support” on page 42](#)

[“OpenSolaris 2008.11 Support” on page 43](#)

REQUEST_URI and SCRIPT_FILENAME Support

This Web Server update release includes addition of environment variables REQUEST_URI and SCRIPT_FILENAME in CGI and FastCGI subsystems. These variables are set by default for both CGI and FastCGI on Apache and are used by many PHP applications including WordPress.

For more information on issues related to these variables, see Problem ID 6785490 in [“Core” on page 22](#).

default-sun-web.xml Support

default-sun-web.xml support has been provided in Web Server Update 4 release. For Admin server's LDAP authorization, default-sun-web.xml support is necessary and this will enable the group Id's to be configured.

OpenSolaris 2008.11 Support

OpenSolaris 2008.11 support has been provided in Web Server Update 4 release, OpenSolaris 2008.11 is the latest release of OpenSolaris Operating System, a powerful, secure, stable, highly scalable, and complete operating environment for users, developers, and deployers.

Package Requirements

For installing Sun Java System Web Server 7.0 Update 4 or higher in the OpenSolaris OS, you must install the following additional IPS packages from the repository:

- SUNWpkgcmds
- SUNWmfrun
- java-dev

Features and Enhancements in 7.0 Update 3

Web Server Update 3 is an update release to Web Server 7.0. In addition to the features and enhancements in Web Server 7.0 and Web Server 7.0 Update 1 and Update 2 releases, Web Server 7.0 Update 3 release brings the following value-additional features and enhancements to the product.

New features and enhancements are described in the sections below.

[“AIX Platform Support” on page 43](#)

[“Auto-Deploying Web Applications” on page 43](#)

AIX Platform Support

AIX 5.3 and 6.1 platform support has been provided in Web Server Update 3 release.

Auto-Deploying Web Applications

This Web Server update release introduces auto-deployment functionality that enables you to deploy one or more web applications, just by copying them to a designated directory. The server auto-deploys web applications that are in the form of web archives (.war files) or in a directory in which a web archive has been exploded.

For more information about auto-deployment feature in Web Server, see [“Auto-Deploying Web Applications”](#) in *Oracle iPlanet Web Server 7.0.9 Developer’s Guide to Java Web Applications*.

Features and Enhancements in 7.0 Update 2

Web Server Update 2 is an update release to Web Server 7.0. In addition to the features and enhancements in Web Server 7.0, and Web Server 7.0 Update 1 releases, Web Server 7.0 Update 2 release brings the following value-additional features and enhancements to the product.

New features and enhancements are described in the sections below.

“PKCS#11 Bypass Support” on page 44

“Service Management Facility (SMF) Support” on page 44

“Asynchronous Accelerator Cache Support” on page 45

“Enhanced Web Container” on page 45

“Improved Administration Experience” on page 45

“Red Hat 4.0 64-bit Support” on page 46

“NetBeans 6.5 IDE Support” on page 46

PKCS#11 Bypass Support

This Web Server update release introduces an option to instruct NSS to bypass the PKCS#11 layer during parts of the SSL/TLS processing. Bypassing the PKCS#11 layer improves performance. By default, the PKCS#11 layer is bypassed. At the time of server startup, the server queries each token holding a server key to verify that each token can support PKCS#11 bypass. If any of the tokens cannot support bypass, bypass is disabled. Therefore, no user action is required to take advantage of the performance benefits of the PKCS#11 bypass. The server automatically takes advantage of the bypass and automatically disables the bypass if the token cannot be used given the current configuration. For more information, see *Oracle iPlanet Web Server 7.0.9 Administrator's Configuration File Reference*.

Web Server provides Command Line Interface (CLI) and Admin Console support to enable or disable the bypass. For more information about how to enable or disable PKCS#11 bypass using the Admin Console or the CLI, see “To Enable and Bypass PKCS#11 Tokens” in *Oracle iPlanet Web Server 7.0.9 Administrator's Guide*.

Service Management Facility (SMF) Support

This Web Server update release integrates with the Solaris 10 Service Management Facility (SMF) for the Java platform. SMF is a new feature of the Solaris Operating System that creates a supported, unified model for services and service management on each Solaris system. It is a mechanism to define, deliver, and manage long-running application services for Solaris. A service is defined by a service manifest, an XML file which describes a service and any instances associated with that service.

For more information about SMF support in Web Server, see the “[Integrating Service Management Facility for the Java Platform with Web Server](#)” in *Oracle iPlanet Web Server 7.0.9 Administrator’s Guide*.

Asynchronous Accelerator Cache Support

This release of Web Server supports processing of requests that can be served from the accelerator cache asynchronously thereby improves the performance of the server. Value added features are:

- Handle dynamic reconfiguration
- Introduced flag `AsyncAccelerator` in the `magnus.conf` to turn off async cache.
- Requests are serviced through asynchronous accelerator to stats
- Batch up access log writes when requests are serviced by asynchronous accelerator

Enhanced Web Container

This Web Server update release introduces the ability to display the exception stack trace or JSP compiler errors in a browser. In the earlier releases of Web Server, when an exception occurs in the servlet container at the request time, a "Server Error" is displayed at the client without exposing internal application details. The exception is always logged in the error log with or without this feature enabled.

Note – Displaying exception stack trace or JSP compiler errors in a browser feature is not enabled by default. You can enable this feature through `set-servlet-container-prop` command or through the Display Exception checkbox in the Servlet Container tab of the Admin Console. This is useful for development purposes. It is strongly recommended not to enable this feature in production systems.

Improved Administration Experience

Administration experience is improved in this release of Web Server by introducing the following key features:

Roll Back Deployed Configuration Support

Web Server supports rolling back of deployed configuration. Web Server administration now enables administrators to take backups automatically on every deployed configuration. Using the administration CLI, it is possible to list backups and restore a specified backup.

Support To Set Administration Server Password

This release of Web Server enables you to reset the administration server's user password. However, this functionality works only locally on the administration server's node.

Support for Managing CA Certificates

Administration Console enables you to install, delete, filter CA certificates, Cert chain, and the CRLs. Additionally, the server also warns the users about the certificates that are about to expire.

For information about the administration features, see the [Oracle iPlanet Web Server 7.0.9 Administrator's Guide](#).

Red Hat 4.0 64-bit Support

Support for a 64-bit standalone version of Web Server is provided in this release. Web Server 7.0 64-bit Linux is a separate standalone only distribution and does not coexist with Web Server 7.0 32-bit Linux. Web Server 7.0 64-bit Linux requires 64-bit Java Development Kit 5.0 Update 12 or above. Both Administration Server and server instance are only 64-bit server. Migration from previous releases is not supported on Web Server 7.0 64-bit for Linux.

NetBeans 6.5 IDE Support

This update release of Web Server provides support to connect to the NetBeans 6.5 IDE and allows users to develop, debug, and deploy applications to the web server. The NetBeans plug-in can be downloaded from the update center using the NetBeans 6.5 IDE.

Note – In addition to the support for NetBeans 6.5 IDE, Web Server provides support for NetBeans 6.1, 6.0, and 5.5.1 versions of the IDE.

Features and Enhancements in 7.0 Update 1

Web Server 7.0 Update 1 is an update release to the major release of Web Server 7.0.

In addition to the features and enhancements in Web Server 7.0 listed later in these release notes, Web Server 7.0 Update 1 supports the Java Platform, Enterprise Edition (Java EE) 5.0 and Web 2.0 technologies. The details of these features and enhancements are described in the sections below.

- “Java Servlet 2.5 and JavaServer Pages (JSP) 2.1 Support” on page 47
- “JavaServer Pages Standard Tag Library 1.2 and JavaServer Faces 1.2 Support” on page 47
- “Accelerator Cache Technology” on page 47
- “Administration Support for Configuring FastCGI” on page 47
- “NetBeans Support” on page 48
- “Admin Console Support for Configuring Regular Expressions” on page 48
- “GUI and CLI Support for Pattern Matching” on page 48

Java Servlet 2.5 and JavaServer Pages (JSP) 2.1 Support

Web Server includes a Java Platform, Enterprise Edition (Java EE) 5 compliant implementation of the Java Servlet 2.5 and JavaServer Pages (JSP) 2.1 technology specifications. Web Server provides the flexibility and reliability needed to design and deploy web applications that comply with Java technology standards.

Java Servlet technology provides web developers with a simple, consistent mechanism for extending the functionality of a Web Server and for accessing existing business systems. JSP technology provides a simplified and a fast way to create dynamic web content. JSP technology enables rapid development of web-based applications that are server and platform-independent.

For information about these technologies, see <http://java.sun.com/javaee/5/docs/tutorial/doc/>.

JavaServer Pages Standard Tag Library 1.2 and JavaServer Faces 1.2 Support

The JavaServer Pages Standard Tag Library 1.2 provides custom tags that encapsulate core functionality common to many web applications. JavaServer Pages Standard Tag Library has support for common, structural tasks such as iteration and conditionals. It provides tags for manipulating XML documents, internationalization tags, and SQL tags. It also provides a framework for integrating existing custom tags with JavaServer Pages Standard Tag Library tags.

Web Server supports JavaServer Faces technology. JavaServer Faces is a user interface framework for building web applications.

For information about these technologies, see: <http://java.sun.com/j2ee/1.4/docs/tutorial/doc/index.html>.

Accelerator Cache Technology

Web Server includes new accelerator cache technology that speeds the delivery of small files. The accelerator cache is automatically enabled and requires no configuration. For more information, see “[File Cache Statistics Information](#)” in *Oracle iPlanet Web Server 7.0.9 Performance Tuning, Sizing, and Scaling Guide*.

Administration Support for Configuring FastCGI

You can configure a single FastCGI application using the Admin Console as well as the Command Line Interface (CLI). You can also configure the FastCGI with Web Server using the configuration files.

To configure multiple FastCGI applications, see “[Configuring Multiple FastCGI Applications](#)” in *Oracle iPlanet Web Server 7.0.9 Administrator’s Guide*.

NetBeans Support

Web Server provides plug-ins to integrate with the NetBeans Integrated Development Environment (IDE) for deploying and debugging web applications. NetBeans is a complete development environment to create Java Platform Enterprise Edition (Java EE) based web applications with the standard components.

In addition to the deployment of web applications, the plug-in also provides support for the following activities:

- Manage instances, such as start or stop server instances
- Enable or disable applications
- Create server wide resources, such as JDBC resources and JDBC connection pools

For information about NetBeans, see: <http://www.netbeans.org/kb/index.html>.

For more information about using NetBeans with Web Server, see: <http://webserver.netbeans.org>.

Admin Console Support for Configuring Regular Expressions

Web Server provides support for writing regular expressions within the `obj.conf` file through the Admin Console. However, writing regular expressions through the Admin Console is limited to the form of `<If> . . </If>` conditions for URL redirects.

For more information on using the Admin Console for writing regular expressions, see the *Oracle iPlanet Web Server 7.0.9 Administrator's Guide*.

GUI and CLI Support for Pattern Matching

Web Server provides support for configuring the URIs, URI prefixes, URI wildcard patterns properties through the Admin Console and the Admin CLI.

For more information on using the Admin Console for configuring URI pattern properties, see the *Oracle iPlanet Web Server 7.0.9 Administrator's Guide*.

For more information on using the CLI commands for configuring URI pattern properties, see the *Oracle iPlanet Web Server 7.0.9 CLI Reference Manual*.

Features and Enhancements in 7.0

Web Server can be configured to run as a 64-bit application on the Solaris, SPARC and AMD64 platforms.

Web Server provides comprehensive command-line interface support, consolidated configuration, enhanced security with elliptic curve cryptography support, and clustering support. It also comes with a robust built-in migration tool that helps migrate applications and configurations from Web Server 6.0 and Web Server 6.1 to Web Server 7.0.

Oracle iPlanet Web Server includes the following new features:

- “JMX Based Management Infrastructure” on page 49
- “Redesigned Administration Server Interface” on page 49
- “Command-Line Interface Support” on page 50
- “Sun N1 Service Provisioning System Support” on page 50
- “Consolidated Configuration Files” on page 50
- “JNDI Support” on page 51
- “Java Database Connectivity and Connection Pooling Support” on page 51
- “Enhanced Hardware Accelerator Encryption Support” on page 51
- “Integrated Java Web Services Developer Pack 2.0 Technologies” on page 51
- “Lightweight Session Replication Support” on page 52
- “URL Redirection and Rewriting with Regular Expressions” on page 52
- “Extensive Real-Time Monitoring Support” on page 52
- “Integrated Reverse Proxy” on page 53
- “Enhanced Security” on page 53
- “Elliptic Curve Cryptography Support” on page 54
- “Oracle Java Studio Enterprise Support” on page 54
- “Localization Support” on page 55

JMX Based Management Infrastructure

Web Server management infrastructure is based on the modern distributed Java Management Extensions (JMX) technology. JMX technology provides tools for building distributed, web-based, modular and dynamic solutions for managing and monitoring devices, applications, and service-driven networks. JMX helps to manage and monitor instances, configurations, and web applications across clustered Web Server deployments.

Redesigned Administration Server Interface

The Administration Server is a specially configured Web Server instance on which the administration applications are deployed. An administration instance runs on each node in the server farm. Of these nodes, one node is configured to be the Administration Server and the rest are configured to be Administration Nodes.

The web-based Administration Server is redesigned to make common tasks easier to access and complex tasks easier to accomplish.

The Administration Server includes the following new features:

- Web-based wizards for performing most common tasks
- Comprehensive command-line interface (CLI) support for server configuration and server administration tasks
- Centralized configuration store
- Support for deploying Web Server configuration information on multiple machines. This feature extends to support Web Server in a server farms and clusters.

- Built-in management and monitoring of server clusters

For more information on using the administration interface to perform administrative tasks, see the [Oracle iPlanet Web Server 7.0.9 Administrator's Guide](#).

Command-Line Interface Support

The command-line interface enables you to easily configure and administer the server.

The administration CLI has the following key features:

- Embedded Java Command Language (j a c l) shell for scripting
- Extensible CLI, which enables you to add more commands by using the third-party plug-ins
- Support for local and remote administration, configuration, and management of one or more server instances
- Automatically completes commands when you type one or more characters and then press a tab key
- Easy-to-use CLI-based operational modes including single mode, shell mode, and file mode

For more information on the commands, see the [Oracle iPlanet Web Server 7.0.9 CLI Reference Manual](#).

Sun N1 Service Provisioning System Support

Web Server is integrated with Sun N1 Service Provisioning Server 5.2. Sun N1 Service Provisioning System is an application provisioning tool that eliminates the need for custom scripts. With the integration of Web Server with Sun N1 Service Provisioning System, as an administrator, you do not need to write custom scripts for installing multiple Web Servers in a datacenter environment or in a server farm.

Consolidated Configuration Files

Configuration files in Web Server are rearranged and consolidated to simplify administration.

In the earlier versions of Web Server, the configuration files in `userdb` were shared by all instances, while the information contained in these files was often instance-specific. In Web Server 7.0, configuration files from the `userdb` directory are removed. Their functionality is incorporated into the `server.xml` file in the `config` directory. Configuration files from the `alias` and `httpacl` directories are moved into the `config` directory. These changes consolidate instance-specific configuration information within the instance-specific `config` directory.

For information about the configuration files, see the [Oracle iPlanet Web Server 7.0.9 Administrator's Configuration File Reference](#).

JNDI Support

The Java Naming and Directory Interface (J.N.D.I.) API provides seamless connectivity to heterogeneous enterprise naming and directory services.

Java Database Connectivity and Connection Pooling Support

Web Server provides out-of-the-box, seamless Java DataBase Connectivity (JDBC), technology and supports a wide range of industry-standard and customized JDBC drivers.

Web Server supports JDBC connection pooling, that is, a group of reusable connections for a particular database. Because creating each new connection is time consuming, the server maintains a pool of available connections to increase performance. When an application requests a connection, it obtains a connection from the pool. When an application closes a connection, the connection is returned to the pool.

For information on creating JDBC connection pools, see the *Oracle iPlanet Web Server 7.0.9 Administrator's Guide*.

Enhanced Hardware Accelerator Encryption Support

Sun Java System Web Server 7.0 provides hardware accelerator support for Sun Crypto Accelerator 4000 and 6000 boards, which enhance the performance of SSL on web server.

Note – Initialize the Sun Crypto Accelerator card when using with web server. For more information about Sun Crypto Accelerator, see *Sun Crypto Accelerator 6000 Board Version 1.1 User's Guide* at <http://docs.sun.com/source/820-4144-11/>.

Integrated Java Web Services Developer Pack 2.0 Technologies

Web Server includes Java Web Services Developer Pack (Java WSDP) 2.0 and XML technologies. Web services developed by using Java WSDP can be deployed on Web Server as a web application by using the `wadm` command.

Web Server 7.0 provides support for security features such as XML Encryption, XML Digital Signature, and support for message security provider.

For more information on Java WSDP 2.0, see the following resource:

<http://java.sun.com/webservices/jwsdp/index.jsp>

Java WSDP 2.0 samples are located at the following location. These samples can be deployed on Web Server 7.0.

http://java.sun.com/webservices/downloads/2.0_preview_webservicespack.html

Lightweight Session Replication Support

Web Server supports cluster-based session replication and failover. Session replication and failover provides high availability to web applications by replicating HTTP sessions from one server instance to another in the same server cluster. Because each HTTP session has a backup copy on a remote instance, a server failure that renders one instance in the cluster unavailable does not disturb session continuity.

For more information on Light Weight Session Replication support, [Oracle iPlanet Web Server 7.0.9 Administrator's Guide](#).

URL Redirection and Rewriting with Regular Expressions

Web Server 7.0 introduces enhanced support for regular expressions and conditional processing in the `obj.conf` configuration file.

Key enhancements include the following:

- Support for regular expressions
- A restart Server Application Function (SAF) for restarting requests with a new URI
- Support for dynamic SAF parameters that include expressions, variables, regular expression back references
- `<If>`, `<ElseIf>`, and `<Else>` tags for conditional processing
- Support for complex conditions that use `and`, `or`, and `not` operators
- `sed-request` and `sed-response` filters for rewriting request and response bodies

You can use these new features to define flexible URL rewriting and redirection rules such as those possible with `mod_rewrite` from the Apache HTTP server. Unlike `mod_rewrite`, regular expressions and conditional processing in Web Server 7.0 can be used at any stage of request processing, even with third-party plug-ins.

For more information on regular expressions and URL rewrite functions, see the [Oracle iPlanet Web Server 7.0.9 Administrator's Configuration File Reference](#).

Extensive Real-Time Monitoring Support

In addition to the monitoring facilities in earlier versions of Web Server, Web Server adds the following enhancements:

- Monitors Servlets, JSPs, and JavaServer Pages Standard Tag Library container characteristics
- Monitors process and virtual server statistics from within the Administration Server
- Integrates with System Management Agent on the Solaris 10 platform. Integrates with the Java Enterprise System Monitoring Framework (Java ES Monitoring Framework) that makes Web Server monitoring information available within the Java ES Monitoring Framework.

- Accesses monitoring data as Management Beans (MBeans) using the Java Monitoring and Management Console (`jconsole`) script, Java ES Monitoring Framework or any Java Management Extensions (JMX) compliant client applications.

For more information on Monitoring feature in Web Server, see the [Oracle iPlanet Web Server 7.0.9 Administrator's Guide](#).

Integrated Reverse Proxy

Sun Java System Web Server 7.0 integrates the reverse proxy functionality within the core server.

When web server is configured with reverse proxy functionality, it acts as a proxy for one or more backend servers and serves as a single point of access or gateway in a server farm. In a reverse proxy setup, the web server forwards the HTTP request it received from the browser client to the appropriate backend server. The HTML response from the backend server is sent back to the browser through the web server. Thus, the web server with reverse proxy hides the existence of backend servers to the browser.

Web Server provides GUI and CLI support for configuring the reverse proxy.

For information about configuring reverse proxy, see “[Configuring Reverse Proxy in Web Server](#)” in [Oracle iPlanet Web Server 7.0.9 Administrator's Guide](#).

Enhanced Security

Web Server supports a wide variety of technologies that allow data encryption and validation, request authentication, and server process protection. Key security feature enhancements include the following:

- Solaris 10 platform cryptographic framework support. For example, `libpkcs11.so` including support for UltraSPARC T1 processor hardware acceleration.
- Denial of Service (DoS) attack protection enhancements.
- Cross site scripting protection through the native `sed(1)` based input filtering. For information about cross site scripting, see “[Preventing Cross Site Scripting Attacks](#)” in [Oracle iPlanet Web Server 7.0.9 Administrator's Guide](#).
- Web services security:
 - IETF XML Digital Signature
 - W3C XML Encryption
- Integrated Platform for Privacy Preferences (P3P) support.
- Web-based Distributed Authoring and Versioning (WebDAV) access control support.
- The Lightweight Directory Access Protocol (LDAP) `auth-db` is enhanced to make search expressions and match attributes configurable.
- The LDAP `auth-db` supports Microsoft Active Directory interoperability.

- Support for migration of certificate from Tomcat or other Java keystore file based repositories.
- Support for dynamically applied Certificate Revocation Lists (CRLs).
- Integrated IPv6 support.

Elliptic Curve Cryptography Support

Sun Java System Web Server has always supported RSA keys. In addition to the continued support for RSA keys, Web Server 7.0 introduces support for Elliptic Curve Cryptography (ECC).

ECC is the next generation of public-key cryptography for mobile or wireless environments. ECC is based on a set of algorithms for key generation, encryption, and decryption for performing asymmetric cryptography.

For more information on how to use ECC in Web Server, see the [Oracle iPlanet Web Server 7.0.9 Administrator's Guide](#).

Oracle Java Studio Enterprise Support

Web Server 7.0 supports Oracle Java Studio Enterprise 8.1. Oracle Java Studio software is a powerful, extensible IDE for Java technology developers, based on the NetBeans software and integrated with the Java platform.

The plug-in for the Web Server can be obtained in the following ways:

- From the companion CD in the Sun Java System Web Server Media Kit
- By using the companion *AutoUpdate* feature of Oracle Java Studio
- From the download center for Sun Java System Web Server

Note – Oracle Java Studio 8.1 plug-in for Web Server works only with a local web server. That is, the IDE and the web server must be installed on the same machine.

For information about using the web application features in Oracle Java Studio 8.1, see the following tutorial:

<http://developers.sun.com/prodtech/javatools/jsenterprise/learning/tutorials/index.jsp>

For more information about Oracle Java Studio 8, visit:

<http://www.sun.com/software/sundev/jde/>

Localization Support

Web Server is available in the following languages:

- French
- German
- Spanish
- Japanese
- Simplified Chinese
- Traditional Chinese
- Korean

Issues Resolved in Previous Web Server Releases

This section lists the important issues fixed in the following releases:

- [“Issues Resolved in 7.0 Update 8”](#) on page 55
- [“Issues Resolved in 7.0 Update 7”](#) on page 56
- [“Issues Resolved in 7.0 Update 6”](#) on page 57
- [“Issues Resolved in 7.0 Update 5”](#) on page 58
- [“Issues Resolved in 7.0 Update 4”](#) on page 60
- [“Issues Resolved in 7.0 Update 3”](#) on page 63
- [“Issues Resolved in 7.0 Update 2”](#) on page 69
- [“Issues Resolved in 7.0 Update 1”](#) on page 71

Issues Resolved in 7.0 Update 8

This section lists the issues resolved in Sun Java System Web Server 7.0 Update 8.

Problem ID	Description
6916391	Digest authentication buffer overflows.
6916392	TRACE heap overflow.
6916390	WebDav format string bug.
6916389	WebDav stack overflow.
6917879	TRACE request with empty header names can cause malformed responses.
6930175	Web Server 7.0 Update 8 supports Windows 2008 Standard Edition Service Pack 2 32-bit(x86).

Issues Resolved in 7.0 Update 7

This section lists the issues resolved in Sun Java System Web Server 7.0 Update 7.

Problem ID	Description
6888100	While migrating from Web Server 7.0 Update 5 to Update 6, the LDAP authentication fails because rebind is not done after password validation.
6898371	Severe TLS/SSL protocol vulnerability. It requires NSS upgrade
6811286	Admin GUI becomes unresponsive when large web application has been deployed.
6849009	When using the admin gui or CLI to list the certificates using <code>CertificateMgrUtil</code> in Web Server 7.0 Update 4 and Web Server 7.0 Update 5, it can take over 60 seconds to perform the listing.
6855262	Web Server runs out of FILEs when using ≥ 128 vcpus
6855513	In Web Server 7.0 Update 7, the <code>thread-pool</code> auto configuration algorithm is broken.
6857815	Kerberos/SPNEGO support was added.
6867192	Web Server 7.0 Update 7 documents auto configuration feature for configuring the web servers <code>max-threads</code> , <code>thread-pool queue-size</code> , and <code>keep alive max-connections</code> .
6869991	Xerces C library has a vulnerability.
6880214	Web Server 7.0 needs to bundle JDK 6 instead of JDK 5 as JDK 5 is getting EOSL-ed.
6881339	Server crashes if async request is aborted by keep alive thread (if stats is turned on).
6882830	Single-Sign-on (SSO) for FORM authenticated application, the <code>JSESSIONIDSSO</code> cookie is not set.
6887782	If <code>PR_GetSockName</code> fails, then <code>Connection::create</code> will return failure and then the connection gets added in both unused and Ready Queue.
6741844	In Web Server 7.0 session failover doesn't happen after "Invalid Sequence Number" exception is thrown.
6763470	LDAP group authentication from Microsoft Active Directory fails if user name has a "," in between.
6815996	Web Server 7.0 Update 4 64 bit crashes when accessing a file in a directory that has a <code>.htaccess</code> file.
6830258	Web Server closes the Keep alive connections much before keep alive timeout (poor QoS on Specweb on Linux).
6841548	The <code>flexlog.cpp</code> code is optimized.
6849198	The URLs of server side include files work after "/" is appended to URL.

6857790	Admin server's auto tuning of threads takes lots of resources on CMT systems.
6873985	Web Server 7.0 Update 7 documents the list of unsupported file formats that can't be indexed and searched.
6875450	Web Server 7.0 Update 4 core patches (SPARC, x86) includes the localization patch "126332-06" in SUNW_REQUIRES field.
6877764	Web Server 7.0 Update 7 will not return Content - type: text/html when there is no message body.
6878259	Webstack PHP support for Sun Web Server 7.0 Update 7.
6885643	Web Server 7.0 <code>classdebuginfo</code> set to false is not working with JDK6.
6897071	Web Server 7.0 Update 6 - Admin GUI shows null in NODES when installed with external JDK.
6567720	Enhances admin framework to support enabling Kerberos authentication.
6853924	Web Server 7.0 Update 7 states that when renewing a certificate the key size can be changed.
6854885	Web Server 7.0 CA-signed certificate created through admin GUI is not associating the certificate with listener.

Issues Resolved in 7.0 Update 6

This section lists the issues resolved in Sun Java System Web Server 7.0 Update 6.

Problem ID	Description
6854841	Web Server 7 appears to ignore any attempt at configuring the " <code>classdebuginfo</code> " in <code>sun-web.xml</code> .
6813426	Detailed error message should be logged when adding of PDF documents to search collection fails.
6801517	Virtual server creation will fail if there is a trailing space in the "Name" or "Hosts" fields.
6809090	Self-signed certificate should use SHA1 as signature algorithm.
6856484	Error while renewing a certificate in Sun Metaslot.
6847901	Web Server should bundle the latest SASL.
6707244	Race condition in the JVM when deploying a web application that contains a logger.
6856472	<code><request-header-timeout></code> should default to 30 from -1.
6826625	Remove the Localization package/patch dependency check in the <code>checkinstall</code> script.
6781962	Favicon does not show up correctly in Internet Explorer 7.

6749879	LDAP authentication fails with Directory Proxy server where anonymous authentication is set to false.
6806858	ACL vulnerability (when dynamic group is used) allows non-authorized user to login.
6811110	LDAP update in the Administration GUI fails if LDAP is a Directory Server consumer.
6832878	In the Administration Console, the new configuration wizard text has to be improved.
6801700	When configuring the error code for request limits, there is no mention of valid values.
6814138	Last Modified date and the creation dates are incorrectly displayed in PROPFIND.
6856456	Last line of installation log file points to itself. The end of the log file has reference to the same file for more information.
6834762	In certain scenarios, "Unable to connect to the node host" error from the Administration Server.
6848803	CLI page for add-webapps and Admin Guide's page titled 'Deploying Java Web Applications' should be updated.
6828720	use-responseCT-for-headers should be documented.
6827940	Support for FastCGI suid environment on RHEL5.0 in Web Server 7.0
6809081	Sample application documentation must say that Admin server must be started for ant deploy to be successful.
6860680	Windows vulnerability — Appending " : \$DATA" to the file extension discloses the contents of JSP page.
6841507	Document typo in Sun Java System Web Server 7.0 U5 Administrator's Configuration File Reference Guide.
6834770	Very little information about virtual-server-name_obj.conf in documentation.
6839431	ADMIN4159 error while renewing a certificate in Sun MetaSlot.
6842383	Document the configuration settings necessary to get the FastCGI suid environment working for the different OS platforms.
6841454	CSR generated while renewing a CA-signed certificate needs formatting in GUI.

Issues Resolved in 7.0 Update 5

This section lists the issues resolved in Sun Java System Web Server 7.0 Update 5.

Problem ID	Description
6732548	create-fastcgi-handler does not work as expected when value of app-args is specified as "a=b" or "c=d" .

6750707	Admin CLI does not accept input strings that has multibyte characters.
6723824	Migration from the previous versions of Web Server to Web Server 7.0 Update 3, resulted in unusual migration log files, although the migration of instance was successful.
6764940	<p>obj-https-INSTANCE.conf is different from obj.conf.</p> <p><https-instance>-obj.conf gets created when a first change is made to obj.conf from admin server GUI or CLI. This situation occurs only if the Client tag is added, before this first change is made to the instance configuration through admin server. Once the <https-instance>-obj.conf is created, the same steps does not simulate this phenomenon.</p>
6765451	<p>The admin server adds the check-request-limits function at an invalid location in obj.conf.</p> <p>While configuring check-request-limits function to obj.conf, you should ensure that it is inserted before find-index function.</p>
6769410	<p>Variables are removed from server.xml.</p> <p>The null values for the CGI variables names, of a migrated instance, cannot be saved in the admin GUI. Hence they are removed from the server.xml.</p>
6772188	Web Server 7.0 Admin GUI, throws the following error when Java is disabled- "BreadCrumbsModel: index out of bounds 1".
6709085	<p>Admin server fails to start.</p> <p>The admin tools allow default language to be set to zh_cn, after which the server will not start and throws an error:</p> <pre>config:CONF1104:File /sun/webserver7/https-agc184.PRC.Sun.COM/config/server.xml line 98: Invalid <default-language> value:zh_cn</pre>
6759756	Permission error occurs while uploading a .war file using the admin GUI.
6762245	Usage of blank spaces while creating a new configuration, using admin GUI, throws an error.
6777195	The setNodeProperties in NodeMBean always rewrites the server-farm.xml. While rewriting, it converts the host name entry of the node to lowercase.
6772231	The admin server hangs during startup or configuration listing or any activity that is not directly on the instance or node.
6780377	The Web Server 7.0 Admin server fails to recognize the reason parameter of send-error SAF.
6793862	The Admin server fails to recognize Extended Validation SSL Server Certification.
6798954	Web Server should support binary logging.
6542360	Setting java-home of admin server does not propagate the settings to admin scripts.

6781234	Web Server 7.0 has a problem while using JSTL tlds and jaxp.
6790392	Web Server 7.0 Update 3 displays a blank screen as a response to maxSessions, instead of an error response.
6768357	NSAPI functions like vs_get_mime_type crashes Web Server for internal non-HTTP requests.
6776108	Increase MaxKeepAliveThread limit from 128 to 256.
6781976	Require binary logging, as access logging is affecting performance.
6806781	%Req->reqpb.clf-request.protocol.version% is not set properly in binary mode and hence binlog throws an error.
6707017	Web server setup fails when a localized directory is specified for document root.
6753741	Web Server installer throws a “PatchListener-Solaris-detectPatches-Failed” error under certain circumstances.
6774822	During unconfigureServer process a warning message “WARNING: ADMIN2028: Error removing init scripts” is displayed in case of AIX.
6775953	Update Web Server plugin to work with Netbeans 6.5.
6722375	Patches 125437-14 and 125438-14 are not alternate root compliant.
6779166	Web Server 7.0 Update 3 does not scale well on Windows, when compared to Apache.
6781147	Web Server 7.0 Update 3 throws an error while trying to create a new search event by Japanese encoding.
6761027	In Web Server 7.0, wildcard pattern matching for ACL does not work properly with IP addresses.
6775403	REQUEST_HEADERS: '/ regular expression /' does not work properly.
6773327	Enabling sendfilev for JSP applications can cause the server response to fail.
6775948	<p>Include file missing in nsapi.h throws a warning message while compiling some NSAPI modules.</p> <p>Workaround:</p> <p>Add include <netdb.h> before nsapi.h.</p>

Issues Resolved in 7.0 Update 4

The following table lists the issues resolved in Sun Java System Web Server 7.0 Update 4.

Problem ID	Description
------------	-------------

6708647	Set environment variables REQUEST_URI and SCRIPT_FILENAME in CGI and FastCGI subsystems.
6715164	When starting a server instance that has a long running plugin initialization, the Admin server process produces high CPU load.
6740996	Incompatibility with Reuters IFP leads to server crash.
6747181	Renewed/new certificates are not utilized after configuration is deployed and restarted.
6620166	Session failover behaves incorrectly when two NICs are active on deployed nodes.
6663982	default-sun-web.xml is not referenced.
6707017	Setup fails when a localized directory is specified for Document Root.
6708894	The new Virtual Server wizard does not allow non-ASCII characters.
6712479	When using a LDAP authentication database, with a base DN having UTF8 characters, it causes an error such as: ADMIN3143: Base DN 'ou=k?v?nok,dc=red,dc=iplanet,dc=com' does not exist
6713238	Web Server 7.0 Update 2 shows an error on startup, when the document root directory name ends in a .war.
6713786	When upgrading Web Server 7.0 Update 2 to Update 3, some no longer required files are left behind.
6714230	CgiStub exhibits unstable behavior when freeing file descriptors on Solaris.
6716553	An error is reported when creating a certificate with some Country selections.
6717187	State is sometimes not properly referenced when configuring new server configurations.
6717328	The registration page in setup displays very small text fields.
6718752	Upgrades from previous Update releases fail, if there exists a file named https-<instancename>.
6721107	Administration server does not startup on a new Java Enterprise System installation.
6721193	When deploying a web application using Admin GUI, the target directory is ignored if the file is on the server.
6722701	Silent install fails if CONFIGURE_LATER is set to true. CONFIGURE_LATER=true
6722702	unconfigureServer is required when server is configured in configure later mode.
6722727	Create service in Admin GUI allows you to create a new service, even when the service already exists.

6724246	<p>An incorrect error message is displayed in Admin GUI while saving the "Forward Parameters" as below:</p> <p>Child 'from_hidden' does not have a registered descriptor in 'editReverseProxyPS1'</p>
6728160	htaccess can cause server crashes.
6729296	Temporary directory of the Admin server /tmp/admin-server-xxx with /tmp/admin-server-xxx/configname/extracted/config/server.xml file is not being deleted, during a ./admin-server/bin/stopserv.
6731124	If a request is wrapped by a servlet or filter and forwarded to a static resource, an incorrect error HTTP 405 is returned.
6740786	<If> statements can corrupt the obj.conf files in the Admin Server.
6714929	SNMP is not compatible with default tcp_hiwat setting on Solaris 10.
6741649	In Update 2, the output of get-perfdump should not include sessions that are in keep alive mode.
6743019	<p>When using Admin GUI in French locale the error message does not give the nodename during deployment, as shown below:</p> <p>The administration server has detected that you have modified some of the instance configuration files on the following nodes: \{0\}.</p>
6751264	In the French and Japanese locale Admin GUI, Sun Online account signup form for registration is not being properly displayed.
6760687	The Administration server does not always display the latest certificate.
6765564	The online installer help does not properly reflect removal of language packs from the installer component panel.
6766109	Creating a new configuration with CGI Enabled as File Type causes a failure.
6629611	Toggle state in some Admin server tables is incorrect.
6633333	Links do not point to localized sun.com sites.
6608135	Search engine fails with an error, when a html document with title contain characters like A&B.
6705752	The Admin GUI does not allow server header to be suppressed.
6708548	Provide consistent translations in German locale.
6709378	Inconsistency exists between button in a description and button's label.
6709427	A part of the table title in logviewer is corrupted.
6711035	Part of the French translation on Web Server parameters page is cut off.
6711518	Inconsistent translation of "Core Server" in French locale.

6712045	Button labels and Message strings should have consistent translations.
6723559	Allowed to register, even though the password and retype password are not identical.
6733189	The wadm cli does not display web application path.
6754078	The Japanese Admin GUI displays garbled messages.
6762559	Inconsistent translation of Reverse-proxy.
6763094	Bad translation of the term 'fancy' in French locale.
6715350	In Japanese locale, the OLH have invalid character.

Issues Resolved in 7.0 Update 3

The following table lists the issues resolved in Sun Java System Web Server 7.0 Update 3.

Problem ID	Description
6387762	Cannot access shell/system variables from wadm.
4793938	User and password dialog presented instead of directory index. By default, Web Server 7.0 does not send a directory index unless the user has been authenticated. Attempting to access a directory prompts the user to enter a user name and password. This occurs because the default Access Control List (ACL) in Web Server 7.0 grants the list access right only to authenticated users.
6426116	Clicking on the Version button in the Admin Console result in “file not found” warning in Administration error logs.
6446206	When a single user in group is deleted, an incorrect message “Group Saved Successfully” is displayed.
6431984	Web Server should store its pid file and UNIX domain sockets in /var/run instead of /tmp.
6475536	No obvious way to reset the administration server password.
6489727	[JESMF CONFORM] CP when stopping should call MfManagedElementServer_stop().
6493971	Admin Server does not time-out if the server instance restart does not respond. On UNIX systems, the Administration Server waits until the server instance is restarted when the <code>restart - instance</code> command is executed. If the instance is not successfully restarted, the Administration Server does not respond to requests.
6515745	SNMP master agent process fails to start on Web Server
6545779	On Windows, wdeploy command fails if older version of libnspr4.dll is found in the system32 directory.

6606243	<p>Web Server installer should import the admin self signed certificate into IE certificate tab.</p> <p>When the Admin console is accessed using a browser, a pop-up (in the case of IE6 and Mozilla/Firefox) or a warning page (IE7) may be displayed stating that the certificate is not issued by a trusted certificate authority. This is because, the administration server uses a self-signed certificate. To proceed to the Administration GUI login page, do the following:</p> <ul style="list-style-type: none"> ■ On Mozilla/Firefox, click on the OK button in the pop-up window. ■ On Internet Explorer 6, click on the Yes button in the pop-up window. ■ On Internet Explorer 7, click on the "Continue to this website" link in the page. <p>The above procedure will accept the certificate temporarily for that browser session.</p> <p>To accept the certificate permanently, follow the steps below:</p> <ul style="list-style-type: none"> ■ On Firefox/Mozilla: Select the "Accept this certificate permanently" radio button in the pop-up window and click OK. ■ On Internet Explorer 6.0: <ol style="list-style-type: none"> 1. Click on the "View Certificate" button in the pop-up window. Displays another pop-up window. 2. Select the "Certification Path" tab, select the admin-ca-cert. 3. Click on the "View Certificate" button and then on "Install Certificate..." button. Invokes the certificate import wizard using which you can import the admin CA certificate into the trusted root certificate database. ■ On Internet Explorer 7: <ol style="list-style-type: none"> 1. Click on the "Continue to this website" link on the warning page. The login page is displayed. 2. Click on the "Certificate Error" link located next to the address bar. A warning window is displayed. Click on the "View certificates" link. 3. Follow the steps 1 to 3 as described in the section "On Internet Explorer 6" to import the admin CA certificate into the trusted root certificate database.
6606132	<p>Create self signed certificate fails when the "Sun Metaslot" pin is not set</p>
6709477	<p>GUI Registration reminder doesn't show up properly on IE6</p> <p>IE6 select element does not support z-index which is necessary for layering to work. Thus, if there is a layer, registration reminder, overlapping the drop downs (config and vs) , the drop downs will still be visible.</p>

6639402	<p>Connection queue size set by server for 1024 max file descriptor is very less (128)</p> <p>Web Server reserves the file descriptors for various components. If connection pool queue size, file cache max open files and keep-alive max connections are not set, then after reserving file descriptors for other components, Web Server divides the available descriptors among three. On systems where default value of max file descriptor is low, for example, Solaris 8 and RHEL, the connection pool size might be set to a low value. For example, on RHEL, the default value of max file descriptors is 1024. If the connection queue size is not assigned, then Web Server assigns 128 connections to connection queue. The value can be very low on busy systems. If connections starts timing out, users should set higher value for max file descriptors.</p>
6644322	<p>Memory leak in Fastcgistub causes hang in the Fastcgi sub-system</p>
6474037	<p>Exception installing Web Server on Ubuntu.</p> <p>On Linux Ubuntu, the package which contains the /bin/domainname is not available by default. You must install these packages for the Web Server installation to succeed.</p> <p>To install the package, type the following command:</p> <pre>sudo apt-get install nis</pre>
6414481	<p>Web Server cannot be installed without installing compat-libstdc++.</p>
6641672	<p>REDHAT ES4.0 Linux 64-bit installation fails by having compat-libstdc++-33-3* (64-bit)version</p>
6472668	<p>On Windows, Web Server installation should use -Xrs JVM option by default.</p> <p>Workaround:For more information on this fix, see Oracle iPlanet Web Server 7.0.9 Administrator's Guide.</p>
6559918	<p>Unclear error message if CLI and Administration Server versions are incompatible.</p> <p>While upgrading Web Server 7.0 installation to Web Server 7.0 Update 2 , make sure that the entire setup CLI, Administration Server and all the Administration Nodes are also upgraded to Web Server 7.0 Update 2. This is because, Web Server 7.0 administration interfaces will not work correctly with Web Server 7.0 Update 2 administration interfaces.</p>
6595795	<p>The Admin console does not add the required functions in the obj.conf file for a migrated instance.</p> <p>When a JVM disabled Web Server 6.0 instance is migrated to Web Server 7.0 and when the migrated instance is enabled with the JVM option using the Admin console, the process does not add the following necessary lines in obj . conf file.</p> <pre>NameTrans fn="ntrans-j2ee" name="j2ee" PathCheck fn="find-index-j2ee" ObjectType fn="type-j2ee" Error fn="error-j2ee"</pre>
6641844	<p>On Windows, server fails to start after upgrading from Web Server 7 that is part of the Java ES 5 release to Web Server 7.0 Update 2 release using the patch.</p>

6644314	<p>Security patch 121656-16 is a mandatory prerequisite for Sun Java System Web Server 7.0 Update 2 Linux patch on Java ES 5/U1.</p> <p>However, the security patch exhibits cyclic dependency, hence making it impossible to apply any of the patches.</p>
6640206	<p>Upgrade fails when upgrading to U2 when no sample apps is present in the existing installation.</p> <p>On non-windows platforms (Solaris, Linux and HP-UX), if you have installed Web Server 7.0 or 7.0 update 1 without sample applications and if you upgrade to Web Server 7.0 update 2, you will see the following error message:</p> <p>A problem occurred during upgrade. To troubleshoot the problem, review the installation log at: <code><install-dir>/setup/Sun_Java_System_Web_Server_install.log</code></p> <p>Note – This error does not impact the upgrade.</p>
6559735	<p>Sample applications documentation must mention adding jar file to the class path in the properties file.</p> <p>In the <i>install-dir</i>/samples/java/webapps/security/jdbcrealm/docs/index.html, under 'Compiling and Assembling the Application' section, there must be a mention of adding JDBC driver jar file to class path suffix in the <code>jdbcrealm.build.properties</code> file.</p>
6413058	<p>server.xml does not store the full file pattern for converting and including search .</p> <p>The schema does not store the full file pattern allowed by both the Admin Console and the search administration tools in this version of the Web Server. It also has no way to represent the full file pattern that might sometimes need migration from the previous versions of the Web Server.</p>
6632936	<p>On Red Hat Linux Enterprise Linux 5, Search functionality does not work properly.</p> <p>On a Red Hat Enterprise Linux machine, if the <code>compat-libstdc++</code> library is installed, you must remove the installed rpm and download/install the <code>compat-libstdc++-296-2.96-132.7.2.i386.rpm</code>.</p> <p>For x86 32-bit and 64-bit download and install the <code>compat-libstdc++-296-2.96-132.7.2.i386.rpm</code>.</p> <p>Note – Do not download/install an rpm from unreliable sources as it may lead to security vulnerabilities.</p>

6611067	<p>Red Hat Enterprise Linux instance fails to start when the file system SELinux security is enabled.</p> <p>Newer Linux distributions have new kernel security extensions enabled from the SELinux project. These extensions allow finer grained control over system security. However, SELinux also changes some default system behaviors, such as shared library loading that can be problematic to third-party programs. If you receive the error message "Cannot restore segment prot after reloc: Permission denied" when starting the Web Server Admin Server or instance, that means the system is SELinux enabled.</p> <p>Workaround</p> <ol style="list-style-type: none"> 1. Change the default security context for the libraries loaded by the Web Server by typing the following command: <pre>chcon -t texrel_shlib_t \$WS_DIR/lib/*.so</pre> 2. Disable SELinux by adding the following line to the <code>/etc/sysconfig/selinux</code> file. <pre>SELINUX=disabled</pre>
6602075	<p>Sun crypto 1000 with Web Server needs Solaris 10 patch 125465-02 (SPARC) and 125466-02 (x86).</p>
6432870	<p>Servlet container collects statistics when stats enabled element is set to false in the server.xml file.</p>
6567124	<p>JSF Web Applications running on Web Server 7.0 may break when running on Web Server 7.0 Update 1.</p> <p>Web Server 7.0 Update 1 ships with JavaServer Faces 1.2 technology. All JavaServer Faces web applications are expected to work with Web Server 7.0 Update 1 without any modifications. However, there are a few known compatibility issues with JavaServer Faces 1.2 and might require applications to be modified to address these incompatibilities. The incompatibilities are documented in the JavaServer Faces release notes at: https://javaserverfaces.dev.java.net/rlnotes/1.2_04/issues.html.</p> <p>Java ES 5 Portal Server users are suggested to delay upgrading to Web Server 7.0 Update 1 until Java ES 5 Update 1 is released.</p>
6549619	<p>On Windows 2003, when a command is executed from the CLI, the message is not encoded correctly.</p>
6630841	<p>FastCGI Handler new Role is always created with "English" name.</p>
6632818	<p>Unlocalized strings are seen in CGI settings page.</p>
6628910	<p>CLI installer "Enter your option" is in English in localization locale.</p>

6484181	<p>Portal Server configures JVM stack size to 128K (too low) for Web Server 7.0 64-bit to start.</p> <p>If Web Server 7.0 is already configured in 64-bit mode, and the Portal Server installation is started, Portal Server configuration does not set stack size to 128K. However, if both Portal Server and Web Server are already installed and configured in 32-bit mode, switching to 64-bit mode involve series of manual steps that are described in the Workaround section.</p>
6487041	<p>schemagen/xjc/wsgen/wsimport scripts not present in Java ES Web Server installation.</p> <p>schemagen/xjc/wsgen/wsimport scripts are present in different locations in Java ES installation and stand-alone installation of Web Server.</p>
6550622	<p>When upgrading Java ES 5 software to Java ES 5 Update 1, Portal Server samples fail with JSF exceptions if you have upgraded only Web Server but not the Portal Server.</p> <p>For more information, see “Compatibility Issues” on page 13.</p>
6643821	<p>SMF commands removes Java ES environment from startserv and stopserv scripts (Solaris 10 only).</p>
6549580	<p>Web Server running on Windows contains no description for the service and the description is not updated after applying Java ES Update 1 patches.</p>
6641175	<p>Streaming data (>2GB) to server using POST has problems. <code>request.getInputStream().read()</code> returns -1</p>
6576542	<p>Samples bundled with WS 7.0 cannot be used for experimenting session replication feature</p>
6600183	<p>Transfer-encoding header is sent after the body has been sent for fastcgi-perl.</p>
6613414	<p>iWS7.0U1 - Page-encoding is not case sensitive capable, e.g. utf-8 is different from UTF-8</p>
6613865	<p>servlet container implementation of encode/decode cookies has changed from >= SJSWS6.1</p>
6641175	<p>Streaming data (>2GB) to server using POST has problems. <code>request.getInputStream().read()</code> returns -1</p>
6641231	<p>Uploading file > 2MB is limited by java webcontainer.</p>
6658609	<p>web 7.0 u2 jdbc resource settings do not allow -1 in maximum wait time and idle time out</p>
6660297	<p>JDBC resource pool of web70 doesn't work as expected after restarting RDB.</p>
6671260	<p>Can't redirect the stderr message from FastCGI into error log.</p> <p>The data sent from FastCGI to <code>stderr</code> is not logged into the error log.</p>
6671957	<p>compress-file function lacks documentation (SJSWS7.0)</p>
6671992	<p>web server documentation needs to be more specific on filter it's scope and what they are</p>
6680376	<p>server goes into a loop given a particular htaccess configuration</p>

6681681	filter is applied twice when a web-apps 's welcome file list is accessed as /contextroot When a welcome file is accessed as /context - root, filters present are applied twice.
6708333	web 7.0 u2 patch 125437-13 should doc pre-requisite of nss patch 3.11.8 or above as needed
6697002	pull-config garbles binary file in config/ directory due to tokenizing (SJSWS7.0u2)
6701520	instance does not start if the user has certain umask settings during installation
6710993	es, fr - OLH is not displaying, exception thrown
6641109	Websserver crashing configured with an NFS-mounted docroot directory Web Server crashes if NFS file is removed or replaced, while using NFS and MediumFileSizeLimit >0. Therefore, you should not use MediumFileSizeLimit>0, if the document root is mounted over NFS. Workaround: When Web Server documents are residing on an NFS mount, as in NFS client, set MediumFileSizeLimit to 0 in nsfc.conf.

Issues Resolved in 7.0 Update 2

The following table lists the issues resolved in Sun Java System Web Server 7.0 Update 2.

Problem ID	Description
6467621	Request to the server fails with using of "Sun Software PKCS#11 softtoken".
6564797	Server should automatically size connection queue, keep-alive subsystem, and file cache.
6493271	Java garbage collector activity is higher in Web Server 7.0 when compared against Web Server 6.1. The servlet container in Web Server 7.0 creates many Java objects.
6497803	If a servlet is mapped to req URI formed by partial req + welcome file, the behavior is wrong. If a web container receives a valid partial request, the web container must examine the welcome file list defined in the deployment descriptor. The welcome file list is an ordered list of partial URLs with no trailing or leading /. The Web Server must append each welcome file in the order specified in the deployment descriptor to the partial request and check whether a static resource or a servlet in the WAR file is mapped to that request URI. The web container must send the request to the first resource in the WAR that matches.
6316881	Multi-byte characters in headers can not be retrieved by req.getHeader(). The characters are not parsed correctly, when request.getHeader() is called.

6554326	The hardcoded message "ADMIN3594: Configuration changes require a server restart" is not localized.
6565615	In the Japanese locale online help, the description about the PAM for "Editing Authentication Databases" incorrectly states the name of Directory Server. The description must be read as: "Editing Authentication Databases" PAM -- PAM is the new auth-db supported by Sun Java System Web Server 7.0.
6563951	Search collection subdirectory with leading slash causes confusing error. When you try to create a search collection and set the document root subdirectory with a leading slash, the error message produced wrongly informs you that a slash at the beginning is needed.
6571208	Inconsistent wording found in Directory listing type. The sentence "Error response file to use when indexing is None" should be changed to "Error response file to use when listing is None".
6549584	The word "Other" in the list of countries is not translated.
6556225	In the Add Documents window, Included checkbox for subdirectory is not translated.
6565615	Japanese language help: "Editing Authentication Databases" have different description about PAM.
6628918	Translation issue of Admin GUI messages in Japanese.
6628917	Translation issue of GUI installer OLH.
6604075	In Java ES, Web Server 7.0 with Access Manager displays a null pointer exception.
6479062	Web Server fails to start when HTTP listener protocol family="nca" is used for Solaris SPARC, Linux and HP-UX platforms. Web Server instance does not restart on setting the Protocol-Family property to nca in the EditHTTPListener wizard.
6464953	Setting digestauthstate property through the set-authdb-prop CLI does not validate the value and allows to set junk value for this property.
6504050	The Results page in all Admin Console wizards should be aligned properly.
6473376	The default server.xml should not contain the <stack-size> element.
6367751	The create-instance command fails on remote node intermittently and logs HTTP 400 error.
6547264	Executing the create-instance command immediately after starting a remote node fails on the remote node.
6468132	The list-cert command does not list the certificates if the certificate nickname contains a colon.
6437577	<pkcs11> element not removed from server.xml even when child elements are absent.

6473589	<pkcs11/> added to <code>server.xml</code> when token pin is set.
6534202	Cannot edit WebDAV collection properties through the Admin Console When a configuration is deployed on multiple nodes, the lockdb path must be a shared location mounted on the same path on all the nodes. Additionally, to list or expire locks in the lockdb from the Admin Console, the same path must be writable from the Administration Server.
6554691	The add-webapp command when used with JSP pre-compilation option does not delete the previously precompiled JSP files.
6556820	The Admin Console or the Admin CLI does not provide support to add CA certificates to the Administration Server.
6489269	'external' expression function with quoted path is not working.
6432375	On HP-UX, SNMP fails for some oid values.
6483212	On HP-UX 11.11, Web Server fails to start when max heap size is 2048 MBytes or greater.
6474011	The basic-search.html has unclear description.
4988156	Installing the stand-alone product over an existing Java ES installation and vice-versa is not supported.
6610103	On Windows - unable to deploy configuration and start up after disabled Java
6856484	Server should automatically size connection queue, keep-alive subsystem, and file cache.

Issues Resolved in 7.0 Update 1

The following table lists the issues resolved in Sun Java System Web Server 7.0 Update 1.

Problem ID	Description
6390112	Java LDAP connection pool interaction issue - initial connection is never timed out. Specifying a Java LDAP connection pool through the JVM options in the <code>server.xml</code> file and referencing this with an external JNDI resource when the web server is started, creates a pooled LDAP connection. With this connection, it is always marked as busy and the connection never expires.
6472223	Values of 'mail-resource' sub elements are not getting set on mail session object.
6487083	NSAPIRequest.setupRequestFields is slow. <code>com.sun.webserver.connector.nsapi.NSAPIRequest.setupRequestFields</code> is slow primarily because of excessive <code>String-->byte</code> and <code>byte-->String</code> conversion when parsing Cookie headers.

Problem ID	Description
6501785	The servlet container does not use accelerator cache when processing RequestDispatcher includes.
6500647	On Windows, dynamic reloading of JSP produces incorrect output.
6433752	<p>ssl-check is not working with NSAPI based plug-in.</p> <p>"PathCheck fn="ssl-check" secret-keysize=128 bong file="xxxxx.yyy.html"</p> <p>For static file requests, if the secret - keysize of the client is less than the size specified by the server and a bong file is present, then the bong file is sent back as the response. However, requests for dynamic content (for example, JSP files) return the actual requested object (for example, the JSP file) rather than the bong file.</p>
6421617	<p>Problem having server-parsed HTML (ParseHTML) and .htaccess with restricted group option.</p> <p>Authentication succeeds when parsing through a HTML file which has the shtml include entries and is configured to authenticate through .htaccess which has the "restricted by group" option enabled. If the group user gets authenticated, then the result page does not get shtml include entries. This however works fine with the user in .htaccess file has "restricted by user" option.</p>
6489913	<p>SSL session cache cannot be disabled.</p> <p>Session cache is enabled by default. When the session cache is disabled and URL is accessed through the HTTPs protocol, the URL does not go through and the server log displays an error message indicating that the SSL cannot be configured without session-cache.</p>
6302983	<p>Samples refer to "Sun ONE" instead of "Sun Java System".</p> <p>The servlet sample, LocalCharsetServlet.java, co-packaged with Web Server 7.0 refers to "SunONE" instead of "Sun Java System".</p>
6495588	<p>sampleapps/java/webapps/simple docs invalid.</p> <p>The documents for a simple sample application shows an incorrect pathname. The path should be <i>install-dir/plugins/java/samples/webapps/simple/src</i> instead of <i>install-dir/samples/java/webapps/simple/src</i>.</p>
6347905	No CLI support to configure FastCGI. Need to manually edit obj.conf or magnus.conf files to configure FastCGI.
6504587	Memory leak found in FastCGI.

Problem ID	Description
6479045	<p>Admin Console online help needs to be updated.</p> <p>The online help needs to be updated for the following:</p> <ol style="list-style-type: none"> 1. Context-based help should be provided. 2. All screens must have a corresponding help page. 3. Help pages must reflect the changes in the GUI. 4. Inconsistent usage of terminology between the GUI and online help. 5. Fix grammatical errors. 6. Detailed description for some topics.
6482764	<p>Mismatch between online help and the Admin Console.</p>
6498477	<p>Missing help file under config tokens page.</p> <p>Common Tasks > Edit Configuration > Certificates > PKCS11 Tokens, the help file for this screen is missing.</p>
6479062	<p>Cannot dynamically reconfigure HTTP listener family. The Instance does not start on setting the protocol family to nca.</p>
6482536	<p><listen-queue-size> upper bound is set to 65535, which is too small. Need to increase the <listen-queue-size> upper bound.</p>
6500715	<p>Incorrect ObjectType fn="force_type" added in object cgi on creation of new cgi directory.</p> <p>When creating a new cgi directory, an incorrect object type force_type is added to the obj.conf file.</p>
6479247	<p>On Windows, dialog box to enter the token password appears on restarting an instance after the deployment. This behavior is not see on other platforms.</p>
6425144	<p>On Windows, wadm does not update classpath correctly if classpath contains a semicolon (;)</p> <p>The semicolon in tcl is interpreted as a command terminator, which is used to group multiple commands in a single line. On Windows, semicolon is used as a path separator.</p>
6292582	<p>SNMP Management Information Base (MIB) for "iwsFractionSysMemUsage" does not show correct results</p> <p>SNMP MIB "Fraction of process memory in system memory" which is part of iws.mib gives wrong results when queried by the SNMP manager utility.</p>
6471744	<p>Incorrect error message is displayed if you execute the list-tokens command without specifying the configuration value.</p>
6471754	<p>Incorrect error message is displayed if you execute the list-authdb-userprops command without specifying the authdb value.</p>
6472210	<p>No error message is displayed if you execute the get-ssl-prop command with an invalid http-listener value.</p>

Problem ID	Description
6476111	Cannot edit the MIME types using the Admin Console.
6478601	Displays an improper message when you stop an instance that does not exist. An error message 'Successfully stopped the server instance' is displayed if you try to stop an instance that does not exist.
6480523	wadm allows you to create a configuration with a negative port number.
6489765	Incorrect error message is displayed if you execute the create-cert-request command with an invalid key-size value.
6489777	The delete-group command displays an incorrect error message if you specify an invalid group value.
6489779	No error message is displayed when you execute the list-group-members command with an invalid group-ID value.
6490728	Cannot set the rewrite-location properties using the set-reverse-proxy-prop command. You cannot set the <code>-rewrite-location</code> property to <code>false</code> . The value specified for the <code>-rewrite-location</code> is not validated. For example, specifying the <code>=</code> symbol for the <code>i-rewrite-location</code> option corrupts the <code>obj.conf</code> file and results in parser error.
6492315	The set-token-prop command sets wrong passwords in the server.xml file even if the token pin has not been specified.
6492469	Incorrect error message is displayed on LDAP user creation failure.
6494353	If an invalid node name is specified while deleting an instance, an incorrect error message is displayed.
6494950	The register-node command runs successfully with non SSL port only in shell mode. In shell mode, typing the <code>register-node</code> command with the <code>-no-ssl</code> option registers the node successfully as the command is falsely executed in the SSL mode.
6405018	The get-jvm-prop command does not print the command when echo is enabled in shell mode.
6499507	Incorrect error messages are displayed when you execute the list-locks and expire-lock commands.
6499510	A 'null' message is displayed if you execute the list-instances, list-crls, list-tokens, and list-certs commands without specifying the configuration name.
6499512	The error message for the list-url-redirects command is not localized.
6500119	wadm prompts for a token pin if you specify an invalid configuration name while trying to delete an existing certificate.
6500146	While creating an HTTP listener using the CLI, the create-http-listener command creates a listener with null value as name.

Problem ID	Description
6500150	If you do not specify a virtual server while executing the list-dav-collections command, an incorrect error message is displayed.
6500151	If you do not specify the authentication database while executing the list-users, list-org-units, list-groups, and list-group-members commands, an incorrect error message is displayed.
6500152	If you do not specify a virtual server while executing the list-uri-patterns command, an incorrect error message is displayed.
6500154	list-userprops CLI gives improper message. If you do not specify a JNDI name or specify an invalid JNDI name while executing the list-jdbc-resource-userprops, list-soap-auth-provider-userprops, list-auth-realm-userprops, list-external-jndi-resource-userprops, list-custom-resource-userprops commands, an incorrect error message is displayed.
6503350	Error message given when entering invalid wadm command is misleading. When you type an invalid command, an error message "Invalid command <command name>. Use "help" command for a list of valid commands." is displayed. The help man page does not contain a list of valid command. Therefore this error message is misleading.
6503944	The create-user command usage for the LDAP authentication database is ambiguous.
6504095	The set-cert-trust-prop command accepts incorrect properties and does not show proper error message.
6443845	Administration Server does not validate the password length and mechanism support of the given token.
6449506	Certificate with same server name as existing certificate cannot be created with the same nickname.
6461553	Virtual Server Web Applications page title help is incorrect.
6473518	Prompt to enter token pin while starting instance should not appear if configuration has not been deployed.
6476095	Admin Console does not provide an option to edit document directories and CGI records.
6476736	Admin Console should have a tab to add and edit MIME mappings at the Virtual server level.
6478090	'Current Password' field in the Nodes -> Select Administration Server-> Certificates -> Token Password Management page should be disabled if no token password has been set for the administrator.
6490705	Unable to configure uri-pattern specific configurations using the Admin Console.
6496545	Admin Console displays invalid properties when custom authentication database user properties are created through Administration CLI.

Problem ID	Description
6502303	The Admin Console Migrate wizard creates multiple configurations if you click the Finish button multiple times.
6504495	Admin Console has 508 compliance issues.
6504951	User selection process in the Common Tasks->Edit Virtual Server->WebDAV->New page needs validation.
6360666	Installed CRL should have a meaningful name.
6364821	Administration CLI should support URIs, URI prefixes, URI wildcard patterns, and URI regular expressions for all commands that operate on URI space.
6366956	Search schedule events do not work from the Admin Console.
6378612	64-bit instance does not start on 32-bit remote node.
6423391	When a server certificate with data in non-DER format is installed, an incorrect error message is displayed.
6439132	Exceptions in Certificate Installation wizard not clear.
6468676	No validation exists for 'Java Home' field; accepts invalid data.
6474668	HTTP Listener field accepts names with spaces. This is invalid.
6476111	Unable to edit MIME types either using the Admin Console or the CLI.
6483365	GUI and CLI accept Web Server 7.0's server root for migration The Admin Console and the CLI accept the Web Server 7.0 path instead of Web Server 6.1 or Web Server 6.0 path during migration. Web Server 7.0 path is not a valid path for the server-root property in the migrate-server command.
6492176	Default and null values get stored in obj.conf when a new configuration is created and saved using the Admin Console. Administration Server stores the values passed by the Admin Console into obj.conf file without any validation.
6497004	SaveConfigException displayed on CLI during set-authdb-prop. If a nonexistent file path is provided to the path property for keyfile authdb by using the set-authdb-prop command, results in SaveConfigException instead of a File does not exist message. See the error log for the Administration Server.
6497143	At times, the execution of stop-admin command displays the "Admin Server Not Running" message when the Administration Server is actually running.
6498411	The get-cert-prop does not display only those properties mentioned in the <displayproperties> element.

Problem ID	Description
6500715	Server error on trying to access a file in the cgi-bin directory.
6364702	wadm commands do not return valid error codes [0-125] when success or failure.
6370032	Session failover does not happen with RequestDispatcher include call. While deploying two web applications on a cluster where the first application calls on the second application using the <code>RequestDispatcher()</code> include call, the persistence valves are not called during the <code>RequestDispatcher()</code> 's <code>invoke()</code> method, and session replication does not occur.
6381950	Incorrect load factor set for BaseCache. Session replication does not support more than two web applications.
6381954	Session replication fails to work on multiple web applications involving RequestDispatcher due to bad sequence.
6383313	Incorrect path is set on SR-instanceId cookie. The <code>SR-instanceId</code> cookie should be set to the web application's path instead of the servlet's path.
6450360	The create-authdb command does not validate the URL at the time of the authentication database (authdb) creation. The create-authdb command successfully creates an authentication database with the wrong URL.
6450800	The get-error-log and the get-access-log commands displays cluttered and improper messages.
6459106	The wadm deploy fails to deploy the cluster configuration. If any changes occur to the instance configuration files, manually or otherwise, the <code>deploy-config</code> command displays an error message stating that the instance has been modified.
6462891	No Admin Console is available to deploy web applications in user specific location.
6439577	Does not prompt for the token password when the instance is started from the wadm command prompt with a wrong token-pin.
6465470	Incorrect text in Groups settings page. The text should read as "From this page you can add/remove user groups in the selected Authentication Database" instead of "From this page you add/remove user groups in the selected Authentication Database."
6465480	Incorrect message when you delete a JVM profiler. The message should read as "Profiler deleted successfully" instead of "Profiler saved successfully".
6466409	Incorrect error message is displayed when you provide a wrong path while adding web application.

Problem ID	Description
6467164	The window titles of the Admin Console wizards are not consistent.
6467785	Admin Console gives incorrect error message when you provide invalid Directory Server configuration values.
6470585	URI prefix of document directories is accepts the value without '\ .
6471737	The list-instances command lists the instances even if you do not specify the configuration value.
6472385	Token password changes made through the CLI is not reflected in GUI. It requires a browser refresh.
6467665	Migrating certificate with an invalid file path using the migrate-jks-keycert command, prompts the user to enter the keystore-password and the key-password.
6469104	The create-selfsigned-cert command allows you to define an inappropriate validity period while creating a server certificate.
6469109	The delete-cert command does not delete a certificate which is created with token "Sun Software PKCS#11 softtoken".
6471649	The list-events command output is not aligned.
6474584	<p>dayofweek does not take "*" as an option.</p> <p>For example, set an ACL as follows:</p> <pre>acl "uri="/"; deny (all) dayofweek="*"; allow (all) dayofweek="Sat,Sun";</pre> <p>In this program, you are restricting access on all days of week except Saturday and Sunday. This program does not work as you can you can successfully access the ACL on a Monday.</p>
6477840	Admin Console should provide large text region for entering class path prefix, class path suffix, and native library path prefix.
6478165	Usability issues in the Install CRL page after incorrect file path is entered for CRL file on server.
6478229	The Instance->New page has incorrect title.
6478292	The Common Tasks->Select configuration ->Select Virtual Server ->Edit Virtual Server ->WebDAV->New page should have the Enter Users field only if the authentication database is PAM.
6478303	Admin Console allows you to create an ACE without entering user or group information for ACL. The check is not done if the authentication database is PAM.
6478612	Inline help for range of values accepted by Request Header Time-out text field is incorrect.

Problem ID	Description
6500228	The Admin Console displays an exception when you create a duplicate record of a MIME types.
6501807	Deploying a new web application using the Admin console kills sessions for all existing web applications.
6504748	With delete instance option, instead of deleting the symbolic links, the uninstaller deletes files from symbolic links.
6505994	Crash detected when creating properties with empty URI pattern
6510486	htaccess rules can become corrupted in memory. If a single .htaccess file has more than five allow or deny rules, it is possible that some of the rules may become corrupted in memory. If this occurs, some of the rules may be bypassed.
6506936	deploy-config fails when you modify JSPs or any other files in the webapps directory of the instance. When using the pull-config either through the Admin Console or through the CLI, only the contents of the <i>instance-dir/config</i> directory is pulled into the <i>config-store</i> . In Web Server 7.0, when pull-config was used, the contents were pulled into <i>instance-dir/config</i> , <i>instance-dir/lib</i> , and <i>instance-dir/web-app</i> directories.
6492407	Front-end file accelerator cache. Depending on ACLs and obj.conf configuration, a front end accelerator cache can service static file requests for URLs that were previously processed using NSAPI. The accelerator cache must work with the default configuration.
6498928	Output directives are not invoked for 0-byte files. Output directives are not invoked for 0-length responses unless <code>protocol_start_response()</code> is called. <code>send-file</code> does not call <code>protocol_start_response()</code> function. Output directives are not invoked when sending 0-byte files.
6502258	Server crash with large output buffers. If the output stream buffer size is bigger than the input buffer size, the server might attempt to buffer data at an invalid address. The default input buffer size is 8192 bytes.
6504755	Cannot disable access logging in default server instance. The value of the <code><access-log></code> <code><enabled></code> element is ignored in the <code>server.xml</code> file.
6505390	Accelerator cache does not handle ssl-unclean-shutdown properly. The accelerator cache does not interact correctly with the <code>AuthTrans fn="match-browser" browser="*MSIE*"</code> directive in the default configuration. When such a directive is present, the accelerator cache applies the "unclean shutdown" setting to every connection, regardless of the browser used.

Problem ID	Description
6432375	<p>On HP-UX, SNMP fails for some oid values.</p> <p>Workaround</p> <p>Due to lack of the HP-UX API support and complexity, network in and out traffic statistics is not implemented. Use HP tools for monitoring the traffic statistics.</p>
6430293	<p>The AdminException messages displayed on the Admin Console are not localized.</p>
6508299	<p>Displays incorrect characters in search results on the left panel of online help on non-English locales.</p>
6507819	<p>Localized online help content have some differences from the English version.</p>
6536820	<p>Intermittent deploy-config failure while running QA Regression Tests on tinderbox</p>
6486480	<p>service-nsfc-dump entry hit counts are 0 with <replacement>false</replacement>.</p> <p>If <replacement>false</replacement> is specified in server.xml file, entry hit counts show as 0 in the service-nsfc-dump output. However, the cache hit counts are displayed correctly.</p>