



Sun Cluster Data Service for Oracle Application Server Guide for Solaris OS

SPARC Platform Edition

Sun Microsystems, Inc.
4150 Network Circle
Santa Clara, CA 95054
U.S.A.

Part No: 817-5721-10
September 2004, Revision A

Copyright 2004 Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, CA 95054 U.S.A. All rights reserved.

This product or document is distributed under licenses restricting its use, copying, distribution, and decompilation. No part of this product or document may be reproduced in any form by any means without prior written authorization of Sun and its licensors, if any. Third-party software, including font technology, is copyrighted and licensed from Sun suppliers.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, Solstice DiskSuite, iPlanet, and Solaris are trademarks, registered trademarks, or service marks of Sun Microsystems, Inc. in the U.S. and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc.

The OPEN LOOK and Sun™ Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

Federal Acquisitions: Commercial Software—Government Users Subject to Standard License Terms and Conditions.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright 2001 Sun Microsystems, Inc., 901 San Antonio Road, Palo Alto, CA 94303-4900 Etats-Unis. Tous droits réservés.

Ce produit ou document est distribué avec des licences qui en restreignent l'utilisation, la copie, la distribution, et la décompilation. Aucune partie de ce produit ou document ne peut être reproduite sous aucune forme, par quelque moyen que ce soit, sans l'autorisation préalable et écrite de Sun et de ses bailleurs de licence, s'il y en a. Le logiciel détenu par des tiers, et qui comprend la technologie relative aux polices de caractères, est protégé par un copyright et licencié par des fournisseurs de Sun.

Des parties de ce produit pourront être dérivées des systèmes Berkeley BSD licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, Solstice DiskSuite, iPlanet, et Solaris sont des marques de fabrique ou des marques déposées, ou marques de service, de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays. Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

L'interface d'utilisation graphique OPEN LOOK et Sun™ a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciés de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui en outre se conforment aux licences écrites de Sun.

LA DOCUMENTATION EST FOURNIE "EN L'ETAT" ET TOUTES AUTRES CONDITIONS, DECLARATIONS ET GARANTIES EXPRESSES OU TACITES SONT FORMELLEMENT EXCLUES, DANS LA MESURE AUTORISEE PAR LA LOI APPLICABLE, Y COMPRIS NOTAMMENT TOUTE GARANTIE IMPLICITE RELATIVE A LA QUALITE MARCHANDE, A L'APTITUDE A UNE UTILISATION PARTICULIERE OU A L'ABSENCE DE CONTREFAÇON.



040812@9495



Contents

| | |
|---|----------|
| Installing and Configuring Sun Cluster HA for Oracle Application Server | 5 |
| Installing and Configuring Sun Cluster HA for Oracle Application Server | 5 |
| Sun Cluster HA for Oracle Application Server Overview | 6 |
| Planning the Sun Cluster HA for Oracle Application Server Installation and Configuration | 7 |
| Configuration Restrictions | 8 |
| Configuration Requirements | 8 |
| Installing and Configuring Oracle Application Server | 12 |
| ▼ How to Install and Configure Oracle Application Server | 13 |
| Verifying the Installation and Configuration of Oracle Application Server | 19 |
| ▼ How to Verify the Installation and Configuration of Oracle Application Server | 19 |
| Installing the Sun Cluster HA for Oracle Application Server Packages | 21 |
| ▼ How to Install the Sun Cluster HA for Oracle Application Server Packages Using the Web Start Program | 21 |
| ▼ How to Install the Sun Cluster HA for Oracle Application Server Packages Using the <code>scinstall</code> Utility | 23 |
| Registering and Configuring Sun Cluster HA for Oracle Application Server | 23 |
| ▼ How to Register and Configure Sun Cluster HA for Oracle Application Server as a Failover Service | 24 |
| Verifying the Sun Cluster HA for Oracle Application Server Installation and Configuration | 29 |
| ▼ How to Verify the Sun Cluster HA for Oracle Application Server Installation and Configuration | 29 |
| Understanding the Sun Cluster HA for Oracle Application Server Fault Monitor | 30 |
| Resource Properties | 30 |
| Probing Algorithm and Functionality | 30 |
| Debug Sun Cluster HA for Oracle Application Server | 31 |

▼ How to turn on debug for Sun Cluster HA for Oracle Application Server 32

Index 33

Installing and Configuring Sun Cluster HA for Oracle Application Server

Installing and Configuring Sun Cluster HA for Oracle Application Server

Table 1 lists the tasks for installing and configuring Sun Cluster HA for Oracle Application Server. Perform these tasks in the order that they are listed.

TABLE 1 Task Map: Installing and Configuring Sun Cluster HA for Oracle Application Server

| Task | For Instructions, Go To |
|---|---|
| Plan the installation. | “Sun Cluster HA for Oracle Application Server Overview” on page 6 “Planning the Sun Cluster HA for Oracle Application Server Installation and Configuration” on page 7 |
| Install and configure Oracle Application Server. | “How to Install and Configure Oracle Application Server” on page 13 |
| Verify installation and configuration. | “How to Verify the Installation and Configuration of Oracle Application Server” on page 19 |
| Install Sun Cluster HA for Oracle Application Server Packages. | “How to Install the Sun Cluster HA for Oracle Application Server Packages Using the <code>scinstall</code> Utility” on page 23 |
| Register and Configure Sun Cluster HA for Oracle Application Server. | “How to Register and Configure Sun Cluster HA for Oracle Application Server as a Failover Service” on page 24 |
| Verify Sun Cluster HA for Oracle Application Server Installation and Configuration. | “How to Verify the Sun Cluster HA for Oracle Application Server Installation and Configuration” on page 29 |

TABLE 1 Task Map: Installing and Configuring Sun Cluster HA for Oracle Application Server *(Continued)*

| Task | For Instructions, Go To |
|--|---|
| Understand Sun Cluster HA for Oracle Application Server fault monitor. | “Understanding the Sun Cluster HA for Oracle Application Server Fault Monitor” on page 30 |
| Debug Sun Cluster HA for Oracle Application Server. | “Debug Sun Cluster HA for Oracle Application Server” on page 31 |

Sun Cluster HA for Oracle Application Server Overview

The Sun Cluster HA for Oracle Application Server can be used to provide high availability for either the Oracle 9iAS Infrastructure or Oracle 10g AS Infrastructure.

Oracle 9iAS (version 9.0.2 and 9.0.3) and Oracle 10g AS (version 9.0.4) introduced a new component called “Oracle Infrastructure”. This infrastructure component provides centralized product metadata, security and management services, configuration information, and data repositories for middle tier installations.

The Sun Cluster HA for Oracle Application Server data service provides high availability for either the Oracle 9iAS Infrastructure or the Oracle 10g AS Infrastructure components. Additionally the Sun Cluster HA for Oracle is also required to provide high availability for the Oracle Database.

TABLE 2 Oracle Application Server Architecture

| Middle Tier | Infrastructure Tier | Database Tier |
|--------------------------|--------------------------|---------------------|
| Oracle HTTP Server (OHS) | Oracle HTTP Server (OHS) | Metadata Repository |
| J2EE Server (OC4J) | J2EE Server (OC4J) | |
| | LDAP Server (OID) | |
| | Enterprise Manager (EM) | |

The middle tier may be installed on multiple nodes to achieve high availability, however the infrastructure tier and database tier are installed onto one node and require more than one Sun Cluster Data Service to manage the infrastructure (requires the Sun Cluster HA for Oracle Application Server data service) and database tier (requires the Sun Cluster HA for Oracle data service).

Note – The middle tier components listed in [Table 2](#) only refer to those components installed through an Oracle Application Server installation. There are other Oracle Applications that qualify as middle tier components, however these are not listed here.

[Table 3](#) lists the Oracle 9iAS Infrastructure services and how they are managed by the Oracle components, which are then managed by the Sun Cluster HA for Oracle Application Server.

TABLE 3 Oracle 9iAS Infrastructure Components

| Services | Component |
|--|--|
| Oracle HTTP Server (OHS) J2EE Server (OC4J) | Oracle Process Management and Notification (OPMN) |
| LDAP Server (OID) | Oracle Internet Directory Monitor (OIDMON) and Process (OIDLDAP) |
| Enterprise Manager (EM) | Enterprise Manager (EM) |

[Table 4](#) lists the Oracle 10g AS Infrastructure services and how they are managed by the Oracle components, which are then managed by the Sun Cluster HA for Oracle Application Server.

TABLE 4 Oracle 10g AS Infrastructure Components

| Services | Component |
|--|---|
| Oracle HTTP Server (OHS) J2EE Server (OC4J) Oracle LDAP Server (OID) | Oracle Process Management and Notification (OPMN) |
| Enterprise Manager (EM) | Enterprise Manager (EM) |

Planning the Sun Cluster HA for Oracle Application Server Installation and Configuration

This section contains the information you need to plan your Sun Cluster HA for Oracle Application Server installation and configuration.

Configuration Restrictions

This section provides a list of software and hardware configuration restrictions that apply to Sun Cluster HA for Oracle Application Server only.



Caution – Your data service configuration might not be supported if you do not observe these restrictions.

For restrictions that apply to all data services, see the *Sun Cluster Release Notes*.

- **Installing Oracle Application Server onto Cluster File Systems** — The Oracle Application Server can be installed onto a Global File System or Failover File System.

Note – It is considered best practice when mounting Global File Systems to mount them with the /global prefix and to mount Failover File Systems with the /local prefix.

Configuration Requirements

The requirements in this section apply to the Sun Cluster HA for Oracle Application Server only.

These requirements are setup in configuration and registration files within /opt/SUNWsc9ias/util. These files allow you to register the Oracle Application Server components with Sun Cluster, with appropriate dependencies applied.

You must use these files to register the Sun Cluster HA for Oracle Application Server resources.

Files within /opt/SUNWsc9ias/util that are prefixed 9ias should be used for the Oracle 9iAS Infrastructure components and files prefixed 10gas should be used for the Oracle 10g AS Infrastructure components.



Caution – Your data service configuration might not be supported if you do not adhere to these requirements.

- **Oracle Application Server components and their dependencies –**

TABLE 5 Oracle 9iAS Infrastructure components and their dependencies (via → symbol)

| Component | Description |
|---|---|
| Oracle Internet Directory Monitor (OIDMON) | → <i>SUNW.HASStoragePlus</i> resource → <i>Oracle Database Server</i> resource → <i>Oracle Database Listener</i> resource |
| Oracle Internet Directory Process (OIDLDAP) | → <i>Oracle Internet Directory Monitor (OIDMON)</i> resource |
| Oracle Process Management and Notification (OPMN) | → <i>Oracle Internet Directory Process (OIDLDAP)</i> resource |
| Enterprise Manager (EM) | → <i>Oracle Process Management and Notification (OPMN)</i> resource |

TABLE 6 Oracle 10g AS Infrastructure components and their dependencies (via → symbol)

| Component | Description |
|---|---|
| Oracle Process Management and Notification (OPMN) | → <i>SUNW.HASStoragePlus</i> resource → <i>Oracle Database Server</i> resource → <i>Oracle Database Listener</i> resource |
| Enterprise Manager (EM) | → <i>Oracle Process Management and Notification (OPMN)</i> resource |

The Sun Cluster HA for Oracle Application Server configuration and registration files within `/opt/SUNWsc9ias/util` define these dependencies. [Example 1](#) lists the Oracle 10g AS configuration and registration files.

EXAMPLE 1 Oracle 10g AS Infrastructure configuration and registration files for Sun Cluster

```
# cd /opt/SUNWsc9ias/util
#
# ls -l
total 24
-rwxr-xr-x  1 root    sys      1516 Jul 14 12:33 10gas_config
-r-xr-xr-x  1 root    sys      2738 Jul 14 12:33 10gas_register
-rwxr-xr-x  1 root    sys      1671 Jul 14 12:33 9ias_config
-r-xr-xr-x  1 root    sys      4383 May 27 09:48 9ias_register
# more 10g*
::::::::::::
10gas_config
::::::::::::
#
# Copyright 2004 Sun Microsystems, Inc. All rights reserved.
```

EXAMPLE 1 Oracle 10g AS Infrastructure configuration and registration files for Sun Cluster *(Continued)*

```
# Use is subject to license terms.
#
# This file will be sourced in by 10gas_register and the parameters
# listed below will be used.
#
# These parameters can be customized in (key=value) form
#
#           RG - name of the SC resource group containing the resources
#           RS_OPMN - name of the SC Oracle Process Monitor Notification resource
#           RS_EM - name of the SC Enterprise Manager Web site resource
#
# ORACLE_HOME - name of the Oracle home directory
# ORACLE_SID - name of the Oracle SID
# OIAS_LHOST - name of the Oracle 10gAS Infrastructure logical hostname
# OIAS_USER - name of the Oracle 10gAS Infrastructure userid
# OIAS_ADMIN - name of the Oracle 10gAS Internet Directory Admin password
# OIAS_INFRA - name of the Oracle 10gAS Infrastructure /var/opt/oracle
# OIAS_FQDN - name of the Oracle 10gAS fully qualified domainname
# OIAS_OPMN - name of the Oracle 10gAS ias-components
#           e.g. OIAS_OPMN=OID/HTTP_Server/OC4J or OIAS_OPMN=all
#
#           ALL indicates all the installed ias-components
#
#           RS_LH - name of the SC Logical Hostname resource
#           RS_HAS - name of the SC Oracle 10gAS HAStoragePlus resource
#           RS_ORACLE - name of the SC Oracle resource
#           RS_ORALSR - name of the SC Oracle Listener resource
#
RG=
RS_OPMN=
RS_EM=

ORACLE_HOME=
ORACLE_SID=
OIAS_LHOST=
OIAS_USER=
OIAS_ADMIN=
OIAS_INFRA=
OIAS_FQDN=
OIAS_OPMN=

RS_LH=
RS_HAS=
RS_ORACLE=
RS_ORALSR=

:::
10gas_register
:::
#
# Copyright 2004 Sun Microsystems, Inc. All rights reserved.
```

EXAMPLE 1 Oracle 10g AS Infrastructure configuration and registration files for Sun Cluster *(Continued)*

```
# Use is subject to license terms.
#

. `dirname $0`/10gas_config

PORT=10000
OIAS_ADMIN=dummy
OIAS_FQDN=dummy

validate_registration()
{
St=$?
RS=$1
RG=$2
ORACLE_HOME=$3
ORACLE_SID=$4
OIAS_LHOST=$5
OIAS_USER=$6
OIAS_ADMIN=$7
OIAS_INFRA=$8
OIAS_FQDN=$9

if [ "${St}" -ne 0 ]; then
    echo "Registration of resource ${RS} failed,\
        please correct the wrong parameters"
    exit 1
else
    echo "Registration of resource ${RS} succeeded"
fi

# VALIDATE RESOURCE

`dirname $0`/../bin/validate_9ias -R $RS -G $RG \
-O $ORACLE_HOME -S $ORACLE_SID -H $OIAS_LHOST \
-U $OIAS_USER -P $OIAS_ADMIN -E $OIAS_INFRA -D $OIAS_FQDN

St=$?

if [ "${St}" -ne 0 ]; then
    echo "Validation of resource ${RS} failed, \
        please correct the wrong parameters"
    echo "Removing resource ${RS} from the cluster configuration"

    scrgadm -r -j ${RS}
    exit 1
else
    echo "Validation of resource ${RS} succeeded"
fi
}

scrgadm -a -j $RS_OPMN -g $RG -t SUNW.gds \
-x Start_command="/opt/SUNWsc9ias/bin/start-opmn \
```

EXAMPLE 1 Oracle 10g AS Infrastructure configuration and registration files for Sun Cluster (Continued)

```
-R $RS_OPMN -G $RG -O $ORACLE_HOME -S $ORACLE_SID -H $OIAS_LHOST \  
-U $OIAS_USER -P $OIAS_ADMIN -E $OIAS_INFRA -D $OIAS_FQDN -C $OIAS_OPMN " \  
-x Stop_command="/opt/SUNWsc9ias/bin/stop-opmn \  
-R $RS_OPMN -G $RG -O $ORACLE_HOME -S $ORACLE_SID -H $OIAS_LHOST \  
-U $OIAS_USER -P $OIAS_ADMIN -E $OIAS_INFRA -D $OIAS_FQDN -C $OIAS_OPMN " \  
-x Probe_command="/opt/SUNWsc9ias/bin/probe-opmn \  
-R $RS_OPMN -G $RG -O $ORACLE_HOME -S $ORACLE_SID -H $OIAS_LHOST \  
-U $OIAS_USER -P $OIAS_ADMIN -E $OIAS_INFRA -D $OIAS_FQDN -C $OIAS_OPMN " \  
-y Port_list=$PORT/tcp -y Network_resources_used=$RS_LH \  
-x Stop_signal=9 -x Probe_timeout=90 \  
-y Resource_dependencies=$RS_HAS,$RS_ORACLE,$RS_ORALSR  
  
validate_registration $RS_OPMN $RG \  
$ORACLE_HOME $ORACLE_SID $OIAS_LHOST \  
$OIAS_USER $OIAS_ADMIN $OIAS_INFRA $OIAS_FQDN $OIAS_OPMN  
  
if [ ! -z "$RS_EM" ]; then  
  
scrgadm -a -j $RS_EM -g $RG -t SUNW.gds \  
-x Start_command="/opt/SUNWsc9ias/bin/start-em \  
-R $RS_EM -G $RG -O $ORACLE_HOME -S $ORACLE_SID -H $OIAS_LHOST \  
-U $OIAS_USER -P $OIAS_ADMIN -E $OIAS_INFRA -D $OIAS_FQDN " \  
-x Stop_command="/opt/SUNWsc9ias/bin/stop-em \  
-R $RS_EM -G $RG -O $ORACLE_HOME -S $ORACLE_SID -H $OIAS_LHOST \  
-U $OIAS_USER -P $OIAS_ADMIN -E $OIAS_INFRA -D $OIAS_FQDN " \  
-x Probe_command="/opt/SUNWsc9ias/bin/probe-em \  
-R $RS_EM -G $RG -O $ORACLE_HOME -S $ORACLE_SID -H $OIAS_LHOST \  
-U $OIAS_USER -P $OIAS_ADMIN -E $OIAS_INFRA -D $OIAS_FQDN " \  
-y Port_list=$PORT/tcp -y Network_resources_used=$RS_LH \  
-x Stop_signal=9 \  
-y Resource_dependencies=$RS_OPMN  
  
validate_registration $RS_EM $RG \  
$ORACLE_HOME $ORACLE_SID $OIAS_LHOST \  
$OIAS_USER $OIAS_ADMIN $OIAS_INFRA $OIAS_FQDN  
  
fi
```

Installing and Configuring Oracle Application Server

This section contains the procedures you need to install and configure Oracle Application Server.

▼ How to Install and Configure Oracle Application Server



Caution – Oracle 9iAS (version 9.0.2 and 9.0.3) and Oracle 10g AS (version 9.0.4) does not support installation on a hardware cluster. So for the duration of the install and post install configuration, Sun Cluster must be stopped. You should have access to the console before the next step. Your data service configuration might not be supported if you do not adhere to these requirements.

Note – This sections assumes you have setup a Cluster File System to support either the Oracle 9iAS Infrastructure or Oracle 10g AS Infrastructure installation.

1. Edit `/etc/vfstab` to temporarily remove the global mount option

As the Infrastructure mount point will be mounted while the node is in non-cluster mode you must edit `/etc/vfstab` to temporarily remove the `global` mount option, if the Infrastructure mount point is a Global File System.

It is recommended that you repeat the line and comment out the original entry and amend the copied entry to omit the `global` option.

2. Stop the Cluster

```
# scshutdown -g0 -y
```

3. Boot each Cluster Node in Non-Cluster Mode

```
ok boot -x
```

4. Take ownership of the Infrastructure File System `diskset/diskgroup`

For Solaris Volume Manager

```
# metaset -s <diskset> -f -C take
# mount <Infrastructure mount point>
```

For Veritas Volume Manager

```
# vxdg -C import <diskgroup>
# vxdg -g <diskgroup> startall
# mount <Infrastructure mount point>
```

5. Plumb the Infrastructure logical IP address

```
# ifconfig <interface> addif <logical host> up
```

6. Install the Oracle 9iAS Infrastructure

Note – Refer to [Step 7](#) if you are installing the Oracle 10g AS Infrastructure

For this section, follow the *Oracle Application Server, Installation Guide* manual to install Oracle Application Server .

a. **Enable and test the interposed logical host**

This step requires that the Sun Cluster HA for Oracle Application Server data service has been installed on all nodes that will be part of the Sun Cluster.

If you did not install the Sun Cluster HA for Oracle Application Server package during your initial Sun Cluster installation, proceed to “[Installing the Sun Cluster HA for Oracle Application Server Packages](#)” on page 21 before you continue with this step.

Note – Oracle 9iAS Infrastructure requires that the logical host is interposed for any `gethostname()` calls. You must carry out this step on all nodes that will be part of the Sun Cluster. The logical hostname being set in `LHOSTNAME` is the short name not the fully qualified name.

```
# cd /opt/SUNWsc9ias/lib
# cp libloghost_32.so.1 /usr/lib/libloghost_32.so.1
# cp libloghost_64.so.1 /usr/lib/sparcv9/libloghost_64.so.1
#
# cd /usr/lib/secure
# ln -s /usr/lib/libloghost_32.so.1 libloghost_32.so.1
#
# cd /usr/lib/secure/sparcv9
# ln -s /usr/lib/sparcv9/libloghost_64.so.1 libloghost_64.so.1
#
# su - <Oracle Application Server Userid>
$ LD_PRELOAD_32=libloghost_32.so.1
$ LHOSTNAME=<logical hostname>
$ export LHOSTNAME LD_PRELOAD_32
$
$ uname -n
<logical host>      <- The logical host should be returned
```

b. **Setting ORACLE_HOME during the install**

When prompted for the `ORACLE_HOME` variable during the install, point to a directory on the Infrastructure File System you mounted in [Step 4](#).

The hostname picked up by `runInstaller` will be the logical hostname you plumbed in [Step 5](#)

c. **Pre-task before running the configuration assistants**

After installing the software, the Oracle 9iAS installer runs the configuration assistants for the various Oracle 9iAS Infrastructure components. Prior to starting the configuration assistants, the installer will prompt to execute a script

— root.sh. Before running the root.sh script, the following needs to be done in another window. This is because OHS uses configuration information defined in apachectl and does not inherit the variable values LD_PRELOAD_32 and LHOSTNAME.

Add the following three lines to the CONFIGURATION section in apachectl (you can add these three lines just before the PIDFILE= setting in the file).

```
$ cd $ORACLE_HOME/Apache/Apache/bin
$
$ vi apachectl
```

and add the following three lines to the CONFIGURATION section in apachectl (you can add these three lines just before the PIDFILE= setting)

```
LD_PRELOAD_32=libloghost_32.so.1
LHOSTNAME=<logical hostname>
export LHOSTNAME LD_PRELOAD_32
```

d. Install Patches

Note – It is important that you follow the patch installations very carefully within the patch README files. Failure to do so will mean that certain functions within the Sun Cluster HA for Oracle Application Server will not work correctly.

Issues have been traced back to patches not being installed correctly. Oracle 9iAS version 9.0.2 requires that it is patched correctly before being used within Sun Cluster, including any post patch installation steps. Time spent here will be worthwhile in the end.

Tip – When installing patches it is worthwhile checking \$ORACLE_HOME/opmn/conf/opmn.xml to see if any more sections have been added by the patch. You should perform this check only if you are requested to run a root.sh script.

If you are requested to run a root.sh script, then before you hit OK for that script, you should check \$ORACLE_HOME/opmn/conf/opmn.xml. If any new sections have been added please include LD_LIBRARY_PATH, LD_PRELOAD_32, LHOSTNAME and DISPLAY as listed within the next step, before hitting enter to the OK message.

Check the latest release notes for any post install patches.

e. Edit opmn.xml

Stop opmn by issuing the following command

```
$ $ORACLE_HOME/opmn/bin/opmnctl stopall
```

Edit the \$ORACLE_HOME/opmn/conf/opmn.xml file and add entries for the LD_PRELOAD_32 and LHOSTNAME environment variables in the environment section for OC4J_DAS, home, OC4J_Demos, CUSTOM, etc. For example

Note – In the example below, the LD_LIBRARY_PATH value should be replaced by your \$ORACLE_HOME/lib, the DISPLAY value replaced with your logical hostname and the LHOSTNAME replaced by the fully qualified logical hostname.

```
$ cat /global/ora9ias/infra/opmn/config/opmn.xml
<ias-instance xmlns="http://www.oracle.com/ias-instance">
  <notification-server>
    <port local="6100" remote="6200" request="6003"/>
    <log-file path="/global/ora9ias/infra/opmn/logs/ons.log" level="3"/>
  </notification-server>
  <process-manager>
    <ohs gid="HTTP Server" maxRetry="3">
      <start-mode mode="ssl"/>
    </ohs>
    <oc4j maxRetry="3" instanceName="home" numProcs="1">
      <config-file path="/global/ora9ias/infra/j2ee/home/config/server.xml"/>
      <oc4j-option value="-properties"/>
      <port ajp="3000-3100" jms="3201-3300" rmi="3101-3200"/>
      <environment>
        <prop name="DISPLAY" value="ora9ias:0.0"/>
        <prop name="LD_LIBRARY_PATH" value="/global/ora9ias/infra/lib"/>
        <prop name="LHOSTNAME" value="ora9ias.com"/>
        <prop name="LD_PRELOAD_32" value="libloghost_32.so.1"/>
      </environment>
    </oc4j>
    <oc4j maxRetry="3" instanceName="OC4J_DAS" gid="OC4J_DAS" numProcs="1">
      <config-file path="/global/ora9ias/infra/j2ee/OC4J_DAS/config/server.xml"/>
      <java-option value="-server -Xincgc -Xnoclassgc -Xmx256m"/>
      <oc4j-option value="-properties"/>
      <port ajp="3001-3100" jms="3201-3300" rmi="3101-3200"/>
      <environment>
        <prop name="DISPLAY" value="ora9ias:0.0"/>
        <prop name="LD_LIBRARY_PATH" value="/global/ora9ias/infra/lib"/>
        <prop name="LHOSTNAME" value="ora9ias.com"/>
        <prop name="LD_PRELOAD_32" value="libloghost_32.so.1"/>
      </environment>
    </oc4j>
    <oc4j maxRetry="3" instanceName="OC4J_Demos" gid="OC4J_Demos" numProcs="1">
      <config-file path="/global/ora9ias/infra/j2ee/OC4J_Demos/config/server.xml"/>
      <java-option value="-Xmx512M"/>
      <oc4j-option value="-userThreads -properties"/>
      <port ajp="3001-3100" jms="3201-3300" rmi="3101-3200"/>
      <environment>
        <prop name="%LIB_PATH_ENV%" value="%LIB_PATH_VALUE"/>
        <prop name="DISPLAY" value="ora9ias:0.0"/>
        <prop name="LD_LIBRARY_PATH" value="/global/ora9ias/infra/lib"/>
        <prop name="LHOSTNAME" value="ora9ias.com"/>
        <prop name="LD_PRELOAD_32" value="libloghost_32.so.1"/>
      </environment>
    </oc4j>
  </process-manager>
</ias-instance>
```



```

        </environment>
    </oc4j>
    <custom gid="dcm-daemon" numProcs="1" noGidWildcard="true">
        <start path="/global/ora9ias/infra/dcm/bin/dcmctl daemon -logdir
/global/ora9ias/infra/dcm/logs/daemon_logs"/>
        <stop path="/global/ora9ias/infra/dcm/bin/dcmctl shutdowndaemon"/>
        <environment>
    <prop name="DISPLAY" value="ora9ias:0.0"/>
        <prop name="LD_LIBRARY_PATH" value="/global/ora9ias/infra/lib"/>
        <prop name="LHOSTNAME" value="ora9ias.com"/>
        <prop name="LD_PRELOAD_32" value="libloghost_32.so.1"/>
    </environment>
    </custom>
    <log-file path="/global/ora9ias/infra/opmn/logs/ipm.log" level="3"/>
</process-manager>
</ias-instance>

```

f. Restart OPMN

```
$ $ORACLE_HOME/opmn/bin/opmnctl startall
```

g. Update the OPMN configuration

```
$ $ORACLE_HOME/dcm/bin/dcmctl updateConfig -ct opmn
```

h. Stop all the Infrastructure processes

After the install, all the Infrastructure processes will be started. These need to be stopped so that they can be started under the control of Sun Cluster.

7. Install the Oracle 10g AS Infrastructure

Note – Refer to [Step 6](#) if you are installing the Oracle 9iAS Infrastructure

For this section, follow the *Oracle Application Server, Installation Guide* manual to install Oracle Application Server.

a. Setting ORACLE_HOME during the install

When prompted for the ORACLE_HOME during the install, point to a directory on the Infrastructure File System you mounted in [Step 4](#).

b. Install Patches

Check the latest release notes for any post install patches.

c. Stop all the Infrastructure processes

After the install, all the Infrastructure processes will be started. These need to be stopped so that they can be started under the control of Sun Cluster.

8. Prepare the other Cluster Nodes

Since the ORACLE_HOME is on shared storage, there is no need to install the software again on the other nodes within the cluster. Once the Oracle 9iAS or

Oracle 10g AS Infrastructure file system is under the control of Sun Cluster, either as a Global File System or Failover File System, the Infrastructure files can be made available to other nodes within Sun Cluster.

It is however necessary to update the oratab and emtab files in `/var/opt/oracle` on the other nodes within the cluster. If there are no other Oracle database instances on the other nodes, simply copy the two files from the first node to the second node etc. If there are other Oracle database instances, then add the `iasdb` entries from the oratab and emtab files on node 1 to the same files on node 2 etc. Create the files on node 2 if necessary.

9. Preparation if installing the Middle Tier on the same nodes as the Infrastructure.

Unlike the Oracle 9iAS or Oracle 10g AS Infrastructure, the middle tier may be installed on multiple active nodes to achieve high availability. Typically the middle tier and infrastructure are installed on separate nodes. However, you may wish to install the middle tier on the node(s) where the clustered infrastructure has been installed. This can be done by installing the middle tier on local disks of the nodes that could host the infrastructure.

However, whenever the middle tier and infrastructure share a cluster node, two `/var/opt/oracle` areas must be maintained. One for the infrastructure where the `oraInst.loc` points to the `oraInventory` directory on the shared disk and another for the middle tier instance installed on local disk on each cluster node where it's `oraInst.loc` points to another `oraInventory` directory on local disk of that node. These directories are needed for applying patches and performing other upgrades or maintenance tasks and therefore must be saved.

Note – When applying patches or upgrades on the infrastructure or middle tiers, the corresponding original copy of `/var/opt/oracle` must be reinstated and made available before the Oracle installer is invoked.

Save `/var/opt/oracle` on each cluster node where the middle tier and infrastructure are installed together.

```
# cp -rp /var/opt/oracle /var/opt/oracle_infra
```

Note – You will need to supply the directory for the Oracle 9iAS Infrastructure `/var/opt/oracle` location when you register the Sun Cluster HA for Oracle Application Server data service later on. In this case we have copied this to `/var/opt/oracle_infra`.

10. Stop the Oracle Application Server Infrastructure

For Oracle 9iAS Infrastructure

```
# su - <Oracle Application Server Userid>  
$ <Oracle Home>/bin/emctl stop
```

```
$ <Oracle Home>/opmn/bin/opmnctl stopall
$ <Oracle Home>/bin/oidctl server=oidldapd configset=0 instance=1 stop
$ <Oracle Home>/bin/oidmon stop
```

For Oracle 10g AS Infrastructure

```
# su - <Oracle Application Server Userid>
$ <Oracle Home>/bin/emctl stop iasconsole
$ <Oracle Home>/opmn/bin/opmnctl stopall
```

11. Stop the Oracle Database and Listener

```
# su - <Oracle Database Userid>
$ <Oracle Home>/bin/lsnrctl stop
$ <Oracle Home>/bin/sqlplus "/" as sysdba"
$ shutdown normal
$ quit
```

12. Edit /etc/vfstab to reinstate the global mount option

If the Infrastructure mount point is a Global File System and you temporarily removed the global option in [Step 1](#) you must now reinstate the global mount option.

You must edit `/etc/vfstab` to reinstate the global mount option. If you commented out the original entry just remove just that comment and comment out the copied entry you made in [Step 1](#).

13. Boot each Node in Cluster Mode

```
# reboot
```

Verifying the Installation and Configuration of Oracle Application Server

This section contains the procedure you need to verify the installation and configuration.

▼ How to Verify the Installation and Configuration of Oracle Application Server

This procedure does not verify that your application is highly available because you have not yet installed your data service.

Before verifying the Installation and Configuration of Oracle Application Server, ensure that the installation has been completed by following the steps in "Installing and Configuring Oracle Application Server" on page 12.

1. Start the Oracle Database and Listener

```
# su - <Oracle Database Userid>
$ <Oracle Home>/bin/lsnrctl start
$ <Oracle Home>/bin/sqlplus "/ as sysdba"
$ startup
$ quit
```

2. Start the Oracle Application Server Infrastructure

For Oracle 9iAS Infrastructure

```
# su - <Oracle Application Server Userid>
$ <Oracle Home>/bin/oidmon start
$ <Oracle Home>/bin/oidctl server=oidldapd configset=0 instance=1 start
$ <Oracle Home>/opmn/bin/opmnctl startall
$ <Oracle Home>/bin/emctl start
```

For Oracle 10g AS Infrastructure

```
# su - <Oracle Application Server Userid>
$ <Oracle Home>/opmn/bin/opmnctl startall
$ <Oracle Home>/bin/emctl start iasconsole
```

3. Verifying the Oracle 9iAS Infrastructure

```
# su - <Oracle Application Server Userid>
$
$ <Oracle Home>/bin/emctl status
EMD is up and running : 200 OK
$
$ <Oracle Home>/dcm/bin/dcmctl getstate -v
```

Current State for Instance:iasdb1.psemea14.uk.sun.com

| Component | Type | Up Status | In Sync Status |
|---------------|------|-----------|----------------|
| 1 HTTP Server | ohs | Up | True |
| 2 OC4J_DAS | oc4j | Up | True |
| 3 OC4J_Demos | oc4j | Down | True |
| 4 home | oc4j | Down | True |

4. Verifying the Oracle 10g AS Infrastructure

```
# su - <Oracle Application Server Userid>
$
$ <Oracle Home>/bin/emctl status iasconsole
Oracle Enterprise Manager 10g Application Server Control 9.0.4.0.0
Copyright (c) 2002, 2003 Oracle Corporation. All rights reserved.
Oracle 10g Application Server Control is running.
$
$ <Oracle Home>/opmn/bin/opmnctl status
```

```
Processes in Instance: 10g_inst1.psemeal2
```

| ias-component | process-type | pid | status |
|---------------|---------------|-------|--------|
| OID | OID | 17961 | Alive |
| HTTP_Server | HTTP_Server | 18065 | Alive |
| OC4J | OC4J_SECURITY | 18318 | Alive |
| dcm-daemon | dcm-daemon | 19324 | Alive |
| LogLoader | logloaderd | N/A | Down |

Installing the Sun Cluster HA for Oracle Application Server Packages

If you did not install the Sun Cluster HA for Oracle Application Server packages during your initial Sun Cluster installation, perform this procedure to install the packages. Perform this procedure on each cluster node where you are installing the Sun Cluster HA for Oracle Application Server packages. To complete this procedure, you need the Sun Java Enterprise System Accessory CD Volume 3.

If you are installing more than one data service simultaneously, perform the procedure in "Installing the Software" in *Sun Cluster 3.1 Software Installation Guide*.

Install the Sun Cluster HA for Oracle Application Server packages by using one of the following installation tools:

- The Web Start program
- The `scinstall` utility

Note – The Web Start program is *not* available in releases earlier than Sun Cluster 3.1 Data Services 10/03.

▼ How to Install the Sun Cluster HA for Oracle Application Server Packages Using the Web Start Program

You can run the Web Start program with a command-line interface (CLI) or with a graphical user interface (GUI). The content and sequence of instructions in the CLI and the GUI are similar. For more information about the Web Start program, see the `installer(1M)` man page.

1. **Become superuser of the cluster node where you are installing the Sun Cluster HA for Oracle Application Server packages.**

2. **(Optional) If you intend to run the Web Start program with a GUI, ensure that your DISPLAY environment variable is set.**
3. **Load the Sun Java Enterprise System Accessory CD Volume 3 into the CD-ROM drive.**

If the Volume Management daemon vold(1M) is running and configured to manage CD-ROM devices, it automatically mounts the CD-ROM on the /cdrom/cdrom0 directory.
4. **Change to the Sun Cluster HA for Oracle Application Server component directory of the CD-ROM.**

The Web Start program for the Sun Cluster HA for Oracle Application Server data service resides in this directory.

```
# cd /cdrom/cdrom0/components/SunCluster_HA_ORACLE9I_AS_3.1
```
5. **Start the Web Start program.**

```
# ./installer
```
6. **When you are prompted, select the type of installation.**
 - To install only the C locale, select Typical.
 - To install other locales, select Custom.
7. **Follow instructions on the screen to install the Sun Cluster HA for Oracle Application Server packages on the node.**

After the installation is finished, the Web Start program provides an installation summary. This summary enables you to view logs that the Web Start program created during the installation. These logs are located in the /var/sadm/install/logs directory.
8. **Exit the Web Start program.**
9. **Unload the Sun Java Enterprise System Accessory CD Volume 3 from the CD-ROM drive.**
 - a. **To ensure that the CD-ROM is not being used, change to a directory that does not reside on the CD-ROM.**
 - b. **Eject the CD-ROM.**

```
# eject cdrom
```

▼ How to Install the Sun Cluster HA for Oracle Application Server Packages Using the `scinstall` Utility

You need the Sun Cluster Agents CD-ROM to perform this procedure. This procedure assumes that you did not install the data services packages during your initial Sun Cluster installation.

If you installed the Sun Cluster HA for Oracle Application Server packages as part of your initial Sun Cluster installation, proceed to [“Registering and Configuring Sun Cluster HA for Oracle Application Server”](#) on page 23.

Perform this procedure on all nodes that can run Sun Cluster HA for Oracle Application Server data service.

- 1. Load the Sun Cluster Agents CD-ROM into the CD-ROM drive.**
- 2. Run the `scinstall` utility with no options.**
This step starts the `scinstall` utility in interactive mode.
- 3. Choose the menu option, Add Support for New Data Service to This Cluster Node.**
The `scinstall` utility prompts you for additional information.
- 4. Provide the path to the Sun Cluster Agents CD-ROM.**
The utility refers to the CD as the “data services cd.”
- 5. Specify the data service to install.**
The `scinstall` utility lists the data service that you selected and asks you to confirm your choice.
- 6. Exit the `scinstall` utility.**
- 7. Unload the CD from the drive.**

Registering and Configuring Sun Cluster HA for Oracle Application Server

This section contains the procedures you need to configure Sun Cluster HA for Oracle Application Server.

▼ How to Register and Configure Sun Cluster HA for Oracle Application Server as a Failover Service

This procedure assumes that you installed the data service packages during your initial Sun Cluster installation.

If you did not install the Sun Cluster HA for Oracle Application Server packages as part of your initial Sun Cluster installation, go to [“How to Install the Sun Cluster HA for Oracle Application Server Packages Using the `scinstall` Utility”](#) on page 23.

1. **Become superuser on one of the nodes in the cluster that will host Oracle Application Server.**

2. **Register the `SUNW.gds` resource type.**

```
# scrgadm -a -t SUNW.gds
```

3. **Register the `SUNW.HAStoragePlus` resource type.**

```
# scrgadm -a -t SUNW.HAStoragePlus
```

4. **Register the `SUNW.oracle_server` and `SUNW.oracle_listener` resource type.**

```
# scrgadm -a -t SUNW.oracle_server
# scrgadm -a -t SUNW.oracle_listener
```

5. **Create a failover resource group.**

```
# scrgadm -a -g Oracle Application Server-failover-resource-group
```

6. **Create a resource for the Oracle Application Server Disk Storage.**

```
# scrgadm -a -j Oracle Application Server-has-resource \
-g Oracle Application Server-failover-resource-group \
-t SUNW.HAStoragePlus \
-x FilesystemMountPoints=Oracle Application Server -Infrastructure instance-mount-points
```

7. **Create a resource for the Oracle Application Server Logical Hostname.**

```
# scrgadm -a -L -j Oracle Application Server-lh-resource \
-g Oracle Application Server-failover-resource-group \
-l Oracle Application Server-logical-hostname
```

8. **Enable the failover resource group that now includes the Oracle Application Server Disk Storage and Logical Hostname resources.**

```
# scswitch -z -g Oracle Application Server-failover-resource-group
```

9. **Create a resource for the Oracle Application Server Oracle Database.**

Note – For detailed information about Sun Cluster HA for Oracle, refer to the *Sun Cluster Data Services Installation and Configuration Guide*.

```
#
scrgadm -a -j Oracle Application Server-ORACLE-resource \
-t SUNW.oracle_server \
-g Oracle Application Server-failover-resource-group\
-x Connect_string=<user/passwd>\
-x ORACLE_SID=<Oracle 9iAS instance>\
-x ORACLE_HOME=<Oracle 9iAS Infrastructure directory> \
-x Alert_log_file=<${ORACLE_HOME} alert log file>
#
# scswitch -e -j Oracle Application Server-ORACLE-resource
```

10. Create a resource for the Oracle Application Server Oracle Listener.

Note – For detailed information about Sun Cluster HA for Oracle, refer to the *Sun Cluster Data Services Installation and Configuration Guide*.

```
# scrgadm -a -j Oracle Application Server-ORALSR-resource \
-t SUNW.oracle_listener \
-g Oracle Application Server-failover-resource-group\
-x Listener_name=<Instance>\
-x ORACLE_HOME=<Oracle 9iAS Infrastructure directory>\
#
# scswitch -e -j Oracle Application Server-ORALSR-resource
```

11. Create the Oracle 9iAS Infrastructure resources.

Note – Refer to [Step 13](#) for Oracle 10g AS Infrastructure

Edit the `9ias_config` file and follow the comments with that file, for example

```
#
# Copyright 2004 Sun Microsystems, Inc. All rights reserved.
# Use is subject to license terms.
#
# This file will be sourced in by 9ias_register and the parameters
# listed below will be used.
#
# These parameters can be customized in (key=value) form
#
#           RG - name of the SC resource group containing the resources
#   RS_OIDMON - name of the SC Oracle Internet Directory Monitor resource
#   RS_OIDLDAP - name of the SC Oracle Internet Directory resource
```

```

#       RS_OPMN - name of the SC Oracle Process Monitor Notification resource
#       RS_EM   - name of the SC Enterprise Manager Web site resource
#
#       Note: Only one Enterprise Manager is required if multiple
#             infrastructure instances are being deployed.
#
#             Omit the value to RS_EM if you do not require a SC resource
#             for the Enterprise Manager.
#
# ORACLE_HOME - name of the Oracle home directory
# ORACLE_SID  - name of the Oracle SID
# OIAS_LHOST  - name of the Oracle 9iAS Infrastructure logical hostname
# OIAS_USER   - name of the Oracle 9iAS Infrastructure userid
# OIAS_ADMIN  - name of the Oracle 9iAS Internet Directory Admin password
# OIAS_INFRA  - name of the Oracle 9iAS Infrastructure /var/opt/oracle
# OIAS_FQDN   - name of the Oracle 9iAS fully qualified domainname
# OIAS_OPMN   - name of the Oracle 9iAS OPMN instance names to start
#             e.g. OIAS_OPMN=ohs,OC4J_DAS or ALL
#             ALL indicates all instance names in $ORACLE_HOME/opmn/conf/opmn.xml
#
#       RS_LH   - name of the SC Logical Hostname resource
#       RS_HAS  - name of the SC Oracle 9iAS HAStoragePlus resource
#       RS_ORACLE - name of the SC Oracle resource
#       RS_ORALSR - name of the SC Oracle Listener resource
#

```

```

RG=
RS_OIDMON=
RS_OIDLDAP=
RS_OPMN=
RS_EM=

```

```

ORACLE_HOME=
ORACLE_SID=
OIAS_LHOST=
OIAS_USER=
OIAS_ADMIN=
OIAS_INFRA=
OIAS_FQDN=
OIAS_OPMN=

```

```

RS_LH=
RS_HAS=
RS_ORACLE=
RS_ORALSR=

```

The following is an example for Oracle Application Server for Oracle 9iAS Infrastructure.

```

RG=9ias-infra-rg
RS_OIDMON=9ias-oidmon-res
RS_OIDLDAP=9ias-oidldap-res
RS_OPMN=9ias-opmn-res
RS_EM=9ias-em-res

```

```

ORACLE_HOME=/global/ora9ias/infra

```

```

ORACLE_SID=iasdb
OIAS_LHOST=ora9ias
OIAS_USER=oraprod
OIAS_ADMIN=ias_admin
OIAS_INFRA=/var/opt/oracle or
            /var/opt/oracle_infra if the middle tier is also installed and
            /var/opt/oracle was renamed to /var/opt/oracle_infra
OIAS_FQDN=ora9ias.com
OIAS_OPMN=ohs/oc4j_das or
            all if all components are required
RS_LH=9ias-lhs-res
RS_HAS=9ias-has-res
RS_ORACLE=9ias-oracle-res
RS_ORALSR=9ias-oralsr-res

# ./9ias_register

```

12. Enable each Oracle 9iAS Infrastructure resource.

```

# scstat
#
# scswitch -e -j Oracle Application Server-OIDMON-resource
# scswitch -e -j Oracle Application Server-OIDLDAP-resource
# scswitch -e -j Oracle Application Server-OPMN-resource
# scswitch -e -j Oracle Application Server-EM-resource

```

13. Create the Oracle 10g AS Infrastructure resources.

Note – Refer to [Step 11](#) for Oracle 9iAS Infrastructure

Edit the 10gas_config file and follow the comments with that file, for example

```

#
# Copyright 2004 Sun Microsystems, Inc. All rights reserved.
# Use is subject to license terms.
#
# This file will be sourced in by 10gas_register and the parameters
# listed below will be used.
#
# These parameters can be customized in (key=value) form
#
#           RG - name of the SC resource group containing the resources
#           RS_OPMN - name of the SC Oracle Process Monitor Notification resource
#           RS_EM - name of the SC Enterprise Manager Web site resource
#
# ORACLE_HOME - name of the Oracle home directory
# ORACLE_SID - name of the Oracle SID
# OIAS_LHOST - name of the Oracle 10gAS Infrastructure logical hostname
# OIAS_USER - name of the Oracle 10gAS Infrastructure userid
# OIAS_ADMIN - name of the Oracle 10gAS Internet Directory Admin password
# OIAS_INFRA - name of the Oracle 10gAS Infrastructure /var/opt/oracle
# OIAS_FQDN - name of the Oracle 10gAS fully qualified domainname
# OIAS_OPMN - name of the Oracle 10gAS ias-components

```

```

#           e.g. OIAS_OPMN=OID/HTTP_Server/OC4J or OIAS_OPMN=all
#
#       ALL indicates all the installed ias-components
#
#       RS_LH - name of the SC Logical Hostname resource
#       RS_HAS - name of the SC Oracle 10gAS HAStoragePlus resource
#       RS_ORACLE - name of the SC Oracle resource
#       RS_ORALSR - name of the SC Oracle Listener resource
#
RG=
RS_OPMN=
RS_EM=

ORACLE_HOME=
ORACLE_SID=
OIAS_LHOST=
OIAS_USER=
OIAS_ADMIN=
OIAS_INFRA=
OIAS_FQDN=
OIAS_OPMN=

RS_LH=
RS_HAS=
RS_ORACLE=
RS_ORALSR=

```

The following is an example for Oracle Application Server for Oracle 10g AS Infrastructure.

Note – The values for OIAS_ADMIN and OIAS_FQDN are not used within the Sun Cluster HA for Oracle Application Server for Oracle 10g AS, however you need to supply a value for the registration script and therefore can supply the value dummy.

```

RG=10gas-infra-rg
RS_OPMN=10gas-opmn-res
RS_EM=10gas-em-res

ORACLE_HOME=/global/ora10gas/infra
ORACLE_SID=iasdb
OIAS_LHOST=ora10gas
OIAS_USER=oraprod
OIAS_ADMIN=dummy
OIAS_INFRA=/var/opt/oracle or
           /var/opt/oracle_infra if the middle tier is also installed and
           /var/opt/oracle was renamed to /var/opt/oracle_infra
OIAS_FQDN=dummy
OIAS_OPMN=OID/HTTP_Server/OC4J or
           all if all components are required
RS_LH=10gas-lhs-res
RS_HAS=10gas-has-res
RS_ORACLE=10gas-oracle-res

```

```
RS_ORALSR=10gas-oralsr-res
# ./10gas_register
```

14. Enable each Oracle 10g AS Infrastructure resource.

```
# scstat
#
# scswitch -e -j Oracle Application Server-OPMN-resource
# scswitch -e -j Oracle Application Server-EM-resource
```

Verifying the Sun Cluster HA for Oracle Application Server Installation and Configuration

This section contains the procedure you need to verify that you installed and configured your data service correctly.

▼ How to Verify the Sun Cluster HA for Oracle Application Server Installation and Configuration

1. Become superuser on one of the nodes in the cluster that will host Oracle Application Server.
2. Ensure all the Oracle Application Server resources are online with `scstat`.

```
# scstat
```

For each Oracle Application Server resource that is not online, use the `scswitch` command as follows.

```
# scswitch -e -j Oracle Application Server- resource
```

3. Run the `scswitch` command to switch the Oracle Application Server resource group to another cluster node, such as `node2`.

```
# scswitch -z -g Oracle Application Server-failover-resource-group -h node2
```

Understanding the Sun Cluster HA for Oracle Application Server Fault Monitor

This section describes the Sun Cluster HA for Oracle Application Server fault monitor's probing algorithm or functionality.

For conceptual information on fault monitors, see the *Sun Cluster Concepts Guide*.

Resource Properties

The Sun Cluster HA for Oracle Application Server fault monitor uses the same resource properties as resource type `SUNW.gds`. Refer to the `SUNW.gds(5)` man page for a complete list of resource properties used.

Probing Algorithm and Functionality

■ Oracle Internet Directory Monitor (OIDMON)

Note – This test is only performed for the Oracle 9iAS Infrastructure.

- Sleeps for `Thorough_probe_interval`
- Test whether the `OIDMON` process is running. If this fails, then the probe will restart the `OIDMON` resource.
- If the `OIDMON` resource is repeatedly restarted and subsequently exhausts the `Retry_count` within the `Retry_interval` then a failover is initiated for the Resource Group onto another node.

■ Oracle Internet Directory Process (OIDLDAP)

Note – This test is only performed for the Oracle 9iAS Infrastructure.

- Sleeps for `Thorough_probe_interval`
- Test whether the directory service is available by running `$ORACLE_HOME/bin/ldapsearch`. If this fails, then the probe will issue a half failure as usually the Oracle Internet Directory Monitor (`OIDMON`) process will restart the Oracle Internet Directory Process (`OIDLDAP`). If at the next probe cycle the test fails again then another half failure is issued. If two half failures are issued by successive probes, then the probe will restart the `OIDLDAP`

resource.

- If the OIDLDAP resource is repeatedly restarted and subsequently exhausts the `Retry_count` within the `Retry_interval` then a failover is initiated for the Resource Group onto another node. However, in reality because the OIDLDAP probe reports a half failure every time the test fails and that usually the OIEMON process is responsible for restarting the OIDLDAP process, it is very unlikely that a failover will be initiated.
- **Oracle Process Management and Notification (OPMN)**
 - Sleeps for `Thorough_probe_interval`
 - Test whether the OPMN process is running. If this fails, then the probe will restart the OPMN resource.
 - For Oracle 9iAS, test whether each managed OPMN component reported by `$ORACLE_HOME/dcm/bin/dcmctl getstate -v` is Up. If this fails, then the probe will try to (re)start the OPMN component. However, in reality the OPMN process is responsible for restarting these components. If the OPMN probe tries to (re)start the OPMN component and the OPMN process has already tried to start the OPMN component then the duplicate (re)start will simply be ignored.
 - For Oracle 10g AS, test whether OPMN is working by `$ORACLE_HOME/opmn/bin/opmnctl status`. If this fails, then the probe will report an error and request a restart.
 - If the OPMN resource is repeatedly restarted and subsequently exhausts the `Retry_count` within the `Retry_interval` then a failover is initiated for the Resource Group onto another node.
- **Enterprise Manager (EM)**
 - Sleeps for `Thorough_probe_interval`
 - Test whether the EM process is running. If this fails, then the probe will restart the EM resource.
 - Test whether the EM status is `EMD is up and running`. If this fails, then the probe will restart the EM resource.
 - If the EM resource is repeatedly restarted and subsequently exhausts the `Retry_count` within the `Retry_interval` then a failover is initiated for the Resource Group onto another node.

Debug Sun Cluster HA for Oracle Application Server

Sun Cluster HA for Oracle Application Server can be used by multiple Oracle Application Server instances. However, it is possible to turn on debug for all Oracle Application Server instances or a particular Oracle Application Server instance.

Each Oracle Application Server component has a `DEBUG` file in `/opt/SUNWsc9ias/etc`.

This files allows you to turn on debug for all Oracle Application Server resources or for a specific Oracle Application Server resource on a particular node with Sun Cluster. If you require debug to be turned on for Sun Cluster HA for Oracle Application Server across the whole Sun Cluster, repeat this step on all nodes within Sun Cluster.

▼ How to turn on debug for Sun Cluster HA for Oracle Application Server

1. Edit `/etc/syslog.conf` and change `daemon.notice` to `daemon.debug`.

```
# grep daemon /etc/syslog.conf
*.err;kern.debug;daemon.notice;mail.crit      /var/adm/messages
*.alert;kern.err;daemon.err                   operator
#
```

Change the `daemon.notice` to `daemon.debug` and restart `syslogd`. The output below, from the command `grep daemon /etc/syslog.conf`, shows that `daemon.debug` has now been set.

```
# grep daemon /etc/syslog.conf
*.err;kern.debug;daemon.debug;mail.crit      /var/adm/messages
*.alert;kern.err;daemon.err                   operator
#
# pkill -1 syslogd
#
```

2. Edit `/opt/SUNWsc9ias/etc/config`

Edit `/opt/SUNWsc9ias/etc/config` and change `DEBUG=` to `DEBUG=ALL` or `DEBUG=resource`

```
# cat /opt/SUNWsc9ias/etc/config
#
# Copyright 2003 Sun Microsystems, Inc. All rights reserved.
# Use is subject to license terms.
#
# Usage:
#     DEBUG=<RESOURCE_NAME> or ALL
#
DEBUG=ALL
#
```

Note – To turn off debug, reverse the steps above.

Index

C

- C locale, 22
- commands
 - scinstall, 23
 - scrgadm, 24
 - scstat, 27
 - scswitch, 24
- configuration
 - requirements, 8-12
 - restrictions, 8

D

- debug, 32

F

- fault monitor, 30
- files, installation logs, 22

I

- installing
 - Oracle Application Server
 - by using rapidwiz, 13
 - Sun Cluster HA for Oracle Application Server
 - by using Web Start program, 21-22
 - log files created, 22

L

- locales, 22
- log files, installation, 22

O

- Oracle Application Server, 6-7

R

- registering
 - Sun Cluster HA for Oracle Application Server
 - 10gas_config, 27
 - 10gas_register, 29
 - 9ias_register, 27
 - Oracle database resource, 24
 - Resource Types, 24

V

- /var/sadm/install/logs directory, 22
- verifying
 - Oracle Application Server installation, 19-21
 - Sun Cluster HA for Oracle Application Server installation, 29

W

Web Start program, 21-22