



Sun SPARC® Enterprise M3000/M4000/M5000/M8000/M9000 Servers XSCF Reference Manual

XSCF Control Package (XCP) 1080

Sun Microsystems, Inc.
www.sun.com

Part No. 820-5872-10
October 2008, Revision A

Submit comments about this document at: <http://www.sun.com/hwdocs/feedback>

Copyright 2008 Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, California 95054, U.S.A. and FUJITSU LIMITED, 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki-shi, Kanagawa-ken 211-8588, Japan. All rights reserved.

Sun Microsystems, Inc. and Fujitsu Limited each own or control intellectual property rights relating to products and technology described in this document, and such products, technology and this document are protected by copyright laws, patents and other intellectual property laws and international treaties. The intellectual property rights of Sun Microsystems, Inc. and Fujitsu Limited in such products, technology and this document include, without limitation, one or more of the United States patents listed at <http://www.sun.com/patents> and one or more additional patents or patent applications in the United States or other countries.

This document and the product and technology to which it pertains are distributed under licenses restricting their use, copying, distribution, and decompilation. No part of such product or technology, or of this document, may be reproduced in any form by any means without prior written authorization of Fujitsu Limited and Sun Microsystems, Inc., and their applicable licensors, if any. The furnishing of this document to you does not give you any rights or licenses, express or implied, with respect to the product or technology to which it pertains, and this document does not contain or represent any commitment of any kind on the part of Fujitsu Limited or Sun Microsystems, Inc., or any affiliate of either of them.

This document and the product and technology described in this document may incorporate third-party intellectual property copyrighted by and/or licensed from suppliers to Fujitsu Limited and/or Sun Microsystems, Inc., including software and font technology.

Per the terms of the GPL or LGPL, a copy of the source code governed by the GPL or LGPL, as applicable, is available upon request by the End User. Please contact Fujitsu Limited or Sun Microsystems, Inc.

This distribution may include materials developed by third parties.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and in other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, Java, Netra, Solaris, Sun Ray, Answerbook2, docs.sun.com, OpenBoot, and Sun Fire are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries.

Fujitsu and the Fujitsu logo are registered trademarks of Fujitsu Limited.

All SPARC trademarks are used under license and are registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon architecture developed by Sun Microsystems, Inc.

SPARC64 is a trademark of SPARC International, Inc., used under license by Fujitsu Microelectronics, Inc. and Fujitsu Limited.

The OPEN LOOK and Sun™ Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

United States Government Rights - Commercial use. U.S. Government users are subject to the standard government user license agreements of Sun Microsystems, Inc. and Fujitsu Limited and the applicable provisions of the FAR and its supplements.

Disclaimer: The only warranties granted by Fujitsu Limited, Sun Microsystems, Inc. or any affiliate of either of them in connection with this document or any product or technology described herein are those expressly set forth in the license agreement pursuant to which the product or technology is provided. EXCEPT AS EXPRESSLY SET FORTH IN SUCH AGREEMENT, FUJITSU LIMITED, SUN MICROSYSTEMS, INC. AND THEIR AFFILIATES MAKE NO REPRESENTATIONS OR WARRANTIES OF ANY KIND (EXPRESS OR IMPLIED) REGARDING SUCH PRODUCT OR TECHNOLOGY OR THIS DOCUMENT, WHICH ARE ALL PROVIDED AS IS, AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID. Unless otherwise expressly set forth in such agreement, to the extent allowed by applicable law, in no event shall Fujitsu Limited, Sun Microsystems, Inc. or any of their affiliates have any liability to any third party under any legal theory for any loss of revenues or profits, loss of use or data, or business interruptions, or for any indirect, special, incidental or consequential damages, even if advised of the possibility of such damages.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright 2008 Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, California 95054, U.S.A. et FUJITSU LIMITED, 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki-shi, Kanagawa-ken 211-8588, Japon. Tous droits réservés.

Sun Microsystems, Inc. et Fujitsu Limited détiennent et contrôlent toutes deux des droits de propriété intellectuelle relatifs aux produits et technologies décrits dans ce document. De même, ces produits, technologies et ce document sont protégés par des lois sur le copyright, des brevets, d'autres lois sur la propriété intellectuelle et des traités internationaux. Les droits de propriété intellectuelle de Sun Microsystems, Inc. et Fujitsu Limited concernant ces produits, ces technologies et ce document comprennent, sans que cette liste soit exhaustive, un ou plusieurs brevets déposés aux États-Unis et indiqués à l'adresse <http://www.sun.com/patents> de même qu'un ou plusieurs brevets ou applications brevetées supplémentaires aux États-Unis et dans d'autres pays.

Ce document, le produit et les technologies afférents sont exclusivement distribués avec des licences qui en restreignent l'utilisation, la copie, la distribution et la décompilation. Aucune partie de ce produit, de ces technologies ou de ce document ne peut être reproduite sous quelque forme que ce soit, par quelque moyen que ce soit, sans l'autorisation écrite préalable de Fujitsu Limited et de Sun Microsystems, Inc., et de leurs éventuels bailleurs de licence. Ce document, bien qu'il vous ait été fourni, ne vous confère aucun droit et aucune licence, expresses ou tacites, concernant le produit ou la technologie auxquels il se rapporte. Par ailleurs, il ne contient ni ne représente aucun engagement, de quelque type que ce soit, de la part de Fujitsu Limited ou de Sun Microsystems, Inc., ou des sociétés affiliées.



Adobe PostScript

Ce document, et le produit et les technologies qu'il décrit, peuvent inclure des droits de propriété intellectuelle de parties tierces protégés par copyright et/ou cédés sous licence par des fournisseurs à Fujitsu Limited et/ou Sun Microsystems, Inc., y compris des logiciels et des technologies relatives aux polices de caractères.

Cette distribution peut comprendre des composants développés par des tierces parties.

Des parties de ce produit pourront être dérivées des systèmes Berkeley BSD licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, Java, Netra, Solaris, Sun Ray, Answerbook2, docs.sun.com, OpenBoot, et Sun Fire sont des marques de fabrique ou des marques déposées de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays.

Fujitsu et le logo Fujitsu sont des marques déposées de Fujitsu Limited.

Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

SPARC64 est une marques déposée de SPARC International, Inc., utilisée sous le permis par Fujitsu Microelectronics, Inc. et Fujitsu Limited.

L'interface d'utilisation graphique OPEN LOOK et Sun™ a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciés de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui, en outre, se conforment aux licences écrites de Sun.

Droits du gouvernement américain - logiciel commercial. Les utilisateurs du gouvernement américain sont soumis aux contrats de licence standard de Sun Microsystems, Inc. et de Fujitsu Limited ainsi qu'aux clauses applicables stipulées dans le FAR et ses suppléments.

Avis de non-responsabilité: les seules garanties octroyées par Fujitsu Limited, Sun Microsystems, Inc. ou toute société affiliée de l'une ou l'autre entité en rapport avec ce document ou tout produit ou toute technologie décrit(e) dans les présentes correspondent aux garanties expressément stipulées dans le contrat de licence régissant le produit ou la technologie fourni(e). SAUF MENTION CONTRAIRE EXPRESSÉMENT STIPULÉE DANS CE CONTRAT, FUJITSU LIMITED, SUN MICROSYSTEMS, INC. ET LES SOCIÉTÉS AFFILIÉES REJETTENT TOUTE REPRÉSENTATION OU TOUTE GARANTIE, QUELLE QU'EN SOIT LA NATURE (EXPRESSE OU IMPLICITE) CONCERNANT CE PRODUIT, CETTE TECHNOLOGIE OU CE DOCUMENT, LESQUELS SONT FOURNIS EN L'ÉTAT. EN OUTRE, TOUTES LES CONDITIONS, REPRÉSENTATIONS ET GARANTIES EXPRESSES OU TACITES, Y COMPRIS NOTAMMENT TOUTE GARANTIE IMPLICITE RELATIVE À LA QUALITÉ MARCHANDE, À L'APTITUDE À UNE UTILISATION PARTICULIÈRE OU À L'ABSENCE DE CONTREFAÇON, SONT EXCLUES, DANS LA MESURE AUTORISÉE PAR LA LOI APPLICABLE. Sauf mention contraire expressément stipulée dans ce contrat, dans la mesure autorisée par la loi applicable, en aucun cas Fujitsu Limited, Sun Microsystems, Inc. ou l'une de leurs filiales ne sauraient être tenues responsables envers une quelconque partie tierce, sous quelque théorie juridique que ce soit, de tout manque à gagner ou de perte de profit, de problèmes d'utilisation ou de perte de données, ou d'interruptions d'activités, ou de tout dommage indirect, spécial, secondaire ou consécutif, même si ces entités ont été préalablement informées d'une telle éventualité.

LA DOCUMENTATION EST FOURNIE "EN L'ÉTAT" ET TOUTES AUTRES CONDITIONS, DECLARATIONS ET GARANTIES EXPRESSES OU TACITES SONT FORMELLEMENT EXCLUES, DANS LA MESURE AUTORISÉE PAR LA LOI APPLICABLE, Y COMPRIS NOTAMMENT TOUTE GARANTIE IMPLICITE RELATIVE A LA QUALITE MARCHANDE, A L'APTITUDE A UNE UTILISATION PARTICULIERE OU A L'ABSENCE DE CONTREFAÇON.

Contents

Preface	v
Intro	1
addboard	7
addcodlicense	11
addfru	13
adduser	15
applynetwork	17
cfgdevice	23
clockboard	29
console	31
deleteboard	33
deletecodlicense	37
deletefru	39
deleteuser	41
disableuser	43
dumpconfig	45
enableuser	51
exit	53
flashupdate	55
fmadm	59
fmdump	61
fmstat	69
getflashimage	73

ioxadm 79
man 89
moveboard 91
nslookup 95
password 97
ping 101
poweroff 103
poweron 107
prtfru 111
rebootxscf 115
replacefru 117
reset 119
resetdateoffset 123
restoreconfig 125
restoredefaults 133
sendbreak 139
setaltitude 141
setarchiving 143
setaudit 147
setautologout 153
setcod 155
setdate 159
setdcl 163
setdomainmode 169
setdomparam 177
setdscp 181
setdualpowerfeed 185
setemailreport 187
sethostname 191
sethttps 193
setldap 199
setlocale 203
setlocator 205
setlookup 207

setnameserver 209
setnetwork 211
setntp 217
setpasswordpolicy 221
setpowerupdelay 225
setprivileges 227
setroute 231
setshutdowndelay 235
setsntp 237
setsnmp 241
setsnmpusm 247
setsnmpvacm 251
setssh 255
settelnet 261
settimezone 263
setupfru 271
setupplatform 273
showaltitude 279
showarchiving 281
showaudit 285
showautologout 289
showboards 291
showcod 297
showcodlicense 299
showcodusage 301
showconsolepath 307
showdate 309
showdcl 311
showdevices 317
showdomainmode 323
showdomainstatus 327
showdscp 329
showdualpowerfeed 333
showemailreport 335

showenvironment 337
showfru 343
showhardconf 345
showhostname 353
showhttps 355
showldap 357
showlocale 359
showlocator 361
showlogs 363
showlookup 379
showmonitorlog 381
shownameserver 383
shownetwork 385
shownotice 391
showntp 393
showpasswordpolicy 397
showpowerupdelay 399
showresult 401
showroute 403
showshutdowndelay 407
showsmtp 409
showsnmp 411
showsnmpusm 415
showsnmpvacm 417
showssh 419
showstatus 423
showtelnet 425
showtimezone 427
showuser 431
snapshot 433
switchscf 441
testsb 443
traceroute 449
unlockmaintenance 453

version 455
viewaudit 459
who 467

Preface

This manual contains the man pages for the eXtended System Control Facility (XSCF) firmware for Sun SPARC® Enterprise M3000/M4000/M5000/M8000/M9000 servers.

Overview of Man Page Structure

The following table describes the sections included in man pages. The man pages of each manual section generally follow this order, but include only needed headings. For example, if there are no examples, there is no EXAMPLES section. Refer to the Intro page for a description of each man page, and man(1) for more information about man pages in general.

NAME	This section gives the names of the commands or functions documented, followed by a brief description of what they do.
SYNOPSIS	<p>This section shows the syntax of commands or functions. Options and arguments are alphabetized, with single-letter arguments first, and options with arguments next, unless a different argument order is required.</p> <p>The following special characters are used in this section:</p> <ul style="list-style-type: none">[] Brackets. The option or argument enclosed in these brackets is optional. If the brackets are omitted, the argument must be specified.

- ... Ellipses. Several values may be provided for the previous argument, or the previous argument can be specified multiple times, for example "filename...".
- | Separator. Only one of the arguments separated by this character can be specified at one time.
- { } Braces. The options and/or arguments enclosed within braces are interdependent, such that everything enclosed must be treated as a unit.

DESCRIPTION	This section defines the functionality and behavior of the service. Thus it describes concisely what the command does. It does not discuss OPTIONS or cite EXAMPLES.
OPTIONS	This lists the command options with a concise summary of what each option does. The options are listed literally and in alphabetical order. Possible arguments to options are discussed under the option, and where appropriate, default values are supplied.
OPERANDS	This section lists the command operands and describes how they affect the actions of the command.
EXTENDED DESCRIPTION	This section includes further description.
EXAMPLES	This section provides examples of usage or of how to use a command or function. Wherever possible, a complete example including command-line entry and machine response is shown. Most examples illustrate concepts from the SYNOPSIS, DESCRIPTION, OPTIONS, and OPERANDS sections.
EXIT STATUS	This section lists the values the command returns to the calling program or shell and the conditions that cause these values to be returned. Usually, zero is returned for successful completion and values other than zero for various error conditions.
SEE ALSO	This section lists references to other man pages.

NAME	Intro - list the commands provided by the XSCF firmware																																						
DESCRIPTION	<p>Intro(8) command lists the commands provided by the XSCF firmware of the M3000/M4000/M5000/M8000/M9000 servers.</p> <p>Some commands are used in a different way or not supported on your server. For details, refer to the pages of each command.</p>																																						
LIST OF COMMANDS	<p>In XSCF, the following commands are provided:</p> <table border="1"> <tr> <td>Intro, intro</td> <td>list the commands provided by the XSCF firmware</td> </tr> <tr> <td>addboard</td> <td>configure an eXtended System Board(XSB) into the domain configuration or assigns it to the domain configuration</td> </tr> <tr> <td>addcodlicense</td> <td>add a Capacity on Demand (COD) right-to-use (RTU) license key to the COD license database</td> </tr> <tr> <td>addfru</td> <td>add a Field Replaceable Unit (FRU)</td> </tr> <tr> <td>adduser</td> <td>create an XSCF user account</td> </tr> <tr> <td>applynetwork</td> <td>reflect the information that has been set for the XSCF network</td> </tr> <tr> <td>cfgdevice</td> <td>connect a CD-RW/DVD-RW and TAPE drive unit to the port, disconnect it from the port, or display the status of the drive</td> </tr> <tr> <td>clockboard</td> <td>set or display the clock control unit used at system startup</td> </tr> <tr> <td>console</td> <td>connect to a domain console</td> </tr> <tr> <td>deleteboard</td> <td>disconnect an eXtended System Board (XSB) from the domain configuration</td> </tr> <tr> <td>deletecodlicense</td> <td>remove a Capacity on Demand (COD) right-to-use (RTU) license key from the COD license database</td> </tr> <tr> <td>deletefru</td> <td>delete a Field Replaceable Unit (FRU)</td> </tr> <tr> <td>deleteuser</td> <td>delete an XSCF user account</td> </tr> <tr> <td>disableuser</td> <td>disable an XSCF user account</td> </tr> <tr> <td>dumpconfig</td> <td>save system configuration information</td> </tr> <tr> <td>enableuser</td> <td>enable an XSCF user account</td> </tr> <tr> <td>exit</td> <td>exit the XSCF shell</td> </tr> <tr> <td>flashupdate</td> <td>update the firmware</td> </tr> <tr> <td>fmadm</td> <td>fault management configuration tool</td> </tr> </table>	Intro, intro	list the commands provided by the XSCF firmware	addboard	configure an eXtended System Board(XSB) into the domain configuration or assigns it to the domain configuration	addcodlicense	add a Capacity on Demand (COD) right-to-use (RTU) license key to the COD license database	addfru	add a Field Replaceable Unit (FRU)	adduser	create an XSCF user account	applynetwork	reflect the information that has been set for the XSCF network	cfgdevice	connect a CD-RW/DVD-RW and TAPE drive unit to the port, disconnect it from the port, or display the status of the drive	clockboard	set or display the clock control unit used at system startup	console	connect to a domain console	deleteboard	disconnect an eXtended System Board (XSB) from the domain configuration	deletecodlicense	remove a Capacity on Demand (COD) right-to-use (RTU) license key from the COD license database	deletefru	delete a Field Replaceable Unit (FRU)	deleteuser	delete an XSCF user account	disableuser	disable an XSCF user account	dumpconfig	save system configuration information	enableuser	enable an XSCF user account	exit	exit the XSCF shell	flashupdate	update the firmware	fmadm	fault management configuration tool
Intro, intro	list the commands provided by the XSCF firmware																																						
addboard	configure an eXtended System Board(XSB) into the domain configuration or assigns it to the domain configuration																																						
addcodlicense	add a Capacity on Demand (COD) right-to-use (RTU) license key to the COD license database																																						
addfru	add a Field Replaceable Unit (FRU)																																						
adduser	create an XSCF user account																																						
applynetwork	reflect the information that has been set for the XSCF network																																						
cfgdevice	connect a CD-RW/DVD-RW and TAPE drive unit to the port, disconnect it from the port, or display the status of the drive																																						
clockboard	set or display the clock control unit used at system startup																																						
console	connect to a domain console																																						
deleteboard	disconnect an eXtended System Board (XSB) from the domain configuration																																						
deletecodlicense	remove a Capacity on Demand (COD) right-to-use (RTU) license key from the COD license database																																						
deletefru	delete a Field Replaceable Unit (FRU)																																						
deleteuser	delete an XSCF user account																																						
disableuser	disable an XSCF user account																																						
dumpconfig	save system configuration information																																						
enableuser	enable an XSCF user account																																						
exit	exit the XSCF shell																																						
flashupdate	update the firmware																																						
fmadm	fault management configuration tool																																						

<code>fmddump</code>	view fault management logs
<code>fmstat</code>	report fault management module statistics
<code>getflashimage</code>	download a firmware image file
<code>ioxadm</code>	manage External I/O Expansion Units
<code>man</code>	display manual pages of specified XSCF shell command
<code>moveboard</code>	move an eXtended System Board (XSB) from the current domain to another
<code>nslookup</code>	refer to the DNS server for the host
<code>password</code>	manage user passwords and expiration settings
<code>ping</code>	sends the ICMP ECHO_REQUEST packets to the network host or the network device
<code>poweroff</code>	turn off the power to the specified domain
<code>poweron</code>	turn on the power to the specified domain
<code>prtfru</code>	display FRUID data on the system and External I/O Expansion Unit
<code>rebootxscf</code>	reset the XSCF
<code>replacefru</code>	replace a Field Replaceable Unit (FRU)
<code>reset</code>	reset the specified domain
<code>resetdateoffset</code>	reset the time subtraction between XSCF and the domain.
<code>restoreconfig</code>	restore the system configuration information previously saved by <code>dumpconfig</code>
<code>restoredefaults</code>	delete the setting and the log information that stored in the server or the XSCF unit, and restore it to the state as of the factory shipment
<code>sendbreak</code>	send a break signal to the specified domain
<code>setaltitude</code>	set the altitude of the system or whether or not the air filter installed
<code>setarchiving</code>	configure the log archiving functionality
<code>setaudit</code>	manage the system auditing functionality
<code>setautologout</code>	set the session timeout time of the XSCF shell
<code>setcod</code>	set up the Capacity on Demand (COD) resources used for domains
<code>setdate</code>	set the date and time of XSCF

<code>setdcl</code>	set a domain component list (DCL)
<code>setdomainmode</code>	set a domain mode
<code>setdomparam</code>	forcibly rewrite OpenBoot PROM environment variables
<code>setdscp</code>	set the IP address assignments for the Domain to Service Processor Communications Protocol (DSCP)
<code>setdualpowerfeed</code>	set dual power feed mode
<code>setemailreport</code>	set up the email report configuration data
<code>sethostname</code>	set a host name and domain name for an XSCF unit
<code>sethttps</code>	start or stop the HTTPS service, which is used in the XSCF network. This command also performs authentication-related settings.
<code>setldap</code>	configure the Service Processor as a Lightweight Directory Access Protocol (LDAP) client
<code>setlocale</code>	sets the default locale of the XSCF
<code>setlocator</code>	control the blinking of the CHECK LED on the operator panel
<code>setlookup</code>	enable or disable the use of the Lightweight Directory Access Protocol (LDAP) server for authentication and privilege lookup
<code>setnameserver</code>	set the domain name system (DNS) servers used in the XSCF network
<code>setnetwork</code>	sets or removes the network interface that used in XSCF
<code>setntp</code>	set the NTP servers used in the XSCF network
<code>setpasswordpolicy</code>	manage the system password policy
<code>setpowerupdelay</code>	set the warm-up time of the system and wait time before system startup
<code>setprivileges</code>	assign user privileges
<code>setroute</code>	set routing information for an XSCF network interface
<code>setshutdowndelay</code>	set the shutdown wait time at power interruption of the uninterruptible power supply (UPS)
<code>setsmtp</code>	set up the Simple Mail Transfer Protocol (SMTP) settings
<code>setsnmp</code>	manage the SNMP agent
<code>setsnmpusm</code>	specify the SNMPv3 agent's User-based Security Model (USM) configuration

setsnmpvacm	modify the SNMPv3 agent's View-based Access Control Model (VACM) configuration
setssh	set the SSH service used in the XSCF network. Also, generate the host public key, and register or delete the user public key, which are necessary for the SSH service
settelnet	start or stop the telnet service used in the XSCF network
settimezone	set the time zone and Daylight Saving Time of XSCF
setupfru	set up device hardware
setupplatform	set up platform specific settings
showaltitude	display the altitude of the system and whether the air filter installed
showarchiving	display log archiving configuration and status
showaudit	display the current auditing system state
showautologout	display the session timeout time of the XSCF shell
showboards	display information on an eXtended System Board (XSB)
showcod	display Capacity on Demand (COD) configuration information
showcodlicense	display the current Capacity on Demand (COD) right-to-use (RTU) licenses stored in the COD license database
showcodusage	display the current usage statistics for Capacity on Demand (COD) resources
showconsolepath	display information on the domain console that is currently connected
showdate	show the date and time of XSCF
showdcl	display the current domain component list (DCL)
showdevices	display current information on an eXtended System Board (XSB)
showdomainmode	display the domain mode
showdomainstatus	display the current domain component list (DCL)
showdscp	display the IP addresses assigned to the Domain to Service Processor Communications Protocol (DSCP)
showdualpowerfeed	display the current setting of dual power feed mode
showemailreport	display the email report configuration data

showenvironment	display the intake air temperature and humidity, temperature sensor information, voltage sensor information, and fan speed information about the system
showfru	display the hardware settings of specified device
showhardconf	display information about Field Replaceable Units (FRUs) installed in the system
showhostname	display the current host name for the XSCF unit
showhttps	display the status of the HTTPS service set for the XSCF network
showldap	display the Lightweight Directory Access Protocol (LDAP) configuration for the Service Processor
showlocale	display the current setting for the XSCF locale
showlocator	display the state of the CHECK LED on the operator panel
showlogs	display the specified log
showlookup	display the configuration for authentication and privileges lookup
showmonitorlog	display the contents of monitoring messages in real time.
shownameserver	display the registered domain name system (DNS) servers specified on the XSCF network
shownetwork	display information of network interfaces for XSCF
shownotice	display copyright and license information for the copyright information for eXtended System Control Facility (XSCF) Control Package (XCP)
showntp	display the NTP servers currently set for the XSCF network
showpasswordpolicy	display the current password settings
showpowerupdelay	display the current settings for the warm-up time of the system and wait time before system startup
showresult	display the exit status of the most recently executed command
showroute	display routing information for an XSCF network interface
showshutdowndelay	show the shutdown wait time at power interruption of the uninterruptible power supply (UPS)
showsmtp	display the Simple Mail Transfer Protocol (SMTP) configuration information

showsnmp	display the configuration information and current status of the SNMP agent
showsnmpusm	display the current User-based Security Model (USM) information for the SNMP agent
showsnmpvacm	display the current View-based Access Control Access (VACM) information for the SNMP agent
showssh	display the status, host public keys, fingerprint, or user public keys of the SSH service configured for the XSCF network
showstatus	display the degraded Field Replaceable Units (FRUs)
showtelnet	display the current status of the telnet service for the XSCF network
showtimezone	display the XSCF time zone and Daylight Saving Time information of current settings
showuser	display user account information
snapshot	collect and transfer environment, log, error, and FRUID data
switchscf	switch the XSCF unit between the active and standby states
testsb	perform an initial diagnosis of the specified physical system board (PSB)
traceroute	displays the route packets take to the specified network host or the network device
unlockmaintenance	forcibly release the locked status of XSCF
version	display firmware version
viewaudit	display audit records
who	display a list of the user accounts who are logged in to the XSCF

NAME	addboard - configure an eXtended System Board (XSB) into the domain configuration or assign it to the domain configuration
SYNOPSIS	<p>addboard [[-q] -{y n}] [-f] [-v] [-c configure] -d <i>domain_id</i> <i>xsb</i> [<i>xsb...</i>]</p> <p>addboard [[-q] -{y n}] [-f] [-v] -c assign -d <i>domain_id</i> <i>xsb</i> [<i>xsb...</i>]</p> <p>addboard [[-q] -{y n}] [-f] [-v] -c reserve -d <i>domain_id</i> <i>xsb</i> [<i>xsb...</i>]</p> <p>addboard -h</p>
DESCRIPTION	<p>The <code>addboard(8)</code> command, based on domain component list (DCL), configures a XSB into the domain configuration or assigns it to the domain configuration.</p> <p>The <code>addboard(8)</code> command is not available on the M3000 server.</p> <p>One of the following configuration methods can be specified:</p> <p><code>configure</code> Configures an XSB into the specified domain configuration. The incorporated XSB can be accessed from the Solaris OS.</p> <p><code>assign</code> Assigns an XSB to the specified domain. The assigned XSB is reserved for the specified domain and cannot be configured in or assigned to other domains. The assigned XSB is configured in the domain by reboot or execution of the <code>addboard(8)</code> command with "<code>-c configure</code>".</p> <p><code>reserve</code> Reserves incorporation of an XSB into the domain configuration. The action of "<code>reserve</code>" is the same as "<code>assign</code>".</p>
Privileges	<p>You must have one of the following privileges to run this command:</p> <p><code>platadm</code> Can run this command for all domains.</p> <p><code>domainadm</code> Can run this command only for your managed domains.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p><code>-c assign</code> Assigns an XSB to the domain configuration. If the <code>-c</code> option is omitted, "<code>-c configure</code>" is used.</p> <p><code>-c configure</code> Configures an XSB in the domain configuration. If the <code>-c</code> option is omitted, "<code>-c configure</code>" is used.</p> <p><code>-c reserve</code> Reserves incorporation of an XSB into the domain configuration. If the <code>-c</code> option is omitted, "<code>-c configure</code>" is used.</p>

-d *domain_id* Specifies the ID of the domain in which an XSB is to be configured or to which it is to be assigned. *domain_id* can be 0–23 depending on the system configuration.

-f Forcibly incorporates into a domain an XSB.

Caution – If the **-f** option is used to forcibly add an XSB to a domain, all the added hardware resources may not work normally. For this reason, use of the **-f** option is not recommended in normal operation. If the **-f** option must be specified, verify the status of every added XSB and device.

-h Displays usage statement. When used with other options or operands, an error occurs.

-n Automatically answers "n" (no) to all prompts.

-q Suppresses all messages to stdout, including prompts.

-v Displays a detailed message. If this option is specified with the **-q** option, the **-v** option is ignored.

-y Automatically answers "y" (yes) to all prompts.

OPERANDS

The following operand is supported:

xsb Specifies the XSB number to be configured or assigned. Multiple *xsb* operands are permitted, separated by spaces. The following *xsb* form is accepted:

x-y

where:

x An integer from 00–15.

y An integer from 0–3.

EXTENDED DESCRIPTION

- When the command is executed, a prompt to confirm execution of the command with the specified options is displayed. Enter "y" to execute the command or "n" to cancel the command.
- If "**-c configure**" is specified when either the domain power has been turned off or the Solaris OS is not running, an error occurs.
- When "**-c configure**" is specified, hardware diagnosis is performed on the XSB before it is incorporated into the domain. Therefore, command execution may take time.

- To use the `addboard(8)` command to configure or assign an XSB, DCL must be set up in advance using the `setdcl(8)` command.
- If the `addboard(8)` command is executed under the progress of power-on or power-off processing, the busy status is returned. After that processing in the domain is completed, reexecute the command.
- See the `setdcl(8)` and `showdcl(8)` commands for DCL.

EXAMPLES

EXAMPLE 1 Configures XSB#00-0, #01-0, #02-0, and #03-0 into domain ID 0.

```
XSCF> addboard -y -c assign -d 0 00-0 01-0 02-0 03-0
```

EXAMPLE 2 Configures XSB#00-0, #01-0, #02-0, and #03-0 forcibly into domain ID 2.

```
XSCF> addboard -f -d 2 00-0 01-0 02-0 03-0
```

EXIT STATUS

The following exit values are returned:

- | | |
|----|------------------------|
| 0 | Successful completion. |
| >0 | An error occurred. |

SEE ALSO

`deleteboard(8)`, `moveboard(8)`, `replacefru(8)`, `setdcl(8)`, `setdomainmode(8)`, `setupfru(8)`, `showboards(8)`, `showdcl(8)`, `showdevices(8)`, `showdomainstatus(8)`, `showfru(8)`, `testsb(8)`

addboard(8)



NAME	addcodlicense - add a Capacity on Demand (COD) right-to-use (RTU) license key to the COD license database
SYNOPSIS	addcodlicense <i>license-signature</i> addcodlicense -h
DESCRIPTION	<p>addcodlicense(8) adds the COD RTU specified license key to the COD license database on the Service Processor.</p> <p>The addcodlicense(8) command is not available on the M3000 server.</p> <p>When the license key is added, the quantity of headroom is reduced by the quantity provided by the license key. The quantity of headroom cannot be lower than 0.</p> <p>Note – Before you run this command, you must obtain a COD license key. To obtain a license key, contact your sales representative. For details on COD RTU license keys, refer to the <i>COD User's Guide</i> for your server.</p>
Privileges	<p>You must have platadm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following option is supported:</p> <p>-h Displays usage statement.</p> <p> When used with other options or operands, an error occurs.</p>
OPERANDS	<p>The following operands are supported:</p> <p><i>license-signature</i> Specifies the COD RTU license key to be added to the COD license database.</p>
EXAMPLES	<p>EXAMPLE 1 Adding a COD RTU License Key</p> <pre>XSCF> addcodlicense \ 01:84000000:104:0301010100:3:00000000:xxxxxxxxxxxxxxxxxxxxxxxx</pre>
EXIT STATUS	<p>The following exit values are returned:</p> <p>0 Successful completion.</p> <p>>0 An error occurred.</p>
SEE ALSO	deletecodlicense (8), setcod (8), showcod (8), showcodlicense (8), showcodusage (8)

addcodlicense(8)



NAME	addfru - add a Field Replaceable Unit (FRU)
SYNOPSIS	addfru addfru -h
DESCRIPTION	<p>The <code>addfru(8)</code> command adds an FRU.</p> <p>The <code>addfru(8)</code> command enables the user to make the settings that are required for FRU addition and related to selecting, confirming, and mounting FRUs, interactively using menus.</p> <p>The following FRUs can be added by the <code>addfru(8)</code> command:</p> <ul style="list-style-type: none"> ■ CPU/Memory Board unit (CMU) ■ I/O unit (IOU) ■ Fan unit (FANU) ■ Power supply unit (PSU)
Privileges	<p>You must have <code>fieldeng</code> privileges to run this command.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>
OPTIONS	<p>The following option is supported:</p> <p><code>-h</code> Displays usage statement.</p>
EXIT STATUS	<p>The following exit values are returned:</p> <p>0 Successful completion.</p> <p>>0 An error occurred.</p>
SEE ALSO	deletefru(8) , replacefru(8) , setupfru(8) , showfru(8) , showhardconf(8) , testsb(8) , unlockmaintenance(8)

addfru(8)



NAME	adduser - create an XSCF user account
SYNOPSIS	adduser [-u <i>UID</i>] <i>user</i> adduser -h
DESCRIPTION	<p>adduser(8) creates a new local XSCF user account. This account is used to configure, operate, manage and administrate the XSCF firmware. Initially, this account has no password. It cannot be used for login until either the password is set (using password(8)) or Secure Shell (SSH) public key authentication is set for the user. The new account will be locked but not disabled. The system can support up to 100 local users with an average length of 10 characters for the <i>user</i> operand.</p> <p>When invoked without the -u option, adduser automatically assigns a UID for the user account. When invoked with the -u option adduser assigns the given UID to the user account. Automatic UIDs are assigned starting from 100.</p> <p>If the Service Processor is configured to use Lightweight Directory Access Protocol (LDAP) for user account data, the user name and UID (if specified) must not already be in use, either locally or in LDAP.</p> <p>When a user is created, adduser(8) command stores the current password policy values in a file for the user. For more information on setting password policy see, setpasswordpolicy(8).</p>
Privileges	<p>You must have useradm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported.</p> <p>-h Displays usage statement.</p> <p> When used with other options or operands, an error occurs.</p> <p>-u <i>UID</i> Creates a new user with the given user identifier (UID). Specifying a UID is optional. If specified, the UID must be greater than or equal to 100; and 65534 and 65535 are reserved. If not specified, a UID is automatically assigned.</p>
OPERANDS	<p>The following operand is supported:</p> <p><i>user</i> Specifies a valid user name to be added. The maximum length of the user name is 31 characters. New local XSCF user account can be combination of alpha-numeric, "-", or "_". Any combination of upper and lower case letters can be used. The first character must be an alphabetical character ("jsmith", "j_smith", "j_smith-0123", or "J_Smith-0123" for example).</p>

EXAMPLES

EXAMPLE 1 Creating a New User

```
XSCF> adduser -u 359 jsmith
```

EXIT STATUS

The following exit values are returned:

0 Successful completion.

>0 An error occurred.

SEE ALSO

deleteuser(8), disableuser(8), enableuser(8), password(8), setldap(8), setpasswordpolicy(8), showldap(8), showpasswordpolicy(8), showuser(8)

NAME	applynetwork - reflect the information that has been set for the XSCF network										
SYNOPSIS	applynetwork [[-q] -{y n}] [-M] applynetwork -h										
DESCRIPTION	<p>applynetwork(8) command reflects the information that has been set for the XSCF network to XSCF.</p> <p>When you set one of the following for the XSCF network, it is necessary to execute the applynetwork(8) command to reflect the information to XSCF.</p> <ul style="list-style-type: none"> ■ XSCF host name ■ DNS domain name ■ IP address ■ netmask ■ routing <p>When you execute the applynetwork(8) command, it displays the information which has been set to XSCF host name, DNS domain name, name server, IP address, net mask, and routing. After reflected the information of XSCF network, use the rebootxscf(8) command to reset XSCF, to complete the setting.</p> <p>Note – If XSCF is reset without executing the applynetwork(8) command, network information that is set is not reflected in XSCF. Also, information that is set is deleted.</p>										
Privileges	<p>You must have platadm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>										
OPTIONS	<p>The following options are supported:</p> <table border="0" style="width: 100%;"> <tr> <td style="padding-right: 20px;">-h</td> <td>Displays usage statement. When used with other options or operands, an error occurs.</td> </tr> <tr> <td style="padding-right: 20px;">-M</td> <td>Displays text by page. This option provides a function that is the same as that of the more command.</td> </tr> <tr> <td style="padding-right: 20px;">-n</td> <td>Automatically answers "n" (no) to all prompts.</td> </tr> <tr> <td style="padding-right: 20px;">-q</td> <td>Suppresses all messages to stdout, including prompts.</td> </tr> <tr> <td style="padding-right: 20px;">-y</td> <td>Automatically answers "y" (yes) to all prompts.</td> </tr> </table>	-h	Displays usage statement. When used with other options or operands, an error occurs.	-M	Displays text by page. This option provides a function that is the same as that of the more command.	-n	Automatically answers "n" (no) to all prompts.	-q	Suppresses all messages to stdout, including prompts.	-y	Automatically answers "y" (yes) to all prompts.
-h	Displays usage statement. When used with other options or operands, an error occurs.										
-M	Displays text by page. This option provides a function that is the same as that of the more command.										
-n	Automatically answers "n" (no) to all prompts.										
-q	Suppresses all messages to stdout, including prompts.										
-y	Automatically answers "y" (yes) to all prompts.										
EXTENDED DESCRIPTION	<ul style="list-style-type: none"> ■ When the command is executed, a prompt to confirm execution of the command with the specified options is displayed. Enter "y" to execute the command or "n" to cancel the command. 										

- Unless all of the host name, DNS domain name, IP address, net mask, and routing settings have been made on the target interface, it results in errors. Please execute the `sethostname(8)` and `setnetwork(8)` command to set all items, then reexecute the `applynetwork(8)` command.
- To set to multiple interfaces, all of the host name, DNS domain name, IP address, and net mask settings need to be set on every interface. In these interfaces, if any of these setting items omitted, it results in errors.
- To specify a host name, use the `sethostname(8)` command. To specify an IP address and net mask, use the `setnetwork(8)` command.
- When the status is down in all network interfaces, it results in errors.
- On the M8000/M9000 servers, when you set different netmask in the following interfaces, it results in errors.
 - `xscf#0-lan#0`, `xscf#1-lan#0`, `lan#0`
 - `xscf#0-lan#1`, `xscf#1-lan#1`, `lan#1`
 - `xscf#0-if`, `xscf#1-if`

EXAMPLES

EXAMPLE 1 Reflects the information that has been set for the XSCF network.

On the M3000/M4000/M5000 servers:

```
XSCF> applynetwork
```

The following network settings will be applied:

```
xscf#0 hostname :hostname-0
DNS domain name :example.com
nameserver      :10.23.4.3

interface       :xscf#0-lan#0
status          :up
IP address      :10.24.144.214
netmask         :255.255.255.0
route          :-n 0.0.0.0 -m 0.0.0.0 -g 10.24.144.1

interface       :xscf#0-lan#1
status          :down
IP address      :
netmask         :
```

```
route :
```

```
Continue? [y|n] :y
```

On the M8000/M9000 servers:

```
XSCF> applynetwork
```

The following network settings will be applied:

```
xscf#0 hostname :hostname-0
```

```
xscf#1 hostname :hostname-1
```

```
DNS domain name :example.com
```

```
nameserver :10.23.4.3
```

```
interface :xscf#0-lan#0
```

```
status :up
```

```
IP address :10.24.144.214
```

```
netmask :255.255.255.0
```

```
route : -n 0.0.0.0 -m 0.0.0.0 -g 10.24.144.1
```

```
interface :xscf#0-lan#1
```

```
status :down
```

```
IP address :
```

```
netmask :
```

```
route :
```

```
interface :xscf#0-if
```

```
status :down
```

```
IP address :10.24.100.1
```

```
netmask :255.255.255.0
```

```
interface :lan#0
```

```
status :down
```

```
IP address :
```

```
netmask :
```

```

interface      :xscf#1-lan#0
status         :up
IP address     :10.24.144.215
netmask       :255.255.255.0
route         : -n 0.0.0.0 -m 0.0.0.0 -g 10.24.144.1

```

```

interface      :xscf#1-lan#1
status         :down
IP address     :
netmask       :
route         :

```

```

interface      :xscf#1-if
status         :down
IP address     :10.24.100.2
netmask       :255.255.255.0

```

```

interface      :lan#1
status         :down
IP address     :
netmask       :

```

Continue? [y|n] :**y**

EXAMPLE 2 Reflects the information that has been set for the XSCF network, on the M3000/M4000/M5000 servers. Automatically answers "y" to all prompts.

XSCF> **applynetwork -y**

The following network settings will be applied:

```

xscf#0 hostname :hostname-0
DNS domain name :example.com
nameserver      :10.23.4.3

```



```

interface      :xscf#0-lan#0
status         :up
IP address     :10.24.144.214
netmask       :255.255.255.0
route         :-n 0.0.0.0 -m 0.0.0.0 -g 10.24.144.1

interface      :xscf#0-lan#1
status         :down
IP address     :
netmask       :
route         :
```

Continue? [y|n] :**y**

Please reset the XSCF by `rebootxscf` to apply the network settings.

Please confirm that the settings have been applied by executing `showhostname`, `shownetwork`, `showroute` and `shownameserver` after rebooting the XSCF.

EXAMPLE 3 Reflects the information that has been set for the XSCF network. Suppresses prompts, and automatically answers "y" to all prompts.

```
XSCF> applynetwork -q -y
```

EXIT STATUS

The following exit values are returned:

```

0           Successful completion.
>0         An error occurred.
```

SEE ALSO

`rebootxscf(8)`, `sethostname(8)`, `setnameserver(8)`, `setnetwork(8)`, `setroute(8)`

applynetwork(8)



NAME	cfgdevice - connect the CD-RW/DVD-RW drive unit and the tape drive unit to the port, disconnect it from the port, or display the status of the drive				
SYNOPSIS	<pre> cfgdevice [[-q] -{y n}] -c attach -p <i>port_no</i> cfgdevice [[-q] -{y n}] -c detach -p <i>port_no</i> cfgdevice -l [-M] cfgdevice -h </pre>				
DESCRIPTION	<p>The <code>cfgdevice(8)</code> connects the CD-RW/DVD-RW drive unit and the tape drive unit to the specified port, disconnects it from the domain, or displays the current status.</p> <p>The <code>cfgdevice(8)</code> command is available only for the M8000/M9000 servers.</p> <p>To connect the CD-RW/DVD-RW drive unit and the tape drive unit, the port number which is a PCI slot number on the I/O unit which installed IOU Onboard Device Card A (IOUA) needs to specify. Executing the <code>cfgdevice(8)</code> command, the CD-RW/DVD-RW drive unit and the tape drive unit is connected to specified port by the built-in switching unit.</p> <p>The current status of the drive that is displayed with this command includes the following types of status information:</p> <table border="0" style="margin-top: 10px;"> <tr> <td style="padding-right: 20px;"><code>port_no</code></td> <td>Port number of the port where the IOUA is installed and that can be connected to the CD-RW/DVD-RW drive unit and the tape drive unit. It is displayed in the "<i>IOU number-PCI slot number</i>" format.</td> </tr> <tr> <td style="padding-right: 20px;"><code>IOU/SAS-status</code></td> <td> Connection status between IOUA and built-in switching unit. It is changed by specifying "attach" or "detach." <ul style="list-style-type: none"> ■ enable/disable: Setting status of the <code>cfgdevice(8)</code> command <ul style="list-style-type: none"> enable: Connected with "-c attach." disable: Not connected. ■ up/down: Logical connection between IOUA and built-in switching unit. <ul style="list-style-type: none"> up: Connected. down: Not connected. </td> </tr> </table>	<code>port_no</code>	Port number of the port where the IOUA is installed and that can be connected to the CD-RW/DVD-RW drive unit and the tape drive unit. It is displayed in the " <i>IOU number-PCI slot number</i> " format.	<code>IOU/SAS-status</code>	Connection status between IOUA and built-in switching unit. It is changed by specifying "attach" or "detach." <ul style="list-style-type: none"> ■ enable/disable: Setting status of the <code>cfgdevice(8)</code> command <ul style="list-style-type: none"> enable: Connected with "-c attach." disable: Not connected. ■ up/down: Logical connection between IOUA and built-in switching unit. <ul style="list-style-type: none"> up: Connected. down: Not connected.
<code>port_no</code>	Port number of the port where the IOUA is installed and that can be connected to the CD-RW/DVD-RW drive unit and the tape drive unit. It is displayed in the " <i>IOU number-PCI slot number</i> " format.				
<code>IOU/SAS-status</code>	Connection status between IOUA and built-in switching unit. It is changed by specifying "attach" or "detach." <ul style="list-style-type: none"> ■ enable/disable: Setting status of the <code>cfgdevice(8)</code> command <ul style="list-style-type: none"> enable: Connected with "-c attach." disable: Not connected. ■ up/down: Logical connection between IOUA and built-in switching unit. <ul style="list-style-type: none"> up: Connected. down: Not connected. 				

SAS-status Connection status between I/O unit and the system.

- enable/disable: Connection setting between I/O unit and the system. When starting a domain with no I/O unit, the "disable" may be displayed.
 - enable: Yes
 - disable: No
- up/down: Logical connection between I/O unit and the system.
 - up: Connected.
 - down: Not connected.

Privileges You must have `platadm` or `fieldeng` privileges to run this command.
Refer to `setprivileges(8)` for more information.

OPTIONS The following options are supported:

-c attach Connects the CD-RW/DVD-RW drive unit and the tape drive unit to the specified port.

-c detach Disconnects the CD-RW/DVD-RW drive unit and the tape drive unit from the specified port.

-h Displays usage statement. When used with other options or operands, an error occurs.

-l Displays the current status of the CD-RW/DVD-RW drive unit and the tape drive unit currently set up.

-M Displays text by page. This option provides a function that is the same as that of the `more` command.

-n Automatically answers "n" (no) to all prompts.

-p *port_no* Specifies the number of the port, in the specified domain, to which the CD-RW/DVD-RW drive unit and the tape drive unit is to be connected. *port_no* can be specified in the '*I/O number-PCI slot number*' format. The -p option cannot be omitted.

-q Suppresses all messages to stdout, including prompts.

-y Automatically answers "y" (yes) to all prompts.

EXTENDED DESCRIPTION ■ When the command is executed, a prompt to confirm execution of the command with the specified options is displayed. Enter "y" to execute the command or "n" to cancel the command.

- If connection or disconnection is made when the power supply of the system is ON, settings are made immediately after `cfgdevice(8)` command execution. When the power supply of the system is OFF, connection or disconnection is reserved and settings are made after the power supply is turned on.
- The CD-RW/DVD-RW and the tape connection is maintained even if the domain configuration is changed, or a CPU/Memory Board unit (CMU) or I/O unit (IOU) is replaced with a connected CD-RW/DVD-RW drive unit and the tape drive unit.
- The CD-RW/DVD-RW and the tape connection is maintained even if the domain power is turned off or the system is rebooted.
- The CD-RW/DVD-RW drive unit and the tape drive unit is mounted in each of the base and expansion cabinets in the M9000 server that has the expansion cabinet. In such cases, each CD-RW/DVD-RW drive unit and the tape drive unit can be connected only to a domain within the cabinet in which the drive is mounted. Settings for connection must be made for both the base cabinet and expansion cabinet.

```
XSCF> cfgdevice -l
```

```
Current connection for DVD/DAT:
```

```
  Main chassis:      port 0-0
```

```
  Expansion chassis: port 8-0
```

```
Expander status
```

```
Port No.  IOU/SAS-status  SAS-status
```

```
-----
```

0-0	enable up	enable up
0-2	disable down	enable up
0-4	disable down	enable up
0-6	disable down	enable up
1-0	disable down	enable up
1-2	disable down	enable up
1-4	disable down	enable up
1-6	disable down	enable up
2-0	disable down	enable up
2-2	disable down	enable up
2-4	disable down	enable up
2-6	disable down	enable up
8-0	enable up	enable up

```

8-2      disable down  enable  up
8-4      disable down  enable  up
8-6      disable down  enable  up

```

EXAMPLES

EXAMPLE 1 When the system is being powered off, reserves the connection of the CD-RW/DVD-RW drive unit and the tape drive unit to the port 0-0.

```

XSCF> cfgdevice -c attach -p 0-0
Are you sure you want to attach the device [y|n] :y
Completed. ( Reservation )

```

EXAMPLE 2 When the system is being powered on, connects the CD-RW/DVD-RW drive unit and the tape drive unit to port 0-0.

```

XSCF> cfgdevice -c attach -p 0-0
Are you sure you want to attach the device [y|n] :y
Completed.

```

EXAMPLE 3 Disconnects the CD-RW/DVD-RW drive unit and the tape drive unit from the port 0-0.

```

XSCF> cfgdevice -f -c detach -p 0-0
Are you sure you want to detach the device [y|n] :y
Completed.

```

EXAMPLE 4 Displays the status of individual CD-RW/DVD-RW drive unit and the tape drive unit set on the M8000 server and the M9000 server without the expansion cabinet.

```

XSCF> cfgdevice -l
Current connection for DVD/DAT: port 0-0
Expander status
Port No. IOU/SAS-status SAS-status
-----
0-0      enable up      enable up
0-2      disable down   enable up

```

EXAMPLE 5 Displays the status of individual CD-RW/DVD-RW drive unit and the tape

drive unit set on the M9000 server with the expansion cabinet.

```
XSCF> cfgdevice -l
Current connection for DVD/DAT: port 0-0
  Main chassis:      port 0-0
  Expansion chassis: port 8-0
Expander status
Port No. IOU/SAS-status SAS-status
-----
0-0      enable up      enable up
0-2      disable down  enable up
0-4      disable down  enable up
0-6      disable down  enable up
1-0      disable down  enable up
1-2      disable down  enable up
1-4      disable down  enable up
1-6      disable down  enable up
2-0      disable down  enable up
2-2      disable down  enable up
2-4      disable down  enable up
2-6      disable down  enable up
8-0      enable up      enable up
8-2      disable down  enable up
8-4      disable down  enable up
8-6      disable down  enable up
```

EXAMPLE 6 Connects the CD-RW/DVD-RW drive unit and the tape drive unit to port 0-0 when the system is being powered on. Automatically answers "y" to all prompts.

```
XSCF> cfgdevice -y -c attach -p 0-0
Are you sure you want to attach the device [y|n] :y
Completed.
```

EXAMPLE 7 Connects the CD-RW/DVD-RW drive unit and the tape drive unit to port 0-0 when the system is being powered on. Automatically answers "y" to all

prompts without displaying messages.

```
XSCF> cfgdevice -q -y -c attach -p 0-0
```

EXIT STATUS

The following exit values are returned:

0 Successful completion.

>0 An error occurred.

NAME	clockboard - Set or display the clock control unit used at system startup
SYNOPSIS	<p>clockboard</p> <p>clockboard -s <i>CLKU_B-number</i></p> <p>clockboard -h</p>
DESCRIPTION	<p>The <code>clockboard(8)</code> command specifies the clock control unit used when the system power is turned on, or it displays the clock control unit that is currently used and the clock control unit used at the next system startup.</p> <p>The <code>clockboard(8)</code> command is available only for the M8000/M9000 servers.</p> <p>The number 0 or 1 is used to specify or display a clock control unit. When the <code>clockboard(8)</code> command is executed with no options, the clock control unit that is currently used and the one used at the next system startup are displayed.</p>
Privileges	<p>You must have <code>fieldeng</code> privilege to run this command.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p>-h Displays usage statement. When used with other options or operands, an error occurs.</p> <p>-s <i>CLKU_B-number</i> Specifies the clock control unit to be used the next time the system power is turned on. Either 0 or 1 can be specified for <i>CLKU_B-number</i>.</p>
EXAMPLES	<p>EXAMPLE 1 Displays the clock control unit that is currently used and the one used at the next system startup.</p> <pre>XSCF> clockboard current CLKU_B number :0 next CLKU_B number :1</pre> <p>EXAMPLE 2 Specifies the clock control unit used at the next system startup.</p> <pre>XSCF> clockboard -s 1</pre>
EXIT STATUS	<p>The following exit values are returned:</p> <p>0 Successful completion.</p> <p>>0 An error occurred.</p>

clockboard(8)



NAME	console - connect to a domain console
SYNOPSIS	console [[-q] -{y n}] -d <i>domain_id</i> [-f -r] [-s <i>escapeChar</i>] console -h
DESCRIPTION	<p>The console(8) command connects the XSCF shell console to the console of the specified domain (domain console).</p> <p>Domain consoles include a writable console and read-only console. Only one writable console and multiple read-only consoles can be connected to one domain. An attempt to set up a connection to another writable console while one writable console is already connected results in an error. Even in this case, however, a user with the platadm or domainadm privilege can forcibly establish a connection to a writable console, in which case the currently connected writable console is disconnected.</p> <p>To exit the domain console and return to the XSCF shell console, press the Enter key and then enter "#" and "." (period).</p> <p>Note – When you return to XSCF shell console without logging out from the domain, the return causes automatically logging out from the domain.</p>
Privileges	<p>You must have one of the following privileges to run this command:</p> <p>platadm, platop, fieldeng Can run this command for all domains.</p> <p>domainadm, domainmgr, domainop Can run this command only for your accessible domains.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported.</p> <p>-d <i>domain_id</i> Specifies only one ID of the domain to which to connect to a domain console. <i>domain_id</i> can be 0–23 depending on the system configuration.</p> <p>-f Forcibly connects to a writable console. The currently connected writable console is disconnected. Only users who belong to the platadm or domainadm privilege can specify this option.</p> <p>-h Displays usage statement. When used with other options or operands, an error occurs.</p> <p>-n Automatically answers "n" (no) to all prompts.</p> <p>-q Suppresses all messages to stdout, including prompts.</p>

- r** Sets up a connection to a read-only console.
- s *escapeChar*** Specifies an escape character. The default is "#". The character specified for *escapeChar* must be enclosed in "" (double quotation). The following symbols can be specified for *escapeChar*:
- "#", "@", "^", "&", "?", "*", "=", ".", "|"
- Specified escape character is available only in the session that executed the `console(8)` command.
- y** Automatically answers "y" (yes) to all prompts.

EXTENDED DESCRIPTION

- When the command is executed, a prompt to confirm execution of the command with the specified options is displayed. Enter "y" to execute the command or "n" to cancel the command.
- The domain console regards "#" used at the beginning of a line as an escape character. An escape character is specified to instruct the console to perform special processing. Examples of processing that can be specified in combination with "#" are as follows.

"#" and "?" Outputs a status message.

"#" and "." (period) Disconnects the console.

- To enter "#" at the beginning of a line, enter "#" twice.
- To display information on the currently connected domain console, use the `showconsolepath(8)` command.

EXIT STATUS

The following exit values are returned:

0 Successful completion.

>0 An error occurred.

SEE ALSO

`sendbreak(8)`, `showconsolepath(8)`

NAME	deleteboard - disconnect an eXtended System Board (XSB) from the domain configuration						
SYNOPSIS	<pre>deleteboard [[-q] -{y n}] [-f] [-v] [-c disconnect] xsb [xsb...] deleteboard [[-q] -{y n}] [-f] [-v] -c unassign xsb [xsb...] deleteboard [[-q] -{y n}] [-f] [-v] -c reserve xsb [xsb...] deleteboard -h</pre>						
DESCRIPTION	<p>The deleteboard(8) command disconnects an XSB from the domain configuration in which it has been configured.</p> <p>The deleteboard(8) command is not available on the M3000 server.</p> <p>One of the following disconnection methods can be specified:</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;">disconnect</td> <td>Disconnects the XSB from the domain configuration but keeps it assigned. Because the XSB thus remains assigned to the domain configuration, it can be configured again in the domain by reboot the domain or execution of the addboard(8) command.</td> </tr> <tr> <td>unassign</td> <td>Completely disconnects the XSB from the main configuration and puts it in the system board pool. The XSB in the system board pool can be incorporated into or assigned to other domain configurations.</td> </tr> <tr> <td>reserve</td> <td>Does not immediately disconnects the XSB from the domain configuration but only reserves detachment. When the domain power is shut down, the reserved XSB is disconnected from the domain configuration and put in the system board pool.</td> </tr> </table>	disconnect	Disconnects the XSB from the domain configuration but keeps it assigned. Because the XSB thus remains assigned to the domain configuration, it can be configured again in the domain by reboot the domain or execution of the addboard(8) command.	unassign	Completely disconnects the XSB from the main configuration and puts it in the system board pool. The XSB in the system board pool can be incorporated into or assigned to other domain configurations.	reserve	Does not immediately disconnects the XSB from the domain configuration but only reserves detachment. When the domain power is shut down, the reserved XSB is disconnected from the domain configuration and put in the system board pool.
disconnect	Disconnects the XSB from the domain configuration but keeps it assigned. Because the XSB thus remains assigned to the domain configuration, it can be configured again in the domain by reboot the domain or execution of the addboard(8) command.						
unassign	Completely disconnects the XSB from the main configuration and puts it in the system board pool. The XSB in the system board pool can be incorporated into or assigned to other domain configurations.						
reserve	Does not immediately disconnects the XSB from the domain configuration but only reserves detachment. When the domain power is shut down, the reserved XSB is disconnected from the domain configuration and put in the system board pool.						
Privileges	<p>You must have one of the following privileges to run this command:</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;">platadm</td> <td>Can run this command for all domains.</td> </tr> <tr> <td>domainadm</td> <td>Can run this command only for your managed domains.</td> </tr> </table> <p>Refer to setprivileges(8) for more information.</p>	platadm	Can run this command for all domains.	domainadm	Can run this command only for your managed domains.		
platadm	Can run this command for all domains.						
domainadm	Can run this command only for your managed domains.						

OPTIONS

The following options are supported.

- c *disconnect* Detaches the XSB from the domain configuration and keeps it assigned. If the -c option is omitted, "-c disconnect" is used.
- c *reset* Reserves disconnect of an XSB. If the -c option is omitted, "-c disconnect" is used.
- c *unassign* Disconnects the XSB completely from the domain configuration and puts it in the system board pool. If the -c option is omitted, "-c disconnect" is used.
- f Forcibly detaches the specified XSB.

Caution – If the -f option is used to forcibly add a system board to a domain, all the added hardware resources may not work normally. For this reason, use of the -f option is not recommended in normal operation. If the -f option must be specified, verify the status of every added system board and device.

- h Displays usage statement. When used with other options or operands, an error occurs.
- n Automatically answers "n" (no) to all prompts.
- q Suppresses all messages to stdout, including prompts.
- v Displays a detailed message. If this option is specified with the -q option, the -v option is ignored.
- y Automatically answers "y" (yes) to all prompts.

OPERANDS

The following operand is supported:

xsb Specifies the XSB number to be disconnected. Multiple *xsb* operands are permitted, separated by spaces. The following *xsb* form is accepted:

x-y

where:

x An integer from 00–15.

y An integer from 0–3.

EXTENDED DESCRIPTION

- When the command is executed, a prompt to confirm execution of the command with the specified options is displayed. Enter "y" to execute the command or "n" to cancel the command.
- If "-c disconnect" is specified when either the domain power has been turned off or the XSB is already disconnected from the domain configuration, no operation is performed. If domain power-on or power-off is in progress, the command results in an error.
- If "-c unassign" is specified when either the domain power has been turned off or the XSB is already disconnected from the domain configuration, the XSB is switched from the assigned state to a system board pool. If the XSB is already in a system board pool, no operation is performed.
- If "-c reserve" is specified when either the domain power has been turned off or the XSB is already disconnected from the domain configuration, the XSB is immediately switched from the assigned state to a system board pool. If the XSB is already in a system board pool, no operation is performed. If domain power-on or power-off is in progress, the command results in an error.
- When the XSB is disconnected, the hardware resource on the XSB is disconnected from the operating system. For this reason, command execution may take time.
- The state in which an XSB has been assigned means that configuring the XSB in the specified domain has been reserved. The reserved XSB is configured when the domain is rebooted or the `addboard(8)` command is executed. An already assigned XSB cannot be specified for configuring or assignment from other domains.
- An XSB in the system board pool means that the XSB belongs to no domain and is therefore available for configuring or assignment.

EXAMPLES

EXAMPLE 1 Puts the system board XSB#00-0, #01-0, #02-0, and #03-0 in the system board pool

```
XSCF> deleteboard -c unassign 00-0 01-0 02-0 03-0
```

EXAMPLE 2 Reserves disconnection of XSB#00-0, #01-0, #02-0, and #03-0 .

```
XSCF> deleteboard -c reserve 00-0 01-0 02-0 03-0
```

EXIT STATUS

The following exit values are returned:

- | | |
|----|------------------------|
| 0 | Successful completion. |
| >0 | An error occurred. |

SEE ALSO

`addboard(8)`, `moveboard(8)`, `replacefru(8)`, `setdcl(8)`, `setupfru(8)`, `showboards(8)`, `showdcl(8)`, `showdevices(8)`, `showdomainstatus(8)`, `showfru(8)`

deleteboard(8)



NAME	deletecodlicense - remove a Capacity on Demand (COD) right-to-use (RTU) license key from the COD license database
SYNOPSIS	deletecodlicense [-f] <i>license-signature</i> deletecodlicense -h
DESCRIPTION	<p>The <code>deletecodlicense(8)</code> command removes the specified COD RTU license key from the COD license database on the Service Processor.</p> <p>The <code>deletecodlicense(8)</code> command is not available on the M3000 server.</p> <p>For further information about COD RTU license keys, refer to the <i>Administration Guide</i>.</p> <p>The system checks the number of COD RTU licenses against the number of COD CPUs in use. If the license removal will result in an insufficient number of COD RTU licenses with respect to the CPU in use, the system does not delete the license key from the COD RTU license database. If you still want to delete the COD RTU license key, you must reduce the number of COD CPUs in use. Power off the appropriate number of domains or disconnect the appropriate number of the eXtended System Boards (XSBs).</p>
Privileges	<p>You must have <code>platadm</code> privileges to run this command.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p>-f Forces the specified COD RTU license key to be deleted from the COD license database.</p> <p>-h Displays usage statement.</p> <p> When used with other options or operands, an error occurs.</p>
OPERANDS	<p>The following operands are supported:</p> <p><i>license-signature</i> Specifies the COD RTU license key to be deleted from the COD license database.</p>
EXAMPLES	<p>EXAMPLE 1 Deleting a COD RTU license key</p> <pre>XSCF> deletecodlicense \ 01:84000000:104:0301010100:3:00000000:xxxxxxxxxxxxxxxxxxxxxxxx</pre>

deletecodlicense(8)

EXIT STATUS

The following exit values are returned:

- 0 Successful completion.
- >0 An error occurred.

SEE ALSO

addcodlicense (8), **setcod** (8), **showcod** (8), **showcodlicense** (8),
showcodusage (8)

NAME	deletefru - delete a Field Replaceable Unit (FRU)
SYNOPSIS	deletefru deletefru -h
DESCRIPTION	<p>The <code>deletefru(8)</code> command deletes an FRU.</p> <p>The <code>deletefru(8)</code> command is available only for the M8000/M9000 servers.</p> <p>The <code>deletefru(8)</code> command allows the user to make the settings that are required for FRU deletion and related to selecting, confirming, and removing FRUs interactively using menus.</p> <p>The following FRUs can be deleted:</p> <ul style="list-style-type: none"> ■ CPU/Memory Board unit (CMU) ■ I/O unit (IOU)
Privileges	<p>You must have <code>fieldeng</code> privileges to run this command.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>
OPTIONS	<p>The following option is supported:</p> <p><code>-h</code> Displays usage statement.</p>
EXIT STATUS	<p>The following exit values are returned:</p> <p>0 Successful completion.</p> <p>>0 An error occurred.</p>
SEE ALSO	addfru (8), deleteboard (8), replacefru (8), setupfru (8), showdomainstatus (8), showfru (8), showhardconf (8), unlockmaintenance (8)

deleterfru(8)



NAME	deleteuser - delete an XSCF user account
SYNOPSIS	deleteuser <i>user</i> deleteuser -h
DESCRIPTION	<p>deleteuser(8) deletes a local XSCF user account. All local account data associated with the user account is deleted including password and Secure Shell (SSH) keys.</p> <p>The local user's currently running XSCF shell and browser sessions are terminated at once. The user's account is removed from the system and they cannot log back in. You cannot delete your own account.</p>
Privileges	<p>You must have useradm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following option is supported:</p> <p>-h Displays usage statement.</p> <p> When used with other options or operands, an error occurs.</p>
OPERANDS	<p>The following operands are supported:</p> <p><i>user</i> Specifies a valid user name. The name of the user account to be deleted.</p>
EXAMPLES	<p>EXAMPLE 1 Deleting a User</p> <p>XSCF> deleteuser jsmith</p>
EXIT STATUS	<p>The following exit values are returned:</p> <p>0 Successful completion.</p> <p>>0 An error occurred.</p>
SEE ALSO	adduser (8), disableuser (8), enableuser (8)

deleteuser(8)



NAME	disableuser - disable an XSCF user account
SYNOPSIS	disableuser <i>user</i> disableuser -h
DESCRIPTION	<p>disableuser(8) disables a local XSCF user account for subsequent logins. Current sessions are not affected.</p> <p>When an account is disabled, it cannot be used for login. This applies to console (serial) and telnet connections, as well as the Secure Shell (SSH). XSCF Web login is also disabled. All local XSCF account data associated with the user remains on the system. This includes password and SSH keys. You can reenable a disabled account using enableuser(8).</p>
Privileges	<p>You must have useradm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following option is supported:</p> <p>-h Displays usage statement.</p> <p> When used with other options or operands, an error occurs.</p>
OPERANDS	<p>The following operands are supported:</p> <p><i>user</i> Specifies a valid user name of the user account to be disabled.</p>
EXAMPLES	<p>EXAMPLE 1 Disabling a User Account</p> <p style="padding-left: 20px;">XSCF> disableuser jsmith</p>
EXIT STATUS	<p>The following exit values are returned:</p> <p>0 Successful completion.</p> <p>>0 An error occurred.</p>
SEE ALSO	adduser (8), deleteuser (8), enableuser (8), showuser (8)

disableuser(8)



NAME	dumpconfig - save system configuration information
SYNOPSIS	<p>dumpconfig [-v] [-V] [[-q] -{Y n}] [-e [-P <i>password</i>]] [-c <i>comment</i>] [-u <i>user</i>] [-p <i>proxy</i> [-t <i>proxy_type</i>]] <i>url</i></p> <p>dumpconfig -h</p>
DESCRIPTION	The dumpconfig(8) command downloads the system configuration information into a file specified by the user.
Privileges	You must have platadm, platop, or fieldeng privileges to run this command. Refer to setprivileges(8) for more information.
OPTIONS	<p>The following options are supported:</p> <ul style="list-style-type: none"> -c <i>comment</i> Accepts a user-provided comment in the file to distinguish between different backup copies and is not read by the software. This comment must be 132 chars or less in length. -e Encrypt the file. "-P <i>password</i>" option can be used to specify the password. If a password is not specified the key will be prompted. Once encrypted the configuration file cannot be decrypted without the key. If the key is lost, there is no possibility of recovering the configuration data. -h Displays usage statement. When used with other options or operands, an error occurs. -n Automatically answers "n" (no) to all prompts. -P <i>password</i> With -e option, password can be provided on command line. The command will prompt for the password if a password is not provided on command line. -p <i>proxy</i> Specifies the proxy server to be used for transfers. The default transfer type is http, unless modified using the -t <i>proxy_type</i> option. The value for proxy must be in the format <i>servername:port</i>. -q Suppresses all messages to stdout, including prompts. -t <i>proxy_type</i> Used with the -p option to specify the type of proxy. Possible values for <i>proxy_type</i> are: http, socks4, and socks5. The default value is http. -u <i>user</i> Specifies the user name when logging in to a remote ftp or http server that requires authentication. You will be prompted for a password.

- v Displays verbose output. This may be helpful when diagnosing server problems.
- V Displays details of network activity. This may be helpful when diagnosing network or server problems.
- y Automatically answers "y" (yes) to all prompts.

OPERANDS

The following operands are supported:

- url* Specifies the URL where the configuration will be dumped. Supported formats for this value include the following:
- `http://server[:port]/path/file`
 - `https://server[:port]/path/file`
 - `ftp://server[:port]/path/file`
 - `file:///media/usb_msd/path/file`

EXAMPLES**EXAMPLE 1** Dumping the Configuration using FTP

```
XSCF> dumpconfig -V -p 129.145.155.156:8080 -u minilla ftp://
10.7.79.18/sollgell/proxytest-ftp.cfg

transfer from '/tmp/dumpconfig.EvY1Yf' to 'ftp://10.7.79.18/sollgell/
proxytest-ftp.cfg'

Password:

* About to connect() to 129.145.155.166 port 8080
*   Trying 129.145.155.166... * connected
* Connected to 129.145.155.166 (129.145.155.166) port 8080
* Proxy auth using (nil) with user ''
* Server auth using Basic with user 'minilla'
> PUT ftp://10.7.79.18/iktest/proxytest-ftp.cfg HTTP/1.1
Authorization: Basic bHdhbmc6bHdhbmc=
User-Agent: dumpconfig
Host: 10.7.79.18:21
Pragma: no-cache
Accept: */*
Content-Length: 24720
Expect: 100-continue
```

```

< HTTP/1.1 100 Continue
< HTTP/1.1 200 OK
< Server: Sun-Java-System-Web-Proxy-Server/4.0
< Date: Mon, 04 Aug 2008 16:46:11 GMT
< Transfer-encoding: chunked
* Connection #0 to host 129.145.155.166 left intact
* Closing connection #0
operation completed
XSCF>

```

EXAMPLE 2 Dumping the Configuration Using http

```

XSCF> dumpconfig -v -p 129.145.155.166:8080 http://10.7.79.18/
sollgell/proxytest.cfg
reading database ... .....*done
creating temporary file ... done
starting file transfer ...done
removing temporary file ... done
operation completed
XSCF>

```

EXAMPLE 3 Dumping the Configuration Using Https

```

XSCF> dumpconfig -v -p 129.145.155.166:8080 http://10.7.79.18/
sollgell/proxytest-https.cfg
transfer from '/tmp/dumpconfig.ZMCI3d' to 'http://10.7.79.18/iktest/
proxytest-https.cfg'
* About to connect() to 129.145.155.166 port 8080
* Trying 129.145.155.166... * connected
* Connected to 129.145.155.166 (129.145.155.166) port 8080
> > PUT http://10.7.79.18/iktest/proxytest-https.cfg HTTP/1.1
User-Agent: dumpconfig
Host: 10.7.79.18
Pragma: no-cache
Accept: */*
Content-Length: 24720

```

```

Expect: 100-continue
< HTTP/1.1 100 Continue
< HTTP/1.1 204 No Content
< Content-type: text/html
< Date: Mon, 04 Aug 2008 16:42:46 GMT
< Server: Apache/1.3.36 (Unix) mod_perl/1.29 mod_ssl/2.8.27 OpenSSL/0.9.7d
< Via: 1.1 proxy-proxy
< Proxy-agent: Sun-Java-System-Web-Proxy-Server/4.0
* Connection #0 to host 129.145.155.166 left intact
* Closing connection #0
operation completed
XSCF>

```

EXAMPLE 4 Dumping the Configuration Using USB

```

XSCF> dumpconfig -v -V file:///media/usb_msd/proxytest.cfg
Making sure mount point is clear
Trying to mount USB device /dev/sda1 as /media/usb_msd
Mounted USB device
file '/media/usb_msd/proxytest.cfg' already exists
Do you want to overwrite this file? [y|n]: y
removing file 'file:///media/usb_msd/proxytest.cfg' ... done
reading database ... .....*done
creating temporary file ... done
starting file transfer ...transfer from '/tmp/dumpconfig.HE1RZa' to
'file:///media/usb_msd/san-ff1-54.cfg'
done
removing temporary file ... done
operation completed
Unmounted USB device
XSCF>

```

EXAMPLE 5 Encrypting and Password Protecting the Configuration

```
XSCF> dumpconfig -v -e -P kamacuras -p 129.145.155.166:8080 http://  
/10.7.79.18/sollgell/proxytest.cfg  
reading database ... .....*done  
creating temporary file ... done  
starting file transfer ...done  
removing temporary file ... done  
operation completed  
XSCF>
```

EXIT STATUS The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO [restoreconfig\(8\)](#)

dumpconfig(8)



NAME	enableuser - enable an XSCF user account
SYNOPSIS	enableuser <i>user</i> enableuser -h
DESCRIPTION	enableuser(8) enables a local XSCF user account. An enabled account can be used for login at the console, using Secure Shell (SSH). Using this command, you can reenable accounts disabled by <code>disableuser</code> .
Privileges	You must have <code>useradm</code> privileges to run this command. Refer to <code>setprivileges(8)</code> for more information.
OPTIONS	The following option is supported. -h Displays usage statement. When used with other options or operands, an error occurs.
OPERANDS	The following operands are supported: <i>user</i> Specifies the valid user name of the account to be enabled.
EXAMPLES	EXAMPLE 1 Enable a User Account XSCF> enableuser jsmith
EXIT STATUS	The following exit values are returned: 0 Successful completion. >0 An error occurred.
SEE ALSO	adduser(8) , deleteuser(8) , disableuser(8) , showuser(8)

enableuser(8)



NAME	exit - exit the XSCF shell
SYNOPSIS	exit
DESCRIPTION	The <code>exit(1)</code> command exits and closes the XSCF shell.
Privileges	No privileges are required to run this command. Refer to <code>setprivileges(8)</code> for more information.

exit(1)



NAME	flashupdate - update the firmware
SYNOPSIS	<p>flashupdate -c check -m xcp -s <i>version</i></p> <p>flashupdate [[-q] -{y n}] -c update -m xcp -s <i>version</i></p> <p>flashupdate -c sync</p> <p>flashupdate -h</p>
DESCRIPTION	<p>The flashupdate(8) command updates the firmware.</p> <p>The entire firmware shown below is updated. Whether update can be performed can be checked beforehand.</p> <ul style="list-style-type: none"> ■ Update of the entire firmware (XSCF, OpenBoot PROM including Power-On Self-Test (POST)) (xcp)
Privileges	<p>You must have platadm or fieldeng privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:.</p> <p>-c check Checks whether the specified firmware can be updated.</p> <p>-c update Updates the specified firmware. In the M8000/M9000 servers, updates the firmware of both XSCF units.</p> <p>-c sync Synchronizes the firmware versions of the XSCF units in the M8000/M9000 servers. This option is used when replacing an XSCF unit.</p> <p>-h Displays usage statement. When used with other options or operands, an error occurs.</p> <p>-m xcp Specifies the entire firmware as a target.</p> <p>-n Automatically answers "n" (no) to all prompts.</p>

- q Suppresses all messages to stdout, including prompts.
- s *version* Specifies an XCP comprehensive firmware version. For *version*, specify a major version, minor version and micro version continuously.

The XCP version number appears as *xyyz* by four digits, where:
 - x* Major firmware release number
 - yy* Minor release number
 - z* Micro release number
- y Automatically answers "y" (yes) to all prompts.

EXTENDED DESCRIPTION

- When the command is executed, a prompt to confirm execution of the command with the specified options is displayed. Enter "y" to execute the command or "n" to cancel the command.
- When the firmware is updated, the XSCF unit is reset. Therefore, LAN connection to the XSCF is canceled if already established.
- When there's a faulty Field Replaceable Unit (FRU), can't update the firmware. Resolve the FRU fault then update.

EXAMPLES

EXAMPLE 1 Check whether the entire firmware can be updated to version 1020.

```
XSCF> flashupdate -c check -m xcp -s 1020
```

EXAMPLE 2 Updates the entire firmware to version from 1010 to 1020.

```
XSCF> flashupdate -c update -m xcp -s 1020
```

```
The XSCF will be reset. Continue? [y|n] :y
```

```
XCP update is started (XCP version=1020:last version=1010)
```

```
OpenBoot PROM update is started
```

```
OpenBoot PROM update has been completed (OpenBoot PROM version=01010001)
```

```
XSCF update is started (SCF=0, bank=1, XCP version=1020:last version=1010)
```

```
XSCF download is started (SCF=0, bank=1, XCP version=1020:last  
version=1010, Firmware Element ID=00:version=01010002:last  
version=01010001)
```

```
XSCF download has been completed (SCF=0, bank=1, XCP version=1020:last  
version=1010, Firmware Element ID=00:version=01010002:last  
version=01010001)
```

```

:
:
XSCF download is started (SCF=0, bank=1, XCP version=1020:last
version=1010, Firmware Element ID=07:version=01010002:last
version=01010001)
XSCF download has been completed (SCF=0, bank=1, XCP version=1020:last
version=1010, Firmware Element ID=07:version=01010002:last
version=01010001)
XSCF update has been completed (SCF=0, bank=1, XCP version=1020:last
version=1010)
XSCF update is started (SCF=0, bank=0, XCP version=1020:last version=1010)
XSCF download is started (SCF=0, bank=0, XCP version=1020:last
version=1010, Firmware Element ID=00:version=01010002:last
version=01010001)
XSCF download has been completed (SCF=0, bank=0, XCP version=1020:last
version=1010, Firmware Element ID=00:version=01010002:last
version=01010001)
:
:
XSCF download is started (SCF=0, bank=0, XCP version=1020:last
version=1010, Firmware Element ID=07:version=01010002:last
version=01010001)
XSCF download has been completed (SCF=0, bank=0, XCP version=1020:last
version=1010, Firmware Element ID=07:version=01010002:last
version=01010001)
XSCF is rebooting to update the reserve bank

```

EXAMPLE 3 Synchronizes the firmware version of the replaced XSCF units in the M8000/M9000 servers.

```
XSCF> flashupdate -c sync
```

flashupdate(8)

EXIT STATUS	The following exit values are returned:
0	Successful completion
>0	An error occurred.
SEE ALSO	version (8)

NAME	fmadm - fault management configuration tool
SYNOPSIS	fmadm [-q] config fmadm -h
DESCRIPTION	<p>fmadm (8) can be used to view system configuration parameters related to fault management.</p> <p>fmadm can be used to:</p> <ul style="list-style-type: none"> View the set of diagnosis engines and agents that are currently participating in fault management View the list of system components that have been diagnosed as faulty <p>The Fault Manager attempts to automate as many activities as possible, so use of fmadm is typically not required. When the Fault Manager needs help from a human administrator or service representative, it produces a message indicating its needs. It also refers you to a URL containing the relevant knowledge article. The web site might ask you to use fmadm or one of the other fault management utilities to gather more information or perform additional tasks. The documentation for fmdump(8) describes more about tools to observe fault management activities.</p>
Privileges	<p>You must have platop, platadm, or fieldeng privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported.</p> <ul style="list-style-type: none"> -h Displays usage statement. When used with other options or operands, an error occurs. -q Sets quiet mode. fmadm does not produce messages indicating the result of successful operations to standard output.
OPERANDS	<p>The following operands are supported:</p> <ul style="list-style-type: none"> config Displays the configuration of the Fault Manager itself, including the module name, version, and description of each component module. Fault Manager modules provide services such as automated diagnosis, self-healing, and messaging for hardware and software present on the system.

EXAMPLES

EXAMPLE 1 Displaying the Fault Manager Configuration

```
XSCF> fmadm config
MODULE             VERSION STATUS  DESCRIPTION
case-close         1.0    active  Case-Close Agent
fmd-self-diagnosis 1.0    active  Fault Manager Self-Diagnosis
sysevent-transport 1.0    active  SysEvent Transport Agent
syslog-msgs        1.0    active  Syslog Messaging Agent
```

EXIT STATUS

The following exit values are returned:

```
0             Successful completion.
>0           An error occurred.
```

SEE ALSO

fmdump(8), **fmstat**(8)

NAME	fmdump - view fault management logs				
SYNOPSIS	<p>fmdump</p> <p>fmdump [-e] [-f] [-M] [-v] [-V] [-c <i>class</i>] [-t <i>time</i>] [-T <i>time</i>] [-u <i>uuid</i>]</p> <p>fmdump -m [-M] [-t <i>time</i>] [-T <i>time</i>]</p> <p>fmdump -h</p>				
DESCRIPTION	<p>The <code>fmdump</code> utility displays the contents of any of the logs associated with the Fault Manager (fault manager daemon). The Fault Manager runs in the background on each server. It records, in the error log, faults detected by the XSCF, and initiates proactive self-healing activities, such as disabling faulty components.</p> <p>The Fault Manager maintains two sets of logs for use by system administrators and service personnel:</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;">Error log</td> <td>Records error telemetry, the symptoms of problems detected by the system</td> </tr> <tr> <td>Fault log</td> <td>Records fault diagnosis information; the problems believed to explain these symptoms. By default, <code>fmdump</code> displays the contents of the fault log, which records the result of each diagnosis made by the fault manager or one of its component modules.</td> </tr> </table> <p>Each problem recorded in the fault log is identified by:</p> <ul style="list-style-type: none"> ■ The time of its diagnosis ■ A Universal Unique Identifier (UUID) that can be used to uniquely identify this particular problem across any set of systems ■ A message identifier (MSG-ID) that can be used to access a corresponding knowledge article located at the specified website. <p>If a problem requires action by a system administrator or service personnel or affects system behavior, the Fault Manager also issues a human-readable message. This message provides a summary of the problem and a reference to the knowledge article on the specified website.</p> <p>You can use the <code>-v</code> and <code>-V</code> options to expand the display from a single-line summary to increased levels of detail for each event recorded in the log. You can also use the <code>-M</code> option to display only one screen at a time. The <code>-c</code>, <code>-t</code>, <code>-T</code>, and <code>-u</code> options can be used to filter the output by selecting only those events that match the specified <i>class</i>, range of times, or <i>uuid</i>. If more than one filter option is present on the command line, the options combine to display only those events that are selected by the logical AND of the options. If more than one instance of the same</p>	Error log	Records error telemetry, the symptoms of problems detected by the system	Fault log	Records fault diagnosis information; the problems believed to explain these symptoms. By default, <code>fmdump</code> displays the contents of the fault log, which records the result of each diagnosis made by the fault manager or one of its component modules.
Error log	Records error telemetry, the symptoms of problems detected by the system				
Fault log	Records fault diagnosis information; the problems believed to explain these symptoms. By default, <code>fmdump</code> displays the contents of the fault log, which records the result of each diagnosis made by the fault manager or one of its component modules.				

filter option is present on the command-line, the like options combine to display any events selected by the logical OR of the options.

You can use the `-m` option to display the Fault Manager `syslog` contents.

Privileges

You must have `platop`, `platadm`, or `fieldeng` privileges to run this command.

Refer to `setprivileges(8)` for more information.

OPTIONS

The following options are supported.

- `-c class` Selects events that match the specified class. The class argument can use the global pattern matching syntax, which is similar to global pattern matching for files. For example `xyz.*` would match `xyz.sxc` and `xyz.pdf`. The class represents a hierarchical classification string indicating the type of telemetry event.
- `-h` Displays usage statement.

When used with other options or operands, an error occurs.
- `-e` Displays events from the fault management error log instead of the fault log.

The error log contains private telemetry information used by XSCF's automated diagnosis software. This information is recorded to facilitate post-mortem analysis of problems and event replay, and should not be parsed or relied upon for the development of scripts and other tools.
- `-f` Displays only lines that have been appended to the dump file since the command was executed. Output continues until interrupted by `Ctrl-C`.
- `-m` Displays the Fault Manager `syslog` message contents.
- `-M` Displays text by page. This option provides a function that is the same as that of the `more` command.
- `-t time` Selects events that occurred at or after the specified time. The time can be specified using the forms in the Time Formats following this section. Used with `-T` you can specify a range.
- `-T time` Selects events that occurred at or before the specified time. *time* can be specified using any of the time formats described for the `-t` option. Used with `-t` you can specify a range.

- `-u uuid` Selects fault diagnosis events that exactly match the specified *uuid*. Each diagnosis is associated with a UUID for identification purposes. The `-u` option can be combined with other options such as `-v` to show all of the details associated with a particular diagnosis.
- If the `-e` option and `-u` option are specified at the same time, `fmdump` displays the relevant error events.
- `-v` Displays verbose event detail. The event display is enlarged to show additional common members of the selected events.
- `-V` Displays very verbose event detail. The event display is enlarged to show every member of the name-value pair list associated with each event. In addition, for fault logs, the event display includes a list of cross-references to the corresponding errors that were associated with the diagnosis.

The following are the Time Formats:

Time Format	Description
<i>mm/dd/yy hh:mm:ss</i>	Month, day, year, hour in 24-hour format, minute, and second. Any amount of whitespace can separate the date and time. The argument should be quoted so that the shell interprets the two strings as a single argument.
<i>mm/dd/yy hh:mm</i>	Month, day, year, hour in 24-hour format, and minute. Any amount of whitespace can separate the date and time. The argument should be quoted so that the shell interprets the two strings as a single argument.
<i>mm/dd/yy</i>	12:00:00AM on the specified month, day, and year
<i>ddMonyy hh:mm:ss</i>	Day, month name, year, hour in 24-hour format, minute, and second. Any amount of whitespace can separate the date and time. The argument should be quoted so that the shell interprets the two strings as a single argument.
<i>Mon dd hh:mm:ss</i>	Month, day, hour in 24-hour format, minute, and second of the current year. Any amount of whitespace can separate the date and time. The argument should be quoted so that the shell interprets the two strings as a single argument.

Time Format	Description
<i>yyyy-mm-dd</i> [<i>T hh:mm[:ss]</i>]	Year, month, day, and optional hour in 24-hour format, minute, and second, where T is an integer value specified in base 10. The second, or hour, minute, and second, can be optionally omitted.
<i>ddMonyy</i>	12:00:00AM on the specified day, month name, and year.
<i>hh:mm:ss</i>	Hour in 24-hour format, minute, and second of the current day.
<i>hh:mm</i>	Hour in 24-hour format and minute of the current day.
<i>Tns</i> <i>Tnsec</i>	T nanoseconds ago where T is an integer value specified in base 10.
<i>Tus</i> <i>Tusec</i>	T microseconds ago where T is an integer value specified in base 10
<i>Tms</i> <i>Tmsec</i>	T milliseconds ago where T is an integer value specified in base 10.
<i>Ts</i> <i>Tsec</i>	T seconds ago where T is an integer value specified in base 10.
<i>Tm</i> <i>Tmin</i>	T minutes ago where T is an integer value specified in base 10.
<i>Th</i> <i>Thour</i>	T hours ago where T is an integer value specified in base 10.
<i>Td</i> <i>Tday</i>	T days ago where T is an integer value specified in base 10.

You can append a decimal fraction of the form *.n* to any *-t* option argument to indicate a fractional number of seconds beyond the specified time.

EXAMPLES

EXAMPLE 1 Default fmdump Display

```
XSCF> fmdump
TIME                UUID                MSG-ID
Aug 12 16:12:13.2811 7868c1cc-23d4-c575-8659-85cdb61842e FMD-8000-77
Aug 12 16:12:13.2985 7868c1cc-23d4-c575-8659-85cdb61842e FMD-8000-77
Sep 01 16:06:57.5839 3ceca439-b0b2-4db1-9123-c8ace3f2b371 FMD-8000-77
Sep 01 16:06:57.6278 3ceca439-b0b2-4db1-9123-c8ace3f2b371 FMD-8000-77
Sep 06 09:37:05.0983 6485b42b-6638-4c5d-b652-bec485290788 LINUX-8000-1N
```

```

Sep 06 09:38:10.8584 77435994-5b99-4db8-bdcd-985c7d3ae3e4 LINUX-8000-1N
Sep 06 09:57:44.6502 0087d58c-e5b9-415d-91bc-adf7c41dd316 LINUX-8000-1N
Sep 06 12:40:59.2801 97de2cef-8ea1-407a-8a53-c7a67e61987a LINUX-8000-1N
Sep 06 12:41:10.1076 fa7304f9-c9e8-4cd1-9ca5-e35f57d53b2c LINUX-8000-1N
Sep 06 13:01:49.1462 ce550611-4308-4336-8a9a-19676f828515 LINUX-8000-1N
Sep 06 15:42:56.6132 0f4b429f-c048-47cd-9d9f-a2f7b6d4c957 LINUX-8000-1N
Sep 06 16:07:14.4652 7d5fb282-e01b-476a-b7e1-1a0f8de80758 LINUX-8000-1N
Sep 06 16:08:16.3755 41379237-9750-4fd6-bce3-b5131d864d34 LINUX-8000-1N
Sep 29 14:49:27.8452 0455ceaa-e226-424a-9b34-27603ca603f1 FMD-8000-58
Sep 29 15:02:00.3039 fb550ebc-80e9-41c8-8afc-ac680b9eb613 FMD-8000-58
Sep 29 15:09:25.4335 8cec9a83-e2a3-4dc3-a7cd-de01caef5c63 FMD-8000-4M
Sep 29 15:10:09.6151 5f88d7d5-a107-4435-99c9-7c59479d22ed FMD-8000-58

```

EXAMPLE 2 Display in Verbose Mode

```

XSCF> fmdump -v
TIME                UUID                                MSG-ID
Nov 30 20:44:55.1283 9f773e33-e46f-466c-be86-fd3fcc449935 FMD-8000-0W
    100% defect.sunos.fmd.nosub
:

```

EXAMPLE 3 Display Very Verbose Event Detail for the Last UUID

```

XSCF> fmdump -e -v -u 5f88d7d5-a107-4435-99c9-7c59479d22ed
TIME                CLASS
Sep 29 2005 15:10:09.565220864 ereport.io.iox.cp.seeprom0.nresp
nvlst version: 0
    detector = (embedded nvlst)
    nvlst version: 0
        scheme = hc
        version = 0
        hc-root = /
        hc-list_sz = 0x1
        hc-list = (array of embedded nvlsts)
        (start hc-list[0])

```

```

        nvlist version: 0
            scheme = hc
            hc-name = iox
            hc-id = 0
        (end hc-list[0])
    (end detector)
    IOXserial_no = 123456
    class = ereport.io.iox.cp.seeprom0.nresp
    ena = 0x921b650000000001

```

EXAMPLE 4 Displaying the Full Fault Report for the Specified UUID

```

XSCF> fmdump -v -u 5f88d7d5-a107-4435-99c9-7c59479d22ed

```

TIME	UUID	MSG-ID
Sep 29 15:10:09.6151	5f88d7d5-a107-4435-99c9-7c59479d22ed	FMD-8000-58

```

    TIME                CLASS                ENA
    Sep 29 15:10:09.5652 ereport.io.iox.cp.seeprom0.nresp
    0x921b650000000001
    nvlist version: 0
        version = 0x0
        class = list.suspect
        uuid = 5f88d7d5-a107-4435-99c9-7c59479d22ed
        code = FMD-8000-58
        diag-time = 1128021009 615016
        de = (embedded nvlist)
    nvlist version: 0
        version = 0x0
        scheme = fmd
        authority = (embedded nvlist)
    nvlist version: 0
        version = 0x0
        product-id = SUNW,SPARC-Enterprise
        chassis-id = BF0000001V
        server-id = localhost
    (end authority)

```

```

        mod-name = sde
        mod-version = 1.13
    (end de)
    fault-list-sz = 0x1
    fault-list = (array of embedded nvlists)
    (start fault-list[0])
    nvlist version: 0
        version = 0x0
        class = fault.io.iox.cp.seeeprom
        certainty = 0x64
        fru = (embedded nvlist)
        nvlist version: 0
            scheme = hc
            version = 0x0
            hc-root =
            hc-list-sz = 0x1
            hc-list = (array of embedded nvlists)
            (start hc-list[0])
            nvlist version: 0
                hc-name = iox
                hc-id = 0
            (end hc-list[0])
        (end fru)
    (end fault-list[0])

```

EXAMPLE 5 Displaying Contents of the Fault Manager syslog Message

```

XSCF> fmdump -m -M
MSG-ID: FMD-8000-11, TYPE: Defect, VER: 1, SEVERITY: Minor
EVENT-TIME: Tue Nov 7 07:01:44 PST 2006
PLATFORM: SUNW,SPARC-Enterprise, CSN: 7860000764, HOSTNAME: san-ff2-20-0
SOURCE: sde, REV: 1.5
EVENT-ID: 2daddee0-2f42-47ee-b5b2-57ae6a41bfc0

```

fmdump(8)

DESC: A Solaris Fault Manager component generated a diagnosis for which no message summary exists. Refer to <http://www.sun.com/msg/FMD-8000-11> for more information.

AUTO-RESPONSE: The diagnosis has been saved in the fault log for examination by Sun.

IMPACT: The fault log will need to be manually examined using `fmdump(1M)` in order to determine if any human response is required.

MSG-ID: FMD-8000-11, TYPE: Defect, VER: 1, SEVERITY: Minor

EVENT-TIME: Tue Nov 7 07:03:25 PST 2006

PLATFORM: SUNW,SPARC-Enterprise, CSN: 7860000764, HOSTNAME: san-ff2-20-0

SOURCE: sde, REV: 1.5

EVENT-ID: 2b03ab60-96db-439d-a13a-2f420a1b73c7

DESC: A Solaris Fault Manager component generated a diagnosis for which no message summary exists. Refer to <http://www.sun.com/msg/FMD-8000-11> for more information.

AUTO-RESPONSE: The diagnosis has been saved in the fault log for examination by Sun.

IMPACT: The fault log will need to be manually examined using `fmdump(1M)` in order to determine if any human response is required.

EXIT STATUS

The following exit values are returned:

- | | |
|----|--|
| 0 | Successful completion. All records in the log file were examined successfully. |
| >0 | An error occurred. |

SEE ALSO

`fmadm(8)`, `fmstat(8)`

NAME fmstat - report fault management module statistics

SYNOPSIS **fmstat** [-a] [[-s] [-z] [-m *module*]] [*interval* [*count*]]

fmstat -h

DESCRIPTION The `fmstat` utility can be used by system administrators and service personnel to report statistics associated with the Fault Manager (fault manager daemon), and its associated set of modules. The Fault Manager runs in the background on each system. It receives telemetry information relating to problems detected by the system software, diagnoses these problems, and initiates proactive self-healing activities such as disabling faulty components.

You can use `fmstat` to view statistics for diagnosis engines and agents that are currently participating in fault management. The `fmadm(8)`, and `fmdump(8)` man pages describe more about tools to observe fault management activities.

If the `-m` option is present, `fmstat` reports any statistics kept by the specified fault management module. The module list can be obtained using `fmadm config`.

If the `-m` option is not present, `fmstat` reports the following statistics for each of its client modules:

<code>module</code>	The name of the fault management module as reported by <code>fmadm config</code> .
<code>ev_recv</code>	The number of telemetry events received by the module.
<code>ev_acpt</code>	The number of events accepted by the module as relevant to a diagnosis.
<code>wait</code>	The average number of telemetry events waiting to be examined by the module.
<code>svc_t</code>	The average service time for telemetry events received by the module, in milliseconds.
<code>%w</code>	The percentage of time that there were telemetry events waiting to be examined by the module.
<code>%b</code>	The percentage of time that the module was busy processing telemetry events.
<code>open</code>	The number of active cases (open problem investigations) owned by the module.

<code>solve</code>	The total number of cases solved by this module since it was loaded.
<code>memsz</code>	The amount of dynamic memory currently allocated by this module.
<code>bufsz</code>	The amount of persistent buffer space currently allocated by this module.

Privileges

You must have `platadm`, `platop`, or `fieldeng` privileges to run this command.

Refer to `setprivileges(8)` for more information.

OPTIONS

The following options are supported.

- `-a` Prints the default global statistics for the Fault Manager or a module. If used without the `-m module` option, the default global Fault Manager statistics are displayed. If used with the `-m module` option, the global statistics for a module are displayed.
- `-h` Displays usage statement.

When used with other options or operands, an error occurs.
- `-m module` Prints a report on the statistics associated with the specified fault management module, instead of the default statistics report.

Modules can publish an arbitrary set of statistics to help service the fault management software itself.

If used without the `-a` option, displays only those statistics kept by the module. If used with the `-a` option, displays statistics kept by the module and the global statistics associated with the module.
- `-s` Prints a report on Soft Error Rate Discrimination (SERD) engines associated with the module instead of the default module statistics report. A SERD engine is a construct used by fault management software to determine if a statistical threshold measured as N events in some time T has been exceeded. The `-s` option can only be used in combination with the `-m` option.
- `-z` Omits statistics with a zero value from the report associated with the specified fault management module. The `-z` option can only be used in combination with the `-m` option.

OPERANDS

The following operands are supported:

- `count` Print only *count* reports, and then exit.
- `interval` Print a new report every *interval* seconds.

If neither *count* nor *interval* is specified, a single report is printed and `fmstat` exits.

If an *interval* is specified but no *count* is specified, `fmstat` prints reports every *interval* seconds indefinitely until the command is interrupted by Ctrl-C.

EXAMPLES

EXAMPLE 1 Displaying FM Statistics for the Syslog Module

```
XSCF> fmstat -a -m syslog-msgs
NAME VALUE          DESCRIPTION
bad_code 0              event code has no dictionary name
bad_fmri 0              event fmri is missing or invalid
bad_time 0              event time is not properly encoded
bad_vers 0              event version is missing or invalid
fmd.accepted 0          total events accepted by module
fmd.buflimit 10M       limit on total buffer space
fmd.buftotal 0          total buffer space used by module
fmd.caseclosed 0        total cases closed by module
fmd.caseopen 0         cases currently open by module
fmd.casesolved 0       total cases solved by module
fmd.ckptcnt 0          number of checkpoints taken
fmd.ckptrestore true  restore checkpoints for module
fmd.ckptsave true     save checkpoints for module
fmd.ckpttime 0d        total checkpoint time
fmd.ckptzero false    zeroed checkpoint at startup
fmd.debugdrop 4        dropped debug messages
fmd.dequeued 1         total events dequeued by module
fmd.dispatched 1       total events dispatched to module
fmd.dlastupdate 1144424838299131us hrtime of last event dequeue completion
fmd.dropped 0          total events dropped on queue overflow
fmd.dtime 0d          total processing time after dequeue
fmd.loadtime 1144424251692484us hrtime at which module was loaded
fmd.memlimit 10M       limit on total memory allocated
fmd.memtotal 97b       total memory allocated by module
fmd.prdequeued 0       protocol events dequeued by module
fmd.snaptime 1144424838299148us hrtime of last statistics snapshot
fmd.thrlimit 8         limit on number of auxiliary threads
```

fmstat(8)

```
fmd.thrtotal 0      total number of auxiliary threads
fmd.wcnt 0          count of events waiting on queue
fmd.wlastupdate 1144424838299131us hrtime of last wait queue update
fmd.wlentime 30us   total wait length * time product
fmd.wtime 30us      total wait time on queue
fmd.xprtlimit 256   limit on number of open transports
fmd.xprtopen 0      total number of open transports
fmd.xprtqlimit 256 limit on transport event queue length
log_err 0           failed to log message to log(7D)
msg_err 0           failed to log message to sysmsg(7D)
no_msg 0            message logging suppressed
```

XSCF> **fmstat**

module	ev_recv	ev_acpt	wait	svc_t	%w	%b	open	solve	memsz	bufsz
case-close	0	0	0.0	0.0	0	0	0	0	0	0
fmd-self-diagnosis	1	1	0.0	0.2	0	0	1	0	27b	0
sysevent-transport	0	0	0.0	573.2	0	0	0	0	0	0
syslog-msgs	0	0	0.0	0.0	0	0	0	0	97b	0

EXAMPLE 2 Displaying FM Statistics for fmd Self-Diagnosis Module

XSCF> **fmstat -z -m fmd-self-diagnosis**

NAME	VALUE	DESCRIPTION
module	1	error events received from fmd modules

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

fmadm(8), **fmdump(8)**

NAME	getflashimage - download a firmware image file
SYNOPSIS	<pre>getflashimage [-v] [[-q] [-y n]] [-u user] [-p proxy [-t proxy_type]] url getflashimage -l getflashimage [[-q] [-y n]] [-d] getflashimage -h</pre>
DESCRIPTION	<p>The <code>getflashimage(8)</code> command downloads a firmware image file for use by the <code>flashupdate(8)</code> command.</p> <p>If any previous image files of the firmware are present on the XSCF unit, they are deleted prior to downloading the new version. After successful download, the image file is checked for integrity, and the MD5 checksum is displayed.</p>
Privileges	<p>You must have <code>platadm</code> or <code>fieldeng</code> privileges to run this command.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>
OPTIONS	<p>The following options are supported:</p> <ul style="list-style-type: none"> -d Deletes all previous firmware image files still on the XSCF unit, then exits. -h Displays usage statement. When used with other options or operands, an error occurs. -l Lists firmware image files that are still on the XSCF unit, then exits. -n Automatically answers "n" (no) to all prompts. -p <i>proxy</i> Specifies the proxy server to be used for transfers. The default transfer type is <code>http</code>, unless modified using the <code>-t proxy_type</code> option. The value for proxy must be in the format <code>servername:port</code>. (Refer to Example 3.) -q Suppresses all messages to stdout, including prompts. -t <i>proxy_type</i> Used with the <code>-p</code> option to specify the type of proxy. Possible values for <i>proxy_type</i> are: <code>http</code>, <code>socks4</code>, and <code>socks5</code>. The default value is <code>http</code>. -u <i>user</i> Specifies the user name when logging in to a remote ftp or http server that requires authentication. You will be prompted for a password. -v Displays verbose output. This may be helpful when diagnosing network or server problems. -y Automatically answers "y" (yes) to all prompts.

OPERANDS

The following operands are supported:

url Specifies the URL of the firmware image to download. Supported formats for this value include the following:

`http://server[:port]/path/file`

`https://server[:port]/path/file`

`ftp://server[:port]/path/file`

`file:///media/usb_msd/path/file`

where the value for *file* is in one of the following formats:

`XCPvvvv.tar.gz`

`IKXCPvvvv.tar.gz`

`FFXCPvvvv.tar.gz`

`DCXCPvvvv.tar.gz`

and *vvvv* is the four-character version number.

EXAMPLES

EXAMPLE 1 Downloading a Version from an http Server

```
XSCF> getflashimage http://imageserver/images/FFXCP1041.tar.gz
```

```
Existing versions:
```

Version	Size	Date
FFXCP1040.tar.gz	46827123	Wed Mar 14 19:11:40 2007

```
Warning: About to delete existing versions.
```

```
Continue? [y|n]: y
```

```
Removing FFXCP1040.tar.gz.
```

```
0MB received
```

```
1MB received
```

```
2MB received
```

```
...
```

```
43MB received
```

```
44MB received
```

```
45MB received
```

```
Download successful: 46827KB at 1016.857KB/s
Checking file...
MD5: e619e6dd367c888507427e58cdb8e0a0
```

EXAMPLE 2 Downloading a Version from an ftp Server

```
XSCF> getflashimage ftp://imageserver/images/FFXCP1041.tar.gz
Existing versions:
      Version              Size  Date
      FFXCP1040.tar.gz    46827123  Wed Mar 14 19:11:40 2007
Warning: About to delete existing versions.
Continue? [y|n]: y
Removing FFXCP1040.tar.gz.
  0MB received
  1MB received
  2MB received
...
 43MB received
 44MB received
 45MB received
Download successful: 46827KB at 1016.857KB/s
Checking file...
MD5: e619e6dd367c888507427e58cdb8e0a1
```

EXAMPLE 3 Downloading Using an http Proxy Server With Port 8080

```
XSCF> getflashimage -p webproxy.sun.com:8080 \
http://imageserver/images/FFXCP1041.tar.gz
Existing versions:
      Version              Size  Date
      FFXCP1040.tar.gz    46827123  Wed Mar 14 19:11:40 2007
Warning: About to delete existing versions.
Continue? [y|n]: y
Removing FFXCP1040.tar.gz.
  0MB received
```

```
1MB received
2MB received
...
43MB received
44MB received
45MB received
Download successful: 46827KB at 1016.857KB/s
Checking file...
MD5: e619e6dd367c888507427e58cdb8e0a2
```

EXAMPLE 4 Downloading Using a User Name and Password

```
XSCF> getflashimage -u jsmith \
http://imageserver/images/FFXCP1041.tar.gz
Existing versions:
      Version              Size  Date
      FFXCP1040.tar.gz    46827123  Wed Mar 14 19:11:40 2007
Warning: About to delete existing versions.
Continue? [y|n]: y
Removing FFXCP1040.tar.gz.
Password: [not echoed]
0MB received
1MB received
2MB received
...
43MB received
44MB received
45MB received
Download successful: 46827KB at 1016.857KB/s
Checking file...
MD5: e619e6dd367c888507427e58cdb8e0a3
```


EXAMPLE 5 Downloading From a USB Memory Stick

```
XSCF> getflashimage file:///media/usb_msd/images/FFXCP1041.tar.gz
```

```
Existing versions:
```

Version	Size	Date
FFXCP1040.tar.gz	46827123	Wed Mar 14 19:11:40 2007

```
Warning: About to delete existing versions.
```

```
Continue? [y|n]: y
```

```
Removing FFXCP1040.tar.gz.
```

```
Mounted USB device
```

```
0MB received
```

```
1MB received
```

```
...
```

```
44MB received
```

```
45MB received
```

```
Download successful: 46827 Kbytes in 109 secs (430.094 Kbytes/sec)
```

```
Checking file...
```

```
MD5: e619e6dd367c888507427e58cdb8e0a4
```

EXIT STATUS

The following exit values are returned:

0 Successful completion.

>0 An error occurred.

SEE ALSO

flashupdate (8)

getflashimage(8)



NAME	ioxadm - manage External I/O Expansion Units								
SYNOPSIS	<pre> ioxadm [-f] [-p] [-v] [-M] env [-e] [-l] [-t] [<i>target</i> [<i>sensors</i>]] ioxadm [-f] [-p] [-v] [-M] list [<i>target</i>] ioxadm [-f] [-p] [-v] [-M] locator [on off] [<i>target</i>] ioxadm [-f] [-p] [-v] [-M] poweroff <i>target</i> ioxadm [-f] [-p] [-v] [-M] poweron <i>target</i> ioxadm [-f] [-p] [-v] [-M] reset <i>target</i> ioxadm [-f] [-p] [-v] [-M] settled [on off slow fast] <i>target led_type</i> ioxadm -h </pre>								
DESCRIPTION	<p>ioxadm(8) manages External I/O Expansion Units and link cards attached to the system.</p> <p>The ioxadm(8) command is not available on the M3000 server.</p> <p>For this utility, an operand with parameters and a target device must both be specified. The target device can be a downlink card mounted in a built-in PCI slot in the host system; an External I/O Expansion Unit; or a field replaceable unit (FRU) in an External I/O Expansion Unit. The downlink card is identified by a string which identifies the host path to the card. An uplink card is an FRU in the I/O boat.</p>								
Privileges	<p>You must have one of the following privileges to run these commands:</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; padding: 5px;">Required Privileges</th> <th style="text-align: left; padding: 5px;">Operands</th> </tr> </thead> <tbody> <tr> <td style="padding: 5px;">platop</td> <td style="padding: 5px;">env, list</td> </tr> <tr> <td style="padding: 5px;">platadm</td> <td style="padding: 5px;">env, list, locator, poweroff, poweron</td> </tr> <tr> <td style="padding: 5px;">fieldeng</td> <td style="padding: 5px;">All operands</td> </tr> </tbody> </table> <p>Refer to setprivileges(8) for more information.</p>	Required Privileges	Operands	platop	env, list	platadm	env, list, locator, poweroff, poweron	fieldeng	All operands
Required Privileges	Operands								
platop	env, list								
platadm	env, list, locator, poweroff, poweron								
fieldeng	All operands								

OPTIONS

The following options are supported.

- f Forces command execution by ignoring warnings.
- h Displays usage statement.
- When used with other options or operands, an error occurs.
- M Displays text by page. This option provides a function that is the same as that of the `more` command.
- p Parsable output. Suppresses headers in display output. Fields are separated by single tabs.
- v Specifies verbose output. Refer to specific operands for details.

OPERANDS

The following operands are supported:

`env [-e|l|t] [target [sensors]]`

Displays a summary of an External I/O Expansion Unit or link card's environmental state.

- -e

Displays electrical states: measured voltage, current, fan speed, switch settings.

- -l

Displays LED states.

- -t

Displays thermal readings.

If no *target* is specified, `env` displays a list of all sensors for all External I/O Expansion Units.

If *target* specifies a *box_id*, `env` displays a list of sensor readings for all frus in the specified External I/O Expansion Unit and the attached downlink cards.

If *target* is in the form of *box_id* followed by *fru*, then only environmentals from that FRU will be printed. If an optional value for *sensors* is specified, then only those types of sensors are displayed. These options may be used concurrently.

If *target* is in the form of a *host path*, only the downlink card information is displayed. See EXAMPLE 2.

The results are listed in tabular format. Each FRU sensor is listed in the first column. In the next column is the sensor name, such as `T_AMBIENT` for ambient temperature, or `V_12V_0V` for the voltage reading of the 12V rail. The third, fourth, and fifth columns display the sensor reading (Value), sensor resolution (Res), and Units, respectively. See EXAMPLE 1.

Each FRU can have a variety of different sensors. When specifying multiple values for *sensors*, use spaces to separate the values. Possible values for *sensors* can be seen in the *Sensor* column of EXAMPLE 1. Units are given in Celsius degrees, Volts, Amperes, SWITCH and RPM.

The *sensors* names are FRU-dependent and may change from FRU type to FRU type and even among individual FRUs.

If the `-v` option is set, verbose output is displayed. In addition to the regular output, the output also includes: the maximum and minimum values supported by the sensors (*Max* and *Min*), along with the low and high warning thresholds (*Min Alarm* and *Max Alarm*).

LED indicators do not support these fields.

Fields containing a "-" indicate an unsupported setting. For example, there may be no minimum temperature alarm threshold.

led_type

Used with the `setled` operand, specifies a software-controlled FRU LED. The following table indicates which LED states can be controlled using the `setled` operand with the `off`, `on`, `fast`, and `slow` LED state settings. Y (yes) indicates that the LED can be controlled, N (no) indicates that it cannot be controlled.

LED	Name	off	on	fast	slow
ACTIVE	Power/OK	Y	Y	Y	Y
LOCATE	Locate	Y	N	Y	N
SERVICE	Fault/Locate	Y	Y	Y	Y
RDY2RM	Ready to remove	Y	Y	Y	Y
OVERTEMP	Overtemp	*	*	*	*
DCOK	DC Power	N	N	N	N
POWER	AC Power	N	N	N	N
DATA	Data	N	N	N	N
MGMT	Management	N	N	N	N

* The `OVERTEMP` LED and chassis `ACTIVE` LED may be set to each state. However, the hardware frequently updates the LED state so changes to the LED state may not be visible.

Note – Other LEDs are not under software control. A list of LEDs present in the system can be displayed by using the `"env -1"` operand.

`list` [*target*]

Lists the External I/O Expansion Units under system management.

If no *target* is specified, `list` displays a list of External I/O Expansion Units, one per line. Each line contains the unique identifier for that box and the host-specific name(s) for its downlink card(s). See EXAMPLE 3.

If an External I/O Expansion Unit argument or downlink card path is specified, the command displays a single line with the indicated FRU. If a *host path* is specified, only the downlink card information is displayed. See EXAMPLE 4 and EXAMPLE 6.

If the verbose option is set [-v], the output includes detailed FRU information. See EXAMPLE 5.

`locator` [on |off] [*target*]

Sets or queries the state of the locator indicator (LED).

Without options, `locator` reports the current state of the LED on the specified FRU.

If no *target* is specified, `locator` returns the current state of all locator LEDs.

A *target* argument is required when using the option fields:

`on`

Turns the LED on.

`off`

Turns the LED off.

The chassis locator is a white LED. If an FRU is specified, the FRU yellow service LED is used along with the chassis (locator) LED.

Only one FRU can have a location indicator enabled at a time in an External I/O Expansion Unit chassis. Turning off the chassis (locator) LED will also turn off the blinking (service) FRU LED.

`poweroff` *target*

Powers down the given FRU and lights appropriate LEDs to indicate the FRU is ready to remove. Must be used with the `-f` option. Be aware that using `-f` can crash the domain.

Do not remove both power supply units (PSUs) in the same External I/O Expansion Unit. If both PSUs are powered down in this way, then the External I/O Expansion Unit cannot be turned back on from the command line. It must be powered on physically.

Note – When a power supply is powered off, the LEDs and fan may still run since they receive power from both supplies.

poweron target

Restores full power to an I/O boat or reenables output from the power supply (PS) that has previously been marked ready-to-remove. When a PSU is newly installed and the power switch is in the on position, or a boat is connected to a powered link card, they automatically power themselves on. However, this command can be used to power a PSU or I/O boat back on that previously had been powered down for removal as long as the power switch is in the on position.

reset target

Reinitializes FRU components used to monitor External I/O Expansion Unit environmental. If a boat or link card is specified, the bridge controllers in the link cards are reset and re-initialized. If a box is specified, the fan controller and demux in the box are reset and re-initialized along with all bridge controllers associated with the External I/O Expansion Unit.

setled [on|off|slow|fast] target led_type

Sets LED state:

<i>off</i>	Off.
<i>on</i>	On.
<i>fast</i>	Fast blink.
<i>slow</i>	Slow blink.

Refer to the entry for *led_type* in this section for detailed information about LED types.

target

Specifies the target device which can be a downlink card in a host slot, an External I/O Expansion Unit, or an FRU in an External I/O Expansion Unit.

The downlink card is identified by the *hostpath* to the card.

hostpath is platform dependent and indicates the path to the slot on the host system which contains the downlink card. On SPARC Enterprise M4000/M5000/M8000/M9000 servers, the *hostpath* has the following format:

```
IOU#0-PCI#0 IO Board 0, PCI-E slot0
```

The External I/O Expansion Unit (*box_id*) is identified by serial number.

Use `iox@nnnn`, where *nnnn* represents the last four digits of the box serial number.

Some commands affect only a single component of an External I/O Expansion Unit system. For example, individual boats and power supplies may be turned on and turned off independently.

An FRU in an External I/O Expansion Unit (*fru*) is identified as:

`iox@nnnn/iob0` – I/O boat in the left tray (rear view)

`iox@nnnn/iob1` – I/O boat in the right tray (rear view)

`iox@nnnn/iob0/link` – Uplink card in boat 0

`iox@nnnn/iob1/link` – Uplink card in boat 1

`iox@nnnn/ps0` – Power supply in the left bay (front view)

`iox@nnnn/ps1` – Power supply in the right bay (front view)

EXAMPLES

EXAMPLE 1 Displaying Temperature, Voltage, Current, and Fanspeed Sensor Readings

```
XSCF> ioxadm env -te iox@A3B5
```

Location	Sensor	Value	Res	Units
IOX@A3B5/PS0	T_AMBIENT	28.000	1.000	C
IOX@A3B5/PS0	T_CHIP	28.000	1.000	C
IOX@A3B5/PS0	T_HOTSPOT	31.000	1.000	C
IOX@A3B5/PS0	SWITCH	On	-	SWITCH
IOX@A3B5/PS0	V_12V_ANODE	11.703	0.059	V
IOX@A3B5/PS0	V_12V_CATHODE	11.703	0.059	V
IOX@A3B5/PS0	V_ISHARE	0.632	0.040	V
IOX@A3B5/PS0	I_DC	2.316	0.289	A
IOX@A3B5/PS0	S_FAN_ACTUAL	3708.791	40.313	RPM
IOX@A3B5/PS0	S_FAN_SET	4500.000	300.000	RPM
IOX@A3B5/PS1	T_AMBIENT	28.000	1.000	C
IOX@A3B5/PS1	T_CHIP	29.000	1.000	C
IOX@A3B5/PS1	T_HOTSPOT	31.000	1.000	C
IOX@A3B5/PS1	SWITCH	On	-	SWITCH
IOX@A3B5/PS1	V_12V_ANODE	11.762	0.059	V
IOX@A3B5/PS1	V_12V_CATHODE	11.762	0.059	V
IOX@A3B5/PS1	V_ISHARE	0.672	0.040	V

IOX@A3B5/PS1	I_DC	5.211	0.289	A
IOX@A3B5/PS1	S_FAN_ACTUAL	4115.854	49.588	RPM
IOX@A3B5/PS1	S_FAN_SET	4500.000	300.000	RPM
IOX@A3B5/IOB0	T_CHIP	32.000	1.000	C
IOX@A3B5/IOB0	T_HOTSPOT	35.000	1.000	C
IOX@A3B5/IOB1	T_CHIP	33.000	1.000	C
IOX@A3B5/IOB1	T_HOTSPOT	36.000	1.000	C
IOX@A3B5/IOB1	V_12_0V	12.052	0.005	V
IOX@A3B5/IOB1	V_12V_MAIN	12.000	0.400	V
IOX@A3B5/IOB1	V_1_0V	1.030	0.001	V
IOX@A3B5/IOB1	V_1_5V	1.496	0.001	V
IOX@A3B5/IOB1	V_3_3V	3.291	0.002	V
IOX@A3B5/IOB1	V_3_3AUX	3.308	0.002	V
IOX@A3B5/IOB1	I_DC	8.600	0.200	A
IOX@A3B5/IOB1/LINK	T_SIGCON0	45.000	40.000	C
IOX@A3B5/IOB1/LINK	T_SIGCON1	45.000	40.000	C
IOU#1-PCI#1	T_SIGCON0	45.000	40.000	C
IOU#1-PCI#1	T_SIGCON1	45.000	40.000	C

EXAMPLE 2 Display All Sensor Readings on a Link and Suppressing Headers

```
XSCF> ioxadm -p env iou#1-pci#1
IOU#1-PCI#1 T_SIGCON0 45.000 40.000 C
IOU#1-PCI#1 T_SIGCON1 45.000 40.000 C
IOU#1-PCI#1 DATA      On      -      LED
IOU#1-PCI#1 MGMT      Flash  -      LED
```

EXAMPLE 3 Display All External I/O Expansion Units or Downlink Card Paths

```
XSCF> ioxadm list
IOX          Link 0          Link 1
IOX@0033     IOU#1-PCI#4     IOU#1-PCI#1
IOX@12B4     -               IOU#1-PCI#2
-           IOU#2-PCI#1
```

In EXAMPLE 3, the `list` command is used to display the connections between External I/O Expansion Units and downlink cards in the host. IOX@0033 (which includes boats, uplink cards, and power supplies) is connected to the host through two downlink cards. The `Link 0` column shows which host downlink card is attached to `boat0`. The `Link 1` column shows which host downlink card is attached to `boat1`. IOX@12B4 is connected to the host through one downlink card. This card is connected to `boat1`. A "-" shows that there is no host link connection to the box. It may have a boat and uplink card installed in the bay, or the bay could be empty. If the boat is installed, either it is not connected to the host, or the host downlink card slot is powered off.

EXAMPLE 4 Displaying a Single External I/O Expansion Unit

```
XSCF> ioxadm list iox@12B4
```

IOX	Link 0	Link 1
IOX@12B4	-	IOU#1-PCI#2

EXAMPLE 5 Displaying a Single External I/O Expansion Unit Using Verbose Output

```
XSCF> ioxadm -v list IOU#1-PCI#1
```

Location	Type	FW Ver	Serial Num	Part Num	State
IOX@X07A	IOX	2.1	XCX07A	CF005016937/5016937-03	On
IOX@X07A/PS0	A195	-	DD0579	CF003001701/3001701-04	On
IOX@X07A/PS1	A195	-	DD0588	CF003001701/3001701-04	On
IOX@X07A/IOB0	PCIE	-	XE00E5	CF005016939/5016939-05	On
IOX@X07A/IOB0/LINK	CU	2.0	XF01HJ	CF005017040/5017040-04	On
IOU#0-PCI#3	CU	2.0	XF01AD	CF005017040/5017040-03	On

EXAMPLE 6 Displaying a Downlink Card Using Hostpath in Verbose Mode With Headers Suppressed

```
XSCF> ioxadm -p -v list IOU#0-PCI#2
```

IOU#0-PCI#2	OP	2.0	XF01A1	CF005017040/5017040-03	on
-------------	----	-----	--------	------------------------	----

EXAMPLE 7 Powering On the Locator LED for Power Supply 0 in External I/O Expansion Unit 12B4

```
XSCF> ioxadm locator on iox@12B4/ps0
```

EXAMPLE 8 Displaying Locator LED Status for the External I/O Expansion Unit

```
XSCF> ioxadm locator iox@12B4
```

Location	Sensor	Value	Resolution	Units
IOX@12B4	LOCATE	Fast	-	LED
IOX@12B4/PS0	SERVICE	Fast	-	LED

If the FRU service indicator is already on due to a detected fault condition, only the box locator LED will be set to fast.

EXAMPLE 9 Enabling the Indicator for Power Supply 1 When Power Supply 1 Has a Fault Indication

```
XSCF> ioxadm locator on iox@x031/ps1
```

```
XSCF> ioxadm locator
```

Location	Sensor	Value	Resolution	Units
IOX@X031	LOCATE	Fast	-	LED

```
XSCF> ioxadm env -1 iox@x031/ps1 SERVICE
```

Location	Sensor	Value	Resolution	Units
IOX@X031/PS1	SERVICE	On	-	LED

The External I/O Expansion Unit chassis white LED has an integrated push button. The button can be used to toggle the state of the chassis white locator LED between off and fast. If the push button is used to turn off the locator LED, fast blink FRU service LEDs are cleared.

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.



NAME	man - display manual pages of specified XSCF shell command										
SYNOPSIS	man <i>command_name</i> ... man -h										
DESCRIPTION	man(1) displays manual pages of specified XSCF shell command.										
Privileges	No privileges are required to run this command. Refer to <code>setprivileges(8)</code> for more information.										
OPTIONS	The following option is supported; -h Displays usage statement. When used with other options or operands, an error occurs.										
OPERANDS	The following operand is supported: <i>command_name</i> Specifies the command name whose manual page is displayed. Multiple <i>command_name</i> can be specified by delimited the spaces.										
EXTENDED DESCRIPTION	<ul style="list-style-type: none"> ■ If the relevant manual page is too long, the page is divided into pages that each can fit on one screen. In such cases, the following key operations are available: <table border="0" style="margin-left: 2em;"> <thead> <tr> <th style="text-align: left;">Key</th> <th style="text-align: left;">Description</th> </tr> </thead> <tbody> <tr> <td>Enter</td> <td>Displays the next line.</td> </tr> <tr> <td>space</td> <td>Displays the next page.</td> </tr> <tr> <td>b</td> <td>Goes back half a page.</td> </tr> <tr> <td>q</td> <td>Quits display of the page in the manual.</td> </tr> </tbody> </table> <ul style="list-style-type: none"> ■ If <code>intro</code> is specified for <i>command_name</i>, a list of XSCF shell commands is displayed. 	Key	Description	Enter	Displays the next line.	space	Displays the next page.	b	Goes back half a page.	q	Quits display of the page in the manual.
Key	Description										
Enter	Displays the next line.										
space	Displays the next page.										
b	Goes back half a page.										
q	Quits display of the page in the manual.										
EXAMPLES	<p>EXAMPLE 1 Displays the manual page of the <code>addboard(8)</code> command.</p> <pre style="margin-left: 2em;">XSCF> man addboard</pre> <p>EXAMPLE 2 Displays a list of XSCF shell commands.</p> <pre style="margin-left: 2em;">XSCF> man intro</pre>										

man(1)

EXIT STATUS

The following exit values are returned:

0	Successful completion
>0	An error occurred.

NAME	moveboard - move an eXtended System Board (XSB) from the current domain to another						
SYNOPSIS	<pre>moveboard [[-q] -{y n}] [-f] [-v] [-c configure] -d <i>domain_id</i> <i>xsb</i> [<i>xsb...</i>]</pre> <pre>moveboard [[-q] -{y n}] [-f] [-v] -c assign -d <i>domain_id</i> <i>xsb</i> [<i>xsb...</i>]</pre> <pre>moveboard [[-q] -{y n}] [-f] [-v] -c reserve -d <i>domain_id</i> <i>xsb</i> [<i>xsb...</i>]</pre> <pre>moveboard -h</pre>						
DESCRIPTION	<p>The <code>moveboard(8)</code> command disconnects an XSB from the current domain and, based on the domain component list (DCL), assigns it to, or configures it in, the specified domain.</p> <p>The <code>moveboard(8)</code> command is not available on the M3000 server.</p> <p>One of the following movement methods can be specified:</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;"><code>configure</code></td> <td>Disconnects a configured XSB from its domain configuration and configures it into the specified destination domain configuration. The incorporated XSB can be accessed from the Solaris OS.</td> </tr> <tr> <td style="padding-right: 20px;"><code>assign</code></td> <td>Disconnects a configured XSB from its domain configuration and assigns it to the specified destination domain configuration. The assigned XSB is reserved for the specified domain and cannot be configured in or assigned to other domains. The assigned system board is configured in the domain by reboot the domain or execution of the <code>addboard(8)</code> command with "<code>-c configure</code>".</td> </tr> <tr> <td style="padding-right: 20px;"><code>reserve</code></td> <td>Reserves disconnection of the specified XSB from the domain configuration of the move source, and reserves assignment of the XSB to the domain configuration of the move destination. The XSB is assigned to the domain configuration of the move destination when the domain power of the move source is turned off or rebooted. The XSB is subsequently incorporated when the domain power of the move destination is turned on or rebooted.</td> </tr> </table>	<code>configure</code>	Disconnects a configured XSB from its domain configuration and configures it into the specified destination domain configuration. The incorporated XSB can be accessed from the Solaris OS.	<code>assign</code>	Disconnects a configured XSB from its domain configuration and assigns it to the specified destination domain configuration. The assigned XSB is reserved for the specified domain and cannot be configured in or assigned to other domains. The assigned system board is configured in the domain by reboot the domain or execution of the <code>addboard(8)</code> command with " <code>-c configure</code> ".	<code>reserve</code>	Reserves disconnection of the specified XSB from the domain configuration of the move source, and reserves assignment of the XSB to the domain configuration of the move destination. The XSB is assigned to the domain configuration of the move destination when the domain power of the move source is turned off or rebooted. The XSB is subsequently incorporated when the domain power of the move destination is turned on or rebooted.
<code>configure</code>	Disconnects a configured XSB from its domain configuration and configures it into the specified destination domain configuration. The incorporated XSB can be accessed from the Solaris OS.						
<code>assign</code>	Disconnects a configured XSB from its domain configuration and assigns it to the specified destination domain configuration. The assigned XSB is reserved for the specified domain and cannot be configured in or assigned to other domains. The assigned system board is configured in the domain by reboot the domain or execution of the <code>addboard(8)</code> command with " <code>-c configure</code> ".						
<code>reserve</code>	Reserves disconnection of the specified XSB from the domain configuration of the move source, and reserves assignment of the XSB to the domain configuration of the move destination. The XSB is assigned to the domain configuration of the move destination when the domain power of the move source is turned off or rebooted. The XSB is subsequently incorporated when the domain power of the move destination is turned on or rebooted.						
Privileges	<p>You must have one of the following privileges to run this command:</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;"><code>platadm</code></td> <td>Can run this command for all domains.</td> </tr> <tr> <td style="padding-right: 20px;"><code>domainadm</code></td> <td>Can run this command only for your managed domains.</td> </tr> </table> <p>Note – You must have the <code>domainadm</code> privileges for both of source domain and destination domain to run <code>moveboard(8)</code> command.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>	<code>platadm</code>	Can run this command for all domains.	<code>domainadm</code>	Can run this command only for your managed domains.		
<code>platadm</code>	Can run this command for all domains.						
<code>domainadm</code>	Can run this command only for your managed domains.						

OPTIONS

The following options are supported:

- c *assign* Disconnects a configured XSB from its domain configuration and assigns it to the domain configuration of the move destination. If the -c option is omitted, "-c *configure*" is used.
- c *configure* Disconnects a configured XSB from its domain configuration and configures it in the domain configuration of the move destination. If the -c option is omitted, "-c *configure*" is used.
- c *reserve* Reserves disconnection of an XSB from its current domain configuration, and reserves assignment of the XSB to the domain configuration of the move destination. If the -c option is omitted, "-c *configure*" is used.
- d *domain_id* Specifies the ID of the destination domain in which an XSB is to be moved. *domain_id* can be 0–23 depending on the system configuration.
- f Forcibly detaches the specified XSB.

Caution – If the -f option is used to forcibly remove the XSB from the source domain, a serious problem may occur in a process bound to CPU or process accessing a device. For this reason, use of the -f option is not recommended in normal operation. If the -f option must be specified, verify the statuses of the source domain and job processes.

Note – The XSB which failed or detected the failure will not be configured to the DCL forcibly.

- h Displays usage statement. When used with other options or operands, an error occurs.
- n Automatically answers "n" (no) to all prompts.
- q Suppresses all messages to stdout, including prompts.
- v Specifies verbose output. If this option is specified with the -q option, the -v option is ignored.
- y Automatically answers "y" (yes) to all prompts.

OPERANDS The following operand is supported:

xsb Specifies the XSB number to be moved. Multiple *xsb* operands are permitted, separated by spaces. The following *xsb* form is accepted:

x-y

where:

x An integer from 00–15.

y An integer from 0–3.

EXTENDED DESCRIPTION

- When the command is executed, a prompt to confirm execution of the command with the specified options is displayed. Enter "y" to execute the command or "n" to cancel the command.
- If "-c configure" is specified when either of the following conditions apply to the domains, the XSB is configured in the domain configuration:
 - The Solaris OS of both the source and destination domains are running.
 - The Solaris OS of the destination domain is running even though the source domain is powered off.
- If "-c assign" is specified when either of the following conditions apply to the domains, the XSB is assigned to the domain configuration:
 - The Solaris OS of the source domain is running.
 - The source domain is powered off
- If "-c reserve" is specified when either the domain power of the move source has been turned off or the Solaris OS is not running, the XSB is immediately disconnected from the domain of the move source and assigned to the domain of the move destination
- Moving the XSB involves the following internal operations and therefore command execution may take time.
 - Disconnecting the hardware resource of the XSB from the Solaris OS
 - Running a hardware diagnosis on the XSB when connecting it
- See the `setdcl(8)` and `showdcl(8)` commands for DCL.

EXAMPLES

EXAMPLE 1 Disconnects XSB#00-0 from the current domain and attaches it to domain ID 1.

```
XSCF> moveboard -d 1 00-0
```

EXAMPLE 2 Reserves assignment of the XSB#00-0 to the domain ID 1.

```
XSCF> moveboard -d 1 -c reserve 00-0
```

EXIT STATUS

The following exit values are returned:

0 Successful completion.

>0 An error occurred.

SEE ALSO

addboard (8), deleteboard (8), setdcl (8), setupfru (8), showboards (8), showdcl (8), showdevices (8), showdomainstatus (8), showfru (8)

NAME	nslookup - refer to the DNS server for the host								
SYNOPSIS	nslookup <i>hostname</i> nslookup -h								
DESCRIPTION	nslookup(8) refers to the DNS server for the host. The following information is displayed: <table border="0"> <tr> <td>Server</td> <td>DNS server name</td> </tr> <tr> <td>Address</td> <td>IP address of DNS server</td> </tr> <tr> <td>Name</td> <td>Specified host name</td> </tr> <tr> <td>Address</td> <td>IP address of the host name</td> </tr> </table>	Server	DNS server name	Address	IP address of DNS server	Name	Specified host name	Address	IP address of the host name
Server	DNS server name								
Address	IP address of DNS server								
Name	Specified host name								
Address	IP address of the host name								
Privileges	You must have one of the following privileges to run this command: useradm, platadm, platop, auditadm, auditop, domainadm, domainmgr, domainop, fieldeng Refer to setprivileges(8) for more information.								
OPTIONS	The following option is supported: <table border="0"> <tr> <td>-h</td> <td>Displays usage statement. When used with other options or operands, an error occurs.</td> </tr> </table>	-h	Displays usage statement. When used with other options or operands, an error occurs.						
-h	Displays usage statement. When used with other options or operands, an error occurs.								
OPERANDS	The following operand is supported: <table border="0"> <tr> <td><i>hostname</i></td> <td>Specifies the host name to be referred. A Fully Qualified Domain Name (FQDN) or a short form of the name can be specified.</td> </tr> </table>	<i>hostname</i>	Specifies the host name to be referred. A Fully Qualified Domain Name (FQDN) or a short form of the name can be specified.						
<i>hostname</i>	Specifies the host name to be referred. A Fully Qualified Domain Name (FQDN) or a short form of the name can be specified.								
EXAMPLES	EXAMPLE 1 Displays the host whose host name is scf0-hostname0. <pre>XSCF> nslookup scf0-hostname0 Server: server.example.com Address: xx.xx.xx.xx Name: scf0-hostname0.example.com Address: xx.xx.xx.xx</pre>								

nslookup(8)

EXIT STATUS

The following exit values are returned:

- | | |
|----|------------------------|
| 0 | Successful completion. |
| >0 | An error occurred. |

NAME	password - manage user passwords and expiration settings		
SYNOPSIS	<p>password [-e <i>days</i> <i>date</i> Never] [-i <i>inactive</i>] [-M <i>maxdays</i>] [-n <i>mindays</i>] [-w <i>warn</i>] [<i>user</i>]</p> <p>password -h</p>		
DESCRIPTION	<p>password (8) changes a user's password and password expiration settings.</p> <p>The password is specified in up to 32 characters. The following characters are valid:</p> <ol style="list-style-type: none"> 1. abcdefghijklmnopqrstuvwxyz 2. ABCDEFGHIJKLMNOPQRSTUVWXYZ 3. 0123456789 4. !@#%\$%^&*[]{}()-+= '~></'?;:[SPACE] <p>When invoked with one or more options, password will make changes to the expiration settings of the account. See <code>setpasswordpolicy(8)</code> for a description of default values.</p> <p>When invoked without options, password prompts you to change the account password.</p> <p>When invoked without a <i>user</i> operand, password operates on the current user account.</p> <hr/> <p>Caution – When you change the password for another user by using the <i>user</i> operand, the system password policy is <i>not</i> enforced. The <i>user</i> operand is intended only for creating a new user's initial password or replacing a lost or forgotten password for a user account. When changing another user's password, be sure to choose a password that conforms with the system password policy. You can display the current password policy settings with the <code>showpasswordpolicy(8)</code> command.</p> <hr/> <p>Whether the user name is specified or not, the account must be local. password returns an error if it is not local.</p>		
Privileges	<p>You must have one of the following privileges to run this command:</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;">useradm</td> <td>Can run this command with or without any options or operand. Can change the password for any account.</td> </tr> </table> <p>No privileges are required in the following cases:</p> <ul style="list-style-type: none"> ■ To change the password for the current user account ■ To use the -h option 	useradm	Can run this command with or without any options or operand. Can change the password for any account.
useradm	Can run this command with or without any options or operand. Can change the password for any account.		

Refer to `setprivileges(8)` for more information.

OPTIONS

The following options are supported

`-e days | date | Never` *days* sets the number of days, starting from today, during which the XSCF account is enabled. *days* is in the format of a number (0-10730). If the current date plus the number of *days* exceeds January 2038 the number is considered invalid and the command will fail.

date sets the date when the account expires, not exceeding January 2038. The *date* format can be:

mm/dd/yy (10/30/08)

yyyy-mm-dd (2008-10-30)

yy-mm-dd (08-10-30)

dd-Mmm-yy (30-Oct-08)

dd-Mmm-yyyy (30-Oct-2008)

dd Mmm yy ("30 Oct 08")

dd Mmm yyyy ("30 Oct 2008")

Mmm dd, yy ("Oct 30, 08")

Mmm dd, yyyy ("Oct 30, 2008")

Quotes must be used for formats with an embedded space. It is case insensitive.

Never means an account will not expire.

`-h` Displays usage statement.

When used with other options or operands, an error occurs.

`-i inactive` Sets the number of days after a password expires until the account is locked. This value is assigned to new user accounts when they are created. The initial value is `-1`. A value of `-1` means that the account will not be locked after the password expires. Valid values are integers with value of `-1` or greater.

- M *maxdays*** Sets the maximum number of days that a password is valid. This value is assigned to new user accounts when they are created. The initial value is 999999.
- Valid values are integers with value of zero or greater.
- n *mindays*** Sets the minimum number of days between password changes. An initial value of zero for this field indicates that you can change the password at any time.
- Valid values are integers with value of zero or greater.
- This value is assigned to new user accounts when they are created.
- w *warn*** Sets the default number of days before password expiration at which to start warning the user. This value is assigned to new user accounts when they are created. The initial value is 7.
- Valid values are integers with value of zero or greater.

OPERANDS The following operands are supported:

user Specifies a valid user name.

EXAMPLES **EXAMPLE 1** Enabling Password Until February 2, 2008

```
XSCF> password -e 2008-02-02
```

EXAMPLE 2 Set Password Lock 10 Days After Password Expiration

```
XSCF> password -i 10
```

EXIT STATUS The following exit values are returned:

0 Successful completion.

>0 An error occurred.

SEE ALSO `setpasswordpolicy(8)`, `showpasswordpolicy(8)`

password(8)



NAME	ping - sends the ICMP ECHO_REQUEST packets to the network host or the network device
SYNOPSIS	ping [-c <i>count</i>] [-q] <i>host</i> ping -h
DESCRIPTION	The ping(8) command utilizes the ICMP ECHO_REQUEST datagram to elicit an ICMP ECHO_RESPONSE from the specified host or network device. When the ping(8) command normally executed, the network between XSCF and the specified host or network device can be judged as normal. And the network performance can be measured from the result.
Privileges	You must have one of the following privileges to run this command: <ul style="list-style-type: none"> ■ To execute the command to DSCP address: <i>plataadm, fieldeng</i> ■ To execute the command to "localhost" or to the loopback address (127.0.0.0/8): <i>fieldeng</i> ■ To execute the command to Inter SCF Network (ISN): <i>fieldeng</i> ■ The case other than those above: No privileges are required. Refer to <code>setprivileges(8)</code> for more information.
OPTIONS	The following options are supported: <ul style="list-style-type: none"> -c <i>count</i> Specifies the number of times to send the packet. After sent the packet for the number of specified times and received its response, the ping(8) command terminates. If omitted, the command continues sending the packet until the interrupt occurs. -h Displays usage statement. When used with other options or operands, an error occurs. -q Suppresses the output. Outputs the data at the start and at the end of the command.
OPERANDS	The following operand is supported: <ul style="list-style-type: none"> <i>host</i> Specifies the network host or the network device to send the packet. Can be specified with host name or IP address.

ping(8)

EXAMPLES

EXAMPLE 1 Sends the packet three times to a host named scf0-hostname0.

```
XSCF> ping -c 3 scf0-hostname0
PING scf0-hostname0 (XX.XX.XX.XX): 56 data bytes
64 bytes from XX.XX.XX.XX: icmp_seq=0 ttl=64 time=0.1 ms
64 bytes from XX.XX.XX.XX: icmp_seq=1 ttl=64 time=0.1 ms
64 bytes from XX.XX.XX.XX: icmp_seq=2 ttl=64 time=0.1 ms

--- scf0-hostname0 ping statistics ---
3 packets transmitted, 3 packets received, 0% packet loss
round-trip min/avg/max = 0.1/0.1/0.1 ms
```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

NAME	poweroff - turn off the power to the specified domain
SYNOPSIS	<p>poweroff [[-q] -{y n}] [-f] [-M] -d <i>domain_id</i></p> <p>poweroff [[-q] -{y n}] -a [-M]</p> <p>poweroff -h</p>
DESCRIPTION	<p>The <code>poweroff(8)</code> command turns off the power to the specified domain.</p> <p>The command can turn off the power to the specified domain or to all domains. After ordinary shutdown processing for the operating system is executed, the power is turned off.</p>
Privileges	<p>You must have one of the following privileges to run this command:</p> <p><code>platadm, fieldeng</code> Can run this command for all domains.</p> <p><code>domainadm, domainmgr</code> Can run this command only for your managed domains.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p>-a Turns off the power to all domains. Only users who have the <code>platadm</code> and <code>fieldeng</code> privileges can specify this option. This option turns off the power to a system in process of warm-up or air-conditioning, or to a domain in process of power-on.</p> <p>-d <i>domain_id</i> Specifies the ID of the domain to be turned off. <i>domain_id</i> can be 0–23 depending on the system configuration. This option does not turn off the power to a system in process of warm-up or air-conditioning, or to a domain in process of power-on.</p> <p>-f Uses XSCF to forcibly turn off the power to the specified domain. This option is used together with the <code>-d</code> option.</p> <p>-h Displays usage statement. When used with other options or operands, an error occurs.</p> <p>-M Displays text by page. This option provides a function that is the same as that of the <code>more</code> command.</p> <p>-n Automatically answers "n" (no) to all prompts.</p> <p>-q Suppresses all messages to stdout, including prompts.</p> <p>-y Automatically answers "y" (yes) to all prompts.</p>

**EXTENDED
DESCRIPTION**

- When the command is executed, a prompt to confirm execution of the command with the specified options is displayed. Enter "y" to execute the command or "n" to cancel the command.
- If the Solaris OS of the target domain is running, the `poweroff(8)` command processing is equivalent to that of the `shutdown(1M)` command with the "-i5" option specified.
- A domain cannot be powered off while the Solaris OS of the domain is booting. Execute the `poweroff(8)` command again after the booting is completed.
- A domain cannot be powered off by the `poweroff(8)` command while the Solaris OS of the domain is running in single-user mode. Execute the `shutdown(1M)` command in the domain.
- When the `poweroff(8)` command is executed, power-off results for each of the specified domains are displayed in the following format:

Powered off The power was turned off normally.

Not Powering off An error occurred, and the power could not be turned off. An error message is displayed with "Not Powering off."

- The `showdomainstatus(8)` command can be used to check the power of each domain on the system is off.

EXAMPLES

EXAMPLE 1 Turns off power to all domains.

```
XSCF> poweroff -a
```

```
DomainIDs to power off:00,01,02,03
```

```
Continue? [y|n]:y
```

```
00:Powering off
```

```
01:Powering off
```

```
02:Powering off
```

```
03:Powering off
```

Note

This command only issues the instruction to power-off.

The result of the instruction can be checked by the "showlogs power".

EXAMPLE 2 Turns off power to domains with domain IDs 0.

```
XSCF> poweroff -d 0
```

```
DomainIDs to power off:00
```

```
Continue? [y|n]:y
```

```
00:Powering off
```

Note

This command only issues the instruction to power-off.

The result of the instruction can be checked by the "showlogs power".

EXAMPLE 3 Forcibly turns off power to domains with domain IDs 0.

```
XSCF> poweroff -f -d 0
```

```
DomainIDs to power off:00
```

The -f option will cause domains to be immediately resets.

```
Continue? [y|n]:y
```

```
00:Powering off
```

Note

This command only issues the instruction to power-off.

The result of the instruction can be checked by the "showlogs power".

EXAMPLE 4 Turns off power to domains with domain IDs 2. Automatically replies with 'y' to the prompt.

```
XSCF> poweroff -y -d 2
```

```
DomainIDs to power off:02
```

```
Continue? [y|n]:y
```

```
02:Powering off
```

Note

This command only issues the instruction to power-off.

The result of the instruction can be checked by the "showlogs power".

EXAMPLE 5 Turns off power to domains with domain IDs 2. Automatically replies with

'y' without displaying the prompt.

```
XSCF> poweroff -q -y -d 2
```

EXIT STATUS

The following exit values are returned:

0 Successful completion.

>0 An error occurred.

SEE ALSO

poweron(8), reset(8), showdomainstatus(8)

NAME	poweron - turn on the power to the specified domain
SYNOPSIS	<p>poweron [[-q] -{y n}] [-M] -d <i>domain_id</i></p> <p>poweron [[-q] -{y n}] [-M] -a</p> <p>poweron -h</p>
DESCRIPTION	<p>The poweron(8) command turns on the power to the specified domain.</p> <p>The command can turn on the power to the specified domain or to all domains.</p>
Privileges	<p>You must have one of the following privileges to run this command:</p> <p>platadm, fieldeng Can run this command for all domains.</p> <p>domainadm, domainmgr Can run this command only for your managed domains.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p>-a Turns on the power to every domain that has been completely set up. Only users who have the platadm or fieldeng privileges can specify this option. The "domain that has been completely set up" means a domain that has been completely set up with the setdcl(8) and addboard(8) commands.</p> <p>-d <i>domain_id</i> Specifies the ID of the domain to be turned on. <i>domain_id</i> can be 0-23 depending on the system configuration.</p> <p>-h Displays usage statement. When used with other options or operands, an error occurs.</p> <p>-M Displays text by page. This option provides a function that is the same as that of the more command.</p> <p>-n Automatically answers "n" (no) to all prompts.</p> <p>-q Suppresses all messages to stdout, including prompts.</p> <p>-y Automatically answers "y" (yes) to all prompts.</p>
EXTENDED DESCRIPTION	<ul style="list-style-type: none"> ■ When the command is executed, a prompt to confirm execution of the command with the specified options is displayed. Enter "y" to execute the command or "n" to cancel the command.

- When the `poweron(8)` command is executed, power-on results for each of the specified domains are displayed in the following format:

Powering on The power was turned on normally.

Not Powering on An error occurred, and the power could not be turned on. An error message is displayed with Not Powering on.

- The `showdomainstatus(8)` command can be used to check whether the power of each domain on the system is on.

EXAMPLES

EXAMPLE 1 Turns on power to all domains.

```
XSCF> poweron -a
```

```
DomainIDs to power on:00,01,02,03
```

```
Continue? [y|n]:y
```

```
00:Powering on
```

```
01:Powering on
```

```
02:Powering on
```

```
03:Powering on
```

Note

This command only issues the instruction to power-on.

The result of the instruction can be checked by the "showlogs power".

EXAMPLE 2 Turns on power to domains with domain IDs 0.

```
XSCF> poweron -d 0
```

```
DomainIDs to power on:00
```

```
Continue? [y|n]:y
```

```
00:Powering on
```

Note

This command only issues the instruction to power-on.

The result of the instruction can be checked by the "showlogs power".

EXAMPLE 3 Turns on power to domains with domain IDs 0. Automatically replies with 'y'

to the prompt.

```
XSCF> poweron -y -d 0
```

```
DomainIDs to power on:00
```

```
Continue? [y|n]:y
```

```
00:Powering on
```

Note

This command only issues the instruction to power-on.

The result of the instruction can be checked by the "showlogs power".

```
XSCF>
```

EXAMPLE 4 Turns on power to domains with domain IDs 1. Automatically replies with 'y' without displaying the prompt.

```
XSCF> poweron -q -y -d 1
```

EXIT STATUS

The following exit values are returned:

0 Successful completion.

>0 An error occurred.

SEE ALSO

poweroff(8), **reset**(8), **showdomainstatus**(8)

poweron(8)



NAME	prtfriu - display FRUID data on the system and External I/O Expansion Unit
SYNOPSIS	prtfriu [-c] [-l] [-M] [-x] [<i>container</i>] prtfriu -h
DESCRIPTION	<p>prtfriu is used to obtain Field Replaceable Unit Identifier (FRUID) data from the system and External I/O Expansion Unit. Its output is a tree structure, echoing the path in the FRU tree to each container. When a container is found, the data from that container is printed in a tree structure as well.</p> <p>prtfriu without any arguments prints the FRU hierarchy and all of the FRUID container data. prtfriu prints to the screen. Output can be redirected to a file.</p> <p>Note – FRU information from the domains is not available using this command.</p>
Privileges	<p>You must have <code>fieldeng</code> privileges to run this command.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>
OPTIONS	<p>The following options are supported:</p> <ul style="list-style-type: none"> -c Prints only the containers and their data. This option does not print the FRU tree hierarchy. -h Displays usage statement. When used with other options or operands, an error occurs. -M Displays text by page. This option provides a function that is the same as that of the <code>more</code> command. -l Prints only the FRU tree hierarchy. This option does not print the container data. -x Prints in XML format with a system identifier (SYSTEM) of <code>prtfriureg.dtd</code>.
OPERANDS	<p>The following operands are supported:</p> <ul style="list-style-type: none"> <i>container</i> The path and name of the particular hardware that holds data.
EXAMPLES	<p>EXAMPLE 1 Displaying FRU Tree Hierarchy</p> <pre>XSCF> prtfriu -l /frutree /frutree/chassis (fru) /frutree/chassis/iou0</pre>

```

/frutree/chassis/iou0/IOU (fru)
/frutree/chassis/iou0/IOU/slot3
/frutree/chassis/iou0/IOU/slot3/LINK (container)
/frutree/chassis/iou0/IOU/slot3/LINK/iox983392.IOX.iob1.PCIX.LINK (fru)
/frutree/chassis/iox983392?Label=IOX@XCX031
/frutree/chassis/iox983392?Label=IOX@XCX031/IOX (container)
/frutree/chassis/iox983392?Label=IOX@XCX031/IOX/ps0
/frutree/chassis/iox983392?Label=IOX@XCX031/IOX/ps0/A195 (container)
/frutree/chassis/iox983392?Label=IOX@XCX031/IOX/ps1
/frutree/chassis/iox983392?Label=IOX@XCX031/IOX/ps1/A195 (container)
/frutree/chassis/iox983392?Label=IOX@XCX031/IOX/iob1
/frutree/chassis/iox983392?Label=IOX@XCX031/IOX/iob1/PCIX (container)
/frutree/chassis/iox983392?Label=IOX@XCX031/IOX/iob1/PCIX/LINK
(container)
/frutree/chassis/iox983392?Label=IOX@XCX031/IOX/iob1/PCIX/LINK/
iou0.IOU.slot3.LINK (fru)
/frutree/chassis/MBU_B (container)
/frutree/chassis/MBU_B/CPUM#0/CPUM (container)
/frutree/chassis/MBU_B/CPUM#1/CPUM (container)
/frutree/chassis/MBU_B/MEMB#0 (fru)
/frutree/chassis/MBU_B/CPUM#1/CPUM (container)
/frutree/chassis/MBU_B/MEMB#0 (fru)
/frutree/chassis/MBU_B/MEMB#0/MEMB (container)
/frutree/chassis/MBU_B/MEMB#0/MEMB/MEM#0/MEM (container)
/frutree/chassis/MBU_B/MEMB#0/MEMB/MEM#1/MEM (container)
/frutree/chassis/MBU_B/MEMB#0/MEMB/MEM#2/MEM (container)
/frutree/chassis/MBU_B/MEMB#0/MEMB/MEM#3/MEM (container)
/frutree/chassis/MBU_B/MEMB#0/MEMB/MEM#4/MEM (container)
/frutree/chassis/MBU_B/MEMB#0/MEMB/MEM#5/MEM (container)
/frutree/chassis/MBU_B/MEMB#0/MEMB/MEM#6/MEM (container)
/frutree/chassis/MBU_B/MEMB#0/MEMB/MEM#7/MEM (container)
/frutree/chassis/MBU_B/MEMB#1 (fru)
/frutree/chassis/MBU_B/MEMB#1/MEMB (container)
/frutree/chassis/MBU_B/MEMB#1/MEMB/MEM#8/MEM (container)

```

```

/frutree/chassis/MBU_B/MEMB#1/MEMB/MEM#9/MEM (container)
/frutree/chassis/MBU_B/MEMB#1/MEMB/MEM#10/MEM (container)
/frutree/chassis/MBU_B/MEMB#1/MEMB/MEM#11/MEM (container)
/frutree/chassis/MBU_B/MEMB#1/MEMB/MEM#12/MEM (container)
/frutree/chassis/MBU_B/MEMB#1/MEMB/MEM#13/MEM (container)
/frutree/chassis/MBU_B/MEMB#1/MEMB/MEM#14/MEM (container)
/frutree/chassis/MBU_B/MEMB#1/MEMB/MEM#15/MEM (container)
/frutree/chassis/XSCFU (container)
/frutree/chassis/OPNL (container)
/frutree/chassis/PSU#0 (fru)
/frutree/chassis/PSU#0/PSU (container)
/frutree/chassis/PSU#2 (fru)
/frutree/chassis/PSU#2/PSU (container)
/frutree/chassis/IOU#0 (fru)
/frutree/chassis/IOU#0/IOU (container)
/frutree/chassis/IOU#0/IOU/DDCR#0/DDCR (container)
/frutree/chassis/FANBP_C#0 (fru)
/frutree/chassis/FANBP_C#0/FANBP_C (container)

```

EXAMPLE 2 Displaying A list of Containers

```

XSCF> prtf -lc
/frutree/chassis/iou0/IOU/slot3/LINK (container)
/frutree/chassis/iox983392?Label=IOX@XCX031/IOX (container)
/frutree/chassis/iox983392?Label=IOX@XCX031/IOX/ps0/A195 (container)
/frutree/chassis/iox983392?Label=IOX@XCX031/IOX/ps1/A195 (container)
/frutree/chassis/iox983392?Label=IOX@XCX031/IOX/iob1/PCIX (container)
/frutree/chassis/iox983392?Label=IOX@XCX031/IOX/iob1/PCIX/LINK
(container)
/frutree/chassis/MBU_B (container)
/frutree/chassis/MBU_B/CPUM#0/CPUM (container)
/frutree/chassis/MBU_B/CPUM#1/CPUM (container)
/frutree/chassis/MBU_B/MEMB#0/MEMB (container)
/frutree/chassis/MBU_B/MEMB#0/MEMB/MEM#0/MEM (container)
/frutree/chassis/MBU_B/MEMB#0/MEMB/MEM#1/MEM (container)

```

```

/frutree/chassis/MBU_B/MEMB#0/MEMB/MEM#2/MEM (container)
/frutree/chassis/MBU_B/MEMB#0/MEMB/MEM#3/MEM (container)
/frutree/chassis/MBU_B/MEMB#0/MEMB/MEM#4/MEM (container)
/frutree/chassis/MBU_B/MEMB#0/MEMB/MEM#5/MEM (container)
/frutree/chassis/MBU_B/MEMB#0/MEMB/MEM#6/MEM (container)
/frutree/chassis/MBU_B/MEMB#0/MEMB/MEM#7/MEM (container)
/frutree/chassis/MBU_B/MEMB#1/MEMB (container)
/frutree/chassis/MBU_B/MEMB#1/MEMB/MEM#8/MEM (container)
/frutree/chassis/MBU_B/MEMB#1/MEMB/MEM#9/MEM (container)
/frutree/chassis/MBU_B/MEMB#1/MEMB/MEM#10/MEM (container)
/frutree/chassis/MBU_B/MEMB#1/MEMB/MEM#11/MEM (container)
/frutree/chassis/MBU_B/MEMB#1/MEMB/MEM#12/MEM (container)
/frutree/chassis/MBU_B/MEMB#1/MEMB/MEM#13/MEM (container)
/frutree/chassis/MBU_B/MEMB#1/MEMB/MEM#14/MEM (container)
/frutree/chassis/MBU_B/MEMB#1/MEMB/MEM#15/MEM (container)
/frutree/chassis/XSCFU (container)
/frutree/chassis/OPNL (container)
/frutree/chassis/PSU#0/PSU (container)
/frutree/chassis/PSU#2/PSU (container)
/frutree/chassis/IOU#0/IOU (container)
/frutree/chassis/IOU#0/IOU/DDCR#0/DDCR (container)
/frutree/chassis/FANBP_C#0/FANBP_C (container)

```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

ioxadm(8)

NAME	rebootxscf - reset the XSCF								
SYNOPSIS	rebootxscf [[-q] -{y n}] rebootxscf -h								
DESCRIPTION	The <code>rebootxscf(8)</code> command resets the XSCF. In the M8000/M9000 servers, both of the active XSCF and the standby XSCF will be reset.								
Privileges	You must have <code>platadm</code> or <code>fieldeng</code> privilege to run this command. Refer to <code>setprivileges(8)</code> for more information.								
OPTIONS	The following options are supported: <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;">-h</td> <td>Displays usage statement. When used with other options or operands, an error occurs.</td> </tr> <tr> <td style="padding-right: 20px;">-n</td> <td>Automatically answers "n" (no) to all prompts.</td> </tr> <tr> <td style="padding-right: 20px;">-q</td> <td>Suppresses all messages to stdout, including prompts.</td> </tr> <tr> <td style="padding-right: 20px;">-y</td> <td>Automatically answers "y" (yes) to all prompts.</td> </tr> </table>	-h	Displays usage statement. When used with other options or operands, an error occurs.	-n	Automatically answers "n" (no) to all prompts.	-q	Suppresses all messages to stdout, including prompts.	-y	Automatically answers "y" (yes) to all prompts.
-h	Displays usage statement. When used with other options or operands, an error occurs.								
-n	Automatically answers "n" (no) to all prompts.								
-q	Suppresses all messages to stdout, including prompts.								
-y	Automatically answers "y" (yes) to all prompts.								
EXTENDED DESCRIPTION	<ul style="list-style-type: none"> ■ When the command is executed, a prompt to confirm execution of the command is displayed. Enter "y" to execute the command or "n" to cancel the command. ■ When you cancel the XSCF reset using the <code>setdate(8)</code> which commands reset XSCF automatically, even if you perform this command, the information that is set is not applied in XSCF. 								
EXAMPLES	<p>EXAMPLE 1 Resets the XSCF.</p> <pre>XSCF> rebootxscf The XSCF will be reset. Continue? [y n]:y</pre> <p>EXAMPLE 2 Resets the XSCF. Automatically replies with 'y' to the prompt.</p> <pre>XSCF> rebootxscf -y The XSCF will be reset. Continue? [y n]:y</pre> <p>EXAMPLE 3 Resets the XSCF. Automatically replies with 'y' without displaying the prompt.</p> <pre>XSCF> rebootxscf -q -y</pre>								

EXAMPLE 4 Cancels the `rebootxscf(8)` command execution that is in progress.

```
XSCF> rebootxscf  
The XSCF will be reset. Continue? [y|n]:n  
XSCF>
```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

`applynetwork(8)`, `setdate(8)`, `sethttps(8)`, `setssh(8)`

NAME	replacefru - replace a field replaceable unit (FRU)
SYNOPSIS	replacefru replacefru -h
DESCRIPTION	<p>The <code>replacefru(8)</code> command replaces an FRU. The command allows the user to select, confirm, and replace the FRU interactively using menus.</p> <p>The following FRUs can be replaced using the <code>replacefru(8)</code> command.</p> <ul style="list-style-type: none"> ■ CPU/Memory Board unit (CMU) ■ I/O unit (IOU) ■ FAN unit (FANU) ■ Power supply unit (PSU) ■ XSCF unit (XSCFU)
Privileges	<p>You must have <code>fieldeng</code> privileges to run this command.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>
OPTIONS	<p>The following option is supported.</p> <p><code>-h</code> Displays usage statement.</p>
EXIT STATUS	<p>The following exit values are returned:</p> <p>0 Successful completion.</p> <p>>0 An error occurred.</p>
SEE ALSO	addboard(8) , addfru(8) , deleteboard(8) , deletefru(8) , setupfru(8) , showdcl(8) , showdomainstatus(8) , showfru(8) , showhardconf(8) , testsb(8) , unlockmaintenance(8)

replacefru(8)



NAME	reset - reset the specified domain										
SYNOPSIS	<pre>reset [[-q] -{y n}] -d <i>domain_id</i> <i>level</i> reset -h</pre>										
DESCRIPTION	<p>Note – Since the <code>reset(8)</code> command forcibly resets the system, this command may cause a failure in a hard disk drive or other components. Use this command only for the purpose of recovery, such as if the Solaris OS hangs, and for other limited purposes.</p> <p>The <code>reset(8)</code> command resets the specified domain.</p> <p>The following three levels of resetting can be specified:</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;"><code>por</code></td> <td>Resets the domain system.</td> </tr> <tr> <td><code>panic</code></td> <td>Instructs the Solaris OS of the domain to generate a panic. The command is ignored if it is issued during power-off or shutdown.</td> </tr> <tr> <td><code>xir</code></td> <td>Resets the domain CPU.</td> </tr> </table>	<code>por</code>	Resets the domain system.	<code>panic</code>	Instructs the Solaris OS of the domain to generate a panic. The command is ignored if it is issued during power-off or shutdown.	<code>xir</code>	Resets the domain CPU.				
<code>por</code>	Resets the domain system.										
<code>panic</code>	Instructs the Solaris OS of the domain to generate a panic. The command is ignored if it is issued during power-off or shutdown.										
<code>xir</code>	Resets the domain CPU.										
Privileges	<p>You must have one of the following privileges to run this command:</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;"><code>platadm, fieldeng</code></td> <td>Can run this command for all domains.</td> </tr> <tr> <td><code>domainadm, domainmgr</code></td> <td>Can run this command only for your managed domains.</td> </tr> </table> <p>Refer to <code>setprivileges(8)</code> for more information.</p>	<code>platadm, fieldeng</code>	Can run this command for all domains.	<code>domainadm, domainmgr</code>	Can run this command only for your managed domains.						
<code>platadm, fieldeng</code>	Can run this command for all domains.										
<code>domainadm, domainmgr</code>	Can run this command only for your managed domains.										
OPTIONS	<p>The following options are supported:</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;"><code>-d <i>domain_id</i></code></td> <td>Specifies only one ID of the domain to be reset. <i>domain_id</i> can be 0–23 depending on the system configuration.</td> </tr> <tr> <td><code>-h</code></td> <td>Displays usage statement. When used with other options or operands, an error occurs.</td> </tr> <tr> <td><code>-n</code></td> <td>Automatically answers "n" (no) to all prompts.</td> </tr> <tr> <td><code>-q</code></td> <td>Suppresses all messages to stdout, including prompts.</td> </tr> <tr> <td><code>-y</code></td> <td>Automatically answers "y" (yes) to all prompts.</td> </tr> </table>	<code>-d <i>domain_id</i></code>	Specifies only one ID of the domain to be reset. <i>domain_id</i> can be 0–23 depending on the system configuration.	<code>-h</code>	Displays usage statement. When used with other options or operands, an error occurs.	<code>-n</code>	Automatically answers "n" (no) to all prompts.	<code>-q</code>	Suppresses all messages to stdout, including prompts.	<code>-y</code>	Automatically answers "y" (yes) to all prompts.
<code>-d <i>domain_id</i></code>	Specifies only one ID of the domain to be reset. <i>domain_id</i> can be 0–23 depending on the system configuration.										
<code>-h</code>	Displays usage statement. When used with other options or operands, an error occurs.										
<code>-n</code>	Automatically answers "n" (no) to all prompts.										
<code>-q</code>	Suppresses all messages to stdout, including prompts.										
<code>-y</code>	Automatically answers "y" (yes) to all prompts.										

OPERANDS

The following operand is supported:

<i>level</i>	Specifies the level of resetting. One of the following can be specified. This operand cannot be omitted.
<code>por</code>	Resets the domain system.
<code>panic</code>	Instructs the Solaris OS of the domain to generate a panic.
<code>xir</code>	Resets the domain CPU.

EXTENDED DESCRIPTION

- When the command is executed, a prompt to confirm execution of the command with the specified options is displayed. Enter "y" to execute the command or "n" to cancel the command.
- The `showdomainstatus(8)` command can be used to check whether the domain has been reset.
- If the `reset(8)` command is executed under either of the following conditions, processing is stopped before the Solaris OS is started:
 - The Mode switch on the operator panel is set to Service mode
 - The auto boot function has been disabled by the `setdomainmode(8)` command

EXAMPLES

EXAMPLE 1 Causes a panic in domain ID 0.

```
XSCF> reset -d 0 panic
```

```
DomainID to panic:00
```

```
Continue? [y|n]:y
```

```
00:Panicked
```

Note

This command only issues the instruction to reset.

The result of the instruction can be checked by the "showlogs power".

EXAMPLE 2 Resets the CPU in domain ID 0. Automatically answers 'y' to all prompts.

```
XSCF> reset -y -d 0 xir
```

```
DomainID to reset:00
```

```
Continue? [y|n]:y
```

```
00:Reset
```

Note

This command only issues the instruction to reset.

The result of the instruction can be checked by the "showlogs power".

EXAMPLE 3 Resets domain ID 0. Suppresses prompts, and automatically answers 'y' to all prompts.

```
XSCF> reset -q -y -d 0 por
```

EXAMPLE 4 Cancels the reset command execution that is in progress.

```
XSCF> reset -d 0 panic
```

```
DomainID to panic:00
```

```
Continue? [y|n]:n
```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

poweroff(8), poweron(8), setdomainmode(8), showdomainstatus(8)

reset(8)



NAME	resetdateoffset - reset the time subtraction between XSCF and the domain
SYNOPSIS	resetdateoffset resetdateoffset -h
DESCRIPTION	<p>The <code>resetdateoffset(8)</code> command resets the time subtraction between XSCF and the domain, which stored in XSCF.</p> <p>Usually, the time of the domain is synchronized with the time of XSCF. When the time of the domain changed by using a command such as the <code>date(1M)</code> which prepared in the Solaris OS of domain, the time subtraction between the time of XSCF and the changed time of domain will be stored in XSCF. The stored time subtraction remains after the domain reboot or after the XSCF reset by using a command such as the <code>rebootxscf(8)</code>, with the result that the time subtraction between XSCF and the domain remains stored.</p> <p>The <code>resetdateoffset(8)</code> command resets the every time subtraction between XSCF and each domain, which stored in XSCF. As a result, the time of domain after startup will be set to the same time as XSCF.</p>
Privileges	<p>You must have <code>platadm</code> or <code>fieldeng</code> privileges to run this command.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p><code>-h</code> Displays usage statement.</p>
EXTENDED DESCRIPTION	The <code>resetdateoffset(8)</code> command needs to be executed in the system power-off status.
EXAMPLES	<p>EXAMPLE 1 Resets the time subtraction between XSCF and the domain.</p> <pre>XSCF> resetdateoffset</pre>
EXIT STATUS	<p>The following exit values are returned:</p> <p>0 Successful completion.</p> <p>>0 An error occurred.</p>

resetdateoffset(8)



NAME	restoreconfig - restore the system configuration information previously saved by dumpconfig
SYNOPSIS	<p>restoreconfig [-v] [-V] [[-q] -{y n}] [-P <i>password</i>] [-s network={yes no}] [-u <i>user</i>] [-p <i>proxy</i>] [-t <i>proxy_type</i>] <i>url</i></p> <p>restoreconfig -h</p>
DESCRIPTION	<p>The restoreconfig(8) command will restore system configuration information saved using the dumpconfig(8) command.</p> <p>The command will verify the integrity of the configuration file, look for network information, and detect if the configuration file version and system class are compatible.</p>
Privileges	<p>You must have platadm privileges to run this command. Reserved user accounts default and admin can also run this command.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:</p> <ul style="list-style-type: none"> -h Displays usage statement. When used with other options or operands, an error occurs. -n Automatically answers "n" (no) to all prompts. -P <i>password</i> The password to decode an encrypted file. The command will prompt for the password if a password is not provided on command line. -p <i>proxy</i> Specifies the proxy server to be used for transfers. The default transfer type is http, unless modified using the -t <i>proxy_type</i> option. The value for proxy must be in the format <i>servername:port</i>. (Refer to Example 3.) -q Suppresses all messages to stdout, including prompts. -s network={yes no} force/prevent restoration of the network configuration. <ul style="list-style-type: none"> If network=yes, the network configuration data will be restored. If network=no, the network configuration data will not be restored. If this option is not specified, the serial number of the target system will be compared with the serial number of the configuration file and if the numbers match the configuration data will be restored.

<code>-t proxy_type</code>	Used with the <code>-p</code> option to specify the type of proxy. Possible values for <i>proxy_type</i> are: <code>http</code> , <code>socks4</code> , and <code>socks5</code> . The default value is <code>http</code> .
<code>-u user</code>	Specifies the user name when logging in to a remote ftp or http server that requires authentication. You will be prompted for a password.
<code>-v</code>	Displays verbose output. This may be helpful when diagnosing server problems.
<code>-V</code>	Displays details of network activity. This may be helpful when diagnosing network or server problems.
<code>-Y</code>	Automatically answers "y" (yes) to all prompts.

OPERANDS

The following operand is supported:

<i>url</i>	Specifies the URL of the firmware image to download. Supported formats for this value include the following: <pre>http://server[:port]/path/file</pre> <pre>https://server[:port]/path/file</pre> <pre>ftp://server[:port]/path/file</pre> <pre>file:///media/usb_msd/path/file</pre>
------------	--

EXTENDED DESCRIPTION

Basic identification information is included in plain text at the top of the configuration file. The user can use any text viewer to determine information such as:

- which system created the backup up configuration
- when the backup was created
- if the backup is encrypted

All the domains must be turned off before this command can be used. This command will download and validate the configuration file. After validation, the system will be rebooted in order to perform the restoration. After the data is restored, the system will be halted, and will need to be power-cycled to restart. Please make sure that you have the ability to power-cycle the system before initiating this command.

On an M8000/M9000 server, both XSCF units will be halted. Please check that both XSCF units are halted before performing the power cycle.

Note that the configuration data file can be restored only to the same class of server, i.e. a configuration file created by `dumpconfig(8)` on an M5000 server can be

restored to another M5000 server, but it cannot be restored to an M3000 or M8000 etc server.

EXAMPLES

EXAMPLE 1 Restoring the Configuration using FTP

```
XSCF> restoreconfig -v -u manilla 129.145.155.156:8080 ftp:/
10.7.79.18/sollgell/proxytest-ftp.cfg

transfer from '/tmp/dumpconfig.EVY1Yf' to 'ftp://10.7.79.18/sollgell/
proxytest-ftp.cfg'

Password:

* About to connect() to 129.145.155.166 port 8080
*   Trying 129.145.155.166... * connected
* Connected to 129.145.155.166 (129.145.155.166) port 8080
* Proxy auth using (nil) with user ''
* Server auth using Basic with user 'minilla'
> GET ftp://10.7.79.18/sollgell/proxytest-ftp.cfg HTTP/1.1
Authorization: Basic bHdhbmc6bHdhbmc=
User-Agent: restoreconfig
Host: 10.7.79.18:21
Pragma: no-cache
Accept: */*
< HTTP/1.1 200 OK
< Server: Sun-Java-System-Web-Proxy-Server/4.0
< Date: Thu, 07 Aug 2008 18:01:00 GMT
< Proxy-agent: Sun-Java-System-Web-Proxy-Server/4.0
< Via: 1.1 proxy-proxy
< Transfer-encoding: chunked
* Connection #0 to host 129.145.155.166 left intact
* Closing connection #0
Configuration backup created on Mon Aug  4 12:58:19 2008
  from system 'M3000' with serial number 'IKS08220xx', version '19830000'
*** You will need to power-cycle the entire system after this operation is
completed
*** Do you want to restore this configuration to your system? [y|n]: y
requesting XSCF reboot to perform restore ... requested
Connection to ghidorah.com closed by foreign host.
```

EXAMPLE 2 Restoring the Configuration Using http

```

XSCF> restoreconfig -V -p 129.145.155.166:8080 http://10.7.79.18/
sollgell/proxytest.cfg

transfer from '/scf/firmtmp/hcp/config/config_file.bin' to
'http://10.7.79.18/sollgell/proxytest.cfg'

* About to connect() to 129.145.155.166 port 8080
*   Trying 129.145.155.166... * connected
* Connected to 129.145.155.166 (129.145.155.166) port 8080
GET http://10.7.79.18/sollgell/proxytest.cfg HTTP/1.1
User-Agent: restoreconfig
Host: 10.7.79.18
Pragma: no-cache
Accept: */*

< HTTP/1.1 200 OK
< Content-length: 24603
< Content-type: text/plain
< Date: Thu, 07 Aug 2008 17:07:43 GMT
< Server: Apache/1.3.36 (Unix) mod_perl/1.2.9 mod_ssl/2.8.27 OpenSSL/0.9.7d
< Last-modified: Mon, 04 Aug 2008 20:01:51 GMT
< Etag: "4fa2a-601b-4897602f"
< Accept-ranges: bytes
< Via: 1.1 proxy-proxy
< Proxy-agent: Sun-Java-System-Web-Proxy-Server/4.0
* Connection #0 to host 129.145.155.166 left intact
* Closing connection #0

Configuration backup created on Mon Aug  4 12:58:19 2008
  from system 'M3000' with serial number 'IKS08220xx', version '19830000'
*** You will need to power-cycle the entire system after this operation is
completed
*** Do you want to restore this configuration to your system? [y|n]: y
requesting XSCF reboot to perform restore ... requested
Connection to ghidorah.com closed by foreign host.

```

EXAMPLE 3 Restoring the Configuration Using https

```

XSCF> restoreconfig -v -V https://10.7.79.18/sollgell/
proxytest.cfg

obtaining lock ... done

initiating file transfer from 'https://10.7.79.18/sollgell/proxytest.cfg'
... transfer from

'/scf/firmtmp/hcp/config/config_file.bin' to 'https://10.7.79.18/
sollgell/proxytest.cfg'

* About to connect() to 10.7.79.18 port 443
*   Trying 10.7.79.18... * connected
* Connected to 10.7.79.18 (10.7.79.18) port 443
* error setting certificate verify locations, continuing anyway:
*   CAfile: /home/ares/cross/fje/pwrqcc3/target_root/usr/share/ssl/certs/
ca-bundle.crt
*   CAspath: none
* SSL connection using EDH-RSA-DES-CBC3-SHA
* Server certificate:
*
*   subject:
/C=US/ST=California/L=SanDiego/O=toho/OU=QT/CN=10.7.79.18/
emailAddress=minilla.zilla@toho.com
*
*   start date: 2008-07-22 18:32:49 GMT
*
*   expire date: 2009-07-22 18:32:49 GMT
*
*   common name: 10.7.79.18 (matched)
*
*   issuer:
/C=US/ST=California/L=SanDiego/O=toho/OU=QT/CN=Lwang/
emailAddress=minilla.zilla@toho.com
* SSL certificate verify result: error number 1 (20), continuing anyway.
> GET /sollgell/proxytest.cfg HTTP/1.1
User-Agent: restoreconfig
Host: 10.7.79.18
Pragma: no-cache
Accept: */*
< HTTP/1.1 200 OK
< Date: Tue, 12 Aug 2008 22:02:12 GMT
< Server: Apache/1.3.36 (Unix) mod_perl/1.29 mod_ssl/2.8.27 OpenSSL/0.9.7d
< Last-Modified: Mon, 04 Aug 2008 20:01:51 GMT

```

```

< ETag: "4fa2a-601b-4897602f"
< Accept-Ranges: bytes
< Content-Length: 24603
< Content-Type: text/plain
* Connection #0 to host 10.7.79.18 left intact
* Closing connection #0

done
file decoding done.

Configuration backup created on Mon Aug  4 12:58:19 2008

  from system 'M3000' with serial number 'IKS08220xx', version '19830000'
validating backup configuration data

*** You will need to power-cycle the entire system after this operation is
completed

*** Do you want to restore this configuration to your system? [y|n]: y
requesting XSCF reboot to perform restore ... requested

Connection to ghidorah.com closed by foreign host.

```

EXAMPLE 4 Restoring the Configuration Using USB

```

XSCF> restoreconfig -V -p 129.145.155.166:8080 file:///media/
usb_msd/proxytest.cfg

transfer from '/scf/firmtmp/hcp/config/config_file.bin' to 'file:///media/
usb_msd/proxytest.cfg'

Configuration backup created on Mon Aug  4 14:38:27 2008

  from system 'M3000' with serial number 'IKS08220xx', version '19830000'

*** You will need to power-cycle the entire system after this operation is
completed

*** Do you want to restore this configuration to your system? [y|n]: y
requesting XSCF reboot to perform restore ... requested

Connection to ghidorah.com closed by foreign host.

```

EXAMPLE 5 Restoring An Encrypted Configuration

```

XSCF> restoreconfig -v -V -P encryption http://10.7.79.18/sollgell/
proxytest.cfg

obtaining lock ... done

initiating file transfer from 'http://10.7.79.18/sollgell/proxytest.cfg'

```

```
... transfer from '/scf/firmtmp/hcp/config/config_file.bin' to
'http://10.7.79.18/sollgell/proxytest.cfg'
* About to connect() to 10.7.79.18 port 80
*   Trying 10.7.79.18... * connected
* Connected to 10.7.79.18 (10.7.79.18) port 80
GET /sollgell/proxytest.cfg HTTP/1.1
User-Agent: restoreconfig
Host: 10.7.79.18
Pragma: no-cache
Accept: */*
< HTTP/1.1 200 OK
< Date: Wed, 13 Aug 2008 23:29:42 GMT
< Server: Apache/1.3.36 (Unix) mod_perl/1.29 mod_ssl/2.8.27
OpenSSL/0.9.7d
< Last-Modified: Wed, 13 Aug 2008 23:25:16 GMT
< ETag: "4fa55-501b-48a36d5c"
< Accept-Ranges: bytes
< Content-Length: 20507
< Content-Type: text/plain
* Connection #0 to host 10.7.79.18 left intact
* Closing connection #0
done
file decoding done.
Configuration backup created on Wed Aug 13 16:21:01 2008
  from system 'M3000' with serial number 'IKS08220xx', version
'19830000'
validating backup configuration data
File decryption completed
*** You will need to power-cycle the entire system after this operation
is completed
*** Do you want to restore this configuration to your system? [y|n]: y
requesting XSCF reboot to perform restore ... requested
Connection to ghidorah.com closed by foreign host.
```

restoreconfig(8)

EXIT STATUS

The following exit values are returned:

- | | |
|----|------------------------|
| 0 | Successful completion. |
| >0 | An error occurred. |

NAME	restoredefaults - delete the setting and the log information that stored in the server or the XSCF unit, and restore it to the state as of the factory shipment						
SYNOPSIS	<p>restoredefaults -c <i>range</i></p> <p>restoredefaults -h</p>						
DESCRIPTION	<p>The <code>restoredefaults(8)</code> command deletes the setting and the log information that stored in the server or the XSCF unit, and restores it to the state as of the factory shipment.</p> <p>As the range of restoration, one of the following can be specified:</p> <p>XSCF unit (<i>xscfu</i>)</p> <p>Restores the following information in XSCF unit to the state as of the factory shipment:</p> <ul style="list-style-type: none"> ■ Various setting information in XSCF ■ Log information that stored in XSCF unit ■ Backup information of operator panel <p>server (<i>factory</i>)</p> <p>Restores the setting and the log information that stored in operator panel and XSCF unit to the state as of the factory shipment.</p>						
Privileges	<p>You must have <code>plataadm</code> privileges to run this command.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>						
OPTIONS	<p>The following option is supported:</p> <table border="0" style="width: 100%;"> <tr> <td style="vertical-align: top; padding-right: 20px;"><code>-c <i>range</i></code></td> <td>Specifies the target of restoration. In <i>range</i>, one of the following values can be specified:</td> </tr> <tr> <td style="padding-left: 40px;"><code>xscfu</code></td> <td>Restores the XSCF unit.</td> </tr> <tr> <td style="padding-left: 40px;"><code>factory</code></td> <td>Restores the server.</td> </tr> </table> <p><code>-h</code> Displays usage statement. When used with other options or operands, an error occurs.</p>	<code>-c <i>range</i></code>	Specifies the target of restoration. In <i>range</i> , one of the following values can be specified:	<code>xscfu</code>	Restores the XSCF unit.	<code>factory</code>	Restores the server.
<code>-c <i>range</i></code>	Specifies the target of restoration. In <i>range</i> , one of the following values can be specified:						
<code>xscfu</code>	Restores the XSCF unit.						
<code>factory</code>	Restores the server.						
EXTENDED DESCRIPTION	<p>In case the <code>restoredefaults(8)</code> command executed to the standby XSCF,</p> <ul style="list-style-type: none"> ■ when you specify <code>factory</code>, it results in an error; ■ when you specify <code>xscfu</code>, only the standby XSCF will be initialized. 						

EXAMPLES

EXAMPLE 1 Restores the XSCF unit to the state as of the factory shipment.

```
XSCF> restoredefaults -c xscfu
```

WARNING:

If this system does not have OPNL, this command will set all the user settable XSCF configuration parameters to their default value as they were set when the system was shipped out.

Furthermore, this command will delete all logs on both XSCFUs. Check the man page of this command before you run it.

Continue?[yes/no](default no):**yes**

You must check the following points.

1. Have the ability to powercycle the system.
2. Have access to the serial console and hold the serial console of the XSCFU to confirm the completion of the command.

If you answer "yes" this command will HALT the XSCFU when it completes. You will need to powercycle the system after the XSCF BOOT STOP.

Do you really want to continue?

Continue?[yes/no](default no):**yes**

The initialization of XSCFU will be started.

XSCFU : all data clear

OPNL : not clear

XSCF will be automatically rebooted. Afterwards, XSCFU will be initialized.

Continue?[yes/no](default no):**yes**

The NVRAM setting of XSCFU#0 was completed.

XSCF shutdown request was completed.

<snip>...XSCF reboot..<snip>

***** WARNING *****

XSCF initialization terminate for XSCF data clear.

execute "setdefaults xscf" (AUTO)

setdefaults : XSCF clear : start

setdefaults : XSCF clear : DBS start

setdefaults : XSCF clear : wait 20s for DBS initialization

setdefaults : XSCF clear : common database clear complete

setdefaults : XSCF clear : /bin/rm /var/log/lastlog >/dev/null 2>&1

setdefaults : XSCF clear : /bin/rm /var/log/boot.log >/dev/null 2>&1

...

setdefaults : XSCF clear : /bin/rm /hcpcommon/tmp/panel_up_to_date_fail >/dev/null 2>&1

setdefaults : XSCF clear : log data clear complete

setdefaults : XSCF clear : NVRAM(PAGE#0) clear complete

...

setdefaults : XSCF clear : NVRAM(PAGE#7) clear complete

setdefaults : XSCF clear : NVRAM reset complete

...

```

setdefaults : XSCF clear : unmount filesystem start
dbs[282]: NOTICE: received signal: 15
setdefaults : XSCF clear : unmount /hcp0/linux
...
setdefaults : XSCF clear : unmount /hcpcommon/firmtmp -- complete
setdefaults : XSCF clear : unmount filesystem complete
setdefaults : XSCF clear : end
setdefaults : complete

```

Please turn off the breaker after XSCF halt.

```

The system is going down NOW !!
Please stand by while rebooting the system.
Restarting system.
XSCF uboot 01950000 (Apr 15 2007 - 11:08:18)

```

```

XSCF uboot 01950000 (Apr 15 2007 - 11:08:18)

```

```

SCF board boot factor = a040
DDR Real size: 512 MB
DDR: 480 MB

```

```

XSCF BOOT STOP (recover by NFB-OFF/ON)

```

EXAMPLE 2 Restores the server to the state as of the factory shipment.

```

XSCF> restoreddefaults -c factory

```

WARNING:

If this system does not have OPNL, this command will set all the user settable XSCF configuration parameters to their default value as they were set when the system was shipped out. Furthermore, this command will delete all logs on both XSCFUs. Check the man page of this command before you run it.

```

Continue?[yes/no] (default no):yes
You must check the following points.

```

1. Have the ability to powercycle the system.
2. Have access to the serial console and hold the serial console of the XSCFU to confirm the completion of the command.

If you answer "yes" this command will HALT the XSCFU when it completes. You will need to powercycle the system after the XSCF BOOT STOP.

```

Do you really want to continue?

```

```

Continue?[yes/no] (default no):yes
The initialization of XSCFU will be started.
XSCFU : all data clear
OPNL  : all data clear (exclude SYSTEM ID data)

```

```

XSCF will be automatically rebooted. Afterwards, XSCFU will be
initialized.
Continue?[yes/no] (default no):yes
The NVRAM setting of XSCFU#0 was completed.
XSCF shutdown request was completed.

    <snip>....XSCF reboot..<snip>

***** WARNING *****
XSCF initialization terminate for XSCF/OPNL data clear.
execute "setdefaults factory" (AUTO)

setdefaults : FACTORY mode clear : start
setdefaults : FACTORY mode clear : DBS start
setdefaults : FACTORY mode clear : wait 20s for DBS initialization
initialize OPNL SEEPR0M 1/6 -- complete
...
initialize OPNL SEEPR0M 6/6 -- complete
setdefaults : FACTORY mode clear : OPNL reset complete
setdefaults : FACTORY mode clear : restore SYSTEM-ID data complete
setdefaults : FACTORY mode clear : /bin/rm /var/log/lastlog >/dev/null
2>&l
setdefaults : FACTORY mode clear : /bin/rm /var/log/boot.log >/dev/null
2>&l
...
setdefaults : FACTORY mode clear : /bin/rm /hcpcommon/tmp/
panel_up_to_date_fail >/dev...
setdefaults : FACTORY mode clear : log data clear complete
setdefaults : FACTORY mode clear : NVRAM(PAGE#0) clear complete
...
setdefaults : FACTORY mode clear : NVRAM(PAGE#7) clear complete
setdefaults : FACTORY mode clear : NVRAM reset complete
...
setdefaults : FACTORY mode clear : unmount filesystem start
dbs[283]: NOTICE: received signal: 15
setdefaults : FACTORY mode clear : unmount /hcp0/linux
...
setdefaults : FACTORY mode clear : unmount /hcpcommon/firmtmp -- complete
setdefaults : FACTORY mode clear : unmount filesystem complete
Please stand by while rebooting the system.
Restarting system.
XSCF uboot 01950000 (Apr 15 2007 - 11:08:18)

XSCF uboot 01950000 (Apr 15 2007 - 11:08:18)

SCF board boot factor = 4040
DDR Real size: 512 MB
DDR: 480 MB

XSCF BOOT STOP (recover by NFB-OFF/ON)

```

EXIT STATUS | The following exit values are returned:

0	Successful completion.
>0	An error occurred.

restoredefaults(8)



NAME	sendbreak - send a break signal to the specified domain										
SYNOPSIS	<p>sendbreak -d <i>domain_id</i></p> <p>sendbreak [[-q] [-y n]] -d <i>domain_id</i></p> <p>sendbreak -h</p>										
DESCRIPTION	<p>The sendbreak(8) command sends a break signal to the specified domain.</p> <p>When a break signal is sent from the domain console to the Solaris OS of the domain, control is transferred from the Solaris OS to OpenBoot PROM and the OpenBoot PROM prompt "ok>" is displayed.</p> <p>Note – sendbreak(8) command will not work when the secure mode is set to 'on' while the mode switch on the operator panel is set to "Locked". Refer to the setdomainmode(8) for more information.</p>										
Privileges	<p>You must have one of the following privileges to run this command:</p> <table border="0"> <tr> <td style="padding-right: 20px;">platadm</td> <td>Can run this command for all domains.</td> </tr> <tr> <td>domainadm</td> <td>Can run this command only for your managed domains.</td> </tr> </table> <p>Refer to setprivileges(8) for more information.</p>	platadm	Can run this command for all domains.	domainadm	Can run this command only for your managed domains.						
platadm	Can run this command for all domains.										
domainadm	Can run this command only for your managed domains.										
OPTIONS	<p>The following options are supported:</p> <table border="0"> <tr> <td style="padding-right: 20px;">-d <i>domain_id</i></td> <td>Specifies only one ID of the domain to which to send the break signal. <i>domain_id</i> can be 0–23 depending on the system configuration.</td> </tr> <tr> <td>-h</td> <td>Displays usage statement. When used with other options or operands, an error occurs.</td> </tr> <tr> <td>-n</td> <td>Automatically answers "n" (no) to all prompts.</td> </tr> <tr> <td>-q</td> <td>Suppresses all messages to stdout, including prompts.</td> </tr> <tr> <td>-y</td> <td>Automatically answers "y" (yes) to all prompts.</td> </tr> </table>	-d <i>domain_id</i>	Specifies only one ID of the domain to which to send the break signal. <i>domain_id</i> can be 0–23 depending on the system configuration.	-h	Displays usage statement. When used with other options or operands, an error occurs.	-n	Automatically answers "n" (no) to all prompts.	-q	Suppresses all messages to stdout, including prompts.	-y	Automatically answers "y" (yes) to all prompts.
-d <i>domain_id</i>	Specifies only one ID of the domain to which to send the break signal. <i>domain_id</i> can be 0–23 depending on the system configuration.										
-h	Displays usage statement. When used with other options or operands, an error occurs.										
-n	Automatically answers "n" (no) to all prompts.										
-q	Suppresses all messages to stdout, including prompts.										
-y	Automatically answers "y" (yes) to all prompts.										
EXIT STATUS	<p>The following exit values are returned:</p> <table border="0"> <tr> <td style="padding-right: 20px;">0</td> <td>Successful completion.</td> </tr> <tr> <td>>0</td> <td>An error occurred.</td> </tr> </table>	0	Successful completion.	>0	An error occurred.						
0	Successful completion.										
>0	An error occurred.										
SEE ALSO	console (8), showconsolepath (8)										

sendbreak(8)



NAME	setaltitude - set the altitude of the system or whether or not the air filter installed								
SYNOPSIS	<p>setaltitude -s <i>key=value</i></p> <p>setaltitude -h</p>								
DESCRIPTION	<p>The <code>setaltitude(8)</code> command sets the altitude of the system or whether or not the air filter installed.</p> <p>Whether or not the air filter installed can be specified on the M4000/M5000 servers only.</p>								
Privileges	<p>You must have <code>platadm</code> or <code>fieldeng</code> privileges to run this command.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>								
OPTIONS	<p>The following options are supported:</p> <p>-h Displays usage statement. When used with other options or operands, an error occurs.</p> <p>-s <i>key=value</i> The item to be set is specified by <i>key</i>. The following value can be specified:</p> <table border="0" style="margin-left: 40px;"> <tr> <td style="padding-right: 20px;"><code>altitude</code></td> <td>Sets the altitude of the system.</td> </tr> <tr> <td style="padding-right: 20px;"><code>filter</code></td> <td>Sets whether or not to install the air filter. You can specify this on the M4000/M5000 servers only.</td> </tr> </table> <p>When you specified <code>altitude</code> as <i>key</i>, specify the altitude of the system in <i>value</i> in units of meters (m). An integer equal to or greater than 0 can be specified, and the specified value is rounded up to the nearest hundred meters. The default value is 0 meters.</p> <p>When you specified <code>filter</code> as <i>key</i>, either of the following can be specified for value:</p> <table border="0" style="margin-left: 40px;"> <tr> <td style="padding-right: 20px;"><code>installed</code></td> <td>Air filter is installed.</td> </tr> <tr> <td style="padding-right: 20px;"><code>uninstalled</code></td> <td>Air filter is not installed.</td> </tr> </table>	<code>altitude</code>	Sets the altitude of the system.	<code>filter</code>	Sets whether or not to install the air filter. You can specify this on the M4000/M5000 servers only.	<code>installed</code>	Air filter is installed.	<code>uninstalled</code>	Air filter is not installed.
<code>altitude</code>	Sets the altitude of the system.								
<code>filter</code>	Sets whether or not to install the air filter. You can specify this on the M4000/M5000 servers only.								
<code>installed</code>	Air filter is installed.								
<code>uninstalled</code>	Air filter is not installed.								
EXTENDED DESCRIPTION	<ul style="list-style-type: none"> ■ If the altitude of the system is set, any abnormality in the intake air temperature can be detected quickly. If the altitude of the system is unknown, set a high value. However, even if no altitude is set for the system, any abnormality in temperatures such as the CPU temperature can still be detected, so the system would not be damaged by a fatal error. 								

- To apply the specified configuration, execute the `rebootxscf(8)` command and reset XSCF.
- The command does not accept negative numbers. If the system is below sea-level use `altitude=0`.
- When you specified either of the altitude of the system or whether or not the air filter installed, the current settings are listed. The setting of the air filter is displayed only when it is set to installed.
- When the `showaltitude(8)` command is executed, the current settings are displayed.

EXAMPLES

EXAMPLE 1 Sets the altitude of the system to 1000 m.

```
XSCF> setaltitude -s altitude=1000
1000m
```

EXAMPLE 2 Sets the altitude of the system to 200 m. The specified value is rounded up to the nearest hundred meters.

```
XSCF> setaltitude -s altitude=157
200m
```

EXAMPLE 3 Sets the altitude of the system to 1000 m, on the M4000/M5000 servers with the air filter installed.

```
XSCF> setaltitude -s altitude=1000
1000m
Filter is installed.
```

EXAMPLE 4 Sets the air filter uninstalled, on the M4000/M5000 servers.

```
XSCF> setaltitude -s filter=uninstalled
1000m
```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

`showaltitude(8)`

NAME	setarchiving - configure the log archiving functionality
SYNOPSIS	<p>setarchiving [-k <i>host-key</i>] [-l <i>audit-limit, non-audit-limit</i>] [-p <i>password</i> -r] [-t <i>user@host:directory</i>] [-v] [-y -n]</p> <p>setarchiving enable disable</p> <p>setarchiving -h</p>
DESCRIPTION	<p>setarchiving(8) manages the log archiving configuration. Persistent storage space on the Service Processor is limited. Some logs may grow to the point where old log entries must be overwritten or deleted. Log archiving allows the user to set up the Service Processor to automatically archive its log data on a remote host.</p> <p>Note – You must set up the archive host correctly prior to enabling the log archiving feature. (See EXAMPLE 1.) If you attempt to enable archiving while the configuration is invalid (for example, if the specified archive host does not exist), setarchiving exits with an error message. setarchiving exits with an error message if you request invalid configuration changes while archiving is enabled.</p> <p>Note – setarchiving(8) requires at least one option or operand.</p>
Privileges	<p>You must have platadm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>

OPTIONS

The following options are supported:

- h** Displays usage statement.
- When used with other options or operands, an error occurs.
- k *host-key*** Sets the public key that XSCF uses to verify the identity of the host. Possible values for the *host-key* are shown here:
- none**
- This literal value specifies that a public key should not be used to authenticate the archive host. If an archive host public key was previously configured, it is deleted.
- download**
- This literal value specifies that `setarchiving` should download the public host key from the archive host using the SSH protocol. If the `-t` option is used, `setarchiving` downloads the key from the host specified in the argument to `-t`. Otherwise, `setarchiving` downloads the key from the current archive host. Next, `setarchiving` displays the key's md5 fingerprint and prompts you for confirmation of the identity of the host to continue. If you accept the key, it is saved and used for server authentication. If you reject the key, `setarchiving` exits without changing the configuration.
- public-key***
- The specified public key is stored and used for server authentication. The *host-key* argument should be the complete *public-key* for the archive host, beginning with the key type.
- Note** – The *public-key* should be enclosed in quotes to ensure that the shell treats it as a single word.

- `-l audit-limit,non-audit-limit` Sets the space limits for log archives in megabytes. The option argument must consist of two values separated by a comma.
- The *audit-limit* value specifies the archive space limit for audit logs. It must be either 0 (zero), `unlimited` or an integer in the range of 500–50000. If you do not use the `-l` option to modify the value of *audit-limit*, the initial archive space limit for audit logs is unlimited.
- The *non-audit-limit* value specifies the archive space limit for all other logs, in megabytes. It must be an integer in the range of 500–50000. If unset, the initial value for *non-audit-limit* depends on the type of server. Use the `showarchiving(8)` command to determine the value for your server.
- If either of the specified values is invalid, the command displays an error and exits without making any changes.
- `-n` Automatically answers "n" (no) to all prompts. Prompts are displayed.
- `-p password` Sets the password used for `ssh` login. This option is provided to facilitate scripting. To change the password interactively, use the `-r` option.
- `-r` Reads the password used for `ssh` login. The `setarchiving` command displays a prompt and reads the new password without echoing it to the screen.
- `-t user@host:directory` Sets the archive target. The *host* field specifies the host name or IP address of the archive host. The *user* field specifies the user name for the `ssh` login to the archive host. The *directory* field specifies the archive directory on the archive host where the archives should be stored. The directory field must not begin with a "~".
- `-v` Specifies verbose output. When this option is used in conjunction with `-k download`, `setarchiving` displays the downloaded public key in addition to its md5 fingerprint.
- `-y` Automatically answers "y" (yes) to all prompts. Prompts are displayed.

OPERANDS

The following operands are supported:

- enable** Activates the log archiving feature. Cannot be used with any options.
- disable** De-activates the log archiving feature. Cannot be used with any options.

EXAMPLES**EXAMPLE 1** Setting the Archiving Target and Password

```
XSCF> setarchiving -t jsmith@somehost.company.com:/home/jsmith/  
logs -r
```

```
Enter ssh password for jsmith@somehost.company.com: []
```

EXAMPLE 2 Setting the Public Host Key

```
XSCF> setarchiving -k download
```

```
Downloading public host key from somehost.company.com...
```

```
Fingerprint: c3:75:f9:97:7d:dc:1e:1e:62:06:c1:6f:87:bc:e8:0d
```

```
Accept this public key (yes|no): yes
```

EXAMPLE 3 Setting the Space Limits for Archives

```
XSCF> setarchiving -l 10000,10000
```

EXAMPLE 4 Enabling Archiving

```
XSCF> setarchiving enable
```

```
Testing the archiving configuration...
```

```
Logs will be archived to somehost.company.com.
```

EXIT STATUS

The following exit values are returned:

- 0 Successful completion. Configuration updated.
- >0 An error occurred.

SEE ALSO

showarchiving (8)

NAME	setaudit - manage the system auditing functionality
SYNOPSIS	<p>setaudit enable disable archive delete</p> <p>setaudit [-p count suspend] [-m mailaddr] [-a users=enable disable default] [-c classes= {enable disable }]... [-e events=enable disable]... [-g {enable disable }] [-t percents]</p> <p>setaudit -h</p>
DESCRIPTION	<p>setaudit(8) manages the collection of data on the use of system resources. Audit data provides a record of security-related system events. This data can be used to assign responsibility for actions that have taken place on the system. Auditing generates records when specified events occur. Events that generate audit records include:</p> <ul style="list-style-type: none"> ■ System startup and shutdown ■ Login and logout ■ Authentication actions ■ Administrative actions
Privileges	<p>You must have auditadm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p>-a users=enable disable default</p> <p>Sets the audit record generation policy for the specified users. <i>users</i> is a comma-separated list of valid user names.</p> <p>When set to <i>enable</i> or <i>disable</i>, audit record generation for the users is turned on or off respectively. This setting overrides the global policy for the specified user.</p> <p>When set to <i>default</i>, the policy for the users is set to follow the global policy. Use <code>showaudit -g</code> to display the global user audit record generation policy.</p> <p>-c classes=enable disable</p> <p>Changes the audit record generation policy for the specified audit classes. <i>classes</i> is a comma-separated list of audit classes. A class may be specified by its numeric value or its name. The <code>ACS_</code> prefix may be omitted. For example, the class of audit-related events can be expressed as <code>ACS_AUDIT</code>, <code>AUDIT</code> or <code>16</code>.</p>

The following are valid classes:

<code>all</code>	Denotes all classes.
<code>ACS_SYSTEM(1)</code>	System-related events
<code>ACS_WRITE(2)</code>	Commands that can modify a state
<code>ACS_READ(4)</code>	Commands that read a current state
<code>ACS_LOGIN(8)</code>	Login-related events
<code>ACS_AUDIT(16)</code>	Audit-related events
<code>ACS_DOMAIN(32)</code>	Domain management-related events
<code>ACS_USER(64)</code>	User management-related events
<code>ACS_PLATFORM(128)</code>	Platform management-related events
<code>ACS_MODES(256)</code>	Mode-related events

This option may be specified multiple times. Multiple specification are processed together with an `-e` options in the order listed. See EXAMPLE 1.

When set to `enable` or `disable`, audit record generation for the classes is turned on or off respectively. This setting overrides the global policy. When set to `default`, the policy for the users is set to follow the global policy. Use `showaudit -g` to display the global user audit record generation policy.

`-e events=enable|disable`

Changes the audit record generation policy for the specified audit events. *events* is a comma-separated list of audit events. An event may be specified by its numeric value or its name. The `AEV_` prefix may be omitted. For example, the event for SSH login can be expressed as `AEV_LOGIN_SSH`, `LOGIN_SSH` or `0`.

See `showaudit -e all` for a list of valid events.

This option may be specified multiple times. Multiple specification are processed together with an `-c` options in the order listed. See EXAMPLE 3.

When set to `enable` or `disable`, audit record generation for the events is turned on or off respectively. This setting overrides the global policy. When set to `default`, the policy for the users is set to follow the global policy. Use `showaudit -g` to display the global user audit record generation policy.

`-g enable|disable`

Sets the global user audit record generation policy.

When set to `disable`, no audit record which can be attributed to any user account is generated. These settings can be overridden on an individual user basis using the `-a` option.

`-h`

Displays usage statement.

When used with other options or operands, an error occurs.

`-m mailaddr`

Sets the mail address to which email is sent when the local audit storage space usage reaches a threshold (see option `-t`). Email addresses must be a valid email address of the form `user@company.com`. Specifying `none` for `mailaddr` turns off email notification.

`-p suspend|count`

Sets the policy to follow when the audit trail becomes full. The following are valid values:

<code>suspend</code>	All processes which try to write to audit records will be suspended until either space becomes available and records can be written, or the policy is changed to <code>count</code> .
<code>count</code>	New audit records are dropped and a count is kept of how many records are dropped.

`-t percents`

Sets thresholds at which to issue a warning about local audit storage usage. `percents` is a comma-separated list of percentages of available space used. At most four values may be set. For example, values of 50, 75, 80, 90 would cause warnings to be issued when 50%, 75%, 80% and 90% respectively, of the available storage for audit records is consumed. The default value is 80%.

Warnings are issued as a message to the console and optionally to an administrator using email. See `-m mailaddr`.

OPERANDS

The following operands are supported:

archive	Notifies the log archiving facility to archive the current audit trail.
delete	Delete the portion of the local audit trail in the secondary partition. This can be used to free space for new audit records if the local audit trail becomes full. For more information on the secondary partition, refer to the <i>Administration Guide</i> for your server.
disable	Turns off the writing of audit records to the audit trail and notifies the log archiving facility to archive the current audit trail.
enable	Turns on the writing of audit records to the audit trail.

EXAMPLES**EXAMPLE 1** Changing Classes Using Names

```
XSCF> setaudit -c LOGIN,AUDIT=disable -c ACS_READ=enable
```

Auditing for LOGIN and AUDIT classes has been disabled. Auditing for READ class is enabled.

EXAMPLE 2 Changing Classes Using Numbers

```
XSCF> setaudit -c 8,16=disable -c 1=enable
```

Auditing for classes 8 (LOGIN) and 16 (AUDIT) has been disabled. Auditing for class 1 (SYSTEM) is enabled.

EXAMPLE 3 Changing Classes and Enabling an Event

```
XSCF> setaudit -c 1=enable -e 64=disable
```

Auditing is enabled for all of Class 1 (SYSTEM) except for event 64 (USER) is disabled.

EXAMPLE 4 Enabling Auditing

```
XSCF> setaudit enable
```

Turns on writing of the audit records for the audit trail.

EXAMPLE 5 Enabling Warnings

```
XSCF> setaudit -t 50,75
```

Warnings will be sent at 50% capacity and 75% capacity.

EXIT STATUS The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO `showaudit(8)`

setaudit(8)



NAME	setautologout - set the session timeout time of the XSCF shell				
SYNOPSIS	setautologout -s <i>timeout</i> setautologout -h				
DESCRIPTION	The <code>setautologout(8)</code> command sets the session timeout time of the XSCF shell. The default of the session timeout time is 10 minutes.				
Privileges	You must have <code>platadm</code> or <code>fieldeng</code> privileges to run this command. Refer to <code>setprivileges(8)</code> for more information.				
OPTIONS	The following options are supported: <table border="0"> <tr> <td style="padding-right: 20px;">-h</td> <td>Displays usage statement. When used with other options or operands, an error occurs.</td> </tr> <tr> <td style="padding-right: 20px;">-s <i>timeout</i></td> <td>Specifies the session timeout time of the XSCF shell. Specify a timeout time value in units of minutes for <i>timeout</i>. An integer ranging from 1 to 255 can be specified.</td> </tr> </table>	-h	Displays usage statement. When used with other options or operands, an error occurs.	-s <i>timeout</i>	Specifies the session timeout time of the XSCF shell. Specify a timeout time value in units of minutes for <i>timeout</i> . An integer ranging from 1 to 255 can be specified.
-h	Displays usage statement. When used with other options or operands, an error occurs.				
-s <i>timeout</i>	Specifies the session timeout time of the XSCF shell. Specify a timeout time value in units of minutes for <i>timeout</i> . An integer ranging from 1 to 255 can be specified.				
EXTENDED DESCRIPTION	The specified session timeout time becomes effective after the subsequent login.				
EXAMPLES	EXAMPLE 1 Sets the session timeout time of the XSCF shell to 30 minutes. <pre>XSCF> setautologout -s 30 30min</pre>				
EXIT STATUS	The following exit values are returned: <table border="0"> <tr> <td style="padding-right: 20px;">0</td> <td>Successful completion.</td> </tr> <tr> <td style="padding-right: 20px;">>0</td> <td>An error occurred.</td> </tr> </table>	0	Successful completion.	>0	An error occurred.
0	Successful completion.				
>0	An error occurred.				
SEE ALSO	showautologout (8)				

setautologout(8)



NAME	setcod - set up the Capacity on Demand (COD) resources used for domains														
SYNOPSIS	<pre> setcod setcod [-v] setcod [[-q] -{y n}] [-v] <i>headroom</i> setcod [-v] -d <i>domain_id</i> [<i>proc-rtus</i>] setcod -h </pre>														
DESCRIPTION	<p>setcod(8) sets up the COD resources to be used for domains. License keys must be installed (see addcodlicense(8)) before COD boards in a domain can be utilized. You can also enable headroom and reserve licenses for some domains with setcod(8).</p> <p>The setcod(8) command is not available on the M3000 server.</p> <p>When no <i>domain_id</i> is specified, current values are displayed in the square brackets ([]) at the command prompt. If no value is specified for an operand, it retains its current value.</p>														
Privileges	<p>You must have platadm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>														
OPTIONS	<p>The following options are supported:</p> <table border="0"> <tr> <td style="padding-right: 20px;">-d <i>domain_id</i></td> <td>Domain identifier. <i>domain_id</i> can be 0–23 depending on the system configuration.</td> </tr> <tr> <td style="padding-right: 20px;">-h</td> <td>Displays usage statement.</td> </tr> <tr> <td></td> <td>When used with other options or operands, an error occurs.</td> </tr> <tr> <td style="padding-right: 20px;">-n</td> <td>Automatically answers "n" (no) to all prompts.</td> </tr> <tr> <td style="padding-right: 20px;">-q</td> <td>Suppresses all messages to stdout, including prompts.</td> </tr> <tr> <td style="padding-right: 20px;">-v</td> <td>Specifies verbose output.</td> </tr> <tr> <td style="padding-right: 20px;">-y</td> <td>Automatically answers "y" (yes) to all prompts.</td> </tr> </table>	-d <i>domain_id</i>	Domain identifier. <i>domain_id</i> can be 0–23 depending on the system configuration.	-h	Displays usage statement.		When used with other options or operands, an error occurs.	-n	Automatically answers "n" (no) to all prompts.	-q	Suppresses all messages to stdout, including prompts.	-v	Specifies verbose output.	-y	Automatically answers "y" (yes) to all prompts.
-d <i>domain_id</i>	Domain identifier. <i>domain_id</i> can be 0–23 depending on the system configuration.														
-h	Displays usage statement.														
	When used with other options or operands, an error occurs.														
-n	Automatically answers "n" (no) to all prompts.														
-q	Suppresses all messages to stdout, including prompts.														
-v	Specifies verbose output.														
-y	Automatically answers "y" (yes) to all prompts.														

OPERANDS

The following operands are supported:

<i>headroom</i>	Amount of headroom (processors) to be enabled. Maximum value is 4.
<i>proc-rtus</i>	The number of Right To Use (RTUs) licenses reserved for a domain. One RTU license is required for each CPU.

EXTENDED DESCRIPTION

If you run the `setcod` command without specifying any options, the command prompts you for COD information.

You are asked to specify the amount of COD headroom to be used, and the number of COD RTU licenses to be reserved for your domains. When you are prompted for COD information, the maximum values allowed are displayed within parentheses () and default values are displayed within brackets [].

`setcod` enables COD headroom (processors to be used on demand). Use the `-d domain_id` to specify the number of domain COD RTU licenses to be reserved.

EXAMPLES

EXAMPLE 1 Setting COD CPU Headroom Quantity and Reserve Domain COD RTU Licenses

```
XSCF> setcod
```

```
PROC RTUs installed: 0
```

```
PROC Headroom Quantity (0 to disable, 4 MAX) [0]: 1
```

```
WARNING:Using headroom requires you to install license key(s) within 30 days. Do you agree? [y|n]: y
```

```
PROC RTUs reserved for domain 0 (1 MAX) [0]:
```

```
PROC RTUs reserved for domain 1 (0 MAX) [0]:
```

```
PROC RTUs reserved for domain 2 (0 MAX) [0]:
```

```
PROC RTUs reserved for domain 3 (0 MAX) [0]:
```

```
PROC RTUs reserved for domain 4 (0 MAX) [0]:
```

```
PROC RTUs reserved for domain 5 (0 MAX) [0]:
```

```
PROC RTUs reserved for domain 6 (0 MAX) [0]:
```

```
PROC RTUs reserved for domain 7 (0 MAX) [0]:
```

```
PROC RTUs reserved for domain 8 (0 MAX) [0]:
```

```
PROC RTUs reserved for domain 9 (0 MAX) [0]:
```

```
PROC RTUs reserved for domain 10 (0 MAX) [0]:
```

```
PROC RTUs reserved for domain 11 (0 MAX) [0]:
```

```
PROC RTUs reserved for domain 12 (0 MAX) [0]:
```



```
PROC RTUs reserved for domain 13 (0 MAX) [0]:  
PROC RTUs reserved for domain 14 (0 MAX) [0]:  
PROC RTUs reserved for domain 15 (0 MAX) [0]:
```

After this command completes, you will see a message similar to this one in the XSCF console:

```
Aug 28 17:28:30 FF1-1-0 codd[PID]: COD PROC Headroom changed to 3
```

EXAMPLE 2 Set the COD Headroom CPUs to 0

```
XSCF> setcod 0
```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

addcodlicense(8), **showcod**(8)

setcod(8)



NAME	setdate - set the date and time of XSCF																
SYNOPSIS	setdate [[-q] [-y n]] [-u] -s <i>date</i> setdate -h																
DESCRIPTION	The <code>setdate(8)</code> command sets the date and time of XSCF. If the local date and time are specified, they are set following conversion to coordinated universal time (UTC). After the command executed, XSCF will be reset automatically.																
Privileges	You must have <code>platadm</code> or <code>fieldeng</code> privileges to run this command. Refer to <code>setprivileges(8)</code> for more information.																
OPTIONS	The following options are supported: <table border="0" style="width: 100%;"> <tr> <td style="vertical-align: top; padding-right: 20px;">-h</td> <td>Displays usage statement. When used with other options or operands, an error occurs.</td> </tr> <tr> <td style="vertical-align: top; padding-right: 20px;">-n</td> <td>Automatically answers "n" (no) to all prompts.</td> </tr> <tr> <td style="vertical-align: top; padding-right: 20px;">-q</td> <td>Suppresses all messages to stdout, including prompts.</td> </tr> <tr> <td style="vertical-align: top; padding-right: 20px;">-s <i>date</i></td> <td>Sets date and time. <i>date</i> can be specified in either of the following formats: <table border="0" style="width: 100%;"> <tr> <td style="vertical-align: top; padding-right: 20px;"><i>YYYY.MM.DD-hh:mm:ss</i></td> <td>Specifies date in the format of "<i>year.month.day-hour:minute:second.</i>"</td> </tr> <tr> <td style="vertical-align: top; padding-right: 20px;"><i>MMDDhhmmYYYY.ss</i></td> <td>Specifies data in the format "<i>MonthDayHourMinuteYear.second.</i>"</td> </tr> </table> </td> </tr> <tr> <td style="vertical-align: top; padding-right: 20px;">-u</td> <td>Specifies time in UTC. When omitted, the local time is specified.</td> </tr> <tr> <td style="vertical-align: top; padding-right: 20px;">-y</td> <td>Automatically answers "y" (yes) to all prompts.</td> </tr> </table>	-h	Displays usage statement. When used with other options or operands, an error occurs.	-n	Automatically answers "n" (no) to all prompts.	-q	Suppresses all messages to stdout, including prompts.	-s <i>date</i>	Sets date and time. <i>date</i> can be specified in either of the following formats: <table border="0" style="width: 100%;"> <tr> <td style="vertical-align: top; padding-right: 20px;"><i>YYYY.MM.DD-hh:mm:ss</i></td> <td>Specifies date in the format of "<i>year.month.day-hour:minute:second.</i>"</td> </tr> <tr> <td style="vertical-align: top; padding-right: 20px;"><i>MMDDhhmmYYYY.ss</i></td> <td>Specifies data in the format "<i>MonthDayHourMinuteYear.second.</i>"</td> </tr> </table>	<i>YYYY.MM.DD-hh:mm:ss</i>	Specifies date in the format of " <i>year.month.day-hour:minute:second.</i> "	<i>MMDDhhmmYYYY.ss</i>	Specifies data in the format " <i>MonthDayHourMinuteYear.second.</i> "	-u	Specifies time in UTC. When omitted, the local time is specified.	-y	Automatically answers "y" (yes) to all prompts.
-h	Displays usage statement. When used with other options or operands, an error occurs.																
-n	Automatically answers "n" (no) to all prompts.																
-q	Suppresses all messages to stdout, including prompts.																
-s <i>date</i>	Sets date and time. <i>date</i> can be specified in either of the following formats: <table border="0" style="width: 100%;"> <tr> <td style="vertical-align: top; padding-right: 20px;"><i>YYYY.MM.DD-hh:mm:ss</i></td> <td>Specifies date in the format of "<i>year.month.day-hour:minute:second.</i>"</td> </tr> <tr> <td style="vertical-align: top; padding-right: 20px;"><i>MMDDhhmmYYYY.ss</i></td> <td>Specifies data in the format "<i>MonthDayHourMinuteYear.second.</i>"</td> </tr> </table>	<i>YYYY.MM.DD-hh:mm:ss</i>	Specifies date in the format of " <i>year.month.day-hour:minute:second.</i> "	<i>MMDDhhmmYYYY.ss</i>	Specifies data in the format " <i>MonthDayHourMinuteYear.second.</i> "												
<i>YYYY.MM.DD-hh:mm:ss</i>	Specifies date in the format of " <i>year.month.day-hour:minute:second.</i> "																
<i>MMDDhhmmYYYY.ss</i>	Specifies data in the format " <i>MonthDayHourMinuteYear.second.</i> "																
-u	Specifies time in UTC. When omitted, the local time is specified.																
-y	Automatically answers "y" (yes) to all prompts.																
EXTENDED DESCRIPTION	<ul style="list-style-type: none"> ■ When the command is executed, a prompt to confirm execution of the command with the specified options is displayed. Enter "y" to execute the command or "n" to cancel the command. ■ In the M8000/M9000 servers, the setting automatically reflected to the standby XSCF. When there is a defect on the standby XSCF, it leads to an error and the setting will be reflected to the active XSCF only. ■ If the XSCF is used as an NTP server, change the XSCF time, and synchronize the domain times with the XSCF time. The XSCF time is applied to a domain during either of the following operations: 																

- The ntpdate(1M) command is executed in the domain.
- Rebooting the domain
- The setdate(8) command needs to be executed in the system power-off status.
- When an NTP server has been set to XSCF, the setdate(8) command results in an error. Whether an NTP server set to XSCF or not can be checked by using the showntp(8) command.
- To check the currently set XSCF date and time, execute the showdate(8) command.

EXAMPLES

EXAMPLE 1 Sets "January 27 16:59:00 2006" of the local time (JST) as the current time.

```
XSCF> setdate -s 012716592006.00
Fri Jan 27 16:59:00 JST 2006
The XSCF will be reset. Continue? [y|n] :y
Fri Jan 27 07:59:00 UTC 2006
XSCF>
The reset continues after this point.
```

EXAMPLE 2 Sets "January 27 07:59:00 2006" of UTC as the current time.

```
XSCF> setdate -u -s 012707592006.00
Fri Jan 27 07:59:00 UTC 2006
The XSCF will be reset. Continue? [y|n] :y
Fri Jan 27 07:59:00 UTC 2006
XSCF>
The reset continues after this point.
```

EXAMPLE 3 Sets "January 27 16:59:00 2006" of the local time (JST) as the current time. Automatically replies with 'y' to the prompt.

```
XSCF> setdate -y -s 012716592006.00
Fri Jan 27 16:59:00 JST 2006
The XSCF will be reset. Continue? [y|n] :y
Fri Jan 27 07:59:00 UTC 2006
XSCF>
The reset continues after this point.
```

EXAMPLE 4 Sets "January 27 16:59:00 2006" of the local time (JST) as the current time. Au-

tomatically replies with 'y' without displaying the prompt.

```
XSCF> setdate -q -y -s 012716592006.00
```

```
XSCF>
```

The reset continues after this point.

EXIT STATUS The following exit values are returned:

0 Successful completion.

>0 An error occurred.

SEE ALSO [setntp\(8\)](#), [settimezone\(8\)](#), [showdate\(8\)](#), [showntp\(8\)](#), [showtimezone\(8\)](#)

setdate(8)



NAME	setdcl - set a domain component list (DCL)
SYNOPSIS	<pre>setdcl -d domain_id -s policy=value</pre> <pre>setdcl -d domain_id -s option=value lsb [lsb...]</pre> <pre>setdcl -d domain_id -a lsb=xsb [lsb=xsb...]</pre> <pre>setdcl -d domain_id -r lsb [lsb...]</pre> <pre>setdcl -h</pre>
DESCRIPTION	<p>The <code>setdcl(8)</code> command sets a DCL.</p> <p>A DCL is hardware resource information that can be set for a domain or the logical system boards (LSBs) that are components of a domain.</p> <p>An LSB is a board unit recognized by the Solaris OS in a domain. Up to 16 boards can be registered in each domain, and they are represented by integer numbers ranging from 0 to 15.</p> <p>An extended system board (XSB) is a board unit that can be used in the system and is one partition of a partitioned physical system board (PSB). An XSB is represented by <i>x-y</i>, a combination of a PSB number and the number of one partition of the partitioned PSB (<i>x</i> is an integer ranging from 00 to 15, and <i>y</i> is an integer ranging from 0 to 3).</p> <p>The <code>setdcl(8)</code> command associates an XSB with an LSB that can be recognized by the Solaris OS in the domain, and its settings enable the Solaris OS in the domain to use hardware resources on the associated XSB.</p> <p>The <code>setdcl(8)</code> command can set the following types of DCL information:</p> <p>For the domain:</p> <ul style="list-style-type: none"> ■ Degradation range applicable for an error detected during an initial diagnosis of hardware (<code>policy</code>) <ul style="list-style-type: none"> On the M3000 server, the <code>setdcl(8)</code> command can set <code>policy</code> only. <p>For the LSB:</p> <ul style="list-style-type: none"> ■ XSB number of the XSB to be associated with an LSB (<code>lsb, xsb</code>) <ul style="list-style-type: none"> The XSB with the specified XSB number is associated with an LSB. ■ Using memory mounted on an LSB (<code>no-mem</code>) <ul style="list-style-type: none"> The user can specify whether an operating system in the domain can use memory mounted on an LSB. ■ Using I/O devices mounted on an LSB (<code>no-io</code>) <ul style="list-style-type: none"> The user can specify whether an operating system in the domain can use I/O devices, such as a PCI card, mounted on an LSB.

- Whether to set a priority for the specified LSB as a floating board, relative to other boards (`float`)

The user can specify whether to set a priority for the specified LSB as a floating board, relative to other boards. A floating board is used for dynamic reconfiguration (DR) for purposes such as changing the domain configuration, while minimizing effect of DR on the operating system.

Privileges

You must have `plataadm` privileges to run this command.

Refer to `setprivileges(8)` for more information.

OPTIONS

The following options are supported:

`-a lsb=xsb` Specifies an XSB number to be associated with an LSB number in the domain. The following form can be accepted. On the M3000 server, you cannot specify this option.

lsb=xsb

lsb Specifies an LSB number. An integer ranging from 0 to 15 can be specified.

xsb Specifies an XSB number. The following *xsb* form is accepted:

x-y *x*: An integer from 00–15.
y: An integer from 0–3.

lsb and *xsb* can be specified with an equal sign (=) as a delimiter. The space character must not be inserted immediately before and after "=". *lsb=xsb* can be repeated multiple times by using a space character as a delimiter.

If the same pair of an LSB number and XSB number is duplicated, an error occurs. Also, if an XSB number has already been set for the specified *lsb*, an error occurs.

If the specified *xsb* has already been set for another LSB, the existing setting is canceled and the specified *xsb* is set for the specified *lsb*.

`-d domain_id` Specifies the domain ID to be set. An integer ranging from 0 to 23 can be specified for *domain_id*, depending on the system configuration.

`-h` Displays usage statement. When used with other options or operands, an error occurs.

- `-r` Clears the XSB number associated with an LSB number in the specified domain. On the M3000 server, you cannot specify this option.
- `-s option=value` Makes settings regarding hardware resources of the XSB associated with an LSB. An item to be set is specified for *option*, and a value corresponding to *option* is specified for *value*. *option* and *value* are specified only once in a format using an equal sign (=) to delimit the specified values. The space character must not be inserted immediately before and after "=".
- One of the following can be specified for *option*. On the M3000 server, only `policy` can be specified.
- | | |
|---------------------|--|
| <code>policy</code> | Degradation range applicable for a detected error during an initial diagnosis of hardware. |
| <code>no-mem</code> | Whether to omit the use of memory on a domain |
| <code>no-io</code> | Whether to omit the use of I/O devices on a domain |
| <code>float</code> | Whether to set a priority for the board as a floating board, relative to other boards |
- If `policy` is specified for *option*, either of the following can be specified for *value*:
- | | |
|---------------------|--|
| <code>fru</code> | Degrades the target Field Replaceable Unit (FRU) for an error detected by a diagnosis. |
| <code>xsb</code> | Degrades the target XSB for an error detected by a diagnosis. |
| <code>system</code> | Stops the target domain for an error detected by a diagnosis. |
- If `no-mem` is specified for *option*, either of the following can be specified for *value*:
- | | |
|--------------------|--|
| <code>true</code> | Omits the use of memory on a domain. |
| <code>false</code> | Does not omit the use of memory on a domain (default). |

If `no-io` is specified for *option*, either of the following can be specified for *value*:

<code>true</code>	Omits the use of I/O devices on a domain.
<code>false</code>	Does not omit the use of I/O devices on a domain (default).

If `float` is specified for *option*, either of the following can be specified for *value*:

<code>true</code>	Gives a higher priority regarding floating boards.
<code>false</code>	Does not give a higher priority regarding floating boards (default).

OPERANDS

The following operands are supported:

<i>lsb</i>	Specifies the number of the LSB whose information is to be set. Specify by using an integer ranging from 0 to 15. Multiple <i>lsb</i> s can be specified by delimiting with spaces. Specifies unique <i>lsb</i> within the domain. If the same <i>lsb</i> number is specified, an error occurs. On the M3000 server, you cannot specify this option.
------------	--

EXTENDED DESCRIPTION

- If the XSB associated with the specified LSB has been configured in the domain configuration, the information that is set for the LSB cannot be changed. Before making such a change, unassign the XSB from the domain configuration by executing the `deleteboard(8)` command, or re-configure it in another domain configuration by executing the `moveboard(8)` command.
- If the specified domain is running, the value of `policy` cannot be changed. To change the value, first turn off power to the domain.
- The currently set DCL information can be checked by using the `showdcl(8)` command.

EXAMPLES

EXAMPLE 1 Sets XSB#00-0 for LSB#00 and XSB#00-1 for LSB#01 of domain ID 0.

```
XSCF> setdcl -d 0 -a 00=00-0 01=00-1
```

EXAMPLE 2 Sets `no-mem=true` for LSB#00 and #01 of domain ID 0.

```
XSCF> setdcl -d 0 -s no-mem=true 00 01
```

EXAMPLE 3 Sets `policy=system` for domain ID 0.

```
XSCF> setdcl -d 0 -s policy=system
```

EXAMPLE 4 Clear the XSBs associated with LSB#00 and #01 of domain ID 0.

```
XSCF> setdcl -d 0 -r 00 01
```

EXIT STATUS

The following exit values are returned:

0 Successful completion.

>0 An error occurred.

SEE ALSO

addboard(8), **deleteboard**(8), **moveboard**(8), **setupfru**(8), **showboards**(8), **showdcl**(8), **showdevices**(8), **showfru**(8)

setdcl(8)



NAME	setdomainmode - set the modes of operation for the specified domain																
SYNOPSIS	<p>setdomainmode [[-q] [-y n]] -d <i>domain_id</i> -m <i>function=mode</i></p> <p>setdomainmode -h</p>																
DESCRIPTION	<p>setdomainmode(8) sets the modes of operation for the specified domain.</p> <p>The modes of operation for the specified domain include the following types:</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;">Diagnostics Level</td> <td>OpenBoot PROM diagnostic levels. The default is standard.</td> </tr> <tr> <td>Secure Mode</td> <td>Whether to enable or disable the host watchdog and suppress break signal reception. The default of the host watchdog is enable and suppress break signal reception is enable.</td> </tr> <tr> <td>Autoboot</td> <td>Whether to enable or disable the auto boot function used at domain startup. The default is enable.</td> </tr> <tr> <td>CPU Mode</td> <td>Way of determining the CPU operational mode mounted on the domain. The CPU operational mode can be automatically determined at domain startup (<code>auto</code>), or manually set to the compatible mode (<code>compatible</code>). The default is to let it automatically determined at domain startup. On the M3000 server, you cannot specify CPU Mode.</td> </tr> </table> <p style="margin-left: 20px;">The CPU operational mode includes the following two types:</p> <table border="0" style="margin-left: 20px;"> <tr> <td colspan="2">SPARC64 VII enhanced mode</td> </tr> <tr> <td colspan="2">Operates using the enhanced functions of SPARC64 VII processor. This mode is set to the domain consists only of SPARC64 VII processors and when the CPU operational mode determined automatically.</td> </tr> <tr> <td colspan="2">SPARC64 VI compatible mode</td> </tr> <tr> <td colspan="2">All the mounted CPUs operate with the functions equivalent to the SPARC64 VI processor. This mode can be set to a domain of any CPU configuration.</td> </tr> </table> <p>If any of the modes of operation for the specified domain is set, the current settings are listed.</p>	Diagnostics Level	OpenBoot PROM diagnostic levels. The default is standard.	Secure Mode	Whether to enable or disable the host watchdog and suppress break signal reception. The default of the host watchdog is enable and suppress break signal reception is enable.	Autoboot	Whether to enable or disable the auto boot function used at domain startup. The default is enable.	CPU Mode	Way of determining the CPU operational mode mounted on the domain. The CPU operational mode can be automatically determined at domain startup (<code>auto</code>), or manually set to the compatible mode (<code>compatible</code>). The default is to let it automatically determined at domain startup. On the M3000 server, you cannot specify CPU Mode.	SPARC64 VII enhanced mode		Operates using the enhanced functions of SPARC64 VII processor. This mode is set to the domain consists only of SPARC64 VII processors and when the CPU operational mode determined automatically.		SPARC64 VI compatible mode		All the mounted CPUs operate with the functions equivalent to the SPARC64 VI processor. This mode can be set to a domain of any CPU configuration.	
Diagnostics Level	OpenBoot PROM diagnostic levels. The default is standard.																
Secure Mode	Whether to enable or disable the host watchdog and suppress break signal reception. The default of the host watchdog is enable and suppress break signal reception is enable.																
Autoboot	Whether to enable or disable the auto boot function used at domain startup. The default is enable.																
CPU Mode	Way of determining the CPU operational mode mounted on the domain. The CPU operational mode can be automatically determined at domain startup (<code>auto</code>), or manually set to the compatible mode (<code>compatible</code>). The default is to let it automatically determined at domain startup. On the M3000 server, you cannot specify CPU Mode.																
SPARC64 VII enhanced mode																	
Operates using the enhanced functions of SPARC64 VII processor. This mode is set to the domain consists only of SPARC64 VII processors and when the CPU operational mode determined automatically.																	
SPARC64 VI compatible mode																	
All the mounted CPUs operate with the functions equivalent to the SPARC64 VI processor. This mode can be set to a domain of any CPU configuration.																	
Privileges	<p>You must have one of the following privileges to run this command:</p> <ul style="list-style-type: none"> ■ OpenBoot PROM diagnostic levels: <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;"><code>fieldeng</code></td> <td>Can run this command for all domains.</td> </tr> </table>	<code>fieldeng</code>	Can run this command for all domains.														
<code>fieldeng</code>	Can run this command for all domains.																

- Host watchdog and suppress break signal reception, auto boot function, and operational mode of CPU:

platadm Can run this command for all domains.

domainadm Can run this command only for your managed domains.

Refer to `setprivileges(8)` for more information.

OPTIONS

The following options are supported:

-d *domain_id* Specifies the domain ID to be set. *domain_id* can be 0-23 depending on the system configuration.

-h Displays usage statement. When used with other options or operands, an error occurs.

`-m function=mode` Sets the modes of operation and specifies its values. Use *function* to set the modes of operation. One of the following can be specified:

<code>diag</code>	Specifies the OpenBoot PROM diagnostic level.
<code>secure</code>	Specifies whether to enable or disable the host watchdog and suppress break signal reception.
<code>autoboot</code>	Specifies whether to enable or disable the Auto boot function.
<code>cpumode</code>	Sets the operational mode of CPU. When you specified <code>cpumode</code> on the M3000 server, it results in an error.

When `diag` is specified for *function*, any of the following can be specified for *mode*:

Note – This function cannot be specified for the domain which is powered on.

<code>none</code>	No diagnosis is performed.
<code>min</code>	Sets standard for the diagnostic level.
<code>max</code>	Sets maximum for the diagnostic level.

When `secure` is specified for *function*, one of the following can be specified for *mode*. The setting will be reflected after domain power on or restart.

<code>on</code>	Enables the host watchdog and suppress break signal reception.
<code>off</code>	Disables the host watchdog and suppress break signal reception.

When `autoboot` is specified for *function*, one of the following can be specified for *mode*. The setting will be reflected after domain power on or restart.

<code>on</code>	Enables the Auto boot function.
<code>off</code>	Disables the Auto boot function.

(continued)

When `cpumode` is specified for *function*, one of the following can be specified for *mode*:

Note – This function cannot be specified for the domain which is powered on.

`auto`

Automatically determines the operational mode of CPU at domain startup. Depending on the CPU configuration on the domain, any of the following CPU operational mode is set:

- Consists only of SPARC64 VII processors: SPARC64 VII enhanced mode
- SPARC64 VII and VI processors mixed: SPARC64 VI compatible mode
- Consists only of SPARC64 VI processors: SPARC64 VI compatible mode

`compatible`

Regardless of the CPUs mounted, sets the operational mode of CPU to the SPARC64 VI compatible mode.

`-n` Automatically answers "n" (no) to all prompts.

`-q` Suppresses all messages to stdout, including prompts.

`-y` Automatically answers "y" (yes) to all prompts.

EXTENDED DESCRIPTION

- When the command is executed, a prompt to confirm execution of the command with the specified options is displayed. Enter "y" to execute the command or "n" to cancel the command.
- The system board (XSB) which can be added by Dynamic Reconfiguration (DR) is decided by the CPU operational mode currently set to the domain, which is as follows:

Domain CPU configuration	Value of CPU Mode	Current CPU operational mode	CPU configuration of a system board which can be added by DR operation
SPARC64 VII	auto	SPARC64 VII enhanced mode	SPARC64 VII

Domain CPU configuration	Value of CPU Mode	Current CPU operational mode	CPU configuration of a system board which can be added by DR operation
SPARC64 VII	compatible	SPARC64 VI compatible mode	Any CPU configuration
SPARC64 VII/VI	auto or compatible	SPARC64 VI compatible mode	Any CPU configuration
SPARC64 VI	auto or compatible	SPARC64 VI compatible mode	Any CPU configuration

For details of the CPU operational mode and the DR operation, see the *DR User's Guide*.

- To add the XSB other than those above, you need to perform the domain reconfiguration accompanied by the domain power off/on or reboot.
- When the operational mode of CPU has been automatically determined, if a situation as described below occurred, the CPU operational mode changes at the domain restart, from the SPARC64 VI compatible mode to the SPARC64 VII enhanced mode. In the SPARC64 VII enhanced mode, an XSB mounted with the SPARC64 VI processors cannot be added by DR operation.
 - When the SPARC64 VII and VI processors are mixed, after the restart due to the SPARC64 VI processor failure, there is no SPARC64 VI processor on a domain.

When the SPARC64 VI processors mounted, or planned to be mounted on the domain, set the operational mode of CPU to the SPARC64 VI compatible mode.

- To check the mode of CPUs which currently set to the domain, execute the `prtdiag(1M)` command on Solaris OS. For the `prtdiag(1M)` command, see the manual page of Solaris OS.
- If the Mode switch of the operator panel is set to *Service*, the settings of the modes of operation for the specified domain have the following values, regardless of the settings of the `setdomainmode(8)` command:
 - OpenBoot PROM diagnostic level (`Diagnostic Level`), operational mode of CPU (`CPU Mode`): operates as the `setdomainmode(8)` command setting
 - Host watchdog and suppress break signal reception (`Secure Mode`), auto boot function (`Autoboot`): `off`
- When the OpenBoot PROM environmental variable '`auto-boot?`' has been set to `false`, the auto boot function is disabled.
- The diagnostics level of OpenBoot PROM is applied to the `diag level` of the `addboard(8)` command and `moveboard(8)` command.
- The settings of the current modes of operation for the specified domain can be checked by using the `showdomainmode(8)` command.

EXAMPLES

EXAMPLE 1 Sets the OpenBoot PROM diagnostic level for domain ID 0 to none.

```
XSCF> setdomainmode -d 0 -m diag=none
Diagnostic Level      :min      -> none
Secure Mode          :on       -> -
Autoboot             :on       -> -
CPU Mode             :auto     -> -
The specified modes will be changed.
Continue? [y|n]:y
configured.
Diagnostic Level      :none
Secure Mode          :on (host watchdog: available Break-signal:non-receive)
Autoboot             :on (autoboot:on)
CPU Mode             :auto
```

EXAMPLE 2 Enables the auto boot function for domain ID 0. Automatically answers "y" to all prompts.

```
XSCF> setdomainmode -y -d 0 -m autoboot=on
Diagnostic Level      :none      -> -
Secure Mode          :on       -> -
Autoboot             :off      -> on
CPU Mode             :auto     -> -
The specified modes will be changed.
Continue? [y|n]:y
configured.
Diagnostic Level      :none
Secure Mode          :on (host watchdog: available Break-signal:non-receive)
Autoboot             :on (autoboot:on)
CPU Mode             :auto
```

EXAMPLE 3 Cancels the `setdomainmode(8)` command execution that is in progress.

```
XSCF> setdomainmode -d 0 -m diag=none
```

```
Diagnostic Level      :min      -> none
```

```
Secure Mode          :on       -> -
```

```
Autoboot             :on       -> -
```

```
CPU Mode             :auto     -> -
```

The specified modes will be changed.

```
Continue? [y|n]:n
```

EXAMPLE 4 Enables the auto boot function for domain ID 0. Suppresses prompts, and automatically answers "y" to all prompts

```
XSCF> setdomainmode -q -y -d 0 -m autoboot=on
```

EXIT STATUS

The following exit values are returned:

0 Successful completion.

>0 An error occurred.

SEE ALSO

`showdomainmode(8)`

setdomainmode(8)



NAME	setdomparam - forcibly rewrite OpenBoot PROM environment variables												
SYNOPSIS	<pre>setdomparam [[-q] -{y n}] -d <i>domain_id</i> use-nvramrc setdomparam [[-q] -{y n}] -d <i>domain_id</i> security-mode setdomparam [[-q] -{y n}] -d <i>domain_id</i> set-defaults setdomparam -h</pre>												
DESCRIPTION	<p>The setdomparam(8) command rewrites OpenBoot PROM environment variables of a specified domain.</p> <p>The following OpenBoot PROM environment variables can be specified.</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;">use-nvramrc?</td> <td>Whether to execute the contents of the NVRAM at the boot or reboot of a domain.</td> </tr> <tr> <td>security-mode?</td> <td>Firmware security level setting</td> </tr> <tr> <td>set-defaults</td> <td>Whether to restore OpenBoot PROM environment variables to the settings at the time of shipment from the factory</td> </tr> </table>	use-nvramrc?	Whether to execute the contents of the NVRAM at the boot or reboot of a domain.	security-mode?	Firmware security level setting	set-defaults	Whether to restore OpenBoot PROM environment variables to the settings at the time of shipment from the factory						
use-nvramrc?	Whether to execute the contents of the NVRAM at the boot or reboot of a domain.												
security-mode?	Firmware security level setting												
set-defaults	Whether to restore OpenBoot PROM environment variables to the settings at the time of shipment from the factory												
Privileges	<p>You must have one of the following privileges to run this command:</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;">platadm</td> <td>Can run this command for all domains.</td> </tr> <tr> <td>domainadm</td> <td>Can run this command only for your managed domain.</td> </tr> </table> <p>Refer to setprivileges(8) for more information.</p>	platadm	Can run this command for all domains.	domainadm	Can run this command only for your managed domain.								
platadm	Can run this command for all domains.												
domainadm	Can run this command only for your managed domain.												
OPTIONS	<p>The following options are supported:.</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;">-d <i>domain_id</i></td> <td>Specifies the ID of the domain which OpenBoot PROM environment variables are rewritten. <i>domain_id</i> can be 0–23 depending on the system configuration.</td> </tr> <tr> <td></td> <td>Note – The domain which is powered on cannot specify.</td> </tr> <tr> <td>-h</td> <td>Displays usage statement. When used with other options or operands, an error occurs.</td> </tr> <tr> <td>-n</td> <td>Automatically answers "n" (no) to all prompts.</td> </tr> <tr> <td>-q</td> <td>Suppresses all messages to stdout, including prompts.</td> </tr> <tr> <td>-y</td> <td>Automatically answers "y" (yes) to all prompts.</td> </tr> </table>	-d <i>domain_id</i>	Specifies the ID of the domain which OpenBoot PROM environment variables are rewritten. <i>domain_id</i> can be 0–23 depending on the system configuration.		Note – The domain which is powered on cannot specify.	-h	Displays usage statement. When used with other options or operands, an error occurs.	-n	Automatically answers "n" (no) to all prompts.	-q	Suppresses all messages to stdout, including prompts.	-y	Automatically answers "y" (yes) to all prompts.
-d <i>domain_id</i>	Specifies the ID of the domain which OpenBoot PROM environment variables are rewritten. <i>domain_id</i> can be 0–23 depending on the system configuration.												
	Note – The domain which is powered on cannot specify.												
-h	Displays usage statement. When used with other options or operands, an error occurs.												
-n	Automatically answers "n" (no) to all prompts.												
-q	Suppresses all messages to stdout, including prompts.												
-y	Automatically answers "y" (yes) to all prompts.												

OPERANDS

The following operands are supported:

`use-nvramrc` Sets false for the `use-nvramrc?` environment variable.
`security-mode` Sets none to the `security-mode?` environment variable.
`set-defaults` Restores the OpenBoot PROM environment variables to the settings at the time of shipment from the factory

EXTENDED DESCRIPTION

When the command is executed, a prompt to confirm execution of the command with the specified options is displayed. Enter "y" to execute the command or "n" to cancel the command.

EXAMPLES

EXAMPLE 1 Sets false for the `use-nvramrc?` OpenBoot PROM environment variable of domain ID 0.

```
XSCF> setdomparam -d 0 use-nvramrc
DomainIDs of domains that will be affected:00
OpenBoot PROM variable use-nvram will be set to false.
Continue? [y|n]:y
```

EXAMPLE 2 Sets none for the `security-mode` OpenBoot PROM environment variable of domain ID 0.

```
XSCF> setdomparam -d 0 security-mode
DomainIDs of domains that will be affected:00
OpenBoot PROM variable security-mode will be set to none.
Continue? [y|n]:y
```

EXAMPLE 3 Initializes the OpenBoot PROM environment variables of the domain ID 0 to the settings at the time of shipment from the factory.

```
XSCF> setdomparam -d 0 set-defaults
DomainIDs of domains that will be affected:00
All OpenBoot PROM variable will be reset to original default values.
Continue? [y|n]:y
```

EXAMPLE 4 Initializes the OpenBoot PROM environment variables of the domain ID 1 to the settings at the time of shipment from the factory. Automatically replies with 'y' without displaying the prompt.

```
XSCF> setdomparam -q -y -d 1 set-defaults
```

EXIT STATUS | The following exit values are returned:

0	Successful completion.
>0	An error occurred.

setdomparam(8)



NAME	setdscp - set the IP address assignments for the Domain to Service Processor Communications Protocol (DSCP)
SYNOPSIS	<pre> setdscp [-v] setdscp [-f] [-v] [[-q] -{y n}] -i <i>address</i> -m <i>netmask</i> setdscp [-f] [-v] [[-q] -{y n}] -s -i <i>address</i> setdscp [-f] [-v] [[-q] -{y n}] -d <i>domain_id</i> -i <i>address</i> setdscp -h </pre>
DESCRIPTION	<p>setdscp(8) assigns IP addresses to the DSCP links.</p> <p>setdscp is intended for initial configuration only. Domains should not be powered on when running this command.</p> <p>Note – You are required to reboot the Service Processor after modifying the DSCP IP address assignment using this command, and before the IP addresses you specified are used.</p> <p>You can specify a network address for use by all of the DSCP links using the <i>-i address</i> and <i>-m netmask</i> arguments. In this mode of operation, the IP addresses used by the Service Processor and each domain-specific DSCP link are automatically selected from within the range of addresses indicated by the network address.</p> <p>You can set the IP address of an individual, domain-specific DSCP link independently of all other DSCP address settings using the <i>-d domain_id</i> and <i>-i address</i> arguments.</p> <p>You can set the IP address of the Service Processor independently of all other DSCP address settings using the <i>-s</i> and <i>-i address</i> arguments.</p> <p>If DSCP has been previously configured, the current settings are displayed. If they are correct, they can be accepted by pressing the <code>Enter</code> key.</p> <p>An error occurs if you set the address of the Service Processor or a domain to a value that either is out of range for a previously configured network address, or conflicts with an address already assigned to another domain or the Service Processor. You can override such errors by using the <i>-f</i> option.</p> <p>Using the <i>-f</i> option with a conflicting IP address may cause misconfiguration. You must resolve such conflicts for DSCP to operate properly.</p> <p>With no arguments, setdscp enters an interactive mode that prompts you to enter all of the DSCP IP address information sequentially. (The noninteractive method, setting up the IP addresses of all domains using the <i>-i</i> and <i>-m</i> options, is preferred.) After inputting all the requested settings, you can review the settings and decide whether to commit them to the DSCP configuration database.</p>

Note – The `-y` and `-n` options can be used (with or without the `-q` option) when running `setdscp` in interactive mode.

Privileges

You must have `platadm` or `fieldeng` privileges to run this command.

Refer to `setprivileges(8)` for more information.

OPTIONS

The following options are supported:

- `-d domain_id` Domain identifier. Must be used with `-i address` option. *domain_id* can be 0–23 depending on the system configuration.
- `-f` Forces `setdscp` to ignore out of range and address conflict errors and commits the new settings.
- `-h` Displays usage statement.

When used with other options or operands, an error occurs.
- `-i address` Specifies an IP address in the IPv4 dotted decimal format.

When used with `-m netmask` it specifies a network address for all DSCP links in the system.

When used with `-d domain_id` it specifies an individual, domain-specific IP address for use by DSCP.

When used with `-s`, it specifies the IP address used for the Service Processor end of all DSCP links in the system.
- `-m netmask` Specifies a netmask address for all DSCP links in the system. Must be used with `-i address`.
- `-n` Automatically answers "n" (no) to all prompts.
- `-q` Suppresses all messages to stdout, including prompts.
- `-s` Must be used with the `-i address` option. Specifies the Service Processor end of all DSCP links in the system.
- `-v` Displays a detailed message. If this option is specified with the `-q` option, the `-v` option is ignored.
- `-y` Automatically answers "y" (yes) to all prompts.

EXAMPLES

Caution – The IP addresses shown in the following examples are examples only. When choosing DSCP IP addresses avoid choosing addresses that are used elsewhere in your local area network (LAN). For information about DSCP IP addresses refer to the System Configuration chapter of the Administration Guide.

EXAMPLE 1 Assigning All DSCP Addresses

```
XSCF> setdscp -y -i 10.1.1.0 -m 255.255.255.0
Commit these changes to the database? [y|n] : y
```

EXAMPLE 2 Assigning an Alternative IP address to Domain 1

```
XSCF> setdscp -d 1 -i 10.1.1.26
Commit these changes to the database? [y|n] : y
```

EXAMPLE 3 Specifying a Netmask Address With `-q` and `-y` Options

```
XSCF> setdscp -q -y -i 10.1.1.0 -m 255.255.255.0
```

EXAMPLE 4 Setting DSCP Addresses Using Interactive Mode

The default value displayed by each prompt in interactive mode matches the previous configuration. This makes it possible to interactively review and modify DSCP configuration. In this example you only input the network address portion and then press the Enter key to accept all subsequent settings.

```
XSCF> setdscp
DSCP network [0.0.0.0      ] > 10.1.1.0

DSCP netmask [255.0.0.0   ] > 255.255.255.0

XSCF address [10.1.1.1    ] > [Enter]
Domain #00 address [10.1.1.2      ] > [Enter]
Domain #01 address [10.1.1.3      ] > [Enter]
Domain #02 address [10.1.1.4      ] > [Enter]
Domain #03 address [10.1.1.5      ] > [Enter]
Domain #04 address [10.1.1.6      ] > [Enter]
Domain #05 address [10.1.1.7      ] > [Enter]
Domain #06 address [10.1.1.8      ] > [Enter]
Domain #07 address [10.1.1.9      ] > [Enter]
Domain #08 address [10.1.1.10     ] > [Enter]
Domain #09 address [10.1.1.11     ] > [Enter]
Domain #10 address [10.1.1.12     ] > [Enter]
```

```

Domain #11 address [10.1.1.13    ] > [Enter]
Domain #12 address [10.1.1.14    ] > [Enter]
Domain #13 address [10.1.1.15    ] > [Enter]
Domain #14 address [10.1.1.16    ] > [Enter]
Domain #15 address [10.1.1.17    ] > [Enter]
Domain #16 address [10.1.1.18    ] > [Enter]
Domain #17 address [10.1.1.19    ] > [Enter]
Domain #18 address [10.1.1.20    ] > [Enter]
Domain #19 address [10.1.1.21    ] > [Enter]
Domain #20 address [10.1.1.22    ] > [Enter]
Domain #21 address [10.1.1.23    ] > [Enter]
Domain #22 address [10.1.1.24    ] > [Enter]
Domain #23 address [10.1.1.25    ] > [Enter]
Commit these changes to the database [y|n]? y

```

EXIT STATUS

The following exit values are returned:

```

0           Successful completion.
>0         An error occurred.

```

SEE ALSO

showdscp(8)

NAME	setdualpowerfeed - set dual power feed mode								
SYNOPSIS	setdualpowerfeed -s <i>key</i> setdualpowerfeed -h								
DESCRIPTION	<p>The setdualpowerfeed(8) command specifies dual power feed mode in the system.</p> <p>The setdualpowerfeed(8) command is available on the M3000/M4000/M5000 servers only. On the M8000/M9000 servers, when the power cabinet for dual power feed connected, it automatically configures the dual power feed mode.</p> <p>To apply the specified configuration, reboot the system.</p>								
Privileges	<p>You must have platadm or fieldeng privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>								
OPTIONS	<p>The following options are supported:</p> <table border="0"> <tr> <td style="padding-right: 20px;">-h</td> <td>Displays usage statement. When used with other options or operands, an error occurs.</td> </tr> <tr> <td style="padding-right: 20px;">-s <i>key</i></td> <td>Sets dual power feed mode in the system. Either of the following can be specified for <i>key</i>:</td> </tr> <tr> <td style="padding-left: 40px;">enable</td> <td>Enables the dual power feed mode.</td> </tr> <tr> <td style="padding-left: 40px;">disable</td> <td>Disables dual power feed mode.</td> </tr> </table>	-h	Displays usage statement. When used with other options or operands, an error occurs.	-s <i>key</i>	Sets dual power feed mode in the system. Either of the following can be specified for <i>key</i> :	enable	Enables the dual power feed mode.	disable	Disables dual power feed mode.
-h	Displays usage statement. When used with other options or operands, an error occurs.								
-s <i>key</i>	Sets dual power feed mode in the system. Either of the following can be specified for <i>key</i> :								
enable	Enables the dual power feed mode.								
disable	Disables dual power feed mode.								
EXTENDED DESCRIPTION	The state of the current dual power feed mode can be checked by using the showdualpowerfeed(8) command.								
EXAMPLES	<p>EXAMPLE 1 Disables dual power feed mode in the system. Before rebooting the system, a message is displayed.</p> <pre>XSCF> setdualpowerfeed -s disable enable -> disable</pre> <p>NOTE: Dual power feed will be disabled the next time the platform is powered on.</p> <p>EXAMPLE 2 Enables dual power feed mode in the system. Before rebooting the system, a</p>								

setdualpowerfeed(8)

message is displayed.

```
XSCF> setdualpowerfeed -s enable
```

```
disable -> enable
```

NOTE: Dual power feed will be enabled the next time the platform is powered on.

EXIT STATUS

The following exit values are returned:

0 Successful completion.

>0 An error occurred.

SEE ALSO

showdualpowerfeed (8)

NAME	setemailreport - set up the email report configuration data						
SYNOPSIS	<p>setemailreport [-v] [-t]</p> <p>setemailreport [-s <i>variable= value</i>]...</p> <p>setemailreport -h</p>						
DESCRIPTION	<p>setemailreport(8) sets up email reporting configuration data for remote maintenance. Once the configuration data is set up, it is used by the fault management daemon to send email reports as required.</p> <p>If you run the <code>setemailreport</code> command without specifying any options, you will be prompted to answer whether email reporting is to be enabled. If enabled, you will be prompted to provide a list of email addresses.</p> <p>Where:</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;">-a</td> <td>Add recipient</td> </tr> <tr> <td style="padding-right: 20px;">-d</td> <td>Delete recipient</td> </tr> <tr> <td style="padding-right: 20px;">-r</td> <td>Replace recipient (Default)</td> </tr> </table> <p>You can set up email reporting noninteractively by using the <code>-s</code> option.</p> <p>After the email server and port have been set up using <code>setsmtpt(8)</code>, you can use <code>setemailreport -t</code> to send a test email message.</p>	-a	Add recipient	-d	Delete recipient	-r	Replace recipient (Default)
-a	Add recipient						
-d	Delete recipient						
-r	Replace recipient (Default)						
Privileges	<p>You must have <code>platadm</code> privileges to run this command.</p> <p>Refer to <code>setprivileges(8)</code> and for more information.</p>						

OPTIONS

The following options are supported:

- h Displays usage statement.
When used with other options or operands, an error occurs.
- s *variable=value* Configures email reporting.
Valid entries for *variable* are:
 enable
 recipient
Valid *value* entries for enable are:
 yes
 no
Valid *value* entries for recipient are:
 Any valid company email account
- t Sends test email.
- v Specifies verbose output.

EXAMPLES**EXAMPLE 1** Enable Email Reporting Interactively

```
XSCF> setemailreport
Enable Email Reporting? [no]:yes
Email Recipient Address [useradm@company.com]:
Do you want to send a test mail now (Yes/No): no
```

EXAMPLE 2 Adding an Email Report Recipient Using -a

```
XSCF> setemailreport
Enable Email Reporting? [yes]: [RETURN]
Email Recipient Address[useradmin@company.com]: -a adm2@company.com
```

EXAMPLE 3 Deleting an Email Report Recipient Using -d

```
XSCF> setemailreport
Enable Email Reporting? [yes]: [RETURN]
Email Recipient Address[adm2@company.com]: -d adm2@company.com
```


EXAMPLE 4 Enable Email Reporting Noninteractively

```
XSCF> setemailreport -s enable=yes -s  
recipient="useradm@company.com, adm2@company.com"
```

EXAMPLE 5 Sending Test Email

```
XSCF> setemailreport -t  
....Sending test email to useradm@company.com  
[Email contents shown below]  
Host Name: jupiter  
Send Timestamp: 04-20-2006 16:31:45 PST  
Mail Server: 10.4.1.1
```

EXIT STATUS The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO [setsmtp\(8\)](#), [showemailreport\(8\)](#)

setemailreport(8)



NAME	sethostname - set a host name and a DNS domain name for an XSCF unit
SYNOPSIS	<p>sethostname <i>xscfu hostname</i></p> <p>sethostname -<i>d domainname</i></p> <p>sethostname -h</p>
DESCRIPTION	<p>sethostname(8) command sets a host name and a DNS domain name for an XSCF unit.</p> <p>In the M8000/M9000 servers, the DNS domain name becomes common to XSCF units. The host name can be specified for each XSCF unit.</p>
Privileges	<p>You must have platadm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p>-<i>d domainname</i> Specifies a DNS domain name to be set for the XSCF unit. The <i>domainname</i> is specified in up to 254 characters with the <i>hostname</i> included, with label elements delimited by a "." (period). If a domain name exceeding 254 characters is specified, an error occurs. A label element can contain alphanumeric characters and "-". Each label element must always begin with an alphabetic character and end with an alphanumeric character. If "localdomain" specified, an error occurs.</p> <p>-h Displays usage statement. When used with other options or operands, an error occurs.</p>

OPERANDS	<p>The following operands are supported:</p> <p><i>hostname</i> Specifies a host name to be set for the XSCF unit. The <i>hostname</i> is specified in up to 64 characters, not in Fully Qualified Domain Name (FQDN) but in an abbreviated form. If a host name exceeding 64 characters is specified, an error occurs. Alphanumeric character and "-" can be used. However, a host name must always begin with an alphabetic character and end with an alphanumeric character. If "localhost" specified, an error occurs.</p> <p><i>xscfu</i> Specifies the name of the XSCF unit to be set. The following values can be specified, depending on the system configuration. If no value is specified, an error occurs.</p> <table border="0" style="margin-left: 40px;"> <tr> <td><code>xscf#0</code></td> <td>XSCF unit 0</td> </tr> <tr> <td><code>xscf#1</code></td> <td>XSCF unit 1 (In the M8000/M9000 servers)</td> </tr> </table>	<code>xscf#0</code>	XSCF unit 0	<code>xscf#1</code>	XSCF unit 1 (In the M8000/M9000 servers)
<code>xscf#0</code>	XSCF unit 0				
<code>xscf#1</code>	XSCF unit 1 (In the M8000/M9000 servers)				
EXTENDED DESCRIPTION	<ul style="list-style-type: none"> ■ To reflect the host name and the DNS domain name to XSCF, execute the <code>applynetwork(8)</code> command. After reflected the information, use the <code>rebootxscf(8)</code> command to reset XSCF to complete the setting. ■ The currently set host name and DNS domain name of the XSCF unit can be checked by using the <code>shownetwork(8)</code> command. 				
EXAMPLES	<p>EXAMPLE 1 Sets the host name <code>scf0-hostname</code> for XSCF unit 0.</p> <pre>XSCF> sethostname xscf#0 scf0-hostname</pre> <p>EXAMPLE 2 Sets the DNS domain name <code>example.com</code> for XSCF unit.</p> <pre>XSCF> sethostname -d example.com</pre>				
EXIT STATUS	<p>The following exit values are returned:</p> <table border="0" style="margin-left: 40px;"> <tr> <td>0</td> <td>Successful completion.</td> </tr> <tr> <td>>0</td> <td>An error occurred.</td> </tr> </table>	0	Successful completion.	>0	An error occurred.
0	Successful completion.				
>0	An error occurred.				
SEE ALSO	<p><code>applynetwork(8)</code>, <code>rebootxscf(8)</code>, <code>showhostname(8)</code></p>				

NAME	sethttps - start or stop the HTTPS service, which is used in the XSCF network. This command also performs authentication-related settings
SYNOPSIS	<pre>sethttps [[-q] -{y n}] -c enable</pre> <pre>sethttps -c disable</pre> <pre>sethttps -c genscr country state province locality organization organizationalunit common e-mail</pre> <pre>sethttps [[-q] -{y n}] -c genserverkey</pre> <pre>sethttps -c importca</pre> <pre>sethttps [[-q] -{y n}] -c selfsign country state province locality organization organizationalunit common e-mail</pre> <pre>sethttps -h</pre>
DESCRIPTION	<p>The sethttps(8) command starts or stops the HTTPS service, which is used in the XSCF network. Also, this command performs authentication-related settings for authentication used in the HTTPS service.</p> <p>The following authentication-related items can be set:</p> <ul style="list-style-type: none"> ■ Configuring the self-certification authority ■ Creating a self-signed web server certificate ■ Creating the private key of the web server ■ Creating a web server certificate signing request (CSR) to an external certification authority ■ Importing a web server certificate signed by an external certification authority <p>XSCF does not support HTTP service. Only HTTPS service is supported.</p>
Privileges	<p>You must have platadm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>

OPTIONS

The following options are supported:

<code>-c {enable disable}</code>	Specify whether to enable the HTTPS service. One of the following values can be specified. If none of them is specified, an error occurs.
<code>enable</code>	Starts the HTTPS service.
<code>disable</code>	Stops the HTTPS service.
<code>-c genscr</code>	Creates a CSR.
<code>-c genserverkey</code>	Creates the private key of the web server.
<code>-c importca</code>	Imports a web server certificate signed by the certification authority to the XSCF.
<code>-c selfsign</code>	Configures the self-certification authority. Also, this operand creates a self-signing web server certificate.
<code>-h</code>	Displays usage statement. When used with other options or operands, an error occurs.
<code>-n</code>	Automatically answers "n" (no) to all prompts.
<code>-q</code>	Suppresses all messages to stdout, including prompts.
<code>-y</code>	Automatically answers "y" (yes) to all prompts.

OPERANDS

The following operands are supported:

<i>common</i>	Specifies common names such as the creator name and the host name of a server.
<i>country</i>	Specifies a country name with a two-letter code such as JP or US.
<i>e-mail</i>	Specifies an E-mail address.
<i>locality</i>	Specifies a city name, etc.
<i>organization</i>	Specifies a company name, etc.
<i>organizationalunit</i>	Specifies an organization such as a section or department.
<i>state province</i>	Specifies the name of a state, province, etc.

EXTENDED DESCRIPTION

- When the HTTPS server is enabled or there is a private certificate authority, web server certificate, or web server secret key, a prompt to confirm execution of the command with the specified options is displayed. Enter "y" to execute the command or "n" to cancel the command.
- The CSR is overwritten.

- In case the XSCF unit is duplicated configuration, the setting automatically reflected to the standby XSCF. When there's a defect on the standby XSCF, it leads to an error.
- When using an external certification authority, it leads to an error in the following cases.
 - When the "-c genscr" option or the "-c enable" option is executed, without executing the "-c genserverkey" option.
Create the private key of the web server using the "-c genserverkey" option.
 - When the "-c enable" option is executed, without executing the "-c importca" option.
Import a web server certificate using the "-c importca" option.
 - When the web server certificate which imported by executing the "-c importca" option does not correspond to the private key of the web server which has been created by executing the "-c genserverkey" option.
Confirm the validity of the web server certificate.
- The information which has been set will be reflected by using the `rebootxscf(8)` command to reset XSCF.
- The details of the current HTTPS service can be checked by using the `showhttps(8)` command.

EXAMPLES

EXAMPLE 1 Starts the HTTPS service.

```
XSCF> sethttps -c enable
Continue? [y|n] :y
Please reset the XSCF by rebootxscf to apply the https settings.
```

EXAMPLE 2 Stops the HTTPS service.

```
XSCF> sethttps -c disable
```

EXAMPLE 3 Creates a CSR with the following settings: *country*: JP, *state* | *province*: Kanagawa, *locality*: Kawasaki, *organization*: Example, *organizationalunit*: development, *common*: scf-host, *e-mail*: abc@example.com

```
XSCF> sethttps -c genscr JP Kanagawa Kawasaki Example development
\ scf-host abc@example.com
```

EXAMPLE 4 Creates the self-certification authority with the following settings, and creates a self-signed web server certificate: *country*: JP, *state* | *province*: Kanagawa, *locality*: Kawasaki, *organization*: Example, *organizationalunit*: development, *com-*

mon: scf-host, e-mail: abc@example.com

```
XSCF> sethttps -c selfsign JP Kanagawa Kawasaki Example development
scf-host abc@example.com
```

CA key and CA cert already exist. Do you still wish to update? [y|n] :**y**

Enter passphrase:

Verifying - Enter passphrase:

EXAMPLE 5 Creates the private key of the web server.

```
XSCF> sethttps -c genserverkey
```

Server key already exists. Do you still wish to update? [y|n] :**y**

Enter passphrase:

Verifying - Enter passphrase:

EXAMPLE 6 Creates the private key of the web server. Automatically replies with "y" to the prompt.

```
XSCF> sethttps -c genserverkey
```

Server key already exists. Do you still wish to update? [y|n] :**y**

Enter passphrase:

Verifying - Enter passphrase:

EXAMPLE 7 Creates the private key of the web server. Automatically replies with "y" without displaying the prompt.

```
XSCF> sethttps -c genserverkey -q -y
```

Enter passphrase:

Verifying - Enter passphrase:

EXAMPLE 8 Imports the web server certificate. To exit, press the Enter key and then press "Ctrl" and "D".

```
XSCF> sethttps -c importca
```

Please import a certificate:

-----BEGIN CERTIFICATE-----

MIIDdTCCAt6gAwIBAgIBATANBgkqhkiG9w0BAQQFADCBgTELMakGA1UEBhMCamox

DjAMBgNVBAGTBXN0YXR1MREwDwYDVQQHEwhsb2NhbG10eTEVMBMGA1UEChMMb3Jn

YW5pemF0aW9uMQ8wDQYDVQQLEwZvcmdhbmksDzANBgNVBAMTBmNvbW1vbWljEWMBOG


```

CSqGSIb3DQEJARYHZWUubWFpbD AeFw0wNjA1MzAwNTI5MTVaFw0xNjA1MjcwNTI5
MTVaMG4xCzAJBGNVBAYTAmpqMQ4wDAYDVQOIEwVzdGF0ZTEVMBMGA1UEChMm3Jn
YW5pemF0aW9uMQ8wDQYDVQLEwZvcmdhbmksDzANBgNVBAMTBmNvbW1vbjEWMmQG
CSqGSIb3DQEJARYHZWUubWFpbD BnzANBgkqhkiG9w0BAQEFAAOBjQAwYkCgYEA
nkPntf+TjYtyK1NYFbo/YavFpUzkYTLHdt0Fbz/tZmGd3e6Jn34A2W9EC7D9hjLs
j+kAP41A16wFwGO7KP3H4iImX0Uysj19Hyk4jLBU51sw8JqvT2utTj1tV5mFPKL6
5A51Yuhf8OGrR+bYGl i6H1a6RPm1MSD7Z0AGDxR0eY0CAwEAAaOCAQ0wggEJMAkG
A1UdEwQCAAwLAYJYIZIAyb4QgENBB8WHU9wZW5TU0wgR2VuZXJhdGVkIEN1cnRp
ZmljYXR1MB0GA1UdDgQWBBI1CmI7QyZa8zpt1H16EfLR+EwDCBrgYDVR0jBI Gm
MIGjgBTnQYs6jzD7wdDhk7wsFeJGVaUTtaGBh6SBhDCBgTELMaKGA1UEBhMCamox
DjAMBGNVBAGTBXN0YXR1MREwDwYDVQQHEwHsb2NhbG10eTEVMBMGA1UEChMm3Jn
YW5pemF0aW9uMQ8wDQYDVQLEwZvcmdhbmksDzANBgNVBAMTBmNvbW1vbjEWMmQG
CSqGSIb3DQEJARYHZWUubWFpbIIBADANBgkqhkiG9w0BAQQFAAOBgQCqBFbo88Hi
yvOUyW8E8111AbuA04IrnjHI4cjHq9NuSX1w8mJsXKTVMx3WZCJpJDC+f/WoRMKw
R+OpXAVQvb2tjIn3k099dq+begECO4mwknW1t7QI7A1BkcW2/MkOo1IRa6iPlZwg
JoPmwAbrGyAvGUtdzUoyIH0j17dRQrVIRA==
-----END CERTIFICATE-----

```

[Enter]

[Ctrl] and [D]

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

showhttps (8)

sethttps(8)



NAME	setldap - configure the Service Processor as a Lightweight Directory Access Protocol (LDAP) client
SYNOPSIS	setldap {-b <i>bind</i> } {-B <i>baseDN</i> } {-c <i>certchain</i> } {-p } {-s <i>servers</i> } {-t <i>user</i> } -T <i>timeout</i> setldap -h
DESCRIPTION	setldap(8) allows you to configure the Service Processor as an LDAP client. Note – The LDAP client supports passwords only in the CRYPT format; UNIX Crypt or MD5. Therefore the passwords on the LDAP server must support it as well. Refer to the <i>Administration Guide</i> for more information.
Privileges	You must have useradm privileges to run this command. Refer to setprivileges(8) for more information.
OPTIONS	The following options are supported: -B <i>baseDN</i> Specifies distinguished name for the search base. Maximum character length is 128 characters. -b <i>bind</i> Sets the identity to use when binding to the LDAP server. Maximum character length is 128 characters -c <i>certchain</i> Imports an LDAP server certificate chain from the remote file specified in <i>certchain</i> . The certificate chain must be in PEM format. Remote files are specified using the standard scp syntax, that is, [user@]host:file., and imported using scp. If the copy requires a user password you will be prompted for it. Use of this option implicitly enables the use of Transport Layer Security (TLS) when connecting to LDAP. This may be disabled by specifying <i>certchain</i> as none. The certificate chain must be 64 Kbytes in size or less, and it must be valid or it will be rejected. -h Displays usage statement. When used with other options or operands, an error occurs. -p Sets a password to use when binding to the LDAP server. You will be prompted for the password.

- s *servers* Sets the primary and secondary LDAP servers and ports. *servers* is a comma-separated list of *server:port*. Ports are specified numerically and servers can be specified either by name or IP address in the dotted decimal format. For example, 10.8.31.14.636, *company:636*. The first server in the list is the primary. Server names must be resolvable. Maximum name length is 128 characters.
- t *user* Tests connections to all configured LDAP servers. Attempts to retrieve the password data for the specified user from each configured server and reports success or failure in each case.
- T *timeout* Sets the maximum time allowed for an LDAP search before it returns search results.

EXAMPLES**EXAMPLE 1** Configuring Bind Name

```
XSCF> setldap -b user -p
Password: <Enter password>
XSCF> showldap
Bind Name:                user
Base Distinguished Name:  Not set
LDAP Search Timeout:     0
Bind Password:           Set
LDAP Servers:            None
CERTS:                   None
```

EXAMPLE 2 Configuring Base Distinguished Name

```
XSCF> setldap -B ou=people,dc=company,dc=com
XSCF> showldap
Bind Name:                user
Base Distinguished Name:  ou=people,dc=company,dc=com
LDAP Search Timeout:     0
Bind Password:           Set
LDAP Servers:            None
CERTS:                   None
```

EXAMPLE 3 Setting the LDAP Timeout

```
XSCF> setldap -T 60
XSCF> showldap
Bind Name:                user
Base Distinguished Name:  ou=people,dc=company,dc=com
LDAP Search Timeout:      60
Bind Password:            Set
LDAP Servers:             None
CERTS:                   None
```

EXAMPLE 4 Setting the LDAP Server

```
XSCF> setldap -s ldap://company.com,ldaps://company2.com
XSCF> showldap
Bind Name:                user
Base Distinguished Name:  ou=people,dc=company,dc=com
LDAP Search Timeout:      60
Bind Password:            Set
LDAP Servers:             ldap://company.com:389 ldaps://company2.com:636
CERTS:                   None
```

EXAMPLE 5 Importing a Certificate

```
XSCF> setldap -c user@remote.machine:/path/to/cacert.pem
XSCF> showldap
Bind Name:                user
Base Distinguished Name:  ou=people,dc=company,dc=com
LDAP Search Timeout:      60
Bind Password:            Set
LDAP Servers:             ldap://company.com:389 ldaps://company2.com:636
CERTS:                   cacert.pem
```

EXAMPLE 6 Testing the LDAP connection

```
XSCF> setldap -t jsmith
company.com:389 PASSED
```

setldap(8)

EXIT STATUS	The following exit values are returned:
	0 Successful completion.
	>0 An error occurred.
SEE ALSO	showldap (8)

NAME	setlocale - set the default locale of the XSCF
SYNOPSIS	<p>setlocale -s <i>locale</i></p> <p>setlocale -h</p>
DESCRIPTION	<p>The setlocale(8) command sets the default locale of the XSCF.</p> <p>The locale that can be set is English or Japanese.</p>
Privileges	<p>You must have platadm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p>-h Displays usage statement. When used with other options or operands, an error occurs.</p> <p>-s <i>locale</i> Specifies the default locale of the XSCF. Either of the following can be specified for <i>locale</i>:</p> <p style="padding-left: 40px;">C Sets the locale for English.</p> <p style="padding-left: 40px;">ja_JP.UTF-8 Sets the locale for Japanese.</p>
EXTENDED DESCRIPTION	<ul style="list-style-type: none"> ■ The specified locale becomes effective after the subsequent login. ■ The currently set locale can be checked by using the showlocale(8) command.
EXAMPLES	<p>EXAMPLE 1 Sets the XSCF default locale for English.</p> <pre>XSCF> setlocale -s C C</pre> <p>EXAMPLE 2 Sets the XSCF default locale for Japanese.</p> <pre>XSCF> setlocale -s ja_JP.UTF-8 ja_JP.UTF-8</pre>
EXIT STATUS	<p>The following exit values are returned:</p> <p>0 Successful completion.</p> <p>>0 An error occurred.</p>
SEE ALSO	showlocale (8)

setlocale(8)



NAME	setlocator - control the blinking of the CHECK LED on the operator panel						
SYNOPSIS	setlocator <i>value</i> setlocator -h						
DESCRIPTION	<p>setlocator(8) command controls the blink state of the CHECK LED on the operator panel.</p> <p>The following states can be set:</p> <table border="0"> <tr> <td>Start blinking</td> <td>Makes the CHECK LED blink.</td> </tr> <tr> <td>Stop blinking</td> <td>Stops the blinking of the CHECK LED.</td> </tr> </table>	Start blinking	Makes the CHECK LED blink.	Stop blinking	Stops the blinking of the CHECK LED.		
Start blinking	Makes the CHECK LED blink.						
Stop blinking	Stops the blinking of the CHECK LED.						
Privileges	<p>You must have platadm or fieldeng privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>						
OPTIONS	<p>The following option is supported:</p> <table border="0"> <tr> <td>-h</td> <td>Displays usage statement. When used with other options or operands, an error occurs.</td> </tr> </table>	-h	Displays usage statement. When used with other options or operands, an error occurs.				
-h	Displays usage statement. When used with other options or operands, an error occurs.						
OPERANDS	<p>The following operand is supported:</p> <table border="0"> <tr> <td><i>value</i></td> <td>Specifies the CHECK LED state. One of the following can be specified:</td> </tr> <tr> <td>blink</td> <td>Starts the CHECK LED blinking.</td> </tr> <tr> <td>reset</td> <td>Stops the CHECK LED blinking.</td> </tr> </table>	<i>value</i>	Specifies the CHECK LED state. One of the following can be specified:	blink	Starts the CHECK LED blinking.	reset	Stops the CHECK LED blinking.
<i>value</i>	Specifies the CHECK LED state. One of the following can be specified:						
blink	Starts the CHECK LED blinking.						
reset	Stops the CHECK LED blinking.						
EXTENDED DESCRIPTION	The showlocator(8) command can be used to check the CHECK LED state.						
EXAMPLES	<p>EXAMPLE 1 Starts the CHECK LED blinking.</p> <pre>XSCF> setlocator blink</pre> <p>EXAMPLE 2 Stops the CHECK LED blinking.</p> <pre>XSCF> setlocator reset</pre>						

setlocator(8)

EXIT STATUS	The following exit values are returned:
	0 Successful completion.
	>0 An error occurred.
SEE ALSO	showlocator (8)

NAME	setlookup - enable or disable the use of the Lightweight Directory Access Protocol (LDAP) server for authentication and privilege lookup								
SYNOPSIS	<pre>setlookup -a {local ldap} setlookup -p {local ldap} setlookup -h</pre>								
DESCRIPTION	setlookup(8) sets whether authentication and privileges data are looked up in LDAP or not.								
Privileges	<p>You must have useradm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>								
OPTIONS	<p>The following options are supported:</p> <table border="0"> <tr> <td style="vertical-align: top;">-a</td> <td>Sets the authentication lookup. Used with one of the required operands ldap or local.</td> </tr> <tr> <td style="vertical-align: top;">-h</td> <td>Displays usage statement.</td> </tr> <tr> <td></td> <td>When used with other options or operands, an error occurs.</td> </tr> <tr> <td style="vertical-align: top;">-p</td> <td>Sets privileges lookup. Used with one of the required operands ldap or local.</td> </tr> </table>	-a	Sets the authentication lookup. Used with one of the required operands ldap or local.	-h	Displays usage statement.		When used with other options or operands, an error occurs.	-p	Sets privileges lookup. Used with one of the required operands ldap or local.
-a	Sets the authentication lookup. Used with one of the required operands ldap or local.								
-h	Displays usage statement.								
	When used with other options or operands, an error occurs.								
-p	Sets privileges lookup. Used with one of the required operands ldap or local.								
OPERANDS	<p>The following operands are supported:</p> <table border="0"> <tr> <td style="vertical-align: top;">ldap</td> <td>Used with the -a and -p options. When set to ldap, authentication or privileges are first looked up locally and then in LDAP if not found locally.</td> </tr> <tr> <td style="vertical-align: top;">local</td> <td>Used with the -a and -p options. When set to local, authentication or privileges are looked up only locally.</td> </tr> </table>	ldap	Used with the -a and -p options. When set to ldap, authentication or privileges are first looked up locally and then in LDAP if not found locally.	local	Used with the -a and -p options. When set to local, authentication or privileges are looked up only locally.				
ldap	Used with the -a and -p options. When set to ldap, authentication or privileges are first looked up locally and then in LDAP if not found locally.								
local	Used with the -a and -p options. When set to local, authentication or privileges are looked up only locally.								
EXAMPLES	<p>EXAMPLE 1 Enabling LDAP Lookup of Privilege Data</p> <pre>XSCF> setlookup -p ldap</pre>								
EXIT STATUS	<p>The following exit values are returned:</p> <table border="0"> <tr> <td style="vertical-align: top;">0</td> <td>Successful completion.</td> </tr> <tr> <td style="vertical-align: top;">>0</td> <td>An error occurred.</td> </tr> </table>	0	Successful completion.	>0	An error occurred.				
0	Successful completion.								
>0	An error occurred.								

setlookup(8)

SEE ALSO | **showlookup (8)**

NAME	setnameserver - set the domain name system (DNS) servers used in the XSCF network
SYNOPSIS	<p>setnameserver [-c add] <i>address</i> ...</p> <p>setnameserver -c del <i>address</i> ...</p> <p>setnameserver -c del -a</p> <p>setnameserver -h</p>
DESCRIPTION	<p>setnameserver(8) command specifies the DNS servers used in the XSCF network.</p> <p>Up to three DNS servers can be registered for XSCF. Any attempt to register four or more DNS servers causes an error.</p>
Privileges	<p>You must have platadm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p>-a Deletes all the DNS servers that are currently registered. This option is used with the "-c del".</p> <p>-c add Adds the host with the specified IP address as a DNS server. This option is used together with <i>address</i>. If the -c option is omitted, "-c add" is assumed specified. When a DNS server is registered, the existing setting is deleted, and overwriting is performed with the specified address.</p> <p>-c del Deletes the host with the specified IP address from the DNS servers that are set. If the -c option is omitted, "-c add" is assumed specified.</p> <p>-h Displays usage statement. When used with other options or operands, an error occurs.</p>
OPERANDS	<p>The following operand is supported:</p> <p>address Specifies the IP address of a DNS server to be added or deleted using four sets of integers. Up to three addresses delimited by the space can be specified. The following <i>address</i> form is accepted:</p> <p style="margin-left: 40px;"><i>xxx.xxx.xxx.xxx</i></p> <p style="margin-left: 40px;"><i>xxx</i> An integer from 0–255. Zero suppression can be used to specify the integer.</p>

setnameserver(8)

EXTENDED DESCRIPTION

- If multiple DNS servers are specified, names are solved in the order specified.
- To reflect the DNS server name to XSCF, execute the `applynetwork(8)` command. After reflected the information, use the `rebootxscf(8)` command to reset XSCF to complete the setting.
- The currently set DNS server can be checked by using the `shownameserver(8)` command.

EXAMPLES

EXAMPLE 1 Adds the hosts with the IP addresses 192.168.1.2, 10.18.108.10, and 10.24.1.2 as DNS server. Names are solved in the order specified.

```
XSCF> setnameserver 192.168.1.2 10.18.108.10 10.24.1.2
```

EXAMPLE 2 Deletes the host with the IP address 10.18.108.10 from the DNS server.

```
XSCF> setnameserver -c del 10.18.108.10
```

EXAMPLE 3 Deletes all the DNS servers.

```
XSCF> setnameserver -c del -a
```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

`rebootxscf(8)`, `shownameserver(8)`

NAME	setnetwork - sets or removes an XSCF network interface
SYNOPSIS	<p>setnetwork [-m <i>addr</i>] <i>interface address</i></p> <p>setnetwork -c {up down} <i>interface</i></p> <p>setnetwork [[-q] -{y n}] -r <i>interface</i></p> <p>setnetwork -h</p>
DESCRIPTION	<p>setnetwork(8) command sets or removes an XSCF network interface.</p> <p>The following settings can be made for the specified network interface:</p> <ul style="list-style-type: none"> ■ Whether to enable or disable the network interface. ■ IP address ■ Netmask <p>When you set an IP address or netmask, the specified network interface will be enabled at the same time as the setting.</p> <p>When you removed the netmask interface, the specified network interface will be disabled at the same time as the removal. And when the routing information is set to the target network interface, it will be removed together.</p>
Privileges	<p>You must have platadm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>

OPTIONS

The following options are supported:

- c {up|down}** Specifies whether to enable the specified network interface. One of the following values can be specified. If none of them is specified, an error occurs.
- up Enables the network interface.
- down Disables the network interface.
- h** Displays usage statement. When used with other options or operands, an error occurs.
- m *addr*** Specifies a netmask. The following *addr* form is accepted:
- xxx.xxx.xxx.xxx*
- xxx* An integer from 0–255. Zero suppression can be used to specify the integer.
- If the **-m** option is omitted, one of the following netmask corresponding to *address* is set.
- class A: 255.0.0.0
 - class B: 255.255.0.0
 - class C: 255.255.255.0
- n** Automatically answers "n" (no) to all prompts.
- q** Suppresses all messages to stdout, including prompts.
- r** Removes the IP address and netmask of the network interface.
- y** Automatically answers "y" (yes) to all prompts.

OPERANDS

The following operands are supported:

- address*** Specifies an IP address. The specified value is a set of four integer values delimited by the "." (period). The following *address* form is accepted:
- xxx.xxx.xxx.xxx*
- xxx* An integer from 0–255. Zero suppression can be used to specify the integer.
- When you specify the loopback address (127.0.0.0/8), it results in errors.

interface

Specifies the network interface to be configured. One of the following values can be specified:

- In the M3000/M4000/M5000 servers:

For XSCF unit 0:

xscf#0-lan#0 XSCF-LAN#0

xscf#0-lan#1 XSCF-LAN#1

For abbreviation:

lan#0 an abbreviation of XSCF-LAN#0

lan#1 an abbreviation of XSCF-LAN#1

- In the M8000/M9000 servers:

When you specify the `-c` or `-r` option and Inter SCF Network (ISN) together, it results in errors.

For XSCF unit 0:

xscf#0-lan#0 XSCF-LAN#0

xscf#0-lan#1 XSCF-LAN#1

xscf#0-if ISN

For XSCF unit 1 :

xscf#1-lan#0 XSCF-LAN#0

xscf#1-lan#1 XSCF-LAN#1

xscf#1-if ISN

For takeover IP address:

lan#0 takeover IP address for XSCF-LAN#0

lan#1 takeover IP address for XSCF-LAN#1

EXTENDED DESCRIPTION

- In the M8000/M9000 servers, a takeover IP address can be used without a need to determine whether XSCF has been switched. By setting the LAN ports of the active XSCF unit as `lan#0` and `lan#1`, they can be accessed with the names `lan#0` and `lan#1`.
- In the M3000/M4000/M5000 servers, the value of the `lan#0` is fixed with `xscf#0-lan#0`, and the `lan#1` is fixed with `xscf#0-lan#1`.

- After you set the network interface, if you disable that network interface and execute the `applynetwork(8)` command, the setting data of IP address and netmask will be stored in XSCF. When you enable the network interface, the setting of IP address and netmask will be used.
- In the following cases, the `setnetwork(8)` command results in an error:
 - When specified the same subnet in `XSCF-LAN#0` and `XSCF-LAN#1`
 - When specified the same IP address as DSCP
 - When specified a subnet which overlaps with DSCP
 - When specified the overlapped subnets in ISN and in other network interface
 - When specified the `-c` or `-r` option and ISN together
- In case you specified the IP address and the netmask to the interfaces other than ISN and when the ISN is not configured, the following default value will be set:
 - `xscf#0-if`:
IP address: 192.168.1.1 Netmask: 255.255.255.0
 - `xscf#1-if`:
IP address: 192.168.1.2 Netmask: 255.255.255.0
- The `shownetwork(8)` command can display current information on a network interface configured for XSCF.
- To reflect information on the specified network interface, execute the `applynetwork(8)` command and reset XSCF.

EXAMPLES

EXAMPLE 1 Sets the IP address 192.168.10.10 and netmask 255.255.255.0 for XSCF-LAN#0 on XSCF unit 0.

```
XSCF> setnetwork xscf#0-lan#0 -m 255.255.255.0 192.168.10.10
```

EXAMPLE 2 Sets the IP address 192.168.10.10 and netmask 255.255.255.0 for XSCF-LAN#0 on XSCF unit 0 in the M3000/M4000/M5000 server.

```
XSCF> setnetwork lan#0 -m 255.255.255.0 192.168.10.10
```

EXAMPLE 3 Disables XSCF-LAN#1 on XSCF unit 0.

```
XSCF> setnetwork xscf#0-lan#1 -c down
```

EXAMPLE 4 Sets the IP address 192.168.10.128 on ISN on the XSCF unit 0. By default, 255.255.255.0 is set for the netmask.

```
XSCF> setnetwork xscf#0-if 192.168.10.128
```

EXAMPLE 5 Sets the IP address 192.168.11.10 and netmask 255.255.255.0 for XSCF-LAN#0

on XSCF unit 1.

```
XSCF> setnetwork xscf#1-lan#0 -m 255.255.255.0 192.168.11.10
```

EXAMPLE 6 Sets the IP address 192.168.1.10 and netmask 255.255.255.0 for the takeover IP address of XSCF-LAN#0.

```
XSCF> setnetwork lan#0 -m 255.255.255.0 192.168.1.10
```

EXAMPLE 7 Removes the IP address and netmask that set in XSCF-LAN#0 on XSCF unit 0

```
XSCF> setnetwork -r xscf#0-lan#0
```

You specified '-r' interface remove option.

So, we delete routing information that interface corresponds.

Continue? [y|n] :y

If you choose 'y'es, you must execute 'applynetwork' command for application.

Or you choose 'y'es, but you don't want to apply, you execute 'rebootxscf' for reboot.

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

applynetwork(8), **shownetwork(8)**

setnetwork(8)



NAME	setntp - set the NTP information for XSCF												
SYNOPSIS	<pre>setntp [-c add] address ...</pre> <pre>setntp -c del address ...</pre> <pre>setntp -c del -a</pre> <pre>setntp -c stratum -i stratum_no</pre> <pre>setntp -h</pre>												
DESCRIPTION	<p>setntp(8) command sets the NTP information for XSCF.</p> <p>The setntp(8) command can specify the following information:</p> <ul style="list-style-type: none"> ■ The NTP servers which are used on the XSCF network. Up to three NTP servers can be registered for the XSCF network. Any attempt to register four or more servers causes an error. ■ The stratum value which has been set to XSCF. 												
Privileges	<p>You must have platadm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>												
OPTIONS	<p>The following options are supported:</p> <table border="0" style="width: 100%;"> <tr> <td style="vertical-align: top; padding-right: 20px;">-a</td> <td>Deletes all the NTP servers that are currently registered. This option is used with the "-c del".</td> </tr> <tr> <td style="vertical-align: top; padding-right: 20px;">-c add</td> <td>Adds the host with the specified address or the host as an NTP server. This option is used together with <i>address</i>. If the -c option is omitted, "-c add" is used. When an NTP server is registered, the existing setting is deleted and overwriting is performed with the specified <i>address</i>.</td> </tr> <tr> <td style="vertical-align: top; padding-right: 20px;">-c del</td> <td>Deletes the host with the specified address or the host from the NTP servers. If the -c option is omitted, "-c add" is assumed specified.</td> </tr> <tr> <td style="vertical-align: top; padding-right: 20px;">-c stratum</td> <td>Sets the stratum value in case you regard XSCF as an NTP server.</td> </tr> <tr> <td style="vertical-align: top; padding-right: 20px;">-h</td> <td>Displays usage statement. When used with other options or operands, an error occurs.</td> </tr> <tr> <td style="vertical-align: top; padding-right: 20px;">-i stratum_no</td> <td>Specifies the stratum value. This option is used together with the "-c stratum". An integer from 1 to 15 can be specified. If the stratum value not specified, it is 5.</td> </tr> </table>	-a	Deletes all the NTP servers that are currently registered. This option is used with the "-c del".	-c add	Adds the host with the specified address or the host as an NTP server. This option is used together with <i>address</i> . If the -c option is omitted, "-c add" is used. When an NTP server is registered, the existing setting is deleted and overwriting is performed with the specified <i>address</i> .	-c del	Deletes the host with the specified address or the host from the NTP servers. If the -c option is omitted, "-c add" is assumed specified.	-c stratum	Sets the stratum value in case you regard XSCF as an NTP server.	-h	Displays usage statement. When used with other options or operands, an error occurs.	-i stratum_no	Specifies the stratum value. This option is used together with the "-c stratum". An integer from 1 to 15 can be specified. If the stratum value not specified, it is 5.
-a	Deletes all the NTP servers that are currently registered. This option is used with the "-c del".												
-c add	Adds the host with the specified address or the host as an NTP server. This option is used together with <i>address</i> . If the -c option is omitted, "-c add" is used. When an NTP server is registered, the existing setting is deleted and overwriting is performed with the specified <i>address</i> .												
-c del	Deletes the host with the specified address or the host from the NTP servers. If the -c option is omitted, "-c add" is assumed specified.												
-c stratum	Sets the stratum value in case you regard XSCF as an NTP server.												
-h	Displays usage statement. When used with other options or operands, an error occurs.												
-i stratum_no	Specifies the stratum value. This option is used together with the "-c stratum". An integer from 1 to 15 can be specified. If the stratum value not specified, it is 5.												

OPERANDS

The following operands are supported:

address

Specifies the IP address or host name of an NTP server to be added or deleted. Up to three IP addresses or XSCF host names can be specified by delimited the spaces.

A specified IP address is a set of four integer values delimited by the "." (period). The following address form is accepted:

xxx.xxx.xxx.xxx

xxx

An integer from 0–255. Zero suppression can be used to specify the integer.

Do not use the Fully Qualified Domain Name (FQDN) format to specify an XSCF host name, but specify only a host name. The host name can be specified in the format that complies with RFC 1034.

If "-c add" is specified and *address* is omitted, an error occurs.

EXTENDED DESCRIPTION

- If multiple NTP servers are specified, the NTP server specified first has priority over the others.
- In the M8000/M9000 servers, the setting automatically reflected to the standby XSCF. When there's a defect on the standby XSCF, it leads to an error.
- To apply the specified configuration, execute the `rebootxscf(8)` command and reset XSCF.
- After resetting the XSCF, the time of XSCF will be synchronized with the time of NTP server.
- When an NTP server set to XSCF, the time of the domain may be changed. If necessary, set the time of the domain.
- The currently set NTP server can be checked by using the `showntp(8)` command.

EXAMPLES

EXAMPLE 1 Adds the three NTP servers with the addresses 192.168.1.2, 10.18.108.10, and 10.24.1.2.

```
XSCF> setntp 192.168.1.2 10.18.108.10 10.24.1.2
```

Please reset the XSCF by `rebootxscf` to apply the ntp settings.

EXAMPLE 2 Deletes the NTP server 10.18.108.10.

```
XSCF> setntp -c del 10.18.108.10
```

Please reset the XSCF by `rebootxscf` to apply the ntp settings.

EXAMPLE 3 Adds the two NTP servers ntp1.example.com and ntp2.example.com.

```
XSCF> setntp ntp1.example.com ntp2.example.com
```

Please reset the XSCF by `rebootxscf` to apply the ntp settings.

EXAMPLE 4 Sets the stratum value to 7.

```
XSCF> setntp -c stratum -i 7
```

Please reset the XSCF by `rebootxscf` to apply the ntp settings.

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

`rebootxscf(8)`, `showntp(8)`

setntp(8)



NAME	setpasswordpolicy - manage the system password policy
SYNOPSIS	<p>setpasswordpolicy [-d <i>dcredit</i>] [-e <i>expiry</i>] [-i <i>inactive</i>] [-k <i>difok</i>] [-l <i>lcredit</i>] [-M <i>maxdays</i>] [-m <i>minlen</i>] [-n <i>mindays</i>] [-o <i>ocredit</i>] [-r <i>remember</i>] [-u <i>ucredit</i>] [-w <i>warn</i>] [-y <i>retry</i>]</p> <p>setpasswordpolicy -h</p>
DESCRIPTION	<p>setpasswordpolicy(8) allows an administrator to change the system password policy. These policies are enforced by XSCF on the Service Processor. The new password policy applies only to users added after the setpasswordpolicy(8) command is executed.</p> <p>The following parameters control creation of new user accounts: <i>expiry</i>, <i>inactive</i>, <i>maxdays</i>, <i>mindays</i>, and <i>warn</i>. When a user is created, the adduser(8) command uses these parameters as the password expiration settings for the new account. The password(8) command can be used to change the password expiration settings for an existing account.</p>
Privileges	<p>You must have useradm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:</p> <ul style="list-style-type: none"> -d <i>dcredit</i> Sets maximum number of digits in a password. Each digit counts as one <i>credit</i>. The minimum acceptable password length is decreased by one for each digit in the password, up to <i>dcredit</i> digits. Valid values are integers with value of zero or greater. The initial setting is 1. -e <i>expiry</i> Sets the number of days a new account will be valid before expiring and becoming disabled. This value is assigned to new user accounts when they are created. The initial value is 0. A zero means that the account will not expire. Valid values are integers with value of zero or greater. -h Displays usage statement. When used with other options or operands, an error occurs. -i <i>inactive</i> Sets the number of days after a password expires until the account is locked. This value is assigned to new user accounts when they are created. The initial value is -1. A value of -1 means that the account will not be locked after the password expires. Valid values are integers with value of -1 or greater.

- k *difok*** Sets the minimum number of new characters (characters which were not present in the old password) that a new password must contain. The initial setting is 3.
- Valid values are integers with value of zero or greater.
- l *lcredit*** Sets the maximum credit for lower case letters in a password. The minimum acceptable password length is decreased by one for each digit in the password, up to *lcredit* digits.
- Valid values are integers with value of zero or greater. The initial setting is 1.
- M *maxdays*** Sets the maximum number of days that a password is valid. This value is assigned to new user accounts when they are created. The initial value is 999999.
- Valid values are integers with value of zero or greater.
- m *minlen*** Sets the minimum size for a new password.
- Note** – *minlen* cannot be set less than 6.
- Valid values are integers with value of 6 or greater.
- n *mindays*** Sets the minimum number of days between password changes. An initial value of zero for this field indicates that you can change the password at any time.
- Valid values are integers with value of zero or greater.
- o *ocredit*** Sets the maximum credit for nonalphanumeric characters in a password. The minimum acceptable password length is decreased by one for each digit in the password, up to *ocredit* digits.
- Valid values are integers with value of zero or greater. The initial setting is 1.
- r *remember*** Sets the number of passwords remembered in the password history.
- The maximum valid value is 10. The initial setting is 3.

- `-u ucredit` Sets the maximum credit for uppercase letters in a password. The minimum acceptable password length is decreased by one for each digit in the password, up to *ucredit* digits.
- The initial setting is 1.
- `-w warn` Sets the default number of days before password expiration at which to start warning the user. This value is assigned to new user accounts when they are created. The initial value is 7.
- Valid values are integers with value of zero or greater.
- `-y retry` Sets the number of retries permitted when using the password command to change the password for a user account. The initial value is 3.
- Valid values are integers with value of zero or greater.

EXAMPLES

EXAMPLE 1 Setting the Minimum Size and Number of Passwords Remembered

```
XSCF> setpasswordpolicy -m 12 -r 5
```

EXAMPLE 2 Setting Minimum Password Length and Maximum Credits

```
XSCF> setpasswordpolicy -m 10 -d 1 -u 0 -l 0 -o 1
```

After running this command, the minimum password length for new passwords is 10 characters. A password of 9 characters is accepted if it contains at least one digit or nonalphanumeric character. A password of 8 characters is accepted if it contains a digit and a nonalphanumeric character.

EXIT STATUS

The following exit values are returned:

- 0 Successful completion.
- >0 An error occurred.

SEE ALSO

`adduser(8)`, `password(8)`, `showpasswordpolicy(8)`

setpasswordpolicy(8)



NAME	setpowerupdelay - set the warm-up time of the system and wait time before system startup								
SYNOPSIS	<p>setpowerupdelay -c warmup -s <i>time</i></p> <p>setpowerupdelay -c wait -s <i>time</i></p> <p>setpowerupdelay -h</p>								
DESCRIPTION	<p>The setpowerupdelay(8) command sets the warm-up time of the system and wait time before system startup.</p> <p>The wait time before system startup can be used to control the system startup time so that the system is started only after air-conditioning makes the temperature of the computer room suitable. If the system power has already been turned on and the system is operating, the setting takes effect at the next startup.</p>								
Privileges	<p>You must have platadm or fieldeng privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>								
OPTIONS	<p>The following options are supported:</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;">-c warmup</td> <td>Specifies the warm-up time.</td> </tr> <tr> <td style="padding-right: 20px;">-c wait</td> <td>Specifies the wait time before system startup.</td> </tr> <tr> <td style="padding-right: 20px;">-h</td> <td>Displays usage statement. When used with other options or operands, an error occurs.</td> </tr> <tr> <td style="padding-right: 20px;">-s <i>time</i></td> <td>Specifies the warm-up time or wait time before system startup in minutes. An integer ranging from 0 to 255 can be specified for time.</td> </tr> </table>	-c warmup	Specifies the warm-up time.	-c wait	Specifies the wait time before system startup.	-h	Displays usage statement. When used with other options or operands, an error occurs.	-s <i>time</i>	Specifies the warm-up time or wait time before system startup in minutes. An integer ranging from 0 to 255 can be specified for time.
-c warmup	Specifies the warm-up time.								
-c wait	Specifies the wait time before system startup.								
-h	Displays usage statement. When used with other options or operands, an error occurs.								
-s <i>time</i>	Specifies the warm-up time or wait time before system startup in minutes. An integer ranging from 0 to 255 can be specified for time.								
EXTENDED DESCRIPTION	<ul style="list-style-type: none"> ■ The currently set warm-up time and wait time before system startup can be checked by using the showpowerupdelay(8) command. ■ When the power is turned on from the operator panel, the wait time and warm-up time that you set are ignored. If you have set these times and wish to observe them at startup, perform the poweron(8) command. 								
EXAMPLES	<p>EXAMPLE 1 Sets the warm-up time to 10 minutes.</p> <pre style="margin-left: 20px;">XSCF> setpowerupdelay -c warmup -s 10</pre> <p>EXAMPLE 2 Sets the wait time before system startup to 20 minutes.</p> <pre style="margin-left: 20px;">XSCF> setpowerupdelay -c wait -s 20</pre>								

setpowerupdelay(8)

EXIT STATUS	The following exit values are returned:
0	Successful completion.
>0	An error occurred.
SEE ALSO	showpowerupdelay (8)

NAME	setprivileges - assign user privileges
SYNOPSIS	setprivileges <i>user</i> [<i>privileges</i>] [<i>domainprivilege@ domains</i>] setprivileges -h
DESCRIPTION	<p>setprivileges(8) assigns privileges to an XSCF user. setprivileges modifies only local privileges data. Multiple privileges are separated by one or more spaces. There is a maximum of 100 unique users to whom privileges can be assigned. Each of the 100 unique user can be assigned more than one privilege. A list of privileges can be found in the OPERANDS section.</p> <p>The privileges <i>domainop</i>, <i>domainmgr</i>, and <i>domainadm</i> must be assigned to a specific domain. Other privileges do not have this ability. Refer to the OPERANDS section and EXAMPLE 1 for details.</p> <p>If no privileges are specified, setprivileges deletes any local privilege data for the specified user. Subsequently, the user's privilege data is looked up in Lightweight Directory Access Protocol (LDAP), if LDAP privilege lookup is enabled.</p> <p>If the none privilege is specified, the specified user does not have any privileges, regardless of privilege data in LDAP.</p>
Privileges	You must have <i>useradm</i> privileges to run this command.
OPTIONS	<p>The following option is supported:</p> <p>-h Displays usage statement.</p> <p> When used with other options or operands, an error occurs.</p>

OPERANDS

The following operands are supported:

domainprivilege@domains

Specifies `domainadm`, `domainmgr`, or `domainop` privileges for a specific domain or domains.

The following are valid values for *domainprivilege*, each of which must be used with *@domains*:

<code>domainadm</code>	Can perform all operations and view status on the hardware assigned to the domains on which this privilege is held (assign, unassign, power, and so on). Can perform all operations on domains on which this privilege is held. Can view all states of domains on which this privilege is held.
<code>domainmgr</code>	Can reboot and power on and off all domains on which this privilege is held. Can view all states of all hardware assigned to the domains on which this privilege is held. Can view all states of domains on which this privilege is held.
<code>domainop</code>	Can view all states of all the hardware assigned to the domains on which this privilege is held. Can view all states of all domains on which this privilege is held.
<i>domains</i>	Specifies a domain or domains, using the appropriate value for <i>domainprivilege</i> with the @ symbol and the <i>domains</i> descriptor: To specify a single domain, use the @ symbol followed by a single domain number. Example: <code>domainadm@3</code> . To specify a range of domains, use a "-" to indicate to start and end of the domains in the range, inclusive. Example: <code>domainadm@3-4</code> . To specify multiple single domains and multiple domain ranges, separate the domains or domain ranges with commas. Do not repeat domains or cause them to overlap or an error will result. Example: <code>domainadm@1-2, 4</code> .

privileges

The following are valid values for *privileges*:

auditadm	Can configure auditing. Can delete audit trail.
auditop	Can view all audit state and audit trail.
fieldeng	Can perform all operations reserved for field engineers and authorized service personnel.
none	Cannot perform any operations on the Service Processor that require privilege, even if privileges are set for the user in LDAP. This privilege allows the administrator to restrict access to such operations on the Service Processor and domains.
platadm	Can perform all Service Processor configuration other than the useradm and auditadm tasks. Can assign and unassign hardware from domains, perform domain and XSCF power operations and all operations on domain hardware (assign, unassign, power, and so on). Can perform Service Processor failover operations and view all platform states.
platop	Can view all platform states but not perform any modifications.
useradm	Can create, delete, disable, or enable user accounts. Can change a user's password and password properties (for example, <i>expiry</i>). Can modify a user's privileges.

user

Specifies a valid user name.

EXAMPLES

EXAMPLE 1 Setting Privileges for JSmith

```
XSCF> setprivileges jsmith platadm domainadm@1-4,6,9
```

EXAMPLE 2 Removing All Privileges for JSmith

```
XSCF> setprivileges jsmith none
```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

setprivileges(8)

SEE ALSO | **setpasswordpolicy**(8), **showuser**(8)

NAME	setroute - set routing information for an XSCF network interface												
SYNOPSIS	setroute -c {add del} -n <i>address</i> [-m <i>address</i>] [-g <i>address</i>] <i>interface</i> setroute -h												
DESCRIPTION	<code>setroute(8)</code> command sets routing information for an XSCF network interface. Up to eight routing information items can be registered for each network interface. Any attempt to register more than eight items causes an error.												
Privileges	You must have <code>platadm</code> privilege to run this command. Refer to <code>setprivileges(8)</code> for more information.												
OPTIONS	The following options are supported: <table border="0" style="margin-left: 20px;"> <tr> <td style="vertical-align: top; padding-right: 10px;">-c {add del}</td> <td>Specifies a function for routing information. One of the following values can be specified. If none of them is specified, an error occurs.</td> </tr> <tr> <td style="padding-left: 40px;">add</td> <td>Adds routing information.</td> </tr> <tr> <td style="padding-left: 40px;">del</td> <td>Deletes routing information.</td> </tr> <tr> <td style="vertical-align: top; padding-right: 10px;">-g <i>address</i></td> <td>Specifies a gateway address used for routing. The specified value of <i>address</i> is a set of four integer values delimited by the "." (period). If this option is omitted, the gateway address is not set. The following <i>address</i> form is accepted: <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-left: 40px;"><i>xxx.xxx.xxx.xxx</i></td> <td></td> </tr> <tr> <td style="padding-left: 40px;"><i>xxx</i></td> <td>An integer from 0–255. Zero suppression can be used to specify the integer.</td> </tr> </table> </td> </tr> </table>	-c {add del}	Specifies a function for routing information. One of the following values can be specified. If none of them is specified, an error occurs.	add	Adds routing information.	del	Deletes routing information.	-g <i>address</i>	Specifies a gateway address used for routing. The specified value of <i>address</i> is a set of four integer values delimited by the "." (period). If this option is omitted, the gateway address is not set. The following <i>address</i> form is accepted: <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-left: 40px;"><i>xxx.xxx.xxx.xxx</i></td> <td></td> </tr> <tr> <td style="padding-left: 40px;"><i>xxx</i></td> <td>An integer from 0–255. Zero suppression can be used to specify the integer.</td> </tr> </table>	<i>xxx.xxx.xxx.xxx</i>		<i>xxx</i>	An integer from 0–255. Zero suppression can be used to specify the integer.
-c {add del}	Specifies a function for routing information. One of the following values can be specified. If none of them is specified, an error occurs.												
add	Adds routing information.												
del	Deletes routing information.												
-g <i>address</i>	Specifies a gateway address used for routing. The specified value of <i>address</i> is a set of four integer values delimited by the "." (period). If this option is omitted, the gateway address is not set. The following <i>address</i> form is accepted: <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-left: 40px;"><i>xxx.xxx.xxx.xxx</i></td> <td></td> </tr> <tr> <td style="padding-left: 40px;"><i>xxx</i></td> <td>An integer from 0–255. Zero suppression can be used to specify the integer.</td> </tr> </table>	<i>xxx.xxx.xxx.xxx</i>		<i>xxx</i>	An integer from 0–255. Zero suppression can be used to specify the integer.								
<i>xxx.xxx.xxx.xxx</i>													
<i>xxx</i>	An integer from 0–255. Zero suppression can be used to specify the integer.												

- h** Displays usage statement. When used with other options or operands, an error occurs.
- m *address*** Specifies the netmask to which routing information is forwarded. The specified value is a set of four integer values delimited by the "." (period). The following *address* form is accepted:
- ```
xxx.xxx.xxx.xxx
```
- xxx* An integer from 0–255. Zero suppression can be used to specify the integer.
- If the **-m** option is omitted and the **-n** option is used to specify the network address (containing "0" in the default host address which depends on the class), the following netmask value is set, according to the class of the network address:
- | class | Mask value    |
|-------|---------------|
| A     | 255.0.0.0     |
| B     | 255.255.0.0   |
| C     | 255.255.255.0 |
- If the **-m** option is omitted and the host address specified by the **-n** option, netmask is not set.
- If "0.0.0.0" specified by the **-n** option, netmask is invalid.
- n *address*** Specifies an IP address to which routing information is forwarded. The specified value is a set of four integer values delimited by the "." (period). The following *address* form is accepted:
- ```
xxx.xxx.xxx.xxx
```
- xxx* An integer from 0–255. Zero suppression can be used to specify the integer.
- If "0.0.0.0" is specified for *address*, the default routing information can be set.

OPERANDS The following operand is supported:

interface Specifies the network interface to be set with routing information. One of the following values can be specified:

- In the M3000/M4000/M5000 servers:

For XSCF unit 0:

xscf#0-lan#0 XSCF-LAN#0

xscf#0-lan#1 XSCF-LAN#1

For abbreviation:

lan#0 XSCF-LAN#0

lan#1 XSCF-LAN#1

- In the M8000/M9000 servers:

For XSCF unit 0:

xscf#0-lan#0 XSCF-LAN#0

xscf#0-lan#1 XSCF-LAN#1

For XSCF unit 1:

xscf#1-lan#0 XSCF-LAN#0

xscf#1-lan#1 XSCF-LAN#1

EXTENDED DESCRIPTION

- If the specified address is the same as the DSCP address, an error occurs.
- For XSCF-LAN#0 and XSCF-LAN#1, do not set the routing to the same network or the same host.
- To reflect the routing information to XSCF, execute the `applynetwork(8)` command. After reflected the information, use the `rebootxscf(8)` command to reset XSCF to complete the setting.
- The `showroute(8)` command can display the current routing information that is set for the XSCF network.

EXAMPLES

EXAMPLE 1 Adds the routing of destination 192.168.1.0 and netmask 255.255.255.0 for XSCF-LAN#0 on XSCF unit 0.

```
XSCF> setroute -c add -n 192.168.1.0 -m 255.255.255.0 xscf#0-lan#0
```

EXAMPLE 2 Adds the routing of destination 192.168.1.0 and gateway 192.168.1.1 for

XSCF-LAN#1 on XSCF unit 0.

```
XSCF> setroute -c add -n 192.168.1.0 -g 192.168.1.1 xscf#0-lan#1
```

EXAMPLE 3 Adds the routing of destination 192.168.1.0 and default netmask (255.255.255.0) for XSCF-LAN#1 on XSCF unit 0.

```
XSCF> setroute -c add -n 192.168.1.0 xscf#0-lan#1
```

EXAMPLE 4 Deletes the routing of destination 192.168.1.0 and default netmask (255.255.255.0) from XSCF-LAN#1 on XSCF unit 0.

```
XSCF> setroute -c del -n 192.168.1.0 -m 255.255.255.0 xscf#0-lan#1
```

EXAMPLE 5 Adds the routing of destination 192.168.1.4 for XSCF-LAN#1 on XSCF unit 0.

```
XSCF> setroute -c add -n 192.168.1.4 xscf#0-lan#1
```

EXAMPLE 6 Deletes the routing of destination 192.168.1.4 from XSCF-LAN#1 on XSCF unit 0.

```
XSCF> setroute -c del -n 192.168.1.4 xscf#0-lan#1
```

EXAMPLE 7 Adds routing information for the default gateway 192.168.10.1 for XSCF-LAN#1 on XSCF unit 0.

```
XSCF> setroute -c add -n 0.0.0.0 -g 192.168.10.1 xscf#0-lan#1
```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

`applynetwork(8)`, `rebootxscf(8)`, `showroute(8)`

NAME	setshutdowndelay - set the shutdown wait time at power interruption of the uninterruptible power supply (UPS)
SYNOPSIS	setshutdowndelay -s <i>time</i> setshutdowndelay -h
DESCRIPTION	The <code>setshutdowndelay(8)</code> command sets the wait time before the start of system shutdown for when power interruption occurs in a system connected to the UPS. The start of system shutdown can be delayed until the specified time. When power recovery is reported from the UPS within the specified time, shutdown will not occur.
Privileges	You must have <code>platadm</code> or <code>fieldeng</code> privileges to run this command. Refer to <code>setprivileges(8)</code> for more information.
OPTIONS	The following options are supported: -h Displays usage statement. When used with other options or operands, an error occurs. -s <i>time</i> Specifies the wait time before the start of shutdown in units of seconds. Specify an integer number ranging from 0 to 9999 for <i>time</i> . The default value is 10 seconds.
EXTENDED DESCRIPTION	The currently set wait time can be displayed by using the <code>showshutdowndelay(8)</code> command.
EXAMPLES	EXAMPLE 1 Sets 600 seconds as the wait time before the start of shutdown. XSCF> setshutdowndelay -s 600
EXIT STATUS	The following exit values are returned: 0 Successful completion. >0 An error occurred.
SEE ALSO	showshutdowndelay (8)

setshutdowndelay(8)



NAME	setsmtp - set up the Simple Mail Transfer Protocol (SMTP) settings
SYNOPSIS	setsmtp [-v] setsmtp [-s <i>variable= value</i>]... setsmtp -h
DESCRIPTION	<p>setsmtp(8) sets up the SMTP configuration values.</p> <p>When used without options, you will be prompted to provide the name of the SMTP email server to be used. You will also be prompted for the port and the Reply-To address to be used on outgoing email. Make sure that a valid email address is specified here. You can set up SMTP settings noninteractively using the -s option.</p> <p>After you have set up the email server and port have been set up using setsmtp(8), you can use setemailreport(8) to set up email report configuration data and send a test email message.</p>
Privileges	<p>You must have platadm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>

OPTIONS

The following options are supported:

- h** Displays usage statement.
- When used with other options or operands, an error occurs.
- s *variable=value*** Sets SMTP.
- Valid entries for *variable* are:
- mailserver
 - port
 - auth
 - user
 - password
 - replyaddress
- Where:
- auth* is the authentication mechanism.
- user/password* are the smtp mail server authentication.
- Valid auth entries are:
- none
 - pop
 - smtp-auth
- v** Specifies verbose output.

EXAMPLES

EXAMPLE 1 Setting Up Mailserver and No Authentication in Noninteractive Mode

```
XSCF> setsntp -s mailserver=10.4.1.1 -s auth=none
```

EXAMPLE 2 Setting Up Authentication in Noninteractive Mode

```
XSCF> setsntp -s auth=pop -s user=jsmith -s password=*****
```

EXAMPLE 3 Setting Up SMTP Authentication in Interactive Mode

```
XSCF> setsntp
```

```
Mail Server [10.4.1.1]:
```

```
Port [25]:
```

```

Authentication Mechanism [none]: smtp-auth
User Name []: jsmith
Password []: *****
Reply Address [useradm@company.com]:

```

EXAMPLE 4 Setting Up Mailserver With Invalid Authentication Mechanism

```

XSCF> setsmtp
Mail Server [10.4.1.1]:
Port [25]:
Authentication Mechanism [none]: ?
Invalid value '?'. Valid authentication mechanism are: none pop smtp-auth
Authentication Mechanism [none]:
Reply Address [useradm@company.com]:

```

EXIT STATUS The following exit values are returned:

```

0           Successful completion.
>0         An error occurred.

```

SEE ALSO [setemailreport\(8\)](#), [showsmtp\(8\)](#)

setsntp(8)



NAME	setsnmp - manage the SNMP agent														
SYNOPSIS	<pre> setsnmp enable [<i>mib_name</i>] setsnmp disable [<i>mib_name</i>] setsnmp addtraphost -t <i>type</i> -s <i>community-string</i> [-p <i>trap-port</i>] <i>traphost</i> setsnmp remtraphost -t <i>type</i> <i>traphost</i> setsnmp addv3traphost -u <i>username</i> -r <i>authentication-protocol</i> {-n <i>engine_id</i> -i} [-a <i>authentication-password</i>] [-e <i>encryption-password</i>] [-p <i>trap-port</i>] <i>traphost</i> setsnmp remv3traphost -u <i>username</i> <i>traphost</i> setsnmp enablev1v2c <i>read-only-community-string</i> setsnmp disablev1v2c setsnmp [-l <i>system-location</i>] [-c <i>system-contact</i>] [-d <i>system-description</i>] [-p <i>agent- port</i>] setsnmp -h </pre>														
DESCRIPTION	setsnmp(8) enables or disables the SNMP Agent, as well as configures the SNMP agent settings.														
Privileges	<p>You must have platadm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>														
OPTIONS	<p>The following options are supported:</p> <table border="0"> <tr> <td style="padding-right: 20px;">-c <i>system-contact</i></td> <td>Specifies the system contact information for the agent.</td> </tr> <tr> <td style="padding-right: 20px;">-d <i>system-description</i></td> <td>Specifies the system description for the agent.</td> </tr> <tr> <td style="padding-right: 20px;">-h</td> <td>Displays usage statement.</td> </tr> <tr> <td></td> <td>When used with other options or operands, an error occurs.</td> </tr> <tr> <td style="padding-right: 20px;">-l <i>system-location</i></td> <td>Specifies the system location for the agent.</td> </tr> <tr> <td style="padding-right: 20px;">-p <i>agent-port</i></td> <td>Specifies the listening port for the agent. The default is 161.</td> </tr> <tr> <td style="padding-right: 20px;">-s <i>community-string</i></td> <td>Acts like a password to control access to the SNMP v1 and v2 agents. It is a clear text string which can be intercepted. For password encryption and no visibility, use addv3traphost instead.</td> </tr> </table>	-c <i>system-contact</i>	Specifies the system contact information for the agent.	-d <i>system-description</i>	Specifies the system description for the agent.	-h	Displays usage statement.		When used with other options or operands, an error occurs.	-l <i>system-location</i>	Specifies the system location for the agent.	-p <i>agent-port</i>	Specifies the listening port for the agent. The default is 161.	-s <i>community-string</i>	Acts like a password to control access to the SNMP v1 and v2 agents. It is a clear text string which can be intercepted. For password encryption and no visibility, use addv3traphost instead.
-c <i>system-contact</i>	Specifies the system contact information for the agent.														
-d <i>system-description</i>	Specifies the system description for the agent.														
-h	Displays usage statement.														
	When used with other options or operands, an error occurs.														
-l <i>system-location</i>	Specifies the system location for the agent.														
-p <i>agent-port</i>	Specifies the listening port for the agent. The default is 161.														
-s <i>community-string</i>	Acts like a password to control access to the SNMP v1 and v2 agents. It is a clear text string which can be intercepted. For password encryption and no visibility, use addv3traphost instead.														

OPERANDS

The following operands are supported:

`addtraphost` Enables the SNMP agent to send the chosen type of trap to the desired host. If no *trap-port* is provided, the default is 162. A community string is mandatory.

`addtraphost` takes the following options and operand:

`-p trap-port` ID of the trap port. Default value is 162.

`-s community-string` Acts like a password to control access to the SNMP v1 and v2 agents. It is a clear text string which can be intercepted. For password encryption and no visibility, use `addv3traphost` instead.

`-t type` Type of trap. Valid trap types are:

`v1` = The agent will send SNMPv1 traps

`v2` = The agent will send SNMPv2 traps

`inform` = The agent will send inform notifications

`traphost` Host name of the trap host.

`addv3traphost` Enables the SNMP agent to send SNMPv3 traps or informs to the desired host. An authentication protocol must be chosen. Valid protocols are:

MD5 = Uses the MD5 algorithm for authentication

SHA = Uses SHA (Secure Hash Algorithm) for authentication

The encryption protocol used in all communication is DES (Data Encryption Standard). If the password option is not used, you will be prompted for a password. Passwords will be read but not echoed to the screen. `addv3traphost` takes the following options:

`-a authentication-password`

Sets the authentication password. Must be equal to or greater than 8 characters.

`-e encryption-password`

Sets the encryption password.

`-i`

Asks for an acknowledgment from the receiving host.

`-n engine_id`

Sets identifier of the local agent sending the trap. It can be the engine ID of the local SNMP agent or not but it must match the engine ID expected by the receiving host. Must start with "0x" and should consist of even hexadecimal characters or you will get an error.

`-p trap-port`

ID of the trap port. Default value is 162.

`-r authentication-protocol`

Sets the authentication protocol.

`traphost`

Host name of the trap host.

`-u username`

Specifies a valid user name.

disable	<p>When used alone, stops the SNMP agent.</p> <p>When used with the value <code>ALL</code> for the optional <code>mib_name</code>, stops the SNMP agent.</p> <p>When used with a value other than <code>ALL</code> for the optional <code>mib_name</code>, removes support for the targeted MIB module. If support remains for another MIB module, the SNMP agent remains enabled. If support for both MIB modules is removed, the SNMP agent is disabled and, therefore, stops. You can specify only one value at a time for <code>mib_name</code>.</p> <p><i>mib_name</i></p> <p style="padding-left: 20px;">Name of the MIB module to be disabled.</p> <p>Valid MIB modules are:</p> <p style="padding-left: 20px;"><code>SP_MIB</code> = XSCF extension MIB</p> <p style="padding-left: 20px;"><code>FM_MIB</code> = Fault Management MIB</p> <p style="padding-left: 20px;"><code>ALL</code> = All the MIB modules in this list.</p>
disablev1v2c	<p>Disables the SNMP agent from communicating using SNMPv1/v2c. These versions provide insecure SNMP communication.</p>
enable	<p>When used alone, activates the SNMP agent with support for all MIB modules.</p> <p>When used with the value <code>ALL</code> for the optional <code>mib_name</code>, activates the SNMP agent with support for all MIB modules.</p> <p>When used with a value other than <code>ALL</code> for the optional <code>mib_name</code>, adds support for the targeted MIB module and, if necessary, activates the SNMP agent. You can specify only one value at a time for <code>mib_name</code>.</p> <p><i>mib_name</i></p> <p style="padding-left: 20px;">Name of the MIB module to be enabled.</p> <p>Valid MIB modules are:</p> <p style="padding-left: 20px;"><code>SP_MIB</code> = XSCF extension MIB</p> <p style="padding-left: 20px;"><code>FM_MIB</code> = Fault Management MIB</p> <p style="padding-left: 20px;"><code>ALL</code> = All the MIB modules in this list.</p>
enablev1v2c	<p>Enables the SNMP agent to communicate using SNMPv1/v2c. These versions provide insecure SNMP communication, which is why the agent runs SNMPv3 by default. This agent is read-only. The only community string asked for is read-only.</p>

remtraphost Disables the SNMP agent from sending the chosen type of trap to the desired host.

-t type

Type of trap. Valid trap types are:

v1 = The agent will send SNMPv1 traps

v2 = The agent will send SNMPv2 traps

inform = The agent will send inform notifications

traphost

Host name of the trap host.

remv3traphost Disables the SNMP agent from sending SNMPv3 traps to the desired host.

traphost

Host name of the trap host.

-u username

Specifies a valid user name.

EXAMPLES

EXAMPLE 1 Setting Up System Information

```
XSCF> setsnmp -l sandiego -c username@company.com -d ff1
```

EXAMPLE 2 Setting Up and SNMPv3 Trap Host With Password Options

```
XSCF> setsnmp addv3traphost -u jsmith -n 0x### -r SHA -a xxxxxxxx
-e yyyyyyyy fiche
```

EXAMPLE 3 Setting Up and SNMPv3 Trap Host without Password Options

```
XSCF> setsnmp addv3traphost -u bob -i -r SHA fiche
```

Authentication Password:

Encryption Password:

EXAMPLE 4 Starting the Agent

```
XSCF> setsnmp enable SP_MIB
```

setsnmp(8)

EXIT STATUS	The following exit values are returned:
	0 Successful completion.
	>0 An error occurred.
SEE ALSO	showsnp (8)

NAME	setsnmpusm - specify the SNMPv3 agent's User-based Security Model (USM) configuration
SYNOPSIS	<p>setsnmpusm create -a <i>authentication_protocol</i> [-p <i>authentication_password</i>] [-e <i>encryption_password</i>] <i>user</i></p> <p>setsnmpusm delete <i>user</i></p> <p>setsnmpusm clone -u <i>clone_user</i> <i>user</i></p> <p>setsnmpusm passwd [-c {auth encrypt}] [-o <i>old_password</i>] [-n <i>new_password</i>] <i>user</i></p> <p>setsnmpusm -h</p>
DESCRIPTION	setsnmpusm(8) modifies the SNMP Agent's USM configuration.
Privileges	<p>You must have platadm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p>-h Displays usage statement.</p> <p> When used with other options or operands, an error occurs.</p>

OPERANDS

The following operands are supported:

<code>clone</code>	Makes the supplied user known to the agent for subsequent SNMP communication with the identical settings as the specified <i>clone_user</i> .
<code>-u clone_user</code>	Specifies a valid user name of the user settings to be cloned.
<code>user</code>	Specifies a different user name for the clone of <i>clone_user</i> .

create	<p>Makes the supplied user known to the agent for subsequent SNMP communication. When used without the <code>-a</code> or <code>-p</code> options, <code>create</code> displays a prompt for passwords and reads them without echoing them to the screen. The encryption protocol used in all SNMP communication is Data Encryption Standard (DES). An authentication protocol must be chosen for SNMP communication. Possible values are MD5 Algorithm and Secure Hash Algorithm (SHA).</p> <p><i>user</i></p> <p>Specifies a valid user name.</p> <p><code>-a authentication_protocol</code></p> <p>Specifies the authentication protocol.</p> <p><code>-e encryption_password</code></p> <p>Specifies the encryption password. Must be equal to or greater than 8 characters.</p> <p><code>-p authentication_password</code></p> <p>Specifies the authentication password. Must be equal to or greater than 8 characters.</p>
delete	<p>Removes the supplied user making the user unknown to the agent for subsequent SNMP communication.</p> <p><i>user</i> Specifies a valid user name.</p>
passwd	<p>Changes the appropriate password for the specified user. The changed password is either the authentication password or the encrypted password, or both, if <code>-c</code> is not used. If <code>-c</code> is not used then both passwords must be the same or an error is generated. With no options, <code>passwd</code> displays a prompt for the passwords and reads them without echoing them to the screen.</p> <p><code>-c auth encrypt</code> Specifies whether to change the authentication password or the encrypted password.</p> <p><code>-n new_password</code> Specifies the new password. The password must be equal to or greater than 8 characters.</p> <p><code>-o old_password</code> Specifies the old password.</p> <p><i>user</i> Specifies a valid user name.</p>

EXAMPLES

EXAMPLE 1 Adding a User With Password Options

```
XSCF> setsnmpusm create -a SHA -p xxxxxxxx -e yyyyyyyy jsmith
```

EXAMPLE 2 Adding a User Without Specifying Password Options

```
XSCF> setsnmpusm create -a SHA bob
```

Authetication Password:

Encryption Password:

EXAMPLE 3 Cloning a User

```
XSCF> setsnmpusm clone -u sue joe
```

Authentication Password:

Encryption Password:

EXAMPLE 4 Deleting a User

```
XSCF> setsnmpusm delete joe
```

EXIT STATUS

The following exit values are returned:

0 Successful completion.

>0 An error occurred.

SEE ALSO

showsnpusm (8)

NAME	setsnmpvacm - modify the SNMPv3 agent's View-based Access Control Model (VACM) configuration
SYNOPSIS	<pre>setsnmpvacm creategroup -u <i>username</i> <i>groupname</i> setsnmpvacm deletegroup -u <i>username</i> <i>groupname</i> setsnmpvacm createview -s <i>OID_subtree</i> [-e] [-m <i>OID_Mask</i>] <i>viewname</i> setsnmpvacm deleteview -s <i>OID_subtree</i> <i>viewname</i> setsnmpvacm createaccess -r <i>read_viewname</i> <i>groupname</i> setsnmpvacm deleteaccess <i>groupname</i> setsnmpvacm -h</pre>
DESCRIPTION	setsnmpvacm(8) modifies the SNMP Agent's VACM configuration. Using this command requires a basic knowledge of SNMP.
Privileges	<p>You must have platadm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p>-h Displays usage statement.</p> <p> When used with other options or operands, an error occurs.</p>

OPERANDS

The following operands are supported:

<code>createaccess</code>	Sets access to a MIB view for the specified group.
<code>-r <i>read_viewname</i></code>	Specifies an SNMP Agent view.
<code><i>groupname</i></code>	Specifies a valid group name.
<code>creategroup</code>	Sets up a group for the specified user for view access.
<code>-u <i>username</i></code>	Specifies a valid user name.
<code><i>groupname</i></code>	Specifies a valid group name.
<code>createview</code>	Sets up a view of the SNMP Agent exported MIB information. View access is limited to read-only for this Agent. The view is identified through a MIB OID subtree and can be limited to specific portions of that subtree using the OID Mask.
<code>-e</code>	Specifies an excluded view. The default is an included view.
<code>-m <i>OID_Mask</i></code>	Specifies a valid OID subtree mask. By default, the mask is <code>ff</code> (entire subtree).
<code>-s <i>OID_subtree</i></code>	Specifies a MIB OID subtree. Values start at <code>.1</code> for the entire MIB tree.
<code><i>viewname</i></code>	Specifies a valid view name.
<code>deleteaccess</code>	Removes access entry.
<code><i>groupname</i></code>	Specifies a valid group name.
<code>deletegroup</code>	Removes a group from use.
<code>-u <i>username</i></code>	Specifies a valid user name.
<code><i>groupname</i></code>	Specifies a valid group name.
<code>deleteview</code>	Removes this view from use.
<code>-s <i>OID_subtree</i></code>	Specifies a MIB OID subtree. Values start at <code>.1</code> for the entire MIB tree.
<code><i>viewname</i></code>	Specifies a valid view name.

EXAMPLES**EXAMPLE 1** Create a Group

```
XSCF> setsnmpvacm creategroup -u jsmith admin
```


EXAMPLE 2 Create a View of the Entire MIB

```
XSCF> setsnmpvacm createview -s .1 all_view
```

EXAMPLE 3 Create a View Where the Subtree Is Excluded

```
XSCF> setsnmpvacm createview -e -s .1.3.6.1.2.1.1 -m fe excl_view
```

EXAMPLE 4 Create Access

```
XSCF> setsnmpvacm createaccess -r all admin
```

EXIT STATUS The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO [shownmpvacm\(8\)](#)

setsnmpvacm(8)



NAME	setssh - set the Secure Shell (SSH) service used in the XSCF network. Also, generate the host public key, and register or delete the user public key, which are necessary for the SSH service						
SYNOPSIS	<pre>setssh [[-q] -{y n}] -c enable</pre> <pre>setssh -c disable</pre> <pre>setssh -c addpubkey [-u <i>user_name</i>]</pre> <pre>setssh -c delpubkey {-a -s <i>line</i> } [-u <i>user_name</i>]</pre> <pre>setssh [[-q] -{y n}] -c genhostkey</pre> <pre>setssh -h</pre>						
DESCRIPTION	<p>setssh(8) command starts or stops the SSH service used in the XSCF network. Also, generates the host public key, and registers or deletes the user public key, which are necessary for the SSH service.</p> <p>If a host public key already exists when a new host public key is to be generated, an update confirmation prompt about the existing key is displayed.</p> <p>The user public key can be registered on each user account. Per user account, multiple user public keys can be registered. Per user account, the user public keys can be registered up to 1,023 characters including the linefeed.</p> <p>Only SSH2 is supported for XSCF.</p>						
Privileges	<p>You must have one of the following privileges to run this command:</p> <ul style="list-style-type: none"> ■ To start or stop the SSH service, and to generate the host public key: platadm ■ To register or delete the user public key of other user account: useradm ■ To register or delete the user public key of the current login user account: useradm, platadm, platop, auditadm, auditop, domainadm, domainmgr, domainop, fieldeng <p>Refer to setprivileges(8) for more information.</p>						
OPTIONS	<p>The following options are supported:</p> <table border="0" style="width: 100%;"> <tr> <td style="padding-right: 20px;">-a</td> <td>Deletes all registered user public keys. Should be specified with "-c delpubkey."</td> </tr> <tr> <td>-c addpubkey</td> <td>Registers the user public key.</td> </tr> <tr> <td>-c delpubkey</td> <td>Deletes the user public key.</td> </tr> </table>	-a	Deletes all registered user public keys. Should be specified with "-c delpubkey."	-c addpubkey	Registers the user public key.	-c delpubkey	Deletes the user public key.
-a	Deletes all registered user public keys. Should be specified with "-c delpubkey."						
-c addpubkey	Registers the user public key.						
-c delpubkey	Deletes the user public key.						

<code>-c {enable disable}</code>	Specifies whether to enable the SSH service. One of the following values can be specified: <table> <tr> <td><code>enable</code></td> <td>Starts the SSH2 service.</td> </tr> <tr> <td><code>disable</code></td> <td>Stops the SSH2 service.</td> </tr> </table>	<code>enable</code>	Starts the SSH2 service.	<code>disable</code>	Stops the SSH2 service.
<code>enable</code>	Starts the SSH2 service.				
<code>disable</code>	Stops the SSH2 service.				
<code>-c genhostkey</code>	Generates a host public key for SSH2.				
<code>-h</code>	Displays usage statement. When used with other options or operands, an error occurs.				
<code>-n</code>	Automatically answers "n" (no) to all prompts.				
<code>-q</code>	Suppresses all messages to stdout, including prompts.				
<code>-s line</code>	Specifies the user public key number to delete. For line, specify the number which displayed after the <code>showssh -c pubkey</code> command executed. Should be specified with " <code>-c delpubkey</code> ."				
<code>-u user_name</code>	Specifies the user account name to register or delete the user public key. Should be specified with " <code>-c addpubkey</code> " or " <code>-c delpubkey</code> ." When the <code>-u</code> option omitted, the user public key of the current login user account becomes the target.				
<code>-y</code>	Automatically answers "y" (yes) to all prompts.				

EXTENDED DESCRIPTION

- When a host public key is created, a prompt to confirm execution of the command with the specified options is displayed. Enter "y" to execute the command or "n" to cancel the command.
- The `setssh(8)` command can register one user public key at a time.
- In time of `setssh(8)` command execution, finish the input of user public key by pressing `Enter` and then pressing "`Ctrl`" and "`D`" (EOF).
- In case the XSCF unit is duplicated configuration, the setting automatically reflected to the standby XSCF. When there is a defect on the standby XSCF, it leads to an error and the setting will be reflected to the active XSCF only.
- The information which has been set will be reflected by using the `rebootxscf(8)` command to reset XSCF.
- The current SSH service settings can be checked by using the `showssh(8)` command.

EXAMPLES

EXAMPLE 1 Starts the SSH service.

```
XSCF> setssh -c enable  
Continue? [y|n] :y  
Please reset the XSCF by rebootxscf to apply the ssh settings.
```

EXAMPLE 2 Starts the SSH service. Automatically replies with "y" to the prompt.

```
XSCF> setssh -y -c enable  
Continue? [y|n] :y  
Please reset the XSCF by rebootxscf to apply the ssh settings.
```

EXAMPLE 3 Starts the SSH service. Automatically replies with "y" without displaying the prompt.

```
XSCF> setssh -q -y -c enable
```

EXAMPLE 4 Stops the SSH service.

```
XSCF> setssh -c disable
```

EXAMPLE 5 Generates a host public key for SSH.

```
XSCF> setssh -c genhostkey  
Host key create. Continue? [y|n] :y  
Please reset the XSCF by rebootxscf to apply the ssh settings.
```

EXAMPLE 6 Generates a host public key for SSH. Automatically replies with "y" to the prompt.

```
XSCF> setssh -c genhostkey -y  
Host key create. Continue? [y|n] :y  
Please reset the XSCF by rebootxscf to apply the ssh settings.
```

EXAMPLE 7 Generates a host public key for SSH. Automatically replies with "y" without displaying the prompt.

```
XSCF> setssh -c genhostkey -q -y
```

EXAMPLE 8 Registers the user public key. Finish the input of public key by pressing En-

ter and then pressing "Ctrl" and "D"

```
XSCF> setssh -c addpubkey
```

Please input a public key:

```
ssh-rsa AAAAB3NzaC1yc2EAAAABIwAAAIEAzFh95SohrDgpnN7zFCJCVNy+jazPTjNDxcid
QGbihYDCBttI4151Y0Sv85FJwDpSNHNKoVLMYLjtBmUMPhGgGVB61qskSv/
FeV44hefNCZMiXGItIIPK
P0nBK4XJpCFoFbPXNUHDw1rTD9icD5U/wRFGSRRxFI+Ub5oLRxN8+A8=abcd@example.com
```

[Enter]

[Ctrl]and[D]

EXAMPLE 9 Registers the user public key by specifying the user name. Finish the input of public key by pressing Enter and then pressing "Ctrl" and "D".

```
XSCF> setssh -c addpubkey -u efgh
```

Please input a public key:

```
ssh-rsa AAAAB3NzaC1yc2EAAAABIwAAAIEAzFh95SohrDgpnN7zFCJCVNy+jazPTjNDxcid
QGbihYDCBttI4151Y0Sv85FJwDpSNHNKoVLMYLjtBmUMPhGgGVB61qskSv/
FeV44hefNCZMiXGItIIPK
P0nBK4XJpCFoFbPXNUHDw1rTD9icD5U/wRFGSRRxFI+Ub5oLRxN8+A8=abcd@example.com
```

[Enter]

[Ctrl]and[D]

EXAMPLE 10 Specifies the public key number to delete the user public key.

```
XSCF> setssh -c delpubkey -s 1
```

```
1 ssh-rsa
```

```
AAAAB3NzaC1yc2EAAAABIwAAAIEAzFh95SohrDgpnN7zFCJCVNy+jazPTjNDxcid
QGbihYDCBttI4151Y0Sv85FJwDpSNHNKoVLMYLjtBmUMPhGgGVB61qskSv/
FeV44hefNCZMiXGItIIPK
P0nBK4XJpCFoFbPXNUHDw1rTD9icD5U/wRFGSRRxFI+Ub5oLRxN8+A8=abcd@example.com
```

EXAMPLE 11 Deletes all user public keys.

```
XSCF> setssh -c delpubkey -a
```

EXIT STATUS The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO **rebootxscf(8)**, **showssh(8)**

setssh(8)



NAME	settelnet - start or stop the Telnet service used in the XSCF network								
SYNOPSIS	<pre>settelnet -c {enable disable}</pre> <pre>settelnet -h</pre>								
DESCRIPTION	settelnet(8) command starts or stops the Telnet service used in the XSCF network.								
Privileges	<p>You must have platadm privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>								
OPTIONS	<p>The following options are supported:</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="vertical-align: top; padding-right: 10px;">-c {enable disable}</td> <td>Specify whether to start the Telnet service. One of the following values can be specified. If none of them is specified, an error occurs.</td> </tr> <tr> <td style="padding-left: 40px; vertical-align: top; padding-right: 10px;">enable</td> <td>Starts the Telnet service.</td> </tr> <tr> <td style="padding-left: 40px; vertical-align: top; padding-right: 10px;">disable</td> <td>Stops the Telnet service.</td> </tr> <tr> <td style="vertical-align: top; padding-right: 10px;">-h</td> <td>Displays usage statement. When used with other options or operands, an error occurs.</td> </tr> </table>	-c {enable disable}	Specify whether to start the Telnet service. One of the following values can be specified. If none of them is specified, an error occurs.	enable	Starts the Telnet service.	disable	Stops the Telnet service.	-h	Displays usage statement. When used with other options or operands, an error occurs.
-c {enable disable}	Specify whether to start the Telnet service. One of the following values can be specified. If none of them is specified, an error occurs.								
enable	Starts the Telnet service.								
disable	Stops the Telnet service.								
-h	Displays usage statement. When used with other options or operands, an error occurs.								
EXTENDED DESCRIPTION	<ul style="list-style-type: none"> ■ In the M8000/M9000 servers, the setting automatically reflected to the standby XSCF. When there's a defect on the standby XSCF, it leads to an error and the setting will be reflected to the active XSCF only. ■ In case you stop the Telnet service, it will be reflected by using the rebootxscf(8) command to reset XSCF. ■ The current Telnet service state can be checked by using the showtelnet(8) command. 								
EXAMPLES	<p>EXAMPLE 1 Starts the Telnet service.</p> <pre>XSCF> settelnet -c enable</pre> <p>EXAMPLE 2 Stops the Telnet service.</p> <pre>XSCF> settelnet -c disable</pre> <p>Please reset the XSCF by rebootxscf to apply the telnet settings.</p>								

settelnet(8)

EXIT STATUS	The following exit values are returned:
0	Successful completion.
>0	An error occurred.
SEE ALSO	rebootxscf(8) , showtelnet(8)

NAME	settimezone - set the time zone and Daylight Saving Time of XSCF
SYNOPSIS	<p>settimezone -c settz -s <i>timezone</i></p> <p>settimezone -c settz -a [-M]</p> <p>settimezone -c adddst -b <i>std</i> -o <i>offset</i> -d <i>dst</i> [-p <i>offset</i>] -f <i>date</i> [/time] -t <i>date</i> [/time]</p> <p>settimezone -c deldst -b <i>std</i> -o <i>offset</i></p> <p>settimezone -h</p>
DESCRIPTION	<p>The <code>settimezone(8)</code> command sets the time zone and Daylight Saving Time of XSCF.</p> <p>The time zone is pursuant to POSIX standard.</p>
Privileges	<p>You must have <code>platadm</code> or <code>fieldeng</code> privileges to run this command.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>
OPTIONS	<p>The following options are supported:</p> <ul style="list-style-type: none"> -a Lists the time zones that can be set. -c settz Sets the time zone which complies with POSIX standards. -c adddst Manually sets the time zone and Daylight Saving Time. -c deldst Deletes the time zone and Daylight Saving Time. -b <i>std</i> Specifies the abbreviations of time zone. For <i>std</i>, specify an abbreviation of 3 letters or more. You can specify it in the format which complies with RFC2822. In case specified in combination with "-c adddst," it will be linked with the time zone to be set. When specified in combination with "-c deldst," the link with the time zone which has been set will be cancelled. -d <i>dst</i> Specifies the name of Daylight Saving Time. For <i>dst</i>, specify the alphabets of 3 letters or more. You can specify it in the format which complies with RFC2822.

- f *date* [*/time*] Specifies the starting time of Daylight Saving Time. You can specify *date* in any of the following formats.
- Mm.w.d*
- Mm*: Specifies the month to start Daylight Saving Time. For *m*, you can specify any integer from 1 to 12.
- w*: Specifies the week to start Daylight Saving Time. You can specify the integer from 1 to 5, "1" for the first week and "5" for the last week in the month.
- d*: Specifies the day of the week to start Daylight Saving Time. You can specify the integer from 0 to 6, "0" for Sunday and "6" for Saturday.
- Jn*
- Jn*: Specifies the sequential day in the year to start Daylight Saving Time. You can specify the integer from 1 to 365, "1" for January 1st. It does not count the leap-year day.
- n*
- n*: Specifies the sequential day in the year to start Daylight Saving Time. You can specify the integer from 1 to 365, "1" for January 1st. It counts the leap-year day.
- In *time*, you specify the time. You can specify it in the following format.
- hh:mm:ss* Specifies the time in "*hh:mm:ss*" format. *hh* is 00–23, *mm* is 00–59, *ss* is 00–60. In case omitted, "02:00:00."
- h Displays usage statement. When used with other options or operands, an error occurs.
- M Displays text by page. This option provides a function that is the same as that of the `more` command.

-o *offset*

Specifies the offset of time zone and Greenwich mean time (GMT). You can specify *offset* in the following format.

GMT{+|-}hh[:mm[:ss]]

GMT Greenwich mean time

{+|-} Specifies "-" to set the standard time to the time which is ahead of GMT. (To adjust to the local time east to Greenwich, the offset is a negative value.) Specifies "+" to set the standard time to the time which is behind the GMT. (To adjust to the local time west to Greenwich, the offset is a positive value.)

hh[:mm[:ss]] Specifies the offset time. *hh* is 00-23, *mm* is 00-59, *ss* is 00-59.

`-p offset` Specifies the offset of Daylight Saving Time and Greenwich mean time (GMT). You can specify *offset* in the following format. In case omitted, it is 1 hour before the specified time.

GMT{+|-}hh[:mm[:ss]]

GMT Greenwich mean time

{+|-} Specifies "-" to set the standard time to the time which is ahead of GMT. (To adjust to the local time east to Greenwich, the offset is a negative value.) Specifies "+" to set the standard time to the time which is behind the GMT. (To adjust to the local time west to Greenwich, the offset is a positive value.)

hh[:mm[:ss]] Specifies the offset time. *hh* is 00-23, *mm* is 00-59, *ss* is 00-59.

`-s timezone` Specifies the time zone. One of the time zone displayed by the `-a` option can be specified for *timezone*.

`-t date [/time]` Specifies the termination time of Daylight Saving Time. You can specify *date* in any of the following formats.

Mm.w.d

Mm: Specifies the month to terminate Daylight Saving Time. For *m*, you can specify any integer from 1 to 12.

w: Specifies the week to terminate Daylight Saving Time. You can specify the integer from 1 to 5, "1" for the first week and "5" for the last week in the month.

d: Specifies the day of the week to terminate Daylight Saving Time. You can specify the integer from 0 to 6, "0" for Sunday and "6" for Saturday.

Jn

Jn: Specifies the sequential day in the year to terminate Daylight Saving Time. You can specify the integer from 1 to 365, "1" for January 1st. It does not count the leap-year day.

n

n: Specifies the sequential day in the year to terminate Daylight Saving Time. You can specify the integer from 1 to 365, "1" for January 1st. It counts the leap-year day.

In *time*, you specify the time. You can specify it in the following format.

hh:mm:ss Specifies the time in "*hh:mm:ss*" format. *hh* is 00–23, *mm* is 00–59, *ss* is 00–60. In case omitted, "02:00:00."

EXTENDED DESCRIPTION

- You cannot specify the years of validity for time zone and Daylight Saving Time. In case the Daylight Saving Time is changed each year, you need to set anew by using the `settimezone(8)` command.
- The addition of the offset time to the standard time which has been set by the `settimezone(8)` command comes to GMT.
- The current time zone settings can be checked by using the `showtimezone(8)` command.
- To reflect the Daylight Saving Time information which modified by `-c adddst` or `-c deldst` option, log out and then log in again.

EXAMPLES

EXAMPLE 1 Sets "Asia/Tokyo" as the time zone.

```
XSCF> settimezone -c settz -s Asia/Tokyo
Asia/Tokyo
```

EXAMPLE 2 Lists the time zones that can be set.

```
XSCF> settimezone -c settz -a
Africa/Abidjan
Africa/Accra
Africa/Addis_Ababa
Africa/Algiers
Africa/Asmera
Africa/Bamako
Africa/Bangui
.
.
```

EXAMPLE 3 Sets the Daylight Saving Time information as follows: abbreviation of time zone is JST, the offset from GMT is +9, the name of Daylight Saving Time is JDT, Daylight Saving Time is 1 hour ahead, and the time period is from the last Monday of March 2:00 to the last Sunday of October 2:00.

```
XSCF> settimezone -c adddst -b JST -o GMT-9 -d JDT -f M3.5.0 -t M10.5.0
JST-9JDT,M3.5.0,M10.5.0
```

EXAMPLE 4 Sets the Daylight Saving Time information as follows: abbreviation of time zone is JST, the offset from GMT is +9, the name of Daylight Saving Time is JDT, the offset of Daylight Saving Time from GMT is +10, and the time period is from the first Sunday of April 0:00 to the first Sunday of September 0:00.

```
XSCF> settimezone -c adddst -b JST -o GMT-9 -d JDT -p GMT-10 -f M4.1.0/00:00:00 -t M9.1.0/00:00:00
JST-9JDT-10,M4.1.0/00:00:00,M9.1.0/00:00:00
```

EXAMPLE 5 Deletes the Daylight Saving Time information of current settings.

```
XSCF> settimezone -c deldst -b JST -o GMT-9
```


EXIT STATUS The following exit values are returned:

0 Successful completion.
>0 An error occurred.

SEE ALSO **setdate (8), showdate (8), showtimezone (8)**

settimezone(8)



NAME	setupfru - set up device hardware
SYNOPSIS	setupfru [-m {y n}] [-x {1 4}] <i>device location</i> setupfru -h
DESCRIPTION	<p>The setupfru(8) command makes hardware settings for the specified device.</p> <p>The setupfru(8) command is not supported on the M3000 server.</p> <p>Only a physical system board (PSB) can be specified as a device. After a PSB is added, the following settings can be specified for PSB:</p> <p>XSB type To use an added PSB in the system, hardware resources on the PSB must be logically divided and reconfigured as eXtended System Boards (XSBs). Two types of XSB are used: Uni-XSB and Quad-XSB. The Uni-XSB is configured with undivided PSB, and the Quad-XSB is configured with one of divided PSB into four parts. Specify either the Uni-XSB configuration or Quad-XSB configuration for the PSB.</p> <p>Memory mirror mode In mirror mode, data is mirrored by dividing the memory mounted on a PSB into two parts. Since the memory is divided into two parts, the memory capacity is halved, but data reliability increases. Specify whether to operate the memory in mirror mode.</p>
Privileges	<p>You must have platadm or fieldeng privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p>-h Displays usage statement. When used with other options or operands, an error occurs.</p> <p>-m {y n} Specifies whether to use the memory mounted on the XSB in mirror mode. Specify this option when sb is specified for <i>device</i>. Specify y to enable mirror mode; otherwise, specify n. If the -m option is omitted, the previous setting is inherited.</p> <p>-x {1 4} Specifies whether to configure PSB as a Uni-XSB or Quad-XSB. Specify this option when sb is specified for <i>device</i>. Specify 1 for Uni-XSB or specify 4 for Quad-XSB. If the -x option is omitted, the previous setting is inherited.</p>

OPERANDS

The following operands are supported:

<i>device</i>	Specifies the device to be set up. Only the following device can be specified:
sb	Physical system board (PSB)
<i>location</i>	Specifies the location of the device.
sb	Integer from 0–15. Specify only one <i>location</i> .

EXTENDED DESCRIPTION

- In the M8000/M9000 server, the Quad-XSB configuration cannot be set in memory mirror mode.
- To set up an already mounted PSB again, all XSBs comprising the target PSB must have been disconnected from the domain configuration and placed under the system board pool. See the `deleteboard(8)` command for information on how to disconnect XSBs from the domain configuration.
- The configuration of the PSB varies according to the system as shown below.
 - In the M8000/M9000 servers, the PSB consists of one CPU/memory board unit and one I/O unit in combination.
 - In the M4000/M5000 servers, the PSB consists of one CPU module and one memory module logically divided into two on the motherboard unit, and one I/O module.
- The current PSB settings can be checked by using the `showfru(8)` command.

EXAMPLES

EXAMPLE 1 Configures PSB#00 as a Quad-XSB (with memory in non-mirror mode because the memory mirror mode setting is omitted).

```
XSCF> setupfru -x 4 sb 0
```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

`addboard(8)`, `deleteboard(8)`, `moveboard(8)`, `setdcl(8)`, `showboards(8)`, `showdcl(8)`, `showdevices(8)`, `showfru(8)`

NAME	setupplatform - set up platform specific settings								
SYNOPSIS	<p>setupplatform [-v]</p> <p>setupplatform [-v] -p <i>part</i> [-p <i>part</i>]</p> <p>setupplatform -h</p>								
DESCRIPTION	<p>The setupplatform(8) command sets up platform specific settings. The command leads an administrator through Service Processor installation tasks.</p> <p>By default, setupplatform command walks through each of the available settings. Individual settings may be selected using the -p option.</p>								
Privileges	<p>You must have one of the following privileges to run this command:</p> <ul style="list-style-type: none"> ■ To use the -p user option: usradm ■ To use the -p network, -p altitude, -p timezone options: platadm <p>Refer to setprivileges(8) for more information.</p>								
OPTIONS	<p>The following options are supported:</p> <p>-h Displays usage statement. When used with other options or operands, an error occurs.</p> <p>-p <i>part</i> Specifies the setting you want to do. One of the following can be specified for part:</p> <table border="0" style="margin-left: 40px;"> <tr> <td style="padding-right: 20px;">altitude</td> <td>Configures the chassis altitude.</td> </tr> <tr> <td>network</td> <td>Configures the XSCF network, DSCP, DNS, NTP, SSH, https, and SMTP.</td> </tr> <tr> <td>timezone</td> <td>Sets the time zone for the XSCF. The time zone is chosen from a list of time zones.</td> </tr> <tr> <td>user</td> <td>Creates a new local XSCF user account with platadm, platop, and useradm privileges.</td> </tr> </table> <p>-v Specifies verbose output.</p>	altitude	Configures the chassis altitude.	network	Configures the XSCF network, DSCP, DNS, NTP, SSH, https, and SMTP.	timezone	Sets the time zone for the XSCF. The time zone is chosen from a list of time zones.	user	Creates a new local XSCF user account with platadm, platop, and useradm privileges.
altitude	Configures the chassis altitude.								
network	Configures the XSCF network, DSCP, DNS, NTP, SSH, https, and SMTP.								
timezone	Sets the time zone for the XSCF. The time zone is chosen from a list of time zones.								
user	Creates a new local XSCF user account with platadm, platop, and useradm privileges.								
EXTENDED DESCRIPTION	<p>The available interfaces on the M3000/M4000/M5000 servers are xscf#0-lan#0, xscf#0-lan#1, lan#0, lan#1. The available interfaces on the M8000/M9000 servers are the same but they also include the xscf#0-if, xscf#1-lan#0, xscf#1-lan#1, and xscf#1-if.</p> <p>In user setup, a new local user account can be created with a user supplied password.</p>								

In network setup, the following items can be optionally configured:

- XSCF Network Settings
- Internal DSCP Network
- DNS
- NTP
- SSH
- HTTPS Server
- Email reports

EXAMPLES

EXAMPLE 1 Creating a New User.

```
XSCF> setupplatform -p user
Do you want to set up an account? [y|n]: y
Username: myadminuser
User id in range 100 to 65533 or leave blank to let the system
choose one:
    Username: myadminuser
    User id:
Are these settings correct? [y|n]: y
XSCF> adduser myadminuser
XSCF> setprivileges myadminuser useradm platadm platop
XSCF> password myadminuser
New XSCF password: [not echoed]
Retype new XSCF password: [not echoed]
```

EXAMPLE 2 Configuring the XSCF Network.

```
XSCF> setupplatform
Do you want to set up an account? [y|n]: n
Do you want to set up the XSCF network interfaces? [y|n]: y
Do you want to configure xscf#0-lan#0? [y|n]: y
xscf#0-lan#0 ip address? []: 192.168.1.4
xscf#0-lan#0 netmask? [255.255.255.0]: 255.255.254.0
xscf#0-lan#0 default gateway? []: 192.168.1.1
    xscf#0-lan#0 ip address: 192.168.1.4
    xscf#0-lan#0 netmask: 255.255.254.0
```

```

xscf#0-lan#0 default gateway: 192.168.1.1
Are these settings correct? [y|n]: y
XSCF> setnetwork xscf#0-lan#0 -m 255.255.254.0 192.168.1.4
. . .

```

EXAMPLE 3 Enabling ssh.

```

XSCF> setupplatform -p network
Do you want to set up the XSCF network interfaces? [y|n]: n
Do you want to set up the DSCP network? [y|n]: n
Do you want to set up the domain name service? [y|n]: n
Do you want to set up the network time protocol? [y|n]: n
Do you want to set up ssh? [y|n]: y
Enable ssh service? [y|n]: y
XSCF> setssh -q -y -c enable
Do you want to set up https? [y|n]: n
. . .

```

EXAMPLE 4 Configuring the Altitude.

```

XSCF> setupplatform -p altitude
Do you want to set up the chassis altitude? [y|n]: y
Chassis altitude is already configured:
    Chassis altitude in meters: 200
Continue setting up the chassis altitude? [y|n]: y
Chassis altitude in meters: 400
    Chassis altitude in meters: 400
Is this setting correct? [y|n]: y
XSCF> setaltitude -s altitude=400
400m

```

The specified altitude becomes valid when the circuit breakers of the system are switched on again.

```

Do you want to reboot the XSCF now? [y|n]: n
XSCF>

```

EXAMPLE 5 Setting the Time Zone.

```
XSCF> setupplatform -p timezone
Do you want to set up the XSCF time zone? [y|n]: y
Chassis time zone is already configured:
    XSCF time zone: US/Pacific
Continue setting up the XSCF time zone? [y|n]: y
0      Africa/Abidjan
1      Africa/Accra
2      Africa/Addis_Ababa
3      Africa/Algiers
4      Africa/Asmera
5      Africa/Bamako
6      Africa/Bangui
7      Africa/Banjul
8      Africa/Bissau
9      Africa/Blantyre
10     Africa/Brazzaville
11     Africa/Bujumbura
12     Africa/Cairo
13     Africa/Casablanca
14     Africa/Ceuta
15     Africa/Conakry
16     Africa/Dakar
17     Africa/Dar_es_Salaam
18     Africa/Djibouti
19     Africa/Douala
20     Africa/El_Aaiun
21     Africa/Freetown
22     Africa/Gaborone
Enter number to choose time zone or return for next set of time zones: 21
    XSCF time zone: Africa/Freetown
Is this setting correct? [y|n]: y
```



```
XSCF> setaltitude -c settz -s Africa/Freetown
Africa/Freetown
XSCF>
```

EXIT STATUS The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO [adduser\(8\)](#), [applynetwork\(8\)](#), [password\(8\)](#), [setaltitude\(8\)](#), [setdscp\(8\)](#), [setemailreport\(8\)](#), [sethostname\(8\)](#), [sethttps\(8\)](#), [setnameserver\(8\)](#), [setnetwork\(8\)](#), [setntp\(8\)](#), [setprivileges\(8\)](#), [setsmtp\(8\)](#), [setssh\(8\)](#), [setroute\(8\)](#), [settimezone\(8\)](#)

setupplatform(8)



NAME	showaltitude - display the altitude of the system and whether the air filter installed
SYNOPSIS	showaltitude showaltitude -h
DESCRIPTION	The <code>showaltitude(8)</code> command displays the current settings for the altitude of the system and whether the air filter installed. Whether the air filter installed is displayed on the M4000/M5000 servers only. The displayed altitude value is a multiple of 100 meters.
Privileges	You must have <code>plataadm</code> or <code>fieldeng</code> privileges to run this command. Refer to <code>setprivileges(8)</code> for more information.
OPTIONS	The following option is supported: -h Displays usage statement.
EXTENDED DESCRIPTION	<ul style="list-style-type: none"> ■ The air filter is displayed only when it is installed. If the filter is not installed nothing is displayed. ■ The <code>setaltitude(8)</code> command sets the altitude of the system and whether or not the air filter installed.
EXAMPLES	<p>EXAMPLE 1 Displays the altitude of the system.</p> <pre>XSCF> showaltitude 1000m</pre> <p>EXAMPLE 2 Displays the altitude of the M4000/M5000 servers with the air filter installed.</p> <pre>XSCF> showaltitude 1000m Filter is installed.</pre>
EXIT STATUS	The following exit values are returned: 0 Successful completion. >0 An error occurred.
SEE ALSO	setaltitude (8)

showaltitude(8)



NAME	showarchiving - display log archiving configuration and status						
SYNOPSIS	<p>showarchiving</p> <p>showarchiving [-e] [-v]</p> <p>showarchiving -h</p>						
DESCRIPTION	showarchiving(8) displays the status and configuration information for log archiving on the Service Processor.						
Privileges	<p>You must have <code>platadm</code>, <code>platop</code> or <code>fieldeng</code> privileges to run this command.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>						
OPTIONS	<p>The following options are supported:</p> <p>-e Displays information about the last ten archiving errors.</p> <p>-h Displays usage statement.</p> <p> When used with other options or operands, an error occurs.</p> <p>-v Specifies verbose output.</p>						
EXTENDED DESCRIPTION	<p>If the <code>-e</code> option is not specified, <code>showarchiving</code> displays the following information:</p> <p>1. A list of archiving configuration data:</p> <table border="0" style="width: 100%;"> <tr> <td style="padding-right: 20px;">Archiving state</td> <td>Log archiving is enabled or disabled.</td> </tr> <tr> <td>Archive host</td> <td>The host on which the logs are archived. Initial value is <code>Not configured</code>. Possible values are a host name or IPv4 address.</td> </tr> <tr> <td>Archive directory</td> <td>The directory on the archive host where the archives are stored. Initial value is <code>Not configured</code>.</td> </tr> </table>	Archiving state	Log archiving is enabled or disabled.	Archive host	The host on which the logs are archived. Initial value is <code>Not configured</code> . Possible values are a host name or IPv4 address.	Archive directory	The directory on the archive host where the archives are stored. Initial value is <code>Not configured</code> .
Archiving state	Log archiving is enabled or disabled.						
Archive host	The host on which the logs are archived. Initial value is <code>Not configured</code> . Possible values are a host name or IPv4 address.						
Archive directory	The directory on the archive host where the archives are stored. Initial value is <code>Not configured</code> .						

Username for ssh login	User name which the Service Processor uses to login to the archive host. Initial value is Not configured.
Archive host public key	The public key which the Service Processor uses to verify the identity of the archive host. This field is not displayed unless the <code>-v</code> option is specified.
Archive host fingerprint	The md5 fingerprint of the public key which the Service Processor uses to verify the identity of the archive host.

2. Time of the most recent attempt to connect to the archive host, and the outcome of that attempt (success or failure):

Latest communication	The completion time of the latest attempt to communicate with the archive host.
Connection status	The outcome of the latest attempt to connect to the archive host; successful (OK) or unsuccessful (FAILED).

3. Table of the status information for audit logs and non-audit logs:

Archive space limit	The amount of space allocated for the archives.
Archive space used	The amount of space currently consumed by the archives.
Total archiving failures	A counter of failed archiving operations.
Unresolved failures	A counter of failed archiving operations which the Service Processor will continue to retry.

If the `-e` option is specified `showarchiving` displays the details of the last ten archiving errors that occurred.

EXAMPLES

EXAMPLE 1 Viewing Status and Configuration Data

```
XSCF> showarchiving
*** Archiving Configuration ***
Archiving state ----- Disabled
Archive host ----- Not configured
Archive directory ----- Not configured
User name for ssh login -- Not configured
```

```
Archive host fingerprint - Server authentication disabled
```

```
*** Connection to Archive Host ***
```

```
Latest communication ----- None
```

```
Connection status ----- None
```

	AUDIT LOGS	OTHER LOGS
	-----	-----
Archive space limit	Unlimited	2000 MB
Archive space used	Not monitored	Not monitored
Total archiving failures	0	0
Unresolved failures	0	0

EXAMPLE 2 Displaying Archiving Error Information

```
XSCF> showarchiving -e
```

```
No archiving errors have occurred.
```

EXIT STATUS

The following exit values are returned:

```
0           Successful completion.
>0         An error occurred.
```

SEE ALSO

setarchiving (8)

showarchiving(8)



NAME	showaudit - display the current auditing system state
SYNOPSIS	showaudit showaudit [all] showaudit [-a <i>users</i>] [-c <i>classes</i>] [-e <i>events</i>] [-g] [-m] [-p] [-s] [-t] showaudit -h
DESCRIPTION	<code>showaudit(8)</code> displays the current state of system auditing. When invoked without options <code>showaudit</code> displays whether the writing of audit records is enabled or disabled.
Privileges	You must have <code>auditadm</code> or <code>auditop</code> privileges to run this command. Refer to <code>setprivileges(8)</code> for more information.

OPTIONS

The following options are supported:

- a *users* Displays the audit record generation policy for the specified users. *users* is a comma-separated list of valid user names.
- c *classes* Displays the audit record generation policy for the specified audit classes. *classes* is a comma-separated list of audit classes. A class may be specified by its numeric value or its name. The ACS_ prefix may be omitted. For example, the class of audit related events can be expressed as ACS_AUDIT, AUDIT or 16.

The following are valid classes:

all	Denotes all classes.
ACS_SYSTEM(1)	System-related events
ACS_WRITE(2)	Commands that can modify a state
ACS_READ(4)	Commands that read a current state
ACS_LOGIN(8)	Login-related events
ACS_AUDIT(16)	Audit-related events
ACS_DOMAIN(32)	Domain management-related events
ACS_USER(64)	User management-related events
ACS_PLATFORM(128)	Platform management-related events
ACS_MODES(256)	Mode-related events

- e *events* Displays the audit record generation policy for the specified audit events. *events* is a comma-separated list of audit events. An event may be specified by its numeric value or its name. The AEV_ prefix may be omitted. For example, the event for SSH login can be expressed as AEV_LOGIN_SSH, LOGIN_SSH, or 0.

See `showaudit -e all` for a list of all valid events.

- g Displays the global user audit record generation policy.
- h Displays usage statement.
- When used with other options or operands, an error occurs.
- m Displays the address to which email is sent when the local audit storage space usages reaches a threshold.

- p Displays the policy to follow when the audit trail reaches full capacity.
- s Displays the following auditing states:
 - Space consumed by local audit records
 - Free space remaining for local audit records
 - Number of audit records dropped (since the last boot) since the audit trail reached full capacity.
- t Displays the thresholds at which to issue warning(s) about local storage usage.

OPERANDS The following operands are supported:

- all Displays the following information:
 - Whether the writing of audit trails is set to `enable` or `disable`. This is the same display that is shown for `showaudit` when invoked without any options.
 - All the information that would be displayed by invoking `showaudit` with the options: `-a`, `-c all`, `-e all`, `-g`, `-m`, `-p`, `-s`, `-t`.

EXAMPLES **EXAMPLE 1** Displaying Auditing Status

```
XSCF> showaudit
Auditing: enabled
```

EXAMPLE 2 Displaying All Class Information For Login Auditing

```
XSCF> showaudit -c LOGIN

Events:
AEV_LOGIN_BUI                enabled
AEV_LOGIN_CONSOLE           enabled
AEV_LOGIN_SSH                enabled
AEV_LOGIN_TELNET            enabled
AEV_LOGOUT                   enabled
AEV_AUTHENTICATE             enabled
```

EXAMPLE 3 Displaying All Event Information

```
XSCF> showaudit -e all

Events:

AEV_AUDIT_START           enabled
AEV_AUDIT_STOP           enabled
AEV_ENTER_MODE           enabled
AEV_EXIT_MODE            enabled
AEV_LOGIN_BUI            enabled
AEV_LOGIN_CONSOLE       enabled
AEV_LOGIN_SSH           enabled
AEV_LOGIN_TELNET        enabled
AEV_LOGOUT               enabled
AEV_AUTHENTICATE        enabled
AEV_addboard             enabled
AEV_addcodlicense       enabled
AEV_addfru               enabled
[...]
```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

setaudit(8), **viewaudit**(8)

NAME	showautologout - display the session timeout time of the XSCF shell
SYNOPSIS	showautologout showautologout -h
DESCRIPTION	The showautologout(8) command displays the session timeout time of the XSCF shell. The session timeout time is displayed in units of minutes. If the session timeout time has not been specified with the setautologout(8) command, a time of 10 minutes is set by default.
Privileges	You must have one of the following privileges to run this command: useradm, platadm, platop, auditadm, auditop, domainadm, domainmgr, domainop, fieldeng Refer to setprivileges(8) for more information.
OPTIONS	The following option is supported: -h Displays usage statement.
EXAMPLES	EXAMPLE 1 Displays the session timeout time of the XSCF shell. XSCF> showautologout 30min EXAMPLE 2 Displays the session timeout time of the XSCF shell (the time is default). XSCF> showautologout 10min
EXIT STATUS	The following exit values are returned: 0 Successful completion. >0 An error occurred.
SEE ALSO	setautologout (8)

showautologout(8)



NAME	showboards - display information on an eXtended System Board (XSB)																		
SYNOPSIS	<p>showboards [-v] -a [-c sp]</p> <p>showboards [-v] -d <i>domain_id</i> [-c sp]</p> <p>showboards [-v] <i>xsb</i></p> <p>showboards -h</p>																		
DESCRIPTION	<p>The <code>showboards(8)</code> command displays information on XSBs.</p> <p>This command displays information on XSBs currently configured in or assigned to a domain and information on all mounted XSBs. If a domain is specified, the command displays only information defined with the corresponding domain component list (DCL).</p> <p>The following types of information are displayed:</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="vertical-align: top; padding-right: 20px;">XSB</td> <td>XSB number. The format of the displayed number is as follows:</td> </tr> <tr> <td></td> <td style="padding-left: 20px;"><i>x-y</i></td> </tr> <tr> <td></td> <td style="padding-left: 20px;"><i>x</i> An integer from 00–15.</td> </tr> <tr> <td></td> <td style="padding-left: 20px;"><i>y</i> An integer from 0–3.</td> </tr> <tr> <td style="vertical-align: top; padding-right: 20px;">DID</td> <td>Domain ID. One of the following is displayed:</td> </tr> <tr> <td></td> <td style="padding-left: 20px;">00–23 Domain ID to which the XSB is assigned</td> </tr> <tr> <td></td> <td style="padding-left: 20px;">SP This is displayed if the XSB does not belong to any domain but is located in the system board pool.</td> </tr> <tr> <td></td> <td style="padding-left: 20px;">Other This is displayed if the XSB belongs to a domain to which no user privilege has been granted.</td> </tr> <tr> <td style="vertical-align: top; padding-right: 20px;">LSB</td> <td>Logical system board (LSB) number defined for the domain. The displayed number is an integer ranging from 0 to 15.</td> </tr> </table>	XSB	XSB number. The format of the displayed number is as follows:		<i>x-y</i>		<i>x</i> An integer from 00–15.		<i>y</i> An integer from 0–3.	DID	Domain ID. One of the following is displayed:		00–23 Domain ID to which the XSB is assigned		SP This is displayed if the XSB does not belong to any domain but is located in the system board pool.		Other This is displayed if the XSB belongs to a domain to which no user privilege has been granted.	LSB	Logical system board (LSB) number defined for the domain. The displayed number is an integer ranging from 0 to 15.
XSB	XSB number. The format of the displayed number is as follows:																		
	<i>x-y</i>																		
	<i>x</i> An integer from 00–15.																		
	<i>y</i> An integer from 0–3.																		
DID	Domain ID. One of the following is displayed:																		
	00–23 Domain ID to which the XSB is assigned																		
	SP This is displayed if the XSB does not belong to any domain but is located in the system board pool.																		
	Other This is displayed if the XSB belongs to a domain to which no user privilege has been granted.																		
LSB	Logical system board (LSB) number defined for the domain. The displayed number is an integer ranging from 0 to 15.																		

Assignment	Domain assignment state of the XSB. Either of the following is displayed:	
	Unavailable	The XSB cannot be used. The XSB may be unrecognizable because it is not mounted, it contains an error, it has been assigned to another domain, or the settings of the domain or system board are not complete.
	Available	The XSB is registered on the DCL and can be used. The XSB may be located in the system board pool.
	Assigned	The XSB is reserved for or assigned to the domain.
Pwr	Power status of the XSB	
	n	Power is off.
	y	Power is on.
Conn	Status of the XSB connection to the domain configuration	
	n	The XSB is not connected to the domain, or it is located in the system board pool.
	y	The XSB is connected to the domain.

Conf	Incorporation state of XSB hardware resources into the Solaris OS	
	n	The resources are not connected to the Solaris OS.
	y	The resources are incorporated in the Solaris OS.
Test	Status of an initial diagnosis on an XSB	
	Unmount	The XSB cannot be recognized because it is not mounted or because it has an error.
	Unknown	Not performed.
	Testing	The initial diagnosis is in progress.
	Passed	The initial diagnosis ended normally.
	Failed	Error (test=fail) detected by an initial diagnosis. The XSB cannot be used or is in a degraded state.
Fault	XSB degradation status	
	Normal	Normal
	Degraded	Component in a degraded state. The XSB can operate.
	Faulted	An error occurred and the XSB cannot operate.
When the <code>-v</code> option is specified, the following types of information are displayed as XSB detail status information:		
R	Dynamic reconfiguration(DR) involving the reservation state of the XSB in the domain	
	*	DR processing is reserved. When the domain is rebooted, the XSB is incorporated into or disconnected from the domain, and the domain configuration is changed.
Cod	Whether the XSB is a COD board	
	n	The XSB is not a COD board.
	y	The XSB is a COD board.

Privileges | You must have one of the following privileges to run this command:

platadm, platop, fieldeng

Can execute the command for all domains.

domainadm, domainmgr, domainop

Can execute the command only for accessible domains.

Refer to `setprivileges(8)` for more information.

OPTIONS | The following options are supported:

- a Displays the state of XSBs configured in or assigned to a domain and the state of all mounted XSBs.
- c *sp* Displays the system boards located in the system board pool. System boards in the system board pool do not belong to any domain.
- d *domain_id* Specifies the ID of the domain whose status of XSB is displayed. Only information that is defined with the DCL of the specified domain is displayed. An integer ranging from 0 to 23 can be specified for *domain_id*, depending on the system configuration.
- h Displays usage statement. When used with other options or operands, an error occurs.
- v Displays detailed information on XSB.

OPERANDS | The following operand is supported:

xsb Specifies the XSB number to be displayed. The following *xsb* form is accepted:

x-y

where:

x An integer from 00–15.

y An integer from 0–3.

EXAMPLES | **EXAMPLE 1** Displays information on all mounted system boards.

```
XSCF> showboards -a
```

```
XSB  DID(LSB) Assignment  Pwr  Conn Conf Test      Fault
```

```
-----
```

```

00-0 00(00)  Assigned  y   y   y   Passed  Normal
00-1 00(01)  Assigned  y   y   y   Passed  Normal
00-2 SP      Available y   n   n   Passed  Normal
00-3 02(00)  Unavailable y   n   n   Unknown Normal

```

EXAMPLE 2 Displays detailed information on all mounted system boards.

```

XSCF> showboards -v -a
XSB  R DID(LSB) Assignment  Pwr  Conn Conf Test   Fault   COD
-----
00-0  00(00)  Assigned  y   y   y   Passed  Normal  n
00-1  * 00(01)  Assigned  y   y   y   Passed  Normal  n
00-2  SP      Available y   n   n   Passed  Normal  n
00-3  02(00)  Unavailable y   n   n   Unknown Normal  n

```

EXAMPLE 3 Displays information on XSB#00-0.

```

XSCF> showboards 00-0
XSB  DID(LSB) Assignment  Pwr  Conn Conf Test   Fault
-----
00-0 15(00)  Assigned  y   y   y   Passed  Normal

```

EXAMPLE 4 Displays detailed information on XSB#00-0.

```

XSCF> showboards -v 00-0
XSB  R DID(LSB) Assignment  Pwr  Conn Conf Test   Fault   COD
-----
00-0  * 15(00)  Assigned  y   n   n   Passed  Normal  y

```

EXAMPLE 5 Displays system boards located in the system board pool.

```

XSCF> showboards -a -c sp
XSB  DID(LSB) Assignment  Pwr  Conn Conf Test   Fault
-----
00-0 SP      Available y   n   n   Passed  Normal
00-2 SP      Available y   n   n   Passed  Normal
00-3 SP      Available y   n   n   Passed  Normal

```

EXAMPLE 6 Displays the system boards that are defined for domain ID 0 and located in the system board pool.

```
XSCF> showboards -d 0 -c sp
XSB  DID(LSB) Assignment  Pwr  Conn Conf Test      Fault
-----
00-2 SP      Available   y   n   n   Passed Normal
```

EXIT STATUS

The following exit values are returned:

0 Successful completion.
 >0 An error occurred.

SEE ALSO

addboard (8), **addcodlicense** (8), **deleteboard** (8), **deletecodlicense** (8), **moveboard** (8), **setdcl** (8), **setupfru** (8), **showcodlicense** (8), **showcodusage** (8), **showdcl** (8), **showdevices** (8), **showfru** (8)

NAME	showcod - display Capacity on Demand (COD) configuration information
SYNOPSIS	<pre>showcod [-v] [-d <i>domain_id</i>]</pre> <pre>showcod -h</pre>
DESCRIPTION	<p>showcod(8) displays the COD information which includes the headroom amount, number of installed COD right-to-use (RTU) licenses, the number of COD RTU licenses reserved for domains, and the Chassis Hostid.</p> <p>The showcod(8) command is not supported on the M3000 server.</p> <p>When used without arguments it displays the current COD information.</p>
Privileges	<p>You must have one of the following privileges to run this command:</p> <pre>platadm, platop</pre> <p>Can execute the command for all domains.</p> <pre>domainadm, domainmgr, domainop</pre> <p>Can execute the command only for accessible domains.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:</p> <pre>-d <i>domain_id</i> Domain identifier. <i>domain_id</i> can be 0-23 depending on system configuration.</pre> <pre>-h Displays usage statement.</pre> <p>When used with other options or operands, an error occurs.</p> <pre>-v Specifies verbose output.</pre>
EXAMPLES	<p>EXAMPLE 1 Displaying All COD Information</p> <p>The output shown is what you would see if you had domainadm, domainop, or domainmgr privileges for Domain 1.</p> <pre>XSCF> showcod</pre> <pre>PROC RTUs reserved for domain 1 : 0</pre> <p>EXAMPLE 2 Displaying All COD Information</p>

The output shown is what you would see if you had platform privileges.

```
XSCF> showcod
Chassis HostID : 81000001
PROC RTUs installed : 8
PROC Headroom Quantity : 0
PROC RTUs reserved for domain 0 : 4
PROC RTUs reserved for domain 1 : 0
PROC RTUs reserved for domain 2 : 0
PROC RTUs reserved for domain 3 : 0
PROC RTUs reserved for domain 4 : 0
PROC RTUs reserved for domain 5 : 0
PROC RTUs reserved for domain 6 : 0
PROC RTUs reserved for domain 7 : 0
PROC RTUs reserved for domain 8 : 0
PROC RTUs reserved for domain 9 : 0
PROC RTUs reserved for domain 10 : 0
PROC RTUs reserved for domain 11 : 0
PROC RTUs reserved for domain 12 : 0
PROC RTUs reserved for domain 13 : 0
PROC RTUs reserved for domain 14 : 0
PROC RTUs reserved for domain 15 : 0
```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

setcod(8)

NAME	showcodlicense - display the current Capacity on Demand (COD) right-to-use (RTU) licenses stored in the COD license database										
SYNOPSIS	showcodlicense [-r] [-v] showcodlicense -h										
DESCRIPTION	<p>showcodlicense(8) displays COD license information stored in the COD license database.</p> <p>The showcodlicense(8) command is not available on the M3000 server.</p> <p>When used without options it displays the current licenses.</p>										
Privileges	<p>You must have platadm or platop privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>										
OPTIONS	<p>The following options are supported:</p> <p>-h Displays usage statement.</p> <p> When used with other options or operands, an error occurs.</p> <p>-r Displays the license information in the raw <i>license-signature</i> format, as stored in the COD license database.</p> <p>-v Specifies verbose output. Displays both the formatted license information and raw <i>license-signature</i> data.</p>										
EXTENDED DESCRIPTION	<p>The showcodlicense command displays the following COD information:</p> <table border="0" style="margin-left: 2em;"> <tr> <td style="padding-right: 1em;">Description</td> <td>Type of resource (processor).</td> </tr> <tr> <td>Ver</td> <td>Version number of the license, which is always set to 01.</td> </tr> <tr> <td>Expiration</td> <td>Expiration of the license.</td> </tr> <tr> <td>Count</td> <td>Number of right-to-use licenses granted for the given resource.</td> </tr> <tr> <td>Status</td> <td>GOOD, which indicates that the given resource is valid, or EXPIRED, which indicates that the resource license is no longer valid.</td> </tr> </table>	Description	Type of resource (processor).	Ver	Version number of the license, which is always set to 01.	Expiration	Expiration of the license.	Count	Number of right-to-use licenses granted for the given resource.	Status	GOOD, which indicates that the given resource is valid, or EXPIRED, which indicates that the resource license is no longer valid.
Description	Type of resource (processor).										
Ver	Version number of the license, which is always set to 01.										
Expiration	Expiration of the license.										
Count	Number of right-to-use licenses granted for the given resource.										
Status	GOOD, which indicates that the given resource is valid, or EXPIRED, which indicates that the resource license is no longer valid.										
EXAMPLES	The following examples display the COD license information:										

EXAMPLE 1 Displaying Formatted License Data

```
XSCF> showcodlicense -v
Description  Ver   Expiration  Count  Status
-----
PROC         01      NONE       16    GOOD
01:84000000:00000001:0301010100:16:00000000:xxxxxxxxxxxxxxxxxxxxxxxx
```

EXAMPLE 2 Displaying Raw License Data

```
XSCF> showcodlicense -r
01:84000000:104:0301010100:3:00000000:xxxxxxxxxxxxxxxx
```

EXIT STATUS

The following exit values are returned:

- 0 Successful completion.
- >0 An error occurred.

SEE ALSO

addcodlicense (8), deletecodlicense (8), showcodusage (8)

NAME	showcodusage - display the current usage statistics for Capacity on Demand (COD) resources
SYNOPSIS	showcodusage [-v] [-M] [-p resource domain all] showcodusage -h
DESCRIPTION	<p>showcodusage(8) shows current information about COD right-to-use (RTU) licenses in use.</p> <p>The showcodusage(8) command is not available on the M3000 server.</p> <p>By default, this command displays a summary of COD RTU licenses used and installed, along with the current state of each resource. When used without options, it displays the current usage.</p>
Privileges	<p>You must have one of the following privileges to run this command:</p> <p>platadm, platop, fieldeng:</p> <p>Can run this command for all resources and domains.</p> <p>domainadm, domainmgr, domainop:</p> <p>Can run this command for available resources only for those domains that you can access.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p>-h Displays usage statement.</p> <p> When used with other options or operands, an error occurs.</p> <p>-M Displays text by page. This option provides a function that is the same as that of the more command.</p> <p>-p domain Displays the license usage for each domain. The statistics reported include the number of COD RTU licenses used by the domain, resources assigned to the domain, and COD RTU licenses reserved for the domain.</p> <p>-p resource Displays license usage by resource type.</p> <p>-p all Displays all COD usage information.</p> <p>-v Specifies verbose output. Displays all available COD usage information, including COD RTU license use for both the system and its domains.</p>

**EXTENDED
DESCRIPTION**

The `showcodusage -p resource` command displays the following COD usage information for the system:

Resource	Identifies the type of COD resources available (processors).	
In Use	Specifies the number of COD CPUs currently used in the system.	
Installed	Specifies the number of COD CPUs installed in the system.	
License	Specifies the number of COD RTU licenses installed.	
Status	Specifies one of the following COD attributes:	
	OK	Indicates that there are sufficient licenses for the COD CPUs in use. Also displays the number of remaining COD resources available and the number of any instant access CPUs (headroom) available.
	HEADROOM	The number of instant access COD CPUs in use.
	Violation	Indicates a COD RTU license violation exists. Displays the number of COD CPUs in use that exceeds the number of COD RTU licenses available. This situation can occur when you force the deletion of a COD RTU license key from the COD RTU license database, but the COD CPU associated with the license key is still in use.

The `showcodusage -p domain` command displays the following COD usage information for each domain:

Domain/Resource	Identifies COD RTU resource (processor) for each domain. An Unused processor is a COD CPU that has not yet been assigned to a domain.	
In Use	Specifies the number of COD CPUs currently used in the domain.	

Installed	Specifies the number of COD CPU resources installed in the domain.	
Reserved	Specifies the number of COD RTU licenses allocated to the domain.	
Status	Contains one of the following when the <code>-v</code> option is specified:	
	Licensed	The domain COD CPU has a COD RTU license and is in use.
	Unlicensed	A COD RTU license for the domain COD CPU could not be obtained and it is not in use.
	Unused	The COD CPU is not in use.

EXAMPLES

Users with platform administrator privileges can view both resource and domain usage summaries. Users with domain administrator privileges can view only the domain usage summaries for which they have privileges, and a report of unused licenses.

EXAMPLE 1 Displaying COD Usage by Resource

```
XSCF> showcodusage -p resource
Resource  In Use  Installed  Licensed  Status
-----  -
PROC      4       4          16      OK: 12 available
```

EXAMPLE 2 Displaying COD Usage by Domain

```
XSCF> showcodusage -p domains
Domain/Resource  In Use  Installed  Reserved
-----
0 - PROC         4       4          0
1 - PROC         4       4          0
2 - PROC         4       4          0
3 - PROC         4       4          0
4 - PROC         0       0          0
Unused - PROC    0       0          12
```

EXAMPLE 3 Displaying COD Usage by Resource and Domain: M8000 Server With CMU00

Quad-XSB, CMU02 Uni-XSB

XSCF> **showcodusage -v**

Resource	In Use	Installed	Licensed	Status
PROC	0	8	0	OK: 0 available Headroom: 2

Domain/Resource	In Use	Installed	Reserved	Status
0 - PROC	0	8	0	
00-0 - PROC	0	1		
CMU00-CPU0				Unused
00-1 - PROC	0	1		
CMU00-CPU1				Unused
00-2 - PROC	0	1		
CMU00-CPU2				Unused
00-3 - PROC	0	1		
CMU00-CPU3				Unused
02-0 - PROC	0	4		
CMU02-CPU0				Unused
CMU02-CPU1				Unused
CMU02-CPU2				Unused
CMU02-CPU3				Unused
1 - PROC	0	0	0	
2 - PROC	0	0	0	
3 - PROC	0	0	0	
4 - PROC	0	0	0	
5 - PROC	0	0	0	
6 - PROC	0	0	0	
7 - PROC	0	0	0	
8 - PROC	0	0	0	
9 - PROC	0	0	0	
10 - PROC	0	0	0	
11 - PROC	0	0	0	
12 - PROC	0	0	0	

```

13 - PROC          0          0          0
14 - PROC          0          0          0
15 - PROC          0          0          0
Unused - PROC      0          0          2

```

EXAMPLE 4 Displaying COD Usage by Resource and Domain: M5000 Server

```

XSCF> showcodusage -v
Resource  In Use  Installed  Licensed  Status
-----  -----  -----  -----  -----
PROC          0          4          0  OK: 0 available
Domain/Resource  In Use  Installed  Reserved  Status
-----  -----  -----  -----  -----
0 - PROC          0          0          0
1 - PROC          0          0          0
2 - PROC          0          0          0
3 - PROC          0          0          0
Unused - PROC      0          4          0
          00-0 - PROC  0          4
          CPUM00-CPU0          Unused
          CPUM00-CPU1          Unused
          CPUM01-CPU0          Unused
          CPUM01-CPU1          Unused

```

EXIT STATUS The following exit values are returned:

```

0          Successful completion.
>0        An error occurred.

```

SEE ALSO **addcodlicense (8)**, **deletecodlicense (8)**, **showcodlicense (8)**

showcodusage(8)



NAME	showconsolepath - displays information on the domain console that is currently connected														
SYNOPSIS	<p>showconsolepath -a</p> <p>showconsolepath -d <i>domain_id</i></p> <p>showconsolepath -h</p>														
DESCRIPTION	<p>The showconsolepath(8) command displays information on the domain console that is currently connected.</p> <p>The following information can be displayed:</p> <table border="0"> <tr> <td>User</td> <td>User account of the XSCF connected to the domain console</td> </tr> <tr> <td>DID</td> <td>Domain ID</td> </tr> <tr> <td>ro/rw</td> <td>Domain console type</td> </tr> <tr> <td></td> <td>ro Read-only console</td> </tr> <tr> <td></td> <td>rw Writable console</td> </tr> <tr> <td>escape</td> <td>Escape mark specified for the console</td> </tr> <tr> <td>Date</td> <td>Date connected to the domain console</td> </tr> </table>	User	User account of the XSCF connected to the domain console	DID	Domain ID	ro/rw	Domain console type		ro Read-only console		rw Writable console	escape	Escape mark specified for the console	Date	Date connected to the domain console
User	User account of the XSCF connected to the domain console														
DID	Domain ID														
ro/rw	Domain console type														
	ro Read-only console														
	rw Writable console														
escape	Escape mark specified for the console														
Date	Date connected to the domain console														
Privileges	<p>You must have one of the following privileges to run this command:</p> <p>useradm, platadm, platop</p> <p> Can run this command for all domains.</p> <p>domainadm, domainmgr, domainop</p> <p> Can run this command only for your accessible domains.</p> <p>Refer to setprivileges(8) for more information.</p>														
OPTIONS	<p>The following options are supported.</p> <table border="0"> <tr> <td>-a</td> <td>Displays console information on all domains that can be accessed.</td> </tr> <tr> <td>-d <i>domain_id</i></td> <td>Specifies only one ID of the domain for which information is to be displayed. <i>domain_id</i> can be 0-23 depending on the system configuration.</td> </tr> <tr> <td>-h</td> <td>Displays usage statement. When used with other options or operands, an error occurs.</td> </tr> </table>	-a	Displays console information on all domains that can be accessed.	-d <i>domain_id</i>	Specifies only one ID of the domain for which information is to be displayed. <i>domain_id</i> can be 0-23 depending on the system configuration.	-h	Displays usage statement. When used with other options or operands, an error occurs.								
-a	Displays console information on all domains that can be accessed.														
-d <i>domain_id</i>	Specifies only one ID of the domain for which information is to be displayed. <i>domain_id</i> can be 0-23 depending on the system configuration.														
-h	Displays usage statement. When used with other options or operands, an error occurs.														

showconsolepath(8)

EXTENDED DESCRIPTION

Only one writable console and one or more read-only consoles can be connected to one domain.

EXAMPLES

EXAMPLE 1 Displays console information on all domains that can be accessed.

```
XSCF> showconsolepath -a
```

User	DID	ro/rw	escape	Date
nakagawa	00	rw	@	Fri Jul 29 21:23:34
hana	00	ro	#	Fri Jul 29 09:49:12
k-okano	00	ro	#	Fri Jul 29 18:21:50
yuuki	01	rw		Fri Jul 29 10:19:18
uchida	01	ro	*	Fri Jul 29 13:30:41

EXIT STATUS

The following exit values are returned:

0 Successful completion.
>0 An error occurred.

SEE ALSO

console(8), **sendbreak(8)**

NAME	showdate - display the date and time of XSCF
SYNOPSIS	showdate [-u] showdate -h
DESCRIPTION	The showdate(8) command displays the date and time of XSCF.
Privileges	You must have one of the following privileges to run this command: useradm, platadm, platop, auditadm, auditop, domainadm, domainmgr, domainop, fieldeng Refer to setprivileges(8) for more information.
OPTIONS	The following options are supported: -h Displays usage statement. When used with other options or operands, an error occurs. -u Specifies time in coordinated universal time (UTC). When the -u option is omitted, the local time is specified.
EXTENDED DESCRIPTION	The setdate(8) command sets the XSCF date and time.
EXAMPLES	EXAMPLE 1 Displays the current time as the local time (JST). XSCF> showdate Mon Jan 23 14:53:00 JST 2006 EXAMPLE 2 Displays the current time in UTC. XSCF> showdate -u Mon Jan 23 05:56:15 UTC 2006
EXIT STATUS	The following exit values are returned: 0 Successful completion. >0 An error occurred.
SEE ALSO	setdate (8), settimezone (8), showtimezone (8)

showdate(8)



NAME	showdcl - display the current domain component list (DCL)														
SYNOPSIS	<p>showdcl [-v] -a</p> <p>showdcl [-v] -d <i>domain_id</i> [-1 <i>lsb</i> [-1 <i>lsb</i>]]...</p> <p>showdcl -h</p>														
DESCRIPTION	<p>The showdcl(8) command displays the DCL that has been set by the setdcl(8) command.</p> <p>The DCL is hardware resource information that can be set for a domain or the logical system boards (LSBs) that are components of a domain.</p> <p>An LSB is a board unit recognized by the Solaris OS in a domain. Up to 16 LSBs can be registered for each domain, and they are represented by integer numbers ranging from 0 to 15.</p> <p>An XSB is a board unit that can be used in the system and is one division of a divided physical system board (PSB). An XSB is represented by <i>x-y</i>, a combination of a PSB number and the number of one division of the divided PSB (<i>x</i> is an integer ranging from 00 to 15, and <i>y</i> is an integer ranging from 0 to 3).</p> <p>The showdcl(8) command can display the following information that is part of a DCL:</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;">DID</td> <td>Domain ID</td> </tr> <tr> <td>LSB</td> <td>LSB number. The displayed number is an integer ranging from 00 to 15.</td> </tr> <tr> <td>XSB</td> <td>XSB number corresponding to the LSB. The displayed number has the following format:</td> </tr> <tr> <td></td> <td style="padding-left: 20px;"><i>x-y</i></td> </tr> <tr> <td></td> <td style="padding-left: 20px;">where:</td> </tr> <tr> <td></td> <td style="padding-left: 40px;"><i>x</i> An integer from 00–15.</td> </tr> <tr> <td></td> <td style="padding-left: 40px;"><i>y</i> An integer from 0–3.</td> </tr> </table>	DID	Domain ID	LSB	LSB number. The displayed number is an integer ranging from 00 to 15.	XSB	XSB number corresponding to the LSB. The displayed number has the following format:		<i>x-y</i>		where:		<i>x</i> An integer from 00–15.		<i>y</i> An integer from 0–3.
DID	Domain ID														
LSB	LSB number. The displayed number is an integer ranging from 00 to 15.														
XSB	XSB number corresponding to the LSB. The displayed number has the following format:														
	<i>x-y</i>														
	where:														
	<i>x</i> An integer from 00–15.														
	<i>y</i> An integer from 0–3.														

Status	<p>Domain status. One of the following status is displayed. Additional information may be displayed.</p> <p>Powered Off Power is off.</p> <p>Panic State A panic occurred, and the domain is in the reboot state.</p> <p>Shutdown Started The power-off process is starting.</p> <p>Initialization Phase OpenBoot PROM initialization is in progress.</p> <p>OpenBoot Executing Completed The system is in the OpenBoot PROM (ok prompt) state.</p> <p>Booting/OpenBoot PROM prompt The Solaris OS is booting. Or due to the domain shutdown or reboot, the system is in the OpenBoot PROM running state or is suspended in the OpenBoot PROM (ok prompt) state.</p> <p>Running The Solaris OS is running.</p>
--------	--

If the `-v` option is specified, the following information is added:

<code>Cfg-policy</code>	Degradation range applicable for an error detected during an initial diagnosis of hardware. Any of the following is displayed:
	FRU Degradation of a component (default)
	XSB Degradation of an XSB.
	System Degradation of a domain
<code>No-Mem</code>	Whether to omit the use of memory on a domain. Either of the following is displayed:
	True Omits the use of memory on a domain.
	False Does not omit the use of memory on a domain (default).
<code>No-IO</code>	Whether to omit the use of I/O devices on a domain. Either of the following is displayed:
	True Omits the use of I/O devices on a domain.
	False Does not omit the use of I/O devices on a domain (default).
<code>Float</code>	Whether to set a priority for the specified LSB as a floating board, relative to other boards. Either of the following is displayed:
	True Gives a higher priority to the LSB to become a floating board.
	False Does not give a higher priority regarding floating boards (default).

Privileges

You must have one of the following privileges to run this command:

`platadm, platop, fieldeng`

Can execute the command for all domains.

`domainadm, domainmgr, domainop`

Can execute the command only for accessible domain.

Refer to `setprivileges(8)` for more information.

OPTIONS

The following options are supported:.

- a Displays information that is set for all domains.
- d *domain_id* Specifies the ID of the domain for which information is to be displayed. The *domain_id* can be 0–23 depending on the system configuration.
- h Displays usage statement. When used with other options or operands, an error occurs.
- l *lsb* Specifies the LSB number whose information is to be displayed. Multiple -l options can be specified by delimiting them with spaces. Specify an *lsb* value by using an integer ranging from 0 to 15. If *lsb* is omitted, all the LSBs in the domain are targets.
- v Also displays information on Cfg-policy, No-Mem, No-IO, and Float in the DCL.

EXTENDED DESCRIPTION

- An XSB for which the floating board priority is set to a low value is difficult to use as a floating board. Accordingly, it is difficult for the system board to affect the domain Solaris OS.
- The `setdcl(8)` command sets the DCL.

EXAMPLES

EXAMPLE 1 Displays detailed information on the DCL that is set for domain ID 0

```
XSCF> showdcl -d 0
DID  LSB  XSB  Status
00
    00  00-0
    04  01-0
    08  02-0
    12  03-0
```

EXAMPLE 2 Displays details in the DCL that is set for domain ID 0.

```
XSCF> showdcl -v -d 0
DID  LSB  XSB  Status  No-Mem  No-IO  Float  Cfg-policy
00
    00  00-0      False  False  False  FRU
    01  -
    02  -
```

```

03  -
04  01-0      False   True    False
05  -
06  -
07  -
08  02-0      True    True    True
09  -
10  -
11  -
12  03-0      True    True    False
13  -
14  -
15  -

```

EXAMPLE 3 Displays details in the DCL that are set for all domains.

```

XSCF> showdcl -v -a

```

DID	LSB	XSB	Status	No-Mem	No-IO	Float	Cfg-policy
00			Running				FRU
	00	00-0		False	False	False	
	01	-					
	02	-					
	03	-					
	04	01-0		False	True	False	
	05	-					
	06	-					
	07	-					
	08	02-0		True	True	True	
	09	-					
	10	-					
	11	-					
	12	03-0		True	True	False	
	13	-					
	14	-					

showdcl(8)

```
15 -
-----
01          Running (Waiting for OS Shutdown)  FRU
00  01-2          True      True      False
01  04-0          False     False     False
02  -
03  -
04  -
05  -
06  -
07  05-0          True      False     False
08  -
09  -
10  -
11  -
12  -
13  -
14  06-0          True      True      True
15  -
-----
:
:
```

EXIT STATUS

The following exit values are returned:

0 Successful completion.
>0 An error occurred.

SEE ALSO

addboard (8), **deleteboard** (8), **moveboard** (8), **setdcl** (8), **setupfru** (8), **showboards** (8), **showdevices** (8), **showfru** (8)

NAME	showdevices - display current information on an eXtended System Board (XSB)																				
SYNOPSIS	<p>showdevices [-v] [-p bydevice byboard query force] <i>xsb</i></p> <p>showdevices [-v] [-p bydevice byboard] -d <i>domain_id</i></p> <p>showdevices -h</p>																				
DESCRIPTION	<p>The showdevices(8) command displays the information of the physical devices configured on XSB and their available resources of these devices.</p> <p>The information of available resources can be obtained for the devices managed by the operating system. The command can also display in advance whether the XSB can be disconnected from the domain using the dynamic reconfiguration (DR) function.</p> <p>The following types of information are displayed:</p> <p>Common:</p> <table border="0" style="margin-left: 20px;"> <tr> <td>DID</td> <td>Domain ID</td> </tr> <tr> <td>XSB</td> <td>XSB number</td> </tr> </table> <p>CPU:</p> <table border="0" style="margin-left: 20px;"> <tr> <td>id</td> <td>processor ID</td> </tr> <tr> <td>state</td> <td>status of processor</td> </tr> <tr> <td>speed</td> <td>CPU frequency (MHz)</td> </tr> <tr> <td>ecache</td> <td>CPU external cache size (MB)</td> </tr> </table> <p>MEMORY:</p> <table border="0" style="margin-left: 20px;"> <tr> <td>board mem</td> <td>Size of memory mounted on the XSB (MB)</td> </tr> <tr> <td>perm mem</td> <td>Size of memory that mounted and cannot be relocated on the XSB (MB)</td> </tr> <tr> <td>base address</td> <td>Physical address of memory mounted on the XSB</td> </tr> <tr> <td>domain mem</td> <td>Size of memory on the domain (MB)</td> </tr> </table>	DID	Domain ID	XSB	XSB number	id	processor ID	state	status of processor	speed	CPU frequency (MHz)	ecache	CPU external cache size (MB)	board mem	Size of memory mounted on the XSB (MB)	perm mem	Size of memory that mounted and cannot be relocated on the XSB (MB)	base address	Physical address of memory mounted on the XSB	domain mem	Size of memory on the domain (MB)
DID	Domain ID																				
XSB	XSB number																				
id	processor ID																				
state	status of processor																				
speed	CPU frequency (MHz)																				
ecache	CPU external cache size (MB)																				
board mem	Size of memory mounted on the XSB (MB)																				
perm mem	Size of memory that mounted and cannot be relocated on the XSB (MB)																				
base address	Physical address of memory mounted on the XSB																				
domain mem	Size of memory on the domain (MB)																				

When memory is being disconnected, the following items are displayed:

target	XSB	XSB number at the move destination
deleted	mem	Size of memory which was already deleted (MB)
remaining	mem	Size of remaining memory to be deleted (MB)

I/O devices:

device	Instance name of I/O device
resource	Managed resource name
usage	Description of the instance using resources
query	Results of an off-line inquiry about resources

Privileges

You must have one of the following privileges to run this command:

platadm, platop, fieldeng

Can run this command for all domains.

domainadm, domainmgr, domainop

Can run this command only for your accessible domains.

Refer to `setprivileges(8)` for more information.

OPTIONS

The following options are supported.

-d <i>domain_id</i>	Specifies the ID of the domain for which information is to be displayed. <i>domain_id</i> can be 0–23 depending on the system configuration.
-h	Displays usage statement. When used with other options or operands, an error occurs.
-p byboard	Displays results organized by XSB. The results can be further summarized by device and displayed. If the -p option is omitted, "-p bydevice" is used.
-p bydevice	Displays results organized by device type (CPU, memory, I/O, etc.). If the -p option is omitted, "-p bydevice" is used.

- p force Predicts system resources deleted from the Solaris OS when an XSB is forcibly disconnected by "deleteboard -f" command. If the -p option is omitted, "-p bydevice" is used.
- p query Predicts system resources deleted from the Solaris OS when an XSB is disconnected by deleteboard command. If the -p option is omitted, "-p bydevice" is used.
- v Displays information on all I/O devices, including those that are not management targets. As information on the I/O devices that are not management targets, however, only physical configurations are displayed, and resources and use states are not displayed.

OPERANDS

The following operand is supported:

xsb Specifies the XSB number for which information is to be displayed. The following *xsb* form is accepted:

x-y

where:

x An integer from 00–15.

y An integer from 0–3.

EXAMPLES

EXAMPLE 1 Displays the information of the physical devices configured on the XSB#00-0 and their available resources.

```
XSCF> showdevices 00-0
```

```
CPU:
```

```
----
```

DID	XSB	id	state	speed	ecache
00	00-0	40	on-line	2048	4
00	00-0	41	on-line	2048	4
00	00-0	42	on-line	2048	4
00	00-0	43	on-line	2048	4

```
Memory:
```

```
-----
```

board	perm	base	domain	target	deleted	remaining
-------	------	------	--------	--------	---------	-----------

showdevices(8)

DID	XSB	mem MB	mem MB	address	mem MB	XSB	mem MB	mem MB
00	00-0	2048	1290	0x0000003c000000000	2048	03-0	250	1500
00	00-1	2048	0	0x00000038000000000	2048		0	0
00	00-2	2048	0	0x00000034000000000	2048		0	0
00	00-3	2048	0	0x00000030000000000	2048		0	0
00	01-0	2048	0	0x0000002c000000000	2048		1024	0
00	02-0	2048	0	0x00000028000000000	2048		0	0

IO Devices:

DID	XSB	device	resource	usage
00	00-0	sd3	/dev/dsk/c0t3d0s0	mounted filesystem "/"
00	00-0	sd3	/dev/dsk/c0t3s0s1	dump device (swap)
00	00-0	sd3	/dev/dsk/c0t3s0s1	swap area
00	00-0	sd3	/dev/dsk/c0t3d0s3	mounted filesystem "/var"
00	00-0	sd3	/var/run	mounted filesystem "/var/run"

EXAMPLE 2 Displays detail information of the physical devices and their available resources in domain ID 0.

```
XSCF> showdevices -v -d 0
```

CPU:

DID	XSB	id	state	speed	ecache
00	00-0	40	on-line	2048	4
00	00-0	41	on-line	2048	4
00	00-0	42	on-line	2048	4
00	00-0	43	on-line	2048	4
00	01-0	50	on-line	2048	4
00	01-0	51	on-line	2048	4
00	01-0	52	on-line	2048	4
00	01-0	53	on-line	2048	4

Memory:

```

-----
          board  perm  base          domain target  deleted  remaining
DID XSB  mem MB  mem MB  address          mem MB  XSB      mem MB  mem MB
00 00-0   2048   1290 0x000003c000000000  4096 00-1      250    1500
00 01-0    2048     0 0x000002c000000000   4096

```

IO Devices:

```

-----
DID XSB      device  resource          usage
00 00-0      sd0
00 00-0      sd1
00 00-0      sd2
00 00-0      sd3      /dev/dsk/c0t3d0s0  mounted filesystem "/"
00 00-0      sd3      /dev/dsk/c0t3s0s1  dump device (swap)
00 00-0      sd3      /dev/dsk/c0t3s0s1  swap area
00 00-0      sd3      /dev/dsk/c0t3d0s3  mounted filesystem "/var"
00 00-0      sd3      /var/run           mounted filesystem "/var/run"
00 00-0      sd4
00 00-0      sd5
00 00-0      sd6

```

EXIT STATUS

The following exit values are returned:

```

0          Successful completion.
>0        An error occurred.

```

SEE ALSO

addboard(8), **deleteboard**(8), **moveboard**(8), **setdcl**(8), **setupfru**(8), **showboards**(8), **showdcl**(8), **showfru**(8)

showdevices(8)



NAME	showdomainmode - display the modes of operation for the specified domain																												
SYNOPSIS	<p>showdomainmode -d <i>domain_id</i></p> <p>showdomainmode -h</p>																												
DESCRIPTION	<p>showdomainmode(8) command displays the modes of operation that is set for the specified domain.</p> <p>The following states are displayed:</p> <table border="0" style="width: 100%;"> <tr> <td style="padding-right: 20px;">HOST-ID</td> <td>Displays the host ID.</td> </tr> <tr> <td style="padding-right: 20px;">Diagnostic Level</td> <td>Displays the OpenBoot PROM diagnostic level. One of the following is displayed:</td> </tr> <tr> <td style="padding-right: 40px;">none</td> <td>None</td> </tr> <tr> <td style="padding-right: 40px;">min</td> <td>Standard</td> </tr> <tr> <td style="padding-right: 40px;">max</td> <td>Maximum</td> </tr> <tr> <td style="padding-right: 20px;">Secure Mode</td> <td>Displays the states of the host watchdog function and function that suppresses break signal reception. One of the following is displayed:</td> </tr> <tr> <td style="padding-right: 40px;">on</td> <td>Enabled</td> </tr> <tr> <td style="padding-right: 40px;">off</td> <td>Disabled</td> </tr> <tr> <td style="padding-right: 20px;">Autoboot</td> <td>Displays the state of the auto boot function. One of the following is displayed:</td> </tr> <tr> <td style="padding-right: 40px;">on</td> <td>Enabled</td> </tr> <tr> <td style="padding-right: 40px;">off</td> <td>Disabled</td> </tr> <tr> <td style="padding-right: 20px;">CPU Mode</td> <td>Way of determining the CPU operational mode mounted on the domain. One of the following is displayed.</td> </tr> <tr> <td style="padding-right: 40px;">auto</td> <td>Automatically determines at domain startup</td> </tr> <tr> <td style="padding-right: 40px;">compatible</td> <td>Sets to the SPARC64 VI compatible mode regardless of the CPUs mounted</td> </tr> </table>	HOST-ID	Displays the host ID.	Diagnostic Level	Displays the OpenBoot PROM diagnostic level. One of the following is displayed:	none	None	min	Standard	max	Maximum	Secure Mode	Displays the states of the host watchdog function and function that suppresses break signal reception. One of the following is displayed:	on	Enabled	off	Disabled	Autoboot	Displays the state of the auto boot function. One of the following is displayed:	on	Enabled	off	Disabled	CPU Mode	Way of determining the CPU operational mode mounted on the domain. One of the following is displayed.	auto	Automatically determines at domain startup	compatible	Sets to the SPARC64 VI compatible mode regardless of the CPUs mounted
HOST-ID	Displays the host ID.																												
Diagnostic Level	Displays the OpenBoot PROM diagnostic level. One of the following is displayed:																												
none	None																												
min	Standard																												
max	Maximum																												
Secure Mode	Displays the states of the host watchdog function and function that suppresses break signal reception. One of the following is displayed:																												
on	Enabled																												
off	Disabled																												
Autoboot	Displays the state of the auto boot function. One of the following is displayed:																												
on	Enabled																												
off	Disabled																												
CPU Mode	Way of determining the CPU operational mode mounted on the domain. One of the following is displayed.																												
auto	Automatically determines at domain startup																												
compatible	Sets to the SPARC64 VI compatible mode regardless of the CPUs mounted																												

showdomainmode(8)

Privileges	<p>You must have one of the following privileges to run this command:</p> <table><tr><td>platadm, fieldeng</td><td>Can run this command for all domains.</td></tr><tr><td>domainadm</td><td>Can run this command only for your managed domains.</td></tr></table> <p>Refer to <code>setprivileges(8)</code> for more information.</p>	platadm, fieldeng	Can run this command for all domains.	domainadm	Can run this command only for your managed domains.
platadm, fieldeng	Can run this command for all domains.				
domainadm	Can run this command only for your managed domains.				
OPTIONS	<p>The following operands are supported:</p> <table><tr><td><code>-d domain_id</code></td><td>Specifies the domain ID of the domain to be displayed. <i>domain_id</i> can be 0–23 depending on the system configuration.</td></tr><tr><td><code>-h</code></td><td>Displays usage statement. When used with other options or operands, an error occurs.</td></tr></table>	<code>-d domain_id</code>	Specifies the domain ID of the domain to be displayed. <i>domain_id</i> can be 0–23 depending on the system configuration.	<code>-h</code>	Displays usage statement. When used with other options or operands, an error occurs.
<code>-d domain_id</code>	Specifies the domain ID of the domain to be displayed. <i>domain_id</i> can be 0–23 depending on the system configuration.				
<code>-h</code>	Displays usage statement. When used with other options or operands, an error occurs.				
EXTENDED DESCRIPTION	<ul style="list-style-type: none">■ If the Mode switch of the operator panel is set to <i>Service</i>, the settings of the modes of operation for the specified domain have the following values, regardless of the domain mode displayed by the <code>showdomainmode(8)</code> command:<ul style="list-style-type: none">■ OpenBoot PROM diagnostic level (<i>Diagnostic Level</i>), CPU operational mode (<i>CPU Mode</i>): operates as the <code>showdomainmode(8)</code> command display■ Host watchdog and suppress break signal reception (<i>Secure Mode</i>), auto boot function (<i>Autoboot</i>): <code>off</code>■ When the OpenBoot PROM environmental variable '<code>auto-boot?</code>' has been set to <code>false</code>, the auto boot function is disabled.■ The <code>setdomainmode(8)</code> command sets the modes of operation specified for a domain.				
EXAMPLES	<p>EXAMPLE 1 Displays the modes of operation that is set for domain ID 0.</p> <pre>XSCF> showdomainmode -d 0 Host-ID :0f010f10 Diagnostic Level :min Secure Mode :on Autoboot :on CPU Mode :auto</pre>				
EXIT STATUS	<p>The following exit values are returned:</p> <table><tr><td>0</td><td>Successful completion.</td></tr><tr><td>>0</td><td>An error occurred.</td></tr></table>	0	Successful completion.	>0	An error occurred.
0	Successful completion.				
>0	An error occurred.				

SEE ALSO | **setdomainmode** (8)

showdomainmode(8)



NAME	showdomainstatus - display the current domain component list (DCL)
SYNOPSIS	<p>showdomainstatus -d <i>domain_id</i></p> <p>showdomainstatus -a</p> <p>showdomainstatus -h</p>
DESCRIPTION	<p>The showdomainstatus(8) command displays the current status of the specified domain.</p> <p>One of the following states is displayed for each domain. Additional information may be displayed.</p> <p>Powered Off Power is off.</p> <p>Panic State A panic occurred, and the domain is in the reboot state.</p> <p>Shutdown Started The power-off process is starting.</p> <p>Initialization Phase OpenBoot PROM initialization is in progress.</p> <p>OpenBoot Execution Completed The system is in the OpenBoot PROM (ok prompt) state.</p> <p>Booting/OpenBoot PROM prompt The Solaris OS is booting. Or due to the domain shutdown or reboot, the system is in the OpenBoot PROM running state or is suspended in the OpenBoot PROM (ok prompt) state.</p> <p>Running The Solaris OS is running.</p> <p>- Domain is not defined.</p>
Privileges	<p>You must have one of the following privileges to run this command:</p> <p>useradm, platadm, platop, fieldeng</p>

Can run this command for all domains.

domainadm, domainmgr, domainop

Can run this command only for your accessible domains.

Refer to `setprivileges(8)` for more information.

OPTIONS

The following options are supported.

- a Displays status information on all domains that can be accessed.
- d *domain_id* Specifies only one ID of the domain to be displayed. *domain_id* can be 0–23 depending on the system configuration.
- h Displays usage statement. When used with other options or operands, an error occurs.

EXAMPLES

EXAMPLE 1 Displays status information on all domains.

```
XSCF> showdomainstatus -a
DID          Domain Status
00           Running
01           Running (Waiting for OS Shutdown)
02           Powered Off
03           Panic State
04           Shutdown Started
05           Booting/OpenBoot PROM prompt
06           Initialization Phase
07           OpenBoot Execution Completed
```

EXIT STATUS

The following exit values are returned:

- 0 Successful completion.
- >0 An error occurred.

SEE ALSO

`poweroff(8)`, `poweron(8)`, `reset(8)`, `showdcl(8)`

NAME	showdscp - display the IP addresses assigned to the Domain to Service Processor Communications Protocol (DSCP)
SYNOPSIS	<p>showdscp</p> <p>showdscp [-v] [-p]</p> <p>showdscp [-v] [-p] -d <i>domain_id</i></p> <p>showdscp [-v] [-p] -s</p> <p>showdscp -h</p>
DESCRIPTION	<p>showdscp(8) displays the IP addresses assigned for DSCP usage, the IP addresses for an individual domain, the Service Processor, or for the entire system. When used without options, it displays current IP data.</p> <p>When displaying IP addresses for all DSCP links in the system, the output is a table. The table is sorted by numerical domain IDs.</p> <p>When displaying IP addresses for a particular domain or just the Service Processor, then the output is not a table but simply the IP address of the specified domain or Service Processor.</p> <p>The -p option can be used to generate parsable output that would then be suitable for use in a script. Parsable displays of individual IP addresses exclude any additional labels, and only an IPv4 address in dotted-decimal form is output. The parsable version of tabular output includes only the values (no table headings are included), and each column is separated by a single tab character.</p>
Privileges	<p>You must have one of the following privileges to run this command:</p> <p>fieldeng, platadm, platop:</p> <p>Can display any DSCP IP information.</p> <p>domainadm, domainmgr, domainop:</p> <p>Can display individual IP addresses for domains for which you have privileges only.</p> <p>Refer to setprivileges(8) for more information.</p>

OPTIONS

The following options are supported:

- d *domain_id* Displays an individual domain's IP address.
- h Displays usage statement.
 When used with other options or operands, an error occurs.
- p Generates parsable output.
- s Displays the Service Processor's IP address.
- v Specifies verbose output. Prints additional information about internal progress of the program's operations to the screen.

EXAMPLES

Caution – The IP addresses shown in the following examples are examples only.

EXAMPLE 1 Displaying a Table of All DSCP IP Addresses

```
XSCF> showdscp
```

```
DSCP Configuration
```

```
Network: 10.1.1.0
```

```
Netmask: 255.255.255.0
```

Location	Address
-----	-----
XSCF	10.1.1.1
Domain #00	10.1.1.2
Domain #01	10.1.1.3
Domain #02	10.1.1.4
Domain #03	10.1.1.5
Domain #04	10.1.1.6
Domain #05	10.1.1.7
Domain #06	10.1.1.8
Domain #07	10.1.1.9
Domain #08	10.1.1.10
Domain #09	10.1.1.11
Domain #10	10.1.1.12

```

Domain #11  10.1.1.13
Domain #12  10.1.1.14
Domain #13  10.1.1.15
Domain #14  10.1.1.16
Domain #15  10.1.1.17
Domain #16  10.1.1.18
Domain #17  10.1.1.19
Domain #18  10.1.1.20
Domain #19  10.1.1.21
Domain #20  10.1.1.22
Domain #21  10.1.1.23
Domain #22  10.1.1.24
Domain #23  10.1.1.25

```

EXAMPLE 2 Displaying a Specific Domain's IP Address

```

XSCF> showdscp -d 1
Domain #01 Address: 10.1.1.3

```

EXAMPLE 3 Displaying a Specific Domain's IP Address in a Parsable Form

```

XSCF> showdscp -p -d 1
Domain[1] 10.1.1.3

```

EXAMPLE 4 Displaying All DSCP Address Information In a Parsable Form

```

XSCF> showdscp -p
Network 10.1.1.0
Netmask 255.255.255.0
XSCF 10.1.1.1
Domain[0] 10.1.1.2
Domain[1] 10.1.1.3
Domain[2] 10.1.1.4
Domain[3] 10.1.1.5
Domain[4] 10.1.1.6
Domain[5] 10.1.1.7

```

showdscp(8)

```
Domain[6]      10.1.1.8
Domain[7]      10.1.1.9
Domain[8]      10.1.1.10
Domain[9]      10.1.1.11
...
```

EXIT STATUS

The following exit values are returned:

```
0              Successful completion.
>0            An error occurred.
```

SEE ALSO

setdscp(8)

NAME	showdualpowerfeed - display the current setting of dual power feed mode
SYNOPSIS	showdualpowerfeed showdualpowerfeed -h
DESCRIPTION	<p>The showdualpowerfeed(8) command displays the current setting of dual power feed mode in the system.</p> <p>The showdualpowerfeed(8) command is valid in the M3000/M4000/M5000 servers only.</p> <p>The dual power feed mode can be set by the setdualpowerfeed(8) command. Also, before the dual power feed mode is changed by the setdualpowerfeed(8) command, the values of changed settings are displayed.</p>
Privileges	<p>You must have platadm or fieldeng privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p>-h Displays usage statement.</p>
EXAMPLES	<p>EXAMPLE 1 Displays the current setting of dual power feed mode in the system.</p> <pre>XSCF> showdualpowerfeed Dual power feed is enabled.</pre> <p>EXAMPLE 2 Changes the dual power feed mode with the setdualpowerfeed(8) command and then displays the current state.</p> <pre>XSCF> showdualpowerfeed enable -> disable</pre> <p>NOTE: Dual power feed will be disabled the next time the platform is powered on.</p>
EXIT STATUS	<p>The following exit values are returned:</p> <p>0 Successful completion.</p> <p>>0 An error occurred.</p>
SEE ALSO	setdualpowerfeed (8)

showdualpowerfeed(8)



NAME	showemailreport - display the email report configuration data
SYNOPSIS	showemailreport [-v] showemailreport -h
DESCRIPTION	showemailreport(8) displays the email reporting configuration data. When used without options, it displays current email report configuration data.
Privileges	You must have platadm, platop or fieldeng privileges to run this command. Refer to setprivileges(8) for more information.
OPTIONS	The following options are supported: -h Displays usage statement. When used with other options or operands, an error occurs. -v Specifies verbose output.
EXTENDED DESCRIPTION	Emailreport information includes whether Emailreporting is enabled. If enabled, it also includes the list of addresses.
EXAMPLES	EXAMPLE 1 Displaying Emailreport configuration XSCF> showemailreport EMail Reporting: enabled Email Recipient Address: admin@company.com, adm2@company.com
EXIT STATUS	The following exit values are returned: 0 Successful completion. >0 An error occurred.
SEE ALSO	setemailreport (8)

showemailreport(8)



NAME	showenvironment - display the intake air temperature and humidity, temperature sensor information, voltage sensor information, and fan speed information about the system														
SYNOPSIS	showenvironment [-M] [<i>type</i>] showenvironment -h														
DESCRIPTION	<p>showenvironment(8) command displays the information listed below.</p> <p>The following types of the information are displayed:</p> <table border="0"> <tr> <td style="vertical-align: top;">Environment information</td> <td>Intake temperature and humidity of the system Humidity can be checked in the M8000/M9000 servers.</td> </tr> <tr> <td style="vertical-align: top;">Temperature information</td> <td>Intake temperature of the system and exhaust temperature of each component You can check the exhaust temperature of the following components. <table border="0"> <tr> <td style="padding-right: 20px;">M3000 server</td> <td>motherboard unit(MBU_A), CPU</td> </tr> <tr> <td>M4000/M5000 servers</td> <td>CPU module(CPUM), I/O unit(IOU)</td> </tr> <tr> <td>M8000/M9000 servers</td> <td>CPU/memory board unit(CMU), CPU module(CPUM), crossbar unit(XBU_B)</td> </tr> </table> </td> </tr> <tr> <td style="vertical-align: top;">Voltage information</td> <td>Voltage sensor value</td> </tr> <tr> <td style="vertical-align: top;">Fan speed information</td> <td>Fan rotational state and revolutions per unit of time</td> </tr> </table>	Environment information	Intake temperature and humidity of the system Humidity can be checked in the M8000/M9000 servers.	Temperature information	Intake temperature of the system and exhaust temperature of each component You can check the exhaust temperature of the following components. <table border="0"> <tr> <td style="padding-right: 20px;">M3000 server</td> <td>motherboard unit(MBU_A), CPU</td> </tr> <tr> <td>M4000/M5000 servers</td> <td>CPU module(CPUM), I/O unit(IOU)</td> </tr> <tr> <td>M8000/M9000 servers</td> <td>CPU/memory board unit(CMU), CPU module(CPUM), crossbar unit(XBU_B)</td> </tr> </table>	M3000 server	motherboard unit(MBU_A), CPU	M4000/M5000 servers	CPU module(CPUM), I/O unit(IOU)	M8000/M9000 servers	CPU/memory board unit(CMU), CPU module(CPUM), crossbar unit(XBU_B)	Voltage information	Voltage sensor value	Fan speed information	Fan rotational state and revolutions per unit of time
Environment information	Intake temperature and humidity of the system Humidity can be checked in the M8000/M9000 servers.														
Temperature information	Intake temperature of the system and exhaust temperature of each component You can check the exhaust temperature of the following components. <table border="0"> <tr> <td style="padding-right: 20px;">M3000 server</td> <td>motherboard unit(MBU_A), CPU</td> </tr> <tr> <td>M4000/M5000 servers</td> <td>CPU module(CPUM), I/O unit(IOU)</td> </tr> <tr> <td>M8000/M9000 servers</td> <td>CPU/memory board unit(CMU), CPU module(CPUM), crossbar unit(XBU_B)</td> </tr> </table>	M3000 server	motherboard unit(MBU_A), CPU	M4000/M5000 servers	CPU module(CPUM), I/O unit(IOU)	M8000/M9000 servers	CPU/memory board unit(CMU), CPU module(CPUM), crossbar unit(XBU_B)								
M3000 server	motherboard unit(MBU_A), CPU														
M4000/M5000 servers	CPU module(CPUM), I/O unit(IOU)														
M8000/M9000 servers	CPU/memory board unit(CMU), CPU module(CPUM), crossbar unit(XBU_B)														
Voltage information	Voltage sensor value														
Fan speed information	Fan rotational state and revolutions per unit of time														
Privileges	<p>You must have one of the following privileges to run this command:</p> <p>useradm, platadm, platop, fieldeng</p> <p>Refer to setprivileges(8) for more information.</p>														
OPTIONS	<p>The following options are supported:</p> <table border="0"> <tr> <td style="padding-right: 20px;">-h</td> <td>Displays usage statement. When used with other options or operands, an error occurs.</td> </tr> <tr> <td>-M</td> <td>Displays text by page. This option provides a function that is the same as that of the <code>more</code> command.</td> </tr> </table>	-h	Displays usage statement. When used with other options or operands, an error occurs.	-M	Displays text by page. This option provides a function that is the same as that of the <code>more</code> command.										
-h	Displays usage statement. When used with other options or operands, an error occurs.														
-M	Displays text by page. This option provides a function that is the same as that of the <code>more</code> command.														

OPERANDS

The following operand is supported:

<i>type</i>	Specifies the one of the type of information to be displayed. The following types can be specified. If this type setting is omitted, intake temperature and humidity information about the system is displayed:
temp	Displays temperature information.
volt	Displays voltage information.
Fan	Displays fan speed information.

EXAMPLES

EXAMPLE 1 Displays the intake temperature and humidity of the system on the M8000/M9000 servers.

```
XSCF> showenvironment
```

```
Temperature:30.71C
```

```
Humidity:90.05%
```

EXAMPLE 2 Displays temperature information about the system and each component on the M8000 server.

```
XSCF> showenvironment temp
```

```
Temperature:30.71C
```

```
CMU#0:30.71C
```

```
CPUM#0-CHIP#0:30.71C
```

```
CPUM#1-CHIP#0:30.71C
```

```
CPUM#2-CHIP#0:30.71C
```

```
CPUM#3-CHIP#0:30.71C
```

```
CMU#1:30.71C
```

```
CPUM#0-CHIP#0:30.71C
```

```
CPUM#1-CHIP#0:30.71C
```

```
CPUM#2-CHIP#0:30.71C
```

```
CPUM#3-CHIP#0:30.71C
```

```
CMU#2:30.71C
```

```
CPUM#0-CHIP#0:30.71C
```

```
CPUM#1-CHIP#0:30.71C
```

```
CPUM#2-CHIP#0:30.71C
```

```
CPUM#3-CHIP#0:30.71C
CMU#3:30.71C
CPUM#0-CHIP#0:30.71C
CPUM#1-CHIP#0:30.71C
CPUM#2-CHIP#0:30.71C
CPUM#3-CHIP#0:30.71C
```

EXAMPLE 3 Displays voltage information about each component on the M4000 server.

```
XSCF> showenvironment volt
MBU_A
  1.0V Power Supply Group:1.010V
  1.8V Power Supply Group:1.700V
CPUM#0-CHIP#0
  1.0V Power Supply Group:1.000V
CPUM#1-CHIP#0
  1.0V Power Supply Group:1.000V
MEMB#0
  1.2V Power Supply Group:1.200V
  1.8V Power Supply Group:1.700V
  2.5V Power Supply Group:2.500V
MEMB#1
  1.2V Power Supply Group:1.200V
  1.8V Power Supply Group:1.700V
  2.5V Power Supply Group:2.500V
MEMB#2
  1.2V Power Supply Group:1.200V
  1.8V Power Supply Group:1.700V
  2.5V Power Supply Group:2.500V
MEMB#3
  1.2V Power Supply Group:1.200V
  1.8V Power Supply Group:1.700V
  2.5V Power Supply Group:2.500V
IOU#0
```

showenvironment(8)

```
1.0V Power Supply Group:1.020V
1.2V Power Supply Group:1.180V
1.5V Power Supply Group:1.500V
1.8V Power Supply Group:1.850V
2.5V Power Supply Group:2.510V
3.3V Power Supply Group:3.300V
5.0V Power Supply Group:5.000V
 12V Power Supply Group:12.000V
-12V Power Supply Group:-12.000V

FANBP
3.3V Power Supply Group:3.300V
5.0V Power Supply Group:5.010V
 12V Power Supply Group:12.020V
-12V Power Supply Group:-12.030V
```

EXAMPLE 4 Displays the fan speed information on the M5000 server.

```
XSCF> showenvironment Fan
FAN_A#0:Low speed
      FAN_A#0: 4101rpm
FAN_A#1:Low speed
      FAN_A#1: 4101rpm
FAN_A#2:Low speed
      FAN_A#2: 4177rpm
FAN_A#3:Low speed
      FAN_A#3: 4101rpm

PSU#0
      PSU#0:Low speed
      PSU#0: 3879rpm
      PSU#0: 3835rpm

PSU#1
      PSU#1:Low speed
      PSU#1: 3924rpm
      PSU#1: 3970rpm
```



```
PSU#2
  PSU#2:Low speed
    PSU#2: 4218rpm
    PSU#2: 4066rpm
PSU#3
  PSU#3:Low speed
    PSU#3: 3835rpm
    PSU#3: 3970rpm
```

EXAMPLE 5 Displays the fan speed information on the M3000 server.

```
XSCF> showenvironment Fan
FAN_A#0:Low speed (level-4)
  FAN_A#0: 4134rpm
FAN_A#1:Low speed (level-4)
  FAN_A#1: 4212rpm
PSU#0
  PSU#0:Low speed (level-4)
    PSU#0: 6436rpm
PSU#1
  PSU#1:Low speed (level-4)
    PSU#1: 6352rpm
```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

showenvironment(8)



NAME	showfru - display the hardware settings of specified device																
SYNOPSIS	<p>showfru <i>device location</i></p> <p>showfru -a <i>device</i></p> <p>showfru -h</p>																
DESCRIPTION	<p>The showfru(8) command displays the hardware settings of specified device by the setupfru(8) command.</p> <p>The command can display the settings of the specified device or of all devices. Only the physical system board (PSB) can be specified as a device.</p> <p>The following settings are displayed:</p> <table border="0" style="margin-left: 2em;"> <tr> <td style="padding-right: 1em;">Device</td> <td>Specified device name. Only sb is displayed.</td> </tr> <tr> <td style="padding-right: 1em;">Location</td> <td>Device location. If the <i>device</i> is "sb", the indicated location is an integer ranging from 00 to 15.</td> </tr> <tr> <td style="padding-right: 1em;">XSB Mode</td> <td>XSB mode set for the PSB. One of the following values is displayed:</td> </tr> <tr> <td style="padding-right: 2em;"></td> <td style="padding-left: 2em;">Uni Uni-XSB</td> </tr> <tr> <td style="padding-right: 2em;"></td> <td style="padding-left: 2em;">Quad Quad-XSB</td> </tr> <tr> <td style="padding-right: 1em;">Memory Mirror Mode</td> <td>Memory mirror mode set for the PSB. One of the following values is displayed:</td> </tr> <tr> <td style="padding-right: 2em;"></td> <td style="padding-left: 2em;">yes Memory mirror mode</td> </tr> <tr> <td style="padding-right: 2em;"></td> <td style="padding-left: 2em;">no Memory no-mirror mode</td> </tr> </table>	Device	Specified device name. Only sb is displayed.	Location	Device location. If the <i>device</i> is "sb", the indicated location is an integer ranging from 00 to 15.	XSB Mode	XSB mode set for the PSB. One of the following values is displayed:		Uni Uni-XSB		Quad Quad-XSB	Memory Mirror Mode	Memory mirror mode set for the PSB. One of the following values is displayed:		yes Memory mirror mode		no Memory no-mirror mode
Device	Specified device name. Only sb is displayed.																
Location	Device location. If the <i>device</i> is "sb", the indicated location is an integer ranging from 00 to 15.																
XSB Mode	XSB mode set for the PSB. One of the following values is displayed:																
	Uni Uni-XSB																
	Quad Quad-XSB																
Memory Mirror Mode	Memory mirror mode set for the PSB. One of the following values is displayed:																
	yes Memory mirror mode																
	no Memory no-mirror mode																
Privileges	<p>You must have platadm or fieldeng privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>																
OPTIONS	<p>The following options are supported.</p> <table border="0" style="margin-left: 2em;"> <tr> <td style="padding-right: 1em;">-a</td> <td>Displays the settings of all devices.</td> </tr> <tr> <td style="padding-right: 1em;">-h</td> <td>Displays usage statement. When used with other options or operands, an error occurs.</td> </tr> </table>	-a	Displays the settings of all devices.	-h	Displays usage statement. When used with other options or operands, an error occurs.												
-a	Displays the settings of all devices.																
-h	Displays usage statement. When used with other options or operands, an error occurs.																

OPERANDS | The following operands are supported:

device | Specifies the device to display. Currently, only the following device can be specified:

sb | Physical system board (PSB)

location | Specifies the location of *device*. If the *device* is "sb", an integer ranging from 00 to 15 can be specified.

EXTENDED DESCRIPTION

The `setupfru(8)` command makes hardware settings for a device.

EXAMPLES

EXAMPLE 1 | Displays the settings of all PSBs.

```
XSCF> showfru -a sb
```

Device	Location	XSB Mode	Memory Mirror Mode
sb	00	Quad	no
sb	01	Uni	yes
sb	02	Quad	no
sb	03	Uni	no

EXIT STATUS

The following exit values are returned:

0 | Successful completion.

>0 | An error occurred.

SEE ALSO

addboard(8), **deleteboard(8)**, **moveboard(8)**, **setdcl(8)**, **setupfru(8)**, **showboards(8)**, **showdcl(8)**, **showdevices(8)**

NAME	showhardconf - display information about field replaceable unit (FRU) installed in the system
SYNOPSIS	showhardconf [-u] [-M] showhardconf -h
DESCRIPTION	<p>showhardconf(8) command displays information about each FRU.</p> <p>The following information is displayed:</p> <ul style="list-style-type: none"> ■ Current configuration and status ■ Number of installed FRUs ■ Domain information ■ External I/O Expansion Unit information ■ Name properties of PCI cards
Privileges	<p>You must have one of the following privileges to run this command:</p> <p>useradm, platadm, platop, fieldeng</p> <p style="padding-left: 40px;">Can run this command for all domains.</p> <p>domainadm, domainmgr, domainop</p> <p style="padding-left: 40px;">Can run this command only for your accessible domains.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:.</p> <p>-h Displays usage statement. When used with other options or operands, an error occurs.</p> <p>-M Displays text by page. This option provides a function that is the same as that of the more command.</p> <p>-u Displays the number of FRUs installed in each unit. For CPU modules, operating frequencies are displayed. For memory units, the capacity of each memory unit is displayed. If this option is omitted, the current configuration and status information regarding FRUs and domain information are displayed.</p>

**EXTENDED
DESCRIPTION**

When the configuration and status information regarding FRUs and domain information are displayed, for any failed or degraded unit, an asterisk (*) indicating an abnormal unit is displayed along with any of the following states:

Status	Description
Failed	The component is faulty and is not operating
Degraded	The component is operating. However, either an error has been detected or the component is faulty. As a result, the component might be operating with reduced functionality or performance.
Deconfigured	As a result of another component's failed or degraded status, the component is not operating. (The component itself is not failed or degraded.)
Maintenance	The component is under maintenance. A <code>deletefru(8)</code> , <code>replacefru(8)</code> , or <code>addfru(8)</code> operation is currently underway
Normal	It is operating normally.

EXAMPLES

EXAMPLE 1 Displays the information of the FRUs in the M5000 server.

```
XSCF> showhardconf
SPARC Enterprise M5000;
+ Serial:BE80601021; Operator_Panel_Switch:Service;
+ Power_Supply_System:Single; SCF-ID:XSCF#0;
+ System_Power:On; System_Phase:Cabinet Power On;
Domain#0 Domain_Status:Powered Off;

MBU_B Status:Normal; Ver:0101h; Serial:7867000297 ;
+ FRU-Part-Number:CA20393-B50X A2 ;
+ Memory_Size:64 GB;
CPUM#0-CHIP#0 Status:Normal; Ver:0201h; Serial:PP0629L068 ;
+ FRU-Part-Number:CA06761-D104 A0 ;
+ Freq:2.150 GHz; Type:16;
+ Core:2; Strand:2;
CPUM#0-CHIP#1 Status:Normal; Ver:0201h; Serial:PP0629L068 ;
+ FRU-Part-Number:CA06761-D104 A0 ;
+ Freq:2.150 GHz; Type:16;
+ Core:2; Strand:2;
```

```
      :
CPUM#3-CHIP#0 Status:Normal; Ver:0201h; Serial:PP0629L066  ;
      + FRU-Part-Number:CA06761-D104 A0                      ;
      + Freq:2.150 GHz; Type:16;
      + Core:2; Strand:2;
CPUM#3-CHIP#1 Status:Normal; Ver:0201h; Serial:PP0629L066  ;
      + FRU-Part-Number:CA06761-D104 A0                      ;
      + Freq:2.150 GHz; Type:16;
      + Core:2; Strand:2;
MEMB#0 Status:Normal; Ver:0101h; Serial:01068              ;
      + FRU-Part-Number:CA20393-B54X A1                      ;
MEM#0A Status:Normal;
      + Code:c100000000000004572T128000HR3.7A 252b-04123520;
      + Type:1B; Size:1 GB;
MEM#0B Status:Normal;
      + Code:c100000000000004572T128000HR3.7A 252b-04123e25;
      + Type:1B; Size:1 GB;
MEM#1A Status:Normal;
      + Code:c100000000000004572T128000HR3.7A 252b-04123722;
      + Type:1B; Size:1 GB;
MEM#1B Status:Normal;
      + Code:c100000000000004572T128000HR3.7A 252b-04123b25;
      + Type:1B; Size:1 GB;
MEM#2A Status:Normal;
      + Code:c100000000000004572T128000HR3.7A 252b-04123e20;
      + Type:1B; Size:1 GB;
MEM#2B Status:Normal;
      + Code:c100000000000004572T128000HR3.7A 252b-04123822;
      + Type:1B; Size:1 GB;
MEM#3A Status:Normal;
      + Code:c100000000000004572T128000HR3.7A 252b-04123724;
      + Type:1B; Size:1 GB;
MEM#3B Status:Normal;
```

```

+ Code:c1000000000000004572T128000HR3.7A 252b-04123b20;
+ Type:1B; Size:1 GB;
:
MEMB#7 Status:Normal; Ver:0101h; Serial:01100 ;
+ FRU-Part-Number:CA20393-B54X A1 ;
MEM#0A Status:Normal;
+ Code:c10000000000000005372T128000HR3.7A 356d-0d016910;
+ Type:1B; Size:1 GB;
MEM#0B Status:Normal;
+ Code:c10000000000000005372T128000HR3.7A 356d-0d016911;
+ Type:1B; Size:1 GB;
MEM#1A Status:Normal;
+ Code:c10000000000000005372T128000HR3.7A 356d-0d016a14;
+ Type:1B; Size:1 GB;
MEM#1B Status:Normal;
+ Code:c10000000000000005372T128000HR3.7A 356d-0d017e22;
+ Type:1B; Size:1 GB;
MEM#2A Status:Normal;
+ Code:c10000000000000005372T128000HR3.7A 356d-0d016a13;
+ Type:1B; Size:1 GB;
MEM#2B Status:Normal;
+ Code:c10000000000000005372T128000HR3.7A 356d-0d016417;
+ Type:1B; Size:1 GB;
MEM#3A Status:Normal;
+ Code:c10000000000000005372T128000HR3.7A 356d-0d017617;
+ Type:1B; Size:1 GB;
MEM#3B Status:Normal;
+ Code:c10000000000000005372T128000HR3.7A 356d-0d016b12;
+ Type:1B; Size:1 GB;
DDC_A#0 Status:Normal;
DDC_A#1 Status:Normal;
DDC_A#2 Status:Normal;
DDC_A#3 Status:Normal;

```



```

        DDC_B#0 Status:Normal;
        DDC_B#1 Status:Normal;
IOU#0 Status:Normal; Ver:0101h; Serial:7867000395 ;
    + FRU-Part-Number:CF00541-0483 0040 /541-0483-00-40 ;
        DDC_A#0 Status:Normal;
        DDCR Status:Normal;
            DDC_B#0 Status:Normal;
PCI#2 Status:Normal; Name_Property:; Card_Type:DownLink;
    + Ver:21h; Serial:XF01NW; Type:Optic;
    + Connection:IOX@X0DF/IOB0;
    + FRU-Part-Number:CF00501-7040 04 /501-7040-04;
*   IOX@X0DF Status:Faulted; Serial:XCX0DF;
        + FRU-Part-Number:CF00541-0314 05 /501-6937-05;
        IOB0 Status:Normal; Serial:XX00KA; Type:PCI-X;
            + FRU-Part-Number:CF00541-0316 03 /501-6938-05;
            LINK Status:Normal; Ver:21h; Serial:1F0090; Type:Optic;
                + FRU-Part-Number:CF00501-7040 04 /501-7040-04;
        PS0 Status:Normal; Serial:LL0807;
            + FRU-Part-Number:CF00300-2001 02 /300-2001-02;
        PS1 Status:Normal; Serial:LL0381;
            + FRU-Part-Number:CF00300-2001 02 /300-2001-02;
PCI#4 Status:Normal; Name_Property:; Card_Type:DownLink;
    + Ver:17h; Serial:XF01LM; Type:Optic;
    + Connection:IOX@X07P/IOB1;
    + FRU-Part-Number:CF00501-7040 04 /501-7040-04;
*   IOX@X07P Status:Faulted; Serial:XCX07P;
        + FRU-Part-Number:CF00541-0314 05 /501-6937-03;
        IOB1 Status:Normal; Serial:XE00F9; Type:PCI-Express;
            + FRU-Part-Number:CF00541-0507 03 /501-6939-05;
            LINK Status:Normal; Ver:17h; Serial:XF01N0; Type:Optic;
                + FRU-Part-Number:CF00501-7040 04 /501-7040-04;
        PS0 Status:Normal; Serial:LL1097;
            + FRU-Part-Number:CF00300-2001 02 /300-2001-02;

```

```

        PS1 Status:Normal; Serial:LL1121;
            + FRU-Part-Number:CF00300-2001 02 /300-2001-02;
IOU#1 Status:Normal; Ver:0101h; Serial:78670000376 ;
    + FRU-Part-Number:CA20393-B55X A4 ;
    DDC_A#0 Status:Normal;
    DDCR Status:Normal;
        DDC_B#0 Status:Normal;
XSCFU Status:Normal,Active; Ver:0101h; Serial:7867000262 ;
    + FRU-Part-Number:CA20393-B56X A0 ;
OPNL Status:Normal; Ver:0101h; Serial:7867000087 ;
    + FRU-Part-Number:CA00629-D061 A0 ;
PSU#0 Status:Normal; Serial:0000000-ASTECEB10 ;
    + FRU-Part-Number:CF00300-1898 0002 /300-1898-00-02;
    + Power_Status:Off; AC:200 V;
PSU#1 Status:Normal; Serial:0000000-ASTECEB18 ;
    + FRU-Part-Number:CF00300-1898 0002 /300-1898-00-02;
    + Power_Status:Off; AC:200 V;
PSU#2 Status:Normal; Serial:0000000-DELTAB19 ;
    + FRU-Part-Number:CF00300-1898 0002 /300-1898-00-02;
    + Power_Status:Off; AC:200 V;
PSU#3 Status:Normal; Serial:0000000-ASTECEB09 ;
    + FRU-Part-Number:CF00300-1898 0002 /300-1898-00-02;
    + Power_Status:Off; AC:200 V;
FANBP_C Status:Normal; Ver:0101h; Serial:7867000053 ;
    + FRU-Part-Number:CA06629-D051 001AA ;
    FAN_A#0 Status:Normal;
    FAN_A#1 Status:Normal;
    FAN_A#2 Status:Normal;
    FAN_A#3 Status:Normal;

```

EXAMPLE 2 Displays the number of installed FRUs in the M9000 server.

```
XSCF> showhardconf -u
```

```
SPARC Enterprise M9000; Memory_Size:432 GB;
```

FRU	Quantity
CMU	9
CPUM	36
Freq:2.277 GHz;	(30)
Freq:2.376 GHz;	(6)
MEM	224
Type:1B; Size:1 GB;	(16)
Type:2B; Size:2 GB;	(208)
IOU	9
IOBOX	1
IOB	2
PSU	2
XSCFU_B	2
XSCFU_C	2
XBU_B	16
CLKU_B	4
OPNL	1
PSU	30
FANBP_A	2
FANBP_B	2
FAN_A	32
SWBP	2
MEDBP	2

EXAMPLE 3 Displays the number of installed FRUs in the M3000 server.

```
XSCF> showhardconf -u
SPARC Enterprise M3000; Memory_Size:8 GB;
-----+
|          FRU          | Quantity |
-----+
| MBU_A                 |         1 |
|      CPU              | ( 1)    |
|      Freq:2.520 GHz;  | ( 1)    |
|      MEM              |         8 |
|      Type:1A; Size:1 GB; | ( 8)    |
| OPNL                  |         1 |
| PSU                   |         2 |
| FANBP_B              |         1 |
|      FAN_A           |         2 |
-----+

```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

NAME	showhostname - display the current host name for the XSCF unit				
SYNOPSIS	<p>showhostname {-a <i>xscfu</i>}</p> <p>showhostname -h</p>				
DESCRIPTION	<p>showhostname(8) command displays the current host name for the XSCF unit.</p> <p>The host name is displayed in Fully Qualified Domain Name (FQDN) format.</p>				
Privileges	<p>You must have one of the following privileges to run this command:</p> <p>useradm, platadm, platop, auditadm, auditop, domainadm, domainmgr, domainop, fieldeng</p> <p>Refer to setprivileges(8) for more information.</p>				
OPTIONS	<p>The following options are supported:</p> <p>-a Displays the current host names for all XSCF units. If an XSCF unit name is specified with the -a option, the XSCF unit name is ignored.</p> <p>-h Displays usage statement. When used with other options or operands, an error occurs.</p>				
OPERANDS	<p>The following operand is supported:</p> <p><i>xscfu</i> Specifies the XSCF unit name to be displayed. One of the following values can be specified. If <i>xscfu</i> is specified with the -a option, <i>xscfu</i> is ignored.</p> <table border="0" style="margin-left: 40px;"> <tr> <td><i>xscf</i>#0</td> <td>XSCF unit 0</td> </tr> <tr> <td><i>xscf</i>#1</td> <td>XSCF unit 1 (In the M8000/M9000 servers)</td> </tr> </table>	<i>xscf</i> #0	XSCF unit 0	<i>xscf</i> #1	XSCF unit 1 (In the M8000/M9000 servers)
<i>xscf</i> #0	XSCF unit 0				
<i>xscf</i> #1	XSCF unit 1 (In the M8000/M9000 servers)				
EXTENDED DESCRIPTION	<ul style="list-style-type: none"> ■ In the M8000/M9000 servers, a defect occurred on standby XSCF unit shows a message. ■ The sethostname(8) command sets a host name for an XSCF unit. 				
EXAMPLES	<p>EXAMPLE 1 Displays the current host names for all XSCF units.</p> <pre>XSCF> showhostname -a xscf#0: scf0-hostname.example.com xscf#1: scf1-hostname.example.com</pre>				

showhostname(8)

EXAMPLE 2 Displays the host name for XSCF unit 0.

```
XSCF> showhostname xscf#0  
xscf#0: scf0-hostname.example.com
```

EXIT STATUS The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO [sethostname\(8\)](#)

NAME	showhttps - display the status of the HTTPS service set for the XSCF network										
SYNOPSIS	showhttps showhttps -h										
DESCRIPTION	<p>The <code>showhttps(8)</code> command displays the status of the HTTPS service currently set for the XSCF network.</p> <p>With this command, whether the HTTPS service is operating and the installation status of the information that is necessary for authentication can be checked. If it is installed, the installation date is also displayed.</p> <p>The following states are displayed:</p> <table border="0"> <tr> <td>HTTPS Status</td> <td>Indicates whether the HTTPS service is operating</td> </tr> <tr> <td>Server key</td> <td>Indicates whether the private key of the web server has been installed</td> </tr> <tr> <td>CA key</td> <td>Indicates whether the private key of the certification authority has been installed</td> </tr> <tr> <td>CA cert</td> <td>Indicates whether the certificate of the certification authority has been installed</td> </tr> <tr> <td>CSR</td> <td>The certificate of the web server</td> </tr> </table>	HTTPS Status	Indicates whether the HTTPS service is operating	Server key	Indicates whether the private key of the web server has been installed	CA key	Indicates whether the private key of the certification authority has been installed	CA cert	Indicates whether the certificate of the certification authority has been installed	CSR	The certificate of the web server
HTTPS Status	Indicates whether the HTTPS service is operating										
Server key	Indicates whether the private key of the web server has been installed										
CA key	Indicates whether the private key of the certification authority has been installed										
CA cert	Indicates whether the certificate of the certification authority has been installed										
CSR	The certificate of the web server										
Privileges	<p>You must have one of the following privileges to run this command:</p> <p>useradm, platadm, platop, auditadm, auditop, domainadm, domainmgr, domainop, fieldeng</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>										
OPTIONS	<p>The following option is supported:</p> <table border="0"> <tr> <td>-h</td> <td>Displays usage statement.</td> </tr> </table>	-h	Displays usage statement.								
-h	Displays usage statement.										
EXTENDED DESCRIPTION	The <code>sethttps(8)</code> command make settings for the HTTPS service in the XSCF network.										
EXAMPLES	<p>EXAMPLE 1 Displays the status of the HTTPS service.</p> <pre>XSCF> showhttps HTTPS status: enabled Server key: installed in Apr 24 12:34:56 JST 2006 CA key: installed in Apr 24 12:00:34 JST 200</pre>										

showhttps(8)

```
CA cert: installed in Apr 24 12:00:34 JST 200
CSR:
-----BEGIN CERTIFICATE REQUEST-----
MIIBWjCCASsCAQAwYExCzAJBgNVBAYTAmpqMQ4wDAYDVQQIEWVzdGF0ZTERMA8G
A1UEBxMIbG9jYWxpdkhkaFTATBgNVBAoTDG9yZ2FuaXphdGlvbGjEPMA0GA1UECxMG
b3JnYW5pMQ8wDQYDVQQDEWZjb21tb24xFTJAUBgkqhkiG9w0BCQEWB2V1Lm1haWww
gZ8wDQYJKoZIhvcNAQEBBQADgY0AMIGJAoGBAJ5D57X/k42LcIpTbWzV2GrxaVM
5GEyx3bdBW8/7Wzhnd3uiZ9+ANlvRAuw/YYy7I/pAD+NQJesBcBjuyj9x+IiJl9F
MrI5fR8pOIywVObMPCar09rrU45bVeZhTyi+uQOdWLoX/Dhq0fm2BpYuh9WukT5
pTEg+2dABg8UdHmNagMBAAGgADANBgkqhkiG9w0BAQQFAAOBgQAux1jH3dyB6Xho
PgBuVIakDzIKEPipK9qQfC57YI43uRBGRubu0AHEcLVue5yTu6G5SxHTCq07tV5g
38UHSg5Kqy9QuWHWMri/hxm0kQ4gBpApjNb6F/B+ngBE3j/thGbEuvJb+0wbycvu
5jrHB/ZV9k8X/MbDOxSx/U5nF+Zuyw==
-----END CERTIFICATE REQUEST-----
```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

sethttps(8)

NAME	showldap - display the Lightweight Directory Access Protocol (LDAP) configuration for the Service Processor
SYNOPSIS	<p>showldap</p> <p>showldap [-c]</p> <p>showldap -h</p>
DESCRIPTION	showldap(8) displays the Service Processor LDAP configuration. When invoked without options, showldap displays all LDAP configuration except for the certificate chain and the password used when binding to the LDAP server.
Privileges	<p>You must have useradm or fieldeng privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p>-c Displays the LDAP server certification chain.</p> <p>-h Displays usage statement.</p> <p> When used with other options or operands, an error occurs.</p>
EXAMPLES	<p>EXAMPLE 1 Displaying All LDAP Configuration Data</p> <pre>XSCF> showldap Bind Name: user Base Distinguishing Name: ou=people,dc=company,dc=com LDAP Search Timeout: 60 Bind password: Set LDAP Servers: ldap://company.com:389 CERTS: None</pre> <p>EXAMPLE 2 Displaying All LDAP Configuration Data</p> <pre>XSCF> showldap -c There are no certificates configured.</pre>
EXIT STATUS	<p>The following exit values are returned:</p> <p>0 Successful completion.</p> <p>>0 An error occurred.</p>

showldap(8)

SEE ALSO

setldap(8)

NAME	showlocale - display the current setting for the XSCF locale
SYNOPSIS	showlocale showlocale -h
DESCRIPTION	The showlocale(8) command displays the current setting for the XSCF locale. Either of the following is displayed: C English ja_JP.UTF-8 Japanese Privileges You must have one of the following privileges to run this command: useradm, platadm, platop, auditadm, auditop, domainadm, domainmgr, domainop Refer to setprivileges(8) for more information.
OPTIONS	The following option is supported: -h Displays usage statement.
EXTENDED DESCRIPTION	The setlocale(8) command sets a locale for the XSCF.
EXAMPLES	EXAMPLE 1 Displays the current setting for the XSCF locale (when English is set). XSCF> showlocale C EXAMPLE 2 Displays the current setting for the XSCF locale (when Japanese is set). XSCF> showlocale ja_JP.UTF-8
EXIT STATUS	The following exit values are returned: 0 Successful completion. >0 An error occurred.
SEE ALSO	setlocale (8)

showlocale(8)



NAME	showlocator - display the state of the CHECK LED on the operator panel						
SYNOPSIS	showlocator showlocator -h						
DESCRIPTION	<p>showlocator(8) command displays the blink state of the CHECK LED on the operator panel.</p> <p>The one of the following state is displayed:</p> <table border="0"> <tr> <td style="padding-right: 20px;">Off</td> <td>Indicates normal operation, which means either the circuit breaker is off or power is not being supplied.</td> </tr> <tr> <td>Blinking</td> <td>Indicates that the unit is a maintenance target.</td> </tr> <tr> <td>On</td> <td>Indicates that an error was detected in the main unit.</td> </tr> </table>	Off	Indicates normal operation, which means either the circuit breaker is off or power is not being supplied.	Blinking	Indicates that the unit is a maintenance target.	On	Indicates that an error was detected in the main unit.
Off	Indicates normal operation, which means either the circuit breaker is off or power is not being supplied.						
Blinking	Indicates that the unit is a maintenance target.						
On	Indicates that an error was detected in the main unit.						
Privileges	<p>You must have one of the following privileges to run this command:</p> <p>useradm, platadm, platop, fieldeng</p> <p>Refer to setprivileges(8) for more information.</p>						
OPTIONS	<p>The following option is supported:</p> <table border="0"> <tr> <td style="padding-right: 20px;">-h</td> <td>Displays usage statement.</td> </tr> </table>	-h	Displays usage statement.				
-h	Displays usage statement.						
EXTENDED DESCRIPTION	The setlocator(8) command can be used to specify the blink state of the CHECK LED.						
EXAMPLES	<p>EXAMPLE 1 Displays the CHECK LED state.</p> <pre>XSCF> showlocator Locator LED status:Blinking</pre>						
EXIT STATUS	<p>The following exit values are returned:</p> <table border="0"> <tr> <td style="padding-right: 20px;">0</td> <td>Successful completion.</td> </tr> <tr> <td>>0</td> <td>An error occurred.</td> </tr> </table>	0	Successful completion.	>0	An error occurred.		
0	Successful completion.						
>0	An error occurred.						
SEE ALSO	setlocator (8)						

showlocator(8)



NAME	showlogs - display the specified log
SYNOPSIS	<pre> showlogs [-t <i>time</i> [-T <i>time</i>] -p <i>timestamp</i>] [-v -V -S] [-r] [-M] error showlogs [-t <i>time</i> [-T <i>time</i>] -p <i>timestamp</i>] [-v] [-r] [-M] event showlogs [-t <i>time</i> [-T <i>time</i>]] [-r] [-M] {power env} showlogs [-r] [-M] monitor showlogs -d <i>domain_id</i> [-t <i>time</i> [-T <i>time</i>]] [-r] [-M] {console ipl panic} showlogs -h </pre>
DESCRIPTION	<p>The showlogs(8) command displays the specified log.</p> <p>Log data is displayed in the order of timestamps, starting from the oldest data by default. Depending on the target for the log collection, the following logs can be specified:</p> <ul style="list-style-type: none"> For Field Replaceable Unit (FRU) <ul style="list-style-type: none"> ■ Error log (sometimes includes scan log) ■ Power log ■ Event log ■ Temperature and humidity record ■ Monitoring message log For domain <ul style="list-style-type: none"> ■ Console message log ■ Panic message log ■ IPL message log
Privileges	<p>You must have one of the following privileges to run this command:</p> <ul style="list-style-type: none"> ■ Error log, Event log, Temperature and humidity record, and Monitor message log: platadm, platop, fieldeng ■ Power log: platadm, platop, domainadm, domainmgr, fieldeng ■ Scan log: fieldeng ■ Console message log, Panic message log, and IPL message log: platadm, platop, domainadm, domainmgr, domainop, fieldeng <p>Refer to setprivileges(8) for more information.</p>

OPTIONS

The following options are supported:

- d *domain_id* Specifies the ID of a domain to be displayed. This option can be specified for domain specific log. *domain_id* can be 0–23 depending on the system configuration.
- h Displays usage statement. When used with other options or operands, an error occurs.
- M Displays text by page. This option provides a function that is the same as that of the `more` command.
- p *timestamp* Specifies a *timestamp* in a log when one log is to be displayed. This option can be specified for an error log or event log.

 timestamp is specified in one of the following formats:

 yyyy-mm-dd,hh:mm:ss
 The *timestamp* is specified in the 'year-month-day, hour:minute:second' format.

 mm/dd/yy,hh:mm:ss
 The *timestamp* is specified in the 'month/day/year, hour:minute:second' format.

 Monddhh:mm:ssyyyy
 The *timestamp* is specified in the 'month-name, day, hour:minute:second, year' format.
- r Displays a log in the order of timestamps, starting from the latest timestamp. By default, the display of log data in the order of timestamps starts from the oldest data.
- S Displays a scan log attached to an error log. Only a user having the `fieldeng` privilege can specify this operand. This cannot be specified together with the `-v` option or `-V` option.

-t *time*

Specifies the start date and time of the display range for log data. It is specified in one of the following formats:

yyyy-mm-dd,hh:mm

The *timestamp* is specified in the 'year-month-day, hour:minute' format.

mm/dd/yy,hh:mm

The *timestamp* is specified in the 'month/day/year, hour:minute' format.

Monddh:mmyyyy

The *timestamp* is specified in the 'month-name, day, hour:minute, year' format.

yyyy-mm-dd,hh:mm:ss

The *timestamp* is specified in the 'year-month-day, hour:minute:second' format.

mm/dd/yy,hh:mm:ss

The *timestamp* is specified in the 'month/day/year, hour:minute:second' format.

Monddh:mm:ssyyyy

The *timestamp* is specified in the 'month-name, day, hour:minute:second, year' format.

Even if the -r option is specified together with this option, the specified -t and -T options are not reversed. The -t option cannot be used for the monitoring message log.

- T** *time* Specifies the end date and time of the display range for log data. It is specified in one of the following formats:
- yyyy-mm-dd,hh:mm*
The *timestamp* is specified in the 'year-month-day, hour:minute' format.
- mm/dd/yy,hh:mm*
The *timestamp* is specified in the 'month/day/year, hour:minute' format.
- Monddhh:mmyyyy*
The *timestamp* is specified in the 'month-name, day, hour:minute, year' format.
- yyyy-mm-dd,hh:mm:ss*
The *timestamp* is specified in the 'year-month-day, hour:minute:second' format.
- mm/dd/yy,hh:mm:ss*
The *timestamp* is specified in the 'month/day/year, hour:minute:second' format.
- Monddhh:mm:ssyyyy*
The *timestamp* is specified in the 'month-name, day, hour:minute:second, year' format.
- Even if the **-r** option is specified together with this option, the specified **-t** and **-T** options are not reversed. The **-T** option cannot be used for the monitoring message log.
- v** Displays a log in detail. Details of Diagnostic Codes UUID and MSG-ID, which are used by the `fmadm(8)` and `fmdump(8)` commands, are also displayed in addition to the items normally displayed. This option cannot be specified together with the **-S** or **-V** option. This option can be specified for an error log or event log.
- V** Displays a log in greater detail. If detailed log information on machine administration and OBP console log information have already been collected, they are also displayed in addition to the information displayed by the **-v** option. This option cannot be specified together with the **-S** or the **-v** option. This option can be specified for an error log.

OPERANDS The following operands are supported:

error	Displays the error log. (sometimes includes scan log)
power	Displays the power log.
event	Displays the event log.
env	Displays the temperature and humidity record.
monitor	Displays the monitoring message log.
console	Displays the console message log.
panic	Displays the panic message log.
ipl	Displays the IPL message log.

**EXTENDED
DESCRIPTION**

Logs are displayed in the following formats:

■ Error log

Default

```
Date: Mar 30 17:45:31 JST 2005      Code: xxxxxxxx-xxxxxxx-
xxxxxxxxxxxxxxxxxxxxx

Status: Alarm                       Occurred: Mar 30 17:45:31.000 JST 2005

FRU: PSU#1,PSU#2,*

Msg: ACFAIL occurred (ACS=3) (FEP type = A1)
```

Case where the `-v` option is specified

```
Date: Mar 30 17:45:31 JST 2005      Code: xxxxxxxx-xxxxxxx-xxxxxxxxxxxxxxxxxxxxx

Status: Alarm                       Occurred: Mar 30 17:45:31.000 JST 2005

FRU: PSU#1,PSU#2,*

Msg: ACFAIL occurred (ACS=3) (FEP type = A1)

Diagnostic Code:

xxxxxxx xxxxxxxx xxxxxxxx

xxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx

xxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx

UUID: bf36f0ea-9e47-42b5-fc6f-c0d979c4c8f4 MSG-ID:FMD-8000-11
```

Case where the -V option is specified

```
Date: Mar 30 17:45:31 JST 2005      Code: xxxxxxxx-xxxxxxx-xxxxxxxxxxxxxxxxxxxxx
Status: Alarm                       Occurred: Mar 30 17:45:31.000 JST 2005
FRU: PSU#1,PSU#2,*
Msg: ACFAIL occurred (ACS=3) (FEP type = A1)
Diagnostic Code:
    xxxxxxxx xxxxxxxx xxxxxxxx
    xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx
    xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx
UUID: bf36f0ea-9e47-42b5-fc6f-c0d979c4c8f4 MSG-ID:FMD-8000-11
Diagnostic Messages:
    :
    :
```

Case where the -S option is specified

```
Date: Mar 30 17:45:31 JST 2005      Code: xxxxxxxx-xxxxxxx-xxxxxxxxxxxxxxxxxxxxx
Status: Alarm                       Occurred: Mar 30 17:45:31.000 JST 2005
FRU: PSU#1,PSU#2,*
Msg: ACFAIL occurred (ACS=3) (FEP type = A1)
Diagnostic Code:
    xxxxxxxx xxxxxxxx xxxxxxxx
    xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx
    xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx
UUID: bf36f0ea-9e47-42b5-fc6f-c0d979c4c8f4 MSG-ID:FMD-8000-11
Detail log: SCAN MINOR RC 2K
    0000: xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx
    0010: xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx
    :
    :
```

Date:	Log collection date and time (month day hour:minute:second time-zone year) The displayed time is the local time.
Code:	Error code Data is displayed in 16-byte format.
Occurred:	Date (Month Day Hour: Minute: Second TimeZone Year) when an error occurred. This date is displayed as the local time.
Status:	Error status Either of the following is displayed: Warning Partial degradation of the unit or warning about the FRU Alarm FRU failure or error
FRU:	Suspected faulty unit The suspected faulty units that are displayed and delimited by a ", " (comma) are the units most likely and second most likely to be faulty. If there are three suspected faulty units, an "*" is displayed next to the unit third most likely to be faulty. Display of more than two suspected faulty units depends on whether more than two suspected faulty units are detected.
Msg:	Error description
Diagnostic Code:	Detailed error code The displayed code is a hexadecimal number.
UUID:	Abbreviation for Universal Unique Identifier This is a globally unique ID that is a 32-digit hexadecimal number.
MSG-ID:	Unique message ID
Diagnostic Messages:	Detailed message If the log has a detailed message, it is displayed.
Detail log:	Scan log code This code is displayed when the log includes a scan log. Address: Displayed in hexadecimal notation.

■ Power log

Date	Event	Cause	DID	Switch
Mar 30 17:25:31 JST 2005	System Power Off	Power Failure	--	Service
Mar 30 17:35:31 JST 2005	System Power On	AC Restored	--	Locked
Mar 30 17:45:31 JST 2005	Domain Power On	Panel	00	Locked
Mar 30 17:50:31 JST 2005	Domain Power Off	Operator	10	Service
:				
:				

Date: Log collection date and time (month day hour:minute:second time-zone year)

The displayed time is the local time.

Event: Power status

One of the following states is displayed:

Domain Power On The domain power is on.

Domain Power Off The domain power is off.

System Power On The system power is on.

System Power Off The system power is off.

SCF Reset XSCF is in the reset state.

Domain Reset The domain is in the reset state.

XIR The domain CPU is in the reset state.

Cause: Factor that caused this Status

One of the following factors is displayed:

Self Reset, Power On, System Reset, Panel, Scheduled, RCI, AC Restored, Operator, Poweron Restart, Power Failure, SW Request, Alarm, Fatal, Panic

DID: Domain ID

domain_id can be 00–23 depending on the system configuration.

Switch: Status of the mode switch of the operator panel

One of the following states are displayed:

Locked	Normal operation mode
Service	Service mode

■ Event log

Default

Date	Message
Mar 30 17:45:31 JST 2005	System power on
Mar 30 17:55:31 JST 2005	System power off
:	
:	

Case where the `-v` option is specified

Date	Message
Mar 30 17:45:31 JST 2005	System power on
	Switch= Service
	Code=xxxx xxxx xxxx xxxx xxxx xxxx xxxx xxxx
	xxxx xxxx xxxx xxxx xxxx xxxx xxxx xxxx

Date: Log collection date and time (month day hour:minute:second time-zone year)

The displayed time is the local time.

Message: Event message

Switch: Status of the mode switch of the operator panel

One of the following states are displayed:

Locked Normal operation mode

Service Service mode

Code: Detailed event information

The displayed information is in hexadecimal format

■ TEMPERATURE AND HUMIDITY RECORD

Date	Temperature	Humidity	Power
Mar 30 17:45:31 JST 2005	32.56 (C)	60.20%	System Power On
Mar 30 17:55:31 JST 2005	32.56 (C)	60.25%	System Power Off
:			
:			

Date: Log collection date and time (month day hour:minute:second time-zone year)

The displayed time is the local time.

Temperature: Intake air temperature

Decimal numbers are displayed to two decimal places. The unit is degree Celsius (C).

Humidity: Humidity

The displayed numbers are percentages (%). Humidity is displayed on the M8000/M9000 servers only.

Power: Power state of the main unit

Either of the following states is displayed:

System Power ON The main unit power is on.

System Power OFF The main unit power is off.

- Monitoring message log

```
Mar 30 17:45:31 JST 2005      monitor message
Mar 30 17:55:31 JST 2005      monitor message
:
```

Each line of display has a date and time paired with a monitoring message. The time in the displayed log collection date and time (month day hour:minute:second time-zone year) is the local time.

- Console message log

```
DomainID: 00
Mar 30 17:45:31 JST 2005      console message
Mar 30 17:55:31 JST 2005      console message
:
```

[First line]

DomainID: Domain ID

domain_id can be 00–23 depending on the system configuration.

[Second and subsequent lines]

Each line of display has a date and time paired with a console message.

The time in the displayed log collection date and time (month day hour:minute:second time-zone year) is the local time.

- Panic message log

```
<<panic>>
Date: Mar 30 18:45:31 JST 2005      DomainID: 00
Mar 30 17:45:31 JST 2005      panic message
Mar 30 17:55:31 JST 2005      panic message
:
```

[Second line]

Date: Panic occurrence date and time (month day hour:minute:second time-zone year)

The displayed time is the local time.

DomainID: Domain ID

domain_id can be 00–23 depending on the system configuration.

[Third and subsequent lines]

Each line of display has a date and time paired with a panic message.

The time in the displayed log collection date and time (month day hour:minute:second time-zone year) is the local time.

■ IPL message log

```
<<ipl>>
```

```
Date: Mar 30 18:45:31 JST 2005      DomainID: 00
```

```
Mar 30 17:45:31 JST 2005      ipl message
```

```
Mar 30 17:55:31 JST 2005      ipl message
```

```
:
```

[Second line]

Date: IPL date and time (month day hour:minute:second time-zone year)

The displayed time is the local time.

DomainID: Domain ID

domain_id can be 00–23 depending on the system configuration.

[Third and subsequent lines]

Each line of display has a date and time paired with an IPL message.

The time in the displayed log collection date and time (month day hour:minute:second time-zone year) is the local time.

EXAMPLES

EXAMPLE 1 Displays an error log.

```
XSCF> showlogs error
Date: Mar 30 12:45:31 JST 2005      Code: 00112233-44556677-8899aabbccceeff0
  Status: Alarm                      Occurred: Mar 30 17:45:31.000 JST 2005
  FRU: IOU#0/PCI#3
  Msg: offline(vendor=FUJITSU, product=MAJ3182MC)
Date: Mar 30 15:45:31 JST 2005      Code: 00112233-44556677-8899aabbccceeff0
  Status: Warning                    Occurred: Mar 30 17:45:31.000 JST 2005
  FRU: PSU#1,PSU#2
  Msg: ACFAIL occurred (ACS=3)(FEP type = A1)
Date: Mar 30 17:45:31 JST 2005      Code: 00112233-44556677-8899aabbccceeff0
  Status: Alarm                      Occurred: Mar 30 17:45:31.000 JST 2005
  FRU: PSU#1,PSU#2,*
  Msg: ACFAIL occurred (ACS=3)(FEP type = A1)
```

EXAMPLE 2 Displays an error log in detail for the times of the specified timestamp (-v).

```
XSCF> showlogs error -p Mar3012:45:312005 -v
Date: Mar 30 12:45:31 JST 2005      Code: 00112233-44556677-8899aabbccceeff0
  Status: Alarm
  Component: IOU#0/PCI#3
  Msg: offline(vendor=FUJITSU, product=MAJ3182MC)
  Diagnostic Code:
    00112233 44556677 8899aabb
    00112233 44556677 8899aabb ccddeeff
    00112233 44556677 8899aabb ccddeeff
  UUID: bf36f0ea-9e47-42b5-fc6f-c0d979c4c8f4 MSG-ID: FMD-8000-11
```

EXAMPLE 3 Displays an error log in greater detail for the times of the specified timestamp (-v).

```
XSCF> showlogs error -p Mar3012:45:312005 -v
Date: Mar 30 12:45:31 JST 2005      Code: 00112233-44556677-8899aabbccceeff0
  Status: Alarm                      Occurred: Mar 30 17:45:31.000 JST 2005
  FRU: IOU#0/PCI#3
```

```

Msg: offline (vendor=FUJITSU, product=MAJ3182MC)
Diagnostic Code:
    00112233 44556677 8899aabb
    00112233 44556677 8899aabb ccddeeff
    00112233 44556677 8899aabb ccddeeff
UUID: bf36f0ea-9e47-42b5-fc6f-c0d979c4c8f4 MSG-ID: FMD-8000-11
Diagnostic Messages
Jul 11 16:17:42 plato10 root: [ID 702911 user.error] WARNING: /
pci@83,4000/scsi@2/sd@0,0 (sd47):
Jul 11 16:17:42 plato10 root: [ID 702911 user.error] incomplete write-
giving up

```

EXAMPLE 4 Displays a power log.

```

XSCF> showlogs power

```

Date	Event	Cause	DID	Switch
Mar 30 17:25:31 JST 2005	System Power Off	Power Failure	--	Service
Mar 30 17:35:31 JST 2005	System Power On	AC Restored	--	Locked
Mar 30 17:45:31 JST 2005	Domain Power Off	Operator	00	Locked
Mar 30 17:50:31 JST 2005	Domain Power On	Operator	00	Service

EXAMPLE 5 Displays a power log in the order of timestamps, starting from the latest timestamp.

```

XSCF> showlogs power -r

```

Date	Event	Cause	DID	Switch
Mar 30 17:50:31 JST 2005	Domain Power On	Operator	00	Service
Mar 30 17:45:31 JST 2005	Domain Power Off	Operator	00	Locked
Mar 30 17:35:31 JST 2005	System Power On	AC Restored	--	Locked
Mar 30 17:25:31 JST 2005	System Power Off	Power Failure	--	Service

EXAMPLE 6 Displays the specified range of a power log.

```

XSCF> showlogs power -t Mar3017:302005 -T Mar3017:492005

```

Date	Event	Cause	DID	Switch
Mar 30 17:35:31 JST 2005	System Power On	AC Restored	--	Locked
Mar 30 17:45:31 JST 2005	Domain Power Off	Operator	00	Locked

EXAMPLE 7 Displays the specified range of a power log. The log is displayed in the order of timestamps, starting from the latest timestamp.

```
XSCF> showlogs power -t Mar3017:302005 -T Mar3017:492005 -r
Date                               Event                               Cause                               DID  Switch
Mar 30 17:45:31 JST 2005           Domain Power Off                    Operator                            00   Locked
Mar 30 17:35:31 JST 2005           System Power On                      AC Restored                         --   Locked
```

EXAMPLE 8 Displays the specified date of a power log. Data with this date or later in the log is displayed.

```
XSCF> showlogs power -t Mar3017:302005
Date                               Event                               Cause                               DID  Switch
Mar 30 17:35:31 JST 2005           System Power On                      AC Restored                         --   Locked
Mar 30 17:45:31 JST 2005           Domain Power Off                    Panel                               00   Locked
Mar 30 17:50:31 JST 2005           Domain Power On                      Operator                            00   Service
```

EXAMPLE 9 Displays a console message log of the domain ID 0.

```
XSCF> showlogs console -d 00
DomainID:00
Mar 30 17:45:31 JST 2005           Executing last command: boot
Mar 30 17:55:31 JST 2005           Boot device: /pci@83,4000/FJSV,ulsa@2,1/
disk@0,0:a File and args:
Mar 30 17:55:32 JST 2005           SunOS Release 5.10 Version Generic 64-bit
```

Note: The codes or messages shown here may differ from those actually displayed.

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

showlogs(8)



NAME	showlookup - display the configuration for authentication and privileges lookup
SYNOPSIS	showlookup showlookup -h
DESCRIPTION	showlookup(8) displays configuration settings for authentication and privileges. Privileges You must have useradm or fieldeng privileges to run this command. Refer to setprivileges(8) for more information.
OPTIONS	The following option is supported: -h Displays usage statement.
EXAMPLES	EXAMPLE 1 Displaying Settings for Authentication and Privileges XSCF> showlookup Privileges lookup: Local only Authentication lookup: Local and LDAP
EXIT STATUS	The following exit values are returned: 0 Successful completion. >0 An error occurred.
SEE ALSO	setlookup (8)

showlookup(8)



NAME	showmonitorlog - display the contents of monitoring messages in real time
SYNOPSIS	<p>showmonitorlog</p> <p>showmonitorlog -h</p>
DESCRIPTION	<p>The <code>showmonitorlog(8)</code> command displays the contents of monitoring messages in real time.</p> <p>When executed, the <code>showmonitorlog(8)</code> command will not terminate in order to display the monitoring message log, and the XSCF shell is occupied for the display. When a monitoring message is registered, the contents of the message are displayed.</p> <p>To stop the real-time display, press the "Ctrl" and "C" key combination.</p>
Privileges	<p>You must have one of the following privileges to run this command:</p> <p><code>platadm, platop, fieldeng</code></p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>
OPTIONS	<p>The following option is supported:</p> <p><code>-h</code> Displays usage statement.</p>
EXAMPLES	<p>EXAMPLE 1 Displays the contents of a monitoring message in real time.</p> <pre>XSCF> showmonitorlog Apr 13 12:32:16 XXXXX Alarm: /CMU#1,/CMU#0/DDC#0:ANALYZE:SC-IOU I/F fatal error 0x00000000; : :</pre>
EXIT STATUS	<p>The following exit values are returned:</p> <p>0 Successful completion.</p> <p>>0 An error occurred.</p>

showmonitorlog(8)



NAME	shownameserver - display the registered domain name system (DNS) servers specified on the XSCF network
SYNOPSIS	shownameserver shownameserver -h
DESCRIPTION	shownameserver(8) command displays the registered DNS servers in the XSCF network.
Privileges	You must have one of the following privileges to run this command: useradm, platadm, platop, auditadm, auditop, domainadm, domainmgr, domainop, fieldeng Refer to setprivileges(8) for more information.
OPTIONS	The following option is supported: -h Displays usage statement.
EXTENDED DESCRIPTION	The setnameserver(8) command sets the DNS servers used in the XSCF network.
EXAMPLES	EXAMPLE 1 Displays the DNS servers currently set for the XSCF network. The following example shows that three DNS servers have been set: <pre>XSCF> shownameserver nameserver 192.168.1.2 nameserver 10.18.108.10 nameserver 10.24.1.2</pre> EXAMPLE 2 Displays the DNS servers currently set for the XSCF network. The following example shows that no DNS server is set: <pre>XSCF> shownameserver ---</pre>
EXIT STATUS	The following exit values are returned: 0 Successful completion. >0 An error occurred.
SEE ALSO	setnameserver (8)

shownameserver(8)



NAME	shownetwork - display information of network interfaces for XSCF												
SYNOPSIS	shownetwork [-M] {-a -i <i>interface</i> } shownetwork -h												
DESCRIPTION	<p>shownetwork(8) command displays current information of network interfaces for XSCF.</p> <p>Information on the specified network interface or all the network interfaces can be displayed. The following information is displayed:</p> <table border="0"> <tr> <td>xscf#x-y</td> <td>XSCF network interface name</td> </tr> <tr> <td>HWaddr</td> <td>MAC address (hexadecimal notation)</td> </tr> <tr> <td>inet addr</td> <td>IP address</td> </tr> <tr> <td>Bcast</td> <td>Broadcast</td> </tr> <tr> <td>Mask</td> <td>Netmask</td> </tr> <tr> <td>UP/DOWN</td> <td>Whether the network interface is enabled</td> </tr> </table>	xscf#x-y	XSCF network interface name	HWaddr	MAC address (hexadecimal notation)	inet addr	IP address	Bcast	Broadcast	Mask	Netmask	UP/DOWN	Whether the network interface is enabled
xscf#x-y	XSCF network interface name												
HWaddr	MAC address (hexadecimal notation)												
inet addr	IP address												
Bcast	Broadcast												
Mask	Netmask												
UP/DOWN	Whether the network interface is enabled												
Privileges	<p>You must have one of the following privileges to run this command:</p> <p>useradm, platadm, platop, auditadm, auditop, domainadm, domainmgr, domainop, fieldeng</p> <p>Refer to setprivileges(8) for more information.</p>												
OPTIONS	<p>The following options are supported:</p> <table border="0"> <tr> <td>-a</td> <td>Displays information for all XSCF network interfaces.</td> </tr> <tr> <td>-h</td> <td>Displays usage statement. When used with other options or operands, an error occurs.</td> </tr> <tr> <td>-M</td> <td>Displays text by page. This option provides a function that is the same as that of the more command.</td> </tr> </table>	-a	Displays information for all XSCF network interfaces.	-h	Displays usage statement. When used with other options or operands, an error occurs.	-M	Displays text by page. This option provides a function that is the same as that of the more command.						
-a	Displays information for all XSCF network interfaces.												
-h	Displays usage statement. When used with other options or operands, an error occurs.												
-M	Displays text by page. This option provides a function that is the same as that of the more command.												

OPERANDS

The following operands are supported:

interface

Specifies the network interface whose information is to be displayed. One of the following values can be specified, depending on the system configuration. If this operand is specified with the `-a` option, the operand is ignored.

- In the M3000/M4000/M5000 servers:

For XSCF unit 0 :

`xscf#0-lan#0` XSCF-LAN#0

`xscf#0-lan#1` XSCF-LAN#1

For abbreviation:

`lan#0` an abbreviation of XSCF-LAN#0

`lan#1` an abbreviation of XSCF-LAN#1

- In the M8000/M9000 servers:

For XSCF unit 0 :

`xscf#0-lan#0` XSCF-LAN#0

`xscf#0-lan#1` XSCF-LAN#1

`xscf#0-if` Interface between XSCF units (Inter SCF Network; ISN)

For XSCF unit 1:

`xscf#1-lan#0` XSCF-LAN#0

`xscf#1-lan#1` XSCF-LAN#1

`xscf#1-if` ISN

For takeover IP address:

`lan#0` takeover IP address for XSCF-LAN#0

`lan#1` takeover IP address for XSCF-LAN#1

EXTENDED DESCRIPTION

- In the M8000/M9000 servers, a takeover IP address can be used without a need to determine whether XSCF has been switched. By setting the LAN ports of the active XSCF unit as `lan#0` and `lan#1`, they can be accessed with the names `lan#0` and `lan#1`.
- In the M3000/M4000/M5000 servers, the value of the `lan#0` is fixed with `xscf#0-lan#0`, and the `lan#1` is fixed with `xscf#0-lan#1`.

- In the M8000/M9000 servers and when the takeover IP address has been disabled by `setnetwork(8)` command, nothing will be displayed even though the takeover IP address is specified by the `shownetwork(8)` command.
- The `setnetwork(8)` command configures a network interface used by the XSCF.

EXAMPLES

EXAMPLE 1 Displays the information for XSCF-LAN#0 on XSCF unit 0.

```
XSCF> shownetwork xscf#0-lan#1
xscf#0-lan#1
Link encap:Ethernet HWaddr 00:00:00:12:34:56
inet addr:192.168.10.11 Bcast: 192.168.10.255 Mask:255.255.255.0
UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
RX packets:54424 errors:0 dropped:0 overruns:0 frame:0
TX packets:14369 errors:0 dropped:0 overruns:0 carrier:0
collisions:0 txqueuelen:1000
RX bytes:20241827 (19.3 MiB) TX bytes:2089769 (1.9 MiB)
Base address:0x1000
```

EXAMPLE 2 Displays the information for XSCF-LAN#1 on XSCF unit 0 in the M3000/M4000/M5000 server.

```
XSCF> shownetwork lan#1
xscf#0-lan#1
Link encap:Ethernet HWaddr 00:00:00:12:34:56
inet addr:192.168.10.11 Bcast: 192.168.10.255 Mask:255.255.255.0
UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
RX packets:54424 errors:0 dropped:0 overruns:0 frame:0
TX packets:14369 errors:0 dropped:0 overruns:0 carrier:0
collisions:0 txqueuelen:1000
RX bytes:20241827 (19.3 MiB) TX bytes:2089769 (1.9 MiB)
Base address:0x1000
```

EXAMPLE 3 Displays the information for ISN on the XSCF unit 0.

```
XSCF> shownetwork xscf#0-if
xscf#0-if
Link encap:Ethernet HWaddr 00:00:00:12:34:56
```

```

inet addr:192.168.10.128 Bcast: 192.168.10.255 Mask:255.255.255.0
UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
RX packets:54424 errors:0 dropped:0 overruns:0 frame:0
TX packets:14369 errors:0 dropped:0 overruns:0 carrier:0
collisions:0 txqueuelen:1000
RX bytes:(0.0 B) TX bytes:17010 (16.6 KiB)
Base address:0x1000

```

EXAMPLE 4 Displays the information for XSCF-LAN#0 on XSCF Unit 0.

```

XSCF> shownetwork xscf#0-lan#0
xscf#0-lan#0
Link encap:Ethernet HWaddr 00:00:00:12:34:56
inet addr:192.168.11.10 Bcast:192.168.11.255 Mask 255.255.255.0
UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
RX packets:54424 errors:0 dropped:0 overruns:0 frame:0
TX packets:14369 errors:0 dropped:0 overruns:0 carrier:0
collisions:0 txqueuelen:1000
RX bytes:14541827 (13.8 MiB) TX bytes:1459769 (1.3 MiB)
Base address:0x1000

```

EXAMPLE 5 Displays the information for the takeover IP address for XSCF-LAN#0.

```

XSCF> shownetwork lan#0
lan#0 Link encap:Ethernet HWaddr 00:00:00:12:34:56
inet addr:192.168.1.10 Bcast:192.168.1.255 Mask:255.255.255.0
UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
Base address:0xe000

```

EXAMPLE 6 Displays the current settings of XSCF network.

```

XSCF> shownetwork -i
Active Internet connections (without servers)

```

Proto	Recv-Q	Send-Q	Local Address	Foreign Address	State
tcp	0	0	xx.xx.xx.xx:telnet	xxxx:1617	ESTABLISHED

EXAMPLE 7 Displays the information for XSCF unit 0 and XSCF unit 1 in the M8000/M9000 servers.

```
XSCF> shownetwork -a

xscf#0-lan#0

Link encap:Ethernet HWaddr 00:00:00:12:34:56
inet addr: 192.168.11.10 Bcast: 192.168.11.255 Mask:255.255.255.0
UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
RX packets:54424 errors:0 dropped:0 overruns:0 frame:0
TX packets:14369 errors:0 dropped:0 overruns:0 carrier:0
collisions:0 txqueuelen:1000
RX bytes:12241827 (11.3 MiB) TX bytes:1189769 (0.9 MiB)
Base address:0x1000

xscf#0-lan#1

Link encap:Ethernet HWaddr 00:00:00:12:34:57
inet addr:192.168.10.11 Bcast: 192.168.10.255 Mask:255.255.255.0
UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
RX packets:54424 errors:0 dropped:0 overruns:0 frame:0
TX packets:14369 errors:0 dropped:0 overruns:0 carrier:0
collisions:0 txqueuelen:1000
RX bytes:20241827 (19.3 MiB) TX bytes:2089769 (1.9 MiB)
Base address:0x1000

xscf#0-if Link encap:Ethernet HWaddr 00:00:00:00:00:00
inet addr:192.168.10.128 Bcast:192.168.10.255 Mask: 255.255.255.0
UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
RX packets:54424 errors:0 dropped:0 overruns:0 frame:0
TX packets:14369 errors:0 dropped:0 overruns:0 carrier:0
collisions:0 txqueuelen:1000
RX bytes:0 (0.0 B) TX bytes:17010 (16.6 KiB)
Base address:0x1000

xscf#1-lan#0
```

shownetwork(8)

```
HWaddr 00:00:00:12:34:59
inet addr:192.168.10.12  Mask:255.255.255.0
```

```
xscf#1-lan#1
```

```
HWaddr 00:00:00:12:34:60
```

```
xscf#1-if
```

```
HWaddr 00:00:00:12:34:61
```

```
XSCF>
```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

applynetwork(8), **setnetwork(8)**

NAME	shownotice - display copyright and license information for the XSCF Control Package (XCP)
SYNOPSIS	shownotice [-c {copyright license}] shownotice -h
DESCRIPTION	The shownotice(8) command displays by page the copyright and, if available, license files for the XCP. When used without an option, shownotice displays copyright information and any available license information. You can display only the copyright or the license file by specifying the -c option.
Privileges	No privileges are required to run this command. Refer to setprivileges(8) for more information.
OPTIONS	The following options are supported: -c {copyright license} Specifies for display by page either the copyright file or the license file for the XCP. copyright Specifies for display only the copyright file. license Specifies for display only the license file, if a license file is available for your platform. If the license file for your platform is not available for the shownotice command, the license argument is not supported. -h Displays usage statement. When used with other options or operands, an error occurs.
EXAMPLES	EXAMPLE 1 Display Only Copyright Information XSCF> shownotice -c copyright <i>[Copyright text displays.]</i> EXAMPLE 2 Display Copyright and License Information XSCF> shownotice <i>[Copyright text displays.]</i> <i>[License text displays (if available).]</i>

shownotice(8)



NAME	showntp - display the NTP information which currently set for XSCF
SYNOPSIS	showntp {-l -a <i>address</i> -s} showntp -h
DESCRIPTION	<p>The showntp(8) command displays the NTP information which currently set for XSCF.</p> <p>The showntp(8) command can display the following information:</p> <ul style="list-style-type: none"> ■ NTP servers which have been registered to the XSCF network ■ Status of synchronization with the NTP servers ■ Stratum value which has been set to XSCF
Privileges	<p>You must have one of the following privileges to run this command:</p> <p>useradm, platadm, platop, auditadm, auditop, domainadm, domainmgr, domainop, fieldeng</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:</p> <ul style="list-style-type: none"> -a Displays all the NTP servers currently set for the XSCF network. -h Displays usage statement. When used with other options or operands, an error occurs. -l Displays whether synchronization with an NTP server is being maintained. -s Displays the stratum value which has been set to XSCF.

OPERANDS

The following operand is supported:

address Specifies the IP address or the XSCF host name of an NTP server to be displayed. If the `-a` option is specified, the operand is ignored.

A specified IP address is a set of four integer values delimited by the "." (period). The following address form is accepted:

xxx.xxx.xxx.xxx

where:

xxx An integer from 0–255. Zero suppression can be used to specify the integer.

The host name can be specified in the format that complies with RFC 1034.

EXTENDED DESCRIPTION

The `setntp(8)` command sets the NTP servers used in the XSCF network.

EXAMPLES

EXAMPLE 1 Displays all NTP servers being currently set.

```
XSCF> showntp -a
server ntp1.example.com prefer # [1] ntp server name
server ntp2.example.com # [2] ntp server name
```

EXAMPLE 2 Confirms synchronization with an NTP server and displays the results.

```
XSCF> showntp -l
remote          refid          st t when poll reach  delay  offset jitter
=====
*192.168.0.27   192.168.1.56  2 u  27  64  377  12.929  -2.756  1.993
+192.168.0.57   192.168.1.86  2 u  32  64  377  13.030   2.184  94.421
127.127.1.0     LOCAL(0)      5 l  44  64  377   0.000   0.000  0.008
```

EXAMPLE 3 Displays the stratum value which has been set to XSCF.

```
XSCF> showntp -s
stratum : 5
```

EXIT STATUS The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO **setntp (8)**

showntp(8)



NAME	showpasswordpolicy - display the current password settings
SYNOPSIS	showpasswordpolicy showpasswordpolicy -h
DESCRIPTION	showpasswordpolicy(8) displays the password policy settings. These include default password expiration settings for new accounts, pam_cracklib parameters, and the number of passwords to keep in password history for each user.
Privileges	You must have useradm privileges to run this command. Refer to setprivileges(8) for more information.
OPTIONS	The following option is supported: -h Displays usage statement.
EXAMPLES	EXAMPLE 1 Displaying Password Policy Settings <pre>XSCF> showpasswordpolicy Mindays: 0 Maxdays: 99999 Warn: 7 Inactive: -1 Expiry: 0 Retry: 3 Difok: 10 Minlen: 9 Dcredit: 1 Ucredit: 1 Lcredit: 1 Ocredit: 1 Remember: 3</pre>
EXIT STATUS	The following exit values are returned: 0 Successful completion. >0 An error occurred.

showpasswordpolicy(8)

SEE ALSO | [setpasswordpolicy\(8\)](#)

NAME	showpowerupdelay - display the current settings for the warm-up time of the system and wait time before system startup
SYNOPSIS	showpowerupdelay showpowerupdelay -h
DESCRIPTION	The showpowerupdelay(8) command displays the current settings for the warm-up time of the system and wait time before system startup. The following settings are displayed: warmup time Warm-up time wait time Wait time before system startup
Privileges	You must have one of the following privileges to run this command: platadm, platop, domainadm, domainmgr, domainop, fieldeng Refer to setprivileges(8) for more information.
OPTIONS	The following options are supported: -h Displays usage statement.
EXTENDED DESCRIPTION	The setpowerupdelay(8) command sets the warm-up time of the system and a wait time before system startup.
EXAMPLES	EXAMPLE 1 Displays the warm-up time of the system and wait time before system start-up. XSCF> showpowerupdelay warmup time : 10 minute(s) wait time : 20 minute(s)
EXIT STATUS	The following exit values are returned: 0 Successful completion. >0 An error occurred.
SEE ALSO	setpowerupdelay (8)

showpowerupdelay(8)



NAME	showresult - display the exit status of the most recently executed command
SYNOPSIS	showresult showresult -h
DESCRIPTION	showresult(8) command displays the exit status of the most recently executed. showresult(8) is convenient for a remote control program to confirm whether the most recently executed command is successfully completed.
Privileges	No privileges are required to run this command. Refer to setprivileges(8) for more information.
OPTIONS	The following options are supported: -h Displays usage statement.
EXAMPLES	EXAMPLE 1 display the exit status of setupfru(8). XSCF> setupfru -x 1 sb 0 XSCF> showresult 0
EXIT STATUS	The following exit values are returned: 0 Successful completion. >0 An error occurred.

showresult(8)



NAME	showroute - display routing information for an XSCF network interface																						
SYNOPSIS	showroute [-M] [-n] {-a <i>interface</i> }																						
DESCRIPTION	<p>showroute -h</p> <p>showroute(8) command displays the current routing information for an XSCF network interface.</p> <p>Routing information for the specified network interface or all the network interfaces can be displayed. The following information is displayed:</p> <table border="0"> <tr> <td>Destination</td> <td>Destination IP address</td> </tr> <tr> <td>Gateway</td> <td>Gateway address</td> </tr> <tr> <td>Netmask</td> <td>Netmask address</td> </tr> <tr> <td>Flags</td> <td>Flag which indicates the status of specified routing</td> </tr> <tr> <td></td> <td>U route is up</td> </tr> <tr> <td></td> <td>H target is host</td> </tr> <tr> <td></td> <td>G use gateway</td> </tr> <tr> <td></td> <td>R reinstate route for dynamic routing</td> </tr> <tr> <td></td> <td>C cache entry</td> </tr> <tr> <td></td> <td>! reject route</td> </tr> <tr> <td>Interface</td> <td>XSCF network interface name</td> </tr> </table>	Destination	Destination IP address	Gateway	Gateway address	Netmask	Netmask address	Flags	Flag which indicates the status of specified routing		U route is up		H target is host		G use gateway		R reinstate route for dynamic routing		C cache entry		! reject route	Interface	XSCF network interface name
Destination	Destination IP address																						
Gateway	Gateway address																						
Netmask	Netmask address																						
Flags	Flag which indicates the status of specified routing																						
	U route is up																						
	H target is host																						
	G use gateway																						
	R reinstate route for dynamic routing																						
	C cache entry																						
	! reject route																						
Interface	XSCF network interface name																						
Privileges	<p>You must have one of the following privileges to run this command:</p> <p>useradm, platadm, platop, auditadm, auditop, domainadm, domainmgr, domainop, fieldeng</p> <p>Refer to setprivileges(8) for more information.</p>																						
OPTIONS	<p>The following options are supported:</p> <table border="0"> <tr> <td>-a</td> <td>Displays routing information that is set for all XSCF network interfaces.</td> </tr> </table>	-a	Displays routing information that is set for all XSCF network interfaces.																				
-a	Displays routing information that is set for all XSCF network interfaces.																						

- h Displays usage statement. When used with other options or operands, an error occurs.
- M Displays text by page. This option provides a function that is the same as that of the more command.
- n Displays IP address without the name resolution of host name.

OPERANDS

The following operand is supported:

interface Specifies the network interface whose information is to be displayed. One of the following values can be specified, depending on the system configuration. If this operand is specified with the -a option, the operand is ignored.

- In the M3000/M4000/M5000 servers:

For XSCF unit 0:

xscf#0-lan#0 XSCF-LAN#0

xscf#0-lan#1 XSCF-LAN#1

For abbreviation:

lan#0 XSCF-LAN#0

lan#1 XSCF-LAN#1

- In the M8000/M9000 servers:

For XSCF unit 0:

xscf#0-lan#0 XSCF-LAN#0

xscf#0-lan#1 XSCF-LAN#1

For XSCF unit 1 :

xscf#1-lan#0 XSCF-LAN#0

xscf#1-lan#1 XSCF-LAN#1

EXTENDED DESCRIPTION

The setroute(8) command sets routing information for the XSCF network.

EXAMPLES**EXAMPLE 1** Displays routing information for XSCF-LAN#0 on XSCF unit 0.XSCF> **showroute xscf#0-lan#0**

Destination	Gateway	Netmask	Flags	Interface
server1.example	*	255.255.255.0	U	xscf#0-lan#0
default	192.168.10.1	0.0.0.0	UG	xscf#0-lan#0

EXAMPLE 2 Displays routing information for XSCF-LAN#0 on XSCF unit 0 without the name resolution of host name.XSCF> **showroute -n xscf#0-lan#0**

Destination	Gateway	Netmask	Flags	Interface
192.168.10.0	0.0.0.0	255.255.255.0	U	xscf#0-lan#0
0.0.0.0	192.168.10.1	0.0.0.0	UG	xscf#0-lan#0

EXAMPLE 3 Displays all routing information for XSCF unit 0 and XSCF unit 1 in the M8000/M9000 server.XSCF> **showroute -a**

Kernel IP routing table

Destination	Gateway	Netmask	Flags	Interface
192.168.10.0	*	255.255.255.0	U	xscf#0-lan#0
default	192.168.10.1	0.0.0.0	UG	xscf#0-lan#0

Destination	Gateway	Netmask	Interface
default	192.168.10.1	0.0.0.0	xscf#1-lan#0

XSCF>

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO**setroute** (8)

showroute(8)



NAME	showshutdowndelay - display the shutdown wait time at power interruption of the uninterruptible power supply (UPS)
SYNOPSIS	showshutdowndelay showshutdowndelay -h
DESCRIPTION	The showshutdowndelay(8) command displays the wait time before the start of system shutdown for when power interruption occurs in a system connected to the UPS. The time set by the setshutdowndelay(8) command is displayed. The default time set is 10 seconds.
Privileges	You must have one of the following privileges to run this command: platadm, platop, domainadm, domainmgr, domainop, fieldeng Refer to setprivileges(8) for more information.
OPTIONS	The following options are supported: -h Displays usage statement.
EXAMPLES	EXAMPLE 1 Displays the wait time before the start of shutdown. XSCF> showshutdowndelay UPS shutdown wait time : 600 second(s)
EXIT STATUS	The following exit values are returned: 0 Successful completion. >0 An error occurred.
SEE ALSO	setshutdowndelay (8)

showshutdowndelay(8)



NAME	showsmtp - display the Simple Mail Transfer Protocol (SMTP) configuration information
SYNOPSIS	<p>showsmtp</p> <p>showsmtp [-v]</p> <p>showsmtp -h</p>
DESCRIPTION	showsmtp(8) displays the SMTP configuration. When used without options, it displays current SMTP configuration data.
Privileges	<p>You must have <code>platadm</code> or <code>platop</code> privileges to run this command.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p>-h Displays usage statement.</p> <p> When used with other options or operands, an error occurs.</p> <p>-v Specifies verbose output.</p>
EXTENDED DESCRIPTION	SMTP information includes the Mail Server and Reply addresses.
EXAMPLES	<p>EXAMPLE 1 Displaying SMTP configuration</p> <pre>XSCF> showsmtp Mail Server: 10.4.1.1 Port: 25 Authentication Mechanism: smtp-auth User Name: jsmith Password: ***** Reply Address: adm@customer.com</pre>
EXIT STATUS	<p>The following exit values are returned:</p> <p>0 Successful completion.</p> <p>>0 An error occurred.</p>
SEE ALSO	setsmtp (8)

showsmtp(8)



NAME	showsnmp - display the configuration information and current status of the SNMP agent
SYNOPSIS	showsnmp showsnmp -h
DESCRIPTION	showsnmp(8) displays the configuration and information and current status of the SNMP agent. This includes: agent status, port, system location, contact and description, traphosts, SNMP version, and any enabled MIB modules.
Privileges	You must have platadm or platop privileges to run this command. Refer to setprivileges(8) for more information.
OPTIONS	The following option is supported: -h Displays usage statement.
EXAMPLES	<p>EXAMPLE 1 Displaying SNMP Information for a System That Has Not Been Set Up</p> <pre>XSCF> showsnmp Agent Status: Disabled Agent Port: 161 System Location: Unknown System Contact: Unknown System Description: Unknown Trap Hosts: None SNMP V1/V2c: None Enabled MIB Modules: None</pre> <p>EXAMPLE 2 Displaying SNMP Information for a Disabled System Set Up With SNMPv3 Trap Host</p> <pre>XSCF> showsnmp Agent Status: Disabled Agent Port: 161</pre>

showsnmp(8)

```
System Location: SanDiego
System Contact: bob@jupiter.west
System Description: FF1
```

Trap Hosts:

Hostname	Port	Type	Community String	Username	Auth Protocol
-----	----	----	-----	-----	-----
host1	162	v3	n/a	jsmith	SHA

SNMP V1/V2c: None

Enabled MIB Modules: None

EXAMPLE 3 Displaying SNMP Information for a Enabled System Set Up With SNMPv1/v2c Trap Host

```
XSCF> showsnmp
```

```
Agent Status: Enabled
Agent Port: 161
System Location: SanDiego
System Contact: jsmith@jupiter.west
System Description: FF1
```

Trap Hosts:

Hostname	Port	Type	Community String	Username	Auth Protocol
-----	----	----	-----	-----	-----
host1	162	v1	public	jsmith	SHA
host2	162	v2c	public	n/a	n/a
host3	162	v3	n/a	bob	SHA

SNMP V1/V2c:

Status: Enabled

Community String: public

Enabled MIB Modules:

SP_MIB

FM_MIB

EXIT STATUS The following exit values are returned:

0 Successful completion.

>0 An error occurred.

SEE ALSO [setsnmp\(8\)](#)

showsnmp(8)



NAME	showsnmpusm - display the current User-based Security Model (USM) information for the SNMP agent
SYNOPSIS	showsnmpusm showsnmpusm -h
DESCRIPTION	showsnmpusm(8) displays the current USM information for the SNMP agent.
Privileges	You must have platadm or platop privileges to run this command. Refer to setprivileges(8) for more information.
OPTIONS	The following option is supported: -h Displays usage statement.
EXAMPLES	EXAMPLE 1 Displaying SNMP Information for a System <pre> XSCF> showsnmpusm Username Auth Protocol ----- - jsmith SHA sue MD5 </pre>
EXIT STATUS	The following exit values are returned: 0 Successful completion. >0 An error occurred.
SEE ALSO	setsnmpusm (8)

showsnpusm(8)



NAME	showsnmpvacm - display the current View-based Access Control Access (VACM) information for the SNMP agent
SYNOPSIS	showsnmpvacm showsnmpvacm -h
DESCRIPTION	showsnmpvacm(8) displays the current VACM information for the SNMP agent.
Privileges	You must have platadm or platop privileges to run this command. Refer to setprivileges(8) for more information.
OPTIONS	The following option is supported: -h Displays usage statement.
EXAMPLES	EXAMPLE 1 Displaying SNMP Information for a System <pre> XSCF> showsnmpvacm Groups: Groupname Username ----- - admin jsmith, bob Views: View Subtree Mask Type ---- - all_view .1 ff include Access: View Group ---- - all_view admin </pre>
EXIT STATUS	The following exit values are returned: 0 Successful completion. >0 An error occurred.

showsnmvacm(8)

SEE ALSO

setsnmvacm (8)

NAME	showssh - display the status, host public keys, fingerprint, or user public keys of the Secure Shell (SSH) service configured for the XSCF network								
SYNOPSIS	<p>showssh [-c hostkey] [-M]</p> <p>showssh -c pubkey [-u <i>user_name</i>] [-M]</p> <p>showssh -h</p>								
DESCRIPTION	<p>showssh(8) command displays the status, host public keys, fingerprint, or user public keys of the SSH service configured for the XSCF network.</p> <p>The following information is displayed:</p> <table border="0" style="margin-left: 20px;"> <tr> <td>SSH status</td> <td>Validity of the SSH service</td> </tr> <tr> <td>RSA key</td> <td>Host public key in RSA format</td> </tr> <tr> <td>DSA key</td> <td>Host public key in DSA format</td> </tr> <tr> <td>Fingerprint</td> <td>Host public key in fingerprint format</td> </tr> </table> <p>When specified the display of user public key, the user public key number, which automatically numbered by system, and the user public key are displayed.</p> <p>Only SSH2 is supported for XSCF.</p>	SSH status	Validity of the SSH service	RSA key	Host public key in RSA format	DSA key	Host public key in DSA format	Fingerprint	Host public key in fingerprint format
SSH status	Validity of the SSH service								
RSA key	Host public key in RSA format								
DSA key	Host public key in DSA format								
Fingerprint	Host public key in fingerprint format								
Privileges	<p>You must have one of the following privileges to run this command:</p> <ul style="list-style-type: none"> ■ To display the user public key of other user account: useradm ■ To display the information other than above: useradm, platadm, platop, auditadm, auditop, domainadm, domainmgr, domainop, fieldeng <p>Refer to setprivileges(8) for more information.</p>								
OPTIONS	<p>The following options are supported:</p> <table border="0" style="margin-left: 20px;"> <tr> <td>-c hostkey</td> <td>Displays a host public key. If the -c option is omitted, "-c hostkey" is assumed specified.</td> </tr> <tr> <td>-c pubkey</td> <td>Displays the user public key. If the -c option is omitted, "-c hostkey" is assumed specified</td> </tr> </table>	-c hostkey	Displays a host public key. If the -c option is omitted, "-c hostkey" is assumed specified.	-c pubkey	Displays the user public key. If the -c option is omitted, "-c hostkey" is assumed specified				
-c hostkey	Displays a host public key. If the -c option is omitted, "-c hostkey" is assumed specified.								
-c pubkey	Displays the user public key. If the -c option is omitted, "-c hostkey" is assumed specified								

- h Displays usage statement. When used with other options or operands, an error occurs.
- M Displays text by page. This option provides a function that is the same as that of the more command.
- u *user_name* Specify the user account name to display the user public key. Should be specified with "-c pubkey." When the -u option omitted, the user public key of the current login user account will be displayed.

EXTENDED DESCRIPTION

- You can specify the automatically-numbered user public key number to delete the user public key by setssh(8) command.
- The setssh(8) command makes settings for the SSH service in the XSCF network.

EXAMPLES

EXAMPLE 1 Displays the information of host public keys.

```
XSCF> showssh

SSH status: enabled

RSA key:

ssh-rsa AAAAB3NzaC1yc2EAAAABIwAAAIEAt0IG3wfpQnGr51znS9XtzwHcBBB/
UU0LN08SilUXE6j+

avlxdY7AFqBf1wGxLF+Tx5pTa6HuZ8o8yUBbDZVJAAAAFQCfKPxarV+/5qzK4A43Qaigkqu/
6QAAAIBM

LQ122G8pwibESrh5JmOhSxpLz13P26ksI8qPr+7BxmjLR0k=

Fingerprint:

1024 e4:35:6a:45:b4:f7:e8:ce:b0:b9:82:80:2e:73:33:c4 /etc/ssh/
ssh_host_rsa_key.pub

DSA key:

ssh-dss
AAAAB3NzaC1kc3MAAACBAJSy4GxD7Tk4fxFvyW1D0NUDqZQPYP3PuY2IG7QC4BQ1kewDnblB8
/
JEqI+8pnfbWzmOWU37KHL19OEYNAv6v+WZT6RE1U5Pyb8F16uq96L8QDMswF1ICMZgrn+ilJN
Str6r8

KDJfwOQMmK0eeDFj2mL40NOvaLQ83+rRwW6Ny/yF1Rgv6PUPuqRLw4VeRb+uOfmPRpe6/
kb4z++lOhtp

WI9bay6CK0nrFRok+z54ez7BrDFBQVuNZx9PyEFezJG9ziEYVUag/23LIAiLxxBmW9pqa/
WxC21Ja4RQ

VN3009kmVwAAAAIAON1LR/
9Jdd7yyG18+Ue7eBBJHrCA0pkSzvffzFFj5XUzQBdabh5p5Rwz+1vriawFI
```



```
ZI9j2uhM/3HQdrvYSVBEdMjaasF9hB6T/
uFwP8yqtJf6Y9GdjBAhWuH8F13pX4BtvK9IeldqCscnOuu0

e2r1UoI6GICMr64FL0YYBSwfbwLiz6PSA/yKQe23dwfkSfcwQZNq/
5pThGPi3tob5Qev2KCK20yEDMCA

OvVlMhqHuPNpX+hE19nPdBFGzQ==

Fingerprint:

1024 9e:39:8e:cb:8a:99:ff:b4:45:12:04:2d:39:d3:28:15 /etc/ssh/
ssh_host_dsa_key.pub
```

EXAMPLE 2 Displays the user public key of the current login user account.

```
XSCF> showssh -c pubkey

Public key:

 1  ssh-rsa
AAAAB3NzaC1yc2EAAAABIwAAAIEAzFh95SohrDgpnN7zFCJCVNy+jazPTjNDxcid
QGbihYDCBttI4151Y0Sv85FJwDpSNHNkoVLMYLjtBmUMPbGgGVB61qskSv/
FeV44hefNCZMiXGItIIPk
P0nBK4XJpCFoFbPXNUHDwlrTD9icD5U/wRFGSRRxFI+Ub5oLRxN8+A8=abcd@example.com

 2  ssh-rsa
CSqGSIb3DQEJARYHZWUubWFpbDCBnzANBggqhkiG9w0BAQEFAAOBjQAwgYkCgYEA
nkPntf+TjYtyKlNYFbO/YavFpUzkYTLHdt0Fbz/
tZmGd3e6Jn34A2W9EC7D9hjLsj+kAP41A16wFwGO7
KP3H4iImX0Uysj19Hyk4jLBU51sw8JqvT2utTj1tV5mFPKL6bDcAgY9=efgh@example.com
```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

setssh (8)

showssh(8)



NAME	showstatus - display the degraded Field Replaceable Units (FRUs)												
SYNOPSIS	showstatus [-M] showstatus -h												
DESCRIPTION	showstatus(8) command displays information about degraded units that are among the FRUs composing the system.												
Privileges	You must have one of the following privileges to run this command: useradm, platadm, platop, domainadm, domainmgr, domainop, fieldeng Refer to setprivileges(8) for more information.												
OPTIONS	The following options are supported:. -h Displays usage statement. When used with other options or operands, an error occurs. -M Displays text by page. This option provides a function that is the same as that of the more command.												
EXTENDED DESCRIPTION	The showstatus(8) shows the information concerning a unit failed or degraded and the unit on the upper hierarchy, among the FRUs composing the system. "Status:" will be followed by any of the status described below. Beside a unit failed or degraded, placed an "*" indicating the locating fault. <table border="0"> <thead> <tr> <th style="text-align: left;">Status</th> <th style="text-align: left;">Description</th> </tr> </thead> <tbody> <tr> <td>Normal</td> <td>The component is normally operating.</td> </tr> <tr> <td>Faulted</td> <td>The component is faulty and is not operating.</td> </tr> <tr> <td>Degraded</td> <td>The component is operating. However, either an error has been detected or the component is faulty. As a result, the component might be operating with reduced functionality or performance.</td> </tr> <tr> <td>Deconfigured</td> <td>As a result of another component's faulted or degraded status, the component is not operating. (The component itself is not faulted or degraded.)</td> </tr> <tr> <td>Maintenance</td> <td>The component is under maintenance. A deletefru(8), replacefru(8), or addfru(8) operation is currently underway.</td> </tr> </tbody> </table>	Status	Description	Normal	The component is normally operating.	Faulted	The component is faulty and is not operating.	Degraded	The component is operating. However, either an error has been detected or the component is faulty. As a result, the component might be operating with reduced functionality or performance.	Deconfigured	As a result of another component's faulted or degraded status, the component is not operating. (The component itself is not faulted or degraded.)	Maintenance	The component is under maintenance. A deletefru(8), replacefru(8), or addfru(8) operation is currently underway.
Status	Description												
Normal	The component is normally operating.												
Faulted	The component is faulty and is not operating.												
Degraded	The component is operating. However, either an error has been detected or the component is faulty. As a result, the component might be operating with reduced functionality or performance.												
Deconfigured	As a result of another component's faulted or degraded status, the component is not operating. (The component itself is not faulted or degraded.)												
Maintenance	The component is under maintenance. A deletefru(8), replacefru(8), or addfru(8) operation is currently underway.												
EXAMPLES	EXAMPLE 1 Displays the degraded units. In this example, a CPU module and memory												

module in a CPU memory unit are degraded because of an error.

```
XSCF> showstatus
    CMU#0;
*      CPUM#0-CHIP#0 Status:Faulted;
*      MEM#00A Status:Faulted;
```

EXAMPLE 2 Displays the degraded units. In this example, a memory module on a memory board is degraded because of an error.

```
XSCF> showstatus
    MBU_B;
    MEMB#0;
*      MEM#0A Status:Faulted;
```

EXAMPLE 3 Displays the degraded units. In this example, a CPU/memory board unit and memory module on a motherboard unit are degraded because of an error.

```
XSCF> showstatus
    MBU_B Status:Normal;
*      MEMB#1 Status:Deconfigured;
*      MEM#3B Status:Deconfigured;
```

EXAMPLE 4 Displays the degraded units. In this example, a CPU/memory board unit is degraded because a crossbar unit is degraded.

```
XSCF> showstatus
    MBU_B Status:Normal;
*      CPUM#1-CHIP#1 Status:Deconfigured;
*      XB_U_B#0 Status:Degraded;
```

EXIT STATUS

The following exit values are returned:

```
0          Successful completion.
>0        An error occurred.
```

NAME	showtelnet - display the current status of the Telnet service for the XSCF network
SYNOPSIS	showtelnet showtelnet -h
DESCRIPTION	<p>showtelnet(8) command displays the current status of the Telnet service for the XSCF network.</p> <p>One of the following states is displayed:</p> <p>enable The Telnet service is enabled.</p> <p>disable The Telnet service is disabled.</p>
Privileges	<p>You must have one of the following privileges to run this command:</p> <p>useradm, platadm, platop, auditadm, auditop, domainadm, domainmgr, domainop, fieldeng</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following option is supported:</p> <p>-h Displays usage statement.</p>
EXTENDED DESCRIPTION	The settelnet(8) command makes settings for the Telnet service in the XSCF network.
EXAMPLES	<p>EXAMPLE 1 Displays the status of the Telnet service for the XSCF network.</p> <pre>XSCF> showtelnet Telnet status:enabled</pre>
EXIT STATUS	<p>The following exit values are returned:</p> <p>0 Successful completion.</p> <p>>0 An error occurred.</p>
SEE ALSO	settelnet(8)

showtelnet(8)



NAME	showtimezone - display the XSCF time zone and Daylight Saving Time information of current settings
SYNOPSIS	<p>showtimezone -c tz</p> <p>showtimezone -c dst [-m {standard custom}]</p> <p>showtimezone -h</p>
DESCRIPTION	The showtimezone(8) command displays the XSCF time zone and Daylight Saving Time information of current settings.
Privileges	<p>You must have one of the following privileges to run this command:</p> <p>useradm, platadm, platop, auditadm, auditop, domainadm, domainmgr, domainop, fieldeng</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following option is supported:</p> <p>-c tz Displays the time zone.</p> <p>-c dst Displays the Daylight Saving Time information.</p> <p>-h Displays usage statement. When used with other options or operands, an error occurs.</p> <p>-m {standard custom} Specifies the Daylight Saving Time information to be displayed. Either of the following can be specified. If the -m option omitted, it is regarded as "-m custom" specified.</p> <p style="padding-left: 40px;">standard</p> <p style="padding-left: 80px;">Displays the Daylight Saving Time information that has been set in the current time zone by default.</p> <p style="padding-left: 40px;">custom</p> <p style="padding-left: 80px;">Displays the Daylight Saving Time information that you set by using the settimezone(8) command. If the Daylight Saving Time is not set, nothing displayed.</p>
EXTENDED DESCRIPTION	<ul style="list-style-type: none"> ■ The Daylight Saving Time information is displayed in the following format. <ul style="list-style-type: none"> ■ When specified custom: <p style="margin: 0;"><i>std offset dst[offset2] [from-date/time] to-date/time]</i></p> <p><i>std</i> Abbreviations of time zone.</p>

<i>offset</i>	Offset time of time zone and Greenwich mean time (GMT). Displayed in minus "-" in case the offset is plus, and displayed in plus "+" in case the offset is minus.
<i>dst</i>	Name of Daylight Saving Time.
<i>offset2</i>	Offset time of Daylight Saving Time and Greenwich mean time (GMT). Displayed in minus "-" in case the offset is plus, and displayed in plus "+" in case the offset is minus.
<i>from-date[/time]</i>	The starting time of Daylight Saving Time. Any of the following formats displays <i>from-date</i> . <i>Mm.w.d</i> <i>Mm</i> : Shows the month when Daylight Saving Time starts. Any numeric from 1 to 12 comes in <i>m</i> . <i>w</i> : Shows the week when Daylight Saving Time starts. Any numeric from 1 to 5 comes in, "1" for the first week and "5" for the last week in the month. <i>d</i> : Shows the day of the week when Daylight Saving Time starts. Any numeric from 0 to 6 comes in, "0" for Sunday and "6" for Saturday. <i>Jn</i> <i>Jn</i> : The date when Daylight Saving Time starts. Any numeric from 1 to 365 comes in, "1" for January 1st. The leap-year day is not counted. <i>n</i> <i>n</i> : The date when Daylight Saving Time starts. Any numeric from 1 to 365 comes in, "1" for January 1st. The leap-year day is counted. In <i>time</i> , the time to switch to Daylight Saving Time is shown in the pre-switched time. <i>hh:mm:ss</i> Shows the time in "hh:mm:ss" format. The default value is "02:00:00."

to-date[/time]

The termination time of Daylight Saving Time.

Any of the following formats displays *to-date*.*Mm.w.d**Mm*: Shows the month when Daylight Saving Time terminates. Any numeric from 1 to 12 comes in *m*.*w*: Shows the week when Daylight Saving Time terminates. Any numeric from 1 to 5 comes in, "1" for the first week and "5" for the last week in the month.*d*: Shows the day of the week when start Daylight Saving Time terminates. Any numeric from 0 to 6 comes in, "0" for Sunday and "6" for Saturday.*Jn**Jn*: The date when Daylight Saving Time terminates. Any numeric from 1 to 365 comes in, "1" for January 1st. The leap-year day is not counted.*n**n*: The date when Daylight Saving Time terminates. Any numeric from 1 to 365 comes in, "1" for January 1st. The leap-year day is counted.In *time*, the time to switch from Daylight Saving Time is shown in the pre-switched time.*hh:mm:ss*

Shows the time in "hh:mm:ss" format. The default value is "02:00:00."

- When specified `standard`:

From: *ddd MM dd hh:mm:ss yyyy dst*To: *ddd MM dd hh:mm:ss yyyy dst**ddd* a day of the week*MM* month*dd* day*hh* hour*mm* minutes*ss* second*yyyy* year

dst dst name

- The `settimezone(8)` command sets the time zone of the XSCF.

EXAMPLES

EXAMPLE 1 Displays the time zone.

```
XSCF> showtimezone -c tz
```

```
Asia/Tokyo
```

EXAMPLE 2 Displays the Daylight Saving Time information as follows: the abbreviation of time zone is JST, the offset from GMT is +9, the name of Daylight Saving Time is JDT, Daylight Saving Time is 1 hour ahead, and the time period is from the last Sunday of March 2:00 to the last Sunday of October 2:00.

```
XSCF> showtimezone -c dst -m custom
```

```
JST-9JDT,M3.5.0,M10.5.0
```

EXAMPLE 3 Displays the Daylight Saving Time information as follows: the abbreviation of time zone is JST, the offset from GMT is +9, the name of Daylight Saving Time is JDT, Daylight Saving Time is 1 hour ahead, and the time period is from the first Sunday of April 0:00 to the first Sunday of September 0:00.

```
XSCF> showtimezone -c dst
```

```
JST-9JDT-10,M4.1.0/00:00:00,M9.1.0/00:00:00
```

EXAMPLE 4 Displays the Daylight Saving Time information that has been set in the current time zone by default.

```
XSCF> showtimezone -c dst -m standard
```

```
From: Sun Mar 9 03:00:00 2008 PDT
```

```
To: Sun Nov 2 01:59:59 2008 PDT
```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

`setdate(8)`, `settimezone(8)`, `showdate(8)`

NAME	showuser - display user account information
SYNOPSIS	<p>showuser</p> <p>showuser [[-a] [-M] [-p] [-u] [<i>user</i>]]</p> <p>showuser [[-a] [-l] [-M] [-p] [-u]]</p> <p>showuser -h</p>
DESCRIPTION	<p>showuser (8) displays XSCF user account information. If the user argument is specified, showuser displays account information for the specified user. If the user argument is not specified, then showuser displays account information for the current user. If the -l option is specified, showuser displays account information for all local users.</p> <p>When invoked with one or more of the options -a, -p, or -u, showuser displays information as described in the OPTIONS section below. When invoked without any of these options, showuser displays all account information.</p>
Privileges	<p>No privileges are needed for you to view your own account. You must have useradm privileges to run this command for any other user.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p>-a Displays password validity and account state information. This is only valid for XSCF user accounts.</p> <p>-h Displays usage statement.</p> <p> When used with other options or operands, an error occurs.</p> <p>-l Displays information on all local XSCF user accounts sorted by user login name. Cannot be used with the <i>user</i> operand.</p> <p>-M Displays text by page. This option provides a function that is the same as that of the more command.</p> <p>-p Displays all privileges assigned to the user. This is valid for local and remote users.</p> <p>-u Displays user ID (UID). This is valid for local and remote users.</p>
OPERANDS	<p>The following operands are supported:</p> <p><i>user</i> Name of an existing user account. Cannot be used with the -l option.</p>

EXAMPLES

EXAMPLE 1 Displays Password and Account Validity Information

```
XSCF> showuser -a
User Name:      jsmith
Status:         Enabled
Minimum:        0
Maximum:        99999
Warning:        7
Inactive:       -1
Last Change:    Aug 22, 2005
Password Expires: Never
Password Inactive: Never
Account Expires: Never
```

EXAMPLE 2 Displays Privileges Information

```
XSCF> showuser -p
User Name:      jsmith
Privileges:     domainadm@1,3-6,8,9
                platadm
```

EXIT STATUS

The following exit values are returned:

0 Successful completion.
>0 An error occurred.

SEE ALSO

adduser(8), deleteuser(8), disableuser(8), enableuser(8), password(8), setprivileges(8)

NAME	snapshot - collect and transfer environment, log, error, and FRUID data
SYNOPSIS	<pre> snapshot -d <i>device</i> [-r] [-e [-P <i>password</i>]] [-L {F I R}] [-l] [-v] [[-q] -{Y n}] [-S <i>time</i> [-E <i>time</i>]] snapshot -t <i>user@host: directory</i> [-e [-P <i>password</i>]] [-k <i>host-key</i>] [-l] [-L {F I R}] [-p <i>password</i>] [-v] [[-q] -{Y n}] [-S <i>time</i> [-E <i>time</i>]] snapshot -T [-D <i>directory</i>] [-e [-P <i>password</i>]] [-k <i>host-key</i>] [-l] [-L {F I R}] [-v] [[-q] -{Y n}] [-S <i>time</i> [-E <i>time</i>]] snapshot -h </pre>
DESCRIPTION	<p>The snapshot(8) command provides a data-collection mechanism that enables rapid, reliable, and flexible retrieval of diagnostic information on the Service Processor. snapshot(8) collects the following data: Configuration, Environmentals, Logs, Errors, and FRUID information. It transfers data to the specified destination.</p> <p>snapshot opens an output file, the name of which is automatically generated based on the host name and IP address assigned to the Service Processor and the UTC time (in hours, minutes, and seconds) and date on the Service Processor at the time snapshot is invoked. For example: <code>jupiter_10.1.1.1_2006-07-08T22-33-44</code>. snapshot does not support user-specified file names for the output file. As files and command output are collected from the Service Processor, snapshot compresses the output data and writes it in the format of a <code>.zip</code> archive.</p> <p>snapshot stores the collected data on a remote network host or on an external media device, based upon the use of the <code>-t</code>, <code>-T</code> or <code>-d</code> option. To store the collected data on a remote network host using the <code>-t</code> option, you must specify a host name (or IP address), a target directory on the remote network host, and the user name of a user on the remote host. If you have already set an archive target using <code>setarchiving(8)</code>, you can use the <code>-T</code> option to store the data on a remote network host using that same information, or use <code>-T</code> in conjunction with the <code>-D</code> option to change only the target directory. When storing data on a remote network host, snapshot opens a network connection using SSH to act as a data pipe to the remote file.</p> <p>It is possible to restrict data collection on some larger log files to a specific date range using the options <code>-S</code> and, optionally, <code>-E</code>.</p> <p>Encrypted network protocols, such as SSH and SSL, are used for transmission of the data across a network connection. The entire <code>.zip</code> archive itself can be encrypted using the <code>-e</code> flag. To decrypt a <code>.zip</code> archive that has been encrypted with this process, use the encryption password given to snapshot with the <code>openssl</code></p>

command. The following example decrypts the file
 jupiter_10.1.1.1_2006-07-08T22-33-44.zip.e:

```
% openssl aes-128-cbc -d -in jupiter_10.1.1.1_2006-07-08T22-33-44.zip.e -out jupiter_10.1.1.1_2006-07-08T22-33-44.zip
```

Every .zip archive generated by snapshot includes two files generated by snapshot itself. The first file, called README, contains the original name of the .zip archive, the name of the configuration file on the Service Processor used to create the .zip archive, the version of snapshot and whether log-only mode (the -l flag) was used to generate the archive. The second file, called CONFIG, is a copy of the actual configuration file used by snapshot to generate the archive.

The data collected by snapshot may potentially be used by Service personnel to diagnose problems with the system. snapshot can collect different sets of data for different diagnostic purposes. The three different sets are named Initial, Root Cause, and Full, and are specified through the use of the -L option.

Privileges

You must have platadm or fieldeng privileges to run this command.

Refer to setprivileges(8) for more information.

OPTIONS

The following options are supported.

- D *directory* Used with the -T option, specifies a value for *directory* instead of the value set using setarchiving(8). The directory field must not begin with a "-" or a "~". Refer to the description of the -T option for more detailed information.
- d *device* Specifies the external media device to use. The following option is available to -d:
 - r Removes all files from the external media device prior to data collection. This option is not valid with the -t or -T options.
- E *time* Specifies the end time for the time period for which data is collected. Used with the -S *time* option for the start time, defines the period of time for which log messages are collected by snapshot. Only those log entries created before the time specified by -E *time* are collected by snapshot. Refer also to the description of the -S option.
 - time* Interpreted using strptime(3), using one of the following two formats:
 - %Y-%m-%d, %H:%M:%S
 - %Y-%m-%d_%H-%M-%S

- e Encrypts the zip archive. Required when using `-P password`.
- h Displays usage statement.
- When used with other options or operands, an error occurs.
- k *host-key* Used with the `-t` or `-T` option, sets the public key that the Service Processor uses to log in to the network host. This option is not valid with the `-d` option.
- Possible values for *host-key* are as follows:
- none
- This literal value specifies that a public key should not be used to authenticate the network host.
- download
- This literal value specifies that `snapshot` will use `ssh` to download a public host key for the network host and download the key from the host specified in the `-t` argument. `snapshot` displays the key's md5 fingerprint and prompts for confirmation. If you accept the key, it is used for server authentication. If you reject the key, `snapshot` exits without doing anything. This is the default behavior in SSH Target Mode if `-k` is not specified.
- public*
- The specified public key is used for server authentication. The *host-key* argument should be the complete public key of the network host, beginning with key type (the complete contents of `/etc/ssh/ssh_host_rsa_key.pub` on the network host).
- Note** – The public key should be enclosed in quotes to ensure that the shell treats it as a single word.
- L {F|I|R} Specifies which set of logs will be collected.
- | | |
|---|---------------------|
| F | Full log set. |
| I | Initial log set. |
| R | Root Cause log set. |
- If no log set is specified, the Initial log set is collected by default.
- l Specifies collecting only log files. Does not collect command output.
- n Automatically answers "n" (no) to all prompts.

-P <i>password</i>	Used with the -e option, sets the encryption password used for encrypting the output file.
-p <i>password</i>	Specifies the user password used to log in to the host using SSH. This option is valid with the -t option, not with the -d or -T options.
-q	Suppresses all messages to stdout, including prompts.
-S <i>time</i>	Specifies the start time for the time period for which data is collected. Used with the -E <i>time</i> option for the end time, defines the period of time for which log messages are collected by <code>snapshot</code> . If no end time is specified, the target time period ends at the time the <code>snapshot</code> command is launched. Refer also to the description of the -E option.
	<i>time</i> Interpreted using <code>strptime(3)</code> , using one of the following two formats:
	%Y-%m-%d, %H:%M:%S
	%Y-%m-%d_%H-%M-%S
-T	Specifies executing <code>snapshot</code> in SSH target mode using the value for <code>user@host:directory</code> previously set using <code>setarchiving(8)</code> . Can be used with the -D option to substitute an alternative value for <i>directory</i> .
	Note – The user must create the target directory on the remote host, <code>snapshot</code> does not create the target directory.
-t <i>user@host:directory</i>	Sets the network host and remote directory for data destination. The <i>host</i> field specifies the host name or IP address of the network host. The <i>user</i> field specifies the user name for the <code>ssh</code> login to the archive host. The <i>directory</i> field specifies the archive directory on the archive host where the output file should be stored. The directory field must not begin with a "-" or a "~".
	Note – The user must create the target directory on the remote host, <code>snapshot</code> does not create the target directory.
-v	Specifies verbose output. Displays all actions and commands as they are executed. If this option is specified with the -q option, the -v option is ignored.
	Note – You may not have the required privileges to run all the commands that are executed by the <code>snapshot</code> configuration file. If this occurs, you will see error messages indicating these operations are not permitted.
-y	Automatically answers "y" (yes) to all prompts.

**EXTENDED
DESCRIPTION****Modes of Operation**

The following is a brief overview of the modes of operation for the `snapshot` command.

The first mode is *SSH Target Mode*. The data collector is run in this mode when it is invoked with the `-t` or `-T` option. In this mode, the data collector opens an SSH connection from the Service Processor to the specified target (after appropriate authentication) and sends the zip data archive through the SSH connection to the target host. The user must create the target directory on the remote host, `snapshot` does not create the target directory. The transmission encryption in this mode is provided by SSH.

The second mode is *USB Device Mode*. The data collector is run in this mode when it is invoked with the `-d` flag. In this mode, the data collector's output (which is the zip archive) is saved in a file on the USB device. The USB device should be formatted using the FAT32 file system. As in SSH Target mode, you can use the `-e` option to encrypt the zip file in this mode. However, no transmission encryption (such as SSH) occurs in this mode, since the data stays local to the Service Processor.

EXAMPLES**EXAMPLE 1** Downloading a Public Key Using SSH

```
XSCF> snapshot -t joe@jupiter.west:/home/joe/logs/x -k download
Downloading Public Key from 'jupiter.west'...
Key fingerprint in md5: c9:e0:bc+b2:1a:80:29:24:13:d9:f1:13:f5:5c:2c:0f
Accept this public key (yes/no)? Y
Enter ssh password for user 'joe' on host 'jupiter.west'
Setting up ssh connection to remote host...
Collecting data into joe@jupiter.west:/home/joe/logs/x/archive.zip
Data collection complete.
```

EXAMPLE 2 Downloading a Host Key

```
XSCF> snapshot -t joe@jupiter.west:/home/joe/logs/x
Downloading Public Key from 'jupiter.west'...
Public Key Fingerprint: c9:e0:bc+b2:1a:80:29:24:13:d9:f1:13:f5:5c:2c:0f
Accept this public key (yes/no)? Y
Enter ssh password for user 'joe' on host 'jupiter.west'
```

```
Setting up ssh connection to remote host...
Collecting data into joe@jupiter.west:/home/joe/logs/x/archive.zip
Data collection complete.
```

EXAMPLE 3 Downloading With a User-Provided Public Key

```
XSCF> snapshot -t joe@jupiter.west:/home/joe/logs/x -k "ssh-rsa
AAAAB3NzaC1yc2EAAAABIwAAAIEAwVFISQNVBFhTTzq0AX5iQgCkkJjd6ezWkVgt
mMkJJzzMjYK0sBlhn6dGETiHdBSzO8QLAXb8N4Kq8JDOBpLSN4yokUPTcZQNxJaY
A0W058Qgxbn"
```

```
Enter ssh password for user 'joe' on host 'jupiter.west'
Setting up ssh connection to remote host...
Collecting data into joe@jupiter.west:/home/joe/logs/x/archive.zip
Data collection complete.
```

EXAMPLE 4 Log Files Only Using No Public Key

```
XSCF> snapshot -t bob@mars.east:/home/bob/logs/x -k none -l
Enter ssh password for user 'bob' on host 'mars.east'
Log only mode. No commands will be collected.
Setting up ssh connection to remote host...
Collecting data into joe@jupiter.west:/home/joe/logs/x/archive.zip
Data collection complete.
```

EXAMPLE 5 Downloading Using Encryption With Provided Password and No Public Key

```
XSCF> snapshot -t bob@mars.east:/home/bob/logs/x -k none -e -P
password
Output data will be encrypted.
Enter ssh password for user 'bob' on host 'mars.east'
Setting up ssh connection to remote host...
Collecting data into joe@jupiter.west:/home/joe/logs/x/archive.zip
Data collection complete.
```

EXAMPLE 6 Downloading Using No Key to Invalid Directory

```
XSCF> snapshot -t sue@saturn.north:/home/sue/logs/bad_dir -k none
Enter ssh password for user 'sue' on host 'saturn.north'
Setting up ssh connection to remote host...
Failed to create remote file:
/home/sue/logs/bad_dir/archive.zip
Verify adequate disk permissions and disk space on target host
Error opening SSH target
Exiting with error 1
```

EXAMPLE 7 Downloading Public Key With Connectivity Failure

```
XSCF> snapshot -t sue@saturne.west:/home/sue/logs/x -k download
Downloading Public Key from 'saturne.west'...
Error downloading key for host 'saturne.west'
Error opening SSH target
Exiting with error 1
```

EXAMPLE 8 Downloading Public Key and Answering No to All Prompts

```
XSCF> snapshot -v -t jill@earth.east:/home/jill/logs/x -k download
-n
Downloading Public Key from 'earth.east'...
Public Key: ssh-rsa
AAAAB3NzaC1yc2EAAAABIwAAAIEAwVFISQNVBFhTTzq0AX5iQqCkkJjd6ezWkVGtmMkJJzzM
jYK0sBlhn6dGEBIiHdBSzO8QLAXb8N4Kq8JDOBpLSN4yokUPTcZQNxJaYA0W058Qgxbn
Key fingerprint in md5: c9:e0:bc+b2:1a:80:29:24:13:d9:f1:13:f5:5c:2c:0f
Accept this public key (yes/no)? no
Public Key declined
Error opening SSH target
Exiting with error 1
```

EXAMPLE 9 Downloading Public Key Attempted by Unauthorized User

```
XSCF> snapshot -t fakeuser@fakehost.com:/fakedir -p fake-password
Downloading Public Key from 'fakehost.com'...
Error downloading key for host 'fakehost.com'
Error opening SSH target
Exiting with error 1
```

EXAMPLE 10 Downloading to External Media Device

```
XSCF> snapshot -d usb0 -r
Testing writability of USB device....SUCCESS
About to remove all files from device 'usb0'. Continue? [y|n] : y
Collecting data into /media/usb_msd/jupiter_10.1.1.1_2006-04-17T22-41-51.zip
Data collection complete.
```

EXAMPLE 11 Limiting Data Collection for Certain Logs to a Date Range

```
XSCF> snapshot -d usb0 -S 2007-01-01,01:00:00 -E 2007-01-31_14-00-00
Testing writability of USB device....SUCCESS
Collecting data into /media/usb_msd/jupiter_10.1.1.1_2006-04-17T22-41-51.zip
Data collection complete.
```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

setarchiving (8), **showarchiving** (8), **showlogs** (8)

NAME	switchscf - switch the XSCF unit between the active and standby states
SYNOPSIS	<p>switchscf [[-q] -{y n}] -t {Active Standby} [-f]</p> <p>switchscf -h</p>
DESCRIPTION	<p>The <code>switchscf(8)</code> command switches the XSCF unit that the user is currently logged in to, between the active and standby states.</p> <p>The <code>switchscf(8)</code> command is available on the M8000/M9000 servers only.</p> <p>When the active XSCF unit currently logged in to is switched from active to standby or vice versa, the state of the standby XSCF unit is also switched.</p> <p>Note – When switched, the session of the network which has been connected to the active XSCF is terminated.</p> <hr/> <p>Caution – Usually, XSCFs cannot be switched while maintenance work is in progress. If "Switching of XSCF state is disabled due to a maintenance operation. Try again later." is displayed as a result from the <code>switchscf(8)</code> command and XSCFs cannot be switched, check whether the <code>addfru(8)</code>, <code>deletefru(8)</code>, <code>replacefru(8)</code>, or <code>flashupdate(8)</code> maintenance command is being executed. If the command is being executed, wait until the command ends. If XSCFs cannot be switched though none of those maintenance commands is being executed, use the <code>-f</code> option to switch them.</p> <hr/>
Privileges	<p>You must have <code>platadm</code> or <code>fieldeng</code> privileges to run this command.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p><code>-f</code> Switches the state in a case XSCF state can't be changed due to a maintenance operation.</p> <hr/> <p>Caution – Since the <code>-f</code> option forcibly switches XSCF, limit the use of this option to such cases as when switching does not work in normal operations.</p> <hr/> <p><code>-h</code> Displays usage statement. When used with other options or operands, an error occurs.</p> <p><code>-n</code> Automatically answers "n" (no) to all prompts.</p> <p><code>-q</code> Suppresses all messages to stdout, including prompts.</p>

-t Active Switches the state of the XSCF unit to active.
 -t Standby Switches the state of the XSCF unit to standby.
 -y Automatically answers "y" (yes) to all prompts.

EXTENDED DESCRIPTION

When the command is executed, a prompt to confirm execution of the command with the specified options is displayed. Enter "y" to execute the command or "n" to cancel the command.

EXAMPLES

EXAMPLE 1 Switches the state of the XSCF unit that the user is currently logged in to, to standby.

```
XSCF> switchscf -t Standby
```

```
The XSCF unit switch between the Active and Standby states. Continue? [y|n]:y
```

EXAMPLE 2 Switches the state of the XSCF unit that the user is currently logged in to, to standby. Automatically answers "y" to all prompts.

```
XSCF> switchscf -t Standby -y
```

```
The XSCF unit switch between the Active and Standby states. Continue? [y|n]:y
```

EXIT STATUS

The following exit values are returned:

0 Successful completion.
 >0 An error occurred.

NAME	testsb - perform an initial diagnosis of the specified physical system board (PSB)
SYNOPSIS	<pre> testsb [[-q] [-y n]] [-m <i>diag=mode</i>] <i>location</i> testsb [[-q] [-y n]] [-m <i>diag=mode</i>] -c {all expansion} testsb -v [-y n] [-m <i>diag=mode</i>] <i>location</i> testsb -v [-y n] [-m <i>diag=mode</i>] -c {all expansion} testsb -h </pre>
DESCRIPTION	<p>testsb(8) command performs an initial diagnosis of the specified PSB.</p> <p>The testsb(8) command is not available on the M3000 server.</p> <p>The configuration of the PSB and operation of each device mounted on the PSB are checked. After the diagnostics, the result is displayed. The PSB must not be configured in the domain, or the domain in which the PSB configured must be powered off.</p> <p>The result also can be seen in "Test" and "Fault" displayed by showboards(8) command.</p>
Privileges	<p>You must have platadm or fieldeng privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>

OPTIONS

The following options are supported:.

- `-c {all|expansion}` Specifies the target PSB to be diagnosed. One of the values shown below can be specified:
- `all` Diagnoses all the PSB that are mounted.
- If the following conditions not satisfied, it leads to an error.
- The system has been powered off.
 - All of the target PSB are Uni-XSB.
- `expansion` Diagnoses all the PSB that are mounted on the expansion cabinet.
- If the following conditions not satisfied, it leads to an error.
- All of the target PSB are not operating on the domain.
 - All of the target PSB are Uni-XSB.
- `-h` Displays usage statement. When used with other options or operands, an error occurs.
- `-m diag=mode` Specifies the diagnostic level of initial diagnosis. One of the values shown below can be specified:
- `min` Normal (default)
- `max` Maximum
- `-n` Automatically answers "n" (no) to all prompts.
- `-q` Suppresses all messages to stdout, including prompts.
- `-v` Displays a detailed message of initial diagnosis.
- `-y` Automatically answers "y" (yes) to all prompts.

OPERANDS

The following operand is supported:

- location* Specifies only one PSB number. An integer from 00–15 can be specified.

EXTENDED DESCRIPTION

- When the command is executed, a prompt to confirm execution of the command with the specified options is displayed. Enter "y" to execute the command or "n" to cancel the command.
- When the system board (XSB) belonging to the specified PSB is in any status below, the testsb(8) command results in an error.
 - XSB is installed in the domain and this domain is in operation.

- XSB is installed in the domain and this domain is in OpenBoot PROM (ok> prompt) status.
- XSB is installed in the domain and this domain is power ON status, power OFF status, or reboot status.
- The addboard(8), deleteboard(8), or moveboard(8) command is executed for XSB.
- In case an XSB which belongs to the specified PSB is in Unmount or Faulted status, it may be excluded from the target of diagnosis and may not be shown in the diagnosis result. In a case like this, use the showboards(8) command to check the diagnosis result.
- In case there are the settings for the warm-up time of the system and the wait time before system startup, a prompt appears to confirm whether or not it can ignore these settings to execute the testsb(8) command. Enter "y" to execute the command or "n" to cancel the command.
- The displayed diagnostic results of the testsb(8) command are as follows:

XSB	XSB numbers belonging to the specified PSBs. One XSB number is displayed for the Uni-XSB type, and four XSB numbers are displayed for the Quad-XSB type.	
Test	Status of the initial diagnosis of XSBs. One of the following status values is displayed:	
	Unmount	No XSB could be recognized because no XSB is mounted or because an error occurred.
	Unknown	Not tested.
	Testing	Initial diagnosis is in progress.
	Passed	Initial diagnosis ended normally.
	Failed	An error was detected during the initial diagnosis. An XSB cannot be used or is in a degraded state.
Fault	XSB error. One or more states are displayed:	
	Normal	Normal state.
	Degraded	One or more components are degraded. Each XSB can operate.
	Faulted	An XSB cannot operate because an error occurred.

EXAMPLES

EXAMPLE 1 Performs the initial diagnosis on PSB#00.

```
XSCF> testsb 0
Initial diagnosis is about to start, Continue?[y|n] :y
SB#00 power on sequence started.
    0end
Initial diagnosis started. [1800sec]
    0..... 30..... 60..... 90.....120end
Initial diagnosis has completed.
SB power off sequence started. [1200sec]
    0.end
SB powered off.
XSB Test      Fault
-----
00-0 Passed   Normal
00-1 Passed   Normal
00-2 Passed   Normal
00-3 Passed   Normal
```

EXAMPLE 2 Performs an initial diagnosis of PSB#01 with detailed messages displayed.

```
XSCF> testsb -v 1
Initial diagnosis is about to start. Continue? [y|n] :y
SB#01 powered on sequence started.
    :
    :
Initial diagnosis has completed.
{0} ok SB power off sequence started. [1200sec]
    0.end
SB powered off.
XSB Test      Fault
-----
01-0 Passed   Normal
```

EXAMPLE 3 Performs the initial diagnosis on all the PSB that are mounted.

```
XSCF> testsb -c all
Initial diagnosis is about to start. Continue? [y|n] :y
SB power on sequence started.
  0end
Initial diagnosis started. [1800sec]
  0..... 30..... 60..... 90.....120end
Initial diagnosis has completed.
SB power off sequence started. [1200sec]
  0.end
SB powered off.
XSB  Test    Fault
----  -
00-0 Passed  Normal
01-0 Passed  Normal
02-0 Passed  Normal
03-0 Passed  Normal
```

EXAMPLE 4 Ignores the settings for the warm-up time of the system and the wait time before system startup to perform the initial diagnosis on the PSB that are mounted.

```
XSCF> testsb -c all
Initial diagnosis is about to start. Continue? [y|n] :y
Ignore warmup-time and air-conditioner-wait-time, Continue?[y|n] :y
SB power on sequence started.
  0end
Initial diagnosis started. [1800sec]
  0..... 30..... 60..... 90.....120end
Initial diagnosis has completed.
SB power off sequence started. [1200sec]
  0.end
SB powered off.
XSB  Test    Fault
----  -
```

testsb(8)

00-0 Passed Normal

01-0 Passed Normal

02-0 Passed Normal

03-0 Passed Normal

EXIT STATUS

The following exit values are returned:

0 Successful completion.

>0 An error occurred.

SEE ALSO

addfru (8), deletefru (8), replacefru (8), setupfru (8), showboards (8), showfru (8)

NAME	tracert - displays the route packets take to the specified network host or the network device
SYNOPSIS	tracert [-n] [-r] [-v] [-m <i>maxttl</i>] [-p <i>port</i>] [-q <i>nqueries</i>] [-s <i>src_addr</i>] [-w <i>wait</i>] <i>host</i> tracert -h
DESCRIPTION	<p>The <code>tracert(8)</code> command displays the route packets take to the specified network host or the network device.</p> <p>The route packets take indicates the router (gateway) which interconnects the specified host or the network device, and indicates what kind of the routers located on the route.</p> <p>The <code>tracert(8)</code> command uses the TTL field of IP protocol and tries to elicit the ICMP TIME_EXCEEDED responses from every gateway on the route packets take to the specified network host or the network device.</p>
Privileges	<p>You must have one of the following privileges to run this command:</p> <ul style="list-style-type: none"> ■ To execute the command to DSCP address: <code>fieldng</code> ■ To execute the command to "localhost" or to the loopback address (127.0.0.0/8): <code>fieldng</code> ■ To execute the command to Inter SCF Network (ISN): <code>fieldng</code> ■ The case other than those above: No privileges are required. <p>Refer to <code>setprivileges(8)</code> for more information.</p>
OPTIONS	<p>The following options are supported:</p> <ul style="list-style-type: none"> -h Displays usage statement. When used with other options or operands, an error occurs. -m <i>maxttl</i> Specifies the maximum number of hops. It displays the gateways for the number of hops specified. If omitted, it is set to 30. -n With no reverse DNS lookup, outputs the IP address. -p <i>port</i> Specifies the port number of the UDP packet to be used. Valid only in case using the UDP packet. If omitted, it is set to 33434. -q <i>nqueries</i> Specifies the number of retries to a single gateway. If omitted, it is set to three times.

<code>-r</code>	Bypasses the routing table and directly sends the packet to the specified network host or the network device. If the desired host or the network device is not on the same physical network, it results in errors.
<code>-s <i>src_addr</i></code>	Specifies the source address to start tracking the route.
<code>-v</code>	Displays verbose output. The size of the sending packet will be displayed.
<code>-w <i>wait</i></code>	tSpecifies the timeout period in units of seconds. If omitted, it is set to 3 seconds.

OPERANDS

The following operand is supported:

<i>host</i>	Specifies the network host or the network device to send the packet. Can be specified with host name or IP address.
-------------	---

EXAMPLES

EXAMPLE 1 Displays the route packets take to the host named server.example.com.

```
XSCF> tracert server.example.com
tracert to server.example.com (XX.XX.XX.XX), 30 hops max, 40 byte
packets
 1 XX.XX.XX.1 (XX.XX.XX.1)  1.792 ms  1.673 ms  1.549 ms
 2 XX.XX.XX.2 (XX.XX.XX.2)  2.235 ms  2.249 ms  2.367 ms
 3 XX.XX.XX.3 (XX.XX.XX.3)  2.199 ms  2.228 ms  2.361 ms
 4 XX.XX.XX.4 (XX.XX.XX.4)  2.516 ms  2.229 ms  2.357 ms
 5 XX.XX.XX.5 (XX.XX.XX.5)  2.546 ms  2.347 ms  2.272 ms
 6 server.example.com (XX.XX.XX.XX)  2.172 ms  2.313 ms  2.36 ms
```

EXAMPLE 2 Displays the detailed route packets take to the host named server.example.com. (XSCF-LAN=192.168.100.10)

```
XSCF> tracert -v server.example.com
tracert to server.example.com (XX.XX.XX.XX), 30 hops max, 40 byte packets
 1 XX.XX.XX.1 36 bytes to 192.168.100.10  1.792 ms  1.673 ms  1.549 ms
 2 XX.XX.XX.2 36 bytes to 192.168.100.10  2.235 ms  2.249 ms  2.367 ms
 3 XX.XX.XX.3 36 bytes to 192.168.100.10  2.199 ms  2.228 ms  2.361 ms
 4 XX.XX.XX.4 36 bytes to 192.168.100.10  2.516 ms  2.229 ms  2.357 ms
 5 XX.XX.XX.5 36 bytes to 192.168.100.10  2.546 ms  2.347 ms  2.272 ms
 6 server.example.com 48 bytes to 192.168.100.10  2.172 ms  2.313 ms  2.36 ms
```

EXIT STATUS | The following exit values are returned:

0	Successful completion.
>0	An error occurred.

traceroute(8)



NAME	unlockmaintenance - forcibly release the locked status of XSCF
SYNOPSIS	unlockmaintenance [[-q] -{y n}] unlockmaintenance -h
DESCRIPTION	unlockmaintenance(8) command releases the locked status of XSCF forcibly. Normally, while the maintenance command <code>addfru(8)</code> , <code>deletefru(8)</code> , or <code>replacefru(8)</code> is in execution, XSCF is in the locked status. After the command complete, the lock is released. However, in case an error such as LAN disconnection occurred while executing any of the maintenance command, the XSCF lock may become unable to release. In such a case, you can execute the <code>unlockmaintenance(8)</code> command to forcibly release the locked status of XSCF.
Privileges	You must have <code>fieldeng</code> privileges to run this command. Refer to <code>setprivileges(8)</code> for more information.
OPTIONS	The following options are supported: -h Displays usage statement. When used with other options or operands, an error occurs. -n Automatically answers "n" (no) to all prompts. -q Suppresses all messages to stdout, including prompts. -y Automatically answers "y" (yes) to all prompts.
EXTENDED DESCRIPTION	When the command is executed, a prompt to confirm execution of the command with the specified options is displayed. Enter "y" to execute the command or "n" to cancel the command.
EXAMPLES	EXAMPLE 1 Unlocks the maintenance lock status. XSCF> unlockmaintenance This command unlocks the maintenance lock which prevents the multiple execution of maintenance commands. *Never* use this command, except when the lock state remains by some reason. Careless execution of this command causes serious situation because it interrupts the running command and XSCF might not be able to recognize the parts. Continue? [y n] : y

EXAMPLE 2 Unlocks the maintenance lock status. Automatically answers "y" to all prompts.

```
XSCF> unlockmaintenance -y
```

This command unlocks the maintenance lock which prevents the multiple execution of maintenance commands.

Never use this command, except when the lock state remains by some reason. Careless execution of this command causes serious situation because it interrupts the running command and XSCF might not be able to recognize the parts.

```
Continue? [y|n] :y
```

EXAMPLE 3 Unlocks the maintenance lock status. Suppresses prompts, and automatically answers "y" to all prompts.

```
XSCF> unlockmaintenance -q -y
```

```
XSCF>
```

EXIT STATUS

The following exit values are returned:

0	Successful completion.
>0	An error occurred.

SEE ALSO

addfru (8), deletefru (8), replacefru (8)

NAME	version - display firmware version												
SYNOPSIS	<p>version -c xcp [-v] [-t]</p> <p>version -c {cmu xscf} [-v]</p> <p>version -h</p>												
DESCRIPTION	<p>The <code>version(8)</code> command displays firmware version.</p> <p>The following versions can be displayed:</p> <table border="0" style="margin-left: 2em;"> <tr> <td style="padding-right: 1em;"><code>xcp</code></td> <td>The comprehensive version of the XSCF control package (XCP) firmware currently applied to the system.</td> </tr> <tr> <td><code>cmu</code></td> <td>The version of OpenBoot PROM firmware.</td> </tr> <tr> <td><code>xscf</code></td> <td>The version of XSCF firmware.</td> </tr> </table>	<code>xcp</code>	The comprehensive version of the XSCF control package (XCP) firmware currently applied to the system.	<code>cmu</code>	The version of OpenBoot PROM firmware.	<code>xscf</code>	The version of XSCF firmware.						
<code>xcp</code>	The comprehensive version of the XSCF control package (XCP) firmware currently applied to the system.												
<code>cmu</code>	The version of OpenBoot PROM firmware.												
<code>xscf</code>	The version of XSCF firmware.												
Privileges	<p>You must have <code>platadm</code> or <code>fieldeng</code> privileges to run this command.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>												
OPTIONS	<p>The following options are supported:</p> <table border="0" style="margin-left: 2em;"> <tr> <td style="padding-right: 1em;"><code>-c xcp</code></td> <td>Displays the XCP version.</td> </tr> <tr> <td><code>-c cmu</code></td> <td>Displays the version of OpenBoot PROM firmware.</td> </tr> <tr> <td><code>-c xscf</code></td> <td>Displays the version of XSCF firmware.</td> </tr> <tr> <td><code>-h</code></td> <td>Displays usage statement. When used with other options or operands, an error occurs.</td> </tr> <tr> <td><code>-t</code></td> <td>Displays information of the XCP version that is registered in the XSCF. This option is used together with "<code>-c xcp</code>".</td> </tr> <tr> <td><code>-v</code></td> <td>Displays detailed information. Specifying this option with "<code>-c xscf</code>" displays the same information as the usual information.</td> </tr> </table>	<code>-c xcp</code>	Displays the XCP version.	<code>-c cmu</code>	Displays the version of OpenBoot PROM firmware.	<code>-c xscf</code>	Displays the version of XSCF firmware.	<code>-h</code>	Displays usage statement. When used with other options or operands, an error occurs.	<code>-t</code>	Displays information of the XCP version that is registered in the XSCF. This option is used together with " <code>-c xcp</code> ".	<code>-v</code>	Displays detailed information. Specifying this option with " <code>-c xscf</code> " displays the same information as the usual information.
<code>-c xcp</code>	Displays the XCP version.												
<code>-c cmu</code>	Displays the version of OpenBoot PROM firmware.												
<code>-c xscf</code>	Displays the version of XSCF firmware.												
<code>-h</code>	Displays usage statement. When used with other options or operands, an error occurs.												
<code>-t</code>	Displays information of the XCP version that is registered in the XSCF. This option is used together with " <code>-c xcp</code> ".												
<code>-v</code>	Displays detailed information. Specifying this option with " <code>-c xscf</code> " displays the same information as the usual information.												
EXAMPLES	<p>EXAMPLE 1 Displays the XCP version.</p> <pre style="margin-left: 2em;">XSCF> version -c xcp XSCF#0 (Active) XCP0 (Current): 1020 XCP1 (Reserve): 1020</pre>												

```
XSCF#1 (Standby)
XCP0 (Current): 1020
XCP1 (Reserve): 1020
```

EXAMPLE 2 Displays the details of the XCP version.

```
XSCF> version -c xcp -v
XSCF#0 (Active)
XCP0 (Current): 1020
OpenBoot PROM : 01.01.0001
SCF           : 01.01.0001
XCP1 (Reserve): 1020
OpenBoot PROM : 01.01.0001
OpenBoot PROM BACKUP
#0:          01.01.0001
#1:          01.02.0001
XSCF#1 (Standby)
XCP0 (Current): 1020
OpenBoot PROM : 01.01.0001
SCF           : 01.01.0001
XCP1 (Reserve): 1020
OpenBoot PROM : 01.01.0001
SCF           : 01.01.0001
OpenBoot PROM BACKUP
#0:          01.01.0001
#1:          01.02.0001
```

EXAMPLE 3 Displays the XCP version that is registered in the XSCF.

```
XSCF> version -c xcp -t
XCP: 1020
```

EXAMPLE 4 Displays the details of the XCP version that is registered in the XSCF.

```
XSCF> version -c xcp -v -t
XCP          : 1020
OpenBoot PROM: 01.01.0001
SCF          : 01.01.0001
```

EXAMPLE 5 Displays the version of OpenBoot PROM firmware.

```
XSCF> version -c cmu
DomainID 00 : 01.01.0001
DomainID 01 : 01.01.0001
DomainID 02 : 01.01.0001
DomainID 03 : 01.01.0001
:
DomainID 23: 01.01.0001
```

EXAMPLE 6 Displays the detailed version of OpenBoot PROM firmware.

```
XSCF> version -c cmu -v
DomainID 00 : 01.01.0001
DomainID 01 : 01.01.0001
DomainID 02 : 01.01.0001
DomainID 03 : 01.01.0001
:
DomainID 23: 01.01.0001

XSB#00-0   : 01.01.0001 (Current), 01.01.0001 (Reserve)
XSB#00-1   : 01.01.0001 (Reserve), 01.01.0001 (Current)
XSB#00-2   : 01.01.0001 (Current), 01.01.0001 (Reserve)
XSB#00-3   : 01.01.0001 (Current), 01.01.0001 (Reserve)
:
XSB#15-3   : 01.01.0001 (Current), 01.01.0001 (Reserve)
```

version(8)

EXAMPLE 7 Displays the version of XSCF firmware.

```
XSCF> version -c xscf
```

```
XSCF#0 (Active) 01.01.0001 (Current), 01.01.0001 (Reserve)
```

```
XSCF#1 (Standby) 01.01.0001 (Current), 01.01.0001 (Reserve)
```

EXIT STATUS

The following exit values are returned:

0 Successful completion.

>0 An error occurred.

NAME	viewaudit - display audit records
SYNOPSIS	<p>viewaudit</p> <p>viewaudit [-A <i>date-time</i>] [-B <i>date-time</i>] [-C] [-c <i>classes</i>] [-D <i>date-time</i>] [-E <i>end-record</i>] [-e <i>events</i>] [-i <i>audit-ids</i>] [-l] [-m <i>del</i>] [-n] [-p <i>privilege-results</i>] [-r <i>return-values</i>] [-S <i>start-record</i>] [-u <i>users</i>] [-x]</p> <p>viewaudit -h</p>
DESCRIPTION	<p>viewaudit(8) displays audit records. When invoked without options, viewaudit displays all current local audit records. When invoked with options, viewaudit displays only the selected records. By default, records are displayed in text format, one token per line, with a comma as the field separator. The output can be modified using the -C, -E, -l, -m <i>del</i>, -n, -S, or -x option.</p>
Privileges	<p>You must have auditadm or auditop privileges to run this command.</p> <p>Refer to setprivileges(8) for more information.</p>
OPTIONS	<p>The following options are supported:</p> <p>-A <i>date-time</i> Selects records that occurred at or after <i>date-time</i>. The <i>date-time</i> argument is in local time. the -A and -B options can be used together to form a range. Valid values for <i>date-time</i> are:</p> <p style="padding-left: 40px;">Absolute <i>date-time</i> : <i>yyyymmdd[hh[mm[ss]]]</i></p> <p style="padding-left: 40px;">where:</p> <ul style="list-style-type: none"> ■ <i>yyyy</i> = year (1970 is the earliest valid value) ■ <i>mm</i> = month (01-12) ■ <i>dd</i> = day (01-31) ■ <i>hh</i> = hour (00-23) ■ <i>mm</i> = minutes (00-59) ■ <i>ss</i> = seconds (00-59) <p style="padding-left: 40px;">The default value is 00 for <i>hh</i>, <i>mm</i>, and <i>ss</i>.</p>

-B *date-time*

Selects records that occurred before *date-time*. The *date-time* argument is in local time. the -A and -B options can be used together to form a range. Valid values for *date-time* are either absolute or offset:

Absolute *date-time* : *yyyymmdd[hh[mm[ss]]]*

where:

- *yyyy* = year (1970 is the earliest valid value)
- *mm* = month (01-12)
- *dd* = day (01-31)
- *hh* = hour (00-23)
- *mm* = minutes (00-59)
- *ss* = seconds (00-59)

Offset *date-time*: *+n d|h|m|s*

where:

- *n* = number of units
- *d* = days
- *h* = hours
- *m* = minutes
- *s* = seconds

Offset is only available with the -B option and must be used with -A.

(The default value is 00 for *hh*, *mm* and *ss*.)

-C

Appends the number of records that matched the selection criteria to the end of the output.

- c classes* Selects records in indicated classes. *classes* is a comma-separated list of audit classes. A class may be specified by its numeric value or its name. The ACS_ prefix may be omitted. For example, the class of audit related events can be expressed as ACS_AUDIT, AUDIT or 16.
- The following are valid classes:
- | | |
|-------------------|------------------------------------|
| all | Denotes all classes. |
| ACS_SYSTEM(1) | System-related events |
| ACS_WRITE(2) | Commands that can modify a state |
| ACS_READ(4) | Commands that read a current state |
| ACS_LOGIN(8) | Login-related events |
| ACS_AUDIT(16) | Audit-related events |
| ACS_DOMAIN(32) | Domain management-related events |
| ACS_USER(64) | User management-related events |
| ACS_PLATFORM(128) | Platform management-related events |
| ACS_MODES(256) | Mode-related events |
- D date-time* Selects records that occurred on a specific day (a 24-hour period beginning at 00:00:00 of the day specified and ending at 23:59:59). The day specified is in local time in the following format: *yyyymmddhhmmss* (year,month,day, hour,minute,second). The time portion of the argument, if supplied, is ignored. Any records with timestamps during that day are selected. If any hours, minutes, or seconds are given, they are ignored. *-D* cannot be used with *-A* or *-B*.
- E end-record* Selects the last record matching the selection criteria to display.

<code>-e <i>events</i></code>	<p>Selects records of the indicated events. <i>events</i> is a comma-separated list of audit events. An event may be specified by its numeric value or its name. The <code>AEV_</code> prefix may be omitted. For example, the event for SSH login can be expressed as <code>AEV_LOGIN_SSH</code>, <code>LOGIN_SSH</code> or <code>4</code>.</p> <p>See <code>showaudit -e all</code> for a list of valid events.</p>
<code>-h</code>	<p>Displays usage statement.</p> <p>When used with other options or operands, an error occurs.</p>
<code>-i <i>audit-ids</i></code>	<p>Selects records of the indicated audit session identifier. If you become interested in activity reflected in a particular audit record, you might wish to view all the audit records for that session. An <i>audit-id</i> is not persistent and can be reassigned across resets of the Service Processor. <i>audit-ids</i> is a comma-separated list of audit session identifiers. The <i>audit-id</i> is the number following the label subject in an audit file.</p> <p>For example, in the following listing, the <i>audit-id</i> is 1 (shown in boldface for emphasis).</p> <pre>subject, 1, bob, normal, telnet 45880 jupiter</pre>
<code>-l</code>	Prints one line per record.
<code>-m <i>del</i></code>	<p>Uses <i>del</i> as the field delimiter instead of the default delimiter, which is the comma. If <i>del</i> has special meaning for the shell, it must be quoted. The maximum size of a delimiter is three characters. The delimiter is not meaningful and is not used with the <code>-x</code> option.</p>
<code>-n</code>	Specifies that UIDs and IP addresses should not be converted to user names or host names.
<code>-p <i>privilege-results</i></code>	<p>Select records according to the indicated <i>privilege-results</i>. <i>privilege-results</i> is a comma-separated list. <i>privilege-results</i> are: <code>granted</code>, <code>denied</code>, or <code>error</code>.</p>
<code>-r <i>return-values</i></code>	<p>Selects records according to the indicated return values. <i>returnvals</i> is a comma-separated list of the values: <code>success</code>, or <code>failure</code>. <code>success</code> corresponds to a return value of 0. <code>failure</code> corresponds to a nonzero return value.</p>
<code>-S <i>start-record</i></code>	Selects the first record matching the selection criteria to display.

`-u users` Selects records attributed to indicated users. *users* is a comma-separated list of users. A user can be specified by user name or numeric UID.

`-x` Prints in XML format.

EXAMPLES**EXAMPLE 1** Displaying Audit Records for December 12, 2005

```
XSCF> viewaudit -D 20051212
```

```
file,1,2006-01-11 10:52:30.391 -05:00,20060111155230.0000000000.jupiter
```

EXAMPLE 2 Displaying User Audit Records

```
XSCF> viewaudit -u jsmith
```

```
file,1,2006-01-11 10:52:30.391 -05:00,20060111155230.0000000000.jupiter
```

```
header,37,1,login - telnet,jupiter,2006-01-11 11:31:09.659 -05:00
```

```
subject,1,jsmith,normal,ssh 45880 jupiter
```

```
command,showuser
```

```
platform access,granted
```

```
return,0
```

EXAMPLE 3 Displaying Audit Records for Privileges

```
XSCF> viewaudit -p granted
```

```
file,1,2006-01-11 10:52:30.391 -05:00,20060111155230.0000000000.jupiter
```

```
header,37,1,login - telnet,jupiter,2006-01-11 11:31:09.659 -05:00
```

```
subject,1,jsmith,normal,ssh 45880 jupiter
```

```
command,showuser
```

```
platform access,granted
```

```
return,0
```

EXAMPLE 4 Displaying Audit Records for Successful Access

```
XSCF> viewaudit -r success

file,1,2006-01-11 10:52:30.391 -05:00,20060111155230.0000000000.jupiter
header,37,1,login - telnet,jupiter,2006-01-11 11:31:09.659 -05:00
subject,1,jsmith,normal,ssh 45880 jupiter
command,showuser
platform access,granted
return,0

header,57,1,command - viewaudit,jupiter.company.com,2006-01-26
16:13:09.128 -05:00
subject,5,sue,normal,ssh 1282 saturn
command,viewaudit
platform access,granted
return,0

...
```

EXAMPLE 5 Displaying Audit Records Within a Range of Two Days

```
XSCF> viewaudit -A 20080108 -B +2d

file,1,2008-01-09 20:12:12.968 -08:00,20080110041212.0000000004.sca-m5k-0-0
file,1,2008-01-10 21:14:49.481 -08:00,terminated
file,1,2008-01-10 21:14:49.485 -08:00,20080111051449.0000000005.sca-m5k-0-0
```

EXAMPLE 6 Displaying First 5 Records (of 4238) that Match a Date Range

```
XSCF> viewaudit -l -A 20070515 -B 20080110 -C -S 1 -E 5

file,1,2008-01-09 20:12:12.968 -08:00,20080110041212.0000000004.sca-m5k-0-0
header,63,1,command - setaudit,sca-m5k-0-0.sfbay.sun.com,2008-01-09
20:12:12.974 -08:00,s subject,250,opl,normal,ssh 42759 san-e4900-
0.West.Sun.COM,command,setaudit,delete,platform access,granted,return,0
header,37,1,login - ssh,sca-m5k-0-0.sfbay.sun.com,2008-01-09 20:12:14.455 -
08:00,subject, 252,scfroot,normal,ssh 42761 san-e4900-0.West.Sun.COM
```

```
header,37,1,logout,sca-m5k-0-0.sfbay.sun.com,2008-01-09 20:12:14.800 -
08:00,subject,250,o pl,normal,ssh 42759 san-e4900-0.West.Sun.COM
header,37,1,login - ssh,sca-m5k-0-0.sfbay.sun.com,2008-01-09 20:12:15.595 -
08:00,subject, 253,scfroot,normal,ssh 42762 san-e4900-0.West.Sun.COM
4238
```

EXIT STATUS The following exit values are returned:

0 Successful completion.
>0 An error occurred.

SEE ALSO **setaudit(8)**, **showaudit(8)**

viewaudit(8)



NAME	who - display a list of the user accounts who are logged in to the XSCF
SYNOPSIS	who who -h
DESCRIPTION	<p>who(1) displays a list of the user accounts who are logged in to the XSCF.</p> <p>The following information is displayed:</p> <ul style="list-style-type: none"> ■ XSCF user account name ■ Terminal used ■ Idle time ■ Login time ■ Remote host name
Privileges	<p>No privileges are required to run this command.</p> <p>Refer to <code>setprivileges(8)</code> for more information.</p>
OPTIONS	<p>The following option is supported:</p> <p>-h Displays usage statement.</p>
EXAMPLES	<p>EXAMPLE 1 Displays a list of the user accounts who are logged in to the XSCF.</p> <pre>XSCF> who USER TTY IDLE FROM HOST scf pts/0 00:00m Dec 21 13:57 JJJJ.ggg.fujitsu.com</pre>
EXIT STATUS	<p>The following exit values are returned:</p> <p>0 Successful completion.</p> <p>>0 An error occurred.</p>

who(1)

