



C User's Guide

Sun™ Studio 11

Sun Microsystems, Inc.
www.sun.com

Part No. 819-3688-10
November 2005, Revision A

Submit comments about this document at: <http://www.sun.com/hwdocs/feedback>

Copyright © 2005 Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, California 95054, U.S.A. All rights reserved.

U.S. Government Rights - Commercial software. Government users are subject to the Sun Microsystems, Inc. standard license agreement and applicable provisions of the FAR and its supplements. Use is subject to license terms.

This distribution may include materials developed by third parties.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and in other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, Java, and JavaHelp are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon architecture developed by Sun Microsystems, Inc.

This product is covered and controlled by U.S. Export Control laws and may be subject to the export or import laws in other countries. Nuclear, missile, chemical biological weapons or nuclear maritime end uses or end users, whether direct or indirect, are strictly prohibited. Export or reexport to countries subject to U.S. embargo or to entities identified on U.S. export exclusion lists, including, but not limited to, the denied persons and specially designated nationals lists is strictly prohibited.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright © 2005 Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, California 95054, Etats-Unis. Tous droits réservés.

L'utilisation est soumise aux termes de la Licence.

Cette distribution peut comprendre des composants développés par des tierces parties.

Des parties de ce produit pourront être dérivées des systèmes Berkeley BSD licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, Java, et JavaHelp sont des marques de fabrique ou des marques déposées de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays. Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

Ce produit est soumis à la législation américaine en matière de contrôle des exportations et peut être soumis à la réglementation en vigueur dans d'autres pays dans le domaine des exportations et importations. Les utilisations, ou utilisateurs finaux, pour des armes nucléaires, des missiles, des armes biologiques et chimiques ou du nucléaire maritime, directement ou indirectement, sont strictement interdites. Les exportations ou réexportations vers les pays sous embargo américain, ou vers des entités figurant sur les listes d'exclusion d'exportation américaines, y compris, mais de manière non exhaustive, la liste de personnes qui font objet d'un ordre de ne pas participer, d'une façon directe ou indirecte, aux exportations des produits ou des services qui sont régis par la législation américaine en matière de contrôle des exportations et la liste de ressortissants spécifiquement désignés, sont rigoureusement interdites.

LA DOCUMENTATION EST FOURNIE "EN L'ÉTAT" ET TOUTES AUTRES CONDITIONS, DECLARATIONS ET GARANTIES EXPRESSES OU TACITES SONT FORMELLEMENT EXCLUES, DANS LA MESURE AUTORISEE PAR LA LOI APPLICABLE, Y COMPRIS NOTAMMENT TOUTE GARANTIE IMPLICITE RELATIVE A LA QUALITE MARCHANDE, A L'APTITUDE A UNE UTILISATION PARTICULIERE OU A L'ABSENCE DE CONTREFAÇON.



Adobe PostScript

Contents

Before You Begin	xxxi
Typographic Conventions	xxxii
Shell Prompts	xxxiii
Supported Platforms	xxxiii
Accessing Sun Studio Software and Man Pages	xxxiv
Accessing Sun Studio Documentation	xxxvii
Accessing Related Solaris Documentation	xxxix
Resources for Developers	xxxix
Contacting Sun Technical Support	xl
Sending Your Comments	xl
1. Introduction to the C Compiler	1-1
1.1 New Features and Functionality of the Sun Studio 10 C 5.8 Compiler	1-1
1.2 New Features and Functionality of the Sun Studio 10 C 5.7 Compiler	1-3
1.3 Standards Conformance	1-4
1.4 C Readme File	1-5
1.5 Man Pages	1-6
1.6 Organization of the Compiler	1-6
1.7 C-Related Programming Tools	1-8

- 2. C-Compiler Information Specific to Sun's Implementation 2-1
 - 2.1 Constants 2-1
 - 2.1.1 Integral Constants 2-1
 - 2.1.2 Character Constants 2-2
 - 2.2 Linker Scoping Specifiers 2-3
 - 2.3 Thread Local Storage Specifier 2-3
 - 2.4 Floating Point, Nonstandard Mode 2-4
 - 2.5 Labels as Values 2-5
 - 2.6 long long Data Type 2-8
 - 2.6.1 Printing long long Data Types 2-8
 - 2.6.2 Usual Arithmetic Conversions 2-8
 - 2.7 Assertions 2-9
 - 2.8 Pragmas 2-10
 - 2.8.1 align 2-10
 - 2.8.2 c99 2-11
 - 2.8.3 does_not_read_global_data 2-11
 - 2.8.4 does_not_return 2-12
 - 2.8.5 does_not_write_global_data 2-12
 - 2.8.6 error_messages 2-12
 - 2.8.7 fini 2-13
 - 2.8.8 hdrstop 2-13
 - 2.8.9 ident 2-14
 - 2.8.10 init 2-14
 - 2.8.11 inline 2-15
 - 2.8.12 int_to_unsigned 2-15
 - 2.8.13 MP serial_loop 2-16
 - 2.8.14 MP serial_loop_nested 2-16
 - 2.8.15 MP taskloop 2-16

- 2.8.16 `nomemorydepend` 2-16
- 2.8.17 `no_side_effect` 2-17
- 2.8.18 `opt` 2-17
- 2.8.19 `pack` 2-18
- 2.8.20 `pipelooop` 2-19
- 2.8.21 `rarely_called` 2-19
- 2.8.22 `redefine_extname` 2-19
- 2.8.23 `returns_new_memory` 2-21
- 2.8.24 `unknown_control_flow` 2-21
- 2.8.25 `unroll` 2-21
- 2.8.26 `warn_missing_parameter_info` 2-22
- 2.8.27 `weak` 2-23
- 2.9 Predefined Names 2-23
- 2.10 The Value of `errno` 2-24
- 2.11 `_Restrict` Keyword 2-25
- 2.12 `_ _asm` Keyword 2-25
- 2.13 Environment Variables 2-25
 - 2.13.1 `OMP_DYNAMIC` 2-25
 - 2.13.2 `OMP_NESTED` 2-26
 - 2.13.3 `OMP_NUM_THREADS` 2-26
 - 2.13.4 `OMP_SCHEDULE` 2-26
 - 2.13.5 `PARALLEL` 2-26
 - 2.13.6 `SUN_PROFDATA` 2-26
 - 2.13.7 `SUN_PROFDATA_DIR` 2-26
 - 2.13.8 `SUNPRO_SB_INIT_FILE_NAME` 2-26
 - 2.13.9 `SUNW_MP_THR_IDLE` 2-27
 - 2.13.10 `TMPDIR` 2-27

- 2.14 How to Specify Include Files 2-27
 - 2.14.1 Using the `-I-` Option to Change the Search Algorithm 2-28

3. Parallelizing Sun C Code 3-1

- 3.1 Overview 3-1
 - 3.1.1 Example of Use 3-1
- 3.2 Parallelizing for OpenMP 3-2
 - 3.2.1 Handling OpenMP Runtime Warnings 3-2
- 3.3 Environment Variables 3-2
- 3.4 Data Dependence and Interference 3-5
 - 3.4.1 Parallel Execution Model 3-7
 - 3.4.2 Private Scalars and Private Arrays 3-8
 - 3.4.3 Storeback 3-10
 - 3.4.4 Reduction Variables 3-11
- 3.5 Speedups 3-11
 - 3.5.1 Amdahl's Law 3-12
- 3.6 Load Balance and Loop Scheduling 3-15
 - 3.6.1 Static or Chunk Scheduling 3-15
 - 3.6.2 Self Scheduling 3-15
 - 3.6.3 Guided Self Scheduling 3-16
- 3.7 Loop Transformations 3-16
 - 3.7.1 Loop Distribution 3-16
 - 3.7.2 Loop Fusion 3-17
 - 3.7.3 Loop Interchange 3-19
- 3.8 Aliasing and Parallelization 3-20
 - 3.8.1 Array and Pointer References 3-20
 - 3.8.2 Restricted Pointers 3-21
 - 3.8.3 Explicit Parallelization and Pragmas 3-22

4.	lint	Source Code Checker	4-1
4.1		Basic and Enhanced lint Modes	4-1
4.2		Using lint	4-2
4.3		The lint Options	4-4
4.3.1		-#	4-4
4.3.2		-###	4-4
4.3.3		-a	4-4
4.3.4		-b	4-4
4.3.5		-C <i>filename</i>	4-5
4.3.6		-c	4-5
4.3.7		-dirout= <i>dir</i>	4-5
4.3.8		-err=warn	4-5
4.3.9		-errchk= <i>l, l</i>	4-5
4.3.10		-errfmt= <i>f</i>	4-6
4.3.11		-errhdr= <i>h</i>	4-7
4.3.12		-erroff= <i>tag, tag</i>	4-7
4.3.13		-errsecurity= <i>v</i>	4-8
4.3.14		-errtags= <i>a</i>	4-10
4.3.15		-errwarn= <i>t</i>	4-10
4.3.16		-F	4-11
4.3.17		-fd	4-11
4.3.18		-flagsrc= <i>file</i>	4-11
4.3.19		-h	4-11
4.3.20		-I <i>dir</i>	4-11
4.3.21		-k	4-11
4.3.22		-L <i>dir</i>	4-11
4.3.23		-lx	4-12
4.3.24		-m	4-12

- 4.3.25 `-Ncheck=c` 4-12
- 4.3.26 `-Nlevel=n` 4-13
- 4.3.27 `-n` 4-14
- 4.3.28 `-ox` 4-14
- 4.3.29 `-p` 4-14
- 4.3.30 `-Rfile` 4-14
- 4.3.31 `-s` 4-15
- 4.3.32 `-u` 4-15
- 4.3.33 `-V` 4-15
- 4.3.34 `-v` 4-15
- 4.3.35 `-Wfile` 4-15
- 4.3.36 `-XCC=a` 4-15
- 4.3.37 `-Xalias_level[=l]` 4-16
- 4.3.38 `-Xarch=amd64` 4-16
- 4.3.39 `-Xarch=v9` 4-16
- 4.3.40 `-Xc99[=o]` 4-16
- 4.3.41 `-Xexplicitpar=a` 4-17
- 4.3.42 `-Xkeeptmp=a` 4-17
- 4.3.43 `-Xtemp=dir` 4-17
- 4.3.44 `-Xtime=a` 4-17
- 4.3.45 `-Xtransition=a` 4-17
- 4.3.46 `-Xustr={ascii_utf16_ushort|no}` 4-18
- 4.3.47 `-x` 4-18
- 4.3.48 `-y` 4-18
- 4.4 `lint` Messages 4-18
 - 4.4.1 Options to Suppress Messages 4-18
 - 4.4.2 `lint` Message Formats 4-19

4.5	lint Directives	4-22
4.5.1	Predefined Values	4-22
4.5.2	Directives	4-22
4.6	lint Reference and Examples	4-26
4.6.1	Diagnostics Performed by lint	4-26
4.6.2	lint Libraries	4-31
4.6.3	lint Filters	4-32
5.	Type-Based Alias Analysis	5-1
5.1	Introduction to Type-Based Analysis	5-1
5.2	Using Pragmas for Finer Control	5-2
5.3	Checking With lint	5-5
5.3.1	Struct Pointer Cast of Scalar Pointer	5-6
5.3.2	Struct Pointer Cast of Void Pointer	5-6
5.3.3	Cast of Struct Field to Structure Pointer	5-7
5.3.4	Explicit Aliasing Required	5-7
5.4	Examples of Memory Reference Constraints	5-8
6.	Transitioning to ISO C	6-1
6.1	Basic Modes	6-1
6.1.1	-xc	6-1
6.1.2	-xa	6-1
6.1.3	-xt	6-2
6.1.4	-xs	6-2
6.2	A Mixture of Old- and New-Style Functions	6-2
6.2.1	Writing New Code	6-2
6.2.2	Updating Existing Code	6-3
6.2.3	Mixing Considerations	6-3
6.3	Functions With Varying Arguments	6-6

- 6.4 Promotions: Unsigned Versus Value Preserving 6–9
 - 6.4.1 Background 6–9
 - 6.4.2 Compilation Behavior 6–9
 - 6.4.3 First Example: The Use of a Cast 6–10
 - 6.4.4 Bit-fields 6–11
 - 6.4.5 Second Example: Same Result 6–11
 - 6.4.6 Integral Constants 6–11
 - 6.4.7 Third Example: Integral Constants 6–12
- 6.5 Tokenization and Preprocessing 6–13
 - 6.5.1 ISO C Translation Phases 6–13
 - 6.5.2 Old C Translation Phases 6–14
 - 6.5.3 Logical Source Lines 6–15
 - 6.5.4 Macro Replacement 6–15
 - 6.5.5 Using Strings 6–16
 - 6.5.6 Token Pasting 6–17
- 6.6 `const` and `volatile` 6–17
 - 6.6.1 Types, Only for `lvalue` 6–18
 - 6.6.2 Type Qualifiers in Derived Types 6–18
 - 6.6.3 `const` Means `readonly` 6–19
 - 6.6.4 Examples of `const` Usage 6–20
 - 6.6.5 `volatile` Means Exact Semantics 6–20
 - 6.6.6 Examples of `volatile` Usage 6–20
- 6.7 Multibyte Characters and Wide Characters 6–21
 - 6.7.1 Asian Languages Require Multibyte Characters 6–21
 - 6.7.2 Encoding Variations 6–22
 - 6.7.3 Wide Characters 6–22
 - 6.7.4 Conversion Functions 6–23
 - 6.7.5 C Language Features 6–23

- 6.8 Standard Headers and Reserved Names 6–24
 - 6.8.1 Standard Headers 6–24
 - 6.8.2 Names Reserved for Implementation Use 6–25
 - 6.8.3 Names Reserved for Expansion 6–26
 - 6.8.4 Names Safe to Use 6–26
- 6.9 Internationalization 6–27
 - 6.9.1 Locales 6–27
 - 6.9.2 The `setlocale()` Function 6–27
 - 6.9.3 Changed Functions 6–28
 - 6.9.4 New Functions 6–29
- 6.10 Grouping and Evaluation in Expressions 6–30
 - 6.10.1 Definitions 6–30
 - 6.10.2 The K&R C Rearrangement License 6–31
 - 6.10.3 The ISO C Rules 6–32
 - 6.10.4 The Parentheses 6–32
 - 6.10.5 The As If Rule 6–32
- 6.11 Incomplete Types 6–33
 - 6.11.1 Types 6–33
 - 6.11.2 Completing Incomplete Types 6–34
 - 6.11.3 Declarations 6–34
 - 6.11.4 Expressions 6–34
 - 6.11.5 Justification 6–35
 - 6.11.6 Examples 6–35
- 6.12 Compatible and Composite Types 6–36
 - 6.12.1 Multiple Declarations 6–36
 - 6.12.2 Separate Compilation Compatibility 6–36
 - 6.12.3 Single Compilation Compatibility 6–37
 - 6.12.4 Compatible Pointer Types 6–37

- 6.12.5 Compatible Array Types 6–37
 - 6.12.6 Compatible Function Types 6–37
 - 6.12.7 Special Cases 6–38
 - 6.12.8 Composite Types 6–38
- 7. Converting Applications for a 64-Bit Environment 7–1**
- 7.1 Overview of the Data Model Differences 7–1
 - 7.2 Implementing Single Source Code 7–2
 - 7.2.1 Derived Types 7–3
 - 7.2.2 Tools 7–6
 - 7.3 Converting to the LP64 Data Type Model 7–7
 - 7.3.1 Integer and Pointer Size Change 7–7
 - 7.3.2 Integer and Long Size Change 7–8
 - 7.3.3 Sign Extension 7–8
 - 7.3.4 Pointer Arithmetic Instead of Integers 7–10
 - 7.3.5 Structures 7–10
 - 7.3.6 Unions 7–11
 - 7.3.7 Type Constants 7–12
 - 7.3.8 Beware of Implicit Declarations 7–12
 - 7.3.9 `sizeof()` Is an Unsigned `long` 7–13
 - 7.3.10 Use Casts to Show Your Intentions 7–13
 - 7.3.11 Check Format String Conversion Operation 7–14
 - 7.4 Other Considerations 7–15
 - 7.4.1 Derived Types That Have Grown in Size 7–15
 - 7.4.2 Check for Side Effects of Changes 7–15
 - 7.4.3 Check Whether Literal Uses of `long` Still Make Sense 7–15
 - 7.4.4 Use `#ifdef` for Explicit 32-bit Versus 64-bit Prototypes 7–16
 - 7.4.5 Calling Convention Changes 7–16
 - 7.4.6 Algorithm Changes 7–16
 - 7.5 Checklist for Getting Started 7–17

- 8. **cscope: Interactively Examining a C Program** 8-1
 - 8.1 The cscope Process 8-1
 - 8.2 Basic Use 8-2
 - 8.2.1 Step 1: Set Up the Environment 8-2
 - 8.2.2 Step 2: Invoke the cscope Program 8-3
 - 8.2.3 Step 3: Locate the Code 8-4
 - 8.2.4 Step 4: Edit the Code 8-10
 - 8.2.5 Command-Line Options 8-11
 - 8.2.6 View Paths 8-14
 - 8.2.7 cscope and Editor Call Stacks 8-15
 - 8.2.8 Examples 8-15
 - 8.2.9 Command-Line Syntax for Editors 8-19
 - 8.3 Unknown Terminal Type Error 8-20

- A. **Compiler Options Grouped by Functionality** A-1
 - A.1 Options Summarized by Function A-1
 - A.1.1 Optimization and Performance Options A-1
 - A.1.2 Compile-Time and Link-Time Options A-3
 - A.1.3 Data-Alignment Options A-4
 - A.1.4 Numerics and Floating Point Options A-5
 - A.1.5 Parallelization Options A-6
 - A.1.6 Source-Code Options A-7
 - A.1.7 Compiled-Code Options A-8
 - A.1.8 Compilation-Mode Options A-8
 - A.1.9 Diagnostic Options A-9
 - A.1.10 Debugging Options A-10
 - A.1.11 Linking and Libraries Options A-11
 - A.1.12 Target-Platform Options A-12
 - A.1.13 x86-Specific Options A-12

A.1.14 Licensing Options A-13

A.1.15 Obsolete Options A-13

B. C Compiler Options Reference B-1

B.1 Option Syntax B-1

B.2 The `cc` Options B-2

B.2.1 `-#` B-2

B.2.2 `-###` B-3

B.2.3 `-Aname[(tokens)]` B-3

B.2.4 `-B[static|dynamic]` B-3

B.2.5 `-C` B-4

B.2.6 `-c` B-4

B.2.7 `-Dname[=tokens]` B-4

B.2.8 `-d[y|n]` B-5

B.2.9 `-dalign` B-5

B.2.10 `-E` B-5

B.2.11 `-errfmt[=[no%]error]` B-5

B.2.12 `-erroff[=t]` B-6

B.2.13 `-errshort[=i]` B-6

B.2.14 `-errtags[=a]` B-7

B.2.15 `-errwarn[=t]` B-7

B.2.16 `-fast` B-8

B.2.17 `-fd` B-10

B.2.18 `-features=[[no%]extinl|%none]` B-11

B.2.19 `-flags` B-11

B.2.20 `-flteval[={any|2}]` B-11

B.2.21 `-fnonstd` B-12

B.2.22 `-fns[={no|yes}]` B-12

B.2.23 `-fprecision=p` B-13

B.2.24 `-fround=r` B-13
B.2.25 `-fsimple[=n]` B-13
B.2.26 `-fsingle` B-15
B.2.27 `-fstore` B-15
B.2.28 `-ftrap=t[,t...]` B-15
B.2.29 `-G` B-16
B.2.30 `-g` B-16
B.2.31 `-H` B-17
B.2.32 `-h name` B-18
B.2.33 `-I[- |dir]` B-18
B.2.34 `-i` B-18
B.2.35 `-KPIC` B-18
B.2.36 `-Kpic` B-19
B.2.37 `-keeptmp` B-19
B.2.38 `-Ldir` B-19
B.2.39 `-lname` B-19
B.2.40 `-mc` B-19
B.2.41 `-misalign` B-20
B.2.42 `-misalign2` B-20
B.2.43 `-mr[,string]` B-20
B.2.44 `-mt` B-20
B.2.45 `-native` B-20
B.2.46 `-nofstore` B-21
B.2.47 `-O` B-21
B.2.48 `-o filename` B-21
B.2.49 `-P` B-21
B.2.50 `-p` B-21
B.2.51 `-Q[y|n]` B-22

B.2.52 `-qp` B-22
B.2.53 `-Rdir[:dir]` B-22
B.2.54 `-s` B-22
B.2.55 `-s` B-22
B.2.56 `-Uname` B-23
B.2.57 `-v` B-23
B.2.58 `-v` B-23
B.2.59 `-Wc, arg` B-24
B.2.60 `-w` B-25
B.2.61 `-X[c|a|t|s]` B-25
B.2.62 `-x386` B-26
B.2.63 `-x486` B-26
B.2.64 `-xa` B-26
B.2.65 `-xalias_level[=l]` B-26
B.2.66 `-xarch=isa` B-29
B.2.67 `-xautopar` B-36
B.2.68 `-xbinopt={prepare|off}` B-37
B.2.69 `-xbuiltin[=(%all|%none)]` B-38
B.2.70 `-xCC` B-38
B.2.71 `-xc99[=o]` B-38
B.2.72 `-xcache[=c]` B-39
B.2.73 `-xcg[89|92]` B-41
B.2.74 `-xchar[=o]` B-41
B.2.75 `-xchar_byte_order[=o]` B-42
B.2.76 `-xcheck[=o]` B-42
B.2.77 `-xchip[=c]` B-43
B.2.78 `-xcode[=v]` B-45
B.2.79 `-xcrossfile[=n]` B-47

B.2.80 -xcsi B-47
B.2.81 -xdebugformat=[stabs|dwarf] B-48
B.2.82 -xdepend=[yes|no] B-48
B.2.83 -xdryrun B-49
B.2.84 -xe B-49
B.2.85 -xexplicitpar B-49
B.2.86 -xF B-50
B.2.87 -xhelp=*f* B-51
B.2.88 -xhwcprof B-51
B.2.89 -xinline=*list* B-52
B.2.90 -xipo[=*a*] B-54
B.2.91 -xipo_archive=[*a*] B-56
B.2.92 -xjobs=*n* B-57
B.2.93 -xldscope={*v*} B-57
B.2.94 -xlibmieee B-59
B.2.95 -xlibmil B-59
B.2.96 -xlibmopt B-59
B.2.97 -xlic_lib=sunperf B-60
B.2.98 -xlicinfo B-60
B.2.99 -xlinkopt[=*level*] B-60
B.2.100 -xloopinfo B-61
B.2.101 -xM B-61
B.2.102 -xM1 B-62
B.2.103 -xMerge B-63
B.2.104 -xmaxopt[=*v*] B-63
B.2.105 -xmemalign=*ab* B-63
B.2.106 -xmodel=[*a*] B-64
B.2.107 -xnativeconnect[=*a*[,*a*]. . .] B-65

B.2.108 `-xnolib` B-66
B.2.109 `-xnolibmil` B-66
B.2.110 `-xnolibmopt` B-67
B.2.111 `-xO[1|2|3|4|5]` B-67
B.2.112 `-xopenmp[=i]` B-70
B.2.113 `-xP` B-71
B.2.114 `-xpagesize=n` B-71
B.2.115 `-xpagesize_heap=n` B-72
B.2.116 `-xpagesize_stack=n` B-73
B.2.117 `-xparallel` B-74
B.2.118 `-xpch=v` B-74
B.2.119 `-xpchstop=[file|<include>]` B-80
B.2.120 `-xpentium` B-80
B.2.121 `-xpg` B-80
B.2.122 `-xprefetch[=val[,val]]` B-81
B.2.123 `-xprefetch_auto_type=a` B-82
B.2.124 `-xprefetch_level=l` B-83
B.2.125 `-xprofile=p` B-83
B.2.126 `-xprofile_ircache[=path]` B-86
B.2.127 `-xprofile_pathmap` B-87
B.2.128 `-xreduction` B-87
B.2.129 `-xregs=r[,r...]` B-88
B.2.130 `-xrestrict[=f]` B-90
B.2.131 `-xs` B-90
B.2.132 `-xsafe=mem` B-90
B.2.133 `-xsb` B-91
B.2.134 `-xsbfast` B-91
B.2.135 `-xsfpcnst` B-91

- B.2.136 `-xspace` B-92
 - B.2.137 `-xstrconst` B-92
 - B.2.138 `-xtarget=t` B-92
 - B.2.139 `-xtemp=dir` B-97
 - B.2.140 `-xthreadvar[=o]` B-97
 - B.2.141 `-xtime` B-98
 - B.2.142 `-xtransition` B-98
 - B.2.143 `-xtrigraphs` B-99
 - B.2.144 `-xunroll=n` B-100
 - B.2.145 `-xustr={ascii_utf16_ushort|no}` B-100
 - B.2.146 `-xvector[=a]` B-101
 - B.2.147 `-xvis` B-102
 - B.2.148 `-xvpara` B-102
 - B.2.149 `-Yc, dir` B-103
 - B.2.150 `-YA, dir` B-103
 - B.2.151 `-YI, dir` B-103
 - B.2.152 `-YP, dir` B-103
 - B.2.153 `-YS, dir` B-103
 - B.2.154 `-z11` B-104
- B.3 Options Passed to the Linker B-104

C. Implementation-Defined ISO/IEC C99 Behavior C-1

- C.1 Implementation-defined Behavior (J.3) C-1
 - C.1.1 Translation (J.3.1) C-1
 - C.1.2 Environment (J.3.2) C-2
 - C.1.3 Identifiers (J.3.3) C-5
 - C.1.4 Characters (J.3.4) C-5
 - C.1.5 Integers (J.3.5) C-6
 - C.1.6 Floating point (J.3.6) C-7

- C.1.7 Arrays and Pointers (J.3.7) C-8
- C.1.8 Hints (J.3.8) C-8
- C.1.9 Structures, Unions, Enumerations, and Bit-fields (J.3.9) C-9
- C.1.10 Qualifiers (J.3.10) C-10
- C.1.11 Preprocessing Directives (J.3.11) C-10
- C.1.12 Library Functions (J.3.12) C-11
- C.1.13 Architecture (J.3.13) C-17
- C.1.14 Locale-specific Behavior (J.4) C-22

D. Supported Features of C99 D-1

- D.1 Discussion and Examples D-1
 - D.1.1 Precision of Floating Point Evaluators D-2
 - D.1.2 C99 Keywords D-3
 - D.1.3 `__func__` Support D-4
 - D.1.4 Universal Character Names (UCN) D-4
 - D.1.5 Commenting Code With `//` D-4
 - D.1.6 Disallowed Implicit `int` and Implicit Function Declarations D-5
 - D.1.7 Declarations Using Implicit `int` D-5
 - D.1.8 Flexible Array Members D-6
 - D.1.9 Idempotent Qualifiers D-7
 - D.1.10 `inline` Functions D-8
 - D.1.11 `static` and Other Type Qualifiers Allowed in Array Declarators D-9
 - D.1.12 Variable Length Arrays (VLA): D-9
 - D.1.13 Designated Initializers D-10
 - D.1.14 Mixed Declarations and Code D-11
 - D.1.15 Declaration in `for`-Loop Statement D-12
 - D.1.16 Macros With a Variable Number of Arguments D-12
 - D.1.17 `_Pragma` D-13

E. Implementation-Defined ISO/IEC C90 Behavior E-1

- E.1 Implementation Compared to the ISO Standard E-1
 - E.1.1 Translation (G.3.1) E-1
 - E.1.2 Environment (G.3.2) E-2
 - E.1.3 Identifiers (G.3.3) E-2
 - E.1.4 Characters (G.3.4) E-3
 - E.1.5 Integers (G.3.5) E-4
 - E.1.6 Floating-Point (G.3.6) E-6
 - E.1.7 Arrays and Pointers (G.3.7) E-7
 - E.1.8 Registers (G.3.8) E-8
 - E.1.9 Structures, Unions, Enumerations, and Bit-Fields (G.3.9) E-8
 - E.1.10 Qualifiers (G.3.10) E-10
 - E.1.11 Declarators (G.3.11) E-10
 - E.1.12 Statements (G.3.12) E-10
 - E.1.13 Preprocessing Directives (G.3.13) E-10
 - E.1.14 Library Functions (G.3.14) E-12
 - E.1.15 Locale-Specific Behavior (G.4) E-18

F. ISO C Data Representations F-1

- F.1 Storage Allocation F-1
- F.2 Data Representations F-2
 - F.2.1 Integer Representations F-3
 - F.2.2 Floating-Point Representations F-4
 - F.2.3 Exceptional Values F-6
 - F.2.4 Hexadecimal Representation of Selected Numbers F-7
 - F.2.5 Pointer Representation F-7
 - F.2.6 Array Storage F-8
 - F.2.7 Arithmetic Operations on Exceptional Values F-8
- F.3 Argument-Passing Mechanism F-10

G. Performance Tuning (SPARC) G-1

G.1 Limits G-1

G.2 `libfast.a` Library G-2

H. The Differences Between K&R Sun C and Sun ISO C H-1

H.1 K&R Sun C Incompatibilities With Sun ISO C H-1

H.2 Keywords H-7

Index Index-1

Figures

- FIGURE 1-1 Organization of the C Compilation System 1–7
- FIGURE 3-1 Master and Slave Threads 3–7
- FIGURE 3-2 Parallel Execution of a Loop 3–8
- FIGURE 3-3 Fixed Problem Speedups 3–12
- FIGURE 3-4 Amdahl's Law Speedup Curve 3–13
- FIGURE 3-5 Speedup Curve With Overheads 3–14

Tables

TABLE 1-1	Components of the C Compilation System	1–8
TABLE 2-1	Data Type Suffixes	2–1
TABLE 2-2	Declaration Specifiers	2–3
TABLE 2-3	Predefined Identifier	2–23
TABLE 4-1	The <code>-errchk</code> Flags	4–5
TABLE 4-2	The <code>-errfmt</code> Flags	4–6
TABLE 4-3	The <code>-errhdr</code> Flags	4–7
TABLE 4-4	The <code>-erroff</code> Flags	4–8
TABLE 4-5	The <code>-errsecurity</code> Flags	4–9
TABLE 4-6	The <code>-errwarn</code> Flags	4–10
TABLE 4-7	The <code>-Ncheck</code> Flags	4–12
TABLE 4-8	<code>lint</code> Options to Suppress Messages	4–19
TABLE 4-9	The <code>lint</code> Directives	4–23
TABLE 6-1	Trigraph Sequences	6–13
TABLE 6-2	Standard Headers	6–24
TABLE 6-3	Names Reserved for Expansion	6–26
TABLE 7-1	Data Type Size for ILP32 and LP64	7–2
TABLE 8-1	<code>cscope</code> Menu Manipulation Commands	8–4
TABLE 8-2	Commands for Use After an Initial Search	8–6
TABLE 8-3	Commands for Selecting Lines to Be Changed	8–16

TABLE A-1	Optimization and Performance Options	A-1
TABLE A-2	Compile-Time and Link-Time Options	A-3
TABLE A-3	Data-Alignment Options	A-4
TABLE A-4	Numerics and Floating Point Options	A-5
TABLE A-5	Parallelization Options	A-6
TABLE A-6	Source-Code Options	A-7
TABLE A-7	Compiled-Code Options	A-8
TABLE A-8	Compilation-Mode Options	A-8
TABLE A-9	Diagnostic Options	A-9
TABLE A-10	Debugging Options	A-10
TABLE A-11	Linking and Libraries Options	A-11
TABLE A-12	Target-Platform Options	A-12
TABLE A-13	x86-Specific Options	A-12
TABLE A-14	Licensing Options	A-13
TABLE A-15	Obsolete Options	A-13
TABLE B-1	The <code>-errfmt</code> Flags	B-5
TABLE B-2	The <code>-erroff</code> Flags	B-6
TABLE B-3	The <code>-errshort</code> Flags	B-7
TABLE B-4	The <code>-errwarn</code> Flags	B-8
TABLE B-5	The <code>-fast</code> Expansion Flags	B-9
TABLE B-6	The <code>-features</code> Flags	B-11
TABLE B-7	The <code>-fiteval</code> Flags	B-11
TABLE B-8	The <code>-fsimple</code> Flags	B-14
TABLE B-9	The <code>-ftrap</code> Flags	B-15
TABLE B-10	The <code>-w</code> Flags	B-24
TABLE B-11	The Levels of Alias-Disambiguation	B-27
TABLE B-12	The <code>-xarch</code> Flags	B-29
TABLE B-13	The <code>-xarch</code> Matrix	B-29
TABLE B-14	The <code>-xarch</code> Flags for SPARC Platforms	B-31
TABLE B-15	The <code>-xarch</code> Flags on x86	B-34

TABLE B-16	The <code>-xc99</code> Flags	B-39
TABLE B-17	The <code>-xcache</code> Flags	B-40
TABLE B-18	The <code>-xchar</code> Flags	B-41
TABLE B-19	The <code>-xcheck</code> Flags	B-42
TABLE B-20	The SPARC <code>-xchip</code> Flags	B-43
TABLE B-21	The x86 <code>-xchip</code> Flags	B-44
TABLE B-22	The <code>-xcode</code> Flags	B-45
TABLE B-23	The <code>-xdebugformat</code> Flags	B-48
TABLE B-24	The <code>-xF</code> Flags	B-51
TABLE B-25	The <code>-xinline</code> Flags	B-53
TABLE B-26	The <code>-xipo_archive</code> Flags	B-56
TABLE B-27	The <code>-xldscope</code> Flags	B-58
TABLE B-28	The <code>-xlinkopt</code> Flags	B-60
TABLE B-29	The <code>-xmemalign</code> Alignment and Behavior Flags	B-63
TABLE B-30	Examples of <code>-xmemalign</code>	B-64
TABLE B-31	The <code>-xmodel</code> Flags	B-65
TABLE B-32	The <code>-xnativeconnect</code> Flags	B-66
TABLE B-33	The <code>-xO</code> Flags on SPARC Platforms	B-68
TABLE B-34	The <code>-xO</code> Flags on x86 Platforms	B-69
TABLE B-35	The <code>-xopenmp</code> Flags	B-70
TABLE B-36	The <code>-xpch</code> Flags	B-75
TABLE B-37	The <code>-xprefetch</code> Flags	B-81
TABLE B-38	The <code>-xregs</code> Flags	B-88
TABLE B-39	The <code>-xtarget</code> Flags	B-92
TABLE B-40	The <code>-xtarget</code> Expansions on SPARC	B-93
TABLE B-41	The <code>-xtarget</code> Expansions on x86 Architecture	B-97
TABLE B-42	The <code>-xthreadvar</code> Flags	B-98
TABLE B-43	The <code>-xvector</code> Flags	B-101
TABLE C-1	Semantics of <code>signal</code> Function Signals	C-2
TABLE C-2	Standard Alphabetic Escape Sequence Unique Values	C-5

TABLE C-3	Padding and Alignment of Structure Members	C-9
TABLE C-4	Results From the <code>sizeof</code> Operator in Bytes	C-21
TABLE C-5	The Names of the Months	C-23
TABLE C-6	Days and Abbreviated Days of the Week	C-23
TABLE D-1	The <code>FLT_EVAL_METHOD</code> Values	D-2
TABLE E-1	Representations and Sets of Values of Integers	E-4
TABLE E-2	Values for a <code>float</code>	E-6
TABLE E-3	Values for a <code>double</code>	E-6
TABLE E-4	Values for <code>long double</code>	E-6
TABLE E-5	Padding and Alignment of Structure Members	E-8
TABLE E-6	Character Sets Tested by <code>isalpha</code> , <code>islower</code> , Etc.	E-13
TABLE E-7	Values Returned on Domain Errors	E-13
TABLE E-8	Semantics for <code>signal</code> Signals	E-14
TABLE E-9	Names of Months	E-19
TABLE E-10	Days and Abbreviated Days of the Week	E-19
TABLE F-1	Storage Allocation for Data Types	F-1
TABLE F-2	Representation of <code>short</code>	F-3
TABLE F-3	Representation of <code>int</code>	F-3
TABLE F-4	Representation of <code>long</code> on x86 and SPARC v8 versus SPARC v9	F-3
TABLE F-5	Representation of <code>long long</code>	F-4
TABLE F-6	<code>float</code> Representation	F-5
TABLE F-7	<code>double</code> Representation	F-5
TABLE F-8	<code>long double</code> Representation (<i>SPARC</i>)	F-5
TABLE F-9	<code>long double</code> Representation (<i>x86</i>)	F-5
TABLE F-10	<code>float</code> Representations	F-6
TABLE F-11	<code>double</code> Representations	F-6
TABLE F-12	<code>long double</code> Representations	F-6
TABLE F-13	Hexadecimal Representation of Selected Numbers (<i>SPARC</i>)	F-7
TABLE F-14	Hexadecimal Representation of Selected Numbers (<i>x86</i>)	F-7
TABLE F-15	Array Types and Storage	F-8

TABLE F-16	Abbreviation Usage	F-9
TABLE F-17	Addition and Subtraction Results	F-9
TABLE F-18	Multiplication Results	F-9
TABLE F-19	Division Results	F-10
TABLE F-20	Comparison Results	F-10
TABLE F-21	Registers Used by x86 Functions to Return Types	F-11
TABLE H-1	K&R Sun C Incompatibilities With Sun ISO C	H-1
TABLE H-2	ISO C Standard Keywords	H-8
TABLE H-3	Sun C (K&R) Keywords	H-8

Before You Begin

This manual describes the C compiler 5.8 for Sun™ Studio 11. This manual is intended for application developers who have a working knowledge of C, and UNIX®.

This manual provides information for many programming and compiler related topics including the following:

- A list of compiler options grouped by function such as optimization or debugging
- An exhaustive, alphabetical, reference of compiler options
- Descriptions of supported ISO/IEC 9899:1999 (referred to as C99 in this manual) features as well as the details of Sun's implementation of the standard
- Information specific to this implementation of the C standard such as pragmas and declaration specifiers
- Description and reference for the `lint` code-checking program
- Instructions for parallelizing code
- Instructions for transitioning 32-bit code to 64-bit code

Typographic Conventions

TABLE P-1 Typeface Conventions

Typeface	Meaning	Examples
AaBbCc123	The names of commands, files, and directories; on-screen computer output	Edit your <code>.login</code> file. Use <code>ls -a</code> to list all files. % You have mail.
AaBbCc123	What you type, when contrasted with on-screen computer output	% su Password:
<i>AaBbCc123</i>	Book titles, new words or terms, words to be emphasized	Read Chapter 6 in the <i>User's Guide</i> . These are called <i>class</i> options. You <i>must</i> be superuser to do this.
<i>AaBbCc123</i>	Command-line placeholder text; replace with a real name or value	To delete a file, type <code>rm filename</code> .

TABLE P-2 Code Conventions

Code Symbol	Meaning	Notation	Code Example
[]	Brackets contain arguments that are optional.	<code>O[n]</code>	<code>O4, O</code>
{ }	Braces contain a set of choices for a required option.	<code>d{y n}</code>	<code>dy</code>
	The “pipe” or “bar” symbol separates arguments, only one of which may be chosen.	<code>B{dynamic static}</code>	<code>Bstatic</code>
:	The colon, like the comma, is sometimes used to separate arguments.	<code>Rdir[:dir]</code>	<code>R/local/libs:/U/a</code>
...	The ellipsis indicates omission in a series.	<code>xinline=<i>fl</i>[...<i>fn</i>]</code>	<code>xinline=alpha,dos</code>

Shell Prompts

Shell	Prompt
C shell	<i>machine-name%</i>
C shell superuser	<i>machine-name#</i>
Bourne shell, Korn shell, and GNU Bourne-Again shell	\$
Superuser for Bourne shell, Korn shell, and GNU Bourne-Again shell	#

Supported Platforms

This Sun Studio release supports systems that use the SPARC® and x86 families of processor architectures: UltraSPARC®, SPARC64, AMD64, Pentium, and Xeon EM64T. The supported systems for the version of the Solaris Operating System you are running are available in the hardware compatibility lists at <http://www.sun.com/bigadmin/hcl>. These documents cite any implementation differences between the platform types.

In this document, these x86 related terms mean the following:

- “x86” refers to the larger family of 64-bit and 32-bit x86 compatible products.
- “x64’ points out specific 64-bit information about AMD64 or EM64T systems.
- “32-bit x86” points out specific 32-bit information about x86 based systems.

For supported systems, see the hardware compatibility lists.

Accessing Sun Studio Software and Man Pages

The Sun Studio software and its man pages are not installed into the standard `/usr/bin/` and `/usr/share/man` directories. To access the software, you must have your `PATH` environment variable set correctly (see [“Accessing the Software” on page xxxiv](#)). To access the man pages, you must have your `MANPATH` environment variable set correctly (see [“Accessing the Man Pages” on page xxxv](#)).

For more information about the `PATH` variable, see the `cs(1)`, `sh(1)`, `ksh(1)`, and `bash(1)` man pages. For more information about the `MANPATH` variable, see the `man(1)` man page. For more information about setting your `PATH` variable and `MANPATH` variable to access this release, see the installation guide or your system administrator.

Note – The information in this section assumes that your Sun Studio software is installed in the `/opt` directory on Solaris platforms and in the `/opt/sun` directory on Linux platforms. If your software is not installed in the default directory, ask your system administrator for the equivalent path on your system.

Accessing the Software

Use the steps below to determine whether you need to change your `PATH` variable to access the software.

To Determine Whether You Need to Set Your `PATH` Environment Variable

1. Display the current value of the `PATH` variable by typing the following at a command prompt.

```
% echo $PATH
```

2. **On Solaris platforms, review the output to find a string of paths that contain `/opt/SUNWspro/bin`. On Linux platforms, review the output to find a string of paths that contain `/opt/sun/sunstudio11/bin`.**

If you find the path, your `PATH` variable is already set to access the software. If you do not find the path, set your `PATH` environment variable by following the instructions in the next procedure.

To Set Your `PATH` Environment Variable to Enable Access to the Software

- **On Solaris platforms, add the following path to your `PATH` environment variable. If you have previously installed Forte Developer software, Sun ONE Studio software, or another release of Sun Studio software, add the following path before the paths to those installations.**

```
/opt/SUNWspro/bin
```

- **On Linux platforms, add the following path to your `PATH` environment variable.**

```
/opt/sun/sunstudio11/bin
```

Accessing the Man Pages

Use the following steps to determine whether you need to change your `MANPATH` variable to access the man pages.

To Determine Whether You Need to Set Your `MANPATH` Environment Variable

1. **Request the `dbx` man page by typing the following at a command prompt.**

```
% man dbx
```

2. **Review the output, if any.**

If the `dbx(1)` man page cannot be found or if the man page displayed is not for the current version of the software, follow the instructions in the next procedure to set your `MANPATH` environment variable.

To Set Your MANPATH Environment Variable to Enable Access to the Man Pages

- **On Solaris platforms, add the following path to your MANPATH environment variable.**

`/opt/SUNWspro/man`

- **On Linux platforms, add the following path to your MANPATH environment variable.**

`/opt/sun/sunstudio11/man`

Accessing the Integrated Development Environment

The Sun Studio integrated development environment (IDE) provides modules for creating, editing, building, debugging, and analyzing the performance of a C, C++, or Fortran application.

The command to start the IDE is `sunstudio`. For details on this command, see the `sunstudio(1)` man page.

The correct operation of the IDE depends on the IDE being able to find the core platform. The `sunstudio` command looks for the core platform in two locations:

- The command looks first in the default installation directory,
`/opt/netbeans/3.5V11` on Solaris platforms and
`/opt/sun/netbeans/3.5V11` on Linux platforms.
- If the command does not find the core platform in the default directory, it assumes that the directory that contains the IDE and the directory that contains the core platform are both installed in or mounted to the same location. For example, on Solaris platforms, if the path to the directory that contains the IDE is `/foo/SUNWspro`, the command looks for the core platform in `/foo/netbeans/3.5V11`. On Linux platforms, if the path to the directory that contains the IDE is `/foo/sunstudio11`, the command looks for the core platform in `/foo/netbeans/3.5V11`.

If the core platform is not installed or mounted to either of the locations where the `sunstudio` command looks for it, then each user on a client system must set the environment variable `SPRO_NETBEANS_HOME` to the location where the core platform is installed or mounted (`/installation_directory/netbeans/3.5V11`).

On Solaris platforms, each user of the IDE also must add `/installation_directory/SUNWspro/bin` to their `$PATH` in front of the path to any other release of Forte Developer software, Sun ONE Studio software, or Sun Studio

software. On Linux platforms, each user of the IDE also must add `/installation_directory/sunstudio11/bin` to their `$PATH` in front of the path to any other release of Sun Studio software.

The path `/installation_directory/netbeans/3.5V11/bin` should not be added to the user's `$PATH`.

Accessing Sun Studio Documentation

You can access the documentation at the following locations:

- The documentation is available from the documentation index that is installed with the software on your local system or network at `file:/opt/SUNWsprow/docs/index.html` on Solaris platforms and at `file:/opt/sun/sunstudio11/docs/index.html` on Linux platforms.

If your software is not installed in the `/opt` directory on a Solaris platform or the `/opt/sun` directory on a Linux platform, ask your system administrator for the equivalent path on your system.

- Most manuals are available from the `docs.sun.comsm` web site. The following titles are available through your installed software on Solaris platforms only:
 - *Standard C++ Library Class Reference*
 - *Standard C++ Library User's Guide*
 - *Tools.h++ Class Library Reference*
 - *Tools.h++ User's Guide*
- The release notes for both Solaris platforms and Linux platforms are available from the `docs.sun.com` web site.
- Online help for all components of the IDE is available through the Help menu, as well as through Help buttons on many windows and dialog boxes, in the IDE.

The `docs.sun.com` web site (<http://docs.sun.com>) enables you to read, print, and buy Sun Microsystems manuals through the Internet. If you cannot find a manual, see the documentation index that is installed with the software on your local system or network.

Note – Sun is not responsible for the availability of third-party Web sites mentioned in this document. Sun does not endorse and is not responsible or liable for any content, advertising, products, or other materials that are available on or through such sites or resources. Sun will not be responsible or liable for any actual or alleged damage or loss caused by or in connection with the use of or reliance on any such content, goods, or services that are available on or through such sites or resources.

Documentation in Accessible Formats

The documentation is provided in accessible formats that are readable by assistive technologies for users with disabilities. You can find accessible versions of documentation as described in the following table. If your software is not installed in the `/opt` directory, ask your system administrator for the equivalent path on your system.

Type of Documentation	Format and Location of Accessible Version
Manuals (except third-party manuals)	HTML at http://docs.sun.com
Third-party manuals: <ul style="list-style-type: none">• <i>Standard C++ Library Class Reference</i>• <i>Standard C++ Library User's Guide</i>• <i>Tools.h++ Class Library Reference</i>• <i>Tools.h++ User's Guide</i>	HTML in the installed software on Solaris platforms through the documentation index at <code>file:/opt/SUNWspro/docs/index.html</code>
Readmes	HTML on the Sun Developer Network portal at http://developers.sun.com/prodtech/cc/documentation/
Man pages	HTML in the installed software through the documentation index at <code>file:/opt/SUNWspro/docs/index.html</code> on Solaris platforms, and at <code>file:/opt/sun/sunstudio11/docs/index.html</code> on Linux platforms,
Online help	HTML available through the Help menu and Help buttons in the IDE
Release notes	HTML at http://docs.sun.com

Related Documentation

The following table describes related documentation that is available at `/opt/SUNWspro/docs/index.html` and at <http://docs.sun.com>. If your software is not installed in the `/opt` directory, ask your system administrator for the equivalent path on your system.

Accessing Related Solaris Documentation

The following table describes related documentation that is available through the docs.sun.com web site.

Document Collection	Document Title	Description
Solaris Reference Manual Collection	See the titles of man page sections.	Provides information about the Solaris OS.
Solaris Software Developer Collection	<i>Linker and Libraries Guide</i>	Describes the operations of the Solaris link-editor and runtime linker.

Resources for Developers

Visit the Sun Developer Network Sun Studio portal at <http://developers.sun.com/prodtech/cc> to find these frequently updated resources:

- Articles on programming techniques and best practices
- A knowledge base of short programming tips
- Documentation of the software, as well as corrections to the documentation that is installed with your software
- Information on support levels
- User forums
- Downloadable code samples
- New technology previews

The Sun Studio portal is one of a number of additional resources for developers at the Sun Developer Network website, <http://developers.sun.com>.

Contacting Sun Technical Support

If you have technical questions about this product that are not answered in this document, go to:

<http://www.sun.com/service/contacting>

Sending Your Comments

Sun is interested in improving its documentation and welcomes your comments and suggestions. Submit your comments to Sun at this URL:

<http://www.sun.com/hwdocs/feedback>

Please include the part number of the document in the subject line of your email. For example, the part number for this document is 819-3688-10.

Introduction to the C Compiler

This chapter provides information about the following:

- [Section 1.1, “New Features and Functionality of the Sun Studio 10 C 5.8 Compiler” on page 1-1.](#)
- [Section 1.2, “New Features and Functionality of the Sun Studio 10 C 5.7 Compiler” on page 1-3.](#)
- [Section 1.3, “Standards Conformance” on page 1-4.](#)
- [Section 1.4, “C Readme File” on page 1-5.](#)
- [Section 1.5, “Man Pages” on page 1-6.](#)
- [Section 1.6, “Organization of the Compiler” on page 1-6.](#)
- [Section 1.7, “C-Related Programming Tools” on page 1-8.](#)

1.1 New Features and Functionality of the Sun Studio 10 C 5.8 Compiler

This section provides a brief overview of the new C compiler features and functionality introduced in the Sun Studio 10 C 5.8 Compiler release. For specific explanations, follow the cross references provided for each item.

- **New `-xarch` Flags For x86 Development**

The `-xarch` option now supports the following new flags for development on the x86 platform: `amd64a`, `pentium_proa`, `ssea`, `sse2a`. See “[-xarch=isa](#)” on [page B 29](#) for more information.

- **Support For x86 `-xpagesize` Options**

The `-xpagesize`, `-xpagesize_heap`, `-xpagesize_stack` options are now enabled for x86 platforms as well as SPARC. See “[-xpagesize=n](#)” on [page B 71](#).

- A New `-xmodel` Option To Specify x86 Memory Models

The new `-xmodel` option lets you specify the kernel, small, or medium memory models on the 64-bit AMD architecture. If the size of your global and static variables exceeds two gigabytes, specify `-xmodel=medium`. Otherwise, use the default `-xmodel=small` setting. See “`-xmodel=[a]`” on page B 64 for more information.

- Support For SSE/SSE2 Integral Media Intrinsics

This release supports intrinsic functions for SSE2 128-bit XMM register integral media-instructions. Include the `sunmedia_intrin.h` header file in the source code and specify the `-xbuiltin` option to take advantage of these functions. Furthermore, these intrinsic functions require SSE2 support so specify options such as

```
-xarch=sse2, -xarch=amd64, or -xtarget=opteron.
```

Essentially, the compiler generates inline code for these intrinsic functions. This is easier than manipulating the instructions through assembly language and it can be optimized by the compiler.

For more information about intrinsics, explanations for the function prototypes contained in the header files, and the data types used by these functions, see the ‘Intel C++ Intrinsics Reference’ section of the Intel(R) *C++ Compiler for Linux Systems* manual.

- New `-xvector` Flags for x86 SSE2 Platforms

The `-xvector` option enables automatic generation of calls to the vector library functions and/or the generation of the SIMD (Single Instruction Multiple Data) instructions. See “`-xvector=[a]`” on page B 101 for more information.

- Binary Optimizer for SPARC

A new `-xbinopt` option allows the compiler to prepare the binary file for further optimization by the `binopt(1)` binary optimizer. See “`-xbinopt={prepare|off}`” on page B 37 for more information.

- New SPARC `-xtarget` and `-xchip` Values

The new `-xtarget` flags `ultra3iplus`, `ultra4plus`, and `ultraT1` along with the new `-xchip` flags `ultra3iplus`, `ultra4plus`, and `ultraT1` provide code generation for the UltraSPARC IIIplus, UltraSPARC T1, and UltraSPARC IVplus processors. See “`-xchip=[c]`” on page B 43 and “`-xtarget=t`” on page B 92 for more information.

- A New Default Format For Debugger Information

The C compiler now generates debugger information in the dwarf format by default. This change should be transparent, as the dbx and Performance Analyzer software readily accept and prefer the dwarf format. You can still generate debugger information in the stabs format by specifying `-xdebugformat=stabs`.

- Enhancements to the STACKSIZE Environment Variable

The syntax of the STACKSIZE environment variable has been enhanced to accept a units keyword for denoting the slave thread stacksize: B for Bytes, K for Kilobytes, M for Megabytes, G for Gigabytes.

For example, `setenv STACKSIZE 8192` sets the slave thread stack size to 8 MB. `1235B` sets the slave thread stack size for 1235 Bytes. `1235G` sets it for 1235 Gigabytes. The default for an integer value without a suffix letter is still Kilobytes.

- OpenMP Autoscopying

Autoscopying is now available for C programs. This feature is described in chapter 3 of the Sun Studio *OpenMP API User's Guide*.

- New Pragmas

There are two new pragmas in this release of the C compiler:

- `c99`

- Use the `c99 (implicit | no%implicit)` pragma to find implicit function declarations.

- `[no_]warn_missing_parameter_info`

- Use the `[no_]warn_missing_parameter_info` pragma to find function declarations which contain no parameter-type information.

1.2 New Features and Functionality of the Sun Studio 10 C 5.7 Compiler

This section provides a brief overview of the new C compiler features and functionality introduced in the Sun Studio 10 C 5.7 Compiler release. For specific explanations, follow the cross references provided for each item.

- A new `-xarch` option, `-xarch=amd64`, specifies compilation for the 64-bit AMD instruction set. For more information about `-xarch=amd64`, see [Section B.2.66](#), “`-xarch=isa`” on page B-29.
- A new `-xtarget` option, `-xtarget=opteron`, specifies the `-xarch`, `-xchip`, and `-xcache` settings for 32-bit AMD compilation. For more information about `-xtarget=opteron`, see [Section B.2.138](#), “`-xtarget=t`” on page B-92.

Note – You must specify `-xarch=amd64` to the right of `-fast` and `-xtarget` on the command line to generate 64-bit code. For example, specify `cc -fast -xarch=amd64` or `cc -xtarget=opteron -xarch=amd64`. The new `-xtarget=opteron` option does not automatically generate 64-bit code. It expands to `-xarch=sse2`, `-xchip=opteron`, and `-xcache=64/64/2:1024/64/16` which results in 32-bit code. The `-fast` option also results in 32-bit code because it is a macro which also defines `-xtarget=native`.

- The existing `-xarch=generic64` option now supports the x86 platform in addition to the traditional SPARC platform.
- The C compiler now predefines `__amd64` and `__x86_64` when you specify `-xarch=amd64`.
- A new x86-only flag for the `-xregs` option, `-xregs=[no%]frameptr`, lets you use the frame-pointer register as an unallocated callee-saves register to increase the run-time performance of applications. For more information about `-xregs=[no%]frameptr`, see [Section B.2.129](#), “`-xregs=r[r..]`” on page B-88.
- The C utility `lint` now accepts a new option `-Xarch=amd64`. For more information, see [Section 4.3.38](#), “`-Xarch=amd64`” on page 4-16.
- This release provides OpenMP API for shared-memory parallelism on both the Solaris OS based on x86 platforms as well as the Solaris OS based on SPARC platforms. The same functionality is now enabled on both platforms.

1.3 Standards Conformance

The term C99 used in this book refers to the ISO/IEC 9899:1999 C programming language. The term C90 refers to the ISO/IEC 9899:1990 C programming language.

This compiler supports most of the language features specified in the ISO/IEC 9899:1999, Programming Language - C standard on operating systems earlier than Solaris 10 software. This compiler is in full compliance with the C99 standard on Solaris 10 software when you specify `-xc99=all,lib`.

This compiler also conforms with the ISO/IEC 9899:1990, Programming Languages - C standard.

Because the compiler also supports traditional K&R C (Kernighan and Ritchie, or pre-ANSI C), it can ease your migration to ISO C.

For information on C90 implementation-specific behavior, see [Appendix E](#).

For more information on supported C99 features, see [Appendix D](#).

1.4 C Readme File

The C compiler's readme file highlights important information about the compiler, including:

- Information discovered after the manuals were printed
- New and changed features
- Software corrections
- Problems and workarounds
- Limitations and incompatibilities

To view the text version of the C readme file, type the following at a command prompt:

```
example% cc -xhelp=readme
```

To access the HTML version of the readme, in your Netscape Communicator 4.0 or compatible version browser, open the following file:

```
/opt/SUNWspro/docs/index.html
```

(If your C compiler-software is not installed in the /opt directory, ask your system administrator for the equivalent path on your system.) Your browser displays an index of HTML documents. To open the readme, find its entry in the index, then click the title.

1.5 Man Pages

Online manual (`man`) pages provide immediate documentation about a command, function, subroutine, or collection of such things.

You can display a man page by running the command:

```
example% man topic
```

Throughout the C documentation, man page references appear with the topic name and man section number: `cc(1)` is accessed with `man cc`. Other sections, denoted by `ieee_flags(3M)` for example, are accessed using the `-s` option on the `man` command:

```
example% man -s 3M ieee_flags
```

1.6 Organization of the Compiler

The C compilation system consists of a compiler, an assembler, and a link editor. The `cc` command invokes each of these components automatically unless you use command-line options to specify otherwise.

[Appendix B](#) discusses all the options available with `cc`.

The following figure shows the organization of the C compilation system.




FIGURE 1-1 Organization of the C Compilation System

The following table summarizes the components of the compilation system.

TABLE 1-1 Components of the C Compilation System

Component	Description	Notes on Use
cpp	Preprocessor	-Xs only
acomp	Compiler (preprocessor built in for non-Xs modes)	
ssbd	Static synchronization bug detection	(SPARC)
iropt	Code optimizer	-O, -xO2, -xO3, -xO4, -xO5, -fast
fbe	Assembler	
cg	Code generator, inliner, assembler	(SPARC)
ipo	Interprocedural Optimizer	(SPARC)
postopt	Postoptimizer	(SPARC)
ir2hf	Intermediate code translator	(x86)
ube	Code generator	(x86)
ube_ipa	Interprocedure analyzer	(x86)
ld	Linker	
mcs	Manipulate comment section	-mr

1.7 C-Related Programming Tools

There are a number of tools available to aid in developing, maintaining, and improving your C programs. The two most closely tied to C, `cscope` and `lint`, are described in this book. In addition, a man page exists for each of these tools.

Other tools for source browsing, debugging and performance analysis are available. See [“Accessing Sun Studio Documentation” on page xxxvii](#) for more information.

C-Compiler Information Specific to Sun's Implementation

This chapter documents those areas specific to the C compiler. The information is organized into language extensions and the environment.

The C compiler is compatible with some of the features of the C language described in the new ISO C standard, ISO/IEC 9899-1999. If you wish to compile code that is compatible with the previous C standard, ISO/IEC 9889-1990 standard (and amendment 1), use `-xc99=none` and the compiler disregards the enhancements of the ISO/IEC 9899-1999 standard.

2.1 Constants

This section contains information related to constants that are specific to the Sun C compiler.

2.1.1 Integral Constants

Decimal, octal, and hexadecimal integral constants can be suffixed to indicate type, as shown in the following table.

TABLE 2-1 Data Type Suffixes

Suffix	Type
u or U	unsigned
l or L	long
ll or LL	long long*

TABLE 2-1 Data Type Suffixes (*Continued*)

Suffix	Type
lu, LU, Lu, lU, ul, uL, Ul, or UL	unsigned long
llu, LLU, LLu, llU, ull, ULL, uLL, Ull	unsigned long long*

* The long long and unsigned long long are not available with `-xc99=none` and `-xc` mode.

With the `-xc99=all`, the compiler uses the first item of the following list in which the value can be represented, as required by the size of the constant:

- int
- long int
- long long int

The compiler issues a warning if the value exceeds the largest value a long long int can represent.

With the `-xc99=none`, the compiler uses the first item of the following list in which the value can be represented, as required by the size of the constant, when assigning types to unsuffixed constants:

- int
- long int
- unsigned long int
- long long int
- unsigned long long int

2.1.2 Character Constants

A multiple-character constant that is not an escape sequence has a value derived from the numeric values of each character. For example, the constant `'123'` has a value of:

0	'3'	'2'	'1'
---	-----	-----	-----

or `0x333231`.

With the `-xs` option and in other, non-ISO versions of C, the value is:

0	'1'	'2'	'3'
---	-----	-----	-----

or `0x313233`.

2.2 Linker Scoping Specifiers

Use the following declaration specifiers to help hide declarations and definitions of extern symbols. By using these specifiers, you no longer need to use mapfiles for linker scoping. You can also control the default setting for variable scoping by specifying `-xldscope` on the command line. For more information, see [Section B.2.93, “-xldscope={v}”](#) on page B-57.

TABLE 2-2 Declaration Specifiers

Value	Meaning
<code>__global</code>	The symbol has global linker scoping and is the least restrictive linker scoping. All references to the symbol bind to the definition in the first dynamic module that defines the symbol. This linker scoping is the current linker scoping for extern symbols.
<code>__symbolic</code>	The symbol has symbolic linker scoping and is more restrictive than global linker scoping. All references to the symbol from within the dynamic module being linked bind to the symbol defined within the module. Outside of the module, the symbol appears as though it were global. This linker scoping corresponds to the linker option <code>-Bsymbolic</code> . For more information on the linker, see <code>ld(1)</code> .
<code>__hidden</code>	The symbol has hidden linker scoping. Hidden linker scoping is more restrictive than symbolic and global linker scoping. All references within a dynamic module bind to a definition within that module. The symbol will not be visible outside of the module.

An object or function may be redeclared with a more restrictive specifier, but may not be redeclared with a less restrictive specifier. A symbol may not be declared with a different specifier once the symbol has been defined.

`__global` is the least restrictive scoping, `__symbolic` is more restrictive, and `__hidden` is the most restrictive scoping.

2.3 Thread Local Storage Specifier

Take advantage of thread-local storage by declaring thread-local variables. A thread-local variable declaration consists of a normal variable declaration with the addition of the variable specifier `__thread`. For more information, see [Section B.2.140, “-xthreadvar\[=o\]”](#) on page B-97.

You must include the `__thread` specifier in the first declaration of the thread variable in the source file being compiled.

You can only use the `__thread` specifier in the declaration of an object with static storage duration. You can statically initialize a thread variable as you would any other object of static-storage duration.

Variables that you declare with the `__thread` specifier have the same linker binding as they would without the `__thread` specifier. This includes tentative definitions, such as declarations without initializers.

The address of a thread variable is not a constant. Therefore, the address-of operator (&) for a thread variable is evaluated at run time and returns the address of the thread variable for the current thread. As a consequence, objects of static storage duration are initialized dynamically to the address of a thread variable.

The address of a thread variable is stable for the lifetime of the corresponding thread. Any thread in the process can freely use the address of a thread variable during the variable's lifetime. You cannot use a thread variable's address after its thread terminates. After a thread terminates, all addresses of that thread's variables are invalid.

2.4 Floating Point, Nonstandard Mode

IEEE 754 floating-point default arithmetic is “nonstop.” Underflows are “gradual.” The following is a summary, see the *Numerical Computation Guide* for details.

Nonstop means that execution does not halt on occurrences like division by zero, floating-point overflow, or invalid operation exceptions. For example, consider the following, where x is zero and y is positive:

```
z = y / x;
```

By default, z is set to the value `+Inf`, and execution continues. With the `-fnonstd` option, however, this code causes an exit, such as a core dump.

Here is how gradual underflow works. Suppose you have the following code:

```
x = 10;
for (i = 0; i < LARGE_NUMBER; i++)
    x = x / 10;
```

The first time through the loop, `x` is set to 1; the second time through, to 0.1; the third time through, to 0.01; and so on. Eventually, `x` reaches the lower limit of the machine's capacity to represent its value. What happens the next time the loop runs?

Let's say that the smallest number characterizable is `1.234567e-38`

The next time the loop runs, the number is modified by "stealing" from the mantissa and "giving" to the exponent so the new value is `1.23456e-39` and, subsequently, `1.2345e-40` and so on. This is known as "gradual underflow," which is the default behavior. In nonstandard mode, none of this "stealing" takes place; typically, `x` is simply set to zero.

2.5 Labels as Values

The C compiler recognizes the extension to C known as computed `goto`. Computed `goto` enables runtime determination of branching destinations. The address of a label can be acquired by using the `'&&'` operator and assigned to a pointer of type `void *`:

```
void *ptr;
...
ptr = &&label1;
```

A later `goto` statement can branch to `label1` through `ptr`:

```
goto *ptr;
```

Because `ptr` is computed at runtime, `ptr` can take on the address of any label that is in-scope and the `goto` statement can branch to it.

One way of using computed `goto` is for the implementation of a jump table:

```
static void *ptrarray[] = { &&label1, &&label2, &&label3 };
```

Now the array elements can be selected by indexing:

```
goto *ptrarray[i];
```

Addresses of labels can only be computed from the current function scope. Attempting to take addresses of labels out of the current function yields unpredictable results.

The jump table works similarly to a switch statement though there are some key differences and the jump table can make it more difficult to follow program flow. A notable difference is that the switch-statement jump-destinations are all in the forward direction from the switch reserved word; using computed goto to implement a jump table enables branching in both forward and reverse directions.

```
#include <stdio.h>
void foo()
{
    void *ptr;

    ptr = &&labell;

    goto *ptr;

    printf("Failed!\n");
    return;

    labell:
    printf("Passed!\n");
    return;
}

int main(void)
{
    void *ptr;

    ptr = &&labell;

    goto *ptr;

    printf("Failed!\n");
    return 0;

    labell:
    foo();
    return 0;
}
```

The following example also makes use of a jump table to control program flow:

```
#include <stdio.h>

int main(void)
{
    int i = 0;
    static void * ptr[3]={&&label1, &&label2, &&label3};

    goto *ptr[i];

    label1:
    printf("label1\n");
    return 0;

    label2:
    printf("label2\n");
    return 0;

    label3:
    printf("label3\n");
    return 0;
}

%example: a.out
%example: label1
```

Another application of computed goto is as an interpreter for threaded code. The label addresses within the interpreter function can be stored in the threaded code for fast dispatching.

Here is an alternate way to write the above example:

```
static const int ptrarray[] = { &&label1 - &&label1,
&&label2 - &&label1, &&label3 - &&label1 };
goto *(&&label1 + ptrarray[i]);
```

This is more efficient for shared library code, as it reduces the number of dynamic relocations that are needed, and by consequence, allows the data (ptrarray elements) to be read-only.

2.6 long long Data Type

When you compile with `-xc99=none`, the Sun C compiler includes the data-types `long long`, and `unsigned long long`, which are similar to the data-type `long`. The `long long` data-type stores 64 bits of information; `long` stores 32 bits of information on SPARC V8 and x86. The `long` data-type stores 64 bits on SPARC V9. The `long long` data-type is not available in `-xc` mode.

2.6.1 Printing long long Data Types

To print or scan `long long` data types, prefix the conversion specifier with the letters `ll`. For example, to print `llvar`, a variable of `long long` data type, in signed decimal format, use:

```
printf("%lld\n", llvar);
```

2.6.2 Usual Arithmetic Conversions

Some binary operators convert the types of their operands to yield a common type, which is also the type of the result. These are called the usual arithmetic conversions:

- If either operand is type `long double`, the other operand is converted to `long double`.
- Otherwise, if either operand has type `double`, the other operand is converted to `double`.
- Otherwise, if either operand has type `float`, the other operand is converted to `float`.
- Otherwise, the integral promotions are performed on both operands. Then, these rules are applied:
 - If either operand has type `unsigned long long int`, the other operator is converted to `unsigned long long int`.
 - If either operand has type `long long int`, the other operator is converted to `long long int`.
 - If either operand has type `unsigned long int`, the other operand is converted to `unsigned long int`.

- Otherwise, when you compile on SPARC V9 only and specify `cc -xc99=none`, if one operand has type `long int` and the other has type `unsigned int`, both operands are converted to `unsigned long int`.
- Otherwise, if either operand has type `long int`, the other operand is converted to `long int`.
- Otherwise, if either operand has type `unsigned int`, the other operand is converted to `unsigned int`.
- Otherwise, both operands have type `int`.

2.7 Assertions

A line of the form:

```
#assert predicate (token-sequence)
```

associates the *token-sequence* with the predicate in the assertion name space (separate from the space used for macro definitions). The predicate must be an identifier token.

```
#assert predicate
```

asserts that *predicate* exists, but does not associate any token sequence with it.

The compiler provides the following predefined predicates by default (not in `-xc` mode):

```
#assert system (unix)
#assert machine (sparc) (SPARC)
#assert machine (i386)(x86)
#assert cpu (sparc) (SPARC)
#assert cpu (i386)(x86)
```

`lint` provides the following predefinition predicate by default (not in `-xc` mode):

```
#assert lint (on)
```

Any assertion may be removed by using `#unassert`, which uses the same syntax as `assert`. Using `#unassert` with no argument deletes all assertions on the predicate; specifying an assertion deletes only that assertion.

An assertion may be tested in a `#if` statement with the following syntax:

```
#if #predicate(non-empty token-list)
```

For example, the predefined predicate `system` can be tested with the following line:

```
#if #system(unix)
```

which evaluates true.

2.8 Pragmas

Preprocessing lines of the form:

```
#pragma pp-tokens
```

specify implementation-defined actions.

The following `#pragmas` are recognized by the compilation system. The compiler ignores unrecognized `pragmas`. Using the `-v` option will give a warning for unrecognized `pragmas`.

2.8.1 align

```
#pragma align integer (variable [, variable])
```

The `align` pragma makes all the mentioned variables memory aligned to *integer* bytes, overriding the default. The following limitations apply:

- The *integer* value must be a power of 2 between 1 and 128; valid values are: 1, 2, 4, 8, 16, 32, 64, and 128.
- *variable* is a global or static variable; it cannot be an automatic variable.
- If the specified alignment is smaller than the default, the default is used.

- The pragma line must appear before the declaration of the variables which it mentions; otherwise, it is ignored.
- Any variable that is mentioned but not declared in the text following the pragma line is ignored. For example:

```
#pragma align 64 (aninteger, astring, astruct)
int aninteger;
static char astring[256];
struct astruct{int a; char *b};
```

2.8.2 c99

```
#pragma c99("implicit" | "no%implicit")
```

This pragma controls diagnostics for implicit function declarations. If the `c99` pragma value is set to `"implicit"`, note the use of quotation marks, a warning is generated when the compiler finds an implicit function declaration. If the `c99` pragma value is set to `"no%implicit"`, note the use of quotation marks, the compiler silently accepts implicit function declaration until the pragma value is reset.

The value of the `-xc99` option impacts this pragma. If `-xc99=all`, the pragma is set to `#pragma c99("implicit")` and when `-xc99=none`, the pragma is set to `#pragma c99("no%implicit")`.

This pragma is set to `c99=("implicit")` by default.

2.8.3 does_not_read_global_data

```
#pragma does_not_read_global_data (funcname [,funcname])
```

This pragma asserts that the specified list of routines do not read global data directly or indirectly. This allows for better optimization of code around calls to such routines. In particular, assignment statements or stores could be moved around such calls.

The specified functions must be declared with a prototype or empty parameter list prior to this pragma. If the assertion about global access is not true, then the behavior of the program is undefined.

2.8.4 does_not_return

```
#pragma does_not_return (funcname [, funcname])
```

This pragma is an assertion to the compiler that the calls to the specified routines will not return. This allows the compiler to perform optimizations consistent with that assumption. For example, register life-times will terminate at the call sites which in turn allows more optimizations.

If the specified function does return, then the behavior of the program is undefined. This pragma is permitted only after the specified functions are declared with a prototype or empty parameter list as the following example shows:

```
extern void exit(int);
#pragma does_not_return(exit)

extern void __assert(int);
#pragma does_not_return(__assert)
```

2.8.5 does_not_write_global_data

```
#pragma does_not_write_global_data (funcname [, funcname])
```

This pragma asserts that the specified list of routines do not write global data directly or indirectly. This allows for better optimization of code around calls to such routines. In particular, assignment statements or stores could be moved around such calls.

The specified functions must be declared with a prototype or empty parameter list prior to this pragma. If the assertion about global access is not true, then the behavior of the program is undefined.

2.8.6 error_messages

```
#pragma error_messages (on|off|default, tag... tag)
```

The error message pragma provides control within the source program over the messages issued by the C compiler and lint. For the C compiler, the pragma has an effect on warning messages only. The `-w` option of the C compiler overrides this pragma by suppressing all warning messages.

- `#pragma error_messages (on, tag... tag)`

The `on` option ends the scope of any preceding `#pragma error_messages` option, such as the `off` option, and overrides the effect of the `-erroff` option.

- `#pragma error_messages (off, tag... tag)`

The `off` option prevents the C compiler or the lint program from issuing the given messages beginning with the token specified in the pragma. The scope of the pragma for any specified error message remains in effect until overridden by another `#pragma error_messages`, or the end of compilation.

- `#pragma error_messages (default, tag... tag)`

The `default` option ends the scope of any preceding `#pragma error_messages` directive for the specified tags.

2.8.7 fini

```
#pragma fini (f1[, f2...fn]
```

Causes the implementation to call functions *f1* to *fn* (finalization functions) after it calls `main()` routine. Such functions are expected to be of type `void` and to accept no arguments, and are called either when a program terminates under program control or when the containing shared object is removed from memory. As with “initialization functions,” finalization functions are executed in the order processed by the link editors.

You should be careful when a finalization function affects the global-program state. For example, unless an interface explicitly states what happens when you use a system-library finalization-function, you should capture and restore any global state information, such as the value of `errno`, that the system-library finalization-function may change.

2.8.8 hdrstop

```
#pragma hdrstop
```

The `hdrstop` pragma must be placed after the last header file to identify the end of the viable prefix in each source file that is to share the same precompiled-header file. For example, consider the following files:

```
example% cat a.c
#include "a.h"
#include "b.h"
#include "c.h"
#include <stdio.h>
#include "d.h"
.
.
.
example% cat b.h
#include "a.h"
#include "b.h"
#include "c.h"
```

The viable source prefix ends at `c.h` so you would insert a `#pragma hdrstop` after `c.h` in each file.

`#pragma hdrstop` must only appear at the end of the viable prefix of a source file that is specified with the `cc` command. Do not specify `#pragma hdrstop` in any include file.

2.8.9 ident

```
#pragma ident string
```

Places *string* in the `.comment` section of the executable.

2.8.10 init

```
#pragma init (f1[, f2...fn])
```

Causes the implementation to call functions *f1* to *fn* (initialization functions) before it calls `main()`. Such functions are expected to be of type `void` and to accept no arguments, and are called while constructing the memory image of the program at the start of execution. In the case of initializers in a shared object, they are executed during the operation that brings the shared object into memory, either program start-up or some dynamic loading operation, such as `dlopen()`. The only ordering of calls to initialization functions is the order in which they were processed by the link editors, both static and dynamic.

You should be careful when an initialization function affects the global-program state. For example, unless an interface explicitly states what happens when you use a system-library initialization-function, you should capture and restore any global state information, such as the value of `errno`, that the system-library initialization-function may change.

2.8.11 inline

```
#pragma [no_]inline (funcname [, funcname])
```

This pragma controls the inlining of routine names listed in the argument of the pragma. The scope of this pragma is over the entire file. Only global inlining control is allowed, call-site specific control is not permitted by this pragma.

If you use `#pragma inline`, it provides a suggestion to the compiler to inline the calls in the current file that match the list of routines listed in the pragma. This suggestion may be ignored under certain cases. For example, the suggestion is ignored when the body of the function is in a different module and the crossfile option is not used.

If you use `#pragma no_inline`, it provides a suggestion to the compiler to not inline the calls in the current file that match the list of routines listed in the pragma.

Both `#pragma inline` and `#pragma no_inline` are permitted only after the function is declared with a prototype or empty parameter list as the following example shows:

```
static void foo(int);
static int bar(int, char *);
#pragma inline(foo, bar)
```

See also `-xldscope`, `-xinline`, `-x0`, and `-xcrossfile`.

2.8.12 int_to_unsigned

```
#pragma int_to_unsigned (funcname)
```

For a function that returns a type of `unsigned`, in `-Xt` or `-Xs` mode, changes the function return to be of type `int`.

2.8.13 MP serial_loop

(SPARC) #pragma MP serial_loop

Note – The Sun-specific MP pragmas have been deprecated and are no longer supported. However, the compiler supports the APIs specified by the OpenMP 2.5 standard instead. See the *OpenMP API User’s Guide* for migration information to the directives of the standard.

Refer to [Section 3.8.3.1, “Serial Pragmas”](#) on page 3-22 for details.

2.8.14 MP serial_loop_nested

(SPARC) #pragma MP serial_loop_nested

Note – The Sun-specific MP pragmas have been deprecated and are no longer supported. However, the compiler supports the APIs specified by the OpenMP 2.5 standard instead. See the *OpenMP API User’s Guide* for migration information to the directives of the standard.

Refer to [Section 3.8.3.1, “Serial Pragmas”](#) on page 3-22 for details.

2.8.15 MP taskloop

(SPARC) #pragma MP taskloop

Note – The Sun-specific MP pragmas have been deprecated and are no longer supported. However, the compiler supports the APIs specified by the OpenMP 2.5 standard instead. See the *OpenMP API User’s Guide* for migration information to the directives of the standard.

Refer to [Section 3.8.3.2, “Parallel Pragma”](#) on page 3-23 for details.

2.8.16 nomemorydepend

(SPARC) #pragma nomemorydepend

This pragma specifies that for any iteration of a loop, there are no memory dependences. That is, within any iteration of a loop there are no references to the same memory. This pragma will permit the compiler (pipeliner) to schedule instructions, more effectively, within a single iteration of a loop. If any memory dependences exist within any iteration of a loop, the results of executing the program are undefined. The compiler takes advantage of this information at optimization level of 3 or above.

The scope of this pragma begins with the pragma and ends with whichever of the following occurs first: the beginning of the next block, the next for loop within the current block, the end of the current block. The pragma applies to the next for loop prior to the end of the pragmas scope.

2.8.17 `no_side_effect`

```
(SPARC) #pragma no_side_effect (funcname[, funcname...])
```

funcname specifies the name of a function within the current translation unit. The function must be declared with a prototype or empty parameter list prior to the pragma. The pragma must be specified prior to the function's definition. For the named function, *funcname*, the pragma declares that the function has no side effects of any kind. This means that *funcname* returns a result value that depends only on the passed arguments. In addition, *funcname* and any called descendants:

- Do not access for reading or writing any part of the program state visible in the caller at the point of the call.
- Do not perform I/O.
- Do not change any part of the program state not visible at the point of the call.

The compiler can use this information when doing optimizations using the function. If the function does have side effects, the results of executing a program which calls this function are undefined. The compiler takes advantage of this information at optimization level of 3 or above.

2.8.18 `opt`

```
#pragma opt level (funcname[, funcname])
```

funcname specifies the name of a function defined within the current translation unit. The value of *level* specifies the optimization level for the named function. You can assign optimization levels 0, 1, 2, 3, 4, 5. You can turn off optimization by setting *level* to 0. The functions must be declared with a prototype or empty parameter list prior to the pragma. The pragma must proceed the definitions of the functions to be optimized.

The level of optimization for any function listed in the pragma is reduced to the value of `-xmaxopt`. The pragma is ignored when `-xmaxopt=off`.

2.8.19 pack

```
#pragma pack(n)
```

Use `#pragma pack(n)` to affect member packing of a structure or a union. By default, members of a structure or union are aligned on their natural boundaries; one byte for a char, two bytes for a short, four bytes for an integer etc. If *n* is present, it must be a power of 2 specifying the strictest natural alignment for any structure or union member. Zero is not accepted.

You can use `#pragma pack(n)` to specify an alignment boundary for a structure or union member. For example, `#pragma pack(2)` aligns int, long, long long, float, double, long double, and pointers on two byte boundaries instead of their natural alignment boundaries.

If *n* is the same or greater than the strictest alignment on your platform, (four on x86, eight on SPARC v8, and 16 on SPARC v9), the directive has the effect of natural alignment. Also, if *n* is omitted, member alignment reverts to the natural alignment boundaries.

The `#pragma pack(n)` directive applies to all structure or union definitions which follow it until the next pack directive. If the same structure or union is defined in different translation units with different packing, your program may fail in unpredictable ways. In particular, you should not use `#pragma pack(n)` prior to including a header that defines the interface of a precompiled library. The recommended usage of `#pragma pack(n)` is to place it in your program code immediately before any structure or union to be packed. Follow the packed structure immediately with `#pragma pack()`.

Note that when you use `#pragma pack`, the alignment of the packed structure or union itself is the same as its more strictly aligned member. Therefore any declaration of that struct or union will be at the pack alignment. For example, a struct with only chars has no alignment restrictions, whereas a struct containing a double would be aligned on an 8-byte boundary.

Note – If you use `#pragma pack` to align struct or union members on boundaries other than their natural boundaries, accessing these fields usually leads to a bus error on SPARC. In order to avoid such an error, be sure to also specify the `-xmemalign` option. See [Section B.2.105, “-xmemalign=ab” on page B-63](#), for the optimal way to compile such programs.

2.8.20 pipelooop

(SPARC) `#pragma pipelooop(n)`

This pragma accepts a positive constant integer value, or 0, for the argument *n*. This pragma specifies that a loop is pipelineable and the minimum dependence distance of the loop-carried dependence is *n*. If the distance is 0, then the loop is effectively a Fortran-style `doall` loop and should be pipelined on the target processors. If the distance is greater than 0, then the compiler (pipeliner) will only try to pipeline *n* successive iterations. The compiler takes advantage of this information at optimization level of 3 or above.

The scope of this pragma begins with the pragma and ends with which ever of the following occurs first: the beginning of the next block, the next for loop within the current block, the end of the current block. The pragma applies to the next for loop prior to the end of the pragmas scope.

2.8.21 rarely_called

`#pragma rarely_called(funcname[, funcname])`

This pragma provides a hint to the compiler that the specified functions are called infrequently. This allows the compiler to perform profile-feedback style optimizations on the call-sites of such routines without the overhead of a profile-collections phase. Since this pragma is a suggestion, the compiler may not perform any optimizations based on this pragma.

The specified functions must be declared with a prototype or empty parameter list prior to this pragma. The following is an example of `#pragma rarely_called`:

```
extern void error (char *message);  
#pragma rarely_called(error)
```

2.8.22 redefine_extname

`#pragma redefine_extname old_extname new_extname`

This pragma causes every externally defined occurrence of the name *old_extname* in the object code to be replaced by *new_extname*. As a result, the linker only sees the name *new_extname* at link time. If `#pragma redefine_extname` is encountered after the first use of *old_extname*, as a function definition, an initializer, or an expression, the effect is undefined. (This pragma is not supported in `-Xs` mode.)

When `#pragma redefine_extname` is available, the compiler provides a definition of the predefined macro `__PRAGMA_REDEFINE_EXTNAME`, which lets you write portable code that works both with and without `#pragma redefine_extname`.

The purpose of `#pragma redefine_extname` is to allow an efficient means of redefining a function interface when the name of the function cannot be changed. For example, when the original function definition must be maintained in a library, for compatibility with existing programs, along with a new definition of the same function for use by new programs. This can be accomplished by adding the new function definition to the library by a new name. Consequently, the header file that declares the function uses `#pragma redefine_extname` so that all of the uses of the function are linked with the new definition of that function.

```
#if defined(__STDC__)

#ifdef __PRAGMA_REDEFINE_EXTNAME
extern int myroutine(const long *, int *);
#pragma redefine_extname myroutine __fixed_myroutine
#else /* __PRAGMA_REDEFINE_EXTNAME */

static int
myroutine(const long * arg1, int * arg2)
{
    extern int __myroutine(const long *, int*);
    return (__myroutine(arg1, arg2));
}
#endif /* __PRAGMA_REDEFINE_EXTNAME */

#else /* __STDC__ */

#ifdef __PRAGMA_REDEFINE_EXTNAME
extern int myroutine();
#pragma redefine_extname myroutine __fixed_myroutine
#else /* __PRAGMA_REDEFINE_EXTNAME */

static int
myroutine(arg1, arg2)
    long *arg1;
    int *arg2;
{
    extern int __fixed_myroutine();
    return (__fixed_myroutine(arg1, arg2));
}
#endif /* __PRAGMA_REDEFINE_EXTNAME */

#endif /* __STDC__ */
```

2.8.23 returns_new_memory

```
#pragma returns_new_memory (funcname, funcname)
```

This pragma asserts that the return value of the specified functions does not alias with any memory at the call site. In effect, this call returns a new memory location. This information allows the optimizer to better track pointer values and clarify memory location. This results in improved scheduling, pipelining, and parallelization of loops. However, if the assertion is false, the behavior of the program is undefined.

This pragma is permitted only after the specified functions are declared with a prototype or empty parameter list as the following example shows:

```
void *malloc(unsigned);  
#pragma returns_new_memory(malloc)
```

2.8.24 unknown_control_flow

```
#pragma unknown_control_flow (funcname, funcname)
```

In order to describe procedures that alter the flow graphs of their callers, the C compiler provides the `#pragma unknown_control_flow` directive. Typically, this directive accompanies declarations of functions like `setjmp()`. On Sun systems, the include file `<setjmp.h>` contains the following:

```
extern int setjmp();  
#pragma unknown_control_flow(setjmp)
```

Other functions with properties like those of `setjmp()` must be declared similarly.

In principle, an optimizer that recognizes this attribute could insert the appropriate edges in the control flow graph, thus handling function calls safely in functions that call `setjmp()`, while maintaining the ability to optimize code in unaffected parts of the flow graph.

The specified functions must be declared with a prototype or empty parameter list prior to this pragma.

2.8.25 unroll

```
(SPARC) #pragma unroll (unroll_factor)
```

This pragma accepts a positive constant integer value for the argument *unroll_factor*. For unroll factor other than 1, this directive serves as a suggestion to the compiler that the specified loop should be unrolled by the given factor. The compiler will, when possible, use that unroll factor. When the unroll factor value is 1, this directive serves as a command which specifies to the compiler that the loop is not to be unrolled. The compiler takes advantage of this information at optimization level of 3 or above.

The scope of this pragma begins with the pragma and ends with which ever of the following occurs first: the beginning of the next block, the next for loop within the current block, the end of the current block. The pragma applies to the next for loop prior to the end of the pragmas scope.

2.8.26 warn_missing_parameter_info

`#pragma [no_]warn_missing_parameter_info`

When you specify `#pragma warn_missing_parameter_info`, the compiler issues a warning for a function call whose function declaration contains no parameter type information. Consider the following example:

```
example% cat -n t.c
  1 #pragma warn_missing_parameter_info
  2
  3 int foo();
  4
  5 int bar () {
  6
  7     int i;
  8
  9     i = foo(i);
 10
 11     return i;
 12 }
% cc t.c -c -errtags
"t.c", line 9: warning: function foo has no prototype
(E_NO_MISSED_PARAMS_ALLOWED)
example%
```

`#pragma no_warn_missing_parameter_info` turns off the effect of any previous `#pragma warn_missing_parameter_info`.

By default, `#pragma no_warn_missing_parameter_info` is in effect.

2.8.27 weak

```
#pragma weak symbol1 [= symbol2]
```

Defines a weak global symbol. This pragma is used mainly in source files for building libraries. The linker does not produce an error message if it is unable to resolve a weak symbol.

```
#pragma weak symbol
```

defines *symbol* to be a weak symbol. The linker does not produce an error message if it does not find a definition for *symbol*.

```
#pragma weak symbol1 = symbol2
```

defines *symbol1* to be a weak symbol, which is an alias for the symbol *symbol2*. This form of the pragma can only be used in the same translation unit where *symbol2* is defined, either in the sourcefiles or one of its included headerfiles. Otherwise, a compilation error will result.

If your program calls but does not define *symbol1*, and *symbol1* is a weak symbol in a library being linked, the linker uses the definition from that library. However, if your program defines its own version of *symbol1*, then the program's definition is used and the weak global definition of *symbol1* in the library is not used. If the program directly calls *symbol2*, the definition from the library is used; a duplicate definition of *symbol2* causes an error.

2.9 Predefined Names

The following identifier is predefined as an object-like macro:

TABLE 2-3 Predefined Identifier

Identifier	Description
__STDC__	__STDC__ 1 -Xc __STDC__ 0 -Xa, -Xt Not defined -Xs

The compiler issues a warning if __STDC__ is undefined (#undef __STDC__).
__STDC__ is not defined in -Xs mode.

Predefinitions (not valid in `-xc` mode):

- `sun`
- `unix`
- `sparc` (*SPARC*)
- `i386` (*x86*)

The following predefinitions are valid in all modes:

- `__sun`
- `__unix`
- `__SUNPRO_C=0x580`
- `__`uname -s`_`uname -r`` (example: `__SunOS_5_7`)
- `__sparc` (*SPARC*)
- `__i386` (*x86*)
- `__BUILTIN_VA_ARG_INCR`
- `__SVR4`
- `__sparcv9` (`-Xarch=v9, v9a`)

The compiler also predefines the object-like macro `__PRAGMA_REDEFINE_EXTNAME` to indicate that the pragma will be recognized. The following is predefined in `-xa` and `-xt` modes only:

`__RESTRICT`

2.10 The Value of `errno`

If you specify `-fast`, you should not rely on the value of `errno` because the value can change as a result of code optimization. The easiest way to avoid this problem is to not specify `-fast`.

If, however, you specify `-fast` and you are relying on the value of `errno`, do the following:

- Do not link with the math optimization library by specifying `-lmopt`.
- Specify `-xbuiltin=none`, `-U__MATHERR_ERRNO_DONTCARE`, `-xnolibmopt`, and `-xnolibmil`.

2.11 `_Restrict` Keyword

The C compiler supports the `_Restrict` keyword as an equivalent to the `restrict` keyword in the C99 standard. The `_Restrict` keyword is available with `-xc99=none` and `-xc99=all`, whereas the `restrict` keyword is only available with `-xc99=all`.

For more information on supported C99 features, see [Appendix D](#).

2.12 `__asm` Keyword

The `__asm` keyword (note the initial double-underscore) is a synonym for the `asm` keyword. If you use `asm`, rather than `__asm`, and compile in `-Xc` mode, the compiler issues a warning. The compiler does not issue a warning if you use `__asm` in `-Xc` mode. The `__asm` statement has the form:

```
__asm( "string" );
```

where *string* is a valid assembly language statement. The `__asm` statements must appear within function bodies.

2.13 Environment Variables

This section lists the environment variables that let you control the compilation and runtime environment.

2.13.1 `OMP_DYNAMIC`

Enable or disable dynamic adjustment of the number of threads.

2.13.2 OMP_NESTED

Enable or disable nested parallelism.

2.13.3 OMP_NUM_THREADS

Set the number of threads to use during execution.

2.13.4 OMP_SCHEDULE

Set the run-time schedule type and chunk size.

2.13.5 PARALLEL

(SPARC) Specifies the number of processors available to the program for multiprocessor execution. If the target machine has multiple processors, the threads can map to independent processors. Running the program leads to the creation of two threads that execute the parallelized portions of the program.

2.13.6 SUN_PROFDATA

Controls the name of the file in which the `-xprofile=collect` command stores execution-frequency data.

2.13.7 SUN_PROFDATA_DIR

Controls in which directory the `-xprofile=collect` command places the execution-frequency data-file.

2.13.8 SUNPRO_SB_INIT_FILE_NAME

The absolute path name of the directory containing the `.sbinit(5)` file. This variable is used only if the `-xsb` or `-xsbfast` flag is used.

2.13.9 SUNW_MP_THR_IDLE

Controls end-of-task status of each helper thread and can be set to `spin ns`, or `sleep nms`. The default is `sleep`. See the *OpenMP API User's Guide* for details.

2.13.10 TMPDIR

`cc` normally creates temporary files in the directory `/tmp`. You can specify another directory by setting the environment variable `TMPDIR` to the directory of your choice. However, if `TMPDIR` is not a valid directory, `cc` uses `/tmp`. The `-xtemp` option has precedence over the `TMPDIR` environment variable.

If you use a Bourne shell, type:

```
$ TMPDIR=dir; export TMPDIR
```

If you use a C shell, type:

```
% setenv TMPDIR dir
```

2.14 How to Specify Include Files

To include any of the standard header files supplied with the C compilation system, use this format:

```
#include <stdio.h>
```

The angle brackets (`<>`) cause the preprocessor to search for the header file in the standard place for header files on your system, usually the `/usr/include` directory.

The format is different for header files that you have stored in your own directories:

```
#include "header.h"
```

For statements of the form `#include "foo.h"` (where quotation marks are used), the compiler searches for include files in the following order:

1. The current directory (that is, the directory containing the “including” file)
2. The directories named with `-I` options, if any
3. The `/usr/include` directory

If your header file is not in the same directory as the source files that include it, specify the path of the directory in which it is stored with the `-I` option to `cc`. Suppose, for instance, that you have included both `stdio.h` and `header.h` in the source file `mycode.c`:

```
#include <stdio.h>
#include "header.h"
```

Suppose further that `header.h` is stored in the directory `../defs`. The command:

```
% cc -I../defs mycode.c
```

directs the preprocessor to search for `header.h` first in the directory containing `mycode.c`, then in the directory `../defs`, and finally in the standard place. It also directs the preprocessor to search for `stdio.h` first in `../defs`, then in the standard place. The difference is that the current directory is searched only for header files whose names you have enclosed in quotation marks.

You can specify the `-I` option more than once on the `cc` command-line. The preprocessor searches the specified directories in the order they appear. You can specify multiple options to `cc` on the same command-line:

```
% cc -o prog -I../defs mycode.c
```

2.14.1 Using the `-I-` Option to Change the Search Algorithm

The new `-I-` option gives more control over the default search rules. Only the first `-I-` option on the command line works as described in this section. When `-I-` appears in the command line:

For include files of the form `#include "foo.h"`, search the directories in the following order:

1. The directories named with `-I` options (both before and after `-I-`).

2. The directories for compiler-provided C++ header files, ANSI C header files, and special-purpose files.
3. The `/usr/include` directory.

For include files of the form `#include <foo.h>`, search the directories in the following order:

1. The directories named in the `-I` options that appear after `-I-`.
2. The directories for compiler-provided C++ header files, ANSI C header files, and special-purpose files.
3. The `/usr/include` directory.

The following example shows the results of using `-I-` when compiling `prog.c`.

<code>prog.c</code>	<pre>#include "a.h" #include <b.h> #include "c.h"</pre>
<code>c.h</code>	<pre>#ifndef _C_H_1 #define _C_H_1 int c1; #endif</pre>
<code>inc/a.h</code>	<pre>#ifndef _A_H #define _A_H #include "c.h" int a; #endif</pre>
<code>inc/b.h</code>	<pre>#ifndef _B_H #define _B_H #include <c.h> int b; #endif</pre>
<code>inc/c.h</code>	<pre>#ifndef _C_H_2 #define _C_H_2 int c2; #endif</pre>

The following command shows the default behavior of searching the current directory (the directory of the including file) for include statements of the form `#include "foo.h"`. When processing the `#include "c.h"` statement in `inc/a.h`, the preprocessor includes the `c.h` header file from the `inc` subdirectory. When

processing the `#include "c.h"` statement in `prog.c`, the preprocessor includes the `c.h` file from the directory containing `prog.c`. Note that the `-H` option instructs the compiler to print the paths of the included files.

```
example% cc -c -Iinc -H prog.c
inc/a.h
           inc/c.h
inc/b.h
           inc/c.h
c.h
```

The next command shows the effect of the `-I-` option. The preprocessor does not look in the including directory first when it processes statements of the form `#include "foo.h"`. Instead, it searches the directories named by the `-I` options in the order that they appear in the command line. When processing the `#include "c.h"` statement in `inc/a.h`, the preprocessor includes the `./c.h` header file instead of the `inc/c.h` header file.

```
example% cc -c -I. -I- -Iinc -H prog.c
inc/a.h
           ./c.h
inc/b.h
           inc/c.h
./c.h
```

Warnings

Never specify the compiler installation area, `/usr/include`, `/lib`, or `/usr/lib`, as search directories.

For more information, see [Section B.2.33, “-I\[- | dir\]”](#) on page B-18.

Parallelizing Sun C Code

The Sun C compiler can optimize code to run on SPARC shared-memory multiprocessor machines. The process is called *parallelizing*. The compiled code can execute in parallel using the multiple processors on the system. This chapter explains how you can take advantage of the compiler's parallelizing features.

3.1 Overview

The C compiler generates parallel code for those loops that it determines are safe to parallelize. Typically, these loops have iterations that are independent of each other. For such loops, it does not matter in what order the iterations are executed or if they are executed in parallel. Many, though not all, vector loops fall into this category.

Because of the way aliasing works in C, it is difficult to determine the safety of parallelization. To help the compiler, Sun C offers pragmas and additional pointer qualifications to provide aliasing information known to the programmer that the compiler cannot determine. See [Section , "Type-Based Alias Analysis" on page 5-1](#) for more information.

3.1.1 Example of Use

The following example illustrates how to enable and control parallelized C:

```
% cc -fast -xO4 -xautopar example.c -o example
```

This generates an executable called `example`, which can be executed normally. If you wish to take advantage of multiprocessor execution, see [Section B.2.67, "-xautopar" on page B-36](#).

3.2 Parallelizing for OpenMP

You can compile your code so that it complies with the OpenMP specification. For more information on the OpenMP specification for C, visit the web site at <http://www.openmp.org/specs/>.

To take advantage of the compiler's OpenMP support, you need to issue the compiler's `-xopenmp` option. See [Section B.2.112, “-xopenmp\[=i\]” on page B-70](#).

See the *OpenMP API User's Guide* for migration information to the directives of the standard.

3.2.1 Handling OpenMP Runtime Warnings

The OpenMP runtime system can issue warnings for non-fatal errors. Use the following function to register a call back function to handle these warnings:

```
int sunw_mp_register_warn(void (*func) (void *) )
```

You can access the prototype for this function by issuing a `#include` preprocessor directive for `<sunw_mp_misc.h>`.

If you do not want to register a function, set the environment variable `SUNW_MP_WARN` to `TRUE` and the warning messages are sent to `stderr`. For more information on `SUNW_MP_WARN`, see [Section , “SUNW_MP_WARN” on page 3-4](#).

For information specific to this implementation of OpenMP, see the *OpenMP API User's Guide*.

3.3 Environment Variables

There are four environment variables that relate to parallelized C:

- `PARALLEL`
- `SUNW_MP_THR_IDLE`
- `SUNW_MP_WARN`
- `STACKSIZE`

PARALLEL

Set the `PARALLEL` environment variable if you can take advantage of multiprocessor execution. The `PARALLEL` environment variable specifies the number of processors available to the program. The following example shows that `PARALLEL` is set to two:

```
% setenv PARALLEL 2
```

If the target machine has multiple processors, the threads can map to independent processors. Running the program leads to the creation of two threads that execute the parallelized portions of the program.

SUNW_MP_THR_IDLE

Currently, the starting thread of a program creates bound threads. Once created, these bound threads participate in executing the parallel part of a program (parallel loop, parallel region, etc.) and keep spin-waiting while the sequential part of the program runs. These bound threads never sleep or stop until the program terminates. Having these threads spin-wait generally gives the best performance when a parallelized program runs on a dedicated system. However, threads that are spin-waiting use system resources.

Use the `SUNW_MP_THR_IDLE` environment variable to control the status of each thread after it finishes its share of a parallel job.

```
% setenv SUNW_MP_THR_IDLE value
```

You can substitute either `spin` or `sleep[n s | n ms]` for *value*. The default is `spin`, which means the thread should spin (or busy-wait) after completing a parallel task, until a new parallel task arrives.

The other choice, `sleep[n s | n ms]` puts the thread to sleep after spin-waiting *n* units. The wait unit can be seconds (*s*, the default unit) or milliseconds (*ms*), where 1s means one second, and 10ms means ten milliseconds. `sleep` with no arguments puts the thread to sleep immediately after completing a parallel task. `sleep`, `sleep0`, `sleep0s`, and `sleep0ms` are all equivalent.

If a new job arrives before *n* units is reached, the thread stops spin-waiting and starts doing the new job. If `SUNW_MP_THR_IDLE` contains an illegal value or isn't set, `spin` is used as the default.

SUNW_MP_WARN

Set this environment variable to `TRUE` to print warning messages from OpenMP and other parallelization runtime-systems.

```
% setenv SUNW_MP_WARN TRUE
```

If you registered a function by using `sunw_mp_register_warn()` to handle warning messages, then `SUNW_MP_WARN` prints no warning messages, even if you set it to `TRUE`. If you did not register a function and set `SUNW_MP_WARN` to `TRUE`, `SUNW_MP_WARN` prints the warning messages to `stderr`. If you do not register a function and you do not set `SUNW_MP_WARN`, no warning messages are issued. For more information on `sunw_mp_register_warn()` see [Section 3.2.1, “Handling OpenMP Runtime Warnings”](#) on page 3-2.

STACKSIZE

The executing program maintains a main memory stack for the master thread and distinct stacks for each slave thread. Stacks are temporary memory address spaces used to hold arguments and automatic variables over subprogram invocations.

The default size of the main stack is about eight megabytes. Use the `limit` command to display the current main stack size as well as set it.

```
% limit  
cputime unlimited  
filesize unlimited  
datasize 2097148 kbytes  
stacksize 8192 kbytes <- current main stack size  
coredumpsize 0 kbytes  
descriptors 256  
memorysize unlimited  
% limit stacksize 65536 <- set main stack to 64Mb
```

Each slave thread of a multithreaded program has its own thread stack. This stack mimics the main stack of the master thread but is unique to the thread. The thread’s private arrays and variables (local to the thread) are allocated on the thread stack.

All slave threads have the same stack size, which is four megabytes for 32-bit applications and eight megabytes for 64-bit applications by default. The size is set with the `STACKSIZE` environment variable:

```
% setenv STACKSIZE 16483 <- Set thread stack size to 16 Mb
```

Setting the thread stack size to a value larger than the default may be necessary for some parallelized code.

Sometimes the compiler may generate a warning message that indicates a bigger stack size is needed. However, it may not be possible to know just how large to set it, except by trial and error, especially if private/local arrays are involved. If the stack size is too small for a thread to run, the program will abort with a segmentation fault.

3.3.0.1 Keyword

The keyword `restrict` can be used with parallelized C. The proper use of the keyword `restrict` helps the optimizer in understanding the aliasing of data required to determine if a code sequence can be parallelized. Refer to [Section D.1.2, “C99 Keywords” on page D-3](#) for details.

3.4 Data Dependence and Interference

The C compiler performs analysis on loops in programs to determine if it is safe to execute different iterations of the loops in parallel. The purpose of this analysis is to determine if any two iterations of the loop could interfere with each other. Typically this happens if one iteration of a variable could read a variable while another iteration is writing the very same variable. Consider the following program fragment:

CODE EXAMPLE 3-1 A Loop With Dependence

```
for (i=1; i < 1000; i++) {  
    sum = sum + a[i]; /* S1 */  
}
```

In [CODE EXAMPLE 3-1](#) any two successive iterations, `i` and `i+1`, will write and read the same variable `sum`. Therefore, in order for these two iterations to execute in parallel some form of locking on the variable would be required. Otherwise it is not safe to allow the two iterations to execute in parallel.

However, the use of locks imposes overhead that might slowdown the program. The C compiler will not ordinarily parallelize the loop in [CODE EXAMPLE 3-1](#). In [CODE EXAMPLE 3-1](#) there is a data dependence between two iterations of the loop. Consider another example:

CODE EXAMPLE 3-2 A Loop Without Dependence

```
for (i=1; i < 1000; i++) {  
    a[i] = 2 * a[i]; /* S1 */  
}
```

In this case each iteration of the loop references a different array element. Therefore different iterations of the loop can be executed in any order. They may be executed in parallel without any locks because no two data elements of different iterations can possibly interfere.

The analysis performed by the compiler to determine if two different iterations of a loop could reference the same variable is called data dependence analysis. Data dependences prevent loop parallelization if one of the references writes to the variable. The dependence analysis performed by the compiler can have three outcomes:

- There is a dependence. In this case, it is not safe to execute the loop in parallel. [CODE EXAMPLE 3-1](#) illustrates this case.
- There is no dependence. The loop may safely execute in parallel using an arbitrary number of processors. [CODE EXAMPLE 3-2](#) illustrates this case.
- The dependence cannot be determined. The compiler assumes, for safety, that there might be a dependence that prevents parallel execution of the loop and will not parallelize the loop.

In [CODE EXAMPLE 3-3](#), whether or not two iterations of the loop write to the same element of array `a` depends on whether or not array `b` contains duplicate elements. Unless the compiler can determine this fact, it assumes there is a dependence and does not parallelize the loop.

CODE EXAMPLE 3-3 A Loop That May or May Not Contain Dependencies

```
for (i=1; i < 1000; i++) {  
    a[b[i]] = 2 * a[i];  
}
```

3.4.1 Parallel Execution Model

The parallel execution of loops is performed by Solaris threads. The thread starting the initial execution of the program is called the master thread. At program start-up the master thread creates multiple slave threads as shown in the following figure. At the end of the program all the slave threads are terminated. Slave thread creation is performed exactly once to minimize the overhead.




FIGURE 3-1 Master and Slave Threads

After start-up, the master thread starts the execution of the program while slave threads wait idly. When the master thread encounters a parallel loop, different iterations of the loop are distributed among the slave and master threads which start the execution of the loop. After each thread finishes execution of its chunk it synchronizes with the remaining threads. This synchronization point is called a *barrier*. The master thread cannot continue executing the remainder of the program until all the threads have finished their work and reached the barrier. The slave threads go into a wait state after the barrier waiting for more parallel work, and the master thread continues to execute the program.

During this process, various overheads can occur:

- The overhead of synchronization and work distribution
- The overhead of barrier synchronization

In general, there may be some parallel loops for which the amount of useful work performed is not enough to justify the overhead. For such loops, there may be appreciable slowdown. In the following figure, a loop is parallelized. However the barriers, represented by horizontal bars, introduce significant overhead. The work between the barriers is performed serially or in parallel as indicated. The amount of time required to execute the loop in parallel is considerably less than the amount of time required to synchronize the master and slave threads at the barriers.




FIGURE 3-2 Parallel Execution of a Loop

3.4.2 Private Scalars and Private Arrays

There are some data dependences for which the compiler may still be able to parallelize a loop. Consider the following example.

CODE EXAMPLE 3-4 A Parallelizable Loop With Dependence

```
for (i=1; i < 1000; i++) {
    t = 2 * a[i];          /* S1 */
    b[i] = t;             /* S2 */
}
```

In this example, assuming that arrays *a* and *b* are non-overlapping arrays, there appears to be a data dependence in any two iterations due to the variable *t*. The following statements execute during iterations one and two.

CODE EXAMPLE 3-5 Iterations One and Two

```
t = 2*a[1]; /* 1 */
b[1] = t; /* 2 */
t = 2*a[2]; /* 3 */
b[2] = t; /* 4 */
```

Because statements one and three modify the variable *t*, the compiler cannot execute them in parallel. However, the value of *t* is always computed and used in the same iteration so the compiler can use a separate copy of *t* for each iteration. This

eliminates the interference between different iterations due to such variables. In effect, we have made variable `t` as a private variable for each thread executing that iteration. This can be illustrated as follows:

CODE EXAMPLE 3-6 Variable `t` as a Private Variable for Each Thread

```
for (i=1; i < 1000; i++) {
    pt[i] = 2 * a[i];          /* S1 */
    b[i] = pt[i];            /* S2 */
}
```

[CODE EXAMPLE 3-6](#) is essentially the same example as [CODE EXAMPLE 3-3](#), but each scalar variable reference `t` is now replaced by an array reference `pt`. Each iteration now uses a different element of `pt`, and this results in eliminating any data dependencies between any two iterations. Of course one problem with this illustration is that it may lead to an extra large array. In practice, the compiler only allocates one copy of the variable for each thread that participates in the execution of the loop. Each such variable is, in effect, private to the thread.

The compiler can also privatize array variables to create opportunities for parallel execution of loops. Consider the following example:

CODE EXAMPLE 3-7 A Parallelizable Loop With an Array Variable

```
for (i=1; i < 1000; i++) {
    for (j=1; j < 1000; j++) {
        x[j] = 2 * a[i];      /* S1 */
        b[i][j] = x[j];     /* S2 */
    }
}
```

In [CODE EXAMPLE 3-7](#), different iterations of the outer loop modify the same elements of array `x`, and thus the outer loop cannot be parallelized. However, if each thread executing the outer loop iterations has a private copy of the entire array `x`, then there would be no interference between any two iterations of the outer loop. This is illustrated as follows:

CODE EXAMPLE 3-8 A Parallelizable Loop Using a Privatized Array

```
for (i=1; i < 1000; i++) {
    for (j=1; j < 1000; j++) {
        px[i][j] = 2 * a[i]; /* S1 */
        b[i][j] = px[i][j]; /* S2 */
    }
}
```

As in the case of private scalars, it is not necessary to expand the array for all the iterations, but only up to the number of threads executing in the systems. This is done automatically by the compiler by allocating one copy of the original array in the private space of each thread.

3.4.3 Storeback

Privatization of variables can be very useful for improving the parallelism in the program. However, if the private variable is referenced outside the loop then the compiler needs to assure that it has the right value. Consider the following example:

CODE EXAMPLE 3-9 A Parallelized Loop Using Storeback

```
for (i=1; i < 1000; i++) {  
    t = 2 * a[i];           /* S1 */  
    b[i] = t;              /* S2 */  
}  
x = t;                     /* S3 */
```

In [CODE EXAMPLE 3-9](#) the value of `t` referenced in statement S3 is the final value of `t` computed by the loop. After the variable `t` has been privatized and the loop has finished executing, the right value of `t` needs to be stored back into the original variable. This is called storeback. This is done by copying the value of `t` on the final iteration back to the original location of variable `t`. In many cases the compiler can do this automatically. But there are situations where the last value cannot be computed so easily:

CODE EXAMPLE 3-10 A Loop That Cannot Use Storeback

```
for (i=1; i < 1000; i++) {  
    if (c[i] > x[i] ) {     /* C1 */  
        t = 2 * a[i];      /* S1 */  
        b[i] = t;         /* S2 */  
    }  
}  
x = t*t;                   /* S3 */
```

For correct execution, the value of `t` in statement S3 is not, in general, the value of `t` on the final iteration of the loop. It is in fact the last iteration for which the condition C1 is true. Computing the final value of `t` is quite hard in the general cases. In cases like this the compiler will not parallelize the loop.

3.4.4 Reduction Variables

There are cases when there is a real dependence between iterations of a loop and the variables causing the dependence cannot simply be privatized. This can arise, for example, when values are being accumulated from one iteration to the next.

CODE EXAMPLE 3-11 A Loop That May or May Not Be Parallelized

```
for (i=1; i < 1000; i++) {  
    sum += a[i]*b[i]; /* S1 */  
}
```

In [CODE EXAMPLE 3-11](#), the loop computes the vector product of two arrays into a common variable called `sum`. This loop cannot be parallelized in a simple manner. The compiler can take advantage of the associative nature of the computation in statement S1 and allocate a private variable called `psum[i]` for each thread. Each copy of the variable `psum[i]` is initialized to 0. Each thread computes its own partial sum in its own copy of the variable `psum[i]`. Before crossing the barrier, all the partial sums are added onto the original variable `sum`. In this example, the variable `sum` is called a reduction variable because it computes a sum-reduction. However, one danger of promoting scalar variables to reduction variables is that the manner in which rounded values are accumulated can change the final value of `sum`. The compiler performs this transformation only if you specifically give permission for it to do so.

3.5 Speedups

If the compiler does not parallelize a portion of a program where a significant amount of time is spent, then no speedup occurs. This is basically a consequence of Amdahl's Law. For example, if a loop that accounts for five percent of the execution time of a program is parallelized, then the overall speedup is limited to five percent. However, there may not be any improvement depending on the size of the workload and parallel execution overheads.

As a general rule, the larger the fraction of program execution that is parallelized, the greater the likelihood of a speedup.

Each parallel loop incurs a small overhead during start-up and shutdown. The start overhead includes the cost of work distribution, and the shutdown overhead includes the cost of the barrier synchronization. If the total amount of work performed by the loop is not big enough then no speedup will occur. In fact the loop might even slow down. So if a large amount of program execution is accounted by a large number of short parallel loops, then the whole program may slow down instead of speeding up.

The compiler performs several loop transformations that try to increase the granularity of the loops. Some of these transformations are loop interchange and loop fusion. So in general, if the amount of parallelism in a program is small or is fragmented among small parallel regions, then the speedup is less.

Often scaling up a problem size improves the fraction of parallelism in a program. For example, consider a problem that consists of two parts: a quadratic part that is sequential, and a cubic part that is parallelizable. For this problem the parallel part of the workload grows faster than the sequential part. So at some point the problem will speedup nicely, unless it runs into resource limitations.

It is beneficial to try some tuning, experimentation with directives, problem sizes and program restructuring in order to achieve benefits from parallel C.

3.5.1 Amdahl's Law

Fixed problem-size speedup is generally governed by Amdahl's law. Amdahl's Law simply says that the amount of parallel speedup in a given problem is limited by the sequential portion of the problem. The following equation describes the speedup of a problem where F is the fraction of time spent in sequential region, and the remaining fraction of the time is spent uniformly among P processors. If the second term of the equation drops to zero, the total speedup is bounded by the first term, which remains fixed.

$$\frac{1}{S} = F + \frac{(1-F)}{P}$$

The following figure illustrates this concept diagrammatically. The darkly shaded portion represents the sequential part of the program, and remains constant for one, two, four, and eight processors, while the lightly shaded portion represents the parallel portion of the program that can be divided uniformly among an arbitrary number of processors.




FIGURE 3-3 Fixed Problem Speedups

In reality, however, you may incur overheads due to communication and distribution of work to multiple processors. These overheads may or may not be fixed for arbitrary number of processors used.

FIGURE 3-4 illustrates the ideal speedups for a program containing 0%, 2%, 5%, and 10% sequential portions. Here, no overhead is assumed.




FIGURE 3-4 Amdahl's Law Speedup Curve

3.5.1.1 Overheads

Once the overheads are incorporated in the model the speedup curves change dramatically. Just for the purposes of illustration we assume that overheads consist of two parts: a fixed part which is independent of the number of processors, and a non-fixed part that grows quadratically with the number of the processors used:

$$\frac{1}{S} = \frac{1}{F + \left(1 - \frac{F}{P}\right) + K_1 + K_2 P^2}$$

In this equation, K_1 and K_2 are some fixed factors. Under these assumptions the speedup curve is shown in the following figure. It is interesting to note that in this case the speedups peak out. After a certain point adding more processors is detrimental to performance as shown in the following figure.




FIGURE 3-5 Speedup Curve With Overheads

3.5.1.2 Gustafson's Law

Amdahls Law can be misleading for predicting parallel speedups in real problems. The fraction of time spent in sequential sections of the program sometimes depends on the problem size. That is, by scaling the problem size, you may improve the chances of speedup. The following example demonstrates this.

CODE EXAMPLE 3-12 Scaling the Problem Size May Improve Chances of Speedup

```

/*
 * initialize the arrays
 */
for (i=0; i < n; i++) {
    for (j=0; j < n; j++) {
        a[i][j] = 0.0;
        b[i][j] = ...
        c[i][j] = ...
    }
}
/*
 * matrix multiply
 */
for (i=0; i < n; i++) {
    for(j=0; j < n; j++) {
        for (k=0; k < n; k++) {
            a[i][j] = b[i][k]*c[k][j];
        }
    }
}

```

Assume an ideal overhead of zero and assume that only the second loop nest is executed in parallel. It is easy to see that for small problem sizes (i.e. small values of n), the sequential and parallel parts of the program are not so far from each other. However, as n grows larger, the time spent in the parallel part of the program grows faster than the time spent in the sequential part. For this problem, it is beneficial to increase the number of processors as the problem size increases.

3.6 Load Balance and Loop Scheduling

Loop scheduling is the process of distributing iterations of a parallel loop to multiple threads. In order to maximize the speedup, it is important that the work be distributed evenly among the threads while not imposing too much overhead. The compiler offers several types of scheduling for different situations.

3.6.1 Static or Chunk Scheduling

It is beneficial to divide the work evenly among the different threads on the system when the work performed by different iterations of a loop is the same. This approach is known as static scheduling.

CODE EXAMPLE 3-13 A Good Loop for Static Scheduling

```
for (i=1; i < 1000; i++) {  
    sum += a[i]*b[i];      /* S1 */  
}
```

Under static or chunk scheduling, each thread will get the same number of iterations. If there were 4 threads, then in the above example, each thread will get 250 iterations. Provided there are no interruptions and each thread progresses at the same rate, all the threads will complete at the same time.

3.6.2 Self Scheduling

Static scheduling will not achieve good load balance, in general, when the work performed by each iteration varies. In static scheduling, each thread grabs the same chunk of iterations. Each thread, except the master thread, upon completion of its chunk waits to participate in the next parallel loop execution. The master thread continues execution of the program. In self scheduling, each thread grabs a different small chunk of iteration and after completion of its assigned chunk, tries to acquire more chunks from the same loop.

3.6.3 Guided Self Scheduling

In guided self scheduling (GSS), each thread gets successively smaller number of chunks. In cases where the size of each iteration varies, GSS can help balance the load.

3.7 Loop Transformations

The compiler performs several loop restructuring transformations to help improve the parallelization of a loop in programs. Some of these transformations can also improve the single processor execution of loops as well. The transformations performed by the compiler are described below.

3.7.1 Loop Distribution

Often loops contain a few statements that cannot be executed in parallel and many statements that can be executed in parallel. Loop Distribution attempts to remove the sequential statements into a separate loop and gather the parallelizable statements into a different loop. This is illustrated in the following example:

CODE EXAMPLE 3-14 A Candidate for Loop Distribution

```
for (i=0; i < n; i++) {  
    x[i] = y[i] + z[i]*w[i];           /* S1 */  
    a[i+1] = (a[i-1] + a[i] + a[i+1])/3.0; /* S2 */  
    y[i] = z[i] - x[i];               /* S3 */  
}
```

Assuming that arrays *x*, *y*, *w*, *a*, and *z* do not overlap, statements S1 and S3 can be parallelized but statement S2 cannot be. Here is how the loop looks after it is split or distributed into two different loops:

CODE EXAMPLE 3-15 The Distributed Loop

```
/* L1: parallel loop */
for (i=0; i < n; i++) {
    x[i] = y[i] + z[i]*w[i];          /* S1 */
    y[i] = z[i] - x[i];              /* S3 */
}
/* L2: sequential loop */
for (i=0; i < n; i++) {
    a[i+1] = (a[i-1] + a[i] + a[i+1])/3.0; /* S2 */
}
```

After this transformation, loop L1 does not contain any statements that prevent the parallelization of the loop and may be executed in parallel. Loop L2, however, still has a non-parallelizable statement from the original loop.

Loop distribution is not always profitable or safe to perform. The compiler performs analysis to determine the safety and profitability of distribution.

3.7.2 Loop Fusion

If the granularity of a loop, or the work performed by a loop, is small, the performance gain from distribution may be insignificant. This is because the overhead of parallel loop start-up is too high compared to the loop workload. In such situations, the compiler uses loop fusion to combine several loops into a single parallel loop, and thus increase the granularity of the loop. Loop fusion is easy and safe when loops with identical trip counts are adjacent to each other. Consider the following example:

CODE EXAMPLE 3-16 Loops With Small Work Loads

```
/* L1: short parallel loop */
for (i=0; i < 100; i++) {
    a[i] = a[i] + b[i];          /* S1 */
}
/* L2: another short parallel loop */
for (i=0; i < 100; i++) {
    b[i] = a[i] * d[i];          /* S2 */
}
```

The two short parallel loops are next to each other, and can be safely combined as follows:

CODE EXAMPLE 3-17 The Two Loops Fused

```
/* L3: a larger parallel loop */
for (i=0; i < 100; i++) {
    a[i] = a[i] + b[i];      /* S1 */
    b[i] = a[i] * d[i];     /* S2 */
}
```

The new loop generates half the parallel loop execution overhead. Loop fusion can also help in other ways. For example if the same data is referenced in two loops, then combining them can improve the locality of reference.

However, loop fusion is not always safe to perform. If loop fusion creates a data dependence that did not exist before then the fusion may result in incorrect execution. Consider the following example:

CODE EXAMPLE 3-18 Unsafe Fusion Candidates

```
/* L1: short parallel loop */
for (i=0; i < 100; i++) {
    a[i] = a[i] + b[i];      /* S1 */
}
/* L2: a short loop with data dependence */
for (i=0; i < 100; i++) {
    a[i+1] = a[i] * d[i];   /* S2 */
}
```

If the loops in [CODE EXAMPLE 3-18](#) are fused, a data dependence is created from statement S2 to S1. In effect, the value of `a[i]` in the right hand side of statement S1 is computed in statement S2. If the loops are not fused, this would not happen. The compiler performs safety and profitability analysis to determine if loop fusion should be done. Often, the compiler can fuse an arbitrary number of loops. Increasing the granularity in this manner can sometimes push a loop far enough up for it to be profitable for parallelization.

3.7.3 Loop Interchange

It is generally more profitable to parallelize the outermost loop in a nest of loops, since the overheads incurred are small. However, it is not always safe to parallelize the outermost loops due to dependences that might be carried by such loops. This is illustrated in the following:

CODE EXAMPLE 3-19 Nested Loop That Cannot Be Parallelized

```
for (i=0; i <n; i++) {
    for (j=0; j <n; j++) {
        a[j][i+1] = 2.0*a[j][i-1];
    }
}
```

In this example, the loop with the index variable *i* cannot be parallelized, because of a dependency between two successive iterations of the loop. The two loops can be interchanged and the parallel loop (the *j*-loop) becomes the outer loop:

CODE EXAMPLE 3-20 The Loops Interchanged

```
for (j=0; j<n; j++) {
    for (i=0; i<n; i++) {
        a[j][i+1] = 2.0*a[j][i-1];
    }
}
```

The resulting loop incurs an overhead of parallel work distribution only once, while previously, the overhead was incurred *n* times. The compiler performs safety and profitability analysis to determine whether to perform loop interchange.

3.8 Aliasing and Parallelization

ISO C aliasing can often prevent loops from getting parallelized. Aliasing occurs when there are two possible references to the same memory location. Consider the following example:

CODE EXAMPLE 3-21 A Loop With Two References to the Same Memory Location

```
void copy(float a[], float b[], int n) {
    int i;
    for (i=0; i < n; i++) {
        a[i] = b[i]; /* S1 */
    }
}
```

Since variables `a` and `b` are parameters, it is possible that `a` and `b` may be pointing to overlapping regions of memory; e.g, if `copy` were called as follows:

```
copy (x[10], x[11], 20);
```

In the called routine, two successive iterations of the copy loop may be reading and writing the same element of the array `x`. However, if the routine `copy` were called as follows then there is no possibility of overlap in any of the 20 iterations of the loop:

```
copy (x[10], x[40], 20);
```

In general, it is not possible for the compiler to analyze this situation correctly without knowing how the routine is called. The compiler provides a keyword extension to ISO C that lets you convey this kind of aliasing information. See [Section 3.8.2, “Restricted Pointers” on page 3-21](#) for more information.

3.8.1 Array and Pointer References

Part of the aliasing problem is that the C language can define array referencing and definition through pointer arithmetic. In order for the compiler to effectively parallelize loops, either automatically or explicitly with pragmas, all data that is laid out as an array must be referenced using C array reference syntax and not pointers. If pointer syntax is used, the compiler cannot determine the relationship of the data between different iterations of a loop. Thus it will be conservative and not parallelize the loop.

3.8.2 Restricted Pointers

In order for a compiler to effectively perform parallel execution of a loop, it needs to determine if certain lvalues designate distinct regions of storage. Aliases are lvalues whose regions of storage are not distinct. Determining if two pointers to objects are aliases is a difficult and time consuming process because it could require analysis of the entire program. Consider function `vsq()` below:

CODE EXAMPLE 3-22 A Loop With Two Pointers

```
void vsq(int n, double * a, double * b) {
    int i;
    for (i=0; i<n; i++) {
        b[i] = a[i] * a[i];
    }
}
```

The compiler can parallelize the execution of the different iterations of the loops if it knows that pointers `a` and `b` access different objects. If there is an overlap in objects accessed through pointers `a` and `b` then it would be unsafe for the compiler to execute the loops in parallel. At compile time, the compiler does not know if the objects accessed by `a` and `b` overlap by simply analyzing the function `vsq()`; the compiler may need to analyze the whole program to get this information.

Restricted pointers are used to specify pointers which designate distinct objects so that the compiler can perform pointer alias analysis. The following is an example of function `vsq()` in which function parameters are declared as restricted pointers:

```
void vsq(int n, double * restrict a, double * restrict b)
```

Pointers `a` and `b` are declared as restricted pointers, so the compiler knows that `a` and `b` point to distinct regions of storage. With this alias information, the compiler is able to parallelize the loop.

The keyword `restrict` is a type-qualifier, like `volatile`, and it shall only qualify pointer types. `restrict` is recognized as a keyword when you use `-xc99=all` (except with `-Xs`). There are situations in which you may not want to change the source code. You can specify that pointer-valued function-parameters be treated as restricted pointers by using the following command line option:

```
-xrestrict=[func1, ..., funcn]
```

If a function list is specified, then pointer parameters in the specified functions are treated as restricted; otherwise, all pointer parameters in the entire C file are treated as restricted. For example, `-xrestrict=vsq`, qualifies the pointers `a` and `b` given in the first example of the function `vsq()` with the keyword `restrict`.

It is critical that you use `restrict` correctly. If pointers qualified as restricted pointers point to objects which are not distinct, the compiler can incorrectly parallelize loops resulting in undefined behavior. For example, assume that pointers `a` and `b` of function `vsq()` point to objects which overlap, such that `b[i]` and `a[i+1]` are the same object. If `a` and `b` are not declared as restricted pointers the loops will be executed serially. If `a` and `b` are incorrectly qualified as restricted pointers the compiler may parallelize the execution of the loops, which is not safe, because `b[i+1]` should only be computed after `b[i]` is computed.

3.8.3 Explicit Parallelization and Pragmas

Often, there is not enough information available for the compiler to make a decision on the legality or profitability of parallelization. The compiler supports pragmas that allow the programmer to effectively parallelize loops that otherwise would be too difficult or impossible for the compiler to handle. The Sun-Specific MP pragmas detailed in the rest of this section have been deprecated in favor of the OpenMP standard. See the *OpenMP API User's Guide* for information to the directives of the standard.

3.8.3.1 Serial Pragmas

Note – The Sun-specific MP pragmas have been deprecated and are no longer supported. However, the compiler supports the APIs specified by the OpenMP 2.5 standard instead. See the *OpenMP API User's Guide* for migration information to the directives of the standard.

There are two serial pragmas, and both apply to `for` loops:

- `#pragma MP serial_loop`
- `#pragma MP serial_loop_nested`

The `#pragma MP serial_loop` pragma indicates to the compiler that the next `for` loop is not to be automatically parallelized.

The `#pragma MP serial_loop_nested` pragma indicates to the compiler that the next `for` loop and any `for` loops nested within the scope of this `for` loop are not to be automatically parallelized.

The scope of these pragmas begins with the pragma and ends with the beginning of the next block, the next for loop within the current block, or the end of the current block, whichever occurs first.

3.8.3.2 Parallel Pragma

Note – The Sun-specific MP pragmas have been deprecated and are no longer supported. However, the compiler supports the APIs specified by the OpenMP 2.5 standard instead. See the *OpenMP API User's Guide* for migration information to the directives of the standard.

There is one parallel pragma: `#pragma MP taskloop [options]`.

The MP `taskloop` pragma can, optionally, take one or more of the following arguments.

- `maxcpus` (*number_of_processors*)
- `private` (*list_of_private_variables*)
- `shared` (*list_of_shared_variables*)
- `readonly` (*list_of_readonly_variables*)
- `storeback` (*list_of_storeback_variables*)
- `savelast`
- `reduction` (*list_of_reduction_variables*)
- `schedtype` (*scheduling_type*)

The scope of these pragmas begins with the pragma and ends with whichever of the following occurs first: the beginning of the next block, the next for loop within the current block, the end of the current block. The pragma applies to the next for loop prior to the end of the pragmas scope.

Only one option can be specified per MP `taskloop` pragma; however, the pragmas are cumulative and apply to the next for loop within the pragmas scope:

```
#pragma MP taskloop maxcpus(4)
#pragma MP taskloop shared(a,b)
#pragma MP taskloop storeback(x)
```

These options may appear multiple times prior to the for loop to which they apply. In case of conflicting options, the compiler will issue a warning message.

Nesting of for Loops

An `MP taskloop` pragma applies to the next `for` loop within the current block. There is no nesting of parallelized `for` loops by parallelized C.

Eligibility for Parallelizing

An `MP taskloop` pragma suggests to the compiler that, unless otherwise disallowed, the specified `for` loop should be parallelized.

Any `for` loop with irregular control flow and unknown loop iteration increment is ineligible for parallelization. For example, `for` loops containing `setjmp`, `longjmp`, `exit`, `abort`, `return`, `goto`, labels, and `break` should not be considered as candidates for parallelization.

Of particular importance is to note that `for` loops with inter-iteration dependencies can be eligible for explicit parallelization. This means that if an `MP taskloop` pragma is specified for such a loop the compiler will simply honor it, unless the `for` loop is disqualified. It is the user's responsibility to make sure that such explicit parallelization will not lead to incorrect results.

If both the `serial_loop` or `serial_loop_nested` and `taskloop` pragmas are specified for a `for` loop, the last one specified will prevail.

Consider the following example:

```
#pragma MP serial_loop_nested
  for (i=0; i<100; i++) {
    # pragma MP taskloop
      for (j=0; j<1000; j++) {
        ...
      }
    }
  }
```

The `i` loop will not be parallelized but the `j` loop might be.

Number of Processors

`#pragma MP taskloop maxcpus (number_of_processors)` specifies the number of processors to be used for this loop, if possible.

The value of `maxcpus` must be a positive integer. If `maxcpus` equals 1, then the specified loop will be executed in serial. (Note that setting `maxcpus` to be 1 is equivalent to specifying the `serial_loop` pragma.) The smaller of the values of

`maxcpus` or the interpreted value of the `PARALLEL` environment variable will be used. When the environment variable `PARALLEL` is not specified, it is interpreted as having the value 1.

If more than one `maxcpus` pragma is specified for a `for` loop, the last one specified will prevail.

Classifying Variables

A variable used in a loop is classified as being either a `private`, `shared`, `reduction`, or `readonly` variable. The variable belongs to only one of these classifications. A variable can only be classified as a `reduction` or `readonly` variable through an explicit pragma. See `#pragma MP taskloop reduction` and `#pragma MP taskloop readonly`. A variable can be classified as being either a `private` or `shared` variable through an explicit pragma or through the following default scoping rules.

Default Scoping Rules for private and shared Variables

A `private` variable is one whose value is private to each processor processing some iterations of a `for` loop. In other words, the value assigned to a `private` variable in one iteration of a `for` loop is not propagated to other processors processing other iterations of that `for` loop. A `shared` variable, on the other hand, is a variable whose current value is accessible by all processors processing iterations of a `for` loop. The value assigned to a `shared` variable by one processor working on iterations of a loop may be seen by other processors working on other iterations of the loop. Loops being explicitly parallelized through use of `#pragma MP taskloop` directives, that contain references to shared variables, must ensure that such sharing of values does not cause any correctness problems (such as race conditions). No synchronization is provided by the compiler on updates and accesses to shared variables in an explicitly parallelized loop.

In analyzing explicitly parallelized loops, the compiler uses the following “default scoping rules” to determine whether a variable is `private` or `shared`:

- If a variable is not explicitly classified via a pragma, the variable will default to being classified as a `shared` variable if it is declared as a pointer or array, and is only referenced using array syntax within the loop. Otherwise, it will be classified as a `private` variable.
- The loop index variable is always treated as a `private` variable and is always a storeback variable.

It is *highly recommended* that all variables used in an explicitly parallelized `for` loop be explicitly classified as one of `shared`, `private`, `reduction`, or `readonly`, to avoid the “default scoping rules.”

Since the compiler does not perform any synchronization on accesses to shared variables, extreme care must be exercised before using an `MP taskloop` pragma for a loop that contains, for example, array references. If inter-iteration data dependencies exist in such an explicitly parallelized loop, then its parallel execution may give erroneous results. The compiler may or may not be able to detect such a potential problem situation and issue a warning message. In any case, the compiler will not disable the explicit parallelization of loops with potential shared variable problems.

`private` Variables

```
#pragma MP taskloop private (list_of_private_variables)
```

Use this pragma to specify all the variables that should be treated as private variables for this loop. All other variables used in the loop that are not explicitly specified as `shared`, `readonly`, or `reduction` variables, are either `shared` or `private` as defined by the default scoping rules.

A `private` variable is one whose value is private to each processor processing some iterations of a loop. In other words, the value assigned to a `private` variable by one of the processors working on iterations of a loop is not propagated to other processors processing other iterations of that loop. A `private` variable has no initial value at the start of each iteration of a loop and must be set to a value within the iteration of a loop prior to its first use within that iteration. Execution of a program with a loop containing an explicitly declared `private` variable whose value is used prior to being set will result in undefined behavior.

`shared` Variables

```
#pragma MP taskloop shared (list_of_shared_variables)
```

Use this pragma to specify all the variables that should be treated as shared variables for this loop. All other variables used in the loop that are not explicitly specified as `private`, `readonly`, `storeback` or `reduction` variables, are either `shared` or `private` as defined by the default scoping rules.

A `shared` variable is a variable whose current value is accessible by all processors processing iterations of a `for` loop. The value assigned to a `shared` variable by one processor working on iterations of a loop may be seen by other processors working on other iterations of the loop.

`readonly` Variables

```
#pragma MP taskloop readonly (list_of_readonly_variables)
```


readonly variables are a special class of shared variables that are not modified in any iteration of a loop. Use this pragma to indicate to the compiler that it may use a separate copy of that variable's value for each processor processing iterations of the loop.

storeback Variables

```
#pragma MP taskloop storeback (list_of_storeback_variables)
```

Use this pragma to specify all the variables to be treated as storeback variables.

A storeback variable is one whose value is computed in a loop, and this computed value is then used after the termination of the loop. The last loop iteration values of storeback variables are available for use after the termination of the loop. Such a variable is a good candidate to be declared explicitly via this directive as a storeback variable when the variable is a private variable, whether by explicitly declaring the variable private or by the default scoping rules.

Note that the storeback operation for a storeback variable occurs at the last iteration of the explicitly parallelized loop, regardless of whether or not that iteration updates the value of the storeback variable. In other words, the processor that processes the last iteration of a loop may not be the same processor that currently contains the last updated value for a storeback variable. Consider the following example:

```
#pragma MP taskloop private(x)
#pragma MP taskloop storeback(x)
  for (i=1; i <= n; i++) {
    if (...) {
      x=...
    }
  }
  printf ("%d", x);
```

In the previous example the value of the storeback variable `x` printed out via the `printf()` call may not be the same as that printed out by a serial version of the `i` loop, because in the explicitly parallelized case, the processor that processes the last iteration of the loop (when `i==n`), which performs the storeback operation for `x` may not be the same processor that currently contains the last updated value for `x`. The compiler will attempt to issue a warning message to alert the user of such potential problems.

In an explicitly parallelized loop, variables referenced as arrays are not treated as storeback variables. Hence it is important to include them in the *list_of_storeback_variables* if such storeback operation is desired (for example, if the variables referenced as arrays have been declared as private variables).

savelast

```
#pragma MP taskloop savelast
```

Use this pragma to specify all the private variables of a loop that you want to be treated as storeback variables. The syntax of this pragma is as follows:

```
#pragma MP taskloop savelast
```

It is often convenient to use this form, rather than list out each private variable of a loop when declaring each variable as storeback variables.

reduction *Variables*

`#pragma MP taskloop reduction (list_of_reduction_variables)` specifies that all the variables appearing in the reduction list will be treated as reduction variables for the loop. A reduction variable is one whose partial values can be individually computed by each of the processors processing iterations of the loop, and whose final value can be computed from all its partial values. The presence of a list of reduction variables can facilitate the compiler in identifying that the loop is a reduction loop, allowing generation of parallel reduction code for it. Consider the following example:

```
#pragma MP taskloop reduction(x)
  for (i=0; i<n; i++) {
    x = x + a[i];
  }
```

the variable *x* is a (sum) reduction variable and the *i* loop is a (sum) reduction loop.

Scheduling Control

The Sun ISO C compiler supports several pragmas that can be used in conjunction with the `taskloop` pragma to control the loop scheduling strategy for a given loop. The syntax for this pragma is:

```
#pragma MP taskloop schedtype (scheduling_type)
```

This pragma can be used to specify the specific *scheduling_type* to be used to schedule the parallelized loop. *Scheduling_type* can be one of the following:

- `static`

In static scheduling all the iterations of the loop are uniformly distributed among all the participating processors. Consider the following example:

```
#pragma MP taskloop maxcpus(4)
#pragma MP taskloop schedtype(static)
    for (i=0; i<1000; i++) {
    ...
}
```

In the above example, each of the four processors will process 250 iterations of the loop.

■ `self [(chunk_size)]`

In `self` scheduling, each participating processor processes a fixed number of iterations (called the “*chunk size*”) until all the iterations of the loop have been processed. The optional *chunk_size* parameter specifies the “*chunk size*” to be used. *Chunk_size* must be a positive integer constant, or variable of integral type. If specified as a variable, *chunk_size* must evaluate to a positive integer value at the beginning of the loop. If this optional parameter is not specified or its value is not positive, the compiler will select the chunk size to be used. Consider the following example:

```
#pragma MP taskloop maxcpus(4)
#pragma MP taskloop schedtype(self(120))
for (i=0; i<1000; i++) {
    ...
}
```

In the above example, the number of iterations of the loop assigned to each participating processor, in order of work request, are:

120, 120, 120, 120, 120, 120, 120, 40.

■ `gss [(min_chunk_size)]`

In guided `self` scheduling, each participating processor processes a variable number of iterations (called the “*min chunk size*”) until all the iterations of the loop have been processed. The optional *min_chunk_size* parameter specifies that each variable chunk size used must be at least *min_chunk_size* in size. *Min_chunk_size* must be a positive integer constant, or variable of integral type. If specified as a variable, *min_chunk_size* must evaluate to a positive integer value at

the beginning of the loop. If this optional parameter is not specified or its value is not positive, the compiler will select the chunk size to be used. Consider the following example:

```
#pragma MP taskloop maxcpus(4)
#pragma MP taskloop schedtype(gss(10))
for (i=0; i<1000; i++) {
    ...
}
```

In the above example, the number of iterations of the loop assigned to each participating processor, in order of work request, are:

250, 188, 141, 106, 79, 59, 45, 33, 25, 19, 14, 11, 10, 10, 10.

■ factoring [*min_chunk_size*]

In factoring scheduling, each participating processor processes a variable number of iterations (called the “min chunk size”) until all the iterations of the loop have been processed. The optional *min_chunk_size* parameter specifies that each variable chunk size used must be at least *min_chunk_size* in size.

Min_chunk_size must be a positive integer constant, or variable of integral type. If specified as a variable *min_chunk_size* must evaluate to a positive integer value at the beginning of the loop. If this optional parameter is not specified or its value is not positive, the compiler will select the chunk size to be used. Consider the following example:

```
#pragma MP taskloop maxcpus(4)
#pragma MP taskloop schedtype(factoring(10))
for (i=0; i<1000; i++) {
    ...
}
```

In the above example, the number of iterations of the loop assigned to each participating processor, in order of work request, are:

125, 125, 125, 125, 62, 62, 62, 62, 32, 32, 32, 32, 16, 16, 16, 16, 10, 10, 10, 10, 10, 10

lint Source Code Checker

This chapter explains how you can use the `lint` program to check your C code for errors that may cause a compilation failure or unexpected results at runtime. In many cases, `lint` warns you about incorrect, error-prone, or nonstandard code that the compiler does not necessarily flag.

The `lint` program issues every error and warning message produced by the C compiler. It also issues warnings about potential bugs and portability problems. Many messages issued by `lint` can assist you in improving your program's effectiveness, including reducing its size and required memory.

The `lint` program uses the same locale as the compiler and the output from `lint` is directed to `stderr`. See [Chapter 5](#) for more information on and examples of how to use `lint` to check code before you perform type-based alias-disambiguation.

4.1 Basic and Enhanced `lint` Modes

The `lint` program operates in two modes:

- *Basic*, which is the default
- *Enhanced*, which includes everything done by basic `lint`, as well as additional, detailed analysis of code

In both basic and enhanced modes, `lint` compensates for separate and independent compilation in C by flagging inconsistencies in definition and use across files, including any libraries you have used. In a large project environment especially, where the same function may be used by different programmers in hundreds of separate modules of code, `lint` can help discover bugs that otherwise might be difficult to find. A function called with one less argument than expected, for example, looks at the stack for a value the call has never pushed, with results correct in one condition, incorrect in another, depending on whatever happens to be in

memory at that stack location. By identifying dependencies like this one and dependencies on machine architecture as well, `lint` can improve the reliability of code run on your machine or someone else's.

In enhanced mode, `lint` provides more detailed reporting than in basic mode. In basic mode, `lint`'s capabilities include:

- Structure and flow analysis of the source program
- Constant propagations and constant expression evaluations
- Analysis of control flow and data flow
- Analysis of data types usage

In enhanced mode, `lint` can detect these problems:

- Unused `#include` directives, variables, and procedures
- Memory usage after its deallocation
- Unused assignments
- Usage of a variable value before its initialization
- Deallocation of nonallocated memory
- Usage of pointers when writing in constant data segments
- Nonequivalent macro redefinitions
- Unreached code
- Conformity of the usage of value types in unions
- Implicit casts of actual arguments.

4.2 Using `lint`

Invoke the `lint` program and its options from the command line. To invoke `lint` in the basic mode, use the following command:

```
% lint file1.c file2.c
```

Enhanced `lint` is invoked with the `-Nlevel` or `-Ncheck` option. For example, you can invoke enhanced `lint` as follows:

```
% lint -Nlevel=3 file1.c file2.c
```

`lint` examines code in two *passes*. In the first pass, `lint` checks for error conditions within C source files; in the second pass, it checks for inconsistencies across C source files. This process is invisible to the user unless `lint` is invoked with `-c`:

```
% lint -c file1.c file2.c
```

That command directs `lint` to execute the first pass only and collect information relevant to the second—about inconsistencies in definition and use across `file1.c` and `file2.c`—in intermediate files named `file1.ln` and `file2.ln`:

```
% ls  
file1.c  
file1.ln  
file2.c  
file2.ln
```

This way, the `-c` option to `lint` is analogous to the `-c` option to `cc`, which suppresses the link editing phase of compilation. Generally speaking, `lint`'s command-line syntax closely follows `cc`'s.

When the `.ln` files are linted:

```
% lint file1.ln file2.ln
```

the second pass is executed. `lint` processes any number of `.c` or `.ln` files in their command-line order. Thus,

```
% lint file1.ln file2.ln file3.c
```

directs `lint` to check `file3.c` for errors internal to it and all three files for consistency.

`lint` searches directories for included header files in the same order as `cc`. You can use the `-I` option to `lint` as you would the `-I` option to `cc`. See [Section 2.14, “How to Specify Include Files”](#) on page 2-27.

You can specify multiple options to `lint` on the same command line. Options can be concatenated unless one of the options takes an argument or if the option has more than one letter:

```
% lint -cp -Idir1 -Idir2 file1.c file2.c
```

That command directs `lint` to:

- Execute the first pass only
- Perform additional portability checks
- Search the specified directories for included header files

`lint` has many options you can use to direct `lint` to perform certain tasks and report on certain conditions.

4.3 The `lint` Options

The `lint` program is a static analyzer. It cannot evaluate the runtime consequences of the dependencies it detects. Certain programs, for instance, may contain hundreds of unreachable `break` statements that are of little importance, but which `lint` flags nevertheless. This is one example where the `lint` command-line options and directives—special comments embedded in the source text—come in:

- You can invoke `lint` with the `-b` option to suppress all the error messages about unreachable `break` statements.
- You can precede any unreachable statement with the comment `/*NOTREACHED*/` to suppress the diagnostic for that statement.

The `lint` options are listed below alphabetically. Several `lint` options relate to suppressing `lint` diagnostic messages. These options are also listed in [TABLE 4-8](#), following the alphabetized options, along with the specific messages they suppress. The options for invoking enhanced `lint` begin with `-N`.

`lint` recognizes many `cc` command-line options, including `-A`, `-D`, `-E`, `-g`, `-H`, `-O`, `-P`, `-U`, `-Xa`, `-Xc`, `-Xs`, `-Xt`, and `-Y`, although `-g` and `-O` are ignored. Unrecognized options are warned about and ignored.

4.3.1 `-#`

Turns on verbose mode, showing each component as it is invoked.

4.3.2 `-###`

Shows each component as it is invoked, but does not actually execute it.

4.3.3 `-a`

Suppresses certain messages. Refer to [TABLE 4-8](#).

4.3.4 `-b`

Suppresses certain messages. Refer to [TABLE 4-8](#).

4.3.5 `-C filename`

Creates a `.ln` file with the file name specified. These `.ln` files are the product of `lint`'s first pass only. *filename* can be a complete path name.

4.3.6 `-c`

Creates a `.ln` file consisting of information relevant to `lint`'s second pass for every `.c` file named on the command line. The second pass is not executed.

4.3.7 `-dirout=dir`

Specifies the directory *dir* where the `lint` output files (`.ln` files) will be placed. This option affects the `-c` option.

4.3.8 `-err=warn`

`-err=warn` is a macro for `-errwarn=%all`. See [Section 4.3.15, “-errwarn=t” on page 4-10](#).

4.3.9 `-errchk=l(, l)`

Perform additional checking as specified by *l*. The default is `-errchk=%none`. Specifying `-errchk` is equivalent to specifying `-errchk=%all`. *l* is a comma-separated list of checks that consists of one or more of the following. For example, `-errchk=longptr64,structarg`.

TABLE 4-1 The `-errchk` Flags

Value	Meaning
<code>%all</code>	Perform all of <code>-errchk</code> 's checks.
<code>%none</code>	Perform none of <code>-errchk</code> 's checks. This is the default.
<code>[no%]locfmtchk</code>	Check for <code>printf</code> -like format strings during the first pass of <code>lint</code> . Regardless of whether or not you use <code>-errchk=locfmtchk</code> , <code>lint</code> always checks for <code>printf</code> -like format strings in its second pass.

TABLE 4-1 The `-errchk` Flags (*Continued*)

Value	Meaning
<code>[no%]longptr64</code>	Check portability to environment for which the size of long integers and pointers is 64 bits and the size of plain integers is 32 bits. Check assignments of pointer expressions and long integer expressions to plain integers, even when explicit cast is used.
<code>[no%]structarg</code>	Check structural arguments passed by value and report the cases when formal parameter type is not known.
<code>[no%]parentheses</code>	Check the clarity of precedence within your code. Use this option to enhance the maintainability of code. If <code>-errchk=parentheses</code> returns a warning, consider using additional parentheses to clearly signify the precedence of operations within the code.
<code>[no%]signext</code>	Check for situations in which the normal ISO C value-preserving rules allow the extension of the sign of a signed-integral value in an expression of unsigned-integral type. This option only produces error messages when you specify <code>-errchk=longptr64</code> as well.
<code>[no%]sizematch</code>	Check for the assignment of a larger integer to a smaller integer and issue a warning. These warnings are also issued for assignment between same size integers that have different signs (unsigned int gets a signed int).

4.3.10 `-errfmt=f`

Specifies the format of lint output. *f* can be one of the following: `macro`, `simple`, `src`, or `tab`.

TABLE 4-2 The `-errfmt` Flags

Value	Meaning
<code>macro</code>	Displays the source code, the line number, and the place of the error, with macro unfolding
<code>simple</code>	Displays the line number and the place number, in brackets, of the error, for one-line (simple) diagnostic messages. Similar to the <code>-s</code> option, but includes error-position information
<code>src</code>	Displays the source code, the line number, and the place of the error (no macro unfolding)
<code>tab</code>	Displays in tabular format. This is the default.

The default is `-errfmt=tab`. Specifying `-errfmt` is equivalent to specifying `-errfmt=tab`.

If more than one format is specified, the last format specified is used, and `lint` warns about the unused formats.

4.3.11 `-errhdr=h`

Enables `lint` to report certain messages for header files when you also specify `-Ncheck`. *h* is a comma-separated list that consists of one or more of the following: *dir*, `no%dir`, `%all`, `%none`, `%user`.

TABLE 4-3 The `-errhdr` Flags

Value	Meaning
<i>dir</i>	Report the <code>-Ncheck</code> messages for header files included from the directory <i>dir</i>
<code>no%dir</code>	Does not report the <code>-Ncheck</code> messages for header files included from the directory <i>dir</i>
<code>%all</code>	Checks all used header files
<code>%none</code>	Does not check header files. This is the default.
<code>%user</code>	Checks all used user header files, that is, all header files except those in <code>/usr/include</code> and its subdirectories, as well as those supplied by the compiler

The default is `-errhdr=%none`. Specifying `-errhdr` is equivalent to specifying `-errhdr=%user`.

Examples:

```
% lint -errhdr=inc1 -errhdr=../inc2
```

checks used header files in directories `inc1` and `../inc2`.

```
% lint -errhdr=%all,no%../inc
```

checks all used header files except those in the directory `../inc`.

4.3.12 `-erroff=tag(, tag)`

Suppresses or enables `lint` error messages.

t is a comma-separated list that consists of one or more of the following: *tag*, *no%tag*, *%all*, *%none*.

TABLE 4-4 The `-erroff` Flags

Value	Meaning
<i>tag</i>	Suppresses the message specified by this <i>tag</i> . You can display the tag for a message by using the <code>-errtags=yes</code> option.
<i>no%tag</i>	Enables the message specified by this <i>tag</i>
<i>%all</i>	Suppresses all messages
<i>%none</i>	Enables all messages. This is the default.

The default is `-erroff=%none`. Specifying `-erroff` is equivalent to specifying `-erroff=%all`.

Examples:

```
% lint -erroff=%all,no%E_ENUM_NEVER_DEF,no%E_STATIC_UNUSED
```

prints only the messages “enum never defined” and “static unused”, and suppresses other messages.

```
% lint -erroff=E_ENUM_NEVER_DEF,E_STATIC_UNUSED
```

suppresses only the messages “enum never defined” and “static unused”.

4.3.13 `-errsecurity=v`

Use the `-errsecurity` option to check your code for security loopholes.

v must be one of the following:

TABLE 4-5 The `-errsecurity` Flags

Option	Meaning
core	<p>This level checks for source code constructs that are almost always either unsafe or difficult to verify. Checks at this level include:</p> <ul style="list-style-type: none">• Use of variable format strings with the <code>printf()</code> and <code>scanf()</code> family of functions• Use of unbounded string (<code>%s</code>) formats in <code>scanf()</code> functions• Use of functions with no safe usage: <code>gets()</code>, <code>cftime()</code>, <code>ascftime()</code>, <code>creat()</code>• Incorrect use of <code>open()</code> with <code>O_CREAT</code> <p>Consider source code that produces warnings at this level to be a bug. The source code in question should be changed. In all cases, straightforward safer alternatives are available.</p>
standard	<p>This level includes all checks from the core level plus constructs that may be safe, but have better alternatives available. This level is recommended when checking newly-written code. Additional checks at this level include:</p> <ul style="list-style-type: none">• Use of string copy functions other than <code>strncpy()</code>• Use of weak random number functions• Use of unsafe functions to generate temporary files• Use of <code>fopen()</code> to create files• Use of functions that invoke the shell <p>Replace source code that produces warnings at this level with new or significantly modified code. Balance addressing these warnings in legacy code against the risks of destabilizing the application.</p>
extended	<p>This level contains the most complete set of checks, including everything from the Core and Standard levels. In addition, a number of warnings are generated about constructs that may be unsafe in some situations. The checks at this level are useful as an aid in reviewing code, but need not be used as a standard with which acceptable source code must comply. Additional checks at this level include:</p> <ul style="list-style-type: none">• Calls to <code>getc()</code> or <code>fgetc()</code> inside a loop• Use of functions prone to pathname race conditions• Use of the <code>exec()</code> family of functions• Race conditions between <code>stat()</code> and other functions <p>Review source code which produces warnings at this level to determine if the potential security issue is present.</p>
%none	Turns off <code>-errsecurity</code> checks

If you do not specify a setting for `-errsecurity`, the lint sets it to `-errsecurity=%none`. If you do specify `-errsecurity` but not an argument, the lint sets it to `-errsecurity=standard`.

4.3.14 `-errtags=a`

Displays the message tag for each error message. *a* can be either yes or no. The default is `-errtags=no`. Specifying `-errtags` is equivalent to specifying `-errtags=yes`.

Works with all `-errfmt` options.

4.3.15 `-errwarn=t`

If the indicated warning message is issued, lint exits with a failure status. *t* is a comma-separated list that consists of one or more of the following: *tag*, `no%tag`, `%all`, `%none`. Order is important; for example `%all,no%tag` causes lint to exit with a fatal status if any warning except *tag* is issued. The following table list the `-errwarn` values:

TABLE 4-6 The `-errwarn` Flags

<i>tag</i>	Cause lint to exit with a fatal status if the message specified by this <i>tag</i> is issued as a warning message. Has no effect if <i>tag</i> is not issued.
<code>no%tag</code>	Prevent lint from exiting with a fatal status if the message specified by <i>tag</i> is issued only as a warning message. Has no effect if <i>tag</i> is not issued. Use this option to revert a warning message that was previously specified by this option with <i>tag</i> or <code>%all</code> from causing lint to exit with a fatal status when issued as a warning message.
<code>%all</code>	Cause lint to exit with a fatal status if any warning messages are issued. <code>%all</code> can be followed by <code>no%tag</code> to exempt specific warning messages from this behavior.
<code>%none</code>	Prevents any warning message from causing lint to exit with a fatal status should any warning message be issued.

The default is `-errwarn=%none`. If you specify `-errwarn` alone, it is equivalent to `-errwarn=%all`.

- 4.3.16 `-F`
- Prints the path names as supplied on the command line rather than only their base names when referring to the `.c` files named on the command line.
- 4.3.17 `-fd`
- Reports about old-style function definitions or declarations.
- 4.3.18 `-flagsrc=file`
- Executes `lint` with options contained in the file *file*. Multiple options can be specified in *file*, one per line.
- 4.3.19 `-h`
- Suppresses certain messages. Refer to [TABLE 4-8](#).
- 4.3.20 `-Idir`
- Searches the directory *dir* for included header files.
- 4.3.21 `-k`
- Alter the behavior of `/* LINTED [message] */` directives or `NOTE(LINTED(message))` annotations. Normally, `lint` suppresses warning messages for the code following these directives. Instead of suppressing the messages, `lint` prints an additional message containing the comment inside the directive or annotation.
- 4.3.22 `-Ldir`
- Searches for a `lint` library in the directory *dir* when used with `-l`.

4.3.23 -lx

Accesses the lint library `llib-lx.ln`.

4.3.24 -m

Suppresses certain messages. Refer to [TABLE 4-8](#).

4.3.25 -Ncheck=c

Checks header files for corresponding declarations; checks macros. *c* is a comma-separated list of checks that consists of one or more of the following: `macro`, `extern`, `%all`, `%none`, `no%macro`, `no%extern`.

TABLE 4-7 The -Ncheck Flags

Value	Meaning
<code>macro</code>	Checks for consistency of macro definitions across files
<code>extern</code>	Checks for one-to-one correspondence of declarations between source files and their associated header files (for example, for <code>file1.c</code> and <code>file1.h</code>). Ensure that there are neither extraneous nor missing <code>extern</code> declarations in a header file.
<code>%all</code>	Performs all of -Ncheck's checks
<code>%none</code>	Performs none of -Ncheck's checks. This is the default.
<code>no%macro</code>	Performs none of -Ncheck's <code>macro</code> checks
<code>no%extern</code>	Performs none of -Ncheck's <code>extern</code> checks

The default is `-Ncheck=%none`. Specifying `-Ncheck` is equivalent to specifying `-Ncheck=%all`.

Values may be combined with a comma, for example, `-Ncheck=extern,macro`.

Example:

```
% lint -Ncheck=%all,no%macro
```

performs all checks except macro checks.

4.3.26 `-Nlevel=n`

Turns on enhanced `lint` mode by specifying the level of enhanced `lint` analysis for reporting problems. This option allows you to control the amount of detected errors. The higher the level, the longer the verification time. *n* is a number: 1, 2, 3, or 4. There is no default. If you do not specify `-Nlevel`, `lint` uses its basic analysis mode. If you specify `-Nlevel` without an argument, `lint` sets `-Nlevel=4`.

See [Section 4.2, “Using `lint`” on page 4-2](#) for an explanation of basic and enhanced `lint` modes.

4.3.26.1 `-Nlevel=1`

Analyzes single procedures. Reports unconditional errors that occur on some program execution paths. Does not do global data and control flow analysis.

4.3.26.2 `-Nlevel=2`

Analyzes the whole program, including global data and control flow. Reports unconditional errors that occur on some program execution paths.

4.3.26.3 `-Nlevel=3`

Analyzes the whole program, including constant propagation, cases when constants are used as actual arguments, as well as the analysis performed under `-Nlevel=2`.

Verification of a C program at this analysis level takes two to four times longer than at the preceding level. The extra time is required because `lint` assumes partial interpretation of the program by creating sets of possible values for program variables. These sets of variables are created on the basis of constants and conditional statements that contain constant operands available in the program. The sets form the basis for creating other sets (a form of constant propagation). Sets received as the result of the analysis are evaluated for correctness according to the following algorithm:

If a correct value exists among all possible values of an object, then that correct value is used as the basis for further propagation; otherwise an error is diagnosed.

4.3.26.4 `-Nlevel=4`

Analyzes the whole program, and reports conditional errors that could occur when certain program execution paths are used, as well as the analysis performed under `-Nlevel=3`.

At this analysis level, there are additional diagnostic messages. The analysis algorithm generally corresponds to the analysis algorithm of `-Nlevel=3` with the exception that any invalid values now generate an error message. The amount of time required for analysis at this level can increase as much as two orders (about 20 to 100 time more slowly). In this case the extra time required is directly proportional to the program complexity as characterized by recursion, conditional statements etc. As a result of this, it may be difficult to use this level of analysis for a program that exceeds 100,000 lines.

4.3.27 `-n`

Suppresses checks for compatibility with the default `lint` standard C library.

4.3.28 `-o α`

Causes `lint` to create a `lint` library with the name `llib- α .ln`. This library is created from all the `.ln` files that `lint` used in its second pass. The `-c` option nullifies any use of the `-o` option. To produce a `llib- α .ln` without extraneous messages, you can use the `-x` option. The `-v` option is useful if the source file(s) for the `lint` library are just external interfaces. The `lint` library produced can be used later if `lint` is invoked with `- α` .

By default, you create libraries in `lint`'s basic format. If you use `lint`'s enhanced mode, the library created will be in enhanced format, and can only be used in enhanced mode.

4.3.29 `-p`

Enables certain messages relating to portability issues.

4.3.30 `-Rfile`

Write a `.ln` file to *file*, for use by `cxref(1)`. This option disables the enhanced mode, if it is switched on.

4.3.31 -s

Produce simple diagnostics with "warning:" or "error:" prefixes. By default `lint` buffers some messages to produce compound output.

4.3.32 -u

Suppresses certain messages. Refer to [TABLE 4-8](#). This option is suitable for running `lint` on a subset of files of a larger program.

4.3.33 -V

Writes the product name and releases to standard error.

4.3.34 -v

Suppresses certain messages. Refer to [TABLE 4-8](#).

4.3.35 -Wfile

Write a `.ln` file to *file*, for use by `cf1ow(1)`. This option disables the enhanced mode, if it is switched on.

4.3.36 -XCC=*a*

Accepts C++-style comments. In particular, `//` can be used to indicate the start of a comment. *a* can be either `yes` or `no`. The default is `-XCC=no`. Specifying `-XCC` is equivalent to specifying `-XCC=yes`.

Note – You only need to use this option if you use `-xc99=none`. Under `-xc99=all` (the default), `lint` accepts comments which are indicated by `//`.

4.3.37 `-Xalias_level [=l]`

where *l* is one of `any`, `basic`, `weak`, `layout`, `strict`, `std`, or `strong`. See [TABLE B-11](#) for a detailed explanation of the different levels of disambiguation.

If you do not specify `-Xalias_level`, the default of the flag is `-Xalias_level=any`. This means that there is no type-based alias-analysis. If you specify `-Xalias_level` but do not supply a level, the default is `-Xalias_level=layout`.

Be sure to run lint at a level of disambiguation that is no more strict than the level at which you ran the compiler. If you run lint at a level of disambiguation that is more strict than the level at which you compiled, the results will be difficult to interpret and possibly misleading.

See [Chapter 5](#) for a detailed explanation of disambiguation as well as a list of pragmas designed to help with disambiguation.

4.3.38 `-Xarch=amd64`

Predefines the `__amd64` and `__x86_64` macros and searches for x86 versions of lint libraries.

4.3.39 `-Xarch=v9`

Predefines the `__sparcv9` macro and searches for v9 versions of lint libraries.

4.3.40 `-Xc99 [=o]`

The `-Xc99` flag controls compiler recognition of the implemented features from the C99 standard (ISO/IEC 9899:1999, Programming Language - C).

o can be one of the following: `all`, `none`.

`-Xc99=none` turns off recognition of C99 features. `-Xc99=all` turns on recognition of supported C99 features.

Specifying `-Xc99` without any arguments is the same as `-Xc99=all`.

Note – Though the compiler support-level defaults to the features of C99 listed in [Appendix D](#), the standard headers provided by Solaris software in `/usr/include` do not yet conform with the 1999 ISO/IEC C standard. If you encounter error messages, try using `-xc99=none` to obtain the 1990 ISO/IEC C standard behavior for these headers.

4.3.41 `-Xexplicitpar=a`

(SPARC) Directs `lint` to recognize `#pragma MP` directives. *a* can be either `yes` or `no`. The default is `-Xexplicitpar=no`. Specifying `-Xexplicitpar` is equivalent to specifying `-Xexplicitpar=yes`.

4.3.42 `-Xkeeptmp=a`

Keeps temporary files created during linting instead of deleting them automatically. *a* can be either `yes` or `no`. The default is `-Xkeeptmp=no`. Specifying `-Xkeeptmp` is equivalent to specifying `-Xkeeptmp=yes`.

4.3.43 `-Xtemp=dir`

Sets the directory for temporary files to *dir*. Without this option, temporary files go into `/tmp`.

4.3.44 `-Xtime=a`

Reports the execution time for each `lint` pass. *a* can be either `yes` or `no`. The default is `-Xtime=no`. Specifying `-Xtime` is equivalent to specifying `-Xtime=yes`.

4.3.45 `-Xtransition=a`

Issues warnings for the differences between K&R C and Sun ISO C. *a* can be either `yes` or `no`. The default is `-Xtransition=no`. Specifying `-Xtransition` is equivalent to specifying `-Xtransition=yes`.

4.3.46 `-Xustr={ascii_utf16_ushort|no}`

This option enables recognition of string literals of the form `U"ASCII_string"` as an array of unsigned short int. The default is `-Xustr=no` which disables compiler recognition of `U"ASCII_string"` string literals. `-Xustr=ascii_utf16_ushort` enables compiler recognition of `U"ASCII_string"` string literals.

4.3.47 `-x`

Suppresses certain messages. Refer to [TABLE 4-8](#).

4.3.48 `-y`

Treats every `.c` file named on the command line as if it begins with the directive `/* LINTLIBRARY */` or the annotation `NOTE(LINTLIBRARY)`. A `lint` library is normally created using the `/* LINTLIBRARY */` directive or the `NOTE(LINTLIBRARY)` annotation.

4.4 `lint` Messages

Most of `lint`'s messages are simple, one-line statements printed for each occurrence of the problem they diagnose. Errors detected in included files are reported multiple times by the compiler, but only once by `lint`, no matter how many times the file is included in other source files. Compound messages are issued for inconsistencies across files and, in a few cases, for problems within them as well. A single message describes every occurrence of the problem in the file or files being checked. When use of a `lint` filter (see [Section 4.6.2, "lint Libraries" on page 4-31](#)) requires that a message be printed for each occurrence, compound diagnostics can be converted to the simple type by invoking `lint` with the `-s` option.

`lint`'s messages are written to `stderr`.

4.4.1 Options to Suppress Messages

You can use several `lint` options to suppress `lint` diagnostic messages. Messages can be suppressed with the `-erroff` option, followed by one or more *tags*. These mnemonic tags can be displayed with the `-errtags=yes` option.

The following table lists the options that suppress lint messages.

TABLE 4-8 lint Options to Suppress Messages

Option	Messages Suppressed
-a	assignment causes implicit narrowing conversion conversion to larger integral type may sign-extend incorrectly
-b	statement not reached (unreachable break and empty statements)
-h	assignment operator "=" found where equality operator "==" was expected constant operand to op: "!" fallthrough on case statements pointer cast may result in improper alignment precedence confusion possible; parenthesize statement has no consequent: if statement has no consequent: else
-m	declared global, could be static
-erroff= <i>tag</i>	One or more lint messages specified by <i>tag</i>
-u	name defined but never used name used but not defined
-v	arguments unused in function
-x	name declared but never used or defined

4.4.2 lint Message Formats

The lint program can, with certain options, show precise source file lines with pointers to the line position where the error occurred. The option enabling this feature is `-errfmt=f`. Under this option, lint provides the following information:

- Source line(s) and position(s)
- Macro unfolding
- Error-prone stack(s)

For example, the following program, `Test1.c`, contains an error.

```
1 #include <string.h>
2 static void cpv(char *s, char* v, unsigned n)
3 { int i;
4   for (i=0; i<=n; i++){
5     *v++ = *s++;}
6 }
7 void main(int argc, char* argv[])
8 {
9   if (argc != 0){
10    cpv(argv[0], argc, strlen(argv[0]));}
11}
```

Using `lint` on `Test1.c` with the option:

```
% lint -errfmt=src -Nlevel=2 Test1.c
```

produces the following output:

```
static void cpv(char *s, char* v, unsigned n)
    ^ line 2, Test1.c
    cpv(argv[0], argc, strlen(argv[0]));
    ^ line 10, Test1.c
warning: improper pointer/integer combination: arg #2
static void cpv(char *s, char* v, unsigned n)
    ^ line 2, Test1.c
cpv(argv[0], argc, strlen(argv[0]));
    ^ line 10, Test1.c
    *v++ = *s++;
    ^ line 5, Test1.c
warning:use of a pointer produced in a questionable way
v defined at Test1.c(2)::Test1.c(5)
call stack:
    main() ,Test1.c(10)
    cpv() ,Test1.c(5)
```

The first warning indicates two source lines that are contradictory. The second warning shows the call stack, with the control flow leading to the error.

Another program, `Test2.c`, contains a different error:

```
1 #define AA(b) AR[b+1]
2 #define B(c,d) c+AA(d)
3
4 int x=0;
5
6 int AR[10]={1,2,3,4,5,6,77,88,99,0};
7
8 main()
9 {
10  int y=-5, z=5;
11  return B(y,z);
12 }
```

Using `lint` on `Test2.c` with the option:

```
% lint -errfmt=macro Test2.c
```

produces the following output, showing the steps of macro substitution:

```
| return B(y,z);
|         ^ line 11, Test2.c
|
| #define B(c,d) c+AA(d)
|                 ^ line 2, Test2.c
|
| #define AA(b) AR[b+1]
|                 ^ line 1, Test2.c
error: undefined symbol: l
|
|     return B(y,z);
|             ^ line 11, Test2.c
|
| #define B(c,d) c+AA(d)
|                 ^ line 2, Test2.c
|
| #define AA(b) AR[b+1]
|                 ^ line 1, Test2.c
variable may be used before set: l
lint: errors in Test2.c; no output created
lint: pass2 not run - errors in Test2.c
```

4.5 lint Directives

4.5.1 Predefined Values

The following predefinitions are valid in all modes:

- `__sun`
- `__unix`
- `__lint`
- `__SUNPRO_C=0x580`
- `__'uname -s'_'uname -r'` (example: `__SunOS_5_7`)
- `__RESTRICT` (`-Xa` and `-Xt` modes only)
- `__sparc` (*SPARC*)
- `__i386` (*x86*)
- `__BUILTIN_VA_ARG_INCR`
- `__SVR4`
- `__sparcv9` (`-Xarch=v9`)

These predefinitions are not valid in `-xc` mode:

- `sun`
- `unix`
- `sparc` (*SPARC*)
- `i386` (*x86*)
- `lint`

4.5.2 Directives

`lint` directives in the form of `/*...*/` are supported for existing annotations, but will not be supported for future annotations. Directives in the form of source code annotations, `NOTE(...)`, are recommended for all annotations.

Specify `lint` directives in the form of source code annotations by including the file `note.h`, for example:

```
#include <note.h>
```

`Lint` shares the Source Code Annotations scheme with several other tools. When you install the Sun C compiler, you also automatically install the file `/usr/lib/note/SUNW_SPRO-lint`, which contains the names of all the

annotations that LockLint understands. However, the Sun C source code checker, `lint`, also checks all the files in `/usr/lib/note` and `/opt/SUNWspr/prod/lib/note` for all valid annotations.

You may specify a location other than `/usr/lib/note` by setting the environment variable `NOTEPATH`, as in:

```
setenv NOTEPATH $NOTEPATH:other_location
```

The following table lists the `lint` directives along with their actions.

TABLE 4-9 The `lint` Directives

Directive	Action
<code>NOTE(ALIGNMENT(<i>fname,n</i>))</code> where $n=1, 2, 4, 8, 16, 32, 64, 128$	Makes <code>lint</code> set the following function result alignment in n bytes. For example, <code>malloc()</code> is defined as returning a <code>char*</code> or <code>void*</code> when in fact it really returns pointers that are word, or even doubleword, aligned. Suppresses the following message: <ul style="list-style-type: none"> • <code>improper alignment</code>
<code>NOTE(ARGSUSED(<i>n</i>))</code> <code>/*ARGSUSED<i>n</i>*/</code>	This directive acts like the <code>-v</code> option for the next function. Suppresses the following message for every argument but the first n in the function definition it precedes. Default is 0. For the <code>NOTE</code> format, n must be specified. <ul style="list-style-type: none"> • <code>argument unused in function</code>
<code>NOTE(ARGUNUSED(<i>par_name[,par_name...]</i>))</code>	Makes <code>lint</code> not check the mentioned arguments for usage (this option acts only for the next function). Suppresses the following message for every argument listed in <code>NOTE</code> or directive. <ul style="list-style-type: none"> • <code>argument unused in function</code>
<code>NOTE(CONSTCOND)</code> <code>/*CONSTCOND*/</code>	Suppresses complaints about constant operands for the conditional expression. Suppresses the following messages for the constructs it precedes. Also <code>NOTE(CONSTANTCONDITION)</code> or <code>/* CONSTANTCONDITION */.</code> <code>constant in conditional context</code> <code>constant operands to op: "!"</code> <code>logical expression always false: op "&&"</code> <code>logical expression always true: op " "</code>

TABLE 4-9 The lint Directives (*Continued*)

Directive	Action
<code>NOTE (EMPTY) /*EMPTY*/</code>	<p>Suppresses complaints about a null statement consequent on an <code>if</code> statement. This directive should be placed after the test expression, and before the semicolon. This directive is supplied to support empty <code>if</code> statements when a valid <code>else</code> statement follows. It suppresses messages on an empty <code>else</code> consequent.</p> <p>Suppresses the following messages when inserted between the controlling expression of the <code>if</code> and semicolon.</p> <ul style="list-style-type: none">• <code>statement has no consequent: else</code> when inserted between the <code>else</code> and semicolon;• <code>statement has no consequent: if</code>
<code>NOTE (FALLTHRU) /*FALLTHRU*/</code>	<p>Suppresses complaints about a fall through to a case or default labelled statement. This directive should be placed immediately preceding the label.</p> <p>Suppresses the following message for the case statement it precedes. Also <code>NOTE (FALLTHROUGH)</code> or <code>/* FALLTHROUGH */</code>.</p> <ul style="list-style-type: none">• <code>fallthrough on case statement</code>
<code>NOTE (LINTED (msg)) /*LINTED [msg]*/</code>	<p>Suppresses any intra-file warning except those dealing with unused variables or functions. This directive should be placed on the line immediately preceding where the <code>lint</code> warning occurred. The <code>-k</code> option alters the way in which <code>lint</code> handles this directive. Instead of suppressing messages, <code>lint</code> prints an additional message, if any, contained in the comments. This directive is useful in conjunction with the <code>-s</code> option for post-lint filtering.</p> <p>When <code>-k</code> is not invoked, suppresses every warning pertaining to an intra-file problem, except:</p> <ul style="list-style-type: none">• <code>argument unused in function</code>• <code>declarations unused in block</code>• <code>set but not used in function</code>• <code>static unused</code>• <code>variable not used in function</code> <p>for the line of code it precedes. <code>msg</code> is ignored.</p>
<code>NOTE (LINTLIBRARY) /*LINTLIBRARY*/</code>	<p>When <code>-o</code> is invoked, writes to a library <code>.ln</code> file only definitions in the <code>.c</code> file it heads. This directive suppresses complaints about unused functions and function arguments in this file.</p>

TABLE 4-9 The lint Directives (*Continued*)

Directive	Action
<code>NOTE (NOTREACHED)</code> <code>/*NOTREACHED*/</code>	<p>At appropriate points, stops comments about unreachable code. This comment is typically placed just after calls to functions such as <code>exit(2)</code>.</p> <p>Suppresses the following messages for the closing curly brace it precedes at the end of the function.</p> <ul style="list-style-type: none">• <code>statement not reached</code> for the unreachable statements it precedes;• <code>fallthrough on case statement</code> for the case it precedes that cannot be reached from the preceding case;• <code>function falls off bottom without returning value</code>
<code>NOTE (PRINTF LIKE (n))</code> <code>NOTE (PRINTF LIKE (fun_name,n))</code> <code>/*PRINTF LIKE n*/</code>	<p>Treats the <i>n</i>th argument of the function definition it precedes as a <code>[fs]printf()</code> format string and issues the following messages for mismatches between the remaining arguments and the conversion specifications. <code>lint</code> issues these warnings by default for errors in the calls to <code>[fs]printf()</code> functions provided by the standard C library.</p> <p>For the <code>NOTE</code> format, <i>n</i> must be specified.</p> <ul style="list-style-type: none">• <code>malformed format strings</code> for invalid conversion specifications in that argument, and function argument type inconsistent with format;• <code>too few arguments for format</code>• <code>too many arguments for format</code>
<code>NOTE (PROTOLIB (n))</code> <code>/*PROTOLIB n*/</code>	<p>When <i>n</i> is 1 and <code>NOTE (LINTLIBRARY)</code> or <code>/* LINTLIBRARY */</code> is used, writes to a library <code>.ln</code> file only function prototype declarations in the <code>.c</code> file it heads. The default is 0, which cancels the process.</p> <p>For the <code>NOTE</code> format, <i>n</i> must be specified.</p>

TABLE 4-9 The lint Directives (*Continued*)

Directive	Action
<code>NOTE (SCANFLIKE (n))</code> <code>NOTE (SCANFLIKE(fun_name,n))</code> <code>/*SCANFLIKEn*/</code>	Same as <code>NOTE (PRINTFLIKE (n))</code> or <code>/*PRINTFLIKEn */</code> , except that the <i>n</i> th argument of the function definition is treated as a <code>[fs]scanf ()</code> format string. By default, <code>lint</code> issues warnings for errors in the calls to <code>[fs]scanf ()</code> functions provided by the standard C library. For the <code>NOTE</code> format, <i>n</i> must be specified.
<code>NOTE (VARARGS (n))</code> <code>NOTE (VARARGS (fun_name,n))</code> <code>/*VARARGSn*/</code>	Suppresses the usual checking for variable numbers of arguments in the following function declaration. The data types of the first <i>n</i> arguments are checked; a missing <i>n</i> is taken to be 0. The use of the ellipsis (...) terminator in the definition is suggested in new or updated code. For the function whose definition it precedes, suppresses the following message for calls to the function with <i>n</i> or more arguments. For the <code>NOTE</code> format, <i>n</i> must be specified. <ul style="list-style-type: none">• functions called with variable number of arguments

4.6 lint Reference and Examples

This section provides reference information on `lint`, including checks performed by `lint`, `lint` libraries, and `lint` filters.

4.6.1 Diagnostics Performed by lint

`lint`-specific diagnostics are issued for three broad categories of conditions: inconsistent use, nonportable code, and questionable constructs. In this section, we review examples of `lint`'s behavior in each of these areas, and suggest possible responses to the issues they raise.

4.6.1.1 Consistency Checks

Inconsistent use of variables, arguments, and functions is checked within files as well as across them. Generally speaking, the same checks are performed for prototype uses, declarations, and parameters as `lint` checks for old-style functions.

If your program does not use function prototypes, `lint` checks the number and types of parameters in each call to a function more strictly than the compiler. `lint` also identifies mismatches of conversion specifications and arguments in `[fs]printf()` and `[fs]scanf()` control strings.

Examples:

- Within files, `lint` flags non-void functions that “fall off the bottom” without returning a value to the invoking function. In the past, programmers often indicated that a function was not meant to return a value by omitting the return type: `fun() {}`. That convention means nothing to the compiler, which regards `fun()` as having the return type `int`. Declare the function with the return type `void` to eliminate the problem.
- Across files, `lint` detects cases where a non-void function does not return a value, yet is used for its value in an expression—and the opposite problem, a function returning a value that is sometimes or always ignored in subsequent calls. When the value is *always* ignored, it may indicate an inefficiency in the function definition. When it is *sometimes* ignored, it’s probably bad style (typically, not testing for error conditions). If you need not check the return values of string functions like `strcat()`, `strcpy()`, and `sprintf()`, or output functions like `printf()` and `putchar()`, cast the offending calls to `void`.
- `lint` identifies variables or functions that are declared but not used or defined; used, but not defined; or defined, but not used. When `lint` is applied to some, but not all files of a collection to be loaded together, it produces error messages about functions and variables that are:
 - Declared in those files, but defined or used elsewhere
 - Used in those files, but defined elsewhere
 - Defined in those files, but used elsewhere

Invoke the `-x` option to suppress the first complaint, `-u` to suppress the latter two.

4.6.1.2 Portability Checks

Some nonportable code is flagged by `lint` in its default behavior, and a few more cases are diagnosed when `lint` is invoked with `-p` or `-xc`. The latter causes `lint` to check for constructs that do not conform to the ISO C standard. For the messages issued under `-p` and `-xc`, see [Section 4.6.2, “lint Libraries” on page 4-31](#).

Examples:

- In some C language implementations, character variables that are not explicitly declared `signed` or `unsigned` are treated as signed quantities with a range typically from -128 to 127. In other implementations, they are treated as nonnegative quantities with a range typically from 0 to 255. So the test:

```
char c;  
c = getchar();  
if (c == EOF) ...
```

where `EOF` has the value -1, always fails on machines where character variables take on nonnegative values. `lint` invoked with `-p` checks all comparisons that imply a *plain* `char` may have a negative value. However, declaring `c` as a signed `char` in the above example eliminates the diagnostic, not the problem. That's because `getchar()` must return all possible characters and a distinct `EOF` value, so a `char` cannot store its value. We cite this example, perhaps the most common one arising from implementation-defined sign-extension, to show how a thoughtful application of `lint`'s portability option can help you discover bugs not related to portability. In any case, declare `c` as an `int`.

- A similar issue arises with bit-fields. When constant values are assigned to bit-fields, the field may be too small to hold the value. On a machine that treats bit-fields of type `int` as unsigned quantities, the values allowed for `int x:3` range from 0 to 7, whereas on machines that treat them as signed quantities, they range from -4 to 3. However, a three-bit field declared type `int` cannot hold the value 4 on the latter machines. `lint` invoked with `-p` flags all bit-field types other than `unsigned int` or `signed int`. These are the only *portable* bit-field types. The compiler supports `int`, `char`, `short`, and `long` bit-field types that may be unsigned, signed, or *plain*. It also supports the `enum` bit-field type.
- Bugs can arise when a larger-sized type is assigned to a smaller-sized type. If significant bits are truncated, accuracy is lost:

```
short s;  
long l;  
s = l;
```

`lint` flags all such assignments by default; the diagnostic can be suppressed by invoking the `-a` option. Bear in mind that you may be suppressing other diagnostics when you invoke `lint` with this or any other option. Check the list in [Section 4.6.2, "lint Libraries"](#) on page 4-31 for the options that suppress more than one diagnostic.

- A cast of a pointer to one object type to a pointer to an object type with stricter alignment requirements may not be portable. `lint` flags:

```
int *fun(y)
char *y;
{
    return(int *)y;
}
```

because, on most machines, an `int` cannot start on an arbitrary byte boundary, whereas a `char` can. You can suppress the diagnostic by invoking `lint` with `-h`, although, again, you may be disabling other messages. Better still, eliminate the problem by using the generic pointer `void *`.

- ISO C leaves the order of evaluation of complicated expressions undefined. That is, when function calls, nested assignment statements, or the increment and decrement operators cause side effects when a variable is changed as a by-product of the evaluation of an expression, the order in which the side effects take place is highly machine-dependent. By default, `lint` flags any variable changed by a side effect and used elsewhere in the same expression:

```
int a[10];
main()
{
    int i = 1;
    a[i++] = i;
}
```

In this example, the value of `a[1]` may be 1 if one compiler is used, 2 if another. The bitwise logical operator `&` can give rise to this diagnostic when it is mistakenly used in place of the logical operator `&&`:

```
if ((c = getchar()) != EOF & c != '0')
```

4.6.1.3 Questionable Constructs

`lint` flags a miscellany of legal constructs that may not represent what the programmer intended. Examples:

- An unsigned variable always has a nonnegative value. So the test:

```
unsigned x;
if (x < 0) ...
```

always fails. The test:

```
unsigned x;  
if (x > 0) ...
```

is equivalent to:

```
if (x != 0) ...
```

This may not be the intended action. `lint` flags questionable comparisons of unsigned variables with negative constants or 0. To compare an unsigned variable to the bit pattern of a negative number, cast it to unsigned:

```
if (u == (unsigned) -1) ...
```

Or use the `U` suffix:

```
if (u == -1U) ...
```

- `lint` flags expressions without side effects that are used in a context where side effects are expected—that is, where the expression may not represent what the programmer intends. It issues an additional warning whenever the equality operator is found where the assignment operator is expected—that is, where a side effect is expected:

```
int fun()  
{  
    int a, b, x, y;  
    (a = x) && (b == y);  
}
```

- `lint` cautions you to parenthesize expressions that mix both the logical and bitwise operators (specifically, `&`, `|`, `^`, `<<`, `>>`), where misunderstanding of operator precedence may lead to incorrect results. Because the precedence of bitwise `&`, for example, falls below logical `==`, the expression:

```
if (x & a == 0) ...
```

is evaluated as:

```
if (x & (a == 0)) ...
```

which is most likely not what you intended. Invoking `lint` with `-h` disables the diagnostic.

4.6.2 lint Libraries

You can use `lint` libraries to check your program for compatibility with the library functions you have called in it—the declaration of the function return type, the number and types of arguments the function expects, and so on. The standard `lint` libraries correspond to libraries supplied by the C compilation system, and generally are stored in a standard place on your system. By convention, `lint` libraries have names of the form `llib-lx.ln`.

The `lint` standard C library, `llib-lc.ln`, is appended to the `lint` command line by default; checks for compatibility with it can be suppressed by invoking the `-n` option. Other `lint` libraries are accessed as arguments to `-l`. That is:

```
% lint -lx file1.c file2.c
```

directs `lint` to check the usage of functions and variables in `file1.c` and `file2.c` for compatibility with the `lint` library `llib-lx.ln`. The library file, which consists only of definitions, is processed exactly as are ordinary source files and ordinary `.ln` files, except that functions and variables used inconsistently in the library file, or defined in the library file but not used in the source files, elicit no complaints.

To create your own `lint` library, insert the directive `NOTE(LINTLIBRARY)` at the head of a C source file, then invoke `lint` for that file with the `-o` option and the library name given to `-l`:

```
% lint -ox file1.c file2.c
```

causes only definitions in the source files headed by `NOTE(LINTLIBRARY)` to be written to the file `llib-lx.ln`. (Note the analogy of `lint -o` to `cc -o`.) A library can be created from a file of function prototype declarations in the same way, except that both `NOTE(LINTLIBRARY)` and `NOTE(PROTOLIB(n))` must be inserted at the head of the declarations file. If *n* is 1, prototype declarations are written to a library

.ln file just as are old-style definitions. If *n* is 0, the default, the process is cancelled. Invoking `lint` with `-y` is another way of creating a `lint` library. The command line:

```
% lint -y -ox file1.c file2.c
```

causes each source file named on that line to be treated as if it begins with `NOTE(LINTLIBRARY)`, and only its definitions to be written to `llib-lx.ln`.

By default, `lint` searches for `lint` libraries in the standard place. To direct `lint` to search for a `lint` library in a directory other than the standard place, specify the path of the directory with the `-L` option:

```
% lint -Ldir -lx file1.c file2.c
```

In enhanced mode, `lint` produces .ln files which store additional information than .ln files produced in basic mode. In enhanced mode, `lint` can read and understand all .ln files generated by either basic or enhanced `lint` modes. In basic mode, `lint` can read and understand .ln files generated only using basic `lint` mode.

By default, `lint` uses libraries from the `/usr/lib` directory. These libraries are in the basic `lint` format. You can run a `makefile` once, and create enhanced `lint` libraries in a new format, which will enable enhanced `lint` to work more effectively. To run the `makefile` and create the new libraries, enter the command:

```
% cd /opt/SUNWspro/prod/src/lintlib; make
```

where `/opt/SUNWspro/prod` is the installation directory. After the `makefile` is run, `lint` uses the new libraries in enhanced mode, instead of the libraries in the `/usr/lib` directory.

The specified directory is searched before the standard place.

4.6.3 lint Filters

A `lint` filter is a project-specific post-processor that typically uses an `awk` script or similar program to read the output of `lint` and discard messages that your project has deemed as *not* identifying real problems—string functions, for instance, returning values that are sometimes or always ignored. `lint` filters generate customized diagnostic reports when `lint` options and directives do not provide sufficient control over output.

Two options to `lint` are particularly useful in developing a filter:

- Invoking `lint` with `-s` causes compound diagnostics to be converted into simple, one-line messages issued for each occurrence of the problem diagnosed. The easily parsed message format is suitable for analysis by an `awk` script.
- Invoking `lint` with `-k` causes certain comments you have written in the source file to be printed in output, and can be useful both in documenting project decisions and specifying the post-processor's behavior. In the latter instance, if the comment identifies an expected `lint` message, and the reported message is the same, the message can be filtered out. To use `-k`, insert on the line preceding the code you wish to comment the `NOTE(LINTED(msg))` directive, where `msg` refers to the comment to be printed when `lint` is invoked with `-k`.

Refer to the list of directives in [TABLE 4-9](#) for an explanation of what `lint` does when `-k` is *not* invoked for a file containing `NOTE(LINTED(msg))`.

Type-Based Alias Analysis

This document explains how to use the `-xalias_level` option and several pragmas to enable the compiler to perform type-based alias analysis and optimizations. You use these extensions to express type-based information about the way pointers are used in your C program. The C compiler uses this information, in turn, to do a significantly better job of alias disambiguation for pointer-based memory references in your program.

See [Section B.2.65, “-xalias_level\[=l\]” on page B-26](#) for a detailed explanation of this command’s syntax. Also, see [Section 4.3.37, “-xalias_level\[=l\]” on page 4-16](#) for an explanation of the `lint` program’s type-based alias-analysis capabilities.

5.1 Introduction to Type-Based Analysis

You can use the `-xalias_level` option to specify one of seven alias levels. Each level specifies a certain set of properties about the way you use pointers in your C program.

As you compile with higher levels of the `-xalias_level` option, the compiler makes increasingly extensive assumptions about the pointers in your code. You have greater programming freedom when the compiler makes fewer assumptions. However, the optimizations that result from these narrow assumptions may not result in significant runtime performance improvement. If you code in accordance with the compiler assumptions of the more advanced levels of the `-xalias_level` option, there is a greater chance that the resulting optimizations will enhance runtime performance.

The `-xalias_level` option specifies which alias level applies to each translation unit. For cases where more detail is beneficial, you can use new pragmas to override whatever alias levels are in effect so that you can explicitly specify the aliasing relationships between individual types or pointer variables in the translation unit.

These pragmas are most useful when the pointer usage in a translation unit is covered by one of the available alias levels, but a few specific pointer variables are used in an irregular way that is not allowed by one of the available levels.

5.2 Using Pragmas for Finer Control

For cases in which type-based analysis can benefit from more detail, you can use the following pragmas to override the alias level in effect and specify the aliasing relationships between individual types or pointer variables in the translation unit. These pragmas provide the most benefit when the use of pointers in a translation unit is consistent with one of the available alias levels, but a few specific pointer variables are used in an irregular way not allowed by one of the available levels.

Note – You must declare the named type or variable prior to the pragma or a warning message is issued and the pragma is ignored. The results of the program are undefined if the pragma appears after the first memory reference to which its meaning applies.

The following terms are used in the pragma definitions.

Term	Meaning
<i>level</i>	Any of the alias levels listed under Section B.2.65 , “ <code>-xalias_level[=l]</code> ” on page B-26.
<i>type</i>	Any of the following: <ul style="list-style-type: none">• <code>char</code>, <code>short</code>, <code>int</code>, <code>long</code>, <code>long long</code>, <code>float</code>, <code>double</code>, <code>long double</code>• <code>void</code>, which denotes all pointer types• <code>typedef name</code>, which is the name of a defined type from a <code>typedef</code> declaration• <code>struct name</code>, which is the keyword <code>struct</code> followed by a <i>struct tag name</i>• <code>union</code>, which is the keyword <code>union</code> followed by a <i>union tag name</i>
<i>pointer_name</i>	The name of any variable of pointer type in the translation unit.

5.2.0.1 `#pragma alias_level level (list)`

Replace *level* with one of the seven alias levels: *any*, *basic*, *weak*, *layout*, *strict*, *std*, or *strong*. You can replace *list* with either a single type or a comma-delimited list of types, or you can replace *list* with either a single pointer or a comma-delimited list of pointers. For example, you can issue `#pragma alias_level` as follows:

- `#pragma alias_level level (type [, type])`
- `#pragma alias_level level (pointer [, pointer])`

This pragma specifies that the indicated alias level applies either to all of the memory references of the translation unit for the listed types, or to all of the dereferences of the translation unit where any of the named pointer variables are being dereferenced.

If you specify more than one alias level to be applied to a particular dereference, the level that is applied by the pointer name, if any, has precedence over all other levels. The level applied by the type name, if any, has precedence over the level applied by the option. In the following example, the *std* level applies to *p* if the program is compiled with `#pragma alias_level` set higher than *any*.

```
typedef int * int_ptr;
int_ptr p;
#pragma alias_level strong (int_ptr)
#pragma alias_level std (p)
```

5.2.0.2 `#pragma alias (type, type [, type]...)`

This pragma specifies that all the listed types alias each other. In the following example, the compiler assumes that the indirect access `*pt` aliases the indirect access `*pf`.

```
#pragma alias (int, float)
int *pt;
float *pf;
```

5.2.0.3 `#pragma alias (pointer, pointer [, pointer]...)`

This pragma specifies that at the point of any dereference of any of the named pointer variables, the pointer value being dereferenced can point to the same object as any of the other named pointer variables. However, the pointer is not limited to only the objects contained in the named variables and can point to objects that are

not included in the list. This pragma overrides the aliasing assumptions of any applied alias levels. In the following example, any indirect accesses of `p` and `q` after the pragma are considered to alias regardless of their type.

```
#pragma alias(p, q)
```

5.2.0.4 `#pragma may_point_to` (pointer, variable [, variable]...)

This pragma specifies that at the point of any dereference of the named pointer variable, the pointer value being dereferenced can point to the objects that are contained in any of the named variables. However, the pointer is not limited to only the objects contained in the named variables and can point to objects that are not included in the list. This pragma overrides the aliasing assumptions of any applied alias levels. In the following example, the compiler assumes that any indirect access of `*p`, aliases any direct accesses `a`, `b`, and `c`.

```
#pragma alias may_point_to(p, a, b, c)
```

5.2.0.5 `#pragma noalias` (type, type [, type]...)

This pragma specifies that the listed types do not alias each other. In the following example, the compiler assumes that any indirect access of `*p` does not alias the indirect access `*ps`.

```
struct S {
    float f;
    ...} *ps;

#pragma noalias(int, struct S)
int *p;
```

5.2.0.6 `#pragma noalias` (pointer, pointer [, pointer]...)

This pragma specifies that at the point of any dereference of any of the named pointer variables, the pointer value being dereferenced does not point to the same object as any of the other named pointer variables. This pragma overrides all other

applied alias levels. In the following example, the compiler assumes that any indirect access of `*p` does not alias the indirect access `*q` regardless of the types of the two pointers.

```
#pragma noalias(p, q)
```

5.2.0.7 `#pragma may_not_point_to` (pointer, variable [, variable]...)

This pragma specifies that at the point of any dereference of the named pointer variable, the pointer value being dereferenced does not point to the objects that are contained in any of the named variables. This pragma overrides all other applied alias levels. In the following example, the compiler assumes that any indirect access of `*p` does not alias the direct accesses `a`, `b`, or `c`.

```
#pragma may_not_point_to(p, a, b, c)
```

5.3 Checking With `lint`

The `lint` program recognizes the same levels of type-based alias-disambiguation as the compiler's `-xalias_level` command. The `lint` program also recognizes the pragmas related to type-based alias-disambiguation documented in this chapter. For a detailed explanation of the `lint -xalias_level` command, see [Section 4.3.37](#), "`-xalias_level [=l]`" on page 4-16.

There are four situations that `lint` detects and for which it generates warnings:

- Casting a scalar pointer to a struct pointer
- Casting a void pointer to a struct pointer
- Casting a structure field to a scalar pointer
- Casting a struct pointer to a struct pointer at the level of `-xalias_level=strict` without explicit aliasing.

5.3.1 Struct Pointer Cast of Scalar Pointer

In the following example, the pointer `p` of type `integer` is cast as a pointer of type `struct foo`. With lint `-Xalias_level=weak` (or higher), this generates an error.

```
struct foo {
    int a;
    int b;
};

struct foo *f;
int *p;

void main()
{
    f = (struct foo *)p; /* struct pointer cast of scalar pointer
error */
}
```

5.3.2 Struct Pointer Cast of Void Pointer

In the following example, the void pointer `vp`, is cast as a struct pointer. With lint `-Xalias_level=weak` (or higher), this generates a warning.

```
struct foo {
    int a;
    int b;
};

struct foo *f;
void *vp;

void main()
{
    f = (struct foo *)vp; /* struct pointer cast of void pointer
error */
}
```

5.3.3 Cast of Struct Field to Structure Pointer

In the following example, the address of structure member `foo.b` is being cast as a struct pointer and then assigned to `p`. With lint `-Xalias_level=weak` (or higher), this generates a warning.

```
struct foo p{
    int a;
    int b;
};

struct foo *f1;
struct foo *f2;

void main()
{
    f2 = (struct foo *)&f1->b; /* cast of a scalar pointer to
    struct pointer error*/
}
```

5.3.4 Explicit Aliasing Required

In the following example, the pointer `f1` of type `struct fooa` is being cast as a pointer of type `struct foob`. With lint `-Xalias_level=strict` (or higher) such a cast requires explicit aliasing, unless the struct types are identical (the same number of fields of the same type). In addition, at alias levels `standard` and `strong`, the

assumptions is that the tags must match for aliasing to occur. Use `#pragma alias (struct fooa, struct foob)` before the assignment to `f1` and lint stops generating the warning.

```
struct fooa {
    int a;
};

struct foob {
    int b;
};

struct fooa *f1;
struct foob *f2;

void main()
{
    f1 = (struct fooa *)f2; /* explicit aliasing required warning
*/
}
```

5.4 Examples of Memory Reference Constraints

This section provides examples of code that are likely to appear in your source files. Each example is followed by a discussion of the compiler's assumptions about the code as dictated by the applied level of type-based analysis.

Consider the following code. It can be compiled with different levels of aliasing to demonstrate the aliasing relationship of the shown types.

CODE EXAMPLE 5-1

```
struct foo {
    int f1;
    short f2;
    short f3;
    int f4;
} *fp;

struct bar {
    int b1;
    int b2;
    int b3;
} *bp;

int *ip;
short *sp;
```

If [CODE EXAMPLE 5-1](#) is compiled with the `-xalias_level=any` option, the compiler considers the following indirect accesses as aliases to each other:

`*ip, *sp, *fp, *bp, fp->f1, fp->f2, fp->f3, fp->f4, bp->b1, bp->b2, bp->b3`

If [CODE EXAMPLE 5-1](#) is compiled with the `-xalias_level=basic` option, the compiler considers the following indirect accesses as aliases to each other:

`*ip, *bp, fp->f1, fp->f4, bp->b1, bp->b2, bp->b3`

Additionally, `*sp, fp->f2, and fp->f3` can alias each other, and `*sp` and `*fp` can alias each other.

However, under `-xalias_level=basic`, the compiler assumes the following:

- `*ip` does not alias `*sp`.
- `*ip` does not alias `fp->f2` and `fp->f3`.
- `*sp` does not alias `fp->f1, fp->f4, bp->b1, bp->b2, and bp->b3`.

The compiler makes these assumptions because the access types of the two indirect accesses are different basic types.

If [CODE EXAMPLE 5-1](#) is compiled with the `-xalias_level=weak` option, the compiler assumes the following alias information:

- `*ip` can alias `*fp, fp->f1, fp->f4, *bp, bp->b1, bp->b2, and bp->b3`.
- `*sp` can alias `*fp, fp->f2 and fp->f3`.
- `fp->f1` can alias `bp->b1`.
- `fp->f4` can alias `bp->b3`.

The compiler assumes that `fp->fp1` does not alias `bp->b2` because `f1` is a field with offset 0 in a structure, whereas `b2` is a field with a 4-byte offset in a structure. Similarly, the compiler assumes that `fp->f1` does not alias `bp->b3`, and `fp->f4` does not alias either `bp->b1` or `bp->b2`.

If [CODE EXAMPLE 5-1](#) is compiled with the `-xalias_level=layout` option, the compiler assumes the following information:

- `*ip` can alias `*fp`, `*bp`, `fp->f1`, `fp->f4`, `bp->b1`, `bp->b2`, and `bp->b3`.
- `*sp` can alias `*fp`, `fp->f2`, and `fp->f3`.
- `fp->f1` can alias `bp->b1` and `*bp`.
- `*fp` and `*bp` can alias each other.

`fp->f4` does not alias `bp->b3` because `f4` and `b3` are not corresponding fields in the common initial sequence of `foo` and `bar`.

If [CODE EXAMPLE 5-1](#) is compiled with the `-xalias_level=strict` option, the compiler assumes the following alias information:

- `*ip` can alias `*fp`, `fp->f1`, `fp->f4`, `*bp`, `bp->b1`, `bp->b2`, and `bp->b3`.
- `*sp` can alias `*fp`, `fp->f2`, and `fp->f3`.

With `-xalias_level=strict`, the compiler assumes that `*fp`, `*bp`, `fp->f1`, `fp->f2`, `fp->f3`, `fp->f4`, `bp->b1`, `bp->b2`, and `bp->b3` do not alias each other because `foo` and `bar` are not the same when field names are ignored. However, `fp` aliases `fp->f1` and `bp` aliases `bp->b1`.

If [CODE EXAMPLE 5-1](#) is compiled with the `-xalias_level=std` option, the compiler assumes the following alias information:

- `*ip` can alias `*fp`, `fp->f1`, `fp->f4`, `*bp`, `bp->b1`, `bp->b2`, and `bp->b3`.
- `*sp` can alias `*fp`, `fp->f2`, and `fp->f3`.

However, `fp->f1` does not alias `bp->b1`, `bp->b2`, or `bp->b3` because `foo` and `bar` are not the same when field names are considered.

If [CODE EXAMPLE 5-1](#) is compiled with the `-xalias_level=strong` option, the compiler assumes the following alias information:

- `*ip` does not alias `fp->f1`, `fp->f4`, `bp->b1`, `bp->b2`, and `bp->b3` because a pointer, such as `*ip`, should not point to the interior of a structure.
- Similarly, `*sp` does not alias `fp->f1` or `fp->f3`.
- `*ip` does not alias `*fp`, `*bp`, and `*sp` due to differing types.
- `*sp` does not alias `*fp`, `*bp`, and `*ip` due to differing types.

Consider the following example source code. It demonstrates the aliasing relationship of the shown types when compiled with different levels of aliasing.

CODE EXAMPLE 5-2

```
struct foo {
    int f1;
    int f2;
    int f3;
} *fp;

struct bar {
    int b1;
    int b2;
    int b3;
} *bp;
```

If [CODE EXAMPLE 5-2](#) is compiled with the `-xalias_level=any` option, the compiler assumes the following alias information:

`*fp`, `*bp`, `fp->f1`, `fp->f2`, `fp->f3`, `bp->b1`, `bp->b2` and `bp->b3` all can alias each other because any two memory accesses alias each other at the level of `-xalias_level=any`.

If [CODE EXAMPLE 5-2](#) is compiled with the `-xalias_level=basic` option, the compiler assumes the following alias information:

`*fp`, `*bp`, `fp->f1`, `fp->f2`, `fp->f3`, `bp->b1`, `bp->b2` and `bp->b3` all can alias each other. Any two field accesses using pointers `*fp` and `*bp` can alias each other in this example because all the structure fields are the same basic type.

If [CODE EXAMPLE 5-2](#) is compiled with the `-xalias_level=weak` option, the compiler assumes the following alias information:

- `*fp` and `*fp` can alias each other.
- `fp->f1` can alias `bp->b1`, `*bp` and `*fp`.
- `fp->f2` can alias `bp->b2`, `*bp` and `*fp`.
- `fp->f3` can alias `bp->b3`, `*bp` and `*fp`.

However, `-xalias_level=weak` imposes the following restrictions:

- `fp->f1` does not alias `bp->b2` or `bp->b3` because `f1` has an offset of zero, which is different from that of `b2` (four bytes) and `b3` (eight bytes).
- `fp->f2` does not alias `bp->b1` or `bp->b3` because `f2` has an offset of four bytes, which is different from `b1` (zero bytes) and `b3` (eight bytes).
- `fp->f3` does not alias `bp->b1` or `bp->b2` because `f3` has an offset of eight bytes, which is different from `b1` (zero bytes) and `b2` (four bytes).

If [CODE EXAMPLE 5-2](#) is compiled with the `-xalias_level=layout` options, the compiler assumes the following alias information:

- *fp and *bp can alias each other.
- fp->f1 can alias bp->b1, *bp, and *fp.
- fp->f2 can alias bp->b2, *bp, and *fp.
- fp->f3 can alias bp->b3, *bp, and *fp.

However, `-xalias_level=layout` imposes the following restrictions:

- fp->f1 does not alias bp->b2 or bp->b3 because field f1 corresponds to field b1 in the common initial sequence of `foo` and `bar`.
- fp->f2 does not alias bp->b1 or bp->b3 because f2 corresponds to field b2 in the common initial sequence of `foo` and `bar`.
- fp->f3 does not alias bp->b1 or bp->b2 because f3 corresponds to field b3 in the common initial sequence of `foo` and `bar`.

If [CODE EXAMPLE 5-2](#) is compiled with the `-xalias_level=strict` option, the compiler assumes the following alias information:

- *fp and *bp can alias each other.
- fp->f1 can alias bp->b1, *bp, and *fp.
- fp->f2 can alias bp->b2, *bp, and *fp.
- fp->f3 can alias bp->b3, *bp, and *fp.

However, `-xalias_level=strict` imposes the following restrictions:

- fp->f1 does not alias bp->b2 or bp->b3 because field f1 corresponds to field b1 in the common initial sequence of `foo` and `bar`.
- fp->f2 does not alias bp->b1 or bp->b3 because f2 corresponds to field b2 in the common initial sequence of `foo` and `bar`.
- fp->f3 does not alias bp->b1 or bp->b2 because f3 corresponds to field b3 in the common initial sequence of `foo` and `bar`.

If [CODE EXAMPLE 5-2](#) is compiled with the `-xalias_level=std` option, the compiler assumes the following alias information:

fp->f1, fp->f2, fp->f3, bp->b1, bp->b2, and bp->b3 do not alias each other.

If [CODE EXAMPLE 5-2](#) is compiled with the `-xalias_level=strong` option, the compiler assumes the following alias information:

fp->f1, fp->f2, fp->f3, bp->b1, bp->b2, and bp->b3 do not alias each other.

Consider the following example source code that demonstrates that certain levels of aliasing cannot handle interior pointers. For a definition of interior pointers see [TABLE B-11](#).

CODE EXAMPLE 5-3

```
struct foo {
    int f1;
    struct bar *f2;
    struct bar *f3;
    int f4;
    int f5;
    struct bar fb[10];
} *fp;

struct bar
    struct bar *b2;
    struct bar *b3;
    int b4;
} *bp;

bp=(struct bar*) (&fp->f2);
```

The dereference in [CODE EXAMPLE 5-3](#) is not supported by `weak`, `layout`, `strict`, or `std`. After the pointer assignment `bp=(struct bar*) (&fp->f2)`, the following pair of memory accesses touches the same memory locations:

- `fp->f2` and `bp->b2` access the same memory location
- `fp->f3` and `bp->b3` access the same memory location
- `fp->f4` and `bp->b4` access the same memory location

However, under options `weak`, `layout`, `strict`, and `std`, the compiler assumes that `fp->f2` and `bp->b2` do not alias. The compiler makes this assumption because `b2` has an offset of zero, which is different from the offset of `f2` (four bytes), and `foo` and `bar` do not have a common initial sequence. Similarly, the compiler also assumes that `bp->b3` does not alias `fp->f3`, and `bp->b4` does not alias `fp->f4`.

Thus, the pointer assignment `bp=(struct bar*) (&fp->f2)` creates a situation in which the compiler's assumptions about alias information are incorrect. This may lead to incorrect optimization.

Try compiling after you make the modifications shown in the following example.

```
struct foo {
    int f1;
    struct bar fb; /* Modified line */
#define f2 fb.b2 /* Modified line */
#define f3 fb.b3 /* Modified line */
#define f4 fb.b4 /* Modified line */
    int f5;
    struct bar fb[10];
} *fp;

struct bar
    struct bar *b2;
    struct bar *b3;
    int b4;
} *bp;

bp=(struct bar*)&fp->f2;
```

After the pointer assignment `bp=(struct bar*)&fp->f2`, the following pair of memory accesses touches the same memory locations:

- `fp->f2` and `bp->b2`
- `fp->f3` and `bp->b3`
- `fp->f4` and `bp->b4`

By examining the changes shown in the preceding code example, you can see that the expression `fp->f2` is another form of the expression `fp->fb.b2`. Because `fp->fb` is of type `bar`, `fp->f2` accesses the `b2` field of `bar`. Furthermore, `bp->b2` also accesses the `b2` field of `bar`. Therefore, the compiler assumes that `fp->f2` aliases `bp->b2`. Similarly, the compiler assumes that `fp->f3` aliases `bp->b3`, and `fp->f4` aliases `bp->b4`. As a result, the aliasing assumed by the compiler matches the actual aliases caused by the pointer assignment.

Consider the following example source code.

CODE EXAMPLE 5-4

```
struct foo {
    int f1;
    int f2;
} *fp;

struct bar {
    int b1;
    int b2;
} *bp;

struct cat {
    int c1;
    struct foo cf;
    int c2;
    int c3;
} *cp;

struct dog {
    int d1;
    int d2;
    struct bar db;
    int d3;
} *dp;
```

If [CODE EXAMPLE 5-4](#) is compiled with the `-xalias_level=weak` option, the compiler assumes the following alias information:

- `fp->f1` can alias `bp->b1`, `cp->c1`, `dp->d1`, `cp->cf.f1`, and `df->db.b1`.
 - `fp->f2` can alias `bp->b2`, `cp->cf.f1`, `dp->d2`, `cp->cf.f2`, `df->db.b2`, `cp->c2`.
 - `bp->b1` can alias `fp->f1`, `cp->c1`, `dp->d1`, `cp->cf.f1`, and `df->db.b1`.
 - `bp->b2` can alias `fp->f2`, `cp->cf.f1`, `dp->d2`, `cp->cf.f1`, and `df->db.b2`.
- `fp->f2` can alias `cp->c2` because `*dp` can alias `*cp` and `*fp` can alias `dp->db`.
- `cp->c1` can alias `fp->f1`, `bp->b1`, `dp->d1`, and `dp->db.b1`.
 - `cp->cf.f1` can alias `fp->f1`, `fp->f2`, `bp->b1`, `bp->b2`, `dp->d2`, and `dp->d1`.
- `cp->cf.f1` does not alias `dp->db.b1`.
- `cp->cf.f2` can alias `fp->f2`, `bp->b2`, `dp->db.b1`, and `dp->d2`.
 - `cp->c2` can alias `dp->db.b2`.
- `cp->c2` does not alias `dp->db.b1` and `cp->c2` does not alias `dp->d3`.

With respect to offsets, `cp->c2` can alias `db->db.b1` only if `*dp` aliases `cp->cf`. However, if `*dp` aliases `cp->cf`, then `dp->db.b1` must alias beyond the end of `f00cf`, which is prohibited by object restrictions. Therefore, the compiler assumes that `cp->c2` cannot alias `db->db.b1`.

`cp->c3` can alias `dp->d3`.

Notice that `cp->c3` does not alias `dp->db.b2`. These memory references do not alias because the offsets of the fields of the types involved in the dereferences differ and do not overlap. Based on this, the compiler assumes they cannot alias.

- `dp->d1` can alias `fp->f1`, `bp->b1`, and `cp->c1`.
- `dp->d2` can alias `fp->f2`, `bp->b2`, and `cp->cf.f1`.
- `dp->db.b1` can alias `fp->f1`, `bp->b1`, and `cp->c1`.
- `dp->db.b2` can alias `fp->f2`, `bp->b2`, `cp->c2`, and `cp->cf.f1`.
- `dp->d3` can alias `cp->c3`.

Notice that `dp->d3` does not alias `cp->cf.f2`. These memory references do not alias because the offsets of the fields of the types involved in the dereferences differ and do not overlap. Based on this, the compiler assumes they cannot alias.

If [CODE EXAMPLE 5-4](#) is compiled with the `-xalias_level=layout` option, the compiler assumes only the following alias information:

- `fp->f1`, `bp->b1`, `cp->c1` and `dp->d1` all can alias each other.
- `fp->f2`, `bp->b2` and `dp->d2` all can alias each other.
- `fp->f1` can alias `cp->cf.f1` and `dp->db.b1`.
- `bp->b1` can alias `cp->cf.f1` and `dp->db.b1`.
- `fp->f2` can alias `cp->cf.f2` and `dp->db.b2`.
- `bp->b2` can alias `cp->cf.f2` and `dp->db.b2`.

If [CODE EXAMPLE 5-4](#) is compiled with the `-xalias_level=strict` option, the compiler assumes only the following alias information:

- `fp->f1` and `bp->b1` can alias each other.
- `fp->f2` and `bp->b2` can alias each other.
- `fp->f1` can alias `cp->cf.f1` and `dp->db.b1`.
- `bp->b1` can alias `cp->cf.f1` and `dp->db.b1`.
- `fp->f2` can alias `cp->cf.f2` and `dp->db.b2`.
- `bp->b2` can alias `cp->cf.f2` and `dp->db.b2`.

If [CODE EXAMPLE 5-4](#) is compiled with the `-xalias_level=std` option, the compiler assumes only the following alias information:

- `fp->f1` can alias `cp->cf.f1`.
- `bp->b1` can alias `dp->db.b1`.
- `fp->f2` can alias `cp->cf.f2`.
- `bp->b2` can alias `dp->db.b2`.

Consider the following example source code.

CODE EXAMPLE 5-5

```
struct foo {
    short f1;
    short f2;
    int f3;
} *fp;

struct bar {
    int b1;
    int b2;
} *bp;

union moo {
    struct foo u_f;
    struct bar u_b;
} u;
```

Here are the compiler's assumptions based on the following alias levels:

- If [CODE EXAMPLE 5-5](#) is compiled with the `-xalias_level=weak` option, `fp->f3` and `bp->b2` can alias each other.
- If [CODE EXAMPLE 5-5](#) is compiled with the `-xalias_level=layout` option, no fields can alias each other.
- If [CODE EXAMPLE 5-5](#) is compiled with the `-xalias_level=strict` option, `fp->f3` and `bp->b2` can alias each other.
- If [CODE EXAMPLE 5-5](#) is compiled with the `-xalias_level=std` option, no fields can alias each other.

Consider the following example source code.

CODE EXAMPLE 5-6

```
struct bar;

struct foo {
    struct foo *ffp;
    struct bar *fbp;
} *fp;

struct bar {
    struct bar *bbp;
    long b2;
} *bp;
```

Here are the compiler's assumptions based on the following alias levels:

- If [CODE EXAMPLE 5-6](#) is compiled with the `-xalias_level=weak` option, only `fp->ffp` and `bp->bbp` can alias each other.
- If [CODE EXAMPLE 5-6](#) is compiled with the `-xalias_level=layout` option, only `fp->ffp` and `bp->bbp` can alias each other.
- If [CODE EXAMPLE 5-6](#) is compiled with the `-xalias_level=strict` option, no fields can alias because the two struct types are still different even after their tags are removed.
- If [CODE EXAMPLE 5-6](#) is compiled with the `-xalias_level=std` option, no fields can alias because the two types and the tags are not the same.

Consider the following example source code:

CODE EXAMPLE 5-7

```
struct foo;
struct bar;
#pragma alias (struct foo, struct bar)

struct foo {
    int f1;
    int f2;
} *fp;

struct bar {
    short b1;
    short b2;
    int b3;
} *bp;
```

The pragma in this example tells the compiler that `foo` and `bar` are allowed to alias each other. The compiler makes the following assumptions about alias information:

- `fp->f1` can alias with `bp->b1`, `bp->b2`, and `bp->b3`
- `fp->f2` can alias with `bp->b1`, `bp->b2`, and `bp->b3`

Transitioning to ISO C

This chapter provides information which you can use to help you port applications for K&R style C to conform with 9899:1990 ISO/IEC C standard. The information is presented under the assumption that you are using `-xc99=none` because you do not want to conform with the newer, 9899:1999 ISO/IEC C standard. The C compiler defaults to `-xc99=all` which supports the 9899:1999 ISO/IEC C standard.

6.1 Basic Modes

The ISO C compiler allows both old-style and new-style C code. The compiler provides varying degrees of compliance to the ISO C standard when you use the following `-X` (note case) options with `-xc99=none`. `-Xa` is the default mode. Note that the compiler's default mode is `-xc99=all`, so its behavior under each of the `-X` options depends on the setting of `-xc99`.

6.1.1 `-XC`

(c = conformance) Maximally conformant ISO C, without K&R C compatibility extensions. The compiler issues errors and warnings for programs that use ISO C constructs.

6.1.2 `-Xa`

ISO C plus K&R C compatibility extensions, with semantic changes required by ISO C. Where K&R C and ISO C specify different semantics for the same construct, the compiler issues warnings about the conflict and uses the ISO C interpretation. This is the default mode.

6.1.3 -Xt

(t = transition) ISO C plus K&R C compatibility extensions, *without* semantic changes required by ISO C. Where K&R C and ISO C specify different semantics for the same construct, the compiler issues warnings about the conflict and uses the K&R C interpretation.

6.1.4 -Xs

(s = K&R C) The compiled language includes all features compatible with ISO K&R C. The compiler warns about all language constructs that have differing behavior between ISO C and K&R C.

6.2 A Mixture of Old- and New-Style Functions

The 1990 ISO C standard's most sweeping change to the language is the function prototype borrowed from the C++ language. By specifying for each function the number and types of its parameters, not only does every regular compile get the benefits of argument and parameter checks (similar to those of `lint`) for each function call, but arguments are automatically converted (just as with an assignment) to the type expected by the function. The 1990 ISO C standard includes rules that govern the mixing of old- and new-style function declarations since there are many, many lines of existing C code that could and should be converted to use prototypes.

6.2.1 Writing New Code

When you write an entirely new program, use new-style function declarations (function prototypes) in headers and new-style function declarations and definitions in other C source files. However, if there is a possibility that someone will port the code to a machine with a pre-ISO C compiler, we suggest you use the macro `__STDC__` (which is defined only for ISO C compilation systems) in both header and source files. Refer to [Section 6.2.3, "Mixing Considerations"](#) on page 6-3 for an example.

An ISO C-conforming compiler must issue a diagnostic whenever two incompatible declarations for the same object or function are in the same scope. If all functions are declared and defined with prototypes, and the appropriate headers are included by the correct source files, all calls should agree with the definition of the functions. This protocol eliminates one of the most common C programming mistakes.

6.2.2 Updating Existing Code

If you have an existing application and want the benefits of function prototypes, there are a number of possibilities for updating, depending on how much of the code you would like to change:

1. Recompile without making any changes.

Even with no coding changes, the compiler warns you about mismatches in parameter type and number when invoked with the `-v` option.

2. Add function prototypes just to the headers.

All calls to global functions are covered.

3. Add function prototypes to the headers and start each source file with function prototypes for its local (static) functions.

All calls to functions are covered, but doing this requires typing the interface for each local function twice in the source file.

4. Change all function declarations and definitions to use function prototypes.

For most programmers, choices 2 and 3 are probably the best cost/benefit compromise. Unfortunately, these options are precisely the ones that require detailed knowledge of the rules for mixing old and new styles.

6.2.3 Mixing Considerations

For function prototype declarations to work with old-style function definitions, both must specify functionally identical interfaces or have *compatible types* using ISO C's terminology.

For functions with varying arguments, there can be no mixing of ISO C's ellipsis notation and the old-style `varargs()` function definition. For functions with a fixed number of parameters, the situation is fairly straightforward: just specify the types of the parameters as they were passed in previous implementations.

In K&R C, each argument was converted just before it was passed to the called function according to the default argument promotions. These promotions specified that all integral types narrower than `int` were promoted to `int` size, and any `float`

argument was promoted to `double`, hence simplifying both the compiler and libraries. Function prototypes are more expressive—the specified parameter type is what is passed to the function.

Thus, if a function prototype is written for an existing (old-style) function definition, there should be no parameters in the function prototype with any of the following types:

<code>char</code>	<code>signed char</code>	<code>unsigned char</code>	<code>float</code>
<code>short</code>	<code>signed short</code>	<code>unsigned short</code>	

There still remain two complications with writing prototypes: `typedef` names and the promotion rules for narrow unsigned types.

If parameters in old-style functions were declared using `typedef` names, such as `off_t` and `ino_t`, it is important to know whether or not the `typedef` name designates a type that is affected by the default argument promotions. For these two, `off_t` is a `long`, so it is appropriate to use in a function prototype; `ino_t` used to be an `unsigned short`, so if it were used in a prototype, the compiler issues a diagnostic because the old-style definition and the prototype specify different and incompatible interfaces.

Just what should be used instead of an `unsigned short` leads us into the final complication. The one biggest incompatibility between K&R C and the 1990 ISO C compiler is the promotion rule for the widening of `unsigned char` and `unsigned short` to an `int` value. (See [Section 6.4, “Promotions: Unsigned Versus Value Preserving” on page 6-9](#).) The parameter type that matches such an old-style parameter depends on the compilation mode used when you compile:

- `-Xs` and `-Xt` should use `unsigned int`
- `-Xa` and `-Xc` should use `int`

The best approach is to change the old-style definition to specify either `int` or `unsigned int` and use the matching type in the function prototype. You can always assign its value to a local variable with the narrower type, if necessary, after you enter the function.

Watch out for the use of `id`'s in prototypes that may be affected by preprocessing. Consider the following example:

```
#define status 23
void my_exit(int status); /* Normally, scope begins */
                          /* and ends with prototype */
```

Do not mix function prototypes with old-style function declarations that contain narrow types.

```
void foo(unsigned char, unsigned short);  
void foo(i, j) unsigned char i; unsigned short j; {...}
```

Appropriate use of `__STDC__` produces a header file that can be used for both the old and new compilers:

```
header.h:  
struct s { /* . . . */ };  
#ifdef __STDC__  
    void errmsg(int, ...);  
    struct s *f(const char *);  
    int g(void);  
#else  
    void errmsg();  
    struct s *f();  
    int g();  
#endif
```

The following function uses prototypes and can still be compiled on an older system:

```
struct s *  
#ifdef __STDC__  
    f(const char *p)  
#else  
    f(p) char *p;  
#endif  
{  
    /* . . . */  
}
```

Here is an updated source file (as with choice 3 above). The local function still uses an old-style definition, but a prototype is included for newer compilers:

```
source.c:
#include "header.h"
    typedef /* . . . */ MyType;
#ifdef __STDC__
    static void del(MyType *);
    /* . . . */
    static void
    del(p)
    MyType *p;
    {
    /* . . . */
    }
    /* . . . */
```

6.3 Functions With Varying Arguments

In previous implementations, you could not specify the parameter types that a function expected, but ISO C encourages you to use prototypes to do just that. To support functions such as `printf()`, the syntax for prototypes includes a special ellipsis (...) terminator. Because an implementation might need to do unusual things to handle a varying number of arguments, ISO C requires that all declarations and the definition of such a function include the ellipsis terminator.

Since there are no names for the “...” part of the parameters, a special set of macros contained in `stdarg.h` gives the function access to these arguments. Earlier versions of such functions had to use similar macros contained in `varargs.h`.

Let us assume that the function we wish to write is an error handler called `errmsg()` that returns `void`, and whose only fixed parameter is an `int` that specifies details about the error message. This parameter can be followed by a file name, a line number, or both, and these are followed by format and arguments, similar to those of `printf()`, that specify the text of the error message.

To allow our example to compile with earlier compilers, we make extensive use of the macro `__STDC__` which is defined only for ISO C compilation systems. Thus, the function's declaration in the appropriate header file is:

```
#ifdef __STDC__
    void errmsg(int code, ...);
#else
    void errmsg();
#endif
```

The file that contains the definition of `errmsg()` is where the old and new styles can get complex. First, the header to include depends on the compilation system:

```
#ifdef __STDC__
#include <stdarg.h>
#else
#include <varargs.h>
#endif
#include <stdio.h>
```

`stdio.h` is included because we call `fprintf()` and `vfprintf()` later.

Next comes the definition for the function. The identifiers `va_alist` and `va_dcl` are part of the old-style `varargs.h` interface.

```
void
#ifdef __STDC__
errmsg(int code, ...)
#else
errmsg(va_alist) va_dcl /* Note: no semicolon! */
#endif
{
    /* more detail below */
}
```

Since the old-style variable argument mechanism did not allow us to specify any fixed parameters, we must arrange for them to be accessed before the varying portion. Also, due to the lack of a name for the “...” part of the parameters, the new `va_start()` macro has a second argument—the name of the parameter that comes just before the “...” terminator.

As an extension, Sun ISO C allows functions to be declared and defined with no fixed parameters, as in:

```
int f(...);
```

For such functions, `va_start()` should be invoked with an empty second argument, as in:

```
va_start(ap,)
```

The following is the body of the function:

```
{
    va_list ap;
    char *fmt;
#ifdef __STDC__
    va_start(ap, code);
#else
    int code;
    va_start(ap);
    /* extract the fixed argument */
    code = va_arg(ap, int);
#endif
    if (code & FILENAME)
        (void)fprintf(stderr, "\\\"%s\\\": ", va_arg(ap, char *));
    if (code & LINENUMBER)
        (void)fprintf(stderr, "%d: ", va_arg(ap, int));
    if (code & WARNING)
        (void)fputs("warning: ", stderr);
    fmt = va_arg(ap, char *);
    (void)vfprintf(stderr, fmt, ap);
    va_end(ap);
}
```

Both the `va_arg()` and `va_end()` macros work the same for the old-style and ISO C versions. Because `va_arg()` changes the value of `ap`, the call to `vfprintf()` cannot be:

```
(void)vfprintf(stderr, va_arg(ap, char *), ap);
```

The definitions for the macros `FILENAME`, `LINENUMBER`, and `WARNING` are presumably contained in the same header as the declaration of `errmsg()`.

A sample call to `errmsg()` could be:

```
errmsg(FILENAME, "<command line>", "cannot open: %s\n",
argv[optind]);
```

6.4 Promotions: Unsigned Versus Value Preserving

The following information appears in the Rationale section that accompanies the 1990 ISO C Standard: “QUIET CHANGE”. A program that depends on unsigned preserving arithmetic conversions will behave differently, probably without complaint. This is considered to be the most serious change made by the Committee to a widespread current practice.

This section explores how this change affects our code.

6.4.1 Background

According to K&R, *The C Programming Language* (First Edition), unsigned specified exactly one type; there were no unsigned chars, unsigned shorts, or unsigned longs, but most C compilers added these very soon thereafter. Some compilers did not implement unsigned long but included the other two. Naturally, implementations chose different rules for type promotions when these new types mixed with others in expressions.

In most C compilers, the simpler rule, “unsigned preserving,” is used: when an unsigned type needs to be widened, it is widened to an unsigned type; when an unsigned type mixes with a signed type, the result is an unsigned type.

The other rule, specified by ISO C, is known as “value preserving,” in which the result type depends on the relative sizes of the operand types. When an unsigned char or unsigned short is widened, the result type is int if an int is large enough to represent all the values of the smaller type. Otherwise, the result type is unsigned int. The value preserving rule produces the least surprise arithmetic result for most expressions.

6.4.2 Compilation Behavior

Only in the transition or ISO modes (-xt or -xs) does the ISO C compiler use the unsigned preserving promotions; in the other two modes, conforming (-xc) and ISO (-xa), the value preserving promotion rules are used.

6.4.3 First Example: The Use of a Cast

In the following code, assume that an unsigned char is smaller than an int.

```
int f(void)
{
    int i = -2;
    unsigned char uc = 1;

    return (i + uc) < 17;
}
```

The code above causes the compiler to issue the following warning when you use the `-xtransition` option:

```
line 6: warning: semantics of "<" change in ISO C; use explicit cast
```

The result of the addition has type `int` (value preserving) or `unsigned int` (unsigned preserving), but the bit pattern does not change between these two. On a two's-complement machine, we have:

```
    i:   111...110 (-2)
+   uc:  000...001 ( 1)
=====
        111...111 (-1 or UINT_MAX)
```

This bit representation corresponds to `-1` for `int` and `UINT_MAX` for `unsigned int`. Thus, if the result has type `int`, a signed comparison is used and the less-than test is true; if the result has type `unsigned int`, an unsigned comparison is used and the less-than test is false.

The addition of a cast serves to specify which of the two behaviors is desired:

```
value preserving:
    (i + (int)uc) < 17
unsigned preserving:
    (i + (unsigned int)uc) < 17
```

Since differing compilers chose different meanings for the same code, this expression can be ambiguous. The addition of a cast is as much to help the reader as it is to eliminate the warning message.

6.4.4 Bit-fields

The same situation applies to the promotion of bit-field values. In ISO C, if the number of bits in an `int` or `unsigned int` bit-field is less than the number of bits in an `int`, the promoted type is `int`; otherwise, the promoted type is `unsigned int`. In most older C compilers, the promoted type is `unsigned int` for explicitly unsigned bit-fields, and `int` otherwise.

Similar use of casts can eliminate situations that are ambiguous.

6.4.5 Second Example: Same Result

In the following code, assume that both `unsigned short` and `unsigned char` are narrower than `int`.

```
int f(void)
{
    unsigned short us;
    unsigned char uc;
    return uc < us;
}
```

In this example, both automatics are either promoted to `int` or to `unsigned int`, so the comparison is sometimes unsigned and sometimes signed. However, the C compiler does not warn you because the result is the same for the two choices.

6.4.6 Integral Constants

As with expressions, the rules for the types of certain integral constants have changed. In K&R C, an unsuffixed decimal constant had type `int` only if its value fit in an `int`; an unsuffixed octal or hexadecimal constant had type `int` only if its value fit in an `unsigned int`. Otherwise, an integral constant had type `long`. At times, the value did not fit in the resulting type. In the 1990 ISO/IEC C standard, the constant type is the first type encountered in the following list that corresponds to the value:

- unsuffixed decimal: `int`, `long`, `unsigned long`
- unsuffixed octal or hexadecimal: `int`, `unsigned int`, `long`, `unsigned long`
- U suffixed: `unsigned int`, `unsigned long`
- L suffixed: `long`, `unsigned long`
- UL suffixed: `unsigned long`

The ISO C compiler warns you, when you use the `-xtransition` option, about any expression whose behavior might change according to the typing rules of the constants involved. The old integral constant typing rules are used only in the transition mode; the ISO and conforming modes use the new rules.

Note – The rules for typing unsuffixed decimal constants has changed in accordance with the 1999 ISO C standard. See [Section 2.1.1, “Integral Constants” on page 2-1](#).

6.4.7 Third Example: Integral Constants

In the following code, assume `ints` are 16 bits.

```
int f(void)
{
    int i = 0;

    return i > 0xffff;
}
```

Because the hexadecimal constant's type is either `int` (with a value of `-1` on a two's-complement machine) or an `unsigned int` (with a value of `65535`), the comparison is true in `-Xs` and `-Xt` modes, and false in `-Xa` and `-Xc` modes.

Again, an appropriate cast clarifies the code and suppresses a warning:

```
-Xt, -Xs modes:
    i > (int)0xffff

-Xa, -Xc modes:
    i > (unsigned int)0xffff
    or
    i > 0xffffU
```

The `U` suffix character is a new feature of ISO C and probably produces an error message with older compilers.

6.5 Tokenization and Preprocessing

Probably the least specified part of previous versions of C concerned the operations that transformed each source file from a bunch of characters into a sequence of tokens, ready to parse. These operations included recognition of white space (including comments), bundling consecutive characters into tokens, handling preprocessing directive lines, and macro replacement. However, their respective ordering was never guaranteed.

6.5.1 ISO C Translation Phases

The order of these translation phases is specified by ISO C.

Every trigraph sequence in the source file is replaced. ISO C has exactly nine trigraph sequences that were invented solely as a concession to deficient character sets, and are three-character sequences that name a character not in the ISO 646-1983 character set:

TABLE 6-1 Trigraph Sequences

Trigraph Sequence	Converts to
??=	#
??-	~
??([
??)]
??!	
??<	{
??>	}
??/	\
??'	^

These sequences must be understood by ISO C compilers, but we do not recommend their use. The ISO C compiler warns you, when you use the `-xtransition` option, whenever it replaces a trigraph while in transition (`-xt`) mode, even in comments. For example, consider the following:

```
/* comment *??/  
/* still comment? */
```

The `??/` becomes a backslash. This character and the following newline are removed. The resulting characters are:

```
/* comment */ /* still comment? */
```

The first `/` from the second line is the end of the comment. The next token is the `*`.

1. Every backslash/new-line character pair is deleted.
2. The source file is converted into preprocessing tokens and sequences of white space. Each comment is effectively replaced by a space character.
3. Every preprocessing directive is handled and all macro invocations are replaced. Each `#included` source file is run through the earlier phases before its contents replace the directive line.
4. Every escape sequence (in character constants and string literals) is interpreted.
5. Adjacent string literals are concatenated.
6. Every preprocessing token is converted into a regular token; the compiler properly parses these and generates code.
7. All external object and function references are resolved, resulting in the final program.

6.5.2 Old C Translation Phases

Previous C compilers did not follow such a simple sequence of phases, nor were there any guarantees for when these steps were applied. A separate preprocessor recognized tokens and white space at essentially the same time as it replaced macros and handled directive lines. The output was then completely retokenized by the compiler proper, which then parsed the language and generated code.

Because the tokenization process within the preprocessor was a moment-by-moment operation and macro replacement was done as a character-based, not token-based, operation, the tokens and white space could have a great deal of variation during preprocessing.

There are a number of differences that arise from these two approaches. The rest of this section discusses how code behavior may change due to line splicing, macro replacement, stringizing, and token pasting, which occur during macro replacement.

6.5.3 Logical Source Lines

In K&R C, backslash/new-line pairs were allowed only as a means to continue a directive, a string literal, or a character constant to the next line. ISO C extended the notion so that a backslash/new-line pair can continue anything to the next line. The result is a logical source line. Therefore, any code that relied on the separate recognition of tokens on either side of a backslash/new-line pair does not behave as expected.

6.5.4 Macro Replacement

The macro replacement process has never been described in detail prior to ISO C. This vagueness spawned a great many divergent implementations. Any code that relied on anything fancier than manifest constant replacement and simple function-like macros was probably not truly portable. This manual cannot uncover all the differences between the old C macro replacement implementation and the ISO C version. Nearly all uses of macro replacement with the exception of token pasting and stringizing produce exactly the same series of tokens as before. Furthermore, the ISO C macro replacement algorithm can do things not possible in the old C version. For example,

```
#define name (*name)
```

causes any use of name to be replaced with an indirect reference through name. The old C preprocessor would produce a huge number of parentheses and stars and eventually produce an error about macro recursion.

The major change in the macro replacement approach taken by ISO C is to require macro arguments, other than those that are operands of the macro substitution operators # and ##, to be expanded recursively prior to their substitution in the replacement token list. However, this change seldom produces an actual difference in the resulting tokens.

6.5.5 Using Strings

Note – In ISO C, the examples below marked with a † produce a warning about use of old features, when you use the `-xtransition` option. Only in the transition mode (`-xt` and `-xs`) is the result the same as in previous versions of C.

In K&R C, the following code produced the string literal `"x y!"`:

```
#define str(a) "a!" †
str(x y)
```

Thus, the preprocessor searched inside string literals and character constants for characters that looked like macro parameters. ISO C recognized the importance of this feature, but could not condone operations on parts of tokens. In ISO C, all invocations of the above macro produce the string literal `"a!"`. To achieve the old effect in ISO C, we make use of the `#` macro substitution operator and the concatenation of string literals.

```
#define str(a) #a "!"
str(x y)
```

The above code produces the two string literals `"x y"` and `"!"` which, after concatenation, produces the identical `"x y!"`.

There is no direct replacement for the analogous operation for character constants. The major use of this feature was similar to the following:

```
#define CNTL(ch) (037 & 'ch') †
CNTL(L)
```

which produced

```
(037 & 'L')
```

which evaluates to the ASCII control-L character. The best solution we know of is to change all uses of this macro to:

```
#define CNTL(ch) (037 & (ch))
CNTL('L')
```


This code is more readable and more useful, as it can also be applied to expressions.

6.5.6 Token Pasting

In K&R C, there were at least two ways to combine two tokens. Both invocations in the following produced a single identifier `x1` out of the two tokens `x` and `1`.

```
#define self(a) a
#define glue(a,b) a/**/b †
self(x)1
glue(x,1)
```

Again, ISO C could not sanction either approach. In ISO C, both the above invocations would produce the two separate tokens `x` and `1`. The second of the above two methods can be rewritten for ISO C by using the `##` macro substitution operator:

```
#define glue(a,b) a ## b
glue(x, 1)
```

`#` and `##` should be used as macro substitution operators only when `__STDC__` is defined. Since `##` is an actual operator, the invocation can be much freer with respect to white space in both the definition and invocation.

There is no direct approach to effect the first of the two old-style pasting schemes, but since it put the burden of the pasting at the invocation, it was used less frequently than the other form.

6.6 `const` and `volatile`

The keyword `const` was one of the C++ features that found its way into ISO C. When an analogous keyword, `volatile`, was invented by the ISO C Committee, the “type qualifier” category was created.

6.6.1 Types, Only for lvalue

`const` and `volatile` are part of an identifier's type, not its storage class. However, they are often removed from the topmost part of the type when an object's value is fetched in the evaluation of an expression—exactly at the point when an lvalue becomes an rvalue. These terms arise from the prototypical assignment "L=R"; in which the left side must still refer directly to an object (an lvalue) and the right side need only be a value (an rvalue). Thus, only expressions that are lvalues can be qualified by `const` or `volatile` or both.

6.6.2 Type Qualifiers in Derived Types

The type qualifiers may modify type names and derived types. Derived types are those parts of C's declarations that can be applied over and over to build more and more complex types: pointers, arrays, functions, structures, and unions. Except for functions, one or both type qualifiers can be used to change the behavior of a derived type.

For example,

```
const int five = 5;
```

declares and initializes an object with type `const int` whose value is not changed by a correct program. The order of the keywords is not significant to C. For example, the declarations:

```
int const five = 5;
```

and

```
const five = 5;
```

are identical to the above declaration in its effect.

The declaration

```
const int *pci = &five;
```

declares an object with type pointer to `const int`, which initially points to the previously declared object. The pointer itself does not have a qualified type—it points to a qualified type, and can be changed to point to essentially any `int` during program execution. `pci` cannot be used to modify the object to which it points unless a cast is used, as in the following:

```
*(int *)pci = 17;
```

If `pci` actually points to a `const` object, the behavior of this code is undefined.

The declaration

```
extern int *const cpi;
```

says that somewhere in the program there exists a definition of a global object with type `const` pointer to `int`. In this case, `cpi`'s value will not be changed by a correct program, but it can be used to modify the object to which it points. Notice that `const` comes after the `*` in the above declaration. The following pair of declarations produces the same effect:

```
typedef int *INT_PTR;  
extern const INT_PTR cpi;
```

These declarations can be combined as in the following declaration in which an object is declared to have type `const` pointer to `const int`:

```
const int *const cpci;
```

6.6.3 `const` Means `readonly`

In hindsight, `readonly` would have been a better choice for a keyword than `const`. If one reads `const` in this manner, declarations such as:

```
char *strcpy(char *, const char *);
```

are easily understood to mean that the second parameter is only used to read character values, while the first parameter overwrites the characters to which it points. Furthermore, despite the fact that in the above example, the type of `cpi` is a

pointer to a `const int`, you can still change the value of the object to which it points through some other means, unless it actually points to an object declared with `const int` type.

6.6.4 Examples of `const` Usage

The two main uses for `const` are to declare large compile-time initialized tables of information as unchanging, and to specify that pointer parameters do not modify the objects to which they point.

The first use potentially allows portions of the data for a program to be shared by other concurrent invocations of the same program. It may cause attempts to modify this invariant data to be detected immediately by means of some sort of memory protection fault, since the data resides in a read-only portion of memory.

The second use helps locate potential errors before generating a memory fault during that demo. For example, functions that temporarily place a null character into the middle of a string are detected at compile time, if passed a pointer to a string that cannot be so modified.

6.6.5 `volatile` Means Exact Semantics

So far, the examples have all used `const` because it's conceptually simpler. But what does `volatile` really mean? To a compiler writer, it has one meaning: take no code generation shortcuts when accessing such an object. In ISO C, it is a programmer's responsibility to declare every object that has the appropriate special properties with a `volatile` qualified type.

6.6.6 Examples of `volatile` Usage

The usual four examples of `volatile` objects are:

- An object that is a memory-mapped I/O port
- An object that is shared between multiple concurrent processes
- An object that is modified by an asynchronous signal handler
- An automatic storage duration object declared in a function that calls `setjmp`, and whose value is changed between the call to `setjmp` and a corresponding call to `longjmp`

The first three examples are all instances of an object with a particular behavior: its value can be modified at any point during the execution of the program. Thus, the seemingly infinite loop:

```
flag = 1;
while (flag);
```

is valid as long as `flag` has a `volatile` qualified type. Presumably, some asynchronous event sets `flag` to zero in the future. Otherwise, because the value of `flag` is unchanged within the body of the loop, the compilation system is free to change the above loop into a truly infinite loop that completely ignores the value of `flag`.

The fourth example, involving variables local to functions that call `setjmp`, is more involved. The fine print about the behavior of `setjmp` and `longjmp` notes that there are no guarantees about the values for objects matching the fourth case. For the most desirable behavior, it is necessary for `longjmp` to examine every stack frame between the function calling `setjmp` and the function calling `longjmp` for saved register values. The possibility of asynchronously created stack frames makes this job even harder.

When an automatic object is declared with a `volatile` qualified type, the compilation system knows that it has to produce code that exactly matches what the programmer wrote. Therefore, the most recent value for such an automatic object is always in memory and not just in a register, and is guaranteed to be up-to-date when `longjmp` is called.

6.7 Multibyte Characters and Wide Characters

At first, the internationalization of ISO C affected only library functions. However, the final stage of internationalization—multibyte characters and wide characters—also affected the language proper.

6.7.1 Asian Languages Require Multibyte Characters

The basic difficulty in an Asian-language computer environment is the huge number of ideograms needed for I/O. To work within the constraints of usual computer architectures, these ideograms are encoded as sequences of bytes. The associated operating systems, application programs, and terminals understand these byte

sequences as individual ideograms. Moreover, all of these encodings allow intermixing of regular single-byte characters with the ideogram byte sequences. Just how difficult it is to recognize distinct ideograms depends on the encoding scheme used.

The term “multibyte character” is defined by ISO C to denote a byte sequence that encodes an ideogram, no matter what encoding scheme is employed. All multibyte characters are members of the “extended character set.” A regular single-byte character is just a special case of a multibyte character. The only requirement placed on the encoding is that no multibyte character can use a null character as part of its encoding.

ISO C specifies that program comments, string literals, character constants, and header names are all sequences of multibyte characters.

6.7.2 Encoding Variations

The encoding schemes fall into two camps. The first is one in which each multibyte character is self-identifying, that is, any multibyte character can simply be inserted between any pair of multibyte characters.

The second scheme is one in which the presence of special shift bytes changes the interpretation of subsequent bytes. An example is the method used by some character terminals to get in and out of line-drawing mode. For programs written in multibyte characters with a shift-state-dependent encoding, ISO C requires that each comment, string literal, character constant, and header name must both begin and end in the unshifted state.

6.7.3 Wide Characters

Some of the inconvenience of handling multibyte characters would be eliminated if all characters were of a uniform number of bytes or bits. Since there can be thousands or tens of thousands of ideograms in such a character set, a 16-bit or 32-bit sized integral value should be used to hold all members. (The full Chinese alphabet includes more than 65,000 ideograms!) ISO C includes the typedef name `wchar_t` as the implementation-defined integral type large enough to hold all members of the extended character set.

For each wide character, there is a corresponding multibyte character, and vice versa; the wide character that corresponds to a regular single-byte character is required to have the same value as its single-byte value, including the null character. However, there is no guarantee that the value of the macro `EOF` can be stored in a `wchar_t`, just as `EOF` might not be representable as a `char`.

6.7.4 Conversion Functions

The 1990 ISO/IEC C standard provides five library functions that manage multibyte characters and wide characters, the 1999 ISO/IEC C standard provides many more such functions.

6.7.5 C Language Features

To give even more flexibility to the programmer in an Asian-language environment, ISO C provides wide character constants and wide string literals. These have the same form as their non-wide versions, except that they are immediately prefixed by the letter L:

- 'x' regular character constant
- 'x' regular character constant
- L'x' wide character constant
- L'x' wide character constant
- "abcxyz" regular string literal
- L"abcxyz" wide string literal

Multibyte characters are valid in both the regular and wide versions. The sequence of bytes necessary to produce the ideogram `xyz` is encoding-specific, but if it consists of more than one byte, the value of the character constant `'xyz'` is implementation-defined, just as the value of `'ab'` is implementation-defined. Except for escape sequences, a regular string literal contains exactly the bytes specified between the quotes, including the bytes of each specified multibyte character.

When the compilation system encounters a wide character constant or wide string literal, each multibyte character is converted into a wide character, as if by calling the `mbtowc()` function. Thus, the type of `L'xyz'` is `wchar_t`; the type of `L"abcxyz"` is array of `wchar_t` with length eight. Just as with regular string literals, each wide string literal has an extra zero-valued element appended, but in these cases, it is a `wchar_t` with value zero.

Just as regular string literals can be used as a shorthand method for character array initialization, wide string literals can be used to initialize `wchar_t` arrays:

```
wchar_t *wp = L"axyz";
wchar_t x[] = L"axyz";
wchar_t y[] = {L'a', L'x', L'z', 0};
wchar_t z[] = {'a', L'x', 'z', '\0'};
```

In the above example, the three arrays `x`, `y`, and `z`, and the array pointed to by `wp`, have the same length. All are initialized with identical values.

Finally, adjacent wide string literals are concatenated, just as with regular string literals. However, with the 1990 ISO/IEC C standard, adjacent regular and wide string literals produce undefined behavior. Also, the 1990 ISO/IEC C standard specifies that a compiler is not required to produce an error if it does not accept such concatenations.

6.8 Standard Headers and Reserved Names

Early in the standardization process, the ISO Standards Committee chose to include library functions, macros, and header files as part of ISO C.

This section presents the various categories of reserved names and some rationale for their reservations. At the end is a set of rules to follow that can steer your programs clear of any reserved names.

6.8.1 Standard Headers

The standard headers are:

TABLE 6-2 Standard Headers

<code>assert.h</code>	<code>locale.h</code>	<code>stddef.h</code>
<code>ctype.h</code>	<code>math.h</code>	<code>stdio.h</code>
<code>errno.h</code>	<code>setjmp.h</code>	<code>stdlib.h</code>
<code>float.h</code>	<code>signal.h</code>	<code>string.h</code>
<code>limits.h</code>	<code>stdarg.h</code>	<code>time.h</code>

Most implementations provide more headers, but a strictly conforming 1990 ISO/IEC C program can only use these.

Other standards disagree slightly regarding the contents of some of these headers. For example, POSIX (IEEE 1003.1) specifies that `fdopen` is declared in `stdio.h`. To allow these two standards to coexist, POSIX requires the macro `_POSIX_SOURCE` to be `#defined` prior to the inclusion of any header to guarantee that these additional names exist. In its *Portability Guide*, X/Open has also used this macro scheme for its extensions. X/Open's macro is `_XOPEN_SOURCE`.

ISO C requires the standard headers to be both self-sufficient and idempotent. No standard header needs any other header to be `#included` before or after it, and each standard header can be `#included` more than once without causing problems. The Standard also requires that its headers be `#included` only in safe contexts, so that the names used in the headers are guaranteed to remain unchanged.

6.8.2 Names Reserved for Implementation Use

The Standard places further restrictions on implementations regarding their libraries. In the past, most programmers learned not to use names like `read` and `write` for their own functions on UNIX Systems. ISO C requires that only names reserved by the Standard be introduced by references within the implementation.

Thus, the Standard reserves a subset of all possible names for implementations to use. This class of names consists of identifiers that begin with an underscore and continue with either another underscore or a capital letter. The class of names contains all names matching the following regular expression:

```
_[_A-Z][0-9_a-zA-Z]*
```

Strictly speaking, if your program uses such an identifier, its behavior is undefined. Thus, programs using `_POSIX_SOURCE` (or `_XOPEN_SOURCE`) have undefined behavior.

However, undefined behavior comes in different degrees. If, in a POSIX-conforming implementation you use `_POSIX_SOURCE`, you know that your program's undefined behavior consists of certain additional names in certain headers, and your program still conforms to an accepted standard. This deliberate loophole in the ISO C standard allows implementations to conform to seemingly incompatible specifications. On the other hand, an implementation that does not conform to the POSIX standard is free to behave in any manner when encountering a name such as `_POSIX_SOURCE`.

The Standard also reserves all other names that begin with an underscore for use in header files as regular file scope identifiers and as tags for structures and unions, but not in local scopes. The common practice of having functions named `_filbuf` and `_doprnt` to implement hidden parts of the library is allowed.

6.8.3 Names Reserved for Expansion

In addition to all the names explicitly reserved, the 1990 ISO/IEC C standard also reserves (for implementations and future standards) names matching certain patterns:

TABLE 6-3 Names Reserved for Expansion

File	Reserved Name Pattern
<code>errno.h</code>	<code>E[0-9A-Z].*</code>
<code>ctype.h</code>	<code>(to is)[a-z].*</code>
<code>locale.h</code>	<code>LC_[A-Z].*</code>
<code>math.h</code>	<i>current function names</i> [<code>fl</code>]
<code>signal.h</code>	<code>(SIG SIG_) [A-Z].*</code>
<code>stdlib.h</code>	<code>str[a-z].*</code>
<code>string.h</code>	<code>(str mem wcs)[a-z].*</code>

In the above lists, names that begin with a capital letter are macros and are reserved only when the associated header is included. The rest of the names designate functions and cannot be used to name any global objects or functions.

6.8.4 Names Safe to Use

There are four simple rules you can follow to keep from colliding with any ISO C reserved names:

- `#include` all system headers at the top of your source files (except possibly after a `#define` of `_POSIX_SOURCE` or `_XOPEN_SOURCE`, or both).
- Do not define or declare any names that begin with an underscore.
- Use an underscore or a capital letter somewhere within the first few characters of all file scope tags and regular names. Beware of the `va_` prefix found in `stdarg.h` or `varargs.h`.
- Use a digit or a non-capital letter somewhere within the first few characters of all macro names. Almost all names beginning with an `E` are reserved if `errno.h` is `#included`.

These rules are just a general guideline to follow, as most implementations will continue to add names to the standard headers by default.

6.9 Internationalization

Section 6.7, “Multibyte Characters and Wide Characters” on page 6-21 introduced the internationalization of the standard libraries. This section discusses the affected library functions and gives some hints on how programs should be written to take advantage of these features. The section only discusses internationalization with respect to the 1990 ISO/IEC C standard. The 1999 ISO/IEC C standard has no significant extension to support internationalization over those discussed here.

6.9.1 Locales

At any time, a C program has a current locale—a collection of information that describes the conventions appropriate to some nationality, culture, and language. Locales have names that are strings. The only two standardized locale names are "C" and "". Each program begins in the "C" locale, which causes all library functions to behave just like they have historically. The "" locale is the implementation’s best guess at the correct set of conventions appropriate to the program’s invocation. "C" and "" can cause identical behavior. Other locales may be provided by implementations.

For the purposes of practicality and expediency, locales are partitioned into a set of categories. A program can change the complete locale, or just one or more categories. Generally, each category affects a set of functions disjoint from the functions affected by other categories, so temporarily changing one category for a little while can make sense.

6.9.2 The `setlocale()` Function

The `setlocale()` function is the interface to the program’s locale. In general, any program that uses the invocation country’s conventions should place a call such as:

```
#include <locale.h>
/*...*/
setlocale(LC_ALL, "");
```

early in the program's execution path. This call causes the program's current locale to change to the appropriate local version, since `LC_ALL` is the macro that specifies the entire locale instead of one category. The following are the standard categories:

<code>LC_COLLATE</code>	sorting information
<code>LC_CTYPE</code>	character classification information
<code>LC_MONETARY</code>	currency printing information
<code>LC_NUMERIC</code>	numeric printing information
<code>LC_TIME</code>	date and time printing information

Any of these macros can be passed as the first argument to `setlocale()` to specify that category.

The `setlocale()` function returns the name of the current locale for a given category (or `LC_ALL`) and serves in an inquiry-only capacity when its second argument is a null pointer. Thus, code similar to the following can be used to change the locale or a portion thereof for a limited duration:

```
#include <locale.h>
/*...*/
char *oloc;
/*...*/
oloc = setlocale(LC_category, NULL);
if (setlocale(LC_category, "new") != 0)
{
    /* use temporarily changed locale */
    (void)setlocale(LC_category, oloc);
}
```

Most programs do not need this capability.

6.9.3 Changed Functions

Wherever possible and appropriate, existing library functions were extended to include locale-dependent behavior. These functions came in two groups:

- Those declared by the `ctype.h` header (character classification and conversion), and
- Those that convert to and from printable and internal forms of numeric values, such as `printf()` and `strtod()`.

All `ctype.h` predicate functions, except `isdigit()` and `isxdigit()`, can return nonzero (true) for additional characters when the `LC_CTYPE` category of the current locale is other than "C". In a Spanish locale, `isalpha('ñ')` should be true. Similarly, the character conversion functions, `tolower()` and `toupper()`, should appropriately handle any extra alphabetic characters identified by the `isalpha()` function. The `ctype.h` functions are almost always macros that are implemented using table lookups indexed by the character argument. Their behavior is changed by resetting the table(s) to the new locale's values, and therefore there is no performance impact.

Those functions that write or interpret printable floating values can change to use a decimal-point character other than period (.) when the `LC_NUMERIC` category of the current locale is other than "C". There is no provision for converting any numeric values to printable form with thousands separator-type characters. When converting from a printable form to an internal form, implementations are allowed to accept such additional forms, again in other than the "C" locale. Those functions that make use of the decimal-point character are the `printf()` and `scanf()` families, `atof()`, and `strtod()`. Those functions that are allowed implementation-defined extensions are `atof()`, `atoi()`, `atol()`, `strtod()`, `strtol()`, `strtoul()`, and the `scanf()` family.

6.9.4 New Functions

Certain locale-dependent capabilities were added as new standard functions. Besides `setlocale()`, which allows control over the locale itself, the Standard includes the following new functions:

<code>localeconv()</code>	numeric/monetary conventions
<code>strcoll()</code>	collation order of two strings
<code>strxfrm()</code>	translate string for collation
<code>strxfrm()</code>	translate string for collation

In addition, there are the multibyte functions `mblen()`, `mbtowc()`, `mbstowcs()`, `wctomb()`, and `wcstombs()`.

The `localeconv()` function returns a pointer to a structure containing information useful for formatting numeric and monetary information appropriate to the current locale's `LC_NUMERIC` and `LC_MONETARY` categories. This is the only function whose behavior depends on more than one category. For numeric values, the structure describes the decimal-point character, the thousands separator, and where the separator(s) should be located. There are fifteen other structure members that describe how to format a monetary value.

The `strcoll()` function is analogous to the `strcmp()` function, except that the two strings are compared according to the `LC_COLLATE` category of the current locale. The `strxfrm()` function can also be used to transform a string into another, such that any two such after-translation strings can be passed to `strcmp()`, and get an ordering analogous to what `strcoll()` would have returned if passed the two pre-translation strings.

The `strftime()` function provides formatting similar to that used with `sprintf()` of the values in a `struct tm`, along with some date and time representations that depend on the `LC_TIME` category of the current locale. This function is based on the `asctime()` function released as part of UNIX System V Release 3.2.

6.10 Grouping and Evaluation in Expressions

One of the choices made by Dennis Ritchie in the design of C was to give compilers a license to rearrange expressions involving adjacent operators that are mathematically commutative and associative, even in the presence of parentheses. This is explicitly noted in the appendix in the *The C Programming Language* by Kernighan and Ritchie. However, ISO C does not grant compilers this same freedom.

This section discusses the differences between these two definitions of C and clarifies the distinctions between an expression's side effects, grouping, and evaluation by considering the expression statement from the following code fragment.

```
int i, *p, f(void), g(void);
/*...*/
i = *++p + f() + g();
```

6.10.1 Definitions

The side effects of an expression are its modifications to memory and its accesses to `volatile` qualified objects. The side effects in the above expression are the updating of `i` and `p` and any side effects contained within the functions `f()` and `g()`.

An expression's grouping is the way values are combined with other values and operators. The above expression's grouping is primarily the order in which the additions are performed.

An expression's evaluation includes everything necessary to produce its resulting value. To evaluate an expression, all specified side effects must occur anywhere between the previous and next sequence point, and the specified operations are performed with a particular grouping. For the above expression, the updating of `i` and `p` must occur after the previous statement and by the `;` of this expression statement; the calls to the functions can occur in either order, any time after the previous statement, but before their return values are used. In particular, the operators that cause memory to be updated have no requirement to assign the new value before the value of the operation is used.

6.10.2 The K&R C Rearrangement License

The K&R C rearrangement license applies to the above expression because addition is mathematically commutative and associative. To distinguish between regular parentheses and the actual grouping of an expression, the left and right curly braces designate grouping. The three possible groupings for the expression are:

```
i = { { *++p + f() } + g() };  
i = { *++p + { f() + g() } };  
i = { { *++p + g() } + f() };
```

All of these are valid given K&R C rules. Moreover, all of these groupings are valid even if the expression were written instead, for example, in either of these ways:

```
i = *++p + ( f() + g() );  
i = ( g() + *++p ) + f();
```

If this expression is evaluated on an architecture for which either overflows cause an exception, or addition and subtraction are not inverses across an overflow, these three groupings behave differently if one of the additions overflows.

For such expressions on these architectures, the only recourse available in K&R C was to split the expression to force a particular grouping. The following are possible rewrites that respectively enforce the above three groupings:

```
i = *++p; i += f(); i += g()  
i = f(); i += g(); i += *++p;  
i = *++p; i += g(); i += f();
```

6.10.3 The ISO C Rules

ISO C does not allow operations to be rearranged that are mathematically commutative and associative, but that are not actually so on the target architecture. Thus, the precedence and associativity of the ISO C grammar completely describes the grouping for all expressions; all expressions must be grouped as they are parsed. The expression under consideration is grouped in this manner:

```
i = { { *++p + f() } + g() };
```

This code still does not mean that `f()` must be called before `g()`, or that `p` must be incremented before `g()` is called.

In ISO C, expressions need not be split to guard against unintended overflows.

6.10.4 The Parentheses

ISO C is often erroneously described as honoring parentheses or evaluating according to parentheses due to an incomplete understanding or an inaccurate presentation.

Since ISO C expressions simply have the grouping specified by their parsing, parentheses still only serve as a way of controlling how an expression is parsed; the natural precedence and associativity of expressions carry exactly the same weight as parentheses.

The above expression could have been written as:

```
i = ((*(++p)) + f()) + g();
```

with no different effect on its grouping or evaluation.

6.10.5 The As If Rule

There were several reasons for the K&R C rearrangement rules:

- The rearrangements provide many more opportunities for optimizations, such as compile-time constant folding.
- The rearrangements do not change the result of integral-typed expressions on most machines.

- Some of the operations are both mathematically and computationally commutative and associative on all machines.

The ISO C Committee eventually became convinced that the rearrangement rules were intended to be an instance of the *as if* rule when applied to the described target architectures. ISO C's *as if* rule is a general license that permits an implementation to deviate arbitrarily from the abstract machine description as long as the deviations do not change the behavior of a valid C program.

Thus, all the binary bitwise operators (other than shifting) are allowed to be rearranged on any machine because there is no way to notice such regroupings. On typical two's-complement machines in which overflow wraps around, integer expressions involving multiplication or addition can be rearranged for the same reason.

Therefore, this change in C does not have a significant impact on most C programmers.

6.11 Incomplete Types

The ISO C standard introduced the term “incomplete type” to formalize a fundamental, yet misunderstood, portion of C, implicit from its beginnings. This section describes incomplete types, where they are permitted, and why they are useful.

6.11.1 Types

ISO separates C's types into three distinct sets: function, object, and incomplete. Function types are obvious; object types cover everything else, except when the size of the object is not known. The Standard uses the term “object type” to specify that the designated object must have a known size, but it is important to know that incomplete types other than `void` also refer to an object.

There are only three variations of incomplete types: `void`, arrays of unspecified length, and structures and unions with unspecified content. The type `void` differs from the other two in that it is an incomplete type that cannot be completed, and it serves as a special function return and parameter type.

6.11.2 Completing Incomplete Types

An array type is completed by specifying the array size in a following declaration in the same scope that denotes the same object. When an array without a size is declared and initialized in the same declaration, the array has an incomplete type only between the end of its declarator and the end of its initializer.

An incomplete structure or union type is completed by specifying the content in a following declaration in the same scope for the same tag.

6.11.3 Declarations

Certain declarations can use incomplete types, but others require complete object types. Those declarations that require object types are array elements, members of structures or unions, and objects local to a function. All other declarations permit incomplete types. In particular, the following constructs are permitted:

- Pointers to incomplete types
- Functions returning incomplete types
- Incomplete function parameter types
- `typedef` names for incomplete types

The function return and parameter types are special. Except for `void`, an incomplete type used in such a manner must be completed by the time the function is defined or called. A return type of `void` specifies a function that returns no value, and a single parameter type of `void` specifies a function that accepts no arguments.

Since array and function parameter types are rewritten to be pointer types, a seemingly incomplete array parameter type is not actually incomplete. The typical declaration of `main`'s `argv`, namely, `char *argv[]`, as an unspecified length array of character pointers, is rewritten to be a pointer to character pointers.

6.11.4 Expressions

Most expression operators require complete object types. The only three exceptions are the unary `&` operator, the first operand of the comma operator, and the second and third operands of the `?:` operator. Most operators that accept pointer operands also permit pointers to incomplete types, unless pointer arithmetic is required. The list includes the unary `*` operator. For example, given:

```
void *p
```

`&*p` is a valid subexpression that makes use of this.

6.11.5 Justification

Why are incomplete types necessary? Ignoring `void`, there is only one feature provided by incomplete types that C has no other way to handle, and that has to do with forward references to structures and unions. If one has two structures that need pointers to each other, the only way to do so is with incomplete types:

```
struct a { struct b *bp; };
struct b { struct a *ap; };
```

All strongly typed programming languages that have some form of pointer and heterogeneous data types provide some method of handling this case.

6.11.6 Examples

Defining `typedef` names for incomplete structure and union types is frequently useful. If you have a complicated bunch of data structures that contain many pointers to each other, having a list of `typedefs` to the structures up front, possibly in a central header, can simplify the declarations.

```
typedef struct item_tag Item;
typedef union note_tag Note;
typedef struct list_tag List;
. . .
struct item_tag { . . . };
. . .
struct list_tag {
    struct list_tag {
};
```

Moreover, for those structures and unions whose contents should not be available to the rest of the program, a header can declare the tag without the content. Other parts of the program can use pointers to the incomplete structure or union without any problems, unless they attempt to use any of its members.

A frequently used incomplete type is an external array of unspecified length. Generally, it is not necessary to know the extent of an array to make use of its contents.

6.12 Compatible and Composite Types

With K&R C, and even more so with ISO C, it is possible for two declarations that refer to the same entity to be other than identical. The term “compatible type” is used in ISO C to denote those types that are “close enough”. This section describes compatible types as well as “composite types”—the result of combining two compatible types.

6.12.1 Multiple Declarations

If a C program were only allowed to declare each object or function once, there would be no need for compatible types. Linkage, which allows two or more declarations to refer to the same entity, function prototypes, and separate compilation all need such a capability. Separate translation units (source files) have different rules for type compatibility from within a single translation unit.

6.12.2 Separate Compilation Compatibility

Since each compilation probably looks at different source files, most of the rules for compatible types across separate compiles are structural in nature:

- Matching scalar (integral, floating, and pointer) types must be compatible, as if they were in the same source file.
- Matching structures, unions, and enums must have the same number of members. Each matching member must have a compatible type (in the separate compilation sense), including bit-field widths.
- Matching structures must have the members in the same order. The order of union and enum members does not matter.
- Matching enum members must have the same value.

An additional requirement is that the names of members, including the lack of names for unnamed members, match for structures, unions, and enums, but not necessarily their respective tags.

6.12.3 Single Compilation Compatibility

When two declarations in the same scope describe the same object or function, the two declarations must specify compatible types. These two types are then combined into a single composite type that is compatible with the first two. More about composite types later.

The compatible types are defined recursively. At the bottom are type specifier keywords. These are the rules that say that `unsigned short` is the same as `unsigned short int`, and that a type without type specifiers is the same as one with `int`. All other types are compatible only if the types from which they are derived are compatible. For example, two qualified types are compatible if the qualifiers, `const` and `volatile`, are identical, and the unqualified base types are compatible.

6.12.4 Compatible Pointer Types

For two pointer types to be compatible, the types they point to must be compatible and the two pointers must be identically qualified. Recall that the qualifiers for a pointer are specified after the `*`, so that these two declarations

```
int *const cpi;
int *volatile vpi;
```

declare two differently qualified pointers to the same type, `int`.

6.12.5 Compatible Array Types

For two array types to be compatible, their element types must be compatible. If both array types have a specified size, they must match, that is, an incomplete array type (see [Section 6.11, “Incomplete Types” on page 6-33](#)) is compatible both with another incomplete array type and an array type with a specified size.

6.12.6 Compatible Function Types

To make functions compatible, follow these rules:

- For two function types to be compatible, their return types must be compatible. If either or both function types have prototypes, the rules are more complicated.

- For two function types with prototypes to be compatible, they also must have the same number of parameters, including use of the ellipsis (...) notation, and the corresponding parameters must be parameter-compatible.
- For an old-style function definition to be compatible with a function type with a prototype, the prototype parameters must *not* end with an ellipsis (...). Each of the prototype parameters must be parameter-compatible with the corresponding old-style parameter, after application of the default argument promotions.
- For an old-style function declaration (not a definition) to be compatible with a function type with a prototype, the prototype parameters must not end with an ellipsis (...). All of the prototype parameters must have types that would be unaffected by the default argument promotions.
- For two types to be parameter-compatible, the types must be compatible after the top-level qualifiers, if any, have been removed, and after a function or array type has been converted to the appropriate pointer type.

6.12.7 Special Cases

`signed int` behaves the same as `int`, except possibly for bit-fields, in which a plain `int` may denote an unsigned-behaving quantity.

Another interesting note is that each enumeration type must be compatible with some integral type. For portable programs, this means that enumeration types are separate types. In general, the ISO C standard views them in that manner.

6.12.8 Composite Types

The construction of a composite type from two compatible types is also recursively defined. The ways compatible types can differ from each other are due either to incomplete arrays or to old-style function types. As such, the simplest description of the composite type is that it is the type compatible with both of the original types, including every available array size and every available parameter list from the original types.

Converting Applications for a 64-Bit Environment

This chapter provides the information you need for writing code for the 32-bit or the 64-bit compilation environment.

Once you try to write or modify code for both the 32-bit and 64-bit compilation environments, you face two basic issues:

- Data type consistency between the different data-type models
- Interaction between the applications using different data-type models

Maintaining a single code-source with as few `#ifdefs` as possible is usually better than maintaining multiple source trees. Therefore, this chapter provides guidelines for writing code that works correctly in both 32-bit and 64-bit compilation environments. In some cases, the conversion of current code requires only a recompilation and relinking with the 64-bit libraries. However, for those cases where code changes are required, this chapter discusses the tools and strategies that make conversion easier.

7.1 Overview of the Data Model Differences

The biggest difference between the 32-bit and the 64-bit compilation environments is the change in data-type models.

The C data-type model for 32-bit applications is the ILP32 model, so named because integers, longs, and pointers are 32-bit data types. The LP64 data model, so named because longs and pointers grow to 64-bits, is the creation of a consortium of companies across the industry. The remaining C types, `int`, `long long`, `short`, and `char` are the same in both data-type models.

Regardless of the data-type model, the standard relationship between C integral types holds true:

```
sizeof (char) <= sizeof (short) <= sizeof (int) <= sizeof (long)
```

The following table lists the basic C data types and their corresponding sizes in bits for both the ILP32 and LP64 data models.

TABLE 7-1 Data Type Size for ILP32 and LP64

C Data Type	LP32	LP64
char	8	8
short	16	16
int	32	32
long	32	64
long long	64	64
pointer	32	64
enum	32	32
float	32	32
double	64	64
long double	128	128

It is not unusual for current 32-bit applications to assume that integers, pointers, and longs are the same size. Because the size of longs and pointers change in the LP64 data model, you need to be aware that this change alone can cause many ILP32 to LP64 conversion problems.

In addition, it becomes very important to examine declarations and casts; how expressions are evaluated can be affected when the types change. The effects of standard C conversion rules are influenced by the change in data-type sizes. To adequately show what you intend, you need to explicitly declare the types of constants. You can also use casts in expressions to make certain that the expression is evaluated the way you intend. This is particularly true in the case of sign extension, where explicit casting is essential for demonstrating intent.

7.2 Implementing Single Source Code

The following sections describe some of the available resources that you can use to write single-source code that supports 32-bit and 64-bit compilation.

7.2.1 Derived Types

Use the system derived types to make code safe for both the 32-bit and the 64-bit compilation environment. In general, it is good programming practice to use derived types to allow for change. When you use derived data-types, only the system derived types need to change due to data model changes, or due to a port.

The system include files `<sys/types.h>` and `<inttypes.h>` contain constants, macros, and derived types that are helpful in making applications 32-bit and 64-bit safe.

7.2.1.1 `<sys/types.h>`

Include `<sys/types.h>` in an application source file to gain access to the definition of `_LP64` and `_ILP32`. This header also contains a number of basic derived types that should be used whenever appropriate. In particular, the following are of special interest:

- `clock_t` represents the system times in clock ticks.
- `dev_t` is used for device numbers.
- `off_t` is used for file sizes and offsets.
- `ptrdiff_t` is the signed integral type for the result of subtracting two pointers.
- `size_t` reflects the size, in bytes, of objects in memory.
- `ssize_t` is used by functions that return a count of bytes or an error indication.
- `time_t` counts time in seconds.

All of these types remain 32-bit quantities in the ILP32 compilation environment and grow to 64-bit quantities in the LP64 compilation environment.

7.2.1.2 `<inttypes.h>`

The include file `<inttypes.h>` provides constants, macros, and derived types that help you make your code compatible with explicitly sized data items, independent of the compilation environment. It contains mechanisms for manipulating 8-bit, 16-bit, 32-bit, and 64-bit objects. The file is part of the new 1999 ISO/IEC C standard and the contents of the file track the proposals leading to its inclusion in the 1999 ISO/IEC C standard. The file will soon be updated to fully conform with the 1999 ISO/IEC C standard. The following is a discussion of the basic features provided by `<inttypes.h>`:

- Fixed-width integer types.
- Helpful types such as `uintptr_t`
- Constant macros
- Limits
- Format string macros

The following sections provide more information about the basic features of `<inttypes.h>`.

Fixed-Width Integer Types

The fixed-width integer types that `<inttypes.h>` provides, include signed integer types, such as `int8_t`, `int16_t`, `int32_t`, `int64_t`, and unsigned integer types, such as `uint8_t`, `uint16_t`, `uint32_t`, and `uint64_t`.

Derived types defined as the smallest integer types that can hold the specified number of bits include `int_least8_t`, ..., `int_least64_t`, `uint_least8_t`, ..., `uint_least64_t`.

It is safe to use an `int` or unsigned `int` for such operations as loop counters and file descriptors; it is also safe to use a `long` for an array index. However, do not use these fixed-width types indiscriminately. Use fixed-width types for explicit binary representations of the following:

- On-disk data
- Over the data wire
- Hardware registers
- Binary interface specifications
- Binary data structures

Helpful Types Such as `uintptr_t`

The `<inttypes.h>` file includes signed and unsigned integer types large enough to hold a pointer. These are given as `intptr_t` and `uintptr_t`. In addition, `<inttypes.h>` provides `intmax_t` and `uintmax_t`, which are the longest (in bits) signed and unsigned integer types available.

Use the `uintptr_t` type as the integral type for pointers instead of a fundamental type such as unsigned `long`. Even though an unsigned `long` is the same size as a pointer in both the ILP32 and LP64 data models, using `uintptr_t` means that only the definition of `uintptr_t` is effected if the data model changes. This makes your code portable to many other systems. It is also a more clear way to express your intentions in C.

The `intptr_t` and `uintptr_t` types are extremely useful for casting pointers when you want to perform address arithmetic. Use `intptr_t` and `uintptr_t` types instead of `long` or unsigned `long` for this purpose.

Constant Macros

Use the macros `INT8_C(c)`, ..., `INT64_C(c)`, `UINT8_C(c)`, ..., `UINT64_C(c)` to specify the size and sign of a given constant. Basically, these macros place an `l`, `u`, `ll`, or `ull` at the end of the constant, if necessary. For example, `INT64_C(1)` appends `ll` to the constant `1` for ILP32 and an `l` for LP64.

Use the `INTMAX_C(c)` and `UINTMAX_C(c)` macros to make a constant the biggest type. These macros can be very useful for specifying the type of constants described in [Section 7.3, “Converting to the LP64 Data Type Model”](#) on page 7-7.

Limits

The limits defined by `<inttypes.h>` are constants that specify the minimum and maximum values of various integer types. This includes minimum and maximum values for each of the fixed-width types such as `INT8_MIN`, ..., `INT64_MIN`, `INT8_MAX`, ..., `INT64_MAX`, and their unsigned counterparts.

The `<inttypes.h>` file also provides the minimum and maximum for each of the least-sized types. These include `INT_LEAST8_MIN`, ..., `INT_LEAST64_MIN`, `INT_LEAST8_MAX`, ..., `INT_LEAST64_MAX`, as well as their unsigned counterparts.

Finally, `<inttypes.h>` defines the minimum and maximum value of the largest supported integer types. These include `INTMAX_MIN` and `INTMAX_MAX` and their corresponding unsigned versions.

Format String Macros

The `<inttypes.h>` file also includes the macros that specify the `printf(3S)` and `scanf(3S)` format specifiers. Essentially, these macros prepend the format specifier with an `l` or `ll` to identify the argument as a `long` or `long long`, given that the number of bits in the argument is built into the name of the macro.

There are macros for `printf(3S)` that print both the smallest and largest integer types in decimal, octal, unsigned, and hexadecimal formats as the following example shows:

```
int64_t i;
printf("i =%" PRIx64 "\n", i);
```

Similarly, there are macros for `scanf(3S)` that read both the smallest and largest integer types in decimal, octal, unsigned, and hexadecimal formats.

```
uint64_t u;  
scanf("%" SCNu64 "\n", &u);
```

Do not use these macros indiscriminately. They are best used in conjunction with the fixed-width types discussed in [“Fixed-Width Integer Types” on page 74](#).

7.2.2 Tools

The `lint` program’s `-errchk` option detects potential 64-bit porting problems. You can also specify `cc -v` which directs the compiler to perform additional and more strict semantic checks than by compiling without `-v`. The `-v` option also enables certain lint-like checks on the named files.

When you enhance code to be 64-bit safe, use the header files present in the Solaris operating system because these files have the correct definition of the derived types and data structures for the 64-bit compilation environment.

7.2.2.1 `lint`

Use `lint` to check code that is written for both the 32-bit and the 64-bit compilation environment. Specify the `-errchk=longptr64` option to generate LP64 warnings. Also use the `-errchk=longptr64` flag which checks portability to an environment for which the size of long integers and pointers is 64 bits and the size of plain integers is 32 bits. The `-errchk=longptr64` flag checks assignments of pointer expressions and long integer expressions to plain integers, even when explicit casts are used.

Use the `-errchk=longptr64,signext` option to find code where the normal ISO C value-preserving rules allow the extension of the sign of a signed-integral value in an expression of unsigned-integral type.

Use the `-xarch=v9` option of `lint` when you want to check code that you intend to run in the Solaris 64-bit compilation environment only. Use `-xarch=amd64` when you want to check code you intend to run in the x86 64-bit environment.

When `lint` generates warnings, it prints the line number of the offending code, a message that describes the problem, and whether or not a pointer is involved. The warning message also indicates the sizes of the involved data types. When you know a pointer is involved and you know the size of the data types, you can find specific 64-bit problems and avoid the pre-existing problems between 32-bit and smaller types.

Be aware, however, that even though `lint` gives warnings about potential 64-bit problems, it cannot detect all problems. Also, in many cases, code that is intentional and correct for the application generates a warning.

You can suppress the warning for a given line of code by placing a comment of the form `NOTE(LINTED("<optional message">))` on the previous line. This is useful when you want `lint` to ignore certain lines of code such as casts and assignments. Exercise extreme care when you use the `NOTE(LINTED("<optional message">))` comment because it can mask real problems. When you use `NOTE`, include `#include<note.h>`. Refer to the `lint` man page for more information.

7.3 Converting to the LP64 Data Type Model

The examples that follow illustrate some of the more common problems you are likely to encounter when you convert code. Where appropriate, the corresponding `lint` warnings are shown.

7.3.1 Integer and Pointer Size Change

Since integers and pointers are the same size in the ILP32 compilation environment, some code relies on this assumption. Pointers are often cast to `int` or `unsigned int` for address arithmetic. Instead, cast your pointers to `long` because `long` and pointers are the same size in both ILP32 and LP64 data-type models. Rather than explicitly using `unsigned long`, use `uintptr_t` instead because it expresses your intent more closely and makes the code more portable, insulating it against future changes. Consider the following example:

```
char *p;
p = (char *) ((int)p & PAGEOFFSET);
%
warning: conversion of pointer loses bits
```

Here is the modified version:

```
char *p;
p = (char *) ((uintptr_t)p & PAGEOFFSET);
```

7.3.2 Integer and Long Size Change

Because integers and longs are never really distinguished in the ILP32 data-type model, your existing code probably uses them indiscriminately. Modify any code that uses integers and longs interchangeably so it conforms to the requirements of both the ILP32 and LP64 data-type models. While an integer and a long are both 32-bits in the ILP32 data-type model, a long is 64 bits in the LP64 data-type model.

Consider the following example:

```
int waiting;
long w_io;
long w_swap;
...
waiting = w_io + w_swap;

%
warning: assignment of 64-bit integer to 32-bit integer
```

Furthermore, large arrays of integers, such as longs or unsigned longs, can cause serious performance degradation in the LP64 data-type model as compared to arrays of ints or unsigned ints. Large arrays of longs or unsigned longs can also cause significantly more cache misses and consume more memory.

Therefore, if int works just as well as long for the application purposes, it's better to use int rather than long.

This is also an argument for using arrays of ints instead of arrays of pointers. Some C applications suffer from serious performance degradation after conversion to the LP64 data-type model because they rely on many, large, arrays of pointers.

7.3.3 Sign Extension

Sign extension is a common problem when you convert to the 64-bit compilation environment because the type conversion and promotion rules are somewhat obscure. To prevent sign extension problems, use explicit casting to achieve the intended results.

To understand why sign extension occurs, it helps to understand the conversion rules for ISO C. The conversion rules that seem to cause the most sign extension problems between the 32-bit and the 64-bit compilation environment come into effect during the following operations:

- Integral promotion

You can use a char, short, enumerated type, or bit-field, whether signed or unsigned, in any expression that calls for an integer.

If an integer can hold all possible values of the original type, the value is converted to an integer; otherwise, the value is converted to an unsigned integer.

- Conversion between signed and unsigned integers

When an integer with a negative sign is promoted to an unsigned integer of the same or larger type, it is first promoted to the signed equivalent of the larger type, then converted to the unsigned value.

When the following example is compiled as a 64-bit program, the `addr` variable becomes sign-extended, even though both `addr` and `a.base` are unsigned types.

```
%cat test.c
struct foo {
unsigned int base:19, rehash:13;
};

main(int argc, char *argv[])
{
    struct foo a;
    unsigned long addr;

    a.base = 0x40000;
    addr = a.base << 13; /* Sign extension here! */
    printf("addr 0x%lx\n", addr);

    addr = (unsigned int)(a.base << 13); /* No sign extension here! */
    printf("addr 0x%lx\n", addr);
}
```

This sign extension occurs because the conversion rules are applied as follows:

- `a.base` is converted from an unsigned `int` to an `int` because of the integral promotion rule. Thus, the expression `a.base << 13` is of type `int`, but no sign extension has yet occurred.
- The expression `a.base << 13` is of type `int`, but it is converted to a `long` and then to an unsigned `long` before being assigned to `addr`, because of signed and unsigned integer promotion rules. The sign extension occurs when it is converted from an `int` to a `long`.

```
% cc -o test64 -xarch=v9 test.c
% ./test64
addr 0xffffffff80000000
addr 0x80000000
%
```

When this same example is compiled as a 32-bit program it does not display any sign extension:

```
cc -o test test.c
%test

addr 0x80000000
addr 0x80000000
```

For a more detailed discussion of the conversion rules, refer to the ISO C standard. Also included in this standard are useful rules for ordinary arithmetic conversions and integer constants.

7.3.4 Pointer Arithmetic Instead of Integers

In general, using pointer arithmetic works better than integers because pointer arithmetic is independent of the data model, whereas integers might not be. Also, you can usually simplify your code by using pointer arithmetic. Consider the following example:

```
int *end;
int *p;
p = malloc(4 * NUM_ELEMENTS);
end = (int *)((unsigned int)p + 4 * NUM_ELEMENTS);

%
warning: conversion of pointer loses bits
```

Here is the modified version:

```
int *end;
int *p;
p = malloc(sizeof (*p) * NUM_ELEMENTS);
end = p + NUM_ELEMENTS;
```

7.3.5 Structures

Check the internal data structures in an applications for holes. Use extra padding between fields in the structure to meet alignment requirements. This extra padding is allocated when long or pointer fields grow to 64 bits for the LP64 data-type model.

In the 64-bit compilation environment on SPARC platforms, all types of structures are aligned to the size of the largest member within them. When you repack a structure, follow the simple rule of moving the long and pointer fields to the beginning of the structure. Consider the following structure definition:

```
struct bar {
    int i;
    long j;
    int k;
    char *p;
}; /* sizeof (struct bar) = 32 */
```

Here is the same structure with the long and pointer data types defined at the beginning of the structure:

```
struct bar {
    char *p;
    long j;
    int i;
    int k;
}; /* sizeof (struct bar) = 24 */
```

7.3.6 Unions

Be sure to check unions because their fields can change size between the ILP32 and the LP64 data-type models.

```
typedef union {
    double _d;
    long _l[2];
} llx_t;
```

Here is the modified version

```
typedef union {
    double _d;
    int _l[2];
} llx_t;
```

7.3.7 Type Constants

A lack of precision can cause the loss of data in some constant expressions. Be explicit when you specify the data types in your constant expression. Specify the type of each integer constant by adding some combination of {u,U,l,L}. You can also use casts to specify the type of a constant expression. Consider the following example:

```
int i = 32;
long j = 1 << i; /* j will get 0 because RHS is integer */
                /* expression */
```

Here is the modified version:

```
int i = 32;
long j = 1L << i;
```

7.3.8 Beware of Implicit Declarations

If you use `-xc99=none`, the C compiler assumes that any function or variable that is used in a module and not defined or declared externally is an integer. Any longs and pointers used in this way are truncated by the compiler's implicit integer declaration. Place the appropriate extern declaration for the function or variable in a header and not in the C module. Include this header in any C module that uses the function or variable. If this is a function or variable defined by the system headers, you still need to include the proper header in the code. Consider the following example:

```
int
main(int argc, char *argv[])
{
    char *name = getlogin();
    printf("login = %s\n", name);
    return (0);
}

%
warning: improper pointer/integer combination: op "="
warning: cast to pointer from 32-bit integer
implicitly declared to return int
getlogin      printf
```

The proper headers are now in the modified version

```
#include <unistd.h>
#include <stdio.h>

int
main(int argc, char *argv[])
{
    char *name = getlogin();
    (void) printf("login = %s\n", name);
    return (0);
}
```

7.3.9 sizeof () Is an Unsigned long

In the LP64 data-type model, `sizeof()` has the effective type of an unsigned long. Occasionally, `sizeof()` is passed to a function expecting an argument of type `int`, or assigned or cast to an integer. In some cases, this truncation causes loss of data.

```
long a[50];
unsigned char size = sizeof (a);

%
warning: 64-bit constant truncated to 8 bits by assignment
warning: initializer does not fit or is out of range: 0x190
```

7.3.10 Use Casts to Show Your Intentions

Relational expressions can be tricky because of conversion rules. You should be very explicit about how you want the expression to be evaluated by adding casts wherever necessary.

7.3.11 Check Format String Conversion Operation

Make sure the format strings for `printf(3S)`, `sprintf(3S)`, `scanf(3S)`, and `sscanf(3S)` can accommodate long or pointer arguments. For pointer arguments, the conversion operation given in the format string should be `%p` to work in both the 32-bit and 64-bit compilation environments.

```
char *buf;
struct dev_info *devi;
...
(void) sprintf(buf, "di%x", (void *)devi);

%
warning: function argument (number) type inconsistent with format
sprintf (arg 3)      void *: (format) int
```

Here is the modified version

```
char *buf;
struct dev_info *devi;
...
(void) sprintf(buf, `di%p", (void *)devi);
```

For long arguments, the long size specification, `l`, should be prepended to the conversion operation character in the format string. Furthermore, check to be sure that the storage pointed to by `buf` is large enough to contain 16 digits.

```
size_t nbytes;
u_long align, addr, raddr, alloc;
printf("kalloca:%d%%d from heap got%x.%x returns%x\n",
nbytes, align, (int)raddr, (int)(raddr + alloc), (int)addr);

%
warning: cast of 64-bit integer to 32-bit integer
warning: cast of 64-bit integer to 32-bit integer
warning: cast of 64-bit integer to 32-bit integer
```

Here is the modified version

```
size_t nbytes;
u_long align, addr, raddr, alloc;
printf("kalloca:%lu%%lu from heap got%lx.%lx returns%lx\n",
nbytes, align, raddr, raddr + alloc, addr);
```

7.4 Other Considerations

The remaining guidelines highlight common problems encountered when converting an application to a full 64-bit program.

7.4.1 Derived Types That Have Grown in Size

A number of derived types have changed to now represent 64-bit quantities in the 64-bit application compilation environment. This change does not affect 32-bit applications; however, any 64-bit applications that consume or export data described by these types need to be reevaluated. An example of this is in applications that directly manipulate the `utmp(4)` or `utmpx(4)` files. For correct operation in the 64-bit application environment, do not attempt to directly access these files. Instead, use the `getutxent(3C)` and related family of functions.

7.4.2 Check for Side Effects of Changes

Be aware that a type change in one area can result in an unexpected 64-bit conversion in another area. For example, check all the callers of a function that previously returned an `int` and now returns an `ssize_t`.

7.4.3 Check Whether Literal Uses of `long` Still Make Sense

A variable that is defined as a `long` is 32 bits in the ILP32 data-type model and 64 bits in the LP64 data-type model. Where it is possible, avoid problems by redefining the variable and use a more portable derived type.

Related to this, a number of derived types have changed under the LP64 data-type model. For example, `pid_t` remains a `long` in the 32-bit environment, but under the 64-bit environment, a `pid_t` is an `int`.

7.4.4 Use `#ifdef` for Explicit 32-bit Versus 64-bit Prototypes

In some cases, specific 32-bit and 64-bit versions of an interface are unavoidable. You can distinguish these by specifying the `_LP64` or `_ILP32` feature test macros in the headers. Similarly, code that runs in 32-bit and 64-bit environments needs to utilize the appropriate `#ifdefs`, depending on the compilation mode.

7.4.5 Calling Convention Changes

When you pass structures by value and compile the code for a 64-bit environment, the structure is passed in registers rather than as a pointer to a copy if it is small enough. This can cause problems if you try to pass structures between C code and handwritten assembly code.

Floating point parameters work in a similar fashion; some floating point values passed by value are passed in floating point registers.

7.4.6 Algorithm Changes

After your code is safe for the 64-bit environment, review your code again to verify that the algorithms and data structures still make sense. The data types are larger, so data structures might use more space. The performance of your code might change as well. Given these concerns, you might need to modify your code appropriately.

7.5 Checklist for Getting Started

Use the following checklist to help you convert your code to 64-bit.

- Review all data structures and interfaces to verify that these are still valid in the 64-bit environment.
- Include `<inttypes.h>` in your code to pull in the `_ILP32` or `_LP64` definitions as well as many basic derived types. Systems programs may wish to include `<sys/types.h>` (or at a minimum, `<sys/isa_defs.h>`) to obtain the definitions of `_ILP32` or `_LP64`.
- Move function prototypes and external declarations with non-local scope to headers and include these headers in your code.
- Run lint using the `-errchk=longptr64` and `signext` options. Also, specify `-D__sparcv9` for applications intended for SPARC architectures or specify `-Xarch=amd64` for applications intended for x86 architectures. Review each warning individually. Keep in mind that not all warnings require a change to the code. Depending on the changes, run lint again in both 32-bit and 64-bit modes.
- Compile code as both 32-bit and 64-bit, unless the application is being provided only as 64-bit.
- Test the application by executing the 32-bit version on the 32-bit operating system, and the 64-bit version on the 64-bit operating system. You can also test the 32-bit version on the 64-bit operating system.

cscope: Interactively Examining a C Program

`cscope` is an interactive program that locates specified elements of code in C, `lex`, or `yacc` source files. With `cscope`, you can search and edit your source files more efficiently than you could with a typical editor. That's because `cscope` supports function calls—when a function is being called, when it is doing the calling—as well as C language identifiers and keywords.

This chapter is a tutorial on the `cscope` browser provided with this release.

Note – The `cscope` program has not yet been updated to understand codes written for the 1999 ISO/IEC C standard. For example, it does not yet recognize the new keywords introduced in the 1999 ISO/IEC C standard.

8.1 The `cscope` Process

When `cscope` is called for a set of C, `lex`, or `yacc` source files, it builds a symbol cross-reference table for the functions, function calls, macros, variables, and preprocessor symbols in those files. You can then query that table about the locations of symbols you specify. First, it presents a menu and asks you to choose the type of search you would like to have performed. You may, for instance, want `cscope` to find all the functions that call a specified function.

When `cscope` has completed this search, it prints a list. Each list entry contains the name of the file, the number of the line, and the text of the line in which `cscope` has found the specified code. In our case, the list also includes the names of the functions that call the specified function. You now have the option of requesting another search or examining one of the listed lines with the editor. If you choose the latter, `cscope` invokes the editor for the file in which the line appears, with the

cursor on that line. You can now view the code in context and, if you wish, edit the file as any other file. You can then return to the menu from the editor to request a new search.

Because the procedure you follow depends on the task at hand, there is no single set of instructions for using `cscope`. For an extended example of its use, review the `cscope` session described in the next section. It shows how you can locate a bug in a program without learning all the code.

8.2 Basic Use

Suppose you are given responsibility for maintaining the program `prog`. You are told that an error message, out of storage, sometimes appears just as the program starts up. Now you want to use `cscope` to locate the parts of the code that are generating the message. Here is how you do it.

8.2.1 Step 1: Set Up the Environment

`cscope` is a screen-oriented tool that can only be used on terminals listed in the Terminal Information Utilities (`terminfo`) database. Be sure you have set the `TERM` environment variable to your terminal type so that `cscope` can verify that it is listed in the `terminfo` database. If you have not done so, assign a value to `TERM` and export it to the shell as follows:

In a Bourne shell, type:

```
$ TERM=term_name; export TERM
```

In a C shell, type:

```
% setenv TERM term_name
```

You may now want to assign a value to the `EDITOR` environment variable. By default, `cscope` invokes the `vi` editor. (The examples in this chapter illustrate `vi` usage.) If you prefer not to use `vi`, set the `EDITOR` environment variable to the editor of your choice and export `EDITOR`, as follows:

In a Bourne shell, type:

```
$ EDITOR=emacs; export EDITOR
```

In a C shell, type:

```
% setenv EDITOR emacs
```

You may have to write an interface between `cscope` and your editor. For details, see [Section 8.2.9, “Command-Line Syntax for Editors”](#) on page 8-19.

If you want to use `cscope` only for browsing (without editing), you can set the `VIEWER` environment variable to `pg` and export `VIEWER`. `cscope` will then invoke `pg` instead of `vi`.

An environment variable called `VPATH` can be set to specify directories to be searched for source files. See [Section 8.2.6, “View Paths”](#) on page 8-14.

8.2.2 Step 2: Invoke the `cscope` Program

By default, `cscope` builds a symbol cross-reference table for all the `C`, `lex`, and `yacc` source files in the current directory, and for any included header files in the current directory or the standard place. So, if all the source files for the program to be browsed are in the current directory, and if its header files are there or in the standard place, invoke `cscope` without arguments:

```
% cscope
```

To browse through selected source files, invoke `cscope` with the names of those files as arguments:

```
% cscope file1.c file2.c file3.h
```

For other ways to invoke `cscope`, see [Section 8.2.5, “Command-Line Options”](#) on page 8-11.

`cscope` builds the symbol cross-reference table the first time it is used on the source files for the program to be browsed. By default, the table is stored in the file `cscope.out` in the current directory. On a subsequent invocation, `cscope` rebuilds the cross-reference only if a source file has been modified or the list of source files is

different. When the cross-reference is rebuilt, the data for the unchanged files is copied from the old cross-reference, which makes rebuilding faster than the initial build, and reduces startup time for subsequent invocations.

8.2.3 Step 3: Locate the Code

Now let's return to the task we undertook at the beginning of this section: to identify the problem that is causing the error message out of storage to be printed. You have invoked `cscope`, the cross-reference table has been built. The `cscope` menu of tasks appears on the screen.

The `cscope` Menu of Tasks:

```
% cscope

cscope      Press the ? key for help

Find this C symbol:
Find this global definition:
Find functions called by this function:
Find functions calling this function:
Find this text string:
Change this text string:
Find this egrep pattern:
Find this file:
Find files #including this file:
```

Press the Return key to move the cursor down the screen (with wraparound at the bottom of the display), and `^p` (Control-p) to move the cursor up; or use the up (`ua`) and down (`da`) arrow keys. You can manipulate the menu and perform other tasks with the following single-key commands:

TABLE 8-1 `cscope` Menu Manipulation Commands

Tab	Move to the next input field.
Return	Move to the next input field.
<code>^n</code>	Move to the next input field.
<code>^p</code>	Move to the previous input field.
<code>^y</code>	Search with the last text typed.
<code>^b</code>	Move to the previous input field and search pattern.
<code>^f</code>	Move to the next input field and search pattern.

TABLE 8-1 cscope Menu Manipulation Commands (*Continued*)

<code>^c</code>	Toggle ignore/use letter case when searching. For example, a search for <code>FILE</code> matches <code>file</code> and <code>File</code> when ignoring the letter case.
<code>^r</code>	Rebuild cross-reference.
<code>!</code>	Start an interactive shell. Type <code>^d</code> to return to <code>cscope</code> .
<code>^l</code>	Redraw the screen.
<code>?</code>	Display the list of commands.
<code>^d</code>	Exit <code>cscope</code> .

If the first character of the text for which you are searching matches one of these commands, you can escape the command by entering a `\` (backslash) before the character.

Now move the cursor to the fifth menu item, `Find this text string`, enter the text out of storage, and press the Return key.

`cscope` Function: Requesting a Search for a Text String:

```
$ cscope
cscope      Press the ? key for help

Find this C symbol
Find this global definition
Find functions called by this function
Find functions calling this function
Find this text string:  out of storage
Change this text string
Find this egrep pattern
Find this file
Find files #including this file
```

Note – Follow the same procedure to perform any other task listed in the menu except the sixth, `Change this text string`. Because this task is slightly more complex than the others, there is a different procedure for performing it. For a description of how to change a text string, see [Section 8.2.8, “Examples” on page 8-15](#).

`cscope` searches for the specified text, finds one line that contains it, and reports its finding.

cscope Function: Listing Lines Containing the Text String:

```
Text string: out of storage

File Line
1 alloc.c 63 (void) fprintf(stderr, "\n%s: out of storage\n",
argv0);

Find this C symbol:
Find this global definition:
Find functions called by this function:
Find functions calling this function:
Find this text string:
Change this text string:
Find this egrep pattern:
Find this file:
Find files #including this file:
```

After `cscope` shows you the results of a successful search, you have several options. You may want to change one of the lines or examine the code surrounding it in the editor. Or, if `cscope` has found so many lines that a list of them does not fit on the screen at once, you may want to look at the next part of the list. The following table shows the commands available after `cscope` has found the specified text:

TABLE 8-2 Commands for Use After an Initial Search

1 - 9	Edit the file referenced by this line. The number you type corresponds to an item in the list of lines printed by <code>cscope</code> .
Space	Display the next set of matching lines.
+	Display the next set of matching lines.
^v	Display the next set of matching lines.
-	Display the previous set of matching lines.
^e	Edit the displayed files in order.
>	Append the list of lines being displayed to a file.
	Pipe all lines to a shell command.

Again, if the first character of the text for which you are searching matches one of these commands, you can escape the command by entering a backslash before the character.

Now examine the code around the newly found line. Enter **1** (the number of the line in the list). The editor is invoked with the file `alloc.c` with the cursor at the beginning of line 63 of `alloc.c`.

`cscope` Function: Examining a Line of Code:

```
{
    return(alloctest(realloc(p, (unsigned) size)));
}

/* check for memory allocation failure */

static char *
alloctest(p)
char *p;
{
    if (p == NULL) {
        (void) fprintf(stderr, "\n%s: out of storage\n", argv0);
        exit(1);
    }
    return(p);
}
~
~
~
~
~
~
~
~
"alloc.c" 67 lines, 1283 characters
```

You can see that the error message is generated when the variable `p` is `NULL`. To determine how an argument passed to `alloctest()` could have been `NULL`, you must first identify the functions that call `alloctest()`.

Exit the editor by using normal quit conventions. You are returned to the menu of tasks. Now type **alloctest** after the fourth item, Find functions calling this function.

cscope Function: Requesting a List of Functions That Call `alloctest()`:

```
Text string: out of storage

File Line
1 alloc.c 63(void)fprintf(stderr,"\n%s: out of storage\n",argv0);

Find this C symbol:
Find this global definition:
Find functions called by this function:
Find functions calling this function: alloctest
Find this text string:
Change this text string:
Find this egrep pattern:
Find this file:
Find files #including this file:
```

cscope finds and lists three such functions.

cscope Function: Listing Functions That Call `alloctest()`:

```
Functions calling this function: alloctest
File Function Line
1 alloc.c mymalloc 33 return(alloctest(malloc((unsigned) size)));
2 alloc.c mycalloc 43 return(alloctest(calloc((unsigned) nelem,
(unsigned) size)));
3 alloc.c myrealloc 53 return(alloctest(realloc(p, (unsigned)
size)));

Find this C symbol:
Find this global definition:
Find functions called by this function:
Find functions calling this function:
Find this text string:
Change this text string:
Find this egrep pattern:
Find this file:
Find files #including this file:
```

Now you want to know which functions call `mymalloc()`. cscope finds ten such functions. It lists nine of them on the screen and instructs you to press the space bar to see the rest of the list.

cscope Function: Listing Functions That Call mymalloc():

```
Functions calling this function: mymalloc
```

File	Function	Line
1 alloc.c	stralloc	24 return(strcpy(mymalloc (strlen(s) + 1), s));
2 crossref.c	crossref	47 symbol = (struct symbol *)mymalloc (msymbols * sizeof(struct symbol));
3 dir.c	makevpsrkdirs	63 srcdirs = (char **) mymalloc (nsrkdirs * sizeof(char*));
4 dir.c	addinmdir	167 incdirs = (char **)mymalloc (sizeof(char *));
5 dir.c	addinmdir	168 incnames = (char **) mymalloc(sizeof(char *));
6 dir.c	addsrcfile	439 p = (struct listitem *) mymalloc (sizeof(struct listitem));
7 display.c	dispinit	87 displine = (int *) mymalloc (mdisprefs * sizeof(int));
8 history.c	addcmd	19 h = (struct cmd *) mymalloc (sizeof(struct cmd));
9 main.c	main	212 s = mymalloc((unsigned) (strlen(reffile) +strlen(home) + 2));

```
* 9 more lines - press the space bar to display more *
```

```
Find this C symbol:
```

```
Find this global definition:
```

```
Find functions called by this function:
```

```
Find functions calling this function:
```

```
Find this text string:
```

```
Change this text string:
```

```
Find this egrep pattern:
```

```
Find this file:
```

```
Find files #including this file:
```

Because you know that the error message out of storage is generated at the beginning of the program, you can guess that the problem may have occurred in the function `dispinit()` (display initialization).

To view `dispinit()`, the seventh function on the list, type 7.

cscope Function: Viewing `dispinit()` in the Editor:

```
void
dispinit()
{
    /* calculate the maximum displayed reference lines */
    lastdispline = FLDLINE - 4;
    mdisprefs = lastdispline - REFLINE + 1;
    if (mdisprefs > 9) {
        mdisprefs = 9;
    }
    /* allocate the displayed line array */
    dispiline = (int *) mymalloc(mdisprefs * sizeof(int));
}
^L/* display a page of the references */

void
display()
{
    char file[PATHLEN + 1]; /* file name */
    char function[PATLEN + 1]; /* function name */
    char linenum[NUMLLEN + 1]; /* line number */
    int screenline; /* screen line number */
    int width; /* source line display width */
    register int i, j;
    "display.c" 622 lines, 14326 characters
}
```

`mymalloc()` failed because it was called either with a very large number or a negative number. By examining the possible values of `FLDLINE` and `REFLINE`, you can see that there are situations in which the value of `mdisprefs` is negative, that is, in which you are trying to call `mymalloc()` with a negative number.

8.2.4 Step 4: Edit the Code

On a windowing terminal, you may have multiple windows of arbitrary size. The error message out of storage might have appeared as a result of running `prog` in a window with too few lines. In other words, that may have been one of the situations in which `mymalloc()` was called with a negative number. Now you want to be sure that when the program aborts in this situation in the future, it does so after printing the more meaningful error message screen too small. Edit the function `dispinit()` as follows.

cscope Function: Correcting the Problem:

```
void
dispinit()
{
/* calculate the maximum displayed reference lines */
    lastdispline = FLDLINE - 4;
    mdisprefs = lastdispline - REFLINE + 1;
    if (mdisprefs > 9) {
        mdisprefs = 9;
    }
/* allocate the displayed line array */
    dispiline = (int *) mymalloc(mdisprefs * sizeof(int));
}
^L/* display a page of the references */

void
display()
{
    char file[PATHLEN + 1]; /* file name */
    char function[PATLEN + 1]; /* function name */
    char linenum[NUMLLEN + 1]; /* line number */
    int screenline; /* screen line number */
    int width; /* source line display width */
    register int i, j;
"display.c" 622 lines, 14326 characters
}
```

You have fixed the problem we began investigating at the beginning of this section. Now if prog is run in a window with too few lines, it does not simply fail with the unedifying error message out of storage. Instead, it checks the window size and generates a more meaningful error message before exiting.

8.2.5 Command-Line Options

As noted, cscope builds a symbol cross-reference table for the C, lex, and source files in the current directory by default. That is,

```
% cscope
```

is equivalent to:

```
% cscope *. [chly]
```

We have also seen that you can browse through selected source files by invoking `cscope` with the names of those files as arguments:

```
% cscope file1.c file2.c file3.h
```

`cscope` provides command-line options with greater flexibility in specifying source files to be included in the cross-reference. When you invoke `cscope` with the `-s` option and any number of directory names (separated by commas):

```
% cscope -s dir1,dir2,dir3
```

`cscope` builds a cross-reference for all the source files in the specified directories as well as the current directory. To browse through all of the source files whose names are listed in *file* (file names separated by spaces, tabs, or new-lines), invoke `cscope` with the `-i` option and the name of the file containing the list:

```
% cscope -i file
```

If your source files are in a directory tree, use the following commands to browse through all of them:

```
% find . -name '*.chly' -print | sort > file  
% cscope -i file
```

If this option is selected, however, `cscope` ignores any other files appearing on the command-line.

The `-I` option can be used for `cscope` in the same way as the `-I` option to `cc`. See [Section 2.14, “How to Specify Include Files” on page 2-27](#).

You can specify a cross-reference file other than the default `cscope.out` by invoking the `-f` option. This is useful for keeping separate symbol cross-reference files in the same directory. You may want to do this if two programs are in the same directory, but do not share all the same files:

```
% cscope -f admin.ref admin.c common.c aux.c libs.c  
% cscope -f delta.ref delta.c common.c aux.c libs.c
```

In this example, the source files for two programs, `admin` and `delta`, are in the same directory, but the programs consist of different groups of files. By specifying different symbol cross-reference files when you invoke `cscope` for each set of source files, the cross-reference information for the two programs is kept separate.

You can use the `-pn` option to specify that `cscope` display the path name, or part of the path name, of a file when it lists the results of a search. The number you give to `-p` stands for the last n elements of the path name you want to be displayed. The default is 1, the name of the file itself. So if your current directory is `home/common`, the command:

```
% cscope -p2
```

causes `cscope` to display `common/file1.c`, `common/file2.c`, and so forth when it lists the results of a search.

If the program you want to browse contains a large number of source files, you can use the `-b` option, so that `cscope` stops after it has built a cross-reference; `cscope` does not display a menu of tasks. When you use `cscope -b` in a pipeline with the `batch(1)` command, `cscope` builds the cross-reference in the background:

```
% echo 'cscope -b' | batch
```

Once the cross-reference is built, and as long as you have not changed a source file or the list of source files in the meantime, you need only specify:

```
% cscope
```

for the cross-reference to be copied and the menu of tasks to be displayed in the normal way. You can use this sequence of commands when you want to continue working without having to wait for `cscope` to finish its initial processing.

The `-d` option instructs `cscope` not to update the symbol cross-reference. You can use it to save time if you are sure that no such changes have been made; `cscope` does not check the source files for changes.

Note – Use the `-d` option with care. If you specify `-d` under the erroneous impression that your source files have not been changed, `cscope` refers to an outdated symbol cross-reference in responding to your queries.

Check the `cscope(1)` man page for other command-line options.

8.2.6 View Paths

As we have seen, `cscope` searches for source files in the current directory by default. When the environment variable `VPATH` is set, `cscope` searches for source files in directories that comprise your view path. A view path is an ordered list of directories, each of which has the same directory structure below it.

For example, suppose you are part of a software project. There is an *official* set of source files in directories below `/fs1/ofc`. Each user has a home directory (`/usr/you`). If you make changes to the software system, you may have copies of just those files you are changing in `/usr/you/src/cmd/prog1`. The official versions of the entire program can be found in the directory `/fs1/ofc/src/cmd/prog1`.

Suppose you use `cscope` to browse through the three files that comprise `prog1`, namely, `f1.c`, `f2.c`, and `f3.c`. You would set `VPATH` to `/usr/you` and `/fs1/ofc` and export it, as in:

In a Bourne shell, type:

```
$ VPATH=/usr/you:/fs1/ofc; export VPATH
```

In a C shell, type:

```
% setenv VPATH /usr/you:/fs1/ofc
```

You then make your current directory `/usr/you/src/cmd/prog1`, and invoke `cscope`:

```
% cscope
```

The program locates all the files in the view path. In case duplicates are found, `cscope` uses the file whose parent directory appears earlier in `VPATH`. Thus, if `f2.c` is in your directory, and all three files are in the official directory, `cscope` examines `f2.c` from your directory, and `f1.c` and `f3.c` from the official directory.

The first directory in `VPATH` must be a prefix of the directory you will be working in, usually `$HOME`. Each colon-separated directory in `VPATH` must be absolute: it should begin at `/`.

8.2.7 cscope and Editor Call Stacks

`cscope` and editor calls can be stacked. That is, when `cscope` puts you in the editor to view a reference to a symbol and there is another reference of interest, you can invoke `cscope` again from within the editor to view the second reference without exiting the current invocation of either `cscope` or the editor. You can then back up by exiting the most recent invocation with the appropriate `cscope` and editor commands.

8.2.8 Examples

This section presents examples of how `cscope` can be used to perform three tasks: changing a constant to a preprocessor symbol, adding an argument to a function, and changing the value of a variable. The first example demonstrates the procedure for changing a text string, which differs slightly from the other tasks on the `cscope` menu. That is, once you have entered the text string to be changed, `cscope` prompts you for the new text, displays the lines containing the old text, and waits for you to specify which of these lines you want it to change.

8.2.8.1 Changing a Constant to a Preprocessor Symbol

Suppose you want to change a constant, `100`, to a preprocessor symbol, `MAXSIZE`. Select the sixth menu item, `Change this text string`, and enter `\100`. The `1` must be escaped with a backslash because it has a special meaning (item 1 on the menu) to `cscope`. Now press Return. `cscope` prompts you for the new text string. Type **`MAXSIZE`**.

`cscope` Function: Changing a Text String:

```
cscope          Press the ? key for help

Find this C symbol:
Find this global definition:
Find functions called by this function:
Find functions calling this function:
Find this text string:
Change this text string: \100
Find this egrep pattern:
Find this file:
Find files #including this file:
To: MAXSIZE
```

`cscope` displays the lines containing the specified text string, and waits for you to select those in which you want the text to be changed.

`cscope` Function: Prompting for Lines to be Changed:

```
cscope          Press the ? key for help

Find this C symbol:
Find this global definition:
Find functions called by this function:
Find functions calling this function:
Find this text string:
Change this text string: \100
Find this egrep pattern:
Find this file:
Find files #including this file:
To: MAXSIZE
```

You know that the constant `100` in lines 1, 2, and 3 of the list (lines 4, 26, and 8 of the listed source files) should be changed to `MAXSIZE`. You also know that `0100` in `read.c` and `100.0` in `err.c` (lines 4 and 5 of the list) should not be changed. You select the lines you want changed with the following single-key commands:

TABLE 8-3 Commands for Selecting Lines to Be Changed

1-9	Mark or unmark the line to be changed.
*	Mark or unmark all displayed lines to be changed.
Space	Display the next set of lines.
+	Display the next set of lines.
-	Display the previous set of lines.
a	Mark all lines to be changed.
^d	Change the marked lines and exit.
Esc	Exit without changing the marked lines.

In this case, enter **1**, **2**, and **3**. The numbers you type are not printed on the screen. Instead, `cscope` marks each list item you want to be changed by printing a `>` (greater than) symbol after its line number in the list.

cscope Function: Marking Lines to be Changed:

```
Change "100" to "MAXSIZE"
```

```
File Line
1>init.c 4 char s[100];
2>init.c 26 for (i = 0; i < 100; i++)
3>find.c 8 if (c < 100) {
4 read.c 12 f = (bb & 0100);
5 err.c 19 p = total/100.0; /* get percentage */
```

```
Find this C symbol:
```

```
Find this global definition:
```

```
Find functions called by this function:
```

```
Find functions calling this function:
```

```
Find this text string:
```

```
Change this text string:
```

```
Find this egrep pattern:
```

```
Find this file:
```

```
Find files #including this file:
```

```
Select lines to change (press the ? key for help):
```

Now type **^d** to change the selected lines. `cscope` displays the lines that have been changed and prompts you to continue.

cscope Function: Displaying Changed Lines of Text:

```
Changed lines:
```

```
char s[MAXSIZE];
for (i = 0; i < MAXSIZE; i++)
if (c < MAXSIZE) {
```

```
Press the RETURN key to continue:
```

When you press Return in response to this prompt, `cscope` redraws the screen, restoring it to its state before you selected the lines to be changed.

The next step is to add the `#define` for the new symbol `MAXSIZE`. Because the header file in which the `#define` is to appear is not among the files whose lines are displayed, you must escape to the shell by typing **!**. The shell prompt appears at the bottom of the screen. Then enter the editor and add the `#define`.

cscope Function: Exiting to the Shell:

```
Text string: 100

File Line
1 init.c 4 char s[100];
2 init.c 26 for (i = 0; i < 100; i++)
3 find.c 8 if (c < 100) {
4 read.c 12 f = (bb & 0100);
5 err.c 19 p = total/100.0;          /* get percentage */

Find this C symbol:
Find this global definition:
Find functions called by this function:
Find functions calling this function:
Find this text string:
Change this text string:
Find this egrep pattern:
Find this file:
Find files #including this file:
$ vi defs.h
```

To resume the cscope session, quit the editor and type **^d** to exit the shell.

8.2.8.2 Adding an Argument to a Function

Adding an argument to a function involves two steps: editing the function itself and adding the new argument to every place in the code where the function is called.

First, edit the function by using the second menu item, `Find this global definition`. Next, find out where the function is called. Use the fourth menu item, `Find functions calling this function`, to obtain a list of all the functions that call it. With this list, you can either invoke the editor for each line found by entering the list number of the line individually, or invoke the editor for all the lines automatically by typing **^e**. Using cscope to make this kind of change ensures that none of the functions you need to edit are overlooked.

8.2.8.3 Changing the Value of a Variable

At times, you may want to see how a proposed change affects your code.

Suppose you want to change the value of a variable or preprocessor symbol. Before doing so, use the first menu item, `Find this C symbol`, to obtain a list of references that are affected. Then use the editor to examine each one. This step helps you predict the overall effects of your proposed change. Later, you can use `cscope` in the same way to verify that your changes have been made.

8.2.9 Command-Line Syntax for Editors

`cscope` invokes the `vi` editor by default. You can override the default setting by assigning your preferred editor to the `EDITOR` environment variable and exporting `EDITOR`, as described in [Section 8.2.1, “Step 1: Set Up the Environment” on page 8-2](#). However, `cscope` expects the editor it uses to have a command-line syntax of the form:

```
% editor +linenum filename
```

as does `vi`. If the editor you want to use does not have this command-line syntax, you must write an interface between `cscope` and the editor.

Suppose you want to use `ed`. Because `ed` does not allow specification of a line number on the command-line, you cannot use it to view or edit files with `cscope` unless you write a shell script that contains the following line:

```
/usr/bin/ed $2
```

Let's name the shell script `myedit`. Now set the value of `EDITOR` to your shell script and export `EDITOR`:

In a Bourne shell, type:

```
$ EDITOR=myedit; export EDITOR
```

In a C shell, type:

```
% setenv EDITOR myedit
```

When `cscope` invokes the editor for the list item you have specified, say, line 17 in `main.c`, it invokes your shell script with the command-line:

```
% myedit +17 main.c
```

`myedit` then discards the line number (`$1`) and calls `ed` correctly with the file name (`$2`). Of course, you are not moved automatically to line 17 of the file and must execute the appropriate `ed` commands to display and edit the line.

8.3 Unknown Terminal Type Error

If you see the error message:

```
Sorry, I don't know how to deal with your "term" terminal
```

your terminal may not be listed in the Terminal Information Utilities (`terminfo`) database that is currently loaded. Make sure you have assigned the correct value to `TERM`. If the message reappears, try reloading the Terminal Information Utilities.

If this message is displayed:

```
Sorry, I need to know a more specific terminal type than "unknown"
```

set and export the `TERM` variable as described in [Section 8.2.1, “Step 1: Set Up the Environment”](#) on page 8-2.

Compiler Options Grouped by Functionality

This chapter summarizes the C compiler options by function. Detailed explanations of the options and the compiler command-line syntax are provided in [Appendix B](#).

A.1 Options Summarized by Function

In this section, the compiler options are grouped by function to provide a quick reference. For a detailed description of each option, refer to [Appendix B](#). Some flags serve more than one purpose and appear more than once.

The options apply to all platforms except as noted; features that are unique to the Solaris operating system on SPARC based systems are identified as (*SPARC*), and the features that are unique to the Solaris operating system on x86 based systems are identified as (*x86*).

A.1.1 Optimization and Performance Options

The following optimization and performance options are listed in alphabetical order.

TABLE A-1 Optimization and Performance Options

Option	Action
-fast	Selects the optimum combination of compilation options for speed of executable code.
-p	Prepares the object code to collect data for profiling
-xalias_level	(<i>SPARC</i>)Enables the compiler to perform type-based alias analysis and optimizations.

TABLE A-1 Optimization and Performance Options (*Continued*)

Option	Action
-xbinopt	Prepares the binary for later optimizations, transformations and analysis.
-xbuiltin	Improve the optimization of code that calls standard library functions.
-xcrossfile	Enables optimization and inlining across source files.
-xdepend	(SPARC) Analyzes loops for inter-iteration data dependencies and does loop restructuring.
-xF	Enables reordering of data and functions by the linker.
-xhwcprof	(SPARC) Enables compiler support for hardware counter-based profiling.
-xinline	Tries to inline only those functions specified.
-xipo	(SPARC) Performs whole-program optimizations by invoking an interprocedural analysis component.
-xipo_archive	Allows crossfile optimization to include archive (.a) libraries.
-xjobs	Sets how many processes the compiler creates.
-xlibmil	Inlines some library routines for faster execution.
-xlic_lib=sunperf	Links in the Sun-supplied performance libraries.
-xlinkopt	Performs link-time optimizations on relocatable object files.
-xlibmopt	Enable library of optimized math routines.
-xmaxopt	This command limits the level of <code>pragma opt</code> to the level specified.
-xnolibmil	Does not inline math library routines.
-xnolibmopt	Do not enable library of optimized math routines.
-x0	Optimizes the object code.
-xpagesize	Sets the preferred page size for the stack and the heap.
-xpagesize_stack	Sets the preferred page size for the stack.
-xpagesize_heap	Sets the preferred page size for the heap.
-xpch	Reduces compile time for applications whose source files share a common set of include files.
-xpchstop	Can be used in conjunction with <code>-xpch</code> to specify the last include file of the viable prefix.
-xpentium	(x86) Optimizes for the Pentium™ processor.
-xprefetch	(SPARC) Enable prefetch instructions.

TABLE A-1 Optimization and Performance Options (*Continued*)

Option	Action
-xprefetch_level	(SPARC) Control the aggressiveness of automatic insertion of prefetch instructions as set by -xprefetch=auto
-xprefetch_auto_type	(SPARC) Controls how indirect prefetches are generated.
-xprofile	Collects data for a profile or uses a profile to optimize.
-xprofile_ircache	Improves compilation time of -xprofile=use phase by reusing compilation data saved from the -xprofile=collect phase
-xprofile_pathmap	Support for multiple programs or shared libraries in a single profile directory.
-xrestrict	(SPARC) Treats pointer-valued function parameters as restricted pointers.
-xsafe	(SPARC) Allows the compiler to assume no memory-based traps occur.
-xspace	Does no optimizations or parallelization of loops that increase code size.
-xunroll	Suggests to the optimizer to unroll loops <i>n</i> times.

A.1.2 Compile-Time and Link-Time Options

The following table lists the options that must be specified both at link-time and at compile-time.

TABLE A-2 Compile-Time and Link-Time Options

Option	Action
-fast	Selects the optimum combination of compilation options for speed of executable code.
-mt	Macro option that expands to -D_REENTRANT -lthread.
-p	Prepares the object code to collect data for profiling with prof(1)
-xarch	Specify instruction set architecture.
-xautopar	(SPARC) Turns on automatic parallelization for multiple processors.
-xexplicitpar	(SPARC) Generates parallelized code based on specification of #pragma MP directives.
-xhwcprof	(SPARC) Enables compiler support for hardware counter-based profiling.

TABLE A-2 Compile-Time and Link-Time Options (*Continued*)

Option	Action
-xipo	(SPARC) Performs whole-program optimizations by invoking an interprocedural analysis component.
-xlinkopt	Performs link-time optimizations on relocatable object files.
-xmemalign	(SPARC) Specify maximum assumed memory alignment and behavior of misaligned data accesses.
-xopenmp	(SPARC) Supports the OpenMP interface for explicit parallelization including a set of source code directives, run-time library routines, and environment variables
-xpagesize	Sets the preferred page size for the stack and the heap.
-xpagesize_stack	Sets the preferred page size for the stack.
-xpagesize_heap	Sets the preferred page size for the heap.
-xparallel	(SPARC) Parallelizes loops both automatically by the compiler and explicitly specified by the programmer.
-xpg	Prepares the object code to collect data for profiling with <code>gprof(1)</code> .
-xprofile	Collects data for a profile or uses a profile to optimize.
-xsb	Generates extra symbol table information for the Source Browser.
-xvector	Enable automatic generation of calls to the vector library functions.

A.1.3 Data-Alignment Options

The following data-alignment options are listed in alphabetical order.

TABLE A-3 Data-Alignment Options

Option	Action
-xchar_byte_order	Produce an integer constant by placing the characters of a multi-character character-constant in the specified byte order.
-xdepend	(SPARC) Analyzes loops for inter-iteration data dependencies and does loop restructuring.
-xmemalign	(SPARC) Specify maximum assumed memory alignment and behavior of misaligned data accesses.
-xopenmp	(SPARC) Supports the OpenMP interface for explicit parallelization including a set of source code directives, run-time library routines, and environment variables

A.1.4 Numerics and Floating Point Options

The following numerics and floating point options are listed in alphabetical order.

TABLE A-4 Numerics and Floating Point Options

Option	Action
-flteval	(<i>x86</i>) Controls floating point evaluation.
-fnonstd	Causes nonstandard initialization of floating-point arithmetic hardware.
-fns	(<i>SPARC</i>) Turns on the <i>SPARC</i> nonstandard floating-point mode.
-fprecision	(<i>x86</i>) Initializes the rounding-precision mode bits in the Floating-point Control Word
-fround	Sets the IEEE 754 rounding mode that is established at runtime during the program initialization.
-fsimple	Allows the optimizer to make simplifying assumptions concerning floating-point arithmetic.
-fsingle	Causes the compiler to evaluate <code>float</code> expressions as single precision rather than double precision.
-fstore	(<i>x86</i>) Causes the compiler to convert the value of a floating-point expression or function to the type on the left-hand side of an assignment
-ftrap	Sets the IEEE 754 trapping mode in effect at startup.
-nofstore	(<i>x86</i>) Does not convert the value of a floating-point expression or function to the type on the left-hand side of an assignment
-xdepend	(<i>SPARC</i>) Analyzes loops for inter-iteration data dependencies and does loop restructuring.
-xlibieee	Forces IEEE 754 style return values for math routines in exceptional cases.
-xopenmp	(<i>SPARC</i>) Supports the OpenMP interface for explicit parallelization including a set of source code directives, run-time library routines, and environment variables
-xsfpconst	Represents unsuffixed floating-point constants as single precision
-xvector	Enable automatic generation of calls to the vector library functions.

A.1.5 Parallelization Options

The following parallelization options are listed in alphabetical order.

TABLE A-5 Parallelization Options

Option	Action
-mt	Macro option that expands to <code>-D_REENTRANT -lthread</code> .
-xautopar	(SPARC) Turns on automatic parallelization for multiple processors.
-xcheck	(SPARC) Adds a runtime check for stack overflow.
-xdepend	(SPARC) Analyzes loops for inter-iteration data dependencies and does loop restructuring.
-xexplicitpar	(SPARC) Generates parallelized code based on specification of <code>#pragma MP</code> directives.
-xloopinfo	(SPARC) Shows which loops are parallelized and which are not.
-xopenmp	(SPARC) Supports the OpenMP interface for explicit parallelization including a set of source code directives, run-time library routines, and environment variables
-xparallel	(SPARC) Parallelizes loops both automatically by the compiler and explicitly specified by the programmer.
-xreduction	(SPARC) Turns on reduction recognition during automatic parallelization.
-xrestrict	(SPARC) Treats pointer-valued function parameters as restricted pointers.
-xvpara	(SPARC) Warns about loops that have <code>#pragma MP</code> directives specified but may not be properly specified for parallelization.
-xthreadvar	(SPARC) Controls the implementation of thread local variables.
-zll	(SPARC) Creates the program database for <code>lock_lint</code> , but does not generate executable code.

A.1.6 Source-Code Options

The following source-code options are listed in alphabetical order.

TABLE A-6 Source-Code Options

Option	Action
-A	Associates <i>name</i> as a predicate with the specified <i>tokens</i> as if by a <code>#assert</code> preprocessing directive.
-C	Prevents the preprocessor from removing comments, except those on the preprocessing directive lines.
-D	Associates <i>name</i> with the specified <i>tokens</i> as if by a <code>#define</code> preprocessing directive.
-E	Runs the source file through the preprocessor only and sends the output to <code>stdout</code> .
-fd	Reports K&R-style function definitions and declarations.
-H	Prints to standard error, one per line, the path name of each file included during the current compilation.
-I	Adds directories to the list that is searched for <code>#include</code> files with relative file names.
-P	Runs the source file through the C preprocessor only.
-U	Removes any initial definition of the preprocessor symbol <i>name</i> .
-X	The <code>-X</code> options specify varying degrees of compliance to the ISO C standard.
-xCC	Accepts the C++-style comments.
-xc99	Controls compiler recognition of supported C99 features.
-xchar	Helps with migration from systems where <code>char</code> is defined as unsigned.
-xcsi	Allows the C compiler to accept source code written in locales that do not conform to the ISO C source character code requirements
-xM	Runs only the preprocessor on the named C programs, requesting that it generate makefile dependencies and send the result to the standard output
-xM1	Collects dependencies like <code>-xM</code> , but excludes <code>/usr/include</code> files.
-xP	Prints prototypes for all K&R C functions defined in this module
-xpg	Prepares the object code to collect data for profiling with <code>gprof(1)</code> .
-xsb	Generates extra symbol table information for the Source Browser.

TABLE A-6 Source-Code Options (*Continued*)

Option	Action
-xsbfast	Creates the database for the Source Browser.
-xtrigraphs	Determines recognition of trigraph sequences.
-xustr	Enables recognition of string literals composed of sixteen-bit characters.

A.1.7 Compiled-Code Options

The following compiled-code options are listed in alphabetical order.

TABLE A-7 Compiled-Code Options

Option	Action
-c	Directs the compiler to suppress linking with <i>ld(1)</i> and to produce a <code>.o</code> file in the current working directory for each source file
-o	Names the output file
-S	Directs the compiler to produce an assembly source file but not to assemble the program.

A.1.8 Compilation-Mode Options

The following compilation-mode options are listed in alphabetical order.

TABLE A-8 Compilation-Mode Options

Option	Action
-#	Turns on verbose mode, which shows how command options expand and shows each component as it is invoked.
-###	Shows each component as it would be invoked, but does not actually execute it. Also shows how command options expand.
-features	Ensures compatibility between old binaries with extern inline functions and new binaries.
-keeptmp	Retains temporary files created during compilation instead of deleting them automatically.
-V	Directs <code>cc</code> to print the name and version ID of each component as the compiler executes.
-W	Passes arguments to C compilation-system components.

TABLE A-8 Compilation-Mode Options (*Continued*)

Option	Action
-X	The -X options specify varying degrees of compliance to the ISO C standard.
-xc99	Controls compiler recognition of supported C99 features.
-xchar	Preserves the sign of a char
-xhelp	Displays on-line help information.
-xjobs	Sets how many processes the compiler creates.
-xpch	Reduces compile time for applications whose source files share a common set of include files.
-xpchstop	Can be used in conjunction with -xpch to specify the last include file of the viable prefix.
-xtemp	Sets the directory for temporary files used by cc to <i>dir</i> .
-xtime	Reports the time and resources used by each compilation component.
-Y	Specifies a new directory for the location of a C compilation-system component.
-YA	Changes the default directory searched for components.
-YI	Changes the default directory searched for include files.
-YP	Changes the default directory for finding library files.
-YS	Changes the default directory for startup object files.

A.1.9 Diagnostic Options

The following diagnostic options are listed in alphabetical order.

TABLE A-9 Diagnostic Options

Option	Action
-errfmt	Prefix error messages with string "error:" for ready distinction from warning messages.
-erroff	Suppresses compiler warning messages.
-errshort	Control how much detail is in the error message produced by the compiler when it discovers a type mismatch.
-errtags	Displays the message tag for each warning message.

TABLE A-9 Diagnostic Options (*Continued*)

Option	Action
-errwarn	If the indicated warning message is issued, cc exits with a failure status.
-v	Directs the compiler to perform stricter semantic checks and to enable other lint-like checks.
-w	Suppresses compiler warning messages.
-xe	Performs only syntax and semantic checking on the source file, but does not produce any object or executable code.
-xtransition	Issues warnings for the differences between K&R C and Sun ISO C.
-xvpara	(SPARC) Warns about loops that have #pragma MP directives specified but may not be properly specified for parallelization.

A.1.10 Debugging Options

The following debugging options are listed in alphabetical order.

TABLE A-10 Debugging Options

Option	Action
-xcheck	Adds a runtime check for stack overflow.
-g	Produces additional symbol table information for the debugger.
-s	Removes all symbolic debugging information from the output object file.
-xdebugformat	Generates debugging information in dwarf format instead of stabs format.
-xpagesize	Sets the preferred page size for the stack and the heap.
-xpagesize_stack	Sets the preferred page size for the stack.
-xpagesize_heap	Sets the preferred page size for the heap.
-xs	Disables Auto-Read of object files for dbx.
-xvis	(SPARC) Enables compiler recognition of the assembly-language templates defined in the VIS[tm] instruction set

A.1.11 Linking and Libraries Options

The following linking and libraries options are listed in alphabetical order.

TABLE A-11 Linking and Libraries Options

Option	Action
-B	Specifies whether bindings of libraries for linking are <code>static</code> or <code>dynamic</code> .
-d	Specifies dynamic or static linking in the link editor.
-G	Passes the option to the link editor to produce a shared object rather than a dynamically linked executable.
-h	Assigns a name to a shared dynamic library as a way to have different versions of a library.
-i	Passes the option to the linker to ignore any <code>LD_LIBRARY_PATH</code> setting.
-L	Adds directories to the list that the linker searches for libraries.
-l	Links with object library <code>libname.so</code> , or <code>libname.a</code> .
-mc	Removes duplicate strings from the <code>.comment</code> section of the object file.
-mr	Removes all strings from the <code>.comment</code> section. Can also insert a <i>string</i> in that section of the object file.
-Q	Emits or does not emit identification information to the output file.
-R	Passes a colon-separated list of directories used to specify library search directories to the runtime linker.
-xMerge	Merges data segments into text segments.
-xcode	Specify code address space.
-xldscope	Controls the default scope of variable and function definitions to create faster and safer shared libraries.
-xnativeconnect	Includes interface information inside object files and subsequent shared libraries so that the shared library can interface with code written in the Java[tm] programming language.
-xnolib	Does not link any libraries by default
-xnolibmil	Does not inline math library routines.
-xstrconst	Inserts string literals into the read-only data section of the text segment instead of the default data segment.

A.1.12 Target-Platform Options

The following target-platform options are listed in alphabetical order.

TABLE A-12 Target-Platform Options

Option	Action
-xarch	Specify instruction set architecture.
-xcache	Defines the cache properties for use by the optimizer.
-xchip	Specifies the target processor for use by the optimizer.
-xregs	(SPARC) Specifies the usage of registers for the generated code.
-xtarget	Specifies the target system for instruction set and optimization.

A.1.13 x86-Specific Options

The following x86-specific options are listed in alphabetical order.

TABLE A-13 x86-Specific Options

Option	Action
-flteval	Controls floating point evaluation.
-fprecision	Initializes the rounding-precision mode bits in the Floating-point Control Word
-fstore	Causes the compiler to convert the value of a floating-point expression or function to the type on the left-hand side of an assignment
-nofstore	Does not convert the value of a floating-point expression or function to the type on the left-hand side of an assignment
-xmodel	Modifies the form of 64-bit objects for the Solaris x86 platforms
-xpentium	Optimizes for the Pentium™ processor.

A.1.14 Licensing Options

The following table lists the licensing option.

TABLE A-14 Licensing Options

Option	Action
-xlicinfo	Returns information about the licensing system.

A.1.15 Obsolete Options

The following table lists the options that have been deprecated. Note that the compiler may still accept these options, but may not do so in future releases. Begin using the suggested alternative option as soon as possible.

TABLE A-15 Obsolete Options

Option	Action
-dalign	Use -xmemalign=8s instead.
-KPIC (<i>SPARC</i>)	Use -xcode=pic32 instead.
-Kpic (<i>SPARC</i>)	Use -xcode=pic13 instead.
-misalign	Use -xmemalign=1i instead.
-misalign2	Use -xmemalign=2i instead.
-x386	Use -xchip=generic instead.
-x486	Use -xchip=generic instead.
-xa	Use -xprofile=tcov instead.
-xcg	Use -O instead to take advantage of the default values for -xarch, -xchip, and -xcache.
-xprefetch=yes	Use -xprefetch=auto, explicit instead.
-xprefetch=no	Use -xprefetch=no%auto, no%explicit instead.
-xtarget=386	Use -xtarget=generic instead.
-xtarget=486	Use -xtarget=generic instead.

C Compiler Options Reference

This chapter describes the C compiler options in alphabetical order. See [Chapter 2](#) for options grouped by functionality. For example, [TABLE 2-1](#) lists all the optimization and performance options.

Take note that the C compiler recognizes by default some of the constructs of the 1999 ISO/IEC C standard. Specifically, the supported features are detailed in [Section , “Supported Features of C99” on page D-1](#). Use the `-xc99=none` command if you want to limit the compiler to the 1990 ISO/IEC C standard.

If you are porting a K&R C program to ISO C, make special note of the section on compatibility flags, [Section B.2.61, “-x\[clatlsls\]” on page B-25](#). Using them makes the transition to ISO C easier. Also refer to the discussion on the transition in [Chapter 6](#).

B.1 Option Syntax

The syntax of the `cc` command is:

```
% cc [options] filenames [libraries] . . .
```

where:

- *options* represents one or more of the options described in [Appendix B](#).
- *filenames* represents one or more files used in building the executable program

The C compiler accepts a list of C source files and object files contained in the list of files specified by *filenames*. The resulting executable code is placed in `a.out`, unless the `-o` option is used. In this case, the code is placed in the file named by the `-o` option.

Use the C compiler to compile and link any combination of the following:

- C source files, with a `.c` suffix
- Inline template files, with a `.i1` suffix (only when specified with `.c` files)
- C preprocessed source files, with a `.i` suffix
- Object-code files, with `.o` suffixes
- Assembler source files, with `.s` suffixes

After linking, the C compiler places the linked files, now in executable code, into a file named `a.out`, or into the file specified by the `-o` option. When the compiler produces object code for each `.i` or `.c` input file, it always creates an object (`.o`) file in the current working directory.

- *libraries* represents any of a number of standard or user-provided libraries containing functions, macros, and definitions of constants.

See option `-YP, dir` to change the default directories used for finding libraries. *dir* is a colon-separated path list. The default library search order for `cc` is:

```
/opt/SUNWspro/prod/lib
```

```
/usr/ccs/lib
```

```
/usr/lib
```

`cc` uses `getopt` to parse command-line options. Options are treated as a single letter or a single letter followed by an argument. See `getopt(3c)`.

B.2 The `cc` Options

This section describes the `cc` options, arranged alphabetically. These descriptions are also available in the man page, `cc(1)`. Use the `cc -flags` option for a one-line summary of these descriptions.

Options noted as being unique to one or more platforms are accepted without error and ignored on all other platforms. For an explanation of the typographic notations used with the options and arguments, refer to [“Typographic Conventions” on page xxxii](#).

B.2.1 `-#`

Turns on verbose mode, showing how command options expand. Shows each component as it is invoked.

B.2.2 -###

Shows each component as it would be invoked, but does not actually execute it. Also shows how command options would expand.

B.2.3 -Aname[(tokens)]

Associates *name* as a predicate with the specified *tokens* as if by a `#assert` preprocessing directive. Preassertions:

- `system(unix)`
- `machine(sparc) (SPARC)`
- `machine(i386) (x86)`
- `cpu(sparc) (SPARC)`
- `cpu(i386) (x86)`

These preassertions are not valid in `-xc` mode.

If `-A` is followed by a dash (-) only, it causes all predefined macros (other than those that begin with `_`) and predefined assertions to be forgotten.

B.2.4 -B[static|dynamic]

Specifies whether bindings of libraries for linking are *static* or *dynamic*, indicating whether libraries are non-shared or shared, respectively.

`-Bdynamic` causes the link editor to look for files named `libx.so` and then for files named `libx.a` when given the `-lx` option.

`-Bstatic` causes the link editor to look only for files named `libx.a`. This option may be specified multiple times on the command line as a toggle. This option and its argument are passed to `ld(1)`.

Note – Many system libraries, such as `libc`, are only available as dynamic libraries in the Solaris 64-bit compilation environment. Therefore, do not use `-Bstatic` as the last toggle on the command line.

This option and its argument are passed to the linker.

B.2.5 -C

Prevents the C preprocessor from removing comments, except those on the preprocessing directive lines.

B.2.6 -c

Directs the C compiler to suppress linking with `ld(1)` and to produce a `.o` file for each source file. You can explicitly name a single object file using the `-o` option. When the compiler produces object code for each `.i` or `.c` input file, it always creates an object (`.o`) file in the current working directory. If you suppress the linking step, you also suppress the removal of the object files.

B.2.7 -Dname[=tokens]

Associates *name* with the specified *tokens* as if by a `#define` preprocessing directive. If no *=tokens* is specified, the token `1` is supplied.

Predefinitions (not valid in `-xc` mode):

- `sun`
- `unix`
- `sparc` (SPARC)
- `i386` (x86)

The following predefinitions are valid in all modes.

- `__sparcv9` (`-xarch=v9, v9a, v9b`)
- `__sun`
- `__unix`
- `__SUNPRO_C=0x580`
- `__'uname -s'_'uname -r'` (example: `__SunOS_5_7`)
- `__sparc` (SPARC)
- `__i386` (x86)
- `__BUILTIN_VA_ARG_INCR`
- `__SVR4`

The following is predefined in `-xa` and `-xt` modes only:

- `__RESTRICT`

The compiler also predefines the object-like macro `__PRAGMA_REDEFINE_EXTNAME`, to indicate the pragma will be recognized.

B.2.8 `-d[y | n]`

`-dy` specifies dynamic linking, which is the default, in the link editor.

`-dn` specifies static linking in the link editor.

This option and its arguments are passed to `ld(1)`.

Note – This option causes fatal errors if you use it in combination with dynamic libraries. Most system libraries are only available as dynamic libraries.

B.2.9 `-dalign`

(SPARC) Obsolete. You should not use this option. Use `-xmemalign=8s` instead. See [Section B.2.105, “`-xmemalign=ab`” on page B-63](#) for more information. For a complete list of obsolete options, see [Section A.1.15, “Obsolete Options” on page A-13](#).

B.2.10 `-E`

Runs the source file through the preprocessor only and sends the output to `stdout`. The preprocessor is built directly into the compiler, except in `-Xs` mode, where `/usr/ccs/lib/cpp` is invoked. Includes the preprocessor line numbering information. See also the `-P` option.

B.2.11 `-errfmt[=[no%]error]`

Use this option if you want to prefix the string “error:” to the beginning of error messages so they are more easily distinguishable from warning messages. The prefix is also attached to warnings that are converted to errors by `-errwarn`.

TABLE B-1 The `-errfmt` Flags

Flag	Meaning
<code>error</code>	Add the prefix “error:” to all error messages.
<code>no%error</code>	Do not add the prefix “error:” to any error messages.

If you do not specify this option, the compiler sets it to `-errfmt=no%error`. If you specify `-errfmt`, but do not supply a value, the compiler sets it to `-errfmt=error`.

B.2.12 `-erroff[=t]`

This command suppresses C compiler warning messages and has no effect on error messages. This option applies to all warning messages whether or not they have been designated by `-errwarn` to cause a non-zero exit status.

t is a comma-separated list that consists of one or more of the following: *tag*, `no%tag`, `%all`, `%none`. Order is important; for example, `%all, no%tag` suppresses all warning messages except *tag*. The following table lists the `-erroff` values:

TABLE B-2 The `-erroff` Flags

Flag	Meaning
<i>tag</i>	Suppresses the warning message specified by this <i>tag</i> . You can display the tag for a message by using the <code>-errtags=yes</code> option.
<code>no%tag</code>	Enables the warning message specified by this <i>tag</i>
<code>%all</code>	Suppresses all warning messages
<code>%none</code>	Enables all warning messages (default)

The default is `-erroff=%none`. Specifying `-erroff` is equivalent to specifying `-erroff=%all`.

Only warning messages from the C compiler front-end that display a tag when the `-errtags` option is used can be suppressed with the `-erroff` option. You can achieve finer control over error message suppression. See [Section 2.8.6, “error_messages”](#) on page 2-12.

B.2.13 `-errshort[=i]`

Use this option to control how much detail is in the error message produced by the compiler when it discovers a type mismatch. This option is particularly useful when the compiler discovers a type mismatch that involves a large aggregate.

i can be one of the following:

TABLE B-3 The `-errshort` Flags

Flag	Meaning
short	Error messages are printed in short form with no expansion of types. Aggregate members are not expanded, neither are function argument and return types.
full	Error messages are printed in full verbose form showing the full expansion of the mismatched types.
tags	Error messages are printed with tag names for types which have tag names. If there is no tag name, the type is shown in expanded form.

If you do not specify `-errshort`, the compiler sets the option to `-errshort=full`. If you specify `-errshort`, but do not provide a value, the compiler sets the option to `-errshort=tags`.

This option does not accumulate, it accepts the last value specified on the command line.

B.2.14 `-errtags[=a]`

Displays the message tag for each warning message of the C compiler front-end that can be suppressed with the `-erroff` option or made a fatal error with the `-errwarn` option. Messages from the C compiler driver and other components of the C compilation system do not have error tags, and cannot be suppressed with `-erroff` and made fatal with `-errwarn`.

a can be either `yes` or `no`. The default is `-errtags=no`. Specifying `-errtags` is equivalent to specifying `-errtags=yes`.

B.2.15 `-errwarn[=t]`

Use the `-errwarn` option to cause the C compiler to exit with a failure status for the given warning messages.

t is a comma-separated list that consists of one or more of the following: *tag*, `no%tag`, `%all`, `%none`. Order is important; for example `%all, no%tag` causes `cc` to exit with a fatal status if any warning except *tag* is issued.

The warning messages generated by the C compiler change from release to release as the compiler error checking improves and features are added. Code that compiles using `-errwarn=%all` without error may not compile without error in the next release of the compiler.

Only warning messages from the C compiler front-end that display a tag when the `-errtags` option is used can be specified with the `-errwarn` option to cause the C compiler to exit with a failure status.

The following table details the `-errwarn` values:

TABLE B-4 The `-errwarn` Flags

Flag	Meaning
<i>tag</i>	Cause <code>cc</code> to exit with a fatal status if the message specified by this <i>tag</i> is issued as a warning message. Has no effect if <i>tag</i> is not issued.
<code>no%tag</code>	Prevent <code>cc</code> from exiting with a fatal status if the message specified by <i>tag</i> is issued only as a warning message. Has no effect if the message specified by <i>tag</i> is not issued. Use this option to revert a warning message that was previously specified by this option with <i>tag</i> or <code>%all</code> from causing <code>cc</code> to exit with a fatal status when issued as a warning message.
<code>%all</code>	Cause the compiler to exit with a fatal status if any warning messages are issued. <code>%all</code> can be followed by <code>no%tag</code> to exempt specific warning messages from this behavior.
<code>%none</code>	Prevents any warning message from causing the compiler to exit with a fatal status should any warning message be issued.

The default is `-errwarn=%none`. If you specify `-errwarn` alone, it is equivalent to `-errwarn=%all`.

B.2.16 `-fast`

This option is a macro that can be effectively used as a starting point for tuning an executable for maximum runtime performance. `-fast` is a macro that can change from one release of the compiler to the next and expands to options that are target platform specific. Use the `-#` option or `-xdryrun` to examine the expansion of `-fast`, and incorporate the appropriate options of `-fast` into the ongoing process of tuning the executable.

The expansion of `-fast` now includes the new `-xlibmopt` option. This option enables the compiler to use a library of optimized math routines. For more information, see [Section B.2.96, “-xlibmopt” on page B-59](#).

The `-fast` option impacts the value of `errno`. See [Section 2.10, “The Value of `errno`” on page 2-24](#) for more information.

Modules that are compiled with `-fast` must also be linked with `-fast`. For a complete list of all compiler options that must be specified at both compile time and at link time, see [“Compile-Time and Link-Time Options” on page A 3](#).

The `-fast` option is unsuitable for programs intended to run on a different target than the compilation machine. In such cases, follow `-fast` with the appropriate `-xtarget` option. For example:

```
cc -fast -xtarget=ultra ...
```

For C modules that depend on exception handling specified by SUID, follow `-fast` by `-xnolibmil`:

```
% cc -fast -xnolibmil
```

With `-xlibmil`, exceptions cannot be noted by setting `errno` or calling `matherr(3m)`.

The `-fast` option is unsuitable for programs that require strict conformance to the IEEE 754 Standard.

The following table lists the set of options selected by `-fast` across platforms.

TABLE B-5 The `-fast` Expansion Flags

Option	SPARC	x86
<code>-fns</code>	X	X
<code>-fsimple=2</code>	X	X
<code>-fsingle</code>	X	X
<code>-nofstore</code>	-	X
<code>-xalias_level=basic</code>	X	-
<code>-xbuiltin=%all</code>	X	X
<code>-xdepend</code>	X	X
<code>-xlibmil</code>	X	X
<code>-xlibmopt</code>	X	X
<code>-xmemalign=8s</code>	X	-
<code>-xO5</code>	X	X

TABLE B-5 The `-fast` Expansion Flags (*Continued*)

Option	SPARC	x86
<code>-xprefetch=auto,explicit</code>	X	-
<code>-xregs=frameptr</code>	-	X
<code>-xtarget=native</code>	X	X

Note – Some optimizations make certain assumptions about program behavior. If the program does not conform to these assumptions, the application may crash or produce incorrect results. Please refer to the description of the individual options to determine if your program is suitable for compilation with `-fast`.

The optimizations performed by these options may alter the behavior of programs from that defined by the ISO C and IEEE standards. See the description of the specific option for details.

`-fast` acts like a macro expansion on the command line. Therefore, you can override the optimization level and code generation option aspects by following `-fast` with the desired optimization level or code generation option. Compiling with the `-fast -xO4` pair is like compiling with the `-xO2 -xO4` pair. The latter specification takes precedence.

Do not use this option for programs that depend on IEEE standard exception handling; you can get different numerical results, premature program termination, or unexpected `SIGFPE` signals.

B.2.17 `-fd`

Reports K&R-style function definitions and declarations.

B.2.18 `-features=[[no%]extinl| %none]`

The compiler's treatment of extern inline functions conforms by default to the behavior specified by the ISO/IEC 9899:1999 C standard. Compile new codes with `-features=no%extinl` to obtain the same treatment of extern inline functions as provided by versions 5.5, or older, of the C and C++ compilers.

TABLE B-6 The `-features` Flags

Value	Meaning
<code>-features=extinl</code>	Generates extern inline functions as global functions. This is the default, which conforms with the 1999 C standard.
<code>-features=no%extinl</code>	Generates extern inline functions as static functions.
<code>-features=%none</code>	The option is disabled.

Old C and C++ objects (created with Sun compilers prior to this release) can be linked with new C and C++ objects with no change of behavior for the old objects. To get standard conforming behavior, you must recompile old code with the current compiler.

If you do not specify a setting for `-features`, the compiler sets it to `-features=extinl`.

B.2.19 `-flags`

Prints a brief summary of each available compiler option.

B.2.20 `-flteval[={any|2}]`

(x86) Use this option to control how floating point expression are evaluated.

TABLE B-7 The `-flteval` Flags

Flag	Meaning
2	Floating point expressions are evaluated as long double.
any	Floating point expressions are evaluated depending on the combination of the types of the variables and constants that make up an expression.

If you do not specify `-flteval`, the compiler sets it to `-flteval=any`. If you do specify `-flteval`, but do not provide a value, the compiler sets it to `-flteval=2`.

You must not specify the following options in combination with `-flteval=2`:

- `-fprecision`
- `-nofstore`
- `-xarch=amd64`
- `-xarch=sse2`

See also [Section D.1.1, “Precision of Floating Point Evaluators”](#) on page D-2.

B.2.21 `-fnonstd`

(SPARC) This option is a macro for `-fns` and `-ftrap=common`.

B.2.22 `-fns[={no|yes}]`

- (SPARC) Turns on the SPARC nonstandard floating-point mode.

The default is `-fns=no`, the SPARC standard floating-point mode. `-fns` is the same as `-fns=yes`.

Optional use of `=yes` or `=no` provides a way of toggling the `-fns` flag following some other macro flag that includes `-fns`, such as `-fast`.

On some SPARC systems, the nonstandard floating point mode disables “gradual underflow,” causing tiny results to be flushed to zero rather than producing subnormal numbers. It also causes subnormal operands to be replaced silently by zero. On those SPARC systems that do not support gradual underflow and subnormal numbers in hardware, use of this option can significantly improve the performance of some programs.

When nonstandard mode is enabled, floating point arithmetic may produce results that do not conform to the requirements of the IEEE 754 standard. See the Numerical Computation Guide for more information.

This option is effective only on SPARC systems and only if used when compiling the main program. On x86 systems, the option is ignored.

- (x86) Selects SSE flush-to-zero mode and, where available, denormals-are-zero mode.

This option causes subnormal results to be flushed to zero. Where available, this option also causes subnormal operands to be treated as zero.

This option has no effect on traditional x86 floating-point operations that do utilize the SSE or SSE2 instruction set.

B.2.23 `-fprecision=p`

(x86) `-fprecision={single, double, extended}`

Initializes the rounding-precision mode bits in the Floating-point Control Word to single (24 bits), double (53 bits), or extended (64 bits), respectively. The default floating-point rounding-precision mode is extended.

Note that on x86, only the precision, not exponent, range is affected by the setting of floating-point rounding precision mode.

B.2.24 `-fround=r`

Sets the IEEE 754 rounding mode that is established at runtime during the program initialization.

r must be one of: `nearest`, `tozero`, `negative`, `positive`.

The default is `-fround=nearest`.

The meanings are the same as those for the `ieee_flags` subroutine.

When *r* is `tozero`, `negative`, or `positive`, this flag sets the rounding direction mode to round-to-zero, round-to-negative-infinity, or round-to-positive-infinity respectively when a program begins execution. When *r* is `nearest` or the `-fround` flag is not used, the rounding direction mode is not altered from its initial value (round-to-nearest by default).

This option is effective only if used when compiling the main program.

B.2.25 `-fsimple[=n]`

Allows the optimizer to make simplifying assumptions concerning floating-point arithmetic.

The compiler defaults to `-fsimple=0`. Specifying `-fsimple`, is equivalent to `-fsimple=1`.

If n is present, it must be 0, 1, or 2.

TABLE B-8 The `-fsimple` Flags

Value	Meaning
<code>-fsimple=0</code>	Permits no simplifying assumptions. Preserve strict IEEE 754 conformance.
<code>-fsimple=1</code>	Allows conservative simplifications. The resulting code does not strictly conform to IEEE 754, but numeric results of most programs are unchanged. With <code>-fsimple=1</code> , the optimizer can assume the following: <ul style="list-style-type: none">• IEEE 754 default rounding/trapping modes do not change after process initialization.• Computations producing no visible result other than potential floating point exceptions may be deleted.• Computations with Infinity or NaNs as operands need not propagate NaNs to their results; for example, $x*0$ may be replaced by 0.• Computations do not depend on sign of zero. With <code>-fsimple=1</code> , the optimizer is <i>not</i> allowed to optimize completely without regard to roundoff or exceptions. In particular, a floating-point computation cannot be replaced by one that produces different results with rounding modes held constant at runtime.
<code>-fsimple=2</code>	Enables use of SIMD instructions to compute reductions when <code>-xvector=simd</code> is in effect. The compiler attempts aggressive floating point optimizations that may cause many programs to produce different numeric results due to changes in rounding. For example, <code>-fsimple=2</code> permits the optimizer to replace all computations of x/y in a given loop with $x*z$, where x/y is guaranteed to be evaluated at least once in the loop, $z=1/y$, and the values of y and z are known to have constant values during execution of the loop.

Even with `-fsimple=2`, the optimizer is not permitted to introduce a floating point exception in a program that otherwise produces none.

See *Techniques for Optimizing Applications: High Performance Computing* written by Rajat Garg and Ilya Sharapov for a more detailed explanation of how optimization can impact precision.

B.2.26 -fsingle

(-Xt and -Xs modes only) Causes the compiler to evaluate `float` expressions as single precision rather than double precision. This option has no effect if the compiler is used in either -Xa or -Xc modes, as `float` expressions are already evaluated as single precision.

B.2.27 -fstore

(x86) Causes the compiler to convert the value of a floating-point expression or function to the type on the left-hand side of an assignment, when that expression or function is assigned to a variable, or when the expression is cast to a shorter floating-point type, rather than leaving the value in a register. Due to rounding and truncation, the results may be different from those that are generated from the register value. This is the default mode.

To turn off this option, use the `-nofstore` option.

B.2.28 -ftrap=t[, t...]

Sets the IEEE trapping mode in effect at startup but does not install a SIGFPE handler. You can use `ieee_handler(3M)` or `fex_set_handling(3M)` to simultaneously enable traps and install a SIGFPE handler. If you specify more than one value, the list is processed sequentially from left to right.

t can be one of the following values.

TABLE B-9 The `-ftrap` Flags

Flag	Meaning
[no%]division	[Do not] Trap on division by zero.
[no%]inexact	[Do not] Trap on inexact result.
[no%]invalid	[Do not] Trap on invalid operation.
[no%]overflow	[Do not] Trap on overflow.
[no%]underflow	[Do not] Trap on underflow.
%all	Trap on all of the above.
%none	Trap on none of the above.
common	Trap on invalid, division by zero, and overflow.

Note that the [no%] form of the option is used only to modify the meaning of the %all and common values, and must be used with one of these values, as shown in the example. The [no%] form of the option by itself does not explicitly cause a particular trap to be disabled.

If you do not specify `-ftrap`, the compiler assumes `-ftrap=%none`.

Example: `-ftrap=%all,no%inexact` means to set all traps except `inexact`.

If you compile one routine with `-ftrap=t`, compile all routines of the program with the same `-ftrap=t` option; otherwise, you might get unexpected results.

Use the `-ftrap=inexact` trap with caution. Use of `-ftrap=inexact` results in the trap being issued whenever a floating-point value cannot be represented exactly. For example, the following statement generates this condition:

```
x = 1.0 / 3.0;
```

This option is effective only if used when compiling the main program. Be cautious when using this option. If you wish to enable the IEEE traps, use `-ftrap=common`.

B.2.29 -G

Produce a shared object rather than a dynamically linked executable. This option is passed to `ld(1)`, and cannot be used with the `-dn` option.

When you use the `-G` option, the compiler does not pass any default `-l` options to `ld`. If you want the shared library to have a dependency on another shared library, you must pass the necessary `-l` option on the command line.

If you are creating a shared object by specifying `-G` along with other compiler options that must be specified at both compile time and link time, make sure that those same options are also specified when you link with the resulting shared object.

When you create a shared object, all the object files that are compiled with `-xarch=v9` must also be compiled with an explicit `-xcode` value as documented in [Section B.2.78, “-xcode\[=v\]”](#) on page B-45.

B.2.30 -g

Produces additional symbol table information for debugging with `dbx(1)` and the Performance Analyzer `analyzer(1)`.

If you specify `-g`, and the optimization level is `-xO3` or lower, the compiler provides best-effort symbolic information with almost full optimization. Tail-call optimization and back-end inlining are disabled.

If you specify `-g` and the optimization level is `-xO4`, the compiler provides best-effort symbolic information with full optimization.

Compile with the `-g` option to use the full capabilities of the Performance Analyzer. While some performance analysis features do not require `-g`, you must compile with `-g` to view annotated source, some function level information, and compiler commentary messages. See the `analyzer(1)` man page and the *Performance Analyzer* manual for more information.

The commentary messages that are generated with `-g` describe the optimizations and transformations that the compiler made while compiling your program. Use the `er_src(1)` command to display the messages, which are interleaved with the source code.

Note – In previous releases, this option forced the compiler to use the incremental linker (`ild`) by default instead of the linker (`ld`) for link-only invocations of the compiler. That is, with `-g`, the compiler’s default behavior was to automatically invoke `ild` in place of `ld` whenever you used the compiler to link object files, unless you specified `-G` or source files on the command line. This is no longer the case. The incremental linker is no longer available.

For more information on debugging, see the *Debugging a Program With dbx* manual.

B.2.31 `-H`

Prints to standard error, one per line, the path name of each file included during the current compilation. The display is indented so as to show which files are included by other files.

Here, the program `sample.c` includes the files, `stdio.h` and `math.h`; `math.h` includes the file, `floatingpoint.h`, which itself includes functions that use `sys/ieeefp.h`:

```
% cc -H sample.c
  /usr/include/stdio.h
  /usr/include/math.h
    /usr/include/floatingpoint.h
      /usr/include/sys/ieeefp.h
```

B.2.32 `-h name`

Assigns a name to a shared dynamic library as a way to have different versions of a library. In general, the *name* after `-h` should be the same as the file name given after the `-o` option. The space between `-h` and *name* is optional.

The linker assigns the specified *name* to the library and records the name in the library file as the *intrinsic* name of the library. If there is no `-hname` option, then no intrinsic name is recorded in the library file.

When the runtime linker loads the library into an executable file, it copies the intrinsic name from the library file into the executable, into a list of needed shared library files. Every executable has such a list. If there is no intrinsic name of a shared library, then the linker copies the path of the shared library file instead.

B.2.33 `-I[- | dir]`

`-I dir` adds *dir* to the list of directories that are searched for `#include` files with relative file names prior to `/usr/include`, that is, those directory paths not beginning with a `/` (slash).

Directories for multiple `-I` options are searched in the order specified.

For more information on the search pattern of the compiler, see [Section 2.14.1, “Using the `-I-` Option to Change the Search Algorithm”](#) on page 2-28.

B.2.34 `-i`

Passes the option to the linker to ignore any `LD_LIBRARY_PATH` or `LD_LIBRARY_PATH_64` setting.

B.2.35 `-KPIC`

(SPARC) Obsolete. You should not use this option. Use `-xcode=pic32` instead.

For more information, see [Section B.2.78, “`-xcode\[=v\]`”](#) on page B-45. For a complete list of obsolete options, see [Section A.1.15, “Obsolete Options”](#) on page A-13.

(x86) `-KPIC` is identical to `-Kpic`.

B.2.36 -Kpic

(SPARC) Obsolete. You should not use this option. Use `-xcode=pic13` instead. For more information, see [Section B.2.78, “-xcode\[=v\]” on page B-45](#). For a complete list of obsolete options, see [Section A.1.15, “Obsolete Options” on page A-13](#).

(x86) Generate position-independent code for use in shared libraries (small model). Permits references to, at most, 2**11 unique external symbols.

B.2.37 -keeptmp

Retains temporary files created during compilation instead of deleting them automatically.

B.2.38 -Ldir

Adds *dir* to the list of directories searched for libraries by `ld(1)`. This option and its arguments are passed to `ld(1)`.

Note – Never specify the compiler installation area, `/usr/include`, `/lib`, or `/usr/lib`, as search directories.

B.2.39 -lname

Links with object library `libname.so`, or `libname.a`. The order of libraries in the command-line is important, as symbols are resolved from left to right.

This option must follow the *sourcefile* arguments.

B.2.40 -mc

Removes duplicate strings from the `.comment` section of the object file. When you use the `-mc` flag, `mcs -c` is invoked.

B.2.41 `-misalign`

(SPARC) Obsolete. You should not use this option. Use the `-xmemalign=1i` option instead. For more information, see [Section B.2.105, “-xmemalign=ab” on page B-63](#). For a complete list of obsolete options, see [Section A.1.15, “Obsolete Options” on page A-13](#).

B.2.42 `-misalign2`

(SPARC) Obsolete. You should not use this option. Use the `-xmemalign=2i` option instead. For more information, see [Section B.2.105, “-xmemalign=ab” on page B-63](#). For a complete list of obsolete options, see [Section A.1.15, “Obsolete Options” on page A-13](#).

B.2.43 `-mr[, string]`

`-mr` removes all strings from the `.comment` section. When you use this flag, `mcs -d -a` is invoked.

`-mr, string` removes all strings from the `.comment` section and inserts `string` in that section of the object file. If `string` contains embedded blanks, it must be enclosed in quotation marks. A null `string` results in an empty `.comment` section. This option is passed as `-d -astring` to `mcs`.

B.2.44 `-mt`

Macro option that expands to `-D_REENTRANT -lthread`. If you are doing your own multithread coding, you must use this option in the compile and link steps. For a complete list of all compiler options that must be specified at both compile time and at link time, see [TABLE 2-2](#). To obtain faster execution, this option requires a multiprocessor system. On a single-processor system, the resulting executable usually runs more slowly with this option.

B.2.45 `-native`

This option is a synonym for `-xtarget=native`.

B.2.46 `-nofstore`

(x86) Does not convert the value of a floating-point expression or function to the type on the left-hand side of an assignment, when that expression or function is assigned to a variable or is cast to a shorter floating-point type; rather, it leaves the value in a register. See also [Section B.2.27](#), “`-fstore`” on page B-15.

B.2.47 `-O`

Use default optimization level `-xO3`. The `-O` macro now expands to `-xO3` instead of `-xO2`.

The change in default yields higher run-time performance. However, `-xO3` may be inappropriate for programs that rely on all variables being automatically considered volatile. Typical programs that might have this assumption are device drivers and older multi-threaded applications that implement their own synchronization primitives. The work around is to compile with `-xO2` instead of `-O`.

B.2.48 `-o filename`

Names the output file *filename* (as opposed to the default, `a.out`). *filename* cannot be the same as *sourcefile*, since `cc` does not overwrite the source file. This option and its arguments are passed to `ld(1)`.

B.2.49 `-P`

Runs the source file through the C preprocessor only. It then puts the output in a file with a `.i` suffix. Unlike `-E`, this option does not include preprocessor-type line number information in the output. See also the `-E` option.

B.2.50 `-p`

Obsolete, see “`-xpg`” on page B 80.

B.2.51 `-Q[y | n]`

Emits or does not emit identification information to the output file. `-Qy` is the default.

If `-Qy` is used, identification information about each invoked compilation tool is added to the `.comment` section of output files, which is accessible with `mcs`. This option can be useful for software administration.

`-Qn` suppresses this information.

B.2.52 `-qp`

Same as `-p`.

B.2.53 `-Rdir[:dir]`

Passes a colon-separated list of directories used to specify library search directories to the runtime linker. If present and not null, it is recorded in the output object file and passed to the runtime linker.

If both `LD_RUN_PATH` and the `-R` option are specified, the `-R` option takes precedence.

B.2.54 `-S`

Directs `cc` to produce an assembly source file but not to assemble the program.

B.2.55 `-s`

Removes all symbolic debugging information from the output object file. This option cannot be specified with `-g`.

Passed to `ld(1)`.

B.2.56 `-Uname`

Undefines the preprocessor symbol *name*. This option removes any initial definition of the preprocessor symbol *name* created by `-D` on the same command line including those placed there by the command-line driver.

`-U` has no effect on any preprocessor directives in source files. You can give multiple `-U` options on the command line.

If the same *name* is specified for both `-D` and `-U` on the command line, *name* is undefined, regardless of the order the options appear. In the following example, `-U` undefines `__sun`:

```
cc -U__sun text.c
```

Preprocessor statements of the following form in `test.c` will not take effect because `__sun` is undefined.

```
#ifdef(__sun)
```

See [Section B.2.7, “`-Dname\[=tokens\]`”](#) on page B-4 for a list of predefined symbols.

B.2.57 `-V`

Directs `cc` to print the name and version ID of each component as the compiler executes.

B.2.58 `-v`

Directs the compiler to perform stricter semantic checks and to enable other lint-like checks. For example, the code:

```
#include <stdio.h>
main(void)
{
    printf("Hello World.\n");
}
```

compiles and executes without problem. With `-v`, it still compiles; however, the compiler displays this warning:

```
"hello.c", line 5: warning: function has no return statement:
main
```

`-v` does not give all the warnings that `lint(1)` does. Try running the above example through `lint`.

B.2.59 `-Wc, arg`

Passes the argument *arg* to a specified component *c*. See [TABLE 1-1](#) for a list of components.

Each argument must be separated from the preceding only by a comma. All `-W` arguments are passed after the regular command-line arguments. A comma can be part of an argument by using the escape character `\` (backslash) immediately before the comma. All `-W` arguments are passed after the regular command-line arguments.

For example, `-Wa, -o, objfile` passes `-o` and `objfile` to the assembler, in that order. Also, `-Wl, -I, name` causes the linking phase to override the default name of the dynamic linker, `/usr/lib/ld.so.1`.

The order in which the argument(s) are passed to a tool with respect to the other specified command line options may change.

c can be one of the following:

TABLE B-10 The `-W` Flags

Flag	Value
a	Assembler: (fbc); (gas)
c	C code generator: (cg) (SPARC);
d	cc driver*
h	Intermediate code translator (ir2hf)(x86)
i	Interprocedural optimizer (ube_ipa)(x86)
l	Link editor (ld)
m	mcs
O (Capital o)	Interprocedural optimizer
o (Lowercase o)	Postoptimizer

TABLE B-10 The `-w` Flags

Flag	Value
<code>p</code>	Preprocessor (<code>cpp</code>)
<code>u</code>	C code generator (<code>ube</code>) (<i>x86</i>)
<code>0</code> (Zero)	Compiler (<code>acomp</code>) (<code>ssbd</code> , <i>SPARC</i>)
<code>2</code>	Optimizer: (<code>iropt</code>)

* You cannot use `-w` to pass the `cc` options listed in this chapter to the C compiler.

B.2.60 `-w`

Suppresses compiler warning messages.

This option overrides the `error_messages` pragma.

B.2.61 `-X[c|a|t|s]`

The `-X` (note uppercase `X`) options specify varying degrees of compliance to the ISO C standard. The value of `-xc99` affects which version of the ISO C standard the `-X` option applies. The `-xc99` option defaults to `-xc99=all` which supports the 1999 ISO/IEC C standard. `-xc99=none` supports the 1990 ISO/IEC C standard. See [Appendix D](#) for a discussion of supported 1999 ISO/IEC features. See [Appendix H](#) for a discussion of differences between ISO/IEC C and K&R C.

The default mode is `-xa`.

`-Xc`

(`c` = conformance) Issues errors and warnings for programs that use non-ISO C constructs. This option is strictly conformant ISO C, without K&R C compatibility extensions. The predefined macro `__STDC__` has a value of 1 with the `-Xc` option.

`-Xa`

This is the default compiler mode. ISO C plus K&R C compatibility extensions, with semantic changes required by ISO C. Where K&R C and ISO C specify different semantics for the same construct, the compiler uses the ISO C interpretation. If the `-Xa` option is used in conjunction with the `-xtransition` option, the compiler issues warnings about the different semantics. The predefined macro `__STDC__` has a value of 0 with the `-Xa` option.

`-Xt`

(t = transition) This option uses ISO C plus K&R C compatibility extensions *without* semantic changes required by ISO C. Where K&R C and ISO C specify different semantics for the same construct, the compiler uses the K&R C interpretation. If you use the `-xt` option in conjunction with the `-xtransition` option, the compiler issues warnings about the different semantics. The predefined macro `__STDC__` has a value of 0 with the `-xt` option.

`-Xs`

(s = K&R C) Attempts to warn about all language constructs that have differing behavior between ISO C and K&R C. The compiler language includes all features compatible with K&R C. This option invokes `cpp` for preprocessing. `__STDC__` is not defined in this mode.

B.2.62 `-x386`

(x86) Obsolete. You should not use this option. Use `-xchip=generic` instead. For a complete list of obsolete options, see [Section A.1.15, “Obsolete Options” on page A-13](#).

B.2.63 `-x486`

(x86) Obsolete. You should not use this option. Use `-xchip=generic` instead. For a complete list of obsolete options, see [Section A.1.15, “Obsolete Options” on page A-13](#).

B.2.64 `-xa`

Obsolete. Do not use this option. Use `-xprofile=tcov` instead. For a complete list of obsolete options and flags, see [Section A.1.15, “Obsolete Options” on page A-13](#).

B.2.65 `-xalias_level[=l]`

The compiler uses the `-xalias_level` option to determine what assumptions it can make in order to perform optimizations using type-based alias-analysis. This option places the indicated alias level into effect for the translation units being compiled.

If you do not specify the `-xalias_level` command, the compiler assumes `-xalias_level=any`. If you specify `-xalias_level` without a value, the default is `-xalias_level=layout`.

The `-xalias_level` option requires optimization level `-xO3` or above. If optimization is set lower, a warning is issued and the `-xalias_level` option is ignored.

Remember that if you issue the `-xalias_level` option but you fail to adhere to all of the assumptions and restrictions about aliasing described for any of the alias levels, the behavior of your program is undefined.

Replace *l* with one of the terms in the following table.

TABLE B-11 The Levels of Alias-Disambiguation

Flag	Meaning
any	The compiler assumes that all memory references can alias at this level. There is no type-based alias analysis at the level of <code>-xalias_level=any</code> .
basic	<p>If you use the <code>-xalias_level=basic</code> option, the compiler assumes that memory references that involve different C basic types do not alias each other. The compiler also assumes that references to all other types can alias each other as well as any C basic type. The compiler assumes that references using <code>char *</code> can alias any other type.</p> <p>For example, at the <code>-xalias_level=basic</code> level, the compiler assumes that a pointer variable of type <code>int *</code> is not going to access a float object. Therefore it is safe for the compiler to perform optimizations that assume a pointer of type <code>float *</code> will not alias the same memory that is referenced with a pointer of type <code>int *</code>.</p>
weak	<p>If you use the <code>-xalias_level=weak</code> option, the compiler assumes that any structure pointer can point to any structure type.</p> <p>Any structure or union type that contains a reference to any type that is either referenced in an expression in the source being compiled or is referenced from outside the source being compiled, must be declared prior to the expression in the source being compiled.</p> <p>You can satisfy this restriction by including all the header files of a program that contain types that reference any of the types of the objects referenced in any expression of the source being compiled.</p> <p>At the level of <code>-xalias_level=weak</code>, the compiler assumes that memory references that involve different C basic types do not alias each other. The compiler assumes that references using <code>char *</code> alias memory references that involve any other type.</p>

TABLE B-11 The Levels of Alias-Disambiguation (*Continued*)

Flag	Meaning
layout	<p>If you use the <code>-xalias_level=layout</code> option, the compiler assumes that memory references that involve types with the same sequence of types in memory can alias each other.</p> <p>The compiler assumes that two references with types that do not look the same in memory do not alias each other. The compiler assumes that any two memory accesses through different struct types alias if the initial members of the structures look the same in memory. However, at this level, you should not use a pointer to a struct to access some field of a dissimilar struct object that is beyond any of the common initial sequence of members that look the same in memory between the two structs. This is because the compiler assumes that such references do not alias each other.</p> <p>At the level of <code>-xalias_level=layout</code> the compiler assumes that memory references that involve different C basic types do not alias each other. The compiler assumes that references using <code>char *</code> can alias memory references involving any other type.</p>
strict	<p>If you use the <code>-xalias_level=strict</code> option, the compiler assumes that memory references, that involve types such as structs or unions, that are the same when tags are removed, can alias each other. Conversely, the compiler assumes that memory references involving types that are not the same even after tags are removed do not alias each other.</p> <p>However, any structure or union type that contains a reference to any type that is part of any object referenced in an expression in the source being compiled, or is referenced from outside the source being compiled, must be declared prior to the expression in the source being compiled.</p> <p>You can satisfy this restriction by including all the header files of a program that contain types that reference any of the types of the objects referenced in any expression of the source being compiled. At the level of <code>-xalias_level=strict</code> the compiler assumes that memory references that involve different C basic types do not alias each other. The compiler assumes that references using <code>char *</code> can alias any other type.</p>
std	<p>If you use the <code>-xalias_level=std</code> option, the compiler assumes that types and tags need to be the same to alias, however, references using <code>char *</code> can alias any other type. This rule is the same as the restrictions on the dereferencing of pointers that are found in the 1999 ISO C standard. Programs that properly use this rule will be very portable and should see good performance gains under optimization.</p>
strong	<p>If you use the <code>-xalias_level=strong</code> option, the same restrictions apply as at the <code>std</code> level, but additionally, the compiler assumes that pointers of type <code>char *</code> are used only to access an object of type <code>char</code>. Also, the compiler assumes that there are no interior pointers. An interior pointer is defined as a pointer that points to a member of a struct.</p>

B.2.66 `-xarch=isa`

Specify instruction set architecture (ISA). If you use this option with optimization, the appropriate choice can provide good performance of the executable on the specified architecture. An inappropriate choice results in a binary program that is not executable on the intended target platform. Architectures that are accepted by `-xarch` are shown in [TABLE B-12](#):

TABLE B-12 The `-xarch` Flags

Platform	Valid <code>-xarch</code> Keywords
SPARC	<code>generic</code> , <code>generic64</code> , <code>native</code> , <code>native64</code> , <code>v8a</code> , <code>v8</code> , <code>v8plus</code> , <code>v8plusa</code> , <code>v8plusb</code> , <code>v9</code> , <code>v9a</code> , <code>v9b</code>
x86	<code>386</code> , <code>amd64</code> , <code>generic</code> , <code>generic64</code> , <code>native</code> , <code>pentium_pro</code> , <code>sse</code> , <code>sse2</code>

Note that although `-xarch` can be used alone, it is part of the expansion of the `-xtarget` option and may be used to override the `-xarch` value that is set by a specific `-xtarget` option. For example:

```
% cc -xtarget=ultra2 -xarch=v8plusb ...
```

overrides the `-xarch=v8` set by `-xtarget=ultra2`.

B.2.66.1 `-xarch` Flags and Specifics of SPARC

The following table details the performance of an executable that is compiled with a given `-xarch` option and then executed by various SPARC processors. The purpose of this table is to help you identify the best `-xarch` option for your executable given a particular target machine. Start by identifying the range of machines that are of interest to you and then consider the cost of maintaining multiple binaries versus the benefit of extracting the last iota of performance from newer machines.

TABLE B-13 The `-xarch` Matrix

		Instruction Set of SPARC Machine:				
		V8a	V8	V9 (Non-Sun Processor)	V9 (Sun processor)	V9b
v8a		N	S	S	S	S

** Note: An executable compiled with this instruction set may perform nominally on a V9 non-Sun processor chip or it may not execute at all. Check with your hardware vendor to make sure your executable can run on its target machine.

TABLE B-13 The `-xarch` Matrix (Continued)

		Instruction Set of SPARC Machine:				
-xarch compilation option	v8	PD	N	S	S	S
	v8plus	NE	NE	N	S	S
	v8plusa	NE	NE	**	N	S
	v8plusb	NE	NE	**	NE	N
	v9	NE	NE	N	S	S
	v9a	NE	NE	**	N	S
	v9b	NE	NE	**	NE	N

** Note: An executable compiled with this instruction set may perform nominally on a V9 non-Sun processor chip or it may not execute at all. Check with your hardware vendor to make sure your executable can run on its target machine.

- N reflects Nominal performance. The program executes and takes full advantage of the processor's instruction set.
- S reflects Satisfactory performance. The program executes but may not exploit all available processor instructions.
- PD reflects Performance Degradation. The program executes, but depending on the instructions used, may experience slight to significant performance degradation. The degradation occurs when instructions that are not implemented by the processor are emulated by the kernel.
- NE means Not Executable. The program will not execute because the kernel does not emulate the instructions that are not implemented by the processor.

If you are compiling your executable with the `v8plus` or `v8plusa` instruction set, consider compiling with `v9` or `v9a` instead. The `v8plus` and `v8plusa` options are provided so that programs can take advantage of some SPARC V9 and UltraSPARC features prior to the availability of Solaris 8 software with its support for 64-bit programs. Programs compiled with the `v8plus` or `v8plusa` option are not portable to SPARC V8 or older machines. You can recompile such programs with `v9` or `v9a`, respectively, to take full advantage of all the features of SPARC V9 and UltraSPARC. *The V8+ Technical Specification* white paper, part number 802-7447-10, is available through your Sun representative and explains the limitations of `v8plus` and `v8plusa`.

- SPARC instruction set architectures V8 and V8a are binary compatible.
- Object binary files (.o) compiled with `v8plus` and `v8plusa` can be linked and can execute together, but only on a SPARC V8plusa compatible platform.
- Object binary files (.o) compiled with `v8plus`, `v8plusa`, and `v8plusb` can be linked and can execute together, but only on a SPARC V8plusb compatible platform.

- `-xarch` values `v9`, `v9a`, and `v9b` are only available on UltraSPARC 64-bit Solaris operating systems.
- Object binary files (`.o`) compiled with `v9` and `v9a` can be linked and can execute together, but will run only on a SPARC V9a compatible platform.
- Object binary files (`.o`) compiled with `v9`, `v9a`, and `v9b` can be linked and can execute together, but will run only on a SPARC V9b compatible platform.

For any particular choice, the generated executable may run much more slowly on earlier architectures. Also, although quad-precision (`REAL*16` and `long double`) floating-point instructions are available in many of these instruction set architectures, the compiler does not use these instructions in the code it generates.

The following table gives details for each of the `-xarch` keywords on SPARC platforms.

TABLE B-14 The `-xarch` Flags for SPARC Platforms

Flag	Meaning
<code>generic</code>	Compile for good performance on most 32-bit systems. This is no longer the default, see <code>v8plus</code> . This option uses the best instruction set for good performance on most processors without major performance degradation on any of them. With each new release, the definition of “best” instruction set may be adjusted, if appropriate.
<code>generic64</code>	Compile 64-bit object binaries for good performance on most 64-bit platform architectures. This option uses the best instruction set for good performance on Solaris operating systems with 64-bit kernels, without major performance degradation on any of them. With each new release, the definition of best instruction set may be adjusted, if appropriate. Currently, this is equivalent to <code>-xarch=v9</code> .
<code>native</code>	Compile for good performance on this system. The compiler chooses the appropriate setting for producing 32-bit binaries for the current system on which the processor is running.
<code>native64</code>	Compile 64-bit object binaries for good performance on this system. The compiler chooses the appropriate setting for producing 64-bit binaries for the system on which the processor is running.
<code>v7</code>	Compile for the SPARC-V7 ISA. (Obsolete) Current Solaris operating systems no longer support the SPARC V7 architecture, and programs compiled with this option run slower on current platforms. The default is <code>-xarch=v8plus</code> . Examples: <code>SPARCstation 1</code> , <code>SPARCstation 2</code> .

TABLE B-14 The `-xarch` Flags for SPARC Platforms (*Continued*)

Flag	Meaning
<code>v8a</code>	<p>Compile for the V8a version of the SPARC-V8 ISA.</p> <p>By definition, <code>V8a</code> means the V8 ISA, but without the <code>fsmuld</code> instruction. This option enables the compiler to generate code for good performance on the V8a ISA.</p> <p>Example: Any system based on the microSPARC I chip architecture</p>
<code>v8</code>	<p>Compile for the SPARC-V8 ISA.</p> <p>Enables the compiler to generate code for good performance on the V8 architecture.</p> <p>Example: SPARCstation 10</p>
<code>v8plus</code>	<p>Compile for the V8plus version of the SPARC-V9 ISA.</p> <p>This is the default. By definition, <code>V8plus</code> means the V9 ISA, but limited to the 32-bit subset defined by the V8plus ISA specification, without the Visual Instruction Set (VIS), and without other implementation-specific ISA extensions.</p> <ul style="list-style-type: none">• This option enables the compiler to generate code for good performance on the V8plus ISA.• The resulting object code is in SPARC-V8+ ELF32 format and only executes in a Solaris UltraSPARC environment—it does not run on a V7 or V8 processor. <p>Example: Any system based on the UltraSPARC chip architecture</p>
<code>v8plusa</code>	<p>Compile for the V8plusa version of the SPARC-V9 ISA.</p> <p>By definition, <code>V8plusa</code> means the V8plus architecture, plus the Visual Instruction Set (VIS) version 1.0, and with UltraSPARC extensions.</p> <ul style="list-style-type: none">• This option enables the compiler to generate code for good performance on the UltraSPARC architecture, but limited to the 32-bit subset defined by the V8plus specification.• The resulting object code is in SPARC-V8+ ELF32 format and only executes in a Solaris UltraSPARC environment—it does not run on a V8 processor. <p>Example: Any system based on the UltraSPARC chip architecture</p>
<code>v8plusb</code>	<p>Compile for the V8plusb version of the SPARC-V8plus ISA with UltraSPARC III extensions.</p> <p>Enables the compiler to generate object code for the UltraSPARC architecture, plus the Visual Instruction Set (VIS) version 2.0, and with UltraSPARC III extensions.</p> <ul style="list-style-type: none">• The resulting object code is in SPARC-V8+ ELF32 format and executes only in a Solaris UltraSPARC III environment.• Compiling with this option uses the best instruction set for good performance on the UltraSPARC III architecture.

TABLE B-14 The `-xarch` Flags for SPARC Platforms (*Continued*)

Flag	Meaning
v9	<p>Compile for the SPARC-V9 ISA.</p> <p>Enables the compiler to generate code for good performance on the V9 SPARC architecture.</p> <ul style="list-style-type: none">• The resulting .o object files are in ELF64 format and can only be linked with other SPARC-V9 object files in the same format.• The resulting executable can only be run on an UltraSPARC processor running a 64-bit enabled Solaris operating system with the 64-bit kernel.• <code>-xarch=v9</code> is only available when compiling in a 64-bit enabled Solaris operating system.
v9a	<p>Compile for the SPARC-V9 ISA with UltraSPARC extensions.</p> <p>Adds to the SPARC-V9 ISA the Visual Instruction Set (VIS) and extensions specific to UltraSPARC processors, and enables the compiler to generate code for good performance on the V9 SPARC architecture.</p> <ul style="list-style-type: none">• The resulting .o object files are in ELF64 format and can only be linked with other SPARC-V9 object files in the same format.• The resulting executable can only be run on an UltraSPARC processor running a 64-bit enabled Solaris operating system with the 64-bit kernel.• <code>-xarch=v9a</code> is only available when compiling in a 64-bit enabled Solaris operating system.
v9b	<p>Compile for the SPARC-V9 ISA with UltraSPARC III extensions.</p> <p>Adds UltraSPARC III extensions and VIS version 2.0 to the V9a version of the SPARC-V9 ISA. Compiling with this option uses the best instruction set for good performance in a Solaris UltraSPARC III environment.</p> <ul style="list-style-type: none">• The resulting object code is in SPARC-V9 ELF64 format and can only be linked with other SPARC-V9 object files in the same format.• The resulting executable can only be run on an UltraSPARC III processor running a 64-bit enabled Solaris operating system with the 64-bit kernel.• <code>-xarch=v9b</code> is only available when compiling in a 64-bit enabled Solaris operating system.

B.2.66.2 -xarch Flags for x86

The following table lists the `-xarch` flags on the x86 architecture.

TABLE B-15 The `-xarch` Flags on x86

Flag	Meaning
<code>386</code>	Limits the instruction set to the 386/486 architecture.
<code>amd64</code>	Compile for 64-bit the Solaris OS on x86-based platforms.
<code>amd64a</code>	Adds the AMD extensions (3DNow!, 3DNow! extensions, and MMX extensions) to the AMD64 architecture and generates 64-bit ELF format binary file.
<code>generic</code>	Limits instruction set to the x86 architecture and is equivalent to the <code>-xarch=386</code> option. This is the default.
<code>generic64</code>	Product 64-bit object binaries for good performance on most 64-bit platform architectures. This option uses the best instruction set for good performance on Solaris operating systems with 64-bit kernels, without major performance degradation on any of them. With each new release, the definition of "best" instruction set may be adjusted, if appropriate.
<code>native</code>	Compile for good performance on this system. This is the default for the <code>-fast</code> option. The compiler chooses the appropriate setting for the current system processor on which it is compiling.
<code>pentium_pro</code>	Limits the instruction set to the <code>pentium_pro</code> architecture.
<code>pentium_proa</code>	Adds the AMD extensions (3DNow!, 3DNow! extensions, and MMX extensions) to the 32-bit <code>pentium_pro</code> architecture.
<code>sse</code>	Adds the SSE instruction set to the <code>pentium_pro</code> architecture.
<code>ssea</code>	Adds the AMD extensions (3DNow!, 3DNow! extensions, and MMX extensions) to the 32-bit SSE architecture.
<code>sse2</code>	Adds the SSE2 instruction set to the <code>pentium_pro</code> architecture.
<code>sse2a</code>	Adds the AMD extensions (3DNow!, 3DNow! extensions, and MMX extensions) to the 32-bit SSE2 architecture.

Warning

Programs that are compiled with `-xarch` set to `sse` (Pentium 3) or `sse2` (Pentium 4) to run on Solaris x86 SSE or SSE2 compatible platforms must be run only on platforms that are SSE or SSE2 enabled.

Programs compiled with `-xarch` set to `pentium_proa` must be run on platforms supporting AMD 3DNow! and 3DNow! extensions.

Programs compiled with `-xarch` set to `ssea`, or `sse2a` must be run on platforms supporting AMD 3DNow! and 3DNow! extensions as well as platforms that are SSE or SSE2 enabled.

OS releases starting with Solaris 9 4/04 are SSE/SSE2-enabled on Pentium 3 or 4 compatible platforms. Earlier versions of Solaris OS are not SSE/SSE2-enabled.

Similarly, programs compiled with `-xarch=amd64` for Solaris x86 AMD64 platforms must be run on platforms that support the AMD 64-bit architecture. Note that AMD64 architecture supports SSE/SSE2.

Programs compiled with `-xarch=amd64a` must be run on platforms supporting the AMD 64-bit architecture as well as AMD 3DNow! and AMD 3DNow! extensions.

Program binaries compiled and built using these specialized `-xarch` hardware flags are checked by the operating system to verify that they are being run on appropriately enabled hardware. This verification is available with Sun Studio 11 running on the Solaris 10 operating system.

On systems prior to Solaris 10, no verification is done and it is the user's responsibility to ensure objects built using these flags are deployed on suitable hardware.

Running programs compiled with these `-xarch` flags on platforms that are not enabled with the appropriate features or instruction set extensions can result in "Illegal Instruction" errors, segmentation faults or incorrect results occurring without any explicit warning messages. This warning extends also to programs that employ `.il` inline assembly language functions or `__asm()` assembler code that utilize SSE, SSE2, AMD 64, and AMD 3DNow! instructions and AMD 3DNow! extensions.

If you compile and link in separate steps, always link using the compiler and using the same `-xarch` setting to ensure that the correct startup routine is linked.

Arithmetic results on x86 may differ from results on SPARC due to the x86 80-byte floating-point registers. To minimize these differences, use the `-fstore` option or compile with `-xarch=sse2` if the hardware supports SSE2.

B.2.66.3 The SPARC Default

The default architecture for which the C compiler produces code is now `v8plus` (UltraSPARC). Support for `v7` will be dropped in a future release.

The new default yields higher run-time performance for nearly all machines in current use. However, applications that are intended for deployment on pre-UltraSPARC computers no longer execute by default on those computers. Compile with `-xarch=v8` to ensure that the applications execute on those computers.

If you want to deploy on v8 systems, you must specify the option `-xarch=v8` explicitly on every compiler command line as well as any link-time commands. The provided system libraries run on v8 architectures.

If you want to deploy on v7 systems, you must specify the option `-xarch=v7` explicitly on every compiler command line as well as any link-time commands. The provided system libraries use the v8 instruction set. For this release, the only supported operating system for v7 is the Solaris 8 software. When a v8 instruction is encountered, the Solaris 8 operating system interprets the instruction in software. The program runs, but performance is degraded.

B.2.66.4 The x86 Default

For x86, `-xarch` defaults to `generic`. Note that `-fast` on x86 expands to `-xarch=native`. This option limits the code generated by the compiler to the instructions of the specified instruction set architecture. This option does not guarantee use of any target-specific instructions. However, use of this option may affect the portability of a binary program.

If you compile and link in separate steps, make sure you specify the same value for `-xarch` in both steps. For a complete list of all compiler options that must be specified at both compile time and at link time, see [TABLE 2-2](#).

B.2.67 `-xautopar`

Note – This option does not accept OpenMP parallelization directives and that the Sun-specific MP pragmas have been deprecated and are no longer supported. See the *OpenMP API User's Guide* for migration information to the directives of the standard.

(SPARC) Turns on automatic parallelization for multiple processors. Does dependence analysis (analyze loops for inter-iteration data dependence) and loop restructuring. If optimization is not at `-xO3` or higher, optimization is raised to `-xO3` and a warning is emitted.

Avoid `-xautopar` if you do your own thread management.

To achieve faster execution, this option requires a multiple processor system. On a single-processor system, the resulting binary usually runs slower.

To determine how many processors you have, use the `psrinfo` command:

```
% psrinfo
0  on-line since 01/12/95 10:41:54
1  on-line since 01/12/95 10:41:54
3  on-line since 01/12/95 10:41:54
4  on-line since 01/12/95 10:41:54
```

To request a number of processors, set the `PARALLEL` environment variable. The default is 1.

- Do not request more processors than are available.
- If `N` is the number of processors on the machine, then for a one-user, multiprocessor system, try `PARALLEL=N-1`.

If you use `-xautopar` and compile and link in *one* step, then linking automatically includes the microtasking library and the threads-safe C runtime library. If you use `-xautopar` and compile and link in *separate* steps, then you must also link with `-xautopar`. For a complete list of all compiler options that must be specified at both compile time and at link time, see [TABLE 2-2](#).

B.2.68 `-xbinopt={prepare|off}`

(SPARC) Instructs the compiler to prepare the binary for later optimizations, transformations and analysis, see `binopt(1)`. This option may be used for building executables or shared objects. This option must be used with optimization level `-xO1` or higher to be effective. There is a modest increase in size of the binary when built with this option.

If you compile in separate steps, `-xbinopt` must appear on both compile and link steps:

```
example% cc -c -xO1 -xbinopt=prepare a.c b.c
example% cc -o myprog -xbinopt=prepare a.o
```

If some source code is not available for compilation, this option may still be used to compile the remainder of the code. It should then be used in the link step that creates the final binary. In such a situation, only the code compiled with this option can be optimized, transformed or analyzed.

Compiling with `-xbinopt=prepare` and `-g` increases the size of the executable by including debugging information. The default is `-xbinopt=off`.

B.2.69 `-xbuiltin[=(%all|%none)]`

Use the `-xbuiltin[=(%all|%none)]` command when you want to improve the optimization of code that calls standard library functions. Many standard library functions, such as the ones defined in `math.h` and `stdio.h`, are commonly used by various programs. This command lets the compiler substitute intrinsic functions or inline system functions where profitable for performance. See the `er_src(1)` man page for an explanation of how to read compiler commentary in object files to determine for which functions the compiler actually makes a substitution.

However, these substitutions can cause the setting of `errno` to become unreliable. If your program depends on the value of `errno`, avoid this option. See also [Section 2.10, “The Value of `errno`” on page 2-24](#).

If you do not specify `-xbuiltin`, the default is `-xbuiltin=%none`, which means no functions from the standard libraries are substituted or inlined. If you specify `-xbuiltin`, but do not provide any argument, the default is `-xbuiltin%all`, which means the compiler substitutes intrinsics or inlines standard library functions as it determines the optimization benefit.

If you compile with `-fast`, then `-xbuiltin` is set to `%all`.

Note – `-xbuiltin` only inlines global functions defined in system header files, never static functions defined by the user.

B.2.70 `-xCC`

When you specify `-xc99=none` and `-xCC`, the compiler accepts the C++-style comments. In particular, `//` can be used to indicate the start of a comment.

B.2.71 `-xc99[=0]`

The `-xc99` option controls compiler recognition of the implemented features from the C99 standard (ISO/IEC 9899:1999, Programming Language - C).

o can be a comma separated list comprised of the following:

TABLE B-16 The `-xc99` Flags

Flag	Meaning
<code>[no]_lib</code>	[Do not] Enable the 1999 C standard library semantics of routines that appeared in both the 1990 and 1999 C standard.
<code>all</code>	Turn on recognition of supported C99 language features and enable the 1999 C standard library semantics of routines that appear in both the 1990 and 1999 C standard.
<code>none</code>	Turn off recognition of C99 language features, and do not enable the 1999 C standard library semantics of routines that appeared in both the 1990 and 1999 C standard.

If you do not specify `-xc99`, the compiler defaults to `-xc99=all,no_lib`. If you specify `-xc99` without any values, the option is set to `-xc99=all`.

Note – Though the compiler support-level defaults to the language features of the C99 standard, the standard headers provided by the Solaris 8 and Solaris 9 operating systems in `/usr/include` do not conform with the 1999 ISO/IEC C standard. If you encounter error messages, try specifying `-xc99=none` to obtain the 1990 ISO/IEC C standard behavior for these headers.

The 1999 C standard library semantics of routines that appeared in both the 1990 and 1999 C standard are not available and therefore cannot be enabled on Solaris 8 and Solaris 9 software. The compiler issues an error message when you specify `-xc99=lib` directly or indirectly on Solaris 8 or Solaris 9 software.

B.2.72 `-xcache[=c]`

SPARC: Defines cache properties for use by the optimizer. This option specifies the cache properties that the optimizer can use. It does not guarantee that any particular cache property is used. Although this option can be used alone, it is part of the expansion of the `-xtarget` option; its *primary* use is to override a value supplied by the `-xtarget` option.

This release introduces an optional property `[/ti]` which sets the number of threads that can share the cache. If you do not specify a value for `t`, the default is 1.

c must be one of the following:

- `generic`
- `native`
- `s1/l1/a1[/t1]`

- $s1/l1/a1[/t1]:s2/l2/a2[/t2]$
- $s1/l1/a1[/t1]:s2/l2/a2[/t2]:s3/l3/a3[/t3]$

The $s/l/a/t$ properties are defined as follows:

- si The size of the data cache at level i , in kilobytes
- li The line size of the data cache at level i , in bytes
- ai The associativity of the data cache at level i
- ti The number of hardware threads sharing the cache at level i

The following table lists the `-xcache` values.

TABLE B-17 The `-xcache` Flags

Flag	Meaning
generic	This is the default value which directs the compiler to use cache properties for good performance on most x86 and SPARC processors, without major performance degradation on any of them. With each new release, these best timing properties will be adjusted, if appropriate.
native	Set the parameters for the best performance on the host environment.
$s1/l1/a1[/t1]$	Define level 1 cache properties.
$s1/l1/a1[/t1]:s2/l2/a2[/t2]$	Define levels 1 and 2 cache properties.
$s1/l1/a1[/t1]:s2/l2/a2[/t2]:s3/l3/a3[/t3]$	Define levels 1, 2, and 3 cache properties.

Example: `-xcache=16/32/4:1024/32/1` specifies the following:

- | | |
|---------------------|------------------------------|
| Level 1 cache has: | Level 2 cache has: |
| 16K bytes | 1024K bytes |
| 32 bytes line size | 32 bytes line size |
| 4-way associativity | Direct mapping associativity |

B.2.73 `-xcg[89 | 92]`

(SPARC) Obsolete. You should not use this option. Current Solaris operating systems no longer support SPARC V7 architecture. Compiling with this option generates code that runs slower on current SPARC platforms. Use `-O` instead and take advantage of compiler defaults for `-xarch`, `-xchip`, and `-xcache`.

B.2.74 `-xchar[=o]`

The option is provided solely for the purpose of easing the migration of code from systems where the `char` type is defined as unsigned. Unless you are migrating from such a system, do not use this option. Only code that relies on the sign of a `char` type needs to be rewritten to explicitly specify signed or unsigned.

You can substitute one of the following for `o`:

TABLE B-18 The `-xchar` Flags

Flag	Meaning
<code>signed</code>	Treat character constants and variables declared as <code>char</code> as signed. This impacts the behavior of compiled code, it does not affect the behavior of library routines.
<code>s</code>	Equivalent to <code>signed</code>
<code>unsigned</code>	Treat character constants and variables declared as <code>char</code> as unsigned. This impacts the behavior of compiled code, it does not affect the behavior of library routines.
<code>u</code>	Equivalent to <code>unsigned</code>

If you do not specify `-xchar`, the compiler assumes `-xchar=s`.

If you specify `-xchar`, but do not specify a value, the compiler assumes `-xchar=s`.

The `-xchar` option changes the range of values for the type `char` only for code compiled with `-xchar`. This option does not change the range of values for type `char` in any system routine or header file. In particular, the value of `CHAR_MAX` and `CHAR_MIN`, as defined by `limits.h`, do not change when this option is specified. Therefore, `CHAR_MAX` and `CHAR_MIN` no longer represent the range of values encodable in a plain `char`.

If you use `-xchar`, be particularly careful when you compare a `char` against a predefined system macro because the value in the macro may be signed. This is most common for any routine that returns an error code which is accessed through a

macro. Error codes are typically negative values so when you compare a char against the value from such a macro, the result is always false. A negative number can never be equal to any value of an unsigned type.

It is strongly recommended that you never use `-xchar` to compile routines for any interface exported through a library. The Solaris ABI specifies type `char` as signed, and system libraries behave accordingly. The effect of making `char` unsigned has not been extensively tested with system libraries. Instead of using this option, modify your code so that it does not depend on whether type `char` is signed or unsigned. The sign of type `char` varies among compilers and operating systems.

B.2.75 `-xchar_byte_order[=o]`

Produce an integer constant by placing the characters of a multi-character character-constant in the specified byte order. You can substitute one of the following values for *o*:

- `low`: place the characters of a multi-character character-constant in low-to-high byte order.
- `high`: place the characters of a multi-character character-constant in high-to-low byte order.
- `default`: place the characters of a multi-character character-constant in an order determined by the compilation mode `-x[clatlsls]`. For more information, see [Section 2.1.2, “Character Constants” on page 2-2](#).

B.2.76 `-xcheck[=o]`

(SPARC) Compiling with `-xcheck=stkovf` adds a runtime check for stack overflow of the main thread in a singly-threaded program as well as slave-thread stacks in a multithreaded program. If a stack overflow is detected, a `SIGSEGV` is generated. If your application needs to handle a `SIGSEGV` caused by a stack overflow differently than it handles other address-space violations, see `sigaltstack(2)`.

You can substitute one of the following values for *o*:

TABLE B-19 The `-xcheck` Flags

Flag	Meaning
<code>%none</code>	Perform none of the <code>-xcheck</code> checks.
<code>%all</code>	Perform all of the <code>-xcheck</code> checks.
<code>stkovf</code>	Turns on stack-overflow checking.
<code>no%stkovf</code>	Turns off stack-overflow checking.

If you do not specify `-xcheck`, the compiler defaults to `-xcheck=%none`. If you specify `-xcheck` without any arguments, the compiler defaults to `-xcheck=%all` which turns on the runtime check for stack overflow.

The `-xcheck` option does not accumulate on the command line. The compiler sets the flag in accordance with the last occurrence of the command.

B.2.77 `-xchip[=c]`

Specifies the target processor for use by the optimizer.

`c` must be one of the following: `generic`, `old`, `super`, `super2`, `micro`, `micro2`, `hyper`, `hyper2`, `powerup`, `ultra`, `ultra2`, `ultra2e`, `ultra2i`, `ultra3`, `ultra3cu`, `386`, `486`, `pentium`, `pentium_pro`.

Although this option can be used alone, it is part of the expansion of the `-xtarget` option; its *primary* use is to override a value supplied by the `-xtarget` option.

This option specifies timing properties by specifying the target processor.

Some effects are:

- The ordering of instructions, that is, scheduling
- The way the compiler uses branches
- The instructions to use in cases where semantically equivalent alternatives are available

The following table lists the `-xchip` values for SPARC platforms:

TABLE B-20 The SPARC `-xchip` Flags

Flag	Meaning
<code>generic</code>	Use timing properties for good performance on most SPARC architectures. This is the default value that directs the compiler to use the best timing properties for good performance on most processors, without major performance degradation on any of them.
<code>native</code>	Set the parameters for the best performance on the host environment.
<code>old</code>	Uses timing properties of pre-SuperSPARC processors.
<code>super</code>	Uses timing properties of the SuperSPARC processors.
<code>super2</code>	Uses timing properties of the SuperSPARC II processors.
<code>micro</code>	Uses timing properties of the microSPARC processors.
<code>micro2</code>	Uses timing properties of the microSPARC II processors.

TABLE B-20 The SPARC `-xchip` Flags

Flag	Meaning
<code>hyper</code>	Uses timing properties of the hyperSPARC processors.
<code>hyper2</code>	Uses timing properties of the hyperSPARC II processors.
<code>powerup</code>	Uses timing properties of the Weitek PowerUp processors.
<code>ultra</code>	Uses timing properties of the UltraSPARC processors.
<code>ultra2</code>	Uses timing properties of the UltraSPARC II processors.
<code>ultra2e</code>	Uses timing properties of the UltraSPARC Iie processors.
<code>ultra2i</code>	Uses timing properties of the UltraSPARC Ili processors.
<code>ultra3</code>	Uses timing properties of the UltraSPARC III processors.
<code>ultra3cu</code>	Uses timing properties of the UltraSPARC III Cu processors.
<code>ultra3i</code>	Uses the timing properties of the UltraSPARC IIIi processors.
<code>ultra3iplus</code>	Uses the timing properties of the UltraSPARC IIIiplus processor.
<code>ultra4</code>	Uses timing properties of the UltraSPARC IV processors.
<code>ultra4plus</code>	Uses the timing properties of the UltraSPARC IVplus processor.
<code>ultraT1</code>	Uses the timing properties of the UltraSPARC T1 processor.

The following table lists the `-xchip` values for the x86 platforms:

TABLE B-21 The x86 `-xchip` Flags

Flag	Meaning
<code>generic</code>	Use timing properties for good performance on most x86 architectures. This is the default value that directs the compiler to use the best timing properties for good performance on most processors, without major performance degradation on any of them.
<code>native</code>	Set the parameters for the best performance on the host environment.
<code>386</code>	Uses timing properties of the x86 386 architecture.
<code>486</code>	Uses timing properties of the x86 486 architecture
<code>pentium</code>	Uses timing properties of the x86 pentium architecture
<code>pentium_pro</code>	Uses timing properties of the x86 pentium_pro architecture
<code>pentium3</code>	Uses the timing properties of the x86 Pentium 3 architecture.
<code>pentium4</code>	Uses the timing properties of the x86 Pentium 4 architecture.

B.2.78 `-xcode[=v]`

(SPARC) Specify code address space.

Note – You should build shared objects by specifying `-xcode=pic13` or `-xcode=pic32`. It is possible to build workable shared objects with `-xarch=v9` `-xcode=abs64` and with `-xarch=v8` `-xcode=abs32`, but these will be inefficient. Shared objects built with `-xarch=v9`, `-xcode=abs32`, or `-xarch=v9`, `-xcode=abs44` will not work.

v must be one of:

TABLE B-22 The `-xcode` Flags

Flag	Meaning
<code>abs32</code>	Generate 32-bit absolute addresses. Code + data + bss size is limited to 2**32 bytes. This is the default on 32-bit architectures: <code>-xarch=(generic v8 v8a v8plus v8plusa v8plusb)</code>
<code>abs44</code>	Generate 44-bit absolute addresses. Code + data + bss size is limited to 2**44 bytes. This is the default on 64-bit architectures: <code>-xarch=(v9 v9a v9b)</code>
<code>abs64</code>	Generate 64-bit absolute addresses. Available only on 64-bit architectures: <code>-xarch=(v9 v9a v9b)</code>
<code>pic13</code>	Generate position-independent code for use in shared libraries (small model). Equivalent to <code>-Kpic</code> . Permits references to at most 2**11 unique external symbols on 32-bit architectures, 2**10 on 64-bit architectures. The <code>-xcode=pic13</code> command is similar to <code>-xcode=pic32</code> , except that the size of the global offset table is limited to 8 Kbytes.
<code>pic32</code>	Generate position-independent code for use in shared libraries (large model). Equivalent to <code>-KPIC</code> . Permits references to at most 2**30 unique external symbols on 32-bit architectures, 2**29 on 64-bit architectures. Each reference to a global datum is generated as a dereference of a pointer in the global offset table. Each function call is generated in <code>pc</code> -relative addressing mode through a procedure linkage table. With this option, the global offset table spans the range of 32-bit addresses in those rare cases where there are too many global data objects for <code>-xcode=pic32</code> .

The default is `-xcode=abs32` for SPARC V8. The default for SPARC and UltraSPARC V9 (with `-xarch=v9|v9a|v9b`) has now changed. The default was `-xcode=abs64` but that has changed to `-xcode=abs44`.

When building shared dynamic libraries, the default `-xcode` values of `abs44` and `abs32` will not work with `-xarch=v9` or `v9a` or `v9b`, so a `-xcode` value must be given. Specify `-xcode=pic13` or `-xcode=pic32`. There are two nominal performance costs with `-xcode=pic13` and `-xcode=pic32` on SPARC:

- A routine compiled with either `-xcode=pic13` or `-xcode=pic32` executes a few extra instructions upon entry to set a register to point at a table (`_GLOBAL_OFFSET_TABLE_`) used for accessing a shared library's global or static variables.
- Each access to a global or static variable involves an extra indirect memory reference through `_GLOBAL_OFFSET_TABLE_`. If the compilation include `-xcode=pic32`, there are two additional instructions per global and static memory reference.

When considering the above costs, remember that the use of `-xcode=pic13` and `-xcode=pic32` can significantly reduce system memory requirements, due to the effect of library code sharing. Every page of code in a shared library compiled `-xcode=pic13` or `-xcode=pic32` can be shared by every process that uses the library. If a page of code in a shared library contains even a single non-pic (that is, absolute) memory reference, the page becomes nonsharable, and a copy of the page must be created each time a program using the library is executed.

The easiest way to tell whether or not a `.o` file has been compiled with `-xcode=pic13` or `-xcode=pic32` is with the `nm` command:

```
% nm file.o | grep _GLOBAL_OFFSET_TABLE_ U _GLOBAL_OFFSET_TABLE_
```

A `.o` file containing position-independent code contains an unresolved external reference to `_GLOBAL_OFFSET_TABLE_`, as indicated by the letter U.

To determine whether to use `-xcode=pic13` or `-xcode=pic32`, check the size of the Global Offset Table (GOT) by using `elfdump -c` (see the `elfdump(1)` man page for more information) and to look for the section header, `sh_name: .got`. The `sh_size` value is the size of the GOT. If the GOT is less than 8,192 bytes, specify `-xcode=pic13`, otherwise specify `-xcode=pic32`.

In general, use the following guidelines to determine how you should use `-xcode`:

- If you are building an executable you should not use `-xcode=pic13` or `-xcode=pic32`.
- If you are building an archive library only for linking into executables you should not use `-xcode=pic13` or `-xcode=pic32`.
- If you are building a shared library, start with `-xcode=pic13` and once the GOT size exceeds 8,192 bytes, use `-xcode=pic32`.
- If you are building an archive library for linking into shared libraries you should just use `-xcode=pic32`.

B.2.79 `-xcrossfile[=n]`

Enables optimization and inlining across source files. If specified, *n* can be 0 or 1.

The default is `-xcrossfile=0` which specifies that no crossfile optimizations are performed. `-xcrossfile` is equivalent to `-xcrossfile=1`.

Consider the following command-line example:

```
example% cc -xcrossfile -x04 -c f1.c f2.c
example% cc -xcrossfile -x04 -c f3.c f4.c
```

Cross-module optimizations occur between files `f1.c` and `f2.c`, and between `f3.c` and `f4.c`. No optimizations occur between `f1.c` and `f3.c` or `f4.c`.

Normally the scope of the compiler's analysis is limited to each separate file on the command line. For example, `-x04`'s automatic inlining is limited to subprograms defined and referenced within the same source file.

With `-xcrossfile`, the compiler analyzes all the files named on the command line as if they had been concatenated into a single source file. `-xcrossfile` is only effective when used with `-x04` or `-x05`.

However, this option has no effect when you direct the compiler to produce assembly source by specifying the `-S` option. Assembly (`.s`) files do not participate in optimizations and inlining across source files.

The files produced from this compilation are interdependent due to possible inlining, and must be used as a unit when they are linked into a program. If any one routine is changed and the files recompiled, they must all be recompiled. As a result, using this option affects the construction of make files.

See also `-xldscope`.

B.2.80 `-xcsi`

Allows the C compiler to accept source code written in locales that do not conform to the ISO C source character code requirements. These locales include: `ja_JP.PCK`.

The compiler translation phases required to handle such locales may result in significantly longer compilation times. You should only use this option when you compile source files that contain source characters from one of these locales.

The compiler does not recognize source code written in locales that do not conform to the ISO C source character code requirements unless you specify `-xcsi`.

B.2.81 `-xdebugformat=[stabs | dwarf]`

Specify `-xdebugformat=dwarf` if you maintain software which reads debugging information in the dwarf format. This option causes the compiler to generate debugging information by using the dwarf standard format and is the default.

TABLE B-23 The `-xdebugformat` Flags

Value	Meaning
stabs	<code>-xdebugformat=stabs</code> generates debugging information using the stabs standard format.
dwarf	<code>-xdebugformat=dwarf</code> generates debugging information using the dwarf standard format (default).

If you do not specify `-xdebugformat`, the compiler assumes `-xdebugformat=dwarf`. This option requires an argument.

This option affects the format of the data that is recorded with the `-g` option. Some small amount of debugging information is recorded even without `-g`, and the format of that information is also controlled with this option. So `-xdebugformat` has an effect even when `-g` is not used.

The `dbx` and Performance Analyzer software understand both stabs and dwarf format so using this option does not have any effect on the functionality of either tool.

See also the `dumpstabs(1)` and `dwarfdump(1)` man pages for more information.

B.2.82 `-xdepend=[yes | no]`

(SPARC) Analyzes loops for inter-iteration data dependencies and does loop restructuring.

Loop restructuring includes loop interchange, loop fusion, scalar replacement, and elimination of “dead” array assignments. If optimization is not at `-xO3` or higher, the compiler raises optimization to `-xO3` and issues a warning.

If you do not specify `-xdepend`, the default is `-xdepend=no` which means the compiler does not analyze loops for data dependencies. If you specify `-xdepend`, but do not specify an argument, the compiler sets the option to `-xdepend=yes` which means the compiler analyzes loops for data dependencies.

Dependency analysis is also included with `-xautopar` or `-xparallel`. The dependency analysis is done at compile time.

Dependency analysis may help on single-processor systems. However, if you try `-xdepend` on single-processor systems, you should not use either `-xautopar` or `-xexplicitpar`. If either of them is on, then the `-xdepend` optimization is done for multiple-processor systems.

B.2.83 `-xdryrun`

This option is a macro for `-###`.

B.2.84 `-xe`

Performs only syntax and semantic checking on the source file, but does not produce any object or executable code.

B.2.85 `-xexplicitpar`

Note – `-xexplicitpar` does not accept OpenMP parallelization directives. However, the Sun-specific MP pragmas have been deprecated and are no longer supported. However, the compiler supports the APIs specified by the OpenMP 2.5 standard instead. See the *OpenMP API User's Guide* for migration information to the directives of the standard.

(SPARC) Generates parallelized code based on specification of `#pragma MP` directives. You do the dependency analysis: analyze and specify loops for inter-iteration data dependencies. The software parallelizes the specified loops. If optimization is not at `-xO3` or higher, optimization is raised to `-xO3` and a warning is issued. Avoid `-xexplicitpar` if you do your own thread management.

To get faster code, this option requires a multiprocessor system. On a single-processor system, the generated code usually runs slower.

If you identify a loop for parallelization, and the loop has dependencies, you can get incorrect results, possibly different ones with each run, and with no warnings. Do not apply an explicit parallel pragma to a reduction loop. The explicit parallelization is done, but the reduction aspect of the loop is not done, and the results can be incorrect.

In summary, to parallelize explicitly:

- Analyze the loops to find those that are safe to parallelize.

- Insert `#pragma MP taskloop` to parallelize a loop. See the [Section 3.8.3, “Explicit Parallelization and Pragas” on page 3-22](#) for more information.
- Use the `-xexplicitpar` option.

The following is an example of inserting a parallel pragma immediately before the loop:

```
#pragma MP taskloop
for (j=0; j<1000; j++){
    ...
}
```

If you use `-xexplicitpar` and compile and link in *one* step, then linking automatically includes the microtasking library and the threads-safe C runtime library. If you use `-xexplicitpar` and compile and link in *separate* steps, then you must also *link* with `-xexplicitpar`. For a complete list of all compiler options that must be specified at both compile time and at link time, see [TABLE 2-2](#).

Note – Do not specify `-xexplicitpar` and `-xopenmp` together.

B.2.86 `-xF`

Enables optimal reordering of functions and variables by the linker.

This option instructs the compiler to place functions and/or data variables into separate section fragments, which enables the linker, using directions in a mapfile specified by the linker’s `-M` option, to reorder these sections to optimize program performance. Generally, this optimization is only effective when page fault time constitutes a significant fraction of program run time.

Reordering of variables can help solve the following problems which negatively impact run-time performance:

- Cache and page contention caused by unrelated variables that are near each other in memory.
- Unnecessarily large work-set size as a result of related variables which are not near each other in memory.
- Unnecessarily large work-set size as a result of unused copies of weak variables that decrease the effective data density.

Reordering variables and functions for optimal performance requires the following operations:

1. Compiling and linking with `-xF`.
2. Following the instructions in the "Program Performance Analysis" Tools manual regarding how to generate a mapfile for functions or following the instructions in the "Linker and Libraries Guide" regarding how to generate a mapfile for data.
3. Relinking with the new mapfile by using the linker's `-M` option.
4. Re-executing under the Analyzer to verify improvement.

`v` can be one or more of the following:

TABLE B-24 The `-xF` Flags

Value	Meaning
<code>[no%]func</code>	[Do not] fragment functions into separate sections.
<code>[no%]gbldata</code>	[Do not] fragment global data (variables with external linkage) into separate sections.
<code>%all</code>	Fragment functions and global data.
<code>%none</code>	Fragment nothing.

If you do not specify `-xF`, the default is `-xF=%none`. If you specify `-xF` without any arguments, the default is `-xF=%none, func`.

See also `analyzer(1)`, `debugger(1)`, `ld(1)` man pages

B.2.87 `-xhelp=f`

Displays on-line help information.

`f` must be either `flags`, or `readme`.

`-xhelp=flags` displays a summary of the compiler options.

`-xhelp=readme` displays the README file.

B.2.88 `-xhwcprof`

(SPARC) Enables compiler support for hardware counter-based profiling.

When `-xhwcprof=[enable|disable]` is enabled, the compiler generates information that helps tools match hardware-counter data reference and miss events with associated instructions. Corresponding data-types and structure-members may

also be identified in conjunction with symbolic information (produced with `-g`). This information can be useful in performance analysis and it is not easily identified from profiles based on code addresses, source statements, or routines.

You can compile a specified set of object files with `-xhwcprof`. However, `-xhwcprof` is most useful when applied to all object files in the application. This will provide coverage to identify and correlate all memory references distributed in the application's object files.

If you are compiling and linking in separate steps, use `-xhwcprof` at link time as well. Future extensions to `-xhwcprof` may require its use at link time. For a complete list of all compiler options that must be specified at both compile time and at link time, see [TABLE 2-2](#).

An instance of `-xhwcprof=enable` or `-xhwcprof=disable` overrides all previous instances of `-xhwcprof` in the same command line.

`-xhwcprof` is disabled by default. Specifying `-xhwcprof` without any arguments is the equivalent to `-xhwcprof=enable`.

`-xhwcprof` requires that optimization be turned on and that the debug data format be set to DWARF (`-xdebugformat=dwarf`).

The combination of `-xhwcprof` and `-g` increases compiler temporary file storage requirements by more than the sum of the increases due to `-xhwcprof` and `-g` specified alone.

The following command compiles `example.c` and specifies support for hardware counter profiling and symbolic analysis of data types and structure members using DWARF symbols:

```
example% cc -c -O -xhwcprof -g -xdebugformat=dwarf example.c
```

For more information on hardware counter-based profiling, see the *Program Performance Analysis Tools* manual.

B.2.89 `-xinline=list`

The format of the *list* for `-xinline` is as follows:

```
[{%auto,func_name,no%func_name} [, {%auto,func_name,no%func_name}] ...]
```

`-xinline` tries to inline only those functions specified in the optional list. The list is either empty, or comprised of a comma-separated list of `func_name`, `no%func_name`, or `%auto`, where *func_name* is a function name. `-xinline` only has an effect at `-xO3` or higher.

TABLE B-25 The `-xinline` Flags

Flag	Meaning
<code>%auto</code>	Specifies that the compiler is to attempt to automatically inline all functions in the source file. <code>%auto</code> only takes effect at <code>-xO4</code> or higher optimization levels. <code>%auto</code> is silently ignored at <code>-xO3</code> or lower optimization levels.
<code>func_name</code>	Specifies that the compiler is to attempt to inline the named function.
<code>no%func_name</code>	Specifies that the compiler is not to inline the named function.
no value	Specifies that the compiler is not to attempt to inline any functions in the source files.

The list of values accumulates from left to right. So for a specification of `-xinline=%auto,no%foo` the compiler attempts to inline all functions except `foo`. For a specification of `-xinline=%bar,%myfunc,no%bar` the compiler only tries to inline `myfunc`.

When you compile with optimization set at `-xO4` or above, the compiler normally tries to inline all references to functions defined in the source file. You can restrict the set of functions the compiler attempts to inline by specifying the `-xinline` option. If you specify only `-xinline=`, that is you do not name any functions or `%auto`, this indicates that none of the routines in the source files are to be inlined. If you specify a list of `func_name` and `no%func_name` without specifying `%auto`, the compiler only attempts to inline those functions specified in the list. If `%auto` is specified in the list of values with the `-xinline` option at optimization level set at `-xO4` or above, the compiler attempts to inline all functions that are not explicitly excluded by `no%func_name`.

A function is not inlined if any of the following conditions apply. No warning is issued.

- Optimization is less than `-xO3`.
- The routine cannot be found.
- Inlining the routine does not look practicable to the optimizer.
- The source for the routine is not in the file being compiled (however, see `-xcrossfile`).

If you specify multiple `-xinline` options on the command line, they do not accumulate. The last `-xinline` on the command line specifies what functions the compiler attempts to inline.

See also `-xldscope`.

B.2.90 `-xipo[=a]`

(SPARC) Replace *a* with 0, 1, or 2. `-xipo` without any arguments is equivalent `-xipo=1`. `-xipo=0` is the default setting and turns off `-xipo`. With `-xipo=1`, the compiler performs inlining across all source files.

With `-xipo=2`, the compiler performs interprocedural aliasing analysis as well as optimizations of memory allocation and layout to improve cache performance.

The compiler performs partial-program optimizations by invoking an interprocedural analysis component. Unlike `-xcrossfile`, `-xipo` performs optimizations across all object files in the link step, and is not limited to just the source files of the compile command. However, just like `-xcrossfile`, whole-program optimizations performed with `-xipo` do not include assembly (`.s`) source files.

You must specify `-xipo` both at compile time and at link time. For a complete list of all compiler options that must be specified at both compile time and at link time, see [TABLE 2-2](#).

The `-xipo` option generates significantly larger object files due to the additional information needed to perform optimizations across files. However, this additional information does not become part of the final executable binary file. Any increase in the size of the executable program is due to the additional optimizations performed. The object files created in the compilation steps have additional analysis information compiled within them to permit crossfile optimizations to take place at the link step.

`-xipo` is particularly useful when compiling and linking large multi-file applications. Object files compiled with this flag have analysis information compiled within them that enables interprocedural analysis across source and pre-compiled program files.

However, analysis and optimization is limited to the object files compiled with `-xipo`, and does not extend to object files or libraries.

`-xipo` is multiphased, so you need to specify `-xipo` for each step if you compile and link in separate steps.

Other important information about `-xipo`:

- It requires an optimization level of at least `-xO4`.
- It conflicts with `-xcrossfile`. If you use these together, the result is a compilation error.
- Objects that are compiled without `-xipo` can be linked freely with objects that are compiled with `-xipo`.

B.2.90.1 Examples

In this example, compilation and linking occur in a single step:

```
cc -xipo -xO4 -o prog part1.c part2.c part3.c
```

The optimizer performs crossfile inlining across all three source files. This is done in the final link step, so the compilation of the source files need not all take place in a single compilation and could take place over a number of separate compilations, each specifying `-xipo`.

In this example, compilation and linking occur in separate steps:

```
cc -xipo -xO4 -c part1.c part2.c
cc -xipo -xO4 -c part3.c
cc -xipo -xO4 -o prog part1.o part2.o part3.o
```

A restriction is that libraries, even if compiled with `-xipo`, do not participate in crossfile interprocedural analysis, as this example shows:

```
cc -xipo -xO4 one.c two.c three.c
ar -r mylib.a one.o two.o three.o
...
cc -xipo -xO4 -o myprog main.c four.c mylib.a
```

Here interprocedural optimizations are performed between `one.c`, `two.c` and `three.c`, and between `main.c` and `four.c`, but not between `main.c` or `four.c` and the routines on `mylib.a`. (The first compilation may generate warnings about undefined symbols, but the interprocedural optimizations are performed because it is a compile and link step.)

B.2.90.2 When Not To Use `-xipo=2` Interprocedural Analysis

The compiler tries to perform whole-program analysis and optimizations as it works with the set of object files in the link step. The compiler makes the following two assumptions for any function (or subroutine) `foo()` defined in this set of object files:

1. `foo()` is not called explicitly by another routine that is defined outside this set of object files at runtime.
2. The calls to `foo()` from any routine in the set of object files are not interposed upon by a different version of `foo()` defined outside this set of object files.

Do not compile with `-xipo=2`, if assumption 1 is not true for the given application

Do not compile with either `-xipo=1` or `-xipo=2`, if assumption 2 is not true.

As an example, consider interposing on the function `malloc()` with your own version and compiling with `-xipo=2`. Consequently, all the functions in any library that reference `malloc()` that are linked with your code have to be compiled with `-xipo=2` also and their object files need to participate in the link step. Since this might not be possible for system libraries, do not compile your version of `malloc` with `-xipo=2`.

As another example, suppose that you build a shared library with two external calls, `foo()` and `bar()` inside two different source files. Furthermore, suppose that `bar()` calls `foo()`. If there is a possibility that `foo()` could be interposed at runtime, then do not compile the source file for `foo()` or for `bar()` with `-xipo=1` or `-xipo=2`. Otherwise, `foo()` could be inlined into `bar()`, which could cause incorrect results.

See also: `-xjobs`

B.2.91 `-xipo_archive=[a]`

The `-xipo_archive` option enables the compiler to optimize object files that are passed to the linker with object files that were compiled with `-xipo` and that reside in the archive library (.a) before producing an executable. Any object files contained in the library that were optimized during the compilation are replaced with their optimized version.

a is one of the following:

TABLE B-26 The `-xipo_archive` Flags

Flag	Meaning
writeback	The compiler optimizes object files passed to the linker with object files compiled with <code>-xipo</code> that reside in the archive library (.a) before producing an executable. Any object files contained in the library that were optimized during the compilation are replaced with an optimized version.
readonly	The compiler optimizes object files passed to the linker with object files compiled with <code>-xipo</code> that reside in the archive library (.a) before producing an executable.
none	There is no processing of archive files.

If you do not specify a setting for `-xipo_archive`, the compiler sets it to `-xipo_archive=none`.

B.2.92 `-xjobs=n`

(SPARC) Specify the `-xjobs` option to set how many processes the compiler creates to complete its work. This option can reduce the build time on a multi-cpu machine. Currently, `-xjobs` works only with the `-xipo` option. When you specify `-xjobs=n`, the interprocedural optimizer uses *n* as the maximum number of code generator instances it can invoke to compile different files.

Generally, a safe value for *n* is 1.5 multiplied by the number of available processors. Using a value that is many times the number of available processors can degrade performance because of context switching overheads among spawned jobs. Also, using a very high number can exhaust the limits of system resources such as swap space.

You must always specify `-xjobs` with a value. Otherwise an error diagnostic is issued and compilation aborts.

Multiple instances of `-xjobs` on the command line override each other until the right-most instance is reached.

The following example compiles more quickly on a system with two processors than the same command without the `-xjobs` option.

```
example% cc -xipo -x04 -xjobs=3 t1.c t2.c t3.c
```

B.2.93 `-xldscope={v}`

Specify the `-xldscope` option to change the default linker scoping for the definition of extern symbols. Changing the default can result in faster and safer shared libraries because the implementation is better hidden.

v must be one of the following:

TABLE B-27 The `-xldscope` Flags

Flag	Meaning
<code>global</code>	Global linker scoping is the least restrictive linker scoping. All references to the symbol bind to the definition in the first dynamic module that defines the symbol. This linker scoping is the current linker scoping for extern symbols.
<code>symbolic</code>	Symbolic linker scoping and is more restrictive than global linker scoping. All references to the symbol from within the dynamic module being linked bind to the symbol defined within the module. Outside of the module, the symbol appears as though it were global. This linker scoping corresponds to the linker option <code>-Bsymbolic</code> . See <code>ld(1)</code> for more information on the linker.
<code>hidden</code>	Hidden linker scoping is more restrictive than symbolic and global linker scoping. All references within a dynamic module bind to a definition within that module. The symbol will not be visible outside of the module.

If you do not specify `-xldscope`, the compiler assumes `-xldscope=global`. The compiler issues an error if you specify `-xldscope` without an argument. Multiple instances of this option on the command line override each other until the rightmost instance is reached.

If you intend to allow a client to override a function in a library, you must be sure that the function is not generated inline during the library build. The compiler inlines a function if you specify the function name with `-xinline`, if you compile at `-xO4` or higher in which case inlining can happen automatically, if you use the inline specifier, if you use the inline pragma, or if you are using cross-file optimization.

For example, suppose library ABC has a default allocator function that can be used by library clients, and is also used internally in the library:

```
void* ABC_allocator(size_t size) { return malloc(size); }
```

If you build the library at `-xO4` or higher, the compiler inlines calls to `ABC_allocator` that occur in library components. If a library client wants to replace `ABC_allocator` with a customized version, the replacement will not occur in library components that called `ABC_allocator`. The final program will include different versions of the function.

Library functions declared with the `__hidden` or `__symbolic` specifiers can be generated inline when building the library. They are not supposed to be overridden by clients. See [Section 2.2, “Linker Scoping Specifiers” on page 2-3](#).

Library functions declared with the `__global` specifier, should not be declared inline, and should be protected from inlining by use of the `-xinline` compiler option.

See also `-xinline`, `-x0`, `-xcrossfile`, `#pragma inline`

B.2.94 `-xlibmieee`

Forces IEEE 754 style return values for math routines in exceptional cases. In such cases, no exception message is printed, and you should not rely on `errno`.

B.2.95 `-xlibmil`

Inlines some library routines for faster execution. This option selects the appropriate assembly language inline templates for the floating-point option and platform for your system.

`-xlibmil` inlines a function regardless of any specification of the function as part of the `-xinline` flag.

However, these substitutions can cause the setting of `errno` to become unreliable. If your program depends on the value of `errno`, avoid this option. See also [Section 2.10, “The Value of `errno`” on page 2-24](#).

B.2.96 `-xlibmopt`

Enables the compiler to use a library of optimized math routines. You must use default rounding mode by specifying `-fround=nearest` when you use this option.

The math routine library is optimized for performance and usually generates faster code. The results may be slightly different from those produced by the normal math library. If so, they usually differ in the last bit.

However, these substitutions can cause the setting of `errno` to become unreliable. If your program depends on the value of `errno`, avoid this option. See also [Section 2.10, “The Value of `errno`” on page 2-24](#).

The order on the command line for this library option is not significant.

This option is set by the `-fast` option.

See also: `-fast -xnolibmopt`

B.2.97 `-xlic_lib=sunperf`

Links in the Sun supplied performance libraries.

B.2.98 `-xlicinfo`

This option is silently ignored by the compiler.

B.2.99 `-xlinkopt[=level]`

(SPARC) Instructs the compiler to perform link-time optimizations on relocatable object files. These optimizations are performed at link time by analyzing the object binary code. The object files are not rewritten but the resulting executable code may differ from the original object codes.

You must use `-xlinkopt` on at least some of the compilation commands for `-xlinkopt` to be useful at link time. The optimizer can still perform some limited optimizations on object binaries that are not compiled with `-xlinkopt`.

`-xlinkopt` optimizes code coming from static libraries that appear on the compiler command line, but it skips and does not optimize code coming from shared (dynamic) libraries that appear on the command line. You can also use `-xlinkopt` when you build shared libraries (compiling with `-G`).

level sets the level of optimizations performed, and must be 0, 1, or 2. The optimization levels are:

TABLE B-28 The `-xlinkopt` Flags

Flag	Behavior
0	The post-optimizer is disabled. (This is the default.)
1	Perform optimizations based on control flow analysis, including instruction cache coloring and branch optimizations, at link time.
2	Perform additional data flow analysis, including dead-code elimination and address computation simplification, at link time.

If you compile in separate steps, `-xlinkopt` must appear on both compile and link steps:

```
example% cc -c -xlinkopt a.c b.c
example% cc -o myprog -xlinkopt=2 a.o
```

For a complete list of all compiler options that must be specified at both compile time and at link time, see [TABLE 2-2](#).

Note that the level parameter is only used when the compiler is linking. In the example above, the post- optimization level used is 2 even though the object binaries were compiled with an implied level of 1.

Specifying `-xlinkopt` without a level parameter implies `-xlinkopt=1`.

This option is most effective when you use it to compile the whole program, and with profile feedback. Profiling reveals the most and least used parts of the code and building directs the optimizer to focus its effort accordingly. This is particularly important with large applications where optimal placement of code performed at link time can reduce instruction cache misses. Typically, this compiles as follows:

```
example% cc -o progt -xO5 -xprofile=collect:prog file.c
example% progt
example% cc -o prog -xO5 -xprofile=use:prog -xlinkopt file.c
```

For details on using profile feedback, see [Section B.2.125, “-xprofile=p” on page B-83](#).

Do not use the `-zcompreloc` linker option when you compile with `-xlinkopt`.

Note that compiling with this option increases link time slightly. Object file sizes also increase, but the size of the executable remains the same. Compiling with `-xlinkopt` and `-g` increases the size of the executable by including debugging information.

B.2.100 `-xloopinfo`

(SPARC) Shows which loops are parallelized and which are not. Gives a short reason for not parallelizing a loop. The `-xloopinfo` option is valid only if `-xautopar`, or `-xparallel`, or `-xexplicitpar` is specified; otherwise, the compiler issues a warning.

To achieve faster execution, this option requires a multiprocessor system. On a single-processor system, the generated code usually runs slower.

B.2.101 `-xM`

Runs only the preprocessor on the named C programs, requesting that it generate makefile dependencies and send the result to the standard output (see `make(1)` for details about make files and dependencies).

For example:

```
#include <unistd.h>
void main(void)
{ }
```

generates this output:

```
e.o: e.c
e.o: /usr/include/unistd.h
e.o: /usr/include/sys/types.h
e.o: /usr/include/sys/machtypes.h
e.o: /usr/include/sys/select.h
e.o: /usr/include/sys/time.h
e.o: /usr/include/sys/types.h
e.o: /usr/include/sys/time.h
e.o: /usr/include/sys/unistd.h
```

B.2.102 -xM1

Collects dependencies like -xM, but excludes /usr/include files. For example:

```
more hello.c
#include<stdio.h>
main()
{
    (void)printf("hello\n");
}
cc -xM hello.c
hello.o: hello.c
hello.o: /usr/include/stdio.h
```

Compiling with -xM1 does not report header file dependencies:

```
cc -xM1 hello.c
hello.o: hello.c
```

-xM1 is not available under -Xs mode.

B.2.103 `-xMerge`

Merges data segments into text segments. Data initialized in the object file produced by this compilation is read-only and (unless linked with `ld -N`) is shared between processes.

B.2.104 `-xmaxopt[=v]`

This command limits the level of `pragma opt` to the level specified. *v* is one of `off`, `1`, `2`, `3`, `4`, `5`. The default value is `-xmaxopt=off` which causes `pragma opt` to be ignored. If you specify `-xmaxopt` without supplying an argument, that is the equivalent of specifying `-xmaxopt=5`.

If you specify both `-xO` and `-xmaxopt`, the optimization level set with `-xO` must not exceed the `-xmaxopt` value.

B.2.105 `-xmemalign=ab`

(SPARC) Specify maximum assumed memory alignment and behavior of misaligned data accesses. There must be a value for both *a* (alignment) and *b* (behavior). *a* specifies the maximum assumed memory alignment and *b* specifies the behavior for misaligned memory accesses. The following table lists the alignment and behavior values for `-xmemalign`

TABLE B-29 The `-xmemalign` Alignment and Behavior Flags

<i>a</i>		<i>b</i>	
1	Assume at most 1 byte alignment.	<i>i</i>	Interpret access and continue execution.
2	Assume at most 2 byte alignment.	<i>s</i>	Raise signal SIGBUS.
4	Assume at most 4 byte alignment.	<i>f</i>	For variants of <code>-xarch=v9</code> only:
8	Assume at most 8 byte alignment.		Raise signal SIGBUS for alignments less or equal to 4, otherwise interpret access and continue execution. For all other <code>-xarch</code> values, the <i>f</i> flag is equivalent to <i>i</i> .
16	Assume at most 16 byte alignment		

You must specify `-xmemalign` whenever you want to link to an object file that was compiled with the value of *b* set to either *i* or *f*. For a complete list of all compiler options that must be specified at both compile time and at link time, see [TABLE 2-2](#).

For memory accesses where the alignment is determinable at compile time, the compiler generates the appropriate load/store instruction sequence for that alignment of data.

For memory accesses where the alignment cannot be determined at compile time, the compiler must assume an alignment to generate the needed load/store sequence.

The `-xmemalign` option allows you to specify the maximum memory alignment of data to be assumed by the compiler in these indeterminable situations. It also specifies the error behavior to be followed at run time when a misaligned memory access does take place.

The following default values only apply when no `-xmemalign` option is present:

- `-xmemalign=8i` for all v8 architectures.
- `-xmemalign=8s` for all v9 architectures.

Here is the default when `-xmemalign` option is present but no value is given:

- `-xmemalign=1i` for all `-xarch` values.

The following table shows how you can use `-xmemalign` to handle different alignment situations.

TABLE B-30 Examples of `-xmemalign`

Command	Situation
<code>-xmemalign=1s</code>	There are many misaligned accesses so trap handling is too slow.
<code>-xmemalign=8i</code>	There are occasional, intentional, misaligned accesses in code that is otherwise correct.
<code>-xmemalign=8s</code>	There should be no misaligned accesses in the program.
<code>-xmemalign=2s</code>	You want to check for possible odd-byte accesses.
<code>-xmemalign=2i</code>	You want to check for possible odd-byte access and you want the program to work.

B.2.106 `-xmodel=[a]`

The `-xmodel` option enables the compiler to modify the form of 64-bit objects for the Solaris x86 platforms and should only be specified for the compilation of such objects.

This option is valid only when `-xarch=generic64`, `-xarch=amd64`, or `-xarch=amd64a` are also specified.

a must be one of the following:

TABLE B-31 The `-xmodel` Flags

Value	Meaning
small	This option generates code for the small model in which the virtual address of code executed is known at link time and all symbols are known to be located in the virtual addresses in the range from 0 to $2^{31} - 2^{24} - 1$.
kernel	Generates code for the kernel model in which all symbols are defined to be in the range from $2^{64} - 2^{31}$ to $2^{64} - 2^{24}$.
medium	Generates code for the medium model in which no assumptions are made about the range of symbolic references to data sections. Size and address of the text section have the same limits as the small code model.

This option is not cumulative so the compiler sets the model value according to the rightmost instance of `-xmodel` on the command-line.

If you do not specify `-xmodel`, the compiler assumes `-xmodel=small`. Specifying `-xmodel` without an argument is an error.

It is not necessary to compile all translation units with this option. You can compile select files as long as you ensure the object you are accessing is within reach.

B.2.107 `-xnativeconnect[=a[, a] . . .]`

Note – This is an End of Feature notice. This option may be removed in a future release of Sun Studio.

Use the `-xnativeconnect` option when you want to include interface information inside object files and subsequent shared libraries so that the shared library can interface with code written in the Java™ programming language (Java code). You must also include `-xnativeconnect` when you build the shared library with the `cc -G` command.

When you compile with `-xnativeconnect`, you are providing the maximum, external, visibility of the native code interfaces. The Native Connector Tool (NCT) enables the automatic generation of Java code and the Java™ Native Interface (JNI) code. Using `-xnativeconnect` with NCT can make functions in C shared libraries callable from Java code. For more information on how to use the NCT, see the online help.

a can be one of the following:

TABLE B-32 The `-xnativeconnect` Flags

Flag	Meaning
<code>%all</code>	Generates all of the different data described under the individual options of <code>-xnativeconnect</code> .
<code>%none</code>	Generates none of the different data described under the individual options of <code>-xnativeconnect</code> .
<code>[no%]inlines</code>	Forces the generation of out-of-line instances of referenced inline functions. This provides the native connector with an externally visible way to call the inline functions. The normal inlining of these functions at call sites is unaffected
<code>[no%]interfaces</code>	Forces the generation of Binary Interface Descriptors (BIDS)

If you do not specify `-xnativeconnect`, the compiler sets the option to `-xnativeconnect=%none`. If you specify only `-xnativeconnect`, the compiler sets the option to `-xnativeconnect=interfaces`.

`-xnativeconnect=interfaces` forces the generation of Binary Interface Descriptors (BIDS).

B.2.108 `-xnolib`

Does not link any libraries by default; that is, no `-l` options are passed to `ld(1)`. Normally, the `cc` driver passes `-lc` to `ld`.

When you use `-xnolib`, you have to pass all the `-l` options yourself.

B.2.109 `-xnolibmil`

Does not inline math library routines. Use it after the `-fast` option. For example:

```
% cc -fast -xnolibmil....
```

B.2.110 `-xnoibmopt`

Prevents the use of an optimized math library by the compiler by turning off any previously specified `-xlibmopt` option. Use this option after `-fast` which enables use of the optimized math library by setting `-xlibmopt`:

```
% cc -fast -xnoibmopt ...
```

B.2.111 `-xO[1 | 2 | 3 | 4 | 5]`

Optimizes the object code; note the uppercase letter O followed by the digit 1, 2, 3, 4, or 5. Generally, the higher the level of optimization, the better the run-time performance. However, higher optimization levels can result in longer compilation time and larger executable files.

In a few cases, `-xO2` might perform better than the others, and `-xO3` might outperform `-xO4`. Try compiling with each level to see if you have one of these rare cases.

If the optimizer runs out of memory, it tries to recover by retrying the current procedure at a lower level of optimization and resumes subsequent procedures at the original level specified in the command-line option.

The default is no optimization. However, this is only possible if you do not specify an optimization level. If you specify an optimization level, there is no option for turning optimization off.

If you are trying to avoid setting an optimization level, be sure not to specify any option that implies an optimization level. For example, `-fast` is a macro option that sets optimization at `-xO5`. All other options that imply an optimization level give a warning message that optimization has been set. The only way to compile without any optimization is to delete all options from the command line or make file that specify an optimization level.

If you use `-g` and the optimization level is `-xO3` or lower, the compiler provides best-effort symbolic information with almost full optimization. Tail-call optimization and back-end inlining are disabled.

If you use `-g` and the optimization level is `-xO4` or higher, the compiler provides best-effort symbolic information with full optimization.

Debugging with `-g` does not suppress `-xOn`, but `-xOn` limits `-g` in certain ways. For example, the optimization options reduce the utility of debugging so that you cannot display variables from `dbx`, but you can still use the `dbx` where command to get a symbolic traceback. For more information, see “Debugging Optimized Code” in Chapter 1 of *Debugging a Program With dbx*.

If you specify both `-xO` and `-xmaxopt`, the optimization level set with `-xO` must not exceed the `-xmaxopt` value.

If you optimize at `-xO3` or `-xO4` with very large procedures (thousands of lines of code in the same procedure), the optimizer may require a large amount of virtual memory. In such cases, machine performance may degrade.

B.2.111.1 Explanation of SPARC Optimizations

The following table describes how they operate on the SPARC platform.

TABLE B-33 The `-xO` Flags on SPARC Platforms

Flag	Meaning
<code>-xO1</code>	Does basic local optimization (peephole).
<code>-xO2</code>	Does basic local and global optimization. This is induction variable elimination, local and global common subexpression elimination, algebraic simplification, copy propagation, constant propagation, loop-invariant optimization, register allocation, basic block merging, tail recursion elimination, dead code elimination, tail call elimination, and complex expression expansion. The <code>-xO2</code> level does not assign global, external, or indirect references or definitions to registers. It treats these references and definitions as if they were declared <code>volatile</code> . In general, the <code>-xO2</code> level results in minimum code size.
<code>-xO3</code>	Performs like <code>-xO2</code> , but also optimizes references or definitions for external variables. Loop unrolling and software pipelining are also performed. This level does not trace the effects of pointer assignments. When compiling either device drivers, or programs that modify external variables from within signal handlers, you may need to use the <code>volatile</code> type qualifier to protect the object from optimization. In general, the <code>-xO3</code> level results in increased code size.
<code>-xO4</code>	Performs like <code>-xO3</code> , but also automatically inlines functions contained in the same file; this usually improves execution speed. If you want to control which functions are inlined, see Section B.2.89, “-xinline=list” on page B-52 . This level traces the effects of pointer assignments, and usually results in increased code size.
<code>-xO5</code>	Attempts to generate the highest level of optimization. Uses optimization algorithms that take more compilation time or that do not have as high a certainty of improving execution time. Optimization at this level is more likely to improve performance if it is done with profile feedback. See Section B.2.125, “-xprofile=p” on page B-83 .

B.2.111.2 Explanation of x86 Optimizations

The following table describes how the optimization levels work on the x86 platform.

TABLE B-34 The `-xO` Flags on x86 Platforms

Flag	Meaning
<code>-xO1</code>	Preloads arguments from memory, cross-jumping (tail-merging), as well as the single pass of the default optimization.
<code>-xO2</code>	Schedules both high- and low-level instructions and performs improved spill analysis, loop memory-reference elimination, register lifetime analysis, enhanced register allocation, and elimination of global common subexpressions.
<code>-xO3</code>	Performs loop strength reduction, induction variable elimination, as well as the optimization done by level 2.
<code>-xO4</code>	Performs automatic inlining of functions contained in the same file in addition to performing <code>-xO3</code> optimizations. This automatic inlining usually improves execution speed, but sometimes makes it worse. In general, this level results in increased code size.
<code>-xO5</code>	Generates the highest level of optimization. Uses optimization algorithms that take more compilation time or that do not have as high a certainty of improving execution time. Some of these include generating local calling convention entry points for exported functions, further optimizing spill code and adding analysis to improve instruction scheduling.

For more information on debugging, see the *Debugging a Program With dbx* manual. For more information on optimization, see the *Performance Analyzer* manual.

See also `-xldscope` and `-xmaxopt`.

B.2.112 `-xopenmp[=i]`

(SPARC) Use the `-xopenmp` option to enable explicit parallelization with OpenMP directives. The following table lists the values for *i*:

TABLE B-35 The `-xopenmp` Flags

Flag	Meaning
<code>parallel</code>	Enables recognition of OpenMP pragmas. The optimization level under <code>-xopenmp=parallel</code> is <code>-x03</code> . The compiler changes the optimization level to <code>-x03</code> if necessary and issues a warning.
<code>noopt</code>	Enables recognition of OpenMP pragmas. The compiler does not raise the optimization level if it is lower than <code>-O3</code> . If you explicitly set the optimization lower than <code>-O3</code> , as in <code>cc -O2 -xopenmp=noopt</code> , the compiler issues an error. If you do not specify an optimization level with <code>-xopenmp=noopt</code> , the OpenMP pragmas are recognized, the program is parallelized accordingly, but no optimization is done.
<code>stubs</code>	Disables recognition of OpenMP pragmas, links to stub library routines and does not change the optimization level. Use this option if your application makes explicit calls to the OpenMP runtime library routines and you want to compile it to execute serially. The <code>-xopenmp=stubs</code> command also defines the <code>_OPENMP</code> preprocessor token.
<code>none</code>	Does not enable recognition of OpenMP pragmas, makes no change to the optimization level of your program, and does not predefine any preprocessor tokens.

If you specify `-xopenmp`, but do not include a value, the compiler assumes `-xopenmp=parallel`. If you do not specify `-xopenmp`, the compiler assumes `-xopenmp=none`.

If you are debugging an OpenMP program with `dbx`, compile with `-g` and `-xopenmp=noopt` so you can breakpoint within parallel regions and display the contents of variables.

Note – Do not specify `-xopenmp`, with either `-xexplicitpar`, or `-xparallel`.

The default for `-xopenmp` might change in future releases. You can avoid warning messages by explicitly specifying an appropriate optimization.

If you use `-xopenmp` building any `.so`, you must use `-xopenmp` when linking the executable, and the compiler of the executable must not be any older than the compiler that built the `.so` with `-xopenmp`. This is especially important when you compile libraries that contain OpenMP directives. For a complete list of all compiler options that must be specified at both compile time and at link time, see [TABLE 2-2](#).

For more information on how to compile a program that is OpenMP compliant, see [Section 3.2, “Parallelizing for OpenMP” on page 3-2](#).

For information on OpenMP, see the *OpenMP API User’s Guide*.

For a complete summary of the OpenMP Fortran 95, C, and C++ application program interface (API) for building multiprocessing applications, see the *OpenMP API User’s Guide*.

B.2.113 `-xP`

The compiler performs only syntax and semantic checking on the source file in order to print prototypes for all K&R C functions. This option does not produce any object or executable code. For example, specifying `-xP` with the following source file,

```
f()
{
}

main(argc, argv)
int argc;
char *argv[];
{
}
```

produces this output:

```
int f(void);
int main(int, char **);
```

B.2.114 `-xpagesize=n`

Sets the preferred page size for the stack and the heap.

The *n* value must be one of the following: 8K, 64K, 512K, 4M, 32M, 256M, 2G, 16G, or default. If you do not specify a valid page size, the request is silently ignored at run-time.

You must specify a valid page size for the target platform.

Use the `getpagesize(3C)` command on the Solaris operating system to determine the number of bytes in a page. The Solaris operating system offers no guarantee that the page size request will be honored. You can use `pmap(1)` or `meminfo(2)` to determine page size of the target platform.

You can use `pmap(1)` or `meminfo(2)` to determine page size of the target platform.

The `-xpagesize` option has no effect unless you use it at compile time and at link time. For a complete list of all compiler options that must be specified at both compile time and at link time, see [TABLE 2-2](#).

Note – This feature is not available on the Solaris 8 operating system. A program compiled with this option will not link on the Solaris 8 operating system.

If you specify `-xpagesize=default`, the Solaris operating system sets the page size.

Compiling with this option has the same effect as setting the `LD_PRELOAD` environment variable to `mpss.so.1` with the equivalent options, or running the Solaris command `ppgsz(1)` with the equivalent options before running the program. See the Solaris man pages for details.

This option is a macro for `-xpagesize_heap` and `-xpagesize_stack`. These two options accept the same arguments as `-xpagesize`: 8K, 64K, 512K, 4M, 32M, 256M, 2G, 16G, or default. You can set them both with the same value by specifying `-xpagesize` or you can specify them individually with different values.

B.2.115 `-xpagesize_heap=n`

Set the page size in memory for the heap.

The value for *n* must be one of the following: 8K, 64K, 512K, 4M, 32M, 256M, 2G, 16G, or default. If you do not specify a valid page size, the request is silently ignored at run-time.

Use the `getpagesize(3C)` command on the Solaris operating system to determine the number of bytes in a page. The Solaris operating system offers no guarantee that the page size request will be honored. You can use `pmap(1)` or `meminfo(2)` to determine page size of the target platform.

You can use `pmap(1)` or `meminfo(2)` to determine page size at the target platform.

If you specify `-xpagesize_heap=default`, the Solaris operating system sets the page size.

Compiling with this option has the same effect as setting the `LD_PRELOAD` environment variable to `mpss.so.1` with the equivalent options, or running the Solaris command `ppgsz(1)` with the equivalent options before running the program. See the Solaris man pages for details.

The `-xpagesize_heap` option has no effect unless you use it at compile time and at link time. For a complete list of all compiler options that must be specified at both compile time and at link time, see [TABLE 2-2](#).

Note – This feature is not available on the Solaris 8 operating system. A program compiled with this option will not link on the Solaris 8 operating system.

B.2.116 `-xpagesize_stack=n`

Set the page size in memory for the stack.

The value for *n* must be one of the following: 8K, 64K, 512K, 4M, 32M, 256M, 2G, 16G, or `default`. If you do not specify a valid page size, the request is silently ignored at run-time.

Use the `getpagesize(3C)` command on the Solaris operating system to determine the number of bytes in a page. The Solaris operating system offers no guarantee that the page size request will be honored. You can use `pmap(1)` or `meminfo(2)` to determine page size of the target platform.

If you specify `-xpagesize_stack=default`, the Solaris operating system sets the page size.

Compiling with this option has the same effect as setting the `LD_PRELOAD` environment variable to `mpss.so.1` with the equivalent options, or running the Solaris command `ppgsz(1)` with the equivalent options before running the program. See the Solaris man pages for details.

The `-xpagesize_stack` option has no effect unless you use it at compile time and at link time. For a complete list of all compiler options that must be specified at both compile time and at link time, see [TABLE 2-2](#).

Note – This feature is not available on the Solaris 8 operating system. A program compiled with this option will not link on the Solaris 8 operating system.

B.2.117 `-xparallel`

Note – `-xparallel` does not accept OpenMP parallelization directives. However, the Sun-specific MP pragmas have been deprecated and are no longer supported. However, the compiler supports the APIs specified by the OpenMP 2.5 standard instead. See the *OpenMP API User's Guide* for migration information to the directives of the standard.

(SPARC) Parallelizes loops both automatically by the compiler and explicitly specified by the programmer. The `-xparallel` option is a macro, and is equivalent to specifying all three of `-xautopar`, `-xdepend`, and `-xexplicitpar`. With explicit parallelization of loops, there is a risk of producing incorrect results. If optimization is not at `-xO3` or higher, optimization is raised to `-xO3` and a warning is issued.

Avoid `-xparallel` if you do your own thread management. Do not use `-xparallel` if you are issuing `-xopenmp`. `-xparallel` sets `-xexplicitpar` which should not be used if you specify `-xopenmp`.

To get faster code, this option requires a multiprocessor system. On a single-processor system, the generated code usually runs slower.

If you compile and link in one step, `-xparallel` links with the microtasking library and the threads-safe C runtime library. If you compile and link in separate steps, and you compile with `-xparallel`, then link with `-xparallel`. For a complete list of all compiler options that must be specified at both compile time and at link time, see [TABLE 2-2](#).

B.2.118 `-xpch=v`

This compiler option activates the precompiled-header feature. *v* can be `auto`, `autofirst`, `collect:pch_filename`, or `use:pch_filename`. You can take advantage of this feature through the `-xpch` (detailed in [Section B.2.118](#), “`-xpch=v`” on [page B-74](#)) and `-xpchstop` (detailed in [Section B.2.119](#), “`-xpchstop=[file|<include>]`” on [page B-80](#)) options in combination with the `#pragma hdrstop` directive (detailed under [Section 2.8.8](#), “`hdrstop`” on [page 2-13](#)).

Use the `-xpch` option to create a precompiled-header file and improve your compilation time. The precompiled-header file is designed to reduce compile time for applications whose source files share a common set of include files containing a large amount of source code. A precompiled header works by collecting information about a sequence of header files from one source file, and then using that information when recompiling that source file, and when compiling other source files that have the same sequence of headers. The information that the compiler collects is stored in a precompiled-header file.

See Also:

- Section B.2.119, “`-xpchstop=[file|<include>]`” on page B-80.
- Section 2.8.8, “`hdrstop`” on page 2-13.

B.2.118.1 Creating a Precompiled-Header File Automatically

You can let the compiler generate the precompiled- header file for you automatically. Choose between one of the following two ways to do this. One way is for the compiler to create the precompiled-header file from the first include file it finds in the source file. The other way is for the compiler to select from the set of include files found in the source file starting with the first include file and extending through a well- defined point that determines which include file is the last one. Use one of the following two flags to determine which method the compiler uses to automatically generate a precompiled header:

TABLE B-36 The `-xpch` Flags

Flag	Meaning
<code>-xpch=auto</code>	The contents of the precompiled-header file is based on the longest viable prefix (see the following section for an explanation of how a viable prefix is identified) that the compiler finds in the source file. This flag produces a precompiled header file that consists of the largest possible number of header files.
<code>-xpch=autofirst</code>	This flag produces a precompiled-header file that contains only the first header found in the source file.

B.2.118.2 Creating a Precompiled-Header File Manually

If you decide to create your precompiled-header file manually, you must start by first using `-xpch`, and specifying the `collect` mode. The compilation command that specifies `-xpch=collect` must only specify one source file. In the following example, the `-xpch` option creates a precompiled-header file called `myheader.cpch` based on the source file `a.c`:

```
cc -xpch=collect:myheader a.c
```

A valid precompiled-header filename always has the suffix `.cpch`. When you specify *pch_filename*, you can add the suffix or let the compiler add it for you. For example, if you specify `cc -xpch=collect:foo a.c`, the precompiled-header file is called `foo.cpch`.

B.2.118.3 How the Compiler Handles an Existing Precompiled-Header File

If the compiler cannot use the precompiled-header file, under `-xpch=auto` and `-xpch=autofirst`, it generates a new precompiled-header file. If the compiler cannot use the precompiled-header file under `-xpch=use`, a warning is issued and the compilation is done using the real headers.

B.2.118.4 Directing the Compiler to Use a Specific Precompiled-Header File

You can also direct the compiler to use a specific precompiled header. Specify `-xpch=use:pch_filename` to do this. You can specify any number of source files with the same sequence of include files as the source file that was used to create the precompiled-header file. For example, your command in `use` mode could look like this: `cc -xpch=use:foo.cpch foo.c bar.c foobar.c`.

You should only use an existing precompiled-header file if the following are true. If any of the following is not true, you should recreate the precompiled-header file:

- The compiler that you are using to access the precompiled-header file is the same as the compiler that created the precompiled-header file. A precompiled-header file created by one version of the compiler may not be usable by another version of the compiler.
- Except for the `-xpch` option, the compiler options you specify with `-xpch=use` must match the options that were specified when the precompiled-header file was created.
- The set of included headers you specify with `-xpch=use` is identical to the set of headers that were specified when the precompile header was created.
- The contents of the included headers that you specify with `-xpch=use` is identical to the contents of the included headers that were specified when the precompiled header was created.
- The current directory (that is, the directory in which the compilation is occurring and attempting to use a given precompiled-header file) is the same as the directory in which the precompiled-header file was created.
- The initial sequence of pre-processing directives, including `#include` directives, in the file you specified with `-xpch=collect` are the same as the sequence of pre-processing directives in the files you specify with `-xpch=use`.

B.2.118.5 The Viable Prefix

In order to share a precompiled-header file across multiple source files, those source files must share a common set of include files as their initial sequence of tokens. A token is a keyword, name or punctuation mark. Comments and code that is excluded by `#if` directives are not recognized by the compiler as tokens. This initial sequence of tokens is known as the viable prefix. In other words, the viable prefix is the top portion of the source file that is common to all source files. The compiler uses this viable prefix as the basis for creating a precompiled-header file and thereby determining which header files from the source are pre-compiled.

The viable prefix that the compiler finds during the current compilation must match the viable prefix that it used to create the precompiled-header file. In other words, viable prefix must be interpreted consistently across all the source files that use the same precompiled-header file.

The viable prefix of a source file can only be comprised of comments and any of the following pre-processor directives:

```
#include
#if/ifdef/ifndef/else/elif/endif
#define/undef
#ident (if identical, passed through as is)
#pragma (if identical)
```

Any of these may reference macros. The `#else`, `#elif`, and `#endif` directives must match within the viable prefix. Comments are ignored.

The compiler determines the end point of the viable prefix automatically when you specify `-xpch=auto` or `-xpch=autofirst` and is defined as follows. For `-xpch=collect` or `-xpch=use`, the viable prefix ends with a `#pragma hdrstop`.

- The first declaration/definition statement
- The first `#line` directive
- A `#pragma hdrstop` directive
- After the named include file if you specify `-xpch=auto` and `-xpchstop`
- The first include file if you specify `-xpch=autofirst`

Note – An end point within a conditional statement generates a warning and disables the automatic creation of a precompiled-header file. Also, if you specify both the `#pragma hdrstop` and the `-xpchstop` option, then the compiler uses the earlier of the two stop points to terminate the viable prefix.

Within the viable prefix of each file that shares a precompiled-header file, each corresponding `#define` and `#undef` directive must reference the same symbol (in the case of `#define`, each one must reference the same value). Their order of

appearance within each viable prefix must be the same as well. Each corresponding pragma must also be the same and appear in the same order across all the files sharing a precompiled header.

B.2.118.6 Screening a Header File for Problems

What makes a header file precompilable? A header file is precompilable when it is interpreted consistently across different source files. Specifically, when it contains only complete declarations. That is, a declaration in any one file must stand alone as a valid declaration. Incomplete type declarations, such as `struct S;`, are valid declarations. The complete type declaration can appear in some other file. Consider these example header files:

```
file a.h
struct S {
#include "x.h" /* not allowed */
};

file b.h
struct T; // ok, complete declaration
struct S {
    int i;
[end of file, continued in another file] /* not allowed*/
```

A header file that is incorporated into a precompiled-header file must not violate the following. The results of compiling a program that violates any of these constraints is undefined.

- The header file must not use `__DATE__` and `__TIME__`.
- The header file must not contain `#pragma hdrstop`.

B.2.118.7 The Precompiled-Header File Cache

When the compiler creates a precompiled-header file automatically, the compiler writes it to the `SunWS_cache` directory. This directory always resides in the location where the object file is created. Updates to the file are preformed under a lock so that it works properly under `dmake`.

If you need to force the compiler to rebuild automatically-generated precompiled-header files, you can clear the precompiled-header file cache-directory with the `CCadmin` tool. See the `CCadmin(1)` man page for more information.

B.2.118.8 Warnings

- Do not specify conflicting `-xpch` flags on the command line. For example, specifying both `-xpch=collect` and `-xpch=auto`, or specifying both `-xpch=autofirst` with `-xpchstop=<include>` generates an error.
- If you specify `-xpch=autofirst` or you specify `-xpch=auto` without `-xpchstop`, any declaration, definition, or `#line` directive that appears prior to the first include file, or appears prior to the include file that is specified with `-xpchstop` for `-xpch=auto`, generates a warning and disables the automatic generation of the precompiled-header file.
- A `#pragma hdrstop` before the first include file under `-xpch=autofirst` or `-xpch=auto` disables the automatic generation of the precompiled-header file.

B.2.118.9 Precompiled-Header File Dependencies and make Files

The compiler generates dependency information for precompiled-header files when you specify `-xpch=collect`. You need to create the appropriate rules in your make files to take advantage of these dependencies. Consider this sample make file:

```
%o : %.c shared.cpch
    $(CC) -xpch=use:shared -xpchstop=foo.h -c $<
default : a.out

foo.o + shared.cpch : foo.c
    $(CC) -xpch=collect:shared -xpchstop=foo.h foo.c -c

a.out : foo.o bar.o foobar.o
    $(CC) foo.o bar.o foobar.o

clean :
    rm -f *.o shared.cpch .make.state a.out
```

These make rules, along with the dependencies generated by the compiler, force a manually created precompiled- header file to be recreated if any source file you used with `-xpch=collect`, or any of the headers that are part of the precompiled-header file, have changed. This prevents the use of an out of date precompiled-header file.

You do not have to create any additional make rules in your makefiles for `-xpch=auto` or `-xpch=autofirst`.

B.2.119 `-xpchstop= [file | <include>]`

Use the `-xpchstop=file` option to specify the last include file of the viable prefix for the precompiled-header file. Using `-xpchstop` on the command line is equivalent to placing a `hdrstop` pragma after the first include-directive that references *file* in each of the source files that you specify with the `cc` command.

Use `-xpchstop=<include>` with `-xpch=auto` to create a precompiled-header file that is based on header files up through and including `<include>`. This flag overrides the default `-xpch=auto` behavior of using all header files that are contained in the entire viable prefix.

In the following example, the `-xpchstop` option specifies that the viable prefix for the precompiled-header file ends with the include of `projectheader.h`. Therefore, `privateheader.h` is not a part of the viable prefix.

```
example% cat a.c
#include <stdio.h>
#include <strings.h>
#include "projectheader.h"
#include "privateheader.h"
.
.
.
example% cc -xpch=collect:foo.cpch a.c -xpchstop=projectheader.h
-c
```

See also `-xpch`.

B.2.120 `-xpentium`

(x86) Generates code for the Pentium processor.

B.2.121 `-xpg`

Prepares the object code to collect data for profiling with `gprof(1)`. It invokes a runtime recording mechanism that produces a `gmon.out` file at normal termination.

Note – There is no advantage for `-xprofile` if you specify `-xpg`. The two do not prepare or use data provided by the other.

Profiles are generated by using `prof(1)` or `gprof(1)` on 64 bit Solaris platforms or just `gprof` on 32 bit Solaris platforms and include approximate user CPU times. These times are derived from PC sample data (see `pcsample(2)`) for routines in the main executable and routines in shared libraries specified as linker arguments when the executable is linked. Other shared libraries (libraries opened after process startup using `dlopen(3DL)`) are not profiled.

On 32 bit Solaris systems, profiles generated using `prof(1)` are limited to routines in the executable. 32 bit shared libraries can be profiled by linking the executable with `-xpg` and using `gprof(1)`.

The Solaris 10 software does not include system libraries compiled with `-p`. As a result, profiles collected on Solaris 10 platforms do not include call counts for system library routines.

If you specify `-xpg` at compile time, you must also specify it at link time. See [“Compile-Time and Link-Time Options” on page A 3](#) for a complete list of options that must be specified at both compile time and link time.

B.2.122 `-xprefetch[=val[, val]]`

(SPARC) Enable prefetch instructions on those architectures that support prefetch, such as UltraSPARC II. (`-xarch=v8plus, v9plusa, v9, or v9a`)

Explicit prefetching should only be used under special circumstances that are supported by measurements.

val must be one of the following:

TABLE B-37 The `-xprefetch` Flags

Flag	Meaning
<code>latx:factor</code>	Adjust the compiler’s assumed prefetch-to-load and prefetch-to-store latencies by the specified factor. You can only combine this flag with <code>-xprefetch=auto</code> . See Section B.2.122.1, “Prefetch Latency Ratio” on page B-82
<code>[no%]auto</code>	[Disable] Enable automatic generation of prefetch instructions
<code>[no%]explicit</code>	(SPARC) [Disable] Enable explicit prefetch macros
<code>yes</code>	Obsolete - do not use. Use <code>-xprefetch=auto, explicit</code> instead.
<code>no</code>	Obsolete - do not use. Use <code>-xprefetch=no%auto, no%explicit</code> instead.

The default for `-xprefetch` has changed and is now `-xprefetch=auto,explicit`. This change adversely affects applications that have essentially non-linear memory access patterns. To disable the change, specify `-xprefetch=no%auto,no%explicit`.

The `sun_prefetch.h` header file provides the macros that you can use to specify explicit prefetch instructions. The prefetches are approximately at the place in the executable that corresponds to where the macros appear.

B.2.122.1 Prefetch Latency Ratio

The prefetch latency is the hardware delay between the execution of a prefetch instruction and the time the data being prefetched is available in the cache.

The factor must be a positive number of the form *n.n*.

The compiler assumes a prefetch latency value when determining how far apart to place a prefetch instruction and the load or store instruction that uses the prefetched data. The assumed latency between a prefetch and a load may not be the same as the assumed latency between a prefetch and a store.

The compiler tunes the prefetch mechanism for optimal performance across a wide range of machines and applications. This tuning may not always be optimal. For memory-intensive applications, especially applications intended to run on large multiprocessors, you may be able to obtain better performance by increasing the prefetch latency values. To increase the values, use a factor that is greater than 1 (one). A value between .5 and 2.0 will most likely provide the maximum performance.

For applications with datasets that reside entirely within the external cache, you may be able to obtain better performance by decreasing the prefetch latency values. To decrease the values, use a factor that is less than one.

To use the `latx:factor` suboption, start with a factor value near 1.0 and run performance tests against the application. Then increase or decrease the factor, as appropriate, and run the performance tests again. Continue adjusting the factor and running the performance tests until you achieve optimum performance. When you increase or decrease the factor in small steps, you will see no performance difference for a few steps, then a sudden difference, then it will level off again.

B.2.123 `-xprefetch_auto_type=a`

(SPARC) Where *a* is `[no%]indirect_array_access`.

Use this option to determine whether or not the compiler generates indirect prefetches for the loops indicated by the option `-xprefetch_level` in the same fashion the prefetches for direct memory accesses are generated.

If you do not specify a setting for `-xprefetch_auto_type`, the compiler sets it to `-xprefetch_auto_type=no%indirect_array_access`.

Options such as `-xalias_level` can affect the aggressiveness of computing the indirect prefetch candidates and therefore the aggressiveness of the automatic indirect prefetch insertion due to better memory alias disambiguation information.

B.2.124 `-xprefetch_level=l`

(SPARC) Use the `-xprefetch_level` option to control the aggressiveness of automatic insertion of prefetch instructions as determined with `-xprefetch=auto`. *l* must be 1, 2, or 3. The compiler becomes more aggressive, or in other words, introduces more prefetches with each, higher, level of `-xprefetch_level`.

The appropriate value for the `-xprefetch_level` depends on the number of cache misses the application may have. Higher `-xprefetch_level` values have the potential to improve the performance of applications.

This option is effective only when it is compiled with `-xprefetch=auto`, with optimization level 3 or greater, and generate code for a platform that supports prefetch (`v8plus`, `v8plusa`, `v9`, `v9a`, `v9b`, `generic64`, `native64`).

`-xprefetch_level=1` enables automatic generation of prefetch instructions.

`-xprefetch_level=2` enables additional generation beyond level 1 and

`-xprefetch_level=3` enables additional generation beyond level 2.

The default is `-xprefetch_level=1` when you specify `-xprefetch=auto`.

B.2.125 `-xprofile=p`

Use this option to collect and save execution-frequency data so you can then use the data in subsequent runs to improve performance. This option is only valid when you specify optimization at level `-xO2` or above.

You must specify `-xprofile` at compile time as well as link time. For a complete list of all compiler options that must be specified at both compile time and at link time, see [TABLE 2-2](#).

Compiling with high optimization levels (for example `-xO5`) is enhanced by providing the compiler with runtime-performance feedback. In order to produce runtime-performance feedback, you must compile with `-xprofile=collect`, run the executable against a typical data set, and then recompile at the highest optimization level and with `-xprofile=use`.

Profile collection is safe for multithreaded applications. That is, profiling a program that does its own multitasking (`-mt`) produces accurate results.

p must be `collect[:name]`, `use[:name]`, or `tcov`.

- `collect[:name]`

Collects and saves execution-frequency data for later use by the optimizer with `-xprofile=use`. The compiler generates code to measure statement execution-frequency.

The *name* is the name of the program that is being analyzed. This name is optional. If *name* is not specified, `a.out` is assumed to be the name of the executable.

You can set the environment variables `SUN_PROFDATA` and `SUN_PROFDATA_DIR` to control where a program compiled with `-xprofile=collect` stores the profile data. If set, the `-xprofile=collect` data is written to `SUN_PROFDATA_DIR/SUN_PROFDATA`.

These environment variables similarly control the path and names of the profile data files written by `tcov`, as described in the `tcov(1)` man page.

If these environment variables are not set, the profile data is written to `name.profile/feedback` in the current directory, where *name* is the name of the executable or the name specified in the `-xprofile=collect:name` flag. `-xprofile` does not append `.profile` to *name* if *name* already ends in `.profile`. If you run the program several times, the executions-frequency data accumulates in the `feedback` file; that is, output from prior executions is not lost.

If you are compiling and linking in separate steps, make sure that any object files compiled with `-xprofile=collect` are also linked with `-xprofile=collect`.

- `use[:name]`

The program is optimized by using the execution-frequency data generated and saved in the `feedback` files from a previous execution of the program that was compiled with `-xprofile=collect`.

The *name* is the name of the program that is being analyzed. This name is optional. If *name* is not specified, `a.out` is assumed to be the name of the executable.

Except for the `-xprofile` option which changes from `-xprofile=collect` to `-xprofile=use`, the source files and other compiler options must be exactly the same as those used for the compilation that created the compiled program which in turn generated the `feedback` file. The same version of the compiler must be

used for both the collect build and the use build as well. If compiled with `-xprofile=collect:name`, the same program name *name* must appear in the optimizing compilation: `-xprofile=use:name`.

The association between an object file and its profile data is based on the UNIX pathname of the object file when it is compiled with `-xprofile=collect`. In some circumstances, the compiler will not associate an object file with its profile data: the object file has no profile data because it was not previously compiled with `-xprofile=collect`, the object file is not linked in a program with `-xprofile=collect`, the program has never been executed.

The compiler can also become confused if an object file was previously compiled in a different directory with `-xprofile=collect` and this object file shares a common basename with other object files compiled with `-xprofile=collect` but they cannot be uniquely identified by the names of their containing directories. In this case, even if the object file has profile data, the compiler will not be able to find it in the feedback directory when the object file is recompiled with `-xprofile=use`.

All of these situations cause the compiler to lose the association between an object file and its profile data. Therefore, if an object file has profile data but the compiler is unable to associate it with the object file's pathname when you specify `-xprofile=use`, use the `-xprofile_pathmap` option to identify correct directory. See [Section B.2.127](#), “`-xprofile_pathmap`” on [page B-87](#).

■ tcov

Basic block coverage analysis using “new” style tcov.

The `-xprofile=tcov` option is the new style of basic block profiling for tcov. It has similar functionality to the `-xa` option, but correctly collects data for programs that have source code in header files. See [Section B.2.64](#), “`-xa`” on [page B-26](#) for information on the old style of profiling, the `tcov(1)` man page, and *Program Performance Analysis Tools* for more details.

Code instrumentation is performed similarly to that of the `-xa` option, but `.d` files are no longer generated. Instead, a single file is generated, the name of which is based on the final executable. For example, if the program is run out of `/foo/bar/myprog.profile`, the data file is stored in `/foo/bar/myprog.profile/myprog.tcovd`.

The `-xprofile=tcov` and the `-xa` options are compatible in a single executable. That is, you can link a program that contains some files that have been compiled with `-xprofile=tcov`, and others with `-xa`. You cannot compile a single file with both options.

When running tcov, you must pass it the `-x` option to make it use the new style of data. If not, tcov uses the old `.d` files, if any, by default for data, and produces unexpected output.

Unlike the `-xa` option, the `TCOVDIR` environment variable has no effect at compile-time. However, its value is used at program runtime. See `tcov(1)` and *Program Performance Analysis Tools* for more details.

Note – `tcov`'s code coverage report can be unreliable if there is inlining of routines due to `-xO4` or `-xinline`.

When you use `-xprofile=collect` to compile a program for profile collection and `-xprofile=use` to compile a program for profile feedback, the source files and compiler options other than `-xprofile=collect` and `-xprofile=use` must be identical in both compilations.

The profile feedback directory names specified by the `-xprofile=use:name` option are accumulated from all instances of the option in a single invocation of the compiler. For example, assume that profile directories `a.profile`, `b.profile` and `c.profile` are created as a result of executing profiled binaries named `a`, `b`, and `c` respectively.

```
cc -O -c foo.c -xprofile=use:a -xprofile=use:b -xprofile=use:c
```

All three profile directories are used. Any valid profile feedback data pertaining to a particular object file is accumulated from the specified feedback directories when the object file is compiled.

If both `-xprofile=collect` and `-xprofile=use` are specified in the same command line, the rightmost `-xprofile` option in the command line is applied as follows:

- If the rightmost `-xprofile` option is `-xprofile=use`, all profile feedback directory names specified by the `-xprofile=use` options are used for feedback-directed optimization, and the previous `-xprofile=collect` options are ignored.
- If the right-most `-xprofile` option is `-xprofile=collect`, all profile feedback directory names specified by `-xprofile=use` options are ignored, and instrumentation for profile generation is enabled.

See also: `-xhwcprof`, `-xprofile_ircache`, `-xprofile_pathmap`

B.2.126 `-xprofile_ircache[=path]`

(SPARC) Use `-xprofile_ircache[=path]` with `-xprofile=collect|use` to improve compilation time during the use phase by reusing compilation data saved from the collect phase.

With large programs, compilation time in the use phase can improve significantly because the intermediate data is saved. Note that the saved data could increase disk space requirements considerably.

When you use `-xprofile_ircache[=path]`, *path* overrides the location where the cached files are saved. By default, these files are saved in the same directory as the object file. Specifying a path is useful when the `collect` and `use` phases happen in two different directories. Here's a typical sequence of commands:

```
example% cc -xO5 -xprofile=collect -xprofile_ircache t1.c t2.c
example% a.out // run collects feedback data
example% cc -xO5 -xprofile=use -xprofile_ircache t1.c t2.c
```

B.2.127 `-xprofile_pathmap`

(SPARC) Use the `-xprofile_pathmap=collect_prefix:use_prefix` option when you are also specifying the `-xprofile=use` command. Use `-xprofile_pathmap` when both of the following are true and the compiler is unable to find profile data for an object file that is compiled with `-xprofile=use`.

- You are compiling the object file with `-xprofile=use` in a directory that is different from the directory in which the object file was previously compiled with `-xprofile=collect`.
- Your object files share a common basename in the profile but are distinguished from each other by their location in different directories.

The *collect-prefix* is the prefix of the UNIX pathname of a directory tree in which object files were compiled using `-xprofile=collect`.

The *use-prefix* is the prefix of the UNIX pathname of a directory tree in which object files are to be compiled using `-xprofile=use`.

If you specify multiple instances of `-xprofile_pathmap`, the compiler processes them in the order of their occurrence. Each *use-prefix* specified by an instance of `-xprofile_pathmap` is compared with the object file pathname until either a matching *use-prefix* is identified or the last specified *use-prefix* is found not to match the object file pathname.

B.2.128 `-xreduction`

(SPARC) Turns on reduction recognition during automatic parallelization.

`-xreduction` must be specified with `-xautopar`, or `-xparallel` otherwise the compiler issues a warning.

When reduction recognition is enabled, the compiler parallelizes reductions such as *dot* products, maximum and minimum finding. These reductions yield different roundoffs than obtained by unparallelized code.

B.2.129 `-xregs=r[,r...]`

Specifies the usage of registers for the generated code.

r is a comma-separated list that consists of one or more of the following: `[no%]appl`, `[no%]float`, `[no%]frameptr`.

Example: `-xregs=appl,no%float`

TABLE B-38 The `-xregs` Flags

Flag	Meaning
<code>[no%]appl</code>	<p>(SPARC) [Does not] Allow the compiler to generate code using the application registers as scratch registers. The application registers are: <code>g2, g3, g4 (v8a, v8, v8plus, v8plusa, v8plusb)</code> <code>g2, g3 (v9, v9a, v9b)</code></p> <p>It is strongly recommended that all system software and libraries be compiled using <code>-xregs=no%appl</code>. System software (including shared libraries) must preserve these registers' values for the application. Their use is intended to be controlled by the compilation system and must be consistent throughout the application.</p> <p>For more information on SPARC instruction sets, see Section B.2.66, "<code>-xarch=isa</code>" on page B-29.</p> <p>In the SPARC ABI, these registers are described as <i>application</i> registers. Using these registers can increase performance because fewer load and store instructions are needed. However, such use can conflict with some old library programs written in assembly code.</p>
<code>[no%]float</code>	<p>(SPARC) [Does not] Allow the compiler to generate code by using the floating-point registers as scratch registers for integer values. Use of floating-point values may use these registers regardless of this option. If you want your code to be free of all references to floating point registers, you need to use <code>-xregs=no%float</code> and also make sure your code does not use floating point types in any way.</p>

TABLE B-38 The `-xregs` Flags (*Continued*)

Flag	Meaning
<code>[no%] frameptr</code>	<p data-bbox="568 241 1279 319">(x86) [Does not] Allow the compiler to use the frame-pointer register (<code>%ebp</code> on IA32, <code>%rbp</code> on AMD64) as an unallocated callee-saves register.</p> <p data-bbox="568 331 1296 493">Using this register as an unallocated callee-saves register may improve program run time. However, it also reduces the capacity of some tools to inspect and follow the stack. This stack inspection capability is important for system performance measurement and tuning. Therefore, using this optimization may improve local program performance at the expense of global system performance.</p> <ul data-bbox="568 505 1296 774" style="list-style-type: none"> <li data-bbox="568 505 1265 557">• Tools, such as the Performance Analyzer, that dump the stack for postmortem diagnosis will not work. <li data-bbox="568 569 1296 621">• Debuggers (e.g. <code>adb</code>, <code>mdb</code>, <code>dbx</code>) will not be able to dump the stack or directly pop stack frames. <li data-bbox="568 633 1296 708">• The <code>dtrace</code> performance analysis facility will be unable to collect information on any frames on the stack before the most recent frame missing the frame pointer. <li data-bbox="568 720 1265 743">• Posix <code>pthread_cancel</code> will fail trying to find cleanup handlers. <li data-bbox="568 755 1153 774">• C++ exceptions cannot propagate through C functions. <p data-bbox="568 786 1296 916">The failures in C++ exceptions occur when a C function that has lost its frame pointer calls a C++ function that throws an exception through the C function. Such calls typically occur when a function accepts a function pointer (for example, <code>qsort</code>) or when a global function, such as <code>malloc</code>, is interposed upon.</p> <p data-bbox="568 928 1296 1058">The last two affects listed above may impact the correct operation of applications. Most application code will not encounter these problems. Libraries that are developed by using <code>-xO4</code>, however, need documentation that details the restrictions of their usage by their clients.</p> <p data-bbox="568 1071 1296 1130">Note: The compiler ignores <code>-xregs=frameptr</code> and issues a warning if you also specify <code>-xpg</code>.</p>

The (SPARC) default is `-xregs=appl, float`.

The x86 default is `-xregs=no%frameptr` unless you specify `-fast` or an optimization of `-xO5` in which case `-xregs=frameptr`.

It is strongly recommended that you compile code intended for shared libraries that will link with applications, with `-xregs=no%appl, float`. At the very least, the shared library should explicitly document how it uses the application registers so that applications linking with those libraries know how to cope with the issue.

For example, an application using the registers in some global sense (such as using a register to point to some critical data structure) would need to know exactly how a library with code compiled without `-xregs=no%appl` is using the application registers in order to safely link with that library.

B.2.130 `-xrestrict[=f]`

(SPARC) Treats pointer-valued function parameters as restricted pointers. *f* is `%all`, `%none`, or a comma-separated list of one or more function names: `{%all|%none|fn[,fn...]}`.

If a function list is specified with this option, pointer parameters in the specified functions are treated as restricted; if `-xrestrict=%all` is specified, all pointer parameters in the entire C file are treated as restricted. Refer to [Section 3.8.2, “Restricted Pointers” on page 3-21](#), for more information.

This command-line option can be used on its own, but it is best used with optimization. For example, the command:

```
%cc -xO3 -xrestrict=%all prog.c
```

treats all pointer parameters in the file `prog.c` as restricted pointers. The command:

```
%cc -xO3 -xrestrict=agc prog.c
```

treats all pointer parameters in the function `agc` in the file `prog.c` as restricted pointers.

The default is `%none`; specifying `-xrestrict` is equivalent to specifying `-xrestrict=%all`.

B.2.131 `-xs`

Allows debugging by `dbx` without object files.

This option causes all the debug information to be copied into the executable. This has little impact on `dbx` performance or the run-time performance of the program, but it does take more disk space.

B.2.132 `-xsafe=mem`

(SPARC) Allows the compiler to assume no memory-based traps occur.

This option grants permission to use the speculative load instruction on V9 machines. It is only effective when you specify `-xO5` optimization and `-xarch=v8plus|v8plusa|v9|v9a`.

Note – Because non-faulting loads do not cause a trap when a fault such as address misalignment or segmentation violation occurs, you should use this option only for programs in which such faults cannot occur. Because few programs incur memory-based traps, you can safely use this option for most programs. Do not use this option for programs that explicitly depend on memory-based traps to handle exceptional conditions.

B.2.133 `-xsb`

Use this option to generate extra symbol table information for the Source Browser. This option is not valid with the `-xs` mode of the compiler.

If you are compiling and linking in separate steps, be sure to specify `-xsb` in both the compile step and the link step otherwise you will see error messages from the linker. For a complete list of all compiler options that must be specified at both compile time and at link time, see [TABLE 2-2](#).

If you do not use `-xsb` to link objects that were compiled with `-xsb`, you limit the source browser data to those references used by the executable that was created with the link step. Also, if you do not specify `-xsb` in separate compile and link steps, some symbol references in the source browser database may be lost.

By including `-xsb` in both the compile step and the separate link step, you ensure that all symbol references in both objects are visible to the source browser when the objects are compiled in different ways in the same directory and linked with different executables.

B.2.134 `-xsbfast`

Creates the database for the Source Browser. Does not compile source into an object file. This option is not valid with the `-xs` mode of the compiler.

B.2.135 `-xsfpcnst`

Represents unsuffixed floating-point constants as single precision, instead of the default mode of double precision. Not valid with `-xc`.

B.2.136 `-xspace`

Does no optimizations or parallelization of loops that increase code size.

Example: The compiler will not unroll loops or parallelize loops if it increases code size.

B.2.137 `-xstrconst`

Inserts string literals into the read-only data section of the text segment instead of the default data segment. Duplicate strings will be eliminated and the remaining copy shared amongst references in the code.

B.2.138 `-xtarget=t`

Specifies the target system for instruction set and optimization.

The value of *t* must be one of the following: *native*, *generic*, *system-name*.

Each specific value for `-xtarget` expands into a specific set of values for the `-xarch`, `-xchip`, and `-xcache` options. Use the `-xdryrun` option to determine the expansion of `-xtarget=native` on a running system. See [TABLE B-40](#) and [TABLE B-41](#) for the expansion values.

TABLE B-39 The `-xtarget` Flags

Flag	Meaning
<code>native</code>	Gets the best performance on the host system. The compiler generates code for the best performance on the host system. It determines the available architecture, chip, and cache properties of the machine on which the compiler is running.
<code>native64</code>	Gets the best performance for 64-bit object binaries on the host system. The compiler generates 64-bit object binaries optimized for the host system. It determines the available 64-bit architecture, chip, and cache properties of the machine on which the compiler is running.

TABLE B-39 The `-xtarget` Flags

Flag	Meaning
<code>generic</code>	Gets the best performance for generic architecture, chip, and cache. The compiler expands <code>-xtarget=generic</code> to: <code>-xarch=generic -xchip=generic -xcache=generic</code> This is the default value.
<code>generic64</code>	Sets the parameters for the best performance of 64-bit object binaries over most 64-bit platform architectures.
<i>system-name</i>	Gets the best performance for the specified system. You select a system name from TABLE B-40 that lists the mnemonic encodings of the actual system name and numbers.

The performance of some programs may benefit by providing the compiler with an accurate description of the target computer hardware. When program performance is critical, the proper specification of the target hardware could be very important. This is especially true when running on the newer SPARC processors. However, for most programs and older SPARC processors, the performance gain is negligible and a generic specification is sufficient.

Each specific value for `-xtarget` expands into a specific set of values for the `-xarch`, `-xchip`, and `-xcache` options. Use the `-xdryrun` option to determine the expansion of `-xtarget=native` on a running system. See [TABLE B-40](#) for the values.

For example, `-xtarget=sun4/15` is equivalent to: `-xarch=v8a -xchip=micro -xcache=2/16/1`.

Note – The expansion of `-xtarget` for a specific host platform might not result in the same `-xarch`, `-xchip`, or `-xcache` settings as `-xtarget=native` when compiling on that platform.

TABLE B-40 The `-xtarget` Expansions on SPARC

<code>-xtarget=</code>	<code>-xarch</code>	<code>-xchip</code>	<code>-xcache</code>
<code>generic</code>	<code>generic</code>	<code>generic</code>	<code>generic</code>
<code>cs6400</code>	<code>v8</code>	<code>super</code>	<code>16/32/4:2048/64/1</code>
<code>entr150</code>	<code>v8</code>	<code>ultra</code>	<code>16/32/1:512/64/1</code>
<code>entr2</code>	<code>v8plusa</code>	<code>ultra</code>	<code>16/32/1:512/64/1</code>
<code>entr2/1170</code>	<code>v8plusa</code>	<code>ultra</code>	<code>16/32/1:512/64/1</code>
<code>entr2/1200</code>	<code>v8plusa</code>	<code>ultra</code>	<code>16/32/1:512/64/1</code>
<code>entr2/2170</code>	<code>v8plusa</code>	<code>ultra</code>	<code>16/32/1:512/64/1</code>

TABLE B-40 The `-xtarget` Expansions on SPARC (*Continued*)

-xtarget=	-xarch	-xchip	-xcache
entr2/2200	v8plusa	ultra	16/32/1:512/64/1
entr3000	v8plusa	ultra	16/32/1:512/64/1
entr4000	v8plusa	ultra	16/32/1:512/64/1
entr5000	v8plusa	ultra	16/32/1:512/64/1
entr6000	v8plusa	ultra	16/32/1:512/64/1
sc2000	v8	super	16/32/4:2048/64/1
solb6	v8	super	16/32/4:1024/32/1
ss10	v8	super	16/32/4
ss10/20	v8	super	16/32/4
ss10/30	v8	super	16/32/4
ss10/40	v8	super	16/32/4
ss10/402	v8	super	16/32/4
ss10/41	v8	super	16/32/4:1024/32/1
ss10/412	v8	super	16/32/4:1024/32/1
ss10/50	v8	super	16/32/4
ss10/51	v8	super	16/32/4:1024/32/1
ss10/512	v8	super	16/32/4:1024/32/1
ss10/514	v8	super	16/32/4:1024/32/1
ss10/61	v8	super	16/32/4:1024/32/1
ss10/612	v8	super	16/32/4:1024/32/1
ss10/71	v8	super2	16/32/4:1024/32/1
ss10/712	v8	super2	16/32/4:1024/32/1
ss10/hs11	v8	hyper	256/64/1
ss10/hs12	v8	hyper	256/64/1
ss10/hs14	v8	hyper	256/64/1
ss10/hs21	v8	hyper	256/64/1
ss10/hs22	v8	hyper	256/64/1
ss1000	v8	super	16/32/4:1024/32/1
ss20	v8	super	16/32/4:1024/32/1
ss20/151	v8	hyper	512/64/1

TABLE B-40 The `-xtarget` Expansions on SPARC (Continued)

<code>-xtarget=</code>	<code>-xarch</code>	<code>-xchip</code>	<code>-xcache</code>
ss20/152	v8	hyper	512/64/1
ss20/50	v8	super	16/32/4
ss20/502	v8	super	16/32/4
ss20/51	v8	super	16/32/4:1024/32/1
ss20/512	v8	super	16/32/4:1024/32/1
ss20/514	v8	super	16/32/4:1024/32/1
ss20/61	v8	super	16/32/4:1024/32/1
ss20/612	v8	super	16/32/4:1024/32/1
ss20/71	v8	super2	16/32/4:1024/32/1
ss20/712	v8	super2	16/32/4:1024/32/1
ss20/hs11	v8	hyper	256/64/1
ss20/hs12	v8	hyper	256/64/1
ss20/hs14	v8	hyper	256/64/1
ss20/hs21	v8	hyper	256/64/1
ss20/hs22	v8	hyper	256/64/1
ss4	v8a	micro2	8/16/1
ss4/110	v8a	micro2	8/16/1
ss4/85	v8a	micro2	8/16/1
ss5	v8a	micro2	8/16/1
ss5/110	v8a	micro2	8/16/1
ss5/85	v8a	micro2	8/16/1
ss600/41	v8	super	16/32/4:1024/32/1
ss600/412	v8	super	16/32/4:1024/32/1
ss600/51	v8	super	16/32/4:1024/32/1
ss600/512	v8	super	16/32/4:1024/32/1
ss600/514	v8	super	16/32/4:1024/32/1
ss600/61	v8	super	16/32/4:1024/32/1
ss600/612	v8	super	16/32/4:1024/32/1
sslc	v8a	micro	2/16/1
sslx	v8a	micro	2/16/1

TABLE B-40 The `-xtarget` Expansions on SPARC (*Continued*)

<code>-xtarget=</code>	<code>-xarch</code>	<code>-xchip</code>	<code>-xcache</code>
sslx2	v8a	micro2	8/16/1
ssvyger	v8a	micro2	8/16/1
sun4/15	v8a	micro	2/16/1
sun4/30	v8a	micro	2/16/1
ultra	v8plusa	ultra	16/32/1:512/64/1
ultra1/140	v8plusa	ultra	16/32/1:512/64/1
ultra1/170	v8plusa	ultra	16/32/1:512/64/1
ultra1/200	v8plusa	ultra	16/32/1:512/64/1
ultra2	v8plusa	ultra2	16/32/1:512/64/1
ultra2/1170	v8plusa	ultra	16/32/1:512/64/1
ultra2/1200	v8plusa	ultra	16/32/1:1024/64/1
ultra2/1300	v8plusa	ultra2	16/32/1:2048/64/1
ultra2/2170	v8plusa	ultra	16/32/1:512/64/1
ultra2/2200	v8plusa	ultra	16/32/1:1024/64/1
ultra2/2300	v8plusa	ultra2	16/32/1:2048/64/1
ultra2e	v8plusa	ultra2e	16/32/1:256/64/4
ultra2i	v8plusa	ultra2i	16/32/1:512/64/1
ultra3	v8plusa	ultra3	64/32/4:8192/512/1
ultra3cu	v8plusa	ultra3cu	64/32/4:8192/512/2
ultra3i	v8plusa	ultra3i	64/32/4:1024/64/4
ultra3iplus	v8plusa	ultra3iplus	64/32/4:4096/64/4
ultra4	v8plusa	ultra4	64/32/4:8192/128/2
ultra4plus	v8plusa	ultra4plus	64/32/4:2048/64/4/2:32768/64/4**
ultraT1	v8plusa	ultraT1	8/16/4/4:3072/64/12/32**

** See "`-xcache=c`" on page B 39 for an explanation of the cache properties associated with the UltraSPARC IVplus and UltraSPARC T1 chips.

The following table lists the `-xtarget` values for the x86 architecture:

TABLE B-41 The `-xtarget` Expansions on x86 Architecture

<code>-xtarget=</code>	<code>-xarch</code>	<code>-xchip</code>	<code>-xcache</code>
generic	generic	generic	generic
386*			
486*			
opteron	sse2	opteron	64/64/2:1024/64/16
pentium	386	pentium	generic
pentium_pro	pentium_pro	pentium_pro	generic
pentium3	sse	pentium3	16/32/4:256/32/4
pentium4	sse2	pentium4	8/64/4:256/128/8

* Obsolete. Use `-xtarget=generic` instead. For a complete list of obsolete options, see [Section A.1.15, “Obsolete Options” on page A-13](#).

Note – The new `-xtarget=opteron` option does not automatically generate 64-bit code. It expands to `-xarch=sse2`, `-xchip=opteron`, and `-xcache=64/64/2:1024/64/16` which results in 32-bit code. You must specify `-xarch=amd64` after (to the right of) `-xtarget` to compile 64-bit code.

B.2.139 `-xtemp=dir`

Sets the directory for temporary files used by `cc` to *dir*. No space is allowed within this option string. Without this option, temporary files go into `/tmp`. `-xtemp` has precedence over the `TMPDIR` environment variable.

B.2.140 `-xthreadvar[=0]`

Specify `-xthreadvar` to control the implementation of thread local variables. Use this option in conjunction with the `__thread` declaration specifier to take advantage of the compiler’s thread-local storage facility. After you declare the thread variables with the `__thread` specifier, specify `-xthreadvar` to enable the use of thread-local storage with position dependent code (non-PIC code) in dynamic (shared) libraries. For more information on how to use `__thread`, see [Section 2.3, “Thread Local Storage Specifier” on page 2-3](#).

o must be one the following:

TABLE B-42 The `-xthreadvar` Flags

Flag	Meaning
<code>[no%]dynamic</code>	[[Do not] Compile variables for dynamic loading. Access to thread variables is significantly faster when <code>-xthreadvar=no%dynamic</code> but you cannot use the object file within a dynamic library. That is, you can only use the object file in an executable file.

If you do not specify `-xthreadvar`, the default used by the compiler depends upon whether or not position-independent code is enabled. If position-independent code is enabled, the option is set to `-xthreadvar=dynamic`. If position-independent code is disabled, the option is set to `-xthreadvar=no%dynamic`.

If you specify `-xthreadvar`, but do not specify any values, the option is set to `-xthreadvar=dynamic`.

If there is non-position-independent code within a dynamic library, you must specify `-xthreadvar`.

The linker cannot support the thread-variable equivalent of non-PIC code in dynamic libraries. Non-PIC thread variables are significantly faster, and hence should be the default for executables.

Using thread variables on different versions of Solaris software requires different options on the command line.

- On Solaris 8 software, objects that use `__thread` must be compiled with `-mt` and must be linked with `-mt -L/usr/lib/lwp -R/usr/lib/lwp`.
- On Solaris 9 software, objects that use `__thread` must be compiled and linked with `-mt`.

See Also: `-xcode`, `-KPIC`, `-Kpic`

B.2.141 `-xtime`

Reports the time and resources used by each compilation component.

B.2.142 `-xtransition`

Issues warnings for the differences between K&R C and Sun ISO C.

The `-xtransition` option issues warnings in conjunction with the `-Xa` and `-Xt` options. You can eliminate all warning messages about differing behavior through appropriate coding. The following warnings no longer appear unless you issue the `-xtransition` option:

- `\a` is ISO C "alert" character
- `\x` is ISO C hex escape
- bad octal digit
- base type is really *type tag: name*
- comment is replaced by `"##"`
- comment does not concatenate tokens
- declaration introduces new type in ISO C: *type tag*
- macro replacement within a character constant
- macro replacement within a string literal
- no macro replacement within a character constant
- no macro replacement within a string literal
- operand treated as unsigned
- trigraph sequence replaced
- ISO C treats constant as unsigned: *operator*
- semantics of *operator* change in ISO C; use explicit cast

B.2.143 `-xtrigraphs`

The `-xtrigraphs` option determines whether the compiler recognizes trigraph sequences as defined by the ISO C standard.

By default, the compiler assumes `-xtrigraphs=yes` and recognizes all trigraph sequences throughout the compilation unit.

If your source code has a literal string containing question marks (?) that the compiler is interpreting as a trigraph sequence, you can use the `-xtrigraph=no` suboption to turn off the recognition of trigraph sequences. The `-xtrigraphs=no` option turns off recognition of all trigraphs throughout the entire compilation unit.

Consider the following example source file named `trigraphs_demo.c`.

```
#include <stdio.h>

int main ()
{
    (void) printf("(\\?\\?) in a string appears as (??)\\n");
    return 0;
}
```

Here is the output if you compile this code with `-xtrigraphs=yes`.

```
example% cc -xtrigraphs=yes trigraphs_demo.c
example% a.out
(??) in a string appears as {}
```

Here is the output if you compile this code with `-xtrigraphs=no`.

```
example% cc -xtrigraphs=no trigraphs_demo.c
example% a.out
(??) in a string appears as (??)
```

B.2.144 `-xunroll=n`

Suggests to the optimizer to unroll loops *n* times. *n* is a positive integer. When *n* is 1, it is a command, and the compiler unrolls no loops. When *n* is greater than 1, the `-xunroll=n` merely suggests to the compiler that it unroll loops *n* times.

B.2.145 `-xustr={ascii_utf16_ushort|no}`

Use this option if you need to support an internationalized application that uses ISO10646 UTF-16 string literals. In other words, use this option if your code contains a string literal that you want the compiler to convert to UTF-16 strings in the object file. Without this option, the compiler neither produces nor recognizes sixteen-bit character string literals. This option enables recognition of the U"ASCII_string" string literals as an array of type unsigned short int. Since such strings are not yet part of any standard, this option enables recognition of non-standard C.

You can turn off compiler recognition of U"ASCII_string" string literals by specifying `-xustr=no`. The rightmost instance of this option on the command line overrides all previous instances.

The default is `-xustr=no`. If you specify `-xustr` without an argument, the compiler won't accept it and instead issues a warning. The default can change if the C or C++ standards define a meaning for the syntax.

It is not an error to specify `-xustr=ascii_utf16_ushort` without also specifying a U"ASCII_string" string literals.

Not all files have to be compiled with this option.

The following example shows a string literal in quotes that is prepended by U. It also shows a command line that specifies `-xustr`.

```
example% cat file.c
const unsigned short *foo = U"foo";
const unsigned short bar[] = U"bar";
const unsigned short *fun() { return
example% cc -xustr=ascii_utf16_ushort file.c -c
```

B.2.146 `-xvector[=a]`

Enable automatic generation of calls to the vector library functions and/or the generation of the SIMD (Single Instruction Multiple Data) instructions. You must use default rounding mode by specifying `-fround=nearest` when you use this option.

a is the equivalent of the following:

TABLE B-43 The `-xvector` Flags

Value	Meaning
[no%]lib	Does [not] enable the compiler to transform math library calls within loops into single calls to the equivalent vector math routines when such transformations are possible. This could result in a performance improvement for loops with large loop counts.
[no%]simd	Does [not] direct the compiler to use the native x86 SSE SIMD instructions to improve performance of certain loops. The compiler can only accept this switch if the target architecture supports SIMD instructions. For example, you must specify <code>-xarch=amd64</code> , <code>-xarch=amd64a</code> or <code>-xarch=generic64</code> . You must also specify an optimization level of <code>-xO3</code> or above as well as <code>-xdepend</code> when you specify <code>-xvector=simd</code> .
yes	This option may be deprecated in a future release. Specify <code>-xvector=lib</code> instead.
no	This option may be deprecated in a future release. Specify <code>-xvector=none</code> instead.

The default is `-xvector=%none`. If you specify `-xvector`, but do not provide a flag, the compiler assumes `-xvector=lib`.

If you use `-xvector` on the command line without previously specifying `-xdepend`, `-xvector` triggers `-xdepend`. The `-xvector` option also raises the optimization level to `-xO3` if optimization is not specified or optimization is set lower than `-xO3`.

The compiler includes the `libmvec` libraries in the load step. If you compile and link with separate commands, be sure to use `-xvector` in the linking `cc` command. For a complete list of all compiler options that must be specified at both compile time and at link time, see [TABLE 2-2](#).

B.2.147 `-xvis`

(SPARC) Use the `-xvis=[yes|no]` command when you are using the assembly-language templates defined in the VIS[tm] instruction-set Software Developers Kit (VSDK). The default is `-xvis=no`. Specifying `-xvis` is equivalent to specifying `-xvis=yes`.

The VIS instruction set is an extension to the SPARC v9 instruction set. Even though the UltraSPARC processors are 64-bit, there are many cases, especially in multimedia applications, when the data are limited to eight or 16 bits in size. The VIS instructions can process four 16-bit data with one instruction so they greatly improve the performance of applications that handle new media such as imaging, linear algebra, signal processing, audio, video and networking.

For more information on the VSDK, see <http://www.sun.com/processors/vis/>.

B.2.148 `-xvpara`

Show parallelization warning messages.

Issues warnings about potential parallel programming related problems that may cause incorrect results when using OpenMP or Sun parallel directives and pragmas.

Use with `-xopenmp` and OpenMP API directives, or with `-xexplicitpar` and MP parallelization directives.

Warnings are issued when the compiler detects the following situations:

- Loops that are parallelized using MP directives when there are data dependencies between different loop iterations
- Problematic use of OpenMP data sharing attributes clauses, such as declaring a variable "shared" whose accesses in an OpenMP parallel region may cause data race, or declaring a variable "private" whose value in a parallel region is used after the parallel region.

No warnings appear if all parallelization directives are processed without problems.

Example:

```
cc -xopenmp -vpara any.c
```

Note – Sun Studio compilers support OpenMP 2.5 API parallelization. Consequently, the MP pragmas directives are deprecated and are no longer supported. See the *OpenMP API User's Guide* for information on migrating to the OpenMP API.

B.2.149 `-Yc, dir`

Specifies a new directory *dir* for the location of component *c*. *c* can consist of any of the characters representing components that are listed under the `-W` option.

If the location of a component is specified, then the new path name for the tool is *dir/tool*. If more than one `-Y` option is applied to any one item, then the last occurrence holds.

B.2.150 `-YA, dir`

Specifies a directory *dir* to search for all compiler components. If a component is not found in *dir*, the search reverts to the directory where the compiler is installed.

B.2.151 `-YI, dir`

Changes the default directory searched for `include` files.

B.2.152 `-YP, dir`

Changes the default directory for finding library files.

B.2.153 `-YS, dir`

Changes the default directory for startup object files.

B.2.154 -Z11

(SPARC) Creates the program database for `lock_lint`, but does not generate executable code. Refer to the `lock_lint(1)` man page for more details.

B.3 Options Passed to the Linker

`cc` recognizes `-a`, `-e`, `-r`, `-t`, `-u`, and `-z` and passes these options and their arguments to `ld`. `cc` passes any unrecognized options to `ld` with a warning.

Implementation-Defined ISO/IEC C99 Behavior

The ISO/IEC 9899:1999, Programming Languages - C standard specifies the form and establishes the interpretation of programs written in C. However, this standard leaves a number of issues as implementation-defined, that is, as varying from compiler to compiler. This chapter details these areas. The section numbers are provided as part of the headings in this appendix for ready comparison to the ISO/IEC 9899:1999 standard itself:

- Each section heading uses the same section text and letter.number identifier as found in the ISO standard.
- Each section provides the requirement (preceded by a bullet) from the ISO standard which describes what it is that the implementation shall define. This requirement is then followed by an explanation of our implementation.

C.1 Implementation-defined Behavior (J.3)

A conforming implementation is required to document its choice of behavior in each of the areas listed in this subclause. The following are implementation-defined:

C.1.1 Translation (J.3.1)

- How a diagnostic is identified (3.10, 5.1.1.3).

Error and warning messages have the following format:

filename, line number: message

Where *filename* is the name of the file that contains the error or warning,

line number is the number of the line on which the error or warning is found, and *message* is the diagnostic message.

- Whether each nonempty sequence of white-space characters other than new-line is retained or replaced by one space character in translation phase 3 (5.1.1.2).

A sequence of nonempty characters consisting of a tab (`\t`), form-feed (`\f`), or vertical-feed (`\v`) are replaced by a single space character.

C.1.2 Environment (J.3.2)

- The mapping between physical source file multibyte characters and the source character set in translation phase 1 (5.1.1.2).

There are eight bits in a character for the ASCII portion; locale-specific multiples of eight bits for locale-specific extended portion.

- The name and type of the function called at program startup in a freestanding environment (5.1.2.1).

The implementation is hosted environment.

- The effect of program termination in a freestanding environment (5.1.2.1).

The implementation is in a hosted environment.

- An alternative manner in which the `main` function may be defined (5.1.2.2.1).

There is no alternative way to define `main` other than that defined in the standard.

- The values given to the strings pointed to by the `argv` argument to `main` (5.1.2.2.1).

`argv` is an array of pointers to the command-line arguments, where `argv[0]` represents the program name if it is available.

- What constitutes an interactive device (5.1.2.3).

An interactive device is one for which the system library call `isatty()` returns a nonzero value

- The set of signals, their semantics, and their default handling (7.14).

The following table shows the semantics for each signal as recognized by the `signal` function:

TABLE C-1 Semantics of `signal` Function Signals

Signal Number	Default Event	Semantics of Signal
SIGHUP 1	Exit	hangup
SIGINT 2	Exit	interrupt (rubout)
SIGQUIT 3	Core	quit (ASCII FS)
SIGILL 4	Core	illegal instruction (not reset when caught)

TABLE C-1 Semantics of signal Function Signals (*Continued*)

Signal Number	Default Event	Semantics of Signal
SIGTRAP 5	Core	trace trap (not reset when caught)
SIGIOT 6	Core	IOT instruction
SIGABRT 6	Core	Used by abort
SIGEMT 7	Core	EMT instruction
SIGFPE 8	Core	floating point exception
SIGKILL 9	Exit	kill (cannot be caught or ignored)
SIGBUS 10	Core	bus error
SIGSEGV 11	Core	segmentation violation
SIGSYS 12	Core	bad argument to system call
SIGPIPE 13	Exit	write on a pipe with no one to read it
SIGALRM 14	Exit	alarm clock
SIGTERM 15	Exit	software termination signal from kill
SIGUSR1 16	Exit	user defined signal 1
SIGUSR2 17	Exit	user defined signal 2
SIGCLD 18	Ignore	child status change
SIGCHLD 18	Ignore	child status change alias (POSIX)
SIGPWR 19	Ignore	power-fail restart
SIGWINCH 20	Ignore	window size change
SIGURG 21	Ignore	urgent socket condition
SIGPOLL 22	Exit	pollable event occurred
SIGIO 22	Sigpoll	socket I/O possible
SIGSTOP 23	Stop	stop (cannot be caught or ignored)
SIGTSTP 24	Stop	user stop requested from tty
SIGCONT 25	Ignore	stopped process has been continued
SIGTTIN 26	Stop	background tty read attempted
SIGTTOU 27	Stop	background tty write attempted
SIGVTALRM 28	Exit	virtual timer expired
SIGPROF 29	Exit	profiling timer expired
SIGXCPU 30	Core	exceeded cpu limit

TABLE C-1 Semantics of signal Function Signals (*Continued*)

Signal Number	Default Event	Semantics of Signal
SIGXFSZ 31	Core	exceeded file size limit
SIGWAITING 32	Ignore	reserved signal no longer used by threading code
SIGLWP 33	Ignore	reserved signal no longer used by threading code
SIGFREEZE 34	Ignore	Checkpoint suspend
SIGTHAW 35	Ignore	Checkpoint resume
SIGCANCEL 36	Ignore	Cancellation signal used by threads library
SIGLOST 37	Ignore	resource lost (record-lock lost)
SIGXRES 38	Ignore	Resource control exceeded (see <code>setrctl(2)</code>)
SIGJVM1 39	Ignore	Reserved for Java Virtual Machine 1
SIGJVM2 40	Ignore	Reserved for Java Virtual Machine 2

- Signal values other than `SIGFPE`, `SIGILL`, and `SIGSEGV` that correspond to a computational exception (7.14.1.1).
`SIGILL`, `SIGFPE`, `SIGSEGV`, `SIGTRAP`, `SIGBUS`, and `SIGEMT`, see [TABLE C-1](#).
- Signals for which the equivalent of `signal(sig, SIG_IGN)`; is executed at program startup (7.14.1.1).A
`SIGILL`, `SIGFPE`, `SIGSEGV`, `SIGTRAP`, `SIGBUS`, and `SIGEMT`, see [TABLE C-1](#).
- The set of environment names and the method for altering the environment list used by the `getenv` function (7.20.4.5).
- The manner of execution of the string by the `system` function (7.20.4.6).

From the `system(3C)` man page:

The `system()` function causes *string* to be given to the shell as input, as if *string* had been typed as a command at a terminal. The invoker waits until the shell has completed, then returns the exit status of the shell in the format specified by `waitpid(2)`.

If *string* is a null pointer, `system()` checks if the shell exists and is executable. If the shell is available, `system()` returns a non-zero value; otherwise, it returns 0.

C.1.3 Identifiers (J.3.3)

- Which additional multibyte characters may appear in identifiers and their correspondence to universal character names (6.4.2).

None

- The number of significant initial characters in an identifier (5.2.4.1, 6.4.2).

1023

C.1.4 Characters (J.3.4)

- The number of bits in a byte (3.6).

There are 8 bits in a byte.

- The values of the members of the execution character set (5.2.1).

Mapping is identical between source and execution characters.

- The unique value of the member of the execution character set produced for each of the standard alphabetic escape sequences (5.2.2).

TABLE C-2 Standard Alphabetic Escape Sequence Unique Values

Escape Sequence	Unique Value
\a (alert)	7
\b (backspace)	8
\f (form feed)	12
\n (new line)	10
\r (carriage return)	13
\t (horizontal tab)	9
\v (vertical tab)	11

- The value of a char object into which has been stored any character other than a member of the basic execution character set (6.2.5).

It is the numerical value of the low order 8 bits associated with the character assigned to the char object.

- Which of signed char or unsigned char has the same range, representation, and behavior as “plain” char (6.2.5, 6.3.1.1).

A signed char is treated as a “plain” char (SPARC) (x86).

- The mapping of members of the source character set (in character constants and string literals) to members of the execution character set (6.4.4.4, 5.1.1.2).

Mapping is identical between source and execution characters.

- The value of an integer character constant containing more than one character or containing a character or escape sequence that does not map to a single-byte execution character (6.4.4.4).

A multiple-character constant that is not an escape sequence has a value derived from the numeric values of each character.

- The value of a wide character constant containing more than one multibyte character, or containing a multibyte character or escape sequence not represented in the extended execution character set (6.4.4.4).

A multiple-character wide character constant that is not an escape sequence has a value derived from the numeric values of each character.

- The current locale used to convert a wide character constant consisting of a single multibyte character that maps to a member of the extended execution character set into a corresponding wide character code (6.4.4.4).

The valid locale specified by `LC_ALL`, `LC_CTYPE`, or `LANG` environment variable.

- The current locale used to convert a wide string literal into corresponding wide character codes (6.4.5).

The valid locale specified by `LC_ALL`, `LC_CTYPE`, or `LANG` environment variable.

- The value of a string literal containing a multibyte character or escape sequence not represented in the execution character set (6.4.5).

Each byte of the multibyte character forms a character of the string literal, with a value equivalent to the numerical value of that byte in the multibyte character.

C.1.5 Integers (J.3.5)

- Any extended integer types that exist in the implementation (6.2.5).

None

- Whether signed integer types are represented using sign and magnitude, two's complement, or one's complement, and whether the extraordinary value is a trap representation or an ordinary value (6.2.6.2).

Signed integer types are represented as two's complement. Extraordinary value is an ordinary value.

- The rank of any extended integer type relative to another extended integer type with the same precision (6.3.1.1).

Not applicable to this implementation.

- The result of, or the signal raised by, converting an integer to a signed integer type when the value cannot be represented in an object of that type (6.3.1.3).

When an integer is converted to a shorter signed integer, the low order bits are copied from the longer integer to the shorter signed integer. The result may be negative.

When an unsigned integer is converted to a signed integer of equal size, the low order bits are copied from the unsigned integer to the signed integer. The result may be negative.

- The results of some bitwise operations on signed integers (6.5).

The result of a bitwise operation applied to a signed type is the bitwise operation of the operands, including the sign bit. Thus, each bit in the result is set if--and only if--each of the corresponding bits in both of the operands is set.

C.1.6 Floating point (J.3.6)

- The accuracy of the floating-point operations and of the library functions in `<math.h>` and `<complex.h>` that return floating-point results (5.2.4.2.2).

The accuracy of floating point operations is consistent with the settings of `FLT_EVAL_METHOD`. The accuracy of the library functions in `<math.h>` and `<complex.h>` is as specified in the `libm(3LIB)` man page.

- The rounding behaviors characterized by non-standard values of `FLT_ROUNDS` (5.2.4.2.2).

Not applicable to this implementation.

- The evaluation methods characterized by non-standard negative values of `FLT_EVAL_METHOD` (5.2.4.2.2).

Not applicable to this implementation.

- The direction of rounding when an integer is converted to a floating-point number that cannot exactly represent the original value (6.3.1.4).

It honors the prevailing rounding direction mode.

- The direction of rounding when a floating-point number is converted to a narrower floating-point number (6.3.1.5).

It honors the prevailing rounding direction mode.

- How the nearest representable value or the larger or smaller representable value immediately adjacent to the nearest representable value is chosen for certain floating constants (6.4.4.2).

Floating-point constant is always rounded to the nearest representable value.

- Whether and how floating expressions are contracted when not disallowed by the `FP_CONTRACT` pragma (6.5).

Not applicable to this implementation.

- The default state for the `FENV_ACCESS` pragma (7.6.1).
For `-fsimple=0`, the default value is `ON`. Otherwise for all other values of `-fsimple`, the default value for `FENV_ACCESS` is `OFF`.
- Additional floating-point exceptions, rounding modes, environments, and classifications, and their macro names (7.6, 7.12).
Not applicable to this implementation.
- The default state for the `FP_CONTRACT` pragma (7.12.2).
For `-fsimple=0`, the default value is `OFF`. Otherwise for all other values of `-fsimple`, the default value for `FENV_ACCESS` is `ON`.
- Whether the “inexact” floating-point exception can be raised when the rounded result actually does equal the mathematical result in an IEC 60559 conformant implementation (F.9).
Results are indeterminable.
- Whether the underflow (and ‘inexact’) floating-point exception can be raised when a result is tiny but not inexact in an IEC 60559 conformant implementation(F.9).
The hardware does not raise underflow or inexact in such cases when trapping on underflow is disabled (the default).

C.1.7 Arrays and Pointers (J.3.7)

- The result of converting a pointer to an integer or `-xarch=v9` vice versa (6.3.2.3).
The bit pattern does not change when converting pointers and integers. Except when the results cannot be represented in the integer or pointer type, and then the results are undefined.
- The size of the result of subtracting two pointers to elements of the same array (6.5.6).
`int` as defined in `stddef.h`. `long` for `-xarch=v9`

C.1.8 Hints (J.3.8)

- The extent to which suggestions made by using the register storage-class specifier are effective (6.7.1).
The number of effective register declarations depends on patterns of use and definition within each function and is bounded by the number of registers available for allocation. Neither the compiler nor the optimizer is required to honor register declarations.

- The extent to which suggestions made by using the `inline` function specifier are effective (6.7.4).

The `inline` keyword is effective in causing the inlining of code only when using optimization, and only when the optimizer determines it is profitable to inline. See [Section A.1.1, “Optimization and Performance Options” on page A-1](#) for a list of optimization options.

C.1.9 Structures, Unions, Enumerations, and Bit-fields (J.3.9)

- Whether a “plain” int bit-field is treated as signed int bit-field or as an unsigned int bit-field (6.7.2, 6.7.2.1).

It is treated as an unsigned int.

- Allowable bit-field types other than `_Bool`, signed int, and unsigned int (6.7.2.1).

A bit field can be declared as any integer type.

- Whether a bit-field can straddle a storage-unit boundary (6.7.2.1).

Bit-fields do not straddle storage-unit boundaries.

- The order of allocation of bit-fields within a unit (6.7.2.1).

Bit-fields are allocated within a storage unit from high-order to low-order.

- The alignment of non-bit-field members of structures (6.7.2.1). This should present no problem unless binary data written by one implementation is read by another.

TABLE C-3 Padding and Alignment of Structure Members

Type	Alignment Boundary	Byte Alignment
<code>char</code>	byte	1
<code>short</code>	halfword	2
<code>int</code>	word	4
<code>long (SPARC) v8</code>	word	4
<code>long (SPARC) v9</code>	doubleword	8
<code>float (SPARC)</code>	word	4
<code>double (SPARC)</code>	doubleword	8
<code>double (x86)</code>	doubleword	4
<code>long double (SPARC) v8</code>	doubleword	8
<code>long double (x86)</code>	word	4

TABLE C-3 Padding and Alignment of Structure Members (*Continued*)

Type	Alignment Boundary	Byte Alignment
long double (<i>SPARC</i>) v9	quadword	16
pointer (<i>SPARC</i>) v8	word	4
pointer (<i>SPARC</i>) v9	quadword	8
long long	doubleword (<i>SPARC</i>)	8
long long (<i>x86</i>)	word	4
_Complex	float	8
_Complex	double	16
_Complex	long double	32
_Imaginary	float	4
_Imaginary (<i>SPARC</i>)	double	8
_Imaginary (<i>x86</i>)	double	4
_Imaginary (<i>SPARC</i>) v8	long double	8
_Imaginary (<i>SPARC</i>) v9	long double	16
_Imaginary (<i>x86</i>)	long double	4

- The integer type compatible with each enumerated type (6.7.2.2).
This is an int.

C.1.10 Qualifiers (J.3.10)

- What constitutes an access to an object that has volatile-qualified type (6.7.3).
Each reference to the name of an object constitutes one access to the object.

C.1.11 Preprocessing Directives (J.3.11)

- How sequences in both forms of header names are mapped to headers or external source file names (6.4.7).
Source file characters are mapped to their corresponding ASCII values.
- Whether the value of a character constant in a constant expression that controls conditional inclusion matches the value of the same character constant in the execution character set (6.10.1).
A character constant within a preprocessing directive has the same numeric value as it has within any other expression.

- Whether the value of a single-character character constant in a constant expression that controls conditional inclusion may have a negative value (6.10.1).
Character constants in this context may have negative values (SPARC) (x86).
- The places that are searched for an included `< >` delimited header, and how the places are specified other header is identified (6.10.2).
The location of header files depends upon the options specified on the command line, and in which file the `#include` directive appears. For more information, see [Section 2.14, “How to Specify Include Files” on page 2-27](#).
- How the named source file is searched for in an included `" "` delimited header (6.10.2).
The location of header files depends upon the options specified on the command line, and in which file the `#include` directive appears. For more information, see [Section 2.14, “How to Specify Include Files” on page 2-27](#).
- The method by which preprocessing tokens (possibly resulting from macro expansion) in a `#include` directive are combined into a header name (6.10.2).
All the tokens making up the header name (including white space) are treated as the file path used when searching for the header as described in [Section 2.14, “How to Specify Include Files” on page 2-27](#).
- The nesting limit for `#include` processing (6.10.2).
No limit is imposed by the compiler.
- Whether the `#` operator inserts a `\` character before the `\` character that begins a universal character name in a character constant or string literal (6.10.3.2).
No.
- The behavior on each recognized non-STDC `#pragma` directive (6.10.6).
See [Section 2.8, “Pragmas” on page 2-10](#) for a description of the behavior of each recognized non-STDC `#pragma` directive.
- The definitions for `__DATE__` and `__TIME__` when respectively, the date and time of translation are not available (6.10.8).
These macros are always available from the environment.

C.1.12 Library Functions (J.3.12)

- Any library facilities available to a freestanding program, other than the minimal set required by clause 4 (5.1.2.1).
The implementation is on a hosted environment.

- The format of the diagnostic printed by the assert macro (7.2.1.1).

The diagnostic is structured as follows:

Assertion failed: *statement*. file *filename*, line number, function name

statement is the statement which failed the assertion. *filename* is the value of `__FILE__`. *line number* is the value of `__LINE__`. *function name* is the value of `__func__`.

- The representation of the floating-point status flags stored by the `fegetexceptflag` function (7.6.2.2).

Each exception stored in the status flag by `fegetexceptflag` expands to an integer constant expression with values such that bitwise-inclusive ORs of all combinations of the constants result in distinct values.

- Whether the `feraiseexcept` function raises the “inexact” floating-point exception in addition to the “overflow” or “underflow” floating-point exception (7.6.2.3).

No, “inexact” is not raised.

- Strings other than “C” and “” that may be passed as the second argument to the `setlocale` function (7.11.1.1).

Intentionally left blank.

- The types defined for `float_t` and `double_t` when the value of the `FLT_EVAL_METHOD` macro is less than zero or greater than two (7.12).

- For SPARC, the types are as follows:

```
typedef float float_t;
typedef double double_t;
```

- For x86 the types are as follows:

```
typedef long double float_t;
typedef long double double_t;
```

- Domain errors for the mathematics functions, other than those required by this International Standard (7.12.1).

`ilogb()`, `ilogbf()` and `ilogbl()` raise the invalid exception if the input argument is 0, +/-Inf or NaN.

- The values returned by the mathematics functions on domain errors (7.12.1).

The values returned on domain errors in full C99 mode (`-xc99=%all,lib`), are as specified in Annex F of ISO/IEC 9899:1999, Programming Languages - C.

- The values returned by the mathematics functions on underflow range errors, whether `errno` is set to the value of the macro `ERANGE` when the integer expression `math_errhandling & MATH_ERRNO` is nonzero, and whether the “underflow” floating-point exception is raised when the integer expression `math_errhandling & MATH_ERREXCEPT` is nonzero. (7.12.1).

For underflow range errors: if the value can be represented as a subnormal number, the subnormal number is returned; otherwise `+0` is returned as appropriate.

As for whether `errno` is set to the value of the macro `ERANGE` when the integer expression `math_errhandling & MATH_ERRNO` is nonzero, since `(math_errhandling & MATH_ERRNO) == 0` in our implementation, this part does not apply.

Whether the “underflow” floating-point exception is raised when the integer expression `math_errhandling & MATH_ERREXCEPT` is nonzero (7.12.1), the exception is raised when a floating-point underflow is coupled with loss of accuracy.

- Whether a domain error occurs or zero is returned when an `fmod` function has a second argument of zero(7.12.10.1).

A domain error occurs.

- The base-2 logarithm of the modulus used by the `remquo` functions in reducing the quotient (7.12.10.3).

31.

- Whether the equivalent of `signal(sig, SIG_DFL)`; is executed prior to the call of a signal handler, and, if not, the blocking of signals that is performed (7.14.1.1).

The equivalent of `signal(sig, SIG_DFL)`; is executed prior to the call of a signal handler.

- The null pointer constant to which the macro `NULL` expands (7.17).

`NULL` expands to 0.

- Whether the last line of a text stream requires a terminating new-line character (7.19.2).

The last line does not need to end in a newline.

- Whether space characters that are written out to a text stream immediately before a new-line character appear when read in (7.19.2).

All characters appear when the stream is read.

- The number of null characters that may be appended to data written to a binary stream (7.19.2).

No null characters are appended to a binary stream.

- Whether the file position indicator of an append-mode stream is initially positioned at the beginning or end of the file (7.19.3).
The file position indicator is initially positioned at the end of the file.
- Whether a write on a text stream causes the associated file to be truncated beyond that point (7.19.3).
A write on a text stream does not cause a file to be truncated beyond that point unless a hardware device forces it to happen.
- The characteristics of file buffering (7.19.3).
Output streams, with the exception of the standard error stream (`stderr`), are by default-buffered if the output refers to a file, and line-buffered if the output refers to a terminal. The standard error output stream (`stderr`) is by default unbuffered.
A buffered output stream saves many characters, and then writes the characters as a block. An unbuffered output stream queues information for immediate writing on the destination file or terminal immediately. Line-buffered output queues each line of output until the line is complete (a newline character is requested).
- Whether a zero-length file actually exists (7.19.3).
A zero-length file does exist since it has a directory entry.
- The rules for composing valid file names (7.19.3).
A valid file name can be from 1 to 1,023 characters in length and can use all character except the characters null and / (slash).
- Whether the same file can be simultaneously open multiple times (7.19.3).
The same file can be opened multiple times.
- The nature and choice of encodings used for multibyte characters in files (7.19.3).
The encodings used for multibyte characters are the same for each file.
- The effect of the `remove` function on an open file (7.19.4.1).
The file is deleted on the last call which closes the file. A program cannot open a file which has already been removed.
- The effect if a file with the new name exists prior to a call to the `rename` function (7.19.4.2).
If the file exists, it is removed and the new file is written over the previously existing file.
- Whether an open temporary file is removed upon abnormal program termination (7.19.4.3).
If the process is killed in the period between file creation and unlinking, a permanent file may be left behind. See the `freopen(3C)` man page.

- Which changes of mode are permitted (if any), and under what circumstances (7.19.5.4).

The following changes of mode are permitted, depending upon the access mode of the file descriptor underlying the stream:

- When + is specified, the file descriptor mode must be `O_RDWR`.
- When `r` is specified, the file descriptor mode must be `O_RDONLY` or `O_RDWR`.
- When `a` or `w` is specified, the file descriptor mode must be `O_WRONLY` or `O_RDWR`.

See the `freopen(3C)` man page.

- The style used to print an infinity or NaN, and the meaning of any `n-char` or `n-wchar` sequence printed for a NaN (7.19.6.1, 7.24.2.1).

`[-]Inf`, `[-]NaN`. With `F` conversion specifier, `[-]INF`, `[-]NAN`.

- The output for `%p` conversion in the `fprintf` or `fwprintf` function (7.19.6.1, 7.24.2.1).

The output for `%p` is equivalent to `%x`.

- The interpretation of a - character that is neither the first nor the last character, nor the second where a ^ character is the first, in the scanlist for `%[` conversion in the `fscanf()` or `fwscanf()` function (7.19.6.2, 7.24.2.1).

If a - is in the scanlist and is not the first character, nor the second where the first character is a ^, nor the last character, it indicates a range of characters to be matched.

See the `fscanf(3C)` man page.

- The set of sequences matched by a `%p` conversion and the interpretation of the corresponding input item in the `fscanf()` or `fwscanf()` function (7.19.6.2, 7.24.2.2).

Matches the set of sequences that is the same as the set of sequences that is produced by the `%p` conversion of the corresponding `printf(3C)` functions. The corresponding argument must be a pointer to a pointer to void. If the input item is a value converted earlier during the same program execution, the pointer that results will compare equal to that value; otherwise the behavior of the `%p` conversion is undefined.

See the `fscanf(3C)` man page.

- The value to which the macro `errno` is set by the `fgetpos`, `fsetpos`, or `ftell` functions on failure (7.19.9.1, 7.19.9.3, 7.19.9.4).
 - `EBADF` The file descriptor underlying stream is not valid. See the `fgetpos(3C)` man page.
 - `ESPIPE` The file descriptor underlying stream is associated with a pipe, a FIFO, or a socket. See the `fgetpos(3C)` man page.

- EOVERFLOW The current value of the file position cannot be represented correctly in an object of type `fpos_t`. See the `fgetpos(3C)` man page.
- EBADF The file descriptor underlying stream is not valid. See the `fsetpos(3C)` man page.
- ESPIPE The file descriptor underlying stream is associated with a pipe, a FIFO, or a socket. See the `fsetpos(3C)` man page.
- EBADF The file descriptor underlying stream is not an open file descriptor. See the `ftell(3C)` man page.
- ESPIPE The file descriptor underlying stream is associated with a pipe, a FIFO, or a socket. See the `ftell(3C)` man page.
- EOVERFLOW The current file offset cannot be represented correctly in an object of type `long`. See the `ftell(3C)` man page.
- The meaning of any `n-char` or `n-wchar` sequence in a string representing a NaN that is converted by the `strtod()`, `strtof()`, `strtold()`, `wcstod()`, `wcstof()`, or `wcstold()` function (7.20.1.3, 7.24.4.1.1).

No special meaning is given to the `n-char` sequence.

- Whether or not the `strtod`, `strtof`, `strtold`, `wcstod`, `wcstof`, or `wcstold` function sets `errno` to `ERANGE` when underflow occurs (7.20.1.3, 7.24.4.1.1).

Yes, `errno` is set to `ERANGE` on underflow.

- Whether the `calloc`, `malloc`, and `realloc` functions return a null pointer or a pointer to an allocated object when the size requested is zero (7.20.3).

Either a null pointer or a unique pointer that can be passed to `free()` is returned.

See the `malloc(3C)` man page.

- Whether open streams with unwritten buffered data are flushed, open streams are closed, or temporary files are removed when the `abort` or `_Exit` function is called (7.20.4.1, 7.20.4.4).

The abnormal termination processing includes at least the effect of `fclose(3C)` on all open streams. See the `abort(3C)` man page.

Open streams are closed and do not flush open streams. See the `_Exit(2)` man page.

- The termination status returned to the host environment by the `abort`, `exit`, or `_Exit` function (7.20.4.1, 7.20.4.3, 7.20.4.4).

The status made available to `wait(3C)` or `waitpid(3C)` by `abort` will be that of a process terminated by the `SIGABRT` signal. See the `abort(3C)`, `exit(1)`, and `_Exit(2)` man pages.

The termination status returned by `exit`, or `_Exit`, depends on the what the parent process of the calling process is doing.

If the parent process of the calling process is executing a `wait(3C)`, `wait3(3C)`, `waitid(2)`, or `waitpid(3C)`, and has neither set its `SA_NOCLDWAIT` flag nor set `SIGCHLD` to `SIG_IGN`, it is notified of the calling process's termination and the low-order eight bits (that is, bits 0377) of status are made available to it. If the parent is not waiting, the child's status is made available to it when the parent subsequently executes `wait()`, `wait3()`, `waitid()`, or `waitpid()`.

- The value returned by the `system` function when its argument is not a null pointer (7.20.4.6).

The exit status of the shell in the format specified by `waitpid(3C)`.
- The local time zone and Daylight Saving Time (7.23.1).

The local time zone is set by the environment variable `TZ`.
- The range and precision of times representable in `clock_t` and `time_t` (7.23).

The precision of `clock_t` and `time_t` is one millionth of a second. The range is -2147483647-1 to 4294967295 millionths of a second on x86 and sparc v8. And -9223372036854775807LL-1 to 18446744073709551615 on SPARC v9.
- The era for the `clock` function (7.23.2.1).

The era for the clock is represented as clock ticks with the origin at the beginning of the execution of the program.
- The replacement string for the `%Z` specifier to the `strftime`, and `wcsftime` functions in the "C" locale (7.23.3.5, 7.24.5.1).

The time zone name or abbreviation, or by no characters if no time zone is determinable.
- Whether or when the trigonometric, hyperbolic, base-e exponential, base-e logarithmic, error, and log gamma functions raise the "inexact" floating-point exception in an IEC 60559 conformant implementation (F.9).

The inexact exception is generally raised when the result is not exactly representable. The inexact exception can be raised even when the result is exactly representable.
- Whether the functions in `<math.h>` honor the rounding direction mode in an IEC 60559 conformant implementation (F.9).

No attempt is made to force the default rounding direction mode for all functions in `<math.h>`.

C.1.13 Architecture (J.3.13)

- The values or expressions assigned to the macros specified in the headers `<float.h>`, `<limits.h>`, and `<stdint.h>` (5.2.4.2, 7.18.2, 7.18.3).
 - Here are the values or expressions for the macros specified in `<float.h>`:

```

#define CHAR_BIT 8 /* max # of bits in a "char" */
#define SCHAR_MIN (-128) /* min value of a "signed char" */
#define SCHAR_MAX 127 /* max value of a "signed char" */
#define CHAR_MIN SCHAR_MIN /* min value of a "char" */
#define CHAR_MAX SCHAR_MAX /* max value of a "char" */
#define MB_LEN_MAX 5
#define SHRT_MIN (-32768) /* min value of a "short int" */
#define SHRT_MAX 32767 /* max value of a "short int" */
#define USHRT_MAX 65535 /* max value of "unsigned short int" */
#define INT_MIN (-2147483647-1) /* min value of an "int" */
#define INT_MAX 2147483647 /* max value of an "int" */
#define UINT_MAX 4294967295U /* max value of an "unsigned int" */
#define LONG_MIN (-2147483647L-1L)
#define LONG_MAX 2147483647L /* max value of a "long int" */
#define ULONG_MAX 4294967295UL /* max value of "unsigned long int" */
#define LLONG_MIN (-9223372036854775807LL-1LL)
#define LLONG_MAX 9223372036854775807LL
#define ULLONG_MAX 18446744073709551615ULL

#define FLT_RADIX 2
#define FLT_MANT_DIG 24
#define DBL_MANT_DIG 53
#define LDBL_MANT_DIG 64

#if defined(__sparc)
#define DECIMAL_DIG 36
#elif defined(__i386)
#define DECIMAL_DIG 21
#endif
#define FLT_DIG 6
#define DBL_DIG 15
#if defined(__sparc)
#define LDBL_DIG 33
#elif defined(__i386)
#define LDBL_DIG 18
#endif

```

```

#define FLT_MIN_EXP (-125)
#define DBL_MIN_EXP (-1021)
#define LDBL_MIN_EXP (-16381)

#define FLT_MIN_10_EXP (-37)
#define DBL_MIN_10_EXP (-307)
#define LDBL_MIN_10_EXP (-4931)

#define FLT_MAX_EXP (+128)
#define DBL_MAX_EXP (+1024)
#define LDBL_MAX_EXP (+16384)

#define FLT_EPSILON 1.192092896E-07F
#define DBL_EPSILON 2.2204460492503131E-16

#if defined(__sparc)
#define LDBL_EPSILON 1.925929944387235853055977942584927319E-34L
#elif defined(__i386)
#define LDBL_EPSILON 1.0842021724855044340075E-19L
#endif

#define FLT_MIN 1.175494351E-38F
#define DBL_MIN 2.2250738585072014E-308

#if defined(__sparc)
#define LDBL_MIN 3.362103143112093506262677817321752603E-4932L
#elif defined(__i386)
#define LDBL_MIN 3.3621031431120935062627E-4932L
#endif

```

■ Here are the values or expressions for the macros specified in <limits.h>:

```

#define INT8_MAX (127)
#define INT16_MAX (32767)
#define INT32_MAX (2147483647)
#define INT64_MAX (9223372036854775807LL)

```

```

#define INT8_MIN (-128)
#define INT16_MIN (-32767-1)
#define INT32_MIN (-2147483647-1)
#define INT64_MIN (-9223372036854775807LL-1)

#define UINT8_MAX (255U)
#define UINT16_MAX (65535U)
#define UINT32_MAX (4294967295U)
#define UINT64_MAX (18446744073709551615ULL)

#define INT_LEAST8_MIN INT8_MIN
#define INT_LEAST16_MIN INT16_MIN
#define INT_LEAST32_MIN INT32_MIN
#define INT_LEAST64_MIN INT64_MIN

#define INT_LEAST8_MAX INT8_MAX
#define INT_LEAST16_MAX INT16_MAX
#define INT_LEAST32_MAX INT32_MAX
#define INT_LEAST64_MAX INT64_MAX

#define UINT_LEAST8_MAX UINT8_MAX
#define UINT_LEAST16_MAX UINT16_MAX
#define UINT_LEAST32_MAX UINT32_MAX
#define UINT_LEAST64_MAX UINT64_MAX

```

■ Here are the values or expressions for the macros specified in `<stdint.h>`:

```

#define INT_FAST8_MIN INT8_MIN
#define INT_FAST16_MIN INT16_MIN
#define INT_FAST32_MIN INT32_MIN
#define INT_FAST64_MIN INT64_MIN

#define INT_FAST8_MAX INT8_MAX
#define INT_FAST16_MAX INT16_MAX
#define INT_FAST32_MAX INT32_MAX
#define INT_FAST64_MAX INT64_MAX

```

```
#define UINT_FAST8_MAX  UINT8_MAX
#define UINT_FAST16_MAX  UINT16_MAX
#define UINT_FAST32_MAX  UINT32_MAX
#define UINT_FAST64_MAX  UINT64_MAX
```

- The number, order, and encoding of bytes in any object (when not explicitly specified in this International Standard) (6.2.6.1).

The implementation-defined number, order, and encodings of objects not explicitly specified in the 1999 C standard have been defined elsewhere in this chapter.

- The value of the result of the `sizeof` operator (6.5.3.4).

The following table lists the results for `sizeof`.

TABLE C-4 Results From the `sizeof` Operator in Bytes

Type	Size in Bytes
char	1
short	2
int	4
long	4
long v9	8
long long	8
float	4
double	8
long double (SPARC)	16
long double (x86)	12
pointer	4
pointer v9	8
_Complex float	8
_Complex double	16
_Complex long double	32
_Imaginary float	4
_Imaginary double	8
_Imaginary long double (SPARC)	16
_Imaginary long double (x86)	12

C.1.14 Locale-specific Behavior (J.4)

The following characteristics of a hosted environment are locale-specific and are required to be documented by the implementation:

- Additional members of the source and execution character sets beyond the basic character set (5.2.1).

Locale-specific (no extension in C locale).

- The presence, meaning, and representation of additional multibyte characters in the execution character set beyond the basic character set (5.2.1.2).

There are no multibyte characters present in the execution characters set in the default or C locales.

- The shift states used for the encoding of multibyte characters (5.2.1.2).

There are no shift states.

- The direction of writing of successive printing characters (5.2.2).

Printing is always left to right.

- The decimal-point character (7.1.1).

Locale-specific (“.” in C locale).

- The set of printing characters (7.4, 7.25.2).

Locale-specific (“.” in C locale).

- The set of control characters (7.4, 7.25.2).

The control character set is comprised of horizontal tab, vertical tab, form feed, alert, backspace, carriage return, and new line.

- The sets of characters tested for by the `isalpha`, `isblank`, `islower`, `ispunct`, `isspace`, `isupper`, `iswalpha`, `iswblank`, `iswlower`, `iswpunct`, `iswspace`, or `iswupper` functions (7.4.1.2, 7.4.1.3, 7.4.1.7, 7.4.1.9, 7.4.1.10, 7.4.1.11, 7.25.2.1.2, 7.25.2.1.3, 7.25.2.1.7, 7.25.2.1.9, 7.25.2.1.10, 7.25.2.1.11).

See the `isalpha(3C)` and `iswalpha(3C)` man pages for descriptions of `isalpha()` and `iswalpha()` as well as information on the related macros mentioned above. Note that their behaviors can be modified by changing locale.

- The native environment (7.11.1.1).

The native environment is specified by the `LANG` and `LC_*` environment variables as described in the `setlocale(3C)` man page. However, if these environment variables are not set, the native environment is set to the C locale.

- Additional subject sequences accepted by the numeric conversion functions (7.20.1, 7.24.4.1).

The radix character is defined in the program’s locale (category `LC_NUMERIC`), and may be defined as something other than a period (.).

- The collation sequence of the execution character set (7.21.4.3, 7.24.4.4.2).
Locale-specific (ASCII collation in C locale).
- The contents of the error message strings set up by the `strerror` function (7.21.6.2).
If the application is linked with `-lintl`, then messages returned by this function are in the native language specified by the `LC_MESSAGES` locale category. Otherwise they are in the C locale.
- The formats for time and date (7.23.3.5, 7.24.5.1).
Locale-specific. Formats for the C locale are shown in the tables below.
The names of the months are specified below:

TABLE C-5 The Names of the Months

January	May	September
February	June	October
March	July	November
April	August	December

The names of the days of the week are specified below:

TABLE C-6 Days and Abbreviated Days of the Week

Days	Abbreviated Days
Sunday Thursday	Sun Thu
Monday Friday	Mon Fri
Tuesday Saturday	Tue Sat
Wednesday	Wed

The format for time is:

`%H:%M:%S`

The format for date is:

`%m/%d/ -Xc mode.`

The formats for AM and PM designation are: AM PM

- Character mappings that are supported by the `towctrans` function (7.25.1).
The rules of the coded character set defined by character mapping information in the program's locale (category `LC_CTYPE`) may provide for character mappings other than `tolower` and `toupper`. Refer to the *Solaris Internationalization Guide For Developers*, for details of available locales and their definitions.

- Character classifications that are supported by the `iswctype` function (7.25.1).
See the *Solaris Internationalization Guide For Developers*, for details of available locales and any non-standard reserved character classifications.

Supported Features of C99

This appendix lists the supported features of the ISO/IEC 9899:1999, Programming Language - C standard.

The `-xc99` flag controls compiler recognition of the implemented features. For more information on the syntax of `-xc99`, see [Section B.2.71, “-xc99\[=o\]”](#) on page B-38.

Note – Though the compiler defaults to supporting the features of C99 listed below, standard headers provided by the Solaris software in `/usr/include` do not yet conform with the 1999 ISO/IEC C standard. If error messages are encountered, try using `-xc99=none` to obtain the 1990 ISO/IEC C standard behavior for these headers.

D.1 Discussion and Examples

This appendix provides discussions and examples for some of the following supported features:

- Sub-clause 5.2.4.2.2 Characteristics of floating types `<float.h>`
- Sub-clause 6.2.5 `_Bool`
- Sub-clause 6.2.5 `_Complex` type

The Solaris 8 and Solaris 9 operating systems provide a partial implementation of `_Complex` data types. `_Complex` data are fully supported beginning in the Solaris 10 software. Do not use `-lcplxsupp` on the Solaris 10 OS.

- Sub-clause 6.3.2.1 Conversion of arrays to pointers not limited to lvalues
- Sub-clause 6.4.1 Keywords
- Sub-clause 6.4.2.2 Predefined identifiers
- 6.4.3 Universal character names
- Sub-clause 6.4.4.2 Hexadecimal floating-point literals

- Sub-clause 6.4.9 Comments
- Sub-clause 6.5.2.2 Function calls
- Sub-clause 6.5.2.5 Compound literals
- Sub-clause 6.7.2 Type specifiers
- Sub-clause 6.7.2.1 Structure and union specifiers
- Sub-clause 6.7.3 Type Qualifier
- Sub-clause 6.7.4 Function specifiers
- Sub-clause 6.7.5.2 Array declarator
- Sub-clause 6.7.8 Initialization
- Sub-clause 6.8.2 Compound statement
- Sub-clause 6.8.5 Iteration statements
- Sub-clause 6.10.3 Macro replacement
- Sub-clause 6.10.6 STDC pragmas
- Sub-clause 6.10.8 `__STDC_IEC_559` and `__STDC_IEC_559_COMPLEX` macros
- Sub-clause 6.10.9 Pragma operator

D.1.1 Precision of Floating Point Evaluators

5.2.4.2.2 Characteristics of floating types `<float.h>`

The values of operations with floating operands, and the values that are subject to both the usual arithmetic conversions and to floating constants are evaluated to a format whose range and precision may be greater than required by the type. The use of evaluation formats is characterized by the implementation-defined value of `FLT_EVAL_METHOD`:

TABLE D-1 The `FLT_EVAL_METHOD` Values

Value	Meaning
-1	Indeterminable.
0	The compiler evaluates all operations and constants just to the range and precision of the type.
1	The compiler evaluates operations and constants of type <code>float</code> and <code>double</code> to the range and precision of a <code>double</code> . Evaluate long double operations and constants to the range and precision of a long double.
2	The compiler evaluates all operations and constants to the range and precision of a long double.

When you include `float.h` on SPARC architectures, `FLT_EVAL_METHOD` expands to 0 by default and all floating point expressions are evaluated according to their type.

When you include `float.h` on x86 architectures, `FLT_EVAL_METHOD` expands to `-1` by default (except when `-xarch=sse2` or `-xarch=amd64`), and all floating point constant expressions are evaluated according to their type and all other floating point expressions are evaluated as long double.

When you specify `-flt_eval=2` and include `float.h`, `FLT_EVAL_METHOD` expands to `2` and all floating expressions are evaluated as long double. See [Section B.2.20, “-flt_eval\[={any|2}\]” on page B-11](#) for more information.

When you specify `-xarch=sse2` or `-xarch=amd64` on x86, and include `float.h`, `FLT_EVAL_METHOD` expands to `0` and all floating point expressions are evaluated according to their type.

The `-xt` option does not affect the expansion of `FLT_EVAL_METHOD`, even though float expressions are evaluated as double. See [Section B.2.61, “-x\[claltls\]” on page B-25](#) for more information.

The `-fsingle` option causes float expressions to be evaluated with single precision. See [Section B.2.26, “-fsingle” on page B-15](#) for more information.

When you specify `-fprecision` on x86 architectures with `-xarch=sse2` or `-xarch=amd64` and include `float.h`, `FLT_EVAL_METHOD` expands to `-1`.

D.1.2 C99 Keywords

6.4.1 Keywords

The C99 standard introduces the following new keywords. The compiler issues a warning if you use these keywords as identifiers while compiling with `-xc99=none`. Without `-xc99=none` the compiler issues a warning or error messages for use of these keywords as identifiers depending on the context.

- `inline`
- `_Imaginary`
- `_Complex`
- `_Bool`
- `restrict`

D.1.2.1 Using the `restrict` Keyword

An object that is accessed through a `restrict` qualified pointer requires that all accesses to that object use, directly or indirectly, the value of that particular `restrict` qualified pointer. Any access to the object through any other means may result in undefined behavior. The intended use of the `restrict` qualifier is to allow the compiler to make assumptions that promote optimizations.

See [Section 3.8.2, “Restricted Pointers”](#) on page 3-21 for examples and an explanation on how to use the `restrict` qualifier effectively.

D.1.3 `__func__` Support

6.4.2.2 Predefined identifiers

The compiler provides support for the predefined identifier `__func__`. `__func__` is defined as an array of chars which contains the name of the current function in which `__func__` appears.

D.1.4 Universal Character Names (UCN)

6.4.3 Universal character names

UCN allows the use of any character in a C source, not just English characters. A UCN has the format:

- `\u 4_hex_digits_value`
- `\U 8_hex_digits_value`

A UCN must not specify a value less than 00A0 other than 0024 (\$), 0040 (@), or 0060 (?), nor a value in the range D800 through DFFF inclusive.

UCN may be used in identifiers, character constants, and string literals to designate characters that are not in the C basic character set.

The UCN `\unnnnnnnn` designates the character whose eight-digit short identifier (as specified by ISO/IEC 10646) is `nnnnnnnn`. Similarly, the universal character name `~nnnn` designates the character whose four-digit short identifier is `nnnn` (and whose eight-digit short identifier is `0000nnnn`).

D.1.5 Commenting Code With `//`

6.4.9 Comments

The characters `//` introduce a comment that includes all multibyte characters up to, but not including, the next new-line character except when the `//` characters appear within a character constant, a string literal, or a comment.

D.1.6 Disallowed Implicit `int` and Implicit Function Declarations

6.5.2.2 Function calls

Implicit declarations are no longer allowed in the 1999 C standard as they were in the 1990 C standard. Previous versions of the C compiler issued warning messages about implicit definitions only with `-v` (verbose). These messages and new additional warnings about implicit definitions, are now issued whenever identifiers are implicitly defined as `int` or functions.

This change is very likely to be noticed by nearly all users of this compiler because it can lead to a large number of warning messages. Common causes include a failure to include the appropriate system header files that declare functions being used, like `printf` which needs `<stdio.h>` included. The 1990 C standard behavior of accepting implicit declarations silently can be restored using `-xc99=none`.

The C compiler now generates a warning for an implicit function declaration:

```
example% cat test.c
void main()
{
    printf("Hello, world!\n");
}
example% cc test.c
"test.c", line 3: warning: implicit function declaration: printf
example%
```

D.1.7 Declarations Using Implicit `int`

6.7.2 Type specifiers:

At least one type specifier shall be given in the declaration specifiers in each declaration. See also [Section D.1.6, "Disallowed Implicit `int` and Implicit Function Declarations"](#) on page D-5.

The C compiler now issues warnings on any implicit int declaration as in the following example:

```
example% more test.c
volatile i;
const foo()
{
    return i;
}
example% cc test.c
"test.c", line 1: warning: no explicit type given
"test.c", line 3: warning: no explicit type given
example%
```

D.1.8 Flexible Array Members

6.7.2.1 Structure and union specifiers

Also known as the “struct hack”. Allows the last member of a struct to be an array of zero length, such as `int foo[]`; Such a struct is commonly used as the header to access malloced memory.

For example, in this structure, `struct s { int n; double d[]; } S;`, the array, `d`, is an incomplete array type. The C compiler does not count any memory offset for this member of `S`. In other words, `sizeof(struct s)` is the same as the offset of `S.n`.

`d` can be used like any, ordinary, array-member. `S.d[10] = 0;`

Without the C compiler’s support for an incomplete array type, you would define and declare a structure as the following example, called `DynamicDouble`, shows:

```
typedef struct { int n; double d[1]; } DynamicDouble;
```

Note that the array `d` is not an incomplete array type and is declared with one member.

Next, you declare a pointer `dd` and allocate memory thus:

```
DynamicDouble *dd =
malloc(sizeof(DynamicDouble)+(actual_size-1)*sizeof(double));
```


You then store the size of the offset in `S.n` thus:

```
dd->n = actual_size;
```

Because the compiler supports incomplete array types, you can achieve the same result without declaring the array with one member:

```
typedef struct { int n; double d[]; } DynamicDouble;
```

You now declare a pointer `dd` and allocate memory as before, except that it is no longer necessary to subtract one from `actual_size`:

```
DynamicDouble *dd = malloc (sizeof(DynamicDouble) +  
(actual_size)*sizeof(double));
```

The offset is stored, as before, in `S.n` thus:

```
dd->n = actual_size;
```

D.1.9 Idempotent Qualifiers

6.7.3 Type qualifiers:

If the same qualifier appears more than once in the same specifier-qualifier-list, either directly or through one or more typedefs, the behavior is the same as when the type qualifier appears only once.

In C90, the following code would cause an error:

```
%example cat test.c  
  
const const int a;  
  
int main(void) {  
    return(0);  
}  
  
%example cc -xc99=none test.c  
"test.c", line 1: invalid type combination
```

However, with C99, the C compiler accepts multiple qualifiers.

```
%example cc -xc99 test.c
%example
```

D.1.10 inline Functions

6.7.4 Function specifiers

The C99 function-specifier `inline` has been added. `inline` is fully functional for functions with both internal and external linkage. Inline function definitions and extern inline functions now work as specified by the 1999 C ISO standard.

An inline function definition is a function defined with the keyword `inline`, and without either the keywords `static` or `extern`, and all prototypes appearing within the source (or included files) also contain the keyword `inline` without either the keywords `static` or `extern`.

An inline function definition does not provide an external definition for the function. Any function call appearing in the source file containing an inline definition will either be satisfied by inlining the function definition at the call site, or by a reference to an externally defined function.

The compiler will inline calls to inline definitions only when optimizing and only when the compiler optimizer believes it is profitable to do so. Otherwise a call to an external function will be made. Therefore any program containing inline definitions should link with an object file containing an extern function definition.

Use of both the keywords `extern` and `inline` with a function definition (or on any prototype in the file continuing the function definition) will result in an external function being defined in that object file. To be compatible with C++ linking with objects that contain multiple definitions of extern inline functions will result in the linker choosing just one of these functions to satisfy any external references.

To get standard conforming behavior, old code must be recompiled using the current compiler. However, if you have instances of extern inline function definitions in old C and C++ binaries (pre C/C++ 5.6) and you wish to link those binaries with new C and C++ binaries without changing the behavior of the old binaries, specify `-features=no%extinl`.

D.1.11 Static and Other Type Qualifiers Allowed in Array Declarators

6.7.5.2 Array declarator:

The keyword `static` can now appear in the Array declarator of a parameter in a function declarator to indicate that the compiler can assume at least that many elements will be passed to the function being declared. Allows the optimizer to make assumptions about which it otherwise could not determine.

The C compiler adjusts array parameters into pointers therefore `void foo(int a[])` is the same as `void foo(int *a)`.

If you specify type qualifiers such as `void foo(int * restrict a);`, the C compiler expresses it with array syntax `void foo(int a[restrict]);` which is essentially the same as declaring a restricted pointer.

The C compiler also uses a `static` qualifier to preserve information about the array size. For example, if you specify `void foo(int a[10])` the compiler still expresses it as `void foo(int *a)`. Use a `static` qualifier as follows, `void foo(int a[static 10])`, to let the compiler know that pointer `a` is not NULL and that it provides access to an integer array of at least ten elements.

D.1.12 Variable Length Arrays (VLA):

6.7.5.2 Array declarators

VLAs are allocated on the stack as if by calling the `alloca` function. Their lifetime, regardless of their scope, is the same as any data allocated on the stack by calling `alloca`; until the function returns. The space allocated is freed when the stack is released upon returning from the function in which the VLA is allocated.

Not all constraints are yet enforced for variable length arrays. Constraint violations lead to undefined results.

```
#include <stdio.h>
void foo(int);

int main(void) {
    foo(4);
    return(0);
}

void foo (int n) {
    int i;
    int a[n];
    for (i = 0; i < n; i++)
        a[i] = n-i;
    for (i = n-1; i >= 0; i--)
        printf("a[%d] = %d\n", i, a[i]);
}

example% cc test.c
example% a.out
a[3] = 1
a[2] = 2
a[1] = 3
a[0] = 4
```

D.1.13 Designated Initializers

6.7.8 Initialization

Designated initializers provide a mechanism for initializing sparse arrays, a practice common in numerical programming.

Designated initializers allows initialization of sparse structures, common in systems programming, and allows initialization of unions via any member, regardless of whether or not it is the first member.

Consider these examples. This first example shows how designated initializers are used to initialize an array:

```
enum { first, second, third };
const char *nm[] = {
    [third] = "third member",
    [first] = "first member",
    [second] = "second member",
};
```

The following example demonstrates how designated initializers are used to initialize the fields of a struct object:

```
division_t result = { .quot = 2, .rem = -1 };
```

The following example shows how designated initializers can be used to initialize complicated structures that might otherwise be misunderstood:

```
struct { int z[3], count; } w[] = { [0].z = {1}, [1].z[0] = 2 };
```

An array can be created from both ends by using a single designator:

```
int z[MAX] = {1, 3, 5, 7, 9, [MAX-5] = 8, 6, 4, 2, 0};
```

If *MAX* is greater than ten, the array will contain zero-valued elements in the middle; if *MAX* is less than ten, some of the values provided by the first five initializers will be overridden by the second five.

Any member of a union can be initialized:

```
union { int i; float f;} data = { .f = 3.2 };
```

D.1.14 Mixed Declarations and Code

6.8.2 Compound statement

The C compiler now accepts mixing type declarations with executable code as shown by the following example:

```
#include <stdio.h>

int main(void){
    int num1 = 3;
    printf("%d\n", num1);

    int num2 = 10;
    printf("%d\n", num2);
    return(0);
}
```

D.1.15 Declaration in for-Loop Statement

6.8.5 Iteration statements

The C compiler now accepts a type declaration as the first expression in a for loop-statement:

```
for (int i=0; i<10; i++){ //loop body };
```

The scope of any variable declared in the initialization statement of the for loop is the entire loop (including controlling and iteration expressions).

D.1.16 Macros With a Variable Number of Arguments

6.10.3 Macro replacement

The C compiler accepts #define preprocessor directives of the following form:

```
#define identifier (...) replacement_list
#define identifier (identifier_list, ...) replacement_list
```

If the *identifier_list* in the macro definition ends with an ellipsis, it means that there will be more arguments in the invocation than there are parameters in the macro definition, excluding the ellipsis. Otherwise, the number of parameters in the macro definition, including those arguments which consist of no preprocessing tokens, matches the number of arguments. Use the identifier `__VA_ARGS__` in the

replacement list of a #define preprocessing directive which uses the ellipsis notation in its arguments. The following example demonstrates the variable argument list macro facilities.

```
#define debug(...) fprintf(stderr, __VA_ARGS__)
#define showlist(...) puts(__VA_ARGS__)
#define report(test, ...) ((test)?puts(#test):\
    printf(__VA_ARGS__))
debug("Flag");
debug("X = %d\n",x);
showlist(The first, second, and third items.);
report(x>y, "x is %d but y is %d", x, y);
```

which results in the following:

```
fprintf(stderr, "Flag");
fprintf(stderr, "X = %d\n", x);
puts("The first, second, and third items.");
((x>y)?puts("x>y"):printf("x is %d but y is %d", x, y));
```

D.1.17 _Pragma

6.10.9 Pragma operator

A unary operator expression of the form: `_Pragma (string-literal)` is processed as follows:

- The L prefix of the string literal is deleted, if it is present.
- The leading and trailing double-quotes are deleted.
- Each escape sequence ' is replaced by a double-quote.
- Each escape sequence \\ is replaced by a single backslash.

The resulting sequence of preprocessing tokens are processed as if they were the preprocessor tokens in a pragma directive.

The original four preprocessing tokens in the unary operator expression are removed.

`_Pragma` offers an advantage over `#pragma` in that `_Pragma` can be used in a macro definition.

`_Pragma("string")` behaves exactly the same as `#pragma string`. Consider the following example. First, the example's source code is listed and then the example's source is listed after the preprocessor has made it's pass.

```
example% cat test.c

#include <omp.h>
#include <stdio.h>

#define Pragma(x) _Pragma(#x)
#define OMP(directive) Pragma(omp directive)

void main()
{
    omp_set_dynamic(0);
    omp_set_num_threads(2);
    OMP(parallel)
    {
        printf("Hello!\n");
    }
}

example% cc test.c -P -xopenmp -x03
example% cat test.i
```

Here's the source after the preprocessor has finished.

```
void main()
{
    omp_set_dynamic(0);
    omp_set_num_threads(2);
    # pragma omp parallel
    {
        printf("Hello!\n");
    }
}

example% cc test.c -xopenmp -->
example% ./a.out
Hello!
Hello!
example%
```


Implementation-Defined ISO/IEC C90 Behavior

The ISO/IEC 9899:1990, Programming Languages - C standard specifies the form and establishes the interpretation of programs written in C. However, this standard leaves a number of issues as implementation-defined, that is, as varying from compiler to compiler. This chapter details these areas. They can be readily compared to the ISO/IEC 9899:1990 standard itself:

- Each item uses the same section text as found in the ISO standard.
- Each item is preceded by its corresponding section number in the ISO standard.

E.1 Implementation Compared to the ISO Standard

E.1.1 Translation (G.3.1)

The numbers in parentheses correspond to section numbers in the ISO/IEC 9899:1990 standard.

(5.1.1.3) Identification of diagnostics:

Error messages have the following format:

filename, line line number: message

Warning messages have the following format:

filename, line line number: warning message

Where:

- *filename* is the name of the file containing the error or warning
- *line number* is the number of the line on which the error or warning is found
- *message* is the diagnostic message

E.1.2 Environment (G.3.2)

(5.1.2.2.1) *Semantics of arguments to main:*

```
int main (int argc, char *argv[])
{
    ....
}
```

`argc` is the number of command-line arguments with which the program is invoked with. After any shell expansion, `argc` is always equal to at least 1, the name of the program.

`argv` is an array of pointers to the command-line arguments.

(5.1.2.3) *What constitutes an interactive device:*

An interactive device is one for which the system library call `isatty()` returns a nonzero value.

E.1.3 Identifiers (G.3.3)

(6.1.2) *The number of significant initial characters (beyond 31) in an identifier without external linkage:*

The first 1,023 characters are significant. Identifiers are case-sensitive.

(6.1.2) *The number of significant initial characters (beyond 6) in an identifier with external linkage:*

The first 1,023 characters are significant. Identifiers are case-sensitive.

E.1.4 Characters (G.3.4)

(5.2.1) The members of the source and execution character sets, except as explicitly specified in the Standard:

Both sets are identical to the ASCII character sets, plus locale-specific extensions.

(5.2.1.2) The shift states used for the encoding of multibyte characters:

There are no shift states.

(5.2.4.2.1) The number of bits in a character in the execution character set:

There are 8 bits in a character for the ASCII portion; locale-specific multiple of 8 bits for locale-specific extended portion.

(6.1.3.4) The mapping of members of the source character set (in character and string literals) to members of the execution character set:

Mapping is identical between source and execution characters.

(6.1.3.4) The value of an integer character constant that contains a character or escape sequence not represented in the basic execution character set or the extended character set for a wide character constant:

It is the numerical value of the rightmost character. For example, `'\a'` equals `'a'`. A warning is emitted if such an escape sequence occurs.

(3.1.3.4) The value of an integer character constant that contains more than one character or a wide character constant that contains more than one multibyte character:

A multiple-character constant that is not an escape sequence has a value derived from the numeric values of each character.

(6.1.3.4) *The current locale used to convert multibyte characters into corresponding wide characters (codes) for a wide character constant:*

The valid locale specified by LC_ALL, LC_CTYPE, or LANG environment variable.

(6.2.1.1) *Whether a plain char has the same range of values as signed char or unsigned char:*

A char is treated as a signed char (SPARC) (x86).

E.1.5 Integers (G.3.5)

(6.1.2.5) *The representations and sets of values of the various types of integers:*

TABLE E-1 Representations and Sets of Values of Integers

Integer	Bits	Minimum	Maximum
char (SPARC) (x86)	8	-128	127
signed char	8	-128	127
unsigned char	8	0	255
short	16	-32768	32767
signed short	16	-32768	32767
unsigned short	16	0	65535
int	32	-2147483648	2147483647
signed int	32	-2147483648	2147483647
unsigned int	32	0	4294967295
long (SPARC) v8	32	-2147483648	2147483647
long (SPARC) v9	64	-9223372036854775808	9223372036854775807
signed long (SPARC)v8	32	-2147483648	2147483647
signed long (SPARC) v9	64	-9223372036854775808	9223372036854775807
unsigned long (SPARC) v8	32	0	4294967295

TABLE E-1 Representations and Sets of Values of Integers (*Continued*)

Integer	Bits	Minimum	Maximum
unsigned long (SPARC) v9	64	0	18446744073709551615
long long*	64	-9223372036854775808	9223372036854775807
signed long long*	64	-9223372036854775808	9223372036854775807
unsigned long long*	64	0	18446744073709551615

* Not valid in `-xc` mode

(6.2.1.2) *The result of converting an integer to a shorter signed integer, or the result of converting an unsigned integer to a signed integer of equal length, if the value cannot be represented:*

When an integer is converted to a shorter `signed` integer, the low order bits are copied from the longer integer to the shorter `signed` integer. The result may be negative.

When an unsigned integer is converted to a `signed` integer of equal size, the low order bits are copied from the unsigned integer to the `signed` integer. The result may be negative.

(6.3) *The results of bitwise operations on signed integers:*

The result of a bitwise operation applied to a `signed` type is the bitwise operation of the operands, including the `sign` bit. Thus, each bit in the result is set if—and only if—each of the corresponding bits in both of the operands is set.

(6.3.5) *The sign of the remainder on integer division:*

The result is the same sign as the dividend; thus, the remainder of $-23/4$ is -3 .

(6.3.7) *The result of a right shift of a negative-valued signed integral type:*

The result of a right shift is a `signed` right shift.

E.1.6 Floating-Point (G.3.6)

(6.1.2.5) *The representations and sets of values of the various types of floating-point numbers:*

TABLE E-2 Values for a `float`

<i>float</i>	
Bits	32
Min	1.17549435E-38
Max	3.40282347E+38
Epsilon	1.19209290E-07

TABLE E-3 Values for a `double`

<i>double</i>	
Bits	64
Min	2.2250738585072014E-308
Max	1.7976931348623157E+308
Epsilon	2.2204460492503131E-16

TABLE E-4 Values for long `double`

<i>long double</i>	
Bits	128 (SPARC) 80 (x86)
Min	3.362103143112093506262677817321752603E-4932 (SPARC) 3.3621031431120935062627E-4932 (x86)
Max	1.189731495357231765085759326628007016E+4932 (SPARC) 1.1897314953572317650213E4932 (x86)
Epsilon	1.925929944387235853055977942584927319E-34 (SPARC) 1.0842021724855044340075E-19 (x86)

(6.2.1.3) *The direction of truncation when an integral number is converted to a floating-point number that cannot exactly represent the original value:*

Numbers are rounded to the nearest value that can be represented.

(6.2.1.4) *The direction of truncation or rounding when a floating-point number is converted to a narrower floating-point number:*

Numbers are rounded to the nearest value that can be represented.

E.1.7 Arrays and Pointers (G.3.7)

(6.3.3.4, 7.1.1) *The type of integer required to hold the maximum size of an array; that is, the type of the sizeof operator, size_t:*

unsigned int as defined in `stddef.h`.

unsigned long for `-Xarch=v9`

(6.3.4) *The result of casting a pointer to an integer, or vice versa:*

The bit pattern does not change for pointers and values of type int, long, unsigned int and unsigned long.

(6.3.6, 7.1.1) *The type of integer required to hold the difference between two pointers to members of the same array, ptrdiff_t:*

int as defined in `stddef.h`.

long for `-Xarch=v9`

E.1.8 Registers (G.3.8)

(6.5.1) *The extent to which objects can actually be placed in registers by use of the register storage-class specifier:*

The number of effective register declarations depends on patterns of use and definition within each function and is bounded by the number of registers available for allocation. Neither the compiler nor the optimizer is required to honor register declarations.

E.1.9 Structures, Unions, Enumerations, and Bit-Fields (G.3.9)

(6.3.2.3) *A member of a union object is accessed using a member of a different type:*

The bit pattern stored in the union member is accessed, and the value interpreted, according to the type of the member by which it is accessed.

(6.5.2.1) *The padding and alignment of members of structures.*

TABLE E-5 Padding and Alignment of Structure Members

Type	Alignment Boundary	Byte Alignment
char	Byte	1
short	Halfword	2
int	Word	4
long (SPARC) v8	Word	4
long (SPARC) v9	Doubleword	8
float (SPARC)	Word	4
double (SPARC)	Doubleword (SPARC) Word (x86)	8 (SPARC) 4 (x86)
long double (SPARC) v8	Doubleword (SPARC) Word (x86)	8 (SPARC) 4 (x86)

TABLE E-5 Padding and Alignment of Structure Members (*Continued*)

Type	Alignment Boundary	Byte Alignment
long double (SPARC) v9	Quadword	16
pointer (SPARC) v8	Word	4
pointer (SPARC) v9	Quadword	8
long long*	Doubleword (SPARC) Word (x86)	8 (SPARC) 4 (x86)

* Not available in `-xc` mode.

Structure members are padded internally, so that every element is aligned on the appropriate boundary.

Alignment of structures is the same as its more strictly aligned member. For example, a `struct` with only `chars` has no alignment restrictions, whereas a `struct` containing a `double` would be aligned on an 8-byte boundary.

(6.5.2.1) Whether a plain `int` bit-field is treated as a signed `int` bit-field or as an unsigned `int` bit-field:

It is treated as an unsigned `int`.

(6.5.2.1) The order of allocation of bit-fields within an `int`:

Bit-fields are allocated within a storage unit from high-order to low-order.

(6.5.2.1) Whether a bit-field can straddle a storage-unit boundary:

Bit-fields do not straddle storage-unit boundaries.

(6.5.2.2) The integer type chosen to represent the values of an enumeration type:

This is an `int`.

E.1.10 Qualifiers (G.3.10)

(6.5.5.3) What constitutes an access to an object that has volatile-qualified type:

Each reference to the name of an object constitutes one access to the object.

E.1.11 Declarators (G.3.11)

(6.5.4) The maximum number of declarators that may modify an arithmetic, structure, or union type:

No limit is imposed by the compiler.

E.1.12 Statements (G.3.12)

(6.6.4.2) The maximum number of case values in a switch statement:

No limit is imposed by the compiler.

E.1.13 Preprocessing Directives (G.3.13)

(6.8.1) Whether the value of a single-character character constant in a constant expression that controls conditional inclusion matches the value of the same character constant in the execution character set:

A character constant within a preprocessing directive has the same numeric value as it has within any other expression.

(6.8.1) Whether such a character constant may have a negative value:

Character constants in this context may have negative values (SPARC) (x86).

(6.8.2) The method for locating includable source files:

A file whose name is delimited by `< >` is searched for first in the directories named by the `-I` option, and then in the standard directory. The standard directory is `/usr/include`, unless the `-YI` option is used to specify a different default location.

A file whose name is delimited by quotes is searched for first in the directory of the source file that contains the `#include`, then in directories named by the `-I` option, and last in the standard directory.

If a file name enclosed in `< >` or double quotes begins with a `/` character, the file name is interpreted as a path name beginning in the root directory. The search for this file begins in the root directory only.

(6.8.2) The support of quoted names for includable source files:

Quoted file names in `include` directives are supported.

(6.8.2) The mapping of source file character sequences:

Source file characters are mapped to their corresponding ASCII values.

(6.8.6) The behavior on each recognized #pragma directive:

The following pragmas are supported. See [Section 2.8, “Pragmas” on page 2-10](#) for more information.

- `align integer (variable[, variable])`
- `does_not_read_global_data (funcname [, funcname])`
- `does_not_return (funcname[, funcname])`
- `does_not_write_global_data (funcname[, funcname])`
- `error_messages (on|off|default, tag1[tag2... tagn])`
- `fini (f1[, f2..., fn])`
- `ident string`
- `init (f1[, f2..., fn])`
- `inline (funcname[, funcname])`
- `int_to_unsigned (funcname)`
- `MP serial_loop`
- `MP serial_loop_nested`
- `MP taskloop`
- `no_inline (funcname[, funcname])`
- `nomemorydepend`
- `no_side_effect (funcname[, funcname])`
- `opt_level (funcname[, funcname])`
- `pack(n)`

- `pipeline(n)`
- `rarely_called(funcname[, funcname])`
- `redefine_extname old_extname new_extname`
- `returns_new_memory(funcname[, funcname])`
- `unknown_control_flow(name[, name])`
- `unroll(unroll_factor)`
- `weak(symbol1 [= symbol2])`

(6.8.8) *The definitions for `__DATE__` and `__TIME__` when, respectively, the date and time of translation are not available:*

These macros are always available from the environment.

E.1.14 Library Functions (G.3.14)

(7.1.6) *The null pointer constant to which the macro `NULL` expands:*

`NULL` equals 0.

(7.2) *The diagnostic printed by and the termination behavior of the `assert` function:*

The diagnostic is:

Assertion failed: *statement*. file *filename*, line *number*

Where:

- *statement* is the statement which failed the assertion
- *filename* is the name of the file containing the failure
- *line number* is the number of the line on which the failure occurs

(7.3.1) *The sets of characters tested for by the isalnum, isalpha, iscntrl, islower, isprint, and isupper functions:*

TABLE E-6 Character Sets Tested by isalpha, islower, Etc.

isalnum	ASCII characters A-Z, a-z and 0-9
isalpha	ASCII characters A-Z and a-z, plus locale-specific single-byte letters
iscntrl	ASCII characters with value 0-31 and 127
islower	ASCII characters a-z
isprint	Locale-specific single-byte printable characters
isupper	ASCII characters A-Z

(7.5.1) *The values returned by the mathematics functions on domain errors:*

TABLE E-7 Values Returned on Domain Errors

Error	Math Functions	Compiler Modes	
		-Xs, -Xt	-Xa, -Xc
DOMAIN	acos(x >1)	0.0	0.0
DOMAIN	asin(x >1)	0.0	0.0
DOMAIN	atan2(+0,+0)	0.0	0.0
DOMAIN	y0(0)	-HUGE	-HUGE_VAL
DOMAIN	y0(x<0)	-HUGE	-HUGE_VAL
DOMAIN	y1(0)	-HUGE	-HUGE_VAL
DOMAIN	y1(x<0)	-HUGE	-HUGE_VAL
DOMAIN	yn(n,0)	-HUGE	-HUGE_VAL
DOMAIN	yn(n,x<0)	-HUGE	-HUGE_VAL
DOMAIN	log(x<0)	-HUGE	-HUGE_VAL
DOMAIN	log10(x<0)	-HUGE	-HUGE_VAL
DOMAIN	pow(0,0)	0.0	1.0
DOMAIN	pow(0,neg)	0.0	-HUGE_VAL
DOMAIN	pow(neg,non-integral)	0.0	NaN
DOMAIN	sqrt(x<0)	0.0	NaN

TABLE E-7 Values Returned on Domain Errors (*Continued*)

Error	Math Functions	Compiler Modes	
		-Xs, -Xt	-Xa, -Xc
DOMAIN	fmod(x,0)	x	NaN
DOMAIN	remainder(x,0)	NaN	NaN
DOMAIN	acosh(x<1)	NaN	NaN
DOMAIN	atanh(x >1)	NaN	NaN

(7.5.1) *Whether the mathematics functions set the integer expression `errno` to the value of the macro `ERANGE` on underflow range errors:*

Mathematics functions, except `scalbn`, set `errno` to `ERANGE` when underflow is detected.

(7.5.6.4) *Whether a domain error occurs or zero is returned when the `fmod` function has a second argument of zero:*

In this case, it returns the first argument with domain error.

(7.7.1.1) *The set of signals for the `signal` function:*

The following table shows the semantics for each signal as recognized by the `signal` function:

TABLE E-8 Semantics for `signal` Signals

Signal	No.	Default	Event
SIGHUP	1	Exit	hangup
SIGINT	2	Exit	interrupt
SIGQUIT	3	Core	quit
SIGILL	4	Core	illegal instruction (not reset when caught)
SIGTRAP	5	Core	trace trap (not reset when caught)
SIGIOT	6	Core	IOT instruction
SIGABRT	6	Core	Used by <code>abort</code>
SIGEMT	7	Core	EMT instruction
SIGFPE	8	Core	floating point exception

TABLE E-8 Semantics for signal Signals (*Continued*)

Signal	No.	Default	Event
SIGKILL	9	Exit	kill (cannot be caught or ignored)
SIGBUS	10	Core	bus error
SIGSEGV	11	Core	segmentation violation
SIGSYS	12	Core	bad argument to system call
SIGPIPE	13	Exit	write on a pipe with no one to read it
SIGALRM	14	Exit	alarm clock
SIGTERM	15	Exit	software termination signal from kill
SIGUSR1	16	Exit	user defined signal 1
SIGUSR2	17	Exit	user defined signal 2
SIGCLD	18	Ignore	child status change
SIGCHLD	18	Ignore	child status change alias
SIGPWR	19	Ignore	power-fail restart
SIGWINCH	20	Ignore	window size change
SIGURG	21	Ignore	urgent socket condition
SIGPOLL	22	Exit	pollable event occurred
SIGIO	22	Exit	socket I/O possible
SIGSTOP	23	Stop	stop (cannot be caught or ignored)
SIGTSTP	24	Stop	user stop requested from tty
SIGCONT	25	Ignore	stopped process has been continued
SIGTTIN	26	Stop	background tty read attempted
SIGTTOU	27	Stop	background tty write attempted
SIGVTALRM	28	Exit	virtual timer expired
SIGPROF	29	Exit	profiling timer expired
SIGXCPU	30	Core	exceeded cpu limit
SIGXFSZ	31	Core	exceeded file size limit
SIGWAITINGT	32	Ignore	process's lwps are blocked

(7.7.1.1) The default handling and the handling at program startup for each signal recognized by the signal function:

See above.

(7.7.1.1) If the equivalent of `signal(sig, SIG_DFL)`; is not executed prior to the call of a signal handler, the blocking of the signal that is performed:

The equivalent of `signal(sig, SIG_DFL)` is always executed.

(7.7.1.1) Whether the default handling is reset if the SIGILL signal is received by a handler specified to the signal function:

Default handling is not reset in SIGILL.

(7.9.2) Whether the last line of a text stream requires a terminating new-line character:

The last line does not need to end in a newline.

(7.9.2) Whether space characters that are written out to a text stream immediately before a new-line character appear when read in:

All characters appear when the stream is read.

(7.9.2) The number of null characters that may be appended to data written to a binary stream:

No null characters are appended to a binary stream.

(7.9.3) Whether the file position indicator of an append mode stream is initially positioned at the beginning or end of the file:

The file position indicator is initially positioned at the end of the file.

(7.9.3) Whether a write on a text stream causes the associated file to be truncated beyond that point:

A write on a text stream does not cause a file to be truncated beyond that point unless a hardware device forces it to happen.

(7.9.3) The characteristics of file buffering:

Output streams, with the exception of the standard error stream (`stderr`), are by default-buffered if the output refers to a file, and line-buffered if the output refers to a terminal. The standard error output stream (`stderr`) is by default unbuffered.

A buffered output stream saves many characters, and then writes the characters as a block. An unbuffered output stream queues information for immediate writing on the destination file or terminal immediately. Line-buffered output queues each line of output until the line is complete (a newline character is requested).

(7.9.3) Whether a zero-length file actually exists:

A zero-length file does exist since it has a directory entry.

(7.9.3) The rules for composing valid file names:

A valid file name can be from 1 to 1,023 characters in length and can use all character except the characters `null` and `/` (slash).

(7.9.3) Whether the same file can be open multiple times:

The same file can be opened multiple times.

(7.9.4.1) The effect of the `remove` function on an open file:

The file is deleted on the last call which closes the file. A program cannot open a file which has already been removed.

(7.9.4.2) The effect if a file with the new name exists prior to a call to the `rename` function:

If the file exists, it is removed and the new file is written over the previously existing file.

(7.9.6.1) The output for `%p` conversion in the `fprintf` function:

The output for `%p` is equivalent to `%x`.

(7.9.6.2) The input for %p conversion in the fscanf function:

The input for %p is equivalent to %x.

(7.9.6.2) The interpretation of a - character that is neither the first nor the last character in the scan list for %[conversion in the fscanf function:

The - character indicates an inclusive range; thus, [0-9] is equivalent to [0123456789].

E.1.15 Locale-Specific Behavior (G.4)

(7.12.1) The local time zone and Daylight Savings Time:

The local time zone is set by the environment variable TZ.

(7.12.2.1) The era for the clock function

The era for the clock is represented as clock ticks with the origin at the beginning of the execution of the program.

The following characteristics of a hosted environment are locale-specific:

(5.2.1) The content of the execution character set, in addition to the required members:

Locale-specific (no extension in C locale).

(5.2.2) The direction of printing:

Printing is always left to right.

(7.1.1) The decimal-point character:

Locale-specific ("." in C locale).

(7.3) The implementation-defined aspects of character testing and case mapping functions:

Same as 4.3.1.

(7.11.4.4) The collation sequence of the execution character set:

Locale-specific (ASCII collation in C locale).

(7.12.3.5) The formats for time and date:

Locale-specific. Formats for the C locale are shown in the tables below.

The names of the months are:

TABLE E-9 Names of Months

January	May	September
February	June	October
March	July	November
April	August	December

The names of the days of the week are:

TABLE E-10 Days and Abbreviated Days of the Week

Days		Abbreviated Days	
Sunday	Thursday	Sun	Thu
Monday	Friday	Mon	Fri
Tuesday	Saturday	Tue	Sat
Wednesday		Wed	

The format for time is:

`%H:%M:%S`

The format for date is:

`%m/%d/%y`

The formats for AM and PM designation are: AM PM

ISO C Data Representations

This appendix describes how ISO C represents data in storage and the mechanisms for passing arguments to functions. It is intended as a guide to programmers who want to write or use modules in languages other than C and have those modules interface with C code.

F.1 Storage Allocation

The following table shows the data types and how they are represented.

Note – Storage allocated on the stack (identifiers with internal, or automatic, linkage) should be limited to two gigabytes or less.

TABLE F-1 Storage Allocation for Data Types

Data Type	Internal Representation
char elements	A single 8-bit byte aligned on a byte boundary.
short integers	Halfword (two bytes or 16 bits), aligned on a two-byte boundary
int	32 bits (four bytes or one word), aligned on a four-byte boundary
long	32 bits on v8 and x86 (four bytes or one word), aligned on a four-byte boundary 64 bits on v9 (eight bytes or two words) aligned on an eight-byte boundary)
pointer	32 bits on v8 and x86 (four bytes or one word), aligned on a four-byte boundary 64 bits on v9 (eight bytes or two words) aligned on an eight-byte boundary)

TABLE F-1 Storage Allocation for Data Types (*Continued*)

Data Type	Internal Representation
<code>long long</code> *	(<i>SPARC</i>) 64 bits (eight bytes or two words), aligned on an eight-byte boundary (<i>x86</i>) 64 bits (eight bytes or two words), aligned on a four-byte boundary
<code>float</code>	32 bits (four bytes or one word), aligned on a four-byte boundary. A <code>float</code> has a <code>sign</code> bit, 8-bit exponent, and 23-bit fraction.
<code>double</code>	64 bits (eight bytes or two words), aligned on an eight-byte boundary (<i>SPARC</i>) or aligned on a four-byte boundary (<i>x86</i>). A <code>double</code> element has a <code>sign</code> bit, an 11-bit exponent and a 52-bit fraction.
<code>long double</code>	<code>v8</code> (<i>SPARC</i>) 128 bits (16 bytes or four words), aligned on an eight-byte boundary. A <code>long double</code> element has a <code>sign</code> bit, a 15-bit exponent and a 112-bit fraction. <code>v9</code> (<i>SPARC</i>) 128 bits (16 bytes or four words), aligned on a 16 byte boundary. A <code>long double</code> element has a <code>sign</code> bit, a 15-bit exponent and a 112-bit fraction. (<i>x86</i>) 96 bits (12 bytes or three words) aligned on a four-byte boundary. A <code>long double</code> element has a <code>sign</code> bit, a 16-bit exponent, and a 64-bit fraction. 16 bits are unused.

* `long long` is not available in `-Xc` mode with `-xc99=none`.

F.2 Data Representations

Bit numbering of any given data element depend on the architecture in use: *SPARCstation*[™] machines use bit 0 as the least significant bit, with byte 0 being the most significant byte. The tables in this section describe the various representations.

F.2.1 Integer Representations

Integer types used in ISO C are short, int, long, and long long:

TABLE F-2 Representation of short

Bits	Content
8 - 15	Byte 0 (<i>SPARC</i>) Byte 1 (<i>x86</i>)
0 - 7	Byte 1 (<i>SPARC</i>) Byte 0 (<i>x86</i>)

TABLE F-3 Representation of int

Bits	Content
24 - 31	Byte 0 (<i>SPARC</i>) Byte 3 (<i>x86</i>)
16 - 23	Byte 1 (<i>SPARC</i>) Byte 2 (<i>x86</i>)
8 - 15	Byte 2 (<i>SPARC</i>) Byte 1 (<i>x86</i>)
0 - 7	Byte 3 (<i>SPARC</i>) Byte 0 (<i>x86</i>)

TABLE F-4 Representation of long on x86 and SPARC v8 versus SPARC v9

Bits	Content
24 - 31	Byte 0 (<i>SPARC</i>) v8 Byte 4 (<i>SPARC</i>) v9 Byte 3 (<i>x86</i>)
16 - 23	Byte 1 (<i>SPARC</i>) v8 Byte 5 (<i>SPARC</i>) v9 Byte 2 (<i>x86</i>)
8 - 15	Byte 2 (<i>SPARC</i>) v8 Byte 6 (<i>SPARC</i>) v9 Byte 1 (<i>x86</i>)
0 - 7	Byte 3 (<i>SPARC</i>) v8 Byte 7 (<i>SPARC</i>) v9 Byte 0 (<i>x86</i>)

TABLE F-5 Representation of long long*

Bits	Content
56 - 63	Byte 0 (<i>SPARC</i>) Byte 7 (<i>x86</i>)
48 - 55	Byte 1 (<i>SPARC</i>) Byte 6 (<i>x86</i>)
40 - 47	Byte 2 (<i>SPARC</i>) Byte 5 (<i>x86</i>)
32 - 39	Byte 3 (<i>SPARC</i>) Byte 4 (<i>x86</i>)
24 - 31	Byte 4 (<i>SPARC</i>) Byte 3 (<i>x86</i>)
16 - 23	Byte 5 (<i>SPARC</i>) Byte 2 (<i>x86</i>)
8 - 15	Byte 6 (<i>SPARC</i>) Byte 1 (<i>x86</i>)
0 - 7	Byte 7 (<i>SPARC</i>) Byte 0 (<i>x86</i>)

* long long is not available in `-xc` mode.

F.2.2 Floating-Point Representations

`float`, `double`, and `long double` data elements are represented according to the ISO IEEE 754-1985 standard. The representation is:

$$(-1)^{s(e - bias)} \times 2^{j-f}$$

where:

- s = sign
- e = biased exponent
- j is the leading bit, determined by the value of e . In the case of `long double (x86)`, the leading bit is explicit; in all other cases, it is implicit.
- f = fraction
- u means that the bit can be either 0 or 1.

The following tables show the position of the bits.

TABLE F-6 float Representation

Bits	Name
31	Sign
23 - 30	Exponent
0 - 22	Fraction

TABLE F-7 double Representation

Bits	Name
63	Sign
52 - 62	Exponent
0 - 51	Fraction

TABLE F-8 long double Representation (*SPARC*)

Bits	Name
127	Sign
112 - 126	Exponent
0 - 111	Fraction

TABLE F-9 long double Representation (*x86*)

Bits	Name
80 - 95	Unused
79	Sign
64 - 78	Exponent
63	Leading bit
0 - 62	Fraction

For further information, refer to the *Numerical Computation Guide*.

F.2.3 Exceptional Values

`float` and `double` numbers are said to contain a “hidden,” or implied, bit, providing for one more bit of precision than would otherwise be the case. In the case of `long double`, the leading bit is implicit (*SPARC*) or explicit (*x86*); this bit is 1 for normal numbers, and 0 for subnormal numbers.

TABLE F-10 `float` Representations

normal number ($0 < e < 255$):	$(-1)^{\text{Sign}} 2^{(\text{exponent} - 127)} 1.f$
subnormal number ($e=0, f \neq 0$):	$(-1)^{\text{Sign}} 2^{(-126)} 0.f$
zero ($e=0, f=0$):	$(-1)^{\text{Sign}} 0.0$
signaling NaN	$s=u, e=255(\text{max}); f=.0uuu-uu$; at least one bit must be nonzero
quiet NaN	$s=u, e=255(\text{max}); f=.1uuu-uu$
Infinity	$s=u, e=255(\text{max}); f=.0000-00$ (all zeroes)

TABLE F-11 `double` Representations

normal number ($0 < e < 2047$):	$(-1)^{\text{Sign}} 2^{(\text{exponent} - 1023)} 1.f$
subnormal number ($e=0, f \neq 0$):	$(-1)^{\text{Sign}} 2^{(-1022)} 0.f$
zero ($e=0, f=0$):	$(-1)^{\text{Sign}} 0.0$
signaling NaN	$s=u, e=2047(\text{max}); f=.0uuu-uu$; at least one bit must be nonzero
quiet NaN	$s=u, e=2047(\text{max}); f=.1uuu-uu$
Infinity	$s=u, e=2047(\text{max}); f=.0000-00$ (all zeroes)

TABLE F-12 `long double` Representations

normal number ($0 < e < 32767$):	$(-1)^{\text{Sign}} 2^{(\text{exponent} - 16383)} 1.f$
subnormal number ($e=0, f \neq 0$):	$(-1)^{\text{Sign}} 2^{(-16382)} 0.f$
zero ($e=0, f=0$):	$(-1)^{\text{Sign}} 0.0$
signaling NaN	$s=u, e=32767(\text{max}); f=.0uuu-uu$; at least one bit must be nonzero
quiet NaN	$s=u, e=32767(\text{max}); f=.1uuu-uu$
Infinity	$s=u, e=32767(\text{max}); f=.0000-00$ (all zeroes)

F.2.4 Hexadecimal Representation of Selected Numbers

The following tables show the hexadecimal representations.

TABLE F-13 Hexadecimal Representation of Selected Numbers (*SPARC*)

Value	float	double	long double
+0	00000000	0000000000000000	00000000000000000000000000000000
-0	80000000	8000000000000000	80000000000000000000000000000000
+1.0	3F800000	3FF0000000000000	3FFF0000000000000000000000000000
-1.0	BF800000	BFF0000000000000	BFFF0000000000000000000000000000
+2.0	40000000	4000000000000000	40000000000000000000000000000000
+3.0	40400000	4008000000000000	40080000000000000000000000000000
+Infinity	7F800000	7FF0000000000000	7FFF0000000000000000000000000000
-Infinity	FF800000	FFF0000000000000	FFFF0000000000000000000000000000
NaN	7FBFFFFF	7FF7FFFFFFFFFFFF	7FFF7FFFFFFFFFFFFFFFFFFFFFFFFFFFFF

TABLE F-14 Hexadecimal Representation of Selected Numbers (*x86*)

Value	float	double	long double
+0	00000000	0000000000000000	000000000000000000000000
-0	80000000	0000000080000000	800000000000000000000000
+1.0	3F800000	000000003FF00000	3FFF80000000000000000000
-1.0	BF800000	00000000BFF00000	BFFF80000000000000000000
+2.0	40000000	0000000040000000	400080000000000000000000
+3.0	40400000	0000000040080000	4000C0000000000000000000
+Infinity	7F800000	000000007FF00000	7FFF80000000000000000000
-Infinity	FF800000	00000000FFF00000	FFFF80000000000000000000
NaN	7FBFFFFF	FFFFFFFF7FF7FFFF	7FFFBFFFFFFFFFFFFFFFFFFFFFFFFF

For further information, refer to the *Numerical Computation Guide*.

F.2.5 Pointer Representation

A pointer in C occupies four bytes. A pointer in C occupies eight bytes on SPARC v9 architectures. The NULL value pointer is equal to zero.

F.2.6 Array Storage

Arrays are stored with their elements in a specific storage order. The elements are actually stored in a linear sequence of storage elements.

C arrays are stored in row-major order; the last subscript in a multidimensional array varies the fastest.

String data types are simply arrays of `char` elements. The maximum number of characters allowed in a string literal or wide string literal (after concatenation) is 4,294,967,295.

See [Section F.1, “Storage Allocation” on page F-1](#) for information on the size limit of storage allocated on the stack.

TABLE F-15 Array Types and Storage

Type	Maximum Number of Elements for SPARC and x86	Maximum Number of Elements for SPARC V9
<code>char</code>	4,294,967,295	2,305,843,009,213,693,951
<code>short</code>	2,147,483,647	1,152,921,504,606,846,975
<code>int</code>	1,073,741,823	576,460,752,303,423,487
<code>long</code>	1,073,741,823	288,230,376,151,711,743
<code>float</code>	1,073,741,823	576,460,752,303,423,487
<code>double</code>	536,870,911	288,230,376,151,711,743
<code>long double</code>	268,435,451	144,115,188,075,855,871
<code>long long</code> *	536,870,911	288,230,376,151,711,743

* Not valid in `-Xc` mode with `-xc99=none`.

Static and global arrays can accommodate many more elements.

F.2.7 Arithmetic Operations on Exceptional Values

This section describes the results derived from applying the basic arithmetic operations to combinations of exceptional and ordinary floating-point values. The information that follows assumes that no traps or any other exception actions are taken.

The following table explains the abbreviations:

TABLE F-16 Abbreviation Usage

Abbreviation	Meaning
Num	Subnormal or normal number
Inf	Infinity (positive or negative)
NaN	Not a number
Uno	Unordered

The following tables describe the types of values that result from arithmetic operations performed with combinations of different types of operands.

TABLE F-17 Addition and Subtraction Results

	Right Operand: 0	Right Operand: Num	Right Operand: Inf	Right Operand: NaN
Left Operand: 0	0	Num	Inf	NaN
Left Operand: Num	Num	See*	Inf	NaN
Left Operand: Inf	Inf	Inf	See*	NaN
Left Operand: NaN	NaN	NaN	NaN	NaN

* Num + Num could be Inf, rather than Num, when the result is too large (overflow). Inf + Inf = NaN when the infinities are of opposite sign.

TABLE F-18 Multiplication Results

	Right Operand: 0	Right Operand: Num	Right Operand: Inf	Right Operand: NaN
Left Operand: 0	0	0	NaN	NaN
Left Operand: Num	0	Num	Inf	NaN
Left Operand: Inf	NaN	Inf	Inf	NaN
Left Operand: NaN	NaN	NaN	NaN	NaN

TABLE F-19 Division Results

	Right Operand: 0	Right Operand: Num	Right Operand: Inf	Right Operand: NaN
Left Operand: 0	NaN	0	0	NaN
Left Operand: Num	Inf	Num	0	NaN
Left Operand: Inf	Inf	Inf	NaN	NaN
Left Operand: NaN	NaN	NaN	NaN	NaN

TABLE F-20 Comparison Results

	Right Operand: 0	Right Operand: +Num	Right Operand: +Inf	Right Operand: +NaN
Left Operand: 0	=	<	<	Uno
Left Operand: +Num	>	The result of the comparison	<	Uno
Left Operand: +Inf	>	>	=	Uno
Left Operand: +NaN	Uno	Uno	Uno	Uno

Note – NaN compared with NaN is unordered, and results in inequality. +0 compares equal to -0.

F.3 Argument-Passing Mechanism

This section describes how arguments are passed in ISO C.

- All arguments to C functions are passed by value.
- Actual arguments are passed in the reverse order from which they are declared in a function declaration.
- Actual arguments which are expressions are evaluated before the function reference. The result of the expression is then placed in a register or pushed onto the stack.

32-Bit SPARC

Functions return integer results in register %o0, float results in register %f0, and double results in registers %f0 and %f1.

long long¹ integers are passed in registers with the higher word order in %oN, and the lower order word in %o(N+1). In-register results are returned in %o0 and %o1, with similar ordering.

All arguments, except doubles and long doubles, are passed as four-byte values. A double is passed as an eight-byte value. The first six four-byte values (double counts as 8) are passed in registers %o0 through %o5. The rest are passed onto the stack. Structures are passed by making a copy of the structure and passing a pointer to the copy. A long double is passed in the same manner as a structure.

Registers described are as seen by the caller.

64-Bit SPARC

All integral arguments are passed as eight-byte values.

Floating-point arguments are passed in floating-point registers when possible.

(x86)

Functions return results in the following registers:

TABLE F-21 Registers Used by x86 Functions to Return Types

Register	Type Returned
int	%eax
long long	%edx and %eax
float, double, and long double	%st(0)
float _Complex	%eax for the real part and %edx for the imaginary part
double _Complex and long double _Complex	The same as a struct that contains two elements of the corresponding floating point type.

1. Not available in -xc mode with -xc99=none.

All arguments except `structs`, `unions`, `long longs`, `doubles` and `long doubles` are passed as four-byte values; a `long long` is passed as an eight-byte value, a `double` is passed as an eight-byte value, and a `long double` is passed as a 12-byte value.

`structs` and `unions` are copied onto the stack. The size is rounded up to a multiple of four bytes. Functions returning `structs` and `unions` are passed a hidden first argument, pointing to the location into which the returned `struct` or `union` is stored.

Upon return from a function, it is the responsibility of the caller to pop arguments from the stack, except for the extra argument for `struct` and `union` returns that is popped by the called function.

Performance Tuning (*SPARC*)

This appendix describes performance tuning on SPARC platforms.

G.1 Limits

Some parts of the C library cannot be optimized for speed, even though doing so would benefit most applications. Some examples:

- Integer arithmetic routines—Current SPARC V8 processors support integer multiplication and division instructions. However, if standard C library routines were to use these instructions, programs running on V7 SPARC processors would either run slowly due to kernel emulation overhead, or might break altogether. Hence, integer multiplication and division instructions cannot be used in the standard C library routines.
- Doubleword memory access—Block copy and move routines, such as `memmove()` and `bcopy()`, could run considerably faster if they used SPARC doubleword load and store instructions (`ldd` and `std`). Some memory-mapped devices, such as frame buffers, do not support 64-bit access; nevertheless, these devices are expected to work correctly with `memmove()` and `bcopy()`. Hence, `ldd` and `std` cannot be used in the standard C library routines.
- Memory allocation algorithms—The C library routines `malloc()` and `free()` are typically implemented as a compromise between speed, space, and insensitivity to coding errors in old UNIX programs. Memory allocators based on “buddy system” algorithms typically run faster than the standard library version, but tend to use more space.

G.2 libfast.a Library

The library `libfast.a` provides speed-tuned versions of standard C library functions. Because it is an optional library, it can use algorithms and data representations that may not be appropriate for the standard C library, even though they improve the performance of most applications.

Use profiling to determine whether the routines in the following checklist are important to the performance of your application, then use this checklist to decide whether `libfast.a` benefits the performance:

- *Do* use `libfast.a` if performance of integer multiplication or division is important, even if a single binary version of the application must run on both V7 and V8 SPARC platforms. The important routines are: `.mul`, `.div`, `.rem`, `.umul`, `.udiv`, and `.urem`.
- *Do* use `libfast.a` if performance of memory allocation is important, and the size of the most commonly allocated blocks is close to a power of two. The important routines are: `malloc()`, `free()`, `realloc()`.
- *Do* use `libfast.a` if performance of block move or fill routines is important. The important routines are: `bcopy()`, `bzero()`, `memcpy()`, `memmove()`, and `memset()`.
- *Do not* use `libfast.a` if the application requires user mode, memory-mapped access to an I/O device that does not support 64-bit memory operations.
- *Do not* use `libfast.a` if the application is multithreaded.

When linking the application, add the option `-lfast` to the `cc` command used at link time. The `cc` command links the routines in `libfast.a` ahead of their counterparts in the standard C library.

The Differences Between K&R Sun C and Sun ISO C

This appendix describes the differences between the previous K&R Sun C and Sun ISO C.

For more information see [Section 1.3, “Standards Conformance”](#) on page 1-4.

H.1 K&R Sun C Incompatibilities With Sun ISO C

TABLE H-1 K&R Sun C Incompatibilities With Sun ISO C

Topic	Sun C (K&R)	Sun ISO C
<code>envp</code> argument to <code>main()</code>	Allows <code>envp</code> as third argument to <code>main()</code> .	Allows this third argument; however, this usage is not strictly conforming to the ISO C standard.
Keywords	Treats the identifiers <code>const</code> , <code>volatile</code> , and <code>signed</code> as ordinary identifiers.	<code>const</code> , <code>volatile</code> , and <code>signed</code> are keywords.
<code>extern</code> and <code>static</code> functions declarations inside a block	Promotes these function declarations to file scope.	The ISO standard does not guarantee that block scope function declarations are promoted to file scope.
Identifiers	Allows dollar signs (\$) in identifiers.	\$ not allowed.

TABLE H-1 K&R Sun C Incompatibilities With Sun ISO C (*Continued*)

Topic	Sun C (K&R)	Sun ISO C
long float types	Accepts long float declarations and treats these as double(s).	Does not accept these declarations.
Multi-character character-constants	<code>int mc = 'abcd';</code> yields: <code>abcd</code>	<code>int mc = 'abcd';</code> yields: <code>dcba</code>
Integer constants	Accepts 8 or 9 in octal escape sequences.	Does not accept 8 or 9 in octal escape sequences.
Assignment operators	Treats the following operator pairs as two tokens, and as a consequence, permits white space between them: <code>*=, /=, %=, +=, -=, <<=,</code> <code>>>=, &=, ^=, =</code>	Treats them as single tokens, and therefore disallows white space in between.
Unsigned preserving semantics for expressions	Supports unsigned preserving, that is, unsigned char/shorts are converted into unsigned int(s).	Supports value-preserving, that is, unsigned char/short(s) are converted into int(s).
Single/double precision calculations	Promotes the operands of floating point expressions to double. Functions which are declared to return floats always promote their return values to doubles.	Allows operations on floats to be performed in single precision calculations. Allows float return types for these functions.
Name spaces of struct/union members	Allows struct, union, and arithmetic types using member selection operators ('.', '->') to work on members of other struct(s) or unions.	Requires that every unique struct/union have its own unique name space.
A cast as an lvalue	Supports casts as lvalue(s). For example: <code>(char *)ip = &char;</code>	Does not support this feature.
Implied int declarations	Supports declarations without an explicit type specifier. A declaration such as <code>num;</code> is treated as implied int. For example: <code>num; /*num implied as an int*/</code> <code>int num2; /* num2 explicitly*/</code> <code> /* declared an</code> <code>int */</code>	The <code>num;</code> declaration (without the explicit type specifier <code>int</code>) is not supported, and generates a syntax error.

TABLE H-1 K&R Sun C Incompatibilities With Sun ISO C (Continued)

Topic	Sun C (K&R)	Sun ISO C
Empty declarations	Allows empty declarations, such as: <code>int;</code>	Except for tags, disallows empty declarations.
Type specifiers on type definitions	Allows type specifiers such as <code>unsigned</code> , <code>short</code> , <code>long</code> on <code>typedefs</code> declarations. For example: <code>typedef short small;</code> <code>unsigned small x;</code>	Does not allow type specifiers to modify <code>typedef</code> declarations.
Types allowed on bit fields	Allows bit fields of all integral types, including unnamed bit fields. The ABI requires support of unnamed bit fields and the other integral types.	Supports bit-fields only of the type <code>int</code> , <code>unsigned int</code> and <code>signed int</code> . Other types are undefined.
Treatment of tags in incomplete declarations	Ignores the incomplete type declaration. In the following example, <code>f1</code> refers to the outer struct: <pre>struct x { . . . } s1; {struct x; struct y {struct x f1; } s2; struct x { . . . };}</pre>	In an ISO-conforming implementation, an incomplete struct or union type specifier hides an enclosing declaration with the same tag.
Mismatch on struct/union/enum declarations	Allows a mismatch on the struct/enum/union type of a tag in nested struct/union declarations. In the following example, the second declaration is treated as a struct: <pre>struct x { . . . }s1; {union x s2; . . .}</pre>	Treats the inner declaration as a new declaration, hiding the outer tag.
Labels in expressions	Treats labels as <code>(void *)</code> lvalues.	Does not allow labels in expressions.
switch condition type	Allows <code>float(s)</code> and <code>double(s)</code> by converting them to <code>int(s)</code> .	Evaluates only integral types (<code>int</code> , <code>char</code> , and enumerated) for the switch condition type.
Syntax of conditional inclusion directives	The preprocessor ignores trailing tokens after an <code>#else</code> or <code>#endif</code> directive.	Disallows such constructs.

TABLE H-1 K&R Sun C Incompatibilities With Sun ISO C (Continued)

Topic	Sun C (K&R)	Sun ISO C
Token-pasting and the ## preprocessor operator	Does not recognize the ## operator. Token-pasting is accomplished by placing a comment between the two tokens being pasted: #define PASTE(A,B) A/*any comment*/B	Defines ## as the preprocessor operator that performs token-pasting, as shown in this example: #define PASTE(A,B) A##B Furthermore, the Sun ISO C preprocessor doesn't recognize the Sun C method. Instead, it treats the comment between the two tokens as white space.
Preprocessor rescanning	The preprocessor recursively substitutes: #define F(X) X(arg) F(F) yields arg(arg)	A macro is not replaced if it is found in the replacement list during the rescan: #define F(X)X(arg) F(F) yields: F(arg)
typedef names in formal parameter lists	You can use typedef names as formal parameter names in a function declaration. "Hides" the typedef declaration.	Disallows the use of an identifier declared as a typedef name as a formal parameter.
Implementation-specific initializations of aggregates	Uses a bottom-up algorithm when parsing and processing partially elided initializers within braces: struct{ int a[3]; int b; }\nw[]={1,2}; yields sizeof(w)=16 w[0].a=1,0,0 w[0].b=2	Uses a top-down parsing algorithm. For example: struct{int a[3];int b;}\nw[]={1,2}; yields sizeof(w)=32 w[0].a=1,0,0 w[0].b=0 w[1].a=2,0,0 w[1].b=0
Comments spanning include files	Allows comments which start in an #include file to be terminated by the file that includes the first file.	Comments are replaced by a white-space character in the translation phase of the compilation, which occurs before the #include directive is processed.

TABLE H-1 K&R Sun C Incompatibilities With Sun ISO C (*Continued*)

Topic	Sun C (K&R)	Sun ISO C
Formal parameter substitution within a character constant	Substitutes characters within a character constant when it matches the replacement list macro: <pre>#define charize(c) 'c'</pre> charize(Z) yields: 'Z'	The character is not replaced: <pre>#define charize(c) 'c'</pre> charize(Z) yields: 'c'
Formal parameter substitution within a string constant	The preprocessor substitutes a formal parameter when enclosed within a string constant: <pre>#define stringize(str)</pre> 'str' stringize(foo) yields: "foo"	The # preprocessor operator should be used: <pre>#define stringize(str)</pre> 'str' stringize(foo) yields: "str"
Preprocessor built into the compiler "front-end"	Compiler invokes <code>cpp(1)</code> followed by all the other components of the compilation system depending on the options specified.	The ISO C translation phases 1-4, which cover the processing of preprocessor directives, is built directly into <code>acompp</code> , so <code>cpp</code> is not directly invoked during compilation, except in <code>-Xs</code> mode.
Line concatenation with backslash	Does not recognize the backslash character in this context.	Requires that a newline character immediately preceded by a backslash character be spliced together.
Trigraphs in string literals	Does not support this ISO C feature.	
asm keyword	<code>asm</code> is a keyword.	<code>asm</code> is treated as an ordinary identifier.
Linkage of identifiers	Does not treat uninitialized <code>static</code> declarations as tentative declarations. As a consequence, the second declaration will generate a 'redeclaration' error, as in: <pre>static int i = 1;</pre> <pre>static int i;</pre>	Treats uninitialized <code>static</code> declarations as tentative declarations.

TABLE H-1 K&R Sun C Incompatibilities With Sun ISO C (*Continued*)

Topic	Sun C (K&R)	Sun ISO C
Name spaces	Distinguishes only three: <code>struct/union/enum</code> tags, members of <code>struct/union/enum</code> , and everything else.	Recognizes four distinct name spaces: label names, tags (the names that follow the keywords <code>struct</code> , <code>union</code> or <code>enum</code>), members of <code>struct/union/enum</code> , and ordinary identifiers.
<code>long double</code> type	Not supported.	Allows <code>long double</code> type declaration.
Floating point constants	The floating point suffixes, <code>f</code> , <code>l</code> , <code>F</code> , and <code>L</code> , are not supported.	
Unsuffixed integer constants can have different types	The integer constant suffixes <code>u</code> and <code>U</code> are not supported.	
Wide character constants	Does not accept the ISO C syntax for wide character constants, as in: <code>wchar_t wc = L'x';</code>	Supports this syntax.
' <code>\a</code> ' and ' <code>\x</code> '	Treats them as the characters ' <code>a</code> ' and ' <code>x</code> '.	Treats ' <code>\a</code> ' and ' <code>\x</code> ' as special escape sequences.
Concatenation of string literals	Does not support the ISO C concatenation of adjacent string literals.	
Wide character string literal syntax	Does not support the ISO C wide character, string literal syntax shown in this example: <code>wchar_t *ws = L"hello";</code>	Supports this syntax.
Pointers: <code>void *</code> versus <code>char *</code>	Supports the ISO C <code>void *</code> feature.	
Unary plus operator	Does not support this ISO C feature.	
Function prototypes—ellipses	Not supported.	ISO C defines the use of ellipses " <code>...</code> " to denote a variable argument parameter list.
Type definitions	Disallows <code>typedefs</code> to be redeclared in an inner block by another declaration with the same type name.	Allows <code>typedefs</code> to be redeclared in an inner block by another declaration with the same type name.

TABLE H-1 K&R Sun C Incompatibilities With Sun ISO C (*Continued*)

Topic	Sun C (K&R)	Sun ISO C
Initialization of <code>extern</code> variables	Does not support the initialization of variables explicitly declared as <code>extern</code> .	Treats the initialization of variables explicitly declared as <code>extern</code> , as definitions.
Initialization of aggregates	Does not support the ISO C initialization of unions or automatic structures.	
Prototypes	Does not support this ISO C feature.	
Syntax of preprocessing directive	Recognizes only those directives with a # in the first column.	ISO C allows leading white-space characters before a # directive.
The # preprocessor operator	Does not support the ISO C # preprocessor operator.	
<code>#error</code> directive	Does not support this ISO C feature.	
Preprocessor directives	Supports two pragmas, <code>unknown_control_flow</code> and <code>makes_regs_inconsistent</code> along with the <code>#ident</code> directive. The preprocessor issues warnings when it finds unrecognized pragmas.	Does not specify its behavior for unrecognized pragmas.
Predefined macro names	These ISO C-defined macro names are not defined: <code>__STDC__</code> <code>__DATE__</code> <code>__TIME__</code> <code>__LINE__</code>	

H.2 Keywords

The following tables list the keywords for the ISO C Standard, the Sun ISO C compiler, and the Sun C compiler.

The first table lists the keywords defined by the ISO C standard.

TABLE H-2 ISO C Standard Keywords

<code>_Bool¹</code>	<code>_Complex¹</code>	<code>_Imaginary¹</code>	<code>auto</code>
<code>break</code>	<code>case</code>	<code>char</code>	<code>const</code>
<code>continue</code>	<code>default</code>	<code>do</code>	<code>double</code>
<code>else</code>	<code>enum</code>	<code>extern</code>	<code>float</code>
<code>for</code>	<code>goto</code>	<code>if</code>	<code>inline¹</code>
<code>int</code>	<code>long</code>	<code>register</code>	<code>restrict*</code>
<code>return</code>	<code>short</code>	<code>signed</code>	<code>sizeof</code>
<code>static</code>	<code>struct</code>	<code>switch</code>	<code>typedef</code>
<code>union</code>	<code>unsigned</code>	<code>void</code>	<code>volatile</code>
<code>while</code>			

* Defined with `-xc99=all` only.

The C compiler also defines one additional keyword, `asm`. However, `asm` is not supported in `-Xc` mode.

Keywords in Sun C are listed below.

TABLE H-3 Sun C (K&R) Keywords

<code>asm</code>	<code>auto</code>	<code>break</code>	<code>case</code>
<code>char</code>	<code>continue</code>	<code>default</code>	<code>do</code>
<code>double</code>	<code>else</code>	<code>enum</code>	<code>extern</code>
<code>float</code>	<code>for</code>	<code>fortran</code>	<code>goto</code>
<code>if</code>	<code>int</code>	<code>long</code>	<code>register</code>
<code>return</code>	<code>short</code>	<code>sizeof</code>	<code>static</code>
<code>struct</code>	<code>switch</code>	<code>typedef</code>	<code>union</code>
<code>unsigned</code>	<code>void</code>	<code>while</code>	

Index

Symbols

- #, 4-4, B-2
- ###, 4-4, B-3
- #assert, 2-9, B-3
- #define, B-4
- #include, adding header files with, 2-27
- #pragma, 2-10 to 2-23, 5-2 to 5-5
- .profile filename extension, B-84
- // comment indicators
 - in C99, D-4
 - with -xCC, B-38
- _ _asm keyword, 2-25
- _ _STDC_ _ value under -xC, B-25
- __'uname -s'__'uname -r', 2-24, 4-22, B-4
- __amd64, 4-16
- __BUILT_IN_VA_ARG_INCR, 2-24, 4-22, B-4
- __DATE__, E-12
- __func__, D-4
- __global, 2-3
- __hidden, 2-3
- __i386, 2-24, 4-22, B-4
- __lint predefined token, 4-22
- __PRAGMA_REDEFINE_EXTNAME, 2-24
- __RESTRICT, 2-24, 4-22, B-4
- __sparc, 2-24, 4-22, B-4
- __sparcv9, 4-16, 4-22, B-4
- __sun, 2-24, 4-22, B-4
- __SUNPRO_C, 2-24, 4-22, B-4
- __SVR4, 2-24, 4-22, B-4
- __symbolic, 2-3

- __thread, 2-3
- __TIME__, E-12
- __unix, 2-24, 4-22, B-4
- __x86_64, 4-16
- _Exit function, C-16
- _OPENMP preprocessor token, B-70
- _Pragma, D-13
- _REENTRANT-lthread, B-20
- _Restrict, 2-25

A

- A, B-3
- a, 4-4
- abort function, C-16
- accessible documentation, -xxxviii
- acomp (C compiler), 1-8
- alias disambiguation, 5-1 to 5-18
- alignment of structures, E-8
- alphabetic list of compiler options, B-1 to B-104
- any level alias disambiguation, B-27
- arithmetic conversions, 2-8 to 2-9
- array
 - declarators per C99, D-9
 - incomplete array types per C99, D-6
- asctime function, 4-9
- _ _asm keyword, 2-25
- assembler, 1-8
- assembly in source, 2-25
- assembly language templates, B-102
- #assert, 2-9, B-3

- B**
- B, B-3
- b, 4-4
- basic level alias disambiguation, B-27
- basic mode of `lint`, 4-1
- behavior, implementation-defined, E-1 to E-19
- Binary Interface Descriptors (BIDS), B-66
- binary optimization, B-37
- binding, static vs. dynamic, B-3
- bit-field
 - as impacted by transition to ISO C, 6-38
 - portability of constants assigned to, 4-28
 - promotion of, 6-11
 - treating as signed or unsigned, E-9
- bits, in execution character set, E-3
- bitwise operations on signed integers, E-5
- buffering, E-17
- C**
- C, 4-5, B-4
- c, 4-5, B-4
- C compiler
 - changing default dirs searched for libraries, B-2
 - compilation modes and dependencies, 2-23
 - compiling a program, B-1 to B-2
 - components, 1-8
 - options passed to linker, B-104
- C programming tools, 1-8
- C99
 - // comment indicators, D-4
 - `__func__` support, D-4
 - `_Pragma`, D-13
 - array declarator, D-9
 - flexible array members, D-6
 - `FLT_EVAL_METHOD`, D-2
 - idempotent qualifiers, D-7
 - implicit function declaration in, D-5
 - inline function specifier, D-8
 - list of keywords, D-3
 - mixed declarations and code, D-11
 - Sun's implementation of, C-1 to C-24
 - type declaration in `for` loop, D-12
 - type specifier requirement, D-5
 - variable length arrays, D-9
- cache, as used by optimizer, B-39
- `calloc` function, C-16
- case statements, E-10
- cc compiler options, B-2 to B-104
 - #, A-8, B-2
 - ###, A-8, B-3
 - A, A-7, B-3
 - B, A-11, B-3
 - C, A-7, B-4
 - c, A-8, B-4
 - D, A-7, B-4
 - d, A-11, B-5, B-16
 - interaction with -G, B-16
 - E, A-7, B-5
 - errfmt, A-9, B-5
 - erroff, A-9, B-6
 - errshort, A-9, B-6
 - errtags, A-9, B-7
 - errwarn, A-10, B-7
 - fast, A-1, A-3, B-8
 - fd, A-7, B-10
 - features, A-8, B-11
 - flags, B-11
 - flteval, A-5, A-12, B-11
 - interaction with `FLT_EVAL_METHOD`, D-3
 - fnonstd, A-5
 - fns
 - as part of -fast expansion, B-9
 - grouped by functionality, A-5
 - syntax, B-12
 - fprecision, A-5, A-12, B-13
 - interaction with `FLT_EVAL_METHOD`, D-3
 - interaction with -flteval, B-12
 - fround, A-5, B-13
 - interaction with -xlibmopt, B-59
 - fsimple
 - as part of -fast expansion, B-9
 - grouped by functionality, A-5
 - syntax, B-13
 - fsingle
 - as part of -fast expansion, B-9
 - grouped by functionality, A-5
 - interaction with `FLT_EVAL_METHOD`, D-3
 - syntax, B-15
 - fstore, A-5, A-12, B-15
 - ftrap
 - grouped by functionality, A-5
 - syntax, B-15
 - G, A-11, B-16
 - g, A-10, B-16
 - H, A-7, B-17

- h, A-11, B-18
- I, A-7, B-18
- i, A-11, B-18
- keeptmp, A-8, B-19
- KPIC, B-18
- Kpic, B-19
- L, A-11, B-19
- l, A-11, B-19
- mc, A-11, B-19
- mr, A-11, B-20
- mt, A-3, A-6, B-20
- native, B-20
- nofstore
 - as part of `-fast` expansion, B-9
 - grouped by functionality, A-5, A-12
 - interaction with `-flteval`, B-12
 - syntax, B-21
- O, B-21
- o, A-8, B-21
- P, A-7, B-21
- p, A-1, A-3
- Q, A-11, B-22
- qp, B-22
- R, A-11, B-22
- S, A-8, B-22
- s, A-10, B-22
- U, A-7, B-23
- V, A-8, B-23
- v, A-10, B-23
- W, A-8, B-24
- w, A-10, B-25
- X, A-7, A-9, B-25
 - interaction with `FLT_EVAL_METHOD`, D-3
- xalias_level
 - as part of `-fast` expansion, B-9
 - examples, 5-8 to 5-18
 - explanation, 5-1
 - grouped by functionality, A-1
 - syntax, B-26
- xarch
 - grouped by functionality, A-3, A-12
 - interaction with `FLT_EVAL_METHOD`, D-3
 - interaction with `-flteval`, B-12
 - syntax, B-29
- xautopar, A-3, A-6, B-36
- xbinopt
 - grouped by functionality, A-2
 - syntax, B-37
- xbuiltin
 - as part of `-fast` expansion, B-9
 - grouped by functionality, A-2
 - syntax, B-38
- xc99
 - grouped by functionality, A-7, A-9
 - in math conversions, 2-9
 - syntax, B-38
- xcache, A-12
- xCC, A-7, B-38
- xchar, A-7, A-9, B-41
- xchar_byte_order, A-4, B-42
- xcheck, A-6, A-10, B-42
- xchip, A-12, B-43
- xcode, A-11, B-45
- xcrossfile, A-2, B-47
- xcsi, A-7, B-47
- xdebugformat, A-10, B-48
- xdepend
 - as part of `-fast` expansion, B-9
 - grouped by functionality, A-2, A-4, A-5
 - syntax, B-48
- xdryrun, B-49
- xe, A-10, B-49
- xexplicitpar, A-3, A-6, B-49
- xF, A-2, B-50
- xhelp, A-9, B-51
- xhwcpref, A-2, A-3, B-51
- xinline, A-2, B-52
- xipo, A-2, A-4, B-54
- xipo_archive, A-2, B-56
- xjobs, A-2, A-9, B-57
- xldscope, 2-3, A-11, B-57
- xlibieee, A-5, B-59
- xlibmil
 - as part of `-fast` expansion, B-9
 - grouped by functionality, A-2
 - syntax, B-59
- xlibmopt, A-2, B-59
 - as part of `-fast` expansion, B-9
- xlic_lib, A-2
- xlicinfo, A-13
- xlinkopt, A-2, A-4, B-60
 - interaction with `-G`, B-60
- xloopinfo, A-6, B-61
- xM, A-7, B-61
- xM1, A-7, B-62
- xmaxopt, A-2, B-63
 - interaction with `-xO`, B-63
- xmalign

- as part of `-fast` expansion, B-9
- grouped by functionality, A-4
- syntax, B-63
- `-xMerge`, A-11, B-63
- `-xmodel`, A-12, B-64
- `-xnativeconnect`, A-11, B-65
- `-xnolib`, A-11, B-66
- `-xnolibmil`, A-2, A-11, B-66
- `-xnolibmopt`, A-2, B-67
 - interaction with `-xlibmopt`, B-59
- `-xO`
 - grouped by functionality, A-2
 - interaction with `-xmaxopt`, B-68
 - syntax, B-67
- `-xopenmp`, A-4, A-5, A-6, B-70
- `-xP`, A-7, B-71
- `-xpagesize`, A-2, A-4, A-10, B-71
- `-xpagesize_heap`, A-2, A-4, A-10, B-72
- `-xpagesize_stack`, A-2, A-4, A-10, B-73
- `-xparallel`, A-4, A-6, B-74
- `-xpch`, A-2, A-9, B-74
- `-xpchstop`, A-2, A-9, B-80
- `-xpentium`, A-2, A-12, B-80
- `-xpg`, A-4, A-7, B-80
- `-xprefetch`
 - grouped by functionality, A-2
 - syntax, B-81
- `-xprefetch_auto_type`, A-3, B-82
- `-xprefetch_level`, A-3, B-83
- `-xprofile`, A-3, A-4, B-84
- `-xprofile_ircache`, A-3, B-86
- `-xprofile_pathmap`, A-3, B-87
- `-xreduction`, A-6, B-87
- `-xregs`, A-12, B-88
- `-xrestrict`, A-3, B-90
- `-xs`, A-10, B-90
- `-xsafe`, A-3, B-90
- `-xsb`, A-4, A-7, B-91
- `-xsbfast`, A-8, B-91
- `-xsfpconst`, A-5, B-91
- `-xspace`, A-3, B-92
- `-xstrconst`, A-11, B-92
- `-xtarget`
 - grouped by functionality, A-12
 - syntax, B-92
- `-xtemp`, A-9, B-97
- `-xtime`, A-9, B-98
- `-xtransition`, A-10, B-98
 - warning for trigraphs, 6-14

- `-xtrigraphs`, A-8, B-99
- `-xunroll`, A-3, B-100
- `-xustr`, A-8, B-100
- `-xvector`, A-4, A-5, B-101
- `-xvis`, A-10, B-102
- `-xvpara`, A-6, A-10, B-102
- `-Y`, A-9, B-103
- `-YA`, A-9, B-103
- `-YI`, A-9, B-103
- `-YP`, A-9, B-2, B-103
- `-YS`, A-9, B-103
- `-Zll`, A-6, B-104
- `cftime` function, 4-9
- `cg` (code generator), 1-8
- `char`
 - signedness of, B-41
 - storage allocation for, F-1
- character
 - bits in set, E-3
 - decimal point, E-18
 - mapping set, E-3
 - multibyte, shift status, E-3
 - set, collation sequence, E-19
 - single-character character-constant, E-10
 - source and execution of set, E-3
 - space, E-16
 - testing of sets, E-13
- `clock` function, C-17, E-18
- code generator, 1-8
- code optimization
 - by using `-fast`, B-8
 - optimizer, 1-8
 - with `-xO`, B-67
- comments
 - preventing removal by preprocessor, B-4
 - using `//` by issuing `-xCC`, B-38
 - using `//` in C99, D-4
- compatibility options, B-1, B-25
- compilation mode options, list of, A-8
- compiled code options, list of, A-8
- compiler commentary in object file, reading with `er_src` utility, B-38
- compiler options grouped by function, A-1 to A-13
- compilers, accessing, `-xxxiv`
- computed `goto`, 2-5
- consistency checks by `lint`, 4-26

const, 6-17 to 6-20, 6-37
 constants
 promotion of integral, 6-11
 specific to Sun ISO C, 2-1 to 2-2
 conversions, 2-8 to 2-9
 integers, E-5
 cpp (C preprocessor), 1-8
 creat function, 4-9
 cscope, 8-1 to 8-20
 command-line use, 8-3 to 8-4, 8-11 to 8-13
 editing source files, 8-2 to 8-3, 8-10 to 8-11, 8-19 to 8-20
 environment setup, 8-2 to 8-3, 8-20
 environment variables, 8-14
 searching source files, 8-1 to 8-2, 8-3, 8-4 to 8-10
 See also Source Browser
 usage examples, 8-2 to 8-11, 8-15 to 8-19

D

-D, B-4
 -d, B-5
 data alignment, list of compiler options for, A-4
 data reordering, B-50
 data types
 long long, 2-8
 unsigned long long, 2-8
 __DATE__, C-11, E-12
 date and time formats, E-19
 dbx tool
 disable Auto-Read for, B-90
 symbol table information for, B-16
 debugger data format, B-48
 debugging information, removing, B-22
 debugging, list of compiler options for, A-10
 decimal-point character, E-18
 declaration specifiers
 __global, 2-3
 __hidden, 2-3
 __symbolic, 2-3
 __thread, 2-3
 declarators, E-10
 default
 compiler behavior, B-25
 handling and SIGILL, E-16
 locale, E-4
 default dirs searched for libraries, B-2

#define, B-4
 diagnostics, format, E-1
 diagnostics, list of compiler options for, A-9
 -dirout, 4-5
 documentation index, -xxxvii
 documentation, accessing, -xxxvii to ??
 domain errors, math functions, E-13
 double, storage allocation for, F-2
 dwarf debugger-data format, B-48
 dynamic linking, B-5

E

-E, B-5
 edit, source files, *See* cscope
 EDITOR, 8-2, 8-19
 elfdump, B-46
 ellipsis notation, 6-3, 6-6, 6-38
 enhanced mode of lint, 4-1
 environment variable
 EDITOR as used by cscope, 8-2, 8-19
 LANG
 in C90, E-4
 in C99, C-6, C-22
 LC_ALL
 in C90, E-4
 in C99, C-6
 LC_CTYPE
 in C90, E-4
 in C99, C-6
 OMP_DYNAMIC, 2-25
 OMP_NESTED, 2-26
 OMP_NUM_THREADS, 2-26
 OMP_SCHEDULE, 2-26
 PARALLEL, 2-26, B-37
 PARALLEL example, 3-3
 STACKSIZE, 3-4
 SUN_PROFDATA, 2-26, B-84
 SUN_PROFDATA_DIR, 2-26, B-84
 SUNPRO_MP_THR_IDLE, 2-27
 SUNPRO_SB_INIT_FILE_NAME, 2-26
 SUNW_MP_THR_IDLE, 3-3
 SUNW_MP_WARN, 3-4
 TCOVDIR, B-85
 TERM as used by cscope, 8-2
 TMPDIR, 2-27
 TZ, E-18
 VPATH as used by cscope, 8-3

- er_src utility, B-38
- ERANGE, E-14
- ERANGE macro, C-13
- err, 4-5
- errchk, 4-5
- errfmt, 4-6, B-5
- errhdr, 4-7
- errno
 - C98 implementation of, E-14
 - header file, 6-26
 - impact of -fast on, B-8, B-9
 - impact of finalization functions on, 2-13
 - impact of initialization functions on, 2-15
 - impact of -xbuiltin on, B-38
 - impact of -xlibmieee on, B-59
 - impact of -xlibmil on, B-59
 - impact of -xlibmopt on, B-59
 - preserving value of, 2-24
 - setting value to ERANGE on underflow, C-13, C-15, C-16
- erroff, 4-7, B-6
- error messages, E-1
 - adding prefix "error:" to, B-5
 - controlling length for a type mismatch, B-6
 - suppressing in lint, 4-7
- errsecurity, 4-8
- errshort, B-6
- errtags, 4-10, B-7
- errwarn, 4-10, B-7
- exec function, 4-9
- expressions, grouping and evaluation in, 6-30 to 6-33

F

- F, 4-11
- fast, B-8
- fbe (assembler), 1-8
- fclose function, C-16
- fd, 4-11, B-10
- features, B-11
- fegetexceptflag function, C-12
- feraiseexcept function, C-12
- fgetc function, 4-9
- fgetpos function, C-15
- filename, .profile extension for, B-84

- files
 - temporary, 2-27
- filters for lint, 4-32 to 4-33
- flags, B-11
- flagsrc, 4-11
- float expressions as single precision, B-15
- float, storage allocation for, F-2
- float.h
 - in C90, D-2
 - macros defined in, C-17
- floating point, E-6
 - gradual underflows, 2-4
 - list of compiler options for, A-5
 - nonstop, 2-4
 - representations, E-6
 - truncation, E-7
 - values, E-6
- FLT_EVAL_METHOD
 - evaluation format in C99, D-2
 - impact on accuracy of library functions, C-7
 - impact on float_t and double_t, C-12
 - non-standard negative values of, C-7
- flteval, B-11
- fmod function, C-13
- fns, B-12
- fopen function, 4-9
- for loop that contains a type declaration, D-12
- fprecision, B-13
- fprintf function, C-15, E-17
- free function, C-16
- fround, B-13
- fscanf function, C-15, E-18
- fsetpos function, C-15
- fsimple, B-13
- fsingle, B-15
- fstore, B-15
- ftell function, C-15
- ftrap, B-15
- function
 - _Exit, C-16
 - abort, C-16
 - asctime, 4-9
 - calloc, C-16
 - cftime, 4-9
 - clock, C-17, E-18

- creat, 4-9
- declaration specifier, 2-3
- exec, 4-9
- fclose, C-16
- fegetexceptflag, C-12
- feraiseexcept, C-12
- fgetc, 4-9
- fgetpos, C-15
- fmod, C-13, E-14
- fopen, 4-9
- fprintf, C-15, E-17
- free, C-16
- fscanf, C-15, E-18
- fsetpos, C-15
- ftell, C-15
- fwprintf, C-15
- fwscanf, C-15
- getc, 4-9
- getenv, C-4
- gets, 4-9
- getutxent, 7-15
- ilogb, C-12
- ilogbf, C-12
- ilogbl, C-12
- implicit declaration of, D-5
- isalnum, E-13
- isalpha, C-22, E-13
- isatty, C-2
- iscntrl, E-13
- islower, E-13
- isprint, E-13
- isupper, E-13
- iswalph, C-22
- iswctype, C-24
- main, C-2
- malloc, C-16
- printf, C-15
- prototypes, 4-26, 6-2 to 6-6
- prototypes, lint checks for, 4-31
- realloc, C-16
- remove, C-14, E-17
- rename, C-14, E-17
- reordering, B-50
- scanf, 4-9
- setlocale, C-12
- signal, C-2
- sizeof, 7-13
- stat, 4-9
- strerror, C-23

- strftime, C-17
- strncpy, 4-9
- strtod, C-16
- strtof, C-16
- strtold, C-16
- sunw_mp_register, 3-2
- system, C-4, C-17
- towctrans, C-23
- using varying argument lists, 6-6 to 6-8
- wait, C-17
- wait3, C-17
- waitid, C-17
- waitpid, C-17
- wcsftime, C-17
- wcstod, C-16
- wcstof, C-16
- wcstold, C-16
- fwprintf function, C-15
- fwscanf function, C-15

G

- G, B-16
- g, B-16
- getc function, 4-9
- getenv function, C-4
- gets function, 4-9
- getutxent function, 7-15
- gradual underflows, 2-4

H

- H, B-17
- h, 4-11, B-18
- hardware architecture, B-29
- header files
 - float.h in C90, D-2
 - format for #include directives, 2-27
 - how to include, 2-27 to 2-28
 - list of standard headers, 6-24
 - standard place, 2-27 to 2-28
 - sunmedia_intrin.h, 1-2
 - with lint, 4-3
- heap, setting page size for, B-71

I

- I, 4-11, B-18
- i, B-18

- i386 predefined token, 2-24, 4-22, B-4
- idempotent qualifier in C99, D-7
- ilogb function, C-12
- ilogbf function, C-12
- ilogbl function, C-12
- implementation-defined behavior, E-1 to E-19
- incomplete types, 6-33 to 6-35
- inline expansion templates, B-59, B-66
- inline function specifier for C99, D-8
- inlining, B-59
- int, storage allocation for, F-1
- integers, E-4 to E-5
- integral constants, promotion of, 6-11
- interactive device, E-2
- internationalization, 6-21 to 6-24, 6-27 to 6-30
- interprocedural analysis pass, B-54
- ipo (C compiler), 1-8
- ir2hf (C compiler), 1-8
- iropt (code optimizer), 1-8
- isalnum function, E-13
- isalpha function, C-22, E-13
- isatty function, C-2
- isctr1 function, E-13
- islower function, E-13
- ISO C vs. K&R C, B-1, B-25 to B-26
- ISO/IEC 9899:1999 Programming Language C, 1-4, D-1
- ISO/IEC 9899-1990 standard, 2-1
- isprint function, E-13
- isupper function, E-13
- iswalpha function, C-22
- iswctype function, C-24

J

- ja_JP.PCK locale, B-47
- Java Native Interface, B-65
- JNI, B-65

K

- k, 4-11
- K&R C vs. ISO C, B-1, B-25 to B-26
- keeptmp, B-19
- keywords, 2-25
 - list for C99, D-3

L

- L, 4-11, B-19
- l, 4-12, B-19
- LANG environment variable
 - in C90, E-4
 - in C99, C-6, C-22
- layout level alias disambiguation, B-28
- LC_ALL environment variable
 - in C90, E-4
 - in C99, C-6
- LC_CTYPE environment variable
 - in C90, E-4
 - in C99, C-6
- ld (C compiler), 1-8
- libfast.a, G-2
- libraries
 - building shared libraries, B-46
 - default dirs searched by cc, B-2
 - intrinsic name, B-18
 - libfast.a, G-2
 - lint, 4-31 to 4-32
 - llib-lx.ln, 4-31
 - renaming shared, B-18
 - shared or non shared, B-3
 - specifying dynamic or static links, B-3
 - sun_prefetch.h, B-82
- library bindings, B-3
- licensing options, list of, A-13
- limit of memory allocation on stack, F-1
- limits.h
 - macros defined in, C-19
- link, static vs. dynamic, B-5
- linker
 - options received from compiler, B-104
 - specifying dynamic or static linking in, B-5
 - suppressing linking with, B-4
- linking and libraries, list of compiler options for, A-11
- link-time optimization, B-60
- link-time options, list of, A-3
- lint
 - basic mode
 - introduced, 4-1
 - invoking, 4-2
 - commands
 - #, 4-4

- ###, 4-4
- a, 4-4
- b, 4-4
- C, 4-5
- c, 4-5
- dirout, 4-5
- err=warn, 4-5
- errchk, 4-5
- errfmt, 4-6
- errhdr, 4-7
- erroff, 4-7
- errsecurity, 4-8
- errtags, 4-10
- errwarn, 4-10
- F, 4-11
- fd, 4-11
- flagsrc, 4-11
- h, 4-11
- I, 4-11
- k, 4-11
- L, 4-11
- l, 4-12
- m, 4-12
- n, 4-14
- Ncheck, 4-12
- Nlevel, 4-13
- o, 4-14
- p, 4-14
- R, 4-14
- s, 4-15
- u, 4-15
- V, 4-15
- v, 4-15
- W, 4-15
- x, 4-18
- Xalias_level, 4-16
- Xarch=amd64, 4-16
- Xarch=v9, 4-16
- Xc99, 4-16
- XCC, 4-15
- Xexplicitpar, 4-17
- Xkeeptmp, 4-17
- Xtemp, 4-17
- Xtime, 4-17
- Xtransition, 4-17
- Xustr, 4-18
- y, 4-18
- consistency checks, 4-26
- diagnostics, 4-26 to 4-31
- directives, 4-22 to 4-26
- enhanced mode
 - introduced, 4-1
 - invoking, 4-2
- filters, 4-32 to 4-33
- header files, finding, 4-3
- how `lint` examines code, 4-2
- introduction to, 4-1
- libraries, 4-31 to 4-32
- messages
 - formats of, 4-19 to 4-21
 - message ID (tag), identifying, 4-10, 4-18
 - suppressing, 4-18
- portability checks, 4-27 to 4-29
- predefined tokens, 4-22
- predefinition, 2-9
- questionable constructs, 4-29 to 4-31
- recognized `cc` commands, 4-4
- `llib-lx.ln` library, 4-31
- local time zone, E-18
- locale, 6-27, 6-29
 - behavior, E-18
 - default, E-4
 - `ja_JP.PCK`, B-47
 - use of non-conforming, B-47
- long
 - storage allocation for, F-1
- long double
 - passing in ISO C, F-11
 - storage allocation for, F-2
- long int, 2-8
- long long, 2-8 to 2-9
 - arithmetic promotions, 2-8
 - passing, F-11
 - representation of, F-4
 - returning, F-11
 - storage allocation for, F-2
 - suffix, 2-1
 - value preserving, 2-2
- long, storage allocation for, F-1
- loops, B-48

M

- m, 4-12
- macro expansion, 6-15
- macros
 - `__DATE__`, C-11, E-12

- __RESTRICT, 2-24
- __TIME__, C-11, E-12
- ERANGE, C-13
- FLT_EVAL_METHOD, C-12, D-2
- NULL, C-13
 - those specified in `float.h`, C-17
 - those specified in `limits.h`, C-19
 - those specified in `stdint.h`, C-20
- main function, C-2
- main, semantics of args, E-2
- malloc function, C-16
- man pages, accessing, -xxxiv, 1-6
- MANPATH environment variable, setting, -xxxvi
- math functions, domain errors, E-13
 - mc, B-19
- mcs (C compiler), 1-8
- memory allocation on the stack, F-1
- message ID (tag), B-6, B-7
- messages
 - error, E-1
- mode, compiler, B-25 to B-26
- MP C, 3-1 to 3-30
 - mr, B-20
 - mt, B-20
- multibyte characters and wide characters, 6-21 to 6-24
- multimedia types, handling of, B-102
- multiprocessing, 3-1 to 3-30
 - xjobs, B-57

N

- n, 4-14
- native, B-20
- Native Connector Tool (NCT), B-65
 - Ncheck, 4-12
- NCT, B-65
- new features of this release, 1-1 to 1-3
- newline, terminating, E-16
 - Nlevel, 4-13
 - nofstore, B-21
- nonstop
 - floating-point arithmetic, 2-4
- null characters not appended to data, E-16
- NULL macro, C-13

- NULL, value of, E-12

O

- O, B-21
- o, 4-14, B-21
- object file
 - linking with `ld`, B-4
 - producing object file for each source file, B-4
 - reading compiler commentary with `er_src` utility, B-38
 - suppressing removal of, B-4
- obsolete options, list of, A-13
- OMP_DYNAMIC environment variable, 2-25
- OMP_NESTED environment variable, 2-26
- OMP_NUM_THREADS environment variable, 2-26
- OMP_SCHEDULE environment variable, 2-26
- OpenMP
 - how to compile for, 3-2
 - `sunw_mp_register`, 3-2
 - xopenmp command, B-70
- optimization
 - at link time, B-60
 - fast and, B-8
 - for *SPARC*, G-1
 - list of compiler options for, A-1
 - optimizer, 1-8
 - `pragma opt` and, 2-17
 - specify hardware architecture, B-29
 - with `-xmaxopt`, B-63
 - xipo and, B-54
 - xO and, B-67
- options
 - compiler options grouped by functionality, A-1 to A-13
 - compiler options listed alphabetically, B-1 to B-104
 - lint, 4-4 to 4-18

P

- P, B-21
- p, 4-14
- padding of structures, E-8
- page size, setting for stack or heap, B-71
- PARALLEL, 3-3
 - as relates to `-xautopar`, B-37
 - environment variable, 2-26

parallelization, 3-1 to 3-30

- checking for properly parallelized loops with `-xvpara`, B-102
- creating a program database with `-zll`, B-104
- environment variables for, 3-2 to 3-5
- finding parallelized loops with `-xloopinfo`, B-61
- list of compiler commands for, A-6
- See also* OpenMP
- specifying multithread coding with `-mt`, B-20
- specifying OpenMP pragmas with `-xopenmp`, B-70
- turning on reduction recognition with `-xreduction`, B-87
- turning on with `-xautopar` for multiple processors, B-36
- with `-xexplicitpar`, B-49
- `-xparallel` macro, B-74

pass, name and version of each, B-23

PATH environment variable, setting, `-xxxv`

Pentium, B-97

performance

- optimizing for SPARC, G-1
- optimizing with `-fast`, B-8
- optimizing with `-xO`, B-67

portability checks performed by `lint`, 4-27 to 4-29

portability, of code, 4-27 to 4-29

postopt (C compiler), 1-8

`#pragma alias`, 5-3

`#pragma alias_level`, 5-3

`#pragma align`, 2-10

`#pragma c99`, 2-11

`#pragma does_not_read_global_data`, 2-11

`#pragma does_not_return`, 2-12

`#pragma does_not_write_global_data`, 2-12

`#pragma error_messages`, 2-12

`#pragma fini`, 2-13

`#pragma hdrstop`, 2-14

`#pragma ident`, 2-14

`#pragma init`, 2-14

`#pragma inline`, 2-15

`#pragma int_to_unsigned`, 2-15

`#pragma may_not_point_to`, 5-5

`#pragma may_piont_to`, 5-4

`#pragma MP serial_loop`, 2-16, 3-22

`#pragma MP serial_loop-nested`, 2-16, 3-22

`#pragma MP taskloop`, 2-16, 3-23

`#pragma no_inline`, 2-15

`#pragma no_side_effect`, 2-17

`#pragma noalias`, 5-4

`#pragma nomemorydepend`, 2-16

`#pragma opt`, 2-17

`#pragma pack`, 2-18

`#pragma pipelooop`, 2-19

`#pragma rarely_called`, 2-19

`#pragma redefine_extname`, 2-19

`#pragma returns_new_memory`, 2-21

`#pragma unknown_control_flow`, 2-21

`#pragma unroll`, 2-21

`#pragma warn_missing_parameter_info`, 2-22

`#pragma weak`, 2-23

preassertions for `-Aname`, B-3

precompiled-header file, B-74

predefined tokens

- `__'uname -s' 'uname -r'`, 2-24, 4-22, B-4
- `__amd64`, 4-16
- `__BUILTIN_VA_ARG_INCR`, 2-24, 4-22, B-4
- `__i386`, 2-24, 4-22, B-4
- `__lint`, 4-22
- `__RESTRICT`, 2-24, 4-22, B-4
- `__sparc`, 2-24, 4-22, B-4
- `__sparcv9`, 4-16, 4-22, B-4
- `__sun`, 2-24, 4-22, B-4
- `__SUNPRO_C`, 2-24, 4-22, B-4
- `__SVR4`, 2-24, 4-22, B-4
- `__unix`, 2-24, 4-22, B-4
- `__x86_64`, 4-16
- `i386`, 2-24, 4-22, B-4
- `lint`, 4-22
- `sparc`, 2-24, 4-22, B-4
- `sun`, 2-24, 4-22, B-4
- `unix`, 2-24, 4-22, B-4

prefetch, B-81

preprocessing, 6-13 to 6-17

- directives, 2-23, 2-27 to 2-28, B-4, E-10
- how to preserve comments, B-4
- predefined names, 2-23
- stringizing, 6-16
- token pasting, 6-17

preserving signedness of chars, B-41

- printf function, C-15
- printing, 2-8, E-18
- programming tools for C, 1-8
- promotion, 6-9 to 6-12
 - bit-fields, 6-11
 - default arguments, 6-3
 - integral constants, 6-11
 - value preserving, 6-9

Q

- Q, B-22
- qp, B-22
- qualifiers, E-10

R

- R, 4-14, B-22
- readme file, 1-5
- realloc function, C-16
- remove function, C-14, E-17
- removing symbolic debugging information, B-22
- rename function, C-14, E-17
- renaming shared libraries, B-18
- reordering functions and data, B-50
- representation
 - floating point, E-6
 - integers, E-4
- reserved names, 6-24 to 6-26
 - for expansion, 6-26
 - for implementation use, 6-25
 - guidelines for choosing, 6-26
- __RESTRICT macro, 2-24
- restrict keyword
 - as part of supported C99 features, D-3
 - as recognized by -xs, 3-21
 - as type qualifier in parallelized code, 3-21
 - as used in parallelized code, 3-5
- right shift, E-5
- rounding behavior, 2-4

S

- S, B-22
- s, 4-15, B-22
- scanf function, 4-9
- search, source files, *See* cscope
- setlocale function, C-12

- setlocale(3C), 6-27, 6-29
- shared libraries, naming, B-18
- shell prompts, -xxxiii
- short, storage allocation for, F-1
- signal, E-14 to E-16
- signal function, C-2
- signed, E-4
- signedness of chars, B-41
- sizeof function, 7-13
- slave thread default setting for STACKSIZE, 3-4
- source code options, list of, A-7
- source files
 - checking with lint, 4-1 to 4-33
 - compatibility of K&R C and ISO C, B-1
 - editing, *See* cscope
 - locating, E-11
 - searching, *See* cscope
- space characters, E-16
- sparc predefined token, 2-24, 4-22, B-4
- ssbd (C compiler), 1-8
- stabs debugger-data format, B-48
- stack
 - memory allocation maximum, F-1
 - setting page size for, B-71
- STACKSIZE environment variable, 3-4
- standards conformance, 1-4, 2-1
- stat function, 4-9
- static linking, B-5
- std level alias disambiguation, B-28
- stdint.h
 - macros defined in, C-20
- storage allocation for types, F-1
- streams, E-16
- strerror function, C-23
- strftime function, C-17
- strict level alias disambiguation, B-28
- string literals in text segment, B-92
- strncpy function, 4-9
- strong level alias disambiguation, B-28
- strtod function, C-16
- strtod function, C-16
- strtold function, C-16
- structure
 - alignment, E-8

- padding, E-8
- sun predefined token, 2-24, 4-22, B-4
- sun_prefetch.h, B-82
- SUN_PROFDATA
 - definition, 2-26
 - relating to `-xprofile`, B-84
- SUN_PROFDATA_DIR
 - definition, 2-26
 - relating to `-xprofile`, B-84
- SUNPRO_SB_INIT_FILE_NAME environment variable, 2-26
- sunw_mp_register_warn function, 3-2
- SUNW_MP_THR_IDLE environment variable, 2-27, 3-3
- SUNW_MP_WARN environment variable, 3-4
- symbol declaration specifier, 2-3
- symbolic debugging information, removing, B-22
- system function, C-4, C-17

T

- target-platform options, list of, A-12
- tcov
 - new style with `-xprofile`, B-85
- TCOVDIR environment variable, B-85
- Temporary files, 2-27
- TERM environment variable as used by `cscope`, 8-2
- text
 - segment and string literals, B-92
 - stream, E-16
- thread local storage of variables, 2-3
- threads, *See* parallelization
- `__TIME__`, C-11, E-12
- time and date formats, E-19
- `/tmp`, 2-27
- TMPDIR environment variable, 2-27
- tokens, 6-13 to 6-17
- tools for programming with C, 1-8
- `towctrans` function, C-23
- trigraph sequences, 6-13
- type-based alias-disambiguation, 5-1 to 5-18
- types
 - compatible and composite, 6-36 to 6-38
 - `const` and `volatile` qualifier, 6-17 to 6-21
 - declaration in `for` loop, D-12
 - declarations and code, D-11

- incomplete, 6-33 to 6-35
- specifier requirement in declaration, D-5
- storage allocation for, F-1
- typographic conventions, -xxxii
- TZ, E-18

U

- `-U`, B-23
- `-u`, 4-15
- ube (C compiler), 1-8
- ube_ipa (C compiler), 1-8
- unix predefined token, 2-24, 4-22, B-4
- unsigned, E-4
- unsigned long long, 2-8
- using assembly in source, 2-25

V

- `-v`, 4-15, B-23
- `-v`, 4-15, B-23
- value
 - floating point, E-6
 - integers, E-4
- `varargs(5)`, 6-3
- variable declaration specifier, 2-3
- variable length arrays in C99, D-9
- variable, thread-local storage specifier, 2-3
- viable prefix, B-77
- VIS Software Developers Kit, B-102
- volatile
 - compatible declarations with, 6-37
 - definition and examples, 6-20 to 6-21
 - explanation of keyword and usage, 6-17 to 6-19
 - in C90, E-10
- VPATH environment variable, 8-3

W

- `-W`, 4-15, B-24
- `-w`, B-25
- `wait` function, C-17
- `wait3` function, C-17
- `waitid` function, C-17
- `waitpid` function, C-17
- warning messages, E-1
- `wcsftime` function, C-17

wcstod function, C-16
wcstof function, C-16
wcstold function, C-16
weak level alias disambiguation, B-27
what's new in this release, 1-1 to 1-3
whole-program optimizations, B-54
wide character constants, 6-23 to 6-24
wide characters, 6-22 to 6-24
wide string literals, 6-23 to 6-24
write on text stream, E-16

X

-X, B-25
-x, 4-18
-Xalias_level, 4-16
-xalias_level, B-26
-Xarch=amd64, 4-16
-Xarch=v9, 4-16
-xarch, B-29
-xautopar, B-36
-xbinopt, B-37
-xbinopt and, B-37
-xbuiltin, B-38
-Xc99, 4-16
-xc99, B-38
-XCC, 4-15
-xCC, B-38
-xchar, B-41
-xchar_byte_order, B-42
-xcheck, B-42
-xchip, B-43
-xcode, B-45
-xcrossfile, B-47
-xcsi, B-47
-xdebugformat, B-48
-xdepend, B-48
-xdryrun, B-49
-xe, B-49
-Xexplicitpar, 4-17
-xexplicitpar, B-49
-xF, B-50
-xhelp, B-51
-xhwcprof, B-51
-xinline, B-52
-xipo, B-54
-xipo_archive, B-56
-xjobs, B-57
-Xkeeptmp, 4-17
-xldscope, B-57
-xlibmieee, B-59
-xlibmil, B-59
-xlibmopt, B-59
-xlinkopt, B-60
-xloopinfo, B-61
-xM, B-61
-xM1, B-62
-xmaxopt, B-63
-xmemalign, B-63
-xMerge, B-63
-xmodel, B-64
-xnativeconnect, B-65
-xnolib, B-66
-xnolibmil, B-66
-xnolibmopt, B-67
-xO, B-67
-xopenmp, B-70
-xP, B-71
-xpagesize, B-71
-xpagesize_heap, B-72
-xpagesize_stack, B-73
-xparallel, B-74
-xpch, B-74
-xpchstop, B-80
-xpentium, B-80
-xpg, B-80
-xprefetch, B-81
-xprefetch_auto_type, B-82
-xprefetch_level, B-83
-xprofile, B-84
-xprofile_ircache, B-86
-xprofile_pathmap, B-87
-xreduction, B-87
-xregs, B-88
-xrestrict, B-90
-xs, B-90
-xsafe, B-90

- xsb, B-91
- xsbfast, B-91
- xsfpconst, B-91
- xspace, B-92
- xstrconst, B-92
- xtarget, B-92
- Xtemp, 4-17
- xtemp, B-97
- xthreadvar, B-97
- xthreadvar, compiler option, B-97
- Xtime, 4-17
- xtime, B-98
- Xtransition, 4-17
- xtransition, B-98
- xtrigraphs, B-99
- xunroll, B-100
- Xustr, 4-18
- xustr, B-100
- xvector, B-101
- xvis, B-102
- xvpara, B-102

Y

- Y, B-103
- y, 4-18
- YA, B-103
- YI, B-103
- YP, B-103
- YS, B-103

Z

- zero-length file, E-17
- zll, B-104

