



Solaris 8 4/01 What's New

Sun Microsystems, Inc.
901 San Antonio Road
Palo Alto, CA 94303-4900
U.S.A.

Part Number 816-0014-10
April 2001

Copyright 2001 Sun Microsystems, Inc. 901 San Antonio Road, Palo Alto, California 94303-4900 U.S.A. All rights reserved.

This product or document is protected by copyright and distributed under licenses restricting its use, copying, distribution, and decompilation. No part of this product or document may be reproduced in any form by any means without prior written authorization of Sun and its licensors, if any. Third-party software, including font technology, is copyrighted and licensed from Sun suppliers.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, docs.sun.com, AnswerBook, AnswerBook2, Solaris Management Console, iPlanet, Java, J2SE, Java Hotspot, Java Naming and Directory Interface, and Solaris are trademarks, registered trademarks, or service marks of Sun Microsystems, Inc. in the U.S. and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc. PostScript(TM) is a trademark or registered trademark of Adobe Systems, Incorporated, which may be registered in certain jurisdictions.

The OPEN LOOK and Sun™ Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

Federal Acquisitions: Commercial Software—Government Users Subject to Standard License Terms and Conditions.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright 2001 Sun Microsystems, Inc. 901 San Antonio Road, Palo Alto, Californie 94303-4900 Etats-Unis. Tous droits réservés.

Ce produit ou document est protégé par un copyright et distribué avec des licences qui en restreignent l'utilisation, la copie, la distribution, et la décompilation. Aucune partie de ce produit ou document ne peut être reproduite sous aucune forme, par quelque moyen que ce soit, sans l'autorisation préalable et écrite de Sun et de ses bailleurs de licence, s'il y en a. Le logiciel détenu par des tiers, et qui comprend la technologie relative aux polices de caractères, est protégé par un copyright et licencié par des fournisseurs de Sun.

Des parties de ce produit pourront être dérivées du système Berkeley BSD licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, docs.sun.com, AnswerBook, AnswerBook2, Solaris Management Console, iPlanet, Java, J2SE, Java Hotspot, Java Naming and Directory Interface, et Solaris sont des marques de fabrique ou des marques déposées, ou marques de service, de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays. Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc. PostScript est une marque de fabrique d'Adobe Systems, Incorporated, laquelle pourrait être déposée dans certaines juridictions. in the United States and other countries.

L'interface d'utilisation graphique OPEN LOOK et Sun™ a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciés de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui en outre se conforment aux licences écrites de Sun.

CETTE PUBLICATION EST FOURNIE "EN L'ETAT" ET AUCUNE GARANTIE, EXPRESSE OU IMPLICITE, N'EST ACCORDEE, Y COMPRIS DES GARANTIES CONCERNANT LA VALEUR MARCHANDE, L'APTITUDE DE LA PUBLICATION A REpondre A UNE UTILISATION PARTICULIERE, OU LE FAIT QU'ELLE NE SOIT PAS CONTREFAISANTE DE PRODUIT DE TIERS. CE DENI DE GARANTIE NE S'APPLIQUERAIT PAS, DANS LA MESURE OU IL SERAIT TENU JURIDIQUEMENT NUL ET NON AVENU.



Contents

- Preface 5**
- 1. What's New for Desktop Users 7**
- 2. What's New for System Administrators 9**
- 3. What's New for Installation 17**
- 4. What's New for Developers 19**

Preface

Solaris 8 4/01 What's New describes new features in Solaris™ Update releases. The following information adds to or supersedes information in the previous releases of Solaris 8 documentation sets. Solaris documentation is available on the Solaris 8 Documentation CD.

Solaris 8 4/01 What's New is a compilation of the “What's New at a Glance” chapters from the following four supplements:

Solaris 8 Desktop User Supplement

Solaris 8 System Administration Supplement

Solaris 8 Installation Supplement

Solaris 8 Software Developer Supplement

Note - The Solaris operating environment runs on two types of hardware, or platforms—SPARC™ and IA (Intel Architecture). The Solaris operating environment also runs on both 64-bit and 32-bit address spaces. The information in this document pertains to both platforms and address spaces unless called out in a special chapter, section, note, bullet, figure, table, example, or code example.

Ordering Sun Documents

Fatbrain.com, an Internet professional bookstore, stocks select product documentation from Sun Microsystems, Inc.

For a list of documents and how to order them, visit the Sun Documentation Center on Fatbrain.com at <http://www1.fatbrain.com/documentation/sun>.

Accessing Sun Documentation Online

The docs.sun.comSM Web site enables you to access Sun technical documentation online. You can browse the docs.sun.com archive or search for a specific book title or subject. The URL is <http://docs.sun.com>.

Typographic Conventions

The following table describes the typographic changes used in this book.

TABLE P-1 Typographic Conventions

Typeface or Symbol	Meaning	Example
AaBbCc123	The names of commands, files, and directories; on-screen computer output	Edit your <code>.login</code> file. Use <code>ls -a</code> to list all files. <code>machine_name% you have mail.</code>
AaBbCc123	What you type, contrasted with on-screen computer output	<code>machine_name% su</code> <code>Password:</code>
<i>AaBbCc123</i>	Command-line placeholder: replace with a real name or value	To delete a file, type <code>rm filename</code> .
<i>AaBbCc123</i>	Book titles, new words, or terms, or words to be emphasized.	Read Chapter 6 in <i>User's Guide</i> . These are called <i>class</i> options. You must be <i>root</i> to do this.

What's New for Desktop Users

This chapter highlights new desktop use features that have been added to the Solaris 8 operating environment for the Update releases. For further information on these features, see the *Solaris 8 Desktop User Supplement*.

Note - For the most current man pages, use the `man` command. The Solaris 8 Update release man pages include new feature information not found in the *Solaris 8 Reference Manual Collection*.

TABLE 1-1 Solaris 8 Update Features for Desktop Users

Feature Description	First Released
Window Manager Enhancements	
Graphical Workspace Manager provides a graphical representation of all workspaces, the ability to navigate across different workspaces with the press of a button, and the ability to drag and drop applications across different workspaces. With the 4/01 release, you are no longer limited to viewing nine workspaces. Also, the Graphical Workspace Manager Options dialog box has been added to provide a number of additional display options. For more information, see "Graphical Workspace Manager" in the <i>Solaris 8 Desktop User Supplement</i> .	6/00 Updated 4/01
Window List provides a list of all currently running applications. The Window List enables you, with the click of a mouse button, to locate any application, even those in workspaces other than the current workspace. The Window List also provides the ability to perform window actions on a selected group of applications. With the 4/01 release, you can choose to display or not display the Workspace column. For more information, see "Window List" in the <i>Solaris 8 Desktop User Supplement</i> .	6/00 Updated 4/01

TABLE 1-1 Solaris 8 Update Features for Desktop Users *(continued)*

Feature Description	First Released
<p>The Workspace Manager provides a graphical user interface (GUI) for controlling behavior and the number of workspaces. You can add and delete workspaces by using a slider. You can also display the Graphical Workspace Manager in the Workspace Switch Area of the Front Panel.</p>	4/01
<p>For more information, see “Workspace Manager” in the <i>Solaris 8 Desktop User Supplement</i>.</p>	
<p>Adding Multiple Files to Email</p>	
<p>This feature enables you to keep the Mailer - Attachment - Add dialog box open in order to add two or more files to an email. The need to select Add Files from the Attachment menu multiple times is eliminated.</p>	1/01
<p>For more information, see “Adding Multiple Files to Email” in the <i>Solaris 8 Desktop User Supplement</i>.</p>	
<p>Removable Media Manager</p>	
<p>Removable Media Manager centralizes access to removable devices in one window. You can format, query properties, view directory structures, and where applicable, protect and slice media.</p>	6/00 Updated 10/00
<p>For more information, see “Using Removable Media Manager” in the <i>Solaris 8 Desktop User Supplement</i>.</p>	
<p>Energy Star Standards</p>	
<p>X11R6.4 standards have been enhanced with Frame Buffer Power Management (FBPM), an extension to the Display Power Management System (DPMS). This enhancement is added to fulfill the U.S. government’s Energy Star program requirements and only works on Energy Star-compliant hardware.</p>	6/00
<p>Early Access</p>	
<p>This release includes an Early Access (EA) directory with EA software. For more information, see the <code>README</code> on the Solaris Software CD 2 of 2.</p>	

What's New for System Administrators

This chapter highlights new system administration features that have been added to the Solaris 8 Update releases. For further information on these features, see the *Solaris 8 System Administration Supplement*.

Note - For the most current man pages, use the `man` command. The Solaris 8 Update release man pages include new feature information not found in the *Solaris 8 Reference Manual Collection*.

TABLE 2-1 Solaris 8 Features for System Administrators

Description	First Released
Managing With System Administration Tools	
<p>Solaris Management Console™ (SMC) 2.0 is a GUI-based "umbrella application" that serves as the launching point for a variety of management tools. The SMC comes complete with a default toolbox that contains the following tools:</p>	1/01
<ul style="list-style-type: none"> ■ Processes – Suspend, resume, monitor, and control processes. ■ Users – Set up and maintain user accounts, user templates, groups, mailing lists, Administrative Roles, and Rights. Grant or deny rights to users and to administrative roles—to control the specific applications each can work with and which tasks each user can perform. ■ Scheduled Jobs – Schedule, start, and manage jobs. ■ Mounts and Shares – View and manage mounts, shares, and usage information. ■ Disks – Create and view disk partitions. ■ Serial Ports – Configure and manage existing serial ports. ■ Log Viewer – View application and command-line messages and manage log files. 	
<p>You can also manage diskless clients, but with commands only, not through the GUI.</p>	
<p>You can add or delete tools from the default toolbox or create a new toolbox to manage a different set of tools by using the SMC Toolbox Editor.</p>	
<p>For more information about using the command-line interface, see “Solaris Management Console Overview” in the <i>Solaris 8 System Administration Supplement</i>. For information on how to start SMC, see “Starting Solaris Management Console” in the <i>Solaris 8 System Administration Supplement</i>. Also, see the help associated with each tool.</p>	

TABLE 2-1 Solaris 8 Features for System Administrators (continued)

Description	First Released
<p>Web-based enterprise management (WBEM) includes standards for web-based management of systems, networks, and devices on multiple platforms. This standardization enables system administrators to manage desktops, devices, and networks.</p> <p>In the 10/00 Update release, additions include a description of the system properties that the CIM Object Manager uses and descriptions of the new <code>Solaris_Printer</code> and other printing definition classes.</p> <p>In the 1/01 Update release, additions include:</p> <ul style="list-style-type: none"> ■ Updated description of <code>init.wbem</code> command, which now starts the Solaris Management Console (SMC) server as well as the CIM Object Manager ■ Added section that describes how to upgrade the CIM Object Manager repository ■ Updated Security chapter refers the user to Solaris Management Console (SMC) for implementing role-based access control (RBAC) ■ <code>wbemlogviewer</code> application replaced with Solaris Management Console (SMC) Log Viewer for viewing log file information ■ Added description of new <code>Solaris_Network1.0.mof</code> file and <code>Solaris_Users1.0.mof</code> file <p>In the 4/01 Update release, additions include:</p> <ul style="list-style-type: none"> ■ Sun WBEM SDK 2.4 – Prior to this update, Sun WBEM SDK had been delivered as a component of the Solaris Management SDK CD. Sun WBEM SDK 2.4 implements the CIM Event model. The documentation for the Sun WBEM SDK includes man pages, context-sensitive online help for CIM Workshop, Javadoc reference pages for the WBEM application programming interfaces, and an AnswerBook™ version of the <i>Sun WBEM SDK Developer's Guide</i>. 	<p>10/00</p> <p>Updated 1/01 and 4/01</p>
<ul style="list-style-type: none"> ■ New providers: <ul style="list-style-type: none"> ■ SNMP Provider ■ Product Registry Provider ■ Performance Provider <p>The providers are documented with HTML pages derived from the related MOF files at <code>/usr/sadm/lib/wbem/doc</code>.</p> ■ MOF Compiler (<code>mofcomp</code>), which contains enhancements to support standalone mode and conversion of MOF files to XML. Two arguments have been added to the <code>mofcomp</code> command: <ul style="list-style-type: none"> –x converts CIM classes that are defined in the MOF file to XML documents. –o <code>dirname</code> sets the MOF Compiler to run in standalone mode, without a CIM Object Manager. <p>To view the book, see the <i>Solaris WBEM Services Administrator's Guide</i>.</p>	

Managing Servers and Clients

TABLE 2-1 Solaris 8 Features for System Administrators (continued)

Description	First Released
<p>Diskless Client Management is available through the Solaris Management Console command line. You can manage diskless clients, list OS services for diskless clients, and manage patches on all existing diskless clients.</p> <p>For information on diskless client management, see “Managing Diskless Clients Overview” in the <i>Solaris 8 System Administration Supplement</i>.</p>	1/01
Managing System Security	
<p>The role-based access control (RBAC) databases can now be managed through the Solaris Management Console (SMC) graphical interface. Rights can now contain other rights. Rights can now be assigned by default in the <code>policy.conf</code> file.</p> <p>For more information, see “Role-Based Access Control” in the <i>Solaris 8 System Administration Supplement</i>.</p>	1/01
<p>The Generic Security Services Application Programming Interface (GSS-API) is a security framework that enables applications to protect the data they transmit. The GSS-API provides authentication, integrity, and confidentiality services to applications. The interface permits those applications to be entirely generic with respect to security. That is, they do not have to know the underlying platform (such as the Solaris platform) or security mechanism (such as Kerberos) being used. This means that applications that use the GSS-API can be highly portable.</p> <p>For more information, see the <i>GSS-API Programming Guide</i>.</p>	6/00
<p>SPARC: The <i>Solaris Smart Cards Administration Guide</i> has been updated. In the 1/01 release, information on setting up internal card readers has been added. Step-by-step instructions for setting up smart-card support have been streamlined to make setting up smart cards easier.</p> <p>In the 4/01 release, previous technical inaccuracies have been corrected. And, new chapters describe the tasks that you need to perform for smart-card setup and additional configuration tasks that you might need to perform if the default smart-card properties are not sufficient for your security environment.</p> <p>To view this book, see the <i>Solaris Smart Cards Administration Guide</i>.</p>	1/01 Updated 4/01
Managing Networks	
<p>Berkeley Internet Name Domain (BIND) version 8.2.2 new functionality includes:</p> <ul style="list-style-type: none"> ■ <code>In.named</code> configuration options – See <code>conf(4)</code> man page. ■ Extensions to the resolver (3RESOLV) interface that are safe to use in multithreaded applications. ■ The addition of the <code>ndc(1M)</code> command, which is used to start or stop reconfigure <code>in.named</code>, and the <code>dnskeygen(1M)</code> command, which is used to create TSIG and DNSSEC keys. 	4/01
<p>For more information, see the <i>Solaris Naming Administration Guide</i>.</p>	

TABLE 2-1 Solaris 8 Features for System Administrators (continued)

Description	First Released
<p>sendmail has new command-line options, new and revised configuration file options, new defined macros, new and revised m4 configuration macros, new and modified compile flags, new delivery agent flags, new equates for delivery agents, new queue features, new uses for LDAP, new rule set features, new file locations, and a new built-in mailer feature. “Mail Services” also describes changes to mail.local, changes to mailstats, and changes to makemap.</p> <p>For more information, see “Mail Services” in the <i>Solaris 8 System Administration Supplement</i>.</p>	4/01
<p>IP network multipathing provides your system with recovery from single-point failures with network adapters and increased traffic throughput. In the 10/00 release, if a failure occurs in the network adapter, and if you have an alternate adapter connected to the same IP link, the system switches all the network accesses automatically from the failed adapter to the alternate adapter. This process ensures uninterrupted access to the network. Also, when you have multiple network adapters connected to the same IP link, you achieve increased traffic throughput by spreading the traffic across multiple network adapters.</p> <p>In the 4/01 release, dynamic reconfiguration (DR) uses IP network multipathing to decommission a specific network device without impacting existing IP users.</p> <p>For more information, see the <i>IP Network Multipathing Administration Guide</i>.</p>	10/00 Updated 4/01
<p>Mobile Internet Protocol (IP) enables the transfer of information to and from mobile computers, such as laptop and wireless communications. In the 6/00 release, the mobile computer can change its location to a foreign network and still access and communicate with and through the mobile computer’s home network. The Solaris implementation of Mobile IP supports only IPv4.</p> <p>In the 4/01 release, Mobile IP enables system administrators to set up reverse tunnels. By setting up a reverse tunnel from the mobile node’s care-of address to the home agent, you ensure a topologically correct source address for the IP data packet. By using reverse tunnels, system administrators can also assign private addresses to mobile nodes.</p> <p>For more information, see the <i>Mobile IP Administration Guide</i>.</p>	6/00 Updated 4/01
<p>SPARC: Lightweight Directory Access Protocol (LDAP) is now supported in the iPlanet™ Web Server directory server. To set up the iPlanet directory server to support Solaris clients, see the <i>LDAP Setup and Configuration Guide</i>.</p>	1/01
<p>Managing File Systems</p>	
<p>Improved UFS Functionality: The performance of direct I/O, which is used by database applications to access unbuffered file-system data, has been improved by allowing concurrent read access and write access to regular UFS files.</p> <p>For more information on direct I/O concurrency, see “Improved UFS Direct I/O Concurrency” in the <i>Solaris 8 System Administration Supplement</i>.</p>	1/01

TABLE 2-1 Solaris 8 Features for System Administrators (continued)

Description	First Released
<p>UFS Snapshots provides the new <code>fssnap</code> command for backing up a file system while the file system is mounted. A snapshot is a temporary image of a file system, intended for backup operations. Previously, the documentation recommended when using the <code>ufsdump</code> command, you bring the system to single-user mode to keep the file system inactive during a backup.</p> <p>For more information on UFS Snapshots, see “Creating UFS Snapshots” in the <i>Solaris 8 System Administration Supplement</i>.</p>	1/01
<p>The <code>mkfs</code> command has been updated to improve performance when you create file systems. Improved <code>mkfs</code> performance is often 10 times faster than in previous Solaris releases. Performance improvements are seen on systems when you create both large and small file systems. However, the biggest <code>mkfs</code> performance improvements occur on systems with high-capacity or high-speed disks.</p>	1/01
Managing Removable Media	
<p>Removable media management now fully supports removable media such as DVD-ROMs, Zip drives, Jaz drives, CD-ROMs, and diskettes. For information on how to use this feature, see “Managing Removable Media” in the <i>Solaris 8 System Administration Supplement</i>.</p>	6/00 Updated 10/00
Managing Devices	
<p>Reconfiguration Coordination Manager (RCM) scripts enable a Solaris system administrator to use a script that cleanly shuts down devices and applications during a dynamic reconfiguration operation.</p> <p>For more information, see “Reconfiguration Coordination Manager (RCM) Scripts” in the <i>Solaris 8 System Administration Supplement</i>.</p>	4/01
<p>You can use Solaris Print Manager to set up a Universal Serial Bus (USB) printer that is attached to a SPARC system with USB ports. For more information, see “USB Printer Support” in the <i>Solaris 8 System Administration Supplement</i>.</p> <p>For an overview of USB, see “Overview of USB Devices” in <i>Solaris 8 System Administration Supplement</i>.</p>	10/00 Updated 1/01 and 4/01
<p>In the <code>mp</code> program enhancement, the <code>mp(1)</code> command is modified to work as a X Print Server client. With a properly configured X Print Server running in the host machine, <code>mp(1)</code> can print output in any Print Description Language which the X Print Server supports. The newly introduced options, <code>-D</code> and <code>-P</code> can be used for making <code>mp(1)</code> work as a X Print Server client.</p> <p>For more information, see the “mp(1) Print Filter Enhancement Overview” in the <i>Solaris 8 Software Developer Supplement</i>.</p>	4/01

TABLE 2-1 Solaris 8 Features for System Administrators (continued)

Description	First Released
<p>Improved dynamic reconfiguration error messages are intended to help system administrators troubleshoot problems when they remove a system resource, such as a configured swap area or a dedicated dump device.</p> <p>For more information on dynamic reconfiguration, see “New Dynamic Reconfiguration Error Messages” in the <i>Solaris 8 System Administration Supplement</i>.</p>	1/01
Managing System Resources	
<p>Extended accounting introduces a new variable-length, general-purpose accounting file format that represents general groups of accounting data. Also included is the ability to configure resource utilization that was recorded by the kernel in the various accounting files.</p> <p>For information on how to use this feature, see “Extended Accounting Features” in the <i>Solaris 8 System Administration Supplement</i>.</p>	6/00
Managing System Performance	
<p>The enhanced directory name look-up cache (DNLC) improves performance when you access files in large directories.</p> <p>For information on how to use this feature, see “DNLC Improvements” in the <i>Solaris 8 System Administration Supplement</i>.</p>	6/00
<p>The <i>Solaris Tunable Parameters Reference Manual</i> has been updated. Information on the <code>semsys:seminfo_semmnu</code> parameter has been added to this book.</p> <p>To view the book, see the <i>Solaris Tunable Parameters Reference Manual</i>.</p>	1/01
Early Access	
<p>This release includes an Early Access (EA) directory with EA software. For more information, see the README on the Solaris Software CD 2 of 2.</p>	

What's New for Installation

This chapter highlights new installation features in the Solaris 8 Update releases. For further information on these features, see the *Solaris 8 Installation Supplement*.

Note - For the most current man pages, use the `man` command. The Solaris 8 Update release man pages include new feature information not found in the *Solaris 8 Reference Manual Collection*.

TABLE 3-1 Solaris 8 Features for Installation

Description	First Released
Installing	
The Web Start Flash installation feature enables you to create a single reference installation of the Solaris operating environment on a machine and then replicate that installation on several machines.	4/01
The system identification utilities automatically attempt to determine the default router during installation.	4/01
During system identification, the system identification utilities can configure systems to be LDAP clients. Prior Solaris releases allowed the configuration of a machine only as a NIS, NIS+, or DNS client.	1/01
The Solaris™ Web Start 3.0 installation method was updated to allow you to modify the selected Solaris Software Group by adding or removing software packages.	1/01
Upgrading	

TABLE 3-1 Solaris 8 Features for Installation (continued)

Description	First Released
The Patch Analyzer is now available when you upgrade with the Solaris Web Start 3.0 installation method on the Solaris 8 Installation CD. The Patch Analyzer performs an analysis on your system to determine which (if any) patches will be removed or downgraded by upgrading from the Solaris 8 release to a Solaris 8 Update release.	6/00
Administering and Uninstalling Software	
A new version of the Solaris Product Registry tool has been released. The Solaris Product Registry 3.0 includes these new features:	1/01
<ul style="list-style-type: none">■ Ability to uninstall individual system packages.■ All of the Solaris system products that you installed in their localized version appear in the System Software Localizations folder.■ Registry is compatible with more installation wizards.	
Early Access	
This release includes an Early Access (EA) directory with EA software. For more information, see the README on the Solaris 8 Software 2 of 2 CD.	6/00

What's New for Developers

This chapter highlights new features for Solaris developers that have been added to the Solaris™ 8 Update releases. For further information on these features, see the *Solaris 8 Software Developer Supplement*.

Note - For the most current man pages, use the `man` command. The Solaris 8 Update release man pages include new feature information not found in the *Solaris 8 Reference Manual Collection*.

TABLE 4-1 Solaris 8 Update Features for Developers

Feature	Update Release
Writing Device Drivers	
SPARC: The driver hardening test harness is a Solaris device driver development tool. The test harness injects a wide range of simulated hardware faults when the driver under development accesses its hardware. This fault-injection test harness tests the resilience of a SPARC based device driver. For more information, see “Driver Hardening Test Harness” in the <i>Solaris 8 Software Developer Supplement</i> .	4/01
“High-Availability Drivers” provides a detailed description of how to design drivers to support high availability through driver hardening and ensuring serviceability. This material extends information provided in the <i>Solaris 8 Writing Device Drivers</i> . For more information, see “High-Availability Drivers” in the <i>Solaris 8 Software Developer Supplement</i> .	10/00

TABLE 4-1 Solaris 8 Update Features for Developers (continued)

Feature	Update Release
<p>You can use Generic LAN driver (GLD) to implement much of the STREAMS and Data Link Provider Interface (DLPI) functionality for a Solaris network driver. Until the Solaris 8 10/00 release, the GLD module was available only for Solaris <i>Intel Platform Edition</i> network drivers. Now GLD is available for Solaris <i>SPARC Platform Edition</i> network drivers as well.</p> <p>For the 4/01 release, GLD is updated with bug fixes.</p> <p>For more information, see “Drivers for Network Devices” in the <i>Solaris 8 Software Developer Supplement</i>.</p>	<p>10/00 Updated 4/01</p>
<p>Language Support</p>	
<p>The File System Safe Universal Transformation Format, or UTF-8, is an encoding defined by X/Open as a multibyte representation of Unicode. UTF-8 encompasses almost all of the characters for traditional single-byte and multibyte locales for European and Asian languages for Solaris locales. For the 10/00 release, Russian and Polish and two new locales for Catalan are added. For the 4/01 release, two additional languages, Turkish UTF-8 Codeset and Russian UTF-8 Codeset, are added to a table of already existing Eastern European locales.</p> <p>For more information, see “Additional Partial Locales for European Solaris Software” in the <i>Solaris 8 Software Developer Supplement</i>.</p>	<p>10/00 Updated 4/01</p>
<p>The <code>mp</code> program accepts international text files of various Solaris locales and produces output that is proper for the specified locale. The output will also contain proper text layout, for instance, bidirectional text rendering, and shaping, as the complex text layout (CTL) is supported in <code>mp</code>. Depending on each locale’s system font configuration for <code>mp</code>, the PostScript™ output file can contain glyph images from Solaris system-resident scalable or bitmap fonts.</p> <p>For more information, see “Print Filter Enhancement <code>mp(1)</code>” in the <i>Solaris 8 Software Developer Supplement</i>.</p>	<p>4/01</p>
<p>Development Tools</p>	
<p>The <code>appcert</code> utility verifies an object file’s conformance to the Solaris ABI. Conforming to the Solaris ABI greatly increases an application’s probability of being compatible with future releases of Solaris software.</p> <p>For more information, see “Using <code>appcert</code>” in the <i>Solaris 8 Software Developer Supplement</i>.</p>	<p>4/01</p>

TABLE 4-1 Solaris 8 Update Features for Developers (continued)

Feature	Update Release
<p>Web-Based Enterprise Management (WBEM) includes standards for web-based management of systems, networks, and devices on multiple platforms. The Sun WBEM Software Developer's Toolkit (SDK) enables software developers to create standards-based applications that manage resources in the Solaris operating environment. Developers can also use this toolkit to write providers, programs that communicate with managed resources to access data. The Sun WBEM SDK includes Client Application Programming Interfaces (APIs) for describing and managing resources in Common Information Model (CIM), and Provider APIs for getting and setting dynamic data on the managed resource. The Sun WBEM SDK also provides CIM WorkShop, a Java application for creating and viewing the managed resources on a system, and a set of example WBEM client and provider programs.</p> <p>For more information, see the <i>Sun WBEM SDK Developer's Guide</i>.</p>	4/01
<p>SPARC: <i>Multithreaded Programming Guide</i> has been updated with bug fixes: 4308968, 4356675, 4356690.</p> <p>To view the book, see the <i>Multithreaded Programming Guide</i>.</p>	1/01

TABLE 4-1 Solaris 8 Update Features for Developers (continued)

Feature	Update Release
The <i>Linkers and Libraries Guide</i> has been updated with several new features.	10/00
For the 10/00 release, updates include:	Updated 1/01
<ul style="list-style-type: none"> ■ The environment variable LD_BREADTH is ignored by the runtime linker. See the section, “Initialization and Termination Routines.” ■ The runtime linker and its debugger interface have been extended for better runtime and core file analysis. This update is identified by a new version number. See the section “Agent Manipulation.” This update expands the <code>rl_flags</code>, <code>rl_bend</code>, and <code>rl_dynamic</code> fields of the <code>rd_loadobj_t</code> structure. See the section “Scanning Loadable Objects.” ■ The validation of displacement-relocated data in regard to its use, or possible use, with copy relocations is now provided. See the section “Displacement Relocations.” ■ 64-bit filters can be built solely from a mapfile by using the <code>link-editors -64</code> option. See the section “Generating a Standard Filter.” ■ Some explanatory notes are provided on why <code>\$ORIGIN</code> dynamic string token expansion is restricted within secure applications. See the section “Security.” ■ The search paths that are used to locate the dependencies of dynamic objects can be inspected by using <code>dlinfo(3DL)</code>. ■ <code>dlsym(3DL)</code> and <code>dlinfo(3DL)</code> look-up semantics have been expanded with a new handle, <code>RTLD_SELF</code>. ■ The runtime symbol look-up mechanism that is used to relocate dynamic objects can be significantly reduced by establishing direct binding information within each dynamic object. See the sections “External Bindings” or “Direct Binding.” 	
For the 1/01 release, updates include:	
<ul style="list-style-type: none"> ■ The symbolic information available from <code>dladdr(3DL)</code> has been enhanced with the introduction of <code>dladdr1()</code>. ■ The <code>\$ORIGIN</code> of a dynamic object can be obtained from <code>dlinfo(3DL)</code>. ■ The maintenance of runtime configuration files, created with <code>crle(1)</code>, has been simplified with the display of the command-line options that were used to create the configuration file. Also available is an update capability (see the <code>-u</code> option). ■ The runtime linker and its debugger interface have been extended to detect procedure-linkage-table entry resolution. This update is identified by a new version number. See the section “Agent Manipulation.” This update extends the <code>rd_plt_info_t</code> structure. See the section “Procedure Linkage Table Skipping.” ■ An applications stack can be defined non-executable by using the new mapfile segment descriptor <code>STACK</code>. See the section “Segment Declarations.” 	
To view the book, see the <i>Linker and Libraries Guide</i> .	

System Interface Tools

TABLE 4-1 Solaris 8 Update Features for Developers (continued)

Feature	Update Release
<p>The <i>System Interface Guide</i> is updated to incorporate bug fixes. This release corrects several typographical errors in text and source code examples.</p> <p>To view the book, see the <i>System Interface Guide</i>.</p>	6/00
Java Releases	
<p>The Java 2 SDK Standard Edition v. 1.3.0, also known as J2SE™ 1.3.0, is an upgrade release for Java 2 SDK. The J2SE release includes the following new features and enhancements.</p> <ul style="list-style-type: none"> ■ Performance Improvements <p>Java HotSpot™ technology- and performance-tuned runtime libraries make J2SE 1.3.0 the fastest Java™ platform to date.</p> ■ Easier Web Deployment <p>New features such as applet caching and automatic installation of optional packages by J2SE 1.3.0's Java™ Plug-in component enhance the speed and flexibility with which you can display programs on the web.</p> ■ Enterprise Interoperability <p>The addition of RMI/IIOP and the Java Naming and Directory Interface™ in J2SE 1.3.0 enhance the interoperability of the Java 2 Platform.</p> ■ Security Advances <p>New support for RSA electronic signing, dynamic trust management, X.509 certificates, and verification of Netscape-signed files mean more ways for developers to protect their electronic data.</p> ■ Java Sound <p>J2SE 1.3.0 includes a powerful new sound API. Previous releases of the platform limited audio support to basic playback of audio clips. With this release, the Java 2 Platform defines a set of standard classes and interfaces for low-level audio support.</p> ■ Enhanced APIs and Improved Ease of Development <p>In response to requests from the development community, J2SE 1.3.0 adds new features to various areas of the Java 2 Platform. These features expand the functionality of the platform to enable development of more powerful applications. In addition, many of the new features make the development process itself faster and more efficient.</p> <p>For more J2SE improvements, see “Java 2 SDK, Standard Edition, version 1.3.0” in the <i>Solaris 8 Software Developer Supplement</i>.</p>	4/01
<p>The J2SE 1.2.2_07a contains fixes for bugs that were identified in previous releases in the J2SE 1.2.2 series. An important bug fix is a fix for a performance regression that was introduced in J2SE 1.2.2_05. For more information about bug fixes in J2SE 1.2.2_07a, see this web site: http://java.sun.com/j2se/1.2/ReleaseNotes.html.</p>	4/01
<p>The Java 2 SDK 1.2.2_06 and JDK 1.1.8_12 are improved with bug fixes since the last release.</p>	1/01

TABLE 4-1 Solaris 8 Update Features for Developers (continued)

Feature	Update Release
<p>The Java 2 SDK 1.2.2_05a includes the following new features.</p> <ul style="list-style-type: none"> ■ Scalability improvements to over 20 CPUs ■ Improved just-in time (JIT) compiler optimizations ■ Text-rendering performance improvements ■ <code>poller</code> class demo package ■ Swing improvements 	10/00
<p>For more information, see “Previous Java 2 Standard Edition (J2SE) Releases” in the <i>Solaris 8 Software Developer Supplement</i>.</p>	
<p>32-bit: With the addition of the <code>mod_jserv</code> module and related files, the Apache web server now supports Java servlets.</p>	10/00
<p>For more information, see “Java Servlet Support in Apache Web Server” in the <i>Solaris 8 Software Developer Supplement</i>.</p>	
<p>Early Access</p>	
<p>This release includes an Early Access (EA) directory with EA software. For more information, see the <code>README</code> on the Solaris Software CD 2 of 2.</p>	