



# Installing Third-Party JAR Files



Sun Microsystems, Inc.  
4150 Network Circle  
Santa Clara, CA 95054  
U.S.A.

Part No: 820-4720-11  
September 2009

Copyright 2009 Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, CA 95054 U.S.A. All rights reserved.

Sun Microsystems, Inc. has intellectual property rights relating to technology embodied in the product that is described in this document. In particular, and without limitation, these intellectual property rights may include one or more U.S. patents or pending patent applications in the U.S. and in other countries.

U.S. Government Rights – Commercial software. Government users are subject to the Sun Microsystems, Inc. standard license agreement and applicable provisions of the FAR and its supplements.

This distribution may include materials developed by third parties.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, the Solaris logo, the Java Coffee Cup logo, docs.sun.com, Java, and Solaris are trademarks or registered trademarks of Sun Microsystems, Inc. or its subsidiaries in the U.S. and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc.

The OPEN LOOK and Sun™ Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

Products covered by and information contained in this publication are controlled by U.S. Export Control laws and may be subject to the export or import laws in other countries. Nuclear, missile, chemical or biological weapons or nuclear maritime end uses or end users, whether direct or indirect, are strictly prohibited. Export or reexport to countries subject to U.S. embargo or to entities identified on U.S. export exclusion lists, including, but not limited to, the denied persons and specially designated nationals lists is strictly prohibited.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

# Contents

---

<b>Installing Third-Party JAR Files</b> .....	5
Setting Up the Third-Party Library Installer .....	5
▼ To Set Up the Third-Party Installer .....	6
▼ To Configure the Build File .....	6
Installing Third-Party JAR Files for the CICS Adapter .....	7
▼ To Install the JAR Files for CICS .....	8
▼ To Add Third-Party DLLs to the Shared Library .....	8
Installing Third-Party JAR Files for the WebSphere MQ Adapter .....	9
▼ To Install the JAR Files for WebSphere MQ .....	9
WebSphere MQ Adapter Required JAR Files .....	10
Installing Third-Party JAR Files for the SAP Adapters .....	11
▼ To Install the JAR Files for SAP .....	11
Installing Third-Party JAR Files for the Siebel EAI Adapter .....	12
▼ To Install the JAR Files for Siebel EAI .....	12
Installing Third-Party JAR Files for the DB2 Connect Adapter .....	13
▼ To Install the JAR Files for DB2 Connect .....	13
Installing Third-Party JAR Files for the VSAM Adapter .....	14
▼ To Install the JAR Files for VSAM .....	14



# Installing Third-Party JAR Files

---

The following sections provide instructions on how to install and configure Third-Party JAR files. If you have any questions or problems, see the Java CAPS web site at <http://goldstar.stc.com/support>.

- “Setting Up the Third-Party Library Installer” on page 5
- “Installing Third-Party JAR Files for the CICS Adapter” on page 7
- “Installing Third-Party JAR Files for the WebSphere MQ Adapter” on page 9
- “Installing Third-Party JAR Files for the SAP Adapters” on page 11
- “Installing Third-Party JAR Files for the Siebel EAI Adapter” on page 12
- “Installing Third-Party JAR Files for the DB2 Connect Adapter” on page 13
- “Installing Third-Party JAR Files for the VSAM Adapter” on page 14

## Setting Up the Third-Party Library Installer

This section includes information for installing and configuring the Third-Party Library Installer provided by Java CAPS to complete the installation of certain adapters. Third-party libraries are required for the following components:

- Sun Adapter for CICS
- Sun Adapter for WebSphere MQ
- Sun Adapters for SAP BAPI and SAP ALE
- Sun Adapter for Siebel EAI
- Sun Adapter for DB2 Connect
- Sun Adapter for VSAM

The Installer script requires the installation of Apache Ant version 1.7 or above, which can be downloaded from the following location:

<http://ant.apache.org/>

You can also use the ant version distributed with Java CAPS.

## ▼ To Set Up the Third-Party Installer

- 1 On the Java CAPS Uploader, click the Download tab.
- 2 Click Adapter's Third Party Library Installer and extract it into a working directory.
- 3 Set the environment variable `ANT_HOME` to point to the home directory of your ANT installation. For example:  

```
set ANT_HOME=C:\JavaCAPS6\netbeans\java2\ant
```
- 4 Set the environment variable `JAVA_HOME` to point to your JDK installation. For example:  

```
set JAVA_HOME=C:\Program Files\Java\jdk1.6.0_03
```
- 5 Set your `PATH` to include the bin directory of your ANT installation.  

```
set PATH=C:\JavaCAPS6\netbeans\java2\ant
```

## ▼ To Configure the Build File

The installer uses the `build.properties` file to determine where to install the JAR files and where to obtain the JAR files to install. This file contains information specific to each JAR file, so you should make a backup copy before making any changes.

- 1 Make a backup copy of the `build.properties` file.
- 2 Modify the properties listed in the following table. For more information on the `product.name` and third-party files properties, refer to the third-party JAR installation instructions for each Adapter.
- 3 When you are done modifying properties, save and close the file.

Name	Description	Value
<code>netbeans.home</code>	The location of the NetBeans installation in Java CAPS.	For a default installation of Java CAPS, the location is <code>C:/JavaCAPS6/netbeans/</code> for Windows, or <code>~/JavaCAPS6/netbeans/</code> for UNIX.  This property is automatically set. Only change this value if you changed the location of the Java CAPS installation.

Name	Description	Value
glassfish.home	The location of the GlassFish installation in Java CAPS. This allows third-party libraries to be installed to the right location in the runtime environment.	For a default installation of Java CAPS, the location is C:/JavaCAPS6/glassfish for Windows, or ~/JavaCAPS6/glassfish for UNIX.  This property is automatically set. Only change this value if you changed the location of the Java CAPS installation.
installation.domains	The name of the domains in the GlassFish installation where the third-party libraries will be placed.	The default is domain1, which is the name of the default domain that is created when you install Java CAPS.
product.name	A list of products that you are installing third-party jar files for. You can add or remove indicators, but do not change the actual indicator text.	A list of product indicators separated by semicolons. Each Adapter has one or more indicators that let the installer know which components are being updated. To find out which indicators to use for an Adapter, see the instructions for that Adapter.
thirdpartyfiles	For each Adapter, a list of absolute paths and filenames to the JAR files that will be installed. Separate the files by a semicolon.	For each adapter, the libraries vary depending on platform and the paths vary depending on where your third-party software is installed. Below is an example for CICS:  cicsadapterra.thirdpartyfiles=C:/Program Files/IBM/CICS Transaction Gateway/classes/ctgclient.jar;C:/Program Files/IBM/CICS Transaction Gateway/classes/ctgserver.jar  To find out which third-party file properties you need to use for an Adapter, see the instructions for that Adapter.

## Installing Third-Party JAR Files for the CICS Adapter

This section includes information for installing and configuring JAR files for the IBM CICS Transaction Gateway (CTG). The CTG must be installed and configured as the underlying connection transport to access z/OS CICS transactions.

Perform the following steps to install the files for the CICS Adapter:

- [“To Install the JAR Files for CICS” on page 8](#)
- [“To Add Third-Party DLLs to the Shared Library” on page 8](#)

## ▼ To Install the JAR Files for CICS

The following steps are for running the Third-Party Installer with default settings. If you are running the Installer for specific instantiations of NetBeans or GlassFish (separately), you must specify each specifically when running ant (for example, ant install-glassfish or ant install-netbeans).

- 1 **Install the Third-Party Library Installer and set up the environment, as described in “[Setting Up the Third-Party Library Installer](#)” on page 5.**
- 2 **Open a command window and navigate to the directory that you extracted the Third Party Installer ZIP file.**
- 3 **Customize the `build.properties` file with at least the following changes. For more information on build properties, see “[To Configure the Build File](#)” on page 6.**
  - a. **Remove all values from the `product.name` property except `cicsadapterra`.**
  - b. **Modify the `cicsadapterra.thirdpartyfiles` property by adding the paths and filenames of the IBM CTG third-party libraries.**

For example:

```
On Windows: cicsadapterra.thirdpartyfiles=C:/Program Files/IBM/CICS  
Transaction Gateway/classes/ctgclient.jar;C:/Program Files/IBM/CICS  
Transaction Gateway/classes/ctgserver.jar
```

```
On Solaris: cicsadapterra.thirdpartyfiles=  
/opt/IBM/cicstg/classes/ctgclient.jar;  
/opt/IBM/cicstg/classes/ctgserver.jar
```

- 4 **Shutdown the instances of Java CAPS NetBeans and GlassFish.**
- 5 **Invoke the Third Party Installer by typing ant.**
- 6 **Restart the Java CAPS NetBeans instance.**

## ▼ To Add Third-Party DLLs to the Shared Library

The following steps address updating the shared library files during runtime. This procedure only applies to LOCAL: protocol with IBM CTG on GlassFish.

- 1 **Open the Admin Console for your GlassFish instance.**

- 2 **Add the C:\Program Files\IBM\CICS Transaction Gateway\bin path to the Native Library Path Prefix field in the JVM Settings Tab.**
- 3 **Click Save.**

## Installing Third-Party JAR Files for the WebSphere MQ Adapter

This section includes information for installing and configuring the third-party JAR files for the WebSphere MQ Adapter.

### ▼ To Install the JAR Files for WebSphere MQ

The following steps are for running the Third-Party Installer with default settings. If you are running the Installer for specific instantiations of NetBeans or GlassFish (separately), you must specify each specifically when running ant (for example, `ant install-glassfish` or `ant install-netbeans`).

- 1 **Install the Third-Party Library Installer and set up the environment, as described in [“Setting Up the Third-Party Library Installer”](#) on page 5.**
- 2 **Navigate to the location of the Third-Party Library Installer.**
- 3 **Customize the `build.properties` file with at least the following changes. For more information on build properties, see [“To Configure the Build File”](#) on page 6.**
  - a. **Remove all values from the `product.name` property except `webspheremq`.**
  - b. **Modify the `webspheremq.thirdpartyfile` property by adding the full path to `com.ibm.mq.jar`.**  
For example:  
  
On Windows: `webspheremq.thirdpartyfile=C:/Program Files/IBM/WebSphere MQ/Java/lib/com.ibm.mq.jar`  
  
On Solaris: `webspheremq.thirdpartyfile=/opt/IBM/webspheremq/Java/lib/opt/com.ibm.mq.jar`
- 4 **Shutdown the instances of Java CAPS NetBeans and GlassFish.**
- 5 **Invoke the Third Party Installer by typing `ant`.**
- 6 **Restart the Java CAPS NetBeans instance.**

## WebSphere MQ Adapter Required JAR Files

The WebSphere MQ Adapter requires the file **com.ibm.mq.jar**, a system specific JAR file, for normal operation. For XA transactions in Client mode, or for deploying EAR files to a WebLogic application server, the adapter also requires the **com.ibm.mqetclient.jar** file.

The **com.ibm.mq.jar** must be copied from the MQ server that you are running against. Depending on the mode of operation, the WebSphere MQ Library utilized by the adapter requires operating system-specific modules. If a WebSphere MQ Adapter project is deployed to a different MQ server running on a different operating system, the **com.ibm.mq.jar** file on the logical host must be replaced with the **com.ibm.mq.jar** from that specific MQ server to ensure that the JAR file remains operating system-specific with the current MQ server.

### ▼ To install the system-specific com.ibm.mq.jar file

- 1 Copy the **com.ibm.mq.jar** file from the WebSphere MQ server.
- 2 Paste the JAR file to the `\JavaCAPS\logicalhost\is\lib` directory, where JavaCAPS is the Sun Java Composite Application Platform Suite installation directory.

## Adding the required JAR files to the Integration Server Classpath for XA Transactions

The WebSphere MQ Adapter requires the **com.ibm.mqetclient.jar** file for XA transactions in Client mode and for deploying EAR files to a WebLogic application server. The JAR file is installed as part of the WebSphere MQ Extended Transaction client installation. Both the **com.ibm.mq.jar** and the **com.ibm.mqetclient.jar** must be added to the Integration Server classpath to run XA transactions in Client mode.

### ▼ To add the required JAR files to the IS Classpath

- 1 Note the location of the **com.ibm.mq.jar** and the **com.ibm.mqclient.jar** files on your logical host.
- 2 Open the Integration Server Administration tool. Add the absolute path for both JAR files to the IS Administration tool's Classpath Prefix field.
- 3 Save your work.

# Installing Third-Party JAR Files for the SAP Adapters

This section includes information for installing the SAP Java Connector, SAP Java Base IDoc Class Library, and the SAP Java Connector IDoc Class Library. The SAP libraries must be installed and configured as the underlying connection transport to access an SAP instance.

## ▼ To Install the JAR Files for SAP

The following steps are for running the Third-Party Installer with default settings. If you are running the Installer for specific instantiations of NetBeans or GlassFish (separately), you must specify each specifically when running ant (for example, `ant install-glassfish` or `ant install-netbeans`).

- 1 **Install the Third-Party Library Installer and set up the environment, as described in [“Setting Up the Third-Party Library Installer”](#) on page 5.**
- 2 **Navigate to the location of the Third-Party Library Installer.**
- 3 **Customize the `build.properties` file with at least the following. For more information on build properties, refer to [“To Configure the Build File”](#) on page 6.**
  - a. **Remove all values from the `product.name` property except `sapaleadapter` or `sapbapiadapter`**
  - b. **Modify the `sapbapiadapter.thirdpartyfiles` or `sapaleadapter.thirdpartyfiles` property by adding the full paths and filenames to the SAP Connector third-party libraries.**  
 For example:
    - On Windows:
 

```
sapbapiadapter.thirdpartyfiles=C:\Projects\SAP\JCO_jarfiles\sapjco.jar;C:\Projects\
```
    - On Solaris:
 

```
sapaleadapter.thirdpartyfiles=/home/sapuser/SAP/JCO_jarfiles/sapjco.jar;/home/sapuser/
```
- 4 **Shutdown the instances of Java CAPS NetBeans and GlassFish.**
- 5 **Invoke the Third Party Installer by typing `ant`.**
- 6 **Restart the Java CAPS NetBeans instance.**

# Installing Third-Party JAR Files for the Siebel EAI Adapter

This section includes information for installing and configuring the third-party JAR files for the Siebel EAI Adapter.

## ▼ To Install the JAR Files for Siebel EAI

The following steps are for running the Third-Party Installer with default settings. If you are running the Installer for specific instantiations of NetBeans or GlassFish (separately), you must specify each specifically when running ant (for example, ant install-glassfish or ant install-netbeans).

- 1 **Install the Third-Party Library Installer and set up the environment, as described in [“Setting Up the Third-Party Library Installer” on page 5](#).**
- 2 **Navigate to the location of the Third-Party Library Installer.**
- 3 **Customize the `build.properties` file with at least the following. For more information on build properties, see [“To Configure the Build File” on page 6](#).**
  - a. **Remove all values from the `product.name` property except `siebeleaiadapter80`, `siebeleaiadapter78`, `siebeleaiadapter77`, or `siebeleaiadapter75x`.**
  - b. **Modify any of the following properties (depending on what you specified above):**
    - `siebeleaiadapter80.thirdpartyfiles`: Add the full path and file name to `Siebel.jar` and `SiebelJI_enu.jar`
    - `siebeleaiadapter78.thirdpartyfiles`: Add the full path and file name to `Siebel.jar` and `SiebelJI_enu.jar`
    - `siebeleaiadapter77.thirdpartyfiles`: Add the full path and file name to `Siebel.jar` and `SiebelJI_enu.jar`
    - `siebeleaiadapter75x.thirdpartyfiles`: Add the full path and file name to `SiebelJI.jar`, `SiebelJI_Common.jar`, and `SiebelJI_enu.jar`

For example:

On Windows: `siebeleai.thirdpartyfile=C:/Program Files/IBM/Siebel EAI/Java/lib/com.ibm.mq.jar`

On Solaris: `siebeleai /opt/IBM/siebeleai/Java/lib/opt/com.ibm.mq.jar`

- 4 **Shutdown the instances of Java CAPS NetBeans and GlassFish.**

- 5 **Invoke the Third Party Installer by typing ant.**  
Siebel JAR files are only used in design time and not in runtime. The ant script installs Siebel JAR files to the NetBeans environment, but nothing is installed in the GlassFish environment.
- 6 **Restart the Java CAPS NetBeans instance.**

## Installing Third-Party JAR Files for the DB2 Connect Adapter

This section includes information for installing and configuring the third-party JAR files for the DB2 Connect Adapter.

### ▼ To Install the JAR Files for DB2 Connect

The following steps are for running the Third-Party Installer with default settings. If you are running the Installer for specific instantiations of NetBeans or GlassFish (separately), you must specify each specifically when running ant (for example, `ant install-glassfish` or `ant install-netbeans`).

- 1 **Install the Third-Party Library Installer and set up the environment, as described in [“Setting Up the Third-Party Library Installer” on page 5](#).**
- 2 **Navigate to the location of the Third-Party Library Installer.**
- 3 **Customize the `build.properties` file with at least the following. For more information on build properties, see [“To Configure the Build File” on page 6](#).**
  - a. **Remove all values from the `product.name` property except `db2connectadapter`.**
  - b. **Modify the `db2connectadapter.thirdpartyfiles` property by adding the full path and filename of the DB2 Connect third-party libraries.**  
For example:  
On Windows:  
`db2connectadapter.thirdpartyfiles=C:\temp\jars\db2jars\db2jcc.jar;C:\temp\jars\db2j`  
On Solaris:  
`db2connectadapter.thirdpartyfiles=/home/db2jars/db2jcc.jar;/home/db2jars/db2jcc_lic`
- 4 **Shutdown the instances of Java CAPS NetBeans and GlassFish.**
- 5 **Invoke the Third Party Installer by typing ant.**
- 6 **Restart the Java CAPS NetBeans instance.**

# Installing Third-Party JAR Files for the VSAM Adapter

This section includes information for installing and configuring the third-party JAR files for the VSAM Adapter.

## ▼ To Install the JAR Files for VSAM

The following steps are for running the Third-Party Installer with default settings. If you are running the Installer for specific instantiations of NetBeans or GlassFish (separately), you must specify each specifically when running ant (for example, `ant install-glassfish` or `ant install-netbeans`).

- 1 **Install the Third-Party Library Installer and set up the environment, as described in [“Setting Up the Third-Party Library Installer” on page 5](#).**
- 2 **Navigate to the location of the Third-Party Library Installer.**
- 3 **Customize the `build.properties` file with at least the following. For more information on build properties, see [“To Configure the Build File” on page 6](#).**
  - a. **Remove all values from the `product.name` property except `vsamadapter`.**
  - b. **Modify the `vsamadapter.thirdpartyfiles` property by adding the path and filenames of the VSAM third-party libraries.**

For example:

On Windows:

```
vsamadapter.thirdpartyfiles=C:\temp\jars\vsamjars\cacjdbc30.jar;C:\temp\jars\vsamjars\ca
```

On Solaris:

```
vsamadapter.thirdpartyfiles=/home/vsamjars/cacjdbc30.jar;/home/vsamjars/cacjdbc30em21.jar
```

- 4 **Shutdown the instances of Java CAPS NetBeans and GlassFish.**
- 5 **Invoke the Third Party Installer by typing `ant`.**
- 6 **Restart the Java CAPS NetBeans instance.**