



Sun StorageTek™ Enterprise PCI Express 4 Gb FC Single and Dual Port Host Bus Adapters Release Notes

Sun Microsystems, Inc.
www.sun.com

Part No. 819-3324-11
December 2005, Revision A

Submit comments about this document at: <http://www.sun.com/hwdocs/feedback>

Copyright 2005 Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, California 95054, U.S.A. All rights reserved.

Sun Microsystems, Inc. has intellectual property rights relating to technology that is described in this document. In particular, and without imitation, these intellectual property rights may include one or more of the U.S. patents listed at <http://www.sun.com/patents> and one or more additional patents or pending patent applications in the U.S. and in other countries.

This document and the product to which it pertains are distributed under licenses restricting their use, copying, distribution, and decompilation. No part of the product or of this document may be reproduced in any form by any means without prior written authorization of Sun and its licensors, if any.

Third-party software, including font technology, is copyrighted and licensed from Sun suppliers.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and in other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, AnswerBook2, docs.sun.com, Sun StorEdge, Java, Sun Blade, SunSolve, StorageTek, and Solaris are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and in other countries.

All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and in other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc.

Mozilla is a trademark or registered trademark of Netscape Communications Corporation in the United States and other countries.

The OPEN LOOK and Sun™ Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

U.S. Government Rights—Commercial use. Government users are subject to the Sun Microsystems, Inc. standard license agreement and applicable provisions of the FAR and its supplements.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright 2005 Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, Californie 95054, Etats-Unis. Tous droits réservés.

Sun Microsystems, Inc. a les droits de propriété intellectuelle relatant à la technologie qui est décrit dans ce document. En particulier, et sans la limitation, ces droits de propriété intellectuelle peuvent inclure un ou plus des brevets américains énumérés à <http://www.sun.com/patents> et un ou les brevets plus supplémentaires ou les applications de brevet en attente dans les Etats-Unis et dans les autres pays.

Ce produit ou document est protégé par un copyright et distribué avec des licences qui en restreignent l'utilisation, la copie, la distribution, et la décompilation. Aucune partie de ce produit ou document ne peut être reproduite sous aucune forme, par quelque moyen que ce soit, sans l'autorisation préalable et écrite de Sun et de ses bailleurs de licence, s'il y en a.

Le logiciel détenu par des tiers, et qui comprend la technologie relative aux polices de caractères, est protégé par un copyright et licencié par des fournisseurs de Sun.

Des parties de ce produit pourront être dérivées des systèmes Berkeley BSD licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, AnswerBook2, docs.sun.com, Sun StorEdge, Java, Sun Blade, SunSolve, StorageTek, et Solaris sont des marques de fabrique ou des marques déposées de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays.

Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

Mozilla est une marque de Netscape Communications Corporation aux Etats-Unis et à d'autres pays.

L'interface d'utilisation graphique OPEN LOOK et Sun™ a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciées de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui en outre se conforment aux licences écrites de Sun.

LA DOCUMENTATION EST FOURNIE "EN L'ÉTAT" ET TOUTES AUTRES CONDITIONS, DECLARATIONS ET GARANTIES EXPRESSES OU TACITES SONT FORMELLEMENT EXCLUES, DANS LA MESURE AUTORISEE PAR LA LOI APPLICABLE, Y COMPRIS NOTAMMENT TOUTE GARANTIE IMPLICITE RELATIVE A LA QUALITE MARCHANDE, A L'APTITUDE A UNE UTILISATION PARTICULIERE OU A L'ABSENCE DE CONTREFAÇON.



Contents

Features in This Release	2
Supported Operating Systems	2
Solaris 10 Operating Systems	3
System Requirements	3
Minimum OS Levels	3
Host Platform Support	3
Storage System Support	3
Fibre Channel Switch Support	3
Known Issues and Bugs	4
Red Hat Enterprise Linux and SuSE Linux Enterprise Server Systems	5
System Requirements	5
Minimum OS Levels	5
Host Platform Support	5
Storage System Support	6
Fibre Channel Switch Support	6
Known Issues and Bugs	6

Windows Server 2000 and Windows Server 2003 Systems	6
System Requirements	7
Host Platform Support	7
Storage Systems Support	7
Fibre Channel Switch Support	7
Known Issues and Bugs	7
Service Contact Information	7

Sun StorageTek Enterprise PCI Express 4 Gb FC Single and Dual Port Host Bus Adapters Release Notes

This document contains the latest supplementary information for the Sun StorageTek™ Enterprise PCI Express 4 Gb Fibre Channel (FC) Single and Dual Port Host Bus Adapter (HBA) (SG-XPCIE1FC-QF4, SG-XPCIE2FC-QF4). Use it with the latest version of the *Sun StorageTek Enterprise PCI Express 4Gb Fibre Channel Single and Dual Port HBA Installation Guide* (part number 819-3899-11 or later).

It contains the following sections:

- “Features in This Release” on page 2
- “Solaris 10 Operating Systems” on page 3
- “Red Hat Enterprise Linux and SuSE Linux Enterprise Server Systems” on page 5
- “Windows Server 2000 and Windows Server 2003 Systems” on page 6

Note – Sun is not responsible for the availability of third-party Web sites mentioned in this document. Sun does not endorse and is not responsible or liable for any content, advertising, products, or other materials that are available on or through such sites or resources. Sun will not be responsible or liable for any actual or alleged damage or loss caused by or in connection with the use of or reliance on any such content, goods, or services that are available on or through such sites or resources.

Features in This Release

This HBA consists of a single-slot PCI Express bus expansion board that connects to one or two FC optical media busses. Each channel of the host adapter can act as either an initiator or target. The two channels operate independently; each supports a separate FC bus operating at 4.25 Gbits/sec. Each channel is also backward-compatible with 2.125 Gbits/sec and 1.0625 Gbits/sec FC busses.

One or two Small-Form Factor (SFF) LC-duplex connectors are used to connect to the external FC busses. The FC bus operates in short-wave, multi-mode. One ISP2432 processor is used to support the two independent FC busses.

Supported Operating Systems

You can use the Sun StorageTek Enterprise PCI Express 4Gb FC Single and Dual Port HBA with the following operating systems (OSs):

- Solaris 10 OS

To use the adapter with these OSs, you must use the Sun driver as described in “Solaris 10 Operating Systems” on page 3.

- Red Hat Enterprise Linux and SuSE Linux Enterprise Server OSs

To use the adapter with these OSs, you must use the QLogic driver as described in “Red Hat Enterprise Linux and SuSE Linux Enterprise Server Systems” on page 5.

- Windows Server 2000 and Windows Server 2003

To use the adapter with this OS, you must use the QLogic driver as described in “Windows Server 2000 and Windows Server 2003 Systems” on page 6.

Solaris 10 Operating Systems

This section contains the following information about using the Sun StorageTek Enterprise PCI Express 4Gb FC Single and Dual Port HBA with the Solaris OS:

- “System Requirements” on page 3

System Requirements

The following hardware and software are qualified with the Solaris 10 OS.

Minimum OS Levels

- Solaris 10 SPARC or x64 OS with the Solaris 10 recommended patch cluster

Host Platform Support

- Sun Fire T2000 server
- Sun Fire X2100 server (x64)

Storage System Support

- Sun StorEdge™ 3510 and 3511 FC Arrays
- Sun StorEdge™ 6020, 6120, and 6320 Arrays
- Sun StorEdge™ 6130 Array
- Sun StorEdge 6920 system
- Sun StorEdge L25, L100 tape libraries
- Sun StorEdge L500 tape library
- Sun StorEdge L180, L700 tape libraries
- Sun StorEdge L5500, L8500 tape libraries

Fibre Channel Switch Support

FC switch support is shown in TABLE 1TABLE 1.

TABLE 1 Fibre Channel Switch Support

Switch
QLogic SANbox 5200 2 Gb switch
Sun StorEdge Network 2 Gb switch
Sun StorEdge Network 2 Gb Brocade SilkWorm 3200 and 3800 switches
Sun StorEdge Network 2 Gb Brocade SilkWorm 3250 and 3850 switches
Sun StorEdge Network 2 Gb Brocade SilkWorm 3900 switch
Sun StorEdge Network 2 Gb Brocade SilkWorm 12000 and 24000 Core Fabric switches
Sun StorEdge Network 4 Gb Brocade SilkWorm 4100 switch
Sun StorEdge Network 4 Gb Brocade SilkWorm 48000 and 200E
Sun StorEdge Network 2 Gb McDATA Sphereon 4300 switch
Sun StorEdge Network 2 Gb McDATA Sphereon 4500 switch
Sun StorEdge Network 2 Gb McDATA Intrepid 6064 director
Sun StorEdge Network 2 Gb McDATA Intrepid 6140 director

Known Issues and Bugs

The following bugs are under investigation at the time of the release:

- **Bug 6306254** — SunVTS qlctest fails with qlctest.get_port_info.FATAL message
Workaround: On a dual-port HBA, run qlctest on only one port at a time.
- **Bug 6344143** — SunVTS qlctest: Fails on Online Selftest
Workaround: Disable 'Online Selftest' in qlctest 'Test Parameter Options' menu.

Red Hat Enterprise Linux and SuSE Linux Enterprise Server Systems

The Linux Drivers required to run the Sun StorageTek Enterprise PCI Express 4 Gb FC Single and Dual Port HBAs with the Linux OS are available for download at the Sun designated page at:

http://www.qlogic.com/support/sun_page.html

Drivers that support the Linux 2.4 and 2.6 kernels are provided. The Linux 2.4 kernel is used in Red Hat Enterprise Linux (RHEL) 3. The Linux 2.6 kernel is used in RHEL 4 and SLES 9. Consult the Sun hardware platform documentation to verify which Linux releases are supported.

The necessary utilities to perform diagnostics and HBA management are packaged in the Application Kit and are available for download at this Web page. The `SANSurfer` utility performs simple diagnostics, firmware maintenance, general HBA management and configuration functions.

This section contains the following information about using the StorageTek Enterprise PCI Express 4 Gb FC Single and Dual Port HBAs in Red Hat Enterprise Linux and in SuSE Linux Enterprise operating systems:

- “System Requirements” on page 5
- “Known Issues and Bugs” on page 6

System Requirements

The following hardware and software are qualified with the Red Hat Enterprise Linux and with the SuSE Linux Enterprise server systems:

Minimum OS Levels

- Red Hat Enterprise Linux (RHEL) 3
- Red Hat Enterprise Linux (RHEL) 4
- SuSE Linux Enterprise Server (SLES) 9

Host Platform Support

- Sun Fire X2100 server (x64)

Storage System Support

The storage systems supported for Red Hat Enterprise Linux and SuSE Linux Enterprise Server Systems are the same as those listed for “Solaris 10 Operating Systems” on page 3.

Fibre Channel Switch Support

FC switch support is shown in TABLE 1. In other words, it is exactly the same for Red Hat Enterprise Linux and SuSE Linux Enterprise Server Systems as it is for the Solaris 10 OS.

Known Issues and Bugs

The following bugs are under investigation at the time of the release:

- **Bug 6330692** — A system lock up problem occurs when running RHEL3 on a Sun Fire server directly connected to an L100 tape library with three SDLT600 drives.

If the serial port is connected, 10 to 15 seconds after starting a mt test script, the system panics and then reboots. If not, the system hangs and needs to be power-cycled.

Workaround: It is recommended that you not access tape using this HBA on Linux 2.4 kernels.

Windows Server 2000 and Windows Server 2003 Systems

The host adapter device driver for running the Windows Server 2000 and Windows Server 2003 OS is available for download at the QLogic website:

http://www.qlogic.com/support/sun_page.html.

This section contains the following information about using the StorageTek Enterprise PCI Express PCI Express 4 Gb FC Single and Dual Port HBAs in Windows Server 2000 and Windows Server 2003 operating systems:

- “System Requirements” on page 7
- “Known Issues and Bugs” on page 7

System Requirements

The following hardware and software are qualified with the Windows Server 2000 and Windows Server 2003 OS:

Host Platform Support

- Sun Fire X2100 server (x64)

Storage Systems Support

The storage systems supported for the Windows Server 2000 and the Windows Server 2003 operating systems are the same as those listed for “Solaris 10 Operating Systems” on page 3.

Fibre Channel Switch Support

The FC switches supported for the Windows Server 2000 and Windows Server 2003 operating systems are the same as those listed for the Solaris 10 OS in TABLE 1.

Known Issues and Bugs

There are no known HBA issues or bugs for the Windows Server 2000 and Windows Server 2003 operating systems at this time.

Service Contact Information

If you need help installing or using this product in the United States, call 1-800-USA-4SUN, or go to:

<http://www.sun.com/service/contacting/index.html>