



Source Compatibility Guide

Sun Microsystems, Inc.
901 San Antonio Road
Palo Alto, CA 94303-4900
U.S.A.

Part No: 805-4037-10
October 1998

Copyright 1998 Sun Microsystems, Inc. 901 San Antonio Road, Palo Alto, California 94303-4900 U.S.A. All rights reserved.

This product or document is protected by copyright and distributed under licenses restricting its use, copying, distribution, and decompilation. No part of this product or document may be reproduced in any form by any means without prior written authorization of Sun and its licensors, if any. Third-party software, including font technology, is copyrighted and licensed from Sun suppliers.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, SunDocs, Java, the Java Coffee Cup logo, and Solaris are trademarks, registered trademarks, or service marks of Sun Microsystems, Inc. in the U.S. and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc.

The OPEN LOOK and Sun™ Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

RESTRICTED RIGHTS: Use, duplication, or disclosure by the U.S. Government is subject to restrictions of FAR 52.227-14(g)(2)(6/87) and FAR 52.227-19(6/87), or DFAR 252.227-7015(b)(6/95) and DFAR 227.7202-3(a).

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright 1998 Sun Microsystems, Inc. 901 San Antonio Road, Palo Alto, Californie 94303-4900 Etats-Unis. Tous droits réservés.

Ce produit ou document est protégé par un copyright et distribué avec des licences qui en restreignent l'utilisation, la copie, la distribution, et la décompilation. Aucune partie de ce produit ou document ne peut être reproduite sous aucune forme, par quelque moyen que ce soit, sans l'autorisation préalable et écrite de Sun et de ses bailleurs de licence, s'il y en a. Le logiciel détenu par des tiers, et qui comprend la technologie relative aux polices de caractères, est protégé par un copyright et licencié par des fournisseurs de Sun.

Des parties de ce produit pourront être dérivées du système Berkeley BSD licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, SunDocs, Java, le logo Java Coffee Cup, et Solaris sont des marques de fabrique ou des marques déposées, ou marques de service, de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays. Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

L'interface d'utilisation graphique OPEN LOOK et Sun™ a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciés de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui en outre se conforment aux licences écrites de Sun.

CETTE PUBLICATION EST FOURNIE "EN L'ETAT" ET AUCUNE GARANTIE, EXPRESSE OU IMPLICITE, N'EST ACCORDEE, Y COMPRIS DES GARANTIES CONCERNANT LA VALEUR MARCHANDE, L'APTITUDE DE LA PUBLICATION A REpondre A UNE UTILISATION PARTICULIERE, OU LE FAIT QU'ELLE NE SOIT PAS CONTREFAISANTE DE PRODUIT DE TIERS. CE DENI DE GARANTIE NE S'APPLIQUERAIT PAS, DANS LA MESURE OU IL SERAIT TENU JURIDIQUEMENT NUL ET NON AVENU.



Contents

Preface v

1. Introducing the Source Compatibility Package 1

What the Compatibility Package Is 1

Why the Compatibility Package Is Provided 1

Installing the Compatibility Package 2

Using the Compatibility Package 2

2. Compatibility Package Features 5

Source Compatibility Package Contents 5

Commands 5

Printing Commands 13

Mail Commands 14

System Management 15

System Calls 15

Signals 18

Library Routines 19

Routines in libcurses 20

Routines in libdbm 21

Routines in libtermcap 21

Routines in librpcsoc 21

Routines in libucb 22

Header Files 24

Preface

The SunOS 5.x operating system is based on AT&T's System V Release 4.0 (SVR4) and differs considerably from previous releases of the SunOS operating system. We realize these differences can be confusing and may require a period of adjustment. To ease this transition, the SunOS/BSD Source Compatibility Package is provided. This package contains many of the commands, library routines, and files you are familiar with from the SunOS environment.

Scope of this Manual

In the context of this guide, SunOS 4.1 is a universal term that includes these releases:

- SunOS 4.1
- SunOS 4.1.1
- SunOS 4.1.2
- SunOS 4.1.3

A complete discussion of general compatibility issues can be found in *Solaris 1.x to 2.x Transition Guide*. This guide provides a comparative listing of SunOS 4.1 interfaces and their SunOS 5.2 counterparts.

How This Book Is Organized

This guide is provided to document the contents of this package, its usage, and how to install it. Chapter 1 provides an overview of the package and explains the mechanics of using it. Chapter 2 provides detailed descriptions of each interface provided in this package. In some cases, a brief tutorial is also provided.

Notations

References to literal computer input (commands you enter) are shown in a bold, monospace font, and computer output (screen messages produced by the system) are shown in a monospace font, as in the following example:

```
$ ls -l report
--rw--r----r---- 1 jim doc 3239 May 26 11:21 report
```

Substitutable text elements (that is, text elements that you are expected to replace with specific values) are shown in an italic font, as in the following example:

```
$ cat filename
```

The italic font is a signal that you are expected to replace the word *filename* with the name of a file.

Instructions to the reader to type input usually do not include explicit instructions to press the RETURN key at the appropriate times (such as after entering a command or a menu choice) because this instruction is implied for all system commands and menus.

However, an instruction to press the RETURN key is explicitly provided during an interactive routine, when you are expected to press RETURN without having typed any text. An instruction to do so will be provided, as follows:

```
Type any key to continue: RETURN
$
```

Control characters are shown by the string *CTRL-char* where *char* is any character. To enter a control character, hold down the CTRL key and press the letter shown. Be sure to type the letter exactly as specified: when a lowercase letter is shown (such as the "d" in the example above), enter that lowercase letter. If a character is shown in uppercase (such as "CTRL-D") you should enter an uppercase letter.

The system prompt signs shown in examples of interactive sessions are the standard default prompt signs for the system under the following conditions:

- the dollar sign (\$) for an ordinary user
- the pound sign (#) for the owner of the root login

Ordering Sun Documents

The SunDocsSM program provides more than 250 manuals from Sun Microsystems, Inc. If you live in the United States, Canada, Europe, or Japan, you can purchase documentation sets or individual manuals using this program.

For a list of documents and how to order them, see the catalog section of SunExpress™ On The Internet at <http://www.sun.com/sunexpress>.

Introducing the Source Compatibility Package

The SunOS/BSD Source Compatibility Package is an optional package in the SunOS 5.x operating system that makes available many SunOS 4.1 and BSD interfaces otherwise not included, or which may differ in functionality between the SunOS 4.1 and SunOS 5.x releases. This package should be used as a transition aid, and your future development should not depend on its continued existence.

What the Compatibility Package Is

The Source Compatibility Package is a collection of commands, libraries and header files. Many of these may also be present in the default SunOS 5.x environment, but their behavior is different between the two versions. These interfaces are located in the `/usr/ucb`, `/usr/ucplib`, and `/usr/ucbinclude` directories.

Why the Compatibility Package Is Provided

This package and the SunOS Binary Compatibility Package (see the *Binary Compatibility Guide*) are provided as transition aids to help users migrate from SunOS 4.1 to SunOS 5.x. While applications are being ported, this package is available to aid in compiling the existing sources.

Installing the Compatibility Package

This package is optional that is, it is not automatically installed. This package is not required by any default SunOS 5.x commands, utilities, or libraries. Refer to *Solaris Advanced Installation Guide* or *x86: Installing Solaris Software* for instructions on how to install this package.

The contents of the compatibility package are installed into several directories, each corresponding to a default environment counterpart:

- `/usr/ucb` contains the source compatibility package commands. These commands existed in the `/usr/bin`, `/usr/ucb`, and `/usr/etc` directories in the SunOS 4.1 release.
- `/usr/ucblib` contains the source compatibility package libraries and SunOS/BSD system calls that are implemented here as library routines. These interfaces existed in `/usr/lib` in the SunOS 4.1 release.
- `/usr/ucbinclude` contains the source compatibility package header files. These files existed in the `/usr/include` directory in the SunOS 4.1 release.

Using the Compatibility Package

You can make use of the compatibility package in several ways: permanently, temporarily, or on a case-by-case basis.

To always get the compatibility package version of a command, you must set your `PATH` environment variable so that `/usr/ucb` appears before `/usr/bin`.

The following command displays the current setting of your `PATH` environment variable:

```
$ echo $PATH
/home/medici/bin:/usr/bin:/usr/ucb:/etc:.
$
```

For the current shell to find the compatibility package commands by default, switch the order of `/usr/bin` and `/usr/ucb`:

```
$ PATH=/home/medici/bin:/usr/ucb:/usr/bin:/etc:.
$
```

To make this change permanent, put the above line in the `.profile` file in your home directory.

Note - If you're using the C shell, use the following command to switch the order of `/usr/bin` and `/usr/ucb`. To make this change permanent in the C shell, put this line in the `.cshrc` file in your home directory. Changes to the `.cshrc` file do not take effect until that file has been sourced. See the `csh(1)` manual page for more information.

```
% set PATH=(/home/medici/bin /usr/ucb /usr/bin /etc .  
%
```

You can keep the SunOS 5.x commands as your default and still access the compatibility package commands by specifying the command's full path. This is useful when you are interested in the compatibility package version of a particular command only for a given instance:

```
$ which df  
/usr/bin/df  
$ df  
/          (/dev/root ): 231024 blocks 105323 files  
/proc     (/proc ):      0 blocks 123 files  
$ /usr/ucb/df  
Filesystem  kbytes  used   avail  capacity  Mounted on  
/dev/root  1750592 826496 749032 52%      /
```

Compatibility package header files and libraries used by the compatibility package version of the C compiler (`cc`) and linker (`ld`) are located in `/usr/ucbinclude` and `/usr/ucblib`.

By setting your path as shown above, you'll use `/usr/ucb/cc` when you compile C programs. `/usr/ucb/cc` sets its default paths to pick up the following directories in the order specified:

1. User-specified include directories and libraries.
2. The compatibility include files and directories.
3. The base SunOS 5.x system headers and libraries, if unresolved symbols remain.

Compatibility Package Features

This chapter describes the contents of the Source Compatibility Package. The contents are organized as follows:

- Commands
- System calls
- Signals
- Library routines
- Header files

For more information on the interfaces described here, see the *Solaris 7 Reference Manual Collection*.

Source Compatibility Package Contents

This section lists the contents of the Source Compatibility Package, and then describes the individual interfaces.

Commands

The commands below are described in alphabetical order. Following those descriptions, some common usage of related commands is discussed. These commands are located in `/usr/ucb`.

Table 2-1 below lists the commands available with the Source Compatibility Package.

Two versions of some commands exist: one in the default SunOS 5.x command location, and the other in the compatibility package found in `/usr/ucb`. These

commands are shown in bold in the table below. The descriptions in this guide pertain only to the /usr/ucb versions, although, where relevant, the differences between the two versions are discussed.

TABLE 2-1 Commands

	Commands	
Mail	hp722	renice
aedplot	hpplot	plot reset
arch	implot	rusage
atoplot	install	sed
basename	ldd	shutdown
bgplot	lint	stty
biff	ln	sum
cc	logger	t300
chown	lpc	t300s
crtplot	lpq	t4013
df	lpr	t450
du	lprm	tek
dumbplot	lptest	test
echo	ls	touch
expr	mach	tr
fastboot	mail	tset
fasthalt	mkstr	ucblinks
file	pagesize	rusers
from	plot	vipw
gigiplot	plottoa	vplot

TABLE 2-1 Commands (continued)

Commands		
groups	printenv	whereis
hostid	ps	whoami
hostname		

arch Displays your machine architecture. arch uses the SunOS 5.x `uname -m` command. arch is not available in the default SunOS 5.x release.

basename Strips the full path name off a file. If you follow the path name with a suffix, that suffix is stripped, too:

```
$ basename /usr/src/rundog.c .c
rundog
$
```

basename is useful for writing shell scripts. This version parses arguments differently than the SunOS 5.x version.

biff

Enables and disables immediate notification of the arrival of mail. When notification is enabled, biff displays the header and first few lines of mail messages when they are received. This command is not available in the default SunOS 5.x release.

cc

This command is identical to the unbundled C compiler in `/usr/ccs/bin/acc`, except that the following directories are included:

- User-specified include directories and libraries
- The compatibility include files and directories
- The default SunOS 5.x headers and libraries, if unresolved symbols remain

Compatibility package header files and libraries referenced by the compiler (cc) and linker (ld) are located in `/usr/ucbinclude` and `/usr/ucplib`.

chown

Changes the owner of a file. This version allows you to optionally change the group as well. The group may be either a decimal group ID (GID) or a group name found in the GID file.

df

Displays the free disk space of currently mounted file systems. This command differs from `/usr/bin/df` in several ways:

- Blocks sizes are reported in units of 1024-bytes in this version of `df`, while `/usr/bin/df` uses 512-byte blocks.
- Perhaps the most obvious difference between the two versions of this command is their output format, as shown by the example below.

```
$ /usr/ucb/df
Filesystem kbytes used avail capacity Mounted on
/dev/root 1750592 826496 749032 52% /
$ df
/ (/dev/root ): 231024 blocks 105323 files
/proc (/proc ): 0 blocks 123 files
```

du

Displays the number of disk blocks used by files in a directory. It is useful for seeing how disk space is being used. This version reports disk usage in kilobytes, while the default `du` command reports disk usage in blocks.

echo

Echoes arguments to the standard output. This version and the default `echo` command recognize certain escape sequences differently.

expr

Evaluates an expression. This version supports the following additional operators and keywords: `match`, `substr`, `index`, `length()`.

fastboot

Reboots your machine. This command is not available in the default SunOS 5.x release.

fasthalt

Halts your machine. This command is not available in the default SunOS 5.x release.

file

Determines the file type by examining the file's contents. This version supports symbolic links. When the `-L` option is specified for a file that is a symbolic link, `file` tests the file referenced by the link rather than the link itself.

from

Displays mail header information, including the sender and time the mail was received. This command is not available in the default SunOS 5.x release.

groups

Displays the groups to which a user belongs. Although the `id` command in the default SunOS 5.x release has been enhanced to perform this function, `groups` is also available for compatibility.

hostid

Prints the numeric identifier (in hexadecimal) of the current host. This command is not available in the SunOS 5.x release.

hostname

Displays the name of your machine and allows you to rename it. This command is not available in the base release. `uname -n` in the SunOS 5.x release displays the machine name, but does not allow the super-user to rename the machine.

install

Installs files into a destination directory. This version has different options and syntax than the SunOS 5.x one.

ld

This command is identical to the linker in `/usr/ccs/bin/ld`, except that it ensures that libraries in `/usr/ucb/lib` are linked in by `ld`, before the default SunOS 5.x libraries.

When unresolved symbols remain, the libraries in `/usr/lib` are referenced. Note that `/usr/ucb/lib/libucb.so` is always linked when this command is invoked.

lint

Checks C programs for bugs, argument type errors, and potential portability problems. This command uses the lint libraries under `/usr/ucb/lib`.

ln

Creates links to files or directories. The default `ln` removes an existing target if it has the requisite permissions. Because the SunOS 4.1 behavior is not obtained by default, the compatibility package contains a version of `ln` that does not remove an existing target.

logger

Adds entries to a system log. Priorities, tags, and files to write to may be specified.

lpc

`lpc`, the line printer control program, is the same as in SunOS 4.1, except that it does not make use of the file `/etc/printcap`. Use `lpc` to start and stop a printer, disable or enable a spooling queue, rearrange the order of printing jobs, or display the status of each printer. This command is not available in SunOS 5.x.

lpq

Returns information on all print jobs on the local printer; however, for remote printers, it provides the status only for jobs belonging to the user. `lpq` is the equivalent of the SunOS 5.x command `lpstat`.

The command `lpq username` provides the status of all files, on all machines (both local and remote), belonging to the named user. In these examples, user `wesson` sends files `fileX` and `fileY` to the local printer `printerA`, and `fileZ` to a remote printer:

```
$ lpr fileX
$ lpr fileY
$ lpq
Rank Owner Job Files
active smith printerA-111230 file1
1st wesson printerA-111231 fileX
2nd wesson printerA-111232 fileY
3rd jones printerA-111233 file9
$
$ lpr --Pfar_printer fileZ
$ lpq --Pfar_printer
Rank Owner Job Files
4th wesson far_printer-111332 fileZ
$
$ lpq wesson
printerA:
Rank Owner Job Files
1st wesson printerA-111231 FileX
2nd wesson printerA-111232 FileY
far_printer:
Rank Owner Job Files
4th wesson far_printer-111332 FileZ
$
```

`lpr`

Sends files to the printer. The compatibility package version of `lpr` does not support the `-r` option (which removes a file after spooling it). Nor does it allow for specific fonts to be mounted on font positions 1, 2, 3, or 4. `lpr` is the equivalent of the SunOS 5.x `lp` command.

`lprm`

Removes files from the print queue. This is the SunOS 4.1 equivalent of the SunOS 5.x `cancel` command.

`lptest`

Produces a ripple pattern for testing printers.

`ls`

Lists a file or the contents of a directory. The compatibility package version of `ls` differs from the default `ls` command in two ways:

- The `-l` option does not print the group.
- The `-s` option reports block sizes in blocks of 1024 bytes, instead of 512.

```
$ ls --ls
total 24
8 -rw-r--r-- 1 jah staff 268 Nov 10 21:28 test1
8 -rw-r--r-- 1 jah staff 121 Nov 10 21:28 test2
8 -rw-r--r-- 1 jah staff 42 Nov 10 21:28 test3
$ /usr/ucb/ls --ls
total 12
4 -rw-r--r-- 1 jah 268 Nov 10 21:28 test1
4 -rw-r--r-- 1 jah 121 Nov 10 21:28 test2
4 -rw-r--r-- 1 jah 42 Nov 10 21:28 test3
$
```

mach

Reports the machine type. The SunOS 5.x `uname -p` command provides the same behavior. However, because many scripts and makefiles use `mach`, it has been placed in the compatibility package. This command is not available in default SunOS 5.x release.

Mail and mail

Reads and sends mail messages. This command is a version of `mailx(1)` with defaults set to behave like the BSD `mail` command. See the `mailx(1)` manual page in the *Solaris 7 Reference Manual Collection* for complete information on the BSD default settings.

mkstr

Creates a file of all error messages in a C program source file. This is useful for programs with a large number of diagnostic error messages, it reduces the size of the program, and the system overhead when running the program. This command is not available in the default SunOS 5.x release.

pagesize

Reports the size of a page of memory in bytes. This is useful for scripts. This command is not available in the default SunOS 5.x release.

plot

Graphics filters for various plotters. The following filters allow you to run `plot` on a variety of terminals: `aedplot`, `atoplot`, `bgplot`, `crtplot`, `dumbplot`, `gigiplot`, `hp7221plot`, `hpplot`, `implot`, `plottoa`, `t300`, `t300s`, `t4013`, `t450`, `tek`, and `vplot`.

printenv

Reports environment variables as currently set. It is similar to the `env` command. This command is not available in the default SunOS 5.x release.

ps

Displays the status of the current processes. This version displays more information, in a different format, than that of the SunOS 5.x version.

renice

Alters the *nice* value of running processes. This behavior is now present in the SunOS 5.x `prionctl` command; however, for SunOS 4.1 compatibility reasons, `renice` is included in the compatibility package. This command is not available in the default SunOS 5.x release.

reset and tset

SunOS 5.x These commands are similar to `tput reset` and `tput init` respectively; that is, they reset and set terminal-behavior characteristics. However they differ enough to be included here. `reset` and SunOS 5.x `tset` are not available in the default SunOS 5.x release.

rusage

Executes the given command and reports on the resource usage. `rusage` reports the total time elapsed (wall clock), the system CPU, the user CPU, plus 11 other fields in a one line summary following the commands output, if any. This command is not available in the default SunOS 5.x release.

sed

`/usr/ucb/sed` is similar to `/usr/bin/sed` except it strips initial SPACE and TAB characters from text lines.

shutdown

This version of `shutdown` allows you to specify a time and a warning message to be sent. It also sends shutdown messages to other systems if they have mounted filesystems from the machine being shut down. See the `shutdown(1B)` manual page for any limitations on SunOS 4.1 functionality.

stty 5.2

The SunOS 5.x version of `stty` incorporates many of the features of SunOS 4.1 `stty`. The compatibility package version is included for full SunOS 4.1 functionality.

sum

Calculates checksums in a machine-dependent way. Also, it displays the file in kilobytes instead of 512-byte blocks.

test

Evaluates conditional expressions. The SunOS 4.1 and SunOS 5.x versions of `test` differ with respect to the `-f` option. In the SunOS 4.1 release, this option means “is the target not-a-directory?” while in the SunOS 5.x release it means “is the target a plain file?”.

touch

Updates the access and modification times of a file. The SunOS 5.x version of `touch` does not support the `-f` option, which attempts to force the touch in spite of read and write permissions on the file.

tr

Translates characters from the standard input to the standard output. There are two differences between `/usr/bin/tr` and this version:

- In SunOS 4.1, when translating from `string1` to `string2`, if `string2` is shorter than `string1`, `string2` is padded out to the length of `string1` by repeating `string2`'s last character.
- This version does not require enclosing alphanumeric ranges inside square brackets.

`tset`

See `reset`.

`ucblinks`

Creates symbolic links in `/dev` for SunOS 4.1 devices whose names are different in the SunOS 5.x release. When these links are no longer needed, they must be removed by hand.

`users`

Displays a short list of logged-in users. This command is not available in the default SunOS 5.x release. The SunOS 5.x equivalent is `who -q`.

`vipw`

Edits the `/etc/passwd` file, and sets the appropriate locks. `vipw` runs consistency checks on the password file when the edits are complete and the locks have been removed. If these checks fail, `vipw` does not allow the incorrect file to be installed. This command is not available in the default SunOS 5.x release.

`whereis`

Locates the binary, source, and manual page files for the given command. `whereis` searches a standard list of common locations for these files. This command is not available in the default SunOS 5.x release.

`whoami`

Displays your effective user ID; `whoami` works even if you have used `su` to change your current user ID. This command is not available in the default SunOS 5.x release, although it is equivalent to `id`.

Printing Commands

The compatibility package contains five printing commands that are not in the default SunOS 5.x release: `lpr`, `lpq`, `lprm`, `lpc`, and `lptest`. This is how they compare with the base commands:

TABLE 2-2 Printing Commands

SunOS 4.1 Command	SunOS 5.x Equivalent
lpr	lp
lpq	lpstat
lprm	cancel
lpc	no equivalent
lptest	no equivalent

Here is an overview of some important features:

- There are no SunOS 4.1 commands for administration, maintenance, or accounting of printers; you must use SunOS 5.x schemes. The exception is the lpc command, which is included.
- The SunOS 4.1 printcap file does not exist. The printer information is now contained in the files in the directories /etc/lp and /etc/lp/printers/printer-name. You can change this information using the lpadmin command. For more information on this command, refer to the lpadmin(1M) **lpadmin(1M)** manual page in the *Solaris 7 Reference Manual Collection*.
- Printing spooling commands do not depend on the lpd daemon, as in SunOS 4.1. Instead, they use an HPI (High Performance Interface) with the SunOS 5.x printing daemon, lpsched.

Mail Commands

The SunOS 4.1 version of mail, based on sendmail, has been included in the Source Compatibility Package; it has a different user interface than the base SunOS 5.x version of mail. Additionally, some useful mail facilities are included for compatibility.

TABLE 2-3 Mail Commands

Commands	Description
biff	immediate notification of mail
from	display mail header lines

TABLE 2-3 Mail Commands *(continued)*

Commands	Description
mail	send and receive mail messages
Mail	send and receive mail messages

System Management

Because of limitations in underlying SunOS 5.x support, the commands in this section for stopping and starting your system cannot provide full SunOS 4.1 functionality. Nonetheless, they are included here for compatibility, so that existing shell scripts invoking them can still function. For example, the compatibility package versions of `fastboot` and `fasthalt` do not prevent disk checks. See the manual pages on following commands to find out about specific limitations: `fastboot`, `fasthalt`, and `shutdown`.

System Calls

The following system calls are implemented in the compatibility package as library routines:

TABLE 2-4 System Calls

System Calls		
WIFEXITED	getpagesize	setregid
WIFSIGNALED	getpriority	setreuid
WIFSTOPPED	gettimeofday	settimeofday
flock	killpg	statfs
fstatfs	mctl	syscall
getdtablesize	reboot	wait3
gethostid	sethostname	wait4
gethostname	setpriority	

TABLE 2-4 System Calls (continued)

The following routines reside in libucb.

flock

Applies or removes an advisory lock on a file. The compatibility version of flock has been implemented on top of fcntl(2) locking. This version is not completely compatible with the SunOS 4.1 version. The following differences exist:

- To obtain a shared lock (LOCK_SH), read permission on file is required.
- To obtain an exclusive lock (LOCK_EX), write permission on file is required.
- EOPNOTSUPP may not be returned as a result of a call to flock.
- Locking a segment that is already locked by the calling process causes the old lock type to be removed and the new lock type to take effect. That was not the case with flock in the SunOS 4.1 release.
- Locks are not inherited by a child process in a fork(2) function.
- Locks obtained through the flock mechanism under SunOS 4.1 were known only within the system on which they were placed. This is no longer true.

fstatfs

Gets statistics about an open file on a mounted file system.

getdtablesize

Gets the size of a process's descriptor table. This routine calls the getrlimit(2) system call.

gethostid

Returns the 32-bit identifier for the current host. This routine calls the sysinfo(2) system call.

gethostname

Returns the standard hostname for the current processor. This routine calls the sysinfo(2) system call.

getpagesize

Returns the number of bytes in a page. This routine calls the sysconf(3C) routine.

getpriority

Gets the process scheduling priority. Returns the highest priority (lowest numerical value) of any of the specified processes. This routine calls the pricntl(2) system call.

gettimeofday

Gets date and time. This routine calls the default version of `gettimeofday(3C)`. Note that this version of `gettimeofday` accepts two arguments for compatibility purposes, although it ignores the second one.

`killpg`

Sends a signal to a process group. This routine calls the `kill(2)` system call.

`mctl`

Applies memory management control functions. This routine calls the `memcntl(3)` routine.

`reboot`

Restart system or halt processor. This routine calls the `uadmin(2)` system call.

`sethostname`

Sets the name of the host machine. This routine calls the `sysinfo(2)` system call.

`setpriority`

Sets the program scheduling priority. The default priority is 0. It is not possible for the process executing `setpriority` to lower any other process down to its current priority, without appropriate privileges. This routine calls the `prctl(2)` and `prctlset(2)` system calls.

`setregid`

Set real and effective group ID's. This routine calls the `setgid(2)` or `setegid` system calls. Exact BSD semantics are not always maintained. The real gid is not always changed. Not all cases can be handled.

`setreuid`

Sets real and effective user ID's. Calls SunOS 5.x's `setuid` or `seteuid`. Exact BSD semantics are not always maintained. The real uid is not always changed. Not all cases can be handled.

`settimeofday`

Sets date and time of day. This routine calls the `stime(2)` system call. Note that this function accepts two arguments for compatibility purposes, although it ignores the second.

`statfs`

Gets file system statistics about mounted file systems. Calls `statvfs(2)`.

`syscall`

Performs indirect system calls.

`wait3`

Alternative system call to `wait(2)` for waiting for a process to stop. This routine calls the `waitid(2)` system call.

wait4

Alternative system call to wait(2) for waiting for a process to stop. This routine calls the waitid(2) system call.

Signals

The SunOS 4.1 signal handlers and default actions are different from the SunOS 5.x signals.

The following routines are in the compatibility package:

TABLE 2-5 Signals

	Signals	
_longjmp	sigblock	sigpause
_setjmp	siginterrupt	sigsetmask
longjmp	sigmask	sigstack
psignal	signal	sigvec
setjmp		

The SunOS 4.1 style of signal handling is provided in the compatibility package. These routines invoke existing SunOS 5.x signal handling routines. These routines reside in libucb.

_longjmp, longjmp, _setjmp, and setjmp

In the SunOS 4.1 release, setjmp and longjmp save and restore the signal mask. This functionality has been preserved with the sigsetjmp and siglongjmp signals, respectively.

psignal

In the SunOS 4.1 release, psignal flushes stdio buffers, The SunOS 5.x version of psignal does not. This behavior has been preserved in the compatibility version.

sigblock and sigsetmask

In the SunOS 4.1 release, sigblock blocks a signal; sigsetmask sets a signal mask. sigblock and sigsetmask call the sigprocmask(2) system call.

siginterrupt, signal, sigvec and sigaction

In the SunOS 4.1 release, `siginterrupt` is a library function that allows signal interruptions; `signal` is a library function for simplified signal processing. Both now call `sigvec`, which itself calls the `sigaction` routine.

`sigpause`

Releases block signals; waits for interrupts. Implemented in the compatibility package through `sigsuspend`.

Library Routines

The Source Compatibility Package includes a set of compatibility libraries. These libraries can be found in `/usr/ucplib`, and they consist of:

- Routines not in the default SunOS 5.x system
- Routines having different interfaces or different system call “wrappers” than their SunOS 5.x counterparts

The routines in Table 2-6 are available with the compatibility package. Routines shown below in bold also exist in the default system:

TABLE 2-6 Library Routines

Library Routines		
<code>alphasort</code>	<code>printf</code>	<code>setvbuf</code>
<code>bcmp</code>	<code>rand</code>	<code>sleep</code>
<code>bcopy</code>	<code>random</code>	<code>sprintf</code>
<code>bzero</code>	<code>re_comp</code>	<code>srand</code>
<code>fopen</code>	<code>re_exec</code>	<code>srandom</code>
<code>fprintf</code>	<code>readdir</code>	<code>sys_siglist</code>
<code>freopen</code>	<code>rindex</code>	<code>times</code>
<code>ftime</code>	<code>scandir</code>	<code>ualarm</code>
<code>getwd</code>	<code>setbuf</code>	<code>usleep</code>
<code>index</code>	<code>setbuffer</code>	<code>vfprintf</code>
<code>initstate</code>	<code>setlinebuf</code>	<code>vprintf</code>

TABLE 2-6 Library Routines (continued)

Library Routines		
nice	setstate	vsprintf
nlist		

Compatibility library routines are placed in one of the following libraries: libcurses, libdbm, librpcsoc, libtermcap, and libuch.

The descriptions of the routines found in these libraries are divided by the libraries. Many of these routines are not included in the default SunOS 5.x libraries, but are useful enough to be retained for backward compatibility.

The routines in Table 2-6 are included in compatibility libraries for backwards compatibility purposes. At some later date these routines may not be supported and may eventually be discarded.

Routines in libcurses

The routines listed in Table 2-7 are available in the /usr/ucblib version of libcurses. Those routines shown in bold are also available in the default libcurses. The source compatibility version of libcurses uses termcap, while the base version uses terminfo.

TABLE 2-7 Curses Routines

Curses Routines		
box	overlay	wclrtoeol
delwin	overwrite	wclrtoeol
endwin	plod	wdelch
fgoto	plodput	wdeleteln
fullname	printw	werase
getcap	scanw	wgetch
gettmode	scroll	wgetstr
idllok	setterm	winsch

TABLE 2-7 Curses Routines (continued)

Curses Routines		
initscr	subwin	winsertln
longname	tabcol	wmove
mvcur	touchline	wprintw
mvprintw	touchoverlap	wrefresh
mvscanw	touchwin	wscanw
mvwin	tstp	wstandend
mvwprintw	waddch	wstandout
mvwscanw	waddstr	zap
newwin	wclear	

Routines in libdbm

libdbm contains the following routines: `dbmclose`, `dbmdelete`, `fetch`, `firstkey`, `nextkey`, and `store`. These routines maintain key/content pairs in a database using database routines. They are packaged in `/usr/ucblib/libdbm`. For more information, see the appropriate manual pages. These routines are superseded by the libndbm routines in the default system.

Routines in libtermcap

libtermcap contains the following routines: `tgetent`, `tgetnum`, `tgetflag`, `tgetstr`, `tgoto`, and `tputs`.

Routines in librpcsoc

librpcsoc contains the following routines: `clnttcp_create`, `clntudp_bufcreate`, `clntudp_create`, `rtime`, `svcf_create`, `svctcp_create`, `svcdp_bufcreate`, `svcdp_create`, and `svcdp_enablecache`.

Routines found in this library expect a socket descriptor as an argument.

Routines in libucb

alphasort and scandir

These routines combine the functions of `readdir` and `qsort` to process directory information. `scandir` reads a directory and builds an array of pointers to directory entries, returning the number of entries in the array and a pointer to the array through the parameter, `namelist`. `namelist` is a pointer to an arrangement of directory structure pointers. If the directory cannot be opened for reading or if `malloc` cannot allocate enough memory to hold all the data structures, `scandir` returns `-1`. `alphasort` is a routine that alphabetically sorts an array of pointers to directory entries (built by the routine, `scandir`).

These routines are not available in the default SunOS 5.x release.

bcmp, bcopy, and bzero

Functionally equivalent to the `memcmp`, `memcpy`, and `memset` routines, see `memory(3C)`. `bcopy` copies bytes, handling overlapping strings correctly. `bcmp` compares bytes, returning zero if they are identical, non-zero otherwise. `bzero` zeros out bytes. These routines are not available in the default SunOS 5.x release.

fopen and freopen

The SunOS 5.x and SunOS 4.1 versions differ in the handling of the `a` type. If mode `a` is specified, the SunOS 5.x version opens the file with `O_APPEND` set, while the SunOS 4.1 version doesn't. Also, the SunOS 4.1 version always seeks to the end of the file when mode `a` is specified, while the SunOS 5.x version seeks to the end of the file if update mode is not specified.

ftime

Returns a structure that contains elements showing the elapsed time since the epoch (00:00:00, January 1st, 1970). See `ctime(3C)`. This routine is not available in the default SunOS 5.x release.

getwd

Similar to `getcwd`. `getwd` returns the pathname of the current working directory, or `NULL` if there is an error. The return value of `getwd` is placed in a character string allocated by the caller. This routine is not available in the default SunOS 5.x release.

index and rindex

`index` returns a pointer to the first occurrence of a single character in a null-terminated character string. If the character does not occur in the string, `index` returns a `NULL` pointer. In the SunOS 5.x release, `strchr` replaces `index`, see `string(3C)`.

rindex returns a pointer to the last occurrence of a single character in a null-terminated string, or a NULL pointer if the letter does not occur in the string. In the SunOS 5.x release, strchr replaces rindex, see string(3C).

These routines are not available in the default SunOS 5.x release.

initstate, random, setstate, and srandom

Random number generator routines relied on by many user programs in the SunOS 4.1 release. These routines are not available in the default SunOS 5.x release.

See rand(3C), **rand**(3C) srand(3C) **srand**(3C), and drand(3C) **drand48**(3C) in the *Solaris 7 Reference Manual Collection*.

nice

The SunOS 4.1 version always returns 0 if successful. The SunOS 5.x version returns the new nice value minus 20.

nlist

If unsuccessful, returns the number of symbols that were not located in the symbol table. (The SunOS 5.x version returns -1 if unsuccessful.) Also, nlist takes a file name as an argument, rather than a file descriptor.

printf, fprintf, sprintf, vfprintf, vprintf, and vsprintf

The following differences exist for these functions:

- In the SunOS 4.1 release, sprintf returns a pointer to its first argument; in the SunOS 5.x release, it returns the count of characters printed.
- In the SunOS 4.1 release, printf and vprintf always return the number of characters printed or EOF, while the SunOS 5.x version returns only EOF in case of an error.
- fprintf and vfprintf share the same differences as printf and vprintf (above); additionally, the buffering scheme for these routines is different for the SunOS 5.x and SunOS 4.1 release.

rand and srand

The SunOS 5.x returns the generated number shifted to the right by 16 and anded with 0x7fff, while the SunOS 4.1 release returns the generated number anded with 0x7fffffff.

re_comp and re_exec

These routines are similar to the regcmp(3G) and regex routines. re_comp compiles the regular expression in a string, returning 0 if it compiled successfully or returning a pointer to an error message if it did not. regcmp, on the other hand, returns a pointer to the compiled form or NULL if given an incorrect argument. re_exec returns 1 if the string s matches the last compiled regular expression, 0 if it fails to match, and -1 if the regular expression is invalid. regex, however, returns NULL on failure or a pointer to the next unmatched character on success.

readdir

Reads a directory entry. The SunOS 4.1 release `readdir` routine returns a pointer to `struct direct`, while the SunOS 5.x version returns a pointer to `struct dirent`.

`setbuffer` and `setlinebuf`

These routines are used to provide control over the buffering used for input and output.

Similar to `setbuf(3S)` and `setvbuf`, `setbuffer` may be used after a stream has been opened but before it is read or written. It uses the array pointer instead of an automatically allocated buffer. If the buffer is the `NULL` pointer, input/output is completely unbuffered.

`setlinebuf` is used to change the buffering on a stream from block buffered or unbuffered to line buffered. It can be used at any time that the file descriptor is active.

These routines are not available in the default SunOS 5.x release.

`sleep`

The SunOS 5.x version returns the “unslept” amount, that is, the requested time minus the time actually slept. The SunOS 4.1 version does not return anything.

`sys_siglist`

An array containing a message string for each SunOS 4.1 signal number.

`times`

The SunOS 4.1 version returns 0 when successful. The SunOS 5.x version returns the elapsed real time in clock ticks per second from an arbitrary point in the past.

`ualarm` and `usleep`

Simplified interfaces to the system calls handling high-resolution timers. These routines are not available in the default SunOS 5.x release.

Header Files

The Source Compatibility Package header files can be found in `/usr/ucbinclude`. Differences remain in the case of header files, and you should be aware of them; in some cases it was impossible to achieve complete source compatibility. Some SunOS 4.1 header files do not exist in the default SunOS 5.x release. The header files in bold are also available in the default system.

TABLE 2-8 Header Files

Header Files		
a.out.h	struct.h	sys/tty.h
assert.h	sys/dir.h	sys/ttychars.h
curses.h	sys/fcntl.h	sys/types.h
dbm.h	sys/file.h	sys/vfs.h
fcntl.h	sys/ioctl.h	sys/wait.h
regexp.h	sys/param.h	syscall.h
resolv.h	sys/reboot.h	sysexit.h
setjmp.h	sys/resource.h	ufs/quota.h
sgtty.h	sys/rusage.h	unistd.h
signal.h	sys/signal.h	vfont.h
stdio.h	sys/sysmacros.h	vfork.h
strings.h		

As with the library routines, there are some header files under SunOS 5.x that differ slightly from their SunOS 4.1 counterparts. In those instances, the affected header files are included in this compatibility package with as many additions as possible to keep them compatible with SunOS 4.1. The following list shows those files affected and the reasons for their inclusion in this package:

a.out.h

Included for compatibility.

assert.h

Included for compatibility.

curses.h

Included for compatibility.

dbm.h

Used by routines in libdbm and user programs invoking libdbm.

fcntl.h

Included for compatibility.

regex.h

Includes ctype.h for compatibility.

resolv.h

Included for compatibility.

setjmp.h

Includes additional #defines and #includes for compatibility.

sgtty.h

Included for compatibility.

signal.h

Contains sys/signal.h. Included here for compatibility.

stdio.h

Includes SunOS 4.1-specific definitions.

strings.h

Contains the same type of information as string.h.

struct.h

Contains useful macros.

sys/dir.h

Included for compatibility.

sys/fcntl.h

Includes missing #defines.

sys/file.h

Includes missing #defines such as L_SET, and L_INCR.

sys/ioctl.h

Included for compatibility.

sys/param.h

Includes missing #defines.

sys/reboot.h

Included for compatibility.

sys/resource.h

Includes the rusage structure missing from the SunOS 5.x version of resource.h and used by the getrusage function.

sys/rusage.h

Includes the rusage structure.

sys/signal.h

Includes SunOS 4.1-specific data structures and definitions.

sys/sysmacros.h

Included for compatibility.

sys/tty.h

Included for compatibility.

sys/ttychars.h

Included for compatibility.

sys/types.h

Includes the sys/sysmacros header files and additional type definitions.

sys/vfs.h

Includes sys/statfs header file.

sys/wait.h

Includes declarations required by the wait3 system call wrapper.

syscall.h

Included for compatibility.

sysexits.h

Contains useful exit codes.

ufs/quota.h

Includes sys/fs.ufs_quota.h. Added for compatibility.

unistd.h

Includes #defines missing in the SunOS 5.x version of this file.

vfont.h

Included for compatibility.

vfork.h

Included for compatibility.