



# **Sun Java System Application Server Enterprise Edition 8.1 2005Q2 Reference Manual**



Sun Microsystems, Inc.  
4150 Network Circle  
Santa Clara, CA 95054  
U.S.A.

Part No: 819-2558  
July 2005

Copyright 2005 Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, CA 95054 U.S.A. All rights reserved.

This product or document is protected by copyright and distributed under licenses restricting its use, copying, distribution, and decompilation. No part of this product or document may be reproduced in any form by any means without prior written authorization of Sun and its licensors, if any. Third-party software, including font technology, is copyrighted and licensed from Sun suppliers.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, docs.sun.com, AnswerBook, AnswerBook2, and Solaris are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc.

The OPEN LOOK and Sun™ Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

U.S. Government Rights – Commercial software. Government users are subject to the Sun Microsystems, Inc. standard license agreement and applicable provisions of the FAR and its supplements.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

---

Copyright 2005 Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, CA 95054 U.S.A. Tous droits réservés.

Ce produit ou document est protégé par un copyright et distribué avec des licences qui en restreignent l'utilisation, la copie, la distribution, et la décompilation. Aucune partie de ce produit ou document ne peut être reproduite sous aucune forme, par quelque moyen que ce soit, sans l'autorisation préalable et écrite de Sun et de ses bailleurs de licence, s'il y en a. Le logiciel détenu par des tiers, et qui comprend la technologie relative aux polices de caractères, est protégé par un copyright et licencié par des fournisseurs de Sun.

Des parties de ce produit pourront être dérivées du système Berkeley BSD licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, docs.sun.com, AnswerBook, AnswerBook2, et Solaris sont des marques de fabrique ou des marques déposées, de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays. Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

L'interface d'utilisation graphique OPEN LOOK et Sun a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciés de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui en outre se conforment aux licences écrites de Sun.

CETTE PUBLICATION EST FOURNIE "EN L'ETAT" ET AUCUNE GARANTIE, EXPRESSE OU IMPLICITE, N'EST ACCORDEE, Y COMPRIS DES GARANTIES CONCERNANT LA VALEUR MARCHANDE, L'APTITUDE DE LA PUBLICATION A REpondre A UNE UTILISATION PARTICULIERE, OU LE FAIT QU'ELLE NE SOIT PAS CONTREFAISANTE DE PRODUIT DE TIERS. CE DENI DE GARANTIE NE S'APPLIQUERAIT PAS, DANS LA MESURE OU IL SERAIT TENU JURIDIQUEMENT NUL ET NON AVENU.

# Contents

---

<b>Preface</b> .....	11
<b>User Commands</b> .....	13
add-resources(1) .....	14
appclient(1) .....	17
asadmin(1M) .....	19
asant(1M) .....	22
asmigrate(1m) .....	25
asupgrade(1) .....	29
backup-domain(1) .....	33
capture-schema(1m) .....	34
change-master-password(1) .....	36
clear-ha-store(1) .....	38
configure-ha-cluster(1) .....	40
configure-ha-persistence(1) .....	42
copy-config(1) .....	48
create-admin-object(1) .....	50
create-application-ref(1) .....	52
create-audit-module(1) .....	54
create-auth-realm(1) .....	56
create-cluster(1) .....	58
create-connection-group(1) .....	61
create-connector-connection-pool(1) .....	62
create-connector-resource(1) .....	65
create-connector-security-map(1) .....	67
create-custom-resource(1) .....	70
create-domain(1) .....	72
create-file-user(1) .....	75
create-ha-store(1) .....	77

create-http-health-checker(1) .....	79
create-http-lb-config(1) .....	81
create-http-lb-ref(1) .....	84
create-http-listener(1) .....	86
create-iiop-listener(1) .....	89
create-instance(1) .....	91
create-javamail-resource(1) .....	95
create-jdbc-connection-pool(1) .....	98
create-jdbc-resource(1) .....	102
create-jmsdest(1) .....	104
create-jms-host(1) .....	107
create-jms-resource(1) .....	109
create-jndi-resource(1) .....	114
create-jvm-options(1) .....	117
create-lifecycle-module(1) .....	119
create-message-security-provider(1) .....	122
create-node-agent(1) .....	127
create-node-agent-config(1) .....	129
create-password-alias(1) .....	131
create-persistence-resource(1) .....	133
create-profiler(1) .....	136
create-resource-adapter-config(1) .....	138
create-resource-ref(1) .....	140
create-ssl(1) .....	142
create-system-properties(1) .....	146
create-threadpool(1) .....	148
create-virtual-server(1) .....	151
delete-admin-object-1(1) .....	155
delete-application-ref(1) .....	157
delete-audit-module(1) .....	159
delete-auth-realm(1) .....	161
delete-cluster(1) .....	163
delete-config(1) .....	165
delete-connection-group(1) .....	167
delete-connector-connection-pool(1) .....	168
delete-connector-resource(1) .....	170
delete-connector-security-map(1) .....	172

---

delete-custom-resource(1)	174
delete-domain(1)	176
delete-file-user(1)	177
delete-http-health-checker(1)	179
delete-http-lb-config(1)	181
delete-http-lb-ref(1)	183
delete-http-listener(1)	185
delete-iiop-listener(1)	187
delete-instance(1)	189
delete-javamail-resource(1)	191
delete-jdbc-connection-pool(1)	193
delete-jdbc-resource(1)	195
delete-jmsdest(1)	197
delete-jms-host(1)	199
delete-jms-resource(1)	201
delete-jndi-resource(1)	203
delete-jvm-options(1)	205
delete-lifecycle-module(1)	207
delete-message-security-provider(1)	209
delete-node-agent(1)	211
delete-node-agent-config(1)	212
delete-password-alias(1)	214
delete-persistence-resource(1)	216
delete-profiler(1)	218
delete-resource-adapter-config(1)	220
delete-resource-ref(1)	222
delete-ssl(1)	224
delete-system-property(1)	226
delete-threadpool(1)	228
delete-virtual-server(1)	230
deploy(1)	232
deploydir(1)	238
deploytool(1m)	242
disable(1)	243
disable-http-lb-application(1)	245
disable-http-lb-server(1)	247
enable(1)	249

---

enable-http-lb-application(1) .....	251
enable-http-lb-server(1) .....	253
export(1) .....	255
export-http-lb-config(1) .....	256
freeze-transaction-service(1) .....	258
get(1) .....	260
get-client-stubs(1) .....	262
hadbm(1m) .....	264
hadbm-addnodes(1) .....	266
hadbm-clear(1) .....	269
hadbm-clearhistory(1) .....	271
hadbm-create(1) .....	273
hadbm-createdomain(1) .....	279
hadbm-definedomain(1) .....	281
hadbm-delete(1) .....	283
hadbm-deletedomain(1) .....	284
hadbm-deviceinfo(1) .....	285
hadbm-disablehost(1) .....	287
hadbm-extenddomain(1) .....	288
hadbm-get(1) .....	289
hadbm-help(1) .....	292
hadbm-list(1) .....	294
hadbm-listdomain(1) .....	295
hadbm-listpackages(1) .....	296
hadbm-ma(1) .....	297
hadbm-reducedomain(1) .....	299
hadbm-refragment(1) .....	301
hadbm-registerpackage(1) .....	303
hadbm-resourceinfo(1) .....	305
hadbm-restart(1) .....	307
hadbm-restartnode(1) .....	309
hadbm-set(1) .....	311
hadbm-start(1) .....	314
hadbm-startnode(1) .....	315
hadbm-status(1) .....	317
hadbm-stop(1) .....	319
hadbm-stopnode(1) .....	320

---

hadbm-unregisterpackage(1) .....	322
hadbm-version(1) .....	323
help(1) .....	324
jms-ping(1) .....	331
jspc(1M) .....	333
list(1) .....	335
list-admin-objects(1) .....	339
list-application-refs(1) .....	341
list-audit-modules(1) .....	343
list-auth-realms(1) .....	345
list-backups(1) .....	347
list-clusters(1) .....	348
list-components(1) .....	350
list-configs(1) .....	352
list-connection-groups(1) .....	354
list-connector-connection-pools(1) .....	355
list-connector-resources(1) .....	357
list-connector-security-maps(1) .....	359
list-custom-resources(1) .....	362
list-domains(1) .....	364
list-file-groups(1) .....	365
list-file-users(1) .....	367
list-http-lb-configs(1) .....	369
list-http-listeners(1) .....	371
list-iiop-listeners(1) .....	373
list-instances(1) .....	375
list-javamail-resources(1) .....	377
list-jdbc-connection-pools(1) .....	379
list-jdbc-resources(1) .....	381
list-jmsdest(1) .....	383
list-jms-hosts(1) .....	385
list-jms-resources(1) .....	387
list-jndi-entries(1) .....	389
list-jndi-resources(1) .....	391
list-lifecycle-modules(1) .....	393
list-message-security-providers(1) .....	395
list-node-agents(1) .....	397

---

list-password-aliases(1)	399
list-persistence-resources(1)	401
list-resource-adapter-configs(1)	403
list-resource-refs(1)	405
list-sub-components(1)	407
list-system-properties(1)	409
list-threadpools(1)	411
list-timers(1)	413
list-transaction-id(1)	415
list-virtual-servers(1)	417
migrate-timers(1)	419
multimode(1)	421
package-applient(1M)	422
ping-connection-pool(1)	424
ping-connection-pools(1)	426
recover-transactions(1)	428
remove-ha-cluster(1)	430
restore-domain(1)	432
rollback-transaction(1)	433
set(1)	435
show-component-status(1)	437
shutdown(1)	439
start-cluster(1)	440
start-domain(1)	442
start-instance(1)	444
start-node-agent(1)	446
stop-cluster(1)	448
stop-domain(1)	450
stop-instance(1)	452
stop-node-agent(1)	454
undeploy(1)	455
unfreeze-transaction-service(1)	458
unset(1)	460
update-connector-security-map(1)	461
update-file-user(1)	464
update-password-alias(1)	466
verifier(1M)	468



verify-domain-xml(1) .....470

version(1) .....471

wscompile(1M) .....473

wsdeploy(1M) .....477

  

**Index** .....481



# Preface

---

Both novice users and those familiar with the SunOS operating system can use online man pages to obtain information about the system and its features. A man page is intended to answer concisely the question “What does it do?” The man pages in general comprise a reference manual. They are not intended to be a tutorial.

## Overview

The following contains a brief description of each man page section and the information it references:

- Section 1 describes, in alphabetical order, the `asadmin` utility commands.
- Section 1M describes all the other Application Server utility commands.

Below is a generic format for man pages. The man pages of each manual section generally follow this order, but include only needed headings. For example, if there are no bugs to report, there is no BUGS section.

NAME	This section gives the names of the commands or functions documented, followed by a brief description of what they do.
SYNOPSIS	This section shows the syntax of commands or functions.  The following special characters are used in this section:  [ ]        Brackets. The option or argument enclosed in these brackets is optional. If the brackets are omitted, the argument must be specified.            Separator. Only one of the arguments separated by this character can be specified at a time.
DESCRIPTION	This section defines the functionality and behavior of the service. Thus it describes concisely what the command does. It does not discuss OPTIONS or cite EXAMPLES. Interactive commands, subcommands, requests, macros, and functions are described under USAGE.
OPTIONS	This section lists the command options with a concise summary of what each option does. The options are listed literally and in the

	order they appear in the SYNOPSIS section. Possible arguments to options are discussed under the option, and where appropriate, default values are supplied.
OPERANDS	This section lists the command operands and describes how they affect the actions of the command.
EXAMPLES	This section provides examples of usage or of how to use a command or function. Wherever possible a complete example including command-line entry and machine response is shown. Whenever an example is given, the prompt is shown as <code>example%</code> , or if the user must be superuser, <code>example#</code> . Examples are followed by explanations, variable substitution rules, or returned values. Most examples illustrate concepts from the SYNOPSIS, DESCRIPTION, OPTIONS, and USAGE sections.
EXIT STATUS	This section lists the values the command returns to the calling program or shell and the conditions that cause these values to be returned. Usually, zero is returned for successful completion, and values other than zero for various error conditions.
SEE ALSO	This section lists references to other man pages, in-house documentation, and outside publications.
NOTES	This section lists additional information that does not belong anywhere else on the page. It takes the form of an aside to the user, covering points of special interest. Critical information is never covered here.
BUGS	This section describes known bugs and, wherever possible, suggests workarounds.

REFERENCE

User Commands

**Name** add-resources – creates the resources specified in an XML file

**Synopsis** **add-resources** **—user** *admin\_user* [**—passwordfile** *filename*] [**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**-s**] [**—terse**=*false*] [**—echo**=*false*] [**—interactive**=*true*] [**—help**] [**—target** *target*] *xml\_file\_path*

**Description** The add-resources command creates the resources named in the specified XML file. The *xml\_file\_path* is the path to the XML file containing the resources to be created. The DOCTYPE should be specified as *install\_dir/lib/dtds/sun-resources\_1\_0.dtd* in the resources.xml file.

This command is supported in remote mode only.

<b>Options</b> <b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.

<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target for which you are creating the resources. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, which creates the resources for the default server instance <code>server</code> and is the default value</li> <li>▪ <code>domain</code>, which creates the resources for the domain</li> <li>▪ <code>cluster_name</code>, which creates the resources for every server instance in the cluster</li> <li>▪ <code>instance_name</code>, which creates the resources for a particular server instance</li> </ul>

**Operands** *xml\_file\_path*

The path to the XML file containing the resource(s) to be created.

An example XML file follows. Replace `<install_dir>` with the location of your Application Server installation.

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE resources PUBLIC
"-//Sun Microsystems Inc.//DTD Application Server 8.0 Domain//EN"
"*<install_dir>/lib/dtds/sun-resources_1_0.dtd*">

<resources>
<jdbc-connection-pool name="SPECjPool" steady-pool-size="100"
max-pool-size="150" max-wait-time-in-millis="60000"
pool-resize-quantity="2" idle-timeout-in-seconds="300"
is-isolation-level-guaranteed="true"
is-connection-validation-required="false"
connection-validation-method="auto-commit"
fail-all-connections="false"
datasource-classname="oracle.jdbc.pool.OracleDataSource">
<property name="URL"
value="jdbc:oracle:thin:@iasperfsol12:1521:specdb"/>
<property name="User" value="spec"/>
<property name="Password" value="spec"/>
<property name="MaxStatements" value="200"/>
<property name="ImplicitCachingEnabled" value="true"/>
</jdbc-connection-pool>
<jdbc-resource enabled="true" pool-name="SPECjPool"
jndi-name="jdbc/SPECjDB"/>
</resources>
```

**Examples** EXAMPLE 1 Using the add-resources command

The following command creates resources using the contents of the XML file resource.xml:

```
asadmin> add-resources --user admin --passwordfile passwords.txt  
--host localhost --port 4848 resource.xml
```

Command add-resources executed successfully.

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [create-jdbc-connection-pool\(1\)](#), [create-jdbc-resource\(1\)](#), [create-jms-resource\(1\)](#),  
[create-jndi-resource\(1\)](#), [create-javamail-resource\(1\)](#), [create-persistence-resource\(1\)](#),  
[create-custom-resource\(1\)](#)



- 
- Name** appclient – launches the Application Client Container and invokes the client application packaged in the application JAR file
- Synopsis** **appclient** **—client** *client\_application\_jar*  
 [—mainclass *client\_application\_main\_classname*]— name *display\_name*  
 [—xml *sun-acc.xml file*] [—textauth] [—user *username*] [—password *password*]
- Description** Use the appclient command to launch the application client container and invoke a client application that is packaged in an application JAR file. The application client jar file is psecified and created during deployment either by the deploytool or by using the asadmin deploy command.
- The application client container is a set of java classes, libraries and other files that are required to execute a first-tier application client program on a Java Virtual Machine (JVM). The application client container communicates with the Application Server using RMI-IIOP.
- The `client.jar` that is retrieved after deploying an application , should be passed with the `-client` option while running the appclient utility. The `-mainclass` and `-name` options are optional for a single client application. For multiple client applications use either the `-classname` option or the `-name` option.
- Interface Stability** Sun often provides developers with early access to new technologies, which allows developers to evaluate with them as soon as possible. Unfortunately, new technologies are prone to changes and standardization often results in interface incompatibility from previous versions.
- To make reasonable risk assessments, developers need to know how likely an interface is to change in future releases. To aid developers in making these assessments, interface stability information is included on some manual pages for commands, entry-points, and file formats.
- The more stable interfaces can safely be used by nearly all applications, because Sun will endeavor to ensure that these continue to work in future minor releases. Applications that depend only on Standard and Stable interfaces should reliably continue to function correctly on future minor releases (but not necessarily on earlier major releases).
- The less stable interfaces allow experimentation and proto-typing, but should be used only with the understanding that they might change incompatibly or even be dropped or replaced with alternatives in future minor releases.
- "Interfaces" that Sun does not document (for example, most kernel data structures and some symbols in system header files) may be implementation artifacts. Such internal interfaces are not only subject to incompatible change or removal, but we are unlikely to mention such a change in release notes.
- Options** **—client** required; the name and location for the client application jar file. The application client JAR file is specified and created during deployment, either by the `deploytool` or by the `asadmin deploy` command.
- mainclass** optional; the full classname of the main client application `main()` method that will be invoked by the Application Client

	Container. Used for a single client application. By default, uses the class specified in the <code>client.jar</code> . The class name must be the full name. For example, <code>com.sun.test.AppClient</code>
<code>--name</code>	optional; the display name for the client application. Used for multiple client applications. By default, the display name is specified in the <code>client.jar</code> <code>application-client.xml</code> file which is identified by the <code>display-name</code> attribute.
<code>--xml</code>	optional if using the default domain and instance, otherwise it is required; identifies the name and location of the client configuration XML file. If not specified, defaults to the value of <code>\$AS_ACC_CONFIG</code> identified in <code>asenv.conf</code> file.
<code>--textauth</code>	optional; used to specify using text format authentication when authentication is needed.

**Examples** EXAMPLE 1 Using the `appclient` command

```
appclient -client appserv/bin/myclientapp.jar  
-mainclass com.sun.test.TestAppClient -xml sun-acc.xml scott sample
```

Where: *appserv/bin/myclientapp.jar* is the full path for the client application .jar file, *com.sun.test.TestAppClient* is the full Java package name of the main client application, *scott* and *sample* are arguments to pass to the application, and *sun-acc.xml* is the name of the client configuration XML file. If *sun-acc.xml* is not in the current directory, you must give the absolute path location; otherwise the relative path is used. The relative path is relative to the directory where the command is being executed.

**See Also** [package-appclient\(1M\)](#), [asadmin\(1M\)](#)

**Name** asadmin – utility for performing administrative tasks for the Sun Java System Application Server

**Synopsis** **asadmin** *subcommand*[-short\_option[short\_option\_argument]]\*  
 [--long\_option[long\_option\_argument]]\* [*operand*]\*

**Description** Use the asadmin utility to perform any administrative task for the Sun Java System Application Server. You can use this utility in place of using the Administration Console interface.

The *subcommand* identifies the operation or task you wish to perform. Subcommands are case-sensitive. Short option arguments have a single dash (-); while long option arguments have two dashes (--). Options modify how the utility performs a subcommand. Options are also case-sensitive. Most options require argument values except boolean options which toggle to switch a feature ON or OFF. Operands appear after the argument values, and are set off by a space, a tab, or double dashes (—). The asadmin utility treats anything that comes after the options and their values as an operand.

Local subcommands can be executed without the presence of an administration server. However, it is required that the user be logged into the machine hosting the domain in order to execute the subcommand and have access (permissions) for the installation and domain directories.

Remote subcommands are always executed by connecting to an administration server and executing the subcommand there. A running administration server is required. All remote subcommands require the following options:

-u --user	authorized domain application server administrative username.
-w --password	password to administer the domain application server.
	The —password option is deprecated. Use —passwordfile instead.
—passwordfile	The file containing the domain application server password in the following form: AS_ADMIN_PASSWORD= <i>password</i> . Where <i>password</i> is the actual administrator password.
-H --host	machine name where the domain application server is running.
-p --port	port number of the domain application server listening for administration requests. The default port number for Platform Edition is 4848. The default port number for Enterprise Edition is 4949.
-s --secure	if true, uses SSL/TLS to communicate with the domain application server.
-t --terse	indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
-e --echo	setting to true will echo the command line statement on the standard output. Default is false.

- `-I --interactive` if set to true (default), only the required password options are prompted.
- `-h --help` displays the help text for the command.

For security purposes, you can set the password for a subcommand from a file instead of entering the password at the command line. The `--passwordfile` option takes the file containing the passwords. The valid contents for the file are:

```
AS_ADMIN_PASSWORD=value
AS_ADMIN_ADMINPASSWORD=value
AS_ADMIN_USERPASSWORD=value
AS_ADMIN_MASTERPASSWORD=value
```

If `AS_ADMIN_PASSWORD` has been exported to the global environment, specifying the `--passwordfile` option will produce a warning using about the `--password` option. Unset `AS_ADMIN_PASSWORD` to prevent this from happening.

The master password is not propagated on the command line or an environment variable, but can be specified in the `passwordfile`.

To use the `--secure` option, you must use the `set` command to enable the `security-enabled` flag in the `admin http-listener` in the `domain.xml`.

When you use the `asadmin` subcommands to create and/or delete, you must restart the server for the newly created command to take affect. Use the `start-domain` command to restart the server.

To access the manpages for the Application Server command-line interface subcommands on the Solaris platform, add `$AS_INSTALL/man` to your `MANPATH` environment variable.

You can obtain overall usage information for any of the `asadmin` utility subcommands by invoking the `--help` option. If you specify a subcommand, the usage information for that subcommand is displayed. Using the `help` option without a subcommand displays a listing of all the available subcommands.

**Interface Stability** Sun often provides developers with early access to new technologies, which allows developers to evaluate with them as soon as possible. Unfortunately, new technologies are prone to changes and standardization often results in interface incompatibility from previous versions.

To make reasonable risk assessments, developers need to know how likely an interface is to change in future releases. To aid developers in making these assessments, interface stability information is included on some manual pages for commands, entry-points, and file formats.

The more stable interfaces can safely be used by nearly all applications, because Sun will endeavor to ensure that these continue to work in future minor releases. Applications that depend only on Standard and Stable interfaces should reliably continue to function correctly on future minor releases (but not necessarily on earlier major releases).

The less stable interfaces allow experimentation and proto-typing, but should be used only with the understanding that they might change incompatibly or even be dropped or replaced with alternatives in future minor releases.

"Interfaces" that Sun does not document (for example, most kernel data structures and some symbols in system header files) may be implementation artifacts. Such internal interfaces are not only subject to incompatible change or removal, but we are unlikely to mention such a change in release notes.

**See Also** [appclient\(1M\)](#), [package-appclient\(1M\)](#)

**Name** asant – launches the Jakarta Ant tool

**Synopsis** `asant target_list`

**Description** Use the `asant` command to automate repetitive development and deployment tasks. `asant` is a shell script that invokes the underlying Ant infrastructure after initializing the environment to pick up the application server installed targets.

To use Ant as part of the Sun Java System Application Server, verify that your `PATH` includes the provided `asant` (UNIX) or `ant.bat` (Windows) script.

The bundled sample applications use `asant` extensively; however, `asant` can be used in any development or operational environments.

The build targets are represented in the `build.xml` files that accompany the sample applications.

To use the Ant tool to compile and reassemble the sample applications, verify that the `$AS_INSTALL/bin` directory is on your environment's path. On UNIX, add the `$AS_INSTALL/bin` directory to your `PATH` environment variable. On Windows, after installing the Sun ONE Application Server, set the system path by adding `$AS_INSTALL\bin` to the user `PATH`. You can access the `PATH` system variable from: Start menu, Settings, Control Panel, System, Advanced, Environment Variables, User Variables for Administrator, `PATH`.

The `target_list` is one or more space separated tasks as described below.

<b>Targets</b>	<code>compile</code>	compiles all Java source code.
	<code>jar</code>	assembles the EJB JAR module.
	<code>war</code>	assembles the WAR file in <code>sample_dir/assemble/war</code>
	<code>ear</code>	assembles the EAR file in <code>sample_dir/assemble/ear</code>
	<code>core</code>	(default) compiles all sources, builds stubs and skeletons; and assembles EJB JAR, WAR and EAR files. This is the default target for all <code>build.xml</code> files shipped in the Sun ONE Application Server.
	<code>javadocs</code>	creates Java docs in <code>sample_dir/javadocs</code>
	<code>all</code>	builds core and javadocs, verifies and deploys the application, and adds the resources..
	<code>deploy</code>	deploys the application and automatically expands the EJB JAR; does not install Javadocs.
	<code>undeploy</code>	removes the deployed sample from the Sun Java System Application Server.
	<code>clean</code>	removes <code>appname/build/</code> and <code>appname/assemble/</code> and <code>appname/javadocs</code> directories.

`verify` verifies the deployment descriptors in the sample.

**Examples** EXAMPLE 1 Compiling and Assembling a Sample Application

Using the simple stateless EJB sample as an example, execute several of the build targets as follows:

```
cd install_root/samples/ejb/stateless/simple/src
```

Execute the `compile` target to compile the Java sources as follows:

```
asant compile
```

Execute the `war`, `ear`, and `ejbjar` target to assemble the J2EE module files and the EAR file as follows by:

```
asant jar  
asant war  
asant ear
```

Alternatively, all the above tasks can be accomplished by:

```
asant core
```

Since the default build target is `core` you can execute `asant` without any arguments to rebuild the entire application.

EXAMPLE 2 Building Web-based Applications

You can build everything, including installing Javadocs, and deploying the application by:

```
asant all
```

Additionally, you can build everything, except the Javadocs, but deploy the application by:

```
asant core  
or just,  
asant  
then,  
asant deploy
```

To rebuild the `ear` after you have modified the deployment descriptors without recompiling:

```
asant ear  
asant deploy
```

**See Also** See the Apache Software Foundation at <http://www.apache.org> and the Jakarta Ant documentation at <http://jakarta.apache.org/ant/index.html>.

SUNWant documentation is located in `/usr/sfw/share/doc/ant`.

See also [asadmin\(1M\)](#).

See the *Sun Java System Application Server Developer's Guide* for information about special Ant tasks you can use.



**Name** asmigrate – automates migration of J2EE applications from other J2EE platforms to Sun Java System Application Server

**Synopsis** **asmigrate** [-h | --help ] [-v | --version ] [( -c | --commandline ) | ( -u | --ui ) ] [-q | --quiet ] [-d | --debug ] [-s | --sourcedirectory *source\_directory*] [-S | --sourceserver *source\_application\_server*] [-t | --targetdirectory *target\_directory*] [-T | --targetserver *target\_application\_server*] [-n | --scan-native-apis-only ] [-p | --scan-packages *package\_list*] [-j | --java2db **create-tables=true, drop-tables=true, db-vendor-name=dbVendorName**] [-m | --migrate-cmp **comment-pk-modifiers=true, overwrite-conflicting-accessors=true**] [-f | --file-filter **all-files=true, html-files=true, java-files=true, jsp-files=true, xml-files=true, archive-files=true**] [-a | --append-logs ] [**operands**]

**Description** Use the asmigrate utility to analyze your J2EE application and translate vendor specific settings to Sun Java™ System Application Server specific settings that makes the application deployable on Sun's J2EE products.

The following table identifies the supported J2EE product migrations:

Source J2EE Platform	Destination J2EE Platform
WebLogic Application Server 5.1, 6.0, 6.1, 8.1	Sun Java™ System Application Server 8.1 2005Q1
WebSphere Application Server 4.0, 5.x	
Java™ 2 Platform Enterprise Edition 1.3/1.4	
Sun ONE Application Server 6.5, 7.0	
Sun Java™ System Application Server 7 2004Q2	
Sun ONE Web Server 6.0	
J2EE Reference Implementation 1.3, 1.4	
JBoss Application Server 3.0, 3.2	
Tomcat Web Server 4.1.12	

**Options**

- h --help displays the arguments for launching the MigrationTool.
- v --version displays the version of the MigrationTool.
- u --ui invokes the tool in user interface mode.
- c --commandline invokes the tool in command-line mode.
- q --quiet launches the tool in quiet mode.
- d --debug launches the tool in debug mode.

---

<code>-s --sourceDirectory</code>	identifies the directory where the source code to migrate or scan is present.
<code>-S --sourceserver</code>	identifies the source application server of the applications to be migrated. Possible servers include the following: <ul style="list-style-type: none"><li>▪ wl51: WebLogic Application Server 5.1</li><li>▪ wl60: WebLogic Application Server 6.0</li><li>▪ wl61: WebLogic Application Server 6.1</li><li>▪ wl81: WebLogic Application Server 8.1</li><li>▪ as65: Sun ONE Application Server 6.5</li><li>▪ as70: Sun ONE Application Server 7.0</li><li>▪ ws40: WebSphere Application Server 4.0</li><li>▪ ws50: WebSphere Application Server 5.x</li><li>▪ ri13: Java™ 2 Platform Enterprise Edition 1.3</li><li>▪ ri14: Java™ 2 Platform Enterprise Edition 1.3</li><li>▪ slws: Sun ONE Web Server</li><li>▪ jb30: JBoss Application Server 3.0</li><li>▪ tc41: Tomcat Application Server 4.1</li></ul>
<code>-t --targetDirectory</code>	target or output directory where the migrated application should be placed.
<code>-T --targetserver</code>	target application server to which the application is to be migrated. Use sjs80PE as the target server for Sun Java System Application Server 8.1 2005Q1.
<code>-n --scan-native-apis-only</code>	scans the source code only for the presence of application server specific proprietary APIs.
<code>-p --scan-packages</code>	comma-separated list of Java packages to scan.
<code>-j --java2db</code>	bypasses the creation of the <code>sun-cmp-mapping.xml</code> file. Instead, introduces the option argument into the <code>sun-ejb-jar.xml</code> file. Option arguments are: <ul style="list-style-type: none"><li>▪ <code>create-tables</code>: if set to true (default), creates tables at deploy. If set to false tables are not created.</li><li>▪ <code>drop-tables</code>: if set to true (default), tables are dropped at undeploy. If set to false tables are not dropped.</li><li>▪ <code>db-vendor-name</code>: name of the database vendor for the application to be migrated. Supported vendor names include: Oracle, Sybase, DB2, Generic SQL92, PointBase, MSSQL.</li></ul>
<code>-m --migrate-cmp</code>	migrates 1.1 compliant CMPs, if any, to 2.0. Option arguments are:

	<ul style="list-style-type: none"> <li>▪ <code>overwrite-conflicting-accessors</code>: if set to true (default), conflicting accessors are overwritten. If set to false, conflicting accessors are not overwritten.</li> <li>▪ <code>comment-pk-modifiers</code>: if set to true (default), setters of primary key are commented. If set to false, setters of primary key are not commented.</li> </ul>
<code>-f --file-filter</code>	<p>selects the type of files to migrate. Option arguments are:</p> <ul style="list-style-type: none"> <li>▪ <code>all-files</code>: if specified and set to true (default), migrates all types of files.</li> <li>▪ <code>html-files</code>: if specified and set to true (default), migrates HTML files.</li> <li>▪ <code>java-files</code>: if specified and set to true (default), migrates Java files.</li> <li>▪ <code>jsp-files</code>: if specified and set to true (default), migrates JSP type files.</li> <li>▪ <code>xml-files</code>: if specified and set to true (default), migrates all XML type files.</li> <li>▪ <code>archive-files</code>: if specified and set to true (default), migrates <code>jar/ear/war/rar</code> file types.</li> </ul>
<code>-a --append-logs</code>	if specified, appends the logging to the existing or previous logs without overwriting them. If not specified, previous logs are overwritten.
operands	identifies the archive file ( <code>jar/ear/war/rar</code> ) to be migrated.

### Examples EXAMPLE 1 Using asmigrate

This example shows how to migrate the source code for a Websphere 4.0 application to Sun Java System Application Server 8.1 Platform Edition 2005Q1 using the command line options. The output directory for the migrated code is `/tmp/ws_out`. The location of the source code is in directory, `/d1/asmt/examples/websphere_4_0/PeopleDB/src`.

```
asmigrate -c -T sjs80PE -S ws40 -t /tmp/ws_out -s
/d1/asmt/examples/websphere_4_0/PeopleDB/src
```

This example shows how to migrate a Websphere 4.0 application archive to Sun Java System Application Server 8.1 Platform Edition 2005Q1.

```
asmigrate -c -T sjs80PE -S ws40 -t /tmp/ws_out
/d1/asmt/examples/websphere_4_0/PeopleDB/WA
SDeployed/PeopleDBEnEar.ear
```

**EXAMPLE 1** Using asmigrate *(Continued)*

This example shows how to migrate source code from Weblogic 6.1 application to Sun Java System Application Server 8 Platform Edition 2004Q4. Only Java files are designated to be migrated. CMP 1.1 beans will be migrated to CMP 2.0 beans and conflicting CMP related accessors will be overwritten.

```
asmigrate -c -T sjs80PE -S wl61 -t /tmp/ws_out -s  
/d1/asmt_headstrong/asmt/examples/weblogic_6_x/  
iBank -f java-files=true -m overwrite-conflicting-accessors=true
```

This example shows how to start the migration tool UI.

```
asmigrate -u
```

**See Also** [asupgrade\(1M\)](#)

**Name** asupgrade – migrates the configuration of a previously installed Sun Java System Application Server

**Synopsis** **asupgrade** [**—console** ] [**—version** ] [**—help** ]  
 [**—source** *applicationserver\_7.x/8.x\_installation*]  
 [**—target** *applicationserver\_8.1\_installation*] **—adminuser** *admin\_user*  
 [**—adminpassword** *admin\_password*] [**—masterpassword** *changeit*]  
 [**—passwordfile** *path\_to\_password\_file*] [**—domain** *domain\_name*]  
 [**—nsspwdfile** *NSS\_password\_filepath*]  
 [**—targetnsspwdfile** *target\_NSS\_password\_filepath*]  
 [**—jkspwdfile** *JKS\_password\_filepath*] [**—capwdfile** *CA\_password\_filepath*]  
 [**—clinstancefile** *file1* [, *file2*, *file3*, ... *filen*]]

**Description** Use the asupgrade utility to migrate the server configuration and its persisted state, J2EE services, and deployed J2EE applications. The configuration of an installed Sun Java System Application Server 7 is migrated to the Sun Java System Application Server 8.1 installation. If the domain contains information about a deployed application and the installed application components do not agree with the configuration information, the configuration is migrated as is without any attempt to reconfigure the incorrect configurations.

asupgrade migrates the configuration and deployed applications of a previous version of the Application Server; however, the runtime binaries of the server are not updated. Database migrations or conversions are also beyond the scope of the asupgrade command.

Only those instances that do not use Sun Java System Web Server-specific features will be upgraded seamlessly. Configuration files related to HTTP path, CGI bin, SHTML, and NSAPI plugins will not be upgraded.

The upgrade process can also be initiated automatically at installation time using the Upgrade checkbox in the Application Server installer. After completion of the upgrade, use the uninstaller to remove the previous version of the application server.

Application archives (EAR files) and component archives (JAR, WAR, and RAR files) that are deployed in the Application Server 7.x/8.0 environment do not require any modification to run on Application Server 8.1. Applications and components that are deployed in the source server are deployed on the target server during the upgrade. Applications that do not deploy successfully on the target server must be migrated using the Migration Tool or `asmigrate` command, then redeployed manually.

Specify the source and target directories for the upgrade.

If the upgrade includes certificates, provide the passwords for the source PKCS12 file and the target JKS keyfile for each domain that contains certificates to be migrated. Since Application Server 7 uses a different certificate store format (NSS) than Application Server 8 PE (JSSE), the migration keys and certificates are converted to the new format. Only one certificate database password per

domain is supported. If multiple certificate database passwords are used in a single domain, all of the passwords must be made the same before starting the upgrade. The passwords can be reset after the upgrade has been completed.

If the upgrade includes clusters, specify one or more cluster files. Upon successful upgrade, an upgrade report is generated listing successfully migrated items along with a list of the items that could not be migrated.

If you issue the `asupgrade` command with no options, the Upgrade Tool GUI will be displayed. If the `asupgrade` command is used in command-line mode and all of the required information is not supplied, an interviewer will request information for any required options that were omitted.

<b>Options</b>	<code>-c</code> <code>—console</code>	Launches the upgrade command line utility.
	<code>-V</code> <code>—version</code>	The version of the Upgrade Tool.
	<code>-h</code> <code>—help</code>	Displays the arguments for launching the UpgradeTool.
	<code>-s</code> <code>—source</code>	The installation directory for Sun Java System Application Server 7.x/8.x installation that will be upgraded.
	<code>-t</code> <code>—target</code>	The installation directory for Sun Java System Application Server 8.1.
	<code>-a</code> <code>—adminuser</code>	The username of the administrator.
	<code>-w</code> <code>—adminpassword</code>	The password for the adminuser. Although this option can be used, the recommended way to transmit passwords is by using the <code>—passwordfile</code> option.
	<code>-m</code> <code>—masterpassword</code>	The master password that is created during installation. The default value is <code>changeit</code> . Although this option can be used, the recommended way to transmit passwords is by using the <code>—passwordfile</code> option.
	<code>-f</code> <code>—passwordfile</code>	The path to the file that contains the adminpassword and masterpassword. Content of this file should be in the following format: <code>AS_ADMIN_ADMINPASSWORD=<i>adminpassword</i></code> <code>AS_ADMIN_MASTERPASSWORD=<i>masterpassword</i></code>
	<code>-d</code> <code>—domain</code>	The domain name for the migrated certificates.
	<code>-n</code> <code>—nsspwdfile</code>	The path to the NSS password file.
	<code>-e</code> <code>—targetnsspwdfile</code>	The path to the target NSS password file.
	<code>-j</code> <code>—jkspwdfile</code>	The path to the JKS password file.
	<code>-p</code> <code>—capwdfile</code>	The path to the CA certificate password file.
	<code>-i</code> <code>—clinstancefile</code>	The path to the cluster file. The default filename is <code>\$AS_INSTALL/conf/clinstance.conf</code> .

**Examples** **EXAMPLE 1** Upgrading an Application Server 7 Installation to Application Server 8.1 with Prompts for Certificate Migration

This example shows how to upgrade a Sun Java System Application Server 7 installation to Sun Java System Application Server 8.1. You will be prompted to migrate certificates. If you reply no, then no certificates will be migrated.

```
example% asupgrade --adminuser admin --passwordfile password.txt
--source /home/sunas7 --target /home/sjsas8.1
```

**EXAMPLE 2** Upgrading an Application Server 7.1 EE Installation with Clusters and NSS Certificates to Application Server 8.1 EE

This example shows how to upgrade a Sun Java System Application Server 7.1 EE installation with a cluster to Sun Java System Application Server 8.1 EE. NSS certificates will be migrated, as will the `clinstance.conf` cluster file.

```
example% asupgrade --adminuser admin
--passwordfile password.txt
--source /home/sjsas7.1 --target /home/sjsas8.1
--domain domain1 --nsspwdfile /home/sjsas7.1/nsspassword.txt
--targetnsspwdfile /home/sjsas8.1/nsspassword.txt
--clinstancefile /home/sjsas7.1/config/clinstance.conf
```

After the upgrade, node agents for all remote instances must be created and started on their respective host systems.

**EXAMPLE 3** Upgrading an Application Server 7.0 PE Installation with NSS Certificates to Application Server 8.1 PE

This example shows how to upgrade a Sun Java System Application Server 7.0 PE installation to Sun Java System Application Server 8.1 PE. The NSS certificates from the 7.0 PE source server will be converted to JKS and CA certificates in the 8.1 PE target server.

```
example% asupgrade --adminuser admin
--passwordfile password.txt
--source /home/sjsas7.0 --target /home/sjsas8.1
--domain domain1 --nsspwdfile /home/sjsas7.0/nsspassword.txt
--jkspwdfile /home/sjsas7.0/jkspassword.txt
--capwdfile /home/sjsas7.0/capassword.txt
```

**EXAMPLE 4** Upgrading an Application Server 8.0 PE Installation with JKS and CA Certificates to Application Server 8.1 PE

This example shows how to upgrade a Sun Java System Application Server 8.0 PE installation to Sun Java System Application Server 8.1 PE. JKS and CA certificates will be migrated.

**EXAMPLE 4** Upgrading an Application Server 8.0 PE Installation with JKS and CA Certificates to Application Server 8.1 PE *(Continued)*

```
example% asupgrade --adminuser admin  
--passwordfile password.txt  
--source /home/sjsas8.0 --target /home/sjsas8.1  
--domain domain1 --jkspwdfile /home/sjsas8.0/jkspassword.txt  
--capwdfile /home/sjsas8.1/capassword.txt
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [asmigrate\(1M\)](#)



---

**Name** backup-domain – performs a backup on the domain

**Synopsis** **backup-domain** [**—domaindir** *domain\_directory*] [**—descriptioin** *description*]  
 [**—domaindir** *domain\_directory*] [*domain\_name*]

**Description** The backup-domain command backs up files under the named domain. This command is supported in local mode only.

**Options** **—domaindir** This option specifies the parent directory of the domain upon which the command will operate. The default is `install_dir/domains`.

**Operands** *domain\_name* This is the name of the root directory of the domain to be backed up. The default is all domains under `domaindir`.

**Examples** EXAMPLE 1 Using backup-domain  
`asadmin>backup-domain --domaindir directory1 domain1`  
 The command executed successfully.  
 Where: `domain1` is the domain name.

**Exit Status** 0 command executed successfully  
 1 error in executing the command

**See Also** [restore-domain\(1\)](#), [list-backups\(1\)](#)

**Name** capture-schema – stores the database metadata (schema) in a file for use in mapping and execution

**Synopsis** **capture-schema** *-username name -password password -dburl url*  
*-driver jdbc\_driver\_classname [-schemaname schemaname] [-table tablename]*  
*-out filename*

**Description** Stores the database metadata (schema) in a file.

Run capture-schema as the same database user that owns the table(s), and use that same username with the -username option (and -schemaname, if required).

When running capture-schema against an Oracle database, you should grant the database user running the capture-schema command the ANALYZE ANY TABLE privilege.

You can also use the Sun Java System Studio IDE to capture the database schema.

<b>Options</b>	<b>-username</b>	user name for authenticating access to a database.
	<b>-password</b>	password for accessing the selected database.
	<b>-dburl</b>	JDBC URL required by the driver for accessing a database.
	<b>-driver</b>	JDBC driver classname in your CLASSPATH.
	<b>-schemaname</b>	name of the user schema being captured. If not specified, the default will capture metadata for all tables from all the schemas accessible to this user.  <i>Specifying this parameter is highly recommended. Without this option, if more than one schema is accessible to this user, more than one table with the same name may be captured, which will cause problems when mapping CMP fields to tables.</i>  The specified schema name must be uppercase.
	<b>-table</b>	name of a table; multiple table names can be specified. If no table is specified, all the tables in the database or named schema are captured.  The specified table name or names are case sensitive. Be sure to match the case of the previously created table names.
	<b>-out</b>	name of the output file. This option is required. If the specified output file does not contain the .dbschema suffix, it will be appended to the filename.

**Examples** EXAMPLE 1 Using capture-schema

```
capture-schema -username cantiflas -password enigma  
-dburl jdbc:oracle:thin:@sadbuttrue:1521:ora817 -driver oracle.jdbc.driver.OracleDriver  
-schemaname CANTIFLAS -out cantiflas.dbschema
```

**See Also** [asadmin\(1M\)](#)

<b>Name</b>	change-master-password – changes the master password	
<b>Synopsis</b>	<b>change-master-password</b> [ <b>—domaindir</b> <i>domain_path</i>   <b>—agentdir</b> <i>node-agent_path</i> ] [ <b>—savemasterpassword</b> = <i>false</i> ] [ <i>domain_name</i>   <i>node_agent_name</i> ]	
<b>Description</b>	This local command is used to modify the master password. Change-master-password is interactive in that the user is prompted for the old master password, as well as the new master password. This command will not work unless the server is stopped. In a distributed Enterprise Edition environment, this command must run on each machine in the domain, with the Node Agent stopped.	
<b>Options</b>	<b>—domaindir</b>	This option specifies the directory used for this operation. By default, the domaindir is \$AS_DEF_DOMAINS_PATH, which is an environment variable defined in asenv.bat/conf. Both the domaindir and the agentdir options should not be passed together; use one or the other.
	<b>—agentdir</b>	Like a DAS, each Node Agent resides in a top level directory named <agentdir>/<nodeagent_name>. If the agentdir is not specified, then \$AS_DEF_DOMAINS_PATH/./nodeagents is used. Both the domaindir and the agentdir options should not be passed together; use one or the other. This option is supported in Enterprise Edition only.
	<b>—savemasterpassword</b>	This option indicates whether the master password should be written to the file system. This is necessary so that start-domain can start the server without having to prompt the user. WARNING: saving the master password on disk is extremely dangerous and should be avoided.  NOTE: if savemasterpassword is not set, the master password file, if it exists, will be deleted.
<b>Operands</b>	<i>domain_name</i>	This is the domain name whose password is to be changed. If there is only a single domain, this is optional. This option can be used on either the Platform Edition or the Enterprise Edition.
	<i>node-agent_name</i>	This is the name of the node agent whose password is to be changed. If there is only a single domain, this is optional. This option can be used on Enterprise Edition only.
<b>Examples</b>	<b>EXAMPLE 1</b> Using change-master-password asadmin> <b>change-master-password domain44ps</b>  Master password has been changed	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [delete-password-alias\(1\)](#), [list-password-aliases\(1\)](#), [update-password-alias\(1\)](#)

**Name** clear-ha-store – deletes tables in HADB

**Synopsis** **clear-ha-store** **—user** *admin\_user* [**—passwordfile** *filename*] [**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**-s**] [**—terse**=*false*] [**—echo**=*false*] [**—interactive**=*true*] [**—help**] [**—haagentport** *port\_number*] *databaseName*

**Description** This command deletes tables in HADB. You must have created an entry in the HA database before you execute this command, using `configure-ha-cluster` or `create-ha-store`. Use fully qualified hostnames when specifying the hostlist interfaces explicitly for hosts with multiple network interfaces. `clear-ha-store` was named `delete-session-store` in the Sun Java System Application Server 7.1. `delete-session-store` has been deprecated.

This command is supported in remote mode only.

<b>Options</b>	<b>-u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>-w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
	<b>-H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
	<b>-p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>-s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>-t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.

---

<code>-e</code>	<code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code>	<code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code>	<code>—help</code>	Displays the help text for the command.
<code>—haagentport</code>		The name of the HA agent port. If not specified, the default port number is 1862.
<b>Operands</b>	<i>databaseName</i>	The name of the HA database.
<b>Examples</b>	<b>EXAMPLE 1</b> Using clear-ha-store asadmin> <b>clear-ha-store hadatabase1</b> The clear-ha-store command executed successfully	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>See Also</b>	<a href="#">create-ha-store(1)</a>	

**Name** configure-ha-cluster – configures an existing cluster to be High Availability

**Synopsis** **configure-ha-cluster** **—host** *localhost* [**—port** *4848*] [**—user** *user*] [**—passwordfile** *passwordfile\_name*] [**—terse**=*false*] [**—echo**=*false*] [**—interactive**=*true*] [**—secure**=*false*] [**—devicesize** *devicesize*] [**—haagentport** *port\_number*] [**—haadminpassword** *password*] [**—haadminpasswordfile** *file\_name*] [**—hosts** *hadb-host-list*] [**—property** (*name=value*):*name-value*]\*] {*clusterName*}

**Description** The `configure-ha-cluster` command performs the following tasks:

- Verifies that the cluster exists.
- Verifies that the cluster is standalone (an example of this is, that the cluster doesn't share its configuration with any other cluster).
- Checks if a database with the same name as the cluster already exists. If so, an error is logged and the command performs the next task.
- Creates an HA database with the same name as the cluster.
- Creates the correct tables in the database.
- Creates and/or modifies the appropriate resources in `domain.xml`.

This command is supported in remote mode only.

<b>Options</b>	<b>—H—host</b>	This option specifies the machine where the domain application server is located. The default is <code>localhost</code> .
	<b>—p—port</b>	The port number of the domain application server listening for administration requests. The default port number for Platform Edition is 4848. The default port number for Enterprise Edition is 4949.
	<b>—u—user</b>	This option specifies the user name associated with the administrative instance.
	<b>—w—password</b>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
	<b>—W—passwordfile</b>	The file containing the domain application server password associated with the administrative instance. The password is defined in the following form: <code>AS_ADMIN_PASSWORD=<i>password</i></code> . Where <i>password</i> is the actual administrator password for the domain.
	<b>—t—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is <code>false</code> .
	<b>—e—echo</b>	Setting to <code>true</code> will echo the command line statement on to the standard output. Default is <code>false</code> .



---

<code>-I</code>	<code>—interactive</code>	If set to true (default), only the required options are prompted.
<code>-s</code>	<code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>—devicesize</code>		This is the device size in MegaBytes (MB). The valid range is between 208MB and 8+ gigabytes (GB).
<code>—haagentport</code>		This is the number of the HA agent port. The default is 1862.
<code>—haadminpassword</code>		This is the HA administrator's password.
<code>—haadminpasswordfile</code>		The file containing the high-availability password associated with the administrative instance. The password is defined in the following form: <code>HADBM_ADMINPASSWORD=<i>password</i></code> , <code>HADBM_DBPASSWORD=<i>password</i></code> , <code>HADBM_SYSEMPASSWORD=<i>password</i></code> . Where <i>password</i> is the actual HA administrator password for the domain.
<code>—hosts</code>		This is a list of comma separated host names where the HADB instance is configured. The number of hosts must be greater than 1 and must be an even number. The same host names can be repeated. Use fully qualified hostnames when specifying the hostlist interfaces explicitly for hosts with multiple network interfaces.
<code>—property</code>		This is a list of property name/value pairs, which are separated by a colon.
<b>Operands</b>	<i>clusterName</i>	This is the name of the cluster that will be changed to high availability.
<b>Examples</b>	EXAMPLE 1 Using the configure-ha-cluster command	
	This is a basic example of how the command is used.	
	<code>asadmin&gt;configure-ha-cluster --user admin --passwordfile passwordfile --hosts hostha1 cluster1</code>	
	The command configuration-ha-cluster has executed successfully.	
	Where: the hosts name is hostha1 and the cluster name is cluster1.	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>See Also</b>	<a href="#">remove-ha-cluster(1)</a>	

**Name** asadmin configure-ha-persistence, configure-ha-persistence – enables configuration of parameters related to session persistence

**Synopsis** **configure-ha-persistence** `—user` *admin\_user* [`—passwordfile` *filename*]  
 [`—host` *host\_name*] [`—port` *port\_number*] [`—secure|—s`] [`—terse=false`]  
 [`—echo=false`] [`—interactive=true`] [`—help`] [`—type` *persistence\_type*]  
 [`—frequency` *frequency*] [`—scope` *scope*] [`—store` *jdbc\_resource\_jndi\_name*]  
 [`—property` (*name=value*)[`:`*name=value*]\*] [`—haagentport` *portnumber*]  
 [`—hosts` *hadb\_hosts\_list*] *clustername*

**Description** Configure the global session persistence settings to balance your needs for performance, reliability, and high availability. You can override these settings for specific applications by changing the properties of the `manager-properties`, `store-properties`, and `session-properties` subelements of the `session-manager` element in the `sun-web.xml` file.

The `configure-ha-persistence` command is available only in the Enterprise Edition of the Sun Java System Application Server.

<b>Options</b> <code>—u</code>	<code>—user</code>	The authorized domain application server administrative username.
<code>—w</code>	<code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>		This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>—H</code>	<code>—host</code>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
<code>—p</code>	<code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>—s</code>	<code>—secure</code>	If set to <code>true</code> , uses SSL/TLS to communicate with the domain application server.

---

<code>-t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—type</code>	Set the persistence type to specify where session data is stored. The persistence types available are: <ul style="list-style-type: none"> <li>▪ <code>memory</code> If session persistence for the application server instance is disabled, this is the default persistence type. The memory persistence type provides no session persistence in a clustered environment. The memory persistence type is intended for development environments and should not be used for production.</li> <li>▪ <code>file</code> This type provides no session persistence in a clustered environment. Use file persistence type to store session data in a file. If the instance becomes unavailable and restarts, it can recover the session information that was last written to the file. The file persistence type is meant for development environments and should not be used for production.</li> <li>▪ <code>ha</code> If session persistence for the application server instance is enabled, this is the default persistence type. This type allows you to store session data in the HADB. The ha persistence type enables failover of session information between application server instances in a cluster. The session information for each application server instance in a cluster is stored in the HADB. The session information is available to all other instances in the cluster. If an instance in a cluster becomes unavailable, another instance in the cluster can continue to serve the sessions that the now unavailable instance was serving.</li> </ul>
<code>—frequency</code>	Set the persistence frequency to define the frequency at which the session state is stored in the HADB. The persistence frequencies available are: <ul style="list-style-type: none"> <li>▪ <code>web-method</code> The session is stored after every web request just before a response is sent back to the client. Use this frequency when you need very high availability of updated session states.</li> </ul>

- `time-based` The session is stored at the time interval defined in the `reapIntervalSeconds` property. A better throughput is achieved because the session is stored after a configurable time interval instead of after every web request.
- scope
- Set the persistence scope to determine how much of the session is stored. The persistence scopes available are:
- `modified-session` The entire session is stored only if it has been modified since the last time it was stored.
  - `session` The entire session is stored every time session information is saved to the HADB.
  - `modified-attribute` Only the modified attributes of the session are stored. Using this mode can improve the throughput and response time significantly for applications in which only a small portion of the session state is modified for any given request.
- If you use the `modified-attribute` persistence scope, your application should follow these guidelines:
- Call `setAttribute()` every time you modify the session state.
  - Make sure there are no cross-references between attributes. The object graph under each distinct attribute key is serialized and stored separately. If there are any object cross references between the objects under each separate key, they are not serialized and deserialized correctly.
  - Ideally, the session state should be stored in multiple attributes, or at least in a read-only attribute and a modifiable attribute.
- store
- Specify the JNDI name of the JDBC resource for the HADB. The default is `jdbc/hastore`.
- property
- You can configure other session persistence properties to fine tune the session persistence configuration. The following properties are available:

Property	Definition
reapIntervalSeconds	<p>Specifies the number of seconds between checks for modified or timed-out sessions. This is also the frequency at which passivation of sessions occurs. If the persistence type is file or ha, sessions are passivated if maxSessions has been exceeded. If the persistence frequency is time-based, active sessions are stored at this interval. The default is 60.</p>
maxSessions	<p>Specifies the maximum number of sessions that can be in the cache, or -1 for no limit. The default is -1.</p> <p>After this limit is reached:</p> <ul style="list-style-type: none"> <li>■ If the persistence type is memory, an attempt to create a new session causes an <code>IllegalStateException</code> to be thrown.</li> <li>■ If the persistence type is file or ha, the sessions are passivated to the persistent store.</li> </ul>
sessionFilename	<p>Specifies the absolute or relative path to the file in which the session state is preserved between application restarts, if preserving the state is possible. A relative path is relative to the temporary work directory for this application. Applicable only if the persistence type is memory. By default, the session state is not preserved across server restarts.</p>

Property	Definition
directory	<p>Specifies the absolute or relative path to the directory into which individual session files are written. A relative path is relative to the temporary work directory for this application. Applicable only if the persistence type is file.</p> <p>The default is  <i>instance_dir/generated/jsp/j2ee-apps/appname/appname_war.</i></p>
timeoutSeconds	<p>Specifies the default maximum inactive interval (in seconds) for sessions. If set to 0 or less, sessions never expire. If a session-timeout element is specified in the web.xml file, the session-timeout value overrides any timeoutSeconds value. If timeoutSeconds is specified in both sun-web.xml and domain.xml, the value in sun-web.xml takes precedence. If neither session-timeout nor timeoutSeconds is specified, the timeoutSeconds default is used. Note that the session-timeout element in web.xml is specified in minutes, not seconds. The default is 600.</p>

—haagentport Specify the port number for the HADB node agent. The default is 1862.

—hosts Specify a comma-separated list of HADB host names.

**Operands** *clustername* Specify the name of the cluster for which you are configuring session persistence.

**Examples** EXAMPLE 1 Using configure-ha-persistence

```
asadmin> configure-ha-persistence --user admin --passwordfile secret.txt
--type ha --frequency web-method --scope modified-session --store jdbc/hastore
--property maxSessions=1000:reapIntervalSeconds=60 cluster1
```

**Exit Status** 0 command executed successfully

1

error in executing the command

**See Also** [configure-ha-cluster\(1\)](#), [remove-ha-cluster\(1\)](#), [create-ha-store\(1\)](#), [clear-ha-store\(1\)](#)

**Name** copy-config – copies an existing configuration to create a new configuration

**Synopsis** **copy-config** —user *admin\_user* [—passwordfile *filename*] [—host *host\_name*] [—port *port\_number*] [—secure|—s] [—terse=false] [—echo=false] [—interactive=true] [—help] [—systemproperties (*name=value*)[*:name=value*]\*] *source\_configuration\_name destination\_configuration\_name*

**Description** Use the copy-config command to create a new configuration in the domain.xml file by copying an existing configuration. The new configuration is identical to the copied configuration, except for any properties you specify in the —systemproperties option.

The configuration default-config is the configuration that is copied when a standalone sever instance or standalone cluster is created.

<b>Options</b> -u—user	The authorized domain application server administrative username.
-w—password	The —password option is deprecated. Use —passwordfile instead.
—passwordfile	This option replaces the —password option. Using the —password option on the command line or through the environment is deprecated. The —passwordfile option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
-H—host	The machine name where the domain application server is running. The default value is localhost.
-p—port	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
-s—secure	If set to true, uses SSL/TLS to communicate with the domain application server.
-t—terse	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.



<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—systemproperties</code>	Optional attribute name/value pairs for configuring the resource. The following properties are available:

System Property	Definition
HTTP_LISTENER_PORT	This property specifies the port number for http-listener-1. Valid values are 1–65535. On UNIX, creating sockets that listen on ports 1–1024 requires superuser privileges.
HTTP_SSL_LISTENER_PORT	This property specifies the port number for http-listener-2. Valid values are 1–65535. On UNIX, creating sockets that listen on ports 1–1024 requires superuser privileges.
IIOB_LISTENER_PORT	This property specifies which ORB listener port for IIOB connections orb-listener listens on.
IIOB_SSL_LISTENER_PORT	This property specifies which ORB listener port for IIOB connections the IIOB listener called SSL listens on.
IIOB_SSL_MUTUALAUTH_PORT	This property specifies which ORB listener port for IIOB connections the IIOB listener called SSL_MUTUALAUTH listens on.
JMX_SYSTEM_CONNECTOR_PORT	This property specifies the port number on which the JMX connector listens. Valid values are 1–65535. On UNIX, creating sockets that listen on ports 1–1024 requires superuser privileges.

<b>Operands</b>	<i>source_configuration_name</i>	The name of the configuration you are copying.
	<i>destination_configuration_name</i>	The name of the new configuration you are creating by copying the source configuration. This name should be unique within a domain.xml. It should not be the same as the cluster name, serverinstance name, another config name, or node agent name.

**Examples** EXAMPLE 1 Using the copy-config command

```
asadmin> copy-config --user admin --passwordfile passwords.txt
--systemproperties HTTP_LISTENER_PORT=2000:HTTP_SSL_LISTENER_PORT=3000
default-config new-config
Command copy-config executed successfully.
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [list-configs\(1\)](#), [delete-config\(1\)](#)

**Name** create-admin-object – adds the administered object with the specified JNDI name

**Synopsis** **create-admin-object** —user *admin\_user* [—passwordfile *filename*] [—host *host\_name*] [—port *port\_number*] [—secure|—s] [—terse=*false*] [—echo=*false*] [—interactive=*true*] [—help] [—target *target*] —restype *admin\_object\_type* —raname *resource\_adapter\_name* [—description *text*] [—property *name=value[:name=value]\**] *jndi-name*

**Description** This command creates the administered object that has a specified jndi name.

<b>Options</b> —u —user	The authorized domain application server administrative username.
—w —password	The —password option is deprecated. Use —passwordfile instead.
—passwordfile	This option replaces the —password option. Using the —password option on the command line or through the environment is deprecated. The —passwordfile option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
—H —host	The machine name where the domain application server is running. The default value is localhost.
—p —port	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
—s —secure	If set to true, uses SSL/TLS to communicate with the domain application server.
—t —terse	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
—e —echo	Setting to true will echo the command line statement on the standard output. Default is false.

---

<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	This is the name of the target upon which the command is operating. The valid targets for this command are instance, cluster, 'domain,' and 'server.' Server is the default option. This command is used by the Enterprise Edition only.
<code>—restype</code>	This option is used to administer the object resource types, as defined by the resource adapter in the ra.xml file.
<code>—raname</code>	This is the name of the resource adapter associated with this object.
<code>--description</code>	This option is the text description of the administered object.
<code>—property</code>	This option describes the “name/values” pairs for configuring the resource.

**Operands** *jndi\_name* This is the JNDI name of the administered object to be created.

**Examples** EXAMPLE 1 Using create-admin-object

The `javax.jms.Queue` resource type is obtained from the `ra.xml` file. The `jmssra.rar` must be deployed prior to executing this command.

```
asadmin> create-admin-object --user admin1 --password adminadmin1
--restype javax.jms.Queue --raname jmsra --description "sample administered object"
--property Name=sample_jmsqueue --target instance1 jms/samplequeue
Command create-admin-object executed successfully
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [delete-admin-object\(1\)](#), [list-admin-objects\(1\)](#)

**Name** create-application-ref – creates a reference to an application

**Synopsis** **create-application-ref** **—user** *admin\_user* [**—passwordfile** *filename*]  
[**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**—s**] [**—terse**=*false*]  
[**—echo**=*false*] [**—interactive**=*true*] [**—help**] [**—target** *target*] [**—enabled**=*true*]  
[**—virtualservers** *virtual\_servers*] *reference\_name*

**Description** The create-application-ref command creates a reference from a cluster or an unclustered server instance to a previously deployed application element (for example, a J2EE application, a Web module, or an enterprise bean module). This effectively results in the application element being deployed and made available on the targeted instance or cluster.

The target instance or instances making up the cluster need not be running or available for this command to succeed. If one or more instances are not available, they will receive the new application element the next time they start.

This command is supported in remote mode only.

<b>Options</b> <b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.

<code>-t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	Specifies the target for which you are creating the application reference. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, which creates the application reference for the default server instance <code>server</code> and is the default value</li> <li>▪ <code>cluster_name</code>, which creates the application reference for every server instance in the cluster</li> <li>▪ <code>instance_name</code>, which creates the application reference for the named unclustered server instance</li> </ul>
<code>—enabled</code>	Indicates whether the application should be enabled (that is, loaded). This value will take effect only if the application is enabled at the global level. The default is <code>true</code> .
<code>—virtualservers</code>	Comma-separated list of virtual server IDs on which to deploy. This option applies only to Web modules (either standalone or in a J2EE application). If this option is not specified, the application is deployed to all virtual servers except the administrative server, <code>__asadmin</code> .
<b>Operands</b> <code>reference_name</code>	The name of the application or module, which can be a J2EE application, Web module, EJB module, connector module, application client module, or lifecycle module.
<b>Examples</b>	<p><b>EXAMPLE 1</b> Using the <code>create-application-ref</code> command</p> <p>The following command creates a reference to the Web module <code>MyWebApp</code> on the unclustered server instance <code>NewServer</code>.</p> <pre>asadmin&gt; create-application-ref --user admin2 --passwordfile passwords.txt --target NewServer MyWebApp</pre> <p>Command <code>create-application-ref</code> executed successfully.</p>
<b>Exit Status</b>	<p>0                    command executed successfully</p> <p>1                    error in executing the command</p>
<b>See Also</b>	<a href="#">delete-application-ref(1)</a> , <a href="#">list-application-refs(1)</a>

---

<b>Name</b>	create-audit-module – adds an audit-module
<b>Synopsis</b>	<b>create-audit-module</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>—s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—target</b> <i>target_name</i> ] [ <b>—classname</b> <i>realm_class</i> ] [ <b>—property</b> ( <i>name=value</i> )[: <i>name=value</i> ]*] [ <i>audit_module_name</i> ]
<b>Description</b>	Adds the named audit module for the plugin module that implements the audit capabilities. This command is supported in remote mode only.
<b>Options</b>	<p><b>—u</b> <b>—user</b> The authorized domain application server administrative username.</p> <p><b>—w</b> <b>—password</b> The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.</p> <p><b>—passwordfile</b> This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b><i>password</i>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b>, <b>AS_ADMIN_USERPASSWORD</b>, <b>AS_ADMIN_SAVEDMASTERPASSWORD</b>, <b>AS_ADMIN_MQPASSWORD</b>, <b>AS_ADMIN_ALIASPASSWORD</b>, and so on.</p> <p><b>—H</b> <b>—host</b> The machine name where the domain application server is running. The default value is localhost.</p> <p><b>—p</b> <b>—port</b> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><b>—s</b> <b>—secure</b> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><b>—t</b> <b>—terse</b> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p> <p><b>—e</b> <b>—echo</b> Setting to true will echo the command line statement on the standard output. Default is false.</p>

---

<code>-I</code>	<code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code>	<code>—help</code>	Displays the help text for the command.
<code>—target</code>		In Enterprise Edition, specifies the target on which you are creating the audit module. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, which creates the listener for the default server instance <code>server</code> and is the default value</li> <li>▪ <code>configuration_name</code>, which creates the listener for the named configuration</li> <li>▪ <code>cluster_name</code>, which creates the listener for every server instance in the cluster</li> <li>▪ <code>instance_name</code>, which creates the listener for a particular server instance</li> </ul>
<code>--classname</code>		Java class which implements this realm.
<code>--property</code>		optional attributes name/value pairs of provider implementation specific attributes.
<b>Operands</b>	<i>audit_module_name</i>	name of this audit module.
<b>Examples</b>	<p>EXAMPLE 1 Using create-audit-module</p> <pre>asadmin&gt; create-audit-module --user admin1 --passwordfile password.txt --host pigeon --port 5001 --classname com.sun.appserv.auditmodule --property defaultuser=admin:Password=admin sampleAuditModule</pre> <p>Command create-audit-module executed successfully</p>	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>See Also</b>	<a href="#">delete-audit-module(1)</a> , <a href="#">list-audit-modules(1)</a>	

---

<b>Name</b>	create-auth-realm – adds the new authenticated realm
<b>Synopsis</b>	<b>create-auth-realm</b> <code>--user</code> <i>admin_user</i> [ <code>--passwordfile</code> <i>filename</i> ] [ <code>--host</code> <i>host_name</i> ] [ <code>--port</code> <i>port_number</i> ] [ <code>--secure -s</code> ] [ <code>--terse=false</code> ] [ <code>--echo=false</code> ] [ <code>--interactive=true</code> ] [ <code>--help</code> ] [ <code>--target</code> <i>target_name</i> ] [ <code>--classname</code> <i>realm_class</i> ] [ <code>--isdefault-=true</code> ] [ <code>--property(name=value)[:name=value]*</code> ] <i>auth_realm_name</i>
<b>Description</b>	Adds the named authorized realm. This command is supported in remote mode only.
<b>Options</b>	
<code>-u</code> <code>--user</code>	The authorized domain application server administrative username.
<code>-w</code> <code>--password</code>	The <code>--password</code> option is deprecated. Use <code>--passwordfile</code> instead.
<code>--passwordfile</code>	This option replaces the <code>--password</code> option. Using the <code>--password</code> option on the command line or through the environment is deprecated. The <code>--passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>-H</code> <code>--host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>-p</code> <code>--port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>-s</code> <code>--secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>-t</code> <code>--terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>--echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>--interactive</code>	If set to true (default), only the required password options are prompted.



---

<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target on which you are creating the realm. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, which creates the listener for the default server instance <code>server</code> and is the default value</li> <li>▪ <code>configuration_name</code>, which creates the listener for the named configuration</li> <li>▪ <code>cluster_name</code>, which creates the listener for every server instance in the cluster</li> <li>▪ <code>instance_name</code>, which creates the listener for a particular server instance</li> </ul>
<code>--classname</code>	Java class which implements this realm.
<code>--property</code>	optional attributes name/value pairs of provider implementation specific attributes.

**Operands** `auth_realm_name` name of this realm.

**Examples** EXAMPLE 1 Using `create-auth-realm`

```
asadmin> create-auth-realm --user admin1 --passwordfile password.txt
--host pigeon --port 5001 --classname com.iplanet.ias.security.auth.realm.DB.Database
--property defaultuser=admin:Password=admin db
Command create-auth-realm executed successfully
```

Where `db` is the auth realm created.

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [delete-auth-realm\(1\)](#), [list-auth-realms\(1\)](#)

**Name** create-cluster – creates a cluster

**Synopsis** **create-cluster** —user *admin\_user* [—passwordfile *filename*] [—host *host\_name*] [—port *port\_number*] [—secure|-s] [—terse=*false*] [—echo=*false*] [—interactive=*true*] [—help] [—config *config\_name*] [—systemproperties (*name=value*)[*:name=value*]\*] *cluster\_name*

**Description** The `create-cluster` command creates a new cluster. When created, a cluster must reference a configuration (or, as with an unclustered server instance, a configuration can be implicitly created). Initially the cluster has no server instances, applications, or resources.

If you do not use the `—config` option, the command creates a standalone cluster with a configuration named `cluster_name-config`.

To add new instances to the cluster, use the `create-instance` command with the `—cluster` option. Use the `stop-instance` and `delete-instance` commands to delete server instances from the cluster at any time.

To associate new applications and resources with the cluster regardless of the number of instances in the cluster, perform any of the following operations:

- Use the `deploy` command with the option `—target cluster_name`.
- Use resource-creation commands (for example, `create-jdbc-resource`) with the option `—target cluster_name`.
- Use reference management commands (for example, `create-application-ref` or `create-resource-ref`) if the application is already deployed or the resource is already created.

This command is supported in remote mode only.

<b>Options</b>	<code>—u—user</code>	The authorized domain application server administrative username.
	<code>—w—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
	<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> ,

	AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASSPASSWORD, and so on.
-H—host	The machine name where the domain application server is running. The default value is localhost.
-p—port	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
-s—secure	If set to true, uses SSL/TLS to communicate with the domain application server.
-t—terse	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
-e—echo	Setting to true will echo the command line statement on the standard output. Default is false.
-I—interactive	If set to true (default), only the required password options are prompted.
-h—help	Displays the help text for the command.
—config	Creates a shared cluster. The specified configuration name must exist and must not be <code>default-config</code> (the standalone cluster configuration template) or a standalone configuration (including <code>server-config</code> ). If this option is omitted, a standalone cluster is created.
—systemproperties	Defines system properties for the configuration created for by the cluster. These properties override the property values in the <code>default-config</code> configuration. The following properties are available:

Property	Definition
HTTP_LISTENER_PORT	This property specifies the port number for <code>http-listener-1</code> . Valid values are 1–65535. On UNIX, creating sockets that listen on ports 1–1024 requires superuser privileges.

Property	Definition
HTTP_SSL_LISTENER_PORT	This property specifies the port number for <code>http-listener-2</code> . Valid values are 1–65535. On UNIX, creating sockets that listen on ports 1–1024 requires superuser privileges.
IIOP_LISTENER_PORT	This property specifies which ORB listener port for IIOP connections <code>orb-listener-1</code> listens on.
IIOP_SSL_LISTENER_PORT	This property specifies which ORB listener port for IIOP connections the IIOP listener called <code>SSL</code> listens on.
IIOP_SSL_MUTUALAUTH_PORT	This property specifies which ORB listener port for IIOP connections the IIOP listener called <code>SSL_MUTUALAUTH</code> listens on.
JMX_SYSTEM_CONNECTOR_PORT	This property specifies the port number on which the JMX connector listens. Valid values are 1–65535. On UNIX, creating sockets that listen on ports 1–1024 requires superuser privileges.

**Operands** *cluster\_name* A unique identifier for the cluster to be created.

**Examples** EXAMPLE 1 Using the create-cluster command

The following command creates a cluster named `MyCluster`, overriding the default configuration's SSL port value. Because the `—config` option is not specified, the command makes a copy of the `default-config` and names it `MyCluster-config`.

```
asadmin> create-cluster --user admin1
--passwordfile passwords.txt --systemproperties
IIOP_SSL_LISTENER_PORT=1169 MyCluster
Command create-cluster executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [delete-cluster\(1\)](#), [list-clusters\(1\)](#), [start-cluster\(1\)](#), [stop-cluster\(1\)](#), [create-instance\(1\)](#)

**Name** create-connection—group – creates a new connection group with the named group ID

**Synopsis** **create-connection-group**

```
--user user_name --password password --host hostname --port admin_port_number
--instance instance_name --httplistener http_listener_ID --address address
--defaultvs virtual_server --servername server_name connection_group_ID
```

**Description** Creates a new connection group with the named group ID.

**Options**

--user identifies the user name associated with the named instance.

--password identifies the password associated with the user name.

--host identifies the host name for the machine.

--port identifies the administrator port number associated with the hostname.

--instance identifies the name of the instance associated with the JVM option to be created.

--httplistener a unique identifier for the HTTP listener.

--address the IP address of the listen socket. Can be in dotted-pair or IPv6 notation.

--defaultvs the ID attribute of the default virtual server for this particular connection group.

--servername identifies, in the hostname section, the URLs the server sends to the client. This name should be the alias name if your server uses an alias. If you append a colon (:) and port number, that port will be used in the URLs the server sends to the client.

*connection\_group\_ID* a unique identifier for the connection group.

**Examples** asadmin% **create-connection-group**

**See Also** [delete-connection-group\(1\)](#), [list-connection-groups\(1\)](#)

---

**Name** create-connector-connection-pool – adds a connector pool with the specified connection pool name

**Synopsis** **create-connector-connection-pool** `—user` *admin\_user* [`—passwordfile` *filename*] [`—host` *host\_name*] [`—port` *port\_number*] [`—secure|—s`] [`—terse=false`] [`—echo=false`] [`—interactive=true`] [`—help`] [`--steadypoolsize` 8] [`--maxpoolsize` 32] [`--maxwait` 60000] [`--poolresize` 2] [`--idletimeout` 300] [`--failconnection=false`] `--raname` *resource\_adapter\_name* `--connectiondefinition` *connection\_definition\_name* [`--transactionsupport` *transaction\_support*] [`--description` *text*] [`—property` (*name=value*)[*:name=value*]\*] *connector\_connection\_pool\_name*

**Description** Adds a new connector connection pool with the specified connection pool name. This command is supported in remote mode only.

**Options**

<code>—u</code> <code>—user</code>	The authorized domain application server administrative username.
<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>—H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>—p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>—s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.

---

<code>-t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	The target option is deprecated.
<code>—raname</code>	The name of the resource adapter.
<code>—connectiondefinition</code>	The name of the connection definition.
<code>—steadypoolsize</code>	The minimum and initial number of connections maintained in the pool. The default value is 8.
<code>—maxpoolsize</code>	The maximum number of connections that can be created to satisfy client requests. The default value is 32.
<code>—maxwaittime</code>	The amount of time, in milliseconds, that a caller must wait before a connection is created, if a connection is not available. If set to 0, the caller is blocked indefinitely until a resource is available or until an error occurs. The default value is 60000.
<code>—poolresize</code>	The number of connections to be destroyed if the existing number of connections is above the steady-pool-size (subject to the limit specified in the maxpoolsize option). Possible values are from 0 to MAX_INTEGER. The default value is 2.
<code>—idletimeout</code>	The maximum time that a connection can remain idle in the pool. After this amount of time, the pool can close this connection. The default value is 300.
<code>—failconnection</code>	If set to true, all connections in the pool are closed if a single validation check fails. This parameter is mandatory if the is-connection-validation-required is set to true. Legal values are on, off, yes, no, 1, 0, true or false. The default value is false.
<code>—transactionsupport</code>	Indicates the level of transaction support that this pool will have. Possible values are XATransaction, LocalTransaction and NoTransaction. This attribute can support the resource adapter's transaction support attribute when the resource adapter's transaction support attribute is lower than or equal to but not higher than. The default value is true.
<code>—description</code>	Text providing descriptive details about the connector connection pool.

`--property` optional attribute name/value pairs for configuring the resource.

**Operands** `connector_connection_pool_name` the name of the connection pool name to be created.

**Examples** EXAMPLE 1 Using the create-connector-connection-pool command

```
asadmin> create-connector-connection-pool
--passwordfile passwordfile --steadypoolsize 20
--maxpoolsize 100 --poolresize 2 --maxwait 60000 --raname jmsra
--connectiondefinition javax.jms.QueueConnectionFactory jms/qConnPool
Command create-connector-connection-pool executed successfully
```

Where jms/qConnPool is the name of the new connector connection pool.

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [delete-connector-connection-pool\(1\)](#), [list-connector-connection-pools\(1\)](#)



<b>Name</b>	create-connector-resource – registers the connector resource with the specified JNDI name	
<b>Synopsis</b>	<b>create-connector-resource</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ]         [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>—s</b> ] [ <b>—terse</b> = <i>false</i> ]         [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—target</b> <i>target</i> ] <b>--poolname</b> <i>connectorConnectionPoolName</i> [ <b>—enabled</b> = <i>true</i> ] [ <b>--description</b> <i>text</i> ] <i>jndi_name</i>	
<b>Description</b>	This command registers the connector resource with the JNDI name, which is specified by the <i>jndi_name</i> operand.	
<b>Options</b>	<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
	<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
	<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.

<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	valid in Enterprise Edition only, specifies the ending location of the connector resources. Valid values are “server,” “domain,” cluster, instance. The default is server.
<code>—poolname</code>	The name of the connection pool. When two or more resource elements point to the same connection pool element, they use the same pool connections at runtime.
<code>—enabled</code>	This option determines whether the resource is enabled at runtime. The default value is true.
<code>—description</code>	Text providing descriptive details about the connector resource.

**Operands** *jndi\_name* the JNDI name of this connector resource.

**Examples** EXAMPLE 1 Using the create-connector-resource command

```
asadmin> create-connector-resource --target server --poolname jms/qConnPool
--description "creating sample connector resource" jms/qConnFactory
Command create-connector-resource executed successfully
```

Where jms/qConnFactory is the sample connector resource that is created.

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [delete-connector-resource\(1\)](#), [list-connector-resources\(1\)](#)

**Name** create-connector-security-map – creates or modifies a security map for the specified connector connection pool

**Synopsis** **create-connector-security-map** `—user` *admin\_user* [`—passwordfile` *filename*] [`—host` *host\_name*] [`—port` *port\_number*] [`—secure|—s`] [`—terse=false`] [`—echo=false`] [`—interactive=true`] [`—help`] `—poolname` *connector\_connection\_pool\_name* [`—principals` *principal\_name1*[, *principal\_name2*]\* | `—usergroups` *user\_group1*[, *user\_group2*] [`—mappedusername` *username* *security\_map\_name*]

**Description** Use this command to create or modify a security map for the specified connector connection pool. If the security map is not present, one is created. Also, use this command to map the caller identity of the application (principal or user group) to a suitable EIS principal in container-managed transaction-based scenarios. One or more named security maps may be associated with a connector connection pool. The connector security map configuration supports the use of the wild card asterisk (\*) to indicate all users or all user groups.

For this command to succeed, you must have first created a connector connection pool using the `create-connector-connection-pool` command.

The enterprise information system (EIS) is any system that holds the information. It can be a mainframe, a messaging system, a database system, or an application.

This command is supported in remote mode only.

**Options** If an option has a short option name, then the short option precedes the long option name. Short options have one dash whereas long options have two dashes.

<code>—u</code> <code>—user</code>	The authorized domain application server administrative username.
<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> ,

---

	AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASEPASSWORD, and so on.
-H—host	The machine name where the domain application server is running. The default value is localhost.
-p—port	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
-s—secure	If set to true, uses SSL/TLS to communicate with the domain application server.
-t—terse	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
-e—echo	Setting to true will echo the command line statement on the standard output. Default is false.
-I—interactive	If set to true (default), only the required password options are prompted.
-h—help	Displays the help text for the command.
—target	The -target option is deprecated in this release.
—poolname	This property specifies the name of the connector connection pool to which the security map that is to be updated or created belongs.
—principals	This property specifies a comma-separated list of application-specific principals. Use either the -principals or -usergroups options, but not both.
—usergroups	This property specifies a comma-separated list of application-specific user groups. Use either the -principals or -usergroups options, but not both.
—mappedusername	This property specifies the EIS username.
—mappedpassword	The —mappedpassword option is deprecated. Use —passwordfile pointing to a file that contains an entry in the following format: AS_ADMIN_MAPPEDPASSWORD= <i>mapped-password</i> . If not specified using the passwordfile option, the user will be prompted for this password by the asadmin command-line tool.
<b>Operands</b> <i>security_map_name</i>	name of the security map to be created.

**Examples** EXAMPLE 1 Using create-connector-security-map

It is assumed that the connector pool has already been created using the create-connector-pool command.

```
asadmin> create-connector-security-map --user admin
--passwordfile pwd_file --poolname connector-pool1 --principals principal1, principal2
--mappedusername backend-username securityMap1
Command create-connector-security-map executed successfully
```

**Exit Status**

0	command executed successfully
1	error in executing the command

**See Also** [delete-connector-security-map\(1\)](#), [list-connector-security-maps\(1\)](#), [update-connector-security-map\(1\)](#)

---

**Name** create-custom-resource – creates a custom resource

**Synopsis** **create-custom-resource** `—user` *admin\_user* [`—passwordfile` *filename*] [`—host` *host\_name*] [`—port` *port\_number*] [`—secure`|`—s`] [`—terse`=*false*] [`—echo`=*false*] [`—interactive`=*true*] [`—help`] [`--target` *target*] `—restype` *type* `—factoryclassname` *classname* [`--enabled`=*true*] `—description` *text* [`—property` (*name=value*)[*:name=value*]\*] *jndi\_name*

**Description** The create-custom-resource command creates a custom resource. This command is supported in remote mode only.

**Options**

<code>—u</code> <code>—user</code>	The authorized domain application server administrative username.
<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>—H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>—p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>—s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>—t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>—e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.

<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	in Enterprise Edition, specifies the target to which you are deploying. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, which deploys the component to the default server instance <code>server</code> and is the default value</li> <li>▪ <code>domain</code>, which deploys the component to the domain.</li> <li>▪ <code>cluster_name</code>, which deploys the component to every server instance in the cluster.</li> <li>▪ <code>instance_name</code>, which deploys the component to a particular sever instance.</li> </ul>
<code>—resourcetype</code>	The <code>—resourcetype</code> option is deprecated. Use <code>—restype</code> instead.
<code>—restype</code>	The type of custom resource to be created.
<code>—factoryclass</code>	The class that creates the custom resource.
<code>—enabled</code>	Determines whether the custom resource is enable at runtime. The default value is true.
<code>—description</code>	Text providing descriptive details about the custom resource.
<code>—property</code>	optional attribute name/value pairs for configuring the resource.

**Operands** `jndi_name` the JNDI name of this resource.

**Examples** EXAMPLE 1 Using the `create-custom-resource` command

```
asadmin> create-custom-resource [--target plum] [--restype jax.sql.datasource] admin-gui/admin
Command create-custom-resource executed correctly.
```

Where `asadmin` is the command prompt and `jndi_name` is the name of the custom resource to be created.

<b>Exit Status</b> 0	command executed successfully
1	error in executing the command

**See Also** [delete-custom-resource\(1\)](#), [list-custom-resources\(1\)](#)

**Name** create-domain – creates a domain with the given name

**Synopsis** **create-domain** [`—domaindir` *install\_dir/domains*] `—adminuser` *admin\_user*  
`—passwordfile` *passwordfile*] [`—terse=false`] [`—echo=false`] [`—interactive=true`]  
`—instanceport` *port\_number*] [`—domainproperties` (*name=value*)[*:name=value*]\*]  
`—savemasterpassword=false`] *domain\_name*

**Description** Use the `create-domain` command to create a domain containing an instance that can administer itself. By creating a domain, an administration server is created in a directory named as the domain name. If you create a domain in a non-default directory, the domain will not be automatically shutdown during uninstallation. The `—adminpassword` option has been deprecated, use the `—passwordfile` option instead. To maintain high security, omit the `—passwordfile` from the command line and allow the system to prompt you for these options.

This command is supported in local mode only.

<b>Options</b> <code>—domaindir</code>	The directory where the domain is to be created. If specified, the path must be accessible in the filesystem. If not specified, the domain is created in the default domain directory.
<code>—adminport</code>	The administrative instance port number.
<code>—adminuser</code>	The username associated with the administrative instance.
<code>-W—passwordfile</code>	The file containing the domain application server password associated with the administrative instance. The password is defined in the following form: <code>AS_ADMIN_PASSWORD=password</code> . Where <i>password</i> is the actual administrator password for the domain. This file can also contain the <code>AS_ADMIN_ADMINPASSWORD</code> and the <code>AS_MASTERPASSWORD</code> . The syntax for each is the same as the syntax for <code>AS_ADMIN_PASSWORD</code> . Using this option on the command line can be insecure, since the password is stored in clear text. This file, however, can be protected by file system permissions.
<code>-t—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e—echo</code>	Setting to true will echo the command line statement on to the standard output. Default is false.
<code>-I—interactive</code>	If set to true (default), only the required options are prompted.
<code>—instanceport</code>	The port number listening to the HTTP request. The port number cannot be currently in use. If not specified, the default value is 8080.



`—domainproperties`

Setting the optional name/value pairs overrides the default values for the properties of the domain to be created. The list must be separated by the “:” character. The following properties are available:

Property	Definition
<code>jms.port</code>	This property specifies the port number for JMS. Valid value are 7676
<code>domain.jmxport</code>	This property specifies the port on which the JMS connector is initialized. Valid value are 1-65535
<code>orb.listener.port</code>	This property specifies which ORB listener port for IIOP connections <code>orb-listener-1</code> listens on.
<code>http.ssl.port</code>	This property specifies the port number for <code>http-listener-2</code> . Valid values are 1–65535. On UNIX, creating sockets that listen on ports 1–1024 requires superuser privileges.
<code>orb.ssl.port</code>	This property specifies which ORB listener port for IIOP connections the IIOP listener called <code>SSL</code> listens on.
<code>orb.mutualauth.port</code>	This property specifies which ORB listener port for IIOP connections the IIOP listener called <code>SSL_MUTUALAUTH</code> listens on.

`—savemasterpassword`

Setting this option to true allows the masterpassword to be written to the file system. It is best to create a masterpassword when creating a domain, because masterpassword is used by the `start-domain` command. For security purposes, the default setting should be false, because saving the masterpassword on the disk is an insecure practice, unless file system permissions are properly set. If masterpassword is saved, then `start-domain` will not prompt for it. Masterpassword gives an extra level of security to the environment.

**Operands** *domain\_name*                      The name of the domain to be created.

**Examples** EXAMPLE 1 Using the create-domain command

```
asadmin> create-domain --domaindir /export/domains
--adminport 7070 --adminuser admin --instanceport 7071 sampleDomain
created domain sampleDomain successfully
```

Where: the sampleDomain domain is created in the /export/domains directory.

**Exit Status** 0                                      command executed successfully

1    error in executing the command

**See Also** [delete-domain\(1\)](#), [start-domain\(1\)](#), [stop-domain\(1\)](#), [list-domains\(1\)](#)

- Name** create-file-user – creates a new file user
- Synopsis** **create-file-user** —user *admin\_user* [—passwordfile *filename*] [—host *host\_name*] [—port *port\_number*] [—secure|—s] [—terse=false] [—echo=false] [—interactive=true] [—help] [—target *target*] [—authrealmname*auth\_realm\_name*] [—groups *user\_groups[:user\_groups]\**] *user\_name*
- Description** Creates an entry in the keyfile with the specified username, userpassword, and groups. Multiple groups can be created by separating them with a colon ":". If the *auth\_realm\_name* is not specified, an entry is created in the default keyfile. If *auth\_realm\_name* is specified, an entry is created in the keyfile using the auth - realm name.
- This command is supported in remote mode only.
- Options**
- u** —user The authorized domain application server administrative username.
  - w** —password The —password option is deprecated. Use —passwordfile instead.
  - passwordfile** This option replaces the — password option. Using the —password option on the command line or through the environment is deprecated. The —passwordfile option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS\_ADMIN\_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS\_ADMIN\_PASSWORD=*password*, where *password* is the actual administrator password. Other passwords that can be specified include AS\_ADMIN\_MAPPEDPASSWORD, AS\_ADMIN\_USERPASSWORD, AS\_ADMIN\_SAVEDMASTERPASSWORD, AS\_ADMIN\_MQPASSWORD, AS\_ADMIN\_ALIASPASSWORD, and so on.
  - H** —host The machine name where the domain application server is running. The default value is localhost.
  - p** —port The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
  - s** —secure If set to true, uses SSL/TLS to communicate with the domain application server.
  - t** —terse Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.

<code>-e</code> <code>--echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>--interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>--help</code>	Displays the help text for the command.
<code>--target</code>	This is used for Enterprise Edition only. This is the name of the target on which the command operates. The valid targets are <code>config</code> , <code>instance</code> , <code>cluster</code> , or “ <code>server</code> .” By default, the target is the ‘ <code>Server</code> .’
<code>--groups</code>	This is the group associated with this file user.
<code>--authrealmname</code>	This is the file where the file users are stored.

**Operands** *user\_name* This is the name of file user to be created.

**Examples** EXAMPLE 1 Using the create-file-user command

It is assumed that an authority realm has already been created using the `create-auth-realm` command.

```
asadmin> create-file-user --user admin1 --password adminadmin1
--host pigeon --port 5001 --userpassword sample --groups staff:manager
--authrealmname auth-realm1 sample_user
Command create-file-user executed successfully
```

Where: the `sample_user` is the file user created.

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [create-auth-realm\(1\)](#), [delete-file-user\(1\)](#), [list-file-users\(1\)](#), [update-file-user\(1\)](#), [list-file-groups\(1\)](#)

**Name** create-ha-store – creates tables in the HADB that are used by HA the cluster

**Synopsis** **create-ha-store** —user *admin\_user* [—passwordfile *filename*] [—host *host\_name*] [—port *port\_number*] [—secure|—s] [—terse=*false*] [—echo=*false*] [—interactive=*true*] [—help] [—haagentport *port\_number*] *databaseName*

**Description** This command creates tables in the HADB used by the HA cluster. You only need to use this command if you have previously used `clear-ha-store`. The `configure-ha-store` command also creates tables in the HADB. Use fully qualified hostnames when specifying the hostlist interfaces explicitly for hosts with multiple network interfaces. `create-ha-store` was named `create-session-store` in the Sun Java System Application Server 7.1. `create-session-store` has been deprecated.

This command is supported in remote mode only.

<b>Options</b> -u —user	The authorized domain application server administrative username.
-w —password	The —password option is deprecated. Use —passwordfile instead.
—passwordfile	This option replaces the —password option. Using the —password option on the command line or through the environment is deprecated. The —passwordfile option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
-H —host	The machine name where the domain application server is running. The default value is localhost.
-p —port	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
-s —secure	If set to true, uses SSL/TLS to communicate with the domain application server.
-t —terse	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.

<code>-e</code>	<code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code>	<code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code>	<code>—help</code>	Displays the help text for the command.
<code>—haagentport</code>		The name of the HA agent port. If not specified, the default port number is 1862.

**Operands** *databaseName* The name of the HA database.

**Examples** EXAMPLE 1 Using create-ha-store

```
asadmin> create-ha-store hadatabase1  
The create-ha-store command executed successfully
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [clear-ha-store\(1\)](#), [configure-ha-cluster\(1\)](#)

<b>Name</b>	create-http-health-checker – creates a health-checker for a specified load balancer configuration
<b>Synopsis</b>	<b>create-http-health-checker</b> <code>—user</code> <i>admin_user</i> [ <code>—passwordfile</code> <i>filename</i> ] <code>[—host</code> <i>host_name</i> ] [ <code>—port</code> <i>port_number</i> ] [ <code>—secure</code>   <code>—s</code> ] [ <code>—terse</code> = <i>false</i> ] <code>[—echo</code> = <i>false</i> ] [ <code>—interactive</code> = <i>true</i> ] [ <code>—help</code> ] [ <code>—url</code> <i>"/"</i> ] [ <code>—interval</code> <i>30</i> ] <code>[—timeout</code> <i>10</i> ] <code>—config</code> <i>config_name target</i>
<b>Description</b>	This command creates a health checker for a specified load balancer configuration. It only works with the native load balancer provided with the Sun Java System Application Server. It does not work with other load balancers.
<b>Options</b>	
<code>—u</code> <code>—user</code>	The authorized domain application server administrative username.
<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>—H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>—p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>—s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>—t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>—e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.

<code>-I</code> <code>--interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>--help</code>	Displays the help text for the command.
<code>--url</code>	The URL to ping to determine whether the instance is healthy.
<code>--interval</code>	The interval in seconds the health checker waits between checks of an unhealthy instance to see whether it has become healthy. The default value is 30 seconds. A value of 0 disables the health checker.
<code>--timeout</code>	The interval in seconds the health checker waits to receive a response from an instance. If the health checker has not received a response in this interval, the instance is considered unhealthy.
<code>--config</code>	The load balancer configuration for which you create the health-checker.

**Operands** *target*

Specifies the target to which the health checker applies.

Valid values are:

- *cluster\_name*, which specifies the health checker will monitor all instances in the cluster.
- *instance\_name*, which specifies that the health checker will monitor this standalone instance.

**Examples** EXAMPLE 1 Using the create-http-health-checker command

```
asadmin> create-http-health-checker --user admin
--passwordfile password.txt --config mycluster-http-lb-config mycluster
Command create-http-health-checker executed successfully.
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [delete-http-health-checker\(1\)](#)



**Name** `create-http-lb-config` – creates a configuration for the load balancer

**Synopsis** `create-http-lb-config` `--user` *admin\_user* [`--passwordfile` *filename*]  
 [`--host` *host\_name*] [`--port` *port\_number*] [`--secure|-s`] [`--terse=false`]  
 [`--echo=false`] [`--interactive=true`] [`--help`] [`--responsetimeout 60`]  
 [`--httpsrouting=false`] [`--reloadinterval 60`] [`--monitor=false`]  
 [`--routecookie=true`] [`--target` *target*] [*config\_name*]

**Description** Use the `create-http-lb-config` command to create a load balancer configuration. This configuration applies to load balancing in the HTTP path.

You must specify either a target or a configuration name, or both. If you don't specify a target, the configuration is created but not assigned to a target. If you don't specify a configuration name, a name is created based on the target name. If you specify both, the configuration is created with the specified name, referencing the specified target.

<b>Options</b> <code>-u</code> <code>--user</code>	The authorized domain application server administrative username.
<code>-w</code> <code>--password</code>	The <code>--password</code> option is deprecated. Use <code>--passwordfile</code> instead.
<code>--passwordfile</code>	This option replaces the <code>--password</code> option. Using the <code>--password</code> option on the command line or through the environment is deprecated. The <code>--passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>-H</code> <code>--host</code>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
<code>-p</code> <code>--port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>-s</code> <code>--secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.

<code>-t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—responsetimeout</code>	The time in seconds within which a server instance must return a response. If no response is received within the time period, the server is considered unhealthy. If set to a positive number, and the request is idempotent, the request is retried. If the request is not idempotent, an error page is returned. If set to 0 no timeout is used. The default is 60.
<code>—httpsrouting</code>	If set to true, HTTPS requests to the load balancer result in HTTPS requests to the server instance. If set to false, HTTPS requests to the load balancer result in HTTP requests to the server instance. The default is false.
<code>—reloadinterval</code>	The interval between checks for changes to the load balancer configuration file <code>loadbalancer.xml</code> . When the check detects changes, the configuration file is reloaded. A value of 0 disables reloading.
<code>—monitor</code>	Specifies whether monitoring is enabled. The default is false.
<code>—routecookie</code>	Specifies whether a route cookie is enabled.
<code>—target</code>	Specifies the target to which the load balancer configuration applies. If you don't specify a target, the load balancer configuration is created without a target. You can specify targets later using the command <code>create-http-lb-ref</code> .

Valid values are:

- *cluster\_name*, which specifies that requests for this cluster will be handled by the load balancer.
- *instance\_name*, which specifies that requests for this standalone instance will be handled by the load balancer.

**Operands** *config\_name*

The name of the new load balancer configuration. This name must not conflict with any other load balancer groups, agents, configurations, clusters, or sever instances in the domain. If you don't specify a name, the load balancer configuration name is based on the target name, *target\_name-http-lb-config*.

**Examples** EXAMPLE 1 Using the create-http-lb-config command

```
asadmin> create-http-lb-config --user admin --passwordfile file --target mycluster  
mylbconfigname
```

Command create-http-lb-config executed successfully.

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [delete-http-lb-config\(1\)](#), [list-http-lb-configs\(1\)](#)

---

<b>Name</b>	create-http-lb-ref – adds an existing cluster or server instance to an existing load balancer configuration
<b>Synopsis</b>	<b>create-http-lb-ref</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] <b>—config</b> <i>config_name target</i>
<b>Description</b>	Use the create-http-lb-ref command to add an existing cluster or server instance to an existing load balancer configuration. The load balancer forwards the requests to the clustered and standalone instances it references.
<b>Options</b>	<p><b>-u</b> <b>—user</b> The authorized domain application server administrative username.</p> <p><b>-w</b> <b>—password</b> The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.</p> <p><b>—passwordfile</b> This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b><i>password</i>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b>, <b>AS_ADMIN_USERPASSWORD</b>, <b>AS_ADMIN_SAVEDMASTERPASSWORD</b>, <b>AS_ADMIN_MQPASSWORD</b>, <b>AS_ADMIN_ALIASPASSWORD</b>, and so on.</p> <p><b>-H</b> <b>—host</b> The machine name where the domain application server is running. The default value is localhost.</p> <p><b>-p</b> <b>—port</b> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><b>-s</b> <b>—secure</b> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><b>-t</b> <b>—terse</b> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p> <p><b>-e</b> <b>—echo</b> Setting to true will echo the command line statement on the standard output. Default is false.</p>

---

<code>-I</code>	<code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code>	<code>—help</code>	Displays the help text for the command.
	<code>—config</code>	Specifies which load balancer configuration to add clusters and server instances to.
<b>Operands</b>	<i>target</i>	Specifies which cluster or instance to add to the load balancer. Valid values are: <ul style="list-style-type: none"> <li>▪ <i>cluster_name</i>, which specifies that requests for this cluster will be handled by the load balancer.</li> <li>▪ <i>instance_name</i>, which specifies that requests for this standalone instance will be handled by the load balancer.</li> </ul>
<b>Examples</b>	<p>EXAMPLE 1 Using the create-http-lb-ref command</p> <pre>asadmin&gt; create-http-lb-ref --user admin --passwordfile file --config mycluster-http-lb-config cluster2</pre> <p>Command create-http-lb-ref executed successfully.</p>	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>See Also</b>	<a href="#">delete-http-lb-ref(1)</a> , <a href="#">list-http-lb-configs(1)</a>	

---

<b>Name</b>	create-http-listener – adds a new HTTP listener socket
<b>Synopsis</b>	<b>create-http-listener</b> <code>—user</code> <i>admin_user</i> [ <code>—passwordfile</code> <i>filename</i> ] [ <code>—host</code> <i>host_name</i> ] [ <code>—port</code> <i>port_number</i> ] [ <code>—secure</code>   <code>-s</code> ] [ <code>—terse</code> = <i>false</i> ] [ <code>—echo</code> = <i>false</i> ] [ <code>—interactive</code> = <i>true</i> ] [ <code>—help</code> ] [ <code>—target</code> <i>server</i> ] <code>—listeneraddress</code> <i>address</i> <code>—listenerport</code> <i>listener_port</i> <code>—defaultvs</code> <i>virtual_server</i> <code>—servername</code> <i>server_name</i> [ <code>—acceptorthreads</code> <i>1</i> ] [ <code>—securityenabled</code> = <i>false</i> ] [ <code>—redirectport</code> <i>redirect_port</i> ] [ <code>—xpowered</code> = <i>true</i> ] [ <code>—enabled</code> = <i>true</i> ] <i>listener_id</i>
<b>Description</b>	The <code>create-http-listener</code> command creates an HTTP listener. This command is supported in remote mode only.
<b>Options</b>	<p><code>-u</code> <code>—user</code> The authorized domain application server administrative username.</p> <p><code>-w</code> <code>—password</code> The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.</p> <p><code>—passwordfile</code> This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</p> <p><code>-H</code> <code>—host</code> The machine name where the domain application server is running. The default value is <code>localhost</code>.</p> <p><code>-p</code> <code>—port</code> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><code>-s</code> <code>—secure</code> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><code>-t</code> <code>—terse</code> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p> <p><code>-e</code> <code>—echo</code> Setting to true will echo the command line statement on the standard output. Default is false.</p>

---

<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target for which you are creating the HTTP listener. Valid values are <ul style="list-style-type: none"><li>▪ <code>server</code>, which creates the listener for the default server instance <code>server</code> and is the default value</li><li>▪ <code>configuration_name</code>, which creates the listener for the named configuration</li><li>▪ <code>cluster_name</code>, which creates the listener for every server instance in the cluster</li><li>▪ <code>instance_name</code>, which creates the listener for a particular server instance</li></ul>
<code>—listeneraddress</code>	The IP address of the listener address (resolvable by DNS).
<code>—listenerport</code>	The port number to create the listen socket on. Legal values are 1–65535. On UNIX, creating sockets that listen on ports 1–1024 requires superuser privileges. Configuring an SSL listen socket to listen on port 443 is recommended.
<code>—defaultvs</code>	The ID attribute of the default virtual server for this listener.
<code>—servername</code>	Tells the server what to put in the host name section of any URLs it sends to the client. This affects URLs the server automatically generates; it doesn't affect the URLs for directories and files stored in the server. This name should be the alias name if your server uses an alias. If a colon and port number are appended, that port will be used in URLs that the server sends to the client.
<code>—acceptorthreads</code>	The number of acceptor threads for the listen socket. The recommended value is the number of processors in the machine. The default value is 1.
<code>—securityenabled</code>	If set to true, the HTTP listener runs SSL. You can turn SSL2 or SSL3 ON or OFF and set ciphers using an SSL element. The security setting globally enables or disables SSL by making certificates available to the server instance. The default value is false.
<code>—redirectport</code>	Port number for redirects. If the HTTP listener is supporting non-SSL requests, and a request is received for which a matching security-constraint requires SSL transport, the Application Server will automatically redirect the request to this port number. This option is valid for Enterprise Edition only.

`--xpowered` If set to `true`, adds the `X-Powered-By: Servlet/2.4` and `X-Powered-By: JSP/2.0` headers to the appropriate responses. The Servlet 2.4 specification defines the `X-Powered-By: Servlet/2.4` header, which containers may add to servlet-generated responses. Similarly, the JSP 2.0 specification defines the `X-Powered-By: JSP/2.0` header, which containers may add to responses that use JSP technology. The goal of these headers is to aid in gathering statistical data about the use of Servlet and JSP technology.

`--enabled` If set to `true`, the listener is enabled at runtime.

**Operands** `listener_id` The listener ID of the HTTP listener.

**Examples** **EXAMPLE 1** Using the `create-http-listener` command

The following command creates an HTTP listener named `sampleListener` that uses a nondefault number of acceptor threads and is not enabled at runtime:

```
asadmin> create-http-listener --user admin1
--passwordfile passwords.txt --host pigeon --port 5001
--listeneraddress 0.0.0.0 --listenerport 7272
--defaultvs server --servername pigeon.red.planet.com
--acceptorthreads 100 --securityenabled=false
--enabled=false sampleListener
```

Command `create-http-listener` executed successfully.

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [delete-http-listener\(1\)](#), [list-http-listeners\(1\)](#), [create-virtual-server\(1\)](#), [create-ssl\(1\)](#)



<b>Name</b>	create-iiop-listener – adds an IIOP listener	
<b>Synopsis</b>	<b>create-iiop-listener</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>—s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—target</b> <i>server</i> ] <b>—listeneraddress</b> <i>address</i> [ <b>—iiopport</b> <i>1072</i> ] [ <b>—securityenabled</b> = <i>false</i> ] [ <b>—enabled</b> = <i>true</i> ] [ <b>—property</b> ( <i>name=value</i> )[ <i>:name=value</i> ]*] <i>listener_id</i>	
<b>Description</b>	The create-iiop-listener command creates an IIOP listener. This command is supported in remote mode only.	
<b>Options</b>	<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
	<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
	<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.

---

<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target for which you are creating the IIOP listener. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, which creates the listener for the default server instance <code>server</code> and is the default value</li> <li>▪ <code>configuration_name</code>, which creates the listener for the named configuration</li> <li>▪ <code>cluster_name</code>, which creates the listener for every server instance in the cluster</li> <li>▪ <code>instance_name</code>, which creates the listener for a particular server instance</li> </ul>
<code>—listeneraddress</code>	Either the IP address or the hostname (resolvable by DNS).
<code>—iiopport</code>	The IIOP port number. The default value is 1072.
<code>—securityenabled</code>	If set to true, the IIOP listener runs SSL. You can turn SSL2 or SSL3 ON or OFF and set ciphers using an SSL element. The security setting globally enables or disables SSL by making certificates available to the server instance. The default value is false.
<code>—enabled</code>	If set to true, the IIOP listener is enabled at runtime.
<code>—property</code>	Optional attribute name/value pairs for configuring the IIOP listener.

**Operands** *listener\_id* A unique identifier for the IIOP listener to be created.

**Examples** **EXAMPLE 1** Using the `create-iiop-listener` command

The following command creates an IIOP listener named `sample_iiop_listener`:

```
asadmin> create-iiop-listener --user admin
--passwordfile passwords.txt --host fuyako --port 7070
--listeneraddress 192.168.1.100 --iiopport 8080 sample_iiop_listener
Command create-iiop-listener executed successfully.
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [delete-iiop-listener\(1\)](#), [list-iiop-listeners\(1\)](#), [create-ssl\(1\)](#)

**Name** create-instance – creates an instance

**Synopsis** **create-instance** **—user** *admin\_user* [**—passwordfile** *filename*] [**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**-s**] [**—terse**=*false*] [**—echo**=*false*] [**—interactive**=*true*] [**—help**] [**—config** *config\_name* | **—cluster** *cluster\_name*] **—nodeagent** *nodeagent\_name* [**—systemproperties** (*name=value*)[**:***name=value*]\*] *instance\_name*

**Description** Use the create-instance command to create a new server instance residing on a local or remote machine. For a server instance to be functional it must have:

- A reference to a node agent which defines the machine where the server instance resides.
- A reference to a configuration which defines the configuration of the instance. A server instance that is joining a cluster receives its configuration from its parent cluster.

The node agent does not need to be created or started to create the instance; however, if the node agent is running, a remote server instance is created in a stopped state. If the node agent is not running, domain.xml is updated with the instance information and a new server instance is created the next time the node agent is started.

There are three types of server instances that can be created. Each server instance can only be of one type:

1. Standalone server instance: the configuration for this instance is not shared by any other server instances or clusters. When a standalone server instance is created, a standalone configuration is also created based on the default-config configuration. If no configuration or cluster is identified, a standalone server instance is created by default.
2. Shared server instance: the configuration for this instance is shared with other server instances or clusters. A server instance is considered shared if its configuration is shared by any other server instances.
3. Clustered server instance: the configuration for this instance is shared with other instances in the cluster. A server instance that is a member of the cluster inherits its configuration from that cluster. Any server instance that is not part of a cluster is considered an unclustered server instance.

When creating server instances Application Server attempts to resolve possible port conflicts. It also assigns random ports, currently not in use and not already assigned to other instances on the same node agent. Use the **—systemproperties** option to create additional instances on the same node agent and specify system properties to resolve the port conflicts. System properties can be manipulated after instance creation using the system property commands.

<b>Options</b>	<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.

<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>-H—host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>-p—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>-s—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>-t—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h—help</code>	Displays the help text for the command.
<code>—config</code>	Creates a shared server instance. The configuration name must exist and must not be named <code>default-config</code> or <code>server-config</code> . If the configuration name provided is a standalone configuration, an error is displayed.
<code>—cluster</code>	Creates a clustered server instance that inherits its configuration from the named cluster.
<code>—nodeagent</code>	The name of the node agent defining the machine where the server will be created. The node agent does not need to be running or even created. If the node agent does not exist, a placeholder will automatically be created in <code>domain.xml</code> .

## —systemproperties

Defines system properties for the server instance. These properties override property definitions in the server instance's configuration. Currently, these properties allow a way for a server instance to override port settings defined in its configuration. This is necessary if for example two clustered instances (sharing the same configuration) reside on the same machine. The following properties are available:

Property	Definition
http-listener-1-port	This port is used to listen for HTTP requests. This property specifies the port number for http-listener-1. Valid values are 1–65535. On UNIX, creating sockets that listen on ports 1–1024 requires superuser privileges.
http-listener-2-port	This port is used to listen for HTTPS requests. This property specifies the port number for http-listener-2. Valid values are 1–65535. On UNIX, creating sockets that listen on ports 1–1024 requires superuser privileges.
orb-listener-1-port	This property specifies which ORB listener port for IIOp connections orb-listener-1 listens on.
IIOp_SSL_LISTENER_PORT	This port is used for secure IIOp connections.
IIOp_SSL_MUTUALAUTH_PORT	This property specifies which ORB listener port for IIOp connections the IIOp listener called SSL_MUTUALAUTH listens on.
JMS_SYSTEM_CONNECTOR_PORT	This property specifies the port number on which the JMX connector listens. Valid values are 1–65535. On UNIX, creating sockets that listen on ports 1–1024 requires superuser privileges.

**Operands** *instance\_name* The unique name of the instance being created. Each instance in the domain must have a unique name across all node agents, server instances, cluster names, and configuration names.

**Examples** EXAMPLE 1 Using the create-instance command

```
asadmin> create-instance --user admin --passwordfile password.txt
--host myhost --port 4849 --nodeagent agent1 instance1
Command create-instance executed successfully
```

Where: instance1 is created on a machine where node agent, agent1 resides.

EXAMPLE 2 Using the create-instance command with systemproperties

```
asadmin> create-instance --user admin --passwordfile password.txt
--host myhost --port 4849 --nodeagent apple_agent --systemproperties HTTP_LISTENER_PORT=58294:
HTTP_SSL_LISTENER_PORT=58297:IIOP_LISTENER_PORT=58300:IIOP_SSL_LISTENER_PORT=58303:
IIOP_SSL_MUTUALAUTH_PORT=58306:JMX_SYSTEM_CONNECTOR_PORT=58309 instance2
Command create-instance executed successfully
```

Where: instance2 is created on a remote machine apple where node agent, apple\_agent resides.

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [delete-instance\(1\)](#), [list-instances\(1\)](#), [start-instance\(1\)](#), [stop-instance\(1\)](#)

**Name** create-javamail-resource – creates a JavaMail session resource

**Synopsis** **create-javamail-resource** —user *admin\_user* [—passwordfile *filename*]  
 [—host *host\_name*] [—port *port\_number*] [—secure|—s] [—terse=*false*]  
 [—echo=*false*] [—interactive=*true*] [—help] [—target *target*]  
 —mailhost *hostname* —mailuser *username* —fromaddress *address*  
 [—storeprotocol *imap*] [—storeprotocolclass *com.sun.mail.imapIMAPStore*]  
 [—transportprotocol *smtp*] [—transportprotocolclass *com.sun.mail.smtp.SMTPTransport*]  
 [—debug=*false*] [—enabled=*true*] [—description *text*]  
 [—property (*name=value*)[:*name=value*]\*] *jndi\_name*

**Description** The create-javamail-resource command creates a JavaMail session resource. This command is supported in remote mode only.

**Options**

—u —user	The authorized domain application server administrative username.
—w —password	The —password option is deprecated. Use —passwordfile instead.
—passwordfile	This option replaces the —password option. Using the —password option on the command line or through the environment is deprecated. The —passwordfile option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
—H —host	The machine name where the domain application server is running. The default value is localhost.
—p —port	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
—s —secure	If set to true, uses SSL/TLS to communicate with the domain application server.
—t —terse	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.

<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target for which you are creating the JavaMail session resource. Valid values are <ul style="list-style-type: none"><li>▪ <code>server</code>, which creates the resource for the default server instance <code>server</code> and is the default value</li><li>▪ <code>domain</code>, which creates the resource for the domain</li><li>▪ <code>cluster_name</code>, which creates the resource for every server instance in the cluster</li><li>▪ <code>instance_name</code>, which creates the resource for a particular server instance</li></ul>
<code>—mailhost</code>	The DNS name of the default mail server. The connect methods of the Store and Transport objects use this value if a protocol-specific host property is not supplied. The name must be resolvable to an actual host name.
<code>—mailuser</code>	The mail account user name to provide when connecting to a mail server. The connect methods of the Store and Transport objects use this value if a protocol-specific username property is not supplied.
<code>—fromaddress</code>	The email address of the default user, in the form <i>username@host.domain</i> .
<code>—storeprotocol</code>	The mail server store protocol. The default is <code>imap</code> . Change this value only if you have reconfigured the Application Server's mail provider to use a nondefault store protocol.
<code>—storeprotocolclass</code>	The mail server store protocol class name. The default is <code>com.sun.mail.imap.IMAPStore</code> . Change this value only if you have reconfigured the Application Server's mail provider to use a nondefault store protocol.
<code>—transprotocol</code>	The mail server transport protocol. The default is <code>smtp</code> . Change this value only if you have reconfigured the Application Server's mail provider to use a nondefault transport protocol.
<code>—transprotocolclass</code>	The mail server transport protocol class name. The default is <code>com.sun.mail.smtp.SMTPTransport</code> . Change this value only if you have reconfigured the Application Server's mail provider to use a nondefault transport protocol.



<code>—debug</code>	If set to true, server starts up in debug mode for this resource. If the JavaMail log level is set to FINE or finer, the debugging output will be generated and will be included in the server log file. The default value is false.
<code>—enabled</code>	If set to true, the resource is enabled at runtime. The default value is true.
<code>—description</code>	A text description of the JavaMail resource.
<code>—property</code>	Optional attribute name/value pairs for configuring the JavaMail resource. The JavaMail API documentation lists the properties you might want to set.
<b>Operands</b> <i>jndi_name</i>	The JNDI name of the JavaMail resource to be created. It is a recommended practice to use the naming subcontext prefix <code>mail/</code> for JavaMail resources.

**Examples** EXAMPLE 1 Using the create-javamail-resource command

The following command creates a JavaMail resource named `mail/MyMailSession`. The escape character (`\`) is used in the `—fromaddress` option to distinguish the dot (`.`) and at sign (`@`). The JNDI name for a JavaMail session resource customarily includes the `mail/` naming subcontext.

```
asadmin> create-javamail-resource --user admin
--passwordfile passwords.txt --host fuyako --port 7070
--mailhost localhost --mailuser sample
--fromaddress sample\@sun\.com mail/MyMailSession
Command create-javamail-resource executed successfully.
```

<b>Exit Status</b> 0	command executed successfully
1	error in executing the command

**See Also** [delete-javamail-resource\(1\)](#), [list-javamail-resources\(1\)](#)

**Name** create-jdbc-connection-pool – registers the JDBC connection pool

**Synopsis** **create-jdbc-connection-pool** **—user** *admin\_user* [**—passwordfile** *filename*]  
 [**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**—s**] [**—terse**=*false*]  
 [**—echo**=*false*] [**—interactive**=*true*] [**—help**] [**—datasourceclassname** *classname*]  
 [**—restype** *res\_type*] [**—steadypoolsize** *poolsize*] [**—maxpoolsize** *poolsize*]  
 [**—maxwait** *time*] [**—poolresize** *limit*] [**—idletimeout** *time*]  
 [**—isolationlevel** *isolation\_level*] [**—isolationguaranteed** *true*]  
 [**—isconnectvalidatereq** *false*] [**—validationmethod** *auto-commit*]  
 [**—validationtable** *tablename*] [**—failconnection** *false*] [**—description** *text*]  
 [**—property** (*name=value*) [:*name=value*]\*] *connectionpoolid*

**Description** Registers a new JDBC connection pool with the specified JDBC connection pool name.

This command is supported in remote mode only.

<b>Options</b> <b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.

---

<code>-t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	The target option is deprecated.
<code>—datasourceclassname</code>	The name of the vendor supplied JDBC datasource resource manager.
<code>—restype</code>	The interface that the datasource class implements. Must be one of <code>javax.sql.DataSource</code> , <code>javax.sql.ConnectionPoolDataSource</code> or <code>javax.sql.XADataSource</code> . An error is produced when this option has a legal value and the indicated interface is not implemented by the datasource class. This option has no default value.
<code>—steadypoolsize</code>	The minimum and initial number of connections maintained in the pool. The default value is 8.
<code>—maxpoolsize</code>	The maximum number of connections that can be created. The default value is 32.
<code>—maxwait</code>	The amount of time a caller will wait before a connection timeout is sent. The default is 60 seconds. A value of 0 forces the caller to wait indefinitely.
<code>—poolresize</code>	The number of connections to be removed when <code>idletimeout</code> timer expires. Connections that have idled for longer than the timeout are candidates for removal. When the pool size reaches <code>steadypoolsize</code> , the connection removal stops. The default value is 2.
<code>—idletimeout</code>	The maximum time in seconds that a connection can remain idle in the pool. After this time, the implementation can close this connection. It is recommended that this timeout is kept shorter than the server side timeout to prevent the accumulation of unusable connections in the application. The default value is 300.

---

<code>--isolationlevel</code>	<p>This specifies the transaction-isolation-level on the pooled database connections. This option does not have a default value. If not specified, the pool operates with the default isolation level that the JDBC driver provides.</p> <p>You can set a desired isolation level using one of the standard transaction isolation levels: <code>read-uncommitted</code>, <code>read-committed</code>, <code>repeatable-read</code>, <code>serializable</code>. Applications that change the isolation level on a pooled connection programmatically risk polluting the pool. This could lead to program errors.</p>
<code>--isolationguaranteed</code>	<p>This is applicable only when a particular isolation level is specified for <code>transaction-isolation-level</code>. The default value is <code>true</code>.</p> <p>This option assures that every time a connection is obtained from the pool, <code>isolationlevel</code> is set to the desired value. This could have some performance impact on some JDBC drivers. Administrators can set this to <code>false</code> when the application does not change <code>--isolationlevel</code> before returning the connection.</p>
<code>--isconnectvalidatereq</code>	<p>If set to <code>true</code>, connections are validated or checked to see if they are usable before giving out the application. The default value is <code>false</code>.</p>
<code>--validationmethod</code>	<p>The name of the validation table used to perform a query to validate a connection. Valid settings are: <code>auto-commit</code>, <code>meta-data</code>, or <code>table</code>. The default value is <code>auto-commit</code>.</p>
<code>--validationtable</code>	<p>The name of the validation table used to perform a query to validate a connection.</p>
<code>--failconnection</code>	<p>If set to <code>true</code>, all connections in the pool must be closed when a single validation check fails. The default value is <code>false</code>. One attempt is made to re-establish failed connections.</p>
<code>--description</code>	<p>Text providing descriptive details about the specified JDBC connection pool.</p>
<code>--property</code>	<p>Optional attribute name/value pairs for configuring the connection pool.</p>

**Operands** *connection\_pool\_id* The name of the JDBC connection pool to be created.

**Examples** EXAMPLE 1 Using create-jdbc-connection-pool command

```
asadmin> create-jdbc-connection-pool --user admin --passwordfile adminadminfile
--host fuyako --port 7070 --datasourceclassname com.pointbase.jdbc.jdbcUniversalDriver
--restype jax.sql.XADataSource --isolationlevel serializable --isconnectvalidatereq=true
```

---

EXAMPLE 1 Using create-jdbc-connection-pool command (Continued)

```
--validationmethod auto-commit --description "XA Connection"  
--property DatabaseName="jdbc\:pointbase\:server\:\\localhost:9093/sample"  
:User=public:Password=public XA_connection_pool  
Command create-jdbc-connection-pool executed successfully
```

Where: the XA\_connection\_pool is created. The escape character “\” is used in the --property option to distinguish the colons (:) and the backslash (/).

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [delete-jdbc-connection-pool\(1\)](#), [list-jdbc-connection-pools\(1\)](#)

---

<b>Name</b>	create-jdbc-resource – creates a JDBC resource with the specified JNDI name
<b>Synopsis</b>	<b>create-jdbc-resource</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—target</b> <i>target</i> ] <i>connectionpoolid pool_name</i> [ <b>—enabled</b> = <i>true</i> ] [ <b>—description</b> <i>text</i> ] [ <b>—property</b> ( <i>name=value</i> )[ <b>:</b> <i>name=value</i> ]*] <i>jndi_name</i>
<b>Description</b>	The create-jdbc-resource command creates a new JDBC resource. This command is supported in remote mode only.
<b>Options</b>	<p><b>-u</b> <b>—user</b> The authorized domain application server administrative username.</p> <p><b>-w</b> <b>—password</b> The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.</p> <p><b>—passwordfile</b> This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=<i>password</i></b>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b>, <b>AS_ADMIN_USERPASSWORD</b>, <b>AS_ADMIN_SAVEDMASTERPASSWORD</b>, <b>AS_ADMIN_MQPASSWORD</b>, <b>AS_ADMIN_ALIASPASSWORD</b>, and so on.</p> <p><b>-H</b> <b>—host</b> The machine name where the domain application server is running. The default value is localhost.</p> <p><b>-p</b> <b>—port</b> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><b>-s</b> <b>—secure</b> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><b>-t</b> <b>—terse</b> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p> <p><b>-e</b> <b>—echo</b> Setting to true will echo the command line statement on the standard output. Default is false.</p>

---

<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	valid in Enterprise Edition only, specifies the target to which you are deploying. Valid values are 'server,' 'domain,' cluster, and instance. The default is server.
<code>—connectionpoolid</code>	The name of the JDBC connection pool. If two or more JDBC resource elements point to the same connection pool element, they use the same pool connections at runtime.
<code>—enabled</code>	Determines whether the JDBC resource is enable at runtime. The default value is true.
<code>—description</code>	Text providing descriptive details about the JDBC resource.
<code>—property</code>	optional attribute name/value pairs for configuring the resource.

**Operands** *jndi\_name* the JNDI name of this JDBC resource.

**Examples** EXAMPLE 1 Using the create-jdbc-resource command

```
asadmin> create-jdbc-resource --connectionpoolid connPool02 test_jdbc_resource
Command create-jdbc-resource executed successfully.
```

Where test\_jdbc\_resource is the name of the new JDBC resource.

**Exit Status**

0	command executed successfully
1	error in executing the command

**See Also** [delete-jdbc-resource\(1\)](#), [list-jdbc-resources\(1\)](#)

---

<b>Name</b>	create-jmsdest – creates a physical destination	
<b>Synopsis</b>	<b>create-jmsdest</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ]         [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ]         [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—target</b> <i>target</i> ] <b>—desttype</b> <i>dest_type</i> [ <b>—property</b> ( <i>name=value</i> )[ <i>:name=value</i> ]*] <i>dest_name</i>	
<b>Description</b>	The <code>create-jmsdest</code> command creates a JMS physical destination. Along with the physical destination, you use the <code>create-jms-resource</code> command to create a JMS destination resource that has a Name property that specifies the physical destination. This command is supported in remote mode only.	
<b>Options</b>	<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
	<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
	<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.



<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target for which you are creating the physical destination. Although the <code>create-jmsdest</code> command is related to resources, a physical destination is created using the JMS Service, which is part of the configuration. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, which creates the physical destination for the default server instance <code>server</code> and is the default value</li> <li>▪ <code>configuration_name</code>, which creates the physical destination for the named configuration</li> <li>▪ <code>cluster_name</code>, which creates the physical destination for every server instance in the cluster</li> <li>▪ <code>instance_name</code>, which creates the physical destination for a particular server instance</li> </ul>
<code>-T</code> <code>—desttype</code>	The type of the JMS destination. Valid values are <code>topic</code> and <code>queue</code> .
<code>—property</code>	Optional attribute name/value pairs for configuring the physical destination. You can specify the following property for a physical destination:

Property	Definition
<code>maxNumActiveConsumers</code>	The maximum number of consumers that can be active in load-balanced delivery from a queue destination. A value of <code>-1</code> means an unlimited number. The default is <code>1</code> . (Platform Edition limits this value to <code>2</code> .)

To modify the value of this property or to specify other physical destination properties, use the `install_dir/imq/bin/imqcmd` command. See the *Sun Java System Message Queue 3 2005Q1 Administration Guide* for more information.

**Operands** `dest_name` A unique identifier for the the JMS destination to be created.

**Examples** EXAMPLE 1 Using the `create-jmsdest` command

The following command creates a JMS physical queue named `PhysicalQueue`.

**EXAMPLE 1** Using the create-jmsdest command *(Continued)*

```
asadmin> create-jmsdest --user admin
--passwordfile passwords.txt --host localhost --port 4848 --desttype queue
--property User=public:Password=public PhysicalQueue
Command create-jmsdest executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-jms-resource\(1\)](#), [delete-jmsdest\(1\)](#), [list-jmsdest\(1\)](#)

---

<b>Name</b>	create-jms-host – creates a JMS host
<b>Synopsis</b>	<b>create-jms-host</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—target</b> <i>target</i> ] [ <b>—mqhost</b> <i>localhost</i> ] [ <b>—mqport</b> <i>7676</i> ] [ <b>—mquser</b> <i>admin</i> ] [ <b>—mqpassword</b> <i>admin</i> ] <i>jms_host_name</i>
<b>Description</b>	Creates a JMS host within the JMS service. This command is supported in remote mode only.
<b>Options</b>	
<b>—u —user</b>	The authorized domain application server administrative username.
<b>—w —password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
<b>—H —host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>—p —port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>—s —secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
<b>—t —terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<b>—e —echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
<b>—I —interactive</b>	If set to true (default), only the required password options are prompted.

<code>-h</code> <code>--help</code>	Displays the help text for the command.
<code>--target</code>	In Enterprise Edition, specifies the target for which you are creating the JMS host. Valid values are <ul style="list-style-type: none"><li>▪ <code>server</code>, which creates the JMS host for the default server instance <code>server</code> and is the default value</li><li>▪ <code>configuration_name</code>, which creates the JMS host for the named configuration</li><li>▪ <code>cluster_name</code>, which creates the JMS host for every server instance in the cluster</li><li>▪ <code>instance_name</code>, which creates the JMS host for a particular server instance</li></ul>
<code>--mqhost</code>	The host name for the JMS service. The default value is <code>localhost</code> .
<code>--mqport</code>	The port number used by the JMS service. The default value is <code>7676</code> .
<code>--mquser</code>	The user name for the JMS service. The default value is <code>admin</code> .
<code>--mqpassword</code>	The password for the JMS service. The default value is <code>admin</code> .

**Operands** `jms_host_name` A unique identifier for the JMS host to be created.

**Examples** **EXAMPLE 1** Using the `create-jms-host` command

The following command creates a JMS host named `MyNewHost`:

```
asadmin> create-jms-host --user admin
--passwordfile passwords.txt --mqhost pigeon --mqport 7677 MyNewHost
Command create-jms-host executed successfully.
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [list-jms-hosts\(1\)](#), [delete-jms-host\(1\)](#)

**Name** create-jms-resource – creates a JMS resource

**Synopsis** **create-jms-resource** `—user` *admin\_user* [`—passwordfile` *filename*] [`—host` *host\_name*] [`—port` *port\_number*] [`—secure`|`-s`] [`—terse`=*false*] [`—echo`=*false*] [`—interactive`=*true*] [`—help`] [`—target` *target*] `—restype` *type* [`—enabled`=*true*] [`—description` *text*] [`—property` (*name=value*)[*:name=value*]\*] *jndi\_name*

**Description** The `create-jms-resource` command creates a Java Message Service (JMS) connection factory resource or a JMS destination resource. This command is supported in remote mode only.

**Options**

<code>—u</code> <code>—user</code>	The authorized domain application server administrative username.
<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>—H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
<code>—p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>—s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>—t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>—e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.

<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target for which you are creating the JMS resource. Valid values are <ul style="list-style-type: none"><li>▪ <code>server</code>, which creates the resource for the default server instance <code>server</code> and is the default value</li><li>▪ <code>domain</code>, which creates the resource for the domain</li><li>▪ <code>cluster_name</code>, which creates the resource for every server instance in the cluster</li><li>▪ <code>instance_name</code>, which creates the resource for a particular server instance</li></ul>
<code>—restype</code>	The JMS resource type, which can be either <code>javax.jms.Topic</code> , <code>javax.jms.Queue</code> , <code>javax.jms.ConnectionFactory</code> , <code>javax.jms.TopicConnectionFactory</code> , or <code>javax.jms.QueueConnectionFactory</code> .
<code>—enabled</code>	If set to true, the resource is enabled at runtime.
<code>—description</code>	A text description of the JMS resource.
<code>—property</code>	Optional attribute name/value pairs for configuring the JMS resource.

You can specify the following properties for a connection factory resource:

Property	Definition
ClientId	Specifies a client ID for a connection factory that will be used by a durable subscriber.

Property	Definition
AddressList	Specifies the names (and, optionally, port numbers) of a message broker instance or instances with which your application will communicate. Each address in the list specifies the host name (and, optionally, host port and connection service) for the connection. For example, the value could be <code>earth</code> or <code>earth:7677</code> . Specify the port number if the message broker is running on a port other than the default (7676). If you specify multiple hosts and ports in a clustered environment, the first available host on the list is used. Default: The local host and default port number (7676). The client will attempt a connection to a broker on port 7676 of the local host.
MessageServiceAddressList	Same as <code>AddressList</code> . This property name is deprecated. Use <code>AddressList</code> instead.
UserName	The user name for the connection factory. Default: <code>guest</code> .
Password	The password for the connection factory. Default: <code>guest</code> .
ReconnectEnabled	If enabled (value = <code>true</code> ), specifies that the client runtime attempts to reconnect to a message server (or the list of addresses in the <code>AddressList</code> ) when a connection is lost. Default: <code>false</code> .

Property	Definition
ReconnectAttempts	Specifies the number of attempts to connect (or reconnect) for each address in the AddressList before the client runtime tries the next address in the list. A value of -1 indicates that the number of reconnect attempts is unlimited (the client runtime attempts to connect to the first address until it succeeds). Default: 6.
ReconnectInterval	Specifies the interval in milliseconds between reconnect attempts. This applies for attempts on each address in the AddressList and for successive addresses in the list. If the interval is too short, the broker does not have time to recover. If it is too long, the reconnect might represent an unacceptable delay. Default: 30,000 milliseconds.
AddressListBehavior	Specifies whether connection attempts are in the order of addresses in the AddressList attribute (PRIORITY) or in a random order (RANDOM). PRIORITY means that the reconnect will always try to connect to the first server address in the AddressList and will use another one only if the first broker is not available. If you have many clients attempting a connection using the same connection factory, specify RANDOM to prevent them from all being connected to the same address. Default: PRIORITY.
AddressListIterations	Specifies the number of times the client runtime iterates through the AddressList in an effort to establish (or re-establish) a connection). A value of -1 indicates that the number of attempts is unlimited. Default: -1.



You can specify the following properties for a destination resource:

Property	Definition
Name	(Required) This property specifies the name of the physical destination to which the resource will refer. You create a physical destination with the <code>create-jmsdest</code> command.
Description	This property provides a description of the physical destination.

**Operands** *jndi\_name* The JNDI name of the JMS resource to be created.

**Examples** **EXAMPLE 1** Creating a JMS connection factory resource for durable subscriptions

The following command creates a connection factory resource of type `javax.jms.TopicConnectionFactory` whose JNDI name is `jms/DurableTopicConnectionFactory`. The `ClientId` property sets a client ID on the connection factory so that it can be used for durable subscriptions. The JNDI name for a JMS resource customarily includes the `jms/` naming subcontext.

```
asadmin> create-jms-resource --user admin1
--passwordfile passwords.txt --host pigeon --port 5001
--restype javax.jms.TopicConnectionFactory --description
"example of creating a JMS connection factory"
--property ClientId=MyID jms/DurableTopicConnectionFactory
Command create-jms-resource executed successfully.
```

**EXAMPLE 2** Creating a JMS destination resource

The following command creates a destination resource whose JNDI name is `jms/Queue`. The `Name` property specifies the physical destination to which the resource refers.

```
asadmin> create-jms-resource --user admin1
--passwordfile passwords.txt --host pigeon --port 5001
--restype javax.jms.Queue --property Name=PhysicalQueue jms/MyQueue
Command create-jms-resource executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [delete-jms-resource\(1\)](#), [list-jms-resources\(1\)](#), [create-jmsdest\(1\)](#)

---

<b>Name</b>	create-jndi-resource – registers a JNDI resource
<b>Synopsis</b>	<b>create-jndi-resource</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—target</b> <i>target</i> ] <b>—jndilookupname</b> <i>lookup_name</i> <b>—restype</b> <i>type</i> <b>—factoryclass</b> <i>class_name</i> [ <b>—enabled</b> = <i>true</i> ] [ <b>—description</b> <i>text</i> ] [ <b>—property</b> ( <i>name=value</i> )[ <i>:name=value</i> ]*] <i>jndi_name</i>
<b>Description</b>	The create-jndi-resource command registers a JNDI resource. This command is supported in remote mode only.
<b>Options</b>	<p><b>-u</b> <b>—user</b> The authorized domain application server administrative username.</p> <p><b>-w</b> <b>—password</b> The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.</p> <p><b>—passwordfile</b> This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b><i>password</i>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b>, <b>AS_ADMIN_USERPASSWORD</b>, <b>AS_ADMIN_SAVEDMASTERPASSWORD</b>, <b>AS_ADMIN_MQPASSWORD</b>, <b>AS_ADMIN_ALIASPASSWORD</b>, and so on.</p> <p><b>-H</b> <b>—host</b> The machine name where the domain application server is running. The default value is localhost.</p> <p><b>-p</b> <b>—port</b> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><b>-s</b> <b>—secure</b> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><b>-t</b> <b>—terse</b> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p> <p><b>-e</b> <b>—echo</b> Setting to true will echo the command line statement on the standard output. Default is false.</p>

<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	valid in Enterprise Edition only, specifies the target to which you are deploying. Valid values are 'server,' 'domain,' cluster, or instance. The default is server.
<code>—jndilookupname</code>	The lookup name that the external container uses.
<code>—resourcetype</code>	The <code>- resourcetype</code> option is deprecated. Use <code>- restype</code> instead.
<code>—restype</code>	The JNDI resource type. It can be topic or queue.
<code>—factoryclass</code>	The class that creates the JNDI resource.
<code>—enabled</code>	Determines whether the resource is enabled at runtime.
<code>—description</code>	The text that provides details about the JNDI resource.
<code>—property</code>	optional attribute name/value pairs for configuring the resource. The following properties are available:

Property	Definition
http-listener-1-port	This property specifies the port number for http-listener-1. Valid values are 1–65535. On UNIX, creating sockets that listen on ports 1–1024 requires superuser privileges.
http-listener-2-port	This property specifies the port number for http-listener-2. Valid values are 1–65535. On UNIX, creating sockets that listen on ports 1–1024 requires superuser privileges.
orb-listener-1-port	This property specifies which ORB listener port for IIOP connections orb-listener-1 listens on.
IIOP_SSL_LISTENER_PORT	This property specifies which ORB listener port for IIOP connections the IIOP listener called SSL listens on.

Property	Definition
IOP_SSL_MUTUALAUTH_PORT	This property specifies which ORB listener port for IOP connections the IOP listener called SSL_MUTUALAUTH listens on.
JMX_SYSTEM_Connector-port	This property specifies the port number on which the JMX connector listens. Valid values are 1–65535. On UNIX, creating sockets that listen on ports 1–1024 requires superuser privileges.

**Operands** *jndi\_name* The name of the JNDI resource to be created. This name must be unique.

**Examples** EXAMPLE 1 Using the create-jndi-resource command

```
asadmin> create-jndi-resource --user admin --passwordfile filename
--host pigeon --port 4001 --jndilookupname sample_jndi --restype queue
--factoryclass sampleClass --description "this is a sample jndi"
resource: sample_jndi_resource
```

Command create-jndi-resource executed successfully

Where sample\_jndi\_resource is the new JNDI resource created.

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [delete-jndi-resource\(1\)](#), [list-jndi-resources\(1\)](#)

---

<b>Name</b>	create-jvm-options – creates JVM options in the Java configuration or profiler elements of the domain.xml file.
<b>Synopsis</b>	<b>create-jvm-options</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> =false] [ <b>—echo</b> =false] [ <b>—interactive</b> =true] [ <b>—help</b> ] [ <b>—target</b> <i>target</i> ] [ <b>—profiler</b> =false] ( <i>jvm_option_name=jvm_option_value</i> ) [ <i>:jvm_option_name=jvm_option_name</i> ] *
<b>Description</b>	Creates JVM options in the Java configuration or profiler elements of the domain.xml file. JVM options are used to record the settings needed to get a particular profiler going.  This command is supported in remote mode only.  You must restart the server for newly created JVM options to take affect. Use the start/stop-domain command to restart the domain administration server.
<b>Options</b>	<p><b>-u</b> <b>—user</b> The authorized domain application server administrative username.</p> <p><b>-w</b> <b>—password</b> The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.</p> <p><b>—passwordfile</b> This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD=<i>password</i>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.</p> <p><b>-H</b> <b>—host</b> The machine name where the domain application server is running. The default value is localhost.</p> <p><b>-p</b> <b>—port</b> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><b>-s</b> <b>—secure</b> If set to true, uses SSL/TLS to communicate with the domain application server.</p>

<code>-t</code> <code>--terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>--echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>--interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>--help</code>	Displays the help text for the command.
<code>--target</code>	specifies the target to which you are deploying. Valid values are <code>config</code> , <code>instance</code> , <code>cluster</code> , or <code>'server'</code> . The default is <code>server</code> .
<code>--profiler</code>	indicates whether the JVM options are for the profiler. The profiler must exist for this option to be true.

**Operands** `jvm_option_name` the left side of the equal sign (=) is the JVM option name. The right side of the equal sign (=) is the JVM option value. A colon (: ) is a delimiter for multiple options.

**Examples** EXAMPLE 1 Using the create-jvm-options command

JVM options must start with a dash (-), . Use the backslash (\) to escape the dash delimiter.

```
asadmin> create-jvm-options --user admin --passwordfile adminfile
--host localhost --port 4849 --target server "\-Dtmp=sun"-e \-Doption1=value1
create-jvm-options --interactive=true --secure=true --passwordfile /password
--terse=false --user admin --target server --host localhost
--echo=true --port 4849 \-Doption1=value1
Command create-jvm-options executed successfully
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [delete-jvm-options\(1\)](#)

<b>Name</b>	create-lifecycle-module – adds a lifecycle module														
<b>Synopsis</b>	<pre> <b>create-lifecycle-module</b> --user <i>admin_user</i> [--passwordfile <i>filename</i>]   [--host <i>host_name</i>] [--port <i>port_number</i>] [--secure -s] [--terse=<i>false</i>]   [--echo=<i>false</i>] [--interactive=<i>true</i>] [--help] [--enabled=<i>true</i>] [--target <i>target</i>]   --classname <i>classname</i> [--classpath <i>classpath</i>] [--loadorder <i>loadorder</i>]   [--failurefatal=<i>false</i>] [--description <i>description</i>]   [--property (<i>name=value</i>)[:<i>name=value</i>]*] <i>module_name</i> </pre>														
<b>Description</b>	Creates the lifecycle module. The lifecycle modules provide a means of running short or long duration Java-based tasks within the application server environment. This command is supported in remote mode only.														
<b>Options</b>	<table border="0"> <tr> <td style="vertical-align: top;">-u --user</td> <td>The authorized domain application server administrative username.</td> </tr> <tr> <td style="vertical-align: top;">-w --password</td> <td>The --password option is deprecated. Use --passwordfile instead.</td> </tr> <tr> <td style="vertical-align: top;">--passwordfile</td> <td>This option replaces the --password option. Using the --password option on the command line or through the environment is deprecated. The --passwordfile option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD=<i>password</i>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.</td> </tr> <tr> <td style="vertical-align: top;">-H --host</td> <td>The machine name where the domain application server is running. The default value is localhost.</td> </tr> <tr> <td style="vertical-align: top;">-p --port</td> <td>The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</td> </tr> <tr> <td style="vertical-align: top;">-s --secure</td> <td>If set to true, uses SSL/TLS to communicate with the domain application server.</td> </tr> <tr> <td style="vertical-align: top;">-t --terse</td> <td>Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</td> </tr> </table>	-u --user	The authorized domain application server administrative username.	-w --password	The --password option is deprecated. Use --passwordfile instead.	--passwordfile	This option replaces the --password option. Using the --password option on the command line or through the environment is deprecated. The --passwordfile option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.	-H --host	The machine name where the domain application server is running. The default value is localhost.	-p --port	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.	-s --secure	If set to true, uses SSL/TLS to communicate with the domain application server.	-t --terse	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
-u --user	The authorized domain application server administrative username.														
-w --password	The --password option is deprecated. Use --passwordfile instead.														
--passwordfile	This option replaces the --password option. Using the --password option on the command line or through the environment is deprecated. The --passwordfile option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.														
-H --host	The machine name where the domain application server is running. The default value is localhost.														
-p --port	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.														
-s --secure	If set to true, uses SSL/TLS to communicate with the domain application server.														
-t --terse	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.														

<code>-e</code>	<code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code>	<code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code>	<code>—help</code>	Displays the help text for the command.
<code>—target</code>		This option is the name of the resulting location. The valid targets for this command are configuration, instace, cluster, or server. This is used by EE only.
<code>—classname</code>		This is the fully qualified name of the startup class.
<code>—classpath</code>		This option indicates where this module is actually located if it is not under applications-root.
<code>—loadorder</code>		This option represents an integer value that can be used to force the order in which deployed lifecycle modules are loaded at server startup. Smaller numbered modules get loaded sooner. Order is unspecified if two or more lifecycle modules have the same load-order value.
<code>—failurefatal</code>		This options tells the system what to do if the lifecycle module does not load correctly. If this option is set to true, then the system aborts the server startup if this module does not load properly.
<code>—enabled</code>		This option determines whether the resource is enabled at runtime.
<code>—description</code>		This is the text description of the resource associated with this module.
<code>—property</code>		This is an optional attribute containing name/value pairs used to configure the resource.
<b>Operands</b>	<i>module_name</i>	This operand is a unique identifier or the deployed server lifecycle event listener module.

**Examples** EXAMPLE 1 using create-lifecycle-module

```
asadmin> create-lifecycle-module --user admin --passwordfile adminpassword.txt
--host fuyako --port 7070 --classname "com.acme.CustomSetup"
--classpath "/export/customSetup" --loadorder 1 --failurefatal=true
--description "this is a sample customSetup"
--property rmi=Server="acme1\7070":timeout=30 customSetup
Command create-lifecycle-module executed successfully
```

Where: customSetup is the lifecycle module created. The escape character \ is used in the property option to distinguish the colons (:).



**Exit Status** 0                    command executed successfully  
              1                    error in executing the command

**See Also** [delete-lifecycle-module\(1\)](#), [list-lifecycle-modules\(1\)](#)

**Name** create-message-security-provider – enables administrators to create the message-security-config and provider-config sub-elements for the security service in domain.xml

**Synopsis** **create-message-security-provider** `—user admin_user` [`—passwordfile filename`] [`—host host_name`] [`—port port_number`] [`—secure|-s`] [`—terse=false`] [`—echo=false`] [`—interactive=true`] [`—help`] [`—target target`] `—classname provider_class` [`—layer message_layer`] [`—providertype provider_type`] [`—requestauthsource request_auth_source`] [`—requestauthrecipient request_auth_recipient`] [`—responseauthsource response_auth_source`] [`—responseauthrecipient response_auth_recipient`] [`—isdefaultprovider`] [`—property (name=value)[:name=value]*`] provider\_name

**Description** Enables the administrator to create the message-security-config and provider-config sub-elements for the security service in domain.xml (the file that specifies parameters and properties to the Application Server). The options specified in the list below apply to attributes within the message-security-config and provider-config sub-elements of the domain.xml file.

If the message-layer (message-security-config) does not exist, it is created, and then the provider-config is created under it.

This command is supported in remote mode only.

**Options** If an option has a short option name, then the short option precedes the long option name. Short options have one dash whereas long options have two dashes.

<code>—u</code> <code>—user</code>	The authorized domain application server administrative username.
<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.

---

<code>-H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>-p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>-s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>-t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target to which you are deploying. Valid values are <ul style="list-style-type: none"><li>▪ <code>server</code>, which deploys the component to the default server instance <code>server</code> and is the default value</li><li>▪ <code>domain</code>, which deploys the component to the domain.</li><li>▪ <code>cluster_name</code>, which deploys the component to every server instance in the cluster.</li><li>▪ <code>instance_name</code>, which deploys the component to a particular sever instance.</li></ul>

The following optional attribute name/value pairs are available:

Property	Definition
classname	Defines the Java implementation class of the provider. Client authentication providers must implement the <code>com.sun.enterprise.security.jauth.ClientAuthModule</code> interface. Server-side providers must implement the <code>com.sun.enterprise.security.jauth.ServerAuthModule</code> interface. A provider may implement both interfaces, but it must implement the interface corresponding to its provider type.
layer	The message-layer entity used to define the value of the <code>auth-layer</code> attribute of <code>message-security-config</code> elements. The default is <code>SOAP</code> .
providertype	Establishes whether the provider is to be used as client authentication provider, server authentication provider, or both. Valid options for this property include <code>client</code> , <code>server</code> , or <code>client-server</code> . The default value is <code>client-server</code> .
requestauthsource	The <code>auth-source</code> attribute defines a requirement for message-layer sender authentication (e.g. username password) or content authentication (e.g. digital signature) to be applied to request messages. Possible values are <code>sender</code> or <code>content</code> . When this argument is not specified, source authentication of the request is not required.

Property	Definition
requestauthrecipient	The <code>auth-recipient</code> attribute defines a requirement for message-layer authentication of the receiver of a message to its sender (e.g. by XML encryption). Possible values are <code>before-content</code> or <code>after-content</code> . The default value is <code>after-content</code> .
responseauthsource	The <code>auth-source</code> attribute defines a requirement for message-layer sender authentication (e.g. username password) or content authentication (e.g. digital signature) to be applied to response messages. Possible values are <code>sender</code> or <code>content</code> . When this option is not specified, source authentication of the response is not required.
responseauthrecipient	The <code>auth-recipient</code> attribute defines a requirement for message-layer authentication of the receiver of the response message to its sender (e.g. by XML encryption). Possible values are <code>before-content</code> or <code>after-content</code> . The default value is <code>after-content</code> .
isdefaultprovider	The <code>default-provider</code> attribute is used to designate the provider as the default provider (at the layer) of the type or types identified by the <code>providertype</code> argument. There is no default associated with this option.

Property	Definition
property	Use this property to pass provider-specific property values to the provider when it is initialized. Properties passed in this way might include key aliases to be used by the provider to get keys from keystores, signing, canonicalization, encryption algorithms, etc.

**Operands** *provider\_name*                      The name of the provider used to reference the provider-config element.

**Examples** **EXAMPLE 1** Using create-message-security-provider

The following example shows how to create a message security provider for a client.

```
asadmin> create-message-security-provider --user admin
--passwordfile pwd_file
--classname com.sun.enterprise.security.jauth.ClientAuthModule
--providertype client mySecurityProvider
```

**Exit Status** 0                                      command executed successfully  
1    error in executing the command

**See Also** [delete-message-security-provider\(1\)](#), [list-message-security-providers\(1\)](#)

---

<b>Name</b>	create-node-agent – creates a node agent																				
<b>Synopsis</b>	<b>create-node-agent</b> <b>—host</b> <i>DAS_host</i> <b>—port</b> <i>DAS_port</i> [ <b>—user</b> <i>DAS_user</i> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—agentdir</b> <i>nodeagent_path</i> ] [ <b>—agentport</b> <i>port_number</i> ] [ <b>—agentproperties</b> ( <i>name=value</i> )[ <b>:</b> <i>name=value</i> ]*] <b>—passwordfile</b> <i>password</i> [ <b>—savemasterpassword</b> = <i>false</i> ] [ <i>nodeagent_name</i> ]																				
<b>Description</b>	<p>The node agent facilitates remote server instance management. It is the responsibility of the node agent to create, start, stop, and delete a server instance. Every node agent must have a unique name and every new server instance must be created with a reference to a node agent name defining the machine on which the instance will reside. A node agent must be present on every machine that hosts server instances, including the machine hosting the Domain Administration Server (DAS).</p> <p>The domain administration server connection options identify the agent’s initial target domain. The DAS does not need to be running when the node agent is being created.</p>																				
<b>Options</b>	<table> <tr> <td><b>—host</b></td> <td>Specifies the connection attributes to the DAS. The agent attempts to contact the DAS and join the domain when it is started.</td> </tr> <tr> <td><b>—port</b></td> <td>Specifies the connection attributes to the DAS. The agent attempts to contact the DAS and join the domain when it is started.</td> </tr> <tr> <td><b>—user</b></td> <td>The username associated with the administrative instance. Specifies the connection attributes to the DAS. The agent attempts to contact the DAS and join the domain when it is started.</td> </tr> <tr> <td><b>--adminpassword</b></td> <td>The domain application server password associated with the administrative instance.</td> </tr> <tr> <td><b>-t —terse</b></td> <td>Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</td> </tr> <tr> <td><b>-e —echo</b></td> <td>Setting to true will echo the command line statement on to the standard output. Default is false.</td> </tr> <tr> <td><b>-I —interactive</b></td> <td>If set to true (default), only the required options are prompted.</td> </tr> <tr> <td><b>—agentdir</b></td> <td>Like a DAS, each node agent resides in a top level directory named /. If the agentdir is not specified, then the default install_dir/nodeagents is used.</td> </tr> <tr> <td><b>—agentport</b></td> <td>The port on which the node agent’s JMX connector will listen and accept requests. If not specified, then a random unused port is chosen.</td> </tr> <tr> <td><b>—agentproperties</b></td> <td>The following agentproperties are available:</td> </tr> </table>	<b>—host</b>	Specifies the connection attributes to the DAS. The agent attempts to contact the DAS and join the domain when it is started.	<b>—port</b>	Specifies the connection attributes to the DAS. The agent attempts to contact the DAS and join the domain when it is started.	<b>—user</b>	The username associated with the administrative instance. Specifies the connection attributes to the DAS. The agent attempts to contact the DAS and join the domain when it is started.	<b>--adminpassword</b>	The domain application server password associated with the administrative instance.	<b>-t —terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.	<b>-e —echo</b>	Setting to true will echo the command line statement on to the standard output. Default is false.	<b>-I —interactive</b>	If set to true (default), only the required options are prompted.	<b>—agentdir</b>	Like a DAS, each node agent resides in a top level directory named /. If the agentdir is not specified, then the default install_dir/nodeagents is used.	<b>—agentport</b>	The port on which the node agent’s JMX connector will listen and accept requests. If not specified, then a random unused port is chosen.	<b>—agentproperties</b>	The following agentproperties are available:
<b>—host</b>	Specifies the connection attributes to the DAS. The agent attempts to contact the DAS and join the domain when it is started.																				
<b>—port</b>	Specifies the connection attributes to the DAS. The agent attempts to contact the DAS and join the domain when it is started.																				
<b>—user</b>	The username associated with the administrative instance. Specifies the connection attributes to the DAS. The agent attempts to contact the DAS and join the domain when it is started.																				
<b>--adminpassword</b>	The domain application server password associated with the administrative instance.																				
<b>-t —terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.																				
<b>-e —echo</b>	Setting to true will echo the command line statement on to the standard output. Default is false.																				
<b>-I —interactive</b>	If set to true (default), only the required options are prompted.																				
<b>—agentdir</b>	Like a DAS, each node agent resides in a top level directory named /. If the agentdir is not specified, then the default install_dir/nodeagents is used.																				
<b>—agentport</b>	The port on which the node agent’s JMX connector will listen and accept requests. If not specified, then a random unused port is chosen.																				
<b>—agentproperties</b>	The following agentproperties are available:																				

Property	Definition
listenaddress	The address used by the JMX connector to listen for requests or notifications. The default is 0.0.0.0.
remoteclientaddress	The address used by DAS to connect to the Node Agent. The default is the hostname of the server.
loglevel	The initial log level at which messages are logged. The default is INFO.

**-W** **—passwordfile**

The file containing the domain application server password associated with the administrative instance. The password is defined in the following form:  
**AS\_ADMIN\_PASSWORD=***password*. Where *password* is the actual administrator password for the domain.

**—savemasterpassword**

Setting this option to true allows the master password to be written to the file system. This is necessary so that the `start - domain` command can start the server without having to prompt the user. However, for security purposes, the default setting is false because saving the master password on the disk is an insecure practice.

**Operands** *nodeagent\_name*

The name of the node agent must be unique in the domain. If not specified, the `nodeagent_name` defaults to the machine's host name.

**Examples** **EXAMPLE 1** Using `create-node-agent`

```
asadmin>create-node-agent --host dance --port 4848 --user admin1 --passwordfile pass2 nodeagent1
Node Agent nodeagent1 created.
```

Where: `nodeagent1` was created in the default `install_dir/nodeagents` directory.

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [delete-node-agent\(1\)](#), [list-node-agents\(1\)](#), [start-node-agent\(1\)](#), [stop-node-agent\(1\)](#)



---

<b>Name</b>	create-node-agent-config – adds a new unbound node agent to a domain	
<b>Synopsis</b>	<b>create-node-agent-config</b> —user <i>admin_name</i> —passwordfile <i>filename</i> [—host <i>localhost</i> ] [—port <i>port_number</i> ] [—secure= <i>false</i> ] [—terse= <i>false</i> ] [—echo= <i>false</i> ] [—interactive= <i>true</i> ] <i>nodeagent_name</i>	
<b>Description</b>	This command allows an agent placeholder to be created before the node agent’s directory structure is created, using the create-node-agent command. This supports the offline configuration scenario where administrators define server instances in advance of creating the node agents on remote machines.	
<b>Options</b>	—u—user	The authorized domain application server administrative username.
	—w—password	The —password option is deprecated. Use —passwordfile instead.
	—passwordfile	The name of the file containing the domain application server password. The passwordfile should contain either of the following entries: AS_ADMIN_PASSWORD= <i>password</i> or AS_ADMIN_MAPPEDPASSWORD= <i>password</i> . If this option is not called directly, you will be prompted for it before the requested action is completed.
	—H—host	The machine name where the the domain application server is running.
	—p—port	The port number of the domain application server listening for administration requests.
	—s—secure	If set to true, this command uses SSL/TLS to communicate with the domain application server.
	—t—terse	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. The default is false.
	—e—echo	Setting this option to true will echo the command line statement on the standard output. The default is false.
	—I—interactive	If this option is set to true (default), only the required password options are prompted.
<b>Operands</b>	<i>nodeagent_name</i>	The name of the node must be unique on the machine. Typically, the nodeagent_name is the host name of the machine where the node agent will reside.
<b>Examples</b>	EXAMPLE 1 Using create-node-agent-config asadmin> <b>create-node-agent-config --user admin1 --passwordfile filename nodeagent1</b> Command create-node-agent-config executed successfully.	

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [delete-node-agent-config\(1\)](#)

---

<b>Name</b>	create-password-alias – creates a password alias														
<b>Synopsis</b>	<b>create-password-alias</b> <i>—user admin_user</i> [ <i>—passwordfile filename</i> ] <i>[—host host_name]</i> [ <i>—port port_number</i> ] [ <i>—secure —s</i> ] [ <i>—terse=false</i> ] <i>[—echo=false]</i> [ <i>—interactive=true</i> ] [ <i>—help</i> ] [ <i>—aliaspassword alias_password</i> ] <i>aliasname</i>														
<b>Description</b>	This command creates an alias for a password and stores it in domain.xml. An alias is a token of the form <code>#{ALIAS=password-alias-password}</code> . The password corresponding to the alias name is stored in encrypted form. The password-alias commands take both a secure interactive form (in which the user is prompted for all information) and a more script-friendly form, in which the password is propagated on the command line.														
	This command is supported in remote mode only.														
<b>Options</b>	<table border="0"> <tr> <td style="vertical-align: top;"><i>—u —user</i></td> <td>The authorized domain application server administrative username.</td> </tr> <tr> <td style="vertical-align: top;"><i>—w —password</i></td> <td>The <i>—password</i> option is deprecated. Use <i>—passwordfile</i> instead.</td> </tr> <tr> <td style="vertical-align: top;"><i>—passwordfile</i></td> <td>This option replaces the <i>—password</i> option. Using the <i>—password</i> option on the command line or through the environment is deprecated. The <i>—passwordfile</i> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format:  <code>AS_ADMIN_PASSWORD=password</code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</td> </tr> <tr> <td style="vertical-align: top;"><i>—H —host</i></td> <td>The machine name where the domain application server is running. The default value is localhost.</td> </tr> <tr> <td style="vertical-align: top;"><i>—p —port</i></td> <td>The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</td> </tr> <tr> <td style="vertical-align: top;"><i>—s —secure</i></td> <td>If set to true, uses SSL/TLS to communicate with the domain application server.</td> </tr> <tr> <td style="vertical-align: top;"><i>—t —terse</i></td> <td>Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</td> </tr> </table>	<i>—u —user</i>	The authorized domain application server administrative username.	<i>—w —password</i>	The <i>—password</i> option is deprecated. Use <i>—passwordfile</i> instead.	<i>—passwordfile</i>	This option replaces the <i>—password</i> option. Using the <i>—password</i> option on the command line or through the environment is deprecated. The <i>—passwordfile</i> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.	<i>—H —host</i>	The machine name where the domain application server is running. The default value is localhost.	<i>—p —port</i>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.	<i>—s —secure</i>	If set to true, uses SSL/TLS to communicate with the domain application server.	<i>—t —terse</i>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<i>—u —user</i>	The authorized domain application server administrative username.														
<i>—w —password</i>	The <i>—password</i> option is deprecated. Use <i>—passwordfile</i> instead.														
<i>—passwordfile</i>	This option replaces the <i>—password</i> option. Using the <i>—password</i> option on the command line or through the environment is deprecated. The <i>—passwordfile</i> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.														
<i>—H —host</i>	The machine name where the domain application server is running. The default value is localhost.														
<i>—p —port</i>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.														
<i>—s —secure</i>	If set to true, uses SSL/TLS to communicate with the domain application server.														
<i>—t —terse</i>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.														

<code>-e</code> <code>--echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>--interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>--help</code>	Displays the help text for the command.
<code>--aliaspassword</code>	This is a separate and distinct password corresponding to the original password. <b>WARNING:</b> Passing this password on the command line is not secure.  The password is optional and when omitted, the user is prompted.

**Operands** `aliasname` This is the name of the substitute password as it appears in `domain.xml`.

**Examples** `EXAMPLE 1` Using `create-password-alias`

```
asadmin> create-password-alias --aliasname alias1
```

Command `create-password-alias` executed successfully

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [delete-password-alias\(1\)](#), [list-password-aliases\(1\)](#), [update-password-alias\(1\)](#)

**Name** create-persistence-resource – registers a persistence resource

**Synopsis** **create-persistence-resource** **—user** *admin\_user* [**—passwordfile** *filename*]  
 [**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**—s**] [**—terse**=*false*]  
 [**—echo**=*false*] [**—interactive**=*true*] [**—help**] [**—enabled**=*true*] [**—target** *target*]  
 [**—jdbcjndiname** *jndi\_name* | **—connectionpoolid** *id*] [**—factoryclass** *classname*]  
 [**—description** *text*] [**—property** (*name=value*)[*:name=value*]\*] *jndi\_name*

**Description** Registers a persistence resource. This command is supported in remote mode only.

The **—jdbcjndiname** option and the **—connectionpoolid** option are mutually exclusive; only one should be used.

<b>Options</b> <b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=<i>password</i></b> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.

<code>-e</code>	<code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code>	<code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code>	<code>—help</code>	Displays the help text for the command.
	<code>—enabled</code>	Determines whether the resource is enabled at runtime.
	<code>—target</code>	Specifies the target for which you are creating a persistence resource. This option is available only in the Sun Java System Application Server Enterprise Edition. Valid values are <ul style="list-style-type: none"><li>▪ <code>server</code>, which deploys the component to the default server instance <code>server</code> and is the default value</li><li>▪ <code>domain</code>, which deploys the component to the domain.</li><li>▪ <code>cluster_name</code>, which deploys the component to every server instance in the cluster.</li><li>▪ <code>instance_name</code>, which deploys the component to a particular sever instance.</li></ul>
	<code>—jdbcjndiname</code>	Specifies the JDBC resource with which database connections are obtained. It must be the name of a pre-created JDBC resource.
	<code>—connectionpoolid</code>	Specifies the name of the JDBC connection pool. If two or more JDBC resource elements point to the same connection pool element, they use the same pool connections at runtime.
	<code>—factoryclass</code>	Deprecated, and not needed for the default CMP implementation. Specifies the class that creates the persistence manager instance.
	<code>—description</code>	Specifies a text description of the persistence resource.
	<code>—property</code>	Specifies optional name/value pairs for configuring the persistence resource.

**Operands** *jndi\_name* Specifies the JNDI name of the persistence resource.

**Examples** EXAMPLE 1 Using `create-persistence-resource`

```
asadmin> create-persistence-resource --user admin --passwordfile secret.txt
--jdbcjndiname sample_jndi_resource sample_persistence_resource
Command create-persistence-resource executed successfully
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [delete-persistence-resource\(1\)](#), [list-persistence-resources\(1\)](#)

**Name** create-profiler – creates the profiler element

**Synopsis** **create-profiler** `—user` *admin\_user* [`—passwordfile` *filename*] [`—host` *host\_name*] [`—port` *port\_number*] [`—secure`|`—s`] [`—terse`=*false*] [`—echo`=*false*] [`—interactive`=*true*] [`—help`] [`—target` *target\_name*] [`—classpath` *classpath*] [`—native-libpath` *native\_library\_path*] [`—enabled`] [`—property`(*name=value*)[*:name=value*]\*] *profiler\_name*

**Description** Creates the profiler element. A server instance is tied to a particular profiler, by the profiler element in the Java configuration. Changing a profiler requires you to restart the server.

This command is supported in remote mode only.

<b>Options</b> <code>—u</code> <code>—user</code>	The authorized domain application server administrative username.
<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>—H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>—p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>—s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>—t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.



<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target on which you are listing the realms. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, which creates the listener for the default server instance <code>server</code> and is the default value</li> <li>▪ <code>configuration_name</code>, which creates the listener for the named configuration</li> <li>▪ <code>cluster_name</code>, which creates the listener for every server instance in the cluster</li> <li>▪ <code>instance_name</code>, which creates the listener for a particular server instance</li> </ul>
<code>--classpath</code>	Java classpath string that specifies the classes needed by the profiler.
<code>--nativelibpath</code>	automatically constructed to be a concatenation of the Application Server installation relative path for its native shared libraries, standard JRE native library path, the shell environment setting ( <code>LD_LIBRARY_PATH</code> on UNIX) and any path that may be specified in the profile element.
<code>--enabled</code>	profiler is enabled by default.
<code>--property</code>	name/value pairs of provider specific attributes.
<b>Operands</b> <code>profiler_name</code>	name of the profiler.

**Examples** EXAMPLE 1 Using create-profiler

```
asadmin> create-profiler --user admin --passwordfile password.txt
--host localhost --port 4848 --classpath /home/appserver/
--nativelibpath /u/home/lib --enabled=false
--property defaultuser=admin:password=adminadmin sample_profiler
Created Profiler with id = sample_profiler
```

Where: `sample_profiler` is the profiler created.

<b>Exit Status</b> 0	command executed successfully
1	error in executing the command

**See Also** [delete-profiler\(1\)](#)

- Name** create-resource-adapter-config – creates the configuration information in `domain.xml` for the connector module
- Synopsis** **create-resource-adapter-config** `—user` *admin\_user* [`—passwordfile` *filename*] [`—host` *host\_name*] [`—port` *port\_number*] [`—secure|—s`] [`—terse=false`] [`—echo=false`] [`—interactive=true`] [`—help`] [`—threadpoolid` *threadpool*] [`—property` (*property name=value*)[:*name=value*]\*] *raname*
- Description** Creates configuration information for the connector module. This command can be executed prior to deploying a resource adapter, so that the configuration information is available at the time of deployment, or after deployment. If the resource adapter is created after deployment, the resource adapter is started. You must first create a threadpool, using the `create-threadpool` command, and then identify that threadpool value as the ID in the `—threadpoolid` option.
- Options**
- `—u` `—user` The authorized domain application server administrative username.
  - `—w` `—password` The `—password` option is deprecated. Use `—passwordfile` instead.
  - `—passwordfile` This option replaces the `—password` option. Using the `—password` option on the command line or through the environment is deprecated. The `—passwordfile` option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the `AS_ADMIN_` prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: `AS_ADMIN_PASSWORD=password`, where *password* is the actual administrator password. Other passwords that can be specified include `AS_ADMIN_MAPPEDPASSWORD`, `AS_ADMIN_USERPASSWORD`, `AS_ADMIN_SAVEDMASTERPASSWORD`, `AS_ADMIN_MQPASSWORD`, `AS_ADMIN_ALIASPASSWORD`, and so on.
  - `—H` `—host` The machine name where the domain application server is running. The default value is `localhost`.
  - `—p` `—port` The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
  - `—s` `—secure` If set to true, uses SSL/TLS to communicate with the domain application server.
  - `—t` `—terse` Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.

---

<code>-e</code>	<code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code>	<code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code>	<code>—help</code>	Displays the help text for the command.
<code>—target</code>		This option has been deprecated.
<code>—threadpoolid</code>		The threadpool ID from which the work manager gets the thread.
<code>—property</code>		This option specifies the configuration properties of the resource adapter java bean.
<b>Operands</b>	<i>raname</i>	This operand is the value kept in the <code>resource-adapter-name</code> in the <code>domain.xml</code> file.
<b>Examples</b>	<p><b>EXAMPLE 1</b> Using <code>create-resource-adapter-config</code></p> <pre>asadmin&gt; create-resource-adapter-config u--user u1 --passwordfile pfile1 ra1</pre> <p>Command <code>create-resource-adapter-config</code> executed successfully</p>	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>See Also</b>	<a href="#">create-threadpool(1)</a> , <a href="#">delete-resource-adapter-config(1)</a>	

**Name** create-resource-ref – creates a reference to a resource

**Synopsis** **create-resource-ref** **—user** *admin\_user* [**—passwordfile** *filename*] [**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**—s**] [**—terse**=*false*] [**—echo**=*false*] [**—interactive**=*true*] [**—help**] [**—target** *target*] [**—enabled**=*true*] *reference\_name*

**Description** The `create-resource-ref` command creates a reference from a cluster or an unclustered server instance to a previously created resource (for example, a JDBC resource created using the `create-jdbc-resource` command). This effectively results in the resource being made available in the JNDI tree of the targeted instance or cluster.

The target instance or instances making up the cluster need not be running or available for this command to succeed. If one or more instances are not available, they will receive the new resource the next time they start.

This command is supported in remote mode only.

<b>Options</b> <b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>—s</b> <b>—secure</b>	If set to <code>true</code> , uses SSL/TLS to communicate with the domain application server.

---

<code>-t</code> <code>--terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>--echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>--interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>--help</code>	Displays the help text for the command.
<code>--target</code>	Specifies the target for which you are creating the resource reference. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, which creates the resource reference for the default server instance <code>server</code> and is the default value</li> <li>▪ <code>cluster_name</code>, which creates the resource reference for every server instance in the cluster</li> <li>▪ <code>instance_name</code>, which creates the resource reference for the named unclustered server instance</li> </ul>
<code>--enabled</code>	Indicates whether the resource should be enabled. This value will take effect only if the resource is enabled at the global level. The default is <code>true</code> .

**Operands** *reference\_name* The name or JNDI name of the resource.

**Examples** EXAMPLE 1 Using the `create-resource-ref` command

The following command creates a reference to the JMS destination resource `jms/Topic` on the cluster `Cluster1`.

```
asadmin> create-resource-ref --user admin
--passwordfile passwords.txt --target Cluster1 jms/Topic
Command create-resource-ref executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [delete-resource-ref\(1\)](#), [list-resource-refs\(1\)](#)

**Name** create-ssl – creates and configures the SSL element in the selected HTTP listener, IIOP listener, or IIOP service

**Synopsis** **create-ssl** **—user** *admin\_user* [**—passwordfile** *filename*] [**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**-s**] [**—terse**=*false*] [**—echo**=*false*] [**—interactive**=*true*] [**—help**] [**—target** *target*] **—type** *listener\_or\_service\_type* **—certname** *cert\_name* [**—ssl2enabled**=*false*] [**—ssl2ciphers** *ssl2ciphers*] [**—ssl3enabled**=*true*] [**—tlseabled**=*true*] [**—ssl3tlsciphers** *ssl3tlsciphers*] [**—tlsrollbackenabled**=*true*] [**—clientauthenabled**=*false*] [*listener\_id*]

**Description** Creates and configures the SSL element in the selected HTTP listener, IIOP listener, or IIOP service in order to enable secure communication on that listener/service.

This command is supported in remote mode only.

**Options** If an option has a short option name, then the short option precedes the long option name. Short options have one dash whereas long options have two dashes.

<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.

<code>-t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target to which you are deploying. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, the server in which the <code>iiop-service</code> or <code>listener</code> is to be configured for SSL.</li> <li>▪ <code>config</code>, the configuration that contains the <code>listener</code> or <code>iiop-service</code> for which SSL is to be configured.</li> <li>▪ <code>cluster</code>, the cluster in which the <code>listener</code> or <code>iiop-service</code> is to be configured for SSL. All the server instances in the cluster will get the SSL configuration for the respective <code>listener</code> or <code>iiop-service</code>.</li> <li>▪ <code>instance</code>, the instance in which the <code>listener</code> or <code>iiop-service</code> is to be configured for SSL.</li> </ul>

The following optional attribute name/value pairs are available:

Property	Definition
<code>type</code>	The type of service or listener for which the SSL is created. The type can be <code>http-listener</code> , <code>iiop-listener</code> , or <code>iiop-service</code> .
<code>certname</code>	The nickname of the server certificate in the certificate database or the PKCS#11 token. The format of the name in the certificate is <code>tokenname:nickname</code> . For this property, the <code>tokenname</code> is optional.

Property	Definition
ssl2enabled	Set this property to <i>true</i> to enable SSL2. The default value is <i>false</i> . If both SSL2 and SSL3 are enabled for a virtual server, the server tries SSL3 encryption first. In the event SSL3 encryption fails, the server then tries SSL2 encryption.
ssl2ciphers	A comma-separated list of the SSL2 ciphers to be used. Use the prefix + to enable or – to disable a particular cipher. Allowed values are: <i>rc4</i> , <i>rc4export</i> , <i>rc2</i> , <i>rc2export</i> , <i>idea</i> , <i>des</i> , and <i>desede3</i> . If no value is specified, all supported ciphers are assumed to be enabled.
ssl3enabled	Set this property to <i>false</i> to disable SSL3. The default value is <i>true</i> . If both SSL2 and SSL3 are enabled for a virtual server, the server tries SSL3 encryption first. In the event SSL3 encryption fails, the server then tries SSL2 encryption.
tlseabled	Set this property to <i>false</i> to disable TLS. The default value is <i>true</i> . It is good practice to enable TLS, which is a more secure version of SSL.
ssl3tlsciphers	A comma-separated list of the SSL3 and/or TLS ciphers to be used. Use the prefix + to enable or – to disable a particular cipher. Allowed SSL3 values are <i>rsa_rc4_128_md5</i> , <i>rsa3des_sha</i> , <i>rsa_des_sha</i> , <i>rsa_rc4_40_md5</i> , <i>rsa_rc2_40_md5</i> , and <i>rsa_null_md5</i> . Allowed TLS values are <i>rsa_des_56_sha</i> and <i>rsa_rc4_56_sha</i> . If no value is specified, all supported ciphers are assumed to be enabled.



Property	Definition
tlsrollbackenabled	Set to <i>true</i> (default) to enable TLS rollback. TLS rollback should be enabled for Microsoft Internet Explorer 5.0 and 5.5. This option is only valid in the Enterprise Edition. This option is only valid when <code>tlsenabled=true</code> .
clientauthenabled	Set to <i>true</i> if you want SSL3 client authentication performed on every request independent of ACL-based access control. Default value is <i>false</i> .

**Operands** *listener\_id*

The ID of the listener for which the SSL element is to be created. The *listener\_id* is not required if the `--type` is *iiop-service*.

**Examples** EXAMPLE 1 Using create-ssl

The following example shows how to create an SSL element for an HTTP listener named *http-listener-1*.

```
asadmin> create-ssl --user admin --host fuyako --port 7070
--passwordfile adminpassword.txt --type http-listener --certname sampleCert http-listener-1
Created SSL in HTTP Listener
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [delete-ssl\(1\)](#)

---

<b>Name</b>	create-system-properties – adds or updates one or more system properties of the domain, configuration, cluster, or server instance
<b>Synopsis</b>	<b>create-system-properties</b> <code>—user</code> <i>admin_user</i> [ <code>—passwordfile</code> <i>filename</i> ] [ <code>—host</code> <i>host_name</i> ] [ <code>—port</code> <i>port_number</i> ] [ <code>—secure</code>   <code>—s</code> ] [ <code>—terse</code> = <i>false</i> ] [ <code>—echo</code> = <i>false</i> ] [ <code>—interactive</code> = <i>true</i> ] [ <code>—help</code> ] [ <code>—target</code> <i>target_name</i> ] [ <i>name=value</i> ][: <i>name=value</i> ]*]
<b>Description</b>	Shared or clustered server instances will often need to override attributes defined in their referenced configuration. Any configuration attribute in a server instance can be overridden through a system property of the corresponding name. This command adds or updates the system properties of a domain, configuration, cluster, or server instance.
<b>Options</b>	<p><code>—u</code> <code>—user</code> The authorized domain application server administrative username.</p> <p><code>—w</code> <code>—password</code> The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.</p> <p><code>—passwordfile</code> This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</p> <p><code>—H</code> <code>—host</code> The machine name where the domain application server is running. The default value is <code>localhost</code>.</p> <p><code>—p</code> <code>—port</code> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><code>—s</code> <code>—secure</code> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><code>—t</code> <code>—terse</code> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p>

<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target on which you are creating the system properties. The valid targets for this command are instance, cluster, configuration, 'domain,' and 'server.' Server is the default option.

**Operands** *name=value* The name value pairs (separated by the ":" character) of the system properties to add to the specified target. If any of the system properties were previously defined, it will be updated with the newly specified value.

**Examples** EXAMPLE 1 Using create-system-properties

```
asadmin> create-system-properties --user admin --passwordfile password.txt
--host localhost --port 4849 --target mycluster http-listener-port=1088
Command create-system-properties executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [delete-system-property\(1\)](#), [list-system-properties\(1\)](#)

**Name** create-threadpool – adds a threadpool

**Synopsis** **create-threadpool** `—user` *admin\_user* [`—passwordfile` *filename*] [`—host` *host\_name*] [`—port` *port\_number*] [`—secure`|`—s`] [`—terse=false`] [`—echo=false`] [`—interactive=true`] [`—help`] [`—target` *target\_name*] [`—maxthreadpoolsize` *max\_thread\_pool\_size*] [`—minthreadpoolsize` *min\_thread\_pool\_size*] [`—idletimeout` *idle\_thread\_timeout\_in\_seconds*] [`—workqueues` *number\_work\_queues*] {*threadpool\_id*}

**Description** Creates a thread-pool with the specified name. You can specify maximum and minimum number of threads in the pool, the number of work queues, and the idle timeout of a thread. The created thread pool can be used for servicing IOP requests and for resource adapters to service work management requests. Please note that a created thread pool can be used in multiple resource adapters. This command is supported in remote mode only.

<b>Options</b> <code>—u</code> <code>—user</code>	The authorized domain application server administrative username.
<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>—H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>—p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>—s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.

<code>-t</code> <code>--terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>--echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>--interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>--help</code>	Displays the help text for the command.
<code>--target</code>	In Enterprise Edition, specifies the target on which you are creating the threadpool. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, which creates the listener for the default server instance <code>server</code> and is the default value</li> <li>▪ <code>configuration_name</code>, which creates the listener for the named configuration</li> <li>▪ <code>cluster_name</code>, which creates the listener for every server instance in the cluster</li> <li>▪ <code>instance_name</code>, which creates the listener for a particular server instance</li> </ul>
<code>--maxthreadpoolsize</code>	maximum number of threads in the threadpool servicing requests in this queue. This is the upper bound on the number of threads that exist in the threadpool.
<code>--minthreadpoolsize</code>	minimum number of threads in the threadpool servicing requests in this queue. These are created up front when the threadpool is instantiated.
<code>--idletimeout</code>	idle threads are removed from the pool after this time.
<code>--workqueues</code>	identifies the total number of work queues serviced by this threadpool.
<b>Operands</b> <code>threadpool_id</code>	an ID for the work queue; for example, <code>thread-pool-1</code> , <code>thread-pool-2</code> , etc.
<b>Examples</b>	<p><b>EXAMPLE 1</b> Using <code>create-threadpool</code></p> <pre>asadmin&gt; create-threadpool --user admin1 --passwordfile password.txt --maxthreadpoolsize 100 --minthreadpoolsize 20 --idletimeout 2 --workqueues 100 threadpool-1 Command create-threadpool executed successfully</pre>
<b>Exit Status</b>	<p>0 command executed successfully</p> <p>1 error in executing the command</p>

**See Also** [delete-threadpool\(1\)](#), [list-threadpools\(1\)](#)

**Name** create-virtual-server – creates the named virtual server

**Synopsis** **create-virtual-server** **—user** *admin\_user* [**—passwordfile** *filename*]  
 [**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**—s**] [**—terse**=*false*]  
 [**—echo**=*false*] [**—interactive**=*true*] [**—help**] [**—target** *server*] **—hosts** *hosts*  
 [**—httplisteners** *http\_listeners*] [**—defaultwebmodule** *default\_web\_module*]  
 [**—state** *on*] [**—logfile** *log\_file*] [**—property** (*name=value*)[:*name=value*]\*]  
*virtual\_server\_id*

**Description** The create-virtual-server command creates the named virtual server. Virtualization in the Application Server allows multiple URL domains to be served by a single HTTP server process that is listening on multiple host addresses. If the application is available at two virtual servers, they still share the same physical resource pools.

This command is supported in remote mode only.

<b>Options</b> <b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.

<code>-t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target for which you are creating the virtual server. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, which creates the virtual server for the default server instance <code>server</code> and is the default value</li> <li>▪ <code>configuration_name</code>, which creates the virtual server for the named configuration</li> <li>▪ <code>cluster_name</code>, which creates the virtual server for every server instance in the cluster</li> <li>▪ <code>instance_name</code>, which creates the virtual server for a particular server instance</li> </ul>
<code>—hosts</code>	A comma-separated (,) list of values allowed in the host request header to select the current virtual server. Each virtual server that is configured to the same connection group must have a unique hosts value for that group.
<code>—httplisteners</code>	A comma-separated (,) list of HTTP listener IDs. Required only for a virtual server that is not the default virtual server.
<code>—defaultwebmodule</code>	The standalone web module associated with this virtual server by default.
<code>—state</code>	Determines whether a virtual server is active (on) or inactive (off or disabled). Default is active (on). When inactive, the virtual server does not service requests.
<code>—logfile</code>	Name of the file where log entries for this virtual server are to be written. By default, this is the server log.
<code>—property</code>	Optional attribute name/value pairs for configuring the virtual server. The following properties are available:

Property	Definition
<code>docroot</code>	Absolute path to root document directory for server.



Property	Definition
accesslog	Absolute path to server access logs.
sso-enabled	If false, single sign-on is disabled for this virtual server, and users must authenticate separately to every application on the virtual server. Single sign-on across applications on the Application Server is supported by servlets and JSP pages. This feature allows multiple applications that require the same user sign-on information to share this information, rather than have the user sign on separately for each application. Default is true.
sso-max-inactive-seconds	Specifies the number of seconds after which a user's single sign-on record becomes eligible for purging if no client activity is received. Since single sign-on applies across several applications on the same virtual server, access to any of the applications keeps the single sign-on record active. Default is 300 seconds (5 minutes). Higher values provide longer single sign-on persistence for users at the expense of more memory use on the server.
sso-reap-interval-seconds	Specifies the number of seconds between purges of expired single sign-on records. Default is 60.

**Operands** *virtual\_server\_id* Identifies the unique ID for the virtual server to be created. This ID cannot begin with a number.

**Examples** EXAMPLE 1 Using the create-virtual-server command

The following command creates a virtual server named sampleServer:

```
asadmin> create-virtual-server --user admin1
--passwordfile passwords.txt --hosts pigeon,localhost sampleServer
Command create-virtual-server executed successfully.
```

**Exit Status** 0 command executed successfully

1

error in executing the command

**See Also** [delete-virtual-server\(1\)](#), [list-virtual-servers\(1\)](#), [create-http-listener\(1\)](#)

<b>Name</b>	delete-admin-object – removes the administered object with the specified JNDI name	
<b>Synopsis</b>	<b>delete-admin-object</b> —user <i>admin_user</i> [—passwordfile <i>filename</i> ] [—host <i>host_name</i> ] [—port <i>port_number</i> ] [—secure —s] [—terse= <i>false</i> ] [—echo= <i>false</i> ] [—interactive= <i>true</i> ] [—help] [—target <i>target</i> ] <i>jndi_name</i>	
<b>Description</b>	This command removes the administered object with the specified JNDI name.	
<b>Options</b>	—u —user	The authorized domain application server administrative username.
	—w —password	The —password option is deprecated. Use —passwordfile instead.
	—passwordfile	This option replaces the —password option. Using the —password option on the command line or through the environment is deprecated. The —passwordfile option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
	—H —host	The machine name where the domain application server is running. The default value is localhost.
	—p —port	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	—s —secure	If set to true, uses SSL/TLS to communicate with the domain application server.
	—t —terse	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	—e —echo	Setting to true will echo the command line statement on the standard output. Default is false.
	—I —interactive	If set to true (default), only the required password options are prompted.
	—h —help	Displays the help text for the command.

**—target** This is the name of the target upon which the command is operating. The valid targets for this command are instance, cluster, 'domain,' and 'server.' Server is the default option. This command is used by the Enterprise Edition only.

**Operands** *jndi\_name* JNDI name of the administered object to be deleted.

**Examples** **EXAMPLE 1** Using delete-admin-object

The example listed in the add-admin-object command should be executed before attempting to execute this example:

```
asadmin> delete-admin-object --user admin --password admin123
--target instance1 jms/samplequeue
Command delete-admin-object executed successfully
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-admin-object\(1\)](#), [list-admin-objects\(1\)](#)

- Name** delete-application-ref – removes a reference to an application
- Synopsis** **delete-application-ref** **—user** *admin\_user* [**—passwordfile** *filename*]  
 [**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**—s**] [**—terse**=*false*]  
 [**—echo**=*false*] [**—interactive**=*true*] [**—help**] [**—target** *target*] [**—cascade**=*false*]  
*reference\_name*
- Description** The delete-application-ref command removes a reference from a cluster or an unclustered server instance to an application. This effectively results in the application element being undeployed and no longer available on the targeted instance or cluster.
- The target instance or instances making up the cluster need not be running or available for this command to succeed. If one or more instances are not available, they will no longer load the application the next time they start.
- Removal of the reference does not result in removal of the application from the domain. The bits are removed only by the undeploy command.
- This command is supported in remote mode only.
- Options**
- |                            |  |
|----------------------------|--|
| <b>—u</b> <b>—user</b>     | The authorized domain application server administrative username.  |
| <b>—w</b> <b>—password</b> | The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.   |
| <b>—passwordfile</b>       | This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on. |
| <b>—H</b> <b>—host</b>     | The machine name where the domain application server is running. The default value is localhost.   |
| <b>—p</b> <b>—port</b>     | The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.  |

---

<code>-s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>-t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	Specifies the target from which you are removing the application reference. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, which removes the application reference from the default server instance <code>server</code> and is the default value</li> <li>▪ <code>cluster_name</code>, which removes the application reference from every server instance in the cluster</li> <li>▪ <code>instance_name</code>, which removes the application reference from the named unclustered server instance</li> </ul>
<code>—cascade</code>	This option, when set to true, will ensure the removal of the connector from remote instances. The default is false.

**Operands** *reference\_name* The name of the application or module, which can be a J2EE application module, Web module, EJB module, connector module, application client module, or lifecycle module.

**Examples** EXAMPLE 1 Using the delete-application-ref command

The following command removes a reference to the Web module `MyWebApp` from the unclustered server instance `NewServer`.

```
asadmin> delete-application-ref --user admin2
--passwordfile passwords.txt --target NewServer MyWebApp
Command delete-application-ref executed successfully.
```

**Exit Status**

0	command executed successfully
1	error in executing the command

**See Also** [create-application-ref\(1\)](#), [list-application-refs\(1\)](#), [undeploy\(1\)](#)

---

<b>Name</b>	create-audit-module – removes the named audit-module
<b>Synopsis</b>	<b>delete-audit-module</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—target</b> <i>target_name</i> ] [ <i>audit_module_name</i> ]
<b>Description</b>	Removes the named audit module. This command is supported in remote mode only.
<b>Options</b>	
<b>-u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>-w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
<b>-H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>-p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>-s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
<b>-t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<b>-e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
<b>-I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.
<b>-h</b> <b>—help</b>	Displays the help text for the command.

**—target** In Enterprise Edition, specifies the target on which you are deleting the audit module. Valid values are

- `server`, which creates the listener for the default server instance `server` and is the default value
- `configuration_name`, which creates the listener for the named configuration
- `cluster_name`, which creates the listener for every server instance in the cluster
- `instance_name`, which creates the listener for a particular server instance

**Operands** `audit_module_name` name of the audit module to be deleted.

**Examples** EXAMPLE 1 Using `delete-audit-module`

```
asadmin> delete-audit-module --user admin1
--passwordfile password.txt --host pigeon --port 5001 sampleAuditModule
Command delete-audit-module executed successfully
```

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [create-audit-module\(1\)](#), [list-audit-modules\(1\)](#)



---

<b>Name</b>	delete-auth-realm – removes the named authentication realm	
<b>Synopsis</b>	<b>delete-auth-realm</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—target</b> <i>target_name</i> ] { <i>auth_realm-name</i> }	
<b>Description</b>	Removes the named authorized realm. This command is supported in remote mode only.	
<b>Options</b>	<b>-u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>-w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
	<b>-H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
	<b>-p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>-s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>-t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>-e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
	<b>-I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.
	<b>-h</b> <b>—help</b>	Displays the help text for the command.

**—target** In Enterprise Edition, specifies the target on which you are deleting the authentication realm. Valid values are

- `server`, which creates the listener for the default server instance `server` and is the default value
- `configuration_name`, which creates the listener for the named configuration
- `cluster_name`, which creates the listener for every server instance in the cluster
- `instance_name`, which creates the listener for a particular server instance

**Operands** `auth_realm_name` name of this realm.

**Examples** EXAMPLE 1 Using `delete-auth-realm`

```
asadmin> delete-auth-realm --user admin1 --passwordfile password.txt
--host pigeon --port 5001 db
Command delete-auth-realm executed successfully
```

Where `db` is the authentication realm deleted.

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-auth-realm\(1\)](#), [list-auth-realms\(1\)](#)

**Name** delete-cluster – deletes a cluster

**Synopsis** **delete-cluster** **—user** *admin\_user* [**—passwordfile** *filename*] [**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**-s**] [**—terse**=*false*] [**—echo**=*false*] [**—interactive**=*true*] [**—help**] *cluster\_name*

**Description** The `delete-cluster` command deletes a cluster. A cluster can be deleted only if it contains no server instances. Stop and delete all server instances in the cluster before deleting the cluster.

If a standalone cluster is deleted (that is, the cluster's configuration name is *cluster\_name*-config and no other clusters or unclustered instances refer to this configuration), then its standalone configuration is automatically deleted.

This command is supported in remote mode only.

<b>Options</b> <b>-u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>-w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
<b>-H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>-p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>-s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
<b>-t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.

<code>-e</code>	<code>--echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code>	<code>--interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code>	<code>--help</code>	Displays the help text for the command.

**Operands** *cluster\_name* The name of the cluster to be deleted.

**Examples** EXAMPLE 1 Using the delete-cluster command

The following command deletes the cluster named MyCluster. The same command also automatically deletes the configuration named MyCluster-config.

```
asadmin> delete-cluster --user admin1
--passwordfile passwords.txt MyCluster
Command delete-cluster executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-cluster\(1\)](#), [list-clusters\(1\)](#), [start-cluster\(1\)](#), [stop-cluster\(1\)](#), [stop-instance\(1\)](#)

<b>Name</b>	delete-config – deletes an existing configuration	
<b>Synopsis</b>	<b>delete-config</b> <i>—user admin_user</i> [ <i>—passwordfile filename</i> ] [ <i>—host host_name</i> ] [ <i>—port port_number</i> ] [ <i>—secure -s</i> ] [ <i>—terse=false</i> ] [ <i>—echo=false</i> ] [ <i>—interactive=true</i> ] [ <i>—help</i> ] <i>configuration_name</i>	
<b>Description</b>	Use the delete—config command to delete an existing configuration in the domain.xml file. You can delete a configuration only if the configuration has no server instances or clusters referring to it. A standalone configuration is automatically deleted when the sever instance or cluster referring to it is deleted. You cannot delete the default-config configuration that is used to create new standalone configurations.	
<b>Options</b>	<i>—u—user</i>	The authorized domain application server administrative username.
	<i>—w—password</i>	The <i>—password</i> option is deprecated. Use <i>—passwordfile</i> instead.
	<i>—passwordfile</i>	This option replaces the <i>—password</i> option. Using the <i>—password</i> option on the command line or through the environment is deprecated. The <i>—passwordfile</i> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
	<i>—H—host</i>	The machine name where the domain application server is running. The default value is localhost.
	<i>—p—port</i>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<i>—s—secure</i>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<i>—t—terse</i>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<i>—e—echo</i>	Setting to true will echo the command line statement on the standard output. Default is false.

**-I** **—interactive** If set to true (default), only the required password options are prompted.

**-h** **—help** Displays the help text for the command.

**Operands** *configuration\_name* the name of the configuration you are deleting.

**Examples** **EXAMPLE 1** Using the delete-config command

```
asadmin> delete-config --user admin --passwordfile passwords.txt my-config
Command delete-config executed successfully.
```

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [copy-config\(1\)](#), [list-configs\(1\)](#)

---

**Name** delete-connection—group – deletes the connection group

**Synopsis** **delete-connection-group**  
--user *user\_name* --password *password* --host *hostname* --port *admin\_port\_number*  
--instance *instance\_name* --httplistener *http\_listener\_ID* *connection\_group\_ID*

**Description** Deletes the connection group for the named connection group ID associated with the named server instance..

**Options** --user identifies the user name associated with the named instance.  
--password identifies the password associated with the user name.  
--host identifies the host name for the machine.  
--port identifies the administrator port number associated with the hostname.  
--instance identifies the name of the instance associated with the JVM option to be created.  
--httplistener a unique identifier for the HTTP listener.  
*connection\_group\_ID* a unique identifier for the connection group.

**Examples** asadmin% **delete-connection-group**

**Interface** unknown

**Equivalent**

**See Also** [create-connection-group\(1\)](#) [list-connection-groups\(1\)](#)

**Name** delete-connector-connection-pool – removes the specified connector connection pool

**Synopsis** **delete-connector-connection-pool** `—user` *admin\_user* [`—passwordfile` *filename*] [`—host` *host\_name*] [`—port` *port\_number*] [`—secure`|`-s`] [`—terse`=*false*] [`—echo`=*false*] [`—interactive`=*true*] [`—help`] [`—cascade`=*false*] *connector\_connection\_pool\_name*

**Description** Removes the specified connector connection pool. This command is supported in remote mode only.

**Options**

<code>-u</code> <code>—user</code>	The authorized domain application server administrative username.
<code>-w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>-H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>-p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>-s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>-t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.



---

<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—cascade</code>	When set to true, it deletes all connector resources associated with the pool that is named as operand, apart from the pool itself. When set to false, the deletion of pool fails if any resources are associated with the pool. The resource must be deleted explicitly or the option must be set to true. The default setting is false.

**Operands** `connector_connection_pool_name` The name of the connection pool to be removed.

**Examples** **EXAMPLE 1** Using the delete-connector-connection-pool command

```
asadmin> delete-connector-connection-pool --cascade=false jms/qConnPool
Command delete-connector-connection-pool executed successfully
```

Where `.jms/qConnPool` is the connector connection pool that is removed.

**Exit Status**

0	command executed successfully
1	error in executing the command

**See Also** [create-connector-connection-pool\(1\)](#), [list-connector-connection-pools\(1\)](#)

---

<b>Name</b>	delete-connector-resource – removes the connector resource with the specified JNDI name
<b>Synopsis</b>	<b>delete-connector-resource</b> <code>—user</code> <i>admin_user</i> [ <code>—passwordfile</code> <i>filename</i> ] <code>[—host</code> <i>host_name</i> ] [ <code>—port</code> <i>port_number</i> ] [ <code>—secure —s</code> ] [ <code>—terse=false</code> ] <code>[—echo=false</code> ] [ <code>—interactive=true</code> ] [ <code>—help</code> ] [ <code>—target</code> <i>target</i> ] <i>jndi_name</i>
<b>Description</b>	This <code>delete-connector-resource</code> command removes the connector resource with the JNDI name, which is specified by the <i>jndi_name</i> operand.
<b>Options</b>	<p><code>—u</code> <code>—user</code> The authorized domain application server administrative username.</p> <p><code>—w</code> <code>—password</code> The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.</p> <p><code>—passwordfile</code> This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</p> <p><code>—H</code> <code>—host</code> The machine name where the domain application server is running. The default value is <code>localhost</code>.</p> <p><code>—p</code> <code>—port</code> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><code>—s</code> <code>—secure</code> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><code>—t</code> <code>—terse</code> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p> <p><code>—e</code> <code>—echo</code> Setting to true will echo the command line statement on the standard output. Default is false.</p> <p><code>—I</code> <code>—interactive</code> If set to true (default), only the required password options are prompted.</p>

---

<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	valid in Enterprise Edition only, specifies the target to which you are deploying. Valid values are 'server,' 'domain,' cluster, instance.
<code>—poolname</code>	The name of the connection pool. When two or more resource elements point to the same connection pool element, they use the same pool connections at runtime.
<code>—enabled</code>	This option determines whether the resource is enabled at runtime. The default value is true.
<code>—description</code>	Text providing descriptive details about the connector resource.

**Operands** *jndi\_name* the JNDI name of this connector resource.

**Examples** EXAMPLE 1 Using the delete-connector-resource command

```
asadmin> delete-connector-resource --target server
jms/qConnFactory --passwordfile file1
Command delete-connector-resource executed successfully
```

Where `jms/qConnFactory` is the connector resource that is removed.

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-connector-resource\(1\)](#), [list-connector-resources\(1\)](#)

**Name** delete-connector-security-map – deletes a security map for the specified connector connection pool

**Synopsis** **delete-connector-security-map** **—user** *admin\_user* [**—passwordfile** *filename*] [**—host** *host\_name*] [**—port** *port\_number*] [**—secure|-s**] [**—terse=false**] [**—echo=false**] [**—interactive=true**] [**—help**] **—poolname** *connector\_connection\_pool\_name security\_map\_name*

**Description** Use this command to delete a security map for the specified connector connection pool.

For this command to succeed, you must have first created a connector connection pool using the `create-connector-connection-pool` command.

The enterprise information system (EIS) is any system that holds the information. It can be a mainframe, a messaging system, a database system, or an application.

This command is supported in remote mode only.

**Options** If an option has a short option name, then the short option precedes the long option name. Short options have one dash whereas long options have two dashes.

<b>—u—user</b>	The authorized domain application server administrative username.
<b>—w—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<b>—H—host</b>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
<b>—p—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.

---

<code>-s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>-t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	This option is deprecated in this release.
<code>—poolname</code>	This property specifies the name of the connector connection pool to which the security map that is to be deleted belongs.

**Operands** *security\_map\_name* name of the security map to be deleted.

**Examples** EXAMPLE 1 Using `delete-connector-security-map`

It is assumed that the connector pool has already been created using the `create-connector-pool` command.

```
asadmin> delete-connector-security-map --user admin
--passwordfile pwd_file.txt --poolname connector-pool1 securityMap1
Command delete-connector-security-map executed successfully
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-connector-security-map\(1\)](#), [list-connector-security-maps\(1\)](#), [update-connector-security-map\(1\)](#)

**Name** delete-custom-resource – removes a custom resource

**Synopsis** **delete-custom-resource** **—user** *admin\_user* [**—passwordfile** *filename*]  
[**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**—s**] [**—terse**=*false*]  
[**—echo**=*false*] [**—interactive**=*true*] [**—help**] [**—target** *target*] *jndi\_name*

**Description** The delete-custom-resource command removes a custom resource. This command is supported in remote mode only.

**Options**

<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
<b>—I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.

---

<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>--target</code>	valid in Enterprise Edition only, this command, specifies the location of the custom resources that you are deleting. Valid values are 'server,' ,domain,' cluster, and instance. The default is server.

**Operands** *jndi\_name* the JNDI name of this resource.

**Examples** EXAMPLE 1 Using the delete-custom-resource command

```
asadmin> delete-custom-resource --target plm jndi_name_test --passwordfile file1
```

```
Command delete-custom-resource executed correctly.
```

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [create-custom-resource\(1\)](#), [list-custom-resources\(1\)](#)

**Name** delete-domain – deletes the given domain

**Synopsis** **delete-domain** [**--domaindir** *install\_dir/domains*] [**--terse=false**] [**--echo=false**]  
[**--interactive=true**] *domain\_name*

**Description** Use the delete-domain command to delete the named domain. The domain must already exist and must be stopped.

This command is supported in local mode only.

**Options**

<b>--domaindir</b>	The directory where the domain to be deleted is located. If specified, the path must be accessible in the filesystem. If not specified, the domain in the default <i>install_dir/domains</i> directory is deleted.
<b>-t --terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<b>-e --echo</b>	Setting to true will echo the command line statement on to the standard output. Default is false.
<b>-I --interactive</b>	If set to true (default), only the required options are prompted.

**Operands** *domain\_name* The unique name of the domain you wish to delete.

**Examples** EXAMPLE 1 Using the delete-domain command

```
asadmin> delete-domain --domaindir /export/domains sampleDomain
deleted domain sampleDomain successfully
```

Where: the sampleDomain domain is deleted from the /export/domains directory.

**Exit Status**

0	command executed successfully
1	error in executing the command

**See Also** [create-domain\(1\)](#), [start-domain\(1\)](#), [stop-domain\(1\)](#), [list-domains\(1\)](#)



**Name** delete-file-user – removes the named file user

**Synopsis** **delete-file-user** **—user** *admin\_user* [**—passwordfile** *filename*] [**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**-s**] [**—terse**=*false*] [**—echo**=*false*] [**—interactive**=*true*] [**—help**] [**—target** *target*] *username*

**Description** Deletes the entry in the keyfile with the specified username.

<b>Options</b> <b>-u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>-w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
<b>-H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>-p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>-s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
<b>-t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<b>-e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
<b>-I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.
<b>-h</b> <b>—help</b>	Displays the help text for the command.

**—target** This is used for Enterprise Edition only. This is the name of the target on which the command operates. The valid targets are config, instance, cluster, or “server.” By default, the target is the ‘Server.’

**Operands** *username* This is the name of file user to be deleted.

**Examples** EXAMPLE 1 Using the delete-file-user command

It is assumed that an authority realm has already been created using the create-auth-realm command.

```
asadmin> delete-file-user --user admin1 --password adminadmin1
--host pigeon --port 5001 --username admin1
Command delete-file-user executed successfully
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-file-user\(1\)](#), [list-file-users\(1\)](#), [update-file-user\(1\)](#), [list-file-groups\(1\)](#)

<b>Name</b>	delete-http-health-checker – deletes the health-checker for a specified load balancer configuration	
<b>Synopsis</b>	<b>delete-http-health-checker</b> <code>—user</code> <i>admin_user</i> [ <code>—passwordfile</code> <i>filename</i> ] [ <code>—host</code> <i>host_name</i> ] [ <code>—port</code> <i>port_number</i> ] [ <code>—secure</code>   <code>-s</code> ] [ <code>—terse</code> = <i>false</i> ] [ <code>—echo</code> = <i>false</i> ] [ <code>—interactive</code> = <i>true</i> ] [ <code>—help</code> ] <code>—config</code> <i>config_name</i> <i>target</i>	
<b>Description</b>	This command deletes the health checker from a load balancer configuration.	
<b>Options</b>	<code>—u</code> <code>—user</code>	The authorized domain application server administrative username.
	<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
	<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
	<code>—H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
	<code>—p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<code>—s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<code>—t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<code>—e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
	<code>—I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
	<code>—h</code> <code>—help</code>	Displays the help text for the command.

`--config`

The load balancer configuration from which you delete the health-checker.

**Operands** *target*

Specifies the target from which you are deleting the health checker.

Valid values are:

- *cluster\_name*, which deletes the health checker that was monitoring all instances in the cluster.
- *instance\_name*, which deletes the health checker that was monitoring this standalone instance.

**Examples** **EXAMPLE 1** Using the delete-http-health-checker command

```
asadmin> delete-http-health-checker --user admin
--passwordfile password.txt --config mycluster-http-lb-config mycluster
Command delete-http-health-checker executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-http-health-checker\(1\)](#)

---

<b>Name</b>	delete—http—lb—config – deletes a load balancer configuration	
<b>Synopsis</b>	<b>delete-http-lb-config</b> —user <i>admin_user</i> [—passwordfile <i>filename</i> ] [—host <i>host_name</i> ] [—port <i>port_number</i> ] [—secure —s] [—terse= <i>false</i> ] [—echo= <i>false</i> ] [—interactive= <i>true</i> ] [—help] <i>config_name</i>	
<b>Description</b>	Use the delete-http-lb-config command to delete a load balancer configuration. The load balancer must not reference any clusters or server instances.	
<b>Options</b>	—u —user	The authorized domain application server administrative username.
	—w —password	The —password option is deprecated. Use —passwordfile instead.
	—passwordfile	This option replaces the — password option. Using the —password option on the command line or through the environment is deprecated. The —passwordfile option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
	—H —host	The machine name where the domain application server is running. The default value is localhost.
	—p —port	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	—s —secure	If set to true, uses SSL/TLS to communicate with the domain application server.
	—t —terse	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	—e —echo	Setting to true will echo the command line statement on the standard output. Default is false.
	—I —interactive	If set to true (default), only the required password options are prompted.

`-h` `—help` Displays the help text for the command.

**Operands** *config\_name* The name of the new load balancer configuration to delete. The configuration must not reference any clusters or server instances.

**Examples** EXAMPLE 1 Using the `delete—http—lb—config` command  
`asadmin> delete-http-lb-config --user admin --passwordfile file mylbconfig`  
Command `delete-http-lb-config` executed successfully.

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-http-lb-config\(1\)](#), [list-http-lb-configs\(1\)](#)

---

<b>Name</b>	delete-http-lb-ref – deletes the cluster or server instance from a load balancer configuration	
<b>Synopsis</b>	<b>delete-http-lb-ref</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure —s</b> ] [ <b>—terse=false</b> ] [ <b>—echo=false</b> ] [ <b>—interactive=true</b> ] [ <b>—help</b> ] <b>—config</b> <i>config_name target</i>	
<b>Description</b>	Use the delete-http-lb-ref command to remove a reference to a cluster or server instance from a load balancer configuration. So that you do not interrupt user requests, make sure the standalone server instance or all server instances in the cluster are disabled before you remove them from the load balancer configuration.	
<b>Options</b>	<b>—u—user</b>	The authorized domain application server administrative username.
	<b>—w—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=password</b> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
	<b>—H—host</b>	The machine name where the domain application server is running. The default value is localhost.
	<b>—p—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>—s—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>—t—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>—e—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.

<code>-I</code>	<code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code>	<code>—help</code>	Displays the help text for the command.
<code>—config</code>		Specifies which load balancer configuration to delete cluster and server instance references from.
<b>Operands</b>	<i>target</i>	Specifies which cluster or instance to remove from the load balancer. Valid values are: <ul style="list-style-type: none"><li>▪ <i>cluster_name</i>, which specifies that requests for this cluster will no longer be handled by the load balancer.</li><li>▪ <i>instance_name</i>, which specifies that requests for this standalone instance will no longer be handled by the load balancer.</li></ul>
<b>Examples</b>	<b>EXAMPLE 1</b> Using the delete-http-lb-ref command <pre>asadmin&gt; delete-http-lb-ref --user admin --passwordfile file --config mycluster-http-lb-config cluster2</pre> Command delete-http-lb-ref executed successfully.	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>See Also</b>	<a href="#">create-http-lb-ref(1)</a> <a href="#">disable-http-lb-server(1)</a>	



<b>Name</b>	delete-http-listener – removes an HTTP listener	
<b>Synopsis</b>	<b>delete-http-listener</b> <code>--user</code> <i>admin_user</i> [ <code>--passwordfile</code> <i>filename</i> ] [ <code>--host</code> <i>host_name</i> ] [ <code>--port</code> <i>port_number</i> ] [ <code>--secure -s</code> ] [ <code>--terse=false</code> ] [ <code>--echo=false</code> ] [ <code>--interactive=true</code> ] [ <code>--help</code> ] [ <code>--target server</code> ] <i>listener_id</i>	
<b>Description</b>	The <code>delete-http-listener</code> command removes the specified HTTP listener. This command is supported in remote mode only.	
<b>Options</b>	<code>-u</code> <code>--user</code>	The authorized domain application server administrative username.
	<code>-w</code> <code>--password</code>	The <code>--password</code> option is deprecated. Use <code>--passwordfile</code> instead.
	<code>--passwordfile</code>	This option replaces the <code>--password</code> option. Using the <code>--password</code> option on the command line or through the environment is deprecated. The <code>--passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
	<code>-H</code> <code>--host</code>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
	<code>-p</code> <code>--port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<code>-s</code> <code>--secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<code>-t</code> <code>--terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<code>-e</code> <code>--echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
	<code>-I</code> <code>--interactive</code>	If set to true (default), only the required password options are prompted.

<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target from which you are deleting the HTTP listener. Valid values are <ul style="list-style-type: none"><li>▪ <code>server</code>, which deletes the listener from the default server instance <code>server</code> and is the default value</li><li>▪ <code>configuration_name</code>, which deletes the listener from the named configuration</li><li>▪ <code>cluster_name</code>, which deletes the listener from every server instance in the cluster</li><li>▪ <code>instance_name</code>, which deletes the listener from a particular server instance</li></ul>

**Operands** *listener\_id* The unique identifier for the HTTP listener to be deleted.

**Examples** **EXAMPLE 1** Using the `delete-http-listener` command

The following command deletes the HTTP listener named `sampleListener`:

```
asadmin> delete-http-listener --user admin1
--passwordfile passwords.txt --host pigeon --port 5001 sampleListener
Command delete-http-listener executed successfully.
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [create-http-listener\(1\)](#), [list-http-listeners\(1\)](#)

<b>Name</b>	delete-iiop-listener – removes an IIOP listener	
<b>Synopsis</b>	<b>delete-iiop-listener</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—target server</b> ] <i>listener_id</i>	
<b>Description</b>	The delete-iiop-listener command removes the specified IIOP listener. This command is supported in remote mode only.	
<b>Options</b>	<b>-u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>-w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
	<b>-H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
	<b>-p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>-s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>-t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>-e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
	<b>-I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.

- h**—help Displays the help text for the command.
- target** In Enterprise Edition, specifies the target from which you are deleting the IIOP listener. Valid values are
- `server`, which deletes the listener from the default server instance `server` and is the default value
  - `configuration_name`, which deletes the listener from the named configuration
  - `cluster_name`, which deletes the listener from every server instance in the cluster
  - `instance_name`, which deletes the listener from a particular server instance

**Operands** *listener\_id* The unique identifier for the IIOP listener to be deleted.

**Examples** **EXAMPLE 1** Using the `delete-iiop-listener` command

The following command deletes the IIOP listener named `sample_iiop_listener`:

```
asadmin> delete-iiop-listener --user admin
--passwordfile passwords.txt --host fuyako --port 7070 sample_iiop_listener
Command delete-iiop-listener executed successfully.
```

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [create-iiop-listener\(1\)](#), [list-iiop-listeners\(1\)](#)

---

<b>Name</b>	delete-instance – deletes the instance that is not running	
<b>Synopsis</b>	<b>delete-instance</b> <code>—user</code> <i>admin_user</i> [ <code>—passwordfile</code> <i>filename</i> ] [ <code>—host</code> <i>host_name</i> ] [ <code>—port</code> <i>port_number</i> ] [ <code>—secure</code>   <code>-s</code> ] [ <code>—terse</code> = <i>false</i> ] [ <code>—echo</code> = <i>false</i> ] [ <code>—interactive</code> = <i>true</i> ] [ <code>—help</code> ] <i>instance_name</i>	
<b>Description</b>	Use the <code>delete-instance</code> command to delete the instance that you specify. The <code>delete-instance</code> command can be run both locally and remotely. The user authenticates using the password identified for the administration server. Additionally, the instance must already exist within the domain served by the administration server. Use this command with discretion since it is destructive and there is no undo.	
<b>Options</b>	<code>-u</code> <code>—user</code>	The authorized domain application server administrative username.
	<code>-w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
	<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
	<code>-H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
	<code>-p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<code>-s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<code>-t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.

**-I** **—interactive** If set to true (default), only the required password options are prompted.

**-h** **—help** Displays the help text for the command.

**Operands** *instance\_name* name of the instance to be deleted.

**Examples** **EXAMPLE 1** Using delete-instance in local mode

```
asadmin> delete-instance --user admin1 --passwordfile passwords.txt instance1
Command delete-instance executed successfully
```

Where: instance1 is deleted on the local machine.

**EXAMPLE 2** Using delete-instance in remote mode

```
asadmin> delete-instance --user admin --passwordfile passwords.txt
--host pigeon --port 4849 instance2
Deleted Instance server1 successfully
```

Where: instance2 is deleted on the remote machine.

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [create-instance\(1\)](#), [start-instance\(1\)](#), [stop-instance\(1\)](#)

<b>Name</b>	delete-javamail-resource – removes a JavaMail session resource	
<b>Synopsis</b>	<b>delete-javamail-resource</b> <code>--user</code> <i>admin_user</i> [ <code>--passwordfile</code> <i>filename</i> ] <code>[--host</code> <i>host_name</i> ] [ <code>--port</code> <i>port_number</i> ] [ <code>--secure -s</code> ] [ <code>--terse=false</code> ] <code>[--echo=false]</code> [ <code>--interactive=true</code> ] [ <code>--help</code> ] [ <code>--target</code> <i>target</i> ] <i>jndi_name</i>	
<b>Description</b>	The <code>delete-javamail-resource</code> command removes the specified JavaMail session resource. For Enterprise Edition, make sure to remove all references to this resource before executing this command. This command is supported in remote mode only.	
<b>Options</b>	<code>-u</code> <code>--user</code>	The authorized domain application server administrative username.
	<code>-w</code> <code>--password</code>	The <code>--password</code> option is deprecated. Use <code>--passwordfile</code> instead.
	<code>--passwordfile</code>	This option replaces the <code>--password</code> option. Using the <code>--password</code> option on the command line or through the environment is deprecated. The <code>--passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
	<code>-H</code> <code>--host</code>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
	<code>-p</code> <code>--port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<code>-s</code> <code>--secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<code>-t</code> <code>--terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<code>-e</code> <code>--echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.

<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target from which you are deleting the JavaMail session resource. Valid values are <ul style="list-style-type: none"><li>▪ <code>server</code>, which deletes the resource from the default server instance <code>server</code> and is the default value</li><li>▪ <code>domain</code>, which deletes the resource from the domain</li><li>▪ <code>cluster_name</code>, which deletes the resource from every server instance in the cluster</li><li>▪ <code>instance_name</code>, which deletes the resource from a particular server instance</li></ul>

**Operands** *jndi\_name* The JNDI name of the JavaMail session resource to be deleted.

**Examples** **EXAMPLE 1** Using the `delete-javamail-resource` command

The following command deletes the JavaMail session resource named `mail/MyMailSession`:

```
asadmin> delete-javamail-resource --user admin
--passwordfile passwords.txt --host fuyako --port 7070 mail/MyMailSession
Command delete-javamail-resource executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-javamail-resource\(1\)](#), [list-javamail-resources\(1\)](#)



<b>Name</b>	delete-jdbc-connection-pool – removes the specified JDBC connection pool	
<b>Synopsis</b>	<b>delete-jdbc-connection-pool</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>—s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—cascade</b> = <i>false</i> ] <i>connectionpoolid</i>	
<b>Description</b>	Removes a specified JDBC connection pool that was previously created with the <code>creat-jdbc-connection</code> command. The operand identifies the JDBC connection pool to be deleted. This command is supported in remote mode only.	
<b>Options</b>	<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
	<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
	<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.

<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—cascade</code>	If the option is set to true, all the connector resources associated with the pool (mentioned as operand) apart from the pool itself are deleted. When set to false, the deletion of pool fails if any resources are associated with the pool. Resources must be deleted explicitly or the option must be set to true. By default, the option is false.

**Operands** *connectionpoolid* the name of the JDBC resource to be removed.

**Examples** **EXAMPLE 1** Using the delete-jdbc-connection-pool command

```
asadmin> delete-jdbc-connection-pool --passwordfile file1 --user u1 --cascade=false connection_pool
```

Command delete-jdbc-connection-pool executed correctly.

Where: asadmin is the command prompt and connection\_pool\_01 is the connection pool to be removed.

<b>Exit Status</b> 0	command executed successfully
1	error in executing the command

**See Also** [create-jdbc-connection-pool\(1\)](#), [list-jdbc-connection-pools\(1\)](#)

<b>Name</b>	delete-jdbc-resource – removes a JDBC resource with the specified JNDI name	
<b>Synopsis</b>	<b>delete-jdbc-resource</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—target</b> <i>target</i> ] <i>jndi_name</i>	
<b>Description</b>	The delete-jdbc-resource command removes a JDBC resource. This command is supported in remote mode only.	
<b>Options</b>	<b>-u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>-w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
	<b>-H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
	<b>-p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>-s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>-t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>-e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
	<b>-I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.

<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	valid in Enterprise Edition only, specifies the target to which you are deploying. Valid values are 'server,' 'domain,' cluster, or instance. The default is server.

**Operands** *jndi\_name* the JNDI name of this JDBC resource to be removed.

**Examples** EXAMPLE 1 Using the delete-jdbc-resource command

```
asadmin> delete-jdbc-resource --passwordfile pass1 --user u1 --target plum test_jdbc_resource
Command delete-jdbc-resource executed successfully.
```

Where asadmin is the command prompt and test\_jdbc\_resource is the name of the JDBC resource that is removed.

<b>Exit Status</b> 0	command executed successfully
1	error in executing the command

**See Also** [create-jdbc-resource\(1\)](#), [list-jdbc-resources\(1\)](#)

---

<b>Name</b>	delete-jmsdest – removes a physical destination	
<b>Synopsis</b>	<b>delete-jmsdest</b> <i>—user admin_user</i> [ <i>—passwordfile filename</i> ] [ <i>—host host_name</i> ] [ <i>—port port_number</i> ] [ <i>—secure -s</i> ] [ <i>—terse=false</i> ] [ <i>—echo=false</i> ] [ <i>—interactive=true</i> ] [ <i>—help</i> ] [ <i>—target target</i> ] <i>—desttype type dest_name</i>	
<b>Description</b>	The delete-jmsdest command removes the specified physical destination. This command is supported in remote mode only.	
<b>Options</b>	<i>-u</i> <i>—user</i>	The authorized domain application server administrative username.
	<i>-w</i> <i>—password</i>	The <i>—password</i> option is deprecated. Use <i>—passwordfile</i> instead.
	<i>—passwordfile</i>	This option replaces the <i>—password</i> option. Using the <i>—password</i> option on the command line or through the environment is deprecated. The <i>—passwordfile</i> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
	<i>-H</i> <i>—host</i>	The machine name where the domain application server is running. The default value is localhost.
	<i>-p</i> <i>—port</i>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<i>-s</i> <i>—secure</i>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<i>-t</i> <i>—terse</i>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<i>-e</i> <i>—echo</i>	Setting to true will echo the command line statement on the standard output. Default is false.
	<i>-I</i> <i>—interactive</i>	If set to true (default), only the required password options are prompted.

<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target from which you are deleting the physical destination. Although the <code>delete-jmsdest</code> command is related to resources, a physical destination is created and deleted using the JMS Service, which is part of the configuration. Valid values are <ul style="list-style-type: none"><li>▪ <code>server</code>, which deletes the physical destination from the default server instance <code>server</code> and is the default value</li><li>▪ <code>configuration_name</code>, which deletes the physical destination from the named configuration</li><li>▪ <code>cluster_name</code>, which deletes the physical destination from every server instance in the cluster</li><li>▪ <code>instance_name</code>, which deletes the physical destination from a particular server instance</li></ul>
<code>-T</code> <code>—desttype</code>	The type of the JMS destination. Valid values are <code>topic</code> and <code>queue</code> .

**Operands** `dest_name` The unique identifier of the the JMS destination to be deleted.

**Examples** EXAMPLE 1 Using the `delete-jmsdest` command

The following command deletes the queue named `PhysicalQueue`:

```
asadmin> delete-jmsdest --user admin --passwordfile passwords.txt
--host localhost --port 4848 --desttype queue PhysicalQueue
Command delete-jmsdest executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-jmsdest\(1\)](#), [list-jmsdest\(1\)](#)

---

<b>Name</b>	delete-jms-host – removes a JMS host	
<b>Synopsis</b>	<b>delete-jms-host</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—target</b> <i>target</i> ] <i>jms_host_name</i>	
<b>Description</b>	The command removes the specified JMS host. This command is supported in remote mode only.  Deleting the default JMS host, named <code>default_JMS_host</code> , is not recommended.	
<b>Options</b>	<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
	<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
	<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
	<b>—I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.

<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target from which you are deleting the JMS host. Valid values are <ul style="list-style-type: none"><li>▪ <code>server</code>, which deletes the JMS host from the default server instance <code>server</code> and is the default value</li><li>▪ <code>configuration_name</code>, which deletes the JMS host from the named configuration</li><li>▪ <code>cluster_name</code>, which deletes the JMS host from every server instance in the cluster</li><li>▪ <code>instance_name</code>, which deletes the JMS host from a particular server instance</li></ul>

**Operands** `jms_host_name` The name of the host to be deleted.

**Examples** **EXAMPLE 1** Using the `delete-jms-host` command

The following command deletes the JMS host named `MyNewHost`.

```
asadmin> delete-jms-host --user admin1
--passwordfile passwords.txt MyNewHost
Command delete-jms-host executed successfully.
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [create-jms-host\(1\)](#), [list-jms-hosts\(1\)](#)



<b>Name</b>	delete-jms-resource – removes a JMS resource	
<b>Synopsis</b>	<b>delete-jms-resource</b> —user <i>admin_user</i> [—passwordfile <i>filename</i> ] [—host <i>host_name</i> ] [—port <i>port_number</i> ] [—secure —s] [—terse= <i>false</i> ] [—echo= <i>false</i> ] [—interactive= <i>true</i> ] [—help] [—target <i>target</i> ] <i>jndi_name</i>	
<b>Description</b>	The delete-jms-resource command removes the specified JMS resource. For Enterprise Edition, make sure to remove all references to this resource before executing this command. This command is supported in remote mode only.	
<b>Options</b>	—u —user	The authorized domain application server administrative username.
	—w —password	The —password option is deprecated. Use —passwordfile instead.
	—passwordfile	This option replaces the —password option. Using the —password option on the command line or through the environment is deprecated. The —passwordfile option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
	—H —host	The machine name where the domain application server is running. The default value is localhost.
	—p —port	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	—s —secure	If set to true, uses SSL/TLS to communicate with the domain application server.
	—t —terse	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	—e —echo	Setting to true will echo the command line statement on the standard output. Default is false.

<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target from which you are deleting the JMS resource. Valid values are <ul style="list-style-type: none"><li>▪ <code>server</code>, which deletes the resource from the default server instance <code>server</code> and is the default value</li><li>▪ <code>domain</code>, which deletes the resource from the domain</li><li>▪ <code>cluster_name</code>, which deletes the resource from every server instance in the cluster</li><li>▪ <code>instance_name</code>, which deletes the resource from a particular server instance</li></ul>

**Operands** `jndi_name` The JNDI name of the JMS resource to be deleted.

**Examples** **EXAMPLE 1** Using the `delete-jms-resource` command

The following command deletes the JMS resource named `jms/Queue`:

```
asadmin> delete-jms-resource --user admin1
--passwordfile passwords.txt --host pigeon --port 5001 jms/Queue
Command delete-jms-resource executed successfully.
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [create-jms-resource\(1\)](#), [list-jms-resources\(1\)](#)

<b>Name</b>	delete-jdbc-resource – removes the JNDI resource with the specified JNDI name	
<b>Synopsis</b>	<b>delete-jndi-resource</b> <code>—user</code> <i>admin_user</i> [ <code>—passwordfile</code> <i>filename</i> ] [ <code>—host</code> <i>host_name</i> ] [ <code>—port</code> <i>port_number</i> ] [ <code>—secure</code>   <code>-s</code> ] [ <code>—terse</code> = <i>false</i> ] [ <code>—echo</code> = <i>false</i> ] [ <code>—interactive</code> = <i>true</i> ] [ <code>—help</code> ] [ <code>—target</code> <i>target</i> ] <i>jndi_name</i>	
<b>Description</b>	The <code>delete-jndi-resource</code> command removes the specified JNDI resource. This command is supported in remote mode only.	
	In Enterprise Edition, you must remove all associations to the JNDI resource before you execute this command.	
<b>Options</b>	<code>—u</code> <code>—user</code>	The authorized domain application server administrative username.
	<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
	<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
	<code>—H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
	<code>—p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<code>—s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<code>—t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<code>—e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.

<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	valid in Enterprise Edition only. Valid values are 'server,' 'domain,' cluster, or instance. The default is 'server.'

**Operands** *jndi\_name* the name of the JNDI resource to be removed.

**Examples** EXAMPLE 1 Using the delete-jndi-resource command

In Enterprise Edition, you must remove all associations to this resource before you execute this command.

```
asadmin> delete-jndi-resource --passwordfile p1 --user u2 --target plum sample_jndi_resource
Command delete-jndi-resource executed successfully.
```

Where asadmin is the command prompt and sample\_jndi\_resource is the resource to be removed.

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [create-jndi-resource\(1\)](#), [list-jndi-resources\(1\)](#)

<b>Name</b>	delete-jvm-options – removes JVM options from the Java configuration or profiler elements of the domain.xml file
<b>Synopsis</b>	<b>delete-jvm-options</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>—s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—target</b> <i>target</i> ] [ <b>—profiler</b> = <i>false</i> ] [( <i>jvm_option_name=jvm_option_value</i> )] [: <i>jvm_option_name=jvm_option_name</i> ] [*]
<b>Description</b>	Removes JVM options from the Java configuration or profiler elements of the domain.xml file. NOTE: In the syntax, there can be more than one <i>jvm_option</i> , separated by a colon.
<b>Options</b>	
<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.

<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	valid in Enterprise Edition only, specifies the target to which you are deploying. Valid values are 'server,' 'domain,' cluster, or instance. The default is server.
<code>—profiler</code>	indicates whether the JVM options are for the profiler. The profiler must exist for this option to be true.

**Operands** `jvm_option_name=jvm_option_value` The left side of the equal sign (=) is the JVM option name. The right side of the equal sign (=) is the JVM option value. A colon (:) is a delimiter for multiple options.

**Examples** **EXAMPLE 1** Using the delete-jvm-options command

To remove more than one JVM option, use a colon (:) to separate the options. If the JVM option itself contains a colon (:), use the backslash (\) to offset the colon (:) delimiter.

```
asadmin> delete-jvm-options -e \-Dtmp=sun
--interactive=true --secure=true --passwordfile /password
--terse=false --user admin --target server --host localhost
--echo=true --port 4849 \-Dtmp=sun
Command delete-jvm-options executed successfully
```

Where the JVM options are deleted.

```
asadmin> delete-jvm-options -e \-Doption1=value1
--interactive=true --secure=true --passwordfile /password
--terse=false --user admin --target server --host localhost
--echo=true --port 4849 \-Doption1=value1
Command delete-jvm-options executed successfully
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [create-jvm-option\(1\)](#)

---

<b>Name</b>	delete-lifecycle-module – removes the lifecycle module	
<b>Synopsis</b>	<b>delete-lifecycle-module</b> <code>--user admin_user</code> [ <code>--passwordfile filename</code> ] <code>[--host host_name]</code> [ <code>--port port_number</code> ] [ <code>--secure -s</code> ] [ <code>--terse=false</code> ] <code>[--echo=false]</code> [ <code>--interactive=true</code> ] [ <code>--help</code> ] [ <code>--target target</code> ] <i>module_name</i>	
<b>Description</b>	Removes the lifecycle module. This command is supported in remote mode only.	
<b>Options</b>	<code>-u</code> <code>--user</code>	The authorized domain application server administrative username.
	<code>-w</code> <code>--password</code>	The <code>--password</code> option is deprecated. Use <code>--passwordfile</code> instead.
	<code>--passwordfile</code>	This option replaces the <code>--password</code> option. Using the <code>--password</code> option on the command line or through the environment is deprecated. The <code>--passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
	<code>-H</code> <code>--host</code>	The machine name where the domain application server is running. The default value is localhost.
	<code>-p</code> <code>--port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<code>-s</code> <code>--secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<code>-t</code> <code>--terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<code>-e</code> <code>--echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
	<code>-I</code> <code>--interactive</code>	If set to true (default), only the required password options are prompted.
	<code>-h</code> <code>--help</code>	Displays the help text for the command.

**—target** This is the name of the resulting location. The valid targets for this command are configuration, instance, cluster, or server. This is used by EE only.

**Operands** *module\_name* This operand is a unique identifier or the deployed server lifecycle event listener module.

**Examples** EXAMPLE 1 Using delete-lifecycle-module

```
asadmin> delete-lifecycle-module --user admin --passwordfile adminpassword.txt
--host fuyako --port 7070 customSetup
Deleted the Lifecycle module with module name = customSetup
```

Where: customSetup is the lifecycle module deleted.

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-lifecycle-module\(1\)](#), [list-lifecycle-modules\(1\)](#)



- Name** delete-message-security-provider – enables administrators to delete a provider-config sub-element for the given message layer (message-security-config element of domain.xml)
- Synopsis** **delete-message-security-provider** `—user admin_user` [`—passwordfile filename`] [`—host host_name`] [`—port port_number`] [`—secure|—s`] [`—terse=false`] [`—echo=false`] [`—interactive=true`] [`—help`] [`—target target`] `—layer message_layer provider_name`
- Description** Enables administrators to delete a provider-config sub-element for the given message layer (message-security-config element of domain.xml, the file that specifies parameters and properties to the Application Server). The options specified in the list below apply to attributes within the message-security-config and provider-config sub-elements of the domain.xml file.
- If the message-layer (message-security-config attribute) does not exist, it is created, and then the provider-config is created under it.
- This command is supported in remote mode only.
- Options** If an option has a short option name, then the short option precedes the long option name. Short options have one dash whereas long options have two dashes.
- |                            |  |
|----------------------------|--|
| <code>—u —user</code>      | The authorized domain application server administrative username.  |
| <code>—w —password</code>  | The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.   |
| <code>—passwordfile</code> | This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on. |
| <code>—H —host</code>      | The machine name where the domain application server is running. The default value is localhost.   |
| <code>—p —port</code>      | The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.  |

---

<code>-s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>-t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target to which you are deploying. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, which deploys the component to the default server instance <code>server</code> and is the default value</li> <li>▪ <code>domain</code>, which deploys the component to the domain.</li> <li>▪ <code>cluster_name</code>, which deploys the component to every server instance in the cluster.</li> <li>▪ <code>instance_name</code>, which deploys the component to a particular sever instance.</li> </ul>
<code>—layer</code>	The message-layer from which the provider has to be deleted. The default value is SOAP.

**Operands** *provider\_name* The name of the provider used to reference the `provider-config` element.

**Examples** **EXAMPLE 1** Using `delete-message-security-provider`

The following example shows how to delete a message security provider for a client.

```
asadmin> delete-message-security-provider --user admin
--layer SOAP mySecurityProvider
```

**Exit Status**

0	command executed successfully
1	error in executing the command

**See Also** [create-message-security-provider\(1\)](#), [list-message-security-providers\(1\)](#)

---

<b>Name</b>	delete-node-agent – deletes the node agent and its associated directory structure	
<b>Synopsis</b>	<b>delete-node-agent</b> [ <code>--terse=false</code> ] [ <code>--echo=false</code> ] [ <code>--interactive=true</code> ] [ <code>--agentdir nodeagent_path</code> ] <i>nodeagent_name</i>	
<b>Description</b>	Use the delete-node-agent command to delete the named node agent and its directory structure. The node agent must be stopped and have no associated server instances. After successful execution of the command, delete-node-agent-config must be executed to remove the named node agent from domain.xml.	
<b>Options</b>	<code>-t</code> —terse	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<code>-e</code> —echo	Setting to true will echo the command line statement on to the standard output. Default is false.
	<code>-I</code> —Interactive	If set to true (default), only the required options are prompted.
	<code>--agentdir</code>	Like a Domain Administration Server (DAS), each node agent resides in a top level directory named <code>&lt;agentdir&gt;/&lt;nodeagent_name&gt;</code> . If specified, the path must be accessible in the filesystem. If not specified, the node agent is deleted from the default <code>install_dir/nodeagents</code> directory.
<b>Operands</b>	<i>nodeagent_name</i>	This is the name of the node agent to be deleted.
<b>Examples</b>	<p><b>EXAMPLE 1</b> Using delete-node-agent</p> <p>This is a basic example of how to use this command.</p> <pre>% asadmin&gt;delete-node-agent nodeagent1 Node Agent nodeagent1 deleted.</pre> <p>Where: % is the command prompt, and nodeagent1, residing in the default <code>install_dir/nodeagents</code> directory, is deleted together with its directory structure. Please note that at this point nodeagent1 references still exist in domain.xml. Use the following command to complete the removal process:</p> <pre>% asadmin&gt;delete-node-agent-config --user admin1 --passwordfile filename nodeagent1</pre>	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>See Also</b>	<a href="#">create-node-agent(1)</a> , <a href="#">list-node-agents(1)</a> , <a href="#">start-node-agent(1)</a> , <a href="#">stop-node-agent(1)</a>	

---

<b>Name</b>	delete-node-agent-config – removes a node agent from a domain	
<b>Synopsis</b>	<b>delete-node-agent-config</b> —user <i>admin_name</i> —passwordfile <i>filename</i> [—host <i>localhost</i> ] [—port <i>port_number</i> ] [—secure= <i>false</i> ] [—terse= <i>false</i> ] [—echo= <i>false</i> ] [—interactive= <i>true</i> ] <i>nodeagent_name</i>	
<b>Description</b>	<p>This command removes the specified node agent from the domain, at which point the node agent directory structure can also be removed (using the delete-node-agent command).</p> <p>Important: The specified node agent must have no server instances running, This means all the agent’s instances must be deleted (using delete-instance) before executing this command.</p>	
<b>Options</b>	—u—user	The authorized domain application server administrative username.
	—w—password	The —password option is deprecated. Use —passwordfile instead.
	— passwordfile	The name of the file containing the domain application server password. The passwordfile should contain either of the following entries: AS_ADMIN_PASSWORD= <i>password</i> or AS_ADMIN_MAPPEDPASSWORD= <i>password</i> . If this option is not called directly, you will be prompted for it before the requested action is completed.
	—H—host	The machine name where the domain application server is running.
	—p—port	The port number of the domain application server listening for administration requests.
	—s—secure	If set to true, this command uses SSL/TLS to communicate with the domain application server.
	—t—terse	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. The default is false.
	—e—echo	Setting this option to true will echo the command line statement on the standard output. The default is false.
	—I—interactive	If this option is set to true (default), only the required password options are prompted.
<b>Operands</b>	<i>nodeagent_name</i>	The name of the node must be unique on the machine. Typically, the nodeagent_name is the host name of the machine where the node agent will reside.

**Examples** EXAMPLE 1 Using delete-node-agent-config

This is a basic example of how the command is used.

```
asadmin> delete-node-agent-config --user admin1 --passwordfile filename nodeagent1  
Command delete-node-agent-config executed successfully.
```

**Exit Status** 0                                   command executed successfully  
              1                                   error in executing the command

**See Also** [create-node-agent-config\(1\)](#); [delete-instance\(1\)](#)

**Name** delete-password-alias – deletes a password alias

**Synopsis** **delete-password-alias** **—user** *admin\_user* [**—passwordfile** *filename*]  
[**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**—s**] [**—terse**=*false*]  
[**—echo**=*false*] [**—interactive**=*true*] [**—help**] *alias-name*

**Description** This command deletes a password alias.

<b>Options</b> <b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
<b>—I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.
<b>—h</b> <b>—help</b>	Displays the help text for the command.

**Operands** `aliasname` This is the name of the substitute password as it appears in `domain.xml`.

**Examples** `EXAMPLE 1` Using `delete-password-alias`  
`asadmin> delete-password-alias --aliasname alias1`

Command `delete-password-alias` executed successfully

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-password-alias\(1\)](#), [list-password-aliases\(1\)](#), [update-password-alias\(1\)](#)

**Name** delete-persistence-resource – removes a persistence resource

**Synopsis** **delete-persistence-resource** `—user` *admin\_user* [`—passwordfile` *filename*]  
 [`—host` *host\_name*] [`—port` *port\_number*] [`—secure`|`-s`] [`—terse`=*false*]  
 [`—echo`=*false*] [`—interactive`=*true*] [`—help`] [`—target` *target*] *jndi\_name*

**Description** Removes a persistence resource. This command is supported in remote mode only.

**Options**

<code>—u</code> <code>—user</code>	The authorized domain application server administrative username.
<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>—H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>—p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>—s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>—t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>—e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>—I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>—h</code> <code>—help</code>	Displays the help text for the command.



**---target** Specifies the target from which you are deleting a persistence resource. Valid values are

- `server`, which deploys the component to the default server instance `server` and is the default value
- `domain`, which deploys the component to the domain.
- `cluster_name`, which deploys the component to every server instance in the cluster.
- `instance_name`, which deploys the component to a particular sever instance.

**Operands** *jndi\_name* Specifies the JNDI name of the persistence resource.

**Examples** EXAMPLE 1 Using `delete-persistence-resource`

```
asadmin> delete-persistence-resource --user admin --passwordfile secret.txt
--host pigeon --port 5001 sample_persistence_resource
Command delete-persistence-resource executed successfully
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-persistence-resource\(1\)](#), [list-persistence-resources\(1\)](#)

**Name** delete-profiler – deletes the profiler element

**Synopsis** **delete-profiler** `—user` *admin\_user* [`—passwordfile` *filename*] [`—host` *host\_name*] [`—port` *port\_number*] [`—secure`|`-s`] [`—terse=false`] [`—echo=false`] [`—interactive=true`] [`—help`] [`—target` *target\_name*]

**Description** Deletes the profiler element. A server instance is tied to a particular profiler by the profiler element in the Java configuration. Changing a profiler requires you to restart the server.

This command is supported in remote mode only.

<b>Options</b> <code>—u</code> <code>—user</code>	The authorized domain application server administrative username.
<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>—H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>—p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>—s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>—t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>—e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.

---

<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target profiler element which you are deleting. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, deletes the profiler element for the default server instance <code>server</code> and is the default value</li> <li>▪ <code>configuration_name</code>, deletes the profiler element for the named configuration</li> <li>▪ <code>cluster_name</code>, deletes the profiler element for every server instance in the cluster</li> <li>▪ <code>instance_name</code>, deletes the profiler element for a particular server instance</li> </ul>

**Examples** EXAMPLE 1 Using delete-profiler

```
asadmin> delete-profiler --user admin --passwordfile password.txt
--host localhost --port 4848
Deleted Profiler
```

Where: `profiler` is the deleted profile element.

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [create-profiler\(1\)](#), [list-profiler\(1\)](#)

---

<b>Name</b>	delete-resource-adapter-config – deletes the configuration information created in domain.xml for the connector module	
<b>Synopsis</b>	<b>delete-resource-adapter-config</b> —user <i>admin_user</i> [—passwordfile <i>filename</i> ] [—host <i>host_name</i> ] [—port <i>port_number</i> ] [—secure —s] [—terse=false] [—echo=false] [—interactive=true] [—help] <i>raName</i>	
<b>Description</b>	This command deletes the resource adapter javabean.	
<b>Options</b>	—u —user	The authorized domain application server administrative username.
	—w —password	The —password option is deprecated. Use —passwordfile instead.
	—passwordfile	This option replaces the —password option. Using the —password option on the command line or through the environment is deprecated. The —passwordfile option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
	—H —host	The machine name where the domain application server is running. The default value is localhost.
	—p —port	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	—s —secure	If set to true, uses SSL/TLS to communicate with the domain application server.
	—t —terse	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	—e —echo	Setting to true will echo the command line statement on the standard output. Default is false.
	—I —interactive	If set to true (default), only the required password options are prompted.

`-h` `—help` Displays the help text for the command.  
`—target` This option is deprecated.

**Operands** *raname* This value is kept in the `resource-adapter-name` in the `domain.xml` file.

**Examples** **EXAMPLE 1** Using `delete-resource-adapter-config`  
`asadmin> delete-resource-adapter-config --user admin1 --passwordfile pfile1 ra1`  
Command `delete-resource-adapter-config` executed successfully

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-resource-adapter-config\(1\)](#), [list-resource-adapter-configs\(1\)](#)

**Name** delete-resource-ref – removes a reference to a resource

**Synopsis** **delete-resource-ref** **—user** *admin\_user* [**—passwordfile** *filename*] [**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**—s**] [**—terse=false**] [**—echo=false**] [**—interactive=true**] [**—help**] [**—target** *target*] *reference\_name*

**Description** The delete-resource-ref command removes a reference from a cluster or an unclustered server instance to a resource (for example, a JDBC resource). This effectively results in the removal of the resource from the JNDI tree of the targeted instance or cluster.

The target instance or instances making up the cluster need not be running or available for this command to succeed. If one or more instances are not available, they will no longer load the resource in the JNDI tree the next time they start.

Removal of the reference does not result in removal of the resource from the domain. The resource is removed only by the delete command for that resource (for example, delete-jdbc-resource).

This command is supported in remote mode only.

<b>Options</b> <b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.

---

<code>-t</code> <code>--terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>--echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>--interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>--help</code>	Displays the help text for the command.
<code>--target</code>	Specifies the target from which you are removing the resource reference. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, which removes the resource reference from the default server instance <code>server</code> and is the default value</li> <li>▪ <code>cluster_name</code>, which removes the resource reference from every server instance in the cluster</li> <li>▪ <code>instance_name</code>, which removes the resource reference from the named unclustered server instance</li> </ul>

**Operands** *reference\_name*                      The name or JNDI name of the resource.

**Examples** **EXAMPLE 1** Using the delete-resource-ref command

The following command removes a reference to the JMS destination resource `.jms/Topic` on the unclustered server instance `NewServer`.

```
asadmin> delete-resource-ref --user admin2
--passwordfile passwords.txt --target NewServer.jms/Topic
Command delete-resource-ref executed successfully.
```

**Exit Status**    0                                      command executed successfully  
                   1                                      error in executing the command

**See Also** [create-resource-ref\(1\)](#), [list-resource-refs\(1\)](#)

**Name** delete-ssl – deletes the SSL element in the selected HTTP listener, IIOP listener, or IIOP service

**Synopsis** `delete-ssl` `--user` *admin\_user* [`--passwordfile` *filename*] [`--host` *host\_name*]  
 [`--port` *port\_number*] [`--secure`|`-s`] [`--terse=false`] [`--echo=false`]  
 [`--interactive=true`] [`--help`] [`--target` *target*] `--type` *listener\_or\_service\_type*  
*listener\_id*

**Description** Deletes the SSL element in the selected HTTP listener, IIOP listener, or IIOP service.

The *listener\_id* is not required if the `--type` is *iiop-service*.

This command is supported in remote mode only.

**Options** If an option has a short option name, then the short option precedes the long option name. Short options have one dash whereas long options have two dashes.

<code>--u</code> <code>--user</code>	The authorized domain application server administrative username.
<code>--w</code> <code>--password</code>	The <code>--password</code> option is deprecated. Use <code>--passwordfile</code> instead.
<code>--passwordfile</code>	This option replaces the <code>--password</code> option. Using the <code>--password</code> option on the command line or through the environment is deprecated. The <code>--passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>--H</code> <code>--host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>--p</code> <code>--port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>--s</code> <code>--secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.



<code>-t</code> <code>--terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>--echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>--interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>--help</code>	Displays the help text for the command.
<code>--target</code>	In Enterprise Edition, specifies the target to which you are deploying. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, the server in which the <code>iiop-service</code> or listener is to be unconfigured for SSL.</li> <li>▪ <code>config</code>, the configuration that contains the listener or <code>iiop-service</code> for which SSL is to be unconfigured.</li> <li>▪ <code>cluster</code>, the cluster in which the listener or <code>iiop-service</code> is to be unconfigured for SSL. All the server instances in the cluster will get SSL unconfigured for the respective listener or <code>iiop-service</code>.</li> <li>▪ <code>instance</code>, the instance in which the listener or <code>iiop-service</code> is to be unconfigured for SSL.</li> </ul>
<code>--type</code>	The type of service or listener for which the SSL is created. The type can be <code>http-listener</code> , <code>iiop-listener</code> , or <code>iiop-service</code> .
<b>Operands</b> <code>listener_id</code>	The ID of the listener from which the SSL element is to be deleted.  The <code>listener_id</code> operand is not required if the <code>--type</code> is <code>iiop-service</code> .
<b>Examples</b> EXAMPLE 1 Using delete-ssl	The following example shows how to delete an SSL element from an HTTP listener named <code>http-listener-1</code> .  <pre>asadmin&gt; delete-ssl --user admin --secure --host fuyako --port 7070 --passwordfile adminpassword.txt --type http-listener http-listener-1 Deleted SSL in HTTP Listener</pre>
<b>Exit Status</b>	0 command executed successfully 1 error in executing the command
<b>See Also</b>	<code>create-ssl(1)</code>

- Name** delete-system-property – removes one system property of the domain, configuration, cluster, or server instance, at a time
- Synopsis** **delete-system-property** `—user admin_user` [`—passwordfile filename`] [`—host host_name`] [`—port port_number`] [`—secure|—s`] [`—terse=false`] [`—echo=false`] [`—interactive=true`] [`—help`] [`—target target_name`] [`—property_name`]
- Description** Shared or clustered server instances will often need to override attributes defined in their referenced configuration. Any configuration attribute in a server instance can be overridden through a system property of the corresponding name. This command deletes system properties of a domain, configuration, cluster, or server instance.
- Options**
- |                            |   |
|----------------------------|---|
| <code>—u —user</code>      | The authorized domain application server administrative username.   |
| <code>—w —password</code>  | The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.  |
| <code>—passwordfile</code> | This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on. |
| <code>—H —host</code>      | The machine name where the domain application server is running. The default value is localhost.  |
| <code>—p —port</code>      | The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.   |
| <code>—s —secure</code>    | If set to true, uses SSL/TLS to communicate with the domain application server.   |
| <code>—t —terse</code>     | Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.  |

---

<code>-e</code> <code>--echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>--interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>--help</code>	Displays the help text for the command.
<code>--target</code>	In Enterprise Edition, specifies the target on which you are deleting the system properties. The valid targets for this command are instance, cluster, configuration, 'domain,' and 'server.' Server is the default option.

**Operands** *property\_name* The name of the system property to remove.

**Examples** EXAMPLE 1 Using delete-system-properties

```
asadmin> delete-system-property --user admin --passwordfile password.txt
--host localhost --port 4849 --target mycluster http-listener-port
Command delete-system-property executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-system-properties\(1\)](#), [list-system-properties\(1\)](#)

**Name** delete-threadpool – removes the named threadpool

**Synopsis** **delete-threadpool** `—user` *admin\_user* [`—passwordfile` *filename*] [`—host` *host\_name*] [`—port` *port\_number*] [`—secure`|`-s`] [`—terse`=*false*] [`—echo`=*false*] [`—interactive`=*true*] [`—help`] [`—target` *target\_name*] [`—maxthreadpoolsize` *max\_thread\_pool\_size*] [`—minthreadpoolsize` *min\_thread\_pool\_size*] [`—idletimeout` *idle\_thread\_timeout\_in\_seconds*] [`—workqueues` *number\_work\_queues*] {*threadpool\_id*}

**Description** Removes the threadpool with the named ID. This command is supported in remote mode only.

<b>Options</b> <code>—u</code>	<code>—user</code>	The authorized domain application server administrative username.
<code>—w</code>	<code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>		This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>—H</code>	<code>—host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>—p</code>	<code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>—s</code>	<code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>—t</code>	<code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>—e</code>	<code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.

---

<code>-I</code>	<code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code>	<code>—help</code>	Displays the help text for the command.
<code>—target</code>		In Enterprise Edition, specifies the target on which you are creating the threadpool. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, which creates the listener for the default server instance <code>server</code> and is the default value</li> <li>▪ <code>configuration_name</code>, which creates the listener for the named configuration</li> <li>▪ <code>cluster_name</code>, which creates the listener for every server instance in the cluster</li> <li>▪ <code>instance_name</code>, which creates the listener for a particular server instance</li> </ul>
<code>--maxthreadpoolsize</code>		maximum number of threads in the threadpool servicing requests in this queue. This is the upper bound on the number of threads that exist in the threadpool.
<code>--minthreadpoolsize</code>		minimum number of threads in the threadpool servicing requests in this queue. These are created up front when the threadpool is instantiated.
<code>--idletimeout</code>		idle threads are removed from the pool after this time.
<code>--workqueues</code>		identifies the total number of work queues serviced by this threadpool.
<b>Operands</b>	<i>threadpool_id</i>	an ID for the work queue; for example, <code>thread-pool-1</code> , <code>thread-pool-2</code> , etc.
<b>Examples</b>	<p><b>EXAMPLE 1</b> Using <code>delete-threadpool</code></p> <pre>asadmin&gt; delete-threadpool --user admin1 --passwordfile password.txt threadpool-1 Command delete-threadpool executed successfully</pre>	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>See Also</b>	<a href="#">create-threadpool(1)</a> , <a href="#">list-threadpools(1)</a>	

---

<b>Name</b>	delete-virtual-server – removes a virtual server
<b>Synopsis</b>	<b>delete-virtual-server</b> <code>—user</code> <i>admin_user</i> [ <code>—passwordfile</code> <i>filename</i> ] <code>[—host</code> <i>host_name</i> ] [ <code>—port</code> <i>port_number</i> ] [ <code>—secure</code>   <code>—s</code> ] [ <code>—terse</code> = <i>false</i> ] <code>[—echo</code> = <i>false</i> ] [ <code>—interactive</code> = <i>true</i> ] [ <code>—help</code> ] [ <code>—target</code> <i>server</i> ] <i>virtual_server_id</i>
<b>Description</b>	The <code>delete-virtual-server</code> command removes the virtual server with the specified virtual server ID. This command is supported in remote mode only.
<b>Options</b>	<p><code>—u</code> <code>—user</code> The authorized domain application server administrative username.</p> <p><code>—w</code> <code>—password</code> The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.</p> <p><code>—passwordfile</code> This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</p> <p><code>—H</code> <code>—host</code> The machine name where the domain application server is running. The default value is <code>localhost</code>.</p> <p><code>—p</code> <code>—port</code> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><code>—s</code> <code>—secure</code> If set to <code>true</code>, uses SSL/TLS to communicate with the domain application server.</p> <p><code>—t</code> <code>—terse</code> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is <code>false</code>.</p> <p><code>—e</code> <code>—echo</code> Setting to <code>true</code> will echo the command line statement on the standard output. Default is <code>false</code>.</p> <p><code>—I</code> <code>—interactive</code> If set to <code>true</code> (default), only the required password options are prompted.</p>

---

<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	In Enterprise Edition, specifies the target from which you are deleting the virtual server. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, which deletes the virtual server from the default server instance <code>server</code> and is the default value</li> <li>▪ <code>configuration_name</code>, which deletes the virtual server from the named configuration</li> <li>▪ <code>cluster_name</code>, which deletes the virtual server from every server instance in the cluster</li> <li>▪ <code>instance_name</code>, which deletes the virtual server from a particular server instance</li> </ul>

**Operands** *virtual\_server\_id* The unique identifier for the virtual server to be deleted.

**Examples** EXAMPLE 1 Using the `delete-virtual-server` command

The following command deletes the virtual server named `sample_vs1`:

```
asadmin> delete-virtual-server --user admin1
--passwordfile passwords.txt --host pigeon --port 5001 sample_vs1
Command delete-virtual-server executed successfully.
```

**Exit Status**

0	command executed successfully
1	error in executing the command

**See Also** [create-virtual-server\(1\)](#), [list-virtual-servers\(1\)](#)

**Name** `deploy` – deploys the specified component

**Synopsis** `deploy` `—user` *admin\_user* [`—passwordfile` *filename*] [`—host` *host\_name*] [`—port` *port\_number*] [`—secure`|`—s`] [`—terse`=*false*] [`—echo`=*false*] [`—interactive`=*true*] [`—help`] [`—virtualservers` *virtual\_servers*] [`—contextroot` *context\_root*] [`—force`=*true*] [`—precompilejsp`=*false*] [`—verify`=*false*] [`—name` *component\_name*] [`—upload`=*true*] [`—retrieve` *local\_dirpath*] [`—dbvendorname` *dbvendorname*] [`—createtables`=*true|false* | `—dropandcreatetables`=*true|false* ] [`—uniquetablenames`=*true|false*] [`—enabled`=*true*] [`—deploymentplan` *deployment\_plan*] [`—availabilityenabled`=*false*] [`—generateterminstubs`=*false*] [`—target` *target*] *filepath*

**Description** Deploys an EJB, web, connector, or application. If the component is already deployed or already exists, it is forcefully redeployed if the `—force` option is set to `true`.

The `—createtables` and `—dropandcreatetables` options are booleans and therefore can take the values of *true* or *false*. These options are only used during deployment of CMP beans that have not been mapped to a database (i.e., no `sun-cmp-mappings.xml` descriptor is provided in the module's `META-INF` directory). They are ignored otherwise.

The `—createtables` and `—dropandcreatetables` options are mutually exclusive; only one should be used. If drop and/or create tables fails, the deployment does not fail; a warning message is provided in the log file.

This command is supported in remote mode only.

<b>Options</b>	<code>—u</code> <code>—user</code>	The authorized domain application server administrative username.
	<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
	<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> ,



---

	AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASSPASSWORD, and so on.
<code>-H—host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>-p—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>-s—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>-t—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h—help</code>	Displays the help text for the command.
<code>—virtualservers</code>	Comma separated list of virtual server names.
<code>—contextroot</code>	Valid only if the archive is a web module. It is ignored for other archive types; defaults to filename without extension.
<code>—force</code>	Makes sure the component is redeployed even if the specified component has already been deployed or already exists. Use this option when redeploying an existing application, otherwise you see an error.
<code>—precompilejsp</code>	By default this option is set to false, which does not allow the JSP to pre-compile during deployment. Instead JSPs are compiled during runtime.
<code>—verify</code>	If set to true, the syntax and semantics of the deployment descriptor is verified.
<code>—name</code>	Name of the deployable component.
<code>—upload</code>	When set to true, uploads the deployable file to the administration server. If the filepath of the deployable file is mounted to the server machine, or if the administration server is running locally, set the upload option to false.

<code>--retrieve</code>	Retrieves the client stub JAR file from the server machine to the local directory.
<code>--dbvendorname</code>	Name of database vendor being used. Default is the <code>database-entry-name</code> entry in the <code>cmp-resource()</code> element of the <code>sun-ejb-jar.xml</code> file. If not specified the default is SQL92, and the DDL files to create and drop tables are generated in SQL92 format.
<code>--createtables</code>	Creates tables at deployment of an application with unmapped CMP beans. Default is the <code>create-tables-at-deploy</code> entry in the <code>cmp-resource</code> element of the <code>sun-ejb-jar.xml</code> file.
<code>--dropandcreatetables</code>	Drops tables at redeployment of an already deployed application with unmapped CMP beans. If not specified, the tables are dropped if the <code>drop-tables-at-undeploy</code> entry in the <code>cmp-resource</code> element of the <code>sun-ejb-jar.xml</code> file is set to true. The new tables are created if the <code>create-tables-at-deploy</code> entry in the <code>cmp-resource</code> element of the <code>sun-ejb-jar.xml</code> file is set to true. On redeployment the tables created by the previous deploy are dropped before creating the new tables.
<code>--uniquetablenames</code>	Guarantees unique table names for all the beans and results in a hashcode added to the table names. This is useful if you have an application with case-sensitive bean names.
<code>--enabled</code>	If set to true (default), allows users to access the application. If set to false, users will not be able to access the application.  For Enterprise Edition, this option enables the application on the specified target instance or cluster. If you deploy to the target domain, this option is ignored, since deploying to the domain doesn't deploy to a specific instance or cluster.
<code>--deploymentplan</code>	Takes the deployment plan, which is a JAR containing Sun-specific descriptors, and deploys it. This should be passed along when deploying a pure EAR file. A pure EAR file is an EAR without Sun-specific descriptors.

<code>—generateterminstubs</code>	If set to true, static RMI-IIOP stubs are generated and put into the <code>client.jar</code> . If set to false (default) the stubs are not generated.
<code>—availabilityenabled</code>	In Enterprise Edition, if set to true, high-availability is enabled for SFSB checkpointing (and potentially passivation). If set to false (default) all SFSB checkpointing is disabled for the application or EJB module. Set this option to true only high availability is configured and enabled.
<code>—target</code>	In Enterprise Edition, specifies the target to which you are deploying. Valid values are: <ul style="list-style-type: none"> <li>▪ <code>server</code>, which deploys the component to the default server instance <code>server</code> and is the default value.</li> <li>▪ <code>domain</code>, which deploys the component to the domain. If <code>domain</code> is the target for an initial deployment, the application is deployed to the domain, but no server instances or clusters reference the application. If <code>domain</code> is the target for a redeployment (the <code>—force</code> option is set to true), and dynamic reconfiguration is enabled for the clusters or server instances that reference the application, the referencing clusters or server instances automatically get the new version of the application. If redeploying, and dynamic configuration is disabled, the referencing clusters or server instances do not get the new version of the application until the clustered or standalone server instances are restarted.</li> <li>▪ <code>cluster_name</code>, which deploys the component to every server instance in the cluster.</li> <li>▪ <code>instance_name</code>, which deploys the component to a particular sever instance.</li> </ul>

**Operands** *filepath*

Path to the deployable file on the local machine if the `upload` option is set to `true`; otherwise the absolute path to the file on the server machine.

**Examples** EXAMPLE 1 Deploying a J2EE application

Deploy (install) the J2EE application packaged in the `Cart.ear` file.

**EXAMPLE 1** Deploying a J2EE application *(Continued)*

This syntax deploys the application to the default server instance server. For Sun Java System Application Server, Enterprise Edition, use the `—target` option to deploy to a different server instance or to a cluster.

```
asadmin> deploy --user admin --passwordfile filename Cart.ear  
Command deploy executed successfully
```

**EXAMPLE 2** Deploying a Web application with the default context root

Deploy the Web application in the `hello.war` file at the `hello` context root.

This syntax deploys the application to the default server instance server. For Sun Java System Application Server, Enterprise Edition, use the `—target` option to deploy to a different server instance or to a cluster.

```
asadmin> deploy --user admin --passwordfile myfile hello.war  
Command deploy executed successfully
```

**EXAMPLE 3** Deploying an enterprise bean (EJB component)

Deploy an enterprise bean with container-managed persistence (CMP) and create the database tables used by the bean.

This example uses the `—target` option, available with Sun Java System Application Server Enterprise Edition only. To use this example for Standard Edition, omit that option. The target in this example is an existing cluster, `cluster1`.

```
asadmin> deploy --user admin --passwordfile filename --createtables=true  
--target cluster1 EmployeeEJB.jar  
Command deploy executed successfully
```

**EXAMPLE 4** Deploying a connector module (resource adapter)

Deploy a connector module packaged in a RAR file.

This example uses the `—target` option, available with Sun Java System Application Server Enterprise Edition only. To use this example for Standard Edition, omit that option. The target in this example is an existing standalone server instance that does not belong to a cluster.

```
asadmin> deploy --user admin --passwordfile filename --target myinstance jdbcra.rar  
Command deploy executed successfully
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [undeploy\(1\)](#), [list-components\(1\)](#)

**Name** deploydir – deploys an exploded format of application archive

**Synopsis** **deploydir** —user *admin\_user* [—passwordfile *filename*] [—host *host\_name*] [—port *port\_number*] [—secure|—s] [—terse=*false*] [—echo=*false*] [—interactive=*true*] [—help] [—virtualservers *virtual\_servers*] [—contextroot *context\_root*] [—force=*true*] [—verify=*false*] [—precompilejsp=*false*] [—name *component\_name*] [—uniquetablenames=*true|false*] [—dbvendorname *dbvendorname*] [—createtables=*false* | —dropandcreatetables=*false*] [—generateterminstubs=*false*] [—availabilityenabled=*false*] [—target *target*] *dirpath*

**Description** Deploys the exploded format of the application archives present under the directory provided as the command operand.

Directory deployment is for advanced developers only. Do not use it in production environments. In production environments, use the deploy command. Directory deployment is not supported for clusters and remote server instances.

The deployed EAR or WAR applications reside on the Domain Administration Server and have a directory structure that can be used for deployment. The —force option makes sure the component is forcefully (re)deployed even if the specified component has already been deployed or already exists. Set—force to false for a first deployment. If the application with that name is running and force is set to false, the command fails.

If the —uniquetablenames, —createtables, and —dropandcreatetables options are not specified, the entries in the deployment descriptors are used.

This command is supported in remote mode only.

<b>Options</b>	—u —user	The authorized domain application server administrative username.
	—w —password	The —password option is deprecated. Use —passwordfile instead.
	—passwordfile	This option replaces the —password option. Using the —password option on the command line or through the environment is deprecated. The —passwordfile option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other

	passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASSPASSWORD, and so on.
-H—host	The machine name where the domain application server is running. The default value is localhost.
-p—port	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
-s—secure	If set to true, uses SSL/TLS to communicate with the domain application server.
-t—terse	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
-e—echo	Setting to true will echo the command line statement on the standard output. Default is false.
-I—interactive	If set to true (default), only the required password options are prompted.
-h—help	Displays the help text for the command.
—virtualservers	Comma separated list of virtual server IDs.
—contextroot	Valid only if the archive is a web module. It is ignored for other archive types; defaults to filename without extension.
—force	Makes sure the component is forcefully (re)deployed even if the specified component has already been deployed or already exists.
—verify	If set to true, the syntax and semantics of the deployment descriptor is verified.
—precompilejsp	By default, this option is set to false, which does not allow the JSP to pre-compile during deployment. Instead, JSPs are compiled during runtime.
—name	Name of the deployable component.
—uniquetablenames	Guarantees unique table names for all the beans and results in a hashcode added to the table names.

---

	This is useful if you have an application with case-sensitive bean names.
<code>--dbvendorname</code>	Name of the database vendor being used. Default is the corresponding entry in the <code>cmp-resource ()</code> element of the <code>sun-ejb-jar.xml</code> file. If not specified, the default is SQL92, and the DDL files to create and drop tables are generated in SQL92 format.
<code>--createtables</code>	Creates tables during deployment for applications using unmapped CMP beans. Default is the corresponding entry in the <code>cmp-resource</code> element of the <code>sun-ejb-jar.xml</code> file. If not specified, defaults to the entries in the deployment descriptors.
<code>--dropandcreatetables</code>	Drops existing tables and creates tables during deployment for application using unmapped CMP beans. If not specified, the tables are dropped if the <code>drop-tables-at-undeploy</code> entry in the <code>cmp-resource</code> element of the <code>sun-ejb-jar.xml</code> file is set to true. The new tables are created if the <code>create-tables-at-deploy</code> entry in the <code>cmp-resource</code> element of the <code>sun-ejb-jar.xml</code> is set to true. When the component is redeployed, the tables created by the previous deployment are dropped before creating the new tables.
<code>--generatermistubs</code>	if set to true, static RMI-IIOP stubs are generated and put into the <code>client.jar</code> . If set to false (default) the stubs are not generated.
<code>--availabilityenabled</code>	If set to true, high-availability is enabled for SFSB checkpointing (and potentially passivation). If set to false (default) all SFSB checkpointing is disabled for the application or EJB module.
<code>--target</code>	In Enterprise Edition, specifies the target to which you are deploying. Valid values are: <ul style="list-style-type: none"> <li>▪ <code>server</code>, which deploys the component to the default server instance <code>server</code> and is the default value.</li> <li>▪ <code>domain</code>, which deploys the component to the domain.</li> </ul>
<b>Operands</b> <i>dirpath</i>	path to the directory containing the exploded format of the deployable archive.



**Examples** EXAMPLE 1 Using deploydir

```
asadmin> deploydir --user admin --passwordfile passwords.txt  
--host localhost --port 4848 --force=true --precompilejsp=true /home/temp/sampleApp  
Command deploydir executed successfully
```

Where the exploded application to be deployed is in the /home/temp/sampleApp directory.

**Exit Status** 0                                   command executed successfully  
              1                                   error in executing the command

**See Also** [deploy\(1\)](#), [undeploy\(1\)](#), [enable\(1\)](#), [disable\(1\)](#), [list-components\(1\)](#)

**Name** deploytool – launches the deploytool utility to deploy, package, and edit your J2EE applications

**Synopsis** **deploytool** [**--help**] [**--userdir** *user\_directory*]  
 [**--configdir** *configuration\_directory* **--verbose**]

**Description** Use the `deploytool` utility to deploy and package your J2EE applications and components, create and edit J2EE deployment descriptors, and create and edit Sun Java System Application Server specific deployment descriptors. If the application is not J2EE compliant, an error message is displayed.

Only one session of the `deploytool` utility can run with a specific user directory. A lock file is created to ensure that only one utility session is running. A message is displayed if a lock file is detected.

**Options**

<code>--help</code>	displays the arguments for launching the <code>deploytool</code> .
<code>--userdir</code>	identifies the user directory. The default user directory is <code>.deploytool</code> under your home directory. Only one <code>deploytool</code> session can be running per user directory. A lock file is created under the user directory to ensure that only one session of the <code>deploytool</code> is running. The <code>deploytool</code> utility uses this directory to store configuration information. <ul style="list-style-type: none"> <li>▪ On Solaris, the default directory is at <code>~/ .deploytool</code></li> </ul>
<code>--configdir</code>	identifies the configuration directory. The configuration directory is where the <code>asenv.conf</code> file is located. <p>On Solaris, the <code>asenv.conf</code> can be found at:</p> <ul style="list-style-type: none"> <li>▪ Bundled installation: <code>/etc/appserver</code></li> <li>▪ Unbundled installation: default is <code>/etc/opt/SUNWappserver</code> or user specified</li> <li>▪ Evaluation installation: <code>cd /etc</code>. Where <code>AS_SERVER_INSTALL</code> is the directory where you have installed the Sun Java System Application Server 8.</li> </ul>
<code>--verbose</code>	displays the <code>deploytool</code> log messages on the terminal window in Solaris and command window on windows.

**Examples** **EXAMPLE 1** Using `deploytool`

```
example% deploytool --userdir /myapplication --config_dir /myconfigdir
```

Where `--userdir` specifies the destination directory, and `-config_dir` identifies the configuration directory.

**See Also** [verifier\(1M\)](#)

---

<b>Name</b>	disable – disables the component
<b>Synopsis</b>	<b>disable</b> <code>—user</code> <i>admin_user</i> [ <code>—passwordfile</code> <i>filename</i> ] [ <code>—host</code> <i>host_name</i> ] [ <code>—port</code> <i>port_number</i> ] [ <code>—secure —s</code> ] [ <code>—terse=false</code> ] [ <code>—echo=false</code> ] [ <code>—interactive=true</code> ] [ <code>—help</code> ] [ <code>—target</code> <i>target_name</i> ] [ <i>component_name</i> ]
<b>Description</b>	disable immediately disables the named component. The component must have been deployed. If the component has not been deployed, an error message is returned.
<b>Options</b>	<p><code>—u</code> <code>—user</code> The authorized domain application server administrative username.</p> <p><code>—w</code> <code>—password</code> The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.</p> <p><code>—passwordfile</code> This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</p> <p><code>—H</code> <code>—host</code> The machine name where the domain application server is running. The default value is localhost.</p> <p><code>—p</code> <code>—port</code> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><code>—s</code> <code>—secure</code> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><code>—t</code> <code>—terse</code> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p> <p><code>—e</code> <code>—echo</code> Setting to true will echo the command line statement on the standard output. Default is false.</p> <p><code>—I</code> <code>—interactive</code> If set to true (default), only the required password options are prompted.</p>

- `-h` `—help` Displays the help text for the command.
- `—target` In Enterprise Edition, specifies the target on which you are disabling the component. Valid values are
- `server`, which creates the listener for the default server instance `server` and is the default value
  - `cluster_name`, which creates the listener for every server instance in the cluster
  - `instance_name`, which creates the listener for a particular server instance

**Operands** `component_name` name of the component to be disabled.

**Examples** EXAMPLE 1 Using `disable`

```
asadmin> disable --user admin1 --passwordfile password.txt sampleApp  
Command disable executed successfully
```

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [deploy\(1\)](#), [deploydir\(1\)](#), [undeploy\(1\)](#), [enable\(1\)](#)

---

<b>Name</b>	disable-http-lb-application – disables an application managed by a load balancer	
<b>Synopsis</b>	<b>disable-http-lb-application</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>—s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—timeout</b> 30] <b>—name</b> <i>application_name target</i>	
<b>Description</b>	<p>This command disables an application managed by a load balancer. The disabled application goes offline with minimal impact to users. Disabling an application gives a finer granularity of control than disabling a server instance and is most useful when a cluster is hosting multiple independent applications.</p> <p>If an application is deployed across multiple clusters, use this command to disable it in one cluster while leaving it enabled in others.</p> <p>If an application is deployed to a single server instance, use this command to disable it in that instance while leaving the instance itself enabled.</p>	
<b>Options</b>	<b>—u</b> <i>user</i>	The authorized domain application server administrative username.
	<b>—w</b> <i>password</i>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b> <i>filename</i>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASSPASSWORD</b> , and so on.
	<b>—H</b> <i>host</i>	The machine name where the domain application server is running. The default value is localhost.
	<b>—p</b> <i>port</i>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>—s</b> <i>secure</i>	If set to true, uses SSL/TLS to communicate with the domain application server.

<code>-t</code> <code>--terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>--echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>--interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>--help</code>	Displays the help text for the command.
<code>--timeout</code>	The timeout (in minutes) to wait before disabling the specified application. This time allows for a graceful shutdown of the specified application. The default value is 30 minutes.
<code>--name</code>	The name of the application to be disabled.

**Operands** *target*

This operand specifies the server instance or cluster on which to disable the application. Valid values are:

- *cluster\_name*, which disables the application on all server instances in the cluster.
- *instance\_name*, which disables the application on the standalone server instance.

**Examples** EXAMPLE 1 Using the disable-http-lb-server command

```
asadmin> disable-http-lb-application --user admin  
--passwordfile password.txt --name webapps-simple mycluster  
Command disable-http-lb-application executed successfully.
```

**Exit Status**

0	command executed successfully
1	error in executing the command

**See Also** [enable-http-lb-application\(1\)](#)

---

<b>Name</b>	disable-http-lb-server – disables a sever or cluster managed by a load balancer	
<b>Synopsis</b>	<b>disable-http-lb-server</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>—s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—timeout</b> 30] <i>target</i>	
<b>Description</b>	This command disables a server or cluster of servers that a load balancer is managing. The disabled server instance or cluster goes offline with a minimum impact to users.	
<b>Options</b>	<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASSPASSWORD</b> , and so on.
	<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
	<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
	<b>—I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.

`-h` `—help` Displays the help text for the command.

`—timeout` The timeout (in minutes) to wait before disabling the specified target. This time allows for a graceful shutdown of the specified target. The default value is 30 minutes.

**Operands** *target* This operand specifies which server instances and clusters to disable. Valid values are:

- *cluster\_name*, which disables all the server instances in the cluster.
- *instance\_name*, which disables a standalone or clustered server instance.

**Examples** **EXAMPLE 1** Using the `disable-http-lb-server` command

```
asadmin> disable-http-lb-server --user admin --passwordfile filename myserver  
Command disable-http-lb-server executed successfully.
```

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [create-http-lb-ref\(1\)](#), [enable-http-lb-server\(1\)](#)



---

<b>Name</b>	enable – enables the component	
<b>Synopsis</b>	<b>enable</b> <code>--user</code> <i>admin_user</i> [ <code>--passwordfile</code> <i>filename</i> ] [ <code>--host</code> <i>host_name</i> ] [ <code>--port</code> <i>port_number</i> ] [ <code>--secure -s</code> ] [ <code>--terse=false</code> ] [ <code>--echo=false</code> ] [ <code>--interactive=true</code> ] [ <code>--help</code> ] [ <code>--target</code> <i>target_name</i> ] [ <i>component_name</i> ]	
<b>Description</b>	enable command enables the specified component. If the component is already enabled, then it is re-enabled. The component must have been deployed in order to be enabled. If it has not been deployed, then an error message is returned. This command is supported in remote mode only.	
<b>Options</b>	<code>-u</code> <code>--user</code>	The authorized domain application server administrative username.
	<code>-w</code> <code>--password</code>	The <code>--password</code> option is deprecated. Use <code>--passwordfile</code> instead.
	<code>--passwordfile</code>	This option replaces the <code>--password</code> option. Using the <code>--password</code> option on the command line or through the environment is deprecated. The <code>--passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
	<code>-H</code> <code>--host</code>	The machine name where the domain application server is running. The default value is localhost.
	<code>-p</code> <code>--port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<code>-s</code> <code>--secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<code>-t</code> <code>--terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<code>-e</code> <code>--echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.

<code>-I</code> <code>--interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>--help</code>	Displays the help text for the command.
<code>--target</code>	In Enterprise Edition, specifies the target on which you are enabling the component. Valid values are <ul style="list-style-type: none"><li>▪ <code>server</code>, which creates the listener for the default server instance <code>server</code> and is the default value</li><li>▪ <code>cluster_name</code>, which creates the listener for every server instance in the cluster</li><li>▪ <code>instance_name</code>, which creates the listener for a particular server instance</li></ul>

**Operands** *component\_name* name of the component to be enabled.

**Examples** EXAMPLE1 Using `enable`

```
asadmin> enable --user admin1 --passwordfile password.txt sampleApp
Command enable executed successfully
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [deploy\(1\)](#), [deploydir\(1\)](#), [undeploy\(1\)](#), [disable\(1\)](#)

<b>Name</b>	enable-http-lb-application – enables a previously-disabled application managed by a load balancer	
<b>Synopsis</b>	<b>enable-http-lb-application</b> <code>—user admin_user</code> [ <code>—passwordfile filename</code> ] [ <code>—host host_name</code> ] [ <code>—port port_number</code> ] [ <code>—secure -s</code> ] [ <code>—terse=false</code> ] [ <code>—echo=false</code> ] [ <code>—interactive=true</code> ] [ <code>—help</code> ] <code>—name application_name target</code>	
<b>Description</b>	This command enables a previously disabled application managed by a load balancer. You can enable the application on all instances in a cluster, or on a single standalone server instance.	
<b>Options</b>	<code>—u —user</code>	The authorized domain application server administrative username.
	<code>—w —password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
	<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <code>password</code> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
	<code>—H —host</code>	The machine name where the domain application server is running. The default value is localhost.
	<code>—p —port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<code>—s —secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<code>—t —terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<code>—e —echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
	<code>—I —interactive</code>	If set to true (default), only the required password options are prompted.

`-h` `—help` Displays the help text for the command.

`—name` The name of the application to be enabled.

**Operands** *target* This operand specifies on which server instance or cluster to enable the application. Valid values are:

- *cluster\_name*, which enables the application on all server instances in the cluster.
- *instance\_name*, which enables the application in the standalone server instance.

**Examples** **EXAMPLE 1** Using the `enable-http-lb-server` command

```
asadmin> enable-http-lb-application --user admin
--passwordfile password.txt --name webapps-simple mycluster
Command enable-http-lb-application executed successfully.
```

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [disable-http-lb-application\(1\)](#)

---

<b>Name</b>	enable-http-lb-server – enables a previously disabled sever or cluster managed by a load balancer	
<b>Synopsis</b>	<b>enable-http-lb-server</b> <code>—user</code> <i>admin_user</i> [ <code>—passwordfile</code> <i>filename</i> ] [ <code>—host</code> <i>host_name</i> ] [ <code>—port</code> <i>port_number</i> ] [ <code>—secure</code>   <code>—s</code> ] [ <code>—terse</code> = <i>false</i> ] [ <code>—echo</code> = <i>false</i> ] [ <code>—interactive</code> = <i>true</i> ] [ <code>—help</code> ] <i>target</i>	
<b>Description</b>	This command enables a server or cluster of servers that was previously disabled. When a server is enabled, its applications are enabled too.	
<b>Options</b>	<code>—u</code> <code>—user</code>	The authorized domain application server administrative username.
	<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
	<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
	<code>—H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.
	<code>—p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<code>—s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<code>—t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<code>—e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
	<code>—I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.

`-h` `—help`

Displays the help text for the command.

**Operands** *target*

This operand specifies which server instances and clusters to enable. Valid values are:

- *cluster\_name*, which enables all the server instances in the cluster.
- *instance\_name*, which enables a standalone or clustered server instance.

**Examples** **EXAMPLE 1** Using the `enable-http-lb-server` command

```
asadmin> enable-http-lb-server --user admin --passwordfile filename myserver  
Command enable-http-lb-server executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-http-lb-ref\(1\)](#), [disable-http-lb-server\(1\)](#)

- 
- Name** `export` – marks a variable name for automatic export to the environment of subsequent commands in multimode
- Synopsis** `export [ name=value [ name=value] *]`
- Description** Marks a variable name for automatic export to the environment of subsequent commands. All subsequent commands use the variable name values as specified; unless you unset them or exit multimode. If only the variable name is specified, the current value of that variable name is displayed. If the export command is used without any arguments, a list of all the exported variables and their values is displayed. Exported shell environment variables set prior to invoking the `asadmin` utility are imported automatically and set as exported variables within `asadmin`. Unexported environment variables cannot be read by the `asadmin` utility.
- Operands** `name=value` variable name and value for automatic export to the environment to be used by subsequent commands.
- Examples**
- EXAMPLE 1** Using `export` to set an environment variable
- ```
asadmin> export AS_ADMIN_HOST=bluestar
```
- In this case, the `AS_ADMIN_HOST` environment variables has been set to *bluestar*.
- EXAMPLE 2** Using `export` to set multiple environment variables
- ```
asadmin> export AS_ADMIN_HOST=bluestar AS_ADMIN_PORT=8000 AS_ADMIN_USER=admin AS_ADMIN_PREFIX=server1.jms-service
```
- In this case, the environment variables have been set to: the host is *bluestar*, the port is *8000*, the administrator user is *admin*, and the prefix is *server1.jms-service*.
- EXAMPLE 3** Using `export` to list environment variables
- ```
asadmin> export
AS_ADMIN_HOST=bluestar
AS_ADMIN_PORT=8000
AS_ADMIN_USER=admin
AS_ADMIN_PREFIX=server1.jms-service
```
- The `export` with no input lists the set environment variables.
- Exit Status**
- |   |                                |
|---|--------------------------------|
| 0 | command executed successfully  |
| 1 | error in executing the command |
- See Also** `unset(1)`, `multimode(1)`

---

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Name</b>        | export-http-lb-config – exports the load balancer configuration to a file that can be used by the load balancer                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Synopsis</b>    | <b>export-http-lb-config</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] <b>—config</b> <i>config_name</i> [ <i>file_name</i> ]                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Description</b> | Use the export-http-lb-config command to export a load balancer configuration into a file that the load balancer plug-in can use. The default file name is loadbalancer.xml, but you can specify a different name. Once exported, you manually copy the exported file to the load balancer plug-in location before configuration changes are applied.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Options</b>     | <ul style="list-style-type: none"> <li><b>-u</b> <b>—user</b> The authorized domain application server administrative username.</li> <li><b>-w</b> <b>—password</b> The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.</li> <li><b>—passwordfile</b> This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD=<i>password</i>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.</li> <li><b>-H</b> <b>—host</b> The machine name where the domain application server is running. The default value is localhost.</li> <li><b>-p</b> <b>—port</b> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</li> <li><b>-s</b> <b>—secure</b> If set to true, uses SSL/TLS to communicate with the domain application server.</li> <li><b>-t</b> <b>—terse</b> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</li> <li><b>-e</b> <b>—echo</b> Setting to true will echo the command line statement on the standard output. Default is false.</li> </ul> |



|                 |                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-----------------|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>-I</code> | <code>—interactive</code> | If set to true (default), only the required password options are prompted.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>-h</code> | <code>—help</code>        | Displays the help text for the command.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|                 | <code>—config</code>      | Specifies which load balancer configuration to export.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Operands</b> | <i>file_name</i>          | Specifies the file name and location of the exported configuration.<br><br>If you specify a directory (relative or absolute), the file named <code>loadbalancer.xml.load_balancer_config_name</code> is created in that directory. On Microsoft Windows systems the path must be in quotes.<br><br>If you specify a file name in a relative or absolute path, then the file is created with the name you specify.<br><br>If you do not specify this operand, the default value is a file named <code>loadbalancer.xml.load_balancer_config_name</code> created in the <code>app_sever_install/domains/domain_name/generated</code> directory. |

**Examples** EXAMPLE 1 Using the `export-http-lb-config` command on UNIX

The following example exports the load balancing configuration `mycluster-http-lb-config` to a file named `loadbalancer.xml` in the `/Sun/AppServer` directory.

```
asadmin> export-http-lb-config --user admin --passwordfile file
--config mycluster-http-lb-config Sun/AppServer/loadbalancer.xml
Command export-http-lb-config executed successfully.
```

EXAMPLE 2 Using the `export-http-lb-config` command on the Microsoft Windows platform

The following example exports the load balancing configuration `mycluster-http-lb-config` to a file named `loadbalancer.xml` in the `C:\Sun\AppServer` directory on a Microsoft Windows system.

```
asadmin> export-http-lb-config --user admin --passwordfile file
--config mycluster-http-lb-config "C:\Sun\AppServer\loadbalancer.xml"
Command export-http-lb-config executed successfully.
```

|                    |   |                                |
|--------------------|---|--------------------------------|
| <b>Exit Status</b> | 0 | command executed successfully  |
|                    | 1 | error in executing the command |

**See Also** [create-http-lb-config\(1\)](#), [list-http-lb-configs\(1\)](#)

**Name** freeze-transaction-service – freezes the transaction subsystem

**Synopsis** **freeze-transaction-service** `—user` *admin\_user* [`—passwordfile` *filename*]  
 [`—host` *host\_name*] [`—port` *port\_number*] [`—secure`|`—s`] [`—terse`=*false*]  
 [`—echo`=*false*] [`—interactive`=*true*] [`—help`] [`—target` *target\_name*]

**Description** Freezes the transaction subsystem during which time all the inflight transactions are suspended. Invoke this command before rolling back any inflight transactions. Invoking this command on an already frozen transaction subsystem has no effect. This is supported for Enterprise Edition only.

This command is supported in remote mode only.

|                |                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|----------------|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Options</b> | <code>—u</code> <code>—user</code>     | The authorized domain application server administrative username.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|                | <code>—w</code> <code>—password</code> | The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|                | <code>—passwordfile</code>             | This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on. |
|                | <code>—H</code> <code>—host</code>     | The machine name where the domain application server is running. The default value is localhost.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|                | <code>—p</code> <code>—port</code>     | The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|                | <code>—s</code> <code>—secure</code>   | If set to true, uses SSL/TLS to communicate with the domain application server.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|                | <code>—t</code> <code>—terse</code>    | Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|                | <code>—e</code> <code>—echo</code>     | Setting to true will echo the command line statement on the standard output. Default is false.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

---

|                 |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------------|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                 | <code>-I</code> <code>—interactive</code> | If set to true (default), only the required password options are prompted.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|                 | <code>-h</code> <code>—help</code>        | Displays the help text for the command.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Operands</b> | <code>—target</code>                      | specifies the target on which you are freezing the Transaction Service. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, which creates the listener for the default server instance <code>server</code> and is the default value</li> <li>▪ <code>configuration_name</code>, which creates the listener for the named configuration</li> <li>▪ <code>cluster_name</code>, which creates the listener for every server instance in the cluster</li> <li>▪ <code>instance_name</code>, which creates the listener for a particular server instance</li> </ul> |

**Examples** `EXAMPLE 1` Using `freeze-transaction-service`

```
asadmin> freeze-transaction-service --user admin --passwordfile password.txt --target server
```

|                    |   |                                |
|--------------------|---|--------------------------------|
| <b>Exit Status</b> | 0 | command executed successfully  |
|                    | 1 | error in executing the command |

**See Also** [unfreeze-transaction-service\(1\)](#), [rollback-transaction\(1\)](#)

---

**Name** `get` – gets the values of the monitorable or configurable attributes

**Synopsis** `get` `—user` *admin\_user* [`—passwordfile` *filename*] [`—host` *host\_name*]  
 [`—port` *port\_number*] [`—secure`|`-s`] [`—terse`=*false*] [`—echo`=*false*]  
 [`—interactive`=*true*] [`—help`] [`—monitor`=[*true*/*false*]] [*dotted\_attribute\_name*]

**Description** Gets the values of attributes. If the `--monitor` option is set to true, the monitorable attributes are returned. If the `--monitor` option is set to false, the configurable attribute values are returned. On Solaris, quotes are needed when executing commands with `*` as the option value or operand.

**Options**

|                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>-u</code> <code>—user</code>     | The authorized domain application server administrative username.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>-w</code> <code>—password</code> | The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <code>—passwordfile</code>             | This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format:<br><code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on. |
| <code>-H</code> <code>—host</code>     | The machine name where the domain application server is running. The default value is localhost.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <code>-p</code> <code>—port</code>     | The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>-s</code> <code>—secure</code>   | If set to true, uses SSL/TLS to communicate with the domain application server.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>-t</code> <code>—terse</code>    | Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <code>-e</code> <code>—echo</code>     | Setting to true will echo the command line statement on the standard output. Default is false.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

---

|                                           |                                                                                                                                                    |
|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>-I</code> <code>—interactive</code> | If set to true (default), only the required password options are prompted.                                                                         |
| <code>-h</code> <code>—help</code>        | Displays the help text for the command.                                                                                                            |
| <code>--monitor</code>                    | defaults to false; if set to false, the configurable attribute values are returned. If set to true, the monitorable attribute values are returned. |

**Operands** *attributename* attribute name in the dotted notation.

**Examples** EXAMPLE 1 Using `get`

```
asadmin> get --user admin --passwordfile password.txt --host localhost --port 4848
"server.resources.jdbc-resource.jdbc/PointBase.*"
server.resources.jdbc-resource.jdbc/PointBase.description=<null>
server.resources.jdbc-resource.jdbc/PointBase.enabled=true
server.resources.jdbc-resource.jdbc/PointBase.jndi-name=jdbc/PointBase
server.resources.jdbc-resource.jdbc/PointBase.object-type=user
server.resources.jdbc-resource.jdbc/PointBase.pool-name=PointBasePool
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [set\(1\)](#), [list\(1\)](#)

---

**Name** `get-client-stubs` – gets the stubs of the client

**Synopsis** `get-client-stubs` `—user` *admin\_user* [`—passwordfile` *filename*] [`—host` *host\_name*] [`—port` *port\_number*] [`—secure`|`-s`] [`—terse=false`] [`—echo=false`] [`—interactive=true`] [`—help`] [`—target` *target\_name*] [`—apname` *application\_name*] [*local\_directory\_path*]

**Description** Gets the client stubs JAR file for an AppClient standalone module or an application containing the AppClient module, from the server machine to the local directory. This command is supported in remote mode only.

**Options**

|                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>-u</code> <code>—user</code>     | The authorized domain application server administrative username.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <code>-w</code> <code>—password</code> | The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <code>—passwordfile</code>             | This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on. |
| <code>-H</code> <code>—host</code>     | The machine name where the domain application server is running. The default value is localhost.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>-p</code> <code>—port</code>     | The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <code>-s</code> <code>—secure</code>   | If set to true, uses SSL/TLS to communicate with the domain application server.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <code>-t</code> <code>—terse</code>    | Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>-e</code> <code>—echo</code>     | Setting to true will echo the command line statement on the standard output. Default is false.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

---

|                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|----------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>-I</code> <code>—interactive</code>                                  | If set to true (default), only the required password options are prompted.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>-h</code> <code>—help</code>                                         | Displays the help text for the command.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>—target</code>                                                       | In Enterprise Edition, specifies the target on which you are retrieving the client stubs. Valid values are <ul style="list-style-type: none"> <li>▪ <code>server</code>, which creates the listener for the default server instance <code>server</code> and is the default value</li> <li>▪ <code>configuration_name</code>, which creates the listener for the named configuration</li> <li>▪ <code>cluster_name</code>, which creates the listener for every server instance in the cluster</li> <li>▪ <code>instance_name</code>, which creates the listener for a particular server instance</li> </ul> |
| <code>--appname</code>                                                     | name of the application.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Operands</b> <code>local_directory_path</code>                          | path to the local directory where the client stub should be stored.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Examples</b> <code>EXAMPLE 1</code> Using <code>get-client-stubs</code> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|                                                                            | <code>asadmin&gt; get-client-stubs --user admin --passwordfile password.txt --host fuyako --port 7070 --appname myapplication.ear /sample/exmple</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Exit Status</b> <code>0</code>                                          | command executed successfully                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <code>1</code>                                                             | error in executing the command                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>See Also</b> <a href="#">undeploy(1)</a>                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

**Name** hadbm – utility for managing the High Availability Database (HADB)

**Synopsis** **hadbm** *command*

*[-short-option option\_argument | -short-option=option\_argument --long\_option=option\_argument | --operand]\**

**hadbm** *command\_name* **--help** | **hadbm help**

**Description** The hadbm command identifies the operation or task to perform. Commands are case-sensitive. One or more command options can be specified in one of the following formats:

*--option=value*  
*--option value*  
*-short-option value*

Options, like commands, are case-sensitive. Options require argument values except boolean options which toggle to switch a feature ON or OFF. Operands appear after the argument values and are set off by a space or an equal sign (=). Optional options and operands are identified in enclosed square brackets [ ]. For commands that take a database name operand, if a database is not specified, the default database is used. The default database is hadb.

|                 |              |                                                                          |
|-----------------|--------------|--------------------------------------------------------------------------|
| <b>Commands</b> | addnodes     | adds nodes to the named database                                         |
|                 | clear        | reinitializes all the data space on all nodes and starts the database    |
|                 | clearhistory | clears the history files on the database                                 |
|                 | create       | creates a database instance                                              |
|                 | createdomain | creates a management domain of the listed HADB hosts                     |
|                 | delete       | removes the database                                                     |
|                 | deletedomain | deletes the HADB management domain                                       |
|                 | deviceinfo   | displays information about disk storage devices on each active data node |
|                 | disablehost  | selectively disables a host in the management domain                     |
|                 | extenddomain | extends the current HADB management domain                               |
|                 | get          | gets the value of the specified configuration parameter                  |
|                 | help         | displays all the subcommands for the hadbm utility                       |
|                 | list         | lists all the existing databases                                         |
|                 | listdomain   | lists all hosts defined in the management domain                         |
|                 | listpackages | lists the packages registered in the management domain                   |
|                 | reducedomain | removes hosts from the HADB management domain                            |
|                 | refragment   | refragments the schema                                                   |



---

|                       |                                                                                                                            |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------|
| registerpackage       | registers the HADB packages in the management domain                                                                       |
| resourceinfo          | displays database resource information                                                                                     |
| restart               | restarts the database                                                                                                      |
| restartnode           | restarts the specified node                                                                                                |
| set                   | sets the value of the specified configuration attributes to the identified values                                          |
| start                 | starts the database                                                                                                        |
| startnode             | starts the specified node                                                                                                  |
| status                | shows the state of the database                                                                                            |
| stop                  | gracefully stops the database                                                                                              |
| stopnode              | gracefully stops the specified node                                                                                        |
| unregisterpackage     | removes registered HADB packages from the management domain                                                                |
| version               | displays the hadbm version information                                                                                     |
| <b>Common Options</b> |                                                                                                                            |
| -q—quiet              | Performs the operation silently without any descriptive messages.                                                          |
| -?—help               | Displays a brief description of the hadbm utility and all the supported commands.                                          |
| -v—version            | Displays the version details of the hadbm utility.                                                                         |
| -y—yes                | Launches the command in non-interactive mode.                                                                              |
| -f—force              | Launches the command in non-interactive mode, and does not return error if the post condition is already achieved.         |
| -e—echo               | Displays the commands with all the options and their user-defined values or the default values; then launches the command. |

**Name** hadbm addnodes – adds new nodes to the named database, initializes devices for the new nodes, and refragments the schema

**Synopsis** **hadbm addnodes** [**—no-refragment**] [**—spares=spare\_count**] [**—historypath=path**] [**—devicepath=path**] [**—set=attribute\_name\_value\_list**] [**—dbpassword=password** | **—dbpasswordfile=filename**] [**—adminpassword=password** | **—adminpasswordfile=filename**] **—hosts=host\_list** [**dbname**]

**Description** Use the hadbm addnodes command to add new nodes to the named database, initialize the devices for the new nodes, and refragment the schema. The number of spares identified is the number of spares to be allotted from the host list as specified in the **—hosts** option. Hosts must be specified in pairs. All the active nodes in the database should be running when executing the hadbm addnodes command (this means the database has at least FaultTolerant or HAFaultTolerant state). If the database is not specified, the default database is used. The database is restarted without loss of service after adding the nodes.

Refragmentation, though time consuming, is needed to store the data on the newly created nodes. You can elect to perform refragmentation during node creation (default). However, if you have chosen **—no-refragment**, you can refragment later by using the hadbm refragment command. The database is available during refragmentation.

Data devices must have 50% free space to accommodate the old and new copies of the user data during refragmentation.

|                |                             |                                                                                                                                                                                                                                                                                                                                                                                |
|----------------|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Options</b> | <b>—w—adminpassword</b>     | The actual HADBM administration password.                                                                                                                                                                                                                                                                                                                                      |
|                | <b>—W—adminpasswordfile</b> | The file from which the passwords are read.                                                                                                                                                                                                                                                                                                                                    |
|                | <b>—m—agent</b>             | Identifies the URL to the Management Agent(s) (hostlist:port).                                                                                                                                                                                                                                                                                                                 |
|                | <b>—r—no-fragment</b>       | If this option is specified or set to true, refragmentation is not performed on the database after adding the nodes . If the option is not specified, or set to false (default), the database is refragmented after adding the nodes. All tables are refragmented over all nodes; including the new nodes.                                                                     |
|                | <b>—s—spares</b>            | Identifies the number of hosts to be used as spares out of the new nodes that are added.                                                                                                                                                                                                                                                                                       |
|                | <b>—t—historypath</b>       | The path for the database history files.                                                                                                                                                                                                                                                                                                                                       |
|                | <b>—d—devicepath</b>        | The path for the data and log devices. The path to the device must already exist. To set the path differently for each node or device, use the <b>—set</b> option. There are three types of devices: <ul style="list-style-type: none"> <li>■ DataDevice</li> <li>■ NiLogDevice (node internal log device</li> <li>■ RelalgDevice (relational algebra query device)</li> </ul> |

|                                  |                                                                                                                                                                                                                                                                                                                                          |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>-p</b> <b>—dbpassword</b>     | The password string for the system user of the database. The minimum length of the password must be 8 characters. You can identify either the database password, or for higher security, the password file where the password is defined.                                                                                                |
| <b>-P</b> <b>—dbpasswordfile</b> | Identifies the file containing the password to be used for the system user of the database.                                                                                                                                                                                                                                              |
| <b>-S</b> <b>—set</b>            | Identifies the configuration parameters that will be set to the database. Must be specified as a comma-separated list of database configuration attributes in name=value format. See <code>hadbm set</code> command for a list of writable configuration attributes.                                                                     |
| <b>-H</b> <b>—hosts</b>          | A comma-separated list of new host names for the new nodes in the database. Duplicates are allowed; this creates multiple nodes on the same machine with different port numbers. Keep the mirror nodes on separate DRUs for deployment. One node is created for each comma-separated item in the list. The number of nodes must be even. |

If the database is already created with double network configuration, the nodes being added should also support that same configuration. They should have two NIC cards and the `—hosts` option should define the IP addresses for them. See the `hadbm create` command for more details.

**Operands** *dbname* The name of the database. The default database is `hadb`.

**Examples** EXAMPLE 1 Using `addnodes`

```
hadbm addnodes --dbpasswordfile=/home/hadb/dbpfile
--hosts host8,host9 mydatabase
Nodes successfully added to the database
```

EXAMPLE 2 Using `addnodes` with spares identified

```
hadbm addnodes --dbpasswordfile=/home/hadb/dbpfile
--spares=2 --hosts=host8,host9 mydatabase
Nodes successfully added to the database
```

EXAMPLE 3 Using `addnodes` without a password

```
hadbm addnodes --hosts=host7,host8
Please enter password for system user:
Nodes successfully added to the database
```

|                      |                                |
|----------------------|--------------------------------|
| <b>Exit Status</b> 0 | command executed successfully  |
| 1                    | error in executing the command |

|                    |       |                                                                                      |
|--------------------|-------|--------------------------------------------------------------------------------------|
| <b>Error Codes</b> | 22002 | specified database does not exist                                                    |
|                    | 22024 | host unreachable                                                                     |
|                    | 22025 | hosts not added in pairs                                                             |
|                    | 22041 | invalid database state                                                               |
|                    | 22042 | database could not be refragmented (if the option<br>—no - f ragment is not set)     |
|                    | 22043 | specified number of spares could not be allocated                                    |
|                    | 22044 | path on host does not exist                                                          |
|                    | 22045 | path on host needs write permissions                                                 |
|                    | 22046 | database state deteriorated                                                          |
|                    | 22047 | refragmentation cannot be done                                                       |
|                    | 22201 | database not refragmented (warning issued when the option<br>—no - f ragment is set) |

**See Also** [hadbm-clear\(1\)](#), [hadbm-create\(1\)](#), [hadbm-delete\(1\)](#), [hadbm-list\(1\)](#), [hadbm-refragment\(1\)](#), [hadbm-restart\(1\)](#), [hadbm-set\(1\)](#), [hadbm-start\(1\)](#), [hadbm-status\(1\)](#), [hadbm-stop\(1\)](#)

**Name** hadbm clear – reinitializes all the dataspace on all nodes and starts the database

**Synopsis** **hadbm clear** [**—fast**] [**—spares=number\_of\_spares**]  
 [**—adminpassword=password** | **—adminpasswordfile=filename** ]  
 [**—dbpassword=password** | **—dbpasswordfile=filename**] [**—agent=ma\_url**]  
 [*dbname*]

**Description** Use the `hadbm clear` command to reinitialize all the data devices and start the database. The `hadbm clear` command can also be used in the following situations:

- Restarting the database after a disaster. A disaster refers to double failures, where one or more mirror node pairs are down simultaneously. For example, due to a power failure, machine reboot, or some other unforeseen disaster. The `hadbm status` command will indicate a database that is hit by a disaster as “non-functional”.
- The password provided at the time the database was created is lost during clear and the new password given in the `—dbpassword=password` option will be used when accessing the database in the future. The cleared database will be in an HA Fault Tolerant or Fault Tolerant state.

In interactive mode, the `hadbm clear` command prompts for a confirmation before clearing the database.

**Options**

|                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                            |
|----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>-w</code><br><code>—adminpassword</code>     | The actual HADBM administration password.                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>-W</code><br><code>—adminpasswordfile</code> | The file from which the passwords are read.                                                                                                                                                                                                                                                                                                                                                                                |
| <code>-F</code> <code>—fast</code>                 | Use this option to skip device initialization to save time. Do not use if the disk storage device is corrupted. The data devices must be initialized for the first time after the database is created.                                                                                                                                                                                                                     |
| <code>-s</code> <code>—spares</code>               | If specified, identifies the number of spares. The number must be such that there are at least two active nodes. This number of spares must be even and must be less than or equal to the number of active nodes in the database. If not specified, the original number of spare nodes found in the database instance earlier will be preserved. Spare nodes are option, but having two or more ensures high availability. |
| <code>-p</code> <code>—dbpassword</code>           | The password used for the system user of the database. This password must be valid and is expected to be passed in other commands that require data access.                                                                                                                                                                                                                                                                |
| <code>-P</code><br><code>—dbpasswordfile</code>    | Identifies the file containing the password to be used for the system user of the database.                                                                                                                                                                                                                                                                                                                                |
| <code>-m</code> <code>—agent</code>                | Identifies the URL to the Management Agent(s) (hostlist:port).                                                                                                                                                                                                                                                                                                                                                             |

**Operands** *dbname* The name of the database. The default database is `hadb`.

**Examples** EXAMPLE 1 Using clear with the default database

```
hadbm clear
```

```
Type "yes" or "y" to confirm this operation, anything else to cancel: y
Database successfully cleared
```

## EXAMPLE 2 Using clear with a database identified

```
hadbm clear mydatabase
```

```
This command will clear the database.
```

```
Type "yes" or "y" to confirm this operation, anything else to cancel: y
Database successfully cleared
```

**Exit Status** 0 command executed successfully

1 error in executing the command

**Error Codes** 22002 specified database does not exist

22061 database could not be cleared

**See Also** [hadbm-addnodes\(1\)](#), [hadbm-clearhistory\(1\)](#), [hadbm-delete\(1\)](#), [hadbm-list\(1\)](#),  
[hadbm-refragment\(1\)](#), [hadbm-restart\(1\)](#), [hadbm-start\(1\)](#), [hadbm-stop\(1\)](#)

---

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                            |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|
| <b>Name</b>        | hadbm clearhistory – clears the history files on the database                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                            |
| <b>Synopsis</b>    | <b>hadbm clearhistory</b> [ <b>—adminpassword=</b> <i>password</i>   <b>—adminpasswordfile=</b> <i>filename</i> ] [ <b>—saveto=</b> <i>path</i> ] [ <b>—agent=</b> <i>ma_url</i> ] [ <i>dbname</i> ]                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                            |
| <b>Description</b> | Use the hadbm clearhistory command to clear the history files on the database. The directory to which the history files are to be saved must exist and must be writeable. The history file of the named database will be truncated. You can verify by checking the size of the history file. The database state remains unchanged. If a database is identified, it should already exist. If a database is not named, the default database history files are cleared. The default database is hadb.                                                                                                                                          |                                                                            |
|                    | In interactive mode, the hadbm clearhistory command prompts for a confirmation before clearing the history.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                            |
| <b>Options</b>     | <b>-w</b> <b>—adminpassword</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | The actual HADB administration password.                                   |
|                    | <b>-W</b> <b>—adminpasswordfile</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | The file from which the passwords are read.                                |
|                    | <b>-o</b> <b>—saveto</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | The path to where the old history files are to be saved.                   |
|                    | <b>-w</b> <b>—adminpassword</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | The actual HADB administration password.                                   |
|                    | <b>-W</b> <b>—adminpasswordfile</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | The file from which the passwords are read.                                |
|                    | <b>-m</b> <b>—agent</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Identifies the URL to the Management Agent. The default is localhost:1862. |
| <b>Operands</b>    | <i>dbname</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | The name of the database. The default database is hadb.                    |
| <b>Examples</b>    | <p><b>EXAMPLE 1</b> Using clearhistory with a database identified</p> <pre>hadbm clearhistory mydatabase</pre> <p>This command will clear the history file of the database.<br/>Type "yes" or "y" to confirm this operation,<br/>anything else to cancel: y<br/>Database history file successfully cleared</p> <p><b>EXAMPLE 2</b> Using clearhistory with the saveto option</p> <pre>hadbm clearhistory --saveto=/var/tmp mydatabase</pre> <p>This command will clear the history file of the database.<br/>Type "yes" or "y" to confirm this operation,<br/>anything else to cancel: y<br/>Database history file successfully cleared</p> |                                                                            |
| <b>Exit Status</b> | 0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | command executed successfully                                              |
|                    | 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | error in executing the command                                             |
| <b>Error Codes</b> | 22002                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | specified database does not exist                                          |
|                    | 22111                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | directory does not exist                                                   |

22112 specified location is not a directory

22113 directory is not writeable

**See Also** [hadbm-status\(1\)](#), [hadbm-list\(1\)](#), [hadbm-addnodes\(1\)](#), [hadbm-clear\(1\)](#), [hadbm-refragment\(1\)](#), [hadbm-delete\(1\)](#), [hadbm-start\(1\)](#), [hadbm-restart\(1\)](#), [hadbm-stop\(1\)](#)



**Name** hadbm create – creates a database instance

**Synopsis** **hadbm create** [**—package**=*package\_name*] [**—packagepath**=*path*] [**—historypath**=*path*] [**—devicepath**=*path*] [**—datadevices**=*number\_of\_devices\_per\_node*] [**—portbase**=*base\_number*] [**—spares**=*number\_of\_spares*] [**—set**=*attribute\_name\_value\_list*] [**—agent**=*ma\_url*] [**—no-cleanup**] [**—no-clear**] [**—devicesize**=*size*] [**—dbpassword**=*password* | **—dbpasswordfile**=*filename*] [**—adminpassword**=*password* | **—adminpasswordfile**=*filename* | **—no-adminauthentication**] [**—hosts**=*host\_list* [*dbname*]

**Description** The `hadbm create` command creates the specified database in the HADB management domain. The `create` command implicitly maps the `hostlist` to node numbers in the given order (i.e., the first host in the `hostlist` maps to physical node 0). You can specify where to store data devices, log devices, and history files. An HADB instance must have at least two active nodes. The `hostlist` defines which interfaces (IP addresses) the HADB nodes communicates on. If the `hostlist` consists of DNS names, an IP address will be resolved using a resolve mechanism in the management agent.

The database system user will be assigned the password that is supplied in the `—dbpassword` option or the `—dbpasswordfile` option. This password is expected to be passed in other commands that require data access.

All the paths used for the database should exist and should be writeable on the hosts.

If necessary, the `create` command will create or extend the HADB management domain, using the hosts in the `hostlist`. It also registers the HADB software package on all the hosts in the `hostlist` given for the `create` command. If a package has been registered on only some of the hosts in the domain, the `create` command will register the package on the remaining hosts with its current `packagepath`.

Apart from the domain management issues, the `create` command is atomic, and if it fails, all database resources will be cleaned up. To avoid the cleanup, use the `—no-cleanup` option.

**Options**

- `—w` `—adminpassword` The actual HADB administration password.
- `—W` `—adminpasswordfile` The file from which the passwords are read.
- `-k` `—package` The name identifying the software package. If the package is not found, a default package is registered.
- `-L` `—packagepath` Path to the HADB software package. Only used if the package is not registered in the domain. This option is deprecated. Use the `hadbm registerpackage` command to register a package in the domain.
- `-t` `—historypath` The full path to the history files. If the `historypath` option is not specified, the default path is set up by the management agent(s). The management agent uses the entries in the configuration file (`ma.server.dbhistorypath`).

- d** **—devicepath** The path for the data and log devices. The path to the device must already exist. To set the path differently for each node or device, use the **—set** option. There are four types of devices:
- **DataDevice**
  - **NiLogDevice** (node internal log device)
  - **RelAlgDevice** (relational algebra query device)
  - **NoManDevice** (node manager device)
- If the **devicepath** option is not specified, the default path is set up by the management agent(s). The management agent uses the entries in the configuration file (`ma.server.dbdevicepath`).
- a** **—datadevices** The number of data devices. The number must be between 1 and 8, on each node.
- b** **—portbase** The port base number used for node 0. The other nodes are then assigned port number bases in steps of 10 from the number specified here.
- s** **—spares** The number of spares. The number must be less than the length of the host list and at least two active nodes should be there.
- S** **—set** Identifies the configuration parameters that will be set to the database. Must be specified as a comma-separated list of database configuration attributes in `name=value` format.

Use this option to set a different **—devicepath** for each node or each device. The syntax for each `name=value` pair is:

`Node-nodenumber.device-devicenumber.DevicePath=path`

Where: *devicenumber* is only required if the device is a **DataDevice**.

For example: `Node-0.DataDevice-0.DevicePath=/disk0`. Any device path that is not set for a particular node or device defaults to the **—devicepath** value.

The following table identifies the configuration attributes available.

**TABLE 1** Configuration Attributes

| Variable           | Range      | Default |
|--------------------|------------|---------|
| ConnectionTrace    | true/false | false   |
| CoreFile           | true/false | false   |
| DataBufferPoolSize | 16–2047    | 200 MB  |
| DataDeviceSize     | 32–262144  | 1024 MB |

TABLE 1 Configuration Attributes (Continued)

| Variable              | Range            | Default                    |
|-----------------------|------------------|----------------------------|
| DevicePath            | n/a              | n/a                        |
| EagerSessionThreshold | 0-100            | 50 (% of NumberOfSessions) |
| EagerSessionTimeout   | 0-2147483647     | 120 seconds                |
| EventBufferSize       | 0-2097152        | 0 MB                       |
| HistoryPath           | n/a              | n/a                        |
| InternalLogBufferSize | 4-128            | 12 MB                      |
| LogBufferSize         | 4-2047           | 48 MB                      |
| MaxTables             | 100-1100         | 1100                       |
| NumberOfDatadevices   | 1-8              | 1                          |
| NumberOfLocks         | 20000-1073741824 | 50000                      |
| NumberOfSessions      | 1-10000          | 100                        |
| Portbase              | 10000-63000      | 15000                      |
| RelalgDeviceSize      | 32-262144        | 128 MB                     |
| SQLTraceMode          | none/short/full  | none                       |
| SessionTimeout        | 0-214743647      | 1800 seconds               |
| StartRepairDelay      | 0-100000         | 20 seconds                 |
| StatInterval          | 0-600            | 600                        |
| SyslogFacility        | <facility>       | local0                     |
| SyslogLevel           | <level>          | warning                    |
| SyslogPrefix          | <string>         | hadb-<db_name>             |
| TakeoverTime          | 500-16000        | 10000 MS                   |

Valid values for SyslogFacility are:

local0/local1/local2/local3/local4/local5/local7/kern/mail/none

Valid values for SyslogLevel are: info/warning/error/alert/severe/none

Heterogenous attributes:

- Node-<nodeno>.HistoryPath=<path\_to\_history\_files>
- Node-<nodeno>.DevicePath=<default\_path\_for\_devices\_on\_node>
- Node-<nodeno>.<device>.DevicePath=<path\_for\_device\_on\_node>

Where <device> is one of:

- DataDevice-<datadevicenumber>
- RelalgDevice
- NiLogDevice
- NoManDevice

<datadevicenumber> is a number in range of 0 to number of data devices specified in the `—datadevices` option.

|                                        |                                                                                                                                                                                                                                                                                                                                                       |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>-m—agent</code>                  | Identifies the URL to the Management Agent(s) (hostlist:port).                                                                                                                                                                                                                                                                                        |
| <code>—no-cleanup</code>               | Use this option to prevent the deletion of files that are normally deleted (such as the history files, devices, and configuration files) if the <code>create</code> command fails.                                                                                                                                                                    |
| <code>—no-clear</code>                 | By default the database is initialized and started. However, if this option is set, the database processes will not be started, the devices will not be initialized, and you must use the <code>clear</code> command to start the database for the first time.                                                                                        |
| <code>-z—devicesize</code>             | The size of the data devices (specified in MB). This size is applicable on all devices.                                                                                                                                                                                                                                                               |
| <code>-p—dbpassword</code>             | The password string for the system user of the database. The minimum length of the password must be 8 characters. You can identify either the database password, or for higher security, the password file where the password is defined.                                                                                                             |
| <code>-P—dbpasswordfile</code>         | Identifies the file containing the password to be used for the system user of the database.                                                                                                                                                                                                                                                           |
| <code>-w—adminpassword</code>          | The actual HADB administration password.                                                                                                                                                                                                                                                                                                              |
| <code>-W—adminpasswordfile</code>      | The file from which the passwords are read.                                                                                                                                                                                                                                                                                                           |
| <code>-U—no-adminauthentication</code> | Using this option eliminates the need of password identification.                                                                                                                                                                                                                                                                                     |
| <code>-H—hosts</code>                  | A comma-separated list of all the host names or IP addresses used for all the nodes in the database. An HADB Management Agent must be running on each host. Using the IP address is recommended because there is no dependence on DNS lookups. Hostnames must be absolute. Do not use <code>localhost</code> or <code>127.0.0.1</code> as a hostname. |

Configuring an HADB instance with double networks: To make HADB tolerate single network failures, the HADB server machines can be equipped with two NIC cards. The HADB instance must be configured to exploit these cards by specifying both IP addresses of the NIC cards for each node. The first IP

address the HADB considers as “net-0,” the second is set to “net-a.” The syntax for a two-node configuration is:

—hosts=h0a+h0b,h1a+h1b.

- h0a is host-0’s IP address on net-0
- h0b is host-0’s IP address on net-1
- h1a is host-1’s IP address on net-0
- h1b is host-1’s IP address on net-1

All nodes in a database instance must be connected to both networks. It is not allowed to have some nodes connected to both networks while others are connected to only one network. The IP address of each NIC card must be on separate IP subnets.

**Operands** *dbname*                      The name of the database. The default database is hadb.

**Examples** EXAMPLE 1 Using create with two nodes on a single device

The following example creates a database with the default database name hadb with two active nodes, and a single data device. The system prompts you for the password twice. All paths are default paths and must be created before initiating this command.

```
hadbm create --devicesize=256 --hosts=host1,host2
Database successfully created and started
```

EXAMPLE 2 Using create with two nodes on multiple devices

The following example creates a database named mydb with two active nodes, two spare nodes, two devices per node, and a specific port base number for some specific path.

```
hadbm create -H host1,host2 --packagepath=/home/hadb/install
--historypath=/export/home/hadb/history --devicepath =/export/home/hadb/device
--configpath /home/hadb/config --datadevices=2 --portbase=1500
--dbpasswordfile=/home/hadb/dbpfile --spares=2 --devicesize=512
--set "Node-0.DataDevice-0.DevicePath=/disk0 Node-0.DataDevice-0.DevicePath=/disk1" mydb
Database successfully created and started
```

Node 0 gets two data devices: /disk0/mydb.data.0 and /disk1/mydb.data1.1. Since Node 1 is not specified with any specific device path in the —set option, and since the —datadevices option was set to 2, Node 1 gets both devices on the path given in the —devicepath option. The devices for Node 1 are then /export/home/hadb/device/mydb.data.1 and /export/home/hadb/device/mydb.data1.1.

|                    |       |                                |
|--------------------|-------|--------------------------------|
| <b>Exit Status</b> | 0     | command executed successfully  |
|                    | 1     | error in executing the command |
| <b>Error Codes</b> | 22021 | database exists                |
|                    | 22022 | specified path does not exist  |

|       |                                                       |
|-------|-------------------------------------------------------|
| 22023 | specified path does not have write permissions        |
| 22024 | host unreachable                                      |
| 22025 | hosts not added in pairs                              |
| 22026 | database name specified is not valid                  |
| 22027 | port base number is not valid                         |
| 22028 | specified number for data devices cannot be supported |
| 22029 | specified device size cannot be supported             |
| 22030 | specified number of spares could not be allocated     |
| 22031 | attributes are not recognized                         |
| 22032 | password string not valid                             |
| 22033 | invalid value set for attributes                      |

**See Also** [hadbm-clear\(1\)](#), [hadbm-delete\(1\)](#), [hadbm-list\(1\)](#), [hadbm-start\(1\)](#), [hadbm-restart\(1\)](#), [hadbm-status\(1\)](#), [hadbm-stop\(1\)](#)

---

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Name</b>        | hadbm createdomain – creates a management domain of the listed HADB hosts                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Synopsis</b>    | <b>hadbm createdomain</b><br>[—adminpassword= <i>password</i>   —adminpasswordfile= <i>filename</i>   —no-adminauthentication ]<br>[—agent= <i>ma_url</i> ] <i>host_list</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Description</b> | <p>Use the hadbm createdomain command to create the HADB management domains. All the hosts that will be part of the desired domain must be included in the hostlist; including the hosts retrieved through the hadbm listdomaincommand.</p> <p>To form a domain, the hostlist must consist of valid network addresses. After the management domain is successfully completed, all the hosts in the domain are enabled and the management agents are ready to manage databases.</p> <p>The following prerequisites must be met before using the hadbm createdomain command:</p> <ul style="list-style-type: none"> <li>▪ HADB management agents are running on the hosts.</li> <li>▪ The management agents are not members of an existing domain.</li> <li>▪ All the management agents are configured to use the same port.</li> <li>▪ All the management agents can reach each other over UDP, TCP, and with IP multicast.</li> </ul> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Options</b>     | -w—adminpassword<br>-W—adminpasswordfile<br>-w—adminpassword<br><br>-W—adminpasswordfile<br>-U—no-adminauthentication<br><br>-m—agent                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | <p>The actual HADBM administration password.</p> <p>The file from which the passwords are read.</p> <p>The actual HADBM administration password. Using this option with the hadbm createdomain or hadbm create command requires that the password is entered each time any hadbm command is used.</p> <p>The adminpassword is different from the hadbm dbpassword command. You must use both passwords when using the following commands: hadbm create, hadbm addnodes, hadbm refragment.</p> <p>The file from which the passwords are read.</p> <p>Using this option eliminates the need of password identification.</p> <p>Identifies the URL to the Management Agent. The default is localhost:1862.</p> |
| <b>Operands</b>    | <i>host_list</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | A comma-separated list of all the hosts that are part of the Management Agent.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

**Examples** EXAMPLE 1 Creating an HADB management domain

```
hadbm createdomain host1,host2,host3
Domain host1,host2,host3 created
```

**Exit Status** 0 command executed successfully

1 error in executing the command

**Error Codes** 22015 hosts specified in the hostlist contain duplicate host names

22190 a domain with the specified hostlist already exists or the hosts are part of a management domain

22196 the URL used to connect to the management agents spans hosts which are not in the management domain.

**See Also** [hadbm\(1\)](#), [hadbm-create\(1\)](#), [hadbm-listdomain\(1\)](#), [hadbm-extenddomain\(1\)](#), [hadbm-reducedomain\(1\)](#), [hadbm-deletedomain\(1\)](#)



**Name** definedomain – connects to the Management Agent and defines the domain

**Synopsis** **definedomain** [**—remove=***host\_list*]  
 [**—adminpassword=***password* | **—adminpasswordfile=***filename* | **—no-adminauthentication** ]  
 [**—javahome=***JAVA\_HOME*] [**—agent=***HADBM\_agent*] *host\_list*

**Description** Before you can define a domain, ensure that the Management Agents are running on the hosts constituting the domain. Refer to the `ma` command to run the Management Agent. All agents must be listening for client connections on the same port. The Management Agent maintains a domain of hosts to communicate with. When you first define a domain, the listed hosts form a domain by initializing the internal communication channels and the internal persistent configuration store. On later redefinitions of the domain, adding or deleting hosts from the domain, the whole desired domain must be included in the host list. You can identify the current hosts on a domain by using the `listdomain` command. When adding new hosts to the domain, the new hosts must be included in the host list along with the hosts in the current domain. When removing hosts from the domain, the hosts to be dropped should be listed in the list for the `—remove` option, not in the desired domain list. A host which is in use by a database instance, or has a software package which is in use by a database instance, cannot be removed from the domain.

Use the `definedomain` command to plan large deployments. It allows you to add any number of hosts to the management domain without actually creating a database instance.

|                |                                        |                                                                                                                                                                                                                                                                                                     |
|----------------|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Options</b> | <code>—remove</code>                   | A comma-separated list of each host you wish to remove from the previously defined domain.                                                                                                                                                                                                          |
|                | <code>—w—adminpassword</code>          | The actual HADBM administration password as defined in the environment variables of the Management Agent.                                                                                                                                                                                           |
|                | <code>—W—adminpasswordfile</code>      | The file containing the HADBM administration password and defined in your environment variables of the Management Agent. The administration password should be defined in the following form:<br>HADBM_ADMINPASSWORD= <i>password</i> . Where <i>password</i> is the actual administrator password. |
|                | <code>—U—no-adminauthentication</code> | Using this option eliminates the need of password identification.                                                                                                                                                                                                                                   |
|                | <code>—javahome</code>                 | The full path to the Java runtime installation. The default value is the value of the <code>JAVA_HOME</code> variable.                                                                                                                                                                              |
|                | <code>—agent</code>                    | Use this option in place of the <code>HADBM_AGENT</code> variable set in your environment or to override the existing set variable. The value for this option must be in the form of <i>host_list:port_number</i> . Where the <i>host_list</i> is a comma separated list of hosts.                  |

**Operands** *host\_list*                    A comma-separated list of each host defined in your domain which is running the Management Agent. By default, it connects to the first listed host, if unavailable it will continue until an active agent is found.

**Examples** **EXAMPLE 1** Using the hadbm-definedomain to create a new domain

The following command defines a new domain including HostA and HostB.

```
hadbm definedomain HostA,HostB
```

**EXAMPLE 2** Using the hadbm-definedomain to add hosts to an existing domain

The following command adds HostC and HostD to an already existing domain.

```
hadbm> definedomain HostA,HostB,HostC,HostD
```

When adding hosts to a domain, all hosts in the current domain and the new hosts must be listed.

**EXAMPLE 3** Using the hadbm-definedomain to remove hosts from an existing domain

The following command removes HostD from the existing domain.

```
hadbm> definedomain --remove=HostD HostA,HostB,HostC
```

A host which is in use by a database instance, or has a software package which is in use by a database instance, cannot be removed from the domain.

**Exit Status**    0                                    command executed successfully  
                  1                                    error in executing the command

**See Also**    [hadbm-create\(1\)](#), [hadbm-listdomain\(1\)](#)

- Name** hadbm delete – removes the database
- Synopsis** **hadbm delete** [`--adminpassword=password` | `--adminpasswordfile=filename` ] [`--agent=ma_url`] [*dbname*]
- Description** Use the hadbm delete command to remove the database, configuration files, device files, history and log files. If a database is identified, it should already exist and should be in a stopped state. If a database is not named, the default database is used. The default database is hadb.
- In interactive mode, the hadbm delete command prompts for a confirmation before removing the database.
- Options**
- |                 |                                  |                                                                            |
|-----------------|----------------------------------|----------------------------------------------------------------------------|
| <code>-w</code> | <code>--adminpassword</code>     | The actual HADB administration password.                                   |
| <code>-W</code> | <code>--adminpasswordfile</code> | The file from which the passwords are read.                                |
| <code>-m</code> | <code>--agent</code>             | Identifies the URL to the Management Agent. The default is localhost:1862. |
- Operands** *dbname*                      The name of the database. The default database is hadb.
- Examples**
- EXAMPLE 1** Using delete
- ```
hadbm delete
This command will remove the database and all configuration,
history and log files. Type "yes" or "y" to confirm this
operation, anything else to cancel: y
Database successfully deleted
```
- EXAMPLE 2** Using delete with a database identified
- ```
hadbm delete mydatabase
This command will remove the database and all configuration,
history and log files. Type "yes" or "y" to confirm this
operation, anything else to cancel: y
Database successfully deleted
```
- Exit Status**
- |   |                                |
|---|--------------------------------|
| 0 | command executed successfully  |
| 1 | error in executing the command |
- Error Codes**
- |       |                                   |
|-------|-----------------------------------|
| 22002 | specified database does not exist |
| 22065 | database not in a stopped state   |
| 22066 | database could not be removed     |
- See Also** [hadbm-addnodes\(1\)](#), [hadbm-clear\(1\)](#), [hadbm-create\(1\)](#), [hadbm-list\(1\)](#), [hadbm-refragment\(1\)](#), [hadbm-restart\(1\)](#), [hadbm-start\(1\)](#), [hadbm-status\(1\)](#), [hadbm-stop\(1\)](#)

**Name** hadbm deletedomain – removes the HADB management domain

**Synopsis** **hadbm deletedomain** [`—adminpassword=password` | `—adminpasswordfile=filename` ]  
`[—agent=ma_url]`

**Description** Before using the hadbm deletedomain command, the following prerequisites must be met:

- An HADB management domain must already exist
- All agents in the domain must be running
- No databases exist in the domain

After successfully executing , the hadbm deletedomain command, the management agents of the removed hosts are stopped, and the repository of the deleted hosts is cleaned up. If the agents are restarted, they will not be part of any domain. To have the restarted agents associated with a domain, create a new management domain using the hadbm createdomain command.

**Options**

|                                   |                                                                            |
|-----------------------------------|----------------------------------------------------------------------------|
| <code>-w—adminpassword</code>     | The actual HADB administration password.                                   |
| <code>-W—adminpasswordfile</code> | The file from which the passwords are read.                                |
| <code>-m—agent</code>             | Identifies the URL to the Management Agent. The default is localhost:1862. |

**Examples** EXAMPLE 1 Deleting the Management Domain

```
hadbm deletedomain
This command will delete the domain host1,host2,host3.
Type "yes" or "y" to confirm this
operation, anything else to cancel: y
Domain hostlist has been deleted.
```

**Exit Status**

|   |                                |
|---|--------------------------------|
| 0 | command executed successfully  |
| 1 | error in executing the command |

**Error Codes**

|       |                                                                                                 |
|-------|-------------------------------------------------------------------------------------------------|
| 22192 | the management domain does not exist                                                            |
| 22194 | hosts cannot be removed because they contain databases                                          |
| 22196 | the URL used to connect to management agents spans hosts which are not in the management domain |

**See Also** [hadbm\(1\)](#), [hadbm-create\(1\)](#), [hadbm-createdomain\(1\)](#), [hadbm-extenddomain\(1\)](#), [hadbm-listdomain\(1\)](#), [hadbm-reducedomain\(1\)](#)

**Name** hadbm deviceinfo – displays information about disk storage devices on each active data node

**Synopsis** **hadbm deviceinfo** [**—details**]  
 [**—adminpassword=password** | **—adminpasswordfile=filename**] [**—agent=ma\_url**]  
 [**dbname**]

**Description** If a database is specified, the database should be existing as shown by the `hadbm-list` command. If the database name is not specified, the default database should exist as shown by the `hadbm-list` command.

The information displayed for each node of the database is:

- total device size allocated in MB
- free size in MB
- usage in percentage

The status of the database and the nodes are not changed.

**Options**

|                                     |                                                                            |
|-------------------------------------|----------------------------------------------------------------------------|
| <b>-d</b> <b>—details</b>           | This option displays detailed information about the named database.        |
| <b>-w</b> <b>—adminpassword</b>     | The actual HADBM administration password.                                  |
| <b>-W</b> <b>—adminpasswordfile</b> | The file from which the passwords are read.                                |
| <b>-m</b> <b>—agent</b>             | Identifies the URL to the Management Agent. The default is localhost:1862. |

**Operands** *dbname*                      The name of the database. The default database is hadb.

**Examples** **EXAMPLE 1** Using deviceinfo without any options

```
hadbm deviceinfo
NodeNo    TotalSize    Freesize    Usage
3         1048         869         17%
4         1048         869         17%
5         1048         869         17%
6         1048         869         17%
```

**EXAMPLE 2** Using deviceinfo with a database specified and quiet option

```
hadbm deviceinfo -q mydatabase
3         1048         869         17%
4         1048         869         17%
5         1048         869         17%
6         1048         869         17%
```

**EXAMPLE 3** Using deviceinfo with details option

```
hadbm deviceinfo --details
NodeNo    TotalSize    FreeSize    Usage    NReads    Nwrites    DeviceName
3         1048         869         17%      0          42578     /export/home2/tmp//hadb.data
```

**EXAMPLE 3** Using deviceinfo with details option *(Continued)*

|   |      |     |     |   |       |                                  |
|---|------|-----|-----|---|-------|----------------------------------|
| 4 | 1048 | 869 | 17% | 0 | 42554 | /export/home2/tmp//hadb.data-0.4 |
| 5 | 1048 | 869 | 17% | 0 | 42544 | /export/home2/tmp//hadb.data-0.5 |
| 6 | 1048 | 869 | 17% | 0 | 9828  | /export/home2/tmp//hadb.data-0.6 |

**Exit Status** 0 command executed successfully

1 error in executing the command

**Error Codes** 22002 specified database does not exist

**See Also** [hadbm-resourceinfo\(1\)](#)

- 
- Name** hadbm disablehost – selectively disables a host in the management domain
- Synopsis** **hadbm disablehost** [`—adminpassword=password` | `—adminpasswordfile=filename` ] [`—agent=ma_url`] *hostname*
- Description** Use the `disablehost` command to remove an unresponsive host from the management domain. Since the majority of management agents in a management domain must be enabled and running to execute HADB management commands, unresponsive hosts reduce the number of active agents and therefore prevent operation of `hadbm` commands.
- A disabled host is automatically re-enabled when its management agent is restarted.
- Before using the `disablehost` command, ensure the host to be disabled is:
- registered in the management domain
  - enabled
  - the management agent for the host is not running
  - all database nodes configured to run on the host are stopped
- Options**
- |                                   |                                                                            |
|-----------------------------------|----------------------------------------------------------------------------|
| <code>-w—adminpassword</code>     | The actual HADBM administration password.                                  |
| <code>-W—adminpasswordfile</code> | The file from which the passwords are read.                                |
| <code>-m—agent</code>             | Identifies the URL to the Management Agent. The default is localhost:1862. |
- Operands** *hostname*            The hostname for the host to be disabled.
- Examples** **EXAMPLE 1** Disabling a host named host1
- ```
hadbm disablehost host1
Host successfully disabled
```
- Exit Status**
- |   |                                |
|---|--------------------------------|
| 0 | command executed successfully  |
| 1 | error in executing the command |
- Error Codes**
- |       |   |
|-------|---|
| 22176 | the host is not registered in the HADB management domain  |
| 22180 | the host is already disabled  |
| 22181 | database nodes are running on the host. Use <code>hadbm stopnode</code> to stop the nodes before using <code>disablehost</code> |
| 22182 | the management agent is running on the specified host. Stop the management agent before disabling the host                      |
- See Also** [hadbm\(1\)](#), [hadbm-create\(1\)](#), [hadbm-listpackages\(1\)](#), [hadbm-unregisterpackage\(1\)](#)

**Name** hadbm extenddomain – extends the current HADB management domain by adding the specified hosts

**Synopsis** **hadbm extenddomain** [**—adminpassword=***password* | **—adminpasswordfile=***filename* ] [**—agent=***ma\_url*] *host\_list*

**Description** Use the hadbm extenddomain command to add hosts to an existing management domain. All the hosts that will be part of the desired domain must be included in the hostlist. The following prerequisites must be met before using the hadbm extenddomain command:

- An HADB management domain must already exist.
- HADB management agents are running on the hosts.
- The management agents on the hosts to be added are not members of an existing domain.
- All the management agents are configured to use the same port.
- All the management agents can reach each other over UDP, TCP, and with IP multicast.

**Options**

<b>-w</b> <b>—adminpassword</b>	The actual HADBM administration password.
<b>-W</b> <b>—adminpasswordfile</b>	The file from which the passwords are read.
<b>-m</b> <b>—agent</b>	Identifies the URL to the Management Agent. The default is localhost:1862.

**Operands** *host\_list* A comma-separated list of all the hosts that are part of the management domain.

**Examples** **EXAMPLE 1** Adding hosts to an HADB management domain

```
hadbm extenddomain host4,host5,
Hosts added, domain is now host1,host2,host3,host4,host5
```

**Exit Status**

0	command executed successfully
1	error in executing the command

**Error Codes**

22015	the hostlist contains duplicate host names
22016	the host 3 and host 4 are registered in different management domains. Domains cannot be merged. Use hadbm reducedomain to remove one of the hosts from a domain and then restart the agent
22191	the specified hosts are already part of the management domain
22192	the management domain does not exist
22196	the URL used to connect to management agents spans hosts which are not in the management domain

**See Also** [hadbm\(1\)](#), [hadbm-create\(1\)](#), [hadbm-createdomain\(1\)](#), [hadbm-deletedomain\(1\)](#), [hadbm-listdomain\(1\)](#), [hadbm-reducedomain\(1\)](#)



**Name** hadbm-get – gets the value of the specified configuration attribute

**Synopsis** **hadbm get** `—all` | *attribute\_name\_list*  
`[—adminpassword=password | —adminpasswordfile=filename ] [—agent=ma_url]`  
`[dbname]`

**Description** Use the get command to get the value of the named configuration attribute. If the command is run without any attributes, and with the `—all` option, all the supported variables and their values are retrieved. If an attribute is unrecognized, an exception is thrown on the unrecognized attribute name, and the variables and values of the recognized attributes are returned.

The readable configuration attributes are as follows:

Variable	Range	Default
ConnectionTrace	ture/false	false
CoreFile	true/false	false
DatabaseName		hadb
DataBufferPoolSize	16–2047	200 MB
DataDeviceSize	32–262144	1024 MB
DevicePath	n/a	n/a
EagerSessionThreshold	0–100	50 (% of NumberOfSessions)
Eager SessionTimeout	0–2147483647	120 seconds
EventBufferSize	0–2097152	0 MB
HistoryPath	n/a	n/a
InternalLogBufferSize	4–128	12 MB
JdbcUrl	n/a	n/a
LogBufferSize	4–2047	48 MB
MaxTables	100–1100	1100
NumberOfDataDevices	1–8	1
NumberOfLocks	20000–1073741824	50000
NumberOfSessions	1–10000	100
PackageName	n/a	V4.x.x.x
PortBase	10000–63000	15000
RelalgDeviceSize	32–262144	128 MB

Variable	Range	Default
SQLTraceMode	none/short/full	none
SessionTimeout	0–2147483647	1800 seconds
StartRepairDelay	0–100000	20 seconds
StatInterval	0–600	600 seconds
SyslogFacility	<facility>	local0
SyslogLevel	<level>	warning
SyslogPrefix	<string>	hadb-<db_name>
TakeoverTime	500–16000	10000 MS

Heterogenous attributes:

- Node-<nodeno>.HistoryPath=<path\_to\_history\_files>
- Node-<nodeno>.DevicePath=<default\_path\_for\_devices\_on\_node>
- Node-<nodeno>.<device>.DevicePath=<path\_for\_device\_on\_node>

Where <device> is one of:

- DataDevice-<datadevicenumber>
- RelalgDevice
- NiLogDevice
- NoManDevice

<b>Options</b>	<code>—all</code>	If specified, gets all the supported variables and their values.
	<code>—w—adminpassword</code>	The actual HADBM administration password.
	<code>—W—adminpasswordfile</code>	The file from which the passwords are read.
	<code>—m—agent</code>	Identifies the URL to the Management Agent. The default is localhost:1862.
<b>Operands</b>	<i>attribute_name_list</i>	A comma or space separated list of variables whose values have been retrieved.
	<i>dbname</i>	The name of the database. The default database is hadb.

**Examples** EXAMPLE 1 Using get

```
hadbm get "takeoverTime numberOfLocks jdbcURL" mydatabase
Attribute      Value
takeoverTime   10000
numberOfLocks  10000
JdbcUrl        com:sun:hadb:royal:15000,polo:15020
```

**Exit Status** 0                    command executed successfully  
                  1                    error in executing the command

**Error Codes** 22002                specified database does not exist  
                  22071                attribute names are not recognized

**See Also** [hadbm-addnodes\(1\)](#), [hadb-clear\(1\)](#), [hadbm-delete\(1\)](#), [hadb-list\(1\)](#), [hadbm-refragment\(1\)](#),  
[hadbm-restart\(1\)](#), [hadbm-set\(1\)](#), [hadbm-start\(1\)](#), [hadbm-stop\(1\)](#)

**Name** hadbm help – displays a list of all the subcommands to administer HADB

**Synopsis** **hadbm help** or hadbm *command\_name* —help

**Description** The following is a list of all the hadbm subcommands:

addnodes	adds nodes to the named database
clear	reinitializes all the data space on all nodes and starts the database
clearhistory	clears the history files on the database
create	creates a database instance
createdomain	creates a management domain of the listed HADB hosts
delete	removes the database
deletedomain	deletes the HADB management domain
deviceinfo	displays information about disk storage devices on each active data node
disablehost	selectively disables a host in the management domain
extenddomain	extends the current HADB management domain
get	gets the value of the specified configuration parameter
help	displays all the subcommands for the hadbm utility
list	lists all the existing databases
listdomain	lists all hosts defined in the management domain
listpackages	lists the packages registered in the management domain
reducedomain	removes hosts from the HADB management domain
refragment	refragments the schema
registerpackage	registers the HADB packages in the management domain
resourceinfo	displays database resource information
restart	restarts the database
restartnode	restarts the specified node
set	sets the value of the specified configuration attributes to the identified values
start	starts the database
startnode	starts the specified node
status	shows the state of the database
stop	gracefully stops the database
stopnode	gracefully stops the specified node

`unregisterpackage` removes registered HADB packages from the management domain

`version` displays the hadbm version information

**Common Options**

- `-q`—quiet Performs the operation silently without any descriptive messages.
- `-?`—help Displays a brief description of the hadbm utility and all the supported commands.
- `-v`—version Displays the version details of the hadbm utility.
- `-y`—yes Launches the command in non-interactive mode.
- `-f`—force Launches the command in non-interactive mode, and does not return an error if the post condition is already achieved.
- `-e`—echo Displays the commands with all the options and their user-defined values or the default values; then launches the command.

**Examples** EXAMPLE 1 Executing an hadbm command

```
hadbm clear
This command will clear the database
Type "yes" or "y" to confirm this operation, anything else to cancel: y
Database successfully cleared
```

**Exit Status**

0	command executed successfully
1	error in executing the command

**See Also** [hadbm\(1m\)](#)

**Name** hadbm list – lists all the existing databases

**Synopsis** **hadbm list** [`—adminpassword=password` | `—adminpasswordfile=filename` ]  
`[—agent=ma_url]`

**Description** Use the `hadbm list` command to get a listing of all the existing database instances known to the management client running this command. If the list could not display the database instance, see the `hadbm` command if you are sure you have created it earlier.

<b>Options</b>	<code>—w—adminpassword</code>	The actual HADB <sup>™</sup> administration password. Using this option with the <code>hadbm createdomain</code> or <code>hadbm create</code> command requires that the password is entered each time any <code>hadbm</code> command is used.
		The <code>adminpassword</code> is different from the <code>hadbm dbpassword</code> command. You must use both passwords when using the following commands: <code>hadbm create</code> , <code>hadbm addnodes</code> , <code>hadbm refragment</code> .
	<code>—W—adminpasswordfile</code>	The file from which the passwords are read..
	<code>—m—agent</code>	Identifies the URL to the Management Agent. The default is <code>localhost:1862</code> .

**Examples** EXAMPLE 1 Using list

```
hadbm list
Database
hadb
mydatabase
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>Error Codes</b>	22002	specified database does not exist

**See Also** [hadbm-clear\(1\)](#), [hadbm-clearhistory\(1\)](#), [hadbm-delete\(1\)](#), [hadbm-get\(1\)](#), [hadbm-restart\(1\)](#), [hadbm-resourceinfo\(1\)](#), [hadbm-set\(1\)](#), [hadbm-start\(1\)](#), [hadbm-stop\(1\)](#)

- 
- Name** hadbm listdomain – lists all hosts defined in the management domain
- Synopsis** **hadbm listdomain** [**—adminpassword=***password* | **—adminpasswordfile=***filename* ]  
**[—agent=***ma\_url***]**
- Description** Use the hadbm listdomain command to list all hosts defined in the management domain and the status of the management agents.
- Options**
- |                                     |  |
|-------------------------------------|--|
| <b>—w</b> <b>—adminpassword</b>     | The actual HADBМ administration password. Using this option with the hadbm createdomain or hadbm create command requires that the password is entered each time any hadbm command is used. |
| <b>—W</b> <b>—adminpasswordfile</b> | The adminpassword is different from the hadbm dbpassword command. You must use both passwords when using the following commands: hadbm create, hadbm addnodes, hadbm refragment.           |
| <b>—m</b> <b>—agent</b>             | The file from which the passwords are read. Identifies the URL to the Management Agent. The default is localhost:1862.   |
- Examples** **EXAMPLE 1** Using the hadbm-listdomain
- The following command lists all participating members of a previously created domain.
- ```
hadbm listdomain
Hostname    Enabled?   Interfaces
HostA      Yes       10.0.5.70
HostB      Yes       10.0.5.72
HostC      Yes       10.0.5.73
HostD      Yes       10.0.5.74
```
- Exit Status**
- |   |                                |
|---|--------------------------------|
| 0 | command executed successfully  |
| 1 | error in executing the command |
- See Also** hadbm-create(1), hadbm-createdomain(1), hadbm-deletedomain(1), hadbm-extenddomain(1), hadbm-reducedomain(1)

**Name** hadbm listpackages – lists the packages registered in the management domain

**Synopsis** **hadbm listpackages** [`—adminpassword=password` | `—adminpasswordfile=filename` ]  
`[—agent=ma_url]`

**Description** Use the listpackages command to display a list of the packages registered in the management domain and the hosts to which they are registered.

|                |                                   |                                                                                                                                                                                            |
|----------------|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Options</b> | <code>—w—adminpassword</code>     | The actual HADBM administration password. Using this option with the hadbm createdomain or hadbm create command requires that the password is entered each time any hadbm command is used. |
|                |                                   | The adminpassword is different from the hadbm dbpassword command. You must use both passwords when using the following commands: hadbm create, hadbm addnodes, hadbm refragment.           |
|                | <code>—W—adminpasswordfile</code> | The file from which the passwords are read.                                                                                                                                                |
|                | <code>—m—agent</code>             | Identifies the URL to the Management Agent. The default is localhost:1862.                                                                                                                 |

**Examples** EXAMPLE 1 Using the hadbm-listpackages

```
hadbm listpackages
Package   Hosts
V4.4     HostA,HostB,HostC,HostD
```

|                    |   |                                |
|--------------------|---|--------------------------------|
| <b>Exit Status</b> | 0 | command executed successfully  |
|                    | 1 | error in executing the command |

**See Also** [hadbm\(1m\)](#), [hadbm-create\(1\)](#), [hadbm-registerpackage\(1\)](#), [hadbm-unregisterpackage\(1\)](#)



**Name** ma – configures and starts the HADB Management Agent

**Synopsis** **ma** *HADB\_install\_path/bin/ma* [`—define=assignment`] [`—javahome=JAVA_HOME`] [`—systemroot=root_path`] [`—version`] [`—help`] [`—install`] [`—remove`] [`—service`] [`—name=name_of_service`] [*AGENT\_CONFIG\_path*]

**Description** Use the `ma` command to configure and start the HADB Management Agent on a host that will belong to an HADB management domain. The configuration is defined in the `AGENT_CONFIG` file. In addition you can register the Management Agent as a Windows service by using the service options `—install`, `—service`, and `—name`. The Management Agent ensures the availability of the HADB nodes on the host it runs by restarting them if there is a failure during startup, or during normal operation. To ensure the availability of the Management Agent you should register it as a Windows service so it is restarted automatically if it fails or when the computer reboots.

An HADB management domain consists of a set of hosts that are capable of running HADB database nodes. A Management Agent runs on each host belonging to a management domain. `hadbm` management clients communicate with Management Agents to perform the `hadbm` management commands like `create`, `start`, `stop`, and so on.

The Management Agent must be configured and started on all hosts before a database instance can be created. All hosts in a domain run a Management Agent at the same port number. All agents are aware of each other and their participation in the management domain. Agents communicate with each other, and may forward requests to other agents when they perform management commands specific to a host. For example, when an agent is requested to stop a node, it checks whether the mirror host is up and running. To get that information, it communicates with the agent running on the mirror host.

The Management Agent maintains a repository where the database configuration is stored. A majority of agents in the management domain must be available to make changes in the repository.

The `AGENT_CONFIG` file contains the configuration information for the Management Agent. A sample file named `mgt.cfg` is located in the `HADB_install_path/lib` directory. Use this sample file to assist you in defining your configuration files. In addition to the configuration variables, the `AGENT_CONFIG` file also contains the default path information for the history files, and the data device files for the HADB instances managed by this agent. If you have NOT specified the history and device path information using the `create` command, the default values located in the `AGENT_CONFIG` file will be used.

**Options** The following options identify common setup information for the Management Agent:

|                                          |                                                                                                                        |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <code>-D</code> <code>—define</code>     | The agent property assignment in the format of <i>property=value</i>                                                   |
| <code>-j</code> <code>—javahome</code>   | The full path to the Java runtime installation. The default value is the value of the <code>JAVA_HOME</code> variable. |
| <code>-y</code> <code>—systemroot</code> | An alternate specification of the Windows system root path.                                                            |
| <code>-V</code> <code>—version</code>    | Displays the version information and exits.                                                                            |
| <code>-?</code> <code>—help</code>       | Displays this help page and exits.                                                                                     |

The following options identify service configuration information for the Management Agent:

|                                       |                                                                                                          |
|---------------------------------------|----------------------------------------------------------------------------------------------------------|
| <code>-i</code> <code>—install</code> | Registers a service for the agent and starts the service.                                                |
| <code>-r</code> <code>—remove</code>  | Stops and unregisters the agent service.                                                                 |
| <code>-s</code> <code>—service</code> | This option is for internal use by the service control program.                                          |
| <code>-n</code> <code>—name</code>    | Identifies the name to use when registering and operating the service. The default name is HADBMgrAgent. |

**Operands** *AGENT\_CONFIG\_path*      The full path to the AGENT\_CONFIG file.

**Examples** EXAMPLE 1 Sample AGENT\_CONFIG file

The following sample file can be edited for your particular installation:

```
ma.server.jmxmp.port=31108 #this can be any port not currently being used#
ma.server.dbconfigpath=/etc/opt/SUNWhadb/MA
repository.dr.path=/var/opt/SUNWhadb/REP
```

**Exit Status** 0      command executed successfully

1      error in executing the command

**Error Codes** 0      error message

1      error message

**See Also** [hadbm\(1m\)](#)

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                 |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| <b>Name</b>        | hadbm reducedomain – removes hosts from the HADB management domain                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                 |
| <b>Synopsis</b>    | <b>hadbm reducedomain</b> [ <b>—adminpassword=</b> <i>password</i>   <b>—adminpasswordfile=</b> <i>filename</i> ] [ <b>—agent=</b> <i>ma_url</i> ] <i>host_list</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                 |
| <b>Description</b> | <p>The following prerequisites must be met before using the hadbm reducedomain command:</p> <ul style="list-style-type: none"> <li>▪ An HADB management domain must already exist.</li> <li>▪ The hosts to be removed are registered in the domain. No database nodes are configured to be used on the hosts to be removed.</li> <li>▪ The HADB management repository is writable.</li> <li>▪ Software packages that are in use are not registered on the hosts which are to be removed.</li> <li>▪ The hostlist must not contain all agents in the domain. To remove all agents, use the hadbm deletedomain command.</li> </ul> <p>After successfully executing the hadbm reducedomain command, the management agents of the removed hosts are stopped and the repository of the deleted hosts is cleaned up.</p> |                                                                                                 |
| <b>Options</b>     | <b>—w—adminpassword</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | The actual HADBM administration password.                                                       |
|                    | <b>—W—adminpasswordfile</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | The file from which the passwords are read.                                                     |
|                    | <b>—m—agent</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Identifies the URL to the Management Agent. The default is localhost:1862.                      |
| <b>Operands</b>    | <i>host_list</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | A comma-separated list of all the hosts that are part of the management domain.                 |
| <b>Examples</b>    | <p><b>EXAMPLE 1</b> Removing hosts from a management domain</p> <pre>hadbm reducedomain host4,host5</pre> <p>Hosts removed, domain is now host1,host2,host3</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                 |
| <b>Exit Status</b> | 0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | command executed successfully                                                                   |
|                    | 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | error in executing the command                                                                  |
| <b>Error Codes</b> | 22015                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | the hostlist contains duplicate host names                                                      |
|                    | 22192                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | the management domain does not exist                                                            |
|                    | 22193                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | the specified hosts are not part of the domain and cannot be removed                            |
|                    | 22194                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | hosts cannot be removed because they contain databases                                          |
|                    | 22195                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | cannot remove all hosts from the domain                                                         |
|                    | 22196                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | the URL used to connect to management agents spans hosts which are not in the management domain |

**See Also** [hadbm\(1m\)](#), [hadbm-create\(1\)](#), [hadbm-createdomain\(1\)](#), [hadbm-deletedomain\(1\)](#),  
[hadbm-extenddomain\(1\)](#), [hadbm-listdomain\(1\)](#)

**Name** hadbm refagment – refragments the database schema

**Synopsis** **hadbm refagment** [**—dbpassword=***password* | **—passwordfile=***passwordfilename* ] [**—adminpassword=***password* | **—adminpasswordfile=***filename* ] [**—agent=***ma\_url*] [*dbname*]

**Description** Refragmentation is needed to store the data on a newly created node. Run the hadbm refagment command after adding a node using the hadbm addnodes command with the **—no-refagment** option specified. If the hadbm refagment command fails, it can be retried. If it continues to fail, the database must be cleared, and the product-specific schemas must be reloaded. All the user tables are refragmented.

If a database is specified, the database must already exist and must be in an HA Fault Tolerant or Fault Tolerant state. If the database is not named, the default database is refragmented. The default database is hadb.

In interactive mode, the hadbm refagment command prompts for a confirmation before refragmenting the data.

**Options**

|                                     |                                                                                                                                                                                                                                           |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>-p</b> <b>—dbpassword</b>        | The password string for the system user of the database. The minimum length of the password must be 8 characters. You can identify either the database password, or for higher security, the password file where the password is defined. |
| <b>-P</b> <b>—dbpasswordfile</b>    | Identifies the file containing the password to be used for the system user of the database.                                                                                                                                               |
| <b>-w</b> <b>—adminpassword</b>     | The actual HADB administration password.                                                                                                                                                                                                  |
| <b>-W</b> <b>—adminpasswordfile</b> | The file from which the passwords are read.                                                                                                                                                                                               |
| <b>-m</b> <b>—agent</b>             | Identifies the URL to the Management Agent. The default is localhost:1862.                                                                                                                                                                |

**Operands** *dbname*                      The name of the database. The default database is hadb.

**Examples** **EXAMPLE 1** Using refragment

```
hadbm refagment --dbpasswordfile=/home/hadb/dbpfile mydatabase
This command will refragment the data on all active nodes.
Type "yes" or "y" to confirm this operation, anything else to cancel:y
Database successfully refragmented
```

**Exit Status**

|   |                                |
|---|--------------------------------|
| 0 | command executed successfully  |
| 1 | error in executing the command |

**Error Codes**

|       |                                    |
|-------|------------------------------------|
| 22002 | specified database does not exist  |
| 22041 | invalid database state             |
| 22042 | database could not be refragmented |

22051

node not responding

**See Also** [hadbm-clear\(1\)](#), [hadbm-create\(1\)](#), [hadbm-delete\(1\)](#), [hadbm-list\(1\)](#), [hadbm-restart\(1\)](#),  
[hadbm-start\(1\)](#), [hadbm-status\(1\)](#), [hadbm-stop\(1\)](#)

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                                                                                                                                                  |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Name</b>        | hadbm registerpackage – registers HADB packages in the management domain                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                  |
| <b>Synopsis</b>    | <b>hadbm registerpackage</b> <code>--packagepath=</code> <i>path</i> [ <code>--hosts=</code> <i>host_list</i> ]<br><code>[--adminpassword=</code> <i>password</i>   <code>--adminpasswordfile=</code> <i>filename</i> ] [ <code>--agent=</code> <i>ma_url</i> ]<br><code>[</code> <i>package_name</i> <code>]</code>                                                                                                                                                                         |                                                                                                                                                                                                                                  |
| <b>Description</b> | Use the <code>hadbm registerpackage</code> command to register the HADB packages that are installed on the hosts in the management domain. Registering packages can also be done when creating a database with the <code>hadbm create</code> command. The default package name is a string starting with V and containing the version number of the <code>hadbm</code> program. If the <code>--hosts</code> option is omitted, the package is registered on all enabled hosts in the domain. |                                                                                                                                                                                                                                  |
|                    | Before using the <code>hadbm registerpackage</code> command, ensure that all management agents are configured and running on all the hosts in the hostlist, the repository of the management agent is available for updates, and no software package is already registered with the same package name.                                                                                                                                                                                       |                                                                                                                                                                                                                                  |
| <b>Options</b>     | <code>-L --packagepath</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                | The full path to the HADB software package.                                                                                                                                                                                      |
|                    | <code>-H --hosts</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | A comma-separated or double quote enclosed list of hosts to register the package on.                                                                                                                                             |
|                    | <code>-w --adminpassword</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                              | The actual HADBM administration password.                                                                                                                                                                                        |
|                    | <code>-W --adminpasswordfile</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                          | The file from which the passwords are read.                                                                                                                                                                                      |
|                    | <code>-m --agent</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Identifies the URL to the Management Agent. The default is localhost:1862.                                                                                                                                                       |
| <b>Operands</b>    | <i>package_name</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | The name of the package you are registering. If a package name is not specified, the default name of the software package is used. For example, if you are using the software release V4-4-02, the default package name is V4.4. |
| <b>Examples</b>    | <p><b>EXAMPLE 1</b> Registering a software package named v4</p> <pre>hadbm registerpackage --packagepath=hadb_install_dir/SUNWhadb/4.4/v4</pre> <p>Package successfully registered</p> <p><b>EXAMPLE 2</b> Registering a software package name v4 on a specific host in the domain</p> <pre>hadbm registerpackage --packagepath=hadb_install_dir/SUNWhadb/4.4 --hosts=host1,host2,host3 v4</pre> <p>Package successfully registered</p>                                                      |                                                                                                                                                                                                                                  |
| <b>Exit Status</b> | 0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | command executed successfully                                                                                                                                                                                                    |
|                    | 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | error in executing the command                                                                                                                                                                                                   |
| <b>Error Codes</b> | 22170                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | the software package could not be found at the specified path on the host                                                                                                                                                        |

22171

the software package already exists or is registered with the same name

**See Also** [hadbm\(1m\)](#)[hadbm-create\(1\)](#), [hadbm-listpackages\(1\)](#), [hadbm-unregisterpackage\(1\)](#)



**Name** hadbm resourceinfo – gives information about the database resources

**Synopsis** **hadbm resourceinfo** [**—databuf**] [**—locks**] [**—logbuf**] [**—nilogbuf**]  
 [**—adminpassword=password** | **—adminpasswordfile=filename** ] [**—agent=ma\_url**]  
 [*dbname*]

**Description** Use the hadbm resourceinfo command to get information about the various database resources. If a database is named, it must already exist. If a database is not named, the default database is used. The default database is hadb.

**Options**

|                                     |                                                                            |
|-------------------------------------|----------------------------------------------------------------------------|
| <b>-d</b> <b>—databuf</b>           | This option displays the data buffer pool information.                     |
| <b>-l</b> <b>—locks</b>             | This option displays the locks information.                                |
| <b>-b</b> <b>—logbuf</b>            | This option displays the log buffer information.                           |
| <b>-n</b> <b>—nilogbuf</b>          | This option displays the node internal log buffer information.             |
| <b>-w</b> <b>—adminpassword</b>     | The actual HADB administration password.                                   |
| <b>-W</b> <b>—adminpasswordfile</b> | The file from which the passwords are read.                                |
| <b>-m</b> <b>—agent</b>             | Identifies the URL to the Management Agent. The default is localhost:1862. |

**Operands** *dbname* The name of the database. The default database is hadb.

**Examples** EXAMPLE 1 Using resourceinfo

hadbm **resourceinfo**

Databuffer pool:

| NodeNo | Avail | Free | Access | Misses | Copy-on-write |
|--------|-------|------|--------|--------|---------------|
| 3      | 198   | 198  | 201    | 0      | 0             |
| 4      | 198   | 198  | 217    | 0      | 0             |
| 5      | 198   | 198  | 194    | 0      | 0             |
| 6      | 198   | 198  | 43     | 0      | 0             |

Locks:

| NodeNo | Avail | Free  | Waits |
|--------|-------|-------|-------|
| 3      | 50000 | 50000 | na    |
| 4      | 50000 | 50000 | na    |
| 5      | 50000 | 50000 | na    |
| 6      | 50000 | 50000 | na    |

Log buffer:

| NodeNo | Avail | Free |
|--------|-------|------|
| 3      | 44    | 11   |
| 4      | 44    | 11   |
| 5      | 44    | 11   |
| 6      | 44    | 22   |

**EXAMPLE 1** Using resourceinfo *(Continued)*

Node internal log buffer:

| NodeNo | Avail | Free |
|--------|-------|------|
| 3      | 11    | 11   |
| 4      | 11    | 11   |
| 5      | 11    | 11   |
| 6      | 11    | 11   |

**Exit Status** 0 command executed successfully

1 error in executing the command

**Error Codes** 22002 specified database does not exist**See Also** [hadbm-clear\(1\)](#), [hadbm-clearhistory\(1\)](#), [hadbm-delete\(1\)](#), [hadbm-deviceinfo\(1\)](#), [hadbm-list\(1\)](#), [hadbm-restart\(1\)](#), [hadbm-start\(1\)](#), [hadbm-status\(1\)](#), [hadbm-stop\(1\)](#),

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                                                                                                                                                                                                                                                                                                    |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Name</b>        | hadbm restart – restarts the database                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Synopsis</b>    | <b>hadbm restart</b> [ <b>—adminpassword=</b> <i>password</i>   <b>—adminpasswordfile=</b> <i>filename</i> ] [ <b>—agent=</b> <i>ma_url</i> ] [ <b>—no-rolling</b> ] [ <i>dbname</i> ]                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Description</b> | Use the <code>hadbm restart</code> command to restart the database. Once the database is restarted, it returns to the previous state or better. If the database name is specified, the database must exist. If the database name is not specified, the default database is restarted. The default database is <code>hadb</code> .                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                                                                                                    |
|                    | In interactive mode, the <code>hadbm restart</code> command prompts for a confirmation before restarting the database.                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Options</b>     | <code>-w—adminpassword</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | The actual HADBM administration password.                                                                                                                                                                                                                                                                                                                          |
|                    | <code>-W—adminpasswordfile</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | The file from which the passwords are read.                                                                                                                                                                                                                                                                                                                        |
|                    | <code>-m—agent</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Identifies the URL to the Management Agent. The default is <code>localhost:1862</code> .                                                                                                                                                                                                                                                                           |
|                    | <code>-g—no-rolling</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | This option restarts all nodes in the HADB at once with possible loss of service. If this option is not specified, the <code>hadbm restart</code> restarts the nodes one by one and maintains the availability of the HADB. If the option is specified, it stops all nodes in parallel and starts them in parallel. During this period, the HADB is not available. |
| <b>Operands</b>    | <i>dbname</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | The name of the database. The default database is <code>hadb</code> .                                                                                                                                                                                                                                                                                              |
| <b>Examples</b>    | <p><b>EXAMPLE 1</b> Using restart with a database identified</p> <pre>hadbm restart mydatabase</pre> <p>This command will restart the named database.<br/>Type "yes" or "y" to confirm this operation, anything else to cancel: y<br/>Database successfully restarted</p> <p><b>EXAMPLE 2</b> Using restart with no rolling</p> <pre>hadbm restartnode --no-rolling mydatabase</pre> <p>This command will restart the named database.<br/>Type "yes" or "y" to confirm this operation, anything else to cancel: y<br/>Database successfully restarted</p> |                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Exit Status</b> | 0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | command executed successfully                                                                                                                                                                                                                                                                                                                                      |
|                    | 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | error in executing the command                                                                                                                                                                                                                                                                                                                                     |
| <b>Error Codes</b> | 22002                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | specified database does not exist                                                                                                                                                                                                                                                                                                                                  |
|                    | 22105                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | database is not running                                                                                                                                                                                                                                                                                                                                            |
|                    | 22106                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | database could not be restarted                                                                                                                                                                                                                                                                                                                                    |
|                    | 22107                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | database could not return to a previous state                                                                                                                                                                                                                                                                                                                      |

22108

invalid database state

**See Also** [hadbm-addnodes\(1\)](#), [hadbm-clear\(1\)](#), [hadbm-delete\(1\)](#), [hadbm-list\(1\)](#), [hadbm-refragment\(1\)](#),  
[hadbm-start\(1\)](#), [hadbm-status\(1\)](#), [hadbm-stop\(1\)](#)

**Name** hadbm restartnode – restarts the specified node

**Synopsis** **hadbm restartnode** [`--adminpassword=password` | `--adminpasswordfile=filename` ]  
`[--agent=ma_url]` [`--startlevel=level`] *node\_number* [*dbname*]

**Description** Use the hadbm restartnode command to restart the node. The node is restarted by running the startup procedure on the node. The mirror node of the node to be restarted must be up. The node is restarted in the specified start level. The start level indicates the environmental conditions the node should take into consideration while starting. The valid start levels are:

| Start Level      | Description                                                                                                |
|------------------|------------------------------------------------------------------------------------------------------------|
| normal (default) | This start level is used when the node has been stopped earlier in a controlled way (default).             |
| repair           | This start level forces an active node to repair data from its mirror node.                                |
| clear            | This start level reinitializes the devices for the node, and forces a repair of data from its mirror node. |

In interactive mode, the hadbm restartnode command prompts for a confirmation before restarting the node.

**Options**

- `-w` `--adminpassword` The actual HADB administration password.
- `-W` `--adminpasswordfile` The file from which the passwords are read.
- `-m` `--agent` Identifies the URL to the Management Agent. The default is localhost:1862.
- `-l` `--startlevel` Identifies the start level to be used to restart the named node. The default start level is normal.

**Operands**

- node\_number* A positive integer. The node number must be an existing node that is in a running state in the database.
- dbname* The name of the database. The default database is hadb.

**Examples** **EXAMPLE 1** Using restartnode on the default database

```
hadbm restartnode 2
This command will restart the node.
Type "yes" or "y" to confirm this operation, anything else to cancel: y
Node successfully restarted
```

**EXAMPLE 2** Using restartnode with a database identified

```
hadbm restartnode 2 mydatabase
This command will restart the node.
Type "yes" or "y" to confirm this operation, anything else to cancel: y
```

**EXAMPLE 2** Using restartnode with a database identified *(Continued)*

Node successfully restarted

|                    |       |                                                  |
|--------------------|-------|--------------------------------------------------|
| <b>Exit Status</b> | 0     | command executed successfully                    |
|                    | 1     | error in executing the command                   |
| <b>Error Codes</b> | 22002 | specified database does not exist                |
|                    | 22082 | start level is not a recognized level            |
|                    | 22087 | mirror node of the specified node is not running |
|                    | 22088 | node is not running                              |
|                    | 22091 | node could not be restarted                      |

**See Also** [hadbm-addnodes\(1\)](#), [hadbm-list\(1\)](#), [hadbm-startnode\(1\)](#), [hadbm-stopnode\(1\)](#)

**Name** hadbm set – sets the value of the specified configuration attributes to the identified values

**Synopsis** **hadbm set** [**—adminpassword=***password* | **—adminpasswordfile=***filename* ]  
 [**—agent=***ma\_url*] {*attribute\_name\_value\_list*} [*dbname*]

**Description** The hadbm set command is used to reconfigure the database. Multiple configuration attributes can be modified in one single set operation. You can use a comma or space separated list of name=value pairs. If using a space separated list, use quotation marks to preserve the spaces. The writeable configuration attributes are as follows:

| Variable              | Range            | Default                    |
|-----------------------|------------------|----------------------------|
| ConnectionTrace       | ture/false       | false                      |
| CoreFile              | true/false       | false                      |
| DataBufferPoolSize    | 16–2047          | 200 MB                     |
| DataDeviceSize        | 32–262144        | 1024 MB                    |
| DevicePath            | n/a              | n/a                        |
| EagerSessionThreshold | 0–100            | 50 (% of NumberOfSessions) |
| Eager SessionTimeout  | 0–2147483647     | 120 seconds                |
| EventBufferSize       | 0–2097152        | 0 MB                       |
| HistoryPath           | n/a              | n/a                        |
| InternalLogBufferSize | 4–128            | 12 MB                      |
| LogBufferSize         | 4–2047           | 48 MB                      |
| MaxTables             | 100–1100         | 1100                       |
| NumberOfDataDevices   | 1–8              | 1                          |
| NumberOfLocks         | 20000–1073741824 | 50000                      |
| NumberOfSessions      | 1–10000          | 100                        |
| PackageName           | n/a              | V4.x.x.x                   |
| RelalgDeviceSize      | 32–262144        | 128 MB                     |
| SQLTraceMode          | none/short/full  | none                       |
| SessionTimeout        | 0–2147483647     | 1800 seconds               |
| StartRepairDelay      | 0–100000         | 20 seconds                 |
| StatInterval          | 0–600            | 600 seconds                |
| SyslogFacility        | <facility>       | local0                     |

| Variable     | Range     | Default        |
|--------------|-----------|----------------|
| SyslogLevel  | <level>   | warning        |
| SyslogPrefix | <string>  | hadb-<db_name> |
| TakeoverTime | 500-16000 | 10000 MS       |

The values of the configuration attributes will be set into the database configuration. Use the `hadbm get` command to get the new value of an attribute. When the value part of an attribute is missing, the attribute is set to the default value.

Setting the database attribute may require the system to do a rolling restart of the hadb nodes. The database must be in Fault Tolerant or HA Fault Tolerant state before using the `hadbm set` command.

The `JdbcUrl` cannot be set with either the `hadbm set` or `hadbm create` commands. However, the `hadbm create` or `hadbm addnodes` commands derive the `JdbcUrl` value from values given for `—hosts` and `—portbase` options. So, there is no need to set this variable.

The `set` command can be used to do an online upgrade of the database. A pre-condition for online upgrade is that the new version of the HADB software has been installed on all the hosts, and is registered in the domain.

To do an online upgrade, modify the `packagename` attribute and set it to the name of the new package.

- Options**
- `-w—adminpassword` The actual HADB administration password.
  - `-W—adminpasswordfile` The file from which the passwords are read.
  - `-m—agent` Identifies the URL to the Management Agent. The default is `localhost:1862`.

- Operands**
- attribute\_name\_value\_list* A list of variables with values to be set. All the attribute names must be supported attributes.
  - dbname* The name of the database. The default database is `hadb`.

**Examples** EXAMPLE 1 Using `set`

```
hadbm set "connectiontrace=true numberOfLocks=110000"
Database attributes successfully set.
```

- Exit Status**
- 0 command executed successfully
  - 1 error in executing the command

- Error Codes**
- 22002 specified database does not exist
  - 22033 invalid value set for attributes
  - 22071 attributes are not recognized



22072

attribute is not writeable

**See Also** `hadbm-addnodes(1)`, `hadbm-get(1)`, `hadbm-clear(1)`, `hadbm-delete(1)`, `hadbm-list(1)`,  
`hadbm-start(1)`, `hadbm-restart(1)`, `hadbm-status(1)`, `hadbm-stop(1)`

**Name** hadbm start – starts the database

**Synopsis** **hadbm start** [`—adminpassword=password` | `—adminpasswordfile=filename` ]  
 [`—agent=ma_url`] [*dbname*]

**Description** Use the `hadbm start` command to start the database. Only the nodes that were running before the database was stopped will be started. If the database name is specified, it should be an existing database. If the database name is not specified, the default database is used. If one or more mirror node pairs have stopped simultaneously due to a power outage, machine reboot or some other disaster (i.e., the `hadb` instance is in a non-functional state), then the database instance cannot be started. In such a case, use the `hadbm clear` command to start the database and recreate the schema.

|                |                                   |                                                                            |
|----------------|-----------------------------------|----------------------------------------------------------------------------|
| <b>Options</b> | <code>-w—adminpassword</code>     | The actual HADBM administration password.                                  |
|                | <code>-W—adminpasswordfile</code> | The file from which the passwords are read.                                |
|                | <code>-m—agent</code>             | Identifies the URL to the Management Agent. The default is localhost:1862. |

**Operands** *dbname* The name of the database. The default database is `hadb`.

**Examples** **EXAMPLE 1** Using `start` with a database identified

```
hadbm start mydatabase
Database successfully started
```

|                    |   |                                |
|--------------------|---|--------------------------------|
| <b>Exit Status</b> | 0 | command executed successfully  |
|                    | 1 | error in executing the command |

|                    |       |                                                                                                                                                                                                        |
|--------------------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Error Codes</b> | 22002 | specified database does not exist                                                                                                                                                                      |
|                    | 22095 | database could not be started                                                                                                                                                                          |
|                    | 22096 | database is already running                                                                                                                                                                            |
|                    | 22097 | some nodes could not be started                                                                                                                                                                        |
|                    | 22098 | database ( <code>hadb</code> ) could not be started. The stopstate cannot be determined. In case of uncontrolled stop of the database, use the <code>hadbm clear</code> command to start the database. |

**See Also** [hadbm-addnodes\(1\)](#), [hadbm-clear\(1\)](#), [hadbm-delete\(1\)](#), [hadbm-list\(1\)](#), [hadbm-refragment\(1\)](#), [hadbm-restart\(1\)](#), [hadbm-status\(1\)](#), [hadbm-stop\(1\)](#)

**Name** hadbm startnode – starts the specified node

**Synopsis** **hadbm startnode** [**--adminpassword=***password* | **--adminpasswordfile=***filename* ]  
 [**--agent=***ma\_url*] [**--startlevel=***level*] *node\_number* [*dbname*]

**Description** The hadbm startnode command starts the node by running the startup procedure on the node. The node is started in the specified start level. The start level indicates the environmental conditions the node should take into consideration while starting. The valid start levels are as follows:

| Start Level | Description                                                                                               |
|-------------|-----------------------------------------------------------------------------------------------------------|
| normal      | This start level is used when the node was earlier stopped in a controlled way (default).                 |
| repair      | This start level forces an active node to repair data from its mirror node.                               |
| clear       | This start level reinitializes the devices for the node, and force a repair of data from its mirror node. |

**Options**

- w** **--adminpassword** The actual HADB administration password.
- W** **--adminpasswordfile** The file from which the passwords are read.
- m** **--agent** Identifies the URL to the Management Agent. The default is localhost:1862.
- l** **--startlevel** Indicates the start level to be used to start the specified node(s). The default start level is normal.

**Operands**

- node\_number* A positive integer. The node number specified must be an existing node that is in a running state in the database.
- dbname* The name of the database. The default database is hadb.

**Examples** EXAMPLE 1 Using startnode on the default database

```
hadbm startnode 1
Node successfully started
```

EXAMPLE 2 Using startnode with the startlevel and database identified

```
hadbm startnode --startlevel=normal 1 mydatabase
Node successfully started
```

**Exit Status**

- 0 command executed successfully
- 1 error in executing the command

**Error Codes**

- 22002 specified database does not exist
- 22081 node is already running

22082 start level is not a recognized level

22083 node could not be started

**See Also** [hadbm-addnodes\(1\)](#), [hadbm-list\(1\)](#), [hadbm-restartnode\(1\)](#), [hadbm-stopnode\(1\)](#)

---

|                    |                                                                                                                                                      |                                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Name</b>        | hadbm status – shows the state of the database                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Synopsis</b>    | <b>hadbm status</b> [ <b>—nodes</b> ] [ <b>—adminpassword=password   <b>—adminpasswordfile=filename ] [<b>—agent=ma_url] [<i>dbname</i>]</b></b></b> |                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Description</b> | Use the <code>hadbm status</code> command to get the current state of the database. The state can be one of the following:                           |                                                                                                                                                                                                                                                                                                                                                                                                   |
|                    | HA Fault Tolerant (HAFT)                                                                                                                             | The database has at least one spare node on each DRU.                                                                                                                                                                                                                                                                                                                                             |
|                    | Fault Tolerant (FT)                                                                                                                                  | All mirrored node pairs are up and running.                                                                                                                                                                                                                                                                                                                                                       |
|                    | Operational (O)                                                                                                                                      | One node in each mirrored node pair is up and running.                                                                                                                                                                                                                                                                                                                                            |
|                    | Non-operational (NO)                                                                                                                                 | One or more mirrored node pair is missing both nodes. An arbitrary SQL transaction may not succeed.                                                                                                                                                                                                                                                                                               |
|                    | Stopped (S)                                                                                                                                          | No nodes are running.                                                                                                                                                                                                                                                                                                                                                                             |
|                    | Unknown (U)                                                                                                                                          | Unable to determine the state of the database.                                                                                                                                                                                                                                                                                                                                                    |
|                    | If a database is named, it must already exist. If a database is not named, the default database is used. The default database is <code>hadb</code> . |                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Options</b>     | <b>-n</b> <b>—nodes</b>                                                                                                                              | If specified, displays the node status information. The following information is displayed for each node in the database: <ul style="list-style-type: none"> <li>▪ Node number</li> <li>▪ Name of the machine where the node is running</li> <li>▪ Port number of the node</li> <li>▪ Role of the node</li> <li>▪ State of the node</li> <li>▪ Number of the corresponding mirror node</li> </ul> |
|                    | <b>-w</b> <b>—adminpassword</b>                                                                                                                      | The actual HADB administration password.                                                                                                                                                                                                                                                                                                                                                          |
|                    | <b>-W</b> <b>—adminpasswordfile</b>                                                                                                                  | The file from which the passwords are read.                                                                                                                                                                                                                                                                                                                                                       |
|                    | <b>-m</b> <b>—agent</b>                                                                                                                              | Identifies the URL to the Management Agent. The default is <code>localhost:1862</code> .                                                                                                                                                                                                                                                                                                          |
| <b>Operands</b>    | <i>dbname</i>                                                                                                                                        | The name of the database. The default database is <code>hadb</code> .                                                                                                                                                                                                                                                                                                                             |
| <b>Examples</b>    | <p>EXAMPLE 1 Using status</p> <pre>hadbm status Database Status hadb HAFaultTolerant</pre>                                                           |                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Exit Status</b> | 0                                                                                                                                                    | command executed successfully                                                                                                                                                                                                                                                                                                                                                                     |
|                    | 1                                                                                                                                                    | error in executing the command                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Error Codes</b> | 22002                                                                                                                                                | specified database does not exist                                                                                                                                                                                                                                                                                                                                                                 |

**See Also** [hadbm-clear\(1\)](#), [hadbm-clearhistory\(1\)](#), [hadbm-delete\(1\)](#), [hadbm-list\(1\)](#), [hadbm-restart\(1\)](#), [hadbm-resourceinfo\(1\)](#), [hadbm-start\(1\)](#), [hadbm-stop\(1\)](#),

- 
- Name** hadbm stop – gracefully stops the database
- Synopsis** **hadbm stop** [`—adminpassword=password` | `—adminpasswordfile=filename` ] [`—agent=ma_url`] [*dbname*]
- Description** Use the `hadbm stop` command to stop the database gracefully. It is a good practice to stop the database if some maintenance activity is planned that affects the mirror nodes simultaneously. The data is intact in a database that is stopped gracefully, in contrast to the one that has not been stopped gracefully. Once you stop the database using the `hadbm stop` command, use the `hadbm start` command to start the database. If the database name is specified, the named database must exist. If the database name is not identified, the default database is used. The default database is `hadb`.
- In interactive mode, the `hadbm stop` command prompts for a confirmation before stopping the node.
- Options**
- |                                   |                                                                                          |
|-----------------------------------|------------------------------------------------------------------------------------------|
| <code>-w—adminpassword</code>     | The actual HADB administration password.                                                 |
| <code>-W—adminpasswordfile</code> | The file from which the passwords are read.                                              |
| <code>-m—agent</code>             | Identifies the URL to the Management Agent. The default is <code>localhost:1862</code> . |
- Operands** *dbname*                      The name of the database. The default database is `hadb`.
- Examples** **EXAMPLE 1** Using stop with a database identified
- ```
hadbm stop mydatabase
This command will stop the named database.
Type "yes" or "y" to confirm this operation, anything else to cancel: y
Database successfully stopped
```
- Exit Status**
- |   |                                |
|---|--------------------------------|
| 0 | command executed successfully  |
| 1 | error in executing the command |
- Error Codes**
- |       |  |
|-------|--|
| 22002 | specified database does not exist      |
| 22101 | database could not be stopped          |
| 22102 | database is already in a stopped state |
| 22103 | database is not fully stopped          |
- See Also** [hadbm-addnodes\(1\)](#), [hadbm-clear\(1\)](#), [hadbm-delete\(1\)](#), [hadbm-list\(1\)](#), [hadbm-refragment\(1\)](#), [hadbm-restart\(1\)](#), [hadbm-start\(1\)](#), [hadbm-status\(1\)](#)

**Name** hadbm stopnode – gracefully stops the specified node

**Synopsis** **hadbm stopnode** [**—adminpassword=***password* | **—adminpasswordfile=***filename* ]  
 [**—agent=***ma\_url*] [**—no-repair**] *node\_number* [*dbname*]

**Description** The hadbm stopnode command stops the node gracefully. The mirror node of the node that is to be stopped must be running. If a node’s mirror node is not up, the node will not be stopped and an error message is displayed. By default, a spare node can replace the stopped node by copying the data from the stopped node’s mirror. If there is no spare available, an error message is displayed.

In interactive mode, the hadbm stopnode command prompts for a confirmation before stopping the node.

**Options**

<b>—w—adminpassword</b>	The actual HADB administration password.
<b>—W—adminpasswordfile</b>	The file from which the passwords are read.
<b>—m—agent</b>	Identifies the URL to the Management Agent. The default is localhost:1862.
<b>—R—no-repair</b>	If specified, a spare will not replace the stopping node.

**Operands**

<i>node_number</i>	A positive integer. The node number of the node to be stopped.
<i>dbname</i>	The name of the database. The default database is hadb.

**Examples** EXAMPLE 1 Using stopnode

```
hadbm stopnode 1
This command will stop the node.
Type "yes" or "y" to confirm this operation, anything else to cancel: y
Node successfully stopped
```

EXAMPLE 2 Using stopnode with no-repair option

```
hadbm stopnode --no-repair 1 mydatabase
This command will stop the node.
Type "yes" or "y" to confirm this operation, anything else to cancel: y
hadbm:Info 22202 Repair was not initiated while stopping the node {0}.
```

**Exit Status**

0	command executed successfully
1	error in executing the command

**Error Codes**

22002	specified database does not exist
22085	no spare to pickup (if <b>—no-repair</b> is specified)
22086	node could not be stopped
22087	no mirror node
22088	node is not running
22202	repair not initiated



**See Also** [hadbm-get\(1\)](#), [hadbm-clear\(1\)](#), [hadbm-addnodes\(1\)](#), [hadbm-restartnode\(1\)](#), [hadbm-start\(1\)](#), [hadbm-startnode\(1\)](#), [hadbm-stop\(1\)](#)

**Name** hadbm unregisterpackage – removes registered HADB packages from the management domain

**Synopsis** **hadbm unregisterpackage** [**—hosts=hostlist**]  
 [**—adminpassword=password** | **—adminpasswordfile=filename** ] [**—agent=ma\_url**]  
 [*package\_name*]

**Description** Use the hadbm unregisterpackage command to remove the HADB packages that are registered with the management domain. The default package name is a string starting with V and containing the version number of the hadbm program. If the **—hosts** option is omitted, the hostlist defaults to the enabled hosts where the package is registered.

Before using the hadbm unregisterpackage command, ensure that all management agents are configured and running on all the hosts in the hostlist, the management agent’s repository is available for updates, the package is registered in the management domain, and no existing databases are configured to run on the package about to be unregistered.

**Options**

<b>—H—hosts</b>	A comma-separated or double quote enclosed space separated list of hosts to register the package on.
<b>—w—adminpassword</b>	The actual HADB administration password.
<b>—W—adminpasswordfile</b>	The file from which the passwords are read.
<b>—m—agent</b>	Identifies the URL to the Management Agent. The default is localhost:1862.

**Operands** *package\_name* The name of the package you wish to remove from the domain.

**Examples** **EXAMPLE 1** Unregistering a software package named v4

```
hadbm unregisterpackage v4
Package successfully unregistered
```

**EXAMPLE 2** Unregistering a software package named v4 from specific hosts in the domain

```
hadbm unregisterpackage --hosts=host1,host2,host3 v4
Package successfully unregistered
```

**Exit Status**

0	command executed successfully
1	error in executing the command

**Error Codes**

22172	the software package is not registered in the domain
22173	the software package is in use by a database instance and cannot be removed

**See Also** [hadbm\(1m\)](#), [hadbm-registerpackage\(1\)](#), [hadbm-list-packages\(1\)](#)



**Name** help – displays the asadmin utility commands

**Synopsis** help [*or* —help | -h | -? ]

**Description** The help command displays a list of all the asadmin utility commands. Specify the command to display the usage information for that command. To display the manpage of each command, use the syntax: asadmin *command\_name* --help | -h | -? or asadmin help *command\_name*

The following is a list of all the asadmin utility commands:

add-resources	registers the resource in the XML file specified
backup-domain	performs a backup on the domain
change-master-password	changes the master password
clear-ha-store	deletes tables in the HA database
configure-ha-cluster	configures an existing cluster to be High Availability
configure-ha-persistence	enables configuration of parameters related to session persistence
copy-config	copies an existing configuration to create a new configuration
create-admin-object	adds the administered object with the specified JNDI name
create-application-ref	creates a reference to an application
create-audit-module	creates an audit module for the optional plugin module
create-auth-realm	adds the new authorized realm
create-cluster	creates a cluster
create-connector-connection-pool	adds a connection pool with the specified connection pool name
create-connector-resource	registers the resource with the specified JNDI name
create-connector-security-map	creates or modifies a security map for the namedconnector connection pool
create-custom-resource	registers the custom resource
create-domain	creates a domain with the given name
create-file-user	creates a new file user
create-ha-store	creates tables in HA database that are used by HA cluster
create-http-health-checker	creates a health-checker for a specified load balancer configuration
create-http-lb-config	creates a configuration for the load balancer
create-http-lb-ref	add an existing cluster or server instance to an existing load balancer configuration

---

create-http-listener	adds a new HTTP listener socket
create-iiop-listener	adds the IIOP listener
create-instance	creates an instance with the given name
create-javamail-resource	registers the Javamail resource
create-jdbc-connection-pool	registers the JDBC connection pool
create-jdbc-resource	registers the JDBC resource
create-jms-host	creates a JMS host
create-jms-resource	registers the JMS resource
create-jmsdest	adds the named destination
create-jndi-resource	registers the JNDI resource
create-jvm-options	creates the JVM options from the Java configuration or profiler elements
create-lifecycle-module	adds a lifecycle module
create-message-security-provider	enables administrators to create the <code>message-security-config</code> and <code>provider-config</code> sub-elements for the security service in <code>domain.xml</code>
create-node-agent	creates a node agent and its associated directory structure
create-node-agent-config	adds a new unbound node agent to a domain
create-password-alias	creates a password alias
create-persistence-resource	registers the persistence resource
create-profiler	creates the profiler element
create-resource-adapter-config	creates the resource adapter Java bean
create-resource-ref	creates a reference to a resource
create-ssl	creates the SSL element in the HTTP listener or IIOP listener
create-system-properties	adds or updates one or more system properties of the domain, configuration, cluster, or server instance
create-threadpool	creates the thread pool
create-virtual-server	adds the named virtual server
delete-admin-object	removes the administered object with the specified JNDI name
delete-application-ref	removes a reference to an application
delete-audit-module	deletes the audit-module for the optional plugin module

<code>delete-auth-realm</code>	removes the named authorized realm
<code>delete-cluster</code>	deletes a cluster
<code>delete-config</code>	deletes an existing configuration
<code>delete-connector-connection-pool</code>	removes the specified connection pool
<code>delete-connector-resource</code>	removes the named resource connector
<code>delete-connector-security-map</code>	deletes the named security map
<code>delete-custom-resource</code>	removes the custom resource
<code>delete-domain</code>	deletes the given domain
<code>delete-file-user</code>	removes the named file user
<code>delete-http-health-checker</code>	deletes a health-checker for a specified load balancer configuration
<code>delete-http-lb-config</code>	deletes a load balancer configuration
<code>delete-http-lb-ref</code>	deletes the cluster or server instance from a load balancer configuration
<code>delete-iiop-listener</code>	removes the IIOP listener
<code>delete-instance</code>	deletes the instance that is not running
<code>delete-javamail-resource</code>	removes the Javamail resource
<code>delete-jdbc-connection-pool</code>	removes the JDBC connection pool
<code>delete-jdbc-resource</code>	removes the JDBC resource
<code>delete-jms-host</code>	removes a JMS host
<code>delete-jms-resource</code>	removes the JMS resource
<code>delete-jmsdest</code>	destroys the named destination
<code>delete-jndi-resource</code>	removes the JNDI resource
<code>delete-jvm-options</code>	deletes the JVM options from the Java configuration or profiler elements
<code>delete-lifecycle-module</code>	removes the lifecycle module
<code>delete-message-security-provider</code>	enables administrators to delete a <code>provider-config</code> sub-element for the given message layer ( <code>message-security-config</code> element of <code>domain.xml</code> )
<code>delete-node-agent</code>	deletes the node agent and its associated directory structure
<code>delete-node-agent-config</code>	removes a node agent from a domain
<code>delete-password-alias</code>	deletes a password alias

---

delete-persistence-resource	removes the persistence resource
delete-profiler	deletes the profiler element
delete-resource-adapter-config	deletes the resource adapter Java bean
delete-resource-ref	removes a reference to a resource
delete-ssl	deletes the ssl element from the HTTP listener or IIOP listener
delete-system-property	removes one or more system properties of the domain, configuration, cluster, or server instance
delete-threadpool	deletes the thread pool
delete-virtual-server	deletes the virtual server with the named virtual server ID
deploy	deploys the specified component
deploydir	deploys the component that is in the directory located on domain application server
disable	stops the component
disable-http-lb-application	disables an application managed by a load balancer
disable-http-lb-server	disables a sever or cluster managed by a load balancer
enable	runs the component
enable-http-lb-application	enables a previously-disabled application managed by a load balancer
enable-http-lb-server	enables a previously disabled sever or cluster managed by a load balancer
export	marks a variable name for automatic export to the environment of subsequent commands in multimode
export-http-lb-config	exports the load balancer configuration to a file that can be used by the load balancer
freeze-transaction-service	immobilizes the named transaction service
get	gets the values of the monitorable or configurable attributes
get-client-stubs	gets the stubs of the client
help	displays a list of all the commands available in the Command-line interface
jms-ping	checks to see if the JMS provider is up and running
list	lists the configurable elements
list-admin-objects	gets all the administered objects

list-application-refs	lists all application references in a cluster or unclustered server instance
list-audit-modules	lists the audit modules
list-auth-realms	lists the authorized realms
list-backups	lists all backups and restores
list-clusters	lists the existing clusters
list-configs	lists all existing configurations
list-connector-connection-pools	gets all the connection pools
list-connector-resources	gets all the connector resources
list-connector-security-maps	lists the security maps for the connector connection pool
list-custom-resources	gets all the custom resources
list-domains	lists the domains in the given domains directory
list-file-groups	lists the file groups
list-file-users	lists the file users
list-http-lb-configs	lists load balancer configurations
list-http-listeners	gets the HTTP listeners
list-iiop-listeners	gets the IIOP listeners
list-instances	lists all the instances in the server
list-javamail-resources	gets all the Javamail resources
list-jdbc-connection-pools	registers the JDBC connection pool
list-jdbc-resources	gets all the JDBC resources
list-jms-hosts	lists the existing JMS hosts
list-jms-resources	gets all the JMS resources
list-jmsdest	gets all the named destinations
list-jndi-entries	gets all the named destinationsbrowses and queries the JNDI tree
list-jndi-resources	gets all the JNDI resources
list-lifecycle-modules	gets the lifecycle modules
list-message-security-providers	enables administrators to list all security message providers (provider-config sub-elements) for the given message layer (message-security-config element of domain.xml)



---

list-node-agents	lists the node agents along with their status
list-password-aliases	lists all password aliases
list-persistence-resources	gets all the persistence resources
list-resource-adapter-configs	lists the resource adapters configured in an instance
list-resource-refs	lists the existing resource references
list-sub-components	lists EJBs or Servlets in a deployed module or in a module of a deployed application
list-system-properties	lists the system properties of the domain, configuration, cluster, or server instance
list-threadpools	lists the thread pools
list-timers	lists all of the timers owned by server instance(s)
list-virtual-servers	gets the virtual servers
migrate-timers	moves a timer when a server instance stops
multimode	allows you to execute multiple commands while returning environment settings and remaining in the <code>asadmin</code> utility
ping-connection-pool	tests if a connection pool is usable
recover-transactions	manually recovers pending transactions
rollback-transaction	rollback the named transaction
remove-ha-cluster	returns an HA cluster to non-HA status
restore-domain	restores files from backup
set	sets the values of attributes
show-component-status	displays the status of the deployed component
start-cluster	starts a cluster
start-domain	starts the given domain
start-instance	starts a server instance
start-node-agent	starts a node agent
stop-cluster	stops a cluster
stop-domain	stops the given domain
stop-instance	stops a server instance
stop-node-agent	stops a node agent
undeploy	removes a component in the domain application server

<code>unfreeze-transaction-service</code>	mobilizes the named transaction service
<code>unset</code>	removes one or more variables from the multimode environment
<code>update-file-user</code>	updates a current file user as specified
<code>update-password-alias</code>	updates a password alias
<code>update-connector-security-map</code>	updates the security map for the specified connector connection pool
<code>verify-domain-xml</code>	verifies the content of the <code>domain.xml</code>
<code>version</code>	displays the version information

The following commands are deprecated:

1. `display-license`
2. `install-license`
3. `restart-instance`
4. `shutdown`
5. `create-acl`
6. `delete-acl`
7. `list-acls`
8. `start-appserv`
9. `stop-appserv`

**Examples** EXAMPLE 1 Using help

```
asadmin> help
asadmin> create-domain --help
```

Where: **create-domain** is the command you wish to view the usage for.

**See Also** [asadmin\(1\)](#)

---

<b>Name</b>	jms-ping – checks to see if the JMS service is up and running	
<b>Synopsis</b>	<b>jms-ping</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>—s</b> ] [ <b>—terse=false</b> ] [ <b>—echo=false</b> ] [ <b>—interactive=true</b> ] [ <b>—help</b> ] [ <i>target</i> ]	
<b>Description</b>	<p>The <code>jms-ping</code> command checks to see if the JMS service (also known as the JMS provider) is up and running. When you start the Application Server, the JMS service starts by default.</p> <p>The <code>jms-ping</code> command pings only the default JMS host within the JMS service. It throws an exception when it is unable to ping a built-in JMS service.</p> <p>This command is supported in remote mode only.</p>	
<b>Options</b>	<b>—u —user</b>	The authorized domain application server administrative username.
	<b>—w —password</b>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
	<b>—passwordfile</b>	<p>This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</p>
	<b>—H —host</b>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
	<b>—p —port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>—s —secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>—t —terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.

<code>-e</code>	<code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code>	<code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code>	<code>—help</code>	Displays the help text for the command.
<b>Operands</b>	<i>target</i>	In Enterprise Edition, this operand specifies the target for which the operation is to be performed. Valid values are: <ul style="list-style-type: none"><li>▪ <i>server</i>, which pings the JMS service for the default server instance <i>server</i> and is the default value</li><li>▪ <i>configuration_name</i>, which pings the JMS service for all clusters using the specified configuration</li><li>▪ <i>cluster_name</i>, which pings the JMS service for the specified cluster</li><li>▪ <i>instance_name</i>, which pings the JMS service for a particular server instance</li></ul>

**Examples** EXAMPLE 1 Using the jms-ping command

The following command checks to see if the JMS service is running on the server instance *server1*:

```
asadmin> jms-ping --user admin
--passwordfile passwords.txt --host bluestar --port 4848
server1
JMS Ping Status=RUNNING
Command jms-ping executed successfully.
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [create-jmsdest\(1\)](#), [create-jms-resource\(1\)](#)

---

<b>Name</b>	jspc – precompiles JSP source files into servlets	
<b>Synopsis</b>	<b>jspc</b> [ <i>options</i> ] <i>jsp_files</i> or <b>jspc</b> [ <i>options</i> ]-webapp <i>dir</i>	
<b>Description</b>	Use the <code>jspc</code> command to compile your JSP 2.0 compliant source files into servlets. To allow the Application Server to pick up the precompiled JSP pages from a JAR file, specify the <code>-compile</code> and <code>-webinc</code> or <code>-webxml</code> options, which cause the JSP pages to be mapped to their corresponding servlet class files. This means that the JSP compiler will be bypassed when those JSPs are accessed.	
<b>Options</b>	<i>jsp_files</i>	one or more JSP files to be compiled.
	<code>-webapp <i>dir</i></code>	a directory containing a web application. All JSPs in the directory and its subdirectories are compiled. You cannot specify a WAR, JAR, or ZIP file; you must first deploy it to an open directory structure using <code>asadmin deploy</code> .
	<code>-d <i>dir</i></code>	the output directory for the compiled JSPs. Package directories are automatically generated based on the directories containing the uncompiled JSPs. The default directory is the directory specified by the <code>java.io.tmpdir</code> property, or the current directory.
	<code>-p <i>name</i></code>	the name of the target package for all specified JSPs, which is prepended to the package component derived from the directory in which the JSP pages are located. The default is <code>org.apache.jsp</code> .
	<code>-c <i>name</i></code>	the target class name of the first JSP compiled. Subsequent JSPs are unaffected.
	<code>-l</code>	outputs the name of the JSP page upon failure.
	<code>-s</code>	outputs the name of the JSP page upon success.
	<code>-uribase <i>dir</i></code>	the URI directory to which compilations are relative. Applies only to JSP files listed in the command, and not to JSP files specified with <code>-webapp</code> option. This is the location of each JSP file relative to the <code>uriroot</code> . If this cannot be determined, the default is <code>/</code> .
	<code>-uriroot <i>dir</i></code>	the root directory against which URI files are resolved. Applies only to JSP files listed in the command, and not to JSP files specified with <code>-webapp</code> option. If this option is not specified, all parent directories of the first JSP page are searched for a <code>WEB-INF</code> subdirectory. The closest directory to the JSP page that has one is used. If none of the JSP's parent directories have a <code>WEB-INF</code> subdirectory, the directory from which <code>jspc</code> is invoked is used.
	<code>-compile</code>	Compile the generated servlets.

<code>-v</code>	enables verbose mode.
<code>-mapped</code>	generates separate <code>write()</code> calls for each HTML line and comments that describe the location of each line in the JSP file. By default, all adjacent <code>write()</code> calls are combined and no location comments are generated.
<code>-die [code]</code>	causes the JVM to exit and generates an error return code if a fatal error occurs. If the code is absent or unparsable it defaults to 1.
<code>-webinc file</code>	creates partial servlet mappings for the <code>-webapp</code> option, which can be pasted into a <code>web.xml</code> file.
<code>-webxml file</code>	creates an entire <code>web.xml</code> file for the <code>-webapp</code> option.
<code>-classpath path</code>	Override the system classpath with the specified classpath.
<code>-ieplugin class_id</code>	specifies the Java plugin COM class ID for Internet Explorer. Used by the <code>jsp:plugin</code> tags.
<code>-xpoweredBy</code>	Adds an X-Powered-By HTTP response header.
<code>-trimSpaces</code>	Trim spaces in template text between actions and directives.
<code>-help</code>	Print a summary of the syntax and options for this command.

**Examples** EXAMPLE 1 Using `jspc` to compile the JSP pages in a Web application

The following command compiles a set of JSP files into Java source files under `/home/user/Hellodir`:

```
jspc welcome.jsp shop.jsp checkout.jsp -d /home/user/Hellodir
```

The following command compiles all the JSP files in the specified webapp into class files under `/home/user/Hellodir`:

```
jspc -webapp /path_to_source_directory -compile -d /home/user/Hellodir
```

The following command compiles a set of JSP files into Java class files in `/home/user/Hellodir` with the package name `com.test.jsp` prepended to the package hierarchy found in `/path_to_source_directory`. It creates `web.xml` in the output directory.

```
jspc -webapp /path_to_source_directory -compile -webxml  
/home/user/Hellodir/web.xml -d /home/user/Hellodir -p com.test.jsp
```

To use these precompiled JSP pages in your web application, package the servlet class files generated under `/home/user/Hellodir` into a JAR file, place the JAR file under `WEB-INF/lib`, and copy the generated `/home/user/Hellodir/web.xml` to `WEB-INF/web.xml`.

**See Also** [asadmin\(1M\)](#)

- 
- Name** list – lists the configurable elements
- Synopsis** **list** `—user admin_user` [`—passwordfile filename`] [`—host host_name`] [`—port port_number`] [`—secure|-s`] [`—terse=false`] [`—echo=false`] [`—interactive=true`] [`—help`] [`—monitor=[true|false]`] [`dotted_parent_attribute_name`]
- Description** Lists the configurable element. On Solaris, quotes are needed when executing commands with \* as the option value or operand.
- The dotted notation follows these guidelines:
- Any list command that has a dotted name that is not followed by a wildcard (\*) will get, as its result, the current node’s immediate children. For example, list --monitor server lists all immediate children belonging to the server node.
  - Any list command that has a dotted name followed by a wildcard(\*) will get, as its result, a hierarchical tree of children nodes from the current node. For example, list --monitor server.applications.\* will list all children of applications and their subsequent child nodes and so on.
  - Any list command that has a dotted name preceded or followed by a wildcard (\*) of the form \**dotted name* or *dotted \* name* or *dotted name\** will get, as its result, all nodes and their children matching the regular expression created by the provided matching pattern.
- Options**
- |                            |  |
|----------------------------|--|
| <code>—u—user</code>       | The authorized domain application server administrative username.  |
| <code>—w—password</code>   | The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.   |
| <code>—passwordfile</code> | This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on. |
| <code>—H—host</code>       | The machine name where the domain application server is running. The default value is localhost.   |

---

<code>-p</code> — <code>port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>-s</code> — <code>secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>-t</code> — <code>terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> — <code>echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> — <code>interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> — <code>help</code>	Displays the help text for the command.
<code>--monitor</code>	defaults to false; if set to false, the configurable attribute values are returned. If set to true, the monitorable attribute values are returned.

**Operands** *dotted\_parent\_element\_name* configurable or monitorable element name.

**Examples** EXAMPLE 1 Using `list` to view all dotted-name prefixes

```
asadmin> list --user admin --passwordfile password.txt
--port 5001 "*"
server
server.admin-service
server.admin-service.das-config
server.application-ref.MEjbApp
server.application-ref.__ejb_container_timer_app
server.application-ref.adminapp
server.application-ref.admingui
server.application-ref.com_sun_web_ui
server.applications
server.applications.j2ee-application.MEjbApp
server.applications.j2ee-application.__ejb_container_timer_app
server.applications.web-module.adminapp
server.applications.web-module.admingui
server.applications.web-module.com_sun_web_ui
server.ejb-container
server.http-service
server.http-service.http-listener.admin-listener
server.http-service.http-listener.http-listener-1
server.http-service.http-listener.http-listener-2
server.iioop-service
server.iioop-service.iioop-listener.SSL
```



**EXAMPLE 1** Using `list` to view all dotted-name prefixes (Continued)

```
server.iiop-service.iiop-listener.SSL.ssl
server.iiop-service.iiop-listener.SSL_MUTUALAUTH
server.iiop-service.iiop-listener.SSL_MUTUALAUTH.ssl
server.iiop-service.iiop-listener.orb-listener-1
server.iiop-service.orb
server.java-config
server.jms-service
server.jms-service.jms-host.default_JMS_host
server.log-service
server.log-service.module-log-levels
server.mdb-container
server.monitoring-service
server.monitoring-service.module-monitoring-levels
server.resource-ref.jdbc/PointBase
server.resource-ref.jdbc/__TimerPool
server.resources
server.resources.jdbc-connection-pool.PointBasePool
server.resources.jdbc-connection-pool.__TimerPool
server.resources.jdbc-resource.jdbc/PointBase
server.resources.jdbc-resource.jdbc/__TimerPool
server.security-service
server.security-service.audit-module.default
server.security-service.auth-realm.certificate
server.security-service.auth-realm.file
server.security-service.jacc-provider.default
server.thread-pools
server.thread-pools.thread-pool.thread-pool-1
server.transaction-service
server.virtual-server.__asadmin
server.virtual-server.server
server.web-container
```

**EXAMPLE 2** Using `list` for an application

```
asadmin> list --user admin --passwordfile password.txt
--host localhost --port 4848 server.applications.j2ee-application
server.applications.j2ee-application.MEjbApp
server.applications.j2ee-application._ejb_container_timer_app
server.applications.j2ee-application.stateless-simple
```

**EXAMPLE 3** Using `list` for a web module

```
asadmin> list --user admin --passwordfile password.txt
--host localhost --port 4848 server.applications.web-module
server.applications.web-module.adminapp
server.applications.web-module.adminguip
```

**EXAMPLE 3** Using `list` for a web module      *(Continued)*

```
server.applications.web-module.com_sun_web_ui
```

**Exit Status** 0                                    command executed successfully  
              1                                    error in executing the command

**See Also** [get\(1\)](#), [set\(1\)](#)

---

<b>Name</b>	list-admin-objects – gets all the administered objects	
<b>Synopsis</b>	<pre>—user <i>admin_user</i> [—passwordfile <i>filename</i>] [—host <i>host_name</i>] [—port <i>port_number</i>] [—secure —s] [—terse=<i>false</i>] [—echo=<i>false</i>] [—interactive=<i>true</i>] [—help] [<i>target</i>]</pre>	
<b>Description</b>	This command lists all the administered objects. This command is supported in remote mode only.	
<b>Options</b>	—u —user	The authorized domain application server administrative username.
	—w —password	The —password option is deprecated. Use —passwordfile instead.
	—passwordfile	This option replaces the —password option. Using the —password option on the command line or through the environment is deprecated. The —passwordfile option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
	—H —host	The machine name where the domain application server is running. The default value is localhost.
	—p —port	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	—s —secure	If set to true, uses SSL/TLS to communicate with the domain application server.
	—t —terse	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	—e —echo	Setting to true will echo the command line statement on the standard output. Default is false.
	—I —interactive	If set to true (default), only the required password options are prompted.
	—h —help	Displays the help text for the command.

**Operands** *target* This is the name of the target upon which the command is operating. The valid targets for this command are instance, cluster, 'domain,' and 'server.' Server is the default option. This command is used by the Enterprise Edition only.

**Examples** EXAMPLE 1 Using list-admin-objects

```
asadmin> list-admin-objects --user admin --password admin123 instance1  
Command list-admin-objects executed successfully
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-admin-object\(1\)](#), [delete-admin-object\(1\)](#)

<b>Name</b>	list-application-refs – lists the existing application references														
<b>Synopsis</b>	<b>list-application-refs</b> <code>--user</code> <i>admin_user</i> [ <code>--passwordfile</code> <i>filename</i> ] [ <code>--host</code> <i>host_name</i> ] [ <code>--port</code> <i>port_number</i> ] [ <code>--secure -s</code> ] [ <code>--terse=false</code> ] [ <code>--echo=false</code> ] [ <code>--interactive=true</code> ] [ <code>--help</code> ] [ <i>target</i> ]														
<b>Description</b>	<p>The <code>list-application-refs</code> command lists all application references in a cluster or an unclustered server instance. This effectively lists all the modules deployed on the specified target (for example, J2EE applications, Web modules, and enterprise bean modules).</p> <p>The target instance or instances making up the cluster need not be running or available for this command to succeed.</p> <p>This command is supported in remote mode only.</p>														
<b>Options</b>	<table border="0"> <tr> <td style="vertical-align: top;"><code>-u</code> <code>--user</code></td> <td>The authorized domain application server administrative username.</td> </tr> <tr> <td style="vertical-align: top;"><code>-w</code> <code>--password</code></td> <td>The <code>--password</code> option is deprecated. Use <code>--passwordfile</code> instead.</td> </tr> <tr> <td style="vertical-align: top;"><code>--passwordfile</code></td> <td>This option replaces the <code>--password</code> option. Using the <code>--password</code> option on the command line or through the environment is deprecated. The <code>--passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</td> </tr> <tr> <td style="vertical-align: top;"><code>-H</code> <code>--host</code></td> <td>The machine name where the domain application server is running. The default value is <code>localhost</code>.</td> </tr> <tr> <td style="vertical-align: top;"><code>-p</code> <code>--port</code></td> <td>The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</td> </tr> <tr> <td style="vertical-align: top;"><code>-s</code> <code>--secure</code></td> <td>If set to true, uses SSL/TLS to communicate with the domain application server.</td> </tr> <tr> <td style="vertical-align: top;"><code>-t</code> <code>--terse</code></td> <td>Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</td> </tr> </table>	<code>-u</code> <code>--user</code>	The authorized domain application server administrative username.	<code>-w</code> <code>--password</code>	The <code>--password</code> option is deprecated. Use <code>--passwordfile</code> instead.	<code>--passwordfile</code>	This option replaces the <code>--password</code> option. Using the <code>--password</code> option on the command line or through the environment is deprecated. The <code>--passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.	<code>-H</code> <code>--host</code>	The machine name where the domain application server is running. The default value is <code>localhost</code> .	<code>-p</code> <code>--port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.	<code>-s</code> <code>--secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.	<code>-t</code> <code>--terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-u</code> <code>--user</code>	The authorized domain application server administrative username.														
<code>-w</code> <code>--password</code>	The <code>--password</code> option is deprecated. Use <code>--passwordfile</code> instead.														
<code>--passwordfile</code>	This option replaces the <code>--password</code> option. Using the <code>--password</code> option on the command line or through the environment is deprecated. The <code>--passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.														
<code>-H</code> <code>--host</code>	The machine name where the domain application server is running. The default value is <code>localhost</code> .														
<code>-p</code> <code>--port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.														
<code>-s</code> <code>--secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.														
<code>-t</code> <code>--terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.														

<code>-e</code>	<code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code>	<code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code>	<code>—help</code>	Displays the help text for the command.
<b>Operands</b>	<i>target</i>	The target for which you are listing the application references. Valid values are <ul style="list-style-type: none"><li>▪ <code>server</code>, which lists the application references for the default server instance <code>server</code> and is the default value</li><li>▪ <code>cluster_name</code>, which lists the application references for every server instance in the cluster</li><li>▪ <code>instance_name</code>, which lists the application references for the named unclustered server instance</li></ul>

**Examples** EXAMPLE 1 Using the list-application-refs command

The following command lists the application references for the unclustered server instance `NewServer`.

```
asadmin> list-application-refs --user admin2
--passwordfile passwords.txt NewServer
ClientSessionMDBApp
MEjbApp
__ejb_container_timer_app
Command list-application-refs executed successfully.
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [create-application-ref\(1\)](#), [delete-application-ref\(1\)](#)

---

<b>Name</b>	list-audit-modules – gets all audit modules and displays them	
<b>Synopsis</b>	<b>list-audit-modules</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <i>target</i> ]	
<b>Description</b>	Lists all the audit modules. This command is supported in remote mode only.	
<b>Options</b>	<b>-u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>-w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
	<b>-H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
	<b>-p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>-s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>-t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>-e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
	<b>-I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.
	<b>-h</b> <b>—help</b>	Displays the help text for the command.

**Operands** *target*

In Enterprise Edition, specifies the target on which you are listing the audit modules. Valid values are

- `server`, which creates the listener for the default server instance `server` and is the default value
- *configuration\_name*, which creates the listener for the named configuration
- *cluster\_name*, which creates the listener for every server instance in the cluster
- *instance\_name*, which creates the listener for a particular server instance

**Examples** EXAMPLE 1 Using `list-audit-modules`

```
asadmin> list-audit-modules --user admin1
--password adminadmin1 --host pigeon --port 5001
sampleAUditModule1
sampleAuditModule2
Command list-audit-modules executed successfully
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [create-audit-module\(1\)](#), [delete-audit-module\(1\)](#)



---

<b>Name</b>	list-auth-realms – lists the authentication realms
<b>Synopsis</b>	<b>list-auth-realms</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <i>target_name</i> ]
<b>Description</b>	Lists the authentication realms. This command is supported in remote mode only.
<b>Options</b>	
<b>-u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>-w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
<b>-H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>-p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>-s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
<b>-t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<b>-e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
<b>-I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.
<b>-h</b> <b>—help</b>	Displays the help text for the command.

**Operands** *target\_name* name of the target on which you want to list the authentication realms.

- *server*, which creates the listener for the default server instance *server* and is the default value
- *configuration\_name*, which creates the listener for the named configuration
- *cluster\_name*, which creates the listener for every server instance in the cluster
- *instance\_name*, which creates the listener for a particular server instance

**Examples** EXAMPLE 1 Using list-auth-realms

```
asadmin> list-auth-realms --user admin --passwordfile password.txt
--host localhost --port 4848
file
ldap
certificate
db
Command list-auth-realms executed successfully
```

Where file, ldap, certificate, and db are the listed authentication realms.

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-auth-realm\(1\)](#), [delete-auth-realm\(1\)](#)

---

<b>Name</b>	list-backups – lists all backups and restores	
<b>Synopsis</b>	<b>list-backups</b> [ <b>—domaindir</b> <i>domain_directory</i> ] [ <b>—description</b> <i>description</i> ] [ <b>—terse=false</b> ] [ <b>—verbose=false</b> ] <i>domain_name</i>	
<b>Description</b>	This command displays the status information about all backups and restores in the backup repository. The <code>list-backups</code> command is supported in local mode only.	
<b>Options</b>	<b>—domaindir</b>	This option specifies the parent directory of the domain upon which the command will operate. The default is <code>install_dir/domains</code> .
	<b>—description</b>	A description can contain any string to help identify the particular backup. The description is displayed as part of the information for any backup.
	<b>-t —terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>-t —verbose</b>	Indicates that output data is displayed with detailed information. Default is false.
<b>Operands</b>	<i>domain_name</i>	This is the name of directory from which the command extracts the list of files and restores. There must be a subdirectory of <code>domaindir</code> with this name.
<b>Examples</b>	<p><b>EXAMPLE 1</b> Using <code>list-backups</code></p> <pre>asadmin&gt;list-backups --domaindir directory1 sample-backup</pre> <p>The command <code>list-backups</code> executed successfully.</p>	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>See Also</b>	<a href="#">backup-domain(1)</a> , <a href="#">restore-domain(1)</a>	

---

<b>Name</b>	list-clusters – lists the existing clusters
<b>Synopsis</b>	<b>list-clusters</b> <code>—user</code> <i>admin_user</i> [ <code>—passwordfile</code> <i>filename</i> ] [ <code>—host</code> <i>host_name</i> ] [ <code>—port</code> <i>port_number</i> ] [ <code>—secure</code>   <code>-s</code> ] [ <code>—terse</code> = <i>false</i> ] [ <code>—echo</code> = <i>false</i> ] [ <code>—interactive</code> = <i>true</i> ] [ <code>—help</code> ] [ <i>target</i> ]
<b>Description</b>	The <code>list-clusters</code> command lists the existing clusters.  This command is supported in remote mode only.
<b>Options</b>	<p><code>-u</code> <code>—user</code> The authorized domain application server administrative username.</p> <p><code>-w</code> <code>—password</code> The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.</p> <p><code>—passwordfile</code> This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</p> <p><code>-H</code> <code>—host</code> The machine name where the domain application server is running. The default value is <code>localhost</code>.</p> <p><code>-p</code> <code>—port</code> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><code>-s</code> <code>—secure</code> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><code>-t</code> <code>—terse</code> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p> <p><code>-e</code> <code>—echo</code> Setting to true will echo the command line statement on the standard output. Default is false.</p> <p><code>-I</code> <code>—interactive</code> If set to true (default), only the required password options are prompted.</p>

---

	<code>-h</code> <code>—help</code>	Displays the help text for the command.
<b>Operands</b>	<i>target</i>	Specifies the target for which the clusters are to be listed. Valid values are: <ul style="list-style-type: none"> <li>▪ <code>domain</code>, which lists all clusters in the domain and is the default value</li> <li>▪ <code>cluster_name</code>, which lists the named cluster</li> <li>▪ <code>instance_name</code>, which lists the cluster associated with the clustered server instance. Unlike many of the other uses of <code>instance_name</code>, this is one situation where an unclustered instance cannot be specified.</li> <li>▪ <code>node_agent_name</code>, which lists all clusters associated with the named node agent. For example, if <code>agent1</code> manages <code>server1</code> and <code>server2</code>, which are part of <code>cluster1</code> and <code>cluster2</code>, then <code>cluster1</code> and <code>cluster2</code> will be listed.</li> </ul>
<b>Examples</b>	EXAMPLE 1 Using the list-clusters command	
	The following command lists all clusters in the current domain.	
	<pre>asadmin&gt; list-clusters --user admin1 --passwordfile passwords.txt MyCluster not running Command list-clusters executed successfully.</pre>	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>See Also</b>	<a href="#">create-cluster(1)</a> , <a href="#">delete-cluster(1)</a> , <a href="#">start-cluster(1)</a> , <a href="#">stop-cluster(1)</a>	

---

<b>Name</b>	list-components – lists deployed components
<b>Synopsis</b>	<b>list-components</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—type</b> <i>application ejb web connector</i> ] [ <i>target</i> ]
<b>Description</b>	The command <code>list-components</code> lists all deployed J2EE components. If the <code>--type</code> option is not specified, all components are listed. The available type values are: <code>application</code> (default), <code>ejb</code> , <code>web</code> , and <code>connector</code> . This command is supported in remote mode only.
<b>Options</b>	<p><b>-u</b> <b>—user</b> The authorized domain application server administrative username.</p> <p><b>-w</b> <b>—password</b> The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.</p> <p><b>—passwordfile</b> This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</p> <p><b>-H</b> <b>—host</b> The machine name where the domain application server is running. The default value is <code>localhost</code>.</p> <p><b>-p</b> <b>—port</b> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><b>-s</b> <b>—secure</b> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><b>-t</b> <b>—terse</b> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p> <p><b>-e</b> <b>—echo</b> Setting to true will echo the command line statement on the standard output. Default is false.</p>

---

	<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
	<code>-h</code> <code>—help</code>	Displays the help text for the command.
	<code>-I</code> <code>—type</code>	This is the type of component to be listed. The options are application, ejb, web, and connector. If nothing is specified, then all of the components are listed.
<b>Operands</b>	target	This is the name of the target upon which the command operates. The valid options are instance, cluster, 'domain,' and 'server.' This option is used in Enterprise Edition only.
<b>Examples</b>	<p>EXAMPLE 1 Using list-components</p> <pre>asadmin&gt; list-components --type application sampleApp J2EE-application Command list-components executed successfully</pre> <p>Where: the applications that were deployed are listed.</p>	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>See Also</b>	<a href="#">show-component-status(1)</a> , <a href="#">list-sub-components(1)</a>	

---

<b>Name</b>	<code>list-configs</code> – lists all existing configurations
<b>Synopsis</b>	<code>list-configs</code> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <i>target</i> ]
<b>Description</b>	Use the <code>list-configs</code> command to list all existing configurations an existing configuration in the <code>domain.xml</code> file. The <code>target</code> operand is only valid for Enterprise Edition.
<b>Options</b>	
<code>-u</code> <b>—user</b>	The authorized domain application server administrative username.
<code>-w</code> <b>—password</b>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>-H</code> <b>—host</b>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
<code>-p</code> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>-s</code> <b>—secure</b>	If set to <code>true</code> , uses SSL/TLS to communicate with the domain application server.
<code>-t</code> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is <code>false</code> .
<code>-e</code> <b>—echo</b>	Setting to <code>true</code> will echo the command line statement on the standard output. Default is <code>false</code> .
<code>-I</code> <b>—interactive</b>	If set to <code>true</code> (default), only the required password options are prompted.



---

	<code>-h</code> <code>—help</code>	Displays the help text for the command.
<b>Operands</b>	<i>target</i>	In Enterprise Edition, this operand specifies which configurations you can list. Valid values are: <ul style="list-style-type: none"><li>▪ <code>domain</code>, which lists the configurations in the current domain and is the default.</li><li>▪ <code>cluster_name</code>, which lists the configurations in a cluster.</li><li>▪ <code>instance_name</code>, which lists the configurations for a particular instance.</li></ul>
<b>Examples</b>	<b>EXAMPLE 1</b> Using the list-configs command <pre>asadmin&gt; list-configs --user admin --passwordfile passwords.txt server-config default-config my-config Command list-configs executed successfully.</pre>	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>See Also</b>	<a href="#">delete-config(1)</a> , <a href="#">copy-config(1)</a>	

**Name** list-connection—groups – gets the connection groups

**Synopsis** **list-connection-groups**

`--user user_name --password password --host hostname --port admin_port_number  
--instance instance_name http_listener_ID`

**Description** Gets the profiler element associated with the named server instance..

**Options** `--user` identifies the user name associated with the named instance.

`--password` identifies the password associated with the user name.

`--host` identifies the host name for the machine.

`--port` identifies the administrator port number associated with the hostname.

`--instance` identifies the name of the instance associated with the JVM option to be created.

*http\_listener\_ID* a unique identifier for the HTTP listener.

**Examples** `asadmin% list-connection-groups`

**See Also** [create-connection-group\(1\)](#) [delete-connection-group\(1\)](#)

**Name** list-connector-connection-pools – gets connector connection pools that have been created

**Synopsis** **list-connector-connection-pools** `—user` *admin\_user* [`—passwordfile` *filename*] [`—host` *host\_name*] [`—port` *port\_number*] [`—secure|—s`] [`—terse=false`] [`—echo=false`] [`—interactive=true`] [`—help`]

**Description** Use this command to list connector connection pools that have been created.

**Options**

<code>—u</code> <code>—user</code>	The authorized domain application server administrative username.
<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>—H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>—p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>—s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>—t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>—e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>—I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>—h</code> <code>—help</code>	Displays the help text for the command.

**Examples** EXAMPLE 1 Using the list-connector-connection-pools command

```
asadmin> list-connector-connection-pools --user admin -passwordfile filename
jms/qConnPool
Command list-connector-connection-pools executed successfully
```

Where jms/qConnPool is the connector connection pool that is listed.

**Exit Status**

0	command executed successfully
1	error in executing the command

**See Also** [create-connector-connection-pool\(1\)](#), [delete-connector-connection-pool\(1\)](#)

---

<b>Name</b>	list-connector-resources – gets all connector resources
<b>Synopsis</b>	<b>list-connector-resources</b> <code>--user</code> <i>admin_user</i> [ <code>--passwordfile</code> <i>filename</i> ] [ <code>--host</code> <i>host_name</i> ] [ <code>--port</code> <i>port_number</i> ] [ <code>--secure -s</code> ] [ <code>--terse=false</code> ] [ <code>--echo=false</code> ] [ <code>--interactive=true</code> ] [ <code>--help</code> ] [ <code>--target</code> <i>target</i> ]
<b>Description</b>	This command lists all connector resources.
<b>Options</b>	<p><code>-u</code> <code>--user</code> The authorized domain application server administrative username.</p> <p><code>-w</code> <code>--password</code> The <code>--password</code> option is deprecated. Use <code>--passwordfile</code> instead.</p> <p><code>--passwordfile</code> This option replaces the <code>--password</code> option. Using the <code>--password</code> option on the command line or through the environment is deprecated. The <code>--passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</p> <p><code>-H</code> <code>--host</code> The machine name where the domain application server is running. The default value is localhost.</p> <p><code>-p</code> <code>--port</code> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><code>-s</code> <code>--secure</code> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><code>-t</code> <code>--terse</code> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p> <p><code>-e</code> <code>--echo</code> Setting to true will echo the command line statement on the standard output. Default is false.</p> <p><code>-I</code> <code>--interactive</code> If set to true (default), only the required password options are prompted.</p> <p><code>-h</code> <code>--help</code> Displays the help text for the command.</p>

**Operands** *target*

In Enterprise Edition only, this operand specifies which configurations you can list. Valid values are:

- `server`, which lists the connector resources in the current domain and is the default.
- `domain`, which lists the connector resources in the current domain.
- `cluster_name`, which lists the connector resources in a cluster.
- `instance_name`, which lists the connector resources for a particular instance.

**Examples** EXAMPLE 1 Using the list-connector-resources command

```
asadmin> list-connector-resources --user admin
--passwordfile --password --host instance1
--port 5001 target server
resource10
resource20
resource35
```

Command list-connector-resources executed successfully.

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [create-connector-resource\(1\)](#), [delete-connector-resource\(1\)](#)

- Name** list-connector-security-map – lists the security maps belonging to the specified connector connection pool
- Synopsis** **list-connector-security-maps** `—user` *admin\_user* [`—passwordfile` *filename*] [`—host` *host\_name*] [`—port` *port\_number*] [`—secure|—s`] [`—terse=false`] [`—echo=false`] [`—interactive=true`] [`—help`] [`—verbose=false`] [`—securitymap` *security\_map\_name*] *connector\_connection\_pool\_name*
- Description** Use this command to list the security maps belonging to the specified connector connection pool.
- For this command to succeed, you must have first created a connector connection pool using the `create-connector-connection-pool` command.
- This command is supported in remote mode only.
- Options** If an option has a short option name, then the short option precedes the long option name. Short options have one dash whereas long options have two dashes.
- |  |  |
|--|--|
| <code>—u</code> <code>—user</code>     | The authorized domain application server administrative username.  |
| <code>—w</code> <code>—password</code> | The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.   |
| <code>—passwordfile</code>             | This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on. |
| <code>—H</code> <code>—host</code>     | The machine name where the domain application server is running. The default value is localhost.   |
| <code>—p</code> <code>—port</code>     | The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.  |
| <code>—s</code> <code>—secure</code>   | If set to true, uses SSL/TLS to communicate with the domain application server.  |

<code>-t</code> <code>--terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>--echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>--interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>--help</code>	Displays the help text for the command.
<code>--target</code>	This option is deprecated in this release.
<code>--verbose</code>	This property returns a list including the identity, principals, and security name.
<code>--securitymap</code>	This property specifies the name of the security map contained within the connector connection pool from which the identity and principals should be listed. With this option, <code>-verbose</code> is redundant.

**Operands** `connector_connection_pool_name` name of the connector connection pool for which you want to list security maps.

**Examples** **EXAMPLE 1** Using `list-connector-security-maps` with the security map option

It is assumed that the connector pool has already been created using the `create-connector-pool` command.

```
asadmin> list-connector-security-maps --user admin
--passwordfile pwd_file.txt --securitymap mysecuremap securityPool1
Command list-connector-security-maps executed successfully.
```

One security map (mysecuremap) is listed for the securityPool1 pool.

**EXAMPLE 2** Using `list-connector-security-maps` without the security map option

It is assumed that the connector pool has already been created using the `create-connector-pool` command.

```
asadmin> list-connector-security-maps --user admin --passwordfile pwd_file.txt securityPool1
Command list-connector-security-maps executed successfully.
```

All security maps contained within securityPool1 are listed.

<b>Exit Status</b> 0	command executed successfully
1	error in executing the command



**See Also** [delete-connector-security-map\(1\)](#), [create-connector-security-map\(1\)](#),  
[update-connector-security-map\(1\)](#)

**Name** list-custom-resources – gets all custom resources

**Synopsis** **list-custom-resources** `—user` *admin\_user* [`—passwordfile` *filename*]  
 [`—host` *host\_name*] [`—port` *port\_number*] [`—secure`|`-s`] [`—terse=false`]  
 [`—echo=false`] [`—interactive=true`] [`—help`] [*target*]

**Description** Use this command to list custom resources. This command is supported in remote mode only.

**Options**

<code>-u</code> <code>—user</code>	The authorized domain application server administrative username.
<code>-w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>-H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>-p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>-s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>-t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.

---

**Operands** *target* In Enterprise Edition only, this operand specifies the location of the custom resources. Valid values are “domain,” cluster, or instance. The default is domain.

**Examples** EXAMPLE 1 Using the list-custom-resources command

```
asadmin> list-custom-resources --user admin --passwordfile filename
--host plum --port 4848 target6
custom_resource01
custom_resource02
Command list-custom-resources executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-custom-resource\(1\)](#), [delete-custom-resource\(1\)](#)

**Name** list-domains – lists the domains in the specified domain directory

**Synopsis** **list-domains** [`--domaindir` *install\_dir/domains*] [`--terse=false`] [`--echo=false`]  
[`--interactive=true`]

**Description** Use the `list-domains` command to list the domain. If the domain directory is not specified, the domain in the default *install\_dir/domains* directory is listed. If there is more than one domain, the *domain\_name* operand must be identified.

This command is supported in local mode only.

**Options**

<code>--domaindir</code>	The directory where the domains are located. If specified, the path must be accessible in the filesystem. If not specified, the domain in the default <i>install_dir/domains</i> directory are listed.
<code>-t --terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e --echo</code>	Setting to true will echo the command line statement on to the standard output. Default is false.

**Examples** EXAMPLE 1 Using the list-domains command

```
asadmin> list-domains
List of domains:
domain1 running
samples not running
```

Where: the `domain1` and `samples` are the domains located in the default *install\_dir/domains* directory.

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

<b>Error Codes</b>	0	error message
	1	error message

**See Also** [create-domain\(1\)](#), [delete-domain\(1\)](#), [start-domain\(1\)](#), [stop-domain\(1\)](#),

---

<b>Name</b>	list-file-groups – lists file groups	
<b>Synopsis</b>	<b>list-file-groups</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—name</b> <i>username</i> ] [ <i>target</i> ]	
<b>Description</b>	Use this command to administer user support by the file realm authentication. This command lists available groups in the file user. If the <b>--name</b> option is not specified, all groups are listed.	
	This command is supported in remote mode only.	
<b>Options</b>	<b>-u —user</b>	The authorized domain application server administrative username.
	<b>-w —password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=password</b> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
	<b>-H —host</b>	The machine name where the domain application server is running. The default value is localhost.
	<b>-p —port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>-s —secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>-t —terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>-e —echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.

**-I** **—interactive** If set to true (default), only the required password options are prompted.

**-h** **—help** Displays the help text for the command.

**-name** identifies the name of file user to be created.

**Operands** *target* In Enterprise Edition, this operand specifies which configurations you can list. Valid values are:

- *server*, which lists the file groups in the current server and is the default.
- *domain*, which lists the file groups in the current domain.
- *cluster\_name*, which lists the file groups in a cluster.
- *instance\_name*, which lists the file groups for a particular instance.

**Examples** **EXAMPLE 1** Using the list-file-groups command

```
asadmin> list-file-groups --user admin1 --password adminadmin1
--host pigeon --port 5001 --name sample_user
Command list-file-groups executed successfully
```

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [create-file-user\(1\)](#), [update-file-user\(1\)](#), [delete-file-user\(1\)](#), [list-file-users\(1\)](#)

---

<b>Name</b>	list-file-users – creates a list of file users
<b>Synopsis</b>	<b>list-file-users</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <i>target</i> ]
<b>Description</b>	The <code>list-file-users</code> command creates a list of file users supported by file realm authentication.
<b>Options</b>	<p><b>-u</b> <b>—user</b> The authorized domain application server administrative username.</p> <p><b>-w</b> <b>—password</b> The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.</p> <p><b>—passwordfile</b> This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</p> <p><b>-H</b> <b>—host</b> The machine name where the domain application server is running. The default value is <code>localhost</code>.</p> <p><b>-p</b> <b>—port</b> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><b>-s</b> <b>—secure</b> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><b>-t</b> <b>—terse</b> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p> <p><b>-e</b> <b>—echo</b> Setting to true will echo the command line statement on the standard output. Default is false.</p> <p><b>-I</b> <b>—interactive</b> If set to true (default), only the required password options are prompted.</p> <p><b>-h</b> <b>—help</b> Displays the help text for the command.</p>

`--target`

in Enterprise Edition, specifies the target to which you are deploying. Valid values are

- `server`, which deploys the component to the default server instance `server` and is the default value
- `domain`, which deploys the component to the domain.
- `cluster_name`, which deploys the component to every server instance in the cluster.
- `instance_name`, which deploys the component to a particular sever instance.

**Examples** **EXAMPLE 1** Using the `list-file-users` command

Create file users with the `create-file-user` command before you use this command..

```
asadmin> list-file-users plum
sample_user05
sample_user08
sample_user12
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-file-user\(1\)](#), [delete-file-user\(1\)](#)



<b>Name</b>	list-http-lb-configs - lists load balancer configurations	
<b>Synopsis</b>	<b>list-http-lb-configs</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <i>target</i> ]	
<b>Description</b>	Use the list-http-lb-configs command to list the load balancer configurations. List them all or list them by the cluster or server instance they reference.	
<b>Options</b>	<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
	<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
	<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
	<b>—I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.

`-h`—help Displays the help text for the command.

**Operands** *target* Lists the load balancers by target. Valid values are:

- *cluster\_name*, which lists the load balancer configurations for this cluster.
- *instance\_name*, which lists the load balancer configurations for this instance.

**Examples** EXAMPLE 1 Using the `list-http-lb-config` command

```
asadmin> list-http-lb-configs --user admin --passwordfile file
mycluster-http-lb-config
serverinstlb
Command list-http-lb-configs executed successfully.
```

EXAMPLE 2 Using the `list-http-lb-config` command with the `target` operand.

```
asadmin> list-http-lb-configs --user admin --passwordfile file mycluster
mycluster-http-lb-config
Command list-http-lb-configs executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [delete-http-lb-config\(1\)](#), [create-http-lb-config\(1\)](#)

---

<b>Name</b>	list-http-listeners – lists the existing HTTP listeners
<b>Synopsis</b>	<b>list-http-listeners</b> <code>--user</code> <i>admin_user</i> [ <code>--passwordfile</code> <i>filename</i> ] [ <code>--host</code> <i>host_name</i> ] [ <code>--port</code> <i>port_number</i> ] [ <code>--secure -s</code> ] [ <code>--terse=false</code> ] [ <code>--echo=false</code> ] [ <code>--interactive=true</code> ] [ <code>--help</code> ] [ <i>target</i> ]
<b>Description</b>	The <code>list-http-listeners</code> command lists the existing HTTP listeners. This command is supported in remote mode only.
<b>Options</b>	<p><code>-u</code> <code>--user</code> The authorized domain application server administrative username.</p> <p><code>-w</code> <code>--password</code> The <code>--password</code> option is deprecated. Use <code>--passwordfile</code> instead.</p> <p><code>--passwordfile</code> This option replaces the <code>--password</code> option. Using the <code>--password</code> option on the command line or through the environment is deprecated. The <code>--passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</p> <p><code>-H</code> <code>--host</code> The machine name where the domain application server is running. The default value is <code>localhost</code>.</p> <p><code>-p</code> <code>--port</code> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><code>-s</code> <code>--secure</code> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><code>-t</code> <code>--terse</code> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p> <p><code>-e</code> <code>--echo</code> Setting to true will echo the command line statement on the standard output. Default is false.</p> <p><code>-I</code> <code>--interactive</code> If set to true (default), only the required password options are prompted.</p>

`-h` `—help`

Displays the help text for the command.

**Operands** *target*

In Enterprise Edition, this operand specifies the target for which the HTTP listeners are to be listed. Valid values are:

- `server`, which lists the listeners for the default server instance `server` and is the default value
- *configuration\_name*, which lists the listeners for the specified configuration
- *cluster\_name*, which lists the listeners for the specified cluster
- *instance\_name*, which lists the listeners for a particular server instance

**Examples** **EXAMPLE 1** Using the `list-http-listeners` command

The following command lists all the HTTP listeners for the server instance:

```
asadmin> list-http-listeners --user admin1
--passwordfile passwords.txt --host pigeon --port 5001
http-listener-1
http-listener-2
admin-listener
Command list-http-listeners executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-http-listener\(1\)](#), [delete-http-listener\(1\)](#)

---

<b>Name</b>	list-iioP-listeners – lists the existing IIO P listeners
<b>Synopsis</b>	<b>list-iioP-listeners</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <i>target</i> ]
<b>Description</b>	The <code>list-iioP-listeners</code> command lists the existing IIO P listeners. This command is supported in remote mode only.
<b>Options</b>	<ul style="list-style-type: none"> <li><b>—u</b> <b>—user</b> The authorized domain application server administrative username.</li> <li><b>—w</b> <b>—password</b> The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.</li> <li><b>—passwordfile</b> This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</li> <li><b>—H</b> <b>—host</b> The machine name where the domain application server is running. The default value is <code>localhost</code>.</li> <li><b>—p</b> <b>—port</b> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</li> <li><b>—s</b> <b>—secure</b> If set to true, uses SSL/TLS to communicate with the domain application server.</li> <li><b>—t</b> <b>—terse</b> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</li> <li><b>—e</b> <b>—echo</b> Setting to true will echo the command line statement on the standard output. Default is false.</li> <li><b>—I</b> <b>—interactive</b> If set to true (default), only the required password options are prompted.</li> </ul>

`-h`—help

Displays the help text for the command.

**Operands** *target*

In Enterprise Edition, this operand specifies the target for which the IIOP listeners are to be listed. Valid values are:

- `server`, which lists the listeners in the default server instance `server` and is the default value
- `configuration_name`, which lists the listeners in the specified configuration
- `cluster_name`, which lists the listeners in the specified cluster
- `instance_name`, which lists the listeners in a particular server instance

**Examples** **EXAMPLE 1** Using the `list-iiop-listeners` command

The following command lists all the IIOP listeners for the server instance:

```
asadmin> list-iiop-listeners --user admin
--passwordfile passwords.txt --host fuyako --port 7070
orb-listener-1
SSL
SSL_MUTUALAUTH
sample_iiop_listener
Command list-iiop-listeners executed successfully.
```

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [create-iiop-listener\(1\)](#), [delete-iiop-listener\(1\)](#)

---

<b>Name</b>	list-instances – lists all the instances along with their status																
<b>Synopsis</b>	<b>list-instances</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <i>target</i> ]																
<b>Description</b>	Use the <code>list-instances</code> to list all the instance in the server. The <code>list-instances</code> command can be run both locally and remotely. To list remote instances, the named administration server must be running on the hostname and port number specified. The user authenticates using the password identified for the administration server.																
<b>Options</b>	<table> <tr> <td><b>-u</b> <b>—user</b></td> <td>The authorized domain application server administrative username.</td> </tr> <tr> <td><b>-w</b> <b>—password</b></td> <td>The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.</td> </tr> <tr> <td><b>—passwordfile</b></td> <td>This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</td> </tr> <tr> <td><b>-H</b> <b>—host</b></td> <td>The machine name where the domain application server is running. The default value is <code>localhost</code>.</td> </tr> <tr> <td><b>-p</b> <b>—port</b></td> <td>The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</td> </tr> <tr> <td><b>-s</b> <b>—secure</b></td> <td>If set to true, uses SSL/TLS to communicate with the domain application server.</td> </tr> <tr> <td><b>-t</b> <b>—terse</b></td> <td>Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</td> </tr> <tr> <td><b>-e</b> <b>—echo</b></td> <td>Setting to true will echo the command line statement on the standard output. Default is false.</td> </tr> </table>	<b>-u</b> <b>—user</b>	The authorized domain application server administrative username.	<b>-w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.	<b>-H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is <code>localhost</code> .	<b>-p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.	<b>-s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.	<b>-t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.	<b>-e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
<b>-u</b> <b>—user</b>	The authorized domain application server administrative username.																
<b>-w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.																
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.																
<b>-H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is <code>localhost</code> .																
<b>-p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.																
<b>-s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.																
<b>-t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.																
<b>-e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.																

**-I**—*interactive* If set to true (default), only the required password options are prompted.

**-h**—*help* Displays the help text for the command.

**Operands** *target* This is the name of the target domain the instances you want listed are associated with.

**Examples** **EXAMPLE 1** Using list-instances in local mode

```
asadmin> list-instances --user admin --passwordfile passwords.txt instance1
Command list-instances executed successfully
```

Where: instance1 is listed.

**EXAMPLE 2** Using list-instances in remote mode

```
asadmin> list-instances --user admin --passwordfile passwords.txt
--host pigeon --port 4849
remote_instance1 running
Command list-instances executed successfully
```

Where: remote-instance1 associates with user, passwordfile, host, and port of the remote machine.

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [create-instance\(1\)](#)



---

<b>Name</b>	list-javamail-resources – lists the existing JavaMail session resources	
<b>Synopsis</b>	<b>list-javamail-resources</b> <code>—user</code> <i>admin_user</i> [ <code>—passwordfile</code> <i>filename</i> ] [ <code>—host</code> <i>host_name</i> ] [ <code>—port</code> <i>port_number</i> ] [ <code>—secure —s</code> ] [ <code>—terse=false</code> ] [ <code>—echo=false</code> ] [ <code>—interactive=true</code> ] [ <code>—help</code> ] [ <i>target</i> ]	
<b>Description</b>	The command lists the existing JavaMail session resources. This command is supported in remote mode only.	
<b>Options</b>	<code>—u</code> <code>—user</code>	The authorized domain application server administrative username.
	<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
	<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
	<code>—H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.
	<code>—p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<code>—s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<code>—t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<code>—e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
	<code>—I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.

`-h`—`help`

Displays the help text for the command.

**Operands** *target*

In Enterprise Edition, this operand specifies the target for which the JavaMail session resources are to be listed. Valid values are:

- `server`, which lists the resources for the default server instance `server` and is the default value
- `domain`, which lists the resources for the domain
- *cluster\_name*, which lists the resources for the specified cluster
- *instance\_name*, which lists the resources for a particular server instance

**Examples** **EXAMPLE 1** Using the `list-javamail-resources` command

The following command lists the JavaMail session resources for the server instance:

```
asadmin> list-javamail-resources --user admin1
--passwordfile passwords.txt --host pigeon --port 5001
mail/MyMailSession
Command list-javamail-resources executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-javamail-resource\(1\)](#), [delete-javamail-resource\(1\)](#)

<b>Name</b>	list-jdbc-connection-pools – lists all JDBC connection pools	
<b>Synopsis</b>	<b>list-jdbc-connection-pools</b> <i>—user admin_user</i> [ <i>—passwordfile filename</i> ] [ <i>—host host_name</i> ] [ <i>—port port_number</i> ] [ <i>—secure -s</i> ] [ <i>—terse=false</i> ] [ <i>—echo=false</i> ] [ <i>—interactive=true</i> ] [ <i>—help</i> ]	
<b>Description</b>	Use this command to get the JDBC connection pools that have been created. This command is supported in remoted mode only.	
<b>Options</b>	<i>—u —user</i>	The authorized domain application server administrative username.
	<i>—w —password</i>	The <i>—password</i> option is deprecated. Use <i>—passwordfile</i> instead.
	<i>—passwordfile</i>	This option replaces the <i>—password</i> option. Using the <i>—password</i> option on the command line or through the environment is deprecated. The <i>—passwordfile</i> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
	<i>—H —host</i>	The machine name where the domain application server is running. The default value is localhost.
	<i>—p —port</i>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<i>—s —secure</i>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<i>—t —terse</i>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<i>—e —echo</i>	Setting to true will echo the command line statement on the standard output. Default is false.
	<i>—I —interactive</i>	If set to true (default), only the required password options are prompted.

`-h` `—help` Displays the help text for the command.

**Operands** *target* The target operand is deprecated.

**Examples** **EXAMPLE 1** Using the list-jdbc-connection-pools command

```
asadmin> list-jdbc-connection-pools --user admin --password adminadmin
--host plum --port 7070
my_connection_pool
```

Where: *my\_connection\_pool* is the JDBC connection pool listed.

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [create-jdbc-connection-pool\(1\)](#), [delete-jdbc-connection-pool\(1\)](#)

---

<b>Name</b>	list-jdbc-resources – gets all JDBC resources	
<b>Synopsis</b>	<b>list-jdbc-resources</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] <i>target</i>	
<b>Description</b>	The <code>list-jdbc-resource</code> command produces a list of JDBC resources that have been created. This command is supported in remote mode only.	
<b>Options</b>	<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
	<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
	<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
	<b>—I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.

`-h` `—help`

Displays the help text for the command.

**Operands** *target*

In Enterprise Edition, this operand specifies which jdbc resources you can list. Valid values are:

- `server`, which lists the jdbc resources in the current server and is the default.
- `domain`, which lists the jdbc resources in the current domain.
- *cluster\_name*, which lists the jdbc resources in a cluster.
- *instance\_name*, which lists the jdbc resources for a particular instance.

**Examples** **EXAMPLE 1** Using the list-jdbc-resources command

```
asadmin> list-jdbc-resources instance1
sample_jdbc_resource02
sample_jdbc_resource05
Command executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-jdbc-resource\(1\)](#), [delete-jdbc-resource\(1\)](#)

---

<b>Name</b>	list-jmsdest – lists the existing JMS physical destinations
<b>Synopsis</b>	<b>list-jmsdest</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <i>desttype type</i> ] [ <i>target</i> ]
<b>Description</b>	The <code>list-jmsdest</code> command lists the JMS physical destinations. This command is supported in remote mode only.
<b>Options</b>	
<b>-u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>-w</b> <b>—password</b>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<b>—passwordfile</b>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<b>-H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
<b>-p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>-s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
<b>-t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<b>-e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
<b>-I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.

`-h`—help Displays the help text for the command.  
`-T`—desttype The type of JMS destinations to be listed. Valid values are `topic` and `queue`.

**Operands** *target* In Enterprise Edition, this operand specifies the target for which the physical destinations are to be listed. Although the `list-jmsdest` command is related to resources, a physical destination is created and deleted using the JMS Service, which is part of the configuration. Valid values are:

- `server`, which lists the physical destinations for the default server instance `server` and is the default value
- `configuration_name`, which lists the physical destinations for the specified configuration
- `cluster_name`, which lists the physical destinations for the specified cluster
- `instance_name`, which lists the physical destinations for a particular server instance

**Examples** **EXAMPLE 1** Using the `list-jmsdest` command

The following command lists all the physical destinations for the default server instance:

```
asadmin> list-jmsdest --user admin
--passwordfile passwords.txt --host bluestar --port 4848
PhysicalQueue queue {}
PhysicalTopic topic {}
Command list-jmsdest executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-jmsdest\(1\)](#), [delete-jmsdest\(1\)](#)



---

<b>Name</b>	list-jms-hosts – lists the existing JMS hosts
<b>Synopsis</b>	<b>list-jms-hosts</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <i>target</i> ]
<b>Description</b>	The <code>list-jms-hosts</code> command lists the existing JMS hosts for the JMS service. This command is supported in remote mode only.
<b>Options</b>	<p><b>-u</b> <b>—user</b> The authorized domain application server administrative username.</p> <p><b>-w</b> <b>—password</b> The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.</p> <p><b>—passwordfile</b> This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</p> <p><b>-H</b> <b>—host</b> The machine name where the domain application server is running. The default value is <code>localhost</code>.</p> <p><b>-p</b> <b>—port</b> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><b>-s</b> <b>—secure</b> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><b>-t</b> <b>—terse</b> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p> <p><b>-e</b> <b>—echo</b> Setting to true will echo the command line statement on the standard output. Default is false.</p> <p><b>-I</b> <b>—interactive</b> If set to true (default), only the required password options are prompted.</p>

`-h` `—help`

Displays the help text for the command.

**Operands** *target*

In Enterprise Edition, this operand specifies the target for which the JMS hosts are to be listed. Valid values are:

- `server`, which lists the JMS hosts for the default server instance `server` and is the default value
- *configuration\_name*, which lists the JMS hosts for the specified configuration
- *cluster\_name*, which lists the JMS hosts for the specified cluster
- *instance\_name*, which lists the JMS hosts for a particular server instance

**Examples** **EXAMPLE 1** Using the `list-jms-hosts` command

The following command lists the JMS hosts for the server configuration.

```
asadmin> list-jms-hosts --user admin
--passwordfile passwords.txt server-config
default_JMS_host
MyNewHost
Command list-jms-hosts executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-jms-host\(1\)](#), [delete-jms-host\(1\)](#)

---

<b>Name</b>	list-jms-resources – lists the JMS resources
<b>Synopsis</b>	<b>list-jms-resources</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—restype</b> <i>type</i> ] [ <i>target</i> ]
<b>Description</b>	The <code>list-jms-resources</code> command lists the existing JMS resources (destination and connection factory resources). This command is supported in remote mode only.
<b>Options</b>	
<b>-u —user</b>	The authorized domain application server administrative username.
<b>-w —password</b>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<b>—passwordfile</b>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<b>-H —host</b>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
<b>-p —port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>-s —secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
<b>-t —terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<b>-e —echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
<b>-I —interactive</b>	If set to true (default), only the required password options are prompted.

`-h`—help Displays the help text for the command.

`—restype` The JMS resource type, which can be either `javax.jms.Topic`, `javax.jms.Queue`, `javax.jms.ConnectionFactory`, `javax.jms.TopicConnectionFactory`, or `javax.jms.QueueConnectionFactory`.

**Operands** *target* In Enterprise Edition, this operand specifies the target for which the JMS resources are to be listed. Valid values are:

- `server`, which lists the resources for the default server instance `server` and is the default value
- `domain`, which lists the resources for the domain
- *cluster\_name*, which lists the resources for the specified cluster
- *instance\_name*, which lists the resources for a particular server instance

**Examples** **EXAMPLE 1** Using the `list-jms-resources` command to list all JMS resources

The following command lists all JMS resources:

```
asadmin> list-jms-resources --user admin1
--passwordfile passwords.txt
jms/Queue
jms/Topic
jms/QueueConnectionFactory
jms/DurableTopicConnectionFactory
Command list-jms-resources executed successfully.
```

**EXAMPLE 2** Using the `list-jms-resources` command to list JMS resources of a specified type

The following command lists all topic connection factories:

```
asadmin> list-jms-resources --user admin1
--passwordfile passwords.txt --restype javax.jms.TopicConnectionFactory
jms/DurableTopicConnectionFactory
jms/TopicConnectionFactory
Command list-jms-resources executed successfully.
```

**Exit Status**

0	command executed successfully
1	error in executing the command

---

<b>Name</b>	list-jndi-entries – browses and queries the JNDI tree
<b>Synopsis</b>	<b>list-jndi-entries</b> <code>--user</code> <i>admin_user</i> [ <code>--passwordfile</code> <i>filename</i> ] [ <code>--host</code> <i>host_name</i> ] [ <code>--port</code> <i>port_number</i> ] [ <code>--secure -s</code> ] [ <code>--terse=false</code> ] [ <code>--echo=false</code> ] [ <code>--interactive=true</code> ] [ <code>--help</code> ] [ <code>--context</code> <i>context_name</i> ] [ <code>--target</code> ]
<b>Description</b>	Use this command to browse and query the JNDI tree. This command is supported in remote mode only.
<b>Options</b>	<p><code>-u</code> <code>--user</code> The authorized domain application server administrative username.</p> <p><code>-w</code> <code>--password</code> The <code>--password</code> option is deprecated. Use <code>--passwordfile</code> instead.</p> <p><code>--passwordfile</code> This option replaces the <code>--password</code> option. Using the <code>--password</code> option on the command line or through the environment is deprecated. The <code>--passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</p> <p><code>-H</code> <code>--host</code> The machine name where the domain application server is running. The default value is localhost.</p> <p><code>-p</code> <code>--port</code> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><code>-s</code> <code>--secure</code> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><code>-t</code> <code>--terse</code> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p> <p><code>-e</code> <code>--echo</code> Setting to true will echo the command line statement on the standard output. Default is false.</p> <p><code>-I</code> <code>--interactive</code> If set to true (default), only the required password options are prompted.</p>

`-h`—help Displays the help text for the command.

`—context` The name of the JNDI context or subcontext. If context is not specified, all entries in the naming service are returned. If context (such as *ejb*) is specified, all those entries are returned.

**Operands** *target* In Enterprise Edition, this operand specifies which configurations you can list. Valid values are "server," "domain," "cluster," or "instance."

**Examples** EXAMPLE 1 Using the list-jndi-entries command

```
asadmin> list-jndi-entries --user admin1 --passwordfile adminadmin1
--host localhost --port 5001 --context ejb
Command list-jndi-resources executed successfully
```

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [create-jndi-resource\(1\)](#), [delete-jndi-resource\(1\)](#)

---

<b>Name</b>	list-jndi-resources – lists all existing JNDI resources	
<b>Synopsis</b>	<b>list-jndi-resources</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>—s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <i>target</i> ]	
<b>Description</b>	Use the list-jndi-resources command to identify all existing JNDI resources. This command is supported in remote mode only.	
	The target operand is only valid for Enterprise Edition.	
<b>Options</b>	<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
	<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
	<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.

**-I**—*interactive* If set to true (default), only the required password options are prompted.

**-h**—*help* Displays the help text for the command.

**Operands** *target* In Enterprise Edition, this operand specifies which jndi resources you can list. Valid values 'server,' 'domain,' cluster, instance. The default is server.

**Examples** **EXAMPLE 1** Using the list-jndi-resources command

```
asadmin> list-jndi-resources --user admin --passwordfile passwords.txt --host plum --port 4849 --ta
jndi_resource1
jndi_resource2
jndi_resource3
Command list-jndi-resources executed successfully
```

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [create-jndi-resource\(1\)](#), [delete-jndi-resource\(1\)](#)



<b>Name</b>	list-lifecycle-modules – lists the lifecycle modules																
<b>Synopsis</b>	<b>list-lifecycle-modules</b> <code>—user</code> <i>admin_user</i> [ <code>—passwordfile</code> <i>filename</i> ] <code>[—host</code> <i>host_name</i> ] [ <code>—port</code> <i>port_number</i> ] [ <code>—secure</code>   <code>—s</code> ] [ <code>—terse</code> = <i>false</i> ] <code>[—echo</code> = <i>false</i> ] [ <code>—interactive</code> = <i>true</i> ] [ <code>—help</code> ] [ <i>target</i> ]																
<b>Description</b>	Lists the lifecycle modules. The lifecycle modules provide a means of running short or long duration Java-based tasks within the application server environment. This command is supported in remote mode only.																
<b>Options</b>	<table> <tr> <td><code>—u</code> <code>—user</code></td> <td>The authorized domain application server administrative username.</td> </tr> <tr> <td><code>—w</code> <code>—password</code></td> <td>The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.</td> </tr> <tr> <td><code>—passwordfile</code></td> <td>This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</td> </tr> <tr> <td><code>—H</code> <code>—host</code></td> <td>The machine name where the domain application server is running. The default value is localhost.</td> </tr> <tr> <td><code>—p</code> <code>—port</code></td> <td>The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</td> </tr> <tr> <td><code>—s</code> <code>—secure</code></td> <td>If set to true, uses SSL/TLS to communicate with the domain application server.</td> </tr> <tr> <td><code>—t</code> <code>—terse</code></td> <td>Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</td> </tr> <tr> <td><code>—e</code> <code>—echo</code></td> <td>Setting to true will echo the command line statement on the standard output. Default is false.</td> </tr> </table>	<code>—u</code> <code>—user</code>	The authorized domain application server administrative username.	<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.	<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.	<code>—H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.	<code>—p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.	<code>—s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.	<code>—t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.	<code>—e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>—u</code> <code>—user</code>	The authorized domain application server administrative username.																
<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.																
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.																
<code>—H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.																
<code>—p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.																
<code>—s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.																
<code>—t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.																
<code>—e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.																

**-I**—interactive If set to true (default), only the required password options are prompted.

**-h**—help Displays the help text for the command.

**Operands** **target** This is the name of the resulting location. The valid targets for this command are configuration, instance, cluster, or server. This is used by EE only.

**Examples** **EXAMPLE 1** Using list-lifecycle-modules

```
asadmin> list-lifecycle-modules --user admin
--passwordfile adminpassword.txt --host fuyako --port 7070
customSetup
Server1
```

Where: customSetup is the lifecycle module listed and targetserver is the default target.

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [create-lifecycle-module\(1\)](#), [delete-lifecycle-module\(1\)](#)

- Name** list-message-security-providers – enables administrators to list all security message providers (provider-config sub-elements) for the given message layer (message-security-config element of domain.xml)
- Synopsis** **list-message-security-providers** `—user` *admin\_user* [`—passwordfile` *filename*] [`—host` *host\_name*] [`—port` *port\_number*] [`—secure`|-s] [`—terse`=false] [`—echo`=false] [`—interactive`=true] [`—help`] `—layer` *message\_layer* [*target*]
- Description** Enables administrators to list all security message providers (provider-config sub-elements) for the given message layer (message-security-config element of domain.xml).
- This command is supported in remote mode only.
- Options** If an option has a short option name, then the short option precedes the long option name. Short options have one dash whereas long options have two dashes.
- |  |  |
|--|--|
| <code>—u</code> <code>—user</code>     | The authorized domain application server administrative username.  |
| <code>—w</code> <code>—password</code> | The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.   |
| <code>—passwordfile</code>             | This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on. |
| <code>—H</code> <code>—host</code>     | The machine name where the domain application server is running. The default value is localhost.   |
| <code>—p</code> <code>—port</code>     | The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.  |
| <code>—s</code> <code>—secure</code>   | If set to true, uses SSL/TLS to communicate with the domain application server.  |

<code>-t</code> <code>--terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>--echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>--interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>--help</code>	Displays the help text for the command.
<code>--layer</code>	The message-layer for which the provider has to be listed. The default value is SOAP.

**Operands** *target*

Lists all the objects of the specified type in the named configuration referenced by the named server instance or cluster. In Enterprise Edition, valid values include:

- `server`, which deploys the component to the default server instance `server` and is the default value
- `config`, which deploys the component to the domain.
- `cluster`, which deploys the component to every server instance in the cluster.
- `instance`, which deploys the component to a particular server instance.

**Examples** **EXAMPLE 1** Using `list-message-security-providers`

The following example shows how to list message security providers for a message layer.

```
asadmin> list-message-security-providers --user admin
--layer SOAP
Listing of all message security providers
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [create-message-security-provider\(1\)](#), [delete-message-security-provider\(1\)](#)

---

<b>Name</b>	list-node-agents – lists the node agents along with their status	
<b>Synopsis</b>	<b>list-node-agents</b> <code>—user user</code> <code>—passwordfile filename</code> [ <code>—host localhost</code> ] <code>[—port port_number]</code> [ <code>—secure=false</code> ] [ <code>—terse=false</code> ] [ <code>—echo=false</code> ] <code>[—interactive=true]</code> [ <i>target</i> ]	
<b>Description</b>	The list-node-agents command displays the node agents along with their status (as an example, running or stopped). If the target is omitted, all node agents are listed.	
<b>Options</b>	<code>—u —user</code>	The authorized domain application server administrative username.
	<code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
	<code>—W —passwordfile</code>	The name of the file containing the domain application server password. The syntax for passwordfile is as follows: AS_ADMIN_PASSWORD=password. If this option is not called directly, the user will be prompted for it before the requested action is completed.
	<code>—H —host</code>	The machine name where the domain application server is running.
	<code>—p —port</code>	The port number of the domain application server listening for administration requests. The default port number for Platform Edition is 4848. The default port number for Enterprise Edition is 4949.
	<code>—s —secure</code>	If set to true, this command uses SSL/TLS to communicate with the domain application server. The default is false.
	<code>—t —terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. The default is false.
	<code>—e —echo</code>	Setting this option to true will echo the command line statement on the standard output. The default is false.
	<code>—I —interactive</code>	If this option is set to true (default), the user will be prompted for the required password options.
<b>Operands</b>	<i>target</i>	This operand specifies which node agents are to be listed. The options are: <ul style="list-style-type: none"> <li>▪ “domain” This is the default. Domain lists all of the node agents in the domain.</li> <li>▪ &lt;cluster-name&gt; This lists all of the node agents associated with the named cluster.</li> </ul>

- `<instance-name>` This lists all of the node agents associated with the named server instance.
- `<agent-name>` This lists the named node agent.

**Examples** EXAMPLE 1 Using list-node-agents

This is a basic example of how the command is used.

```
%asadmin>list-node-agents --user admin1 --passwordfile filename
agent1 not running
Command list-node-agents executed successfully.
```

Where: % is the command prompt and agent1 is the only node agent in the domain.

**Exit Status**

0	command executed successfully
1	error in executing the command

**See Also** [create-node-agent\(1\)](#), [delete-node-agent\(1\)](#), [start-node-agent\(1\)](#), [stop-node-agent\(1\)](#)

---

<b>Name</b>	list-password-aliases – lists all password aliases
<b>Synopsis</b>	<b>list-password-aliases</b> <code>—user</code> <i>admin_user</i> [ <code>—passwordfile</code> <i>filename</i> ] [ <code>—host</code> <i>host_name</i> ] [ <code>—port</code> <i>port_number</i> ] [ <code>—secure —s</code> ] [ <code>—terse=false</code> ] [ <code>—echo=false</code> ] [ <code>—interactive=true</code> ] [ <code>—help</code> ]
<b>Description</b>	This command lists all of the password aliases.
<b>Options</b>	<p><code>—u</code> <code>—user</code> The authorized domain application server administrative username.</p> <p><code>—w</code> <code>—password</code> The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.</p> <p><code>—passwordfile</code> This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</p> <p><code>—H</code> <code>—host</code> The machine name where the domain application server is running. The default value is localhost.</p> <p><code>—p</code> <code>—port</code> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><code>—s</code> <code>—secure</code> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><code>—t</code> <code>—terse</code> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p> <p><code>—e</code> <code>—echo</code> Setting to true will echo the command line statement on the standard output. Default is false.</p> <p><code>—I</code> <code>—interactive</code> If set to true (default), only the required password options are prompted.</p> <p><code>—h</code> <code>—help</code> Displays the help text for the command.</p>

**Examples** **EXAMPLE 1** Using list-password-aliases

```
asadmin> list-password-aliases
```

Command list-password-aliases executed successfully

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [delete-password-alias\(1\)](#), [update-password-alias\(1\)](#), [create-password-alias\(1\)](#)



---

<b>Name</b>	list-persistence-resources – gets all the persistence resources
<b>Synopsis</b>	<b>list-persistence-resources</b> <code>—user</code> <i>admin_user</i> [ <code>—passwordfile</code> <i>filename</i> ] [ <code>—host</code> <i>host_name</i> ] [ <code>—port</code> <i>port_number</i> ] [ <code>—secure</code>   <code>-s</code> ] [ <code>—terse</code> = <i>false</i> ] [ <code>—echo</code> = <i>false</i> ] [ <code>—interactive</code> = <i>true</i> ] [ <code>—help</code> ] <i>target</i>
<b>Description</b>	Gets all the persistence resources. This command is supported in remote mode only.
<b>Options</b>	
<code>—u</code> <code>—user</code>	The authorized domain application server administrative username.
<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>—H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>—p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>—s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>—t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>—e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>—I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>—h</code> <code>—help</code>	Displays the help text for the command.

**Operands** *target*

Specifies the target for which you are listing all persistence resources. This option is available only in the Sun Java System Application Server Enterprise Edition. Valid values are

- `server`, which deploys the component to the default server instance `server` and is the default value
- `domain`, which deploys the component to the domain.
- `cluster_name`, which deploys the component to every server instance in the cluster.
- `instance_name`, which deploys the component to a particular sever instance.

**Examples** EXAMPLE 1 Using `list-persistence-resources`

```
asadmin> list-persistence-resources --user admin
--passwordfile secret.txt --host pigeon --port 5001
Command list-persistence-resources executed successfully
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [create-persistence-resource\(1\)](#), [delete-persistence-resource\(1\)](#)

- Name** list-resource-adapter-configs – lists the configuration information created in `domain.xml` for the connector module
- Synopsis** **list-resource-adapter-configs** `—user` *admin\_user* [`—passwordfile` *filename*] [`—host` *host\_name*] [`—port` *port\_number*] [`—secure|-s`] [`—terse=false`] [`—echo=false`] [`—interactive=true`] [`—help`] [`—verbose=false`] [`—rname` *connectorModuleName*] [*target*]
- Description** This command lists the configuration information in the `domain.xml` for the connector module. It lists an entry called `resource-adapter-config` in the `domain.xml`.
- This command is supported in remote mode only.
- Options**
- |  |   |
|--|---|
| <code>—u</code> <code>—user</code>     | The authorized domain application server administrative username.   |
| <code>—w</code> <code>—password</code> | The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.  |
| <code>—passwordfile</code>             | This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on. |
| <code>—H</code> <code>—host</code>     | The machine name where the domain application server is running. The default value is <code>localhost</code> .  |
| <code>—p</code> <code>—port</code>     | The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.   |
| <code>—s</code> <code>—secure</code>   | If set to true, uses SSL/TLS to communicate with the domain application server.   |
| <code>—t</code> <code>—terse</code>    | Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.  |

<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—verbose</code>	Setting this property lists the properties that are configured.
<code>—rname</code>	This is the connector module name.

**Operands** *target* This is the name of the target upon which the command is operating. The valid targets for this command are instance, cluster, “domain,” and “server.” Server is the default option.

This operand is used in EE only.

**Examples** **EXAMPLE 1** Using `list-resource-adapter-configs`

```
asadmin> list-resource-adapter-configs --user admin1
--passwordfile pfile1
Command list-resource-adapter-configs executed successfully
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-resource-adapter-config\(1\)](#), [delete-resource-adapter-config\(1\)](#)

- 
- Name** list-resource-refs – lists the existing resource references
- Synopsis** **list-resource-refs** **—user** *admin\_user* [**—passwordfile** *filename*] [**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**—s**] [**—terse**=*false*] [**—echo**=*false*] [**—interactive**=*true*] [**—help**] [*target*]
- Description** The `list-resource-refs` command lists all resource references in a cluster or an unclustered server instance. This effectively lists all the resources (for example, JDBC resources) available in the JNDI tree of the specified target.
- The target instance or instances making up the cluster need not be running or available for this command to succeed.
- This command is supported in remote mode only.
- Options**
- |                            |  |
|----------------------------|--|
| <b>—u</b> <b>—user</b>     | The authorized domain application server administrative username.  |
| <b>—w</b> <b>—password</b> | The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.   |
| <b>—passwordfile</b>       | This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format:<br><code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on. |
| <b>—H</b> <b>—host</b>     | The machine name where the domain application server is running. The default value is <code>localhost</code> .   |
| <b>—p</b> <b>—port</b>     | The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.  |
| <b>—s</b> <b>—secure</b>   | If set to true, uses SSL/TLS to communicate with the domain application server.  |
| <b>—t</b> <b>—terse</b>    | Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.   |

<code>-e</code>	<code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code>	<code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code>	<code>—help</code>	Displays the help text for the command.
<b>Operands</b>	<i>target</i>	The target for which you are listing the resource references. Valid values are <ul style="list-style-type: none"><li>▪ <code>server</code>, which lists the resource references for the default server instance <code>server</code> and is the default value</li><li>▪ <code>cluster_name</code>, which lists the resource references for every server instance in the cluster</li><li>▪ <code>instance_name</code>, which lists the resource references for the named unclustered server instance</li></ul>

**Examples** EXAMPLE 1 Using the list-resource-refs command

The following command lists the resource references for the cluster MyCluster.

```
asadmin> list-resource-refs --user admin
--passwordfile passwords.txt MyCluster
jms/Topic
```

Command list-resource-refs executed successfully.

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [create-resource-ref\(1\)](#), [delete-resource-ref\(1\)](#)

---

<b>Name</b>	list-sub-components – lists EJBs or Servlets in deployed module or module of deployed application
<b>Synopsis</b>	<b>list-sub-components</b> —user <i>admin_user</i> [—passwordfile <i>filename</i> ] [—host <i>host_name</i> ] [—port <i>port_number</i> ] [—secure —s] [—terse=false] [—echo=false] [—interactive=true] [—help] [—type <i>ejbs servlets</i> ] [—appname <i>appname</i> ] <i>modulename</i>
<b>Description</b>	This command lists EJBs or Servlets in a deployed module or in a module of the deployed application. If a module is not identified, all modules are listed. The --appname option functions only when the given module is standalone. To display a specific module in an application, you must specify the module name and the --appname option. This command is supported in remote mode only.
<b>Options</b>	<p>—u —user                      The authorized domain application server administrative username.</p> <p>—w —password                 The —password option is deprecated. Use —passwordfile instead.</p> <p>—passwordfile                This option replaces the — password option. Using the —password option on the command line or through the environment is deprecated. The —passwordfile option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD=<i>password</i>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.</p> <p>—H —host                      The machine name where the domain application server is running. The default value is localhost.</p> <p>—p —port                      The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p>—s —secure                    If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p>—t —terse                    Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p>

<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—type</code>	This is the type of component to be listed. The options are ejbs and servlets. If nothing is specified, then all of the components are listed.
<code>—appname</code>	To display the sub components of a module in the deployed application, you must specify the modulename and use the <code>—appname</code> option. However, this option is required only when the desired output is the sub component of an embedded module of a deployed application.

**Operands** modulename This is the name of the module containing the sub-component.

**Examples** EXAMPLE 1 Using list-sub-components

```
asadmin> list-sub-components --appname sampleApp --modulename --appname appname1  
modulename
```

Command list-sub-components executed successfully.

**Exit Status**

0	command executed successfully
1	error in executing the command

**See Also** [deploy\(1\)](#), [deploydir\(1\)](#), [undeploy\(1\)](#), [enable\(1\)](#), [disable\(1\)](#), [list-components\(1\)](#)



---

<b>Name</b>	list-system-properties – lists the system properties of the domain, configuration, cluster, or server instance																
<b>Synopsis</b>	<b>lists-system-properties</b> <code>—user</code> <i>admin_user</i> [ <code>—passwordfile</code> <i>filename</i> ] [ <code>—host</code> <i>host_name</i> ] [ <code>—port</code> <i>port_number</i> ] [ <code>—secure —s</code> ] [ <code>—terse=false</code> ] [ <code>—echo=false</code> ] [ <code>—interactive=true</code> ] [ <code>—help</code> ] [ <code>target</code> <i>target_name</i> ]																
<b>Description</b>	Shared or clustered server instances will often need to override attributes defined in their referenced configuration. Any configuration attribute in a server instance can be overridden through a system property of the corresponding name. This command lists the system properties of a domain, configuration, cluster, or server instance.																
<b>Options</b>	<table border="0"> <tr> <td style="vertical-align: top;"><code>—u</code> <code>—user</code></td> <td>The authorized domain application server administrative username.</td> </tr> <tr> <td style="vertical-align: top;"><code>—w</code> <code>—password</code></td> <td>The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.</td> </tr> <tr> <td style="vertical-align: top;"><code>—passwordfile</code></td> <td>This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</td> </tr> <tr> <td style="vertical-align: top;"><code>—H</code> <code>—host</code></td> <td>The machine name where the domain application server is running. The default value is localhost.</td> </tr> <tr> <td style="vertical-align: top;"><code>—p</code> <code>—port</code></td> <td>The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</td> </tr> <tr> <td style="vertical-align: top;"><code>—s</code> <code>—secure</code></td> <td>If set to true, uses SSL/TLS to communicate with the domain application server.</td> </tr> <tr> <td style="vertical-align: top;"><code>—t</code> <code>—terse</code></td> <td>Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</td> </tr> <tr> <td style="vertical-align: top;"><code>—e</code> <code>—echo</code></td> <td>Setting to true will echo the command line statement on the standard output. Default is false.</td> </tr> </table>	<code>—u</code> <code>—user</code>	The authorized domain application server administrative username.	<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.	<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.	<code>—H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.	<code>—p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.	<code>—s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.	<code>—t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.	<code>—e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>—u</code> <code>—user</code>	The authorized domain application server administrative username.																
<code>—w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.																
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.																
<code>—H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.																
<code>—p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.																
<code>—s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.																
<code>—t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.																
<code>—e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.																

	<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
	<code>-h</code> <code>—help</code>	Displays the help text for the command.
<b>Operands</b>	<i>target</i>	In Enterprise Edition, specifies the target on which you are listing the system properties. Valid values are <ul style="list-style-type: none"><li>▪ <i>domain</i>, which lists the system properties defined for the domain</li><li>▪ <i>configuration_name</i>, lists the system properties for the named configuration as well as those the cluster inherits from the domain.</li><li>▪ <i>cluster_name</i>, which lists the system properties defined for the named cluster as well as those the cluster inherits from its configuration and the domain.</li><li>▪ <i>instance_name</i>, which lists the system properties defined for the named server instance as well as those the server inherits from its cluster (if the instance is clustered), its configuration, and the domain.</li></ul>
<b>Examples</b>	<b>EXAMPLE 1</b> Using list-system-properties	
	<pre>asadmin&gt; list-system-properties --user admin --passwordfile password.txt --host localhost --port 4849 http-listener-port=1088 mycluster http-listener-port=1088 Command list-system-properties executed successfully.</pre>	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>See Also</b>	<a href="#">create-system-properties(1)</a> , <a href="#">delete-system-property(1)</a>	

---

<b>Name</b>	list-threadpools – lists all the threadpools
<b>Synopsis</b>	<b>list-threadpools</b> <code>--user</code> <i>admin_user</i> [ <code>--passwordfile</code> <i>filename</i> ] [ <code>--host</code> <i>host_name</i> ] [ <code>--port</code> <i>port_number</i> ] [ <code>--secure -s</code> ] [ <code>--terse=false</code> ] [ <code>--echo=false</code> ] [ <code>--interactive=true</code> ] [ <code>--help</code> ] [ <code>--target</code> <i>target_name</i> ]
<b>Description</b>	Lists all the thread pools. This command is supported in remote mode only.
<b>Options</b>	<p><code>-u</code> <code>--user</code> The authorized domain application server administrative username.</p> <p><code>-w</code> <code>--password</code> The <code>--password</code> option is deprecated. Use <code>--passwordfile</code> instead.</p> <p><code>--passwordfile</code> This option replaces the <code>--password</code> option. Using the <code>--password</code> option on the command line or through the environment is deprecated. The <code>--passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</p> <p><code>-H</code> <code>--host</code> The machine name where the domain application server is running. The default value is localhost.</p> <p><code>-p</code> <code>--port</code> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><code>-s</code> <code>--secure</code> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><code>-t</code> <code>--terse</code> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p> <p><code>-e</code> <code>--echo</code> Setting to true will echo the command line statement on the standard output. Default is false.</p> <p><code>-I</code> <code>--interactive</code> If set to true (default), only the required password options are prompted.</p> <p><code>-h</code> <code>--help</code> Displays the help text for the command.</p>

- target** In Enterprise Edition, specifies the target for which you are listing the threadpools. Valid values are
- `server`, which creates the listener for the default server instance `server` and is the default value
  - `configuration_name`, which creates the listener for the named configuration
  - `cluster_name`, which creates the listener for every server instance in the cluster
  - `instance_name`, which creates the listener for a particular server instance

**Examples** EXAMPLE 1 Using `list-threadpools`

```
asadmin> list-threadpools --user admin --passwordfile password.txt
Command list-threadpools executed successfully
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-threadpool\(1\)](#), [delete-threadpool\(1\)](#)

---

<b>Name</b>	list-timers – lists all of the timers owned by server instance(s)
<b>Synopsis</b>	<b>list-timers</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>  -s] [ <b>—terse</b> =false] [ <b>—echo</b> =false] [ <b>—interactive</b> =true] [ <b>—help</b> ] <i>target</i>
<b>Description</b>	This command lists the timers owned by a specific server instance or a cluster of server instances. Administrators can use this information to decide whether to do a timer migration or to verify that a migration has been completed successfully. This command is supported in remote mode only.
<b>Options</b>	<ul style="list-style-type: none"> <li><b>—u —user</b> The authorized domain application server administrative username.</li> <li><b>—w —password</b> The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.</li> <li><b>—passwordfile</b> This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b><i>password</i>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b>, <b>AS_ADMIN_USERPASSWORD</b>, <b>AS_ADMIN_SAVEDMASTERPASSWORD</b>, <b>AS_ADMIN_MQPASSWORD</b>, <b>AS_ADMIN_ALIASPASSWORD</b>, and so on.</li> <li><b>—H —host</b> The machine name where the domain application server is running. The default value is localhost.</li> <li><b>—p —port</b> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</li> <li><b>—s —secure</b> If set to true, uses SSL/TLS to communicate with the domain application server.</li> <li><b>—t —terse</b> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</li> <li><b>—e —echo</b> Setting to true will echo the command line statement on the standard output. Default is false.</li> </ul>

**-I**—*interactive* If set to true (default), only the required password options are prompted.

**-h**—*help* Displays the help text for the command.

**Operands** *target* The target is either a stand-alone server instance or a cluster. If the target is the stand-alone instance, then the number of timers owned by the instance is listed. If the target is a cluster, then the number of timers owned by each instance in the cluster is listed.

**Examples** **EXAMPLE 1** Using list-timers

This is an example of how the command is used.

```
asadmin>list-timers --user admin --passwordfile filename target dancer
```

The list-timers command was executed successfully.

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [migrate-timers\(1\)](#)

---

<b>Name</b>	list-transaction-id – lists the transactions IDs
<b>Synopsis</b>	<b>list-transaction-id</b> <code>--user</code> <i>admin_user</i> [ <code>--passwordfile</code> <i>filename</i> ] [ <code>--host</code> <i>host_name</i> ] [ <code>--port</code> <i>port_number</i> ] [ <code>--secure -s</code> ] [ <code>--terse=false</code> ] [ <code>--echo=false</code> ] [ <code>--interactive=true</code> ] [ <code>--help</code> ] [ <i>target</i> ]
<b>Description</b>	This command lists the transaction IDs in the named target.  This command is supported in remote mode only.
<b>Options</b>	<p><code>-u</code> <code>--user</code> The authorized domain application server administrative username.</p> <p><code>-w</code> <code>--password</code> The <code>--password</code> option is deprecated. Use <code>--passwordfile</code> instead.</p> <p><code>--passwordfile</code> This option replaces the <code>--password</code> option. Using the <code>--password</code> option on the command line or through the environment is deprecated. The <code>--passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</p> <p><code>-H</code> <code>--host</code> The machine name where the domain application server is running. The default value is localhost.</p> <p><code>-p</code> <code>--port</code> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><code>-s</code> <code>--secure</code> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><code>-t</code> <code>--terse</code> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p> <p><code>-e</code> <code>--echo</code> Setting to true will echo the command line statement on the standard output. Default is false.</p> <p><code>-I</code> <code>--interactive</code> If set to true (default), only the required password options are prompted.</p>

`-h`—`help` Displays the help text for the command.

**Operands** *target* This is used in Enterprise Edition only. This is the name of the target upon which the command operates.

**Examples** EXAMPLE 1 Using `list-transaction-id`

```
asadmin> list-transaction-id --user admin --passwordfile password.txt --target server
The list-transaction-id command executed successfully
```

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [freeze-transaction-service\(1\)](#), [unfreeze-transaction-service\(1\)](#), [rollback-transaction\(1\)](#)



---

<b>Name</b>	list-virtual-servers – lists the existing virtual servers	
<b>Synopsis</b>	<b>list-virtual-servers</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <i>target</i> ]	
<b>Description</b>	The <code>list-virtual-servers</code> command lists the existing virtual servers. This command is supported in remote mode only.	
<b>Options</b>	<b>-u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>-w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
	<b>-H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
	<b>-p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>-s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>-t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>-e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
	<b>-I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.

`-h` `—help`

Displays the help text for the command.

**Operands** *target*

In Enterprise Edition, this operand specifies the target for which the virtual servers are to be listed. Valid values are:

- `server`, which lists the virtual servers in the default server instance `server` and is the default value
- *configuration\_name*, which lists the virtual servers in the specified configuration
- *cluster\_name*, which lists the virtual servers in the specified cluster
- *instance\_name*, which lists the virtual servers in a particular server instance

**Examples** **EXAMPLE 1** Using the `list-virtual-servers` command

The following command lists all the virtual servers for the server instance:

```
asadmin> list-virtual-servers --user admin --passwordfile passwords.txt
--host localhost --port 4848
server
__asadmin
Command list-virtual-servers executed successfully.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-virtual-server\(1\)](#), [delete-virtual-server\(1\)](#)

---

<b>Name</b>	migrate-timers – moves a timer when a server instance stops	
<b>Synopsis</b>	<b>migrate-timers</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—destination</b> <i>destination_server_name</i> ] <i>server_name</i>	
<b>Description</b>	The function of the migrate-timer command is to move the timer to a specified server, when the server instance stops or fails abnormally. This command is supported in remote mode only.	
<b>Options</b>	<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
	<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
	<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.

<code>-I</code>	<code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code>	<code>—help</code>	Displays the help text for the command.
<code>—destination</code>		This is the destination server instance. If this option is not specified, then DAS will find a server instance or multiple server instances. A migration notification will be sent to the selected server instances.

**Operands** `server_name` This is the current location of the server instance. The server instance should not be active during this process.

**Examples** EXAMPLE 1 Using migrate-timers

This is a simple example of how to use the command.

```
asadmin>migrate-timers myserver
```

```
This command was successfully executed.
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [list-timers\(1\)](#)

**Name** `multimode` – allows you to execute multiple commands while preserving environment settings and remaining in the `asadmin` utility

**Synopsis** `multimode` [`--file filename`] [`--printprompt=true`] [`--encoding encode`]  
 [`--terse=false`] [`--echo=false`]

**Description** Use `multimode` to process the `asadmin` commands. The command-line interface will prompt you for a command, execute that command, display the results of the command, and then prompt you for the next command. Additionally, all the `asadmin` option names set in this mode are used for all the subsequent commands. You can set your environment and run commands until you exit `multimode` by typing “exit” or “quit.” You can also provide commands by passing a previously prepared list of commands from a file or standard input (pipe). You can invoke `multimode` from within a *multimode* session; once you exit the second *multimode* environment, you return to your original *multimode* environment.

This command is supported in local mode only.

<b>Options</b>	<code>--file</code>	reads the commands as defined in the file.
	<code>--printprompt</code>	allows the printing of <code>asadmin</code> prompt after each command is executed. Set this option to false when the commands are piped or redirected from the standard input or file. By default the option is set to true.
	<code>--encoding</code>	specifies the locale for the file to be decoded.
	<code>--terse</code>	indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<code>--echo</code>	setting to true will echo the command line statement on to the standard output. Default is false.

**Examples** EXAMPLE 1 Using `multimode` to execute multiple commands

```
% asadmin multimode --file commands_file.txt
```

Where: % is the system prompt. The administrative commands are executed from the `commands_file.txt` file.

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [export\(1\)](#), [unset\(1\)](#)

**Name** package-appclient – packs the application client container libraries and jar files

**Synopsis** **package-appclient**

**Description** Use the package-appclient command to pack the application client container libraries and jar files into an appclient.jar file. The created file is located at *appserver\_install\_dir/lib/appclient/appclient.jar*. The appclient.jar file provides an application client container package targeted at remote hosts that do not contain a server installation.

The appclient.jar archive contains native code and can be used on a target machine that is of similar architecture as the machine where it was produced. So, for example, an appclient.jar produced on a Solaris SPARC platform cannot be used on a Windows client machine.

After copying the appclient.jar file to a remote location, unjar it to get a set of libraries and jar files in the appclient directory

After unjarring on the client machine, modify *appclient\_install\_dir/config/asenv.conf* (asenv.bat for Windows) as follows:

- set AS\_WEBSERVICES\_LIB to *appclient\_install\_dir/lib*
- set AS\_NSS to *appclient\_install\_dir/lib* (*appclient\_install\_dir\bin* for Windows)
- set AS\_IMQ\_LIB to *appclient\_install\_dir/imq/lib*
- set AS\_INSTALL to *appclient\_install\_dir*
- set AS\_JAVA to your JDK 1.4 home directory
- set AS\_ACC\_CONFIG to *appclient\_install\_dir/config/sun-acc.xml*

Modify *appclient\_install\_dir/config/sun-acc.xml* as follows:

- Ensure the DOCTYPE file references *appclient\_install\_dir/lib/dtds*
- Ensure that target-server address attribute references the server machine.
- Ensure that target-server port attribute references the ORB port on the remote machine.
- Ensure that log-service references a log file; if the user wants to put log messages to a log file.

Modify *appclient\_install\_dir/bin/appclient* (*appclient.bat* for Windows) as follows:

- change token %CONFIG\_HOME% to *appclient\_install\_dir/config*

**Interface Stability** Sun often provides developers with early access to new technologies, which allows developers to evaluate with them as soon as possible. Unfortunately, new technologies are prone to changes and standardization often results in interface incompatibility from previous versions.

To make reasonable risk assessments, developers need to know how likely an interface is to change in future releases. To aid developers in making these assessments, interface stability information is included on some manual pages for commands, entry-points, and file formats.

The more stable interfaces can safely be used by nearly all applications, because Sun will endeavor to ensure that these continue to work in future minor releases. Applications that depend only on Standard and Stable interfaces should reliably continue to function correctly on future minor releases (but not necessarily on earlier major releases).

The less stable interfaces allow experimentation and proto-typing, but should be used only with the understanding that they might change incompatibly or even be dropped or replaced with alternatives in future minor releases.

"Interfaces" that Sun does not document (for example, most kernel data structures and some symbols in system header files) may be implementation artifacts. Such internal interfaces are not only subject to incompatible change or removal, but we are unlikely to mention such a change in release notes.

**See Also** [appclient\(1M\)](#)

---

<b>Name</b>	ping-connection-pool – tests that a connection pool is usable
<b>Synopsis</b>	<b>ping-connection-pool</b> <code>—user</code> <i>admin_user</i> [ <code>—passwordfile</code> <i>filename</i> ] [ <code>—host</code> <i>host_name</i> ] [ <code>—port</code> <i>port_number</i> ] [ <code>—secure</code>   <code>-s</code> ] [ <code>—terse=false</code> ] [ <code>—echo=false</code> ] [ <code>—interactive=true</code> ] [ <code>—help</code> ] <i>pool_name</i>
<b>Description</b>	This command tests that a connection pool is usable for both JDBC connection pools and connector connection pools. For example, if you create a new JDBC connection pool for use with an application that is expected to be deployed, before deploying the application, the previously created pool is tested with this command.
<b>Options</b>	<p><code>-u</code> <code>—user</code> The authorized domain application server administrative username.</p> <p><code>-w</code> <code>—password</code> The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.</p> <p><code>—passwordfile</code> This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code>, where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code>, <code>AS_ADMIN_USERPASSWORD</code>, <code>AS_ADMIN_SAVEDMASTERPASSWORD</code>, <code>AS_ADMIN_MQPASSWORD</code>, <code>AS_ADMIN_ALIASPASSWORD</code>, and so on.</p> <p><code>-H</code> <code>—host</code> The machine name where the domain application server is running. The default value is localhost.</p> <p><code>-p</code> <code>—port</code> The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.</p> <p><code>-s</code> <code>—secure</code> If set to true, uses SSL/TLS to communicate with the domain application server.</p> <p><code>-t</code> <code>—terse</code> Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.</p> <p><code>-e</code> <code>—echo</code> Setting to true will echo the command line statement on the standard output. Default is false.</p>



---

	<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
	<code>-h</code> <code>—help</code>	Displays the help text for the command.
<b>Operands</b>	<code>pool_name</code>	This is the name of the pool to test.
<b>Examples</b>	<p><b>EXAMPLE 1</b> Using <code>ping-connection-pool</code></p> <p>Before you can ping a connection pool, you must:</p> <ul style="list-style-type: none"> <li>▪ Create a connection pool with authentication.</li> <li>▪ Make sure the Enterprise Information Server (can be the database) is started.</li> </ul> <pre>asadmin&gt; ping-connection-pool --user admin1 --password adminadmin1 -- pool_name sampleConnectionPool Command ping-connection-pool executed successfully</pre>	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>See Also</b>	<a href="#">create-connector-connection-pool(1)</a> , <a href="#">delete-connector-connection-pool(1)</a> , <a href="#">list-connector-connection-pool(1)</a> , <a href="#">create-jdbc-connection-pool(1)</a> , <a href="#">delete-jdbc-connection-pool(1)</a> , <a href="#">list-jdbc-connection-pools(1)</a>	

**Name** ping-connection-pools – tests that a connection pool is usable

**Synopsis** **ping-connection-pools** **—user** *admin\_user* [**—passwordfile** *filename*]  
[**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**—s**] [**—terse**=*false*]  
[**—echo**=*false*] [**—interactive**=*true*] [**—help**] *pool\_name*

**Description** This command tests that a connection pool is usable for both JDBC connection pools and connector connection pools. For example, if you create a new JDBC connection pool for use with an application that is expected to be deployed, before deploying the application, the previously created pool is tested with this command.

Either a JDBC or connector connectionpool with authentication can be created. You can either use a **—property** option to specify user, password, or other connection information using the command line, or specify the connection information in the xml descriptor file.

Before pinging a connection pool, you must create the connection pool with authentication and ensure that the enterprise server or database is started.

**Options**

<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.

---

<code>-t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.

**Operands** *pool\_name* This is the name of the pool to test.

**Examples** **EXAMPLE 1** Using the ping-connection-pool command

```
asadmin> ping-connection-pool --user admin1 --passwordfile pwordfile
Command ping-connection-pool executed successfully
```

Where: asadmin is the command prompt and sampleConnectionPool is the name of the connection pool to ping.

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [create-connector-connection-pool\(1\)](#), [create-jdbc-connection-pool\(1\)](#)

**Name** recover transactions – manually recovers pending transactions

**Synopsis** **recover-transactions** **—user** *user* **—passwordfile** *filename* [**—host** *localhost*]  
 [**—port** *port\_number*] [**—secure=false**] [**—terse=false**] [**—echo=false**]  
 [**—interactive=true**] [**—delegatedrecovery=false**]  
 [**—transactionlogdir** *tx\_log\_dir* ] [**—recoveryserverid** *recovery\_server\_id*]  
*recovery\_server\_name*

**Description** The function of this command is to manually recover pending transactions. This is used in remote mode only.

**Options**

<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	The name of the file containing the domain application server password. The passwordfile should contain either of the following entries: <code>AS_ADMIN_PASSWORD=<i>password</i></code> or <code>AS_ADMIN_MAPPEDPASSWORD=<i>password</i></code> . If this option is not called directly, you will be prompted for it before the requested action is completed.
<b>—H</b> <b>—host</b>	The machine name where the the domain application server is running.
<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests.
<b>—s</b> <b>—secure</b>	If set to true, this command uses SSL/TLS to communicate with the domain application server.
<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. The default is false.
<b>—e</b> <b>—echo</b>	Setting this option to true will echo the command line statement on the standard output. The default is false.
<b>—I</b> <b>—interactive</b>	If this option is set to true (default), only the required password options are prompted.
<b>—delegatedrecovery</b>	When the <code>delegated-recovery</code> is set to false (the default), transaction recovery is done at the running server. When the <code>delegated-recovery</code> is set to true, another server performs the recovery for the failed server. If the command is set to true and there is no server-related data, the DAS does the delegated recovery.

---

<code>--transactionlogdir</code>	When a server fails it writes the location in its transaction log. This option is required if the <code>--delegatedrecovery</code> option is set to true. If the failed server's transaction logs are copied to some other location to make it available to the surrogate recovery server, this option should be used. If the failed server's <code>transaction-service, tx-log-dir</code> is modified to reflect a new location, then this option is not required.
<code>--recoveryserverid</code>	This option is the server identification id or token for the failed server. This option is required if the <code>--delegaterecovery</code> option is set to true. This option is not necessary if the <code>recovery_server_name</code> operand can give a hint of the <code>recovery_server_id</code> . The <code>recoveryserverid</code> option is not only used in recovery but it is also used in the creation of the XID and later used to recognize the XIDs that belong to this server.
<b>Operands</b> <i>recovery_server_name</i>	This is the name of the server that failed. It is this server that is losing the transaction that will be recovered.
<b>Examples</b> EXAMPLE 1 Using recover-transactions	
	<code>asadmin&gt;recover-transactions serverid1</code> Transaction recovered.
<b>Exit Status</b> 0	command executed successfully
1	error in executing the command
<b>See Also</b> <i>none</i>	

**Name** remove-ha-cluster – returns an HA cluster to non-HA status

**Synopsis** —user *admin\_user* [—passwordfile *filename*] [—host *host\_name*] [—port *port\_number*] [—secure|—s] [—terse=*false*] [—echo=*false*] [—interactive=*true*] [—help] [—haagentport *port\_number*] *clusterName*

**Description** This command returns an HA cluster to non-HA status. Use fully qualified hostnames when specifying the hostlist interfaces explicitly for hosts with multiple network interfaces. This command is supported in remote mode only.

The command performs the following tasks:

- The HA database is stopped.
- The HA database is deleted.
- The command deletes and/or modifies the appropriate resources in domain.xml.

<b>Options</b>	—u—user	The authorized domain application server administrative username.
	—w—password	The —password option is deprecated. Use —passwordfile instead.
	—passwordfile	This option replaces the —password option. Using the —password option on the command line or through the environment is deprecated. The —passwordfile option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
	—H—host	The machine name where the domain application server is running. The default value is localhost.
	—p—port	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	—s—secure	If set to true, uses SSL/TLS to communicate with the domain application server.

---

<code>-t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—haagentport</code>	This is the HA agent port containing the cluster to be changed. The default value is 1862.

**Operands** *clustername* This is the name of the cluster to be altered.

**Examples** EXAMPLE 1 Using `remove-ha-cluster`

```
asadmin> remove-ha-cluster --haagentport 1860 cluster1
Command remove-ha-cluster executed successfully
```

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [configure-ha-cluster\(1\)](#)

**Name** restore-domain – restores files from backup

**Synopsis** **restore-domain** [`--domaindir` *domain\_directory*] [`--filename` *backup\_filename*]  
[*domain\_name*]

**Description** This command restores files under the domain from a backup directory. The restore-domain command is supported in local mode only.

**Options**

<code>--domaindir</code>	This option specifies the parent directory of the domain upon which the command will operate. The default is <code>install_dir/domains</code> .
<code>--filename</code>	This option reads the files for this restore from either the directory or from a zip file, depending upon the nature of the file. If this option is set, then the backup is read directly from the given location. This option is required if the backup directory is not set. There is no default.

**Operands** *domain\_name* This is the name of the root directory of the domain to restore. The default is all domains under `backupdir`.

**Examples** EXAMPLE 1 Using restore-domain

```
asadmin>restore-domain --domaindir directory1 --filename file11
The command restore-domain executed successfully.
```

**Exit Status**

0	command executed successfully
1	error in executing the command

**See Also** [backup-domain\(1\)](#), [list-backups\(1\)](#)



---

<b>Name</b>	rollback-transaction – rolls back the named transaction	
<b>Synopsis</b>	<b>rollback-transaction</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—target</b> <i>target_name</i> ] [ <i>transaction_id</i> ]	
<b>Description</b>	Rolls back the named transaction. This command is supported in remote mode only.	
<b>Options</b>	<b>-u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>-w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
	<b>-H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
	<b>-p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>-s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>-t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>-e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
	<b>-I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.
	<b>-h</b> <b>—help</b>	Displays the help text for the command.

**—target** In Enterprise Edition, specifies the target on which you are rolling back the transactions. Valid values are

- `server`, which creates the listener for the default server instance `server` and is the default value
- `configuration_name`, which creates the listener for the named configuration
- `cluster_name`, which creates the listener for every server instance in the cluster
- `instance_name`, which creates the listener for a particular server instance

**Operands** *transaction\_id* identifier for the transaction to be rolled back..

**Examples** EXAMPLE 1 Using rollback-transaction

```
asadmin> rollback-transaction --user admin --passwordfile password.txt --target server 000000000000
```

**Exit Status** 0 command executed successfully

1 error in executing the command

**See Also** [freeze-transaction-service\(1\)](#), [unfreeze-transaction-service\(1\)](#)

---

<b>Name</b>	set – sets the values of attributes	
<b>Synopsis</b>	<b>set</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>—s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <i>attributename=value</i> ]	
<b>Description</b>	Sets the values of one or more configurable attribute. This command is supported in remote mode only. On Solaris, quotes are needed when executing commands with * as the option value or operand.	
<b>Options</b>	<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
	<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
	<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.

	<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
	<code>-h</code> <code>—help</code>	Displays the help text for the command.
<b>Operands</b>	<code>attributename=value</code>	identifies the attribute name and its value. See the <i>Reference</i> for a listing of the available attribute names.
<b>Examples</b>	EXAMPLE 1 Using set <code>asadmin&gt; set --user admin --passwordfile password.txt --host localhost --port 4848 server.transaction-service.automatic-recovery=true</code>	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>See Also</b>	<a href="#">get(1)</a> , <a href="#">list(1)</a>	

---

<b>Name</b>	show-component-status – displays the status of the deployed component	
<b>Synopsis</b>	<b>show-component-status</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>—s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—target</b> <i>target (defaultserver)</i> ] <i>component-name</i>	
<b>Description</b>	The command <code>show-component-status</code> , gets the status of the deployed component. The status is a string representation returned by the server. The possible status strings include: <code>enabled</code> or <code>disabled</code> . This command is supported in remote mode only.	
<b>Options</b>	<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
	<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
	<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
	<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
	<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.

<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	This is the name of the target upon which the command acts. The valid targets for this command are instance, cluster, “domain,” and “server.” The default is server. The target option is used in Enterprise Edition only.

**Operands** `component-name` This is the name of the component to be listed.

**Examples** `EXAMPLE1` Using `show-component-status`

```
asadmin> show-component-status sampleApplication
```

```
Status of sampleApplication is enabled
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [list-components\(1\)](#), [list-sub-components\(1\)](#)

---

**Name** shutdown – brings down the administration server

**Synopsis** **shutdown** [--user *admin\_user*][--password *admin\_password*][--host *localhost*][--port 4848][--passwordfile *filename*][--secure|-s]

**Description** shutdown gracefully brings down the administration server and all the running instances. You must manually start the administration server to bring it up again.

**Options**

--user	administrative user associated for the instance.
--password	administrative password corresponding to the administrative user.
--host	host name of the machine hosting the administrative instance.
--port	administrative port number associated with the administrative host.
--passwordfile	file containing passwords appropriate for the command (e.g., administrative instance).
--secure	if true, uses SSL/TLS to communicate with the administrative instance.

**Examples** EXAMPLE 1 Using the shutdown command

```
asadmin> shutdown --user admin --password adminadmin --host bluestar --port 4848
Waiting for admin server to shutdown...
Admin server has been shutdown
```

**Exit Status**

0	command executed successfully
1	error in executing the command

**Interface Equivalent** Administration Server page

**See Also** [start-instance\(1\)](#), [stop-instance\(1\)](#), [restart-instance\(1\)](#), [start-domain\(1\)](#), [stop-domain\(1\)](#)

**Name** start-cluster – starts a cluster

**Synopsis** **start-cluster** **—user** *admin\_user* [**—passwordfile** *filename*] [**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**-s**] [**—terse**=*false*] [**—echo**=*false*] [**—interactive**=*true*] [**—help**] *cluster\_name*

**Description** The `start-cluster` command attempts to start all non-running instances in the cluster that are reachable through their Node Agent. In other words, some instances may not be started if their Node Agent is not running.

This command is supported in remote mode only.

<b>Options</b> <b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.



---

<code>-I</code>	<code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code>	<code>—help</code>	Displays the help text for the command.

**Operands** *cluster\_name*      The name of the cluster to be started.

**Examples** **EXAMPLE 1** Using the start-cluster command

The following command starts the cluster named MyCluster.

```
asadmin> start-cluster --user admin1  
--passwordfile passwords.txt MyCluster
```

Command start-cluster executed successfully.

**Exit Status** 0      command executed successfully

1      error in executing the command

**See Also** [stop-cluster\(1\)](#), [create-cluster\(1\)](#), [list-clusters\(1\)](#), [delete-cluster\(1\)](#)

**Name** start-domain – starts a domain

**Synopsis** **start-domain** [**—domaindir** *install\_dir/domains*] [**—user** *admin\_user*]  
 [**—passwordfile** *file\_name*] [**—terse=false**] [**—echo=false**] [**—interactive=true**]  
 [**—verbose=false**] [**—debug=false**] [*domain\_name*]

**Description** Use the `start-domain` command to start a domain. If the domain directory is not specified, the domain in the default `install_dir/domains` directory is started. If there is more than one domain, the `domain_name` operand must be identified.

This command is supported in local mode only.

<b>Options</b> <b>—domaindir</b>	The directory where the domain is to be started. If specified, the path must be accessible in the filesystem. If not specified, the domain in the default <code>install_dir/domains</code> directory is started.
<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<b>—W</b> <b>—passwordfile</b>	The file containing the domain application server password associated with the administrative instance. The password is defined in the following form: AS_ADMIN_PASSWORD= <i>password</i> . Where <i>password</i> is the actual administrator password for the domain.
<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on to the standard output. Default is false.
<b>—I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.
<b>—verbose</b>	By default this flag is set to false. If set to true, detailed server startup output is displayed. Press CTRL-C to kill the server. Press CTRL-\ to print a thread dump.
<b>—debug</b>	By default this flag is set to false. If set to true, the server is started in debug mode and prints the JPDA port on the console.
<b>—domaindir</b>	The directory where the domain is to be started. If specified, the path must be accessible in the filesystem. If not specified, the domain in the default <code>install_dir/domains</code> directory is started.
<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.

<code>-w</code>	<code>--password</code>	The <code>--password</code> option is deprecated. Use <code>--passwordfile</code> instead.
	<code>--passwordfile</code>	This option replaces the <code>--password</code> option. Using the <code>--password</code> option on the command line or through the environment is deprecated. The <code>--passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>MAPPEDPASSWORD</code> , <code>USERPASSWORD</code> , <code>SAVEDMASTERPASSWORD</code> , <code>MQPASSWORD</code> , <code>ALIASPASSWORD</code> , and so on.
<code>-t</code>	<code>--terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code>	<code>--echo</code>	Setting to true will echo the command line statement on to the standard output. Default is false.
<code>-I</code>	<code>--interactive</code>	If set to true (default), only the required password options are prompted.
	<code>--verbose</code>	By default this flag is set to false. If set to true, detailed server startup output is displayed. On UNIX, press <code>CTRL-C</code> to kill the server. On Windows, press <code>Ctrl-Break</code> to kill the server. Press <code>CTRL-\</code> to print a thread dump.
	<code>--debug</code>	By default this flag is set to false. If set to true, the server is started in debug mode and prints the JPDA port on the console.
<b>Operands</b>	<i>domain_name</i>	The unique name of the domain you wish to start.
<b>Examples</b>	<b>EXAMPLE 1</b> Using the <code>start-domain</code> command	
	<pre>asadmin&gt; start-domain --domaindir /export/domains --user admin --passwordfile pass sampleDomain</pre> <p>Where: the <code>sampleDomain</code> domain in the <code>/export/domains</code> directory is started using <code>admin</code> password.</p>	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>See Also</b>	<a href="#">create-domain(1)</a> , <a href="#">delete-domain(1)</a> , <a href="#">stop-domain(1)</a> , <a href="#">list-domains(1)</a>	

**Name** start-instance – starts a server instance

**Synopsis** **start-instance** **—user** *admin\_user* [**—passwordfile** *filename*] [**—host** *host\_name*]  
[**—port** *port\_number*] [**—secure**|**-s**] [**—terse**=*false*] [**—echo**=*false*]  
[**—interactive**=*true*] [**—help**] *instance\_name*

**Description** This command starts an instance with the instance name you specify.

**Options**

<b>-u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>-w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=</b> <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
<b>-H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>-p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>-s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
<b>-t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<b>-e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.
<b>-I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.
<b>-h</b> <b>—help</b>	Displays the help text for the command.

---

**Operands** *instance\_name* This is the name of the server instance to start.

**Examples** EXAMPLE 1 Using start-instance

```
asadmin> start-instance -- instance_name instance1  
Instance instance1 started
```

**Exit Status** 0 command executed successfully

1 error in executing the command

**Interface Equivalent** Server Instance page

**See Also** [delete-instance\(1\)](#), [create-instance\(1\)](#), [stop-instance\(1\)](#), [restart-instance\(1\)](#),  
[start-appserv\(1\)](#), [stop-appserv\(1\)](#), [start-domain\(1\)](#), [stop-domain\(1\)](#)

**Name** start-node-agent – starts a node agent

**Synopsis** **start-node-agent** [`—user user`] [`—passwordfile passwordfile`] [`—secure=true`] [`—terse=false`] [`—echo=false`] [`—interactive=true`] [`—agentdir nodeagent_path`] [`—startinstances=true`] [`nodeagent_name`]

**Description** Use the `start-node-agent` command start a node agent. The command will return control to the user before instances are actually started. The `list-instances` command can be executed to see if they have actually started. This command may take a while to execute since the node agent may need to create and start a number of server instances.

This command is supported in local mode only.

<b>Options</b> <code>—u—user</code>	The authorized domain application server administrative username.
<code>—w—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>—s—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>—t—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>—e—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>—I—interactive</code>	If set to true (default), only the required password options are prompted.
<code>—agentdir</code>	Like a Domain Application Server (DAS), each node agent resides in a top level directory named

---

		<i>agentdir/nodeagent_name</i> . If specified, the path must be accessible in the filesystem. If not specified, the node agent is created in the default <i>install_dir/nodeagents</i> directory.
<code>--startinstances</code>		If set to true, all server instances that are not currently running are started. If set to false, instances are not started. If the option is omitted, it defaults to the value of the node agent's <code>start-servers-in-startup</code> attribute, located in the <code>domain.xml</code> .
<b>Operands</b>	<i>nodeagent_name</i>	The name of the node agent to be started.
<b>Examples</b>	<p><b>EXAMPLE 1</b> Using the start-node-agent</p> <p>This is a basic example of how the command is used.</p> <pre>asadmin&gt;start-node-agent --user admin --passwordfile passwordfile nodeagent1</pre> <p>Nodeagent1 started.</p> <p>Where: nodeagent1 is started in the default <i>install_dir/nodeagents</i> directory.</p>	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>See Also</b>	<a href="#">stop-node-agent(1)</a> , <a href="#">delete-node-agent(1)</a> , <a href="#">list-node-agents(1)</a> , <a href="#">create-node-agent(1)</a>	

**Name** stop-cluster – stops a cluster

**Synopsis** **stop-cluster** **—user** *admin\_user* [**—passwordfile** *filename*] [**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**-s**] [**—terse**=*false*] [**—echo**=*false*] [**—interactive**=*true*] [**—help**] *cluster\_name*

**Description** The stop-cluster command attempts to stop all running instances in the cluster that are reachable through their Node Agent. In other words, some instances may not be stopped if their Node Agent is not running.

This command is supported in remote mode only.

<b>Options</b> <b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on the standard output. Default is false.



---

	<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
	<code>-h</code> <code>—help</code>	Displays the help text for the command.
<b>Operands</b>	<i>cluster_name</i>	The name of the cluster to be started.
<b>Examples</b>	<b>EXAMPLE 1</b> Using the stop-cluster command The following command stops the cluster named MyCluster. <code>asadmin&gt; stop-cluster --user admin1</code> <code>--passwordfile passwords.txt MyCluster</code> Command stop-cluster executed successfully.	
<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command
<b>See Also</b>	<code>start-cluster(1)</code> , <code>create-cluster(1)</code> , <code>list-clusters(1)</code> , <code>delete-cluster(1)</code>	

**Name** stop-domain – stops the domain

**Synopsis** **stop-domain** [**—domaindir** *install\_dir/domains*] [**—user** *admin\_user*]  
[**—passwordfile** *file\_name*] [**—terse=false**] [**—echo=false**] [**—interactive=true**]  
[**—verbose=false**] [**—debug=false**] [*domain\_name*]

**Description** Use the stop-domain command to stop a domain. If the domain directory is not specified, the domain in the default *install\_dir/domains* directory is stopped. If there is more than one domain, the *domain\_name* operand must be identified.

**Options**

<b>—domaindir</b>	The directory where the domain is to be started. If specified, the path must be accessible in the filesystem. If not specified, the domain in the default <i>install_dir/domains</i> directory is started.
<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—W</b> <b>—passwordfile</b>	The file containing the domain application server password associated with the administrative instance. The password is defined in the following form: <i>AS_ADMIN_PASSWORD=password</i> . Where <i>password</i> is the actual administrator password for the domain.
<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<b>—e</b> <b>—echo</b>	Setting to true will echo the command line statement on to the standard output. Default is false.
<b>—I</b> <b>—interactive</b>	If set to true (default), only the required password options are prompted.
<b>—verbose</b>	By default this flag is set to false. If set to true, detailed server startup output is displayed. Press CTRL-C to kill the server. Press CTRL-\ to print a thread dump.
<b>—debug</b>	By default this flag is set to false. If set to true, the server is started in debug mode and prints the JPDA port on the console.
<b>—domaindir</b>	The directory where the domain is to be started. If specified, the path must be accessible in the filesystem. If not specified, the domain in the default <i>install_dir/domains</i> directory is started.
<b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.

---

<code>--passwordfile</code>	This option replaces the <code>--password</code> option. Using the <code>--password</code> option on the command line or through the environment is deprecated. The <code>--passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=password</code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>MAPPEDPASSWORD</code> , <code>USERPASSWORD</code> , <code>SAVEDMASTERPASSWORD</code> , <code>MQPASSWORD</code> , <code>ALIASPASSWORD</code> , and so on.
<code>-t --terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e --echo</code>	Setting to true will echo the command line statement on to the standard output. Default is false.
<code>-I --interactive</code>	If set to true (default), only the required password options are prompted.
<code>--verbose</code>	By default this flag is set to false. If set to true, detailed server startup output is displayed. On UNIX, press CTRL-C to kill the server. On Windows, press Ctrl-Break to kill the server. Press CTRL-\ to print a thread dump.
<code>--debug</code>	By default this flag is set to false. If set to true, the server is started in debug mode and prints the JPDA port on the console.
<b>Operands</b> <code>domain_name</code>	The unique name of the domain you wish to start.
<b>Examples</b>	<p><b>EXAMPLE 1</b> Using <code>start-domain</code></p> <pre>asadmin&gt; stop-domain --domaindir /export/domains --user admin --passwordfile pass sampleDomain</pre> <p>Where: the <code>sampleDomain</code> domain in the <code>/export/domains</code> directory is stopped using <code>admin</code> password.</p>
<b>Exit Status</b>	<p>0 command executed successfully</p> <p>1 error in executing the command</p>
<b>See Also</b>	<code>start-domain(1)</code> , <code>create-domain(1)</code> , <code>delete-domain(1)</code>

**Name** stop-instance – stops a server instance

**Synopsis** `—user admin_user [—passwordfile filename] [—host host_name] [—port port_number] [—secure|—s] [—terse=false] [—echo=false] [—interactive=true] [—help] instance_name`

**Description** Use the stop-instance to stop the instance with the instance name specified. The stop-instance can be run both locally and remotely. The named instance must already exist within the given domain; and the instance must be running.

**Options**

<code>—u —user</code>	The authorized domain application server administrative username.
<code>—w —password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>—H —host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>—p —port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>—s —secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>—t —terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>—e —echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.

`-I` `—interactive` If set to true (default), only the required password options are prompted.

`-h` `—help` Displays the help text for the command.

**Operands** *instance\_name* This is the name of the server instance to stop.

**Examples** EXAMPLE 1 Using `stop-instance` in local mode

```
asadmin> stop-instance --local --domain domain1 server1
Instance server1 stopped
```

Where: the `server1` instance associated with the `domain1` domain is stopped locally.

EXAMPLE 2 Using `stop-instance` in remote mode

```
asadmin> stop-instance --user admin --password bluestar --host localhost --port 4848 server1
Instance server1 stopped
```

Where: the `server1` instance associated with the named user, password, host and port is deleted from the remote machine.

**Exit Status** 0 command executed successfully

1 error in executing the command

**Interface** Server Instance page

**Equivalent**

**See Also** [delete-instance\(1\)](#), [start-instance\(1\)](#), [create-instance\(1\)](#), [start-appserv\(1\)](#), [stop-appserv\(1\)](#), [start-domain\(1\)](#), [stop-domain\(1\)](#)

**Name** stop-node-agent – stops a node agent

**Synopsis** **stop-node-agent** [**—agentdir** *nodeagent\_path* [**—terse=false**] [**—echo=false**]  
[**—interactive=true**]] [*nodeagent\_name*]

**Description** The local stop-node-agent command is used to stop a node agent. If the agent directory is not specified, the node agent in the default *install\_dir/nodeagents* directory is stopped. If there is more than one domain, the *domain\_name* operand must be identified. The stop-node-agent command stops all managed server instances of the node agent.

This command is supported in local mode only.

**Options**

<b>—agentdir</b>	Like a Domain Administration Server (DAS), each node agent resides in a top level directory named <i>agentdir/nodeagent_name</i> . If specified, the path must be accessible in the filesystem. If not specified, the node agent is created in the default <i>install_dir/nodeagents</i> directory.
<b>-t —terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<b>-e —echo</b>	Setting to true will echo the command line statement on to the standard output. Default is false.
<b>-I —Interactive</b>	If set to true (default), only the required options are prompted.

**Operands** *nodeagent\_name* This is the name of the node agent to stop.

**Examples** **EXAMPLE 1** Using stop-node-agent

This is a basic example of how to use the command.

```
%asadmin>stop-node-agent nodeagent1
```

Where: % is the command line prompt. Node agent, nodeagent1, located in default *install\_dir/nodeagents* is stopped.

**Exit Status**

0	command executed successfully
1	error in executing the command

**See Also** [start-node-agent\(1\)](#), [delete-node-agent\(1\)](#), [list-node-agents\(1\)](#), [create-node-agent\(1\)](#)

**Name** undeploy – removes a component from the domain application server

**Synopsis** **undeploy** **—user** *admin\_user* [**—passwordfile** *filename*] [**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**-s**] [**—terse**=*false*] [**—echo**=*false*] [**—interactive**=*true*] [**—help**] [**—droptables** *true/false*] [**—cascade**=*false*] [**—target** *target*] *component\_name*

**Description** undeploy removes the specified component in the domain application server.

The **—droptables** option is only used to undeploy CMP beans for which the tables had been created by the deployment. If not specified, the entries in the deployment descriptors are used.

This command is supported in remote mode only.

<b>Options</b> <b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <b>AS_ADMIN_</b> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <b>AS_ADMIN_PASSWORD=password</b> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <b>AS_ADMIN_MAPPEDPASSWORD</b> , <b>AS_ADMIN_USERPASSWORD</b> , <b>AS_ADMIN_SAVEDMASTERPASSWORD</b> , <b>AS_ADMIN_MQPASSWORD</b> , <b>AS_ADMIN_ALIASPASSWORD</b> , and so on.
<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.

<code>-e</code> <code>--echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>--interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>--help</code>	Displays the help text for the command.
<code>--droptables</code>	If set to true, tables created by application using CMP beans during deployment are dropped. Default is the corresponding entry in the <code>cmp-resource</code> element of the <code>sun-ejb-jar.xml</code> file. If not specified, it defaults to the entries specified in the deployment descriptors.
<code>--cascade</code>	If set to true, it deletes all the connection pools and connector resources associated with the resource adapter being undeployed. If set to false, the undeploy fails if any pools and resources are still associated with the resource adapter. Then, either those pools and resources have to be deleted explicitly, or the option has to be set to true. If the option is set to false, and if there are no pools and resources still associated with the resource adapter, the resource adapter is undeployed. This option is applicable to connectors (resource adapters) and applications.
<code>--target</code>	This option is available only in the Sun Java System Application Server Enterprise Edition. Specifies the target from which you are undeploying. Valid values are: <ul style="list-style-type: none"><li>▪ <code>server</code>, which undeploys the component from the default server instance <code>server</code> and is the default value</li><li>▪ <code>domain</code>, which undeploys the component from the domain.</li><li>▪ <code>cluster_name</code>, which undeploys the component from every server instance in the cluster.</li><li>▪ <code>instance_name</code>, which undeploys the component from a particular sever instance.</li></ul>

**Operands** `component_name` name of the deployed component.

**Examples** EXAMPLE 1 Simple undeployment

Undeploy (uninstall) an application named `Cart`

```
asadmin> undeploy --user admin Cart
```



**EXAMPLE 2** Undeploying an enterprise bean with container-managed persistence (CMP)

Undeploy a CMP bean named `myejb` and drop the corresponding database tables. In a production environment, database tables contain valuable information, so use the `--droptables` option with care.

```
asadmin> undeploy --user admin --droptables=true myejb
```

**EXAMPLE 3** Undeploy a connector (resource adapter)

Undeploy the connector module named `jdbcra` and perform a cascading delete to remove the associated resources and connection pools.

```
asadmin> undeploy --user admin --cascade=true jdbcra
```

<b>Exit Status</b>	0	command executed successfully
	1	error in executing the command

**See Also** [deploy\(1\)](#), [deploydir\(1\)](#), [list-components\(1\)](#)

---

**Name** unfreeze-transaction-service – resumes all suspended transactions

**Synopsis** **unfreeze-transaction-service** `—user` *admin\_user* [`—passwordfile` *filename*] [`—host` *host\_name*] [`—port` *port\_number*] [`—secure`|`-s`] [`—terse`=*false*] [`—echo`=*false*] [`—interactive`=*true*] [`—help`] [`—target` *target\_name*]

**Description** Resumes all the suspended inflight transactions. Invoke this command on an already frozen transaction. This command is supported in remote mode only.

**Options**

<code>-u</code> <code>—user</code>	The authorized domain application server administrative username.
<code>-w</code> <code>—password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<code>-H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>-p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>-s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>-t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.

- `-h` `—help` Displays the help text for the command.
- `—target` Supported in Enterprise edition only. This option specifies the target on which you are unfreezing the Transaction Service. Valid values are
- `server`, which creates the listener for the default server instance `server` and is the default value
  - `configuration_name`, which creates the listener for the named configuration
  - `cluster_name`, which creates the listener for every server instance in the cluster
  - `instance_name`, which creates the listener for a particular server instance

**Operands** `—target` Supported in Enterprise edition only. This option specifies the target on which you are unfreezing the Transaction Service. Valid values are

- `server`, which creates the listener for the default server instance `server` and is the default value
- `configuration_name`, which creates the listener for the named configuration
- `cluster_name`, which creates the listener for every server instance in the cluster
- `instance_name`, which creates the listener for a particular server instance

**Examples** **EXAMPLE 1** Using `unfreeze-transaction-service`

```
asadmin> unfreeze-transaction-service --user admin --passwordfile password.txt --target server
```

**Exit Status**

0	command executed successfully
1	error in executing the command

**See Also** [freeze-transaction-service\(1\)](#), [rollback-transaction\(1\)](#)

**Name** unset – removes one or more variables from the multimode environment

**Synopsis** unset [*env\_var*\*]

**Description** Removes one or more variables you set for the multimode environment. The variables and their associated values will no longer exist in the environment.

**Operands** *env\_var* environment variable to be removed.

**Examples** EXAMPLE 1 Using unset to remove environment variables

```
asadmin> export AS_ADMIN_HOST=bluestar AS_ADMIN_PORT=8000 AS_ADMIN_USER=admin
asadmin> export AS_ADMIN_PREFIX=server1.jms-service
asadmin> export
AS_ADMIN_HOST=bluestar
AS_ADMIN_PORT=8000
AS_ADMIN_USER=admin
AS_ADMIN_PREFIX=server1.jms-service
asadmin> unset AS_ADMIN_PREFIX
asadmin> export
AS_ADMIN_HOST=bluestar
AS_ADMIN_PORT=8000
AS_ADMIN_USER=admin
```

Using the export command without the argument lists the environment variables that are set. Notice the AS\_ADMIN\_PREFIX is not in the environment after running the unset command.

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [export\(1\)](#), [multimode\(1\)](#)

**Name** update-connector-security-map – creates or modifies a security map for the specified connector connection pool

**Synopsis** **update-connector-security-map** —user *admin\_user* [—passwordfile *filename*] [—host *host\_name*] [—port *port\_number*] [—secure|—s] [—terse=false] [—echo=false] [—interactive=true] [—help] —poolname *connector\_connection\_pool\_name* [—addprincipals *principal\_name1*[, *principal\_name1*]\* | —addusergroups *user\_group1*[, *user\_group1*]\*] [—removeprincipals *principal\_name1*[, *principal\_name2*]\*] [—removeusergroups *user\_group1*[, *user\_group2*]\*] [—mappedusername *username*] *security\_map\_name*

**Description** Use this command to create or modify a security map for the specified connector connection pool. If the security map is not present, one is created. If a specific security map is specified, the components of the security map (user name, groups, and principals) are provided.

For this command to succeed, you must have first created a connector connection pool using the `create-connector-connection-pool` command.

The enterprise information system (EIS) is any system that holds the information. It can be a mainframe, a messaging system, a database system, or an application.

This command is supported in remote mode only.

**Options** If an option has a short option name, then the short option precedes the long option name. Short options have one dash whereas long options have two dashes.

—u —user	The authorized domain application server administrative username.
—w —password	The —password option is deprecated. Use —passwordfile instead.
—passwordfile	This option replaces the —password option. Using the —password option on the command line or through the environment is deprecated. The —passwordfile option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.

---

<code>-H</code> <code>—host</code>	The machine name where the domain application server is running. The default value is localhost.
<code>-p</code> <code>—port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<code>-s</code> <code>—secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
<code>-t</code> <code>—terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—target</code>	This option is deprecated in this release.
<code>—poolname</code>	This property specifies the name of the connector connection pool to which the security map that is to be updated or created belongs.
<code>—addprincipals</code>	This property specifies a comma-separated list of EIS-specific principals to be added. Use either the <code>-addprincipals</code> or <code>-addusergroups</code> options, but not both.
<code>—addusergroups</code>	This property specifies a comma-separated list of EIS user groups to be added. Use either the <code>-addprincipals</code> or <code>-addusergroups</code> options, but not both at the same time.
<code>—removeprincipals</code>	This property specifies a comma-separated list of EIS-specific principals to be removed.
<code>—removeusergroups</code>	This property specifies a comma-separated list of EIS user groups to be removed.
<code>—mappedusername</code>	This property specifies the EIS username.
<code>—mappedpassword</code>	The <code>—mappedpassword</code> option is deprecated. Use <code>—passwordfile</code> pointing to a file that contains an entry in the following format: AS_ADMIN_MAPPEDPASSWORD= <i>mapped-password</i> . If not specified using the <code>passwordfile</code> option, the user will be prompted for this password by the <code>asadmin</code> command-line tool.

**Operands** `security_map_name` name of the security map to be created or updated.

**Examples** EXAMPLE 1 Using update-connector-security-map

It is assumed that the connector pool has already been created using the create-connector-pool command.

```
asadmin> update-connector-security-map --user admin
--poolname connector-pool1 --addprincipals principal1, principal2
securityMap1
Command update-connector-security-map executed successfully
```

**Exit Status**

0	command executed successfully
1	error in executing the command

**See Also** [delete-connector-security-map\(1\)](#), [list-connector-security-maps\(1\)](#), [create-connector-security-map\(1\)](#)

---

<b>Name</b>	update-file-user – updates a current file user as specified	
<b>Synopsis</b>	<b>update-file-user</b> <i>—user admin_user</i> [ <i>—passwordfile filename</i> ] [ <i>—host host_name</i> ] [ <i>—port port_number</i> ] [ <i>—secure -s</i> ] [ <i>—terse=false</i> ] [ <i>—echo=false</i> ] [ <i>—interactive=true</i> ] [ <i>—help</i> ] [ <i>—userpassword user_password</i> ] [ <i>—groups user_groups[:user_groups]*</i> ] <i>username</i>	
<b>Description</b>	This command updates an existing entry in keyfile using the specified user_name, user_password and groups. Multiple groups can be entered by separating them, with a colon ":"	
<b>Options</b>	<i>-u</i> <i>—user</i>	The authorized domain application server administrative username.
	<i>-w</i> <i>—password</i>	The <i>—password</i> option is deprecated. Use <i>—passwordfile</i> instead.
	<i>—passwordfile</i>	This option replaces the <i>—password</i> option. Using the <i>—password</i> option on the command line or through the environment is deprecated. The <i>—passwordfile</i> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the AS_ADMIN_ prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: AS_ADMIN_PASSWORD= <i>password</i> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include AS_ADMIN_MAPPEDPASSWORD, AS_ADMIN_USERPASSWORD, AS_ADMIN_SAVEDMASTERPASSWORD, AS_ADMIN_MQPASSWORD, AS_ADMIN_ALIASPASSWORD, and so on.
	<i>-H</i> <i>—host</i>	The machine name where the domain application server is running. The default value is localhost.
	<i>-p</i> <i>—port</i>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<i>-s</i> <i>—secure</i>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<i>-t</i> <i>—terse</i>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
	<i>-e</i> <i>—echo</i>	Setting to true will echo the command line statement on the standard output. Default is false.



---

<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—userpassword</code>	This is the password of the file user.
<code>—groups</code>	This is the name of the group to which the file user belongs.
<b>Operands</b> <code>username</code>	This is the name of file user to be deleted.

**Examples** EXAMPLE 1 Using the update-file-user command

```
asadmin> update-file-user --user admin1 --password adminadmin1
--host pigeon --port 5001 --userpassword sample_password
--groups staff:manager:engineer --username dance
Command update-file-user executed successfully
```

Where: the `sample_user` is the file user updated with the updated user password, groups, and user name.

<b>Exit Status</b> 0	command executed successfully
1	error in executing the command

**See Also** [delete-file-user\(1\)](#), [list-file-users\(1\)](#), [create-file-user\(1\)](#), [list-file-groups\(1\)](#)

**Name** update-password-alias – updates a password alias

**Synopsis** **updates-password-alias** **—user** *admin\_user* [**—passwordfile** *filename*]  
 [**—host** *host\_name*] [**—port** *port\_number*] [**—secure**|**—s**] [**—terse**=*false*]  
 [**—echo**=*false*] [**—interactive**=*true*] [**—help**] [**—aliaspassword** *alias\_password*]  
*aliasname*

**Description** This command updates the transaction IDs in the named target. An alias is a token of the form `#{ALIAS=password-alias-password}`. The password corresponding to the alias name is stored in encrypted form. The password-alias commands take both a secure interactive form (in which the user is prompted for all information) and a more script-friendly form, in which the password is propagated on the command line.

This command is supported in remote mode only.

<b>Options</b> <b>—u</b> <b>—user</b>	The authorized domain application server administrative username.
<b>—w</b> <b>—password</b>	The <b>—password</b> option is deprecated. Use <b>—passwordfile</b> instead.
<b>—passwordfile</b>	This option replaces the <b>—password</b> option. Using the <b>—password</b> option on the command line or through the environment is deprecated. The <b>—passwordfile</b> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
<b>—H</b> <b>—host</b>	The machine name where the domain application server is running. The default value is localhost.
<b>—p</b> <b>—port</b>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
<b>—s</b> <b>—secure</b>	If set to true, uses SSL/TLS to communicate with the domain application server.
<b>—t</b> <b>—terse</b>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.

---

<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—aliaspassword</code>	This is a separate and distinct password corresponding to the original password. <b>WARNING:</b> Passing this password on the command line is not secure.  The password is optional and when omitted, the user is prompted.

**Operands** `aliasname` This is the name of the password as it appears in domain.xml.

**Examples** `EXAMPLE 1` Using update-password-alias

```
asadmin> update-password-alias --aliasname alias1
```

Command update-password-alias executed successfully

**Exit Status** 0 command executed successfully  
1 error in executing the command

**See Also** [delete-password-alias\(1\)](#), [list-password-aliases\(1\)](#), [create-password-alias\(1\)](#)

**Name** `verifier` – validates the J2EE Deployment Descriptors against application server DTDs

**Synopsis** `verifier` [*optional\_parameters*] *jar\_filename*

**Description** Use the `verifier` utility to validate the J2EE deployment descriptors and the Sun Java System Application Server specific deployment descriptors. If the application is not J2EE compliant, an error message is printed.

When you run the `verifier` utility, two results files are created in XML and TXT format. The location where the files are created can be configured using the `-d` option. The directory specified as the destination directory for result files should exist. If no directory is specified, the result files are created in the current directory. Result files are named as *jar\_filename.xml* and *jar\_filename.txt*

The XML file has various sections that are dynamically generated depending on what kind of application or module is being verified. The root tag is `static-verification` which may contain the tags `application`, `ejb`, `web`, `appclient`, `connector`, `other`, `error` and `failure-count`. The tags are self explanatory and are present depending on the type of module being verified. For example, an EAR file containing a web and EJB module will contain the tags `application`, `ejb`, `web`, `other`, and `failure-count`.

If the verifier ran successfully, a result code of 0 is returned. A non-zero error code is returned if the verifier failed to run.

**Options** The optional parameters must be specified as follows:

<code>-d   --destdir</code>	Identifies the destination directory. The verifier results are located in this specified directory. The directory must already exist.
<code>-h   --help-?</code>	Displays the verifier help.
<code>-u   --gui</code>	Enables the Verifier graphical user interface.
<code>-v   --verbose</code>	Turns verbose debugging ON. Default mode is verbose turned off. In verbose mode, the status of each run of each test is displayed on the verifier console.
<code>-V   --version</code>	Displays the Verifier tool version.
<code>-r   --reportlevel<i>level</i></code>	Identifies the result reporting level. The default report level is to display all results. The available reporting levels include:
<code>a   all</code>	Set output reporting level to display all results (default).
<code>f   failures</code>	Set output reporting level to display only failure results.
<code>w   warnings</code>	Set output reporting level to display only warning and failure results.

<b>Operands</b>	<i>jar_filename</i>	name of the ear/war/jar/rar file to perform static verification on. The results of verification are placed in two files <i>jar_filename.xml</i> and <i>jar_filename.txt</i> in the destination directory.
	-a  —app	Runs only the application tests.
	--p  —appclient	Runs only the application client tests.
	-c  —connector	Runs only the connector tests.
	-e  —ejb	Runs only the EJB tests.
	-w  —web	Runs only the web tests.
	-s  —webservices	Runs only the web services tests.
	-l  —webservicesclient	Runs only the web services client tests.

### Examples **EXAMPLE 1** Using verifier in the Verbose Mode

The following example runs the verifier in verbose mode and writes all the results of static verification of the `sample.ear` file to the destination directory named `/verifier-results`.

```
example% verifier -v -rf -d /verifier-results sample.ear
```

Where `-v` runs the verifier in verbose mode, `-d` specifies the destination directory, and `-rf` displays only the failures. The results are stored in `/verifier-results/sample.ear.xml` and `/verifier-results/sample.ear.txt`.

**EXAMPLE 2** Using verifier to run Application and EJB tests

```
example% verifier --app --ejb sample.ear
```

**See Also** [asadmin\(1M\)](#)

**Name** verify-domain-xml – verifies the content of the domain.xml file

**Synopsis** **verify-domain-xml** [`--terse=false`] [`--echo=false`] [`--help`] [`--verbose=false`]  
[`--domaindir` *install\_dir/domains*] [*domain\_name*]

**Description** Verifies the content of the domain.xml file.

**Options**

<code>-t --terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.
<code>-e --echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-h --help</code>	Displays the help text for the command.
<code>--verbose</code>	Turns on verbose debugging mode if true. The default is false.
<code>--domaindir</code>	Specifies the directory where the domains are located. The path must be accessible in the file system. The default is the value of the <code>\$AS_DEF_DOMAINS_PATH</code> environment variable. This variable is defined in <code>asenv.bat/conf</code> . The default value of this variable is <code>install_dir/domains</code> .

**Operands** *domain\_name* Specifies the name of the domain. The default is `domain1`.

**Examples** **EXAMPLE 1** Using verify-domain-xml

```
asadmin> verify-domain-xml --verbose=true domain1
Element: applications
Error: J2eeApplication Module does not contains application name 'MEjbApp'
      J2eeApplication Module does not contains application name '__ejb_container_timer_app'
```

**Exit Status**

0	command executed successfully
1	error in executing the command

<b>Name</b>	version – displays the version information	
<b>Synopsis</b>	<b>version</b> <b>—user</b> <i>admin_user</i> [ <b>—passwordfile</b> <i>filename</i> ] [ <b>—host</b> <i>host_name</i> ] [ <b>—port</b> <i>port_number</i> ] [ <b>—secure</b>   <b>-s</b> ] [ <b>—terse</b> = <i>false</i> ] [ <b>—echo</b> = <i>false</i> ] [ <b>—interactive</b> = <i>true</i> ] [ <b>—help</b> ] [ <b>—verbose</b> = <i>false</i> ]	
<b>Description</b>	Use the <code>version</code> command to displays the version information. If the command-line cannot communicate with the administration server with the given user/password and host/port, then the command-line will retrieve the Version locally and display a warning message. If the <code>—user</code> option is not entered, the command-line will retrieve the version locally and display a warning message. The warning message will not be displayed if the <code>—terse</code> option is entered on the command line.	
	This command is supported in remote mode only.	
<b>Options</b>	<code>-u —user</code>	The authorized domain application server administrative username.
	<code>-w —password</code>	The <code>—password</code> option is deprecated. Use <code>—passwordfile</code> instead.
	<code>—passwordfile</code>	This option replaces the <code>—password</code> option. Using the <code>—password</code> option on the command line or through the environment is deprecated. The <code>—passwordfile</code> option specifies the name of a file containing the password entries in a specified format. The entry for the password must have the <code>AS_ADMIN_</code> prefix followed by the password name in capital letters. For example, to specify the domain application server password, use an entry with the following format: <code>AS_ADMIN_PASSWORD=<i>password</i></code> , where <i>password</i> is the actual administrator password. Other passwords that can be specified include <code>AS_ADMIN_MAPPEDPASSWORD</code> , <code>AS_ADMIN_USERPASSWORD</code> , <code>AS_ADMIN_SAVEDMASTERPASSWORD</code> , <code>AS_ADMIN_MQPASSWORD</code> , <code>AS_ADMIN_ALIASPASSWORD</code> , and so on.
	<code>-H —host</code>	The machine name where the domain application server is running. The default value is <code>localhost</code> .
	<code>-p —port</code>	The port number of the domain application server listening for administration requests. The default port number for Enterprise Edition is 4849.
	<code>-s —secure</code>	If set to true, uses SSL/TLS to communicate with the domain application server.
	<code>-t —terse</code>	Indicates that any output data must be very concise, typically avoiding human-friendly sentences and favoring well-formatted data for consumption by a script. Default is false.

<code>-e</code> <code>—echo</code>	Setting to true will echo the command line statement on the standard output. Default is false.
<code>-I</code> <code>—interactive</code>	If set to true (default), only the required password options are prompted.
<code>-h</code> <code>—help</code>	Displays the help text for the command.
<code>—verbose</code>	By default this flag is set to false. If set to true, the version information is displayed in detail.

**Examples** EXAMPLE 1 Using remote mode to display version

```
asadmin> version  
Java 2 Platform Enterprise Edition 1.4 Application Server
```

EXAMPLE 2 Using remote mode to display version in detail

```
asadmin> version --user admin --passwordfile mysecret  
--host bluestar --port 4848 --verbose  
Java 2 Platform Enterprise Edition 1.4 Application Server (build A021930-126949)
```

<b>Exit Status</b> 0	command executed successfully
1	error in executing the command

**See Also** [help\(1\)](#)



**Name** wscompile – generates stubs, ties, serializers, and WSDL files used in JAX-RPC clients and services

**Synopsis** `wscompile [options] configuration_file`

**Description** Generates the client stubs and server-side ties for the service definition interface that represents the web service interface. Additionally, it generates the WSDL description of the web service interface which is then used to generate the implementation artifacts.

In addition to supporting the generation of stubs, ties, server configuration, and WSDL documents from a set of RMI interfaces, `wscompile` also supports generating stubs, ties and remote interfaces from a WSDL document.

You must specify one of the `-gen` options in order to use `wscompile` as a stand alone generator. You must use either `-import` (for WSDL) or `-define` (for an RMI interface) along with the `-model` option in order to use `wscompile` in conjunction with `wsdeploy`.

Invoking the `wscompile` command without specifying any arguments outputs the usage information.

<b>Options</b>	<code>-cp path</code>	location of the input class files.
	<code>-classpath path</code>	same as <code>-cp path</code> option.
	<code>-d directory</code>	where to place the generated output files.
	<code>-define</code>	read the service's RMI interface, define a service. Use this option with the <code>-model</code> option in order to create a model file for use with the <code>wsdeploy</code> command.
	<code>-f:features</code>	enables the given features. Features are specified as a comma separated list of features. See the list of supported features below.
	<code>-features:features</code>	same as <code>-f:features</code> option.
	<code>-g</code>	generates the debugging information.
	<code>-gen</code>	generates the client-side artifacts.
	<code>-gen:client</code>	same as <code>-gen</code> option.
	<code>-gen:server</code>	generates the server-side artifacts and the WSDL file. If you are using <code>wsdeploy</code> , you do not specify this option.
	<code>-httpproxy:host:port</code>	specifies an HTTP proxy server; defaults to port 8080.
	<code>-import</code>	reads a WSDL file, generates the service RMI interface and a template of the class that implements the interface. Use this option with the <code>-model</code> option in order to create a model file for use with the <code>wsdeploy</code> command.
	<code>-mapping file</code>	writes the mapping file to the specified file.

<code>-model</code>	write the internal model for the given file name. Use this option with the <code>-import</code> option in order to create a model file for use with the <code>wsdeploy</code> command.
<code>-keep</code>	keeps the generated files.
<code>-nd <i>directory</i></code>	directory for the non-class generated files are stored.
<code>-O</code>	optimizes the generated code.
<code>-s <i>directory</i></code>	directory for the generated source files.
<code>-source <i>version</i></code>	generate code for the specified JAX-RPC version. Supported versions are 1.0.1, 1.0.3, 1.1, 1.1.1, and 1.1.2 (the default).
<code>-verbose</code>	output messages about what the compiler is doing.
<code>-version</code>	prints version information.

Exactly one of the `-input`, `-define`, `-gen` options must be specified.

**Supported Features** The `--f` option requires a comma-separated list of features. The following are the supported features.

<code>datahandleronly</code>	always map attachments to data handler type
<code>documentliteral</code>	use document literal encoding
<code>donotoverride</code>	do not regenerate classes that already exist in the classpath.
<code>donotunwrap</code>	disable unwrapping of document/literal wrapper elements in WSI mode (default).
<code>explicitcontext</code>	turn on explicit service context mapping.
<code>infix:<i>name</i></code>	specify an <code>infix</code> to use for generated serializers (Solaris).
<code>infix=<i>name</i></code>	specify an <code>infix</code> to use for generated serializers (Windows).
<code>jaxbenumtype</code>	map anonymous enumeration to its base type.
<code>nodatabinding</code>	turn off data binding for literal encoding.
<code>noencodedtypes</code>	turn off encoding type information.
<code>nomultirefs</code>	turn off support for multiple references.
<code>norpcstructures</code>	do not generate RPC structures ( <code>-import</code> only).
<code>novalidation</code>	turn off validation for the imported WSDL file.
<code>resolveidref</code>	resolve <code>xsd:IDREF</code> .
<code>rpclieltral</code>	use the RPC literal encoding.
<code>searchschema</code>	search schema aggressively for subtypes.

<code>serializeinterfaces</code>	turn on direct serialization of interface types.
<code>strict</code>	generate code strictly compliant with JAX-RPC 1.1 specification.
<code>unwrap</code>	enable unwrapping of document/literal wrapper elements in WSI mode.
<code>useonewayoperations</code>	allow generation of one-way operations.
<code>ws</code>	enable WS-I Basic Profile features, to be used for <code>document/literal</code> , and <code>RPC/literal</code> .
<code>donotoverride</code>	do not regenerate the classes
<code>donotunwrap</code>	disables unwrapping of <code>document/literal</code> wrapper elements in WSI mode. This is on by default.

Note: the `-gen` options are not compatible with `wsdeploy`.

**Configuration File** The `wscompile` command reads the configuration file `config.xml` which contains information that describes the web service. The structure of the file is as follows:

```
<?xml version="1.0" encoding="UTF-8"?>
<configuration
xmlns="http://java.sun.com/xml/ns/jax-rpc/ri/config">
<service> or <wsdl> or <modelfile>
</configuration>
```

The configuration element may contain exactly one `<service>`, `<wsdl>` or `<modelfile>`.

**Service Element** If the `<service>` element is specified, `wscompile` reads the RMI interface that describes the service and generates a WSDL file. In the `<interface>` subelement, the `name` attribute specifies the service's RMI interface, and the `servantName` attribute specifies the class that implements the interface. For example:

```
<service name="CollectionIF_Service"
targetNamespace="http://echoservice.org/wsdl"
typeNameSpace="http://echoservice.org/types"
packageName="stub_tie_generator_test">
<interface name="stub_tie_generator_test.CollectionIF"
servantName="stub_tie_generator_test.CollectionImpl"/>
```

```
</service>
```

**Wsd Element** If the `<wsdl>` element is specified, `wscompile` reads the WSDL file and generates the service's RMI interface. The `location` attribute specifies the URL of the WSDL file, and the `packageName` attribute specifies the package of the classes to be generated. For example:

```
<wsdl
  location="http://tempuri.org/sample.wsdl"
  packageName="org.tempuri.sample"/>
```

**Modelfile Element** This element is for advanced users.

If `config.xml` contains a `<service>` or `<wsdl>` element, `wscompile` can generate a model file that contains the internal data structures that describe the service. If a model file is already generated, it can be reused next time while using `wscompile`. For example:

```
<modelfile location="mymodel.xml.gz"/>
```

**Examples** **EXAMPLE 1** Using `wscompile` to generate client-side artifacts

```
wscompile -gen:client -d outputdir -classpath classpathdir config.xml
```

Where a client side artifact is generated in the `outputdir` for running the service as defined in the `config.xml` file.

**EXAMPLE 2** Using `wscompile` to generate server-side artifacts

```
wscompile -gen:server -d outputdir -classpath classpathdir -model modelfile.Z config.xml
```

Where a server side artifact is generated in the `outputdir` and the `modelfile` in `modelfile.Z` for services defined in the `config.xml` file.

**See Also** [wsdeploy\(1M\)](#)

**Name** wsdeploy – reads a WAR file and the jaxrpc-ri.xml file and generates another WAR file that is ready for deployment

**Synopsis** `wsdeploy -o input_WAR_file options`

**Description** Use the `wsdeploy` command to take a WAR file which does not have implementation specific server side tie classes to generate a deployable WAR file that can be deployed on the application server. `wsdeploy` internally runs `wscompile` with the `-gen:server` option. The `wscompile` command generates classes and a WSDL file which `wsdeploy` includes in the generated WAR file.

Generally, you don't have to run `wsdeploy` because the functions it performs are done automatically when you deploy a WAR with `deploytool` or `asadmin`.

<b>Options</b> <code>-classpath path</code>	location of the input class files.
<code>-keep</code>	keep temporary files.
<code>-tmpdir directory</code>	use the specified directory as a temporary directory
<code>-o output WAR file</code>	required; location of the generated WAR file. This option is required.
<code>-source version</code>	generates code for the specified JAX-RPC SI version. Supported version are: 1.0.1, 1.0.3, 1.1, 1.1.1, and 1.1.2 (the default).
<code>-verbose</code>	outputs messages about what the compiler is doing.
<code>-version</code>	prints version information.

**Input War File** The input WAR file for `wsdeploy` will typically have the following structure:

```

META-INF/MANIFEST.MF
WEB-INF/classes/hello/HelloIF.class
WEB-INF/classes/hello/HelloImpl.class
WEB-INF/jaxrpc-ri.xml
WEB-INF/web.xml

```

Where: `HelloIF` is the service endpoint interface, and `HelloImpl` is the class that implements the interface. The `web.xml` file is the deployment descriptor of a web component.

**jaxrpc-ri.xml File** The following is a simple HelloWorld service.

```

<xml version="1.0" encoding="UTF-8"?>
<webServices>
  xmlns="http://java.sun.com/xml/ns/jax-rpc/ri/dd"
  version="1.0"
  targetNamespaceBase="http://com.test/wsdl"
  typeNamespaceBase="http://com.test/types"
  urlPatternBase="/ws">
  <endpoint
    name="MyHello"

```

```

        displayName="HelloWorld Service"
        description="A simple web service"
        wsdl="/WEB-INF/<wsdlname>
        interface="hello.HelloIF"
        implementation="hello.HelloImpl"/>
    <endpointMapping
        endpointName="MyHello"
        urlPattern="/hello"/>
</webServices>

```

The `webServices()` element must contain one or more `endpoint()` elements. The interface and implementation attributes of `endpoint()` specify the service's interface and implementation class. The `endpointMapping()` element associates the service port with the part of the endpoint URL path that follows the `urlPatternBase()`.

**Namespace Mappings** Here is a schema type name example:

```

schemaType="ns1:SampleType"
xmlns:ns1="http://echoservice.org/types"

```

When generating a Java type from a schema type, `wscpile` gets the classname from the local part of the schema type name. To specify the package name of the generated Java classes, you define a mapping between the schema type namespace and the package name. You define this mapping by adding a `<namespaceMappingRegistry>` element to the `config.xml` file. For example:

```

<service>
...
    <namespaceMappingRegistry>
        <namespaceMapping
            namespace="http://echoservice.org/types"
            packageName="echoservice.org.types"/>
        </namespaceMappingRegistry>
    ....
</service>

```

You can also map namespaces in the opposite direction, from schema types to Java types. In this case, the generated schema types are taken from the package that the type comes from.

**Handlers** A handler accesses a SOAP message that represents an RPC request or response. A handler class must implement the `javax.xml.rpc.handler` interface. Because it accesses a SOAP message, a handler can manipulate the message with the APIs of the `javax.xml.soap` package().

A handler chain is a list of handlers. You may specify one handler chain for the client and one for the server. On the client, you include the `handlerChains()` element in the `jaxrpc-ri.xml` file. On the server, you include this element in the `config.xml` file. Here is an example of the `handlerChains()` element in the `config.xml`:

```
<handlerChains>
  <chain runAt="server"
    roles=
      "http://acme.org/auditing
      "http://acme.org/morphing"
    xmlns:ns1="http://foo/fo-1">
    <handler className="acme.MyHandler"
      headers = "ns1:foo ns1:bar"/>
      <property
        name="property" value="xyz"/>
      </handler>
    </chain>
  </handlerChains>
```

For more information on handlers, see the SOAP message Handlers chapter of the JAX-PRC specifications.

**See Also** [wscompile\(1M\)](#)





# Index

---

## Numbers and Symbols

— list-resource-adapter-configs, 403

## A

add an existing cluster or server instance to an existing load balancer configuration — create-http-lb-ref, 84

add-resources — creates the resources specified in an XML file specified, 14

adds a connection pool with the specified connection pool name — create-connector-connection-pool, 62

adds a lifecycle module — create-lifecycle-module, 119

adds a new HTTP listener socket — create-http-listener, 86

adds a new unbound node agent to a domain — create-node-agent-config, 129

adds an audit-module — create-audit-module, 54

adds new nodes to the named database, initializes devices for the new nodes, and refragments the schema — hadbm addnodes, 266

adds the administered object with the specified JNDI name — create-admin-object, 50

adds an IIOP listener — create-iiop-listener, 89

creates a physical destination — create-jmsdest, 104

creates the named virtual server — create-virtual-server, 151

adds the new authenticated realm — create-auth-realm, 56

allows you to execute multiple commands while preserving environment settings and remaining in the asadmin utility — multimode, 421

appliance — launches the Application Client Container and invokes the client application packaged in the application JAR file, 17

asadmin — utility for performing administrative tasks for the Sun Java System Application Server, 19

asadmin create-persistence-resource, create-persistence-resource — registers a persistence resource, 133

asmigrate — automates migration of J2EE applications from other J2EE platforms to Sun Java System Application Server, 25

automates migration of J2EE applications from other J2EE platforms to Sun Java System Application Server — asmigrate, 25

## B

backup-domain — performs a backup on the domain, 33

brings down the administration server and associated instances — shutdown, 439

## C

capture-schema — stores the database metadata (schema) in a file for use in mapping and execution, 34

change-master-password — changes the master password, 36

changes the master password — change-master-password, 36

checks to see if the JMS service is up and running — jms-ping, 331

clear-ha-store — deletes tables in HADB, 38

- clears the history files on the database — `hadbm clearhistory`, 271
- `configure-ha-cluster` — configures an existing cluster to be High Availability, 40
- configures an existing cluster to be High Availability — `configure-ha-cluster`, 40
- configures and starts the HADB Management Agent — `ma`, 297
- connects to the Management Agent and defines the domain — `definedomain`, 281
- copies an existing configuration to create a new configuration — `copy-configuration`, 48
- `copy-config` — copies an existing configuration to create a new configuration, 48
- `create-admin-object` — adds the administered object with the specified JNDI name, 50
- `create-audit-module` — adds an audit-module, 54
- `create-auth-realm` — adds the new authenticated realm, 56
- `create-connector-connection-pool` — adds a connector pool with the specified connection pool name, 62
- `create-domain` — creates a domain with the given name, 72
- `create-file-user` — creates a new file user, 75
- `create-ha-store` — creates tables in the HADB that are used by HA the cluster, 77
- `create-http-health-checker` — creates a health-checker for a specified load balancer configuration, 79
- `create-http-lb-ref` — add an existing cluster or server instance to an existing load balancer configuration, 84
- `create-http-listener` — adds a new HTTP listener socket, 86
- `create-iiop-listener` — adds an IIOP listener, 89
- `create-instance` — creates an instance, 91
- `create-javamail-resource` — creates a JavaMail session resource, 95
- `create-jdbc-resource` — creates a JDBC resource with the specified JNDI name, 102
- `create-jms-resource` — creates a JMS resource, 109
- `create-jmsdest` — creates a physical destination, 104
- `create-lifecycle-module` — adds a lifecycle module, 119
- `create-message-security-provider` — Enables administrators to create the `message-security-config` and `provider-config` sub-elements for the security service in `domain.xml`, 122
- `create-node-agent` — creates a node agent, 127
- `create-node-agent-config` — adds a new unbound node agent to a domain, 129
- `create-password-alias` — creates a password alias, 131
- `create-profiler` — creates the profiler element, 136
- `create-resource-adapter-config` — creates the configuration information in `domain.xml` for the connector module, 138
- `create-ssl` — creates and configures the SSL element in the selected HTTP listener, IIOP listener, or IIOP service, 142
- `create-system-properties` — adds or updates one or more system properties of the domain, configuration, cluster, or server instance, 146
- `list-system-properties` — lists the system properties of the domain, configuration, cluster, or server instance, 409
- `create-virtual-server` — creates the named virtual server, 151
- `create-http-lb-config` — creates a configuration for the load balancer, 81
- creates a configuration for the load balancer — `create-http-lb-config`, 81
- creates a database instance — `hadbm create`, 273
- creates a domain with the given name — `create-domain`, 72
- creates a health-checker for a specified load balancer configuration — `create-http-health-checker`, 79
- creates a JDBC resource with the specified JNDI name — `create-jdbc-resource`, 102
- creates a management domain of the listed HADB hosts — `hadbm createdomain`, 279
- creates a new file user — `create-file-user`, 75
- creates a node agent — `create-node-agent`, 127
- creates a password alias — `create-password-alias`, 131
- creates an instance — `create-instance`, 91
- creates and configures the SSL element in the selected HTTP listener, IIOP listener, or IIOP service — `create-ssl`, 142
- creates or modifies a security map for the specified connector connection pool — `create-connector-security-map`, 67
- creates or modifies a security map for the specified connector connection pool — `update-connector-security-map`, 461
- creates tables in the HADB that are used by HA the cluster — `create-ha-store`, 77

creates the configuration information in `domain.xml` for the connector module —  
 create-resource-adapter-config, 138  
 creates the profiler element — create-profiler, 136

## D

definedomain — connects to the Management Agent and defines the domain, 281  
 delete-auth-realm — removes the named authentication realm, 161  
 delete-config — deletes an existing configuration, 165  
 delete-connector-connection-pool — removes the specified connector connection pool, 168  
 delete-connector-security-map — deletes a security map for the specified connector connection pool, 172  
 delete-domain — deletes the given domain, 176  
 delete-file-user — removes the named file user, 177  
 delete-http-health-checker — deletes a health-checker for a specified load balancer configuration, 179  
 delete-http-lb-ref — deletes the cluster or server instance from a load balancer configuration, 183  
 delete-http-listener — removes an HTTP listener, 185  
 delete-iiop-listener — removes an IIOP listener, 187  
 delete-instance — deletes the instance that is not running., 189  
 delete-javamail-resource — removes a JavaMail session resource, 191  
 delete-jms-resource — removes a JMS resource, 201  
 delete-jmsdest — removes a physical destination, 197  
 delete-jvm-options — removes JVM options from the Java configuration or profiler elements of the `domain.xml` file, 205  
 delete-lifecycle-module — removes the lifecycle module, 207  
 delete-message-security-provider — enables administrators to delete a `provider-config` sub-element for the given message layer (`message-security-config` element of `domain.xml`), 209  
 delete-node-agent — deletes the node agent and its associated directory structure, 211  
 delete-node-agent-config — removes a node agent from a domain, 212  
 delete-password-alias — deletes a password alias, 214  
 delete-profiler — deletes the profiler element, 218  
 delete-resource-adapter-config — deletes the configuration information created in `domain.xml` for the connector module, 220  
 delete-ssl — deletes the SSL element in the selected HTTP listener, IIOP listener, or IIOP service, 224  
 delete-system-property — removes one system property of the domain, configuration, cluster, or server instance, at a time, 226  
 delete-virtual-server — removes a virtual server, 230  
 delete-admin-object — removes the administered object with the specified JNDI name, 155  
 delete-http-lb-config — deletes a load balancer configuration, 181  
 deletes a health-checker for a specified load balancer configuration — delete-http-health-checker, 179  
 deletes a load balancer configuration — delete-http-lb-config, 181  
 deletes a password alias — delete-password-alias, 214  
 deletes a security map for the specified connector connection pool — delete-connector-security-map, 172  
 deletes an existing configuration — delete-config, 165  
 deletes tables in HADB — clear-ha-store, 38  
 deletes the cluster or server instance from a load balancer configuration — delete-http-lb-ref, 183  
 deletes the configuration information created in `domain.xml` for the connector module — delete-resource-adapter-config, 220  
 deletes the given domain — delete-domain, 176  
 deletes the instance that is not running. — delete-instance, 189  
 deletes the node agent and its associated directory structure — delete-node-agent, 211  
 deletes the profiler element — delete-profiler, 218  
 deletes the SSL element in the selected HTTP listener, IIOP listener, or IIOP service — delete-ssl, 224  
 removes a virtual server — delete-virtual-server, 230  
 deploy — deploys the specified component, 232  
 deploydir — deploys an exploded format of application archive, 238  
 deploys an exploded format of application archive — deploydir, 238  
 deploys the specified component — deploy, 232  
 removes a physical destination — delete-jmsdest, 197  
 disable — disables the component, 243

`disable-http-lb-application` — disables an application managed by a load balancer, 245  
`disable-http-lb-server` — disables a sever or cluster managed by a load balancer, 247  
disables a sever or cluster managed by a load balancer — `disable-http-lb-server`, 247  
disables an application managed by a load balancer — `disable-http-lb-application`, 245  
displays a list of all the subcommands to administer HADB — `hadbm help`, 292  
displays information about disk storage devices on each active data node — `hadbm deviceinfo`, 285  
displays the `hadbm` version information — `hadbm version`, 323  
displays the status of the deployed component — `show-component-status`, 437  
displays the version information — `version`, 471

## E

`enable` — enables the component, 249  
`enable-http-lb-application` — enables a previously-disabled application managed by a load balancer, 251  
`enable-http-lb-server` — enables a previously disabled sever or cluster managed by a load balancer, 253  
enables a previously-disabled application managed by a load balancer — `enable-http-lb-application`, 251  
enables a previously disabled sever or cluster managed by a load balancer — `enable-http-lb-server`, 253  
Enables administrators to create the `message-security-config` and `provider-config` sub-elements for the security service in `domain.xml`. — `create-message-security-provider`, 122  
enables administrators to delete a `provider-config` sub-element for the given message layer (`message-security-config` element of `domain.xml`) — `delete-message-security-provider`, 209  
`export` — marks a variable name for automatic export to the environment of subsequent commands in `multimode`, 255  
`export-http-lb-config` — exports the load balancer configuration to a file that can be used by the load balancer, 256

exports the load balancer configuration to a file that can be used by the load balancer — `export-http-lb-config`, 256  
extends the current HADB management domain by adding the specified hosts — `hadbm extenddomain`, 288

## G

generates stubs, ties, serializers, and WSDL files used in JAX-RPC clients and services — `wscmpile`, 473  
`get` — gets the values of the monitorable or configurable attributes, 260  
`get-client-stubs` — gets the stubs of the client, 262  
gets all audit modules and displays them — `list-audit-modules`, 343  
gets all custom resources — `list-custom-resources`, 362  
gets all JDBC resources — `list-jdbc-resources`, 381  
gets all the administered objects — `list-admin-objects`, 339  
lists the existing JavaMail session resources — `list-javamail-resources`, 377  
lists the JMS resources — `list-jms-resources`, 387  
lists the existing JMS physical destinations — `list-jmsdest`, 383  
gets connector connection pools that have been created — `list-connector-connection-pools`, 355  
lists the existing HTTP listeners — `list-http-listeners`, 371  
lists the existing IIOP listeners — `list-iiop-listeners`, 373  
gets the stubs of the client — `get-client-stubs`, 262  
gets the value of the specified configuration attribute — `hadbm-get`, 289  
gets the values of the monitorable or configurable attributes — `get`, 260  
lists the existing virtual servers — `list-virtual-servers`, 417  
gracefully stops the specified node — `hadbm stopnode`, 320

## H

`hadbm` — utility for managing the High Availability Database (HADB), 264

**hadbm addnodes** — adds new nodes to the named database, initializes devices for the new nodes, and refragments the schema, 266  
**hadbm clear** — reinitializes all the dataspace on all nodes and starts the database, 269  
**hadbm clearhistory** — clears the history files on the database, 271  
**hadbm create** — creates a database instance, 273  
**hadbm createdomain** — creates a management domain of the listed HADB hosts, 279  
**hadbm delete** — removes the database, 283  
**hadbm deletedomain** — removes the HADB management domain, 284  
**hadbm deviceinfo** — displays information about disk storage devices on each active data node, 285  
**hadbm disablehost** — selectively disables a host in the management domain, 287  
**hadbm extenddomain** — extends the current HADB management domain by adding the specified hosts, 288  
**hadbm-get** — gets the value of the specified configuration attribute, 289  
**hadbm help** — displays a list of all the subcommands to administer HADB, 292  
**hadbm list** — lists all the existing databases, 294  
**hadbm listdomain** — lists all hosts defined in the management domain, 295  
**hadbm listpackages** — lists the packages registered in the management domain, 296  
**hadbm reducedomain** — removes hosts from the HADB management domain, 299  
**hadbm refragment** — refragments the database schema, 301  
**hadbm registerpackage** — registers HADB packages in the management domain, 303  
**hadbm restart** — restarts the database, 307  
**hadbm set** — sets the value of the specified configuration attributes to the identified values, 311  
**hadbm start** — starts the database, 314  
**hadbm startnode** — starts the specified node, 315  
**hadbm status** — shows the state of the database, 317  
**hadbm stopnode** — gracefully stops the specified node, 320  
**hadbm version** — displays the hadbm version information, 323

## J

**jms-ping** — checks to see if the JMS service is up and running, 331  
**jspc** — precompiles JSP source files into servlets, 333

## L

**launches the Application Client Container and invokes the client application packaged in the application JAR file.**  
 — **appclient**, 17  
**list** — lists the configurable elements, 335  
**list-audit-modules** — gets all audit modules and displays them, 343  
**list-auth-realms** — lists the authentication realms, 345  
**list-backups** — lists all backups and restores, 347  
**list-components** — lists deployed components, 350  
**list-connector-connection-pools** — gets connector connection pools that have been created, 355  
**list-connector-security-maps** — lists the security maps belonging to the specified connector connection pool, 359  
**list-custom-resources** — gets all custom resources, 362  
**list-domains** — lists the domains in the specified domain directory, 364  
**list-file-groups** — lists the file groups, 365  
**list-http-listeners** — lists the existing HTTP listeners, 371  
**list-iiop-listeners** — lists the existing IIOP listeners, 373  
**list-instances** — lists all the instances along with their status, 375  
**list-javamail-resources** — lists the existing JavaMail session resources, 377  
**list-jdbc-connection-pools** — lists all JDBC connection pools, 379  
**list-jdbc-resources** — gets all JDBC resources, 381  
**list-jms-resources** — lists the JMS resources, 387  
**list-jmsdest** — lists the existing JMS physical destinations, 383  
**list-lifecycle-modules** — lists the lifecycle modules, 393  
**list-node-agents** — lists the node agents along with their status, 397  
**list-password-aliases** — lists all password aliases, 399  
**list-resource-adapter-configs** —, 403  
**list-sub-components** — lists EJBs or Servlets in deployed module or module of deployed application, 407

list-timers — lists all of the timers owned by server instance(s), 413

list-transaction-id — lists the transactions IDs, 415

list-virtual-servers — lists the existing virtual servers, 417

list-admin-objects — gets all the administered objects, 339

list—configs — lists all existing configurations, 352

list—http—lb—configs — lists load balancer configurations, 369

lists all backups and restores — list-backups, 347

lists all existing configurations — list—configs, 352

lists all hosts defined in the management domain — hadbm listdomain, 295

lists all JDBC connection pools — list-jdbc-connection-pools, 379

lists all of the timers owned by server instance(s) — list-timers, 413

lists all password aliases — list-password-aliases, 399

lists all the existing databases — hadbm list, 294

lists all the instances along with their status — list-instances, 375

lists deployed components — list-components, 350

lists EJBs or Servlets in deployed module or module of deployed application — list-sub-components, 407

lists load balancer configurations — list—http—lb—configs, 369

lists the authentication realms — list-auth-realms, 345

lists the configurable elements — list, 335

lists the domains in the specified domain directory — list-domains, 364

lists the file groups — list-file-groups, 365

lists the lifecycle modules — list-lifecycle-modules, 393

lists the node agents along with their status — list-node-agents, 397

lists the packages registered in the management domain — hadbm listpackages, 296

lists the security maps belonging to the specified connector connection pool — list-connector-security-maps, 359

lists the transactions IDs — list-transaction-id, 415

## M

ma — configures and starts the HADB Management Agent, 297

manually recovers pending transactions — recover transactions, 428

marks a variable name for automatic export to the environment of subsequent commands in multimode — export, 255

migrate-timers — moves a timer when a server instance stops, 419

moves a timer when a server instance stops — migrate-timers, 419

multimode — allows you to execute multiple commands while preserving environment settings and remaining in the asadmin utility, 421

## P

package-appclient — packs the application client container libraries and jar files, 422

packs the application client container libraries and jar files — package-appclient, 422

performs a backup on the domain — backup-domain, 33

ping-connection-pool — tests that a connection pool is usable, 424

ping-connection-pools — tests that a connection pool is usable, 426

precompiles JSP source files into servlets — jspc, 333

## R

reads a WAR file and the `jaxrpc-ri.xml` file and generates another WAR file that is ready for deployment — wsdeploy, 477

recover transactions — manually recovers pending transactions, 428

refragments the database schema — hadbm refragment, 301

registers a persistence resource — asadmin create-persistence-resource, create-persistence-resource, 133

registers HADB packages in the management domain — hadbm registerpackage, 303

creates a JavaMail session resource — create-javamail-resource, 95

creates a JMS resource — create-jms-resource, 109

registers the resource in the XML file specified —

add-resources, 14

reinitializes all the dataspace on all nodes and starts the database — hadbm clear, 269

remove-ha-cluster — returns an HA cluster to non-HA status, 430

removes a component from the domain application server — undeploy, 455

removes a node agent from a domain — delete-node-agent-config, 212

removes hosts from the HADB management domain — hadbm reducedomain, 299

removes JVM options from the Java configuration or profiler elements of the domain.xml file — delete-jvm-options, 205

removes one or more variables from the multimode environment — unset, 460

removes one system property of the domain, configuration, cluster, or server instance, at a time — delete-system-property, 226

removes the administered object with the specified JNDI name — delete-admin-object, 155

removes the database — hadbm delete, 283

removes the HADB management domain — hadbm deletedomain, 284

removes an HTTP listener — delete-http-listener, 185

removes an IIOP listener — delete-iiop-listener, 187

removes a JavaMail session resource —

delete-javamail-resource, 191

removes a JMS resource — delete-jms-resource, 201

removes the lifecycle module —

delete-lifecycle-module, 207

removes the named authentication realm —

delete-auth-realm, 161

removes the named file user — delete-file-user, 177

removes the specified connector connection pool — delete-connector-connection-pool, 168

restarts the database — hadbm restart, 307

restore-domain — restores files from backup, 432

restores files from backup — restore-domain, 432

returns an HA cluster to non-HA status —

remove-ha-cluster, 430

enables the component — enable, 249

## S

selectively disables a host in the management domain — hadbm disablehost, 287

set — sets the values of attributes, 435

sets the value of the specified configuration attributes to the identified values — hadbm set, 311

sets the values of attributes — set, 435

show-component-status — displays the status of the deployed component, 437

shows the state of the database — hadbm status, 317

shutdown — brings down the administration server and associated instances, 439

start-cluster — starts a cluster, 440

start-domain — starts a domain, 442

start-instance — starts a server instance, 444

start-node-agent — starts a node agent, 446

starts a cluster — start-cluster, 440

starts a domain — start-domain, 442

starts a node agent — start-node-agent, 446

starts a server instance — start-instance, 444

starts the database — hadbm start, 314

starts the specified node — hadbm startnode, 315

stop-cluster — stops a cluster, 448

stop-instance — stops a server instance, 452

stop-node-agent — stops a node agent, 454

stops a cluster — stop-cluster, 448

stops a node agent — stop-node-agent, 454

stops a server instance — stop-instance, 452

disables the component — disable, 243

stores the database metadata (schema) in a file for use in mapping and execution — capture-schema, 34

## T

create-cluster — creates a cluster, 58

create-jms-host — creates a JMS host, 107

create-application-ref — creates a reference to an application, 52

create-connector-resource — registers the connector resource with the specified JNDI name, 65

create-connector-security-map, 67

create-jdbc-connection-pool — registers the JDBC connection pool, 98

create-jndi-resource — registers a JNDI resource, 114

- create-jvm-options — creates the JVM options from the Java configuration or profiler elements, 117
  - create-resource-ref — creates a reference to a resource, 140
  - delete—cluster — deletes a cluster, 163
  - delete-application-ref — removes a reference to an application, 157
  - delete-connector-resource — removes the connector resource with the specified JNDI name, 170
  - delete-custom-resource—removes a custom resource, 174
  - delete-jdbc-connection-pool — removes the specified JDBC connection pool, 193
  - delete-jdbc-resource — removes a JDBC resource, 195
  - delete-jms-host — removes a JMS host, 199
  - delete-jndi-resource — removes a JNDI resource, 203
  - delete-resource-ref — removes a reference to a resource, 222
  - list—clusters — lists the existing clusters, 348
  - list-application-refs — lists the existing application references, 341
  - list-connector-resources — gets all connector resources, 357
  - list-file-users — creates a list of file users, 367
  - list-jms-hosts — lists the existing JMS hosts, 385
  - list-jndi-entries — browses and queries the JNDI tree, 389
  - list-jndi-resources — lists all existing JNDI resources, 391
  - list-resource-refs — lists the existing references to an application, 405
  - template — template for documenting manpages for the Sun Java System Application Server, 22, 29, 42, 70, 216, 401, 470
  - browses and queries the JNDI tree — list-jndi-entries, 389
  - creates a cluster— create-cluster, 58
  - creates a JMS host — create-jms-host, 107
  - creates a list of file users — list-file-users, 367
  - creates a reference to a resource— create-resource-ref, 140
  - creates a reference to an application—
    - create-application-ref, 52
  - creates the JVM options from the Java configuration or profiler elements — create-jvm-options, 117
  - deletes a cluster— delete-cluster, 163
  - gets all connector resources —
    - templatelists-connector-resources, 357
  - lists all existing JNDI resources— list-jndi-resources, 391
  - lists the existing application references—
    - list-application-refs, 341
    - lists the existing clusters— list-clusters, 348
    - lists the existing JMS hosts — list-jms-hosts, 385
    - lists the existing references to a resource—
      - list-application-refs, 405
    - registers a JNDI resource— create-jndi-resource, 114
    - registers the connector resource with the specified JNDI name — create-connector—resource, 65
    - registers the JDBC connection pool —
      - create-jdbc-connection-pool, 98
    - removes a custom resource —
      - delete-custom-resource, 174
    - removes a JCBC resource— delete-jdbc-resource, 195
    - removes a JMS host— delete-jms-host, 199
    - removes a JNDI resource— delete-jndi-resource, 203
    - removes a reference to a resource—
      - delete-resource-ref, 222
    - removes a reference to an application—
      - delete-application-ref, 157
    - removes the connector resource with the specified JNDI name — delete-connector—resource, 170
    - removes the specified JDBC connection pool
      - delete-jdbc-connection-pool, 193
  - template for documenting manpages for the Sun Java System Application Server — template, 22, 29, 42, 70, 216, 401, 470
  - tests that a connection pool is usable —
    - ping-connection-pool, 424
  - tests that a connection pool is usable —
    - ping-connection-pools, 426
- U**
- undeploy — removes a component from the domain application server, 455
  - unset — removes one or more variables from the multimode environment, 460
  - update-connector-security-map — creates or modifies a security map for the specified connector connection pool, 461
  - update-file-user — updates a current file user as specified, 464
  - update-password-alias — updates a password alias, 466
  - updates a current file user as specified —
    - update-file-user, 464
  - updates a password alias — update-password-alias, 466



- 
- utility for managing the High Availability Database (HADB) — `hadbm`, 264
  - utility for performing administrative tasks for the Sun Java System Application Server — `asadmin`, 19

**V**

- validates the J2EE Deployment Descriptors against application server DTDs — `verifier`, 468
- `verifier` — validates the J2EE Deployment Descriptors against application server DTDs, 468
- `version` — displays the version information, 471

**W**

- `wscompile` — generates stubs, ties, serializers, and WSDL files used in JAX-RPC clients and services, 473
- `wsdeploy` — reads a WAR file and the `jaxrpc-ri.xml` file and generates another WAR file that is ready for deployment, 477

