

Sun Java™ System Directory Server Release Notes for Microsoft Windows

Version 5.2 2005Q4

Part Number 819-4267-10

These Release Notes contain important information available at the time of release of Sun Java System Directory Server 5.2 2005Q4 for Windows. Known issues and limitations, and other information are addressed here. Read this document before you begin using Directory Server 5.2.

The most up-to-date version of these release notes can be found at the Sun Java System documentation web site: <http://docs.sun.com/app/docs/prod/entsys.05q4#hic>. Check the web site prior to installing and setting up your software. Then check the web site periodically thereafter to view the most up-to-date release notes and product documentation.

These release notes contain the following sections:

- [Release Notes Revision History](#)
- [About Directory Server 5.2 2005Q4](#)
- [Bugs Fixed in This Release](#)
- [Important Information](#)
- [Known Issues and Limitations](#)
- [Redistributable Files](#)
- [How to Report Problems and Provide Feedback](#)
- [Additional Sun Resources](#)

Third-party URLs are referenced in this document and provide additional, related information.

NOTE Sun is not responsible for the availability of third-party web sites mentioned in this document. Sun does not endorse and is not responsible or liable for any content, advertising, products, or other materials that are available on or through such sites or resources. Sun will not be responsible or liable for any actual or alleged damage or loss caused by or in connection with the use of or reliance on any such content, goods, or services that are available on or through such sites or resources.

Release Notes Revision History

Table 1 Revision History

Date	Description of Changes
February 2006	Revenue release.
November 2005	Beta release.

About Directory Server 5.2 2005Q4

Directory Server 5.2 2005Q4 is part of the Sun Java Enterprise System that delivers an integrated, core set of industry-leading enterprise network services that virtually all businesses need today.

This section includes:

- [What's New in Directory Server 5.2 2005Q4](#)
- [Hardware and Software Requirements](#)

What's New in Directory Server 5.2 2005Q4

Directory Server 5.2 2005Q4 is a maintenance release of Directory Server 5.2 2004Q2. No new features have been introduced in Directory Server 5.2 2005Q4:

For information about the bugs fixed in Directory Server 5.2 2005Q4, see [“Bugs Fixed in This Release” on page 4](#).

The following feature was available in Directory Server 4.x but is not available in Directory Server 5.2:

Database Backend Plug-in Interface. The enhanced pre-operation interfaces may be used instead of the database backend plug-in interface, to implement plug-ins that are designed to provide access to alternative directory data stores.

Hardware and Software Requirements

The following software is required for Directory Server 5.2 2005Q4.

Table 2 Windows Hardware and Software Requirements

Component	Platform Requirement
Operating System	Windows 2000 Advanced Server, Service Pack4 Windows Server 2003 Enterprise Edition Windows XP Professional, Service Pack 2
RAM	512 Mbytes
Disk Space	50 Mbytes

NOTE Directory Server 5.2 has been validated with Windows 2000, 2003, XP.

Bugs Fixed in This Release

Table 3 Fixed Bugs in Directory Server 5.2 2005Q4

Bug Number	Bug Synopsis
4817331	allow "Administrators" to reset the password
4972234	Account validation via LDAP bind without user password
5010313	DS 5.2. db2ldif -r removes the guardian file
5049830	Deletion operation is not flagged as dependent of a previous modification
5072212	MMR+SSL: Can't stop or use master after total update that failed
5100203	Add the rc code inside the could not be logged in the Changelog error
5103276	Hub not replicating due to Wrong ReplicaId 65535 in the Hub RUV
5106142	lack of out of disk space causes looping in db2bak internal TASK
6174806	Huge memory leak on mixed 5.1/5.2 topology (5.1 protocol)
6195685	DS 5.2patch2/aci returns incorrect results when fix for 4886766 is applied
6197763	fix 4974942 (in 5.2patch2) is wrong and can lead to a race condition when closing the connections
6199981	Memory leak in search "cn=config"
6200727	Memory leak in each replication session coming from a hub
6208161	Online indexation task request + search (evaluating role aci) -> DS deadlock hang
6209991	bad server side sorting performances when data contains a lot of identical values
6212643	ns-slaped Memory leak when dn_normalization failed
6213363	Index corruption
6216291	passwordRetryCount does not get incremented when passwordResetFailureCount is set to 0
6218066	performance degradation in sub string searches using P2
6221840	DS5.2: Memory leak in Individual Password Policies
6224967	performance problems when doing searches with the en-US collation rule
6229360	Random crash with DSML pdu larger than 2K
6233091	memory leak with virtual attributes
6236844	add/delete of an attribute in one ldapmodify is not replicated correctly
6237734	multivalued substring index of DN syntax gets corrupted if value deleted

Table 3 Fixed Bugs in Directory Server 5.2 2005Q4

Bug Number	Bug Synopsis
6239107	fildif is not able to work with files larger than 2GB (CU LDIF export file in this case is 28GB)
6242270	Retro Changelog plugin fails to record changes if "regular" replication is disabled
6242420	Deleting multivalued attribute(s) in directory server 5.2 patch2 results in high etimes
6242741	Directory server crashes while processing ldapmodify with Retro Changelog plugin turned on
6252050	DS exits when aclas__handle_group_entry() tries to allocate 4GB
6245092	Directory Server hangs when running stop-slapd command
6252452	db2ldif.pl -r may hangs the server
6255151	duplicate nsunique ids can be generated
6255780	COS doesn't get effective for sub-sub-org. cos attributes are empty for a user in sub-sub-org
6261456	DS 5.2 P2 forces a checkpoint at the specified checkpoint interval even when no mods performed
6262066	On UNIX, Directory Server may crash if #fd resource limit is dynamically increased
6267280	Error during the creation of subsuffix or clone under a search workload
6267965	Searches for subtype attributes does not work correctly with nsslapd-search-tune enabled
6275420	Deadlock in database while evaluating the acls in a modify operation
6276993	DS 5.2p3: crash in is_pending_value_mods because of uid uniqueness plugin
6281506	Replication may be slow to restart after a network outage
6282564	Restart of a Fractional Consumer breaks replication with WARNING<10271> - Partial Config Error
6283105	DS5.2 Patch3 Core Dumps within ids_sasl_check_bind due to NPE
6283717	A consumer does not detect there is pending operation and when closing an 'idle' replication cnx
6283860	DS5.2p3: modification lost when using ldapmodify
6285785	ds5ReplicaConsumerTimeout cannot be configured
6288249	Directory Server can hang if replication agreement is being initialized from another master
6290059	Performance issue when deleting non existent attribute
6343255	Remove time bomb in ns-slapd

Important Information

This section covers the following topics:

- [Installation Notes](#)
- [Documentation Notes](#)
- [Accessibility Features for People With Disabilities](#)

Installation Notes

For information about patch requirements and installation, see the following sections:

- [Patch Requirement Information](#)
- [General Installation Information](#)

Patch Requirement Information

The following table gives the numbers and minimum versions for the alignment patches. All patches referred to in this section are the minimum version number required for upgrade. It is possible that a new version of the patch has been issued since this document was published. A newer version is indicated by a different version number at the end of the patch. For example: 123456-04 is a newer version of 123456-02 but they are the same patch ID. Refer to the README file for each patch listed for special instructions.

To access the patches, go to <http://sunsolve.sun.com>.

Table 4 Directory Server 5.2 2005Q4 Alignment Patches Required For Windows

Patch Number	Patch Description
121529-01	Windows (MSI): Sun Java™ System Administration Server 5 2005Q4
121392-02	Windows (MSI): Sun Java™ System Directory Server 5 2005Q4

For detailed information about Upgrade procedure of the Directory Server from JES3 to JES4 refer *Sun Java Enterprise System 2005Q4 Upgrade Guide for Microsoft Windows* located at <http://docs.sun.com/app/docs/doc/819-4461>.

General Installation Information

- For information about the default installation location, see “Documentation Notes” on page 7.
- Installation paths that contain space characters are not supported. Do not use space characters in your installation path.

Documentation Notes

Man Pages

Directory Server commands and Administration Server commands are now documented as man pages and delivered in the following formats:

- As HTML and PDF in the following new documents: *Sun Java System Directory Server 5.2 2005Q1 Man Page Reference* and *Sun Java System Administration Server 5.2 2005Q1 Man Page Reference*.
- As packages in the software distribution

For information about how to access the man pages, see the *Java Enterprise System Installation Guide*.

Product Version Number

In some parts of the Directory Server documentation and console, the version number of the product is referred to as 5.2. Directory Server 5 2005Q4 is a maintenance release of Directory Server 5.2.

Localized Documentation

Localized documentation is posted to <http://docs.sun.com/> as it becomes available.

Accessibility Features for People With Disabilities

To obtain accessibility features that have been released since the publishing of this media, consult Section 508 product assessments available from Sun upon request to determine which versions are best suited for deploying accessible solutions. Updated versions of applications can be found at: <http://sun.com/software/javaenterprisesystem/get.html>.

For information on Sun's commitment to accessibility, visit <http://sun.com/access>.

Known Issues and Limitations

This section contains a list of the known issues and limitations with Directory Server 5.2 2005Q4. The issues are grouped into the following categories:

- [Installation, Uninstallation, and Migration](#)
- [Security](#)
- [Replication](#)
- [Conformance](#)
- [Directory Server Console](#)
- [Core Server](#)
- [Directory Server Plug-ins](#)
- [Miscellaneous](#)

Installation, Uninstallation, and Migration

Cannot Install Directory Server When the Root Suffix Contains Spaces (4526501)

A root suffix cannot contain space characters.

Workaround

If your root suffix contains space characters, correct the suffix generated at installation time to remove the spaces:

1. In the Sun Java System Server console, select the top directory entry in the left-hand navigation pane of the Servers and Applications tab.
2. Click Edit and modify the suffix in the User directory subtree field.
3. Click OK to save the change.

Error Message When Running migrateInstance5 Script (4529552)

When the migrateInstance5 script is run with the error logging feature disabled, a message indicates that the migration procedure is attempting to restart the server while the server is already running.

Workaround

- If error logging is disabled, ignore this error message.
- If error logging is enabled, consult the error log for more information.

Duplicate Value Error Logged in the Configuration Directory Server During Installation (4841576)

During configuration of Directory Server, an ACI on the server group entry for each new server installation is added. If the entry already exists and the ACI value already exists on the entry (which is the case when Administration Server is installed after Directory Server), then the following error is logged in the Configuration Directory Server:

```
[07/May/2004:16:52:29 +0200] - ERROR<5398> - Entry - conn=-1 op=-1msgId=-1 - Duplicate value addition in attribute "aci" of entry "cn=Server Groups, cn=sorgho.france.sun.com, ou=france.sun.com, o=NetscapeRoot"
```

Workaround

Ignore the error message.

Configuration of Directory Server Fails When Using a Remote Configuration Directory (4931503)

When configuring Directory Server by using a remote configuration directory, configuration fails if the administration domain of the remote directory does not match the administration domain in the setup procedure.

Workaround

When configuring Directory Server by using a remote configuration directory, use the same administration domain as defined in the remote configuration directory.

Installation Fails When the Base DN Contains a White Space (5040621)

During installation, if the base DN contains a white space (for example, o=example east) the directoryURL entry is incorrectly parsed for the UserDirectory global preferences. Consequently, all operations to the userDirectory fail to find the entries in user/groups in the console.

Workaround

Modify the base DN value in one of the following ways:

- Using the console, correct the nsDirectoryURL attribute to reflect the correct base DN
- Using the command line, perform the ldapmodify command on the nsDirectoryURL attribute and the ldapdelete command on the nsDirectoryFailoverList attribute.

nsSchemaCSN Has Multiple Values After upgrade of AS and DS (5041885)

After upgrade of Administration Server or Directory Server, the nsSchemaCSN attribute has several values. This issue occurs because the 60iplanet-calendar.ldif file and the 99user.ldif file both contain the nsSchemaCSN attribute. The nsSchemaCSN attribute should be in the 99user.ldif file only.

Workaround

1. Remove the nsSchemaCSN attribute from 99user.ldif file and the 60iplanet-calendar.ldif file.

2. Rename the script from

```
<server_root>\slapd-<instance>\schema_push.pl
```

to

```
<server_root>\slapd-<instance>\schema_push.pl.ref
```

3. Copy the template file from

```
<server_root>\bin\slapd\admin\scripts\template-schema_push.pl
```

to

```
<server_root>\slapd-<instance>\schema_push.pl
```

4. Edit the new schema_push.pl file as follows:

- a. Replace {{PERL-EXEC}} by !<server_root>\bin\slapd\admin\bin\perl

- b. Replace {{MY-DS-ROOT}} by <server_root>\slapd-<instance>

- c. Replace {{SEP}} by "\"

5. Add the execute mode to the schema_push.pl file.

6. Force the schema replication by running the script, as follows:

```
<server_root>\schema_push.pl
```

7. Confirm that the nsSchemaCSN attribute has been added to 99user.ldif file.

To backout, restore the original schema_push.pl file under <slapd-instance>.

Backout Fails When the Previous Version Is Not Configured (6196574)

Backout fails in the following scenario:

- Install but do not configure a previous version of Directory Server and Administration Server

- Install and configure the latest version of Directory Server and Administration Server
- Backout from the latest version of Directory Server and Administration Server to the previous version of Directory Server and Administration Server

The backout fails because the `<ServerRoot>\admin-serv\upgrade\versions.conf` file does not contain the correct information.

Workaround

Configure the previous version of Directory Server and Administration Server before installing the latest version of Directory Server and Administration Server.

Upgrade of a Standalone Instance of Directory Server Requires the `sync-cds` Command to be Run (6208268)

When a standalone instance of Directory Server 5.2 is upgraded, the upgrade procedure requires the data in the Configuration Directory Server to be synchronized. Before running the `sync-cds` command, Directory Server searches for the presence of the `adm.conf` file. When the Administration Server is not configured, the file is not present and the `sync-cds` command cannot run.

Workaround

Create a dummy `adm.conf` file so that the `sync-cds` command can run:

1. Create a file called `<ServerRoot>\admin-serv\config\adm.conf`
2. Edit the file to contain the following line only:

```
isie: cn=Administration Server, cn=Server Group, cn=<hostname>,
      ou=<administration_domain>, o=NetscapeRoot
```

Where `<hostname>` is a fully qualified domain name for the host that the Directory Server is running on, and `<administration_domain>` is typically the host domain name.

For example:

```
isie: cn=Administration Server, cn=Server Group,
      cn=starfish.Ireland.Sun.com,
      ou=Ireland.Sun.com, o=NetscapeRoot
```

Entries With Password Expiration Cannot be Replicated to Older Versions of Directory Server (6209543)

The `pwdChangedTime` attribute and `usePwdChangedTime` attribute are defined in Directory Server 5.2 2004Q2 and later versions. These attributes are not defined in Directory Server 5.2 2003Q4 or earlier versions.

When an entry is defined with password expiration in Directory Server 5.2 2004Q2 or later versions, the entry contains the `pwdChangedTime` attribute and `usePwdChangedTime` attribute. When that entry is replicated to a supplier running Directory Server 5.2 2003Q4 or an earlier version, the supplier cannot process any modifications to that entry. A schema violation error occurs because the supplier does not have the `pwdChangedTime` attribute in its schema.

Workaround

Define the `pwdChangedTime` attribute and `usePwdChangedTime` attribute in the `00core.ldif` file for all servers in the replication topology that are running Directory Server 5.2 2003Q4 or an earlier version.

To define the attributes, add the following lines to the `00core.ldif` file for each server:

```
attributeTypes: ( 1.3.6.1.4.1.42.2.27.8.1.16 NAME 'pwdChangedTime' DESC 'Directory
Server defined password policy attribute type' SYNTAX 1.3.6.1.4.1.1466.115.121.1.24
SINGLE-VALUE USAGE directoryOperation X-DS-USE 'internal' X-ORIGIN 'Sun Directory
Server' )
```

```
attributeTypes: ( 1.3.6.1.4.1.42.2.27.9.1.597 NAME 'usePwdChangedTime' DESC 'Directory
Server defined attribute type' SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 SINGLE-VALUE
X-DS-USE 'internal' X-ORIGIN 'Sun Directory Server' )
```

During installation of Directory Server With Access Manager the Index Is Corrupted (6305723)

During installation of Directory Server, the Access Manager adds indexes for the 'ou' attribute if they don't exist. When the tool `comms_dssetup.pl` is run, the index is corrupted.

Workaround

Reindex the Directory Server.

Security

Bind With Zero-Length Password Is Treated as an Anonymous Bind (4703503)

If you use a zero-length password to bind to a directory, your bind is an anonymous bind - it is not a simple bind. Third party applications that authenticate users by performing a test bind might exhibit a security hole if they are not aware of this behavior.

Workaround

Ensure that your client applications are aware of this feature.

DNS keyword in ACIs (4725671)

If the DNS keyword is used in an ACI, any DNS administrator can access the directory by modifying a PTR record, and can thereby provide the privileges granted by the ACI.

Workaround

Use the IP keyword in the ACI, to include all IP addresses in the domain.

LDAP Modify Operations Through SSL Fail When Referred to Master Replica From Consumer Replica (4922620)

ldapmodify update operations over SSL fail when they are referred to a master replica from a consumer replica.

Error Message At Startup When passwordisglobalpolicy Is Enabled (4964523)

When the passwordisglobalpolicy attribute is enabled on both masters in a 2-master, multi-master replication topology it works correctly but can generate the following incorrect error message:

```
[03/Dec/2003:11:32:54 -0500]ERROR<5897> - Schema - conn=-1 op=-1 msgId =-1 - User
error: Entry "cn=Password Policy,cn=config", attribute "passwordisglobalpolicy" is not
allowed [03/Dec/2003:11:32:54 -0500] - Sun-ONE-Directory/5.2 B2003.143.0020 (64-bit)
starting up
```

Workaround

Ignore the incorrect error message.

Invalid Values Are Accepted for passwordMinLength in Individual Password Policies (4969034)

The passwordMinLength attribute in individual password policies is 2 - 512 characters. However, values outside of this range are accepted when an individual password policy is configured.

Workaround

Configure individual password policies with passwordMinLength attribute of 2 - 512 characters.

Replication

Addition of Entries With objectClass=nsTomstone Can Cause Replication to Fail (2122375/5021269)

Adding an entry with objectClass=nstombstone can cause replication to fail.

Workaround

Do not add entries with objectClass=nstombstone.

Local Schema Modifications Can Be Overwritten When a Consumer Database Is Created (4537230)

The replication monitoring tools rely on read access to cn=config to obtain the replication status. This should be taken into account when replication is configured over SSL.

In Directory Server 5.2, the schema file `11rfc2307.ldif` has been altered to conform to `rfc2307`. If replication is enabled between 5.2 servers and 5.1 servers, the `rfc2307` schema MUST be corrected on the 5.1 servers, or replication will not work correctly.

Workaround

To ensure correct replication between Directory Server 5.2 and Directory Server 5.1, perform the following tasks:

- For zip installations, remove the `10rfc2307.ldif` file from the 5.1 schema directory and copy the 5.2 `11rfc2307.ldif` file to the 5.1 schema directory. (5.1 Directory Server Solaris packages already include this change.)
- Copy the following files from the 5.2 schema directory into the 5.1 schema directory, overwriting the 5.1 copies of these files:
`11rfc2307.ldif`, `50ns-msg.ldif`, `30ns-common.ldif`, `50ns-directory.ldif`,
`50ns-mail.ldif`, `50ns-mlm.ldif`, `50ns-admin.ldif`, `50ns-certificate.ldif`,
`50ns-netshare.ldif`, `50ns-legacy.ldif`, and `20subscriber.ldif`.
- Restart the Directory Server 5.1 server.
- In the Directory Server 5.2 server, set the `nsslapd-schema-repl-useronly` attribute under `cn=config` to `on`.
- Configure replication on both servers.
- Initialize the replicas.

Initially, certain schema attributes may be replicated between the servers as they synchronize other schema elements but this is benign and will not cause any problems. See the Installation Notes for details on how the schema has changed.

Updates to the Retro Change Log on a Master Server Can be Lost (2121137/6178461)

When a master server crashes, changes made to the retro change log on that server can be lost.

Workaround

Do not to use the retro change log on a master server. Instead, use the retro change log on the consumer server. If you are implementing failover of the retro change log, ensure that you have at least two consumer servers with enabled retro change logs.

Replication Monitoring Tools Do Not Support LDAP URLs That Contain Literal IPv6 Addresses (4702476)

The replication monitoring tools `entrycmp`, `insync`, and `repldisc` do not support LDAP URLs that contain literal IPv6 addresses.

Workaround

None

Multi-Master Replication Over SSL With Certificate-Based Client Authentication Does Not Work If Preceded by SSL With Simple Authentication (4727672)

In a multi-master replication scenario, if replication is enabled over SSL by using simple authentication, it is not possible to enable replication between the same servers over SSL by using certificate-based client authentication.

Workaround

To enable replication over SSL using certificate-based client authentication, restart at least one of the servers.

After Aborting a Total Update Cannot Restart a Total Update or Re-enable Replication on the Suffix (4741320)

If a total update is aborted while in progress, it is not possible to launch another total update, or to re-enable replication on the suffix.

Workaround

Do not abort a total update while it is in progress.

Reports of Replication Delays With the `insync` Command and Fractional Replication (4856286)

The `insync` command-line tool has no concept of fractional replication. If fractional replication is configured, false reports of replication delays can be produced.

Workaround

None

Schema Modifications Are Not Replicated in Incremental Updates (4868960)

If you modify the schema without making any other non schema-related modifications, your schema modifications will not be replicated immediately.

Workaround

Wait for five minutes for your schema modifications to be replicated, or force replication by using the `Send Updates Now` option in the Directory Server Console.

Errors in Multi-Master Replication When `nsslapd-lastmod` Attribute Set to OFF (5010186)

The `nsslapd-lastmod` attribute specifies whether Directory Server maintains the modification attributes for Directory Server entries. When this attribute is set to OFF errors occur in multi-master replication.

Workaround

When using multi-master replication, leave the `nsslapd-lastmod` attribute set to ON.

During Replication an Error Message Is Written Frequently to the Error Log (5029597)

During replication the following error message can be written frequently to the error log:

```
[09/Apr/2004:06:47:45 +0200] - INFORMATION - conn=-1 op=-1 msgId=-1 -  
csngen_adjust_time: remote offset now 33266 sec
```

This error message increases the size of the error log file.

Workaround

Ignore this error message.

passwordExpirationTime Attribute Is Unsynchronized After First Password Expiration Warning (5102180)

The `passwordExpirationTime` attribute is reset on the master when the first password expiration warning is given to the consumer. This attribute is not reset on the consumer and is therefore out of sync after the first password expiration warning.

Workaround

None.

Directory Server Can Crash If Backoff Timer Expires When Replication Agreement Detects an External Event (6272611)

If the backoff timer set by the replication agreement expires at the same time the replication agreement receives an external event, a race condition occurs that might cause the Directory Server to crash.

The issue can occur in the following scenarios:

- When a Directory Server 5.2 supplier or hub is replicating to Directory Server 5.1 consumer
 - The Directory Server is stopped
 - The replication agreements are disabled
 - The replication agreements are modified to change the scheduled replication time
- When a Directory Server 5.2 supplier or hub is replicating to Directory Server 5.2 consumer
 - The Directory Server is stopped
 - The replication agreements are disabled
 - The replication agreements are modified to change the scheduled replication time

- The replication breaks (the consumer fails to apply modifications, the consumer is not initialized, the last update to the consumer is too old...)

Workaround

None

Conformance

DN Normalization Code Does Not Treat Case Sensitive Attributes Properly (4933500)

DN normalization code puts attribute names in lower case. The DN normalization code does not take into account the attribute syntax and the associated matching rule.

Workaround

None

Directory Server Console

Internal Search Causes Directory Server Console to Display a Yellow Warning Flag (2113362)

In some search contexts a yellow warning flag is displayed. The yellow flag indicates that the Directory Server internal search mechanism has encountered an All IDs Threshold / Sorting issue. This flag does not represent a problem.

Workaround

Either ignore the flag or create a browsing index (VLV index) to prevent the flag from occurring.

Console Does Not Support Passwords That Contain a Colon ":" (4535932)

The console does not support passwords that contain a colon ":".

Workaround

Do not use a colon in a password.

Console Does Not Support the Management of External Security Devices (4795512)

The console does not support the management of external security devices, such as Sun Crypto Accelerator 1000 Board.

Workaround

Manage external security devices by using the command line.

slapd Daemon Takes the Administration Server Port When Restarted From the Console (5002054)

When the slapd daemon is restarted from the console, it can take the Administration Server port and prevent Administration Server from being restarted by the console.

Workaround

Restart the slapd daemon from the command line.

German Entries Are Sorted Incorrectly in Directory Server Console (4889951)

In the Directory Server console some german characters are sorted incorrectly. See the following examples:

- “a with diaeresis” is sorted after “a”
- “o” is sorted after “u”

Workaround

None.

Path to Help File for Directory Server Login Dialog Box Is Incorrect for Non-English Languages (5046970)

The path to the help .htm file for the Directory Server Login dialog box in non-English languages is incorrect. For example, for the Korean language, the incorrect path is as follows:

```
<Server-Root>\manual\ko\console\help\help\login.htm.
```

Workaround

Change the path to the help .htm file as shown in the following example. This example uses the Korean locale:

1. Close Directory Server Console.
2. Change directory to the <Server-Root>\java directory.
3. Extract the mcc52_ko.jar file using for the `jar xvf mcc52_ko.jar` command.
4. Remove the mcc52_ko.jar file.
5. Open the following file in a text editor:

```
com\netscape\management\client\console\console_ko.properties
```

6. Change the path from

```
login-help>manual\ko\console\help\help\login.htm
```

to

```
login-help>manual\ko\console\help\login.htm
```

7. Recreate the `mcc52_ko.jar META-INF* com* jar` file by using the `jar cvf mcc52_ko.jar META-INF* com*` command.
8. Restart Directory Server Console.

LDIF Files Exported by Using the Tasks Tab on the Console Contain Additional Unnecessary Information for Backup (6197903)

This issue concerns LDIF files exported by using the Export to LDIF button in Tasks tab on the console. When a server is configured as a supplier or a hub, an exported LDIF file starts to collect replication information to initialize consumers. The exported LDIF file cannot be used with the Import from LDIF button in Tasks tab on the console.

Workaround

Select one of the following workarounds:

Workaround 1: Export the LDIF file for a suffix by using the `Object/Export` command from the console menu. In the `Export suffix` dialog box, do not tick the Export replication information box. The resulting LDIF file can be used by the Import from LDIF button in the Tasks tab and by the `Object/Initialize` command in the console menu.

Workaround 2: Export the LDIF file without supplementary information by using the `db2ldif` command.

Workaround 3: Import the LDIF file for a suffix by using the `Object/Initialize` command from the console menu. This command handles LDIF files correctly, with and without replication information. Note, to initialize the contents of a suffix, you require an LDIF file with replication information.

Server Console Help Index Search Does Not Work in Traditional Chinese (zh_TW) (6205531)

Core Server

Server Crashes When Stopped During Export, Backup, Restore, or Index Creation (2121645/4678334)

Stopping the server during export, backup, restore, or index creation can cause it to crash.

Backend Instances Called “Default” Do Not Work (2122630)

Backend instances, or databases, called “Default” do not work.

Workaround

Do not name a database “Default”.

Database Becomes Unavailable if LDIF File Is Inaccessible During Import (2126979)

If a non-existent file is specified for an online import, the server still deletes the existing database.

tcp_keepalive_interval and tcp_ip_abort_interval Configuration Attributes Cannot be Used for Timeout (5087249)

The `tcp_keepalive_interval` and `tcp_ip_abort_interval` configuration attributes cannot be used to close idle connections on Directory Server.

Workaround

Use the `nsslapd-idletimeout` configuration attribute to close idle connections.

Directory Server Plug-ins

When the Pass-Through Authentication plug-in (PTA plug-in) detects that a suffix configured for pass-through authentication is local to the machine, the plug-in is not automatically disabled (4938821)

If the plug-in configuration entry attribute values in the `dse.ldif` end with extra blank spaces, Directory Server will either fail to start or behave in unexpected ways (4986088)

Post Operation Plug-In Function Not Called When Search Operation on Non-Existent Base DNs (5032637)

The post operation plug-in function for a search operation is not called if the search is performed on a non-existent base DN. This is inconsistent with the description of post-operation plug-ins in “Extending Client Request Handling” in the Directory Server Plug-in Developer’s Guide.

Workaround

None

Error Message When ACL Plug-In Unable to Normalize Attribute Value (5089207)

The ACL plug-in normalizes attribute values in order to compare them with DN provided in the ACL rules. If an attribute value is not a DN, an error message is logged.

Workaround

Ignore the error message.

If you have two Directory Server instances, DS1 and DS2, with your Configuration Directory Server installed on DS1, and you subsequently replicate the `o=NetScapeRoot` configuration information to DS2, as opposed to automatically disabling the PTA plug-in will continue to point to DS1 for any `o=NetScapeRoot` relevant searches despite the fact that the information is now local.

Miscellaneous

Maximum Size of Transaction Log File Cannot be Changed (4523783)

If you change the maximum size of the transaction log file when the database directory contains log files, the new size is not taken into account.

Workaround

None.

Cannot Create a Chained Suffix With an IPv6 Address by Using the Console (5019414)

When you create a new chained suffix with an IPv6 address by using the New Chained Suffix window of the console the Testing connection parameters popup window does not close automatically and the validity of the IPv6 address is not tested. Although the local configuration of the chained suffix is successful, the validity of the IPv6 address is not assured.

Workaround

Do not to use the Test connection option when you configure a chaining suffix with an IPv6 address.

International substring search on unaccented characters returns only unaccented characters (4955638)

Instead of returning the unaccented character *and* all of its possible accented variants, which would seem to be the logical approach, a search on an unaccented character only returns the unaccented character in question. Searching for an accented character however, returns not only that character but all other variants.

Certain error messages reference a database error guide which does not exist (4979319)

When the ldapsearch size limit option is hit on a chained suffix an error message is issued and the access number of entries count is incorrect (5029026)

Command Line Tools

The db2ldif -s Command Causes Errors on Suffixes With a Subtree (2122385)

When the db2ldif -s command is run on a suffix with one or more subtrees, errors occur. Also, all entries under the suffix are exported, including entries under subtree. This can cause problems if the ldif2db command is used on the exported LDIF file to re-initialize the suffix.

Workaround

Do not use the `db2ldif -s` command on a suffix with one or more subtrees. Instead, use the `db2ldif -n` command as shown here:

```
<Server-Root>\slapd-<hostname>\db2ldif.bat -n <suffixname>
```

Incorrect Error Message When Exporting a Subtree by Using the `db2ldif -s` Option (2122386)

When the `db2ldif -s` command is run on a suffix to export a subtree, the following incorrect error message can be generated:

```
Failed to fetch subtree lists (error -30991) DB_NOTFOUND: No matching key/data pair found
```

Workaround

Ignore this error message.

Absolute Paths Must be Specified for the Following Commands: `db2bak`, `db2bak.pl`, `bak2db`, and `bak2db.pl` (4897068)

`db2ldif` Command Creates an Output File In an Incorrect Directory (5029598)

The `db2ldif` command creates output LDIF files in an incorrect default directory when the file name only is specified. The `db2ldif` command should create output LDIF files in this directory:

```
<Server-Root>\slapd-<hostname>\ldif
```

Workaround

Specify the absolute path to the file name of the output LDIF file.

`mmldif` Command Crashes (6205803)

The `mmldif` command crashes when used.

Workaround

None

`createtimestamp` and `modifytimestamp` not Generated During `ldif` Import (6235452)

When an `ldif` file is imported to directory server by using the `ldif2db.pl` script, the `createtimestamp` and `modifytimestamp` are not generated. Note that this feature does not occur for online adds done by LDAP clients like `ldapmodify`.

Workaround 1

Edit the LDIF source file before import. This workaround works for LDIF input files that do not contain any entry with `createtimestamp` or `modifytimestamp` values. This workaround is good for Substitute ALL empty lines in the LDIF source file with the following 3 lines:

```

createtimestamp: 20050301132421Z
modifytimestamp: 20050301132421Z
empty_line

```

Then import the file into the Directory Server.

Workaround 2

Import the source file by using `ldapmodify` instead of `ldif2db`. This workaround is slower than Workaround 1 but it works for LDIF input files with entries with `createtimestamp` or `modifytimestamp` values.

1. Export the contents of your Directory Server by using `db2ldif`:


```
db2ldif -n $instance -a <tmp>\exported.ldif
```
2. Copy the first entry of `<tmp>\exported.ldif` into a new file named `<tmp>\rootsuffix.ldif`
3. Re-import back the database only with the root suffix:


```
ldif2db -n $instance -i <tmp>\rootsuffix.ldif
```
4. Add all of the entries in `<tmp>\rootsuffix.ldif` by using the `ldapmodify` command:


```
ldapmodify -a -c -h <host> -p <port> -D "cn=Directory Manager" -w &lt;password> -f <tmp>\exported.ldif
```

ldapdelete Command Hangs When NDS Plug-in Returns a Non-zero Value (6301267)

When the pre-operation plug-in for schema deletion returns a non-zero value, the `ldapdelete` command hangs.

Workaround

Ensure that the pre-operation plug-ins (except `abandon` and `unbind`) send back a result (by using `slapi_send_ldap_result`) before returning a non zero status.

Redistributable Files

Sun Java System Directory Server 5.2 2005Q4 does not contain any files which you can redistribute.

How to Report Problems and Provide Feedback

If you have problems with Sun Java System Directory Server, contact Sun customer support using one of the following mechanisms:

- Sun Software Support services online at <http://www.sun.com/service/sunone/software>

This site has links to the Online Support Center, and ProductTracker, as well as to maintenance programs and support contact numbers.

- The SunSolve support web site at <http://sunsolve.sun.com>

This site includes patches, support documents, security information, and the Sun System Handbook.

- The telephone dispatch number associated with your maintenance contract

So that we can best assist you in resolving problems, please have the following information available when you contact support:

- Description of the problem, including the situation where the problem occurs and its impact on your operation
- Machine type, operating system version, and product version, including any patches and other software that might be affecting the problem
- Detailed steps on the methods you have used to reproduce the problem
- Any error logs or core dumps

You might also find it useful to subscribe to the following interest groups, where Sun Java System Directory Server topics are discussed:

<http://swforum.sun.com>

Sun Welcomes Your Comments

Sun is interested in improving its documentation and welcomes your comments and suggestions. Use the web-based form to provide feedback to Sun:

<http://www.sun.com/contact/feedback/?refurl=http://www.sun.com>

Please provide the full document title and part number in the appropriate fields. The part number can be found on the title page of the book or at the top of the document, and is usually a seven or nine digit number. For example, the part number of these Directory Server 5.2 Release Notes is 819-4267-10.

Additional Sun Resources

Useful Sun Java System information can be found at the following Internet locations:

- Sun Java System Documentation
<http://docs.sun.com/app/docs/prod/entsys.05q4#hic>
- Sun Java Enterprise System Software Services
<http://www.sun.com/service/products/software/javaenterprisesystem>
- Sun Java System Software Products and Service
<http://www.sun.com/software>
- Sun Java System Support and Knowledge Base
<http://sunsolve.sun.com>
- Sun Java System Consulting and Professional Services
<http://www.sun.com/service/products/software/javaenterprisesystem>
- Sun Developer Information
<http://developers.sun.com>
- Sun Developer Support Services
<http://www.sun.com/developers/support>
- Sun Software Data Sheets
<http://www.sun.com/software>
- Directory Server Certified Engineer Training Program
http://training.sun.com/US/certification/middleware/dir_server.html

Copyright © 2006 Sun Microsystems, Inc. All rights reserved.

Sun Microsystems, Inc. has intellectual property rights relating to technology embodied in the product that is described in this document. In particular, and without limitation, these intellectual property rights may include one or more of the U.S. patents listed at <http://www.sun.com/patents> and one or more additional patents or pending patent applications in the U.S. and in other countries.

SUN PROPRIETARY/CONFIDENTIAL.

U.S. Government Rights - Commercial software. Government users are subject to the Sun Microsystems, Inc. standard license agreement and applicable provisions of the FAR and its supplements.

Use is subject to license terms.

This distribution may include materials developed by third parties.

Portions may be derived from Berkeley BSD systems, licensed from U. of CA.

Sun, Sun Microsystems, the Sun logo, Java and Solaris are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries.

Copyright © 2006 Sun Microsystems, Inc. Tous droits réservés.

Sun Microsystems, Inc. détient les droits de propriété intellectuels relatifs à la technologie incorporée dans le produit qui est décrit dans ce document. En particulier, et ce sans limitation, ces droits de propriété intellectuelle peuvent inclure un ou plus des brevets américains listés à l'adresse <http://www.sun.com/patents> et un ou les brevets supplémentaires ou les applications de brevet en attente aux Etats - Unis et dans les autres pays.

Propriété de SUN/CONFIDENTIEL.

L'utilisation est soumise aux termes du contrat de licence.

Cette distribution peut comprendre des composants développés par des tierces parties.

Des parties de ce produit pourront être dérivées des systèmes Berkeley BSD licenciés par l'Université de Californie.

Sun, Sun Microsystems, le logo Sun, Java et Solaris sont des marques de fabrique ou des marques déposées de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays.

Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays.