

SUN RAY 270 VIRTUAL DISPLAY CLIENT

KEY FEATURES AND BENEFITS

A DESKTOP SOLUTION FOR
THE NETWORK ERA

FEATURES

- Lower costs with no local operating system to manage and administer.
- Access applications on virtually any platform.
- Enhance security with user authentication and encryption between server and client.
- Enjoy automatic load balancing that reduces complexity and administration.
- Adapts easily for legacy peripherals.

BENEFITS

- Affordably manage thousands of desktops with just a few systems administrators.
- Centralized data and applications mean easier back up, greater security, and intellectually property protection.
- Rapidly upgrade applications on thousands of desktops.

Oracle's Sun Ray virtual display clients provide customers with an interoperable desktop computing solution that reduces the maintenance, upgrade, and operational costs associated with most desktop environments. The Sun Ray 270 virtual display client is an all-in-one unit that includes a brilliant, 17-inch flat panel monitor. Its compact design and flexible Video Electronics Standards Association (VESA) mounting options make the Sun Ray 270 particularly well suited for space-constrained environments such as call centers, healthcare, finance, service providers, and education.

Access Applications on Virtually Any Platform

Zero-administration Sun Ray virtual display clients enable access to applications on virtually any platform—the Oracle's Solaris Operating System, Java technology, Linux, UNIX, Microsoft Windows, AS/400, and mainframes. Sun Ray clients differ from complex PCs and thin clients with embedded operating systems, because Sun Ray clients have no local operating system (such as Windows XP Embedded or Windows CE) to manage and administer.

Sun Ray architecture consists of two types of components: the Sun Ray virtual display clients and Sun Ray Software.

Sun Ray Virtual Display Clients

The Sun Ray 270 virtual display client requires no desktop administration. Unlike complex Windows or Embedded Linux-based thin clients and PCs, Sun Ray clients do not need to be upgraded when new applications are introduced or more computing power is required. Users can access their sessions from any Sun Ray client on the local area network (LAN) or wide area network (WAN). The user simply inserts a smart card into any available Sun Ray client to instantaneously access an existing session.

Sun Ray Software

Sun Ray Software provides user authentication and encryption between server and client, as well as user session management. It not only enhances security, but also helps reduce the complexity and administration of IT environments. Sun Ray Software provides automatic load balancing, optimizing performance by distributing sessions across servers in the group. Load balancing takes into account each server's load and capacity (number and speed of its CPUs), so that larger or less heavily loaded servers bear more of the load. In addition, Sun Ray Software enables Sun Ray clients to be connected to a LAN or WAN.

Sun Ray 270

Sun Ray 270 virtual display clients are plug-and-play devices that can be easily connected to any Sun Ray environment. No costly server, client, or software upgrades are necessary, because these new clients work well with all past and current versions of Sun Ray Software. This provides tremendous investment protection for Sun Ray customers.

The Sun Ray 270 all-in-one virtual display client integrates Sun Ray functionality with a 17-inch, flat-panel display for a sleek, ergonomic design. The compact unit is perfect for tight desktop spaces. With four USB ports and two serial ports, the Sun Ray 270 virtual display client is also ideal for situations that require legacy peripherals. A projector port makes this unit the right choice for conference rooms, allowing presenters to bring a smart card, rather than a laptop. An additional port for PC displays is included.

When coupled with Sun Ray Software 4, the Sun Ray 270 virtual display client interoperates with Microsoft applications better than ever before. Oracle now offers a fully licensed Remote Desktop Protocol (RDP) client, the Sun Ray Connector for Windows. This feature enables a direct connection between the Sun Ray Server and Windows Terminal Services. It can be used to provide a full-screen Windows desktop or provide access to specific Windows applications on Solaris or Linux desktops. Users can access local peripherals, cut and paste between applications on different operating systems, and authenticate Windows applications with a smart card.

Sun Ray 270 Virtual Display Client System Specifications

Hardware	
Graphics	24-bit graphics, 17-inch thin film transistor (TFT) and flat-panel liquid crystal display (LCD), up to 1280 × 1024 resolution maximum @ 75 Hz
Peripheral interface	Four powered USB ports, two serial ports, one RGB projector port, one DB15 port for display input
Networking	10/100Base-T
Input devices	USB keyboard, USB mouse, smart card reader ISO-7816-1
Audio	CD-quality audio in/out, microphone, headphone jacks, stereo line level in
Monitor	Integrated 17-inch TFT and LCD flat-panel display
Adjustments	Monitor tilt
Dimensions and Weight	
Width	376.6 mm
Depth	191.0 mm
Height	407.0 mm
Weight	5.2 kg

Regulations (Meets or Exceeds the Following Requirements)	
<ul style="list-style-type: none"> • Safety: UL 60950/CSA C22.2-60950; EN 60950 • Ergonomics: GS Mark • EMC: CISPR22; EN55022 Class B; FCC CFR Title 47, Part 15, Subpart B, Class B; EN55024:1998; IEC6100-3-2; IEC6100-3-3 (CISPR24:1997) • Power management: EPA Energy Star compliant • RoHS-6 Compliant 	
Environment	
Operating	Nonoperating
<ul style="list-style-type: none"> • 0°C to 35°C (32°F to 95°F) • 5% to 93% RH • 3 km (10 K ft.) 	<ul style="list-style-type: none"> • – 20°C to 60°C (– 4°F to 140°F) • 5% to 93% RH • 12 km (39 K ft.)
Power	
<ul style="list-style-type: none"> • AC power • Power consumption: 100 V to 240 V AC autoranging power supply, 50 Hz to 60 Hz, 1.5 A • System power consumption: 60 W AC maximum, 40 W typical with keyboard and mouse attached 	
Acoustic Emissions	
<p><3.0 B, <28 dBA (operator), ISO 9296</p>	

Warranty

Visit oracle.com/sun/warranty for Oracle's global warranty support information on Sun products.

Services

Visit oracle.com/sun/services for information on Oracle's service program offerings for Sun products.

Contact Us

For more information about Oracle's Sun Ray 270 virtual display client, please visit oracle.com/sun or call +1.800.786.0404 to speak to an Oracle representative.



Copyright © 2006, 2009, Oracle and/or its affiliates. All rights reserved.

This document is provided for information purposes only and the contents hereof are subject to change without notice. This document is not warranted to be error-free, nor subject to any other warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose. We specifically disclaim any liability with respect to this document and no contractual obligations are formed either directly or indirectly by this document. This document may not be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without our prior written permission.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. UNIX is a registered trademark licensed through X/Open Company, Ltd. 0909

