

Trusted Solaris Global Index

Sun Microsystems Federal, Inc.
A Sun Microsystems, Inc. Business
901 San Antonio Road
Palo Alto, CA 94303
U.S.A.

Part No: 805-8015-10
Revision A, July 1997



THE NETWORK IS THE COMPUTER™

Copyright 1997 Sun Microsystems, Inc. 2550 Garcia Avenue, Mountain View, California 94043-1100 U.S.A. All rights reserved.

This product or document is protected by copyright and distributed under licenses restricting its use, copying, distribution, and decompilation. No part of this product or document may be reproduced in any form by any means without prior written authorization of Sun and its licensors, if any. Third-party software, including font technology, is copyrighted and licensed from Sun suppliers.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, SunSoft, SunDocs, SunExpress, and SunOS, OpenWindows, NFS, Sun Ultra, Ultra, JumpStart, Solaris, Solstice, Solstice AdminSuite, Solstice AdminTools, Solstice Autoclient, Solstice CacheOS, DiskSuite, ToolTalk, X11/NeWS, Trusted NeWSprint, IPC, OpenBoot, SHIELD, XView, SunInstall, and Trusted Solaris are trademarks, registered trademarks, or service marks of Sun Microsystems, Inc. in the U.S. and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc. X/Open® is a registered trademark and "X" device is a trademark of X/Open Company Limited, Netscape is a trademark of Netscape Communications Corporation, and PostScript is a trademark of Adobe Systems, Incorporated.

The OPEN LOOK and Sun™ Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

RESTRICTED RIGHTS: Use, duplication, or disclosure by the U.S. Government is subject to restrictions of FAR 52.227-14(g)(2)(6/87) and FAR 52.227-19(6/87), or DFAR 252.227-7015(b)(6/95) and DFAR 227.7202-3(a).

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright 1997 Sun Microsystems, Inc., 2550 Garcia Avenue, Mountain View, Californie 94043-1100 Etats-Unis. Tous droits réservés.

Ce produit ou document est protégé par un copyright et distribué avec des licences qui en restreignent l'utilisation, la copie, la distribution, et la décompilation. Aucune partie de ce produit ou document ne peut être reproduite sous aucune forme, par quelque moyen que ce soit, sans l'autorisation préalable et écrite de Sun et de ses bailleurs de licence, s'il y en a. Le logiciel détenu par des tiers, et qui comprend la technologie relative aux polices de caractères, est protégé par un copyright et licencié par des fournisseurs de Sun.

Des parties de ce produit pourront être dérivées des systèmes Berkeley BSD licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, SunSoft, SunDocs, SunExpress, et Solaris SunOS, OpenWindows, NFS, Sun Ultra, Ultra, JumpStart, Solstice, Solstice AdminSuite, Solstice AdminTools, Solstice Autoclient, Solstice CacheOS, DiskSuite, ToolTalk, X11/NeWS, Trusted NeWSprint, IPC, OpenBoot, SHIELD, XView, SunInstall, et Trusted Solaris sont des marques de fabrique ou des marques déposées, ou marques de service, de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays. Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc. X/Open® est une marque enregistrée et "X" device est une marque de X/Open Company Limited, Netscape est une marque de Netscape Communications Corporation, et PostScript est une marque de Adobe Systems, Incorporated.

L'interface d'utilisation graphique OPEN LOOK et Sun™ a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciés de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui en outre se conforment aux licences écrites de Sun.

CETTE PUBLICATION EST FOURNIE "EN L'ETAT" ET AUCUNE GARANTIE, EXPRESSE OU IMPLICITE, N'EST ACCORDEE, Y COMPRIS DES GARANTIES CONCERNANT LA VALEUR MARCHANDE, L'APTITUDE DE LA PUBLICATION A REpondre A UNE UTILISATION PARTICULIERE, OU LE FAIT QU'ELLE NE SOIT PAS CONTREFAISANTE DE PRODUIT DE TIERS. CE DENI DE GARANTIE NE S'APPLIQUERAIT PAS, DANS LA MESURE OU IL SERAIT TENU JURIDIQUEMENT NUL ET NON AVENU.



Contents

Global Index.....	1
-------------------	---

Preface

This document provides a global index that covers the following manuals:

- *Trusted Solaris Audit Administration* (805-8010-10)
- *Trusted Solaris Administration Overview* (805-8007-10)
- *Trusted Solaris Administrator's Procedures* (805-8008-10)
- *Trusted Solaris Developer's Guide* (805-8014-10)
- *Trusted Solaris Label Administration* (805-8011-10)
- *Trusted Solaris Installation and Configuration* (805-8009-10)
- *Trusted Solaris User's Guide* (805-8006-10)

How This Index is Organized

The global index begins on page 1 and uses the following prefixes to identify the manuals referred to:

- aa-Audit Admin (*Trusted Solaris Audit Administration*)
- ao-Admin Overview (*Trusted Solaris Administration Overview*)
- at-Admin Tasks (*Trusted Solaris Administrator's Procedures*)
- dg-Developer's Guide (*Trusted Solaris Developer's Guide*)
- la-Label Admin (*Trusted Solaris Label Administration*)
- ic-Installation & Configuration (*Trusted Solaris Installation and Configuration*)
- ug-User's Guide (*Trusted Solaris User's Guide*)

Global Index

Symbols

- (minus sign)
 - in begin and finish scripts, ic:196
 - in rules, ic:169
- ! (exclamation mark) rule field, ic:166
- audit flag prefix, aa:10
- # (pound sign)
 - in profiles, ic:155
 - in rules, ic:169
- && (ampersands) rule field, ic:166
- + audit flag prefix, aa:10
- ... (ellipsis points) rule field, ic:166
- /etc/passwd file, ic:65
- /etc/shadow file, ic:65
- = (equals sign) in profile field, ic:182
- > prompt, changing to ok prompt, ic:198
- [] (brackets) rule field, ic:166
- \ (backslash) in rules, ic:169
- ^- audit flag prefix, aa:10
- ^+ audit flag prefix, aa:10

A

- abbreviations in names, dg:327
- accept command
 - modified for Trusted Solaris, at:382
 - default profile, at:493, ao:149

access

- access control decisions, la:11
- checks
 - executing a file, dg:23
 - IPC files, dg:217
 - mapped memory, dg:220
 - MLDs, dg:168
 - network, dg:217, dg:221
 - opening a file, dg:20
 - pipes, dg:218, dg:219
 - process tracing, dg:220
 - processes, dg:217
 - PTYs, dg:219
 - signals, dg:220
 - SLDs, dg:168
 - sockets, dg:223
 - System V IPC, dg:217, dg:221
 - TLI, dg:223
 - writing to a file, dg:22
 - X Window System, dg:284
- discretionary operations, dg:17
- file
 - algorithms, ao:44, ao:47
 - data files, ao:40
 - executables, ao:36
 - overview, ao:33, ao:47
- file labels, dg:93
- file privileges, dg:55
- file systems

- code examples, dg:19
 - privileges, dg:18
 - security policy, dg:17
- guidelines for SLs, dg:95
- mandatory operations, dg:17
- multilevel port connections, dg:222
- protection, dg:87
- review of concepts, at:305 to at:317
- access audit record, aa:157
- access control, la:5
- access control lists, *See* ACLs
- access policy
 - files, directories and file systems, at:306
- ACCESS_RELATED flag, dg:137
- access-related words
 - defined, la:76
- account label ranges
 - defined, la:6
 - overview, ao:10 to ao:11
 - setting minimum SL
 - setting on user and role accounts, la:33
- account SL ranges
 - assigning, ao:76
- account status
 - Password dialog box, ao:72
- accounts
 - assigning account type, at:105
 - assigning clearances, at:116
 - assigning comments, at:103
 - assigning execution profiles, at:120 to at:121
 - assigning home directories, at:113 to at:115
 - assigning idle time, at:122 to at:123
 - assigning labels, at:116 to at:119
 - assigning passwords, at:106 to at:113
 - assigning roles, at:122
 - assigning shells, at:104
 - assigning user information, at:102
 - authorizations for setting up, at:62
 - configuring, *See* User Manager
 - creating the first two users, ic:95
 - division of setup tasks, at:61 to at:62
 - label range
 - example, ao:11
 - overview, ao:10 to ao:11
 - managing, at:57 to at:85
 - planning, at:58 to at:60
 - preconditions for setup, at:58
 - procedures for setting up, at:124 to at:155
 - roles, ug:13
 - setting labels, la:33
 - startup files, at:65 to at:85
 - users, ug:18
 - worksheet, at:192
- accreditation checking
 - networks, ao:97, ao:98
- ACCREDITATION RANGE section
 - label_encodings example, la:161
- accreditation ranges
 - See also* label ranges
 - checking, dg:131, dg:132
 - described, at:308
 - label encodings file, ao:5
 - network interfaces, ao:93
 - networks, dg:238
 - overview, ao:7 to ao:9
 - structurs, dg:99
 - system, ao:7
 - user, ao:8
- acct audit record, aa:158
- acl token
 - described, aa:128
 - praudit display, aa:129
- ACLs
 - (access control lists)
 - adding entries, ug:102 to ug:103
 - changing entries, ug:104 to ug:105
 - defined, ug:96 to ug:97
 - deleting entries, ug:106
 - described, at:305
 - displaying entries, ug:100 to ug:101
 - information on, dg:33
 - introduction, ug:4

actions

- adding new administrative, at:24 to at:26
- assigning inheritable privileges, dg:332, ao:29
- assigning to execution profiles, at:221, ao:117
- creating, dg:332
- defined, at:441
- execution profiles, ao:38
- in execution profiles, at:195, ao:21
- linked list data type, dg:208
- restricted by account profiles, at:444
- running, ao:23
- using actions, at:466

actions field, dg:207

actname field, dg:208

ad audit class, aa:95 to aa:99

ad audit flag, aa:8, aa:94

adb command

- default profile, at:493, ao:149

Add Workspace menu item

- described, ug:78

add_drv audit record, aa:236

add_drv command

- default profile, at:493, ao:149
- Trusted Solaris modifications, ao:135

add_install_client command

- custom JumpStart example, ic:257 to ic:258
- example, ic:134, ic:179
- install server setup, ic:133 to ic:135
- JumpStart directory access, ic:151, ic:153
- syntax, ic:133, ic:179

adjtime audit record, aa:158

adjunct file, *See* vfstab_adjunct(4TSOL)

Admin Edit action, at:12

admin role, *See* system administrator

admin tools

- authorizations, ao:26
- overview, ao:50 to ao:58

ADMIN_HIGH label

- defined, dg:113, ao:6
- initialize to, dg:113
- overview, la:20
- replacing with CIPSO label, at:296
- running applications, dg:15

ADMIN_LOW label

- defined, dg:113, ao:6
- initial administrative workspace label, la:28
- initialize to, dg:113
- installing publicly available software, at:437
- overview, la:20
- running applications, dg:15

administration labels

- defined, ao:6
- visibility, ao:77

administrative actions

- accessible through the Application Manager, ic:76
- creating, at:24 to at:26
- in Solstice_Apps folder, ic:79
- in System_Admin folder, ic:78
- introduced, at:444

administrative audit class, aa:8

administrative labels

- changing names, la:102
- displaying and hiding, la:102
- displaying substitute names, la:109
- number defined for each label type, la:21
- overriding the system default view, la:34
- overview, la:20
- setting view on user and role accounts, la:33
- visible to the install team, ic:71
- workspace use, la:28

administrative role workspaces, la:11

administrative roles

- See also* roles
- adding to three /etc files, ic:64
- applications

launching, at:23
 location on the desktop, at:23
 assuming, aa:42
 background, at:4 to at:5
 procedure, at:12 to at:20
 changing workspace SLs, at:21
 configuring
 See also User Manager
 configuring Trusted Solaris, ic:5
 defined, ao:24
 described, at:89 to at:90
 in installation, ic:17
 password, at:5
 planning role account security, ic:51
 switching workspaces, at:21
 task division, ic:17
 verifying during configuration, ic:97
 workspaces
 display when role is
 assumed, at:5
 using, at:7 to at:24
 adminvi command
 default profile, at:493, ao:149
 described, at:12
 overview, ao:138
 adorned pathnames
 described, at:309, dg:170
 translating, dg:170
 adornfc(3TSOL)
 code example, dg:176
 declaration, dg:174
 adornments
 defined, ao:17
 described, at:44
 advisory labels
 See also ILs
 advisory labels
 synonym for ILs, ug:8
 ahl_t policy
 flag, aa:25
 algorithms
 file access, ao:44, ao:47
 IL floating, dg:90
 process privileges, dg:52
 aliases
 creating audit_warn mail
 alias, aa:52
 setting up, at:164, at:167
 all
 audit class, aa:9, aa:94
 audit flag, aa:94
 caution for using, aa:10
 described, aa:9
 in user audit fields, aa:15
 value for *filesys*, ic:160
 All execution profile
 allowing standard UNIX access to
 commands and
 actions, at:442
 ordering in an account's profile
 list, at:443
 ALL_ENTRIES flag, dg:137
 allhard string with audit_warn
 script, aa:20
 allocatable devices
 labeling, ic:75
 managing allocation, at:420
 allocate audit record
 allocate-list device
 failure, aa:238
 allocate-list device
 success, aa:238
 deallocate device, aa:237
 deallocate device
 failure, aa:238
 device allocate
 failure, aa:237
 device allocate
 success, aa:237
 allocate command
 default profile, at:493, ao:149
 Trusted Solaris modifications, ao:134
 Allocate Device menu item
 described, ug:88 to ug:91
 allocate error state, at:408, at:413
 allowed privileges, at:440
 See also privilege sets

assigning, ao:29
 defined, dg:52, ao:26
 file attributes, ao:39
 on file systems, ao:124, dg:33
 set to none during write, dg:55
 turning off, dg:68

allsoft string with *audit_warn*
 script, aa:20

alternative installation programs, ic:196

always-audit flags
 described, aa:15 to aa:16
 process preselection mask, aa:17

ampersands (&&) rule field, ic:166

aname
 classification keyword, la:53

AND rule field, ic:166

angle bracket (>) prompt, ic:198

any
 rule keyword
 description and values, ic:169
 rootdisk matching, ic:174
 slice value for *filesys*, ic:160

ap audit flag, aa:9, aa:94

APIs
 (application programming interfaces)
 See also library routines
 See also system calls
 declarations, dg:339 to dg:361
 list of types, dg:5 to dg:12
 security policy on man pages, dg:325

application audit class, aa:9

application auditing
 See also auditing
 See also code examples
 API declarations, dg:347
 appending record
 information, dg:192
 argument information, dg:201
 audit trail, dg:186
 command line arguments, dg:202
 control commands, dg:183
 creating audit records, dg:187
 creating parallel audit
 records, dg:196
 described, dg:182
 event definition numbers, dg:182
 information label, dg:192
 invalid call, dg:187
 IPC identifier, dg:204
 preselection mask, dg:195
 privilege sets, dg:203
 privileged tasks, dg:46, dg:183
 process preselection mask, dg:185
 queueing record information, dg:193
 return token, dg:190
 return values, dg:190
 save area, dg:197
 sensitivity label, dg:199
 server area, dg:199
 subject token, dg:190
 terminator command, dg:184
 token commands, dg:184
 valid call, dg:188

Application Manager
 accessing administrative
 programs, ic:76
 accessing applications, ao:23
 as trusted process, at:444
 differences in Trusted Solaris, ug:76
 launching, ao:51
 passing inheritable privileges, at:454
 using AdminSuite, at:8
 using Solstice_Apps, at:8
 using System_Admin, at:8

application programming interfaces, *See*
 APIs

applications
 See also application auditing
 accessing, ao:23
 administering, ao:19
 administrative, dg:15
 launching, at:23
 assigning forced privileges, at:476
 importing, at:438
 integration, dg:331
 MLDs, dg:169
 setting up with a real UID of 0, at:473
 setting up with effective UID of
 0, at:473

- testing and debugging, dg:328
 - user, dg:16
- arbitrary token
 - described, aa:129
 - praudit display, aa:130
- arch* rule keyword, ic:169
- archived information
 - affixing physical labels, la:18
- areas of interest
 - represented by compartment, la:7
- arg token
 - described, aa:130, aa:134
 - praudit display, aa:131
- argclass field, dg:208
- argcount field, dg:208
- arge policy
 - exec_env token and, aa:133
- argmode field, dg:208
- argtype field, dg:208
- argv policy
 - exec_args token and, aa:133
- arp command
 - Trusted Solaris modifications, ao:101
- ASCII
 - See also* translation
 - color names, dg:134
- aspppd command
 - default profile, at:493, ao:149
- assigning privileges
 - allowed, ao:29
 - forced, ao:29
 - inheritable, ao:29
 - overview, ao:26, ao:31
- at command
 - administrative differences, at:73 to at:82
 - running privileged commands, at:75
 - Trusted Solaris changes, at:81
- at audit record
 - at-create crontab, aa:239
 - at-delete atjob, aa:239
 - at-permission, aa:240
- at.allow file, at:76
- at.deny file, at:76
- atohexlabel command
 - default profile, at:493, ao:149
 - overview, ao:131
- atoms, predefined, dg:286
- atq command
 - administrative differences, at:73 to at:82
 - Trusted Solaris changes, at:81
- atrm command
 - administrative differences, at:73 to at:82
 - Trusted Solaris changes, at:82
- attr token
 - described, aa:131
- attribute flags
 - See also* security attribute flags
 - file systems, ao:124
- attribute token
 - praudit display, aa:132
- attributes
 - See also* security attribute flags
 - See also* security attributes
 - execution profile, ao:38
 - file, ao:39, ao:40
 - process, ao:42
 - user, ao:37
- audio coprocessor, at:409
- audit audit record, aa:159, aa:240
- audit classes
 - adding, aa:56
 - changing definitions, aa:5
 - mapping events, aa:4
 - overview, aa:4 to aa:5, ao:108
 - process preselection mask, dg:185
 - selecting for auditing, aa:4
 - setting mappings for attributable events, aa:90
 - setting mappings for non-attributable events, aa:90
 - third-party, dg:182

audit clients, aa:34
 audit command
 default profile, at:493, ao:149
 overview, ao:110
 audit daemon
 audit trail creation, aa:18, aa:66
 audit_startup file, aa:4
 audit_warn script
 conditions invoking, aa:19 to
 aa:21
 described, aa:18, aa:19
 directories suitable to, aa:18
 enabling auditing, aa:4
 functions, aa:18
 order audit files are opened, aa:13
 rereading the audit_control
 file, aa:13
 starting, aa:64
 starting manually, aa:89
 terminating, aa:64
 audit directories
 creating, aa:46
 mounting, aa:48
 audit events
 adding, aa:57
 audit_event file
 audit event type, aa:67
 audited by default, aa:3
 C library functions, aa:263
 categories, aa:6
 finding in audit trail, aa:80
 including in audit trail, aa:4
 kernel events
 audit tokens, aa:68
 auditconfig command
 options, aa:24
 described, aa:6
 mapping to classes, aa:4
 non-attributable, aa:6
 number ranges, aa:6
 numbers, aa:6
 numbers of system calls, aa:6
 overview, aa:4, aa:7
 pseudo-events, aa:6
 record formats and, aa:67
 third-party, dg:182
 user-level events
 audit tokens, aa:68
 auditconfig command
 options, aa:24
 described, aa:6
 viewing, dg:186
 audit files
 cleaning up not_terminated
 file, aa:87
 combing selected ones, aa:80
 copying login/logout messages to
 single file, aa:79
 directory locations, aa:11 to aa:12,
 aa:65
 displaying in entirety, aa:77
 /etc/security/audit_class
 file, aa:3
 /etc/security/audit_control
 file, aa:3
 /etc/security/audit_event
 file, aa:3
 /etc/security/audit_user
 file, aa:3
 /etc/security/audit_warn
 file, aa:3
 managing, aa:74
 managing size of, aa:19
 merging, aa:77
 minimum free space for file
 systems, aa:13
 names
 closed files, aa:73
 examples, aa:73
 form, aa:72
 still-active files, aa:73
 time stamps, aa:72
 use, aa:72
 nonactive files marked not_
 terminated, aa:87
 order for opening, aa:13
 overflow prevention, aa:85
 printing, aa:77, aa:78
 reading closed file, aa:76
 reading still-open file, aa:77

- reducing size, aa:81
- reducing storage space
 - requirements, aa:21 to aa:22
- specifying location, aa:49
- switching to new file, aa:64
- time stamps, aa:72
- audit flags
 - audit_control file line, aa:12
 - audit_user file, aa:14 to aa:16
 - C library functions, aa:263
 - changing dynamically, aa:63
 - definitions, aa:8
 - machine-wide, aa:8, aa:12
 - overview, aa:8
 - policy flags, aa:25
 - prefixes, aa:9 to aa:10
 - prefixes (modify), aa:10
 - process preselection mask, aa:16
 - setting, aa:50
 - setting user exceptions, aa:51
 - syntax, aa:9 to aa:10
- audit IDs
 - acquired at login, aa:17
 - ensuring successful tracking, aa:3
 - example audit record, aa:70
 - process attributes, aa:42
 - purpose when a role is assumed, aa:5
 - user attributes, aa:37
- audit mappings, aa:93 to aa:123
- audit -n command, aa:64
- audit partitions
 - creating, aa:41
 - removing free space, aa:44
- audit policies
 - determining, aa:61
 - setting, aa:25
 - setting permanently, aa:52
 - setting temporarily, aa:62
- audit records, aa:125 to aa:260
 - adding sequence token, aa:89
 - audit directories full, aa:18, aa:20
 - audit ID, aa:70
 - audit session ID, aa:70
 - C library functions, aa:263
 - converting to human-readable format, aa:76 to aa:82
 - creating in an application, dg:187
 - displaying by designated dates, aa:79
 - displaying user activities, aa:78
 - features in audit trail, aa:70 to aa:71
 - format, aa:67
 - format in audit trail, aa:67 to aa:68
 - format or structure, aa:67 to aa:71, aa:126, aa:157
 - human-readable format, aa:68
 - kernel-level generated, aa:157, aa:235
 - login record, aa:69 to aa:71
 - MAC, aa:235
 - MAC use, aa:235
 - minimum, dg:188
 - overview, aa:7
 - policy flags, aa:25
 - printing user activities, aa:78
 - pseudo-events, aa:235
 - reading, aa:69
 - removing sequence token, aa:89
 - selecting from audit trail, aa:75
 - self-contained records, aa:71
 - sending to a different file, aa:64
 - time-stamp format, aa:72
 - use of privilege, aa:235
 - user-level generated, aa:236 to aa:260
- audit -s command
 - preselection mask for existing processes, aa:13
 - rereading audit files, aa:18, aa:64
 - resetting directory pointer, aa:64
- audit servers
 - mount-point path names, aa:11
 - partitioning example, aa:41
 - planning, aa:34
- audit session ID, aa:17, aa:70
- audit -t command, aa:64
- audit tokens
 - described, aa:7
 - examples, aa:128 to aa:156
 - acl token, aa:128
 - arbitrary token, aa:129

arg token, aa:130, aa:134
 attr token, aa:131
 audit record format, aa:67 to aa:71,
 aa:126
 clearance token, aa:132
 exec_args token, aa:132
 exec_env token, aa:133
 exit token, aa:134
 file token, aa:134
 groups token, aa:135
 header token, aa:68, aa:69, aa:136
 host token, aa:137
 ilabel token, aa:137
 in_addr token, aa:138
 ip token, aa:139
 ipc token, aa:132, aa:139, aa:139 to
 aa:140
 ipc_perm token, aa:140
 iport token, aa:141
 liaison token, aa:141
 newgroups token, aa:142
 opaque token, aa:143
 order, aa:68
 order in audit record, aa:68
 path token, aa:143
 policy flags, aa:25
 priv token, aa:144
 privilege token, aa:144
 process token, aa:145
 reading, aa:68
 return token, dg:190
 return token, aa:146 to aa:147
 seq token, aa:147
 slabel token, aa:147
 socket token, aa:148 to aa:149
 socket_inet token, aa:149
 subject token, aa:150
 subject token structure, dg:190
 table of, aa:126
 text token, aa:150
 trailer token, aa:68, aa:151
 types, aa:67
 xatom token, aa:152
 xcolormap token, aa:152
 xcursor token, aa:153
 xfont token, aa:153
 xgc token, aa:153
 xpixmap token, aa:154
 xproperty token, aa:154
 xselect token, aa:155
 xwindow token, aa:155
 audit trail
 analysis
 auditing features, aa:70 to aa:71
 auditreduce
 command, aa:74 to aa:80
 costs, aa:21
 finding failed login
 attempts, aa:91
 of cost, aa:21
 praudit command, aa:76 to
 aa:82
 analyzing, aa:74
 auditreduce command, aa:74 to
 aa:80
 creating
 audit daemon's role, aa:18, aa:66
 audit_data file, aa:17
 directory suitability, aa:18
 managing audit file size, aa:19
 overview, aa:66
 debugging, aa:88
 directory locations, aa:11 to aa:12,
 aa:65
 events included, aa:4
 merging, aa:74
 monitoring in real time, aa:22
 overflow prevention, aa:85
 praudit command, aa:76 to aa:82
 audit_class file
 application auditing, dg:182
 creating class, dg:185
 overview, ao:110
 audit_control file
 application auditing, dg:182
 audit daemon rereading after
 editing, aa:13

audit_user file modification, aa:15
 C library functions, aa:263
 dir: line
 examples, aa:13
 files subdirectory, aa:11
 examples, aa:13
 flags: line
 described, aa:12
 prefixes in, aa:10
 process preselection mask, aa:16
 minfree: line
 audit_warn condition, aa:20
 described, aa:13
 naflags: line, aa:12
 overview, aa:3 to aa:6
 prefixes in flags line, aa:10
 problem with contents, aa:21
 process preselection mask, dg:185
 audit_data file, aa:17
 audit_event file
 application auditing, dg:182
 audit event type, aa:67
 creating event, dg:185
 overview, aa:4, aa:7, ao:110
 audit_startup file, aa:4
 audit_startup script
 overview, ao:111
 audit_user file
 overview, ao:109
 prefixes for flags, aa:10 to aa:11
 process preselection mask, aa:16
 user audit fields, aa:14 to aa:16
 audit_warn script, aa:19 to aa:21
 allhard string, aa:20
 allsoft string, aa:20
 auditsvc string, aa:20
 conditions invoking, aa:19 to aa:21
 described, aa:18, aa:19
 ebusy string, aa:20
 hard string, aa:20
 overview, ao:111
 postsigterm signal, aa:20
 soft string, aa:19
 tmpfile string, aa:20
 auditconfig command
 changing class mappings, aa:90
 default profile, at:493, ao:149
 options, aa:23 to aa:25
 overview, ao:111
 prefixes for flags, aa:10
 auditd command
 default profile, at:493, ao:149
 auditd daemon
 audit trail creation, aa:18, aa:66
 audit_startup file, aa:4
 audit_warn script
 conditions invoking, aa:19 to aa:21
 described, aa:18, aa:19
 execution of, aa:18
 directories suitable to, aa:18
 enabling auditing, aa:4
 functions, aa:18
 order audit files are opened, aa:13
 rereading the audit_control file, aa:13
 terminating, aa:64
 auditid field, dg:289
 auditing
 See also application auditing
 advanced setup procedures, aa:56 to aa:60
 advanced tasks for security administrator, aa:38
 audit ID, aa:70
 audit session ID, aa:70
 basic setup procedures, aa:40 to aa:56
 basic tasks for security administrator, aa:38
 client-server relationships, aa:39
 configuration files, ao:109
 considerations, aa:30
 defaults, aa:3, aa:4
 audit_startup file, aa:4
 disabling, aa:39
 dynamic procedures, aa:60
 for efficiency, aa:31

enabling, aa:4, aa:39 to aa:40
 header files, aa:264
 introduction, ug:3
 macro files, aa:264
 NIS+ client setup, ic:114
 NIS+ root master setup, ic:99
 non-networked workstation, ic:66 to
 ic:67
 overview, ao:107 to ao:112
 overview of administration, aa:1 to
 aa:3
 planning, ic:23 to ic:27, aa:28 to aa:36,
 ao:108 to ao:110
 preselection mask
 classes on file systems, dg:34
 process privileges, ao:28
 public files and directories, dg:36
 removing free space, aa:44
 setup tasks for system
 administrator, aa:37
 shutdown, aa:38
 site planning, aa:27
 software packages, aa:2
 space planning, aa:32, aa:33
 startup, aa:4, aa:38
 system privileges, ao:28
 tools, ao:110 to ao:112
 user ID, aa:70
 warning of trouble, aa:52

auditon audit record
 A_GETCAR command, aa:159
 A_GETCLASS command, aa:159
 A_GETCOND command, aa:160
 A_GETCWD command, aa:160
 A_GETKMASK command, aa:160
 A_GETSTAT command, aa:161
 A_GPOLICY command, aa:161
 A_GQCTRL command, aa:161
 A_SETCLASS command, aa:162
 A_SETCOND command, aa:162
 A_SETKMASK command, aa:163
 A_SETSMASK command, aa:163
 A_SETSTAT command, aa:163
 A_SETUMASK command, aa:164
 A_SPOLICY command, aa:164
 A_SQCTRL command, aa:165

auditreduce command
 capabilities, aa:75
 cleaning not_terminated
 files, aa:88
 default profile, at:494, ao:150
 described, aa:74
 distributed systems, aa:74
 examples, aa:76, aa:79, aa:88
 overview, ao:111
 time stamp use, aa:72

auditstat audit record, aa:165
 auditstat command
 default profile, at:494, ao:150
 overview, ao:112

auditsvc
 system call fails, aa:20

auditsvc audit record, aa:166

auditwrite(3TSOL)
 code examples, dg:46, dg:187 to
 dg:200
 declaration, dg:183
 invalid call, dg:187
 valid call, dg:188

AUE... names, aa:6

AUTH_authorized name, See
 authorizations and auth_
 desc(4TSOL)

auth_name file, at:35
 auth_names.h file, at:33
 auth_set_t type, dg:81
 auth_set_to_str(3TSOL)
 code example, dg:86
 declaration, dg:82

auth_t type, dg:81
 auth_to_str(3TSOL)
 code example, dg:84
 declaration, dg:82

authentication
 defined, ug:18
 procedure, ug:21 to ug:22

authorizations
 See also auth_desc(4TSOL) man page
 See also code examples
 See also privileges
 See also security policy
 See also translation
 adding, at:33
 administering printing, at:383
 and privileges, dg:41
 API declarations, dg:81 to dg:82,
 dg:342
 assigning to execution
 profiles, at:219, ao:117
 categories, ao:25
 device allocation, dg:80
 files, dg:80
 labels, dg:80
 login, dg:80
 software administration, dg:80
 X Window System, dg:80
 data types
 authorization ID, dg:81
 structure, dg:81
 defined, ug:13, ao:2
 downgrade file sensitivity label, la:9
 enable logins, at:6
 in execution profiles, ao:21, ao:38
 file access, ao:34
 for specifying fields in the User
 Manager, at:61
 Label builder, dg:315
 modify at admin, at:78
 modify at user, at:79
 modify cron admin, at:79
 modify cron user, at:79
 needed for users who assume
 secadmin role, at:5
 overview, ao:25 to ao:26
 print without banners, at:383
 print without labels, at:383
 and privileges, dg:40
 procedure for adding, at:36
 required for account setup, at:62
 required for User Manager, at:92 to
 at:94
 self-modification, at:94
 in software administration, ao:19
 tsolprof file, at:32
 upgrade file sensitivity label, la:9
 when to check, dg:41, dg:79
 auths field, dg:207
 auto size value, ic:160
 auto_install_sample directory
 check script, ic:175
 copying files to JumpStart
 directory, ic:148, ic:151
 set_root_pw finish script, ic:186 to
 ic:188
 automounting
 AutoHome Setup toggle, ao:74
 autopush command
 default profile, at:494, ao:150

AW_APPEND control command, dg:192
AW_ARG token command, dg:201
AW_CLEARANCE token
command, dg:192
AW_DEFAULTRD token
command, dg:197
AW_DISCARDRD token
command, dg:196
AW_END terminator command, dg:187
AW_EVENT token command, dg:188
AW_EXEC_ARGS token
command, dg:202
AW_FLUSH token command, dg:193
AW_GETRD token command, dg:196
AW_ILABEL token command, dg:192
AW_IPC token command, dg:204
AW_NOPRESELECT token
command, dg:195
AW_NOQUEUE token command, dg:193
AW_NOSAVE token command, dg:197
AW_NOSERVER token command, dg:199
AW_PATH token command, dg:196
AW_PRESELECT token
command, dg:195
AW_PRIVILEGE token
command, dg:203
AW_QUEUE token command, dg:193
AW_RETURN token command, dg:189,
dg:190
AW_SAVERD token command, dg:197
AW_SERVER token command, dg:199
AW_SLABEL token command, dg:189,
dg:199
AW_SUBJECT token command, dg:189
AW_TEXT token command, dg:190
AW_USERD token command, dg:196
AW_WRITE control command, dg:192
awk command
default profile, at:494, ao:150

B

backslash (\) in rules, ic:169
backup
before installation, ic:52
banner command, ic:120
banner pages
computing the classification, la:77
labeling, la:73 to la:75
printing without, at:397
banner_fields structure, dg:100
banners on print jobs, at:378
batch command
administrative differences, at:73 to
at:82
running privileged commands, at:75
bclabel_t type, dg:98
bclear_t type, dg:151
bclearhigh(3TSOL)
code example, dg:156
declaration, dg:152
bclearlow(3TSOL)
code example, dg:157
declaration, dg:152
bcleartoh(3TSOL)
code example, dg:164
declaration, dg:155
bcleartoh_r(3TSOL)
code example, dg:146, dg:165
declaration, dg:155
bcleartos(3TSOL)
code example, dg:162
declaration, dg:154
bclearundef(3TSOL)
code example, dg:157
declaration, dg:152
bclearvalid(3TSOL)
code example, dg:161
declaration, dg:154
bclhigh(3TSOL)
code example, dg:138
declaration, dg:102

bcllow (3TSOL)
 declaration, dg:102
bcltobanner(3TSOL)
 code example, dg:147
 declarationBinary, dg:107
bcltoh(3TSOL), declaration, dg:109
bcltoh_r(3TSOL), declaration, dg:109
bcltoil(3TSOL)
 code example, dg:128
 declaration, dg:103
bcltos(3TSOL)
 code example, dg:115, dg:138
 declaration, dg:107
bcltosl(3TSOL)
 code example, dg:128
 declaration, dg:102
bclundef(3TSOL)
 code example, dg:114
 declaration, dg:102
begin rule field
 described, ic:167
 valid entries, ic:169
 validation, ic:175
begin scripts
 creating derived profiles with, ic:182
 to ic:183
 overview, ic:181
 permissions, ic:182
 rule field, ic:167
 site-specific installation
 programs, ic:196
begin.log file, ic:182
bilabel_t type, dg:98
bilconjoin(3TSOL)
 code example, dg:129
 declaration, dg:105
bildominates(3TSOL)
 code example, dg:125
 declaration, dg:104
bilequal(3TSOL)
 code example, dg:125
 declaration, dg:104
bilhigh(3TSOL)
 code example, dg:140
 declaration, dg:103
billow(3TSOL)
 code example, dg:114
 declaration, dg:103
biltoh(3TSOL), declaration, dg:109
biltoh_r(3TSOL), declaration, dg:109
biltolev(3TSOL)
 code example, dg:128
 declaration, dg:103
 when to use, dg:123
biltos(3TSOL)
 code example, dg:140
 declaration, dg:108
bilundef(3TSOL), declaration, dg:103
bilvalid(3TSOL), declaration, dg:106
bimdominates(3TSOL)
 code example, dg:127
 declaration, dg:104
bimequal(3TSOL)
 code example, dg:127
 declaration, dg:104
binary
 to hexadecimal, dg:142, dg:145
binary audit record format, aa:67
bldominates(3TSOL)
 code example, dg:43, dg:124, dg:158
 declaration, dg:103, dg:152
blequal(3TSOL)
 code example, dg:124, dg:158
 declaration, dg:103, dg:152
blevel_t type, dg:151
blinrange(3TSOL)
 code example, dg:121
 declaration, dg:103, dg:152
blinset(3TSOL)
 code example, dg:131
 declaration, dg:107
blmaximum(3TSOL)
 code example, dg:130, dg:160
 declaration, dg:105, dg:153

blminimum(3TSOL)
 code example, dg:131, dg:161
 declaration, dg:105, dg:153
 blstrictdom(3TSOL)
 code example, dg:124, dg:158
 declaration, dg:103, dg:152
 bltocolo(3TSOL)
 code example, dg:134
 declaration, dg:106
 bltocolo_t(3TSOL),
 declaration, dg:106
 bltype(3TSOL)
 code example, dg:114, dg:157
 declaration, dg:105, dg:153
 body pages
 labels, at:368, la:72
 specifying SLs to print instead of
 ILs, at:396
 boot execution profile, at:457
 boot information
 copying during custom
 JumpStart, ic:257
 boot server
 adding Trusted Solaris files, ic:124
 creating on subnet, ic:136
 booting the workstation
 during installation, ic:91
 I/O interrupt error messages, ic:120
 interactive installation, ic:56
 resetting terminals and display
 first, ic:120
 system privileges, ao:28
 bootparams file
 adding *tsol_config* keyword, ic:131
 enabling JumpStart directory
 access, ic:152
 Bourne shell scripts in rule fields, ic:167
 bracketing, *See* privilege bracketing
 brackets [] rule field, ic:166
 brange_t type, dg:99
 broadcast messages
 network privileges, ao:28
 bslabel_t type, dg:98, dg:171
 bslevel_t type, dg:99
 bsllow(3TSOL)
 code example, dg:114
 declaration, dg:103
 bsllow(3TSOL), declaration, dg:103
 bslttoh(3TSOL), declaration, dg:109
 bslttoh_r(3TSOL), declaration, dg:109
 bsltos(3TSOL)
 code example, dg:130, dg:138
 declaration, dg:108
 bslundef(3TSOL), declaration, dg:103
 bsvalid(3TSOL)
 code example, dg:133
 declaration, dg:106
 bsmconv command
 default profile, at:494, ao:150
 overview, ao:112
 bsmconv script
 enabling auditing, aa:39 to aa:40
 bsmunconv command
 default profile, at:494, ao:150
 overview, ao:112
 bsmunconv script, aa:39
 builders, GUI
 See also label builder
 API declarations, dg:351
 interfaces described, dg:309
 buses
 SBus requirements, ic:38
 supported, ic:248
 VMEbus requirements, ic:38
C
 C library functions, aa:263
 cacheofs, at:327
 cacheofslog command
 default profile, at:494, ao:150
 calendar
 differences in Trusted Solaris, ug:72
 cancel command
 modified for Trusted Solaris, at:382

- default profile, at:494, ao:150
- carat (^) in audit flag prefixes, aa:10
- cat command
 - default profile, at:494, ao:150
- caveats field, dg:100
- caveats_len field, dg:99, dg:100
- cd command
 - default profile, at:494, ao:150
- CDE actions, *See* actions
- CDE configuration file default, at:114
- CDE workspaces
 - Trusted Solaris differences, la:10
- CDROM devices
 - device_clean script, at:408
 - mounting, at:343
 - requirement for Trusted Solaris installation, ic:38
- Change Input IL menu item
 - described, ug:85 to ug:87
- change password audit record, aa:250
- Change Password menu item
 - described, ug:80 to ug:84
- Change Workspace SL menu item
 - described, ug:78 to ug:79
 - example, ug:48
- changes to printing in Trusted Solaris, at:364 to at:393
- channels
 - configuring, la:96
 - on print job banner and trailer pages, la:86 to la:95
 - worksheet example, la:148
- channels field, dg:100
- CHANNELS section
 - label_encodings example, la:157
 - label_encodings file, la:86 to la:95
- channels_len field, dg:99, dg:100
- chdir audit record, aa:166
- check script
 - comments and, ic:169
 - derived profiles and, ic:183
 - directory for, ic:175
 - rules file validation, ic:175 to ic:176
 - rules.ok file creation, ic:175
 - starting, ic:175 to ic:179
 - testing rules, ic:176
- checklists for administrators, ic:241 to ic:246
- chgrp command
 - default profile, at:494, ao:150
- chk_encodings command
 - default profile, at:494, ao:150
 - description, la:47
 - overview, ao:131
 - scope of check, la:40
- chkauth(3TSOL)
 - code example, dg:41, dg:83
 - declaration, dg:81
- chkey command
 - default profile, at:494, ao:150
- chmod audit record, aa:167
- chmod command
 - default profile, at:494, ao:150
- chown audit record, aa:167
- chown command
 - default profile, at:494, ao:150
- chroot audit record, aa:168, aa:241
- CIPSO
 - (Common Internet Protocol Security Option)
 - host type, ao:87
 - described, at:265
 - remote host templates, ao:90
 - replacing ADMIN_HIGH, at:296
 - use in packets, at:250

cl audit class, aa:100
 cl audit flag, aa:8, aa:94
 cl_tsol_incoming_attrsp field, dg:274
 cl_tsol_outgoing_attrsp field, dg:274
 clabel_len field, dg:99
 classes
 changing definitions, aa:5
 flags and definitions, aa:8, aa:9
 mapping events, aa:4
 overview, aa:4, aa:7
 selecting for auditing, aa:4
 classification label component
 defined, ug:5, ao:4
 maximum number definable, la:7
 classifications
 changing, la:53
 changing display in label builder, la:103
 clearance component, dg:149
 described, at:309
 dominate, dg:123, dg:125, dg:158
 equal, dg:123, dg:125, dg:158
 field length, la:7
 IL component, dg:89
 keywords, la:53
 maximum number, la:7, la:53
 minimum number definable, la:7
 planning example, la:139
 rules for printing, la:77
 site analysis example, la:134 to la:138
 SL component, dg:89
 specifying colors, la:105 to la:113
 strictly dominate, dg:124, dg:158
 CLASSIFICATIONS section
 label_encodings example, la:153
 clear command
 default profile, at:494, ao:150
 clear_len field, dg:99
 clearance labels
 setting on user and role accounts, la:33
 clearance token
 described, aa:132
 praudit display, aa:132
 clearances
 See also process clearances
 account label range, ao:10
 assigning, at:116, ao:76
 checking clearances, dg:42
 defined, ug:5
 described, at:309
 label encodings file, la:5
 label overview, ao:4, ao:16
 minimum, ao:9
 minimum number to define, la:2
 network interfaces, ao:93
 planning, ic:18 to ic:23
 process attributes, ao:42
 remote host templates, ao:90
 session, dg:149
 setting for a single-SL system, la:9
 setting session, ug:26
 user, dg:149
 user attributes, ao:37
 worksheet example, la:146
 process clearances
 See also code examples
 See also labels
 See also translation
 CLEARANCES section
 label_encodings example, la:157
 CLIENT structure, dg:274
 client_arch profile keyword, ic:158
 client_root profile keyword, ic:158
 client_swap profile keyword, ic:158
 clist command
 overview, ao:141
 clock
 differences in Trusted Solaris, ug:72
 time zones for setting, ic:279 to ic:280
 clock_settime audit record, aa:168
 close audit record, aa:169
 closed networks
 defined, ao:84

`clri` command
 default profile, at:494, at:495, ao:150, ao:151
cluster profile keyword
 description and values, ic:159
 examples, ic:156
`.cm.rc` file, at:68
`cmds` field, dg:207
`cmp` command
 default profile, at:495, ao:151
 CMW labels
 (compartmented mode workstation labels)
 See also code examples
 See also ILs
 See also labels
 See also SLs
 See also translation
 API declarations, dg:345
 components, dg:88
 defined, ug:9, dg:87
 described, at:309
 file attributes, ao:39
 file systems, dg:33
 objects, dg:92
 on removable media, at:403
 processes, dg:91
 rules, la:14
 user interface appearance, dg:91
`cnt` policy
 flag, aa:25
 code examples
 accreditation range, checking, dg:131
 adding information label, dg:192
 auditing
 adding a sensitivity label, dg:199
 appending information, dg:192
 creating audit records, dg:46
 creating minimum record, dg:188
 creating parallel records, dg:196
 handling return values, dg:190
 invalid call, dg:187
 preliminary setup, dg:184 to dg:186
 queueing information, dg:193
 using preselection mask, dg:195
 using save area, dg:197
 using server area, dg:199
 valid call, dg:188
 writing arguments, dg:201
 writing command line arguments, dg:202
 writing IPC identifier, dg:204
 writing privilege sets, dg:203
 authorizations
 and privileges, dg:41
 checking, dg:41, dg:83
 freeing authorization sets, dg:86
 getting description text, dg:85
 translating ID to string, dg:84
 translating set to string, dg:85, dg:86
 translating string to ID, dg:84
 checking SLs, dg:42
 clearances
 checking before file access, dg:43
 checking if valid, dg:161
 checking type, dg:157
 checking prior to access, dg:42
 finding lower bound, dg:161
 finding upper bound, dg:160
 getting, dg:155
 initializing to ADMIN_
 LOW, dg:157
 initializing to undefined, dg:157
 setting, dg:156
 testing relationships, dg:158
 translating, dg:162, dg:163
 translating and clipping, dg:163
 translating to hex, dg:146, dg:164, dg:165
 CMW labels
 getting on file system, dg:118
 getting on window, dg:301
 getting pointers to portions, dg:128
 getting process label, dg:43, dg:115

- getting SL and IL, dg:115
- setting on file system, dg:119
- setting on window, dg:302
- setting process label, dg:117
- translating to ASCII, dg:138
- translating to binary, dg:143
- translating to hex, dg:145
- databases
 - enumerating, dg:216
 - getting profile entries, dg:212
 - getting user entries, dg:48, dg:212
- file systems
 - accessing, dg:19
 - executing, dg:23
 - getting attribute flags, dg:35
 - getting attributes, dg:31
 - getting attributes (inode), dg:33
 - getting CMW label, dg:118
 - getting label range, dg:121
 - opening a file, dg:20
 - setting CMW label, dg:119
 - writing to a file, dg:22
- ILs
 - conjoining, dg:129
 - creating, dg:117
 - floating, dg:116
 - testing markings, dg:127
 - testing relationships, dg:125
 - translating binary to
 - ASCII, dg:140
 - translating to binary, dg:143
- Label builder, dg:312
- label_encodings file
 - getting ASCII color
 - names, dg:134
 - getting information on, dg:135
 - retrieving version string, dg:112
 - translating printer
 - banner, dg:147
- labels, dg:111 to dg:148
 - checking accreditation
 - ranges, dg:131
 - checking if valid, dg:133
 - initializing, dg:114
 - translating with font list, dg:300
- MLDs
 - creating a file, dg:179
 - getting adorned name, dg:176
 - getting MLD name, dg:175
 - getting real path, dg:176
 - getting security attribute
 - flags, dg:35
 - getting security
 - attributes, dg:177
 - getting SLD name, dg:45
 - getting working
 - directory, dg:176
 - opening a file, dg:178
- printer banner, translating, dg:147
- privilege sets
 - bracketing effective set, dg:71
 - checking allowed set, dg:67
 - checking permitted set, dg:72
 - checking saved set, dg:74
 - clearing allowed set, dg:65
 - clearing effective set, dg:71
 - clearing inheritable set, dg:74
 - exec'ing a process, dg:77
 - forking a process, dg:75
 - removing permitted privs, dg:73
 - setting forced set on file, dg:67
 - setting inheritable set, dg:74
 - translating set to string, dg:67
- privileges
 - after checking
 - authorizations, dg:41
 - and authorizations, dg:41
 - asserting privileges in sets, dg:67
 - getting description text, dg:64
 - setting user ID, dg:78
 - translating ID to string, dg:63
 - translating string to ID, dg:63
 - when to use, dg:42
- processes, getting attribute
 - flags, dg:37
- RPC
 - example application, dg:275 to dg:279
 - header file, dg:275
 - running the application, dg:280

security configuration
 variables, dg:29

SLDs
 creating a file, dg:179
 getting name, dg:45
 getting security
 attributes, dg:177
 getting SLD name, dg:175
 getting working
 directory, dg:176
 opening a file, dg:178

SLs
 checking before file access, dg:43
 creating, dg:117
 finding lower bound, dg:131
 finding upper bound, dg:130
 getting file system range, dg:121
 testing relationships, dg:124
 translating to ASCII, dg:138
 translating to binary, dg:143

System V IPC
 using message queue
 labels, dg:230
 using semaphore set
 labels, dg:233
 using shared memory
 labels, dg:235

TSIX
 allocating space, dg:248
 clearing attributes, dg:256
 client application, dg:266 to
 dg:269
 comparing attributes, dg:256
 copying attribute
 structures, dg:255
 creating attribute masks, dg:257
 duplicating structures, dg:255
 examining the last
 attribute, dg:253
 example application, dg:258 to
 dg:269
 freeing allocated space, dg:258
 getting attribute size, dg:254
 getting attributes, dg:251
 getting endpoint
 defaults, dg:250
 getting endpoint mask, dg:250
 peeking at attributes, dg:253
 receiving attributes, dg:251
 receiving new attributess, dg:252
 replying to request, dg:260
 sending attributes, dg:248
 server application, dg:259 to
 dg:265
 setting attributes, dg:248
 setting endpoint defaults, dg:250
 setting enpoint mask, dg:250
 using multilevel ports, dg:258

vfstab_adjunct(4TSOL), dg:31

X Window System
 getting window
 attributes, dg:299
 getting window CMW
 label, dg:301
 getting window userID, dg:302
 getting workstation
 owner, dg:302
 Motif application, dg:298
 setting window CMW
 label, dg:302
 translating with font list, dg:300

col command
 default profile, at:495, ao:151

COLOR NAMES section
 label_encodings example, la:165

colormaps
 window privileges, ao:28

command arguments
 control, dg:183
 terminator, dg:184
 token, dg:184

commands
 assigning inheritable
 privileges, ao:29
 assigning to execution
 profiles, at:217, ao:117
 executing with privilege, aa:42
 execution profiles, ao:38
 in execution profiles, ao:21
 launching, ao:51
 linked list data type, dg:208

- maintenance commands, aa:261
 - privileged
 - run by `cron(1MTSOL)`, at:75
 - privileges, at:461
 - summary table, ao:58
 - trusted, at:461
- comments
 - assigning to accounts, at:103
 - assigning to users, ao:66
 - in profiles, ic:155
 - in `rules` file, ic:169
- commercial applications
 - adding, at:461
- Common Internet Protocol Security
 - Option, *See* CIPSO
- communication endpoints
 - See also* IPC
 - See also* TLI
 - access checks, dg:217, dg:221
 - connections described, dg:222
 - objects, dg:4
 - security attributes (TSIX), dg:239
- compartment label component
 - defined, ug:5, ao:4
- compartmented mode workstation labels,
 - See* CMW labels
- compartments
 - changing display in label
 - builder, la:103
 - clearance component, dg:149
 - defined, la:7
 - described, at:309
 - dominate, dg:123, dg:125, dg:158
 - equal, dg:123, dg:125, dg:158
 - field length, la:7
 - IL component, dg:89
 - planning example, la:140
 - setting up hierarchies, la:7
 - site analysis example, la:134 to la:138
 - SL component, dg:89
 - strictly dominate, dg:124, dg:158
 - worksheet example, la:145
- compile
 - auditing libraries, dg:183
 - authorization libraries, dg:80
 - clearance libraries, dg:151
 - Label builder libraries, dg:310
 - label libraries, dg:98
 - MLD libraries, dg:171
 - privilege libraries, dg:57
 - profile database access
 - libraries, dg:206
 - RPC libraries, dg:274
 - SLD libraries, dg:171
 - System V IPC libraries, dg:228
 - TSIX libraries, dg:241
 - user database access libraries, dg:206
 - X Window System libraries, dg:288
- component definitions
 - label encodings file, ao:5
- compress command
 - default profile, at:495, ao:151
- config_data file, ic:126
- configuration
 - labels, la:29
 - running with a single sensitivity
 - label, la:9
- configuration files
 - copying for distribution, ic:103
 - creating directory, ic:103
 - distributing to workstations, aa:53
 - SPARC systems
 - for concatenating multiple
 - disks, ic:194 to ic:196
- configuration files, *See also* databases
- configuration management
 - system privileges, ao:28
- configurations, *See* system security
 - configuration
- conjoining ILs, dg:90, dg:129
- connection requests
 - security attributes, dg:283
 - security policy, dg:284
- console redirection
 - system privileges, ao:28
- control commands, dg:183
- .copy_files file
 - described, ug:114

.copy_files files
 using, at:70

copy-and-paste
 effect on ILs, ug:9
 effect on SLs, ug:7
 example, ug:56 to ug:58

core files, dg:56

cost control, aa:21 to aa:23
 analysis, aa:21
 processing time, aa:21
 storage, aa:21 to aa:22

covert channel delays
 process privileges, ao:28

covert channels, dg:57

cp command
 default profile, at:495, ao:151

cpio command
 default profile, at:495, ao:151

CPUs (processors)
 rule keywords, ic:169

crash command
 default profile, at:495, ao:151

creat audit record, aa:169

creating the audit trail
 audit daemon's role, aa:18
 audit_data file, aa:17
 directory suitability, aa:18
 overview, aa:66

credentials
 installing, ic:91 to ic:92
 updating during configuration, ic:91

cron command
 administrative differences, at:73 to
 at:82
 running privileged commands, at:75
 default profile, at:495, ao:151

cron job, aa:19

cron.allow file, at:76

cron.deny file, at:76

cron command
 Trusted Solaris changes, at:80

crontab command
 administrative differences, at:73 to
 at:82

crontab audit record
 cron-invoke at job, aa:243
 crontab, aa:243
 crontab-crontab
 created, aa:242
 crontab-crontab
 deleted, aa:242
 crontab-permission, aa:243

crontabs documentation, ic:211

csh command
 default profile, at:495, ao:151

custom JumpStart installation
 advantages, ic:140
 booting and installing
 booting the system, ic:198 to
 ic:199
 described, ic:139
 diskless clients, ic:200
 examples, ic:251 to ic:258
 check script, ic:255
 engineering systems
 setup, ic:256
 JumpStart directory, ic:252 to
 ic:253
 marketing systems setup, ic:257
 to ic:258
 networked, ic:145
 non-networked, ic:144
 rules file editing, ic:254 to
 ic:255
 site setup, ic:251 to ic:252
 standalone system, ic:144

hands-off installation, ic:118
 requirements, ic:119

JumpStart directory, ic:179

optional features, ic:181 to ic:196
 begin scripts, ic:181 to ic:183
 finish scripts, ic:184 to ic:188
 overview, ic:181
 pfinstall command, ic:188
 to ic:191

- site-specific installation
 - programs, ic:196
 - overview, ic:143 to ic:145
 - preparing, ic:139 to ic:179
- customizations
 - changing printer output, at:372, la:75
 - label encodings file, ao:6
- Customize Trusted Solaris Configuration
 - dialog box
 - described, la:29
 - example, ic:261, la:151
 - planning before install, ic:19
- cut command
 - default profile, at:495, ao:151

D

- DAC
 - (discretionary access control)
 - See also* security policy
 - accessing System V IPC
 - objects, dg:226
 - cautions about override
 - privileges, at:460
 - defined, ug:4, ao:2
 - described, at:310
 - file access, ao:34
 - override privileges, at:439
 - privilege bracketing, dg:69
 - security policy, dg:13
- Data Encryption Standard, *See* DES
- data objects, *See* objects
- data packets, *See* packets
- data types
 - auditing, dg:183
 - authorization APIs, dg:80
 - clearance APIs, dg:151
 - label APIs, dg:98
 - Label buider APIs, dg:316, dg:317, dg:320
 - MLD APIs, dg:171
 - privilege APIs, dg:57
 - profile database access APIs, dg:206
 - RPC APIs, dg:273
 - SLD APIs, dg:171
 - System V IPC APIs, dg:228
 - TSIX APIs, dg:241
 - user database access APIs, dg:206
 - X Window System APIs, dg:288
- Database Manager
 - accessing network databases, at:280
 - adding a host to a running
 - system, at:348
 - installing local hosts, ic:79 to ic:80
 - installing tnrhdb(4TSOL), ic:80 to ic:83
 - installing tnrhttp(4TSOL), ic:80 to ic:82
 - network configuration
 - databases, ao:87
 - tnidb(4TSOL), ao:93
 - tnrhdb(4TSOL), ao:88
 - tnrhttp(4TSOL), ao:91
- databases
 - See also* code examples
 - accessing tnidb(4TSOL), at:254
 - accessing tnrhdb file, at:254
 - accessing tnrhttp(4TSOL), at:254
 - API declarations, dg:208, dg:209 to dg:211, dg:348
 - device_allocate file, ao:136
 - device_deallocate file, ao:136
 - device_maps file, ao:136
 - profile
 - data types, dg:207, dg:208
 - described, dg:205
 - src parameter, dg:208
 - tnidb database, ao:93
 - tnrhdb(4TSOL), ao:88
 - tnrhttp(4TSOL), ao:90
 - tsoluser(4TSOL), ic:65, ic:85
 - user
 - data types, dg:206
 - described, dg:205
 - during install, ic:85
 - during installation, ic:65
- date command
 - default profile, at:495, ao:151
- date-time auditreduce command
 - options, aa:79

dbmgr command
 default profile, at:495, ao:151

deallocate command
 default profile, at:495, ao:151
 Trusted Solaris modifications, ao:134

debugging
 applications, dg:328
 See also privilege debugging

default configuration, at:413

default groups
 ACL entry, ug:97

default label view, la:24

default masks
 ACL entry, ug:97

default others
 ACL entry, ug:97

default owning groups
 ACL entry, ug:97

default owning users
 ACL entry, ug:97

default routes
 setting, ic:78 to ic:79

default shells
 assigning to accounts, at:104

default users
 ACL entry, ug:97

defaults
 audit policies, aa:25
 derived profile name, ic:183
 execution profiles, ao:21
 machine-wide, aa:8
 partitioning, ic:162
 designating disks, ic:163
 excluding disks, ic:159
 privileges, ao:28
 SI_CONFIG_DIR variable, ic:185
 software group installed, ic:159

Defense Intelligence Agency
 See DIA

Delete menu item
 described, ug:78

derived profiles, ic:182 to ic:183

DES
 (Data Encryption Standard)

desc field, dg:207

/dev/kmem kernel image file
 security violation, at:463

Developer system support software
 cluster name, ic:159
 hard disk space required, ic:39
 profile example, ic:156

developers
 responsibilities, at:464

development environment privs, dg:40

device allocation
 during install, ic:75
 lock files, at:412
 meeting the object reuse
 requirement, at:403

Device Allocation Manager
 launching, ao:51
 overview, ao:132 to ao:134
 using, ic:75

device policy
 setting, ic:89

device_allocate file
 default contents, at:414
 Trusted Solaris modifications, ao:136

device_clean scripts
 for tape devices, at:408
 meeting object reuse
 requirements, at:403
 review, at:407

device_deallocate file
 Trusted Solaris modifications, ao:136

device_maps file
 Trusted Solaris modifications, ao:136

device_policy(4TSOL)
 setting, ic:89

devices
 allocatable
 default configuration, at:413
 allocating, aa:55
 allocating and deallocating, aa:55

allocation, ao:32, ao:132 to ao:138
 description, ug:88 to ug:91
 introduction, ug:4
 associated security risks, at:402
 authorizations, ao:25
 authorizations, defined, dg:80
 clean scripts, ao:137
 clearing prior to reuse, at:403, ug:13
 configuration files, ao:132, ao:135 to
 ao:136
 deallocating, aa:56
 displaying allocation
 information, ao:135
 frame buffer, at:413
 input device privileges, dg:287
 label ranges, dg:122, ao:32, ao:138
 managing allocation, at:420
 modified Solaris commands, ao:134
 to ao:135
 non-allocatable
 setting the label range, at:413
 overview, ao:32
 policy for access to, at:306
 printers
 default configuration, at:413
 required location of device special
 files, at:407
 setting policy for, at:419
 with removable media
 special object reuse
 requirements, at:403
 devpolicy audit record, aa:170
 df command
 default profile, at:495, ao:151
 dfstab file, ic:253
 DGA
 (Direct Graphics Access)
 See also X Window System
 privileges, dg:287
 DGA (direct graphics access)
 window privileges, ao:28
 DIA
 Encodings Format manual, la:4
 IL requirements, la:17
 diff command
 default profile, at:495, ao:151
 diff3 command
 default profile, at:495, ao:151
 dir field, dg:208
 dir: line in audit_control file
 example, aa:13
 for files subdirectory, aa:11
 dircmp command
 default profile, at:495, ao:151
 Direct Graphics Access, *See* DGA
 directories
 audit daemon pointer, aa:18
 audit directories full, aa:18, aa:20
 audit directory locations, aa:11 to
 aa:12, aa:65
 audit_control file
 definitions, aa:13
 changing
 to JumpStart directory, ic:176
 to mounted CD, ic:148, ic:151
 to Trusted Solaris CD image on
 local disk, ic:148, ic:150
 changing flags, at:321
 changing labels and privileges, at:336
 changing to mounted CD, ic:148,
 ic:151
 changing to Trusted Solaris CD image
 on local disk, ic:148
 diskfull machines, aa:41
 files subdirectory, aa:46
 files subdirectory for audit
 records, aa:11
 JumpStart
 adding files, ic:184, ic:185
 copying files, ic:185, ic:192
 copying installation files from
 CD, ic:148, ic:151
 creating, ic:142, ic:252
 creating for SPARC
 systems, ic:146 to ic:148
 enabling access, ic:151 to ic:153
 install server setup, ic:179
 permissions, ic:146, ic:149

- rules file example, ic:164
 - sharing, ic:253
- mounting audit directories, aa:48
- security attributes, at:318 to at:326
- sharing, at:343
- suitable to audit daemon, aa:18
- dirname command
 - default profile, at:495, ao:151
- disable command
 - modified for Trusted Solaris, at:382
 - default profile, at:495, ao:151
- discretionary access control, *See* DAC
- disk configuration files
 - copying to JumpStart
 - directory, ic:192
 - creating, ic:192
 - SPARC multiple disks, ic:194 to ic:196
 - SPARC systems, ic:192 to ic:193
 - creation using `prtvtoc`, ic:192
 - described, ic:188, ic:192
- disk space requirements, aa:21 to aa:22
- diskettes
 - allocating at ADMIN_LOW, ic:75
 - copying Trusted Solaris boot
 - diskette, ic:147
 - formatting, ic:147
 - JumpStart directory
 - access, ic:152
 - creating for SPARC
 - systems, ic:146 to ic:148
 - mounting, ic:147
- diskfull machines' audit directory, aa:41
- diskless boot flag, dg:38
- diskless clients
 - accessing a Trusted Solaris
 - image, ic:202
 - adding, ic:205
 - boot server, ic:205
 - configuring, ic:205
 - described, ic:40
 - platforms, ic:158
 - prerequisites, ic:201
 - providing a root password, ic:208
 - setting up home directories, ic:207
 - swap space, ic:158
 - task map, ic:13
- disksize* rule keyword
 - description and values, ic:170
 - rootdisk* matching, ic:174
- dispadm audit record, aa:244
- display
 - resetting after I/O interrupts, ic:120
- distributed computing, *See* IPC
- distributed systems' *auditreduce*
 - command use, aa:74
- dminfo command
 - Trusted Solaris modifications, ao:135
- DNS
 - (Domain Name Service)
 - setup, ic:88
- documents, policy for access to, at:306
- domain of interpretation, ao:90
- domainname* rule keyword, ic:169
- domains
 - rule keyword, ic:169
- dominance, la:11, la:12
- dominance of labels
 - described, at:310
 - overview, ug:6, ao:4
 - strict dominance, ug:7
- dominate
 - ILs, dg:125
 - levels, dg:123, dg:158
 - markings, dg:127
- dontuse* profile keyword, ic:159, ic:163
- downgrade file sensitivity label*
 - authorization, la:9
- downgrading labels
 - guidelines, dg:96
 - privileges needed, dg:93, dg:94
 - X Window System, dg:287
- drag-and-drop
 - effect on ILs, ug:9
 - effect on SLs, ug:7
- drvconfig command
 - default profile, at:495, ao:151

dtwm(1) command, at:444
du command
 default profile, at:495, ao:151

E

ebusy string and audit_warn
 script, aa:20
echo command
 default profile, at:495, ao:151
editing privileged executables, at:472
eeprom audit record, aa:244
eeprom command
 default profile, at:495, ao:151
effective GIDs, *See* GIDs
effective privileges
 See also privilege sets
 bracketing, dg:69, dg:70, dg:71
 change UID, GUID, or SGUID, dg:54
 code example, dg:71
 defined, dg:54
 privilege to change IDs, dg:56
effective UIDs, *See* UIDs
egid field, dg:208
ellipsis points (...) rule field, ic:166
e-mail
 labels, la:18
email
 aliases, at:164, at:167
 in Trusted Solaris, ug:12
 listing mail queues, at:167
 managing, at:157 to at:189
 options, at:176 to at:179
 overview, at:158 to at:164
 switching mail tools, at:180 to at:189
 troubleshooting, at:171 to at:176
enable command
 modified for Trusted Solaris, at:382
 default profile, at:496, ao:152
enable logins authorization, at:6
enabling logins
 after a reboot, at:5

End user system support software
 cluster name, ic:159
 hard disk space required, ic:39
ending
 signal received during auditing
 shutdown, aa:20
 terminating audit daemon, aa:64
endpoints, *See* communication endpoints
endprofent(3TSOL),
 declaration, dg:210
endprofstr(3TSOL),
 declaration, dg:210
enduserent(3TSOL)
 code example, dg:216
 declaration, dg:209
eng_profile example, ic:253
enter prom audit record, aa:170
Entire distribution software
 cluster name, ic:159
env command
 default profile, at:496, ao:152
equal
 ILs, dg:125
 levels, dg:123, dg:158
 markings, dg:127
equals sign (=) in profile field, ic:182
ERRORS
 section on man pages, at:439
errors, dg:15
 audit directories full, aa:18, aa:20
 internal errors, aa:20
/etc/bootparams file
 enabling JumpStart directory
 access, ic:152
/etc/cron.d/CRON,
 cron(1MTSOL) lock file, at:76
/etc/dfs/dfstab file, ic:253
/etc/init.d directory
 changing scripts, at:457
 starting and stopping scripts, at:459

/etc/nsswitch.conf file, ic:88
 /etc/security directory, aa:11
 /etc/security/audit
 directory, aa:11, aa:65
 /etc/security/audit/bsmconv
 script
 enabling auditing, aa:39 to aa:40
 /etc/security/audit/bsmunconv
 script, aa:39
 /etc/security/audit_data
 file, aa:17
 /etc/security/audit_event file
 overview, aa:4 to aa:6
 audit event type, aa:67
 /etc/security/audit_startup
 file, aa:4
 /etc/security/audit_warn
 script, aa:18, aa:19 to aa:21
 /etc/security/tsol/device_
 policy file, ic:89
 /etc/security/tsol/tnidb
 file, ic:46
 /etc/shadow file, ic:187
 /etc/skel file, at:69, at:114
 /etc/system file
 See system file
 /etc/vfstab file
 mount options, ic:161
 euid field, dg:208
 event numbers, aa:6
 event-class mappings
 changing, aa:32, aa:58
 planning, aa:31
 events
 C library functions, aa:263
 categories, aa:6
 including in audit trail, aa:4
 kernel events
 audit tokens, aa:68
 auditconfig command
 options, aa:24
 described, aa:6
 mapping to classes, aa:4
 non-attributable, aa:6
 numbers, aa:6
 overview, aa:4, aa:7
 record formats and, aa:67
 user-level events
 audit tokens, aa:68
 auditconfig command
 options, aa:24
 described, aa:6
 ex audit class, aa:100
 ex audit flag, aa:9, aa:94
 examples
 See also code examples
 CMW labels, la:15
 label planning, la:127 to la:166
 MAC decisions, la:11
 exclamation mark (!) rule field, ic:166
 exec audit class, aa:9
 exec audit record, aa:171
 exec system call
 CMW label values, dg:92
 inheritable privileges, dg:74
 privileges in new program, dg:77
 reset_il_on_exec, dg:92
 exec_args token
 described, aa:132
 praudit display, aa:133
 exec_env token
 described, aa:133
 praudit display, aa:134
 executable files
 assigning forced privileges, at:476
 editing while preserving
 privileges, at:472
 privilege sets, at:440
 execution profiles
 accessing, dg:210
 All
 allowing standard UNIX access
 to commands and
 actions, at:442
 contents, at:488, ao:144
 described, ao:21

ordering in an account's profile
 list, at:443
 All Authorizations
 contents, at:488, ao:144
 described, ao:21
 assigning, at:120, at:121, ao:77 to
 ao:79
 attributes, ao:38
 Audit Control
 contents, at:488, ao:144
 described, ao:21
 Audit Review
 contents, at:488, ao:144
 described, ao:21
 Basic Actions
 contents, at:488, ao:144
 described, ao:21
 Basic Commands
 contents, at:489, ao:145
 described, ao:22
 boot, at:457
 contents, at:492, ao:148
 checking, dg:40
 controlling the use of actions, at:444
 Convenient Authorizations
 contents, at:489, ao:145
 described, ao:22
 creating new for boot
 commands, at:457
 default, ao:21
 defined, ug:14
 described, at:310
 editing, at:198, at:232
 Enable Login
 contents, at:489, ao:145
 described, ao:22
 importance of order, at:442
 inetd command
 contents, ao:148
 inetd profile
 contents, at:492
 Maintenance and Repair
 contents, at:489, ao:145
 described, ao:22
 managing, at:193 to at:232
 Media Backup
 contents, at:489, ao:145
 described, ao:22
 Media Restore
 contents, at:489, ao:145
 described, ao:22
 NIS+ Administration
 contents, at:490, ao:146
 described, ao:22
 NIS+ Security Administration
 contents, at:490, ao:146
 described, ao:22
 Object Access Management
 contents, at:490, ao:146
 described, ao:22
 Object Label Management
 contents, at:490, ao:146
 described, ao:22
 Object Privilege Management
 contents, at:490, ao:146
 described, ao:22
 Outside Accred
 contents, at:490, ao:146
 described, ao:22
 overview, at:194 to at:197, ao:21 to
 ao:24
 Privileged Shells
 contents, at:490, ao:146
 described, ao:22
 using to start commands from
 run control scripts, at:459
 software administration, ao:19
 System Management
 contents, at:491, ao:147
 described, ao:22
 System Security
 contents, at:491, ao:147
 described, ao:22
 table of commands, at:493 to at:506,
 ao:149 to ao:162
 table of profile contents, at:488 to
 at:492, ao:144 to ao:148
 user attributes, ao:37
 User Management
 contents, at:491, ao:147
 described, ao:22

User Security
 contents, at:491, ao:147
 described, ao:22
 execve audit record, aa:171
 execve system call
 inheriting privileges across, at:450
 replacing the executing
 program, at:445
existing
 partitioning value, ic:162
 size value for *filesys*, ic:160
 exit audit record, aa:172
 Exit control, ug:92
 exit prom audit record, aa:172
 exit token
 described, aa:134
 praudit display, aa:134
explicit, partitioning value, ic:162
 exporting information
 rules for physical label, la:18
 exporting shared directories, ic:102
 exporting software, at:437
 expr command
 default profile, at:496, ao:152
 extended operations, dg:317
 external label view, la:23

F

fa audit class, aa:100
 fa audit flag, aa:8, aa:94
 FAF_ALL flag, dg:36
 FAF_MLD flag, dg:35
 FAF_PUBLIC flag, dg:36
 FAF_SLD flag, dg:35
 failsafe login
 defined, ug:34
 failure
 audit flag prefix, aa:10
 turning off audit flags for, aa:10
 fallback mechanism
 creating, at:287

 networks, at:274
 using for network
 configuration, ic:82
 false command
 default profile, at:496, ao:152
 fc audit class, aa:101
 fc audit flag, aa:8, aa:94
 fchdir audit record, aa:173
 fchmod audit record, aa:173
 fchown audit record, aa:174
 fchroot audit record, aa:174
 fcntl audit record, aa:175
 fd audit class, aa:102
 fd audit flag, aa:8, aa:94
 fdformat command, ic:147
 FDFS
 mounting in Trusted Solaris, at:328
fdisk profile keyword
 example, ic:157
 features, operating system, dg:2
 fgetcmwfsrange system call,
 declaration, dg:102
 fgetcmwlabel system call,
 declaration, dg:101
 fgetfatrflag(2TSOL),
 declaration, dg:27
 fgetfpriv system call,
 declaration, dg:60
 fgetfsattr system call,
 declaration, dg:27
 fgetmldadorn system call,
 declaration, dg:173
 fgetslldname system call
 creating SLDs, dg:168
 declaration, dg:172
 fgrep command
 default profile, at:496, ao:152
 file access algorithms, ao:44 to ao:47
 file command
 default profile, at:496, ao:152

- identifying multilevel
 - directories, at:50
- file field, dg:208
- File Manager
 - accessing applications, ao:23
 - ACLs, ug:98 to ug:107
 - adding ACL entries, ug:102 to ug:103
 - as trusted process, at:444
 - browsing other files and
 - folders, ug:106 to ug:107
 - changing ACL entries, ug:104 to ug:105
 - changing file ILS, ug:108 to ug:110
 - changing file SLs, ug:111 to ug:113
 - changing permissions, ug:100
 - changing privileges, ao:29
 - deleting ACL entries, ug:106
 - determining labels, ug:108
 - differences in Trusted Solaris, ug:72
 - displaying ACL entries, ug:100 to ug:101
 - displaying basic information, ug:99
 - labels, ug:108 to ug:114
 - launching, ao:50
 - overview, ao:117 to ao:120
 - overview for users, ug:94 to ug:114
 - passing inheritable privileges, at:454
 - permissions, ug:98 to ug:107
 - Privileges dialog box, at:453, at:454
 - viewing SLD contents, ug:51 to ug:53
- file privilege sets, at:440
- file systems, ao:124
 - See also* code examples
 - See also* label ranges
 - See also* MLDs
 - See also* security attribute flags
 - See also* security attributes
 - See also* SLDs
 - access privileges, dg:18
 - accessing MLDs, dg:168
 - ACL information, dg:33
 - attribute flags, ao:124
 - changing security attributes using
 - mount -S
 - command, at:340
 - changing security attributes using
 - newsecfs(1MTSOL), at:339
 - changing security attributes using
 - setfsattr(1MTSOL), at:339
 - changing security attributes using
 - vfstab file, at:340
 - differences in Trusted Solaris, ao:124 to ao:128
 - free space on audit servers, aa:13
 - hide upgraded names, dg:29
 - ILS, ao:124
 - IPC bind to file, dg:4
 - managing, at:303, at:344
 - MLDs, ao:124
 - modified Solaris commands, ao:125, ao:128
 - mounting, ao:125 to ao:128
 - objects, dg:3
 - polyinstantiated, dg:167
 - privileges, ao:28
 - privileges, defined, dg:51
 - review of concepts, at:305 to at:317
 - security attributes, at:318 to at:326, ao:124
 - security policy, dg:16, dg:17
 - sharing audit file system, aa:47
 - single label, at:325
 - accessing SLDs, dg:169
 - SLs, ao:124
 - Trusted Solaris commands, ao:124 to ao:125
 - types, at:327
- file token
 - described, aa:134
 - praudit display, aa:135

file_attr_acc audit class, aa:8
 file_attr_mod audit class, aa:8
 file_audit privilege, dg:34, dg:36
 file_audit privilege, dg:36
 file_close audit class, aa:8
 file_creation audit class, aa:8
 file_dac_execute privilege, dg:18
 file_dac_read privilege, dg:18
 file_dac_search privilege, dg:18,
 dg:78
 file_dac_write privilege, dg:18,
 dg:217
 file_deletion audit class, aa:8
 file_downgrade_il privilege, dg:94
 file_downgrade_sl
 privilege, dg:41, dg:93
 file_mac_read privilege, dg:18,
 dg:217
 file_mac_search privilege, dg:18
 file_mac_write privilege, dg:18
 resulting in a file's dominating its
 directory's SL, at:356
 file_nofloat privilege, dg:94
 file_owner privilege, dg:36, dg:93,
 dg:94
 file_read audit class, aa:8
 file_setfpriv privilege, dg:186
 file_setpriv privilege, dg:55
 file_upgrade_il privilege, dg:93,
 dg:94
 file_upgrade_sl privilege
 resulting in upgraded names, at:356
 file_write audit class, aa:8
 files
 accessing, ao:33 to ao:47
 ACLs, ug:94 to ug:107
 allowed privileges, dg:52
 attributes, ao:39 to ao:40
 authorizations, ao:25, ao:26
 authorizations, defined, dg:80
 changing flags, at:321
 changing labels, at:320
 changing labels and privileges, at:336
 changing privileges, at:320
 copying between File
 Managers, ug:113
 copying to other SLs with .copy_
 files, ug:114
 forced privileges, dg:52
 interpreted, dg:52
 label privileges, dg:93
 linking between File
 Managers, ug:113
 linking to other SLs with .link_
 files, ug:114
 managing, at:303 to at:344
 moving between File
 Managers, ug:111 to ug:113
 permissions, ug:94 to ug:107
 policy for access to, at:306
 privilege sets, dg:51
 privileges for creating core
 files, dg:56
 review of concepts, at:305 to at:317
 setting public object bit, aa:59
 when writing to executables, dg:55
 files and file systems
 begin scripts output, ic:182
 copying
 JumpStart installation files from
 CD, ic:148, ic:151
 Trusted Solaris boot
 diskette, ic:147
 creating local file systems, ic:160 to
 ic:161
 handling audit trail overflow, aa:87
 mounting, aa:47
 preserving data
 existing data, ic:161
 protecting, aa:45
 security attributes
 auditing, aa:264
 showing if shared, ic:127

files subdirectory, aa:11, aa:46
filesys profile keyword
 description and values, ic:158
 examples, ic:156 to ic:157
 finish rule field
 described, ic:167
 valid entries, ic:169
 validation, ic:175
 finish scripts
 adding, ic:185
 rule field, ic:167
 finish.log file, ic:184
 flags
 audit_control file line, aa:12
 audit_user file, aa:14 to aa:16
 C library functions, aa:263
 definitions, aa:8
 machine-wide, aa:8, aa:12
 overview, aa:8
 policy flags, aa:25
 process preselection mask, aa:16
 syntax, aa:9 to aa:10
 flags, *See* security attribute flags
 flags: line in audit_control file
 described, aa:12
 prefixes in, aa:10
 process preselection mask, aa:17
 floating, *See* ILS
 floppy devices
 device_clean script, at:408
 floppy disks
 physical labeling, la:18
 fm audit class, aa:103
 fm audit flag, aa:8, aa:94
 fold command
 default profile, at:496, ao:152
 font paths
 window privileges, ao:28
 fonts
 font list translation, dg:300
 font path privileges, dg:288
 forced privileges, at:440
 See also privilege sets
 when turning off allowed, dg:68
 assigning, ao:29
 clearing, dg:68
 defined, dg:52, ao:27
 file attributes, ao:39
 file systems, ao:124
 on file systems, dg:33
 set to none during write, dg:55
 fork audit record, aa:175
 fork system call
 CMW label values, dg:91
 creating processes, at:445
 guidelines for changing SLs, dg:96
 inheritable privileges, dg:74
 inheriting privileges across, at:450
 privileges in child, dg:75
 fork1 audit record, aa:176
 format command
 default profile, at:496, ao:152
 formatting diskettes, ic:147
 fr audit class, aa:103
 fr audit flag, aa:8, aa:94
 free size value for filesys, ic:160
 free_auth_set(3TSOL)
 code example, dg:86
 declaration, dg:82
 free_profent(3TSOL)
 code example, dg:212
 declaration, dg:211
 free_profstr(3TSOL)
 code example, dg:212
 declaration, dg:211
 free_userent(3TSOL)
 code example, dg:212
 declaration, dg:209
 Front Panel
 accessing applications, ao:23
 as trusted process, at:444
 differences in Trusted Solaris, ug:70
 to ug:76
 modifying, at:467
 passing inheritable privileges, at:454
 Style Manager

- changing session
 - characteristics, la:11
- Subpanels
 - as trusted processes, at:444
- FSA_ACL value, dg:33
- FSA_ACLCNT value, dg:33
- FSA_AFLAGS value, dg:33
- FSA_APRIV value, dg:33
- FSA_APSA value, dg:34
- FSA_APSACNT value, dg:34
- FSA_DFACL value, dg:33
- FSA_DFACLCNT value, dg:33
- FSA_FPRIV value, dg:33
- FSA_LABEL value, dg:33
- FSA_LBLRNG value, dg:34
- FSA_MLDPFX value, dg:34
- fsck command
 - default profile, at:496, ao:152
- fsdb command
 - default profile, at:496, ao:152
- fsetcmwlabel system call,
 - declaration, dg:101
- fsetfattrflag system call,
 - declaration, dg:27
- fsetfpriv system call,
 - declaration, dg:60
- fsirand command
 - default profile, at:496, ao:152
- fstatfs audit record, aa:176
- ftpd login audit record, aa:246
- functions, *See* APIs
- fuser audit record, aa:245
- fw audit class, aa:104
- fw audit flag, aa:8, aa:94

G

- gateway host
 - defined, ao:85

- gateways
 - concepts, at:240, at:246
 - default, at:271
 - per network, at:271
- gen field, dg:206
- get_auth_text(3TSOL)
 - code example, dg:85
 - declaration, dg:82
- get_priv_text(3TSOL)
 - code example, dg:64
 - declaration, dg:62
- getaudit audit record, aa:177
- getaudit audit record, aa:177
- getcil(3TSOL)
 - code example, dg:115
 - declaration, dg:103
- getclearance system call
 - code example, dg:155
 - declaration, dg:152
- getcmwfsrange system call
 - declaration, dg:102
- getcmwfsrange(2TSOL)
 - code example, dg:121
- getcmwlabel system call
 - code example, dg:43, dg:118
 - declaration, dg:101
- getcmwplabel system call
 - code example, dg:43, dg:115
 - declaration, dg:101
- getcsl(3TSOL)
 - code example, dg:43, dg:115
 - declaration, dg:102
- getdents system call
 - restricting from returning upgraded names, at:356
- getfacl command
 - default profile, at:496, ao:152
- getfattrflag command
 - default profile, at:496, ao:152
 - described, at:321
 - identifying multilevel directories, at:50
 - overview, ao:121

getfattrflag system call
 code example, dg:35
 declaration, dg:27

getfile: RPC failed: error 5:
 RPC Timed out
 message, ic:153, ic:278

getfpriv command
 default profile, at:496, ao:152
 overview, ao:122
 using to save privileges, at:483

getfpriv system call
 code example, dg:67
 declaration, dg:60
 privileges needed, dg:55

getfpriv(1TSOL), dg:65

getfsattr command
 default profile, at:496, ao:152
 described, at:324
 overview, ao:125

getfsattr system call
 code example, dg:33
 declaration, dg:27

getlabel (1TSOL), dg:120

getlabel command
 default profile, at:496, ao:152
 overview, ao:122

getmldadorn command
 default profile, at:496, ao:152

getmldadorn system call
 code example, dg:175
 declaration, dg:173

getmsg audit record, aa:177
 socket accept, aa:178
 socket receive, aa:178

getmsgqcmwlabel audit
 record, aa:179

getmsgqcmwlabel system call,
 declaration, dg:228

getpattr system call
 code example, dg:37
 declaration, dg:27

getpmsg audit record, aa:179

getportaudit audit record, aa:180

getppriv system call
 code example, dg:41, dg:72, dg:74
 declaration, dg:60

getprofent(3TSOL),
 declaration, dg:210

getprofentbyname(3TSOL)
 code example, dg:212
 declaration, dg:210

getprofstr(3TSOL),
 declaration, dg:210

getprofstrbyname(3TSOL)
 code example, dg:212
 declaration, dg:210

getsemcmwlabel audit record, aa:180

getsemcmwlabel system call
 code example, dg:233
 declaration, dg:229

getshmcmwlabel audit record, aa:181

getshmcmwlabel system call
 code example, dg:235
 declaration, dg:230

getsldname command
 default profile, at:496, ao:152

getsldname system call
 code example, dg:45, dg:175
 creating SLDs, dg:168
 declaration, dg:172

getuserent(3TSOL)
 code example, dg:216
 declaration, dg:209

getuserentbyname(3TSOL)
 code example, dg:48, dg:212
 declaration, dg:209

getuserentbyuid(3TSOL),
 declaration, dg:209
getvfsaent(3TSOL), code
 example, dg:31
getvfsafile(3TSOL), code
 example, dg:31
GFI
 label encodings, la:3
gid field, dg:289
GIDs
 (group IDs)
 assigning, ao:65
 assigning to actions, ao:117
 assigning to commands, ao:117
 effective
 alternative to privileges, at:440
 defaults, at:460
 defined, at:438
 execution profiles, ao:38
 in execution profiles, at:195, ao:21
 network interfaces, ao:93
 privilege to change, dg:56
 process attributes, ao:42
 remote host templates, ao:90
 user attributes, ao:37
graphical user interfaces, *See* GUIs
Greenwich Meantime map, ic:280
grep command
 default profile, at:496, ao:152
group IDs
 assigning, at:102
group IDs, *See* GIDs
group names
 assigning, at:102
group token
 praudit display, aa:135
groupmgr command
 default profile, at:497, ao:153
groups
 ACL entry, ug:97
groups token
 described, aa:135

grpck command
 default profile, at:497, ao:153
GUIs
 (graphical user interfaces)
 See also builders, GUI
 CDE, dg:10
 Motif, dg:10
 Xlib, dg:10
 Xlib objects, dg:283

H

h_alloc(3TSOL)
 code example, dg:146, dg:165
 declaration, dg:108, dg:155
h_free(3TSOL)
 code example, dg:146, dg:165
 declaration, dg:108, dg:155
halt command
 default profile, at:497, ao:153
halt: machine halt audit
 record, aa:245
handling caveats
 printer banners, la:37
hands-off installation
 requirements, ic:118
hard disk space requirements, aa:21 to
 aa:22
hard disks
 copying Trusted Solaris CD to install
 server, ic:122
 interfaces supported, ic:38
 local disks in networked
 systems, ic:40
 partitioning
 designating for *partitioning*
 default, ic:163
 examples, ic:156 to ic:157
 excluding for *partitioning*
 default, ic:159
 profile keyword, ic:162
 rootdisk values, ic:160, ic:174 to ic:175
 size
 root space, ic:158

- rule keywords, ic:170, ic:173
- space available, ic:122
- swap space
 - diskless client, ic:158
 - maximum size, ic:163
 - networked systems, ic:40
 - profile examples, ic:156, ic:157
- hard string with audit_warn
 - script, aa:20
- hardware
 - disk space required, ic:39
 - frame buffers, ic:249
 - graphics accelerators, ic:249
 - input devices, ic:249
 - installation requirements, ic:38
 - multimedia, ic:250
 - platform names and groups by
 - system, ic:247 to ic:248
 - platforms supported, ic:38
 - printers, ic:250
 - SBus components, ic:248
 - supported, ic:247 to ic:250
 - video, ic:250
- head command
 - default profile, at:497, ao:153
- header field, dg:100
- header files
 - auditing APIs, dg:183
 - authorization APIs, dg:80
 - clearance APIs, dg:151
 - label APIs, dg:98
 - Label builder APIs, dg:310
 - locations, list of, dg:327
 - MLD APIs, dg:171
 - privilege APIs, dg:57
 - profile database access APIs, dg:206
 - RPC APIs, dg:274
 - SLD APIs, dg:171
 - System V IPC APIs, dg:228
 - TSIX APIs, dg:241
 - user database access APIs, dg:206
 - X Window System APIs, dg:288
- header token
 - described, aa:69, aa:71, aa:136
 - fields, aa:69, aa:71
 - format, aa:136
 - order in audit record, aa:68
 - praudit display, aa:69, aa:137
- header_len field, dg:100
- header_len field, dg:99
- Help menu item
 - described, ug:92
- hexadecimal
 - to binary, dg:142, dg:145
- hexadecimal label equivalents
 - determining, at:30
- hextoalabel command, dg:192
 - default profile, at:497, ao:153
 - overview, ao:132
- hide upgraded names, dg:29
- Home dialog box
 - User Manager, at:113 to at:115
- home directories
 - assigning, ao:73 to ao:74
 - mounting, ic:112
 - setup, ic:93, ic:111
 - sharing, ic:93 to ic:94, ic:111
- Host Manager
 - adding a host to a running
 - system, at:348
 - adding diskless clients, ic:204
 - adding hosts, ic:130, ic:135, ic:203
 - described, ic:120
- host token
 - described, aa:137
 - praudit display, aa:137
- host types
 - CIPSO, at:265
 - cipso, ao:87
 - MSIX, at:263
 - msix, ao:87
 - networking, at:255 to at:270, ao:85
 - remote host templates, ao:90
 - RIPSO, at:267
 - ripso, ao:87
 - sun_tsol, at:257, ao:86
 - TSIX, at:260

tsix, ao:87
 unlabeled, at:269, ao:86
hostaddress rule keyword, ic:170
hostid command
 default profile, at:497, ao:153
hostname command
 default profile, at:497, ao:153
hostname rule keyword
 description and values, ic:170
 example, ic:168
 hosts
 adding for network Trusted Solaris
 installation, ic:130
 assigning templates, at:282 to at:286
 installing, ic:80 to ic:83
 installing local hosts, ic:79 to ic:80
 installing templates, ic:80 to ic:82
 networking concepts, at:235, at:246
 worksheet, at:485
 HSFS
 mounting in Trusted Solaris, at:328
htobcl(3TSOL)
 code example, dg:145
 declaration, dg:109
htobclear(3TSOL)
 code example, dg:164
 declaration, dg:155
htobil(3TSOL), declaration, dg:109
htobs1(3TSOL), declaration, dg:109
 human-readable audit record format
 converting audit records to, aa:76 to
 aa:82
 described, aa:67

I

I/O interrupt error messages, ic:120
iaddr field, dg:289
 icons
 for Application Manager, ic:76
 for device allocation, ic:75
 for Solstice_Apps actions, ic:79
 for System_Admin actions, ic:78
 using to launch actions, ic:72
 visibility
 in the File Manager, at:444
 in the Workspace Menu, at:444
id command
 default profile, at:497, ao:153
 identification
 defined, ug:18
 procedure, ug:20 to ug:21
 identification and authentication
 See also administrative roles,
 assuming
 before assuming a role, at:5
 Identity dialog box
 User Manager, at:102
 Idle dialog box
 User Manager, at:122, at:123
 idle time
 assigning, ao:81 to ao:82
idlecmd field, dg:206
idletime field, dg:206
 IDs
 See also audit IDs
 See also GIDs
 See also UIDs
 audit, aa:3, aa:17, aa:70
 audit session, aa:17, aa:70
 audit user, aa:70
 terminal, aa:17
ifconfig command
 Trusted Solaris modifications, ao:101
iil field, dg:289
 IILs
 (input information labels)
 defined, ug:85
 described, dg:285
 security policy, dg:285
 setting, la:17
 INET Domain sockets
 (Internet Domain sockets)
il field, dg:289
ilabel field, dg:100
ilabel token
 described, aa:137

praudit display, aa:138
 ilabel_len field, dg:99, dg:100
 ILs
 (information labels)
 See also CMW labels
 See also code examples
 See also labels
 See also SLs
 See also translation
 API declarations, dg:344
 changing file ILs, ug:108 to ug:110
 changing input ILs, ug:85 to ug:87
 in CMW label, dg:88
 components, dg:89
 conjoin, defined, dg:90
 Customize Trusted Solaris
 Configuration dialog
 box, la:31
 deciding whether to allow
 floating, la:33
 deciding whether to reset when a new
 command is executed, la:33
 deciding whether to use, la:32
 defined, ug:8, ao:2
 described, at:310
 determining by window query, ug:84
 determining with File
 Manager, ug:108
 DIA requirement, la:17
 displaying and hiding, at:117 to
 at:119
 dominate, dg:125
 enabling, dg:28
 enabling floating, dg:28
 enabling floating system-wide, la:32
 enabling message floating, dg:28
 enabling semaphore set
 floating, dg:28
 enabling shared memory
 floating, dg:28
 enabling system-wide, la:32
 equal, dg:125
 file systems, ao:124
 floating, ug:9
 algorithms, dg:90
 cases when it occurs, la:17
 described, at:311
 guidelines, dg:97
 object CMW label, dg:92
 process CMW label, dg:91
 stopping, dg:94
 System V IPC objects, dg:227
 TSIX, dg:239
 X Window, dg:288
 initial setting on an empty
 object, la:16
 label overview, ao:4, ao:16
 length of component fields, la:8
 limits on floating, la:17
 on banner and trailer pages, la:80
 privileges
 changing process IL, dg:93
 downgrading ILs, dg:94
 upgrading ILs, dg:94
 purpose, dg:87
 remote host templates, ao:90
 resetting on exec, la:32, dg:29
 setting an input IL, la:17
 setting user and role accounts
 locally, la:34
 site implementation example, la:129
 to la:133
 TSIX, dg:240
 uses
 controlling information
 distribution, la:17
 visibility, ao:76
 in.ftpd audit record, aa:246
 in.ftpd command
 default profile, at:497, ao:153
 in.named command
 default profiles, at:497, ao:153
 in.rexecd audit record, aa:253
 in.rexecd command
 default profile, at:497, ao:153
 in.rlogind command
 default profile, at:497, ao:153
 in.rshd command
 default profile, at:497, ao:153

in.rshd: rshd access
 denials/grants audit
 record, aa:254

in.telnetd command
 default profile, at:497, ao:153

in.tftpd command
 default profile, at:497, ao:153

in_addr token
 described, aa:138
 praudit display, aa:138

include files, *See* header files

INET Domain sockets, *See* IPC

inetd command
 default profile, at:497, ao:153

inetd: inetd service request
 audit record, aa:246

information label float audit
 record, aa:181

INFORMATION LABELS section
 label_encodings example, la:154

information labels, *See* ILS

inheritable privileges, at:450
 See also privilege sets
 assigning, ao:29
 code example, dg:74
 defined, dg:53, ao:27
 execution profiles, ao:38

init audit record
 run level change
 information, aa:255

init command
 default profile, at:497, ao:153

init.d directory
 starting commands during
 boot, at:457

initial compartments
 classification keyword, la:54

initial markings
 classification keyword, la:54

initialization files
 Trusted Solaris differences, at:65

Input IL field
 described, ug:70

input information labels, *See* IILs

install server
 copying Trusted Solaris CD to local
 disk, ic:120, ic:122
 creating, ic:122
 described, ic:116
 requirement for network
 installation, ic:116

install team, ic:5, la:1

install user
 deleting, ic:68

install_config command, ic:152 to
 ic:153

install_type profile keyword
 description and values, ic:161
 examples, ic:156
 requirement, ic:154, ic:156
 testing profiles, ic:188 to ic:190

installation
 adding software, at:463
 boot commands, ic:57
 disk space requirements, ic:39
 using DNS, ic:88
 interactive, ic:114
 manual reboot, ic:60
 memory requirements, ic:38
 networked workstations
 config_data file, ic:126
 division of tasks, ic:55
 setting date and time, ic:128
 NIS+ clients, ic:105 to ic:114
 NIS+ root master, ic:69 to ic:104
 over networks, ic:115 to ic:138
 overview, ic:6
 planning, ic:16 to ic:53
 planning auditing, ic:23 to ic:27
 planning clearances, ic:18 to ic:23
 planning first two users, ic:48
 planning hardware, ic:38
 planning labels, ic:18 to ic:23
 planning network interface
 security, ic:46

- planning NIS+ domain, ic:34, ic:41 to ic:44
 - planning passwords, ic:45
 - planning workstation security, ic:44
 - role division, ic:17
 - root password creation, ic:60
 - system type choices, ic:40
 - understanding security, ic:16
- installed* rule keyword
 - description and values, ic:170
 - rootdisk* matching, ic:174
- integrating an application, dg:331
- interactive installation
 - booting the system, ic:56
 - CDROM drive preparation, ic:56
 - CDROM task map, ic:9
 - JumpStart diskette installation task map, ic:12
 - networked workstations, ic:55 to ic:60
 - NIS+ rootmaster, ic:69 to ic:104
- interfaces, *See* APIs
- internationalization
 - changing banner/trailer pages, la:37
 - changing printer output, at:372, la:75
- Internet Domain sockets, *See* INET Domain sockets
- Internet Protocol, *See* IP
- Internet-related tokens
 - socket token, aa:149
- interprocess communication, *See* IPC
- inter-window movement
 - window privileges, ao:28
- io audit class, aa:100, aa:104
- io audit flag, aa:9, aa:94
- ioctl audit class, aa:9
- ioctl system calls, aa:9
- ioctl: ioctl to special devices audit record, aa:183
- IP
 - (Internet Protocol)
- IP addresses
 - rule keyword, ic:170
 - tnrddb database, ao:88
- ip audit class, aa:105
- ip audit flag, aa:9, aa:94
- IP labels
 - remote host templates, ao:90
- IP Options field
 - Trusted Solaris data packets, ao:86
 - use, at:249
- ip token
 - described, aa:139
- IPC
 - (interprocess communication)
 - See also* communication endpoints
 - See also* RPC
 - See also* System V IPC
 - See also* TLI
 - See also* TSIX library
 - See also* X Window System communication endpoint objects, dg:4
 - file binding, dg:4
 - mechanisms described, dg:217
 - multilevel port connections, dg:222
 - network accreditation range, dg:238
 - objects, dg:4
 - polyinstantiated ports, dg:223
 - port binding, dg:4
 - privileges, ao:28
 - privileges, defined, dg:51
 - security attributes
 - changing, dg:239
 - contrast with Solaris, dg:12
 - described, dg:238
 - security policy, dg:16, dg:217
 - single-level port connections, dg:222
- ipc audit class, aa:9
- ipc token, aa:139 to aa:140
 - described, aa:132, aa:139
 - praudit display, aa:140

ipc type field values (ipc token), aa:140
ipc_dac_read privilege, dg:226
ipc_dac_write privilege, dg:226
ipc_downgrade_il privilege, dg:227
ipc_mac_rad privilege, dg:226
ipc_mac_read privilege, dg:217,
dg:226
ipc_mac_write privilege, dg:226
ipc_nofloat privilege, dg:217, dg:227
ipc_owner privilege, dg:217, dg:226
ipc_perm token
described, aa:140
praudit display, aa:141
ipc_upgrade_il privilege, dg:227
ipcrm command
Trusted Solaris modifications, ao:101
ipcs command
Trusted Solaris modifications, ao:102
IPI interface, ic:38
iport token
described, aa:141
praudit display, aa:141
item size field values (arbitrary
token), aa:130

J

join command
default profile, at:497, ao:153
JumpStart directory
adding files with finish scripts, ic:184,
ic:185
copying files
disk configuration files, ic:192
installation files from CD, ic:148,
ic:151
using finish scripts, ic:185
creating, ic:142
diskette for SPARC
systems, ic:146 to ic:148
example, ic:252
server, ic:149 to ic:151

install server setup, ic:179
permissions, ic:146, ic:149
rules file example, ic:164
sharing, ic:149 to ic:151, ic:253

JumpStart installation
diskette task map, ic:12
network task map, ic:11

K

karch rule keyword, ic:171
kernel events
audit number range, aa:6
audit records, aa:157 to aa:235
audit tokens, aa:68
auditconfig command
options, aa:24
described, aa:6
kernel switches
configurable, at:354
keywords, la:53
kill audit record, aa:184
kill command
default profile, at:497, ao:153
kmem(7D) kernel image file, at:463
ksh command
default profile, at:497, ao:153

L

Label builder
Cancel pushbutton, dg:315
declarations, dg:310
described, dg:309
Downgrade SL Using IL
pushbutton, dg:315
extended operations, dg:317
functionality, dg:314
IL radio button, dg:315
Reset pushbutton, dg:315
SL radio button, dg:315
label builder
See also code examples
changing component names, la:103

- label clipping
 - API declarations, dg:297, dg:346
 - translating with font list, dg:300
- label configuration
 - file location, ic:21
 - planning, ic:18 to ic:22
 - settings, ic:21
- label data types
 - accreditation ranges, dg:99
 - banner fields, dg:100
 - CMW label structure, dg:98
 - information labels, dg:98
 - label information, dg:99
 - levels, dg:99
 - sensitivity labels, dg:98
 - setting flags, dg:98
 - SL ranges, dg:99
- label encodings file
 - checking, ic:74
 - copying, ic:103
 - modifying, ic:74 to ic:77
 - other file constraints, ao:9
 - overview, ao:5 to ao:6
 - planning, ic:18 to ic:22
- label ranges
 - accreditation, dg:99, dg:131
 - actions, ao:38
 - assigning, dg:91
 - assigning to devices, ao:32
 - checking, dg:122
 - commands, ao:38
 - defined, ao:6
 - described, at:311, dg:121
 - devices, at:414, ao:138
 - in execution profiles, ao:21
 - file systems
 - API declarations, dg:342
 - data structure, dg:99
 - overview, la:6
 - See also* accreditation ranges
 - setting on individual
 - computers, at:413
- label translation, la:13
- label view
 - hierarchy of settings, la:24
 - process flag, la:27
 - setting in label_encodings
 - file, la:24
- label_encodings file
 - access-related words, la:76
 - adding to a government-supplied
 - encodings, la:3
 - API declarations, dg:342
 - changing after system start-up, la:51
 - changing classifications, la:53
 - checking, la:47
 - classification keywords, la:53
 - color names, dg:134
 - copying to client, ic:106
 - distributing changes, at:361, at:362,
 - la:115 to la:125
 - encoding example, la:139 to la:151
 - government-supplied, la:61
 - hints for managing, la:48
 - information on, dg:135
 - introduction, la:1
 - Label builder, dg:314
 - label translation flag, dg:39
 - LOCAL DEFINITIONS
 - section, la:100 to la:101
 - modifying, ic:63
 - multiple sensitivity labels, la:49
 - Non-English, dg:300
 - optional flags, la:103
 - placeholder files, la:48, la:54
 - planning example, la:127 to la:166
 - preparing, la:45 to la:46
 - procedures
 - assigning colors to labels or
 - words, la:111
 - changing administrative
 - labels, la:108
 - changing classifications, la:62
 - changing component names in
 - label builder, la:111
 - changing single-label
 - default, la:65
 - configuring channels, la:96
 - configuring printers, la:95
 - creating single-label file, la:67

displaying administrative label names, la:109
 displaying administrative label substitutes, la:109
 distributing label information, la:119
 distributing label information changes, la:124
 hiding labels, la:68
 modifying, la:60
 printing without banners and trailers, at:397
 printing without labeled pages, at:379, at:399
 printing without page labels, at:398
 running without labels, la:61
 specifying default and inverse words, la:64
 specifying default flags, la:110
 specifying forced flags, la:110
 protect as classification, la:76
 retrieving version string, dg:112
 running without labels, la:51
 sample listing, la:169 to la:177
 sections, la:52
 single sensitivity labels, la:50
 single- vs multilabel, la:49
 site-specific, la:4
 specifying label colors, la:105 to la:113
 Sun extensions to GFI encodings, la:3
 valid clearances, dg:152
 valid labels, dg:100
 view flag, dg:39
 label_info structure, dg:99
 labelinfo(3TSOL)
 code example, dg:135
 declaration, dg:106
 labelmax field, dg:206
 labelmin field, dg:206
 labels
 See also clearances
 See also CMW labels
 See also ILs
 See also SLs
 See also translation
 acquiring, dg:91
 administrative, dg:113
 advisory, la:13
 API declarations
 CMW labels, dg:345
 entire, dg:100 to dg:109, dg:342 to dg:346
 file systems, dg:342
 ILs, dg:344
 label clipping with font list, dg:346
 label types, dg:343
 label_
 encodings(4TSOL), dg:342
 levels, dg:343
 reentrant routines, dg:343
 SLs, dg:344
 assigning to accounts, ao:75 to ao:77
 assigning to files, ao:119
 authorizations, dg:80, ao:26
 avoiding abbreviations and acronyms, la:16
 changing on files and directories, at:336
 checking validity, ao:131
 classification component, ao:4
 classification field length, la:7
 color planning example, la:150
 compartment component, ao:4
 components
 arranging the relationships, la:40
 configuration choices, ic:19
 configuring, the big picture, la:29
 converting to ASCII, ao:132
 converting to hex, ao:131
 default Label View, la:101
 defined, dg:87
 described, at:311
 displayed in Trusted Solaris environment, ug:65 to ug:68
 displaying, at:117 to at:119
 distributing changes, at:361 to at:362, la:115 to la:125

dominance, ug:6, la:12, ao:4
 dominate levels, dg:123
 downgrading, la:20
 downgrading of SLs based on
 ILs, la:17
 equal levels, dg:123
 guidelines, dg:94
 how used in MAC, la:5
 ILs on printer output, la:19
 installation example, ic:261, la:151 to
 la:165
 Label builder, dg:309
 markings, ao:4
 minimum number of SLs, la:2
 minimum protect as
 classification, la:76
 on archived information
 physical, la:18
 on e-mail, la:18
 on imported and exported
 data, at:411
 overview, ao:4 to ao:16
 physical, on removable media, at:403
 planning, ic:18 to ic:23
 planning example, la:127 to la:166
 printed body pages, at:368, la:72
 privileged tasks, dg:93
 privileges for overriding, ao:28
 procedures
 changing system file
 information, la:123
 reentrant routines, dg:108, dg:109
 relationships, ug:6, dg:123, ao:4
 required types defined at each
 site, la:37
 result of configuration choice, ic:21
 running without labels, la:2
 site analysis example, la:134 to la:138
 specifying colors, la:105 to la:113
 strictly dominate levels, dg:124
 translation flag, dg:39
 Trusted Solaris commands, ao:131 to
 ao:132
 types that must be specified, la:37
 undefined, dg:113
 valid, dg:100
 view, dg:137
 setting default label view, la:24
 view flag, dg:39
 view settings
 hierarchy, la:24
 visibility, ic:21
 setting on user and role
 accounts, la:34
 visibility of components, la:15
 well-formed, ao:6
 where configuration choices
 stored, ic:21
 worksheet examples, la:144 to la:151
 Labels dialog box
 User Manager, at:116, at:119
 labeltrans field, dg:206
 labelvers(3TSOL)
 code example, dg:112
 declaration, dg:106

labelview field, dg:206
 LBUILD_CHECK_AR operation, dg:319
 LBUILD_LOWER_BOUND operation, dg:319
 LBUILD_MODE operation, dg:317
 LBUILD_MODE_CLR value, dg:317
 LBUILD_MODE_CMW value, dg:317
 LBUILD_MODE_IL value, dg:317
 LBUILD_MODE_SL value, dg:317
 LBUILD_SHOW operation, dg:318
 LBUILD_TITLE operation, dg:318
 LBUILD_UPPER_BOUND operation, dg:319
 LBUILD_USERFIELD operation, dg:318
 LBUILD_VALUE_CLR operation, dg:318
 LBUILD_VALUE_CMW operation, dg:317
 LBUILD_VALUE_IL operation, dg:317
 LBUILD_VALUE_SL operation, dg:317
 LBUILD_VIEW operation, dg:319
 LBUILD_VIEW_EXTERNAL value, dg:319
 LBUILD_VIEW_INTERNAL value, dg:319
 LBUILD_WORK_CMW operation, dg:318
 LBUILD_WORK_IL operation, dg:318
 LBUILD_WORK_SL operation, dg:318
 LBUILD_WORKJ_CLR operation, dg:318
 LBUILD_X operation, dg:318
 LBUILD_Y operation, dg:319
 lchown audit record, aa:184
 LD_LIBRARY_PATH, dg:326
 ldd command
 default profile, at:497, at:498, ao:153
 to ao:154
 levels
 defined, dg:123, dg:158
 relationship, dg:123
 relationships, dg:158
 See also labels
 translating IL, dg:128
 upper and lower bounds, dg:130,
 dg:160
 lgetcmwlabel system call,
 declaration, dg:101
 liaison token
 described, aa:141
 praudit display, aa:142
 libraries, C functions, aa:263
 libraries, compile
 auditing APIs, dg:183
 authorization APIs, dg:80
 clearance APIs, dg:151
 label APIs, dg:98
 Label builder APIs, dg:310
 MLD APIs, dg:171
 privilege APIs, dg:57
 profile database access APIs, dg:206
 RPC APIs, dg:274
 SLD APIs, dg:171
 System V IPC APIs, dg:228
 trusted shared libraries, dg:326
 TSIX APIs, dg:241
 user database access APIs, dg:206
 X Window System APIs, dg:288
 library routines
 API declarations, dg:356
 security policy on man pages, dg:325
 libt6(3NTSOL), at:76
 link audit record, aa:185
 .link_files file
 described, ug:114
 using, at:70
 linking
 system privileges, ao:28
 list_devices command
 default profile, at:498, ao:154
 Trusted Solaris modifications, ao:135
 ln command
 default profile, at:498, ao:154
 lo audit class, aa:106
 lo audit flag, aa:9, aa:94
 loadable modules
 system privileges, ao:28
 LOCAL DEFINITIONS section
 label_encodings example, la:162

label_encodings file, la:3, la:100
 to la:101

local file systems

- creating, ic:160 to ic:161

local.login file

- defining printers, at:399

Lock control, ug:92

lock control, ug:30 to ug:31

lock field, dg:206

lock files

- for allocatable devices, at:412

lock screen

- specifying after idle time, ao:81

LOFS

- mounting in Trusted Solaris, at:328

log files

- begin scripts output, ic:182
- finish scripts output, ic:184
- installation output, ic:59
- security violation from
 - sharing, at:463

logical AND rule field, ic:166

.login file, at:114

login

- as user during configuration, ic:113
- authorizations, ao:25
- by administrative roles, at:4 to at:5
- disabled, ug:32
- enabling, ug:32 to ug:34
- example, ug:36 to ug:37
- failsafe, ug:34
- fixing initialization problems, ug:34
- procedure, ug:18 to ug:29

login audit record

- logout, aa:248
- rlogin, aa:247
- telnet login, aa:247
- terminal login, aa:247

login authorizations, defined, dg:80

login record

- praudit display, aa:70

login sequence, at:6

login shells

- assigning, ao:66

login/logout messages, copying to single
 file, aa:79

login_logout audit class, aa:9

logout

- procedure, ug:31 to ug:32
- specifying after idle time, ao:81

LONG_CLASSIFICATION flag, dg:137

LONG_WORDS flag, dg:137

look command

- default profile, at:498, ao:154

lp command

- default profile, at:498, ao:154

lpadmin command

- modified for Trusted Solaris, at:382
- default profile, at:498, ao:154

lpc command

- modified for Trusted Solaris, at:382

lpfilter command

- default profile, at:498, ao:154

lpmove command

- modified for Trusted Solaris, at:382
- default profile, at:498, ao:154

lpr command

- modified for Trusted Solaris, at:382

lprm command

- modified for Trusted Solaris, at:382

lpsched command

- modified for Trusted Solaris, at:382
- default profile, at:498, ao:154

lpshut command

- modified for Trusted Solaris, at:382
- default profile, at:498, ao:154

lpstat command

- modified for Trusted Solaris, at:382
- default profile, at:498, ao:154

lpssystem command

- modified for Trusted Solaris, at:382
- default profile, at:498, ao:154

`lpctest` command
 modified for Trusted Solaris, at:382
`lpusers` command
 default profile, at:498, ao:154
`ls` command
 default profile, at:498, ao:154
`lsetcmwlabel` system call,
 declaration, dg:101
`lstat` audit record, aa:185
`lxstat` audit record, aa:186

M

MAC
 (mandatory access control)
See also security policy
 accessing System V IPC
 objects, dg:226
 audit records, aa:235
 bypassing restrictions, at:439
 cautions about override
 privileges, at:462
 clearance limits, dg:13
 comparing labels, la:5
 defined, ug:5, ao:2
 described, at:311
 file access, ao:34
 guidelines for bypassing, dg:95
 incoming packets, at:253
 labels, la:1
 outgoing packets, at:252
 override privileges, at:439
 privilege bracketing, dg:69
 security policy, dg:13
 SL limits, dg:13, dg:87
 MAC check audit record, aa:235
 machine halt audit record, aa:245
 machine reboot audit record, aa:252
 macros, *See* privilege macros
 mail
 aliases, at:164 to at:167
 creating `audit_warn` alias, aa:52
 differences in Trusted Solaris, ug:73
 listing mail queues, at:167
 managing, at:157 to at:189
 messages, policy for access to, at:306
 options, at:176 to at:179
 overview, at:158 to at:164
 switching mail tools, at:180 to at:189
 troubleshooting, at:171 to at:176
 mail accounts, ic:210
`mailq` command
 default profile, at:498, ao:154
 `.mailrc` file, at:68
 maintenance commands, aa:261
`man` command
 default profile, at:498, ao:154
 man pages, ic:156
 ERRORS sections, at:439
 mandatory access control, *See* MAC
 manual pages
 modified, dg:324
 requesting, dg:324
 security policy on, dg:325
 mapped memory, access checks, dg:220
 mappings
 multilevel, dg:272
 single-level, dg:272
`marketing_profile` example, ic:254
 markings
 defined, ug:8
 described, at:312
 dominate, dg:127
 equal, dg:127
 field length, la:8
 planning example, la:140
 worksheet example, la:147
 markings label component
 defined, ao:4
 mask, process preselection
 C library functions, aa:263
 described, aa:16
 reducing storage costs, aa:22 to aa:23
 masks
 See also process preselection mask
 See also TSIX library

ACL entry, ug:97

matching

- derived profiles, ic:182
- order for rules, ic:164, ic:167
- rootdisk* values, ic:174 to ic:175

max field, dg:208

maximum SL

- remote host templates, ao:90

media labeling

- clean scripts, ao:137

memcntl audit record, aa:186

memory

- displaying amount installed, ic:120
- minimum required, ic:38
- rule keyword, ic:168, ic:171
- setting size, ic:189
- swap space size and, ic:163
- virtual, ic:38

memsize rule keyword

- description and values, ic:171
- example, ic:168

Message of the Day dialog box

- example, ug:37 to ug:38
- introduction, ug:18
- procedure, ug:22 to ug:25

message queues

- See also* code examples
- See also* System V IPC
- API declarations, dg:228, dg:349
- IL floating, dg:227
- overriding restrictions, ao:28
- system privileges, ao:28

microprocessors

- rule keywords, ic:169

min field, dg:208

minfree: line in *audit_control* file

- audit_warn* condition, aa:20
- described, aa:13

minfree: line in *audit_control* file

- audit_warn* condition, aa:19

minimum clearance

- label encodings file, ao:9

minimum labels

- assigning, at:116

minimum protect as classification, la:76

- example, la:76

minimum sensitivity labels

- account label range, ao:10

minimum SLs, la:5

- assigning to users, ao:76
- described, at:312
- equal to clearance on a multiple-SL system, la:10
- equal to clearance on a single-SL system, la:9
- remote host templates, ao:90
- user attributes, ao:37
- worksheet example, la:150

minus (-) audit flag prefix, aa:10, aa:146, aa:147

minus sign (-)

- in begin and finish scripts, ic:196
- in rules, ic:169

mkdir audit record, aa:187

mkdir command

- default profile, at:498, ao:154
- default profiles, at:498, ao:154

mkfile command

- default profile, at:498, ao:154

mkfs command

- default profile, at:498, at:499, ao:154, ao:155

mknod audit record, aa:187

mldgetcwd(3TSOL)

- code example, dg:176
- declaration, dg:174

mldgetfattrflag system call

- code example, dg:35
- declaration, dg:27

mldpwd command

- default profile, at:499, ao:155

mldrealpath command

- default profile, at:499, ao:155
- identifying multilevel directories, at:50

mldrealpath(3TSOL)
 code example, dg:176
 declaration, dg:174
 mldrealpath1(3TSOL),
 declaration, dg:174
 MLDs
 (multilevel directories)
 See also code examples
 See also SLDs
 accessing, dg:168
 adorned names, dg:170
 API declarations, dg:172 to dg:174,
 dg:348
 backing up, at:51
 creating, dg:168
 defined, ug:11
 described, at:313, dg:167
 example, ug:51 to ug:53
 file systems, ao:124
 identifying, at:50
 information structure, dg:172
 prefix on file systems, dg:34
 privileged tasks, dg:171
 querying MLD flag, dg:35
 security attribute flags, dg:35
 security policy, dg:168
 structure, dg:168
 symbolic links, dg:169
 used by applications, dg:169
 working with, at:43 to at:53
 mldsetfattrflag system call
 code example, dg:35
 declaration, dg:27
 mldstat system call
 code example, dg:177
 declaration, dg:173
 mmap audit record, aa:188
 modctl audit record
 MODADDMAJBIND
 command, aa:188
 MODCONFIG command, aa:189
 MODLOAD command, aa:189
 MODUNLOAD command, aa:190
 model name, ic:120
model rule keyword
 description and values, ic:172
 example, ic:168
 modify at admin authorization, at:78
 modify at user authorization, at:79
 modify cron admin authorization, at:79
 modify cron user authorization, at:79
 ModLabelData structure, dg:320
 modload audit record, aa:248
 modunload audit record, aa:249
 monitoring audit trail in real time, aa:22
 more command
 default profile, at:499, ao:155
 Most, aa:42
 Motif application
 described, dg:298
 Label builder widgets, dg:320
 online help, dg:321
 source code, dg:303 to dg:307
 Motif, described, dg:10
 mount command
 nodevices option
 controlling location of
 devices, at:407
 mount audit record, aa:190
 mount command, ic:120, ic:147
 default profile, at:499, ao:155
 Trusted Solaris modifications, ao:126
 mount points
 creating, ic:101
 mount_hfs command
 Trusted Solaris modifications, ao:126
 mount_nfs command
 Trusted Solaris modifications, ao:127
 mount_tmpfs command
 Trusted Solaris modifications, ao:127
 mount_ufs command
 Trusted Solaris modifications, ao:126
 mountall command
 default profile, at:499, ao:155

mountd audit record
 NFS mount request, aa:249
 NFS unmount request, aa:250
 mountd command
 Trusted Solaris modifications, ao:126
 mounting
 begin script caution, ic:182
 defined for Trusted Solaris, ao:95
 diskettes, ic:147
 displaying mounted file systems, ic:120
 overview, ao:99 to ao:100
 Trusted Solaris CD, ic:136, ic:148, ic:151
 Trusted Solaris differences, ao:125, ao:128
 by Trusted Solaris installation, ic:184
 unlabeled file systems, ic:100
 mounts
 managing, at:303 to at:344
 permitted file systems, at:327
 procedure for TMPFS, at:343
 troubleshooting, at:344
 msgctl audit record
 IPC_RMID command, aa:191
 IPC_SET command, aa:192
 IPC_STAT command, aa:193
 msgget audit record, aa:193
 msggetl audit record, aa:194
 msggetl system call
 code example, dg:230
 declaration, dg:228
 msgrcv audit record, aa:195
 msgrcvl audit record, aa:195
 msgrcvl system call
 code example, dg:232
 declaration, dg:228
 msgsnd audit record, aa:195, aa:196
 msgsndl system call
 code example, dg:230
 declaration, dg:228
 MSIX host type
 defined, ao:87
 described, at:263
 mt command
 default profile, at:499, ao:155
 MT_SAFE, dg:146, dg:165
 multilabel file systems, dg:121
 multilevel directories, *See* MLDs
 multilevel mappings, dg:272
 multilevel port bindings
 network privileges, ao:28
 multilevel ports
 contrast to polyinstantiated, dg:223
 described, dg:222
 example application, dg:258
 replying at equal SL, dg:239
 RPC, dg:272
 multilevel sessions
 defined, ug:10
 multiple disk configuration file
 SPARC systems, ic:194 to ic:196
 multiple lines in rules, ic:169
 munmap audit record, aa:196
 mv command
 default profile, at:499, ao:155

N
 na audit flag, aa:8, aa:94
 naflags: line in audit_control file, aa:12
name
 classification keyword, la:53
 name field, dg:206, dg:207
 NAME INFORMATION LABELS section
 label_encodings example, la:162
 name server, ic:116
 names
 audit classes, aa:8
 audit files
 closed files, aa:73
 form, aa:72
 still-active files, aa:73

- time stamps, aa:72
 - use, aa:72
- audit flags, aa:8
- audited kernel events, aa:6
- IDs
 - audit, aa:3, aa:17
 - audit session, aa:17, aa:70
 - terminal, aa:17
- mount-point path names on audit servers, aa:11
- names, abbreviations, dg:327
- names/naming
 - derived profile names, ic:183
 - host name, ic:170
 - profile names, ic:154
 - rules file, ic:165, ic:168
 - software group cluster names, ic:159
 - system model names, ic:172
 - system platform name determination, ic:247
- ncheck command
 - default profile, at:499, ao:155
- ndd command
 - overview, ao:138
 - Trusted Solaris modifications, ao:103
- net_downgrade_il privilege, dg:240
- net_downgrade_sl privilege, dg:240
- net_mac_read privilege, dg:222
- net_nofloat privilege, dg:217, dg:239
- net_reply_equal privilege, dg:239, dg:260
- net_setclr privilege, dg:240
- net_setid privilege, dg:240
- net_setpriv privilege, dg:241
- net_upgrade_il privilege, dg:217, dg:240
- .netscape file, at:68
- netstat command
 - default profile, at:499, ao:155
 - Trusted Solaris modifications, ao:102
- network accreditation range
 - example, at:279
- network accreditation ranges
 - described, at:237
 - requirements, at:239
 - setting up, at:290
- network audit class, aa:9
- network installation
 - custom JumpStart installation example, ic:145
 - diskless booting task map, ic:13
 - hands-off configuration, ic:119
 - JumpStart installation task map, ic:11
 - modifying files on the client, ic:109
 - preparation, ic:115, ic:138
 - task map, ic:10
- network interfaces
 - configuring, at:291 to at:296
 - default security attributes, ic:46
 - defined, ao:84
 - described, at:237
 - planning security, ic:46
 - requirements, at:239
 - tnidb(4TSOL), ao:93
- network rule keyword
 - description and values, ic:173
 - example, ic:168
- network security
 - open versus closed, ic:28
 - planning, ic:27
 - unlabeled host defaults, ic:31
- networked workstations
 - choosing system type, ic:40
 - planning space, aa:33
- networking
 - concepts, at:235 to at:246
- networks
 - See also* IPC
 - default labeling, at:253 to at:279
 - example, ao:97 to ao:98
 - fallback mechanism, at:274
 - modified Solaris commands, ao:100 to ao:103
 - overview, ao:83 to ao:106
 - privileges, ao:28

procedures for configuring, at:280 to at:302
 remote host templates, ao:90
 security attributes, at:248 to at:279, dg:12
 Trusted Solaris commands, ao:103 to ao:106
 using templates, at:273
 never-audit flags, aa:15 to aa:16
 NEW_LABEL flag, dg:142
 newaliases command
 default profile, at:499, ao:155
 newfs command
 default profile, at:499, ao:155
 newgroups token
 described, aa:142
 praudit display, aa:142
 newkey command
 default profile, at:499, ao:155
 newsecfs command
 default profile, at:499, ao:155
 overview, ao:125
 newsecfs command)
 described, at:324
 .newsrc file, at:68
 NFS
 mounting in Trusted Solaris, at:328
 NFS mount request audit
 record, aa:249
 NFS unmount request audit
 record, aa:250
 nfsd command
 Trusted Solaris modifications, ao:128
 nfsstat command
 Trusted Solaris modifications, ao:128
 nice audit record, aa:197
 nice command
 default profile, at:499, ao:155
 NIS+
 configuration files not administered, at:347
 tables
 adding protected data, at:348
 new in Trusted Solaris, at:347
 NIS+ client host
 adding to a running system, at:348
 NIS+ credentials
 Password dialog box, ao:72
 NIS+ domain
 client setup, ic:111
 configuring root master, ic:69 to ic:104
 planning, ic:33
 planning root master, ic:41
 setup, ic:87
 NIS+, managing, at:345 to at:348
 nisaddcred command
 default profile, at:499, ao:155
 nisaddent command
 default profile, at:499, ao:155
 niscat command
 default profile, at:499, ao:155
 nischgrp command
 default profile, at:499, ao:155
 nischmod command
 default profile, at:500, ao:156
 nischown command
 default profile, at:500, ao:156
 nischttl command
 default profile, at:500, ao:156
 nisclient command
 default profile, at:500, ao:156
 nisctl command
 default profile, at:500, ao:156
 nisdefaults command
 default profile, at:500, ao:156
 niserror command
 default profile, at:500, ao:156
 nisgrep command
 default profile, at:500, ao:156
 nisgrpadm command
 default profile, at:500, ao:156
 nisinit command
 default profile, at:500, ao:156

`nisl` command
 default profile, at:500, ao:156

`nislog` command
 default profile, at:500, ao:156

`nismatch` command
 default profile, at:500, ao:156

`nismkdir` command
 default profile, at:500, ao:156

`nispaswd` command
 default profile, at:500, ao:156

`nisping` command
 default profile, at:500, ao:156

`nispopulate` command
 default profile, at:500, ao:156

`nism` command
 default profile, at:500, ao:156

`nismdir` command
 default profile, at:500, ao:156

`niss` command
 default profile, at:500, ao:156

`nissetup` command
 default profile, at:500, ao:156

`nisshowcache` command
 default profile, at:500, ao:156

`nisstat` command
 default profile, at:500, ao:156

`nistbladm` command
 default profile, at:500, ao:156

`nistest` command
 default profile, at:500, ao:156

`nistnsetup` command
 default profile, at:500, ao:156

`nistntime` command
 default profile, at:500, ao:156

`nisupdkeys` command
 default profile, at:501, ao:157

`no audit class`, aa:108

`no audit flag`, aa:8, aa:94

`no_class` audit class, aa:8

`NO_CLASSIFICATION` flag, dg:137

`NO_CORRECTION` flag, dg:142

`non_attr` audit class, aa:8

non-administrative roles
 defined, ao:24
 described, at:88, at:89

nonattributable flags in `audit_control`
 file, aa:12

non-networked workstations
 planning space, aa:33

`nr` command
 default profile, at:501, ao:157

`nscd` command
 default profiles, at:501, ao:157

`nt` audit class, aa:109

`nt` audit flag, aa:9, aa:94

`null` audit class, aa:8

`num_clients` profile keyword, ic:161

numbers
 audit events, aa:6

O

object
 defined, ug:6

object reuse
 how device allocation satisfies, at:403

object-reuse
 clean scripts, ao:137
 introduction, ug:13
 review, at:403

objects, dg:3 to dg:4

Occupy Workspace
 example, ug:53 to ug:55

ok prompt, ic:198

`ONLY_INFORMATION_LABEL`
 flag, dg:142

opaque token
 described, aa:143

praudit display, aa:143
 open audit record
 read, aa:197
 read, create, aa:198
 read, create,
 truncate, aa:198
 read, truncate, aa:199
 read, write, aa:199
 read, write, create, aa:200
 read, write, create,
 truncate, aa:200
 read, write,
 truncate, aa:201
 write, aa:201
 write, create, aa:202
 write, create,
 truncate, aa:202
 write, truncate, aa:203
 Open Look Interface Toolkit (OLIT), dg:10
 open networks
 defined, ao:85
 OpenWindows, dg:10
 oper role, *See* system operator
 operating system features, dg:2
 OS servers
 adding, ic:129, ic:138
 converting from standalone, ic:202
 described, ic:40, ic:116
 for diskless clients, ic:201
 requirement for network
 installation, ic:116
 OS services
 adding to network server, ic:203
osname rule keyword, ic:173
 ot audit class, aa:110
 ot audit flag, aa:9, aa:94
 other audit class, aa:9
 ouid field, dg:289
 output files
 begin scripts log, ic:182
 finish scripts log, ic:184

overlap value for *filesys*, ic:161

P

package profile keyword
 description and values, ic:162
 examples, ic:156
 packages from software groups
 adding, ic:162
 deleting, ic:162
 packages, *See* software packages
 packets
 IP options, at:249
 location of security attributes, dg:237
 security attributes, at:249 to at:254,
 dg:238
 standard Solaris, ao:85
 Trusted Solaris, ao:85
 PAF_DISKLESS_BOOT value, dg:38
 PAF_LABEL_VIEW
 process flag, la:27
 PAF_LABEL_VIEW value, dg:39
 PAF_LABEL_XLATE value, dg:39
 PAF_NO_TOKMAP value, dg:38
 PAF_PRINT_SYSTEM value, dg:38
 PAF_PRIV_DEBUG value, dg:38
 PAF_SELAGENT value, dg:38
 PAF_SELAGENT flag, dg:286
 PAF_TRUSTED_PATH value, dg:38
 page command
 default profile, at:501, ao:157
 PAM
 *See pluggable authentication
 module*, at:111
 pam_headers.h file
 settings for password values, at:110
 partitioning
 examples, ic:156 to ic:157
 excluding disks, ic:159
 fdisk partitions, ic:157
 profile keyword, ic:162

partitioning profile keyword, ic:163
 passwd audit record, aa:250
PASSWD variable, ic:187
 passwords
 account status, ao:72
 aging, ao:71
 assigning, at:106, at:113
 changing, ug:80 to ug:84, ao:71
 entry procedure, ug:21 to ug:22
 expiration, ug:80
 initial, ao:69
 installing, ic:91 to ic:92
 introduction, ug:3
 manual creation, ao:69
 NIS+ credentials, ao:72
 overview, ao:67 to ao:72
 requiring changes, at:111
 role, at:5
 root, ic:186 to ic:188
 root password creation, ic:60
 root password use, ic:72
 rules for manual creation, at:109
 system-generated, ao:69
 user attributes, ao:37
 path policy flag, aa:25
 path token
 described, aa:143
 praudit display, aa:144
 pathconf audit record, aa:203
 pathnames
 adorned names, dg:170
 translation, dg:170
 paths
 check script, ic:176
 install server setup, ic:134
 Trusted Solaris server setup, ic:134
 patrr command
 default profile, at:501, ao:157
 overview, ao:129
 pbind audit record, aa:251
 pc audit class, aa:110
 pc audit flag, aa:9, aa:94
 PCFS
 mounting in Trusted Solaris, at:328
 pclear command
 default profile, at:501, ao:157
 overview, ao:129
 pcred command
 default profile, at:501, ao:157
 permission bits
 changing, ug:100
 defined, ug:96
 described, at:314
 introduction, ug:4
 permissions
 begin scripts, ic:182
 described, at:305
 finish scripts, ic:184
 JumpStart directory, ic:146, ic:149
 overriding, ao:28
 permitted privileges
 See also privilege sets
 checking, dg:72
 code example, dg:73
 defined, dg:54
 pfiles command
 default profile, at:501, ao:157
 pfinstall command, ic:188 to ic:191
 pflags command
 default profile, at:501, ao:157
 pflash audit record, aa:251
 pflash command
 default profile, at:501, ao:157
 purpose, at:11
 pflash(ITSOL)
 determining privilege
 origination, dg:53
 inheriting privileges, dg:53
 pflash, *See* profile shell
 pg command
 default profile, at:501, ao:157

pid field, dg:289
 ping command
 default profile, at:501, ao:157
 pipe audit record, aa:204
 pipes, access checks, dg:218, dg:219
 pkgadd command
 default profile, at:501, ao:157
 pkgchk command
 default profile, at:501, ao:157
 pkginfo command
 default profile, at:501, ao:157
 pkgrm command
 default profile, at:501, ao:157
 plabel command
 default profile, at:501, ao:157
 overview, ao:130
 placeholder files
 label_encodings file, la:1, la:48,
 la:54
 planning security, ic:44
 platform groups, ic:247 to ic:248
 platforms
 diskless client, ic:158
 group determination, ic:247
 matching system attributes and
 profiles, ic:164, ic:167
 name determination, ic:120, ic:247
 rule keywords, ic:171
 supported, ic:38, ic:247
 system model names, ic:172
 table of names and groups by
 system, ic:247 to ic:248
 pldd command
 default profile, at:501, ao:157
 pluggable authentication module
 default settings, at:111
 plus (+) audit flag prefix, aa:10, aa:146,
 aa:147
 pmap command
 default profile, at:501, ao:157
 policy, *See* security policy
 polyinstantiation
 described, dg:281
 files and directories, dg:167
 network connections, dg:223
 port bindings
 network privileges, ao:28
 porting software, at:438
 ports
 See also multilevel ports
 single-level, dg:222
 postsigterm string and audit_warn
 script, aa:20
 pound sign (#)
 in profiles, ic:155
 in rules, ic:169
 poweroff command
 default profile, at:501, ao:157
 ppriv command
 overview, ao:130
 pprivtest command
 overview, ao:130
 pr command
 default profile, at:501, ao:157
 praudit command
 audit trail, dg:186
 changing field separator, aa:81
 changing token separator, aa:82
 default profile, at:501, ao:157
 human-readable format, aa:68
 output formats, aa:76 to aa:82
 overview, ao:111
 piping auditreduce output
 to, aa:77
 using, aa:76 to aa:82
 prefixes in audit flags, aa:10
 preselection mask
 C library functions, aa:263
 described, aa:16
 reducing storage costs, aa:22 to aa:23

preserve value for *filesystems*, ic:161
 preserving data
 existing data during
 installation, ic:161
 primary audit directory, aa:13
 principle of least privilege, at:440
 print format field values (arbitrary
 token), aa:130
 print server applications, dg:147
 printer banner page, label
 translation, dg:147
 PRINTER BANNERS section
 label_encodings example, la:160
 Printer Manager
 launching, at:384
 printer output
 changing label types, la:37
 labels, la:19
 Printer tool
 differences in Trusted Solaris, ug:74
 PRINTER variable
 printing without labels, at:399
 printers
 configuring, la:95
 label ranges
 setting, at:413
 printing
 authorizations, at:383
 banner text, la:81
 configuring labels and text, at:372,
 la:75
 planning example, la:141
 protecting printer output, la:76
 setting minimum protect as
 classification, la:76
 specifying SLs to print instead of ILs
 on body pages, at:396
 suppressing page labels, at:379
 without banners and trailers, at:397
 without banners
 authorization, at:383
 without page labels, at:398
 printing definitions
 label encodings file, ao:5
 printing flag, dg:38
 priocntlsys audit record, aa:204
 priv token
 described, aa:144
 praudit display, aa:144
 PRIV_ALLOWED value, dg:58
 PRIV_ASSERT macro
 and *str_to_priv(3TSOL)*, dg:68
 described, dg:59
 PRIV_CLEAR macro, dg:59
 PRIV_EFFECTIVE value, dg:58
 PRIV_EMPTY macro, dg:59
 PRIV_EQUAL macro, dg:59
 PRIV_FILL macro, dg:59
 PRIV_FORCED value, dg:58
 priv_ftype_t type, dg:58
 PRIV_INHERITABLE value, dg:58
 PRIV_INTERSECT macro, dg:59
 PRIV_ISASSERT macro
 code example, dg:72, dg:74
 described, dg:59
 PRIV_ISEEMPTY macro, dg:59
 PRIV_ISFULL macro, dg:59
 PRIV_ISSUBSET macro
 described, dg:59
 purpose, dg:73

priv_name file, at:39
 priv_names.h file, at:37
 PRIV_OFF value, dg:58
 PRIV_ON value, dg:58
 priv_op_t type, dg:58
 PRIV_PERMITTED value, dg:58
 PRIV_privilege name, *See* privileges and
 priv_desc(4TSOL)
 priv_ptype_t type, dg:58
 PRIV_SAVED value, dg:58
 PRIV_SET value, dg:58
 priv_set_t structure, dg:58
 priv_set_to_str(3TSOL)
 code example, dg:67
 declaration, dg:62
 priv_t type, dg:58
 PRIV_TEST macro, dg:59
 priv_to_str(3TSOL)
 code example, dg:63
 declaration, dg:62
 PRIV_UNION macro, dg:59
 PRIV_XOR macro, dg:59
 privilege
 audit records for use of, aa:235
 when executing commands, aa:42
 privilege APIs
 declarations, dg:60 to dg:62, dg:341
 macros, dg:59
 privilege bracketing
 benefits, dg:69
 code example, dg:71
 procedure, dg:70
 privilege data types
 file sets, dg:58
 operations on sets, dg:58
 privilege ID, dg:58
 process sets, dg:58
 structure, dg:58
 privilege debugging
 enabling, dg:29, dg:329
 flag, dg:38
 setting tsol_privs_debug, at:357
 privilege macros
 API declarations, dg:341
 asserting privilege example, dg:67
 described, dg:59
 initializing set example, dg:65
 privilege sets
 See also allowed privileges
 See also code examples
 See also effective privileges
 See also forced privileges
 See also inheritable privileges
 See also permitted privileges
 See also privileges
 See also saved privileges
 after exec(2TSOL), dg:77
 after fork(2TSOL), dg:75
 algorithms, dg:52
 allowed privileges, ao:26
 API declarations, dg:341
 defined, ao:26
 file, dg:51
 forced privileges, ao:27
 inheritable privileges, ao:27
 on network messages, dg:241
 privileged tasks, dg:55
 privileges needed, dg:55
 process, at:445, dg:52
 turning off allowed sey, dg:68
 privilege token
 described, aa:144
 praudit display, aa:145
 Privilege use audit record, aa:235
 privileged commands
 run by cron
 command(1MTSOL), at:75
 privileged process defined, dg:54
 privileged programs, at:461
 privileged tasks
 auditing, dg:183
 clearance, dg:150
 IPC, dg:217
 Label builder, dg:315
 labels, dg:93
 MLDs, dg:171

multilevel port connections, dg:222
 privilege sets, dg:55
 RPC, dg:272
 SLDs, dg:171
 System V IPC, dg:226
 TSIX, dg:239
 X Window System, dg:287

privileges, ao:124
See also authorizations
See also code examples
See also `priv_desc(4TSOL)` man page
See also privilege sets
See also security policy
See also translation

adding, at:37
 administrative applications, dg:15
 allowed, at:454, ao:26, ao:29
 alternatives to using, at:440
 API declarations, dg:341
 applications, privileged, dg:55
 assigning to actions, ao:117
 assigning to commands, ao:117
 assigning to files, ao:118
 and authorizations, dg:40
 availability, ao:27, ao:31, ao:43
 bracketing, at:440
 categories, ao:28

- file system, dg:51
- file system privileges, ao:28
- IPC, dg:51
- network privileges, ao:28
- process, dg:51
- process privileges, ao:28
- system, dg:51
- system privileges, ao:28
- System V IPC, dg:51
- System V IPC privileges, ao:28
- window privileges, ao:28
- X Window System, dg:51

changing on files and directories, at:336
 DAC override, at:439
 defined, at:438, ug:13, dg:49, ao:2
 delimiters, dg:67

described, at:314
 description text API, dg:62
 development environment, dg:40
 effective set

- defined, at:445

errors, dg:15
 example, at:441
 execution profiles, ao:38
 in execution profiles, at:196, ao:21
 file access, ao:34
 file attributes, ao:39
 file_dac_read

- as an override privilege, at:439

file_dac_write

- as an override privilege, at:439

file_mac_read

- as an override privilege, at:439

file_mac_write

- as an override privilege, at:439

forced, ao:27, ao:29

- assigning, at:453, at:476

guidelines, dg:56
 inheritable, at:450, at:454, ao:27, ao:29
 inheritable set

- defined, at:445

inheritance, at:442
 on interpreted files, dg:52
 MAC override, at:439
 making available to

- commands, at:453

network interfaces, ao:93
 non-obvious reasons for

- requiring, at:463

override, at:96

- defined, at:439

overview, ao:26 to ao:31
 permitted set

- defined, at:445

principle of least privilege, at:440
 procedure for adding, at:40
 process attributes, ao:42
 remote host templates, ao:90
 required, at:95, at:439
 running with all, at:444
 saved set

- defined, at:445

- saving and restoring an edited executable, at:483
 - scripts, dg:330
 - separators, dg:67
 - software administration, ao:19
 - contrast to superuser, dg:6
 - TCB, dg:6, dg:55
 - UIDs, changed, dg:54
 - upgraded names
 - hide, dg:29
 - used by commands in the `pfsh` shell, at:443
 - user applications, dg:16
 - when to use, dg:13, dg:40
 - when writing to executable, dg:55
- Privileges dialog box
 - assigning privileges, ao:29
- privs field, dg:208
- `proc_audit_appl` privilege, dg:183
- `proc_audit_tcb` privilege, dg:46
- `proc_mac_owner` privilege, dg:217
- `proc_mac_read` privilege, dg:217
- `proc_nofloat` privilege, dg:94
- `proc_set_sl` privilege, dg:239
- `proc_setclr` privilege, dg:150, dg:260
- `proc_setid` privilege, dg:56
- `proc_setil` privilege, dg:93
- `proc_setsl` privilege, dg:93
- process audit characteristics, aa:16 to aa:17
 - audit ID, aa:17
 - audit session ID, aa:17
 - process preselection mask, aa:16, aa:22 to aa:23
 - terminal ID, aa:17
- process audit class, aa:9
- process clearances
 - acquiring, dg:149
 - API declarations, dg:152 to dg:155, dg:347
 - checking before file access, dg:43
 - components, dg:149
 - data types
 - clearance structure, dg:151
 - levels, dg:151
 - described, dg:149
 - dominate levels, dg:158
 - equal levels, dg:158
 - levels defined, dg:158
 - MAC checks, dg:42
 - mandatory access operations, dg:13
 - privileged tasks, dg:150
 - reentrant routines, dg:165
 - strictly dominate levels, dg:158
 - TSIX, dg:240
 - valid, dg:152
- process dumped core audit record, aa:205
- process preselection mask
 - application auditing, dg:185
 - changing, dg:195
 - described, aa:16
 - reducing storage costs, aa:22 to aa:23
 - return token, dg:190
- process privilege sets, at:445
- process token
 - described, aa:145
 - `praudit` display, aa:146
- process tracing, access checks, dg:220
- processes
 - See also* code examples
 - See also* security attribute flags
 - See also* security attributes
 - accessing data, ao:40
 - attributes, ao:42
 - changing SLs, guidelines, dg:96
 - CMW label, inheriting values, dg:91
 - described, at:314
 - effective privilege set, dg:54
 - inheritable privilege set, dg:53
 - label privileges, dg:93
 - objects, dg:3
 - permitted privilege set, dg:54
 - privilege sets, dg:52
 - privileged tasks, dg:217
 - privileged, defined, dg:54

- privileges, ao:28
- privileges, defined, dg:51
- relationship to programs, at:445
- saved privilege set, dg:53
- processing time costs, aa:21
- processors
 - rule keywords, ic:169
- PROCFS
 - mounting in Trusted Solaris, at:329
- procplabel command
 - default profile, at:502, ao:158
- procppriv command
 - default profile, at:502, ao:158
- procpprivtest command
 - default profile, at:502, ao:158
- profact_t structure, dg:208
- profcmd_t structure, dg:208
- profent_t structure, dg:207
- profile database, *See* databases
- Profile dialog box
 - User Manager, at:120, at:121
- profile keywords, ic:158 to ic:163
 - adding to profiles, ic:155
 - case sensitivity, ic:155
 - client_arch*, ic:158
 - client_root*, ic:158
 - client_swap*, ic:158
 - cluster*
 - description and values, ic:159
 - examples, ic:156
 - dontuse*
 - description and values, ic:159
 - usedisk* and, ic:163
 - fdisk*
 - example, ic:157
 - filesys*
 - description and values, ic:161
 - examples, ic:156 to ic:157
 - local file systems, ic:160 to ic:161
 - install_type*
 - description and values, ic:161
 - examples, ic:156
 - requirement, ic:154, ic:156
 - num_clients*, ic:161
- package*
 - description and values, ic:162
 - examples, ic:156
- partitioning*
 - description and values, ic:162
 - designating disks, ic:163
 - examples, ic:156 to ic:157
 - excluding disks, ic:159
- system_type*
 - description and values, ic:162
 - examples, ic:156 to ic:157
- usedisk*
 - description and values, ic:163
 - dontuse* and, ic:159
- profile keywords to profiles
 - adding, ic:155
- Profile Manager
 - assigning actions, at:221
 - assigning authorizations, at:219
 - assigning commands, at:217
 - assigning inheritable
 - privileges, ao:27, ao:29
 - filtering profiles, at:200
 - overview, ao:114 to ao:117
 - procedures for using, at:223 to at:232
 - setting label ranges, at:215
 - specifying privileges for commands
 - and actions, at:454
 - using, at:198 to at:232
- profile shell
 - adding all privileges, ic:123
 - assigning, ao:66
 - defined, ug:14, ao:23
 - effect on commands, at:442
 - exiting, ic:124
 - managing inherited privileges, at:443
 - opening, ic:72, aa:43
 - purpose, at:11
 - startup algorithm, at:67
- profile shell, *See* pfs(1TSOL)
- profiles
 - comments in, ic:155
 - creating, ic:142, ic:153 to ic:155
 - creating derived, ic:182 to ic:183
 - derived profiles, ic:182 to ic:183

described, ic:142, ic:153
 examples
 eng_profile, ic:253
 marketing_profile, ic:254
 short, ic:156
 matching systems to, ic:164, ic:167
 naming, ic:154
 requirements, ic:154, ic:155
 rule field, ic:167
 See execution profiles
 testing, ic:188 to ic:190
 profiles field, dg:206
 profmgr command
 default profile, at:502, ao:158
 profstr_t structure, dg:207
 programming interfaces, See APIs
 programs
 commercial
 assigning privileges to, at:453
 new, trusted
 assigning privileges to, at:453
 relationship to processes, at:445
 trusted
 defined, at:461
 trustworthy
 defined, at:461
 properties
 described, dg:283, dg:284
 privileges, dg:287
 protect as classification
 overview, la:76
 protect_as field, dg:100
 protect_as_len field, dg:99, dg:100
 prtconf command, ic:172
 default profile, at:502, ao:158
 prtvtoc command
 disk configuration file creation, ic:192
 prun command
 default profile, at:502, ao:158
 ps command
 default profile, at:502, ao:158
 pseudo-events
 audit records, aa:235
 pseudo-terminal devices, See PTYs
 pstat command
 default profile, at:502, ao:158
 psradm audit record, aa:252
 pstack command
 default profile, at:502, ao:158
 pstp command
 default profile, at:502, ao:158
 ptime command
 default profile, at:502, ao:158
 ptree command
 default profile, at:502, ao:158
 PTYs
 (pseudo-terminal devices)
 access checks, dg:219
 putmsg audit record, aa:205
 socket connect, aa:206
 socket send, aa:206
 putpmsg audit record, aa:207
 pwait command
 default profile, at:502, ao:158
 pwck command
 default profile, at:502, ao:158
 pwd command
 default profile, at:502, ao:158
 pwdx command
 default profile, at:502, ao:158

Q

Query Window Label menu item
 described, ug:84

R

rc scripts
 shell use, at:443
 rc2.d directory
 S05RMTMPFILES script, at:6
 rcp command
 default profile, at:502, ao:158
 required privilege, at:462

`rdate` command
 Trusted Solaris modifications, ao:102, ao:138

`rdist` command
 default profile, at:502, ao:158

read access
 IL conjoin, dg:90
 overview, ug:6
 security policy, dg:14

read down, dg:14

read equal, dg:14

`readlink` audit record, aa:207

real UID
 root
 required for applications, at:464

 root requirement for
 installation, at:463

reboot
 preventing disable of logins, at:26
 re-enabling logins, at:5
 workstation during
 configuration, ic:91

`reboot` command
 default profile, at:502, ao:158

`reboot:` machine reboot audit record, aa:252

reentrant routines
 binary to hex declarations, dg:109
 binary to hex translation, dg:146, dg:165

reference
 filesystem security attributes on audit files, aa:264

`reject` command
 modified for Trusted Solaris, at:382
 default profile, at:502, ao:158

relationships
 between ILs, dg:125
 between levels, dg:123, dg:158
 between markings, dg:127

release of Trusted Solaris software
 installed rule keyword, ic:170
 osname rule keyword, ic:173

releasing an application, dg:331

`rem_drv` audit record, aa:254

`rem_drv` command
 default profile, at:502, ao:158
 Trusted Solaris modifications, ao:135

remote file systems
 accessing, ic:210

remote host templates
 creating new template, ic:80
 defined, ao:90

remote hosts
 tnrhdb(4TSOL), ao:88

remote procedure call, *See* RPC

`rename` audit record, aa:208

Rename menu item
 described, ug:78

`renice` command
 default profile, at:502, ao:158

requirements
 labeling printer output, la:76
 network installation
 servers, ic:116 to ic:117
 profiles, ic:154, ic:155

`reset` command, ic:120

`reset_il_on_exec` flag, dg:92

resource file, dg:303

ResourceType structure, dg:289

return token
 praudit display, aa:147

Revised Internet Protocol Security Option,
 See RIPS0

RIPS0
 (Revised Internet Protocol Security Option)
 host type, ao:87
 described, at:267
 remote host templates, ao:90
 use in packets, at:251

`rlogin` command
 default profile, at:502, ao:158

rm command
 default profile, at:502, at:503, ao:158, ao:159
rmdir audit record, aa:208
rmdir command
 default profile, at:503, ao:159
roles
 See also administrative roles
 administrative, at:89 to at:90
 assuming a role, la:27
 administrative workspaces, la:28
 assigning, ao:79 to ao:80
 assuming, ug:80
 combining administrative roles, at:94
 contrasted with user accounts, at:88
 creating, at:95 to at:98
 override privileges, at:96
 required privileges, at:95
 creating accounts, ao:66
 defined, ug:13
 managing, at:87 to at:98
 non-administrative, at:88 to at:89
 overview, ao:24
 password, at:5
 procedure for creating, at:98
 root, at:89
 security administrator contrasted with system administrator, at:91
 user attributes, ao:37
Roles dialog box
 User Manager, at:122
roles field, dg:206
root
 defined, ug:14
 role defined, ao:3
 saving and restoring NIS+ tables, at:349
root (/) file systems
 networked systems, ic:40
 profile example, ic:157
 value set by installation program, ic:174 to ic:175
root environment (customizing), ic:186
root passwords, ic:186 to ic:188
 created, ic:60
 for diskless clients, ic:208
 used, ic:72
root role
 assuming, ic:71
 compared with privileges, at:439
 using to install applications, at:464
root UID
 required for applications, at:464
 requirement for installation, at:463
rootdisk
 defined, ic:174
 slice value for *filesys*, ic:160
 value set by installation program, ic:174 to ic:175
route command
 Trusted Solaris modifications, ao:102
routing
 assigning default, at:297
 concepts, at:240 to at:246
 overview, ao:95 to ao:98
 procedure for setup, at:297
 setting up, at:271 to at:302
RPC
 (remote procedure call)
 See also code examples
 API man pages, dg:275
 client program, dg:276 to dg:277
 described, dg:271
 example application, dg:275 to dg:280
 mappings, dg:272
 multilevel ports, dg:272
 privileged tasks, dg:272
 remote procedure, dg:279
 running the application, dg:280
 security attributes, dg:273
 server program, dg:278

RPC failed: error 5: RPC Timed out message, ic:153, ic:278
 RPC Timed out message, ic:153, ic:278
 rpc.cmsd command
 default profile, at:503, ao:159
 rpc.rexd audit record, aa:253
 rpc.ttdbserverd command
 default profile, at:503, ao:159
 rpcbind command
 default profile, at:503, ao:159
 rsh command
 default profile, at:503, ao:159
 rshd access denials/grants audit record, aa:254
 rule keywords, ic:169 to ic:173
 any
 description and values, ic:169
 rootdisk matching, ic:174
 arch, ic:169
 disksize
 description and values, ic:170
 rootdisk matching, ic:174
 domainname, ic:169
 hostaddress, ic:170
 hostname, ic:168, ic:170
 installed
 description and values, ic:170
 rootdisk matching, ic:174
 karch, ic:171
 memsize, ic:168, ic:171
 model, ic:168, ic:172
 network, ic:168, ic:173
 osname, ic:173
 totaldisk, ic:173
 validation, ic:175
 rule_keyword rule field, ic:166
 rule_value rule field, ic:166, ic:169
 rules
 derived profiles, ic:182 to ic:183
 displaying and entering CMW labels, la:14
 examples, ic:167
 field descriptions, ic:166 to ic:167
 matching order, ic:164, ic:167
 multiple line rules, ic:169
 rootdisk matching rules, ic:174 to ic:175
 syntax, ic:165
 testing validity, ic:176
 rules file
 adding rules, ic:165
 comments, ic:169
 creating, ic:142, ic:164 to ic:167
 described, ic:142, ic:164
 example, ic:164
 multiple line rules, ic:169
 naming, ic:165, ic:168
 syntax, ic:165
 testing rules, ic:176
 validating using *check*, ic:142, ic:175 to ic:176
 derived profiles and, ic:183
 rules files
 adding rules, ic:165
 custom JumpStart example, ic:254 to ic:255
 testing, ic:255
 testing rules, ic:176
 using *check*, ic:142, ic:175 to ic:176
 validating, ic:255
 rules.ok file
 comments and, ic:169
 creating, ic:142, ic:164, ic:169, ic:175
 described, ic:169
 matching order for rules, ic:164, ic:167
 run control scripts
 modifying, at:457
 shell use, at:443
 runpd command
 default profile, at:503, ao:159
 dependency on *tsol_priv_debug* setting, at:357
 overview, ao:130
 using, dg:329
 rup command
 default profile, at:503, ao:159

S

- sadmin command
 - default profile, at:503, ao:159
- SAMP (Security Attribute Modulation Protocol)
- SAMP (Security Attribute Modulation Protocol)
 - Trusted Solaris data packets, ao:86
- SATMP (Security Attribute Token Mapping Protocol)
 - tokmapd command, ao:105
- saved privileges
 - See also privilege sets
 - change UID, GUID, or SGUID, dg:54
 - checking, dg:74
 - defined, dg:53
 - purpose, dg:53
- sbclearaos(3TSOL)
 - code example, dg:163
 - declaration, dg:154
- sbcltos(3TSOL), declaration, dg:107
- sbiltos(3TSOL), declaration, dg:108
- /sbin/rcn scripts
 - Trusted Solaris modifications, at:458
- /sbin/sysh shell
 - using during boot, at:458
- sbsltos(3TSOL)
 - code example, dg:143
 - declaration, dg:108
- screen locking, ug:30 to ug:31
- script command
 - default profile, at:503, ao:159
- scripts
 - adding finish, ic:185
 - begin scripts, ic:181 to ic:183, ic:196
 - Bourne shell scripts in rule fields, ic:167
 - creating finish, ic:184
 - finish scripts, ic:184 to ic:188, ic:196
 - network installation
 - commands, ic:120
 - network installation files, ic:121
 - privileged, dg:330
- SCSI interface, requirement, ic:38
- sdiff command
 - default profile, at:503, ao:159
- secadmin role, See security administrator
- secconf system call
 - code example, dg:29
 - declaration, dg:27
- secondary audit directory, aa:13
- security
 - auditing tasks for
 - administrators, aa:38
 - common violations, ic:217
 - computer publications, ic:220
 - computer recommendations, ic:215
 - personnel recommendations, ic:217
 - physical recommendations, ic:216
 - root password, ic:186 to ic:188
 - site security policy, ic:214
 - U.S. Government publications, ic:219
 - understanding before
 - installation, ic:16
 - understanding during
 - planning, ic:16
 - UNIX publications, ic:219
- security administrator
 - background on labels, la:1
 - defined, ug:14, ao:3
 - label administration
 - responsibilities, la:28
- security administrators
 - accessing the Printer Manager, at:384
 - account management
 - responsibilities, at:61
 - contrasted with system administrators, at:91
 - described, at:314
 - enable logins authorization
 - requirement, at:5
 - modifying window configuration files, at:467
 - system integrity
 - assessing after reboots, at:5

security attribute flags
 See also code examples, file systems
 See also code examples, processes
 API declarations, dg:340
 file systems
 API declarations, dg:27
 contrast with Solaris, dg:11
 manifest constants, dg:33, dg:35
 processes
 API declarations, dg:27
 contrast with Solaris, dg:11
 getting and setting, dg:37
 manifest constants, dg:38
 when to use, dg:26

Security Attribute Modulation Protocol,
 See SAMP

Security Attribute Token Mapping
 Protocol, *See* SATMP

security attributes
 See also code examples, file systems
 access checks, dg:217
 access to privileges, dg:55
 accessing labels, dg:93
 API declarations, dg:340
 in data packets, ao:86
 described, at:315
 file system defaults, ic:47
 file systems, at:318 to at:326
 API declarations, dg:27
 contrast with Solaris, dg:11
 described, dg:31
 manifest constants, dg:33
 vfstab_
 adjunct(4TSOL), dg:31
 when to use, dg:26
 filesystem auditing, aa:264
 MLDs, dg:177
 network interface defaults, ic:46
 privileges, dg:217
 processes, dg:11
 RPC, dg:273
 on software packages, dg:333
 TSIX
 changing, dg:239
 changing procedure, dg:248
 contrast with Solaris, dg:12
 location on packet, dg:237
 sending and receiving, dg:238

X Window System
 contrast with Solaris, dg:12
 described, dg:283

security domain
 defined, ao:84

security domains
 multiple described, at:238
 single described, at:236

security features
 identification and authentication for
 roles, at:5

security mechanisms
 extendable by security
 administrator, at:31

security policy
 See also authorizations
 See also clearances
 See also DAC
 See also MAC
 See also privileges
 See also SLs
 accessing MLDs, dg:168
 accessing SLDs, dg:168
 administrative applications, dg:15
 auditing, dg:183
 CDE actions, dg:332
 clearances, dg:150
 command line execution, dg:57
 communication endpoints, dg:221
 covert channels, dg:57
 defined, ug:2
 described, at:315
 discretionary access
 operations, dg:13
 file system examples, dg:19
 file systems, dg:16
 file systems access, dg:17
 file systems privileges, dg:18
 IPC, dg:16, dg:217
 label guidelines, dg:94
 labels, dg:93
 on man pages, dg:325

mandatory access operations, dg:13
 mapped memory, dg:220
 MLD access, dg:178
 multilevel ports, dg:222
 overriding, ao:28
 pipes, dg:218, dg:219
 planning example, la:141
 principle of least privilege, at:440
 privilege bracketing, dg:56
 privilege guidelines, dg:56
 privilege sets, dg:55
 privileges
 when to use, dg:42
 privileges, when to use, dg:13
 process tracing, dg:220
 PTYs, dg:219
 read access, dg:14
 reading man pages, dg:15
 setting minimum protect on print
 jobs, la:76
 signals, dg:220
 site-specific, la:37
 SLD access, dg:178
 sockets, dg:223
 System V IPC, dg:221, dg:226
 TLI, dg:223
 translating labels, dg:93, dg:150
 user applications, dg:16
 write access, dg:14
 X Window System, dg:284
 sed command
 default profile, at:503, ao:159
 selection agent flag, dg:38
 Selection Manager
 bypassing with flag, dg:286
 Confirmation dialog box
 example, ug:57 to ug:58
 security policy, dg:286
 self-modification authorization, at:94
 semaphore sets
 See also code examples
 See also System V IPC
 API declarations, dg:229, dg:349
 IL floating, dg:227
 overriding restrictions, ao:28
 semctl audit record
 GETALL command, aa:209
 GETNCNT command, aa:209
 GETPID command, aa:210
 GETVAL command, aa:210
 GETZCNT command, aa:211
 IPC_RMID command, aa:211
 IPC_SET command, aa:212
 IPC_STAT command, aa:213
 SETALL command, aa:212
 SETVAL command, aa:213
 semget audit record, aa:214
 semgetl audit record, aa:215
 semgetl system call
 code example, dg:233
 declaration, dg:229
 semop audit record, aa:215
 semopl audit record, aa:216
 semopl system call, declaration, dg:229
 sendmail audit record, aa:255
 sendmail command
 Trusted Solaris modifications, ao:138
 to ao:140
 using, at:168 to at:171
 SENSITIVITY LABELS section
 label_encodings example, la:156
 sensitivity labels, *See* SLs
 sensitivity of information
 downgrading labels, la:20
 seq policy flag, aa:25
 seq token
 described, aa:147
 praudit display, aa:147
 servers
 JumpStart directory creation, ic:149
 to ic:151
 name server, ic:116
 network installation setup, ic:135
 requirements for network
 installation, ic:116 to ic:117
 root space, ic:158

session clearances
 choosing a single SL, la:10
 defined, ug:10
 described, at:316
 overview, la:6
 restricting the upper bound below the
 user's clearance, la:10
 restricting to a single SL, la:10
 setting, ug:39 to ug:40
 session ID, aa:17, aa:70
 session range
 defined, ao:11
 sessionid field, dg:289
 sessions
 duration of label restrictions chosen at
 login, la:10
 restricting to a single SL, la:10
 setting level, ug:24 to ug:29, ug:37 to
 ug:40
 set_effective_priv(3TSOL)
 code example, dg:41, dg:71
 declaration, dg:61
 set_id structure, dg:99
 set_inheritable_priv(3TSOL)
 code example, dg:74
 declaration, dg:61
 set_permitted_priv(3TSOL)
 code example, dg:73
 declaration, dg:61
 set_root_pw finish script, ic:186 to
 ic:188
 setaudit audit record, aa:217
 setaudit audit record, aa:217
 setbltype(3TSOL)
 code example, dg:114, dg:157
 declaration, dg:105, dg:153
 setcil(3TSOL)
 code example, dg:119
 declaration, dg:103
 SETCL_ALL flag, dg:98
 SETCL_IL flag, dg:98
 SETCL_SL flag, dg:98
 setclearance system call
 code example, dg:156
 declaration, dg:152
 setcmwlabel system call
 code example, dg:119
 declaration, dg:101
 setcmwplabel system call
 code example, dg:117
 declaration, dg:101
 when to use, dg:92
 setcsl(3TSOL)
 code example, dg:119
 declaration, dg:102
 setegid audit record, aa:220
 seteuid audit record, aa:220
 seteuid system call
 and privileges, dg:54
 setfacl command
 default profile, at:503, ao:159
 setfattrflag command
 default profile, at:503, ao:159
 described, at:321
 overview, ao:121
 setfattrflag system call
 code example, dg:35
 declaration, dg:27
 setfpriv command
 restricting assignment of forced and
 allowed privileges, at:454
 setfpriv command, at:453
 default profile, at:503, ao:159
 overview, ao:122
 setfpriv system call
 code example, dg:65, dg:67
 declaration, dg:60
 setfpriv(2TSOL)
 scripts, dg:330
 setfsattr command
 default profile, at:503, ao:159

described, at:325
 overview, ao:125
 setgid audit record, aa:221
 setgroups audit record, aa:221
 setlabel command
 default profile, at:503, ao:159
 overview, ao:122
 setpatrr system call
 declaration, dg:27
 setpgrp audit record, aa:222
 setppriv system call
 declaration, dg:60
 privilege bracketing, dg:71
 setprof command
 overview, ao:141
 setprofent(3TSOL),
 declaration, dg:210
 setprofstr(3TSOL),
 declaration, dg:210
 setreuid system call
 and privileges, dg:54
 setrlimit audit record, aa:222
 setting_flag field, dg:98
 setuid audit record, aa:223
 setuid system call
 and privileges, dg:54
 setuname audit record, aa:256
 setup_install_server command
 boot server setup, ic:136
 custom JumpStart example, ic:257
 described, ic:120
 install server setup, ic:122
 setuserent(3TSOL)
 code example, dg:216
 declaration, dg:209
 SGIDs
 (supplementary group IDs)
 privilege to change, dg:56
 sh command
 default profile, at:503, ao:159
 shadow file, ic:187
 share audit record, aa:257
 share command
 default profile, at:503, ao:159
 sharing JumpStart directory, ic:253
 Trusted Solaris modifications, ao:128
 share_nfs command
 Trusted Solaris modifications, ao:127
 shareall command
 default profile, at:503, ao:159
 shared directories
 exporting, ic:102
 starting server daemon, ic:127
 shared libraries, trusted, dg:326
 shared memory regions
 See also code examples
 See also System V IPC
 API declarations, dg:230, dg:349
 IL floating, dg:227
 overriding restrictions, ao:28
 sharing directories, at:343
 shell escapes and privileges, dg:57
 shell scripts
 summary of Trusted Solaris
 behavior, at:470
 writing privileged, at:479
 writing privileged using standard
 shells, at:480
 shells
 assigning to accounts, at:104
 sysh(1MTSOL), at:458
 shmact audit record, aa:223
 shmctl audit record
 IPC_RMID command, aa:224
 IPC_SET command, aa:224
 IPC_STAT command, aa:225
 shmdt audit record, aa:225
 shmget audit record, aa:226
 shmgetl audit record, aa:227
 shmgetl system call
 code example, dg:235
 declaration, dg:230

SHORT_CLASSIFICATION
 flag, dg:137
 SHORT_WORDS flag, dg:137
 showmount command
 default profile, at:503, ao:159
 Shut Down menu item
 described, ug:92
 SI_CONFIG_DIR variable, ic:185
 SI_PROFILE environment variable, ic:183
 SI_SYS_STATE variable, ic:188
 signal received during auditing
 shutdown, aa:20
 signals, access checks, dg:220
 single SL sessions, la:10
 single-label file systems, dg:121
 single-label operation
 label_encodings file, la:59
 single-label systems, la:9
 single-level directories, *See* SLDs
 single-level mappings, dg:272
 single-level ports
 changing client SL, dg:239
 described, dg:222
 single-level sessions
 defined, ug:10
 single-user mode, la:32
 site security policy, ic:213 to ic:220
 site-specific installation programs, ic:196
 size
 hard disk
 root space, ic:158
 rule keywords, ic:170, ic:173
 local file system, ic:160
 managing audit files, aa:19
 memory, ic:168, ic:171, ic:189
 reducing audit files
 storage space
 requirements, aa:21 to
 aa:22
 swap space
 diskless client, ic:158
 maximum size, ic:163
 profile examples, ic:156, ic:157
 skeleton directories
 defining printers, at:399
 use in Trusted Solaris, at:69
 skeleton path, at:114
 sl field, dg:289
 slabel token
 described, aa:147
 praudit display, aa:148
 slabel_len field, dg:99
 SLDs
 (single-level directories)
 See also code examples
 accessing, dg:168
 adorned names, dg:170
 API declarations, dg:172 to dg:174
 creating, dg:168
 defined, ug:11
 described, at:316, dg:167
 example, ug:51 to ug:53
 information structure, dg:172
 privileged tasks, dg:171
 sensitivity labels, dg:171
 structure, dg:168
 working with, at:43 to at:53
 See also MLDs
 sleep command
 default profile, at:503, ao:159
 slices
 filesys values, ic:160
 profile examples, ic:156 to ic:157
 rule keyword, ic:170
 SLs
 (sensitivity labels)
 See also CMW labels
 See also code examples
 See also ILS
 See also labels
 See also translation
 accreditation ranges, dg:131
 adorned pathnames, dg:170
 API declarations, dg:344
 assigning to actions, ao:117
 assigning to commands, ao:117
 authorizations for changing, la:9

changing, ug:111 to ug:113
 by copying, ug:59
 by linking, ug:59
 by moving, ug:59
 example, ug:59 to ug:62
 changing on client, dg:239
 characteristics, la:8
 checking before file access, dg:43
 in CMW label, dg:88
 components, dg:89
 Customize Trusted Solaris
 Configuration dialog
 box, la:30
 defined, ug:6, ao:2
 described, at:316
 determining by window query, ug:84
 determining with File
 Manager, ug:108
 displaying and hiding, at:117 to
 at:119
 example, la:9
 file systems, ao:124
 guidelines, dg:94
 downgrading SLs, dg:96
 upgrading SLs, dg:96
 hiding and restricting user to work at
 a single SL, la:34
 how used in access control, la:11
 label overview, ao:4, ao:16
 length of components, la:7
 MAC checks, dg:42
 mandatory access, dg:13
 minimum number to define, la:2
 network interfaces, ao:93
 on file systems, dg:34
 privileges
 changing process SL, dg:93
 downgrading SLs, dg:93
 upgrading SLs, dg:93
 process attributes, ao:42
 purpose, dg:87
 remote host templates, ao:90
 replying at equal SL, dg:239
 setting session SLs, ug:26 to ug:29
 site analysis example, la:134 to la:138
 site implementation example, la:129
 to la:133
 specifying colors, la:105 to la:113
 System V IPC, dg:228
 TSIX, dg:240
 user processes, dg:91
 visibility, ao:76
 Small Computer System Interface (SCSI),
 requirement, ic:38
sname
 classification keyword, la:53
 snoop command
 default profile, at:504, ao:160
 Trusted Solaris modifications, ao:103
 socket accept audit record, aa:178
 socket connect audit record, aa:206
 socket receive audit record, aa:178
 socket send audit record, aa:206
 socket token
 described, aa:148
 praudit displayA, aa:149
 socket-inet token
 described, aa:149
 praudit display, aa:150
 sockets
 access checks, dg:217, dg:221, dg:223
 See also communication endpoints
 soft limit
 audit_warn condition, aa:19
 minfree: line described, aa:13
 soft string with audit_warn
 script, aa:19
 software
 exporting multiple SLs, at:437
 importing, at:438
 multiple SLs, at:437
 installing publicly available software
 at ADMIN_LOW, at:437
 porting
 reasons against, at:463
 software administration
 overview, ao:19 to ao:31

software administration authorizations,
 defined, dg:80
 software groups
 cluster names for profiles, ic:159
 profile examples, ic:156
 specifying packages, ic:162
 software packages
 adding new, dg:335
 creating, dg:332
 editing existing, dg:335
 MAC attributes on, dg:333
 prototype file, dg:337
 Solaris
 achieving the same look and feel, la:2
 Solstice Application Manager
 See Application Manager
 Solstice_Apps folder
 Host Manager, ic:120
 overview, ao:52 to ao:54
 using, ic:79
 sort command
 default profile, at:504, ao:160
 SPARC systems
 JumpStart directory creation on
 diskette, ic:146 to ic:148
 platform names and groups, ic:247 to
 ic:248
 platforms supported, ic:38
 spell command
 default profile, at:504, ao:160
 spoofing
 defined, ug:3
 spray command
 default profile, at:504, ao:160
 Trusted Solaris modifications, ao:103
 spreadsheet, policy for access to, at:306
 square brackets [] rule field, ic:166
 src parameter values, dg:208
 st_atime field, dg:172
 st_ctime field, dg:172
 st_gid field, dg:172
 st_mode field, dg:172
 st_mtime field, dg:172
 st_nlink field, dg:172
 st_uid field, dg:172
 standalone systems
 adding, ic:129
 custom JumpStart installation
 example, ic:144
 described, ic:40
 networked and non-networked
 systems, ic:40
 profile examples, ic:156 to ic:157
 Standard Time zones, ic:279 to ic:280
 standard UNIX shell
 effect on commands, at:442
 startup files
 .cm.rc file, at:68
 configuring accounts, at:65 to at:85
 .mailrc file, at:68
 .netscape file, at:68
 .newsrc file, at:68
 procedures for customizing, at:83 to
 at:85
 rc2 .d/S05RMTMPFILES, at:6
 read at window system startup, at:65
 stat audit record, aa:227
 stat structure, dg:172
 statfs audit record, aa:228
 statvfs audit record, aa:228
 stime audit record, aa:229
 stobcl(3TSOL)
 code example, dg:143
 declaration, dg:107
 stobclear(3TSOL)
 code example, dg:163
 declaration, dg:154

stobil(3TSOL)
 code example, dg:143
 declaration, dg:108
 stobs1(3TSOL)
 code example, dg:45, dg:143
 declaration, dg:108
 storage costs, aa:21 to aa:22
 str_to_auth(3TSOL)
 code example, dg:84
 declaration, dg:82
 str_to_auth_set(3TSOL)
 code example, dg:85
 declaration, dg:82
 str_to_priv(3TSOL)
 and PRIV_ASSERT macro, dg:68
 code example, dg:63
 declaration, dg:62
 str_to_priv_set(3TSOL)
 code example, dg:67
 declaration, dg:62
 strace command
 default profile, at:504, ao:160
 STREAMS, *See* trusted streams
 strict dominance, la:12
 defined, ug:7
 described, at:316
 strictly dominate levels, dg:124, dg:158
 stty command
 default profile, at:504, ao:160
 Style Manager, la:11
 su audit record, aa:257
 subject
 defined, ug:6
 subject token
 described, aa:150
 praudit displayA, aa:150
 subnet
 boot server creation on, ic:136
 success
 audit flag prefix, aa:10
 turning off audit flags for, aa:10
 SUN_CLR_ID value, dg:157
 SUN_CLR_UN value, dg:157
 SUN_CMW_ID value, dg:113
 SUN_IL_ID value, dg:113
 SUN_IL_UN value, dg:113
 SUN_SL_ID value, dg:113
 SUN_SL_UN value, dg:113
 sun_tsol host type
 defined, ao:86
 described, at:257
 SUNWCall group, ic:159
 SUNWcar package, aa:2
 SUNWprog group, ic:159
 SUNWcsr package, aa:2
 SUNWcsu package, aa:2
 SUNWUser group, ic:159
 SUNWhea package, aa:2
 SUNWman package, aa:2
 SUNWtsolr package, aa:2
 SUNWtsolu package, aa:2
 superuser, *See* privileges
 supplementary group IDs, *See* SGIDs
 SVCXPRT structure, dg:273
 swap audit record, aa:258
 swap command
 default profile, at:504, ao:160
 swap file systems
 diskless client swap space, ic:158
 memory size and, ic:163
 networked systems, ic:40
 profile examples, ic:156, ic:157
 size determination, ic:163
 swap value for *filesystems*, ic:161
 swmtool command
 default profile, at:504, ao:160
 symbolic links
 information structure, dg:172
 MLDs, dg:169

symlink audit record, aa:229
SYS_MEMSIZE variable, ic:189
 sys_trans_label privilege, dg:45,
 dg:93, dg:150
 sys_trans_label privilege, dg:315
 sysh shell
 using during boot, at:458
 sysh command
 overview, ao:141
 sysh shell
 trusted processes, at:443
 sysinfo audit record, aa:230
 syslogd command
 default profile, at:504, ao:160
 system accreditation range
 defined, ao:7
 described, at:317
 system administration
 in Trusted Solaris, ug:13 to ug:15
 system administrator
 account management
 responsibilities, at:61
 adding a host, at:348
 contrasted with security
 administrator, at:91
 defined, ug:14, ao:3
 system booted audit record, aa:230
 system calls
 API declarations, dg:353 to dg:355
 audit event numbers, aa:6
 auditing, aa:262
 auditsvc fails, aa:20
 close, aa:8
 ioctl, aa:9
 return token, aa:146 to aa:147
 security policy in man pages, dg:325
 system file
 labels-related kernel switch
 settings, la:47
 local tsolsys switch settings, la:31
 results of label configuration, ic:21
 sample Trusted Solaris entry, ic:21
 System Five Interprocess Communication,
 See System V IPC
 system information
 displaying, ic:120
 system operator
 defined, ug:14, ao:3
 system security
 privileges, ao:28
 violations, at:463
 system security configuration
 See also code examples
 API declarations, dg:340
 networks, ao:84 to ao:85
 variables described, dg:28
 when to check, dg:26
 system shell
 described, at:443
 system types, ic:40
 System V interprocess communication, See
 System V IPC
 System V IPC
 (System Five Interprocess
 Communication)
 See also message queues
 See also semaphore seats
 See also shared memory regions
 access checks, dg:217, dg:221
 API declarations, dg:228 to dg:230,
 dg:349
 described, dg:225
 discretionary access, dg:226
 IL floating, dg:227
 ipc audit class, aa:9
 ipc token, aa:139 to aa:140
 mandatory access, dg:226
 message queue floating, dg:28
 privileged tasks, dg:226
 privileges, ao:28
 privileges, defined, dg:51
 semaphore set floating, dg:28
 sensitivity label structure, dg:228
 shared memory floating, dg:28

system, privileges defined, dg:51
SYSTEM_ACCREDITATION_RANGE
value, dg:99
System_Admin folder
overview, ao:55 to ao:57
using, ic:78
using administrative actions, at:444
system_type profile keyword
description and values, ic:162
examples, ic:156 to ic:157

T

T6_AUDIT_ID value, dg:242
T6_AUDIT_INFO value, dg:242
T6_CLEARANCE value, dg:242
T6_GID value, dg:242
T6_GROUPS value, dg:242
T6_IL value, dg:242
T6_PID value, dg:242
T6_PRIVILEGES value, dg:242
T6_PROC_ATTR value, dg:242
T6_SESSION_IC value, dg:242
T6_SL value, dg:242
T6_UID value, dg:242
t6alloc_blk(3NTSOL)
code example, dg:248
declaration, dg:243
t6allocated_attrs(3NTSOL)
code example, dg:257
declaration, dg:243
t6attr_id_t structure, dg:241
t6attr_t structure, dg:241
t6clear_blk(3NTSOL)
code example, dg:256
declaration, dg:246
t6cmp_blk(3NTSOL)
code example, dg:256
declaration, dg:246
t6copy_blk(3NTSOL)
code example, dg:255
declaration, dg:246
t6dup_blk(3NTSOL)
code example, dg:255
declaration, dg:246
t6ext_attr(3NTSOL),
declaration, dg:247
t6free_blk(3NTSOL)
code example, dg:258
declaration, dg:243
t6get_attr(3NTSOL)
code example, dg:251
declaration, dg:245
t6get_endpt_default(3NTSOL)
code example, dg:250
declaration, dg:247
t6get_endpt_mask(3NTSOL)
code example, dg:250
declaration, dg:247
t6last_attr(3NTSOL)
code example, dg:253
declaration, dg:245
T6M_ALL_ATTRS value, dg:243
T6M_AUDIT_ID value, dg:243
T6M_AUDIT_INFO value, dg:243
T6M_CLEARANCE value, dg:243
T6M_GID value, dg:243
T6M_GROUPS value, dg:243
T6M_IL value, dg:243
T6M_NO_ATTRS value, dg:243
T6M_PID value, dg:243
T6M_PRIVILEGES value, dg:243
T6M_SESSION_ID value, dg:243
T6M_SL value, dg:243
T6M_UID value, dg:243
t6mask_t structure, dg:242
t6new_attr(3NTSOL)
code example, dg:252
declaration, dg:244
t6peek_attr(3NTSOL)
code example, dg:253
declaration, dg:245
t6present_attrs(3NTSOL)
code example, dg:257

declaration, dg:243
 t6recvfrom(3NTSOL)
 code example, dg:251
 declaration, dg:244
 t6sendto(3NTSOL)
 code example, dg:248
 declaration, dg:244
 t6set_attr(3NTSOL)
 code example, dg:248
 declaration, dg:245
 t6set_endpt_default(3NTSOL)
 code example, dg:250
 declaration, dg:247
 t6set_endpt_mask(3NTSOL)
 code example, dg:250
 declaration, dg:247
 t6size_attr(3NTSOL)
 code example, dg:254
 declaration, dg:246
 t6supported_attrs(3NTSOL)
 code example, dg:257
 declaration, dg:243
 tail command
 default profile, at:504, ao:160
 tape devices
 device_clean scripts, at:408
 tapes
 allocating at ADMIN_LOW, ic:75
 physical labeling, la:18
 tar command
 default profile, at:504, ao:160
 allocating a media device, at:411
 task maps
 Trusted Solaris installation and
 configuration, ic:9 to ic:13
 tbl command
 default profile, at:504, ao:160
 TCB
 (trusted computing base)
 defined, ug:2
 network flag, dg:38
 privileged applications, dg:55
 TCP address
 (Transmission Control Protocol
 address)
 templates
 assigning to hosts, at:282, at:286
 temporary file cannot be used, aa:20
 terminal ID, aa:17
 terminals
 resetting after I/O interrupts, ic:120
 terminating
 signal received during auditing
 shutdown, aa:20
 terminator commands, dg:184
 test command
 default profile, at:504, ao:160
 testfpriv command
 default profile, at:504, ao:160
 overview, ao:123
 testing and debugging
 applications, dg:328
 Text Editor
 differences in Trusted Solaris, ug:72
 text token
 described, aa:150
 praudit display, aa:151
 tfind command
 default profile, at:504, ao:160
 time command
 default profile, at:504, ao:160
 time stamps in audit files, aa:72
 time zones, ic:279 to ic:280
 timed out RPC error, ic:278
 time-date auditreduce command
 options, aa:79
 TLI
 (Transport Layer Interface)
 access checks, dg:223
 objects, dg:4
 See also communication endpoints
 See also TSIX library

tmpfile string and audit_warn script, aa:20
 TMPFS
 mounting in Trusted Solaris, at:329
 mounting procedure, at:343
 tnchkdb command
 default profile, at:504, ao:160
 overview, ao:104
 tnctl command
 default profile, at:504, ao:160
 overview, ao:104
 tnd command
 default profile, at:504, ao:160
 overview, ao:104
 tnidb database, ao:93
 tnidb file
 accessing, at:254
 tninfo command
 default profile, at:504, ao:160
 overview, ao:105
 tnrhdb database, ao:88
 tnrhdb file
 accessing, at:254
 installing, ic:80 to ic:83
 tnrhtp database, ao:90
 tnrhtp file
 accessing, at:254
 editing on the client, ic:109
 installing, ic:80 to ic:82
 token commands, dg:184
 token mapping daemon
 defined, ao:105
 tokmapctl command
 default profile, at:505, ao:161
 overview, ao:106
 tokmapd command
 default profile, at:505, ao:161
 overview, ao:105
 totaldisk rule keyword, ic:173
 touch command
 default profile, at:505, ao:161
 trailer pages
 computing the classification, la:77
 labeling, la:73 to la:75
 trailer token
 described, aa:151
 format, aa:151
 order in audit record, aa:68
 praudit display, aa:151
 translation
 adorned pathnames, dg:170
 authorizations
 ID to string, dg:84
 string to ID, dg:84
 clearances
 ASCII to binary, dg:163
 binary and hexadecimal, dg:164
 binary to ASCII, dg:162
 binary to ASCII, clipped, dg:163
 binary to hex, dg:165
 forms, dg:162
 reentrant routines, dg:165
 CMW labels
 ASCII to binary, dg:143
 binary to ASCII, dg:138
 binary to hex, dg:145
 input form, dg:142
 output form, dg:138
 font list, dg:300
 IIs
 binary to ASCII, dg:140
 input form, dg:142
 output form, dg:138
 to level, dg:128
 labels
 ASCII to binary
 correction, dg:142
 binary and ASCII rules, dg:136
 binary and hexadecimal, dg:142,
 dg:145
 binary to ASCII
 guidelines, dg:137
 flag values, dg:137, dg:142
 font list, dg:300
 forms, dg:136
 reentrant routines, dg:108

- view, dg:137
 - privileges
 - ID to string, dg:63
 - string to ID, dg:63
 - privileges needed, dg:93, dg:150
 - privileges, binary and ASCII, dg:62
 - reentrant binary to hex, dg:146
 - SLs
 - binary to ASCII, dg:138
 - input form, dg:142
 - output form, dg:138
- Transmission Control Protocol, *See* TCP
- Transport Layer Interface, *See* TLI
- Trash Can
 - differences in Trusted Solaris, ug:76
- troff command
 - default profile, at:505, ao:161
- Trojan horse protection, dg:52
- troubleshoot, aa:85 to aa:91
- troubleshooting, ic:277 to ic:278
 - I/O interrupt messages, ic:120
- true command
 - default profile, at:505, ao:161
- truss command
 - default profile, at:505, ao:161
- trusted applications
 - defined, ao:19
- trusted computing base, *See* TCB
- Trusted Desktop subpanel
 - defined, ug:76
- trusted network
 - editing local files, ic:80
- trusted network daemon
 - defined, ao:104
- trusted networks
 - See* networks
- trusted path
 - attribute flag, dg:38
- trusted path attribute, la:28
 - defined, ao:24
 - tools requiring, at:90
- trusted path indicator
 - defined, ao:2
- Trusted Path menu, at:5
 - described, ug:77 to ug:92
 - example, ug:42
- trusted path symbol
 - described, ug:69
 - example, ug:41 to ug:42
- trusted processes
 - defined, at:444
 - launching actions, at:444
 - passing inheritable privileges, at:454
- trusted programs, at:461
 - adding, at:464
- Trusted Security Information eXchange
 - library
 - See* TSIX library
- Trusted Security Information eXchange, *See* TSIX
- Trusted Security Interoperability Working Group, *See* TSIG
- trusted shared libraries, dg:326
- Trusted Solaris
 - changes to printing, at:364 to at:393
- Trusted Solaris boot diskette
 - copying to disk, ic:147
- Trusted Solaris CD
 - copying to install server's local disk, ic:120, ic:122
 - displaying mounted file systems, ic:120
 - image on local disk, ic:148, ic:150
 - mounting, ic:136, ic:148, ic:151
- Trusted Solaris configuration
 - adding users, ic:95
 - auditing NIS+ clients, ic:114
 - copying label encodings file to client, ic:107
 - creating mount points, ic:101
 - editing `tnrhtp` file on the client, ic:109
 - exporting directories, ic:102
 - logging on as a user, ic:113
 - modifying network files, ic:109
 - mounting unlabeled file systems, ic:100

NIS+ clients, ic:105 to ic:114
 protecting workstation, ic:73
 setting default routes, ic:78
 setting device policy, ic:89
 setting up home directories, ic:93,
 ic:111
 task maps, ic:9 to ic:13
 updating credentials, ic:91
 verifying that roles work, ic:97
 workstation without NIS+, ic:61 to
 ic:68

Trusted Solaris environment
 basic features, ug:64
 guided tour, ug:41 to ug:62
 overview, ug:2 to ug:15

Trusted Solaris installation
 config_data file, ic:126
 interactive
 networked workstations, ic:55 to
 ic:60
 log files, ic:59
 NIS+ clients, ic:105 to ic:114
 NIS+ root master, ic:69 to ic:104
 over networks, ic:115 to ic:138
 planning first two users, ic:48
 preparing custom JumpStart
 installation, ic:139 to ic:179
 setting default date and time, ic:128
 task maps, ic:9 to ic:13
Trusted Solaris configuration
 settings, ic:126
 worksheet examples, ic:259, ic:276
 workstation without NIS+, ic:61 to
 ic:68

Trusted Solaris software
 groups
 cluster names for profiles, ic:159
 profile examples, ic:156
 specifying packages, ic:162
 platforms supported, ic:38
 release or version
 installed rule keyword, ic:170
 osname rule keyword, ic:173

trusted streams
 API declarations, dg:353, dg:355
 objects, dg:4
 policy switch, dg:29

trusted stripe
 changing display, at:42
 defined, ug:64
 described, ug:69 to ug:70
 example, ug:41 to ug:42

Trusted X Window System, See X Window System

trustworthy programs, at:461

TSIG
 (Trusted Security Interoperability Working Group)

TSIX
 (Trusted Security Information eXchange)

TSIX host type
 described, at:260

tsix host type
 defined, ao:87

TSIX library
 See also code examples
 See also IPC
 API declarations, dg:243 to dg:247,
 dg:350
 attribute enumerations, dg:241
 attribute masks, dg:242
 attribute structure, dg:241
 changing client SL, dg:239
 changing security attributes, dg:239,
 dg:248
 client application, dg:266 to dg:269
 described, dg:237
 example application, dg:258 to
 dg:269
 information label floating, dg:239
 network accreditation range, dg:238
 privileged tasks, dg:239
 replying at equal SL, dg:239
 security attributes, dg:238
 server application, dg:259 to dg:265

tsol_attr flag
 described, at:323

TSOL_AUTH_FILE_DOWNGRADE
 authorization, dg:41
tsol_config keyword, ic:131
 TSOL_DB_SRC_FILES flag, dg:208
 TSOL_DB_SRC_NISPLUS flag, dg:208
 TSOL_DB_SRC_SWITCH flag, dg:208
tsol_enable configurable kernel
 switch, at:355
 TSOL_ENABLE_IL variable, dg:28,
 dg:29
tsol_enable_il_floating configurable
 kernel switch, at:355
 TSOL_ENABLE_IL_FLOATING
 variable, dg:28
 TSOL_FLOAT_SYSV_MSG_IL
 variable, dg:28
 TSOL_FLOAT_SYSV_SEM_IL
 variable, dg:28
 TSOL_FLOAT_SYSV_SHM_IL
 variable, dg:28
tsol_hide_upgraded_names configurable
 kernel switch
 defined, at:356
 TSOL_HIDE_UPGRADED_NAMES
 variable, dg:29
tsol_lbuild_create(3TSOL)
 declaration, dg:310
 description, dg:316
tsol_lbuild_destroy(3TSOL)
 declaration, dg:310
tsol_lbuild_get(3TSOL)
 code example, dg:312
 declaration, dg:310
tsol_lbuild_set(3TSOL)
 code example, dg:312
 declaration, dg:310
tsol_privs_debug
 use of, la:32
tsol_privs_debug configurable kernel
 switch
 defined, at:357
tsol_privs_debug switch
 described, at:460
tsol_reset_il_on_exec configurable kernel
 switch
 defined, at:356
 TSOL_RESET_IL_ON_EXEC
 variable, dg:29
tsol_separator.ps file, la:37
tsol_separator.ps file
 procedures
 specifying SLs to print instead of
 ILs, at:396
 TSOL_STR_LINB variable, dg:29
tsolprof(4TSOL)
 See also databases
tsolprof file
 accessing, dg:205
tsolsys switch settings, la:31
tsoluser(4TSOL)
 See also databases
tsoluser file
 accessing, dg:205
tsolxagent command
 default profile, at:505, ao:161
ttsession command
 default profile, at:505, ao:161
tty command
 default profile, at:505, ao:161
tunefs command
 default profile, at:505, ao:161
 two-person control
 adding privileges to programs, at:464
 during installation and
 configuration, ic:5

U

uadmin audit record, aa:258
 uauth audit record, aa:259
 UDP address
 (User Datagram Protocol address)

UFS
 mounting in Trusted Solaris, at:329

ufsdump command
 default profile, at:505, ao:161

ufsrestore command
 default profile, at:505, ao:161

uid field, dg:289

UIDs
 (user IDs)
 and roles, ug:80
 assigning, at:102, ao:65
 assigning to actions, ao:117
 assigning to commands, ao:117
 changed, dg:54
 effective
 alternative to privileges, at:440
 defaults, at:460
 defined, at:438
 effective UID of root, at:464
 execution profiles, ao:38
 in execution profiles, at:195, ao:21
 getting on window, dg:302
 getting on workstation, dg:302
 network interfaces, ao:93
 privilege to change, dg:56
 process attributes, ao:42
 remote host templates, ao:90
 user attributes, ao:37
 user ID (audit ID), aa:3, aa:17, aa:70

umount command
 default profile, at:505, ao:161

umount: old version audit
 record, aa:231

umountall command
 default profile, at:505, ao:161

uname audit record, aa:259

uname command, ic:120, ic:247
 default profile, at:505, ao:161

unbundled Sun applications
 adding, at:461

uncompress command
 default profile, at:505, ao:161

undefined labels, described, dg:113

uniq command
 default profile, at:505, ao:161

UNIX domain socket
 used by cron(1MTSOL) and its
 clients, at:76

UNIX Domain sockets, *See* IPC

UNIX publications
 general, ic:220
 security, ic:219

unlabeled host type
 creating (example), ic:80
 defined, ao:86
 described, at:269

unlink audit record, aa:231

unnamed value for *filesystems*, ic:161

unshare audit record, aa:260

unshare command
 default profile, at:505, ao:161
 Trusted Solaris modifications, ao:128

unshareall command
 default profile, at:505, ao:161

upgrade file sensitivity label
 authorization, la:9

upgrade installation
 profile keywords, ic:161

upgraded names
 defined, at:356
 hide, dg:29

upgrading labels
 guidelines, dg:96
 privileges needed, dg:93, dg:94
 X Window System, dg:288

usedisk profile keyword
 description and values, ic:163
 dontuse and, ic:159

user accounts
 See also accounts
 See also User Manager

user accreditation range
 defined, ao:8
 described, at:317
 minimum clearance, ao:9

- minimum sensitivity label, ao:9
- user audit fields, aa:14 to aa:16
- user clearances
 - defined, ug:5
 - described, at:317
- user comments
 - assigning, ao:66
- user database, *See* databases
- User Datagram Protocol, *See* UDP
- user ID (audit ID), aa:3
- user IDs, *See* UIDs
- User Manager
 - assigning account type, at:105, ao:66
 - assigning GIDs, ao:65
 - assigning login shells, ao:66
 - assigning passwords, at:106 to at:113
 - assigning profiles in the desired order, at:442
 - assigning profiles to accounts, at:454
 - assigning UIDs, ao:65
 - assigning user comments, ao:66
 - assigning user names, ao:65
 - data entries explained, at:100 to at:123
 - dialog boxes
 - Audit, ao:63
 - Home, ao:63, ao:73 to ao:74
 - Identity, ao:63, ao:64 to ao:67
 - Idle, ao:63, ao:81 to ao:82
 - Labels, ao:63, ao:75 to ao:77
 - Load dialog box, ao:60
 - Navigator, ao:62
 - Password, ao:63, ao:67 to ao:72
 - Profiles, ao:63, ao:77 to ao:79
 - Roles, ao:63, ao:79 to ao:80
 - Edit menu, ao:61
 - Home dialog box, at:113 to at:115
 - identity dialog box, at:102
 - Idle dialog box, at:122 to at:123
 - Labels dialog box, at:116 to at:119
 - launching, ao:60
 - main window, ao:61
 - overview, ao:60 to ao:82
 - procedures, at:124 to at:155
 - Profile dialog box, at:120 to at:121
 - required authorizations, at:92, at:94
 - Roles dialog box, at:122
 - setting labels, la:33
 - worksheet, at:192
- user names
 - assigning, at:102, ao:65
- USER_ACCREDITATION_RANGE
 - value, dg:99
- userent_t structure, dg:206
- user-level events
 - audit number range, aa:6
 - audit records, aa:236 to aa:260
 - audit tokens, aa:68
 - auditconfig command
 - options, aa:24
 - described, aa:6
- usermgr command
 - default profile, at:505, ao:161
- users
 - See also* User Manager
 - ACL entry, ug:97
 - administering, ao:59 to ao:82
 - attributes, ao:37
 - auditing normal users, aa:14
 - exceptions to audit flags, aa:51
 - first two created, ic:48
 - logon during configuration, ic:113
 - planning account information, ic:49
 - planning account security, ic:50
 - session range, ao:11
- usertype field, dg:206
- /usr file systems, ic:40
- /usr/bin/at audit record
 - at-create crontab, aa:239
 - at-delete atjob, aa:239
 - at-permission, aa:240
- /usr/bin/crontab audit record
 - crontab, aa:243
 - cron-invoke atjob, aa:243
 - crontab-crontab
 - created, aa:242

crontab-crontab
 deleted, aa:242
 crontab-permission, aa:243
 /usr/bin/login audit record
 logout, aa:248
 rlogin, aa:247
 telnet login, aa:247
 terminal login, aa:247
 /usr/bin/passwd: change
 password audit record, aa:250
 /usr/bin/su audit record, aa:257
 /usr/lib/nfs/mountd audit record
 NFS mount request, aa:249
 NFS unmount request, aa:250
 /usr/sbin/allocate audit record
 allocate-list device
 failure, aa:238
 allocate-list device
 success, aa:238
 deallocate device, aa:237
 deallocate device
 failure, aa:238
 device allocate
 failure, aa:237
 device allocate
 success, aa:237
 /usr/sbin/halt audit record, aa:245
 /usr/sbin/in.ftpd audit
 record, aa:246
 /usr/sbin/in.rexecd audit
 record, aa:253
 /usr/sbin/in.rshd audit
 record, aa:254
 /usr/sbin/inetd audit
 record, aa:246
 /usr/sbin/reboot audit
 record, aa:252
 /usr/sbin/rpc.rexd audit
 record, aa:253
 utilities
 C library functions, aa:263
 headers, tables, and macros, aa:264
 maintenance commands, aa:261
 system calls, aa:262
 utime audit record, aa:232
 utimes audit record, aa:232
 utssys - fusers audit
 record, aa:233

V

valid clearances
 checking, dg:161
 ensuring, dg:152
 valid labels
 accreditation ranges, dg:131
 checking, dg:133
 ensuring, dg:100
value
 classification keyword, la:54
 /var/sadm/system/logs/install_
 log file, ic:59
 /var/sadm/begin.log file, ic:182
 /var/sadm/finish.log file, ic:184
 variables
 PASSWD, ic:187
 SI_CONFIG_DIR, ic:185
 SI_PROFILE, ic:183
 SI_SYS_STATE, ic:188
 SYS_MEMSIZE, ic:189
 vers_len field, dg:99
 version of Trusted Solaris software
 installed rule keyword, ic:170
 osname rule keyword, ic:173
 VERSION section
 label_encodings example, la:153
 version string retrieval, dg:112
 vfork audit record, aa:233
 vfstab file, ic:161
 vfstab_adjunct file
 code example, dg:31
 retrieving entries, dg:31

VIEW_EXTERNAL flag, dg:137
VIEW_INTERNAL flag, dg:137
virtual memory requirements, ic:38
vmstat command
 default profile, at:505, ao:161
vtrace audit record, aa:234

W

well-formed labels
 defined, ao:6
whereis command
 default profile, at:506, ao:162
which command
 default profile, at:506, ao:162
who command
 default profile, at:506, ao:162
whoami command
 default profile, at:506, ao:162
win_config privilege, dg:287
win_dac_read privilege, dg:287
win_dac_write privilege, dg:287
win_devices privilege, dg:287
win_dga privilege, dg:287
win_downgrade_il privilege, dg:287
win_downgrade_sl privilege, dg:287
win_fontpath privilege, dg:288
win_mac_read privilege, dg:287
win_mac_write privilege, dg:287
win_nofloat privilege, dg:288
win_upgrade_il privilege, dg:288
win_upgrade_sl privilege, dg:288
window manager, at:444
Window SL field
 described, ug:69
window system
 differences in Trusted Solaris, la:10
 trusted processes, at:444
 passing inheritable
 privileges, at:454

windows
 See also X Window System
 authorizations, ao:25
 client, security policy, dg:285
 defaults, dg:286
 described, dg:283
 moving data between, ug:56 to ug:58
 override-redirect, security
 policy, dg:285
 privileges, dg:287, ao:28
 root, security policy, dg:285
 security policy, dg:284
word order requirements
 label_encodings file
 word order requirements, la:52
work groups
 represented by label
 compartments, la:7
worksheets
 blanks, ic:221 to ic:239
 examples, ic:260 to ic:276
 for hosts, at:485
 for user accounts, at:192
Workspace Menu
 as trusted process, at:444
 modifying, at:467
workspace switch area
 controls, ug:92
 differences in Trusted Solaris, ug:71
workspaces
 administrative
 using, at:7 to at:24
 administrative role, la:11
 changing, ug:47 to ug:50
 changing to admin_high, aa:61
 changing what displays after
 login, la:11
 initial, la:10
 labeled, la:10
 relabeling, la:11
workstation configuration
 system privileges, ao:28
workstations
 booting, ic:91

- planning audit space, aa:32
- planning security, ic:44
- protecting, ic:73
- wrapping lines in rules, ic:169
- write access
 - IL conjoin, dg:90
 - overview, ug:7
 - security policy, dg:14
- write equal, dg:14
- write up, dg:14
- writeaudit command
 - default profile, at:506, ao:162
- WURD
 - defined, ug:7

X

- X server
 - window privileges, ao:28
- X Window System
 - See also* code examples
 - API declarations, dg:291 to dg:297, dg:352
 - authorizations, defined, dg:80
 - client attributes structure, dg:289
 - client window, dg:285
 - defaults, dg:286
 - input devices, dg:285
 - label clipping API
 - declarations, dg:346
 - Motif source code, dg:303 to dg:307
 - object attribute structure, dg:289
 - object type definition, dg:289
 - objects, dg:3, dg:283
 - override-redirect, dg:285
 - predefined atoms, dg:286
 - privileged tasks, dg:287
 - privileges, defined, dg:51
 - properties, dg:284
 - property attribute structure, dg:289
 - protocol extensions, dg:281
 - resource file, dg:303
 - root window, dg:285
 - security attributes
 - contrast with Solaris, dg:12

- described, dg:283
- security policy, dg:284
- Selection Manager, dg:286
- server control, dg:285
- xatom token
 - described, aa:152
 - praudit display, aa:152
- xbclearatos(3TSOL),
 - declaration, dg:297
- xbcltos(3TSOL), declaration, dg:297
- xbiltos(3TSOL), declaration, dg:297
- xbsltos(3TSOL)
 - code example, dg:300
 - declaration, dg:297
- xcolormap token
 - described, aa:152
 - praudit display, aa:153
- xcursor token
 - described, aa:153
 - praudit display, aa:153
- xfont token
 - described, aa:153
 - praudit display, aa:153
- xgc token
 - described, aa:153
 - praudit display, aa:154
- xhost command
 - default profile, at:506, ao:162
- Xlib
 - API declarations, dg:291 to dg:297
 - described, dg:10
 - objects, dg:283
- xmknod audit record, aa:234
- xp_tsol_incoming_attrsp
 - field, dg:273
- xp_tsol_incoming_new_attrsp
 - field, dg:273
- xp_tsol_outgoing_attrsp
 - field, dg:273
- xpixmap token
 - described, aa:154
 - praudit display, aa:154

xproperty token
 described, aa:154
 praudit display, aa:155
xselect token
 described, aa:155
 praudit display, aa:155
X-Sender-Information-Label, la:18
xstat audit record, aa:235
XTsolClientAttributes
 structure, dg:289
XTSOLgetClientAttributes(3X11TSOL), declaration, dg:291
XTSOLgetPropAttributes(3X11TSOL), declaration, dg:291
XTSOLgetPropLabel(3X11TSOL), declaration, dg:293
XTSOLgetPropUID(3X11TSOL), declaration, dg:294
XTSOLgetResAttributes(3X11TSOL)
 code example, dg:299
 declaration, dg:291
XTSOLgetResLabel(3X11TSOL)
 code example, dg:301
 declaration, dg:292
XTSOLgetResUID(3X11TSOL)
 code example, dg:302
 declaration, dg:292
XTSOLgetSSHeight(3X11TSOL), declaration, dg:296
XTSOLgetWindowIIL(3X11TSOL), declaration, dg:293
XTSOLgetWorkstationOwner(3X11TSOL)
 code example, dg:302
 declaration, dg:294
XTSOLIsWindowTrusted(3X11TSOL), declaration, dg:295
XTSOLmakeTPWindow(3X11TSOL), declaration, dg:295
XTsolPropAttributes
 structure, dg:289
XTsolResAttributes structure, dg:289
XTSOLsetPropLabel(3X11TSOL), declaration, dg:293
XTSOLsetPropUID(3X11TSOL), declaration, dg:294
XTSOLsetResLabel(3X11TSOL)
 code example, dg:302
 declaration, dg:292
XTSOLsetSessionHI(3X11TSOL), declaration, dg:295
XTSOLsetSessionLO(3X11TSOL), declaration, dg:295
XTSOLsetSSHeight(3X11TSOL), declaration, dg:296
XTSOLsetWindowIIL(3X11TSOL), declaration, dg:293
XTSOLsetWorkstationOwner(3X11TSOL), declaration, dg:294
Xtsolusersession script, at:444
xwindow token
 described, aa:155
 praudit display, aa:156

Z

zones, time, ic:279 to ic:280