

# Trusted Solaris Global Index

**Sun Microsystems Federal, Inc.**  
A Sun Microsystems, Inc. Business  
901 San Antonio Road  
Palo Alto, CA 94303  
U.S.A.

Part No: 805-8032-10  
Revision A, August 1998



THE NETWORK IS THE COMPUTER™

Copyright 1998 Sun Microsystems, Inc. 901 San Antonio Road, Palo Alto, California 94303 U.S.A. All rights reserved.

This product or document is protected by copyright and distributed under licenses restricting its use, copying, distribution, and decompilation. No part of this product or document may be reproduced in any form by any means without prior written authorization of Sun and its licensors, if any. Third-party software, including font technology, is copyrighted and licensed from Sun suppliers.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, SunSoft, SunDocs, SunExpress, and SunOS, OpenWindows, NFS, Sun Ultra, Ultra, JumpStart, Solaris, Solstice, Solstice AdminSuite, Solstice AdminTools, Solstice Autoclient, Solstice CacheOS, DiskSuite, ToolTalk, X11/NeWS, Trusted NeWSprint, IPC, OpenBoot, SHIELD, XView, SunInstall, AnswerBook, and Trusted Solaris are trademarks, registered trademarks, or service marks of Sun Microsystems, Inc. in the U.S. and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc. X/Open<sup>®</sup> is a registered trademark and "X" device is a trademark of X/Open Company Limited, Netscape is a trademark of Netscape Communications Corporation, and PostScript is a trademark of Adobe Systems, Incorporated.

The OPEN LOOK and Sun<sup>™</sup> Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

**RESTRICTED RIGHTS:** Use, duplication, or disclosure by the U.S. Government is subject to restrictions of FAR 52.227-14(g)(2)(6/87) and FAR 52.227-19(6/87), or DFAR 252.227-7015(b)(6/95) and DFAR 227.7202-3(a).

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright 1998 Sun Microsystems, Inc., 901 San Antonio Road, Palo Alto, Californie 94303 Etats-Unis. Tous droits réservés.

Ce produit ou document est protégé par un copyright et distribué avec des licences qui en restreignent l'utilisation, la copie, la distribution, et la décompilation. Aucune partie de ce produit ou document ne peut être reproduite sous aucune forme, par quelque moyen que ce soit, sans l'autorisation préalable et écrite de Sun et de ses bailleurs de licence, s'il y en a. Le logiciel détenu par des tiers, et qui comprend la technologie relative aux polices de caractères, est protégé par un copyright et licencié par des fournisseurs de Sun.

Des parties de ce produit pourront être dérivées des systèmes Berkeley BSD licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, SunSoft, SunDocs, SunExpress, et Solaris SunOS, OpenWindows, NFS, Sun Ultra, Ultra, JumpStart, Solstice, Solstice AdminSuite, Solstice AdminTools, Solstice Autoclient, Solstice CacheOS, DiskSuite, ToolTalk, X11/NeWS, Trusted NeWSprint, IPC, OpenBoot, SHIELD, XView, SunInstall, AnswerBook, et Trusted Solaris sont des marques de fabrique ou des marques déposées, ou marques de service, de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays. Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc. X/Open<sup>®</sup> est une marque enregistrées et "X" device est une marque de X/Open Company Limited, Netscape est une marque de Netscape Communications Corporation, et PostScript est une marque de Adobe Systems, Incorporated.

L'interface d'utilisation graphique OPEN LOOK et Sun<sup>™</sup> a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciés de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui en outre se conforment aux licences écrites de Sun.

CETTE PUBLICATION EST FOURNIE "EN L'ETAT" ET AUCUNE GARANTIE, EXPRESSE OU IMPLICITE, N'EST ACCORDEE, Y COMPRIS DES GARANTIES CONCERNANT LA VALEUR MARCHANDE, L'APTITUDE DE LA PUBLICATION A REpondre A UNE UTILISATION PARTICULIERE, OU LE FAIT QU'ELLE NE SOIT PAS CONTREFAISANTE DE PRODUIT DE TIERS. CE DENI DE GARANTIE NE S'APPLIQUERAIT PAS, DANS LA MESURE OU IL SERAIT TENU JURIDIQUEMENT NUL ET NON AVENU.



## *Contents*

---

Global Index.....	1
-------------------	---



## *Preface*

---

This document provides a global index that covers the following manuals:

- *Trusted Solaris Audit Administration* (805-8027-10)
- *Trusted Solaris Administration Overview* (805-8024-10)
- *Trusted Solaris Administrator's Procedures* (805-8025-10)
- *Compartmented Mode Workstation Labeling: Encodings Format* (805-8004-10)
- *Trusted Solaris Developer's Guide* (805-8031-10)
- *Trusted Solaris Label Administration* (805-8028-10)
- *Trusted Solaris Installation and Configuration* (805-8026-10)
- *Trusted Solaris 2.5.1 Transition Guide* (805-8030-10)
- *Trusted Solaris User's Guide* (805-8023-10)

### *How This Index is Organized*

The global index begins on page 1 and uses the following prefixes to identify the manuals referred to:

- aa-Audit Admin (*Trusted Solaris Audit Administration*)
- ao-Admin Overview (*Trusted Solaris Administration Overview*)
- ap-Admin Procedures (*Trusted Solaris Administrator's Procedures*)
- cm-CMW Labeling (*Compartmented Mode Workstation Labeling: Encodings Format*)
- dg-Developer's Guide (*Trusted Solaris Developer's Guide*)

- 
- ic-Installation & Configuration (*Trusted Solaris Installation and Configuration*)
  - la-Label Admin (*Trusted Solaris Label Administration*)
  - tg-Transition Guide (*Trusted Solaris 2.5.1 Transition Guide*)
  - ug-User's Guide (*Trusted Solaris User's Guide*)

# Global Index

---

## Symbols

- (minus sign)
  - in begin and finish scripts, ic:188
  - in rules, ic:163
- ! (exclamation mark) rule field, ic:160
- audit flag prefix, aa:9 to aa:10
- # (pound sign)
  - in profiles, ic:147
  - in rules, ic:163
- && (ampersands) rule field, ic:160
- + audit flag prefix, aa:9 to aa:10
- ... (ellipsis points) rule field, ic:160
- = (equals sign) in profile field, ic:174
- > prompt, changing to ok prompt, ic:54
- [] (brackets) rule field, ic:160
- \ (backslash) in rules, ic:163
- ^- audit flag prefix, aa:9 to aa:10
- ^+ audit flag prefix, aa:9 to aa:10

## A

- aa audit class, aa:100 to aa:101
- aa audit flag, aa:98
- abbreviations in names, dg:334
- abort\_enable
  - switch in `/etc/system`, ap:419

- accept command
  - modified for Trusted Solaris, ap:465
- access
  - administrator responsibilities, ap:38
  - checks
    - executing a file, dg:23
    - IPC files, dg:223
    - mapped memory, dg:226
    - MLDs, dg:170
    - network, dg:223, dg:227
    - opening a file, dg:20
    - pipes, dg:224, dg:225
    - process tracing, dg:226
    - processes, dg:223
    - PTYs, dg:225
    - signals, dg:226
    - SLDs, dg:170
    - sockets, dg:229
    - System V IPC, dg:223, dg:227
    - TLI, dg:229
    - writing to a file, dg:22
    - X Window System, dg:290
  - discretionary operations, dg:17
  - file
    - overview, ao:35 to ao:46
  - file labels, dg:95
  - file privileges, dg:57
  - file systems
    - code examples, dg:19

---

- privileges, dg:18
  - security policy, dg:17
- guidelines for SLs, dg:97
- mandatory operations, dg:17
- multilevel port connections, dg:228
- protection, dg:89
- review of concepts, ap:361 to ap:374

access audit record, aa:179

access control

- example, la:16
- using labels and clearances, la:5
- using SLs
  - def, la:15

access control lists, *See* ACLs

access policy

- devices, ap:485
- files, directories and file systems, ap:362

access related, cm:25, cm:36, cm:42, cm:98, cm:113, cm:114, cm:129 to cm:133

ACCESS\_RELATED flag, dg:139

access-related words

- defined, la:87

account label ranges

- defined, la:6
- overview, ao:10 to ao:11
- setting minimum SL
  - setting on user and role accounts, la:43

account SL ranges

- assigning, ao:77

account status

- Password dialog box, ao:73

accounts

- assigning account type, ap:127
- assigning clearances, ap:137
- assigning comments, ap:126
- assigning execution profiles, ap:141 to ap:142
- assigning home directories, ap:134 to ap:136
- assigning idle time, ap:143 to ap:144
- assigning labels, ap:136 to ap:140
- assigning passwords, ap:128 to ap:134
- assigning roles, ap:143
- assigning shells, ap:126
- assigning user information, ap:124
- authorizations for setting up, ap:74
- configuring, *See* User Manager
- creating the first users, ic:88
- deletion precautions, ap:40
- division of setup tasks, ap:73 to ap:74
- label range
  - example, ao:11
  - overview, ao:10 to ao:11
- managing, ap:69 to ap:103
- planning, ap:70 to ap:72
- preconditions for setup, ap:70
- procedures for setting up, ap:144 to ap:175
- roles, ug:12
- security precautions, ap:37 to ap:41
- setting labels, la:43
- startup files, ap:77 to ap:103
- users, ug:20
- worksheet, ap:212

accreditation checking

- networks, ao:105

accreditation checks, ap:285 to ap:288

- overview, ao:100 to ao:102

accreditation range, la:6, cm:16, cm:17, cm:81 to cm:82, cm:112, cm:113, cm:115, cm:116, cm:119, cm:141

- system, cm:2, cm:47, cm:51, cm:141
- user, cm:2, cm:4, cm:13, cm:16, cm:47 to cm:52, cm:141, cm:142

ACCREDITATION RANGE section

- label\_encodings example, la:171

accreditation ranges, la:34

- See also* label ranges
- checking, dg:133, dg:134
- described, ap:365
- label encodings file, ao:5
- network interfaces, ao:96
- networks, dg:244
- overview, ao:7 to ao:9
- structurs, dg:101

---

system, ao:7  
 user, ao:8  
 acct audit record, aa:180  
 acl token  
   described, aa:150  
   praudit display, aa:151  
 ACLs  
   (access control lists)  
   adding entries, ug:108 to ug:109  
   changing entries, ug:110 to ug:111  
   defined, ug:102 to ug:103  
   deleting entries, ug:112  
   described, ap:361  
   displaying entries, ug:106 to ug:107  
   information on, dg:33  
   introduction, ug:4  
 ACLs (access control lists), tg:62  
 actions  
   accessing administrative  
     actions, ap:12 to ap:15  
   adding new administrative, ap:29 to  
     ap:31  
   adding outside the System\_Admin  
     folder, ap:31  
   administrative  
     Add Allocatable Device, ap:13  
     Admin Editor, ap:15  
     Audit Classes, ap:13  
     Audit Control, ap:13  
     Audit Events, ap:13  
     Audit Startup, ap:13  
     Audit Users, ap:13  
     Check Encodings, ap:13  
     Check TN Files, ap:13  
     Check TN NIS+ Tables, ap:13  
     Configure Selection  
       Confirmation, ap:13  
     Create NIS+ Client, ap:13  
     Create NIS+ Server, ap:13  
     Edit Encodings, ap:13  
     Name Service Switch, ap:13  
     Set Mail Options, ap:13  
     Set Mount Attributes, ap:14  
     Set Mount Points, ap:14  
     Set Tsol Gateways, ap:14  
     Share Filesystems, ap:14  
   assigning inheritable  
     privileges, dg:339, ao:31  
   assigning to execution  
     profiles, ap:243, ao:122  
   creating, dg:339  
   defined, ap:525  
   in execution profiles, ap:215, ao:21  
   linked list data type, dg:214  
   Name Service Switch, ap:304  
   profile assignments and security  
     attributes, ap:628 to ap:635  
   restricted by account profiles, ap:528  
   running, ao:25  
   Share Filesystem, ap:403  
   SL at launch time, ap:14  
   using actions, ap:546  
 actions field, dg:213  
 actname field, dg:214  
 ad audit flag, aa:98  
 Add Allocatable Device action  
   described, ap:13  
 Add Workspace menu item  
   described, ug:81  
 add\_allocatable(1MVSOL)  
   command, ap:13  
   described, ap:502  
 add\_drv audit record, aa:301  
 add\_drv command  
   Trusted Solaris modifications, ao:146  
 add\_install\_client command  
   custom JumpStart example, ic:245 to  
     ic:246  
   example, ic:124, ic:143  
   install server setup, ic:122 to ic:124  
   JumpStart directory access, ic:144  
   syntax, ic:123, ic:125, ic:143  
 adjtime audit record, aa:180  
 adjudicate, cm:5, cm:7, cm:34, cm:35  
 adjudication, cm:5, cm:7 to cm:13, cm:34,  
   cm:35, cm:73 to cm:79  
 adjunct file, *See* vfstab\_  
   adjunct(4TSOL)

---

Admin Editor

- opening administrative action, ic38 to ic41
- using to create file, ic40

Admin Editor action, ap:15

- described, ap:13

Admin Editor audit record, aa:302

admin role, *See* system administrator

admin tools

- authorizations, ao:27
- overview, ao:48 to ao:58

ADMIN\_HIGH label

- defined, dg:115, ao:6
- initialize to, dg:115
- overview, la:26
- replacing with CIPSO label, ap:350
- running applications, dg:15

ADMIN\_LOW label

- defined, dg:115, ao:6
- initial administrative workspace label, la:38
- initialize to, dg:115
- installing publicly available software, ap:520
- overview, la:26
- running applications, dg:15

administration commands

- new, tg:45
- summary description, tg:42

administration GUI

- distributed, tg:15
- local, tg:17

administration labels

- defined, ao:6
- visibility, ao:78

administrative actions

- accessing, ap:12 to ap:15
- creating, ap:29 to ap:31
- in Solstice\_Apps folder, ic35, ap:26, ap:28
- in System\_Admin folder, ic40
- introduced, ap:528

administrative labels

- changing names, la:28, la:112
- displaying and hiding, la:112
- displaying substitute names, la:119
- number defined for each label type, la:26
- overriding the system default view, la:44
- overview, la:26
- setting view on user and role accounts, la:43
- specifying if users see names, la:28
- visible to the install team, ic23
- workspace use, la:38

administrative roles

*See also* roles

- adding to three /etc files, ic:67
- assuming, aa:42
  - background, ap:5
  - procedure, ap:15 to ap:23
- changing workspace SLs, ap:24
- configuring
  - See also* User Manager
- configuring Trusted Solaris, ic:13
- defined, ao:26
- described, ap:107 to ap:108
- login shell, tg:4
- password, ap:5
- review, la:37
- switching workspaces, ap:24
- verifying during configuration, ic:92
- workspaces, la:14
  - display when role is assumed, ap:5
  - using, ap:8 to ap:29

adminvi command

- overview, ao:150

adminvi(IMTSOL) command

- default editor for administrative actions, ap:14
- aliasing vi(1), ap:117
- described, ap:15

adorned pathnames

- described, ap:365, dg:172
- translating, dg:172

adornfc(3TSOL)

- code example, dg:179

---

declaration, dg:177  
 adornments  
   defined, ao:17  
   described, ap:56  
 advisory labels, tg:18  
   *See also* ILS  
   synonym for ILS, ug:14  
 ahl<sub>t</sub> policy  
   flag, aa:24  
 algorithms  
   IL floating, dg:92  
   process privileges, dg:54  
 algorithms for process privileges, tg:57  
 aliases  
   creating audit\_warn mail  
     alias, aa:52  
   setting up, ap:184, ap:187  
 all  
   audit flag, aa:98  
     caution for using, aa:9  
   in user audit fields, aa:14  
   value for *filesys*, ic:152  
 all audit class, aa:131  
 All execution profile  
   allowing standard UNIX access to  
     commands and  
     actions, ap:526  
   ordering in an account's profile  
     list, ap:527  
 ALL\_ENTRIES flag, dg:139  
 allhard string with audit\_warn  
   script, aa:19 to aa:20  
 allocate audit record  
   deallocate device, aa:311  
   deallocate device  
     failure, aa:311  
   device allocate  
     failure, aa:303  
   device allocate  
     success, aa:302  
   list device failure, aa:304  
   list device success, aa:303  
 allocate command  
   Trusted Solaris modifications, ao:146  
 Allocate Device menu item  
   described, ug:89 to ug:93  
 allocate error state  
   caused by failure of  
     eject(1), ap:404, ap:497  
   defined, ap:495  
   procedure for correcting, ap:509  
 allocate(1M<sub>T</sub>SOL) command  
   described, ap:502  
 allocation of devices  
   from Front Panel, tg:34, tg:36  
   from Trusted Path menu, tg:53  
 allowed privileges, ap:524  
   *See also* privilege sets  
   assigning, ao:30  
   defined, dg:54, ao:28  
   on file systems, ao:134, dg:33  
   set to none during write, dg:57  
   turning off, dg:70  
 allsoft string with audit\_warn  
   script, aa:19  
 alternative installation programs, ic:188  
 always-audit flags  
   described, aa:14 to aa:15  
   process preselection mask, aa:16  
 ampersands (&&) rule field, ic:160  
*aname*  
   classification keyword, la:63  
 ancillary files  
   for allocatable devices, ap:495  
   tar(1<sub>T</sub>SOL), ap:500  
 AND rule field, ic:160  
 angle bracket (>) prompt, ic:54  
 AnswerBook  
   assigning to profiles, ap:573  
   installation procedure, ap:571  
   installing and viewing, ap:557 to  
     ap:558  
   viewing procedure, ap:574  
*any*  
   rule keyword  
     description and values, ic:163  
     rootdisk matching, ic:168  
     slice value for *filesys*, ic:152

---

ao audit class, aa:101 to aa:104  
 ao audit flag, aa:98  
 ap audit class, aa:104  
 ap audit flag, aa:98  
 APIs  
     (application programming interfaces)  
     *See also* library routines  
     *See also* system calls  
     declarations, dg:345 to dg:367  
     list of types, dg:5 to dg:12  
     security policy on man pages, dg:331  
 application auditing  
     *See also* auditing  
     *See also* code examples  
     API declarations, dg:353  
     appending record  
         information, dg:196  
     argument information, dg:207  
     audit trail, dg:191  
     command line arguments, dg:208  
     control commands, dg:188  
     creating audit records, dg:192  
     creating parallel audit  
         records, dg:202  
     described, dg:186  
     event definition numbers, dg:186  
     information label, dg:196  
     invalid call, dg:192  
     IPC identifier, dg:210  
     preselection mask, dg:200  
     privilege sets, dg:209  
     privileged tasks, dg:46, dg:187  
     process preselection mask, dg:190  
     queueing record information, dg:198  
     return token, dg:195  
     return values, dg:195  
     save area, dg:203  
     sensitivity label, dg:205  
     server area, dg:205  
     subject token, dg:195  
     terminator command, dg:188  
     token commands, dg:188  
     valid call, dg:193  
 Application Manager  
     accessing applications, ao:25  
     as trusted process, ap:527  
     differences in Trusted Solaris, ug:79  
     launching, ao:49  
     modified for Trusted Solaris, tg:35  
     opening, ic:34  
     passing inheritable privileges, ap:538  
     using AdminSuite, ap:10  
     using Solstice\_Apps, ap:10  
     using System\_Admin, ap:10  
 application programming interfaces, *See*  
     APIs  
 applications  
     *See also* application auditing  
     accessing, ao:25  
     administering, ao:19  
     administrative, dg:15, tg:15, tg:17  
     assigning forced privileges, ap:563  
     graphical user interface  
         toolkits, tg:73  
     importing, ap:522  
     integration, dg:338  
     MLDs, dg:171  
     porting, tg:38, tg:40  
     possible modifications, tg:20  
     setting up with a real UID of 0, ap:560  
     setting up with effective UID of  
         0, ap:560  
     testing and debugging, dg:335  
     testing for privileges, tg:41  
     user, dg:16  
 arbitrary token  
     described, aa:151  
     praudit display, aa:152  
 arch rule keyword, ic:163  
 archived information  
     affixing physical labels, la:24  
 areas of interest  
     represented by compartment, la:10  
 arg token  
     described, aa:153  
     praudit display, aa:153

---

argclass field, dg:214  
 argcount field, dg:214  
 arge policy  
     exec\_env token and, aa:155  
 argmode field, dg:214  
 argtype field, dg:214  
 argv policy  
     exec\_args token and, aa:155  
 arp command  
     Trusted Solaris modifications, ao:106  
 as audit class, aa:118  
 as audit flag, aa:98  
 ASCII  
     *See also* translation  
     color names, dg:136  
 assigning privileges  
     allowed, ao:30  
     forced, ao:30  
     inheritable, ao:31  
     overview, ao:27, ao:33  
 at command  
     administrative differences, ap:90 to  
         ap:99  
     running privileged commands, ap:92  
     Trusted Solaris changes, ap:98  
 at audit record  
     at-create crontab, aa:304  
     at-delete atjob, aa:305  
     at-permission, aa:305  
 at.allow file, ap:93  
 at.deny file, ap:93  
 atohexlabel command  
     overview, ao:142  
 atoms, predefined, dg:292  
 atq command  
     administrative differences, ap:90 to  
         ap:99  
 atrm command  
     administrative differences, ap:90 to  
         ap:99  
 attr token  
     described, aa:153  
     praudit display, aa:154  
 attr\_mac\_policy, ap:485  
 attribute flags  
     *See also* security attribute flags  
     file systems, ao:134  
 attributes  
     *See also* security attribute flags  
     *See also* security attributes  
 audio coprocessor, ap:498  
 AUDIO\_DRAIN ioctl  
     run by device\_  
         clean(1MTSOL), ap:498  
 AUDIO\_SETINFO ioctl  
     resetting device to default, ap:498  
 AUDIOGETREG ioctl  
     run by device\_  
         clean(1MTSOL), ap:498  
 audit audit record, aa:181, aa:306  
 audit classes  
     adding, aa:56  
     changing definitions, aa:5  
     mapping events, aa:4  
     overview, aa:4 to aa:6, ao:114  
     process preselection mask, dg:190  
     selecting for auditing, aa:4  
     setting mappings for attributable  
         events, aa:94  
     setting mappings for non-attributable  
         events, aa:95  
     third-party, dg:186  
 Audit Classes action  
     described, ap:13  
 audit clients, aa:34  
 audit command  
     overview, ao:116  
 Audit Control action  
     described, ap:13  
 audit daemon  
     audit trail creation, aa:17 to aa:18,  
         aa:68  
     audit\_startup file, aa:4  
     audit\_warn script  
         conditions invoking, aa:19 to  
             aa:20  
         described, aa:17, aa:18 to aa:19

---

- directories suitable to, aa:18
- enabling auditing, aa:4
- functions, aa:17
- order audit files are opened, aa:12
- rereading the `audit_control` file, aa:12
- starting, aa:64
- starting manually, aa:94
- terminating, aa:64
- audit directories
  - creating, aa:46
  - mounting, aa:47
- audit events
  - adding, aa:57
  - `audit_event` file
    - audit event type, aa:69
  - audited by default, aa:3
  - C library functions, aa:341
  - categories, aa:6
  - finding in audit trail, aa:82
  - including in audit trail, aa:4
  - kernel events
    - audit tokens, aa:70
    - `auditconfig` command
      - options, aa:23
    - described, aa:6
  - mapping to classes, aa:4
  - non-attributable, aa:7
  - number ranges, aa:6
  - numbers, aa:6
  - numbers of system calls, aa:6
  - overview, aa:4, aa:7
  - pseudo-events, aa:6
  - record formats and, aa:69
  - third-party, dg:186
  - user-level events
    - audit tokens, aa:70
    - `auditconfig` command
      - options, aa:23
    - described, aa:6
  - viewing, dg:191
- Audit Events action
  - described, ap:13
- audit files
  - backup, aa:85
  - cleaning up `not_terminated` file, aa:91
  - combing selected ones, aa:82
  - copying login/logout messages to single file, aa:81
  - directory locations, aa:10 to aa:11, aa:67
  - displaying in entirety, aa:79
    - `/etc/security/audit_class` file, aa:3
    - `/etc/security/audit_control` file, aa:3
    - `/etc/security/audit_event` file, aa:3
    - `/etc/security/audit_user` file, aa:3
    - `/etc/security/audit_warn` file, aa:3
  - managing, aa:76
  - managing size of, aa:18
  - merging, aa:79
  - minimum free space for file systems, aa:12
  - names
    - closed files, aa:75
    - examples, aa:75
    - form, aa:74
    - still-active files, aa:75
    - time stamps, aa:75
    - use, aa:74
  - nonactive files marked `not_terminated`, aa:91
  - order for opening, aa:12
  - overflow prevention, aa:89
  - printing, aa:79, aa:80
  - reading closed file, aa:78
  - reading still-open file, aa:79
  - reducing size, aa:83
  - reducing storage space requirements, aa:21
  - restoring, aa:86
  - specifying location, aa:49
  - switching to new file, aa:65
  - time stamps, aa:75

---

audit flags

- audit\_control file line, aa:12
- audit\_user file, aa:14 to aa:15
- C library functions, aa:341
- changing dynamically, aa:63
- definitions, aa:8
- list of, aa:98 to aa:99
- machine-wide, aa:8, aa:12
- overview, aa:8
- policy flags, aa:24
- prefixes, aa:8 to aa:10
- prefixes (modify), aa:9
- process preselection mask, aa:16
- setting, aa:50
- setting user exceptions, aa:51
- syntax, aa:8 to aa:9

audit IDs

- acquired at login, aa:16
- ensuring successful tracking, aa:3
- example audit record, aa:73
- purpose when a role is assumed, ap:5
- purpose when role assumed, ap:5

audit mappings, aa:97 to aa:145

audit -n command, aa:65

audit partitions

- creating, aa:41
- removing free space, aa:44

audit policies

- determining, aa:61
- setting, aa:24
- setting permanently, aa:52
- setting temporarily, aa:62

audit records, aa:147 to aa:337

- adding sequence token, aa:93
- audit directories full, aa:17, aa:20
- audit ID, aa:73
- audit session ID, aa:73
- C library functions, aa:341
- converting to human-readable
  - format, aa:78 to aa:84
- creating in an application, dg:192
- displaying by designated dates, aa:81
- displaying user activities, aa:80
- features in audit trail, aa:73
- format, aa:69
- format in audit trail, aa:69 to aa:70
- format or structure, aa:69 to aa:74,
  - aa:148, aa:179
- human-readable format, aa:71
- kernel-level generated, aa:179 to
  - aa:277
- login record, aa:72 to aa:74
- minimum, dg:193
- overview, aa:7
- policy flags, aa:24
- printing user activities, aa:80
- pseudo-events, aa:277
- reading, aa:72
- removing sequence token, aa:93
- selecting from audit trail, aa:77
- self-contained records, aa:73
- sending to a different file, aa:65
- time-stamp format, aa:75
- use of privilege, aa:277
- user-level generated, aa:301 to aa:337

audit -s command

- preselection mask for existing
  - processes, aa:12
- rereading audit files, aa:17, aa:64
- resetting directory pointer, aa:64

audit script, aa:39, aa:40

audit servers

- mount-point path names, aa:10
- partitioning example, aa:41
- planning, aa:34

audit session ID, aa:16, aa:73

Audit Startup action

- described, ap:13

audit -t command, aa:64

audit tokens

- described, aa:7
- examples, aa:150 to aa:178
- acl token, aa:150
- arbitrary token, aa:151
- arg token, aa:153
- attr token, aa:153
- audit record format, aa:69 to aa:74,
  - aa:148
- clearance token, aa:154
- exec\_args token, aa:154

---

exec\_env token, aa:155  
 exit token, aa:152, aa:156  
 file token, aa:156  
 groups token, aa:157  
 header token, aa:70, aa:71 to aa:72,  
     aa:158  
 host token, aa:159  
 ilabel token, aa:159  
 in\_addr token, aa:160  
 ip token, aa:161  
 ipc token, aa:161, aa:161 to aa:162  
 ipc\_perm token, aa:162  
 iport token, aa:163  
 liaison token, aa:163  
 newgroups token, aa:164  
 opaque token, aa:165  
 order, aa:70  
 order in audit record, aa:70  
 path token, aa:165  
 policy flags, aa:24  
 priv token, aa:166  
 privilege token, aa:166  
 process token, aa:167  
 reading, aa:71  
 return token, dg:195  
 return token, aa:168 to aa:169  
 seq token, aa:169  
 slabel token, aa:169  
 socket token, aa:170 to aa:171  
 socket-inet token, aa:171  
 subject token, aa:172  
 subject token structure, dg:195  
 table of, aa:148  
 text token, aa:172  
 trailer token, aa:70, aa:173  
 types, aa:70  
 xatom token, aa:174  
 xclient token, aa:174  
 xcolormap token, aa:175  
 xcursor token, aa:175  
 xfont token, aa:175  
 xgc token, aa:176  
 xpixmap token, aa:176  
 xproperty token, aa:177  
 xselect token, aa:177  
 xwindow token, aa:178

**audit trail**  
   **analysis**  
     auditing features, aa:73  
     auditreduce command, aa:76  
       to aa:82  
     costs, aa:20  
     finding failed login  
       attempts, aa:95  
     of cost, aa:20  
     praudit command, aa:78 to  
       aa:84  
   analyzing, aa:76  
   auditreduce command, aa:76 to  
     aa:82  
   **creating**  
     audit daemon's role, aa:17 to  
       aa:18, aa:68  
     audit\_data file, aa:17  
     directory suitability, aa:18  
     managing audit file size, aa:18  
     overview, aa:68  
   debugging, aa:93  
   directory locations, aa:10 to aa:11,  
     aa:67  
   events included, aa:4  
   merging, aa:76  
   monitoring in real time, aa:21  
   overflow prevention, aa:89  
   praudit command, aa:78 to aa:84  
**Audit Users action**  
   described, ap:13  
**audit\_class file**  
   application auditing, dg:186  
   creating class, dg:190  
   overview, ao:115  
**audit\_class(4TSOL) file**  
   action for editing, ap:13  
**audit\_control file**  
   application auditing, dg:186  
   audit daemon rereading after  
     editing, aa:12  
   audit\_user file modification, aa:14  
**C library functions, aa:341**  
**dir: line**  
   examples, aa:13

---

- files subdirectory, aa:10, aa:11
- examples, aa:13
- flags: line
  - described, aa:12
  - prefixes in, aa:9 to aa:10
  - process preselection mask, aa:16
- minfree: line
  - audit\_warn condition, aa:19
  - described, aa:12
- naflags: line, aa:12
- overview, aa:3 to aa:7
- prefixes in flags line, aa:9 to aa:10
- problem with contents, aa:20
- process preselection mask, dg:190
- audit\_control(4TSOL) file
  - action for editing, ap:13
- audit\_data file, aa:17
- audit\_event file
  - application auditing, dg:186
  - creating event, dg:190
  - overview, aa:4, aa:7, ao:116
- audit\_event(4TSOL) file
  - action for editing, ap:13
- audit\_startup file, aa:4
- audit\_startup script
  - overview, ao:117
- audit\_startup(1MTSOL) command
  - action for editing, ap:13
- audit\_user file
  - overview, ao:115
  - prefixes for flags, aa:9 to aa:10
  - process preselection mask, aa:16
  - user audit fields, aa:14 to aa:15
- audit\_user(4TSOL) file
  - action for editing, ap:13
- audit\_warn script, aa:18 to aa:20
  - allhard string, aa:19 to aa:20
  - allsoft string, aa:19
  - auditsvc string, aa:20
  - conditions invoking, aa:19 to aa:20
  - described, aa:17, aa:18 to aa:19
  - ebusy string, aa:20
  - hard string, aa:19
  - overview, ao:117
  - postsigterm signal, aa:20
  - soft string, aa:19
  - tmpfile string, aa:20
- auditconfig command
  - changing class mappings, aa:94
  - options, aa:22 to aa:24
  - overview, ao:117
  - prefixes for flags, aa:9 to aa:10
- auditd daemon
  - audit trail creation, aa:17 to aa:18, aa:68
  - audit\_startup file, aa:4
  - audit\_warn script
    - conditions invoking, aa:19 to aa:20
    - described, aa:17, aa:18 to aa:19
    - execution of, aa:17, aa:18
  - directories suitable to, aa:18
  - enabling auditing, aa:4
  - functions, aa:17
  - order audit files are opened, aa:12
  - rereading the audit\_control file, aa:12
  - terminating, aa:64
- auditid field, dg:295
- auditing
  - See also* application auditing
  - advanced setup procedures, aa:56 to aa:60
  - advanced tasks for security administrator, aa:38
  - audit ID, aa:73
  - audit session ID, aa:73
  - basic setup procedures, aa:41 to aa:56
  - basic tasks for security administrator, aa:38
  - checklists, aa:343 to aa:351
  - client-server relationships, aa:39, aa:40
  - compatibility with Solaris 2.5.1, tg:31
  - compatibility with Trusted Solaris 1.2, tg:31
  - configuration files, ao:115
  - considerations, aa:30
  - defaults, aa:3, aa:4

---

audit\_startup file, aa:4  
 disabling, aa:39, aa:40  
 dynamic procedures, aa:60  
 for efficiency, aa:31  
 enabling, aa:4, aa:40  
 header files, aa:342  
 interfaces, tg:65  
 introduction, ug:3  
 macro files, aa:342  
 NIS+ client setup, ic:105  
 NIS+ root master setup, ic:92  
 non-networked workstation  
   setup, ic:69  
 overview, ao:113 to ao:118  
 overview of administration, aa:1 to  
   aa:3  
 planning, ic:10, aa:28 to aa:36, ao:114  
   to ao:116  
 preselection mask  
   classes on file systems, dg:34  
   process privileges, ao:30  
   public files and directories, dg:36  
   remote host templates, ao:93  
   removing free space, aa:44  
   setup tasks for system  
     administrator, aa:37  
   shutdown, aa:38  
   site planning, aa:27  
   software packages, aa:2  
   space planning, aa:32, aa:33  
   startup, aa:4, aa:38  
   system privileges, ao:30  
   tools, ao:116 to ao:118  
   user ID, aa:73  
   warning of trouble, aa:52  
   worksheets, aa:343 to aa:351  
 auditon audit record  
   A\_GETCAR command, aa:181  
   A\_GETCLASS command, aa:181  
   A\_GETCOND command, aa:182  
   A\_GETCWD command, aa:182  
   A\_GETKMASK command, aa:182  
   A\_GETSTAT command, aa:183  
   A\_GPOLICY command, aa:183  
   A\_GQCTRL command, aa:183  
   A\_SETCLASS command, aa:184  
   A\_SETCOND command, aa:184  
   A\_SETKMASK command, aa:185  
   A\_SETSMASK command, aa:185  
   A\_SETSTAT command, aa:186  
   A\_SETUMASK command, aa:186  
   A\_SPOLICY command, aa:187  
   A\_SQCTRL command, aa:187  
 auditpsa audit record, aa:188  
 auditreduce command  
   capabilities, aa:77  
   cleaning not\_terminated  
     files, aa:92  
   described, aa:76  
   distributed systems, aa:76  
   examples, aa:78, aa:81, aa:92  
   overview, ao:117  
   time stamp use, aa:75  
 auditstat audit record, aa:188  
 auditstat command  
   overview, ao:118  
 auditsvc  
   system call fails, aa:20  
 auditsvc audit record, aa:189  
 auditwrite audit record, aa:306  
 auditwrite(3TSOL)  
   code examples, dg:46, dg:192 to  
     dg:206  
   declaration, dg:187  
   invalid call, dg:192  
   valid call, dg:193  
 AUE... names, aa:6  
 AUTH\_authorization name, *See*  
   authorizations and auth\_  
   desc(4TSOL)  
 auth\_name file, ap:48  
 auth\_names.h file, ap:47  
 auth\_set\_t type, dg:83  
 auth\_set\_to\_str(3TSOL)  
   code example, dg:88  
   declaration, dg:84

---

auth\_t type, dg:83  
 auth\_to\_str(3TSOL)  
     code example, dg:86  
     declaration, dg:84  
 authentication  
     defined, ug:20  
     procedure, ug:23 to ug:24  
 authorization use audit  
     record, aa:335  
 authorizations  
     *See also* auth\_desc(4TSOL) man page  
     *See also* code examples  
     *See also* privileges  
     *See also* security policy  
     *See also* translation  
     adding, ap:47  
     administering printing, ap:466  
     administrative manifest  
         constants, tg:105  
     allocate device, ap:486  
     and privileges, dg:41  
     API declarations, dg:83 to dg:84,  
         dg:348  
     assigning to execution  
         profiles, ap:241, ao:122  
     categories, ao:27  
         device allocation, dg:82  
         files, dg:82  
         labels, dg:82  
         login, dg:82  
         software administration, dg:82  
         X Window System, dg:82  
     complete list, tg:106  
     data types  
         authorization ID, dg:83  
         structure, dg:83  
     defined, ug:12, ao:2  
     description file, tg:100  
     device-related  
         procedure for assigning to an  
             account, ap:514  
     differences, tg:59  
     downgrade file sensitivity label, la:13  
     in execution profiles, ao:21  
     file access, ao:36  
         for accounts that assume secadmin  
             role, ap:6  
         for device administration, ap:491  
         for specifying fields in the User  
             Manager, ap:73  
     Label builder, dg:321  
     manifest constants, tg:104 to tg:108  
     modify at admin, ap:95  
     modify at user, ap:96  
     modify cron admin, ap:96  
     modify cron user, ap:96  
     needed for users who assume  
         secadmin role, ap:6  
     overview, ao:26 to ao:27  
     print without banners, ap:466  
     print without labels, ap:466  
     and privileges, dg:40  
     procedure for adding, ap:49  
     required for account setup, ap:74  
     required for User Manager, ap:110 to  
         ap:112  
     self-modification, ap:112  
     in software administration, ao:19  
     table of device-related, ap:490  
     tsolprof file, ap:46  
     upgrade file sensitivity label, la:13  
     user manifest constants, tg:105  
     when to check, dg:41, dg:81  
 auths field, dg:213  
 auto size value, ic:152  
 auto\_install\_sample directory  
     check script, ic:169  
     copying files to JumpStart  
         directory, ic:138, ic:141  
     set\_root\_pw finish script, ic:178 to  
         ic:180  
 autofs file system  
     modified for Trusted Solaris, tg:29  
 automounter  
     home directories, tg:3, tg:29  
 automounting  
     AutoHome Setup toggle, ao:75

---

AW\_APPEND control command, dg:196  
 AW\_ARG token command, dg:207  
 AW\_CLEARANCE token command, dg:196  
 AW\_DEFAULTRD token command, dg:203  
 AW\_DISCARDRD token command, dg:202  
 AW\_END terminator command, dg:192  
 AW\_EVENT token command, dg:193  
 AW\_EXEC\_ARGS token command, dg:208  
 AW\_FLUSH token command, dg:198  
 AW\_GETRD token command, dg:202  
 AW\_ILABEL token command, dg:196  
 AW\_IPC token command, dg:210  
 AW\_NOPRESELECT token  
     command, dg:200  
 AW\_NOQUEUE token command, dg:198  
 AW\_NOSAVE token command, dg:203  
 AW\_NOSERVER token command, dg:205  
 AW\_PATH token command, dg:202  
 AW\_PRESELECT token command, dg:200  
 AW\_PRIVILEGE token command, dg:209  
 AW\_QUEUE token command, dg:198  
 AW\_RETURN token command, dg:194,  
     dg:195  
 AW\_SAVERD token command, dg:203  
 AW\_SERVER token command, dg:205  
 AW\_SLABEL token command, dg:194,  
     dg:205  
 AW\_SUBJECT token command, dg:194  
 AW\_TEXT token command, dg:195  
 AW\_USERD token command, dg:202  
 AW\_WRITE control command, dg:196  
 ax audit class, aa:120  
 ax audit flag, aa:98

**B**

backslash (\) in rules, ic:163  
 backup  
     audit files, aa:85  
     before installation, ic:11

banner command, ic:112  
 banner pages  
     computing the classification, la:88  
     labeling, la:85 to la:87  
     printing without, ap:478  
 banner\_fields structure, dg:102  
 banners on print jobs, ap:462  
 batch command  
     administrative differences, ap:90 to  
         ap:99  
     running privileged commands, ap:92  
 bclabel\_t type, dg:100  
 bclear\_t type, dg:153  
 bclearhigh(3TSOL)  
     code example, dg:157  
     declaration, dg:154  
 bclearlow(3TSOL)  
     code example, dg:159  
     declaration, dg:154  
 bcleartoh(3TSOL)  
     code example, dg:166  
     declaration, dg:157  
 bcleartoh\_r(3TSOL)  
     code example, dg:148, dg:167  
     declaration, dg:157  
 bcleartos(3TSOL)  
     code example, dg:164  
     declaration, dg:156  
 bclearundef(3TSOL)  
     code example, dg:159  
     declaration, dg:154  
 bclearvalid(3TSOL)  
     code example, dg:163  
     declaration, dg:156  
 bclhigh(3TSOL)  
     code example, dg:140  
     declaration, dg:104  
 bcllow (3TSOL)  
     declaration, dg:104  
 bcltobanner(3TSOL)  
     code example, dg:149  
     declarationBinary, dg:109

---

**bcltoh**(3TSOL), declaration, dg:111  
**bcltoh\_r**(3TSOL), declaration, dg:111  
**bcltoil**(3TSOL)  
     code example, dg:130  
     declaration, dg:105  
**bcltos**(3TSOL)  
     code example, dg:117, dg:140  
     declaration, dg:109  
**bcltosl**(3TSOL)  
     code example, dg:130  
     declaration, dg:104  
**bclundef**(3TSOL)  
     code example, dg:116  
     declaration, dg:104  
**begin rule field**  
     described, ic:161  
     valid entries, ic:163  
     validation, ic:169  
**begin scripts**  
     creating derived profiles with, ic:174  
         to ic:175  
     overview, ic:173  
     permissions, ic:174  
     rule field, ic:161  
     site-specific installation  
         programs, ic:188  
**begin.log** file, ic:174  
**bilabel\_t** type, dg:100  
**bilconjoin**(3TSOL)  
     code example, dg:131  
     declaration, dg:107  
**bilDominates**(3TSOL)  
     code example, dg:127  
     declaration, dg:106  
**bilequal**(3TSOL)  
     code example, dg:127  
     declaration, dg:106  
**bilhigh**(3TSOL)  
     code example, dg:142  
     declaration, dg:105  
**billow**(3TSOL)  
     code example, dg:116  
     declaration, dg:105  
**biltoH**(3TSOL), declaration, dg:111  
**biltoH\_r**(3TSOL), declaration, dg:111  
**biltolev**(3TSOL)  
     code example, dg:130  
     declaration, dg:105  
     when to use, dg:125  
**biltoS**(3TSOL)  
     code example, dg:142  
     declaration, dg:110  
**bilundef**(3TSOL), declaration, dg:105  
**bilvalid**(3TSOL), declaration, dg:108  
**bimDominates**(3TSOL)  
     code example, dg:129  
     declaration, dg:106  
**bimequal**(3TSOL)  
     code example, dg:129  
     declaration, dg:106  
**binary**  
     to hexadecimal, dg:144, dg:147  
**binary audit record format**, aa:70  
**bldominates**(3TSOL)  
     code example, dg:43, dg:126, dg:160  
     declaration, dg:105, dg:154  
**blequal**(3TSOL)  
     code example, dg:126, dg:160  
     declaration, dg:105, dg:154  
**blevel\_t** type, dg:153  
**blinrange**(3TSOL)  
     code example, dg:123  
     declaration, dg:105, dg:154  
**blinset**(3TSOL)  
     code example, dg:133  
     declaration, dg:109  
**blmaximum**(3TSOL)  
     code example, dg:132, dg:162  
     declaration, dg:107, dg:155  
**blminimum**(3TSOL)  
     code example, dg:133, dg:163  
     declaration, dg:107, dg:155  
**blstrictdom**(3TSOL)  
     code example, dg:126, dg:160  
     declaration, dg:105, dg:154

---

`bltocolor`(3TSOL)  
     code example, dg:136  
     declaration, dg:108  
`bltocolor_t`(3TSOL),  
     declaration, dg:108  
`bltype`(3TSOL)  
     code example, dg:116, dg:159  
     declaration, dg:107, dg:155  
 body pages  
     labels, ap:452, la:84  
     specifying SLs to print instead of  
         ILs, ap:477  
 boot  
     setting up communications with the  
         NIS+ master, ap:326  
     using special versions of  
         `tnrhdb/tnrhtp`  
         files, ap:326  
 boot execution profile, ap:553  
 boot information  
     copying during custom  
         JumpStart, ic:245  
 boot server  
     adding Trusted Solaris files, ic:116  
     creating on subnet, ic:126  
 booting the workstation  
     during installation, ic:52, ic:87  
     I/O interrupt error messages, ic:112  
     interactive installation, ic:54  
     resetting terminals and display  
         first, ic:112  
     system privileges, ao:30  
 bootparams database, tg:12  
 bootparams file  
     enabling JumpStart directory  
         access, ic:144  
 Bourne shell scripts in rule fields, ic:161  
 bracketing, *See* privilege bracketing  
 brackets [] rule field, ic:160  
`brange_t` type, dg:101  
 broadcast messages  
     network privileges, ao:29  
  
`bslabel_t` type, dg:100, dg:173  
`bslevel_t` type, dg:101  
`bslhigh`(3TSOL)  
     code example, dg:116  
     declaration, dg:105  
`bsllow`(3TSOL), declaration, dg:105  
`bsltoh`(3TSOL), declaration, dg:111  
`bsltoh_r`(3TSOL), declaration, dg:111  
`bsltos`(3TSOL)  
     code example, dg:132, dg:140  
     declaration, dg:110  
`bslundef`(3TSOL), declaration, dg:105  
`bslvalid`(3TSOL)  
     code example, dg:134  
     declaration, dg:108  
 builders  
     label user interface, tg:56  
 builders, GUI  
     *See also* label builder  
     API declarations, dg:357  
     interfaces described, dg:315  
 buses  
     SBus, ic:7  
     supported, ic:235, ic:236, ic:237  
     VMEbus, ic:7  
  
**C**  
 C library functions, aa:341  
 cache<sub>s</sub> filesysem type, ap:384  
 calendar  
     differences in Trusted Solaris, ug:74  
 Calendar Manager  
     modified for Trusted Solaris, tg:36  
     polyinstantiated, tg:4  
 cancel command  
     modified for Trusted Solaris, ap:465  
 canonical form, cm:1, cm:28, cm:50, cm:51,  
     cm:52, cm:115, cm:119  
 carat (^) in audit flag prefixes, aa:9 to  
     aa:10  
 cards  
     PCI, ic:7

---

caveats field, dg:102  
 caveats\_len field, dg:101, dg:102  
 CD players  
     launching automatically, ap:404  
 CDE  
     applications, tg:73  
     applications modified for Trusted Solaris, tg:35  
     assigning actions, tg:20  
     customizable workspace menu, tg:4  
     customizing, ic:198  
     defaults, tg:19  
     front panel, tg:34  
     multiple workspaces, tg:34  
     role workspaces, tg:34  
     Trusted Path menu, tg:34  
 CDE actions, *See* actions  
 CDE configuration file default, ap:135  
 CDE sessions  
     ending, ic51  
     starting the workstation, ic52  
 CDE workspaces  
     Trusted Solaris differences, la:14  
 CD-ROM devices  
     accessing, ap:486  
     device\_clean script, ap:497  
 CDROM devices  
     requirement for Trusted Solaris installation, ic:7  
 Change Input IL menu item  
     described, ug:95 to ug:96  
 change password audit record, aa:322  
 Change Password menu item  
     described, ug:84 to ug:89  
 change window IIL audit record, aa:315  
 change workspace SL audit record, aa:333  
 Change Workspace SL menu item  
     described, ug:81 to ug:82  
     example, ug:50  
 changes to printing in Trusted Solaris, ap:448 to ap:474  
 channel, la:6, cm:2, cm:4, cm:17, cm:45, cm:60, cm:82 to cm:92, cm:113, cm:114, cm:118, cm:126, cm:128, cm:138, cm:139, cm:140  
 channels  
     configuring, la:107  
     on print job banner and trailer pages, la:97 to la:106  
     worksheet example, la:158  
 channels field, dg:102  
 CHANNELS section  
     label\_encodings example, la:167  
 channels\_len field, dg:101, dg:102  
 chdir audit record, aa:189  
 Check Encodings action  
     described, ap:13  
 check script  
     comments and, ic:163  
     derived profiles and, ic:175  
     directory for, ic:169  
     rules file validation, ic:169 to ic:170  
     rules.ok file creation, ic:169  
     starting, ic:169 to ic:172  
     testing rules, ic:170  
 Check TN Files action  
     described, ap:13  
 Check TN NIS+ Tables action  
     described, ap:13  
 checklists  
     auditing, aa:343 to aa:351  
 checklists for administrators, ic:227 to ic:232  
 Chinese locale value, ic:154  
 chk\_encodings command  
     description, la:57  
     overview, ao:142  
     scope of check, la:50  
 chk\_encodings(1MTSOL) command  
     action for invoking, ap:13  
 chkauth(3TSOL)  
     code example, dg:41, dg:85

---

declaration, dg:83  
 chmod audit record, aa:190  
 chown audit record, aa:190  
 chroot audit record, aa:191, aa:308  
 chstate audit record, aa:191  
 CIPSO  
   (Common Internet Protocol Security Option)  
   host type, ao:89  
     described, ap:314  
   remote host templates, ao:93  
   replacing ADMIN\_HIGH, ap:350  
   use in packets, ap:271  
 cl audit class, aa:104  
 cl audit flag, aa:98  
 cl\_tsol\_incoming\_attrsp field, dg:280  
 cl\_tsol\_outgoing\_attrsp field, dg:280  
 clabel\_len field, dg:101  
 classes  
   changing definitions, aa:5  
   flags and definitions, aa:8  
   mapping events, aa:4  
   overview, aa:4, aa:7  
   selecting for auditing, aa:4  
 classification label component  
   defined, ug:5, ao:4  
   maximum number definable, la:9  
 classification=, cm:49 to cm:51, cm:81, cm:82, cm:113, cm:119, cm:142  
 classifications  
   changing, la:63  
   changing display in label builder, la:113  
   clearance component, dg:151  
   described, ap:365  
   dominate, dg:125, dg:127, dg:160  
   equal, dg:125, dg:127, dg:160  
   field length, la:11, la:12, la:15  
   IL component, dg:91  
   keywords, la:63  
   maximum number, la:11, la:12, la:15, la:63  
   minimum number definable, la:9  
   planning example, la:149  
   rules for printing, la:88  
   site analysis example, la:144 to la:148  
   SL component, dg:91  
   specifying colors, la:115 to la:123  
   strictly dominate, dg:126, dg:160  
 CLASSIFICATIONS section  
   label\_encodings example, la:163  
 clear\_len field, dg:101  
 clearance, cm:2 to cm:21, cm:42 to cm:43, cm:48, cm:50, cm:51, cm:52, cm:53, cm:58 to cm:60, cm:65, cm:69, cm:84, cm:93 to cm:95, cm:113 to cm:117, cm:118, cm:120, cm:137 to cm:138, cm:142  
 clearance labels  
   setting on user and role accounts, la:43  
 clearance token  
   described, aa:154  
   praudit display, aa:154  
 clearances  
   *See also* process clearances  
   account label range, ao:10  
   assigning, ap:137, ao:77  
   checking clearances, dg:42  
   defined, ug:5  
   described, ap:365  
   label encodings file, la:6  
   label overview, ao:4, ao:16  
   minimum, ao:9  
   minimum number to define, la:1  
   network interfaces, ao:96  
   remote host templates, ao:93  
   session, dg:151  
   setting for a single-SL system, la:13  
   setting session, ug:28  
   user, dg:151  
   worksheet example, la:156  
 process clearances  
   *See also* code examples  
   *See also* labels  
   *See also* translation

---

CLEARANCES section  
 label\_encodings example, la:167

CLIENT structure, dg:280

client windows  
 untrusted in trusted role  
 workspace, tg:4

*client\_arch* profile keyword, ic:150

*client\_root* profile keyword, ic:150

*client\_swap* profile keyword, ic:150

clist command  
 overview, ao:153

clock  
 differences in Trusted Solaris, ug:74  
 time zones for setting, ic:267 to ic:268

clock\_settime audit record, aa:192

close audit record, aa:192

closed networks  
 defined, ao:86

*cluster* profile keyword  
 description and values, ic:151  
 examples, ic:147

.cm.rc file, ap:80

cmds field, dg:213

CMW labels, la:20  
 (compartmented mode workstation  
 labels)  
*See also* code examples  
*See also* ILs  
*See also* labels  
*See also* SLs  
*See also* translation

API declarations, dg:351

components, dg:90

defined, ug:16, dg:89

described, ap:365

file systems, dg:33

objects, dg:94

processes, dg:93

rules, la:20

user interface appearance, dg:93

CMWXdefaults file, tg:14

cnt policy  
 flag, aa:25

code examples  
 accreditation range, checking, dg:133  
 adding information label, dg:196  
 auditing  
 adding a sensitivity label, dg:205  
 appending information, dg:196  
 creating audit records, dg:46  
 creating mimimum  
 record, dg:193  
 creating parallel records, dg:202  
 handling return values, dg:195  
 invalid call, dg:192  
 preliminary setup, dg:188 to  
 dg:191  
 queueing information, dg:198  
 using preselection mask, dg:200  
 using save area, dg:203  
 using server area, dg:205  
 valid call, dg:193  
 writing arguments, dg:207  
 writing command line  
 arguments, dg:208  
 writing IPC identifier, dg:210  
 writing privilege sets, dg:209

authorizations  
 and privileges, dg:41  
 checking, dg:41, dg:85  
 freeing authorization sets, dg:88  
 getting description text, dg:87  
 translating ID to string, dg:86  
 translating set to string, dg:87,  
 dg:88  
 translating string to ID, dg:86

checking SLs, dg:42

clearances  
 checking before file access, dg:43  
 checking if valid, dg:163  
 checking type, dg:159  
 ckecking prior to access, dg:42  
 finding lower bound, dg:163  
 finding upper bound, dg:162  
 getting, dg:157  
 initializing to ADMIN\_  
 LOW, dg:159  
 initializing to undefined, dg:159  
 setting, dg:157

---

- testing relationships, dg:160
- translating, dg:164, dg:165
- translating and clipping, dg:165
- translating to hex, dg:148, dg:166, dg:167
- CMW labels
  - getting on file system, dg:120
  - getting on window, dg:307
  - getting pointers to
    - portions, dg:130
  - getting process label, dg:43, dg:117
  - getting SL and IL, dg:117
  - setting on file system, dg:121
  - setting on window, dg:308
  - setting process label, dg:119
  - translating to ASCII, dg:140
  - translating to binary, dg:145
  - translating to hex, dg:147
- databases
  - enumerating, dg:222
  - getting profile entries, dg:218
  - getting user entries, dg:48, dg:218
- file systems
  - accessing, dg:19
  - executing, dg:23
  - getting attribute flags, dg:35
  - getting attributes, dg:31
  - getting attributes (inode), dg:33
  - getting CMW label, dg:120
  - getting label range, dg:123
  - opening a file, dg:20
  - setting CMW label, dg:121
  - writing to a file, dg:22
- ILs
  - conjoining, dg:131
  - creating, dg:119
  - floating, dg:118
  - testing markings, dg:129
  - testing relationships, dg:127
  - translating binary to
    - ASCII, dg:142
  - translating to binary, dg:145
- Label builder, dg:318
- label\_encodings file
  - getting ASCII color
    - names, dg:136
  - getting information on, dg:137
  - retrieving version string, dg:114
  - translating printer
    - banner, dg:149
- labels, dg:113 to dg:150
  - checking accreditation
    - ranges, dg:133
  - checking if valid, dg:134
  - initializing, dg:116
  - translating with font list, dg:306
- MLDs
  - creating a file, dg:182
  - getting adorned name, dg:179
  - getting MLD name, dg:178
  - getting real path, dg:179
  - getting security attribute
    - flags, dg:35
  - getting security
    - attributes, dg:180
  - getting SLD name, dg:45
  - getting working
    - directory, dg:179
  - opening a file, dg:182
- printer banner, translating, dg:149
- privilege sets
  - bracketing effective set, dg:73
  - checking allowed set, dg:69
  - checking permitted set, dg:74
  - checking saved set, dg:76
  - clearing allowed set, dg:67
  - clearing effective set, dg:73
  - clearing inheritable set, dg:76
  - exec'ing a process, dg:79
  - forking a process, dg:77
  - removing permitted privs, dg:75
  - setting forced set on file, dg:69
  - setting inheritable set, dg:76
  - translating set to string, dg:69
- privileges
  - after checking
    - authorizations, dg:41
  - and authorizations, dg:41
  - asserting privileges in sets, dg:69
  - getting description text, dg:66

---

- setting user ID, dg:80
  - translating ID to string, dg:65
  - translating string to ID, dg:65
  - when to use, dg:42
- processes, getting attribute flags, dg:37
- RPC
  - example application, dg:281 to dg:285
  - header file, dg:281
  - running the application, dg:286
- security configuration
  - variables, dg:29
- SLDs
  - creating a file, dg:182
  - getting name, dg:45
  - getting security
    - attributes, dg:180
  - getting SLD name, dg:178
  - getting working
    - directory, dg:179
  - opening a file, dg:182
- SLs
  - checking before file access, dg:43
  - creating, dg:119
  - finding lower bound, dg:133
  - finding upper bound, dg:132
  - getting file system range, dg:123
  - testing relationships, dg:126
  - translating to ASCII, dg:140
  - translating to binary, dg:145
- System V IPC
  - using message queue
    - labels, dg:236
  - using semaphore set
    - labels, dg:239
  - using shared memory
    - labels, dg:241
- TSIX
  - allocating space, dg:254
  - clearing attributes, dg:263
  - client application, dg:273 to dg:276
  - comparing attributes, dg:263
  - copying attribute
    - structures, dg:262
  - creating attribute masks, dg:264
  - duplicating structures, dg:262
  - examining the last
    - attribute, dg:260
  - example application, dg:265 to dg:276
  - freeing allocated space, dg:265
  - getting attribute size, dg:261
  - getting attributes, dg:258
  - getting endpoint
    - defaults, dg:257
  - getting endpoint mask, dg:257
  - peeking at attributes, dg:260
  - receiving attributes, dg:258
  - receiving new attributess, dg:259
  - replying to request, dg:267
  - sending attributes, dg:254
  - server application, dg:266 to dg:272
  - setting attributes, dg:254
  - setting endpoint defaults, dg:257
  - setting endpoint mask, dg:257
  - using multilevel ports, dg:265
- vfstab\_adjunct(4TSOL), dg:31
- X Window System
  - getting window
    - attributes, dg:305
  - getting window CMW
    - label, dg:307
  - getting window userID, dg:308
  - getting workstation
    - owner, dg:308
  - Motif application, dg:304
  - setting window CMW
    - label, dg:308
  - translating with font list, dg:306
- codeword, cm:6, cm:7, cm:28, cm:33, cm:34, cm:60 to cm:63, cm:126 to cm:134
- COLOR NAMES section
  - label\_encodings example, la:175
- colormaps
  - window privileges, ao:30
- command arguments
  - control, dg:188

---

terminator, dg:188  
 token, dg:188

**commands**  
 assigning inheritable  
     privileges, ao:31  
 assigning to execution  
     profiles, ap:238, ao:122  
 changes, tg:43  
 executing with privilege, aa:42  
 in execution profiles, ao:21  
 launching, ao:49  
 linked list data type, dg:214  
 maintenance commands, aa:339  
 new, tg:45  
 privileged  
     run by `cron(1MTSOL)`, ap:92  
 privileges, ap:541  
 profile assignments and security  
     attributes, ap:590 to ap:628  
 summary descriptions, tg:41  
 summary table, ao:58  
 trusted, ap:541

**comments**  
 assigning to accounts, ap:126  
 assigning to users, ao:67  
 in profiles, ic:147  
 in `rules` file, ic:163

**commercial applications**  
 adding, ap:541

**Common Internet Protocol Security**  
 Option, *See* CIPSO

**communication endpoints**  
*See also* IPC  
*See also* TLI  
 access checks, dg:223, dg:227  
 connections described, dg:228  
 objects, dg:4  
 security attributes (TSIX), dg:245

**compartment label component**  
 defined, ug:5, ao:5

**compartmented mode workstation labels,**  
*See* CMW labels

**compartments**  
 changing display in label  
     builder, la:113  
 clearance component, dg:151  
 defined, la:10  
 described, ap:366  
 dominate, dg:125, dg:127, dg:160  
 equal, dg:125, dg:127, dg:160  
 field length, la:11, la:12, la:15  
 IL component, dg:91  
 planning example, la:150  
 setting up hierarchies, la:11, la:12,  
     la:15  
 site analysis example, la:144 to la:148  
 SL component, dg:91  
 strictly dominate, dg:126, dg:160  
 worksheet example, la:155

**compartments=,** cm:6, cm:25, cm:33 to  
 cm:34, cm:59, cm:88, cm:93,  
 cm:98, cm:103, cm:108, cm:112,  
 cm:126 to cm:141

**compile**  
 auditing libraries, dg:187  
 authorization libraries, dg:82  
 clearance libraries, dg:153  
 Label builder libraries, dg:316  
 label libraries, dg:100  
 MLD libraries, dg:173  
 privilege libraries, dg:59  
 profile database access  
     libraries, dg:212  
 RPC libraries, dg:280  
 SLD libraries, dg:173  
 System V IPC libraries, dg:234  
 TSIX libraries, dg:247  
 user database access libraries, dg:212  
 X Window System libraries, dg:294

**component definitions**  
 label encodings file, ao:5  
`config.privs` file, ap:445, tg:4  
`config_data` file, ic:117

**configuration**  
 labels, la:39

---

- running with a single sensitivity label, la:13
- configuration files
  - checking after upgrade, ic:51
  - copying for distribution, ic:94
  - creating directory, ic:94
  - distributing to workstations, aa:53
  - SPARC systems
    - for concatenating multiple disks, ic:186 to ic:188
- configuration files, *See also* databases
- configuration management
  - system privileges, ao:30
- configurations, *See* system security
  - configuration
- Configure Selection Confirmation action
  - described, ap:13
- conjoining ILS, dg:92, dg:131
- connection requests
  - security attributes, dg:289
  - security policy, dg:290
- console redirection
  - system privileges, ao:30
- control commands, dg:188
- .copy\_files file
  - described, ug:121
  - using, ap:87
- copy-and-paste
  - effect on ILS, ug:16
  - effect on SLs, ug:8
  - example, ug:57 to ug:60
- core dump audit record, aa:239
- core files, dg:58
- cost control, aa:20 to aa:22
  - analysis, aa:20
  - processing time, aa:20
  - storage, aa:21
- covert channel delays
  - process privileges, ao:30
- covert channels, dg:59
- CPUs (processors)
  - rule keywords, ic:163
- creat audit record, aa:193
- Create NIS+ Client action
  - described, ap:13
- Create NIS+ Server action
  - described, ap:13
- creating the audit trail
  - audit daemon's role, aa:17 to aa:18
  - audit\_data file, aa:17
  - directory suitability, aa:18
  - overview, aa:68
- credentials
  - giving to roles, ic:87
- cron command
  - administrative differences, ap:90 to ap:99
  - running privileged commands, ap:92
- cron job, aa:18
- cron.allow file, ap:93
- cron.deny file, ap:93
- crontab command
  - administrative differences, ap:90 to ap:99
  - Trusted Solaris changes, ap:97
- crontab audit record
  - cron-invoke atjob, aa:309
  - crontab, aa:309
  - crontab-crontab
    - created, aa:308
    - deleted, aa:309
  - crontab-permission, aa:310
- crontabs documentation, ic:198
- custom execution profiles
  - verifying, ic:48
- custom JumpStart installation
  - advantages, ic:130
  - booting and installing
    - booting the system, ic:54 to ic:56
  - described, ic:129
  - diskless clients, ic:62
  - examples, ic:239 to ic:246
    - check script, ic:243
    - engineering systems setup, ic:244

---

- JumpStart directory, ic:240 to ic:241
- marketing systems setup, ic:245 to ic:246
- networked, ic:135
- non-networked, ic:134
- rules file editing, ic:242 to ic:243
- site setup, ic:239 to ic:240
- standalone system, ic:134
- hands-off installation, ic:110
  - requirements, ic:111
- JumpStart directory, ic:143
- optional features, ic:173 to ic:188
  - begin scripts, ic:173 to ic:175
  - finish scripts, ic:176 to ic:180
  - overview, ic:173
  - pfinstall command, ic:180 to ic:183
  - site-specific installation programs, ic:188
- overview, ic:133 to ic:135
- preparing, ic:129 to ic:172
- customizations
  - changing printer output, ap:457, la:85
  - label encodings file, ao:6
- Customize Trusted Solaris Configuration
  - dialog box
  - described, la:39
  - example, ic:249, la:161
- cut and paste
  - configuring rules, ap:434
- cut-and-paste
  - constraints, tg:20
  - modified for Trusted Solaris, tg:36

**D**

- DAC
  - (discretionary access control)
  - See also* security policy
  - accessing System V IPC objects, dg:232
  - cautions about override privileges, ap:541
  - defined, ug:4, ao:2
  - described, ap:366
  - file access, ao:36
  - override privileges, ap:523
  - policy for devices, ap:485
  - privilege bracketing, dg:71
  - security policy, dg:13
- data
  - interchange, tg:39
  - porting, tg:38
- Data Encryption Standard, *See* DES
- data interchange, tg:39
- data objects, *See* objects
- data packets, *See* packets
- data protection
  - example, ao:35 to ao:46
- data types
  - auditing, dg:187
  - authorization APIs, dg:82
  - clearance APIs, dg:153
  - label APIs, dg:100
  - Label buider APIs, dg:322, dg:324, dg:327
  - MLD APIs, dg:173
  - privilege APIs, dg:59
  - profile database access APIs, dg:212
  - RPC APIs, dg:279
  - SLD APIs, dg:173
  - System V IPC APIs, dg:234
  - TSIX APIs, dg:247
  - user database access APIs, dg:212
  - X Window System APIs, dg:294
- data\_mac\_policy, ap:485
- Database Manager
  - accessing network databases, ap:330
  - adding a host to a running system, ap:410
  - bootparams database, tg:12
  - entering local hosts, ic:78
  - modifying tnrhdb, ic:78 to ic:80
  - modifying tnrhtp, ic:79 to ic:80
  - network configuration
    - databases, ao:90
  - tnidb(4TSOL), ao:96

---

tnrhdb(4TSOL), ao:91  
 tnrhttp(4TSOL), ao:94  
 use, tg:17  
 using, ic:35, ap:26, ap:28

**databases**  
*See also* code examples  
 accessing tnidb(4TSOL), ap:303  
 accessing tnrhdb file, ap:303  
 accessing tnrhttp(4TSOL), ap:303  
 API declarations, dg:214, dg:215 to  
     dg:217, dg:354  
 changes, tg:13  
 device\_allocate file, ao:148  
 device\_deallocate file, ao:148  
 device\_maps file, ao:149  
 distributed administration, tg:15  
 local administration, tg:17  
 locations, tg:51  
 name service, tg:15  
 profile  
     data types, dg:213, dg:214  
     described, dg:211  
 Solstice AdminSuite, tg:15  
 Solstice\_Apps, tg:15  
 src parameter, dg:214  
 summary of changes, tg:13  
 System\_Admin, tg:15  
 tnidb database, ao:96  
 tnidb(4TSOL), tg:23  
 tnrhdb(4TSOL), ao:90, tg:51  
 tnrhttp(4TSOL), ao:93, tg:51  
 tsolprof(4TSOL), tg:16, tg:64  
 tsoluser, ic:67, ic:82  
**user**  
     data types, dg:212  
     described, dg:211  
     during installation, ic:67, ic:82  
     user and profile, tg:63

date-time auditreduce command  
     options, aa:81

dbmgr audit records, aa:310

de locale name, ic:154

deallocate command  
     Trusted Solaris modifications, ao:146  
     described, ap:502

debugging  
     applications, dg:335  
     of privileges, tg:41, tg:58  
     *See also* privilege debugging

Decision to Make for the Install Team to  
     Follow, la:41

default groups  
     ACL entry, ug:103

default label view, la:30

default masks  
     ACL entry, ug:103

default others  
     ACL entry, ug:103

default owning groups  
     ACL entry, ug:103

default owning users  
     ACL entry, ug:103

default routes  
     setting, ic:76

default shells  
     assigning to accounts, ap:126

default users  
     ACL entry, ug:103

default word, cm:5, cm:21, cm:22, cm:23,  
     cm:24, cm:71 to cm:72, cm:116

device\_policy(4TSOL) file  
     described, ap:485

defaultrouter file  
     action for editing, ap:13

**defaults**  
     audit policies, aa:24  
     derived profile name, ic:175  
     execution profiles, ao:21  
     machine-wide, aa:8  
     partitioning, ic:156  
         designating disks, ic:156  
         excluding disks, ic:151  
     privileges, ao:29  
     *SI\_CONFIG\_DIR* variable, ic:177  
     software group installed, ic:151

Defense Intelligence Agency  
     *See* DIA

---

Delete menu item  
     described, ug:81  
 derived profiles, ic:174 to ic:175  
 DES  
     (Data Encryption Standard)  
 desc field, dg:213  
 Desktop Access Tool  
     on Trusted Desktop subpanel, tg:36  
 Desktop Access tool  
     on Trusted Desktop subpanel, tg:4  
 /dev/kmem kernel image file  
     security violation, ap:543  
 Developer system support software  
     cluster name, ic:151  
     profile example, ic:147  
 developers  
     responsibilities, ap:545  
 development environment privs, dg:40  
 Device Administration button, ap:491  
 device allocation  
     ancillary files, ap:495  
     authorization, ap:486  
 Device Allocation action  
     using, ic:32  
 Device Allocation Manager  
     allocating and administering  
         devices, ap:488 to ap:515  
     launching, ao:49  
     overview, ao:143 to ao:145  
     using, aa:55  
 Device Manager  
     on Trusted Desktop subpanel, tg:36  
     on Trusted desktop subpanel, tg:30  
 device policy  
     procedure to set, ap:504  
 device special files  
     access policy, ap:485  
 device\_allocate file  
     Trusted Solaris modifications, ao:148  
 device\_allocate(4TSOL) file  
     action for editing, ap:13  
     described, ap:502  
 device\_clean(1MITSOL) command  
     described, ap:502  
 device\_clean(1MITSOL) script  
     in procedure for adding  
         devices, ap:509  
 device\_clean(1MITSOL) scripts  
     for tape devices, ap:496  
     review, ap:496  
 device\_deallocate file  
     Trusted Solaris modifications, ao:148  
 device\_maps file  
     Trusted Solaris modifications, ao:149  
 device\_maps(4TSOL) file  
     action for editing, ap:13  
     described, ap:502  
 device\_policy(4TSOL) file, ap:363  
 devices  
     access policy  
         defaults, ap:485  
         defining or redefining, ap:485  
     accessing, ap:488  
     adding, ic:198  
     administering, ap:485 to ap:515, tg:30  
     allocating and deallocating, aa:55  
     allocation, ao:34, ao:143 to ao:150,  
         tg:53  
     description, ug:89 to ug:93  
     introduction, ug:4  
     associated security risks, ap:486  
     authorizations, ao:27  
     authorizations, defined, dg:82  
     clean scripts, ao:147 to ao:148  
     clearing prior to reuse, ug:12  
     configuration files, ao:143, ao:148 to  
         ao:149  
     displaying allocation  
         information, ao:146  
     input device privileges, dg:293  
     label ranges, dg:124, ao:34, ao:149  
     modified Solaris commands, ao:145  
         to ao:147  
     non-allocatable  
         setting the label range, ap:487  
     overview, ao:34  
     policy

---

- table of defaults, ap:485
  - policy for accessing, ap:362
  - policy for new, ap:485
  - security policy, tg:53
  - setting device policy, ic:77
  - setting policy
    - procedure, ap:504
  - setting policy for, ap:485
  - setting security policy, ap:363
  - table of related
    - authorizations, ap:490
- dfstab file, ic:241, ap:403
- dfstab(4) file
  - action for editing, ap:14
- DGA
  - (Direct Graphics Access)
  - See also* X Window System
  - privileges, dg:293
- DGA (direct graphics access)
  - window privileges, ao:30
- DIA
  - Encodings Format* manual, la:4
  - IL requirements, la:23
- differences
  - between Trusted Solaris 2.x
    - releases, tg:4
  - from Solaris 2.x releases, tg:2, tg:5
  - from Trusted Solaris 1.2, tg:3, tg:7 to
    - tg:9
- dir field, dg:214
- dir: line in audit\_control file
  - example, aa:13
  - for files subdirectory, aa:10, aa:11
- Direct Graphics Access, *See* DGA
- directories
  - audit daemon pointer, aa:18
  - audit directories full, aa:17, aa:19 to
    - aa:20
  - audit directory locations, aa:10 to
    - aa:11, aa:67
  - audit\_control file
    - definitions, aa:12
  - changing
    - to JumpStart directory, ic:170
    - to mounted CD, ic:126, ic:138
    - to Trusted Solaris CD image on
      - local disk, ic:138, ic:140
  - changing flags, ap:378
  - changing labels and
    - privileges, ap:396
  - changing to mounted CD, ic:138
  - changing to Trusted Solaris CD image
    - on local disk, ic:138
  - diskfull machines, aa:42
  - files subdirectory, aa:46
  - files subdirectory for audit
    - records, aa:10
- JumpStart
  - adding files, ic:176, ic:177
  - copying files, ic:177, ic:184
  - copying installation files from
    - CD, ic:138, ic:141
  - creating, ic:132, ic:240
  - creating for SPARC
    - systems, ic:136 to ic:138
  - enabling access, ic:141 to ic:144
  - install server setup, ic:143
  - permissions, ic:136, ic:139
  - rules file example, ic:158
  - sharing, ic:241
  - making available for mounts, ap:403
  - mounting audit directories, aa:47
  - multilevel, tg:29
  - procedure for sharing with other
    - hosts, ap:403
  - security attributes, ap:378 to ap:383
  - suitable to audit daemon, aa:18
  - upgraded
    - privileges
      - upgrade file, ap:376
- disable command
  - modified for Trusted Solaris, ap:465
- discretionary access control, *See* DAC
- disk configuration files
  - copying to JumpStart
    - directory, ic:184
  - creating, ic:184
    - SPARC multiple disks, ic:186 to
      - ic:188

---

- SPARC systems, ic:184 to ic:185
  - creation using `prtvtoc`, ic:184
  - described, ic:180, ic:184
- disk space requirements, aa:21
- diskette
  - copying files from, ic:31
  - copying files to, ic:30
- diskettes
  - copying Trusted Solaris boot diskette, ic:137
  - formatting, ic:137
  - JumpStart directory
    - access, ic:142
    - creating for SPARC systems, ic:136 to ic:138
  - mounting, ic:137
- diskfull machines' audit directory, aa:42
- diskless boot flag, dg:38
- diskless clients
  - accessing a Trusted Solaris image, ic:190
  - adding, ic:193
  - boot server, ic:193
  - configuring, ic:193
  - platforms, ic:150
  - prerequisites, ic:189
  - providing a root password, ic:196
  - setting up home directories, ic:195
  - swap space, ic:150
  - task map, ic:20
- disks
  - managing use, ic:198
  - setting up, ic:198
- disksize* rule keyword
  - description and values, ic:164
  - rootdisk* matching, ic:168
- `dispadm` audit record, aa:312
- display
  - resetting after I/O interrupts, ic:112
- distributed computing, *See* IPC
- distributed systems' `auditreduce`
  - command use, aa:76
- `dminfo` command
  - Trusted Solaris modifications, ao:146
- DNS
  - (Domain Name Service)
  - setup, ic:86
- documents, policy for accessing, ap:362
- domain of interpretation, ao:93
- domainname* rule keyword, ic:163
- domains
  - rule keyword, ic:163
- dominance, la:15, la:17, cm:2, cm:3, cm:4, cm:6, cm:52, cm:68, cm:116, cm:136
- dominance of labels
  - described, ap:366
  - overview, ug:7, ao:4
  - strict dominance, ug:7
- dominate
  - ILs, dg:127
  - levels, dg:125, dg:160
  - markings, dg:129
- dontuse* profile keyword, ic:151, ic:156
- downgrade file sensitivity label*
  - authorization, la:13
- downgrading labels
  - guidelines, dg:98
  - privileges needed, dg:95, dg:96
  - X Window System, dg:293
- drag 'n drop
  - constraints, tg:20
  - modified for Trusted Solaris, tg:36
- drag and drop
  - configuring rules
    - , ap:434
- drag-and-drop
  - effect on ILs, ug:16
  - effect on SLs, ug:8
- drivers
  - kerneK statistics, ao:149
- `drvpolicy` audit record, aa:193
- `dtfile` audit records, aa:312
- `dtpad(ITSOL)` command
  - using in administrative actions, ap:14

---

`dtsession(1)` command  
     running  
         `updatehome(1MTSOL)`, ap:87  
`dtterm(1)` terminal  
     forcing the sourcing of  
         `.profile`, ap:81, ap:117, ap:101  
`dtwm(1)` command, ap:528  
`dtwmrc`  
     modifying, ap:426 to ap:427  
     `.dtwmrc` file  
         customizable by users, tg:4  
dynamic routing  
     added, tg:3  
     described, ap:282

**E**

`ebusy` string and `audit_warn`  
     script, aa:20  
Edit Encodings action  
     described, ap:13  
editing privileged executables, ap:553  
`eeprom` audit record, aa:313  
effective GIDs, *See* GIDs  
effective privileges  
     *See also* privilege sets  
     bracketing, dg:71, dg:72, dg:73  
     change UID, GUID, or SGUID, dg:56  
     code example, dg:73  
     defined, dg:56  
     privilege to change IDs, dg:58  
effective UIDs, *See* UIDs  
`egid` field, dg:214  
ellipsis points (...) rule field, ic:160  
e-mail  
     labels, la:23  
email  
     aliases, ap:184, ap:187  
     in Trusted Solaris, ug:11  
     listing mail queues, ap:187  
     managing, ap:177 to ap:210  
     options, ap:197 to ap:199  
     overview, ap:178 to ap:184  
     switching mail tools, ap:200 to ap:210  
     troubleshooting, ap:191 to ap:196  
emetric  
     described, ap:278  
emetrics  
     defined, ao:100  
enable command  
     modified for Trusted Solaris, ap:465  
enabling logins  
     after a reboot, ap:6  
End user system support software  
     cluster name, ic:151  
ending  
     signal received during auditing  
         shutdown, aa:20  
     terminating audit daemon, aa:39, aa:64  
endpoints, *See* communication endpoints  
`endprofent(3TSOL)`,  
     declaration, dg:216  
`endprofstr(3TSOL)`,  
     declaration, dg:216  
`enduserent(3TSOL)`  
     code example, dg:222  
     declaration, dg:215  
`eng_profile` example, ic:241  
`enter prom` audit record, aa:194  
Entire distribution software  
     cluster name, ic:151  
equal  
     ILs, dg:127  
     levels, dg:125, dg:160  
     markings, dg:129  
equals sign (=) in profile field, ic:174  
**ERRORS**  
     section on man pages, ap:523  
errors, dg:15  
     audit directories full, aa:17, aa:19 to aa:20  
     internal errors, aa:20

---

es locale name, ic:154  
 /etc/bootparams file  
     enabling JumpStart directory  
         access, ic:144  
 /etc/cron.d/CRON, cron(1MTSOL)  
     lock file, ap:93  
 /etc/default/login file  
     specifying MAXBADLOGINS, ap:43  
 /etc/defaultrouter file, tg:8  
     action for editing, ap:13  
 /etc/dfs/dfstab file, ic:241  
 /etc/dt/ directory, tg:20  
 /etc/dt/config/sys.dtprofile  
     file, tg:19  
 /etc/init.d directory  
     changing scripts, ap:553  
     starting and stopping scripts, ap:556  
 /etc/mail/sendmail.cf file  
     action for editing, ap:13  
 /etc/motd file  
     action for editing, ap:13  
 /etc/nologin file  
     disabling logins, ap:7  
 /etc/nsswitch.conf file, ic:86, tg:8  
 /etc/passwd file, ic:67  
 /etc/rc2.d directory  
     S05RMTMPFILES script, ap:7  
 /etc/security directory, aa:10  
 /etc/init.d/audit script  
     disabling auditing, aa:39  
     enabling auditing, aa:40  
 /etc/security/audit  
     directory, aa:10, aa:67  
 /etc/security/audit\_data  
     file, aa:17  
 /etc/security/audit\_event file  
     overview, aa:4 to aa:7  
     audit event type, aa:69  
     /etc/security/audit\_startup  
         file, aa:4  
     /etc/security/audit\_warn  
         script, aa:17, aa:18 to aa:20  
     /etc/security/boot directory, ap:326  
     /etc/shadow file, ic:67, ic:179  
     /etc/skel file, ap:83, ap:135  
     /etc/system file  
         See system file  
     /etc/syslog.conf file  
         privilege debugging, tg:41  
     /etc/system file, tg:41  
         label configuration file, tg:18  
     /etc/tsolgateways file, tg:8  
     /etc/vfstab file  
         mount options, ic:153  
 euid field, dg:214  
 event numbers, aa:6  
 event-class mappings  
     changing, aa:32, aa:58  
     planning, aa:31  
 events  
     C library functions, aa:341  
     categories, aa:6  
     including in audit trail, aa:4  
     kernel events  
         audit tokens, aa:70  
         auditconfig command  
             options, aa:23  
         described, aa:6  
     mapping to classes, aa:4  
     non-attributable, aa:7  
     numbers, aa:6  
     overview, aa:4, aa:7  
     record formats and, aa:69  
     user-level events  
         audit tokens, aa:70  
         auditconfig command  
             options, aa:23  
         described, aa:6  
 example  
     label view effects, la:29  
     MAC decision, la:16

---

examples  
     *See also* code examples  
     CMW labels, la:20  
     label planning, la:137 to la:176  
 exclamation mark (!) rule field, ic:160  
 exec audit record, aa:194  
 exec system call  
     CMW label values, dg:94  
     inheritable privileges, dg:76  
     privileges in new program, dg:79  
     reset\_il\_on\_exec, dg:94  
 exec\_args token  
     described, aa:154  
     praudit display, aa:155  
 exec\_env token  
     described, aa:155  
     praudit display, aa:156  
 executable files  
     assigning forced privileges, ap:563  
     editing while preserving  
         privileges, ap:553  
     privilege sets, ap:524  
 execution profiles  
     accessing, dg:216  
     All  
         allowing standard UNIX access  
             to commands and  
             actions, ap:526  
         contents, ap:580  
         described, ao:21  
         ordering in an account's profile  
         list, ap:527  
     All Actions  
         contents, ap:580  
     All Authorizations  
         contents, ap:580  
         described, ao:21  
     All Commands  
         contents, ap:580  
     assigning, ap:141, ap:142, ao:78 to  
         ao:80  
     assignments to roles, ap:588 to ap:590  
     Audit Control  
         contents, ap:580  
         described, ao:21  
     Audit Review  
         contents, ap:580  
         described, ao:22  
     Basic Actions  
         contents, ap:581  
         described, ao:22  
     Basic Commands  
         contents, ap:582  
         described, ao:22  
     boot, ap:553  
         contents, ap:587  
     checking, dg:40  
     controlling the use of actions, ap:528  
     Convenient Authorizations  
         contents, ap:582  
         described, ao:22  
     creating new for boot  
         commands, ap:553  
     cron  
         contents, ap:587  
         described, ao:22  
     Cron Management  
         contents, ap:582  
         described, ao:22  
     Cron Security  
         contents, ap:582  
         described, ao:22  
     custom, ap:116, tg:4  
     Custom Admin Role  
         contents, ap:582  
         described, ao:22  
     Custom Admin Secadmin Role  
         described, ao:22  
     Custom Oper Role  
         contents, ap:582  
         described, ao:22  
     Custom Root Role  
         contents, ap:582  
         described, ao:22  
     Custom Secadmin Role  
         contents, ap:582  
     default, ao:21  
     defined, ug:13  
     described, ap:366  
     Device Management  
         contents, ap:583

---

Device Security  
     contents, ap:583  
 dtwm  
     contents, ap:588  
 editing, ap:218  
 Enable Login  
     described, ao:22  
 Enable Logins  
     contents, ap:583  
 File System Management  
     contents, ap:583  
     described, ao:22  
 File System Security  
     contents, ap:583  
     described, ao:22  
 importance of order, ap:526  
 inetd  
     contents, ap:588  
 Mail Management  
     contents, ap:583  
     described, ao:23  
 Maintenance and Repair  
     contents, ap:584  
     described, ao:23  
 managing, ap:213 to ap:255  
 Media Backup  
     contents, ap:584  
     described, ao:23  
 Media Restore  
     contents, ap:584  
     described, ao:23  
 Network Management  
     contents, ap:584  
     described, ao:23  
 Network Security  
     contents, ap:584  
 NIS+ Administration  
     contents, ap:584  
     described, ao:23  
 NIS+ Security Administration  
     described, ao:23  
 NIS+ Security Administration  
     contents, ap:584  
 Object Access Management  
     contents, ap:585  
     described, ao:23  
 Object Label Management  
     contents, ap:585  
     described, ao:23  
 Object Privilege Management  
     contents, ap:585  
     described, ao:23  
 Outside Accred  
     contents, ap:585  
     described, ao:23  
 overview, ap:214 to ap:217, ao:21 to  
     ao:25  
 Printer Security  
     contents, ap:585  
     described, ao:23  
 Privileged Shells  
     described, ao:23  
 Process Management  
     contents, ap:585  
     described, ao:23  
 required  
     contents, ap:588  
 software administration, ao:19  
 Software Installation  
     contents, ap:586  
 System Management  
     contents, ap:585, ap:586  
 System Security  
     contents, ap:586  
 table of actions, ap:628 to ap:635  
 table of commands, ap:590 to ap:628  
 table of profile contents, ap:580 to  
     ap:588  
 updating, ic47 to ic49  
 User Management  
     contents, ap:586  
     described, ao:24  
 User Security  
     contents, ap:587  
     described, ao:24  
 verifying, ic48  
 where assigned, tg:17  
 where defined, tg:16  
`execve` audit record, aa:194  
`execve` system call  
     inheriting privileges across, ap:534

---

- replacing the executing program, ap:529
- existing*
  - partitioning* value, ic:156
  - size value for *filesys*, ic:152
- exit audit record, aa:195
- Exit control, ug:97
- exit prom audit record, aa:194
- exit token
  - described, aa:156
  - praudit display, aa:156
- explicit, partitioning* value, ic:156
- exporting directories, ap:403
- exporting information
  - rules for physical label, la:24
- exporting shared directories, ic:93
- exporting software, ap:520
- extended attributes, ap:371
- extended operations, dg:324
- external view, la:29

**F**

- fa audit class, aa:105
- fa audit flag, aa:98
- FAF\_ALL flag, dg:36
- FAF\_MLD flag, dg:35
- FAF\_PUBLIC flag, dg:36
- FAF\_SLD flag, dg:35
- failsafe login, tg:12
  - defined, ug:36
- failsafe session
  - recovering from startup file errors, ap:79
- failure
  - audit flag prefix, aa:9
  - turning off audit flags for, aa:9 to aa:10
- fallback mechanism
  - creating, ap:339
  - networks, ap:321
  - using for network configuration, ic:80
- fauditpsa audit record, aa:195
- fc audit class, aa:106
- fc audit flag, aa:98
- fchdir audit record, aa:196
- fchmod audit record, aa:197
- fchown audit record, aa:198
- fchroot audit record, aa:199
- fcntl audit record, aa:199
- fd audit class, aa:107
- fd audit flag, aa:98
- fdformat command, ic:137
- FDFS
  - mounting in Trusted Solaris, ap:385
- fdisk* profile keyword
  - example, ic:149
- features, operating system, dg:2
- fgetcmwfsrange system call,
  - declaration, dg:104
- fgetcmwlabel audit record, aa:204
- fgetcmwlabel system call,
  - declaration, dg:103
- fgetfatrflag(2TSOL),
  - declaration, dg:27
- fgetfpriv system call,
  - declaration, dg:62
- fgetfsattr system call,
  - declaration, dg:27
- fgetmldadorn system call,
  - declaration, dg:175
- fgetslldname audit record, aa:200
- fgetslldname system call
  - creating SLDs, dg:170
  - declaration, dg:175
- file
  - trusted network entries, ap:304
- file field, dg:214
- File Manager
  - accessing applications, ao:25
  - ACLs, ug:104 to ug:112
  - adding ACL entries, ug:108 to ug:109
  - as trusted process, ap:527

---

- changing ACL entries, ug:110 to ug:111
- changing file ILSs, ug:119 to ug:121
- changing file SLs, ug:115 to ug:119
- changing permissions, ug:106
- changing privileges, ao:30
- changing security attributes, ap:378
- deleting ACL entries, ug:112
- determining labels, ug:113
- differences in Trusted Solaris, ug:74
- displaying ACL entries, ug:106 to ug:107
- displaying basic information, ug:105
- labels, ug:113 to ug:121
- launching, ao:49
- modified for Trusted Solaris, tg:36
- overview, ao:126 to ao:130
- overview for users, ug:100 to ug:121
- passing inheritable privileges, ap:538
- permissions, ug:104 to ug:112
- Privileges dialog box, ap:537, ap:538
- viewing SLD contents, ug:53 to ug:55
- file privilege sets, ap:524
- file system attributes
  - interfaces, tg:61
  - list of, tg:27
  - storing, tg:26
- file system objects
  - flags, tg:27
- file systems, ao:134
  - fdfs type
    - mounting, ap:385
    - See also* code examples
    - See also* label ranges
    - See also* MLDs
    - See also* security attribute flags
    - See also* security attributes
    - See also* SLDs
    - access privileges, dg:18
    - accessing MLDs, dg:170
    - ACL information, dg:33
    - action for sharing, ap:403
    - administering, ic:198
    - attribute flags, ao:134
    - cachefs type
      - mounting, ap:384
    - changing security attributes using
      - mount -S(1MTSOL) command, ap:400
    - changing security attributes using
      - newsecfs(1MTSOL) command, ap:399
    - changing security attributes using
      - setfsattr(1MTSOL) command, ap:399
    - changing security attributes using
      - vfstab file, ap:401
  - differences in Trusted Solaris, ao:134 to ao:138
  - dump and restore, tg:39
  - fdfs type
    - mounting, ap:385
  - free space on audit servers, aa:12
  - hide upgraded names, dg:29
  - hsfs type
    - mounting, ap:385
  - ILSs, ao:134
  - IPC bind to file, dg:4
  - lofs type
    - mounting, ap:385
  - managing, ap:359 to ap:405
  - MLDs, ao:134
  - modified Solaris commands, ao:135, ao:138
  - mounting, ao:135 to ao:138, tg:38
  - multilabel, tg:28
  - nfs type
    - mounting, ap:385
  - object flags, tg:27
  - objects, dg:3
  - pcfs type
    - mounting, ap:385
  - polyinstantiated, dg:169
  - privileges, ao:29
  - privileges, defined, dg:53
  - review of concepts, ap:361 to ap:374
  - security attributes, ap:380 to ap:383, ao:134
  - security policy, dg:16, dg:17
  - setting security attributes, tg:26
  - sharing audit file system, aa:47

---

- single label, ap:382
- accessing SLDs, dg:171
- SLs, ao:134
- storing attributes, tg:26
- supported types, ap:384
- table of supported types, examples, notes, ap:386
- tmpfs type
  - mounting, ap:386
- Trusted Solaris commands, ao:134 to ao:135
- ufs type
  - mounting, ap:386
- file token
  - described, aa:156
  - praudit display, aa:157
- file(1) command
  - identifying multilevel directories, ap:63
- file\_audit privilege, dg:34, dg:36
- file\_audit privilege, dg:36
- file\_dac\_execute privilege, dg:18
- file\_dac\_read privilege, dg:18
- file\_dac\_search privilege, dg:18, dg:80
- file\_dac\_write privilege, dg:18, dg:223
- file\_downgrade\_il privilege, dg:96
- file\_downgrade\_sl privilege, dg:41, dg:95
- file\_mac\_read privilege, dg:18, dg:223
- file\_mac\_search privilege, dg:18
- file\_mac\_write privilege, dg:18
  - resulting in a file's dominating its directory's SL, ap:418
- file\_nofloat privilege, dg:96
- file\_owner privilege, dg:36, dg:95, dg:96
- file\_setfpriv privilege, dg:191
- file\_setpriv privilege, dg:57
- file\_upgrade\_il privilege, dg:95, dg:96
- file\_upgrade\_sl privilege
  - resulting in upgraded names, ap:418
- files
  - accessing, ao:35 to ao:46
  - ACLs, ug:100 to ug:112
  - allowed privileges, dg:54
  - authorizations, ao:27
  - authorizations, defined, dg:82
  - for booting, ic:197
  - changing flags, ap:378
  - changing labels, ap:378
  - changing privileges, ap:378
  - copying between File Managers, ug:118
  - copying from tape, ic:31
  - copying to other SLs with .copy\_files, ug:121
  - copying to tape, ic:30
  - forced privileges, dg:54
  - interpreted, dg:54
  - label privileges, dg:95
  - linking between File Managers, ug:118
  - linking to other SLs with .link\_files, ug:121
  - managing, ap:359 to ap:405
  - moving between File Managers, ug:115 to ug:118
  - permissions, ug:100 to ug:112
  - policy for accessing, ap:362
  - privilege sets, dg:53
  - privileges for creating core files, dg:58
  - procedure for changing labels and privileges, ap:396
  - review of concepts, ap:361 to ap:374
  - security attributes, ao:38
  - setting public object bit, aa:59
  - setting security attributes, tg:26
  - upgraded, ap:376
  - when writing to executables, dg:57
- files and file systems
  - begin scripts output, ic:174
  - copying

---

- JumpStart installation files from
  - CD, ic:138, ic:141
  - Trusted Solaris boot
    - diskette, ic:137
- creating local file systems, ic:152 to ic:153
- handling audit trail overflow, aa:91
- mounting, ic:47, aa:47
- preserving data
  - existing data, ic:153
- protecting, aa:45
- security attributes
  - auditing, aa:342
  - setting label, ic:45
  - sharing, ic:43
  - showing if shared, ic:45
- files subdirectory, aa:10, aa:46
- filesys profile keyword
  - description and values, ic:150
  - examples, ic:147 to ic:149
- filesystems
  - security attributes, ap:388
- finish rule field
  - described, ic:161
  - valid entries, ic:163
  - validation, ic:169
- finish scripts
  - adding, ic:177
  - rule field, ic:161
- finish.log file, ic:176
- flags, cm:25, cm:36, cm:66, cm:67, cm:88, cm:93, cm:98, cm:103, cm:108, cm:112, cm:129
  - audit\_control file line, aa:12
  - audit\_user file, aa:14 to aa:15
  - C library functions, aa:341
  - definitions, aa:8
  - file system objects, tg:27
  - machine-wide, aa:8, aa:12
  - overview, aa:8
  - policy flags, aa:24
  - process preselection mask, aa:16
  - syntax, aa:8 to aa:9
- flags, *See* security attribute flags
- flags: line in audit\_control file
  - described, aa:12
  - prefixes in, aa:10
  - process preselection mask, aa:16
- flags=, cm:25, cm:36, cm:66, cm:67, cm:88, cm:93, cm:98, cm:103, cm:108, cm:112, cm:129
- floating, *See* ILs
- floppy disk devices
  - accessing, ap:486
  - device\_clean script, ap:497
- floppy disks
  - physical labeling, la:24
- fm audit class, aa:105, aa:106, aa:107, aa:108, aa:110, aa:111, aa:112, aa:114, aa:115, aa:116
- fm audit flag, aa:98
- fn audit class, aa:109
- fn audit flag, aa:98
- Folders subpanel
  - differences in Trusted Solaris, ug:74
- Follow, ap:509
- font paths
  - window privileges, ao:30
- fonts
  - font list translation, dg:306
  - font path privileges, dg:294
- forced privileges, ap:524
  - See also* privilege sets
  - when turning off allowed, dg:70
  - assigning, ao:30
  - clearing, dg:70
  - defined, dg:54, ao:28
  - file systems, ao:134
  - on file systems, dg:33
  - set to none during write, dg:57
- fork audit record, aa:200
- fork system call
  - CMW label values, dg:93
  - creating processes, ap:529
  - guidelines for changing SLs, dg:98
  - inheritable privileges, dg:76

---

inheriting privileges across, ap:534  
   privileges in child, dg:77  
 fork1 audit record, aa:200  
 formatting diskettes, ic:137  
 fr audit class, aa:109  
 fr audit flag, aa:98  
 fr locale name, ic:154  
*free* size value for *filesys*, ic:152  
 free\_auth\_set(3TSOL)  
   code example, dg:88  
   declaration, dg:84  
 free\_profent(3TSOL)  
   code example, dg:218  
   declaration, dg:217  
 free\_profstr(3TSOL)  
   code example, dg:218  
   declaration, dg:217  
 free\_userent(3TSOL)  
   code example, dg:218  
   declaration, dg:215  
 freeze audit record, aa:270  
 French locale value, ic:154  
 Front Panel  
   accessing applications, ao:25  
   as trusted process, ap:527  
   differences in Trusted Solaris, ug:72  
     to ug:79  
   expansion, tg:4  
   modifying, ap:423  
   passing inheritable privileges, ap:538  
   Style Manager  
     changing session  
       characteristics, la:14  
   Subpanels  
     as trusted processes, ap:527  
 front panel in CDE, tg:34  
 FSA\_ACL value, dg:33  
 FSA\_ACLCNT value, dg:33  
 FSA\_AFLAGS value, dg:33  
 FSA\_APRIV value, dg:33  
 FSA\_APSA value, dg:34  
 FSA\_APSACNT value, dg:34  
 FSA\_DFACL value, dg:33  
 FSA\_DFACLCNT value, dg:33  
 FSA\_FPRIV value, dg:33  
 FSA\_LABEL value, dg:33  
 FSA\_LBLRNG value, dg:34  
 FSA\_MLDPFX value, dg:34  
 fsetcmwlabel audit record, aa:201  
 fsetcmwlabel system call,  
   declaration, dg:103  
 fsetfatrflag audit record, aa:201  
 fsetfatrflag system call,  
   declaration, dg:27  
 fsetfpriv system call,  
   declaration, dg:62  
 fstatfs audit record, aa:202  
 ftpd login audit record, aa:316  
 functions, *See* APIs  
 fuser audit record, aa:313  
 fw audit class, aa:110  
 fw audit flag, aa:98

## G

gateway host  
   defined, ao:87  
 gateways  
   concepts, ap:288 to ap:293  
 gen field, dg:212  
 German locale value, ic:154  
 get\_auth\_text(3TSOL)  
   code example, dg:87  
   declaration, dg:84  
 get\_priv\_text(3TSOL)  
   code example, dg:66  
   declaration, dg:64  
 getaudit audit record, aa:202  
 getaudit audit record, aa:203  
 getcil(3TSOL)  
   code example, dg:117  
   declaration, dg:105  
 getclearance system call  
   code example, dg:157  
   declaration, dg:154

---

getcmwfsrange audit record, aa:203  
 getcmwfsrange system call  
     declaration, dg:104  
 getcmwfsrange(2TSOL)  
     code example, dg:123  
 getcmwlabel audit record, aa:204  
 getcmwlabel system call  
     code example, dg:43, dg:120  
     declaration, dg:103  
 getcmwplabel system call  
     code example, dg:43, dg:117  
     declaration, dg:103  
 getcsl(3TSOL)  
     code example, dg:43, dg:117  
     declaration, dg:104  
 getdents audit record, aa:204  
 getdents system call  
     restricting from returning upgraded  
         names, ap:418  
 getfattrflag command  
     described, ap:378  
     overview, ao:131  
 getfattrflag system call  
     code example, dg:35  
     declaration, dg:27  
 getfattrflag(1TSOL) command  
     identifying MLDs, ap:63  
 getfile: RPC failed: error 5:  
     RPC Timed out  
     message, ic:144, ic:266  
 getfilepriv audit record, aa:205  
 getfpriv command  
     overview, ao:132  
     using to save privileges, ap:571  
 getfpriv system call  
     code example, dg:69  
     declaration, dg:62  
     privileges needed, dg:57  
 getfpriv(1TSOL), dg:67  
 getfsattr command  
     described, ap:382  
     overview, ao:135  
 getfsattr system call  
     code example, dg:33  
     declaration, dg:27  
 getlabel (1TSOL), dg:122  
 getlabel command  
     overview, ao:132  
 getmldadorn audit record, aa:205  
 getmldadorn system call  
     code example, dg:178  
     declaration, dg:175  
 getmsg audit record, aa:206  
     socket accept, aa:206  
     socket receive, aa:206  
 getmsgqcmwlabel audit record, aa:207  
 getmsgqcmwlabel system call,  
     declaration, dg:234  
 getpattr system call  
     code example, dg:37  
     declaration, dg:27  
 getpmsg audit record, aa:207  
 getportaudit audit record, aa:208  
 getppriv system call  
     code example, dg:41, dg:74, dg:76  
     declaration, dg:62  
 getprofent(3TSOL),  
     declaration, dg:216  
 getprofentbyname(3TSOL)  
     code example, dg:218  
     declaration, dg:216  
 getprofstr(3TSOL),  
     declaration, dg:216  
 getprofstrbyname(3TSOL)  
     code example, dg:218  
     declaration, dg:216  
 getsemcmwlabel audit record, aa:208  
 getsemcmwlabel system call  
     code example, dg:239  
     declaration, dg:235  
 getshmcmwlabel audit record, aa:209  
 getshmcmwlabel system call  
     code example, dg:241  
     declaration, dg:236

---

getslidname audit record, aa:209  
getslidname system call  
    code example, dg:45, dg:178  
    creating SLDs, dg:170  
    declaration, dg:175  
getuserent(3TSOL)  
    code example, dg:222  
    declaration, dg:215  
getuserentbyname(3TSOL)  
    code example, dg:48, dg:218  
    declaration, dg:215  
getuserentbyuid(3TSOL),  
    declaration, dg:215  
getvfsaent(3TSOL), code  
    example, dg:31  
getvfsafile(3TSOL), code  
    example, dg:31

## GFI

label encodings, la:3

gid field, dg:295

## GIDs

(group IDs)

assigning, ao:66

assigning to actions, ao:122

assigning to commands, ao:122

effective

    alternative to privileges, ap:524

    defaults, ap:540

    defined, ap:522

in execution profiles, ap:214, ao:21

network interfaces, ao:96

privilege to change, dg:58

remote host templates, ao:93

graphical user interfaces

    labels, tg:56

graphical user interfaces, *See* GUIs

Greenwich Meantime map, ic:268

group IDs

    assigning, ap:124

group IDs, *See* GIDs

group names

    assigning, ap:124

group token

    praudit display, aa:157

groupmgr audit record, aa:314

groups

    ACL entry, ug:103

    deletion precautions, ap:40

    managing, ao:52

    security requirements, ap:40

groups token

    described, aa:157

GUIs

(graphical user interfaces)

*See also* builders, GUI

CDE, dg:10

Motif, dg:10

Xlib, dg:10

Xlib objects, dg:289

## H

h\_alloc(3TSOL)

    code example, dg:148, dg:167

    declaration, dg:110, dg:157

h\_free(3TSOL)

    code example, dg:148, dg:167

    declaration, dg:110, dg:157

halt audit record, aa:314

handling caveats

    printer banners, la:47

hands-off installation

    requirements, ic:110

hard disk space requirements, aa:21

hard disks

    interfaces supported, ic:7

    local disks in networked

        systems, ic:59

    partitioning

        designating for *partitioning*

*default*, ic:156

        examples, ic:147 to ic:149

        excluding for *partitioning*

*default*, ic:151

        profile keyword, ic:156

*rootdisk* values, ic:152, ic:168 to ic:169

---

- size
  - root space, ic:150
  - rule keywords, ic:164, ic:167
- swap space
  - diskless client, ic:150
  - maximum size, ic:157
  - profile examples, ic:147, ic:148
- hard string with `audit_warn`
  - script, aa:19
- hardware
  - frame buffers, ic:235, ic:236, ic:237
  - graphics accelerators, ic:235, ic:236, ic:237
  - input devices, ic:236
  - installation requirements, ic:7
  - multimedia, ic:237
  - planning, ic:6 to ic:8
  - platform names and groups by
    - system, ic:233 to ic:234
  - platforms supported, ic:7
  - printers, ic:237
  - SBus components, ic:235, ic:236, ic:237
  - supported, ic:233 to ic:237
  - video, ic:237
- header field, dg:102
- header file locations, tg:50
- header files
  - auditing APIs, dg:187
  - authorization APIs, dg:82
  - clearance APIs, dg:153
  - label APIs, dg:100
  - Label builder APIs, dg:316
  - locations, list of, dg:334
  - MLD APIs, dg:173
  - privilege APIs, dg:59
  - profile database access APIs, dg:212
  - RPC APIs, dg:280
  - SLD APIs, dg:173
  - System V IPC APIs, dg:234
  - TSIX APIs, dg:247
  - user database access APIs, dg:212
  - X Window System APIs, dg:294
- header token
  - described, aa:71, aa:74, aa:158
  - fields, aa:71, aa:74
  - format, aa:158
  - order in audit record, aa:70
  - `praudit display`, aa:71, aa:159
- `header_len` field, dg:102
- `header_len` field, dg:101
- Help menu item
  - described, ug:95
- hexadecimal
  - to binary, dg:144, dg:147
- hexadecimal label equivalents
  - determining, ap:44
- `hextoalabel` command, dg:197
  - overview, ao:142
- `hidden_il_action`, ap:439
- hide upgraded names, dg:29
- Home dialog box
  - User Manager, ap:134 to ap:136
- home directories
  - assigning, ao:74 to ao:75
  - automounting, tg:3, tg:29
  - mounting, ic:47
  - setup, ic:88, ic:104
  - sharing, ic:43 to ic:44
- Host Manager
  - adding a host to a running
    - system, ap:410
  - adding diskless clients, ic:192
  - adding hosts, ic:120 to ic:121, ic:125, ic:191
  - described, ic:112
- host token
  - described, aa:159
  - `praudit display`, aa:159
- host types
  - CIPSO, ap:314
  - cipso, ao:89
  - MSIX, ap:312
  - msix, ao:89
  - network, tg:22
  - networking, ap:265 to ap:267, ap:306 to ap:319, ao:87
  - remote host templates, ao:93
  - RIPSO, ap:316

ripso, ao:89  
 sun\_tsol, ap:306, ao:89  
 table of templates and  
     protocols, ap:265  
 TSIX, ap:308  
 tsix, ao:89  
 unlabeled, ap:318, ao:89  
*hostaddress* rule keyword, ic:164  
 hostmgr audit records, aa:315  
*hostname* rule keyword  
     description and values, ic:164  
     example, ic:162  
 hosts  
     adding for network  
         installation, ic:121  
     assigning templates, ap:332 to ap:335,  
         ap:335 to ap:342  
     entering in network files, ic:75 to ic:81  
     entering in tnrhdb, ic:80 to ic:81  
     modifying templates, ic:79 to ic:80  
     networking concepts, ap:259  
     worksheet, ap:577  
 How Computer Users May Be Restricted  
     to a Single Sensitivity  
         Label, la:13  
 HSFS  
     mounting in Trusted Solaris, ap:385  
     procedure for mounting, ap:403  
 htobcl(3TSOL)  
     code example, dg:147  
     declaration, dg:111  
 htobclear(3TSOL)  
     code example, dg:166  
     declaration, dg:157  
 htobil(3TSOL), declaration, dg:111  
 htobs1(3TSOL), declaration, dg:111  
 human-readable audit record format  
     converting audit records to, aa:78 to  
         aa:84  
     described, aa:69

## I

I/O interrupt error messages, ic:112  
 iaddr field, dg:295  
 administrative labels  
     issues about names, la:27  
 icon labels  
     on windows, tg:19  
 icons  
     for device allocation, ic32, aa:55  
     for System\_Admin actions, ic40  
     using to launch actions, ic25  
     visibility  
         in the File Manager, ap:528  
         in the Workspace Menu, ap:528  
 identification  
     defined, ug:20  
     procedure, ug:22 to ug:23  
 identification and authentication  
     *See also* administrative roles,  
         assuming  
     before assuming a role, ap:5  
 getfattrflag(ITSOL) command  
 identifying MLDs, ap:63  
 Identity dialog box  
     User Manager, ap:124  
 Idle dialog box  
     User Manager, ap:143, ap:144  
 idle time  
     assigning, ao:82 to ao:83  
     customizing, ic37  
 idlecmod field, dg:212  
 idletime field, dg:212  
 IDs  
     *See also* audit IDs  
     *See also* GIDs  
     *See also* UIDs  
     audit, aa:3, aa:16, aa:73  
     audit session, aa:16, aa:73  
     audit user, aa:73  
     terminal, aa:16  
 ifconfig command  
     Trusted Solaris modifications, ao:106

---

*iil* field, dg:295  
**ILs**  
     (input information labels)  
     defined, ug:95  
     described, dg:291  
     security policy, dg:291  
     setting, la:22  
**INET Domain sockets**  
     (Internet Domain sockets)  
*il* field, dg:295  
**IL floating**  
     policy for devices, ap:485  
*il\_float\_policy*, ap:485  
*ilabel* field, dg:102  
*ilabel* token  
     described, aa:159  
     praudit display, aa:160  
*ilabel\_len* field, dg:101, dg:102  
**IL-relation**, ap:438  
**ILs**  
     (information labels)  
     *See also* CMW labels  
     *See also* code examples  
     *See also* labels  
     *See also* SLs  
     *See also* translation  
     API declarations, dg:350  
     changing file ILs, ug:119 to ug:121  
     changing input ILs, ug:95 to ug:96  
     in CMW label, dg:90  
     components, dg:91  
     conjoin, defined, dg:92  
     Customize Trusted Solaris  
         Configuration dialog  
         box, la:41  
     deciding whether to allow  
         floating, la:43  
     deciding whether to reset when a new  
         command is executed, la:43  
     deciding whether to use, la:42  
     default setting, tg:4  
     defined, ug:14, ao:3  
     described, ap:367  
     determining by window query, ug:94  
     determining with File  
         Manager, ug:113  
     devices  
         *il\_float\_policy*, ap:485  
     DIA requirement, la:23  
     displaying and hiding, ap:138 to  
         ap:140  
     dominate, dg:127  
     enabling, dg:28  
     enabling floating, dg:28  
     enabling floating system-wide, la:42  
     enabling message floating, dg:28  
     enabling semaphore set  
         floating, dg:28  
     enabling shared memory  
         floating, dg:28  
     enabling system-wide, la:42  
     equal, dg:127  
     file systems, ao:134  
     floating, ug:16  
         algorithms, dg:92  
         cases when it occurs, la:22  
         described, ap:367  
         guidelines, dg:99  
         object CMW label, dg:94  
         process CMW label, dg:93  
         stopping, dg:96  
         System V IPC objects, dg:233  
         TSIX, dg:245  
         X Window, dg:294  
     hidden\_il\_action, ap:439  
     initial setting on an empty  
         object, la:22  
     label overview, ao:4, ao:16  
     length of component fields, la:18  
     limits on floating, la:23  
     on banner and trailer pages, la:92  
     privileges  
         changing process IL, dg:95  
         downgrading ILs, dg:96  
         upgrading ILs, dg:96  
     purpose, dg:89  
     remote host templates, ao:93  
     resetting on `exec`, la:42, dg:29  
     setting an input IL, la:22  
     setting input IL, la:22

---

setting user and role accounts  
     locally, la:44  
 site implementation example, la:139  
     to la:143  
 TSIX, dg:246  
 uses  
     controlling information  
         distribution, la:23  
 visibility, ao:77  
 in.ftpd audit record, aa:316  
 in.rexecd audit record, aa:328  
 in.rshd audit record, aa:329  
 in\_addr token  
     described, aa:160  
     praudit display, aa:160  
 include files, *See* header files  
 INET Domain sockets, *See* IPC  
 inetd: service request audit  
     record, aa:316  
 information label, la:6 to la:10, cm:2 to  
     cm:17, cm:19, cm:20, cm:21,  
     cm:23, cm:25 to cm:43, cm:45,  
     cm:48, cm:58 to cm:70, cm:74,  
     cm:76, cm:79, cm:83, cm:98,  
     cm:99, cm:100, cm:113, cm:116,  
     cm:117, cm:118, cm:121, cm:125 to  
     cm:134, cm:136, cm:141  
 information label float audit  
     record, aa:210  
 INFORMATION LABELS section  
     label\_encodings example, la:164  
 information labels, *See* ILS  
 inheritable privileges, ap:534  
     *See also* privilege sets  
     assigning, ao:31  
     code example, dg:76  
     defined, dg:55, ao:28  
 init audit record  
     run level change  
         information, aa:330  
 init.d directory  
     starting commands during  
         boot, ap:553  
  
*initial compartments*  
     classification keyword, la:64  
 initial compartments=, cm:5, cm:19, cm:21  
     to cm:23, cm:112, cm:120, cm:124  
*initial markings*  
     classification keyword, la:64  
 initial markings=, cm:5, cm:19, cm:23 to  
     cm:24, cm:63, cm:112, cm:120,  
     cm:124  
 initialization files  
     Trusted Solaris differences  
         shells  
             initialization files  
                 differences, ap:77  
 Input IL field  
     described, ug:72  
 input information labels, *See* IILs  
 install server  
     copying Trusted Solaris CD to local  
         disk, ic:112  
     creating, ic:114  
     described, ic:108  
     requirement for network  
         installation, ic:108  
 install user  
     deleting, ic:38  
 install\_config command, ic:144  
*install\_type* profile keyword  
     description and values, ic:153  
     examples, ic:147  
     requirement, ic:145, ic:148  
     testing profiles, ic:180 to ic:182  
 Installation  
     label\_encodings> summary  
         information, la:3  
 installation  
     adding software, ap:544  
     boot commands, ic:55  
     differences from Solaris 2.x  
         releases, tg:12  
     differences from Trusted  
         Solaris 2.5, tg:12  
     using DNS, ic:86

---

manual reboot, ic:61  
 memory requirements, ic:7  
 networked workstations  
     config\_data file, ic:117  
     division of tasks, ic:53  
     setting date and time, ic:119  
 NIS+ clients, ic:97 to ic:106  
 NIS+ root master, ic:71 to ic:96  
 non-networked workstation, ic:63 to ic:70  
 over networks, ic:107 to ic:128  
 planning, ic:1 to ic:15  
 planning hardware, ic:6  
 root password creation, ic:61  
 upgrade option, ic:58  
 upgrade tasks, ic:49  
*installed* rule keyword  
     description and values, ic:164  
     rootdisk matching, ic:168  
 installf audit record, aa:317  
 integrating an application, dg:338  
 interactive installation  
     booting the system, ic:54  
     CDROM drive preparation, ic:54  
     CDROM task map, ic:16  
     JumpStart diskette installation task map, ic:19  
     networked workstations, ic:53 to ic:62  
     NIS+ rootmaster, ic:71 to ic:96  
 interfaces, *See* APIs  
 internationalization  
     changing printer output, ap:457, la:85  
 Internet Domain sockets, *See* INET Domain sockets  
 Internet Protocol, *See* IP  
 Internet-related tokens  
     socket token, aa:171  
 interoperability  
     between releases, tg:37  
 interprocess communication, *See* IPC  
 inter-window movement  
     window privileges, ao:30  
 inverse bit, cm:10, cm:12, cm:30, cm:32, cm:62, cm:70, cm:75, cm:77, cm:116, cm:124, cm:135  
 inverse word, cm:4, cm:8, cm:9, cm:10 to cm:12, cm:22, cm:23, cm:30, cm:31, cm:32, cm:41, cm:43, cm:62, cm:70, cm:127, cm:132, cm:135, cm:137  
 io audit class, aa:110, aa:112  
 io audit flag, aa:98  
 ioctl: ioctl to special devices audit record, aa:212  
 IP  
     (Internet Protocol)  
 IP addresses  
     rule keyword, ic:164  
     tnrddb database, ao:90  
 ip audit class, aa:111  
 ip audit flag, aa:98  
 IP labels  
     remote host templates, ao:93  
 IP Options field  
     Trusted Solaris data packets, ao:88  
     using for routing, ap:271  
 ip token  
     described, aa:161  
 IPC  
     (interprocess communication)  
     *See also* communication endpoints  
     *See also* RPC  
     *See also* System V IPC  
     *See also* TLI  
     *See also* TSIX library  
     *See also* X Window System  
     communication endpoint  
         objects, dg:4  
     file binding, dg:4  
     mechanisms described, dg:223  
     multilevel port connections, dg:228  
     network accreditation range, dg:244  
     objects, dg:4  
     polyinstantiated ports, dg:229  
     port binding, dg:4  
     privileges, ao:29

---

- privileges, defined, dg:53
- security attributes
  - changing, dg:245
  - contrast with Solaris, dg:12
  - described, dg:244
- security policy, dg:16, dg:223
- single-level port connections, dg:228
- IPC (interprocess communications)
  - multilevel ports, tg:72
  - remote procedure calls, tg:72
  - sockets, tg:69
  - System V IPC, tg:68
  - TLI (Transport Layer Interface), tg:69
  - trusted streams, tg:72
  - TSIX (Trusted Security Information Exchange), tg:71
- ipc token, aa:161 to aa:162
  - described, aa:161
  - praudit display, aa:162
- ipc type field values (ipc token), aa:162
- ipc\_dac\_read privilege, dg:232
- ipc\_dac\_write privilege, dg:232
- ipc\_downgrade\_il privilege, dg:233
- ipc\_mac\_rad privilege, dg:232
- ipc\_mac\_read privilege, dg:223, dg:232
- ipc\_mac\_write privilege, dg:232
- ipc\_nofloat privilege, dg:223, dg:233
- ipc\_owner privilege, dg:223, dg:232
- ipc\_perm token
  - described, aa:162
  - praudit display, aa:163
- ipc\_upgrade\_il privilege, dg:233
- ipcrm command
  - Trusted Solaris modifications, ao:139
- ipcs command
  - Trusted Solaris modifications, ao:139
- IPI interface, ic:7
- iport token
  - described, aa:163
  - praudit display, aa:163
- it locale name, ic:154
- Italian locale value, ic:154
- item size field values (arbitrary token), aa:152

**J**

- ja locale name, ic:154
- Japanese locale value, ic:154
- JumpStart directory
  - adding files with finish scripts, ic:176, ic:177
  - copying files
    - disk configuration files, ic:184
    - installation files from CD, ic:138, ic:141
    - using finish scripts, ic:177
  - creating, ic:132
    - diskette for SPARC systems, ic:136 to ic:138
    - example, ic:240
    - server, ic:139 to ic:141
  - install server setup, ic:143
  - permissions, ic:136, ic:139
  - rules file example, ic:158
  - sharing, ic:139 to ic:141, ic:241
- JumpStart installation
  - diskette task map, ic:19
  - network task map, ic:18

**K**

- kadb(1M) command
  - overriding default system(4) switch setting, ap:419
- karch rule keyword, ic:165
- kernel events
  - audit number range, aa:6
  - audit records, aa:179 to aa:277
  - audit tokens, aa:70
  - auditconfig command
    - options, aa:23
  - described, aa:6

---

kernel functions, tg:78  
 kernel switches  
     configurable, ap:416  
     configurable behaviors, ap:416  
 keyword  
     access related, cm:25, cm:36, cm:42,  
         cm:98, cm:113, cm:114,  
         cm:129 to cm:133  
     all compartment combinations  
         valid, cm:49, cm:49 to cm:50,  
         cm:82, cm:118, cm:119,  
         cm:142  
     all compartment combinations valid  
         except, cm:49 to cm:50,  
         cm:82, cm:113, cm:119,  
         cm:142  
     classification=, cm:49 to cm:51, cm:81,  
         cm:82, cm:113, cm:119,  
         cm:142  
     compartments=, cm:6, cm:25, cm:33  
         to cm:34, cm:59, cm:88,  
         cm:93, cm:98, cm:103,  
         cm:108, cm:112, cm:126 to  
         cm:141  
     flags=, cm:25, cm:36, cm:66, cm:67,  
         cm:88, cm:93, cm:98, cm:103,  
         cm:108, cm:112, cm:129  
     initial compartments=, cm:5, cm:19,  
         cm:21 to cm:23, cm:112,  
         cm:120, cm:124  
     initial markings=, cm:5, cm:19, cm:23  
         to cm:24, cm:63, cm:112,  
         cm:120, cm:124  
     markings=, cm:6, cm:25, cm:34 to  
         cm:35, cm:39, cm:40, cm:42,  
         cm:45, cm:67, cm:73 to cm:79,  
         cm:98, cm:103, cm:112,  
         cm:114, cm:126 to cm:141  
     maxclass=, cm:6, cm:25, cm:31 to  
         cm:32, cm:44, cm:45, cm:88 to  
         cm:110, cm:127, cm:129  
     minclass=, cm:5, cm:25, cm:29 to  
         cm:31, cm:44, cm:45, cm:59,  
         cm:71, cm:89 to cm:110,  
         cm:126 to cm:137  
     minimum clearance=, cm:50 to  
         cm:52, cm:84, cm:112, cm:115,  
         cm:119, cm:142  
     minimum protect as  
         classification=, cm:51,  
         cm:84, cm:113, cm:143  
     minimum sensitivity label=, cm:51,  
         cm:52, cm:84, cm:113, cm:115,  
         cm:143  
     name=, cm:19 to cm:20, cm:25, cm:26,  
         cm:28, cm:39, cm:40, cm:59,  
         cm:67, cm:73 to cm:79, cm:85,  
         cm:124 to cm:141  
     ominclass=, cm:6, cm:25, cm:29 to  
         cm:31, cm:71, cm:89 to  
         cm:105, cm:109, cm:110,  
         cm:129, cm:133, cm:135,  
         cm:137  
     only valid compartment  
         combinations, cm:49, cm:51,  
         cm:82, cm:113, cm:119,  
         cm:142  
     prefix, cm:25, cm:28, cm:92, cm:93,  
         cm:99, cm:104, cm:108,  
         cm:119, cm:125, cm:126,  
         cm:134, cm:137, cm:139  
     prefix=, cm:25, cm:28, cm:93, cm:94,  
         cm:99, cm:104, cm:108,  
         cm:119, cm:130, cm:133,  
         cm:135 to cm:141  
     sname=, cm:19, cm:20, cm:25, cm:27  
         to cm:28, cm:44, cm:45,  
         cm:59, cm:85, cm:89, cm:94,  
         cm:99, cm:104, cm:108,  
         cm:120, cm:124, cm:140  
     suffix, cm:25, cm:28, cm:89, cm:94,  
         cm:99, cm:104, cm:108,  
         cm:109, cm:119, cm:125,  
         cm:126, cm:139  
     suffix=, cm:25, cm:28, cm:89, cm:94,  
         cm:99, cm:109, cm:119,  
         cm:129, cm:130, cm:131,  
         cm:139, cm:140  
     value=, cm:19, cm:21, cm:29, cm:31,  
         cm:59, cm:85, cm:112,  
         cm:120, cm:124

---

keywords, la:63  
kill audit record, aa:213  
kmem(7D) kernel image file, ap:543  
ko locale name, ic:154  
Korean locale value, ic:154  
kstat(3), ao:149

## L

### Label builder

Cancel pushbutton, dg:321  
declarations, dg:316  
described, dg:315  
Downgrade SL Using IL  
pushbutton, dg:321  
extended operations, dg:324  
functionality, dg:320  
IL radio button, dg:321  
Reset pushbutton, dg:321  
SL radio button, dg:321

### label builder

*See also* code examples  
changing component names, la:113

### label builder interfaces, tg:56

### label clipping

API declarations, dg:303, dg:352  
translating with font list, dg:306

### label data types

accreditation ranges, dg:101  
banner fields, dg:102  
CMW label structure, dg:100  
information labels, dg:100  
label information, dg:101  
levels, dg:101  
sensitivity labels, dg:100  
setting flags, dg:100  
SL ranges, dg:101

### label encodings file

checking, ic:74  
copying, ic:94  
localizing, ic:6, ic:229  
modifying, ic:74 to ic:75  
other file constraints, ao:9  
overview, ao:5 to ao:6

### label names

avoiding abbreviations and  
acronyms, la:22

### label ranges

accreditation, dg:101, dg:133  
assigning, dg:93  
assigning to devices, ao:34  
checking, dg:124  
defined, ao:6  
described, ap:367, dg:123  
devices, ao:149  
in execution profiles, ao:21  
file systems  
API declarations, dg:348  
data structure, dg:101  
overview, la:7  
*See also* accreditation ranges  
setting on individual  
computers, ap:487

### label translation, la:18

### label view

example of effects, la:29  
process flag, la:32  
setting in `label_encodings`  
file, la:30

### label\_encodings file, la:62

access-related words, la:87  
adding to a government-supplied  
encodings, la:3  
API declarations, dg:348  
changing after system start-up, la:61  
changing classifications, la:63  
CHANNELS section, la:97, la:106  
checking, la:57  
classification keywords, la:63  
color names, dg:136  
copying to client, ic:99  
creating a site's version, la:3  
distributing changes, ap:42, ap:423,  
la:125 to la:135  
encoding example, la:149 to la:161  
government-supplied, la:73  
hints for managing, la:58  
information on, dg:137  
introduction, la:1

---

Label builder, dg:320  
 label translation flag, dg:39  
 LOCAL DEFINITIONS  
     section, la:110 to la:111  
 modifying, ic:65 to ic:66  
 multiple sensitivity labels, la:59  
 Non-English, dg:306  
 optional flags, la:113  
 placeholder files, la:58, la:64  
 planning, la:48  
 planning example, la:137 to la:176  
 preparing, la:55 to la:56  
 procedures, ap:480  
     assigning colors to labels or  
         words, la:121  
     changing administrative  
         labels, la:118  
     changing classifications, la:74  
     changing component names in  
         label builder, la:121  
     changing single-label  
         default, la:77  
     configuring channels, la:107  
     configuring printers, la:106  
     creating single-label file, la:79  
     displaying administrative label  
         names, la:119  
     displaying administrative label  
         substitutes, la:119  
     distributing label  
         information, la:129  
     distributing label information  
         changes, la:134  
     hiding labels, la:80  
     modifying, la:72  
     printing without banners and  
         trailers, ap:478  
     printing without labeled  
         pages, ap:464, ap:481  
     running without labels, la:73  
     specifying default and inverse  
         words, la:76  
     specifying default flags, la:120  
     specifying forced flags, la:120  
     protect as classification, la:87  
     retrieving version string, dg:114  
     running without labels, la:61  
     sample listing, la:179 to la:187  
     sections, la:62  
     single sensitivity labels, la:60  
     single- vs multilabel, la:59  
     specifying label colors, la:115 to  
         la:123  
     Sun extensions to GFI encodings, la:3  
     valid clearances, dg:154  
     valid labels, dg:102  
     view flag, dg:39  
     word order requirements, la:62  
 label\_encodings(4TSOL) file  
     action for editing and checking, ap:13  
 label\_info structure, dg:101  
 labelinfo(3TSOL)  
     code example, dg:137  
     declaration, dg:108  
 labelmax field, dg:212  
 labelmin field, dg:212  
 labels  
     *See also* clearances  
     *See also* CMW labels  
     *See also* ILS  
     *See also* SLs  
     *See also* translation  
     accreditation ranges, la:34  
     acquiring, dg:93  
     administrative, dg:115, tg:18, tg:19  
     advisory, la:18  
     advisory labels, tg:18  
     API declarations  
         CMW labels, dg:351  
         entire, dg:102 to dg:111, dg:348 to  
             dg:352  
         file systems, dg:348  
         ILs, dg:350  
         label clipping with font  
             list, dg:352  
         label types, dg:349  
         label\_  
             encodings(4TSOL), dg:  
                 348  
         levels, dg:349  
         reentrant routines, dg:349

---

SLs, dg:350  
 assigning to accounts, ao:76 to ao:78  
 assigning to files, ao:129  
 authorizations, dg:82, ao:27  
 avoiding abbreviations and  
     acronyms, la:22  
 changes in label encodings file, tg:18  
 changing on files and  
     directories, ap:396  
 checking validity, ao:142  
 classification component, ao:4  
 classification field length, la:11, la:12,  
     la:15  
 clearances, tg:53  
 color planning example, la:160  
 compartment component, ao:5  
 components  
     arranging the relationships, la:50  
 configuration, tg:19  
 configuration choices, tg:18  
 configuring on banner/trailer and  
     body pages, la:47  
 configuring, the big picture, la:39  
 converting to ASCII, ao:142  
 converting to hex, ao:142  
 default Label View, la:111  
 defined, dg:89  
 described, ap:367, tg:53  
 displayed in Trusted Solaris  
     environment, ug:67 to ug:69  
 displaying, ap:138 to ap:140  
 distributing changes, ap:41 to ap:42,  
     ap:423, la:125 to la:135  
 dominance, ug:7, la:17, ao:4  
 dominance relationships, ap:366  
 dominate levels, dg:125  
 downgrading, la:25  
 downgrading of SLs based on  
     ILs, la:23  
 equal levels, dg:125  
 finding process' current label, ic27  
 guidelines, dg:96  
 how used in MAC, la:5  
 ILs on printer output, la:24  
 installation example, ic:249, la:161 to  
     la:175  
 internal view, la:29  
 Label builder, dg:315  
 markings, ao:5  
 minimum number of SLs, la:1  
 minimum protect as  
     classification, la:88  
 on archived information  
     physical, la:24  
 on e-mail, la:23  
 on icons, tg:19  
 on windows, tg:19  
 overview, ao:4 to ao:16  
 overview of planning, la:47  
 planning, ic:4 to ic:6  
 planning example, la:137 to la:176  
 printed body pages, ap:452, la:84  
 privileged tasks, dg:95  
 privileges for overriding, ao:29  
 procedures  
     changing system file  
         information, la:133  
 reentrant routines, dg:110, dg:111  
 relationships, ug:7, dg:125, ao:4  
 required types defined at each  
     site, la:47  
 running without labels, la:1  
 setting on unlabeled file system, ic45  
 site analysis example, la:144 to la:148  
 specifying colors, la:115 to la:123  
 strictly dominate levels, dg:126  
 translation flag, dg:39  
 Trusted Solaris commands, ao:142  
 undefined, dg:115  
 user interface builder, tg:56  
 valid, la:33, dg:102  
 view, dg:139  
     hierarchy of settings, la:30  
     setting default label view, la:30  
 view flag, dg:39  
 view settings  
     hierarchy, la:30  
 visibility, tg:19  
     setting on user and role  
         accounts, la:44  
 visibility of components, la:21  
 well-formed, ao:6

---

worksheet examples, la:154 to la:161  
**Labels dialog box**  
     User Manager, ap:136, ap:140  
 labeltrans field, dg:212  
 labelvers(3TSOL)  
     code example, dg:114  
     declaration, dg:108  
 labelview field, dg:212  
**Latin America locale value, ic:154**  
 LBUILD\_CHECK\_AR operation, dg:326  
 LBUILD\_LOWER\_BOUND  
     operation, dg:326  
 LBUILD\_MODE operation, dg:324  
 LBUILD\_MODE\_CLR value, dg:324  
 LBUILD\_MODE\_CMW value, dg:324  
 LBUILD\_MODE\_IL value, dg:324  
 LBUILD\_MODE\_SL value, dg:324  
 LBUILD\_SHOW operation, dg:325  
 LBUILD\_TITLE operation, dg:325  
 LBUILD\_UPPER\_BOUND  
     operation, dg:326  
 LBUILD\_USERFIELD operation, dg:325  
 LBUILD\_VALUE\_CLR operation, dg:325  
 LBUILD\_VALUE\_CMW operation, dg:324  
 LBUILD\_VALUE\_IL operation, dg:324  
 LBUILD\_VALUE\_SL operation, dg:324  
 LBUILD\_VIEW operation, dg:326  
 LBUILD\_VIEW\_EXTERNAL value, dg:326  
 LBUILD\_VIEW\_INTERNAL value, dg:326  
 LBUILD\_WORK\_CMW operation, dg:325  
 LBUILD\_WORK\_IL operation, dg:325  
 LBUILD\_WORK\_SL operation, dg:325  
 LBUILD\_WORKJ\_CLR operation, dg:325  
 LBUILD\_X operation, dg:325  
 LBUILD\_Y operation, dg:326  
 lchown audit record, aa:214  
 LD\_LIBRARY\_PATH, dg:332  
**levels**  
     defined, dg:125, dg:160  
     relationship, dg:125  
     relationships, dg:160  
     *See also* labels  
         translating IL, dg:130  
         upper and lower bounds, dg:132, dg:162  
 lgetcmwlabel audit record, aa:204  
 lgetcmwlabel system call,  
     declaration, dg:103  
 liaison token  
     described, aa:163  
     praudit display, aa:164  
**libraries, C functions, aa:341**  
**libraries, compile**  
     auditing APIs, dg:187  
     authorization APIs, dg:82  
     clearance APIs, dg:153  
     label APIs, dg:100  
     Label builder APIs, dg:316  
     MLD APIs, dg:173  
     privilege APIs, dg:59  
     profile database access APIs, dg:212  
     RPC APIs, dg:280  
     SLD APIs, dg:173  
     System V IPC APIs, dg:234  
     trusted shared libraries, dg:332  
     TSIX APIs, dg:247  
     user database access APIs, dg:212  
     X Window System APIs, dg:294  
**library routines**  
     API declarations, dg:362  
     removed, tg:95 to tg:97  
     security policy on man pages, dg:331  
     Solaris, tg:91 to tg:95  
     Trusted Solaris, tg:84 to tg:91  
 libt6(3NTSOL) library, ap:93  
 link audit record, aa:214  
 .link\_files file  
     described, ug:121  
     using, ap:87  
**linking**  
     system privileges, ao:30  
**links**  
     symbolic  
         MAC and IL attributes, ap:377

---

list\_devices command  
     Trusted Solaris modifications, ao:146  
 list\_devices(1MTSOL) command  
     described, ap:502  
 lo audit flag, aa:98  
 loadable modules  
     system privileges, ao:30  
 LOCAL DEFINITIONS section  
     label\_encodings example, la:172  
     label\_encodings file, la:3, la:110  
         to la:111  
 local file systems  
     creating, ic:152 to ic:153  
 local.login file  
     defining printers, ap:481  
 locale profile keyword  
     description and values, ic:154  
 Lock control, ug:97  
 lock control, ug:32 to ug:33  
 lock field, dg:212  
 lock screen  
     specifying after idle time, ao:82  
 LOFS  
     mounting in Trusted Solaris, ap:385  
 lofs file system  
     modified for Trusted Solaris, tg:29  
 log files  
     begin scripts output, ic:174  
     finish scripts output, ic:176  
     installation output, ic49, ic:61  
     security violation from  
         sharing, ap:543  
     upgrade output, ic50  
 logical AND rule field, ic:160  
 .login file, ap:135  
 login  
     authorizations, ao:27  
     by administrative roles, ap:5  
     disabled, ug:35  
     enabling, ug:35 to ug:36  
     example, ug:38 to ug:39  
     failsafe, ug:36, tg:12  
     fixing initialization problems, ug:36  
     procedure, ug:20 to ug:31  
 login audit record  
     logout, aa:318  
     rlogin, aa:317, aa:318  
     telnet login, aa:318  
     terminal login, aa:317  
 login authorizations, defined, dg:82  
 login record  
     praudit display, aa:72  
 login sequence, ap:7  
 login shells  
     assigning, ao:67  
 login/logout messages, copying to single  
     file, aa:81  
 logins  
     enabling after a reboot, ap:6  
     maximum allowed number of  
         failures, ap:42  
     opening an account closed by too  
         many failed logins, ap:43  
     setting the maximum number of  
         failures, ap:43  
 logout  
     procedure, ug:33 to ug:34  
     specifying after idle time, ao:82  
 LONG\_CLASSIFICATION flag, dg:139  
 LONG\_WORDS flag, dg:139  
 lpadmin command  
     modified for Trusted Solaris, ap:465  
 lpc command  
     modified for Trusted Solaris, ap:465  
 lpr command  
     modified for Trusted Solaris, ap:465  
 lprm command  
     modified for Trusted Solaris, ap:465  
 lpsched command  
     modified for Trusted Solaris, ap:465  
 lpsched audit records, aa:319 to aa:320  
 lpstat command  
     modified for Trusted Solaris, ap:465  
 lpssystem command  
     modified for Trusted Solaris, ap:465

---

`lpctest` command  
     modified for Trusted Solaris, ap:465  
`lsetcmwlabel` audit record, aa:253  
`lsetcmwlabel` system call,  
     declaration, dg:103  
`lstat` audit record, aa:215  
`lxstat` audit record, aa:215

**M**

MAC  
 (mandatory access control)  
*See also* security policy  
 accessing System V IPC  
     objects, dg:232  
 bypassing restrictions, ap:523  
 cautions about override  
     privileges, ap:543  
 clearance limits, dg:13  
 comparing labels, la:5  
 defined, ug:5, ao:2  
 described, ap:368  
 file access, ao:36  
 guidelines for bypassing, dg:97  
 incoming packets  
     packets  
     incoming  
         MAC rules, ap:288  
 labels, la:1  
 outgoing packets, ap:285  
 override privileges, ap:523  
 policy for devices, ap:485  
 privilege bracketing, dg:71  
 security policy, dg:13  
 SL limits, dg:13, dg:89  
`machine halt` audit record, aa:314  
`machine reboot` audit record, aa:327  
 macros for privileges, tg:58  
 macros, *See* privilege macros  
 mail  
     aliases, ap:184 to ap:187  
     creating `audit_warn` alias, aa:52  
     default mail utility, tg:33  
     differences in Trusted Solaris, ug:75  
     listing mail queues, ap:187  
     managing, ap:177 to ap:210  
     messages, policy for access to, ap:362  
     options, ap:197 to ap:199  
     overview, ap:178 to ap:184  
     privacy options, tg:33  
     switching mail tools, ap:200 to ap:210  
     troubleshooting, ap:191 to ap:196  
 mail accounts, ic:197  
 mail icon  
     modified for Trusted Solaris, tg:36  
 .`mailrc` file, ap:80  
 maintenance commands, aa:339  
`man(1)` command, ap:86, ap:87  
 man page locations, tg:50  
 man pages, ic:148  
     accessing for all bundled  
         products, ap:86 to ap:87  
     ERRORS sections, ap:523  
 mandatory access control, cm:1, cm:59 to  
     cm:61  
 mandatory access control, *See* MAC  
 manifest constants  
     authorizations  
         administrative, tg:105  
         complete list, tg:106  
         described, tg:104 to tg:108  
         user, tg:105  
     privileges  
         described, tg:100 to tg:104  
         network, tg:104  
         new, tg:103  
         removed, tg:102  
         retained, tg:101  
         system, tg:104  
         windows, tg:104  
 MANPATH environment variable, ap:86  
     to ap:87  
 manual pages  
     modified, dg:330  
     requesting, dg:330  
     security policy on, dg:331

---

mapped memory, access checks, dg:226  
 mappings  
     multilevel, dg:278  
     single-level, dg:278  
 marketing\_profile example, ic:242  
 markings  
     defined, ug:15  
     described, ap:369  
     dominate, dg:129  
     equal, dg:129  
     field length, la:18  
     planning example, la:150  
     worksheet example, la:157  
 markings label component  
     defined, ao:5  
 markings=, cm:6, cm:25, cm:34, cm:39,  
     cm:40, cm:42, cm:45, cm:67, cm:73  
     to cm:79, cm:98, cm:103, cm:112,  
     cm:114, cm:126 to cm:141  
 mask, process preselection  
     C library functions, aa:341  
     described, aa:16  
     reducing storage costs, aa:21 to aa:22  
 masks  
     *See also* process preselection mask  
     *See also* TSIX library  
     ACL entry, ug:103  
 matching  
     derived profiles, ic:174  
     order for rules, ic:158, ic:161  
     rootdisk values, ic:168 to ic:169  
 max field, dg:214  
 MAXBADLOGINS variable, tg:4  
 maxclass=, cm:6, cm:25, cm:31 to cm:32,  
     cm:44, cm:45, cm:88, cm:90,  
     cm:110, cm:127, cm:129  
 maximum SL  
     remote host templates, ao:93  
 media labeling  
     clean scripts, ao:147  
 memcntl audit record, aa:216  
 memory  
     displaying amount installed, ic:112  
     minimum required, ic:7  
     rule keyword, ic:162, ic:165  
     setting size, ic:181  
     swap space size and, ic:157  
 memsize rule keyword  
     description and values, ic:165  
     example, ic:162  
 message queues  
     *See also* code examples  
     *See also* System V IPC  
     API declarations, dg:234, dg:355  
     IL floating, dg:233  
     overriding restrictions, ao:29  
     system privileges, ao:30  
 microprocessors  
     rule keywords, ic:163  
 min field, dg:214  
 minclass=, cm:5, cm:25, cm:29 to cm:31,  
     cm:44, cm:45, cm:59, cm:71, cm:89  
     to cm:110, cm:126 to cm:137  
 minfree: line in audit\_control file  
     audit\_warn condition, aa:19  
     described, aa:12  
 minfree: line in audit\_control file  
     audit\_warn condition, aa:19  
 minimum clearance  
     label encodings file, ao:9  
 minimum clearance=, cm:50 to cm:52,  
     cm:84, cm:112, cm:115, cm:119,  
     cm:142  
 minimum labels  
     assigning, ap:137  
 minimum protect as classification  
     example, la:88  
     printed on banner/trailer  
         pages, la:87  
     setting, la:88  
 minimum protect as  
     classification=, cm:51, cm:52,  
     cm:84, cm:113, cm:143  
 minimum sensitivity label=, cm:51,  
     cm:52, cm:84, cm:113, cm:115,  
     cm:143

---

minimum sensitivity labels  
     account label range, ao:10  
 minimum SLs, la:6  
     assigning to users, ao:77  
     described, ap:369  
     equal to clearance on a multiple-SL system, la:13  
     equal to clearance on a single-SL system, la:13  
     remote host templates, ao:93  
     worksheet example, la:160  
 minus (-) audit flag prefix, aa:9, aa:168, aa:169  
 minus sign (-)  
     in begin and finish scripts, ic:188  
     in rules, ic:163  
 MIT Magic Cookie, tg:4  
 mkdir audit record, aa:216  
 mknod audit record, aa:217  
 mldgetcwd(3TSOL)  
     code example, dg:179  
     declaration, dg:177  
 mldgetfattrflag system call  
     code example, dg:35  
     declaration, dg:27  
 mldlstat audit record, aa:217  
 mldpwd(1TSOL) command, ap:377  
 mldrealpath(1TSOL) command  
     identifying multilevel directories, ap:63  
 mldrealpath(3TSOL)  
     code example, dg:179  
     declaration, dg:177  
 mldrealpath1(3TSOL),  
     declaration, dg:177  
 MLDs  
     (multilevel directories)  
     *See also* code examples  
     *See also* SLDs  
     accessing, dg:170  
     adorned names, dg:172  
     adorned pathnames, ap:365  
     API declarations, dg:174 to dg:177, dg:354  
     backing up, ap:64  
     creating, dg:170  
     defined, ug:10  
     described, ap:369, dg:169  
     example, ug:53 to ug:55  
     file systems, ao:134  
     identifying, ap:63  
     information structure, dg:174  
     mounting, ap:377  
     mounting on unlabeled hosts, ap:377  
     prefix on file systems, dg:34  
     privilege requirements, ap:377  
     privileged tasks, dg:173  
     querying MLD flag, dg:35  
     security attribute flags, dg:35  
     security policy, dg:170  
     structure, dg:170  
     symbolic links, dg:171  
     used by applications, dg:171  
     working with, ap:56 to ap:65  
 mldsetfattrflag audit record, aa:218  
 mldsetfattrflag system call  
     code example, dg:35  
     declaration, dg:27  
 mldstat audit record, aa:217  
 mldstat system call  
     code example, dg:180  
     declaration, dg:175  
 mmap audit record, aa:218  
 modctl audit record  
     MODADDMAJBIND command, aa:219  
     MODCONFIG command, aa:219  
     MODLOAD command, aa:220  
     MODUNLOAD command, aa:220  
 model name, ic:112  
*model* rule keyword  
     description and values, ic:166  
     example, ic:162  
 modify at admin authorization, ap:95  
 modify at user authorization, ap:96  
 modify cron admin authorization, ap:96  
 modify cron user authorization, ap:96  
 modify system files audit record, aa:302

---

ModLabelData structure, dg:327  
 modload audit record, aa:320  
 modunload audit record, aa:320  
 monitoring audit trail in real time, aa:21  
 motd file  
     action for editing, ap:13  
 Motif, tg:73  
 Motif application  
     described, dg:304  
     Label builder widgets, dg:327  
     online help, dg:328  
     source code, dg:309 to dg:313  
 Motif, described, dg:10  
 mount audit record, aa:221  
 mount command, ic:112, ic:137  
     Trusted Solaris modifications, ao:136  
 mount\_hfs command  
     Trusted Solaris modifications, ao:136  
 mount\_nfs command  
     Trusted Solaris modifications, ao:137  
 mount\_tmpfs command  
     Trusted Solaris modifications, ao:137  
 mount\_ufs command  
     Trusted Solaris modifications, ao:136  
 mountd audit record, aa:321  
 mountd command  
     Trusted Solaris modifications, ao:136  
 mounting  
     begin script caution, ic:174  
     defined for Trusted Solaris, ao:99  
     diskettes, ic:137  
     displaying mounted file systems, ic:112  
     overview, ao:124 to ao:125  
     Trusted Solaris CD, ic:126, ic:138  
     Trusted Solaris differences, ao:135, ao:138  
     by Trusted Solaris installation, ic:176  
     unlabeled file systems, ic:93  
 mounts  
     managing, ap:359 to ap:405  
     permitted file systems, ap:384  
     procedure for TMPFS file systems  
         tmpfs type  
         procedure for mounting, ap:403  
         troubleshooting, ap:405  
 msgctl audit record  
     IPC\_RMID command, aa:222  
     IPC\_SET command, aa:223  
     IPC\_STAT command, aa:224  
 msgget audit record, aa:225  
 msggetl audit record, aa:226  
 msggetl system call  
     code example, dg:236  
     declaration, dg:234  
 msgrcv audit record, aa:227  
 msgrcvl audit record, aa:227  
 msgrcvl system call  
     code example, dg:238  
     declaration, dg:234  
 msgsnd audit record, aa:228  
 msgsndl audit record, aa:229  
 msgsndl system call  
     code example, dg:236  
     declaration, dg:234  
 MSIX host type  
     defined, ao:89  
     described, ap:312  
 msix host types, tg:22  
 MT\_SAFE, dg:148, dg:167  
 multilabel file systems, dg:123  
 multilevel directories, tg:29  
     seen by Calendar Manager, tg:4  
 multilevel directories, *See* MLDs  
 multilevel mappings, dg:278  
 multilevel port bindings  
     network privileges, ao:29  
 multilevel ports  
     behavior, tg:23  
     contrast to polyinstantiated, dg:229  
     described, dg:228  
     example application, dg:265  
     introduction, tg:22  
     replying at equal SL, dg:245  
     RPC, dg:278

---

multilevel sessions  
     defined, ug:9  
 multiple disk configuration file  
     SPARC systems, ic:186 to ic:188  
 multiple lines in rules, ic:163  
 munmap audit record, aa:229

**N**

na audit class, aa:113  
 na audit flag, aa:98  
 naflags: line in audit\_control  
     file, aa:12  
*name*  
     classification keyword, la:63  
 name field, dg:212, dg:213  
 NAME INFORMATION LABELS section  
     label\_encodings example, la:172  
 name server, ic:108  
 name service  
     NIS+, tg:15  
 Name Service Switch action  
     described, ap:13  
     modifying trusted network  
         entries, ap:304  
 name=, cm:19 to cm:20, cm:25, cm:26,  
     cm:28, cm:39, cm:40, cm:59,  
     cm:67, cm:73 to cm:79, cm:85,  
     cm:124 to cm:141  
 names  
     audit classes, aa:8  
     audit files  
         closed files, aa:75  
         form, aa:74  
         still-active files, aa:75  
         time stamps, aa:75  
         use, aa:74  
     audit flags, aa:8  
     audited kernel events, aa:6  
     IDs  
         audit, aa:3, aa:16  
         audit session, aa:16, aa:73  
         terminal, aa:16  
     mount-point path names on audit  
         servers, aa:10  
 names, abbreviations, dg:334  
 names/naming  
     derived profile names, ic:175  
     host name, ic:164  
     profile names, ic:146  
     rules file, ic:159, ic:162  
     software group cluster names, ic:151  
     system model names, ic:166  
     system platform name  
         determination, ic:233  
 naming service  
     choosing in Solstice, ic:35, ap:26, ap:28  
 ndd command  
     overview, ao:149  
     Trusted Solaris modifications, ao:106  
 net\_downgrade\_il privilege, dg:246  
 net\_downgrade\_sl privilege, dg:246  
 net\_mac\_read privilege, dg:228  
 net\_nofloat privilege, dg:223, dg:245  
 net\_reply\_equal privilege, dg:245,  
     dg:267  
 net\_setclr privilege, dg:246  
 net\_setid privilege, dg:246  
 net\_setpriv privilege, dg:247  
 net\_upgrade\_il privilege, dg:223,  
     dg:246  
 .netscape file, ap:80  
 netstat command  
     Trusted Solaris modifications, ao:107  
 netstat(IMTSOL)  
     example, ao:103  
 network  
     commands, tg:24  
     distributed services, tg:25  
     host types, tg:21  
     interface database, tg:23  
     packets recognized, tg:25  
     privileges, tg:104  
     routing, tg:23  
     security attributes, tg:71  
     utility commands, tg:24

---

network accreditation ranges  
     described, ap:262  
     example, ap:325  
     requirements, ap:268  
     setting up, ap:342  
 network databases  
     where configured, tg:17  
 network installation  
     custom JumpStart installation  
         example, ic:135  
     diskless booting  
         task map, ic:20  
     hands-off configuration, ic:111  
     JumpStart installation task map, ic:18  
     planning, ic:8 to ic:10  
     preparation, ic:107, ic:128  
     task map, ic:17  
 network interface, tg:23  
     databases, tg:23  
 network interfaces  
     adding, ic41  
     configuring, ap:343 to ap:350  
     defined, ao:86  
     described, ap:262  
     requirements, ap:269  
     tnidb(4TSOL), ao:96  
 network protocols  
     interoperability, tg:37  
*network* rule keyword  
     description and values, ic:167  
     example, ic:162  
 network utilities, tg:24  
 networked workstations  
     planning space, aa:33  
 networking  
     concepts, ap:259 to ap:293  
 networks  
     *See also* IPC  
     default labeling, ap:288, ap:306 to  
         ap:325  
     example, ao:103 to ao:105  
     fallback mechanism, ap:321  
     heterogeneous, ap:263  
     modified Solaris commands, ao:106  
         to ao:108  
     overview, ao:85 to ao:112  
     privileges, ao:29  
     procedures for configuring, ap:329 to  
         ap:357  
     remote host templates, ao:93  
     security attributes, ap:325, dg:12  
     Trusted Solaris commands, ao:108 to  
         ao:112  
     using templates, ap:320  
 never-audit flags, aa:14 to aa:15  
 NEW\_LABEL flag, dg:144  
 newgroups token  
     described, aa:164  
     praudit display, aa:164  
 newsecfs command  
     overview, ao:135  
 newsecfs command)  
     described, ap:382  
 .newsrsrc file, ap:80  
 NFS  
     mounting in Trusted Solaris, ap:385  
 NFS request audit record  
     automount, aa:307  
 NFS request audit record  
     mount, aa:221, aa:321  
     mountd, aa:321  
     unmount, aa:321  
 nfsd command  
     Trusted Solaris modifications, ao:138  
 nfsstat command  
     Trusted Solaris modifications, ao:138  
 nice audit record, aa:230, aa:257  
 NIS+  
     client host  
         adding to a running  
             system, ap:410  
     configuration files not  
         administered, ap:409  
     master  
         loading trusted network  
             databases at boot, ap:326  
     tables

---

- adding protected data, ap:410
  - new in Trusted Solaris, ap:409
- NIS+ commands
  - in System\_Admin actions, tg:4
- NIS+ credentials
  - Password dialog box, ao:73
- NIS+ domain
  - client setup, ic:103
  - configuring root master, ic:71 to ic:96
  - setup, ic:85
  - updating credentials, ic:87
- NIS+ name service, tg:15
- NIS+, managing, ap:407 to ap:411
- niscat(1) command
  - action to invoke, ap:14
- nisclient(1M) command
  - action for creating NIS+ client, ap:13
- nispopulate(1MTSOL) file
  - action for invoking, ap:13
- nisserver(1M) file
  - action for invoking, ap:13
- nsswitch.conf(4TSOL) file
  - action for editing, ap:13
- no audit class, aa:114
- no audit flag, aa:98
- NO\_CLASSIFICATION flag, dg:139
- NO\_CORRECTION flag, dg:144
- non-administrative roles
  - defined, ao:26
  - described, ap:106, ap:107
- nonattributable flags in audit\_control
  - file, aa:12
- non-networked workstations
  - planning space, aa:33
- normal user
  - accessing devices, ap:486
- normal word, cm:4, cm:8, cm:9, cm:11,
  - cm:12, cm:21, cm:74
- nsswitch.conf(4TSOL) file
  - trusted network database
    - entries, ap:304
- nt audit class, aa:115
- nt audit flag, aa:98
- num\_clients profile keyword, ic:154
- numbers
  - audit events, aa:6

**O**

- object
  - defined, ug:6
- object reuse
  - requirements
    - clearing names of empty
      - directories, ap:377
- object-reuse
  - clean scripts, ao:147
  - introduction, ug:12
- objects, dg:3 to dg:4
- Occupy Workspace
  - example, ug:55 to ug:57
- occupying workspaces
  - Trusted Solaris environment, ug:97
- ok prompt, ic:54
- OLIT (OpenLook Interface Toolkit, tg:73
- ominclass=, cm:6, cm:25, cm:29 to cm:31,
  - cm:71, cm:89, cm:90, cm:93,
  - cm:95, cm:99, cm:100, cm:104,
  - cm:105, cm:109, cm:110, cm:129,
  - cm:133, cm:135, cm:137
- ONLY\_INFORMATION\_LABEL
  - flag, dg:144
- opaque token
  - described, aa:165
  - praudit display, aa:165
- open audit record
  - read, aa:230
  - read, create, aa:231
  - read, create, truncate, aa:231
  - read, truncate, aa:232
  - read, write, aa:232
  - read, write, create, aa:233
  - read, write, create,
    - truncate, aa:233
  - read, write, truncate, aa:234

write, aa:234  
 write, create, aa:235  
 write, create,  
     truncate, aa:235  
 write, truncate, aa:236  
 Open Look Interface Toolkit (OLIT), dg:10  
 open networks  
     defined, ao:87  
 open\_priv, ap:485  
 OpenWindows, dg:10  
 openwin-menu file, tg:15  
 oper role, *See* system operator  
 operating system features, dg:2  
 /opt/SUNWadm/2.3/bin/dbmgr audit  
     record, aa:310  
 /opt/SUNWadm/2.3/bin/groupmgr  
     audit record, aa:314  
 /opt/SUNWadm/2.3/bin/hostmgr  
     audit records, aa:315  
 /opt/SUNWadm/2.3/bin/printmgr  
     audit records, aa:324  
 /opt/SUNWadm/2.3/bin/profmgr  
     audit records, aa:325 to aa:326  
 /opt/SUNWadm/2.3/bin/serialmgr  
     audit records, aa:332  
 /opt/SUNWadm/2.3/bin/usermgr  
     audit records, aa:336  
 OS servers  
     adding, ic:120, ic:128  
     converting from standalone, ic:190  
     described, ic:59, ic:108  
     for diskless clients, ic:189  
     requirement for network  
         installation, ic:108  
 OS services  
     adding to network server, ic:191  
 oiname rule keyword, ic:167  
 ot audit class, aa:116  
 ot audit flag, aa:98  
 ouid field, dg:295  
 output files  
     begin scripts log, ic:174  
     finish scripts log, ic:176

overlap value for *filesys*, ic:153

## P

*package* profile keyword  
     description and values, ic:155  
     examples, ic:148  
 packages from software groups  
     adding, ic:155  
     deleting, ic:155  
 packages, *See* software packages  
 packets  
     IP options, ap:271  
     IP options field, ap:271  
     location of security attributes, dg:243  
     outgoing  
         MAC rules, ap:285  
     security attributes, ap:270 to ap:273,  
         dg:244  
     standard Solaris, ao:87  
     Trusted Solaris, ao:87  
 PAF\_DISKLESS\_BOOT value, dg:38  
 PAF\_LABEL\_VIEW  
     process flag, la:32  
 PAF\_LABEL\_VIEW value, dg:39  
 PAF\_LABEL\_XLATE value, dg:39  
 PAF\_NO\_TOKMAP value, dg:38  
 PAF\_PRINT\_SYSTEM value, dg:38  
 PAF\_PRIV\_DEBUG value, dg:38  
 PAF\_SELAGENT value, dg:38  
 PAF\_SELAGENT flag, dg:292  
 PAF\_TRUSTED\_PATH value, dg:38  
 PAM  
     customizable by administrators, tg:4  
 partitioning  
     examples, ic:147 to ic:149  
     excluding disks, ic:151  
     fdisk partitions, ic:149  
     profile keyword, ic:156  
*partitioning* profile keyword, ic:156  
 passwd audit record, aa:322  
 PASSWD variable, ic:179

---

passwords

- account status, ao:73
- aging, ao:72
- assigning, ap:128, ap:134
- changing, ug:84 to ug:89, ao:72, tg:16
- entry procedure, ug:23 to ug:24
- expiration, ug:84
- initial, ao:70
- introduction, ug:3
- manual creation, ao:70
- modifying, ic:37
- NIS+ credentials, ao:73
- overview, ao:68 to ao:73
- role, ap:5
- root, ic:178 to ic:180
- root password creation, ic:61
- root password use, ic:73
- rules for manual creation, ap:132
- security precautions, ap:37 to ap:38
- storage, ap:39
- system-generated, ao:70
- updating role passwords, ic:87

path policy flag, aa:25

path token

- described, aa:165
- praudit display, aa:166

pathconf audit record, aa:236

pathnames

- adorned names, dg:172
- translation, dg:172

paths

- check script, ic:170
- install server setup, ic:123
- Trusted Solaris server setup, ic:123

patrr command

- overview, ao:139

pbind audit record, aa:322

pc audit flag, aa:98

PCFS

- mounting in Trusted Solaris, ap:385

pclear command

- overview, ao:140

permission bits

- changing, ug:106
- defined, ug:102
- described, ap:370
- introduction, ug:4

permissions

- begin scripts, ic:174
- described, ap:361
- finish scripts, ic:176
- JumpStart directory, ic:136, ic:139
- on devices, ap:485
- overriding, ao:29

permitted privileges

- See also* privilege sets
- checking, dg:74
- code example, dg:75
- defined, dg:56

pfinstall command, ic:180 to ic:183

pfsh audit record, aa:323

pfsh(1MTSOL) profile shell

- use in administration, ap:15

pfsh(ITSOL)

- determining privilege
  - origination, dg:55
- inheriting privileges, dg:55

pfsh, *See* profile shell

pid field, dg:295

pipe audit record, aa:237

pipes, access checks, dg:224, dg:225

pkginstall audit record, aa:323

pkgrm audit record, aa:324

plabel command

- overview, ao:140

placeholder files

- label\_encodings file, la:1, la:58, la:64

platform groups, ic:233 to ic:234

platforms

- diskless client, ic:150
- group determination, ic:233
- matching system attributes and profiles, ic:157, ic:158, ic:161
- name determination, ic:112, ic:233
- rule keywords, ic:165
- supported, ic:233

---

system model names, ic:166  
 table of names and groups by  
     system, ic:233 to ic:234  
 plus (+) audit flag prefix, aa:10  
 pm audit flag, aa:98  
 policy  
     configurable, tg:4  
 policy, *See* security policy  
 polyinstantiation  
     described, dg:287  
     files and directories, dg:169  
     network connections, dg:229  
 Populate NIS+ Tables action  
     described, ap:13  
 port bindings  
     network privileges, ao:29  
 porting applications and data, tg:38  
 porting software, ap:522  
 ports  
     *See also* multilevel ports  
     behavior, tg:23  
     multilevel, tg:22  
     multilevel and single-level, tg:72  
     single-level, dg:228, tg:22  
 postsigterm string and audit\_warn  
     script, aa:20  
 pound sign (#)  
     in profiles, ic:147  
     in rules, ic:163  
 ppriv command  
     overview, ao:141  
 pprivtest command  
     overview, ao:141  
 praudit command  
     audit trail, dg:191  
     changing field separator, aa:83  
     changing token separator, aa:84  
     human-readable format, aa:71  
     output formats, aa:78 to aa:84  
     overview, ao:117  
     piping auditreduce output  
         to, aa:79  
     using, aa:78 to aa:84  
 preadl audit record, aa:237  
 prefix, cm:25, cm:26 to cm:28, cm:37,  
     cm:38, cm:39, cm:43, cm:65,  
     cm:92, cm:93, cm:99, cm:104,  
     cm:108, cm:118, cm:119, cm:121,  
     cm:125, cm:126, cm:130, cm:131,  
     cm:134, cm:137, cm:138, cm:139  
 prefix=, cm:25, cm:28, cm:93, cm:94,  
     cm:99, cm:104, cm:108, cm:119,  
     cm:130, cm:133, cm:135 to cm:141  
 prefixes in audit flags, aa:10  
 preselection mask  
     C library functions, aa:341  
     described, aa:16  
     reducing storage costs, aa:21 to aa:22  
 preserve value for *filesys*, ic:153  
 preserving data  
     existing data during  
         installation, ic:153  
 primary audit directory, aa:12  
 principle of least privilege, ap:524  
 print format field values (arbitrary  
     token), aa:152  
 print server applications, dg:149  
 printer banner, cm:4, cm:13 to cm:20,  
     cm:36, cm:44 to cm:61, cm:82,  
     cm:84, cm:103, cm:104, cm:114,  
     cm:118, cm:138, cm:140 to cm:143  
 printer banner page, label  
     translation, dg:149  
 PRINTER BANNERS section  
     label\_encodings example, la:170  
 Printer Manager  
     launching, ap:467  
 printer output  
     changing printed labels, la:47  
     labels, la:24  
 Printer tool  
     differences in Trusted Solaris, ug:77  
 PRINTER variable  
     printing without labels, ap:481  
 printers  
     administering, tg:33

---

configuring, ic:197, la:106  
 label ranges  
     setting, ap:487  
 labeling output, tg:33  
 using unlabeled print server, tg:33  
**printing**  
     authorizations, ap:466  
     banner text, la:92  
     configuring labels and text, ap:457,  
         la:85  
     managing, ap:447 to ap:482  
     planning example, la:151  
     protecting printer output, la:88  
     setting minimum protect as  
         classification, la:88  
     specifying SLs instead of ILs on body  
         pages, ap:477  
     suppressing page labels, ap:464  
     without banners and trailers, ap:478  
     without banners  
         authorization, ap:466  
     without page labels, ap:480  
     without page labels,  
         procedure, ap:480  
**printing definitions**  
     label encodings file, ao:6  
**printing flag, dg:38**  
**printing with authorization audit**  
     record, aa:319  
**printmgr audit record, aa:324**  
**priocntlsys audit record, aa:238**  
**priv token**  
     described, aa:166  
     praudit display, aa:166  
**PRIV\_ALLOWED value, dg:60**  
**PRIV\_ASSERT macro**  
     and str\_to\_priv(3TSOL), dg:70  
     described, dg:61  
**PRIV\_CLEAR macro, dg:61**  
**PRIV\_EFFECTIVE value, dg:60**  
**PRIV\_EMPTY macro, dg:61**  
**PRIV\_EQUAL macro, dg:61**  
**PRIV\_FILL macro, dg:61**  
**PRIV\_FORCED value, dg:60**  
**priv\_ftype\_t type, dg:60**  
**PRIV\_INHERITABLE value, dg:60**  
**PRIV\_INTERSECT macro, dg:61**  
**PRIV\_ISASSERT macro**  
     code example, dg:74, dg:76  
     described, dg:61  
**PRIV\_ISEMPY macro, dg:61**  
**PRIV\_ISFULL macro, dg:61**  
**PRIV\_ISSUBSET macro**  
     described, dg:61  
     purpose, dg:75  
**priv\_names(4TSOL) file, ap:52**  
**priv\_names.h file**  
     See priv\_names(4TSOL) man  
         page, ap:50  
**PRIV\_OFF value, dg:60**  
**PRIV\_ON value, dg:60**  
**priv\_op\_t type, dg:60**  
**PRIV\_PERMITTED value, dg:60**  
**PRIV\_privilege name, See privileges and**  
     priv\_desc(4TSOL)  
**priv\_ptype\_t type, dg:60**  
**PRIV\_SAVED value, dg:60**  
**PRIV\_SET value, dg:60**  
**priv\_set\_t structure, dg:60**  
**priv\_set\_to\_str(3TSOL)**  
     code example, dg:69  
     declaration, dg:64  
**priv\_t type, dg:60**  
**PRIV\_TEST macro, dg:61**  
**priv\_to\_str(3TSOL)**  
     code example, dg:65  
     declaration, dg:64  
**PRIV\_UNION macro, dg:61**  
**PRIV\_XOR macro, dg:61**  
**privenable audit record, aa:238**  
**privilege**  
     audit records for use of, aa:277  
     when executing commands, aa:42  
**privilege APIs**  
     declarations, dg:62 to dg:64, dg:347

---

- macros, dg:61
- privilege bracketing
  - benefits, dg:71
  - code example, dg:73
  - procedure, dg:72
- privilege data types
  - file sets, dg:60
  - operations on sets, dg:60
  - privilege ID, dg:60
  - process sets, dg:60
  - structure, dg:60
- privilege debugging, tg:41
  - enabling, dg:29, dg:336
  - flag, dg:38
  - setting tsol\_privs\_debug, ap:418
- privilege macros
  - API declarations, dg:347
  - asserting privilege example, dg:69
  - described, dg:61
  - initializing set example, dg:67
- privilege sets
  - See also* allowed privileges
  - See also* code examples
  - See also* effective privileges
  - See also* forced privileges
  - See also* inheritable privileges
  - See also* permitted privileges
  - See also* privileges
  - See also* saved privileges
  - after `exec(2TSOL)`, dg:79
  - after `fork(2TSOL)`, dg:77
  - algorithms, dg:54
  - allowed privileges, ao:28
  - API declarations, dg:347
  - defined, ao:28
  - file, dg:53
  - forced privileges, ao:28
  - inheritable privileges, ao:28
  - on network messages, dg:247
  - privileged tasks, dg:57
  - privileges needed, dg:57
  - process, ap:529, dg:54
  - turning off allowed sey, dg:70
- privilege token
  - described, aa:166
- praudit display, aa:167
- privilege use audit record, aa:277
- privileged commands
  - run by `cron(1MTSOL)`
    - command, ap:92
- privileged process defined, dg:56
- privileged programs, ap:541
- privileged tasks
  - auditing, dg:187
  - clearance, dg:152
  - IPC, dg:223
  - Label builder, dg:321
  - labels, dg:95
  - MLDs, dg:173
  - multilevel port connections, dg:228
  - privilege sets, dg:57
  - RPC, dg:278
  - SLDs, dg:173
  - System V IPC, dg:232
  - TSIX, dg:245
  - X Window System, dg:293
- privileges, ao:134
  - See also* authorizations
  - See also* code examples
  - See also* `priv_desc(4TSOL)` man page
  - See also* privilege sets
  - See also* security policy
  - See also* translation
  - adding, ap:50
  - administrative applications, dg:15
  - algorithms, tg:57
  - allowed, ap:538, ao:28, ao:30
  - alternatives to using, ap:524
  - API declarations, dg:347
  - applications, privileged, dg:57
  - assigning to actions, ao:122
  - assigning to commands, ao:122
  - assigning to files, ao:128
  - and authorizations, dg:40
  - availability, ao:29, ao:33
  - bracketing, ap:524
  - categories, ao:29
    - file system, dg:53
    - file system privileges, ao:29

---

IPC, dg:53  
 network privileges, ao:29  
 process, dg:53  
 process privileges, ao:30  
 system, dg:53  
 system privileges, ao:30  
 System V IPC, dg:53  
 System V IPC privileges, ao:29  
 window privileges, ao:30  
 X Window System, dg:53  
 changing on files and  
     directories, ap:396  
 compatibility with Trusted Solaris  
     1.x, tg:37  
 DAC override, ap:523  
 debugging, tg:41, tg:58  
 defined, ap:522, ug:12, dg:51, ao:2  
 delimiters, dg:69  
 described, ap:370, tg:56  
 description file, tg:100  
 description text API, dg:64  
 development environment, dg:40  
 effective set  
     defined, ap:529  
 errors, dg:15  
 example, ap:525  
 in execution profiles, ap:216, ao:21  
 file access, ao:36  
 file\_dac\_read  
     as an override privilege, ap:523  
 file\_dac\_write  
     as an override privilege, ap:523  
 file\_mac\_read  
     as an override privilege, ap:523  
 file\_mac\_write  
     as an override privilege, ap:523  
 finding process' current set, ic:27  
 forced, ao:28, ao:30  
     assigning, ap:537, ap:563  
 guidelines, dg:58  
 inheritable, ap:534, ap:538, ao:28,  
     ao:31  
 inheritable set  
     defined, ap:529  
 inheritance, ap:526  
 on interpreted files, dg:54  
 MAC override, ap:523  
 macros, tg:58  
 making available to  
     commands, ap:537  
 manifest constants, tg:100 to tg:104  
 network, tg:104  
 network interfaces, ao:96  
 new manifest constants, tg:103  
 non-obvious reasons for  
     requiring, ap:543  
 override, ap:114  
     defined, ap:523  
 overview, ao:27 to ao:33  
 permitted set  
     defined, ap:529  
 principle of least privilege, ap:524  
 procedure for adding, ap:53  
 remote host templates, ao:93  
 removed manifest constants, tg:102  
 required, ap:113, ap:523  
 retained manifest constants, tg:101  
 saved set  
     defined, ap:529  
 saving and restoring an edited  
     executable, ap:571  
 scripts, dg:337  
 separators, dg:69  
 software administration, ao:19  
 contrast to superuser, dg:6  
 system, tg:104  
 TCB, dg:6, dg:57  
 UIDs, changed, dg:56  
 upgraded names  
     hide, dg:29  
 used by commands in the `pfsh`  
     shell, ap:527  
 user applications, dg:16  
 when to use, dg:13, dg:40  
 window, tg:104  
 when writing to executable, dg:57  
 Privileges dialog box  
     assigning privileges, ao:30  
`privs` field, dg:214  
`proc_audit_appl` privilege, dg:187  
`proc_audit_tcb` privilege, dg:46

---

proc\_mac\_owner privilege, dg:223  
 proc\_mac\_read privilege, dg:223  
 proc\_nofloat privilege, dg:96  
 proc\_set\_sl privilege, dg:245  
 proc\_setclr privilege, dg:152, dg:267  
 proc\_setid privilege, dg:58  
 proc\_setil privilege, dg:95  
 proc\_setsl privilege, dg:95  
 process audit characteristics, aa:15 to aa:16  
     audit ID, aa:16  
     audit session ID, aa:16  
     process preselection mask, aa:16, aa:21 to aa:22  
     terminal ID, aa:16  
 process clearances  
     acquiring, dg:151  
     API declarations, dg:154 to dg:157, dg:353  
     checking before file access, dg:43  
     components, dg:151  
     data types  
         clearance structure, dg:153  
         levels, dg:153  
     described, dg:151  
     dominate levels, dg:160  
     equal levels, dg:160  
     levels defined, dg:160  
     MAC checks, dg:42  
     mandatory access operations, dg:13  
     privileged tasks, dg:152  
     reentrant routines, dg:167  
     strictly dominate levels, dg:160  
     TSIX, dg:246  
     valid, dg:154  
 process dumped core audit record, aa:239  
 process preselection mask  
     application auditing, dg:190  
     changing, dg:200  
     described, aa:16  
     reducing storage costs, aa:21 to aa:22  
     return token, dg:195  
 process privilege sets, ap:529  
 process token  
     described, aa:167  
     praudit display, aa:168  
 process tracing, access checks, dg:226  
 processes  
     *See also* code examples  
     *See also* security attribute flags  
     *See also* security attributes  
     changing SLs, guidelines, dg:98  
     CMW label, inheriting values, dg:93  
     described, ap:371  
     effective privilege set, dg:56  
     inheritable privilege set, dg:55  
     label privileges, dg:95  
     objects, dg:3  
     permitted privilege set, dg:56  
     privilege sets, dg:54  
     privileged tasks, dg:223  
     privileged, defined, dg:56  
     privileges, ao:30  
     privileges, defined, dg:53  
     relationship to programs, ap:529  
     saved privilege set, dg:55  
     security attributes, ao:39  
 processing time costs, aa:20  
 processors  
     rule keywords, ic:163  
 PROCFS  
     mounting in Trusted Solaris, ap:386  
 profact\_t structure, dg:214  
 profcmd\_t structure, dg:214  
 profent\_t structure, dg:213  
 profile database, *See* databases  
 Profile dialog box  
     User Manager, ap:141, ap:142  
 profile keywords, ic:150 to ic:156  
     adding to profiles, ic:146  
     case sensitivity, ic:147  
     client\_arch, ic:150  
     client\_root, ic:150  
     client\_swap, ic:150  
     cluster  
         description and values, ic:151

---

- examples, ic:147
- dontuse*
  - description and values, ic:151
  - usedisk* and, ic:156
- fdisk*
  - example, ic:149
- fileys*
  - examples, ic:147 to ic:149
  - local file systems, ic:152 to ic:153
- install\_type*
  - description and values, ic:153
  - examples, ic:147
  - requirement, ic:145, ic:148
- locale*
  - description and values, ic:154
- num\_clients*, ic:154
- package*
  - description and values, ic:155
  - examples, ic:148
- partitioning*
  - description and values, ic:156
  - designating disks, ic:156
  - examples, ic:147 to ic:149
  - excluding disks, ic:151
- system\_type*
  - description and values, ic:156
  - examples, ic:147 to ic:149
- usedisk*
  - description and values, ic:156
  - dontuse* and, ic:151
- profile keywords to profiles
  - adding, ic:146
- Profile Manager
  - assigning actions, ap:243
  - assigning authorizations, ap:241
  - assigning commands, ap:238
  - assigning inheritable
    - privileges, ao:28, ao:31
  - filtering profiles, ap:220
  - location and use, tg:16
  - overview, ao:120 to ao:123
  - procedures for using, ap:245 to
    - ap:249
  - setting label ranges, ap:236
  - specifying privileges for commands
    - and actions, ap:538
  - updating custom profiles, ic:47 to ic:49
  - using, ap:218 to ap:255
- profile shell
  - administrative role login shell, tg:4
  - assigning, ao:67
  - audit record, aa:323
  - defined, ug:13, ao:25
  - effect on commands, ap:526
  - managing inherited
    - privileges, ap:527
  - name, tg:17
  - opening, ic:26, aa:43
  - startup algorithm, ap:79
  - viewing privilege information, ic:27
  - viewing process information, ic:27
- profile shell, *See* *pfsh*(ITSOL)
- profiles
  - comments in, ic:147
  - creating, ic:132, ic:145 to ic:147
  - creating derived, ic:174 to ic:175
  - derived profiles, ic:174 to ic:175
  - described, ic:132, ic:145
  - examples
    - eng\_profile*, ic:241
    - marketing\_profile*, ic:242
    - short*, ic:147
  - matching systems to, ic:157, ic:158,
    - ic:161
  - naming, ic:146
  - requirements, ic:145, ic:146
  - rule field, ic:161
  - See* execution profiles
  - testing, ic:180 to ic:182
  - verifying, ic:48
- profiles* field, dg:212
- profmgr* audit records, aa:325 to aa:326
- profstr\_t* structure, dg:213
- programming interfaces
  - access control lists, tg:62
  - auditing, tg:65
  - authorizations, tg:59
  - changes from Trusted Solaris
    - 1.x, tg:52 to tg:73

---

clearances, tg:53  
file system security attributes, tg:61  
interprocess communications, tg:69  
kernel functions, tg:78  
label builder, tg:56  
labels, tg:53  
library routines  
    removed, tg:95 to tg:97  
    Solaris, tg:91 to tg:95  
    Trusted Solaris, tg:84 to tg:91  
macros, privileges, tg:58  
privileges, tg:57  
process security attributes, tg:59  
system calls  
    removed, tg:84  
    Solaris, tg:79 to tg:84  
    Trusted Solaris, tg:76 to tg:78  
System V IPC, tg:68  
trusted streams, tg:72  
TSIX, tg:71  
user databases, tg:63  
X Window System, tg:67  
programming interfaces, *See* APIs  
programs  
    commercial  
        assigning privileges to, ap:537  
    new, trusted  
        assigning privileges to, ap:537  
    relationship to processes, ap:529  
    trusted  
        defined, ap:541  
    trustworthy  
        defined, ap:541  
properties  
    described, dg:289, dg:290  
    privileges, dg:293  
property.atoms file, ap:445  
protect as classification  
    overview, la:87  
protect\_as field, dg:102  
protect\_as\_len field, dg:101, dg:102  
prtconf command, ic:42, ic:166  
prvtoc command  
    disk configuration file creation, ic:184  
ps audit class, aa:117  
ps audit flag, aa:99  
pseudo-events  
    audit records, aa:277  
pseudo-terminal devices, *See* PTYs  
psradm audit record, aa:326  
PTYs  
    (pseudo-terminal devices)  
    access checks, dg:225  
public.atoms file, ap:445  
putmsg audit record, aa:239  
    socket connect, aa:240  
putpmsg audit record, aa:240  
pwritel audit record, aa:276

**Q**

Query Window Label menu item  
    described, ug:94

**R**

randomword functions  
    in PAM, tg:4  
rc scripts  
    shell use, ap:527  
rc2.ddirectory  
    S05RMTMPFILES script, ap:7  
rcp command  
    required privilege, ap:543  
rdate command  
    Trusted Solaris modifications, ao:107,  
        ao:150  
read access  
    IL conjoin, dg:92  
    overview, ug:7  
    security policy, dg:14  
read audit record, aa:241  
read down, dg:14  
read equal, dg:14  
readl audit record, aa:241  
readlink audit record, aa:241  
readvl audit record, aa:241

---

real UID  
   root  
     required for applications, ap:544  
     requirement for  
       installation, ap:544  
 reboot  
   effecting changes to device\_  
     policy(4TSOL), ap:485  
   re-enabling logins, ap:6  
   workstation during  
     configuration, ic:52, ic:87  
 reboot audit record, aa:327  
 reentrant routines  
   binary to hex declarations, dg:111  
   binary to hex translation, dg:148,  
     dg:167  
 relationships  
   between ILs, dg:127  
   between levels, dg:125, dg:160  
   between markings, dg:129  
 release of Trusted Solaris software  
   *installed* rule keyword, ic:164  
   *osname* rule keyword, ic:167  
 releasing an application, dg:338  
 rem\_drv audit record, aa:329  
 rem\_drv command  
   Trusted Solaris modifications, ao:147  
 remote file systems  
   accessing, ic:197  
 remote host templates  
   creating new template, ic:79  
   defined, ao:93  
 remote hosts  
   tnrhdb(4TSOL), ao:90  
 remote procedure call, *See* RPC  
 remove\_allocatable(1MITSOL)  
   command  
   described, ap:502  
 removef audit record, aa:327  
 rename audit record, aa:242  
 Rename menu item  
   described, ug:81  
 requirements  
   labeling printer output, la:88  
   network installation  
     servers, ic:108 to ic:109  
   profiles, ic:145, ic:146  
 reset command, ic:112  
 reset\_il\_on\_exec flag, dg:94  
 resolv.conf(4) file  
   action for editing, ap:13  
 resource file, dg:309  
 ResourceType structure, dg:295  
 restoration  
   audit files, aa:86  
 return token  
   praudit display, aa:169  
 Revised Internet Protocol Security Option,  
   *See* RIPS0  
 RIPS0  
   (Revised Internet Protocol Security  
     Option)  
   host type, ao:89  
     described, ap:316  
   remote host templates, ao:93  
   use in packets, ap:272  
 ripso host type, tg:22  
 rmdir audit record, aa:242  
 roles  
   *See also* administrative roles  
   administrative, ap:107 to ap:108  
     assuming a role, la:37  
   administrative workspaces, la:38  
   assigning, ao:80 to ao:81  
   assuming, ap:7, ug:83  
   combining administrative  
     roles, ap:112  
   contrasted with user accounts, ap:106  
   creating, ap:113 to ap:117  
     override privileges, ap:114  
     required privileges, ap:113  
   creating accounts, ao:67  
   customizing, ap:254  
   defined, ug:12  
   managing, ap:105 to ap:117  
   non-administrative, ap:106 to ap:107

---

- overview, ao:25
- password, ap:5
- procedure for creating, ap:116
- root, ap:107
- security administrator
  - account management
    - responsibilities, ap:73
  - security administrator contrasted with system administrator, ap:109
  - system administrator
    - account management
      - responsibilities, ap:73
    - updating profiles, ic47 to ic49
    - verifying profile contents, ic48
- Roles dialog box
  - User Manager, ap:143
- roles field, dg:212
- root
  - defined, ug:14
  - role defined, ao:3
- root (/) file systems
  - profile example, ic:148
  - value set by installation program, ic:168 to ic:169
- root environment (customizing), ic:178
- root menu
  - modifying, ap:425 to ap:433
- root passwords, ic:178 to ic:180
  - created, ic:61
  - for diskless clients, ic:196
  - used, ic:73
- root role
  - assuming, ic25
  - compared with privileges, ap:523
  - saving and restoring NIS+ tables, ap:411
  - updating profiles, ic47 to ic49
  - using to install applications, ap:544
- root UID
  - required for applications, ap:544
  - requirement for installation, ap:544
- rootdisk*
  - defined, ic:168
  - slice value for *filesystems*, ic:152
  - value set by installation program, ic:168 to ic:169
- route command
  - Trusted Solaris modifications, ao:107
- route(1MTSOL)
  - example, ao:103
- route(1MTSOL) command
  - See also* defaultrouter file
- routers, ap:276
- routing
  - assigning default, ap:351, ap:352
  - concepts, ap:274 to ap:284
  - dynamic, ap:282, tg:3
  - example, ao:103
  - loading data at boot time, ao:99
  - overview, ao:99 to ao:105
  - procedure for setup, ap:353
  - setting up, ap:294 to ap:300, ap:353 to ap:358
  - static, ap:282
  - tables, ao:100
    - defined, ap:276
  - through non-Trusted Solaris clusters, ao:105
- routing commands
  - examples, ao:103
- RPC
  - (remote procedure call)
  - See also* code examples
  - API man pages, dg:281
  - client program, dg:282 to dg:283
  - described, dg:277
  - example application, dg:281 to dg:286
  - mappings, dg:278
  - multilevel ports, dg:278
  - privileged tasks, dg:278
  - remote procedure, dg:285
  - running the application, dg:286
  - security attributes, dg:279
  - server program, dg:284
- RPC (remote procedure calls), tg:72

---

RPC failed: error 5: RPC Timed out message, ic:144, ic:266  
 RPC Timed out message, ic:144, ic:266  
 rpc.rexd audit record, aa:328  
 rsh access audit record, aa:329  
 rule keywords, ic:163 to ic:167
 

- any*
  - description and values, ic:163
  - rootdisk* matching, ic:168
- arch*, ic:163
- disksize*
  - description and values, ic:164
  - rootdisk* matching, ic:168
- domainname*, ic:163
- hostaddress*, ic:164
- hostname*, ic:162, ic:164
- installed*
  - description and values, ic:164
  - rootdisk* matching, ic:168
- karch*, ic:165
- memsize*, ic:162, ic:165
- model*, ic:162, ic:166
- network*, ic:162, ic:167
- osname*, ic:167
- totaldisk*, ic:167
- validation, ic:169

rule\_keyword rule field, ic:160

rule\_value rule field, ic:160, ic:163

rules
 

- derived profiles, ic:174 to ic:175
- displaying and entering CMW labels, la:20
- examples, ic:161
- field descriptions, ic:160 to ic:161
- matching order, ic:158, ic:161
- multiple line rules, ic:163
- rootdisk* matching rules, ic:168 to ic:169
- syntax, ic:159
- testing validity, ic:170

rules file
 

- adding rules, ic:159
- comments, ic:163
- creating, ic:132, ic:157 to ic:161
- described, ic:132, ic:157
- example, ic:158
- multiple line rules, ic:163
- naming, ic:159, ic:162
- syntax, ic:159
- testing rules, ic:170
- validating using *check*, ic:132, ic:169 to ic:170
- derived profiles and, ic:175

rules files
 

- adding rules, ic:159
- custom JumpStart example, ic:242 to ic:243
- testing, ic:243
- testing rules, ic:170
- using *check*, ic:132, ic:169 to ic:170
- validating, ic:243

rules.ok file
 

- comments and, ic:163
- creating, ic:132, ic:157, ic:163, ic:169
- described, ic:163
- matching order for rules, ic:158, ic:161

run control scripts
 

- modifying, ap:553
- shell use, ap:527

runpd command, tg:41, tg:58
 

- dependency on tsol\_priv\_debug setting, ap:418
- overview, ao:141
- using, dg:336

**S**

SAMP  
 (Security Attribute Modulation Protocol)

SAMP (Security Attribute Modulation Protocol)  
 Trusted Solaris data packets, ao:88

SATMP  
 (Security Attribute Token Mapping Protocol)  
 tokmapd command, ao:110

---

saved privileges  
     *See also* privilege sets  
     change UID, GUID, or SGUID, dg:56  
     checking, dg:76  
     defined, dg:55  
     purpose, dg:55  
 sbclearaos(3TSOL)  
     code example, dg:165  
     declaration, dg:156  
 sbcltos(3TSOL), declaration, dg:109  
 sbiltos(3TSOL), declaration, dg:110  
 /sbin/rcn scripts  
     Trusted Solaris modifications, ap:555  
 /sbin/sysh shell  
     using during boot, ap:555  
 sbsltos(3TSOL)  
     code example, dg:145  
     declaration, dg:110  
 screen locking, ug:32 to ug:33  
 screens  
     locking, ic:52  
 scripts  
     adding finish, ic:177  
     begin scripts, ic:173 to ic:175, ic:188  
     Bourne shell scripts in rule  
         fields, ic:161  
     creating finish, ic:176  
     finish scripts, ic:176 to ic:180, ic:188  
     network installation  
         commands, ic:112  
         network installation files, ic:113  
     privileged, dg:337  
 SCSI interface, requirement, ic:7  
 sec\_response packets  
     described, ap:279  
 secadmin role, *See* security administrator  
 secconf system call  
     code example, dg:29  
     declaration, dg:27  
 secondary audit directory, aa:12  
 security  
     auditing tasks for  
         administrators, aa:38  
         common violations, ic:203  
         computer publications, ic:206  
         computer recommendations, ic:201  
         personnel recommendations, ic:203  
         physical recommendations, ic:202  
         root password, ic:178 to ic:180  
         setting up, ic:198  
         site security policy, ic:200  
         U.S. Government publications, ic:205  
         UNIX publications, ic:205  
 security administrator  
     background on labels, la:1  
     defined, ug:14, ao:3  
     label administration  
         responsibilities, la:38  
 security administrator role  
     administering use of devices, ap:489  
 security administrators  
     accessing the Printer  
         Manager, ap:467  
     account management  
         responsibilities, ap:73  
     contrasted with system  
         administrators, ap:109  
     described, ap:371  
     enable logins authorization  
         requirement, ap:6  
     modifying window configuration  
         files, ap:424  
     system integrity  
         assessing after reboots, ap:6  
 security attribute flags  
     *See also* code examples, file systems  
     *See also* code examples, processes  
     API declarations, dg:346  
     file systems  
         API declarations, dg:27  
         contrast with Solaris, dg:11  
         manifest constants, dg:33, dg:35  
     processes  
         API declarations, dg:27  
         contrast with Solaris, dg:11  
         getting and setting, dg:37  
         manifest constants, dg:38  
         when to use, dg:26

---

Security Attribute Modulation Protocol,  
*See* SAMP

Security Attribute Token Mapping  
 Protocol, *See* SATMP

security attributes  
*See also* code examples, file systems  
 access checks, dg:223  
 access to privileges, dg:57  
 accessing labels, dg:95  
 API declarations, dg:346  
 in data packets, ao:88  
 described, ap:371  
 file systems, ap:378 to ap:383, tg:61  
   API declarations, dg:27  
   contrast with Solaris, dg:11  
   described, dg:31  
   manifest constants, dg:33  
   vfstab\_  
     adjunct(4TSOL), dg:31  
   when to use, dg:26  
 files, ao:38  
 filesystem auditing, aa:342  
 MLDs, dg:180  
 network interfaces, tg:71  
 overview, ao:36 to ao:39  
 privileges, dg:223  
 processes, dg:11, ao:39, tg:59  
 role in transactions, ao:40 to ao:46  
 RPC, dg:279  
 on software packages, dg:340  
 TSIX  
   changing, dg:245  
   changing procedure, dg:254  
   contrast with Solaris, dg:12  
   location on packet, dg:243  
   sending and receiving, dg:244  
 users, ao:38  
 X Window System  
   contrast with Solaris, dg:12  
   described, dg:289  
 X Window System interfaces, tg:67

security domain  
 defined, ao:86

security domains  
 multiple described, ap:268

single described, ap:262

security features  
 identification and authentication  
   for roles, ap:5  
 identification and authentication for  
   roles, ap:5

security information  
 finding, ic:198

security mechanisms  
 extendable by security  
   administrator, ap:45

security policy  
*See also* authorizations  
*See also* clearances  
*See also* DAC  
*See also* MAC  
*See also* privileges  
*See also* SLs  
 accessing MLDs, dg:170  
 accessing SLDs, dg:170  
 administrative applications, dg:15  
 allowing a wildcard in special boot  
   files, ap:327  
 auditing, dg:187  
 CDE actions, dg:339  
 clearances, dg:152  
 command line execution, dg:59  
 communication endpoints, dg:227  
 covert channels, dg:59  
 defined, ug:2  
 discretionary access  
   operations, dg:13  
 file system examples, dg:19  
 file systems, dg:16  
 file systems access, dg:17  
 file systems privileges, dg:18  
 IPC, dg:16, dg:223  
 label guidelines, dg:96  
 labels, dg:95  
 on man pages, dg:331  
 mandatory access operations, dg:13  
 mapped memory, dg:226  
 MLD access, dg:181  
 multilevel ports, dg:228  
 overriding, ao:29

---

pipes, dg:224, dg:225  
 planning example, la:151  
 principle of least privilege, ap:524  
 privilege bracketing, dg:58  
 privilege guidelines, dg:58  
 privilege sets, dg:57  
 privileges  
     when to use, dg:42  
 privileges, when to use, dg:13  
 process tracing, dg:226  
 PTYs, dg:225  
 read access, dg:14  
 reading man pages, dg:15  
 setting for devices, ap:363  
 setting minimum protect on print  
     jobs, la:90  
 signals, dg:226  
 site-specific, la:48  
 SLD access, dg:181  
 sockets, dg:229  
 System V IPC, dg:227, dg:232  
 TLI, dg:229  
 training users, ap:36 to ap:37  
 translating labels, dg:95, dg:152  
 user applications, dg:16  
 write access, dg:14  
 X Window System, dg:290  
 sel\_config file  
     configuring selection transfer  
         rules, ap:434  
     sections, ap:437  
 sel\_config(4TSOL) file  
     action for editing, ap:13  
 sel\_mgr command, ap:437  
 selection agent flag, dg:38  
 Selection Manager  
     bypassing with flag, dg:292  
     Confirmation dialog box  
         example, ug:58 to ug:60  
     security policy, dg:292  
 selection manager audit  
     record, aa:330  
 selection.atoms file, ap:445  
 self-modification authorization, ap:112  
 semaphore sets  
     *See also* code examples  
     *See also* System V IPC  
     API declarations, dg:235, dg:355  
     IL floating, dg:233  
     overriding restrictions, ao:29  
 semctl audit record  
     GETALL command, aa:243  
     GETNCNT command, aa:243  
     GETPID command, aa:244  
     GETVAL command, aa:244  
     GETZCNT command, aa:245  
     IPC\_RMID command, aa:245  
     IPC\_SET command, aa:246  
     IPC\_STAT command, aa:248  
     SETALL command, aa:247  
     SETVAL command, aa:247  
 semget audit record, aa:248  
 semgetl audit record, aa:249  
 semgetl system call  
     code example, dg:239  
     declaration, dg:235  
 semop audit record, aa:250  
 semopl audit record, aa:251  
 semopl system call, declaration, dg:235  
 sendmail  
     privacy options, tg:33  
 sendmail audit record, aa:331  
 sendmail command  
     Trusted Solaris modifications, ao:150  
         to ao:153  
     using, ap:188 to ap:191  
 sendmail(1MTSOL) command  
     *See also* sendmail.cf  
 sendmail.cf file  
     action for editing, ap:13  
 sensitivity label, cm:2, cm:13 to cm:21,  
     cm:36, cm:38, cm:41 to cm:45,  
     cm:48 to cm:53, cm:58 to cm:60,  
     cm:65 to cm:70, cm:82, cm:84,  
     cm:108 to cm:114, cm:116 to  
     cm:121, cm:134 to cm:139, cm:141  
 SENSITIVITY LABELS section  
     label\_encodings example, la:166

---

sensitivity labels, *See* SLs

sensitivity of information  
     downgrading labels, la:25

separator .ps file, la:47

seq policy flag, aa:25

seq token  
     described, aa:169  
     praudit display, aa:169

serialmgr audit records, aa:332

servers  
     JumpStart directory creation, ic:139  
         to ic:141  
     name server, ic:108  
     requirements for network  
         installation, ic:108 to ic:109  
     root space, ic:150

services  
     distributed, tg:25

session clearances  
     choosing a single SL, la:13  
     defined, ug:9  
     described, ap:373  
     overview, la:7  
     restricting the upper bound below the  
         user's clearance, la:14  
     restricting to a single SL, la:14  
     setting, ug:41 to ug:42

session ID, aa:16, aa:73

session range  
     defined, ao:11

sessionid field, dg:295

sessions  
     duration of label restrictions chosen at  
         login, la:14  
     restricting to a single SL, la:14  
     setting level, ug:26 to ug:31, ug:39 to  
         ug:42

Set Daily Message action  
     described, ap:13

Set Default Routes action  
     described, ap:13

Set DNS Server action  
     described, ap:13

Set Mail Options action  
     described, ap:13

Set Mount Attributes action  
     described, ap:14

Set Mount Points action  
     described, ap:14

Set Tsol Gateways action  
     described, ap:14

set\_effective\_priv(3TSOL)  
     code example, dg:41, dg:73  
     declaration, dg:63

set\_id structure, dg:101

set\_inheritable\_priv(3TSOL)  
     code example, dg:76  
     declaration, dg:63

set\_permitted\_priv(3TSOL)  
     code example, dg:75  
     declaration, dg:63

set\_root\_pw finish script, ic:178 to  
     ic:180

setacl audit record, aa:251

setaudit audit record, aa:252

setaudit audit record, aa:252

setbltype(3TSOL)  
     code example, dg:116, dg:159  
     declaration, dg:107, dg:155

setcil(3TSOL)  
     code example, dg:121  
     declaration, dg:105

SETCL\_ALL flag, dg:100

SETCL\_IL flag, dg:100

SETCL\_SL flag, dg:100

setclearance audit record, aa:253

setclearance system call  
     code example, dg:157  
     declaration, dg:154

setcmwlabel audit record, aa:253

setcmwlabel system call  
     code example, dg:121  
     declaration, dg:103

setcmwplabel system call  
     code example, dg:119  
     declaration, dg:103

---

when to use, dg:94  
 setcsl(3TSOL)  
     code example, dg:121  
     declaration, dg:104  
 setegid audit record, aa:255  
 seteuid audit record, aa:255  
 seteuid system call  
     and privileges, dg:56  
 setfacl audit record, aa:251  
 setfattrflag audit record, aa:256  
 setfattrflag command  
     described, ap:378  
     overview, ao:131  
 setfattrflag system call  
     code example, dg:35  
     declaration, dg:27  
 setfilepriv audit record, aa:256  
 setfpriv command  
     restricting assignment of forced and  
     allowed privileges, ap:538  
 setfpriv command, ap:537  
     overview, ao:132  
 setfpriv system call  
     code example, dg:67, dg:69  
     declaration, dg:62  
 setfpriv(2TSOL)  
     scripts, dg:337  
 setfsattr command  
     described, ap:382  
     overview, ao:135  
 setgid audit record, aa:255  
 setgroups audit record, aa:257  
 setlabel command  
     overview, ao:132  
 setpatrr system call declaration, dg:27  
 setpgrp audit record, aa:258  
 setppriv system call  
     declaration, dg:62  
     privilege bracketing, dg:73  
 setprocpriv audit record, aa:258  
 setprof command  
     overview, ao:153  
 setprofent(3TSOL),  
     declaration, dg:216  
 setprofstr(3TSOL),  
     declaration, dg:216  
 setregid audit record, aa:259  
 setreuid audit record, aa:259  
 setreuid system call  
     and privileges, dg:56  
 setrlimit audit record, aa:260  
 setting\_flag field, dg:100  
 setuid audit record, aa:260  
 setuid system call  
     and privileges, dg:56  
 setuname audit record, aa:332  
 setup\_install\_server command  
     boot server setup, ic:126  
     custom JumpStart example, ic:245  
     described, ic:112  
 setuserent(3TSOL)  
     code example, dg:222  
     declaration, dg:215  
 SGIDs  
     (supplementary group IDs)  
     privilege to change, dg:58  
 shadow file, ic:179  
 share audit record, aa:333  
 share command  
     sharing JumpStart directory, ic:241  
     Trusted Solaris modifications, ao:138  
 share(1MTSOL) command, ap:403  
 Share Filesystems action  
     described, ap:14  
 share\_nfs command  
     Trusted Solaris modifications, ao:137  
 shareall(1MTSOL) command, ap:403  
 shared directories  
     exporting, ic:93  
     starting server daemon, ic44  
 shared libraries, trusted, dg:332  
 shared memory regions  
     *See also* code examples  
     *See also* System V IPC  
     API declarations, dg:236, dg:355

---

- IL floating, dg:233
  - overriding restrictions, ao:29
- sharing directories, ap:403
- shell escapes and privileges, dg:59
- shell scripts
  - summary of Trusted Solaris
    - behavior, ap:549
    - user and role requirements, ap:552
    - writing privileged, ap:565
    - writing privileged using standard shells, ap:567
- shells
  - assigning to accounts, ap:126
  - profile, tg:17
    - startup algorithm, ap:79
  - restricted, tg:17
  - sysh(1MTSOL), ap:555
- shmat audit record, aa:261
- shmctl audit record
  - IPC\_RMID command, aa:262
  - IPC\_SET command, aa:263
  - IPC\_STAT command, aa:264
- shmdt audit record, aa:264
- shmget audit record, aa:265
- shmgetl audit record, aa:266
- shmgetl system call
  - code example, dg:241
  - declaration, dg:236
- SHORT\_CLASSIFICATION flag, dg:139
- SHORT\_WORDS flag, dg:139
- Shut Down menu item
  - described, ug:94
- shutdown
  - workstation, ic:52
- SI\_CONFIG\_DIR variable, ic:177
- SI\_PROFILE environment variable, ic:175
- SI\_SYS\_STATE variable, ic:180
- signal received during auditing
  - shutdown, aa:20
- signals, access checks, dg:226
- single SL sessions, la:13
- single-label file systems, dg:123
- single-label operation
  - label\_encodings file, la:71
- single-label systems, la:13
- single-level directories, *See* SLDs
- single-level mappings, dg:278
- single-level ports
  - behavior, tg:23
  - changing client SL, dg:245
  - described, dg:228
- single-level sessions
  - defined, ug:9
- single-user mode, la:42
- site security policy, ic:3, ic:199 to ic:206
- site-specific installation programs, ic:188
- size
  - hard disk
    - root space, ic:150
    - rule keywords, ic:164, ic:167
  - local file system, ic:152
  - managing audit files, aa:18
  - memory, ic:162, ic:165, ic:181
  - reducing audit files
    - storage space requirements, aa:21
  - swap space
    - diskless client, ic:150
    - maximum size, ic:157
    - profile examples, ic:148
- skeleton directories
  - defining printers, ap:481
  - use in Trusted Solaris, ap:83
- skeleton path, ap:135
- sl field, dg:295
- slabel token
  - described, aa:169
  - praudit display, aa:170
- slabel\_len field, dg:101
- SLDs
  - (single-level directories)
  - See also* code examples
  - accessing, dg:170
  - adorned names, dg:172
  - API declarations, dg:174 to dg:177

---

creating, dg:170  
 defined, ug:10  
 described, ap:373, dg:169  
 example, ug:53 to ug:55  
 information structure, dg:174  
 privileged tasks, dg:173  
 sensitivity labels, dg:173  
 structure, dg:170  
 working with, ap:56 to ap:65  
*See also* MLDs

slices  
   *filesys* values, ic:152  
   profile examples, ic:147 to ic:149  
   rule keyword, ic:164

SL-relation, ap:438

SLs  
   (sensitivity labels)  
   *See also* CMW labels  
   *See also* code examples  
   *See also* ILs  
   *See also* labels  
   *See also* translation  
   accreditation ranges, dg:133  
   adorned pathnames, dg:172  
   API declarations, dg:350  
   assigning to actions, ao:122  
   assigning to commands, ao:122  
   authorizations for changing, la:13  
   changing, ug:115 to ug:119  
     by copying, ug:61  
     by linking, ug:61  
     by moving, ug:61  
     example, ug:61 to ug:64  
   changing on client, dg:245  
   characteristics, la:12  
   checking before file access, dg:43  
   in CMW label, dg:90  
   components, dg:91  
   Customize Trusted Solaris  
     Configuration dialog  
     box, la:40  
   defined, ug:6, ao:2  
   described, ap:372  
   determining by window query, ug:94  
   determining with File  
     Manager, ug:113  
   displaying and hiding, ap:138 to  
     ap:140  
   example, la:12, la:15  
   file systems, ao:134  
   guidelines, dg:96  
     downgrading SLs, dg:98  
     upgrading SLs, dg:98  
   hiding and restricting user to work at  
     a single SL, la:44  
   how used in access control, la:15  
   label overview, ao:4, ao:16  
   length of components, la:11, la:12,  
     la:15  
   MAC checks, dg:42  
   mandatory access, dg:13  
   minimum number to define, la:1  
   network interfaces, ao:96  
   on file systems, dg:34  
   privileges  
     changing process SL, dg:95  
     downgrading SLs, dg:95  
     upgrading SLs, dg:95  
   purpose, dg:89  
   remote host templates, ao:93  
   replying at equal SL, dg:245  
   setting session SLs, ug:28 to ug:31  
   site analysis example, la:144 to la:148  
   site implementation example, la:139  
     to la:143  
   specifying colors, la:115 to la:123  
   System V IPC, dg:234  
   TSIX, dg:246  
   user processes, dg:93  
   visibility, ao:77

Small Computer System Interface (SCSI),  
   requirement, ic:7

*sname*  
   classification keyword, la:63

*sname=*, cm:19, cm:20, cm:25 to cm:28,  
   cm:44, cm:45, cm:59, cm:85,  
   cm:89, cm:94, cm:99, cm:104,  
   cm:108, cm:120, cm:140

---

snoop command  
 Trusted Solaris modifications, ao:108

socket accept audit record, aa:206

socket connect audit record, aa:240

socket send audit record, aa:240

socket token  
 described, aa:170  
 praudit displayA, aa:171

socket-inet token  
 described, aa:171  
 praudit display, aa:172

sockets, tg:69  
 access checks, dg:223, dg:227, dg:229  
*See also* communication endpoints

soft limit  
 audit\_warn condition, aa:19  
 minfree: line described, aa:12

soft string with audit\_warn  
 script, aa:19

software  
 exporting  
 multiple SLs, ap:520  
 importing, ap:522  
 multiple SLs, ap:520  
 installing, ic:197  
 installing publicly available software  
 at ADMIN\_LOW, ap:520  
 porting  
 reasons against, ap:544  
 third-party, tg:40

software administration  
 overview, ao:19 to ao:33

software administration authorizations,  
 defined, dg:82

software groups  
 cluster names for profiles, ic:151  
 profile examples, ic:147  
 specifying packages, ic:155

software packages, tg:52  
 adding new, dg:342  
 creating, dg:339  
 editing existing, dg:342  
 MAC attributes on, dg:340  
 prototype file, dg:344

Solaris  
 achieving the same look and feel, la:1

Solstice AdminSuite  
 distributed database GUI, tg:15  
 new databases, tg:16  
 unchanged databases, tg:16

Solstice Application Manager  
*See* Application Manager

Solstice\_Apps, tg:16  
 distributed database GUI, tg:15

Solstice\_Apps folder  
 Host Manager, ic:112  
 overview, ao:50 to ao:53  
 using, ic:34 to ic:38, ap:26, ap:28

SPARC systems  
 JumpStart directory creation on  
 diskette, ic:136 to ic:138  
 platform names and groups, ic:233 to  
 ic:234

spoofing  
 defined, ug:3

spray command  
 Trusted Solaris modifications, ao:108

spreadsheet, policy for accessing, ap:362

square brackets [] rule field, ic:160

src parameter values, dg:214

ss audit class, aa:119

ss audit flag, aa:99

st\_atime field, dg:174

st\_ctime field, dg:174

st\_gid field, dg:174

st\_mode field, dg:174

st\_mtime field, dg:174

st\_nlink field, dg:174

st\_uid field, dg:174

standalone systems  
 adding, ic:120  
 custom JumpStart installation  
 example, ic:134  
 described, ic:59  
 profile examples, ic:147 to ic:149

---

Standard Time zones, ic:267 to ic:268

standard UNIX shell  
 effect on commands, ap:526

startup files  
 .cm.rc file, ap:80  
 configuring accounts, ap:77 to ap:103  
 .mailrc file, ap:80  
 .netscape file, ap:80  
 .newsrsrc file, ap:80  
 procedures for customizing, ap:100  
 to ap:103  
 rc2.d/S05RMTMPFILES, ap:7  
 read at window system startup, ap:77

stat audit record, aa:267

stat structure, dg:174

statfs audit record, aa:267

static routes  
 setting, ic:75

static routing  
 described, ap:282

statvfs audit record, aa:267

stime audit record, aa:267

stobcl(3TSOL)  
 code example, dg:145  
 declaration, dg:109

stobclear(3TSOL)  
 code example, dg:165  
 declaration, dg:156

stobil(3TSOL)  
 code example, dg:145  
 declaration, dg:110

stobsl(3TSOL)  
 code example, dg:45, dg:145  
 declaration, dg:110

storage costs, aa:21

str\_to\_auth(3TSOL)  
 code example, dg:86  
 declaration, dg:84

str\_to\_auth\_set(3TSOL)  
 code example, dg:87  
 declaration, dg:84

str\_to\_priv(3TSOL)  
 and PRIV\_ASSERT macro, dg:70  
 code example, dg:65  
 declaration, dg:64

str\_to\_priv\_set(3TSOL)  
 code example, dg:69  
 declaration, dg:64

str\_type\_type, ap:485

STREAMS, *See* trusted streams

streams, trusted, tg:72

strict dominance, la:17  
 defined, ug:7  
 described, ap:373

strictly dominate levels, dg:126, dg:160

Style Manager, la:14

Style Manager control panel  
 modified for Trusted Solaris, tg:36

su audit record, aa:334

subject  
 defined, ug:6

subject token  
 described, aa:172  
 praudit display, aa:172

subnet  
 boot server creation on, ic:126

subpanels  
 differences in Trusted Solaris, ug:75

success  
 audit flag prefix, aa:9  
 turning off audit flags for, aa:9

suffix, cm:25, cm:26 to cm:28, cm:37,  
 cm:38, cm:39, cm:65, cm:89,  
 cm:94, cm:99, cm:104, cm:108,  
 cm:118, cm:129, cm:130, cm:131,  
 cm:138, cm:139

suffix=, cm:25, cm:28, cm:89, cm:94,  
 cm:99, cm:104, cm:109, cm:119,  
 cm:129, cm:130, cm:131, cm:139,  
 cm:140

SUN\_CLR\_ID value, dg:159

SUN\_CLR\_UN value, dg:159

SUN\_CMW\_ID value, dg:115

SUN\_IL\_ID value, dg:115

SUN\_IL\_UN value, dg:115

---

SUN\_SL\_ID value, dg:115  
 SUN\_SL\_UN value, dg:115  
 sun\_tsol host type  
     defined, ao:89  
     described, ap:306  
 SUNWCall group, ic:151  
 SUNWcar package, aa:2  
 SUNWcprog group, ic:151  
 SUNWcsr package, aa:2  
 SUNWcsu package, aa:2  
 SUNWCuser group, ic:151  
 SUNWhea package, aa:2  
 SUNWman package, aa:2  
 SUNWtsolr package, aa:2  
 SUNWtsolu package, aa:2  
 superuser, *See* privileges  
 supplementary group IDs, *See* SGIDs  
 sv locale name, ic:154  
 SVCXPRT structure, dg:279  
 swap audit record, aa:334  
 swap file systems  
     diskless client swap space, ic:150  
     memory size and, ic:157  
     profile examples, ic:148  
     size determination, ic:157  
 swap value for *filesys*, ic:153  
 swapfs file system  
     modified for Trusted Solaris, tg:28  
 Swedish locale value, ic:154  
 swmtool  
     installing AnswerBook, ap:557  
 symbolic links  
     information structure, dg:174  
     MAC and IL attributes, ap:377  
     MLDs, dg:171  
 symlink audit record, aa:268  
 Sys Default, la:45  
 SYS\_MEMSIZE variable, ic:181  
 sys\_trans\_label privilege, dg:45,  
     dg:95, dg:152  
 sys\_trans\_label privilege, dg:321  
 sysh shell  
     using during boot, ap:555  
 sysh command  
     overview, ao:153 to ao:154  
 sysh shell  
     trusted processes, ap:527  
 sysinfo audit record, aa:268  
 syslog.conf(4) file, tg:41  
 system accreditation range  
     administrative labels  
         in the system accreditation  
         range, la:34  
     defined, ao:7  
     described, ap:373  
 system administration  
     in Trusted Solaris, ug:12 to ug:14  
 system administrator  
     adding a host, ap:410  
     contrasted with security  
         administrator, ap:109  
     defined, ug:14, ao:3  
 system administrators  
     account management  
         responsibilities, ap:73  
 system booted audit record, aa:269  
 system calls  
     API declarations, dg:359 to dg:361  
     audit event numbers, aa:6  
     auditing, aa:340  
     auditsvc fails, aa:20  
     removed, tg:84  
     return token, aa:168 to aa:169  
     security policy in man pages, dg:331  
     Solaris, tg:79 to tg:84  
     Trusted Solaris, tg:76 to tg:78  
 system file  
     labels-related kernel switch  
         settings, la:57  
     local tsolsys switch settings, la:41  
 System Five Interprocess Communication,  
     *See* System V IPC  
 system information  
     displaying, ic:112  
     finding, ic:198

---

system operator  
     defined, ug:14, ao:3  
 system packages, tg:52  
 system privileges, tg:104  
 system rebooted audit record, aa:271  
 system remounted audit record, aa:271  
 system security  
     privileges, ao:30  
     violations, ap:543  
 system security configuration  
     *See also* code examples  
     API declarations, dg:346  
     networks, ao:86 to ao:87  
     variables described, dg:28  
     when to check, dg:26  
 system shell  
     described, ap:527  
 system shutdown audit record, aa:272  
 System V interprocess communication, *See*  
     System V IPC  
 System V IPC, tg:68  
     (System Five Interprocess  
         Communication)  
     *See also* message queues  
     *See also* semaphore sets  
     *See also* shared memory regions  
     access checks, dg:223, dg:227  
     API declarations, dg:234 to dg:236,  
         dg:355  
     described, dg:231  
     discretionary access, dg:232  
     IL floating, dg:233  
     ipc token, aa:161 to aa:162  
     mandatory access, dg:232  
     message queue floating, dg:28  
     privileged tasks, dg:232  
     privileges, ao:29  
     privileges, defined, dg:53  
     semaphore set floating, dg:28  
     sensitivity label structure, dg:234  
     shared memory floating, dg:28  
 system(4TSOL) file, tg:18, tg:41  
 system, privileges defined, dg:53  
 SYSTEM\_ACCREDITATION\_RANGE  
     value, dg:101  
 System\_Admin  
     local database GUI, tg:15  
 System\_Admin folder  
     overview, ao:54 to ao:57  
     using, ic:29, ic:38 to ic:41  
     using administrative actions, ap:528  
*system\_type* profile keyword  
     description and values, ic:156  
     examples, ic:147 to ic:149

**T**

T6\_AUDIT\_ID value, dg:248  
 T6\_AUDIT\_INFO value, dg:248  
 T6\_CLEARANCE value, dg:248  
 T6\_GID value, dg:248  
 T6\_GROUPS value, dg:248  
 T6\_IL value, dg:248  
 T6\_PID value, dg:248  
 T6\_PRIVILEGES value, dg:248  
 T6\_PROC\_ATTR value, dg:248  
 T6\_SESSION\_IC value, dg:248  
 T6\_SL value, dg:248  
 T6\_UID value, dg:248  
 t6alloc\_blk(3NTSOL)  
     code example, dg:254  
     declaration, dg:249  
 t6allocated\_attrs(3NTSOL)  
     code example, dg:264  
     declaration, dg:249  
 t6attr\_id\_t structure, dg:247  
 t6attr\_t structure, dg:247  
 t6clear\_blk(3NTSOL)  
     code example, dg:263  
     declaration, dg:252  
 t6cmp\_blk(3NTSOL)  
     code example, dg:263  
     declaration, dg:252  
 t6copy\_blk(3NTSOL)  
     code example, dg:262  
     declaration, dg:252

---

t6dup\_blk(3NTSOL)  
    code example, dg:262  
    declaration, dg:252  
t6ext\_attr(3NTSOL),  
    declaration, dg:253  
t6free\_blk(3NTSOL)  
    code example, dg:265  
    declaration, dg:249  
t6get\_attr(3NTSOL)  
    code example, dg:258  
    declaration, dg:251  
t6get\_endpt\_default(3NTSOL)  
    code example, dg:257  
    declaration, dg:253  
t6get\_endpt\_mask(3NTSOL)  
    code example, dg:257  
    declaration, dg:253  
t6last\_attr(3NTSOL)  
    code example, dg:260  
    declaration, dg:251  
T6M\_ALL\_ATTRS value, dg:249  
T6M\_AUDIT\_ID value, dg:249  
T6M\_AUDIT\_INFO value, dg:249  
T6M\_CLEARANCE value, dg:249  
T6M\_GID value, dg:249  
T6M\_GROUPS value, dg:249  
T6M\_IL value, dg:249  
T6M\_NO\_ATTRS value, dg:249  
T6M\_PID value, dg:249  
T6M\_PRIVILEGES value, dg:249  
T6M\_SESSION\_ID value, dg:249  
T6M\_SL value, dg:249  
T6M\_UID value, dg:249  
t6mask\_t structure, dg:248  
t6new\_attr(3NTSOL)  
    code example, dg:259  
    declaration, dg:250  
t6peek\_attr(3NTSOL)  
    code example, dg:260  
    declaration, dg:251  
t6present\_attrs(3NTSOL)  
    code example, dg:264  
    declaration, dg:249  
t6recvfrom(3NTSOL)  
    code example, dg:258  
    declaration, dg:250  
t6sendto(3NTSOL)  
    code example, dg:254  
    declaration, dg:250  
t6set\_attr(3NTSOL)  
    code example, dg:254  
    declaration, dg:251  
t6set\_endpt\_default(3NTSOL)  
    code example, dg:257  
    declaration, dg:253  
t6set\_endpt\_mask(3NTSOL)  
    code example, dg:257  
    declaration, dg:253  
t6size\_attr(3NTSOL)  
    code example, dg:261  
    declaration, dg:252  
t6supported\_attrs(3NTSOL)  
    code example, dg:264  
    declaration, dg:249  
Taiwanese locale value, ic:154  
tape  
    copying files from, ic:31  
    copying files to, ic:30  
tape devices  
    accessing, ap:486  
    device\_clean scripts, ap:496  
tapes  
    physical labeling, la:24  
tar  
    saving security attributes, ap:503  
tar command, tg:38  
    allocating a media device, ap:500  
tar(1TSOL)  
    overview, ao:154  
tar(1MTSOL) command  
    ancillary files, ap:500  
task maps  
    Trusted Solaris installation and  
        configuration, ic:16 to ic:20

---

TCB  
 (trusted computing base)  
 defined, ug:2  
 network flag, dg:38  
 privileged applications, dg:57

TCP address  
 (Transmission Control Protocol  
 address)

template of sections, la:62

templates  
 assigning to hosts, ap:332, ap:335,  
 ap:342

temporary file cannot be used, aa:20

terminal emulator  
 accessing the profile shell, ap:15

terminal ID, aa:16

terminals  
 resetting after I/O interrupts, ic:112

terminating  
 signal received during auditing  
 shutdown, aa:20

terminator commands, dg:188

testfpriv command  
 overview, ao:133

testing and debugging  
 applications, dg:335

Text Editor  
 differences in Trusted Solaris, ug:75

text token  
 described, aa:172  
 praudit display, aa:173, aa:214

third-party software, tg:40

time stamps in audit files, aa:75

time zones, ic:267 to ic:268

timed out RPC error, ic:266

time-date auditreduce command  
 options, aa:81

TLI  
 (Transport Layer Interface)  
 access checks, dg:229  
 objects, dg:4  
*See also* communication endpoints  
*See also* TSIX library

/tmp directory  
 as an MLD, ap:56

tmpfile string and audit\_warn  
 script, aa:20

TMPFS  
 mounting in Trusted Solaris, ap:386  
 procedure for mounting, ap:403

tmpfs file system  
 modified for Trusted Solaris, tg:28

tnchkdb command  
 overview, ao:109

tnchkdb(1MTSOL) command  
 action for checking local tn\*  
 files, ap:13  
 action for checking NIS+ tn\*  
 tables, ap:13

tnctl command  
 overview, ao:109

tnd command  
 overview, ao:109

tnfs file system  
 modified for Trusted Solaris, tg:28

tnidb database, ao:96

tnidb(4TSOL) database, tg:23

tnidb(4TSOL) file  
 accessing, ap:303  
 action for checking local, ap:13

tnif audit record, aa:269

tninfo command  
 overview, ao:109

tnrh audit record, aa:269

tnrhdb database, ao:90

tnrhdb file  
 configuring, ic:78 to ic:81

tnrhdb(4TSOL) database, tg:51

tnrhdb(4TSOL) file  
 accessing, ap:303  
 action for checking local  
 version, ap:13  
 action for checking NIS+  
 version, ap:13  
 boot time version, ap:326  
 special boot version, ap:326

---

tnrhttp(4TSOL) file  
     action for checking NIS+  
         version, ap:13  
     action for checking local  
         version, ap:13  
 tnrhttp audit record, aa:269  
 tnrhttp database, ao:93  
 tnrhttp file  
     editing on the client, ic:101  
     modifying, ic:79 to ic:80  
 tnrhttp(4TSOL) database, tg:51  
 tnrhttp(4TSOL) file  
     accessing, ap:303  
     special boot version, ap:326  
 token commands, dg:188  
 token mapping daemon  
     defined, ao:110  
 tokmapctl command  
     overview, ao:110  
 tokmapd command  
     overview, ao:110  
 tokmapper audit record, aa:270  
 toolkits, tg:73  
 tools for packaging, tg:52  
 Tooltalk, tg:20  
*totaldisk* rule keyword, ic:167  
 trailer pages  
     computing the classification, la:88  
     labeling, la:85, la:87  
 trailer token  
     described, aa:173  
     format, aa:173  
     order in audit record, aa:70  
     praudit display, aa:173  
 translation  
     adorned pathnames, dg:172  
     authorizations  
         ID to string, dg:86  
         string to ID, dg:86  
     clearances  
         ASCII to binary, dg:165  
         binary and hexadecimal, dg:166  
         binary to ASCII, dg:164  
         binary to ASCII, clipped, dg:165  
         binary to hex, dg:167  
         forms, dg:164  
         reentrant routines, dg:167  
 CMW labels  
     ASCII to binary, dg:145  
     binary to ASCII, dg:140  
     binary to hex, dg:147  
     input form, dg:144  
     output form, dg:140  
 font list, dg:306  
 ILS  
     binary to ASCII, dg:142  
     input form, dg:144  
     output form, dg:140  
     to level, dg:130  
 labels  
     ASCII to binary  
         correction, dg:144  
     binary and ASCII rules, dg:138  
     binary and hexadecimal, dg:144,  
         dg:147  
     binary to ASCII  
         guidelines, dg:139  
     flag values, dg:139, dg:144  
     font list, dg:306  
     forms, dg:138  
     reentrant routines, dg:110  
     view, dg:139  
 privileges  
     ID to string, dg:65  
     string to ID, dg:65  
 privileges needed, dg:95, dg:152  
 privileges, binary and ASCII, dg:64  
 reentrant binary to hex, dg:148  
 SLs  
     binary to ASCII, dg:140  
     input form, dg:144  
     output form, dg:140  
 Transmission Control Protocol, *See* TCP  
 Transport layer Interface, tg:69  
 Transport Layer Interface, *See* TLI  
 Trash Can  
     differences in Trusted Solaris, ug:79

---

Trojan horse protection, dg:54

troubleshoot, aa:89 to aa:96

troubleshooting, ic:265 to ic:266

- I/O interrupt messages, ic:112
- mounts, ap:405

trusted

- Application Manager, tg:35
- drag 'n drop, tg:20
- editor, tg:17
- File Manager, tg:35
- role workspaces, tg:34
- screen stripe, tg:20
- streams, tg:72
- workspace restrictions, tg:34

trusted applications

- defined, ao:19

trusted computing base, *See* TCB

Trusted Desktop subpanel

- defined, ug:79
- Desktop Access tool, tg:36
- Device Manager, tg:36
- with Desktop Access tool, tg:4

trusted editor audit record, aa:302

trusted network

- editing local files, ic:78

trusted network daemon

- defined, ao:109

trusted networking

- databases
  - accessing
    - tnidb(4TSOL), ap:303
    - tnrhdb(4TSOL), ap:303
    - tnrhtp(4TSOL), ap:303
  - boot-time versions of
    - tnrhdb/tnrhtp, ap:326
  - creating fallback entries, ap:339
  - wildcard at boot, ap:327
  - host types, ap:265 to ap:267, ap:305 to ap:319

trusted networks

- See* networks

trusted path

- attribute flag, dg:38
- trusted path attribute, la:38
  - defined, ao:26
  - tools requiring, ap:108
- trusted path indicator
  - defined, ao:2
- Trusted Path menu, ap:5
  - assuming a role, tg:34
  - changing passwords, tg:16
  - described, ug:80 to ug:95
  - example, ug:44
  - location, tg:34
- trusted path symbol
  - described, ug:71
  - example, ug:43 to ug:44
- trusted processes
  - defined, ap:527
  - launching actions, ap:528
  - passing inheritable privileges, ap:538
- trusted programs, ap:541
  - adding, ap:545
- Trusted Security Information eXchange library
  - See* TSIX library
- Trusted Security Information eXchange, *See* TSIX
- Trusted Security Interoperability Working Group, *See* TSIG
- trusted shared libraries, dg:332
- Trusted Solaris
  - changes to printing, ap:448 to ap:474
- Trusted Solaris boot diskette
  - copying to disk, ic:137
- Trusted Solaris CD
  - copying to install server's local disk, ic:112
  - displaying mounted file systems, ic:112
  - image on local disk, ic:138, ic:140
  - mounting, ic:126, ic:138
- Trusted Solaris configuration
  - adding users, ic:88
  - copying label encodings file to client, ic:99

---

- copying `tnrhttp` file to the client, ic:101
  - evaluated configuration, ic:3
  - exporting directories, ic:43
  - logging on as a user, ic:24
  - mounting unlabeled file systems, ic:93
  - NIS+ clients, ic:97 to ic:106
  - protecting workstation, ic:28
  - setting static routes, ic:75
  - setting up home directories, ic:88, ic:104
  - task maps, ic:16 to ic:20
  - updating credentials, ic:87
  - upgrading, ic:49
  - verifying that roles work, ic:92
  - workstation without NIS+, ic:63 to ic:70
- Trusted Solaris environment
  - basic features, ug:66
  - guided tour, ug:43 to ug:64
  - overview, ug:2 to ug:14
- Trusted Solaris installation
  - `config_data` file, ic:117
  - interactive
    - networked workstations, ic:53 to ic:62
    - non-networked workstations, ic:63 to ic:70
  - log files, ic:49, ic:61
  - methods, ic:11
  - NIS+ clients, ic:97 to ic:106
  - NIS+ root master, ic:71 to ic:96
  - over networks, ic:107 to ic:128
  - preparing custom JumpStart installation, ic:129 to ic:172
  - setting default date and time, ic:119
  - task maps, ic:16 to ic:20
  - Trusted Solaris configuration settings, ic:117
  - upgrade files, ic:50
  - upgrade tasks, ic:49
  - worksheet examples, ic:247 to ic:264
  - workstation without NIS+, ic:63 to ic:70
- Trusted Solaris software groups
  - cluster names for profiles, ic:151
  - profile examples, ic:147
  - specifying packages, ic:155
  - platforms supported, ic:7
  - release or version
    - installed* rule keyword, ic:164
    - osname* rule keyword, ic:167
- trusted streams
  - API declarations, dg:359, dg:361
  - objects, dg:4
  - policy switch, dg:29
- trusted stripe
  - defined, ug:66
  - described, ug:71 to ug:72
  - example, ug:43 to ug:44
- Trusted X Window System, tg:66
- Trusted X Window System, *See* X Window System
- `trusted_edit` script
  - assigning as default editor, ap:118
- `trusted_edit` shell script
  - use in administrative actions, ap:14
- trustworthy programs, ap:541
- TSIG
  - (Trusted Security Interoperability Working Group)
- TSIX
  - (Trusted Security Information eXchange)
- TSIX (Trusted Security Information Exchange), tg:71
- TSIX host type
  - described, ap:308
- tsix host type
  - defined, ao:89
  - described, ap:308
- TSIX library
  - See also* code examples
  - See also* IPC

---

API declarations, dg:249 to dg:253, dg:356  
 attribute enumerations, dg:247  
 attribute masks, dg:248  
 attribute structure, dg:247  
 changing client SL, dg:245  
 changing security attributes, dg:245, dg:254  
 client application, dg:273 to dg:276  
 described, dg:243  
 example application, dg:265 to dg:276  
 information label floating, dg:245  
 network accreditation range, dg:244  
 privileged tasks, dg:245  
 replying at equal SL, dg:245  
 security attributes, dg:244  
 server application, dg:266 to dg:272  
*tsol\_attr* flag  
 described, ap:380  
 TSOL\_AUTH\_FILE\_DOWNGRADE  
 authorization, dg:41  
 TSOL\_DB\_SRC\_FILES flag, dg:215  
 TSOL\_DB\_SRC\_NISPLUS flag, dg:214  
 TSOL\_DB\_SRC\_SWITCH flag, dg:214  
*tsol\_enable* configurable kernel  
 switch, ap:417  
 TSOL\_ENABLE\_IL variable, dg:28, dg:29  
*tsol\_enable\_il\_floating* configurable  
 kernel switch, ap:417  
 TSOL\_ENABLE\_IL\_FLOATING  
 variable, dg:28  
 TSOL\_FLOAT\_SYSV\_MSG\_IL  
 variable, dg:28  
 TSOL\_FLOAT\_SYSV\_SEM\_IL  
 variable, dg:28  
 TSOL\_FLOAT\_SYSV\_SHM\_IL  
 variable, dg:28  
*tsol\_hide\_upgraded\_names* configurable  
 kernel switch  
 defined, ap:418  
 TSOL\_HIDE\_UPGRADED\_NAMES  
 variable, dg:29  
*tsol\_lbuild\_create*(3TSOL)  
 declaration, dg:316  
 description, dg:322  
*tsol\_lbuild\_destroy*(3TSOL)  
 declaration, dg:316  
*tsol\_lbuild\_get*(3TSOL)  
 code example, dg:318  
 declaration, dg:316  
*tsol\_lbuild\_set*(3TSOL)  
 code example, dg:318  
 declaration, dg:316  
*tsol\_privs\_debug*  
 use of, la:42  
*tsol\_privs\_debug* configurable kernel  
 switch  
 defined, ap:418  
*tsol\_privs\_debug* switch  
 described, ap:541  
*tsol\_reset\_il\_on\_exec* configurable kernel  
 switch  
 defined, ap:417  
 TSOL\_RESET\_IL\_ON\_EXEC  
 variable, dg:29  
*tsol\_separator.ps* file  
 procedures  
 specifying SLs to print instead of  
 ILs{*tsol\_*  
*separator.ps*}, ap:477  
 TSOL\_STR\_LINB variable, dg:29  
 TSOLadmin.dt file  
 adding an administrative  
 action, ap:29  
*tsolgateways*  
 setting, ic:77  
*tsolgateways*(4TSOL) file  
 action for editing, ap:14  
*tsolprof*(4TSOL)  
*See also* databases  
*tsolprof* database, tg:16, tg:64  
*tsolprof* file  
 accessing, dg:211  
*tsolsys* switch settings, la:41

---

tsoluser(4TSOL)  
     *See also* databases  
 tsoluser file  
     accessing, dg:211  
 tunnel file  
     procedure for creating, ap:350, ap:358  
     setting up tunneling, ap:328  
 tunneling  
     described, ao:105  
 tunnelling  
     passing emetrics through non-TSOL  
         hosts gateways, ap:328  
 two-person control  
     adding privileges to programs, ap:545

**U**

uadmin audit record  
     system freeze, aa:270  
     system reboot, aa:271  
     system remount, aa:271  
     system shutdown, aa:272  
     user-level command, aa:335  
 uauth audit record, aa:319, aa:335  
 uauth printing audit records, aa:319  
 UDP address  
     (User Datagram Protocol address)  
 UFS  
     mounting in Trusted Solaris, ap:386  
 ufs file system  
     modified for Trusted Solaris, tg:28  
 uid field, dg:295  
 UIDs  
     (user IDs)  
     and roles, ug:83  
     assigning, ap:124, ao:66  
     assigning to actions, ao:122  
     assigning to commands, ao:122  
     changed, dg:56  
     effective  
         alternative to privileges, ap:524  
         defaults, ap:540  
         defined, ap:522  
     effective UID of root, ap:544  
         in execution profiles, ap:214, ao:21  
         getting on window, dg:308  
         getting on workstation, dg:308  
         network interfaces, ao:96  
         privilege to change, dg:58  
         remote host templates, ao:93  
         user ID (audit ID), aa:3, aa:16, aa:73  
 umount: old version audit  
     record, aa:272  
 uname audit record, aa:336  
 uname command, ic:112, ic:233  
 unbundled Sun applications  
     adding, ap:541  
 undefined labels, described, dg:115  
 UNIX domain socket  
     used by cron(1MTSOL) and its  
         clients, ap:93  
 UNIX Domain sockets, *See* IPC  
 UNIX publications  
     general, ic:206  
     security, ic:205  
 unlabeled host type  
     creating (example), ic:79  
     defined, ao:89  
     described, ap:318  
 unlabeled host types, tg:22  
 unlabeled hosts  
     mounting MLDs, ap:377  
 unlabeled machines  
     write up policy, tg:4  
 unlink audit record, aa:273  
*unnamed* value for *filesystems*, ic:153  
 unshare audit record, aa:337  
 unshare command  
     Trusted Solaris modifications, ao:138  
 .updatehome(1MTSOL) command  
     using, ap:87  
*upgrade file sensitivity label*  
     authorization, la:13  
 upgrade installation  
     configuration tasks, ic:49  
     profile keywords, ic:153 to ic:155

---

upgrade option  
     installation, tg:12  
 upgraded names  
     defined, ap:418  
     hide, dg:29  
 upgrading labels  
     guidelines, dg:98  
     privileges needed, dg:95, dg:96  
     X Window System, dg:294  
*usedisk* profile keyword  
     description and values, ic:156  
     *dontuse* and, ic:151  
 user accounts  
     *See also* accounts  
     *See also* User Manager  
 user accreditation range, la:34  
     defined, ao:8  
     described, ap:374  
     minimum clearance, ao:9  
     minimum sensitivity label, ao:9  
 user audit fields, aa:14 to aa:15  
 user clearances  
     defined, ug:5  
     described, ap:374  
 user commands  
     new, tg:45  
 user comments  
     assigning, ao:67  
 user database, *See* databases  
 User Datagram Protocol, *See* UDP  
 user ID (audit ID), aa:3  
 user IDs, *See* UIDs  
 User Manager  
     assigning account type, ap:127, ao:67  
     assigning GIDs, ao:66  
     assigning login shells, ao:67  
     assigning passwords, ap:128 to  
         ap:134  
     assigning profiles in the desired  
         order, ap:526  
     assigning profiles to accounts, ap:538  
     assigning UIDs, ao:66  
     assigning user comments, ao:67  
     assigning user names, ao:66  
     data entries explained, ap:122 to  
         ap:144  
     deleting local user, ic:38  
     deleting users, ao:83  
     dialog boxes  
         Home, ao:64, ao:74 to ao:75  
         Identity, ao:64, ao:65 to ao:68  
         Idle, ao:64, ao:82 to ao:83  
         Labels, ao:64, ao:76 to ao:78  
         Load dialog box, ao:60  
         Navigator, ao:63  
         Password, ao:64, ao:68 to ao:73  
         Profiles, ao:64, ao:78 to ao:80  
         Roles, ao:64, ao:80 to ao:81  
     Edit menu, ao:62  
     Home dialog box, ap:134 to ap:136  
     identity dialog box, ap:124  
     Idle dialog box, ap:143 to ap:144  
     Labels dialog box, ap:136 to ap:140  
     launching, ao:60  
     main window, ao:62  
     opening an account closed by too  
         many failed logins, ap:43  
     overview, ao:60 to ao:83  
     Password dialog box  
         opening a closed account, ap:43  
     procedures, ap:144 to ap:175  
     Profile dialog box, ap:141 to ap:142  
     required authorizations, ap:110,  
         ap:112  
     Roles dialog box, ap:143  
     setting labels, la:43  
     use, tg:17  
     using, ic:35, ap:26, ap:28  
     worksheet, ap:212  
 user names  
     assigning, ap:124, ao:66  
 USER\_ACCREDITATION\_RANGE  
     value, dg:101  
 userent\_t structure, dg:212  
 user-level events  
     audit number range, aa:6  
     audit records, aa:301 to aa:337  
     audit tokens, aa:70

---

auditconfig command  
     options, aa:23  
     described, aa:6  
 usermgr audit records, aa:336  
**users**  
     *See also* User Manager  
     ACL entry, ug:103  
     administering, ao:59 to ao:83  
     auditing normal users, aa:13  
     deleting a local user, ic38  
     exceptions to audit flags, aa:51  
     security attributes, ao:38  
     security training, ap:36 to ap:41  
     session range, ao:11  
     setting up accounts, ic:197  
 usertype field, dg:212  
 /usr/bin/at audit record  
     at-create crontab, aa:304  
     at-delete atjob, aa:305  
     at-permission, aa:305  
 /usr/bin/crontab audit record  
     cron-invoke atjob, aa:309  
     crontab-crontab  
         created, aa:308  
     crontab-crontab  
         deleted, aa:309  
     crontab-permission, aa:310  
     crontab, aa:309  
 /usr/bin/login audit record  
     logout, aa:318  
     rlogin, aa:317, aa:318  
     telnet login, aa:318  
     terminal login, aa:317  
 /usr/bin/passwd: change  
     password audit record, aa:322  
 /usr/bin/pfsh audit record, aa:323  
 /usr/bin/setuname audit  
     record, aa:332  
 /usr/bin/su audit record, aa:334  
 /usr/bin/uname audit record, aa:336  
 /usr/dt/ directory, tg:20  
 /usr/dt/appconfig/appmanager/C/  
     System\_Admin file  
     adding an administrative  
         action, ap:30  
 /usr/dt/appconfig/types/C/TSOLa  
     dmin.dt file  
     adding an administrative  
         action, ap:29  
 /usr/dt/bin/dtfile audit  
     record, aa:312  
 /usr/lib/lpadmin audit record, aa:319  
 /usr/lib/lpsched audit  
     records, aa:319 to aa:320  
 /usr/lib/nfs/mountd audit record  
     automount mismatch, aa:307  
     automount request, aa:307  
     NFS mount request, aa:321  
     NFS unmount request, aa:321  
 /usr/lib/sendmail audit  
     record, aa:331  
 /usr/sbin/add\_drv audit  
     record, aa:301  
 /usr/sbin/allocate audit record  
     allocate-list device  
         failure, aa:304  
     allocate-list device  
         success, aa:303  
     device allocate  
         failure, aa:303  
     device allocate  
         success, aa:302  
 /usr/sbin/audit audit record, aa:306  
 /usr/sbin/chroot audit record, aa:308  
 /usr/sbin/deallocate audit record  
     deallocate device, aa:311  
     deallocate device  
         failure, aa:311  
 /usr/sbin/eeprom audit record, aa:313  
 /usr/sbin/fuser audit record, aa:313  
 /usr/sbin/halt audit record, aa:314  
 /usr/sbin/in.ftpd audit  
     record, aa:316  
 /usr/sbin/in.rexecd audit  
     record, aa:328

---

/usr/sbin/in.rshd audit record, aa:329  
 /usr/sbin/inetd audit record, aa:316  
 /usr/sbin/init audit record, aa:330  
 /usr/sbin/installf audit record, aa:317  
 /usr/sbin/modload audit record, aa:320  
 /usr/sbin/modunload audit record, aa:320  
 /usr/sbin/pbind audit record, aa:322  
 /usr/sbin/psradm audit record, aa:326  
 /usr/sbin/reboot audit record, aa:327  
 /usr/sbin/removef audit record, aa:327  
 /usr/sbin/rpc.rexd audit record, aa:328  
 /usr/sbin/swap audit record, aa:334  
 /usr/sbin/uadmin audit record, aa:335  
 utilities  
     C library functions, aa:341  
     headers, tables, and macros, aa:342  
     maintenance commands, aa:339  
     system calls, aa:340  
 utime audit record, aa:273  
 utimes audit record, aa:273  
 utssys - fusers audit record, aa:274

**V**

valid clearances  
     checking, dg:163  
     ensuring, dg:154  
 valid labels  
     accreditation ranges, dg:133  
     checking, dg:134  
     ensuring, dg:102  
 value  
     classification keyword, la:64  
 value=, cm:19, cm:21, cm:29, cm:31, cm:59,  
     cm:85, cm:112, cm:120, cm:124  
 /var/sadm/begin.log file, ic:174  
 /var/sadm/finish.log file, ic:176

/var/sadm/system/data/upgrade\_cleanup file, ic:50  
 /var/sadm/system/logs/install\_log file, ic:61  
 /var/sadm/system/logs/upgrade\_log file, ic:49, ic:61  
 variables  
     PASSWD, ic:179  
     SI\_CONFIG\_DIR, ic:177  
     SI\_PROFILE, ic:175  
     SI\_SYS\_STATE, ic:180  
     SYS\_MEMSIZE, ic:181  
 vers\_len field, dg:101  
 version of Trusted Solaris software  
     *installed* rule keyword, ic:164  
     *osname* rule keyword, ic:167  
 VERSION section  
     label\_encodings example, la:163  
 version string retrieval, dg:114  
 version=, la:6, cm:16, cm:17, cm:82, cm:85,  
     cm:123  
 vfork audit record, aa:274  
 vfstab file, ic:153  
 vfstab, ap:14  
 vfstab\_adjunct file  
     code example, dg:31  
     retrieving entries, dg:31  
 vfstab\_adjunct(4TSOL) file  
     action for editing, ap:14  
 View Table Contents action  
     described, ap:14  
 VIEW\_EXTERNAL flag, dg:139  
 VIEW\_INTERNAL flag, dg:139  
 visible, cm:68  
 vtrace audit record, aa:275

**W**

well formed labels, cm:5 to cm:29, cm:31,  
     cm:37, cm:48 to cm:52, cm:70,  
     cm:114, cm:116  
 well-formed labels  
     defined, ao:6

---

wildcard  
     trusted network fallback  
         option, ap:327

win\_config privilege, dg:293

win\_dac\_read privilege, dg:293

win\_dac\_write privilege, dg:293

win\_devices privilege, dg:293

win\_dga privilege, dg:293

win\_downgrade\_il privilege, dg:293

win\_downgrade\_sl privilege, dg:293

win\_fontpath privilege, dg:294

win\_mac\_read privilege, dg:293

win\_mac\_write privilege, dg:293

win\_nofloat privilege, dg:294

win\_upgrade\_il privilege, dg:294

win\_upgrade\_sl privilege, dg:294

window ILL change audit record, aa:315

window manager, ap:528

Window SL field  
     described, ug:72

window system  
     differences in Trusted Solaris, la:14  
     trusted processes, ap:527  
         passing inheritable  
         privileges, ap:538

windows  
     *See also* X Window System  
     authorizations, ao:27  
     client, security policy, dg:291  
     configuring polyinstantiation, tg:21  
     cut-and-paste, tg:20  
     defaults, dg:292  
     described, dg:289  
     drag 'n drop, tg:20  
     labels, tg:19  
     moving data between, ug:57 to ug:60  
     override-redirect, security  
         policy, dg:291  
     privileges, dg:293, ao:30  
     properties, tg:21  
     remote display, tg:38  
     root, security policy, dg:291  
     security policy, dg:290  
     server policy, tg:21  
     Tootalk, tg:20  
     untrusted client restrictions, tg:34

word  
     default, cm:5, cm:21, cm:22, cm:23,  
         cm:24, cm:72, cm:116  
     inverse, cm:4, cm:8, cm:9, cm:10,  
         cm:22, cm:23, cm:30, cm:31,  
         cm:32, cm:41, cm:43, cm:62,  
         cm:70, cm:127, cm:132,  
         cm:135, cm:137  
     normal, cm:4, cm:8, cm:9, cm:11,  
         cm:12, cm:21, cm:74

word order requirements  
     label\_encodings file, la:62

work groups  
     represented by label  
         compartments, la:10

worksheets  
     auditing, aa:343 to aa:351  
     blanks, ic:207 to ic:225  
     examples, ic:248 to ic:264  
     for hosts, ap:577  
     for user accounts, ap:212

Workspace Menu  
     as trusted process, ap:527  
     modifying, ap:425 to ap:433

workspace switch area  
     controls, ug:97  
     differences in Trusted Solaris, ug:73

workspaces  
     administrative  
         using, ap:8 to ap:29  
     administrative role, la:14  
     Change SL audit record, aa:333  
     changing, ug:49 to ug:52  
     changing to admin\_high, aa:61  
     changing what displays after  
         login, la:14  
     creating at admin\_high, ic:27  
     initial, la:14  
     labeled, la:14  
     multiple, tg:34  
     relabeling, la:14  
     for roles, tg:34

---

trusted restrictions, tg:4  
 workstation configuration  
   system privileges, ao:30  
 Workstation Information dialog box  
   example, ug:39 to ug:40  
   introduction, ug:20  
   procedure, ug:24 to ug:27  
 workstation shutdown  
   not Stop-A, tg:4  
 workstations  
   adding, ic:197  
   booting, ic:52  
   performance, ic:198  
   planning audit space, aa:32  
   protecting, ic:27 to ic:29  
   screen-locking, ic:52  
   shutting down, ic:52  
   starting, ic:52  
 wrapping lines in rules, ic:163  
 write access  
   IL conjoin, dg:92  
   overview, ug:7  
   security policy, dg:14  
 write audit record, aa:275  
 write equal, dg:14  
 write up, dg:14  
 write up policy  
   for unlabeled machines, tg:4  
 writel audit record, aa:276  
 writev1 audit record, aa:276  
 WURD  
   defined, ug:7

**X**

X protocol extensions, tg:67  
 X server  
   window privileges, ao:30  
 X server extensions audit  
   record, aa:300  
 X Window System  
   *See also* code examples  
   API declarations, dg:297 to dg:303,  
   dg:358

authorizations, defined, dg:82  
 client attributes structure, dg:295  
 client window, dg:291  
 configurable policy, tg:4  
 configuring policy, tg:21  
 defaults, dg:292  
 described, tg:66  
 input devices, dg:291  
 label clipping API  
   declarations, dg:352  
 Motif source code, dg:309 to dg:313  
 object attribute structure, dg:295  
 object type definition, dg:295  
 objects, dg:3, dg:289  
 override-redirect, dg:291  
 predefined atoms, dg:292  
 privileged tasks, dg:293  
 privileges, tg:104  
 privileges, defined, dg:53  
 properties, dg:290  
 property attribute structure, dg:295  
 protocol extensions, dg:287  
 resource file, dg:309  
 root window, dg:291  
 security attributes, tg:67  
   contrast with Solaris, dg:12  
   described, dg:289  
 security policy, dg:290  
 Selection Manager, dg:292  
 server control, dg:291

xa audit class, aa:120  
 xa audit flag, aa:99  
 XAllocColor audit record, aa:293  
 XAllocColorCells audit record, aa:293  
 XAllocColorPlanes audit  
   record, aa:293  
 XAllocNamedColor audit record, aa:293  
 xatom token  
   described, aa:174  
   praudit display, aa:174  
 xbcleartos(3TSOL),  
   declaration, dg:303  
 xbc1tos(3TSOL), declaration, dg:303  
 xbiltos(3TSOL), declaration, dg:303

---

**xbsltos(3TSOL)**  
     code example, dg:306  
     declaration, dg:303  
**xc** audit class, aa:121  
**xc** audit flag, aa:99  
**XChangeActivePointerGrab** audit record, aa:283  
**XChangeHosts** audit record, aa:299  
**XChangeKeyboardControl** audit record, aa:297  
**XChangeKeyboardMapping** audit record, aa:297  
**XChangePointerControl** audit record, aa:297  
**XChangeProperty** audit record, aa:281  
**XChangeSaveSet** audit record, aa:280  
**XChangeWindowAttributes** audit record, aa:280  
**XCirculateWindow** audit record, aa:280  
**XClearArea** audit record, aa:290  
**xclient** token  
     described, aa:174  
     praudit display, aa:174  
**XClientConnect** audit record, aa:278  
**XClientDisconnect** audit record, aa:279  
**xcolormap** token  
     described, aa:175  
     praudit display, aa:175  
**XConfigureWindow** audit record, aa:280  
**XConvertSelection** audit record, aa:282  
**XCopyArea** audit record, aa:290  
**XCopyColormapAndFree** audit record, aa:294  
**XCopyPlane** audit record, aa:290  
**XCreateColormap** audit record, aa:292  
**XCreateCursor** audit record, aa:295  
**XCreateGlyphCursor** audit record, aa:296  
**XCreateWindow** audit record, aa:280  
  
**xcursor** token  
     described, aa:175  
     praudit display, aa:175  
**XDeleteProperty** audit record, aa:281  
**XDestroySubwindows** audit record, aa:280  
**XDestroyWindow** audit record, aa:280  
**XFillPolygon** audit record, aa:291  
**xfont** token  
     described, aa:175  
     praudit display, aa:176  
**XForceScreenSaver** audit record, aa:298  
**XFreeColormap** audit record, aa:294  
**XFreeColors** audit record, aa:293  
**XFreePixmap** audit record, aa:297  
**xgc** token  
     described, aa:176  
     praudit display, aa:176  
**XGetAtomName** audit record, aa:281  
**XGetGeometry** audit record, aa:280  
**XGetImage** audit record, aa:291  
**XGetMotionEvents** audit record, aa:286  
**XGetProperty** audit record, aa:281  
**XGetSelectionOwner** audit record, aa:282  
**XGetWindowAttributes** audit record, aa:280  
**XGrabButton** audit record, aa:282  
**XGrabKey** audit record, aa:284  
**XGrabKeyboard** audit record, aa:284  
**XGrabPointer** audit record, aa:283  
**XImageText16** audit record, aa:291  
**XImageText8** audit record, aa:291  
**XInstallColormap** audit record, aa:294  
**XInternAtom** audit record, aa:281  
**XKillClient** audit record, aa:299  
**x1** audit class, aa:122  
**x1** audit flag, aa:99  
**Xlib**  
     API declarations, dg:297 to dg:303  
     described, dg:10

---

objects, dg:289  
 XListInstalledColormap audit record, aa:294  
 XListProperty audit record, aa:281  
 XLookupColor audit record, aa:295  
 XMapSubwindows audit record, aa:280  
 XMapWindow audit record, aa:280  
 xmknod audit record, aa:276  
 xp audit class, aa:122  
 xp audit flag, aa:99  
 xp\_tsol\_incoming\_attrsp field, dg:279  
 xp\_tsol\_incoming\_new\_attrs field, dg:279  
 xp\_tsol\_outgoing\_attrsp field, dg:279  
 xpixmap token described, aa:176  
     praudit display, aa:176  
 XPolyArc audit record, aa:291  
 XPolyFillArc audit record, aa:291  
 XPolyFillRectangle audit record, aa:291  
 XPolyLine audit record, aa:291  
 XPolyPoint audit record, aa:291  
 XPolyRectangle audit record, aa:291  
 XPolySegment audit record, aa:291  
 XPolyText16 audit record, aa:292  
 XPolyText8 audit record, aa:291  
 xproperty token described, aa:177  
     praudit display, aa:177  
 XPutImage audit record, aa:292  
 XQueryColors audit record, aa:295  
 XQueryTree audit record, aa:280  
 XRecolorCursor audit record, aa:296  
 XReparentWindow audit record, aa:280  
 XRotateProperties audit record, aa:299  
 xs audit class, aa:124  
 xs audit flag, aa:99  
 xselect token described, aa:177  
     praudit display, aa:178  
 X-Sender-Information-Label, la:23  
 XSendEvent audit record, aa:286  
 Xserver protocols audit records, aa:278 to aa:300  
 Xsession file, ap:444  
 XSetAccessControl audit record, aa:299  
 XSetClipRecatangles audit record, aa:289  
 XSetCloseDownMode audit record, aa:298  
 XSetDashes audit record, aa:289  
 XSetFontPath audit record, aa:288  
 XSetInputFocus audit record, aa:287  
 XSetModifierMapping audit record, aa:300  
 XSetPointerMapping audit record, aa:300  
 XSetScreenSaver audit record, aa:298  
 XSetSselectionOwner audit record, aa:282  
 xstat audit record, aa:277  
 XStoreColors audit record, aa:295  
 XStoreNamedColor audit record, aa:295  
 XTsolClientAttributes structure, dg:295  
 XTSOLgetClientAttributes(3X11TSOL), declaration, dg:297  
 XTSOLgetPropAttributes(3X11TSOL), declaration, dg:297  
 XTSOLgetPropLabel(3X11TSOL), declaration, dg:299  
 XTSOLgetPropUID(3X11TSOL), declaration, dg:300  
 XTSOLgetResAttributes(3X11TSOL) code example, dg:305  
     declaration, dg:297  
 XTSOLgetResLabel(3X11TSOL) code example, dg:307

---

declaration, dg:298  
 XTSOLgetResUID(3X11TSOL)  
     code example, dg:308  
     declaration, dg:298  
 XTSOLgetSSHeight(3X11TSOL),  
     declaration, dg:302  
 XTSOLgetWindowIIL(3X11TSOL),  
     declaration, dg:299  
 XTSOLgetWorkstationOwner(3X11TSOL),  
     code example, dg:308  
     declaration, dg:300  
 XTSOLisWindowTrusted(3X11TSOL),  
     declaration, dg:301  
 XTSOLmakeTPWindow(3X11TSOL),  
     declaration, dg:301  
 XtsolPropAttributes  
     structure, dg:295  
 XtsolResAttributes structure, dg:295  
 XTSOLsetPropLabel(3X11TSOL),  
     declaration, dg:299  
 XTSOLsetPropUID(3X11TSOL),  
     declaration, dg:300  
 XTSOLsetResLabel(3X11TSOL)  
     code example, dg:308  
     declaration, dg:298  
 XTSOLsetSessionHI(3X11TSOL),  
     declaration, dg:301  
 XTSOLsetSessionLO(3X11TSOL),  
     declaration, dg:301  
 XTSOLsetSSHeight(3X11TSOL),  
     declaration, dg:302  
 XTSOLsetWindowIIL(3X11TSOL),  
     declaration, dg:299  
 XTSOLsetWorkstationOwner(3X11TSOL),  
     declaration, dg:300  
 Xtsolusersession file, ap:444  
 Xtsolusersession script, ap:528  
 XUngrabButton audit record, aa:283  
 XUngrabKey audit record, aa:284  
 XUngrabKeyboard audit record, aa:284  
 XUngrabPointer audit record, aa:283  
 XUngrabServer audit record, aa:285  
 XUninstallColormap audit  
     record, aa:294  
 XUnmapSubwindows audit record, aa:280  
 XUnmapWindow audit record, aa:280  
 XView, tg:73  
 XWarpPointer audit record, aa:286  
 xwindow token  
     described, aa:178  
     praudit display, aa:178  
 xx audit class, aa:126  
 xx audit flag, aa:99

**Z**

zh locale name, ic:154  
 zh\_TW locale name, ic:154  
 zones, time, ic:267 to ic:268