ORACLE
INSURANCE

Oracle Insurance Insight

Oracle Insurance Insight MetaData Dictionary

version 7.0

Part Number: E22075-01

December 2010

All Terms

All Terms

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	BILL_ACCT	BEGIN_DT	Begin Date	DATE	This calendar date represents when the bill account applies.
Warehouse	BILL_ACCT	BILL_ACCT_ID	Billing Account Identifier	NUMBER (22, 0)	This system generated number identifies the billing account instance.
Staging	BILL_ACCT	BILL_ACCT_NAT_KEY	Billing Account Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the billing account.
Warehouse	BILL_ACCT	BILL_ACCT_NAT_KEY	Billing Account Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the billing account.
Staging	BILL_ACCT	BILL_ACCT_NUM	Billing Account Number	VARCHAR2(20)	This value represents the number of the account.
Warehouse	BILL_ACCT	BILL_ACCT_NUM	Billing Account Number	VARCHAR2(20)	This value represents the number of the account.
Staging	BILL_ACCT	BILL_ACCT_UDF_CD_1	Billing Account User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first billing account user defined field.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_CD_1	Billing Account User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first billing account user defined field.
Staging	BILL_ACCT	BILL_ACCT_UDF_CD_2	Billing Account User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second billing account user defined field.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_CD_2	Billing Account User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second billing account user defined field.
Staging	BILL_ACCT	BILL_ACCT_UDF_CD_3	Billing Account User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third billing account user defined field.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_CD_3	Billing Account User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third billing account user defined field.
Staging	BILL_ACCT	BILL_ACCT_UDF_CD_4	Billing Account User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth billing account user defined field.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_CD_4	Billing Account User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth billing account user defined field.
Staging	BILL_ACCT	BILL_ACCT_UDF_CD_5	Billing Account User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth billing account user defined field.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_CD_5	Billing Account User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth billing account user defined field.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_DESC_1	Billing Account User Defined Field Description 1	VARCHAR2(60)	This value describes the first billing account policy user defined field.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_DESC_2	Billing Account User Defined Field Description 2	VARCHAR2(60)	This value describes the second billing account policy user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	BILL_ACCT	BILL_ACCT_UDF_DESC_3	Billing Account User Defined Field Description 3	VARCHAR2(60)	This value describes the third billing account policy user defined field.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_DESC_4	Billing Account User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth billing account policy user defined field.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_DESC_5	Billing Account User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth billing account policy user defined field.
Warehouse	BILL_ACCT	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the bill account is currently applicable.
Warehouse	BILL_ACCT	END_DT	End Date	DATE	This calendar date represents when the bill account is no longer valid.
Staging	BILL_ACCT	METH_OF_PMT_CD	Method of Payment Code	VARCHAR2(25)	This system code indicates the means by which the payment was/will be made and type of account being credited or debited.g. for premium payment, a credit card may be charged, and for a claim payment , a checking account may be credited).
Warehouse	BILL_ACCT	METH_OF_PMT_CD	Method of Payment Code	VARCHAR2(25)	This system code indicates the means by which the payment was/will be made and type of account being credited or debited.g. for premium payment, a credit card may be charged, and for a claim payment , a checking account may be credited).
Warehouse	BILL_ACCT	METH_OF_PMT_DESC	Method of Payment Description	VARCHAR2(60)	This value describes the means by which the payment was/will be made and type of account being credited or debited.g. for premium payment, a credit card may be charged, and for a claim payment, a checking account may be credited).
Staging	BILL_ACCT	PMT_PLAN_CD	Payment Plan Code	VARCHAR2(25)	This system code identifies the frequency of premium payment.
Warehouse	BILL_ACCT	PMT_PLAN_CD	Payment Plan Code	VARCHAR2(25)	This system code identifies the frequency of premium payment.
Warehouse	BILL_ACCT	PMT_PLAN_DESC	Payment Plan Description	VARCHAR2(60)	This value describes the premium payment plan.
Staging	BILL_ACCT	PMT_SVC_CD	Payment Service Code	VARCHAR2(25)	This system code identifies the type of billing plan used.
Warehouse	BILL_ACCT	PMT_SVC_CD	Payment Service Code	VARCHAR2(25)	This system code identifies the type of payment service used.
Warehouse	BILL_ACCT	PMT_SVC_DESC	Payment Service Description	VARCHAR2(60)	This value describes the type of payment service used.
Staging	BILL_ACCT	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the billing account with a specific transaction.
Datamart	BILL_ACCT_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the bill account applies.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	BILL_ACCT_DIM	BILL_ACCT_ID	Billing Account Identifier	NUMBER (22, 0)	This system generated number identifies the billing account instance.
Datamart	BILL_ACCT_DIM	BILL_ACCT_NAT_KEY	Billing Account Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the billing account.
Datamart	BILL_ACCT_DIM	BILL_ACCT_NUM	Billing Account Number	VARCHAR2(20)	This value represents the number of the account.
Datamart	BILL_ACCT_DIM	BILL_ACCT_UDF_1	Billing Account User Defined Field 1	VARCHAR2(60)	This value describes the first billing account policy user defined field.
Datamart	BILL_ACCT_DIM	BILL_ACCT_UDF_2	Billing Account User Defined Field 2	VARCHAR2(60)	This value describes the second billing account policy user defined field.
Datamart	BILL_ACCT_DIM	BILL_ACCT_UDF_3	Billing Account User Defined Field 3	VARCHAR2(60)	This value describes the third billing account policy user defined field.
Datamart	BILL_ACCT_DIM	BILL_ACCT_UDF_4	Billing Account User Defined Field 4	VARCHAR2(60)	This value describes the fourth billing account policy user defined field.
Datamart	BILL_ACCT_DIM	BILL_ACCT_UDF_5	Billing Account User Defined Field 5	VARCHAR2(60)	This value describes the fifth billing account policy user defined field.
Datamart	BILL_ACCT_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the bill account is currently applicable.
Datamart	BILL_ACCT_DIM	END_DT	End Date	DATE	This calendar date represents when the bill account is no longer valid.
Datamart	BILL_ACCT_DIM	METH_OF_PMT	Method of Payment	VARCHAR2(60)	This value represents the manner in which payments are made on an outstanding policy balance.
Datamart	BILL_ACCT_DIM	PMT_PLAN	Payment Plan	VARCHAR2(60)	This value represents the payment schedule applied to a policy balance.
Datamart	BILL_ACCT_DIM	PMT_SVC	Payment Service	VARCHAR2(60)	This value represents the entity that processes insured payments.
Warehouse	CA_DRV	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage.
Warehouse	CA_DRV	CA_DRV_ID	Commercial Auto Driver Identifier	NUMBER (22, 0)	This system generated number identifies the commercial auto driver instance.
Staging	CA_DRV	CA_DRV_UDF_CD_1	Commercial Auto Driver User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first commercial auto driver user defined field.
Warehouse	CA_DRV	CA_DRV_UDF_CD_1	Commercial Auto Driver User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first commercial auto driver user defined field.
Staging	CA_DRV	CA_DRV_UDF_CD_2	Commercial Auto Driver User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second commercial auto driver user defined field.
Warehouse	CA_DRV	CA_DRV_UDF_CD_2	Commercial Auto Driver User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second commercial auto driver user defined field.
Staging	CA_DRV	CA_DRV_UDF_CD_3	Commercial Auto Driver User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third commercial auto driver user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CA_DRV	CA_DRV_UDF_CD_3	Commercial Auto Driver User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third commercial auto driver user defined field.
Staging	CA_DRV	CA_DRV_UDF_CD_4	Commercial Auto Driver User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth commercial auto driver user defined field.
Warehouse	CA_DRV	CA_DRV_UDF_CD_4	Commercial Auto Driver User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth commercial auto driver user defined field.
Staging	CA_DRV	CA_DRV_UDF_CD_5	Commercial Auto Driver User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth commercial auto driver user defined field.
Warehouse	CA_DRV	CA_DRV_UDF_CD_5	Commercial Auto Driver User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth commercial auto driver user defined field.
Warehouse	CA_DRV	CA_DRV_UDF_DESC_1	Commercial Auto Driver User Defined Field Description 1	VARCHAR2(60)	This value describes the first commercial auto driver user defined field.
Warehouse	CA_DRV	CA_DRV_UDF_DESC_2	Commercial Auto Driver User Defined Field Description 2	VARCHAR2(60)	This value describes the second commercial auto driver user defined field.
Warehouse	CA_DRV	CA_DRV_UDF_DESC_3	Commercial Auto Driver User Defined Field Description 3	VARCHAR2(60)	This value describes the third commercial auto driver user defined field.
Warehouse	CA_DRV	CA_DRV_UDF_DESC_4	Commercial Auto Driver User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth commercial auto driver user defined field.
Warehouse	CA_DRV	CA_DRV_UDF_DESC_5	Commercial Auto Driver User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth commercial auto driver user defined field.
Warehouse	CA_DRV	CDL_ENDR_CD	Commercial Driver License Endorsement Code	VARCHAR2(25)	This system code identifies the drivers license endorsements granted to commercial driver.
Warehouse	CA_DRV	CDL_ENDR_DESC	Commercial Driver License Endorsement Description	VARCHAR2(60)	This value describes the commercial driver license endorsements granted to a commercial driver.
Warehouse	CA_DRV	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the commercial auto driver is currently included in policy coverage.
Staging	CA_DRV	DFEN_DRV_CD	Defensive Driving Code	VARCHAR2(25)	This system code indicates the type of defensive driving course the commercial auto driver completed.
Warehouse	CA_DRV	DFEN_DRV_CD	Defensive Driving Code	VARCHAR2(25)	This system code indicates the type of defensive driving course the commercial auto driver completed.
Warehouse	CA_DRV	DFEN_DRV_DESC	Defensive Driving Description	VARCHAR2(60)	This value describes the defensive driving code.
Staging	CA_DRV	DFEN_DRV_TRNG_DSCNT_FLG	Defensive Driving Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a defensive driver training discount applies.
Warehouse	CA_DRV	DFEN_DRV_TRNG_DSCNT_FLG	Defensive Driving Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a defensive driver training discount applies.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CA_DRV	DFEN_DRV_TRNG_DSCNT_PCT	Defensive Driving Training Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when driver training discount applies.
Warehouse	CA_DRV	DFEN_DRV_TRNG_DSCNT_PCT	Defensive Driving Training Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when driver training discount applies.
Staging	CA_DRV	DRV_ACCID_CNT	Driver Accident Count	NUMBER (22,0)	This number represents the number of accidents a driver has been charged against his or her driving record.
Warehouse	CA_DRV	DRV_ACCID_CNT	Driver Accident Count	NUMBER (22, 0)	This number represents the count of accidents a driver has been charged against his or her driving record.
Staging	CA_DRV	DRV_CLASS_CD	Driver Class Code	VARCHAR2(25)	This system code identifies the driver class.
Warehouse	CA_DRV	DRV_CLASS_CD	Driver Class Code	VARCHAR2(25)	This system code identifies the driver class.
Warehouse	CA_DRV	DRV_CLASS_DESC	Driver Class Description	VARCHAR2(60)	This value describes the driver class.
Staging	CA_DRV	DRV_DWI_DUI_VIOLATION_CNT	Driver DWI / DUI Violation Count	NUMBER (22,0)	This number represents the count of Driving While Intoxicated (DWI) and/or Driving Under the Influence (DUI) violations charged against the driver's driving record.
Warehouse	CA_DRV	DRV_DWI_DUI_VIOLATION_CNT	Driver DWI / DUI Violation Count	NUMBER (22, 0)	This number represents the count of Driving While intoxicated (DWI) and/or Driving Under the influence (DUI) violations charged against the driver's driving record.
Staging	CA_DRV	DRV_INTRMDT_VIOLATION_CNT	Driver Intermediate Violation Count	NUMBER (22,0)	This number represents the count of intermediate violations charged against the driver's driving record.
Warehouse	CA_DRV	DRV_INTRMDT_VIOLATION_CNT	Driver Intermediate Violation Count	NUMBER (22, 0)	This number represents the count of intermediate violations charged against the driver's driving record.
Staging	CA_DRV	DRV_LIC_ISSUED_BY_CD	Driver License Issued By Code	VARCHAR2(25)	This system code indentifies which entity granted driving privileges to driver.
Warehouse	CA_DRV	DRV_LIC_ISSUED_BY_CD	Driver License Issued By Code	VARCHAR2(25)	This system code indentifies which entity granted driving privileges to driver.
Warehouse	CA_DRV	DRV_LIC_ISSUED_BY_DESC	Driver License Issued By Description	VARCHAR2(60)	This value describes the entity that issued a drivers license.
Staging	CA_DRV	DRV_LIC_STATUS_CD	Driver License Status Code	VARCHAR2(25)	This system code indicates the driver license status.
Warehouse	CA_DRV	DRV_LIC_STATUS_CD	Driver License Status Code	VARCHAR2(25)	This system code indicates the driver license status.
Warehouse	CA_DRV	DRV_LIC_STATUS_DESC	Driver License Status Description	VARCHAR2(60)	This value describes the status of a drivers license.
Staging	CA_DRV	DRV_MAJOR_VIOLATION_CNT	Driver Major Violation Count	NUMBER (22,0)	This number represents the count of major violations charged against the driver's driving record.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CA_DRV	DRV_MAJOR_VIOLATION_CNT	Driver Major Violation Count	NUMBER (22, 0)	This number represents the count of major violations charged against the driver's driving record.
Staging	CA_DRV	DRV_MINOR_VIOLATION_CNT	Driver Minor Violation Count	NUMBER (22,0)	This number represents the count of minor violations charged against the driver's driving record.
Warehouse	CA_DRV	DRV_MINOR_VIOLATION_CNT	Driver Minor Violation Count	NUMBER (22, 0)	This number represents the count of minor violations charged against the driver's driving record.
Staging	CA_DRV	DRV_NUM	Driver Number	NUMBER (22,0)	This number identifies the driver.
Warehouse	CA_DRV	DRV_NUM	Driver Number	NUMBER (22, 0)	This number identifies the driver.
Staging	CA_DRV	DRV_STATUS_CD	Driver Status Code	VARCHAR2(25)	This system code indicates the driver status.
Warehouse	CA_DRV	DRV_STATUS_CD	Driver Status Code	VARCHAR2(25)	This system code indicates the driver status.
Warehouse	CA_DRV	DRV_STATUS_DESC	Driver Status Description	VARCHAR2(60)	This value describes the status of a driver.
Staging	CA_DRV	DRV_TRNG_DSCNT_FLG	Driver Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not driver training discount applies.
Warehouse	CA_DRV	DRV_TRNG_DSCNT_FLG	Driver Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not driver training discount applies.
Staging	CA_DRV	DRV_TRNG_DSCNT_PCT	Driver Training Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when driver training discount applies.
Warehouse	CA_DRV	DRV_TRNG_DSCNT_PCT	Driver Training Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when driver training discount applies.
Staging	CA_DRV	DRV_TRNG_FLG	Driver Training Flag	CHAR(1)	This value represents based on the yes/no indicator that identifies whether or not a driver has completed a driver training course.
Warehouse	CA_DRV	DRV_TRNG_FLG	Driver Training Flag	CHAR(1)	This value represents based on the yes/no indicator that identifies whether or not a driver has completed a driver training course.
Staging	CA_DRV	DRV_TYP_CD	Driver Type Code	VARCHAR2(25)	This system code describes the driver activities.
Warehouse	CA_DRV	DRV_TYP_CD	Driver Type Code	VARCHAR2(25)	This system code describes the driver activities.
Warehouse	CA_DRV	DRV_TYP_DESC	Driver Type Description	VARCHAR2(60)	This value describes driver type.
Warehouse	CA_DRV	END_DT	End Date	DATE	This calendar date represents when the commercial driver is no longer included in policy coverages.
Staging	CA_DRV	INSD_DT	Insured Date	DATE	This calendar date represents when insurance coverage began for commercial auto driver.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CA_DRV	INSD_DT	Insured Date	DATE	This calendar date represents when insurance coverage began for commercial auto driver.
Staging	CA_DRV	LIC_DT	License Date	DATE	This calendar date represents when commercial auto driver was granted a drivers license.
Warehouse	CA_DRV	LIC_DT	License Date	DATE	This calendar date represents when commercial auto driver was granted a drivers license.
Warehouse	CA_DRV	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	CA_DRV	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person.
Staging	CA_DRV	RLAT_TO_APPLICANT_CD	Relationship to Applicant Code	VARCHAR2(25)	This system code identifies the relationship of this individual to the applicant.
Warehouse	CA_DRV	RLAT_TO_APPLICANT_CD	Relationship to Applicant Code	VARCHAR2(25)	This system code identifies the relationship of this individual to the applicant.
Warehouse	CA_DRV	RLAT_TO_APPLICANT_DESC	Relationship to Applicant Code Description	VARCHAR2(60)	This value describes the relationship to applicant code.
Staging	CA_DRV	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the commercial auto driver with a specific transaction.
Datamart	CA_DRV_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage.
Datamart	CA_DRV_DIM	CA_DFEN_DRV_TRNG_DSCNT_PCT	Commercial Auto Defensive Driving Training Discount Percent	NUMBER (6, 3)	This number represents the percentage of premium waived when the defensive driver training discount applies.
Datamart	CA_DRV_DIM	CA_DFEN_DRV_TRNG_FLG	Commercial Auto Defensive Driving Training Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not the driver completed a defensive driver training course.
Datamart	CA_DRV_DIM	CA_DRV_ACCID_CNT	Commercial Auto Driver Accident Count	NUMBER (22, 0)	This number represents the count of accidents charged against the driver's driving record.
Datamart	CA_DRV_DIM	CA_DRV_BIRTH_DT_ID	Commercial Auto Driver Birth Date Identifier	DATE	This calendar date represents the commercial auto driver's date of birth.
Datamart	CA_DRV_DIM	CA_DRV_CDL_ENDR_CD	Commercial Auto Driver Commercial Drivers License Endorsement Code	VARCHAR2(60)	This system code describes types of endorsements that apply to driver's commercial drivers license.
Datamart	CA_DRV_DIM	CA_DRV_CLASS	Commercial Auto Driver Class	VARCHAR2(60)	This value represents the classification that describes the characteristics of a the driver. It is typically only used for assigned risk, JUA, and in Texas.
Datamart	CA_DRV_DIM	CA_DRV_DFEN_DRV_CD	Commercial Auto Driver Defensive Driving Code	VARCHAR2(60)	This system code indicates the type of defensive driving course the driver completed.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CA_DRV_DIM	CA_DRV_DWI_DUI_VIOLATION_CNT	Commercial Auto Driver DWI / DUI Violation Count	NUMBER (22, 0)	This number represents the count of Driving While intoxicated (DWI) and/or Driving Under the influence (DUI) violations charged against the driver's driving record.
Datamart	CA_DRV_DIM	CA_DRV_GENDER	Commercial Auto Driver Gender	VARCHAR2(60)	This value represents the gender (male or female) of the driver.
Datamart	CA_DRV_DIM	CA_DRV_GOVT_ID_NUM	Commercial Auto Driver Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the commercial auto driver. For example,.
Datamart	CA_DRV_DIM	CA_DRV_ID	Commercial Auto Driver Identifier	NUMBER (22, 0)	The system generated number that identifies the commercial auto driver.
Datamart	CA_DRV_DIM	CA_DRV_INSD_DT_ID	Commercial Auto Driver Insured Date Identifier	DATE	This calendar date represents when insurance coverage began for commercial driver.
Datamart	CA_DRV_DIM	CA_DRV_INTRMDT_VIOLATION_CNT	Commercial Auto Driver Intermediate Violation Count	NUMBER (22, 0)	This number represents the count of intermediate violations charged against the driver's driving record.
Datamart	CA_DRV_DIM	CA_DRV_LIC_DT_ID	Commercial Auto Driver License Date Identifier	DATE	This calendar date represents the driver license date.
Datamart	CA_DRV_DIM	CA_DRV_LIC_ISSUED_BY	Commercial Auto Driver License Issued By	VARCHAR2(60)	This value represents the government entity that issued the commercial drivers license.
Datamart	CA_DRV_DIM	CA_DRV_LIC_STATUS	Commercial Auto Driver License Status	VARCHAR2(60)	This value represents the government-assigned status of driving license privileges.
Datamart	CA_DRV_DIM	CA_DRV_MAJOR_VIOLATION_CNT	Commercial Auto Driver Major Violation Count	NUMBER (22, 0)	This number represents the count of major violations charged against the driver's driving record.
Datamart	CA_DRV_DIM	CA_DRV_MARITAL_STATUS	Commercial Auto Driver Marital Status	VARCHAR2(60)	This value represents the present marital condition (single, married, divorced, widowed) of the commercial auto driver.
Datamart	CA_DRV_DIM	CA_DRV_MINOR_VIOLATION_CNT	Commercial Auto Driver Minor Violation Count	NUMBER (22, 0)	This number represents the count of minor violations charged against the driver's driving record.
Datamart	CA_DRV_DIM	CA_DRV_NAT_KEY	Commercial Auto Driver Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the commercial auto driver.
Datamart	CA_DRV_DIM	CA_DRV_NM	Commercial Auto Driver Name	VARCHAR2(170)	This value represents the full name of commercial auto driver.
Datamart	CA_DRV_DIM	CA_DRV_NUM	Commercial Auto Driver Number	NUMBER (22, 0)	This number identifies the commercial auto driver.
Datamart	CA_DRV_DIM	CA_DRV_PARTY_UDF_1	Commercial Auto Driver Party User Defined Field 1	VARCHAR2(60)	This value describes the first commercial auto driver party user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PARTY_UDF_2	Commercial Auto Driver Party User Defined Field 2	VARCHAR2(60)	This value describes the second commercial auto driver party user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CA_DRV_DIM	CA_DRV_PARTY_UDF_3	Commercial Auto Driver Party User Defined Field 3	VARCHAR2(60)	This value describes the third commercial auto driver party user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PARTY_UDF_4	Commercial Auto Driver Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth commercial auto driver party user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PARTY_UDF_5	Commercial Auto Driver Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth commercial auto driver party user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PERS_UDF_1	Commercial Auto Driver Person User Defined Field 1	VARCHAR2(60)	This value describes the first commercial auto driver person user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PERS_UDF_2	Commercial Auto Driver Person User Defined Field 2	VARCHAR2(60)	This value describes the second commercial auto driver person user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PERS_UDF_3	Commercial Auto Driver Person User Defined Field 3	VARCHAR2(60)	This value describes the third commercial auto driver person user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PERS_UDF_4	Commercial Auto Driver Person User Defined Field 4	VARCHAR2(60)	This value describes the fourth commercial auto driver person user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PERS_UDF_5	Commercial Auto Driver Person User Defined Field 5	VARCHAR2(60)	This value describes the fifth commercial auto driver person user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PRES_EMPLMT_START_YR	Commercial Auto Driver Present Employment Start Year	CHAR(4)	This value represents the calendar year that the commercial auto driver began working for their current employer.
Datamart	CA_DRV_DIM	CA_DRV_RLAT_TO_APPLICANT	Commercial Auto Driver Relationship to Applicant	VARCHAR2(60)	This value represents the relationship of this commercial driver to the applicant.
Datamart	CA_DRV_DIM	CA_DRV_STATUS	Commercial Auto Driver Status	VARCHAR2(60)	This value represents the classification of the driver's coverage to policy coverages.
Datamart	CA_DRV_DIM	CA_DRV_TRNG_DSCNT_FLG	Commercial Auto Driver Training Discount Flag	CHAR(1)	This value represents the yes/no indicator identifying whether or not a driver training discount applies.
Datamart	CA_DRV_DIM	CA_DRV_TRNG_DSCNT_PCT	Commercial Auto Driver Training Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when driver training discount applies.
Datamart	CA_DRV_DIM	CA_DRV_TRNG_FLG	Commercial Auto Driver Training Flag	CHAR(1)	This value represents the yes/no indicator identifying presence or absence of driver training.
Datamart	CA_DRV_DIM	CA_DRV_TYP	Commercial Auto Driver Type	VARCHAR2(60)	This value represents the classification that describes the attributes of a commercial driver.
Datamart	CA_DRV_DIM	CA_DRV_UDF_1	Commercial Auto Driver User Defined Field 1	VARCHAR2(60)	This value describes the first commercial auto driver user defined field.
Datamart	CA_DRV_DIM	CA_DRV_UDF_2	Commercial Auto Driver User Defined Field 2	VARCHAR2(60)	This value describes the second commercial auto driver user defined field.
Datamart	CA_DRV_DIM	CA_DRV_UDF_3	Commercial Auto Driver User Defined Field 3	VARCHAR2(60)	This value describes the third commercial auto driver user defined field.
Datamart	CA_DRV_DIM	CA_DRV_UDF_4	Commercial Auto Driver User Defined Field 4	VARCHAR2(60)	This value describes the fourth commercial auto driver user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CA_DRV_DIM	CA_DRV_UDF_5	Commercial Auto Driver User Defined Field 5	VARCHAR2(60)	This value describes the fifth commercial auto driver user defined field.
Datamart	CA_DRV_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the driver is currently included in policy coverage.
Datamart	CA_DRV_DIM	END_DT	End Date	DATE	This calendar date represents when the commercial driver is no longer included in policy coverages.
Datamart	CA_FACT	CA_DRV_ID	Commercial Auto Driver Identifier	NUMBER (22, 0)	The system generated number that identifies the commercial auto driver instance.
Datamart	CA_FACT	CA_FACT_ID	Commercial Auto Fact Identifier	NUMBER (22, 0)	The system generated number that identifies the commercial vehicle fact instance.
Datamart	CA_FACT	CA_VEH_ID	Commercial Auto VehicleIdentifier	NUMBER (22, 0)	The system generated number that identifies the commercial auto vehicleinstance.
Staging	CA_VEH	ADDL_EQPT_AMT	Additional Equipment Amount	NUMBER (14,3)	This number represents the monetary cost of vehicle alterations or aftermarket custom equipment like custom painting, equipment installed to overcome a physical handicap, etc. installed on a commercial vehicle.
Warehouse	CA_VEH	ADDL_EQPT_AMT	Additional Equipment Amount	NUMBER (14, 3)	This number represents the monetary cost of vehicle alterations or aftermarket custom equipment like custom painting, equipment installed to overcome a physical handicap, etc. installed on a commercial vehicle.
Staging	CA_VEH	AIRBAG_TYP_CD	Airbag Type Code	VARCHAR2(25)	This system code identifies the attributes of airbag system installed.
Warehouse	CA_VEH	AIRBAG_TYP_CD	Airbag Type Code	VARCHAR2(25)	This system code identifies the attributes of airbag system installed.
Warehouse	CA_VEH	AIRBAG_TYP_DESC	Airbag Type Code Description	VARCHAR2(60)	This value describes the airbag type code.
Staging	CA_VEH	ANTI_LOCK_BRAKES_CD	Anti-lock Brake Code	VARCHAR2(25)	This system code identifies the attributes of anti-lock brakes on the commercial vehicle.
Warehouse	CA_VEH	ANTI_LOCK_BRAKES_CD	Anti-lock Brake Code	VARCHAR2(25)	This system code identifies the attributes of anti-lock brakes on the commercial vehicle.
Warehouse	CA_VEH	ANTI_LOCK_BRAKES_DESC	Anti-lock Brake Code Description	VARCHAR2(60)	This value describes the anti-lock brake code.
Staging	CA_VEH	ANTI_THEFT_DEVICE_CD	Anti-Theft Device Code	VARCHAR2(25)	This system code identifies the attributes of vehicle anti-theft device installed on the commercial vehicle.
Warehouse	CA_VEH	ANTI_THEFT_DEVICE_CD	Anti-Theft Device Code	VARCHAR2(25)	This system code identifies the attributes of vehicle anti-theft device installed on the commercial vehicle.
Warehouse	CA_VEH	ANTI_THEFT_DEVICE_DESC	Anti-Theft Device Code Description	VARCHAR2(60)	This value describes the anti-theft device code.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CA_VEH	AUTO_STBLTS_DSCNT_FLG	Automatic Seatbelt Type Code	CHAR(1)	This system code identifies the attributes of automatic seatbelt installed.
Warehouse	CA_VEH	AUTO_STBLTS_DSCNT_FLG	Automatic Seatbelt Type Code	CHAR(1)	This system code identifies the attributes of automatic seatbelt installed.
Staging	CA_VEH	AUTO_STBLTS_DSCNT_PCT	Automatic Seatbelt Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when automatic seatbelt discount applies.
Warehouse	CA_VEH	AUTO_STBLTS_DSCNT_PCT	Automatic Seatbelt Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when automatic seatbelt discount applies.
Warehouse	CA_VEH	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage.
Warehouse	CA_VEH	CA_VEH_ID	Commercial Auto Vehicle Identifier	NUMBER (22, 0)	This system generated number identifies the commercial vehicle instance.
Staging	CA_VEH	CA_VEH_NAT_KEY	Commercial Auto Vehicle Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the commercial vehicle.
Warehouse	CA_VEH	CA_VEH_NAT_KEY	Commercial Auto Vehicle Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the commercial vehicle.
Staging	CA_VEH	CA_VEH_UDF_CD_1	Commercial Auto Vehicle User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first commercial vehicle user defined field.
Warehouse	CA_VEH	CA_VEH_UDF_CD_1	Commercial Auto Vehicle User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first commercial vehicle user defined field.
Staging	CA_VEH	CA_VEH_UDF_CD_2	Commercial Auto Vehicle User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second commercial vehicle user defined field.
Warehouse	CA_VEH	CA_VEH_UDF_CD_2	Commercial Auto Vehicle User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second commercial vehicle user defined field.
Staging	CA_VEH	CA_VEH_UDF_CD_3	Commercial Auto Vehicle User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third commercial vehicle user defined field.
Warehouse	CA_VEH	CA_VEH_UDF_CD_3	Commercial Auto Vehicle User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third commercial vehicle user defined field.
Staging	CA_VEH	CA_VEH_UDF_CD_4	Commercial Auto Vehicle User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth commercial vehicle user defined field.
Warehouse	CA_VEH	CA_VEH_UDF_CD_4	Commercial Auto Vehicle User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth commercial vehicle user defined field.
Staging	CA_VEH	CA_VEH_UDF_CD_5	Commercial Auto Vehicle User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth commercial vehicle user defined field.
Warehouse	CA_VEH	CA_VEH_UDF_CD_5	Commercial Auto Vehicle User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth commercial vehicle user defined field.
Warehouse	CA_VEH	CA_VEH_UDF_DESC_1	Commercial Auto Vehicle User Defined Field Description 1	VARCHAR2(60)	This value describes the first commercial vehicle user defined field.
Warehouse	CA_VEH	CA_VEH_UDF_DESC_2	Commercial Auto Vehicle User Defined Field Description 2	VARCHAR2(60)	This value describes the second commercial vehicle user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CA_VEH	CA_VEH_UDF_DESC_3	Commercial Auto Vehicle User Defined Field Description 3	VARCHAR2(60)	This value describes the third commercial vehicle user defined field.
Warehouse	CA_VEH	CA_VEH_UDF_DESC_4	Commercial Auto Vehicle User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth commercial vehicle user defined field.
Warehouse	CA_VEH	CA_VEH_UDF_DESC_5	Commercial Auto Vehicle User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth commercial vehicle user defined field.
Staging	CA_VEH	CELL_PHONE_TYP_CD	Cellular Phone Type Code	VARCHAR2(25)	This system code identifies the cellular phone type present.
Warehouse	CA_VEH	CELL_PHONE_TYP_CD	Cellular Phone Type Code	VARCHAR2(25)	This system code identifies the cellular phone type present.
Warehouse	CA_VEH	CELL_PHONE_TYP_DESC	Cellular Phone Type Description	VARCHAR2(60)	This value represents the description of the cellular phone type.
Warehouse	CA_VEH	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the commercial vehicle is currently applicable.
Staging	CA_VEH	DAYTIME_RUN_LIGHTS_CD	Daytime Running Lights Code	VARCHAR2(25)	This value represents based on the yes/no indicator that states whether or not a commercial vehicle has daytime running headlights.
Warehouse	CA_VEH	DAYTIME_RUN_LIGHTS_CD	Daytime Running Lights Code	VARCHAR2(25)	This value represents based on the yes/no indicator that states whether or not a commercial vehicle has daytime running headlights.
Warehouse	CA_VEH	DAYTIME_RUN_LIGHTS_DESC	Daytime Running Lights Description	VARCHAR2(60)	This value describes the daytime running headlights of a commercial vehicle.
Warehouse	CA_VEH	END_DT	End Date	DATE	This calendar date represents when the commercial vehicle is no longer included in policy coverages.
Staging	CA_VEH	EST_ANNU_DRVG_DIST	Estimated Annual Driving Distance	NUMBER (22,0)	This number represents the estimated number of distance units (miles/kilometers) a vehicle is driven over a one year period.
Warehouse	CA_VEH	EST_ANNU_DRVG_DIST	Estimated Annual Driving Distance	NUMBER (22, 0)	This number represents the estimated number of distance units (miles/kilometers) a vehicle is driven over a one year period.
Warehouse	CA_VEH	FLEET_FLG	Fleet Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a fleet.
Staging	CA_VEH	GAR_CD	Garaging Code	VARCHAR2(25)	This system code identifies where the commercial vehicle is parked at night.
Warehouse	CA_VEH	GAR_CD	Garaging Code	VARCHAR2(25)	This system code identifies where the commercial vehicle is parked at night.
Warehouse	CA_VEH	GAR_DESC	Garaging Description	VARCHAR2(60)	This value describes where a commercial vehicle is parked at night.
Warehouse	CA_VEH	GAR_LOC_ADDR_ID	Garaging Location Address Identifier	NUMBER (22, 0)	This system generated number identifies the garaging location address instance.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CA_VEH	HIRED_FLG	Hired Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of vehicle usage as a hired vehicle.
Staging	CA_VEH	HP_DSPLCMNT	Horsepower Displacement	VARCHAR2(5)	This value represents represents the cubic centimeters or displacement (for example, motorcycles) or horsepower for recreational vehicles.
Warehouse	CA_VEH	HP_DSPLCMNT	Horsepower Displacement	VARCHAR2(5)	This value represents the cubic centimeters or displacement (for example, motorcycles) or horsepower for recreational vehicles.
Staging	CA_VEH	INSD_DT	Insured Date	DATE	This calendar date represents when insurance coverage began for commercial vehicle.
Warehouse	CA_VEH	INSD_DT	Insured Date	DATE	This calendar date represents when insurance coverage began for commercial vehicle.
Staging	CA_VEH	LEASE_DT	Commercial Auto Vehicle Lease Date	DATE	This calendar date represents when a commercial vehicle was leased by insured.
Warehouse	CA_VEH	LEASE_DT	Commercial Auto Vehicle Lease Date	DATE	This calendar date represents when a commercial vehicle was leased by insured.
Staging	CA_VEH	MSRP	Manufacturer Suggested Retail Price	NUMBER (14,3)	This number represents the price that the manufacturer tells the vehicle dealer the new vehicle is worth.
Warehouse	CA_VEH	MSRP	Manufacturer Suggested Retail Price	NUMBER (14, 3)	This number represents the price that the manufacturer tells the vehicle dealer the new vehicle is worth.
Staging	CA_VEH	MULT_CAR_DSCNT_FLG	Multiple Car Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a multiple car discount applies.
Warehouse	CA_VEH	MULT_CAR_DSCNT_FLG	Multiple Car Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a multiple car discount applies.
Staging	CA_VEH	MULT_CAR_DSCNT_PCT	Multiple Car Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when a multiple car discount applies.
Warehouse	CA_VEH	MULT_CAR_DSCNT_PCT	Multiple Car Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when a multiple car discount applies.
Staging	CA_VEH	NEW_OR_USED_CD	New Or Used Code	VARCHAR2(25)	This system code identifies if the insured is the original owner of the insured vehicle.
Warehouse	CA_VEH	NEW_OR_USED_CD	New Or Used Code	VARCHAR2(25)	This system code identifies if the insured is the original owner of the insured vehicle.
Warehouse	CA_VEH	NEW_OR_USED_DESC	New or Used Description	VARCHAR2(60)	This value describes new or used code.
Staging	CA_VEH	OWNRSHP_TYP_CD	Ownership Type Code	VARCHAR2(25)	This system code describes the ownership type of a vehicle standard code.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CA_VEH	OWNRSHP_TYP_CD	Ownership Type Code	VARCHAR2(25)	This system code describes the ownership type of a vehicle standard code.
Warehouse	CA_VEH	OWNRSHP_TYP_DESC	Ownership Type Description	VARCHAR2(60)	This value represents the classification that describes how a commercial vehicle is owned and titled.
Warehouse	CA_VEH	PSNL_USE_FLG	Personal Use Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the vehicle usage is personal use.
Staging	CA_VEH	PURCH_DT	Purchase Date	DATE	This date represents the calendar date the insured purchased the commercial vehicle.
Warehouse	CA_VEH	PURCH_DT	Purchase Date	DATE	This date represents the calendar date commercial vehicle was purchased by insured.
Staging	CA_VEH	PURCH_PRICE	Purchase Price	NUMBER (14,3)	This number represents the monetary amount paid when the commercial vehicle was purchased.
Warehouse	CA_VEH	PURCH_PRICE	Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when commercial vehicle was purchased.
Staging	CA_VEH	RATING_AGE_CD	Rating Age Code	VARCHAR2(25)	This system code represents the rating age used to rate the vehicle, regardless of its actual age.
Warehouse	CA_VEH	RATING_AGE_CD	Rating Age Code	VARCHAR2(25)	This system code represents the rating age used to rate the vehicle, regardless of its actual age.
Warehouse	CA_VEH	RATING_AGE_DESC	Rating Age Description	VARCHAR2(60)	This value describes rating age.
Staging	CA_VEH	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the commercial vehicle with a specific transaction.
Staging	CA_VEH	STATED_AMT	Stated Amount	NUMBER (14,3)	This number represents the monetary cost used to rate and value a vehicle when a symbol is not available or useful.
Warehouse	CA_VEH	STATED_AMT	Stated Amount	NUMBER (14, 3)	This number represents the amount used to rate and value a vehicle when a symbol is not available or useful.
Warehouse	CA_VEH	TRAILER_LIQ_CAP	Trailer Liquid Capacity	NUMBER (14, 3)	This number represents the volume capacity of a trailer designed to carry liquids.
Staging	CA_VEH	VEH_BODY_TYP_CD	Vehicle Body Type Code	VARCHAR2(25)	This system code describes the attributes of vehicle body for a scheduled commercial vehicle.
Warehouse	CA_VEH	VEH_BODY_TYP_CD	Vehicle Body Type Code	VARCHAR2(25)	This system code describes the attributes of vehicle body for a scheduled commercial vehicle.
Warehouse	CA_VEH	VEH_BODY_TYP_DESC	Vehicle Body Type Description	VARCHAR2(60)	This value represents the description of the vehicle body type.
Staging	CA_VEH	VEH_CLASS_CD	Vehicle Class Code	VARCHAR2(25)	This value represents the classification that describes vehicle size and body type.
Warehouse	CA_VEH	VEH_CLASS_CD	Vehicle Class Code	VARCHAR2(25)	This value represents the classification that describes vehicle size and body type.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CA_VEH	VEH_CLASS_DESC	Vehicle Class Description	VARCHAR2(60)	This value describes the vehicle class.
Staging	CA_VEH	VEH_COST_NEW	Vehicle Cost New	NUMBER (14,3)	This number represents the monetary price of vehicle when purchased as a new vehicle.
Warehouse	CA_VEH	VEH_COST_NEW	Vehicle Cost New	NUMBER (14, 3)	This number represents the monetary price of vehicle when purchased as a new vehicle.
Staging	CA_VEH	VEH_CUR_VAL	Vehicle Current Value	NUMBER (14,3)	This number represents the current monetary value of listed commercial vehicle in marketplace.
Warehouse	CA_VEH	VEH_CUR_VAL	Vehicle Current Value	NUMBER (14, 3)	This number represents the current monetary value of listed commercial vehicle in marketplace.
Staging	CA_VEH	VEH_GROSS_WT	Vehicle Gross Weight	NUMBER (14,3)	This number represents the total weight a vehicle is designed to carry and includes the net weight of the vehicle, plus the weight of passengers, fuel, cargo and any additional accessories.
Warehouse	CA_VEH	VEH_GROSS_WT	Vehicle Gross Weight	NUMBER (14, 3)	This number represents the total weight a vehicle is designed to carry and includes the net weight of the vehicle, plus the weight of passengers, fuel, cargo and any additional accessories.
Staging	CA_VEH	VEH_MFR	Vehicle Manufacturer	VARCHAR2(20)	This value represents the name of manufacturer that created the commercial vehicle.
Warehouse	CA_VEH	VEH_MFR	Vehicle Manufacturer	VARCHAR2(20)	This value represents the name of manufacturer that created the commercial vehicle.
Staging	CA_VEH	VEH_MODEL	Vehicle Model	VARCHAR2(20)	This value represents the model name assigned by manufacturer of commercial vehicle.
Warehouse	CA_VEH	VEH_MODEL	Vehicle Model	VARCHAR2(20)	This value represents the model name assigned by manufacturer of commercial vehicle.
Staging	CA_VEH	VEH_NUM	Vehicle Number	NUMBER (22,0)	This number is the system assigned number that identifies the commercial vehicle.
Warehouse	CA_VEH	VEH_NUM	Vehicle Number	NUMBER (22, 0)	This number is the system assigned number that identifies the commercial vehicle.
Staging	CA_VEH	VEH_PERF_CD	Vehicle Performance Code	VARCHAR2(25)	This system code identifies the performance level of the vehicle.
Warehouse	CA_VEH	VEH_PERF_CD	Vehicle Performance Code	VARCHAR2(25)	This system code identifies the performance level of the vehicle.
Warehouse	CA_VEH	VEH_PERF_DESC	Vehicle Performance Description	VARCHAR2(60)	This value describes the performance level of the vehicle.
Staging	CA_VEH	VEH_SYM_CD	Vehicle Symbol Code	VARCHAR2(25)	This system code is a cost symbol that represents a value.
Warehouse	CA_VEH	VEH_SYM_CD	Vehicle Symbol Code	VARCHAR2(25)	This system code is a cost symbol that represents a value.
Warehouse	CA_VEH	VEH_SYM_DESC	Vehicle Symbol Description	VARCHAR2(60)	This value describes the commercial vehicle symbol.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CA_VEH	VEH_USE_CD	Vehicle Use Code	VARCHAR2(25)	This system code identifies the primary use of the vehicle.
Warehouse	CA_VEH	VEH_USE_CD	Vehicle Use Code	VARCHAR2(25)	This system code identifies the primary use of the vehicle.
Warehouse	CA_VEH	VEH_USE_DESC	Vehicle Use Description	VARCHAR2(60)	This value describes the primary use of the vehicle.
Staging	CA_VEH	VEH_YR	Vehicle Year	CHAR(4)	This value represents the model year assigned by vehicle manufacturer.
Warehouse	CA_VEH	VEH_YR	Vehicle Year	CHAR(4)	This value represents the model year assigned by vehicle manufacturer.
Staging	CA_VEH	VIN	Vehicle Identification Number	VARCHAR2(25)	This value represents the vehicle identification number assigned by the manufacturer of the commercial vehicle at risk.
Warehouse	CA_VEH	VIN	Vehicle Identification Number	VARCHAR2(25)	This value represents the vehicle identification number assigned by the manufacturer of the commercial vehicle at risk.
Datamart	CA_VEH_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage.
Datamart	CA_VEH_DIM	CA_VEH_ADDL_EQPT_AMT	Commercial Auto Vehicle Additional Equipment Amount	NUMBER (14, 3)	This number represents the monetary cost of commercial vehicle alterations or aftermarket custom equipment like custom painting, equipment installed to overcome a physical handicap, etc.
Datamart	CA_VEH_DIM	CA_VEH_AIRBAG_TYP	Commercial Auto Vehicle Airbag Type	VARCHAR2(60)	This value represents the classification of the airbag system installed in commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_ANTI_LOCK_BRAKES_CD	Commercial Auto Vehicle Anti-Lock Brakes Code	VARCHAR2(60)	This system code describes the anti-theft system present on commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_ANTI_THEFT_DEVICE_CD	Commercial Auto Vehicle Anti-Lock Brakes Code	VARCHAR2(60)	This system code describes the anti-lock brakes present on commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_AUTO_STBLTS_DSCNT_FLG	Commercial Auto Vehicle Automatic Seatbelts Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying presence or absence of automatic seatbelts discount.
Datamart	CA_VEH_DIM	CA_VEH_AUTO_STBLTS_DSCNT_PCT	Commercial Auto Vehicle Automatic Seatbelts Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when automatic seatbelt discount applies.
Datamart	CA_VEH_DIM	CA_VEH_BODY_TYP	Commercial Auto Vehicle Body Type	VARCHAR2(60)	This value represents the classification of the characteristics of a commercial vehicle body.
Datamart	CA_VEH_DIM	CA_VEH_CELL_PHONE_TYP	Commercial Auto Vehicle Cellular Phone Type	VARCHAR2(60)	This system code identifies the cellular phone attributes present in vehicle.
Datamart	CA_VEH_DIM	CA_VEH_CLASS	Commercial Auto Vehicle Class	VARCHAR2(60)	This value represents the classification that describes vehicle size and body type.
Datamart	CA_VEH_DIM	CA_VEH_COST_NEW	Commercial Auto Vehicle Cost New	NUMBER (14, 3)	This number represents the monetary price of vehicle when purchased as a new vehicle.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CA_VEH_DIM	CA_VEH_CUR_VAL	Commercial Auto Vehicle Current Value	NUMBER (14, 3)	This number represents the current monetary value of commercial vehicle in marketplace.
Datamart	CA_VEH_DIM	CA_VEH_DAYTIME_RUN_LIGHTS_CD	Commercial Auto Vehicle Daytime Running Lamps Code	VARCHAR2(60)	This system code describes the attributes of daytime running lamps present on commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_EST_ANNU_DRVG_DIST	Commercial Auto Vehicle Estimated Annual Driving Distance	NUMBER (22, 0)	This number identifies estimated annual driving distance units (miles/kilometers).
Datamart	CA_VEH_DIM	CA_VEH_GAR_CD	Commercial Auto Vehicle Garaging Code	VARCHAR2(60)	This system code describes the manner a vehicle is stored at garaging location.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_CNTY	Commercial Auto Vehicle Garaging Location County	VARCHAR2(60)	This value identifies the county where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_CTRY	Commercial Auto Vehicle Garaging Location Country	VARCHAR2(60)	This value identifies the country where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_CTY	Commercial Auto Vehicle Garaging Location City	VARCHAR2(32)	This value identifies the city where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_DSTRCT	Commercial Auto Vehicle Garaging Location District	VARCHAR2(60)	This value represents the district where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_LATITUDE	Commercial Auto Vehicle Garaging Location Latitude	VARCHAR2(11)	This value represents the district where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_LONGITUDE	Commercial Auto Vehicle Garaging Location Longitude	VARCHAR2(11)	This value represents the longitude location of where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_PSTL_CD	Commercial Auto Vehicle Garaging Location Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_PSTL_CD_PRFX	Commercial Auto Vehicle Garaging Location Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_PSTL_SUB_CD	Commercial Auto Vehicle Garaging Location Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies the smaller area of the total area served by a postal code.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_REGION	Commercial Auto Vehicle Garaging Location Region	VARCHAR2(60)	This value identifies the geographic region where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_STATE	Commercial Auto Vehicle Garaging Location State	VARCHAR2(60)	This value identifies the state where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_TAX_LOC_ID	Commercial Auto Vehicle Garaging Location Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier of the location where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_TERR	Commercial Auto Vehicle Garaging Location Territory	VARCHAR2(60)	This value represents the territory where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GEOG_BNDRY_UDF_1	Commercial Auto Vehicle Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first commercial vehicle geographic boundary user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CA_VEH_DIM	CA_VEH_GEOG_BNDRY_UDF_2	Commercial Auto Vehicle Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second commercial vehicle geographic boundary user defined field.
Datamart	CA_VEH_DIM	CA_VEH_GEOG_BNDRY_UDF_3	Commercial Auto Vehicle Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third commercial vehicle geographic boundary user defined field.
Datamart	CA_VEH_DIM	CA_VEH_GEOG_BNDRY_UDF_4	Commercial Auto Vehicle Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth commercial vehicle geographic boundary user defined field.
Datamart	CA_VEH_DIM	CA_VEH_GEOG_BNDRY_UDF_5	Commercial Auto Vehicle Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth commercial vehicle geographic boundary user defined field.
Datamart	CA_VEH_DIM	CA_VEH_GROSS_WT	Commercial Auto Vehicle Gross Weight	NUMBER (14, 3)	This number represents the total weight a vehicle is designed to carry and includes the net weight of the vehicle, plus the weight of passengers, fuel, cargo and any additional accessories.
Datamart	CA_VEH_DIM	CA_VEH_HP_DSPLCMNT	Commercial Auto Vehicle Horsepower Displacement	VARCHAR2(5)	This value represents the cubic centimeters or displacement for a commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_ID	Commercial Auto Vehicle Identifier	NUMBER (22, 0)	This system generated number identifies the commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_INSD_DT_ID	Commercial Auto Vehicle Insured Date Identifier	DATE	This calendar date represents when insurance coverage began for commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_LEASE_DT_ID	Commercial Auto Vehicle Lease Date Identifier	DATE	This date identifies the calendar date when a commercial vehicle was leased by insured.
Datamart	CA_VEH_DIM	CA_VEH_MFR	Commercial Auto Vehicle Manufacturer	VARCHAR2(20)	This value represents the name of manufacturer that created the commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_MODEL	Commercial Auto Vehicle Model	VARCHAR2(20)	This value represents the model name assigned by the manufacturer of commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_MSRP	Commercial Auto Vehicle Manufacturer's Suggested Retail Price	NUMBER (14, 3)	This number represents the price that the manufacturer tells the vehicle dealer the new vehicle is worth.
Datamart	CA_VEH_DIM	CA_VEH_MULT_CAR_DSCNT_FLG	Commercial Auto Vehicle Multiple Car Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a multiple car discount applies.
Datamart	CA_VEH_DIM	CA_VEH_MULT_CAR_DSCNT_PCT	Commercial Auto Vehicle Multiple Car Discount Percentage	NUMBER (6, 3)	This number represents the percentage of rate waived when multiple car discount applies.
Datamart	CA_VEH_DIM	CA_VEH_NAT_KEY	Commercial Auto Vehicle Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_NEW_OR_USED_CD	Commercial Auto Vehicle New or Used Code	VARCHAR2(60)	This system code identifies if the insured is the original owner of the insured commercial vehicle.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CA_VEH_DIM	CA_VEH_NUM	Commercial Auto Vehicle Number	NUMBER (22, 0)	This number identifies the commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_NUM_DAYS_DRVN_PER_WK	Commercial Auto Vehicle Number of Days Driven Per Week	NUMBER (22, 0)	This number represents the count of days vehicle is driven per calendar week.
Datamart	CA_VEH_DIM	CA_VEH_ONE_WAY_DIST_TO_WRK	Commercial Auto Vehicle One Way Distance To Work	NUMBER (22, 0)	This number represents the number of distance units (miles/kilometers) to place of employment from residence.
Datamart	CA_VEH_DIM	CA_VEH_OWNRSHP_TYP	Commercial Auto Vehicle Ownership Type	VARCHAR2(60)	This value represents the classification that describes how a vehicle is owned and titled.
Datamart	CA_VEH_DIM	CA_VEH_PERF_CD	Commercial Auto Vehicle Performance Code	VARCHAR2(60)	This system code identifies the performance level of the commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_PURCH_DT_ID	Commercial Auto Vehicle Purchase Date Identifier	DATE	This calendar date represents when a commercial vehicle was purchased.
Datamart	CA_VEH_DIM	CA_VEH_PURCH_PRICE	Commercial Auto Vehicle Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when a commercial vehicle was purchased.
Datamart	CA_VEH_DIM	CA_VEH_RATING_AGE	Commercial Auto Vehicle Rating Age	VARCHAR2(60)	This value represents the age used to rate the commercial vehicle, regardless of its actual age.
Datamart	CA_VEH_DIM	CA_VEH_STATED_AMT	Commercial Auto Vehicle Stated Amount	NUMBER (14, 3)	This number represents the amount used to rate and value a commercial vehicle when a symbol is not available or useful.
Datamart	CA_VEH_DIM	CA_VEH_SYM	Commercial Auto Vehicle Symbol	VARCHAR2(60)	This value represents the cost symbol that represents a value.
Datamart	CA_VEH_DIM	CA_VEH_UDF_1	Commercial Auto Vehicle User Defined Field 1	VARCHAR2(60)	This value describes the first commercial vehicle user defined field.
Datamart	CA_VEH_DIM	CA_VEH_UDF_2	Commercial Auto Vehicle User Defined Field 2	VARCHAR2(60)	This value describes the second commercial vehicle user defined field.
Datamart	CA_VEH_DIM	CA_VEH_UDF_3	Commercial Auto Vehicle User Defined Field 3	VARCHAR2(60)	This value describes the third commercial vehicle user defined field.
Datamart	CA_VEH_DIM	CA_VEH_UDF_4	Commercial Auto Vehicle User Defined Field 4	VARCHAR2(60)	This value describes the fourth commercial vehicle user defined field.
Datamart	CA_VEH_DIM	CA_VEH_UDF_5	Commercial Auto Vehicle User Defined Field 5	VARCHAR2(60)	This value describes the fifth commercial vehicle user defined field.
Datamart	CA_VEH_DIM	CA_VEH_USE_CD	Commercial Auto Vehicle Use Code	VARCHAR2(60)	This system code identifies the primary use of the commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_YR	Commercial Auto Vehicle Year	CHAR(4)	This value represents the model year assigned by vehicle manufacturer.
Datamart	CA_VEH_DIM	CA_VIN	Commercial Auto Vehicle Identification Number	VARCHAR2(25)	This value represents the unique identification number assigned by the vehicle's manufacturer.
Datamart	CA_VEH_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the commercial vehicle is currently applicable.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CA_VEH_DIM	END_DT	End Date	DATE	This calendar date represents when the commercial vehicle is no longer included in policy coverages.
Warehouse	CAT	BEGIN_DT	Begin Date	DATE	This calendar date represents when the catastrophe applies.
Staging	CAT	CAT_BEGIN_DT	Catastrophe Begin Date	DATE	This calendar date represents when the catastrophe started.
Warehouse	CAT	CAT_BEGIN_DT	Catastrophe Begin Date	DATE	This calendar date represents when the catastrophe started.
Staging	CAT	CAT_CD	Catastrophe Code	VARCHAR2(25)	This system code identifies a catastrophe. This is the number or other identifier assigned by the company.
Warehouse	CAT	CAT_CD	Catastrophe Code	VARCHAR2(25)	This system code identifies a catastrophe. This is the number or other identifier assigned by the company.
Warehouse	CAT	CAT_DESC	Catastrophe Description	VARCHAR2(60)	This value describes a catastrophe. This is the name assigned by the company.
Staging	CAT	CAT_END_DT	Catastrophe Ending Date	DATE	This calendar date represents when a catastrophe ended.
Warehouse	CAT	CAT_END_DT	Catastrophe Ending Date	DATE	This calendar date represents when a catastrophe ended.
Warehouse	CAT	CAT_ID	Catastrophe Identifier	NUMBER (22, 0)	This system generated number identifies the catastrophe instance.
Staging	CAT	CAT_NAT_CD	Catastrophe National Code	VARCHAR2(25)	This system code identifies the national catastrophe occurrence.
Warehouse	CAT	CAT_NAT_CD	Catastrophe National Code	VARCHAR2(25)	This system code identifies the national catastrophe occurrence.
Warehouse	CAT	CAT_NAT_DESC	Catastrophe National Description	VARCHAR2(60)	This value describes the catastrophe national code.
Staging	CAT	CAT_NAT_KEY	Catastrophe Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the catastrophe.
Warehouse	CAT	CAT_NAT_KEY	Catastrophe Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the catastrophe.
Staging	CAT	CAT_SRC_CD	Catastrophe Source Code	VARCHAR2(25)	This system code describes the source of a catastrophe.
Warehouse	CAT	CAT_SRC_CD	Catastrophe Source Code	VARCHAR2(25)	This system code describes the source of a catastrophe.
Warehouse	CAT	CAT_SRC_DESC	Catastrophe Source Description	VARCHAR2(60)	This value describes the catastrophe source code.
Staging	CAT	CAT_STATE_CD	Catastrophe State Code	VARCHAR2(25)	This system code identifies the state where a catastophe occurred.
Warehouse	CAT	CAT_STATE_CD	Catastrophe State Code	VARCHAR2(25)	This system code identifies the state where a catastophe occurred.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CAT	CAT_STATE_DESC	Catastrophe State Description	VARCHAR2(60)	This value identifies the state name of the catastrophe state.
Staging	CAT	CAT_UDF_CD_1	Catastrophe User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first catastrophe user defined field.
Warehouse	CAT	CAT_UDF_CD_1	Catastrophe User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first catastrophe user defined field.
Staging	CAT	CAT_UDF_CD_2	Catastrophe User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second catastrophe user defined field.
Warehouse	CAT	CAT_UDF_CD_2	Catastrophe User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second catastrophe user defined field.
Staging	CAT	CAT_UDF_CD_3	Catastrophe User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third catastrophe user defined field.
Warehouse	CAT	CAT_UDF_CD_3	Catastrophe User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third catastrophe user defined field.
Staging	CAT	CAT_UDF_CD_4	Catastrophe User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth catastrophe user defined field.
Warehouse	CAT	CAT_UDF_CD_4	Catastrophe User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth catastrophe user defined field.
Staging	CAT	CAT_UDF_CD_5	Catastrophe User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth catastrophe user defined field.
Warehouse	CAT	CAT_UDF_CD_5	Catastrophe User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth catastrophe user defined field.
Warehouse	CAT	CAT_UDF_DESC_1	Catastrophe User Defined Field Description 1	VARCHAR2(60)	This value describes the first catastrophe user defined field.
Warehouse	CAT	CAT_UDF_DESC_2	Catastrophe User Defined Field Description 2	VARCHAR2(60)	This value describes the second catastrophe user defined field.
Warehouse	CAT	CAT_UDF_DESC_3	Catastrophe User Defined Field Description 3	VARCHAR2(60)	This value describes the third catastrophe user defined field.
Warehouse	CAT	CAT_UDF_DESC_4	Catastrophe User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth catastrophe user defined field.
Warehouse	CAT	CAT_UDF_DESC_5	Catastrophe User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth catastrophe user defined field.
Warehouse	CAT	CUR_FLG	Current Flag	CHAR(1)	This value based on the yes/no indicator identifying if the catastophe is currently applicable.
Warehouse	CAT	END_DT	End Date	DATE	This calendar date represents when the catastrophe is no longer valid.
Staging	CAT	EXCESS_CAT_CD	Excess Catastrophe Code	VARCHAR2(25)	This system code indicates that a catastrophe loss is in excess of a policyholders' retention.
Warehouse	CAT	EXCESS_CAT_CD	Excess Catastrophe Code	VARCHAR2(25)	This system code indicates that a catastrophe loss is in excess of a policyholders' retention.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CAT	EXCESS_CAT_DESC	Excess Catastrophe Description	VARCHAR2(60)	This value describes the code to indicate that a catastrophe loss is in excess of policyholders' retention.
Staging	CAT	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the catastrophe with a specific transaction.
Datamart	CAT_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the catastrophe started.
Datamart	CAT_DIM	CAT_BEGIN_DT_ID	Catastrophe Begin Date Identifier	DATE	This calendar date that identifies the catastrophe begin date instance.
Datamart	CAT_DIM	CAT_CD	Catastrophe Code	VARCHAR2(60)	This system code identifies a catastrophe. This is the number or other identifier assigned by the company.
Datamart	CAT_DIM	CAT_END_DT_ID	Catastrophe Ending Date Identifier	DATE	This calendar date identifies the catastrophe end date.
Datamart	CAT_DIM	CAT_ID	Catastrophe Identifier	NUMBER (22, 0)	This system generated number identifies the catastrophe instance.
Datamart	CAT_DIM	CAT_NAT_CD	Catastrophe National Code	VARCHAR2(60)	This system code identifies the national catastrophe occurrence.
Datamart	CAT_DIM	CAT_NAT_KEY	Catastrophe Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the catastrophe.
Datamart	CAT_DIM	CAT_SRC_CD	Catastrophe Source Code	VARCHAR2(60)	This system code describes the source of a catastrophe.
Datamart	CAT_DIM	CAT_STATE	Catastrophe State	VARCHAR2(60)	This value identifies the state where a catastrophe occurred.
Datamart	CAT_DIM	CAT_UDF_1	Catastrophe User Defined Field 1	VARCHAR2(60)	This value describes the first catastrophe user defined field.
Datamart	CAT_DIM	CAT_UDF_2	Catastrophe User Defined Field 2	VARCHAR2(60)	This value describes the second catastrophe user defined field.
Datamart	CAT_DIM	CAT_UDF_3	Catastrophe User Defined Field 3	VARCHAR2(60)	This value describes the third catastrophe user defined field.
Datamart	CAT_DIM	CAT_UDF_4	Catastrophe User Defined Field 4	VARCHAR2(60)	This value describes the fourth catastrophe user defined field.
Datamart	CAT_DIM	CAT_UDF_5	Catastrophe User Defined Field 5	VARCHAR2(60)	This value describes the fifth catastrophe user defined field.
Datamart	CAT_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the catastrophe is currently applicable.
Datamart	CAT_DIM	END_DT	End Date	DATE	This calendar date represents when the catastrophe ended.
Datamart	CAT_DIM	EXCESS_CAT_CD	Excess Catastrophe Code	VARCHAR2(60)	This system code indicates that a catastrophe loss is in excess of policyholders' retention.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLASS	BEGIN_DT	Begin Date	DATE	This calendar date represents when the class applies.
Staging	CLASS	CLASS_CD	Class Code	VARCHAR2(25)	This system code classifies the subject of insurance.
Warehouse	CLASS	CLASS_CD	Class Code	VARCHAR2(25)	This system code classifies the subject of insurance.
Warehouse	CLASS	CLASS_DESC	Class Description	VARCHAR2(60)	This value represents the description of the characteristics of a subject of insurance.
Warehouse	CLASS	CLASS_ID	Class Identifier	NUMBER (22, 0)	This system generated number identifies the class.
Staging	CLASS	CLASS_NAT_KEY	Class Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the class.
Warehouse	CLASS	CLASS_NAT_KEY	Class Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the class.
Staging	CLASS	CLASS_STATE_CD	Class State Code	VARCHAR2(25)	This system code abbreviates the class state.
Warehouse	CLASS	CLASS_STATE_CD	Class State Code	VARCHAR2(25)	This system code abbreviates the class state.
Warehouse	CLASS	CLASS_STATE_DESC	Class State Description	VARCHAR2(60)	This value represents the name of the class state.
Staging	CLASS	CLASS_UDF_CD_1	Class User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first class user defined field.
Warehouse	CLASS	CLASS_UDF_CD_1	Class User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first class user defined field.
Staging	CLASS	CLASS_UDF_CD_2	Class User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second class user defined field.
Warehouse	CLASS	CLASS_UDF_CD_2	Class User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second class user defined field.
Staging	CLASS	CLASS_UDF_CD_3	Class User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third class user defined field.
Warehouse	CLASS	CLASS_UDF_CD_3	Class User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third class user defined field.
Staging	CLASS	CLASS_UDF_CD_4	Class User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth class user defined field.
Warehouse	CLASS	CLASS_UDF_CD_4	Class User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth class user defined field.
Staging	CLASS	CLASS_UDF_CD_5	Class User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth class user defined field.
Warehouse	CLASS	CLASS_UDF_CD_5	Class User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth class user defined field.
Warehouse	CLASS	CLASS_UDF_DESC_1	Class User Defined Field Description 1	VARCHAR2(60)	This value describes the first class user defined field.
Warehouse	CLASS	CLASS_UDF_DESC_2	Class User Defined Field Description 2	VARCHAR2(60)	This value describes the second class user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLASS	CLASS_UDF_DESC_3	Class User Defined Field Description 3	VARCHAR2(60)	This value describes the third class user defined field.
Warehouse	CLASS	CLASS_UDF_DESC_4	Class User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth class user defined field.
Warehouse	CLASS	CLASS_UDF_DESC_5	Class User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth class user defined field.
Warehouse	CLASS	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the class is currently applicable.
Warehouse	CLASS	END_DT	End Date	DATE	This calendar date represents when the class is no longer valid.
Staging	CLASS	PRIM_CLASS_CD	Primary Class Code	VARCHAR2(25)	In a situation where the class code is split into more than one useful breakout, this value represents the primary portion.
Warehouse	CLASS	PRIM_CLASS_CD	Primary Class Description	VARCHAR2(25)	This value represents the description of the primary class.
Warehouse	CLASS	PRIM_CLASS_DESC	Primary Class Code	VARCHAR2(60)	In a situation where the class code is split into more than one useful breakout, this value represents the primary portion.
Staging	CLASS	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the class with a specific transaction.
Staging	CLASS	SCND_CLASS_CD	Second Class Code	VARCHAR2(25)	In a situation where the class code is split into more than one useful breakout, this value represents is the secondary portion.
Warehouse	CLASS	SCND_CLASS_CD	Second Class Code	VARCHAR2(25)	In a situation where the class code is split into more than one useful breakout, this value represents is the secondary portion.
Warehouse	CLASS	SCND_CLASS_DESC	Second Class Description	VARCHAR2(60)	This value represents the description of the secondary class.
Datamart	CLASS_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the class applies.
Datamart	CLASS_DIM	CLASS_CD	Class Code	VARCHAR2(60)	This system code classifies the subject of insurance.
Datamart	CLASS_DIM	CLASS_ID	Class Identifier	NUMBER (22, 0)	This system generated number identifies the class instance.
Datamart	CLASS_DIM	CLASS_NAT_KEY	Class Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the class.
Datamart	CLASS_DIM	CLASS_STATE	Class State	VARCHAR2(60)	This value identifies the state associated with the class.
Datamart	CLASS_DIM	CLASS_UDF_1	Class User Defined Field 1	VARCHAR2(60)	This value describes the first class user defined field.
Datamart	CLASS_DIM	CLASS_UDF_2	Class User Defined Field 2	VARCHAR2(60)	This value describes the second class user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLASS_DIM	CLASS_UDF_3	Class User Defined Field 3	VARCHAR2(60)	This value describes the third class user defined field.
Datamart	CLASS_DIM	CLASS_UDF_4	Class User Defined Field 4	VARCHAR2(60)	This value describes the fourth class user defined field.
Datamart	CLASS_DIM	CLASS_UDF_5	Class User Defined Field 5	VARCHAR2(60)	This value describes the fifth class user defined field.
Datamart	CLASS_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the class is currently applicable.
Datamart	CLASS_DIM	END_DT	End Date	DATE	This calendar date represents when the class is no longer valid.
Datamart	CLASS_DIM	PRIM_CLASS_CD	Primary Class Code	VARCHAR2(60)	In a situation where the class code is split into more than one useful breakout, this value represents the primary portion.
Datamart	CLASS_DIM	SCND_CLASS_CD	Second Class Code	VARCHAR2(60)	In a situation where the class code is split into more than one useful breakout, this value represents the secondary portion.
Warehouse	CLM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim occurred.
Staging	CLM	CASE_MADE_RETROACTIVE_DT	Case Made Retroactive Date	DATE	This calendar date represenets when the claim case was made retroactive.
Warehouse	CLM	CASE_MADE_RETROACTIVE_DT	Case Made Retroactive Date	DATE	This calendar date represenets when the claim case was made retroactive.
Staging	CLM	CASE_MGMT_ASSIGNED_DT	Case Management Assigned Date	DATE	This calendar date represents when claim management is assigned to claim.
Warehouse	CLM	CASE_MGMT_ASSIGNED_DT	Case Management Assigned Date	DATE	This calendar date represents when claim management is assigned to claim.
Staging	CLM	CLM_CLOSED_DT	Claim Closed Date	DATE	This calendar date represents when the insurance company closed the claim.
Warehouse	CLM	CLM_CLOSED_DT	Claim Closed Date	DATE	This calendar date represents when the insurance company closed the claim.
Warehouse	CLM	CLM_ID	Claim Identifier	NUMBER (22, 0)	This system generated number identifies the claim instance.
Staging	CLM	CLM_NAT_KEY	Claim Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claim.
Warehouse	CLM	CLM_NAT_KEY	Claim Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claim.
Staging	CLM	CLM_NUM	Claim Number	VARCHAR2(30)	This number or other unique identifier identifies a claim.
Warehouse	CLM	CLM_NUM	Claim Number	VARCHAR2(30)	This number or other unique identifier identifies a claim.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CLM	CLM_OPENED_DT	Claim Opened Date	DATE	This calendar date represents when a claim was opened by the insurance company.
Warehouse	CLM	CLM_OPENED_DT	Claim Opened Date	DATE	This calendar date represents when a claim was opened by the insurance company.
Staging	CLM	CLM_RECLOSED_DT	Claim Re-Closed Date	DATE	This calendar date represents when a claim was re-closed by the insurance company.
Warehouse	CLM	CLM_RECLOSED_DT	Claim Re-Closed Date	DATE	This calendar date represents when a claim was re-closed by the insurance company.
Staging	CLM	CLM_REOPENED_DT	Claim Re-Opened Date	DATE	This calendar date represents when a closed claim was changed to open status by the insurance company.
Warehouse	CLM	CLM_REOPENED_DT	Claim Re-Opened Date	DATE	This calendar date represents when a closed claim was changed to open status by the insurance company.
Staging	CLM	CLM_RPT_BY_CD	Claim Report By Code	VARCHAR2(25)	This system code indicates the claim reported by source.
Warehouse	CLM	CLM_RPT_BY_CD	Claim Report By Code	VARCHAR2(25)	This system code indicates the claim reported by source.
Warehouse	CLM	CLM_RPT_BY_DESC	Claim Report by Description	VARCHAR2(60)	This value describes the claim reported by entity.
Staging	CLM	CLM_RPT_CLASS_CD	Claim Report Class Code	VARCHAR2(25)	This system code describes the class code report class applicable to the claim, regardless of the class codes on the policy.
Warehouse	CLM	CLM_RPT_CLASS_CD	Claim Report Class Code	VARCHAR2(25)	This system code describes the class code report class applicable to the claim, regardless of the class codes on the policy.
Warehouse	CLM	CLM_RPT_CLASS_DESC	Claim Report Class Description	VARCHAR2(60)	This value describes the class code reported as the one applicable to the claim, regardless of the class codes on the policy.
Staging	CLM	CLM_RPT_DT	Claim Report Date	DATE	This calendar date represents when the claim was reported to the insurance carrier.
Warehouse	CLM	CLM_RPT_DT	Claim Report Date	DATE	This calendar date represents when the claim was reported to the insurance carrier.
Staging	CLM	CLM_STATUS_CD	Claim Status Code	VARCHAR2(25)	This system code describes the claim status.
Warehouse	CLM	CLM_STATUS_CD	Claim Status Code	VARCHAR2(25)	This system code describes the claim status.
Warehouse	CLM	CLM_STATUS_DESC	Claim Status Description	VARCHAR2(60)	This value describes the claim status.
Staging	CLM	CLM_UDF_CD_1	Claim User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim user defined field.
Warehouse	CLM	CLM_UDF_CD_1	Claim User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CLM	CLM_UDF_CD_2	Claim User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim user defined field.
Warehouse	CLM	CLM_UDF_CD_2	Claim User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim user defined field.
Staging	CLM	CLM_UDF_CD_3	Claim User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim user defined field.
Warehouse	CLM	CLM_UDF_CD_3	Claim User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim user defined field.
Staging	CLM	CLM_UDF_CD_4	Claim User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim user defined field.
Warehouse	CLM	CLM_UDF_CD_4	Claim User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim user defined field.
Staging	CLM	CLM_UDF_CD_5	Claim User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim user defined field.
Warehouse	CLM	CLM_UDF_CD_5	Claim User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim user defined field.
Warehouse	CLM	CLM_UDF_DESC_1	Claim User Defined Field Description 1	VARCHAR2(60)	This value describes the first claim user defined field.
Warehouse	CLM	CLM_UDF_DESC_2	Claim User Defined Field Description 2	VARCHAR2(60)	This value describes the second claim user defined field.
Warehouse	CLM	CLM_UDF_DESC_3	Claim User Defined Field Description 3	VARCHAR2(60)	This value describes the third claim user defined field.
Warehouse	CLM	CLM_UDF_DESC_4	Claim User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth claim user defined field.
Warehouse	CLM	CLM_UDF_DESC_5	Claim User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth claim user defined field.
Staging	CLM	CLMS_MADE_BASIS_CD	Claims Made Basis Code	VARCHAR2(25)	This system code identifies whether or not the claims made basis is being used for reporting of claims.
Warehouse	CLM	CLMS_MADE_BASIS_CD	Claims Made Basis Code	VARCHAR2(25)	This system code identifies whether or not the claims made basis is being used for reporting of claims.
Warehouse	CLM	CLMS_MADE_BASIS_DESC	Claims Made Basis Description	VARCHAR2(60)	This value describes the yes/no indicator identifying whether or not the claims made basis is being used for reporting of claims.
Warehouse	CLM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim is currently applicable.
Warehouse	CLM	END_DT	End Date	DATE	This calendar date represents when a loss period ended.
Staging	CLM	FIRST_CLM_CNTCT_DT	First Claim Contact Date	DATE	This calendar date represents when the claimant was first contacted by the insuring company or its representative.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLM	FIRST_CLM_CNTCT_DT	First Claim Contact Date	DATE	This calendar date represents when the claimant was first contacted by the insuring company or its representative.
Staging	CLM	FIRST_CLM_PMT_DT	First Claim Payment Date	DATE	This calendar date represents when the first payment was made on a claim.
Warehouse	CLM	FIRST_CLM_PMT_DT	First Claim Payment Date	DATE	This calendar date represents when the first payment was made on a claim.
Staging	CLM	FRAUD_CLM_CD	Fraud Claim Code	VARCHAR2(25)	This system code indicates potential fraudulent claim based on adjusters' investigation.
Warehouse	CLM	FRAUD_CLM_CD	Fraud Claim Code	VARCHAR2(25)	This system code indicates potential fraudulent claim based on adjusters' investigation.
Warehouse	CLM	FRAUD_CLM_DESC	Fraud Claim Description	VARCHAR2(60)	This value represents the description of potential fraudulent claim based on adjusters' investigation.
Staging	CLM	LAST_CLM_PMT_DT	Last Claim Payment Date	DATE	This calendar date represents when the last claim payment was issued.
Warehouse	CLM	LAST_CLM_PMT_DT	Last Claim Payment Date	DATE	This calendar date represents when the last claim payment was issued.
Staging	CLM	LAST_SALV_PMT_DT	Last Salvage Payment Date	DATE	This calendar date represents when last salvage payment was received.
Warehouse	CLM	LAST_SALV_PMT_DT	Last Salvage Payment Date	DATE	This calendar date represents when the last payment was made associated with salvage.
Staging	CLM	LAST_SUBRO_PMT_DT	Last Subrogation Payment Date	DATE	This calendar date represents when last subrogation payment was received.
Warehouse	CLM	LAST_SUBRO_PMT_DT	Last Subrogation Payment Date	DATE	This calendar date represents when last subrogation payment was received.
Warehouse	CLM	LOC_OF_LOSS_ADDR_ID	Location Of Loss Address Identifier	NUMBER (22, 0)	This system generated number identifies the loss location instance.
Staging	CLM	LOSS_DT	Loss Date	DATE	This calendar date represents when an accident or loss occurred regardless of when the claim was filed.
Warehouse	CLM	LOSS_DT	Loss Date	DATE	This calendar date represents when an accident or loss occurred regardless of when the claim was filed.
Staging	CLM	NUM_RENTAL_DAYS	Number Of Rental Days	NUMBER (22,0)	This number represents the count of days a replacement item is rented.
Warehouse	CLM	NUM_RENTAL_DAYS	Number Of Rental Days	NUMBER (22, 0)	This number represents the count of days a replacement item is rented.
Staging	CLM	NUM_REPAIR_DAYS	Number Of Repair Days	NUMBER (22,0)	This number represents the count of days required to repair an item.
Warehouse	CLM	NUM_REPAIR_DAYS	Number Of Repair Days	NUMBER (22, 0)	This number represents the count of days required to repair an item.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CLM	NUM_STORAGE_DAYS	Number Of Storage Days	NUMBER (22,0)	This number represents the count of days an item is stored.
Warehouse	CLM	NUM_STORAGE_DAYS	Number Of Storage Days	NUMBER (22, 0)	This number represents the count of days an item is stored.
Staging	CLM	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the claim with a specific transaction.
Warehouse	CLM_ADJ	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim adjuster begins employment.
Warehouse	CLM_ADJ	CLM_ADJ_ID	Claim Adjuster Identifier	NUMBER (22, 0)	This system generated number identifies the claim adjuster instance.
Staging	CLM_ADJ	CLM_ADJ_NUM	Claim Adjuster Number	VARCHAR2(25)	This value represents a number or other identifier for an adjuster.
Warehouse	CLM_ADJ	CLM_ADJ_NUM	Claim Adjuster Number	VARCHAR2(25)	This value represents a number or other identifier for an adjuster.
Staging	CLM_ADJ	CLM_ADJ_TYP_CD	Claim Adjuster Type Code	VARCHAR2(25)	This system code identifies the type of adjuster used to support the claim process.
Warehouse	CLM_ADJ	CLM_ADJ_TYP_CD	Claim Adjuster Type Code	VARCHAR2(25)	This system code identifies the type of adjuster used to support the claim process.
Warehouse	CLM_ADJ	CLM_ADJ_TYP_DESC	Claim Adjuster Type Description	VARCHAR2(60)	This value describes the type of adjuster used to support the claim process.
Staging	CLM_ADJ	CLM_ADJ_UDF_CD_1	Claim Adjuster User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim adjuster user defined field.
Warehouse	CLM_ADJ	CLM_ADJ_UDF_CD_1	Claim Adjuster User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim adjuster user defined field.
Staging	CLM_ADJ	CLM_ADJ_UDF_CD_2	Claim Adjuster User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim adjuster user defined field.
Warehouse	CLM_ADJ	CLM_ADJ_UDF_CD_2	Claim Adjuster User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim adjuster user defined field.
Staging	CLM_ADJ	CLM_ADJ_UDF_CD_3	Claim Adjuster User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim adjuster user defined field.
Warehouse	CLM_ADJ	CLM_ADJ_UDF_CD_3	Claim Adjuster User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim adjuster user defined field.
Staging	CLM_ADJ	CLM_ADJ_UDF_CD_4	Claim Adjuster User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim adjuster user defined field.
Warehouse	CLM_ADJ	CLM_ADJ_UDF_CD_4	Claim Adjuster User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim adjuster user defined field.
Staging	CLM_ADJ	CLM_ADJ_UDF_CD_5	Claim Adjuster User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim adjuster user defined field.
Warehouse	CLM_ADJ	CLM_ADJ_UDF_CD_5	Claim Adjuster User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim adjuster user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLM_ADJ	CLM_ADJ_UDF_DESC_1	Claim Adjuster User Defined Field Description 1	VARCHAR2(60)	This value describes the first claim adjuster user defined field.
Warehouse	CLM_ADJ	CLM_ADJ_UDF_DESC_2	Claim Adjuster User Defined Field Description 2	VARCHAR2(60)	This value describes the second claim adjuster user defined field.
Warehouse	CLM_ADJ	CLM_ADJ_UDF_DESC_3	Claim Adjuster User Defined Field Description 3	VARCHAR2(60)	This value describes the third claim adjuster user defined field.
Warehouse	CLM_ADJ	CLM_ADJ_UDF_DESC_4	Claim Adjuster User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth claim adjuster user defined field.
Warehouse	CLM_ADJ	CLM_ADJ_UDF_DESC_5	Claim Adjuster User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth claim adjuster user defined field.
Warehouse	CLM_ADJ	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim adjuster is currently applicable.
Warehouse	CLM_ADJ	END_DT	End Date	DATE	This calendar date represents when the claim adjuster is no longer employed.
Warehouse	CLM_ADJ	ORG_ID	Organization Identifier	NUMBER (22, 0)	This system generated number identifies the claim adjuster organization instance.
Warehouse	CLM_ADJ	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	CLM_ADJ	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person.
Staging	CLM_ADJ	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the claim adjuster with a specific transaction.
Datamart	CLM_ADJ_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim adjuster's employment began.
Datamart	CLM_ADJ_DIM	CLM_ADJ_BIRTH_DT_ID	Claim Adjuster Birth Date Identifier	DATE	This calendar date represents the claim adjuster's date of birth.
Datamart	CLM_ADJ_DIM	CLM_ADJ_BUS_START_DT_ID	Claim Adjuster Business Start Date Identifier	DATE	This calendar date represents when the claim adjuster's business began business activities.
Datamart	CLM_ADJ_DIM	CLM_ADJ_CNTCT_DESC	Claim Adjuster Contact Description	VARCHAR2(60)	This value describes the claim adjuster contact.
Datamart	CLM_ADJ_DIM	CLM_ADJ_CNTCT_TYP	Claim Adjuster Contact Type	VARCHAR2(60)	This value identifies the contact method for claim adjuster.
Datamart	CLM_ADJ_DIM	CLM_ADJ_CNTCT_UDF_1	Claim Adjuster Contact User Defined Field 1	VARCHAR2(60)	This value describes the first claim adjuster contact user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_CNTCT_UDF_2	Claim Adjuster Contact User Defined Field 2	VARCHAR2(60)	This value describes the second claim adjuster contact user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_CNTCT_UDF_3	Claim Adjuster Contact User Defined Field 3	VARCHAR2(60)	This value describes the third claim adjuster contact user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_ADJ_DIM	CLM_ADJ_CNTCT_UDF_4	Claim Adjuster Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim adjuster contact user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_CNTCT_UDF_5	Claim Adjuster Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim adjuster contact user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_CNTY	Claim Adjuster County	VARCHAR2(60)	This value identifies the county of the claim adjuster's location.
Datamart	CLM_ADJ_DIM	CLM_ADJ_CTRY	Claim Adjuster Country	VARCHAR2(60)	This value identifies the country of the claim adjuster's location.
Datamart	CLM_ADJ_DIM	CLM_ADJ_CTY	Claim Adjuster City	VARCHAR2(32)	This value identifies the city of the claim adjuster's location.
Datamart	CLM_ADJ_DIM	CLM_ADJ_DBA	Claim Adjuster Doing Business As	VARCHAR2(170)	This value represents the operational name of the claim adjuster's business.
Datamart	CLM_ADJ_DIM	CLM_ADJ_DSTRCT	Claim Adjuster District	VARCHAR2(60)	The district of the claim adjuster's location.
Datamart	CLM_ADJ_DIM	CLM_ADJ_GENDER	Claim Adjuster Gender	VARCHAR2(60)	This value represents the gender (male or female) of the claim adjuster.
Datamart	CLM_ADJ_DIM	CLM_ADJ_GEOG_BNDRY_UDF_1	Claim Adjuster Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first claim adjuster geographic boundary user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_GEOG_BNDRY_UDF_2	Claim Adjuster Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second claim adjuster geographic boundary user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_GEOG_BNDRY_UDF_3	Claim Adjuster Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third claim adjuster geographic boundary user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_GEOG_BNDRY_UDF_4	Claim Adjuster Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim adjuster geographic boundary user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_GEOG_BNDRY_UDF_5	Claim Adjuster Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim adjuster geographic boundary user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_GOVT_ID_NUM	Claim Adjuster Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the claim adjuster. For example,.
Datamart	CLM_ADJ_DIM	CLM_ADJ_ID	Claim Adjuster Identifier	NUMBER (22, 0)	This system generated number identifies the claims adjuster instance.
Datamart	CLM_ADJ_DIM	CLM_ADJ_LATITUDE	Claim Adjuster Latitude	VARCHAR2(11)	This value represents the latitude location of the claim adjuster's location.
Datamart	CLM_ADJ_DIM	CLM_ADJ_LONGITUDE	Claim Adjuster Longitude	VARCHAR2(11)	This value represents the longitude location of the claim adjuster's location.
Datamart	CLM_ADJ_DIM	CLM_ADJ_MARITAL_STATUS	Claim Adjuster Marital Status	VARCHAR2(60)	This value represents the present marital condition (single, married, divorced, widowed) of the claim adjuster.
Datamart	CLM_ADJ_DIM	CLM_ADJ_NAICS_CD	Claim Adjuster North American Industry Classification System Code	VARCHAR2(60)	This value represents the North America Industry Class (NAICS) code assigned to claim adjuster.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_ADJ_DIM	CLM_ADJ_NAT_KEY	Claim Adjuster Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claim adjuster.
Datamart	CLM_ADJ_DIM	CLM_ADJ_NM	Claim Adjuster Name	VARCHAR2(170)	This value represents the name of claims adjuster.
Datamart	CLM_ADJ_DIM	CLM_ADJ_NOB	Claim Adjuster Nature of Business	VARCHAR2(60)	This value represents the type or category of the business activities done by the claim adjuster.
Datamart	CLM_ADJ_DIM	CLM_ADJ_NUM	Claim Adjuster Number	VARCHAR2(25)	This value represents a number or other identifier for an adjuster.
Datamart	CLM_ADJ_DIM	CLM_ADJ_NUM_EMP	Claim Adjuster Number of Employees	NUMBER (22, 0)	This number represents the count of people employed by claim adjuster.
Datamart	CLM_ADJ_DIM	CLM_ADJ_ORG_UDF_1	Claim Adjuster Organization User Defined Field 1	VARCHAR2(60)	This value describes the first claim adjuster organization user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_ORG_UDF_2	Claim Adjuster Organization User Defined Field 2	VARCHAR2(60)	This value describes the second claim adjuster organization user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_ORG_UDF_3	Claim Adjuster Organization User Defined Field 3	VARCHAR2(60)	This value describes the third claim adjuster organization user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_ORG_UDF_4	Claim Adjuster Organization User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim adjuster organization user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_ORG_UDF_5	Claim Adjuster Organization User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim adjuster organization user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PARTY_UDF_1	Claim Adjuster Party User Defined Field 1	VARCHAR2(60)	This value describes the first claim adjuster party user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PARTY_UDF_2	Claim Adjuster Party User Defined Field 2	VARCHAR2(60)	This value describes the second claim adjuster party user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PARTY_UDF_3	Claim Adjuster Party User Defined Field 3	VARCHAR2(60)	This value describes the third claim adjuster party user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PARTY_UDF_4	Claim Adjuster Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim adjuster party user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PARTY_UDF_5	Claim Adjuster Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim adjuster party user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PERS_UDF_1	Claim Adjuster Person User Defined Field 1	VARCHAR2(60)	This value describes the first claim adjuster person user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PERS_UDF_2	Claim Adjuster Person User Defined Field 2	VARCHAR2(60)	This value describes the second claim adjuster person user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PERS_UDF_3	Claim Adjuster Person User Defined Field 3	VARCHAR2(60)	This value describes the third claim adjuster person user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PERS_UDF_4	Claim Adjuster Person User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim adjuster person user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PERS_UDF_5	Claim Adjuster Person User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim adjuster person user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_ADJ_DIM	CLM_ADJ_PRES_EMPLMT_START_YR	Claim Adjuster Present Employment Start Year	CHAR(4)	This value represents the calendar year that the claim adjuster began working for their current employer.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PSTL_CD	Claim Adjuster Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PSTL_CD_PRFX	Claim Adjuster Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PSTL_SUB_CD	Claim Adjuster Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	CLM_ADJ_DIM	CLM_ADJ_REGION	Claim Adjuster Region	VARCHAR2(60)	This value represents the geographic region of the claim adjuster's location.
Datamart	CLM_ADJ_DIM	CLM_ADJ_SIC_CD	Claim Adjuster Standard Industrial Classification Code	VARCHAR2(60)	This system code is the SIC code assigned to the claim adjuster. The Standard Industrial Classification (SIC) code is an industry code that identifies the classification of business activity.
Datamart	CLM_ADJ_DIM	CLM_ADJ_STATE	Claim Adjuster State	VARCHAR2(60)	This value identifies the state where claim adjuster is located.
Datamart	CLM_ADJ_DIM	CLM_ADJ_TAX_LOC_ID	Claim Adjuster Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier.
Datamart	CLM_ADJ_DIM	CLM_ADJ_TERR	Claim Adjuster Territory	VARCHAR2(60)	This value represents the territory of the claim adjuster's location.
Datamart	CLM_ADJ_DIM	CLM_ADJ_TYP	Claim Adjuster Type	VARCHAR2(60)	This value represents the classification of activities of the adjuster used to support the claim process.
Datamart	CLM_ADJ_DIM	CLM_ADJ_UDF_1	Claim Adjuster User Defined Field 1	VARCHAR2(60)	This value describes the first claim adjuster user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_UDF_2	Claim Adjuster User Defined Field 2	VARCHAR2(60)	This value describes the second claim adjuster user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_UDF_3	Claim Adjuster User Defined Field 3	VARCHAR2(60)	This value describes the third claim adjuster user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_UDF_4	Claim Adjuster User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim adjuster user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_UDF_5	Claim Adjuster User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim adjuster user defined field.
Datamart	CLM_ADJ_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim adjuster is currently applicable.
Datamart	CLM_ADJ_DIM	END_DT	End Date	DATE	This calendar date represents when the claim adjuster's employment ended.
Datamart	CLM_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim loss period began.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_DIM	CASE_MADE_RETROACTIVE_DT_ID	Case Made Retroactive Date Identifier	DATE	This calendar date represents the case made retroactive date.
Datamart	CLM_DIM	CASE_MGMT_ASSIGNED_DT_ID	Case Management Assigned Date Identifier	DATE	This calendar date identifies when the case management was assigned.
Datamart	CLM_DIM	CLM_CLOSED_DT_ID	Claim Closed Date Identifier	DATE	This calendar date represents the claim closed date instance.
Datamart	CLM_DIM	CLM_GEOG_BNDRY_UDF_1	Claim Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first claim geographic boundary user defined field.
Datamart	CLM_DIM	CLM_GEOG_BNDRY_UDF_2	Claim Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second claim geographic boundary user defined field.
Datamart	CLM_DIM	CLM_GEOG_BNDRY_UDF_3	Claim Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third claim geographic boundary user defined field.
Datamart	CLM_DIM	CLM_GEOG_BNDRY_UDF_4	Claim Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim geographic boundary user defined field.
Datamart	CLM_DIM	CLM_GEOG_BNDRY_UDF_5	Claim Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim geographic boundary user defined field.
Datamart	CLM_DIM	CLM_ID	Claim Identifier	NUMBER (22, 0)	This system generated number identifies the claim instance.
Datamart	CLM_DIM	CLM_NAT_KEY	Claim Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claim.
Datamart	CLM_DIM	CLM_NUM	Claim Number	VARCHAR2(30)	This number or other unique identifier identifies a claim.
Datamart	CLM_DIM	CLM_OPENED_DT_ID	Claim Opened Date Identifier	DATE	This calendar date represents when the claim opened date instance.
Datamart	CLM_DIM	CLM_RECLOSED_DT_ID	Claim Re-Closed Date Identifier	DATE	This calendar date represents when the claim re-closed date instance.
Datamart	CLM_DIM	CLM_REOPENED_DT_ID	Claim Re-Opened Date Identifier	DATE	This calendar date represents when the claim re-opened date instance.
Datamart	CLM_DIM	CLM_RPT_BY	Claim Report By	VARCHAR2(60)	This value represents the source of claim report.
Datamart	CLM_DIM	CLM_RPT_CLASS_CD	Claim Report Class Code	VARCHAR2(60)	This system code describes the class code report class applicable to the claim, regardless of the class codes on the policy.
Datamart	CLM_DIM	CLM_RPT_DT_ID	Claim Report Date Identifier	DATE	This calendar date represents the claim reported date instance.
Datamart	CLM_DIM	CLM_STATUS	Claim Status	VARCHAR2(60)	This value represents the process condition of a claim.
Datamart	CLM_DIM	CLM_UDF_1	Claim User Defined Field 1	VARCHAR2(60)	This value describes the first claim user defined field.
Datamart	CLM_DIM	CLM_UDF_2	Claim User Defined Field 2	VARCHAR2(60)	This value describes the second claim user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_DIM	CLM_UDF_3	Claim User Defined Field 3	VARCHAR2(60)	This value describes the third claim user defined field.
Datamart	CLM_DIM	CLM_UDF_4	Claim User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim user defined field.
Datamart	CLM_DIM	CLM_UDF_5	Claim User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim user defined field.
Datamart	CLM_DIM	CLMS_MADE_BASIS_CD	Claims Made Basis Code	VARCHAR2(60)	This system code identifies whether or not the claims made basis is being used for reporting of claims.
Datamart	CLM_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim is currently applicable.
Datamart	CLM_DIM	END_DT	End Date	DATE	This calendar date represents when the claim loss period ended.
Datamart	CLM_DIM	FIRST_CLM_CNTCT_DT_ID	First Claim Contact Date Identifier	DATE	This calendar date represents the first claim contact date instance.
Datamart	CLM_DIM	FIRST_CLM_PMT_DT_ID	First Claim Payment Date Identifier	DATE	This calendar date represents the first claim payment date instance.
Datamart	CLM_DIM	FRAUD_CLM_CD	Fraud Claim Code	VARCHAR2(60)	This system code indicates potential fraudulent claim based on adjusters' investigation.
Datamart	CLM_DIM	LAST_CLM_PMT_DT_ID	Last Claim Payment Date Identifier	DATE	This calendar date represents the last claim payment date instance.
Datamart	CLM_DIM	LAST_SALV_PMT_DT_ID	Last Salvage Payment Date Identifier	DATE	This calendar date represents the last salvage payment date instance.
Datamart	CLM_DIM	LAST_SUBRO_PMT_DT_ID	Last Subrogation Payment Date Identifier	DATE	This calendar date represents the last subrogation payment date instance.
Datamart	CLM_DIM	LOC_OF_LOSS_CNTY	Location Of Loss County	VARCHAR2(60)	This value identifies the county where the loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_CTRY	Location Of Loss Country	VARCHAR2(60)	This value identifies the country where the loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_CTY	Location Of Loss City	VARCHAR2(32)	This value identifies the city where the loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_DSTRCT	Location Of Loss District	VARCHAR2(60)	This value identifies the district where the loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_LATITUDE	Location Of Loss Latitude	VARCHAR2(11)	This value identifies the latitude where the loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_LONGITUDE	Location Of Loss Longitude	VARCHAR2(11)	This value identifies the longitude where the loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_PSTL_CD	Location Of Loss Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	CLM_DIM	LOC_OF_LOSS_PSTL_CD_PRFX	Location Of Loss Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_DIM	LOC_OF_LOSS_PSTL_SUB_CD	Location Of Loss Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code. This is the sub code of the location where the loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_REGION	Location Of Loss Region	VARCHAR2(60)	This value identifies the geographic region where the loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_STATE	Location Of Loss State	VARCHAR2(60)	This value identifies the state where a loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_TAX_LOC_ID	Location Of Loss Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier of the location where a loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_TERR	Location Of Loss Territory	VARCHAR2(60)	This value represents the territory where a loss occurred.
Datamart	CLM_DIM	LOSS_DT_ID	Loss Date Identifier	DATE	This calendar date represents when an accident or loss occurred regardless of when the claim was filed.
Datamart	CLM_DIM	LOSS_TIME_ID	Loss Time Identifier	NUMBER (22, 0)	This system generated number identifies the loss time instance.
Datamart	CLM_DIM	NUM_RENTAL_DAYS	Number Of Rental Days	NUMBER (22, 0)	This number represents the count of days a replacement item is rented.
Datamart	CLM_DIM	NUM_REPAIR_DAYS	Number Of Repair Days	NUMBER (22, 0)	This number represents the count of days required to repair an item.
Datamart	CLM_DIM	NUM_STORAGE_DAYS	Number Of Storage Days	NUMBER (22, 0)	This number represents the count of days an item is stored.
Warehouse	CLM_EXAMR	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim examiner's employment began.
Warehouse	CLM_EXAMR	CLM_EXAMR_ID	Claim Examiner Identifier	NUMBER (22, 0)	This system generated number identifies the claim examiner instance.
Staging	CLM_EXAMR	CLM_EXAMR_NUM	Claim Examiner Number	VARCHAR2(25)	This value represents the number or identifier assigned to the claim examiner.
Warehouse	CLM_EXAMR	CLM_EXAMR_NUM	Claim Examiner Number	VARCHAR2(25)	This value represents the number or identifier assigned to the claim examiner.
Staging	CLM_EXAMR	CLM_EXAMR_TYP_CD	Claim Examiner Type Code	VARCHAR2(25)	This system code describes the activities of the claim examiner.
Warehouse	CLM_EXAMR	CLM_EXAMR_TYP_CD	Claim Examiner Type Code	VARCHAR2(25)	This system code describes the activities of the claim examiner.
Warehouse	CLM_EXAMR	CLM_EXAMR_TYP_DESC	Claim Examiner Type Description	VARCHAR2(60)	This value describes the claim examiner type.
Staging	CLM_EXAMR	CLM_EXAMR_UDF_CD_1	Claim Examiner User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim examiner user defined field.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_CD_1	Claim Examiner User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim examiner user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CLM_EXAMR	CLM_EXAMR_UDF_CD_2	Claim Examiner User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim examiner user defined field.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_CD_2	Claim Examiner User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim examiner user defined field.
Staging	CLM_EXAMR	CLM_EXAMR_UDF_CD_3	Claim Examiner User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim examiner user defined field.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_CD_3	Claim Examiner User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim examiner user defined field.
Staging	CLM_EXAMR	CLM_EXAMR_UDF_CD_4	Claim Examiner User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim examiner user defined field.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_CD_4	Claim Examiner User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim examiner user defined field.
Staging	CLM_EXAMR	CLM_EXAMR_UDF_CD_5	Claim Examiner User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim examiner user defined field.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_CD_5	Claim Examiner User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim examiner user defined field.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_DESC_1	Claim Examiner User Defined Field Description 1	VARCHAR2(60)	This value describes the first claim examiner user defined field.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_DESC_2	Claim Examiner User Defined Field Description 2	VARCHAR2(60)	This value describes the second claim examiner user defined field.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_DESC_3	Claim Examiner User Defined Field Description 3	VARCHAR2(60)	This value describes the third claim examiner user defined field.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_DESC_4	Claim Examiner User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth claim examiner user defined field.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_DESC_5	Claim Examiner User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth claim examiner user defined field.
Warehouse	CLM_EXAMR	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim examiner is currently applicable.
Warehouse	CLM_EXAMR	END_DT	End Date	DATE	This calendar date represents when the claim examiner's employment ends.
Warehouse	CLM_EXAMR	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	CLM_EXAMR	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person.
Staging	CLM_EXAMR	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the claim examiner with a specific transaction.
Datamart	CLM_EXAMR_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim examiner's employment began.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_BIRTH_DT_ID	Claim Examiner Birth Date	DATE	This calendar date represents the claim examiner's date of birth.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CNTCT_DESC	Claim Examiner Contact Description	VARCHAR2(60)	This value describes the claim examiner contact.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CNTCT_TYP	Claim Examiner Contact Type	VARCHAR2(60)	This value represents the contact method.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CNTCT_UDF_1	Claim Examiner Contact User Defined Field 1	VARCHAR2(60)	This value describes the first claim examiner contact user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CNTCT_UDF_2	Claim Examiner Contact User Defined Field 2	VARCHAR2(60)	This value describes the second claim examiner contact user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CNTCT_UDF_3	Claim Examiner Contact User Defined Field 3	VARCHAR2(60)	This value describes the third claim examiner contact user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CNTCT_UDF_4	Claim Examiner Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim examiner contact user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CNTCT_UDF_5	Claim Examiner Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim examiner contact user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CNTY	Claim Examiner County	VARCHAR2(60)	This value identifies the county of the claim examiner's location.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CTRY	Claim Examiner Country	VARCHAR2(60)	This value identifies the country of the claim examiner's location.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CTY	Claim Examiner City	VARCHAR2(32)	This value identifies the city of the claim examiner's location.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_DSTRCT	Claim Examiner District	VARCHAR2(60)	This value represents the district of the claim examiner's location.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_GENDER	Claim Examiner Gender	VARCHAR2(60)	This value represents the gender (male or female) of the claim examiner.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_GEOG_BNDRY_UDF_1	Claim Examiner Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first claim examiner geographic boundary user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_GEOG_BNDRY_UDF_2	Claim Examiner Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second claim examiner geographic boundary user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_GEOG_BNDRY_UDF_3	Claim Examiner Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third claim examiner geographic boundary user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_GEOG_BNDRY_UDF_4	Claim Examiner Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim examiner geographic boundary user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_GEOG_BNDRY_UDF_5	Claim Examiner Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim examiner geographic boundary user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_GOVT_ID_NUM	Claim Examiner Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the claim examiner. For example, in the USA: SSN or FEIN.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_ID	Claim Examiner Identifier	NUMBER (22, 0)	This system generated number identifies the claim examiner instance.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_LATITUDE	Claim Examiner Latitude	VARCHAR2(11)	This value represents the latitude location of the geographic boundary.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_LONGITUDE	Claim Examiner Longitude	VARCHAR2(11)	This value represents the longitude location of the geographic boundary.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_MARITAL_STATUS	Claim Examiner Marital Status	VARCHAR2(60)	The present marital condition (single, married, divorced, widowed) of the claim examiner.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_NAT_KEY	Claim Examiner Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claim examiner.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_NM	Claim Examiner Name	VARCHAR2(170)	This value represents the name of the claim examiner.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_NUM	Claim Examiner Number	VARCHAR2(25)	This value represents the number or identifier assigned to the claim examiner.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PARTY_UDF_1	Claim Examiner Party User Defined Field 1	VARCHAR2(60)	This value describes the first claim examiner party user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PARTY_UDF_2	Claim Examiner Party User Defined Field 2	VARCHAR2(60)	This value describes the second claim examiner party user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PARTY_UDF_3	Claim Examiner Party User Defined Field 3	VARCHAR2(60)	This value describes the third claim examiner party user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PARTY_UDF_4	Claim Examiner Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim examiner party user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PARTY_UDF_5	Claim Examiner Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim examiner party user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PERS_UDF_1	Claim Examiner Person User Defined Field 1	VARCHAR2(60)	This value describes the first claim examiner person user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PERS_UDF_2	Claim Examiner Person User Defined Field 2	VARCHAR2(60)	This value describes the second claim examiner person user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PERS_UDF_3	Claim Examiner Person User Defined Field 3	VARCHAR2(60)	This value describes the third claim examiner person user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PERS_UDF_4	Claim Examiner Person User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim examiner person user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PERS_UDF_5	Claim Examiner Person User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim examiner person user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PRES_EMPLMT_START_YR	Claim Examiner Present Employment Start Year	CHAR(4)	This value represents the calendar year that the claim examiner began working for their current employer.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PSTL_CD	Claim Examiner Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PSTL_CD_PRFX	Claim Examiner Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PSTL_SUB_CD	Claim Examiner Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_REGION	Claim Examiner Region	VARCHAR2(60)	This value represents the geographic region of the claim examiner's location.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_STATE	Claim Examiner State	VARCHAR2(60)	This value identifies the state of the claim examiner's location.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_TAX_LOC_ID	Claim Examiner Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier of the claim examiner's location.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_TERR	Claim Examiner Territory	VARCHAR2(60)	This value represents the territory of the claim examiner's location.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_TYP	Claim Examiner Type	VARCHAR2(60)	This value represents the classification describes claim examiner roles.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_UDF_1	Claim Examiner User Defined Field 1	VARCHAR2(60)	This value describes the first claim examiner user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_UDF_2	Claim Examiner User Defined Field 2	VARCHAR2(60)	This value describes the second claim examiner user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_UDF_3	Claim Examiner User Defined Field 3	VARCHAR2(60)	This value describes the third claim examiner user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_UDF_4	Claim Examiner User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim examiner user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_UDF_5	Claim Examiner User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim examiner user defined field.
Datamart	CLM_EXAMR_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim examiner is currently applicable.
Datamart	CLM_EXAMR_DIM	END_DT	End Date	DATE	This calendar date represents when the claim examiner's employment ended.
Warehouse	CLM_MGR	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim manager's employment began.
Warehouse	CLM_MGR	CLM_MGR_ID	Claim Manager Identifier	NUMBER (22, 0)	This system generated number identifies the claim manager instance.
Staging	CLM_MGR	CLM_MGR_NUM	Claim Manager Number	VARCHAR2(25)	This number or other identifiers identifies claim manager.
Warehouse	CLM_MGR	CLM_MGR_NUM	Claim Manager Number	VARCHAR2(25)	This number or other identifiers identifies claim manager.
Staging	CLM_MGR	CLM_MGR_TYP_CD	Claim Manager Type Code	VARCHAR2(25)	This system code indicates the claim manager type.
Warehouse	CLM_MGR	CLM_MGR_TYP_CD	Claim Manager Type Code	VARCHAR2(25)	This system code indicates the claim manager type.
Warehouse	CLM_MGR	CLM_MGR_TYP_DESC	Claim Manager Type Description	VARCHAR2(60)	This value describes the claim manger type.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CLM_MGR	CLM_MGR_UDF_CD_1	Claim Manager User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim manager user defined field.
Warehouse	CLM_MGR	CLM_MGR_UDF_CD_1	Claim Manager User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim manager user defined field.
Staging	CLM_MGR	CLM_MGR_UDF_CD_2	Claim Manager User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim manager user defined field.
Warehouse	CLM_MGR	CLM_MGR_UDF_CD_2	Claim Manager User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim manager user defined field.
Staging	CLM_MGR	CLM_MGR_UDF_CD_3	Claim Manager User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim manager user defined field.
Warehouse	CLM_MGR	CLM_MGR_UDF_CD_3	Claim Manager User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim manager user defined field.
Staging	CLM_MGR	CLM_MGR_UDF_CD_4	Claim Manager User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim manager user defined field.
Warehouse	CLM_MGR	CLM_MGR_UDF_CD_4	Claim Manager User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim manager user defined field.
Staging	CLM_MGR	CLM_MGR_UDF_CD_5	Claim Manager User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim manager user defined field.
Warehouse	CLM_MGR	CLM_MGR_UDF_CD_5	Claim Manager User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim manager user defined field.
Warehouse	CLM_MGR	CLM_MGR_UDF_DESC_1	Claim Manager User Defined Field Description 1	VARCHAR2(60)	This value describes the first claim manager user defined field.
Warehouse	CLM_MGR	CLM_MGR_UDF_DESC_2	Claim Manager User Defined Field Description 2	VARCHAR2(60)	This value describes the second claim manager user defined field.
Warehouse	CLM_MGR	CLM_MGR_UDF_DESC_3	Claim Manager User Defined Field Description 3	VARCHAR2(60)	This value describes the third claim manager user defined field.
Warehouse	CLM_MGR	CLM_MGR_UDF_DESC_4	Claim Manager User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth claim manager user defined field.
Warehouse	CLM_MGR	CLM_MGR_UDF_DESC_5	Claim Manager User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth claim manager user defined field.
Warehouse	CLM_MGR	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim manager is currently applicable.
Warehouse	CLM_MGR	END_DT	End Date	DATE	This calendar date represents when the claim manager's employment ended.
Warehouse	CLM_MGR	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	CLM_MGR	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person instance.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CLM_MGR	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the claim manager with a specific transaction.
Datamart	CLM_MGR_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim manager's employment began.
Datamart	CLM_MGR_DIM	CLM_MGR_BIRTH_DT_ID	Claim Manager Birth Date Identifier	DATE	This calendar date represents the claim manager's date of birth.
Datamart	CLM_MGR_DIM	CLM_MGR_CNTCT_DESC	Claim Manager Contact Description	VARCHAR2(60)	This value describes the claim manager contact.
Datamart	CLM_MGR_DIM	CLM_MGR_CNTCT_TYP	Claim Manager Contact Type	VARCHAR2(60)	This value represents claim manager's contact type.
Datamart	CLM_MGR_DIM	CLM_MGR_CNTCT_UDF_1	Claim Manager Contact User Defined Field 1	VARCHAR2(60)	This value describes the first claim manager contact user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_CNTCT_UDF_2	Claim Manager Contact User Defined Field 2	VARCHAR2(60)	This value describes the second claim manager contact user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_CNTCT_UDF_3	Claim Manager Contact User Defined Field 3	VARCHAR2(60)	This value describes the third claim manager contact user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_CNTCT_UDF_4	Claim Manager Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim manager contact user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_CNTCT_UDF_5	Claim Manager Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim manager contact user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_CNTY	Claim Manager County	VARCHAR2(60)	This value identifies the county of the claim examiner's location.
Datamart	CLM_MGR_DIM	CLM_MGR_CTRY	Claim Manager Country	VARCHAR2(60)	This value identifies the country of the claim examiner's location.
Datamart	CLM_MGR_DIM	CLM_MGR_CTY	Claim Manager City	VARCHAR2(32)	This value identifies the city of the claim examiner's location.
Datamart	CLM_MGR_DIM	CLM_MGR_DSTRCT	Claim Manager District	VARCHAR2(60)	This value represents the first name of the person.
Datamart	CLM_MGR_DIM	CLM_MGR_GENDER	Claim Manager Gender	VARCHAR2(60)	This value represents the gender (male or female) of the claim manager.
Datamart	CLM_MGR_DIM	CLM_MGR_GEOG_BNDRY_UDF_1	Claim Manager Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first claim manager geographic boundary user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_GEOG_BNDRY_UDF_2	Claim Manager Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second claim manager geographic boundary user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_GEOG_BNDRY_UDF_3	Claim Manager Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third claim manager geographic boundary user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_GEOG_BNDRY_UDF_4	Claim Manager Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim manager geographic boundary user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_GEOG_BNDRY_UDF_5	Claim Manager Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim manager geographic boundary user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MGR_DIM	CLM_MGR_GOVT_ID_NUM	Claim Manager Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the claim manger. For example, in the USA: SSN or FEIN.
Datamart	CLM_MGR_DIM	CLM_MGR_ID	Claim Manager Identifier	NUMBER (22, 0)	This system generated number identifies the claim manager instance.
Datamart	CLM_MGR_DIM	CLM_MGR_LATITUDE	Claim Manager Latitude	VARCHAR2(11)	This value represents the claim manager's latitude location.
Datamart	CLM_MGR_DIM	CLM_MGR_LONGITUDE	Claim Manager Longitude	VARCHAR2(11)	This value represents the claim manager's longitude location.
Datamart	CLM_MGR_DIM	CLM_MGR_MARITAL_STATUS	Claim Manager Marital Status	VARCHAR2(60)	This value represents the claim manager's present marital condition (single, married, divorced, widowed).
Datamart	CLM_MGR_DIM	CLM_MGR_NAT_KEY	Claim Manager Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claim manager.
Datamart	CLM_MGR_DIM	CLM_MGR_NM	Claim Manager Name	VARCHAR2(170)	This value represents the name of the claim manager.
Datamart	CLM_MGR_DIM	CLM_MGR_NUM	Claim Manager Number	VARCHAR2(25)	This number or unique identifier identifies a claim manager.
Datamart	CLM_MGR_DIM	CLM_MGR_PARTY_UDF_1	Claim Manager Party User Defined Field 1	VARCHAR2(60)	This value describes the first claim manager party user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PARTY_UDF_2	Claim Manager Party User Defined Field 2	VARCHAR2(60)	This value describes the second claim manager party user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PARTY_UDF_3	Claim Manager Party User Defined Field 3	VARCHAR2(60)	This value describes the third claim manager party user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PARTY_UDF_4	Claim Manager Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim manager party user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PARTY_UDF_5	Claim Manager Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim manager party user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PERS_UDF_1	Claim Manager Person User Defined Field 1	VARCHAR2(60)	This value describes the first claim manager person user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PERS_UDF_2	Claim Manager Person User Defined Field 2	VARCHAR2(60)	This value describes the second claim manager person user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PERS_UDF_3	Claim Manager Person User Defined Field 3	VARCHAR2(60)	This value describes the third claim manager person user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PERS_UDF_4	Claim Manager Person User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim manager person user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PERS_UDF_5	Claim Manager Person User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim manager person user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PRES_EMPLMT_START_YR	Claim Manager Present Employment Start Year	CHAR(4)	This value represents the calendar year the claim manager began working for their current employer.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MGR_DIM	CLM_MGR_PSTL_CD	Claim Manager Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	CLM_MGR_DIM	CLM_MGR_PSTL_CD_PRFX	Claim Manager Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	CLM_MGR_DIM	CLM_MGR_PSTL_SUB_CD	Claim Manager Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	CLM_MGR_DIM	CLM_MGR_REGION	Claim Manager Region	VARCHAR2(60)	This value represents the geographic region of the claim manager's location.
Datamart	CLM_MGR_DIM	CLM_MGR_STATE	Claim Manager State	VARCHAR2(60)	This value identifies the state where claim manager is located.
Datamart	CLM_MGR_DIM	CLM_MGR_TAX_LOC_ID	Claim Manager Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier.
Datamart	CLM_MGR_DIM	CLM_MGR_TERR	Claim Manager Territory	VARCHAR2(60)	This value represents the territory of the claim manager's location.
Datamart	CLM_MGR_DIM	CLM_MGR_TYP	Claim Manager Type	VARCHAR2(60)	This value represents the classification describes claim manager roles.
Datamart	CLM_MGR_DIM	CLM_MGR_UDF_1	Claim Manager User Defined Field 1	VARCHAR2(60)	This value describes the first claim manager user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_UDF_2	Claim Manager User Defined Field 2	VARCHAR2(60)	This value describes the second claim manager user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_UDF_3	Claim Manager User Defined Field 3	VARCHAR2(60)	This value describes the third claim manager user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_UDF_4	Claim Manager User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim manager user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_UDF_5	Claim Manager User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim manager user defined field.
Datamart	CLM_MGR_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim manager is currently applicable.
Datamart	CLM_MGR_DIM	END_DT	End Date	DATE	This calendar date represents when the claim manager's employment ended.
Datamart	CLM_MTH_SNAP_FACT	BILL_ACCT_ID	Billing Account Identifier	NUMBER (22, 0)	This system generated number identifies the billing account instance.
Datamart	CLM_MTH_SNAP_FACT	CAL_MTH_ID	Calendar Month Identifier	NUMBER (22, 0)	This system generated number identifies the calendar month.
Datamart	CLM_MTH_SNAP_FACT	CAT_ID	Catastrophe Identifier	NUMBER (22, 0)	This system generated number identifies the catastrophe.
Datamart	CLM_MTH_SNAP_FACT	CLASS_ID	Class Identifier	NUMBER (22, 0)	This system generated number identifies the class.
Datamart	CLM_MTH_SNAP_FACT	CLM_ADJ_ID	Claim Adjuster Identifier	NUMBER (22, 0)	This system generated number identifies the adjuster instance.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MTH_SNAP_FACT	CLM_EXAMR_ID	Claim Examiner Identifier	NUMBER (22, 0)	This system generated number identifies the claim examiner instance.
Datamart	CLM_MTH_SNAP_FACT	CLM_ID	Claim Identifier	NUMBER (22, 0)	This system generated number identifies the claim instance.
Datamart	CLM_MTH_SNAP_FACT	CLM_MGR_ID	Claim Manager Identifier	NUMBER (22, 0)	This system generated number identifies the claim manager instance.
Datamart	CLM_MTH_SNAP_FACT	CLM_NAT_KEY	Claim Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claim.
Datamart	CLM_MTH_SNAP_FACT	CLMT_ID	Claimant Identifier	NUMBER (22, 0)	This system generated number identifies the claimant instance.
Datamart	CLM_MTH_SNAP_FACT	CLMT_NAT_KEY	Claimant Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claimant.
Datamart	CLM_MTH_SNAP_FACT	CLOSED_CLM_NAT_KEY	Closed Claim Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the closed claim.
Datamart	CLM_MTH_SNAP_FACT	COVRG_ID	Coverage Identifier	NUMBER (22, 0)	This system generated number identifies coverage instance.
Datamart	CLM_MTH_SNAP_FACT	COVRG_STATUS_ID	Coverage Status Identifier	NUMBER (22, 0)	This system generated number identifies coverage status instance.
Datamart	CLM_MTH_SNAP_FACT	DC_ID	Distribution Channel Identifier	NUMBER (22, 0)	This system generated number identifies the distribution channel instance.
Datamart	CLM_MTH_SNAP_FACT	DED_ID	Deductible Identifier	NUMBER (22, 0)	This system generated number identifies the deductible instance.
Datamart	CLM_MTH_SNAP_FACT	DOC_ALAE_AMT	Document Allocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of document allocated loss adjustment expense amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_ALAE_RSRV_AMT	Document Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of document allocated loss adjustment expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_ALLOC_EXPNS_AO_AMT	Document Allocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the document allocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_CTD_INCRD_AMT	Document Claim to Date Incurred Amount	NUMBER (14, 3)	This number represents the cost of document claims to date incurred amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_CTD_INCRD_WEXPNS_AMT	Document Claim to Date Incurred With Expenses Amount	NUMBER (14, 3)	This number represents the cost of document claims to date increased with expense amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_CURR_CD	Document Currency Code	VARCHAR2(25)	This system code identifies document currency for a claim monthly snapshot fact table.
Datamart	CLM_MTH_SNAP_FACT	DOC_DED_LPMT_AMT	Document Deductible Loss Payment Amount	NUMBER (14, 3)	This number represents the cost of document deductible loss payment amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_DED_LRSRV_CHANGE_AMT	Document Deductible Loss Reserve Change Amount	NUMBER (14, 3)	This number represents the cost of document deductible loss reserve change amount.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MTH_SNAP_FACT	DOC_END_ALAE_RSRV_AMT	Document Ending Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of document ending allocated loss adjustment expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_END_DED_LPMT_RSRV_AMT	Document Ending Deductible Loss Payment Reserve Amount	NUMBER (14, 3)	This number represents the cost of document ending deductible loss payment reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_END_LRSRV_AMT	Document Ending Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of document ending loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_END_SALV_RSRV_AMT	Document Ending Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of document ending salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_END_SUBRO_RSRV_AMT	Document Ending Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of document ending subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_END_ULAE_RSRV_AMT	Document Ending Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of document ending unallocated loss adjustment expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_INCRD_AMT	Document Incurred Amount	NUMBER (14, 3)	This number represents the cost of document incurred amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_INCRD_WEXPNS_AMT	Document Incurred With Expense Amount	NUMBER (14, 3)	This number represents the cost of document incurred with expense amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_LEGAL_FEES_AMT	Document Legal Fees Expense Amount	NUMBER (14, 3)	This number represents the cost of document legal fees amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_LRSRV_AMT	Document Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of document loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_OUT_ADJ_FEES_AMT	Document Outside Adjusting Fees Expense Amount	NUMBER (14, 3)	This number represents the cost of document outside adjustment fees amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_PAID_LOSS_AMT	Document Paid Loss Amount	NUMBER (14, 3)	This number represents the cost of document paid loss amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_SALV_AMT	Document Salvage Amount	NUMBER (14, 3)	This number represents the cost of document salvage amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_SALV_RSRV_AMT	Document Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of document salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_SUBRO_AMT	Document Subrogation Amount	NUMBER (14, 3)	This number represents the cost of document subrogation amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_SUBRO_RSRV_AMT	Document Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of document subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_ULAE_AMT	Document Unallocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of document unallocated loss adjustment expense amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_ULAE_RSRV_AMT	Document Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of document unallocated loss adjustment expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_UNALLOC_EXPNS_AO_AMT	Document Unallocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the cost of document unallocated expense approving official amount.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MTH_SNAP_FACT	FEAT_ID	Feature Identifier	NUMBER (22, 0)	This system generated number identifies the claim feature instance.
Datamart	CLM_MTH_SNAP_FACT	FEAT_STATUS_ID	Feature Status Identifier	NUMBER (22, 0)	This system generated number identifies the claim feature status instance.
Datamart	CLM_MTH_SNAP_FACT	FISCAL_MTH_ID	Fiscal Month Identifier	NUMBER (22, 0)	This number identifies fiscal month.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_ALAE_AMT	Global 1 Allocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of the first global allocated loss adjusting expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_ALAE_RSRV_AMT	Global 1 Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global allocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_ALLOC_EXPNS_AO_AMT	Global 1 Allocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the cost of the first global allocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_CTD_INCRD_AMT	Global 1 Claim to Date Incurred Amount	NUMBER (14, 3)	This number represents the cost of the first global claims to date incurred amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_CTD_INCRD_WEXPNS_AMT	Global 1 Claim to Date Incurred With Expenses Amount	NUMBER (14, 3)	This number represents the cost of the first global claims to date increased with expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_DED_LPMT_AMT	Global 1 Deductible Loss Payment Amount	NUMBER (14, 3)	This number represents the cost of the first global deductible loss payment amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_DED_LRSRV_CHANGE_AMT	Global 1 Deductible Loss Reserve Change Amount	NUMBER (14, 3)	This number represents the cost of the first global deductible loss reserve change amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_END_ALAE_RSRV_AMT	Global 1 Ending Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global end allocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_END_DED_LPMT_RSRV_AMT	Global 1 Ending Deductible Loss Payment Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global end deductible loss payment reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_END_LRSRV_AMT	Global 1 Ending Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global ending loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_END_SALV_RSRV_AMT	Global 1 Ending Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global end salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_END_SUBRO_RSRV_AMT	Global 1 Ending Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global end subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_END_ULAE_RSRV_AMT	Global 1 Ending Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global end unallocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_INCRD_AMT	Global 1 Incurred Amount	NUMBER (14, 3)	This number represents the cost of the first global incurred amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_INCRD_WEXPNS_AMT	Global 1 Incurred With Expenses Amount	NUMBER (14, 3)	This number represents the cost of the first global increased with expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_LEGAL_FEES_AMT	Global 1 Legal Fees Expense Amount	NUMBER (14, 3)	This number represents the cost of the first global legal fees amount.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_LRSRV_AMT	Global 1 Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_OUT_ADJ_FEES_AMT	Global 1 Outside Adjusting Fees Amount	NUMBER (14, 3)	This number represents the cost of the first global outside adjustment fees amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_PAID_LOSS_AMT	Global 1 Paid Loss Amount	NUMBER (14, 3)	This number represents the cost of the first global paid loss amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_SALV_AMT	Global 1 Salvage Amount	NUMBER (14, 3)	This number represents the cost of the first global salvage amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_SALV_RSRV_AMT	Global 1 Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_SUBRO_AMT	Global 1 Subrogation Amount	NUMBER (14, 3)	This number represents the cost of the first global subrogation amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_SUBRO_RSRV_AMT	Global 1 Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_ULAE_AMT	Global 1 Unallocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of the first global unallocated loss adjusting expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_ULAE_RSRV_AMT	Global 1 Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global unallocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_UNALLOC_EXPNS_AO_AMT	Global 1 UnAllocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the cost of the first global unallocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_ALAE_AMT	Global 2 Allocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of the second global allocated loss adjusting expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_ALAE_RSRV_AMT	Global 2 Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global allocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_ALLOC_EXPNS_AO_AMT	Global 2 Allocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the cost of the second global allocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_CTD_INCRD_AMT	Global 2 Claim to Date Incurred Amount	NUMBER (14, 3)	This number represents the cost of the second global claims to date incurred amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_CTD_INCRD_WEXPNS_AMT	Global 2 Claim to Date Incurred With Expenses Amount	NUMBER (14, 3)	This number represents the cost of the second global claims to date increased with expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_DED_LPMT_AMT	Global 2 Deductible Loss Payment Amount	NUMBER (14, 3)	This number represents the cost of the second global deductible loss payment amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_DED_LRSRV_CHANGE_AMT	Global 2 Deductible Loss Reserve Change Amount	NUMBER (14, 3)	This number represents the cost of the second global deductible loss reserve change amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_END_ALAE_RSRV_AMT	Global 2 Ending Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global end allocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_END_DED_LPMT_RSRV_AMT	Global 2 Ending Deductible Loss Payment Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global end deductible loss payment reserve amount.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_END_LRSRV_AMT	Global 2 Ending Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global ending loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_END_SALV_RSRV_AMT	Global 2 Ending Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global end salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_END_SUBRO_RSRV_AMT	Global 2 Ending Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global end subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_END_ULAE_RSRV_AMT	Global 2 Ending Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global end unallocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_INCRD_AMT	Global 2 Incurred Amount	NUMBER (14, 3)	This number represents the cost of the second global incurred amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_INCRD_WEXPNS_AMT	Global 2 Incurred With Expenses Amount	NUMBER (14, 3)	This number represents the cost of the second global increased with expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_LEGAL_FEES_AMT	Global 2 Legal Fees Expense Amount	NUMBER (14, 3)	This number represents the cost of the second global legal fees amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_LRSRV_AMT	Global 2 Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_OUT_ADJ_FEES_AMT	Global 2 Outside Adjusting Fees Amount	NUMBER (14, 3)	This number represents the cost of the second global outside adjustment fees amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_PAID_LOSS_AMT	Global 2 Paid Loss Amount	NUMBER (14, 3)	This number represents the cost of the second global paid loss amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_SALV_AMT	Global 2 Salvage Amount	NUMBER (14, 3)	This number represents the cost of the second global salvage amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_SALV_RSRV_AMT	Global 2 Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_SUBRO_AMT	Global 2 Subrogation Amount	NUMBER (14, 3)	This number represents the cost of the second global subrogation amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_SUBRO_RSRV_AMT	Global 2 Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_ULAE_AMT	Global 2 Unallocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of the second global unallocated loss adjusting expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_ULAE_RSRV_AMT	Global 2 Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global unallocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_UNALLOC_EXPNS_AO_AMT	Global 2 UnAllocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the cost of the second global unallocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_ALAE_AMT	Global 3 Allocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of the third global allocated loss adjusting expense amount.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_ALAE_RSRV_AMT	Global 3 Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global allocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_ALLOC_EXPNS_AO_AMT	Global 3 Allocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the cost of the third global allocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_CTD_INCRD_AMT	Global 3 Claim to Date Incurred Amount	NUMBER (14, 3)	This number represents the cost of the third global claims to date incurred amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_CTD_INCRD_WEXPNS_AMT	Global 3 Claim to Date Incurred With Expenses Amount	NUMBER (14, 3)	This number represents the cost of the third global claims to date increased with expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_DED_LPMT_AMT	Global 3 Deductible Loss Payment Amount	NUMBER (14, 3)	This number represents the cost of the third global deductible loss payment amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_DED_LRSRV_CHANGE_AMT	Global 3 Deductible Loss Reserve Change Amount	NUMBER (14, 3)	This number represents the cost of the third global deductible loss reserve change amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_END_ALAE_RSRV_AMT	Global 3 Ending Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global end allocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_END_DED_LPMT_RSRV_AMT	Global 3 Ending Deductible Loss Payment Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global end deductible loss payment reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_END_LRSRV_AMT	Global 3 Ending Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global ending loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_END_SALV_RSRV_AMT	Global 3 Ending Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global end salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_END_SUBRO_RSRV_AMT	Global 3 Ending Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global end subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_END_ULAE_RSRV_AMT	Global 3 Ending Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global end unallocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_INCRD_AMT	Global 3 Incurred Amount	NUMBER (14, 3)	This number represents the cost of the third global incurred amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_INCRD_WEXPNS_AMT	Global 3 Incurred With Expenses Amount	NUMBER (14, 3)	This number represents the cost of the third global increased with expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_LEGAL_FEES_AMT	Global 3 Legal Fees Expense Amount	NUMBER (14, 3)	This number represents the cost of the third global legal fees amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_LRSRV_AMT	Global 3 Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_OUT_ADJ_FEES_AMT	Global 3 Outside Adjusting Fees Amount	NUMBER (14, 3)	This number represents the cost of the third global outside adjustment fees amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_PAID_LOSS_AMT	Global 3 Paid Loss Amount	NUMBER (14, 3)	This number represents the cost of the third global paid loss amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_SALV_AMT	Global 3 Salvage Amount	NUMBER (14, 3)	This number represents the cost of the third global salvage amount.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_SALV_RSRV_AMT	Global 3 Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_SUBRO_AMT	Global 3 Subrogation Amount	NUMBER (14, 3)	This number represents the cost of the third global subrogation amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_SUBRO_RSRV_AMT	Global 3 Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_ULAE_AMT	Global 3 Unallocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of the third global unallocated loss adjusting expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_ULAE_RSRV_AMT	Global 3 Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global unallocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_UNALLOC_EXPNS_AO_AMT	Global 3 UnAllocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the cost of the third global unallocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	GRP_PRG_ID	Group Program Identifier	NUMBER (22, 0)	This system generated number identifies the group program instance.
Datamart	CLM_MTH_SNAP_FACT	INSD_ID	Insured Identifier	NUMBER (22, 0)	This system generated number identifies the insured instance.
Datamart	CLM_MTH_SNAP_FACT	INSUR_CO_ID	Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the insurance company instance in the claim monthly snapshot fact.
Datamart	CLM_MTH_SNAP_FACT	LITG_ID	Litigation Identifier	NUMBER (22, 0)	This system generated number identifies the litigation instance.
Datamart	CLM_MTH_SNAP_FACT	LMT_ID	Limit Identifier	NUMBER (22, 0)	This system generated number identifies the limit instance.
Datamart	CLM_MTH_SNAP_FACT	LOB_FACT_ID	Line Of Business Fact Identifier	NUMBER (22, 0)	This system generated number identifies the line of business fact instance.
Datamart	CLM_MTH_SNAP_FACT	LOB_ID	Line Of Business Identifier	NUMBER (22, 0)	This system generated number identifies the line of business instance.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_ALAE_AMT	Local Allocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of the local allocated loss adjustment expense amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_ALAE_RSRV_AMT	Local Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local allocated loss adjustment expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_ALLOC_EXPNS_AO_AMT	Local Allocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the cost of the local allocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_CTD_INCRD_AMT	Local Claim to Date Incurred Amount	NUMBER (14, 3)	This number represents the cost of the local claims to date incurred amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_CTD_INCRD_WEXPNS_AMT	Local Claim to Date Incurred With Expenses Amount	NUMBER (14, 3)	This number represents the cost of the local claims to date increased with expense amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_DED_LPMT_AMT	Local Deductible Loss Payment Amount	NUMBER (14, 3)	This number represents the cost of the local deductible loss payment amount.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MTH_SNAP_FACT	LOCAL_DED_LRSRV_CHANGE_AMT	Local Deductible Loss Reserve Change Amount	NUMBER (14, 3)	This number represents the cost of the local deductible loss reserve change amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_END_ALAE_RSRV_AMT	Local Ending Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local end allocated loss adjustment expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_END_DED_LPMT_RSRV_AMT	Local Ending Deductible Loss Payment Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local end deductible loss payment reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_END_LRSRV_AMT	Local Ending Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local ending loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_END_SALV_RSRV_AMT	Local Ending Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local end salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_END_SUBRO_RSRV_AMT	Local Ending Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local end subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_END_ULAE_RSRV_AMT	Local Ending Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local end unallocated loss adjustment expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_INCRD_AMT	Local Incurred Amount	NUMBER (14, 3)	This number represents the cost of the local incurred amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_INCRD_WEXPNS_AMT	Local Incurred With Expenses Amount	NUMBER (14, 3)	This number represents the cost of the local increased with expense amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_LEGAL_FEES_AMT	Local Legal Fees Expense Amount	NUMBER (14, 3)	This number represents the cost of the local legal fees amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_LRSRV_AMT	Local Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_OUT_ADJ_FEES_AMT	Local Outside Adjusting Fees Amount	NUMBER (14, 3)	This number represents the cost of the local outside adjustment fees amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_PAID_LOSS_AMT	Local Paid Loss Amount	NUMBER (14, 3)	This number represents the cost of the local paid loss amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_SALV_AMT	Local Salvage Amount	NUMBER (14, 3)	This number represents the cost of the local salvage amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_SALV_RSRV_AMT	Local Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_SUBRO_AMT	Local Subrogation Amount	NUMBER (14, 3)	This number represents the cost of the local subrogation amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_SUBRO_RSRV_AMT	Local Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_ULAE_AMT	Local Unallocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of the local unallocated loss adjustment expense amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_ULAE_RSRV_AMT	Local Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local unallocated loss adjustment expense reserve amount.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MTH_SNAP_FACT	LOCAL_UNALLOC_EXPNS_AO_AMT	Local UnAllocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the cost of the local unallocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	OPENED_CLM_NAT_KEY	Opened Claim Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the opened claim.
Datamart	CLM_MTH_SNAP_FACT	PARENT_INSUR_CO_ID	Parent Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the parent insurance company instance.
Datamart	CLM_MTH_SNAP_FACT	PLCY_ID	Policy Identifier	NUMBER (22, 0)	This system generated number identifies the policy instance.
Datamart	CLM_MTH_SNAP_FACT	PRODR_ID	Producer Identifier	NUMBER (22, 0)	This system generated number identifies the producer instance.
Datamart	CLM_MTH_SNAP_FACT	REINS_CNTRCT_ID	Reinsurance Contract Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance contract instance.
Datamart	CLM_MTH_SNAP_FACT	REINS_CO_ID	Reinsurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance company instance.
Datamart	CLM_MTH_SNAP_FACT	SUB_PRODR_ID	Sub Producer Identifier	NUMBER (22, 0)	This system generated number identifies the sub-producer instance.
Datamart	CLM_MTH_SNAP_FACT	SUPPLIER_ID	Supplier Identifier	NUMBER (22, 0)	This system generated number identifies the supplier instance.
Datamart	CLM_MTH_SNAP_FACT	SYS_PROC_DT	System Process Date	DATE	This calendar date represents when the system processed the claim monthly snapshot fact table.
Datamart	CLM_MTH_SNAP_FACT	UW_ASST_ID	Underwriting Assistant Identifier	NUMBER (22, 0)	This system generated number identifies the underwriting assistant instance.
Datamart	CLM_MTH_SNAP_FACT	UW_ID	Underwriter Identifier	NUMBER (22, 0)	This system generated number identifies the underwriter instance.
Staging	CLM_TRANS	ALLOC_EXPNS_TYP_CD	Allocation Expense Type Code	VARCHAR2(25)	This system code identifies the expense allocation type in the claim transaction.
Warehouse	CLM_TRANS	ALLOC_EXPNS_TYP_CD	Allocation Expense Type Code	VARCHAR2(25)	This system code identifies the expense allocation type in the claim transaction.
Warehouse	CLM_TRANS	ALLOC_EXPNS_TYP_DESC	Allocation Expense Type Code Description	VARCHAR2(60)	This value describes the allocation expense type code in the claim transaction.
Staging	CLM_TRANS	AVG_EXPNS_RSRV_CD	Average Expense Reserve Code	VARCHAR2(25)	This system code identifies the average reserve set in the claim transaction expenses.
Warehouse	CLM_TRANS	AVG_EXPNS_RSRV_CD	Average Expense Reserve Code	VARCHAR2(25)	This system code identifies the average reserve set in the claim transaction expenses.
Warehouse	CLM_TRANS	AVG_EXPNS_RSRV_DESC	Average Expense Reserve Code Description	VARCHAR2(60)	This system code identifies if an average reserve was set for expenses in the claim transaction.
Staging	CLM_TRANS	AVG_RSRV_CD	Average Reserve Code	VARCHAR2(25)	This system code identifies the average reserve set in the claim transaction.
Warehouse	CLM_TRANS	AVG_RSRV_CD	Average Reserve Code	VARCHAR2(25)	This system code identifies the average reserve set for a claim transaction.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLM_TRANS	AVG_RSRV_DESC	Average Reserve Code Description	VARCHAR2(60)	This value describes whether an average reserve was set in the claim transaction.
Warehouse	CLM_TRANS	BILL_ACCT_ID	Billing Account Identifier	NUMBER (22, 0)	This system generated number identifies the billing account instance for claim transaction.
Staging	CLM_TRANS	BILL_HRLY_RATE	Billable Hourly Rate	NUMBER (6,5)	This number represents the charge applicable or each hour for a service associated with a claims transaction.
Warehouse	CLM_TRANS	BILL_HRLY_RATE	Billable Hourly Rate	NUMBER (6, 5)	This number represents the charge applicable or each hour for a service associated with a claims transaction.
Staging	CLM_TRANS	BOOK_DT	Book Date	DATE	This calendar date represents when the claim transaction is recorded into the company's books. Usually, this is the greater of the transaction date or the effective date.
Warehouse	CLM_TRANS	BOOK_DT	Book Date	DATE	This calendar date represents when the claim transaction is recorded into the company's books. Usually, this is the greater of the transaction date or the effective date.
Warehouse	CLM_TRANS	CAT_ID	Catastrophe Identifier	NUMBER (22, 0)	This system generated number identifies the catastrophe in the claim transaction.
Warehouse	CLM_TRANS	CLASS_ID	Class Identifier	NUMBER (22, 0)	This system generated number identifies the class in the claim transaction.
Warehouse	CLM_TRANS	CLM_ID	Claim Identifier	NUMBER (22, 0)	This system generated number identifies the claim instance for claim transaction.
Staging	CLM_TRANS	CLM_TRANS_AMT	Claim Transaction Amount	NUMBER (14,3)	This number represents the actual amount of a claim transaction.
Warehouse	CLM_TRANS	CLM_TRANS_AMT	Claim Transaction Amount	NUMBER (14, 3)	This number represents the actual amount of a claim transaction.
Staging	CLM_TRANS	CLM_TRANS_CATG_CD	Claim Transaction Category Code	VARCHAR2(25)	This value represents a way to combine claim transactions into similar categories.
Warehouse	CLM_TRANS	CLM_TRANS_CATG_CD	Claim Transaction Category Code	VARCHAR2(25)	This value represents a way to combine claim transactions into similar categories.
Warehouse	CLM_TRANS	CLM_TRANS_CATG_DESC	Claim Transaction Category Description	VARCHAR2(60)	This value describes the way to combine claim transactions into similar categories.
Staging	CLM_TRANS	CLM_TRANS_CD	Claim Transaction Code	VARCHAR2(25)	This system code represents what type of loss activity occurred in the claim transaction.
Warehouse	CLM_TRANS	CLM_TRANS_CD	Claim Transaction Code	VARCHAR2(25)	This system code represents what type of loss activity occurred in the claim transaction.
Warehouse	CLM_TRANS	CLM_TRANS_DESC	Claim Transaction Description	VARCHAR2(60)	This value describes the claim transaction.
Warehouse	CLM_TRANS	CLM_TRANS_ID	Claim Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction instance.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLM_TRANS	COVRG_ID	Coverage Identifier	NUMBER (22, 0)	This system generated number identifies coverage instance in the claim transaction.
Warehouse	CLM_TRANS	COVRG_STATUS_ID	Coverage Status Identifier	NUMBER (22, 0)	This system generated number identifies coverage status instance in the claim transaction.
Warehouse	CLM_TRANS	DC_ID	Distribution Channel Identifier	NUMBER (22, 0)	This system generated number identifies the distribution channel instance in the claim transaction.
Warehouse	CLM_TRANS	DED_ID	Deductible Identifier	NUMBER (22, 0)	This system generated number identifies the deductible instance in the claim transaction.
Staging	CLM_TRANS	DIRECT_CEDED_ASSUMED_CD	Direct or Ceded or Assumed Code	VARCHAR2(25)	This system code identifies the claim transaction type as being direct, ceded, or assumed.
Warehouse	CLM_TRANS	DIRECT_CEDED_ASSUMED_CD	Direct or Ceded or Assumed Code	VARCHAR2(25)	This system code identifies the claim transaction type as being direct, ceded, or assumed.
Warehouse	CLM_TRANS	DIRECT_CEDED_ASSUMED_DESC	Direct or Ceded or Assumed Description	VARCHAR2(60)	This value describes a claims transaction to classify if it is direct, ceded or assumed.
Staging	CLM_TRANS	DOC_CURR_CD	Document Currency Code	VARCHAR2(25)	This system code identifies document currency for claim transaction.
Warehouse	CLM_TRANS	DOC_CURR_CD	Document Currency Code	VARCHAR2(25)	This system code identifies document currency for claim transaction.
Warehouse	CLM_TRANS	FEAT_ID	Feature Identifier	NUMBER (22, 0)	This system generated number identifies the claim feature instance for claims transaction.
Warehouse	CLM_TRANS	FEAT_STATUS_ID	Feature Status Identifier	NUMBER (22, 0)	This system generated number identifies the claim feature status instance in the claim transaction.
Warehouse	CLM_TRANS	GLOBAL_CURR_RATE_1	Global Currency Rate 1	NUMBER (22, 7)	This number represents the first global currency rate in the claim transaction.
Warehouse	CLM_TRANS	GLOBAL_CURR_RATE_2	Global Currency Rate 2	NUMBER (22, 7)	This number represents the second global currency rate in the claim transaction.
Warehouse	CLM_TRANS	GLOBAL_CURR_RATE_3	Global Currency Rate 3	NUMBER (22, 7)	This number represents the third global currency rate in the claim transaction.
Warehouse	CLM_TRANS	GRP_PRG_ID	Group Program Identifier	NUMBER (22, 0)	This system generated number identifies the group program instance in the claim transaction.
Warehouse	CLM_TRANS	LITG_ID	Litigation Identifier	NUMBER (22, 0)	This system generated number identifies the litigation instance in the claim transaction.
Warehouse	CLM_TRANS	LMT_ID	Limit Identifier	NUMBER (22, 0)	This system generated number identifies the limit instance in the claim transaction.
Warehouse	CLM_TRANS	LOB_ID	Line Of Business Identifier	NUMBER (22, 0)	This system generated number identifies the line of business instance in the claim transaction.
Warehouse	CLM_TRANS	LOCAL_CURR_RATE	Local Currency Rate	NUMBER (22, 7)	This number represents the local currency rate for claim transaction.
Staging	CLM_TRANS	NUM_HRS_BILLED	Number Of Hours Billed	NUMBER (22,0)	This number represents the count of hours billed to a claims transaction.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLM_TRANS	NUM_HRS_BILLED	Number Of Hours Billed	NUMBER (22, 0)	This number represents the count of hours billed to a claims transaction.
Warehouse	CLM_TRANS	PLCY_ID	Policy Identifier	NUMBER (22, 0)	This system generated number identifies the policy instance in the claim transaction.
Warehouse	CLM_TRANS	REINS_CNTRCT_ID	Reinsurance Contract Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance contract instance for claim transaction.
Staging	CLM_TRANS	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the claim transaction with a specific transaction.
Staging	CLM_TRANS	SRC_SYS_PROC_DT	Source System Process Date	DATE	This calendar date represents when source system processed the claim transaction.
Warehouse	CLM_TRANS	SRC_SYS_PROC_DT	Source System Process Date	DATE	This calendar date represents when source system processed the claim transaction.
Warehouse	CLM_TRANS	SYS_CLM_TRANS_CD	System Claim Transaction Code	VARCHAR2(25)	This system code identifies the system claim transaction.
Warehouse	CLM_TRANS	SYS_CLM_TRANS_DESC	System Claim Transaction Description	VARCHAR2(60)	This system code identifies the system claim transaction.
Warehouse	CLM_TRANS	SYS_PROC_DT	System Process Date	DATE	This calendar date represents when the system processed the claim transaction.
Staging	CLM_TRANS	TRANS_EFF_DT	Transaction Effective Date	DATE	This calendar date represents when a claims transaction is effective.
Warehouse	CLM_TRANS	TRANS_EFF_DT	Transaction Effective Date	DATE	This calendar date represents when a claims transaction is effective.
Datamart	CLM_TRANS_CD_DIM	ALLOC_EXPNS_TYP	Allocation Expense Type	VARCHAR2(60)	This value identifies the allocation expense. This expense represents the item or category against which expenses are applied.
Datamart	CLM_TRANS_CD_DIM	AVG_EXPNS_RSRV_CD	Average Expense Reserve Code	VARCHAR2(60)	This system code identifies the average expense reserve. This reserve is the average reserve set in the claim transaction expenses.
Datamart	CLM_TRANS_CD_DIM	AVG_RSRV_CD	Average Reserve Code	VARCHAR2(60)	This system code identifies the average reserve set.
Datamart	CLM_TRANS_CD_DIM	CLM_TRANS_CATG_CD	Claim Transaction Category Code	VARCHAR2(60)	This system code represents what type of loss activity occurred.
Datamart	CLM_TRANS_CD_DIM	CLM_TRANS_CD	Claim Transaction Code	VARCHAR2(60)	This system code represents what type of loss activity occurred.
Datamart	CLM_TRANS_CD_DIM	CLM_TRANS_CD_ID	Claim Transaction Code Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction code instance.
Datamart	CLM_TRANS_CD_DIM	DIRECT_CEDED_ASSUMED	Direct or Ceded or Assumed	VARCHAR2(60)	This value represents the indicator that identifies if a loss is paid internally, transferred to a reinsurer, or assumed.
Datamart	CLM_TRANS_CD_DIM	SYS_CLM_TRANS_CD	System Claim Transaction Code	VARCHAR2(60)	This system code identifies the system claim transaction.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_TRANS_FACT	BILL_ACCT_ID	Billing Account Identifier	NUMBER (22, 0)	This system generated number identifies the billing account instance.
Datamart	CLM_TRANS_FACT	BILL_HRLY_RATE	Billable Hourly Rate	NUMBER (6, 5)	This number represents the charge applicable or each hour for a service associated with a claims transaction.
Datamart	CLM_TRANS_FACT	BOOK_DT_ID	Book Date Identifier	DATE	This calendar date represents the book date.
Datamart	CLM_TRANS_FACT	CAT_ID	Catastrophe Identifier	NUMBER (22, 0)	This system generated number identifies the catastrophe.
Datamart	CLM_TRANS_FACT	CLASS_ID	Class Identifier	NUMBER (22, 0)	This system generated number identifies the class.
Datamart	CLM_TRANS_FACT	CLM_ADJ_ID	Claim Adjuster Identifier	NUMBER (22, 0)	This system generated number identifies the claim adjuster instance.
Datamart	CLM_TRANS_FACT	CLM_EXAMR_ID	Claim Examiner Identifier	NUMBER (22, 0)	This system generated number identifies the claim examiner instance.
Datamart	CLM_TRANS_FACT	CLM_ID	Claim Identifier	NUMBER (22, 0)	This system generated number identifies the claim instance.
Datamart	CLM_TRANS_FACT	CLM_MGR_ID	Claim Manager Identifier	NUMBER (22, 0)	This system generated number identifies the claim manager instance.
Datamart	CLM_TRANS_FACT	CLM_TRANS_AMT	Claim Transaction Amount	NUMBER (14, 3)	This number represents the actual amount of a claim transaction.
Datamart	CLM_TRANS_FACT	CLM_TRANS_CD_ID	Claim Transaction Code Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction code instance.
Datamart	CLM_TRANS_FACT	CLMT_ID	Claimant Identifier	NUMBER (22, 0)	This system generated number identifies the claimant instance.
Datamart	CLM_TRANS_FACT	COVRG_ID	Coverage Identifier	NUMBER (22, 0)	This system generated number identifies coverage instance in the claim transaction fact.
Datamart	CLM_TRANS_FACT	COVRG_STATUS_ID	Coverage Status Identifier	NUMBER (22, 0)	This system generated number identifies coverage status instance in the claim transaction fact.
Datamart	CLM_TRANS_FACT	DC_ID	Distribution Channel Identifier	NUMBER (22, 0)	This system generated number identifies the distribution channel instance.
Datamart	CLM_TRANS_FACT	DED_ID	Deductible Identifier	NUMBER (22, 0)	This system generated number identifies the deductible instance.
Datamart	CLM_TRANS_FACT	DOC_CURR_CD	Document Currency Code	VARCHAR2(25)	This system code identifies document currency.
Datamart	CLM_TRANS_FACT	FEAT_ID	Feature Identifier	NUMBER (22, 0)	This system generated number identifies the claim feature instance.
Datamart	CLM_TRANS_FACT	FEAT_STATUS_ID	Feature Status Identifier	NUMBER (22, 0)	This system generated number identifies the claim feature status instance.
Datamart	CLM_TRANS_FACT	GLOBAL_CURR_RATE_1	Global Currency Rate 1	NUMBER (22, 7)	This number represents the first global currency rate.
Datamart	CLM_TRANS_FACT	GLOBAL_CURR_RATE_2	Global Currency Rate 2	NUMBER (22, 7)	This number represents the second global currency rate.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_TRANS_FACT	GLOBAL_CURR_RATE_3	Global Currency Rate 3	NUMBER (22, 7)	This number represents the third global currency rate.
Datamart	CLM_TRANS_FACT	GRP_PRG_ID	Group Program Identifier	NUMBER (22, 0)	This system generated number identifies the group program instance.
Datamart	CLM_TRANS_FACT	INSD_ID	Insured Identifier	NUMBER (22, 0)	This system generated number identifies the insured instance in the claim transaction.
Datamart	CLM_TRANS_FACT	INSUR_CO_ID	Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the insurance company instance in the claim monthly snapshot fact.
Datamart	CLM_TRANS_FACT	LITG_ID	Litigation Identifier	NUMBER (22, 0)	This system generated number identifies the litigation instance.
Datamart	CLM_TRANS_FACT	LMT_ID	Limit Identifier	NUMBER (22, 0)	This system generated number identifies the limit instance.
Datamart	CLM_TRANS_FACT	LOB_FACT_ID	Line Of Business Fact Identifier	NUMBER (22, 0)	This system generated number identifies the line of business fact instance in the claim transaction.
Datamart	CLM_TRANS_FACT	LOB_ID	Line Of Business Identifier	NUMBER (22, 0)	This system generated number identifies the line of business instance.
Datamart	CLM_TRANS_FACT	LOCAL_CURR_RATE	Local Currency Rate	NUMBER (22, 7)	This number represents the local currency rate.
Datamart	CLM_TRANS_FACT	NUM_HRS_BILLED	Number Of Hours Billed	NUMBER (22, 0)	This number represents the count of hours billed to a claims transaction fact table.
Datamart	CLM_TRANS_FACT	PARENT_INSUR_CO_ID	Parent Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the parent insurance company instance.
Datamart	CLM_TRANS_FACT	PLCY_ID	Policy Identifier	NUMBER (22, 0)	This system generated number identifies the policy instance.
Datamart	CLM_TRANS_FACT	PRODR_ID	Producer Identifier	NUMBER (22, 0)	This system generated number identifies the producer instance.
Datamart	CLM_TRANS_FACT	REINS_CNTRCT_ID	Reinsurance Contract Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance contract instance.
Datamart	CLM_TRANS_FACT	REINS_CO_ID	Reinsurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance company instance.
Datamart	CLM_TRANS_FACT	SRC_SYS_PROC_DT_ID	Source System Process Date Identifier	DATE	This calendar date represents the system source process date instance.
Datamart	CLM_TRANS_FACT	SUB_PRODR_ID	Sub Producer Identifier	NUMBER (22, 0)	This system generated number identifies the sub-producer instance.
Datamart	CLM_TRANS_FACT	SUPPLIER_ID	Supplier Identifier	NUMBER (22, 0)	This system generated number identifies the supplier instance.
Datamart	CLM_TRANS_FACT	SYS_PROC_DT	System Process Date	DATE	This calendar date represents when the system processed the claim transaction fact table.
Datamart	CLM_TRANS_FACT	TRANS_EFF_DT_ID	Transaction Effective Date Identifier	DATE	This calendar date represents when a claim transaction fact is effective.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_TRANS_FACT	UW_ASST_ID	Underwriting Assistant Identifier	NUMBER (22, 0)	This system generated number identifies the underwriting assistant instance.
Datamart	CLM_TRANS_FACT	UW_ID	Underwriter Identifier	NUMBER (22, 0)	This system generated number identifies the underwriter instance.
Warehouse	CLM_TRANS_TO_CA_VEH	CA_VEH_ID	Commercial Auto Vehicle Identifier	NUMBER (22, 0)	This system generated number identifies the commercial vehicle in the claim transaction to commercial vehicle.
Warehouse	CLM_TRANS_TO_CA_VEH	CLM_TRANS_ID	Claim Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction instance in the claim transaction to commercial vehicle.
Warehouse	CLM_TRANS_TO_CP_BLDG	CLM_TRANS_ID	Claim Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction instance in the claim transaction to commercial property building.
Warehouse	CLM_TRANS_TO_CP_BLDG	CP_BLDG_ID	Commercial Property Building Identifier	NUMBER (22, 0)	This system generated number identifies the property instance in the claim transaction to commercial property building.
Warehouse	CLM_TRANS_TO_DF_DWLNG	CLM_TRANS_ID	Claim Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction instance in the claim transaction to dwelling fire dwelling.
Warehouse	CLM_TRANS_TO_DF_DWLNG	DF_DWLNG_ID	Dwelling Fire Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling instance in the claim transaction to dwelling fire dwelling.
Warehouse	CLM_TRANS_TO_HO_DWLNG	CLM_TRANS_ID	Claim Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction instance for claim transaction to homeowners dwelling.
Warehouse	CLM_TRANS_TO_HO_DWLNG	HO_DWLNG_ID	Homeowners Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling instance.
Warehouse	CLM_TRANS_TO_PA_VEH	CLM_TRANS_ID	Claim Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction instance for claim transaction to personal vehicle.
Warehouse	CLM_TRANS_TO_PA_VEH	PA_VEH_ID	Persona Auto Vehicle Identifier	NUMBER (22, 0)	This system generated number identifies the personal vehicle instance in the claim transaction to personal vehicle.
Warehouse	CLM_TRANS_TO_PARTY	CLM_TRANS_ID	Claim Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction instance in the claim transaction to party.
Warehouse	CLM_TRANS_TO_PARTY	PARTY_ID	Party Identifier	NUMBER (22, 0)	This system generated number identifies the party in the claim transaction to party.
Warehouse	CLM_TRANS_TO_PARTY	PARTY_ROLE_ID	Party Role Identifier	NUMBER (22, 0)	This system generated number identifies the party role instance in the claim transaction to party.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLM_TRANS_TO_PU_PLCY	CLM_TRANS_ID	Claim Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction instance in the claim transaction to personal umbrella policy.
Warehouse	CLM_TRANS_TO_PU_PLCY	PU_PLCY_ID	Personal Umbrella Policy Identifier	NUMBER (22, 0)	This system generated number identifies the personal umbrella policy instance in the claim transaction to personal umbrella policy.
Warehouse	CLMT	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claimant applies.
Warehouse	CLMT	CLMT_ID	Claimant Identifier	NUMBER (22, 0)	This system generated number identifies the claimant instance.
Staging	CLMT	CLMT_TYP_CD	Claimant Type Code	VARCHAR2(25)	This system code refers to the type of entity making the claim.
Warehouse	CLMT	CLMT_TYP_CD	Claimant Type Code	VARCHAR2(25)	This system code refers to the type of entity making the claim.
Warehouse	CLMT	CLMT_TYP_DESC	Claimant Type Description	VARCHAR2(60)	This value describes the type of entity making the claim.
Staging	CLMT	CLMT_UDF_CD_1	Claimant User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claimant user defined field.
Warehouse	CLMT	CLMT_UDF_CD_1	Claimant User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claimant user defined field.
Staging	CLMT	CLMT_UDF_CD_2	Claimant User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claimant user defined field.
Warehouse	CLMT	CLMT_UDF_CD_2	Claimant User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claimant user defined field.
Staging	CLMT	CLMT_UDF_CD_3	Claimant User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claimant user defined field.
Warehouse	CLMT	CLMT_UDF_CD_3	Claimant User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claimant user defined field.
Staging	CLMT	CLMT_UDF_CD_4	Claimant User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claimant user defined field.
Warehouse	CLMT	CLMT_UDF_CD_4	Claimant User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claimant user defined field.
Staging	CLMT	CLMT_UDF_CD_5	Claimant User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claimant user defined field.
Warehouse	CLMT	CLMT_UDF_CD_5	Claimant User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claimant user defined field.
Warehouse	CLMT	CLMT_UDF_DESC_1	Claimant User Defined Field Description 1	VARCHAR2(60)	This value describes the first claimant user defined field.
Warehouse	CLMT	CLMT_UDF_DESC_2	Claimant User Defined Field Description 2	VARCHAR2(60)	This value describes the second claimant user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLMT	CLMT_UDF_DESC_3	Claimant User Defined Field Description 3	VARCHAR2(60)	This value describes the third claimant user defined field.
Warehouse	CLMT	CLMT_UDF_DESC_4	Claimant User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth claimant user defined field.
Warehouse	CLMT	CLMT_UDF_DESC_5	Claimant User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth claimant user defined field.
Warehouse	CLMT	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claimant is currently applicable.
Warehouse	CLMT	END_DT	End Date	DATE	This calendar date represents when the claimant is no longer valid.
Warehouse	CLMT	ORG_ID	Organization Identifier	NUMBER (22, 0)	This system generated number identifies the claimant organization instance.
Warehouse	CLMT	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party in the claimant.
Warehouse	CLMT	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person in the claimant.
Staging	CLMT	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the claimant with a specific transaction.
Datamart	CLMT_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claimant applies.
Datamart	CLMT_DIM	CLMT_BIRTH_DT_ID	Claimant Birth Date Identifier	DATE	This calendar date represents the claimant date of birth.
Datamart	CLMT_DIM	CLMT_BUS_START_DT_ID	Claimant Business Start Date Identifier	DATE	This calendar date represents the claimant business start date.
Datamart	CLMT_DIM	CLMT_CNTCT_DESC	Claimant Contact Description	VARCHAR2(60)	This value describes claimant contact.
Datamart	CLMT_DIM	CLMT_CNTCT_TYP	Claimant Contact Type	VARCHAR2(60)	This value the claimant's method of contact.
Datamart	CLMT_DIM	CLMT_CNTCT_UDF_1	Claimant Contact User Defined Field 1	VARCHAR2(60)	This value describes the first claimant contact user defined field.
Datamart	CLMT_DIM	CLMT_CNTCT_UDF_2	Claimant Contact User Defined Field 2	VARCHAR2(60)	This value describes the second claimant contact user defined field.
Datamart	CLMT_DIM	CLMT_CNTCT_UDF_3	Claimant Contact User Defined Field 3	VARCHAR2(60)	This value describes the third claimant contact user defined field.
Datamart	CLMT_DIM	CLMT_CNTCT_UDF_4	Claimant Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth claimant contact user defined field.
Datamart	CLMT_DIM	CLMT_CNTCT_UDF_5	Claimant Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth claimant contact user defined field.
Datamart	CLMT_DIM	CLMT_CNTY	Claimant County	VARCHAR2(60)	This value identifies the county where claimant is located.
Datamart	CLMT_DIM	CLMT_CTRY	Claimant Country	VARCHAR2(60)	This value identifies the country where claimant is located.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLMT_DIM	CLMT_CTY	Claimant City	VARCHAR2(32)	This value identifies the city where claimant is located.
Datamart	CLMT_DIM	CLMT_DBA	Claimant Doing Business As	VARCHAR2(170)	This value represents the claimant's operating business name.
Datamart	CLMT_DIM	CLMT_DSTRCT	Claimant District	VARCHAR2(60)	This value represents the district where claimant is located.
Datamart	CLMT_DIM	CLMT_GENDER	Claimant Gender	VARCHAR2(60)	This value represents the gender (male or female) of the claimant.
Datamart	CLMT_DIM	CLMT_GEOG_BNDRY_UDF_1	Claimant Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first claimant geographic boundary user defined field.
Datamart	CLMT_DIM	CLMT_GEOG_BNDRY_UDF_2	Claimant Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second claimant geographic boundary user defined field.
Datamart	CLMT_DIM	CLMT_GEOG_BNDRY_UDF_3	Claimant Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third claimant geographic boundary user defined field.
Datamart	CLMT_DIM	CLMT_GEOG_BNDRY_UDF_4	Claimant Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth claimant geographic boundary user defined field.
Datamart	CLMT_DIM	CLMT_GEOG_BNDRY_UDF_5	Claimant Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth claimant geographic boundary user defined field.
Datamart	CLMT_DIM	CLMT_GOVT_ID_NUM	Claimant Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the claimant. For example, in the USA: SSN or FEIN.
Datamart	CLMT_DIM	CLMT_ID	Claimant Identifier	NUMBER (22, 0)	This system generated number identifies the claimant instance.
Datamart	CLMT_DIM	CLMT_LATITUDE	Claimant Latitude	VARCHAR2(11)	This value represents the latitude location of claimant.
Datamart	CLMT_DIM	CLMT_LONGITUDE	Claimant Longitude	VARCHAR2(11)	This value represents the longitude location of claimant.
Datamart	CLMT_DIM	CLMT_MARITAL_STATUS	Claimant Marital Status	VARCHAR2(60)	The present marital condition (single, married, divorced, widowed) of the claimant.
Datamart	CLMT_DIM	CLMT_NAICS_CD	Claimant North American Industry Classification System Code	VARCHAR2(60)	This value represents the North America Industry Class (NAICS) code assigned to claimant.
Datamart	CLMT_DIM	CLMT_NAT_KEY	Claimant Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claimant.
Datamart	CLMT_DIM	CLMT_NM	Claimant Name	VARCHAR2(170)	This value represents the name of the claimant associated with a claim.
Datamart	CLMT_DIM	CLMT_NOB	Claimant Nature of Business	VARCHAR2(60)	This value represents the type or category of the business activities done by the claimant.
Datamart	CLMT_DIM	CLMT_NUM_EMP	Claimant Number of Employees	NUMBER (22, 0)	This number represents the count of people employed by claimant.
Datamart	CLMT_DIM	CLMT_ORG_UDF_1	Claimant Organization User Defined Field 1	VARCHAR2(60)	This value describes the first claimant organization user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLMT_DIM	CLMT_ORG_UDF_2	Claimant Organization User Defined Field 2	VARCHAR2(60)	This value describes the second claimant organization user defined field.
Datamart	CLMT_DIM	CLMT_ORG_UDF_3	Claimant Organization User Defined Field 3	VARCHAR2(60)	This value describes the third claimant organization user defined field.
Datamart	CLMT_DIM	CLMT_ORG_UDF_4	Claimant Organization User Defined Field 4	VARCHAR2(60)	This value describes the fourth claimant organization user defined field.
Datamart	CLMT_DIM	CLMT_ORG_UDF_5	Claimant Organization User Defined Field 5	VARCHAR2(60)	This value describes the fifth claimant organization user defined field.
Datamart	CLMT_DIM	CLMT_PARTY_UDF_1	Claimant Party User Defined Field 1	VARCHAR2(60)	This value describes the first claimant party user defined field.
Datamart	CLMT_DIM	CLMT_PARTY_UDF_2	Claimant Party User Defined Field 2	VARCHAR2(60)	This value describes the second claimant party user defined field.
Datamart	CLMT_DIM	CLMT_PARTY_UDF_3	Claimant Party User Defined Field 3	VARCHAR2(60)	This value describes the third claimant party user defined field.
Datamart	CLMT_DIM	CLMT_PARTY_UDF_4	Claimant Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth claimant party user defined field.
Datamart	CLMT_DIM	CLMT_PARTY_UDF_5	Claimant Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth claimant party user defined field.
Datamart	CLMT_DIM	CLMT_PERS_UDF_1	Claimant Person User Defined Field 1	VARCHAR2(60)	This value describes the first claimant person user defined field.
Datamart	CLMT_DIM	CLMT_PERS_UDF_2	Claimant Person User Defined Field 2	VARCHAR2(60)	This value describes the second claimant person user defined field.
Datamart	CLMT_DIM	CLMT_PERS_UDF_3	Claimant Person User Defined Field 3	VARCHAR2(60)	This value describes the third claimant person user defined field.
Datamart	CLMT_DIM	CLMT_PERS_UDF_4	Claimant Person User Defined Field 4	VARCHAR2(60)	This value describes the fourth claimant person user defined field.
Datamart	CLMT_DIM	CLMT_PERS_UDF_5	Claimant Person User Defined Field 5	VARCHAR2(60)	This value describes the fifth claimant person user defined field.
Datamart	CLMT_DIM	CLMT_PRES_EMPLMT_START_YR	Claimant Present Employment Start Year	CHAR(4)	This value represents the calendar year that the claimant began working for their current employer.
Datamart	CLMT_DIM	CLMT_PSTL_CD	Claimant Postal Code	VARCHAR2(11)	This value represents the claimant's full postal zip code as defined by company specifications.
Datamart	CLMT_DIM	CLMT_PSTL_CD_PRFX	Claimant Postal Code Prefix	VARCHAR2(3)	This value represents the claimant's first 3 digits of a 5 digit geopolitical zip code.
Datamart	CLMT_DIM	CLMT_PSTL_SUB_CD	Claimant Postal Sub Code	VARCHAR2(4)	This value represents the claimant's ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	CLMT_DIM	CLMT_REGION	Claimant Region	VARCHAR2(60)	This value represents the geographic region where claimant is located.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLMT_DIM	CLMT_SIC_CD	Claimant Standard Industrial Classification Code	VARCHAR2(60)	This system code represents the SIC code assigned to the claimant.The Standard industrial Classification (SIC) code is an industry code that identifies the classification of business activity.
Datamart	CLMT_DIM	CLMT_STATE	Claimant State	VARCHAR2(60)	This value identifies the state where claimant is located.
Datamart	CLMT_DIM	CLMT_TAX_LOC_ID	Claimant Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier.
Datamart	CLMT_DIM	CLMT_TERR	Claimant Territory	VARCHAR2(60)	This value represents the territory where the claimant is located.
Datamart	CLMT_DIM	CLMT_TYP	Claimant Type	VARCHAR2(60)	This value represents the attributes of the claimant.
Datamart	CLMT_DIM	CLMT_UDF_1	Claimant User Defined Field 1	VARCHAR2(60)	This value describes the first claimant user defined field.
Datamart	CLMT_DIM	CLMT_UDF_2	Claimant User Defined Field 2	VARCHAR2(60)	This value describes the second claimant user defined field.
Datamart	CLMT_DIM	CLMT_UDF_3	Claimant User Defined Field 3	VARCHAR2(60)	This value describes the third claimant user defined field.
Datamart	CLMT_DIM	CLMT_UDF_4	Claimant User Defined Field 4	VARCHAR2(60)	This value describes the fourth claimant user defined field.
Datamart	CLMT_DIM	CLMT_UDF_5	Claimant User Defined Field 5	VARCHAR2(60)	This value describes the fifth claimant user defined field.
Datamart	CLMT_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claimant is currently applicable.
Datamart	CLMT_DIM	END_DT	End Date	DATE	This date represents the calendar date that the claimant is no longer valid.
Staging	CNTCT	CNTCT_CD	Contact Code	VARCHAR2(25)	This system code indicates the attributes of contact.
Warehouse	CNTCT	CNTCT_CD	Contact Code	VARCHAR2(25)	This system code describes the type of contact.
Warehouse	CNTCT	CNTCT_DESC	Contact Description	VARCHAR2(60)	This value describes the contact.
Warehouse	CNTCT	CNTCT_ID	Contact Identifier	NUMBER (22, 0)	This system generated number identifies the contact instance.
Staging	CNTCT	CNTCT_NAT_KEY	Contact Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the contact.
Warehouse	CNTCT	CNTCT_NAT_KEY	Contact Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the contact.
Staging	CNTCT	CNTCT_RLAT_CD	Contact Relationship Code	VARCHAR2(25)	This system code indicates the contact relationship.
Staging	CNTCT	CNTCT_TYP_CD	Contact Type Code	VARCHAR2(25)	This system code identifies the contact type.
Warehouse	CNTCT	CNTCT_TYP_CD	Contact Type Code	VARCHAR2(25)	This system code indicates the contact type.
Warehouse	CNTCT	CNTCT_TYP_DESC	Contact Type Description	VARCHAR2(60)	This value describes the contact type.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CNTCT	CNTCT_UDF_CD_1	Contact User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_CD_1	Contact User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first contact user defined field.
Staging	CNTCT	CNTCT_UDF_CD_2	Contact User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_CD_2	Contact User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second contact user defined field.
Staging	CNTCT	CNTCT_UDF_CD_3	Contact User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_CD_3	Contact User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third contact user defined field.
Staging	CNTCT	CNTCT_UDF_CD_4	Contact User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_CD_4	Contact User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth contact user defined field.
Staging	CNTCT	CNTCT_UDF_CD_5	Contact User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_CD_5	Contact User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_DESC_1	Contact User Defined Field Description 1	VARCHAR2(60)	This value describes the first contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_DESC_2	Contact User Defined Field Description 2	VARCHAR2(60)	This value describes the second contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_DESC_3	Contact User Defined Field Description 3	VARCHAR2(60)	This value describes the third contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_DESC_4	Contact User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_DESC_5	Contact User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth contact user defined field.
Staging	CNTCT	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the contact with a specific transaction.
Staging	COVRG	ANNU_STMT_LINE_CD	Annual Statement Line Code	VARCHAR2(25)	This system code indicates in which line of the annual statement a transaction belongs.
Warehouse	COVRG	ANNU_STMT_LINE_CD	Annual Statement Line Code	VARCHAR2(25)	This system code indicates in which line of the annual statement a transaction belongs.
Warehouse	COVRG	ANNU_STMT_LINE_DESC	Annual Statement Line Code Description	VARCHAR2(60)	This value represents the description that indicates in which line of the annual statement a transaction belongs.
Warehouse	COVRG	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage was initially available.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	COVRG	BUREAU_RPT_PLAN_CD	Bureau Report Plan Code	VARCHAR2(25)	This system code indicates the statistical plan code used for bureau reporting.
Warehouse	COVRG	BUREAU_RPT_PLAN_CD	Bureau Report Plan Code	VARCHAR2(25)	This system code indicates the statistical plan code used for bureau reporting.
Warehouse	COVRG	BUREAU_RPT_PLAN_DESC	Bureau Report Plan Code Description	VARCHAR2(60)	This system code indicates the statistical plan code used for bureau reporting.
Staging	COVRG	COVRG_CATG_CD	Coverage Category Code	VARCHAR2(25)	This value represents a way to group coverages within a line of business.
Warehouse	COVRG	COVRG_CATG_CD	Coverage Category Code	VARCHAR2(25)	This system code indicates the coverage category.
Warehouse	COVRG	COVRG_CATG_DESC	Coverage Category Description	VARCHAR2(60)	This value describes the coverage category.
Staging	COVRG	COVRG_CD	Coverage Code	VARCHAR2(25)	This system code identifies and/or further defines a type of coverage, discount, surcharge or factor being requested or applied It may also identify the type of insured value or coverage requested as part of a commercial property schedule submission.
Warehouse	COVRG	COVRG_CD	Coverage Code	VARCHAR2(25)	This system code identifies and/or further defines a type of coverage, discount, surcharge or factor being requested or applied It may also identify the type of insured value or coverage requested as part of a commercial property schedule submission.
Warehouse	COVRG	COVRG_DESC	Coverage Description	VARCHAR2(60)	This value describes a single coverage afforded on the insurance policy.
Warehouse	COVRG	COVRG_ID	Coverage Identifier	NUMBER (22, 0)	This system generated number identifies coverage instance.
Staging	COVRG	COVRG_NAT_KEY	Coverage Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the coverage.
Warehouse	COVRG	COVRG_NAT_KEY	Coverage Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the coverage.
Staging	COVRG	COVRG_PART_CD	Coverage Part Code	VARCHAR2(25)	This system code represents a line of business within a package policy.
Warehouse	COVRG	COVRG_PART_CD	Coverage Part Code	VARCHAR2(25)	This system code represents a line of business within a package policy.
Warehouse	COVRG	COVRG_PART_DESC	Coverage Part Description	VARCHAR2(60)	This value describes a line of business within a package policy.
Staging	COVRG	COVRG_UDF_CD_1	Coverage User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first coverage user defined field.
Warehouse	COVRG	COVRG_UDF_CD_1	Coverage User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first coverage user defined field.
Staging	COVRG	COVRG_UDF_CD_2	Coverage User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second coverage user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	COVRG	COVRG_UDF_CD_2	Coverage User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second coverage user defined field.
Staging	COVRG	COVRG_UDF_CD_3	Coverage User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third coverage user defined field.
Warehouse	COVRG	COVRG_UDF_CD_3	Coverage User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third coverage user defined field.
Staging	COVRG	COVRG_UDF_CD_4	Coverage User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth coverage user defined field.
Warehouse	COVRG	COVRG_UDF_CD_4	Coverage User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth coverage user defined field.
Staging	COVRG	COVRG_UDF_CD_5	Coverage User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth coverage user defined field.
Warehouse	COVRG	COVRG_UDF_CD_5	Coverage User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth coverage user defined field.
Warehouse	COVRG	COVRG_UDF_DESC_1	Coverage User Defined Field Description 1	VARCHAR2(60)	This value describes the first coverage user defined field.
Warehouse	COVRG	COVRG_UDF_DESC_2	Coverage User Defined Field Description 2	VARCHAR2(60)	This value describes the second coverage user defined field.
Warehouse	COVRG	COVRG_UDF_DESC_3	Coverage User Defined Field Description 3	VARCHAR2(60)	This value describes the third coverage user defined field.
Warehouse	COVRG	COVRG_UDF_DESC_4	Coverage User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth coverage user defined field.
Warehouse	COVRG	COVRG_UDF_DESC_5	Coverage User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth coverage user defined field.
Warehouse	COVRG	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the coverage is currently available.
Warehouse	COVRG	END_DT	End Date	DATE	This calendar date represents when the coverage is no longer valid.
Staging	COVRG	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the coverage with a specific transaction.
Staging	COVRG	SCND_COVRG_CD	Second Coverage Code	VARCHAR2(25)	This value represents the client defined code that will further breakdown the type of coverage afforded on the insurance line policy.
Warehouse	COVRG	SCND_COVRG_CD	Second Coverage Code	VARCHAR2(25)	This value represents the client defined code that will further breakdown the type of coverage afforded on the insurance policy.
Warehouse	COVRG	SCND_COVRG_DESC	Second Coverage Description	VARCHAR2(60)	This value represents the client defined code that will further breakdown the type of coverage afforded on the insurance policy.
Staging	COVRG	STAT_PLAN_CD	Statistical Plan Code	VARCHAR2(25)	This system code identifies the statistical plan for coverage.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	COVRG	STAT_PLAN_CD	Statistical Plan Code	VARCHAR2(25)	This system code identifies the statistical plan for coverage.
Warehouse	COVRG	STAT_PLAN_DESC	Statistical Plan Description	VARCHAR2(60)	This value describes the statistical plan.
Warehouse	COVRG	SYS_COVRG_PART_CD	System Coverage Part Code	VARCHAR2(25)	This system code represents a system coverage part.
Warehouse	COVRG	SYS_COVRG_PART_DESC	System Coverage Part Description	VARCHAR2(60)	This value describes the system coverage part.
Datamart	COVRG_DIM	ANNU_STMT_LINE	Annual Statement Line	VARCHAR2(60)	This value represents the description that indicates in which line of the annual statement a transaction belongs.
Datamart	COVRG_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage applies.
Datamart	COVRG_DIM	BUREAU_RPT_PLAN_CD	Bureau Report Plan Code	VARCHAR2(60)	This system code indicates the statistical plan code used for bureau reporting.
Datamart	COVRG_DIM	COVRG_CATG	Coverage Category	VARCHAR2(60)	This value represents the way coverages are grouped within a line of business.
Datamart	COVRG_DIM	COVRG_DESC	Coverage Description	VARCHAR2(60)	This value describes a single coverage afforded on the insurance policy.
Datamart	COVRG_DIM	COVRG_ID	Coverage Identifier	NUMBER (22, 0)	This system generated number identifies coverage instance.
Datamart	COVRG_DIM	COVRG_NAT_KEY	Coverage Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the coverage.
Datamart	COVRG_DIM	COVRG_PART	Coverage Part	VARCHAR2(60)	This value describes the portion of a risk to which a coverage applies.
Datamart	COVRG_DIM	COVRG_UDF_1	Coverage User Defined Field 1	VARCHAR2(60)	This value describes the first coverage user defined field.
Datamart	COVRG_DIM	COVRG_UDF_2	Coverage User Defined Field 2	VARCHAR2(60)	This value describes the second coverage user defined field.
Datamart	COVRG_DIM	COVRG_UDF_3	Coverage User Defined Field 3	VARCHAR2(60)	This value describes the third coverage user defined field.
Datamart	COVRG_DIM	COVRG_UDF_4	Coverage User Defined Field 4	VARCHAR2(60)	This value describes the fourth coverage user defined field.
Datamart	COVRG_DIM	COVRG_UDF_5	Coverage User Defined Field 5	VARCHAR2(60)	This value describes the fifth coverage user defined field.
Datamart	COVRG_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the coverage is currently applicable.
Datamart	COVRG_DIM	END_DT	End Date	DATE	This calendar date represents when the coverage is no longer valid.
Datamart	COVRG_DIM	SCND_COVRG_DESC	Second Coverage Description	VARCHAR2(60)	This value represents the client defined code that will further breakdown the type of coverage afforded on the insurance policy.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	COVRG_DIM	STAT_PLAN_CD	Statistical Plan Code	VARCHAR2(60)	This system code identifies the statistical plan for coverage.
Staging	COVRG_STATUS	COVRG_EFF_DT	Coverage Effective Date	DATE	This calender date represents when the policy coverage begins.
Warehouse	COVRG_STATUS	COVRG_EFF_DT	Coverage Effective Date	DATE	This calender date represents when the policy coverage begins.
Staging	COVRG_STATUS	COVRG_EXPR_DT	Coverage Expiration Date	DATE	This calender date represents when the policy coverage ends.
Warehouse	COVRG_STATUS	COVRG_EXPR_DT	Coverage Expiration Date	DATE	This calender date represents when the policy coverage ends.
Warehouse	COVRG_STATUS	COVRG_STATUS_ID	Coverage Status Identifier	NUMBER (22, 0)	This system generated number identifies coverage status instance.
Staging	COVRG_STATUS	COVRG_STATUS_UDF_CD_1	Coverage Status User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first coverage status user defined field.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_CD_1	Coverage Status User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first coverage status user defined field.
Staging	COVRG_STATUS	COVRG_STATUS_UDF_CD_2	Coverage Status User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second coverage status user defined field.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_CD_2	Coverage Status User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second coverage status user defined field.
Staging	COVRG_STATUS	COVRG_STATUS_UDF_CD_3	Coverage Status User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third coverage status user defined field.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_CD_3	Coverage Status User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third coverage status user defined field.
Staging	COVRG_STATUS	COVRG_STATUS_UDF_CD_4	Coverage Status User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth coverage status user defined field.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_CD_4	Coverage Status User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth coverage status user defined field.
Staging	COVRG_STATUS	COVRG_STATUS_UDF_CD_5	Coverage Status User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth coverage status user defined field.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_CD_5	Coverage Status User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth coverage status user defined field.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_DESC_1	Coverage Status User Defined Field Description 1	VARCHAR2(60)	This value describes the first coverage status user defined field.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_DESC_2	Coverage Status User Defined Field Description 2	VARCHAR2(60)	This value describes the second coverage status user defined field.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_DESC_3	Coverage Status User Defined Field Description 3	VARCHAR2(60)	This value describes the third coverage status user defined field.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_DESC_4	Coverage Status User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth coverage status user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_DESC_5	Coverage Status User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth coverage status user defined field.
Staging	COVRG_STATUS	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the coverage status with a specific transaction.
Datamart	COVRG_STATUS_DIM	COVRG_EFF_DT	Coverage Effective Date	DATE	This date represents the calendar date of the policy coverage begins.
Datamart	COVRG_STATUS_DIM	COVRG_EXPR_DT	Coverage Expiration Date	DATE	This date represents the calendar date of the policy coverage ends.
Datamart	COVRG_STATUS_DIM	COVRG_STATUS_ID	Coverage Status Identifier	NUMBER (22, 0)	This system generated number identifies coverage status instance.
Datamart	COVRG_STATUS_DIM	COVRG_STATUS_UDF_1	Coverage Status User Defined Field 1	VARCHAR2(60)	This value describes the first coverage status user defined field.
Datamart	COVRG_STATUS_DIM	COVRG_STATUS_UDF_2	Coverage Status User Defined Field 2	VARCHAR2(60)	This value describes the second coverage status user defined field.
Datamart	COVRG_STATUS_DIM	COVRG_STATUS_UDF_3	Coverage Status User Defined Field 3	VARCHAR2(60)	This value describes the third coverage status user defined field.
Datamart	COVRG_STATUS_DIM	COVRG_STATUS_UDF_4	Coverage Status User Defined Field 4	VARCHAR2(60)	This value describes the fourth coverage status user defined field.
Datamart	COVRG_STATUS_DIM	COVRG_STATUS_UDF_5	Coverage Status User Defined Field 5	VARCHAR2(60)	This value describes the fifth coverage status user defined field.
Staging	CP_BLDG	ALUMINUM_WIRG_FLG	Aluminum Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of aluminum wiring.
Warehouse	CP_BLDG	ALUMINUM_WIRG_FLG	Aluminum Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of aluminum wiring.
Warehouse	CP_BLDG	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage.
Staging	CP_BLDG	BLDG_OCPCY	Building Occupancy	NUMBER (22,0)	This number represents the type of occupants of the commercial building. For example, owner and tenant occupants.
Warehouse	CP_BLDG	BLDG_OCPCY	Building Occupancy	NUMBER (22, 0)	This number represents the type of occupants of the commercial building. For example, owner and tenant occupants.
Warehouse	CP_BLDG	BLDG_USE_CD	Building Use Code	VARCHAR2(25)	This system code indicates the primary use of a commercial building.
Warehouse	CP_BLDG	BLDG_USE_DESC	Building Use Code Description	VARCHAR2(60)	This value describes the business use code.
Staging	CP_BLDG	BURGLAR_MONITOR_TYP_CD	Burglar Monitoring Type Code	VARCHAR2(25)	This system code describes presence or absence and attributes of burglar alarm in use at the building.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CP_BLDG	BURGLAR_MONITOR_TYP_CD	Burglar Monitoring Type Code	VARCHAR2(25)	This system code describes presence or absence and attributes of burglar alarm in use at the building.
Warehouse	CP_BLDG	BURGLAR_MONITOR_TYP_DESC	Burglar Monitoring Type Description	VARCHAR2(60)	This value describes the burglar monitoring type.
Staging	CP_BLDG	CIRCUIT_BREAKERS_FLG	Circuit Breakers Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of circuit breakers.
Warehouse	CP_BLDG	CIRCUIT_BREAKERS_FLG	Circuit Breakers Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of circuit breakers.
Staging	CP_BLDG	CONST_TYP_CD	Construction Type Code	VARCHAR2(25)	This system code describes the type of construction materials primarily used for building exterior.
Warehouse	CP_BLDG	CONST_TYP_CD	Construction Type Code	VARCHAR2(25)	This system code describes the type of construction materials primarily used for building exterior.
Warehouse	CP_BLDG	CONST_TYP_DESC	Construction Type Description	VARCHAR2(60)	This value describes the primary building exterior construction materials.
Staging	CP_BLDG	COPPER_WIRG_FLG	Copper Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of copper wiring.
Warehouse	CP_BLDG	COPPER_WIRG_FLG	Copper Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of copper wiring.
Warehouse	CP_BLDG	CP_BLDG_ID	Commercial Property Building Identifier	NUMBER (22, 0)	This system generated number identifies the property instance.
Staging	CP_BLDG	CP_BLDG_NAT_KEY	Commercial Property Building Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the building.
Warehouse	CP_BLDG	CP_BLDG_NAT_KEY	Commercial Property Building Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the building.
Staging	CP_BLDG	CP_BLDG_UDF_CD_1	Commercial Property Building User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first commercial property building user defined field.
Warehouse	CP_BLDG	CP_BLDG_UDF_CD_1	Commercial Property Building User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first commercial property building user defined field.
Staging	CP_BLDG	CP_BLDG_UDF_CD_2	Commercial Property Building User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second commercial property building user defined field.
Warehouse	CP_BLDG	CP_BLDG_UDF_CD_2	Commercial Property Building User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second commercial property building user defined field.
Staging	CP_BLDG	CP_BLDG_UDF_CD_3	Commercial Property Building User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third commercial property building user defined field.
Warehouse	CP_BLDG	CP_BLDG_UDF_CD_3	Commercial Property Building User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third commercial property building user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CP_BLDG	CP_BLDG_UDF_CD_4	Commercial Property Building User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth commercial property building user defined field.
Warehouse	CP_BLDG	CP_BLDG_UDF_CD_4	Commercial Property Building User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth commercial property building user defined field.
Staging	CP_BLDG	CP_BLDG_UDF_CD_5	Commercial Property Building User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth commercial property building user defined field.
Warehouse	CP_BLDG	CP_BLDG_UDF_CD_5	Commercial Property Building User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth commercial property building user defined field.
Warehouse	CP_BLDG	CP_BLDG_UDF_DESC_1	Commercial Property Building User Defined Field Description 1	VARCHAR2(60)	This value describes the first commercial building user defined field.
Warehouse	CP_BLDG	CP_BLDG_UDF_DESC_2	Commercial Property Building User Defined Field Description 2	VARCHAR2(60)	This value describes the second commercial building user defined field.
Warehouse	CP_BLDG	CP_BLDG_UDF_DESC_3	Commercial Property Building User Defined Field Description 3	VARCHAR2(60)	This value describes the third commercial building user defined field.
Warehouse	CP_BLDG	CP_BLDG_UDF_DESC_4	Commercial Property Building User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth commercial building user defined field.
Warehouse	CP_BLDG	CP_BLDG_UDF_DESC_5	Commercial Property Building User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth commercial building user defined field.
Staging	CP_BLDG	CTY_LMTS_CD	City Limits Code	VARCHAR2(25)	This system code describes if a building is located within or outside city limit boundary.
Warehouse	CP_BLDG	CTY_LMTS_CD	City Limits Code	VARCHAR2(25)	This system code describes if a building is located within or outside city limit boundary.
Warehouse	CP_BLDG	CTY_LMTS_DESC	City Limits Description	VARCHAR2(60)	This value describes the city limits.
Warehouse	CP_BLDG	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the building is currently applicable.
Staging	CP_BLDG	CUR_YR_PROP_INCOME	Current Year Property Income	NUMBER (14,3)	This number represents the total amount of income from activities at the insured building during the current year.
Warehouse	CP_BLDG	CUR_YR_PROP_INCOME	Current Year Property Income	NUMBER (14, 3)	This number represents the total amount of income from activities at the insured building during the current year.
Staging	CP_BLDG	DIST_TO_FIRE_HYDRANT	Distance to Fire Hydrant	NUMBER (14,3)	This number represents the number of distance units (feet/meters) from building to nearest fire hydrant location.
Warehouse	CP_BLDG	DIST_TO_FIRE_HYDRANT	Distance to Fire Hydrant	NUMBER (14, 3)	This number represents the number of distance units (feet/meters) from building to nearest fire hydrant location.
Staging	CP_BLDG	DIST_TO_FIRE_STATION	Distance to Fire Station	NUMBER (14,3)	This number represents the number of distance units (miles/km) from building to nearest fire station location.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CP_BLDG	DIST_TO_FIRE_STATION	Distance to Fire Station	NUMBER (14, 3)	This number represents the number of distance units (miles/km) from building to nearest fire station location.
Staging	CP_BLDG	BLDG_AREA	Building Area	NUMBER (14,3)	This number represents the area measurement of floor contained.
Warehouse	CP_BLDG	BLDG_AREA	Building Area	NUMBER (14, 3)	This number represents the area measurement of floor contained.
Staging	CP_BLDG	BLDG_COND_CD	Building Condition Code	VARCHAR2(25)	This system code indicates the building condition.
Warehouse	CP_BLDG	BLDG_COND_CD	Building Condition Code	VARCHAR2(25)	This system code indicates the building condition.
Warehouse	CP_BLDG	BLDG_COND_DESC	Building Condition Description	VARCHAR2(60)	This value represents the description of the building condition.
Staging	CP_BLDG	BLDG_TYP_CD	Building Type Code	VARCHAR2(25)	This system code indicates the building type.
Warehouse	CP_BLDG	BLDG_TYP_CD	Building Type Code	VARCHAR2(25)	This system code indicates the building type.
Warehouse	CP_BLDG	BLDG_TYP_DESC	Building Type Description	VARCHAR2(60)	This value describes the building type.
Staging	CP_BLDG	ELEC_UPDT_TYP_CD	Electrical Update Type Code	VARCHAR2(25)	This system code indicates changes to electrical system after the building's original construction.
Warehouse	CP_BLDG	ELEC_UPDT_TYP_CD	Electrical Update Type Code	VARCHAR2(25)	This system code indicates changes to electrical system after the building's original construction.
Warehouse	CP_BLDG	ELEC_UPDT_TYP_DESC	Electrical Update Type Description	VARCHAR2(60)	This value describes electrical update type.
Staging	CP_BLDG	ELEC_UPDT_YR	Electrical Update Year	CHAR(4)	This value represents the calendar year of the last update to the building electrical system.
Warehouse	CP_BLDG	ELEC_UPDT_YR	Electrical Update Year	CHAR(4)	This value represents the calendar year of the last update to the building electrical system.
Warehouse	CP_BLDG	END_DT	End Date	DATE	This calendar date represents when the building is no longer included in policy coverages.
Staging	CP_BLDG	FIRE_DSTRCT_CD	Fire District Code	VARCHAR2(25)	This system code describes the fire department response district assigned to a building location.
Warehouse	CP_BLDG	FIRE_DSTRCT_CD	Fire District Code	VARCHAR2(25)	This system code describes the fire department response district assigned to a building location.
Warehouse	CP_BLDG	FIRE_DSTRCT_DESC	Fire District Description	VARCHAR2(60)	This value represents the description of the fire district responsible for building location.
Staging	CP_BLDG	FIRE_EXTINGUISHER_FLG	Fire Extinguisher Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fire extinguisher.
Warehouse	CP_BLDG	FIRE_EXTINGUISHER_FLG	Fire Extinguisher Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fire extinguisher.
Staging	CP_BLDG	FIRE_MONITOR_TYP_CD	Fire Monitoring Type Code	VARCHAR2(25)	This system code indicates the type of fire monitoring alarm used at building.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CP_BLDG	FIRE_MONITOR_TYP_CD	Fire Monitoring Type Code	VARCHAR2(25)	This system code indicates the type of fire monitoring alarm used at building.
Warehouse	CP_BLDG	FIRE_MONITOR_TYP_DESC	Fire Monitoring Type Description	VARCHAR2(60)	This value describes the fire monitoring type code.
Staging	CP_BLDG	FIRE_PROT_CLASS_CD	Fire Protection Class Code	VARCHAR2(25)	This system code describes the fire protection services available at building location.
Warehouse	CP_BLDG	FIRE_PROT_CLASS_CD	Fire Protection Class Code	VARCHAR2(25)	This system code describes the fire protection services available at building location.
Warehouse	CP_BLDG	FIRE_PROT_CLASS_DESC	Fire Protection Class Description	VARCHAR2(60)	This value describes the fire monitoring type code.
Staging	CP_BLDG	FNDN_TYP_CD	Foundation Type Code	VARCHAR2(25)	This system code indicates the construction method used to construct building foundation.
Warehouse	CP_BLDG	FNDN_TYP_CD	Foundation Type Code	VARCHAR2(25)	This system code indicates the construction method used to construct building foundation.
Warehouse	CP_BLDG	FNDN_TYP_DESC	Foundation Type Description	VARCHAR2(60)	This value describes the construction method used to construct the building foundation.
Staging	CP_BLDG	FUSES_FLG	Fuses Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fuses.
Warehouse	CP_BLDG	FUSES_FLG	Fuses Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fuses.
Staging	CP_BLDG	GAS_UPDT_TYP_CD	Gas Update Type Code	VARCHAR2(25)	This system code indicates changes to gas system after the building's original construction.
Warehouse	CP_BLDG	GAS_UPDT_TYP_CD	Gas Update Type Code	VARCHAR2(25)	This system code indicates changes to gas system after the building's original construction.
Warehouse	CP_BLDG	GAS_UPDT_TYP_DESC	Gas Update Type Description	VARCHAR2(60)	This value describes the gas update type.
Staging	CP_BLDG	GAS_UPDT_YR	Gas Update Year	CHAR(4)	This value represents the calendar year of the last update to the building gas system.
Warehouse	CP_BLDG	GAS_UPDT_YR	Gas Update Year	CHAR(4)	This value represents the calendar year of the last update to the building gas system.
Staging	CP_BLDG	HEAT_UPDT_TYP_CD	Heating Update Type Code	VARCHAR2(25)	This system code indicates changes to heating system after the building's original construction.
Warehouse	CP_BLDG	HEAT_UPDT_TYP_CD	Heating Update Type Code	VARCHAR2(25)	This system code indicates changes to heating system after the building's original construction.
Warehouse	CP_BLDG	HEAT_UPDT_TYP_DESC	Heating Update Type Description	VARCHAR2(60)	This value describes heating update type.
Staging	CP_BLDG	HEAT_UPDT_YR	Heating Update Year	CHAR(4)	This value represents the calendar year of the last update to the building heating system.
Warehouse	CP_BLDG	HEAT_UPDT_YR	Heating Update Year	CHAR(4)	This value represents the calendar year of the last update to the building heating system.
Staging	CP_BLDG	KNOB_TUBE_WIRG_FLG	Knob And Tube Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of knob and tube wiring.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CP_BLDG	KNOB_TUBE_WIRG_FLG	Knob And Tube Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of knob and tube wiring.
Warehouse	CP_BLDG	LOC_ADDR_ID	Location Address Identifier	NUMBER (22, 0)	This system generated number identifies the location address instance for commercial property building.
Staging	CP_BLDG	LOC_NUM	Location Number	NUMBER (22,0)	This number identifies the location of a building.
Warehouse	CP_BLDG	LOC_NUM	Location Number	NUMBER (22, 0)	This number identifies the location of a building.
Staging	CP_BLDG	MKT_VAL	Market Value	NUMBER (14,3)	This number represents the average price of similar buildings recently sold in same real estate market.
Warehouse	CP_BLDG	MKT_VAL	Market Value	NUMBER (14, 3)	This number represents the average price of similar buildings recently sold in same real estate market.
Staging	CP_BLDG	NM_OF_OWNER	Name of Owner	VARCHAR2(170)	This value represents the name of the building's owner.
Warehouse	CP_BLDG	NM_OF_OWNER	Name of Owner	VARCHAR2(170)	This value represents the name of the building's owner.
Staging	CP_BLDG	NUM_COML_OCCUPANTS	Number Of Commercial Occupants	NUMBER (22,0)	This number represents the count of all commercial occupants in all units of a building.
Warehouse	CP_BLDG	NUM_COML_OCCUPANTS	Number Of Commercial Occupants	NUMBER (22, 0)	This number represents the count of all commercial occupants of a building.
Staging	CP_BLDG	NUM_ELEC_SYS_AMPS	Number Of Electrical System Amps	NUMBER (22,0)	This number represents the electrical current capacity of a building's electrical system.
Warehouse	CP_BLDG	NUM_ELEC_SYS_AMPS	Number Of Electrical System Amps	NUMBER (22, 0)	This number represents the electrical current capacity of a building's electrical system.
Staging	CP_BLDG	NUM_FMLYS	Number Of Families	NUMBER (22,0)	This number represents the count of individual family units in single commercial building. For example, a duplex would have 2 families.
Warehouse	CP_BLDG	NUM_FMLYS	Number Of Families	NUMBER (22, 0)	This number represents the count of individual family units in single commercial building. For example, a duplex would have 2 families.
Staging	CP_BLDG	NUM_STORIES	Number Of Stories	NUMBER (22,0)	This number represents the count of building floor levels.
Warehouse	CP_BLDG	NUM_STORIES	Number Of Stories	NUMBER (22, 0)	This number represents the count of building floor levels.
Staging	CP_BLDG	OCPCY_TYP_CD	Occupancy Type Code	VARCHAR2(25)	This system code indicates the type of occupants of the building.
Warehouse	CP_BLDG	OCPCY_TYP_CD	Occupancy Type Code	VARCHAR2(25)	This system code indicates the type of occupants of the building.
Warehouse	CP_BLDG	OCPCY_TYP_DESC	Occupancy Type Description	VARCHAR2(60)	This value describes the primary occupant type of a building.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CP_BLDG	PLUMBING_UPDT_TYP_CD	Plumbing Update Type Code	VARCHAR2(25)	This system code indicates changes to plumbing system after the building's original construction.
Warehouse	CP_BLDG	PLUMBING_UPDT_TYP_CD	Plumbing Update Type Code	VARCHAR2(25)	This system code indicates changes to gas system after the building's original construction.
Warehouse	CP_BLDG	PLUMBING_UPDT_TYP_DESC	Plumbing Update Type Description	VARCHAR2(60)	This value describes the plumbing update type.
Staging	CP_BLDG	PLUMBING_UPDT_YR	Plumbing Update Year	CHAR(4)	This value represents the calendar year of the last update to the building's plumbing system.
Warehouse	CP_BLDG	PLUMBING_UPDT_YR	Plumbing Update Year	CHAR(4)	This value represents the calendar year of the last update to the building's plumbing system.
Staging	CP_BLDG	PRIM_HEAT_TYP_CD	Primary Heating Type Code	VARCHAR2(25)	This system code describes the building's primary source of heat.
Warehouse	CP_BLDG	PRIM_HEAT_TYP_CD	Primary Heating Type Code	VARCHAR2(25)	This system code describes the building's primary source of heat.
Warehouse	CP_BLDG	PRIM_HEAT_TYP_DESC	Primary Heating Type Description	VARCHAR2(60)	This value describes the building's primary source of heat.
Staging	CP_BLDG	PROP_LOT_SIZE	Property Lot Size	NUMBER (14,3)	This number represents the area measurement of the land with.
Warehouse	CP_BLDG	PROP_LOT_SIZE	Property Lot Size	NUMBER (14, 3)	This number represents the area measurement of the land with.
Staging	CP_BLDG	PURCH_DT	Purchase Date	DATE	This calendar date represents when the insured purchased the building.
Warehouse	CP_BLDG	PURCH_DT	Purchase Date	DATE	This calendar date represents when the insured purchased the building.
Staging	CP_BLDG	PURCH_PRICE	Purchase Price	NUMBER (14,3)	This number represents the monetary amount paid when building was purchased.
Warehouse	CP_BLDG	PURCH_PRICE	Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when building was purchased.
Staging	CP_BLDG	ROOF_MATL_CD	Roofing Material Code	VARCHAR2(25)	This system code identifies the material used to construct the building's roof.
Warehouse	CP_BLDG	ROOF_MATL_CD	Roofing Material Code	VARCHAR2(25)	This system code identifies the material used to construct the building's roof.
Warehouse	CP_BLDG	ROOF_MATL_DESC	Roofing Material Description	VARCHAR2(60)	This value describes the roof material code.
Staging	CP_BLDG	ROOF_UPDT_TYP_CD	Roofing Update Type Code	VARCHAR2(25)	This system code indicates the type or roofing updates made since the building's original construction.
Warehouse	CP_BLDG	ROOF_UPDT_TYP_CD	Roofing Update Type Code	VARCHAR2(25)	This system code indicates the type or roofing updates made since the building's original construction.
Warehouse	CP_BLDG	ROOF_UPDT_TYP_DESC	Roofing Update Type Description	VARCHAR2(60)	This value describes the roof update type code.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CP_BLDG	ROOF_UPDT_YR	Roofing Update Year	CHAR(4)	This value represents the calendar year of the last update to the building's roofing materials.
Warehouse	CP_BLDG	ROOF_UPDT_YR	Roofing Update Year	CHAR(4)	This value represents the calendar year of the last update to the building's roofing materials.
Staging	CP_BLDG	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the commercial property building (also known as commercial property building) with a specific transaction.
Staging	CP_BLDG	SCND_HEAT_TYP_CD	Secondary Heating Type Code	VARCHAR2(25)	This system code describes the building's secondary source of heat.
Warehouse	CP_BLDG	SCND_HEAT_TYP_CD	Secondary Heating Type Code	VARCHAR2(25)	This system code describes the building's secondary source of heat.
Warehouse	CP_BLDG	SCND_HEAT_TYP_DESC	Secondary Heating Type Description	VARCHAR2(60)	This value describes the building's secondary source of heat.
Staging	CP_BLDG	UNDER_CONST_TYP_CD	Under Construction Type Code	VARCHAR2(25)	This system code indicates active construction activities on the building.
Warehouse	CP_BLDG	UNDER_CONST_TYP_CD	Under Construction Type Code	VARCHAR2(25)	This system code indicates active construction activities on the building.
Warehouse	CP_BLDG	UNDER_CONST_TYP_DESC	Under Construction Type Description	VARCHAR2(60)	This value describes the active construction activities.
Staging	CP_BLDG	WIRG_UPDT_TYP_CD	Wiring Update Type Code	VARCHAR2(25)	This system code identifies the type of update to wiring system.
Warehouse	CP_BLDG	WIRG_UPDT_TYP_CD	Wiring Update Type Code	VARCHAR2(25)	This system code identifies the type of update to wiring system.
Warehouse	CP_BLDG	WIRG_UPDT_TYP_DESC	Wiring Update Type Description	VARCHAR2(60)	This value describes the changes made to wiring system since original construction.
Staging	CP_BLDG	WIRG_UPDT_YR	Wiring Update Year	CHAR(4)	This value represents the calendar year of the last update to the building wiring system.
Warehouse	CP_BLDG	WIRG_UPDT_YR	Wiring Update Year	CHAR(4)	This value represents the calendar year of the last update to the building wiring system.
Staging	CP_BLDG	YR_BUILT	Year Built	CHAR(4)	This value represents the calendar year that the building was constructed.
Warehouse	CP_BLDG	YR_BUILT	Year Built	CHAR(4)	This value represents the calendar year that the building was constructed.
Datamart	CP_BLDG_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage.
Datamart	CP_BLDG_DIM	CP_BLDG_ALUMINUM_WIRG_FLG	Commercial Property Building Aluminum Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of aluminum wiring.
Datamart	CP_BLDG_DIM	CP_BLDG_AREA	Commercial Property Building Area	NUMBER (14, 3)	This number represents the area measurement of floor contained.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CP_BLDG_DIM	CP_BLDG_BLDG_USE	Commercial Property Building Building Use	VARCHAR2(60)	This value represents the classification detailing the activities occurring at a building.
Datamart	CP_BLDG_DIM	CP_BLDG_BSMT_AREA	Commercial Property Building Basement Area	NUMBER (14, 3)	This number represents the total area measurement of all the basements in this building.
Datamart	CP_BLDG_DIM	CP_BLDG_BURGLAR_MONITOR_TYP	Commercial Property Building Burglar Monitoring Type	VARCHAR2(60)	This value describes the attributes of a burglar alarm in use.
Datamart	CP_BLDG_DIM	CP_BLDG_CIRCUIT_BREAKERS_FLG	Commercial Property Building Circuit Breakers Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of circuit breakers.
Datamart	CP_BLDG_DIM	CP_BLDG_COND	Commercial Property Building Condition	VARCHAR2(60)	This value represents the classification detailing the maintenance condition of a building.
Datamart	CP_BLDG_DIM	CP_BLDG_CONST_TYP	Commercial Property Building Construction Type	VARCHAR2(60)	This value describes the building's primary exterior construction materials.
Datamart	CP_BLDG_DIM	CP_BLDG_COPPER_WIRG_FLG	Commercial Property Building Copper Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of copper wiring.
Datamart	CP_BLDG_DIM	CP_BLDG_CTY_LMTS_CD	Commercial Property Building City Limits Code	VARCHAR2(60)	This system code describes if a building is located within or outside city limit boundary.
Datamart	CP_BLDG_DIM	CP_BLDG_CUR_YR_PROP_INCOME	Commercial Property Building Current Year Property Income	NUMBER (14, 3)	This number represents the total amount of income from activities at the insured building during the current year.
Datamart	CP_BLDG_DIM	CP_BLDG_DIST_TO_FIRE_HYDRANT	Commercial Property Building Distance to Fire Hydrant	NUMBER (14, 3)	This number represents the distance units (feet/ meters) from building to nearest fire hydrant location.
Datamart	CP_BLDG_DIM	CP_BLDG_DIST_TO_FIRE_STATION	Commercial Property Building Distance to Fire Station	NUMBER (14, 3)	This number represents the distance units (miles/ kilometers) from building to nearest fire station location.
Datamart	CP_BLDG_DIM	CP_BLDG_ELEC_UPDT_TYP	Commercial Property Building Electrical Update Type	VARCHAR2(60)	This value represents the classification that describes changes to electrical system after the building's original construction.
Datamart	CP_BLDG_DIM	CP_BLDG_ELEC_UPDT_YR	Commercial Property Building Electrical Update Year	CHAR(4)	This value represents the calendar year of the last update to the building electrical system.
Datamart	CP_BLDG_DIM	CP_BLDG_FIRE_DSTRCT	Commercial Property Building Fire District	VARCHAR2(60)	This value represents the fire department response district assigned to a building location.
Datamart	CP_BLDG_DIM	CP_BLDG_FIRE_EXTINGUISHER_FLG	Commercial Property Building Fire Extinguisher Flag	CHAR(1)	This value represents based on the yes/no indicator that a fire extinguisher is present at covered building.
Datamart	CP_BLDG_DIM	CP_BLDG_FIRE_MONITOR_TYP	Commercial Property Building Fire Monitoring Type	VARCHAR2(60)	This value represents the attributes of fire monitoring alarm used at building.
Datamart	CP_BLDG_DIM	CP_BLDG_FIRE_PROT_CLASS	Commercial Property Building Fire Protection Class	VARCHAR2(60)	This system code describes the fire protection services available at building location.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CP_BLDG_DIM	CP_BLDG_FNDN_TYP	Commercial Property Building Foundation Type	VARCHAR2(60)	This value represents the construction method used to construct building foundation.
Datamart	CP_BLDG_DIM	CP_BLDG_FUSES_FLG	Commercial Property Building Fuses Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fuses.
Datamart	CP_BLDG_DIM	CP_BLDG_GAS_UPDT_TYP	Commercial Property Building Gas Update Type	VARCHAR2(60)	This value represents the calendar year of last update of the building gas system.
Datamart	CP_BLDG_DIM	CP_BLDG_GAS_UPDT_YR	Commercial Property Building Gas Update Year	CHAR(4)	This value represents the calendar year of the last update to the building gas system.
Datamart	CP_BLDG_DIM	CP_BLDG_GEOG_BNDRY_UDF_1	Commercial Property Building Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first commercial building geographic boundary user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_GEOG_BNDRY_UDF_2	Commercial Property Building Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second commercial building geographic boundary user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_GEOG_BNDRY_UDF_3	Commercial Property Building Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third commercial building geographic boundary user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_GEOG_BNDRY_UDF_4	Commercial Property Building Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth commercial building geographic boundary user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_GEOG_BNDRY_UDF_5	Commercial Property Building Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth commercial building geographic boundary user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_HEAT_UPDT_TYP	Commercial Property Building Heating Update Type	VARCHAR2(60)	This value represents the changes to heating system after the building's original construction.
Datamart	CP_BLDG_DIM	CP_BLDG_HEAT_UPDT_YR	Commercial Property Building Heating Update Year	CHAR(4)	This value represents the calendar year of the last update to the building heating system.
Datamart	CP_BLDG_DIM	CP_BLDG_ID	Commercial Property Building Identifier	NUMBER (22, 0)	This system generated number identifies the property instance.
Datamart	CP_BLDG_DIM	CP_BLDG_KNOB_TUBE_WIRG_FLG	Commercial Property Building Knob and Tube Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of knob and tube wiring.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_CNTY	Commercial Property Building Location County	VARCHAR2(60)	This value identifies the county where building is located.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_CTRY	Commercial Property Building Location Country	VARCHAR2(60)	This value identifies the country where building is located.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_CTY	Commercial Property Building Location City	VARCHAR2(32)	This value identifies the city where building is located.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_DSTRCT	Commercial Property Building Location District	VARCHAR2(60)	This value represents the district where building is located.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_LATITUDE	Commercial Property Building Location Latitude	VARCHAR2(11)	This value represents the latitude where building is located.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_LONGITUDE	Commercial Property Building Location Longitude	VARCHAR2(11)	This value represents the longitude where building is located.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_NUM	Commercial Property Building Location Number	NUMBER (22, 0)	This number identifies the commercial property building (also known as commercial property building) location number.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_PSTL_CD	Commercial Property Building Location Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_PSTL_CD_PRFX	Commercial Property Building Location Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_PSTL_SUB_CD	Commercial Property Building Location Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_REGION	Commercial Property Building Location Region	VARCHAR2(60)	This value identifies the geographic region associated with building location.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_STATE	Commercial Property Building Location State	VARCHAR2(60)	This value identifies the state associated with building location.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_TAX_LOC_ID	Commercial Property Building Location Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier of the building location.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_TERR	Commercial Property Building Location Territory	VARCHAR2(60)	This value represents the territory where building is located.
Datamart	CP_BLDG_DIM	CP_BLDG_MKT_VAL	Commercial Property Building Market Value	NUMBER (14, 3)	This number represents the average price of similar buildings recently sold in same real estate market.
Datamart	CP_BLDG_DIM	CP_BLDG_NAT_KEY	Commercial Property Building Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the building.
Datamart	CP_BLDG_DIM	CP_BLDG_NM_OF_OWNER	Commercial Property Building Number of Owners	VARCHAR2(170)	This value represents the total count of owners of the building.
Datamart	CP_BLDG_DIM	CP_BLDG_NUM_COML_OCCUPANTS	Commercial Property Building Number of Commercial Occupants	NUMBER (22, 0)	This number represents the count of commercial occupants contained in all units of the building.
Datamart	CP_BLDG_DIM	CP_BLDG_NUM_ELEC_SYS_AMPS	Commercial Property Building Number of Electrical System Amps	NUMBER (22, 0)	This number represents the electrical current capacity of electrical system.
Datamart	CP_BLDG_DIM	CP_BLDG_NUM_FMLYS	Commercial Property Building Number of Families	NUMBER (22, 0)	This number represents the count of individual family units in single building. For example, a duplex would have 2 families.
Datamart	CP_BLDG_DIM	CP_BLDG_NUM_STORIES	Commercial Property Building Number of Stories	NUMBER (22, 0)	This number represents the count of building floor levels contained.
Datamart	CP_BLDG_DIM	CP_BLDG_OCPCY_TYP	Commercial Property Building Occupancy Type	VARCHAR2(60)	This value represents the attributes of occupants of the building. For example, owner and tenant occupants.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CP_BLDG_DIM	CP_BLDG_PLUMBING_UPDT_TYP	Commercial Property Building Plumbing Update Type	VARCHAR2(60)	This value represents the classification detailing changes to plumbing system after the building's original construction.
Datamart	CP_BLDG_DIM	CP_BLDG_PLUMBING_UPDT_YR	Commercial Property Building Plumbing Update Year	CHAR(4)	This value represents the calendar year of the last update to the building plumbing system.
Datamart	CP_BLDG_DIM	CP_BLDG_PRIM_HEAT_TYP	Commercial Property Building Primary Heating Type	VARCHAR2(60)	This value represents the classification of the building's primary source of heat.
Datamart	CP_BLDG_DIM	CP_BLDG_PROP_LOT_SIZE	Commercial Property Building Property Lot Size	NUMBER (14, 3)	This number represents the total area measurement of the land with.
Datamart	CP_BLDG_DIM	CP_BLDG_PURCH_DT_ID	Commercial Property Building Purchase Date Identifier	DATE	This calendar date represents building purchase date instance.
Datamart	CP_BLDG_DIM	CP_BLDG_PURCH_PRICE	Commercial Property Building Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when commercial building was purchased.
Datamart	CP_BLDG_DIM	CP_BLDG_ROOF_MATL	Commercial Property Building Roofing Material	VARCHAR2(60)	This value represents the roofing material used on the building roof.
Datamart	CP_BLDG_DIM	CP_BLDG_ROOF_UPDT_TYP	Commercial Property Building Roofing Update Type	VARCHAR2(60)	This value represents the classification detailing changes to roofing materials after the building's original construction.
Datamart	CP_BLDG_DIM	CP_BLDG_ROOF_UPDT_YR	Commercial Property Building Roofing Update Year	CHAR(4)	This value represents the calendar year of the last update to the building roofing materials.
Datamart	CP_BLDG_DIM	CP_BLDG_SCND_HEAT_TYP	Commercial Property Building Secondary Heat Type	VARCHAR2(60)	This value represents the classification of the secondary source of heat for commercial building.
Datamart	CP_BLDG_DIM	CP_BLDG_TYP	Commercial Property Building Type	VARCHAR2(60)	This value represents the classification that identifies the building unit construction. For example, single-family, multi-family, warehouse, etc.
Datamart	CP_BLDG_DIM	CP_BLDG_UDF_1	Commercial Property Building User Defined Field 1	VARCHAR2(60)	This value describes the first commercial building user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_UDF_2	Commercial Property Building User Defined Field 2	VARCHAR2(60)	This value describes the second commercial building user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_UDF_3	Commercial Property Building User Defined Field 3	VARCHAR2(60)	This value describes the third commercial building user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_UDF_4	Commercial Property Building User Defined Field 4	VARCHAR2(60)	This value describes the fourth commercial building user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_UDF_5	Commercial Property Building User Defined Field 5	VARCHAR2(60)	This value describes the fifth commercial building user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_UNDER_CONST_TYP	Commercial Property Building Under Construction Type	VARCHAR2(60)	This system code indicates active construction activities on the building.
Datamart	CP_BLDG_DIM	CP_BLDG_WIRG_UPDT_TYP	Commercial Property Building Wiring Update Type	VARCHAR2(60)	This value represents the classification detailing changes to wiring system after the building's original construction.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CP_BLDG_DIM	CP_BLDG_WIRG_UPDT_YR	Commercial Property Building Wiring Update Year	CHAR(4)	This value represents the calendar year of the last update to the building wiring system.
Datamart	CP_BLDG_DIM	CP_BLDG_YR_BUILT	Commercial Property Building Year Built	CHAR(4)	This value represents the calendar year that commercial property building (also known as commercial property building) was constructed.
Datamart	CP_BLDG_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the commercial property building (also known as commercial property building) is currently included in policy coverages.
Datamart	CP_BLDG_DIM	END_DT	End Date	DATE	This calendar date represents when the building is no longer included in policy coverages.
Datamart	CP_FACT	CP_BLDG_ID	Commercial Property Building Identifier	NUMBER (22, 0)	This system generated number identifies the commercial property building (also known as commercial property building) instance.
Datamart	CP_FACT	CP_FACT_ID	Commercial Property Fact Identifier	NUMBER (22, 0)	This system generated number identifies the commercial property fact instance.
Staging	CURR_CNV	CURR_CNV_DT	Currency Conversion Date	DATE	This calendar date represents when currency was converted to another currency.
Staging	CURR_CNV	CURR_CNV_FROM_CD	Currency Converted From Code	VARCHAR2(25)	This system code identifies the original currency type that was converted.
Staging	CURR_CNV	CURR_CNV_RATE	Currency Conversion Rate	NUMBER (22,7)	This number represents the rate at which a currency is converted to another currency.
Staging	CURR_CNV	CURR_CNV_TO_CD	Currency Converted To Code	VARCHAR2(25)	This system code identifies currency converted to.
Warehouse	DC	BEGIN_DT	Begin Date	DATE	This calendar date represents when the distribution channel applies.
Warehouse	DC	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the distribution channel is currently applicable.
Warehouse	DC	DC_ID	Distribution Channel Identifier	NUMBER (22, 0)	This system generated number identifies the distribution channel instance.
Staging	DC	DC_NAT_KEY	Distribution Channel Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the distribution channel.
Warehouse	DC	DC_NAT_KEY	Distribution Channel Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the distribution channel.
Staging	DC	DC_NM	Distribution Channel Name	VARCHAR2(60)	This value represents distribution channel's name.
Warehouse	DC	DC_NM	Distribution Channel Name	VARCHAR2(60)	This value represents distribution channel's name.
Staging	DC	DC_NUM	Distribution Channel Number	VARCHAR2(10)	This value represents the number or other identifier assigned to the distribution channel.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	DC	DC_NUM	Distribution Channel Number	VARCHAR2(10)	This value represents the number or other identifier assigned to the distribution channel.
Staging	DC	DC_TYP_CD	Distribution Channel Type Code	VARCHAR2(25)	This system code identifies distribution channel type.
Warehouse	DC	DC_TYP_CD	Distribution Channel Type Code	VARCHAR2(25)	This system code identifies the distribution channel type.
Warehouse	DC	DC_TYP_DESC	Distribution Channel Type Description	VARCHAR2(60)	This value describes the distribution channel type.
Staging	DC	DC_UDF_CD_1	Distribution Channel User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first distribution channel user defined field.
Warehouse	DC	DC_UDF_CD_1	Distribution Channel User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first distribution channel user defined field.
Staging	DC	DC_UDF_CD_2	Distribution Channel User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second distribution channel user defined field.
Warehouse	DC	DC_UDF_CD_2	Distribution Channel User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second distribution channel user defined field.
Staging	DC	DC_UDF_CD_3	Distribution Channel User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third distribution channel user defined field.
Warehouse	DC	DC_UDF_CD_3	Distribution Channel User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third distribution channel user defined field.
Staging	DC	DC_UDF_CD_4	Distribution Channel User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth distribution channel user defined field.
Warehouse	DC	DC_UDF_CD_4	Distribution Channel User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth distribution channel user defined field.
Staging	DC	DC_UDF_CD_5	Distribution Channel User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth distribution channel user defined field.
Warehouse	DC	DC_UDF_CD_5	Distribution Channel User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth distribution channel user defined field.
Warehouse	DC	DC_UDF_DESC_1	Distribution Channel User Defined Field Description 1	VARCHAR2(60)	This value describes the first distribution channel user defined field.
Warehouse	DC	DC_UDF_DESC_2	Distribution Channel User Defined Field Description 2	VARCHAR2(60)	This value describes the second distribution channel user defined field.
Warehouse	DC	DC_UDF_DESC_3	Distribution Channel User Defined Field Description 3	VARCHAR2(60)	This value describes the third distribution channel user defined field.
Warehouse	DC	DC_UDF_DESC_4	Distribution Channel User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth distribution channel user defined field.
Warehouse	DC	DC_UDF_DESC_5	Distribution Channel User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth distribution channel user defined field.
Warehouse	DC	END_DT	End Date	DATE	This calendar date represents when the distribution channel is no longer valid.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	DC	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the distribution channel with a specific transaction.
Staging	DC	TYPICAL_COMM_RATE	Typical Commission Rate	NUMBER (6,5)	This number represents the typical commission rate for distribution channel.
Warehouse	DC	TYPICAL_COMM_RATE	Typical Commission Rate	NUMBER (6, 5)	This number represents the rate of commission given to a producer for a sale of a policy unless the commission rate is overridden.
Datamart	DC_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the distribution channel applies.
Datamart	DC_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the distribution channel is currently applicable.
Datamart	DC_DIM	DC_ID	Distribution Channel Identifier	NUMBER (22, 0)	This system generated number identifies the distribution channel instance.
Datamart	DC_DIM	DC_NAT_KEY	Distribution Channel Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the distribution channel.
Datamart	DC_DIM	DC_NM	Distribution Channel Name	VARCHAR2(60)	This value represents the full name of the distribution channel.
Datamart	DC_DIM	DC_NUM	Distribution Channel Number	VARCHAR2(10)	This value represents the number or other identifier assigned to the distribution channel.
Datamart	DC_DIM	DC_TYP	Distribution Channel Type	VARCHAR2(60)	This value represents the classification of the activities of a distribution channel.
Datamart	DC_DIM	DC_UDF_1	Distribution Channel User Defined Field 1	VARCHAR2(60)	This value describes the first distribution channel user defined field.
Datamart	DC_DIM	DC_UDF_2	Distribution Channel User Defined Field 2	VARCHAR2(60)	This value describes the second distribution channel user defined field.
Datamart	DC_DIM	DC_UDF_3	Distribution Channel User Defined Field 3	VARCHAR2(60)	This value describes the third distribution channel user defined field.
Datamart	DC_DIM	DC_UDF_4	Distribution Channel User Defined Field 4	VARCHAR2(60)	This value describes the fourth distribution channel user defined field.
Datamart	DC_DIM	DC_UDF_5	Distribution Channel User Defined Field 5	VARCHAR2(60)	This value describes the fifth distribution channel user defined field.
Datamart	DC_DIM	END_DT	End Date	DATE	This calendar date represents when the distribution channel is no longer valid.
Datamart	DC_DIM	TYPICAL_COMM_RATE	Typical Commission Rate	NUMBER (6, 5)	This number represents the rate of commission given to a producer for a sale of a policy unless the commission rate is overridden.
Warehouse	DED	BEGIN_DT	Begin Date	DATE	This calendar date represents when the deductible applies.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	DED	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the deductible is currently applicable.
Staging	DED	DED	Deductible	VARCHAR2(10)	This value represents the monetary amount of a claim detailed in policy contract as not covered by the insurer for a covered risk loss.
Warehouse	DED	DED	Deductible	VARCHAR2(10)	This value represents the monetary amount of a claim detailed in policy contract as not covered by the insurer for a covered risk loss.
Staging	DED	DED_APPLIES_TO_CD	Deductible Applies To Code	VARCHAR2(25)	This system code identifies to what coverage the deductible applies.
Warehouse	DED	DED_APPLIES_TO_CD	Deductible Applies To Code	VARCHAR2(25)	This system code identifies to what coverage the deductible applies.
Warehouse	DED	DED_APPLIES_TO_DESC	Deductible Applies to Description	VARCHAR2(60)	This value describes to what coverage the deductible applies.
Staging	DED	DED_BASIS_CD	Deductible Basis Code	VARCHAR2(25)	This system code represents the basis applied to determine the deductible.
Warehouse	DED	DED_BASIS_CD	Deductible Basis Code	VARCHAR2(25)	This system code represents the basis applied to determine the deductible.
Warehouse	DED	DED_BASIS_DESC	Deductible Basis Description	VARCHAR2(60)	This value describes the basis applied to determine the deductible.
Warehouse	DED	DED_ID	Deductible Identifier	NUMBER (22, 0)	This system generated number identifies the deductible instance.
Staging	DED	DED_NAT_KEY	Deductible Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the deductible.
Warehouse	DED	DED_NAT_KEY	Deductible Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the deductible.
Staging	DED	DED_TYP_CD	Deductible Type Code	VARCHAR2(25)	This system code identifies the type of deductible.
Warehouse	DED	DED_TYP_CD	Deductible Type Code	VARCHAR2(25)	This system code identifies the type of deductible.
Warehouse	DED	DED_TYP_DESC	Deductible Type Description	VARCHAR2(60)	This value describes the type of deductible.
Staging	DED	DED_UDF_CD_1	Deductible User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first deductible user defined field.
Warehouse	DED	DED_UDF_CD_1	Deductible User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first deductible user defined field.
Staging	DED	DED_UDF_CD_2	Deductible User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second deductible user defined field.
Warehouse	DED	DED_UDF_CD_2	Deductible User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second deductible user defined field.
Staging	DED	DED_UDF_CD_3	Deductible User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third deductible user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	DED	DED_UDF_CD_3	Deductible User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third deductible user defined field.
Staging	DED	DED_UDF_CD_4	Deductible User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth deductible user defined field.
Warehouse	DED	DED_UDF_CD_4	Deductible User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth deductible user defined field.
Staging	DED	DED_UDF_CD_5	Deductible User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth deductible user defined field.
Warehouse	DED	DED_UDF_CD_5	Deductible User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth deductible user defined field.
Warehouse	DED	DED_UDF_DESC_1	Deductible User Defined Field Description 1	VARCHAR2(60)	This value describes the first deductible user defined field.
Warehouse	DED	DED_UDF_DESC_2	Deductible User Defined Field Description 2	VARCHAR2(60)	This value describes the second deductible user defined field.
Warehouse	DED	DED_UDF_DESC_3	Deductible User Defined Field Description 3	VARCHAR2(60)	This value describes the third deductible user defined field.
Warehouse	DED	DED_UDF_DESC_4	Deductible User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth deductible user defined field.
Warehouse	DED	DED_UDF_DESC_5	Deductible User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth deductible user defined field.
Warehouse	DED	END_DT	End Date	DATE	This calendar date represents when the deductible is no longer valid.
Staging	DED	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the deductible with a specific transaction.
Datamart	DED_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the deductible applies.
Datamart	DED_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the deductible is currently applicable.
Datamart	DED_DIM	DED	Deductible	VARCHAR2(10)	This value represents the type of fire monitoring alarm used at dwelling.
Datamart	DED_DIM	DED_APPLIES_TO	Deductible Applies To	VARCHAR2(60)	This value represents the district where the loss occurred.
Datamart	DED_DIM	DED_BASIS	Deductible Basis	VARCHAR2(60)	This value represents the basis applied to determine the deductible.
Datamart	DED_DIM	DED_ID	Deductible Identifier	NUMBER (22, 0)	This system generated number identifies the deductible instance.
Datamart	DED_DIM	DED_NAT_KEY	Deductible Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the deductible.
Datamart	DED_DIM	DED_TYP	Deductible Type	VARCHAR2(60)	This value represents the manner in which the deducible is calculated. For example, percentage of a total coverage amount.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	DED_DIM	DED_UDF_1	Deductible User Defined Field 1	VARCHAR2(60)	This value describes the first deductible user defined field.
Datamart	DED_DIM	DED_UDF_2	Deductible User Defined Field 2	VARCHAR2(60)	This value describes the second deductible user defined field.
Datamart	DED_DIM	DED_UDF_3	Deductible User Defined Field 3	VARCHAR2(60)	This value describes the third deductible user defined field.
Datamart	DED_DIM	DED_UDF_4	Deductible User Defined Field 4	VARCHAR2(60)	This value describes the fourth deductible user defined field.
Datamart	DED_DIM	DED_UDF_5	Deductible User Defined Field 5	VARCHAR2(60)	This value describes the fifth deductible user defined field.
Datamart	DED_DIM	END_DT	End Date	DATE	This calendar date represents when the deductible is no longer valid.
Warehouse	DF_DWLNG	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage begins for the dwelling.
Staging	DF_DWLNG	CIRCUIT_BREAKERS_FLG	Circuit Breakers Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of circuit breakers.
Warehouse	DF_DWLNG	CIRCUIT_BREAKERS_FLG	Circuit Breakers Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of circuit breakers.
Staging	DF_DWLNG	CONST_TYP_CD	Construction Type Code	VARCHAR2(25)	This system code describes the type of construction materials primarily used for dwelling exterior.
Warehouse	DF_DWLNG	CONST_TYP_CD	Construction Type Code	VARCHAR2(25)	This system code describes the type of construction materials primarily used for dwelling exterior.
Warehouse	DF_DWLNG	CONST_TYP_DESC	Construction Type Description	VARCHAR2(60)	This value describes the primary dwelling exterior construction materials.
Staging	DF_DWLNG	CTY_LMTS_CD	City Limits Code	VARCHAR2(25)	This system code describes if a dwelling is located within or outside city limit boundary.
Warehouse	DF_DWLNG	CTY_LMTS_CD	City Limits Code	VARCHAR2(25)	This system code describes if a dwelling is located within or outside city limit boundary.
Warehouse	DF_DWLNG	CTY_LMTS_DESC	City Limits Description	VARCHAR2(60)	This value describes the city limits where a dwelling is located.
Warehouse	DF_DWLNG	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the dwelling is currently included in policy coverages.
Warehouse	DF_DWLNG	DF_DWLNG_ID	Dwelling Fire Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling instance.
Staging	DF_DWLNG	DF_DWLNG_NAT_KEY	Dwelling Fire Dwelling Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the dwelling.
Warehouse	DF_DWLNG	DF_DWLNG_NAT_KEY	Dwelling Fire Dwelling Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the dwelling.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	DF_DWLNG	DF_DWLNG_UDF_CD_1	Dwelling Fire Dwelling User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_CD_1	Dwelling Fire Dwelling User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first dwelling fire dwelling user defined field.
Staging	DF_DWLNG	DF_DWLNG_UDF_CD_2	Dwelling Fire Dwelling User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_CD_2	Dwelling Fire Dwelling User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second dwelling fire dwelling user defined field.
Staging	DF_DWLNG	DF_DWLNG_UDF_CD_3	Dwelling Fire Dwelling User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_CD_3	Dwelling Fire Dwelling User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third dwelling fire dwelling user defined field.
Staging	DF_DWLNG	DF_DWLNG_UDF_CD_4	Dwelling Fire Dwelling User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_CD_4	Dwelling Fire Dwelling User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth dwelling fire dwelling user defined field.
Staging	DF_DWLNG	DF_DWLNG_UDF_CD_5	Dwelling Fire Dwelling User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_CD_5	Dwelling Fire Dwelling User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_DESC_1	Dwelling Fire Dwelling User Defined Field Description 1	VARCHAR2(60)	This value describes the first dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_DESC_2	Dwelling Fire Dwelling User Defined Field Description 2	VARCHAR2(60)	This value describes the second dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_DESC_3	Dwelling Fire Dwelling User Defined Field Description 3	VARCHAR2(60)	This value describes the third dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_DESC_4	Dwelling Fire Dwelling User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_DESC_5	Dwelling Fire Dwelling User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth dwelling fire dwelling user defined field.
Staging	DF_DWLNG	DIST_TO_FIRE_HYDRANT	Distance to Fire Hydrant	NUMBER (14,3)	This number represents the distance units (feet/ meters) from dwelling to nearest fire hydrant location.
Warehouse	DF_DWLNG	DIST_TO_FIRE_HYDRANT	Distance to Fire Hydrant	NUMBER (14, 3)	This number represents the distance units (feet/ meters) from dwelling to nearest fire hydrant location.
Staging	DF_DWLNG	DIST_TO_FIRE_STATION	Distance to Fire Station	NUMBER (14,3)	This number represents the distance units (miles/ kilometers) from dwelling to nearest fire station location.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	DF_DWLNG	DIST_TO_FIRE_STATION	Distance to Fire Station	NUMBER (14, 3)	This number represents the distance units (miles/ kilometers) from dwelling to nearest fire station location.
Staging	DF_DWLNG	DWLNG_AREA	Dwelling Area	NUMBER (14,3)	This number represents the area measurement of floor contained.
Warehouse	DF_DWLNG	DWLNG_AREA	Dwelling Area	NUMBER (14, 3)	This number represents the area measurement of floor contained.
Staging	DF_DWLNG	DWLNG_COND_CD	Dwelling Condition Code	VARCHAR2(25)	This system code indicates the dwelling condition.
Warehouse	DF_DWLNG	DWLNG_COND_CD	Dwelling Condition Code	VARCHAR2(25)	This system code indicates the dwelling condition.
Warehouse	DF_DWLNG	DWLNG_COND_DESC	Dwelling Condition Description	VARCHAR2(60)	This value represents the description of the dwelling condition.
Staging	DF_DWLNG	DWLNG_TYP_CD	Dwelling Type Code	VARCHAR2(25)	This system code indicates the dwelling type.
Warehouse	DF_DWLNG	DWLNG_TYP_CD	Dwelling Type Code	VARCHAR2(25)	This system code indicates the dwelling type.
Warehouse	DF_DWLNG	DWLNG_TYP_DESC	Dwelling Type Description	VARCHAR2(60)	This value describes the dwelling type.
Staging	DF_DWLNG	ELEC_UPDT_TYP_CD	Electrical Update Type Code	VARCHAR2(25)	This system code indicates changes to electrical system after the dwelling's original construction.
Warehouse	DF_DWLNG	ELEC_UPDT_TYP_CD	Electrical Update Type Code	VARCHAR2(25)	This system code indicates changes to electrical system after the dwelling's original construction.
Warehouse	DF_DWLNG	ELEC_UPDT_TYP_DESC	Electrical Update Type Description	VARCHAR2(60)	This value describes electrical update type.
Staging	DF_DWLNG	ELEC_UPDT_YR	Electrical Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling electrical system.
Warehouse	DF_DWLNG	ELEC_UPDT_YR	Electrical Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling electrical system.
Warehouse	DF_DWLNG	END_DT	End Date	DATE	This calendar date represents when the dwelling is no longer included in policy coverages.
Staging	DF_DWLNG	FIRE_DSTRCT_CD	Fire District Code	VARCHAR2(25)	This system code describes the fire department response district assigned to a dwelling location.
Warehouse	DF_DWLNG	FIRE_DSTRCT_CD	Fire District Code	VARCHAR2(25)	This system code describes the fire department response district assigned to a dwelling location.
Warehouse	DF_DWLNG	FIRE_DSTRCT_DESC	Fire District Description	VARCHAR2(60)	This value represents the description of the fire district responsible for dwelling location.
Staging	DF_DWLNG	FIRE_PROT_CLASS_CD	Fire Protection Class Code	VARCHAR2(25)	This system code describes the fire protection services available at dwelling location.
Warehouse	DF_DWLNG	FIRE_PROT_CLASS_CD	Fire Protection Class Code	VARCHAR2(25)	This system code describes the fire protection services available at dwelling location.
Warehouse	DF_DWLNG	FIRE_PROT_CLASS_DESC	Fire Protection Class Description	VARCHAR2(60)	This value describes the fire monitoring type code.
Staging	DF_DWLNG	FNDN_TYP_CD	Foundation Type Code	VARCHAR2(25)	This system code indicates the construction method used to construct dwelling foundation.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	DF_DWLNG	FNDN_TYP_CD	Foundation Type Code	VARCHAR2(25)	This system code indicates the materials used to construct dwelling foundation.
Warehouse	DF_DWLNG	FNDN_TYP_DESC	Foundation Type Description	VARCHAR2(60)	This value describes the construction method used to construct the dwelling foundation.
Staging	DF_DWLNG	FUSES_FLG	Fuses Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fuses.
Warehouse	DF_DWLNG	FUSES_FLG	Fuses Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fuses.
Staging	DF_DWLNG	GAS_UPDT_TYP_CD	Gas Update Type Code	VARCHAR2(25)	This system code indicates changes to gas system after the dwelling's original construction.
Warehouse	DF_DWLNG	GAS_UPDT_TYP_CD	Gas Update Type Code	VARCHAR2(25)	This system code indicates changes to gas system after the dwelling's original construction.
Warehouse	DF_DWLNG	GAS_UPDT_TYP_DESC	Gas Update Type Description	VARCHAR2(60)	This value describes the gas update type.
Staging	DF_DWLNG	GAS_UPDT_YR	Gas Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling gas system.
Warehouse	DF_DWLNG	GAS_UPDT_YR	Gas Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling gas system.
Staging	DF_DWLNG	HEAT_UPDT_TYP_CD	Heating Update Type Code	VARCHAR2(25)	This system code indicates changes to heating system after the dwelling's original construction.
Warehouse	DF_DWLNG	HEAT_UPDT_TYP_CD	Heating Update Type Code	VARCHAR2(25)	This system code indicates changes to heating system after the dwelling's original construction.
Warehouse	DF_DWLNG	HEAT_UPDT_TYP_DESC	Heating Update Type Description	VARCHAR2(60)	This value describes heating update type.
Staging	DF_DWLNG	HEAT_UPDT_YR	Heating Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling heating system.
Warehouse	DF_DWLNG	HEAT_UPDT_YR	Heating Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling heating system.
Warehouse	DF_DWLNG	LOC_ADDR_ID	Location Address Identifier	NUMBER (22, 0)	This system generated number identifies the location address instance for dwelling fire dwelling.
Staging	DF_DWLNG	LOC_NUM	Location Number	NUMBER (22,0)	This number identifies the location of a dwelling.
Warehouse	DF_DWLNG	LOC_NUM	Location Number	NUMBER (22, 0)	This number identifies the location of a dwelling.
Staging	DF_DWLNG	MINE_SUBSIDENCE_FLG	Mine Subsidence Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of mine subsidence coverage.
Warehouse	DF_DWLNG	MINE_SUBSIDENCE_FLG	Mine Subsidence Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of mine subsidence coverage.
Staging	DF_DWLNG	MKT_VAL	Market Value	NUMBER (14,3)	This number represents the average price of similar dwellings recently sold in same real estate market.
Warehouse	DF_DWLNG	MKT_VAL	Market Value	NUMBER (14, 3)	This number represents the average price of similar dwellings recently sold in same real estate market.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	DF_DWLNG	NUM_ELEC_SYS_AMPS	Number Of Electrical System Amps	NUMBER (22,0)	This number represents the electrical current capacity of electrical system.
Warehouse	DF_DWLNG	NUM_ELEC_SYS_AMPS	Number Of Electrical System Amps	NUMBER (22, 0)	This number represents the electrical current capacity of electrical system.
Staging	DF_DWLNG	NUM_FMLYS	Number Of Families	NUMBER (22,0)	This number represents the count of individual family units in single dwelling. For example, a duplex would have 2 families.
Warehouse	DF_DWLNG	NUM_FMLYS	Number Of Families	NUMBER (22, 0)	This number represents the count of individual family units in single dwelling. For example, a duplex would have 2 families.
Staging	DF_DWLNG	NUM_OR_RMS	Number Of Rooms	NUMBER (22,0)	This number represents the count of rooms contained in all units of the dwelling.
Warehouse	DF_DWLNG	NUM_OR_RMS	Number Of Rooms	NUMBER (22, 0)	This number represents the count of rooms contained in all units of the dwelling.
Staging	DF_DWLNG	NUM_STORIES	Number Of Stories	NUMBER (22,0)	This number represents the count of building floor levels.
Warehouse	DF_DWLNG	NUM_STORIES	Number Of Stories	NUMBER (22, 0)	This number represents the count of building floor levels.
Staging	DF_DWLNG	NUM_WKS_RENTED	Number Of Weeks Rented	NUMBER (22,0)	This number represents the count of weeks dwelling is rented per calendar year.
Warehouse	DF_DWLNG	NUM_WKS_RENTED	Number Of Weeks Rented	NUMBER (22, 0)	This number represents the count of weeks dwelling is rented per calendar year.
Staging	DF_DWLNG	OCPCY_TYP_CD	Occupancy Type Code	VARCHAR2(25)	This system code indicates the type of occupants of the dwelling.
Warehouse	DF_DWLNG	OCPCY_TYP_CD	Occupancy Type Code	VARCHAR2(25)	This system code indicates the type of occupants of the dwelling.
Warehouse	DF_DWLNG	OCPCY_TYP_DESC	Occupancy Type Description	VARCHAR2(60)	This value describes the primary occupant type of a dwelling.
Staging	DF_DWLNG	PLUMBING_UPDT_TYP_CD	Plumbing Update Type Code	VARCHAR2(25)	This system code indicates changes to the plumbing system after the dwelling's original construction.
Warehouse	DF_DWLNG	PLUMBING_UPDT_TYP_CD	Plumbing Update Type Code	VARCHAR2(25)	This system code indicates changes to the plumbing system after the dwelling's original construction.
Warehouse	DF_DWLNG	PLUMBING_UPDT_TYP_DESC	Plumbing Update Type Description	VARCHAR2(60)	This value describes the plumbing update type.
Staging	DF_DWLNG	PLUMBING_UPDT_YR	Plumbing Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling plumbing system.
Warehouse	DF_DWLNG	PLUMBING_UPDT_YR	Plumbing Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling plumbing system.
Staging	DF_DWLNG	PP_MERCNTL_BLDG_FLG	Personal Property Mercantile Building Flag	CHAR(1)	This value represents based on the yes/no indicator identifying presence or absence of personal property storage in a mercantile building.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	DF_DWLNG	PP_MERCNTL_BLDG_FLG	Personal Property Mercantile Building Flag	CHAR(1)	This value represents based on the yes/no indicator identifying presence or absence of personal property storage in a mercantile building.
Staging	DF_DWLNG	PRIM_HEAT_TYP_CD	Primary Heating Type Code	VARCHAR2(25)	This system code describes the primary source of heat for dwelling.
Warehouse	DF_DWLNG	PRIM_HEAT_TYP_CD	Primary Heating Type Code	VARCHAR2(25)	This system code describes the primary source of heat for dwelling.
Warehouse	DF_DWLNG	PRIM_HEAT_TYP_DESC	Primary Heating Type Description	VARCHAR2(60)	This value describes the primary source of heat for dwelling.
Staging	DF_DWLNG	PURCH_DT	Purchase Date	DATE	This calendar date represents when the insured purchased the dwelling.
Warehouse	DF_DWLNG	PURCH_DT	Purchase Date	DATE	This calendar date represents when the insured purchased the dwelling.
Staging	DF_DWLNG	PURCH_PRICE	Purchase Price	NUMBER (14,3)	This number represents the monetary amount paid when dwelling was purchased.
Warehouse	DF_DWLNG	PURCH_PRICE	Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when dwelling was purchased.
Staging	DF_DWLNG	REPL_COST	Replacement Cost	NUMBER (14,3)	This number represents the monetary amount it would cost to replace a dwelling at current prices with like materials.
Warehouse	DF_DWLNG	REPL_COST	Replacement Cost	NUMBER (14, 3)	This number represents the amount it would cost to replace a dwelling at current prices with like materials.
Staging	DF_DWLNG	ROOF_MATL_CD	Roofing Material Code	VARCHAR2(25)	This system code identifies the material used to construct the roof.
Warehouse	DF_DWLNG	ROOF_MATL_CD	Roofing Material Code	VARCHAR2(25)	This system code identifies the material used to construct the roof.
Warehouse	DF_DWLNG	ROOF_MATL_DESC	Roofing Material Description	VARCHAR2(60)	This value describes the roof material code.
Staging	DF_DWLNG	ROOF_UPDT_TYP_CD	Roofing Update Type Code	VARCHAR2(25)	This system code indicates the type or roofing updates made since the dwelling's original construction.
Warehouse	DF_DWLNG	ROOF_UPDT_TYP_CD	Roofing Update Type Code	VARCHAR2(25)	This system code indicates the type or roofing updates made since the dwelling's original construction.
Warehouse	DF_DWLNG	ROOF_UPDT_TYP_DESC	Roofing Update Type Description	VARCHAR2(60)	This value describes the roof update type code.
Staging	DF_DWLNG	ROOF_UPDT_YR	Roofing Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling roofing materials.
Warehouse	DF_DWLNG	ROOF_UPDT_YR	Roofing Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling roofing materials.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	DF_DWLNG	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the dwelling fire dwelling with a specific transaction.
Staging	DF_DWLNG	SCND_HEAT_TYP_CD	Secondary Heating Type Code	VARCHAR2(25)	This system code describes the secondary source of heat for dwelling.
Warehouse	DF_DWLNG	SCND_HEAT_TYP_CD	Secondary Heating Type Code	VARCHAR2(25)	This system code describes the secondary source of heat for dwelling.
Warehouse	DF_DWLNG	SCND_HEAT_TYP_DESC	Secondary Heating Type Description	VARCHAR2(60)	This value describes the secondary source of heat for dwelling.
Staging	DF_DWLNG	STORM_SHUTTERS_CD	Storm Shutters Code	VARCHAR2(25)	This system code describes the existence or absence and type of storm shutters.
Staging	DF_DWLNG	UNDER_CONST_TYP_CD	Under Construction Type Code	VARCHAR2(25)	This system code indicates active construction activities on the dwelling.
Warehouse	DF_DWLNG	UNDER_CONST_TYP_CD	Under Construction Type Code	VARCHAR2(25)	This system code indicates active construction activities on the dwelling.
Warehouse	DF_DWLNG	UNDER_CONST_TYP_DESC	Under Construction Type Description	VARCHAR2(60)	This value describes the active construction activities.
Staging	DF_DWLNG	VACANT_PCT	Vacant Percentage	NUMBER (6,3)	This number represents the percentage of total dwelling area not currently occupied.
Warehouse	DF_DWLNG	VACANT_PCT	Vacant Percentage	NUMBER (6, 3)	This number represents the percentage of total dwelling area not currently occupied.
Staging	DF_DWLNG	WIRG_UPDT_TYP_CD	Wiring Update Type Code	VARCHAR2(25)	This system code identifies the type of update to wiring system.
Warehouse	DF_DWLNG	WIRG_UPDT_TYP_CD	Wiring Update Type Code	VARCHAR2(25)	This system code identifies the type of update to wiring system.
Warehouse	DF_DWLNG	WIRG_UPDT_TYP_DESC	Wiring Update Type Description	VARCHAR2(60)	This value describes the changes made to wiring system since original construction.
Staging	DF_DWLNG	WIRG_UPDT_YR	Wiring Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling wiring system.
Warehouse	DF_DWLNG	WIRG_UPDT_YR	Wiring Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling wiring system.
Staging	DF_DWLNG	YR_BUILT	Year Built	CHAR(4)	This value represents the calendar year that the dwelling was constructed.
Warehouse	DF_DWLNG	YR_BUILT	Year Built	CHAR(4)	This value represents the calendar year that the dwelling was constructed.
Datamart	DF_DWLNG_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the policy coverages began for the dwelling.
Datamart	DF_DWLNG_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the policy coverages for the dwelling is currently applicable.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	DF_DWLNG_DIM	DF_DWLNG_AREA	Dwelling Fire Dwelling Area	NUMBER (14, 3)	This number represents the area measurement of floor contained.
Datamart	DF_DWLNG_DIM	DF_DWLNG_CIRCUIT_BREAKERS_FLG	Dwelling Fire Dwelling Circuit Breakers Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of circuit breakers.
Datamart	DF_DWLNG_DIM	DF_DWLNG_COND	Dwelling Fire Dwelling Condition	VARCHAR2(60)	This value represents the classification detailing the maintenance condition of a dwelling.
Datamart	DF_DWLNG_DIM	DF_DWLNG_CONST_TYP	Dwelling Fire Dwelling Construction Type	VARCHAR2(60)	This value describes the primary dwelling exterior construction materials.
Datamart	DF_DWLNG_DIM	DF_DWLNG_CTY_LMTS_CD	Dwelling Fire Dwelling City Limits Code	VARCHAR2(60)	This system code describes if a dwelling is located within or outside city limit boundary.
Datamart	DF_DWLNG_DIM	DF_DWLNG_DIST_TO_FIRE_HYDRANT	Dwelling Fire Dwelling Distance to Fire Hydrant	NUMBER (14, 3)	This number represents the distance units (feet/ meters) from dwelling to nearest fire hydrant location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_DIST_TO_FIRE_STATION	Dwelling Fire Dwelling Distance to Fire Station	NUMBER (14, 3)	This number represents the distance units (miles/ kilometers) from dwelling to nearest fire station location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_ELEC_UPDT_TYP	Dwelling Fire Dwelling Electrical Update Type	VARCHAR2(60)	This value represents the classification detailing changes to electrical system after the dwelling's original construction.
Datamart	DF_DWLNG_DIM	DF_DWLNG_ELEC_UPDT_YR	Dwelling Fire Dwelling Electrical Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling electrical system.
Datamart	DF_DWLNG_DIM	DF_DWLNG_FIRE_DSTRCT	Dwelling Fire Dwelling Fire District	VARCHAR2(60)	This value represents the fire department response district assigned to a dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_FIRE_PROT_CLASS	Dwelling Fire Dwelling Fire Protection Class	VARCHAR2(60)	This system code describes the fire protection services available at dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_FNDN_TYP	Dwelling Fire Dwelling Foundation Type	VARCHAR2(60)	This value represents the construction method used for dwelling foundation.
Datamart	DF_DWLNG_DIM	DF_DWLNG_FUSES_FLG	Dwelling Fire Dwelling Fuses Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fuses.
Datamart	DF_DWLNG_DIM	DF_DWLNG_GAS_UPDT_TYP	Dwelling Fire Dwelling Gas Update Type	VARCHAR2(60)	This value represents the classification detailing changes to gas system after the dwelling's original construction.
Datamart	DF_DWLNG_DIM	DF_DWLNG_GAS_UPDT_YR	Dwelling Fire Dwelling Gas Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling gas system.
Datamart	DF_DWLNG_DIM	DF_DWLNG_GEOG_BNDRY_UDF_1	Dwelling Fire Dwelling Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first dwelling fire dwelling geographic boundary user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_GEOG_BNDRY_UDF_2	Dwelling Fire Dwelling Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second dwelling fire dwelling geographic boundary user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_GEOG_BNDRY_UDF_3	Dwelling Fire Dwelling Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third dwelling fire dwelling geographic boundary user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	DF_DWLNG_DIM	DF_DWLNG_GEOG_BNDRY_UDF_4	Dwelling Fire Dwelling Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth dwelling fire dwelling geographic boundary user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_GEOG_BNDRY_UDF_5	Dwelling Fire Dwelling Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth dwelling fire dwelling geographic boundary user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_HEAT_UPDT_TYP	Dwelling Fire Dwelling Heating Update Type	VARCHAR2(60)	This value represents the classification detailing changes to heating system after the dwelling's original construction.
Datamart	DF_DWLNG_DIM	DF_DWLNG_HEAT_UPDT_YR	Dwelling Fire Dwelling Heating Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling heating system.
Datamart	DF_DWLNG_DIM	DF_DWLNG_ID	Dwelling Fire Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling instance.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_CNTY	Dwelling Fire Dwelling Location County	VARCHAR2(60)	This value identifies the county of the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_CTRY	Dwelling Fire Dwelling Location Country	VARCHAR2(60)	This value identifies the country of the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_CTY	Dwelling Fire Dwelling Location City	VARCHAR2(32)	This value identifies the city of the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_DSTRCT	Dwelling Fire Dwelling Location District	VARCHAR2(60)	This value identifies the district of the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_LATITUDE	Dwelling Fire Dwelling Location Latitude	VARCHAR2(11)	This value identifies the latitude location of the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_LONGITUDE	Dwelling Fire Dwelling Location Longitude	VARCHAR2(11)	This value identifies the longitude location of the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_NUM	Dwelling Fire Dwelling Location Number	NUMBER (22, 0)	This number identifies the dwelling included in a dwelling fire policy.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_PSTL_CD	Dwelling Fire Dwelling Location Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications for the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_PSTL_CD_PRFX	Dwelling Fire Dwelling Location Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_PSTL_SUB_CD	Dwelling Fire Dwelling Location Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_REGION	Dwelling Fire Dwelling Location Region	VARCHAR2(60)	This value identifies the geographic region of the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_STATE	Dwelling Fire Dwelling Location State	VARCHAR2(60)	This value identifies the state associated with the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_TAX_LOC_ID	Dwelling Fire Dwelling Location Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier of the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_TERR	Dwelling Fire Dwelling Location Territory	VARCHAR2(60)	This value represents the territory of the dwelling location.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	DF_DWLNG_DIM	DF_DWLNG_MINE_SUBSIDENCE_FLG	Dwelling Fire Dwelling Mine Subsidence Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of mine subsidence coverage.
Datamart	DF_DWLNG_DIM	DF_DWLNG_MKT_VAL	Dwelling Fire Dwelling Market Value	NUMBER (14, 3)	This number represents the average price of similar dwellings recently sold in same real estate market.
Datamart	DF_DWLNG_DIM	DF_DWLNG_NAT_KEY	Dwelling Fire Dwelling Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the dwelling.
Datamart	DF_DWLNG_DIM	DF_DWLNG_NUM_ELEC_SYS_AMPS	Dwelling Fire Dwelling Number of Electric System Amps	NUMBER (22, 0)	This number represents the electrical current capacity of electrical system.
Datamart	DF_DWLNG_DIM	DF_DWLNG_NUM_FMLYS	Dwelling Fire Dwelling Number of Families	NUMBER (22, 0)	This number represents the count of individual family units in single dwelling. For example, a duplex would have 2 families.
Datamart	DF_DWLNG_DIM	DF_DWLNG_NUM_OR_RMS	Dwelling Fire Dwelling Number of Rooms	NUMBER (22, 0)	This number represents the count of rooms contained in all units of the dwelling.
Datamart	DF_DWLNG_DIM	DF_DWLNG_NUM_STORIES	Dwelling Fire Dwelling Number of Stories	NUMBER (22, 0)	This number represents the count of building floor levels contained.
Datamart	DF_DWLNG_DIM	DF_DWLNG_NUM_WKS_RENTED	Dwelling Fire Dwelling Number of Weeks Rented	NUMBER (22, 0)	This number represents the number of weeks the dwelling is rented per calendar year.
Datamart	DF_DWLNG_DIM	DF_DWLNG_OCPCY_TYP	Dwelling Fire Dwelling Occupancy Type	VARCHAR2(60)	This value represents the attributes of occupants of the dwelling. For example, owner and tenant occupants.
Datamart	DF_DWLNG_DIM	DF_DWLNG_PLUMBING_UPDT_TYP	Dwelling Fire Dwelling Plumbing Update Type	VARCHAR2(60)	This value represents the classification detailing changes to plumbing system after the dwelling's original construction.
Datamart	DF_DWLNG_DIM	DF_DWLNG_PLUMBING_UPDT_YR	Dwelling Fire Dwelling Plumbing Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling plumbing system.
Datamart	DF_DWLNG_DIM	DF_DWLNG_PP_MERCNTL_BLDG_FLG	Dwelling Fire Dwelling Personal Property Mercantile Building Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of personal property stored in a mercantile building.
Datamart	DF_DWLNG_DIM	DF_DWLNG_PRIM_HEAT_TYP	Dwelling Fire Dwelling Primary Heating Type	VARCHAR2(60)	This value represents the classification of the primary source of heat for dwelling.
Datamart	DF_DWLNG_DIM	DF_DWLNG_PURCH_DT_ID	Dwelling Fire Dwelling Purchase Date Identifier	DATE	This calendar date represents the dwelling purchase date.
Datamart	DF_DWLNG_DIM	DF_DWLNG_PURCH_PRICE	Dwelling Fire Dwelling Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when dwelling was purchased.
Datamart	DF_DWLNG_DIM	DF_DWLNG_REPL_COST	Dwelling Fire Dwelling Replacement Cost	NUMBER (14, 3)	This number represents the amount it would cost to replace a dwelling at current prices with like materials.
Datamart	DF_DWLNG_DIM	DF_DWLNG_ROOF_MATL	Dwelling Fire Dwelling RoofingMaterial	VARCHAR2(60)	This value represents the roofing material used on the dwelling roof.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	DF_DWLNG_DIM	DF_DWLNG_ROOF_UPDT_TYP	Dwelling Fire Dwelling RoofingUpdate Type	VARCHAR2(60)	This value represents the classification detailing changes to roofing materials after the dwelling's original construction.
Datamart	DF_DWLNG_DIM	DF_DWLNG_ROOF_UPDT_YR	Dwelling Fire Dwelling RoofingUpdate Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling roofing materials.
Datamart	DF_DWLNG_DIM	DF_DWLNG_SCND_HEAT_TYP	Dwelling Fire Dwelling Secondary Heating Type	VARCHAR2(60)	This value represents the classification of the secondary source of heat for dwelling.
Datamart	DF_DWLNG_DIM	DF_DWLNG_TYP	Dwelling Fire Dwelling Type	VARCHAR2(60)	This value represents the classification that identifies the dwelling unit construction. For example, single-family, multi-family, warehouse, etc.
Datamart	DF_DWLNG_DIM	DF_DWLNG_UDF_1	Dwelling Fire Dwelling User Defined Field 1	VARCHAR2(60)	This value describes the first dwelling fire dwelling user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_UDF_2	Dwelling Fire Dwelling User Defined Field 2	VARCHAR2(60)	This value describes the second dwelling fire dwelling user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_UDF_3	Dwelling Fire Dwelling User Defined Field 3	VARCHAR2(60)	This value describes the third dwelling fire dwelling user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_UDF_4	Dwelling Fire Dwelling User Defined Field 4	VARCHAR2(60)	This value describes the fourth dwelling fire dwelling user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_UDF_5	Dwelling Fire Dwelling User Defined Field 5	VARCHAR2(60)	This value describes the fifth dwelling fire dwelling user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_UNDER_CONST_TYP	Dwelling Fire Dwelling Under Construction Type	VARCHAR2(60)	This system code indicates active construction activities on the dwelling.
Datamart	DF_DWLNG_DIM	DF_DWLNG_VACANT_PCT	Dwelling Fire Dwelling Vacant Percentage	NUMBER (6, 3)	This number represents the percentage of total dwelling area that is not currently occupied.
Datamart	DF_DWLNG_DIM	DF_DWLNG_WIRG_UPDT_TYP	Dwelling Fire Dwelling Wiring Update Type	VARCHAR2(60)	This value represents the classification detailing changes to wiring system after the dwelling's original construction.
Datamart	DF_DWLNG_DIM	DF_DWLNG_WIRG_UPDT_YR	Dwelling Fire Dwelling Wiring Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling wiring system.
Datamart	DF_DWLNG_DIM	DF_DWLNG_YR_BUILT	Dwelling Fire Dwelling Year Built	CHAR(4)	This value represents the calendar year that the dwelling was constructed.
Datamart	DF_DWLNG_DIM	END_DT	End Date	DATE	This calendar date represents when the dwelling is no longer included in policy coverages.
Datamart	DF_DWLNG_DIM	HO_DWLNG_FARMING_FLG	Homeowners Dwelling Farming Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of farming activities occurring on insured premises.
Datamart	DF_FACT	DF_DWLNG_ID	Dwelling Fire Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling instance.
Datamart	DF_FACT	DF_FACT_ID	Dwelling Fire Fact Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling fire fact instance.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	DT_DIM	CAL_HALF_YR	Calendar Half Year	CHAR(2)	This value represents the calendar half year.
Datamart	DT_DIM	CAL_MTH_LONG_NM	Calendar Month Long Name	VARCHAR2(60)	This value describes the calendar month long name.
Datamart	DT_DIM	CAL_MTH_NM	Calendar Month Name	VARCHAR2(60)	This value describes the calendar month name.
Datamart	DT_DIM	CAL_MTH_NUM_IN_YR	Calendar Month Number In Year	NUMBER (22, 0)	This number identifies the calendar month in year.
Datamart	DT_DIM	CAL_QTR	Calendar Quarter	CHAR(2)	This value represents the calendar quarter.
Datamart	DT_DIM	CAL_QTR_NUM_IN_YR	Calendar Quarter Number In Year	NUMBER (22, 0)	This number identifies the calendar quarter number in year.
Datamart	DT_DIM	CAL_WK_BEGIN_DT	Calendar Week Begin Date	DATE	This calendar date represents when the calendar week begins.
Datamart	DT_DIM	CAL_WK_END_DT	Calendar Week Ending Date	DATE	This calendar date represents when the calendar week ends.
Datamart	DT_DIM	CAL_WK_NUM_IN_YR	Calendar Week Number In Year	NUMBER (22, 0)	This number identifies the calendar week number in year.
Datamart	DT_DIM	CAL_YR	Calendar Year	CHAR(4)	This value represents the calendar year.
Datamart	DT_DIM	CAL_YR_MTH	Calendar Year Month	CHAR(6)	This value represents identifies the calendar year month.
Datamart	DT_DIM	CAL_YR_MTH_NUM	Calendar Year Month Number	NUMBER (22, 0)	This number identifies the calendar year month.
Datamart	DT_DIM	CAL_YR_NUM	Calendar Year Number	NUMBER (22, 0)	This number identifies the calendar year.
Datamart	DT_DIM	CAL_YR_QTR	Calendar Year Quarter	CHAR(6)	A value that identifies calendar year quarter.
Datamart	DT_DIM	CAL_YR_QTR_NUM	Calendar Year Quarter Number	NUMBER (22, 0)	This number identifies the calendar year quarter number.
Datamart	DT_DIM	DAY_LONG_NM	Day of Week Long Name	VARCHAR2(60)	This value represents the day of week long name.
Datamart	DT_DIM	DAY_NM	Day of Week Name	VARCHAR2(60)	This value represents the name of the day of week.
Datamart	DT_DIM	DAY_NUM_IN_CAL_MTH	Day Number in Calendar Month	NUMBER (22, 0)	This number identifies day of week number in calendar month.
Datamart	DT_DIM	DAY_NUM_IN_CAL_YR	Day Number in Calendar Year	NUMBER (22, 0)	This number identifies day of week number in calendar year.
Datamart	DT_DIM	DAY_NUM_IN_FISCAL_MTH	Day Number in Fiscal Month	NUMBER (22, 0)	This number identifies day of week number in fiscal month.
Datamart	DT_DIM	DAY_NUM_IN_FISCAL_YR	Day Number in Fiscal Year	NUMBER (22, 0)	This number identifies day of week number in fiscal year.
Datamart	DT_DIM	DAY_NUM_IN_WK	Day Number in Week	NUMBER (22, 0)	This number identifies day of week number in week.
Datamart	DT_DIM	DT_FULL_DESC	Date Full Description	VARCHAR2(60)	This value represents the full description of the date.
Datamart	DT_DIM	DT_ID	Date Identifier	DATE	This calendar date represents the actual date.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	DT_DIM	FISCAL_HALF_YR	Fiscal Half Year	CHAR(2)	This value represents the fiscal half year.
Datamart	DT_DIM	FISCAL_MTH_LONG_NM	Fiscal Month Long Name	VARCHAR2(60)	This value represents the long name of fiscal month.
Datamart	DT_DIM	FISCAL_MTH_NM	Fiscal Month Name	VARCHAR2(60)	This value represents the name of fiscal month.
Datamart	DT_DIM	FISCAL_MTH_NUM_IN_YR	Fiscal Month Number In Year	NUMBER (22, 0)	This number identifies fiscal month number in year.
Datamart	DT_DIM	FISCAL_QTR	Fiscal Quarter	CHAR(2)	This value describes the fiscal quarter.
Datamart	DT_DIM	FISCAL_QTR_NUM_IN_YR	Fiscal Quarter Number In Year	NUMBER (22, 0)	This number identifies fiscal quarter number in year.
Datamart	DT_DIM	FISCAL_WK_BEGIN_DT	Fiscal Week Beginning Date	DATE	This date identifies the fiscal week begin date.
Datamart	DT_DIM	FISCAL_WK_END_DT	Fiscal Week Ending Date	DATE	This date identifies the fiscal week end date.
Datamart	DT_DIM	FISCAL_WK_NUM_IN_YR	Fiscal Week Number In Year	NUMBER (22, 0)	This number identifies fiscal number in year.
Datamart	DT_DIM	FISCAL_YR	Fiscal Year	CHAR(4)	This value describes the fiscal year.
Datamart	DT_DIM	FISCAL_YR_MTH	Fiscal Year Month	CHAR(6)	This value describes the fiscal year month.
Datamart	DT_DIM	FISCAL_YR_MTH_NUM	Fiscal Year Month Number	NUMBER (22, 0)	This number represents the fiscal year month number.
Datamart	DT_DIM	FISCAL_YR_NUM	Fiscal Year Number	NUMBER (22, 0)	This number represents the fiscal year number.
Datamart	DT_DIM	FISCAL_YR_QTR	Fiscal Year Quarter	CHAR(6)	This value describes the fiscal year quarter.
Datamart	DT_DIM	FISCAL_YR_QTR_NUM	Fiscal Year Quarter Number	NUMBER (22, 0)	This number represents the fiscal year quarter number.
Datamart	DT_DIM	LAST_DAY_IN_CAL_MTH_FLG	Last Day in Calendar Month Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the date is the last day in the calendar month.
Datamart	DT_DIM	LAST_DAY_IN_CAL_WK_FLG	Last Day in Calendar Week Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the date is the last day in the calendar week.
Datamart	DT_DIM	LAST_DAY_IN_FISCAL_MTH_FLG	Last Day in Fiscal Month Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the date is the last day in the fiscal month.
Datamart	DT_DIM	LAST_DAY_IN_FISCAL_WK_FLG	Last Day in Fiscal Week Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the date is the last day in the fiscal week.
Datamart	DT_DIM	WK_DAY_FLG	Weekday Flag	CHAR(1)	This value represents based on the yes/no indicator identifying presence or absence of week day.
Staging	ERND_EXPO_TRANS	ERND_EXPO_AMT	Earned Exposure Amount	NUMBER (14,3)	This number represents the amount of written exposure that is recognized as earned within a given time period.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	ERND_EXPO_TRANS	ERND_EXPO_AMT	Earned Exposure Amount	NUMBER (14, 3)	This number represents the amount of written exposure that is recognized as earned within a given time period.
Warehouse	ERND_EXPO_TRANS	ERND_EXPO_ID	Earned Exposure Identifier	NUMBER (22, 0)	This system generated number identifies the earned exposure.
Staging	ERND_EXPO_TRANS	FISCAL_YR_MTH	Fiscal Year Month	NUMBER (22,0)	This number represents the fiscal year month.
Warehouse	ERND_EXPO_TRANS	FISCAL_YR_MTH	Fiscal Year Month	CHAR(6)	This value describes the fiscal year month.
Warehouse	ERND_EXPO_TRANS	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction.
Staging	ERND_EXPO_TRANS	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the earned exposure transaction with a specific transaction.
Warehouse	ERND_EXPO_TRANS	SYS_PROC_DT	System Process Date	DATE	This calendar date represents when the system processed the earned exposure transaction.
Staging	ERND_EXPO_TRANS	UNERND_EXPO_AMT	Unearned Exposure Amount	NUMBER (14,3)	This number represents the monetary cost of exposure that is recognized as unearned within a given time period.
Warehouse	ERND_EXPO_TRANS	UNERND_EXPO_AMT	Unearned Exposure Amount	NUMBER (14, 3)	This number represents the amount of exposure that is recognized as unearned within a given time period.
Staging	ERND_PREM_TRANS	ERND_PREM_AMT	Earned Premium Amount	NUMBER (14,3)	This number represents the amount of written premium that that is recognized as earned within a given time period.
Warehouse	ERND_PREM_TRANS	ERND_PREM_AMT	Earned Premium Amount	NUMBER (14, 3)	This number represents the amount of written premium that that is recognized as earned within a given time period.
Warehouse	ERND_PREM_TRANS	ERND_PREM_TRANS_ID	Earned Premium Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the earned premium transaction instance.
Staging	ERND_PREM_TRANS	FISCAL_YR_MTH	Fiscal Year Month	VARCHAR2(6)	This value describes the fiscal year month in the earned premium transaction.
Warehouse	ERND_PREM_TRANS	FISCAL_YR_MTH	Fiscal Year Month	CHAR(6)	This value describes the fiscal year month.
Warehouse	ERND_PREM_TRANS	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction instance in the earned premium transaction.
Staging	ERND_PREM_TRANS	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the earned premium transaction with a specific transaction.
Warehouse	ERND_PREM_TRANS	SYS_PROC_DT	System Process Date	DATE	This calendar date represents when the system processed the earned premium transaction.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	ERND_PREM_TRANS	UNERND_PREM_AMT	Unearned Premium Amount	NUMBER (14,3)	This number represents the monetary cost of written premium that is recognized as unearned within a given time period.
Warehouse	ERND_PREM_TRANS	UNERND_PREM_AMT	Unearned Premium Amount	NUMBER (14, 3)	This number represents the amount of written premium that is recognized as unearned within a given time period.
Staging	FEAT	ACCID_INJY_ANLYS_CD	Accident Injury Analysis Code (AIA)	VARCHAR2(25)	This system code summarizes the facts relating to a claim. The code can be used to indicate injuries such as body parts involved, type of injury or disease and cause of condition related to a claim.
Warehouse	FEAT	ACCID_INJY_ANLYS_CD	Accident Injury Analysis Code (AIA)	VARCHAR2(25)	This system code summarizes the facts relating to a claim. The code can be used to indicate injuries such as body parts involved, type of injury or disease and cause of condition related to a claim.
Warehouse	FEAT	ACCID_INJY_ANLYS_DESC	Accident Injury Analysis Code Description	VARCHAR2(60)	This system code summarizes the facts relating to a claim. The description can be that identifies injuries such as body parts involved, type of injury or disease and cause of condition related to a claim.
Staging	FEAT	ACCID_INJY_ANLYS_SUB_CD	Accident Injury Analysis Sub Code	VARCHAR2(25)	This system code describes the loss in more detail than the accident injury analysis code and further describes such things as the object/incident involved in the loss (i.e. machinery, wet floor, etc.).
Warehouse	FEAT	ACCID_INJY_ANLYS_SUB_CD	Accident Injury Analysis Sub Code	VARCHAR2(25)	This system code describes the loss in more detail than the accident injury analysis code and further describes such things as the object/incident involved in the loss (i.e. machinery, wet floor, etc.).
Warehouse	FEAT	ACCID_INJY_ANLYS_SUB_DESC	Accident Injury Analysis Sub Code Description	VARCHAR2(60)	This description identifies the loss in more detail than the accident injury analysis sub code. This description further identifies such things as the object/incident involved in the loss (i.e. machinery, wet floor, etc.).
Warehouse	FEAT	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim feature applies.
Staging	FEAT	CAUSE_OF_LOSS_CD	Cause of Loss Code	VARCHAR2(25)	This system code represents the condition that caused a loss to occur.
Warehouse	FEAT	CAUSE_OF_LOSS_CD	Cause of Loss Code	VARCHAR2(25)	This system code represents the condition that caused a loss to occur.
Warehouse	FEAT	CAUSE_OF_LOSS_DESC	Cause of Loss Description	VARCHAR2(60)	This value describes the condition that caused a loss to occur.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	FEAT	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim feature is currently applicable.
Staging	FEAT	DSBLY_TYP_CD	Disability Type Code	VARCHAR2(25)	This system code indicates the disability type.
Warehouse	FEAT	DSBLY_TYP_CD	Disability Type Code	VARCHAR2(25)	This system code indicates the disability type.
Warehouse	FEAT	DSBLY_TYP_DESC	Disability Type Description	VARCHAR2(60)	This value describes disability type.
Warehouse	FEAT	END_DT	End Date	DATE	This calendar date represents when the claim feature is no longer valid.
Warehouse	FEAT	FEAT_ID	Feature Identifier	NUMBER (22, 0)	This system generated number identifies the claim feature instance.
Staging	FEAT	FEAT_NAT_KEY	Feature Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claim feature.
Warehouse	FEAT	FEAT_NAT_KEY	Feature Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claim feature.
Staging	FEAT	FEAT_UDF_CD_1	Feature User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim feature user defined field.
Warehouse	FEAT	FEAT_UDF_CD_1	Feature User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim feature user defined field.
Staging	FEAT	FEAT_UDF_CD_2	Feature User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim feature user defined field.
Warehouse	FEAT	FEAT_UDF_CD_2	Feature User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim feature user defined field.
Staging	FEAT	FEAT_UDF_CD_3	Feature User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim feature user defined field.
Warehouse	FEAT	FEAT_UDF_CD_3	Feature User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim feature user defined field.
Staging	FEAT	FEAT_UDF_CD_4	Feature User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim feature user defined field.
Warehouse	FEAT	FEAT_UDF_CD_4	Feature User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim feature user defined field.
Staging	FEAT	FEAT_UDF_CD_5	Feature User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim feature user defined field.
Warehouse	FEAT	FEAT_UDF_CD_5	Feature User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim feature user defined field.
Warehouse	FEAT	FEAT_UDF_DESC_1	Feature User Defined Field Description 1	VARCHAR2(60)	This value describes the first claim feature user defined field.
Warehouse	FEAT	FEAT_UDF_DESC_2	Feature User Defined Field Description 2	VARCHAR2(60)	This value describes the second claim feature user defined field.
Warehouse	FEAT	FEAT_UDF_DESC_3	Feature User Defined Field Description 3	VARCHAR2(60)	This value describes the third claim feature user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	FEAT	FEAT_UDF_DESC_4	Feature User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth claim feature user defined field.
Warehouse	FEAT	FEAT_UDF_DESC_5	Feature User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth claim feature user defined field.
Staging	FEAT	INJURED_BODY_PART_CD	Injured Body Part Code	VARCHAR2(25)	This system code represents an anatomical part of the insured body.
Warehouse	FEAT	INJURED_BODY_PART_CD	Injured Body Part Code	VARCHAR2(25)	This system code represents an anatomical part of the insured body.
Warehouse	FEAT	INJURED_BODY_PART_DESC	Injured Body Part Description	VARCHAR2(60)	This value describes an anatomical part of the insured body.
Staging	FEAT	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the claim feature with a specific transaction.
Staging	FEAT	TYP_OF_LOSS_CD	Type of Loss Code	VARCHAR2(25)	This system code describes the type of loss.
Warehouse	FEAT	TYP_OF_LOSS_CD	Type of Loss Code	VARCHAR2(25)	This is the CSP type of loss code It includes the loss location and the loss cause.
Warehouse	FEAT	TYP_OF_LOSS_DESC	Type of Loss Description	VARCHAR2(60)	This is the CSP type of loss code It includes the loss location and the loss cause.
Datamart	FEAT_DIM	ACCID_INJY_ANLYS_CD	Accident Injury Analysis Code (AIA)	VARCHAR2(60)	This system code summarizes the facts relating to a claim. The code can be used to indicate injuries such as body parts involved, type of injury or disease and cause of condition related to a claim.
Datamart	FEAT_DIM	ACCID_INJY_ANLYS_SUB_CD	Accident Injury Analysis Sub Code	VARCHAR2(60)	This system code describes the loss in more detail than the accident injury analysis code and further describes such things as the object/incident involved in the loss (i.e. machinery, wet floor, etc.).
Datamart	FEAT_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim feature applies.
Datamart	FEAT_DIM	CAUSE_OF_LOSS	Cause of Loss	VARCHAR2(60)	This value describes the condition that caused a loss to occur.
Datamart	FEAT_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim feature is currently applicable.
Datamart	FEAT_DIM	DSBLY_TYP	Disability Type	VARCHAR2(60)	This value represents the classification that identifies physical impairments.
Datamart	FEAT_DIM	END_DT	End Date	DATE	This calendar date represents when the claim feature is no longer valid.
Datamart	FEAT_DIM	FEAT_ID	Feature Identifier	NUMBER (22, 0)	This system generated number identifies the claim feature instance.
Datamart	FEAT_DIM	FEAT_NAT_KEY	Feature Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the Feature.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	FEAT_DIM	FEAT_UDF_1	Feature User Defined Field 1	VARCHAR2(60)	This value describes the first claim feature user defined field.
Datamart	FEAT_DIM	FEAT_UDF_2	Feature User Defined Field 2	VARCHAR2(60)	This value describes the second claim feature user defined field.
Datamart	FEAT_DIM	FEAT_UDF_3	Feature User Defined Field 3	VARCHAR2(60)	This value describes the third claim feature user defined field.
Datamart	FEAT_DIM	FEAT_UDF_4	Feature User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim feature user defined field.
Datamart	FEAT_DIM	FEAT_UDF_5	Feature User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim feature user defined field.
Datamart	FEAT_DIM	INJURED_BODY_PART	Injured Body Part	VARCHAR2(60)	This value represents the anatomical part of the insured's body.
Datamart	FEAT_DIM	TYP_OF_LOSS	Type of Loss	VARCHAR2(60)	This is the CSP type of loss code It includes the loss location and the loss cause.
Staging	FEAT_STATUS	FEAT_CLOSED_DT	Feature Closed Date	DATE	This calendar date represents when the claim feature, defined as a subset of a claim occurrence, was closed.
Warehouse	FEAT_STATUS	FEAT_CLOSED_DT	Feature Closed Date	DATE	This calendar date represents when the claim feature, defined as a subset of a claim occurrence, was closed.
Staging	FEAT_STATUS	FEAT_OPENED_DT	Feature Opened Date	DATE	This calendar date represents when the claim feature, defined as a subset of a claim occurrence, was opened.
Warehouse	FEAT_STATUS	FEAT_OPENED_DT	Feature Opened Date	DATE	This calendar date represents when the claim feature, defined as a subset of a claim occurrence, was opened.
Staging	FEAT_STATUS	FEAT_RECLOSED_DT	Feature Re-closed Date	DATE	This calendar date represents when the claim feature, defined as a subset of a claim occurrence, was reclosed.
Warehouse	FEAT_STATUS	FEAT_RECLOSED_DT	Feature Re-closed Date	DATE	This date represents the calendar date the claim feature was closed after original closing.
Staging	FEAT_STATUS	FEAT_REOPENED_DT	Feature Re-Opened Date	DATE	This calendar date represents when the claim feature, defined as a subset of a claim occurrence, was reopened.
Warehouse	FEAT_STATUS	FEAT_REOPENED_DT	Feature Re-Opened Date	DATE	This calendar date represents when the claim feature was opened after previous closing.
Staging	FEAT_STATUS	FEAT_STATUS_CD	Feature Status Code	VARCHAR2(25)	This system code identifies the current condition of the claim feature, defined as a subset of a claim occurrence.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	FEAT_STATUS	FEAT_STATUS_CD	Feature Status Code	VARCHAR2(25)	This system code identifies the current condition of the claim feature, defined as a subset of a claim occurrence.
Warehouse	FEAT_STATUS	FEAT_STATUS_DESC	Feature Status Description	VARCHAR2(60)	This value describes the current condition of the claim feature, defined as a subset of a claim.
Warehouse	FEAT_STATUS	FEAT_STATUS_ID	Feature Status Identifier	NUMBER (22, 0)	This system generated number identifies the feature status instance.
Staging	FEAT_STATUS	FEAT_STATUS_UDF_CD_1	Feature Status User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_CD_1	Feature Status User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim feature status user defined field.
Staging	FEAT_STATUS	FEAT_STATUS_UDF_CD_2	Feature Status User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_CD_2	Feature Status User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim feature status user defined field.
Staging	FEAT_STATUS	FEAT_STATUS_UDF_CD_3	Feature Status User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_CD_3	Feature Status User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim feature status user defined field.
Staging	FEAT_STATUS	FEAT_STATUS_UDF_CD_4	Feature Status User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_CD_4	Feature Status User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim feature status user defined field.
Staging	FEAT_STATUS	FEAT_STATUS_UDF_CD_5	Feature Status User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_CD_5	Feature Status User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_DESC_1	Feature Status User Defined Field Description 1	VARCHAR2(60)	This value describes the first claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_DESC_2	Feature Status User Defined Field Description 2	VARCHAR2(60)	This value describes the second claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_DESC_3	Feature Status User Defined Field Description 3	VARCHAR2(60)	This value describes the third claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_DESC_4	Feature Status User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_DESC_5	Feature Status User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth claim feature status user defined field.
Staging	FEAT_STATUS	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the claim feature status with a specific transaction.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	FEAT_STATUS_DIM	FEAT_CLOSED_DT_ID	Feature Closed Date	DATE	This calendar date represents when the claim feature, defined as a subset of a claim occurrence, was closed.
Datamart	FEAT_STATUS_DIM	FEAT_OPENED_DT_ID	Feature Opened Date	DATE	This calendar date represents when the claim feature, defined as a subset of a claim occurrence, was opened.
Datamart	FEAT_STATUS_DIM	FEAT_RECLOSED_DT_ID	Feature Re-closed Date Identifier	DATE	This calendar date represents when a claim feature was closed after original closing.
Datamart	FEAT_STATUS_DIM	FEAT_REOPENED_DT_ID	Feature Re-Opened Date Identifier	DATE	This date identifies when a claim feature was opened after a previous closing.
Datamart	FEAT_STATUS_DIM	FEAT_STATUS	Feature Status	VARCHAR2(60)	This value describes the current condition of the claim feature, defined as a subset of a claim.
Datamart	FEAT_STATUS_DIM	FEAT_STATUS_ID	Feature Status Identifier	NUMBER (22, 0)	This system generated number identifies the claim feature status instance.
Datamart	FEAT_STATUS_DIM	FEAT_STATUS_UDF_1	Feature Status User Defined Field 1	VARCHAR2(60)	This value describes the first claim feature status user defined field.
Datamart	FEAT_STATUS_DIM	FEAT_STATUS_UDF_2	Feature Status User Defined Field 2	VARCHAR2(60)	This value describes the second claim feature status user defined field.
Datamart	FEAT_STATUS_DIM	FEAT_STATUS_UDF_3	Feature Status User Defined Field 3	VARCHAR2(60)	This value describes the third claim feature status user defined field.
Datamart	FEAT_STATUS_DIM	FEAT_STATUS_UDF_4	Feature Status User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim feature status user defined field.
Datamart	FEAT_STATUS_DIM	FEAT_STATUS_UDF_5	Feature Status User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim feature status user defined field.
Warehouse	GEOG_BNDRY	CNTY_CD	County Code	VARCHAR2(25)	This system code describes a county.
Warehouse	GEOG_BNDRY	CNTY_DESC	County Description	VARCHAR2(60)	This value identifies the county where the geographic boundary exists.
Warehouse	GEOG_BNDRY	CTRY_CD	Country Code	VARCHAR2(25)	This value identifies the country code of the geographic boundary.
Warehouse	GEOG_BNDRY	CTRY_DESC	Country Description	VARCHAR2(60)	This value identifies the country where the geographic boundary is established.
Warehouse	GEOG_BNDRY	CTY	City	VARCHAR2(32)	This value identifies the city in the geographic boundary.
Warehouse	GEOG_BNDRY	DSTRCT_CD	District Code	VARCHAR2(25)	This system code identifies the company-defined district.
Warehouse	GEOG_BNDRY	DSTRCT_DESC	District Description	VARCHAR2(60)	This value describes the company-defined district for geographic boundary category.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_ID	Geographic Boundary Identifier	NUMBER (22, 0)	This system generated number identifies the geographic boundary instance.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_CD_1	Geographic Boundary User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first geographic boundary user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_CD_2	Geographic Boundary User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second geographic boundary user defined field.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_CD_3	Geographic Boundary User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third geographic boundary user defined field.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_CD_4	Geographic Boundary User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth geographic boundary user defined field.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_CD_5	Geographic Boundary User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth geographic boundary user defined field.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_DESC_1	Geographic Boundary User Defined Field Description 1	VARCHAR2(60)	This value describes the first geographic boundary user defined field.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_DESC_2	Geographic Boundary User Defined Field Description 2	VARCHAR2(60)	This value describes the second geographic boundary user defined field.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_DESC_3	Geographic Boundary User Defined Field Description 3	VARCHAR2(60)	This value describes the third geographic boundary user defined field.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_DESC_4	Geographic Boundary User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth geographic boundary user defined field.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_DESC_5	Geographic Boundary User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth geographic boundary user defined field.
Warehouse	GEOG_BNDRY	LATITUDE	Latitude	VARCHAR2(11)	This value represents the latitude location of the geographic boundary.
Warehouse	GEOG_BNDRY	LONGITUDE	Longitude	VARCHAR2(11)	This value represents the longitude location for the geographic boundary.
Warehouse	GEOG_BNDRY	PSTL_CD	Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Warehouse	GEOG_BNDRY	PSTL_CD_PRFX	Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Warehouse	GEOG_BNDRY	PSTL_SUB_CD	Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Warehouse	GEOG_BNDRY	REGION_CD	Region Code	VARCHAR2(25)	This system code identifies the geographic region as defined by company specifications.
Warehouse	GEOG_BNDRY	REGION_DESC	Region Description	VARCHAR2(60)	This value describes the company-defined geographic boundary.
Warehouse	GEOG_BNDRY	STATE_CD	State Code	VARCHAR2(25)	This system code identifies the state where the geographic boundary is established.
Warehouse	GEOG_BNDRY	STATE_DESC	State Description	VARCHAR2(60)	This value represents the name of the state where the geographic boundary is established.
Warehouse	GEOG_BNDRY	TAX_LOC_ID	Tax Location Identifier	VARCHAR2(6)	This system code identifies company-defined areas for tax purposes.
Warehouse	GEOG_BNDRY	TERR_CD	Territory Code	VARCHAR2(25)	This system code identifies the company-defined territory.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	GEOG_BNDRY	TERR_DESC	Territory Description	VARCHAR2(60)	This value represents the description of territory located in geographic boundary.
Staging	GRP_PRG	ANNIVERSARY_DT	Anniversary Date	DATE	This calendar date represents the annual anniversary of a program or association. Often, it is the calendar date of the dividend declaration.
Warehouse	GRP_PRG	ANNIVERSARY_DT	Anniversary Date	DATE	This calendar date represents the annual anniversary of a program or association. Often, it is the calendar date of the dividend declaration.
Warehouse	GRP_PRG	BEGIN_DT	Begin Date	DATE	This calendar date represents when the group program applies.
Warehouse	GRP_PRG	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the group program is currently applicable.
Staging	GRP_PRG	DIVIDEND_DT	dividend Date	DATE	This calendar date represents when the dividend applies to a program or association.
Warehouse	GRP_PRG	DIVIDEND_DT	dividend Date	DATE	This calendar date represents when the dividend applies to a program or association.
Staging	GRP_PRG	DIVIDEND_PLAN_CD	Dividend Plan Code	VARCHAR2(25)	This system code identifies the type of dividend plan offered by the company.
Warehouse	GRP_PRG	DIVIDEND_PLAN_CD	Dividend Plan Code	VARCHAR2(25)	This system code identifies the type of dividend plan offered by the company.
Warehouse	GRP_PRG	DIVIDEND_PLAN_DESC	Dividend Plan Description	VARCHAR2(60)	This value describes the type of dividend plan offered by the company.
Warehouse	GRP_PRG	END_DT	End Date	DATE	This calendar date represents when the group program is no longer valid.
Staging	GRP_PRG	GRP_PRG_CD	Group Program Code	VARCHAR2(25)	This system code represents the program that a group of policies are associated with.
Warehouse	GRP_PRG	GRP_PRG_CD	Group Program Code	VARCHAR2(25)	This system code represents the program that a group of policies are associated with.
Warehouse	GRP_PRG	GRP_PRG_DESC	Group Program Description	VARCHAR2(60)	This value represents the name of the program, other than state or national, that a group of policies are associated with.
Warehouse	GRP_PRG	GRP_PRG_ID	Group Program Identifier	NUMBER (22, 0)	This system generated number identifies the group program instance.
Staging	GRP_PRG	GRP_PRG_NAT_CD	Group Program National Code	VARCHAR2(25)	This system code identifies the national group program.
Warehouse	GRP_PRG	GRP_PRG_NAT_CD	Group Program National Code	VARCHAR2(25)	This system code represents the national program with which a group of policies are associated.
Warehouse	GRP_PRG	GRP_PRG_NAT_DESC	Group Program National Description	VARCHAR2(60)	This value represents the name of the national program that a group of policies are associated with.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	GRP_PRG	GRP_PRG_NAT_KEY	Group Program Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the group program.
Warehouse	GRP_PRG	GRP_PRG_NAT_KEY	Group Program Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the group program.
Staging	GRP_PRG	GRP_PRG_STATE_CD	Group Program State Code	VARCHAR2(25)	This system code represents the state program with which a group of policies is associated.
Warehouse	GRP_PRG	GRP_PRG_STATE_CD	Group Program State Code	VARCHAR2(25)	This system code represents the state program with which a group of policies is associated.
Warehouse	GRP_PRG	GRP_PRG_STATE_DESC	Group Program State Description	VARCHAR2(60)	This value represents the name of the state with which a group of policies is associated.
Staging	GRP_PRG	GRP_PRG_STATUS_CD	Group Program Status Code	VARCHAR2(25)	This system code represents the current condition of a program with which a group of policies is associated.
Warehouse	GRP_PRG	GRP_PRG_STATUS_CD	Group Program Status Code	VARCHAR2(25)	This system code represents the current condition of a program with which a group of policies is associated.
Warehouse	GRP_PRG	GRP_PRG_STATUS_DESC	Group Program Status Description	VARCHAR2(60)	This value describes the current condition of a program with which a group of policies is associated.
Staging	GRP_PRG	GRP_PRG_TYP_CD	Group Program Type Code	VARCHAR2(25)	This system code describes the type of group program that is represented.
Warehouse	GRP_PRG	GRP_PRG_TYP_CD	Group Program Type Code	VARCHAR2(25)	This system code describes the type of program that is represented.
Warehouse	GRP_PRG	GRP_PRG_TYP_DESC	Group Program Type Description	VARCHAR2(60)	This value describes the type of program that is represented.
Staging	GRP_PRG	GRP_PRG_UDF_CD_1	Group Program User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first group program user defined field.
Warehouse	GRP_PRG	GRP_PRG_UDF_CD_1	Group Program User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first group program user defined field.
Staging	GRP_PRG	GRP_PRG_UDF_CD_2	Group Program User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second group program user defined field.
Warehouse	GRP_PRG	GRP_PRG_UDF_CD_2	Group Program User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second group program user defined field.
Staging	GRP_PRG	GRP_PRG_UDF_CD_3	Group Program User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third group program user defined field.
Warehouse	GRP_PRG	GRP_PRG_UDF_CD_3	Group Program User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third group program user defined field.
Staging	GRP_PRG	GRP_PRG_UDF_CD_4	Group Program User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth group program user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	GRP_PRG	GRP_PRG_UDF_CD_4	Group Program User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth group program user defined field.
Staging	GRP_PRG	GRP_PRG_UDF_CD_5	Group Program User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth group program user defined field.
Warehouse	GRP_PRG	GRP_PRG_UDF_CD_5	Group Program User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth group program user defined field.
Warehouse	GRP_PRG	GRP_PRG_UDF_DESC_1	Group Program User Defined Field Description 1	VARCHAR2(60)	This value describes the first group program user defined field.
Warehouse	GRP_PRG	GRP_PRG_UDF_DESC_2	Group Program User Defined Field Description 2	VARCHAR2(60)	This value describes the second group program user defined field.
Warehouse	GRP_PRG	GRP_PRG_UDF_DESC_3	Group Program User Defined Field Description 3	VARCHAR2(60)	This value describes the third group program user defined field.
Warehouse	GRP_PRG	GRP_PRG_UDF_DESC_4	Group Program User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth group program user defined field.
Warehouse	GRP_PRG	GRP_PRG_UDF_DESC_5	Group Program User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth group program user defined field.
Staging	GRP_PRG	MBR_CNT	Member Count	NUMBER (22,0)	This number represents the count of members in a group or program.
Warehouse	GRP_PRG	MBR_CNT	Member Count	NUMBER (22, 0)	This number represents the count of members in a group or program.
Staging	GRP_PRG	ORIG_DT	Original Date	DATE	This calendar date describes the date a group program was applicable.
Warehouse	GRP_PRG	ORIG_DT	Original Date	DATE	This calendar date describes the date a group program was applicable.
Staging	GRP_PRG	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the group program with a specific transaction.
Datamart	GRP_PRG_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the group program applies.
Datamart	GRP_PRG_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the group program is currently applicable.
Datamart	GRP_PRG_DIM	END_DT	End Date	DATE	This calendar date represents when the group program is no longer valid.
Datamart	GRP_PRG_DIM	GRP_PRG_ANNIVERSARY_DT_ID	Group Program Anniversary Date Identifier	DATE	This calendar date represents the anniversary of a group program.
Datamart	GRP_PRG_DIM	GRP_PRG_DIVIDEND_DT_ID	Group Program dividend Date Identifier	DATE	This calendar date represents when identifies the dividend date of a group program.
Datamart	GRP_PRG_DIM	GRP_PRG_DIVIDEND_PLAN	Group Program Dividend Plan	VARCHAR2(60)	This value represents the classification of the manner in which a group program dividend is paid.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	GRP_PRG_DIM	GRP_PRG_ID	Group Program Identifier	NUMBER (22, 0)	This system generated number identifies the group program instance.
Datamart	GRP_PRG_DIM	GRP_PRG_MBR_CNT	Group Program Member Count	NUMBER (22, 0)	This number identifies the count of the members of a group program.
Datamart	GRP_PRG_DIM	GRP_PRG_NAT_KEY	Group Program Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the group program.
Datamart	GRP_PRG_DIM	GRP_PRG_NAT_NM	Group Program National Name	VARCHAR2(60)	This value represents the name of the national program that a group of policies are associated with.
Datamart	GRP_PRG_DIM	GRP_PRG_NM	Group Program Name	VARCHAR2(60)	This value represents the name of the program, other than state or national, that a group of policies are associated with.
Datamart	GRP_PRG_DIM	GRP_PRG_ORIG_DT_ID	Group Program Origination Date Identifier	DATE	This calendar date represents when identifies group program origination date.
Datamart	GRP_PRG_DIM	GRP_PRG_STATE	Group Program State	VARCHAR2(60)	This value identifies the state associated with group program.
Datamart	GRP_PRG_DIM	GRP_PRG_STATUS	Group Program Status	VARCHAR2(60)	This value describes the current condition of a program with which a group of policies is associated.
Datamart	GRP_PRG_DIM	GRP_PRG_TYP	Group Program Type	VARCHAR2(60)	This value represents the type of program that is represented.
Datamart	GRP_PRG_DIM	GRP_PRG_UDF_1	Group Program User Defined Field 1	VARCHAR2(60)	This value describes the first group program user defined field.
Datamart	GRP_PRG_DIM	GRP_PRG_UDF_2	Group Program User Defined Field 2	VARCHAR2(60)	This value describes the second group program user defined field.
Datamart	GRP_PRG_DIM	GRP_PRG_UDF_3	Group Program User Defined Field 3	VARCHAR2(60)	This value describes the third group program user defined field.
Datamart	GRP_PRG_DIM	GRP_PRG_UDF_4	Group Program User Defined Field 4	VARCHAR2(60)	This value describes the fourth group program user defined field.
Datamart	GRP_PRG_DIM	GRP_PRG_UDF_5	Group Program User Defined Field 5	VARCHAR2(60)	This value describes the fifth group program user defined field.
Staging	HO_DWLNG	ALUMINUM_WIRG_FLG	Aluminum Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of aluminum wiring.
Warehouse	HO_DWLNG	ALUMINUM_WIRG_FLG	Aluminum Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of aluminum wiring.
Staging	HO_DWLNG	ATTACHED_GAR_FLG	Attached Garage Indicator	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a garage that is attached to the dwelling.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	HO_DWLNG	ATTACHED_GAR_FLG	Attached Garage Indicator	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a garage that is attached to the dwelling.
Warehouse	HO_DWLNG	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage in the dwelling begins.
Staging	HO_DWLNG	BSMT_AREA	Basement Area	NUMBER (14,3)	This number represents the total area measurement of all the basements in this dwelling.
Warehouse	HO_DWLNG	BSMT_AREA	Basement Area	NUMBER (14, 3)	This number represents the total area measurement of all the basements in this dwelling.
Staging	HO_DWLNG	BURGLAR_MONITOR_TYP_CD	Burglar Monitoring Type Code	VARCHAR2(25)	This system code describes presence or absence and attributes of burglar alarm in use at the dwelling.
Warehouse	HO_DWLNG	BURGLAR_MONITOR_TYP_CD	Burglar Monitoring Type Code	VARCHAR2(25)	This system code describes presence or absence and attributes of burglar alarm in use at the dwelling.
Warehouse	HO_DWLNG	BURGLAR_MONITOR_TYP_DESC	Burglar Monitoring Type Description	VARCHAR2(60)	This value describes the burglar monitoring type.
Staging	HO_DWLNG	CARPORT_FLG	Carport Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a carport.
Warehouse	HO_DWLNG	CARPORT_FLG	Carport Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a carport.
Staging	HO_DWLNG	CIRCUIT_BREAKERS_FLG	Circuit Breakers Flag	CHAR(1)	This value represents the yes/no indicator identifying the presence or absence of circuit breakers.
Warehouse	HO_DWLNG	CIRCUIT_BREAKERS_FLG	Circuit Breakers Flag	CHAR(1)	This value represents the yes/no indicator identifying the presence or absence of circuit breakers.
Staging	HO_DWLNG	CONST_TYP_CD	Construction Type Code	VARCHAR2(25)	This system code describes the type of construction materials primarily used for dwelling exterior.
Warehouse	HO_DWLNG	CONST_TYP_CD	Construction Type Code	VARCHAR2(25)	This system code describes the type of construction materials primarily used for dwelling exterior.
Warehouse	HO_DWLNG	CONST_TYP_DESC	Construction Type Description	VARCHAR2(60)	This value describes the primary dwelling exterior construction materials.
Staging	HO_DWLNG	COPPER_WIRG_FLG	Copper Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of copper wiring.
Warehouse	HO_DWLNG	COPPER_WIRG_FLG	Copper Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of copper wiring.
Staging	HO_DWLNG	CTY_LMTS_CD	City Limits Code	VARCHAR2(25)	This system code describes if a dwelling is located within or outside city limit boundary.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	HO_DWLNG	CTY_LMTS_CD	City Limits Code	VARCHAR2(25)	This system code describes if a dwelling is located within or outside city limit boundary.
Warehouse	HO_DWLNG	CTY_LMTS_DESC	City Limits Description	VARCHAR2(60)	This value describes the city limits of the dwelling's location.
Warehouse	HO_DWLNG	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the dwelling is currently applicable.
Staging	HO_DWLNG	DIST_TO_FIRE_HYDRANT	Distance to Fire Hydrant	NUMBER (14,3)	This number represents the distance units (feet/ meters) from dwelling to nearest fire hydrant location.
Warehouse	HO_DWLNG	DIST_TO_FIRE_HYDRANT	Distance to Fire Hydrant	NUMBER (14, 3)	This number represents the distance units (feet/ meters) from dwelling to nearest fire hydrant location.
Staging	HO_DWLNG	DIST_TO_FIRE_STATION	Distance to Fire Station	NUMBER (14,3)	This number represents the distance units (miles/ kilometers) from dwelling to nearest fire station location
Warehouse	HO_DWLNG	DIST_TO_FIRE_STATION	Distance to Fire Station	NUMBER (14, 3)	This number represents the distance units (miles/ kilometers) from dwelling to nearest fire station location
Staging	HO_DWLNG	DWLNG_AREA	Dwelling Area	NUMBER (14,3)	This number represents the area measurement of floor contained in the dwelling.
Warehouse	HO_DWLNG	DWLNG_AREA	Dwelling Area	NUMBER (14, 3)	This number represents the area measurement of floor contained in the dwelling.
Staging	HO_DWLNG	DWLNG_COND_CD	Dwelling Condition Code	VARCHAR2(25)	This system code indicates the dwelling condition.
Warehouse	HO_DWLNG	DWLNG_COND_CD	Dwelling Condition Code	VARCHAR2(25)	This system code indicates the dwelling condition.
Warehouse	HO_DWLNG	DWLNG_COND_DESC	Dwelling Condition Description	VARCHAR2(60)	This value represents the description of the dwelling condition.
Staging	HO_DWLNG	DWLNG_TYP_CD	Dwelling Type Code	VARCHAR2(25)	This system code indicates the dwelling type.
Warehouse	HO_DWLNG	DWLNG_TYP_CD	Dwelling Type Code	VARCHAR2(25)	This system code indicates the dwelling type.
Warehouse	HO_DWLNG	DWLNG_TYP_DESC	Dwelling Type Description	VARCHAR2(60)	This value describes the dwelling type.
Staging	HO_DWLNG	ELEC_UPDT_TYP_CD	Electrical Update Type Code	VARCHAR2(25)	This system code indicates changes to electrical system after the dwelling's original construction.
Warehouse	HO_DWLNG	ELEC_UPDT_TYP_CD	Electrical Update Type Code	VARCHAR2(25)	This system code indicates changes to electrical system after the dwelling's original construction.
Warehouse	HO_DWLNG	ELEC_UPDT_TYP_DESC	Electrical Update Type Description	VARCHAR2(60)	This value describes electrical update type.
Staging	HO_DWLNG	ELEC_UPDT_YR	Electrical Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling electrical system.
Warehouse	HO_DWLNG	ELEC_UPDT_YR	Electrical Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling electrical system.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	HO_DWLNG	ENCLOSED_GAR_FLG	Enclosed Garage Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of an enclosed garage.
Warehouse	HO_DWLNG	ENCLOSED_GAR_FLG	Enclosed Garage Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of enclosed garage.
Warehouse	HO_DWLNG	END_DT	End Date	DATE	This calendar date represents when the dwelling is no longer included in policy coverages.
Staging	HO_DWLNG	EXT_PAINT_UPDT_YR	Exterior Paint Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling exterior paint.
Warehouse	HO_DWLNG	EXT_PAINT_UPDT_YR	Exterior Paint Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling exterior paint.
Staging	HO_DWLNG	FARMING_FLG	Farming Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of farming activities occurring on insured premises.
Warehouse	HO_DWLNG	FARMING_FLG	Farming Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of farming activities occurring on insured premises.
Staging	HO_DWLNG	FIRE_DSTRCT_CD	Fire District Code	VARCHAR2(25)	This system code describes the fire department response district assigned to a dwelling location.
Warehouse	HO_DWLNG	FIRE_DSTRCT_CD	Fire District Code	VARCHAR2(25)	This system code describes the fire department response district assigned to a dwelling location.
Warehouse	HO_DWLNG	FIRE_DSTRCT_DESC	Fire District Description	VARCHAR2(60)	This value represents the description of the fire district responsible for dwelling location.
Staging	HO_DWLNG	FIRE_EXTINGUISHER_FLG	Fire Extinguisher Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fire extinguisher.
Warehouse	HO_DWLNG	FIRE_EXTINGUISHER_FLG	Fire Extinguisher Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fire extinguisher.
Staging	HO_DWLNG	FIRE_MONITOR_TYP_CD	Fire Monitoring Type Code	VARCHAR2(25)	This system code indicates the type of fire monitoring alarm used at dwelling.
Warehouse	HO_DWLNG	FIRE_MONITOR_TYP_CD	Fire Monitoring Type Code	VARCHAR2(25)	This system code indicates the type of fire monitoring alarm used at dwelling.
Warehouse	HO_DWLNG	FIRE_MONITOR_TYP_DESC	Fire Monitoring Type Description	VARCHAR2(60)	This value describes the fire monitoring type code.
Staging	HO_DWLNG	FIRE_PROT_CLASS_CD	Fire Protection Class Code	VARCHAR2(25)	This system code describes the fire protection services available at dwelling location.
Warehouse	HO_DWLNG	FIRE_PROT_CLASS_CD	Fire Protection Class Code	VARCHAR2(25)	This system code describes the fire protection services available at dwelling location.
Warehouse	HO_DWLNG	FIRE_PROT_CLASS_DESC	Fire Protection Class Description	VARCHAR2(60)	This value describes the responding fire protection service available at dwelling location.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	HO_DWLNG	FNDN_TYP_CD	Foundation Type Code	VARCHAR2(25)	This system code indicates the construction method used to construct dwelling foundation.
Warehouse	HO_DWLNG	FNDN_TYP_CD	Foundation Type Code	VARCHAR2(25)	This system code indicates the construction method used to construct dwelling foundation.
Warehouse	HO_DWLNG	FNDN_TYP_DESC	Foundation Type Description	VARCHAR2(60)	This value describes the construction method used to construct the dwelling foundation.
Staging	HO_DWLNG	FUSES_FLG	Fuses Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fuses.
Warehouse	HO_DWLNG	FUSES_FLG	Fuses Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fuses.
Staging	HO_DWLNG	GAS_UPDT_TYP_CD	Gas Update Type Code	VARCHAR2(25)	This system code indicates changes to gas system after the dwelling's original construction.
Warehouse	HO_DWLNG	GAS_UPDT_TYP_CD	Gas Update Type Code	VARCHAR2(25)	This system code indicates changes to gas system after the dwelling's original construction.
Warehouse	HO_DWLNG	GAS_UPDT_TYP_DESC	Gas Update Type Description	VARCHAR2(60)	This value describes the gas update type.
Staging	HO_DWLNG	GAS_UPDT_YR	Gas Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling gas system.
Warehouse	HO_DWLNG	GAS_UPDT_YR	Gas Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling gas system.
Staging	HO_DWLNG	HEAT_UPDT_TYP_CD	Heating Update Type Code	VARCHAR2(25)	This system code indicates changes to heating system after the dwelling's original construction.
Warehouse	HO_DWLNG	HEAT_UPDT_TYP_CD	Heating Update Type Code	VARCHAR2(25)	This system code indicates changes to heating system after the dwelling's original construction.
Warehouse	HO_DWLNG	HEAT_UPDT_TYP_DESC	Heating Update Type Description	VARCHAR2(60)	This value describes heating update type.
Staging	HO_DWLNG	HEAT_UPDT_YR	Heating Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling heating system.
Warehouse	HO_DWLNG	HEAT_UPDT_YR	Heating Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling heating system.
Warehouse	HO_DWLNG	HO_DWLNG_ID	Homeowners Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling instance.
Staging	HO_DWLNG	HO_DWLNG_NAT_KEY	Homeowners Dwelling Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the dwelling.
Warehouse	HO_DWLNG	HO_DWLNG_NAT_KEY	Homeowners Dwelling Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the dwelling.
Staging	HO_DWLNG	HO_DWLNG_UDF_CD_1	Homeowners Dwelling User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first homeowners dwelling user defined field.
Warehouse	HO_DWLNG	HO_DWLNG_UDF_CD_1	Homeowners Dwelling User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first homeowners dwelling user defined field.
Staging	HO_DWLNG	HO_DWLNG_UDF_CD_2	Homeowners Dwelling User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second homeowners dwelling user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	HO_DWLNG	HO_DWLNG_UDF_CD_2	Homeowners Dwelling User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second homeowners dwelling user defined field.
Staging	HO_DWLNG	HO_DWLNG_UDF_CD_3	Homeowners Dwelling User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third homeowners dwelling user defined field.
Warehouse	HO_DWLNG	HO_DWLNG_UDF_CD_3	Homeowners Dwelling User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third homeowners dwelling user defined field.
Staging	HO_DWLNG	HO_DWLNG_UDF_CD_4	Homeowners Dwelling User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth homeowners dwelling user defined field.
Warehouse	HO_DWLNG	HO_DWLNG_UDF_CD_4	Homeowners Dwelling User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth homeowners dwelling user defined field.
Staging	HO_DWLNG	HO_DWLNG_UDF_CD_5	Homeowners Dwelling User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth homeowners dwelling user defined field.
Warehouse	HO_DWLNG	HO_DWLNG_UDF_CD_5	Homeowners Dwelling User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth homeowners dwelling user defined field.
Warehouse	HO_DWLNG	HO_DWLNG_UDF_DESC_1	Homeowners Dwelling User Defined Field Description 1	VARCHAR2(60)	This value describes the first homeowners dwelling user defined field.
Warehouse	HO_DWLNG	HO_DWLNG_UDF_DESC_2	Homeowners Dwelling User Defined Field Description 2	VARCHAR2(60)	This value describes the second homeowners dwelling user defined field.
Warehouse	HO_DWLNG	HO_DWLNG_UDF_DESC_3	Homeowners Dwelling User Defined Field Description 3	VARCHAR2(60)	This value describes the third homeowners dwelling user defined field.
Warehouse	HO_DWLNG	HO_DWLNG_UDF_DESC_4	Homeowners Dwelling User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth homeowners dwelling user defined field.
Warehouse	HO_DWLNG	HO_DWLNG_UDF_DESC_5	Homeowners Dwelling User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth homeowners dwelling user defined field.
Staging	HO_DWLNG	HURCN_RST_GLASS_FLG	Hurricane Resistant Glass Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of hurricane resistant glass.
Warehouse	HO_DWLNG	HURCN_RST_GLASS_FLG	Hurricane Resistant Glass Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of hurricane resistant glass.
Staging	HO_DWLNG	KNOB_TUBE_WIRG_FLG	Knob And Tube Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of knob and tube wiring.
Warehouse	HO_DWLNG	KNOB_TUBE_WIRG_FLG	Knob And Tube Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of knob and tube wiring.
Warehouse	HO_DWLNG	LOC_ADDR_ID	Location Address Identifier	NUMBER (22, 0)	This system generated number identifies the location address instance.
Staging	HO_DWLNG	LOC_NUM	Location Number	NUMBER (22,0)	This number identifies the location of a dwelling.
Warehouse	HO_DWLNG	LOC_NUM	Location Number	NUMBER (22, 0)	This number identifies the location of a dwelling.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	HO_DWLNG	MKT_VAL	Market Value	NUMBER (14,3)	This number represents the average price of similar dwellings recently sold in same real estate market.
Warehouse	HO_DWLNG	MKT_VAL	Market Value	NUMBER (14, 3)	This number represents the average price of similar dwellings recently sold in same real estate market.
Staging	HO_DWLNG	NUM_CHIMNEYS	Number Of Chimneys	NUMBER (22,0)	This number represents the total count of all chimneys in all units of a dwelling.
Warehouse	HO_DWLNG	NUM_CHIMNEYS	Number Of Chimneys	NUMBER (22, 0)	This number represents the count of chimneys in all units of a dwelling.
Staging	HO_DWLNG	NUM_ELEC_SYS_AMPS	Number Of Electrical System Amps	NUMBER (22,0)	This number represents the electrical current capacity of electrical system.
Warehouse	HO_DWLNG	NUM_ELEC_SYS_AMPS	Number Of Electrical System Amps	NUMBER (22, 0)	This number represents the electrical current capacity of electrical system.
Staging	HO_DWLNG	NUM_FMLYS	Number Of Families	NUMBER (22,0)	This number represents the count of individual family units in single dwelling. For example, a duplex would have 2 families.
Warehouse	HO_DWLNG	NUM_FMLYS	Number Of Families	NUMBER (22, 0)	This number represents the count of individual family units in single dwelling. For example, a duplex would have 2 families.
Staging	HO_DWLNG	NUM_HEARTHS	Number Of Hearths	NUMBER (22,0)	This number represents the count of individual fireplace hearths in all units of a dwelling.
Warehouse	HO_DWLNG	NUM_HEARTHS	Number Of Hearths	NUMBER (22, 0)	This number represents the count of individual fireplace hearths in all units of a dwelling.
Staging	HO_DWLNG	NUM_OR_RMS	Number Of Rooms	NUMBER (22,0)	This number represents the count of rooms contained in all units of the dwelling.
Warehouse	HO_DWLNG	NUM_OR_RMS	Number Of Rooms	NUMBER (22, 0)	This number represents the count of Rooms contained in all units of the dwelling.
Staging	HO_DWLNG	NUM_PRE_FAB_FPS	Number Of Pre-Fabricated Fireplaces	NUMBER (22,0)	This number represents the count of pre-fabricated fireplaces contained in all units of the dwelling.
Warehouse	HO_DWLNG	NUM_PRE_FAB_FPS	Number Of Pre-Fabricated Fireplaces	NUMBER (22, 0)	This number represents the count of pre-fabricated fireplaces contained in all units of the dwelling.
Staging	HO_DWLNG	NUM_RSDTS	Number Of Residents	NUMBER (22,0)	This number represents the count of residents in all units of a dwelling.
Warehouse	HO_DWLNG	NUM_RSDTS	Number Of Residents	NUMBER (22, 0)	This number represents the count of residents in all units of a dwelling.
Staging	HO_DWLNG	NUM_STORIES	Number Of Stories	NUMBER (22,0)	This number represents the count of building floor levels.
Warehouse	HO_DWLNG	NUM_STORIES	Number Of Stories	NUMBER (22, 0)	This number represents the count of building floor levels.
Staging	HO_DWLNG	NUM_WOOD_STOVE_ISRTS	Number Of Wood Stove Inserts	NUMBER (22,0)	This number represents the count of wood stove inserts contained in all units of the dwelling.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	HO_DWLNG	NUM_WOOD_STOVE_ISRTS	Number Of Wood Stove Inserts	NUMBER (22, 0)	This number represents the count of wood stove inserts contained in all units of the dwelling.
Staging	HO_DWLNG	OCPCY_TYP_CD	Occupancy Type Code	VARCHAR2(25)	This system code indicates the type of occupants of the dwelling.
Warehouse	HO_DWLNG	OCPCY_TYP_CD	Occupancy Type Code	VARCHAR2(25)	This system code indicates the type of occupants of the dwelling.
Warehouse	HO_DWLNG	OCPCY_TYP_DESC	Occupancy Type Description	VARCHAR2(60)	This value describes the primary occupant type of a dwelling.
Staging	HO_DWLNG	PLUMBING_UPDT_TYP_CD	Plumbing Update Type Code	VARCHAR2(25)	This system code indicates changes to plumbing system after the dwelling's original construction.
Warehouse	HO_DWLNG	PLUMBING_UPDT_TYP_CD	Plumbing Update Type Code	VARCHAR2(25)	This system code indicates changes to plumbing system after the dwelling's original construction.
Warehouse	HO_DWLNG	PLUMBING_UPDT_TYP_DESC	Plumbing Update Type Description	VARCHAR2(60)	This value describes the plumbing update type.
Staging	HO_DWLNG	PLUMBING_UPDT_YR	Plumbing Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling plumbing system.
Warehouse	HO_DWLNG	PLUMBING_UPDT_YR	Plumbing Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling plumbing system.
Staging	HO_DWLNG	PRIM_HEAT_TYP_CD	Primary Heating Type Code	VARCHAR2(25)	This system code describes the primary source of heat for dwelling.
Warehouse	HO_DWLNG	PRIM_HEAT_TYP_CD	Primary Heating Type Code	VARCHAR2(25)	This system code describes the primary source of heat for dwelling.
Warehouse	HO_DWLNG	PRIM_HEAT_TYP_DESC	Primary Heating Type Description	VARCHAR2(60)	This value describes the primary source of heat for dwelling.
Staging	HO_DWLNG	PROP_LOT_SIZE	Property Lot Size	NUMBER (14,3)	This number represents the area measurement of the land within the property lot boundaries.
Warehouse	HO_DWLNG	PROP_LOT_SIZE	Property Lot Size	NUMBER (14, 3)	This number represents the area measurement of the land within the property lot boundaries.
Staging	HO_DWLNG	PURCH_DT	Purchase Date	DATE	This calendar date represents when the insured purchased the dwelling.
Warehouse	HO_DWLNG	PURCH_DT	Purchase Date	DATE	This calendar date represents when the insured purchased the dwelling.
Staging	HO_DWLNG	PURCH_PRICE	Purchase Price	NUMBER (14,3)	This number represents the monetary amount paid when dwelling was purchased.
Warehouse	HO_DWLNG	PURCH_PRICE	Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when dwelling was purchased.
Staging	HO_DWLNG	REPL_COST	Replacement Cost	NUMBER (14,3)	This number represents the monetary amount it would cost to replace a dwelling at current prices with like materials.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	HO_DWLNG	REPL_COST	Replacement Cost	NUMBER (14, 3)	This number represents the amount it would cost to replace a dwelling at current prices with like materials.
Staging	HO_DWLNG	ROOF_IMPACT_RATING_CD	RoofingImpact Rating Code	VARCHAR2(25)	This system code describes the level of hail impact a roof material can withstand.
Warehouse	HO_DWLNG	ROOF_IMPACT_RATING_CD	RoofingImpact Rating Code	VARCHAR2(25)	This system code describes the level of hail impact a roof material can withstand.
Warehouse	HO_DWLNG	ROOF_IMPACT_RATING_DESC	RoofingImpact Rating Description	VARCHAR2(60)	This value represents the description that describes the size of hail a roof material is manufactured to withstand.
Staging	HO_DWLNG	ROOF_MATL_CD	RoofingMaterial Code	VARCHAR2(25)	This system code identifies the material used to construct the roof.
Warehouse	HO_DWLNG	ROOF_MATL_CD	RoofingMaterial Code	VARCHAR2(25)	This system code identifies the material used to construct the roof.
Warehouse	HO_DWLNG	ROOF_MATL_DESC	RoofingMaterial Description	VARCHAR2(60)	This value describes the roof material code.
Staging	HO_DWLNG	ROOF_UPDT_TYP_CD	RoofingUpdate Type Code	VARCHAR2(25)	This system code indicates the type or roofing updates made since the dwelling's original construction.
Warehouse	HO_DWLNG	ROOF_UPDT_TYP_CD	RoofingUpdate Type Code	VARCHAR2(25)	This system code indicates the type or roofing updates made since the dwelling's original construction.
Warehouse	HO_DWLNG	ROOF_UPDT_TYP_DESC	RoofingUpdate Type Description	VARCHAR2(60)	This value describes the roof update type code.
Staging	HO_DWLNG	ROOF_UPDT_YR	RoofingUpdate Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling roofing materials.
Warehouse	HO_DWLNG	ROOF_UPDT_YR	RoofingUpdate Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling roofing materials.
Staging	HO_DWLNG	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the homeowners dwelling with a specific transaction.
Staging	HO_DWLNG	SCND_HEAT_TYP_CD	Secondary Heating Type Code	VARCHAR2(25)	This system code describes the secondary source of heat for dwelling.
Warehouse	HO_DWLNG	SCND_HEAT_TYP_CD	Secondary Heating Type Code	VARCHAR2(25)	This system code describes the secondary source of heat for dwelling.
Warehouse	HO_DWLNG	SCND_HEAT_TYP_DESC	Secondary Heating Type Description	VARCHAR2(60)	This value describes the secondary source of heat for dwelling.
Staging	HO_DWLNG	SIDING_CD	Siding Code	VARCHAR2(25)	This system code identifies the type of material used as siding on the dwelling.
Warehouse	HO_DWLNG	SIDING_CD	Siding Code	VARCHAR2(25)	This system code identifies the type of material used as siding on the dwelling.
Warehouse	HO_DWLNG	SIDING_DESC	Siding Description	VARCHAR2(60)	This value describes the siding material used on the dwelling.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	HO_DWLNG	SIDING_PCT	Siding Percentage	NUMBER (6,3)	This number represents the percentage of total dwelling exterior covered with siding.
Warehouse	HO_DWLNG	SIDING_PCT	Siding Percentage	NUMBER (6, 3)	This number represents the percentage of total dwelling exterior covered with siding.
Staging	HO_DWLNG	SPRINKLER_TYP_CD	Sprinkler Type Code	VARCHAR2(25)	This system code identifies the sprinkler system type.
Warehouse	HO_DWLNG	SPRINKLER_TYP_CD	Sprinkler Type Code	VARCHAR2(25)	This system code identifies the sprinkler system type.
Warehouse	HO_DWLNG	SPRINKLER_TYP_DESC	Sprinkler Type Description	VARCHAR2(60)	This value describes the characteristics of a sprinkler system.
Staging	HO_DWLNG	STORM_SHUTTERS_CD	Storm Shutters Code	VARCHAR2(25)	This system code describes the existence or absence and type of storm shutters.
Warehouse	HO_DWLNG	STORM_SHUTTERS_CD	Storm Shutters Code	VARCHAR2(25)	This system code describes the existence or absence and type of storm shutters.
Warehouse	HO_DWLNG	STORM_SHUTTERS_DESC	Storm Shutters Description	VARCHAR2(60)	This value describes storm shutters attached to a dwelling.
Staging	HO_DWLNG	SWIM_POOL_CD	Swimming Pool Code	VARCHAR2(25)	This system code indicates the presence or absence and type of swimming pool.
Warehouse	HO_DWLNG	SWIM_POOL_CD	Swimming Pool Code	VARCHAR2(25)	This system code indicates the presence or absence and type of swimming pool.
Warehouse	HO_DWLNG	SWIM_POOL_DESC	Swimming Pool Description	VARCHAR2(60)	This value describes the type of swimming pool.
Staging	HO_DWLNG	TRAMPOLINE_FLG	Trampoline Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a trampoline.
Warehouse	HO_DWLNG	TRAMPOLINE_FLG	Trampoline Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a trampoline.
Staging	HO_DWLNG	UNDER_CONST_TYP_CD	Under Construction Type Code	VARCHAR2(25)	This system code indicates active construction activities on the dwelling.
Warehouse	HO_DWLNG	UNDER_CONST_TYP_CD	Under Construction Type Code	VARCHAR2(25)	This system code indicates active construction activities on the dwelling.
Warehouse	HO_DWLNG	UNDER_CONST_TYP_DESC	Under Construction Type Description	VARCHAR2(60)	This value describes the active construction activities.
Staging	HO_DWLNG	WIRG_LAST_INSP_DT	Wiring Last InspectedDate	DATE	This calendar date represents the occurance of the last inspection of the wiring system.
Warehouse	HO_DWLNG	WIRG_LAST_INSP_DT	Wiring Last InspectedDate	DATE	This calendar date represents the occurance of the last inspection of the wiring system.
Staging	HO_DWLNG	WIRG_UPDT_TYP_CD	Wiring Update Type Code	VARCHAR2(25)	This system code identifies the type of update to wiring system.
Warehouse	HO_DWLNG	WIRG_UPDT_TYP_CD	Wiring Update Type Code	VARCHAR2(25)	This system code identifies the type of update to wiring system.
Warehouse	HO_DWLNG	WIRG_UPDT_TYP_DESC	Wiring Update Type Description	VARCHAR2(60)	This value describes the changes made to wiring system since original construction.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	HO_DWLNG	WIRG_UPDT_YR	Wiring Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling wiring system.
Warehouse	HO_DWLNG	WIRG_UPDT_YR	Wiring Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling wiring system.
Staging	HO_DWLNG	YR_BUILT	Year Built	CHAR(4)	This value represents the calendar year that the dwelling was constructed.
Warehouse	HO_DWLNG	YR_BUILT	Year Built	CHAR(4)	This value represents the calendar year that the dwelling was constructed.
Datamart	HO_DWLNG_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage in the dwelling begins.
Datamart	HO_DWLNG_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the dwelling is currently applicable.
Datamart	HO_DWLNG_DIM	END_DT	End Date	DATE	This calendar date represents when the dwelling is no longer included in policy coverages.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ALUMINUM_WIRG_FLG	Homeowners Dwelling Aluminum Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of aluminum wiring.
Datamart	HO_DWLNG_DIM	HO_DWLNG_AREA	Homeowners Dwelling Area	NUMBER (14, 3)	This number represents the area measurement of floor contained in the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ATTACHED_GAR_FLG	Homeowners Dwelling Attached Garage Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of an attached garage.
Datamart	HO_DWLNG_DIM	HO_DWLNG_BSMT_AREA	Homeowners Dwelling Basement Area	NUMBER (14, 3)	This number represents the total area measurement of all the basements in this dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_BURGLAR_MONITOR_TYP	Homeowners Dwelling Burglar Monitoring Type	VARCHAR2(60)	This value describes the attributes of a burglar alarm in use.
Datamart	HO_DWLNG_DIM	HO_DWLNG_CARPORT_FLG	Homeowners Dwelling Carport Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a carport.
Datamart	HO_DWLNG_DIM	HO_DWLNG_CIRCUIT_BREAKERS_FLG	Homeowners Dwelling Circuit Breakers Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of circuit breakers.
Datamart	HO_DWLNG_DIM	HO_DWLNG_COND	Homeowners Dwelling Condition	VARCHAR2(60)	This value represents the classification detailing the maintenance condition of a dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_CONST_TYP	Homeowners Dwelling Construction Type	VARCHAR2(60)	This value describes the primary dwelling exterior construction materials.
Datamart	HO_DWLNG_DIM	HO_DWLNG_COPPER_WIRG_FLG	Homeowners Dwelling Copper Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of copper wiring.
Datamart	HO_DWLNG_DIM	HO_DWLNG_CTY_LMTS_CD	Homeowners Dwelling City Limits Code	VARCHAR2(60)	This system code describes if a dwelling is located within or outside city limit boundary.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	HO_DWLNG_DIM	HO_DWLNG_DIST_TO_FIRE_HYDRANT	Homeowners Dwelling Distance to Fire Hydrant	NUMBER (14, 3)	This number represents the distance units (feet/ meters) from dwelling to nearest fire hydrant location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_DIST_TO_FIRE_STATION	Homeowners Dwelling Distance to Fire Station	NUMBER (14, 3)	This number represents the distance units (miles/ kilometers) from dwelling to nearest fire station location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ELEC_UPDT_TYP	Homeowners Dwelling Electrical Update Type	VARCHAR2(60)	This value represents the classification that describes changes to electrical system after the dwelling's original construction.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ELEC_UPDT_YR	Homeowners Dwelling Electrical Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling electrical system.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ENCLOSED_GAR_FLG	Homeowners Dwelling Enclosed Garage Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of enclosed garage.
Datamart	HO_DWLNG_DIM	HO_DWLNG_EXT_PAINT_UPDT_YR	Homeowners Dwelling Exterior Paint Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling exterior paint.
Datamart	HO_DWLNG_DIM	HO_DWLNG_FARMING_FLG	Homeowners Dwelling Farming Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of farming activities occurring on insured premises.
Datamart	HO_DWLNG_DIM	HO_DWLNG_FIRE_DSTRCT	Homeowners Dwelling Fire District	VARCHAR2(60)	This value represents the fire department response district assigned to a dwelling location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_FIRE_EXTINGUISHER_FLG	Homeowners Dwelling Fire Extinguishers Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a fire extinguisher.
Datamart	HO_DWLNG_DIM	HO_DWLNG_FIRE_MONITOR_TYP	Homeowners Dwelling Fire Monitoring Type	VARCHAR2(60)	This value represents the type of fire monitoring alarm used at dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_FIRE_PROT_CLASS	Homeowners Dwelling Fire Protection Class	VARCHAR2(60)	This system code describes the fire protection services available at dwelling location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_FNDN_TYP	Homeowners Dwelling Foundation Type	VARCHAR2(60)	This value represents the construction method used to construct dwelling foundation.
Datamart	HO_DWLNG_DIM	HO_DWLNG_FUSES_FLG	Homeowners Dwelling Fuses Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fuses.
Datamart	HO_DWLNG_DIM	HO_DWLNG_GAS_UPDT_TYP	Homeowners Dwelling Gas Update Type	VARCHAR2(60)	This value represents the classification that describes changes to gas system after the dwelling's original construction.
Datamart	HO_DWLNG_DIM	HO_DWLNG_GAS_UPDT_YR	Homeowners Dwelling Gas Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling gas system.
Datamart	HO_DWLNG_DIM	HO_DWLNG_GEOG_BNDRY_UDF_1	Homeowners Dwelling Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first homeowners dwelling geographic boundary user defined field.
Datamart	HO_DWLNG_DIM	HO_DWLNG_GEOG_BNDRY_UDF_2	Homeowners Dwelling Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second homeowners dwelling geographic boundary user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	HO_DWLNG_DIM	HO_DWLNG_GEOG_BNDRY_UDF_3	Homeowners Dwelling Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third homeowners dwelling geographic boundary user defined field.
Datamart	HO_DWLNG_DIM	HO_DWLNG_GEOG_BNDRY_UDF_4	Homeowners Dwelling Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth homeowners dwelling geographic boundary user defined field.
Datamart	HO_DWLNG_DIM	HO_DWLNG_GEOG_BNDRY_UDF_5	Homeowners Dwelling Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth homeowners dwelling geographic boundary user defined field.
Datamart	HO_DWLNG_DIM	HO_DWLNG_HEAT_UPDT_TYP	Homeowners Dwelling Heating Update Type	VARCHAR2(60)	This value represents the classification that describes changes to heating system after the dwelling's original construction.
Datamart	HO_DWLNG_DIM	HO_DWLNG_HEAT_UPDT_YR	Homeowners Dwelling Heating Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling heating system.
Datamart	HO_DWLNG_DIM	HO_DWLNG_HURCN_RST_GLASS_FLG	Homeowners Dwelling Hurricane Resistant Glass Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of hurricane resistant glass.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ID	Homeowners Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling instance.
Datamart	HO_DWLNG_DIM	HO_DWLNG_KNOB_TUBE_WIRG_FLG	Homeowners Dwelling Knob and Tube Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of knob and tube wiring.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_CNTY	Homeowners Dwelling Location County	VARCHAR2(60)	This value identifies the county of the dwelling's location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_CTRY	Homeowners Dwelling Location Country	VARCHAR2(60)	This value identifies the country of the dwelling's location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_CTY	Homeowners Dwelling Location City	VARCHAR2(32)	This value identifies the city of the dwelling's location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_DSTRCT	Homeowners Dwelling Location District	VARCHAR2(60)	This value represents the district where the dwelling is located.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_LATITUDE	Homeowners Dwelling Location Latitude	VARCHAR2(11)	This value represents the latitude location of the dwelling location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_LONGITUDE	Homeowners Dwelling Location Longitude	VARCHAR2(11)	This value represents the longitude location of the dwelling location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_NUM	Homeowners Dwelling Location Number	NUMBER (22, 0)	This number represents the specific dwelling location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_PSTL_CD	Homeowners Dwelling Location Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_PSTL_CD_PRFX	Homeowners Dwelling Location Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_PSTL_SUB_CD	Homeowners Dwelling Location Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_REGION	Homeowners Dwelling Location Region	VARCHAR2(60)	This value represents the geographic region where the dwelling is located.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_STATE	Homeowners Dwelling Location State	VARCHAR2(60)	This value identifies the state associated with the dwelling location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_TAX_LOC_ID	Homeowners Dwelling Location Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier of the dwelling location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_TERR	Homeowners Dwelling Location Territory	VARCHAR2(60)	This value represents the territory where a dwelling is located.
Datamart	HO_DWLNG_DIM	HO_DWLNG_MKT_VAL	Homeowners Dwelling Market Value	NUMBER (14, 3)	This number represents the average price of similar dwellings recently sold in same real estate market.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NAT_KEY	Homeowners Dwelling Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NUM_CHIMNEYS	Homeowners Dwelling Number Chimneys	NUMBER (22, 0)	This number represents the count of chimneys contained in all units of the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NUM_ELEC_SYS_AMPS	Homeowners Dwelling Number of Electric System Amps	NUMBER (22, 0)	This number represents the electrical current capacity of electrical system.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NUM_FMLYS	Homeowners Dwelling Number Families	NUMBER (22, 0)	This number represents the count of individual family units in single dwelling. For example, a duplex would have 2 families.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NUM_HEARTHS	Homeowners Dwelling Number Hearths	NUMBER (22, 0)	This number represents the count of hearths contained in all units of the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NUM_OR_RMS	Homeowners Dwelling Number Of Rooms	NUMBER (22, 0)	This number represents the count of rooms contained in all units of the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NUM_PRE_FAB_FPS	Homeowners Dwelling Number Pre-Fabricated Fireplaces	NUMBER (22, 0)	This number represents the count of pre-fabricated fireplaces contained in all units of the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NUM_RSDTS	Homeowners Dwelling Number of Residents	NUMBER (22, 0)	This number represents the count of residents contained in all units of the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NUM_STORIES	Homeowners Dwelling Number Stories	NUMBER (22, 0)	This number represents the count of building floor levels in the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NUM_WOOD_STOVE_ISRTS	Homeowners Dwelling Number Wood Stove Inserts	NUMBER (22, 0)	This number represents the count of wood stove inserts contained in all units of the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_OCPCY_TYP	Homeowners Dwelling Occupancy Type	VARCHAR2(60)	This value represents the type of occupants of the dwelling. For example, owner and tenant occupants.
Datamart	HO_DWLNG_DIM	HO_DWLNG_PLUMBING_UPDT_TYP	Homeowners Dwelling Plumbing Update Type	VARCHAR2(60)	This value represents the classification that describes changes to plumbing system after the dwelling's original construction.
Datamart	HO_DWLNG_DIM	HO_DWLNG_PLUMBING_UPDT_YR	Homeowners Dwelling Plumbing Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling plumbing system.
Datamart	HO_DWLNG_DIM	HO_DWLNG_PRIM_HEAT_TYP	Homeowners Dwelling Primary Heating Type	VARCHAR2(60)	This value represents the classification of the primary source of heat for dwelling.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	HO_DWLNG_DIM	HO_DWLNG_PROP_LOT_SIZE	Homeowners Dwelling Property Lot Size	NUMBER (14, 3)	This number represents the total area measurement of the land within the property lot boundaries.
Datamart	HO_DWLNG_DIM	HO_DWLNG_PURCH_DT_ID	Homeowners Dwelling Purchase Date Identifier	DATE	This date identifies when the dwelling was purchased.
Datamart	HO_DWLNG_DIM	HO_DWLNG_PURCH_PRICE	Homeowners Dwelling Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when dwelling was purchased.
Datamart	HO_DWLNG_DIM	HO_DWLNG_REPL_COST	Homeowners Dwelling Replacement Cost	NUMBER (14, 3)	This number represents the amount it would cost to replace a dwelling at current prices with like materials.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ROOF_IMPACT_RATING	Homeowners Dwelling Roofing Impact Rating	VARCHAR2(60)	This value represents the rating of the level of hail impact a roof material can withstand.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ROOF_MATL	Homeowners Dwelling Roofing Material	VARCHAR2(60)	This value represents the construction material used to construct the roof of the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ROOF_UPDT_TYP	Homeowners Dwelling Roofing Update Type	VARCHAR2(60)	This value represents the type of change made to roofing materials after original construction.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ROOF_UPDT_YR	Homeowners Dwelling Roofing Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling roofing materials.
Datamart	HO_DWLNG_DIM	HO_DWLNG_SCND_HEAT_TYP	Homeowners Dwelling Secondary Heating Type	VARCHAR2(60)	This value represents the classification of the secondary source of heat for dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_SIDING	Homeowners Dwelling Siding	VARCHAR2(60)	This value represents the type of construction material used as siding on the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_SIDING_PCT	Homeowners Dwelling Siding Percentage	NUMBER (6, 3)	This number represents the percentage of total dwelling exterior covered with siding.
Datamart	HO_DWLNG_DIM	HO_DWLNG_SPRINKLER_TYP	Homeowners Dwelling Sprinkler Type	VARCHAR2(60)	This value represents the classification that identifies the sprinkler system type.
Datamart	HO_DWLNG_DIM	HO_DWLNG_STORM_SHUTTERS	Homeowners Dwelling Storm Shutters	VARCHAR2(60)	This value represents the classification that indicates the presence or absence and type of storm shutters.
Datamart	HO_DWLNG_DIM	HO_DWLNG_SWIM_POOL	Homeowners Dwelling Swimming Pool	VARCHAR2(60)	This value represents the classification that indicates the presence or absence and type of swimming pool.
Datamart	HO_DWLNG_DIM	HO_DWLNG_TRAMPOLINE_FLG	Homeowners Dwelling Trampoline Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a trampoline.
Datamart	HO_DWLNG_DIM	HO_DWLNG_TYP	Homeowners Dwelling Type	VARCHAR2(60)	This value represents the classification that identifies the dwelling unit construction. For example, single-family, multi-family, warehouse, etc.
Datamart	HO_DWLNG_DIM	HO_DWLNG_UDF_1	Homeowners Dwelling User Defined Field 1	VARCHAR2(60)	This value describes the first homeowners dwelling user defined field.
Datamart	HO_DWLNG_DIM	HO_DWLNG_UDF_2	Homeowners Dwelling User Defined Field 2	VARCHAR2(60)	This value describes the second homeowners dwelling user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	HO_DWLNG_DIM	HO_DWLNG_UDF_3	Homeowners Dwelling User Defined Field 3	VARCHAR2(60)	This value describes the third homeowners dwelling user defined field.
Datamart	HO_DWLNG_DIM	HO_DWLNG_UDF_4	Homeowners Dwelling User Defined Field 4	VARCHAR2(60)	This value describes the fourth homeowners dwelling user defined field.
Datamart	HO_DWLNG_DIM	HO_DWLNG_UDF_5	Homeowners Dwelling User Defined Field 5	VARCHAR2(60)	This value describes the fifth homeowners dwelling user defined field.
Datamart	HO_DWLNG_DIM	HO_DWLNG_UNDER_CONST_TYP	Homeowners Dwelling Under Construction Type	VARCHAR2(60)	This system code indicates active construction activities on the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_WIRG_LAST_INSP_DT_ID	Homeowners Dwelling Wiring Last InspectedDate Identifier	DATE	This calendar date represents the occurance of the last inspection of the dwelling wiring system.
Datamart	HO_DWLNG_DIM	HO_DWLNG_WIRG_UPDT_TYP	Homeowners Dwelling Wiring Update Type	VARCHAR2(60)	This value represents the classification that describes changes to wiring system after the dwelling's original construction.
Datamart	HO_DWLNG_DIM	HO_DWLNG_WIRG_UPDT_YR	Homeowners Dwelling Wiring Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling wiring system.
Datamart	HO_DWLNG_DIM	HO_DWLNG_YR_BUILT	Homeowners Dwelling Year Built	CHAR(4)	This value represents the calendar year that the dwelling was constructed.
Datamart	HO_FACT	HO_DWLNG_ID	Homeowners Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling instance.
Datamart	HO_FACT	HO_FACT_ID	Homeowners Fact Identifier	NUMBER (22, 0)	This system generated number identifies the homeowners fact instance.
Staging	INSD	AUDIT_FREQ_CD	Audit Frequency Code	VARCHAR2(25)	This system code identifies the intervals at which audits of the insured attributes are performed at the insurance company.
Warehouse	INSD	AUDIT_FREQ_CD	Audit Frequency Code	VARCHAR2(25)	This system code identifies the intervals at which audits of the insured attributes are performed at the insurance company.
Warehouse	INSD	AUDIT_FREQ_DESC	Audit Frequency Code Description	VARCHAR2(60)	This value describes the intervals at which audits are performed at the insured company.
Staging	INSD	AUDIT_TYP_CD	Audit Type Code	VARCHAR2(25)	This system code identifies what type of audit will be performed when the insured is audited.
Warehouse	INSD	AUDIT_TYP_CD	Audit Type Code	VARCHAR2(25)	This system code identifies what type of audit will be performed when the insured is audited.
Warehouse	INSD	AUDIT_TYP_DESC	Audit Type Code Description	VARCHAR2(60)	This value describes what type of audit will be performed when the insured is audited.
Warehouse	INSD	BEGIN_DT	Begin Date	DATE	This calendar date represents when the insured applies.
Staging	INSD	CRED_SCORE	Credit Score	VARCHAR2(11)	This value represents the rating from the current credit report.
Warehouse	INSD	CRED_SCORE	Credit Score	VARCHAR2(11)	This value represents the rating from the current credit report.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	INSD	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the insured is currently applicable.
Warehouse	INSD	END_DT	End Date	DATE	This calendar date represents when the insured is no longer valid.
Warehouse	INSD	INSD_ID	Insured Identifier	NUMBER (22, 0)	This system generated number identifies the insured instance.
Staging	INSD	INSD_TYP_CD	Insured Type Code	VARCHAR2(25)	This system code indicates the type of entity that a policy represents.
Warehouse	INSD	INSD_TYP_CD	Insured Type Code	VARCHAR2(25)	This system code indicates the type of entity that a policy represents.
Warehouse	INSD	INSD_TYP_DESC	Insured Type Description	VARCHAR2(60)	This value describes the type of entity that a policy represents.
Staging	INSD	INSD_UDF_CD_1	Insured User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first insured user defined field.
Warehouse	INSD	INSD_UDF_CD_1	Insured User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first insured user defined field.
Staging	INSD	INSD_UDF_CD_2	Insured User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second insured user defined field.
Warehouse	INSD	INSD_UDF_CD_2	Insured User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second insured user defined field.
Staging	INSD	INSD_UDF_CD_3	Insured User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third insured user defined field.
Warehouse	INSD	INSD_UDF_CD_3	Insured User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third insured user defined field.
Staging	INSD	INSD_UDF_CD_4	Insured User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth insured user defined field.
Warehouse	INSD	INSD_UDF_CD_4	Insured User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth insured user defined field.
Staging	INSD	INSD_UDF_CD_5	Insured User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth insured user defined field.
Warehouse	INSD	INSD_UDF_CD_5	Insured User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth insured user defined field.
Warehouse	INSD	INSD_UDF_DESC_1	Insured User Defined Field Description 1	VARCHAR2(60)	This value describes the first insured user defined field.
Warehouse	INSD	INSD_UDF_DESC_2	Insured User Defined Field Description 2	VARCHAR2(60)	This value describes the second insured user defined field.
Warehouse	INSD	INSD_UDF_DESC_3	Insured User Defined Field Description 3	VARCHAR2(60)	This value describes the third insured user defined field.
Warehouse	INSD	INSD_UDF_DESC_4	Insured User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth insured user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	INSD	INSD_UDF_DESC_5	Insured User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth insured user defined field.
Warehouse	INSD	ORG_ID	Organization Identifier	NUMBER (22, 0)	This system generated number identifies the insured organization instance.
Warehouse	INSD	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	INSD	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person.
Staging	INSD	PRIOR_INSUR_CO_CD	Prior Insurance Company Code	VARCHAR2(25)	This system code represents the prior insurance company.
Warehouse	INSD	PRIOR_INSUR_CO_CD	Prior Insurance Company Code	VARCHAR2(25)	This system code represents the prior insurance company.
Warehouse	INSD	PRIOR_INSUR_CO_DESC	Prior Insurance Company Description	VARCHAR2(60)	This value represents the name of the insurance company writing a policyholder's insurance before the current carrier.
Staging	INSD	RISK_GRADE_CD	Risk Grade Code	VARCHAR2(25)	This system code represents the A.M. Best or company defined risk grade in the insured.
Warehouse	INSD	RISK_GRADE_CD	Risk Grade Code	VARCHAR2(25)	This system code represents the A.M. Best or company defined risk grade in the insured.
Warehouse	INSD	RISK_GRADE_DESC	Risk Grade Code	VARCHAR2(60)	This value describes the A.M. Best or company defined risk grade.
Staging	INSD	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the insured with a specific transaction.
Staging	INSD	RPT_PERIOD_CD	Reporting Period Code	VARCHAR2(25)	This system code identifies the frequency with which reports are due for policies issued on a reporting basis.
Warehouse	INSD	RPT_PERIOD_CD	Reporting Period Code	VARCHAR2(25)	This system code identifies the frequency with which reports are due for policies issued on a reporting basis.
Warehouse	INSD	RPT_PERIOD_DESC	Reporting Period Description	VARCHAR2(60)	This value describes the frequency of reports sent to the company for reporting form coverage.
Datamart	INSD_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the insured applies.
Datamart	INSD_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the insured is currently applicable.
Datamart	INSD_DIM	END_DT	End Date	DATE	This calendar date represents when the insured is no longer valid.
Datamart	INSD_DIM	INSD_AUDIT_FREQ	Insured Audit Frequency	VARCHAR2(60)	This value represents the indicator of when an insured audit is scheduled.
Datamart	INSD_DIM	INSD_AUDIT_TYP	Insured Audit Type	VARCHAR2(60)	This value represents the classification of the audit activities conducted on insured.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	INSD_DIM	INSD_BIRTH_DT_ID	Insured Birth Date Identifier	DATE	This calendar date represents the insured date of birth instance.
Datamart	INSD_DIM	INSD_BUS_START_DT_ID	Insured Business Start Date Identifier	DATE	This calendar date represents when insured business operations began.
Datamart	INSD_DIM	INSD_CNTCT_DESC	Insured Contact Description	VARCHAR2(60)	This value represents the description of the insured's contact type.
Datamart	INSD_DIM	INSD_CNTCT_TYP	Insured Contact Type	VARCHAR2(60)	This value represents the contact method for insured.
Datamart	INSD_DIM	INSD_CNTCT_UDF_1	Insured Contact User Defined Field 1	VARCHAR2(60)	This value describes the first insured contact user defined field.
Datamart	INSD_DIM	INSD_CNTCT_UDF_2	Insured Contact User Defined Field 2	VARCHAR2(60)	This value describes the second insured contact user defined field.
Datamart	INSD_DIM	INSD_CNTCT_UDF_3	Insured Contact User Defined Field 3	VARCHAR2(60)	This value describes the third insured contact user defined field.
Datamart	INSD_DIM	INSD_CNTCT_UDF_4	Insured Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth insured contact user defined field.
Datamart	INSD_DIM	INSD_CNTCT_UDF_5	Insured Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth insured contact user defined field.
Datamart	INSD_DIM	INSD_CNTY	Insured County	VARCHAR2(60)	This value identifies the county associated with the insured.
Datamart	INSD_DIM	INSD_CRED_SCORE	Insured Credit Score	VARCHAR2(11)	This system code or number that represents the insured credit rating score.
Datamart	INSD_DIM	INSD_CTRY	Insured Country	VARCHAR2(60)	This value identifies the country associated with the insured.
Datamart	INSD_DIM	INSD_CTY	Insured City	VARCHAR2(32)	This value identifies the city associated with the insured.
Datamart	INSD_DIM	INSD_DBA	Insured Doing Business As	VARCHAR2(170)	This value represents the insured business operating name.
Datamart	INSD_DIM	INSD_DSTRCT	Insured District	VARCHAR2(60)	This value represents the district where the insured is located.
Datamart	INSD_DIM	INSD_GENDER	Insured Gender	VARCHAR2(60)	This value represents the gender (male or female) of the insured.
Datamart	INSD_DIM	INSD_GEOG_BNDRY_UDF_1	Insured Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first insured geographic boundary user defined field.
Datamart	INSD_DIM	INSD_GEOG_BNDRY_UDF_2	Insured Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second insured geographic boundary user defined field.
Datamart	INSD_DIM	INSD_GEOG_BNDRY_UDF_3	Insured Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third insured geographic boundary user defined field.
Datamart	INSD_DIM	INSD_GEOG_BNDRY_UDF_4	Insured Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth insured geographic boundary user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	INSD_DIM	INSD_GEOG_BNDRY_UDF_5	Insured Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth insured geographic boundary user defined field.
Datamart	INSD_DIM	INSD_GOVT_ID_NUM	Insured Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the insured. For example, in the USA: SSN or FEIN.
Datamart	INSD_DIM	INSD_ID	Insured Identifier	NUMBER (22, 0)	This system generated number identifies the insured instance.
Datamart	INSD_DIM	INSD_LATITUDE	Insured Latitude	VARCHAR2(11)	This value represents the latitude location of the insured's location.
Datamart	INSD_DIM	INSD_LONGITUDE	Insured Longitude	VARCHAR2(11)	This value represents the longitude location of the insured's location.
Datamart	INSD_DIM	INSD_MARITAL_STATUS	Insured Marital Status	VARCHAR2(60)	This value represents the present marital condition (single, married, divorced, widowed) of the insured.
Datamart	INSD_DIM	INSD_NAICS_CD	Insured North American Industry Classification System Code	VARCHAR2(60)	This value represents the North America Industry Class (NAICS) code assigned to insured.
Datamart	INSD_DIM	INSD_NAT_KEY	Insured Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the insured.
Datamart	INSD_DIM	INSD_NM	Insured Name	VARCHAR2(170)	This value represents the full given name of the insured.
Datamart	INSD_DIM	INSD_NOB	Insured Nature of Business	VARCHAR2(60)	This value represents the type or category of the business activities done by the insured.
Datamart	INSD_DIM	INSD_NUM_EMP	Insured Number of Employees	NUMBER (22, 0)	This number represents the count of people employed by insured.
Datamart	INSD_DIM	INSD_ORG_UDF_1	Insured Organization User Defined Field 1	VARCHAR2(60)	This value describes the first insured organization user defined field.
Datamart	INSD_DIM	INSD_ORG_UDF_2	Insured Organization User Defined Field 2	VARCHAR2(60)	This value describes the second insured organization user defined field.
Datamart	INSD_DIM	INSD_ORG_UDF_3	Insured Organization User Defined Field 3	VARCHAR2(60)	This value describes the third insured organization user defined field.
Datamart	INSD_DIM	INSD_ORG_UDF_4	Insured Organization User Defined Field 4	VARCHAR2(60)	This value describes the fourth insured organization user defined field.
Datamart	INSD_DIM	INSD_ORG_UDF_5	Insured Organization User Defined Field 5	VARCHAR2(60)	This value describes the fifth insured organization user defined field.
Datamart	INSD_DIM	INSD_PARTY_UDF_1	Insured Party User Defined Field 1	VARCHAR2(60)	This value describes the first insured party user defined field.
Datamart	INSD_DIM	INSD_PARTY_UDF_2	Insured Party User Defined Field 2	VARCHAR2(60)	This value describes the second insured party user defined field.
Datamart	INSD_DIM	INSD_PARTY_UDF_3	Insured Party User Defined Field 3	VARCHAR2(60)	This value describes the third insured party user defined field.
Datamart	INSD_DIM	INSD_PARTY_UDF_4	Insured Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth insured party user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	INSD_DIM	INSD_PARTY_UDF_5	Insured Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth insured party user defined field.
Datamart	INSD_DIM	INSD_PERS_UDF_1	Insured Person User Defined Field 1	VARCHAR2(60)	This value describes the first insured person user defined field.
Datamart	INSD_DIM	INSD_PERS_UDF_2	Insured Person User Defined Field 2	VARCHAR2(60)	This value describes the second insured person user defined field.
Datamart	INSD_DIM	INSD_PERS_UDF_3	Insured Person User Defined Field 3	VARCHAR2(60)	This value describes the third insured person user defined field.
Datamart	INSD_DIM	INSD_PERS_UDF_4	Insured Person User Defined Field 4	VARCHAR2(60)	This value describes the fourth insured person user defined field.
Datamart	INSD_DIM	INSD_PERS_UDF_5	Insured Person User Defined Field 5	VARCHAR2(60)	This value describes the fifth insured person user defined field.
Datamart	INSD_DIM	INSD_PRES_EMPLMT_START_YR	Insured Present Employment Start Year	CHAR(4)	This value represents the calendar year that the insured began working for their current employer.
Datamart	INSD_DIM	INSD_PRIOR_INSUR_CO	Insured Prior Insurance Company	VARCHAR2(60)	This value represents the name of insurance company that last provided insurance prior to policy inception.
Datamart	INSD_DIM	INSD_PSTL_CD	Insured Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	INSD_DIM	INSD_PSTL_CD_PRFX	Insured Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	INSD_DIM	INSD_PSTL_SUB_CD	Insured Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	INSD_DIM	INSD_REGION	Insured Region	VARCHAR2(60)	This value represents the geographic region of the insured's location.
Datamart	INSD_DIM	INSD_RISK_GRADE	Insured Risk Grade	VARCHAR2(60)	This system code represents the A.M. Best or company defined risk grade for insured.
Datamart	INSD_DIM	INSD_RPT_PERIOD	Insured Report Period	VARCHAR2(60)	This value describes the timeframe of activities considered in an insured report.
Datamart	INSD_DIM	INSD_SIC_CD	Insured Standard Industrial Classification Code	VARCHAR2(60)	This system code is the SIC code assigned to the insured.The Standard Industrial Classification (SIC) code is an industry code that identifies the classification of business activity.
Datamart	INSD_DIM	INSD_STATE	Insured State	VARCHAR2(60)	This value identifies the state of the insured's location.
Datamart	INSD_DIM	INSD_TAX_LOC_ID	Insured Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier in the insured's location.
Datamart	INSD_DIM	INSD_TERR	Insured Territory	VARCHAR2(60)	This value represents the territory of the insured's location.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	INSD_DIM	INSD_TYP	Insured Type	VARCHAR2(60)	This value represents the type of entity that contracted with insurance company to obtain a policy.
Datamart	INSD_DIM	INSD_UDF_1	Insured User Defined Field 1	VARCHAR2(60)	This value describes the first insured user defined field.
Datamart	INSD_DIM	INSD_UDF_2	Insured User Defined Field 2	VARCHAR2(60)	This value describes the second insured user defined field.
Datamart	INSD_DIM	INSD_UDF_3	Insured User Defined Field 3	VARCHAR2(60)	This value describes the third insured user defined field.
Datamart	INSD_DIM	INSD_UDF_4	Insured User Defined Field 4	VARCHAR2(60)	This value describes the fourth insured user defined field.
Datamart	INSD_DIM	INSD_UDF_5	Insured User Defined Field 5	VARCHAR2(60)	This value describes the fifth insured user defined field.
Staging	INSUR_CO	AM_BEST_NUM	A.M. Best Number	VARCHAR2(5)	This value represents the insurance company code assigned by A.M. Best.
Warehouse	INSUR_CO	AM_BEST_NUM	A.M. Best Number	VARCHAR2(5)	This value represents the insurance company code assigned by A.M. Best.
Warehouse	INSUR_CO	BEGIN_DT	Begin Date	DATE	This calendar date represents when the insurance company applies.
Warehouse	INSUR_CO	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the insurance company is currently applicable.
Warehouse	INSUR_CO	END_DT	End Date	DATE	This calendar date represents when the insurance company is no longer valid.
Warehouse	INSUR_CO	INSUR_CO_ID	Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the insurance company instance.
Staging	INSUR_CO	INSUR_CO_RLAT_CD	Insurance Company Relationship Code	VARCHAR2(25)	This system code identifies the insurance company relationship.
Staging	INSUR_CO	INSUR_CO_TYP_CD	Insurance Company Type Code	VARCHAR2(25)	This system code identifies insurance company type.
Warehouse	INSUR_CO	INSUR_CO_TYP_CD	Insurance Company Type Code	VARCHAR2(25)	This system code identifies insurance company type.
Warehouse	INSUR_CO	INSUR_CO_TYP_DESC	Insurance Company Type Description	VARCHAR2(60)	This value describes the insurance company type.
Staging	INSUR_CO	INSUR_CO_UDF_CD_1	Insurance Company User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first insurance company user defined field.
Warehouse	INSUR_CO	INSUR_CO_UDF_CD_1	Insurance Company User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first insurance company user defined field.
Staging	INSUR_CO	INSUR_CO_UDF_CD_2	Insurance Company User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second insurance company user defined field.
Warehouse	INSUR_CO	INSUR_CO_UDF_CD_2	Insurance Company User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second insurance company user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	INSUR_CO	INSUR_CO_UDF_CD_3	Insurance Company User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third insurance company user defined field.
Warehouse	INSUR_CO	INSUR_CO_UDF_CD_3	Insurance Company User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third insurance company user defined field.
Staging	INSUR_CO	INSUR_CO_UDF_CD_4	Insurance Company User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth insurance company user defined field.
Warehouse	INSUR_CO	INSUR_CO_UDF_CD_4	Insurance Company User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth insurance company user defined field.
Staging	INSUR_CO	INSUR_CO_UDF_CD_5	Insurance Company User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth insurance company user defined field.
Warehouse	INSUR_CO	INSUR_CO_UDF_CD_5	Insurance Company User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth insurance company user defined field.
Warehouse	INSUR_CO	INSUR_CO_UDF_DESC_1	Insurance Company User Defined Field Description 1	VARCHAR2(60)	This value describes the first insurance company user defined field.
Warehouse	INSUR_CO	INSUR_CO_UDF_DESC_2	Insurance Company User Defined Field Description 2	VARCHAR2(60)	This value describes the second insurance company user defined field.
Warehouse	INSUR_CO	INSUR_CO_UDF_DESC_3	Insurance Company User Defined Field Description 3	VARCHAR2(60)	This value describes the third insurance company user defined field.
Warehouse	INSUR_CO	INSUR_CO_UDF_DESC_4	Insurance Company User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth insurance company user defined field.
Warehouse	INSUR_CO	INSUR_CO_UDF_DESC_5	Insurance Company User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth insurance company user defined field.
Staging	INSUR_CO	ISO_CD	Insurance Services Office Code	VARCHAR2(5)	This value represents the company code assigned by ISO.
Warehouse	INSUR_CO	ISO_CD	Insurance Services Office Code	VARCHAR2(5)	This value represents the Insurance Services Office code assigned to insurance company.
Staging	INSUR_CO	NAIC_CD	National Association of Insurance Commissioners Code	VARCHAR2(5)	This system code is assigned to the company to use for NAIC reporting - The National Association of Insurance Commissioners Code groups types of business.
Warehouse	INSUR_CO	NAIC_CD	National Association of Insurance Commissioners Code Code	VARCHAR2(5)	This system code is assigned to the company to use for NAIC reporting - The National Association of Insurance Commissioners Code groups types of business.
Staging	INSUR_CO	NCCI_CD	NCCI Code	VARCHAR2(5)	This system code is assigned to the company to use for National Council on Compensation insurance (NCCI) reporting.
Warehouse	INSUR_CO	NCCI_CD	NCCI Code	VARCHAR2(5)	This system code is assigned to the company to use for National Council on Compensation insurance (NCCI) reporting.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	INSUR_CO	ORG_ID	Organization Identifier	NUMBER (22, 0)	This system generated number identifies the insurance company organization instance.
Warehouse	INSUR_CO	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Staging	INSUR_CO	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the insurance company with a specific transaction.
Datamart	INSUR_CO_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the insurance company applies.
Datamart	INSUR_CO_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the insurance company is currently applicable.
Datamart	INSUR_CO_DIM	END_DT	End Date	DATE	This calendar date represents when the insurance company is no longer valid.
Datamart	INSUR_CO_DIM	INSUR_CO_AM_BEST_NUM	Insurance Company A.M. Best Number	VARCHAR2(5)	This value represents the number or other identifier that identifies the insurance company A.M. Best Rating.
Datamart	INSUR_CO_DIM	INSUR_CO_BUS_START_DT_ID	Insurance Company Business Start Date Identifier	DATE	This calendar date represents when the insurance company began business operations.
Datamart	INSUR_CO_DIM	INSUR_CO_CNTCT_DESC	Insurance Company Contact Description	VARCHAR2(60)	This value describes the insurance company contact type.
Datamart	INSUR_CO_DIM	INSUR_CO_CNTCT_TYP	Insurance Company Contact Type	VARCHAR2(60)	This value represents the contact method for insurance company.
Datamart	INSUR_CO_DIM	INSUR_CO_CNTCT_UDF_1	Insurance Company Contact User Defined Field 1	VARCHAR2(60)	This value describes the first insured company contact user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_CNTCT_UDF_2	Insurance Company Contact User Defined Field 2	VARCHAR2(60)	This value describes the second insured company contact user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_CNTCT_UDF_3	Insurance Company Contact User Defined Field 3	VARCHAR2(60)	This value describes the third insured company contact user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_CNTCT_UDF_4	Insurance Company Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth insured company contact user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_CNTCT_UDF_5	Insurance Company Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth insured company contact user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_CNTY	Insurance Company County	VARCHAR2(60)	This value identifies the county where insurance company is located.
Datamart	INSUR_CO_DIM	INSUR_CO_CTRY	Insurance Company Country	VARCHAR2(60)	This value identifies the country where insurance company is located.
Datamart	INSUR_CO_DIM	INSUR_CO_CTY	Insurance Company City	VARCHAR2(32)	This value identifies the city where insurance company is located.
Datamart	INSUR_CO_DIM	INSUR_CO_DBA	Insurance Company Doing Business As	VARCHAR2(170)	This value represents the business operating name.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	INSUR_CO_DIM	INSUR_CO_DSTRCT	Insurance Company District	VARCHAR2(60)	This value represents the district where insurance company is located.
Datamart	INSUR_CO_DIM	INSUR_CO_GEOG_BNDRY_UDF_1	Insurance Company Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first insurance company geographic boundary user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_GEOG_BNDRY_UDF_2	Insurance Company Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second insurance company geographic boundary user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_GEOG_BNDRY_UDF_3	Insurance Company Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third insurance company geographic boundary user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_GEOG_BNDRY_UDF_4	Insurance Company Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth insurance company geographic boundary user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_GEOG_BNDRY_UDF_5	Insurance Company Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth insurance company geographic boundary user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_GOVT_ID_NUM	Insurance Company Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the insurance company. For example, in the USA: SSN or FEIN.
Datamart	INSUR_CO_DIM	INSUR_CO_ID	Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the insurance company instance.
Datamart	INSUR_CO_DIM	INSUR_CO_ISO_CD	Insurance Company Insurance Services Office Code	VARCHAR2(5)	This value represents the insurance company's Insurance Services Office (ISO) code.
Datamart	INSUR_CO_DIM	INSUR_CO_LATITUDE	Insurance Company Latitude	VARCHAR2(11)	This value represents the latitude location of insurance company.
Datamart	INSUR_CO_DIM	INSUR_CO_LONGITUDE	Insurance Company Longitude	VARCHAR2(11)	This value represents the longitude location of insurance company.
Datamart	INSUR_CO_DIM	INSUR_CO_NAIC_CD	Insurance Company National Association of Insurance Commissioners Code	VARCHAR2(5)	This value represents the National Association of Insurance Commissioners Code (NAIC) code assigned to insurance company.
Datamart	INSUR_CO_DIM	INSUR_CO_NAICS_CD	Insurance Company North American Industry Classification System Code	VARCHAR2(60)	This value represents the North America Industry Class (NAICS) code assigned to insurance company.
Datamart	INSUR_CO_DIM	INSUR_CO_NAT_KEY	Insurance Company Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the insurance company.
Datamart	INSUR_CO_DIM	INSUR_CO_NCCI_CD	Insurance Company National Council on Compensation Insurance Code	VARCHAR2(5)	This value represents the insurance company's National Council on Compensation insurance (NCCI) code.
Datamart	INSUR_CO_DIM	INSUR_CO_NM	Insurance Company Name	VARCHAR2(170)	This value represents the name of insurance company.
Datamart	INSUR_CO_DIM	INSUR_CO_NOB	Insurance Company Nature of Business	VARCHAR2(60)	This value represents the type or category of the business activities done by the insurance company.
Datamart	INSUR_CO_DIM	INSUR_CO_NUM_EMP	Insurance Company Number of Employees	NUMBER (22, 0)	This number represents the count of people employed at insurance company.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	INSUR_CO_DIM	INSUR_CO_ORG_UDF_1	Insurance Company Organization User Defined Field 1	VARCHAR2(60)	This value describes the first insurance company organization user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_ORG_UDF_2	Insurance Company Organization User Defined Field 2	VARCHAR2(60)	This value describes the second insurance company organization user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_ORG_UDF_3	Insurance Company Organization User Defined Field 3	VARCHAR2(60)	This value describes the third insurance company organization user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_ORG_UDF_4	Insurance Company Organization User Defined Field 4	VARCHAR2(60)	This value describes the fourth insurance company organization user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_ORG_UDF_5	Insurance Company Organization User Defined Field 5	VARCHAR2(60)	This value describes the fifth insurance company organization user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_PARTY_UDF_1	Insurance Company Party User Defined Field 1	VARCHAR2(60)	This value describes the first insurance company party user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_PARTY_UDF_2	Insurance Company Party User Defined Field 2	VARCHAR2(60)	This value describes the second insurance company party user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_PARTY_UDF_3	Insurance Company Party User Defined Field 3	VARCHAR2(60)	This value describes the third insurance company party user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_PARTY_UDF_4	Insurance Company Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth insurance company party user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_PARTY_UDF_5	Insurance Company Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth insurance company party user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_PSTL_CD	Insurance Company Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	INSUR_CO_DIM	INSUR_CO_PSTL_CD_PRFX	Insurance Company Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	INSUR_CO_DIM	INSUR_CO_PSTL_SUB_CD	Insurance Company Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	INSUR_CO_DIM	INSUR_CO_REGION	Insurance Company Region	VARCHAR2(60)	This value represents the geographic region where insurance company is located.
Datamart	INSUR_CO_DIM	INSUR_CO_SIC_CD	Insurance Company Standard Industrial Classification Code	VARCHAR2(60)	The Standard Industrial Classification (SIC) code is an industry code that identifies the classification of business activity. This system code is the SIC code assigned to the insurance company.
Datamart	INSUR_CO_DIM	INSUR_CO_STATE	Insurance Company State	VARCHAR2(60)	This value identifies the state where insurance company is located.
Datamart	INSUR_CO_DIM	INSUR_CO_TAX_LOC_ID	Insurance Company Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier in the insurance company's location.
Datamart	INSUR_CO_DIM	INSUR_CO_TERR	Insurance Company Territory	VARCHAR2(60)	This value represents the territory where insurance company is located.
Datamart	INSUR_CO_DIM	INSUR_CO_TYP	Insurance Company Type	VARCHAR2(60)	This value represents the classification of the insurance company's primary operations.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	INSUR_CO_DIM	INSUR_CO_UDF_1	Insurance Company User Defined Field 1	VARCHAR2(60)	This value describes the first insurance company user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_UDF_2	Insurance Company User Defined Field 2	VARCHAR2(60)	This value describes the second insurance company user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_UDF_3	Insurance Company User Defined Field 3	VARCHAR2(60)	This value describes the third insurance company user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_UDF_4	Insurance Company User Defined Field 4	VARCHAR2(60)	This value describes the fourth insurance company user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_UDF_5	Insurance Company User Defined Field 5	VARCHAR2(60)	This value describes the fifth insurance company user defined field.
Staging	LITG	ALT_DISPUTE_RESOLUTION_CD	Alternate Dispute Resolution Code	VARCHAR2(25)	This system code identifies the outcome of using an intermediary for dispute settlement.
Warehouse	LITG	ALT_DISPUTE_RESOLUTION_CD	Alternate Dispute Resolution Code	VARCHAR2(25)	This system code identifies the outcome of using an intermediary for dispute settlement.
Warehouse	LITG	BEGIN_DT	Begin Date	DATE	This calendar date represents when the litigation began.
Staging	LITG	COMPENSATORY_DEMAND_AMT	Compensatory Demand Amount	NUMBER (14,3)	This number represents the amount of requested compensatory damages.
Warehouse	LITG	COMPENSATORY_DEMAND_AMT	Compensatory Demand Amount	NUMBER (14, 3)	This number represents the amount of requested compensatory damages.
Staging	LITG	COMPENSATORY_OFFER_AMT	Compensatory Offer Amount	NUMBER (14,3)	This number represents the amount of offered compensatory damages.
Warehouse	LITG	COMPENSATORY_OFFER_AMT	Compensatory Offer Amount	NUMBER (14, 3)	This number represents the amount of offered compensatory damages.
Warehouse	LITG	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the litigation is currently applicable.
Staging	LITG	DISCLOSURE_DT	Disclosure Date	DATE	This date represents the calendar date of disclosure of information related to litigation.
Warehouse	LITG	DISCLOSURE_DT	Disclosure Date	DATE	This date represents the calendar date of disclosure of information related to litigation.
Warehouse	LITG	END_DT	End Date	DATE	This calendar date represents when the litigation is no longer valid.
Staging	LITG	LITG_AMT	Litigation Amount	NUMBER (14,3)	This number represents the amount of litigation case.
Warehouse	LITG	LITG_AMT	Litigation Amount	NUMBER (14, 3)	This number represents the amount of litigation case.
Staging	LITG	LITG_CLOSED_DT	Litigation Closed Date	DATE	This calendar date represents when litigation case was closed.
Warehouse	LITG	LITG_CLOSED_DT	Litigation Closed Date	DATE	This calendar date represents when litigation case was closed.
Staging	LITG	LITG_CNTY_CD	Litigation County Code	VARCHAR2(25)	This system code describes a litigation county.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	LITG	LITG_CNTY_CD	Litigation County Code	VARCHAR2(25)	This system code describes a litigation county.
Warehouse	LITG	LITG_CNTY_DESC	Litigation County Description	VARCHAR2(60)	This value identifies the county of jurisdiction over litigation case.
Staging	LITG	LITG_DISPOSITION_CD	Litigation Disposition Code	VARCHAR2(25)	This system code identifies the litigation disposition.
Warehouse	LITG	LITG_DISPOSITION_CD	Litigation Disposition Code	VARCHAR2(25)	This system code identifies the litigation disposition.
Warehouse	LITG	LITG_DISPOSITION_DESC	Litigation Disposition Description	VARCHAR2(60)	This value describes the litigation Disposition.
Warehouse	LITG	LITG_ID	Litigation Identifier	NUMBER (22, 0)	This system generated number identifies the litigation instance.
Staging	LITG	LITG_NAT_KEY	Litigation Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the litigation.
Warehouse	LITG	LITG_NAT_KEY	Litigation Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the litigation.
Staging	LITG	LITG_OPENED_DT	Litigation Opened Date	DATE	This calendar date represents when litigation case was filed in court.
Warehouse	LITG	LITG_OPENED_DT	Litigation Opened Date	DATE	This calendar date represents when litigation case was filed in court.
Staging	LITG	LITG_STATE_CD	Litigation State Code	VARCHAR2(25)	This system code identifies the litigation state.
Warehouse	LITG	LITG_STATE_CD	Litigation State Code	VARCHAR2(25)	This system code identifies the litigation state.
Warehouse	LITG	LITG_STATE_DESC	Litigation State Description	VARCHAR2(60)	This value represents the name of the litigation state.
Staging	LITG	LITG_UDF_CD_1	Litigation User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first litigation user defined field.
Warehouse	LITG	LITG_UDF_CD_1	Litigation User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first litigation user defined field.
Staging	LITG	LITG_UDF_CD_2	Litigation User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second litigation user defined field.
Warehouse	LITG	LITG_UDF_CD_2	Litigation User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second litigation user defined field.
Staging	LITG	LITG_UDF_CD_3	Litigation User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third litigation user defined field.
Warehouse	LITG	LITG_UDF_CD_3	Litigation User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third litigation user defined field.
Staging	LITG	LITG_UDF_CD_4	Litigation User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth litigation user defined field.
Warehouse	LITG	LITG_UDF_CD_4	Litigation User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth litigation user defined field.
Staging	LITG	LITG_UDF_CD_5	Litigation User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth litigation user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	LITG	LITG_UDF_CD_5	Litigation User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth litigation user defined field.
Warehouse	LITG	LITG_UDF_DESC_1	Litigation User Defined Field Description 1	VARCHAR2(60)	This value describes the first litigation user defined field.
Warehouse	LITG	LITG_UDF_DESC_2	Litigation User Defined Field Description 2	VARCHAR2(60)	This value describes the second litigation user defined field.
Warehouse	LITG	LITG_UDF_DESC_3	Litigation User Defined Field Description 3	VARCHAR2(60)	This value describes the third litigation user defined field.
Warehouse	LITG	LITG_UDF_DESC_4	Litigation User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth litigation user defined field.
Warehouse	LITG	LITG_UDF_DESC_5	Litigation User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth litigation user defined field.
Staging	LITG	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the litigation with a specific transaction.
Staging	LITG	TRIAL_DT	Trial Date	DATE	This calendar date represents the when the trial is scheduled, or has already occurred.
Warehouse	LITG	TRIAL_DT	Trial Date	DATE	This calendar date represents the when the trial is scheduled, or has already occurred.
Datamart	LITG_DIM	ALT_DISPUTE_RESOLUTION	Alternate Dispute Resolution	VARCHAR2(60)	This value represents the intermediary for used for dispute settlement.
Datamart	LITG_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the litigation begins.
Datamart	LITG_DIM	COMPENSATORY_DEMAND_AMT	Compensatory Demand Amount	NUMBER (14, 3)	This number represents the amount of requested compensatory damages.
Datamart	LITG_DIM	COMPENSATORY_OFFER_AMT	Compensatory Offer Amount	NUMBER (14, 3)	This number represents the amount of offered compensatory damages.
Datamart	LITG_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the litigation is currently applicable.
Datamart	LITG_DIM	DISCLOSURE_DT_ID	Disclosure Date Identifier	DATE	This date is the unique identifier assigned to the litigation disclosure date.
Datamart	LITG_DIM	END_DT	End Date	DATE	This calendar date represents when the litigation is no longer valid.
Datamart	LITG_DIM	LITG_AMT	Litigation Amount	NUMBER (14, 3)	This number represents the amount of litigation case.
Datamart	LITG_DIM	LITG_CLOSED_DT_ID	Litigation Closed Date Identifier	DATE	This calendar date represents when identifies when litigation case was closed.
Datamart	LITG_DIM	LITG_CNTY	Litigation County	VARCHAR2(60)	This value identifies the county where litigation occurs.
Datamart	LITG_DIM	LITG_DISPOSITION	Litigation Disposition	VARCHAR2(60)	This value describes the status of a litigation case.
Datamart	LITG_DIM	LITG_ID	Litigation Identifier	NUMBER (22, 0)	This system generated number identifies the litigation instance.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	LITG_DIM	LITG_NAT_KEY	Litigation Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the litigation.
Datamart	LITG_DIM	LITG_OPENED_DT_ID	Litigation Opened Date Identifier	DATE	This calendar date represents when identifies when litigation case was filed in court.
Datamart	LITG_DIM	LITG_STATE	Litigation State	VARCHAR2(60)	This value identifies the state associated with the litigation.
Datamart	LITG_DIM	LITG_UDF_1	Litigation User Defined Field 1	VARCHAR2(60)	This value describes the first litigation user defined field.
Datamart	LITG_DIM	LITG_UDF_2	Litigation User Defined Field 2	VARCHAR2(60)	This value describes the second litigation user defined field.
Datamart	LITG_DIM	LITG_UDF_3	Litigation User Defined Field 3	VARCHAR2(60)	This value describes the third litigation user defined field.
Datamart	LITG_DIM	LITG_UDF_4	Litigation User Defined Field 4	VARCHAR2(60)	This value describes the fourth litigation user defined field.
Datamart	LITG_DIM	LITG_UDF_5	Litigation User Defined Field 5	VARCHAR2(60)	This value describes the fifth litigation user defined field.
Datamart	LITG_DIM	TRIAL_DT_ID	Trial Date Identifier	DATE	This calendar date represents when identifies when a trial begins.
Warehouse	LMT	BEGIN_DT	Begin Date	DATE	This calendar date represents when the limit applies.
Warehouse	LMT	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the limit is currently applicable.
Warehouse	LMT	END_DT	End Date	DATE	This calendar date represents when the limit is no longer valid.
Staging	LMT	FIRST_LMT	First Limit	VARCHAR2(15)	This value represents the first limit.
Warehouse	LMT	FIRST_LMT	First Limit	VARCHAR2(15)	This value represents the first limit.
Staging	LMT	FULL_LMT	Full Limit	VARCHAR2(50)	This value represents the unabbreviated limit amount.
Warehouse	LMT	FULL_LMT	Full Limit	VARCHAR2(50)	This value represents the unabbreviated limit amount.
Staging	LMT	LMT_APPLIES_TO_CD	Limit Applies To Code	VARCHAR2(25)	This system code identifies the limit applies to.
Warehouse	LMT	LMT_APPLIES_TO_CD	Limit Applies To Code	VARCHAR2(25)	This system code identifies the limit applies to.
Warehouse	LMT	LMT_APPLIES_TO_DESC	Limit Applies To Description	VARCHAR2(60)	This value describes the classification of coverage for which a limit applies.
Staging	LMT	LMT_BASIS_CD	Limit Basis Code	VARCHAR2(25)	This system code identifies limit basis.
Warehouse	LMT	LMT_BASIS_CD	Limit Basis Code	VARCHAR2(25)	This system code identifies limit basis.
Warehouse	LMT	LMT_BASIS_DESC	Limit Basis Description	VARCHAR2(60)	This value describes limit basis.
Warehouse	LMT	LMT_ID	Limit Identifier	NUMBER (22, 0)	This system generated number identifies the limit instance.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	LMT	LMT_NAT_KEY	Limit Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the limit.
Warehouse	LMT	LMT_NAT_KEY	Limit Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the limit.
Staging	LMT	LMT_TYP_CD	Limit Type Code	VARCHAR2(25)	This system code identifies limit type.
Warehouse	LMT	LMT_TYP_CD	Limit Type Code	VARCHAR2(25)	This system code identifies limit type.
Warehouse	LMT	LMT_TYP_DESC	Limit Type Description	VARCHAR2(60)	This value describes limit type.
Staging	LMT	LMT_UDF_CD_1	Limit User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first limit user defined field.
Warehouse	LMT	LMT_UDF_CD_1	Limit User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first limit user defined field.
Staging	LMT	LMT_UDF_CD_2	Limit User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second limit user defined field.
Warehouse	LMT	LMT_UDF_CD_2	Limit User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second limit user defined field.
Staging	LMT	LMT_UDF_CD_3	Limit User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third limit user defined field.
Warehouse	LMT	LMT_UDF_CD_3	Limit User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third limit user defined field.
Staging	LMT	LMT_UDF_CD_4	Limit User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth limit user defined field.
Warehouse	LMT	LMT_UDF_CD_4	Limit User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth limit user defined field.
Staging	LMT	LMT_UDF_CD_5	Limit User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth limit user defined field.
Warehouse	LMT	LMT_UDF_CD_5	Limit User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth limit user defined field.
Warehouse	LMT	LMT_UDF_DESC_1	Limit User Defined Field Description 1	VARCHAR2(60)	This value describes the first limit user defined field.
Warehouse	LMT	LMT_UDF_DESC_2	Limit User Defined Field Description 2	VARCHAR2(60)	This value describes the second limit user defined field.
Warehouse	LMT	LMT_UDF_DESC_3	Limit User Defined Field Description 3	VARCHAR2(60)	This value describes the third limit user defined field.
Warehouse	LMT	LMT_UDF_DESC_4	Limit User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth limit user defined field.
Warehouse	LMT	LMT_UDF_DESC_5	Limit User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth limit user defined field.
Staging	LMT	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the limit with a specific transaction.
Staging	LMT	SECOND_LMT	Second Limit	VARCHAR2(15)	This value represents the second limit.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	LMT	SECOND_LMT	Second Limit	VARCHAR2(15)	This value represents the second limit.
Staging	LMT	THIRD_LMT	Third Limit	VARCHAR2(15)	This value identifies the third limit.
Warehouse	LMT	THIRD_LMT	Third Limit	VARCHAR2(15)	This value identifies the third limit.
Staging	LMT	VALUATION_CD	Valuation Code	VARCHAR2(25)	This value describes the code assigned in the method of loss valuation.
Warehouse	LMT	VALUATION_CD	Valuation Code	VARCHAR2(25)	This system code identifies the type of valuation or valuation requested.
Warehouse	LMT	VALUATION_DESC	Valuation Description	VARCHAR2(60)	This value describes the code assigned in the method of loss valuation.
Datamart	LMT_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the limit applies.
Datamart	LMT_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the limit is currently applicable.
Datamart	LMT_DIM	END_DT	End Date	DATE	This calendar date represents when the limit is no longer valid.
Datamart	LMT_DIM	FIRST_LMT	First Limit	VARCHAR2(15)	This value represents the first limit.
Datamart	LMT_DIM	FULL_LMT	Full Limit	VARCHAR2(50)	This value represents the unabbreviated limit amount.
Datamart	LMT_DIM	LMT_APPLIES_TO	Limit Applies To	VARCHAR2(60)	This value represents the classification of coverage for which a limit applies.
Datamart	LMT_DIM	LMT_BASIS	Limit Basis	VARCHAR2(60)	This value represents the basis to which limits are applied.
Datamart	LMT_DIM	LMT_ID	Limit Identifier	NUMBER (22, 0)	This system generated number identifies the limit instance.
Datamart	LMT_DIM	LMT_NAT_KEY	Limit Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the limit.
Datamart	LMT_DIM	LMT_TYP	Limit Type	VARCHAR2(60)	This value represents the indicator of the category of how a limit is determined.
Datamart	LMT_DIM	LMT_UDF_1	Limit User Defined Field 1	VARCHAR2(60)	This value describes the first limit user defined field.
Datamart	LMT_DIM	LMT_UDF_2	Limit User Defined Field 2	VARCHAR2(60)	This value describes the second limit user defined field.
Datamart	LMT_DIM	LMT_UDF_3	Limit User Defined Field 3	VARCHAR2(60)	This value describes the third limit user defined field.
Datamart	LMT_DIM	LMT_UDF_4	Limit User Defined Field 4	VARCHAR2(60)	This value describes the fourth limit user defined field.
Datamart	LMT_DIM	LMT_UDF_5	Limit User Defined Field 5	VARCHAR2(60)	This value describes the fifth limit user defined field.
Datamart	LMT_DIM	SECOND_LMT	Second Limit	VARCHAR2(15)	This value represents the second limit of limit dimension table.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	LMT_DIM	THIRD_LMT	Third Limit	VARCHAR2(15)	This value identifies the third limit of limit dimension table.
Datamart	LMT_DIM	VALUATION_CD	Valuation Code	VARCHAR2(60)	This value describes the code assigned in the method of loss valuation.
Warehouse	LOB	BEGIN_DT	Begin Date	DATE	This calendar date represents when the line of business applies.
Staging	LOB	CO_PROD_CD	Company Product Code	VARCHAR2(25)	This system code identifies the company product.
Warehouse	LOB	CO_PROD_CD	Company Product Code	VARCHAR2(25)	This system code identifies the company product.
Warehouse	LOB	CO_PROD_DESC	Company Producer Description	VARCHAR2(60)	This value describes the company producer.
Warehouse	LOB	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the line of business is currently applicable.
Warehouse	LOB	END_DT	End Date	DATE	This calendar date represents when the line of business is no longer valid.
Staging	LOB	LOB_CD	Line Of Business Code	VARCHAR2(25)	This system code identifies the line of business classification.
Warehouse	LOB	LOB_CD	Line Of Business Code	VARCHAR2(25)	This system code identifies the line of business classification.
Warehouse	LOB	LOB_DESC	Line Of Business Description	VARCHAR2(60)	This value describes the line of business.
Warehouse	LOB	LOB_ID	Line Of Business Identifier	NUMBER (22, 0)	This system generated number identifies the line of business instance.
Staging	LOB	LOB_NAT_KEY	Line of Business Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the line of business.
Warehouse	LOB	LOB_NAT_KEY	Line of Business Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the line of business.
Staging	LOB	LOB_SUB_CD	Line Of Business Sub Code	VARCHAR2(25)	This system code identifies the line of business sub code that further refines the line of business code.
Warehouse	LOB	LOB_SUB_CD	Line Of Business Sub Code	VARCHAR2(25)	This system code identifies the line of business sub code that further refines the line of business code.
Warehouse	LOB	LOB_SUB_DESC	Line Of Business Sub Code Description	VARCHAR2(60)	This value represents the further breakdown of line of business that may be defined by company.
Staging	LOB	LOB_UDF_CD_1	Line of Business User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first line of business user defined field.
Warehouse	LOB	LOB_UDF_CD_1	Line of Business User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first line of business user defined field.
Staging	LOB	LOB_UDF_CD_2	Line of Business User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second line of business user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	LOB	LOB_UDF_CD_2	Line of Business User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second line of business user defined field.
Staging	LOB	LOB_UDF_CD_3	Line of Business User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third line of business user defined field.
Warehouse	LOB	LOB_UDF_CD_3	Line of Business User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third line of business user defined field.
Staging	LOB	LOB_UDF_CD_4	Line of Business User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth line of business user defined field.
Warehouse	LOB	LOB_UDF_CD_4	Line of Business User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth line of business user defined field.
Staging	LOB	LOB_UDF_CD_5	Line of Business User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth line of business user defined field.
Warehouse	LOB	LOB_UDF_CD_5	Line of Business User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth line of business user defined field.
Warehouse	LOB	LOB_UDF_DESC_1	Line of Business User Defined Field Description 1	VARCHAR2(60)	This value describes the first line of business user defined field.
Warehouse	LOB	LOB_UDF_DESC_2	Line of Business User Defined Field Description 2	VARCHAR2(60)	This value describes the second line of business user defined field.
Warehouse	LOB	LOB_UDF_DESC_3	Line of Business User Defined Field Description 3	VARCHAR2(60)	This value describes the third line of business user defined field.
Warehouse	LOB	LOB_UDF_DESC_4	Line of Business User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth line of business user defined field.
Warehouse	LOB	LOB_UDF_DESC_5	Line of Business User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth line of business user defined field.
Staging	LOB	PSNL_OR_COML_CD	Personal Or Commercial Code	VARCHAR2(25)	This system code indicates if the policy is a personal or commercial policy.
Warehouse	LOB	PSNL_OR_COML_CD	Personal Or Commercial Code	VARCHAR2(25)	This system code indicates if the policy is a personal or commercial policy.
Warehouse	LOB	PSNL_OR_COML_DESC	Personal Or Commercial Description	VARCHAR2(60)	This value describes a policy's status as personal or commercial lines.
Staging	LOB	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the line of business with a specific transaction.
Warehouse	LOB	SYS_LOB_CD	System Line of Business Code	VARCHAR2(25)	This system code represents a system line of business.
Warehouse	LOB	SYS_LOB_DESC	System Line of Business Description	VARCHAR2(60)	This value describes the system line of business.
Datamart	LOB_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the line of business applies.
Datamart	LOB_DIM	CO_PROD_CD	Company Producer Code	VARCHAR2(60)	This system code identifies the company producer.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	LOB_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the line of business is currently applicable.
Datamart	LOB_DIM	END_DT	End Date	DATE	This calendar date represents when the line of business is no longer valid.
Datamart	LOB_DIM	LOB_CD	Line Of Business Code	VARCHAR2(60)	This system code identifies the line of business classification.
Datamart	LOB_DIM	LOB_ID	Line Of Business Identifier	NUMBER (22, 0)	This system generated number identifies the line of business instance.
Datamart	LOB_DIM	LOB_NAT_KEY	Line of Business Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the line of business.
Datamart	LOB_DIM	LOB_SUB_CD	Line Of Business Sub Code	VARCHAR2(60)	This system code identifies the line of business sub code that further refines the line of business code. This system code identifies the product classification of the policy.
Datamart	LOB_DIM	LOB_UDF_1	Line of Business User Defined Field 1	VARCHAR2(60)	This value describes the first line of business user defined field.
Datamart	LOB_DIM	LOB_UDF_2	Line of Business User Defined Field 2	VARCHAR2(60)	This value describes the second line of business user defined field.
Datamart	LOB_DIM	LOB_UDF_3	Line of Business User Defined Field 3	VARCHAR2(60)	This value describes the third line of business user defined field.
Datamart	LOB_DIM	LOB_UDF_4	Line of Business User Defined Field 4	VARCHAR2(60)	This value describes the fourth line of business user defined field.
Datamart	LOB_DIM	LOB_UDF_5	Line of Business User Defined Field 5	VARCHAR2(60)	This value describes the fifth line of business user defined field.
Datamart	LOB_DIM	PSNL_OR_COML	Personal Or Commercial	VARCHAR2(60)	This value describes a policy coverage type as personal or commercial lines.
Datamart	LOB_DIM	SYS_LOB_CD	System Line of Business Code	VARCHAR2(60)	This system code represents the system line of business.
Datamart	MTH_DIM	CAL_HALF_YR	Calendar Half Year	CHAR(2)	This value represents the the calendar half year for the month dimension.
Datamart	MTH_DIM	CAL_MTH_LONG_NM	Calendar Month Long Name	VARCHAR2(60)	This value identifies calendar month long name.
Datamart	MTH_DIM	CAL_MTH_NM	Calendar Month Name	VARCHAR2(60)	This description identifies calendar month name.
Datamart	MTH_DIM	CAL_MTH_NUM_IN_YR	Calendar Month Number In Year	NUMBER (22, 0)	This number identifies the calendar month in year.
Datamart	MTH_DIM	CAL_QTR	Calendar Quarter	CHAR(2)	This value represents the calendar quarter for the month dimension.
Datamart	MTH_DIM	CAL_QTR_NUM_IN_YR	Calendar Quarter Number In Year	NUMBER (22, 0)	This number represents the calendar quarter number in year.
Datamart	MTH_DIM	CAL_YR	Calendar Year	CHAR(4)	This value represents the calendar year.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	MTH_DIM	CAL_YR_MTH	Calendar Year Month	CHAR(6)	This value represents the calendar year month.
Datamart	MTH_DIM	CAL_YR_MTH_NUM	Calendar Year Month Number	NUMBER (22, 0)	This value represents the calendar year month.
Datamart	MTH_DIM	CAL_YR_NUM	Calendar Year Number	NUMBER (22, 0)	This number identifies the calendar year.
Datamart	MTH_DIM	CAL_YR_QTR	Calendar Year Quarter	CHAR(6)	A value that identifies calendar year quarter.
Datamart	MTH_DIM	CAL_YR_QTR_NUM	Calendar Year Quarter Number	NUMBER (22, 0)	This number identifies the calendar year quarter number.
Datamart	MTH_DIM	FISCAL_HALF_YR	Fiscal Half Year	CHAR(2)	This value represents the fiscal half year.
Datamart	MTH_DIM	FISCAL_MTH_LONG_NM	Fiscal Month Long Name	VARCHAR2(60)	This value represents the long name of fiscal month.
Datamart	MTH_DIM	FISCAL_MTH_NM	Fiscal Month Name	VARCHAR2(60)	This value represents the name of fiscal month.
Datamart	MTH_DIM	FISCAL_MTH_NUM_IN_YR	Fiscal Month Number In Year	NUMBER (22, 0)	This number identifies fiscal month number in year.
Datamart	MTH_DIM	FISCAL_QTR	Fiscal Quarter	CHAR(2)	This value represents the fiscal quarter.
Datamart	MTH_DIM	FISCAL_QTR_NUM_IN_YR	Fiscal Quarter Number In Year	NUMBER (22, 0)	This number identifies fiscal quarter number in year.
Datamart	MTH_DIM	FISCAL_YR	Fiscal Year	CHAR(4)	This value describes the fiscal year.
Datamart	MTH_DIM	FISCAL_YR_MTH	Fiscal Year Month	CHAR(6)	This value describes the fiscal year month.
Datamart	MTH_DIM	FISCAL_YR_MTH_NUM	Fiscal Year Month Number	NUMBER (22, 0)	This number represents the fiscal year month number.
Datamart	MTH_DIM	FISCAL_YR_NUM	Fiscal Year Number	NUMBER (22, 0)	This number represents the fiscal year number.
Datamart	MTH_DIM	FISCAL_YR_QTR	Fiscal Year Quarter	CHAR(6)	This value describes the fiscal year quarter.
Datamart	MTH_DIM	FISCAL_YR_QTR_NUM	Fiscal Year Quarter Number	NUMBER (22, 0)	This number represents the fiscal year quarter number.
Datamart	MTH_DIM	MTH_ID	Month Identifier	NUMBER (22, 0)	This number represents the month instance.
Warehouse	ORG	BEGIN_DT	Begin Date	DATE	This calendar date represents when the organization applies.
Staging	ORG	BUS_START_DT	Business Start Date	DATE	This calendar date represents when the insurance company began business operations.
Warehouse	ORG	BUS_START_DT	Business Start Date	DATE	This calendar date represents when the insurance company began business operations.
Warehouse	ORG	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the organization is currently applicable.
Staging	ORG	DBA	Doing Business As	VARCHAR2(170)	This value represents the type or category of the business activities done by the organization.
Warehouse	ORG	DBA	Doing Business As	VARCHAR2(170)	This value represents the type or category of the business activities done by the producer.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	ORG	END_DT	End Date	DATE	This calendar date represents when the organization is no longer valid.
Staging	ORG	NAICS_CD	North American Industry Classification System Code	VARCHAR2(25)	This system code is assigned to the company to use for NAICS reporting - The North American Industry Classification System groups types of business.
Warehouse	ORG	NAICS_CD	North American Industry Classification System Code	VARCHAR2(25)	This system code is assigned to the company to use for NAICS reporting - The North American Industry Classification System groups types of business.
Warehouse	ORG	NAICS_DESC	North American Industry Classification System Description	VARCHAR2(60)	This value describes The North American Industry Classification System code.
Staging	ORG	NOB_CD	Nature of Business Code	VARCHAR2(25)	This system code identifies the nature of business of organization.
Warehouse	ORG	NOB_CD	Nature of Business Code	VARCHAR2(25)	This system code identifies the nature of business of organization.
Warehouse	ORG	NOB_DESC	Nature of Business Description	VARCHAR2(60)	This value represents the type or category of the business activities done by the organization.
Staging	ORG	NUM_EMP	Number Of Employees	NUMBER (22,0)	This number represents the count of people employed by organization.
Warehouse	ORG	NUM_EMP	Number Of Employees	NUMBER (22, 0)	This number represents the count of people employed by organization.
Warehouse	ORG	ORG_ID	Organization Identifier	NUMBER (22, 0)	This system generated number identifies the organization instance.
Staging	ORG	ORG_NM	Organization Name	VARCHAR2(170)	This value represents the name of an organization.
Warehouse	ORG	ORG_NM	Organization Name	VARCHAR2(170)	This value represents the name of an organization.
Staging	ORG	ORG_RLAT_CD	Organization Relationship Code	VARCHAR2(25)	This system code indicates the organization relationship.
Staging	ORG	ORG_UDF_CD_1	Organization User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first organization user defined field.
Warehouse	ORG	ORG_UDF_CD_1	Organization User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first organization user defined field.
Staging	ORG	ORG_UDF_CD_2	Organization User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second organization user defined field.
Warehouse	ORG	ORG_UDF_CD_2	Organization User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second organization user defined field.
Staging	ORG	ORG_UDF_CD_3	Organization User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third organization user defined field.
Warehouse	ORG	ORG_UDF_CD_3	Organization User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third organization user defined field.
Staging	ORG	ORG_UDF_CD_4	Organization User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth organization user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	ORG	ORG_UDF_CD_4	Organization User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth organization user defined field.
Staging	ORG	ORG_UDF_CD_5	Organization User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth organization user defined field.
Warehouse	ORG	ORG_UDF_CD_5	Organization User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth organization user defined field.
Warehouse	ORG	ORG_UDF_DESC_1	Organization User Defined Field Description 1	VARCHAR2(60)	This value describes the first organization user defined field.
Warehouse	ORG	ORG_UDF_DESC_2	Organization User Defined Field Description 2	VARCHAR2(60)	This value describes the second organization user defined field.
Warehouse	ORG	ORG_UDF_DESC_3	Organization User Defined Field Description 3	VARCHAR2(60)	This value describes the third organization user defined field.
Warehouse	ORG	ORG_UDF_DESC_4	Organization User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth organization user defined field.
Warehouse	ORG	ORG_UDF_DESC_5	Organization User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth organization user defined field.
Warehouse	ORG	PARTY_ID	Party Identifier	NUMBER (22, 0)	This system generated number identifies the party.
Warehouse	ORG	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Staging	ORG	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the organization with a specific transaction.
Warehouse	ORG	SIC_CD	Standard Industrial Classification Code	VARCHAR2(25)	The Standard Industrial Classification (SIC) code is an industry code that identifies the classification of business activity. This is the SIC assigned to the company.
Staging	ORG	SIC_CD	Standard Industrial Classification Code	VARCHAR2(25)	The Standard Industrial Classification (SIC) code is an industry code that identifies the classification of business activity. This is the SIC assigned to the company.
Warehouse	ORG	SIC_DESC	Standard Industrial Classification Code Description	VARCHAR2(60)	This value describes the Standard industrial Classification code assigned to the company.
Warehouse	PA_DRV	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage in the personal driver begins.
Staging	PA_DRV	COMMUTER_DSCNT_FLG	Commuter Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of commuter discount.
Warehouse	PA_DRV	COMMUTER_DSCNT_FLG	Commuter Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of commuter discount.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PA_DRV	COMMUTER_DSCNT_PCT	Commuter Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when commuter discount applies.
Warehouse	PA_DRV	COMMUTER_DSCNT_PCT	Commuter Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when commuter discount applies.
Warehouse	PA_DRV	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the personal vehicle driver is currently applicable.
Staging	PA_DRV	DFEN_DRV_CD	Defensive Driving Code	VARCHAR2(25)	This system code indicates the type of defensive driving course the driver completed.
Warehouse	PA_DRV	DFEN_DRV_CD	Defensive Driving Code	VARCHAR2(25)	This system code indicates the type of defensive driving course the driver completed.
Warehouse	PA_DRV	DFEN_DRV_DESC	Defensive Driving Description	VARCHAR2(60)	This value describes the defensive driving code.
Staging	PA_DRV	DFEN_DRV_TRNG_DSCNT_FLG	Defensive Driving Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a defensive driver training discount is applicable.
Warehouse	PA_DRV	DFEN_DRV_TRNG_DSCNT_FLG	Defensive Driving Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a defensive driver training discount is applicable.
Staging	PA_DRV	DFEN_DRV_TRNG_DSCNT_PCT	Defensive Driving Training Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when driver training discount applies.
Warehouse	PA_DRV	DFEN_DRV_TRNG_DSCNT_PCT	Defensive Driving Training Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when driver training discount applies.
Staging	PA_DRV	DIST_STUDENT_FLG	Distant Student Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not the student driver meets the company definition of distant driver.
Warehouse	PA_DRV	DIST_STUDENT_FLG	Distant Student Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not the student driver meets the company definition of distant driver.
Staging	PA_DRV	DRV_ACCID_CNT	Driver Accident Count	NUMBER (22,0)	This number represents the count of reported accidents charged against the driver's driving record.
Warehouse	PA_DRV	DRV_ACCID_CNT	Driver Accident Count	NUMBER (22, 0)	This number represents the count of reported accidents charged against the driver's driving record.
Staging	PA_DRV	DRV_CLASS_CD	Driver Class Code	VARCHAR2(25)	This system code identifies the class assigned to a personal vehicle driver.
Warehouse	PA_DRV	DRV_CLASS_CD	Driver Class Code	VARCHAR2(25)	This system code identifies the class assigned to a personal vehicle driver.
Warehouse	PA_DRV	DRV_CLASS_DESC	Driver Class Description	VARCHAR2(60)	This value describes the driver class.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PA_DRV	DRV_DWI_DUI_VIOLATION_CNT	Driver DWI / DUI Violation Count	NUMBER (22,0)	This number represents the count of Driving While intoxicated (DWI) and/or Driving Under the influence (DUI) violations charged against the driver's driving record.
Warehouse	PA_DRV	DRV_DWI_DUI_VIOLATION_CNT	Driver DWI / DUI Violation Count	NUMBER (22, 0)	This number represents the count of Driving While intoxicated (DWI) and/or Driving Under the influence (DUI) violations charged against the driver's driving record.
Staging	PA_DRV	DRV_INTRMDT_VIOLATION_CNT	Driver Intermediate Violation Count	NUMBER (22,0)	This number represents the count of intermediate violations charged against the driver's driving record.
Warehouse	PA_DRV	DRV_INTRMDT_VIOLATION_CNT	Driver Intermediate Violation Count	NUMBER (22, 0)	This number represents the count of intermediate violations charged against the driver's driving record.
Staging	PA_DRV	DRV_LIC_ISSUED_BY_CD	Driver License Issued By Code	VARCHAR2(25)	This system code indentifies which entity granted driving privileges to driver.
Warehouse	PA_DRV	DRV_LIC_ISSUED_BY_CD	Driver License Issued By Code	VARCHAR2(25)	This system code indentifies which entity granted driving privileges to driver.
Warehouse	PA_DRV	DRV_LIC_ISSUED_BY_DESC	Driver License Issued By Description	VARCHAR2(60)	This value describes the entity that issued a drivers license.
Staging	PA_DRV	DRV_LIC_STATUS_CD	Driver License Status Code	VARCHAR2(25)	This system code indicates the driver license status.
Warehouse	PA_DRV	DRV_LIC_STATUS_CD	Driver License Status Code	VARCHAR2(25)	This system code indicates the driver license status.
Warehouse	PA_DRV	DRV_LIC_STATUS_DESC	Driver License Status Description	VARCHAR2(60)	This value describes the status of a drivers license.
Staging	PA_DRV	DRV_MAJOR_VIOLATION_CNT	Driver Major Violation Count	NUMBER (22,0)	This number represents the count of major violations charged against the driver's driving record.
Warehouse	PA_DRV	DRV_MAJOR_VIOLATION_CNT	Driver Major Violation Count	NUMBER (22, 0)	This number represents the count of major violations charged against the driver's driving record.
Staging	PA_DRV	DRV_MINOR_VIOLATION_CNT	Driver Minor Violation Count	NUMBER (22,0)	This number represents the count of minor violations charged against the driver's driving record.
Warehouse	PA_DRV	DRV_MINOR_VIOLATION_CNT	Driver Minor Violation Count	NUMBER (22, 0)	This number represents the count of minor violations charged against the driver's driving record.
Staging	PA_DRV	DRV_NUM	Driver Number	NUMBER (22,0)	This number identifies the driver.
Warehouse	PA_DRV	DRV_NUM	Driver Number	NUMBER (22, 0)	This number identifies the driver.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PA_DRV	DRV_OCP	Driver Occupation	VARCHAR2(50)	This value represents the classification of employment tasks completed during personal vehicle driver's employment.
Warehouse	PA_DRV	DRV_OCP	Driver Occupation	VARCHAR2(50)	This value represents the classification of employment tasks completed during personal vehicle driver's employment.
Staging	PA_DRV	DRV_STATUS_CD	Driver Status Code	VARCHAR2(25)	This system code indicates the driver status.
Warehouse	PA_DRV	DRV_STATUS_CD	Driver Status Code	VARCHAR2(25)	This system code indicates the driver status.
Warehouse	PA_DRV	DRV_STATUS_DESC	Driver Status Description	VARCHAR2(60)	This value describes the status of a driver.
Staging	PA_DRV	DRV_TRNG_DSCNT_FLG	Driver Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not the driver is receiving a driver training discount.
Warehouse	PA_DRV	DRV_TRNG_DSCNT_FLG	Driver Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not the driver is receiving a driver training discount.
Staging	PA_DRV	DRV_TRNG_DSCNT_PCT	Driver Training Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when driver training discount applies.
Warehouse	PA_DRV	DRV_TRNG_DSCNT_PCT	Driver Training Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when driver training discount applies.
Staging	PA_DRV	DRV_TRNG_FLG	Driver Training Flag	CHAR(1)	This value represents based on the yes/no indicator that identifies whether or not a driver has completed a driver training course.
Warehouse	PA_DRV	DRV_TRNG_FLG	Driver Training Flag	CHAR(1)	This value represents based on the yes/no indicator that identifies whether or not a driver has completed a driver training course.
Staging	PA_DRV	DRV_TYP_CD	Driver Type Code	VARCHAR2(25)	This system code describes the driver activities.
Warehouse	PA_DRV	DRV_TYP_CD	Driver Type Code	VARCHAR2(25)	This system code describes the driver activities.
Warehouse	PA_DRV	DRV_TYP_DESC	Driver Type Description	VARCHAR2(60)	This value describes driver type.
Warehouse	PA_DRV	END_DT	End Date	DATE	This calendar date represents when the personal driver is no longer included in policy coverages.
Staging	PA_DRV	GOOD_STUDENT_CD	Good Student Code	VARCHAR2(25)	This system code identifies if the driver qualifies in the good student credit.
Warehouse	PA_DRV	GOOD_STUDENT_CD	Good Student Code	VARCHAR2(25)	This system code identifies if the driver qualifies in the good student credit.
Warehouse	PA_DRV	GOOD_STUDENT_DESC	Good Student Description	VARCHAR2(60)	This value describes the good student attributes.
Staging	PA_DRV	GOOD_STUDENT_DSCNT_FLG	Good Student Discount Flag	CHAR(1)	This value represents based on the yes/no indicator that identifies whether or not a driver has met the company's definition of a good student.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PA_DRV	GOOD_STUDENT_DSCNT_FLG	Good Student Discount Flag	CHAR(1)	This value represents based on the yes/no indicator that identifies whether or not a driver has met the company's definition of a good student.
Staging	PA_DRV	GOOD_STUDENT_DSCNT_PCT	Good Student Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when good student discount applies.
Warehouse	PA_DRV	GOOD_STUDENT_DSCNT_PCT	Good Student Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when good student discount applies.
Staging	PA_DRV	INSD_DT	Insured Date	DATE	This calendar date represents when insurance coverage began for personal driver.
Warehouse	PA_DRV	INSD_DT	Insured Date	DATE	This calendar date represents when insurance coverage began for personal driver.
Staging	PA_DRV	LIC_DT	License Date	DATE	This calendar date represents when personal vehicle driver was granted a drivers license.
Warehouse	PA_DRV	LIC_DT	License Date	DATE	This date represents the original date on which the driver's license was issued to this driver.
Staging	PA_DRV	NUM_YRS_AT_CUR_ADDR	Number Of Years At Current Address	NUMBER (22,0)	This number represents the count of years personal vehicle driver has resided at current address.
Warehouse	PA_DRV	NUM_YRS_AT_CUR_ADDR	Number Of Years At Current Address	NUMBER (22, 0)	This number represents the count of years personal vehicle driver has resided at current address.
Warehouse	PA_DRV	PA_DRV_ID	Personal Auto Driver Identifier	NUMBER (22, 0)	This system generated number identifies the personal vehicle driver instance.
Staging	PA_DRV	PA_DRV_UDF_CD_1	Personal Auto Driver User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first personal vehicle driver user defined field.
Warehouse	PA_DRV	PA_DRV_UDF_CD_1	Personal Auto Driver User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first personal vehicle driver user defined field.
Staging	PA_DRV	PA_DRV_UDF_CD_2	Personal Auto Driver User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second personal vehicle driver user defined field.
Warehouse	PA_DRV	PA_DRV_UDF_CD_2	Personal Auto Driver User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second personal vehicle driver user defined field.
Staging	PA_DRV	PA_DRV_UDF_CD_3	Personal Auto Driver User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third personal vehicle driver user defined field.
Warehouse	PA_DRV	PA_DRV_UDF_CD_3	Personal Auto Driver User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third personal vehicle driver user defined field.
Staging	PA_DRV	PA_DRV_UDF_CD_4	Personal Auto Driver User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth personal vehicle driver user defined field.
Warehouse	PA_DRV	PA_DRV_UDF_CD_4	Personal Auto Driver User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth personal vehicle driver user defined field.
Staging	PA_DRV	PA_DRV_UDF_CD_5	Personal Auto Driver User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth personal vehicle driver user defined field.
Warehouse	PA_DRV	PA_DRV_UDF_CD_5	Personal Auto Driver User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth personal vehicle driver user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PA_DRV	PA_DRV_UDF_DESC_1	Personal Auto Driver User Defined Field Description 1	VARCHAR2(60)	This value describes the first personal vehicle driver user defined field.
Warehouse	PA_DRV	PA_DRV_UDF_DESC_2	Personal Auto Driver User Defined Field Description 2	VARCHAR2(60)	This value describes the second personal vehicle driver user defined field.
Warehouse	PA_DRV	PA_DRV_UDF_DESC_3	Personal Auto Driver User Defined Field Description 3	VARCHAR2(60)	This value describes the third personal vehicle driver user defined field.
Warehouse	PA_DRV	PA_DRV_UDF_DESC_4	Personal Auto Driver User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth personal vehicle driver user defined field.
Warehouse	PA_DRV	PA_DRV_UDF_DESC_5	Personal Auto Driver User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth personal vehicle driver user defined field.
Warehouse	PA_DRV	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	PA_DRV	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person.
Staging	PA_DRV	RLAT_TO_APPLICANT_CD	Relationship to Applicant Code	VARCHAR2(25)	This system code identifies the relationship of this individual to the applicant.
Warehouse	PA_DRV	RLAT_TO_APPLICANT_CD	Relationship to Applicant Code	VARCHAR2(25)	This system code identifies the relationship of this individual to the applicant.
Warehouse	PA_DRV	RLAT_TO_APPLICANT_DESC	Relationship to Applicant Code Description	VARCHAR2(60)	This value describes the relationship to applicant code.
Staging	PA_DRV	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the personal vehicle driver with a specific transaction.
Staging	PA_DRV	YOUTHFUL_CD	Youthful Code	VARCHAR2(25)	This value represents based on the yes/no indicator identifying whether or not a driver meets the company criteria of a youthful driver.
Warehouse	PA_DRV	YOUTHFUL_CD	Youthful Code	VARCHAR2(25)	This value represents based on the yes/no indicator identifying whether or not a driver meets the company criteria of a youthful driver.
Warehouse	PA_DRV	YOUTHFUL_DESC	Youthful Description	VARCHAR2(60)	This value represents the description of youthful personal vehicle driver.
Datamart	PA_DRV_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage in the personal driver begins.
Datamart	PA_DRV_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the driver is currently applicable.
Datamart	PA_DRV_DIM	END_DT	End Date	DATE	This calendar date represents when the personal driver is no longer included in policy coverages.
Datamart	PA_DRV_DIM	PA_DFEN_DRV_TRNG_DSCNT_FLG	Defensive Driving Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a defensive driver training discount applies.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PA_DRV_DIM	PA_DFEN_DRV_TRNG_DSCNT_PCT	Defensive Driving Training Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when Defensive driver discount applies.
Datamart	PA_DRV_DIM	PA_DRV_ACCID_CNT	Personal Auto Driver Accident Count	NUMBER (22, 0)	This number represents the count of accidents charged against the driver's driving record.
Datamart	PA_DRV_DIM	PA_DRV_BIRTH_DT_ID	Personal Auto Driver Birth Date Identifier	DATE	This date identifies the personal vehicle driver's date of birth.
Datamart	PA_DRV_DIM	PA_DRV_CLASS	Personal Auto Driver Class	VARCHAR2(60)	This value represents the classification that describes the characteristics of a the driver It is typically only used for assigned risk, JUA, and in Texas.
Datamart	PA_DRV_DIM	PA_DRV_COMMUTER_DSCNT_FLG	Personal Auto Driver Commuter Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a commuter discount applies.
Datamart	PA_DRV_DIM	PA_DRV_COMMUTER_DSCNT_PCT	Personal Auto Driver Commuter Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when commuter discount applies.
Datamart	PA_DRV_DIM	PA_DRV_DFEN_DRV_CD	Personal Auto Defensive Driving Training Code	VARCHAR2(60)	This value describes of the defensive driving code.
Datamart	PA_DRV_DIM	PA_DRV_DIST_STUDENT_FLG	Personal Auto Driver Distant Student Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a Distant Student applies.
Datamart	PA_DRV_DIM	PA_DRV_DWI_DUI_VIOLATION_CNT	Personal Auto Driver DWI and DUI Violation Count	NUMBER (22, 0)	This number represents the count of Driving While Intoxicated (DWI) and/or Driving Under the Influence (DUI) violations charged against the driver's driving record.
Datamart	PA_DRV_DIM	PA_DRV_GENDER	Personal Auto Driver Gender	VARCHAR2(60)	This value represents the gender (male or female) of the driver.
Datamart	PA_DRV_DIM	PA_DRV_GOOD_STUDENT_CD	Personal Auto Driver Good Student Code	VARCHAR2(60)	This system code identifies the good student type.
Datamart	PA_DRV_DIM	PA_DRV_GOOD_STUDENT_DSCNT_FLG	Personal Auto Driver Good Student Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a good student discount applies.
Datamart	PA_DRV_DIM	PA_DRV_GOOD_STUDENT_DSCNT_PCT	Personal Auto Driver Good Student Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when good student discount applies.
Datamart	PA_DRV_DIM	PA_DRV_GOVT_ID_NUM	Personal Auto Driver Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the personal vehicle driver. For example, in the USA: SSN or FEIN.
Datamart	PA_DRV_DIM	PA_DRV_ID	Personal Auto Driver Identifier	NUMBER (22, 0)	This system generated number identifies the personal vehicle driver instance.
Datamart	PA_DRV_DIM	PA_DRV_INSD_DT_ID	Personal Auto Driver Insured Date Identifier	DATE	This calendar date represents when insurance coverage began for personal vehicle driver.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PA_DRV_DIM	PA_DRV_INTRMDT_VIOLATION_CNT	Personal Auto Driver Intermediate Violation Count	NUMBER (22, 0)	This number represents the count of intermediate violations charged against the driver's driving record.
Datamart	PA_DRV_DIM	PA_DRV_LIC_DT_ID	Personal Auto Driver Licensed Date Identifier	DATE	This calendar date represents when personal vehicle driver was granted a drivers license.
Datamart	PA_DRV_DIM	PA_DRV_LIC_ISSUED_BY	Personal Auto Driver License Issued By	VARCHAR2(60)	This value represents the governmental entity which granted drivers license.
Datamart	PA_DRV_DIM	PA_DRV_LIC_STATUS	Personal Auto Driver License Status	VARCHAR2(60)	This value represents the latitude location of the reinsurance company.
Datamart	PA_DRV_DIM	PA_DRV_MAJOR_VIOLATION_CNT	Personal Auto Driver Major Violation Count	NUMBER (22, 0)	This number represents the count of major violations charged against the driver's driving record.
Datamart	PA_DRV_DIM	PA_DRV_MARITAL_STATUS	Personal Auto Driver Marital Status	VARCHAR2(60)	This value represents the third limit of limit dimension table.
Datamart	PA_DRV_DIM	PA_DRV_MINOR_VIOLATION_CNT	Personal Auto Driver Minor Violation Count	NUMBER (22, 0)	This number represents the count of minor violations charged against the driver's driving record.
Datamart	PA_DRV_DIM	PA_DRV_NAT_KEY	Personal Auto Driver Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the personal vehicle driver.
Datamart	PA_DRV_DIM	PA_DRV_NM	Personal Auto Driver Name	VARCHAR2(170)	This value represents the full given name of personal vehicle driver.
Datamart	PA_DRV_DIM	PA_DRV_NUM	Personal Auto Driver Number	NUMBER (22, 0)	This number identifies personal vehicle driver.
Datamart	PA_DRV_DIM	PA_DRV_NUM_YRS_AT_CUR_ADDR	Personal Auto Driver Number of Years at Current Address	NUMBER (22, 0)	This number represents the count of the years the driver has resided at current address.
Datamart	PA_DRV_DIM	PA_DRV_OCP	Personal Auto Driver Occupation	VARCHAR2(50)	This value represents the classification of employment tasks completed during personal vehicle driver's employment.
Datamart	PA_DRV_DIM	PA_DRV_PARTY_UDF_1	Personal Auto Driver Party User Defined Field 1	VARCHAR2(60)	This value describes the first personal vehicle driver party user defined field.
Datamart	PA_DRV_DIM	PA_DRV_PARTY_UDF_2	Personal Auto Driver Party User Defined Field 2	VARCHAR2(60)	This value describes the second personal vehicle driver party user defined field.
Datamart	PA_DRV_DIM	PA_DRV_PARTY_UDF_3	Personal Auto Driver Party User Defined Field 3	VARCHAR2(60)	This value describes the third personal vehicle driver party user defined field.
Datamart	PA_DRV_DIM	PA_DRV_PARTY_UDF_4	Personal Auto Driver Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth personal vehicle driver party user defined field.
Datamart	PA_DRV_DIM	PA_DRV_PARTY_UDF_5	Personal Auto Driver Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth personal vehicle driver party user defined field.
Datamart	PA_DRV_DIM	PA_DRV_PERS_UDF_1	Personal Auto Driver Person Defined Field 1	VARCHAR2(60)	This value describes the first personal vehicle driver person user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PA_DRV_DIM	PA_DRV_PERS_UDF_2	Personal Auto Driver Person Defined Field 1	VARCHAR2(60)	This value describes the second personal vehicle driver person user defined field.
Datamart	PA_DRV_DIM	PA_DRV_PERS_UDF_3	Personal Auto Driver Person Defined Field 1	VARCHAR2(60)	This value describes the third personal vehicle driver person user defined field.
Datamart	PA_DRV_DIM	PA_DRV_PERS_UDF_4	Personal Auto Driver Person Defined Field 1	VARCHAR2(60)	This value describes the fourth personal vehicle driver person user defined field.
Datamart	PA_DRV_DIM	PA_DRV_PERS_UDF_5	Personal Auto Driver Person Defined Field 1	VARCHAR2(60)	This value describes the fifth personal vehicle driver person user defined field.
Datamart	PA_DRV_DIM	PA_DRV_PRES_EMPLMT_START_YR	Personal Auto Driver Present Employment Start Year	CHAR(4)	This value represents the calendar year that the personal vehicle driver began working for their current employer.
Datamart	PA_DRV_DIM	PA_DRV_RLAT_TO_APPLICANT	Personal Auto Driver Relationship to Applicant	VARCHAR2(60)	This value represents the relationship of this driver to the applicant.
Datamart	PA_DRV_DIM	PA_DRV_STATUS	Personal Auto Driver Status	VARCHAR2(60)	This value represents the classification of the driver's coverage to policy coverages.
Datamart	PA_DRV_DIM	PA_DRV_TRNG_DSCNT_FLG	Personal Auto Driver Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a driver training discount applies.
Datamart	PA_DRV_DIM	PA_DRV_TRNG_DSCNT_PCT	Personal Auto Driver Training Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when driving training discount applies.
Datamart	PA_DRV_DIM	PA_DRV_TRNG_FLG	Personal Auto Driver Training Flag	CHAR(1)	This value represents based on the yes/no indicator identifying presence or absence of driver training.
Datamart	PA_DRV_DIM	PA_DRV_TYP	Personal Auto Driver Type	VARCHAR2(60)	This value represents the indicator that describes the characteristics of a personal vehicle driver.
Datamart	PA_DRV_DIM	PA_DRV_UDF_1	Personal Auto Driver User Defined Field 1	VARCHAR2(60)	This value describes the first personal vehicle driver user defined field.
Datamart	PA_DRV_DIM	PA_DRV_UDF_2	Personal Auto Driver User Defined Field 2	VARCHAR2(60)	This value describes the second personal vehicle driver user defined field.
Datamart	PA_DRV_DIM	PA_DRV_UDF_3	Personal Auto Driver User Defined Field 3	VARCHAR2(60)	This value describes the third personal vehicle driver user defined field.
Datamart	PA_DRV_DIM	PA_DRV_UDF_4	Personal Auto Driver User Defined Field 4	VARCHAR2(60)	This value describes the fourth personal vehicle driver user defined field.
Datamart	PA_DRV_DIM	PA_DRV_UDF_5	Personal Auto Driver User Defined Field 5	VARCHAR2(60)	This value describes the fifth personal vehicle driver user defined field.
Datamart	PA_DRV_DIM	PA_DRV_YOUTHFUL_CD	Personal Auto Driver Youthful Code	VARCHAR2(60)	This system code is that identifies the youthful personal vehicle driver.
Datamart	PA_FACT	PA_DRV_ID	Personal Auto Driver Identifier	NUMBER (22, 0)	This system generated number identifies the personal vehicle driver instance.
Datamart	PA_FACT	PA_FACT_ID	Persona Auto Vehicle Fact Identifier	NUMBER (22, 0)	This number identifies the personal vehicle fact instance.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PA_FACT	PA_VEH_ID	Persona Auto Vehicle Identifier	NUMBER (22, 0)	This system generated number identifies the personal vehicle instance.
Staging	PA_VEH	ADDL_EQPT_AMT	Additional Equipment Amount	NUMBER (14,3)	This number represents the monetary cost of vehicle alterations or aftermarket custom equipment like custom painting, equipment installed to overcome a physical handicap, etc. installed on a personal vehicle.
Warehouse	PA_VEH	ADDL_EQPT_AMT	Additional Equipment Amount	NUMBER (14, 3)	This number represents the monetary cost of vehicle alterations or aftermarket custom equipment like custom painting, equipment installed to overcome a physical handicap, etc. installed on a personal vehicle.
Staging	PA_VEH	AIRBAG_TYP_CD	Airbag Type Code	VARCHAR2(25)	This system code identifies the attributes of the airbag system installed in the personal vehicle.
Warehouse	PA_VEH	AIRBAG_TYP_CD	Airbag Type Code	VARCHAR2(25)	This system code identifies the attributes of the airbag system installed in the personal vehicle.
Warehouse	PA_VEH	AIRBAG_TYP_DESC	Airbag Type Code Description	VARCHAR2(60)	This value describes the airbag type code.
Staging	PA_VEH	ANTI_LOCK_BRAKES_CD	Anti-lock Brake Code	VARCHAR2(25)	This system code identifies the attributes of anti-lock brakes on the personal vehicle.
Warehouse	PA_VEH	ANTI_LOCK_BRAKES_CD	Anti-lock Brake Code	VARCHAR2(25)	This system code identifies the attributes of anti-lock brakes on the personal vehicle.
Warehouse	PA_VEH	ANTI_LOCK_BRAKES_DESC	Anti-lock Brake Code Description	VARCHAR2(60)	This value describes the anti-lock brake code.
Staging	PA_VEH	ANTI_THEFT_DEVICE_CD	Anti-Theft Device Code	VARCHAR2(25)	This system code identifies the attributes of the anti-theft system installed on the personal vehicle.
Warehouse	PA_VEH	ANTI_THEFT_DEVICE_CD	Anti-Theft Device Code	VARCHAR2(25)	This system code identifies the attributes of the anti-theft system installed on the personal vehicle.
Warehouse	PA_VEH	ANTI_THEFT_DEVICE_DESC	Anti-Theft Device Code Description	VARCHAR2(60)	This value describes the anti-theft device code.
Staging	PA_VEH	AUTO_STBLTS_DSCNT_FLG	Automatic Seatbelt Type Code	CHAR(1)	This system code identifies whether an automatic seatbelt discount applies to the personal vehicle.
Warehouse	PA_VEH	AUTO_STBLTS_DSCNT_FLG	Automatic Seatbelt Type Code	CHAR(1)	This system code identifies whether an automatic seatbelt discount applies to the personal vehicle.
Staging	PA_VEH	AUTO_STBLTS_DSCNT_PCT	Automatic Seatbelt Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when automatic seatbelt discount applies.
Warehouse	PA_VEH	AUTO_STBLTS_DSCNT_PCT	Automatic Seatbelt Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when automatic seatbelt discount applies.
Warehouse	PA_VEH	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage in the personal driver begins.
Staging	PA_VEH	CELL_PHONE_TYP_CD	Cellular Phone Type Code	VARCHAR2(25)	This system code identifies the attributes of a cellular phone present in the vehicle.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PA_VEH	CELL_PHONE_TYP_CD	Cellular Phone Type Code	VARCHAR2(25)	This system code identifies the attributes of a cellular phone present in the vehicle.
Warehouse	PA_VEH	CELL_PHONE_TYP_DESC	Cellular Phone Type Description	VARCHAR2(60)	This value represents the description of the cellular phone type.
Warehouse	PA_VEH	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the personal vehicle is currently applicable.
Staging	PA_VEH	DAYTIME_RUN_LIGHTS_CD	Daytime Running Lights Code	VARCHAR2(25)	This value represents based on the yes/no indicator that states whether or not a vehicle has daytime running headlights.
Warehouse	PA_VEH	DAYTIME_RUN_LIGHTS_CD	Daytime Running Lights Code	VARCHAR2(25)	This value represents based on the yes/no indicator that states whether or not a vehicle has daytime running headlights.
Warehouse	PA_VEH	DAYTIME_RUN_LIGHTS_DESC	Daytime Running Lights Description	VARCHAR2(60)	This value describes the daytime running headlights of a personal vehicle.
Warehouse	PA_VEH	END_DT	End Date	DATE	This calendar date represents when the personal vehicle is no longer included in policy coverages.
Staging	PA_VEH	EST_ANNU_DRVG_DIST	Estimated Annual Driving Distance	NUMBER (22,0)	This number represents the estimated number of distance units (miles/kilometers) a vehicle is driven over a one year period.
Warehouse	PA_VEH	EST_ANNU_DRVG_DIST	Estimated Annual Driving Distance	NUMBER (22, 0)	This number represents the estimated number of distance units (miles/kilometers) a vehicle is driven over a one year period.
Staging	PA_VEH	GAR_CD	Garaging Code	VARCHAR2(25)	This system code identifies where the vehicle is parked at night.
Warehouse	PA_VEH	GAR_CD	Garaging Code	VARCHAR2(25)	This system code identifies where the vehicle is parked at night.
Warehouse	PA_VEH	GAR_DESC	Garaging Description	VARCHAR2(60)	This value describes where a vehicle is parked at night.
Warehouse	PA_VEH	GAR_LOC_ADDR_ID	Garaging Location Address Identifier	NUMBER (22, 0)	This system generated number identifies the garaging location address instance in the personal vehicle.
Staging	PA_VEH	HP_DSPLCMNT	Horsepower Displacement	VARCHAR2(5)	This value represents the cubic centimeters or displacement (for example, motorcycles) or horsepower for recreational vehicles.
Warehouse	PA_VEH	HP_DSPLCMNT	Horsepower Displacement	VARCHAR2(5)	This value represents the cubic centimeters or displacement (for example, motorcycles) or horsepower for recreational vehicles.
Staging	PA_VEH	INSD_DT	Insured Date	DATE	This calendar date represents when insurance coverage began for a personal vehicle.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PA_VEH	INSD_DT	Insured Date	DATE	This calendar date represents when insurance coverage began for a personal vehicle.
Staging	PA_VEH	LEASE_DT	Persona Auto Vehicle Lease Date	DATE	This calendar date represents when a personal vehicle was leased by insured.
Warehouse	PA_VEH	LEASE_DT	Persona Auto Vehicle Lease Date	DATE	This calendar date represents when a personal vehicle was leased by insured.
Staging	PA_VEH	MSRP	Manufacturer Suggested Retail Price	NUMBER (14,3)	This number represents the price that the manufacturer tells the vehicle dealer the new vehicle is worth.
Warehouse	PA_VEH	MSRP	Manufacturer Suggested Retail Price	NUMBER (14, 3)	This number represents the price that the manufacturer tells the vehicle dealer the new vehicle is worth.
Staging	PA_VEH	MULT_CAR_DSCNT_FLG	Multiple Car Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a multiple car discount applies.
Warehouse	PA_VEH	MULT_CAR_DSCNT_FLG	Multiple Car Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a multiple car discount applies.
Staging	PA_VEH	MULT_CAR_DSCNT_PCT	Multiple Car Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when a multiple car discount applies.
Warehouse	PA_VEH	MULT_CAR_DSCNT_PCT	Multiple Car Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when a multiple car discount applies.
Staging	PA_VEH	NEW_OR_USED_CD	New Or Used Code	VARCHAR2(25)	This system code identifies if the insured is the original owner of the insured vehicle.
Warehouse	PA_VEH	NEW_OR_USED_CD	New Or Used Code	VARCHAR2(25)	This system code identifies if the insured is the original owner of the insured vehicle.
Warehouse	PA_VEH	NEW_OR_USED_DESC	New or Used Description	VARCHAR2(60)	This value describes new or used code.
Staging	PA_VEH	NUM_DAYS_DRVN_PER_WK	Number Of Days Driven Per Week	NUMBER (22,0)	This number represents the count of days the personal vehicle is driven each calendar week.
Warehouse	PA_VEH	NUM_DAYS_DRVN_PER_WK	Number Of Days Driven Per Week	NUMBER (22, 0)	This number represents the count of days the personal vehicle is driven each calendar week.
Staging	PA_VEH	ONE_WAY_DIST_TO_WRK	One Way Distance To Work	NUMBER (22,0)	This number represents the number of distance units (miles/kilometers) to place of employment.
Warehouse	PA_VEH	ONE_WAY_DIST_TO_WRK	One Way Distance To Work	NUMBER (22, 0)	This number represents the number of distance units (miles/kilometers) to place of employment.
Staging	PA_VEH	OWNRSHP_TYP_CD	Ownership Type Code	VARCHAR2(25)	This system code describes the ownership type of a vehicle Standard code.
Warehouse	PA_VEH	OWNRSHP_TYP_CD	Ownership Type Code	VARCHAR2(25)	This system code describes the ownership type of a vehicle standard code.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PA_VEH	OWNRSHP_TYP_DESC	Ownership Type Description	VARCHAR2(60)	This value represents the classification that describes how a personal vehicle is owned and titled.
Warehouse	PA_VEH	PA_VEH_ID	Persona Auto Vehicle Identifier	NUMBER (22, 0)	This system generated number identifies the personal vehicle instance.
Staging	PA_VEH	PA_VEH_NAT_KEY	Persona Auto Vehicle Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the personal vehicle.
Warehouse	PA_VEH	PA_VEH_NAT_KEY	Persona Auto Vehicle Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the personal vehicle.
Staging	PA_VEH	PA_VEH_UDF_CD_1	Persona Auto Vehicle User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first personal vehicle user defined field.
Warehouse	PA_VEH	PA_VEH_UDF_CD_1	Persona Auto Vehicle User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first personal vehicle user defined field.
Staging	PA_VEH	PA_VEH_UDF_CD_2	Persona Auto Vehicle User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second personal vehicle user defined field.
Warehouse	PA_VEH	PA_VEH_UDF_CD_2	Persona Auto Vehicle User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second personal vehicle user defined field.
Staging	PA_VEH	PA_VEH_UDF_CD_3	Persona Auto Vehicle User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third personal vehicle user defined field.
Warehouse	PA_VEH	PA_VEH_UDF_CD_3	Persona Auto Vehicle User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third personal vehicle user defined field.
Staging	PA_VEH	PA_VEH_UDF_CD_4	Persona Auto Vehicle User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth personal vehicle user defined field.
Warehouse	PA_VEH	PA_VEH_UDF_CD_4	Persona Auto Vehicle User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth personal vehicle user defined field.
Staging	PA_VEH	PA_VEH_UDF_CD_5	Persona Auto Vehicle User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth personal vehicle user defined field.
Warehouse	PA_VEH	PA_VEH_UDF_CD_5	Persona Auto Vehicle User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth personal vehicle user defined field.
Warehouse	PA_VEH	PA_VEH_UDF_DESC_1	Persona Auto Vehicle User Defined Field Description 1	VARCHAR2(60)	This value describes the first personal vehicle user defined field.
Warehouse	PA_VEH	PA_VEH_UDF_DESC_2	Persona Auto Vehicle User Defined Field Description 2	VARCHAR2(60)	This value describes the second personal vehicle user defined field.
Warehouse	PA_VEH	PA_VEH_UDF_DESC_3	Persona Auto Vehicle User Defined Field Description 3	VARCHAR2(60)	This value describes the third personal vehicle user defined field.
Warehouse	PA_VEH	PA_VEH_UDF_DESC_4	Persona Auto Vehicle User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth personal vehicle user defined field.
Warehouse	PA_VEH	PA_VEH_UDF_DESC_5	Persona Auto Vehicle User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth personal vehicle user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PA_VEH	PURCH_DT	Purchase Date	DATE	This calendar date represents when the insured purchased the personal vehicle.
Warehouse	PA_VEH	PURCH_DT	Purchase Date	DATE	This calendar date represents when the insured purchased the personal vehicle.
Staging	PA_VEH	PURCH_PRICE	Purchase Price	NUMBER (14,3)	This number represents the monetary amount paid when personal vehicle was purchased.
Warehouse	PA_VEH	PURCH_PRICE	Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when personal vehicle was purchased.
Staging	PA_VEH	RATING_AGE_CD	Rating Age Code	VARCHAR2(25)	This system code represents the rating age used to rate the vehicle, regardless of its actual age.
Warehouse	PA_VEH	RATING_AGE_CD	Rating Age Code	VARCHAR2(25)	This system code represents the rating age used to rate the vehicle, regardless of its actual age.
Warehouse	PA_VEH	RATING_AGE_DESC	Rating Age Description	VARCHAR2(60)	This value describes rating age.
Staging	PA_VEH	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the personal vehicle with a specific transaction.
Staging	PA_VEH	STATED_AMT	Stated Amount	NUMBER (14,3)	This number represents the monetary cost used to rate and value a vehicle when a symbol is not available or useful.
Warehouse	PA_VEH	STATED_AMT	Stated Amount	NUMBER (14, 3)	This number represents the amount used to rate and value a vehicle when a symbol is not available or useful.
Staging	PA_VEH	VEH_BODY_TYP_CD	Vehicle Body Type Code	VARCHAR2(25)	This system code describes the attributes of vehicle body for a scheduled personal vehicle.
Warehouse	PA_VEH	VEH_BODY_TYP_CD	Vehicle Body Type Code	VARCHAR2(25)	This system code describes the attributes of vehicle body for a scheduled personal vehicle.
Warehouse	PA_VEH	VEH_BODY_TYP_DESC	Vehicle Body Type Description	VARCHAR2(60)	This value represents the description of the vehicle body type.
Staging	PA_VEH	VEH_CLASS_CD	Vehicle Class Code	VARCHAR2(25)	This value represents the classification that describes vehicle size and body type.
Warehouse	PA_VEH	VEH_CLASS_CD	Vehicle Class Code	VARCHAR2(25)	This value represents the classification that describes vehicle size and body type.
Warehouse	PA_VEH	VEH_CLASS_DESC	Vehicle Class Description	VARCHAR2(60)	This value describes the vehicle class.
Staging	PA_VEH	VEH_COST_NEW	Vehicle Cost New	NUMBER (14,3)	This number represents the monetary price of vehicle when purchased as a new vehicle.
Warehouse	PA_VEH	VEH_COST_NEW	Vehicle Cost New	NUMBER (14, 3)	This number represents the monetary price of vehicle when purchased as a new vehicle.
Staging	PA_VEH	VEH_CUR_VAL	Vehicle Current Value	NUMBER (14,3)	This number represents the current monetary value of the personal vehicle in marketplace.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PA_VEH	VEH_CUR_VAL	Vehicle Current Value	NUMBER (14, 3)	This number represents the current monetary value of the personal vehicle in marketplace.
Staging	PA_VEH	VEH_GROSS_WT	Vehicle Gross Weight	NUMBER (14,3)	This number represents the total weight a vehicle is designed to carry and includes the net weight of the vehicle, plus the weight of passengers, fuel, cargo and any additional accessories.
Warehouse	PA_VEH	VEH_GROSS_WT	Vehicle Gross Weight	NUMBER (14, 3)	This number represents the total weight a vehicle is designed to carry and includes the net weight of the vehicle, plus the weight of passengers, fuel, cargo and any additional accessories.
Staging	PA_VEH	VEH_MFR	Vehicle Manufacturer	VARCHAR2(20)	This value represents the name of manufacturer that created the personal vehicle.
Warehouse	PA_VEH	VEH_MFR	Vehicle Manufacturer	VARCHAR2(20)	This value represents the name of manufacturer that created the personal vehicle.
Staging	PA_VEH	VEH_MODEL	Vehicle Model	VARCHAR2(20)	This value represents the model name assigned by manufacturer of personal vehicle.
Warehouse	PA_VEH	VEH_MODEL	Vehicle Model	VARCHAR2(20)	This value represents the model name assigned by manufacturer of personal vehicle.
Staging	PA_VEH	VEH_NUM	Vehicle Number	NUMBER (22,0)	This number is the system assigned number that identifies personal vehicle.
Warehouse	PA_VEH	VEH_NUM	Vehicle Number	NUMBER (22, 0)	This number is the system assigned number that identifies personal vehicle.
Staging	PA_VEH	VEH_PERF_CD	Vehicle Performance Code	VARCHAR2(25)	This system code identifies the performance level of the vehicle.
Warehouse	PA_VEH	VEH_PERF_CD	Vehicle Performance Code	VARCHAR2(25)	This system code identifies the performance level of the vehicle.
Warehouse	PA_VEH	VEH_PERF_DESC	Vehicle Performance Description	VARCHAR2(60)	This value describes the performance level of the vehicle.
Staging	PA_VEH	VEH_SYM_CD	Vehicle Symbol Code	VARCHAR2(25)	This system code is a cost symbol that represents a value in the personal vehicle.
Warehouse	PA_VEH	VEH_SYM_CD	Vehicle Symbol Code	VARCHAR2(25)	This system code is a cost symbol that represents a value in the personal vehicle.
Warehouse	PA_VEH	VEH_SYM_DESC	Vehicle Symbol Description	VARCHAR2(60)	This value describes the personal vehicle symbol.
Staging	PA_VEH	VEH_USE_CD	Vehicle Use Code	VARCHAR2(25)	This system code identifies the primary use of the vehicle.
Warehouse	PA_VEH	VEH_USE_CD	Vehicle Use Code	VARCHAR2(25)	This system code identifies the primary use of the vehicle.
Warehouse	PA_VEH	VEH_USE_DESC	Vehicle Use Description	VARCHAR2(60)	This value describes the primary use of the vehicle.
Staging	PA_VEH	VEH_YR	Vehicle Year	CHAR(4)	This value represents the model year assigned by vehicle manufacturer.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PA_VEH	VEH_YR	Vehicle Year	CHAR(4)	This value represents the model year assigned by vehicle manufacturer.
Staging	PA_VEH	VIN	Vehicle Identification Number	VARCHAR2(25)	This value represents the vehicle identification number assigned by the manufacturer of the personal vehicle at risk.
Warehouse	PA_VEH	VIN	Vehicle Identification Number	VARCHAR2(25)	This value represents the vehicle identification number assigned by the manufacturer of the personal vehicle at risk.
Datamart	PA_VEH_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage in the personal driver begins.
Datamart	PA_VEH_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the vehicle is currently applicable.
Datamart	PA_VEH_DIM	END_DT	End Date	DATE	This calendar date represents when the personal vehicle is no longer included in policy coverages.
Datamart	PA_VEH_DIM	PA_VEH_ADDL_EQPT_AMT	Persona Auto Vehicle Additional Equipment Amount	NUMBER (14, 3)	This number represents the monetary cost of personal vehicle alterations or aftermarket custom equipment like custom painting, equipment installed to overcome a physical handicap, etc.
Datamart	PA_VEH_DIM	PA_VEH_AIRBAG_TYP	Persona Auto Vehicle Airbag Type	VARCHAR2(60)	This value represents the classification of the airbag system installed in personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_ANTI_LOCK_BRAKES_CD	Persona Auto Vehicle Anti-Lock Brakes Code	VARCHAR2(60)	This system code describes the type of anti-lock brakes system present on a personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_ANTI_THEFT_DEVICE_CD	Persona Auto Vehicle Anti-Theft Device Code	VARCHAR2(60)	This system code describes the type of anti-theft system present on a personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_AUTO_STBLTS_DSCNT_FLG	Persona Auto Vehicle Automatic Seatbelts Flag	CHAR(1)	This value represents based on the yes/no indicator identifying presence or absence of automatic seatbelts.
Datamart	PA_VEH_DIM	PA_VEH_AUTO_STBLTS_DSCNT_PCT	Persona Auto Vehicle Automatic Seatbelts Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when automatic seatbelts discount applies.
Datamart	PA_VEH_DIM	PA_VEH_BODY_TYP	Persona Auto Vehicle Body Type	VARCHAR2(60)	This value represents the classification of the characteristics of a personal vehicle body.
Datamart	PA_VEH_DIM	PA_VEH_CELL_PHONE_TYP	Persona Auto Vehicle Cellular Phone Type	VARCHAR2(60)	This system code identifies the cellular phone type present in vehicle.
Datamart	PA_VEH_DIM	PA_VEH_CLASS	Persona Auto Vehicle Class	VARCHAR2(60)	This value represents the classification that describes vehicle size and body type.
Datamart	PA_VEH_DIM	PA_VEH_COST_NEW	Persona Auto Vehicle Cost New	NUMBER (14, 3)	This number represents the monetary amount of vehicle when Purchased as a New vehicle.
Datamart	PA_VEH_DIM	PA_VEH_CUR_VAL	Persona Auto Vehicle Current Value	NUMBER (14, 3)	This number represents the current monetary value of personal vehicle in marketplace.
Datamart	PA_VEH_DIM	PA_VEH_DAYTIME_RUN_LIGHTS_CD	Persona Auto Vehicle Daytime Running Lights Code	VARCHAR2(60)	This system code describes the type of daytime running headlights present on a personal vehicle.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PA_VEH_DIM	PA_VEH_EST_ANNU_DRVG_DIST	Persona Auto Vehicle Estimated Annual Driving Distance	NUMBER (22, 0)	This number identifies the count of the annual estimated driving distance units.
Datamart	PA_VEH_DIM	PA_VEH_GAR_CD	Persona Auto Vehicle Garaging Code	VARCHAR2(60)	This system code describes where a vehicle is parked at night.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_CNTY	Persona Auto Vehicle Garaging Location County	VARCHAR2(60)	This value identifies the county where a vehicle is parked at night.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_CTRY	Persona Auto Vehicle Garaging Location Country	VARCHAR2(60)	This value identifies the country where a vehicle is parked at night.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_CTY	Persona Auto Vehicle Garaging Location City	VARCHAR2(32)	This value identifies the city where a vehicle is parked at night.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_DSTRCT	Persona Auto Vehicle Garaging Location District	VARCHAR2(60)	This value represents the full name of the distribution channel.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_LATITUDE	Persona Auto Vehicle Garaging Location Latitude	VARCHAR2(11)	This value represents the present marital condition (single, married, divorced, widowed) of the claim examiner.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_LONGITUDE	Persona Auto Vehicle Garaging Location Longitude	VARCHAR2(11)	This value represents the longitude location where a vehicle is parked at night.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_PSTL_CD	Persona Auto Vehicle Garaging Location Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_PSTL_CD_PRFX	Persona Auto Vehicle Garaging Location Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_PSTL_SUB_CD	Persona Auto Vehicle Garaging Location Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_REGION	Persona Auto Vehicle Garaging Location Region	VARCHAR2(60)	This value represents the geographic region where a vehicle is parked at night.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_STATE	Persona Auto Vehicle Garaging Location State	VARCHAR2(60)	This value identifies the state where a vehicle is parked at night.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_TAX_LOC_ID	Persona Auto Vehicle Garaging Location Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier of where a vehicle is parked at night.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_TERR	Persona Auto Vehicle Garaging Location Territory	VARCHAR2(60)	This value represents the territory where a vehicle is parked at night.
Datamart	PA_VEH_DIM	PA_VEH_GEOG_BNDRY_UDF_1	Persona Auto Vehicle Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first personal vehicle geographic boundary user defined field.
Datamart	PA_VEH_DIM	PA_VEH_GEOG_BNDRY_UDF_2	Persona Auto Vehicle Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second personal vehicle geographic boundary user defined field.
Datamart	PA_VEH_DIM	PA_VEH_GEOG_BNDRY_UDF_3	Persona Auto Vehicle Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third personal vehicle geographic boundary user defined field.
Datamart	PA_VEH_DIM	PA_VEH_GEOG_BNDRY_UDF_4	Persona Auto Vehicle Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth personal vehicle geographic boundary user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PA_VEH_DIM	PA_VEH_GEOG_BNDRY_UDF_5	Persona Auto Vehicle Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth personal vehicle geographic boundary user defined field.
Datamart	PA_VEH_DIM	PA_VEH_GROSS_WT	Persona Auto Vehicle Gross Weight	NUMBER (14, 3)	This number represents the total weight a vehicle is designed to carry and includes the net weight of the vehicle, plus the weight of passengers, fuel, cargo and any additional accessories.
Datamart	PA_VEH_DIM	PA_VEH_HP_DSPLCMNT	Persona Auto Vehicle Horsepower Displacement	VARCHAR2(5)	This value represents the district of the dwelling's location.
Datamart	PA_VEH_DIM	PA_VEH_ID	Persona Auto Vehicle Identifier	NUMBER (22, 0)	This system generated number identifies the personal vehicle instance.
Datamart	PA_VEH_DIM	PA_VEH_INSD_DT_ID	Persona Auto Vehicle Insured Date Identifier	DATE	This calendar date represents when insurance coverage began for a personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_LEASE_DT_ID	Persona Auto Vehicle Lease Date Identifier	DATE	This calendar date represents when a personal vehicle was leased by insured.
Datamart	PA_VEH_DIM	PA_VEH_MFR	Persona Auto Vehicle Manufacturer	VARCHAR2(20)	This value represents the name of manufacturer that created the personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_MODEL	Persona Auto Vehicle Model	VARCHAR2(20)	This value represents the model name assigned by manufacturer of personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_MSRP	Persona Auto Vehicle Manufacturer's Suggested Retail Price	NUMBER (14, 3)	This number represents the price that the manufacturer tells the vehicle dealer the new vehicle is worth.
Datamart	PA_VEH_DIM	PA_VEH_MULT_CAR_DSCNT_FLG	Persona Auto Vehicle Multiple Car Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not multiple car discount applies.
Datamart	PA_VEH_DIM	PA_VEH_MULT_CAR_DSCNT_PCT	Persona Auto Vehicle Multiple Car Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when multiple car discount applies.
Datamart	PA_VEH_DIM	PA_VEH_NAT_KEY	Persona Auto Vehicle Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_NEW_OR_USED_CD	Persona Auto Vehicle New or Used Code	VARCHAR2(60)	This system code identifies if the insured is the original owner of the insured personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_NUM	Persona Auto Vehicle Number	NUMBER (22, 0)	This number identifies personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_NUM_DAYS_DRVN_PER_WK	Persona Auto Vehicle Number of Days Driven Per Week	NUMBER (22, 0)	This number represents the count of days vehicle is driven per calendar week.
Datamart	PA_VEH_DIM	PA_VEH_ONE_WAY_DIST_TO_WRK	Persona Auto Vehicle One Way Distance To Work	NUMBER (22, 0)	This number represents the number of distance units (miles/kilometers) to place of employment from residence.
Datamart	PA_VEH_DIM	PA_VEH_OWNRSHP_TYP	Persona Auto Vehicle Ownership Type	VARCHAR2(60)	This value represents the classification that describes how a personal vehicle is owned and titled.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PA_VEH_DIM	PA_VEH_PERF_CD	Persona Auto Vehicle Performance Code	VARCHAR2(60)	This system code identifies the performance level of the personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_PURCH_DT_ID	Persona Auto Vehicle Purchase Date Identifier	DATE	This calendar date represents when personal vehicle purchase date instance.
Datamart	PA_VEH_DIM	PA_VEH_PURCH_PRICE	Persona Auto Vehicle Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when personal vehicle was purchased.
Datamart	PA_VEH_DIM	PA_VEH_RATING_AGE	Persona Auto Vehicle Rating Age	VARCHAR2(60)	This value represents the age used to rate the personal vehicle, regardless of its actual age.
Datamart	PA_VEH_DIM	PA_VEH_STATED_AMT	Persona Auto Vehicle Stated Amount	NUMBER (14, 3)	This number represents the amount used to rate and value a personal vehicle when a symbol is not available or useful.
Datamart	PA_VEH_DIM	PA_VEH_SYM	Persona Auto Vehicle Symbol	VARCHAR2(60)	This value represents the cost symbol that represents a value in the personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_UDF_1	Persona Auto Vehicle User Defined Field 1	VARCHAR2(60)	This value describes the first personal vehicle user defined field.
Datamart	PA_VEH_DIM	PA_VEH_UDF_2	Persona Auto Vehicle User Defined Field 2	VARCHAR2(60)	This value describes the second personal vehicle user defined field.
Datamart	PA_VEH_DIM	PA_VEH_UDF_3	Persona Auto Vehicle User Defined Field 3	VARCHAR2(60)	This value describes the third personal vehicle user defined field.
Datamart	PA_VEH_DIM	PA_VEH_UDF_4	Persona Auto Vehicle User Defined Field 4	VARCHAR2(60)	This value describes the fourth personal vehicle user defined field.
Datamart	PA_VEH_DIM	PA_VEH_UDF_5	Persona Auto Vehicle User Defined Field 5	VARCHAR2(60)	This value describes the fifth personal vehicle user defined field.
Datamart	PA_VEH_DIM	PA_VEH_USE_CD	Persona Auto Vehicle Use Code	VARCHAR2(60)	This system code identifies the primary use of the personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_YR	Persona Auto Vehicle Year	CHAR(4)	This value represents the model year assigned by vehicle manufacturer.
Datamart	PA_VEH_DIM	PA_VIN	Persona Auto Vehicle Identification Number	VARCHAR2(25)	This value represents the unique identification number assigned by the vehicle's manufacturer.
Staging	PARTY	GOVT_ID_NUM	Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the party. For example, in the USA: SSN or FEIN.
Warehouse	PARTY	GOVT_ID_NUM	Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the party. For example, in the USA: SSN or FEIN.
Warehouse	PARTY	PARTY_ID	Party Identifier	NUMBER (22, 0)	This system generated number identifies the party.
Staging	PARTY	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	PARTY	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PARTY	PARTY_RLAT_CD	Party Relationship Code	VARCHAR2(25)	This system code identifies the party relationship.
Staging	PARTY	PARTY_UDF_CD_1	Party User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first party user defined field.
Warehouse	PARTY	PARTY_UDF_CD_1	Party User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first party user defined field.
Staging	PARTY	PARTY_UDF_CD_2	Party User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second party user defined field.
Warehouse	PARTY	PARTY_UDF_CD_2	Party User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second party user defined field.
Staging	PARTY	PARTY_UDF_CD_3	Party User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third party user defined field.
Warehouse	PARTY	PARTY_UDF_CD_3	Party User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third party user defined field.
Staging	PARTY	PARTY_UDF_CD_4	Party User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth party user defined field.
Warehouse	PARTY	PARTY_UDF_CD_4	Party User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth party user defined field.
Staging	PARTY	PARTY_UDF_CD_5	Party User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth party user defined field.
Warehouse	PARTY	PARTY_UDF_CD_5	Party User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth party user defined field.
Warehouse	PARTY	PARTY_UDF_DESC_1	Party User Defined Field Description 1	VARCHAR2(60)	This value describes the first party user defined field.
Warehouse	PARTY	PARTY_UDF_DESC_2	Party User Defined Field Description 2	VARCHAR2(60)	This value describes the second party user defined field.
Warehouse	PARTY	PARTY_UDF_DESC_3	Party User Defined Field Description 3	VARCHAR2(60)	This value describes the third party user defined field.
Warehouse	PARTY	PARTY_UDF_DESC_4	Party User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth party user defined field.
Warehouse	PARTY	PARTY_UDF_DESC_5	Party User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth party user defined field.
Staging	PARTY	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the party with a specific transaction.
Warehouse	PARTY_ROLE	PARTY_ROLE_CD	Party Role Code	VARCHAR2(25)	This system code identifies the party role.
Warehouse	PARTY_ROLE	PARTY_ROLE_DESC	Party Role Description	VARCHAR2(60)	This value describes party role.
Warehouse	PARTY_ROLE	PARTY_ROLE_ID	Party Role Identifier	NUMBER (22, 0)	This system generated number identifies the party role instance.
Warehouse	PARTY_TO_CNTCT	BEGIN_DT	Begin Date	DATE	This calendar date represents when the party to contact applies.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PARTY_TO_CNTCT	CNTCT_ID	Contact Identifier	NUMBER (22, 0)	This system generated number identifies the contact instance.
Warehouse	PARTY_TO_CNTCT	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the party to contact is currently applicable.
Warehouse	PARTY_TO_CNTCT	END_DT	End Date	DATE	This calendar date represents when the party to contact is no longer valid.
Warehouse	PARTY_TO_CNTCT	PARTY_ID	Party Identifier	NUMBER (22, 0)	This system generated number identifies the party instance.
Warehouse	PARTY_TO_CNTCT	PARTY_TO_CNTCT_ID	Party To Contract Identifier	NUMBER (22, 0)	This system generated number identifies the party to contact instance.
Warehouse	PARTY_TO_CNTCT	PARTY_TO_CNTCT_NAT_KEY	Party To Contact Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party to contact.
Warehouse	PARTY_TO_PARTY	BEGIN_DT	Begin Date	DATE	This calendar date represents when the party to party applies.
Warehouse	PARTY_TO_PARTY	CHILD_PARTY_ID	Child Party Identifier	NUMBER (22, 0)	This system generated number identifies the child party instance.
Warehouse	PARTY_TO_PARTY	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the party to party is currently applicable.
Warehouse	PARTY_TO_PARTY	END_DT	End Date	DATE	This calendar date represents when the party to party longer applies.
Warehouse	PARTY_TO_PARTY	PARENT_PARTY_ID	Parent Party Identifier	NUMBER (22, 0)	This system generated number identifies the parent party instance.
Warehouse	PARTY_TO_PARTY	PARTY_TO_PARTY_ID	Party To Party Identifier	NUMBER (22, 0)	This system generated number identifies the party to party instance.
Warehouse	PARTY_TO_PARTY	PARTY_TO_PARTY_NAT_KEY	Party To Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party to party.
Warehouse	PARTY_TO_PARTY	PARTY_TO_PARTY_TYP_CD	Party To Party Type Code	VARCHAR2(25)	This system code identifies the party to party type.
Warehouse	PARTY_TO_PARTY	PARTY_TO_PARTY_TYP_DESC	Party To Party Type Description	VARCHAR2(60)	This value describes the party to party type.
Warehouse	PARTY_TO_PARTY_ROLE	BEGIN_DT	Begin Date	DATE	This calendar date represents when the party to party role applies.
Warehouse	PARTY_TO_PARTY_ROLE	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the party to party role is currently applicable.
Warehouse	PARTY_TO_PARTY_ROLE	END_DT	End Date	DATE	This calendar date represents when the party to party role is no longer valid.
Warehouse	PARTY_TO_PARTY_ROLE	PARTY_ID	Party Identifier	NUMBER (22, 0)	This system generated number identifies the party instance.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PARTY_TO_PARTY_ROLE	PARTY_ROLE_ID	Party Role Identifier	NUMBER (22, 0)	This system generated number identifies the party role.
Warehouse	PARTY_TO_PARTY_ROLE	PARTY_TO_PARTY_ROLE_ID	Party To Party Role Identifier	NUMBER (22, 0)	This system generated number identifies the party to party role instance.
Warehouse	PARTY_TO_PARTY_ROLE	PARTY_TO_PARTY_ROLE_NAT_KEY	Party To Party Role Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party to party role.
Warehouse	PERS	BEGIN_DT	Begin Date	DATE	This calendar date represents when the insurance policy coverage applies to the person.
Staging	PERS	BIRTH_DT	Birth Date	DATE	This date represents the calendar date of birth of the person listed on an insurance policy.
Warehouse	PERS	BIRTH_DT	Birth Date	DATE	This date represents the calendar date of birth of the person listed on an insurance policy.
Warehouse	PERS	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the person is currently applicable.
Warehouse	PERS	END_DT	End Date	DATE	This calendar date represents when the insurance policy coverage ends in the person.
Staging	PERS	FIRST_NM	First Name	VARCHAR2(50)	This value represents the first name of the person.
Warehouse	PERS	FIRST_NM	First Name	VARCHAR2(50)	This value represents the first name of the person.
Staging	PERS	GENDER_CD	Gender Code	VARCHAR2(25)	This system code abbreviates the gender (male or female).
Warehouse	PERS	GENDER_CD	Gender Code	VARCHAR2(25)	This system code abbreviates the gender (male or female).
Warehouse	PERS	GENDER_DESC	Gender Description	VARCHAR2(60)	This value represents the full description of the gender (male or female).
Staging	PERS	LAST_NM	Last Name	VARCHAR2(50)	This value represents the last name of the person.
Warehouse	PERS	LAST_NM	Last Name	VARCHAR2(50)	This value represents the last name of person.
Staging	PERS	MARITAL_STATUS_CD	Marital Status Code	VARCHAR2(25)	This system code identifies the present marital condition (single, married, divorced, widowed) of the person.
Warehouse	PERS	MARITAL_STATUS_CD	Marital Status Code	VARCHAR2(25)	This system code identifies the present marital condition (single, married, divorced, widowed) of the person.
Warehouse	PERS	MARITAL_STATUS_DESC	Marital Status Description	VARCHAR2(60)	This value describes the present marital condition (single, married, divorced, widowed) of the claimant.
Staging	PERS	MIDDLE_NM	Middle Name	VARCHAR2(50)	This value represents the middle name of the person.
Warehouse	PERS	MIDDLE_NM	Middle Name	VARCHAR2(50)	This value represents the middle name of the person.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PERS	PARTY_ID	Party Identifier	NUMBER (22, 0)	This system generated number identifies the party instance.
Warehouse	PERS	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	PERS	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person instance.
Staging	PERS	PERS_RLAT_CD	Person Relationship Code	VARCHAR2(25)	This system code identifies the person relationship.
Staging	PERS	PERS_UDF_CD_1	Person User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first person user defined field.
Warehouse	PERS	PERS_UDF_CD_1	Person User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first person user defined field.
Staging	PERS	PERS_UDF_CD_2	Person User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second person user defined field.
Warehouse	PERS	PERS_UDF_CD_2	Person User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second person user defined field.
Staging	PERS	PERS_UDF_CD_3	Person User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third person user defined field.
Warehouse	PERS	PERS_UDF_CD_3	Person User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third person user defined field.
Staging	PERS	PERS_UDF_CD_4	Person User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth person user defined field.
Warehouse	PERS	PERS_UDF_CD_4	Person User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth person user defined field.
Staging	PERS	PERS_UDF_CD_5	Person User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth person user defined field.
Warehouse	PERS	PERS_UDF_CD_5	Person User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth person user defined field.
Warehouse	PERS	PERS_UDF_DESC_1	Person User Defined Field Description 1	VARCHAR2(60)	This value describes the first person user defined field.
Warehouse	PERS	PERS_UDF_DESC_2	Person User Defined Field Description 2	VARCHAR2(60)	This value describes the second person user defined field.
Warehouse	PERS	PERS_UDF_DESC_3	Person User Defined Field Description 3	VARCHAR2(60)	This value describes the third person user defined field.
Warehouse	PERS	PERS_UDF_DESC_4	Person User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth person user defined field.
Warehouse	PERS	PERS_UDF_DESC_5	Person User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth person user defined field.
Staging	PERS	PRES_EMPLMT_START_YR	Present Employment Start Year	CHAR(4)	This value represents the calendar year that the person began working for their current employer.
Warehouse	PERS	PRES_EMPLMT_START_YR	Present Employment Start Year	CHAR(4)	This value represents the calendar year that the person began working for their current employer.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PERS	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the person with a specific transaction.
Staging	PERS	SUFFIX	Suffix	VARCHAR2(8)	This value represents the suffix after a surname to identify a person. Examples include Jr. and Sr.
Warehouse	PERS	SUFFIX	Suffix	VARCHAR2(8)	This value represents the suffix after a surname to identify a person. Examples include Jr. and Sr.
Staging	PERS	TITLE	Title	VARCHAR2(8)	This value represents the title to precede the name which is not part of the actual name.
Warehouse	PERS	TITLE	Title	VARCHAR2(8)	This value represents the title to precede the name which is not part of the actual name.
Staging	PLCY	ACTV_OR_CNCLD_CD	Active Or Canceled Code	VARCHAR2(25)	This system code describes whether this policy is active or canceled.
Warehouse	PLCY	ACTV_OR_CNCLD_CD	Active Or Canceled Code	VARCHAR2(25)	This system code describes whether this policy is active or canceled.
Warehouse	PLCY	ACTV_OR_CNCLD_DESC	Active Or Canceled Code Description	VARCHAR2(60)	This value describes active or canceled code.
Warehouse	PLCY	BEGIN_DT	Begin Date	DATE	This calendar date represents when the policy applies.
Staging	PLCY	CNCL_REASON_CD	Cancel Reason Code	VARCHAR2(25)	This system code describes the reason for a cancellation.
Warehouse	PLCY	CNCL_REASON_CD	Cancel Reason Code	VARCHAR2(25)	This system code describes the reason for a cancellation.
Warehouse	PLCY	CNCL_REASON_DESC	Cancel Reason Description	VARCHAR2(60)	This value describes the cancel reason.
Warehouse	PLCY	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the policy is currently applicable.
Warehouse	PLCY	END_DT	End Date	DATE	This calendar date represents when the policy is no longer valid.
Staging	PLCY	EXPO_BASIS_CD	Exposure Basis Code	VARCHAR2(25)	This value represents the exposure basis is the denomination in which the exposure units are expressed.
Warehouse	PLCY	EXPO_BASIS_CD	Exposure Basis Code	VARCHAR2(25)	This value represents the exposure basis is the denomination in which the exposure units are expressed.
Warehouse	PLCY	EXPO_BASIS_DESC	Exposure Basis Description	VARCHAR2(60)	This value represents the description of exposure basis.
Staging	PLCY	MONOLINE_OR_PKG_CD	Monoline or Package Code	VARCHAR2(25)	This system code tells if a policy is a monoline policy or is written as part of a package.
Warehouse	PLCY	MONOLINE_OR_PKG_CD	Monoline or Package Code	VARCHAR2(25)	This system code identifies if a policy is monoline or package.
Warehouse	PLCY	MONOLINE_OR_PKG_DESC	Monoline or Package Description	VARCHAR2(60)	This value describes the monoline or package type.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PLCY	NEW_OR_RENEWAL_CD	New or Renewal Code	VARCHAR2(25)	This value represents the indicator of whether this policy is a new policy or a renewal policy.
Warehouse	PLCY	NEW_OR_RENEWAL_CD	New or Renewal Code	VARCHAR2(25)	This value represents the indicator of whether this policy is a new policy or a renewal policy.
Warehouse	PLCY	NEW_OR_RENEWAL_DESC	New or Renewal Description	VARCHAR2(60)	This value describes the indicator of whether this policy is a new policy or a renewal policy.
Staging	PLCY	PKG_DSCNT_CD	Package Discount Code	VARCHAR2(25)	This system code indicates the presence or absence of a package discount.
Warehouse	PLCY	PKG_DSCNT_CD	Package Discount Code	VARCHAR2(25)	This system code indicates the presence or absence of a package discount.
Warehouse	PLCY	PKG_DSCNT_DESC	Package Discount Description	VARCHAR2(60)	This value describes the package discount.
Staging	PLCY	PKG_DSCNT_PCT	Package Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when package discount applies.
Warehouse	PLCY	PKG_DSCNT_PCT	Package Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when package discount applies.
Staging	PLCY	PKG_MOD_ASSIGNMENT_CD	Package Modification Assignment Code	VARCHAR2(25)	This system code indicates the package modification assignment.
Warehouse	PLCY	PKG_MOD_ASSIGNMENT_CD	Package Modification Assignment Code	VARCHAR2(25)	This system code indicates the package modification assignment.
Warehouse	PLCY	PKG_MOD_ASSIGNMENT_DESC	Package Modification Assignment Description	VARCHAR2(60)	This value describes the package modification assignment.
Staging	PLCY	PKG_MOD_FCT	Package Modification Factor	NUMBER (6,3)	This number represents the percentage of premium waived as a result of packaging coverages.
Warehouse	PLCY	PKG_MOD_FCT	Package Modification Factor	NUMBER (6, 3)	This number represents the percentage of premium waived as a result of packaging coverages.
Staging	PLCY	PLCY_CNCL_DT	Policy Cancellation Date	DATE	This calendar date represents when policy coverage ceased due to a cancellation.
Warehouse	PLCY	PLCY_CNCL_DT	Policy Cancellation Date	DATE	This calendar date represents when policy coverage ceased due to a cancellation.
Staging	PLCY	PLCY_EFF_DT	Policy Effective Date	DATE	This calendar date represents when policy coverage began.
Warehouse	PLCY	PLCY_EFF_DT	Policy Effective Date	DATE	This calendar date represents when policy coverage began.
Staging	PLCY	PLCY_EXPR_DT	Policy Expiration Date	DATE	This calendar date represents when the policy term ends.
Warehouse	PLCY	PLCY_EXPR_DT	Policy Expiration Date	DATE	This calendar date represents when the policy term ends.
Warehouse	PLCY	PLCY_ID	Policy Identifier	NUMBER (22, 0)	This system generated number identifies the policy instance.
Staging	PLCY	PLCY_NAT_KEY	Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the policy.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PLCY	PLCY_NAT_KEY	Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the policy.
Staging	PLCY	PLCY_NUM	Policy Number	VARCHAR2(25)	This value represents a number or other identifier for a policy.
Warehouse	PLCY	PLCY_NUM	Policy Number	VARCHAR2(25)	This value represents a number or other identifier for a policy.
Staging	PLCY	PLCY_ORIG_INCPN_DT	Policy Original Inception Date	DATE	This calendar date represents when insured originally purchased insurance coverage with the insurance company.
Warehouse	PLCY	PLCY_ORIG_INCPN_DT	Policy Original Inception Date	DATE	This calendar date represents when insured originally purchased insurance coverage with the insurance company.
Staging	PLCY	PLCY_TYP_CATG_CD	Policy Type Category Code	VARCHAR2(25)	This system code identifies the policy type category.
Warehouse	PLCY	PLCY_TYP_CATG_CD	Policy Type Category Code	VARCHAR2(25)	This system code identifies the policy type category.
Warehouse	PLCY	PLCY_TYP_CATG_DESC	Policy Type Category Description	VARCHAR2(60)	This value describes an additional way to categorize policies.
Staging	PLCY	PLCY_TYP_CD	Policy Type Code	VARCHAR2(25)	This system code identifies the type of policy as it would normally be identified on a coverage level.
Warehouse	PLCY	PLCY_TYP_CD	Policy Type Code	VARCHAR2(25)	This system code identifies the type of policy as it would normally be identified on a coverage level.
Warehouse	PLCY	PLCY_TYP_DESC	Policy Type Description	VARCHAR2(60)	This value describes the type of policy as it would normally be identified on a coverage level.
Staging	PLCY	PLCY_UDF_CD_1	Policy User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first policy user defined field.
Warehouse	PLCY	PLCY_UDF_CD_1	Policy User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first policy user defined field.
Staging	PLCY	PLCY_UDF_CD_2	Policy User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second policy user defined field.
Warehouse	PLCY	PLCY_UDF_CD_2	Policy User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second policy user defined field.
Staging	PLCY	PLCY_UDF_CD_3	Policy User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third policy user defined field.
Warehouse	PLCY	PLCY_UDF_CD_3	Policy User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third policy user defined field.
Staging	PLCY	PLCY_UDF_CD_4	Policy User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth policy user defined field.
Warehouse	PLCY	PLCY_UDF_CD_4	Policy User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth policy user defined field.
Staging	PLCY	PLCY_UDF_CD_5	Policy User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth policy user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PLCY	PLCY_UDF_CD_5	Policy User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth policy user defined field.
Warehouse	PLCY	PLCY_UDF_DESC_1	Policy User Defined Field Description 1	VARCHAR2(60)	This value describes the first policy user defined field.
Warehouse	PLCY	PLCY_UDF_DESC_2	Policy User Defined Field Description 2	VARCHAR2(60)	This value describes the second policy user defined field.
Warehouse	PLCY	PLCY_UDF_DESC_3	Policy User Defined Field Description 3	VARCHAR2(60)	This value describes the third policy user defined field.
Warehouse	PLCY	PLCY_UDF_DESC_4	Policy User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth policy user defined field.
Warehouse	PLCY	PLCY_UDF_DESC_5	Policy User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth policy user defined field.
Staging	PLCY	PLCY_VERSION	Policy Version	VARCHAR2(4)	This value represents the number or other identifier used by the company to identify 'this' version of the policy.
Warehouse	PLCY	PLCY_VERSION	Policy Version	VARCHAR2(4)	This value represents the number or other identifier used by the company to identify 'this' version of the policy.
Staging	PLCY	PREM_BASIS_CD	Premium Basis Code	VARCHAR2(25)	This system code identifies the type of rating scale used.
Warehouse	PLCY	PREM_BASIS_CD	Premium Basis Code	VARCHAR2(25)	This system code identifies the type of rating scale used.
Warehouse	PLCY	PREM_BASIS_DESC	Premium Basis Description	VARCHAR2(60)	This value describes the type of rating scale used.
Staging	PLCY	RENEWAL_TERM	Renewal Term in Months	VARCHAR2(3)	This value represents the length of the renewal policy period (term) in months (006,012).
Warehouse	PLCY	RENEWAL_TERM	Renewal Term in Months	VARCHAR2(3)	This value represents the length of the renewal policy period (term) in months (006,012).
Staging	PLCY	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the policy with a specific transaction.
Staging	PLCY	SUPPORTING_BUS_DSCNT_PCT	Supporting Business Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when supporting business discount applies.
Warehouse	PLCY	SUPPORTING_BUS_DSCNT_PCT	Supporting Business Discount Percentage	NUMBER (6, 3)	This number represents the percent of discount for supporting business issued with the company.
Staging	PLCY	SUPPORTING_BUS_TYP_CD	Supporting Business Type Code	VARCHAR2(25)	This value represents the type of supporting business for which the policyholder received a discount standard code.
Warehouse	PLCY	SUPPORTING_BUS_TYP_CD	Supporting Business Type Code	VARCHAR2(25)	This value represents the type of supporting business for which the policyholder received a discount.
Warehouse	PLCY	SUPPORTING_BUS_TYP_DESC	Supporting Business Type Description	VARCHAR2(60)	This value describes the Supporting business type.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PLCY_DIM	ACTV_OR_CNCLD	Active Or Canceled Code Description	VARCHAR2(60)	This value describes the active or canceled code.
Datamart	PLCY_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the policy applies.
Datamart	PLCY_DIM	CNCL_REASON	Cancel Reason	VARCHAR2(60)	This value represents the cancellation reason.
Datamart	PLCY_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the policy is currently applicable.
Datamart	PLCY_DIM	END_DT	End Date	DATE	This calendar date represents when the policy is no longer valid.
Datamart	PLCY_DIM	EXPO_BASIS	Exposure Basis	VARCHAR2(60)	This value represents the basis for which exposure applies.
Datamart	PLCY_DIM	MONOLINE_OR_PKG	Monoline or Package	VARCHAR2(60)	This value represents the indicator that describes if a policy is a monoline or a package policy.
Datamart	PLCY_DIM	NEW_OR_RENEWAL	New or Renewal	VARCHAR2(60)	This value represents the indicator that describes if the policy is a new business or renewal policy type.
Datamart	PLCY_DIM	PKG_DSCNT	Package Discount	VARCHAR2(60)	This value represents the indicator that describes the presence or absence of a discount for packaging of insurance coverage.
Datamart	PLCY_DIM	PKG_DSCNT_PCT	Package Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when package discount applies.
Datamart	PLCY_DIM	PKG_MOD_ASSIGNMENT_CD	Package Modification Assignment Code	VARCHAR2(60)	This system code indicates the package modification assignment.
Datamart	PLCY_DIM	PKG_MOD_FCT	Package Modification Factor	NUMBER (6, 3)	This number represents the percentage of premium waived as a result of packaging coverages.
Datamart	PLCY_DIM	PLCY_CNCL_DT_ID	Policy Cancellation Date Identifier	DATE	This calendar date iendtifies the policy cancellation date instance.
Datamart	PLCY_DIM	PLCY_EFF_DT_ID	Policy Effective Date Identifier	DATE	This calendar date represents the policy effective date instance.
Datamart	PLCY_DIM	PLCY_EXPR_DT_ID	Policy Expiration Date Identifier	DATE	This calendar date represents the policy expiration date instance.
Datamart	PLCY_DIM	PLCY_ID	Policy Identifier	NUMBER (22, 0)	This system generated number identifies the policy instance.
Datamart	PLCY_DIM	PLCY_NAT_KEY	Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the policy.
Datamart	PLCY_DIM	PLCY_NUM	Policy Number	VARCHAR2(25)	This value represents the number or other identifier that is assigned to policy.
Datamart	PLCY_DIM	PLCY_ORIG_INCPN_DT_ID	Policy Original Inception Date Identifier	DATE	This calendar date represents when identifies policy original inception date.
Datamart	PLCY_DIM	PLCY_TYP	Policy Type	VARCHAR2(60)	This value describes the type of coverage included in a policy.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PLCY_DIM	PLCY_TYP_CATG	Policy Type Category	VARCHAR2(60)	This value represents the categorization of the type of coverage a policy includes.
Datamart	PLCY_DIM	PLCY_UDF_1	Policy User Defined Field 1	VARCHAR2(60)	This value describes the first policy user defined field.
Datamart	PLCY_DIM	PLCY_UDF_2	Policy User Defined Field 2	VARCHAR2(60)	This value describes the second policy user defined field.
Datamart	PLCY_DIM	PLCY_UDF_3	Policy User Defined Field 3	VARCHAR2(60)	This value describes the third policy user defined field.
Datamart	PLCY_DIM	PLCY_UDF_4	Policy User Defined Field 4	VARCHAR2(60)	This value describes the fourth policy user defined field.
Datamart	PLCY_DIM	PLCY_UDF_5	Policy User Defined Field 5	VARCHAR2(60)	This value describes the fifth policy user defined field.
Datamart	PLCY_DIM	PLCY_VERSION	Policy Version	VARCHAR2(4)	This value represents the number or other identifier used by the company to identify 'this' version of the policy.
Datamart	PLCY_DIM	PREM_BASIS	Premium Basis	VARCHAR2(60)	This value represents the basis to which rates are applied to determine premiums.
Datamart	PLCY_DIM	RENEWAL_TERM	Renewal Term in Months	VARCHAR2(3)	This value represents the length of the renewal policy period (term) in months.
Datamart	PLCY_DIM	SUPPORTING_BUS_DSCNT_PCT	Supporting Business Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when supporting business discount applies.
Datamart	PLCY_DIM	SUPPORTING_BUS_TYP	Supporting Business Type	VARCHAR2(60)	This value represents the indicator that describes the type of policy that is also issued by the insurer.
Datamart	PLCY_MTH_SNAP_FACT	BILL_ACCT_ID	Billing Account Identifier	NUMBER (22, 0)	This system generated number identifies the billing account instance.
Datamart	PLCY_MTH_SNAP_FACT	CAL_MTH_ID	Calendar Month Identifier	NUMBER (22, 0)	This system generated number identifies the calendar month.
Datamart	PLCY_MTH_SNAP_FACT	CLASS_ID	Class Identifier	NUMBER (22, 0)	This system generated number identifies the class.
Datamart	PLCY_MTH_SNAP_FACT	CNCLD_PREM_PLCY_NAT_KEY	Canceled Premium Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the canceled premium.
Datamart	PLCY_MTH_SNAP_FACT	COVRG_ID	Coverage Identifier	NUMBER (22, 0)	This system generated number identifies coverage instance.
Datamart	PLCY_MTH_SNAP_FACT	COVRG_STATUS_ID	Coverage Status Identifier	NUMBER (22, 0)	This system generated number identifies coverage status instance.
Datamart	PLCY_MTH_SNAP_FACT	DC_ID	Distribution Channel Identifier	NUMBER (22, 0)	This system generated number identifies the distribution channel instance.
Datamart	PLCY_MTH_SNAP_FACT	DED_ID	Deductible Identifier	NUMBER (22, 0)	This system generated number identifies the deductible instance.
Datamart	PLCY_MTH_SNAP_FACT	DOC_CNCLD_PREM_AMT	Document Canceled Premium Amount	NUMBER (14, 3)	This number represents the document canceled premium amount.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PLCY_MTH_SNAP_FACT	DOC_COMM_AMT	Document Commission Amount	NUMBER (14, 3)	This number represents the document commission amount.
Datamart	PLCY_MTH_SNAP_FACT	DOC_CURR_CD	Document Currency Code	VARCHAR2(25)	This system code identifies document currency.
Datamart	PLCY_MTH_SNAP_FACT	DOC_EFF_PREM_AMT	Document Effective Premium Amount	NUMBER (14, 3)	This number represents the document effective premium amount.
Datamart	PLCY_MTH_SNAP_FACT	DOC_ERND_EXPO_AMT	Document Earned Exposure Amount	NUMBER (14, 3)	This number represents the amount of written exposure that is recognized as earned within a given time period.
Datamart	PLCY_MTH_SNAP_FACT	DOC_ERND_PREM_AMT	Document Earned Premium Amount	NUMBER (14, 3)	This number represents the document earned premium amount.
Datamart	PLCY_MTH_SNAP_FACT	DOC_EXPR_PREM_AMT	Document Expired Premium Amount	NUMBER (14, 3)	This number represents the document expired premium amount.
Datamart	PLCY_MTH_SNAP_FACT	DOC_FUTURE_WRTN_PREM_AMT	Document Future Written Premium Amount	NUMBER (14, 3)	This number represents the document future written premium amount.
Datamart	PLCY_MTH_SNAP_FACT	DOC_IN_FORCE_PREM_AMT	Document In-Force Premium Amount	NUMBER (14, 3)	This number represents the document in-force premium amount.
Datamart	PLCY_MTH_SNAP_FACT	DOC_PROC_PREM_AMT	Document Processed Premium Amount	NUMBER (14, 3)	This number represents the document processed premium amount.
Datamart	PLCY_MTH_SNAP_FACT	DOC_RETAINED_PREM_AMT	Document Retained Premium Amount	NUMBER (14, 3)	This number represents the document retained premium amount.
Datamart	PLCY_MTH_SNAP_FACT	DOC_WRTN_EXPO_AMT	Document Written Exposure Amount	NUMBER (14, 3)	This number represents the document written exposure amount.
Datamart	PLCY_MTH_SNAP_FACT	DOC_WRTN_PREM_AMT	Document Written Premium Amount	NUMBER (14, 3)	This number represents the document written premium amount.
Datamart	PLCY_MTH_SNAP_FACT	EFF_PREM_PLCY_NAT_KEY	Effective Premium Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the effective premium policy.
Datamart	PLCY_MTH_SNAP_FACT	EXPR_PREM_PLCY_NAT_KEY	Expired Premium Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the expired premium policy.
Datamart	PLCY_MTH_SNAP_FACT	FISCAL_MTH_ID	Fiscal Month Identifier	NUMBER (22, 0)	This number identifies fiscal month.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_CNCLD_PREM_AMT	Global 1 Canceled Premium Amount	NUMBER (14, 3)	This number represents the first global canceled premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_COMM_AMT	Global 1 Commission Amount	NUMBER (14, 3)	This number represents the first global commission amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_EFF_PREM_AMT	Global 1 Effective Premium Amount	NUMBER (14, 3)	This number represents the first global effective premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_ERND_EXPO_AMT	Global 1 Earned Exposure Amount	NUMBER (14, 3)	This number represents the amount of written exposure that is recognized as earned within a given time period.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_ERND_PREM_AMT	Global 1 Earned Premium Amount	NUMBER (14, 3)	This number represents the first global earned premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_EXPR_PREM_AMT	Global 1 Expired Premium Amount	NUMBER (14, 3)	This number represents the first global expired premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_FUTURE_WRTN_PREM_AMT	Global 1 Future Written Premium Amount	NUMBER (14, 3)	This number represents the first global future written premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_IN_FORCE_PREM_AMT	Global 1 In-Force Premium Amount	NUMBER (14, 3)	This number represents the first global in-force premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_PROC_PREM_AMT	Global 1 Processed Premium Amount	NUMBER (14, 3)	This number represents the first global processed premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_RETAINED_PREM_AMT	Global 1 Retained Premium Amount	NUMBER (14, 3)	This number represents the first global retained premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_WRTN_EXPO_AMT	Global 1 Written Exposure Amount	NUMBER (14, 3)	This number represents the first global written exposure amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_WRTN_PREM_AMT	Global 1 Written Premium Amount	NUMBER (14, 3)	This number represents the first global written premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_CNCLD_PREM_AMT	Global 2 Canceled Premium Amount	NUMBER (14, 3)	This number represents the second global canceled premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_COMM_AMT	Global 2 Commission Amount	NUMBER (14, 3)	This number represents the second global commission amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_EFF_PREM_AMT	Global 2 Effective Premium Amount	NUMBER (14, 3)	This number represents the second global effective premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_ERND_EXPO_AMT	Global 2 Earned Exposure Amount	NUMBER (14, 3)	This number represents the amount of written exposure that is recognized as earned within a given time period.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_ERND_PREM_AMT	Global 2 Earned Premium Amount	NUMBER (14, 3)	This number represents the second global earned premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_EXPR_PREM_AMT	Global 2 Expired Premium Amount	NUMBER (14, 3)	This number represents the second global expired premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_FUTURE_WRTN_PREM_AMT	Global 2 Future Written Premium Amount	NUMBER (14, 3)	This number represents the second global future written premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_IN_FORCE_PREM_AMT	Global 2 In-Force Premium Amount	NUMBER (14, 3)	This number represents the second global in-force premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_PROC_PREM_AMT	Global 2 Processed Premium Amount	NUMBER (14, 3)	This number represents the second global processed premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_RETAINED_PREM_AMT	Global 2 Retained Premium Amount	NUMBER (14, 3)	This number represents the second global retained premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_WRTN_EXPO_AMT	Global 2 Written Exposure Amount	NUMBER (14, 3)	This number represents the second global written exposure amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_WRTN_PREM_AMT	Global 2 Written Premium Amount	NUMBER (14, 3)	This number represents the second global written premium amount.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_CNCLD_PREM_AMT	Global 3 Canceled Premium Amount	NUMBER (14, 3)	This number represents the third global canceled premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_COMM_AMT	Global 3 Commission Amount	NUMBER (14, 3)	This number represents the third global commission amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_EFF_PREM_AMT	Global 3 Effective Premium Amount	NUMBER (14, 3)	This number represents the third global effective premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_ERND_EXPO_AMT	Global 3 Earned Exposure Amount	NUMBER (14, 3)	This number represents the amount of written exposure that is recognized as earned within a given time period.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_ERND_PREM_AMT	Global 3 Earned Premium Amount	NUMBER (14, 3)	This number represents the third global earned premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_EXPR_PREM_AMT	Global 3 Expired Premium Amount	NUMBER (14, 3)	This number represents the third global expired premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_FUTURE_WRTN_PREM_AMT	Global 3 Future Written Premium Amount	NUMBER (14, 3)	This number represents the third global future written premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_IN_FORCE_PREM_AMT	Global 3 In-Force Premium Amount	NUMBER (14, 3)	This number represents the third global in-force premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_PROC_PREM_AMT	Global 3 Processed Premium Amount	NUMBER (14, 3)	This number represents the third global processed premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_RETAINED_PREM_AMT	Global 3 Retained Premium Amount	NUMBER (14, 3)	This number represents the third global retained premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_WRTN_EXPO_AMT	Global 3 Written Exposure Amount	NUMBER (14, 3)	This number represents the third global written exposure amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_WRTN_PREM_AMT	Global 3 Written Premium Amount	NUMBER (14, 3)	This number represents the monthly written premium amount based on the third global currency rate.
Datamart	PLCY_MTH_SNAP_FACT	GRP_PRG_ID	Group Program Identifier	NUMBER (22, 0)	This system generated number identifies the group program instance.
Datamart	PLCY_MTH_SNAP_FACT	IN_FORCE_PREM_PLCY_NAT_KEY	In-Force Premium Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the in-force premium policy.
Datamart	PLCY_MTH_SNAP_FACT	INSD_ID	Insured Identifier	NUMBER (22, 0)	This system generated number identifies the insured instance.
Datamart	PLCY_MTH_SNAP_FACT	INSUR_CO_ID	Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the insurance company instance in the monthly snapshot fact.
Datamart	PLCY_MTH_SNAP_FACT	LMT_ID	Limit Identifier	NUMBER (22, 0)	This system generated number identifies the limit instance.
Datamart	PLCY_MTH_SNAP_FACT	LOB_FACT_ID	Line Of Business Fact Identifier	NUMBER (22, 0)	This system generated number identifies the line of business fact instance.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PLCY_MTH_SNAP_FACT	LOB_ID	Line Of Business Identifier	NUMBER (22, 0)	This system generated number identifies the line of business instance.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_CNCLD_PREM_AMT	Local Canceled Premium Amount	NUMBER (14, 3)	This number represents the local canceled premium amount.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_COMM_AMT	Local Commission Amount	NUMBER (14, 3)	This number represents the local commission amount.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_EFF_PREM_AMT	Local Effective Premium Amount	NUMBER (14, 3)	This number represents the local effective premium amount.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_ERND_EXPO_AMT	Local Earned Exposure Amount	NUMBER (14, 3)	This number represents the amount of written exposure that is recognized as earned within a given time period.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_ERND_PREM_AMT	Local Earned Premium Amount	NUMBER (14, 3)	This number represents the local earned premium amount.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_EXPR_PREM_AMT	Local Expired Premium Amount	NUMBER (14, 3)	This number represents the local expired premium amount.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_FUTURE_WRTN_PREM_AMT	Local Future Written Premium Amount	NUMBER (14, 3)	This number represents the local future written premium amount.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_IN_FORCE_PREM_AMT	Local In-Force Premium Amount	NUMBER (14, 3)	This number represents the local.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_PROC_PREM_AMT	Local Processed Premium Amount	NUMBER (14, 3)	This number represents the local processed premium amount.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_RETAINED_PREM_AMT	Local Retained Premium Amount	NUMBER (14, 3)	This number represents the local retained premium amount.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_WRTN_EXPO_AMT	Local Written Exposure Amount	NUMBER (14, 3)	This number represents the local written exposure amount.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_WRTN_PREM_AMT	Local Written Premium Amount	NUMBER (14, 3)	This number represents the local written premium amount.
Datamart	PLCY_MTH_SNAP_FACT	PARENT_INSUR_CO_ID	Parent Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the parent insurance company instance.
Datamart	PLCY_MTH_SNAP_FACT	PLCY_ID	Policy Identifier	NUMBER (22, 0)	This system generated number identifies the policy instance.
Datamart	PLCY_MTH_SNAP_FACT	PRODR_ID	Producer Identifier	NUMBER (22, 0)	This system generated number identifies the producer instance.
Datamart	PLCY_MTH_SNAP_FACT	REINS_CNTRCT_ID	Reinsurance Contract Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance contract instance.
Datamart	PLCY_MTH_SNAP_FACT	REINS_CO_ID	Reinsurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance company instance.
Datamart	PLCY_MTH_SNAP_FACT	RETAINED_PREM_PLCY_NAT_KEY	Retained Premium Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the retained premium.
Datamart	PLCY_MTH_SNAP_FACT	SUB_PRODR_ID	Sub Producer Identifier	NUMBER (22, 0)	This system generated number identifies the sub-producer instance.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PLCY_MTH_SNAP_FACT	SYS_PROC_DT	System Process Date	DATE	This calendar date represents when the system processed the policy monthly snapshot fact table.
Datamart	PLCY_MTH_SNAP_FACT	UW_ASST_ID	Underwriting Assistant Identifier	NUMBER (22, 0)	This system generated number identifies the underwriting assistant instance.
Datamart	PLCY_MTH_SNAP_FACT	UW_ID	Underwriter Identifier	NUMBER (22, 0)	This system generated number identifies the underwriter instance.
Datamart	PLCY_MTH_SNAP_FACT	WRTN_PREM_PLCY_NAT_KEY	Written Premium Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the written premium policy.
Warehouse	PLCY_TRANS	BILL_ACCT_ID	Billing Account Identifier	NUMBER (22, 0)	This system generated number identifies the billing account instance.
Staging	PLCY_TRANS	BOOK_DT	Book Date	DATE	This date represents the calendar date the policy transaction is recorded into the company's books. Usually, this is the greater of the transaction date or the effective date.
Warehouse	PLCY_TRANS	BOOK_DT	Book Date	DATE	This date represents the calendar date the policy transaction is recorded into the company's books. Usually, this is the greater of the transaction date or the effective date.
Warehouse	PLCY_TRANS	CLASS_ID	Class Identifier	NUMBER (22, 0)	This system generated number identifies the class instance.
Staging	PLCY_TRANS	COMM_AMT	Commission Amount	NUMBER (14,3)	This number represents the amount of commission to be paid for a transaction.
Warehouse	PLCY_TRANS	COMM_AMT	Commission Amount	NUMBER (14, 3)	This number represents the amount of commission to be paid for a transaction.
Staging	PLCY_TRANS	COMM_RATE	Commission Rate	NUMBER (6,5)	This number represents the rate at which the policy commission is to be paid.
Warehouse	PLCY_TRANS	COMM_RATE	Commission Rate	NUMBER (6, 5)	This number represents the rate at which the policy commission is to be paid.
Staging	PLCY_TRANS	COVRG_EFF_DT	Coverage Effective Date	DATE	This date represents the calendar date of the policy coverage begins.
Warehouse	PLCY_TRANS	COVRG_EFF_DT	Coverage Effective Date	DATE	This date represents the calendar date of the policy coverage begins.
Staging	PLCY_TRANS	COVRG_EXPR_DT	Coverage Expiration Date	DATE	This date represents the calendar date of the policy coverage ends.
Warehouse	PLCY_TRANS	COVRG_EXPR_DT	Coverage Expiration Date	DATE	This date represents the calendar date of the policy coverage ends.
Warehouse	PLCY_TRANS	COVRG_ID	Coverage Identifier	NUMBER (22, 0)	This system generated number identifies coverage instance.
Warehouse	PLCY_TRANS	COVRG_STATUS_ID	Coverage Status Identifier	NUMBER (22, 0)	This system generated number identifies coverage status instance.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PLCY_TRANS	DC_ID	Distribution Channel Identifier	NUMBER (22, 0)	This system generated number identifies the distribution channel instance.
Staging	PLCY_TRANS	DED_AMT	Deductible Amount	NUMBER (14,3)	This number represents the monetary cost portion of any claim that is not covered by the insurer.
Warehouse	PLCY_TRANS	DED_AMT	Deductible Amount	NUMBER (14, 3)	This number represents the monetary amount portion of any claim that is not covered by the insurer.
Warehouse	PLCY_TRANS	DED_ID	Deductible Identifier	NUMBER (22, 0)	This system generated number identifies the deductible instance.
Staging	PLCY_TRANS	DIRECT_CEDED_ASSUMED_CD	Direct or Ceded or Assumed Code	VARCHAR2(25)	This system code identifies the transaction type as being direct, ceded, or assumed.
Warehouse	PLCY_TRANS	DIRECT_CEDED_ASSUMED_CD	Direct or Ceded or Assumed Code	VARCHAR2(25)	This system code identifies the transaction type as being direct, ceded, or assumed.
Warehouse	PLCY_TRANS	DIRECT_CEDED_ASSUMED_DESC	Direct or Ceded or Assumed Description	VARCHAR2(60)	This value describes a policy transaction that identifies if the risk is insured internally, transferred to a reinsurer, or assumed.
Staging	PLCY_TRANS	DOC_CURR_CD	Document Currency Code	VARCHAR2(25)	This system code identifies document currency for a policy transaction.
Warehouse	PLCY_TRANS	DOC_CURR_CD	Document Currency Code	VARCHAR2(25)	This system code identifies document currency.
Warehouse	PLCY_TRANS	GLOBAL_CURR_RATE_1	Global Currency Rate 1	NUMBER (22, 7)	This number represents the first global currency rate.
Warehouse	PLCY_TRANS	GLOBAL_CURR_RATE_2	Global Currency Rate 2	NUMBER (22, 7)	This number represents the second global currency rate.
Warehouse	PLCY_TRANS	GLOBAL_CURR_RATE_3	Global Currency Rate 3	NUMBER (22, 7)	This number represents the third global currency rate.
Warehouse	PLCY_TRANS	GRP_PRG_ID	Group Program Identifier	NUMBER (22, 0)	This system generated number identifies the group program instance.
Warehouse	PLCY_TRANS	LMT_ID	Limit Identifier	NUMBER (22, 0)	This system generated number identifies the limit instance.
Warehouse	PLCY_TRANS	LOB_ID	Line Of Business Identifier	NUMBER (22, 0)	This system generated number identifies the line of business instance.
Warehouse	PLCY_TRANS	LOCAL_CURR_RATE	Local Currency Rate	NUMBER (22, 7)	This number represents the local currency rate.
Staging	PLCY_TRANS	ONSET_OR_OFFSET_CD	Onset or Offset Code	VARCHAR2(25)	This value represents the indicator of onset or offset transactions.
Warehouse	PLCY_TRANS	ONSET_OR_OFFSET_CD	Onset or Offset Code	VARCHAR2(25)	This value represents the indicator of onset or offset transactions.
Warehouse	PLCY_TRANS	ONSET_OR_OFFSET_DESC	Onset or Office Description	VARCHAR2(60)	This value describes onset or offset transaction.
Staging	PLCY_TRANS	ORIG_PREM_AMT	Original Premium Amount	NUMBER (14,3)	This number represents the original premium in the term of coverage.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PLCY_TRANS	ORIG_PREM_AMT	Original Premium Amount	NUMBER (14, 3)	This number represents the original premium in the term of coverage.
Warehouse	PLCY_TRANS	PLCY_ID	Policy Identifier	NUMBER (22, 0)	This system generated number identifies the policy instance.
Staging	PLCY_TRANS	PLCY_TRANS_AMT	Policy Transaction Amount	NUMBER (14,3)	This number represents the amount of any transaction processed for a policy.
Warehouse	PLCY_TRANS	PLCY_TRANS_AMT	Policy Transaction Amount	NUMBER (14, 3)	This number represents the amount of any transaction processed for a policy.
Staging	PLCY_TRANS	PLCY_TRANS_CATG_CD	Policy Transaction Category Code	VARCHAR2(25)	This system code groups like transactions for analysis.
Warehouse	PLCY_TRANS	PLCY_TRANS_CATG_CD	Policy Transaction Category Code	VARCHAR2(25)	This system code groups like transactions for analysis.
Warehouse	PLCY_TRANS	PLCY_TRANS_CATG_DESC	Policy Transaction Category Description	VARCHAR2(60)	This value describes the code groups like transactions for analysis.
Staging	PLCY_TRANS	PLCY_TRANS_CD	Policy Transaction Code	VARCHAR2(25)	This system code identifies the policy transaction.
Warehouse	PLCY_TRANS	PLCY_TRANS_CD	Policy Transaction Code	VARCHAR2(25)	This system code identifies the policy transaction.
Warehouse	PLCY_TRANS	PLCY_TRANS_DESC	Policy Transaction Description	VARCHAR2(60)	This value describes the policy transaction.
Warehouse	PLCY_TRANS	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction instance.
Staging	PLCY_TRANS	PREM_OR_NON_PREM_CD	Premium or Non-Premium Code	VARCHAR2(25)	This system code describes if a policy transaction resulted in a change in the premium charged for an existing policy.
Warehouse	PLCY_TRANS	PREM_OR_NON_PREM_CD	Premium or Non-Premium Code	VARCHAR2(25)	This system code describes if a policy transaction resulted in a change in the premium charged for an existing policy.
Warehouse	PLCY_TRANS	PREM_OR_NON_PREM_DESC	Premium or Non-Premium Description	VARCHAR2(60)	This value describes the premium or non-premium transaction.
Warehouse	PLCY_TRANS	REINS_CNTRCT_ID	Reinsurance Contract Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance contract instance.
Staging	PLCY_TRANS	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the policy transaction with a specific transaction.
Staging	PLCY_TRANS	SRC_SYS_PROC_DT	Source System Process Date	DATE	This calendar date represents when source system processed the policy transaction.
Warehouse	PLCY_TRANS	SRC_SYS_PROC_DT	Source System Process Date	DATE	This calendar date represents when source system processed the policy transaction.
Warehouse	PLCY_TRANS	SYS_PLCY_TRANS_CD	System Policy Transaction Code	VARCHAR2(25)	This system code represents the system policy transaction for a policy transaction.
Warehouse	PLCY_TRANS	SYS_PLCY_TRANS_DESC	System Policy Transaction Description	VARCHAR2(60)	This value describes a system policy transaction.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PLCY_TRANS	SYS_PROC_DT	System Process Date	DATE	This calendar date represents when the system processed the policy transaction.
Staging	PLCY_TRANS	TRANS_EFF_DT	Transaction Effective Date	DATE	This calendar date represents when a policy transaction is effective.
Warehouse	PLCY_TRANS	TRANS_EFF_DT	Transaction Effective Date	DATE	This calendar date represents when a policy transaction is effective.
Staging	PLCY_TRANS	WRTN_EXPO_AMT	Written Exposure Amount	NUMBER (14,3)	This number represents the measure of the loss exposure assumed by the insurer.
Warehouse	PLCY_TRANS	WRTN_EXPO_AMT	Written Exposure Amount	NUMBER (14, 3)	This number represents the measure of the loss exposure assumed by the insurer.
Datamart	PLCY_TRANS_CD_DIM	ONSET_OR_OFFSET	Onset or Offset	VARCHAR2(60)	This value represents the indicator that describes if a policy transaction is an onset transaction or offset transaction.
Datamart	PLCY_TRANS_CD_DIM	PLCY_TRANS_CATG_CD	Policy Transaction Category Code	VARCHAR2(60)	This system code identifies the policy transaction category.
Datamart	PLCY_TRANS_CD_DIM	PLCY_TRANS_CD	Policy Transaction Code	VARCHAR2(60)	This system code identifies the policy transaction.
Datamart	PLCY_TRANS_CD_DIM	PLCY_TRANS_CD_ID	Policy Transaction Code Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction code instance.
Datamart	PLCY_TRANS_CD_DIM	PREM_OR_NON_PREM	Premium or Non-Premium	VARCHAR2(60)	This value represents the indicator that describes if a policy transaction resulted in a change in the premium charged for an existing policy.
Datamart	PLCY_TRANS_CD_DIM	SYS_PLCY_TRANS_CD	System Policy Transaction Code	VARCHAR2(60)	This system code represents the system policy transaction.
Datamart	PLCY_TRANS_FACT	BILL_ACCT_ID	Billing Account Identifier	NUMBER (22, 0)	This system generated number identifies the billing account instance.
Datamart	PLCY_TRANS_FACT	BOOK_DT_ID	Book Date Identifier	DATE	This calendar date represents when identifies the book date instance.
Datamart	PLCY_TRANS_FACT	CLASS_ID	Class Identifier	NUMBER (22, 0)	This system generated number identifies the class instance.
Datamart	PLCY_TRANS_FACT	COMM_AMT	Commission Amount	NUMBER (14, 3)	This number represents the amount of commission to be paid for a transaction.
Datamart	PLCY_TRANS_FACT	COMM_RATE	Commission Rate	NUMBER (6, 5)	This number represents the rate at which the policy commission is to be paid.
Datamart	PLCY_TRANS_FACT	COVRG_ID	Coverage Identifier	NUMBER (22, 0)	This system generated number identifies coverage instance.
Datamart	PLCY_TRANS_FACT	COVRG_STATUS_ID	Coverage Status Identifier	NUMBER (22, 0)	This system generated number identifies coverage status instance.
Datamart	PLCY_TRANS_FACT	DC_ID	Distribution Channel Identifier	NUMBER (22, 0)	This system generated number identifies the distribution channel instance.
Datamart	PLCY_TRANS_FACT	DED_ID	Deductible Identifier	NUMBER (22, 0)	This system generated number identifies the deductible instance.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PLCY_TRANS_FACT	DOC_CURR_CD	Document Currency Code	VARCHAR2(25)	This system code identifies document currency.
Datamart	PLCY_TRANS_FACT	GLOBAL_CURR_RATE_1	Global Currency Rate 1	NUMBER (22, 7)	This number represents the first global currency rate.
Datamart	PLCY_TRANS_FACT	GLOBAL_CURR_RATE_2	Global Currency Rate 2	NUMBER (22, 7)	This number represents the second global currency rate.
Datamart	PLCY_TRANS_FACT	GLOBAL_CURR_RATE_3	Global Currency Rate 3	NUMBER (22, 7)	This number represents the third global currency rate.
Datamart	PLCY_TRANS_FACT	GRP_PRG_ID	Group Program Identifier	NUMBER (22, 0)	This system generated number identifies the group program instance.
Datamart	PLCY_TRANS_FACT	INSD_ID	Insured Identifier	NUMBER (22, 0)	This system generated number identifies the insured instance.
Datamart	PLCY_TRANS_FACT	INSUR_CO_ID	Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the insurance company instance.
Datamart	PLCY_TRANS_FACT	LMT_ID	Limit Identifier	NUMBER (22, 0)	This system generated number identifies the limit instance.
Datamart	PLCY_TRANS_FACT	LOB_FACT_ID	Line Of Business Fact Identifier	NUMBER (22, 0)	This system generated number identifies the line of business fact instance.
Datamart	PLCY_TRANS_FACT	LOB_ID	Line Of Business Identifier	NUMBER (22, 0)	This system generated number identifies the line of business instance.
Datamart	PLCY_TRANS_FACT	LOCAL_CURR_RATE	Local Currency Rate	NUMBER (22, 7)	This number represents the local currency rate.
Datamart	PLCY_TRANS_FACT	ORIG_PREM_AMT	Original Premium Amount	NUMBER (14, 3)	This number represents the original premium charge for the policy term.
Datamart	PLCY_TRANS_FACT	PARENT_INSUR_CO_ID	Parent Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the parent insurance company instance.
Datamart	PLCY_TRANS_FACT	PLCY_ID	Policy Identifier	NUMBER (22, 0)	This system generated number identifies the policy instance.
Datamart	PLCY_TRANS_FACT	PLCY_TRANS_AMT	Policy Transaction Amount	NUMBER (14, 3)	This number represents the amount of any transaction processed for a policy.
Datamart	PLCY_TRANS_FACT	PLCY_TRANS_CD_ID	Policy Transaction Code Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction code instance.
Datamart	PLCY_TRANS_FACT	PRODR_ID	Producer Identifier	NUMBER (22, 0)	This system generated number identifies the producer instance.
Datamart	PLCY_TRANS_FACT	REINS_CNTRCT_ID	Reinsurance Contract Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance contract instance.
Datamart	PLCY_TRANS_FACT	REINS_CO_ID	Reinsurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance contract instance.
Datamart	PLCY_TRANS_FACT	SRC_SYS_PROC_DT_ID	Source System Process Date Identifier	DATE	This calendar date represents the source system process date instance.
Datamart	PLCY_TRANS_FACT	SUB_PRODR_ID	Sub Producer Identifier	NUMBER (22, 0)	This system generated number identifies the sub-producer instance.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PLCY_TRANS_FACT	SYS_PROC_DT	System Process Date	DATE	This calendar date represents when the system processed the policy transaction.
Datamart	PLCY_TRANS_FACT	TRANS_EFF_DT_ID	Transaction Effective Date Identifier	DATE	This calendar date represents the transaction effective date instance.
Datamart	PLCY_TRANS_FACT	UW_ASST_ID	Underwriting Assistant Identifier	NUMBER (22, 0)	This system generated number identifies the underwriting assistant instance.
Datamart	PLCY_TRANS_FACT	UW_ID	Underwriter Identifier	NUMBER (22, 0)	This system generated number identifies the underwriter instance.
Datamart	PLCY_TRANS_FACT	WRTN_EXPO_AMT	Written Exposure Amount	NUMBER (14, 3)	This number represents the measure of the loss exposure assumed by the insurer.
Warehouse	PLCY_TRANS_TO_CA_VEH	CA_VEH_ID	Commercial Auto Vehicle Identifier	NUMBER (22, 0)	This system generated number identifies the commercial vehicle instance.
Warehouse	PLCY_TRANS_TO_CA_VEH	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction instance in the policy transaction to commercial vehicle.
Warehouse	PLCY_TRANS_TO_CP_BLDG	CP_BLDG_ID	Commercial Property Building Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling in the policy transaction to commercial property building.
Warehouse	PLCY_TRANS_TO_CP_BLDG	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction instance .
Warehouse	PLCY_TRANS_TO_DF_DWLNG	DF_DWLNG_ID	Dwelling Fire Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling instance .
Warehouse	PLCY_TRANS_TO_DF_DWLNG	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction instance .
Warehouse	PLCY_TRANS_TO_HO_DWLNG	HO_DWLNG_ID	Homeowners Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the homeowners dwelling instance.
Warehouse	PLCY_TRANS_TO_HO_DWLNG	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction instance.
Warehouse	PLCY_TRANS_TO_PA_VEH	PA_VEH_ID	Persona Auto Vehicle Identifier	NUMBER (22, 0)	This system generated number identifies the personal vehicle instance.
Warehouse	PLCY_TRANS_TO_PA_VEH	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction instance.
Warehouse	PLCY_TRANS_TO_PARTY	PARTY_ID	Party Identifier	NUMBER (22, 0)	This system generated number identifies the party instance.
Warehouse	PLCY_TRANS_TO_PARTY	PARTY_ROLE_ID	Party Role Identifier	NUMBER (22, 0)	This system generated number identifies the party role instance.
Warehouse	PLCY_TRANS_TO_PARTY	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction instance.
Warehouse	PLCY_TRANS_TO_PU_PLCY	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction instance.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PLCY_TRANS_TO_PU_PLCY	PU_PLCY_ID	Personal Umbrella Policy Identifier	NUMBER (22, 0)	This system generated number identifies the personal umbrella policy instance.
Warehouse	PRODR	BEGIN_DT	Begin Date	DATE	This calendar date represents when the producer appointment begins.
Warehouse	PRODR	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the producer is currently applicable.
Warehouse	PRODR	END_DT	End Date	DATE	This calendar date represents when the producer is no longer valid.
Warehouse	PRODR	ORG_ID	Organization Identifier	NUMBER (22, 0)	This system generated number identifies the producer organization instance.
Warehouse	PRODR	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	PRODR	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person instance.
Staging	PRODR	PRODR_EFF_DT	Producer Effective Date	DATE	This date represents the calendar date the producer appointment begins.
Warehouse	PRODR	PRODR_EFF_DT	Producer Effective Date	DATE	This date represents the calendar date the producer appointment begins.
Warehouse	PRODR	PRODR_ID	Producer Identifier	NUMBER (22, 0)	This system generated number identifies the producer instance.
Staging	PRODR	PRODR_NUM	Producer Number	VARCHAR2(10)	This value represents the number or other identifier assigned to the producer of the business.
Warehouse	PRODR	PRODR_NUM	Producer Number	VARCHAR2(10)	This value represents the number or other identifier assigned to the producer of the business.
Staging	PRODR	PRODR_RLAT_CD	Producer Relationship Code	VARCHAR2(25)	This system code identifies the producer relationship.
Staging	PRODR	PRODR_TYP_CD	Producer Type Code	VARCHAR2(25)	This system code represents the producer type standard code.
Warehouse	PRODR	PRODR_TYP_CD	Producer Type Code	VARCHAR2(25)	This system code represents the producer type Standard code.
Warehouse	PRODR	PRODR_TYP_DESC	Producer Type Description	VARCHAR2(60)	This value describes the producer type.
Staging	PRODR	PRODR_UDF_CD_1	Producer User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first producer user defined field.
Warehouse	PRODR	PRODR_UDF_CD_1	Producer User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first producer user defined field.
Staging	PRODR	PRODR_UDF_CD_2	Producer User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second producer user defined field.
Warehouse	PRODR	PRODR_UDF_CD_2	Producer User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second producer user defined field.
Staging	PRODR	PRODR_UDF_CD_3	Producer User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third producer user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PRODR	PRODR_UDF_CD_3	Producer User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third producer user defined field.
Staging	PRODR	PRODR_UDF_CD_4	Producer User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth producer user defined field.
Warehouse	PRODR	PRODR_UDF_CD_4	Producer User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth producer user defined field.
Staging	PRODR	PRODR_UDF_CD_5	Producer User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth producer user defined field.
Warehouse	PRODR	PRODR_UDF_CD_5	Producer User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth producer user defined field.
Warehouse	PRODR	PRODR_UDF_DESC_1	Producer User Defined Field Description 1	VARCHAR2(60)	This value describes the first producer user defined field.
Warehouse	PRODR	PRODR_UDF_DESC_2	Producer User Defined Field Description 2	VARCHAR2(60)	This value describes the second producer user defined field.
Warehouse	PRODR	PRODR_UDF_DESC_3	Producer User Defined Field Description 3	VARCHAR2(60)	This value describes the third producer user defined field.
Warehouse	PRODR	PRODR_UDF_DESC_4	Producer User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth producer user defined field.
Warehouse	PRODR	PRODR_UDF_DESC_5	Producer User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth producer user defined field.
Staging	PRODR	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the producer with a specific transaction.
Staging	PRODR	STATE_LIC_NUM	State License Number	VARCHAR2(10)	This value represents the license number of the producer as assigned by the state insurance department.
Warehouse	PRODR	STATE_LIC_NUM	State License Number	VARCHAR2(10)	This value represents the license number of the producer as assigned by the state insurance department.
Datamart	PRODR_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the producer applies.
Datamart	PRODR_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the producer is currently applicable.
Datamart	PRODR_DIM	END_DT	End Date	DATE	This calendar date represents when the producer is no longer valid.
Datamart	PRODR_DIM	PRODR_BIRTH_DT_ID	Producer Birth Date Identifier	DATE	This calendar date represents the producer's date of birth.
Datamart	PRODR_DIM	PRODR_BUS_START_DT_ID	Producer Business Start Date Identifier	DATE	This calendar date represents the producer business start date instance.
Datamart	PRODR_DIM	PRODR_CNTCT_DESC	Producer Contact Description	VARCHAR2(60)	This value describes a producer's contact method.
Datamart	PRODR_DIM	PRODR_CNTCT_TYP	Producer Contact Type	VARCHAR2(60)	This value represents the contact method for producer.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PRODR_DIM	PRODR_CNTCT_UDF_1	Producer Contact User Defined Field 1	VARCHAR2(60)	This value describes the first producer contact user defined field.
Datamart	PRODR_DIM	PRODR_CNTCT_UDF_2	Producer Contact User Defined Field 2	VARCHAR2(60)	This value describes the second producer contact user defined field.
Datamart	PRODR_DIM	PRODR_CNTCT_UDF_3	Producer Contact User Defined Field 3	VARCHAR2(60)	This value describes the third producer contact user defined field.
Datamart	PRODR_DIM	PRODR_CNTCT_UDF_4	Producer Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth producer contact user defined field.
Datamart	PRODR_DIM	PRODR_CNTCT_UDF_5	Producer Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth producer contact user defined field.
Datamart	PRODR_DIM	PRODR_CNTY	Producer County	VARCHAR2(60)	This value identifies the county where producer is located.
Datamart	PRODR_DIM	PRODR_CTRY	Producer Country	VARCHAR2(60)	This value identifies the country where producer is located.
Datamart	PRODR_DIM	PRODR_CTY	Producer City	VARCHAR2(32)	This value identifies the city where producer is located.
Datamart	PRODR_DIM	PRODR_DBA	Producer Doing Business As	VARCHAR2(170)	This value represents the operational name of a producer's business.
Datamart	PRODR_DIM	PRODR_DSTRCT	Producer District	VARCHAR2(60)	This value represents the district where producer is located.
Datamart	PRODR_DIM	PRODR_EFF_DT_ID	Producer Effective Date Identifier	DATE	This calendar date represents the producer effective date instance.
Datamart	PRODR_DIM	PRODR_GENDER	Producer Gender	VARCHAR2(60)	This value represents the gender (male or female) of the producer.
Datamart	PRODR_DIM	PRODR_GEOG_BNDRY_UDF_1	Producer Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first producer geographic boundary user defined field.
Datamart	PRODR_DIM	PRODR_GEOG_BNDRY_UDF_2	Producer Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second producer geographic boundary user defined field.
Datamart	PRODR_DIM	PRODR_GEOG_BNDRY_UDF_3	Producer Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third producer geographic boundary user defined field.
Datamart	PRODR_DIM	PRODR_GEOG_BNDRY_UDF_4	Producer Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth producer geographic boundary user defined field.
Datamart	PRODR_DIM	PRODR_GEOG_BNDRY_UDF_5	Producer Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth producer geographic boundary user defined field.
Datamart	PRODR_DIM	PRODR_GOVT_ID_NUM	Producer Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the producer. For example, in the USA: SSN or FEIN.
Datamart	PRODR_DIM	PRODR_ID	Producer Identifier	NUMBER (22, 0)	This system generated number identifies the producer instance.
Datamart	PRODR_DIM	PRODR_LATITUDE	Producer Latitude	VARCHAR2(11)	This value represents the latitude location of the producer

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PRODR_DIM	PRODR_LONGITUDE	Producer Longitude	VARCHAR2(11)	This value represents the longitude location of the producer
Datamart	PRODR_DIM	PRODR_MARITAL_STATUS	Producer Marital Status	VARCHAR2(60)	This value represents the present marital condition (single, married, divorced, widowed) of the producer.
Datamart	PRODR_DIM	PRODR_NAICS_CD	Producer North American Industry Classification System Code	VARCHAR2(60)	This value represents the North American Industry Classification System (NAICS) code issued to producer.
Datamart	PRODR_DIM	PRODR_NAT_KEY	Producer Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the producer.
Datamart	PRODR_DIM	PRODR_NM	Producer Name	VARCHAR2(170)	This value represents the full name of producer.
Datamart	PRODR_DIM	PRODR_NOB	Producer Nature of Business	VARCHAR2(60)	This value represents the type or category of the business activities done by the producer.
Datamart	PRODR_DIM	PRODR_NUM	Producer Number	VARCHAR2(10)	This value represents the number or other identifier assigned to the producer of the business.
Datamart	PRODR_DIM	PRODR_NUM_EMP	Producer Number of Employees	NUMBER (22, 0)	This number represents the count of people employed by producer.
Datamart	PRODR_DIM	PRODR_ORG_UDF_1	Producer Organization User Defined Field 1	VARCHAR2(60)	This value describes the first producer organization user defined field.
Datamart	PRODR_DIM	PRODR_ORG_UDF_2	Producer Organization User Defined Field 2	VARCHAR2(60)	This value describes the second producer organization user defined field.
Datamart	PRODR_DIM	PRODR_ORG_UDF_3	Producer Organization User Defined Field 3	VARCHAR2(60)	This value describes the third producer organization user defined field.
Datamart	PRODR_DIM	PRODR_ORG_UDF_4	Producer Organization User Defined Field 4	VARCHAR2(60)	This value describes the fourth producer organization user defined field.
Datamart	PRODR_DIM	PRODR_ORG_UDF_5	Producer Organization User Defined Field 5	VARCHAR2(60)	This value describes the fifth producer organization user defined field.
Datamart	PRODR_DIM	PRODR_PARTY_UDF_1	Producer Party User Defined Field 1	VARCHAR2(60)	This value describes the first producer party user defined field.
Datamart	PRODR_DIM	PRODR_PARTY_UDF_2	Producer Party User Defined Field 2	VARCHAR2(60)	This value describes the second producer party user defined field.
Datamart	PRODR_DIM	PRODR_PARTY_UDF_3	Producer Party User Defined Field 3	VARCHAR2(60)	This value describes the third producer party user defined field.
Datamart	PRODR_DIM	PRODR_PARTY_UDF_4	Producer Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth producer party user defined field.
Datamart	PRODR_DIM	PRODR_PARTY_UDF_5	Producer Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth producer party user defined field.
Datamart	PRODR_DIM	PRODR_PERS_UDF_1	Producer Person on User Defined Field 1	VARCHAR2(60)	This value describes the first producer person user defined field.
Datamart	PRODR_DIM	PRODR_PERS_UDF_2	Producer Person on User Defined Field 2	VARCHAR2(60)	This value describes the second producer person user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PRODR_DIM	PRODR_PERS_UDF_3	Producer Person on User Defined Field 3	VARCHAR2(60)	This value describes the third producer person user defined field.
Datamart	PRODR_DIM	PRODR_PERS_UDF_4	Producer Person on User Defined Field 4	VARCHAR2(60)	This value describes the fourth producer person user defined field.
Datamart	PRODR_DIM	PRODR_PERS_UDF_5	Producer Person on User Defined Field 5	VARCHAR2(60)	This value describes the fifth producer person user defined field.
Datamart	PRODR_DIM	PRODR_PRES_EMPLMT_START_YR	Producer Present Employment Start Year	CHAR(4)	This value represents the calendar year when producer began working for their current employer.
Datamart	PRODR_DIM	PRODR_PSTL_CD	Producer Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	PRODR_DIM	PRODR_PSTL_CD_PRFX	Producer Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	PRODR_DIM	PRODR_PSTL_SUB_CD	Producer Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	PRODR_DIM	PRODR_REGION	Producer Region	VARCHAR2(60)	This value represents the geographic region where producer is located.
Datamart	PRODR_DIM	PRODR_SIC_CD	Producer Standard Industrial Classification Code	VARCHAR2(60)	This system code is the SIC code assigned to the producer. The Standard Industrial Classification (SIC) code is an industry code that identifies the classification of business activity.
Datamart	PRODR_DIM	PRODR_STATE	Producer State	VARCHAR2(60)	This value identifies the state where producer is located.
Datamart	PRODR_DIM	PRODR_STATE_LIC_NUM	Producer State License Number	VARCHAR2(10)	This value represents the government-issued license number issued to producer.
Datamart	PRODR_DIM	PRODR_TAX_LOC_ID	Producer Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier in the producer's location.
Datamart	PRODR_DIM	PRODR_TERR	Producer Territory	VARCHAR2(60)	This value represents the territory where producer is located.
Datamart	PRODR_DIM	PRODR_TYP	Producer Type	VARCHAR2(60)	This value describes the producer type.
Datamart	PRODR_DIM	PRODR_UDF_1	Producer User Defined Field 1	VARCHAR2(60)	This value describes the first producer user defined field.
Datamart	PRODR_DIM	PRODR_UDF_2	Producer User Defined Field 2	VARCHAR2(60)	This value describes the second producer user defined field.
Datamart	PRODR_DIM	PRODR_UDF_3	Producer User Defined Field 3	VARCHAR2(60)	This value describes the third producer user defined field.
Datamart	PRODR_DIM	PRODR_UDF_4	Producer User Defined Field 4	VARCHAR2(60)	This value describes the fourth producer user defined field.
Datamart	PRODR_DIM	PRODR_UDF_5	Producer User Defined Field 5	VARCHAR2(60)	This value describes the fifth producer user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PSTL_ADDR	ADDR_1	Address Line 1	VARCHAR2(60)	This value represents the first line of the postal address.
Warehouse	PSTL_ADDR	ADDR_1	Address Line 1	VARCHAR2(60)	This value represents the first line of the postal address.
Staging	PSTL_ADDR	ADDR_2	Address Line 2	VARCHAR2(60)	This value represents the second line of the postal address.
Warehouse	PSTL_ADDR	ADDR_2	Address Line 2	VARCHAR2(60)	This value represents the second line of the postal address.
Warehouse	PSTL_ADDR	CNTCT_ID	Contact Identifier	NUMBER (22, 0)	This system generated number identifies the contact instance.
Staging	PSTL_ADDR	CNTY_CD	County Code	VARCHAR2(25)	This system code describes a county associated with the postal address.
Staging	PSTL_ADDR	CTRY_CD	Country Code	VARCHAR2(25)	This system code describes a county associated with the postal address.
Staging	PSTL_ADDR	CTY	City	VARCHAR2(32)	This value identifies the city in the postal address.
Staging	PSTL_ADDR	DSTRCT_CD	District Code	VARCHAR2(25)	This system code identifies the company-defined district associated with the postal address.
Warehouse	PSTL_ADDR	GEOG_BNDRY_ID	Geographic Boundary Identifier	NUMBER (22, 0)	This system generated number identifies the geographic boundary instance in the postal address.
Staging	PSTL_ADDR	LATITUDE	Latitude	VARCHAR2(11)	This value represents the latitude location of the postal address.
Staging	PSTL_ADDR	LONGITUDE	Longitude	VARCHAR2(11)	This value represents the longitude location of the postal address.
Warehouse	PSTL_ADDR	PSTL_ADDR_ID	Postal Address Identifier	NUMBER (22, 0)	This system generated number identifies the postal address.
Staging	PSTL_ADDR	PSTL_ADDR_RLAT_CD	Postal Address Relationship Code	VARCHAR2(25)	This system code identifies the postal address relationship.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_1	Postal Address User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first postal address user defined field.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_CD_1	Postal Address User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first postal address user defined field.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_10	Postal Address User Defined Field Code 10	VARCHAR2(25)	This system code identifies the tenth postal address user defined field.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_2	Postal Address User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second postal address user defined field.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_CD_2	Postal Address User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second postal address user defined field.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_3	Postal Address User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third postal address user defined field.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_CD_3	Postal Address User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third postal address user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_4	Postal Address User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth postal address user defined field.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_CD_4	Postal Address User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth postal address user defined field.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_5	Postal Address User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth postal address user defined field.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_CD_5	Postal Address User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth postal address user defined field.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_6	Postal Address User Defined Field Code 6	VARCHAR2(25)	This system code identifies the sixth postal address user defined field.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_7	Postal Address User Defined Field Code 7	VARCHAR2(25)	This system code identifies the seventh postal address user defined field.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_8	Postal Address User Defined Field Code 8	VARCHAR2(25)	This system code identifies the eighth postal address user defined field.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_9	Postal Address User Defined Field Code 9	VARCHAR2(25)	This system code identifies the ninth postal address user defined field.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_DESC_1	Postal Address User Defined Field Description 1	VARCHAR2(60)	This value describes the first postal address user defined field.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_DESC_2	Postal Address User Defined Field Description 2	VARCHAR2(60)	This value describes the second postal address user defined field.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_DESC_3	Postal Address User Defined Field Description 3	VARCHAR2(60)	This value describes the third postal address user defined field.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_DESC_4	Postal Address User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth postal address user defined field.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_DESC_5	Postal Address User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth postal address user defined field.
Staging	PSTL_ADDR	PSTL_CD	Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Staging	PSTL_ADDR	PSTL_CD_PRFX	Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Staging	PSTL_ADDR	PSTL_SUB_CD	Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Staging	PSTL_ADDR	REGION_CD	Region Code	VARCHAR2(25)	This system code identifies the geographic region as defined by company specifications.
Staging	PSTL_ADDR	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the postal address with a specific transaction.
Staging	PSTL_ADDR	STATE_CD	State Code	VARCHAR2(25)	This value identifies the state associated with the postal address.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PSTL_ADDR	TAX_LOC_ID	Tax Location Identifier	VARCHAR2(6)	This value represents the classification of the taxing entity for a postal address.
Staging	PSTL_ADDR	TERR_CD	Territory Code	VARCHAR2(25)	This system code describes the territory for a postal address.
Datamart	PU_FACT	PU_FACT_ID	Personal Umbrella Fact Identifier	NUMBER (22, 0)	This system generated number identifies the personal umbrella fact instance.
Datamart	PU_FACT	PU_PLCY_ID	Personal Umbrella Policy Identifier	NUMBER (22, 0)	This system generated number identifies the personal umbrella policy instance.
Staging	PU_PLCY	DF_INSUR_CO_NM	Dwelling Fire Insurance Company Name	VARCHAR2(170)	This value represents the name of insurance company that provides dwelling fire policy coverage for insured.
Warehouse	PU_PLCY	DF_INSUR_CO_NM	Dwelling Fire Insurance Company Name	VARCHAR2(170)	This value represents the name of insurance company that provides dwelling fire policy coverage for insured.
Staging	PU_PLCY	DF_PLCY_EFF_DT	Dwelling Fire Policy Effective Date	DATE	This date represents the calendar date dwelling fire policy coverage begins.
Warehouse	PU_PLCY	DF_PLCY_EFF_DT	Dwelling Fire Policy Effective Date	DATE	This date represents the calendar date dwelling fire policy coverage begins.
Staging	PU_PLCY	DF_PLCY_EXPR_DT	Dwelling Fire Expiration Date	DATE	This date represents the calendar date dwelling fire policy term ends.
Warehouse	PU_PLCY	DF_PLCY_EXPR_DT	Dwelling Fire Expiration Date	DATE	This date represents the calendar date dwelling fire policy term ends.
Staging	PU_PLCY	DF_PLCY_NUM	Dwelling Fire Policy Number	VARCHAR2(25)	This value represents a number or other identifier for a dwelling fire policy owned by named insured.
Warehouse	PU_PLCY	DF_PLCY_NUM	Dwelling Fire Policy Number	VARCHAR2(25)	This value represents a number or other identifier for a dwelling fire policy owned by named insured.
Staging	PU_PLCY	DF_PSNL_LIAB_LMT	Dwelling Fire Personal Liability Limit	VARCHAR2(15)	This value represents the personal liability coverage limit provided by dwelling fire policy owned by insured.
Warehouse	PU_PLCY	DF_PSNL_LIAB_LMT	Dwelling Fire Personal Liability Limit	VARCHAR2(15)	This value represents the personal liability coverage limit provided by dwelling fire policy owned by insured.
Staging	PU_PLCY	HO_INSUR_CO_NM	Homeowners Insurance Company Name	VARCHAR2(170)	This value represents the insurance company name of the insured's homeowners policy.
Warehouse	PU_PLCY	HO_INSUR_CO_NM	Homeowners Insurance Company Name	VARCHAR2(170)	This value represents the insurance company name of the insured's homeowners policy.
Staging	PU_PLCY	HO_PLCY_EFF_DT	Homeowners Policy Effective Date	DATE	This date is when coverage begins for a homeowners policy.
Warehouse	PU_PLCY	HO_PLCY_EFF_DT	Homeowners Policy Effective Date	DATE	This date is when coverage begins for a homeowners policy.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PU_PLCY	HO_PLCY_EXPR_DT	Homeowners Policy Expiration Date	DATE	This calendar date represents when homeowners coverage policy term ends.
Warehouse	PU_PLCY	HO_PLCY_EXPR_DT	Homeowners Policy Expiration Date	DATE	This calendar date represents when homeowners coverage policy term ends.
Staging	PU_PLCY	HO_PLCY_NUM	Homeowners Policy Number	VARCHAR2(25)	This value represents a number or other identifier for a homeowners policy.
Warehouse	PU_PLCY	HO_PLCY_NUM	Homeowners Policy Number	VARCHAR2(25)	This value represents a number or other identifier for a homeowners policy.
Staging	PU_PLCY	HO_PSNL_LIAB_LMT	Homeowners Personal Liability Limit	VARCHAR2(15)	This value represents the personal liability limit included under an insured's homeowners insurance policy.
Warehouse	PU_PLCY	HO_PSNL_LIAB_LMT	Homeowners Personal Liability Limit	VARCHAR2(15)	This value represents the personal liability limit included under an insured's homeowners insurance policy.
Staging	PU_PLCY	PA_INSUR_CO_NM	Personal Auto Insurance Company Name	VARCHAR2(170)	This value represents the insurance company name that issued the insured's personal automobile policy.
Warehouse	PU_PLCY	PA_INSUR_CO_NM	Personal Auto Insurance Company Name	VARCHAR2(170)	This value represents the insurance company name that issued the insured's personal automobile policy.
Staging	PU_PLCY	PA_LIAB_FIRST_LMT	Personal Auto Liability First Limit	VARCHAR2(15)	This value represents the personal vehicle liability limit first limit.
Warehouse	PU_PLCY	PA_LIAB_FIRST_LMT	Personal Auto Liability First Limit	VARCHAR2(15)	This value represents the personal vehicle liability limit first limit.
Staging	PU_PLCY	PA_LIAB_SECOND_LMT	Personal Auto Liability Second Limit	VARCHAR2(15)	This value represents the personal vehicle liability limit second limit.
Warehouse	PU_PLCY	PA_LIAB_SECOND_LMT	Personal Auto Liability Second Limit	VARCHAR2(15)	This value represents the personal vehicle liability limit second limit.
Staging	PU_PLCY	PA_PLCY_EFF_DT	Personal Auto Policy Effective Date	DATE	This calendar date represents when insured's personal vehicle policy coverage began.
Warehouse	PU_PLCY	PA_PLCY_EFF_DT	Personal Auto Policy Effective Date	DATE	This calendar date represents when insured's personal vehicle policy coverage began.
Staging	PU_PLCY	PA_PLCY_EXPR_DT	Personal Auto Policy Expiration Date	DATE	This calendar date represents when insured's personal vehicle policy term ends.
Warehouse	PU_PLCY	PA_PLCY_EXPR_DT	Personal Auto Policy Expiration Date	DATE	This calendar date represents when insured's personal vehicle policy term ends.
Staging	PU_PLCY	PA_PLCY_NUM	Personal Auto Policy Number	VARCHAR2(25)	This value represents the personal vehicle policy number.
Warehouse	PU_PLCY	PA_PLCY_NUM	Personal Auto Policy Number	VARCHAR2(25)	This value represents the personal vehicle policy number.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PU_PLCY	PA_PROP_DMG_LMT	Personal Auto Property Damage Limit	VARCHAR2(15)	This value represents the personal vehicle property damage limit.
Warehouse	PU_PLCY	PA_PROP_DMG_LMT	Personal Auto Property Damage Limit	VARCHAR2(15)	This value represents the personal vehicle property damage limit.
Staging	PU_PLCY	PA_UM_FIRST_LMT	Personal Auto Uninsured Motorist First Limit	VARCHAR2(15)	This value represents the personal vehicle uninsured/underinsured motorist first limit.
Warehouse	PU_PLCY	PA_UM_FIRST_LMT	Personal Auto Uninsured Motorist First Limit	VARCHAR2(15)	This value represents the personal vehicle uninsured/underinsured motorist first limit.
Staging	PU_PLCY	PA_UM_SECOND_LMT	Personal Auto Uninsured Motorist Second Limit	VARCHAR2(15)	This value represents the personal vehicle uninsured/underinsured motorist second limit.
Warehouse	PU_PLCY	PA_UM_SECOND_LMT	Personal Auto Uninsured Motorist Second Limit	VARCHAR2(15)	This value represents the personal vehicle uninsured/underinsured motorist second limit.
Staging	PU_PLCY	PA_UM_THIRD_LMT	Personal Auto Uninsured Motorist Third Limit	VARCHAR2(15)	This value represents the personal vehicle uninsured/underinsured motorist third limit.
Warehouse	PU_PLCY	PA_UM_THIRD_LMT	Personal Auto Uninsured Motorist Third Limit	VARCHAR2(15)	This value represents the personal vehicle uninsured/underinsured motorist third limit.
Warehouse	PU_PLCY	PU_PLCY_ID	Personal Umbrella Policy Identifier	NUMBER (22, 0)	This system generated number identifies the personal umbrella policy instance.
Staging	PU_PLCY	PU_PLCY_NAT_KEY	Personal Umbrella Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the personal umbrella policy.
Warehouse	PU_PLCY	PU_PLCY_NAT_KEY	Personal Umbrella Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the personal umbrella policy.
Staging	PU_PLCY	PU_PLCY_UDF_CD_1	Personal Umbrella Policy User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_CD_1	Personal Umbrella Policy User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first personal umbrella policy user defined field.
Staging	PU_PLCY	PU_PLCY_UDF_CD_2	Personal Umbrella Policy User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_CD_2	Personal Umbrella Policy User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second personal umbrella policy user defined field.
Staging	PU_PLCY	PU_PLCY_UDF_CD_3	Personal Umbrella Policy User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_CD_3	Personal Umbrella Policy User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third personal umbrella policy user defined field.
Staging	PU_PLCY	PU_PLCY_UDF_CD_4	Personal Umbrella Policy User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_CD_4	Personal Umbrella Policy User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth personal umbrella policy user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PU_PLCY	PU_PLCY_UDF_CD_5	Personal Umbrella Policy User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_CD_5	Personal Umbrella Policy User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_DESC_1	Personal Umbrella Policy User Defined Field Description 1	VARCHAR2(60)	This value describes the first personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_DESC_2	Personal Umbrella Policy User Defined Field Description 2	VARCHAR2(60)	This value describes the second personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_DESC_3	Personal Umbrella Policy User Defined Field Description 3	VARCHAR2(60)	This value describes the third personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_DESC_4	Personal Umbrella Policy User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_DESC_5	Personal Umbrella Policy User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth personal umbrella policy user defined field.
Staging	PU_PLCY	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the personal umbrella policy with a specific transaction.
Datamart	PU_PLCY_DIM	PU_PLCY_DF_INSUR_CO_NM	Personal Umbrella Policy Dwelling Fire Insurance Company Name	VARCHAR2(170)	This value represents the insurance company name that issued insured's dwelling fire insurance policy.
Datamart	PU_PLCY_DIM	PU_PLCY_DF_PLCY_EFF_DT_ID	Personal Umbrella Policy Dwelling Fire Policy Effective Date Identifier	DATE	This value represents the personal umbrella dwelling fire policy effective date instance.
Datamart	PU_PLCY_DIM	PU_PLCY_DF_PLCY_EXPR_DT_ID	Personal Umbrella Policy Dwelling Fire Policy Expiration Date Identifier	DATE	This value represents the personal umbrella dwelling fire policy expiration date instance.
Datamart	PU_PLCY_DIM	PU_PLCY_DF_PLCY_NUM	Personal Umbrella Policy Dwelling Fire Policy Number	VARCHAR2(25)	This number or unique identifier identifes the personal umbrella policy dwelling fire policy.
Datamart	PU_PLCY_DIM	PU_PLCY_DF_PSNL_LIAB_LMT	Personal Umbrella Policy Dwelling Fire Personal Liability Limit	VARCHAR2(15)	This value represents the personal liability coverage limit included under an insured's dwelling fire insurance policy.
Datamart	PU_PLCY_DIM	PU_PLCY_HO_INSUR_CO_NM	Personal Umbrella Policy Homeowners Insurance Company Name	VARCHAR2(170)	This value represents the insurance company name for insured's homeowners insurance policy.
Datamart	PU_PLCY_DIM	PU_PLCY_HO_PLCY_EFF_DT_ID	Personal Umbrella Policy Homeowners Policy Effective Date Identifier	DATE	This calendar date represents the personal umbrella homeowners policy effective date instance.
Datamart	PU_PLCY_DIM	PU_PLCY_HO_PLCY_EXPR_DT_ID	Personal Umbrella Policy Homeowners Policy Expiration Date Identifier	DATE	This calendar date represents the personal umbrella homeowners policy expiration date instance.
Datamart	PU_PLCY_DIM	PU_PLCY_HO_PLCY_NUM	Personal Umbrella Policy Homeowners Policy Number	VARCHAR2(25)	This number or unique identifier identifes the personal umbrella policy homeowners policy.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PU_PLCY_DIM	PU_PLCY_HO_PSNL_LIAB_LMT	Personal Umbrella Policy Homeowners Personal Liability Limit	VARCHAR2(15)	This value represents the personal liability coverage limit included under an insured's homeowners insurance policy.
Datamart	PU_PLCY_DIM	PU_PLCY_ID	Personal Umbrella Policy Identifier	NUMBER (22, 0)	This system generated number identifies the personal umbrella policy instance.
Datamart	PU_PLCY_DIM	PU_PLCY_NAT_KEY	Personal Umbrella Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the personal umbrella policy.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_INSUR_CO_NM	Personal Umbrella Policy Personal Auto Insurance Company Name	VARCHAR2(170)	This value represents the insurance company name for insured's personal vehicle insurance policy.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_LIAB_FIRST_LMT	Personal Umbrella Policy Personal Auto Liability First Limit	VARCHAR2(15)	This value represents the personal vehicle liability limit coverage first limit.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_LIAB_SECOND_LMT	Personal Umbrella Policy Personal Auto Liability Second Limit	VARCHAR2(15)	This value represents the personal vehicle policy liability coverage second limit.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_PLCY_EFF_DT_ID	Personal Umbrella Policy Personal Auto Policy Effective Date Identifier	DATE	This calendar date represents the personal umbrella policy personal vehicle policy instance.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_PLCY_EXPR_DT_ID	Personal Umbrella Policy Personal Auto Policy Expiration Date Identifier	DATE	This calendar date represents when personal vehicle insurance policy term ends.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_PLCY_NUM	Personal Umbrella Policy Personal Auto Policy Number	VARCHAR2(25)	This value represents the number or other identifier that identifies the specific personal vehicle policy.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_PROP_DMG_LMT	Personal Umbrella Policy Personal Auto Property Damage Limit	VARCHAR2(15)	This value represents the personal vehicle policy property damage coverage limit.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_UM_FIRST_LMT	Personal Umbrella Policy Personal Auto Uninsured Motorist First Limit	VARCHAR2(15)	This value represents the personal vehicle policy uninsured/underinsured motorist coverage first limit.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_UM_SECOND_LMT	Personal Umbrella Policy Personal Auto Uninsured Motorist Second Limit	VARCHAR2(15)	This value represents the personal vehicle policy uninsured/underinsured motorist coverage second limit.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_UM_THIRD_LMT	Personal Umbrella Policy Personal Auto Uninsured Motorist Third Limit	VARCHAR2(15)	This value represents the personal vehicle policy uninsured/underinsured motorist coverage third limit.
Datamart	PU_PLCY_DIM	PU_PLCY_UDF_1	Personal Umbrella Policy User Defined Field 1	VARCHAR2(60)	This value describes the first personal umbrella policy user defined field.
Datamart	PU_PLCY_DIM	PU_PLCY_UDF_2	Personal Umbrella Policy User Defined Field 2	VARCHAR2(60)	This value describes the second personal umbrella policy user defined field.
Datamart	PU_PLCY_DIM	PU_PLCY_UDF_3	Personal Umbrella Policy User Defined Field 3	VARCHAR2(60)	This value describes the third personal umbrella policy user defined field.
Datamart	PU_PLCY_DIM	PU_PLCY_UDF_4	Personal Umbrella Policy User Defined Field 4	VARCHAR2(60)	This value describes the fourth personal umbrella policy user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PU_PLCY_DIM	PU_PLCY_UDF_5	Personal Umbrella Policy User Defined Field 5	VARCHAR2(60)	This value describes the fifth personal umbrella policy user defined field.
Warehouse	REINS_CNTRCT	BEGIN_DT	Begin Date	DATE	This calendar date represents when the reinsurance contract terms apply.
Staging	REINS_CNTRCT	CEDED_LOSS_RATIO	Ceded Loss Ratio	NUMBER (6,3)	This value represents the ratio of losses and loss adjustment expenses incurred to premiums earned for the portion of exposure that is transferred to a reinsurance company.
Warehouse	REINS_CNTRCT	CEDED_LOSS_RATIO	Ceded Loss Ratio	NUMBER (6, 3)	This value represents the ratio of losses and loss adjustment expenses incurred to premiums earned for the portion of exposure that is transferred to a reinsurance company.
Warehouse	REINS_CNTRCT	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the reinsurance contract is currently applicable.
Warehouse	REINS_CNTRCT	END_DT	End Date	DATE	This calendar date represents when the reinsurance contract terms no longer apply.
Staging	REINS_CNTRCT	FAC_COMM_PCT	Faculative Commission Percentage	NUMBER (6,3)	This number represents the percentage of premium the ceding company retains as a commission from the reinsurer.
Warehouse	REINS_CNTRCT	FAC_COMM_PCT	Faculative Commission Percentage	NUMBER (6, 3)	This number represents the percentage of premium the ceding company retains as a commission from the reinsurer.
Staging	REINS_CNTRCT	REINS_CNTRCT_BEGIN_DT	Reinsurance Contract Begin Date	DATE	This calendar date represents when reinsurance contract terms apply.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_BEGIN_DT	Reinsurance Contract Begin Date	DATE	This calendar date represents when reinsurance contract terms apply.
Staging	REINS_CNTRCT	REINS_CNTRCT_CATG_CD	Reinsurance Contract Category Code	VARCHAR2(25)	This system code identifies the reinsurance contract category.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_CATG_CD	Reinsurance Contract Category Code	VARCHAR2(25)	This system code identifies the reinsurance contract category.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_CATG_DESC	Reinsurance Contract Category Description	VARCHAR2(60)	This value describes the reinsurance contract category.
Staging	REINS_CNTRCT	REINS_CNTRCT_CERT_NUM	Reinsurance Contract Certificate Number	VARCHAR2(8)	This value represents the unique identifier assigned to the reinsurance contract certificate.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_CERT_NUM	Reinsurance Contract Certificate Number	VARCHAR2(8)	This value represents the unique number or other identifier assigned to the reinsurance contract certificate.
Staging	REINS_CNTRCT	REINS_CNTRCT_CESSION_NUM	Reinsurance Contract Cession Number	VARCHAR2(10)	This value represents the unique number or other identifier of the reinsurance contract cession.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	REINS_CNTRCT	REINS_CNTRCT_CESSION_NUM	Reinsurance Contract Cession Number	VARCHAR2(10)	This value represents a number or other identifier of the reinsurance contract cession.
Staging	REINS_CNTRCT	REINS_CNTRCT_END_DT	Reinsurance Contract Ending Date	DATE	This date represents the calendar date reinsurance contract ends.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_END_DT	Reinsurance Contract Ending Date	DATE	This date represents the calendar date reinsurance contract ends.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_ID	Reinsurance Contract Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance contract instance.
Staging	REINS_CNTRCT	REINS_CNTRCT_LAYER_CD	Reinsurance Contract Layer Code	VARCHAR2(25)	This system code identifies the reinsurance contract layer.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_LAYER_CD	Reinsurance Contract Layer Code	VARCHAR2(25)	This system code identifies the reinsurance contract layer.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_LAYER_DESC	Reinsurance Contract Layer Description	VARCHAR2(60)	This value describes the reinsurance contract layer.
Staging	REINS_CNTRCT	REINS_CNTRCT_NAT_KEY	Reinsurance Contract Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the reinsurance contract.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_NAT_KEY	Reinsurance Contract Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the reinsurance contract.
Staging	REINS_CNTRCT	REINS_CNTRCT_TREATY_NUM	Reinsurance Contract Treaty Number	VARCHAR2(8)	This value represents the number or other identifier assigned to the reinsurance contract treaty.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_TREATY_NUM	Reinsurance Contract Treaty Number	VARCHAR2(8)	This value represents the number or other identifier assigned to the reinsurance contract treaty.
Staging	REINS_CNTRCT	REINS_CNTRCT_TYP_CD	Reinsurance Contract Type Code	VARCHAR2(25)	This system code identifies the reinsurance contract type.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_TYP_CD	Reinsurance Contract Type Code	VARCHAR2(25)	This system code identifies the reinsurance contract type.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_TYP_DESC	Reinsurance Contract Type Description	VARCHAR2(60)	This value describes the reinsurance contract type.
Staging	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_1	Reinsurance Contract User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first reinsurance contract user defined field.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_1	Reinsurance Contract User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first reinsurance contract user defined field.
Staging	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_2	Reinsurance Contract User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second reinsurance contract user defined field.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_2	Reinsurance Contract User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second reinsurance contract user defined field.
Staging	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_3	Reinsurance Contract User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third reinsurance contract user defined field.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_3	Reinsurance Contract User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third reinsurance contract user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_4	Reinsurance Contract User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth reinsurance contract user defined field.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_4	Reinsurance Contract User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth reinsurance contract user defined field.
Staging	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_5	Reinsurance Contract User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth reinsurance contract user defined field.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_5	Reinsurance Contract User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth reinsurance contract user defined field.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_DESC_1	Reinsurance Contract User Defined Field Description 1	VARCHAR2(60)	This value describes the first reinsurance contract user defined field.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_DESC_2	Reinsurance Contract User Defined Field Description 2	VARCHAR2(60)	This value describes the second reinsurance contract user defined field.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_DESC_3	Reinsurance Contract User Defined Field Description 3	VARCHAR2(60)	This value describes the third reinsurance contract user defined field.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_DESC_4	Reinsurance Contract User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth reinsurance contract user defined field.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_DESC_5	Reinsurance Contract User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth reinsurance contract user defined field.
Staging	REINS_CNTRCT	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the reinsurance contract with a specific transaction.
Datamart	REINS_CNTRCT_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the reinsurance contract terms apply.
Datamart	REINS_CNTRCT_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the reinsurance contract is currently applicable.
Datamart	REINS_CNTRCT_DIM	END_DT	End Date	DATE	This calendar date represents when the reinsurance contract terms no longer apply.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_BEGIN_DT_ID	Reinsurance Contract Begin Date Identifier	DATE	This calendar date represents the reinsurance contract begin date instance.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_CATG	Reinsurance Contract Category	VARCHAR2(60)	This value represents the category of the reinsurance contract.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_CEDED_LOSS_RATIO	Reinsurance Contract Ceded Loss Ratio	NUMBER (6, 3)	This number represents the ratio of losses and loss adjustment expenses incurred to premiums earned in the portion of exposure that is transferred to a reinsurance company.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_CERT_NUM	Reinsurance Contract Certificate Number	VARCHAR2(8)	This value represents the unique number or other identifier assigned to the reinsurance contract certificate.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_CESSION_NUM	Reinsurance Contract Cession Number	VARCHAR2(10)	This value represents the number or other identifier of the reinsurance contract cession.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_END_DT_ID	Reinsurance Contract Ending Date Identifier	DATE	This calendar date represents when identifies when a reinsurance contract ends.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_FAC_COMM_PCT	Reinsurance Contract Faculative Commission Percent	NUMBER (6, 3)	This number represents the percentage commission paid to reinsurer.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_ID	Reinsurance Contract Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance contract instance.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_LAYER	Reinsurance Contract Layer	VARCHAR2(60)	This value represents the reinsurance contract layer describes the amount of reinsurance provided in the reinsurance contract.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_NAT_KEY	Reinsurance Contract Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the reinsurance contract.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_TREATY_NUM	Reinsurance Contract Treaty Number	VARCHAR2(8)	This value represents the unique number or other identifier assigned to a reinsurance contract treaty.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_TYP	Reinsurance Contract Type	VARCHAR2(60)	This value represents the attributes of the reinsurance contract.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_UDF_1	Reinsurance Contract User Defined Field 1	VARCHAR2(60)	This value describes the first reinsurance contract user defined field.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_UDF_2	Reinsurance Contract User Defined Field 2	VARCHAR2(60)	This value describes the second reinsurance contract user defined field.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_UDF_3	Reinsurance Contract User Defined Field 3	VARCHAR2(60)	This value describes the third reinsurance contract user defined field.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_UDF_4	Reinsurance Contract User Defined Field 4	VARCHAR2(60)	This value describes the fourth reinsurance contract user defined field.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_UDF_5	Reinsurance Contract User Defined Field 5	VARCHAR2(60)	This value describes the fifth reinsurance contract user defined field.
Warehouse	REINS_CO	BEGIN_DT	Begin Date	DATE	This calendar date represents when the reinsurance company applies.
Warehouse	REINS_CO	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the reinsurance company is currently applicable.
Warehouse	REINS_CO	END_DT	End Date	DATE	This calendar date represents when the reinsurance company is no longer valid.
Warehouse	REINS_CO	ORG_ID	Organization Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance company organization instance.
Warehouse	REINS_CO	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	REINS_CO	REINS_CO_ID	Reinsurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance company instance.
Staging	REINS_CO	REINS_CO_NUM	Reinsurance Company Number	VARCHAR2(4)	This value represents the number or other identifier assigned to the reinsurance company.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	REINS_CO	REINS_CO_NUM	Reinsurance Company Number	VARCHAR2(4)	This value represents the number or other identifier assigned to the reinsurance company.
Staging	REINS_CO	REINS_CO_TYP_CD	Reinsurance Company Type Code	VARCHAR2(25)	This system code identifies reinsurance company type.
Warehouse	REINS_CO	REINS_CO_TYP_CD	Reinsurance Company Type Code	VARCHAR2(25)	This system code identifies reinsurance company type.
Warehouse	REINS_CO	REINS_CO_TYP_DESC	Reinsurance Company Type Description	VARCHAR2(60)	This value describes the reinsurance company type.
Staging	REINS_CO	REINS_CO_UDF_CD_1	Reinsurance Company User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first reinsurance company user defined field.
Warehouse	REINS_CO	REINS_CO_UDF_CD_1	Reinsurance Company User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first reinsurance company user defined field.
Staging	REINS_CO	REINS_CO_UDF_CD_2	Reinsurance Company User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second reinsurance company user defined field.
Warehouse	REINS_CO	REINS_CO_UDF_CD_2	Reinsurance Company User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second reinsurance company user defined field.
Staging	REINS_CO	REINS_CO_UDF_CD_3	Reinsurance Company User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third reinsurance company user defined field.
Warehouse	REINS_CO	REINS_CO_UDF_CD_3	Reinsurance Company User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third reinsurance company user defined field.
Staging	REINS_CO	REINS_CO_UDF_CD_4	Reinsurance Company User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth reinsurance company user defined field.
Warehouse	REINS_CO	REINS_CO_UDF_CD_4	Reinsurance Company User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth reinsurance company user defined field.
Staging	REINS_CO	REINS_CO_UDF_CD_5	Reinsurance Company User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth reinsurance company user defined field.
Warehouse	REINS_CO	REINS_CO_UDF_CD_5	Reinsurance Company User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth reinsurance company user defined field.
Warehouse	REINS_CO	REINS_CO_UDF_DESC_1	Reinsurance Company User Defined Field Description 1	VARCHAR2(60)	This value describes the first reinsurance company user defined field.
Warehouse	REINS_CO	REINS_CO_UDF_DESC_2	Reinsurance Company User Defined Field Description 2	VARCHAR2(60)	This value describes the second reinsurance company user defined field.
Warehouse	REINS_CO	REINS_CO_UDF_DESC_3	Reinsurance Company User Defined Field Description 3	VARCHAR2(60)	This value describes the third reinsurance company user defined field.
Warehouse	REINS_CO	REINS_CO_UDF_DESC_4	Reinsurance Company User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth reinsurance company user defined field.
Warehouse	REINS_CO	REINS_CO_UDF_DESC_5	Reinsurance Company User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth reinsurance company user defined field.
Staging	REINS_CO	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the reinsurance company with a specific transaction.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	REINS_CO_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the reinsurance company applies.
Datamart	REINS_CO_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the reinsurance company is currently applicable.
Datamart	REINS_CO_DIM	END_DT	End Date	DATE	This calendar date represents when the reinsurance company is no longer valid.
Datamart	REINS_CO_DIM	REINS_CO_BUS_START_DT_ID	Reinsurance Company Business Start Date Identifier	DATE	This calendar date represents when the reinsurance company began business operations.
Datamart	REINS_CO_DIM	REINS_CO_CNTCT_DESC	Reinsurance Company Contract Description	VARCHAR2(60)	This value describes the reinsurance company contract.
Datamart	REINS_CO_DIM	REINS_CO_CNTCT_TYP	Reinsurance Company Contact Type	VARCHAR2(60)	This value represents the contact method for reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_CNTCT_UDF_1	Reinsurance Company Contact User Defined Field 1	VARCHAR2(60)	This value describes the first reinsurance company contact user defined field.
Datamart	REINS_CO_DIM	REINS_CO_CNTCT_UDF_2	Reinsurance Company Contact User Defined Field 2	VARCHAR2(60)	This value describes the second reinsurance company contact user defined field.
Datamart	REINS_CO_DIM	REINS_CO_CNTCT_UDF_3	Reinsurance Company Contact User Defined Field 3	VARCHAR2(60)	This value describes the third reinsurance company contact user defined field.
Datamart	REINS_CO_DIM	REINS_CO_CNTCT_UDF_4	Reinsurance Company Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth reinsurance company contact user defined field.
Datamart	REINS_CO_DIM	REINS_CO_CNTCT_UDF_5	Reinsurance Company Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth reinsurance company contact user defined field.
Datamart	REINS_CO_DIM	REINS_CO_CNTY	Reinsurance Company County	VARCHAR2(60)	This value identifies the county where reinsurance company is located.
Datamart	REINS_CO_DIM	REINS_CO_CTRY	Reinsurance Company Country	VARCHAR2(60)	This value identifies the country where reinsurance company is located.
Datamart	REINS_CO_DIM	REINS_CO_CTY	Reinsurance Company City	VARCHAR2(32)	This value identifies the city where reinsurance company is located.
Datamart	REINS_CO_DIM	REINS_CO_DBA	Reinsurance Company Doing Business As	VARCHAR2(170)	This value represents operational name of a reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_DSTRCT	Reinsurance Company District	VARCHAR2(60)	This value represents the district where reinsurance company is located.
Datamart	REINS_CO_DIM	REINS_CO_GEOG_BNDRY_UDF_1	Reinsurance Company Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first reinsurance company geographic boundary user defined field.
Datamart	REINS_CO_DIM	REINS_CO_GEOG_BNDRY_UDF_2	Reinsurance Company Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second reinsurance company geographic boundary user defined field.
Datamart	REINS_CO_DIM	REINS_CO_GEOG_BNDRY_UDF_3	Reinsurance Company Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third reinsurance company geographic boundary user defined field.
Datamart	REINS_CO_DIM	REINS_CO_GEOG_BNDRY_UDF_4	Reinsurance Company Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth reinsurance company geographic boundary user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	REINS_CO_DIM	REINS_CO_GEOG_BNDRY_UDF_5	Reinsurance Company Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth reinsurance company geographic boundary user defined field.
Datamart	REINS_CO_DIM	REINS_CO_GOVT_ID_NUM	Reinsurance Company Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the reinsurance company. For example, in the USA: SSN or FEIN.
Datamart	REINS_CO_DIM	REINS_CO_ID	Reinsurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance company instance.
Datamart	REINS_CO_DIM	REINS_CO_LATITUDE	Reinsurance Company Latitude	VARCHAR2(11)	This value represents the latitude location of the reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_LONGITUDE	Reinsurance Company Longitude	VARCHAR2(11)	This value represents the longitude location of the reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_NAICS_CD	Reinsurance Company North American Industry Classification System Code	VARCHAR2(60)	This value represents the North America Industry Class (NAICS) code assigned to the reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_NAT_KEY	Reinsurance Company Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_NM	Reinsurance Company Name	VARCHAR2(170)	This value represents the name of the reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_NOB	Reinsurance Company Nature of Business	VARCHAR2(60)	This value represents the type or category of the business activities done by the reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_NUM	Reinsurance Company Number	VARCHAR2(4)	This value represents the number or other identifier assigned to the reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_NUM_EMP	Reinsurance Company Number of Employees	NUMBER (22, 0)	This number represents the count of people employed by reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_ORG_UDF_1	Reinsurance Company Organization User Defined Field 1	VARCHAR2(60)	This value describes the first reinsurance company organization user defined field.
Datamart	REINS_CO_DIM	REINS_CO_ORG_UDF_2	Reinsurance Company Organization User Defined Field 2	VARCHAR2(60)	This value describes the second reinsurance company organization user defined field.
Datamart	REINS_CO_DIM	REINS_CO_ORG_UDF_3	Reinsurance Company Organization User Defined Field 3	VARCHAR2(60)	This value describes the third reinsurance company organization user defined field.
Datamart	REINS_CO_DIM	REINS_CO_ORG_UDF_4	Reinsurance Company Organization User Defined Field 4	VARCHAR2(60)	This value describes the fourth reinsurance company organization user defined field.
Datamart	REINS_CO_DIM	REINS_CO_ORG_UDF_5	Reinsurance Company Organization User Defined Field 5	VARCHAR2(60)	This value describes the fifth reinsurance company organization user defined field.
Datamart	REINS_CO_DIM	REINS_CO_PARTY_UDF_1	Reinsurance Company Party User Defined Field 1	VARCHAR2(60)	This value describes the first reinsurance company party user defined field.
Datamart	REINS_CO_DIM	REINS_CO_PARTY_UDF_2	Reinsurance Company Party User Defined Field 2	VARCHAR2(60)	This value describes the second reinsurance company party user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	REINS_CO_DIM	REINS_CO_PARTY_UDF_3	Reinsurance Company Party User Defined Field 3	VARCHAR2(60)	This value describes the third reinsurance company party user defined field.
Datamart	REINS_CO_DIM	REINS_CO_PARTY_UDF_4	Reinsurance Company Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth reinsurance company party user defined field.
Datamart	REINS_CO_DIM	REINS_CO_PARTY_UDF_5	Reinsurance Company Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth reinsurance company party user defined field.
Datamart	REINS_CO_DIM	REINS_CO_PSTL_CD	Reinsurance Company Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	REINS_CO_DIM	REINS_CO_PSTL_CD_PRFX	Reinsurance Company Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	REINS_CO_DIM	REINS_CO_PSTL_SUB_CD	Reinsurance Company Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	REINS_CO_DIM	REINS_CO_REGION	Reinsurance Company Region	VARCHAR2(60)	This value represents the geographic region of the reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_SIC_CD	Reinsurance Company Standard Industrial Classification Code	VARCHAR2(60)	This system code is the SIC code assigned to the reinsurance company. The Standard Industrial Classification (SIC) code is an industry code that identifies the classification of business activity.
Datamart	REINS_CO_DIM	REINS_CO_STATE	Reinsurance Company State	VARCHAR2(60)	This value identifies the state where the reinsurance company is located.
Datamart	REINS_CO_DIM	REINS_CO_TAX_LOC_ID	Reinsurance Company Tax Location Identifier	VARCHAR2(6)	This value represents the reinsurance company tax location instance.
Datamart	REINS_CO_DIM	REINS_CO_TERR	Reinsurance Company Territory	VARCHAR2(60)	This value represents the territory where the reinsurance company is located.
Datamart	REINS_CO_DIM	REINS_CO_TYP	Reinsurance Company Type	VARCHAR2(60)	This value represents the classification of the activities of a reinsurance company. Examples include proportional and non-proportional.
Datamart	REINS_CO_DIM	REINS_CO_UDF_1	Reinsurance Company User Defined Field 1	VARCHAR2(60)	This value describes the first reinsurance company user defined field.
Datamart	REINS_CO_DIM	REINS_CO_UDF_2	Reinsurance Company User Defined Field 2	VARCHAR2(60)	This value describes the second reinsurance company user defined field.
Datamart	REINS_CO_DIM	REINS_CO_UDF_3	Reinsurance Company User Defined Field 3	VARCHAR2(60)	This value describes the third reinsurance company user defined field.
Datamart	REINS_CO_DIM	REINS_CO_UDF_4	Reinsurance Company User Defined Field 4	VARCHAR2(60)	This value describes the fourth reinsurance company user defined field.
Datamart	REINS_CO_DIM	REINS_CO_UDF_5	Reinsurance Company User Defined Field 5	VARCHAR2(60)	This value describes the fifth reinsurance company user defined field.
Warehouse	SUPPLIER	BEGIN_DT	Begin Date	DATE	This calendar date represents when the supplier applies.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	SUPPLIER	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the supplier is currently applicable.
Warehouse	SUPPLIER	END_DT	End Date	DATE	This calendar date represents when the supplier is no longer valid.
Warehouse	SUPPLIER	ORG_ID	Organization Identifier	NUMBER (22, 0)	This system generated number identifies the supplier organization instance.
Warehouse	SUPPLIER	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	SUPPLIER	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person instance.
Staging	SUPPLIER	PREF_SUPPLIER_CD	Preferred Supplier Code	VARCHAR2(25)	This system code identifies if a supplier is a preferred supplier.
Warehouse	SUPPLIER	PREF_SUPPLIER_CD	Preferred Supplier Code	VARCHAR2(25)	This system code identifies if a supplier is a preferred supplier.
Warehouse	SUPPLIER	PREF_SUPPLIER_DESC	Preferred Supplier Description	VARCHAR2(60)	This value describes the preferred supplier attributes.
Staging	SUPPLIER	PREF_SUPPLIER_TYP_CD	Preferred Supplier Type Code	VARCHAR2(25)	This system code identifies preferred supplier type.
Warehouse	SUPPLIER	PREF_SUPPLIER_TYP_CD	Preferred Supplier Type Code	VARCHAR2(25)	This system code identifies preferred supplier type.
Warehouse	SUPPLIER	PREF_SUPPLIER_TYP_DESC	Preferred Supplier Type Description	VARCHAR2(60)	This value represents the description of preferred supplier type attributes.
Staging	SUPPLIER	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the supplier with a specific transaction.
Staging	SUPPLIER	SUPPLIER_CATG_CD	Supplier Category Code	VARCHAR2(25)	This system code represents supplier category.
Warehouse	SUPPLIER	SUPPLIER_CATG_CD	Supplier Category Code	VARCHAR2(25)	This system code represents supplier category.
Warehouse	SUPPLIER	SUPPLIER_CATG_DESC	Supplier Category Description	VARCHAR2(60)	This value describes the supplier category.
Warehouse	SUPPLIER	SUPPLIER_ID	Supplier Identifier	NUMBER (22, 0)	This system generated number identifies the supplier instance.
Staging	SUPPLIER	SUPPLIER_TYP_CD	Supplier Type Code	VARCHAR2(25)	This system code identifies supplier type.
Warehouse	SUPPLIER	SUPPLIER_TYP_CD	Supplier Type Code	VARCHAR2(25)	This system code identifies supplier type.
Warehouse	SUPPLIER	SUPPLIER_TYP_DESC	Supplier Type Description	VARCHAR2(60)	This value describes the supplier type.
Staging	SUPPLIER	SUPPLIER_UDF_CD_1	Supplier User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_CD_1	Supplier User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first supplier user defined field.
Staging	SUPPLIER	SUPPLIER_UDF_CD_2	Supplier User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_CD_2	Supplier User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second supplier user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	SUPPLIER	SUPPLIER_UDF_CD_3	Supplier User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_CD_3	Supplier User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third supplier user defined field.
Staging	SUPPLIER	SUPPLIER_UDF_CD_4	Supplier User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_CD_4	Supplier User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth supplier user defined field.
Staging	SUPPLIER	SUPPLIER_UDF_CD_5	Supplier User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_CD_5	Supplier User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_DESC_1	Supplier User Defined Field Description 1	VARCHAR2(60)	This value describes the first supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_DESC_2	Supplier User Defined Field Description 2	VARCHAR2(60)	This value describes the second supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_DESC_3	Supplier User Defined Field Description 3	VARCHAR2(60)	This value describes the third supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_DESC_4	Supplier User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_DESC_5	Supplier User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth supplier user defined field.
Datamart	SUPPLIER_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the supplier applies.
Datamart	SUPPLIER_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the supplier is currently applicable.
Datamart	SUPPLIER_DIM	END_DT	End Date	DATE	This calendar date represents when the supplier is no longer valid.
Datamart	SUPPLIER_DIM	PREF_SUPPLIER_CD	Preferred Supplier Code	VARCHAR2(60)	This system code identifies if a supplier is a preferred supplier.
Datamart	SUPPLIER_DIM	PREF_SUPPLIER_TYP	Preferred Supplier Type	VARCHAR2(60)	This value represents the classification assigned to preferred suppliers based on company-defined attributes.
Datamart	SUPPLIER_DIM	SUPPLIER_BIRTH_DT_ID	Supplier Birth Date Identifier	DATE	This calendar date represents the supplier's date of birth.
Datamart	SUPPLIER_DIM	SUPPLIER_BUS_START_DT_ID	Supplier Business Start Date Identifier	DATE	This calendar date represents when the supplier began business operations.
Datamart	SUPPLIER_DIM	SUPPLIER_CATG	Supplier Category	VARCHAR2(60)	This value represents the category of supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_CNTCT_DESC	Supplier Category Description	VARCHAR2(60)	This value describes the supplier category.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	SUPPLIER_DIM	SUPPLIER_CNTCT_TYP	Supplier Contact Type	VARCHAR2(60)	This value represents the contact method for supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_CNTCT_UDF_1	Supplier Contact User Defined Field 1	VARCHAR2(60)	This value describes the first supplier contact user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_CNTCT_UDF_2	Supplier Contact User Defined Field 2	VARCHAR2(60)	This value describes the second supplier contact user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_CNTCT_UDF_3	Supplier Contact User Defined Field 3	VARCHAR2(60)	This value describes the third supplier contact user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_CNTCT_UDF_4	Supplier Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth supplier contact user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_CNTCT_UDF_5	Supplier Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth supplier contact user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_CNTY	Supplier County	VARCHAR2(60)	This value identifies the county where supplier is located.
Datamart	SUPPLIER_DIM	SUPPLIER_CTRY	Supplier Country	VARCHAR2(60)	This value identifies the country where supplier is located.
Datamart	SUPPLIER_DIM	SUPPLIER_CTY	Supplier City	VARCHAR2(32)	This value identifies the city where supplier is located.
Datamart	SUPPLIER_DIM	SUPPLIER_DBA	Supplier Doing Business As	VARCHAR2(170)	This value represents the type or category of the business activities done by the reinsurance company.
Datamart	SUPPLIER_DIM	SUPPLIER_DSTRCT	Supplier District	VARCHAR2(60)	This value represents the district where supplier is located.
Datamart	SUPPLIER_DIM	SUPPLIER_GENDER	Supplier Gender	VARCHAR2(60)	This value represents the gender (male or female) of the supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_GEOG_BNDRY_UDF_1	Supplier Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first supplier geographic boundary user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_GEOG_BNDRY_UDF_2	Supplier Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second supplier geographic boundary user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_GEOG_BNDRY_UDF_3	Supplier Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third supplier geographic boundary user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_GEOG_BNDRY_UDF_4	Supplier Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth supplier geographic boundary user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_GEOG_BNDRY_UDF_5	Supplier Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth supplier geographic boundary user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_GOVT_ID_NUM	Supplier Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the supplier. For example, in the USA: SSN or FEIN.
Datamart	SUPPLIER_DIM	SUPPLIER_ID	Supplier Identifier	NUMBER (22, 0)	This system generated number identifies the supplier instance.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	SUPPLIER_DIM	SUPPLIER_LATITUDE	Supplier Latitude	VARCHAR2(11)	This value represents the latitude location of the supplier location.
Datamart	SUPPLIER_DIM	SUPPLIER_LONGITUDE	Supplier Longitude	VARCHAR2(11)	This value represents the longitude location of the supplier location.
Datamart	SUPPLIER_DIM	SUPPLIER_MARITAL_STATUS	Supplier Marital Status	VARCHAR2(60)	This value represents the present marital condition (single, married, divorced, widowed) of the supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_NAICS_CD	Supplier North American Industry Classification System Code	VARCHAR2(60)	This value represents the North America Industry Class (NAICS) code assigned to supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_NAT_KEY	Supplier Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_NM	Supplier Name	VARCHAR2(170)	This value represents the name of supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_NOB	Supplier Nature of Business	VARCHAR2(60)	This value represents the type or category of the business activities done by the supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_NUM_EMP	Supplier Number of Employees	NUMBER (22, 0)	This number represents the count of people employed by supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_ORG_UDF_1	Supplier Organization User Defined Field 1	VARCHAR2(60)	This value describes the first supplier organization user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_ORG_UDF_2	Supplier Organization User Defined Field 2	VARCHAR2(60)	This value describes the second supplier organization user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_ORG_UDF_3	Supplier Organization User Defined Field 3	VARCHAR2(60)	This value describes the third supplier organization user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_ORG_UDF_4	Supplier Organization User Defined Field 4	VARCHAR2(60)	This value describes the fourth supplier organization user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_ORG_UDF_5	Supplier Organization User Defined Field 5	VARCHAR2(60)	This value describes the fifth supplier organization user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PARTY_UDF_1	Supplier Party User Defined Field 1	VARCHAR2(60)	This value describes the first supplier party user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PARTY_UDF_2	Supplier Party User Defined Field 2	VARCHAR2(60)	This value describes the second supplier party user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PARTY_UDF_3	Supplier Party User Defined Field 3	VARCHAR2(60)	This value describes the third supplier party user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PARTY_UDF_4	Supplier Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth supplier party user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PARTY_UDF_5	Supplier Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth supplier party user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PERS_UDF_1	Supplier Person User Defined Field 1	VARCHAR2(60)	This value describes the first supplier person user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PERS_UDF_2	Supplier Person User Defined Field 2	VARCHAR2(60)	This value describes the second supplier person user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	SUPPLIER_DIM	SUPPLIER_PERS_UDF_3	Supplier Person User Defined Field 3	VARCHAR2(60)	This value describes the third supplier person user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PERS_UDF_4	Supplier Person User Defined Field 4	VARCHAR2(60)	This value describes the fourth supplier person user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PERS_UDF_5	Supplier Person User Defined Field 5	VARCHAR2(60)	This value describes the fifth supplier person user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PRES_EMPLMT_START_YR	Supplier Present Employment Start Year	CHAR(4)	This value represents the calendar year that the supplier began working for their current employer.
Datamart	SUPPLIER_DIM	SUPPLIER_PSTL_CD	Supplier Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	SUPPLIER_DIM	SUPPLIER_PSTL_CD_PRFX	Supplier Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	SUPPLIER_DIM	SUPPLIER_PSTL_SUB_CD	Supplier Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	SUPPLIER_DIM	SUPPLIER_REGION	Supplier Region	VARCHAR2(60)	This value represents the geographic region where supplier is located.
Datamart	SUPPLIER_DIM	SUPPLIER_SIC_CD	Supplier Standard Industrial Classification Code	VARCHAR2(60)	This system code is the SIC code assigned to the supplier. The Standard Industrial Classification (SIC) code is an industry code that identifies the classification of business activity.
Datamart	SUPPLIER_DIM	SUPPLIER_STATE	Supplier State	VARCHAR2(60)	This value identifies the state where supplier is located.
Datamart	SUPPLIER_DIM	SUPPLIER_TAX_LOC_ID	Supplier Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier in the supplier's location.
Datamart	SUPPLIER_DIM	SUPPLIER_TERR	Supplier Territory	VARCHAR2(60)	This value represents the territory where supplier is located.
Datamart	SUPPLIER_DIM	SUPPLIER_TYP	Supplier Type	VARCHAR2(60)	This value represents the classification that describes supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_UDF_1	Supplier User Defined Field 1	VARCHAR2(60)	This value describes the first supplier user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_UDF_2	Supplier User Defined Field 2	VARCHAR2(60)	This value describes the second supplier user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_UDF_3	Supplier User Defined Field 3	VARCHAR2(60)	This value describes the third supplier user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_UDF_4	Supplier User Defined Field 4	VARCHAR2(60)	This value describes the fourth supplier user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_UDF_5	Supplier User Defined Field 5	VARCHAR2(60)	This value describes the fifth supplier user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	TIME_DIM	AM_PM_CD	Indication of the time of day - AM: ante meridiem (before midday/ noon), PM: post meridiem (after midday/noon)	VARCHAR2(2)	This value represents the code indicates whether time of day is before or after midday.
Datamart	TIME_DIM	HR_12_LONG	Hour 12 Long	VARCHAR2(8)	This value represents the ong name for Hour 12.
Datamart	TIME_DIM	HR_12_NUM	Hour 12 Number	NUMBER (22, 0)	This number identifies Hour 12.
Datamart	TIME_DIM	HR_12_SHORT	Hour 12 Short	VARCHAR2(5)	This value represents the abbreviated name for Hour 12.
Datamart	TIME_DIM	HR_24_LONG	Hour 24 Long	VARCHAR2(5)	This value represents the long name for Hour 24.
Datamart	TIME_DIM	HR_24_NUM	Hour 24 Number	NUMBER (22, 0)	This number identifies Hour 24.
Datamart	TIME_DIM	TIME_ID	Time Identifier	NUMBER (22, 0)	This number identifies the time.
Warehouse	UW	BEGIN_DT	Begin Date	DATE	This calendar date represents when the underwriter applies.
Warehouse	UW	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the underwriter is currently applicable.
Warehouse	UW	END_DT	End Date	DATE	This calendar date represents when the underwriter is no longer valid.
Warehouse	UW	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	UW	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person.
Staging	UW	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the underwriter with a specific transaction.
Warehouse	UW	UW_ID	Underwriter Identifier	NUMBER (22, 0)	This system generated number identifies the underwriter instance.
Staging	UW	UW_NUM	Underwriter Number	VARCHAR2(25)	This value represents the number or other identifier that identifies the underwriter.
Warehouse	UW	UW_NUM	Underwriter Number	VARCHAR2(25)	This value represents the number or other identifier that identifies the underwriter.
Staging	UW	UW_RLAT_CD	Underwriter Relationship Code	VARCHAR2(25)	This system code identifies the underwriter relationship.
Staging	UW	UW_TYP_CD	Underwriter Type Code	VARCHAR2(25)	This system code identifies the underwriter type.
Warehouse	UW	UW_TYP_CD	Underwriter Type Code	VARCHAR2(25)	This system code identifies the underwriter type.
Warehouse	UW	UW_TYP_DESC	Underwriter Type Description	VARCHAR2(60)	This value describes the underwriter type.
Staging	UW	UW_UDF_CD_1	Underwriter User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first underwriter user defined field.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	UW	UW_UDF_CD_1	Underwriter User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first underwriter user defined field.
Staging	UW	UW_UDF_CD_2	Underwriter User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second underwriter user defined field.
Warehouse	UW	UW_UDF_CD_2	Underwriter User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second underwriter user defined field.
Staging	UW	UW_UDF_CD_3	Underwriter User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third underwriter user defined field.
Warehouse	UW	UW_UDF_CD_3	Underwriter User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third underwriter user defined field.
Staging	UW	UW_UDF_CD_4	Underwriter User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth underwriter user defined field.
Warehouse	UW	UW_UDF_CD_4	Underwriter User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth underwriter user defined field.
Staging	UW	UW_UDF_CD_5	Underwriter User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth underwriter user defined field.
Warehouse	UW	UW_UDF_CD_5	Underwriter User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth underwriter user defined field.
Warehouse	UW	UW_UDF_DESC_1	Underwriter User Defined Field Description 1	VARCHAR2(60)	This value describes the first underwriter user defined field.
Warehouse	UW	UW_UDF_DESC_2	Underwriter User Defined Field Description 2	VARCHAR2(60)	This value describes the second underwriter user defined field.
Warehouse	UW	UW_UDF_DESC_3	Underwriter User Defined Field Description 3	VARCHAR2(60)	This value describes the third underwriter user defined field.
Warehouse	UW	UW_UDF_DESC_4	Underwriter User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth underwriter user defined field.
Warehouse	UW	UW_UDF_DESC_5	Underwriter User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth underwriter user defined field.
Datamart	UW_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the underwriter applies.
Datamart	UW_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the underwriter is currently applicable.
Datamart	UW_DIM	END_DT	End Date	DATE	This calendar date represents when the underwriter is no longer valid.
Datamart	UW_DIM	UW_BIRTH_DT_ID	Underwriter Birth Date Identifier	DATE	This calendar date represents the underwriter's date of birth.
Datamart	UW_DIM	UW_CNTCT_DESC	Underwriter Contact Description	VARCHAR2(60)	This value describes the contact method for underwriter.
Datamart	UW_DIM	UW_CNTCT_TYP	Underwriter Contact Type	VARCHAR2(60)	This value represents the contact method for the underwriter.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	UW_DIM	UW_CNTCT_UDF_1	Underwriter Contact User Defined Field 1	VARCHAR2(60)	This value describes the first underwriter contact user defined field.
Datamart	UW_DIM	UW_CNTCT_UDF_2	Underwriter Contact User Defined Field 2	VARCHAR2(60)	This value describes the second underwriter contact user defined field.
Datamart	UW_DIM	UW_CNTCT_UDF_3	Underwriter Contact User Defined Field 3	VARCHAR2(60)	This value describes the third underwriter contact user defined field.
Datamart	UW_DIM	UW_CNTCT_UDF_4	Underwriter Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth underwriter contact user defined field.
Datamart	UW_DIM	UW_CNTCT_UDF_5	Underwriter Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth underwriter contact user defined field.
Datamart	UW_DIM	UW_CNTY	Underwriter County	VARCHAR2(60)	This value identifies the county of the underwriter's location.
Datamart	UW_DIM	UW_CTRY	Underwriter Country	VARCHAR2(60)	This value identifies the country of the underwriter's location.
Datamart	UW_DIM	UW_CTY	Underwriter City	VARCHAR2(32)	This value identifies the city of the underwriter's location.
Datamart	UW_DIM	UW_DSTRCT	Underwriter District	VARCHAR2(60)	This value identifies the district of the underwriter's location.
Datamart	UW_DIM	UW_GENDER	Underwriter Gender	VARCHAR2(60)	This value identifies the gender (male or female) of the underwriter.
Datamart	UW_DIM	UW_GEOG_BNDRY_UDF_1	Underwriter Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first underwriter geographic boundary user defined field.
Datamart	UW_DIM	UW_GEOG_BNDRY_UDF_2	Underwriter Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second underwriter geographic boundary user defined field.
Datamart	UW_DIM	UW_GEOG_BNDRY_UDF_3	Underwriter Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third underwriter geographic boundary user defined field.
Datamart	UW_DIM	UW_GEOG_BNDRY_UDF_4	Underwriter Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth underwriter geographic boundary user defined field.
Datamart	UW_DIM	UW_GEOG_BNDRY_UDF_5	Underwriter Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth underwriter geographic boundary user defined field.
Datamart	UW_DIM	UW_GOVT_ID_NUM	Underwriter Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the underwriter. For example, in the USA: SSN or FEIN.
Datamart	UW_DIM	UW_ID	Underwriter Identifier	NUMBER (22, 0)	This system generated number identifies the underwriter instance.
Datamart	UW_DIM	UW_LATITUDE	Underwriter Latitude	VARCHAR2(11)	This value identifies the latitude location of underwriter.
Datamart	UW_DIM	UW_LONGITUDE	Underwriter Longitude	VARCHAR2(11)	This value identifies the longitude location of underwriter.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	UW_DIM	UW_MARITAL_STATUS	Underwriter Marital Status	VARCHAR2(60)	This value identifies the present marital condition (single, married, divorced, widowed) of the underwriter.
Datamart	UW_DIM	UW_NAT_KEY	Underwriter Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the underwriter.
Datamart	UW_DIM	UW_NM	Underwriter Name	VARCHAR2(170)	This value represents the name of underwriter.
Datamart	UW_DIM	UW_NUM	Underwriter Number	VARCHAR2(25)	This value identifies the number or other identifier that identifies the underwriter.
Datamart	UW_DIM	UW_PARTY_UDF_1	Underwriter Party User Defined Field 1	VARCHAR2(60)	This value describes the first underwriter party user defined field.
Datamart	UW_DIM	UW_PARTY_UDF_2	Underwriter Party User Defined Field 2	VARCHAR2(60)	This value describes the second underwriter party user defined field.
Datamart	UW_DIM	UW_PARTY_UDF_3	Underwriter Party User Defined Field 3	VARCHAR2(60)	This value describes the third underwriter party user defined field.
Datamart	UW_DIM	UW_PARTY_UDF_4	Underwriter Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth underwriter party user defined field.
Datamart	UW_DIM	UW_PARTY_UDF_5	Underwriter Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth underwriter party user defined field.
Datamart	UW_DIM	UW_PERS_UDF_1	Underwriter Person User Defined Field 1	VARCHAR2(60)	This value describes the first underwriter person user defined field.
Datamart	UW_DIM	UW_PERS_UDF_2	Underwriter Person User Defined Field 2	VARCHAR2(60)	This value describes the second underwriter person user defined field.
Datamart	UW_DIM	UW_PERS_UDF_3	Underwriter Person User Defined Field 3	VARCHAR2(60)	This value describes the third underwriter person user defined field.
Datamart	UW_DIM	UW_PERS_UDF_4	Underwriter Person User Defined Field 4	VARCHAR2(60)	This value describes the fourth underwriter person user defined field.
Datamart	UW_DIM	UW_PERS_UDF_5	Underwriter Person User Defined Field 5	VARCHAR2(60)	This value describes the fifth underwriter person user defined field.
Datamart	UW_DIM	UW_PRES_EMPLMT_START_YR	Underwriter Present Employment Start Year	CHAR(4)	This value represents the calendar year that the underwriter began employment at current employer.
Datamart	UW_DIM	UW_PSTL_CD	Underwriter Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	UW_DIM	UW_PSTL_CD_PRFX	Underwriter Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	UW_DIM	UW_PSTL_SUB_CD	Underwriter Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	UW_DIM	UW_REGION	Underwriter Region	VARCHAR2(60)	This value represents the geographic region of the underwriter's location.

All Terms (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	UW_DIM	UW_STATE	Underwriter State	VARCHAR2(60)	This value identifies the state of the underwriter's location.
Datamart	UW_DIM	UW_TAX_LOC_ID	Underwriter Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier in the underwriter's location.
Datamart	UW_DIM	UW_TERR	Underwriter Territory	VARCHAR2(60)	This value represents the territory of the underwriter's location.
Datamart	UW_DIM	UW_TYP	Underwriter Type	VARCHAR2(60)	This value represents the classification of the underwriter's role.
Datamart	UW_DIM	UW_UDF_1	Underwriter User Defined Field 1	VARCHAR2(60)	This value describes the first underwriter user defined field.
Datamart	UW_DIM	UW_UDF_2	Underwriter User Defined Field 2	VARCHAR2(60)	This value describes the second underwriter user defined field.
Datamart	UW_DIM	UW_UDF_3	Underwriter User Defined Field 3	VARCHAR2(60)	This value describes the third underwriter user defined field.
Datamart	UW_DIM	UW_UDF_4	Underwriter User Defined Field 4	VARCHAR2(60)	This value describes the fourth underwriter user defined field.
Datamart	UW_DIM	UW_UDF_5	Underwriter User Defined Field 5	VARCHAR2(60)	This value describes the fifth underwriter user defined field.

Datamart

Datamart

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	BILL_ACCT_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the bill account applies.
Datamart	BILL_ACCT_DIM	BILL_ACCT_ID	Billing Account Identifier	NUMBER (22, 0)	This system generated number identifies the billing account instance.
Datamart	BILL_ACCT_DIM	BILL_ACCT_NAT_KEY	Billing Account Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the billing account.
Datamart	BILL_ACCT_DIM	BILL_ACCT_NUM	Billing Account Number	VARCHAR2(20)	This value represents the number of the account.
Datamart	BILL_ACCT_DIM	BILL_ACCT_UDF_1	Billing Account User Defined Field 1	VARCHAR2(60)	This value describes the first billing account policy user defined field.
Datamart	BILL_ACCT_DIM	BILL_ACCT_UDF_2	Billing Account User Defined Field 2	VARCHAR2(60)	This value describes the second billing account policy user defined field.
Datamart	BILL_ACCT_DIM	BILL_ACCT_UDF_3	Billing Account User Defined Field 3	VARCHAR2(60)	This value describes the third billing account policy user defined field.
Datamart	BILL_ACCT_DIM	BILL_ACCT_UDF_4	Billing Account User Defined Field 4	VARCHAR2(60)	This value describes the fourth billing account policy user defined field.
Datamart	BILL_ACCT_DIM	BILL_ACCT_UDF_5	Billing Account User Defined Field 5	VARCHAR2(60)	This value describes the fifth billing account policy user defined field.
Datamart	BILL_ACCT_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the bill account is currently applicable.
Datamart	BILL_ACCT_DIM	END_DT	End Date	DATE	This calendar date represents when the bill account is no longer valid.
Datamart	BILL_ACCT_DIM	METH_OF_PMT	Method of Payment	VARCHAR2(60)	This value represents the manner in which payments are made on an outstanding policy balance.
Datamart	BILL_ACCT_DIM	PMT_PLAN	Payment Plan	VARCHAR2(60)	This value represents the payment schedule applied to a policy balance.
Datamart	BILL_ACCT_DIM	PMT_SVC	Payment Service	VARCHAR2(60)	This value represents the entity that processes insured payments.
Datamart	CA_DRV_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage.
Datamart	CA_DRV_DIM	CA_DFEN_DRV_TRNG_DSCNT_PCT	Commercial Auto Defensive Driving Training Discount Percent	NUMBER (6, 3)	This number represents the percentage of premium waived when the defensive driver training discount applies.
Datamart	CA_DRV_DIM	CA_DFEN_DRV_TRNG_FLG	Commercial Auto Defensive Driving Training Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not the driver completed a defensive driver training course.
Datamart	CA_DRV_DIM	CA_DRV_ACCID_CNT	Commercial Auto Driver Accident Count	NUMBER (22, 0)	This number represents the count of accidents charged against the driver's driving record.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CA_DRV_DIM	CA_DRV_BIRTH_DT_ID	Commercial Auto Driver Birth Date Identifier	DATE	This calendar date represents the commercial auto driver's date of birth.
Datamart	CA_DRV_DIM	CA_DRV_CDL_ENDR_CD	Commercial Auto Driver Commercial Drivers License Endorsement Code	VARCHAR2(60)	This system code describes types of endorsements that apply to driver's commercial drivers license.
Datamart	CA_DRV_DIM	CA_DRV_CLASS	Commercial Auto Driver Class	VARCHAR2(60)	This value represents the classification that describes the characteristics of a the driver. It is typically only used for assigned risk, JUA, and in Texas.
Datamart	CA_DRV_DIM	CA_DRV_DFEN_DRV_CD	Commercial Auto Driver Defensive Driving Code	VARCHAR2(60)	This system code indicates the type of defensive driving course the driver completed.
Datamart	CA_DRV_DIM	CA_DRV_DWI_DUI_VIOLATION_CNT	Commercial Auto Driver DWI / DUI Violation Count	NUMBER (22, 0)	This number represents the count of Driving While intoxicated (DWI) and/or Driving Under the influence (DUI) violations charged against the driver's driving record.
Datamart	CA_DRV_DIM	CA_DRV_GENDER	Commercial Auto Driver Gender	VARCHAR2(60)	This value represents the gender (male or female) of the driver.
Datamart	CA_DRV_DIM	CA_DRV_GOVT_ID_NUM	Commercial Auto Driver Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the commercial auto driver. For example,.
Datamart	CA_DRV_DIM	CA_DRV_ID	Commercial Auto Driver Identifier	NUMBER (22, 0)	The system generated number that identifies the commercial auto driver.
Datamart	CA_DRV_DIM	CA_DRV_INSD_DT_ID	Commercial Auto Driver Insured Date Identifier	DATE	This calendar date represents when insurance coverage began for commercial driver.
Datamart	CA_DRV_DIM	CA_DRV_INTRMDT_VIOLATION_CNT	Commercial Auto Driver Intermediate Violation Count	NUMBER (22, 0)	This number represents the count of intermediate violations charged against the driver's driving record.
Datamart	CA_DRV_DIM	CA_DRV_LIC_DT_ID	Commercial Auto Driver License Date Identifier	DATE	This calendar date represents the driver license date.
Datamart	CA_DRV_DIM	CA_DRV_LIC_ISSUED_BY	Commercial Auto Driver License Issued By	VARCHAR2(60)	This value represents the government entity that issued the commercial drivers license.
Datamart	CA_DRV_DIM	CA_DRV_LIC_STATUS	Commercial Auto Driver License Status	VARCHAR2(60)	This value represents the government-assigned status of driving license privileges.
Datamart	CA_DRV_DIM	CA_DRV_MAJOR_VIOLATION_CNT	Commercial Auto Driver Major Violation Count	NUMBER (22, 0)	This number represents the count of major violations charged against the driver's driving record.
Datamart	CA_DRV_DIM	CA_DRV_MARITAL_STATUS	Commercial Auto Driver Marital Status	VARCHAR2(60)	This value represents the present marital condition (single, married, divorced, widowed) of the commercial auto driver.
Datamart	CA_DRV_DIM	CA_DRV_MINOR_VIOLATION_CNT	Commercial Auto Driver Minor Violation Count	NUMBER (22, 0)	This number represents the count of minor violations charged against the driver's driving record.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CA_DRV_DIM	CA_DRV_NAT_KEY	Commercial Auto Driver Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the commercial auto driver.
Datamart	CA_DRV_DIM	CA_DRV_NM	Commercial Auto Driver Name	VARCHAR2(170)	This value represents the full name of commercial auto driver.
Datamart	CA_DRV_DIM	CA_DRV_NUM	Commercial Auto Driver Number	NUMBER (22, 0)	This number identifies the commercial auto driver.
Datamart	CA_DRV_DIM	CA_DRV_PARTY_UDF_1	Commercial Auto Driver Party User Defined Field 1	VARCHAR2(60)	This value describes the first commercial auto driver party user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PARTY_UDF_2	Commercial Auto Driver Party User Defined Field 2	VARCHAR2(60)	This value describes the second commercial auto driver party user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PARTY_UDF_3	Commercial Auto Driver Party User Defined Field 3	VARCHAR2(60)	This value describes the third commercial auto driver party user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PARTY_UDF_4	Commercial Auto Driver Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth commercial auto driver party user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PARTY_UDF_5	Commercial Auto Driver Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth commercial auto driver party user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PERS_UDF_1	Commercial Auto Driver Person User Defined Field 1	VARCHAR2(60)	This value describes the first commercial auto driver person user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PERS_UDF_2	Commercial Auto Driver Person User Defined Field 2	VARCHAR2(60)	This value describes the second commercial auto driver person user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PERS_UDF_3	Commercial Auto Driver Person User Defined Field 3	VARCHAR2(60)	This value describes the third commercial auto driver person user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PERS_UDF_4	Commercial Auto Driver Person User Defined Field 4	VARCHAR2(60)	This value describes the fourth commercial auto driver person user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PERS_UDF_5	Commercial Auto Driver Person User Defined Field 5	VARCHAR2(60)	This value describes the fifth commercial auto driver person user defined field.
Datamart	CA_DRV_DIM	CA_DRV_PRES_EMPLMT_START_YR	Commercial Auto Driver Present Employment Start Year	CHAR(4)	This value represents the calendar year that the commercial auto driver began working for their current employer.
Datamart	CA_DRV_DIM	CA_DRV_RLAT_TO_APPLICANT	Commercial Auto Driver Relationship to Applicant	VARCHAR2(60)	This value represents the relationship of this commercial driver to the applicant.
Datamart	CA_DRV_DIM	CA_DRV_STATUS	Commercial Auto Driver Status	VARCHAR2(60)	This value represents the classification of the driver's coverage to policy coverages.
Datamart	CA_DRV_DIM	CA_DRV_TRNG_DSCNT_FLG	Commercial Auto Driver Training Discount Flag	CHAR(1)	This value represents the yes/no indicator identifying whether or not a driver training discount applies.
Datamart	CA_DRV_DIM	CA_DRV_TRNG_DSCNT_PCT	Commercial Auto Driver Training Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when driver training discount applies.
Datamart	CA_DRV_DIM	CA_DRV_TRNG_FLG	Commercial Auto Driver Training Flag	CHAR(1)	This value represents the yes/no indicator identifying presence or absence of driver training.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CA_DRV_DIM	CA_DRV_TYP	Commercial Auto Driver Type	VARCHAR2(60)	This value represents the classification that describes the attributes of a commercial driver.
Datamart	CA_DRV_DIM	CA_DRV_UDF_1	Commercial Auto Driver User Defined Field 1	VARCHAR2(60)	This value describes the first commercial auto driver user defined field.
Datamart	CA_DRV_DIM	CA_DRV_UDF_2	Commercial Auto Driver User Defined Field 2	VARCHAR2(60)	This value describes the second commercial auto driver user defined field.
Datamart	CA_DRV_DIM	CA_DRV_UDF_3	Commercial Auto Driver User Defined Field 3	VARCHAR2(60)	This value describes the third commercial auto driver user defined field.
Datamart	CA_DRV_DIM	CA_DRV_UDF_4	Commercial Auto Driver User Defined Field 4	VARCHAR2(60)	This value describes the fourth commercial auto driver user defined field.
Datamart	CA_DRV_DIM	CA_DRV_UDF_5	Commercial Auto Driver User Defined Field 5	VARCHAR2(60)	This value describes the fifth commercial auto driver user defined field.
Datamart	CA_DRV_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the driver is currently included in policy coverage.
Datamart	CA_DRV_DIM	END_DT	End Date	DATE	This calendar date represents when the commercial driver is no longer included in policy coverages.
Datamart	CA_FACT	CA_DRV_ID	Commercial Auto Driver Identifier	NUMBER (22, 0)	The system generated number that identifies the commercial auto driver instance.
Datamart	CA_FACT	CA_FACT_ID	Commercial Auto Fact Identifier	NUMBER (22, 0)	The system generated number that identifies the commercial vehicle fact instance.
Datamart	CA_FACT	CA_VEH_ID	Commercial Auto VehicleIdentifier	NUMBER (22, 0)	The system generated number that identifies the commercial auto vehicleinstance.
Datamart	CA_VEH_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage.
Datamart	CA_VEH_DIM	CA_VEH_ADDL_EQPT_AMT	Commercial Auto Vehicle Additional Equipment Amount	NUMBER (14, 3)	This number represents the monetary cost of commercial vehicle alterations or aftermarket custom equipment like custom painting, equipment installed to overcome a physical handicap, etc.
Datamart	CA_VEH_DIM	CA_VEH_AIRBAG_TYP	Commercial Auto Vehicle Airbag Type	VARCHAR2(60)	This value represents the classification of the airbag system installed in commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_ANTI_LOCK_BRAKES_CD	Commercial Auto Vehicle Anti-Lock Brakes Code	VARCHAR2(60)	This system code describes the anti-theft system present on commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_ANTI_THEFT_DEVICE_CD	Commercial Auto Vehicle Anti-Lock Brakes Code	VARCHAR2(60)	This system code describes the anti-lock brakes present on commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_AUTO_STBLTS_DSCNT_FLG	Commercial Auto Vehicle Automatic Seatbelts Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying presence or absence of automatic seatbelts discount.
Datamart	CA_VEH_DIM	CA_VEH_AUTO_STBLTS_DSCNT_PCT	Commercial Auto Vehicle Automatic Seatbelts Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when automatic seatbelt discount applies.
Datamart	CA_VEH_DIM	CA_VEH_BODY_TYP	Commercial Auto Vehicle Body Type	VARCHAR2(60)	This value represents the classification of the characteristics of a commercial vehicle body.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CA_VEH_DIM	CA_VEH_CELL_PHONE_TYP	Commercial Auto Vehicle Cellular Phone Type	VARCHAR2(60)	This system code identifies the cellular phone attributes present in vehicle.
Datamart	CA_VEH_DIM	CA_VEH_CLASS	Commercial Auto Vehicle Class	VARCHAR2(60)	This value represents the classification that describes vehicle size and body type.
Datamart	CA_VEH_DIM	CA_VEH_COST_NEW	Commercial Auto Vehicle Cost New	NUMBER (14, 3)	This number represents the monetary price of vehicle when purchased as a new vehicle.
Datamart	CA_VEH_DIM	CA_VEH_CUR_VAL	Commercial Auto Vehicle Current Value	NUMBER (14, 3)	This number represents the current monetary value of commercial vehicle in marketplace.
Datamart	CA_VEH_DIM	CA_VEH_DAYTIME_RUN_LIGHTS_CD	Commercial Auto Vehicle Daytime Running Lamps Code	VARCHAR2(60)	This system code describes the attributes of daytime running lamps present on commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_EST_ANNU_DRVG_DIST	Commercial Auto Vehicle Estimated Annual Driving Distance	NUMBER (22, 0)	This number identifies estimated annual driving distance units (miles/kilometers).
Datamart	CA_VEH_DIM	CA_VEH_GAR_CD	Commercial Auto Vehicle Garaging Code	VARCHAR2(60)	This system code describes the manner a vehicle is stored at garaging location.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_CNTY	Commercial Auto Vehicle Garaging Location County	VARCHAR2(60)	This value identifies the county where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_CTRY	Commercial Auto Vehicle Garaging Location Country	VARCHAR2(60)	This value identifies the country where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_CTY	Commercial Auto Vehicle Garaging Location City	VARCHAR2(32)	This value identifies the city where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_DSTRCT	Commercial Auto Vehicle Garaging Location District	VARCHAR2(60)	This value represents the district where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_LATITUDE	Commercial Auto Vehicle Garaging Location Latitude	VARCHAR2(11)	This value represents the district where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_LONGITUDE	Commercial Auto Vehicle Garaging Location Longitude	VARCHAR2(11)	This value represents the longitude location of where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_PSTL_CD	Commercial Auto Vehicle Garaging Location Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_PSTL_CD_PRFX	Commercial Auto Vehicle Garaging Location Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_PSTL_SUB_CD	Commercial Auto Vehicle Garaging Location Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies the smaller area of the total area served by a postal code.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_REGION	Commercial Auto Vehicle Garaging Location Region	VARCHAR2(60)	This value identifies the geographic region where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_STATE	Commercial Auto Vehicle Garaging Location State	VARCHAR2(60)	This value identifies the state where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_TAX_LOC_ID	Commercial Auto Vehicle Garaging Location Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier of the location where a vehicle is parked at night.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CA_VEH_DIM	CA_VEH_GAR_LOC_TERR	Commercial Auto Vehicle Garaging Location Territory	VARCHAR2(60)	This value represents the territory where a vehicle is parked at night.
Datamart	CA_VEH_DIM	CA_VEH_GEOG_BNDRY_UDF_1	Commercial Auto Vehicle Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first commercial vehicle geographic boundary user defined field.
Datamart	CA_VEH_DIM	CA_VEH_GEOG_BNDRY_UDF_2	Commercial Auto Vehicle Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second commercial vehicle geographic boundary user defined field.
Datamart	CA_VEH_DIM	CA_VEH_GEOG_BNDRY_UDF_3	Commercial Auto Vehicle Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third commercial vehicle geographic boundary user defined field.
Datamart	CA_VEH_DIM	CA_VEH_GEOG_BNDRY_UDF_4	Commercial Auto Vehicle Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth commercial vehicle geographic boundary user defined field.
Datamart	CA_VEH_DIM	CA_VEH_GEOG_BNDRY_UDF_5	Commercial Auto Vehicle Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth commercial vehicle geographic boundary user defined field.
Datamart	CA_VEH_DIM	CA_VEH_GROSS_WT	Commercial Auto Vehicle Gross Weight	NUMBER (14, 3)	This number represents the total weight a vehicle is designed to carry and includes the net weight of the vehicle, plus the weight of passengers, fuel, cargo and any additional accessories.
Datamart	CA_VEH_DIM	CA_VEH_HP_DSPLCMNT	Commercial Auto Vehicle Horsepower Displacement	VARCHAR2(5)	This value represents the cubic centimeters or displacement for a commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_ID	Commercial Auto Vehicle Identifier	NUMBER (22, 0)	This system generated number identifies the commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_INSD_DT_ID	Commercial Auto Vehicle Insured Date Identifier	DATE	This calendar date represents when insurance coverage began for commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_LEASE_DT_ID	Commercial Auto Vehicle Lease Date Identifier	DATE	This date identifies the calendar date when a commercial vehicle was leased by insured.
Datamart	CA_VEH_DIM	CA_VEH_MFR	Commercial Auto Vehicle Manufacturer	VARCHAR2(20)	This value represents the name of manufacturer that created the commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_MODEL	Commercial Auto Vehicle Model	VARCHAR2(20)	This value represents the model name assigned by the manufacturer of commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_MSRP	Commercial Auto Vehicle Manufacturer's Suggested Retail Price	NUMBER (14, 3)	This number represents the price that the manufacturer tells the vehicle dealer the new vehicle is worth.
Datamart	CA_VEH_DIM	CA_VEH_MULT_CAR_DSCNT_FLG	Commercial Auto Vehicle Multiple Car Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a multiple car discount applies.
Datamart	CA_VEH_DIM	CA_VEH_MULT_CAR_DSCNT_PCT	Commercial Auto Vehicle Multiple Car Discount Percentage	NUMBER (6, 3)	This number represents the percentage of rate waived when multiple car discount applies.
Datamart	CA_VEH_DIM	CA_VEH_NAT_KEY	Commercial Auto Vehicle Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_NEW_OR_USED_CD	Commercial Auto Vehicle New or Used Code	VARCHAR2(60)	This system code identifies if the insured is the original owner of the insured commercial vehicle.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CA_VEH_DIM	CA_VEH_NUM	Commercial Auto Vehicle Number	NUMBER (22, 0)	This number identifies the commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_NUM_DAYS_DRVN_PER_WK	Commercial Auto Vehicle Number of Days Driven Per Week	NUMBER (22, 0)	This number represents the count of days vehicle is driven per calendar week.
Datamart	CA_VEH_DIM	CA_VEH_ONE_WAY_DIST_TO_WRK	Commercial Auto Vehicle One Way Distance To Work	NUMBER (22, 0)	This number represents the number of distance units (miles/kilometers) to place of employment from residence.
Datamart	CA_VEH_DIM	CA_VEH_OWNRSHP_TYP	Commercial Auto Vehicle Ownership Type	VARCHAR2(60)	This value represents the classification that describes how a vehicle is owned and titled.
Datamart	CA_VEH_DIM	CA_VEH_PERF_CD	Commercial Auto Vehicle Performance Code	VARCHAR2(60)	This system code identifies the performance level of the commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_PURCH_DT_ID	Commercial Auto Vehicle Purchase Date Identifier	DATE	This calendar date represents when a commercial vehicle was purchased.
Datamart	CA_VEH_DIM	CA_VEH_PURCH_PRICE	Commercial Auto Vehicle Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when a commercial vehicle was purchased.
Datamart	CA_VEH_DIM	CA_VEH_RATING_AGE	Commercial Auto Vehicle Rating Age	VARCHAR2(60)	This value represents the age used to rate the commercial vehicle, regardless of its actual age.
Datamart	CA_VEH_DIM	CA_VEH_STATED_AMT	Commercial Auto Vehicle Stated Amount	NUMBER (14, 3)	This number represents the amount used to rate and value a commercial vehicle when a symbol is not available or useful.
Datamart	CA_VEH_DIM	CA_VEH_SYM	Commercial Auto Vehicle Symbol	VARCHAR2(60)	This value represents the cost symbol that represents a value.
Datamart	CA_VEH_DIM	CA_VEH_UDF_1	Commercial Auto Vehicle User Defined Field 1	VARCHAR2(60)	This value describes the first commercial vehicle user defined field.
Datamart	CA_VEH_DIM	CA_VEH_UDF_2	Commercial Auto Vehicle User Defined Field 2	VARCHAR2(60)	This value describes the second commercial vehicle user defined field.
Datamart	CA_VEH_DIM	CA_VEH_UDF_3	Commercial Auto Vehicle User Defined Field 3	VARCHAR2(60)	This value describes the third commercial vehicle user defined field.
Datamart	CA_VEH_DIM	CA_VEH_UDF_4	Commercial Auto Vehicle User Defined Field 4	VARCHAR2(60)	This value describes the fourth commercial vehicle user defined field.
Datamart	CA_VEH_DIM	CA_VEH_UDF_5	Commercial Auto Vehicle User Defined Field 5	VARCHAR2(60)	This value describes the fifth commercial vehicle user defined field.
Datamart	CA_VEH_DIM	CA_VEH_USE_CD	Commercial Auto Vehicle Use Code	VARCHAR2(60)	This system code identifies the primary use of the commercial vehicle.
Datamart	CA_VEH_DIM	CA_VEH_YR	Commercial Auto Vehicle Year	CHAR(4)	This value represents the model year assigned by vehicle manufacturer.
Datamart	CA_VEH_DIM	CA_VIN	Commercial Auto Vehicle Identification Number	VARCHAR2(25)	This value represents the unique identification number assigned by the vehicle's manufacturer.
Datamart	CA_VEH_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the commercial vehicle is currently applicable.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CA_VEH_DIM	END_DT	End Date	DATE	This calendar date represents when the commercial vehicle is no longer included in policy coverages.
Datamart	CAT_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the catastrophe started.
Datamart	CAT_DIM	CAT_BEGIN_DT_ID	Catastrophe Begin Date Identifier	DATE	This calendar date that identifies the catastrophe begin date instance.
Datamart	CAT_DIM	CAT_CD	Catastrophe Code	VARCHAR2(60)	This system code identifies a catastrophe. This is the number or other identifier assigned by the company.
Datamart	CAT_DIM	CAT_END_DT_ID	Catastrophe Ending Date Identifier	DATE	This calendar date identifies the catastrophe end date.
Datamart	CAT_DIM	CAT_ID	Catastrophe Identifier	NUMBER (22, 0)	This system generated number identifies the catastrophe instance.
Datamart	CAT_DIM	CAT_NAT_CD	Catastrophe National Code	VARCHAR2(60)	This system code identifies the national catastrophe occurrence.
Datamart	CAT_DIM	CAT_NAT_KEY	Catastrophe Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the catastrophe.
Datamart	CAT_DIM	CAT_SRC_CD	Catastrophe Source Code	VARCHAR2(60)	This system code describes the source of a catastrophe.
Datamart	CAT_DIM	CAT_STATE	Catastrophe State	VARCHAR2(60)	This value identifies the state where a catastrophe occurred.
Datamart	CAT_DIM	CAT_UDF_1	Catastrophe User Defined Field 1	VARCHAR2(60)	This value describes the first catastrophe user defined field.
Datamart	CAT_DIM	CAT_UDF_2	Catastrophe User Defined Field 2	VARCHAR2(60)	This value describes the second catastrophe user defined field.
Datamart	CAT_DIM	CAT_UDF_3	Catastrophe User Defined Field 3	VARCHAR2(60)	This value describes the third catastrophe user defined field.
Datamart	CAT_DIM	CAT_UDF_4	Catastrophe User Defined Field 4	VARCHAR2(60)	This value describes the fourth catastrophe user defined field.
Datamart	CAT_DIM	CAT_UDF_5	Catastrophe User Defined Field 5	VARCHAR2(60)	This value describes the fifth catastrophe user defined field.
Datamart	CAT_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the catastrophe is currently applicable.
Datamart	CAT_DIM	END_DT	End Date	DATE	This calendar date represents when the catastrophe ended.
Datamart	CAT_DIM	EXCESS_CAT_CD	Excess Catastrophe Code	VARCHAR2(60)	This system code indicates that a catastrophe loss is in excess of policyholders' retention.
Datamart	CLASS_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the class applies.
Datamart	CLASS_DIM	CLASS_CD	Class Code	VARCHAR2(60)	This system code classifies the subject of insurance.
Datamart	CLASS_DIM	CLASS_ID	Class Identifier	NUMBER (22, 0)	This system generated number identifies the class instance.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLASS_DIM	CLASS_NAT_KEY	Class Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the class.
Datamart	CLASS_DIM	CLASS_STATE	Class State	VARCHAR2(60)	This value identifies the state associated with the class.
Datamart	CLASS_DIM	CLASS_UDF_1	Class User Defined Field 1	VARCHAR2(60)	This value describes the first class user defined field.
Datamart	CLASS_DIM	CLASS_UDF_2	Class User Defined Field 2	VARCHAR2(60)	This value describes the second class user defined field.
Datamart	CLASS_DIM	CLASS_UDF_3	Class User Defined Field 3	VARCHAR2(60)	This value describes the third class user defined field.
Datamart	CLASS_DIM	CLASS_UDF_4	Class User Defined Field 4	VARCHAR2(60)	This value describes the fourth class user defined field.
Datamart	CLASS_DIM	CLASS_UDF_5	Class User Defined Field 5	VARCHAR2(60)	This value describes the fifth class user defined field.
Datamart	CLASS_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the class is currently applicable.
Datamart	CLASS_DIM	END_DT	End Date	DATE	This calendar date represents when the class is no longer valid.
Datamart	CLASS_DIM	PRIM_CLASS_CD	Primary Class Code	VARCHAR2(60)	In a situation where the class code is split into more than one useful breakout, this value represents the primary portion.
Datamart	CLASS_DIM	SCND_CLASS_CD	Second Class Code	VARCHAR2(60)	In a situation where the class code is split into more than one useful breakout, this value represents the secondary portion.
Datamart	CLM_ADJ_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim adjuster's employment began.
Datamart	CLM_ADJ_DIM	CLM_ADJ_BIRTH_DT_ID	Claim Adjuster Birth Date Identifier	DATE	This calendar date represents the claim adjuster's date of birth.
Datamart	CLM_ADJ_DIM	CLM_ADJ_BUS_START_DT_ID	Claim Adjuster Business Start Date Identifier	DATE	This calendar date represents when the claim adjuster's business began business activities.
Datamart	CLM_ADJ_DIM	CLM_ADJ_CNTCT_DESC	Claim Adjuster Contact Description	VARCHAR2(60)	This value describes the claim adjuster contact.
Datamart	CLM_ADJ_DIM	CLM_ADJ_CNTCT_TYP	Claim Adjuster Contact Type	VARCHAR2(60)	This value identifies the contact method for claim adjuster.
Datamart	CLM_ADJ_DIM	CLM_ADJ_CNTCT_UDF_1	Claim Adjuster Contact User Defined Field 1	VARCHAR2(60)	This value describes the first claim adjuster contact user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_CNTCT_UDF_2	Claim Adjuster Contact User Defined Field 2	VARCHAR2(60)	This value describes the second claim adjuster contact user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_CNTCT_UDF_3	Claim Adjuster Contact User Defined Field 3	VARCHAR2(60)	This value describes the third claim adjuster contact user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_CNTCT_UDF_4	Claim Adjuster Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim adjuster contact user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_ADJ_DIM	CLM_ADJ_CNTCT_UDF_5	Claim Adjuster Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim adjuster contact user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_CNTY	Claim Adjuster County	VARCHAR2(60)	This value identifies the county of the claim adjuster's location.
Datamart	CLM_ADJ_DIM	CLM_ADJ_CTRY	Claim Adjuster Country	VARCHAR2(60)	This value identifies the country of the claim adjuster's location.
Datamart	CLM_ADJ_DIM	CLM_ADJ_CTY	Claim Adjuster City	VARCHAR2(32)	This value identifies the city of the claim adjuster's location.
Datamart	CLM_ADJ_DIM	CLM_ADJ_DBA	Claim Adjuster Doing Business As	VARCHAR2(170)	This value represents the operational name of the claim adjuster's business.
Datamart	CLM_ADJ_DIM	CLM_ADJ_DSTRCT	Claim Adjuster District	VARCHAR2(60)	The district of the claim adjuster's location.
Datamart	CLM_ADJ_DIM	CLM_ADJ_GENDER	Claim Adjuster Gender	VARCHAR2(60)	This value represents the gender (male or female) of the claim adjuster.
Datamart	CLM_ADJ_DIM	CLM_ADJ_GEOG_BNDRY_UDF_1	Claim Adjuster Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first claim adjuster geographic boundary user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_GEOG_BNDRY_UDF_2	Claim Adjuster Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second claim adjuster geographic boundary user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_GEOG_BNDRY_UDF_3	Claim Adjuster Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third claim adjuster geographic boundary user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_GEOG_BNDRY_UDF_4	Claim Adjuster Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim adjuster geographic boundary user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_GEOG_BNDRY_UDF_5	Claim Adjuster Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim adjuster geographic boundary user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_GOVT_ID_NUM	Claim Adjuster Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the claim adjuster. For example,.
Datamart	CLM_ADJ_DIM	CLM_ADJ_ID	Claim Adjuster Identifier	NUMBER (22, 0)	This system generated number identifies the claims adjuster instance.
Datamart	CLM_ADJ_DIM	CLM_ADJ_LATITUDE	Claim Adjuster Latitude	VARCHAR2(11)	This value represents the latitude location of the claim adjuster's location.
Datamart	CLM_ADJ_DIM	CLM_ADJ_LONGITUDE	Claim Adjuster Longitude	VARCHAR2(11)	This value represents the longitude location of the claim adjuster's location.
Datamart	CLM_ADJ_DIM	CLM_ADJ_MARITAL_STATUS	Claim Adjuster Marital Status	VARCHAR2(60)	This value represents the present marital condition (single, married, divorced, widowed) of the claim adjuster.
Datamart	CLM_ADJ_DIM	CLM_ADJ_NAICS_CD	Claim Adjuster North American Industry Classification System Code	VARCHAR2(60)	This value represents the North America Industry Class (NAICS) code assigned to claim adjuster.
Datamart	CLM_ADJ_DIM	CLM_ADJ_NAT_KEY	Claim Adjuster Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claim adjuster.
Datamart	CLM_ADJ_DIM	CLM_ADJ_NM	Claim Adjuster Name	VARCHAR2(170)	This value represents the name of claims adjuster.
Datamart	CLM_ADJ_DIM	CLM_ADJ_NOB	Claim Adjuster Nature of Business	VARCHAR2(60)	This value represents the type or category of the business activities done by the claim adjuster.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_ADJ_DIM	CLM_ADJ_NUM	Claim Adjuster Number	VARCHAR2(25)	This value represents a number or other identifier for an adjuster.
Datamart	CLM_ADJ_DIM	CLM_ADJ_NUM_EMP	Claim Adjuster Number of Employees	NUMBER (22, 0)	This number represents the count of people employed by claim adjuster.
Datamart	CLM_ADJ_DIM	CLM_ADJ_ORG_UDF_1	Claim Adjuster Organization User Defined Field 1	VARCHAR2(60)	This value describes the first claim adjuster organization user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_ORG_UDF_2	Claim Adjuster Organization User Defined Field 2	VARCHAR2(60)	This value describes the second claim adjuster organization user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_ORG_UDF_3	Claim Adjuster Organization User Defined Field 3	VARCHAR2(60)	This value describes the third claim adjuster organization user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_ORG_UDF_4	Claim Adjuster Organization User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim adjuster organization user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_ORG_UDF_5	Claim Adjuster Organization User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim adjuster organization user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PARTY_UDF_1	Claim Adjuster Party User Defined Field 1	VARCHAR2(60)	This value describes the first claim adjuster party user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PARTY_UDF_2	Claim Adjuster Party User Defined Field 2	VARCHAR2(60)	This value describes the second claim adjuster party user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PARTY_UDF_3	Claim Adjuster Party User Defined Field 3	VARCHAR2(60)	This value describes the third claim adjuster party user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PARTY_UDF_4	Claim Adjuster Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim adjuster party user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PARTY_UDF_5	Claim Adjuster Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim adjuster party user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PERS_UDF_1	Claim Adjuster Person User Defined Field 1	VARCHAR2(60)	This value describes the first claim adjuster person user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PERS_UDF_2	Claim Adjuster Person User Defined Field 2	VARCHAR2(60)	This value describes the second claim adjuster person user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PERS_UDF_3	Claim Adjuster Person User Defined Field 3	VARCHAR2(60)	This value describes the third claim adjuster person user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PERS_UDF_4	Claim Adjuster Person User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim adjuster person user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PERS_UDF_5	Claim Adjuster Person User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim adjuster person user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PRES_EMPLMT_START_YR	Claim Adjuster Present Employment Start Year	CHAR(4)	This value represents the calendar year that the claim adjuster began working for their current employer.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PSTL_CD	Claim Adjuster Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_ADJ_DIM	CLM_ADJ_PSTL_CD_PRFX	Claim Adjuster Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	CLM_ADJ_DIM	CLM_ADJ_PSTL_SUB_CD	Claim Adjuster Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	CLM_ADJ_DIM	CLM_ADJ_REGION	Claim Adjuster Region	VARCHAR2(60)	This value represents the geographic region of the claim adjuster's location.
Datamart	CLM_ADJ_DIM	CLM_ADJ_SIC_CD	Claim Adjuster Standard Industrial Classification Code	VARCHAR2(60)	This system code is the SIC code assigned to the claim adjuster. The Standard Industrial Classification (SIC) code is an industry code that identifies the classification of business activity.
Datamart	CLM_ADJ_DIM	CLM_ADJ_STATE	Claim Adjuster State	VARCHAR2(60)	This value identifies the state where claim adjuster is located.
Datamart	CLM_ADJ_DIM	CLM_ADJ_TAX_LOC_ID	Claim Adjuster Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier.
Datamart	CLM_ADJ_DIM	CLM_ADJ_TERR	Claim Adjuster Territory	VARCHAR2(60)	This value represents the territory of the claim adjuster's location.
Datamart	CLM_ADJ_DIM	CLM_ADJ_TYP	Claim Adjuster Type	VARCHAR2(60)	This value represents the classification of activities of the adjuster used to support the claim process.
Datamart	CLM_ADJ_DIM	CLM_ADJ_UDF_1	Claim Adjuster User Defined Field 1	VARCHAR2(60)	This value describes the first claim adjuster user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_UDF_2	Claim Adjuster User Defined Field 2	VARCHAR2(60)	This value describes the second claim adjuster user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_UDF_3	Claim Adjuster User Defined Field 3	VARCHAR2(60)	This value describes the third claim adjuster user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_UDF_4	Claim Adjuster User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim adjuster user defined field.
Datamart	CLM_ADJ_DIM	CLM_ADJ_UDF_5	Claim Adjuster User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim adjuster user defined field.
Datamart	CLM_ADJ_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim adjuster is currently applicable.
Datamart	CLM_ADJ_DIM	END_DT	End Date	DATE	This calendar date represents when the claim adjuster's employment ended.
Datamart	CLM_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim loss period began.
Datamart	CLM_DIM	CASE_MADE_RETROACTIVE_DT_ID	Case Made Retroactive Date Identifier	DATE	This calendar date represents the case made retroactive date.
Datamart	CLM_DIM	CASE_MGMT_ASSIGNED_DT_ID	Case Management Assigned Date Identifier	DATE	This calendar date identifies when the case management was assigned.
Datamart	CLM_DIM	CLM_CLOSED_DT_ID	Claim Closed Date Identifier	DATE	This calendar date represents the claim closed date instance.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_DIM	CLM_GEOG_BNDRY_UDF_1	Claim Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first claim geographic boundary user defined field.
Datamart	CLM_DIM	CLM_GEOG_BNDRY_UDF_2	Claim Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second claim geographic boundary user defined field.
Datamart	CLM_DIM	CLM_GEOG_BNDRY_UDF_3	Claim Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third claim geographic boundary user defined field.
Datamart	CLM_DIM	CLM_GEOG_BNDRY_UDF_4	Claim Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim geographic boundary user defined field.
Datamart	CLM_DIM	CLM_GEOG_BNDRY_UDF_5	Claim Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim geographic boundary user defined field.
Datamart	CLM_DIM	CLM_ID	Claim Identifier	NUMBER (22, 0)	This system generated number identifies the claim instance.
Datamart	CLM_DIM	CLM_NAT_KEY	Claim Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claim.
Datamart	CLM_DIM	CLM_NUM	Claim Number	VARCHAR2(30)	This number or other unique identifier identifies a claim.
Datamart	CLM_DIM	CLM_OPENED_DT_ID	Claim Opened Date Identifier	DATE	This calendar date represents when the claim opened date instance.
Datamart	CLM_DIM	CLM_RECLOSED_DT_ID	Claim Re-Closed Date Identifier	DATE	This calendar date represents when the claim re-closed date instance.
Datamart	CLM_DIM	CLM_REOPENED_DT_ID	Claim Re-Opened Date Identifier	DATE	This calendar date represents when the claim re-opened date instance.
Datamart	CLM_DIM	CLM_RPT_BY	Claim Report By	VARCHAR2(60)	This value represents the source of claim report.
Datamart	CLM_DIM	CLM_RPT_CLASS_CD	Claim Report Class Code	VARCHAR2(60)	This system code describes the class code report class applicable to the claim, regardless of the class codes on the policy.
Datamart	CLM_DIM	CLM_RPT_DT_ID	Claim Report Date Identifier	DATE	This calendar date represents the claim reported date instance.
Datamart	CLM_DIM	CLM_STATUS	Claim Status	VARCHAR2(60)	This value represents the process condition of a claim.
Datamart	CLM_DIM	CLM_UDF_1	Claim User Defined Field 1	VARCHAR2(60)	This value describes the first claim user defined field.
Datamart	CLM_DIM	CLM_UDF_2	Claim User Defined Field 2	VARCHAR2(60)	This value describes the second claim user defined field.
Datamart	CLM_DIM	CLM_UDF_3	Claim User Defined Field 3	VARCHAR2(60)	This value describes the third claim user defined field.
Datamart	CLM_DIM	CLM_UDF_4	Claim User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim user defined field.
Datamart	CLM_DIM	CLM_UDF_5	Claim User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_DIM	CLMS_MADE_BASIS_CD	Claims Made Basis Code	VARCHAR2(60)	This system code identifies whether or not the claims made basis is being used for reporting of claims.
Datamart	CLM_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim is currently applicable.
Datamart	CLM_DIM	END_DT	End Date	DATE	This calendar date represents when the claim loss period ended.
Datamart	CLM_DIM	FIRST_CLM_CNTCT_DT_ID	First Claim Contact Date Identifier	DATE	This calendar date represents the first claim contact date instance.
Datamart	CLM_DIM	FIRST_CLM_PMT_DT_ID	First Claim Payment Date Identifier	DATE	This calendar date represents the first claim payment date instance.
Datamart	CLM_DIM	FRAUD_CLM_CD	Fraud Claim Code	VARCHAR2(60)	This system code indicates potential fraudulent claim based on adjusters' investigation.
Datamart	CLM_DIM	LAST_CLM_PMT_DT_ID	Last Claim Payment Date Identifier	DATE	This calendar date represents the last claim payment date instance.
Datamart	CLM_DIM	LAST_SALV_PMT_DT_ID	Last Salvage Payment Date Identifier	DATE	This calendar date represents the last salvage payment date instance.
Datamart	CLM_DIM	LAST_SUBRO_PMT_DT_ID	Last Subrogation Payment Date Identifier	DATE	This calendar date represents the last subrogation payment date instance.
Datamart	CLM_DIM	LOC_OF_LOSS_CNTY	Location Of Loss County	VARCHAR2(60)	This value identifies the county where the loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_CTRY	Location Of Loss Country	VARCHAR2(60)	This value identifies the country where the loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_CTY	Location Of Loss City	VARCHAR2(32)	This value identifies the city where the loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_DSTRCT	Location Of Loss District	VARCHAR2(60)	This value identifies the district where the loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_LATITUDE	Location Of Loss Latitude	VARCHAR2(11)	This value identifies the latitude where the loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_LONGITUDE	Location Of Loss Longitude	VARCHAR2(11)	This value identifies the longitude where the loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_PSTL_CD	Location Of Loss Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	CLM_DIM	LOC_OF_LOSS_PSTL_CD_PRFX	Location Of Loss Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	CLM_DIM	LOC_OF_LOSS_PSTL_SUB_CD	Location Of Loss Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code. This is the sub code of the location where the loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_REGION	Location Of Loss Region	VARCHAR2(60)	This value identifies the geographic region where the loss occurred.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_DIM	LOC_OF_LOSS_STATE	Location Of Loss State	VARCHAR2(60)	This value identifies the state where a loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_TAX_LOC_ID	Location Of Loss Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier of the location where a loss occurred.
Datamart	CLM_DIM	LOC_OF_LOSS_TERR	Location Of Loss Territory	VARCHAR2(60)	This value represents the territory where a loss occurred.
Datamart	CLM_DIM	LOSS_DT_ID	Loss Date Identifier	DATE	This calendar date represents when an accident or loss occurred regardless of when the claim was filed.
Datamart	CLM_DIM	LOSS_TIME_ID	Loss Time Identifier	NUMBER (22, 0)	This system generated number identifies the loss time instance.
Datamart	CLM_DIM	NUM_RENTAL_DAYS	Number Of Rental Days	NUMBER (22, 0)	This number represents the count of days a replacement item is rented.
Datamart	CLM_DIM	NUM_REPAIR_DAYS	Number Of Repair Days	NUMBER (22, 0)	This number represents the count of days required to repair an item.
Datamart	CLM_DIM	NUM_STORAGE_DAYS	Number Of Storage Days	NUMBER (22, 0)	This number represents the count of days an item is stored.
Datamart	CLM_EXAMR_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim examiner's employment began.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_BIRTH_DT_ID	Claim Examiner Birth Date	DATE	This calendar date represents the claim examiner's date of birth.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CNTCT_DESC	Claim Examiner Contact Description	VARCHAR2(60)	This value describes the claim examiner contact.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CNTCT_TYP	Claim Examiner Contact Type	VARCHAR2(60)	This value represents the contact method.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CNTCT_UDF_1	Claim Examiner Contact User Defined Field 1	VARCHAR2(60)	This value describes the first claim examiner contact user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CNTCT_UDF_2	Claim Examiner Contact User Defined Field 2	VARCHAR2(60)	This value describes the second claim examiner contact user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CNTCT_UDF_3	Claim Examiner Contact User Defined Field 3	VARCHAR2(60)	This value describes the third claim examiner contact user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CNTCT_UDF_4	Claim Examiner Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim examiner contact user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CNTCT_UDF_5	Claim Examiner Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim examiner contact user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CNTY	Claim Examiner County	VARCHAR2(60)	This value identifies the county of the claim examiner's location.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CTRY	Claim Examiner Country	VARCHAR2(60)	This value identifies the country of the claim examiner's location.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_CTY	Claim Examiner City	VARCHAR2(32)	This value identifies the city of the claim examiner's location.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_DSTRCT	Claim Examiner District	VARCHAR2(60)	This value represents the district of the claim examiner's location.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_GENDER	Claim Examiner Gender	VARCHAR2(60)	This value represents the gender (male or female) of the claim examiner.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_GEOG_BNDRY_UDF_1	Claim Examiner Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first claim examiner geographic boundary user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_GEOG_BNDRY_UDF_2	Claim Examiner Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second claim examiner geographic boundary user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_GEOG_BNDRY_UDF_3	Claim Examiner Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third claim examiner geographic boundary user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_GEOG_BNDRY_UDF_4	Claim Examiner Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim examiner geographic boundary user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_GEOG_BNDRY_UDF_5	Claim Examiner Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim examiner geographic boundary user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_GOVT_ID_NUM	Claim Examiner Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the claim examiner. For example, in the USA: SSN or FEIN.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_ID	Claim Examiner Identifier	NUMBER (22, 0)	This system generated number identifies the claim examiner instance.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_LATITUDE	Claim Examiner Latitude	VARCHAR2(11)	This value represents the latitude location of the geographic boundary.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_LONGITUDE	Claim Examiner Longitude	VARCHAR2(11)	This value represents the longitude location of the geographic boundary.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_MARITAL_STATUS	Claim Examiner Marital Status	VARCHAR2(60)	The present marital condition (single, married, divorced, widowed) of the claim examiner.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_NAT_KEY	Claim Examiner Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claim examiner.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_NM	Claim Examiner Name	VARCHAR2(170)	This value represents the name of the claim examiner.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_NUM	Claim Examiner Number	VARCHAR2(25)	This value represents the number or identifier assigned to the claim examiner.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PARTY_UDF_1	Claim Examiner Party User Defined Field 1	VARCHAR2(60)	This value describes the first claim examiner party user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PARTY_UDF_2	Claim Examiner Party User Defined Field 2	VARCHAR2(60)	This value describes the second claim examiner party user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PARTY_UDF_3	Claim Examiner Party User Defined Field 3	VARCHAR2(60)	This value describes the third claim examiner party user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PARTY_UDF_4	Claim Examiner Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim examiner party user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PARTY_UDF_5	Claim Examiner Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim examiner party user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PERS_UDF_1	Claim Examiner Person User Defined Field 1	VARCHAR2(60)	This value describes the first claim examiner person user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PERS_UDF_2	Claim Examiner Person User Defined Field 2	VARCHAR2(60)	This value describes the second claim examiner person user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PERS_UDF_3	Claim Examiner Person User Defined Field 3	VARCHAR2(60)	This value describes the third claim examiner person user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PERS_UDF_4	Claim Examiner Person User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim examiner person user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PERS_UDF_5	Claim Examiner Person User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim examiner person user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PRES_EMPLMT_START_YR	Claim Examiner Present Employment Start Year	CHAR(4)	This value represents the calendar year that the claim examiner began working for their current employer.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PSTL_CD	Claim Examiner Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PSTL_CD_PRFX	Claim Examiner Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_PSTL_SUB_CD	Claim Examiner Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_REGION	Claim Examiner Region	VARCHAR2(60)	This value represents the geographic region of the claim examiner's location.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_STATE	Claim Examiner State	VARCHAR2(60)	This value identifies the state of the claim examiner's location.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_TAX_LOC_ID	Claim Examiner Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier of the claim examiner's location.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_TERR	Claim Examiner Territory	VARCHAR2(60)	This value represents the territory of the claim examiner's location.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_TYP	Claim Examiner Type	VARCHAR2(60)	This value represents the classification describes claim examiner roles.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_UDF_1	Claim Examiner User Defined Field 1	VARCHAR2(60)	This value describes the first claim examiner user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_UDF_2	Claim Examiner User Defined Field 2	VARCHAR2(60)	This value describes the second claim examiner user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_UDF_3	Claim Examiner User Defined Field 3	VARCHAR2(60)	This value describes the third claim examiner user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_UDF_4	Claim Examiner User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim examiner user defined field.
Datamart	CLM_EXAMR_DIM	CLM_EXAMR_UDF_5	Claim Examiner User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim examiner user defined field.
Datamart	CLM_EXAMR_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim examiner is currently applicable.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_EXAMR_DIM	END_DT	End Date	DATE	This calendar date represents when the claim examiner's employment ended.
Datamart	CLM_MGR_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim manager's employment began.
Datamart	CLM_MGR_DIM	CLM_MGR_BIRTH_DT_ID	Claim Manager Birth Date Identifier	DATE	This calendar date represents the claim manager's date of birth.
Datamart	CLM_MGR_DIM	CLM_MGR_CNTCT_DESC	Claim Manager Contact Description	VARCHAR2(60)	This value describes the claim manager contact.
Datamart	CLM_MGR_DIM	CLM_MGR_CNTCT_TYP	Claim Manager Contact Type	VARCHAR2(60)	This value represents claim manager's contact type.
Datamart	CLM_MGR_DIM	CLM_MGR_CNTCT_UDF_1	Claim Manager Contact User Defined Field 1	VARCHAR2(60)	This value describes the first claim manager contact user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_CNTCT_UDF_2	Claim Manager Contact User Defined Field 2	VARCHAR2(60)	This value describes the second claim manager contact user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_CNTCT_UDF_3	Claim Manager Contact User Defined Field 3	VARCHAR2(60)	This value describes the third claim manager contact user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_CNTCT_UDF_4	Claim Manager Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim manager contact user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_CNTCT_UDF_5	Claim Manager Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim manager contact user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_CNTY	Claim Manager County	VARCHAR2(60)	This value identifies the county of the claim examiner's location.
Datamart	CLM_MGR_DIM	CLM_MGR_CTRY	Claim Manager Country	VARCHAR2(60)	This value identifies the country of the claim examiner's location.
Datamart	CLM_MGR_DIM	CLM_MGR_CTY	Claim Manager City	VARCHAR2(32)	This value identifies the city of the claim examiner's location.
Datamart	CLM_MGR_DIM	CLM_MGR_DSTRCT	Claim Manager District	VARCHAR2(60)	This value represents the first name of the person.
Datamart	CLM_MGR_DIM	CLM_MGR_GENDER	Claim Manager Gender	VARCHAR2(60)	This value represents the gender (male or female) of the claim manager.
Datamart	CLM_MGR_DIM	CLM_MGR_GEOG_BNDRY_UDF_1	Claim Manager Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first claim manager geographic boundary user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_GEOG_BNDRY_UDF_2	Claim Manager Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second claim manager geographic boundary user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_GEOG_BNDRY_UDF_3	Claim Manager Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third claim manager geographic boundary user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_GEOG_BNDRY_UDF_4	Claim Manager Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim manager geographic boundary user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_GEOG_BNDRY_UDF_5	Claim Manager Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim manager geographic boundary user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_GOVT_ID_NUM	Claim Manager Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the claim manger. For example, in the USA: SSN or FEIN.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MGR_DIM	CLM_MGR_ID	Claim Manager Identifier	NUMBER (22, 0)	This system generated number identifies the claim manager instance.
Datamart	CLM_MGR_DIM	CLM_MGR_LATITUDE	Claim Manager Latitude	VARCHAR2(11)	This value represents the claim manager's latitude location.
Datamart	CLM_MGR_DIM	CLM_MGR_LONGITUDE	Claim Manager Longitude	VARCHAR2(11)	This value represents the claim manager's longitude location.
Datamart	CLM_MGR_DIM	CLM_MGR_MARITAL_STATUS	Claim Manager Marital Status	VARCHAR2(60)	This value represents the claim manager's present marital condition (single, married, divorced, widowed).
Datamart	CLM_MGR_DIM	CLM_MGR_NAT_KEY	Claim Manager Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claim manager.
Datamart	CLM_MGR_DIM	CLM_MGR_NM	Claim Manager Name	VARCHAR2(170)	This value represents the name of the claim manager.
Datamart	CLM_MGR_DIM	CLM_MGR_NUM	Claim Manager Number	VARCHAR2(25)	This number or unique identifier identifies a claim manager.
Datamart	CLM_MGR_DIM	CLM_MGR_PARTY_UDF_1	Claim Manager Party User Defined Field 1	VARCHAR2(60)	This value describes the first claim manager party user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PARTY_UDF_2	Claim Manager Party User Defined Field 2	VARCHAR2(60)	This value describes the second claim manager party user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PARTY_UDF_3	Claim Manager Party User Defined Field 3	VARCHAR2(60)	This value describes the third claim manager party user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PARTY_UDF_4	Claim Manager Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim manager party user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PARTY_UDF_5	Claim Manager Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim manager party user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PERS_UDF_1	Claim Manager Person User Defined Field 1	VARCHAR2(60)	This value describes the first claim manager person user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PERS_UDF_2	Claim Manager Person User Defined Field 2	VARCHAR2(60)	This value describes the second claim manager person user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PERS_UDF_3	Claim Manager Person User Defined Field 3	VARCHAR2(60)	This value describes the third claim manager person user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PERS_UDF_4	Claim Manager Person User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim manager person user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PERS_UDF_5	Claim Manager Person User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim manager person user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_PRES_EMPLMT_START_YR	Claim Manager Present Employment Start Year	CHAR(4)	This value represents the calendar year the claim manager began working for their current employer.
Datamart	CLM_MGR_DIM	CLM_MGR_PSTL_CD	Claim Manager Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MGR_DIM	CLM_MGR_PSTL_CD_PRFX	Claim Manager Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	CLM_MGR_DIM	CLM_MGR_PSTL_SUB_CD	Claim Manager Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	CLM_MGR_DIM	CLM_MGR_REGION	Claim Manager Region	VARCHAR2(60)	This value represents the geographic region of the claim manager's location.
Datamart	CLM_MGR_DIM	CLM_MGR_STATE	Claim Manager State	VARCHAR2(60)	This value identifies the state where claim manager is located.
Datamart	CLM_MGR_DIM	CLM_MGR_TAX_LOC_ID	Claim Manager Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier.
Datamart	CLM_MGR_DIM	CLM_MGR_TERR	Claim Manager Territory	VARCHAR2(60)	This value represents the territory of the claim manager's location.
Datamart	CLM_MGR_DIM	CLM_MGR_TYP	Claim Manager Type	VARCHAR2(60)	This value represents the classification describes claim manager roles.
Datamart	CLM_MGR_DIM	CLM_MGR_UDF_1	Claim Manager User Defined Field 1	VARCHAR2(60)	This value describes the first claim manager user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_UDF_2	Claim Manager User Defined Field 2	VARCHAR2(60)	This value describes the second claim manager user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_UDF_3	Claim Manager User Defined Field 3	VARCHAR2(60)	This value describes the third claim manager user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_UDF_4	Claim Manager User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim manager user defined field.
Datamart	CLM_MGR_DIM	CLM_MGR_UDF_5	Claim Manager User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim manager user defined field.
Datamart	CLM_MGR_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim manager is currently applicable.
Datamart	CLM_MGR_DIM	END_DT	End Date	DATE	This calendar date represents when the claim manager's employment ended.
Datamart	CLM_MTH_SNAP_FACT	BILL_ACCT_ID	Billing Account Identifier	NUMBER (22, 0)	This system generated number identifies the billing account instance.
Datamart	CLM_MTH_SNAP_FACT	CAL_MTH_ID	Calendar Month Identifier	NUMBER (22, 0)	This system generated number identifies the calendar month.
Datamart	CLM_MTH_SNAP_FACT	CAT_ID	Catastrophe Identifier	NUMBER (22, 0)	This system generated number identifies the catastrophe.
Datamart	CLM_MTH_SNAP_FACT	CLASS_ID	Class Identifier	NUMBER (22, 0)	This system generated number identifies the class.
Datamart	CLM_MTH_SNAP_FACT	CLM_ADJ_ID	Claim Adjuster Identifier	NUMBER (22, 0)	This system generated number identifies the adjuster instance.
Datamart	CLM_MTH_SNAP_FACT	CLM_EXAMR_ID	Claim Examiner Identifier	NUMBER (22, 0)	This system generated number identifies the claim examiner instance.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MTH_SNAP_FACT	CLM_ID	Claim Identifier	NUMBER (22, 0)	This system generated number identifies the claim instance.
Datamart	CLM_MTH_SNAP_FACT	CLM_MGR_ID	Claim Manager Identifier	NUMBER (22, 0)	This system generated number identifies the claim manager instance.
Datamart	CLM_MTH_SNAP_FACT	CLM_NAT_KEY	Claim Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claim.
Datamart	CLM_MTH_SNAP_FACT	CLMT_ID	Claimant Identifier	NUMBER (22, 0)	This system generated number identifies the claimant instance.
Datamart	CLM_MTH_SNAP_FACT	CLMT_NAT_KEY	Claimant Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claimant.
Datamart	CLM_MTH_SNAP_FACT	CLOSED_CLM_NAT_KEY	Closed Claim Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the closed claim.
Datamart	CLM_MTH_SNAP_FACT	COVRG_ID	Coverage Identifier	NUMBER (22, 0)	This system generated number identifies coverage instance.
Datamart	CLM_MTH_SNAP_FACT	COVRG_STATUS_ID	Coverage Status Identifier	NUMBER (22, 0)	This system generated number identifies coverage status instance.
Datamart	CLM_MTH_SNAP_FACT	DC_ID	Distribution Channel Identifier	NUMBER (22, 0)	This system generated number identifies the distribution channel instance.
Datamart	CLM_MTH_SNAP_FACT	DED_ID	Deductible Identifier	NUMBER (22, 0)	This system generated number identifies the deductible instance.
Datamart	CLM_MTH_SNAP_FACT	DOC_ALAE_AMT	Document Allocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of document allocated loss adjustment expense amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_ALAE_RSRV_AMT	Document Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of document allocated loss adjustment expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_ALLOC_EXPNS_AO_AMT	Document Allocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the document allocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_CTD_INCRD_AMT	Document Claim to Date Incurred Amount	NUMBER (14, 3)	This number represents the cost of document claims to date incurred amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_CTD_INCRD_WEXPNS_AMT	Document Claim to Date Incurred With Expenses Amount	NUMBER (14, 3)	This number represents the cost of document claims to date increased with expense amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_CURR_CD	Document Currency Code	VARCHAR2(25)	This system code identifies document currency for a claim monthly snapshot fact table.
Datamart	CLM_MTH_SNAP_FACT	DOC_DED_LPMT_AMT	Document Deductible Loss Payment Amount	NUMBER (14, 3)	This number represents the cost of document deductible loss payment amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_DED_LRSRV_CHANGE_AMT	Document Deductible Loss Reserve Change Amount	NUMBER (14, 3)	This number represents the cost of document deductible loss reserve change amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_END_ALAE_RSRV_AMT	Document Ending Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of document ending allocated loss adjustment expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_END_DED_LPMT_RSRV_AMT	Document Ending Deductible Loss Payment Reserve Amount	NUMBER (14, 3)	This number represents the cost of document ending deductible loss payment reserve amount.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MTH_SNAP_FACT	DOC_END_LRSRV_AMT	Document Ending Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of document ending loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_END_SALV_RSRV_AMT	Document Ending Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of document ending salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_END_SUBRO_RSRV_AMT	Document Ending Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of document ending subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_END_ULAE_RSRV_AMT	Document Ending Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of document ending unallocated loss adjustment expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_INCRD_AMT	Document Incurred Amount	NUMBER (14, 3)	This number represents the cost of document incurred amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_INCRD_WEXPNS_AMT	Document Incurred With Expense Amount	NUMBER (14, 3)	This number represents the cost of document incurred with expense amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_LEGAL_FEES_AMT	Document Legal Fees Expense Amount	NUMBER (14, 3)	This number represents the cost of document legal fees amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_LRSRV_AMT	Document Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of document loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_OUT_ADJ_FEES_AMT	Document Outside Adjusting Fees Expense Amount	NUMBER (14, 3)	This number represents the cost of document outside adjustment fees amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_PAID_LOSS_AMT	Document Paid Loss Amount	NUMBER (14, 3)	This number represents the cost of document paid loss amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_SALV_AMT	Document Salvage Amount	NUMBER (14, 3)	This number represents the cost of document salvage amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_SALV_RSRV_AMT	Document Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of document salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_SUBRO_AMT	Document Subrogation Amount	NUMBER (14, 3)	This number represents the cost of document subrogation amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_SUBRO_RSRV_AMT	Document Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of document subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_ULAE_AMT	Document Unallocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of document unallocated loss adjustment expense amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_ULAE_RSRV_AMT	Document Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of document unallocated loss adjustment expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	DOC_UNALLOC_EXPNS_AO_AMT	Document Unallocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the cost of document unallocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	FEAT_ID	Feature Identifier	NUMBER (22, 0)	This system generated number identifies the claim feature instance.
Datamart	CLM_MTH_SNAP_FACT	FEAT_STATUS_ID	Feature Status Identifier	NUMBER (22, 0)	This system generated number identifies the claim feature status instance.
Datamart	CLM_MTH_SNAP_FACT	FISCAL_MTH_ID	Fiscal Month Identifier	NUMBER (22, 0)	This number identifies fiscal month.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_ALAE_AMT	Global 1 Allocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of the first global allocated loss adjusting expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_ALAE_RSRV_AMT	Global 1 Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global allocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_ALLOC_EXPNS_AO_AMT	Global 1 Allocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the cost of the first global allocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_CTD_INCRD_AMT	Global 1 Claim to Date Incurred Amount	NUMBER (14, 3)	This number represents the cost of the first global claims to date incurred amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_CTD_INCRD_WEXPNS_AMT	Global 1 Claim to Date Incurred With Expenses Amount	NUMBER (14, 3)	This number represents the cost of the first global claims to date increased with expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_DED_LPMT_AMT	Global 1 Deductible Loss Payment Amount	NUMBER (14, 3)	This number represents the cost of the first global deductible loss payment amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_DED_LRSRV_CHANGE_AMT	Global 1 Deductible Loss Reserve Change Amount	NUMBER (14, 3)	This number represents the cost of the first global deductible loss reserve change amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_END_ALAE_RSRV_AMT	Global 1 Ending Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global end allocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_END_DED_LPMT_RSRV_AMT	Global 1 Ending Deductible Loss Payment Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global end deductible loss payment reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_END_LRSRV_AMT	Global 1 Ending Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global ending loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_END_SALV_RSRV_AMT	Global 1 Ending Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global end salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_END_SUBRO_RSRV_AMT	Global 1 Ending Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global end subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_END_ULAE_RSRV_AMT	Global 1 Ending Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global end unallocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_INCRD_AMT	Global 1 Incurred Amount	NUMBER (14, 3)	This number represents the cost of the first global incurred amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_INCRD_WEXPNS_AMT	Global 1 Incurred With Expenses Amount	NUMBER (14, 3)	This number represents the cost of the first global increased with expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_LEGAL_FEES_AMT	Global 1 Legal Fees Expense Amount	NUMBER (14, 3)	This number represents the cost of the first global legal fees amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_LRSRV_AMT	Global 1 Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_OUT_ADJ_FEES_AMT	Global 1 Outside Adjusting Fees Amount	NUMBER (14, 3)	This number represents the cost of the first global outside adjustment fees amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_PAID_LOSS_AMT	Global 1 Paid Loss Amount	NUMBER (14, 3)	This number represents the cost of the first global paid loss amount.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_SALV_AMT	Global 1 Salvage Amount	NUMBER (14, 3)	This number represents the cost of the first global salvage amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_SALV_RSRV_AMT	Global 1 Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_SUBRO_AMT	Global 1 Subrogation Amount	NUMBER (14, 3)	This number represents the cost of the first global subrogation amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_SUBRO_RSRV_AMT	Global 1 Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_ULAE_AMT	Global 1 Unallocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of the first global unallocated loss adjusting expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_ULAE_RSRV_AMT	Global 1 Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the first global unallocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_1_UNALLOC_EXPNS_AO_AMT	Global 1 UnAllocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the cost of the first global unallocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_ALAE_AMT	Global 2 Allocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of the second global allocated loss adjusting expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_ALAE_RSRV_AMT	Global 2 Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global allocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_ALLOC_EXPNS_AO_AMT	Global 2 Allocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the cost of the second global allocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_CTD_INCRD_AMT	Global 2 Claim to Date Incurred Amount	NUMBER (14, 3)	This number represents the cost of the second global claims to date incurred amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_CTD_INCRD_WEXPNS_AMT	Global 2 Claim to Date Incurred With Expenses Amount	NUMBER (14, 3)	This number represents the cost of the second global claims to date increased with expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_DED_LPMT_AMT	Global 2 Deductible Loss Payment Amount	NUMBER (14, 3)	This number represents the cost of the second global deductible loss payment amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_DED_LRSRV_CHANGE_AMT	Global 2 Deductible Loss Reserve Change Amount	NUMBER (14, 3)	This number represents the cost of the second global deductible loss reserve change amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_END_ALAE_RSRV_AMT	Global 2 Ending Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global end allocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_END_DED_LPMT_RSRV_AMT	Global 2 Ending Deductible Loss Payment Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global end deductible loss payment reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_END_LRSRV_AMT	Global 2 Ending Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global ending loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_END_SALV_RSRV_AMT	Global 2 Ending Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global end salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_END_SUBRO_RSRV_AMT	Global 2 Ending Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global end subrogation reserve amount.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_END_ULAE_RSRV_AMT	Global 2 Ending Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global end unallocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_INCRD_AMT	Global 2 Incurred Amount	NUMBER (14, 3)	This number represents the cost of the second global incurred amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_INCRD_WEXPNS_AMT	Global 2 Incurred With Expenses Amount	NUMBER (14, 3)	This number represents the cost of the second global increased with expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_LEGAL_FEES_AMT	Global 2 Legal Fees Expense Amount	NUMBER (14, 3)	This number represents the cost of the second global legal fees amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_LRSRV_AMT	Global 2 Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_OUT_ADJ_FEES_AMT	Global 2 Outside Adjusting Fees Amount	NUMBER (14, 3)	This number represents the cost of the second global outside adjustment fees amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_PAID_LOSS_AMT	Global 2 Paid Loss Amount	NUMBER (14, 3)	This number represents the cost of the second global paid loss amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_SALV_AMT	Global 2 Salvage Amount	NUMBER (14, 3)	This number represents the cost of the second global salvage amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_SALV_RSRV_AMT	Global 2 Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_SUBRO_AMT	Global 2 Subrogation Amount	NUMBER (14, 3)	This number represents the cost of the second global subrogation amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_SUBRO_RSRV_AMT	Global 2 Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_ULAE_AMT	Global 2 Unallocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of the second global unallocated loss adjusting expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_ULAE_RSRV_AMT	Global 2 Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the second global unallocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_2_UNALLOC_EXPNS_AO_AMT	Global 2 UnAllocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the cost of the second global unallocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_ALAE_AMT	Global 3 Allocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of the third global allocated loss adjusting expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_ALAE_RSRV_AMT	Global 3 Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global allocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_ALLOC_EXPNS_AO_AMT	Global 3 Allocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the cost of the third global allocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_CTD_INCRD_AMT	Global 3 Claim to Date Incurred Amount	NUMBER (14, 3)	This number represents the cost of the third global claims to date incurred amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_CTD_INCRD_WEXPNS_AMT	Global 3 Claim to Date Incurred With Expenses Amount	NUMBER (14, 3)	This number represents the cost of the third global claims to date increased with expense amount.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_DED_LPMT_AMT	Global 3 Deductible Loss Payment Amount	NUMBER (14, 3)	This number represents the cost of the third global deductible loss payment amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_DED_LRSRV_CHANGE_AMT	Global 3 Deductible Loss Reserve Change Amount	NUMBER (14, 3)	This number represents the cost of the third global deductible loss reserve change amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_END_ALAE_RSRV_AMT	Global 3 Ending Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global end allocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_END_DED_LPMT_RSRV_AMT	Global 3 Ending Deductible Loss Payment Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global end deductible loss payment reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_END_LRSRV_AMT	Global 3 Ending Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global ending loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_END_SALV_RSRV_AMT	Global 3 Ending Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global end salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_END_SUBRO_RSRV_AMT	Global 3 Ending Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global end subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_END_ULAE_RSRV_AMT	Global 3 Ending Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global end unallocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_INCRD_AMT	Global 3 Incurred Amount	NUMBER (14, 3)	This number represents the cost of the third global incurred amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_INCRD_WEXPNS_AMT	Global 3 Incurred With Expenses Amount	NUMBER (14, 3)	This number represents the cost of the third global increased with expense amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_LEGAL_FEES_AMT	Global 3 Legal Fees Expense Amount	NUMBER (14, 3)	This number represents the cost of the third global legal fees amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_LRSRV_AMT	Global 3 Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_OUT_ADJ_FEES_AMT	Global 3 Outside Adjusting Fees Amount	NUMBER (14, 3)	This number represents the cost of the third global outside adjustment fees amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_PAID_LOSS_AMT	Global 3 Paid Loss Amount	NUMBER (14, 3)	This number represents the cost of the third global paid loss amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_SALV_AMT	Global 3 Salvage Amount	NUMBER (14, 3)	This number represents the cost of the third global salvage amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_SALV_RSRV_AMT	Global 3 Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_SUBRO_AMT	Global 3 Subrogation Amount	NUMBER (14, 3)	This number represents the cost of the third global subrogation amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_SUBRO_RSRV_AMT	Global 3 Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_ULAE_AMT	Global 3 Unallocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of the third global unallocated loss adjusting expense amount.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_ULAE_RSRV_AMT	Global 3 Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the third global unallocated loss adjusting expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	GLOBAL_3_UNALLOC_EXPNS_AO_AMT	Global 3 UnAllocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the cost of the third global unallocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	GRP_PRG_ID	Group Program Identifier	NUMBER (22, 0)	This system generated number identifies the group program instance.
Datamart	CLM_MTH_SNAP_FACT	INSD_ID	Insured Identifier	NUMBER (22, 0)	This system generated number identifies the insured instance.
Datamart	CLM_MTH_SNAP_FACT	INSUR_CO_ID	Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the insurance company instance in the claim monthly snapshot fact.
Datamart	CLM_MTH_SNAP_FACT	LITG_ID	Litigation Identifier	NUMBER (22, 0)	This system generated number identifies the litigation instance.
Datamart	CLM_MTH_SNAP_FACT	LMT_ID	Limit Identifier	NUMBER (22, 0)	This system generated number identifies the limit instance.
Datamart	CLM_MTH_SNAP_FACT	LOB_FACT_ID	Line Of Business Fact Identifier	NUMBER (22, 0)	This system generated number identifies the line of business fact instance.
Datamart	CLM_MTH_SNAP_FACT	LOB_ID	Line Of Business Identifier	NUMBER (22, 0)	This system generated number identifies the line of business instance.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_ALAE_AMT	Local Allocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of the local allocated loss adjustment expense amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_ALAE_RSRV_AMT	Local Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local allocated loss adjustment expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_ALLOC_EXPNS_AO_AMT	Local Allocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the cost of the local allocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_CTD_INCRD_AMT	Local Claim to Date Incurred Amount	NUMBER (14, 3)	This number represents the cost of the local claims to date incurred amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_CTD_INCRD_WEXPNS_AMT	Local Claim to Date Incurred With Expenses Amount	NUMBER (14, 3)	This number represents the cost of the local claims to date increased with expense amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_DED_LPMT_AMT	Local Deductible Loss Payment Amount	NUMBER (14, 3)	This number represents the cost of the local deductible loss payment amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_DED_LRSRV_CHANGE_AMT	Local Deductible Loss Reserve Change Amount	NUMBER (14, 3)	This number represents the cost of the local deductible loss reserve change amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_END_ALAE_RSRV_AMT	Local Ending Allocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local end allocated loss adjustment expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_END_DED_LPMT_RSRV_AMT	Local Ending Deductible Loss Payment Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local end deductible loss payment reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_END_LRSRV_AMT	Local Ending Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local ending loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_END_SALV_RSRV_AMT	Local Ending Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local end salvage reserve amount.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MTH_SNAP_FACT	LOCAL_END_SUBRO_RSRV_AMT	Local Ending Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local end subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_END_ULAE_RSRV_AMT	Local Ending Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local end unallocated loss adjustment expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_INCRD_AMT	Local Incurred Amount	NUMBER (14, 3)	This number represents the cost of the local incurred amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_INCRD_WEXPNS_AMT	Local Incurred With Expenses Amount	NUMBER (14, 3)	This number represents the cost of the local increased with expense amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_LEGAL_FEES_AMT	Local Legal Fees Expense Amount	NUMBER (14, 3)	This number represents the cost of the local legal fees amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_LRSRV_AMT	Local Loss Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local loss reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_OUT_ADJ_FEES_AMT	Local Outside Adjusting Fees Amount	NUMBER (14, 3)	This number represents the cost of the local outside adjustment fees amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_PAID_LOSS_AMT	Local Paid Loss Amount	NUMBER (14, 3)	This number represents the cost of the local paid loss amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_SALV_AMT	Local Salvage Amount	NUMBER (14, 3)	This number represents the cost of the local salvage amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_SALV_RSRV_AMT	Local Salvage Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local salvage reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_SUBRO_AMT	Local Subrogation Amount	NUMBER (14, 3)	This number represents the cost of the local subrogation amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_SUBRO_RSRV_AMT	Local Subrogation Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local subrogation reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_ULAE_AMT	Local Unallocated Loss Adjustment Expense Amount	NUMBER (14, 3)	This number represents the cost of the local unallocated loss adjustment expense amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_ULAE_RSRV_AMT	Local Unallocated Loss Adjustment Expense Reserve Amount	NUMBER (14, 3)	This number represents the cost of the local unallocated loss adjustment expense reserve amount.
Datamart	CLM_MTH_SNAP_FACT	LOCAL_UNALLOC_EXPNS_AO_AMT	Local UnAllocated Expense Adjusting and Other Amount	NUMBER (14, 3)	This number represents the cost of the local unallocated expense approving official amount.
Datamart	CLM_MTH_SNAP_FACT	OPENED_CLM_NAT_KEY	Opened Claim Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the opened claim.
Datamart	CLM_MTH_SNAP_FACT	PARENT_INSUR_CO_ID	Parent Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the parent insurance company instance.
Datamart	CLM_MTH_SNAP_FACT	PLCY_ID	Policy Identifier	NUMBER (22, 0)	This system generated number identifies the policy instance.
Datamart	CLM_MTH_SNAP_FACT	PRODR_ID	Producer Identifier	NUMBER (22, 0)	This system generated number identifies the producer instance.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_MTH_SNAP_FACT	REINS_CNTRCT_ID	Reinsurance Contract Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance contract instance.
Datamart	CLM_MTH_SNAP_FACT	REINS_CO_ID	Reinsurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance company instance.
Datamart	CLM_MTH_SNAP_FACT	SUB_PRODR_ID	Sub Producer Identifier	NUMBER (22, 0)	This system generated number identifies the sub-producer instance.
Datamart	CLM_MTH_SNAP_FACT	SUPPLIER_ID	Supplier Identifier	NUMBER (22, 0)	This system generated number identifies the supplier instance.
Datamart	CLM_MTH_SNAP_FACT	SYS_PROC_DT	System Process Date	DATE	This calendar date represents when the system processed the claim monthly snapshot fact table.
Datamart	CLM_MTH_SNAP_FACT	UW_ASST_ID	Underwriting Assistant Identifier	NUMBER (22, 0)	This system generated number identifies the underwriting assistant instance.
Datamart	CLM_MTH_SNAP_FACT	UW_ID	Underwriter Identifier	NUMBER (22, 0)	This system generated number identifies the underwriter instance.
Datamart	CLM_TRANS_CD_DIM	ALLOC_EXPNS_TYP	Allocation Expense Type	VARCHAR2(60)	This value identifies the allocation expense. This expense represents the item or category against which expenses are applied.
Datamart	CLM_TRANS_CD_DIM	AVG_EXPNS_RSRV_CD	Average Expense Reserve Code	VARCHAR2(60)	This system code identifies the average expense reserve. This reserve is the average reserve set in the claim transaction expenses.
Datamart	CLM_TRANS_CD_DIM	AVG_RSRV_CD	Average Reserve Code	VARCHAR2(60)	This system code identifies the average reserve set.
Datamart	CLM_TRANS_CD_DIM	CLM_TRANS_CATG_CD	Claim Transaction Category Code	VARCHAR2(60)	This system code represents what type of loss activity occurred.
Datamart	CLM_TRANS_CD_DIM	CLM_TRANS_CD	Claim Transaction Code	VARCHAR2(60)	This system code represents what type of loss activity occurred.
Datamart	CLM_TRANS_CD_DIM	CLM_TRANS_CD_ID	Claim Transaction Code Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction code instance.
Datamart	CLM_TRANS_CD_DIM	DIRECT_CEDED_ASSUMED	Direct or Ceded or Assumed	VARCHAR2(60)	This value represents the indicator that identifies if a loss is paid internally, transferred to a reinsurer, or assumed.
Datamart	CLM_TRANS_CD_DIM	SYS_CLM_TRANS_CD	System Claim Transaction Code	VARCHAR2(60)	This system code identifies the system claim transaction.
Datamart	CLM_TRANS_FACT	BILL_ACCT_ID	Billing Account Identifier	NUMBER (22, 0)	This system generated number identifies the billing account instance.
Datamart	CLM_TRANS_FACT	BILL_HRLY_RATE	Billable Hourly Rate	NUMBER (6, 5)	This number represents the charge applicable or each hour for a service associated with a claims transaction.
Datamart	CLM_TRANS_FACT	BOOK_DT_ID	Book Date Identifier	DATE	This calendar date represents the book date.
Datamart	CLM_TRANS_FACT	CAT_ID	Catastrophe Identifier	NUMBER (22, 0)	This system generated number identifies the catastrophe.
Datamart	CLM_TRANS_FACT	CLASS_ID	Class Identifier	NUMBER (22, 0)	This system generated number identifies the class.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_TRANS_FACT	CLM_ADJ_ID	Claim Adjuster Identifier	NUMBER (22, 0)	This system generated number identifies the claim adjuster instance.
Datamart	CLM_TRANS_FACT	CLM_EXAMR_ID	Claim Examiner Identifier	NUMBER (22, 0)	This system generated number identifies the claim examiner instance.
Datamart	CLM_TRANS_FACT	CLM_ID	Claim Identifier	NUMBER (22, 0)	This system generated number identifies the claim instance.
Datamart	CLM_TRANS_FACT	CLM_MGR_ID	Claim Manager Identifier	NUMBER (22, 0)	This system generated number identifies the claim manager instance.
Datamart	CLM_TRANS_FACT	CLM_TRANS_AMT	Claim Transaction Amount	NUMBER (14, 3)	This number represents the actual amount of a claim transaction.
Datamart	CLM_TRANS_FACT	CLM_TRANS_CD_ID	Claim Transaction Code Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction code instance.
Datamart	CLM_TRANS_FACT	CLMT_ID	Claimant Identifier	NUMBER (22, 0)	This system generated number identifies the claimant instance.
Datamart	CLM_TRANS_FACT	COVRG_ID	Coverage Identifier	NUMBER (22, 0)	This system generated number identifies coverage instance in the claim transaction fact.
Datamart	CLM_TRANS_FACT	COVRG_STATUS_ID	Coverage Status Identifier	NUMBER (22, 0)	This system generated number identifies coverage status instance in the claim transaction fact.
Datamart	CLM_TRANS_FACT	DC_ID	Distribution Channel Identifier	NUMBER (22, 0)	This system generated number identifies the distribution channel instance.
Datamart	CLM_TRANS_FACT	DED_ID	Deductible Identifier	NUMBER (22, 0)	This system generated number identifies the deductible instance.
Datamart	CLM_TRANS_FACT	DOC_CURR_CD	Document Currency Code	VARCHAR2(25)	This system code identifies document currency.
Datamart	CLM_TRANS_FACT	FEAT_ID	Feature Identifier	NUMBER (22, 0)	This system generated number identifies the claim feature instance.
Datamart	CLM_TRANS_FACT	FEAT_STATUS_ID	Feature Status Identifier	NUMBER (22, 0)	This system generated number identifies the claim feature status instance.
Datamart	CLM_TRANS_FACT	GLOBAL_CURR_RATE_1	Global Currency Rate 1	NUMBER (22, 7)	This number represents the first global currency rate.
Datamart	CLM_TRANS_FACT	GLOBAL_CURR_RATE_2	Global Currency Rate 2	NUMBER (22, 7)	This number represents the second global currency rate.
Datamart	CLM_TRANS_FACT	GLOBAL_CURR_RATE_3	Global Currency Rate 3	NUMBER (22, 7)	This number represents the third global currency rate.
Datamart	CLM_TRANS_FACT	GRP_PRG_ID	Group Program Identifier	NUMBER (22, 0)	This system generated number identifies the group program instance.
Datamart	CLM_TRANS_FACT	INSD_ID	Insured Identifier	NUMBER (22, 0)	This system generated number identifies the insured instance in the claim transaction.
Datamart	CLM_TRANS_FACT	INSUR_CO_ID	Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the insurance company instance in the claim monthly snapshot fact.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLM_TRANS_FACT	LITG_ID	Litigation Identifier	NUMBER (22, 0)	This system generated number identifies the litigation instance.
Datamart	CLM_TRANS_FACT	LMT_ID	Limit Identifier	NUMBER (22, 0)	This system generated number identifies the limit instance.
Datamart	CLM_TRANS_FACT	LOB_FACT_ID	Line Of Business Fact Identifier	NUMBER (22, 0)	This system generated number identifies the line of business fact instance in the claim transaction.
Datamart	CLM_TRANS_FACT	LOB_ID	Line Of Business Identifier	NUMBER (22, 0)	This system generated number identifies the line of business instance.
Datamart	CLM_TRANS_FACT	LOCAL_CURR_RATE	Local Currency Rate	NUMBER (22, 7)	This number represents the local currency rate.
Datamart	CLM_TRANS_FACT	NUM_HRS_BILLED	Number Of Hours Billed	NUMBER (22, 0)	This number represents the count of hours billed to a claims transaction fact table.
Datamart	CLM_TRANS_FACT	PARENT_INSUR_CO_ID	Parent Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the parent insurance company instance.
Datamart	CLM_TRANS_FACT	PLCY_ID	Policy Identifier	NUMBER (22, 0)	This system generated number identifies the policy instance.
Datamart	CLM_TRANS_FACT	PRODR_ID	Producer Identifier	NUMBER (22, 0)	This system generated number identifies the producer instance.
Datamart	CLM_TRANS_FACT	REINS_CNTRCT_ID	Reinsurance Contract Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance contract instance.
Datamart	CLM_TRANS_FACT	REINS_CO_ID	Reinsurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance company instance.
Datamart	CLM_TRANS_FACT	SRC_SYS_PROC_DT_ID	Source System Process Date Identifier	DATE	This calendar date represents the system source process date instance.
Datamart	CLM_TRANS_FACT	SUB_PRODR_ID	Sub Producer Identifier	NUMBER (22, 0)	This system generated number identifies the sub-producer instance.
Datamart	CLM_TRANS_FACT	SUPPLIER_ID	Supplier Identifier	NUMBER (22, 0)	This system generated number identifies the supplier instance.
Datamart	CLM_TRANS_FACT	SYS_PROC_DT	System Process Date	DATE	This calendar date represents when the system processed the claim transaction fact table.
Datamart	CLM_TRANS_FACT	TRANS_EFF_DT_ID	Transaction Effective Date Identifier	DATE	This calendar date represents when a claim transaction fact is effective.
Datamart	CLM_TRANS_FACT	UW_ASST_ID	Underwriting Assistant Identifier	NUMBER (22, 0)	This system generated number identifies the underwriting assistant instance.
Datamart	CLM_TRANS_FACT	UW_ID	Underwriter Identifier	NUMBER (22, 0)	This system generated number identifies the underwriter instance.
Datamart	CLMT_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claimant applies.
Datamart	CLMT_DIM	CLMT_BIRTH_DT_ID	Claimant Birth Date Identifier	DATE	This calendar date represents the claimant date of birth.
Datamart	CLMT_DIM	CLMT_BUS_START_DT_ID	Claimant Business Start Date Identifier	DATE	This calendar date represents the claimant business start date.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLMT_DIM	CLMT_CNTCT_DESC	Claimant Contact Description	VARCHAR2(60)	This value describes claimant contact.
Datamart	CLMT_DIM	CLMT_CNTCT_TYP	Claimant Contact Type	VARCHAR2(60)	This value the claimant's method of contact.
Datamart	CLMT_DIM	CLMT_CNTCT_UDF_1	Claimant Contact User Defined Field 1	VARCHAR2(60)	This value describes the first claimant contact user defined field.
Datamart	CLMT_DIM	CLMT_CNTCT_UDF_2	Claimant Contact User Defined Field 2	VARCHAR2(60)	This value describes the second claimant contact user defined field.
Datamart	CLMT_DIM	CLMT_CNTCT_UDF_3	Claimant Contact User Defined Field 3	VARCHAR2(60)	This value describes the third claimant contact user defined field.
Datamart	CLMT_DIM	CLMT_CNTCT_UDF_4	Claimant Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth claimant contact user defined field.
Datamart	CLMT_DIM	CLMT_CNTCT_UDF_5	Claimant Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth claimant contact user defined field.
Datamart	CLMT_DIM	CLMT_CNTY	Claimant County	VARCHAR2(60)	This value identifies the county where claimant is located.
Datamart	CLMT_DIM	CLMT_CTRY	Claimant Country	VARCHAR2(60)	This value identifies the country where claimant is located.
Datamart	CLMT_DIM	CLMT_CTY	Claimant City	VARCHAR2(32)	This value identifies the city where claimant is located.
Datamart	CLMT_DIM	CLMT_DBA	Claimant Doing Business As	VARCHAR2(170)	This value represents the claimant's operating business name.
Datamart	CLMT_DIM	CLMT_DSTRCT	Claimant District	VARCHAR2(60)	This value represents the district where claimant is located.
Datamart	CLMT_DIM	CLMT_GENDER	Claimant Gender	VARCHAR2(60)	This value represents the gender (male or female) of the claimant.
Datamart	CLMT_DIM	CLMT_GEOG_BNDRY_UDF_1	Claimant Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first claimant geographic boundary user defined field.
Datamart	CLMT_DIM	CLMT_GEOG_BNDRY_UDF_2	Claimant Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second claimant geographic boundary user defined field.
Datamart	CLMT_DIM	CLMT_GEOG_BNDRY_UDF_3	Claimant Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third claimant geographic boundary user defined field.
Datamart	CLMT_DIM	CLMT_GEOG_BNDRY_UDF_4	Claimant Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth claimant geographic boundary user defined field.
Datamart	CLMT_DIM	CLMT_GEOG_BNDRY_UDF_5	Claimant Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth claimant geographic boundary user defined field.
Datamart	CLMT_DIM	CLMT_GOVT_ID_NUM	Claimant Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the claimant. For example, in the USA: SSN or FEIN.
Datamart	CLMT_DIM	CLMT_ID	Claimant Identifier	NUMBER (22, 0)	This system generated number identifies the claimant instance.
Datamart	CLMT_DIM	CLMT_LATITUDE	Claimant Latitude	VARCHAR2(11)	This value represents the latitude location of claimant.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLMT_DIM	CLMT_LONGITUDE	Claimant Longitude	VARCHAR2(11)	This value represents the longitude location of claimant.
Datamart	CLMT_DIM	CLMT_MARITAL_STATUS	Claimant Marital Status	VARCHAR2(60)	The present marital condition (single, married, divorced, widowed) of the claimant.
Datamart	CLMT_DIM	CLMT_NAICS_CD	Claimant North American Industry Classification System Code	VARCHAR2(60)	This value represents the North America Industry Class (NAICS) code assigned to claimant.
Datamart	CLMT_DIM	CLMT_NAT_KEY	Claimant Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claimant.
Datamart	CLMT_DIM	CLMT_NM	Claimant Name	VARCHAR2(170)	This value represents the name of the claimant associated with a claim.
Datamart	CLMT_DIM	CLMT_NOB	Claimant Nature of Business	VARCHAR2(60)	This value represents the type or category of the business activities done by the claimant.
Datamart	CLMT_DIM	CLMT_NUM_EMP	Claimant Number of Employees	NUMBER (22, 0)	This number represents the count of people employed by claimant.
Datamart	CLMT_DIM	CLMT_ORG_UDF_1	Claimant Organization User Defined Field 1	VARCHAR2(60)	This value describes the first claimant organization user defined field.
Datamart	CLMT_DIM	CLMT_ORG_UDF_2	Claimant Organization User Defined Field 2	VARCHAR2(60)	This value describes the second claimant organization user defined field.
Datamart	CLMT_DIM	CLMT_ORG_UDF_3	Claimant Organization User Defined Field 3	VARCHAR2(60)	This value describes the third claimant organization user defined field.
Datamart	CLMT_DIM	CLMT_ORG_UDF_4	Claimant Organization User Defined Field 4	VARCHAR2(60)	This value describes the fourth claimant organization user defined field.
Datamart	CLMT_DIM	CLMT_ORG_UDF_5	Claimant Organization User Defined Field 5	VARCHAR2(60)	This value describes the fifth claimant organization user defined field.
Datamart	CLMT_DIM	CLMT_PARTY_UDF_1	Claimant Party User Defined Field 1	VARCHAR2(60)	This value describes the first claimant party user defined field.
Datamart	CLMT_DIM	CLMT_PARTY_UDF_2	Claimant Party User Defined Field 2	VARCHAR2(60)	This value describes the second claimant party user defined field.
Datamart	CLMT_DIM	CLMT_PARTY_UDF_3	Claimant Party User Defined Field 3	VARCHAR2(60)	This value describes the third claimant party user defined field.
Datamart	CLMT_DIM	CLMT_PARTY_UDF_4	Claimant Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth claimant party user defined field.
Datamart	CLMT_DIM	CLMT_PARTY_UDF_5	Claimant Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth claimant party user defined field.
Datamart	CLMT_DIM	CLMT_PERS_UDF_1	Claimant Person User Defined Field 1	VARCHAR2(60)	This value describes the first claimant person user defined field.
Datamart	CLMT_DIM	CLMT_PERS_UDF_2	Claimant Person User Defined Field 2	VARCHAR2(60)	This value describes the second claimant person user defined field.
Datamart	CLMT_DIM	CLMT_PERS_UDF_3	Claimant Person User Defined Field 3	VARCHAR2(60)	This value describes the third claimant person user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CLMT_DIM	CLMT_PERS_UDF_4	Claimant Person User Defined Field 4	VARCHAR2(60)	This value describes the fourth claimant person user defined field.
Datamart	CLMT_DIM	CLMT_PERS_UDF_5	Claimant Person User Defined Field 5	VARCHAR2(60)	This value describes the fifth claimant person user defined field.
Datamart	CLMT_DIM	CLMT_PRES_EMPLMT_START_YR	Claimant Present Employment Start Year	CHAR(4)	This value represents the calendar year that the claimant began working for their current employer.
Datamart	CLMT_DIM	CLMT_PSTL_CD	Claimant Postal Code	VARCHAR2(11)	This value represents the claimant's full postal zip code as defined by company specifications.
Datamart	CLMT_DIM	CLMT_PSTL_CD_PRFX	Claimant Postal Code Prefix	VARCHAR2(3)	This value represents the claimant's first 3 digits of a 5 digit geopolitical zip code.
Datamart	CLMT_DIM	CLMT_PSTL_SUB_CD	Claimant Postal Sub Code	VARCHAR2(4)	This value represents the claimant's ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	CLMT_DIM	CLMT_REGION	Claimant Region	VARCHAR2(60)	This value represents the geographic region where claimant is located.
Datamart	CLMT_DIM	CLMT_SIC_CD	Claimant Standard Industrial Classification Code	VARCHAR2(60)	This system code represents the SIC code assigned to the claimant.The Standard industrial Classification (SIC) code is an industry code that identifies the classification of business activity.
Datamart	CLMT_DIM	CLMT_STATE	Claimant State	VARCHAR2(60)	This value identifies the state where claimant is located.
Datamart	CLMT_DIM	CLMT_TAX_LOC_ID	Claimant Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier.
Datamart	CLMT_DIM	CLMT_TERR	Claimant Territory	VARCHAR2(60)	This value represents the territory where the claimant is located.
Datamart	CLMT_DIM	CLMT_TYP	Claimant Type	VARCHAR2(60)	This value represents the attributes of the claimant.
Datamart	CLMT_DIM	CLMT_UDF_1	Claimant User Defined Field 1	VARCHAR2(60)	This value describes the first claimant user defined field.
Datamart	CLMT_DIM	CLMT_UDF_2	Claimant User Defined Field 2	VARCHAR2(60)	This value describes the second claimant user defined field.
Datamart	CLMT_DIM	CLMT_UDF_3	Claimant User Defined Field 3	VARCHAR2(60)	This value describes the third claimant user defined field.
Datamart	CLMT_DIM	CLMT_UDF_4	Claimant User Defined Field 4	VARCHAR2(60)	This value describes the fourth claimant user defined field.
Datamart	CLMT_DIM	CLMT_UDF_5	Claimant User Defined Field 5	VARCHAR2(60)	This value describes the fifth claimant user defined field.
Datamart	CLMT_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claimant is currently applicable.
Datamart	CLMT_DIM	END_DT	End Date	DATE	This date represents the calendar date that the claimant is no longer valid.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	COVRG_DIM	ANNU_STMT_LINE	Annual Statement Line	VARCHAR2(60)	This value represents the description that indicates in which line of the annual statement a transaction belongs.
Datamart	COVRG_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage applies.
Datamart	COVRG_DIM	BUREAU_RPT_PLAN_CD	Bureau Report Plan Code	VARCHAR2(60)	This system code indicates the statistical plan code used for bureau reporting.
Datamart	COVRG_DIM	COVRG_CATG	Coverage Category	VARCHAR2(60)	This value represents the way coverages are grouped within a line of business.
Datamart	COVRG_DIM	COVRG_DESC	Coverage Description	VARCHAR2(60)	This value describes a single coverage afforded on the insurance policy.
Datamart	COVRG_DIM	COVRG_ID	Coverage Identifier	NUMBER (22, 0)	This system generated number identifies coverage instance.
Datamart	COVRG_DIM	COVRG_NAT_KEY	Coverage Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the coverage.
Datamart	COVRG_DIM	COVRG_PART	Coverage Part	VARCHAR2(60)	This value describes the portion of a risk to which a coverage applies.
Datamart	COVRG_DIM	COVRG_UDF_1	Coverage User Defined Field 1	VARCHAR2(60)	This value describes the first coverage user defined field.
Datamart	COVRG_DIM	COVRG_UDF_2	Coverage User Defined Field 2	VARCHAR2(60)	This value describes the second coverage user defined field.
Datamart	COVRG_DIM	COVRG_UDF_3	Coverage User Defined Field 3	VARCHAR2(60)	This value describes the third coverage user defined field.
Datamart	COVRG_DIM	COVRG_UDF_4	Coverage User Defined Field 4	VARCHAR2(60)	This value describes the fourth coverage user defined field.
Datamart	COVRG_DIM	COVRG_UDF_5	Coverage User Defined Field 5	VARCHAR2(60)	This value describes the fifth coverage user defined field.
Datamart	COVRG_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the coverage is currently applicable.
Datamart	COVRG_DIM	END_DT	End Date	DATE	This calendar date represents when the coverage is no longer valid.
Datamart	COVRG_DIM	SCND_COVRG_DESC	Second Coverage Description	VARCHAR2(60)	This value represents the client defined code that will further breakdown the type of coverage afforded on the insurance policy.
Datamart	COVRG_DIM	STAT_PLAN_CD	Statistical Plan Code	VARCHAR2(60)	This system code identifies the statistical plan for coverage.
Datamart	COVRG_STATUS_DIM	COVRG_EFF_DT	Coverage Effective Date	DATE	This date represents the calendar date of the policy coverage begins.
Datamart	COVRG_STATUS_DIM	COVRG_EXPR_DT	Coverage Expiration Date	DATE	This date represents the calendar date of the policy coverage ends.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	COVRG_STATUS_DIM	COVRG_STATUS_ID	Coverage Status Identifier	NUMBER (22, 0)	This system generated number identifies coverage status instance.
Datamart	COVRG_STATUS_DIM	COVRG_STATUS_UDF_1	Coverage Status User Defined Field 1	VARCHAR2(60)	This value describes the first coverage status user defined field.
Datamart	COVRG_STATUS_DIM	COVRG_STATUS_UDF_2	Coverage Status User Defined Field 2	VARCHAR2(60)	This value describes the second coverage status user defined field.
Datamart	COVRG_STATUS_DIM	COVRG_STATUS_UDF_3	Coverage Status User Defined Field 3	VARCHAR2(60)	This value describes the third coverage status user defined field.
Datamart	COVRG_STATUS_DIM	COVRG_STATUS_UDF_4	Coverage Status User Defined Field 4	VARCHAR2(60)	This value describes the fourth coverage status user defined field.
Datamart	COVRG_STATUS_DIM	COVRG_STATUS_UDF_5	Coverage Status User Defined Field 5	VARCHAR2(60)	This value describes the fifth coverage status user defined field.
Datamart	CP_BLDG_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage.
Datamart	CP_BLDG_DIM	CP_BLDG_ALUMINUM_WIRG_FLG	Commercial Property Building Aluminum Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of aluminum wiring.
Datamart	CP_BLDG_DIM	CP_BLDG_AREA	Commercial Property Building Area	NUMBER (14, 3)	This number represents the area measurement of floor contained.
Datamart	CP_BLDG_DIM	CP_BLDG_BLDG_USE	Commercial Property Building Building Use	VARCHAR2(60)	This value represents the classification detailing the activities occurring at a building.
Datamart	CP_BLDG_DIM	CP_BLDG_BSMT_AREA	Commercial Property Building Basement Area	NUMBER (14, 3)	This number represents the total area measurement of all the basements in this building.
Datamart	CP_BLDG_DIM	CP_BLDG_BURGLAR_MONITOR_TYP	Commercial Property Building Burglar Monitoring Type	VARCHAR2(60)	This value describes the attributes of a burglar alarm in use.
Datamart	CP_BLDG_DIM	CP_BLDG_CIRCUIT_BREAKERS_FLG	Commercial Property Building Circuit Breakers Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of circuit breakers.
Datamart	CP_BLDG_DIM	CP_BLDG_COND	Commercial Property Building Condition	VARCHAR2(60)	This value represents the classification detailing the maintenance condition of a building.
Datamart	CP_BLDG_DIM	CP_BLDG_CONST_TYP	Commercial Property Building Construction Type	VARCHAR2(60)	This value describes the building's primary exterior construction materials.
Datamart	CP_BLDG_DIM	CP_BLDG_COPPER_WIRG_FLG	Commercial Property Building Copper Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of copper wiring.
Datamart	CP_BLDG_DIM	CP_BLDG_CTY_LMTS_CD	Commercial Property Building City Limits Code	VARCHAR2(60)	This system code describes if a building is located within or outside city limit boundary.
Datamart	CP_BLDG_DIM	CP_BLDG_CUR_YR_PROP_INCOME	Commercial Property Building Current Year Property Income	NUMBER (14, 3)	This number represents the total amount of income from activities at the insured building during the current year.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CP_BLDG_DIM	CP_BLDG_DIST_TO_FIRE_HYDRANT	Commercial Property Building Distance to Fire Hydrant	NUMBER (14, 3)	This number represents the distance units (feet/ meters) from building to nearest fire hydrant location.
Datamart	CP_BLDG_DIM	CP_BLDG_DIST_TO_FIRE_STATION	Commercial Property Building Distance to Fire Station	NUMBER (14, 3)	This number represents the distance units (miles/ kilometers) from building to nearest fire station location.
Datamart	CP_BLDG_DIM	CP_BLDG_ELEC_UPDT_TYP	Commercial Property Building Electrical Update Type	VARCHAR2(60)	This value represents the classification that describes changes to electrical system after the building's original construction.
Datamart	CP_BLDG_DIM	CP_BLDG_ELEC_UPDT_YR	Commercial Property Building Electrical Update Year	CHAR(4)	This value represents the calendar year of the last update to the building electrical system.
Datamart	CP_BLDG_DIM	CP_BLDG_FIRE_DSTRCT	Commercial Property Building Fire District	VARCHAR2(60)	This value represents the fire department response district assigned to a building location.
Datamart	CP_BLDG_DIM	CP_BLDG_FIRE_EXTINGUISHER_FLG	Commercial Property Building Fire Extinguisher Flag	CHAR(1)	This value represents based on the yes/no indicator that a fire extinguisher is present at covered building.
Datamart	CP_BLDG_DIM	CP_BLDG_FIRE_MONITOR_TYP	Commercial Property Building Fire Monitoring Type	VARCHAR2(60)	This value represents the attributes of fire monitoring alarm used at building.
Datamart	CP_BLDG_DIM	CP_BLDG_FIRE_PROT_CLASS	Commercial Property Building Fire Protection Class	VARCHAR2(60)	This system code describes the fire protection services available at building location.
Datamart	CP_BLDG_DIM	CP_BLDG_FNDN_TYP	Commercial Property Building Foundation Type	VARCHAR2(60)	This value represents the construction method used to construct building foundation.
Datamart	CP_BLDG_DIM	CP_BLDG_FUSES_FLG	Commercial Property Building Fuses Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fuses.
Datamart	CP_BLDG_DIM	CP_BLDG_GAS_UPDT_TYP	Commercial Property Building Gas Update Type	VARCHAR2(60)	This value represents the calendar year of last update of the building gas system.
Datamart	CP_BLDG_DIM	CP_BLDG_GAS_UPDT_YR	Commercial Property Building Gas Update Year	CHAR(4)	This value represents the calendar year of the last update to the building gas system.
Datamart	CP_BLDG_DIM	CP_BLDG_GEOG_BNDRY_UDF_1	Commercial Property Building Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first commercial building geographic boundary user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_GEOG_BNDRY_UDF_2	Commercial Property Building Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second commercial building geographic boundary user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_GEOG_BNDRY_UDF_3	Commercial Property Building Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third commercial building geographic boundary user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_GEOG_BNDRY_UDF_4	Commercial Property Building Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth commercial building geographic boundary user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_GEOG_BNDRY_UDF_5	Commercial Property Building Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth commercial building geographic boundary user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_HEAT_UPDT_TYP	Commercial Property Building Heating Update Type	VARCHAR2(60)	This value represents the changes to heating system after the building's original construction.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CP_BLDG_DIM	CP_BLDG_HEAT_UPDT_YR	Commercial Property Building Heating Update Year	CHAR(4)	This value represents the calendar year of the last update to the building heating system.
Datamart	CP_BLDG_DIM	CP_BLDG_ID	Commercial Property Building Identifier	NUMBER (22, 0)	This system generated number identifies the property instance.
Datamart	CP_BLDG_DIM	CP_BLDG_KNOB_TUBE_WIRG_FLG	Commercial Property Building Knob and Tube Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of knob and tube wiring.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_CNTY	Commercial Property Building Location County	VARCHAR2(60)	This value identifies the county where building is located.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_CTRY	Commercial Property Building Location Country	VARCHAR2(60)	This value identifies the country where building is located.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_CTY	Commercial Property Building Location City	VARCHAR2(32)	This value identifies the city where building is located.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_DSTRCT	Commercial Property Building Location District	VARCHAR2(60)	This value represents the district where building is located.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_LATITUDE	Commercial Property Building Location Latitude	VARCHAR2(11)	This value represents the latitude where building is located.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_LONGITUDE	Commercial Property Building Location Longitude	VARCHAR2(11)	This value represents the longitude where building is located.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_NUM	Commercial Property Building Location Number	NUMBER (22, 0)	This number identifies the commercial property building (also known as commercial property building) location number.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_PSTL_CD	Commercial Property Building Location Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_PSTL_CD_PRFX	Commercial Property Building Location Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_PSTL_SUB_CD	Commercial Property Building Location Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_REGION	Commercial Property Building Location Region	VARCHAR2(60)	This value identifies the geographic region associated with building location.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_STATE	Commercial Property Building Location State	VARCHAR2(60)	This value identifies the state associated with building location.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_TAX_LOC_ID	Commercial Property Building Location Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier of the building location.
Datamart	CP_BLDG_DIM	CP_BLDG_LOC_TERR	Commercial Property Building Location Territory	VARCHAR2(60)	This value represents the territory where building is located.
Datamart	CP_BLDG_DIM	CP_BLDG_MKT_VAL	Commercial Property Building Market Value	NUMBER (14, 3)	This number represents the average price of similar buildings recently sold in same real estate market.
Datamart	CP_BLDG_DIM	CP_BLDG_NAT_KEY	Commercial Property Building Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the building.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CP_BLDG_DIM	CP_BLDG_NM_OF_OWNER	Commercial Property Building Number of Owners	VARCHAR2(170)	This value represents the total count of owners of the building.
Datamart	CP_BLDG_DIM	CP_BLDG_NUM_COML_OCCUPANTS	Commercial Property Building Number of Commercial Occupants	NUMBER (22, 0)	This number represents the count of commercial occupants contained in all units of the building.
Datamart	CP_BLDG_DIM	CP_BLDG_NUM_ELEC_SYS_AMPS	Commercial Property Building Number of Electrical System Amps	NUMBER (22, 0)	This number represents the electrical current capacity of electrical system.
Datamart	CP_BLDG_DIM	CP_BLDG_NUM_FMLYS	Commercial Property Building Number of Families	NUMBER (22, 0)	This number represents the count of individual family units in single building. For example, a duplex would have 2 families.
Datamart	CP_BLDG_DIM	CP_BLDG_NUM_STORIES	Commercial Property Building Number of Stories	NUMBER (22, 0)	This number represents the count of building floor levels contained.
Datamart	CP_BLDG_DIM	CP_BLDG_OCPCY_TYP	Commercial Property Building Occupancy Type	VARCHAR2(60)	This value represents the attributes of occupants of the building. For example, owner and tenant occupants.
Datamart	CP_BLDG_DIM	CP_BLDG_PLUMBING_UPDT_TYP	Commercial Property Building Plumbing Update Type	VARCHAR2(60)	This value represents the classification detailing changes to plumbing system after the building's original construction.
Datamart	CP_BLDG_DIM	CP_BLDG_PLUMBING_UPDT_YR	Commercial Property Building Plumbing Update Year	CHAR(4)	This value represents the calendar year of the last update to the building plumbing system.
Datamart	CP_BLDG_DIM	CP_BLDG_PRIM_HEAT_TYP	Commercial Property Building Primary Heating Type	VARCHAR2(60)	This value represents the classification of the building's primary source of heat.
Datamart	CP_BLDG_DIM	CP_BLDG_PROP_LOT_SIZE	Commercial Property Building Property Lot Size	NUMBER (14, 3)	This number represents the total area measurement of the land with.
Datamart	CP_BLDG_DIM	CP_BLDG_PURCH_DT_ID	Commercial Property Building Purchase Date Identifier	DATE	This calendar date represents building purchase date instance.
Datamart	CP_BLDG_DIM	CP_BLDG_PURCH_PRICE	Commercial Property Building Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when commercial building was purchased.
Datamart	CP_BLDG_DIM	CP_BLDG_ROOF_MATL	Commercial Property Building Roofing Material	VARCHAR2(60)	This value represents the roofing material used on the building roof.
Datamart	CP_BLDG_DIM	CP_BLDG_ROOF_UPDT_TYP	Commercial Property Building Roofing Update Type	VARCHAR2(60)	This value represents the classification detailing changes to roofing materials after the building's original construction.
Datamart	CP_BLDG_DIM	CP_BLDG_ROOF_UPDT_YR	Commercial Property Building Roofing Update Year	CHAR(4)	This value represents the calendar year of the last update to the building roofing materials.
Datamart	CP_BLDG_DIM	CP_BLDG_SCND_HEAT_TYP	Commercial Property Building Secondary Heat Type	VARCHAR2(60)	This value represents the classification of the secondary source of heat for commercial building.
Datamart	CP_BLDG_DIM	CP_BLDG_TYP	Commercial Property Building Type	VARCHAR2(60)	This value represents the classification that identifies the building unit construction. For example, single-family, multi-family, warehouse, etc.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	CP_BLDG_DIM	CP_BLDG_UDF_1	Commercial Property Building User Defined Field 1	VARCHAR2(60)	This value describes the first commercial building user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_UDF_2	Commercial Property Building User Defined Field 2	VARCHAR2(60)	This value describes the second commercial building user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_UDF_3	Commercial Property Building User Defined Field 3	VARCHAR2(60)	This value describes the third commercial building user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_UDF_4	Commercial Property Building User Defined Field 4	VARCHAR2(60)	This value describes the fourth commercial building user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_UDF_5	Commercial Property Building User Defined Field 5	VARCHAR2(60)	This value describes the fifth commercial building user defined field.
Datamart	CP_BLDG_DIM	CP_BLDG_UNDER_CONST_TYP	Commercial Property Building Under Construction Type	VARCHAR2(60)	This system code indicates active construction activities on the building.
Datamart	CP_BLDG_DIM	CP_BLDG_WIRG_UPDT_TYP	Commercial Property Building Wiring Update Type	VARCHAR2(60)	This value represents the classification detailing changes to wiring system after the building's original construction.
Datamart	CP_BLDG_DIM	CP_BLDG_WIRG_UPDT_YR	Commercial Property Building Wiring Update Year	CHAR(4)	This value represents the calendar year of the last update to the building wiring system.
Datamart	CP_BLDG_DIM	CP_BLDG_YR_BUILT	Commercial Property Building Year Built	CHAR(4)	This value represents the calendar year that commercial property building (also known as commercial property building) was constructed.
Datamart	CP_BLDG_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the commercial property building (also known as commercial property building) is currently included in policy coverages.
Datamart	CP_BLDG_DIM	END_DT	End Date	DATE	This calendar date represents when the building is no longer included in policy coverages.
Datamart	CP_FACT	CP_BLDG_ID	Commercial Property Building Identifier	NUMBER (22, 0)	This system generated number identifies the commercial property building (also known as commercial property building) instance.
Datamart	CP_FACT	CP_FACT_ID	Commercial Property Fact Identifier	NUMBER (22, 0)	This system generated number identifies the commercial property fact instance.
Datamart	DC_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the distribution channel applies.
Datamart	DC_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the distribution channel is currently applicable.
Datamart	DC_DIM	DC_ID	Distribution Channel Identifier	NUMBER (22, 0)	This system generated number identifies the distribution channel instance.
Datamart	DC_DIM	DC_NAT_KEY	Distribution Channel Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the distribution channel.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	DC_DIM	DC_NM	Distribution Channel Name	VARCHAR2(60)	This value represents the full name of the distribution channel.
Datamart	DC_DIM	DC_NUM	Distribution Channel Number	VARCHAR2(10)	This value represents the number or other identifier assigned to the distribution channel.
Datamart	DC_DIM	DC_TYP	Distribution Channel Type	VARCHAR2(60)	This value represents the classification of the activities of a distribution channel.
Datamart	DC_DIM	DC_UDF_1	Distribution Channel User Defined Field 1	VARCHAR2(60)	This value describes the first distribution channel user defined field.
Datamart	DC_DIM	DC_UDF_2	Distribution Channel User Defined Field 2	VARCHAR2(60)	This value describes the second distribution channel user defined field.
Datamart	DC_DIM	DC_UDF_3	Distribution Channel User Defined Field 3	VARCHAR2(60)	This value describes the third distribution channel user defined field.
Datamart	DC_DIM	DC_UDF_4	Distribution Channel User Defined Field 4	VARCHAR2(60)	This value describes the fourth distribution channel user defined field.
Datamart	DC_DIM	DC_UDF_5	Distribution Channel User Defined Field 5	VARCHAR2(60)	This value describes the fifth distribution channel user defined field.
Datamart	DC_DIM	END_DT	End Date	DATE	This calendar date represents when the distribution channel is no longer valid.
Datamart	DC_DIM	TYPICAL_COMM_RATE	Typical Commission Rate	NUMBER (6, 5)	This number represents the rate of commission given to a producer for a sale of a policy unless the commission rate is overridden.
Datamart	DED_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the deductible applies.
Datamart	DED_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the deductible is currently applicable.
Datamart	DED_DIM	DED	Deductible	VARCHAR2(10)	This value represents the type of fire monitoring alarm used at dwelling.
Datamart	DED_DIM	DED_APPLIES_TO	Deductible Applies To	VARCHAR2(60)	This value represents the district where the loss occurred.
Datamart	DED_DIM	DED_BASIS	Deductible Basis	VARCHAR2(60)	This value represents the basis applied to determine the deductible.
Datamart	DED_DIM	DED_ID	Deductible Identifier	NUMBER (22, 0)	This system generated number identifies the deductible instance.
Datamart	DED_DIM	DED_NAT_KEY	Deductible Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the deductible.
Datamart	DED_DIM	DED_TYP	Deductible Type	VARCHAR2(60)	This value represents the manner in which the deducible is calculated. For example, percentage of a total coverage amount.
Datamart	DED_DIM	DED_UDF_1	Deductible User Defined Field 1	VARCHAR2(60)	This value describes the first deductible user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	DED_DIM	DED_UDF_2	Deductible User Defined Field 2	VARCHAR2(60)	This value describes the second deductible user defined field.
Datamart	DED_DIM	DED_UDF_3	Deductible User Defined Field 3	VARCHAR2(60)	This value describes the third deductible user defined field.
Datamart	DED_DIM	DED_UDF_4	Deductible User Defined Field 4	VARCHAR2(60)	This value describes the fourth deductible user defined field.
Datamart	DED_DIM	DED_UDF_5	Deductible User Defined Field 5	VARCHAR2(60)	This value describes the fifth deductible user defined field.
Datamart	DED_DIM	END_DT	End Date	DATE	This calendar date represents when the deductible is no longer valid.
Datamart	DF_DWLNG_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the policy coverages began for the dwelling.
Datamart	DF_DWLNG_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the policy coverages for the dwelling is currently applicable.
Datamart	DF_DWLNG_DIM	DF_DWLNG_AREA	Dwelling Fire Dwelling Area	NUMBER (14, 3)	This number represents the area measurement of floor contained.
Datamart	DF_DWLNG_DIM	DF_DWLNG_CIRCUIT_BREAKERS_FLG	Dwelling Fire Dwelling Circuit Breakers Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of circuit breakers.
Datamart	DF_DWLNG_DIM	DF_DWLNG_COND	Dwelling Fire Dwelling Condition	VARCHAR2(60)	This value represents the classification detailing the maintenance condition of a dwelling.
Datamart	DF_DWLNG_DIM	DF_DWLNG_CONST_TYP	Dwelling Fire Dwelling Construction Type	VARCHAR2(60)	This value describes the primary dwelling exterior construction materials.
Datamart	DF_DWLNG_DIM	DF_DWLNG_CTY_LMTS_CD	Dwelling Fire Dwelling City Limits Code	VARCHAR2(60)	This system code describes if a dwelling is located within or outside city limit boundary.
Datamart	DF_DWLNG_DIM	DF_DWLNG_DIST_TO_FIRE_HYDRANT	Dwelling Fire Dwelling Distance to Fire Hydrant	NUMBER (14, 3)	This number represents the distance units (feet/ meters) from dwelling to nearest fire hydrant location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_DIST_TO_FIRE_STATION	Dwelling Fire Dwelling Distance to Fire Station	NUMBER (14, 3)	This number represents the distance units (miles/ kilometers) from dwelling to nearest fire station location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_ELEC_UPDT_TYP	Dwelling Fire Dwelling Electrical Update Type	VARCHAR2(60)	This value represents the classification detailing changes to electrical system after the dwelling's original construction.
Datamart	DF_DWLNG_DIM	DF_DWLNG_ELEC_UPDT_YR	Dwelling Fire Dwelling Electrical Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling electrical system.
Datamart	DF_DWLNG_DIM	DF_DWLNG_FIRE_DSTRCT	Dwelling Fire Dwelling Fire District	VARCHAR2(60)	This value represents the fire department response district assigned to a dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_FIRE_PROT_CLASS	Dwelling Fire Dwelling Fire Protection Class	VARCHAR2(60)	This system code describes the fire protection services available at dwelling location.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	DF_DWLNG_DIM	DF_DWLNG_FNDN_TYP	Dwelling Fire Dwelling Foundation Type	VARCHAR2(60)	This value represents the construction method used for dwelling foundation.
Datamart	DF_DWLNG_DIM	DF_DWLNG_FUSES_FLG	Dwelling Fire Dwelling Fuses Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fuses.
Datamart	DF_DWLNG_DIM	DF_DWLNG_GAS_UPDT_TYP	Dwelling Fire Dwelling Gas Update Type	VARCHAR2(60)	This value represents the classification detailing changes to gas system after the dwelling's original construction.
Datamart	DF_DWLNG_DIM	DF_DWLNG_GAS_UPDT_YR	Dwelling Fire Dwelling Gas Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling gas system.
Datamart	DF_DWLNG_DIM	DF_DWLNG_GEOG_BNDRY_UDF_1	Dwelling Fire Dwelling Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first dwelling fire dwelling geographic boundary user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_GEOG_BNDRY_UDF_2	Dwelling Fire Dwelling Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second dwelling fire dwelling geographic boundary user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_GEOG_BNDRY_UDF_3	Dwelling Fire Dwelling Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third dwelling fire dwelling geographic boundary user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_GEOG_BNDRY_UDF_4	Dwelling Fire Dwelling Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth dwelling fire dwelling geographic boundary user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_GEOG_BNDRY_UDF_5	Dwelling Fire Dwelling Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth dwelling fire dwelling geographic boundary user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_HEAT_UPDT_TYP	Dwelling Fire Dwelling Heating Update Type	VARCHAR2(60)	This value represents the classification detailing changes to heating system after the dwelling's original construction.
Datamart	DF_DWLNG_DIM	DF_DWLNG_HEAT_UPDT_YR	Dwelling Fire Dwelling Heating Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling heating system.
Datamart	DF_DWLNG_DIM	DF_DWLNG_ID	Dwelling Fire Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling instance.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_CNTY	Dwelling Fire Dwelling Location County	VARCHAR2(60)	This value identifies the county of the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_CTRY	Dwelling Fire Dwelling Location Country	VARCHAR2(60)	This value identifies the country of the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_CTY	Dwelling Fire Dwelling Location City	VARCHAR2(32)	This value identifies the city of the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_DSTRCT	Dwelling Fire Dwelling Location District	VARCHAR2(60)	This value identifies the district of the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_LATITUDE	Dwelling Fire Dwelling Location Latitude	VARCHAR2(11)	This value identifies the latitude location of the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_LONGITUDE	Dwelling Fire Dwelling Location Longitude	VARCHAR2(11)	This value identifies the longitude location of the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_NUM	Dwelling Fire Dwelling Location Number	NUMBER (22, 0)	This number identifies the dwelling included in a dwelling fire policy.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_PSTL_CD	Dwelling Fire Dwelling Location Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications for the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_PSTL_CD_PRFX	Dwelling Fire Dwelling Location Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_PSTL_SUB_CD	Dwelling Fire Dwelling Location Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_REGION	Dwelling Fire Dwelling Location Region	VARCHAR2(60)	This value identifies the geographic region of the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_STATE	Dwelling Fire Dwelling Location State	VARCHAR2(60)	This value identifies the state associated with the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_TAX_LOC_ID	Dwelling Fire Dwelling Location Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier of the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_LOC_TERR	Dwelling Fire Dwelling Location Territory	VARCHAR2(60)	This value represents the territory of the dwelling location.
Datamart	DF_DWLNG_DIM	DF_DWLNG_MINE_SUBSIDENCE_FLG	Dwelling Fire Dwelling Mine Subsidence Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of mine subsidence coverage.
Datamart	DF_DWLNG_DIM	DF_DWLNG_MKT_VAL	Dwelling Fire Dwelling Market Value	NUMBER (14, 3)	This number represents the average price of similar dwellings recently sold in same real estate market.
Datamart	DF_DWLNG_DIM	DF_DWLNG_NAT_KEY	Dwelling Fire Dwelling Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the dwelling.
Datamart	DF_DWLNG_DIM	DF_DWLNG_NUM_ELEC_SYS_AMPS	Dwelling Fire Dwelling Number of Electric System Amps	NUMBER (22, 0)	This number represents the electrical current capacity of electrical system.
Datamart	DF_DWLNG_DIM	DF_DWLNG_NUM_FMLYS	Dwelling Fire Dwelling Number of Families	NUMBER (22, 0)	This number represents the count of individual family units in single dwelling. For example, a duplex would have 2 families.
Datamart	DF_DWLNG_DIM	DF_DWLNG_NUM_OR_RMS	Dwelling Fire Dwelling Number of Rooms	NUMBER (22, 0)	This number represents the count of rooms contained in all units of the dwelling.
Datamart	DF_DWLNG_DIM	DF_DWLNG_NUM_STORIES	Dwelling Fire Dwelling Number of Stories	NUMBER (22, 0)	This number represents the count of building floor levels contained.
Datamart	DF_DWLNG_DIM	DF_DWLNG_NUM_WKS_RENTED	Dwelling Fire Dwelling Number of Weeks Rented	NUMBER (22, 0)	This number represents the number of weeks the dwelling is rented per calendar year.
Datamart	DF_DWLNG_DIM	DF_DWLNG_OCPCY_TYP	Dwelling Fire Dwelling Occupancy Type	VARCHAR2(60)	This value represents the attributes of occupants of the dwelling. For example, owner and tenant occupants.
Datamart	DF_DWLNG_DIM	DF_DWLNG_PLUMBING_UPDT_TYP	Dwelling Fire Dwelling Plumbing Update Type	VARCHAR2(60)	This value represents the classification detailing changes to plumbing system after the dwelling's original construction.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	DF_DWLNG_DIM	DF_DWLNG_PLUMBING_UPDT_YR	Dwelling Fire Dwelling Plumbing Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling plumbing system.
Datamart	DF_DWLNG_DIM	DF_DWLNG_PP_MERCNTL_BLDG_FLG	Dwelling Fire Dwelling Personal Property Mercantile Building Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of personal property stored in a mercantile building.
Datamart	DF_DWLNG_DIM	DF_DWLNG_PRIM_HEAT_TYP	Dwelling Fire Dwelling Primary Heating Type	VARCHAR2(60)	This value represents the classification of the primary source of heat for dwelling.
Datamart	DF_DWLNG_DIM	DF_DWLNG_PURCH_DT_ID	Dwelling Fire Dwelling Purchase Date Identifier	DATE	This calendar date represents the dwelling purchase date.
Datamart	DF_DWLNG_DIM	DF_DWLNG_PURCH_PRICE	Dwelling Fire Dwelling Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when dwelling was purchased.
Datamart	DF_DWLNG_DIM	DF_DWLNG_REPL_COST	Dwelling Fire Dwelling Replacement Cost	NUMBER (14, 3)	This number represents the amount it would cost to replace a dwelling at current prices with like materials.
Datamart	DF_DWLNG_DIM	DF_DWLNG_ROOF_MATL	Dwelling Fire Dwelling RoofingMaterial	VARCHAR2(60)	This value represents the roofing material used on the dwelling roof.
Datamart	DF_DWLNG_DIM	DF_DWLNG_ROOF_UPDT_TYP	Dwelling Fire Dwelling RoofingUpdate Type	VARCHAR2(60)	This value represents the classification detailing changes to roofing materials after the dwelling's original construction.
Datamart	DF_DWLNG_DIM	DF_DWLNG_ROOF_UPDT_YR	Dwelling Fire Dwelling RoofingUpdate Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling roofing materials.
Datamart	DF_DWLNG_DIM	DF_DWLNG_SCND_HEAT_TYP	Dwelling Fire Dwelling Secondary Heating Type	VARCHAR2(60)	This value represents the classification of the secondary source of heat for dwelling.
Datamart	DF_DWLNG_DIM	DF_DWLNG_TYP	Dwelling Fire Dwelling Type	VARCHAR2(60)	This value represents the classification that identifies the dwelling unit construction. For example, single-family, multi-family, warehouse, etc.
Datamart	DF_DWLNG_DIM	DF_DWLNG_UDF_1	Dwelling Fire Dwelling User Defined Field 1	VARCHAR2(60)	This value describes the first dwelling fire dwelling user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_UDF_2	Dwelling Fire Dwelling User Defined Field 2	VARCHAR2(60)	This value describes the second dwelling fire dwelling user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_UDF_3	Dwelling Fire Dwelling User Defined Field 3	VARCHAR2(60)	This value describes the third dwelling fire dwelling user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_UDF_4	Dwelling Fire Dwelling User Defined Field 4	VARCHAR2(60)	This value describes the fourth dwelling fire dwelling user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_UDF_5	Dwelling Fire Dwelling User Defined Field 5	VARCHAR2(60)	This value describes the fifth dwelling fire dwelling user defined field.
Datamart	DF_DWLNG_DIM	DF_DWLNG_UNDER_CONST_TYP	Dwelling Fire Dwelling Under Construction Type	VARCHAR2(60)	This system code indicates active construction activities on the dwelling.
Datamart	DF_DWLNG_DIM	DF_DWLNG_VACANT_PCT	Dwelling Fire Dwelling Vacant Percentage	NUMBER (6, 3)	This number represents the percentage of total dwelling area that is not currently occupied.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	DF_DWLNG_DIM	DF_DWLNG_WIRG_UPDT_TYP	Dwelling Fire Dwelling Wiring Update Type	VARCHAR2(60)	This value represents the classification detailing changes to wiring system after the dwelling's original construction.
Datamart	DF_DWLNG_DIM	DF_DWLNG_WIRG_UPDT_YR	Dwelling Fire Dwelling Wiring Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling wiring system.
Datamart	DF_DWLNG_DIM	DF_DWLNG_YR_BUILT	Dwelling Fire Dwelling Year Built	CHAR(4)	This value represents the calendar year that the dwelling was constructed.
Datamart	DF_DWLNG_DIM	END_DT	End Date	DATE	This calendar date represents when the dwelling is no longer included in policy coverages.
Datamart	DF_DWLNG_DIM	HO_DWLNG_FARMING_FLG	Homeowners Dwelling Farming Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of farming activities occurring on insured premises.
Datamart	DF_FACT	DF_DWLNG_ID	Dwelling Fire Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling instance.
Datamart	DF_FACT	DF_FACT_ID	Dwelling Fire Fact Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling fire fact instance.
Datamart	DT_DIM	CAL_HALF_YR	Calendar Half Year	CHAR(2)	This value represents the calendar half year.
Datamart	DT_DIM	CAL_MTH_LONG_NM	Calendar Month Long Name	VARCHAR2(60)	This value describes the calendar month long name.
Datamart	DT_DIM	CAL_MTH_NM	Calendar Month Name	VARCHAR2(60)	This value describes the calendar month name.
Datamart	DT_DIM	CAL_MTH_NUM_IN_YR	Calendar Month Number In Year	NUMBER (22, 0)	This number identifies the calendar month in year.
Datamart	DT_DIM	CAL_QTR	Calendar Quarter	CHAR(2)	This value represents the calendar quarter.
Datamart	DT_DIM	CAL_QTR_NUM_IN_YR	Calendar Quarter Number In Year	NUMBER (22, 0)	This number identifies the calendar quarter number in year.
Datamart	DT_DIM	CAL_WK_BEGIN_DT	Calendar Week Begin Date	DATE	This calendar date represents when the calendar week begins.
Datamart	DT_DIM	CAL_WK_END_DT	Calendar Week Ending Date	DATE	This calendar date represents when the calendar week ends.
Datamart	DT_DIM	CAL_WK_NUM_IN_YR	Calendar Week Number In Year	NUMBER (22, 0)	This number identifies the calendar week number in year.
Datamart	DT_DIM	CAL_YR	Calendar Year	CHAR(4)	This value represents the calendar year.
Datamart	DT_DIM	CAL_YR_MTH	Calendar Year Month	CHAR(6)	This value represents identifies the calendar year month.
Datamart	DT_DIM	CAL_YR_MTH_NUM	Calendar Year Month Number	NUMBER (22, 0)	This number identifies the calendar year month.
Datamart	DT_DIM	CAL_YR_NUM	Calendar Year Number	NUMBER (22, 0)	This number identifies the calendar year.
Datamart	DT_DIM	CAL_YR_QTR	Calendar Year Quarter	CHAR(6)	A value that identifies calendar year quarter.
Datamart	DT_DIM	CAL_YR_QTR_NUM	Calendar Year Quarter Number	NUMBER (22, 0)	This number identifies the calendar year quarter number.
Datamart	DT_DIM	DAY_LONG_NM	Day of Week Long Name	VARCHAR2(60)	This value represents the day of week long name.
Datamart	DT_DIM	DAY_NM	Day of Week Name	VARCHAR2(60)	This value represents the name of the day of week.
Datamart	DT_DIM	DAY_NUM_IN_CAL_MTH	Day Number in Calendar Month	NUMBER (22, 0)	This number identifies day of week number in calendar month.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	DT_DIM	DAY_NUM_IN_CAL_YR	Day Number in Calendar Year	NUMBER (22, 0)	This number identifies day of week number in calendar year.
Datamart	DT_DIM	DAY_NUM_IN_FISCAL_MTH	Day Number in Fiscal Month	NUMBER (22, 0)	This number identifies day of week number in fiscal month.
Datamart	DT_DIM	DAY_NUM_IN_FISCAL_YR	Day Number in Fiscal Year	NUMBER (22, 0)	This number identifies day of week number in fiscal year.
Datamart	DT_DIM	DAY_NUM_IN_WK	Day Number in Week	NUMBER (22, 0)	This number identifies day of week number in week.
Datamart	DT_DIM	DT_FULL_DESC	Date Full Description	VARCHAR2(60)	This value represents the full description of the date.
Datamart	DT_DIM	DT_ID	Date Identifier	DATE	This calendar date represents the actual date.
Datamart	DT_DIM	FISCAL_HALF_YR	Fiscal Half Year	CHAR(2)	This value represents the fiscal half year.
Datamart	DT_DIM	FISCAL_MTH_LONG_NM	Fiscal Month Long Name	VARCHAR2(60)	This value represents the long name of fiscal month.
Datamart	DT_DIM	FISCAL_MTH_NM	Fiscal Month Name	VARCHAR2(60)	This value represents the name of fiscal month.
Datamart	DT_DIM	FISCAL_MTH_NUM_IN_YR	Fiscal Month Number In Year	NUMBER (22, 0)	This number identifies fiscal month number in year.
Datamart	DT_DIM	FISCAL_QTR	Fiscal Quarter	CHAR(2)	This value describes the fiscal quarter.
Datamart	DT_DIM	FISCAL_QTR_NUM_IN_YR	Fiscal Quarter Number In Year	NUMBER (22, 0)	This number identifies fiscal quarter number in year.
Datamart	DT_DIM	FISCAL_WK_BEGIN_DT	Fiscal Week Beginning Date	DATE	This date identifies the fiscal week begin date.
Datamart	DT_DIM	FISCAL_WK_END_DT	Fiscal Week Ending Date	DATE	This date identifies the fiscal week end date.
Datamart	DT_DIM	FISCAL_WK_NUM_IN_YR	Fiscal Week Number In Year	NUMBER (22, 0)	This number identifies fiscal number in year.
Datamart	DT_DIM	FISCAL_YR	Fiscal Year	CHAR(4)	This value describes the fiscal year.
Datamart	DT_DIM	FISCAL_YR_MTH	Fiscal Year Month	CHAR(6)	This value describes the fiscal year month.
Datamart	DT_DIM	FISCAL_YR_MTH_NUM	Fiscal Year Month Number	NUMBER (22, 0)	This number represents the fiscal year month number.
Datamart	DT_DIM	FISCAL_YR_NUM	Fiscal Year Number	NUMBER (22, 0)	This number represents the fiscal year number.
Datamart	DT_DIM	FISCAL_YR_QTR	Fiscal Year Quarter	CHAR(6)	This value describes the fiscal year quarter.
Datamart	DT_DIM	FISCAL_YR_QTR_NUM	Fiscal Year Quarter Number	NUMBER (22, 0)	This number represents the fiscal year quarter number.
Datamart	DT_DIM	LAST_DAY_IN_CAL_MTH_FLG	Last Day in Calendar Month Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the date is the last day in the calendar month.
Datamart	DT_DIM	LAST_DAY_IN_CAL_WK_FLG	Last Day in Calendar Week Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the date is the last day in the calendar week.
Datamart	DT_DIM	LAST_DAY_IN_FISCAL_MTH_FLG	Last Day in Fiscal Month Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the date is the last day in the fiscal month.
Datamart	DT_DIM	LAST_DAY_IN_FISCAL_WK_FLG	Last Day in Fiscal Week Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the date is the last day in the fiscal week.
Datamart	DT_DIM	WK_DAY_FLG	Weekday Flag	CHAR(1)	This value represents based on the yes/no indicator identifying presence or absence of week day.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	FEAT_DIM	ACCID_INJY_ANLYS_CD	Accident Injury Analysis Code (AIA)	VARCHAR2(60)	This system code summarizes the facts relating to a claim. The code can be used to indicate injuries such as body parts involved, type of injury or disease and cause of condition related to a claim.
Datamart	FEAT_DIM	ACCID_INJY_ANLYS_SUB_CD	Accident Injury Analysis Sub Code	VARCHAR2(60)	This system code describes the loss in more detail than the accident injury analysis code and further describes such things as the object/incident involved in the loss (i.e. machinery, wet floor, etc.).
Datamart	FEAT_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim feature applies.
Datamart	FEAT_DIM	CAUSE_OF_LOSS	Cause of Loss	VARCHAR2(60)	This value describes the condition that caused a loss to occur.
Datamart	FEAT_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim feature is currently applicable.
Datamart	FEAT_DIM	DSBLY_TYP	Disability Type	VARCHAR2(60)	This value represents the classification that identifies physical impairments.
Datamart	FEAT_DIM	END_DT	End Date	DATE	This calendar date represents when the claim feature is no longer valid.
Datamart	FEAT_DIM	FEAT_ID	Feature Identifier	NUMBER (22, 0)	This system generated number identifies the claim feature instance.
Datamart	FEAT_DIM	FEAT_NAT_KEY	Feature Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the Feature.
Datamart	FEAT_DIM	FEAT_UDF_1	Feature User Defined Field 1	VARCHAR2(60)	This value describes the first claim feature user defined field.
Datamart	FEAT_DIM	FEAT_UDF_2	Feature User Defined Field 2	VARCHAR2(60)	This value describes the second claim feature user defined field.
Datamart	FEAT_DIM	FEAT_UDF_3	Feature User Defined Field 3	VARCHAR2(60)	This value describes the third claim feature user defined field.
Datamart	FEAT_DIM	FEAT_UDF_4	Feature User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim feature user defined field.
Datamart	FEAT_DIM	FEAT_UDF_5	Feature User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim feature user defined field.
Datamart	FEAT_DIM	INJURED_BODY_PART	Injured Body Part	VARCHAR2(60)	This value represents the anatomical part of the insured's body.
Datamart	FEAT_DIM	TYP_OF_LOSS	Type of Loss	VARCHAR2(60)	This is the CSP type of loss code It includes the loss location and the loss cause.
Datamart	FEAT_STATUS_DIM	FEAT_CLOSED_DT_ID	Feature Closed Date	DATE	This calendar date represents when the claim feature, defined as a subset of a claim occurrence, was closed.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	FEAT_STATUS_DIM	FEAT_OPENED_DT_ID	Feature Opened Date	DATE	This calendar date represents when the claim feature, defined as a subset of a claim occurrence, was opened.
Datamart	FEAT_STATUS_DIM	FEAT_RECLOSED_DT_ID	Feature Re-closed Date Identifier	DATE	This calendar date represents when a claim feature was closed after original closing.
Datamart	FEAT_STATUS_DIM	FEAT_REOPENED_DT_ID	Feature Re-Opened Date Identifier	DATE	This date identifies when a claim feature was opened after a previous closing.
Datamart	FEAT_STATUS_DIM	FEAT_STATUS	Feature Status	VARCHAR2(60)	This value describes the current condition of the claim feature, defined as a subset of a claim.
Datamart	FEAT_STATUS_DIM	FEAT_STATUS_ID	Feature Status Identifier	NUMBER (22, 0)	This system generated number identifies the claim feature status instance.
Datamart	FEAT_STATUS_DIM	FEAT_STATUS_UDF_1	Feature Status User Defined Field 1	VARCHAR2(60)	This value describes the first claim feature status user defined field.
Datamart	FEAT_STATUS_DIM	FEAT_STATUS_UDF_2	Feature Status User Defined Field 2	VARCHAR2(60)	This value describes the second claim feature status user defined field.
Datamart	FEAT_STATUS_DIM	FEAT_STATUS_UDF_3	Feature Status User Defined Field 3	VARCHAR2(60)	This value describes the third claim feature status user defined field.
Datamart	FEAT_STATUS_DIM	FEAT_STATUS_UDF_4	Feature Status User Defined Field 4	VARCHAR2(60)	This value describes the fourth claim feature status user defined field.
Datamart	FEAT_STATUS_DIM	FEAT_STATUS_UDF_5	Feature Status User Defined Field 5	VARCHAR2(60)	This value describes the fifth claim feature status user defined field.
Datamart	GRP_PRG_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the group program applies.
Datamart	GRP_PRG_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the group program is currently applicable.
Datamart	GRP_PRG_DIM	END_DT	End Date	DATE	This calendar date represents when the group program is no longer valid.
Datamart	GRP_PRG_DIM	GRP_PRG_ANNIVERSARY_DT_ID	Group Program Anniversary Date Identifier	DATE	This calendar date represents the anniversary of a group program.
Datamart	GRP_PRG_DIM	GRP_PRG_DIVIDEND_DT_ID	Group Program dividend Date Identifier	DATE	This calendar date represents when identifies the dividend date of a group program.
Datamart	GRP_PRG_DIM	GRP_PRG_DIVIDEND_PLAN	Group Program Dividend Plan	VARCHAR2(60)	This value represents the classification of the manner in which a group program dividend is paid.
Datamart	GRP_PRG_DIM	GRP_PRG_ID	Group Program Identifier	NUMBER (22, 0)	This system generated number identifies the group program instance.
Datamart	GRP_PRG_DIM	GRP_PRG_MBR_CNT	Group Program Member Count	NUMBER (22, 0)	This number identifies the count of the members of a group program.
Datamart	GRP_PRG_DIM	GRP_PRG_NAT_KEY	Group Program Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the group program.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	GRP_PRG_DIM	GRP_PRG_NAT_NM	Group Program National Name	VARCHAR2(60)	This value represents the name of the national program that a group of policies are associated with.
Datamart	GRP_PRG_DIM	GRP_PRG_NM	Group Program Name	VARCHAR2(60)	This value represents the name of the program, other than state or national, that a group of policies are associated with.
Datamart	GRP_PRG_DIM	GRP_PRG_ORIG_DT_ID	Group Program Origination Date Identifier	DATE	This calendar date represents when identifies group program origination date.
Datamart	GRP_PRG_DIM	GRP_PRG_STATE	Group Program State	VARCHAR2(60)	This value identifies the state associated with group program.
Datamart	GRP_PRG_DIM	GRP_PRG_STATUS	Group Program Status	VARCHAR2(60)	This value describes the current condition of a program with which a group of policies is associated.
Datamart	GRP_PRG_DIM	GRP_PRG_TYP	Group Program Type	VARCHAR2(60)	This value represents the type of program that is represented.
Datamart	GRP_PRG_DIM	GRP_PRG_UDF_1	Group Program User Defined Field 1	VARCHAR2(60)	This value describes the first group program user defined field.
Datamart	GRP_PRG_DIM	GRP_PRG_UDF_2	Group Program User Defined Field 2	VARCHAR2(60)	This value describes the second group program user defined field.
Datamart	GRP_PRG_DIM	GRP_PRG_UDF_3	Group Program User Defined Field 3	VARCHAR2(60)	This value describes the third group program user defined field.
Datamart	GRP_PRG_DIM	GRP_PRG_UDF_4	Group Program User Defined Field 4	VARCHAR2(60)	This value describes the fourth group program user defined field.
Datamart	GRP_PRG_DIM	GRP_PRG_UDF_5	Group Program User Defined Field 5	VARCHAR2(60)	This value describes the fifth group program user defined field.
Datamart	HO_DWLNG_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage in the dwelling begins.
Datamart	HO_DWLNG_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the dwelling is currently applicable.
Datamart	HO_DWLNG_DIM	END_DT	End Date	DATE	This calendar date represents when the dwelling is no longer included in policy coverages.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ALUMINUM_WIRG_FLG	Homeowners Dwelling Aluminum Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of aluminum wiring.
Datamart	HO_DWLNG_DIM	HO_DWLNG_AREA	Homeowners Dwelling Area	NUMBER (14, 3)	This number represents the area measurement of floor contained in the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ATTACHED_GAR_FLG	Homeowners Dwelling Attached Garage Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of an attached garage.
Datamart	HO_DWLNG_DIM	HO_DWLNG_BSMT_AREA	Homeowners Dwelling Basement Area	NUMBER (14, 3)	This number represents the total area measurement of all the basements in this dwelling.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	HO_DWLNG_DIM	HO_DWLNG_BURGLAR_MONITOR_TYP	Homeowners Dwelling Burglar Monitoring Type	VARCHAR2(60)	This value describes the attributes of a burglar alarm in use.
Datamart	HO_DWLNG_DIM	HO_DWLNG_CARPORT_FLG	Homeowners Dwelling Carport Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a carport.
Datamart	HO_DWLNG_DIM	HO_DWLNG_CIRCUIT_BREAKERS_FLG	Homeowners Dwelling Circuit Breakers Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of circuit breakers.
Datamart	HO_DWLNG_DIM	HO_DWLNG_COND	Homeowners Dwelling Condition	VARCHAR2(60)	This value represents the classification detailing the maintenance condition of a dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_CONST_TYP	Homeowners Dwelling Construction Type	VARCHAR2(60)	This value describes the primary dwelling exterior construction materials.
Datamart	HO_DWLNG_DIM	HO_DWLNG_COPPER_WIRG_FLG	Homeowners Dwelling Copper Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of copper wiring.
Datamart	HO_DWLNG_DIM	HO_DWLNG_CTY_LMTS_CD	Homeowners Dwelling City Limits Code	VARCHAR2(60)	This system code describes if a dwelling is located within or outside city limit boundary.
Datamart	HO_DWLNG_DIM	HO_DWLNG_DIST_TO_FIRE_HYDRANT	Homeowners Dwelling Distance to Fire Hydrant	NUMBER (14, 3)	This number represents the distance units (feet/ meters) from dwelling to nearest fire hydrant location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_DIST_TO_FIRE_STATION	Homeowners Dwelling Distance to Fire Station	NUMBER (14, 3)	This number represents the distance units (miles/ kilometers) from dwelling to nearest fire station location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ELEC_UPDT_TYP	Homeowners Dwelling Electrical Update Type	VARCHAR2(60)	This value represents the classification that describes changes to electrical system after the dwelling's original construction.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ELEC_UPDT_YR	Homeowners Dwelling Electrical Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling electrical system.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ENCLOSED_GAR_FLG	Homeowners Dwelling Enclosed Garage Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of enclosed garage.
Datamart	HO_DWLNG_DIM	HO_DWLNG_EXT_PAINT_UPDT_YR	Homeowners Dwelling Exterior Paint Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling exterior paint.
Datamart	HO_DWLNG_DIM	HO_DWLNG_FARMING_FLG	Homeowners Dwelling Farming Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of farming activities occurring on insured premises.
Datamart	HO_DWLNG_DIM	HO_DWLNG_FIRE_DSTRCT	Homeowners Dwelling Fire District	VARCHAR2(60)	This value represents the fire department response district assigned to a dwelling location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_FIRE_EXTINGUISHER_FLG	Homeowners Dwelling Fire Extinguishers Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a fire extinguisher.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	HO_DWLNG_DIM	HO_DWLNG_FIRE_MONITOR_TYP	Homeowners Dwelling Fire Monitoring Type	VARCHAR2(60)	This value represents the type of fire monitoring alarm used at dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_FIRE_PROT_CLASS	Homeowners Dwelling Fire Protection Class	VARCHAR2(60)	This system code describes the fire protection services available at dwelling location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_FNDN_TYP	Homeowners Dwelling Foundation Type	VARCHAR2(60)	This value represents the construction method used to construct dwelling foundation.
Datamart	HO_DWLNG_DIM	HO_DWLNG_FUSES_FLG	Homeowners Dwelling Fuses Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fuses.
Datamart	HO_DWLNG_DIM	HO_DWLNG_GAS_UPDT_TYP	Homeowners Dwelling Gas Update Type	VARCHAR2(60)	This value represents the classification that describes changes to gas system after the dwelling's original construction.
Datamart	HO_DWLNG_DIM	HO_DWLNG_GAS_UPDT_YR	Homeowners Dwelling Gas Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling gas system.
Datamart	HO_DWLNG_DIM	HO_DWLNG_GEOG_BNDRY_UDF_1	Homeowners Dwelling Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first homeowners dwelling geographic boundary user defined field.
Datamart	HO_DWLNG_DIM	HO_DWLNG_GEOG_BNDRY_UDF_2	Homeowners Dwelling Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second homeowners dwelling geographic boundary user defined field.
Datamart	HO_DWLNG_DIM	HO_DWLNG_GEOG_BNDRY_UDF_3	Homeowners Dwelling Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third homeowners dwelling geographic boundary user defined field.
Datamart	HO_DWLNG_DIM	HO_DWLNG_GEOG_BNDRY_UDF_4	Homeowners Dwelling Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth homeowners dwelling geographic boundary user defined field.
Datamart	HO_DWLNG_DIM	HO_DWLNG_GEOG_BNDRY_UDF_5	Homeowners Dwelling Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth homeowners dwelling geographic boundary user defined field.
Datamart	HO_DWLNG_DIM	HO_DWLNG_HEAT_UPDT_TYP	Homeowners Dwelling Heating Update Type	VARCHAR2(60)	This value represents the classification that describes changes to heating system after the dwelling's original construction.
Datamart	HO_DWLNG_DIM	HO_DWLNG_HEAT_UPDT_YR	Homeowners Dwelling Heating Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling heating system.
Datamart	HO_DWLNG_DIM	HO_DWLNG_HURCN_RST_GLASS_FLG	Homeowners Dwelling Hurricane Resistant Glass Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of hurricane resistant glass.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ID	Homeowners Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling instance.
Datamart	HO_DWLNG_DIM	HO_DWLNG_KNOB_TUBE_WIRG_FLG	Homeowners Dwelling Knob and Tube Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of knob and tube wiring.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_CNTY	Homeowners Dwelling Location County	VARCHAR2(60)	This value identifies the county of the dwelling's location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_CTRY	Homeowners Dwelling Location Country	VARCHAR2(60)	This value identifies the country of the dwelling's location.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_CTY	Homeowners Dwelling Location City	VARCHAR2(32)	This value identifies the city of the dwelling's location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_DSTRCT	Homeowners Dwelling Location District	VARCHAR2(60)	This value represents the district where the dwelling is located.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_LATITUDE	Homeowners Dwelling Location Latitude	VARCHAR2(11)	This value represents the latitude location of the dwelling location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_LONGITUDE	Homeowners Dwelling Location Longitude	VARCHAR2(11)	This value represents the longitude location of the dwelling location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_NUM	Homeowners Dwelling Location Number	NUMBER (22, 0)	This number represents the specific dwelling location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_PSTL_CD	Homeowners Dwelling Location Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_PSTL_CD_PRFX	Homeowners Dwelling Location Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_PSTL_SUB_CD	Homeowners Dwelling Location Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_REGION	Homeowners Dwelling Location Region	VARCHAR2(60)	This value represents the geographic region where the dwelling is located.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_STATE	Homeowners Dwelling Location State	VARCHAR2(60)	This value identifies the state associated with the dwelling location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_TAX_LOC_ID	Homeowners Dwelling Location Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier of the dwelling location.
Datamart	HO_DWLNG_DIM	HO_DWLNG_LOC_TERR	Homeowners Dwelling Location Territory	VARCHAR2(60)	This value represents the territory where a dwelling is located.
Datamart	HO_DWLNG_DIM	HO_DWLNG_MKT_VAL	Homeowners Dwelling Market Value	NUMBER (14, 3)	This number represents the average price of similar dwellings recently sold in same real estate market.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NAT_KEY	Homeowners Dwelling Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NUM_CHIMNEYS	Homeowners Dwelling Number Chimneys	NUMBER (22, 0)	This number represents the count of chimneys contained in all units of the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NUM_ELEC_SYS_AMPS	Homeowners Dwelling Number of Electric System Amps	NUMBER (22, 0)	This number represents the electrical current capacity of electrical system.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NUM_FMLYS	Homeowners Dwelling Number Families	NUMBER (22, 0)	This number represents the count of individual family units in single dwelling. For example, a duplex would have 2 families.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NUM_HEARTHS	Homeowners Dwelling Number Hearths	NUMBER (22, 0)	This number represents the count of hearths contained in all units of the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NUM_OR_RMS	Homeowners Dwelling Number Of Rooms	NUMBER (22, 0)	This number represents the count of rooms contained in all units of the dwelling.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	HO_DWLNG_DIM	HO_DWLNG_NUM_PRE_FAB_FPS	Homeowners Dwelling Number Pre-Fabricated Fireplaces	NUMBER (22, 0)	This number represents the count of pre-fabricated fireplaces contained in all units of the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NUM_RSDTS	Homeowners Dwelling Number of Residents	NUMBER (22, 0)	This number represents the count of residents contained in all units of the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NUM_STORIES	Homeowners Dwelling Number Stories	NUMBER (22, 0)	This number represents the count of building floor levels in the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_NUM_WOOD_STOVE_ISRTS	Homeowners Dwelling Number Wood Stove Inserts	NUMBER (22, 0)	This number represents the count of wood stove inserts contained in all units of the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_OCPCY_TYP	Homeowners Dwelling Occupancy Type	VARCHAR2(60)	This value represents the type of occupants of the dwelling. For example, owner and tenant occupants.
Datamart	HO_DWLNG_DIM	HO_DWLNG_PLUMBING_UPDT_TYP	Homeowners Dwelling Plumbing Update Type	VARCHAR2(60)	This value represents the classification that describes changes to plumbing system after the dwelling's original construction.
Datamart	HO_DWLNG_DIM	HO_DWLNG_PLUMBING_UPDT_YR	Homeowners Dwelling Plumbing Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling plumbing system.
Datamart	HO_DWLNG_DIM	HO_DWLNG_PRIM_HEAT_TYP	Homeowners Dwelling Primary Heating Type	VARCHAR2(60)	This value represents the classification of the primary source of heat for dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_PROP_LOT_SIZE	Homeowners Dwelling Property Lot Size	NUMBER (14, 3)	This number represents the total area measurement of the land within the property lot boundaries.
Datamart	HO_DWLNG_DIM	HO_DWLNG_PURCH_DT_ID	Homeowners Dwelling Purchase Date Identifier	DATE	This date identifies when the dwelling was purchased.
Datamart	HO_DWLNG_DIM	HO_DWLNG_PURCH_PRICE	Homeowners Dwelling Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when dwelling was purchased.
Datamart	HO_DWLNG_DIM	HO_DWLNG_REPL_COST	Homeowners Dwelling Replacement Cost	NUMBER (14, 3)	This number represents the amount it would cost to replace a dwelling at current prices with like materials.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ROOF_IMPACT_RATING	Homeowners Dwelling Roofing Impact Rating	VARCHAR2(60)	This value represents the rating of the level of hail impact a roof material can withstand.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ROOF_MATL	Homeowners Dwelling Roofing Material	VARCHAR2(60)	This value represents the construction material used to construct the roof of the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ROOF_UPDT_TYP	Homeowners Dwelling Roofing Update Type	VARCHAR2(60)	This value represents the type of change made to roofing materials after original construction.
Datamart	HO_DWLNG_DIM	HO_DWLNG_ROOF_UPDT_YR	Homeowners Dwelling Roofing Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling roofing materials.
Datamart	HO_DWLNG_DIM	HO_DWLNG_SCND_HEAT_TYP	Homeowners Dwelling Secondary Heating Type	VARCHAR2(60)	This value represents the classification of the secondary source of heat for dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_SIDING	Homeowners Dwelling Siding	VARCHAR2(60)	This value represents the type of construction material used as siding on the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_SIDING_PCT	Homeowners Dwelling Siding Percentage	NUMBER (6, 3)	This number represents the percentage of total dwelling exterior covered with siding.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	HO_DWLNG_DIM	HO_DWLNG_SPRINKLER_TYP	Homeowners Dwelling Sprinkler Type	VARCHAR2(60)	This value represents the classification that identifies the sprinkler system type.
Datamart	HO_DWLNG_DIM	HO_DWLNG_STORM_SHUTTERS	Homeowners Dwelling Storm Shutters	VARCHAR2(60)	This value represents the classification that indicates the presence or absence and type of storm shutters.
Datamart	HO_DWLNG_DIM	HO_DWLNG_SWIM_POOL	Homeowners Dwelling Swimming Pool	VARCHAR2(60)	This value represents the classification that indicates the presence or absence and type of swimming pool.
Datamart	HO_DWLNG_DIM	HO_DWLNG_TRAMPOLINE_FLG	Homeowners Dwelling Trampoline Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a trampoline.
Datamart	HO_DWLNG_DIM	HO_DWLNG_TYP	Homeowners Dwelling Type	VARCHAR2(60)	This value represents the classification that identifies the dwelling unit construction. For example, single-family, multi-family, warehouse, etc.
Datamart	HO_DWLNG_DIM	HO_DWLNG_UDF_1	Homeowners Dwelling User Defined Field 1	VARCHAR2(60)	This value describes the first homeowners dwelling user defined field.
Datamart	HO_DWLNG_DIM	HO_DWLNG_UDF_2	Homeowners Dwelling User Defined Field 2	VARCHAR2(60)	This value describes the second homeowners dwelling user defined field.
Datamart	HO_DWLNG_DIM	HO_DWLNG_UDF_3	Homeowners Dwelling User Defined Field 3	VARCHAR2(60)	This value describes the third homeowners dwelling user defined field.
Datamart	HO_DWLNG_DIM	HO_DWLNG_UDF_4	Homeowners Dwelling User Defined Field 4	VARCHAR2(60)	This value describes the fourth homeowners dwelling user defined field.
Datamart	HO_DWLNG_DIM	HO_DWLNG_UDF_5	Homeowners Dwelling User Defined Field 5	VARCHAR2(60)	This value describes the fifth homeowners dwelling user defined field.
Datamart	HO_DWLNG_DIM	HO_DWLNG_UNDER_CONST_TYP	Homeowners Dwelling Under Construction Type	VARCHAR2(60)	This system code indicates active construction activities on the dwelling.
Datamart	HO_DWLNG_DIM	HO_DWLNG_WIRG_LAST_INSP_DT_ID	Homeowners Dwelling Wiring Last InspectedDate Identifier	DATE	This calendar date represents the occurance of the last inspection of the dwelling wiring system.
Datamart	HO_DWLNG_DIM	HO_DWLNG_WIRG_UPDT_TYP	Homeowners Dwelling Wiring Update Type	VARCHAR2(60)	This value represents the classification that describes changes to wiring system after the dwelling's original construction.
Datamart	HO_DWLNG_DIM	HO_DWLNG_WIRG_UPDT_YR	Homeowners Dwelling Wiring Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling wiring system.
Datamart	HO_DWLNG_DIM	HO_DWLNG_YR_BUILT	Homeowners Dwelling Year Built	CHAR(4)	This value represents the calendar year that the dwelling was constructed.
Datamart	HO_FACT	HO_DWLNG_ID	Homeowners Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling instance.
Datamart	HO_FACT	HO_FACT_ID	Homeowners Fact Identifier	NUMBER (22, 0)	This system generated number identifies the homeowners fact instance.
Datamart	INSD_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the insured applies.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	INSD_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the insured is currently applicable.
Datamart	INSD_DIM	END_DT	End Date	DATE	This calendar date represents when the insured is no longer valid.
Datamart	INSD_DIM	INSD_AUDIT_FREQ	Insured Audit Frequency	VARCHAR2(60)	This value represents the indicator of when an insured audit is scheduled.
Datamart	INSD_DIM	INSD_AUDIT_TYP	Insured Audit Type	VARCHAR2(60)	This value represents the classification of the audit activities conducted on insured.
Datamart	INSD_DIM	INSD_BIRTH_DT_ID	Insured Birth Date Identifier	DATE	This calendar date represents the insured date of birth instance.
Datamart	INSD_DIM	INSD_BUS_START_DT_ID	Insured Business Start Date Identifier	DATE	This calendar date represents when insured business operations began.
Datamart	INSD_DIM	INSD_CNTCT_DESC	Insured Contact Description	VARCHAR2(60)	This value represents the description of the insured's contact type.
Datamart	INSD_DIM	INSD_CNTCT_TYP	Insured Contact Type	VARCHAR2(60)	This value represents the contact method for insured.
Datamart	INSD_DIM	INSD_CNTCT_UDF_1	Insured Contact User Defined Field 1	VARCHAR2(60)	This value describes the first insured contact user defined field.
Datamart	INSD_DIM	INSD_CNTCT_UDF_2	Insured Contact User Defined Field 2	VARCHAR2(60)	This value describes the second insured contact user defined field.
Datamart	INSD_DIM	INSD_CNTCT_UDF_3	Insured Contact User Defined Field 3	VARCHAR2(60)	This value describes the third insured contact user defined field.
Datamart	INSD_DIM	INSD_CNTCT_UDF_4	Insured Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth insured contact user defined field.
Datamart	INSD_DIM	INSD_CNTCT_UDF_5	Insured Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth insured contact user defined field.
Datamart	INSD_DIM	INSD_CNTY	Insured County	VARCHAR2(60)	This value identifies the county associated with the insured.
Datamart	INSD_DIM	INSD_CRED_SCORE	Insured Credit Score	VARCHAR2(11)	This system code or number that represents the insured credit rating score.
Datamart	INSD_DIM	INSD_CTRY	Insured Country	VARCHAR2(60)	This value identifies the country associated with the insured.
Datamart	INSD_DIM	INSD_CTY	Insured City	VARCHAR2(32)	This value identifies the city associated with the insured.
Datamart	INSD_DIM	INSD_DBA	Insured Doing Business As	VARCHAR2(170)	This value represents the insured business operating name.
Datamart	INSD_DIM	INSD_DSTRCT	Insured District	VARCHAR2(60)	This value represents the district where the insured is located.
Datamart	INSD_DIM	INSD_GENDER	Insured Gender	VARCHAR2(60)	This value represents the gender (male or female) of the insured.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	INSD_DIM	INSD_GEOG_BNDRY_UDF_1	Insured Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first insured geographic boundary user defined field.
Datamart	INSD_DIM	INSD_GEOG_BNDRY_UDF_2	Insured Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second insured geographic boundary user defined field.
Datamart	INSD_DIM	INSD_GEOG_BNDRY_UDF_3	Insured Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third insured geographic boundary user defined field.
Datamart	INSD_DIM	INSD_GEOG_BNDRY_UDF_4	Insured Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth insured geographic boundary user defined field.
Datamart	INSD_DIM	INSD_GEOG_BNDRY_UDF_5	Insured Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth insured geographic boundary user defined field.
Datamart	INSD_DIM	INSD_GOVT_ID_NUM	Insured Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the insured. For example, in the USA: SSN or FEIN.
Datamart	INSD_DIM	INSD_ID	Insured Identifier	NUMBER (22, 0)	This system generated number identifies the insured instance.
Datamart	INSD_DIM	INSD_LATITUDE	Insured Latitude	VARCHAR2(11)	This value represents the latitude location of the insured's location.
Datamart	INSD_DIM	INSD_LONGITUDE	Insured Longitude	VARCHAR2(11)	This value represents the longitude location of the insured's location.
Datamart	INSD_DIM	INSD_MARITAL_STATUS	Insured Marital Status	VARCHAR2(60)	This value represents the present marital condition (single, married, divorced, widowed) of the insured.
Datamart	INSD_DIM	INSD_NAICS_CD	Insured North American Industry Classification System Code	VARCHAR2(60)	This value represents the North America Industry Class (NAICS) code assigned to insured.
Datamart	INSD_DIM	INSD_NAT_KEY	Insured Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the insured.
Datamart	INSD_DIM	INSD_NM	Insured Name	VARCHAR2(170)	This value represents the full given name of the insured.
Datamart	INSD_DIM	INSD_NOB	Insured Nature of Business	VARCHAR2(60)	This value represents the type or category of the business activities done by the insured.
Datamart	INSD_DIM	INSD_NUM_EMP	Insured Number of Employees	NUMBER (22, 0)	This number represents the count of people employed by insured.
Datamart	INSD_DIM	INSD_ORG_UDF_1	Insured Organization User Defined Field 1	VARCHAR2(60)	This value describes the first insured organization user defined field.
Datamart	INSD_DIM	INSD_ORG_UDF_2	Insured Organization User Defined Field 2	VARCHAR2(60)	This value describes the second insured organization user defined field.
Datamart	INSD_DIM	INSD_ORG_UDF_3	Insured Organization User Defined Field 3	VARCHAR2(60)	This value describes the third insured organization user defined field.
Datamart	INSD_DIM	INSD_ORG_UDF_4	Insured Organization User Defined Field 4	VARCHAR2(60)	This value describes the fourth insured organization user defined field.
Datamart	INSD_DIM	INSD_ORG_UDF_5	Insured Organization User Defined Field 5	VARCHAR2(60)	This value describes the fifth insured organization user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	INSD_DIM	INSD_PARTY_UDF_1	Insured Party User Defined Field 1	VARCHAR2(60)	This value describes the first insured party user defined field.
Datamart	INSD_DIM	INSD_PARTY_UDF_2	Insured Party User Defined Field 2	VARCHAR2(60)	This value describes the second insured party user defined field.
Datamart	INSD_DIM	INSD_PARTY_UDF_3	Insured Party User Defined Field 3	VARCHAR2(60)	This value describes the third insured party user defined field.
Datamart	INSD_DIM	INSD_PARTY_UDF_4	Insured Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth insured party user defined field.
Datamart	INSD_DIM	INSD_PARTY_UDF_5	Insured Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth insured party user defined field.
Datamart	INSD_DIM	INSD_PERS_UDF_1	Insured Person User Defined Field 1	VARCHAR2(60)	This value describes the first insured person user defined field.
Datamart	INSD_DIM	INSD_PERS_UDF_2	Insured Person User Defined Field 2	VARCHAR2(60)	This value describes the second insured person user defined field.
Datamart	INSD_DIM	INSD_PERS_UDF_3	Insured Person User Defined Field 3	VARCHAR2(60)	This value describes the third insured person user defined field.
Datamart	INSD_DIM	INSD_PERS_UDF_4	Insured Person User Defined Field 4	VARCHAR2(60)	This value describes the fourth insured person user defined field.
Datamart	INSD_DIM	INSD_PERS_UDF_5	Insured Person User Defined Field 5	VARCHAR2(60)	This value describes the fifth insured person user defined field.
Datamart	INSD_DIM	INSD_PRES_EMPLMT_START_YR	Insured Present Employment Start Year	CHAR(4)	This value represents the calendar year that the insured began working for their current employer.
Datamart	INSD_DIM	INSD_PRIOR_INSUR_CO	Insured Prior Insurance Company	VARCHAR2(60)	This value represents the name of insurance company that last provided insurance prior to policy inception.
Datamart	INSD_DIM	INSD_PSTL_CD	Insured Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	INSD_DIM	INSD_PSTL_CD_PRFX	Insured Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	INSD_DIM	INSD_PSTL_SUB_CD	Insured Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	INSD_DIM	INSD_REGION	Insured Region	VARCHAR2(60)	This value represents the geographic region of the insured's location.
Datamart	INSD_DIM	INSD_RISK_GRADE	Insured Risk Grade	VARCHAR2(60)	This system code represents the A.M. Best or company defined risk grade for insured.
Datamart	INSD_DIM	INSD_RPT_PERIOD	Insured Report Period	VARCHAR2(60)	This value describes the timeframe of activities considered in an insured report.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	INSD_DIM	INSD_SIC_CD	Insured Standard Industrial Classification Code	VARCHAR2(60)	This system code is the SIC code assigned to the insured.The Standard Industrial Classification (SIC) code is an industry code that identifies the classification of business activity.
Datamart	INSD_DIM	INSD_STATE	Insured State	VARCHAR2(60)	This value identifies the state of the insured's location.
Datamart	INSD_DIM	INSD_TAX_LOC_ID	Insured Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier in the insured's location.
Datamart	INSD_DIM	INSD_TERR	Insured Territory	VARCHAR2(60)	This value represents the territory of the insured's location.
Datamart	INSD_DIM	INSD_TYP	Insured Type	VARCHAR2(60)	This value represents the type of entity that contracted with insurance company to obtain a policy.
Datamart	INSD_DIM	INSD_UDF_1	Insured User Defined Field 1	VARCHAR2(60)	This value describes the first insured user defined field.
Datamart	INSD_DIM	INSD_UDF_2	Insured User Defined Field 2	VARCHAR2(60)	This value describes the second insured user defined field.
Datamart	INSD_DIM	INSD_UDF_3	Insured User Defined Field 3	VARCHAR2(60)	This value describes the third insured user defined field.
Datamart	INSD_DIM	INSD_UDF_4	Insured User Defined Field 4	VARCHAR2(60)	This value describes the fourth insured user defined field.
Datamart	INSD_DIM	INSD_UDF_5	Insured User Defined Field 5	VARCHAR2(60)	This value describes the fifth insured user defined field.
Datamart	INSUR_CO_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the insurance company applies.
Datamart	INSUR_CO_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the insurance company is currently applicable.
Datamart	INSUR_CO_DIM	END_DT	End Date	DATE	This calendar date represents when the insurance company is no longer valid.
Datamart	INSUR_CO_DIM	INSUR_CO_AM_BEST_NUM	Insurance Company A.M. Best Number	VARCHAR2(5)	This value represents the number or other identifier that identifies the insurance company A.M. Best Rating.
Datamart	INSUR_CO_DIM	INSUR_CO_BUS_START_DT_ID	Insurance Company Business Start Date Identifier	DATE	This calendar date represents when the insurance company began business operations.
Datamart	INSUR_CO_DIM	INSUR_CO_CNTCT_DESC	Insurance Company Contact Description	VARCHAR2(60)	This value describes the insurance company contact type.
Datamart	INSUR_CO_DIM	INSUR_CO_CNTCT_TYP	Insurance Company Contact Type	VARCHAR2(60)	This value represents the contact method for insurance company.
Datamart	INSUR_CO_DIM	INSUR_CO_CNTCT_UDF_1	Insurance Company Contact User Defined Field 1	VARCHAR2(60)	This value describes the first insured company contact user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	INSUR_CO_DIM	INSUR_CO_CNTCT_UDF_2	Insurance Company Contact User Defined Field 2	VARCHAR2(60)	This value describes the second insured company contact user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_CNTCT_UDF_3	Insurance Company Contact User Defined Field 3	VARCHAR2(60)	This value describes the third insured company contact user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_CNTCT_UDF_4	Insurance Company Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth insured company contact user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_CNTCT_UDF_5	Insurance Company Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth insured company contact user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_CNTY	Insurance Company County	VARCHAR2(60)	This value identifies the county where insurance company is located.
Datamart	INSUR_CO_DIM	INSUR_CO_CTRY	Insurance Company Country	VARCHAR2(60)	This value identifies the country where insurance company is located.
Datamart	INSUR_CO_DIM	INSUR_CO_CTY	Insurance Company City	VARCHAR2(32)	This value identifies the city where insurance company is located.
Datamart	INSUR_CO_DIM	INSUR_CO_DBA	Insurance Company Doing Business As	VARCHAR2(170)	This value represents the business operating name.
Datamart	INSUR_CO_DIM	INSUR_CO_DSTRCT	Insurance Company District	VARCHAR2(60)	This value represents the district where insurance company is located.
Datamart	INSUR_CO_DIM	INSUR_CO_GEOG_BNDRY_UDF_1	Insurance Company Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first insurance company geographic boundary user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_GEOG_BNDRY_UDF_2	Insurance Company Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second insurance company geographic boundary user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_GEOG_BNDRY_UDF_3	Insurance Company Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third insurance company geographic boundary user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_GEOG_BNDRY_UDF_4	Insurance Company Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth insurance company geographic boundary user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_GEOG_BNDRY_UDF_5	Insurance Company Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth insurance company geographic boundary user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_GOVT_ID_NUM	Insurance Company Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the insurance company. For example, in the USA: SSN or FEIN.
Datamart	INSUR_CO_DIM	INSUR_CO_ID	Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the insurance company instance.
Datamart	INSUR_CO_DIM	INSUR_CO_ISO_CD	Insurance Company Insurance Services Office Code	VARCHAR2(5)	This value represents the insurance company's Insurance Services Office (ISO) code.
Datamart	INSUR_CO_DIM	INSUR_CO_LATITUDE	Insurance Company Latitude	VARCHAR2(11)	This value represents the latitude location of insurance company.
Datamart	INSUR_CO_DIM	INSUR_CO_LONGITUDE	Insurance Company Longitude	VARCHAR2(11)	This value represents the longitude location of insurance company.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	INSUR_CO_DIM	INSUR_CO_NAIC_CD	Insurance Company National Association of Insurance Commissioners Code	VARCHAR2(5)	This value represents the National Association of Insurance Commissioners Code (NAIC) code assigned to insurance company.
Datamart	INSUR_CO_DIM	INSUR_CO_NAICS_CD	Insurance Company North American Industry Classification System Code	VARCHAR2(60)	This value represents the North America Industry Class (NAICS) code assigned to insurance company.
Datamart	INSUR_CO_DIM	INSUR_CO_NAT_KEY	Insurance Company Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the insurance company.
Datamart	INSUR_CO_DIM	INSUR_CO_NCCI_CD	Insurance Company National Council on Compensation Insurance Code	VARCHAR2(5)	This value represents the insurance company's National Council on Compensation insurance (NCCI) code.
Datamart	INSUR_CO_DIM	INSUR_CO_NM	Insurance Company Name	VARCHAR2(170)	This value represents the name of insurance company.
Datamart	INSUR_CO_DIM	INSUR_CO_NOB	Insurance Company Nature of Business	VARCHAR2(60)	This value represents the type or category of the business activities done by the insurance company.
Datamart	INSUR_CO_DIM	INSUR_CO_NUM_EMP	Insurance Company Number of Employees	NUMBER (22, 0)	This number represents the count of people employed at insurance company.
Datamart	INSUR_CO_DIM	INSUR_CO_ORG_UDF_1	Insurance Company Organization User Defined Field 1	VARCHAR2(60)	This value describes the first insurance company organization user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_ORG_UDF_2	Insurance Company Organization User Defined Field 2	VARCHAR2(60)	This value describes the second insurance company organization user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_ORG_UDF_3	Insurance Company Organization User Defined Field 3	VARCHAR2(60)	This value describes the third insurance company organization user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_ORG_UDF_4	Insurance Company Organization User Defined Field 4	VARCHAR2(60)	This value describes the fourth insurance company organization user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_ORG_UDF_5	Insurance Company Organization User Defined Field 5	VARCHAR2(60)	This value describes the fifth insurance company organization user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_PARTY_UDF_1	Insurance Company Party User Defined Field 1	VARCHAR2(60)	This value describes the first insurance company party user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_PARTY_UDF_2	Insurance Company Party User Defined Field 2	VARCHAR2(60)	This value describes the second insurance company party user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_PARTY_UDF_3	Insurance Company Party User Defined Field 3	VARCHAR2(60)	This value describes the third insurance company party user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_PARTY_UDF_4	Insurance Company Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth insurance company party user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_PARTY_UDF_5	Insurance Company Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth insurance company party user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_PSTL_CD	Insurance Company Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	INSUR_CO_DIM	INSUR_CO_PSTL_CD_PRFX	Insurance Company Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	INSUR_CO_DIM	INSUR_CO_PSTL_SUB_CD	Insurance Company Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	INSUR_CO_DIM	INSUR_CO_REGION	Insurance Company Region	VARCHAR2(60)	This value represents the geographic region where insurance company is located.
Datamart	INSUR_CO_DIM	INSUR_CO_SIC_CD	Insurance Company Standard Industrial Classification Code	VARCHAR2(60)	The Standard Industrial Classification (SIC) code is an industry code that identifies the classification of business activity. This system code is the SIC code assigned to the insurance company.
Datamart	INSUR_CO_DIM	INSUR_CO_STATE	Insurance Company State	VARCHAR2(60)	This value identifies the state where insurance company is located.
Datamart	INSUR_CO_DIM	INSUR_CO_TAX_LOC_ID	Insurance Company Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier in the insurance company's location.
Datamart	INSUR_CO_DIM	INSUR_CO_TERR	Insurance Company Territory	VARCHAR2(60)	This value represents the territory where insurance company is located.
Datamart	INSUR_CO_DIM	INSUR_CO_TYP	Insurance Company Type	VARCHAR2(60)	This value represents the classification of the insurance company's primary operations.
Datamart	INSUR_CO_DIM	INSUR_CO_UDF_1	Insurance Company User Defined Field 1	VARCHAR2(60)	This value describes the first insurance company user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_UDF_2	Insurance Company User Defined Field 2	VARCHAR2(60)	This value describes the second insurance company user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_UDF_3	Insurance Company User Defined Field 3	VARCHAR2(60)	This value describes the third insurance company user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_UDF_4	Insurance Company User Defined Field 4	VARCHAR2(60)	This value describes the fourth insurance company user defined field.
Datamart	INSUR_CO_DIM	INSUR_CO_UDF_5	Insurance Company User Defined Field 5	VARCHAR2(60)	This value describes the fifth insurance company user defined field.
Datamart	LITG_DIM	ALT_DISPUTE_RESOLUTION	Alternate Dispute Resolution	VARCHAR2(60)	This value represents the intermediary for used for dispute settlement.
Datamart	LITG_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the litigation begins.
Datamart	LITG_DIM	COMPENSATORY_DEMAND_AMT	Compensatory Demand Amount	NUMBER (14, 3)	This number represents the amount of requested compensatory damages.
Datamart	LITG_DIM	COMPENSATORY_OFFER_AMT	Compensatory Offer Amount	NUMBER (14, 3)	This number represents the amount of offered compensatory damages.
Datamart	LITG_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the litigation is currently applicable.
Datamart	LITG_DIM	DISCLOSURE_DT_ID	Disclosure Date Identifier	DATE	This date is the unique identifier assigned to the litigation disclosure date.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	LITG_DIM	END_DT	End Date	DATE	This calendar date represents when the litigation is no longer valid.
Datamart	LITG_DIM	LITG_AMT	Litigation Amount	NUMBER (14, 3)	This number represents the amount of litigation case.
Datamart	LITG_DIM	LITG_CLOSED_DT_ID	Litigation Closed Date Identifier	DATE	This calendar date represents when identifies when litigation case was closed.
Datamart	LITG_DIM	LITG_CNTY	Litigation County	VARCHAR2(60)	This value identifies the county where litigation occurs.
Datamart	LITG_DIM	LITG_DISPOSITION	Litigation Disposition	VARCHAR2(60)	This value describes the status of a litigation case.
Datamart	LITG_DIM	LITG_ID	Litigation Identifier	NUMBER (22, 0)	This system generated number identifies the litigation instance.
Datamart	LITG_DIM	LITG_NAT_KEY	Litigation Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the litigation.
Datamart	LITG_DIM	LITG_OPENED_DT_ID	Litigation Opened Date Identifier	DATE	This calendar date represents when identifies when litigation case was filed in court.
Datamart	LITG_DIM	LITG_STATE	Litigation State	VARCHAR2(60)	This value identifies the state associated with the litigation.
Datamart	LITG_DIM	LITG_UDF_1	Litigation User Defined Field 1	VARCHAR2(60)	This value describes the first litigation user defined field.
Datamart	LITG_DIM	LITG_UDF_2	Litigation User Defined Field 2	VARCHAR2(60)	This value describes the second litigation user defined field.
Datamart	LITG_DIM	LITG_UDF_3	Litigation User Defined Field 3	VARCHAR2(60)	This value describes the third litigation user defined field.
Datamart	LITG_DIM	LITG_UDF_4	Litigation User Defined Field 4	VARCHAR2(60)	This value describes the fourth litigation user defined field.
Datamart	LITG_DIM	LITG_UDF_5	Litigation User Defined Field 5	VARCHAR2(60)	This value describes the fifth litigation user defined field.
Datamart	LITG_DIM	TRIAL_DT_ID	Trial Date Identifier	DATE	This calendar date represents when identifies when a trial begins.
Datamart	LMT_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the limit applies.
Datamart	LMT_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the limit is currently applicable.
Datamart	LMT_DIM	END_DT	End Date	DATE	This calendar date represents when the limit is no longer valid.
Datamart	LMT_DIM	FIRST_LMT	First Limit	VARCHAR2(15)	This value represents the first limit.
Datamart	LMT_DIM	FULL_LMT	Full Limit	VARCHAR2(50)	This value represents the unabbreviated limit amount.
Datamart	LMT_DIM	LMT_APPLIES_TO	Limit Applies To	VARCHAR2(60)	This value represents the classification of coverage for which a limit applies.
Datamart	LMT_DIM	LMT_BASIS	Limit Basis	VARCHAR2(60)	This value represents the basis to which limits are applied.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	LMT_DIM	LMT_ID	Limit Identifier	NUMBER (22, 0)	This system generated number identifies the limit instance.
Datamart	LMT_DIM	LMT_NAT_KEY	Limit Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the limit.
Datamart	LMT_DIM	LMT_TYP	Limit Type	VARCHAR2(60)	This value represents the indicator of the category of how a limit is determined.
Datamart	LMT_DIM	LMT_UDF_1	Limit User Defined Field 1	VARCHAR2(60)	This value describes the first limit user defined field.
Datamart	LMT_DIM	LMT_UDF_2	Limit User Defined Field 2	VARCHAR2(60)	This value describes the second limit user defined field.
Datamart	LMT_DIM	LMT_UDF_3	Limit User Defined Field 3	VARCHAR2(60)	This value describes the third limit user defined field.
Datamart	LMT_DIM	LMT_UDF_4	Limit User Defined Field 4	VARCHAR2(60)	This value describes the fourth limit user defined field.
Datamart	LMT_DIM	LMT_UDF_5	Limit User Defined Field 5	VARCHAR2(60)	This value describes the fifth limit user defined field.
Datamart	LMT_DIM	SECOND_LMT	Second Limit	VARCHAR2(15)	This value represents the second limit of limit dimension table.
Datamart	LMT_DIM	THIRD_LMT	Third Limit	VARCHAR2(15)	This value identifies the third limit of limit dimension table.
Datamart	LMT_DIM	VALUATION_CD	Valuation Code	VARCHAR2(60)	This value describes the code assigned in the method of loss valuation.
Datamart	LOB_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the line of business applies.
Datamart	LOB_DIM	CO_PROD_CD	Company Producer Code	VARCHAR2(60)	This system code identifies the company producer.
Datamart	LOB_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the line of business is currently applicable.
Datamart	LOB_DIM	END_DT	End Date	DATE	This calendar date represents when the line of business is no longer valid.
Datamart	LOB_DIM	LOB_CD	Line Of Business Code	VARCHAR2(60)	This system code identifies the line of business classification.
Datamart	LOB_DIM	LOB_ID	Line Of Business Identifier	NUMBER (22, 0)	This system generated number identifies the line of business instance.
Datamart	LOB_DIM	LOB_NAT_KEY	Line of Business Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the line of business.
Datamart	LOB_DIM	LOB_SUB_CD	Line Of Business Sub Code	VARCHAR2(60)	This system code identifies the line of business sub code that further refines the line of business code. This system code identifies the product classification of the policy.
Datamart	LOB_DIM	LOB_UDF_1	Line of Business User Defined Field 1	VARCHAR2(60)	This value describes the first line of business user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	LOB_DIM	LOB_UDF_2	Line of Business User Defined Field 2	VARCHAR2(60)	This value describes the second line of business user defined field.
Datamart	LOB_DIM	LOB_UDF_3	Line of Business User Defined Field 3	VARCHAR2(60)	This value describes the third line of business user defined field.
Datamart	LOB_DIM	LOB_UDF_4	Line of Business User Defined Field 4	VARCHAR2(60)	This value describes the fourth line of business user defined field.
Datamart	LOB_DIM	LOB_UDF_5	Line of Business User Defined Field 5	VARCHAR2(60)	This value describes the fifth line of business user defined field.
Datamart	LOB_DIM	PSNL_OR_COML	Personal Or Commercial	VARCHAR2(60)	This value describes a policy coverage type as personal or commercial lines.
Datamart	LOB_DIM	SYS_LOB_CD	System Line of Business Code	VARCHAR2(60)	This system code represents the system line of business.
Datamart	MTH_DIM	CAL_HALF_YR	Calendar Half Year	CHAR(2)	This value represents the the calendar half year for the month dimension.
Datamart	MTH_DIM	CAL_MTH_LONG_NM	Calendar Month Long Name	VARCHAR2(60)	This value identifies calendar month long name.
Datamart	MTH_DIM	CAL_MTH_NM	Calendar Month Name	VARCHAR2(60)	This description identifies calendar month name.
Datamart	MTH_DIM	CAL_MTH_NUM_IN_YR	Calendar Month Number In Year	NUMBER (22, 0)	This number identifies the calendar month in year.
Datamart	MTH_DIM	CAL_QTR	Calendar Quarter	CHAR(2)	This value represents the calendar quarter for the month dimension.
Datamart	MTH_DIM	CAL_QTR_NUM_IN_YR	Calendar Quarter Number In Year	NUMBER (22, 0)	This number represents the calendar quarter number in year.
Datamart	MTH_DIM	CAL_YR	Calendar Year	CHAR(4)	This value represents the calendar year.
Datamart	MTH_DIM	CAL_YR_MTH	Calendar Year Month	CHAR(6)	This value represents the calendar year month.
Datamart	MTH_DIM	CAL_YR_MTH_NUM	Calendar Year Month Number	NUMBER (22, 0)	This value represents the calendar year month.
Datamart	MTH_DIM	CAL_YR_NUM	Calendar Year Number	NUMBER (22, 0)	This number identifies the calendar year.
Datamart	MTH_DIM	CAL_YR_QTR	Calendar Year Quarter	CHAR(6)	A value that identifies calendar year quarter.
Datamart	MTH_DIM	CAL_YR_QTR_NUM	Calendar Year Quarter Number	NUMBER (22, 0)	This number identifies the calendar year quarter number.
Datamart	MTH_DIM	FISCAL_HALF_YR	Fiscal Half Year	CHAR(2)	This value represents the fiscal half year.
Datamart	MTH_DIM	FISCAL_MTH_LONG_NM	Fiscal Month Long Name	VARCHAR2(60)	This value represents the long name of fiscal month.
Datamart	MTH_DIM	FISCAL_MTH_NM	Fiscal Month Name	VARCHAR2(60)	This value represents the name of fiscal month.
Datamart	MTH_DIM	FISCAL_MTH_NUM_IN_YR	Fiscal Month Number In Year	NUMBER (22, 0)	This number identifies fiscal month number in year.
Datamart	MTH_DIM	FISCAL_QTR	Fiscal Quarter	CHAR(2)	This value represents the fiscal quarter.
Datamart	MTH_DIM	FISCAL_QTR_NUM_IN_YR	Fiscal Quarter Number In Year	NUMBER (22, 0)	This number identifies fiscal quarter number in year.
Datamart	MTH_DIM	FISCAL_YR	Fiscal Year	CHAR(4)	This value describes the fiscal year.
Datamart	MTH_DIM	FISCAL_YR_MTH	Fiscal Year Month	CHAR(6)	This value describes the fiscal year month.
Datamart	MTH_DIM	FISCAL_YR_MTH_NUM	Fiscal Year Month Number	NUMBER (22, 0)	This number represents the fiscal year month number.
Datamart	MTH_DIM	FISCAL_YR_NUM	Fiscal Year Number	NUMBER (22, 0)	This number represents the fiscal year number.
Datamart	MTH_DIM	FISCAL_YR_QTR	Fiscal Year Quarter	CHAR(6)	This value describes the fiscal year quarter.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	MTH_DIM	FISCAL_YR_QTR_NUM	Fiscal Year Quarter Number	NUMBER (22, 0)	This number represents the fiscal year quarter number.
Datamart	MTH_DIM	MTH_ID	Month Identifier	NUMBER (22, 0)	This number represents the month instance.
Datamart	PA_DRV_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage in the personal driver begins.
Datamart	PA_DRV_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the driver is currently applicable.
Datamart	PA_DRV_DIM	END_DT	End Date	DATE	This calendar date represents when the personal driver is no longer included in policy coverages.
Datamart	PA_DRV_DIM	PA_DFEN_DRV_TRNG_DSCNT_FLG	Defensive Driving Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a defensive driver training discount applies.
Datamart	PA_DRV_DIM	PA_DFEN_DRV_TRNG_DSCNT_PCT	Defensive Driving Training Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when Defensive driver discount applies.
Datamart	PA_DRV_DIM	PA_DRV_ACCID_CNT	Personal Auto Driver Accident Count	NUMBER (22, 0)	This number represents the count of accidents charged against the driver's driving record.
Datamart	PA_DRV_DIM	PA_DRV_BIRTH_DT_ID	Personal Auto Driver Birth Date Identifier	DATE	This date identifies the personal vehicle driver's date of birth.
Datamart	PA_DRV_DIM	PA_DRV_CLASS	Personal Auto Driver Class	VARCHAR2(60)	This value represents the classification that describes the characteristics of a the driver It is typically only used for assigned risk, JUA, and in Texas.
Datamart	PA_DRV_DIM	PA_DRV_COMMUTER_DSCNT_FLG	Personal Auto Driver Commuter Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a commuter discount applies.
Datamart	PA_DRV_DIM	PA_DRV_COMMUTER_DSCNT_PCT	Personal Auto Driver Commuter Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when commuter discount applies.
Datamart	PA_DRV_DIM	PA_DRV_DFEN_DRV_CD	Personal Auto Defensive Driving Training Code	VARCHAR2(60)	This value describes of the defensive driving code.
Datamart	PA_DRV_DIM	PA_DRV_DIST_STUDENT_FLG	Personal Auto Driver Distant Student Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a Distant Student applies.
Datamart	PA_DRV_DIM	PA_DRV_DWI_DUI_VIOLATION_CNT	Personal Auto Driver DWI and DUI Violation Count	NUMBER (22, 0)	This number represents the count of Driving While Intoxicated (DWI) and/or Driving Under the Influence (DUI) violations charged against the driver's driving record.
Datamart	PA_DRV_DIM	PA_DRV_GENDER	Personal Auto Driver Gender	VARCHAR2(60)	This value represents the gender (male or female) of the driver.
Datamart	PA_DRV_DIM	PA_DRV_GOOD_STUDENT_CD	Personal Auto Driver Good Student Code	VARCHAR2(60)	This system code identifies the good student type.
Datamart	PA_DRV_DIM	PA_DRV_GOOD_STUDENT_DSCNT_FLG	Personal Auto Driver Good Student Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a good student discount applies.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PA_DRV_DIM	PA_DRV_GOOD_STUDENT_DSCNT_PCT	Personal Auto Driver Good Student Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when good student discount applies.
Datamart	PA_DRV_DIM	PA_DRV_GOVT_ID_NUM	Personal Auto Driver Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the personal vehicle driver. For example, in the USA: SSN or FEIN.
Datamart	PA_DRV_DIM	PA_DRV_ID	Personal Auto Driver Identifier	NUMBER (22, 0)	This system generated number identifies the personal vehicle driver instance.
Datamart	PA_DRV_DIM	PA_DRV_INSD_DT_ID	Personal Auto Driver Insured Date Identifier	DATE	This calendar date represents when insurance coverage began for personal vehicle driver.
Datamart	PA_DRV_DIM	PA_DRV_INTRMDT_VIOLATION_CNT	Personal Auto Driver Intermediate Violation Count	NUMBER (22, 0)	This number represents the count of intermediate violations charged against the driver's driving record.
Datamart	PA_DRV_DIM	PA_DRV_LIC_DT_ID	Personal Auto Driver Licensed Date Identifier	DATE	This calendar date represents when personal vehicle driver was granted a drivers license.
Datamart	PA_DRV_DIM	PA_DRV_LIC_ISSUED_BY	Personal Auto Driver License Issued By	VARCHAR2(60)	This value represents the governmental entity which granted drivers license.
Datamart	PA_DRV_DIM	PA_DRV_LIC_STATUS	Personal Auto Driver License Status	VARCHAR2(60)	This value represents the latitude location of the reinsurance company.
Datamart	PA_DRV_DIM	PA_DRV_MAJOR_VIOLATION_CNT	Personal Auto Driver Major Violation Count	NUMBER (22, 0)	This number represents the count of major violations charged against the driver's driving record.
Datamart	PA_DRV_DIM	PA_DRV_MARITAL_STATUS	Personal Auto Driver Marital Status	VARCHAR2(60)	This value represents the third limit of limit dimension table.
Datamart	PA_DRV_DIM	PA_DRV_MINOR_VIOLATION_CNT	Personal Auto Driver Minor Violation Count	NUMBER (22, 0)	This number represents the count of minor violations charged against the driver's driving record.
Datamart	PA_DRV_DIM	PA_DRV_NAT_KEY	Personal Auto Driver Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the personal vehicle driver.
Datamart	PA_DRV_DIM	PA_DRV_NM	Personal Auto Driver Name	VARCHAR2(170)	This value represents the full given name of personal vehicle driver.
Datamart	PA_DRV_DIM	PA_DRV_NUM	Personal Auto Driver Number	NUMBER (22, 0)	This number identifies personal vehicle driver.
Datamart	PA_DRV_DIM	PA_DRV_NUM_YRS_AT_CUR_ADDR	Personal Auto Driver Number of Years at Current Address	NUMBER (22, 0)	This number represents the count of the years the driver has resided at current address.
Datamart	PA_DRV_DIM	PA_DRV_OCP	Personal Auto Driver Occupation	VARCHAR2(50)	This value represents the classification of employment tasks completed during personal vehicle driver's employment.
Datamart	PA_DRV_DIM	PA_DRV_PARTY_UDF_1	Personal Auto Driver Party User Defined Field 1	VARCHAR2(60)	This value describes the first personal vehicle driver party user defined field.
Datamart	PA_DRV_DIM	PA_DRV_PARTY_UDF_2	Personal Auto Driver Party User Defined Field 2	VARCHAR2(60)	This value describes the second personal vehicle driver party user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PA_DRV_DIM	PA_DRV_PARTY_UDF_3	Personal Auto Driver Party User Defined Field 3	VARCHAR2(60)	This value describes the third personal vehicle driver party user defined field.
Datamart	PA_DRV_DIM	PA_DRV_PARTY_UDF_4	Personal Auto Driver Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth personal vehicle driver party user defined field.
Datamart	PA_DRV_DIM	PA_DRV_PARTY_UDF_5	Personal Auto Driver Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth personal vehicle driver party user defined field.
Datamart	PA_DRV_DIM	PA_DRV_PERS_UDF_1	Personal Auto Driver Person Defined Field 1	VARCHAR2(60)	This value describes the first personal vehicle driver person user defined field.
Datamart	PA_DRV_DIM	PA_DRV_PERS_UDF_2	Personal Auto Driver Person Defined Field 1	VARCHAR2(60)	This value describes the second personal vehicle driver person user defined field.
Datamart	PA_DRV_DIM	PA_DRV_PERS_UDF_3	Personal Auto Driver Person Defined Field 1	VARCHAR2(60)	This value describes the third personal vehicle driver person user defined field.
Datamart	PA_DRV_DIM	PA_DRV_PERS_UDF_4	Personal Auto Driver Person Defined Field 1	VARCHAR2(60)	This value describes the fourth personal vehicle driver person user defined field.
Datamart	PA_DRV_DIM	PA_DRV_PERS_UDF_5	Personal Auto Driver Person Defined Field 1	VARCHAR2(60)	This value describes the fifth personal vehicle driver person user defined field.
Datamart	PA_DRV_DIM	PA_DRV_PRES_EMPLMT_START_YR	Personal Auto Driver Present Employment Start Year	CHAR(4)	This value represents the calendar year that the personal vehicle driver began working for their current employer.
Datamart	PA_DRV_DIM	PA_DRV_RLAT_TO_APPLICANT	Personal Auto Driver Relationship to Applicant	VARCHAR2(60)	This value represents the relationship of this driver to the applicant.
Datamart	PA_DRV_DIM	PA_DRV_STATUS	Personal Auto Driver Status	VARCHAR2(60)	This value represents the classification of the driver's coverage to policy coverages.
Datamart	PA_DRV_DIM	PA_DRV_TRNG_DSCNT_FLG	Personal Auto Driver Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a driver training discount applies.
Datamart	PA_DRV_DIM	PA_DRV_TRNG_DSCNT_PCT	Personal Auto Driver Training Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when driving training discount applies.
Datamart	PA_DRV_DIM	PA_DRV_TRNG_FLG	Personal Auto Driver Training Flag	CHAR(1)	This value represents based on the yes/no indicator identifying presence or absence of driver training.
Datamart	PA_DRV_DIM	PA_DRV_TYP	Personal Auto Driver Type	VARCHAR2(60)	This value represents the indicator that describes the characteristics of a personal vehicle driver.
Datamart	PA_DRV_DIM	PA_DRV_UDF_1	Personal Auto Driver User Defined Field 1	VARCHAR2(60)	This value describes the first personal vehicle driver user defined field.
Datamart	PA_DRV_DIM	PA_DRV_UDF_2	Personal Auto Driver User Defined Field 2	VARCHAR2(60)	This value describes the second personal vehicle driver user defined field.
Datamart	PA_DRV_DIM	PA_DRV_UDF_3	Personal Auto Driver User Defined Field 3	VARCHAR2(60)	This value describes the third personal vehicle driver user defined field.
Datamart	PA_DRV_DIM	PA_DRV_UDF_4	Personal Auto Driver User Defined Field 4	VARCHAR2(60)	This value describes the fourth personal vehicle driver user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PA_DRV_DIM	PA_DRV_UDF_5	Personal Auto Driver User Defined Field 5	VARCHAR2(60)	This value describes the fifth personal vehicle driver user defined field.
Datamart	PA_DRV_DIM	PA_DRV_YOUTHFUL_CD	Personal Auto Driver Youthful Code	VARCHAR2(60)	This system code is that identifies the youthful personal vehicle driver.
Datamart	PA_FACT	PA_DRV_ID	Personal Auto Driver Identifier	NUMBER (22, 0)	This system generated number identifies the personal vehicle driver instance.
Datamart	PA_FACT	PA_FACT_ID	Persona Auto Vehicle Fact Identifier	NUMBER (22, 0)	This number identifies the personal vehicle fact instance.
Datamart	PA_FACT	PA_VEH_ID	Persona Auto Vehicle Identifier	NUMBER (22, 0)	This system generated number identifies the personal vehicle instance.
Datamart	PA_VEH_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage in the personal driver begins.
Datamart	PA_VEH_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the vehicle is currently applicable.
Datamart	PA_VEH_DIM	END_DT	End Date	DATE	This calendar date represents when the personal vehicle is no longer included in policy coverages.
Datamart	PA_VEH_DIM	PA_VEH_ADDL_EQPT_AMT	Persona Auto Vehicle Additional Equipment Amount	NUMBER (14, 3)	This number represents the monetary cost of personal vehicle alterations or aftermarket custom equipment like custom painting, equipment installed to overcome a physical handicap, etc.
Datamart	PA_VEH_DIM	PA_VEH_AIRBAG_TYP	Persona Auto Vehicle Airbag Type	VARCHAR2(60)	This value represents the classification of the airbag system installed in personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_ANTI_LOCK_BRAKES_CD	Persona Auto Vehicle Anti-Lock Brakes Code	VARCHAR2(60)	This system code describes the type of anti-lock brakes system present on a personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_ANTI_THEFT_DEVICE_CD	Persona Auto Vehicle Anti-Theft Device Code	VARCHAR2(60)	This system code describes the type of anti-theft system present on a personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_AUTO_STBLTS_DSCNT_FLG	Persona Auto Vehicle Automatic Seatbelts Flag	CHAR(1)	This value represents based on the yes/no indicator identifying presence or absence of automatic seatbelts.
Datamart	PA_VEH_DIM	PA_VEH_AUTO_STBLTS_DSCNT_PCT	Persona Auto Vehicle Automatic Seatbelts Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when automatic seatbelts discount applies.
Datamart	PA_VEH_DIM	PA_VEH_BODY_TYP	Persona Auto Vehicle Body Type	VARCHAR2(60)	This value represents the classification of the characteristics of a personal vehicle body.
Datamart	PA_VEH_DIM	PA_VEH_CELL_PHONE_TYP	Persona Auto Vehicle Cellular Phone Type	VARCHAR2(60)	This system code identifies the cellular phone type present in vehicle.
Datamart	PA_VEH_DIM	PA_VEH_CLASS	Persona Auto Vehicle Class	VARCHAR2(60)	This value represents the classification that describes vehicle size and body type.
Datamart	PA_VEH_DIM	PA_VEH_COST_NEW	Persona Auto Vehicle Cost New	NUMBER (14, 3)	This number represents the monetary amount of vehicle when Purchased as a New vehicle.
Datamart	PA_VEH_DIM	PA_VEH_CUR_VAL	Persona Auto Vehicle Current Value	NUMBER (14, 3)	This number represents the current monetary value of personal vehicle in marketplace.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PA_VEH_DIM	PA_VEH_DAYTIME_RUN_LIGHTS_CD	Persona Auto Vehicle Daytime Running Lights Code	VARCHAR2(60)	This system code describes the type of daytime running headlights present on a personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_EST_ANNU_DRVG_DIST	Persona Auto Vehicle Estimated Annual Driving Distance	NUMBER (22, 0)	This number identifies the count of the annual estimated driving distance units.
Datamart	PA_VEH_DIM	PA_VEH_GAR_CD	Persona Auto Vehicle Garaging Code	VARCHAR2(60)	This system code describes where a vehicle is parked at night.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_CNTY	Persona Auto Vehicle Garaging Location County	VARCHAR2(60)	This value identifies the county where a vehicle is parked at night.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_CTRY	Persona Auto Vehicle Garaging Location Country	VARCHAR2(60)	This value identifies the country where a vehicle is parked at night.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_CTY	Persona Auto Vehicle Garaging Location City	VARCHAR2(32)	This value identifies the city where a vehicle is parked at night.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_DSTRCT	Persona Auto Vehicle Garaging Location District	VARCHAR2(60)	This value represents the full name of the distribution channel.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_LATITUDE	Persona Auto Vehicle Garaging Location Latitude	VARCHAR2(11)	This value represents the present marital condition (single, married, divorced, widowed) of the claim examiner.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_LONGITUDE	Persona Auto Vehicle Garaging Location Longitude	VARCHAR2(11)	This value represents the longitude location where a vehicle is parked at night.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_PSTL_CD	Persona Auto Vehicle Garaging Location Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_PSTL_CD_PRFX	Persona Auto Vehicle Garaging Location Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_PSTL_SUB_CD	Persona Auto Vehicle Garaging Location Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_REGION	Persona Auto Vehicle Garaging Location Region	VARCHAR2(60)	This value represents the geographic region where a vehicle is parked at night.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_STATE	Persona Auto Vehicle Garaging Location State	VARCHAR2(60)	This value identifies the state where a vehicle is parked at night.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_TAX_LOC_ID	Persona Auto Vehicle Garaging Location Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier of where a vehicle is parked at night.
Datamart	PA_VEH_DIM	PA_VEH_GAR_LOC_TERR	Persona Auto Vehicle Garaging Location Territory	VARCHAR2(60)	This value represents the territory where a vehicle is parked at night.
Datamart	PA_VEH_DIM	PA_VEH_GEOG_BNDRY_UDF_1	Persona Auto Vehicle Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first personal vehicle geographic boundary user defined field.
Datamart	PA_VEH_DIM	PA_VEH_GEOG_BNDRY_UDF_2	Persona Auto Vehicle Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second personal vehicle geographic boundary user defined field.
Datamart	PA_VEH_DIM	PA_VEH_GEOG_BNDRY_UDF_3	Persona Auto Vehicle Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third personal vehicle geographic boundary user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PA_VEH_DIM	PA_VEH_GEOG_BNDRY_UDF_4	Persona Auto Vehicle Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth personal vehicle geographic boundary user defined field.
Datamart	PA_VEH_DIM	PA_VEH_GEOG_BNDRY_UDF_5	Persona Auto Vehicle Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth personal vehicle geographic boundary user defined field.
Datamart	PA_VEH_DIM	PA_VEH_GROSS_WT	Persona Auto Vehicle Gross Weight	NUMBER (14, 3)	This number represents the total weight a vehicle is designed to carry and includes the net weight of the vehicle, plus the weight of passengers, fuel, cargo and any additional accessories.
Datamart	PA_VEH_DIM	PA_VEH_HP_DSPLCMNT	Persona Auto Vehicle Horsepower Displacement	VARCHAR2(5)	This value represents the district of the dwelling's location.
Datamart	PA_VEH_DIM	PA_VEH_ID	Persona Auto Vehicle Identifier	NUMBER (22, 0)	This system generated number identifies the personal vehicle instance.
Datamart	PA_VEH_DIM	PA_VEH_INSD_DT_ID	Persona Auto Vehicle Insured Date Identifier	DATE	This calendar date represents when insurance coverage began for a personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_LEASE_DT_ID	Persona Auto Vehicle Lease Date Identifier	DATE	This calendar date represents when a personal vehicle was leased by insured.
Datamart	PA_VEH_DIM	PA_VEH_MFR	Persona Auto Vehicle Manufacturer	VARCHAR2(20)	This value represents the name of manufacturer that created the personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_MODEL	Persona Auto Vehicle Model	VARCHAR2(20)	This value represents the model name assigned by manufacturer of personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_MSRP	Persona Auto Vehicle Manufacturer's Suggested Retail Price	NUMBER (14, 3)	This number represents the price that the manufacturer tells the vehicle dealer the new vehicle is worth.
Datamart	PA_VEH_DIM	PA_VEH_MULT_CAR_DSCNT_FLG	Persona Auto Vehicle Multiple Car Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not multiple car discount applies.
Datamart	PA_VEH_DIM	PA_VEH_MULT_CAR_DSCNT_PCT	Persona Auto Vehicle Multiple Car Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when multiple car discount applies.
Datamart	PA_VEH_DIM	PA_VEH_NAT_KEY	Persona Auto Vehicle Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_NEW_OR_USED_CD	Persona Auto Vehicle New or Used Code	VARCHAR2(60)	This system code identifies if the insured is the original owner of the insured personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_NUM	Persona Auto Vehicle Number	NUMBER (22, 0)	This number identifies personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_NUM_DAYS_DRVN_PER_WK	Persona Auto Vehicle Number of Days Driven Per Week	NUMBER (22, 0)	This number represents the count of days vehicle is driven per calendar week.
Datamart	PA_VEH_DIM	PA_VEH_ONE_WAY_DIST_TO_WRK	Persona Auto Vehicle One Way Distance To Work	NUMBER (22, 0)	This number represents the number of distance units (miles/kilometers) to place of employment from residence.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PA_VEH_DIM	PA_VEH_OWNRSHP_TYP	Persona Auto Vehicle Ownership Type	VARCHAR2(60)	This value represents the classification that describes how a personal vehicle is owned and titled.
Datamart	PA_VEH_DIM	PA_VEH_PERF_CD	Persona Auto Vehicle Performance Code	VARCHAR2(60)	This system code identifies the performance level of the personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_PURCH_DT_ID	Persona Auto Vehicle Purchase Date Identifier	DATE	This calendar date represents when personal vehicle purchase date instance.
Datamart	PA_VEH_DIM	PA_VEH_PURCH_PRICE	Persona Auto Vehicle Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when personal vehicle was purchased.
Datamart	PA_VEH_DIM	PA_VEH_RATING_AGE	Persona Auto Vehicle Rating Age	VARCHAR2(60)	This value represents the age used to rate the personal vehicle, regardless of its actual age.
Datamart	PA_VEH_DIM	PA_VEH_STATED_AMT	Persona Auto Vehicle Stated Amount	NUMBER (14, 3)	This number represents the amount used to rate and value a personal vehicle when a symbol is not available or useful.
Datamart	PA_VEH_DIM	PA_VEH_SYM	Persona Auto Vehicle Symbol	VARCHAR2(60)	This value represents the cost symbol that represents a value in the personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_UDF_1	Persona Auto Vehicle User Defined Field 1	VARCHAR2(60)	This value describes the first personal vehicle user defined field.
Datamart	PA_VEH_DIM	PA_VEH_UDF_2	Persona Auto Vehicle User Defined Field 2	VARCHAR2(60)	This value describes the second personal vehicle user defined field.
Datamart	PA_VEH_DIM	PA_VEH_UDF_3	Persona Auto Vehicle User Defined Field 3	VARCHAR2(60)	This value describes the third personal vehicle user defined field.
Datamart	PA_VEH_DIM	PA_VEH_UDF_4	Persona Auto Vehicle User Defined Field 4	VARCHAR2(60)	This value describes the fourth personal vehicle user defined field.
Datamart	PA_VEH_DIM	PA_VEH_UDF_5	Persona Auto Vehicle User Defined Field 5	VARCHAR2(60)	This value describes the fifth personal vehicle user defined field.
Datamart	PA_VEH_DIM	PA_VEH_USE_CD	Persona Auto Vehicle Use Code	VARCHAR2(60)	This system code identifies the primary use of the personal vehicle.
Datamart	PA_VEH_DIM	PA_VEH_YR	Persona Auto Vehicle Year	CHAR(4)	This value represents the model year assigned by vehicle manufacturer.
Datamart	PA_VEH_DIM	PA_VIN	Persona Auto Vehicle Identification Number	VARCHAR2(25)	This value represents the unique identification number assigned by the vehicle's manufacturer.
Datamart	PLCY_DIM	ACTV_OR_CNCLD	Active Or Canceled Code Description	VARCHAR2(60)	This value describes the active or canceled code.
Datamart	PLCY_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the policy applies.
Datamart	PLCY_DIM	CNCL_REASON	Cancel Reason	VARCHAR2(60)	This value represents the cancellation reason.
Datamart	PLCY_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the policy is currently applicable.
Datamart	PLCY_DIM	END_DT	End Date	DATE	This calendar date represents when the policy is no longer valid.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PLCY_DIM	EXPO_BASIS	Exposure Basis	VARCHAR2(60)	This value represents the basis for which exposure applies.
Datamart	PLCY_DIM	MONOLINE_OR_PKG	Monoline or Package	VARCHAR2(60)	This value represents the indicator that describes if a policy is a monoline or a package policy.
Datamart	PLCY_DIM	NEW_OR_RENEWAL	New or Renewal	VARCHAR2(60)	This value represents the indicator that describes if the policy is a new business or renewal policy type.
Datamart	PLCY_DIM	PKG_DSCNT	Package Discount	VARCHAR2(60)	This value represents the indicator that describes the presence or absence of a discount for packaging of insurance coverage.
Datamart	PLCY_DIM	PKG_DSCNT_PCT	Package Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when package discount applies.
Datamart	PLCY_DIM	PKG_MOD_ASSIGNMENT_CD	Package Modification Assignment Code	VARCHAR2(60)	This system code indicates the package modification assignment.
Datamart	PLCY_DIM	PKG_MOD_FCT	Package Modification Factor	NUMBER (6, 3)	This number represents the percentage of premium waived as a result of packaging coverages.
Datamart	PLCY_DIM	PLCY_CNCL_DT_ID	Policy Cancellation Date Identifier	DATE	This calendar date iendtifies the policy cancellation date instance.
Datamart	PLCY_DIM	PLCY_EFF_DT_ID	Policy Effective Date Identifier	DATE	This calendar date represents the policy effective date instance.
Datamart	PLCY_DIM	PLCY_EXPR_DT_ID	Policy Expiration Date Identifier	DATE	This calendar date represents the policy expiration date instance.
Datamart	PLCY_DIM	PLCY_ID	Policy Identifier	NUMBER (22, 0)	This system generated number identifies the policy instance.
Datamart	PLCY_DIM	PLCY_NAT_KEY	Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the policy.
Datamart	PLCY_DIM	PLCY_NUM	Policy Number	VARCHAR2(25)	This value represents the number or other identifier that is assigned to policy.
Datamart	PLCY_DIM	PLCY_ORIG_INCPN_DT_ID	Policy Original Inception Date Identifier	DATE	This calendar date represents when identifies policy original inception date.
Datamart	PLCY_DIM	PLCY_TYP	Policy Type	VARCHAR2(60)	This value describes the type of coverage included in a policy.
Datamart	PLCY_DIM	PLCY_TYP_CATG	Policy Type Category	VARCHAR2(60)	This value represents the categorization of the type of coverage a policy includes.
Datamart	PLCY_DIM	PLCY_UDF_1	Policy User Defined Field 1	VARCHAR2(60)	This value describes the first policy user defined field.
Datamart	PLCY_DIM	PLCY_UDF_2	Policy User Defined Field 2	VARCHAR2(60)	This value describes the second policy user defined field.
Datamart	PLCY_DIM	PLCY_UDF_3	Policy User Defined Field 3	VARCHAR2(60)	This value describes the third policy user defined field.
Datamart	PLCY_DIM	PLCY_UDF_4	Policy User Defined Field 4	VARCHAR2(60)	This value describes the fourth policy user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PLCY_DIM	PLCY_UDF_5	Policy User Defined Field 5	VARCHAR2(60)	This value describes the fifth policy user defined field.
Datamart	PLCY_DIM	PLCY_VERSION	Policy Version	VARCHAR2(4)	This value represents the number or other identifier used by the company to identify 'this' version of the policy.
Datamart	PLCY_DIM	PREM_BASIS	Premium Basis	VARCHAR2(60)	This value represents the basis to which rates are applied to determine premiums.
Datamart	PLCY_DIM	RENEWAL_TERM	Renewal Term in Months	VARCHAR2(3)	This value represents the length of the renewal policy period (term) in months.
Datamart	PLCY_DIM	SUPPORTING_BUS_DSCNT_PCT	Supporting Business Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when supporting business discount applies.
Datamart	PLCY_DIM	SUPPORTING_BUS_TYP	Supporting Business Type	VARCHAR2(60)	This value represents the indicator that describes the type of policy that is also issued by the insurer.
Datamart	PLCY_MTH_SNAP_FACT	BILL_ACCT_ID	Billing Account Identifier	NUMBER (22, 0)	This system generated number identifies the billing account instance.
Datamart	PLCY_MTH_SNAP_FACT	CAL_MTH_ID	Calendar Month Identifier	NUMBER (22, 0)	This system generated number identifies the calendar month.
Datamart	PLCY_MTH_SNAP_FACT	CLASS_ID	Class Identifier	NUMBER (22, 0)	This system generated number identifies the class.
Datamart	PLCY_MTH_SNAP_FACT	CNCLD_PREM_PLCY_NAT_KEY	Canceled Premium Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the canceled premium.
Datamart	PLCY_MTH_SNAP_FACT	COVRG_ID	Coverage Identifier	NUMBER (22, 0)	This system generated number identifies coverage instance.
Datamart	PLCY_MTH_SNAP_FACT	COVRG_STATUS_ID	Coverage Status Identifier	NUMBER (22, 0)	This system generated number identifies coverage status instance.
Datamart	PLCY_MTH_SNAP_FACT	DC_ID	Distribution Channel Identifier	NUMBER (22, 0)	This system generated number identifies the distribution channel instance.
Datamart	PLCY_MTH_SNAP_FACT	DED_ID	Deductible Identifier	NUMBER (22, 0)	This system generated number identifies the deductible instance.
Datamart	PLCY_MTH_SNAP_FACT	DOC_CNCLD_PREM_AMT	Document Canceled Premium Amount	NUMBER (14, 3)	This number represents the document canceled premium amount.
Datamart	PLCY_MTH_SNAP_FACT	DOC_COMM_AMT	Document Commission Amount	NUMBER (14, 3)	This number represents the document commission amount.
Datamart	PLCY_MTH_SNAP_FACT	DOC_CURR_CD	Document Currency Code	VARCHAR2(25)	This system code identifies document currency.
Datamart	PLCY_MTH_SNAP_FACT	DOC_EFF_PREM_AMT	Document Effective Premium Amount	NUMBER (14, 3)	This number represents the document effective premium amount.
Datamart	PLCY_MTH_SNAP_FACT	DOC_ERND_EXPO_AMT	Document Earned Exposure Amount	NUMBER (14, 3)	This number represents the amount of written exposure that is recognized as earned within a given time period.
Datamart	PLCY_MTH_SNAP_FACT	DOC_ERND_PREM_AMT	Document Earned Premium Amount	NUMBER (14, 3)	This number represents the document earned premium amount.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PLCY_MTH_SNAP_FACT	DOC_EXPR_PREM_AMT	Document Expired Premium Amount	NUMBER (14, 3)	This number represents the document expired premium amount.
Datamart	PLCY_MTH_SNAP_FACT	DOC_FUTURE_WRTN_PREM_AMT	Document Future Written Premium Amount	NUMBER (14, 3)	This number represents the document future written premium amount.
Datamart	PLCY_MTH_SNAP_FACT	DOC_IN_FORCE_PREM_AMT	Document In-Force Premium Amount	NUMBER (14, 3)	This number represents the document in-force premium amount.
Datamart	PLCY_MTH_SNAP_FACT	DOC_PROC_PREM_AMT	Document Processed Premium Amount	NUMBER (14, 3)	This number represents the document processed premium amount.
Datamart	PLCY_MTH_SNAP_FACT	DOC_RETAINED_PREM_AMT	Document Retained Premium Amount	NUMBER (14, 3)	This number represents the document retained premium amount.
Datamart	PLCY_MTH_SNAP_FACT	DOC_WRTN_EXPO_AMT	Document Written Exposure Amount	NUMBER (14, 3)	This number represents the document written exposure amount.
Datamart	PLCY_MTH_SNAP_FACT	DOC_WRTN_PREM_AMT	Document Written Premium Amount	NUMBER (14, 3)	This number represents the document written premium amount.
Datamart	PLCY_MTH_SNAP_FACT	EFF_PREM_PLCY_NAT_KEY	Effective Premium Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the effective premium policy.
Datamart	PLCY_MTH_SNAP_FACT	EXPR_PREM_PLCY_NAT_KEY	Expired Premium Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the expired premium policy.
Datamart	PLCY_MTH_SNAP_FACT	FISCAL_MTH_ID	Fiscal Month Identifier	NUMBER (22, 0)	This number identifies fiscal month.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_CNCLD_PREM_AMT	Global 1 Canceled Premium Amount	NUMBER (14, 3)	This number represents the first global canceled premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_COMM_AMT	Global 1 Commission Amount	NUMBER (14, 3)	This number represents the first global commission amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_EFF_PREM_AMT	Global 1 Effective Premium Amount	NUMBER (14, 3)	This number represents the first global effective premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_ERND_EXPO_AMT	Global 1 Earned Exposure Amount	NUMBER (14, 3)	This number represents the amount of written exposure that is recognized as earned within a given time period.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_ERND_PREM_AMT	Global 1 Earned Premium Amount	NUMBER (14, 3)	This number represents the first global earned premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_EXPR_PREM_AMT	Global 1 Expired Premium Amount	NUMBER (14, 3)	This number represents the first global expired premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_FUTURE_WRTN_PREM_AMT	Global 1 Future Written Premium Amount	NUMBER (14, 3)	This number represents the first global future written premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_IN_FORCE_PREM_AMT	Global 1 In-Force Premium Amount	NUMBER (14, 3)	This number represents the first global in-force premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_PROC_PREM_AMT	Global 1 Processed Premium Amount	NUMBER (14, 3)	This number represents the first global processed premium amount.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_RETAINED_PREM_AMT	Global 1 Retained Premium Amount	NUMBER (14, 3)	This number represents the first global retained premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_WRTN_EXPO_AMT	Global 1 Written Exposure Amount	NUMBER (14, 3)	This number represents the first global written exposure amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_1_WRTN_PREM_AMT	Global 1 Written Premium Amount	NUMBER (14, 3)	This number represents the first global written premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_CNCLD_PREM_AMT	Global 2 Canceled Premium Amount	NUMBER (14, 3)	This number represents the second global canceled premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_COMM_AMT	Global 2 Commission Amount	NUMBER (14, 3)	This number represents the second global commission amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_EFF_PREM_AMT	Global 2 Effective Premium Amount	NUMBER (14, 3)	This number represents the second global effective premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_ERND_EXPO_AMT	Global 2 Earned Exposure Amount	NUMBER (14, 3)	This number represents the amount of written exposure that is recognized as earned within a given time period.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_ERND_PREM_AMT	Global 2 Earned Premium Amount	NUMBER (14, 3)	This number represents the second global earned premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_EXPR_PREM_AMT	Global 2 Expired Premium Amount	NUMBER (14, 3)	This number represents the second global expired premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_FUTURE_WRTN_PREM_AMT	Global 2 Future Written Premium Amount	NUMBER (14, 3)	This number represents the second global future written premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_IN_FORCE_PREM_AMT	Global 2 In-Force Premium Amount	NUMBER (14, 3)	This number represents the second global in-force premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_PROC_PREM_AMT	Global 2 Processed Premium Amount	NUMBER (14, 3)	This number represents the second global processed premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_RETAINED_PREM_AMT	Global 2 Retained Premium Amount	NUMBER (14, 3)	This number represents the second global retained premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_WRTN_EXPO_AMT	Global 2 Written Exposure Amount	NUMBER (14, 3)	This number represents the second global written exposure amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_2_WRTN_PREM_AMT	Global 2 Written Premium Amount	NUMBER (14, 3)	This number represents the second global written premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_CNCLD_PREM_AMT	Global 3 Canceled Premium Amount	NUMBER (14, 3)	This number represents the third global canceled premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_COMM_AMT	Global 3 Commission Amount	NUMBER (14, 3)	This number represents the third global commission amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_EFF_PREM_AMT	Global 3 Effective Premium Amount	NUMBER (14, 3)	This number represents the third global effective premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_ERND_EXPO_AMT	Global 3 Earned Exposure Amount	NUMBER (14, 3)	This number represents the amount of written exposure that is recognized as earned within a given time period.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_ERND_PREM_AMT	Global 3 Earned Premium Amount	NUMBER (14, 3)	This number represents the third global earned premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_EXPR_PREM_AMT	Global 3 Expired Premium Amount	NUMBER (14, 3)	This number represents the third global expired premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_FUTURE_WRTN_PREM_AMT	Global 3 Future Written Premium Amount	NUMBER (14, 3)	This number represents the third global future written premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_IN_FORCE_PREM_AMT	Global 3 In-Force Premium Amount	NUMBER (14, 3)	This number represents the third global in-force premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_PROC_PREM_AMT	Global 3 Processed Premium Amount	NUMBER (14, 3)	This number represents the third global processed premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_RETAINED_PREM_AMT	Global 3 Retained Premium Amount	NUMBER (14, 3)	This number represents the third global retained premium amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_WRTN_EXPO_AMT	Global 3 Written Exposure Amount	NUMBER (14, 3)	This number represents the third global written exposure amount.
Datamart	PLCY_MTH_SNAP_FACT	GLOBAL_3_WRTN_PREM_AMT	Global 3 Written Premium Amount	NUMBER (14, 3)	This number represents the monthly written premium amount based on the third global currency rate.
Datamart	PLCY_MTH_SNAP_FACT	GRP_PRG_ID	Group Program Identifier	NUMBER (22, 0)	This system generated number identifies the group program instance.
Datamart	PLCY_MTH_SNAP_FACT	IN_FORCE_PREM_PLCY_NAT_KEY	In-Force Premium Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the in-force premium policy.
Datamart	PLCY_MTH_SNAP_FACT	INSD_ID	Insured Identifier	NUMBER (22, 0)	This system generated number identifies the insured instance.
Datamart	PLCY_MTH_SNAP_FACT	INSUR_CO_ID	Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the insurance company instance in the monthly snapshot fact.
Datamart	PLCY_MTH_SNAP_FACT	LMT_ID	Limit Identifier	NUMBER (22, 0)	This system generated number identifies the limit instance.
Datamart	PLCY_MTH_SNAP_FACT	LOB_FACT_ID	Line Of Business Fact Identifier	NUMBER (22, 0)	This system generated number identifies the line of business fact instance.
Datamart	PLCY_MTH_SNAP_FACT	LOB_ID	Line Of Business Identifier	NUMBER (22, 0)	This system generated number identifies the line of business instance.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_CNCLD_PREM_AMT	Local Canceled Premium Amount	NUMBER (14, 3)	This number represents the local canceled premium amount.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_COMM_AMT	Local Commission Amount	NUMBER (14, 3)	This number represents the local commission amount.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_EFF_PREM_AMT	Local Effective Premium Amount	NUMBER (14, 3)	This number represents the local effective premium amount.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_ERND_EXPO_AMT	Local Earned Exposure Amount	NUMBER (14, 3)	This number represents the amount of written exposure that is recognized as earned within a given time period.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_ERND_PREM_AMT	Local Earned Premium Amount	NUMBER (14, 3)	This number represents the local earned premium amount.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_EXPR_PREM_AMT	Local Expired Premium Amount	NUMBER (14, 3)	This number represents the local expired premium amount.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_FUTURE_WRTN_PREM_AMT	Local Future Written Premium Amount	NUMBER (14, 3)	This number represents the local future written premium amount.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_IN_FORCE_PREM_AMT	Local In-Force Premium Amount	NUMBER (14, 3)	This number represents the local.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_PROC_PREM_AMT	Local Processed Premium Amount	NUMBER (14, 3)	This number represents the local processed premium amount.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_RETAINED_PREM_AMT	Local Retained Premium Amount	NUMBER (14, 3)	This number represents the local retained premium amount.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_WRTN_EXPO_AMT	Local Written Exposure Amount	NUMBER (14, 3)	This number represents the local written exposure amount.
Datamart	PLCY_MTH_SNAP_FACT	LOCAL_WRTN_PREM_AMT	Local Written Premium Amount	NUMBER (14, 3)	This number represents the local written premium amount.
Datamart	PLCY_MTH_SNAP_FACT	PARENT_INSUR_CO_ID	Parent Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the parent insurance company instance.
Datamart	PLCY_MTH_SNAP_FACT	PLCY_ID	Policy Identifier	NUMBER (22, 0)	This system generated number identifies the policy instance.
Datamart	PLCY_MTH_SNAP_FACT	PRODR_ID	Producer Identifier	NUMBER (22, 0)	This system generated number identifies the producer instance.
Datamart	PLCY_MTH_SNAP_FACT	REINS_CNTRCT_ID	Reinsurance Contract Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance contract instance.
Datamart	PLCY_MTH_SNAP_FACT	REINS_CO_ID	Reinsurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance company instance.
Datamart	PLCY_MTH_SNAP_FACT	RETAINED_PREM_PLCY_NAT_KEY	Retained Premium Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the retained premium.
Datamart	PLCY_MTH_SNAP_FACT	SUB_PRODR_ID	Sub Producer Identifier	NUMBER (22, 0)	This system generated number identifies the sub-producer instance.
Datamart	PLCY_MTH_SNAP_FACT	SYS_PROC_DT	System Process Date	DATE	This calendar date represents when the system processed the policy monthly snapshot fact table.
Datamart	PLCY_MTH_SNAP_FACT	UW_ASST_ID	Underwriting Assistant Identifier	NUMBER (22, 0)	This system generated number identifies the underwriting assistant instance.
Datamart	PLCY_MTH_SNAP_FACT	UW_ID	Underwriter Identifier	NUMBER (22, 0)	This system generated number identifies the underwriter instance.
Datamart	PLCY_MTH_SNAP_FACT	WRTN_PREM_PLCY_NAT_KEY	Written Premium Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the written premium policy.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PLCY_TRANS_CD_DIM	ONSET_OR_OFFSET	Onset or Offset	VARCHAR2(60)	This value represents the indicator that describes if a policy transaction is an onset transaction or offset transaction.
Datamart	PLCY_TRANS_CD_DIM	PLCY_TRANS_CATG_CD	Policy Transaction Category Code	VARCHAR2(60)	This system code identifies the policy transaction category.
Datamart	PLCY_TRANS_CD_DIM	PLCY_TRANS_CD	Policy Transaction Code	VARCHAR2(60)	This system code identifies the policy transaction.
Datamart	PLCY_TRANS_CD_DIM	PLCY_TRANS_CD_ID	Policy Transaction Code Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction code instance.
Datamart	PLCY_TRANS_CD_DIM	PREM_OR_NON_PREM	Premium or Non-Premium	VARCHAR2(60)	This value represents the indicator that describes if a policy transaction resulted in a change in the premium charged for an existing policy.
Datamart	PLCY_TRANS_CD_DIM	SYS_PLCY_TRANS_CD	System Policy Transaction Code	VARCHAR2(60)	This system code represents the system policy transaction.
Datamart	PLCY_TRANS_FACT	BILL_ACCT_ID	Billing Account Identifier	NUMBER (22, 0)	This system generated number identifies the billing account instance.
Datamart	PLCY_TRANS_FACT	BOOK_DT_ID	Book Date Identifier	DATE	This calendar date represents when identifies the book date instance.
Datamart	PLCY_TRANS_FACT	CLASS_ID	Class Identifier	NUMBER (22, 0)	This system generated number identifies the class instance.
Datamart	PLCY_TRANS_FACT	COMM_AMT	Commission Amount	NUMBER (14, 3)	This number represents the amount of commission to be paid for a transaction.
Datamart	PLCY_TRANS_FACT	COMM_RATE	Commission Rate	NUMBER (6, 5)	This number represents the rate at which the policy commission is to be paid.
Datamart	PLCY_TRANS_FACT	COVRG_ID	Coverage Identifier	NUMBER (22, 0)	This system generated number identifies coverage instance.
Datamart	PLCY_TRANS_FACT	COVRG_STATUS_ID	Coverage Status Identifier	NUMBER (22, 0)	This system generated number identifies coverage status instance.
Datamart	PLCY_TRANS_FACT	DC_ID	Distribution Channel Identifier	NUMBER (22, 0)	This system generated number identifies the distribution channel instance.
Datamart	PLCY_TRANS_FACT	DED_ID	Deductible Identifier	NUMBER (22, 0)	This system generated number identifies the deductible instance.
Datamart	PLCY_TRANS_FACT	DOC_CURR_CD	Document Currency Code	VARCHAR2(25)	This system code identifies document currency.
Datamart	PLCY_TRANS_FACT	GLOBAL_CURR_RATE_1	Global Currency Rate 1	NUMBER (22, 7)	This number represents the first global currency rate.
Datamart	PLCY_TRANS_FACT	GLOBAL_CURR_RATE_2	Global Currency Rate 2	NUMBER (22, 7)	This number represents the second global currency rate.
Datamart	PLCY_TRANS_FACT	GLOBAL_CURR_RATE_3	Global Currency Rate 3	NUMBER (22, 7)	This number represents the third global currency rate.
Datamart	PLCY_TRANS_FACT	GRP_PRG_ID	Group Program Identifier	NUMBER (22, 0)	This system generated number identifies the group program instance.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PLCY_TRANS_FACT	INSD_ID	Insured Identifier	NUMBER (22, 0)	This system generated number identifies the insured instance.
Datamart	PLCY_TRANS_FACT	INSUR_CO_ID	Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the insurance company instance.
Datamart	PLCY_TRANS_FACT	LMT_ID	Limit Identifier	NUMBER (22, 0)	This system generated number identifies the limit instance.
Datamart	PLCY_TRANS_FACT	LOB_FACT_ID	Line Of Business Fact Identifier	NUMBER (22, 0)	This system generated number identifies the line of business fact instance.
Datamart	PLCY_TRANS_FACT	LOB_ID	Line Of Business Identifier	NUMBER (22, 0)	This system generated number identifies the line of business instance.
Datamart	PLCY_TRANS_FACT	LOCAL_CURR_RATE	Local Currency Rate	NUMBER (22, 7)	This number represents the local currency rate.
Datamart	PLCY_TRANS_FACT	ORIG_PREM_AMT	Original Premium Amount	NUMBER (14, 3)	This number represents the original premium charge for the policy term.
Datamart	PLCY_TRANS_FACT	PARENT_INSUR_CO_ID	Parent Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the parent insurance company instance.
Datamart	PLCY_TRANS_FACT	PLCY_ID	Policy Identifier	NUMBER (22, 0)	This system generated number identifies the policy instance.
Datamart	PLCY_TRANS_FACT	PLCY_TRANS_AMT	Policy Transaction Amount	NUMBER (14, 3)	This number represents the amount of any transaction processed for a policy.
Datamart	PLCY_TRANS_FACT	PLCY_TRANS_CD_ID	Policy Transaction Code Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction code instance.
Datamart	PLCY_TRANS_FACT	PRODR_ID	Producer Identifier	NUMBER (22, 0)	This system generated number identifies the producer instance.
Datamart	PLCY_TRANS_FACT	REINS_CNTRCT_ID	Reinsurance Contract Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance contract instance.
Datamart	PLCY_TRANS_FACT	REINS_CO_ID	Reinsurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance contract instance.
Datamart	PLCY_TRANS_FACT	SRC_SYS_PROC_DT_ID	Source System Process Date Identifier	DATE	This calendar date represents the source system process date instance.
Datamart	PLCY_TRANS_FACT	SUB_PRODR_ID	Sub Producer Identifier	NUMBER (22, 0)	This system generated number identifies the sub-producer instance.
Datamart	PLCY_TRANS_FACT	SYS_PROC_DT	System Process Date	DATE	This calendar date represents when the system processed the policy transaction.
Datamart	PLCY_TRANS_FACT	TRANS_EFF_DT_ID	Transaction Effective Date Identifier	DATE	This calendar date represents the transaction effective date instance.
Datamart	PLCY_TRANS_FACT	UW_ASST_ID	Underwriting Assistant Identifier	NUMBER (22, 0)	This system generated number identifies the underwriting assistant instance.
Datamart	PLCY_TRANS_FACT	UW_ID	Underwriter Identifier	NUMBER (22, 0)	This system generated number identifies the underwriter instance.
Datamart	PLCY_TRANS_FACT	WRTN_EXPO_AMT	Written Exposure Amount	NUMBER (14, 3)	This number represents the measure of the loss exposure assumed by the insurer.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PRODR_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the producer applies.
Datamart	PRODR_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the producer is currently applicable.
Datamart	PRODR_DIM	END_DT	End Date	DATE	This calendar date represents when the producer is no longer valid.
Datamart	PRODR_DIM	PRODR_BIRTH_DT_ID	Producer Birth Date Identifier	DATE	This calendar date represents the producer's date of birth.
Datamart	PRODR_DIM	PRODR_BUS_START_DT_ID	Producer Business Start Date Identifier	DATE	This calendar date represents the producer business start date instance.
Datamart	PRODR_DIM	PRODR_CNTCT_DESC	Producer Contact Description	VARCHAR2(60)	This value describes a producer's contact method.
Datamart	PRODR_DIM	PRODR_CNTCT_TYP	Producer Contact Type	VARCHAR2(60)	This value represents the contact method for producer.
Datamart	PRODR_DIM	PRODR_CNTCT_UDF_1	Producer Contact User Defined Field 1	VARCHAR2(60)	This value describes the first producer contact user defined field.
Datamart	PRODR_DIM	PRODR_CNTCT_UDF_2	Producer Contact User Defined Field 2	VARCHAR2(60)	This value describes the second producer contact user defined field.
Datamart	PRODR_DIM	PRODR_CNTCT_UDF_3	Producer Contact User Defined Field 3	VARCHAR2(60)	This value describes the third producer contact user defined field.
Datamart	PRODR_DIM	PRODR_CNTCT_UDF_4	Producer Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth producer contact user defined field.
Datamart	PRODR_DIM	PRODR_CNTCT_UDF_5	Producer Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth producer contact user defined field.
Datamart	PRODR_DIM	PRODR_CNTY	Producer County	VARCHAR2(60)	This value identifies the county where producer is located.
Datamart	PRODR_DIM	PRODR_CTRY	Producer Country	VARCHAR2(60)	This value identifies the country where producer is located.
Datamart	PRODR_DIM	PRODR_CTY	Producer City	VARCHAR2(32)	This value identifies the city where producer is located.
Datamart	PRODR_DIM	PRODR_DBA	Producer Doing Business As	VARCHAR2(170)	This value represents the operational name of a producer's business.
Datamart	PRODR_DIM	PRODR_DSTRCT	Producer District	VARCHAR2(60)	This value represents the district where producer is located.
Datamart	PRODR_DIM	PRODR_EFF_DT_ID	Producer Effective Date Identifier	DATE	This calendar date represents the producer effective date instance.
Datamart	PRODR_DIM	PRODR_GENDER	Producer Gender	VARCHAR2(60)	This value represents the gender (male or female) of the producer.
Datamart	PRODR_DIM	PRODR_GEOG_BNDRY_UDF_1	Producer Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first producer geographic boundary user defined field.
Datamart	PRODR_DIM	PRODR_GEOG_BNDRY_UDF_2	Producer Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second producer geographic boundary user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PRODR_DIM	PRODR_GEOG_BNDRY_UDF_3	Producer Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third producer geographic boundary user defined field.
Datamart	PRODR_DIM	PRODR_GEOG_BNDRY_UDF_4	Producer Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth producer geographic boundary user defined field.
Datamart	PRODR_DIM	PRODR_GEOG_BNDRY_UDF_5	Producer Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth producer geographic boundary user defined field.
Datamart	PRODR_DIM	PRODR_GOVT_ID_NUM	Producer Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the producer. For example, in the USA: SSN or FEIN.
Datamart	PRODR_DIM	PRODR_ID	Producer Identifier	NUMBER (22, 0)	This system generated number identifies the producer instance.
Datamart	PRODR_DIM	PRODR_LATITUDE	Producer Latitude	VARCHAR2(11)	This value represents the latitude location of the producer
Datamart	PRODR_DIM	PRODR_LONGITUDE	Producer Longitude	VARCHAR2(11)	This value represents the longitude location of the producer
Datamart	PRODR_DIM	PRODR_MARITAL_STATUS	Producer Marital Status	VARCHAR2(60)	This value represents the present marital condition (single, married, divorced, widowed) of the producer.
Datamart	PRODR_DIM	PRODR_NAICS_CD	Producer North American Industry Classification System Code	VARCHAR2(60)	This value represents the North American Industry Classification System (NAICS) code issued to producer.
Datamart	PRODR_DIM	PRODR_NAT_KEY	Producer Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the producer.
Datamart	PRODR_DIM	PRODR_NM	Producer Name	VARCHAR2(170)	This value represents the full name of producer.
Datamart	PRODR_DIM	PRODR_NOB	Producer Nature of Business	VARCHAR2(60)	This value represents the type or category of the business activities done by the producer.
Datamart	PRODR_DIM	PRODR_NUM	Producer Number	VARCHAR2(10)	This value represents the number or other identifier assigned to the producer of the business.
Datamart	PRODR_DIM	PRODR_NUM_EMP	Producer Number of Employees	NUMBER (22, 0)	This number represents the count of people employed by producer.
Datamart	PRODR_DIM	PRODR_ORG_UDF_1	Producer Organization User Defined Field 1	VARCHAR2(60)	This value describes the first producer organization user defined field.
Datamart	PRODR_DIM	PRODR_ORG_UDF_2	Producer Organization User Defined Field 2	VARCHAR2(60)	This value describes the second producer organization user defined field.
Datamart	PRODR_DIM	PRODR_ORG_UDF_3	Producer Organization User Defined Field 3	VARCHAR2(60)	This value describes the third producer organization user defined field.
Datamart	PRODR_DIM	PRODR_ORG_UDF_4	Producer Organization User Defined Field 4	VARCHAR2(60)	This value describes the fourth producer organization user defined field.
Datamart	PRODR_DIM	PRODR_ORG_UDF_5	Producer Organization User Defined Field 5	VARCHAR2(60)	This value describes the fifth producer organization user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PRODR_DIM	PRODR_PARTY_UDF_1	Producer Party User Defined Field 1	VARCHAR2(60)	This value describes the first producer party user defined field.
Datamart	PRODR_DIM	PRODR_PARTY_UDF_2	Producer Party User Defined Field 2	VARCHAR2(60)	This value describes the second producer party user defined field.
Datamart	PRODR_DIM	PRODR_PARTY_UDF_3	Producer Party User Defined Field 3	VARCHAR2(60)	This value describes the third producer party user defined field.
Datamart	PRODR_DIM	PRODR_PARTY_UDF_4	Producer Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth producer party user defined field.
Datamart	PRODR_DIM	PRODR_PARTY_UDF_5	Producer Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth producer party user defined field.
Datamart	PRODR_DIM	PRODR_PERS_UDF_1	Producer Person on User Defined Field 1	VARCHAR2(60)	This value describes the first producer person user defined field.
Datamart	PRODR_DIM	PRODR_PERS_UDF_2	Producer Person on User Defined Field 2	VARCHAR2(60)	This value describes the second producer person user defined field.
Datamart	PRODR_DIM	PRODR_PERS_UDF_3	Producer Person on User Defined Field 3	VARCHAR2(60)	This value describes the third producer person user defined field.
Datamart	PRODR_DIM	PRODR_PERS_UDF_4	Producer Person on User Defined Field 4	VARCHAR2(60)	This value describes the fourth producer person user defined field.
Datamart	PRODR_DIM	PRODR_PERS_UDF_5	Producer Person on User Defined Field 5	VARCHAR2(60)	This value describes the fifth producer person user defined field.
Datamart	PRODR_DIM	PRODR_PRES_EMPLMT_START_YR	Producer Present Employment Start Year	CHAR(4)	This value represents the calendar year when producer began working for their current employer.
Datamart	PRODR_DIM	PRODR_PSTL_CD	Producer Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	PRODR_DIM	PRODR_PSTL_CD_PRFX	Producer Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	PRODR_DIM	PRODR_PSTL_SUB_CD	Producer Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	PRODR_DIM	PRODR_REGION	Producer Region	VARCHAR2(60)	This value represents the geographic region where producer is located.
Datamart	PRODR_DIM	PRODR_SIC_CD	Producer Standard Industrial Classification Code	VARCHAR2(60)	This system code is the SIC code assigned to the producer. The Standard Industrial Classification (SIC) code is an industry code that identifies the classification of business activity.
Datamart	PRODR_DIM	PRODR_STATE	Producer State	VARCHAR2(60)	This value identifies the state where producer is located.
Datamart	PRODR_DIM	PRODR_STATE_LIC_NUM	Producer State License Number	VARCHAR2(10)	This value represents the government-issued license number issued to producer.
Datamart	PRODR_DIM	PRODR_TAX_LOC_ID	Producer Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier in the producer's location.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PRODR_DIM	PRODR_TERR	Producer Territory	VARCHAR2(60)	This value represents the territory where producer is located.
Datamart	PRODR_DIM	PRODR_TYP	Producer Type	VARCHAR2(60)	This value describes the producer type.
Datamart	PRODR_DIM	PRODR_UDF_1	Producer User Defined Field 1	VARCHAR2(60)	This value describes the first producer user defined field.
Datamart	PRODR_DIM	PRODR_UDF_2	Producer User Defined Field 2	VARCHAR2(60)	This value describes the second producer user defined field.
Datamart	PRODR_DIM	PRODR_UDF_3	Producer User Defined Field 3	VARCHAR2(60)	This value describes the third producer user defined field.
Datamart	PRODR_DIM	PRODR_UDF_4	Producer User Defined Field 4	VARCHAR2(60)	This value describes the fourth producer user defined field.
Datamart	PRODR_DIM	PRODR_UDF_5	Producer User Defined Field 5	VARCHAR2(60)	This value describes the fifth producer user defined field.
Datamart	PU_FACT	PU_FACT_ID	Personal Umbrella Fact Identifier	NUMBER (22, 0)	This system generated number identifies the personal umbrella fact instance.
Datamart	PU_FACT	PU_PLCY_ID	Personal Umbrella Policy Identifier	NUMBER (22, 0)	This system generated number identifies the personal umbrella policy instance.
Datamart	PU_PLCY_DIM	PU_PLCY_DF_INSUR_CO_NM	Personal Umbrella Policy Dwelling Fire Insurance Company Name	VARCHAR2(170)	This value represents the insurance company name that issued insured's dwelling fire insurance policy.
Datamart	PU_PLCY_DIM	PU_PLCY_DF_PLCY_EFF_DT_ID	Personal Umbrella Policy Dwelling Fire Policy Effective Date Identifier	DATE	This value represents the personal umbrella dwelling fire policy effective date instance.
Datamart	PU_PLCY_DIM	PU_PLCY_DF_PLCY_EXPR_DT_ID	Personal Umbrella Policy Dwelling Fire Policy Expiration Date Identifier	DATE	This value represents the personal umbrella dwelling fire policy expiration date instance.
Datamart	PU_PLCY_DIM	PU_PLCY_DF_PLCY_NUM	Personal Umbrella Policy Dwelling Fire Policy Number	VARCHAR2(25)	This number or unique identifier identifes the personal umbrella policy dwelling fire policy.
Datamart	PU_PLCY_DIM	PU_PLCY_DF_PSNL_LIAB_LMT	Personal Umbrella Policy Dwelling Fire Personal Liability Limit	VARCHAR2(15)	This value represents the personal liability coverage limit included under an insured's dwelling fire insurance policy.
Datamart	PU_PLCY_DIM	PU_PLCY_HO_INSUR_CO_NM	Personal Umbrella Policy Homeowners Insurance Company Name	VARCHAR2(170)	This value represents the insurance company name for insured's homeowners insurance policy.
Datamart	PU_PLCY_DIM	PU_PLCY_HO_PLCY_EFF_DT_ID	Personal Umbrella Policy Homeowners Policy Effective Date Identifier	DATE	This calendar date represents the personal umbrella homeowners policy effective date instance.
Datamart	PU_PLCY_DIM	PU_PLCY_HO_PLCY_EXPR_DT_ID	Personal Umbrella Policy Homeowners Policy Expiration Date Identifier	DATE	This calendar date represents the personal umbrella homeowners policy expiration date instance.
Datamart	PU_PLCY_DIM	PU_PLCY_HO_PLCY_NUM	Personal Umbrella Policy Homeowners Policy Number	VARCHAR2(25)	This number or unique identifier identifes the personal umbrella policy homeowners policy.
Datamart	PU_PLCY_DIM	PU_PLCY_HO_PSNL_LIAB_LMT	Personal Umbrella Policy Homeowners Personal Liability Limit	VARCHAR2(15)	This value represents the personal liability coverage limit included under an insured's homeowners insurance policy.
Datamart	PU_PLCY_DIM	PU_PLCY_ID	Personal Umbrella Policy Identifier	NUMBER (22, 0)	This system generated number identifies the personal umbrella policy instance.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	PU_PLCY_DIM	PU_PLCY_NAT_KEY	Personal Umbrella Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the personal umbrella policy.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_INSUR_CO_NM	Personal Umbrella Policy Personal Auto Insurance Company Name	VARCHAR2(170)	This value represents the insurance company name for insured's personal vehicle insurance policy.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_LIAB_FIRST_LMT	Personal Umbrella Policy Personal Auto Liability First Limit	VARCHAR2(15)	This value represents the personal vehicle liability limit coverage first limit.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_LIAB_SECOND_LMT	Personal Umbrella Policy Personal Auto Liability Second Limit	VARCHAR2(15)	This value represents the personal vehicle policy liability coverage second limit.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_PLCY_EFF_DT_ID	Personal Umbrella Policy Personal Auto Policy Effective Date Identifier	DATE	This calendar date represents the personal umbrella policy personal vehicle policy instance.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_PLCY_EXPR_DT_ID	Personal Umbrella Policy Personal Auto Policy Expiration Date Identifier	DATE	This calendar date represents when personal vehicle insurance policy term ends.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_PLCY_NUM	Personal Umbrella Policy Personal Auto Policy Number	VARCHAR2(25)	This value represents the number or other identifier that identifies the specific personal vehicle policy.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_PROP_DMG_LMT	Personal Umbrella Policy Personal Auto Property Damage Limit	VARCHAR2(15)	This value represents the personal vehicle policy property damage coverage limit.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_UM_FIRST_LMT	Personal Umbrella Policy Personal Auto Uninsured Motorist First Limit	VARCHAR2(15)	This value represents the personal vehicle policy uninsured/underinsured motorist coverage first limit.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_UM_SECOND_LMT	Personal Umbrella Policy Personal Auto Uninsured Motorist Second Limit	VARCHAR2(15)	This value represents the personal vehicle policy uninsured/underinsured motorist coverage second limit.
Datamart	PU_PLCY_DIM	PU_PLCY_PA_UM_THIRD_LMT	Personal Umbrella Policy Personal Auto Uninsured Motorist Third Limit	VARCHAR2(15)	This value represents the personal vehicle policy uninsured/underinsured motorist coverage third limit.
Datamart	PU_PLCY_DIM	PU_PLCY_UDF_1	Personal Umbrella Policy User Defined Field 1	VARCHAR2(60)	This value describes the first personal umbrella policy user defined field.
Datamart	PU_PLCY_DIM	PU_PLCY_UDF_2	Personal Umbrella Policy User Defined Field 2	VARCHAR2(60)	This value describes the second personal umbrella policy user defined field.
Datamart	PU_PLCY_DIM	PU_PLCY_UDF_3	Personal Umbrella Policy User Defined Field 3	VARCHAR2(60)	This value describes the third personal umbrella policy user defined field.
Datamart	PU_PLCY_DIM	PU_PLCY_UDF_4	Personal Umbrella Policy User Defined Field 4	VARCHAR2(60)	This value describes the fourth personal umbrella policy user defined field.
Datamart	PU_PLCY_DIM	PU_PLCY_UDF_5	Personal Umbrella Policy User Defined Field 5	VARCHAR2(60)	This value describes the fifth personal umbrella policy user defined field.
Datamart	REINS_CNTRCT_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the reinsurance contract terms apply.
Datamart	REINS_CNTRCT_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the reinsurance contract is currently applicable.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	REINS_CNTRCT_DIM	END_DT	End Date	DATE	This calendar date represents when the reinsurance contract terms no longer apply.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_BEGIN_DT_ID	Reinsurance Contract Begin Date Identifier	DATE	This calendar date represents the reinsurance contract begin date instance.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_CATG	Reinsurance Contract Category	VARCHAR2(60)	This value represents the category of the reinsurance contract.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_CEDED_LOSS_RATIO	Reinsurance Contract Ceded Loss Ratio	NUMBER (6, 3)	This number represents the ratio of losses and loss adjustment expenses incurred to premiums earned in the portion of exposure that is transferred to a reinsurance company.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_CERT_NUM	Reinsurance Contract Certificate Number	VARCHAR2(8)	This value represents the unique number or other identifier assigned to the reinsurance contract certificate.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_CESSION_NUM	Reinsurance Contract Cession Number	VARCHAR2(10)	This value represents the number or other identifier of the reinsurance contract cession.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_END_DT_ID	Reinsurance Contract Ending Date Identifier	DATE	This calendar date represents when identifies when a reinsurance contract ends.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_FAC_COMM_PCT	Reinsurance Contract Faculative Commission Percent	NUMBER (6, 3)	This number represents the percentage commission paid to reinsurer.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_ID	Reinsurance Contract Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance contract instance.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_LAYER	Reinsurance Contract Layer	VARCHAR2(60)	This value represents the reinsurance contract layer describes the amount of reinsurance provided in the reinsurance contract.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_NAT_KEY	Reinsurance Contract Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the reinsurance contract.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_TREATY_NUM	Reinsurance Contract Treaty Number	VARCHAR2(8)	This value represents the unique number or other identifier assigned to a reinsurance contract treaty.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_TYP	Reinsurance Contract Type	VARCHAR2(60)	This value represents the attributes of the reinsurance contract.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_UDF_1	Reinsurance Contract User Defined Field 1	VARCHAR2(60)	This value describes the first reinsurance contract user defined field.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_UDF_2	Reinsurance Contract User Defined Field 2	VARCHAR2(60)	This value describes the second reinsurance contract user defined field.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_UDF_3	Reinsurance Contract User Defined Field 3	VARCHAR2(60)	This value describes the third reinsurance contract user defined field.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_UDF_4	Reinsurance Contract User Defined Field 4	VARCHAR2(60)	This value describes the fourth reinsurance contract user defined field.
Datamart	REINS_CNTRCT_DIM	REINS_CNTRCT_UDF_5	Reinsurance Contract User Defined Field 5	VARCHAR2(60)	This value describes the fifth reinsurance contract user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	REINS_CO_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the reinsurance company applies.
Datamart	REINS_CO_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the reinsurance company is currently applicable.
Datamart	REINS_CO_DIM	END_DT	End Date	DATE	This calendar date represents when the reinsurance company is no longer valid.
Datamart	REINS_CO_DIM	REINS_CO_BUS_START_DT_ID	Reinsurance Company Business Start Date Identifier	DATE	This calendar date represents when the reinsurance company began business operations.
Datamart	REINS_CO_DIM	REINS_CO_CNTCT_DESC	Reinsurance Company Contract Description	VARCHAR2(60)	This value describes the reinsurance company contract.
Datamart	REINS_CO_DIM	REINS_CO_CNTCT_TYP	Reinsurance Company Contact Type	VARCHAR2(60)	This value represents the contact method for reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_CNTCT_UDF_1	Reinsurance Company Contact User Defined Field 1	VARCHAR2(60)	This value describes the first reinsurance company contact user defined field.
Datamart	REINS_CO_DIM	REINS_CO_CNTCT_UDF_2	Reinsurance Company Contact User Defined Field 2	VARCHAR2(60)	This value describes the second reinsurance company contact user defined field.
Datamart	REINS_CO_DIM	REINS_CO_CNTCT_UDF_3	Reinsurance Company Contact User Defined Field 3	VARCHAR2(60)	This value describes the third reinsurance company contact user defined field.
Datamart	REINS_CO_DIM	REINS_CO_CNTCT_UDF_4	Reinsurance Company Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth reinsurance company contact user defined field.
Datamart	REINS_CO_DIM	REINS_CO_CNTCT_UDF_5	Reinsurance Company Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth reinsurance company contact user defined field.
Datamart	REINS_CO_DIM	REINS_CO_CNTY	Reinsurance Company County	VARCHAR2(60)	This value identifies the county where reinsurance company is located.
Datamart	REINS_CO_DIM	REINS_CO_CTRY	Reinsurance Company Country	VARCHAR2(60)	This value identifies the country where reinsurance company is located.
Datamart	REINS_CO_DIM	REINS_CO_CTY	Reinsurance Company City	VARCHAR2(32)	This value identifies the city where reinsurance company is located.
Datamart	REINS_CO_DIM	REINS_CO_DBA	Reinsurance Company Doing Business As	VARCHAR2(170)	This value represents operational name of a reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_DSTRCT	Reinsurance Company District	VARCHAR2(60)	This value represents the district where reinsurance company is located.
Datamart	REINS_CO_DIM	REINS_CO_GEOG_BNDRY_UDF_1	Reinsurance Company Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first reinsurance company geographic boundary user defined field.
Datamart	REINS_CO_DIM	REINS_CO_GEOG_BNDRY_UDF_2	Reinsurance Company Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second reinsurance company geographic boundary user defined field.
Datamart	REINS_CO_DIM	REINS_CO_GEOG_BNDRY_UDF_3	Reinsurance Company Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third reinsurance company geographic boundary user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	REINS_CO_DIM	REINS_CO_GEOG_BNDRY_UDF_4	Reinsurance Company Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth reinsurance company geographic boundary user defined field.
Datamart	REINS_CO_DIM	REINS_CO_GEOG_BNDRY_UDF_5	Reinsurance Company Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth reinsurance company geographic boundary user defined field.
Datamart	REINS_CO_DIM	REINS_CO_GOVT_ID_NUM	Reinsurance Company Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the reinsurance company. For example, in the USA: SSN or FEIN.
Datamart	REINS_CO_DIM	REINS_CO_ID	Reinsurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance company instance.
Datamart	REINS_CO_DIM	REINS_CO_LATITUDE	Reinsurance Company Latitude	VARCHAR2(11)	This value represents the latitude location of the reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_LONGITUDE	Reinsurance Company Longitude	VARCHAR2(11)	This value represents the longitude location of the reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_NAICS_CD	Reinsurance Company North American Industry Classification System Code	VARCHAR2(60)	This value represents the North America Industry Class (NAICS) code assigned to the reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_NAT_KEY	Reinsurance Company Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_NM	Reinsurance Company Name	VARCHAR2(170)	This value represents the name of the reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_NOB	Reinsurance Company Nature of Business	VARCHAR2(60)	This value represents the type or category of the business activities done by the reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_NUM	Reinsurance Company Number	VARCHAR2(4)	This value represents the number or other identifier assigned to the reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_NUM_EMP	Reinsurance Company Number of Employees	NUMBER (22, 0)	This number represents the count of people employed by reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_ORG_UDF_1	Reinsurance Company Organization User Defined Field 1	VARCHAR2(60)	This value describes the first reinsurance company organization user defined field.
Datamart	REINS_CO_DIM	REINS_CO_ORG_UDF_2	Reinsurance Company Organization User Defined Field 2	VARCHAR2(60)	This value describes the second reinsurance company organization user defined field.
Datamart	REINS_CO_DIM	REINS_CO_ORG_UDF_3	Reinsurance Company Organization User Defined Field 3	VARCHAR2(60)	This value describes the third reinsurance company organization user defined field.
Datamart	REINS_CO_DIM	REINS_CO_ORG_UDF_4	Reinsurance Company Organization User Defined Field 4	VARCHAR2(60)	This value describes the fourth reinsurance company organization user defined field.
Datamart	REINS_CO_DIM	REINS_CO_ORG_UDF_5	Reinsurance Company Organization User Defined Field 5	VARCHAR2(60)	This value describes the fifth reinsurance company organization user defined field.
Datamart	REINS_CO_DIM	REINS_CO_PARTY_UDF_1	Reinsurance Company Party User Defined Field 1	VARCHAR2(60)	This value describes the first reinsurance company party user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	REINS_CO_DIM	REINS_CO_PARTY_UDF_2	Reinsurance Company Party User Defined Field 2	VARCHAR2(60)	This value describes the second reinsurance company party user defined field.
Datamart	REINS_CO_DIM	REINS_CO_PARTY_UDF_3	Reinsurance Company Party User Defined Field 3	VARCHAR2(60)	This value describes the third reinsurance company party user defined field.
Datamart	REINS_CO_DIM	REINS_CO_PARTY_UDF_4	Reinsurance Company Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth reinsurance company party user defined field.
Datamart	REINS_CO_DIM	REINS_CO_PARTY_UDF_5	Reinsurance Company Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth reinsurance company party user defined field.
Datamart	REINS_CO_DIM	REINS_CO_PSTL_CD	Reinsurance Company Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	REINS_CO_DIM	REINS_CO_PSTL_CD_PRFX	Reinsurance Company Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	REINS_CO_DIM	REINS_CO_PSTL_SUB_CD	Reinsurance Company Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	REINS_CO_DIM	REINS_CO_REGION	Reinsurance Company Region	VARCHAR2(60)	This value represents the geographic region of the reinsurance company.
Datamart	REINS_CO_DIM	REINS_CO_SIC_CD	Reinsurance Company Standard Industrial Classification Code	VARCHAR2(60)	This system code is the SIC code assigned to the reinsurance company. The Standard Industrial Classification (SIC) code is an industry code that identifies the classification of business activity.
Datamart	REINS_CO_DIM	REINS_CO_STATE	Reinsurance Company State	VARCHAR2(60)	This value identifies the state where the reinsurance company is located.
Datamart	REINS_CO_DIM	REINS_CO_TAX_LOC_ID	Reinsurance Company Tax Location Identifier	VARCHAR2(6)	This value represents the reinsurance company tax location instance.
Datamart	REINS_CO_DIM	REINS_CO_TERR	Reinsurance Company Territory	VARCHAR2(60)	This value represents the territory where the reinsurance company is located.
Datamart	REINS_CO_DIM	REINS_CO_TYP	Reinsurance Company Type	VARCHAR2(60)	This value represents the classification of the activities of a reinsurance company. Examples include proportional and non-proportional.
Datamart	REINS_CO_DIM	REINS_CO_UDF_1	Reinsurance Company User Defined Field 1	VARCHAR2(60)	This value describes the first reinsurance company user defined field.
Datamart	REINS_CO_DIM	REINS_CO_UDF_2	Reinsurance Company User Defined Field 2	VARCHAR2(60)	This value describes the second reinsurance company user defined field.
Datamart	REINS_CO_DIM	REINS_CO_UDF_3	Reinsurance Company User Defined Field 3	VARCHAR2(60)	This value describes the third reinsurance company user defined field.
Datamart	REINS_CO_DIM	REINS_CO_UDF_4	Reinsurance Company User Defined Field 4	VARCHAR2(60)	This value describes the fourth reinsurance company user defined field.
Datamart	REINS_CO_DIM	REINS_CO_UDF_5	Reinsurance Company User Defined Field 5	VARCHAR2(60)	This value describes the fifth reinsurance company user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	SUPPLIER_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the supplier applies.
Datamart	SUPPLIER_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the supplier is currently applicable.
Datamart	SUPPLIER_DIM	END_DT	End Date	DATE	This calendar date represents when the supplier is no longer valid.
Datamart	SUPPLIER_DIM	PREF_SUPPLIER_CD	Preferred Supplier Code	VARCHAR2(60)	This system code identifies if a supplier is a preferred supplier.
Datamart	SUPPLIER_DIM	PREF_SUPPLIER_TYP	Preferred Supplier Type	VARCHAR2(60)	This value represents the classification assigned to preferred suppliers based on company-defined attributes.
Datamart	SUPPLIER_DIM	SUPPLIER_BIRTH_DT_ID	Supplier Birth Date Identifier	DATE	This calendar date represents the supplier's date of birth.
Datamart	SUPPLIER_DIM	SUPPLIER_BUS_START_DT_ID	Supplier Business Start Date Identifier	DATE	This calendar date represents when the supplier began business operations.
Datamart	SUPPLIER_DIM	SUPPLIER_CATG	Supplier Category	VARCHAR2(60)	This value represents the category of supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_CNTCT_DESC	Supplier Category Description	VARCHAR2(60)	This value describes the supplier category.
Datamart	SUPPLIER_DIM	SUPPLIER_CNTCT_TYP	Supplier Contact Type	VARCHAR2(60)	This value represents the contact method for supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_CNTCT_UDF_1	Supplier Contact User Defined Field 1	VARCHAR2(60)	This value describes the first supplier contact user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_CNTCT_UDF_2	Supplier Contact User Defined Field 2	VARCHAR2(60)	This value describes the second supplier contact user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_CNTCT_UDF_3	Supplier Contact User Defined Field 3	VARCHAR2(60)	This value describes the third supplier contact user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_CNTCT_UDF_4	Supplier Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth supplier contact user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_CNTCT_UDF_5	Supplier Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth supplier contact user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_CNTY	Supplier County	VARCHAR2(60)	This value identifies the county where supplier is located.
Datamart	SUPPLIER_DIM	SUPPLIER_CTRY	Supplier Country	VARCHAR2(60)	This value identifies the country where supplier is located.
Datamart	SUPPLIER_DIM	SUPPLIER_CTY	Supplier City	VARCHAR2(32)	This value identifies the city where supplier is located.
Datamart	SUPPLIER_DIM	SUPPLIER_DBA	Supplier Doing Business As	VARCHAR2(170)	This value represents the type or category of the business activities done by the reinsurance company.
Datamart	SUPPLIER_DIM	SUPPLIER_DSTRCT	Supplier District	VARCHAR2(60)	This value represents the district where supplier is located.
Datamart	SUPPLIER_DIM	SUPPLIER_GENDER	Supplier Gender	VARCHAR2(60)	This value represents the gender (male or female) of the supplier.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	SUPPLIER_DIM	SUPPLIER_GEOG_BNDRY_UDF_1	Supplier Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first supplier geographic boundary user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_GEOG_BNDRY_UDF_2	Supplier Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second supplier geographic boundary user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_GEOG_BNDRY_UDF_3	Supplier Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third supplier geographic boundary user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_GEOG_BNDRY_UDF_4	Supplier Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth supplier geographic boundary user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_GEOG_BNDRY_UDF_5	Supplier Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth supplier geographic boundary user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_GOVT_ID_NUM	Supplier Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the supplier. For example, in the USA: SSN or FEIN.
Datamart	SUPPLIER_DIM	SUPPLIER_ID	Supplier Identifier	NUMBER (22, 0)	This system generated number identifies the supplier instance.
Datamart	SUPPLIER_DIM	SUPPLIER_LATITUDE	Supplier Latitude	VARCHAR2(11)	This value represents the latitude location of the supplier location.
Datamart	SUPPLIER_DIM	SUPPLIER_LONGITUDE	Supplier Longitude	VARCHAR2(11)	This value represents the longitude location of the supplier location.
Datamart	SUPPLIER_DIM	SUPPLIER_MARITAL_STATUS	Supplier Marital Status	VARCHAR2(60)	This value represents the present marital condition (single, married, divorced, widowed) of the supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_NAICS_CD	Supplier North American Industry Classification System Code	VARCHAR2(60)	This value represents the North America Industry Class (NAICS) code assigned to supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_NAT_KEY	Supplier Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_NM	Supplier Name	VARCHAR2(170)	This value represents the name of supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_NOB	Supplier Nature of Business	VARCHAR2(60)	This value represents the type or category of the business activities done by the supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_NUM_EMP	Supplier Number of Employees	NUMBER (22, 0)	This number represents the count of people employed by supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_ORG_UDF_1	Supplier Organization User Defined Field 1	VARCHAR2(60)	This value describes the first supplier organization user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_ORG_UDF_2	Supplier Organization User Defined Field 2	VARCHAR2(60)	This value describes the second supplier organization user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_ORG_UDF_3	Supplier Organization User Defined Field 3	VARCHAR2(60)	This value describes the third supplier organization user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_ORG_UDF_4	Supplier Organization User Defined Field 4	VARCHAR2(60)	This value describes the fourth supplier organization user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_ORG_UDF_5	Supplier Organization User Defined Field 5	VARCHAR2(60)	This value describes the fifth supplier organization user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	SUPPLIER_DIM	SUPPLIER_PARTY_UDF_1	Supplier Party User Defined Field 1	VARCHAR2(60)	This value describes the first supplier party user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PARTY_UDF_2	Supplier Party User Defined Field 2	VARCHAR2(60)	This value describes the second supplier party user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PARTY_UDF_3	Supplier Party User Defined Field 3	VARCHAR2(60)	This value describes the third supplier party user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PARTY_UDF_4	Supplier Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth supplier party user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PARTY_UDF_5	Supplier Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth supplier party user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PERS_UDF_1	Supplier Person User Defined Field 1	VARCHAR2(60)	This value describes the first supplier person user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PERS_UDF_2	Supplier Person User Defined Field 2	VARCHAR2(60)	This value describes the second supplier person user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PERS_UDF_3	Supplier Person User Defined Field 3	VARCHAR2(60)	This value describes the third supplier person user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PERS_UDF_4	Supplier Person User Defined Field 4	VARCHAR2(60)	This value describes the fourth supplier person user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PERS_UDF_5	Supplier Person User Defined Field 5	VARCHAR2(60)	This value describes the fifth supplier person user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_PRES_EMPLMT_START_YR	Supplier Present Employment Start Year	CHAR(4)	This value represents the calendar year that the supplier began working for their current employer.
Datamart	SUPPLIER_DIM	SUPPLIER_PSTL_CD	Supplier Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	SUPPLIER_DIM	SUPPLIER_PSTL_CD_PRFX	Supplier Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	SUPPLIER_DIM	SUPPLIER_PSTL_SUB_CD	Supplier Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	SUPPLIER_DIM	SUPPLIER_REGION	Supplier Region	VARCHAR2(60)	This value represents the geographic region where supplier is located.
Datamart	SUPPLIER_DIM	SUPPLIER_SIC_CD	Supplier Standard Industrial Classification Code	VARCHAR2(60)	This system code is the SIC code assigned to the supplier. The Standard Industrial Classification (SIC) code is an industry code that identifies the classification of business activity.
Datamart	SUPPLIER_DIM	SUPPLIER_STATE	Supplier State	VARCHAR2(60)	This value identifies the state where supplier is located.
Datamart	SUPPLIER_DIM	SUPPLIER_TAX_LOC_ID	Supplier Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier in the supplier's location.
Datamart	SUPPLIER_DIM	SUPPLIER_TERR	Supplier Territory	VARCHAR2(60)	This value represents the territory where supplier is located.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	SUPPLIER_DIM	SUPPLIER_TYP	Supplier Type	VARCHAR2(60)	This value represents the classification that describes supplier.
Datamart	SUPPLIER_DIM	SUPPLIER_UDF_1	Supplier User Defined Field 1	VARCHAR2(60)	This value describes the first supplier user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_UDF_2	Supplier User Defined Field 2	VARCHAR2(60)	This value describes the second supplier user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_UDF_3	Supplier User Defined Field 3	VARCHAR2(60)	This value describes the third supplier user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_UDF_4	Supplier User Defined Field 4	VARCHAR2(60)	This value describes the fourth supplier user defined field.
Datamart	SUPPLIER_DIM	SUPPLIER_UDF_5	Supplier User Defined Field 5	VARCHAR2(60)	This value describes the fifth supplier user defined field.
Datamart	TIME_DIM	AM_PM_CD	Indication of the time of day - AM: ante meridiem (before midday/noon), PM: post meridiem (after midday/noon)	VARCHAR2(2)	This value represents the code indicates whether time of day is before or after midday.
Datamart	TIME_DIM	HR_12_LONG	Hour 12 Long	VARCHAR2(8)	This value represents the ong name for Hour 12.
Datamart	TIME_DIM	HR_12_NUM	Hour 12 Number	NUMBER (22, 0)	This number identifies Hour 12.
Datamart	TIME_DIM	HR_12_SHORT	Hour 12 Short	VARCHAR2(5)	This value represents the abbreviated name for Hour 12.
Datamart	TIME_DIM	HR_24_LONG	Hour 24 Long	VARCHAR2(5)	This value represents the long name for Hour 24.
Datamart	TIME_DIM	HR_24_NUM	Hour 24 Number	NUMBER (22, 0)	This number identifies Hour 24.
Datamart	TIME_DIM	TIME_ID	Time Identifier	NUMBER (22, 0)	This number identifies the time.
Datamart	UW_DIM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the underwriter applies.
Datamart	UW_DIM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the underwriter is currently applicable.
Datamart	UW_DIM	END_DT	End Date	DATE	This calendar date represents when the underwriter is no longer valid.
Datamart	UW_DIM	UW_BIRTH_DT_ID	Underwriter Birth Date Identifier	DATE	This calendar date represents the underwriter's date of birth.
Datamart	UW_DIM	UW_CNTCT_DESC	Underwriter Contact Description	VARCHAR2(60)	This value describes the contact method for underwriter.
Datamart	UW_DIM	UW_CNTCT_TYP	Underwriter Contact Type	VARCHAR2(60)	This value represents the contact method for the underwriter.
Datamart	UW_DIM	UW_CNTCT_UDF_1	Underwriter Contact User Defined Field 1	VARCHAR2(60)	This value describes the first underwriter contact user defined field.
Datamart	UW_DIM	UW_CNTCT_UDF_2	Underwriter Contact User Defined Field 2	VARCHAR2(60)	This value describes the second underwriter contact user defined field.
Datamart	UW_DIM	UW_CNTCT_UDF_3	Underwriter Contact User Defined Field 3	VARCHAR2(60)	This value describes the third underwriter contact user defined field.
Datamart	UW_DIM	UW_CNTCT_UDF_4	Underwriter Contact User Defined Field 4	VARCHAR2(60)	This value describes the fourth underwriter contact user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	UW_DIM	UW_CNTCT_UDF_5	Underwriter Contact User Defined Field 5	VARCHAR2(60)	This value describes the fifth underwriter contact user defined field.
Datamart	UW_DIM	UW_CNTY	Underwriter County	VARCHAR2(60)	This value identifies the county of the underwriter's location.
Datamart	UW_DIM	UW_CTRY	Underwriter Country	VARCHAR2(60)	This value identifies the country of the underwriter's location.
Datamart	UW_DIM	UW_CTY	Underwriter City	VARCHAR2(32)	This value identifies the city of the underwriter's location.
Datamart	UW_DIM	UW_DSTRCT	Underwriter District	VARCHAR2(60)	This value identifies the district of the underwriter's location.
Datamart	UW_DIM	UW_GENDER	Underwriter Gender	VARCHAR2(60)	This value identifies the gender (male or female) of the underwriter.
Datamart	UW_DIM	UW_GEOG_BNDRY_UDF_1	Underwriter Geographic Boundary User Defined Field 1	VARCHAR2(60)	This value describes the first underwriter geographic boundary user defined field.
Datamart	UW_DIM	UW_GEOG_BNDRY_UDF_2	Underwriter Geographic Boundary User Defined Field 2	VARCHAR2(60)	This value describes the second underwriter geographic boundary user defined field.
Datamart	UW_DIM	UW_GEOG_BNDRY_UDF_3	Underwriter Geographic Boundary User Defined Field 3	VARCHAR2(60)	This value describes the third underwriter geographic boundary user defined field.
Datamart	UW_DIM	UW_GEOG_BNDRY_UDF_4	Underwriter Geographic Boundary User Defined Field 4	VARCHAR2(60)	This value describes the fourth underwriter geographic boundary user defined field.
Datamart	UW_DIM	UW_GEOG_BNDRY_UDF_5	Underwriter Geographic Boundary User Defined Field 5	VARCHAR2(60)	This value describes the fifth underwriter geographic boundary user defined field.
Datamart	UW_DIM	UW_GOVT_ID_NUM	Underwriter Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the underwriter. For example, in the USA: SSN or FEIN.
Datamart	UW_DIM	UW_ID	Underwriter Identifier	NUMBER (22, 0)	This system generated number identifies the underwriter instance.
Datamart	UW_DIM	UW_LATITUDE	Underwriter Latitude	VARCHAR2(11)	This value identifies the latitude location of underwriter.
Datamart	UW_DIM	UW_LONGITUDE	Underwriter Longitude	VARCHAR2(11)	This value identifies the longitude location of underwriter.
Datamart	UW_DIM	UW_MARITAL_STATUS	Underwriter Marital Status	VARCHAR2(60)	This value identifies the present marital condition (single, married, divorced, widowed) of the underwriter.
Datamart	UW_DIM	UW_NAT_KEY	Underwriter Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the underwriter.
Datamart	UW_DIM	UW_NM	Underwriter Name	VARCHAR2(170)	This value represents the name of underwriter.
Datamart	UW_DIM	UW_NUM	Underwriter Number	VARCHAR2(25)	This value identifies the number or other identifier that identifies the underwriter.
Datamart	UW_DIM	UW_PARTY_UDF_1	Underwriter Party User Defined Field 1	VARCHAR2(60)	This value describes the first underwriter party user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	UW_DIM	UW_PARTY_UDF_2	Underwriter Party User Defined Field 2	VARCHAR2(60)	This value describes the second underwriter party user defined field.
Datamart	UW_DIM	UW_PARTY_UDF_3	Underwriter Party User Defined Field 3	VARCHAR2(60)	This value describes the third underwriter party user defined field.
Datamart	UW_DIM	UW_PARTY_UDF_4	Underwriter Party User Defined Field 4	VARCHAR2(60)	This value describes the fourth underwriter party user defined field.
Datamart	UW_DIM	UW_PARTY_UDF_5	Underwriter Party User Defined Field 5	VARCHAR2(60)	This value describes the fifth underwriter party user defined field.
Datamart	UW_DIM	UW_PERS_UDF_1	Underwriter Person User Defined Field 1	VARCHAR2(60)	This value describes the first underwriter person user defined field.
Datamart	UW_DIM	UW_PERS_UDF_2	Underwriter Person User Defined Field 2	VARCHAR2(60)	This value describes the second underwriter person user defined field.
Datamart	UW_DIM	UW_PERS_UDF_3	Underwriter Person User Defined Field 3	VARCHAR2(60)	This value describes the third underwriter person user defined field.
Datamart	UW_DIM	UW_PERS_UDF_4	Underwriter Person User Defined Field 4	VARCHAR2(60)	This value describes the fourth underwriter person user defined field.
Datamart	UW_DIM	UW_PERS_UDF_5	Underwriter Person User Defined Field 5	VARCHAR2(60)	This value describes the fifth underwriter person user defined field.
Datamart	UW_DIM	UW_PRES_EMPLMT_START_YR	Underwriter Present Employment Start Year	CHAR(4)	This value represents the calendar year that the underwriter began employment at current employer.
Datamart	UW_DIM	UW_PSTL_CD	Underwriter Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Datamart	UW_DIM	UW_PSTL_CD_PRFX	Underwriter Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Datamart	UW_DIM	UW_PSTL_SUB_CD	Underwriter Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Datamart	UW_DIM	UW_REGION	Underwriter Region	VARCHAR2(60)	This value represents the geographic region of the underwriter's location.
Datamart	UW_DIM	UW_STATE	Underwriter State	VARCHAR2(60)	This value identifies the state of the underwriter's location.
Datamart	UW_DIM	UW_TAX_LOC_ID	Underwriter Tax Location Identifier	VARCHAR2(6)	This value represents the tax location identifier in the underwriter's location.
Datamart	UW_DIM	UW_TERR	Underwriter Territory	VARCHAR2(60)	This value represents the territory of the underwriter's location.
Datamart	UW_DIM	UW_TYP	Underwriter Type	VARCHAR2(60)	This value represents the classification of the underwriter's role.
Datamart	UW_DIM	UW_UDF_1	Underwriter User Defined Field 1	VARCHAR2(60)	This value describes the first underwriter user defined field.
Datamart	UW_DIM	UW_UDF_2	Underwriter User Defined Field 2	VARCHAR2(60)	This value describes the second underwriter user defined field.

Datamart (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Datamart	UW_DIM	UW_UDF_3	Underwriter User Defined Field 3	VARCHAR2(60)	This value describes the third underwriter user defined field.
Datamart	UW_DIM	UW_UDF_4	Underwriter User Defined Field 4	VARCHAR2(60)	This value describes the fourth underwriter user defined field.
Datamart	UW_DIM	UW_UDF_5	Underwriter User Defined Field 5	VARCHAR2(60)	This value describes the fifth underwriter user defined field.

Staging

Staging

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	BILL_ACCT	BILL_ACCT_NAT_KEY	Billing Account Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the billing account.
Staging	BILL_ACCT	BILL_ACCT_NUM	Billing Account Number	VARCHAR2(20)	This value represents the number of the account.
Staging	BILL_ACCT	BILL_ACCT_UDF_CD_1	Billing Account User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first billing account user defined field.
Staging	BILL_ACCT	BILL_ACCT_UDF_CD_2	Billing Account User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second billing account user defined field.
Staging	BILL_ACCT	BILL_ACCT_UDF_CD_3	Billing Account User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third billing account user defined field.
Staging	BILL_ACCT	BILL_ACCT_UDF_CD_4	Billing Account User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth billing account user defined field.
Staging	BILL_ACCT	BILL_ACCT_UDF_CD_5	Billing Account User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth billing account user defined field.
Staging	BILL_ACCT	METH_OF_PMT_CD	Method of Payment Code	VARCHAR2(25)	This system code indicates the means by which the payment was/will be made and type of account being credited or debited.g. for premium payment, a credit card may be charged, and for a claim payment , a checking account may be credited).
Staging	BILL_ACCT	PMT_PLAN_CD	Payment Plan Code	VARCHAR2(25)	This system code identifies the frequency of premium payment.
Staging	BILL_ACCT	PMT_SVC_CD	Payment Service Code	VARCHAR2(25)	This system code identifies the type of billing plan used.
Staging	BILL_ACCT	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the billing account with a specific transaction.
Staging	CA_DRV	CA_DRV_UDF_CD_1	Commercial Auto Driver User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first commercial auto driver user defined field.
Staging	CA_DRV	CA_DRV_UDF_CD_2	Commercial Auto Driver User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second commercial auto driver user defined field.
Staging	CA_DRV	CA_DRV_UDF_CD_3	Commercial Auto Driver User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third commercial auto driver user defined field.
Staging	CA_DRV	CA_DRV_UDF_CD_4	Commercial Auto Driver User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth commercial auto driver user defined field.
Staging	CA_DRV	CA_DRV_UDF_CD_5	Commercial Auto Driver User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth commercial auto driver user defined field.
Staging	CA_DRV	DFEN_DRV_CD	Defensive Driving Code	VARCHAR2(25)	This system code indicates the type of defensive driving course the commercial auto driver completed.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CA_DRV	DFEN_DRV_TRNG_DSCNT_FLG	Defensive Driving Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a defensive driver training discount applies.
Staging	CA_DRV	DFEN_DRV_TRNG_DSCNT_PCT	Defensive Driving Training Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when driver training discount applies.
Staging	CA_DRV	DRV_ACCID_CNT	Driver Accident Count	NUMBER (22,0)	This number represents the number of accidents a driver has been charged against his or her driving record.
Staging	CA_DRV	DRV_CLASS_CD	Driver Class Code	VARCHAR2(25)	This system code identifies the driver class.
Staging	CA_DRV	DRV_DWI_DUI_VIOLATION_CNT	Driver DWI / DUI Violation Count	NUMBER (22,0)	This number represents the count of Driving While Intoxicated (DWI) and/or Driving Under the Influence (DUI) violations charged against the driver's driving record.
Staging	CA_DRV	DRV_INTRMDT_VIOLATION_CNT	Driver Intermediate Violation Count	NUMBER (22,0)	This number represents the count of intermediate violations charged against the driver's driving record.
Staging	CA_DRV	DRV_LIC_ISSUED_BY_CD	Driver License Issued By Code	VARCHAR2(25)	This system code indentifies which entity granted driving privileges to driver.
Staging	CA_DRV	DRV_LIC_STATUS_CD	Driver License Status Code	VARCHAR2(25)	This system code indicates the driver license status.
Staging	CA_DRV	DRV_MAJOR_VIOLATION_CNT	Driver Major Violation Count	NUMBER (22,0)	This number represents the count of major violations charged against the driver's driving record.
Staging	CA_DRV	DRV_MINOR_VIOLATION_CNT	Driver Minor Violation Count	NUMBER (22,0)	This number represents the count of minor violations charged against the driver's driving record.
Staging	CA_DRV	DRV_NUM	Driver Number	NUMBER (22,0)	This number identifies the driver.
Staging	CA_DRV	DRV_STATUS_CD	Driver Status Code	VARCHAR2(25)	This system code indicates the driver status.
Staging	CA_DRV	DRV_TRNG_DSCNT_FLG	Driver Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not driver training discount applies.
Staging	CA_DRV	DRV_TRNG_DSCNT_PCT	Driver Training Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when driver training discount applies.
Staging	CA_DRV	DRV_TRNG_FLG	Driver Training Flag	CHAR(1)	This value represents based on the yes/no indicator that identifies whether or not a driver has completed a driver training course.
Staging	CA_DRV	DRV_TYP_CD	Driver Type Code	VARCHAR2(25)	This system code describes the driver activities.
Staging	CA_DRV	INSD_DT	Insured Date	DATE	This calendar date represents when insurance coverage began for commercial auto driver.
Staging	CA_DRV	LIC_DT	License Date	DATE	This calendar date represents when commercial auto driver was granted a drivers license.
Staging	CA_DRV	RLAT_TO_APPLICANT_CD	Relationship to Applicant Code	VARCHAR2(25)	This system code identifies the relationship of this individual to the applicant.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CA_DRV	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the commercial auto driver with a specific transaction.
Staging	CA_VEH	ADDL_EQPT_AMT	Additional Equipment Amount	NUMBER (14,3)	This number represents the monetary cost of vehicle alterations or aftermarket custom equipment like custom painting, equipment installed to overcome a physical handicap, etc. installed on a commercial vehicle.
Staging	CA_VEH	AIRBAG_TYP_CD	Airbag Type Code	VARCHAR2(25)	This system code identifies the attributes of airbag system installed.
Staging	CA_VEH	ANTI_LOCK_BRAKES_CD	Anti-lock Brake Code	VARCHAR2(25)	This system code identifies the attributes of anti-lock brakes on the commercial vehicle.
Staging	CA_VEH	ANTI_THEFT_DEVICE_CD	Anti-Theft Device Code	VARCHAR2(25)	This system code identifies the attributes of vehicle anti-theft device installed on the commercial vehicle.
Staging	CA_VEH	AUTO_STBLTS_DSCNT_FLG	Automatic Seatbelt Type Code	CHAR(1)	This system code identifies the attributes of automatic seatbelt installed.
Staging	CA_VEH	AUTO_STBLTS_DSCNT_PCT	Automatic Seatbelt Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when automatic seatbelt discount applies.
Staging	CA_VEH	CA_VEH_NAT_KEY	Commercial Auto Vehicle Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the commercial vehicle.
Staging	CA_VEH	CA_VEH_UDF_CD_1	Commercial Auto Vehicle User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first commercial vehicle user defined field.
Staging	CA_VEH	CA_VEH_UDF_CD_2	Commercial Auto Vehicle User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second commercial vehicle user defined field.
Staging	CA_VEH	CA_VEH_UDF_CD_3	Commercial Auto Vehicle User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third commercial vehicle user defined field.
Staging	CA_VEH	CA_VEH_UDF_CD_4	Commercial Auto Vehicle User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth commercial vehicle user defined field.
Staging	CA_VEH	CA_VEH_UDF_CD_5	Commercial Auto Vehicle User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth commercial vehicle user defined field.
Staging	CA_VEH	CELL_PHONE_TYP_CD	Cellular Phone Type Code	VARCHAR2(25)	This system code identifies the cellular phone type present.
Staging	CA_VEH	DAYTIME_RUN_LIGHTS_CD	Daytime Running Lights Code	VARCHAR2(25)	This value represents based on the yes/no indicator that states whether or not a commercial vehicle has daytime running headlights.
Staging	CA_VEH	EST_ANNU_DRVG_DIST	Estimated Annual Driving Distance	NUMBER (22,0)	This number represents the estimated number of distance units (miles/kilometers) a vehicle is driven over a one year period.
Staging	CA_VEH	GAR_CD	Garaging Code	VARCHAR2(25)	This system code identifies where the commercial vehicle is parked at night.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CA_VEH	HP_DSPLCMNT	Horsepower Displacement	VARCHAR2(5)	This value represents represents the cubic centimeters or displacement (for example, motorcycles) or horsepower for recreational vehicles.
Staging	CA_VEH	INSD_DT	Insured Date	DATE	This calendar date represents when insurance coverage began for commercial vehicle.
Staging	CA_VEH	LEASE_DT	Commercial Auto Vehicle Lease Date	DATE	This calendar date represents when a commercial vehicle was leased by insured.
Staging	CA_VEH	MSRP	Manufacturer Suggested Retail Price	NUMBER (14,3)	This number represents the price that the manufacturer tells the vehicle dealer the new vehicle is worth.
Staging	CA_VEH	MULT_CAR_DSCNT_FLG	Multiple Car Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a multiple car discount applies.
Staging	CA_VEH	MULT_CAR_DSCNT_PCT	Multiple Car Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when a multiple car discount applies.
Staging	CA_VEH	NEW_OR_USED_CD	New Or Used Code	VARCHAR2(25)	This system code identifies if the insured is the original owner of the insured vehicle.
Staging	CA_VEH	OWNRSHP_TYP_CD	Ownership Type Code	VARCHAR2(25)	This system code describes the ownership type of a vehicle standard code.
Staging	CA_VEH	PURCH_DT	Purchase Date	DATE	This date represents the calendar date the insured purchased the commercial vehicle.
Staging	CA_VEH	PURCH_PRICE	Purchase Price	NUMBER (14,3)	This number represents the monetary amount paid when the commercial vehicle was purchased.
Staging	CA_VEH	RATING_AGE_CD	Rating Age Code	VARCHAR2(25)	This system code represents the rating age used to rate the vehicle, regardless of its actual age.
Staging	CA_VEH	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the commercial vehicle with a specific transaction.
Staging	CA_VEH	STATED_AMT	Stated Amount	NUMBER (14,3)	This number represents the monetary cost used to rate and value a vehicle when a symbol is not available or useful.
Staging	CA_VEH	VEH_BODY_TYP_CD	Vehicle Body Type Code	VARCHAR2(25)	This system code describes the attributes of vehicle body for a scheduled commercial vehicle.
Staging	CA_VEH	VEH_CLASS_CD	Vehicle Class Code	VARCHAR2(25)	This value represents the classification that describes vehicle size and body type.
Staging	CA_VEH	VEH_COST_NEW	Vehicle Cost New	NUMBER (14,3)	This number represents the monetary price of vehicle when purchased as a new vehicle.
Staging	CA_VEH	VEH_CUR_VAL	Vehicle Current Value	NUMBER (14,3)	This number represents the current monetary value of listed commercial vehicle in marketplace.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CA_VEH	VEH_GROSS_WT	Vehicle Gross Weight	NUMBER (14,3)	This number represents the total weight a vehicle is designed to carry and includes the net weight of the vehicle, plus the weight of passengers, fuel, cargo and any additional accessories.
Staging	CA_VEH	VEH_MFR	Vehicle Manufacturer	VARCHAR2(20)	This value represents the name of manufacturer that created the commercial vehicle.
Staging	CA_VEH	VEH_MODEL	Vehicle Model	VARCHAR2(20)	This value represents the model name assigned by manufacturer of commercial vehicle.
Staging	CA_VEH	VEH_NUM	Vehicle Number	NUMBER (22,0)	This number is the system assigned number that identifies the commercial vehicle.
Staging	CA_VEH	VEH_PERF_CD	Vehicle Performance Code	VARCHAR2(25)	This system code identifies the performance level of the vehicle.
Staging	CA_VEH	VEH_SYM_CD	Vehicle Symbol Code	VARCHAR2(25)	This system code is a cost symbol that represents a value.
Staging	CA_VEH	VEH_USE_CD	Vehicle Use Code	VARCHAR2(25)	This system code identifies the primary use of the vehicle.
Staging	CA_VEH	VEH_YR	Vehicle Year	CHAR(4)	This value represents the model year assigned by vehicle manufacturer.
Staging	CA_VEH	VIN	Vehicle Identification Number	VARCHAR2(25)	This value represents the vehicle identification number assigned by the manufacturer of the commercial vehicle at risk.
Staging	CAT	CAT_BEGIN_DT	Catastrophe Begin Date	DATE	This calendar date represents when the catastrophe started.
Staging	CAT	CAT_CD	Catastrophe Code	VARCHAR2(25)	This system code identifies a catastrophe. This is the number or other identifier assigned by the company.
Staging	CAT	CAT_END_DT	Catastrophe Ending Date	DATE	This calendar date represents when a catastrophe ended.
Staging	CAT	CAT_NAT_CD	Catastrophe National Code	VARCHAR2(25)	This system code identifies the national catastrophe occurrence.
Staging	CAT	CAT_NAT_KEY	Catastrophe Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the catastrophe.
Staging	CAT	CAT_SRC_CD	Catastrophe Source Code	VARCHAR2(25)	This system code describes the source of a catastrophe.
Staging	CAT	CAT_STATE_CD	Catastrophe State Code	VARCHAR2(25)	This system code identifies the state where a catastophe occurred.
Staging	CAT	CAT_UDF_CD_1	Catastrophe User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first catastrophe user defined field.
Staging	CAT	CAT_UDF_CD_2	Catastrophe User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second catastrophe user defined field.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CAT	CAT_UDF_CD_3	Catastrophe User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third catastrophe user defined field.
Staging	CAT	CAT_UDF_CD_4	Catastrophe User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth catastrophe user defined field.
Staging	CAT	CAT_UDF_CD_5	Catastrophe User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth catastrophe user defined field.
Staging	CAT	EXCESS_CAT_CD	Excess Catastrophe Code	VARCHAR2(25)	This system code indicates that a catastrophe loss is in excess of a policyholders' retention.
Staging	CAT	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the catastrophe with a specific transaction.
Staging	CLASS	CLASS_CD	Class Code	VARCHAR2(25)	This system code classifies the subject of insurance.
Staging	CLASS	CLASS_NAT_KEY	Class Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the class.
Staging	CLASS	CLASS_STATE_CD	Class State Code	VARCHAR2(25)	This system code abbreviates the class state.
Staging	CLASS	CLASS_UDF_CD_1	Class User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first class user defined field.
Staging	CLASS	CLASS_UDF_CD_2	Class User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second class user defined field.
Staging	CLASS	CLASS_UDF_CD_3	Class User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third class user defined field.
Staging	CLASS	CLASS_UDF_CD_4	Class User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth class user defined field.
Staging	CLASS	CLASS_UDF_CD_5	Class User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth class user defined field.
Staging	CLASS	PRIM_CLASS_CD	Primary Class Code	VARCHAR2(25)	In a situation where the class code is split into more than one useful breakout, this value represents the primary portion.
Staging	CLASS	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the class with a specific transaction.
Staging	CLASS	SCND_CLASS_CD	Second Class Code	VARCHAR2(25)	In a situation where the class code is split into more than one useful breakout, this value represents is the secondary portion.
Staging	CLM	CASE_MADE_RETROACTIVE_DT	Case Made Retroactive Date	DATE	This calendar date represenets when the claim case was made retroactive.
Staging	CLM	CASE_MGMT_ASSIGNED_DT	Case Management Assigned Date	DATE	This calendar date represents when claim management is assigned to claim.
Staging	CLM	CLM_CLOSED_DT	Claim Closed Date	DATE	This calendar date represents when the insurance company closed the claim.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CLM	CLM_NAT_KEY	Claim Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claim.
Staging	CLM	CLM_NUM	Claim Number	VARCHAR2(30)	This number or other unique identifier identifies a claim.
Staging	CLM	CLM_OPENED_DT	Claim Opened Date	DATE	This calendar date represents when a claim was opened by the insurance company.
Staging	CLM	CLM_RECLOSED_DT	Claim Re-Closed Date	DATE	This calendar date represents when a claim was re-closed by the insurance company.
Staging	CLM	CLM_REOPENED_DT	Claim Re-Opened Date	DATE	This calendar date represents when a closed claim was changed to open status by the insurance company.
Staging	CLM	CLM_RPT_BY_CD	Claim Report By Code	VARCHAR2(25)	This system code indicates the claim reported by source.
Staging	CLM	CLM_RPT_CLASS_CD	Claim Report Class Code	VARCHAR2(25)	This system code describes the class code report class applicable to the claim, regardless of the class codes on the policy.
Staging	CLM	CLM_RPT_DT	Claim Report Date	DATE	This calendar date represents when the claim was reported to the insurance carrier.
Staging	CLM	CLM_STATUS_CD	Claim Status Code	VARCHAR2(25)	This system code describes the claim status.
Staging	CLM	CLM_UDF_CD_1	Claim User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim user defined field.
Staging	CLM	CLM_UDF_CD_2	Claim User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim user defined field.
Staging	CLM	CLM_UDF_CD_3	Claim User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim user defined field.
Staging	CLM	CLM_UDF_CD_4	Claim User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim user defined field.
Staging	CLM	CLM_UDF_CD_5	Claim User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim user defined field.
Staging	CLM	CLMS_MADE_BASIS_CD	Claims Made Basis Code	VARCHAR2(25)	This system code identifies whether or not the claims made basis is being used for reporting of claims.
Staging	CLM	FIRST_CLM_CNTCT_DT	First Claim Contact Date	DATE	This calendar date represents when the claimant was first contacted by the insuring company or its representative.
Staging	CLM	FIRST_CLM_PMT_DT	First Claim Payment Date	DATE	This calendar date represents when the first payment was made on a claim.
Staging	CLM	FRAUD_CLM_CD	Fraud Claim Code	VARCHAR2(25)	This system code indicates potential fraudulent claim based on adjusters' investigation.
Staging	CLM	LAST_CLM_PMT_DT	Last Claim Payment Date	DATE	This calendar date represents when the last claim payment was issued.
Staging	CLM	LAST_SALV_PMT_DT	Last Salvage Payment Date	DATE	This calendar date represents when last salvage payment was received.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CLM	LAST_SUBRO_PMT_DT	Last Subrogation Payment Date	DATE	This calendar date represents when last subrogation payment was received.
Staging	CLM	LOSS_DT	Loss Date	DATE	This calendar date represents when an accident or loss occurred regardless of when the claim was filed.
Staging	CLM	NUM_RENTAL_DAYS	Number Of Rental Days	NUMBER (22,0)	This number represents the count of days a replacement item is rented.
Staging	CLM	NUM_REPAIR_DAYS	Number Of Repair Days	NUMBER (22,0)	This number represents the count of days required to repair an item.
Staging	CLM	NUM_STORAGE_DAYS	Number Of Storage Days	NUMBER (22,0)	This number represents the count of days an item is stored.
Staging	CLM	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the claim with a specific transaction.
Staging	CLM_ADJ	CLM_ADJ_NUM	Claim Adjuster Number	VARCHAR2(25)	This value represents a number or other identifier for an adjuster.
Staging	CLM_ADJ	CLM_ADJ_TYP_CD	Claim Adjuster Type Code	VARCHAR2(25)	This system code identifies the type of adjuster used to support the claim process.
Staging	CLM_ADJ	CLM_ADJ_UDF_CD_1	Claim Adjuster User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim adjuster user defined field.
Staging	CLM_ADJ	CLM_ADJ_UDF_CD_2	Claim Adjuster User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim adjuster user defined field.
Staging	CLM_ADJ	CLM_ADJ_UDF_CD_3	Claim Adjuster User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim adjuster user defined field.
Staging	CLM_ADJ	CLM_ADJ_UDF_CD_4	Claim Adjuster User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim adjuster user defined field.
Staging	CLM_ADJ	CLM_ADJ_UDF_CD_5	Claim Adjuster User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim adjuster user defined field.
Staging	CLM_ADJ	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the claim adjuster with a specific transaction.
Staging	CLM_EXAMR	CLM_EXAMR_NUM	Claim Examiner Number	VARCHAR2(25)	This value represents the number or identifier assigned to the claim examiner.
Staging	CLM_EXAMR	CLM_EXAMR_TYP_CD	Claim Examiner Type Code	VARCHAR2(25)	This system code describes the activities of the claim examiner.
Staging	CLM_EXAMR	CLM_EXAMR_UDF_CD_1	Claim Examiner User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim examiner user defined field.
Staging	CLM_EXAMR	CLM_EXAMR_UDF_CD_2	Claim Examiner User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim examiner user defined field.
Staging	CLM_EXAMR	CLM_EXAMR_UDF_CD_3	Claim Examiner User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim examiner user defined field.
Staging	CLM_EXAMR	CLM_EXAMR_UDF_CD_4	Claim Examiner User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim examiner user defined field.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CLM_EXAMR	CLM_EXAMR_UDF_CD_5	Claim Examiner User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim examiner user defined field.
Staging	CLM_EXAMR	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the claim examiner with a specific transaction.
Staging	CLM_MGR	CLM_MGR_NUM	Claim Manager Number	VARCHAR2(25)	This number or other identifiers identifies claim manager.
Staging	CLM_MGR	CLM_MGR_TYP_CD	Claim Manager Type Code	VARCHAR2(25)	This system code indicates the claim manager type.
Staging	CLM_MGR	CLM_MGR_UDF_CD_1	Claim Manager User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim manager user defined field.
Staging	CLM_MGR	CLM_MGR_UDF_CD_2	Claim Manager User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim manager user defined field.
Staging	CLM_MGR	CLM_MGR_UDF_CD_3	Claim Manager User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim manager user defined field.
Staging	CLM_MGR	CLM_MGR_UDF_CD_4	Claim Manager User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim manager user defined field.
Staging	CLM_MGR	CLM_MGR_UDF_CD_5	Claim Manager User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim manager user defined field.
Staging	CLM_MGR	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the claim manager with a specific transaction.
Staging	CLM_TRANS	ALLOC_EXPNS_TYP_CD	Allocation Expense Type Code	VARCHAR2(25)	This system code identifies the expense allocation type in the claim transaction.
Staging	CLM_TRANS	AVG_EXPNS_RSRV_CD	Average Expense Reserve Code	VARCHAR2(25)	This system code identifies the average reserve set in the claim transaction expenses.
Staging	CLM_TRANS	AVG_RSRV_CD	Average Reserve Code	VARCHAR2(25)	This system code identifies the average reserve set in the claim transaction.
Staging	CLM_TRANS	BILL_HRLY_RATE	Billable Hourly Rate	NUMBER (6,5)	This number represents the charge applicable or each hour for a service associated with a claims transaction.
Staging	CLM_TRANS	BOOK_DT	Book Date	DATE	This calendar date represents when the claim transaction is recorded into the company's books. Usually, this is the greater of the transaction date or the effective date.
Staging	CLM_TRANS	CLM_TRANS_AMT	Claim Transaction Amount	NUMBER (14,3)	This number represents the actual amount of a claim transaction.
Staging	CLM_TRANS	CLM_TRANS_CATG_CD	Claim Transaction Category Code	VARCHAR2(25)	This value represents a way to combine claim transactions into similar categories.
Staging	CLM_TRANS	CLM_TRANS_CD	Claim Transaction Code	VARCHAR2(25)	This system code represents what type of loss activity occurred in the claim transaction.
Staging	CLM_TRANS	DIRECT_CEDED_ASSUMED_CD	Direct or Ceded or Assumed Code	VARCHAR2(25)	This system code identifies the claim transaction type as being direct, ceded, or assumed.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CLM_TRANS	DOC_CURR_CD	Document Currency Code	VARCHAR2(25)	This system code identifies document currency for claim transaction.
Staging	CLM_TRANS	NUM_HRS_BILLED	Number Of Hours Billed	NUMBER (22,0)	This number represents the count of hours billed to a claims transaction.
Staging	CLM_TRANS	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the claim transaction with a specific transaction.
Staging	CLM_TRANS	SRC_SYS_PROC_DT	Source System Process Date	DATE	This calendar date represents when source system processed the claim transaction.
Staging	CLM_TRANS	TRANS_EFF_DT	Transaction Effective Date	DATE	This calendar date represents when a claims transaction is effective.
Staging	CLMT	CLMT_TYP_CD	Claimant Type Code	VARCHAR2(25)	This system code refers to the type of entity making the claim.
Staging	CLMT	CLMT_UDF_CD_1	Claimant User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claimant user defined field.
Staging	CLMT	CLMT_UDF_CD_2	Claimant User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claimant user defined field.
Staging	CLMT	CLMT_UDF_CD_3	Claimant User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claimant user defined field.
Staging	CLMT	CLMT_UDF_CD_4	Claimant User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claimant user defined field.
Staging	CLMT	CLMT_UDF_CD_5	Claimant User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claimant user defined field.
Staging	CLMT	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the claimant with a specific transaction.
Staging	CNTCT	CNTCT_CD	Contact Code	VARCHAR2(25)	This system code indicates the attributes of contact.
Staging	CNTCT	CNTCT_NAT_KEY	Contact Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the contact.
Staging	CNTCT	CNTCT_RLAT_CD	Contact Relationship Code	VARCHAR2(25)	This system code indicates the contact relationship.
Staging	CNTCT	CNTCT_TYP_CD	Contact Type Code	VARCHAR2(25)	This system code identifies the contact type.
Staging	CNTCT	CNTCT_UDF_CD_1	Contact User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first contact user defined field.
Staging	CNTCT	CNTCT_UDF_CD_2	Contact User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second contact user defined field.
Staging	CNTCT	CNTCT_UDF_CD_3	Contact User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third contact user defined field.
Staging	CNTCT	CNTCT_UDF_CD_4	Contact User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth contact user defined field.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CNTCT	CNTCT_UDF_CD_5	Contact User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth contact user defined field.
Staging	CNTCT	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the contact with a specific transaction.
Staging	COVRG	ANNU_STMT_LINE_CD	Annual Statement Line Code	VARCHAR2(25)	This system code indicates in which line of the annual statement a transaction belongs.
Staging	COVRG	BUREAU_RPT_PLAN_CD	Bureau Report Plan Code	VARCHAR2(25)	This system code indicates the statistical plan code used for bureau reporting.
Staging	COVRG	COVRG_CATG_CD	Coverage Category Code	VARCHAR2(25)	This value represents a way to group coverages within a line of business.
Staging	COVRG	COVRG_CD	Coverage Code	VARCHAR2(25)	This system code identifies and/or further defines a type of coverage, discount, surcharge or factor being requested or applied It may also identify the type of insured value or coverage requested as part of a commercial property schedule submission.
Staging	COVRG	COVRG_NAT_KEY	Coverage Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the coverage.
Staging	COVRG	COVRG_PART_CD	Coverage Part Code	VARCHAR2(25)	This system code represents a line of business within a package policy.
Staging	COVRG	COVRG_UDF_CD_1	Coverage User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first coverage user defined field.
Staging	COVRG	COVRG_UDF_CD_2	Coverage User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second coverage user defined field.
Staging	COVRG	COVRG_UDF_CD_3	Coverage User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third coverage user defined field.
Staging	COVRG	COVRG_UDF_CD_4	Coverage User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth coverage user defined field.
Staging	COVRG	COVRG_UDF_CD_5	Coverage User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth coverage user defined field.
Staging	COVRG	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the coverage with a specific transaction.
Staging	COVRG	SCND_COVRG_CD	Second Coverage Code	VARCHAR2(25)	This value represents the client defined code that will further breakdown the type of coverage afforded on the insurance line policy.
Staging	COVRG	STAT_PLAN_CD	Statistical Plan Code	VARCHAR2(25)	This system code identifies the statistical plan for coverage.
Staging	COVRG_STATUS	COVRG_EFF_DT	Coverage Effective Date	DATE	This calender date represents when the policy coverage begins.
Staging	COVRG_STATUS	COVRG_EXPR_DT	Coverage Expiration Date	DATE	This calender date represents when the policy coverage ends.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	COVRG_STATUS	COVRG_STATUS_UDF_CD_1	Coverage Status User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first coverage status user defined field.
Staging	COVRG_STATUS	COVRG_STATUS_UDF_CD_2	Coverage Status User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second coverage status user defined field.
Staging	COVRG_STATUS	COVRG_STATUS_UDF_CD_3	Coverage Status User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third coverage status user defined field.
Staging	COVRG_STATUS	COVRG_STATUS_UDF_CD_4	Coverage Status User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth coverage status user defined field.
Staging	COVRG_STATUS	COVRG_STATUS_UDF_CD_5	Coverage Status User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth coverage status user defined field.
Staging	COVRG_STATUS	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the coverage status with a specific transaction.
Staging	CP_BLDG	ALUMINUM_WIRG_FLG	Aluminum Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of aluminum wiring.
Staging	CP_BLDG	BLDG_OCPCY	Building Occupancy	NUMBER (22,0)	This number represents the type of occupants of the commercial building. For example, owner and tenant occupants.
Staging	CP_BLDG	BURGLAR_MONITOR_TYP_CD	Burglar Monitoring Type Code	VARCHAR2(25)	This system code describes presence or absence and attributes of burglar alarm in use at the building.
Staging	CP_BLDG	CIRCUIT_BREAKERS_FLG	Circuit Breakers Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of circuit breakers.
Staging	CP_BLDG	CONST_TYP_CD	Construction Type Code	VARCHAR2(25)	This system code describes the type of construction materials primarily used for building exterior.
Staging	CP_BLDG	COPPER_WIRG_FLG	Copper Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of copper wiring.
Staging	CP_BLDG	CP_BLDG_NAT_KEY	Commercial Property Building Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the building.
Staging	CP_BLDG	CP_BLDG_UDF_CD_1	Commercial Property Building User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first commercial property building user defined field.
Staging	CP_BLDG	CP_BLDG_UDF_CD_2	Commercial Property Building User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second commercial property building user defined field.
Staging	CP_BLDG	CP_BLDG_UDF_CD_3	Commercial Property Building User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third commercial property building user defined field.
Staging	CP_BLDG	CP_BLDG_UDF_CD_4	Commercial Property Building User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth commercial property building user defined field.
Staging	CP_BLDG	CP_BLDG_UDF_CD_5	Commercial Property Building User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth commercial property building user defined field.
Staging	CP_BLDG	CTY_LMTS_CD	City Limits Code	VARCHAR2(25)	This system code describes if a building is located within or outside city limit boundary.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CP_BLDG	CUR_YR_PROP_INCOME	Current Year Property Income	NUMBER (14,3)	This number represents the total amount of income from activities at the insured building during the current year.
Staging	CP_BLDG	DIST_TO_FIRE_HYDRANT	Distance to Fire Hydrant	NUMBER (14,3)	This number represents the number of distance units (feet/ meters) from building to nearest fire hydrant location.
Staging	CP_BLDG	DIST_TO_FIRE_STATION	Distance to Fire Station	NUMBER (14,3)	This number represents the number of distance units (miles/km) from building to nearest fire station location.
Staging	CP_BLDG	BLDG_AREA	Building Area	NUMBER (14,3)	This number represents the area measurement of floor contained.
Staging	CP_BLDG	BLDG_COND_CD	Building Condition Code	VARCHAR2(25)	This system code indicates the building condition.
Staging	CP_BLDG	BLDG_TYP_CD	Building Type Code	VARCHAR2(25)	This system code indicates the building type.
Staging	CP_BLDG	ELEC_UPDT_TYP_CD	Electrical Update Type Code	VARCHAR2(25)	This system code indicates changes to electrical system after the building's original construction.
Staging	CP_BLDG	ELEC_UPDT_YR	Electrical Update Year	CHAR(4)	This value represents the calendar year of the last update to the building electrical system.
Staging	CP_BLDG	FIRE_DSTRCT_CD	Fire District Code	VARCHAR2(25)	This system code describes the fire department response district assigned to a building location.
Staging	CP_BLDG	FIRE_EXTINGUISHER_FLG	Fire Extinguisher Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fire extinguisher.
Staging	CP_BLDG	FIRE_MONITOR_TYP_CD	Fire Monitoring Type Code	VARCHAR2(25)	This system code indicates the type of fire monitoring alarm used at building.
Staging	CP_BLDG	FIRE_PROT_CLASS_CD	Fire Protection Class Code	VARCHAR2(25)	This system code describes the fire protection services available at building location.
Staging	CP_BLDG	FNDN_TYP_CD	Foundation Type Code	VARCHAR2(25)	This system code indicates the construction method used to construct building foundation.
Staging	CP_BLDG	FUSES_FLG	Fuses Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fuses.
Staging	CP_BLDG	GAS_UPDT_TYP_CD	Gas Update Type Code	VARCHAR2(25)	This system code indicates changes to gas system after the building's original construction.
Staging	CP_BLDG	GAS_UPDT_YR	Gas Update Year	CHAR(4)	This value represents the calendar year of the last update to the building gas system.
Staging	CP_BLDG	HEAT_UPDT_TYP_CD	Heating Update Type Code	VARCHAR2(25)	This system code indicates changes to heating system after the building's original construction.
Staging	CP_BLDG	HEAT_UPDT_YR	Heating Update Year	CHAR(4)	This value represents the calendar year of the last update to the building heating system.
Staging	CP_BLDG	KNOB_TUBE_WIRG_FLG	Knob And Tube Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of knob and tube wiring.
Staging	CP_BLDG	LOC_NUM	Location Number	NUMBER (22,0)	This number identifies the location of a building.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CP_BLDG	MKT_VAL	Market Value	NUMBER (14,3)	This number represents the average price of similar buildings recently sold in same real estate market.
Staging	CP_BLDG	NM_OF_OWNER	Name of Owner	VARCHAR2(170)	This value represents the name of the building's owner.
Staging	CP_BLDG	NUM_COML_OCCUPANTS	Number Of Commercial Occupants	NUMBER (22,0)	This number represents the count of all commercial occupants in all units of a building.
Staging	CP_BLDG	NUM_ELEC_SYS_AMPS	Number Of Electrical System Amps	NUMBER (22,0)	This number represents the electrical current capacity of a building's electrical system.
Staging	CP_BLDG	NUM_FMLYS	Number Of Families	NUMBER (22,0)	This number represents the count of individual family units in single commercial building. For example, a duplex would have 2 families.
Staging	CP_BLDG	NUM_STORIES	Number Of Stories	NUMBER (22,0)	This number represents the count of building floor levels.
Staging	CP_BLDG	OCPCY_TYP_CD	Occupancy Type Code	VARCHAR2(25)	This system code indicates the type of occupants of the building.
Staging	CP_BLDG	PLUMBING_UPDT_TYP_CD	Plumbing Update Type Code	VARCHAR2(25)	This system code indicates changes to plumbing system after the building's original construction.
Staging	CP_BLDG	PLUMBING_UPDT_YR	Plumbing Update Year	CHAR(4)	This value represents the calendar year of the last update to the building's plumbing system.
Staging	CP_BLDG	PRIM_HEAT_TYP_CD	Primary Heating Type Code	VARCHAR2(25)	This system code describes the building's primary source of heat.
Staging	CP_BLDG	PROP_LOT_SIZE	Property Lot Size	NUMBER (14,3)	This number represents the area measurement of the land with.
Staging	CP_BLDG	PURCH_DT	Purchase Date	DATE	This calendar date represents when the insured purchased the building.
Staging	CP_BLDG	PURCH_PRICE	Purchase Price	NUMBER (14,3)	This number represents the monetary amount paid when building was purchased.
Staging	CP_BLDG	ROOF_MATL_CD	Roofing Material Code	VARCHAR2(25)	This system code identifies the material used to construct the building's roof.
Staging	CP_BLDG	ROOF_UPDT_TYP_CD	Roofing Update Type Code	VARCHAR2(25)	This system code indicates the type or roofing updates made since the building's original construction.
Staging	CP_BLDG	ROOF_UPDT_YR	Roofing Update Year	CHAR(4)	This value represents the calendar year of the last update to the building's roofing materials.
Staging	CP_BLDG	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the commercial property building (also known as commercial property building) with a specific transaction.
Staging	CP_BLDG	SCND_HEAT_TYP_CD	Secondary Heating Type Code	VARCHAR2(25)	This system code describes the building's secondary source of heat.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	CP_BLDG	UNDER_CONST_TYP_CD	Under Construction Type Code	VARCHAR2(25)	This system code indicates active construction activities on the building.
Staging	CP_BLDG	WIRG_UPDT_TYP_CD	Wiring Update Type Code	VARCHAR2(25)	This system code identifies the type of update to wiring system.
Staging	CP_BLDG	WIRG_UPDT_YR	Wiring Update Year	CHAR(4)	This value represents the calendar year of the last update to the building wiring system.
Staging	CP_BLDG	YR_BUILT	Year Built	CHAR(4)	This value represents the calendar year that the building was constructed.
Staging	CURR_CNV	CURR_CNV_DT	Currency Conversion Date	DATE	This calendar date represents when currency was converted to another currency.
Staging	CURR_CNV	CURR_CNV_FROM_CD	Currency Converted From Code	VARCHAR2(25)	This system code identifies the original currency type that was converted.
Staging	CURR_CNV	CURR_CNV_RATE	Currency Conversion Rate	NUMBER (22,7)	This number represents the rate at which a currency is converted to another currency.
Staging	CURR_CNV	CURR_CNV_TO_CD	Currency Converted To Code	VARCHAR2(25)	This system code identifies currency converted to.
Staging	DC	DC_NAT_KEY	Distribution Channel Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the distribution channel.
Staging	DC	DC_NM	Distribution Channel Name	VARCHAR2(60)	This value represents distribution channel's name.
Staging	DC	DC_NUM	Distribution Channel Number	VARCHAR2(10)	This value represents the number or other identifier assigned to the distribution channel.
Staging	DC	DC_TYP_CD	Distribution Channel Type Code	VARCHAR2(25)	This system code identifies distribution channel type.
Staging	DC	DC_UDF_CD_1	Distribution Channel User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first distribution channel user defined field.
Staging	DC	DC_UDF_CD_2	Distribution Channel User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second distribution channel user defined field.
Staging	DC	DC_UDF_CD_3	Distribution Channel User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third distribution channel user defined field.
Staging	DC	DC_UDF_CD_4	Distribution Channel User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth distribution channel user defined field.
Staging	DC	DC_UDF_CD_5	Distribution Channel User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth distribution channel user defined field.
Staging	DC	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the distribution channel with a specific transaction.
Staging	DC	TYPICAL_COMM_RATE	Typical Commission Rate	NUMBER (6,5)	This number represents the typical commission rate for distribution channel.
Staging	DED	DED	Deductible	VARCHAR2(10)	This value represents the monetary amount of a claim detailed in policy contract as not covered by the insurer for a covered risk loss.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	DED	DED_APPLIES_TO_CD	Deductible Applies To Code	VARCHAR2(25)	This system code identifies to what coverage the deductible applies.
Staging	DED	DED_BASIS_CD	Deductible Basis Code	VARCHAR2(25)	This system code represents the basis applied to determine the deductible.
Staging	DED	DED_NAT_KEY	Deductible Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the deductible.
Staging	DED	DED_TYP_CD	Deductible Type Code	VARCHAR2(25)	This system code identifies the type of deductible.
Staging	DED	DED_UDF_CD_1	Deductible User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first deductible user defined field.
Staging	DED	DED_UDF_CD_2	Deductible User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second deductible user defined field.
Staging	DED	DED_UDF_CD_3	Deductible User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third deductible user defined field.
Staging	DED	DED_UDF_CD_4	Deductible User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth deductible user defined field.
Staging	DED	DED_UDF_CD_5	Deductible User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth deductible user defined field.
Staging	DED	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the deductible with a specific transaction.
Staging	DF_DWLNG	CIRCUIT_BREAKERS_FLG	Circuit Breakers Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of circuit breakers.
Staging	DF_DWLNG	CONST_TYP_CD	Construction Type Code	VARCHAR2(25)	This system code describes the type of construction materials primarily used for dwelling exterior.
Staging	DF_DWLNG	CTY_LMTS_CD	City Limits Code	VARCHAR2(25)	This system code describes if a dwelling is located within or outside city limit boundary.
Staging	DF_DWLNG	DF_DWLNG_NAT_KEY	Dwelling Fire Dwelling Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the dwelling.
Staging	DF_DWLNG	DF_DWLNG_UDF_CD_1	Dwelling Fire Dwelling User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first dwelling fire dwelling user defined field.
Staging	DF_DWLNG	DF_DWLNG_UDF_CD_2	Dwelling Fire Dwelling User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second dwelling fire dwelling user defined field.
Staging	DF_DWLNG	DF_DWLNG_UDF_CD_3	Dwelling Fire Dwelling User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third dwelling fire dwelling user defined field.
Staging	DF_DWLNG	DF_DWLNG_UDF_CD_4	Dwelling Fire Dwelling User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth dwelling fire dwelling user defined field.
Staging	DF_DWLNG	DF_DWLNG_UDF_CD_5	Dwelling Fire Dwelling User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth dwelling fire dwelling user defined field.
Staging	DF_DWLNG	DIST_TO_FIRE_HYDRANT	Distance to Fire Hydrant	NUMBER (14,3)	This number represents the distance units (feet/meters) from dwelling to nearest fire hydrant location.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	DF_DWLNG	DIST_TO_FIRE_STATION	Distance to Fire Station	NUMBER (14,3)	This number represents the distance units (miles/kilometers) from dwelling to nearest fire station location.
Staging	DF_DWLNG	DWLNG_AREA	Dwelling Area	NUMBER (14,3)	This number represents the area measurement of floor contained.
Staging	DF_DWLNG	DWLNG_COND_CD	Dwelling Condition Code	VARCHAR2(25)	This system code indicates the dwelling condition.
Staging	DF_DWLNG	DWLNG_TYP_CD	Dwelling Type Code	VARCHAR2(25)	This system code indicates the dwelling type.
Staging	DF_DWLNG	ELEC_UPDT_TYP_CD	Electrical Update Type Code	VARCHAR2(25)	This system code indicates changes to electrical system after the dwelling's original construction.
Staging	DF_DWLNG	ELEC_UPDT_YR	Electrical Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling electrical system.
Staging	DF_DWLNG	FIRE_DSTRCT_CD	Fire District Code	VARCHAR2(25)	This system code describes the fire department response district assigned to a dwelling location.
Staging	DF_DWLNG	FIRE_PROT_CLASS_CD	Fire Protection Class Code	VARCHAR2(25)	This system code describes the fire protection services available at dwelling location.
Staging	DF_DWLNG	FNDN_TYP_CD	Foundation Type Code	VARCHAR2(25)	This system code indicates the construction method used to construct dwelling foundation.
Staging	DF_DWLNG	FUSES_FLG	Fuses Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fuses.
Staging	DF_DWLNG	GAS_UPDT_TYP_CD	Gas Update Type Code	VARCHAR2(25)	This system code indicates changes to gas system after the dwelling's original construction.
Staging	DF_DWLNG	GAS_UPDT_YR	Gas Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling gas system.
Staging	DF_DWLNG	HEAT_UPDT_TYP_CD	Heating Update Type Code	VARCHAR2(25)	This system code indicates changes to heating system after the dwelling's original construction.
Staging	DF_DWLNG	HEAT_UPDT_YR	Heating Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling heating system.
Staging	DF_DWLNG	LOC_NUM	Location Number	NUMBER (22,0)	This number identifies the location of a dwelling.
Staging	DF_DWLNG	MINE_SUBSIDENCE_FLG	Mine Subsidence Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of mine subsidence coverage.
Staging	DF_DWLNG	MKT_VAL	Market Value	NUMBER (14,3)	This number represents the average price of similar dwellings recently sold in same real estate market.
Staging	DF_DWLNG	NUM_ELEC_SYS_AMPS	Number Of Electrical System Amps	NUMBER (22,0)	This number represents the electrical current capacity of electrical system.
Staging	DF_DWLNG	NUM_FMLYS	Number Of Families	NUMBER (22,0)	This number represents the count of individual family units in single dwelling. For example, a duplex would have 2 families.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	DF_DWLNG	NUM_OR_RMS	Number Of Rooms	NUMBER (22,0)	This number represents the count of rooms contained in all units of the dwelling.
Staging	DF_DWLNG	NUM_STORIES	Number Of Stories	NUMBER (22,0)	This number represents the count of building floor levels.
Staging	DF_DWLNG	NUM_WKS_RENTED	Number Of Weeks Rented	NUMBER (22,0)	This number represents the count of weeks dwelling is rented per calendar year.
Staging	DF_DWLNG	OCPCY_TYP_CD	Occupancy Type Code	VARCHAR2(25)	This system code indicates the type of occupants of the dwelling.
Staging	DF_DWLNG	PLUMBING_UPDT_TYP_CD	Plumbing Update Type Code	VARCHAR2(25)	This system code indicates changes to the plumbing system after the dwelling's original construction.
Staging	DF_DWLNG	PLUMBING_UPDT_YR	Plumbing Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling plumbing system.
Staging	DF_DWLNG	PP_MERCNTL_BLDG_FLG	Personal Property Mercantile Building Flag	CHAR(1)	This value represents based on the yes/no indicator identifying presence or absence of personal property storage in a mercantile building.
Staging	DF_DWLNG	PRIM_HEAT_TYP_CD	Primary Heating Type Code	VARCHAR2(25)	This system code describes the primary source of heat for dwelling.
Staging	DF_DWLNG	PURCH_DT	Purchase Date	DATE	This calendar date represents when the insured purchased the dwelling.
Staging	DF_DWLNG	PURCH_PRICE	Purchase Price	NUMBER (14,3)	This number represents the monetary amount paid when dwelling was purchased.
Staging	DF_DWLNG	REPL_COST	Replacement Cost	NUMBER (14,3)	This number represents the monetary amount it would cost to replace a dwelling at current prices with like materials.
Staging	DF_DWLNG	ROOF_MATL_CD	Roofing Material Code	VARCHAR2(25)	This system code identifies the material used to construct the roof.
Staging	DF_DWLNG	ROOF_UPDT_TYP_CD	Roofing Update Type Code	VARCHAR2(25)	This system code indicates the type or roofing updates made since the dwelling's original construction.
Staging	DF_DWLNG	ROOF_UPDT_YR	Roofing Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling roofing materials.
Staging	DF_DWLNG	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the dwelling fire dwelling with a specific transaction.
Staging	DF_DWLNG	SCND_HEAT_TYP_CD	Secondary Heating Type Code	VARCHAR2(25)	This system code describes the secondary source of heat for dwelling.
Staging	DF_DWLNG	STORM_SHUTTERS_CD	Storm Shutters Code	VARCHAR2(25)	This system code describes the existence or absence and type of storm shutters.
Staging	DF_DWLNG	UNDER_CONST_TYP_CD	Under Construction Type Code	VARCHAR2(25)	This system code indicates active construction activities on the dwelling.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	DF_DWLNG	VACANT_PCT	Vacant Percentage	NUMBER (6,3)	This number represents the percentage of total dwelling area not currently occupied.
Staging	DF_DWLNG	WIRG_UPDT_TYP_CD	Wiring Update Type Code	VARCHAR2(25)	This system code identifies the type of update to wiring system.
Staging	DF_DWLNG	WIRG_UPDT_YR	Wiring Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling wiring system.
Staging	DF_DWLNG	YR_BUILT	Year Built	CHAR(4)	This value represents the calendar year that the dwelling was constructed.
Staging	ERND_EXPO_TRANS	ERND_EXPO_AMT	Earned Exposure Amount	NUMBER (14,3)	This number represents the amount of written exposure that is recognized as earned within a given time period.
Staging	ERND_EXPO_TRANS	FISCAL_YR_MTH	Fiscal Year Month	NUMBER (22,0)	This number represents the fiscal year month.
Staging	ERND_EXPO_TRANS	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the earned exposure transaction with a specific transaction.
Staging	ERND_EXPO_TRANS	UNERND_EXPO_AMT	Unearned Exposure Amount	NUMBER (14,3)	This number represents the monetary cost of exposure that is recognized as unearned within a given time period.
Staging	ERND_PREM_TRANS	ERND_PREM_AMT	Earned Premium Amount	NUMBER (14,3)	This number represents the amount of written premium that that is recognized as earned within a given time period.
Staging	ERND_PREM_TRANS	FISCAL_YR_MTH	Fiscal Year Month	VARCHAR2(6)	This value describes the fiscal year month in the earned premium transaction.
Staging	ERND_PREM_TRANS	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the earned premium transaction with a specific transaction.
Staging	ERND_PREM_TRANS	UNERND_PREM_AMT	Unearned Premium Amount	NUMBER (14,3)	This number represents the monetary cost of written premium that is recognized as unearned within a given time period.
Staging	FEAT	ACCID_INJY_ANLYS_CD	Accident Injury Analysis Code (AIA)	VARCHAR2(25)	This system code summarizes the facts relating to a claim. The code can be used to indicate injuries such as body parts involved, type of injury or disease and cause of condition related to a claim.
Staging	FEAT	ACCID_INJY_ANLYS_SUB_CD	Accident Injury Analysis Sub Code	VARCHAR2(25)	This system code describes the loss in more detail than the accident injury analysis code and further describes such things as the object/incident involved in the loss (i.e. machinery, wet floor, etc.).
Staging	FEAT	CAUSE_OF_LOSS_CD	Cause of Loss Code	VARCHAR2(25)	This system code represents the condition that caused a loss to occur.
Staging	FEAT	DSBLY_TYP_CD	Disability Type Code	VARCHAR2(25)	This system code indicates the disability type.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	FEAT	FEAT_NAT_KEY	Feature Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claim feature.
Staging	FEAT	FEAT_UDF_CD_1	Feature User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim feature user defined field.
Staging	FEAT	FEAT_UDF_CD_2	Feature User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim feature user defined field.
Staging	FEAT	FEAT_UDF_CD_3	Feature User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim feature user defined field.
Staging	FEAT	FEAT_UDF_CD_4	Feature User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim feature user defined field.
Staging	FEAT	FEAT_UDF_CD_5	Feature User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim feature user defined field.
Staging	FEAT	INJURED_BODY_PART_CD	Injured Body Part Code	VARCHAR2(25)	This system code represents an anatomical part of the insured body.
Staging	FEAT	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the claim feature with a specific transaction.
Staging	FEAT	TYP_OF_LOSS_CD	Type of Loss Code	VARCHAR2(25)	This system code describes the type of loss.
Staging	FEAT_STATUS	FEAT_CLOSED_DT	Feature Closed Date	DATE	This calendar date represents when the claim feature, defined as a subset of a claim occurrence, was closed.
Staging	FEAT_STATUS	FEAT_OPENED_DT	Feature Opened Date	DATE	This calendar date represents when the claim feature, defined as a subset of a claim occurrence, was opened.
Staging	FEAT_STATUS	FEAT_RECLOSED_DT	Feature Re-closed Date	DATE	This calendar date represents when the claim feature, defined as a subset of a claim occurrence, was reclosed.
Staging	FEAT_STATUS	FEAT_REOPENED_DT	Feature Re-Opened Date	DATE	This calendar date represents when the claim feature, defined as a subset of a claim occurrence, was reopened.
Staging	FEAT_STATUS	FEAT_STATUS_CD	Feature Status Code	VARCHAR2(25)	This system code identifies the current condition of the claim feature, defined as a subset of a claim occurrence.
Staging	FEAT_STATUS	FEAT_STATUS_UDF_CD_1	Feature Status User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim feature status user defined field.
Staging	FEAT_STATUS	FEAT_STATUS_UDF_CD_2	Feature Status User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim feature status user defined field.
Staging	FEAT_STATUS	FEAT_STATUS_UDF_CD_3	Feature Status User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim feature status user defined field.
Staging	FEAT_STATUS	FEAT_STATUS_UDF_CD_4	Feature Status User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim feature status user defined field.
Staging	FEAT_STATUS	FEAT_STATUS_UDF_CD_5	Feature Status User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim feature status user defined field.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	FEAT_STATUS	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the claim feature status with a specific transaction.
Staging	GRP_PRG	ANNIVERSARY_DT	Anniversary Date	DATE	This calendar date represents the annual anniversary of a program or association. Often, it is the calendar date of the dividend declaration.
Staging	GRP_PRG	DIVIDEND_DT	dividend Date	DATE	This calendar date represents when the dividend applies to a program or association.
Staging	GRP_PRG	DIVIDEND_PLAN_CD	Dividend Plan Code	VARCHAR2(25)	This system code identifies the type of dividend plan offered by the company.
Staging	GRP_PRG	GRP_PRG_CD	Group Program Code	VARCHAR2(25)	This system code represents the program that a group of policies are associated with.
Staging	GRP_PRG	GRP_PRG_NAT_CD	Group Program National Code	VARCHAR2(25)	This system code identifies the national group program.
Staging	GRP_PRG	GRP_PRG_NAT_KEY	Group Program Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the group program.
Staging	GRP_PRG	GRP_PRG_STATE_CD	Group Program State Code	VARCHAR2(25)	This system code represents the state program with which a group of policies is associated.
Staging	GRP_PRG	GRP_PRG_STATUS_CD	Group Program Status Code	VARCHAR2(25)	This system code represents the current condition of a program with which a group of policies is associated.
Staging	GRP_PRG	GRP_PRG_TYP_CD	Group Program Type Code	VARCHAR2(25)	This system code describes the type of group program that is represented.
Staging	GRP_PRG	GRP_PRG_UDF_CD_1	Group Program User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first group program user defined field.
Staging	GRP_PRG	GRP_PRG_UDF_CD_2	Group Program User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second group program user defined field.
Staging	GRP_PRG	GRP_PRG_UDF_CD_3	Group Program User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third group program user defined field.
Staging	GRP_PRG	GRP_PRG_UDF_CD_4	Group Program User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth group program user defined field.
Staging	GRP_PRG	GRP_PRG_UDF_CD_5	Group Program User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth group program user defined field.
Staging	GRP_PRG	MBR_CNT	Member Count	NUMBER (22,0)	This number represents the count of members in a group or program.
Staging	GRP_PRG	ORIG_DT	Original Date	DATE	This calendar date describes the date a group program was applicable.
Staging	GRP_PRG	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the group program with a specific transaction.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	HO_DWLNG	ALUMINUM_WIRG_FLG	Aluminum Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of aluminum wiring.
Staging	HO_DWLNG	ATTACHED_GAR_FLG	Attached Garage Indicator	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a garage that is attached to the dwelling.
Staging	HO_DWLNG	BSMT_AREA	Basement Area	NUMBER (14,3)	This number represents the total area measurement of all the basements in this dwelling.
Staging	HO_DWLNG	BURGLAR_MONITOR_TYP_CD	Burglar Monitoring Type Code	VARCHAR2(25)	This system code describes presence or absence and attributes of burglar alarm in use at the dwelling.
Staging	HO_DWLNG	CARPORT_FLG	Carport Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a carport.
Staging	HO_DWLNG	CIRCUIT_BREAKERS_FLG	Circuit Breakers Flag	CHAR(1)	This value represents the yes/no indicator identifying the presence or absence of circuit breakers.
Staging	HO_DWLNG	CONST_TYP_CD	Construction Type Code	VARCHAR2(25)	This system code describes the type of construction materials primarily used for dwelling exterior.
Staging	HO_DWLNG	COPPER_WIRG_FLG	Copper Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of copper wiring.
Staging	HO_DWLNG	CTY_LMTS_CD	City Limits Code	VARCHAR2(25)	This system code describes if a dwelling is located within or outside city limit boundary.
Staging	HO_DWLNG	DIST_TO_FIRE_HYDRANT	Distance to Fire Hydrant	NUMBER (14,3)	This number represents the distance units (feet/meters) from dwelling to nearest fire hydrant location.
Staging	HO_DWLNG	DIST_TO_FIRE_STATION	Distance to Fire Station	NUMBER (14,3)	This number represents the distance units (miles/kilometers) from dwelling to nearest fire station location
Staging	HO_DWLNG	DWLNG_AREA	Dwelling Area	NUMBER (14,3)	This number represents the area measurement of floor contained in the dwelling.
Staging	HO_DWLNG	DWLNG_COND_CD	Dwelling Condition Code	VARCHAR2(25)	This system code indicates the dwelling condition.
Staging	HO_DWLNG	DWLNG_TYP_CD	Dwelling Type Code	VARCHAR2(25)	This system code indicates the dwelling type.
Staging	HO_DWLNG	ELEC_UPDT_TYP_CD	Electrical Update Type Code	VARCHAR2(25)	This system code indicates changes to electrical system after the dwelling's original construction.
Staging	HO_DWLNG	ELEC_UPDT_YR	Electrical Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling electrical system.
Staging	HO_DWLNG	ENCLOSED_GAR_FLG	Enclosed Garage Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of an enclosed garage.
Staging	HO_DWLNG	EXT_PAINT_UPDT_YR	Exterior Paint Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling exterior paint.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	HO_DWLNG	FARMING_FLG	Farming Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of farming activities occurring on insured premises.
Staging	HO_DWLNG	FIRE_DSTRCT_CD	Fire District Code	VARCHAR2(25)	This system code describes the fire department response district assigned to a dwelling location.
Staging	HO_DWLNG	FIRE_EXTINGUISHER_FLG	Fire Extinguisher Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fire extinguisher.
Staging	HO_DWLNG	FIRE_MONITOR_TYP_CD	Fire Monitoring Type Code	VARCHAR2(25)	This system code indicates the type of fire monitoring alarm used at dwelling.
Staging	HO_DWLNG	FIRE_PROT_CLASS_CD	Fire Protection Class Code	VARCHAR2(25)	This system code describes the fire protection services available at dwelling location.
Staging	HO_DWLNG	FNDN_TYP_CD	Foundation Type Code	VARCHAR2(25)	This system code indicates the construction method used to construct dwelling foundation.
Staging	HO_DWLNG	FUSES_FLG	Fuses Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fuses.
Staging	HO_DWLNG	GAS_UPDT_TYP_CD	Gas Update Type Code	VARCHAR2(25)	This system code indicates changes to gas system after the dwelling's original construction.
Staging	HO_DWLNG	GAS_UPDT_YR	Gas Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling gas system.
Staging	HO_DWLNG	HEAT_UPDT_TYP_CD	Heating Update Type Code	VARCHAR2(25)	This system code indicates changes to heating system after the dwelling's original construction.
Staging	HO_DWLNG	HEAT_UPDT_YR	Heating Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling heating system.
Staging	HO_DWLNG	HO_DWLNG_NAT_KEY	Homeowners Dwelling Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the dwelling.
Staging	HO_DWLNG	HO_DWLNG_UDF_CD_1	Homeowners Dwelling User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first homeowners dwelling user defined field.
Staging	HO_DWLNG	HO_DWLNG_UDF_CD_2	Homeowners Dwelling User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second homeowners dwelling user defined field.
Staging	HO_DWLNG	HO_DWLNG_UDF_CD_3	Homeowners Dwelling User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third homeowners dwelling user defined field.
Staging	HO_DWLNG	HO_DWLNG_UDF_CD_4	Homeowners Dwelling User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth homeowners dwelling user defined field.
Staging	HO_DWLNG	HO_DWLNG_UDF_CD_5	Homeowners Dwelling User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth homeowners dwelling user defined field.
Staging	HO_DWLNG	HURCN_RST_GLASS_FLG	Hurricane Resistant Glass Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of hurricane resistant glass.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	HO_DWLNG	KNOB_TUBE_WIRG_FLG	Knob And Tube Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of knob and tube wiring.
Staging	HO_DWLNG	LOC_NUM	Location Number	NUMBER (22,0)	This number identifies the location of a dwelling.
Staging	HO_DWLNG	MKT_VAL	Market Value	NUMBER (14,3)	This number represents the average price of similar dwellings recently sold in same real estate market.
Staging	HO_DWLNG	NUM_CHIMNEYS	Number Of Chimneys	NUMBER (22,0)	This number represents the total count of all chimneys in all units of a dwelling.
Staging	HO_DWLNG	NUM_ELEC_SYS_AMPS	Number Of Electrical System Amps	NUMBER (22,0)	This number represents the electrical current capacity of electrical system.
Staging	HO_DWLNG	NUM_FMLYS	Number Of Families	NUMBER (22,0)	This number represents the count of individual family units in single dwelling. For example, a duplex would have 2 families.
Staging	HO_DWLNG	NUM_HEARTHS	Number Of Hearths	NUMBER (22,0)	This number represents the count of individual fireplace hearths in all units of a dwelling.
Staging	HO_DWLNG	NUM_OR_RMS	Number Of Rooms	NUMBER (22,0)	This number represents the count of rooms contained in all units of the dwelling.
Staging	HO_DWLNG	NUM_PRE_FAB_FPS	Number Of Pre-Fabricated Fireplaces	NUMBER (22,0)	This number represents the count of pre-fabricated fireplaces contained in all units of the dwelling.
Staging	HO_DWLNG	NUM_RSDTS	Number Of Residents	NUMBER (22,0)	This number represents the count of residents in all units of a dwelling.
Staging	HO_DWLNG	NUM_STORIES	Number Of Stories	NUMBER (22,0)	This number represents the count of building floor levels.
Staging	HO_DWLNG	NUM_WOOD_STOVE_ISRTS	Number Of Wood Stove Inserts	NUMBER (22,0)	This number represents the count of wood stove inserts contained in all units of the dwelling.
Staging	HO_DWLNG	OCPCY_TYP_CD	Occupancy Type Code	VARCHAR2(25)	This system code indicates the type of occupants of the dwelling.
Staging	HO_DWLNG	PLUMBING_UPDT_TYP_CD	Plumbing Update Type Code	VARCHAR2(25)	This system code indicates changes to plumbing system after the dwelling's original construction.
Staging	HO_DWLNG	PLUMBING_UPDT_YR	Plumbing Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling plumbing system.
Staging	HO_DWLNG	PRIM_HEAT_TYP_CD	Primary Heating Type Code	VARCHAR2(25)	This system code describes the primary source of heat for dwelling.
Staging	HO_DWLNG	PROP_LOT_SIZE	Property Lot Size	NUMBER (14,3)	This number represents the area measurement of the land within the property lot boundaries.
Staging	HO_DWLNG	PURCH_DT	Purchase Date	DATE	This calendar date represents when the insured purchased the dwelling.
Staging	HO_DWLNG	PURCH_PRICE	Purchase Price	NUMBER (14,3)	This number represents the monetary amount paid when dwelling was purchased.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	HO_DWLNG	REPL_COST	Replacement Cost	NUMBER (14,3)	This number represents the monetary amount it would cost to replace a dwelling at current prices with like materials.
Staging	HO_DWLNG	ROOF_IMPACT_RATING_CD	RoofingImpact Rating Code	VARCHAR2(25)	This system code describes the level of hail impact a roof material can withstand.
Staging	HO_DWLNG	ROOF_MATL_CD	RoofingMaterial Code	VARCHAR2(25)	This system code identifies the material used to construct the roof.
Staging	HO_DWLNG	ROOF_UPDT_TYP_CD	RoofingUpdate Type Code	VARCHAR2(25)	This system code indicates the type or roofing updates made since the dwelling's original construction.
Staging	HO_DWLNG	ROOF_UPDT_YR	RoofingUpdate Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling roofing materials.
Staging	HO_DWLNG	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the homeowners dwelling with a specific transaction.
Staging	HO_DWLNG	SCND_HEAT_TYP_CD	Secondary Heating Type Code	VARCHAR2(25)	This system code describes the secondary source of heat for dwelling.
Staging	HO_DWLNG	SIDING_CD	Siding Code	VARCHAR2(25)	This system code identifies the type of material used as siding on the dwelling.
Staging	HO_DWLNG	SIDING_PCT	Siding Percentage	NUMBER (6,3)	This number represents the percentage of total dwelling exterior covered with siding.
Staging	HO_DWLNG	SPRINKLER_TYP_CD	Sprinkler Type Code	VARCHAR2(25)	This system code identifies the sprinkler system type.
Staging	HO_DWLNG	STORM_SHUTTERS_CD	Storm Shutters Code	VARCHAR2(25)	This system code describes the existence or absence and type of storm shutters.
Staging	HO_DWLNG	SWIM_POOL_CD	Swimming Pool Code	VARCHAR2(25)	This system code indicates the presence or absence and type of swimming pool.
Staging	HO_DWLNG	TRAMPOLINE_FLG	Trampoline Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a trampoline.
Staging	HO_DWLNG	UNDER_CONST_TYP_CD	Under Construction Type Code	VARCHAR2(25)	This system code indicates active construction activities on the dwelling.
Staging	HO_DWLNG	WIRG_LAST_INSP_DT	Wiring Last InspectedDate	DATE	This calendar date represents the occurance of the last inspection of the wiring system.
Staging	HO_DWLNG	WIRG_UPDT_TYP_CD	Wiring Update Type Code	VARCHAR2(25)	This system code identifies the type of update to wiring system.
Staging	HO_DWLNG	WIRG_UPDT_YR	Wiring Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling wiring system.
Staging	HO_DWLNG	YR_BUILT	Year Built	CHAR(4)	This value represents the calendar year that the dwelling was constructed.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	INSD	AUDIT_FREQ_CD	Audit Frequency Code	VARCHAR2(25)	This system code identifies the intervals at which audits of the insured attributes are performed at the insurance company.
Staging	INSD	AUDIT_TYP_CD	Audit Type Code	VARCHAR2(25)	This system code identifies what type of audit will be performed when the insured is audited.
Staging	INSD	CRED_SCORE	Credit Score	VARCHAR2(11)	This value represents the rating from the current credit report.
Staging	INSD	INSD_TYP_CD	Insured Type Code	VARCHAR2(25)	This system code indicates the type of entity that a policy represents.
Staging	INSD	INSD_UDF_CD_1	Insured User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first insured user defined field.
Staging	INSD	INSD_UDF_CD_2	Insured User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second insured user defined field.
Staging	INSD	INSD_UDF_CD_3	Insured User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third insured user defined field.
Staging	INSD	INSD_UDF_CD_4	Insured User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth insured user defined field.
Staging	INSD	INSD_UDF_CD_5	Insured User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth insured user defined field.
Staging	INSD	PRIOR_INSUR_CO_CD	Prior Insurance Company Code	VARCHAR2(25)	This system code represents the prior insurance company.
Staging	INSD	RISK_GRADE_CD	Risk Grade Code	VARCHAR2(25)	This system code represents the A.M. Best or company defined risk grade in the insured.
Staging	INSD	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the insured with a specific transaction.
Staging	INSD	RPT_PERIOD_CD	Reporting Period Code	VARCHAR2(25)	This system code identifies the frequency with which reports are due for policies issued on a reporting basis.
Staging	INSUR_CO	AM_BEST_NUM	A.M. Best Number	VARCHAR2(5)	This value represents the insurance company code assigned by A.M. Best.
Staging	INSUR_CO	INSUR_CO_RLAT_CD	Insurance Company Relationship Code	VARCHAR2(25)	This system code identifies the insurance company relationship.
Staging	INSUR_CO	INSUR_CO_TYP_CD	Insurance Company Type Code	VARCHAR2(25)	This system code identifies insurance company type.
Staging	INSUR_CO	INSUR_CO_UDF_CD_1	Insurance Company User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first insurance company user defined field.
Staging	INSUR_CO	INSUR_CO_UDF_CD_2	Insurance Company User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second insurance company user defined field.
Staging	INSUR_CO	INSUR_CO_UDF_CD_3	Insurance Company User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third insurance company user defined field.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	INSUR_CO	INSUR_CO_UDF_CD_4	Insurance Company User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth insurance company user defined field.
Staging	INSUR_CO	INSUR_CO_UDF_CD_5	Insurance Company User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth insurance company user defined field.
Staging	INSUR_CO	ISO_CD	Insurance Services Office Code	VARCHAR2(5)	This value represents the company code assigned by ISO.
Staging	INSUR_CO	NAIC_CD	National Association of Insurance Commissioners Code	VARCHAR2(5)	This system code is assigned to the company to use for NAIC reporting - The National Association of Insurance Commissioners Code groups types of business.
Staging	INSUR_CO	NCCI_CD	NCCI Code	VARCHAR2(5)	This system code is assigned to the company to use for National Council on Compensation insurance (NCCI) reporting.
Staging	INSUR_CO	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the insurance company with a specific transaction.
Staging	LITG	ALT_DISPUTE_RESOLUTION_CD	Alternate Dispute Resolution Code	VARCHAR2(25)	This system code identifies the outcome of using an intermediary for dispute settlement.
Staging	LITG	COMPENSATORY_DEMAND_AMT	Compensatory Demand Amount	NUMBER (14,3)	This number represents the amount of requested compensatory damages.
Staging	LITG	COMPENSATORY_OFFER_AMT	Compensatory Offer Amount	NUMBER (14,3)	This number represents the amount of offered compensatory damages.
Staging	LITG	DISCLOSURE_DT	Disclosure Date	DATE	This date represents the calendar date of disclosure of information related to litigation.
Staging	LITG	LITG_AMT	Litigation Amount	NUMBER (14,3)	This number represents the amount of litigation case.
Staging	LITG	LITG_CLOSED_DT	Litigation Closed Date	DATE	This calendar date represents when litigation case was closed.
Staging	LITG	LITG_CNTY_CD	Litigation County Code	VARCHAR2(25)	This system code describes a litigation county.
Staging	LITG	LITG_DISPOSITION_CD	Litigation Disposition Code	VARCHAR2(25)	This system code identifies the litigation disposition.
Staging	LITG	LITG_NAT_KEY	Litigation Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the litigation.
Staging	LITG	LITG_OPENED_DT	Litigation Opened Date	DATE	This calendar date represents when litigation case was filed in court.
Staging	LITG	LITG_STATE_CD	Litigation State Code	VARCHAR2(25)	This system code identifies the litigation state.
Staging	LITG	LITG_UDF_CD_1	Litigation User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first litigation user defined field.
Staging	LITG	LITG_UDF_CD_2	Litigation User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second litigation user defined field.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	LITG	LITG_UDF_CD_3	Litigation User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third litigation user defined field.
Staging	LITG	LITG_UDF_CD_4	Litigation User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth litigation user defined field.
Staging	LITG	LITG_UDF_CD_5	Litigation User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth litigation user defined field.
Staging	LITG	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the litigation with a specific transaction.
Staging	LITG	TRIAL_DT	Trial Date	DATE	This calendar date represents the when the trial is scheduled, or has already occurred.
Staging	LMT	FIRST_LMT	First Limit	VARCHAR2(15)	This value represents the first limit.
Staging	LMT	FULL_LMT	Full Limit	VARCHAR2(50)	This value represents the unabbreviated limit amount.
Staging	LMT	LMT_APPLIES_TO_CD	Limit Applies To Code	VARCHAR2(25)	This system code identifies the limit applies to.
Staging	LMT	LMT_BASIS_CD	Limit Basis Code	VARCHAR2(25)	This system code identifies limit basis.
Staging	LMT	LMT_NAT_KEY	Limit Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the limit.
Staging	LMT	LMT_TYP_CD	Limit Type Code	VARCHAR2(25)	This system code identifies limit type.
Staging	LMT	LMT_UDF_CD_1	Limit User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first limit user defined field.
Staging	LMT	LMT_UDF_CD_2	Limit User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second limit user defined field.
Staging	LMT	LMT_UDF_CD_3	Limit User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third limit user defined field.
Staging	LMT	LMT_UDF_CD_4	Limit User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth limit user defined field.
Staging	LMT	LMT_UDF_CD_5	Limit User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth limit user defined field.
Staging	LMT	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the limit with a specific transaction.
Staging	LMT	SECOND_LMT	Second Limit	VARCHAR2(15)	This value represents the second limit.
Staging	LMT	THIRD_LMT	Third Limit	VARCHAR2(15)	This value identifies the third limit.
Staging	LMT	VALUATION_CD	Valuation Code	VARCHAR2(25)	This value describes the code assigned in the method of loss valuation.
Staging	LOB	CO_PROD_CD	Company Product Code	VARCHAR2(25)	This system code identifies the company product.
Staging	LOB	LOB_CD	Line Of Business Code	VARCHAR2(25)	This system code identifies the line of business classification.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	LOB	LOB_NAT_KEY	Line of Business Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the line of business.
Staging	LOB	LOB_SUB_CD	Line Of Business Sub Code	VARCHAR2(25)	This system code identifies the line of business sub code that further refines the line of business code.
Staging	LOB	LOB_UDF_CD_1	Line of Business User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first line of business user defined field.
Staging	LOB	LOB_UDF_CD_2	Line of Business User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second line of business user defined field.
Staging	LOB	LOB_UDF_CD_3	Line of Business User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third line of business user defined field.
Staging	LOB	LOB_UDF_CD_4	Line of Business User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth line of business user defined field.
Staging	LOB	LOB_UDF_CD_5	Line of Business User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth line of business user defined field.
Staging	LOB	PSNL_OR_COML_CD	Personal Or Commercial Code	VARCHAR2(25)	This system code indicates if the policy is a personal or commercial policy.
Staging	LOB	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the line of business with a specific transaction.
Staging	ORG	BUS_START_DT	Business Start Date	DATE	This calendar date represents when the insurance company began business operations.
Staging	ORG	DBA	Doing Business As	VARCHAR2(170)	This value represents the type or category of the business activities done by the organization.
Staging	ORG	NAICS_CD	North American Industry Classification System Code	VARCHAR2(25)	This system code is assigned to the company to use for NAICS reporting - The North American Industry Classification System groups types of business.
Staging	ORG	NOB_CD	Nature of Business Code	VARCHAR2(25)	This system code identifies the nature of business of organization.
Staging	ORG	NUM_EMP	Number Of Employees	NUMBER (22,0)	This number represents the count of people employed by organization.
Staging	ORG	ORG_NM	Organization Name	VARCHAR2(170)	This value represents the name of an organization.
Staging	ORG	ORG_RLAT_CD	Organization Relationship Code	VARCHAR2(25)	This system code indicates the organization relationship.
Staging	ORG	ORG_UDF_CD_1	Organization User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first organization user defined field.
Staging	ORG	ORG_UDF_CD_2	Organization User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second organization user defined field.
Staging	ORG	ORG_UDF_CD_3	Organization User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third organization user defined field.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	ORG	ORG_UDF_CD_4	Organization User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth organization user defined field.
Staging	ORG	ORG_UDF_CD_5	Organization User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth organization user defined field.
Staging	ORG	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the organization with a specific transaction.
Staging	ORG	SIC_CD	Standard Industrial Classification Code	VARCHAR2(25)	The Standard Industrial Classification (SIC) code is an industry code that identifies the classification of business activity. This is the SIC assigned to the company.
Staging	PA_DRV	COMMUTER_DSCNT_FLG	Commuter Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of commuter discount.
Staging	PA_DRV	COMMUTER_DSCNT_PCT	Commuter Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when commuter discount applies.
Staging	PA_DRV	DFEN_DRV_CD	Defensive Driving Code	VARCHAR2(25)	This system code indicates the type of defensive driving course the driver completed.
Staging	PA_DRV	DFEN_DRV_TRNG_DSCNT_FLG	Defensive Driving Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a defensive driver training discount is applicable.
Staging	PA_DRV	DFEN_DRV_TRNG_DSCNT_PCT	Defensive Driving Training Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when driver training discount applies.
Staging	PA_DRV	DIST_STUDENT_FLG	Distant Student Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not the student driver meets the company definition of distant driver.
Staging	PA_DRV	DRV_ACCID_CNT	Driver Accident Count	NUMBER (22,0)	This number represents the count of reported accidents charged against the driver's driving record.
Staging	PA_DRV	DRV_CLASS_CD	Driver Class Code	VARCHAR2(25)	This system code identifies the class assigned to a personal vehicle driver.
Staging	PA_DRV	DRV_DWI_DUI_VIOLATION_CNT	Driver DWI / DUI Violation Count	NUMBER (22,0)	This number represents the count of Driving While intoxicated (DWI) and/or Driving Under the influence (DUI) violations charged against the driver's driving record.
Staging	PA_DRV	DRV_INTRMDT_VIOLATION_CNT	Driver Intermediate Violation Count	NUMBER (22,0)	This number represents the count of intermediate violations charged against the driver's driving record.
Staging	PA_DRV	DRV_LIC_ISSUED_BY_CD	Driver License Issued By Code	VARCHAR2(25)	This system code indentifies which entity granted driving privileges to driver.
Staging	PA_DRV	DRV_LIC_STATUS_CD	Driver License Status Code	VARCHAR2(25)	This system code indicates the driver license status.
Staging	PA_DRV	DRV_MAJOR_VIOLATION_CNT	Driver Major Violation Count	NUMBER (22,0)	This number represents the count of major violations charged against the driver's driving record.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PA_DRV	DRV_MINOR_VIOLATION_CNT	Driver Minor Violation Count	NUMBER (22,0)	This number represents the count of minor violations charged against the driver's driving record.
Staging	PA_DRV	DRV_NUM	Driver Number	NUMBER (22,0)	This number identifies the driver.
Staging	PA_DRV	DRV_OCP	Driver Occupation	VARCHAR2(50)	This value represents the classification of employment tasks completed during personal vehicle driver's employment.
Staging	PA_DRV	DRV_STATUS_CD	Driver Status Code	VARCHAR2(25)	This system code indicates the driver status.
Staging	PA_DRV	DRV_TRNG_DSCNT_FLG	Driver Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not the driver is receiving a driver training discount.
Staging	PA_DRV	DRV_TRNG_DSCNT_PCT	Driver Training Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when driver training discount applies.
Staging	PA_DRV	DRV_TRNG_FLG	Driver Training Flag	CHAR(1)	This value represents based on the yes/no indicator that identifies whether or not a driver has completed a driver training course.
Staging	PA_DRV	DRV_TYP_CD	Driver Type Code	VARCHAR2(25)	This system code describes the driver activities.
Staging	PA_DRV	GOOD_STUDENT_CD	Good Student Code	VARCHAR2(25)	This system code identifies if the driver qualifies in the good student credit.
Staging	PA_DRV	GOOD_STUDENT_DSCNT_FLG	Good Student Discount Flag	CHAR(1)	This value represents based on the yes/no indicator that identifies whether or not a driver has met the company's definition of a good student.
Staging	PA_DRV	GOOD_STUDENT_DSCNT_PCT	Good Student Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when good student discount applies.
Staging	PA_DRV	INSD_DT	Insured Date	DATE	This calendar date represents when insurance coverage began for personal driver.
Staging	PA_DRV	LIC_DT	License Date	DATE	This calendar date represents when personal vehicle driver was granted a drivers license.
Staging	PA_DRV	NUM_YRS_AT_CUR_ADDR	Number Of Years At Current Address	NUMBER (22,0)	This number represents the count of years personal vehicle driver has resided at current address.
Staging	PA_DRV	PA_DRV_UDF_CD_1	Personal Auto Driver User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first personal vehicle driver user defined field.
Staging	PA_DRV	PA_DRV_UDF_CD_2	Personal Auto Driver User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second personal vehicle driver user defined field.
Staging	PA_DRV	PA_DRV_UDF_CD_3	Personal Auto Driver User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third personal vehicle driver user defined field.
Staging	PA_DRV	PA_DRV_UDF_CD_4	Personal Auto Driver User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth personal vehicle driver user defined field.
Staging	PA_DRV	PA_DRV_UDF_CD_5	Personal Auto Driver User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth personal vehicle driver user defined field.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PA_DRV	RLAT_TO_APPLICANT_CD	Relationship to Applicant Code	VARCHAR2(25)	This system code identifies the relationship of this individual to the applicant.
Staging	PA_DRV	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the personal vehicle driver with a specific transaction.
Staging	PA_DRV	YOUTHFUL_CD	Youthful Code	VARCHAR2(25)	This value represents based on the yes/no indicator identifying whether or not a driver meets the company criteria of a youthful driver.
Staging	PA_VEH	ADDL_EQPT_AMT	Additional Equipment Amount	NUMBER (14,3)	This number represents the monetary cost of vehicle alterations or aftermarket custom equipment like custom painting, equipment installed to overcome a physical handicap, etc. installed on a personal vehicle.
Staging	PA_VEH	AIRBAG_TYP_CD	Airbag Type Code	VARCHAR2(25)	This system code identifies the attributes of the airbag system installed in the personal vehicle.
Staging	PA_VEH	ANTI_LOCK_BRAKES_CD	Anti-lock Brake Code	VARCHAR2(25)	This system code identifies the attributes of anti-lock brakes on the personal vehicle.
Staging	PA_VEH	ANTI_THEFT_DEVICE_CD	Anti-Theft Device Code	VARCHAR2(25)	This system code identifies the attributes of the anti-theft system installed on the personal vehicle.
Staging	PA_VEH	AUTO_STBLTS_DSCNT_FLG	Automatic Seatbelt Type Code	CHAR(1)	This system code identifies whether an automatic seatbelt discount applies to the personal vehicle.
Staging	PA_VEH	AUTO_STBLTS_DSCNT_PCT	Automatic Seatbelt Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when automatic seatbelt discount applies.
Staging	PA_VEH	CELL_PHONE_TYP_CD	Cellular Phone Type Code	VARCHAR2(25)	This system code identifies the attributes of a cellular phone present in the vehicle.
Staging	PA_VEH	DAYTIME_RUN_LIGHTS_CD	Daytime Running Lights Code	VARCHAR2(25)	This value represents based on the yes/no indicator that states whether or not a vehicle has daytime running headlights.
Staging	PA_VEH	EST_ANNU_DRVG_DIST	Estimated Annual Driving Distance	NUMBER (22,0)	This number represents the estimated number of distance units (miles/kilometers) a vehicle is driven over a one year period.
Staging	PA_VEH	GAR_CD	Garaging Code	VARCHAR2(25)	This system code identifies where the vehicle is parked at night.
Staging	PA_VEH	HP_DSPLCMNT	Horsepower Displacement	VARCHAR2(5)	This value represents the cubic centimeters or displacement (for example, motorcycles) or horsepower for recreational vehicles.
Staging	PA_VEH	INSD_DT	Insured Date	DATE	This calendar date represents when insurance coverage began for a personal vehicle.
Staging	PA_VEH	LEASE_DT	Persona Auto Vehicle Lease Date	DATE	This calendar date represents when a personal vehicle was leased by insured.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PA_VEH	MSRP	Manufacturer Suggested Retail Price	NUMBER (14,3)	This number represents the price that the manufacturer tells the vehicle dealer the new vehicle is worth.
Staging	PA_VEH	MULT_CAR_DSCNT_FLG	Multiple Car Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a multiple car discount applies.
Staging	PA_VEH	MULT_CAR_DSCNT_PCT	Multiple Car Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when a multiple car discount applies.
Staging	PA_VEH	NEW_OR_USED_CD	New Or Used Code	VARCHAR2(25)	This system code identifies if the insured is the original owner of the insured vehicle.
Staging	PA_VEH	NUM_DAYS_DRVN_PER_WK	Number Of Days Driven Per Week	NUMBER (22,0)	This number represents the count of days the personal vehicle is driven each calendar week.
Staging	PA_VEH	ONE_WAY_DIST_TO_WRK	One Way Distance To Work	NUMBER (22,0)	This number represents the number of distance units (miles/ kilometers) to place of employment.
Staging	PA_VEH	OWNRSHP_TYP_CD	Ownership Type Code	VARCHAR2(25)	This system code describes the ownership type of a vehicle Standard code.
Staging	PA_VEH	PA_VEH_NAT_KEY	Persona Auto Vehicle Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the personal vehicle.
Staging	PA_VEH	PA_VEH_UDF_CD_1	Persona Auto Vehicle User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first personal vehicle user defined field.
Staging	PA_VEH	PA_VEH_UDF_CD_2	Persona Auto Vehicle User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second personal vehicle user defined field.
Staging	PA_VEH	PA_VEH_UDF_CD_3	Persona Auto Vehicle User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third personal vehicle user defined field.
Staging	PA_VEH	PA_VEH_UDF_CD_4	Persona Auto Vehicle User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth personal vehicle user defined field.
Staging	PA_VEH	PA_VEH_UDF_CD_5	Persona Auto Vehicle User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth personal vehicle user defined field.
Staging	PA_VEH	PURCH_DT	Purchase Date	DATE	This calendar date represents when the insured purchased the personal vehicle.
Staging	PA_VEH	PURCH_PRICE	Purchase Price	NUMBER (14,3)	This number represents the monetary amount paid when personal vehicle was purchased.
Staging	PA_VEH	RATING_AGE_CD	Rating Age Code	VARCHAR2(25)	This system code represents the rating age used to rate the vehicle, regardless of its actual age.
Staging	PA_VEH	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the personal vehicle with a specific transaction.
Staging	PA_VEH	STATED_AMT	Stated Amount	NUMBER (14,3)	This number represents the monetary cost used to rate and value a vehicle when a symbol is not available or useful.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PA_VEH	VEH_BODY_TYP_CD	Vehicle Body Type Code	VARCHAR2(25)	This system code describes the attributes of vehicle body for a scheduled personal vehicle.
Staging	PA_VEH	VEH_CLASS_CD	Vehicle Class Code	VARCHAR2(25)	This value represents the classification that describes vehicle size and body type.
Staging	PA_VEH	VEH_COST_NEW	Vehicle Cost New	NUMBER (14,3)	This number represents the monetary price of vehicle when purchased as a new vehicle.
Staging	PA_VEH	VEH_CUR_VAL	Vehicle Current Value	NUMBER (14,3)	This number represents the current monetary value of the personal vehicle in marketplace.
Staging	PA_VEH	VEH_GROSS_WT	Vehicle Gross Weight	NUMBER (14,3)	This number represents the total weight a vehicle is designed to carry and includes the net weight of the vehicle, plus the weight of passengers, fuel, cargo and any additional accessories.
Staging	PA_VEH	VEH_MFR	Vehicle Manufacturer	VARCHAR2(20)	This value represents the name of manufacturer that created the personal vehicle.
Staging	PA_VEH	VEH_MODEL	Vehicle Model	VARCHAR2(20)	This value represents the model name assigned by manufacturer of personal vehicle.
Staging	PA_VEH	VEH_NUM	Vehicle Number	NUMBER (22,0)	This number is the system assigned number that identifies personal vehicle.
Staging	PA_VEH	VEH_PERF_CD	Vehicle Performance Code	VARCHAR2(25)	This system code identifies the performance level of the vehicle.
Staging	PA_VEH	VEH_SYM_CD	Vehicle Symbol Code	VARCHAR2(25)	This system code is a cost symbol that represents a value in the personal vehicle.
Staging	PA_VEH	VEH_USE_CD	Vehicle Use Code	VARCHAR2(25)	This system code identifies the primary use of the vehicle.
Staging	PA_VEH	VEH_YR	Vehicle Year	CHAR(4)	This value represents the model year assigned by vehicle manufacturer.
Staging	PA_VEH	VIN	Vehicle Identification Number	VARCHAR2(25)	This value represents the vehicle identification number assigned by the manufacturer of the personal vehicle at risk.
Staging	PARTY	GOVT_ID_NUM	Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the party. For example, in the USA: SSN or FEIN.
Staging	PARTY	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Staging	PARTY	PARTY_RLAT_CD	Party Relationship Code	VARCHAR2(25)	This system code identifies the party relationship.
Staging	PARTY	PARTY_UDF_CD_1	Party User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first party user defined field.
Staging	PARTY	PARTY_UDF_CD_2	Party User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second party user defined field.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PARTY	PARTY_UDF_CD_3	Party User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third party user defined field.
Staging	PARTY	PARTY_UDF_CD_4	Party User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth party user defined field.
Staging	PARTY	PARTY_UDF_CD_5	Party User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth party user defined field.
Staging	PARTY	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the party with a specific transaction.
Staging	PERS	BIRTH_DT	Birth Date	DATE	This date represents the calendar date of birth of the person listed on an insurance policy.
Staging	PERS	FIRST_NM	First Name	VARCHAR2(50)	This value represents the first name of the person.
Staging	PERS	GENDER_CD	Gender Code	VARCHAR2(25)	This system code abbreviates the gender (male or female).
Staging	PERS	LAST_NM	Last Name	VARCHAR2(50)	This value represents the last name of the person.
Staging	PERS	MARITAL_STATUS_CD	Marital Status Code	VARCHAR2(25)	This system code identifies the present marital condition (single, married, divorced, widowed) of the person.
Staging	PERS	MIDDLE_NM	Middle Name	VARCHAR2(50)	This value represents the middle name of the person.
Staging	PERS	PERS_RLAT_CD	Person Relationship Code	VARCHAR2(25)	This system code identifies the person relationship.
Staging	PERS	PERS_UDF_CD_1	Person User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first person user defined field.
Staging	PERS	PERS_UDF_CD_2	Person User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second person user defined field.
Staging	PERS	PERS_UDF_CD_3	Person User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third person user defined field.
Staging	PERS	PERS_UDF_CD_4	Person User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth person user defined field.
Staging	PERS	PERS_UDF_CD_5	Person User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth person user defined field.
Staging	PERS	PRES_EMPLMT_START_YR	Present Employment Start Year	CHAR(4)	This value represents the calendar year that the person began working for their current employer.
Staging	PERS	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the person with a specific transaction.
Staging	PERS	SUFFIX	Suffix	VARCHAR2(8)	This value represents the suffix after a surname to identify a person. Examples include Jr. and Sr.
Staging	PERS	TITLE	Title	VARCHAR2(8)	This value represents the title to precede the name which is not part of the actual name.
Staging	PLCY	ACTV_OR_CNCLD_CD	Active Or Canceled Code	VARCHAR2(25)	This system code describes whether this policy is active or canceled.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PLCY	CNCL_REASON_CD	Cancel Reason Code	VARCHAR2(25)	This system code describes the reason for a cancellation.
Staging	PLCY	EXPO_BASIS_CD	Exposure Basis Code	VARCHAR2(25)	This value represents the exposure basis is the denomination in which the exposure units are expressed.
Staging	PLCY	MONOLINE_OR_PKG_CD	Monoline or Package Code	VARCHAR2(25)	This system code tells if a policy is a monoline policy or is written as part of a package.
Staging	PLCY	NEW_OR_RENEWAL_CD	New or Renewal Code	VARCHAR2(25)	This value represents the indicator of whether this policy is a new policy or a renewal policy.
Staging	PLCY	PKG_DSCNT_CD	Package Discount Code	VARCHAR2(25)	This system code indicates the presence or absence of a package discount.
Staging	PLCY	PKG_DSCNT_PCT	Package Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when package discount applies.
Staging	PLCY	PKG_MOD_ASSIGNMENT_CD	Package Modification Assignment Code	VARCHAR2(25)	This system code indicates the package modification assignment.
Staging	PLCY	PKG_MOD_FCT	Package Modification Factor	NUMBER (6,3)	This number represents the percentage of premium waived as a result of packaging coverages.
Staging	PLCY	PLCY_CNCL_DT	Policy Cancellation Date	DATE	This calendar date represents when policy coverage ceased due to a cancellation.
Staging	PLCY	PLCY_EFF_DT	Policy Effective Date	DATE	This calendar date represents when policy coverage began.
Staging	PLCY	PLCY_EXPR_DT	Policy Expiration Date	DATE	This calendar date represents when the policy term ends.
Staging	PLCY	PLCY_NAT_KEY	Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the policy.
Staging	PLCY	PLCY_NUM	Policy Number	VARCHAR2(25)	This value represents a number or other identifier for a policy.
Staging	PLCY	PLCY_ORIG_INCPN_DT	Policy Original Inception Date	DATE	This calendar date represents when insured originally purchased insurance coverage with the insurance company.
Staging	PLCY	PLCY_TYP_CATG_CD	Policy Type Category Code	VARCHAR2(25)	This system code identifies the policy type category.
Staging	PLCY	PLCY_TYP_CD	Policy Type Code	VARCHAR2(25)	This system code identifies the type of policy as it would normally be identified on a coverage level.
Staging	PLCY	PLCY_UDF_CD_1	Policy User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first policy user defined field.
Staging	PLCY	PLCY_UDF_CD_2	Policy User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second policy user defined field.
Staging	PLCY	PLCY_UDF_CD_3	Policy User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third policy user defined field.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PLCY	PLCY_UDF_CD_4	Policy User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth policy user defined field.
Staging	PLCY	PLCY_UDF_CD_5	Policy User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth policy user defined field.
Staging	PLCY	PLCY_VERSION	Policy Version	VARCHAR2(4)	This value represents the number or other identifier used by the company to identify 'this' version of the policy.
Staging	PLCY	PREM_BASIS_CD	Premium Basis Code	VARCHAR2(25)	This system code identifies the type of rating scale used.
Staging	PLCY	RENEWAL_TERM	Renewal Term in Months	VARCHAR2(3)	This value represents the length of the renewal policy period (term) in months (006,012).
Staging	PLCY	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the policy with a specific transaction.
Staging	PLCY	SUPPORTING_BUS_DSCNT_PCT	Supporting Business Discount Percentage	NUMBER (6,3)	This number represents the percentage of premium waived when supporting business discount applies.
Staging	PLCY	SUPPORTING_BUS_TYP_CD	Supporting Business Type Code	VARCHAR2(25)	This value represents the type of supporting business for which the policyholder received a discount standard code.
Staging	PLCY_TRANS	BOOK_DT	Book Date	DATE	This date represents the calendar date the policy transaction is recorded into the company's books. Usually, this is the greater of the transaction date or the effective date.
Staging	PLCY_TRANS	COMM_AMT	Commission Amount	NUMBER (14,3)	This number represents the amount of commission to be paid for a transaction.
Staging	PLCY_TRANS	COMM_RATE	Commission Rate	NUMBER (6,5)	This number represents the rate at which the policy commission is to be paid.
Staging	PLCY_TRANS	COVRG_EFF_DT	Coverage Effective Date	DATE	This date represents the calendar date of the policy coverage begins.
Staging	PLCY_TRANS	COVRG_EXPR_DT	Coverage Expiration Date	DATE	This date represents the calendar date of the policy coverage ends.
Staging	PLCY_TRANS	DED_AMT	Deductible Amount	NUMBER (14,3)	This number represents the monetary cost portion of any claim that is not covered by the insurer.
Staging	PLCY_TRANS	DIRECT_CEDED_ASSUMED_CD	Direct or Ceded or Assumed Code	VARCHAR2(25)	This system code identifies the transaction type as being direct, ceded, or assumed.
Staging	PLCY_TRANS	DOC_CURR_CD	Document Currency Code	VARCHAR2(25)	This system code identifies document currency for a policy transaction.
Staging	PLCY_TRANS	ONSET_OR_OFFSET_CD	Onset or Offset Code	VARCHAR2(25)	This value represents the indicator of onset or offset transactions.
Staging	PLCY_TRANS	ORIG_PREM_AMT	Original Premium Amount	NUMBER (14,3)	This number represents the original premium in the term of coverage.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PLCY_TRANS	PLCY_TRANS_AMT	Policy Transaction Amount	NUMBER (14,3)	This number represents the amount of any transaction processed for a policy.
Staging	PLCY_TRANS	PLCY_TRANS_CATG_CD	Policy Transaction Category Code	VARCHAR2(25)	This system code groups like transactions for analysis.
Staging	PLCY_TRANS	PLCY_TRANS_CD	Policy Transaction Code	VARCHAR2(25)	This system code identifies the policy transaction.
Staging	PLCY_TRANS	PREM_OR_NON_PREM_CD	Premium or Non-Premium Code	VARCHAR2(25)	This system code describes if a policy transaction resulted in a change in the premium charged for an existing policy.
Staging	PLCY_TRANS	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the policy transaction with a specific transaction.
Staging	PLCY_TRANS	SRC_SYS_PROC_DT	Source System Process Date	DATE	This calendar date represents when source system processed the policy transaction.
Staging	PLCY_TRANS	TRANS_EFF_DT	Transaction Effective Date	DATE	This calendar date represents when a policy transaction is effective.
Staging	PLCY_TRANS	WRTN_EXPO_AMT	Written Exposure Amount	NUMBER (14,3)	This number represents the measure of the loss exposure assumed by the insurer.
Staging	PRODR	PRODR_EFF_DT	Producer Effective Date	DATE	This date represents the calendar date the producer appointment begins.
Staging	PRODR	PRODR_NUM	Producer Number	VARCHAR2(10)	This value represents the number or other identifier assigned to the producer of the business.
Staging	PRODR	PRODR_RLAT_CD	Producer Relationship Code	VARCHAR2(25)	This system code identifies the producer relationship.
Staging	PRODR	PRODR_TYP_CD	Producer Type Code	VARCHAR2(25)	This system code represents the producer type standard code.
Staging	PRODR	PRODR_UDF_CD_1	Producer User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first producer user defined field.
Staging	PRODR	PRODR_UDF_CD_2	Producer User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second producer user defined field.
Staging	PRODR	PRODR_UDF_CD_3	Producer User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third producer user defined field.
Staging	PRODR	PRODR_UDF_CD_4	Producer User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth producer user defined field.
Staging	PRODR	PRODR_UDF_CD_5	Producer User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth producer user defined field.
Staging	PRODR	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the producer with a specific transaction.
Staging	PRODR	STATE_LIC_NUM	State License Number	VARCHAR2(10)	This value represents the license number of the producer as assigned by the state insurance department.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PSTL_ADDR	ADDR_1	Address Line 1	VARCHAR2(60)	This value represents the first line of the postal address.
Staging	PSTL_ADDR	ADDR_2	Address Line 2	VARCHAR2(60)	This value represents the second line of the postal address.
Staging	PSTL_ADDR	CNTY_CD	County Code	VARCHAR2(25)	This system code describes a county associated with the postal address.
Staging	PSTL_ADDR	CTRY_CD	Country Code	VARCHAR2(25)	This system code describes a county associated with the postal address.
Staging	PSTL_ADDR	CTY	City	VARCHAR2(32)	This value identifies the city in the postal address.
Staging	PSTL_ADDR	DSTRCT_CD	District Code	VARCHAR2(25)	This system code identifies the company-defined district associated with the postal address.
Staging	PSTL_ADDR	LATITUDE	Latitude	VARCHAR2(11)	This value represents the latitude location of the postal address.
Staging	PSTL_ADDR	LONGITUDE	Longitude	VARCHAR2(11)	This value represents the longitude location of the postal address.
Staging	PSTL_ADDR	PSTL_ADDR_RLAT_CD	Postal Address Relationship Code	VARCHAR2(25)	This system code identifies the postal address relationship.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_1	Postal Address User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first postal address user defined field.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_10	Postal Address User Defined Field Code 10	VARCHAR2(25)	This system code identifies the tenth postal address user defined field.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_2	Postal Address User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second postal address user defined field.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_3	Postal Address User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third postal address user defined field.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_4	Postal Address User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth postal address user defined field.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_5	Postal Address User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth postal address user defined field.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_6	Postal Address User Defined Field Code 6	VARCHAR2(25)	This system code identifies the sixth postal address user defined field.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_7	Postal Address User Defined Field Code 7	VARCHAR2(25)	This system code identifies the seventh postal address user defined field.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_8	Postal Address User Defined Field Code 8	VARCHAR2(25)	This system code identifies the eighth postal address user defined field.
Staging	PSTL_ADDR	PSTL_ADDR_UDF_CD_9	Postal Address User Defined Field Code 9	VARCHAR2(25)	This system code identifies the ninth postal address user defined field.
Staging	PSTL_ADDR	PSTL_CD	Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PSTL_ADDR	PSTL_CD_PRFX	Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.
Staging	PSTL_ADDR	PSTL_SUB_CD	Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Staging	PSTL_ADDR	REGION_CD	Region Code	VARCHAR2(25)	This system code identifies the geographic region as defined by company specifications.
Staging	PSTL_ADDR	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the postal address with a specific transaction.
Staging	PSTL_ADDR	STATE_CD	State Code	VARCHAR2(25)	This value identifies the state associated with the postal address.
Staging	PSTL_ADDR	TAX_LOC_ID	Tax Location Identifier	VARCHAR2(6)	This value represents the classification of the taxing entity for a postal address.
Staging	PSTL_ADDR	TERR_CD	Territory Code	VARCHAR2(25)	This system code describes the territory for a postal address.
Staging	PU_PLCY	DF_INSUR_CO_NM	Dwelling Fire Insurance Company Name	VARCHAR2(170)	This value represents the name of insurance company that provides dwelling fire policy coverage for insured.
Staging	PU_PLCY	DF_PLCY_EFF_DT	Dwelling Fire Policy Effective Date	DATE	This date represents the calendar date dwelling fire policy coverage begins.
Staging	PU_PLCY	DF_PLCY_EXPR_DT	Dwelling Fire Expiration Date	DATE	This date represents the calendar date dwelling fire policy term ends.
Staging	PU_PLCY	DF_PLCY_NUM	Dwelling Fire Policy Number	VARCHAR2(25)	This value represents a number or other identifier for a dwelling fire policy owned by named insured.
Staging	PU_PLCY	DF_PSNL_LIAB_LMT	Dwelling Fire Personal Liability Limit	VARCHAR2(15)	This value represents the personal liability coverage limit provided by dwelling fire policy owned by insured.
Staging	PU_PLCY	HO_INSUR_CO_NM	Homeowners Insurance Company Name	VARCHAR2(170)	This value represents the insurance company name of the insured's homeowners policy.
Staging	PU_PLCY	HO_PLCY_EFF_DT	Homeowners Policy Effective Date	DATE	This date is when coverage begins for a homeowners policy.
Staging	PU_PLCY	HO_PLCY_EXPR_DT	Homeowners Policy Expiration Date	DATE	This calendar date represents when homeowners coverage policy term ends.
Staging	PU_PLCY	HO_PLCY_NUM	Homeowners Policy Number	VARCHAR2(25)	This value represents a number or other identifier for a homeowners policy.
Staging	PU_PLCY	HO_PSNL_LIAB_LMT	Homeowners Personal Liability Limit	VARCHAR2(15)	This value represents the personal liability limit included under an insured's homeowners insurance policy.
Staging	PU_PLCY	PA_INSUR_CO_NM	Personal Auto Insurance Company Name	VARCHAR2(170)	This value represents the insurance company name that issued the insured's personal automobile policy.
Staging	PU_PLCY	PA_LIAB_FIRST_LMT	Personal Auto Liability First Limit	VARCHAR2(15)	This value represents the personal vehicle liability limit first limit.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	PU_PLCY	PA_LIAB_SECOND_LMT	Personal Auto Liability Second Limit	VARCHAR2(15)	This value represents the personal vehicle liability limit second limit.
Staging	PU_PLCY	PA_PLCY_EFF_DT	Personal Auto Policy Effective Date	DATE	This calendar date represents when insured's personal vehicle policy coverage began.
Staging	PU_PLCY	PA_PLCY_EXPR_DT	Personal Auto Policy Expiration Date	DATE	This calendar date represents when insured's personal vehicle policy term ends.
Staging	PU_PLCY	PA_PLCY_NUM	Personal Auto Policy Number	VARCHAR2(25)	This value represents the personal vehicle policy number.
Staging	PU_PLCY	PA_PROP_DMG_LMT	Personal Auto Property Damage Limit	VARCHAR2(15)	This value represents the personal vehicle property damage limit.
Staging	PU_PLCY	PA_UM_FIRST_LMT	Personal Auto Uninsured Motorist First Limit	VARCHAR2(15)	This value represents the personal vehicle uninsured/ underinsured motorist first limit.
Staging	PU_PLCY	PA_UM_SECOND_LMT	Personal Auto Uninsured Motorist Second Limit	VARCHAR2(15)	This value represents the personal vehicle uninsured/ underinsured motorist second limit.
Staging	PU_PLCY	PA_UM_THIRD_LMT	Personal Auto Uninsured Motorist Third Limit	VARCHAR2(15)	This value represents the personal vehicle uninsured/ underinsured motorist third limit.
Staging	PU_PLCY	PU_PLCY_NAT_KEY	Personal Umbrella Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the personal umbrella policy.
Staging	PU_PLCY	PU_PLCY_UDF_CD_1	Personal Umbrella Policy User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first personal umbrella policy user defined field.
Staging	PU_PLCY	PU_PLCY_UDF_CD_2	Personal Umbrella Policy User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second personal umbrella policy user defined field.
Staging	PU_PLCY	PU_PLCY_UDF_CD_3	Personal Umbrella Policy User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third personal umbrella policy user defined field.
Staging	PU_PLCY	PU_PLCY_UDF_CD_4	Personal Umbrella Policy User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth personal umbrella policy user defined field.
Staging	PU_PLCY	PU_PLCY_UDF_CD_5	Personal Umbrella Policy User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth personal umbrella policy user defined field.
Staging	PU_PLCY	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the personal umbrella policy with a specific transaction.
Staging	REINS_CNTRCT	CEDED_LOSS_RATIO	Ceded Loss Ratio	NUMBER (6,3)	This value represents the ratio of losses and loss adjustment expenses incurred to premiums earned for the portion of exposure that is transferred to a reinsurance company.
Staging	REINS_CNTRCT	FAC_COMM_PCT	Faculative Commission Percentage	NUMBER (6,3)	This number represents the percentage of premium the ceding company retains as a commission from the reinsurer.
Staging	REINS_CNTRCT	REINS_CNTRCT_BEGIN_DT	Reinsurance Contract Begin Date	DATE	This calendar date represents when reinsurance contract terms apply.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	REINS_CNTRCT	REINS_CNTRCT_CATG_CD	Reinsurance Contract Category Code	VARCHAR2(25)	This system code identifies the reinsurance contract category.
Staging	REINS_CNTRCT	REINS_CNTRCT_CERT_NUM	Reinsurance Contract Certificate Number	VARCHAR2(8)	This value represents the unique identifier assigned to the reinsurance contract certificate.
Staging	REINS_CNTRCT	REINS_CNTRCT_CESSION_NUM	Reinsurance Contract Cession Number	VARCHAR2(10)	This value represents the unique number or other identifier of the reinsurance contract cession.
Staging	REINS_CNTRCT	REINS_CNTRCT_END_DT	Reinsurance Contract Ending Date	DATE	This date represents the calendar date reinsurance contract ends.
Staging	REINS_CNTRCT	REINS_CNTRCT_LAYER_CD	Reinsurance Contract Layer Code	VARCHAR2(25)	This system code identifies the reinsurance contract layer.
Staging	REINS_CNTRCT	REINS_CNTRCT_NAT_KEY	Reinsurance Contract Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the reinsurance contract.
Staging	REINS_CNTRCT	REINS_CNTRCT_TREATY_NUM	Reinsurance Contract Treaty Number	VARCHAR2(8)	This value represents the number or other identifier assigned to the reinsurance contract treaty.
Staging	REINS_CNTRCT	REINS_CNTRCT_TYP_CD	Reinsurance Contract Type Code	VARCHAR2(25)	This system code identifies the reinsurance contract type.
Staging	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_1	Reinsurance Contract User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first reinsurance contract user defined field.
Staging	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_2	Reinsurance Contract User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second reinsurance contract user defined field.
Staging	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_3	Reinsurance Contract User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third reinsurance contract user defined field.
Staging	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_4	Reinsurance Contract User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth reinsurance contract user defined field.
Staging	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_5	Reinsurance Contract User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth reinsurance contract user defined field.
Staging	REINS_CNTRCT	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the reinsurance contract with a specific transaction.
Staging	REINS_CO	REINS_CO_NUM	Reinsurance Company Number	VARCHAR2(4)	This value represents the number or other identifier assigned to the reinsurance company.
Staging	REINS_CO	REINS_CO_TYP_CD	Reinsurance Company Type Code	VARCHAR2(25)	This system code identifies reinsurance company type.
Staging	REINS_CO	REINS_CO_UDF_CD_1	Reinsurance Company User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first reinsurance company user defined field.
Staging	REINS_CO	REINS_CO_UDF_CD_2	Reinsurance Company User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second reinsurance company user defined field.
Staging	REINS_CO	REINS_CO_UDF_CD_3	Reinsurance Company User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third reinsurance company user defined field.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	REINS_CO	REINS_CO_UDF_CD_4	Reinsurance Company User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth reinsurance company user defined field.
Staging	REINS_CO	REINS_CO_UDF_CD_5	Reinsurance Company User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth reinsurance company user defined field.
Staging	REINS_CO	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the reinsurance company with a specific transaction.
Staging	SUPPLIER	PREF_SUPPLIER_CD	Preferred Supplier Code	VARCHAR2(25)	This system code identifies if a supplier is a preferred supplier.
Staging	SUPPLIER	PREF_SUPPLIER_TYP_CD	Preferred Supplier Type Code	VARCHAR2(25)	This system code identifies preferred supplier type.
Staging	SUPPLIER	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the supplier with a specific transaction.
Staging	SUPPLIER	SUPPLIER_CATG_CD	Supplier Category Code	VARCHAR2(25)	This system code represents supplier category.
Staging	SUPPLIER	SUPPLIER_TYP_CD	Supplier Type Code	VARCHAR2(25)	This system code identifies supplier type.
Staging	SUPPLIER	SUPPLIER_UDF_CD_1	Supplier User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first supplier user defined field.
Staging	SUPPLIER	SUPPLIER_UDF_CD_2	Supplier User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second supplier user defined field.
Staging	SUPPLIER	SUPPLIER_UDF_CD_3	Supplier User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third supplier user defined field.
Staging	SUPPLIER	SUPPLIER_UDF_CD_4	Supplier User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth supplier user defined field.
Staging	SUPPLIER	SUPPLIER_UDF_CD_5	Supplier User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth supplier user defined field.
Staging	UW	ROW_NUM	Row Number	NUMBER (22,0)	This number, generated during the staging load, associates the underwriter with a specific transaction.
Staging	UW	UW_NUM	Underwriter Number	VARCHAR2(25)	This value represents the number or other identifier that identifies the underwriter.
Staging	UW	UW_RLAT_CD	Underwriter Relationship Code	VARCHAR2(25)	This system code identifies the underwriter relationship.
Staging	UW	UW_TYP_CD	Underwriter Type Code	VARCHAR2(25)	This system code identifies the underwriter type.
Staging	UW	UW_UDF_CD_1	Underwriter User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first underwriter user defined field.
Staging	UW	UW_UDF_CD_2	Underwriter User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second underwriter user defined field.
Staging	UW	UW_UDF_CD_3	Underwriter User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third underwriter user defined field.
Staging	UW	UW_UDF_CD_4	Underwriter User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth underwriter user defined field.

Staging (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Staging	UW	UW_UDF_CD_5	Underwriter User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth underwriter user defined field.

Warehouse

Warehouse

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	BILL_ACCT	BEGIN_DT	Begin Date	DATE	This calendar date represents when the bill account applies.
Warehouse	BILL_ACCT	BILL_ACCT_ID	Billing Account Identifier	NUMBER (22, 0)	This system generated number identifies the billing account instance.
Warehouse	BILL_ACCT	BILL_ACCT_NAT_KEY	Billing Account Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the billing account.
Warehouse	BILL_ACCT	BILL_ACCT_NUM	Billing Account Number	VARCHAR2(20)	This value represents the number of the account.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_CD_1	Billing Account User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first billing account user defined field.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_CD_2	Billing Account User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second billing account user defined field.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_CD_3	Billing Account User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third billing account user defined field.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_CD_4	Billing Account User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth billing account user defined field.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_CD_5	Billing Account User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth billing account user defined field.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_DESC_1	Billing Account User Defined Field Description 1	VARCHAR2(60)	This value describes the first billing account policy user defined field.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_DESC_2	Billing Account User Defined Field Description 2	VARCHAR2(60)	This value describes the second billing account policy user defined field.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_DESC_3	Billing Account User Defined Field Description 3	VARCHAR2(60)	This value describes the third billing account policy user defined field.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_DESC_4	Billing Account User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth billing account policy user defined field.
Warehouse	BILL_ACCT	BILL_ACCT_UDF_DESC_5	Billing Account User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth billing account policy user defined field.
Warehouse	BILL_ACCT	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the bill account is currently applicable.
Warehouse	BILL_ACCT	END_DT	End Date	DATE	This calendar date represents when the bill account is no longer valid.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	BILL_ACCT	METH_OF_PMT_CD	Method of Payment Code	VARCHAR2(25)	This system code indicates the means by which the payment was/will be made and type of account being credited or debited.g. for premium payment, a credit card may be charged, and for a claim payment , a checking account may be credited).
Warehouse	BILL_ACCT	METH_OF_PMT_DESC	Method of Payment Description	VARCHAR2(60)	This value describes the means by which the payment was/will be made and type of account being credited or debited.g. for premium payment, a credit card may be charged, and for a claim payment, a checking account may be credited).
Warehouse	BILL_ACCT	PMT_PLAN_CD	Payment Plan Code	VARCHAR2(25)	This system code identifies the frequency of premium payment.
Warehouse	BILL_ACCT	PMT_PLAN_DESC	Payment Plan Description	VARCHAR2(60)	This value describes the premium payment plan.
Warehouse	BILL_ACCT	PMT_SVC_CD	Payment Service Code	VARCHAR2(25)	This system code identifies the type of payment service used.
Warehouse	BILL_ACCT	PMT_SVC_DESC	Payment Service Description	VARCHAR2(60)	This value describes the type of payment service used.
Warehouse	CA_DRV	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage.
Warehouse	CA_DRV	CA_DRV_ID	Commercial Auto Driver Identifier	NUMBER (22, 0)	This system generated number identifies the commercial auto driver instance.
Warehouse	CA_DRV	CA_DRV_UDF_CD_1	Commercial Auto Driver User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first commercial auto driver user defined field.
Warehouse	CA_DRV	CA_DRV_UDF_CD_2	Commercial Auto Driver User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second commercial auto driver user defined field.
Warehouse	CA_DRV	CA_DRV_UDF_CD_3	Commercial Auto Driver User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third commercial auto driver user defined field.
Warehouse	CA_DRV	CA_DRV_UDF_CD_4	Commercial Auto Driver User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth commercial auto driver user defined field.
Warehouse	CA_DRV	CA_DRV_UDF_CD_5	Commercial Auto Driver User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth commercial auto driver user defined field.
Warehouse	CA_DRV	CA_DRV_UDF_DESC_1	Commercial Auto Driver User Defined Field Description 1	VARCHAR2(60)	This value describes the first commercial auto driver user defined field.
Warehouse	CA_DRV	CA_DRV_UDF_DESC_2	Commercial Auto Driver User Defined Field Description 2	VARCHAR2(60)	This value describes the second commercial auto driver user defined field.
Warehouse	CA_DRV	CA_DRV_UDF_DESC_3	Commercial Auto Driver User Defined Field Description 3	VARCHAR2(60)	This value describes the third commercial auto driver user defined field.
Warehouse	CA_DRV	CA_DRV_UDF_DESC_4	Commercial Auto Driver User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth commercial auto driver user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CA_DRV	CA_DRV_UDF_DESC_5	Commercial Auto Driver User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth commercial auto driver user defined field.
Warehouse	CA_DRV	CDL_ENDR_CD	Commercial Driver License Endorsement Code	VARCHAR2(25)	This system code identifies the drivers license endorsements granted to commercial driver.
Warehouse	CA_DRV	CDL_ENDR_DESC	Commercial Driver License Endorsement Description	VARCHAR2(60)	This value describes the commercial driver license endorsements granted to a commercial driver.
Warehouse	CA_DRV	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the commercial auto driver is currently included in policy coverage.
Warehouse	CA_DRV	DFEN_DRV_CD	Defensive Driving Code	VARCHAR2(25)	This system code indicates the type of defensive driving course the commercial auto driver completed.
Warehouse	CA_DRV	DFEN_DRV_DESC	Defensive Driving Description	VARCHAR2(60)	This value describes the defensive driving code.
Warehouse	CA_DRV	DFEN_DRV_TRNG_DSCNT_FLG	Defensive Driving Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a defensive driver training discount applies.
Warehouse	CA_DRV	DFEN_DRV_TRNG_DSCNT_PCT	Defensive Driving Training Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when driver training discount applies.
Warehouse	CA_DRV	DRV_ACCID_CNT	Driver Accident Count	NUMBER (22, 0)	This number represents the count of accidents a driver has been charged against his or her driving record.
Warehouse	CA_DRV	DRV_CLASS_CD	Driver Class Code	VARCHAR2(25)	This system code identifies the driver class.
Warehouse	CA_DRV	DRV_CLASS_DESC	Driver Class Description	VARCHAR2(60)	This value describes the driver class.
Warehouse	CA_DRV	DRV_DWI_DUI_VIOLATION_CNT	Driver DWI / DUI Violation Count	NUMBER (22, 0)	This number represents the count of Driving While intoxicated (DWI) and/or Driving Under the influence (DUI) violations charged against the driver's driving record.
Warehouse	CA_DRV	DRV_INTRMDT_VIOLATION_CNT	Driver Intermediate Violation Count	NUMBER (22, 0)	This number represents the count of intermediate violations charged against the driver's driving record.
Warehouse	CA_DRV	DRV_LIC_ISSUED_BY_CD	Driver License Issued By Code	VARCHAR2(25)	This system code indentifies which entity granted driving privileges to driver.
Warehouse	CA_DRV	DRV_LIC_ISSUED_BY_DESC	Driver License Issued By Description	VARCHAR2(60)	This value describes the entity that issued a drivers license.
Warehouse	CA_DRV	DRV_LIC_STATUS_CD	Driver License Status Code	VARCHAR2(25)	This system code indicates the driver license status.
Warehouse	CA_DRV	DRV_LIC_STATUS_DESC	Driver License Status Description	VARCHAR2(60)	This value describes the status of a drivers license.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CA_DRV	DRV_MAJOR_VIOLATION_CNT	Driver Major Violation Count	NUMBER (22, 0)	This number represents the count of major violations charged against the driver's driving record.
Warehouse	CA_DRV	DRV_MINOR_VIOLATION_CNT	Driver Minor Violation Count	NUMBER (22, 0)	This number represents the count of minor violations charged against the driver's driving record.
Warehouse	CA_DRV	DRV_NUM	Driver Number	NUMBER (22, 0)	This number identifies the driver.
Warehouse	CA_DRV	DRV_STATUS_CD	Driver Status Code	VARCHAR2(25)	This system code indicates the driver status.
Warehouse	CA_DRV	DRV_STATUS_DESC	Driver Status Description	VARCHAR2(60)	This value describes the status of a driver.
Warehouse	CA_DRV	DRV_TRNG_DSCNT_FLG	Driver Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not driver training discount applies.
Warehouse	CA_DRV	DRV_TRNG_DSCNT_PCT	Driver Training Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when driver training discount applies.
Warehouse	CA_DRV	DRV_TRNG_FLG	Driver Training Flag	CHAR(1)	This value represents based on the yes/no indicator that identifies whether or not a driver has completed a driver training course.
Warehouse	CA_DRV	DRV_TYP_CD	Driver Type Code	VARCHAR2(25)	This system code describes the driver activities.
Warehouse	CA_DRV	DRV_TYP_DESC	Driver Type Description	VARCHAR2(60)	This value describes driver type.
Warehouse	CA_DRV	END_DT	End Date	DATE	This calendar date represents when the commercial driver is no longer included in policy coverages.
Warehouse	CA_DRV	INSD_DT	Insured Date	DATE	This calendar date represents when insurance coverage began for commercial auto driver.
Warehouse	CA_DRV	LIC_DT	License Date	DATE	This calendar date represents when commercial auto driver was granted a drivers license.
Warehouse	CA_DRV	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	CA_DRV	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person.
Warehouse	CA_DRV	RLAT_TO_APPLICANT_CD	Relationship to Applicant Code	VARCHAR2(25)	This system code identifies the relationship of this individual to the applicant.
Warehouse	CA_DRV	RLAT_TO_APPLICANT_DESC	Relationship to Applicant Code Description	VARCHAR2(60)	This value describes the relationship to applicant code.
Warehouse	CA_VEH	ADDL_EQPT_AMT	Additional Equipment Amount	NUMBER (14, 3)	This number represents the monetary cost of vehicle alterations or aftermarket custom equipment like custom painting, equipment installed to overcome a physical handicap, etc. installed on a commercial vehicle.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CA_VEH	AIRBAG_TYP_CD	Airbag Type Code	VARCHAR2(25)	This system code identifies the attributes of airbag system installed.
Warehouse	CA_VEH	AIRBAG_TYP_DESC	Airbag Type Code Description	VARCHAR2(60)	This value describes the airbag type code.
Warehouse	CA_VEH	ANTI_LOCK_BRAKES_CD	Anti-lock Brake Code	VARCHAR2(25)	This system code identifies the attributes of anti-lock brakes on the commercial vehicle.
Warehouse	CA_VEH	ANTI_LOCK_BRAKES_DESC	Anti-lock Brake Code Description	VARCHAR2(60)	This value describes the anti-lock brake code.
Warehouse	CA_VEH	ANTI_THEFT_DEVICE_CD	Anti-Theft Device Code	VARCHAR2(25)	This system code identifies the attributes of vehicle anti-theft device installed on the commercial vehicle.
Warehouse	CA_VEH	ANTI_THEFT_DEVICE_DESC	Anti-Theft Device Code Description	VARCHAR2(60)	This value describes the anti-theft device code.
Warehouse	CA_VEH	AUTO_STBLTS_DSCNT_FLG	Automatic Seatbelt Type Code	CHAR(1)	This system code identifies the attributes of automatic seatbelt installed.
Warehouse	CA_VEH	AUTO_STBLTS_DSCNT_PCT	Automatic Seatbelt Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when automatic seatbelt discount applies.
Warehouse	CA_VEH	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage.
Warehouse	CA_VEH	CA_VEH_ID	Commercial Auto Vehicle Identifier	NUMBER (22, 0)	This system generated number identifies the commercial vehicle instance.
Warehouse	CA_VEH	CA_VEH_NAT_KEY	Commercial Auto Vehicle Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the commercial vehicle.
Warehouse	CA_VEH	CA_VEH_UDF_CD_1	Commercial Auto Vehicle User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first commercial vehicle user defined field.
Warehouse	CA_VEH	CA_VEH_UDF_CD_2	Commercial Auto Vehicle User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second commercial vehicle user defined field.
Warehouse	CA_VEH	CA_VEH_UDF_CD_3	Commercial Auto Vehicle User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third commercial vehicle user defined field.
Warehouse	CA_VEH	CA_VEH_UDF_CD_4	Commercial Auto Vehicle User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth commercial vehicle user defined field.
Warehouse	CA_VEH	CA_VEH_UDF_CD_5	Commercial Auto Vehicle User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth commercial vehicle user defined field.
Warehouse	CA_VEH	CA_VEH_UDF_DESC_1	Commercial Auto Vehicle User Defined Field Description 1	VARCHAR2(60)	This value describes the first commercial vehicle user defined field.
Warehouse	CA_VEH	CA_VEH_UDF_DESC_2	Commercial Auto Vehicle User Defined Field Description 2	VARCHAR2(60)	This value describes the second commercial vehicle user defined field.
Warehouse	CA_VEH	CA_VEH_UDF_DESC_3	Commercial Auto Vehicle User Defined Field Description 3	VARCHAR2(60)	This value describes the third commercial vehicle user defined field.
Warehouse	CA_VEH	CA_VEH_UDF_DESC_4	Commercial Auto Vehicle User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth commercial vehicle user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CA_VEH	CA_VEH_UDF_DESC_5	Commercial Auto Vehicle User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth commercial vehicle user defined field.
Warehouse	CA_VEH	CELL_PHONE_TYP_CD	Cellular Phone Type Code	VARCHAR2(25)	This system code identifies the cellular phone type present.
Warehouse	CA_VEH	CELL_PHONE_TYP_DESC	Cellular Phone Type Description	VARCHAR2(60)	This value represents the description of the cellular phone type.
Warehouse	CA_VEH	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the commercial vehicle is currently applicable.
Warehouse	CA_VEH	DAYTIME_RUN_LIGHTS_CD	Daytime Running Lights Code	VARCHAR2(25)	This value represents based on the yes/no indicator that states whether or not a commercial vehicle has daytime running headlights.
Warehouse	CA_VEH	DAYTIME_RUN_LIGHTS_DESC	Daytime Running Lights Description	VARCHAR2(60)	This value describes the daytime running headlights of a commercial vehicle.
Warehouse	CA_VEH	END_DT	End Date	DATE	This calendar date represents when the commercial vehicle is no longer included in policy coverages.
Warehouse	CA_VEH	EST_ANNU_DRVG_DIST	Estimated Annual Driving Distance	NUMBER (22, 0)	This number represents the estimated number of distance units (miles/kilometers) a vehicle is driven over a one year period.
Warehouse	CA_VEH	FLEET_FLG	Fleet Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a fleet.
Warehouse	CA_VEH	GAR_CD	Garaging Code	VARCHAR2(25)	This system code identifies where the commercial vehicle is parked at night.
Warehouse	CA_VEH	GAR_DESC	Garaging Description	VARCHAR2(60)	This value describes where a commercial vehicle is parked at night.
Warehouse	CA_VEH	GAR_LOC_ADDR_ID	Garaging Location Address Identifier	NUMBER (22, 0)	This system generated number identifies the garaging location address instance.
Warehouse	CA_VEH	HIRED_FLG	Hired Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of vehicle usage as a hired vehicle.
Warehouse	CA_VEH	HP_DSPLCMNT	Horsepower Displacement	VARCHAR2(5)	This value represents the cubic centimeters or displacement (for example, motorcycles) or horsepower for recreational vehicles.
Warehouse	CA_VEH	INSD_DT	Insured Date	DATE	This calendar date represents when insurance coverage began for commercial vehicle.
Warehouse	CA_VEH	LEASE_DT	Commercial Auto Vehicle Lease Date	DATE	This calendar date represents when a commercial vehicle was leased by insured.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CA_VEH	MSRP	Manufacturer Suggested Retail Price	NUMBER (14, 3)	This number represents the price that the manufacturer tells the vehicle dealer the new vehicle is worth.
Warehouse	CA_VEH	MULT_CAR_DSCNT_FLG	Multiple Car Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a multiple car discount applies.
Warehouse	CA_VEH	MULT_CAR_DSCNT_PCT	Multiple Car Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when a multiple car discount applies.
Warehouse	CA_VEH	NEW_OR_USED_CD	New Or Used Code	VARCHAR2(25)	This system code identifies if the insured is the original owner of the insured vehicle.
Warehouse	CA_VEH	NEW_OR_USED_DESC	New or Used Description	VARCHAR2(60)	This value describes new or used code.
Warehouse	CA_VEH	OWNRSHP_TYP_CD	Ownership Type Code	VARCHAR2(25)	This system code describes the ownership type of a vehicle standard code.
Warehouse	CA_VEH	OWNRSHP_TYP_DESC	Ownership Type Description	VARCHAR2(60)	This value represents the classification that describes how a commercial vehicle is owned and titled.
Warehouse	CA_VEH	PSNL_USE_FLG	Personal Use Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the vehicle usage is personal use.
Warehouse	CA_VEH	PURCH_DT	Purchase Date	DATE	This date represents the calendar date commercial vehicle was purchased by insured.
Warehouse	CA_VEH	PURCH_PRICE	Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when commercial vehicle was purchased.
Warehouse	CA_VEH	RATING_AGE_CD	Rating Age Code	VARCHAR2(25)	This system code represents the rating age used to rate the vehicle, regardless of its actual age.
Warehouse	CA_VEH	RATING_AGE_DESC	Rating Age Description	VARCHAR2(60)	This value describes rating age.
Warehouse	CA_VEH	STATED_AMT	Stated Amount	NUMBER (14, 3)	This number represents the amount used to rate and value a vehicle when a symbol is not available or useful.
Warehouse	CA_VEH	TRAILER_LIQ_CAP	Trailer Liquid Capacity	NUMBER (14, 3)	This number represents the volume capacity of a trailer designed to carry liquids.
Warehouse	CA_VEH	VEH_BODY_TYP_CD	Vehicle Body Type Code	VARCHAR2(25)	This system code describes the attributes of vehicle body for a scheduled commercial vehicle.
Warehouse	CA_VEH	VEH_BODY_TYP_DESC	Vehicle Body Type Description	VARCHAR2(60)	This value represents the description of the vehicle body type.
Warehouse	CA_VEH	VEH_CLASS_CD	Vehicle Class Code	VARCHAR2(25)	This value represents the classification that describes vehicle size and body type.
Warehouse	CA_VEH	VEH_CLASS_DESC	Vehicle Class Description	VARCHAR2(60)	This value describes the vehicle class.
Warehouse	CA_VEH	VEH_COST_NEW	Vehicle Cost New	NUMBER (14, 3)	This number represents the monetary price of vehicle when purchased as a new vehicle.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CA_VEH	VEH_CUR_VAL	Vehicle Current Value	NUMBER (14, 3)	This number represents the current monetary value of listed commercial vehicle in marketplace.
Warehouse	CA_VEH	VEH_GROSS_WT	Vehicle Gross Weight	NUMBER (14, 3)	This number represents the total weight a vehicle is designed to carry and includes the net weight of the vehicle, plus the weight of passengers, fuel, cargo and any additional accessories.
Warehouse	CA_VEH	VEH_MFR	Vehicle Manufacturer	VARCHAR2(20)	This value represents the name of manufacturer that created the commercial vehicle.
Warehouse	CA_VEH	VEH_MODEL	Vehicle Model	VARCHAR2(20)	This value represents the model name assigned by manufacturer of commercial vehicle.
Warehouse	CA_VEH	VEH_NUM	Vehicle Number	NUMBER (22, 0)	This number is the system assigned number that identifies the commercial vehicle.
Warehouse	CA_VEH	VEH_PERF_CD	Vehicle Performance Code	VARCHAR2(25)	This system code identifies the performance level of the vehicle.
Warehouse	CA_VEH	VEH_PERF_DESC	Vehicle Performance Description	VARCHAR2(60)	This value describes the performance level of the vehicle.
Warehouse	CA_VEH	VEH_SYM_CD	Vehicle Symbol Code	VARCHAR2(25)	This system code is a cost symbol that represents a value.
Warehouse	CA_VEH	VEH_SYM_DESC	Vehicle Symbol Description	VARCHAR2(60)	This value describes the commercial vehicle symbol.
Warehouse	CA_VEH	VEH_USE_CD	Vehicle Use Code	VARCHAR2(25)	This system code identifies the primary use of the vehicle.
Warehouse	CA_VEH	VEH_USE_DESC	Vehicle Use Description	VARCHAR2(60)	This value describes the primary use of the vehicle.
Warehouse	CA_VEH	VEH_YR	Vehicle Year	CHAR(4)	This value represents the model year assigned by vehicle manufacturer.
Warehouse	CA_VEH	VIN	Vehicle Identification Number	VARCHAR2(25)	This value represents the vehicle identification number assigned by the manufacturer of the commercial vehicle at risk.
Warehouse	CAT	BEGIN_DT	Begin Date	DATE	This calendar date represents when the catastrophe applies.
Warehouse	CAT	CAT_BEGIN_DT	Catastrophe Begin Date	DATE	This calendar date represents when the catastrophe started.
Warehouse	CAT	CAT_CD	Catastrophe Code	VARCHAR2(25)	This system code identifies a catastrophe. This is the number or other identifier assigned by the company.
Warehouse	CAT	CAT_DESC	Catastrophe Description	VARCHAR2(60)	This value describes a catastrophe. This is the name assigned by the company.
Warehouse	CAT	CAT_END_DT	Catastrophe Ending Date	DATE	This calendar date represents when a catastrophe ended.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CAT	CAT_ID	Catastrophe Identifier	NUMBER (22, 0)	This system generated number identifies the catastrophe instance.
Warehouse	CAT	CAT_NAT_CD	Catastrophe National Code	VARCHAR2(25)	This system code identifies the national catastrophe occurrence.
Warehouse	CAT	CAT_NAT_DESC	Catastrophe National Description	VARCHAR2(60)	This value describes the catastrophe national code.
Warehouse	CAT	CAT_NAT_KEY	Catastrophe Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the catastrophe.
Warehouse	CAT	CAT_SRC_CD	Catastrophe Source Code	VARCHAR2(25)	This system code describes the source of a catastrophe.
Warehouse	CAT	CAT_SRC_DESC	Catastrophe Source Description	VARCHAR2(60)	This value describes the catastrophe source code.
Warehouse	CAT	CAT_STATE_CD	Catastrophe State Code	VARCHAR2(25)	This system code identifies the state where a catastophe occurred.
Warehouse	CAT	CAT_STATE_DESC	Catastrophe State Description	VARCHAR2(60)	This value identifies the state name of the catastrophe state.
Warehouse	CAT	CAT_UDF_CD_1	Catastrophe User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first catastrophe user defined field.
Warehouse	CAT	CAT_UDF_CD_2	Catastrophe User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second catastrophe user defined field.
Warehouse	CAT	CAT_UDF_CD_3	Catastrophe User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third catastrophe user defined field.
Warehouse	CAT	CAT_UDF_CD_4	Catastrophe User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth catastrophe user defined field.
Warehouse	CAT	CAT_UDF_CD_5	Catastrophe User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth catastrophe user defined field.
Warehouse	CAT	CAT_UDF_DESC_1	Catastrophe User Defined Field Description 1	VARCHAR2(60)	This value describes the first catastrophe user defined field.
Warehouse	CAT	CAT_UDF_DESC_2	Catastrophe User Defined Field Description 2	VARCHAR2(60)	This value describes the second catastrophe user defined field.
Warehouse	CAT	CAT_UDF_DESC_3	Catastrophe User Defined Field Description 3	VARCHAR2(60)	This value describes the third catastrophe user defined field.
Warehouse	CAT	CAT_UDF_DESC_4	Catastrophe User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth catastrophe user defined field.
Warehouse	CAT	CAT_UDF_DESC_5	Catastrophe User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth catastrophe user defined field.
Warehouse	CAT	CUR_FLG	Current Flag	CHAR(1)	This value based on the yes/no indicator identifying if the catastophe is currently applicable.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CAT	END_DT	End Date	DATE	This calendar date represents when the catastrophe is no longer valid.
Warehouse	CAT	EXCESS_CAT_CD	Excess Catastrophe Code	VARCHAR2(25)	This system code indicates that a catastrophe loss is in excess of a policyholders' retention.
Warehouse	CAT	EXCESS_CAT_DESC	Excess Catastrophe Description	VARCHAR2(60)	This value describes the code to indicate that a catastrophe loss is in excess of policyholders' retention.
Warehouse	CLASS	BEGIN_DT	Begin Date	DATE	This calendar date represents when the class applies.
Warehouse	CLASS	CLASS_CD	Class Code	VARCHAR2(25)	This system code classifies the subject of insurance.
Warehouse	CLASS	CLASS_DESC	Class Description	VARCHAR2(60)	This value represents the description of the characteristics of a subject of insurance.
Warehouse	CLASS	CLASS_ID	Class Identifier	NUMBER (22, 0)	This system generated number identifies the class.
Warehouse	CLASS	CLASS_NAT_KEY	Class Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the class.
Warehouse	CLASS	CLASS_STATE_CD	Class State Code	VARCHAR2(25)	This system code abbreviates the class state.
Warehouse	CLASS	CLASS_STATE_DESC	Class State Description	VARCHAR2(60)	This value represents the name of the class state.
Warehouse	CLASS	CLASS_UDF_CD_1	Class User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first class user defined field.
Warehouse	CLASS	CLASS_UDF_CD_2	Class User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second class user defined field.
Warehouse	CLASS	CLASS_UDF_CD_3	Class User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third class user defined field.
Warehouse	CLASS	CLASS_UDF_CD_4	Class User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth class user defined field.
Warehouse	CLASS	CLASS_UDF_CD_5	Class User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth class user defined field.
Warehouse	CLASS	CLASS_UDF_DESC_1	Class User Defined Field Description 1	VARCHAR2(60)	This value describes the first class user defined field.
Warehouse	CLASS	CLASS_UDF_DESC_2	Class User Defined Field Description 2	VARCHAR2(60)	This value describes the second class user defined field.
Warehouse	CLASS	CLASS_UDF_DESC_3	Class User Defined Field Description 3	VARCHAR2(60)	This value describes the third class user defined field.
Warehouse	CLASS	CLASS_UDF_DESC_4	Class User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth class user defined field.
Warehouse	CLASS	CLASS_UDF_DESC_5	Class User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth class user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLASS	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the class is currently applicable.
Warehouse	CLASS	END_DT	End Date	DATE	This calendar date represents when the class is no longer valid.
Warehouse	CLASS	PRIM_CLASS_CD	Primary Class Description	VARCHAR2(25)	This value represents the description of the primary class.
Warehouse	CLASS	PRIM_CLASS_DESC	Primary Class Code	VARCHAR2(60)	In a situation where the class code is split into more than one useful breakout, this value represents the primary portion.
Warehouse	CLASS	SCND_CLASS_CD	Second Class Code	VARCHAR2(25)	In a situation where the class code is split into more than one useful breakout, this value represents is the secondary portion.
Warehouse	CLASS	SCND_CLASS_DESC	Second Class Description	VARCHAR2(60)	This value represents the description of the secondary class.
Warehouse	CLM	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim occurred.
Warehouse	CLM	CASE_MADE_RETROACTIVE_DT	Case Made Retroactive Date	DATE	This calendar date represenets when the claim case was made retroactive.
Warehouse	CLM	CASE_MGMT_ASSIGNED_DT	Case Management Assigned Date	DATE	This calendar date represents when claim management is assigned to claim.
Warehouse	CLM	CLM_CLOSED_DT	Claim Closed Date	DATE	This calendar date represents when the insurance company closed the claim.
Warehouse	CLM	CLM_ID	Claim Identifier	NUMBER (22, 0)	This system generated number identifies the claim instance.
Warehouse	CLM	CLM_NAT_KEY	Claim Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claim.
Warehouse	CLM	CLM_NUM	Claim Number	VARCHAR2(30)	This number or other unique identifier identifies a claim.
Warehouse	CLM	CLM_OPENED_DT	Claim Opened Date	DATE	This calendar date represents when a claim was opened by the insurance company.
Warehouse	CLM	CLM_RECLOSED_DT	Claim Re-Closed Date	DATE	This calendar date represents when a claim was re-closed by the insurance company.
Warehouse	CLM	CLM_REOPENED_DT	Claim Re-Opened Date	DATE	This calendar date represents when a closed claim was changed to open status by the insurance company.
Warehouse	CLM	CLM_RPT_BY_CD	Claim Report By Code	VARCHAR2(25)	This system code indicates the claim reported by source.
Warehouse	CLM	CLM_RPT_BY_DESC	Claim Report by Description	VARCHAR2(60)	This value describes the claim reported by entity.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLM	CLM_RPT_CLASS_CD	Claim Report Class Code	VARCHAR2(25)	This system code describes the class code report class applicable to the claim, regardless of the class codes on the policy.
Warehouse	CLM	CLM_RPT_CLASS_DESC	Claim Report Class Description	VARCHAR2(60)	This value describes the class code reported as the one applicable to the claim, regardless of the class codes on the policy.
Warehouse	CLM	CLM_RPT_DT	Claim Report Date	DATE	This calendar date represents when the claim was reported to the insurance carrier.
Warehouse	CLM	CLM_STATUS_CD	Claim Status Code	VARCHAR2(25)	This system code describes the claim status.
Warehouse	CLM	CLM_STATUS_DESC	Claim Status Description	VARCHAR2(60)	This value describes the claim status.
Warehouse	CLM	CLM_UDF_CD_1	Claim User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim user defined field.
Warehouse	CLM	CLM_UDF_CD_2	Claim User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim user defined field.
Warehouse	CLM	CLM_UDF_CD_3	Claim User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim user defined field.
Warehouse	CLM	CLM_UDF_CD_4	Claim User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim user defined field.
Warehouse	CLM	CLM_UDF_CD_5	Claim User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim user defined field.
Warehouse	CLM	CLM_UDF_DESC_1	Claim User Defined Field Description 1	VARCHAR2(60)	This value describes the first claim user defined field.
Warehouse	CLM	CLM_UDF_DESC_2	Claim User Defined Field Description 2	VARCHAR2(60)	This value describes the second claim user defined field.
Warehouse	CLM	CLM_UDF_DESC_3	Claim User Defined Field Description 3	VARCHAR2(60)	This value describes the third claim user defined field.
Warehouse	CLM	CLM_UDF_DESC_4	Claim User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth claim user defined field.
Warehouse	CLM	CLM_UDF_DESC_5	Claim User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth claim user defined field.
Warehouse	CLM	CLMS_MADE_BASIS_CD	Claims Made Basis Code	VARCHAR2(25)	This system code identifies whether or not the claims made basis is being used for reporting of claims.
Warehouse	CLM	CLMS_MADE_BASIS_DESC	Claims Made Basis Description	VARCHAR2(60)	This value describes the yes/no indicator identifying whether or not the claims made basis is being used for reporting of claims.
Warehouse	CLM	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim is currently applicable.
Warehouse	CLM	END_DT	End Date	DATE	This calendar date represents when a loss period ended.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLM	FIRST_CLM_CNTCT_DT	First Claim Contact Date	DATE	This calendar date represents when the claimant was first contacted by the insuring company or its representative.
Warehouse	CLM	FIRST_CLM_PMT_DT	First Claim Payment Date	DATE	This calendar date represents when the first payment was made on a claim.
Warehouse	CLM	FRAUD_CLM_CD	Fraud Claim Code	VARCHAR2(25)	This system code indicates potential fraudulent claim based on adjusters' investigation.
Warehouse	CLM	FRAUD_CLM_DESC	Fraud Claim Description	VARCHAR2(60)	This value represents the description of potential fraudulent claim based on adjusters' investigation.
Warehouse	CLM	LAST_CLM_PMT_DT	Last Claim Payment Date	DATE	This calendar date represents when the last claim payment was issued.
Warehouse	CLM	LAST_SALV_PMT_DT	Last Salvage Payment Date	DATE	This calendar date represents when the last payment was made associated with salvage.
Warehouse	CLM	LAST_SUBRO_PMT_DT	Last Subrogation Payment Date	DATE	This calendar date represents when last subrogation payment was received.
Warehouse	CLM	LOC_OF_LOSS_ADDR_ID	Location Of Loss Address Identifier	NUMBER (22, 0)	This system generated number identifies the loss location instance.
Warehouse	CLM	LOSS_DT	Loss Date	DATE	This calendar date represents when an accident or loss occurred regardless of when the claim was filed.
Warehouse	CLM	NUM_RENTAL_DAYS	Number Of Rental Days	NUMBER (22, 0)	This number represents the count of days a replacement item is rented.
Warehouse	CLM	NUM_REPAIR_DAYS	Number Of Repair Days	NUMBER (22, 0)	This number represents the count of days required to repair an item.
Warehouse	CLM	NUM_STORAGE_DAYS	Number Of Storage Days	NUMBER (22, 0)	This number represents the count of days an item is stored.
Warehouse	CLM_ADJ	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim adjuster begins employment.
Warehouse	CLM_ADJ	CLM_ADJ_ID	Claim Adjuster Identifier	NUMBER (22, 0)	This system generated number identifies the claim adjuster instance.
Warehouse	CLM_ADJ	CLM_ADJ_NUM	Claim Adjuster Number	VARCHAR2(25)	This value represents a number or other identifier for an adjuster.
Warehouse	CLM_ADJ	CLM_ADJ_TYP_CD	Claim Adjuster Type Code	VARCHAR2(25)	This system code identifies the type of adjuster used to support the claim process.
Warehouse	CLM_ADJ	CLM_ADJ_TYP_DESC	Claim Adjuster Type Description	VARCHAR2(60)	This value describes the type of adjuster used to support the claim process.
Warehouse	CLM_ADJ	CLM_ADJ_UDF_CD_1	Claim Adjuster User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim adjuster user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLM_ADJ	CLM_ADJ_UDF_CD_2	Claim Adjuster User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim adjuster user defined field.
Warehouse	CLM_ADJ	CLM_ADJ_UDF_CD_3	Claim Adjuster User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim adjuster user defined field.
Warehouse	CLM_ADJ	CLM_ADJ_UDF_CD_4	Claim Adjuster User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim adjuster user defined field.
Warehouse	CLM_ADJ	CLM_ADJ_UDF_CD_5	Claim Adjuster User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim adjuster user defined field.
Warehouse	CLM_ADJ	CLM_ADJ_UDF_DESC_1	Claim Adjuster User Defined Field Description 1	VARCHAR2(60)	This value describes the first claim adjuster user defined field.
Warehouse	CLM_ADJ	CLM_ADJ_UDF_DESC_2	Claim Adjuster User Defined Field Description 2	VARCHAR2(60)	This value describes the second claim adjuster user defined field.
Warehouse	CLM_ADJ	CLM_ADJ_UDF_DESC_3	Claim Adjuster User Defined Field Description 3	VARCHAR2(60)	This value describes the third claim adjuster user defined field.
Warehouse	CLM_ADJ	CLM_ADJ_UDF_DESC_4	Claim Adjuster User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth claim adjuster user defined field.
Warehouse	CLM_ADJ	CLM_ADJ_UDF_DESC_5	Claim Adjuster User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth claim adjuster user defined field.
Warehouse	CLM_ADJ	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim adjuster is currently applicable.
Warehouse	CLM_ADJ	END_DT	End Date	DATE	This calendar date represents when the claim adjuster is no longer employed.
Warehouse	CLM_ADJ	ORG_ID	Organization Identifier	NUMBER (22, 0)	This system generated number identifies the claim adjuster organization instance.
Warehouse	CLM_ADJ	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	CLM_ADJ	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person.
Warehouse	CLM_EXAMR	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim examiner's employment began.
Warehouse	CLM_EXAMR	CLM_EXAMR_ID	Claim Examiner Identifier	NUMBER (22, 0)	This system generated number identifies the claim examiner instance.
Warehouse	CLM_EXAMR	CLM_EXAMR_NUM	Claim Examiner Number	VARCHAR2(25)	This value represents the number or identifier assigned to the claim examiner.
Warehouse	CLM_EXAMR	CLM_EXAMR_TYP_CD	Claim Examiner Type Code	VARCHAR2(25)	This system code describes the activities of the claim examiner.
Warehouse	CLM_EXAMR	CLM_EXAMR_TYP_DESC	Claim Examiner Type Description	VARCHAR2(60)	This value describes the claim examiner type.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_CD_1	Claim Examiner User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim examiner user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_CD_2	Claim Examiner User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim examiner user defined field.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_CD_3	Claim Examiner User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim examiner user defined field.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_CD_4	Claim Examiner User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim examiner user defined field.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_CD_5	Claim Examiner User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim examiner user defined field.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_DESC_1	Claim Examiner User Defined Field Description 1	VARCHAR2(60)	This value describes the first claim examiner user defined field.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_DESC_2	Claim Examiner User Defined Field Description 2	VARCHAR2(60)	This value describes the second claim examiner user defined field.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_DESC_3	Claim Examiner User Defined Field Description 3	VARCHAR2(60)	This value describes the third claim examiner user defined field.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_DESC_4	Claim Examiner User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth claim examiner user defined field.
Warehouse	CLM_EXAMR	CLM_EXAMR_UDF_DESC_5	Claim Examiner User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth claim examiner user defined field.
Warehouse	CLM_EXAMR	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim examiner is currently applicable.
Warehouse	CLM_EXAMR	END_DT	End Date	DATE	This calendar date represents when the claim examiner's employment ends.
Warehouse	CLM_EXAMR	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	CLM_EXAMR	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person.
Warehouse	CLM_MGR	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim manager's employment began.
Warehouse	CLM_MGR	CLM_MGR_ID	Claim Manager Identifier	NUMBER (22, 0)	This system generated number identifies the claim manager instance.
Warehouse	CLM_MGR	CLM_MGR_NUM	Claim Manager Number	VARCHAR2(25)	This number or other identifiers identifies claim manager.
Warehouse	CLM_MGR	CLM_MGR_TYP_CD	Claim Manager Type Code	VARCHAR2(25)	This system code indicates the claim manager type.
Warehouse	CLM_MGR	CLM_MGR_TYP_DESC	Claim Manager Type Description	VARCHAR2(60)	This value describes the claim manger type.
Warehouse	CLM_MGR	CLM_MGR_UDF_CD_1	Claim Manager User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim manager user defined field.
Warehouse	CLM_MGR	CLM_MGR_UDF_CD_2	Claim Manager User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim manager user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLM_MGR	CLM_MGR_UDF_CD_3	Claim Manager User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim manager user defined field.
Warehouse	CLM_MGR	CLM_MGR_UDF_CD_4	Claim Manager User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim manager user defined field.
Warehouse	CLM_MGR	CLM_MGR_UDF_CD_5	Claim Manager User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim manager user defined field.
Warehouse	CLM_MGR	CLM_MGR_UDF_DESC_1	Claim Manager User Defined Field Description 1	VARCHAR2(60)	This value describes the first claim manager user defined field.
Warehouse	CLM_MGR	CLM_MGR_UDF_DESC_2	Claim Manager User Defined Field Description 2	VARCHAR2(60)	This value describes the second claim manager user defined field.
Warehouse	CLM_MGR	CLM_MGR_UDF_DESC_3	Claim Manager User Defined Field Description 3	VARCHAR2(60)	This value describes the third claim manager user defined field.
Warehouse	CLM_MGR	CLM_MGR_UDF_DESC_4	Claim Manager User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth claim manager user defined field.
Warehouse	CLM_MGR	CLM_MGR_UDF_DESC_5	Claim Manager User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth claim manager user defined field.
Warehouse	CLM_MGR	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim manager is currently applicable.
Warehouse	CLM_MGR	END_DT	End Date	DATE	This calendar date represents when the claim manager's employment ended.
Warehouse	CLM_MGR	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	CLM_MGR	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person instance.
Warehouse	CLM_TRANS	ALLOC_EXPNS_TYP_CD	Allocation Expense Type Code	VARCHAR2(25)	This system code identifies the expense allocation type in the claim transaction.
Warehouse	CLM_TRANS	ALLOC_EXPNS_TYP_DESC	Allocation Expense Type Code Description	VARCHAR2(60)	This value describes the allocation expense type code in the claim transaction.
Warehouse	CLM_TRANS	AVG_EXPNS_RSRV_CD	Average Expense Reserve Code	VARCHAR2(25)	This system code identifies the average reserve set in the claim transaction expenses.
Warehouse	CLM_TRANS	AVG_EXPNS_RSRV_DESC	Average Expense Reserve Code Description	VARCHAR2(60)	This system code identifies if an average reserve was set for expenses in the claim transaction.
Warehouse	CLM_TRANS	AVG_RSRV_CD	Average Reserve Code	VARCHAR2(25)	This system code identifies the average reserve set for a claim transaction.
Warehouse	CLM_TRANS	AVG_RSRV_DESC	Average Reserve Code Description	VARCHAR2(60)	This value describes whether an average reserve was set in the claim transaction.
Warehouse	CLM_TRANS	BILL_ACCT_ID	Billing Account Identifier	NUMBER (22, 0)	This system generated number identifies the billing account instance for claim transaction.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLM_TRANS	BILL_HRLY_RATE	Billable Hourly Rate	NUMBER (6, 5)	This number represents the charge applicable or each hour for a service associated with a claims transaction.
Warehouse	CLM_TRANS	BOOK_DT	Book Date	DATE	This calendar date represents when the claim transaction is recorded into the company's books. Usually, this is the greater of the transaction date or the effective date.
Warehouse	CLM_TRANS	CAT_ID	Catastrophe Identifier	NUMBER (22, 0)	This system generated number identifies the catastrophe in the claim transaction.
Warehouse	CLM_TRANS	CLASS_ID	Class Identifier	NUMBER (22, 0)	This system generated number identifies the class in the claim transaction.
Warehouse	CLM_TRANS	CLM_ID	Claim Identifier	NUMBER (22, 0)	This system generated number identifies the claim instance for claim transaction.
Warehouse	CLM_TRANS	CLM_TRANS_AMT	Claim Transaction Amount	NUMBER (14, 3)	This number represents the actual amount of a claim transaction.
Warehouse	CLM_TRANS	CLM_TRANS_CATG_CD	Claim Transaction Category Code	VARCHAR2(25)	This value represents a way to combine claim transactions into similar categories.
Warehouse	CLM_TRANS	CLM_TRANS_CATG_DESC	Claim Transaction Category Description	VARCHAR2(60)	This value describes the way to combine claim transactions into similar categories.
Warehouse	CLM_TRANS	CLM_TRANS_CD	Claim Transaction Code	VARCHAR2(25)	This system code represents what type of loss activity occurred in the claim transaction.
Warehouse	CLM_TRANS	CLM_TRANS_DESC	Claim Transaction Description	VARCHAR2(60)	This value describes the claim transaction.
Warehouse	CLM_TRANS	CLM_TRANS_ID	Claim Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction instance.
Warehouse	CLM_TRANS	COVRG_ID	Coverage Identifier	NUMBER (22, 0)	This system generated number identifies coverage instance in the claim transaction.
Warehouse	CLM_TRANS	COVRG_STATUS_ID	Coverage Status Identifier	NUMBER (22, 0)	This system generated number identifies coverage status instance in the claim transaction.
Warehouse	CLM_TRANS	DC_ID	Distribution Channel Identifier	NUMBER (22, 0)	This system generated number identifies the distribution channel instance in the claim transaction.
Warehouse	CLM_TRANS	DED_ID	Deductible Identifier	NUMBER (22, 0)	This system generated number identifies the deductible instance in the claim transaction.
Warehouse	CLM_TRANS	DIRECT_CEDED_ASSUMED_CD	Direct or Ceded or Assumed Code	VARCHAR2(25)	This system code identifies the claim transaction type as being direct, ceded, or assumed.
Warehouse	CLM_TRANS	DIRECT_CEDED_ASSUMED_DESC	Direct or Ceded or Assumed Description	VARCHAR2(60)	This value describes a claims transaction to classify if it is direct, ceded or assumed.
Warehouse	CLM_TRANS	DOC_CURR_CD	Document Currency Code	VARCHAR2(25)	This system code identifies document currency for claim transaction.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLM_TRANS	FEAT_ID	Feature Identifier	NUMBER (22, 0)	This system generated number identifies the claim feature instance for claims transaction.
Warehouse	CLM_TRANS	FEAT_STATUS_ID	Feature Status Identifier	NUMBER (22, 0)	This system generated number identifies the claim feature status instance in the claim transaction.
Warehouse	CLM_TRANS	GLOBAL_CURR_RATE_1	Global Currency Rate 1	NUMBER (22, 7)	This number represents the first global currency rate in the claim transaction.
Warehouse	CLM_TRANS	GLOBAL_CURR_RATE_2	Global Currency Rate 2	NUMBER (22, 7)	This number represents the second global currency rate in the claim transaction.
Warehouse	CLM_TRANS	GLOBAL_CURR_RATE_3	Global Currency Rate 3	NUMBER (22, 7)	This number represents the third global currency rate in the claim transaction.
Warehouse	CLM_TRANS	GRP_PRG_ID	Group Program Identifier	NUMBER (22, 0)	This system generated number identifies the group program instance in the claim transaction.
Warehouse	CLM_TRANS	LITG_ID	Litigation Identifier	NUMBER (22, 0)	This system generated number identifies the litigation instance in the claim transaction.
Warehouse	CLM_TRANS	LMT_ID	Limit Identifier	NUMBER (22, 0)	This system generated number identifies the limit instance in the claim transaction.
Warehouse	CLM_TRANS	LOB_ID	Line Of Business Identifier	NUMBER (22, 0)	This system generated number identifies the line of business instance in the claim transaction.
Warehouse	CLM_TRANS	LOCAL_CURR_RATE	Local Currency Rate	NUMBER (22, 7)	This number represents the local currency rate for claim transaction.
Warehouse	CLM_TRANS	NUM_HRS_BILLED	Number Of Hours Billed	NUMBER (22, 0)	This number represents the count of hours billed to a claims transaction.
Warehouse	CLM_TRANS	PLCY_ID	Policy Identifier	NUMBER (22, 0)	This system generated number identifies the policy instance in the claim transaction.
Warehouse	CLM_TRANS	REINS_CNTRCT_ID	Reinsurance Contract Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance contract instance for claim transaction.
Warehouse	CLM_TRANS	SRC_SYS_PROC_DT	Source System Process Date	DATE	This calendar date represents when source system processed the claim transaction.
Warehouse	CLM_TRANS	SYS_CLM_TRANS_CD	System Claim Transaction Code	VARCHAR2(25)	This system code identifies the system claim transaction.
Warehouse	CLM_TRANS	SYS_CLM_TRANS_DESC	System Claim Transaction Description	VARCHAR2(60)	This system code identifies the system claim transaction.
Warehouse	CLM_TRANS	SYS_PROC_DT	System Process Date	DATE	This calendar date represents when the system processed the claim transaction.
Warehouse	CLM_TRANS	TRANS_EFF_DT	Transaction Effective Date	DATE	This calendar date represents when a claims transaction is effective.
Warehouse	CLM_TRANS_TO_CA_VEH	CA_VEH_ID	Commercial Auto Vehicle Identifier	NUMBER (22, 0)	This system generated number identifies the commercial vehicle in the claim transaction to commercial vehicle.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLM_TRANS_TO_CA_VEH	CLM_TRANS_ID	Claim Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction instance in the claim transaction to commercial vehicle.
Warehouse	CLM_TRANS_TO_CP_BLDG	CLM_TRANS_ID	Claim Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction instance in the claim transaction to commercial property building.
Warehouse	CLM_TRANS_TO_CP_BLDG	CP_BLDG_ID	Commercial Property Building Identifier	NUMBER (22, 0)	This system generated number identifies the property instance in the claim transaction to commercial property building.
Warehouse	CLM_TRANS_TO_DF_DWLNG	CLM_TRANS_ID	Claim Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction instance in the claim transaction to dwelling fire dwelling.
Warehouse	CLM_TRANS_TO_DF_DWLNG	DF_DWLNG_ID	Dwelling Fire Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling instance in the claim transaction to dwelling fire dwelling.
Warehouse	CLM_TRANS_TO_HO_DWLNG	CLM_TRANS_ID	Claim Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction instance for claim transaction to homeowners dwelling.
Warehouse	CLM_TRANS_TO_HO_DWLNG	HO_DWLNG_ID	Homeowners Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling instance.
Warehouse	CLM_TRANS_TO_PA_VEH	CLM_TRANS_ID	Claim Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction instance for claim transaction to personal vehicle.
Warehouse	CLM_TRANS_TO_PA_VEH	PA_VEH_ID	Persona Auto Vehicle Identifier	NUMBER (22, 0)	This system generated number identifies the personal vehicle instance in the claim transaction to personal vehicle.
Warehouse	CLM_TRANS_TO_PARTY	CLM_TRANS_ID	Claim Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction instance in the claim transaction to party.
Warehouse	CLM_TRANS_TO_PARTY	PARTY_ID	Party Identifier	NUMBER (22, 0)	This system generated number identifies the party in the claim transaction to party.
Warehouse	CLM_TRANS_TO_PARTY	PARTY_ROLE_ID	Party Role Identifier	NUMBER (22, 0)	This system generated number identifies the party role instance in the claim transaction to party.
Warehouse	CLM_TRANS_TO_PU_PLCY	CLM_TRANS_ID	Claim Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the claim transaction instance in the claim transaction to personal umbrella policy.
Warehouse	CLM_TRANS_TO_PU_PLCY	PU_PLCY_ID	Personal Umbrella Policy Identifier	NUMBER (22, 0)	This system generated number identifies the personal umbrella policy instance in the claim transaction to personal umbrella policy.
Warehouse	CLMT	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claimant applies.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CLMT	CLMT_ID	Claimant Identifier	NUMBER (22, 0)	This system generated number identifies the claimant instance.
Warehouse	CLMT	CLMT_TYP_CD	Claimant Type Code	VARCHAR2(25)	This system code refers to the type of entity making the claim.
Warehouse	CLMT	CLMT_TYP_DESC	Claimant Type Description	VARCHAR2(60)	This value describes the type of entity making the claim.
Warehouse	CLMT	CLMT_UDF_CD_1	Claimant User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claimant user defined field.
Warehouse	CLMT	CLMT_UDF_CD_2	Claimant User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claimant user defined field.
Warehouse	CLMT	CLMT_UDF_CD_3	Claimant User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claimant user defined field.
Warehouse	CLMT	CLMT_UDF_CD_4	Claimant User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claimant user defined field.
Warehouse	CLMT	CLMT_UDF_CD_5	Claimant User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claimant user defined field.
Warehouse	CLMT	CLMT_UDF_DESC_1	Claimant User Defined Field Description 1	VARCHAR2(60)	This value describes the first claimant user defined field.
Warehouse	CLMT	CLMT_UDF_DESC_2	Claimant User Defined Field Description 2	VARCHAR2(60)	This value describes the second claimant user defined field.
Warehouse	CLMT	CLMT_UDF_DESC_3	Claimant User Defined Field Description 3	VARCHAR2(60)	This value describes the third claimant user defined field.
Warehouse	CLMT	CLMT_UDF_DESC_4	Claimant User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth claimant user defined field.
Warehouse	CLMT	CLMT_UDF_DESC_5	Claimant User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth claimant user defined field.
Warehouse	CLMT	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claimant is currently applicable.
Warehouse	CLMT	END_DT	End Date	DATE	This calendar date represents when the claimant is no longer valid.
Warehouse	CLMT	ORG_ID	Organization Identifier	NUMBER (22, 0)	This system generated number identifies the claimant organization instance.
Warehouse	CLMT	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party in the claimant.
Warehouse	CLMT	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person in the claimant.
Warehouse	CNTCT	CNTCT_CD	Contact Code	VARCHAR2(25)	This system code describes the type of contact.
Warehouse	CNTCT	CNTCT_DESC	Contact Description	VARCHAR2(60)	This value describes the contact.
Warehouse	CNTCT	CNTCT_ID	Contact Identifier	NUMBER (22, 0)	This system generated number identifies the contact instance.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CNTCT	CNTCT_NAT_KEY	Contact Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the contact.
Warehouse	CNTCT	CNTCT_TYP_CD	Contact Type Code	VARCHAR2(25)	This system code indicates the contact type.
Warehouse	CNTCT	CNTCT_TYP_DESC	Contact Type Description	VARCHAR2(60)	This value describes the contact type.
Warehouse	CNTCT	CNTCT_UDF_CD_1	Contact User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_CD_2	Contact User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_CD_3	Contact User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_CD_4	Contact User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_CD_5	Contact User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_DESC_1	Contact User Defined Field Description 1	VARCHAR2(60)	This value describes the first contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_DESC_2	Contact User Defined Field Description 2	VARCHAR2(60)	This value describes the second contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_DESC_3	Contact User Defined Field Description 3	VARCHAR2(60)	This value describes the third contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_DESC_4	Contact User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth contact user defined field.
Warehouse	CNTCT	CNTCT_UDF_DESC_5	Contact User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth contact user defined field.
Warehouse	COVRG	ANNU_STMT_LINE_CD	Annual Statement Line Code	VARCHAR2(25)	This system code indicates in which line of the annual statement a transaction belongs.
Warehouse	COVRG	ANNU_STMT_LINE_DESC	Annual Statement Line Code Description	VARCHAR2(60)	This value represents the description that indicates in which line of the annual statement a transaction belongs.
Warehouse	COVRG	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage was initially available.
Warehouse	COVRG	BUREAU_RPT_PLAN_CD	Bureau Report Plan Code	VARCHAR2(25)	This system code indicates the statistical plan code used for bureau reporting.
Warehouse	COVRG	BUREAU_RPT_PLAN_DESC	Bureau Report Plan Code Description	VARCHAR2(60)	This system code indicates the statistical plan code used for bureau reporting.
Warehouse	COVRG	COVRG_CATG_CD	Coverage Category Code	VARCHAR2(25)	This system code indicates the coverage category.
Warehouse	COVRG	COVRG_CATG_DESC	Coverage Category Description	VARCHAR2(60)	This value describes the coverage category.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	COVRG	COVRG_CD	Coverage Code	VARCHAR2(25)	This system code identifies and/or further defines a type of coverage, discount, surcharge or factor being requested or applied It may also identify the type of insured value or coverage requested as part of a commercial property schedule submission.
Warehouse	COVRG	COVRG_DESC	Coverage Description	VARCHAR2(60)	This value describes a single coverage afforded on the insurance policy.
Warehouse	COVRG	COVRG_ID	Coverage Identifier	NUMBER (22, 0)	This system generated number identifies coverage instance.
Warehouse	COVRG	COVRG_NAT_KEY	Coverage Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the coverage.
Warehouse	COVRG	COVRG_PART_CD	Coverage Part Code	VARCHAR2(25)	This system code represents a line of business within a package policy.
Warehouse	COVRG	COVRG_PART_DESC	Coverage Part Description	VARCHAR2(60)	This value describes a line of business within a package policy.
Warehouse	COVRG	COVRG_UDF_CD_1	Coverage User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first coverage user defined field.
Warehouse	COVRG	COVRG_UDF_CD_2	Coverage User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second coverage user defined field.
Warehouse	COVRG	COVRG_UDF_CD_3	Coverage User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third coverage user defined field.
Warehouse	COVRG	COVRG_UDF_CD_4	Coverage User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth coverage user defined field.
Warehouse	COVRG	COVRG_UDF_CD_5	Coverage User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth coverage user defined field.
Warehouse	COVRG	COVRG_UDF_DESC_1	Coverage User Defined Field Description 1	VARCHAR2(60)	This value describes the first coverage user defined field.
Warehouse	COVRG	COVRG_UDF_DESC_2	Coverage User Defined Field Description 2	VARCHAR2(60)	This value describes the second coverage user defined field.
Warehouse	COVRG	COVRG_UDF_DESC_3	Coverage User Defined Field Description 3	VARCHAR2(60)	This value describes the third coverage user defined field.
Warehouse	COVRG	COVRG_UDF_DESC_4	Coverage User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth coverage user defined field.
Warehouse	COVRG	COVRG_UDF_DESC_5	Coverage User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth coverage user defined field.
Warehouse	COVRG	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the coverage is currently available.
Warehouse	COVRG	END_DT	End Date	DATE	This calendar date represents when the coverage is no longer valid.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	COVRG	SCND_COVRG_CD	Second Coverage Code	VARCHAR2(25)	This value represents the client defined code that will further breakdown the type of coverage afforded on the insurance policy.
Warehouse	COVRG	SCND_COVRG_DESC	Second Coverage Description	VARCHAR2(60)	This value represents the client defined code that will further breakdown the type of coverage afforded on the insurance policy.
Warehouse	COVRG	STAT_PLAN_CD	Statistical Plan Code	VARCHAR2(25)	This system code identifies the statistical plan for coverage.
Warehouse	COVRG	STAT_PLAN_DESC	Statistical Plan Description	VARCHAR2(60)	This value describes the statistical plan.
Warehouse	COVRG	SYS_COVRG_PART_CD	System Coverage Part Code	VARCHAR2(25)	This system code represents a system coverage part.
Warehouse	COVRG	SYS_COVRG_PART_DESC	System Coverage Part Description	VARCHAR2(60)	This value describes the system coverage part.
Warehouse	COVRG_STATUS	COVRG_EFF_DT	Coverage Effective Date	DATE	This calender date represents when the policy coverage begins.
Warehouse	COVRG_STATUS	COVRG_EXPR_DT	Coverage Expiration Date	DATE	This calender date represents when the policy coverage ends.
Warehouse	COVRG_STATUS	COVRG_STATUS_ID	Coverage Status Identifier	NUMBER (22, 0)	This system generated number identifies coverage status instance.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_CD_1	Coverage Status User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first coverage status user defined field.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_CD_2	Coverage Status User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second coverage status user defined field.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_CD_3	Coverage Status User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third coverage status user defined field.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_CD_4	Coverage Status User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth coverage status user defined field.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_CD_5	Coverage Status User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth coverage status user defined field.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_DESC_1	Coverage Status User Defined Field Description 1	VARCHAR2(60)	This value describes the first coverage status user defined field.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_DESC_2	Coverage Status User Defined Field Description 2	VARCHAR2(60)	This value describes the second coverage status user defined field.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_DESC_3	Coverage Status User Defined Field Description 3	VARCHAR2(60)	This value describes the third coverage status user defined field.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_DESC_4	Coverage Status User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth coverage status user defined field.
Warehouse	COVRG_STATUS	COVRG_STATUS_UDF_DESC_5	Coverage Status User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth coverage status user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CP_BLDG	ALUMINUM_WIRG_FLG	Aluminum Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of aluminum wiring.
Warehouse	CP_BLDG	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage.
Warehouse	CP_BLDG	BLDG_OCPCY	Building Occupancy	NUMBER (22, 0)	This number represents the type of occupants of the commercial building. For example, owner and tenant occupants.
Warehouse	CP_BLDG	BLDG_USE_CD	Building Use Code	VARCHAR2(25)	This system code indicates the primary use of a commercial building.
Warehouse	CP_BLDG	BLDG_USE_DESC	Building Use Code Description	VARCHAR2(60)	This value describes the business use code.
Warehouse	CP_BLDG	BURGLAR_MONITOR_TYP_CD	Burglar Monitoring Type Code	VARCHAR2(25)	This system code describes presence or absence and attributes of burglar alarm in use at the building.
Warehouse	CP_BLDG	BURGLAR_MONITOR_TYP_DESC	Burglar Monitoring Type Description	VARCHAR2(60)	This value describes the burglar monitoring type.
Warehouse	CP_BLDG	CIRCUIT_BREAKERS_FLG	Circuit Breakers Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of circuit breakers.
Warehouse	CP_BLDG	CONST_TYP_CD	Construction Type Code	VARCHAR2(25)	This system code describes the type of construction materials primarily used for building exterior.
Warehouse	CP_BLDG	CONST_TYP_DESC	Construction Type Description	VARCHAR2(60)	This value describes the primary building exterior construction materials.
Warehouse	CP_BLDG	COPPER_WIRG_FLG	Copper Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of copper wiring.
Warehouse	CP_BLDG	CP_BLDG_ID	Commercial Property Building Identifier	NUMBER (22, 0)	This system generated number identifies the property instance.
Warehouse	CP_BLDG	CP_BLDG_NAT_KEY	Commercial Property Building Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the building.
Warehouse	CP_BLDG	CP_BLDG_UDF_CD_1	Commercial Property Building User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first commercial property building user defined field.
Warehouse	CP_BLDG	CP_BLDG_UDF_CD_2	Commercial Property Building User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second commercial property building user defined field.
Warehouse	CP_BLDG	CP_BLDG_UDF_CD_3	Commercial Property Building User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third commercial property building user defined field.
Warehouse	CP_BLDG	CP_BLDG_UDF_CD_4	Commercial Property Building User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth commercial property building user defined field.
Warehouse	CP_BLDG	CP_BLDG_UDF_CD_5	Commercial Property Building User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth commercial property building user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CP_BLDG	CP_BLDG_UDF_DESC_1	Commercial Property Building User Defined Field Description 1	VARCHAR2(60)	This value describes the first commercial building user defined field.
Warehouse	CP_BLDG	CP_BLDG_UDF_DESC_2	Commercial Property Building User Defined Field Description 2	VARCHAR2(60)	This value describes the second commercial building user defined field.
Warehouse	CP_BLDG	CP_BLDG_UDF_DESC_3	Commercial Property Building User Defined Field Description 3	VARCHAR2(60)	This value describes the third commercial building user defined field.
Warehouse	CP_BLDG	CP_BLDG_UDF_DESC_4	Commercial Property Building User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth commercial building user defined field.
Warehouse	CP_BLDG	CP_BLDG_UDF_DESC_5	Commercial Property Building User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth commercial building user defined field.
Warehouse	CP_BLDG	CTY_LMTS_CD	City Limits Code	VARCHAR2(25)	This system code describes if a building is located within or outside city limit boundary.
Warehouse	CP_BLDG	CTY_LMTS_DESC	City Limits Description	VARCHAR2(60)	This value describes the city limits.
Warehouse	CP_BLDG	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the building is currently applicable.
Warehouse	CP_BLDG	CUR_YR_PROP_INCOME	Current Year Property Income	NUMBER (14, 3)	This number represents the total amount of income from activities at the insured building during the current year.
Warehouse	CP_BLDG	DIST_TO_FIRE_HYDRANT	Distance to Fire Hydrant	NUMBER (14, 3)	This number represents the number of distance units (feet/meters) from building to nearest fire hydrant location.
Warehouse	CP_BLDG	DIST_TO_FIRE_STATION	Distance to Fire Station	NUMBER (14, 3)	This number represents the number of distance units (miles/km) from building to nearest fire station location.
Warehouse	CP_BLDG	BLDG_AREA	Building Area	NUMBER (14, 3)	This number represents the area measurement of floor contained.
Warehouse	CP_BLDG	BLDG_COND_CD	Building Condition Code	VARCHAR2(25)	This system code indicates the building condition.
Warehouse	CP_BLDG	BLDG_COND_DESC	Building Condition Description	VARCHAR2(60)	This value represents the description of the building condition.
Warehouse	CP_BLDG	BLDG_TYP_CD	Building Type Code	VARCHAR2(25)	This system code indicates the building type.
Warehouse	CP_BLDG	BLDG_TYP_DESC	Building Type Description	VARCHAR2(60)	This value describes the building type.
Warehouse	CP_BLDG	ELEC_UPDT_TYP_CD	Electrical Update Type Code	VARCHAR2(25)	This system code indicates changes to electrical system after the building's original construction.
Warehouse	CP_BLDG	ELEC_UPDT_TYP_DESC	Electrical Update Type Description	VARCHAR2(60)	This value describes electrical update type.
Warehouse	CP_BLDG	ELEC_UPDT_YR	Electrical Update Year	CHAR(4)	This value represents the calendar year of the last update to the building electrical system.
Warehouse	CP_BLDG	END_DT	End Date	DATE	This calendar date represents when the building is no longer included in policy coverages.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CP_BLDG	FIRE_DSTRCT_CD	Fire District Code	VARCHAR2(25)	This system code describes the fire department response district assigned to a building location.
Warehouse	CP_BLDG	FIRE_DSTRCT_DESC	Fire District Description	VARCHAR2(60)	This value represents the description of the fire district responsible for building location.
Warehouse	CP_BLDG	FIRE_EXTINGUISHER_FLG	Fire Extinguisher Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fire extinguisher.
Warehouse	CP_BLDG	FIRE_MONITOR_TYP_CD	Fire Monitoring Type Code	VARCHAR2(25)	This system code indicates the type of fire monitoring alarm used at building.
Warehouse	CP_BLDG	FIRE_MONITOR_TYP_DESC	Fire Monitoring Type Description	VARCHAR2(60)	This value describes the fire monitoring type code.
Warehouse	CP_BLDG	FIRE_PROT_CLASS_CD	Fire Protection Class Code	VARCHAR2(25)	This system code describes the fire protection services available at building location.
Warehouse	CP_BLDG	FIRE_PROT_CLASS_DESC	Fire Protection Class Description	VARCHAR2(60)	This value describes the fire monitoring type code.
Warehouse	CP_BLDG	FNDN_TYP_CD	Foundation Type Code	VARCHAR2(25)	This system code indicates the construction method used to construct building foundation.
Warehouse	CP_BLDG	FNDN_TYP_DESC	Foundation Type Description	VARCHAR2(60)	This value describes the construction method used to construct the building foundation.
Warehouse	CP_BLDG	FUSES_FLG	Fuses Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fuses.
Warehouse	CP_BLDG	GAS_UPDT_TYP_CD	Gas Update Type Code	VARCHAR2(25)	This system code indicates changes to gas system after the building's original construction.
Warehouse	CP_BLDG	GAS_UPDT_TYP_DESC	Gas Update Type Description	VARCHAR2(60)	This value describes the gas update type.
Warehouse	CP_BLDG	GAS_UPDT_YR	Gas Update Year	CHAR(4)	This value represents the calendar year of the last update to the building gas system.
Warehouse	CP_BLDG	HEAT_UPDT_TYP_CD	Heating Update Type Code	VARCHAR2(25)	This system code indicates changes to heating system after the building's original construction.
Warehouse	CP_BLDG	HEAT_UPDT_TYP_DESC	Heating Update Type Description	VARCHAR2(60)	This value describes heating update type.
Warehouse	CP_BLDG	HEAT_UPDT_YR	Heating Update Year	CHAR(4)	This value represents the calendar year of the last update to the building heating system.
Warehouse	CP_BLDG	KNOB_TUBE_WIRG_FLG	Knob And Tube Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of knob and tube wiring.
Warehouse	CP_BLDG	LOC_ADDR_ID	Location Address Identifier	NUMBER (22, 0)	This system generated number identifies the location address instance for commercial property building.
Warehouse	CP_BLDG	LOC_NUM	Location Number	NUMBER (22, 0)	This number identifies the location of a building.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CP_BLDG	MKT_VAL	Market Value	NUMBER (14, 3)	This number represents the average price of similar buildings recently sold in same real estate market.
Warehouse	CP_BLDG	NM_OF_OWNER	Name of Owner	VARCHAR2(170)	This value represents the name of the building's owner.
Warehouse	CP_BLDG	NUM_COML_OCCUPANTS	Number Of Commercial Occupants	NUMBER (22, 0)	This number represents the count of all commercial occupants of a building.
Warehouse	CP_BLDG	NUM_ELEC_SYS_AMPS	Number Of Electrical System Amps	NUMBER (22, 0)	This number represents the electrical current capacity of a building's electrical system.
Warehouse	CP_BLDG	NUM_FMLYS	Number Of Families	NUMBER (22, 0)	This number represents the count of individual family units in single commercial building. For example, a duplex would have 2 families.
Warehouse	CP_BLDG	NUM_STORIES	Number Of Stories	NUMBER (22, 0)	This number represents the count of building floor levels.
Warehouse	CP_BLDG	OCPCY_TYP_CD	Occupancy Type Code	VARCHAR2(25)	This system code indicates the type of occupants of the building.
Warehouse	CP_BLDG	OCPCY_TYP_DESC	Occupancy Type Description	VARCHAR2(60)	This value describes the primary occupant type of a building.
Warehouse	CP_BLDG	PLUMBING_UPDT_TYP_CD	Plumbing Update Type Code	VARCHAR2(25)	This system code indicates changes to gas system after the building's original construction.
Warehouse	CP_BLDG	PLUMBING_UPDT_TYP_DESC	Plumbing Update Type Description	VARCHAR2(60)	This value describes the plumbing update type.
Warehouse	CP_BLDG	PLUMBING_UPDT_YR	Plumbing Update Year	CHAR(4)	This value represents the calendar year of the last update to the building's plumbing system.
Warehouse	CP_BLDG	PRIM_HEAT_TYP_CD	Primary Heating Type Code	VARCHAR2(25)	This system code describes the building's primary source of heat.
Warehouse	CP_BLDG	PRIM_HEAT_TYP_DESC	Primary Heating Type Description	VARCHAR2(60)	This value describes the building's primary source of heat.
Warehouse	CP_BLDG	PROP_LOT_SIZE	Property Lot Size	NUMBER (14, 3)	This number represents the area measurement of the land with.
Warehouse	CP_BLDG	PURCH_DT	Purchase Date	DATE	This calendar date represents when the insured purchased the building.
Warehouse	CP_BLDG	PURCH_PRICE	Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when building was purchased.
Warehouse	CP_BLDG	ROOF_MATL_CD	Roofing Material Code	VARCHAR2(25)	This system code identifies the material used to construct the building's roof.
Warehouse	CP_BLDG	ROOF_MATL_DESC	Roofing Material Description	VARCHAR2(60)	This value describes the roof material code.
Warehouse	CP_BLDG	ROOF_UPDT_TYP_CD	Roofing Update Type Code	VARCHAR2(25)	This system code indicates the type or roofing updates made since the building's original construction.
Warehouse	CP_BLDG	ROOF_UPDT_TYP_DESC	Roofing Update Type Description	VARCHAR2(60)	This value describes the roof update type code.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	CP_BLDG	ROOF_UPDT_YR	Roofing Update Year	CHAR(4)	This value represents the calendar year of the last update to the building's roofing materials.
Warehouse	CP_BLDG	SCND_HEAT_TYP_CD	Secondary Heating Type Code	VARCHAR2(25)	This system code describes the building's secondary source of heat.
Warehouse	CP_BLDG	SCND_HEAT_TYP_DESC	Secondary Heating Type Description	VARCHAR2(60)	This value describes the building's secondary source of heat.
Warehouse	CP_BLDG	UNDER_CONST_TYP_CD	Under Construction Type Code	VARCHAR2(25)	This system code indicates active construction activities on the building.
Warehouse	CP_BLDG	UNDER_CONST_TYP_DESC	Under Construction Type Description	VARCHAR2(60)	This value describes the active construction activities.
Warehouse	CP_BLDG	WIRG_UPDT_TYP_CD	Wiring Update Type Code	VARCHAR2(25)	This system code identifies the type of update to wiring system.
Warehouse	CP_BLDG	WIRG_UPDT_TYP_DESC	Wiring Update Type Description	VARCHAR2(60)	This value describes the changes made to wiring system since original construction.
Warehouse	CP_BLDG	WIRG_UPDT_YR	Wiring Update Year	CHAR(4)	This value represents the calendar year of the last update to the building wiring system.
Warehouse	CP_BLDG	YR_BUILT	Year Built	CHAR(4)	This value represents the calendar year that the building was constructed.
Warehouse	DC	BEGIN_DT	Begin Date	DATE	This calendar date represents when the distribution channel applies.
Warehouse	DC	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the distribution channel is currently applicable.
Warehouse	DC	DC_ID	Distribution Channel Identifier	NUMBER (22, 0)	This system generated number identifies the distribution channel instance.
Warehouse	DC	DC_NAT_KEY	Distribution Channel Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the distribution channel.
Warehouse	DC	DC_NM	Distribution Channel Name	VARCHAR2(60)	This value represents distribution channel's name.
Warehouse	DC	DC_NUM	Distribution Channel Number	VARCHAR2(10)	This value represents the number or other identifier assigned to the distribution channel.
Warehouse	DC	DC_TYP_CD	Distribution Channel Type Code	VARCHAR2(25)	This system code identifies the distribution channel type.
Warehouse	DC	DC_TYP_DESC	Distribution Channel Type Description	VARCHAR2(60)	This value describes the distribution channel type.
Warehouse	DC	DC_UDF_CD_1	Distribution Channel User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first distribution channel user defined field.
Warehouse	DC	DC_UDF_CD_2	Distribution Channel User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second distribution channel user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	DC	DC_UDF_CD_3	Distribution Channel User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third distribution channel user defined field.
Warehouse	DC	DC_UDF_CD_4	Distribution Channel User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth distribution channel user defined field.
Warehouse	DC	DC_UDF_CD_5	Distribution Channel User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth distribution channel user defined field.
Warehouse	DC	DC_UDF_DESC_1	Distribution Channel User Defined Field Description 1	VARCHAR2(60)	This value describes the first distribution channel user defined field.
Warehouse	DC	DC_UDF_DESC_2	Distribution Channel User Defined Field Description 2	VARCHAR2(60)	This value describes the second distribution channel user defined field.
Warehouse	DC	DC_UDF_DESC_3	Distribution Channel User Defined Field Description 3	VARCHAR2(60)	This value describes the third distribution channel user defined field.
Warehouse	DC	DC_UDF_DESC_4	Distribution Channel User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth distribution channel user defined field.
Warehouse	DC	DC_UDF_DESC_5	Distribution Channel User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth distribution channel user defined field.
Warehouse	DC	END_DT	End Date	DATE	This calendar date represents when the distribution channel is no longer valid.
Warehouse	DC	TYPICAL_COMM_RATE	Typical Commission Rate	NUMBER (6, 5)	This number represents the rate of commission given to a producer for a sale of a policy unless the commission rate is overridden.
Warehouse	DED	BEGIN_DT	Begin Date	DATE	This calendar date represents when the deductible applies.
Warehouse	DED	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the deductible is currently applicable.
Warehouse	DED	DED	Deductible	VARCHAR2(10)	This value represents the monetary amount of a claim detailed in policy contract as not covered by the insurer for a covered risk loss.
Warehouse	DED	DED_APPLIES_TO_CD	Deductible Applies To Code	VARCHAR2(25)	This system code identifies to what coverage the deductible applies.
Warehouse	DED	DED_APPLIES_TO_DESC	Deductible Applies to Description	VARCHAR2(60)	This value describes to what coverage the deductible applies.
Warehouse	DED	DED_BASIS_CD	Deductible Basis Code	VARCHAR2(25)	This system code represents the basis applied to determine the deductible.
Warehouse	DED	DED_BASIS_DESC	Deductible Basis Description	VARCHAR2(60)	This value describes the basis applied to determine the deductible.
Warehouse	DED	DED_ID	Deductible Identifier	NUMBER (22, 0)	This system generated number identifies the deductible instance.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	DED	DED_NAT_KEY	Deductible Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the deductible.
Warehouse	DED	DED_TYP_CD	Deductible Type Code	VARCHAR2(25)	This system code identifies the type of deductible.
Warehouse	DED	DED_TYP_DESC	Deductible Type Description	VARCHAR2(60)	This value describes the type of deductible.
Warehouse	DED	DED_UDF_CD_1	Deductible User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first deductible user defined field.
Warehouse	DED	DED_UDF_CD_2	Deductible User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second deductible user defined field.
Warehouse	DED	DED_UDF_CD_3	Deductible User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third deductible user defined field.
Warehouse	DED	DED_UDF_CD_4	Deductible User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth deductible user defined field.
Warehouse	DED	DED_UDF_CD_5	Deductible User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth deductible user defined field.
Warehouse	DED	DED_UDF_DESC_1	Deductible User Defined Field Description 1	VARCHAR2(60)	This value describes the first deductible user defined field.
Warehouse	DED	DED_UDF_DESC_2	Deductible User Defined Field Description 2	VARCHAR2(60)	This value describes the second deductible user defined field.
Warehouse	DED	DED_UDF_DESC_3	Deductible User Defined Field Description 3	VARCHAR2(60)	This value describes the third deductible user defined field.
Warehouse	DED	DED_UDF_DESC_4	Deductible User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth deductible user defined field.
Warehouse	DED	DED_UDF_DESC_5	Deductible User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth deductible user defined field.
Warehouse	DED	END_DT	End Date	DATE	This calendar date represents when the deductible is no longer valid.
Warehouse	DF_DWLNG	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage begins for the dwelling.
Warehouse	DF_DWLNG	CIRCUIT_BREAKERS_FLG	Circuit Breakers Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of circuit breakers.
Warehouse	DF_DWLNG	CONST_TYP_CD	Construction Type Code	VARCHAR2(25)	This system code describes the type of construction materials primarily used for dwelling exterior.
Warehouse	DF_DWLNG	CONST_TYP_DESC	Construction Type Description	VARCHAR2(60)	This value describes the primary dwelling exterior construction materials.
Warehouse	DF_DWLNG	CTY_LMTS_CD	City Limits Code	VARCHAR2(25)	This system code describes if a dwelling is located within or outside city limit boundary.
Warehouse	DF_DWLNG	CTY_LMTS_DESC	City Limits Description	VARCHAR2(60)	This value describes the city limits where a dwelling is located.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	DF_DWLNG	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the dwelling is currently included in policy coverages.
Warehouse	DF_DWLNG	DF_DWLNG_ID	Dwelling Fire Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling instance.
Warehouse	DF_DWLNG	DF_DWLNG_NAT_KEY	Dwelling Fire Dwelling Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the dwelling.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_CD_1	Dwelling Fire Dwelling User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_CD_2	Dwelling Fire Dwelling User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_CD_3	Dwelling Fire Dwelling User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_CD_4	Dwelling Fire Dwelling User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_CD_5	Dwelling Fire Dwelling User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_DESC_1	Dwelling Fire Dwelling User Defined Field Description 1	VARCHAR2(60)	This value describes the first dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_DESC_2	Dwelling Fire Dwelling User Defined Field Description 2	VARCHAR2(60)	This value describes the second dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_DESC_3	Dwelling Fire Dwelling User Defined Field Description 3	VARCHAR2(60)	This value describes the third dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_DESC_4	Dwelling Fire Dwelling User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DF_DWLNG_UDF_DESC_5	Dwelling Fire Dwelling User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth dwelling fire dwelling user defined field.
Warehouse	DF_DWLNG	DIST_TO_FIRE_HYDRANT	Distance to Fire Hydrant	NUMBER (14, 3)	This number represents the distance units (feet/meters) from dwelling to nearest fire hydrant location.
Warehouse	DF_DWLNG	DIST_TO_FIRE_STATION	Distance to Fire Station	NUMBER (14, 3)	This number represents the distance units (miles/kilometers) from dwelling to nearest fire station location.
Warehouse	DF_DWLNG	DWLNG_AREA	Dwelling Area	NUMBER (14, 3)	This number represents the area measurement of floor contained.
Warehouse	DF_DWLNG	DWLNG_COND_CD	Dwelling Condition Code	VARCHAR2(25)	This system code indicates the dwelling condition.
Warehouse	DF_DWLNG	DWLNG_COND_DESC	Dwelling Condition Description	VARCHAR2(60)	This value represents the description of the dwelling condition.
Warehouse	DF_DWLNG	DWLNG_TYP_CD	Dwelling Type Code	VARCHAR2(25)	This system code indicates the dwelling type.
Warehouse	DF_DWLNG	DWLNG_TYP_DESC	Dwelling Type Description	VARCHAR2(60)	This value describes the dwelling type.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	DF_DWLNG	ELEC_UPDT_TYP_CD	Electrical Update Type Code	VARCHAR2(25)	This system code indicates changes to electrical system after the dwelling's original construction.
Warehouse	DF_DWLNG	ELEC_UPDT_TYP_DESC	Electrical Update Type Description	VARCHAR2(60)	This value describes electrical update type.
Warehouse	DF_DWLNG	ELEC_UPDT_YR	Electrical Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling electrical system.
Warehouse	DF_DWLNG	END_DT	End Date	DATE	This calendar date represents when the dwelling is no longer included in policy coverages.
Warehouse	DF_DWLNG	FIRE_DSTRCT_CD	Fire District Code	VARCHAR2(25)	This system code describes the fire department response district assigned to a dwelling location.
Warehouse	DF_DWLNG	FIRE_DSTRCT_DESC	Fire District Description	VARCHAR2(60)	This value represents the description of the fire district responsible for dwelling location.
Warehouse	DF_DWLNG	FIRE_PROT_CLASS_CD	Fire Protection Class Code	VARCHAR2(25)	This system code describes the fire protection services available at dwelling location.
Warehouse	DF_DWLNG	FIRE_PROT_CLASS_DESC	Fire Protection Class Description	VARCHAR2(60)	This value describes the fire monitoring type code.
Warehouse	DF_DWLNG	FNDN_TYP_CD	Foundation Type Code	VARCHAR2(25)	This system code indicates the materials used to construct dwelling foundation.
Warehouse	DF_DWLNG	FNDN_TYP_DESC	Foundation Type Description	VARCHAR2(60)	This value describes the construction method used to construct the dwelling foundation.
Warehouse	DF_DWLNG	FUSES_FLG	Fuses Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fuses.
Warehouse	DF_DWLNG	GAS_UPDT_TYP_CD	Gas Update Type Code	VARCHAR2(25)	This system code indicates changes to gas system after the dwelling's original construction.
Warehouse	DF_DWLNG	GAS_UPDT_TYP_DESC	Gas Update Type Description	VARCHAR2(60)	This value describes the gas update type.
Warehouse	DF_DWLNG	GAS_UPDT_YR	Gas Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling gas system.
Warehouse	DF_DWLNG	HEAT_UPDT_TYP_CD	Heating Update Type Code	VARCHAR2(25)	This system code indicates changes to heating system after the dwelling's original construction.
Warehouse	DF_DWLNG	HEAT_UPDT_TYP_DESC	Heating Update Type Description	VARCHAR2(60)	This value describes heating update type.
Warehouse	DF_DWLNG	HEAT_UPDT_YR	Heating Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling heating system.
Warehouse	DF_DWLNG	LOC_ADDR_ID	Location Address Identifier	NUMBER (22, 0)	This system generated number identifies the location address instance for dwelling fire dwelling.
Warehouse	DF_DWLNG	LOC_NUM	Location Number	NUMBER (22, 0)	This number identifies the location of a dwelling.
Warehouse	DF_DWLNG	MINE_SUBSIDENCE_FLG	Mine Subsidence Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of mine subsidence coverage.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	DF_DWLNG	MKT_VAL	Market Value	NUMBER (14, 3)	This number represents the average price of similar dwellings recently sold in same real estate market.
Warehouse	DF_DWLNG	NUM_ELEC_SYS_AMPS	Number Of Electrical System Amps	NUMBER (22, 0)	This number represents the electrical current capacity of electrical system.
Warehouse	DF_DWLNG	NUM_FMLYS	Number Of Families	NUMBER (22, 0)	This number represents the count of individual family units in single dwelling. For example, a duplex would have 2 families.
Warehouse	DF_DWLNG	NUM_OR_RMS	Number Of Rooms	NUMBER (22, 0)	This number represents the count of rooms contained in all units of the dwelling.
Warehouse	DF_DWLNG	NUM_STORIES	Number Of Stories	NUMBER (22, 0)	This number represents the count of building floor levels.
Warehouse	DF_DWLNG	NUM_WKS_RENTED	Number Of Weeks Rented	NUMBER (22, 0)	This number represents the count of weeks dwelling is rented per calendar year.
Warehouse	DF_DWLNG	OCPCY_TYP_CD	Occupancy Type Code	VARCHAR2(25)	This system code indicates the type of occupants of the dwelling.
Warehouse	DF_DWLNG	OCPCY_TYP_DESC	Occupancy Type Description	VARCHAR2(60)	This value describes the primary occupant type of a dwelling.
Warehouse	DF_DWLNG	PLUMBING_UPDT_TYP_CD	Plumbing Update Type Code	VARCHAR2(25)	This system code indicates changes to the plumbing system after the dwelling's original construction.
Warehouse	DF_DWLNG	PLUMBING_UPDT_TYP_DESC	Plumbing Update Type Description	VARCHAR2(60)	This value describes the plumbing update type.
Warehouse	DF_DWLNG	PLUMBING_UPDT_YR	Plumbing Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling plumbing system.
Warehouse	DF_DWLNG	PP_MERCNTL_BLDG_FLG	Personal Property Mercantile Building Flag	CHAR(1)	This value represents based on the yes/no indicator identifying presence or absence of personal property storage in a mercantile building.
Warehouse	DF_DWLNG	PRIM_HEAT_TYP_CD	Primary Heating Type Code	VARCHAR2(25)	This system code describes the primary source of heat for dwelling.
Warehouse	DF_DWLNG	PRIM_HEAT_TYP_DESC	Primary Heating Type Description	VARCHAR2(60)	This value describes the primary source of heat for dwelling.
Warehouse	DF_DWLNG	PURCH_DT	Purchase Date	DATE	This calendar date represents when the insured purchased the dwelling.
Warehouse	DF_DWLNG	PURCH_PRICE	Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when dwelling was purchased.
Warehouse	DF_DWLNG	REPL_COST	Replacement Cost	NUMBER (14, 3)	This number represents the amount it would cost to replace a dwelling at current prices with like materials.
Warehouse	DF_DWLNG	ROOF_MATL_CD	Roofing Material Code	VARCHAR2(25)	This system code identifies the material used to construct the roof.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	DF_DWLNG	ROOF_MATL_DESC	Roofing Material Description	VARCHAR2(60)	This value describes the roof material code.
Warehouse	DF_DWLNG	ROOF_UPDT_TYP_CD	Roofing Update Type Code	VARCHAR2(25)	This system code indicates the type or roofing updates made since the dwelling's original construction.
Warehouse	DF_DWLNG	ROOF_UPDT_TYP_DESC	Roofing Update Type Description	VARCHAR2(60)	This value describes the roof update type code.
Warehouse	DF_DWLNG	ROOF_UPDT_YR	Roofing Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling roofing materials.
Warehouse	DF_DWLNG	SCND_HEAT_TYP_CD	Secondary Heating Type Code	VARCHAR2(25)	This system code describes the secondary source of heat for dwelling.
Warehouse	DF_DWLNG	SCND_HEAT_TYP_DESC	Secondary Heating Type Description	VARCHAR2(60)	This value describes the secondary source of heat for dwelling.
Warehouse	DF_DWLNG	UNDER_CONST_TYP_CD	Under Construction Type Code	VARCHAR2(25)	This system code indicates active construction activities on the dwelling.
Warehouse	DF_DWLNG	UNDER_CONST_TYP_DESC	Under Construction Type Description	VARCHAR2(60)	This value describes the active construction activities.
Warehouse	DF_DWLNG	VACANT_PCT	Vacant Percentage	NUMBER (6, 3)	This number represents the percentage of total dwelling area not currently occupied.
Warehouse	DF_DWLNG	WIRG_UPDT_TYP_CD	Wiring Update Type Code	VARCHAR2(25)	This system code identifies the type of update to wiring system.
Warehouse	DF_DWLNG	WIRG_UPDT_TYP_DESC	Wiring Update Type Description	VARCHAR2(60)	This value describes the changes made to wiring system since original construction.
Warehouse	DF_DWLNG	WIRG_UPDT_YR	Wiring Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling wiring system.
Warehouse	DF_DWLNG	YR_BUILT	Year Built	CHAR(4)	This value represents the calendar year that the dwelling was constructed.
Warehouse	ERND_EXPO_TRANS	ERND_EXPO_AMT	Earned Exposure Amount	NUMBER (14, 3)	This number represents the amount of written exposure that is recognized as earned within a given time period.
Warehouse	ERND_EXPO_TRANS	ERND_EXPO_ID	Earned Exposure Identifier	NUMBER (22, 0)	This system generated number identifies the earned exposure.
Warehouse	ERND_EXPO_TRANS	FISCAL_YR_MTH	Fiscal Year Month	CHAR(6)	This value describes the fiscal year month.
Warehouse	ERND_EXPO_TRANS	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction.
Warehouse	ERND_EXPO_TRANS	SYS_PROC_DT	System Process Date	DATE	This calendar date represents when the system processed the earned exposure transaction.
Warehouse	ERND_EXPO_TRANS	UNERND_EXPO_AMT	Unearned Exposure Amount	NUMBER (14, 3)	This number represents the amount of exposure that is recognized as unearned within a given time period.
Warehouse	ERND_PREM_TRANS	ERND_PREM_AMT	Earned Premium Amount	NUMBER (14, 3)	This number represents the amount of written premium that that is recognized as earned within a given time period.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	ERND_PREM_TRANS	ERND_PREM_TRANS_ID	Earned Premium Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the earned premium transaction instance.
Warehouse	ERND_PREM_TRANS	FISCAL_YR_MTH	Fiscal Year Month	CHAR(6)	This value describes the fiscal year month.
Warehouse	ERND_PREM_TRANS	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction instance in the earned premium transaction.
Warehouse	ERND_PREM_TRANS	SYS_PROC_DT	System Process Date	DATE	This calendar date represents when the system processed the earned premium transaction.
Warehouse	ERND_PREM_TRANS	UNERND_PREM_AMT	Unearned Premium Amount	NUMBER (14, 3)	This number represents the amount of written premium that is recognized as unearned within a given time period.
Warehouse	FEAT	ACCID_INJY_ANLYS_CD	Accident Injury Analysis Code (AIA)	VARCHAR2(25)	This system code summarizes the facts relating to a claim. The code can be used to indicate injuries such as body parts involved, type of injury or disease and cause of condition related to a claim.
Warehouse	FEAT	ACCID_INJY_ANLYS_DESC	Accident Injury Analysis Code Description	VARCHAR2(60)	This system code summarizes the facts relating to a claim. The description can be that identifies injuries such as body parts involved, type of injury or disease and cause of condition related to a claim.
Warehouse	FEAT	ACCID_INJY_ANLYS_SUB_CD	Accident Injury Analysis Sub Code	VARCHAR2(25)	This system code describes the loss in more detail than the accident injury analysis code and further describes such things as the object/ incident involved in the loss (i.e. machinery, wet floor, etc.).
Warehouse	FEAT	ACCID_INJY_ANLYS_SUB_DESC	Accident Injury Analysis Sub Code Description	VARCHAR2(60)	This description identifies the loss in more detail than the accident injury analysis sub code. This description further identifies such things as the object/incident involved in the loss (i.e. machinery, wet floor, etc.).
Warehouse	FEAT	BEGIN_DT	Begin Date	DATE	This calendar date represents when the claim feature applies.
Warehouse	FEAT	CAUSE_OF_LOSS_CD	Cause of Loss Code	VARCHAR2(25)	This system code represents the condition that caused a loss to occur.
Warehouse	FEAT	CAUSE_OF_LOSS_DESC	Cause of Loss Description	VARCHAR2(60)	This value describes the condition that caused a loss to occur.
Warehouse	FEAT	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the claim feature is currently applicable.
Warehouse	FEAT	DSBLY_TYP_CD	Disability Type Code	VARCHAR2(25)	This system code indicates the disability type.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	FEAT	DSBLY_TYP_DESC	Disability Type Description	VARCHAR2(60)	This value describes disability type.
Warehouse	FEAT	END_DT	End Date	DATE	This calendar date represents when the claim feature is no longer valid.
Warehouse	FEAT	FEAT_ID	Feature Identifier	NUMBER (22, 0)	This system generated number identifies the claim feature instance.
Warehouse	FEAT	FEAT_NAT_KEY	Feature Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the claim feature.
Warehouse	FEAT	FEAT_UDF_CD_1	Feature User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim feature user defined field.
Warehouse	FEAT	FEAT_UDF_CD_2	Feature User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim feature user defined field.
Warehouse	FEAT	FEAT_UDF_CD_3	Feature User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim feature user defined field.
Warehouse	FEAT	FEAT_UDF_CD_4	Feature User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim feature user defined field.
Warehouse	FEAT	FEAT_UDF_CD_5	Feature User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim feature user defined field.
Warehouse	FEAT	FEAT_UDF_DESC_1	Feature User Defined Field Description 1	VARCHAR2(60)	This value describes the first claim feature user defined field.
Warehouse	FEAT	FEAT_UDF_DESC_2	Feature User Defined Field Description 2	VARCHAR2(60)	This value describes the second claim feature user defined field.
Warehouse	FEAT	FEAT_UDF_DESC_3	Feature User Defined Field Description 3	VARCHAR2(60)	This value describes the third claim feature user defined field.
Warehouse	FEAT	FEAT_UDF_DESC_4	Feature User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth claim feature user defined field.
Warehouse	FEAT	FEAT_UDF_DESC_5	Feature User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth claim feature user defined field.
Warehouse	FEAT	INJURED_BODY_PART_CD	Injured Body Part Code	VARCHAR2(25)	This system code represents an anatomical part of the insured body.
Warehouse	FEAT	INJURED_BODY_PART_DESC	Injured Body Part Description	VARCHAR2(60)	This value describes an anatomical part of the insured body.
Warehouse	FEAT	TYP_OF_LOSS_CD	Type of Loss Code	VARCHAR2(25)	This is the CSP type of loss code It includes the loss location and the loss cause.
Warehouse	FEAT	TYP_OF_LOSS_DESC	Type of Loss Description	VARCHAR2(60)	This is the CSP type of loss code It includes the loss location and the loss cause.
Warehouse	FEAT_STATUS	FEAT_CLOSED_DT	Feature Closed Date	DATE	This calendar date represents when the claim feature, defined as a subset of a claim occurrence, was closed.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	FEAT_STATUS	FEAT_OPENED_DT	Feature Opened Date	DATE	This calendar date represents when the claim feature, defined as a subset of a claim occurrence, was opened.
Warehouse	FEAT_STATUS	FEAT_RECLOSED_DT	Feature Re-closed Date	DATE	This date represents the calendar date the claim feature was closed after original closing.
Warehouse	FEAT_STATUS	FEAT_REOPENED_DT	Feature Re-Opened Date	DATE	This calendar date represents when the claim feature was opened after previous closing.
Warehouse	FEAT_STATUS	FEAT_STATUS_CD	Feature Status Code	VARCHAR2(25)	This system code identifies the current condition of the claim feature, defined as a subset of a claim occurrence.
Warehouse	FEAT_STATUS	FEAT_STATUS_DESC	Feature Status Description	VARCHAR2(60)	This value describes the current condition of the claim feature, defined as a subset of a claim.
Warehouse	FEAT_STATUS	FEAT_STATUS_ID	Feature Status Identifier	NUMBER (22, 0)	This system generated number identifies the feature status instance.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_CD_1	Feature Status User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_CD_2	Feature Status User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_CD_3	Feature Status User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_CD_4	Feature Status User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_CD_5	Feature Status User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_DESC_1	Feature Status User Defined Field Description 1	VARCHAR2(60)	This value describes the first claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_DESC_2	Feature Status User Defined Field Description 2	VARCHAR2(60)	This value describes the second claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_DESC_3	Feature Status User Defined Field Description 3	VARCHAR2(60)	This value describes the third claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_DESC_4	Feature Status User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth claim feature status user defined field.
Warehouse	FEAT_STATUS	FEAT_STATUS_UDF_DESC_5	Feature Status User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth claim feature status user defined field.
Warehouse	GEOG_BNDRY	CNTY_CD	County Code	VARCHAR2(25)	This system code describes a county.
Warehouse	GEOG_BNDRY	CNTY_DESC	County Description	VARCHAR2(60)	This value identifies the county where the geographic boundary exists.
Warehouse	GEOG_BNDRY	CTRY_CD	Country Code	VARCHAR2(25)	This value identifies the country code of the geographic boundary.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	GEOG_BNDRY	CTRY_DESC	Country Description	VARCHAR2(60)	This value identifies the country where the geographic boundary is established.
Warehouse	GEOG_BNDRY	CTY	City	VARCHAR2(32)	This value identifies the city in the geographic boundary.
Warehouse	GEOG_BNDRY	DSTRCT_CD	District Code	VARCHAR2(25)	This system code identifies the company-defined district.
Warehouse	GEOG_BNDRY	DSTRCT_DESC	District Description	VARCHAR2(60)	This value describes the company-defined district for geographic boundary category.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_ID	Geographic Boundary Identifier	NUMBER (22, 0)	This system generated number identifies the geographic boundary instance.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_CD_1	Geographic Boundary User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first geographic boundary user defined field.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_CD_2	Geographic Boundary User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second geographic boundary user defined field.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_CD_3	Geographic Boundary User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third geographic boundary user defined field.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_CD_4	Geographic Boundary User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth geographic boundary user defined field.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_CD_5	Geographic Boundary User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth geographic boundary user defined field.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_DESC_1	Geographic Boundary User Defined Field Description 1	VARCHAR2(60)	This value describes the first geographic boundary user defined field.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_DESC_2	Geographic Boundary User Defined Field Description 2	VARCHAR2(60)	This value describes the second geographic boundary user defined field.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_DESC_3	Geographic Boundary User Defined Field Description 3	VARCHAR2(60)	This value describes the third geographic boundary user defined field.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_DESC_4	Geographic Boundary User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth geographic boundary user defined field.
Warehouse	GEOG_BNDRY	GEOG_BNDRY_UDF_DESC_5	Geographic Boundary User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth geographic boundary user defined field.
Warehouse	GEOG_BNDRY	LATITUDE	Latitude	VARCHAR2(11)	This value represents the latitude location of the geographic boundary.
Warehouse	GEOG_BNDRY	LONGITUDE	Longitude	VARCHAR2(11)	This value represents the longitude location for the geographic boundary.
Warehouse	GEOG_BNDRY	PSTL_CD	Postal Code	VARCHAR2(11)	This value represents the full postal zip code as defined by company specifications.
Warehouse	GEOG_BNDRY	PSTL_CD_PRFX	Postal Code Prefix	VARCHAR2(3)	This value represents the first 3 digits of a 5 digit geopolitical zip code.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	GEOG_BNDRY	PSTL_SUB_CD	Postal Sub Code	VARCHAR2(4)	This value represents the ending digits of postal code that identifies a smaller area of the total area served by a postal code.
Warehouse	GEOG_BNDRY	REGION_CD	Region Code	VARCHAR2(25)	This system code identifies the geographic region as defined by company specifications.
Warehouse	GEOG_BNDRY	REGION_DESC	Region Description	VARCHAR2(60)	This value describes the company-defined geographic boundary.
Warehouse	GEOG_BNDRY	STATE_CD	State Code	VARCHAR2(25)	This system code identifies the state where the geographic boundary is established.
Warehouse	GEOG_BNDRY	STATE_DESC	State Description	VARCHAR2(60)	This value represents the name of the state where the geographic boundary is established.
Warehouse	GEOG_BNDRY	TAX_LOC_ID	Tax Location Identifier	VARCHAR2(6)	This system code identifies company-defined areas for tax purposes.
Warehouse	GEOG_BNDRY	TERR_CD	Territory Code	VARCHAR2(25)	This system code identifies the company-defined territory.
Warehouse	GEOG_BNDRY	TERR_DESC	Territory Description	VARCHAR2(60)	This value represents the description of territory located in geographic boundary.
Warehouse	GRP_PRG	ANNIVERSARY_DT	Anniversary Date	DATE	This calendar date represents the annual anniversary of a program or association. Often, it is the calendar date of the dividend declaration.
Warehouse	GRP_PRG	BEGIN_DT	Begin Date	DATE	This calendar date represents when the group program applies.
Warehouse	GRP_PRG	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the group program is currently applicable.
Warehouse	GRP_PRG	DIVIDEND_DT	dividend Date	DATE	This calendar date represents when the dividend applies to a program or association.
Warehouse	GRP_PRG	DIVIDEND_PLAN_CD	Dividend Plan Code	VARCHAR2(25)	This system code identifies the type of dividend plan offered by the company.
Warehouse	GRP_PRG	DIVIDEND_PLAN_DESC	Dividend Plan Description	VARCHAR2(60)	This value describes the type of dividend plan offered by the company.
Warehouse	GRP_PRG	END_DT	End Date	DATE	This calendar date represents when the group program is no longer valid.
Warehouse	GRP_PRG	GRP_PRG_CD	Group Program Code	VARCHAR2(25)	This system code represents the program that a group of policies are associated with.
Warehouse	GRP_PRG	GRP_PRG_DESC	Group Program Description	VARCHAR2(60)	This value represents the name of the program, other than state or national, that a group of policies are associated with.
Warehouse	GRP_PRG	GRP_PRG_ID	Group Program Identifier	NUMBER (22, 0)	This system generated number identifies the group program instance.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	GRP_PRG	GRP_PRG_NAT_CD	Group Program National Code	VARCHAR2(25)	This system code represents the national program with which a group of policies are associated.
Warehouse	GRP_PRG	GRP_PRG_NAT_DESC	Group Program National Description	VARCHAR2(60)	This value represents the name of the national program that a group of policies are associated with.
Warehouse	GRP_PRG	GRP_PRG_NAT_KEY	Group Program Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the group program.
Warehouse	GRP_PRG	GRP_PRG_STATE_CD	Group Program State Code	VARCHAR2(25)	This system code represents the state program with which a group of policies is associated.
Warehouse	GRP_PRG	GRP_PRG_STATE_DESC	Group Program State Description	VARCHAR2(60)	This value represents the name of the state with which a group of policies is associated.
Warehouse	GRP_PRG	GRP_PRG_STATUS_CD	Group Program Status Code	VARCHAR2(25)	This system code represents the current condition of a program with which a group of policies is associated.
Warehouse	GRP_PRG	GRP_PRG_STATUS_DESC	Group Program Status Description	VARCHAR2(60)	This value describes the current condition of a program with which a group of policies is associated.
Warehouse	GRP_PRG	GRP_PRG_TYP_CD	Group Program Type Code	VARCHAR2(25)	This system code describes the type of program that is represented.
Warehouse	GRP_PRG	GRP_PRG_TYP_DESC	Group Program Type Description	VARCHAR2(60)	This value describes the type of program that is represented.
Warehouse	GRP_PRG	GRP_PRG_UDF_CD_1	Group Program User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first group program user defined field.
Warehouse	GRP_PRG	GRP_PRG_UDF_CD_2	Group Program User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second group program user defined field.
Warehouse	GRP_PRG	GRP_PRG_UDF_CD_3	Group Program User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third group program user defined field.
Warehouse	GRP_PRG	GRP_PRG_UDF_CD_4	Group Program User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth group program user defined field.
Warehouse	GRP_PRG	GRP_PRG_UDF_CD_5	Group Program User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth group program user defined field.
Warehouse	GRP_PRG	GRP_PRG_UDF_DESC_1	Group Program User Defined Field Description 1	VARCHAR2(60)	This value describes the first group program user defined field.
Warehouse	GRP_PRG	GRP_PRG_UDF_DESC_2	Group Program User Defined Field Description 2	VARCHAR2(60)	This value describes the second group program user defined field.
Warehouse	GRP_PRG	GRP_PRG_UDF_DESC_3	Group Program User Defined Field Description 3	VARCHAR2(60)	This value describes the third group program user defined field.
Warehouse	GRP_PRG	GRP_PRG_UDF_DESC_4	Group Program User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth group program user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	GRP_PRG	GRP_PRG_UDF_DESC_5	Group Program User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth group program user defined field.
Warehouse	GRP_PRG	MBR_CNT	Member Count	NUMBER (22, 0)	This number represents the count of members in a group or program.
Warehouse	GRP_PRG	ORIG_DT	Original Date	DATE	This calendar date describes the date a group program was applicable.
Warehouse	HO_DWLNG	ALUMINUM_WIRG_FLG	Aluminum Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of aluminum wiring.
Warehouse	HO_DWLNG	ATTACHED_GAR_FLG	Attached Garage Indicator	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a garage that is attached to the dwelling.
Warehouse	HO_DWLNG	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage in the dwelling begins.
Warehouse	HO_DWLNG	BSMT_AREA	Basement Area	NUMBER (14, 3)	This number represents the total area measurement of all the basements in this dwelling.
Warehouse	HO_DWLNG	BURGLAR_MONITOR_TYP_CD	Burglar Monitoring Type Code	VARCHAR2(25)	This system code describes presence or absence and attributes of burglar alarm in use at the dwelling.
Warehouse	HO_DWLNG	BURGLAR_MONITOR_TYP_DESC	Burglar Monitoring Type Description	VARCHAR2(60)	This value describes the burglar monitoring type.
Warehouse	HO_DWLNG	CARPORT_FLG	Carport Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a carport.
Warehouse	HO_DWLNG	CIRCUIT_BREAKERS_FLG	Circuit Breakers Flag	CHAR(1)	This value represents the yes/no indicator identifying the presence or absence of circuit breakers.
Warehouse	HO_DWLNG	CONST_TYP_CD	Construction Type Code	VARCHAR2(25)	This system code describes the type of construction materials primarily used for dwelling exterior.
Warehouse	HO_DWLNG	CONST_TYP_DESC	Construction Type Description	VARCHAR2(60)	This value describes the primary dwelling exterior construction materials.
Warehouse	HO_DWLNG	COPPER_WIRG_FLG	Copper Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of copper wiring.
Warehouse	HO_DWLNG	CTY_LMTS_CD	City Limits Code	VARCHAR2(25)	This system code describes if a dwelling is located within or outside city limit boundary.
Warehouse	HO_DWLNG	CTY_LMTS_DESC	City Limits Description	VARCHAR2(60)	This value describes the city limits of the dwelling's location.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	HO_DWLNG	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the dwelling is currently applicable.
Warehouse	HO_DWLNG	DIST_TO_FIRE_HYDRANT	Distance to Fire Hydrant	NUMBER (14, 3)	This number represents the distance units (feet/meters) from dwelling to nearest fire hydrant location.
Warehouse	HO_DWLNG	DIST_TO_FIRE_STATION	Distance to Fire Station	NUMBER (14, 3)	This number represents the distance units (miles/kilometers) from dwelling to nearest fire station location
Warehouse	HO_DWLNG	DWLNG_AREA	Dwelling Area	NUMBER (14, 3)	This number represents the area measurement of floor contained in the dwelling.
Warehouse	HO_DWLNG	DWLNG_COND_CD	Dwelling Condition Code	VARCHAR2(25)	This system code indicates the dwelling condition.
Warehouse	HO_DWLNG	DWLNG_COND_DESC	Dwelling Condition Description	VARCHAR2(60)	This value represents the description of the dwelling condition.
Warehouse	HO_DWLNG	DWLNG_TYP_CD	Dwelling Type Code	VARCHAR2(25)	This system code indicates the dwelling type.
Warehouse	HO_DWLNG	DWLNG_TYP_DESC	Dwelling Type Description	VARCHAR2(60)	This value describes the dwelling type.
Warehouse	HO_DWLNG	ELEC_UPDT_TYP_CD	Electrical Update Type Code	VARCHAR2(25)	This system code indicates changes to electrical system after the dwelling's original construction.
Warehouse	HO_DWLNG	ELEC_UPDT_TYP_DESC	Electrical Update Type Description	VARCHAR2(60)	This value describes electrical update type.
Warehouse	HO_DWLNG	ELEC_UPDT_YR	Electrical Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling electrical system.
Warehouse	HO_DWLNG	ENCLOSED_GAR_FLG	Enclosed Garage Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of enclosed garage.
Warehouse	HO_DWLNG	END_DT	End Date	DATE	This calendar date represents when the dwelling is no longer included in policy coverages.
Warehouse	HO_DWLNG	EXT_PAINT_UPDT_YR	Exterior Paint Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling exterior paint.
Warehouse	HO_DWLNG	FARMING_FLG	Farming Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of farming activities occurring on insured premises.
Warehouse	HO_DWLNG	FIRE_DSTRCT_CD	Fire District Code	VARCHAR2(25)	This system code describes the fire department response district assigned to a dwelling location.
Warehouse	HO_DWLNG	FIRE_DSTRCT_DESC	Fire District Description	VARCHAR2(60)	This value represents the description of the fire district responsible for dwelling location.
Warehouse	HO_DWLNG	FIRE_EXTINGUISHER_FLG	Fire Extinguisher Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fire extinguisher.
Warehouse	HO_DWLNG	FIRE_MONITOR_TYP_CD	Fire Monitoring Type Code	VARCHAR2(25)	This system code indicates the type of fire monitoring alarm used at dwelling.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	HO_DWLNG	FIRE_MONITOR_TYP_DESC	Fire Monitoring Type Description	VARCHAR2(60)	This value describes the fire monitoring type code.
Warehouse	HO_DWLNG	FIRE_PROT_CLASS_CD	Fire Protection Class Code	VARCHAR2(25)	This system code describes the fire protection services available at dwelling location.
Warehouse	HO_DWLNG	FIRE_PROT_CLASS_DESC	Fire Protection Class Description	VARCHAR2(60)	This value describes the responding fire protection service available at dwelling location.
Warehouse	HO_DWLNG	FNDN_TYP_CD	Foundation Type Code	VARCHAR2(25)	This system code indicates the construction method used to construct dwelling foundation.
Warehouse	HO_DWLNG	FNDN_TYP_DESC	Foundation Type Description	VARCHAR2(60)	This value describes the construction method used to construct the dwelling foundation.
Warehouse	HO_DWLNG	FUSES_FLG	Fuses Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of fuses.
Warehouse	HO_DWLNG	GAS_UPDT_TYP_CD	Gas Update Type Code	VARCHAR2(25)	This system code indicates changes to gas system after the dwelling's original construction.
Warehouse	HO_DWLNG	GAS_UPDT_TYP_DESC	Gas Update Type Description	VARCHAR2(60)	This value describes the gas update type.
Warehouse	HO_DWLNG	GAS_UPDT_YR	Gas Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling gas system.
Warehouse	HO_DWLNG	HEAT_UPDT_TYP_CD	Heating Update Type Code	VARCHAR2(25)	This system code indicates changes to heating system after the dwelling's original construction.
Warehouse	HO_DWLNG	HEAT_UPDT_TYP_DESC	Heating Update Type Description	VARCHAR2(60)	This value describes heating update type.
Warehouse	HO_DWLNG	HEAT_UPDT_YR	Heating Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling heating system.
Warehouse	HO_DWLNG	HO_DWLNG_ID	Homeowners Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling instance.
Warehouse	HO_DWLNG	HO_DWLNG_NAT_KEY	Homeowners Dwelling Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the dwelling.
Warehouse	HO_DWLNG	HO_DWLNG_UDF_CD_1	Homeowners Dwelling User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first homeowners dwelling user defined field.
Warehouse	HO_DWLNG	HO_DWLNG_UDF_CD_2	Homeowners Dwelling User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second homeowners dwelling user defined field.
Warehouse	HO_DWLNG	HO_DWLNG_UDF_CD_3	Homeowners Dwelling User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third homeowners dwelling user defined field.
Warehouse	HO_DWLNG	HO_DWLNG_UDF_CD_4	Homeowners Dwelling User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth homeowners dwelling user defined field.
Warehouse	HO_DWLNG	HO_DWLNG_UDF_CD_5	Homeowners Dwelling User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth homeowners dwelling user defined field.
Warehouse	HO_DWLNG	HO_DWLNG_UDF_DESC_1	Homeowners Dwelling User Defined Field Description 1	VARCHAR2(60)	This value describes the first homeowners dwelling user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	HO_DWLNG	HO_DWLNG_UDF_DESC_2	Homeowners Dwelling User Defined Field Description 2	VARCHAR2(60)	This value describes the second homeowners dwelling user defined field.
Warehouse	HO_DWLNG	HO_DWLNG_UDF_DESC_3	Homeowners Dwelling User Defined Field Description 3	VARCHAR2(60)	This value describes the third homeowners dwelling user defined field.
Warehouse	HO_DWLNG	HO_DWLNG_UDF_DESC_4	Homeowners Dwelling User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth homeowners dwelling user defined field.
Warehouse	HO_DWLNG	HO_DWLNG_UDF_DESC_5	Homeowners Dwelling User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth homeowners dwelling user defined field.
Warehouse	HO_DWLNG	HURCN_RST_GLASS_FLG	Hurricane Resistant Glass Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of hurricane resistant glass.
Warehouse	HO_DWLNG	KNOB_TUBE_WIRG_FLG	Knob And Tube Wiring Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of knob and tube wiring.
Warehouse	HO_DWLNG	LOC_ADDR_ID	Location Address Identifier	NUMBER (22, 0)	This system generated number identifies the location address instance.
Warehouse	HO_DWLNG	LOC_NUM	Location Number	NUMBER (22, 0)	This number identifies the location of a dwelling.
Warehouse	HO_DWLNG	MKT_VAL	Market Value	NUMBER (14, 3)	This number represents the average price of similar dwellings recently sold in same real estate market.
Warehouse	HO_DWLNG	NUM_CHIMNEYS	Number Of Chimneys	NUMBER (22, 0)	This number represents the count of chimneys in all units of a dwelling.
Warehouse	HO_DWLNG	NUM_ELEC_SYS_AMPS	Number Of Electrical System Amps	NUMBER (22, 0)	This number represents the electrical current capacity of electrical system.
Warehouse	HO_DWLNG	NUM_FMLYS	Number Of Families	NUMBER (22, 0)	This number represents the count of individual family units in single dwelling. For example, a duplex would have 2 families.
Warehouse	HO_DWLNG	NUM_HEARTHS	Number Of Hearths	NUMBER (22, 0)	This number represents the count of individual fireplace hearths in all units of a dwelling.
Warehouse	HO_DWLNG	NUM_OR_RMS	Number Of Rooms	NUMBER (22, 0)	This number represents the count of Rooms contained in all units of the dwelling.
Warehouse	HO_DWLNG	NUM_PRE_FAB_FPS	Number Of Pre-Fabricated Fireplaces	NUMBER (22, 0)	This number represents the count of pre-fabricated fireplaces contained in all units of the dwelling.
Warehouse	HO_DWLNG	NUM_RSDTS	Number Of Residents	NUMBER (22, 0)	This number represents the count of residents in all units of a dwelling.
Warehouse	HO_DWLNG	NUM_STORIES	Number Of Stories	NUMBER (22, 0)	This number represents the count of building floor levels.
Warehouse	HO_DWLNG	NUM_WOOD_STOVE_ISRTS	Number Of Wood Stove Inserts	NUMBER (22, 0)	This number represents the count of wood stove inserts contained in all units of the dwelling.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	HO_DWLNG	OCPCY_TYP_CD	Occupancy Type Code	VARCHAR2(25)	This system code indicates the type of occupants of the dwelling.
Warehouse	HO_DWLNG	OCPCY_TYP_DESC	Occupancy Type Description	VARCHAR2(60)	This value describes the primary occupant type of a dwelling.
Warehouse	HO_DWLNG	PLUMBING_UPDT_TYP_CD	Plumbing Update Type Code	VARCHAR2(25)	This system code indicates changes to plumbing system after the dwelling's original construction.
Warehouse	HO_DWLNG	PLUMBING_UPDT_TYP_DESC	Plumbing Update Type Description	VARCHAR2(60)	This value describes the plumbing update type.
Warehouse	HO_DWLNG	PLUMBING_UPDT_YR	Plumbing Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling plumbing system.
Warehouse	HO_DWLNG	PRIM_HEAT_TYP_CD	Primary Heating Type Code	VARCHAR2(25)	This system code describes the primary source of heat for dwelling.
Warehouse	HO_DWLNG	PRIM_HEAT_TYP_DESC	Primary Heating Type Description	VARCHAR2(60)	This value describes the primary source of heat for dwelling.
Warehouse	HO_DWLNG	PROP_LOT_SIZE	Property Lot Size	NUMBER (14, 3)	This number represents the area measurement of the land within the property lot boundaries.
Warehouse	HO_DWLNG	PURCH_DT	Purchase Date	DATE	This calendar date represents when the insured purchased the dwelling.
Warehouse	HO_DWLNG	PURCH_PRICE	Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when dwelling was purchased.
Warehouse	HO_DWLNG	REPL_COST	Replacement Cost	NUMBER (14, 3)	This number represents the amount it would cost to replace a dwelling at current prices with like materials.
Warehouse	HO_DWLNG	ROOF_IMPACT_RATING_CD	RoofingImpact Rating Code	VARCHAR2(25)	This system code describes the level of hail impact a roof material can withstand.
Warehouse	HO_DWLNG	ROOF_IMPACT_RATING_DESC	RoofingImpact Rating Description	VARCHAR2(60)	This value represents the description that describes the size of hail a roof material is manufactured to withstand.
Warehouse	HO_DWLNG	ROOF_MATL_CD	RoofingMaterial Code	VARCHAR2(25)	This system code identifies the material used to construct the roof.
Warehouse	HO_DWLNG	ROOF_MATL_DESC	RoofingMaterial Description	VARCHAR2(60)	This value describes the roof material code.
Warehouse	HO_DWLNG	ROOF_UPDT_TYP_CD	RoofingUpdate Type Code	VARCHAR2(25)	This system code indicates the type or roofing updates made since the dwelling's original construction.
Warehouse	HO_DWLNG	ROOF_UPDT_TYP_DESC	RoofingUpdate Type Description	VARCHAR2(60)	This value describes the roof update type code.
Warehouse	HO_DWLNG	ROOF_UPDT_YR	RoofingUpdate Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling roofing materials.
Warehouse	HO_DWLNG	SCND_HEAT_TYP_CD	Secondary Heating Type Code	VARCHAR2(25)	This system code describes the secondary source of heat for dwelling.
Warehouse	HO_DWLNG	SCND_HEAT_TYP_DESC	Secondary Heating Type Description	VARCHAR2(60)	This value describes the secondary source of heat for dwelling.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	HO_DWLNG	SIDING_CD	Siding Code	VARCHAR2(25)	This system code identifies the type of material used as siding on the dwelling.
Warehouse	HO_DWLNG	SIDING_DESC	Siding Description	VARCHAR2(60)	This value describes the siding material used on the dwelling.
Warehouse	HO_DWLNG	SIDING_PCT	Siding Percentage	NUMBER (6, 3)	This number represents the percentage of total dwelling exterior covered with siding.
Warehouse	HO_DWLNG	SPRINKLER_TYP_CD	Sprinkler Type Code	VARCHAR2(25)	This system code identifies the sprinkler system type.
Warehouse	HO_DWLNG	SPRINKLER_TYP_DESC	Sprinkler Type Description	VARCHAR2(60)	This value describes the characteristics of a sprinkler system.
Warehouse	HO_DWLNG	STORM_SHUTTERS_CD	Storm Shutters Code	VARCHAR2(25)	This system code describes the existence or absence and type of storm shutters.
Warehouse	HO_DWLNG	STORM_SHUTTERS_DESC	Storm Shutters Description	VARCHAR2(60)	This value describes storm shutters attached to a dwelling.
Warehouse	HO_DWLNG	SWIM_POOL_CD	Swimming Pool Code	VARCHAR2(25)	This system code indicates the presence or absence and type of swimming pool.
Warehouse	HO_DWLNG	SWIM_POOL_DESC	Swimming Pool Description	VARCHAR2(60)	This value describes the type of swimming pool.
Warehouse	HO_DWLNG	TRAMPOLINE_FLG	Trampoline Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of a trampoline.
Warehouse	HO_DWLNG	UNDER_CONST_TYP_CD	Under Construction Type Code	VARCHAR2(25)	This system code indicates active construction activities on the dwelling.
Warehouse	HO_DWLNG	UNDER_CONST_TYP_DESC	Under Construction Type Description	VARCHAR2(60)	This value describes the active construction activities.
Warehouse	HO_DWLNG	WIRG_LAST_INSP_DT	Wiring Last InspectedDate	DATE	This calendar date represents the occurance of the last inspection of the wiring system.
Warehouse	HO_DWLNG	WIRG_UPDT_TYP_CD	Wiring Update Type Code	VARCHAR2(25)	This system code identifies the type of update to wiring system.
Warehouse	HO_DWLNG	WIRG_UPDT_TYP_DESC	Wiring Update Type Description	VARCHAR2(60)	This value describes the changes made to wiring system since original construction.
Warehouse	HO_DWLNG	WIRG_UPDT_YR	Wiring Update Year	CHAR(4)	This value represents the calendar year of the last update to the dwelling wiring system.
Warehouse	HO_DWLNG	YR_BUILT	Year Built	CHAR(4)	This value represents the calendar year that the dwelling was constructed.
Warehouse	INSD	AUDIT_FREQ_CD	Audit Frequency Code	VARCHAR2(25)	This system code identifies the intervals at which audits of the insured attributes are performed at the insurance company.
Warehouse	INSD	AUDIT_FREQ_DESC	Audit Frequency Code Description	VARCHAR2(60)	This value describes the intervals at which audits are performed at the insured company.
Warehouse	INSD	AUDIT_TYP_CD	Audit Type Code	VARCHAR2(25)	This system code identifies what type of audit will be performed when the insured is audited.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	INSD	AUDIT_TYP_DESC	Audit Type Code Description	VARCHAR2(60)	This value describes what type of audit will be performed when the insured is audited.
Warehouse	INSD	BEGIN_DT	Begin Date	DATE	This calendar date represents when the insured applies.
Warehouse	INSD	CRED_SCORE	Credit Score	VARCHAR2(11)	This value represents the rating from the current credit report.
Warehouse	INSD	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the insured is currently applicable.
Warehouse	INSD	END_DT	End Date	DATE	This calendar date represents when the insured is no longer valid.
Warehouse	INSD	INSD_ID	Insured Identifier	NUMBER (22, 0)	This system generated number identifies the insured instance.
Warehouse	INSD	INSD_TYP_CD	Insured Type Code	VARCHAR2(25)	This system code indicates the type of entity that a policy represents.
Warehouse	INSD	INSD_TYP_DESC	Insured Type Description	VARCHAR2(60)	This value describes the type of entity that a policy represents.
Warehouse	INSD	INSD_UDF_CD_1	Insured User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first insured user defined field.
Warehouse	INSD	INSD_UDF_CD_2	Insured User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second insured user defined field.
Warehouse	INSD	INSD_UDF_CD_3	Insured User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third insured user defined field.
Warehouse	INSD	INSD_UDF_CD_4	Insured User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth insured user defined field.
Warehouse	INSD	INSD_UDF_CD_5	Insured User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth insured user defined field.
Warehouse	INSD	INSD_UDF_DESC_1	Insured User Defined Field Description 1	VARCHAR2(60)	This value describes the first insured user defined field.
Warehouse	INSD	INSD_UDF_DESC_2	Insured User Defined Field Description 2	VARCHAR2(60)	This value describes the second insured user defined field.
Warehouse	INSD	INSD_UDF_DESC_3	Insured User Defined Field Description 3	VARCHAR2(60)	This value describes the third insured user defined field.
Warehouse	INSD	INSD_UDF_DESC_4	Insured User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth insured user defined field.
Warehouse	INSD	INSD_UDF_DESC_5	Insured User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth insured user defined field.
Warehouse	INSD	ORG_ID	Organization Identifier	NUMBER (22, 0)	This system generated number identifies the insured organization instance.
Warehouse	INSD	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	INSD	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person.
Warehouse	INSD	PRIOR_INSUR_CO_CD	Prior Insurance Company Code	VARCHAR2(25)	This system code represents the prior insurance company.
Warehouse	INSD	PRIOR_INSUR_CO_DESC	Prior Insurance Company Description	VARCHAR2(60)	This value represents the name of the insurance company writing a policyholder's insurance before the current carrier.
Warehouse	INSD	RISK_GRADE_CD	Risk Grade Code	VARCHAR2(25)	This system code represents the A.M. Best or company defined risk grade in the insured.
Warehouse	INSD	RISK_GRADE_DESC	Risk Grade Code	VARCHAR2(60)	This value describes the A.M. Best or company defined risk grade.
Warehouse	INSD	RPT_PERIOD_CD	Reporting Period Code	VARCHAR2(25)	This system code identifies the frequency with which reports are due for policies issued on a reporting basis.
Warehouse	INSD	RPT_PERIOD_DESC	Reporting Period Description	VARCHAR2(60)	This value describes the frequency of reports sent to the company for reporting form coverage.
Warehouse	INSUR_CO	AM_BEST_NUM	A.M. Best Number	VARCHAR2(5)	This value represents the insurance company code assigned by A.M. Best.
Warehouse	INSUR_CO	BEGIN_DT	Begin Date	DATE	This calendar date represents when the insurance company applies.
Warehouse	INSUR_CO	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the insurance company is currently applicable.
Warehouse	INSUR_CO	END_DT	End Date	DATE	This calendar date represents when the insurance company is no longer valid.
Warehouse	INSUR_CO	INSUR_CO_ID	Insurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the insurance company instance.
Warehouse	INSUR_CO	INSUR_CO_TYP_CD	Insurance Company Type Code	VARCHAR2(25)	This system code identifies insurance company type.
Warehouse	INSUR_CO	INSUR_CO_TYP_DESC	Insurance Company Type Description	VARCHAR2(60)	This value describes the insurance company type.
Warehouse	INSUR_CO	INSUR_CO_UDF_CD_1	Insurance Company User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first insurance company user defined field.
Warehouse	INSUR_CO	INSUR_CO_UDF_CD_2	Insurance Company User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second insurance company user defined field.
Warehouse	INSUR_CO	INSUR_CO_UDF_CD_3	Insurance Company User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third insurance company user defined field.
Warehouse	INSUR_CO	INSUR_CO_UDF_CD_4	Insurance Company User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth insurance company user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	INSUR_CO	INSUR_CO_UDF_CD_5	Insurance Company User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth insurance company user defined field.
Warehouse	INSUR_CO	INSUR_CO_UDF_DESC_1	Insurance Company User Defined Field Description 1	VARCHAR2(60)	This value describes the first insurance company user defined field.
Warehouse	INSUR_CO	INSUR_CO_UDF_DESC_2	Insurance Company User Defined Field Description 2	VARCHAR2(60)	This value describes the second insurance company user defined field.
Warehouse	INSUR_CO	INSUR_CO_UDF_DESC_3	Insurance Company User Defined Field Description 3	VARCHAR2(60)	This value describes the third insurance company user defined field.
Warehouse	INSUR_CO	INSUR_CO_UDF_DESC_4	Insurance Company User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth insurance company user defined field.
Warehouse	INSUR_CO	INSUR_CO_UDF_DESC_5	Insurance Company User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth insurance company user defined field.
Warehouse	INSUR_CO	ISO_CD	Insurance Services Office Code	VARCHAR2(5)	This value represents the Insurance Services Office code assigned to insurance company.
Warehouse	INSUR_CO	NAIC_CD	National Association of Insurance Commissioners Code Code	VARCHAR2(5)	This system code is assigned to the company to use for NAIC reporting - The National Association of Insurance Commissioners Code groups types of business.
Warehouse	INSUR_CO	NCCI_CD	NCCI Code	VARCHAR2(5)	This system code is assigned to the company to use for National Council on Compensation insurance (NCCI) reporting.
Warehouse	INSUR_CO	ORG_ID	Organization Identifier	NUMBER (22, 0)	This system generated number identifies the insurance company organization instance.
Warehouse	INSUR_CO	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	LITG	ALT_DISPUTE_RESOLUTION_CD	Alternate Dispute Resolution Code	VARCHAR2(25)	This system code identifies the outcome of using an intermediary for dispute settlement.
Warehouse	LITG	BEGIN_DT	Begin Date	DATE	This calendar date represents when the litigation began.
Warehouse	LITG	COMPENSATORY_DEMAND_AMT	Compensatory Demand Amount	NUMBER (14, 3)	This number represents the amount of requested compensatory damages.
Warehouse	LITG	COMPENSATORY_OFFER_AMT	Compensatory Offer Amount	NUMBER (14, 3)	This number represents the amount of offered compensatory damages.
Warehouse	LITG	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the litigation is currently applicable.
Warehouse	LITG	DISCLOSURE_DT	Disclosure Date	DATE	This date represents the calendar date of disclosure of information related to litigation.
Warehouse	LITG	END_DT	End Date	DATE	This calendar date represents when the litigation is no longer valid.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	LITG	LITG_AMT	Litigation Amount	NUMBER (14, 3)	This number represents the amount of litigation case.
Warehouse	LITG	LITG_CLOSED_DT	Litigation Closed Date	DATE	This calendar date represents when litigation case was closed.
Warehouse	LITG	LITG_CNTY_CD	Litigation County Code	VARCHAR2(25)	This system code describes a litigation county.
Warehouse	LITG	LITG_CNTY_DESC	Litigation County Description	VARCHAR2(60)	This value identifies the county of jurisdiction over litigation case.
Warehouse	LITG	LITG_DISPOSITION_CD	Litigation Disposition Code	VARCHAR2(25)	This system code identifies the litigation disposition.
Warehouse	LITG	LITG_DISPOSITION_DESC	Litigation Disposition Description	VARCHAR2(60)	This value describes the litigation Disposition.
Warehouse	LITG	LITG_ID	Litigation Identifier	NUMBER (22, 0)	This system generated number identifies the litigation instance.
Warehouse	LITG	LITG_NAT_KEY	Litigation Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the litigation.
Warehouse	LITG	LITG_OPENED_DT	Litigation Opened Date	DATE	This calendar date represents when litigation case was filed in court.
Warehouse	LITG	LITG_STATE_CD	Litigation State Code	VARCHAR2(25)	This system code identifies the litigation state.
Warehouse	LITG	LITG_STATE_DESC	Litigation State Description	VARCHAR2(60)	This value represents the name of the litigation state.
Warehouse	LITG	LITG_UDF_CD_1	Litigation User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first litigation user defined field.
Warehouse	LITG	LITG_UDF_CD_2	Litigation User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second litigation user defined field.
Warehouse	LITG	LITG_UDF_CD_3	Litigation User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third litigation user defined field.
Warehouse	LITG	LITG_UDF_CD_4	Litigation User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth litigation user defined field.
Warehouse	LITG	LITG_UDF_CD_5	Litigation User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth litigation user defined field.
Warehouse	LITG	LITG_UDF_DESC_1	Litigation User Defined Field Description 1	VARCHAR2(60)	This value describes the first litigation user defined field.
Warehouse	LITG	LITG_UDF_DESC_2	Litigation User Defined Field Description 2	VARCHAR2(60)	This value describes the second litigation user defined field.
Warehouse	LITG	LITG_UDF_DESC_3	Litigation User Defined Field Description 3	VARCHAR2(60)	This value describes the third litigation user defined field.
Warehouse	LITG	LITG_UDF_DESC_4	Litigation User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth litigation user defined field.
Warehouse	LITG	LITG_UDF_DESC_5	Litigation User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth litigation user defined field.
Warehouse	LITG	TRIAL_DT	Trial Date	DATE	This calendar date represents the when the trial is scheduled, or has already occurred.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	LMT	BEGIN_DT	Begin Date	DATE	This calendar date represents when the limit applies.
Warehouse	LMT	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the limit is currently applicable.
Warehouse	LMT	END_DT	End Date	DATE	This calendar date represents when the limit is no longer valid.
Warehouse	LMT	FIRST_LMT	First Limit	VARCHAR2(15)	This value represents the first limit.
Warehouse	LMT	FULL_LMT	Full Limit	VARCHAR2(50)	This value represents the unabbreviated limit amount.
Warehouse	LMT	LMT_APPLIES_TO_CD	Limit Applies To Code	VARCHAR2(25)	This system code identifies the limit applies to.
Warehouse	LMT	LMT_APPLIES_TO_DESC	Limit Applies To Description	VARCHAR2(60)	This value describes the classification of coverage for which a limit applies.
Warehouse	LMT	LMT_BASIS_CD	Limit Basis Code	VARCHAR2(25)	This system code identifies limit basis.
Warehouse	LMT	LMT_BASIS_DESC	Limit Basis Description	VARCHAR2(60)	This value describes limit basis.
Warehouse	LMT	LMT_ID	Limit Identifier	NUMBER (22, 0)	This system generated number identifies the limit instance.
Warehouse	LMT	LMT_NAT_KEY	Limit Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the limit.
Warehouse	LMT	LMT_TYP_CD	Limit Type Code	VARCHAR2(25)	This system code identifies limit type.
Warehouse	LMT	LMT_TYP_DESC	Limit Type Description	VARCHAR2(60)	This value describes limit type.
Warehouse	LMT	LMT_UDF_CD_1	Limit User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first limit user defined field.
Warehouse	LMT	LMT_UDF_CD_2	Limit User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second limit user defined field.
Warehouse	LMT	LMT_UDF_CD_3	Limit User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third limit user defined field.
Warehouse	LMT	LMT_UDF_CD_4	Limit User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth limit user defined field.
Warehouse	LMT	LMT_UDF_CD_5	Limit User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth limit user defined field.
Warehouse	LMT	LMT_UDF_DESC_1	Limit User Defined Field Description 1	VARCHAR2(60)	This value describes the first limit user defined field.
Warehouse	LMT	LMT_UDF_DESC_2	Limit User Defined Field Description 2	VARCHAR2(60)	This value describes the second limit user defined field.
Warehouse	LMT	LMT_UDF_DESC_3	Limit User Defined Field Description 3	VARCHAR2(60)	This value describes the third limit user defined field.
Warehouse	LMT	LMT_UDF_DESC_4	Limit User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth limit user defined field.
Warehouse	LMT	LMT_UDF_DESC_5	Limit User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth limit user defined field.
Warehouse	LMT	SECOND_LMT	Second Limit	VARCHAR2(15)	This value represents the second limit.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	LMT	THIRD_LMT	Third Limit	VARCHAR2(15)	This value identifies the third limit.
Warehouse	LMT	VALUATION_CD	Valuation Code	VARCHAR2(25)	This system code identifies the type of valuation or valuation requested.
Warehouse	LMT	VALUATION_DESC	Valuation Description	VARCHAR2(60)	This value describes the code assigned in the method of loss valuation.
Warehouse	LOB	BEGIN_DT	Begin Date	DATE	This calendar date represents when the line of business applies.
Warehouse	LOB	CO_PROD_CD	Company Product Code	VARCHAR2(25)	This system code identifies the company product.
Warehouse	LOB	CO_PROD_DESC	Company Producer Description	VARCHAR2(60)	This value describes the company producer.
Warehouse	LOB	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the line of business is currently applicable.
Warehouse	LOB	END_DT	End Date	DATE	This calendar date represents when the line of business is no longer valid.
Warehouse	LOB	LOB_CD	Line Of Business Code	VARCHAR2(25)	This system code identifies the line of business classification.
Warehouse	LOB	LOB_DESC	Line Of Business Description	VARCHAR2(60)	This value describes the line of business.
Warehouse	LOB	LOB_ID	Line Of Business Identifier	NUMBER (22, 0)	This system generated number identifies the line of business instance.
Warehouse	LOB	LOB_NAT_KEY	Line of Business Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the line of business.
Warehouse	LOB	LOB_SUB_CD	Line Of Business Sub Code	VARCHAR2(25)	This system code identifies the line of business sub code that further refines the line of business code.
Warehouse	LOB	LOB_SUB_DESC	Line Of Business Sub Code Description	VARCHAR2(60)	This value represents the further breakdown of line of business that may be defined by company.
Warehouse	LOB	LOB_UDF_CD_1	Line of Business User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first line of business user defined field.
Warehouse	LOB	LOB_UDF_CD_2	Line of Business User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second line of business user defined field.
Warehouse	LOB	LOB_UDF_CD_3	Line of Business User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third line of business user defined field.
Warehouse	LOB	LOB_UDF_CD_4	Line of Business User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth line of business user defined field.
Warehouse	LOB	LOB_UDF_CD_5	Line of Business User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth line of business user defined field.
Warehouse	LOB	LOB_UDF_DESC_1	Line of Business User Defined Field Description 1	VARCHAR2(60)	This value describes the first line of business user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	LOB	LOB_UDF_DESC_2	Line of Business User Defined Field Description 2	VARCHAR2(60)	This value describes the second line of business user defined field.
Warehouse	LOB	LOB_UDF_DESC_3	Line of Business User Defined Field Description 3	VARCHAR2(60)	This value describes the third line of business user defined field.
Warehouse	LOB	LOB_UDF_DESC_4	Line of Business User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth line of business user defined field.
Warehouse	LOB	LOB_UDF_DESC_5	Line of Business User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth line of business user defined field.
Warehouse	LOB	PSNL_OR_COML_CD	Personal Or Commercial Code	VARCHAR2(25)	This system code indicates if the policy is a personal or commercial policy.
Warehouse	LOB	PSNL_OR_COML_DESC	Personal Or Commercial Description	VARCHAR2(60)	This value describes a policy's status as personal or commercial lines.
Warehouse	LOB	SYS_LOB_CD	System Line of Business Code	VARCHAR2(25)	This system code represents a system line of business.
Warehouse	LOB	SYS_LOB_DESC	System Line of Business Description	VARCHAR2(60)	This value describes the system line of business.
Warehouse	ORG	BEGIN_DT	Begin Date	DATE	This calendar date represents when the organization applies.
Warehouse	ORG	BUS_START_DT	Business Start Date	DATE	This calendar date represents when the insurance company began business operations.
Warehouse	ORG	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the organization is currently applicable.
Warehouse	ORG	DBA	Doing Business As	VARCHAR2(170)	This value represents the type or category of the business activities done by the producer.
Warehouse	ORG	END_DT	End Date	DATE	This calendar date represents when the organization is no longer valid.
Warehouse	ORG	NAICS_CD	North American Industry Classification System Code	VARCHAR2(25)	This system code is assigned to the company to use for NAICS reporting - The North American Industry Classification System groups types of business.
Warehouse	ORG	NAICS_DESC	North American Industry Classification System Description	VARCHAR2(60)	This value describes The North American Industry Classification System code.
Warehouse	ORG	NOB_CD	Nature of Business Code	VARCHAR2(25)	This system code identifies the nature of business of organization.
Warehouse	ORG	NOB_DESC	Nature of Business Description	VARCHAR2(60)	This value represents the type or category of the business activities done by the organization.
Warehouse	ORG	NUM_EMP	Number Of Employees	NUMBER (22, 0)	This number represents the count of people employed by organization.
Warehouse	ORG	ORG_ID	Organization Identifier	NUMBER (22, 0)	This system generated number identifies the organization instance.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	ORG	ORG_NM	Organization Name	VARCHAR2(170)	This value represents the name of an organization.
Warehouse	ORG	ORG_UDF_CD_1	Organization User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first organization user defined field.
Warehouse	ORG	ORG_UDF_CD_2	Organization User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second organization user defined field.
Warehouse	ORG	ORG_UDF_CD_3	Organization User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third organization user defined field.
Warehouse	ORG	ORG_UDF_CD_4	Organization User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth organization user defined field.
Warehouse	ORG	ORG_UDF_CD_5	Organization User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth organization user defined field.
Warehouse	ORG	ORG_UDF_DESC_1	Organization User Defined Field Description 1	VARCHAR2(60)	This value describes the first organization user defined field.
Warehouse	ORG	ORG_UDF_DESC_2	Organization User Defined Field Description 2	VARCHAR2(60)	This value describes the second organization user defined field.
Warehouse	ORG	ORG_UDF_DESC_3	Organization User Defined Field Description 3	VARCHAR2(60)	This value describes the third organization user defined field.
Warehouse	ORG	ORG_UDF_DESC_4	Organization User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth organization user defined field.
Warehouse	ORG	ORG_UDF_DESC_5	Organization User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth organization user defined field.
Warehouse	ORG	PARTY_ID	Party Identifier	NUMBER (22, 0)	This system generated number identifies the party.
Warehouse	ORG	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	ORG	SIC_CD	Standard Industrial Classification Code	VARCHAR2(25)	The Standard Industrial Classification (SIC) code is an industry code that identifies the classification of business activity. This is the SIC assigned to the company.
Warehouse	ORG	SIC_DESC	Standard Industrial Classification Code Description	VARCHAR2(60)	This value describes the Standard industrial Classification code assigned to the company.
Warehouse	PA_DRV	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage in the personal driver begins.
Warehouse	PA_DRV	COMMUTER_DSCNT_FLG	Commuter Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying the presence or absence of commuter discount.
Warehouse	PA_DRV	COMMUTER_DSCNT_PCT	Commuter Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when commuter discount applies.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PA_DRV	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the personal vehicle driver is currently applicable.
Warehouse	PA_DRV	DFEN_DRV_CD	Defensive Driving Code	VARCHAR2(25)	This system code indicates the type of defensive driving course the driver completed.
Warehouse	PA_DRV	DFEN_DRV_DESC	Defensive Driving Description	VARCHAR2(60)	This value describes the defensive driving code.
Warehouse	PA_DRV	DFEN_DRV_TRNG_DSCNT_FLG	Defensive Driving Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a defensive driver training discount is applicable.
Warehouse	PA_DRV	DFEN_DRV_TRNG_DSCNT_PCT	Defensive Driving Training Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when driver training discount applies.
Warehouse	PA_DRV	DIST_STUDENT_FLG	Distant Student Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not the student driver meets the company definition of distant driver.
Warehouse	PA_DRV	DRV_ACCID_CNT	Driver Accident Count	NUMBER (22, 0)	This number represents the count of reported accidents charged against the driver's driving record.
Warehouse	PA_DRV	DRV_CLASS_CD	Driver Class Code	VARCHAR2(25)	This system code identifies the class assigned to a personal vehicle driver.
Warehouse	PA_DRV	DRV_CLASS_DESC	Driver Class Description	VARCHAR2(60)	This value describes the driver class.
Warehouse	PA_DRV	DRV_DWI_DUI_VIOLATION_CNT	Driver DWI / DUI Violation Count	NUMBER (22, 0)	This number represents the count of Driving While intoxicated (DWI) and/or Driving Under the influence (DUI) violations charged against the driver's driving record.
Warehouse	PA_DRV	DRV_INTRMDT_VIOLATION_CNT	Driver Intermediate Violation Count	NUMBER (22, 0)	This number represents the count of intermediate violations charged against the driver's driving record.
Warehouse	PA_DRV	DRV_LIC_ISSUED_BY_CD	Driver License Issued By Code	VARCHAR2(25)	This system code indentifies which entity granted driving privileges to driver.
Warehouse	PA_DRV	DRV_LIC_ISSUED_BY_DESC	Driver License Issued By Description	VARCHAR2(60)	This value describes the entity that issued a drivers license.
Warehouse	PA_DRV	DRV_LIC_STATUS_CD	Driver License Status Code	VARCHAR2(25)	This system code indicates the driver license status.
Warehouse	PA_DRV	DRV_LIC_STATUS_DESC	Driver License Status Description	VARCHAR2(60)	This value describes the status of a drivers license.
Warehouse	PA_DRV	DRV_MAJOR_VIOLATION_CNT	Driver Major Violation Count	NUMBER (22, 0)	This number represents the count of major violations charged against the driver's driving record.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PA_DRV	DRV_MINOR_VIOLATION_CNT	Driver Minor Violation Count	NUMBER (22, 0)	This number represents the count of minor violations charged against the driver's driving record.
Warehouse	PA_DRV	DRV_NUM	Driver Number	NUMBER (22, 0)	This number identifies the driver.
Warehouse	PA_DRV	DRV_OCP	Driver Occupation	VARCHAR2(50)	This value represents the classification of employment tasks completed during personal vehicle driver's employment.
Warehouse	PA_DRV	DRV_STATUS_CD	Driver Status Code	VARCHAR2(25)	This system code indicates the driver status.
Warehouse	PA_DRV	DRV_STATUS_DESC	Driver Status Description	VARCHAR2(60)	This value describes the status of a driver.
Warehouse	PA_DRV	DRV_TRNG_DSCNT_FLG	Driver Training Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not the driver is receiving a driver training discount.
Warehouse	PA_DRV	DRV_TRNG_DSCNT_PCT	Driver Training Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when driver training discount applies.
Warehouse	PA_DRV	DRV_TRNG_FLG	Driver Training Flag	CHAR(1)	This value represents based on the yes/no indicator that identifies whether or not a driver has completed a driver training course.
Warehouse	PA_DRV	DRV_TYP_CD	Driver Type Code	VARCHAR2(25)	This system code describes the driver activities.
Warehouse	PA_DRV	DRV_TYP_DESC	Driver Type Description	VARCHAR2(60)	This value describes driver type.
Warehouse	PA_DRV	END_DT	End Date	DATE	This calendar date represents when the personal driver is no longer included in policy coverages.
Warehouse	PA_DRV	GOOD_STUDENT_CD	Good Student Code	VARCHAR2(25)	This system code identifies if the driver qualifies in the good student credit.
Warehouse	PA_DRV	GOOD_STUDENT_DESC	Good Student Description	VARCHAR2(60)	This value describes the good student attributes.
Warehouse	PA_DRV	GOOD_STUDENT_DSCNT_FLG	Good Student Discount Flag	CHAR(1)	This value represents based on the yes/no indicator that identifies whether or not a driver has met the company's definition of a good student.
Warehouse	PA_DRV	GOOD_STUDENT_DSCNT_PCT	Good Student Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when good student discount applies.
Warehouse	PA_DRV	INSD_DT	Insured Date	DATE	This calendar date represents when insurance coverage began for personal driver.
Warehouse	PA_DRV	LIC_DT	License Date	DATE	This date represents the original date on which the driver's license was issued to this driver.
Warehouse	PA_DRV	NUM_YRS_AT_CUR_ADDR	Number Of Years At Current Address	NUMBER (22, 0)	This number represents the count of years personal vehicle driver has resided at current address.
Warehouse	PA_DRV	PA_DRV_ID	Personal Auto Driver Identifier	NUMBER (22, 0)	This system generated number identifies the personal vehicle driver instance.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PA_DRV	PA_DRV_UDF_CD_1	Personal Auto Driver User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first personal vehicle driver user defined field.
Warehouse	PA_DRV	PA_DRV_UDF_CD_2	Personal Auto Driver User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second personal vehicle driver user defined field.
Warehouse	PA_DRV	PA_DRV_UDF_CD_3	Personal Auto Driver User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third personal vehicle driver user defined field.
Warehouse	PA_DRV	PA_DRV_UDF_CD_4	Personal Auto Driver User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth personal vehicle driver user defined field.
Warehouse	PA_DRV	PA_DRV_UDF_CD_5	Personal Auto Driver User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth personal vehicle driver user defined field.
Warehouse	PA_DRV	PA_DRV_UDF_DESC_1	Personal Auto Driver User Defined Field Description 1	VARCHAR2(60)	This value describes the first personal vehicle driver user defined field.
Warehouse	PA_DRV	PA_DRV_UDF_DESC_2	Personal Auto Driver User Defined Field Description 2	VARCHAR2(60)	This value describes the second personal vehicle driver user defined field.
Warehouse	PA_DRV	PA_DRV_UDF_DESC_3	Personal Auto Driver User Defined Field Description 3	VARCHAR2(60)	This value describes the third personal vehicle driver user defined field.
Warehouse	PA_DRV	PA_DRV_UDF_DESC_4	Personal Auto Driver User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth personal vehicle driver user defined field.
Warehouse	PA_DRV	PA_DRV_UDF_DESC_5	Personal Auto Driver User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth personal vehicle driver user defined field.
Warehouse	PA_DRV	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	PA_DRV	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person.
Warehouse	PA_DRV	RLAT_TO_APPLICANT_CD	Relationship to Applicant Code	VARCHAR2(25)	This system code identifies the relationship of this individual to the applicant.
Warehouse	PA_DRV	RLAT_TO_APPLICANT_DESC	Relationship to Applicant Code Description	VARCHAR2(60)	This value describes the relationship to applicant code.
Warehouse	PA_DRV	YOUTHFUL_CD	Youthful Code	VARCHAR2(25)	This value represents based on the yes/no indicator identifying whether or not a driver meets the company criteria of a youthful driver.
Warehouse	PA_DRV	YOUTHFUL_DESC	Youthful Description	VARCHAR2(60)	This value represents the description of youthful personal vehicle driver.
Warehouse	PA_VEH	ADDL_EQPT_AMT	Additional Equipment Amount	NUMBER (14, 3)	This number represents the monetary cost of vehicle alterations or aftermarket custom equipment like custom painting, equipment installed to overcome a physical handicap, etc. installed on a personal vehicle.
Warehouse	PA_VEH	AIRBAG_TYP_CD	Airbag Type Code	VARCHAR2(25)	This system code identifies the attributes of the airbag system installed in the personal vehicle.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PA_VEH	AIRBAG_TYP_DESC	Airbag Type Code Description	VARCHAR2(60)	This value describes the airbag type code.
Warehouse	PA_VEH	ANTI_LOCK_BRAKES_CD	Anti-lock Brake Code	VARCHAR2(25)	This system code identifies the attributes of anti-lock brakes on the personal vehicle.
Warehouse	PA_VEH	ANTI_LOCK_BRAKES_DESC	Anti-lock Brake Code Description	VARCHAR2(60)	This value describes the anti-lock brake code.
Warehouse	PA_VEH	ANTI_THEFT_DEVICE_CD	Anti-Theft Device Code	VARCHAR2(25)	This system code identifies the attributes of the anti-theft system installed on the personal vehicle.
Warehouse	PA_VEH	ANTI_THEFT_DEVICE_DESC	Anti-Theft Device Code Description	VARCHAR2(60)	This value describes the anti-theft device code.
Warehouse	PA_VEH	AUTO_STBLTS_DSCNT_FLG	Automatic Seatbelt Type Code	CHAR(1)	This system code identifies whether an automatic seatbelt discount applies to the personal vehicle.
Warehouse	PA_VEH	AUTO_STBLTS_DSCNT_PCT	Automatic Seatbelt Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when automatic seatbelt discount applies.
Warehouse	PA_VEH	BEGIN_DT	Begin Date	DATE	This calendar date represents when the coverage in the personal driver begins.
Warehouse	PA_VEH	CELL_PHONE_TYP_CD	Cellular Phone Type Code	VARCHAR2(25)	This system code identifies the attributes of a cellular phone present in the vehicle.
Warehouse	PA_VEH	CELL_PHONE_TYP_DESC	Cellular Phone Type Description	VARCHAR2(60)	This value represents the description of the cellular phone type.
Warehouse	PA_VEH	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the personal vehicle is currently applicable.
Warehouse	PA_VEH	DAYTIME_RUN_LIGHTS_CD	Daytime Running Lights Code	VARCHAR2(25)	This value represents based on the yes/no indicator that states whether or not a vehicle has daytime running headlights.
Warehouse	PA_VEH	DAYTIME_RUN_LIGHTS_DESC	Daytime Running Lights Description	VARCHAR2(60)	This value describes the daytime running headlights of a personal vehicle.
Warehouse	PA_VEH	END_DT	End Date	DATE	This calendar date represents when the personal vehicle is no longer included in policy coverages.
Warehouse	PA_VEH	EST_ANNU_DRVG_DIST	Estimated Annual Driving Distance	NUMBER (22, 0)	This number represents the estimated number of distance units (miles/kilometers) a vehicle is driven over a one year period.
Warehouse	PA_VEH	GAR_CD	Garaging Code	VARCHAR2(25)	This system code identifies where the vehicle is parked at night.
Warehouse	PA_VEH	GAR_DESC	Garaging Description	VARCHAR2(60)	This value describes where a vehicle is parked at night.
Warehouse	PA_VEH	GAR_LOC_ADDR_ID	Garaging Location Address Identifier	NUMBER (22, 0)	This system generated number identifies the garaging location address instance in the personal vehicle.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PA_VEH	HP_DSPLCMNT	Horsepower Displacement	VARCHAR2(5)	This value represents the cubic centimeters or displacement (for example, motorcycles) or horsepower for recreational vehicles.
Warehouse	PA_VEH	INSD_DT	Insured Date	DATE	This calendar date represents when insurance coverage began for a personal vehicle.
Warehouse	PA_VEH	LEASE_DT	Persona Auto Vehicle Lease Date	DATE	This calendar date represents when a personal vehicle was leased by insured.
Warehouse	PA_VEH	MSRP	Manufacturer Suggested Retail Price	NUMBER (14, 3)	This number represents the price that the manufacturer tells the vehicle dealer the new vehicle is worth.
Warehouse	PA_VEH	MULT_CAR_DSCNT_FLG	Multiple Car Discount Flag	CHAR(1)	This value represents based on the yes/no indicator identifying whether or not a multiple car discount applies.
Warehouse	PA_VEH	MULT_CAR_DSCNT_PCT	Multiple Car Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when a multiple car discount applies.
Warehouse	PA_VEH	NEW_OR_USED_CD	New Or Used Code	VARCHAR2(25)	This system code identifies if the insured is the original owner of the insured vehicle.
Warehouse	PA_VEH	NEW_OR_USED_DESC	New or Used Description	VARCHAR2(60)	This value describes new or used code.
Warehouse	PA_VEH	NUM_DAYS_DRVN_PER_WK	Number Of Days Driven Per Week	NUMBER (22, 0)	This number represents the count of days the personal vehicle is driven each calendar week.
Warehouse	PA_VEH	ONE_WAY_DIST_TO_WRK	One Way Distance To Work	NUMBER (22, 0)	This number represents the number of distance units (miles/kilometers) to place of employment.
Warehouse	PA_VEH	OWNRSHP_TYP_CD	Ownership Type Code	VARCHAR2(25)	This system code describes the ownership type of a vehicle standard code.
Warehouse	PA_VEH	OWNRSHP_TYP_DESC	Ownership Type Description	VARCHAR2(60)	This value represents the classification that describes how a personal vehicle is owned and titled.
Warehouse	PA_VEH	PA_VEH_ID	Persona Auto Vehicle Identifier	NUMBER (22, 0)	This system generated number identifies the personal vehicle instance.
Warehouse	PA_VEH	PA_VEH_NAT_KEY	Persona Auto Vehicle Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the personal vehicle.
Warehouse	PA_VEH	PA_VEH_UDF_CD_1	Persona Auto Vehicle User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first personal vehicle user defined field.
Warehouse	PA_VEH	PA_VEH_UDF_CD_2	Persona Auto Vehicle User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second personal vehicle user defined field.
Warehouse	PA_VEH	PA_VEH_UDF_CD_3	Persona Auto Vehicle User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third personal vehicle user defined field.
Warehouse	PA_VEH	PA_VEH_UDF_CD_4	Persona Auto Vehicle User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth personal vehicle user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PA_VEH	PA_VEH_UDF_CD_5	Persona Auto Vehicle User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth personal vehicle user defined field.
Warehouse	PA_VEH	PA_VEH_UDF_DESC_1	Persona Auto Vehicle User Defined Field Description 1	VARCHAR2(60)	This value describes the first personal vehicle user defined field.
Warehouse	PA_VEH	PA_VEH_UDF_DESC_2	Persona Auto Vehicle User Defined Field Description 2	VARCHAR2(60)	This value describes the second personal vehicle user defined field.
Warehouse	PA_VEH	PA_VEH_UDF_DESC_3	Persona Auto Vehicle User Defined Field Description 3	VARCHAR2(60)	This value describes the third personal vehicle user defined field.
Warehouse	PA_VEH	PA_VEH_UDF_DESC_4	Persona Auto Vehicle User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth personal vehicle user defined field.
Warehouse	PA_VEH	PA_VEH_UDF_DESC_5	Persona Auto Vehicle User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth personal vehicle user defined field.
Warehouse	PA_VEH	PURCH_DT	Purchase Date	DATE	This calendar date represents when the insured purchased the personal vehicle.
Warehouse	PA_VEH	PURCH_PRICE	Purchase Price	NUMBER (14, 3)	This number represents the monetary amount paid when personal vehicle was purchased.
Warehouse	PA_VEH	RATING_AGE_CD	Rating Age Code	VARCHAR2(25)	This system code represents the rating age used to rate the vehicle, regardless of its actual age.
Warehouse	PA_VEH	RATING_AGE_DESC	Rating Age Description	VARCHAR2(60)	This value describes rating age.
Warehouse	PA_VEH	STATED_AMT	Stated Amount	NUMBER (14, 3)	This number represents the amount used to rate and value a vehicle when a symbol is not available or useful.
Warehouse	PA_VEH	VEH_BODY_TYP_CD	Vehicle Body Type Code	VARCHAR2(25)	This system code describes the attributes of vehicle body for a scheduled personal vehicle.
Warehouse	PA_VEH	VEH_BODY_TYP_DESC	Vehicle Body Type Description	VARCHAR2(60)	This value represents the description of the vehicle body type.
Warehouse	PA_VEH	VEH_CLASS_CD	Vehicle Class Code	VARCHAR2(25)	This value represents the classification that describes vehicle size and body type.
Warehouse	PA_VEH	VEH_CLASS_DESC	Vehicle Class Description	VARCHAR2(60)	This value describes the vehicle class.
Warehouse	PA_VEH	VEH_COST_NEW	Vehicle Cost New	NUMBER (14, 3)	This number represents the monetary price of vehicle when purchased as a new vehicle.
Warehouse	PA_VEH	VEH_CUR_VAL	Vehicle Current Value	NUMBER (14, 3)	This number represents the current monetary value of the personal vehicle in marketplace.
Warehouse	PA_VEH	VEH_GROSS_WT	Vehicle Gross Weight	NUMBER (14, 3)	This number represents the total weight a vehicle is designed to carry and includes the net weight of the vehicle, plus the weight of passengers, fuel, cargo and any additional accessories.
Warehouse	PA_VEH	VEH_MFR	Vehicle Manufacturer	VARCHAR2(20)	This value represents the name of manufacturer that created the personal vehicle.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PA_VEH	VEH_MODEL	Vehicle Model	VARCHAR2(20)	This value represents the model name assigned by manufacturer of personal vehicle.
Warehouse	PA_VEH	VEH_NUM	Vehicle Number	NUMBER (22, 0)	This number is the system assigned number that identifies personal vehicle.
Warehouse	PA_VEH	VEH_PERF_CD	Vehicle Performance Code	VARCHAR2(25)	This system code identifies the performance level of the vehicle.
Warehouse	PA_VEH	VEH_PERF_DESC	Vehicle Performance Description	VARCHAR2(60)	This value describes the performance level of the vehicle.
Warehouse	PA_VEH	VEH_SYM_CD	Vehicle Symbol Code	VARCHAR2(25)	This system code is a cost symbol that represents a value in the personal vehicle.
Warehouse	PA_VEH	VEH_SYM_DESC	Vehicle Symbol Description	VARCHAR2(60)	This value describes the personal vehicle symbol.
Warehouse	PA_VEH	VEH_USE_CD	Vehicle Use Code	VARCHAR2(25)	This system code identifies the primary use of the vehicle.
Warehouse	PA_VEH	VEH_USE_DESC	Vehicle Use Description	VARCHAR2(60)	This value describes the primary use of the vehicle.
Warehouse	PA_VEH	VEH_YR	Vehicle Year	CHAR(4)	This value represents the model year assigned by vehicle manufacturer.
Warehouse	PA_VEH	VIN	Vehicle Identification Number	VARCHAR2(25)	This value represents the vehicle identification number assigned by the manufacturer of the personal vehicle at risk.
Warehouse	PARTY	GOVT_ID_NUM	Government Identification Number	CHAR(9)	This value represents the government-issued identifier issued to the party. For example, in the USA: SSN or FEIN.
Warehouse	PARTY	PARTY_ID	Party Identifier	NUMBER (22, 0)	This system generated number identifies the party.
Warehouse	PARTY	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	PARTY	PARTY_UDF_CD_1	Party User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first party user defined field.
Warehouse	PARTY	PARTY_UDF_CD_2	Party User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second party user defined field.
Warehouse	PARTY	PARTY_UDF_CD_3	Party User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third party user defined field.
Warehouse	PARTY	PARTY_UDF_CD_4	Party User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth party user defined field.
Warehouse	PARTY	PARTY_UDF_CD_5	Party User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth party user defined field.
Warehouse	PARTY	PARTY_UDF_DESC_1	Party User Defined Field Description 1	VARCHAR2(60)	This value describes the first party user defined field.
Warehouse	PARTY	PARTY_UDF_DESC_2	Party User Defined Field Description 2	VARCHAR2(60)	This value describes the second party user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PARTY	PARTY_UDF_DESC_3	Party User Defined Field Description 3	VARCHAR2(60)	This value describes the third party user defined field.
Warehouse	PARTY	PARTY_UDF_DESC_4	Party User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth party user defined field.
Warehouse	PARTY	PARTY_UDF_DESC_5	Party User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth party user defined field.
Warehouse	PARTY_ROLE	PARTY_ROLE_CD	Party Role Code	VARCHAR2(25)	This system code identifies the party role.
Warehouse	PARTY_ROLE	PARTY_ROLE_DESC	Party Role Description	VARCHAR2(60)	This value describes party role.
Warehouse	PARTY_ROLE	PARTY_ROLE_ID	Party Role Identifier	NUMBER (22, 0)	This system generated number identifies the party role instance.
Warehouse	PARTY_TO_CNTCT	BEGIN_DT	Begin Date	DATE	This calendar date represents when the party to contact applies.
Warehouse	PARTY_TO_CNTCT	CNTCT_ID	Contact Identifier	NUMBER (22, 0)	This system generated number identifies the contact instance.
Warehouse	PARTY_TO_CNTCT	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the party to contact is currently applicable.
Warehouse	PARTY_TO_CNTCT	END_DT	End Date	DATE	This calendar date represents when the party to contact is no longer valid.
Warehouse	PARTY_TO_CNTCT	PARTY_ID	Party Identifier	NUMBER (22, 0)	This system generated number identifies the party instance.
Warehouse	PARTY_TO_CNTCT	PARTY_TO_CNTCT_ID	Party To Contract Identifier	NUMBER (22, 0)	This system generated number identifies the party to contact instance.
Warehouse	PARTY_TO_CNTCT	PARTY_TO_CNTCT_NAT_KEY	Party To Contact Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party to contact.
Warehouse	PARTY_TO_PARTY	BEGIN_DT	Begin Date	DATE	This calendar date represents when the party to party applies.
Warehouse	PARTY_TO_PARTY	CHILD_PARTY_ID	Child Party Identifier	NUMBER (22, 0)	This system generated number identifies the child party instance.
Warehouse	PARTY_TO_PARTY	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the party to party is currently applicable.
Warehouse	PARTY_TO_PARTY	END_DT	End Date	DATE	This calendar date represents when the party to party longer applies.
Warehouse	PARTY_TO_PARTY	PARENT_PARTY_ID	Parent Party Identifier	NUMBER (22, 0)	This system generated number identifies the parent party instance.
Warehouse	PARTY_TO_PARTY	PARTY_TO_PARTY_ID	Party To Party Identifier	NUMBER (22, 0)	This system generated number identifies the party to party instance.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PARTY_TO_PARTY	PARTY_TO_PARTY_NAT_KEY	Party To Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party to party.
Warehouse	PARTY_TO_PARTY	PARTY_TO_PARTY_TYP_CD	Party To Party Type Code	VARCHAR2(25)	This system code identifies the party to party type.
Warehouse	PARTY_TO_PARTY	PARTY_TO_PARTY_TYP_DESC	Party To Party Type Description	VARCHAR2(60)	This value describes the party to party type.
Warehouse	PARTY_TO_PARTY_ROLE	BEGIN_DT	Begin Date	DATE	This calendar date represents when the party to party role applies.
Warehouse	PARTY_TO_PARTY_ROLE	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the party to party role is currently applicable.
Warehouse	PARTY_TO_PARTY_ROLE	END_DT	End Date	DATE	This calendar date represents when the party to party role is no longer valid.
Warehouse	PARTY_TO_PARTY_ROLE	PARTY_ID	Party Identifier	NUMBER (22, 0)	This system generated number identifies the party instance.
Warehouse	PARTY_TO_PARTY_ROLE	PARTY_ROLE_ID	Party Role Identifier	NUMBER (22, 0)	This system generated number identifies the party role.
Warehouse	PARTY_TO_PARTY_ROLE	PARTY_TO_PARTY_ROLE_ID	Party To Party Role Identifier	NUMBER (22, 0)	This system generated number identifies the party to party role instance.
Warehouse	PARTY_TO_PARTY_ROLE	PARTY_TO_PARTY_ROLE_NAT_KEY	Party To Party Role Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party to party role.
Warehouse	PERS	BEGIN_DT	Begin Date	DATE	This calendar date represents when the insurance policy coverage applies to the person.
Warehouse	PERS	BIRTH_DT	Birth Date	DATE	This date represents the calendar date of birth of the person listed on an insurance policy.
Warehouse	PERS	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the person is currently applicable.
Warehouse	PERS	END_DT	End Date	DATE	This calendar date represents when the insurance policy coverage ends in the person.
Warehouse	PERS	FIRST_NM	First Name	VARCHAR2(50)	This value represents the first name of the person.
Warehouse	PERS	GENDER_CD	Gender Code	VARCHAR2(25)	This system code abbreviates the gender (male or female).
Warehouse	PERS	GENDER_DESC	Gender Description	VARCHAR2(60)	This value represents the full description of the gender (male or female).
Warehouse	PERS	LAST_NM	Last Name	VARCHAR2(50)	This value represents the last name of person.
Warehouse	PERS	MARITAL_STATUS_CD	Marital Status Code	VARCHAR2(25)	This system code identifies the present marital condition (single, married, divorced, widowed) of the person.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PERS	MARITAL_STATUS_DESC	Marital Status Description	VARCHAR2(60)	This value describes the present marital condition (single, married, divorced, widowed) of the claimant.
Warehouse	PERS	MIDDLE_NM	Middle Name	VARCHAR2(50)	This value represents the middle name of the person.
Warehouse	PERS	PARTY_ID	Party Identifier	NUMBER (22, 0)	This system generated number identifies the party instance.
Warehouse	PERS	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	PERS	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person instance.
Warehouse	PERS	PERS_UDF_CD_1	Person User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first person user defined field.
Warehouse	PERS	PERS_UDF_CD_2	Person User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second person user defined field.
Warehouse	PERS	PERS_UDF_CD_3	Person User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third person user defined field.
Warehouse	PERS	PERS_UDF_CD_4	Person User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth person user defined field.
Warehouse	PERS	PERS_UDF_CD_5	Person User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth person user defined field.
Warehouse	PERS	PERS_UDF_DESC_1	Person User Defined Field Description 1	VARCHAR2(60)	This value describes the first person user defined field.
Warehouse	PERS	PERS_UDF_DESC_2	Person User Defined Field Description 2	VARCHAR2(60)	This value describes the second person user defined field.
Warehouse	PERS	PERS_UDF_DESC_3	Person User Defined Field Description 3	VARCHAR2(60)	This value describes the third person user defined field.
Warehouse	PERS	PERS_UDF_DESC_4	Person User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth person user defined field.
Warehouse	PERS	PERS_UDF_DESC_5	Person User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth person user defined field.
Warehouse	PERS	PRES_EMPLMT_START_YR	Present Employment Start Year	CHAR(4)	This value represents the calendar year that the person began working for their current employer.
Warehouse	PERS	SUFFIX	Suffix	VARCHAR2(8)	This value represents the suffix after a surname to identify a person. Examples include Jr. and Sr.
Warehouse	PERS	TITLE	Title	VARCHAR2(8)	This value represents the title to precede the name which is not part of the actual name.
Warehouse	PLCY	ACTV_OR_CNCLD_CD	Active Or Canceled Code	VARCHAR2(25)	This system code describes whether this policy is active or canceled.
Warehouse	PLCY	ACTV_OR_CNCLD_DESC	Active Or Canceled Code Description	VARCHAR2(60)	This value describes active or canceled code.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PLCY	BEGIN_DT	Begin Date	DATE	This calendar date represents when the policy applies.
Warehouse	PLCY	CNCL_REASON_CD	Cancel Reason Code	VARCHAR2(25)	This system code describes the reason for a cancellation.
Warehouse	PLCY	CNCL_REASON_DESC	Cancel Reason Description	VARCHAR2(60)	This value describes the cancel reason.
Warehouse	PLCY	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the policy is currently applicable.
Warehouse	PLCY	END_DT	End Date	DATE	This calendar date represents when the policy is no longer valid.
Warehouse	PLCY	EXPO_BASIS_CD	Exposure Basis Code	VARCHAR2(25)	This value represents the exposure basis is the denomination in which the exposure units are expressed.
Warehouse	PLCY	EXPO_BASIS_DESC	Exposure Basis Description	VARCHAR2(60)	This value represents the description of exposure basis.
Warehouse	PLCY	MONOLINE_OR_PKG_CD	Monoline or Package Code	VARCHAR2(25)	This system code identifies if a policy is monoline or package.
Warehouse	PLCY	MONOLINE_OR_PKG_DESC	Monoline or Package Description	VARCHAR2(60)	This value describes the monoline or package type.
Warehouse	PLCY	NEW_OR_RENEWAL_CD	New or Renewal Code	VARCHAR2(25)	This value represents the indicator of whether this policy is a new policy or a renewal policy.
Warehouse	PLCY	NEW_OR_RENEWAL_DESC	New or Renewal Description	VARCHAR2(60)	This value describes the indicator of whether this policy is a new policy or a renewal policy.
Warehouse	PLCY	PKG_DSCNT_CD	Package Discount Code	VARCHAR2(25)	This system code indicates the presence or absence of a package discount.
Warehouse	PLCY	PKG_DSCNT_DESC	Package Discount Description	VARCHAR2(60)	This value describes the package discount.
Warehouse	PLCY	PKG_DSCNT_PCT	Package Discount Percentage	NUMBER (6, 3)	This number represents the percentage of premium waived when package discount applies.
Warehouse	PLCY	PKG_MOD_ASSIGNMENT_CD	Package Modification Assignment Code	VARCHAR2(25)	This system code indicates the package modification assignment.
Warehouse	PLCY	PKG_MOD_ASSIGNMENT_DESC	Package Modification Assignment Description	VARCHAR2(60)	This value describes the package modification assignment.
Warehouse	PLCY	PKG_MOD_FCT	Package Modification Factor	NUMBER (6, 3)	This number represents the percentage of premium waived as a result of packaging coverages.
Warehouse	PLCY	PLCY_CNCL_DT	Policy Cancellation Date	DATE	This calendar date represents when policy coverage ceased due to a cancellation.
Warehouse	PLCY	PLCY_EFF_DT	Policy Effective Date	DATE	This calendar date represents when policy coverage began.
Warehouse	PLCY	PLCY_EXPR_DT	Policy Expiration Date	DATE	This calendar date represents when the policy term ends.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PLCY	PLCY_ID	Policy Identifier	NUMBER (22, 0)	This system generated number identifies the policy instance.
Warehouse	PLCY	PLCY_NAT_KEY	Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the policy.
Warehouse	PLCY	PLCY_NUM	Policy Number	VARCHAR2(25)	This value represents a number or other identifier for a policy.
Warehouse	PLCY	PLCY_ORIG_INCPN_DT	Policy Original Inception Date	DATE	This calendar date represents when insured originally purchased insurance coverage with the insurance company.
Warehouse	PLCY	PLCY_TYP_CATG_CD	Policy Type Category Code	VARCHAR2(25)	This system code identifies the policy type category.
Warehouse	PLCY	PLCY_TYP_CATG_DESC	Policy Type Category Description	VARCHAR2(60)	This value describes an additional way to categorize policies.
Warehouse	PLCY	PLCY_TYP_CD	Policy Type Code	VARCHAR2(25)	This system code identifies the type of policy as it would normally be identified on a coverage level.
Warehouse	PLCY	PLCY_TYP_DESC	Policy Type Description	VARCHAR2(60)	This value describes the type of policy as it would normally be identified on a coverage level.
Warehouse	PLCY	PLCY_UDF_CD_1	Policy User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first policy user defined field.
Warehouse	PLCY	PLCY_UDF_CD_2	Policy User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second policy user defined field.
Warehouse	PLCY	PLCY_UDF_CD_3	Policy User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third policy user defined field.
Warehouse	PLCY	PLCY_UDF_CD_4	Policy User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth policy user defined field.
Warehouse	PLCY	PLCY_UDF_CD_5	Policy User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth policy user defined field.
Warehouse	PLCY	PLCY_UDF_DESC_1	Policy User Defined Field Description 1	VARCHAR2(60)	This value describes the first policy user defined field.
Warehouse	PLCY	PLCY_UDF_DESC_2	Policy User Defined Field Description 2	VARCHAR2(60)	This value describes the second policy user defined field.
Warehouse	PLCY	PLCY_UDF_DESC_3	Policy User Defined Field Description 3	VARCHAR2(60)	This value describes the third policy user defined field.
Warehouse	PLCY	PLCY_UDF_DESC_4	Policy User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth policy user defined field.
Warehouse	PLCY	PLCY_UDF_DESC_5	Policy User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth policy user defined field.
Warehouse	PLCY	PLCY_VERSION	Policy Version	VARCHAR2(4)	This value represents the number or other identifier used by the company to identify 'this' version of the policy.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PLCY	PREM_BASIS_CD	Premium Basis Code	VARCHAR2(25)	This system code identifies the type of rating scale used.
Warehouse	PLCY	PREM_BASIS_DESC	Premium Basis Description	VARCHAR2(60)	This value describes the type of rating scale used.
Warehouse	PLCY	RENEWAL_TERM	Renewal Term in Months	VARCHAR2(3)	This value represents the length of the renewal policy period (term) in months (006,012).
Warehouse	PLCY	SUPPORTING_BUS_DSCNT_PCT	Supporting Business Discount Percentage	NUMBER (6, 3)	This number represents the percent of discount for supporting business issued with the company.
Warehouse	PLCY	SUPPORTING_BUS_TYP_CD	Supporting Business Type Code	VARCHAR2(25)	This value represents the type of supporting business for which the policyholder received a discount.
Warehouse	PLCY	SUPPORTING_BUS_TYP_DESC	Supporting Business Type Description	VARCHAR2(60)	This value describes the Supporting business type.
Warehouse	PLCY_TRANS	BILL_ACCT_ID	Billing Account Identifier	NUMBER (22, 0)	This system generated number identifies the billing account instance.
Warehouse	PLCY_TRANS	BOOK_DT	Book Date	DATE	This date represents the calendar date the policy transaction is recorded into the company's books. Usually, this is the greater of the transaction date or the effective date.
Warehouse	PLCY_TRANS	CLASS_ID	Class Identifier	NUMBER (22, 0)	This system generated number identifies the class instance.
Warehouse	PLCY_TRANS	COMM_AMT	Commission Amount	NUMBER (14, 3)	This number represents the amount of commission to be paid for a transaction.
Warehouse	PLCY_TRANS	COMM_RATE	Commission Rate	NUMBER (6, 5)	This number represents the rate at which the policy commission is to be paid.
Warehouse	PLCY_TRANS	COVRG_EFF_DT	Coverage Effective Date	DATE	This date represents the calendar date of the policy coverage begins.
Warehouse	PLCY_TRANS	COVRG_EXPR_DT	Coverage Expiration Date	DATE	This date represents the calendar date of the policy coverage ends.
Warehouse	PLCY_TRANS	COVRG_ID	Coverage Identifier	NUMBER (22, 0)	This system generated number identifies coverage instance.
Warehouse	PLCY_TRANS	COVRG_STATUS_ID	Coverage Status Identifier	NUMBER (22, 0)	This system generated number identifies coverage status instance.
Warehouse	PLCY_TRANS	DC_ID	Distribution Channel Identifier	NUMBER (22, 0)	This system generated number identifies the distribution channel instance.
Warehouse	PLCY_TRANS	DED_AMT	Deductible Amount	NUMBER (14, 3)	This number represents the monetary amount portion of any claim that is not covered by the insurer.
Warehouse	PLCY_TRANS	DED_ID	Deductible Identifier	NUMBER (22, 0)	This system generated number identifies the deductible instance.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PLCY_TRANS	DIRECT_CEDED_ASSUMED_CD	Direct or Ceded or Assumed Code	VARCHAR2(25)	This system code identifies the transaction type as being direct, ceded, or assumed.
Warehouse	PLCY_TRANS	DIRECT_CEDED_ASSUMED_DESC	Direct or Ceded or Assumed Description	VARCHAR2(60)	This value describes a policy transaction that identifies if the risk is insured internally, transferred to a reinsurer, or assumed.
Warehouse	PLCY_TRANS	DOC_CURR_CD	Document Currency Code	VARCHAR2(25)	This system code identifies document currency.
Warehouse	PLCY_TRANS	GLOBAL_CURR_RATE_1	Global Currency Rate 1	NUMBER (22, 7)	This number represents the first global currency rate.
Warehouse	PLCY_TRANS	GLOBAL_CURR_RATE_2	Global Currency Rate 2	NUMBER (22, 7)	This number represents the second global currency rate.
Warehouse	PLCY_TRANS	GLOBAL_CURR_RATE_3	Global Currency Rate 3	NUMBER (22, 7)	This number represents the third global currency rate.
Warehouse	PLCY_TRANS	GRP_PRG_ID	Group Program Identifier	NUMBER (22, 0)	This system generated number identifies the group program instance.
Warehouse	PLCY_TRANS	LMT_ID	Limit Identifier	NUMBER (22, 0)	This system generated number identifies the limit instance.
Warehouse	PLCY_TRANS	LOB_ID	Line Of Business Identifier	NUMBER (22, 0)	This system generated number identifies the line of business instance.
Warehouse	PLCY_TRANS	LOCAL_CURR_RATE	Local Currency Rate	NUMBER (22, 7)	This number represents the local currency rate.
Warehouse	PLCY_TRANS	ONSET_OR_OFFSET_CD	Onset or Offset Code	VARCHAR2(25)	This value represents the indicator of onset or offset transactions.
Warehouse	PLCY_TRANS	ONSET_OR_OFFSET_DESC	Onset or Office Description	VARCHAR2(60)	This value describes onset or offset transaction.
Warehouse	PLCY_TRANS	ORIG_PREM_AMT	Original Premium Amount	NUMBER (14, 3)	This number represents the original premium in the term of coverage.
Warehouse	PLCY_TRANS	PLCY_ID	Policy Identifier	NUMBER (22, 0)	This system generated number identifies the policy instance.
Warehouse	PLCY_TRANS	PLCY_TRANS_AMT	Policy Transaction Amount	NUMBER (14, 3)	This number represents the amount of any transaction processed for a policy.
Warehouse	PLCY_TRANS	PLCY_TRANS_CATG_CD	Policy Transaction Category Code	VARCHAR2(25)	This system code groups like transactions for analysis.
Warehouse	PLCY_TRANS	PLCY_TRANS_CATG_DESC	Policy Transaction Category Description	VARCHAR2(60)	This value describes the code groups like transactions for analysis.
Warehouse	PLCY_TRANS	PLCY_TRANS_CD	Policy Transaction Code	VARCHAR2(25)	This system code identifies the policy transaction.
Warehouse	PLCY_TRANS	PLCY_TRANS_DESC	Policy Transaction Description	VARCHAR2(60)	This value describes the policy transaction.
Warehouse	PLCY_TRANS	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction instance.
Warehouse	PLCY_TRANS	PREM_OR_NON_PREM_CD	Premium or Non-Premium Code	VARCHAR2(25)	This system code describes if a policy transaction resulted in a change in the premium charged for an existing policy.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PLCY_TRANS	PREM_OR_NON_PREM_DESC	Premium or Non-Premium Description	VARCHAR2(60)	This value describes the premium or non-premium transaction.
Warehouse	PLCY_TRANS	REINS_CNTRCT_ID	Reinsurance Contract Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance contract instance.
Warehouse	PLCY_TRANS	SRC_SYS_PROC_DT	Source System Process Date	DATE	This calendar date represents when source system processed the policy transaction.
Warehouse	PLCY_TRANS	SYS_PLCY_TRANS_CD	System Policy Transaction Code	VARCHAR2(25)	This system code represents the system policy transaction for a policy transaction.
Warehouse	PLCY_TRANS	SYS_PLCY_TRANS_DESC	System Policy Transaction Description	VARCHAR2(60)	This value describes a system policy transaction.
Warehouse	PLCY_TRANS	SYS_PROC_DT	System Process Date	DATE	This calendar date represents when the system processed the policy transaction.
Warehouse	PLCY_TRANS	TRANS_EFF_DT	Transaction Effective Date	DATE	This calendar date represents when a policy transaction is effective.
Warehouse	PLCY_TRANS	WRTN_EXPO_AMT	Written Exposure Amount	NUMBER (14, 3)	This number represents the measure of the loss exposure assumed by the insurer.
Warehouse	PLCY_TRANS_TO_CA_VEH	CA_VEH_ID	Commercial Auto Vehicle Identifier	NUMBER (22, 0)	This system generated number identifies the commercial vehicle instance.
Warehouse	PLCY_TRANS_TO_CA_VEH	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction instance in the policy transaction to commercial vehicle.
Warehouse	PLCY_TRANS_TO_CP_BLDG	CP_BLDG_ID	Commercial Property Building Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling in the policy transaction to commercial property building.
Warehouse	PLCY_TRANS_TO_CP_BLDG	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction instance .
Warehouse	PLCY_TRANS_TO_DF_DWLNG	DF_DWLNG_ID	Dwelling Fire Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the dwelling instance .
Warehouse	PLCY_TRANS_TO_DF_DWLNG	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction instance .
Warehouse	PLCY_TRANS_TO_HO_DWLNG	HO_DWLNG_ID	Homeowners Dwelling Identifier	NUMBER (22, 0)	This system generated number identifies the homeowners dwelling instance.
Warehouse	PLCY_TRANS_TO_HO_DWLNG	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction instance.
Warehouse	PLCY_TRANS_TO_PA_VEH	PA_VEH_ID	Persona Auto Vehicle Identifier	NUMBER (22, 0)	This system generated number identifies the personal vehicle instance.
Warehouse	PLCY_TRANS_TO_PA_VEH	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction instance.
Warehouse	PLCY_TRANS_TO_PARTY	PARTY_ID	Party Identifier	NUMBER (22, 0)	This system generated number identifies the party instance.
Warehouse	PLCY_TRANS_TO_PARTY	PARTY_ROLE_ID	Party Role Identifier	NUMBER (22, 0)	This system generated number identifies the party role instance.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PLCY_TRANS_TO_PARTY	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction instance.
Warehouse	PLCY_TRANS_TO_PU_PLCY	PLCY_TRANS_ID	Policy Transaction Identifier	NUMBER (22, 0)	This system generated number identifies the policy transaction instance.
Warehouse	PLCY_TRANS_TO_PU_PLCY	PU_PLCY_ID	Personal Umbrella Policy Identifier	NUMBER (22, 0)	This system generated number identifies the personal umbrella policy instance.
Warehouse	PRODR	BEGIN_DT	Begin Date	DATE	This calendar date represents when the producer appointment begins.
Warehouse	PRODR	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the producer is currently applicable.
Warehouse	PRODR	END_DT	End Date	DATE	This calendar date represents when the producer is no longer valid.
Warehouse	PRODR	ORG_ID	Organization Identifier	NUMBER (22, 0)	This system generated number identifies the producer organization instance.
Warehouse	PRODR	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	PRODR	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person instance.
Warehouse	PRODR	PRODR_EFF_DT	Producer Effective Date	DATE	This date represents the calendar date the producer appointment begins.
Warehouse	PRODR	PRODR_ID	Producer Identifier	NUMBER (22, 0)	This system generated number identifies the producer instance.
Warehouse	PRODR	PRODR_NUM	Producer Number	VARCHAR2(10)	This value represents the number or other identifier assigned to the producer of the business.
Warehouse	PRODR	PRODR_TYP_CD	Producer Type Code	VARCHAR2(25)	This system code represents the producer type Standard code.
Warehouse	PRODR	PRODR_TYP_DESC	Producer Type Description	VARCHAR2(60)	This value describes the producer type.
Warehouse	PRODR	PRODR_UDF_CD_1	Producer User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first producer user defined field.
Warehouse	PRODR	PRODR_UDF_CD_2	Producer User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second producer user defined field.
Warehouse	PRODR	PRODR_UDF_CD_3	Producer User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third producer user defined field.
Warehouse	PRODR	PRODR_UDF_CD_4	Producer User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth producer user defined field.
Warehouse	PRODR	PRODR_UDF_CD_5	Producer User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth producer user defined field.
Warehouse	PRODR	PRODR_UDF_DESC_1	Producer User Defined Field Description 1	VARCHAR2(60)	This value describes the first producer user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PRODR	PRODR_UDF_DESC_2	Producer User Defined Field Description 2	VARCHAR2(60)	This value describes the second producer user defined field.
Warehouse	PRODR	PRODR_UDF_DESC_3	Producer User Defined Field Description 3	VARCHAR2(60)	This value describes the third producer user defined field.
Warehouse	PRODR	PRODR_UDF_DESC_4	Producer User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth producer user defined field.
Warehouse	PRODR	PRODR_UDF_DESC_5	Producer User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth producer user defined field.
Warehouse	PRODR	STATE_LIC_NUM	State License Number	VARCHAR2(10)	This value represents the license number of the producer as assigned by the state insurance department.
Warehouse	PSTL_ADDR	ADDR_1	Address Line 1	VARCHAR2(60)	This value represents the first line of the postal address.
Warehouse	PSTL_ADDR	ADDR_2	Address Line 2	VARCHAR2(60)	This value represents the second line of the postal address.
Warehouse	PSTL_ADDR	CNTCT_ID	Contact Identifier	NUMBER (22, 0)	This system generated number identifies the contact instance.
Warehouse	PSTL_ADDR	GEOG_BNDRY_ID	Geographic Boundary Identifier	NUMBER (22, 0)	This system generated number identifies the geographic boundary instance in the postal address.
Warehouse	PSTL_ADDR	PSTL_ADDR_ID	Postal Address Identifier	NUMBER (22, 0)	This system generated number identifies the postal address.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_CD_1	Postal Address User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first postal address user defined field.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_CD_2	Postal Address User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second postal address user defined field.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_CD_3	Postal Address User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third postal address user defined field.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_CD_4	Postal Address User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth postal address user defined field.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_CD_5	Postal Address User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth postal address user defined field.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_DESC_1	Postal Address User Defined Field Description 1	VARCHAR2(60)	This value describes the first postal address user defined field.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_DESC_2	Postal Address User Defined Field Description 2	VARCHAR2(60)	This value describes the second postal address user defined field.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_DESC_3	Postal Address User Defined Field Description 3	VARCHAR2(60)	This value describes the third postal address user defined field.
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_DESC_4	Postal Address User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth postal address user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PSTL_ADDR	PSTL_ADDR_UDF_DESC_5	Postal Address User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth postal address user defined field.
Warehouse	PU_PLCY	DF_INSUR_CO_NM	Dwelling Fire Insurance Company Name	VARCHAR2(170)	This value represents the name of insurance company that provides dwelling fire policy coverage for insured.
Warehouse	PU_PLCY	DF_PLCY_EFF_DT	Dwelling Fire Policy Effective Date	DATE	This date represents the calendar date dwelling fire policy coverage begins.
Warehouse	PU_PLCY	DF_PLCY_EXPR_DT	Dwelling Fire Expiration Date	DATE	This date represents the calendar date dwelling fire policy term ends.
Warehouse	PU_PLCY	DF_PLCY_NUM	Dwelling Fire Policy Number	VARCHAR2(25)	This value represents a number or other identifier for a dwelling fire policy owned by named insured.
Warehouse	PU_PLCY	DF_PSNL_LIAB_LMT	Dwelling Fire Personal Liability Limit	VARCHAR2(15)	This value represents the personal liability coverage limit provided by dwelling fire policy owned by insured.
Warehouse	PU_PLCY	HO_INSUR_CO_NM	Homeowners Insurance Company Name	VARCHAR2(170)	This value represents the insurance company name of the insured's homeowners policy.
Warehouse	PU_PLCY	HO_PLCY_EFF_DT	Homeowners Policy Effective Date	DATE	This date is when coverage begins for a homeowners policy.
Warehouse	PU_PLCY	HO_PLCY_EXPR_DT	Homeowners Policy Expiration Date	DATE	This calendar date represents when homeowners coverage policy term ends.
Warehouse	PU_PLCY	HO_PLCY_NUM	Homeowners Policy Number	VARCHAR2(25)	This value represents a number or other identifier for a homeowners policy.
Warehouse	PU_PLCY	HO_PSNL_LIAB_LMT	Homeowners Personal Liability Limit	VARCHAR2(15)	This value represents the personal liability limit included under an insured's homeowners insurance policy.
Warehouse	PU_PLCY	PA_INSUR_CO_NM	Personal Auto Insurance Company Name	VARCHAR2(170)	This value represents the insurance company name that issued the insured's personal automobile policy.
Warehouse	PU_PLCY	PA_LIAB_FIRST_LMT	Personal Auto Liability First Limit	VARCHAR2(15)	This value represents the personal vehicle liability limit first limit.
Warehouse	PU_PLCY	PA_LIAB_SECOND_LMT	Personal Auto Liability Second Limit	VARCHAR2(15)	This value represents the personal vehicle liability limit second limit.
Warehouse	PU_PLCY	PA_PLCY_EFF_DT	Personal Auto Policy Effective Date	DATE	This calendar date represents when insured's personal vehicle policy coverage began.
Warehouse	PU_PLCY	PA_PLCY_EXPR_DT	Personal Auto Policy Expiration Date	DATE	This calendar date represents when insured's personal vehicle policy term ends.
Warehouse	PU_PLCY	PA_PLCY_NUM	Personal Auto Policy Number	VARCHAR2(25)	This value represents the personal vehicle policy number.
Warehouse	PU_PLCY	PA_PROP_DMG_LMT	Personal Auto Property Damage Limit	VARCHAR2(15)	This value represents the personal vehicle property damage limit.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	PU_PLCY	PA_UM_FIRST_LMT	Personal Auto Uninsured Motorist First Limit	VARCHAR2(15)	This value represents the personal vehicle uninsured/underinsured motorist first limit.
Warehouse	PU_PLCY	PA_UM_SECOND_LMT	Personal Auto Uninsured Motorist Second Limit	VARCHAR2(15)	This value represents the personal vehicle uninsured/underinsured motorist second limit.
Warehouse	PU_PLCY	PA_UM_THIRD_LMT	Personal Auto Uninsured Motorist Third Limit	VARCHAR2(15)	This value represents the personal vehicle uninsured/underinsured motorist third limit.
Warehouse	PU_PLCY	PU_PLCY_ID	Personal Umbrella Policy Identifier	NUMBER (22, 0)	This system generated number identifies the personal umbrella policy instance.
Warehouse	PU_PLCY	PU_PLCY_NAT_KEY	Personal Umbrella Policy Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the personal umbrella policy.
Warehouse	PU_PLCY	PU_PLCY_UDF_CD_1	Personal Umbrella Policy User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_CD_2	Personal Umbrella Policy User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_CD_3	Personal Umbrella Policy User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_CD_4	Personal Umbrella Policy User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_CD_5	Personal Umbrella Policy User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_DESC_1	Personal Umbrella Policy User Defined Field Description 1	VARCHAR2(60)	This value describes the first personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_DESC_2	Personal Umbrella Policy User Defined Field Description 2	VARCHAR2(60)	This value describes the second personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_DESC_3	Personal Umbrella Policy User Defined Field Description 3	VARCHAR2(60)	This value describes the third personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_DESC_4	Personal Umbrella Policy User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth personal umbrella policy user defined field.
Warehouse	PU_PLCY	PU_PLCY_UDF_DESC_5	Personal Umbrella Policy User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth personal umbrella policy user defined field.
Warehouse	REINS_CNTRCT	BEGIN_DT	Begin Date	DATE	This calendar date represents when the reinsurance contract terms apply.
Warehouse	REINS_CNTRCT	CEDED_LOSS_RATIO	Ceded Loss Ratio	NUMBER (6, 3)	This value represents the ratio of losses and loss adjustment expenses incurred to premiums earned for the portion of exposure that is transferred to a reinsurance company.
Warehouse	REINS_CNTRCT	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the reinsurance contract is currently applicable.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	REINS_CNTRCT	END_DT	End Date	DATE	This calendar date represents when the reinsurance contract terms no longer apply.
Warehouse	REINS_CNTRCT	FAC_COMM_PCT	Faculative Commission Percentage	NUMBER (6, 3)	This number represents the percentage of premium the ceding company retains as a commission from the reinsurer.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_BEGIN_DT	Reinsurance Contract Begin Date	DATE	This calendar date represents when reinsurance contract terms apply.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_CATG_CD	Reinsurance Contract Category Code	VARCHAR2(25)	This system code identifies the reinsurance contract category.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_CATG_DESC	Reinsurance Contract Category Description	VARCHAR2(60)	This value describes the reinsurance contract category.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_CERT_NUM	Reinsurance Contract Certificate Number	VARCHAR2(8)	This value represents the unique number or other identifier assigned to the reinsurance contract certificate.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_CESSION_NUM	Reinsurance Contract Cession Number	VARCHAR2(10)	This value represents a number or other identifier of the reinsurance contract cession.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_END_DT	Reinsurance Contract Ending Date	DATE	This date represents the calendar date reinsurance contract ends.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_ID	Reinsurance Contract Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance contract instance.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_LAYER_CD	Reinsurance Contract Layer Code	VARCHAR2(25)	This system code identifies the reinsurance contract layer.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_LAYER_DESC	Reinsurance Contract Layer Description	VARCHAR2(60)	This value describes the reinsurance contract layer.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_NAT_KEY	Reinsurance Contract Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the reinsurance contract.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_TREATY_NUM	Reinsurance Contract Treaty Number	VARCHAR2(8)	This value represents the number or other identifier assigned to the reinsurance contract treaty.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_TYP_CD	Reinsurance Contract Type Code	VARCHAR2(25)	This system code identifies the reinsurance contract type.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_TYP_DESC	Reinsurance Contract Type Description	VARCHAR2(60)	This value describes the reinsurance contract type.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_1	Reinsurance Contract User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first reinsurance contract user defined field.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_2	Reinsurance Contract User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second reinsurance contract user defined field.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_3	Reinsurance Contract User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third reinsurance contract user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_4	Reinsurance Contract User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth reinsurance contract user defined field.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_CD_5	Reinsurance Contract User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth reinsurance contract user defined field.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_DESC_1	Reinsurance Contract User Defined Field Description 1	VARCHAR2(60)	This value describes the first reinsurance contract user defined field.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_DESC_2	Reinsurance Contract User Defined Field Description 2	VARCHAR2(60)	This value describes the second reinsurance contract user defined field.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_DESC_3	Reinsurance Contract User Defined Field Description 3	VARCHAR2(60)	This value describes the third reinsurance contract user defined field.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_DESC_4	Reinsurance Contract User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth reinsurance contract user defined field.
Warehouse	REINS_CNTRCT	REINS_CNTRCT_UDF_DESC_5	Reinsurance Contract User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth reinsurance contract user defined field.
Warehouse	REINS_CO	BEGIN_DT	Begin Date	DATE	This calendar date represents when the reinsurance company applies.
Warehouse	REINS_CO	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the reinsurance company is currently applicable.
Warehouse	REINS_CO	END_DT	End Date	DATE	This calendar date represents when the reinsurance company is no longer valid.
Warehouse	REINS_CO	ORG_ID	Organization Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance company organization instance.
Warehouse	REINS_CO	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	REINS_CO	REINS_CO_ID	Reinsurance Company Identifier	NUMBER (22, 0)	This system generated number identifies the reinsurance company instance.
Warehouse	REINS_CO	REINS_CO_NUM	Reinsurance Company Number	VARCHAR2(4)	This value represents the number or other identifier assigned to the reinsurance company.
Warehouse	REINS_CO	REINS_CO_TYP_CD	Reinsurance Company Type Code	VARCHAR2(25)	This system code identifies reinsurance company type.
Warehouse	REINS_CO	REINS_CO_TYP_DESC	Reinsurance Company Type Description	VARCHAR2(60)	This value describes the reinsurance company type.
Warehouse	REINS_CO	REINS_CO_UDF_CD_1	Reinsurance Company User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first reinsurance company user defined field.
Warehouse	REINS_CO	REINS_CO_UDF_CD_2	Reinsurance Company User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second reinsurance company user defined field.
Warehouse	REINS_CO	REINS_CO_UDF_CD_3	Reinsurance Company User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third reinsurance company user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	REINS_CO	REINS_CO_UDF_CD_4	Reinsurance Company User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth reinsurance company user defined field.
Warehouse	REINS_CO	REINS_CO_UDF_CD_5	Reinsurance Company User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth reinsurance company user defined field.
Warehouse	REINS_CO	REINS_CO_UDF_DESC_1	Reinsurance Company User Defined Field Description 1	VARCHAR2(60)	This value describes the first reinsurance company user defined field.
Warehouse	REINS_CO	REINS_CO_UDF_DESC_2	Reinsurance Company User Defined Field Description 2	VARCHAR2(60)	This value describes the second reinsurance company user defined field.
Warehouse	REINS_CO	REINS_CO_UDF_DESC_3	Reinsurance Company User Defined Field Description 3	VARCHAR2(60)	This value describes the third reinsurance company user defined field.
Warehouse	REINS_CO	REINS_CO_UDF_DESC_4	Reinsurance Company User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth reinsurance company user defined field.
Warehouse	REINS_CO	REINS_CO_UDF_DESC_5	Reinsurance Company User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth reinsurance company user defined field.
Warehouse	SUPPLIER	BEGIN_DT	Begin Date	DATE	This calendar date represents when the supplier applies.
Warehouse	SUPPLIER	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the supplier is currently applicable.
Warehouse	SUPPLIER	END_DT	End Date	DATE	This calendar date represents when the supplier is no longer valid.
Warehouse	SUPPLIER	ORG_ID	Organization Identifier	NUMBER (22, 0)	This system generated number identifies the supplier organization instance.
Warehouse	SUPPLIER	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	SUPPLIER	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person instance.
Warehouse	SUPPLIER	PREF_SUPPLIER_CD	Preferred Supplier Code	VARCHAR2(25)	This system code identifies if a supplier is a preferred supplier.
Warehouse	SUPPLIER	PREF_SUPPLIER_DESC	Preferred Supplier Description	VARCHAR2(60)	This value describes the preferred supplier attributes.
Warehouse	SUPPLIER	PREF_SUPPLIER_TYP_CD	Preferred Supplier Type Code	VARCHAR2(25)	This system code identifies preferred supplier type.
Warehouse	SUPPLIER	PREF_SUPPLIER_TYP_DESC	Preferred Supplier Type Description	VARCHAR2(60)	This value represents the description of preferred supplier type attributes.
Warehouse	SUPPLIER	SUPPLIER_CATG_CD	Supplier Category Code	VARCHAR2(25)	This system code represents supplier category.
Warehouse	SUPPLIER	SUPPLIER_CATG_DESC	Supplier Category Description	VARCHAR2(60)	This value describes the supplier category.
Warehouse	SUPPLIER	SUPPLIER_ID	Supplier Identifier	NUMBER (22, 0)	This system generated number identifies the supplier instance.
Warehouse	SUPPLIER	SUPPLIER_TYP_CD	Supplier Type Code	VARCHAR2(25)	This system code identifies supplier type.
Warehouse	SUPPLIER	SUPPLIER_TYP_DESC	Supplier Type Description	VARCHAR2(60)	This value describes the supplier type.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	SUPPLIER	SUPPLIER_UDF_CD_1	Supplier User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_CD_2	Supplier User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_CD_3	Supplier User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_CD_4	Supplier User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_CD_5	Supplier User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_DESC_1	Supplier User Defined Field Description 1	VARCHAR2(60)	This value describes the first supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_DESC_2	Supplier User Defined Field Description 2	VARCHAR2(60)	This value describes the second supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_DESC_3	Supplier User Defined Field Description 3	VARCHAR2(60)	This value describes the third supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_DESC_4	Supplier User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth supplier user defined field.
Warehouse	SUPPLIER	SUPPLIER_UDF_DESC_5	Supplier User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth supplier user defined field.
Warehouse	UW	BEGIN_DT	Begin Date	DATE	This calendar date represents when the underwriter applies.
Warehouse	UW	CUR_FLG	Current Flag	CHAR(1)	This value represents based on the yes/no indicator identifying if the underwriter is currently applicable.
Warehouse	UW	END_DT	End Date	DATE	This calendar date represents when the underwriter is no longer valid.
Warehouse	UW	PARTY_NAT_KEY	Party Natural Key	VARCHAR2(50)	This value represents based on one or more business attributes that identifies the party.
Warehouse	UW	PERS_ID	Person Identifier	NUMBER (22, 0)	This system generated number identifies the person.
Warehouse	UW	UW_ID	Underwriter Identifier	NUMBER (22, 0)	This system generated number identifies the underwriter instance.
Warehouse	UW	UW_NUM	Underwriter Number	VARCHAR2(25)	This value represents the number or other identifier that identifies the underwriter.
Warehouse	UW	UW_TYP_CD	Underwriter Type Code	VARCHAR2(25)	This system code identifies the underwriter type.
Warehouse	UW	UW_TYP_DESC	Underwriter Type Description	VARCHAR2(60)	This value describes the underwriter type.
Warehouse	UW	UW_UDF_CD_1	Underwriter User Defined Field Code 1	VARCHAR2(25)	This system code identifies the first underwriter user defined field.
Warehouse	UW	UW_UDF_CD_2	Underwriter User Defined Field Code 2	VARCHAR2(25)	This system code identifies the second underwriter user defined field.

Warehouse (Continued)

Source	Database Table Name	Database Column Name	Business Name	Data Type	Definition
Warehouse	UW	UW_UDF_CD_3	Underwriter User Defined Field Code 3	VARCHAR2(25)	This system code identifies the third underwriter user defined field.
Warehouse	UW	UW_UDF_CD_4	Underwriter User Defined Field Code 4	VARCHAR2(25)	This system code identifies the fourth underwriter user defined field.
Warehouse	UW	UW_UDF_CD_5	Underwriter User Defined Field Code 5	VARCHAR2(25)	This system code identifies the fifth underwriter user defined field.
Warehouse	UW	UW_UDF_DESC_1	Underwriter User Defined Field Description 1	VARCHAR2(60)	This value describes the first underwriter user defined field.
Warehouse	UW	UW_UDF_DESC_2	Underwriter User Defined Field Description 2	VARCHAR2(60)	This value describes the second underwriter user defined field.
Warehouse	UW	UW_UDF_DESC_3	Underwriter User Defined Field Description 3	VARCHAR2(60)	This value describes the third underwriter user defined field.
Warehouse	UW	UW_UDF_DESC_4	Underwriter User Defined Field Description 4	VARCHAR2(60)	This value describes the fourth underwriter user defined field.
Warehouse	UW	UW_UDF_DESC_5	Underwriter User Defined Field Description 5	VARCHAR2(60)	This value describes the fifth underwriter user defined field.